

$\langle Version \rangle \equiv$
2.1.1

$\langle Date \rangle \equiv$
September 18 2012

WHIZARD¹

Wolfgang Kilian,² Thorsten Ohl,³ Jürgen Reuter⁴ Christian Speckner⁵

Version 2.1.1, Sep 18 2012

¹The original meaning of the acronym is *W, Higgs, Z, And Respective Decays*. The current program is much more than that, however.

²e-mail: kilian@physik.uni-siegen.de

³e-mail: ohl@physik.uni-wuerzburg.de

⁴e-mail: juergen.reuter@desy.de

⁵e-mail: christian.speckner@physik.uni-freiburg.de

Abstract

WHIZARD is an application of the VAMP algorithm: Adaptive multi-channel integration and event generation. The bare VAMP library is augmented by modules for Lorentz algebra, particles, phase space, etc., such that physical processes with arbitrary complex final states [well, in principle. . .] can be integrated and *unweighted* events be generated.

Contents

1	Changes	13
2	Tools	14
2.1	Preliminaries	14
2.2	Parallelization	15
2.3	File utilities	16
2.3.1	Finding an I/O unit	16
2.3.2	String auxiliary functions	17
2.3.3	Formatting numbers	18
2.4	Operating-system interface	20
2.4.1	Path variables	20
2.4.2	System dependencies	21
2.4.3	Dynamic linking	26
2.4.4	Predicates	29
2.4.5	Shell access	30
2.4.6	Querying for a directory	30
2.4.7	Fortran compiler and linker	31
2.4.8	Controlling OpenMP	34
2.4.9	Test	35
2.5	CPU timing	36
2.6	Accessing the system clock	40
2.7	Hashtables	46
2.7.1	The hash function	47
2.7.2	The hash table	47
2.7.3	Hashtable insertion	49
2.7.4	Hashtable lookup	50
2.8	Message and signal handling	52
2.8.1	Logfile	61
2.8.2	Checking values	62
2.8.3	Signal handling	65
2.9	C wrapper for sigaction	68
2.10	C wrapper for printf	70
2.11	Interface for formatted I/O	71
2.11.1	Parsing a C format string	72
2.11.2	API	79
2.11.3	Test	79
2.12	Bytes and such	80
2.12.1	8-bit words: bytes	81

2.12.2	32-bit words	82
2.12.3	Operations on 32-bit words	85
2.12.4	64-bit words	86
2.13	MD5 Checksums	89
2.13.1	Blocks	89
2.13.2	Messages	91
2.13.3	Message I/O	93
2.13.4	Auxiliary functions	95
2.13.5	Auxiliary stuff	95
2.13.6	MD5 algorithm	96
2.13.7	User interface	99
2.14	Permutations	100
2.14.1	Permutations	101
2.14.2	Operations on binary codes	106
2.15	Sorting	107
2.15.1	Implementation	107
2.15.2	Concatenating arrays	109
2.15.3	Test	110
3	Text handling	112
3.1	Internal files	113
3.1.1	iostat codes	113
3.1.2	The line type	113
3.1.3	The ifile type	114
3.1.4	I/O on ifiles	115
3.1.5	Ifile tools	118
3.1.6	Line pointers	118
3.1.7	Access lines via pointers	119
3.2	Lexer	121
3.2.1	Input streams	122
3.2.2	Keyword list	125
3.2.3	Lexeme templates	127
3.2.4	The lexer setup	132
3.2.5	The lexeme type	135
3.2.6	The lexer object	138
3.2.7	The lexer routine	139
3.2.8	Diagnostics	142
3.3	Syntax rules	144
3.3.1	Syntax rules	144
3.3.2	I/O	147
3.3.3	Completing syntax rules	149
3.3.4	Accessing rules	151
3.3.5	Syntax tables	153
3.3.6	Accessing the syntax table	159
3.3.7	I/O	160
3.4	The parser	162
3.4.1	The token type	162
3.4.2	Retrieve token contents	166
3.4.3	The parse tree: nodes	168
3.4.4	Filling nodes	170

3.4.5	Accessing nodes	172
3.4.6	The parse tree	176
3.4.7	Access the parser	182
3.4.8	Tools	182
3.4.9	Applications	183
3.4.10	Test the parser	184
4	Physics library	187
4.1	C-compatible Particle Type	188
4.2	Lorentz algebra	190
4.2.1	Three-vectors	190
4.2.2	Four-vectors	196
4.2.3	Conversions	201
4.2.4	Angles	204
4.2.5	More kinematical functions (some redundant)	209
4.2.6	Lorentz transformations	213
4.2.7	Functions of Lorentz transformations	214
4.2.8	Invariants	215
4.2.9	Boosts	216
4.2.10	Rotations	217
4.2.11	Composite Lorentz transformations	220
4.2.12	Applying Lorentz transformations	220
4.2.13	Special Lorentz transformations	221
4.2.14	Special functions	223
4.3	Special Physics functions	225
4.3.1	Functions for Catani-Seymour dipoles	232
4.3.2	Distributions for integrated dipoles and such	234
5	Physics Analysis	244
5.1	Analysis tools	245
5.1.1	Output formats	245
5.1.2	Graph options	246
5.1.3	Drawing options	250
5.1.4	Observables	254
5.1.5	Output	257
5.1.6	Histograms	259
5.1.7	Plots	269
5.1.8	Graphs	275
5.1.9	Analysis objects	281
5.1.10	Analysis object iterator	287
5.1.11	Analysis store	290
5.1.12	L ^A T _E X driver file	292
5.1.13	API	294
5.1.14	Test	302
5.2	PDG arrays	304
5.2.1	Type definition	304
5.2.2	Parameters	305
5.2.3	Basic operations	305
5.2.4	Matching	306
5.3	subevents	308

5.3.1	Particles	308
5.3.2	C-compatible particle type	315
5.3.3	subevents	316
5.4	User Code Interface	326
5.4.1	User Code Management	327
5.4.2	Libmanager interface	330
5.4.3	Interfaces for user-defined functions	330
5.4.4	Interfaces for user-defined interactions	332
5.5	Variables	334
5.5.1	Variable list entries	335
5.5.2	Setting values	349
5.5.3	Copies and pointer variables	353
5.5.4	Variable lists	355
5.5.5	Tools	364
5.5.6	Process-specific variables	371
5.5.7	Observable initialization	373
5.5.8	Observables	376
5.5.9	Event variables	381
5.5.10	API for variable lists	384
5.5.11	Linking model variables	388
5.6	Expressions	395
5.6.1	Tree nodes	396
5.6.2	Operation types	412
5.6.3	Specific operators	417
5.6.4	Compiling the parse tree	441
5.6.5	Auxiliary functions for the compiler	502
5.6.6	Evaluation	503
5.6.7	Evaluation syntax	510
5.6.8	Set up appropriate parse trees	519
5.6.9	The evaluation tree	521
5.6.10	Direct evaluation	530
5.6.11	Test	534
6	Physics Models	538
6.1	Model module	538
6.1.1	Physics Parameters	539
6.1.2	Particle codes	541
6.1.3	Spin codes	542
6.1.4	Particle data	542
6.1.5	Vertex data	553
6.1.6	Vertex lookup table	554
6.1.7	Model data	558
6.1.8	Reading models from file	569
6.1.9	Model list	579
6.1.10	Test	582

7	Quantum Numbers	584
7.1	Helicities	585
7.1.1	Helicity types	585
7.1.2	Predicates	588
7.1.3	Accessing contents	589
7.1.4	Comparisons	589
7.1.5	Tools	591
7.2	Colors	592
7.2.1	The color type	592
7.2.2	Predicates	597
7.2.3	Accessing contents	599
7.2.4	Comparisons	600
7.2.5	Tools	602
7.2.6	Color counting test	611
7.2.7	The Madgraph color model	612
7.3	Flavors: Particle properties	616
7.3.1	The flavor type	616
7.4	Quantum numbers	631
7.4.1	The quantum number type	631
7.4.2	I/O	634
7.4.3	Accessing contents	636
7.4.4	Predicates	638
7.4.5	Comparisons	639
7.4.6	Operations	642
7.4.7	The quantum number mask	645
7.4.8	Setting mask components	646
7.4.9	Mask predicates	648
7.4.10	Operators	648
7.4.11	Mask comparisons	648
7.4.12	Apply a mask	649
7.5	State matrices	652
7.5.1	Nodes of the quantum state trie	652
7.5.2	State matrix	657
7.5.3	State iterators	666
7.5.4	Operations on quantum states	673
7.5.5	Factorization	678
7.5.6	Test	681
7.6	Interactions	684
7.6.1	External interaction links	685
7.6.2	Internal relations	687
7.6.3	The interaction type	689
7.6.4	Methods inherited from the state matrix member	695
7.6.5	Accessing contents	700
7.6.6	Modifying contents	707
7.6.7	Handling Linked interactions	709
7.6.8	Recovering connections	713
7.6.9	Test	715
7.7	Matrix element evaluation	716
7.7.1	Array of pairings	717
7.7.2	The evaluator type	718

7.7.3	Auxiliary structures for evaluator creation	720
7.7.4	Creating an evaluator: Matrix multiplication	729
7.7.5	Creating an evaluator: square	740
7.7.6	Accessing contents	755
7.7.7	Inherited procedures	755
7.7.8	Deleting the evaluator	759
7.7.9	Evaluation	760
7.7.10	Test	760
8	Particles	764
8.1	Polarization	764
8.1.1	The polarization type	765
8.1.2	Basic initializer and finalizer	765
8.1.3	I/O	766
8.1.4	Accessing contents	767
8.1.5	Initialization from state matrix	768
8.1.6	Specific initializers	769
8.1.7	Operations	776
8.1.8	Test	778
8.2	Event formats	779
8.2.1	Les Houches Event File: header/footer	780
8.2.2	The HEPRUP common block	781
8.2.3	Run parameter output (verbose)	783
8.2.4	Run parameter output (other formats)	784
8.2.5	The HEPEUP And HEPEVT common block	784
8.2.6	Event output	791
8.2.7	Event output in various formats	794
8.3	HepMC events	796
8.3.1	Interface check	796
8.3.2	FourVector	797
8.3.3	Polarization	799
8.3.4	GenParticle	802
8.3.5	GenVertex	809
8.3.6	Vertex-particle-in iterator	811
8.3.7	Vertex-particle-out iterator	814
8.3.8	GenEvent	816
8.3.9	Event-particle iterator	824
8.3.10	I/O streams	826
8.3.11	Test	828
8.4	Particles	831
8.4.1	The particle type	832
8.4.2	Particle sets	842
8.4.3	I/O formats	846
8.4.4	Expression interface	861
8.4.5	Test	862

9	Initial State	866
9.1	Beams for collisions and decays	866
9.1.1	Beam data	867
9.1.2	Initializers: collisions	871
9.1.3	Initializers: decays	873
9.1.4	Data access	873
9.1.5	Sanity check	874
9.1.6	The beams type	874
9.1.7	Inherited procedures	876
9.1.8	Accessing contents	877
9.1.9	Test	877
10	Spectra and structure functions	879
10.1	Tools	879
10.1.1	Momentum splitting	880
10.1.2	Mass-shell projection	885
10.2	Photon radiation: ISR	886
10.2.1	Physics	886
10.2.2	Implementation	888
10.2.3	The ISR data block	889
10.2.4	The ISR object	891
10.2.5	ISR structure function	892
10.2.6	ISR application	893
10.3	EPA	895
10.3.1	Physics	895
10.3.2	The EPA data block	896
10.3.3	The EPA object	898
10.3.4	EPA structure function	899
10.3.5	EPA application	900
10.4	EWA	902
10.4.1	Physics	902
10.4.2	The EWA data block	903
10.4.3	The EWA object	906
10.4.4	EWA structure function	908
10.4.5	EWA application	910
10.5	Lepton collider beamstrahlung: CIRCE1	912
10.5.1	Physics	912
10.5.2	The CIRCE1 data block	913
10.5.3	The CIRCE1 object	915
10.5.4	CIRCE1 structure function	917
10.5.5	CIRCE1 application	922
10.6	Photon collider: CIRCE2	923
10.6.1	Physics	923
10.6.2	The CIRCE2 data block	923
10.6.3	The CIRCE2 object	926
10.6.4	CIRCE2 structure function	927
10.6.5	CIRCE2 application	929
10.7	Energy-scan spectrum	932
10.7.1	Data type	933
10.7.2	The Energy-scan object	934

10.7.3	Energy-scan structure function	935
10.7.4	Energy scan application	935
10.8	Using beam event data	936
10.8.1	Data type	937
10.8.2	The Energy-scan object	938
10.8.3	Beam-event file structure function	940
10.8.4	Energy scan application	940
10.9	LHAPDF	942
10.9.1	The module	942
10.9.2	LHAPDF library interface	943
10.9.3	The LHAPDF status	944
10.9.4	LHAPDF initialization	945
10.9.5	The LHAPDF data block	946
10.9.6	The LHAPDF object	950
10.9.7	Structure function	951
10.10	Builtin PDF sets	953
10.10.1	The module	953
10.10.2	The data block	954
10.10.3	The PDF object	957
10.10.4	Structure function	958
10.11	User Plugin for Structure Functions	960
10.11.1	The module	960
10.11.2	The data block	961
10.11.3	The interaction	963
10.11.4	Structure function	964
10.12	Spectra and structure functions: wrapper	965
10.12.1	The structure functions type	966
10.12.2	Mappings	973
10.12.3	Structure function chains	977
10.12.4	Test	991
11	Partonic Events	995
12	Phase space and hard matrix elements	996
12.1	Mappings	997
12.1.1	Default parameters	997
12.1.2	The Mapping type	998
12.1.3	Screen output	999
12.1.4	Define a mapping	1000
12.1.5	Retrieve contents	1001
12.1.6	Compare mappings	1002
12.1.7	Mappings of the invariant mass	1003
12.1.8	Step mapping	1009
12.1.9	Mappings of the polar angle	1011
12.2	Phase-space trees	1015
12.2.1	Particles	1016
12.2.2	The phase-space tree type	1018
12.2.3	PHS tree setup	1022
12.2.4	Phase-space evaluation	1033
12.3	The phase-space forest	1042

12.3.1	Phase-space setup parameters	1043
12.3.2	Equivalences	1044
12.3.3	Groves	1047
12.3.4	The forest type	1049
12.3.5	Screen output	1051
12.3.6	Accessing contents	1054
12.3.7	Read the phase space setup from file	1056
12.3.8	Preparation	1061
12.3.9	Accessing the particle arrays	1063
12.3.10	Find equivalences among phase-space trees	1064
12.3.11	Interface for VAMP equivalences	1065
12.3.12	Phase-space evaluation	1067
12.3.13	Test of forest setup	1070
12.4	Finding phase space parameterizations	1072
12.4.1	The mapping modes	1073
12.4.2	The cascade type	1073
12.4.3	Creating new cascades	1080
12.4.4	Tools	1081
12.4.5	Hash entries for cascades	1082
12.4.6	The cascade set	1085
12.4.7	Adding cascades	1094
12.4.8	External particles	1096
12.4.9	Cascade combination I: flavor assignment	1099
12.4.10	Cascade combination II: kinematics setup and check . . .	1100
12.4.11	Cascade combination III: node connections and tree fusion	1105
12.4.12	Cascade set generation	1108
12.4.13	Groves	1111
12.4.14	Generate the phase space file	1112
12.4.15	Test	1115
13	Integration and event generation	1116
13.0.16	Process library interface	1116
13.1	Process library access	1121
13.1.1	Process methods	1121
13.1.2	Status codes	1121
13.1.3	Process configuration data	1122
13.1.4	Canonicalize particle names	1125
13.1.5	Process library data	1126
13.1.6	Accessing contents	1129
13.1.7	Creating a process library	1131
13.1.8	Interface file for the generated modules	1148
13.1.9	User code library access	1163
13.1.10	Library manager	1164
13.1.11	Collect model-specific libraries	1168
13.1.12	Compile and link a library	1169
13.1.13	Standalone executable	1170
13.1.14	Loading a library	1171
13.1.15	The library store	1175
13.1.16	Preloading static libraries	1177
13.1.17	Test	1177

13.2	Hard interactions	1179
13.2.1	The hard-interaction data type	1180
13.2.2	The hard-interaction type	1184
13.2.3	Access contents	1188
13.2.4	Evaluators	1192
13.2.5	Matrix-element evaluation	1194
13.2.6	Access results	1196
13.2.7	Reconstruction	1197
13.2.8	Process summary	1197
13.2.9	Test	1198
13.3	Processes	1199
13.3.1	Integration results	1200
13.3.2	Combined integration results	1207
13.3.3	Access results	1214
13.3.4	Results display	1217
13.3.5	Process status	1222
13.3.6	QCD parameters	1224
13.3.7	Grid parameters	1229
13.3.8	MD5 sum collection for grid files	1230
13.3.9	The process type	1231
13.3.10	Process pointers	1244
13.3.11	Accessing contents	1244
13.3.12	Setting values directly	1254
13.3.13	Process preparation: beams and structure functions	1255
13.3.14	Process preparation: phase space	1262
13.3.15	Process preparation: cuts, weight and scale	1267
13.3.16	Process preparation: VAMP grids	1270
13.3.17	Process preparation: Helicity selection counters	1270
13.3.18	Matrix element evaluation	1271
13.3.19	Access VAMP data	1278
13.3.20	Integration	1279
13.3.21	Event generation	1290
13.3.22	Results output	1294
13.3.23	Copies	1295
13.3.24	Process store	1300
13.3.25	Sampling function	1306
13.3.26	Test	1307
13.4	Decays	1316
13.4.1	Decay configuration	1317
13.4.2	List of decay configurations	1323
13.4.3	Decays	1326
13.4.4	Decay trees	1328
13.5	Events	1333
13.5.1	The event type	1334
13.5.2	Event generation	1336
13.5.3	Contents	1342
13.5.4	Binary I/O	1343
13.5.5	HepMC interface	1347
13.5.6	LHEF and HEPEVT interface	1349
13.5.7	Recovering events	1350

13.5.8	Factorization modes	1351
13.5.9	Test	1351
14	External modules	1354
14.1	STDHEP interface	1354
15	The SUSY Les Houches Accord	1356
15.0.1	Preprocessor	1357
15.0.2	Lexer and syntax	1358
15.0.3	Interpreter	1360
15.0.4	Auxiliary function	1366
15.0.5	Parser	1378
15.0.6	API	1379
15.0.7	Test	1380
16	Integration and simulation	1382
16.1	Iterations	1382
16.1.1	The iterations list	1383
16.1.2	Tools	1385
16.2	Beam polarization	1388
16.2.1	Parameters and type definition	1389
16.2.2	Constructors	1389
16.2.3	Tools	1391
16.3	Structure function configuration	1395
16.3.1	Structure function codes	1396
16.3.2	Mapping configuration	1397
16.3.3	Single structure function	1397
16.3.4	Structure function list	1404
16.3.5	Transfer to the process object	1408
16.3.6	The LHAPDF status	1410
16.4	User-controlled File I/O	1410
16.4.1	The file type	1411
16.4.2	The file list	1413
16.5	Runtime data	1416
16.5.1	The data type	1417
16.5.2	Initialization	1418
16.5.3	Local copies	1431
16.5.4	Finalization	1433
16.6	Compilation	1434
16.6.1	The data type	1434
16.6.2	API for compilation and loading	1437
16.7	Integration	1439
16.7.1	The integration type	1439
16.7.2	Initialization	1440
16.7.3	Integration	1449
16.7.4	API for integration objects	1454
16.8	Event files configuration	1461
16.8.1	Available formats	1462
16.8.2	Reading event files	1463
16.8.3	Output file specification and file list	1464

16.8.4	Checking filenames	1466
16.8.5	Handling output event files	1467
16.8.6	Additional tools	1472
16.9	Simulation	1473
16.9.1	Simulation parameters	1473
16.9.2	Screen updates during simulation	1477
16.9.3	The simulation object type	1478
17	Top level API	1501
17.1	Commands	1501
17.1.1	The command type	1502
17.1.2	Specific command types	1512
17.2	User-controlled output to data files	1589
17.2.1	Print default-formatted values	1592
17.2.2	Parameters: random-number generator seed	1610
17.2.3	The command list	1627
17.2.4	Compiling the parse tree	1627
17.2.5	Executing the command list	1628
17.2.6	Command list syntax	1628
17.2.7	Test	1636
17.3	Toplevel module WHIZARD	1637
17.3.1	Initialization and finalization	1638
17.3.2	Execute command lists	1642
17.3.3	The WHIZARD shell	1644
17.3.4	Self-tests	1645
17.4	Driver program	1646
17.5	Shower	1654
17.6	Whizard-C-Interface	1680
18	Cross References	1691
18.1	Identifiers	1691
18.2	Chunks	1691

Chapter 1

Changes

For a comprehensive list of changes confer the ChangeLog file or the subversion log.

Chapter 2

Tools

This part contains modules needed for auxiliary purposes:

limits Compile-time (integer) constants: fixed array sizes, input field lengths, and such. Any module that uses such constants has to access them via **limits**.

mpi90 Parallel execution (currently disabled!). This module contains dummy replacements for the message passing interface subroutines.

clock Store and handle dates and times

diagnostics Error and diagnostic message handling. Any messages and errors issued by WHIZARD functions are handled by the subroutines in this module, if possible.

files Files and auxiliary routines that do not belong anywhere else.

permutations Handle permutations of integers.

unix_args Parse the command-line arguments and options. This part is system-dependent, and we provide a replacement if the functions are not available.

2.1 Preliminaries

The WHIZARD file header:

```
<File header>≡
! WHIZARD <Version> <Date>
!
! Copyright (C) 1999-2012 by
!   Wolfgang Kilian <kilian@physik.uni-siegen.de>
!   Thorsten Ohl <ohl@physik.uni-wuerzburg.de>
!   Juergen Reuter <juergen.reuter@desy.de>
!   Christian Speckner <christian.speckner@physik.uni-freiburg.de>
!   with contributions by Sebastian Schmidt, Daniel Wiesler, Felix Braam
!
! WHIZARD is free software; you can redistribute it and/or modify it
! under the terms of the GNU General Public License as published by
! the Free Software Foundation; either version 2, or (at your option)
```

```

! any later version.
!
! WHIZARD is distributed in the hope that it will be useful, but
! WITHOUT ANY WARRANTY; without even the implied warranty of
! MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
! GNU General Public License for more details.
!
! You should have received a copy of the GNU General Public License
! along with this program; if not, write to the Free Software
! Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.
!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
! This file has been stripped of most comments. For documentation, refer
! to the source 'whizard.nw'

```

We are strict with our names:

```

<Standard module head>≡
    implicit none
    private

```

This is the way to invoke the kinds module (not contained in this source)

```

<Use kinds>≡
    use kinds, only: default !NODEP!

```

And we make heavy use of variable-length strings

```

<Use strings>≡
    use iso_varying_string, string_t => varying_string !NODEP!

```

Some parameters (buffer sizes etc.) are hardcoded. They are collected in this module:

```

<limits.f90>≡
    <File header>

    module limits

    use iso_fortran_env, only: iostat_end, iostat_eor !NODEP!
    <Standard module head>

    <Limits: public parameters>

    end module limits

```

The version string is used for checking files. Note that the string length MUST NOT be changed, because reading binary files relies on it.

```

<Limits: public parameters>≡
    integer, parameter, public :: VERSION_STRLEN = 255
    character(len=VERSION_STRLEN), parameter, public :: &
        & VERSION_STRING = "WHIZARD version <Version> (<Date>)"

```

2.2 Parallelization

This section has been removed, it was never used even in WHIZARD1. Parallelization should be reimplemented from scratch.

2.3 File utilities

This module provides miscellaneous tools associated with strings and files:

- Finding a free unit
- Selecting an output unit (stdout if undefined)
- Upper and lower case for strings
- Formatting a number for T_EX output.

```
<file_utils.f90>≡  
<File header>  
  
module file_utils  
  
    use iso_fortran_env, only: stdout => output_unit !NODEP!  
<Use kinds>  
<Use strings>  
    use limits, only: MIN_UNIT, MAX_UNIT !NODEP!  
  
<Standard module head>  
  
<File utils: public>  
  
<File utils: interfaces>  
  
contains  
  
<File utils: procedures>  
  
end module file_utils
```

2.3.1 Finding an I/O unit

Fortran 95 (even Fortran 2003) has no notion of implicit I/O units. Therefore, we have to find a free unit by trial and error.

```
<Limits: public parameters>+≡  
    integer, parameter, public :: MIN_UNIT = 11, MAX_UNIT = 99  
  
<File utils: public>≡  
    public :: free_unit  
  
<File utils: procedures>≡  
    function free_unit () result (unit)  
        integer :: unit  
        logical :: exists, is_open  
        integer :: i, status  
        do i = MIN_UNIT, MAX_UNIT  
            inquire (unit=i, exist=exists, opened=is_open, iostat=status)  
            if (status == 0) then  
                if (exists .and. .not. is_open) then  
                    unit = i; return  
                end if  
            end if  
        end do  
    end function free_unit
```

```

        end if
    end do
    unit = -1
end function free_unit

```

<Use file utils>≡
 use file_utils !NODEP!

Return the given unit, if present, otherwise the default STDOUT unit.

<File utils: public>+≡
 public :: output_unit

<File utils: procedures>+≡
 function output_unit (unit) result (u)
 integer, intent(in), optional :: unit
 integer :: u
 if (present (unit)) then
 u = unit
 else
 u = stdout
 end if
 end function output_unit

2.3.2 String auxiliary functions

These are, unfortunately, not part of Fortran.

<File utils: public>+≡
 public :: upper_case
 public :: lower_case

<File utils: interfaces>≡
 interface upper_case
 module procedure upper_case_char, upper_case_string
 end interface
 interface lower_case
 module procedure lower_case_char, lower_case_string
 end interface

<File utils: procedures>+≡
 function upper_case_char (string) result (new_string)
 character(*), intent(in) :: string
 character(len(string)) :: new_string
 integer :: pos, code
 integer, parameter :: offset = ichar('A')-ichar('a')
 do pos = 1, len (string)
 code = ichar (string(pos:pos))
 select case (code)
 case (ichar('a'):ichar('z'))
 new_string(pos:pos) = char (code + offset)
 case default
 new_string(pos:pos) = string(pos:pos)
 end select
 end do
 end function upper_case_char

```

function lower_case_char (string) result (new_string)
  character(*), intent(in) :: string
  character(len(string)) :: new_string
  integer :: pos, code
  integer, parameter :: offset = ichar('a')-ichar('A')
  do pos = 1, len (string)
    code = ichar (string(pos:pos))
    select case (code)
      case (ichar('A'):ichar('Z'))
        new_string(pos:pos) = char (code + offset)
      case default
        new_string(pos:pos) = string(pos:pos)
    end select
  end do
end function lower_case_char

function upper_case_string (string) result (new_string)
  type(string_t), intent(in) :: string
  type(string_t) :: new_string
  new_string = upper_case_char (char (string))
end function upper_case_string

function lower_case_string (string) result (new_string)
  type(string_t), intent(in) :: string
  type(string_t) :: new_string
  new_string = lower_case_char (char (string))
end function lower_case_string

```

Quote underscore characters for use in T_EX output.

```

<File utils: public>+≡
  public :: quote_underscore

<File utils: procedures>+≡
  function quote_underscore (string) result (quoted)
    type(string_t) :: quoted
    type(string_t), intent(in) :: string
    type(string_t) :: part
    type(string_t) :: buffer
    buffer = string
    quoted = ""
    do
      call split (part, buffer, "_")
      quoted = quoted // part
      if (buffer == "") exit
      quoted = quoted // "\"
    end do
  end function quote_underscore

```

2.3.3 Formatting numbers

Format a number with n significant digits for use in T_EX documents.

```

<File utils: public>+≡

```

```

public :: tex_format
<File utils: procedures>+≡
function tex_format (rval, n_digits) result (string)
  type(string_t) :: string
  real(default), intent(in) :: rval
  integer, intent(in) :: n_digits
  integer :: e, n, w, d
  real(default) :: absval
  real(default) :: mantissa
  character :: sign
  character(20) :: format
  character(80) :: cstr
  n = min (abs (n_digits), 16)
  if (rval == 0) then
    string = "0"
  else
    absval = abs (rval)
    e = log10 (absval)
    if (rval < 0) then
      sign = "-"
    else
      sign = ""
    end if
    select case (e)
    case (:-3)
      d = max (n - 1, 0)
      w = max (d + 2, 2)
      write (format, "('(F',IO,'.',IO,'A,IO,A)')") w, d
      mantissa = absval * 10._default ** (1 - e)
      write (cstr, fmt=format) mantissa, "\times 10^{", e - 1, "}"
    case (-2:0)
      d = max (n - e, 1 - e)
      w = max (d + e + 2, d + 2)
      write (format, "('(F',IO,'.',IO,')')") w, d
      write (cstr, fmt=format) absval
    case (1:2)
      d = max (n - e - 1, -e, 0)
      w = max (d + e + 2, d + 2, e + 2)
      write (format, "('(F',IO,'.',IO,')')") w, d
      write (cstr, fmt=format) absval
    case default
      d = max (n - 1, 0)
      w = max (d + 2, 2)
      write (format, "('(F',IO,'.',IO,'A,IO,A)')") w, d
      mantissa = absval * 10._default ** (- e)
      write (cstr, fmt=format) mantissa, "\times 10^{", e, "}"
    end select
    string = sign // trim (cstr)
  end if
end function tex_format

```

Write a number for use in Metapost code:

<File utils: public>+≡

```

    public :: mp_format
  <File utils: procedures>+=
    function mp_format (rval) result (string)
      type(string_t) :: string
      real(default), intent(in) :: rval
      character(16) :: tmp
      write (tmp, "(G16.8)")  rval
      string = lower_case (trim (adjustl (trim (tmp))))
    end function mp_format

```

2.4 Operating-system interface

For specific purposes, we need direct access to the OS (system calls). This is, of course, system dependent. The current version is valid for GNU/Linux; we expect to use a preprocessor for this module if different OSs are to be supported.

The current implementation lacks error handling.

```

<os_interface.f90>≡
  <File header>

  module os_interface

    use iso_c_binding !NODEP!
    <Use strings>
    <Use file utils>
    use system_dependencies !NODEP!
    use limits, only: DLERROR_LEN, ENVVAR_LEN !NODEP!
    use diagnostics !NODEP!

    <Standard module head>

    <OS interface: public>

    <OS interface: types>

    <OS interface: interfaces>

    contains

    <OS interface: procedures>

  end module os_interface

```

2.4.1 Path variables

This is a transparent container for storing user-defined path variables.

```

<OS interface: public>≡
  public :: paths_t

```

```

<OS interface: types>≡
  type :: paths_t
    type(string_t) :: prefix
    type(string_t) :: exec_prefix
    type(string_t) :: bindir
    type(string_t) :: libdir
    type(string_t) :: includedir
    type(string_t) :: datarootdir
    type(string_t) :: localprefix
    type(string_t) :: libtool
    type(string_t) :: lhapdfdir
  end type paths_t

<OS interface: public>+≡
  public :: paths_init

<OS interface: procedures>≡
  subroutine paths_init (paths)
    type(paths_t), intent(out) :: paths
    paths%prefix = ""
    paths%exec_prefix = ""
    paths%bindir = ""
    paths%libdir = ""
    paths%includedir = ""
    paths%datarootdir = ""
    paths%localprefix = ""
    paths%libtool = ""
    paths%lhapdfdir = ""
  end subroutine paths_init

```

2.4.2 System dependencies

We store all potentially system- and user/run-dependent data in a transparent container. This includes compiler/linker names and flags, file extensions, etc.

```

<OS interface: public>+≡
  public :: os_data_t

<OS interface: types>+≡
  type :: os_data_t
    logical :: use_libtool
    logical :: use_testfiles
    type(string_t) :: fc
    type(string_t) :: fcflags
    type(string_t) :: fcflags_pic
    type(string_t) :: fc_src_ext
    type(string_t) :: obj_ext
    type(string_t) :: ld
    type(string_t) :: ldflags
    type(string_t) :: ldflags_so
    type(string_t) :: ldflags_static
    type(string_t) :: ldflags_hepmc
    type(string_t) :: shlib_ext
    type(string_t) :: prefix

```



```

type(string_t) :: exec_prefix
type(string_t) :: bindir
type(string_t) :: libdir
type(string_t) :: includedir
type(string_t) :: datarootdir
type(string_t) :: whizard_omega_binpath
type(string_t) :: whizard_includes
type(string_t) :: whizard_ldflags
type(string_t) :: whizard_libtool
type(string_t) :: whizard_modelpath
type(string_t) :: whizard_models_libpath
type(string_t) :: whizard_susypath
type(string_t) :: whizard_gmlpath
type(string_t) :: whizard_cutspath
type(string_t) :: whizard_texpath
type(string_t) :: whizard_testdatapath
type(string_t) :: whizard_modelpath_local
type(string_t) :: whizard_models_libpath_local
type(string_t) :: whizard_omega_binpath_local
type(string_t) :: whizard_circe2path
type(string_t) :: whizard_beamsimpath
type(string_t) :: whizard_mulipath
type(string_t) :: pdf_builtin_datapath
logical :: event_analysis = .false.
logical :: event_analysis_ps = .false.
logical :: event_analysis_pdf = .false.
type(string_t) :: latex
type(string_t) :: mpost
type(string_t) :: gml
type(string_t) :: dvips
type(string_t) :: ps2pdf
end type os_data_t

```

Since all are allocatable strings, explicit initialization is necessary.

```

<Limits: public parameters>+≡
integer, parameter, public :: ENVVAR_LEN = 1000

<OS interface: public>+≡
public :: os_data_init

<OS interface: procedures>+≡
subroutine os_data_init (os_data, paths)
type(os_data_t), intent(out) :: os_data
type(paths_t), intent(in), optional :: paths
character(len=ENVVAR_LEN) :: home
type(string_t) :: localprefix, local_includes
os_data%use_libtool = .true.
inquire (file = "TESTFLAG", exist = os_data%use_testfiles)
call get_environment_variable ("HOME", home)
if(present(paths)) then
  if (paths%localprefix == "") then
    localprefix = trim (home) // "/.whizard"
  else
    localprefix = paths%localprefix
  end if
end if

```

```

else
    localprefix = trim (home) // "/.whizard"
end if
local_includes = localprefix // "/lib/whizard/mod/models"
os_data%whizard_modelpath_local = localprefix // "/share/whizard/models"
os_data%whizard_models_libpath_local = localprefix // "/lib/whizard/models"
os_data%whizard_omega_binpath_local = localprefix // "/bin"
os_data%fc = DEFAULT_FC
os_data%fcflags = DEFAULT_FCFLAGS
os_data%fcflags_pic = DEFAULT_FCFLAGS_PIC
os_data%fc_src_ext = DEFAULT_FC_SRC_EXT
os_data%obj_ext = DEFAULT_OBJ_EXT
os_data%ld = DEFAULT_LD
os_data%ldflags = DEFAULT_LDFLAGS
os_data%ldflags_so = DEFAULT_LDFLAGS_SO
os_data%ldflags_static = DEFAULT_LDFLAGS_STATIC
os_data%ldflags_hepmc = DEFAULT_LDFLAGS_HEPMC
os_data%shlib_ext = DEFAULT_SHLIB_EXT
os_data%prefix = PREFIX
os_data%exec_prefix = EXEC_PREFIX
os_data%bindir = BINDIR
os_data%libdir = LIBDIR
os_data%includedir = INCLUDEDIR
os_data%datarootdir = DATAROOTDIR
if (present (paths)) then
    if (paths%prefix /= "") os_data%prefix = paths%prefix
    if (paths%exec_prefix /= "") os_data%exec_prefix = paths%exec_prefix
    if (paths%bindir /= "") os_data%bindir = paths%bindir
    if (paths%libdir /= "") os_data%libdir = paths%libdir
    if (paths%includedir /= "") os_data%includedir = paths%includedir
    if (paths%datarootdir /= "") os_data%datarootdir = paths%datarootdir
end if
if (os_data%use_testfiles) then
    os_data%whizard_omega_binpath = WHIZARD_TEST_OMEGA_BINPATH
    os_data%whizard_includes = WHIZARD_TEST_INCLUDES
    os_data%whizard_ldflags = WHIZARD_TEST_LDFLAGS
    os_data%whizard_libtool = WHIZARD_LIBTOOL_TEST
    os_data%whizard_modelpath = WHIZARD_TEST_MODELPATH
    os_data%whizard_models_libpath = WHIZARD_TEST_MODELS_LIBPATH
    os_data%whizard_susypath = WHIZARD_TEST_SUSYPATH
    os_data%whizard_gmlpath = WHIZARD_TEST_GMLPATH
    os_data%whizard_cutspath = WHIZARD_TEST_CUTSPATH
    os_data%whizard_texpath = WHIZARD_TEST_TEXPATH
    os_data%whizard_testdatapath = WHIZARD_TEST_TESTDATAPATH
    os_data%whizard_circe2path = WHIZARD_TEST_CIRCE2PATH
    os_data%whizard_beamsimpath = WHIZARD_TEST_BEAMSIMPATH
    os_data%whizard_mulipath = WHIZARD_TEST_MULIPATH
    os_data%pdf_builtin_datapath = PDF_BUILTIN_TEST_DATAPATH
else
    if (os_dir_exist (local_includes)) then
        os_data%whizard_includes = "-I" // local_includes // " //" &
            WHIZARD_INCLUDES
    else
        os_data%whizard_includes = WHIZARD_INCLUDES
    end if
end if

```

```

end if
os_data%whizard_omega_binpath = WHIZARD_OMEGA_BINPATH
os_data%whizard_ldflags      = WHIZARD_LDFLAGS
os_data%whizard_libtool      = WHIZARD_LIBTOOL
if(present(paths)) then
    if (paths%libtool /= "") os_data%whizard_libtool = paths%libtool
end if
os_data%whizard_modelpath    = WHIZARD_MODELPATH
os_data%whizard_models_libpath = WHIZARD_MODELS_LIBPATH
os_data%whizard_susypath     = WHIZARD_SUSYPATH
os_data%whizard_gmlpath      = WHIZARD_GMLPATH
os_data%whizard_cutspath     = WHIZARD_CUTSPATH
os_data%whizard_texpath      = WHIZARD_TEXPATH
os_data%whizard_testdatapath = WHIZARD_TESTDATAPATH
os_data%whizard_circe2path   = WHIZARD_CIRCE2PATH
os_data%whizard_beamsimpath  = WHIZARD_BEAMSIMPATH
os_data%whizard_mulipath     = WHIZARD_MULIPATH
os_data%pdf_builtin_datapath = PDF_BUILTIN_DATAPATH
end if
os_data%event_analysis      = EVENT_ANALYSIS      == "yes"
os_data%event_analysis_ps   = EVENT_ANALYSIS_PS   == "yes"
os_data%event_analysis_pdf  = EVENT_ANALYSIS_PDF  == "yes"
os_data%latex               = PRG_LATEX // " " // OPT_LATEX
os_data%mpost               = PRG_MPOST // " " // OPT_MPOST
os_data%gml                 = os_data%whizard_gmlpath // "/gml" // " " // OPT_MPOST &
// " " // "--gml_dir " // os_data%whizard_gmlpath
os_data%dvips               = PRG_DVIPS
os_data%ps2pdf               = PRG_PS2PDF
call os_data_expand_paths (os_data)
end subroutine os_data_init

```

Replace occurrences of GNU path variables (such as ``${prefix}``) by their values. Do this for all strings that could depend on them, and do the replacement in reverse order, since the path variables may be defined in terms of each other.

(*OS interface: procedures*)+≡

```

subroutine os_data_expand_paths (os_data)
    type(os_data_t), intent(inout) :: os_data
    integer, parameter :: N_VARIABLES = 6
    type(string_t), dimension(N_VARIABLES) :: variable, value
    variable(1) = "`{prefix}`";      value(1) = os_data%prefix
    variable(2) = "`{exec_prefix}`"; value(2) = os_data%exec_prefix
    variable(3) = "`{bindir}`";      value(3) = os_data%bindir
    variable(4) = "`{libdir}`";      value(4) = os_data%libdir
    variable(5) = "`{includedir}`";  value(5) = os_data%includedir
    variable(6) = "`{datarootdir}`"; value(6) = os_data%datarootdir
    call expand_paths (os_data%whizard_omega_binpath)
    call expand_paths (os_data%whizard_includes)
    call expand_paths (os_data%whizard_ldflags)
    call expand_paths (os_data%whizard_libtool)
    call expand_paths (os_data%whizard_modelpath)
    call expand_paths (os_data%whizard_models_libpath)
    call expand_paths (os_data%whizard_susypath)
    call expand_paths (os_data%whizard_gmlpath)

```

```

call expand_paths (os_data%whizard_cutspath)
call expand_paths (os_data%whizard_texpath)
call expand_paths (os_data%whizard_testdatapath)
call expand_paths (os_data%whizard_circe2path)
call expand_paths (os_data%whizard_beamsimpath)
call expand_paths (os_data%whizard_mulipath)
call expand_paths (os_data%whizard_models_libpath_local)
call expand_paths (os_data%whizard_modelpath_local)
call expand_paths (os_data%whizard_omega_binpath_local)
call expand_paths (os_data%pdf_builtin_datapath)
call expand_paths (os_data%latex)
call expand_paths (os_data%mpost)
call expand_paths (os_data%gml)
call expand_paths (os_data%dvips)
call expand_paths (os_data%ps2pdf)
contains
subroutine expand_paths (string)
  type(string_t), intent(inout) :: string
  integer :: i
  do i = N_VARIABLES, 1, -1
    string = replace (string, variable(i), value(i), every=.true.)
  end do
end subroutine expand_paths
end subroutine os_data_expand_paths

```

Write contents

```

<OS interface: public>+≡
  public :: os_data_write

<OS interface: procedures>+≡
subroutine os_data_write (os_data, unit)
  type(os_data_t), intent(in) :: os_data
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, "(A)") "OS data:"
  write (u, *) "use_libtool" = ", os_data%use_libtool
  write (u, *) "use_testfiles" = ", os_data%use_testfiles
  write (u, *) "fc" = ", char (os_data%fc)
  write (u, *) "fcflags" = ", char (os_data%fcflags)
  write (u, *) "fcflags_pic" = ", char (os_data%fcflags_pic)
  write (u, *) "fc_src_ext" = ", char (os_data%fc_src_ext)
  write (u, *) "obj_ext" = ", char (os_data%obj_ext)
  write (u, *) "ld" = ", char (os_data%ld)
  write (u, *) "ldflags" = ", char (os_data%ldflags)
  write (u, *) "ldflags_so" = ", char (os_data%ldflags_so)
  write (u, *) "ldflags_static" = ", char (os_data%ldflags_static)
  write (u, *) "ldflags_hepmc" = ", char (os_data%ldflags_hepmc)
  write (u, *) "shlib_ext" = ", char (os_data%shlib_ext)
  write (u, *) "prefix" = ", char (os_data%prefix)
  write (u, *) "exec_prefix" = ", char (os_data%exec_prefix)
  write (u, *) "bindir" = ", char (os_data%bindir)
  write (u, *) "libdir" = ", char (os_data%libdir)
  write (u, *) "includedir" = ", char (os_data%includedir)

```

```

write (u, *) "datarootdir    = ", char (os_data%datarootdir)
write (u, *) "whizard_omega_binpath = ", &
    char (os_data%whizard_omega_binpath)
write (u, *) "whizard_includes    = ", char (os_data%whizard_includes)
write (u, *) "whizard_ldflags    = ", char (os_data%whizard_ldflags)
write (u, *) "whizard_libtool    = ", char (os_data%whizard_libtool)
write (u, *) "whizard_modelpath  = ", &
    char (os_data%whizard_modelpath)
write (u, *) "whizard_models_libpath = ", &
    char (os_data%whizard_modelpath)
write (u, *) "whizard_susypath    = ", char (os_data%whizard_susypath)
write (u, *) "whizard_gmlpath    = ", char (os_data%whizard_gmlpath)
write (u, *) "whizard_cutspath    = ", char (os_data%whizard_cutspath)
write (u, *) "whizard_texpath    = ", char (os_data%whizard_texpath)
write (u, *) "whizard_circe2path  = ", char (os_data%whizard_circe2path)
write (u, *) "whizard_beamsimpath = ", char (os_data%whizard_beamsimpath)
write (u, *) "whizard_mulipath    = ", char (os_data%whizard_mulipath)
write (u, *) "whizard_testdatapath = ", &
    char (os_data%whizard_testdatapath)
write (u, *) "whizard_modelpath_local = ", &
    char (os_data%whizard_modelpath_local)
write (u, *) "whizard_models_libpath_local = ", &
    char (os_data%whizard_models_libpath_local)
write (u, *) "whizard_omega_binpath_local = ", &
    char (os_data%whizard_omega_binpath_local)
write (u, *) "event_analysis    = ", os_data%event_analysis
write (u, *) "event_analysis_ps = ", os_data%event_analysis_ps
write (u, *) "event_analysis_pdf = ", os_data%event_analysis_pdf
write (u, *) "latex    = ", char (os_data%latex)
write (u, *) "mpost    = ", char (os_data%mpost)
write (u, *) "gml      = ", char (os_data%gml)
write (u, *) "dvips    = ", char (os_data%dvips)
write (u, *) "ps2pdf   = ", char (os_data%ps2pdf)
end subroutine os_data_write

```

2.4.3 Dynamic linking

We define a type that holds the filehandle for a dynamically linked library (shared object), together with functions to open and close the library, and to access functions in this library.

```

<OS interface: public>+≡
    public :: dlaccess_t

<OS interface: types>+≡
    type :: dlaccess_t
    private
    type(string_t) :: filename
    type(c_ptr) :: handle = c_null_ptr
    logical :: is_open = .false.
    logical :: has_error = .false.
    type(string_t) :: error
end type dlaccess_t

```

The interface to the library functions:

(OS interface: interfaces)≡

```

interface
  function dlopen (filename, flag) result (handle) bind(C)
  import
    character(c_char), dimension(*) :: filename
    integer(c_int), value :: flag
    type(c_ptr) :: handle
  end function dlopen
end interface

interface
  function dlclose (handle) result (status) bind(C)
  import
    type(c_ptr), value :: handle
    integer(c_int) :: status
  end function dlclose
end interface

interface
  function dlerror () result (str) bind(C)
  import
    type(c_ptr) :: str
  end function dlerror
end interface

interface
  function dlsym (handle, symbol) result (fptr) bind(C)
  import
    type(c_ptr), value :: handle
    character(c_char), dimension(*) :: symbol
    type(c_funptr) :: fptr
  end function dlsym
end interface

```

This reads an error string and transforms it into a `string_t` object, if an error has occurred. If not, set the error flag to false and return an empty string.

(Limits: public parameters)+≡

```
integer, parameter, public :: DLERROR_LEN = 160
```

(OS interface: procedures)+≡

```

subroutine read_dlerror (has_error, error)
  logical, intent(out) :: has_error
  type(string_t), intent(out) :: error
  type(c_ptr) :: err_cptr
  character(len=DLERROR_LEN, kind=c_char), pointer :: err_fptr
  integer :: str_end
  err_cptr = dlerror ()
  if (c_associated (err_cptr)) then
    call c_f_pointer (err_cptr, err_fptr)
    has_error = .true.
    str_end = scan (err_fptr, c_null_char)
    if (str_end > 0) then
      error = err_fptr(1:str_end-1)
    end if
  end if
end subroutine

```

```

        else
            error = err_fptr
        end if
    else
        has_error = .false.
        error = ""
    end if
end subroutine read_dlerror

```

This is the Fortran API. Init/final open and close the file, i.e., load and unload the library.

The flag with value 1 is defined as `RTLD_LAZY`, which means to resolve symbols only when they are used. The opposite would be `RTLD_NOW=2` (resolve everything immediately).

Note that a library can be opened more than once, and that for an ultimate close as many `dlclose` calls as `dlopen` calls are necessary. However, we assume that it is opened and closed only once.

```

<OS interface: public>+≡
    public :: dlaccess_init
    public :: dlaccess_final

<OS interface: procedures>+≡
    subroutine dlaccess_init (dlaccess, prefix, libname, os_data)
        type(dlaccess_t), intent(out) :: dlaccess
        type(string_t), intent(in) :: prefix, libname
        type(os_data_t), intent(in) :: os_data
        type(string_t) :: filename
        logical :: exist
        dlaccess%filename = libname
        filename = prefix // "/" // libname
        inquire (file=char(filename), exist=exist)
        if (.not. exist) then
            filename = prefix // "/.libs/" // libname
            inquire (file=char(filename), exist=exist)
            if (.not. exist) then
                dlaccess%has_error = .true.
                dlaccess%error = "Library '" // filename // "' not found"
                return
            end if
        end if
        dlaccess%handle = dlopen (char (filename) // c_null_char, 1_c_int)
        dlaccess%is_open = c_associated (dlaccess%handle)
        call read_dlerror (dlaccess%has_error, dlaccess%error)
    end subroutine dlaccess_init

    subroutine dlaccess_final (dlaccess)
        type(dlaccess_t), intent(inout) :: dlaccess
        integer(c_int) :: status
        if (dlaccess%is_open) then
            status = dlclose (dlaccess%handle)
            dlaccess%is_open = .false.
            call read_dlerror (dlaccess%has_error, dlaccess%error)
        end if
    end subroutine dlaccess_final

```

```
end subroutine dlaccess_final
```

Return true if an error has occurred.

```
<OS interface: public>+≡
  public :: dlaccess_has_error

<OS interface: procedures>+≡
  function dlaccess_has_error (dlaccess) result (flag)
    logical :: flag
    type(dlaccess_t), intent(in) :: dlaccess
    flag = dlaccess%has_error
  end function dlaccess_has_error
```

Return the error string currently stored in the dlaccess object.

```
<OS interface: public>+≡
  public :: dlaccess_get_error

<OS interface: procedures>+≡
  function dlaccess_get_error (dlaccess) result (error)
    type(string_t) :: error
    type(dlaccess_t), intent(in) :: dlaccess
    error = dlaccess%error
  end function dlaccess_get_error
```

The symbol handler returns the C address of the function with the given string name. (It is a good idea to use `bind(C)` for all functions accessed by this, such that the name string is well-defined.) Call `c_f_procpointer` to cast this into a Fortran procedure pointer with an appropriate interface.

```
<OS interface: public>+≡
  public :: dlaccess_get_c_funptr

<OS interface: procedures>+≡
  function dlaccess_get_c_funptr (dlaccess, fname) result (fptr)
    type(c_funptr) :: fptr
    type(dlaccess_t), intent(inout) :: dlaccess
    type(string_t), intent(in) :: fname
    fptr = dlsym (dlaccess%handle, char (fname) // c_null_char)
    call read_dlerror (dlaccess%has_error, dlaccess%error)
  end function dlaccess_get_c_funptr
```

2.4.4 Predicates

Return true if the library is loaded. In particular, this is false if loading was unsuccessful.

```
<OS interface: public>+≡
  public :: dlaccess_is_open

<OS interface: procedures>+≡
  function dlaccess_is_open (dlaccess) result (flag)
    logical :: flag
    type(dlaccess_t), intent(in) :: dlaccess
    flag = dlaccess%is_open
```



```
end function dlaccess_is_open
```

2.4.5 Shell access

This is the standard system call for executing a shell command, such as invoking a compiler.

In F2008 there will be the equivalent built-in command `execute_command_line`.

```
<OS interface: public>+≡
  public :: os_system_call

<OS interface: procedures>+≡
  subroutine os_system_call (command_string, status, verbose)
    type(string_t), intent(in) :: command_string
    integer, intent(out), optional :: status
    logical, intent(in), optional :: verbose
    logical :: verb
    integer :: stat
    verb = .false.; if (present (verbose)) verb = verbose
    if (verb) &
      call msg_message ("command: " // char (command_string))
    stat = system (char (command_string) // c_null_char)
    if (present (status)) then
      status = stat
    else if (stat /= 0) then
      if (.not. verb) &
        call msg_message ("command: " // char (command_string))
      write (msg_buffer, "(A,I0)") "Return code = ", stat
      call msg_message ()
      call msg_fatal ("System command returned with nonzero status code")
    end if
  end subroutine os_system_call

<OS interface: interfaces>+≡
  interface
    function system (command) result (status) bind(C)
      import
      integer(c_int) :: status
      character(c_char), dimension(*) :: command
    end function system
  end interface
```

2.4.6 Querying for a directory

This queries for the existence of a directory. There is no standard way to achieve this in FORTRAN, and if we were to call into `libc`, we would need access to C macros for evaluating the result, so we resort to calling `test` as a system call.

```
<OS interface: public>+≡
  public :: os_dir_exist
```

```

<OS interface: procedures>+≡
function os_dir_exist (name) result (res)
  type(string_t), intent(in) :: name
  logical :: res
  integer :: status
  call os_system_call ('test -d "' // name // '"', status=status)
  res = status == 0
end function os_dir_exist

```

2.4.7 Fortran compiler and linker

Compile a single module for use in a shared library, but without linking.

```

<OS interface: public>+≡
  public :: os_compile_shared

<OS interface: procedures>+≡
  subroutine os_compile_shared (src, os_data, status)
    type(string_t), intent(in) :: src
    type(os_data_t), intent(in) :: os_data
    integer, intent(out), optional :: status
    type(string_t) :: command_string
    if (os_data%use_libtool) then
      command_string = &
        os_data%whizard_libtool // " --mode=compile " // &
        os_data%fc // " " // &
        "-c " // &
        os_data%whizard_includes // " " // &
        os_data%fcflags // " " // &
        "' " // src // os_data%fc_src_ext // "' "
    else
      command_string = &
        os_data%fc // " " // &
        "-c " // &
        os_data%fcflags_pic // " " // &
        os_data%whizard_includes // " " // &
        os_data%fcflags // " " // &
        "' " // src // os_data%fc_src_ext // "' "
    end if
    call os_system_call (command_string, status)
  end subroutine os_compile_shared

```

Link an array of object files to build a shared object library. In the libtool case, we have to specify a `-rpath`, otherwise only a static library can be built. However, since the library is never installed, this `rpath` is irrelevant.

```

<OS interface: public>+≡
  public :: os_link_shared

<OS interface: procedures>+≡
  subroutine os_link_shared (objlist, lib, os_data, status)
    type(string_t), intent(in) :: objlist, lib
    type(os_data_t), intent(in) :: os_data
    integer, intent(out), optional :: status
    type(string_t) :: command_string

```

```

if (os_data%use_libtool) then
  command_string = &
    os_data%whizard_libtool // " --mode=link " // &
    os_data%fc // " " // &
    "-module " // &
    "-rpath /usr/local/lib" // " " // &
    os_data%fcflags // " " // &
    os_data%whizard_ldflags // " " // &
    os_data%ldflags // " " // &
    "-o '" // lib // ".la' " // &
    objlist
else
  command_string = &
    os_data%ld // " " // &
    os_data%ldflags_so // " " // &
    os_data%fcflags // " " // &
    os_data%whizard_ldflags // " " // &
    os_data%ldflags // " " // &
    "-o '" // lib // os_data%shlib_ext // "' " // &
    objlist
end if
call os_system_call (command_string, status)
end subroutine os_link_shared

```

Link an array of object files / libraries to build a static executable.

<OS interface: public>+≡

```
public :: os_link_static
```

<OS interface: procedures>+≡

```

subroutine os_link_static (objlist, exec_name, os_data, status)
  type(string_t), intent(in) :: objlist, exec_name
  type(os_data_t), intent(in) :: os_data
  integer, intent(out), optional :: status
  type(string_t) :: command_string
  if (os_data%use_libtool) then
    command_string = &
      os_data%whizard_libtool // " --mode=link " // &
      os_data%fc // " " // &
      "-static-libtool-libs " // &
      os_data%fcflags // " " // &
      os_data%whizard_ldflags // " " // &
      os_data%ldflags // " " // &
      os_data%ldflags_static // " " // &
      "-o '" // exec_name // "' " // &
      objlist // " " // &
      os_data%ldflags_hepmc
  else
    command_string = &
      os_data%ld // " " // &
      os_data%ldflags_so // " " // &
      os_data%fcflags // " " // &
      os_data%whizard_ldflags // " " // &
      os_data%ldflags // " " // &
      os_data%ldflags_static // " " // &

```

```

        "-o '" // exec_name // "' " // &
        objlist // " " // &
        os_data%ldflags_hepmc
    end if
    call os_system_call (command_string, status)
end subroutine os_link_static

```

Determine the name of the shared library to link. If libtool is used, this is encoded in the .la file which resides in place of the library itself.

```

<OS interface: public>+≡
    public :: os_get_dlname

<OS interface: procedures>+≡
    function os_get_dlname (lib, os_data, ignore, silent) result (dlname)
        type(string_t) :: dlname
        type(string_t), intent(in) :: lib
        type(os_data_t), intent(in) :: os_data
        logical, intent(in), optional :: ignore, silent
        type(string_t) :: filename
        type(string_t) :: buffer
        logical :: exist, required, quiet
        integer :: u
        u = free_unit ()
        if (present (ignore)) then
            required = .not. ignore
        else
            required = .true.
        end if
        if (present (silent)) then
            quiet = silent
        else
            quiet = .false.
        end if
        if (os_data%use_libtool) then
            filename = lib // ".la"
            inquire (file=char(filename), exist=exist)
            if (exist) then
                open (unit=u, file=char(filename), action="read", status="old")
                SCAN_LTFILE: do
                    call get (u, buffer)
                    if (extract (buffer, 1, 7) == "dlname=") then
                        dlname = extract (buffer, 9)
                        dlname = remove (dlname, len (dlname))
                        exit SCAN_LTFILE
                    end if
                end do SCAN_LTFILE
                close (u)
            else if (required) then
                if (.not. quiet) call msg_fatal (" Library '" // char (lib) &
                    // "': libtool archive not found")
                dlname = ""
            else
                if (.not. quiet) call msg_message ("[No compiled library '" &
                    // char (lib) // "']")
            end if
        end if
    end function os_get_dlname

```

```

        dlname = ""
    end if
else
    dlname = lib // os_data%shlib_ext
    inquire (file=char(dlname), exist=exist)
    if (.not. exist) then
        if (required) then
            if (.not. quiet) call msg_fatal (" Library '" // char (lib) &
                // "' not found")
        else
            if (.not. quiet) call msg_message &
                ("[No compiled process library '" // char (lib) // "']")
            dlname = ""
        end if
    end if
end if
end function os_get_dlname

```

2.4.8 Controlling OpenMP

OpenMP is handled automatically by the library for the most part. Here is a convenience routine for setting the number of threads, with some diagnostics.

```

<OS interface: public>+≡
    public :: openmp_set_num_threads_verbose

<OS interface: procedures>+≡
    subroutine openmp_set_num_threads_verbose (num_threads)
        integer, intent(in) :: num_threads
        integer :: n_threads
        n_threads = num_threads
        if (openmp_is_active ()) then
            if (num_threads == 1) then
                write (msg_buffer, "(A,I0,A)") "OpenMP: Using ", num_threads, &
                    " thread"
                call msg_message
                n_threads = num_threads
            else if (num_threads > 1) then
                write (msg_buffer, "(A,I0,A)") "OpenMP: Using ", num_threads, &
                    " threads"
                call msg_message
                n_threads = num_threads
            else
                write (msg_buffer, "(A,I0,A)") "OpenMP: " &
                    // "Illegal value of openmp_num_threads (", num_threads, &
                    ") ignored"
                call msg_error
                n_threads = openmp_get_default_max_threads ()
                write (msg_buffer, "(A,I0,A)") "OpenMP: Using ", &
                    n_threads, " threads"
                call msg_message
            end if
            if (n_threads > openmp_get_default_max_threads ()) then
                write (msg_buffer, "(A,I0)") "OpenMP: " &

```

```

        // "Number of threads is greater than library default of ", &
        openmp_get_default_max_threads ()
        call msg_warning
    end if
    call openmp_set_num_threads (n_threads)
else if (num_threads /= 1) then
    write (msg_buffer, "(A,I0,A)") "openmp_num_threads set to ", &
        num_threads, ", but OpenMP is not active: ignored"
    call msg_warning
end if
end subroutine openmp_set_num_threads_verbose

```

2.4.9 Test

```

<OS interface: public>+≡
    public :: os_interface_test

<OS interface: procedures>+≡
    subroutine os_interface_test ()
        call os_interface_test1 ()
    end subroutine os_interface_test

```

Write a Fortran source file, compile it to a shared library, load it, and execute the contained function.

```

<OS interface: procedures>+≡
    subroutine os_interface_test1 ()
        use diagnostics, only: msg_fatal !NODEP!
        type(dlaccess_t) :: dlaccess
        type(string_t) :: fname, libname, ext
        type(os_data_t) :: os_data
        type(string_t) :: filename_src, filename_obj
        abstract interface
            function so_test_proc (i) result (j) bind(C)
                import c_int
                integer(c_int), intent(in) :: i
                integer(c_int) :: j
            end function so_test_proc
        end interface
        procedure(so_test_proc), pointer :: so_test => null ()
        type(c_funptr) :: c_fptr
        integer :: u
        integer(c_int) :: i
        call os_data_init (os_data)
        fname = "so_test"
        filename_src = fname // os_data%fc_src_ext
        if (os_data%use_libtool) then
            ext = ".lo"
        else
            ext = os_data%obj_ext
        end if
        filename_obj = fname // ext
        libname = fname // os_data%shlib_ext
    end subroutine os_interface_test1

```

```

print *, "* write source file 'so_test.f90'"
u = free_unit ()
open (unit=u, file=char(filename_src), action="write")
write (u, "(A)") "function so_test (i) result (j) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " integer(c_int), intent(in) :: i"
write (u, "(A)") " integer(c_int) :: j"
write (u, "(A)") " j = 2 * i"
write (u, "(A)") "end function so_test"
close (u)
print *, "* compile and link as 'so_test.so'"
call os_compile_shared (fname, os_data)
call os_link_shared (filename_obj, fname, os_data)
print *, "* load library 'so_test.so'"
call dlaccess_init (dlaccess, var_str ("."), libname, os_data)
if (dlaccess_is_open (dlaccess)) then
  print *, " success"
else
  print *, " failure"
end if
print *, "* load symbol 'so_test'"
c_fptr = dlaccess_get_c_funptr (dlaccess, fname)
if (c_associated (c_fptr)) then
  print *, " success"
else
  print *, " failure"
end if
call c_f_procpointer (c_fptr, so_test)
print *, "* Execute function from 'so_test.so'"
i = 7
print *, " input = ", i
print *, " result =", so_test(i)
if (so_test(i) / i .ne. 2) then
  call msg_fatal ("Compiling and linking ISO C functions failed.")
else
  print *, "* Successful."
end if
print *, "* Cleanup"
call dlaccess_final (dlaccess)
end subroutine os_interface_test1

```

2.5 CPU timing

This is a simplified module which replaces `clock.f90` below. The time is now stored in a simple derived type which just holds a floating-point number.

```

<cputime.f90>≡
  <File header>

```

```

  module cputime

```

```

    <Use kinds>
    <Use file utils>

```

```

    <Use strings>
    use diagnostics !NODEP!

    <Standard module head>

    <CPU time: public>

    <CPU time: types>

    <CPU time: interfaces>

    contains

    <CPU time: procedures>

    end module cputime

```

The CPU time is a floating-point number with an arbitrary reference time. It is single precision (default real, not `real(default)`). It is measured in seconds.

```

    <CPU time: public>≡
        public :: time_t

    <CPU time: types>≡
        type :: time_t
            private
            logical :: known = .false.
            real :: value = 0
        end type time_t

    <CPU time: public>+≡
        public :: time_write

    <CPU time: procedures>≡
        subroutine time_write (time, unit)
            type(time_t), intent(in) :: time
            integer, intent(in), optional :: unit
            integer :: u
            u = output_unit (unit)
            write (u, "(A)", advance="no") "Time in seconds = "
            if (time%known) then
                write (u, *) time%value
            else
                write (u, *) "[unknown]"
            end if
        end subroutine time_write

    Set the current time

    <CPU time: public>+≡
        public :: time_current

    <CPU time: procedures>+≡
        function time_current () result (time)
            type(time_t) :: time
            integer :: msec
            call system_clock (msec)

```



```

        time%value = real (msecs) / 1000.
        time%known = time%value > 0
    end function time_current

```

Assign to a real(default value. If the time is undefined, return zero.

```

<CPU time: public>+≡
    public :: assignment(=)
<CPU time: interfaces>≡
    interface assignment(=)
        module procedure real_assign_time
    end interface

<CPU time: procedures>+≡
    pure subroutine real_assign_time (r, time)
        real(default), intent(out) :: r
        type(time_t), intent(in) :: time
        if (time%known) then
            r = time%value
        else
            r = 0
        end if
    end subroutine real_assign_time

```

Only time differences have a real meaning. If any input value is undefined, the result is undefined.

```

<CPU time: public>+≡
    public :: operator(-)
<CPU time: interfaces>+≡
    interface operator(-)
        module procedure subtract_times
    end interface

<CPU time: procedures>+≡
    pure function subtract_times (t_end, t_begin) result (time)
        type(time_t) :: time
        type(time_t), intent(in) :: t_end, t_begin
        if (t_end%known .and. t_begin%known) then
            time%known = .true.
            time%value = t_end%value - t_begin%value
        end if
    end function subtract_times

```

We define functions for converting the time into ss / mm:ss / hh:mm:ss / dd:mm:hh:ss.

```

<CPU time: public>+≡
    public :: time_retrieve
    public :: time2string_s
    public :: time2string_ms
    public :: time2string_hms
    public :: time2string_dhms
    public :: time2string

```

```

<CPU time: interfaces>+≡
interface time_retrieve
    module procedure time_retrieve_s, time_retrieve_ms, time_retrieve_hms, &
        time_retrieve_dhms
end interface time_retrieve

<CPU time: procedures>+≡
subroutine time_retrieve_s (time, sec)
    integer, intent(in) :: time
    integer, intent(out) :: sec
    sec = time
end subroutine time_retrieve_s

subroutine time_retrieve_ms (time, min, sec)
    integer, intent(in) :: time
    integer, intent(out) :: min, sec
    sec = mod (time, 60)
    min = time / 60
end subroutine time_retrieve_ms

subroutine time_retrieve_hms (time, hour, min, sec)
    integer, intent(in) :: time
    integer, intent(out) :: hour, min, sec
    call time_retrieve_ms (time, min, sec)
    hour = min / 60
    min = mod (min, 60)
end subroutine time_retrieve_hms

subroutine time_retrieve_dhms (time, day, hour, min, sec)
    integer, intent(in) :: time
    integer, intent(out) :: day, hour, min, sec
    call time_retrieve_hms (time, hour, min, sec)
    day = hour / 24
    hour = mod (hour, 24)
end subroutine time_retrieve_dhms

function time2string_s (time) result (str)
    integer, intent(in) :: time
    type(string_t) :: str
    str = int2string (time) // "s"
end function time2string_s

function time2string_ms (time) result (str)
    integer, intent(in) :: time
    type(string_t) :: str
    integer :: min, sec
    call time_retrieve (time, min, sec)
    str = int2string (min) // "m:" // int2string (sec) // "s"
end function time2string_ms

function time2string_hms (time) result (str)
    integer, intent(in) :: time
    type(string_t) :: str
    integer :: hour, min, sec
    call time_retrieve (time, hour, min, sec)

```

```

        str = int2string (hour) // "h:" // &
            int2string (min) // "m:" // int2string (sec) // "s"
    end function time2string_hms

function time2string_dhms (time) result (str)
    integer, intent(in) :: time
    type(string_t) :: str
    integer :: day, hour, min, sec
    call time_retrieve (time, day, hour, min, sec)
    str = int2string (day) // "d:" // int2string (hour) // "h:" // &
        int2string (min) // "m:" // int2string (sec) // "s"
end function time2string_dhms

function time2string (time) result (str)
    integer, intent(in) :: time
    type(string_t) :: str
    integer :: day, hour, min, sec
    call time_retrieve (time, day, hour, min, sec)
    if (day /= 0) then
        str = time2string_dhms (time)
    else if (hour /= 0) then
        str = time2string_hms (time)
    else if (min /= 0) then
        str = time2string_ms (time)
    else
        str = time2string_s (time)
    end if
end function time2string

```

2.6 Accessing the system clock

This module is currently disabled, we are using the module above instead.

Fortran 90 provides a standard interface for the system clock. Here, we define a record for storing the information, and higher-level functions for accessing it.

```

⟨clock.f90⟩≡
    ⟨File header⟩

    module clock

        ⟨Use kinds⟩
        ⟨Use file utils⟩

        ⟨Standard module head⟩

        ⟨Clock: public⟩

        ⟨Clock: types⟩

        ⟨Clock: interfaces⟩

    contains

```

<Clock: procedures>

end module clock

The format for storing the current date. We want to be able to store time differences, therefore everything is converted to the time difference between now and Jan 01 2000, 0:00. The timezone is ignored.

<Clock: public>≡

public :: time_t

<Clock: types>≡

type :: time_t

integer :: day = 0

integer :: hour = 0

integer :: minute = 0

integer :: second = 0

integer :: millisecond = 0

end type time_t

Write the time in readable form

<Clock: public>+≡

public :: time_write

<Clock: interfaces>≡

interface time_write

module procedure time_write_unit

module procedure time_write_string

end interface

The maximal time that can be written is 999 days. No way to write negative times.

<Clock: procedures>≡

subroutine time_write_unit (t, unit, advance, days, seconds, milliseconds)

type(time_t), intent(in) :: t

integer, intent(in) :: unit

character(len=*), intent(in), optional :: advance

logical, intent(in), optional :: days, seconds, milliseconds

logical :: dd, ss, ms

character(len=3) :: adv

if (present (advance)) then

adv = advance

else

adv = "yes"

end if

dd = .false.; if (present (days)) dd = days

ss = .true.; if (present (seconds)) ss = seconds

ms = .false.; if (present (milliseconds)) ms = milliseconds

if (dd) then

write (unit, "(I3,A,1x,I2.2,A,1x,I2.2,A)", advance="no") &

t%day, "d", t%hour, "h", t%minute, "m"

else

write (unit, "(I5,A,1x,I2.2,A)", advance="no") &

t%day * 24 + t%hour, "h", t%minute, "m"

end if

if (ss) then

write (unit, "(1x,I2.2)", advance="no") t%second

```

        if (ms) then
            write (unit, "(A,I3.3,A)", advance=trim(adv)) " .", t%millisecond, "s"
        else
            write (unit, "(A)", advance=trim(adv)) "s"
        end if
    end if
end subroutine time_write_unit

```

Write the time to a string. This uses a scratch file for simplicity. Non-advancing output is not possible.

```

<Clock: procedures>+≡
subroutine time_write_string (t, string, days, seconds, milliseconds)
    type(time_t), intent(in) :: t
    character(*), intent(out) :: string
    logical, intent(in), optional :: days, seconds, milliseconds
    integer :: unit
    unit = free_unit ()
    open (unit, status="scratch", action="readwrite")
    call time_write_unit (t, unit, &
        days=days, seconds=seconds, milliseconds=milliseconds)
    rewind (unit)
    read (unit, "(A)") string
    close (unit)
end subroutine time_write_string

```

Set the current time to number of days, minutes, seconds, milliseconds elapsed since Jan 1 2000. Works for dates after Jan 1 2001 until Dec 31 2099.

```

<Clock: public>+≡
public :: time_current

<Clock: procedures>+≡
function time_current () result (t)
    type(time_t) :: t
    integer, dimension(8) :: values
    integer :: year
    call date_and_time (values = values)
    t%millisecond = values(8)
    t%second = values(7)
    t%minute = values(6)
    t%hour = values(5)
    ! values(4) is the difference local time - GMT in minutes
    t%day = values(3) - 1
    select case (values(2))
    case ( 1)
    case ( 2); t%day = t%day + 31
    case ( 3); t%day = t%day + 31 + 28
    case ( 4); t%day = t%day + 31 + 28 + 31
    case ( 5); t%day = t%day + 31 + 28 + 31 + 30
    case ( 6); t%day = t%day + 31 + 28 + 31 + 30 + 31
    case ( 7); t%day = t%day + 31 + 28 + 31 + 30 + 31 + 30
    case ( 8); t%day = t%day + 31 + 28 + 31 + 30 + 31 + 30 + 31
    case ( 9); t%day = t%day + 31 + 28 + 31 + 30 + 31 + 30 + 31 + 31
    case (10); t%day = t%day + 31 + 28 + 31 + 30 + 31 + 30 + 31 + 31 + 30
    end select
end function time_current

```

```

case (11); t%day = t%day + 31 + 28 + 31 + 30 + 31 + 30 + 31 + 31 + 30 + 31
case (12); t%day = t%day + 31 + 28 + 31 + 30 + 31 + 30 + 31 + 31 + 30 + 31 + 30
end select
year = values(1) - 2000
if (year < 1) return
t%day = t%day + 365 * year + ((year-1) / 4 + 1)
if (mod (year, 4) == 0 .and. values(2) > 2) t%day = t%day + 1
end function time_current

```

Convert from and to seconds

```

<Clock: public>+≡
public :: time_to_seconds, time_from_seconds

<Clock: procedures>+≡
function time_to_seconds (t) result (s)
  type(time_t), intent(in) :: t
  real(kind=default) :: s
  s = t%millisecond / 1000._default &
    + t%second &
    + 60._default * (t%minute &
      + 60._default * (t%hour &
        + 24._default * t%day))
end function time_to_seconds

<Clock: procedures>+≡
function time_from_seconds (s) result (t)
  real(kind=default), intent(in) :: s
  type(time_t) :: t
  t%millisecond = s * 1000
  t%second = t%millisecond / 1000
  t%millisecond = mod (t%millisecond, 1000)
  t%minute = t%second / 60
  t%second = mod (t%second, 60)
  t%hour = t%minute / 60
  t%minute = mod (t%minute, 60)
  t%day = t%hour / 24
  t%hour = mod (t%hour, 24)
end function time_from_seconds

```

Add and subtract times

```

<Clock: public>+≡
public :: operator(+), operator(-)

<Clock: interfaces>+≡
interface operator(+)
  module procedure time_add
end interface
interface operator(-)
  module procedure time_subtract
end interface

<Clock: procedures>+≡
function time_add (t1, t2) result (t)
  type(time_t), intent(in) :: t1, t2

```

```

type(time_t) :: t
t%millisecond = t1%millisecond + t2%millisecond
t%second = t1%second + t2%second
t%minute = t1%minute + t2%minute
t%hour = t1%hour + t2%hour
t%day = t1%day + t2%day
if (t%millisecond > 999) then
    t%second = t%second + t%millisecond / 1000
    t%millisecond = modulo (t%millisecond, 1000)
end if
if (t%second > 59) then
    t%minute = t%minute + t%second / 60
    t%second = modulo (t%second, 60)
end if
if (t%minute > 59) then
    t%hour = t%hour + t%minute / 60
    t%minute = modulo (t%minute, 60)
end if
if (t%hour > 23) then
    t%day = t%day + t%hour / 24
    t%hour = modulo (t%hour, 24)
end if
end function time_add

```

This works for positive difference only, the first time must be later than the second. Otherwise, the number of days is set to zero.

(Clock: procedures)+≡

```

function time_subtract (t1, t2) result (t)
    type(time_t), intent(in) :: t1, t2
    type(time_t) :: t
    t%millisecond = t1%millisecond - t2%millisecond
    t%second = t1%second - t2%second
    t%minute = t1%minute - t2%minute
    t%hour = t1%hour - t2%hour
    t%day = t1%day - t2%day
    if (t%millisecond < 0) then
        t%second = t%second - 1 + t%millisecond / 1000
        t%millisecond = modulo (t%millisecond, 1000)
    end if
    if (t%second < 0) then
        t%minute = t%minute - 1 + t%second / 60
        t%second = modulo (t%second, 60)
    end if
    if (t%minute < 0) then
        t%hour = t%hour - 1 + t%minute / 60
        t%minute = modulo (t%minute, 60)
    end if
    if (t%hour < 0) then
        t%day = t%day - 1 + t%hour / 24
        t%hour = modulo (t%hour, 24)
    end if
    if (t%day < 0) then
        t%day = 0
    end if
end function time_subtract

```

```

    end if
end function time_subtract

```

Compare times

```

<Clock: public>+≡
    public :: operator(==)
    public :: operator(<), operator(>)
    public :: operator(<=), operator(>=)

<Clock: interfaces>+≡
    interface operator(==)
        module procedure time_equal
    end interface
    interface operator(<)
        module procedure time_less_than
    end interface
    interface operator(>)
        module procedure time_greater_than
    end interface
    interface operator(<=)
        module procedure time_less_equal
    end interface
    interface operator(>=)
        module procedure time_greater_equal
    end interface

<Clock: procedures>+≡
    function time_equal (t1, t2) result (equal)
        type(time_t), intent(in) :: t1, t2
        logical :: equal
        equal = (t1%day==t2%day) .and. (t1%hour==t2%hour) .and. &
            (t1%minute==t2%minute) .and. (t1%second==t2%second) .and. &
            (t1%millisecond==t2%millisecond)
    end function time_equal

<Clock: procedures>+≡
    function time_less_than (t1, t2) result (less)
        type(time_t), intent(in) :: t1, t2
        logical :: less
        if (t1%day < t2%day) then
            less = .true.
        else if (t1%day == t2%day) then
            if (t1%hour < t2%hour) then
                less = .true.
            else if (t1%hour == t2%hour) then
                if (t1%minute < t2%minute) then
                    less = .true.
                else if (t1%minute == t2%minute) then
                    if (t1%second < t2%second) then
                        less = .true.
                    else if (t1%second == t2%second) then
                        if (t1%millisecond < t2%millisecond) then
                            less = .true.
                        else

```



```

        less = .false.
    end if
    else
        less = .false.
    end if
    else
        less = .false.
    end if
    else
        less = .false.
    end if
    else
        less = .false.
    end if
end function time_less_than

```

```

<Clock: procedures>+≡
function time_greater_than (t1, t2) result (greater)
    type(time_t), intent(in) :: t1, t2
    logical :: greater
    greater = time_less_than (t2, t1)
end function time_greater_than

```

```

<Clock: procedures>+≡
function time_less_equal (t1, t2) result (less_equal)
    type(time_t), intent(in) :: t1, t2
    logical :: less_equal
    less_equal = time_equal (t1, t2) .or. time_less_than (t1, t2)
end function time_less_equal

```

```

<Clock: procedures>+≡
function time_greater_equal (t1, t2) result (greater_equal)
    type(time_t), intent(in) :: t1, t2
    logical :: greater_equal
    greater_equal = time_equal (t1, t2) .or. time_greater_than (t1, t2)
end function time_greater_equal

```

2.7 Hashtables

Hash tables, like lists, are not part of Fortran and must be defined on a per-case basis. In this section we define a module that contains a hash function.

Furthermore, for reference there is a complete framework of hashtable type definitions and access functions. This code is to be replicated where hash tables are used, *mutatis mutandis*.

```

<hashes.f90>≡
<File header>

```

```

module hashes

```

```

    use kinds, only: i8, i32 !NODEP!

```

⟨Standard module head⟩

⟨Hashes: public⟩

contains

⟨Hashes: procedures⟩

end module hashes

2.7.1 The hash function

This is the one-at-a-time hash function by Bob Jenkins (from Wikipedia), re-implemented in Fortran. The function works on an array of bytes (8-bit integers), as could be produced by, e.g., the **transfer** function, and returns a single 32-bit integer. For determining the position in a hashtable, one can pick the lower bits of the result as appropriate to the hashtable size (which should be a power of 2). Note that we are working on signed integers, so the interpretation of values differs from the C version. This should not matter in practice, however.

⟨Hashes: public⟩≡

public :: hash

⟨Hashes: procedures⟩≡

```
function hash (key)
  integer(i8), dimension(:), intent(in) :: key
  integer(i32) :: hash
  integer :: i
  hash = 0
  do i = 1, size (key)
    hash = hash + key(i)
    hash = hash + ishft (hash, 10)
    hash = ieor (hash, ishft (hash, -6))
  end do
  hash = hash + ishft (hash, 3)
  hash = ieor (hash, ishft (hash, -11))
  hash = hash + ishft (hash, 15)
end function hash
```

2.7.2 The hash table

We define a generic hashtable type (that depends on the **hash_data_t** type) together with associated methods.

This is a template:

⟨Hashtables: types⟩≡

```
type :: hash_data_t
  integer :: i
end type hash_data_t
```

Associated methods:

(Hashtables: procedures)≡

```

subroutine hash_data_final (data)
  type(hash_data_t), intent(inout) :: data
end subroutine hash_data_final

subroutine hash_data_write (data, unit)
  type(hash_data_t), intent(in) :: data
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, *) data%i
end subroutine hash_data_write

```

Each hash entry stores the unmasked hash value, the key, and points to actual data if present. Note that this could be an allocatable scalar in principle, but making it a pointer avoids deep copy when expanding the hashtable.

(Hashtables: types)+≡

```

type :: hash_entry_t
  integer(i32) :: hashval = 0
  integer(i8), dimension(:), allocatable :: key
  type(hash_data_t), pointer :: data => null ()
end type hash_entry_t

```

The hashtable object holds the actual table, the number of filled entries and the number of entries after which the size should be doubled. The mask is equal to the table size minus one and thus coincides with the upper bound of the table index, which starts at zero.

(Hashtables: types)+≡

```

type :: hashtable_t
  integer :: n_entries = 0
  real :: fill_ratio = 0
  integer :: n_entries_max = 0
  integer(i32) :: mask = 0
  type(hash_entry_t), dimension(:), allocatable :: entry
end type hashtable_t

```

Initializer: The size has to be a power of two, the fill ratio is a real (machine-default!) number between 0 and 1.

(Hashtables: procedures)+≡

```

subroutine hashtable_init (hashtable, size, fill_ratio)
  type(hashtable_t), intent(out) :: hashtable
  integer, intent(in) :: size
  real, intent(in) :: fill_ratio
  hashtable%fill_ratio = fill_ratio
  hashtable%n_entries_max = size * fill_ratio
  hashtable%mask = size - 1
  allocate (hashtable%entry (0:hashtable%mask))
end subroutine hashtable_init

```

Finalizer: This calls a `hash_data_final` subroutine which must exist.

```

(Hashtables: procedures) +=
  subroutine hashtable_final (hashtable)
    type(hashtable_t), intent(inout) :: hashtable
    integer :: i
    do i = 0, hashtable%mask
      if (associated (hashtable%entry(i)%data)) then
        call hash_data_final (hashtable%entry(i)%data)
        deallocate (hashtable%entry(i)%data)
      end if
    end do
    deallocate (hashtable%entry)
  end subroutine hashtable_final

```

Output. Here, we refer to a `hash_data_write` subroutine.

```

(Hashtables: procedures) +=
  subroutine hashtable_write (hashtable, unit)
    type(hashtable_t), intent(in) :: hashtable
    integer, intent(in), optional :: unit
    integer :: u, i
    u = output_unit (unit); if (u < 0) return
    do i = 0, hashtable%mask
      if (associated (hashtable%entry(i)%data)) then
        write (u, *) i, "(hash =", hashtable%entry(i)%hashval, ")", &
          hashtable%entry(i)%key
        call hash_data_write (hashtable%entry(i)%data, unit)
      end if
    end do
  end subroutine hashtable_write

```

2.7.3 Hashtable insertion

Insert a single entry with the hash value as trial place. If the table is filled, first expand it.

```

(Hashtables: procedures) +=
  subroutine hashtable_insert (hashtable, key, data)
    type(hashtable_t), intent(inout) :: hashtable
    integer(i8), dimension(:), intent(in) :: key
    type(hash_data_t), intent(in), target :: data
    integer(i32) :: h
    if (hashtable%n_entries >= hashtable%n_entries_max) &
      call hashtable_expand (hashtable)
    h = hash (key)
    call hashtable_insert_rec (hashtable, h, h, key, data)
  end subroutine hashtable_insert

```

We need this auxiliary routine for doubling the size of the hashtable. We rely on the fact that default assignment copies the data pointer, not the data themselves. The temporary array must not be finalized; it is deallocated automatically together with its allocatable components.

```

(Hashtables: procedures) +=

```

```

subroutine hashtable_expand (hashtable)
  type(hashtable_t), intent(inout) :: hashtable
  type(hash_entry_t), dimension(:), allocatable :: table_tmp
  integer :: i, s
  allocate (table_tmp (0:hashtable%mask))
  table_tmp = hashtable%entry
  deallocate (hashtable%entry)
  s = 2 * size (table_tmp)
  hashtable%n_entries = 0
  hashtable%n_entries_max = s * hashtable%fill_ratio
  hashtable%mask = s - 1
  allocate (hashtable%entry (0:hashtable%mask))
  do i = 0, ubound (table_tmp, 1)
    if (associated (table_tmp(i)%data)) then
      call hashtable_insert_rec (hashtable, table_tmp(i)%hashval, &
        table_tmp(i)%hashval, table_tmp(i)%key, table_tmp(i)%data)
    end if
  end do
end subroutine hashtable_expand

```

Insert a single entry at a trial place h , reduced to the table size. Collision resolution is done simply by choosing the next element, recursively until the place is empty. For bookkeeping, we preserve the original hash value. For a good hash function, there should be no clustering.

Note that if the new key exactly matches an existing key, nothing is done.

(*Hashtables: procedures*) +=

```

recursive subroutine hashtable_insert_rec (hashtable, h, hashval, key, data)
  type(hashtable_t), intent(inout) :: hashtable
  integer(i32), intent(in) :: h, hashval
  integer(i8), dimension(:), intent(in) :: key
  type(hash_data_t), intent(in), target :: data
  integer(i32) :: i
  i = iand (h, hashtable%mask)
  if (associated (hashtable%entry(i)%data)) then
    if (size (hashtable%entry(i)%key) /= size (key)) then
      call hashtable_insert_rec (hashtable, h + 1, hashval, key, data)
    else if (any (hashtable%entry(i)%key /= key)) then
      call hashtable_insert_rec (hashtable, h + 1, hashval, key, data)
    end if
  else
    hashtable%entry(i)%hashval = hashval
    allocate (hashtable%entry(i)%key (size (key)))
    hashtable%entry(i)%key = key
    hashtable%entry(i)%data => data
    hashtable%n_entries = hashtable%n_entries + 1
  end if
end subroutine hashtable_insert_rec

```

2.7.4 Hashtable lookup

The lookup function has to parallel the insert function. If the place is filled, check if the key matches. Yes: return the pointer; no: increment the hash value

and check again.

<Hashtables: procedures>+≡

```
function hashtable_lookup (hashtable, key) result (ptr)
  type(hash_data_t), pointer :: ptr
  type(hashtable_t), intent(in) :: hashtable
  integer(i8), dimension(:), intent(in) :: key
  ptr => hashtable_lookup_rec (hashtable, hash (key), key)
end function hashtable_lookup
```

<Hashtables: procedures>+≡

```
recursive function hashtable_lookup_rec (hashtable, h, key) result (ptr)
  type(hash_data_t), pointer :: ptr
  type(hashtable_t), intent(in) :: hashtable
  integer(i32), intent(in) :: h
  integer(i8), dimension(:), intent(in) :: key
  integer(i32) :: i
  i = iand (h, hashtable%mask)
  if (associated (hashtable%entry(i)%data)) then
    if (size (hashtable%entry(i)%key) == size (key)) then
      if (all (hashtable%entry(i)%key == key)) then
        ptr => hashtable%entry(i)%data
      else
        ptr => hashtable_lookup_rec (hashtable, h + 1, key)
      end if
    else
      ptr => hashtable_lookup_rec (hashtable, h + 1, key)
    end if
  else
    ptr => null ()
  end if
end function hashtable_lookup_rec
```

<Hashtables: public>≡

```
public :: hashtable_test
```

<Hashtables: procedures>+≡

```
subroutine hashtable_test ()
  type(hash_data_t), pointer :: data
  type(hashtable_t) :: hashtable
  integer(i8) :: i
  call hashtable_init (hashtable, 16, 0.25)
  do i = 1, 10
    allocate (data)
    data%i = i*i
    call hashtable_insert (hashtable, (/i, i+i/), data)
  end do
  call hashtable_insert (hashtable, (/2_i8, 4_i8/), data)
  call hashtable_write (hashtable)
  data => hashtable_lookup (hashtable, (/5_i8, 10_i8/))
  if (associated (data)) then
    print *, "lookup:", data%i
  else
    print *, "lookup: --"
  end if
end if
```

```

data => hashtable_lookup (hashtable, (/6_i8, 12_i8/))
if (associated (data)) then
    print *, "lookup:", data%i
else
    print *, "lookup: --"
end if
data => hashtable_lookup (hashtable, (/4_i8, 9_i8/))
if (associated (data)) then
    print *, "lookup:", data%i
else
    print *, "lookup: --"
end if
call hashtable_final (hashtable)
end subroutine hashtable_test

```

2.8 Message and signal handling

We are not so ambitious as to do proper exception handling in WHIZARD, but at least it may be useful to have a common interface for diagnostics: Results, messages, warnings, and such. As module variables we keep a buffer where the current message may be written to and a level indicator which tells which messages should be written on screen and which ones should be skipped. Alternatively, a string may be directly supplied to the message routine: this overrides the buffer, avoiding the necessity of formatted I/O in trivial cases.

<diagnostics.f90>≡

<File header>

`module diagnostics`

`use iso_c_binding !NODEP!`

`use system_dependencies !NODEP!`

<Use kinds>

<Use strings>

`use limits, only: BUFFER_SIZE, MAX_ERRORS !NODEP!`

`use file_utils !NODEP!`

`use iso_fortran_env, only: &`

`stdout => output_unit, stdin => input_unit !NODEP!`

<Standard module head>

<Diagnostics: public>

<Diagnostics: parameters>

<Diagnostics: types>

<Diagnostics: variables>

<Diagnostics: interfaces>

`contains`

<Diagnostics: procedures>

end module diagnostics

Diagnostics levels:

<Diagnostics: parameters>≡
integer, parameter :: &
 & TERMINATE=-2, BUG=-1, &
 & FATAL=1, ERROR=2, WARNING=3, MESSAGE=4, RESULT=5, DEBUG=6

<Diagnostics: variables>≡
integer, save :: msg_level = RESULT

Mask fatal errors so that are treated as normal errors. Useful for interactive mode.

<Diagnostics: public>≡
public :: mask_fatal_errors
<Diagnostics: variables>+≡
logical, save :: mask_fatal_errors = .false.

How to handle bugs and unmasked fatal errors. Either execute a normal stop statement, or call the C `exit()` function, or try to cause a program crash by dereferencing a null pointer.

<Diagnostics: parameters>+≡
integer, parameter :: TERM_STOP = 0, TERM_EXIT = 1, TERM_CRASH = 2
<Diagnostics: variables>+≡
integer, save :: handle_fatal_errors = TERM_EXIT

Keep track of errors. This might be used for exception handling, later. The counter is incremented only for screen messages, to avoid double counting.

<Diagnostics: public>+≡
public :: msg_count
<Diagnostics: variables>+≡
integer, dimension(TERMINATE:DEBUG), save :: msg_count = 0

Keep a list of all errors and warnings. Since we do not know the number of entries beforehand, we use a linked list.

<Diagnostics: types>≡
type :: string_list
 character(len=BUFFER_SIZE) :: string
 type(string_list), pointer :: next
end type string_list
type :: string_list_pointer
 type(string_list), pointer :: first, last
end type string_list_pointer
<Diagnostics: variables>+≡
type(string_list_pointer), dimension(TERMINATE:WARNING), save :: &
 & msg_list = string_list_pointer (null(), null())

Add the current message buffer contents to the internal list.

```

<Diagnostics: procedures>≡
subroutine msg_add (level)
  integer, intent(in) :: level
  type(string_list), pointer :: message
  select case (level)
  case (TERMINATE:WARNING)
    allocate (message)
    message%string = msg_buffer
    nullify (message%next)
    if (.not.associated (msg_list(level)%first)) &
      & msg_list(level)%first => message
    if (associated (msg_list(level)%last)) &
      & msg_list(level)%last%next => message
    msg_list(level)%last => message
    msg_count(level) = msg_count(level) + 1
  end select
end subroutine msg_add

```

Initialization:

```

<Diagnostics: public>+≡
public :: msg_list_clear

<Diagnostics: procedures>+≡
subroutine msg_list_clear
  integer :: level
  type(string_list), pointer :: message
  do level = TERMINATE, WARNING
    do while (associated (msg_list(level)%first))
      message => msg_list(level)%first
      msg_list(level)%first => message%next
      deallocate (message)
    end do
    nullify (msg_list(level)%last)
  end do
  msg_count = 0
end subroutine msg_list_clear

```

Display the summary of errors and warnings (no need to count fatals...)

```

<Diagnostics: public>+≡
public :: msg_summary

<Diagnostics: procedures>+≡
subroutine msg_summary (unit)
  integer, intent(in), optional :: unit
  call expect_summary (unit)
1  format (A,1x,I2,1x,A,I2,1x,A)
  if (msg_count(ERROR) > 0 .and. msg_count(WARNING) > 0) then
    write (msg_buffer, 1) "There were", &
      & msg_count(ERROR), "error(s) and ", &
      & msg_count(WARNING), "warning(s). "
    call msg_message (unit=unit)
  else if (msg_count(ERROR) > 0) then
    write (msg_buffer, 1) "There were", &

```

```

        & msg_count(ERROR), "error(s) and no warnings."
    call msg_message (unit=unit)
else if (msg_count(WARNING) > 0) then
    write (msg_buffer, 1) "There were no errors and ", &
        & msg_count(WARNING), "warning(s)."
    call msg_message (unit=unit)
end if
end subroutine msg_summary

```

Print the list of all messages of a given level.

<Diagnostics: public>+≡

```
public :: msg_listing
```

<Diagnostics: procedures>+≡

```

subroutine msg_listing (level, unit, prefix)
    integer, intent(in) :: level
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: prefix
    type(string_list), pointer :: message
    integer :: u
    u = output_unit (unit); if (u < 0) return
    if (present (unit)) u = unit
    message => msg_list(level)%first
    do while (associated (message))
        if (present (prefix)) then
            write (u, "(A)") prefix // trim (message%string)
        else
            write (u, "(A)") trim (message%string)
        end if
        message => message%next
    end do
    flush (u)
end subroutine msg_listing

```

There is a hard limit on the line length which we should export. This buffer size is used both by the message handler and by the lexer below.

<Limits: public parameters>+≡

```
integer, parameter, public :: BUFFER_SIZE = 1000
```

The message buffer:

<Diagnostics: public>+≡

```
public :: msg_buffer
```

<Diagnostics: variables>+≡

```
character(len=BUFFER_SIZE), save :: msg_buffer = " "
```

After a message is issued, the buffer should be cleared:

<Diagnostics: procedures>+≡

```

subroutine buffer_clear
    msg_buffer = " "
end subroutine buffer_clear

```

The generic handler for messages. If the unit is omitted (or = 6), the message is written to standard output if the precedence is sufficiently high (as determined by the value of `msg_level`). If the string is omitted, the buffer is used. In any case, the buffer is cleared after printing. In accordance with FORTRAN custom, the first column in the output is left blank. For messages and warnings, an additional exclamation mark and a blank is prepended. Furthermore, each message is appended to the internal message list (without prepending anything).

(Diagnostics: procedures)+≡

```

subroutine message_print (level, string, str_arr, unit, logfile)
  integer, intent(in) :: level
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: str_arr
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: logfile
  type(string_t) :: prep_string, aux_string, head_footer
  integer :: lu, i
  logical :: severe, is_error
  severe = .false.
  head_footer = "*****"
  aux_string = ""
  is_error = .false.
  ! integer :: proc_id
  ! call mpi90_rank (proc_id)
  ! if (proc_id==WHIZARD_ROOT) then
    select case (level)
    case (TERMINATE)
      prep_string = ""
    case (BUG)
      prep_string = "*** WHIZARD BUG: "
      aux_string = "***"
      severe = .true.
      is_error = .true.
    case (FATAL)
      prep_string = "*** FATAL ERROR: "
      aux_string = "***"
      severe = .true.
      is_error = .true.
    case (ERROR)
      prep_string = "*** ERROR: "
      aux_string = "***"
      is_error = .true.
    case (WARNING)
      prep_string = "Warning: "
    case (MESSAGE, DEBUG)
      prep_string = "| "
    case default
      prep_string = ""
    end select
    if (present(string)) msg_buffer = string
    lu = log_unit
    if (present(unit)) then
      if (unit /= stdout) then
        if (severe) write (unit, "(A)") char(head_footer)

```

```

        if (is_error) write (unit, "(A)") char(head_footer)
        write (unit, "(A,A)") char(prepare_string), trim(msg_buffer)
        if (present (str_arr)) then
            do i = 1, size(str_arr)
                write (unit, "(A,A)") char(aux_string), char(trim(str_arr(i)))
            end do
        end if
        if (is_error) write (unit, "(A)") char(head_footer)
        if (severe) write (unit, "(A)") char(head_footer)
        flush (unit)
        lu = -1
    else if (level <= msg_level) then
        if (severe) print "(A)", char(head_footer)
        if (is_error) print "(A)", char(head_footer)
        print "(A,A)", char(prepare_string), trim(msg_buffer)
        if (present (str_arr)) then
            do i = 1, size(str_arr)
                print "(A,A)", char(aux_string), char(trim(str_arr(i)))
            end do
        end if
        if (is_error) print "(A)", char(head_footer)
        if (severe) print "(A)", char(head_footer)
        flush (stdout)
        if (unit == log_unit) lu = -1
    end if
    else if (level <= msg_level) then
        if (severe) print "(A)", char(head_footer)
        if (is_error) print "(A)", char(head_footer)
        print "(A,A)", char(prepare_string), trim(msg_buffer)
        if (present (str_arr)) then
            do i = 1, size(str_arr)
                print "(A,A)", char(aux_string), char(trim(str_arr(i)))
            end do
        end if
        if (is_error) print "(A)", char(head_footer)
        if (severe) print "(A)", char(head_footer)
        flush (stdout)
    end if
    if (present (logfile)) then
        if (.not. logfile) lu = -1
    end if
    if (lu >= 0) then
        if (severe) write (lu, "(A)") char(head_footer)
        if (is_error) write (lu, "(A)") char(head_footer)
        write (lu, "(A,A)") char(prepare_string), trim(msg_buffer)
        if (present (str_arr)) then
            do i = 1, size(str_arr)
                write (lu, "(A,A)") char(aux_string), char(trim(str_arr(i)))
            end do
        end if
        if (is_error) write (lu, "(A)") char(head_footer)
        if (severe) write (lu, "(A)") char(head_footer)
        flush (lu)
    end if
end if

```

```

!      end if
      call msg_add (level)
      call buffer_clear
end subroutine message_print

```

The specific handlers. In the case of fatal errors, bugs (failed assertions) and normal termination execution is stopped. For non-fatal errors a message is printed to standard output if no unit is given. Only if the number of `MAX_ERRORS` errors is reached, we abort the program. There are no further actions in the other cases, but this may change.

```

<Diagnostics: public>+≡
  public :: msg_terminate
  public :: msg_bug, msg_fatal, msg_error, msg_warning
  public :: msg_message, msg_result, msg_debug

<Diagnostics: procedures>+≡
  subroutine msg_terminate (string, unit, quit_code)
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: string
    integer, intent(in), optional :: quit_code
    integer(c_int) :: return_code
    call release_term_signals ()
    if (present (quit_code)) then
      return_code = quit_code
    else
      return_code = 0
    end if
    if (present (string)) &
      call message_print (MESSAGE, string, unit=unit)
    call msg_summary (unit)
    if (return_code == 0 .and. expect_failures /= 0) then
      return_code = 5
      call message_print (MESSAGE, &
        "WHIZARD run finished with 'expect' failure(s).", unit=unit)
    else
      call message_print (MESSAGE, "WHIZARD run finished.", unit=unit)
    end if
    call message_print (0, &
      "|=====|", unit=u
    call logfile_final ()
    if (return_code /= 0) then
      call exit (return_code)
    else
      stop
    end if
  end subroutine msg_terminate

  subroutine msg_bug (string, arr, unit)
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: string
    type(string_t), dimension(:), intent(in), optional :: arr
    logical, pointer :: crash_ptr
    call message_print (BUG, string, arr, unit)
    call msg_summary (unit)

```

```

select case (handle_fatal_errors)
case (TERM_EXIT)
    call message_print (TERMINATE, "WHIZARD run aborted.", unit=unit)
    call exit (-1_c_int)
case (TERM_CRASH)
    print *, "*** Intentional crash ***"
    crash_ptr => null ()
    print *, crash_ptr
end select
stop "WHIZARD run aborted."
end subroutine msg_bug

recursive subroutine msg_fatal (string, arr, unit)
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: string
    type(string_t), dimension(:), intent(in), optional :: arr
    logical, pointer :: crash_ptr
    if (mask_fatal_errors) then
        call msg_error (string, arr, unit)
    else
        call message_print (FATAL, string, arr, unit)
        call msg_summary (unit)
        select case (handle_fatal_errors)
        case (TERM_EXIT)
            call message_print (TERMINATE, "WHIZARD run aborted.", unit=unit)
            call exit (1_c_int)
        case (TERM_CRASH)
            print *, "*** Intentional crash ***"
            crash_ptr => null ()
            print *, crash_ptr
        end select
        stop "WHIZARD run aborted."
    end if
end subroutine msg_fatal

subroutine msg_error (string, arr, unit)
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: string
    type(string_t), dimension(:), intent(in), optional :: arr
    call message_print (ERROR, string, arr, unit)
    if (msg_count(ERROR) >= MAX_ERRORS) then
        mask_fatal_errors = .false.
        call msg_fatal (" Too many errors encountered.")
!     else if (.not.present(unit) .and. .not.mask_fatal_errors) then
!         call message_print (MESSAGE, "                (WHIZARD run continues)")
    end if
end subroutine msg_error

subroutine msg_warning (string, arr, unit)
    integer, intent(in), optional :: unit
    character(len=*), intent(in), optional :: string
    type(string_t), dimension(:), intent(in), optional :: arr
    call message_print (WARNING, string, arr, unit)
end subroutine msg_warning

```

```

subroutine msg_message (string, unit, arr, logfile)
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: arr
  logical, intent(in), optional :: logfile
  call message_print (MESSAGE, string, arr, unit, logfile)
end subroutine msg_message

subroutine msg_result (string, arr, unit, logfile)
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: arr
  logical, intent(in), optional :: logfile
  call message_print (RESULT, string, arr, unit, logfile)
end subroutine msg_result

subroutine msg_debug (string, arr, unit)
  integer, intent(in), optional :: unit
  character(len=*), intent(in), optional :: string
  type(string_t), dimension(:), intent(in), optional :: arr
  call message_print (DEBUG, string, arr, unit)
end subroutine msg_debug

```

Interface to the standard clib exit function

$$\langle \textit{Diagnostics: interfaces} \rangle \equiv$$

```

interface
  subroutine exit (status) bind (C)
    use iso_c_binding !NODEP!
    integer(c_int), value :: status
  end subroutine exit
end interface

```

$$\langle Limits: public parameters \rangle + \equiv$$

```
integer, parameter, public :: MAX_ERRORS = 10
```

Print the WHIZARD banner:

$$\langle \textit{Diagnostics: public} \rangle + \equiv$$

```
public :: msg_banner
```

$$\langle \textit{Diagnostics: procedures} \rangle + \equiv$$

```

subroutine msg_banner (unit)
    integer, intent(in), optional :: unit
    integer :: n_proc
    call message_print (0, "|=====|")
    call message_print (0, "|")
    call message_print (0, "|      WW              WW  WW  WW  WW  WWWWWW      WW      WWWWW  WWWW")
    call message_print (0, "|      WW      WW      WW  WW  WW  WW      WW      WWWW  WW  WW  WW")
    call message_print (0, "|      WW  WW  WW  WW      WWWWWWW  WW      WW      WW  WW  WWWWW  WW")
    call message_print (0, "|      WWWW  WWWW      WW  WW  WW  WW      WWWWWWWW  WW  WW  WW")
    call message_print (0, "|      WW      WW      WW  WW  WW  WWWWWW  WW      WW  WW  WW  WWWW")
    call message_print (0, "|")
    call message_print (0, "|")
    call message_print (0, "|")
    call message_print (0, "|")

```



```

<Diagnostics: public>+≡
    public :: logfile_init
<Diagnostics: procedures>+≡
    subroutine logfile_init (filename)
        type(string_t), intent(in) :: filename
        call msg_message ("Writing log to '" // char (filename) // "'")
        log_unit = free_unit ()
        open (file = char (filename), unit = log_unit, &
            action = "write", status = "replace")
    end subroutine logfile_init

<Diagnostics: public>+≡
    public :: logfile_final
<Diagnostics: procedures>+≡
    subroutine logfile_final ()
        if (log_unit >= 0) then
            close (log_unit)
            log_unit = -1
        end if
    end subroutine logfile_final

```

This returns the valid logfile unit only if the default is write to screen, and if logfile is not set false.

```

<Diagnostics: public>+≡
    public :: logfile_unit
<Diagnostics: procedures>+≡
    function logfile_unit (unit, logfile)
        integer :: logfile_unit
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: logfile
        if (present (unit)) then
            if (unit == stdout) then
                logfile_unit = log_unit
            else
                logfile_unit = -1
            end if
        else if (present (logfile)) then
            if (logfile) then
                logfile_unit = log_unit
            else
                logfile_unit = -1
            end if
        else
            logfile_unit = log_unit
        end if
    end function logfile_unit

```

2.8.2 Checking values

The `expect` function does not just check a value for correctness (actually, it checks if a logical expression is true); it records its result here. If failures are

present when the program terminates, the exit code is nonzero.

```

<Diagnostics: variables>+≡
    integer, save :: expect_total = 0
    integer, save :: expect_failures = 0

<Diagnostics: public>+≡
    public :: expect_record

<Diagnostics: procedures>+≡
    subroutine expect_record (success)
        logical, intent(in) :: success
        expect_total = expect_total + 1
        if (.not. success) expect_failures = expect_failures + 1
    end subroutine expect_record

<Diagnostics: public>+≡
    public :: expect_clear

<Diagnostics: procedures>+≡
    subroutine expect_clear ()
        expect_total = 0
        expect_failures = 0
    end subroutine expect_clear

<Diagnostics: public>+≡
    public :: expect_summary

<Diagnostics: procedures>+≡
    subroutine expect_summary (unit)
        integer, intent(in), optional :: unit
        if (expect_total /= 0) then
            call msg_message ("Summary of value checks:", unit)
            write (msg_buffer, "(2x,A,1x,I0,1x,A,1x,A,1x,I0)") &
                "Failures:", expect_failures, "/", "Total:", expect_total
            call msg_message (unit=unit)
        end if
    end subroutine expect_summary

```

Helpers for converting integers into strings with minimal length.

```

<Diagnostics: public>+≡
    public :: int2string
    public :: int2char

<Diagnostics: procedures>+≡
    pure function int2fixed (i) result (c)
        integer, intent(in) :: i
        character(200) :: c
        c = ""
        write (c, *) i
        c = adjustl (c)
    end function int2fixed

    pure function int2string (i) result (s)
        integer, intent(in) :: i

```

```

    type (string_t) :: s
    s = trim (int2fixed (i))
end function int2string

pure function int2char (i) result (c)
    integer, intent(in) :: i
    character(len (trim (int2fixed (i)))) :: c
    c = int2fixed (i)
end function int2char

```

Dito for reals.

```

<Diagnostics: public>+≡
    public :: real2string
    public :: real2char

<Diagnostics: interfaces>+≡
    interface real2string
        module procedure real2string_list, real2string_fmt
    end interface
    interface real2char
        module procedure real2char_list, real2char_fmt
    end interface

<Diagnostics: procedures>+≡
    pure function real2fixed (x, fmt) result (c)
        real(default), intent(in) :: x
        character(*), intent(in), optional :: fmt
        character(200) :: c
        c = ""
        write (c, *) x
        c = adjustl (c)
    end function real2fixed

    pure function real2fixed_fmt (x, fmt) result (c)
        real(default), intent(in) :: x
        character(*), intent(in) :: fmt
        character(200) :: c
        c = ""
        write (c, fmt) x
        c = adjustl (c)
    end function real2fixed_fmt

    pure function real2string_list (x) result (s)
        real(default), intent(in) :: x
        type(string_t) :: s
        s = trim (real2fixed (x))
    end function real2string_list

    pure function real2string_fmt (x, fmt) result (s)
        real(default), intent(in) :: x
        character(*), intent(in) :: fmt
        type(string_t) :: s
        s = trim (real2fixed_fmt (x, fmt))
    end function real2string_fmt

```

```

pure function real2char_list (x) result (c)
  real(default), intent(in) :: x
  character(len_trim (real2fixed (x))) :: c
  c = real2fixed (x)
end function real2char_list

pure function real2char_fmt (x, fmt) result (c)
  real(default), intent(in) :: x
  character(*), intent(in) :: fmt
  character(len_trim (real2fixed_fmt (x, fmt))) :: c
  c = real2fixed_fmt (x, fmt)
end function real2char_fmt

```

Ditto for complex values; we do not use the slightly ugly FORTRAN output form here but instead introduce our own.

```

<Diagnostics: public>+≡
  public :: cmplx2string
  ! Ifort and Portland seem to have problems with this -> temporarily disable it
  !   public :: cmplx2char

<Diagnostics: procedures>+≡
  pure function cmplx2string (x) result (s)
    complex(default), intent(in) :: x
    type(string_t) :: s
    s = real2string (real (x, default))
    if (aimag (x) /= 0) s = s // " + " // real2string (aimag (x)) // " I"
  end function cmplx2string

  pure function cmplx2char (x) result (c)
    complex(default), intent(in) :: x
    character(len (char (cmplx2string (x)))) :: c
    c = char (cmplx2string (x))
  end function cmplx2char

```

2.8.3 Signal handling

Killing the program by external signals may leave the files written by it in an undefined state. This can be avoided by catching signals and deferring program termination. Instead of masking only critical sections, we choose to mask signals globally (done in the main program) and terminate the program at predefined checkpoints only. Checkpoints are after each command, within the sampling function (so the program can be terminated after each event), and after each iteration in the phase-space generation algorithm.

Signal handling is done via a C interface to the `sigaction` system call. When a signal is raised that has been masked by the handler, the corresponding variable is set to the value of the signal. The variables are visible from the C signal handler.

The signal `SIGINT` is for keyboard interrupt (ctrl-C), `SIGTERM` is for system interrupt, e.g., at shutdown. The `SIGXCPU` and `SIGXFSZ` signals may be issued by batch systems.

```

<Diagnostics: public>+≡
  public :: wo_sigint

```

```

public :: wo_sigterm
public :: wo_sigxcpu
public :: wo_sigxfsz

```

```

⟨Diagnostics: variables⟩+≡
integer(c_int), bind(C), volatile :: wo_sigint = 0
integer(c_int), bind(C), volatile :: wo_sigterm = 0
integer(c_int), bind(C), volatile :: wo_sigxcpu = 0
integer(c_int), bind(C), volatile :: wo_sigxfsz = 0

```

Here are the interfaces to the C functions. The routine `mask_term_signals` forces termination signals to be delayed. `release_term_signals` restores normal behavior. However, the program can be terminated anytime by calling `terminate_now_if_signal` which inspects the signals and terminates the program if requested..

```

⟨Diagnostics: public⟩+≡
public :: mask_term_signals

⟨Diagnostics: procedures⟩+≡
subroutine mask_term_signals ()
integer(c_int) :: status
logical :: ok
wo_sigint = 0
ok = wo_mask_sigint () == 0
if (.not. ok) call msg_error ("Masking SIGINT failed")
wo_sigterm = 0
ok = wo_mask_sigterm () == 0
if (.not. ok) call msg_error ("Masking SIGTERM failed")
wo_sigxcpu = 0
ok = wo_mask_sigxcpu () == 0
if (.not. ok) call msg_error ("Masking SIGXCPU failed")
wo_sigxfsz = 0
ok = wo_mask_sigxfsz () == 0
if (.not. ok) call msg_error ("Masking SIGXFSZ failed")
end subroutine mask_term_signals

```

```

⟨Diagnostics: interfaces⟩+≡
interface
integer(c_int) function wo_mask_sigint () bind(C)
import
end function wo_mask_sigint
end interface
interface
integer(c_int) function wo_mask_sigterm () bind(C)
import
end function wo_mask_sigterm
end interface
interface
integer(c_int) function wo_mask_sigxcpu () bind(C)
import
end function wo_mask_sigxcpu
end interface
interface

```

```

        integer(c_int) function wo_mask_sigxfsz () bind(C)
        import
    end function wo_mask_sigxfsz
end interface

<Diagnostics: public>+≡
    public :: release_term_signals

<Diagnostics: procedures>+≡
    subroutine release_term_signals ()
        integer(c_int) :: status
        logical :: ok
        ok = wo_release_sigint () == 0
        if (.not. ok) call msg_error ("Releasing SIGINT failed")
        ok = wo_release_sigterm () == 0
        if (.not. ok) call msg_error ("Releasing SIGTERM failed")
        ok = wo_release_sigxcpu () == 0
        if (.not. ok) call msg_error ("Releasing SIGXCPU failed")
        ok = wo_release_sigxfsz () == 0
        if (.not. ok) call msg_error ("Releasing SIGXFSZ failed")
    end subroutine release_term_signals

<Diagnostics: interfaces>+≡
    interface
        integer(c_int) function wo_release_sigint () bind(C)
        import
    end function wo_release_sigint
    end interface
    interface
        integer(c_int) function wo_release_sigterm () bind(C)
        import
    end function wo_release_sigterm
    end interface
    interface
        integer(c_int) function wo_release_sigxcpu () bind(C)
        import
    end function wo_release_sigxcpu
    end interface
    interface
        integer(c_int) function wo_release_sigxfsz () bind(C)
        import
    end function wo_release_sigxfsz
    end interface

<Diagnostics: public>+≡
    public :: terminate_now_if_signal

<Diagnostics: procedures>+≡
    subroutine terminate_now_if_signal ()
        if (wo_sigint /= 0) then
            call msg_terminate ("Signal SIGINT (keyboard interrupt) received.", &
                quit_code=int (wo_sigint))
        else if (wo_sigterm /= 0) then
            call msg_terminate ("Signal SIGTERM (termination signal) received.", &

```

```

        quit_code=int (wo_sigterm))
    else if (wo_sigxcpu /= 0) then
        call msg_terminate ("Signal SIGXCPU (CPU time limit exceeded) received.", &
            quit_code=int (wo_sigxcpu))
    else if (wo_sigxfsz /= 0) then
        call msg_terminate ("Signal SIGXFSZ (file size limit exceeded) received.", &
            quit_code=int (wo_sigxfsz))
    end if
end subroutine terminate_now_if_signal

```

2.9 C wrapper for sigaction

This implements calls to `sigaction` and the appropriate signal handlers in C.

```

<signal_interface.c>≡
/*
<File header>
*/
#include <signal.h>
#include <stdlib.h>

extern int wo_sigint;
extern int wo_sigterm;
extern int wo_sigxcpu;
extern int wo_sigxfsz;

static void wo_handler_sigint (int sig) {
    wo_sigint = sig;
}

static void wo_handler_sigterm (int sig) {
    wo_sigterm = sig;
}

static void wo_handler_sigxcpu (int sig) {
    wo_sigxcpu = sig;
}

static void wo_handler_sigxfsz (int sig) {
    wo_sigxfsz = sig;
}

int wo_mask_sigint () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = wo_handler_sigint;
    return sigaction(SIGINT, &sa, NULL);
}

```

```

int wo_mask_sigterm () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = wo_handler_sigterm;
    return sigaction(SIGTERM, &sa, NULL);
}

int wo_mask_sigxcpu () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = wo_handler_sigxcpu;
    return sigaction(SIGXCPU, &sa, NULL);
}

int wo_mask_sigxfsz () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = wo_handler_sigxfsz;
    return sigaction(SIGXFSZ, &sa, NULL);
}

int wo_release_sigint () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = SIG_DFL;
    return sigaction(SIGINT, &sa, NULL);
}

int wo_release_sigterm () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = SIG_DFL;
    return sigaction(SIGTERM, &sa, NULL);
}

int wo_release_sigxcpu () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);

```



```

    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = SIG_DFL;
    return sigaction(SIGXCPU, &sa, NULL);
}

int wo_release_sigxfsz () {
    struct sigaction sa;
    sigset_t blocks;
    sigfillset (&blocks);
    sa.sa_flags = 0;
    sa.sa_mask = blocks;
    sa.sa_handler = SIG_DFL;
    return sigaction(SIGXFSZ, &sa, NULL);
}

```

2.10 C wrapper for printf

The `printf` family of functions is implemented in C with an undefined number of arguments. This is not supported by the `bind(C)` interface. We therefore write wrappers for the versions of `sprintf` that we will actually use.

```

⟨sprintf_interface.c⟩≡
/*
  ⟨File header⟩
*/
#include <stdio.h>

int sprintf_none(char* str, const char* format) {
    return sprintf(str, format);
}

int sprintf_int(char* str, const char* format, int val) {
    return sprintf(str, format, val);
}

int sprintf_double(char* str, const char* format, double val) {
    return sprintf(str, format, val);
}

int sprintf_str(char* str, const char* format, const char* val) {
    return sprintf(str, format, val);
}

⟨sprintf interfaces⟩≡
interface
    function sprintf_none (str, fmt) result (stat) bind(C)
        use iso_c_binding !NODEP!
        integer(c_int) :: stat
        character(c_char), dimension(*), intent(inout) :: str
        character(c_char), dimension(*), intent(in) :: fmt
    end function sprintf_none
end interface

```

```

interface
  function sprintf_int (str, fmt, val) result (stat) bind(C)
    use iso_c_binding !NODEP!
    integer(c_int) :: stat
    character(c_char), dimension(*), intent(inout) :: str
    character(c_char), dimension(*), intent(in) :: fmt
    integer(c_int), value :: val
  end function sprintf_int
end interface

interface
  function sprintf_double (str, fmt, val) result (stat) bind(C)
    use iso_c_binding !NODEP!
    integer(c_int) :: stat
    character(c_char), dimension(*), intent(inout) :: str
    character(c_char), dimension(*), intent(in) :: fmt
    real(c_double), value :: val
  end function sprintf_double
end interface

interface
  function sprintf_str(str, fmt, val) result (stat) bind(C)
    use iso_c_binding !NODEP!
    integer(c_int) :: stat
    character(c_char), dimension(*), intent(inout) :: str
    character(c_char), dimension(*), intent(in) :: fmt
    character(c_char), dimension(*), intent(in) :: val
  end function sprintf_str
end interface

```

2.11 Interface for formatted I/O

For access to formatted printing (possibly input), we interface the C `printf` family of functions. There are two important issues here:

1. `printf` takes an arbitrary number of arguments, relying on the C stack. This is not interoperable. We interface it with C wrappers that output a single integer, real or string and restrict the allowed formats accordingly.
2. Restricting format strings is essential also for preventing format string attacks. Allowing arbitrary format string would create a real security hole in a Fortran program.
3. The string returned by `sprintf` must be allocated to the right size.

`<formats.f90>`≡
<File header>

```

module formats

  use iso_c_binding !NODEP!

```

```

    <Use kinds>
    <Use strings>
    <Use file utils>
        use diagnostics !NODEP!

    <Standard module head>

    <Formats: public>

    <Formats: parameters>

    <Formats: types>

    <Formats: interfaces>

contains

    <Formats: procedures>

end module formats

```

2.11.1 Parsing a C format string

The C format string contains characters and format conversion specifications. The latter are initiated by a % sign. If the next letter is also a %, a percent sign is printed and no conversion is done. Otherwise, a conversion is done and applied to the next argument in the argument list. First comes an optional flag (#, 0, -, +, or space), an optional field width (decimal digits starting not with zero), an optional precision (period, then another decimal digit string), a length modifier (irrelevant for us, therefore not supported), and a conversion specifier: **d** or **i** for integer; **e**, **f**, **g** (also upper case) for double-precision real, **s** for a string.

We explicitly exclude all other conversion specifiers, and we check the specifiers against the actual arguments.

A type for passing arguments

This is a polymorphic type that can hold integer, real (double), and string arguments.

```

<Formats: parameters>≡
    integer, parameter :: ARGTYPE_NONE = 0
    integer, parameter :: ARGTYPE_LOG = 1
    integer, parameter :: ARGTYPE_INT = 2
    integer, parameter :: ARGTYPE_REAL = 3
    integer, parameter :: ARGTYPE_STR = 4

```

The integer and real entries are actually scalars, but we avoid relying on the allocatable-scalar feature and make them one-entry arrays. The character entry is a real array which is a copy of the string.

Logical values are mapped to strings (true or false), so this type parameter value is mostly unused.

```

<Formats: public>≡
    public :: sprintf_arg_t

```

```

<Formats: types>≡
type :: sprintf_arg_t
private
integer :: type = ARGTYPE_NONE
integer(c_int), dimension(:), allocatable :: ival
real(c_double), dimension(:), allocatable :: rval
character(c_char), dimension(:), allocatable :: sval
end type sprintf_arg_t

<Formats: public>+≡
public :: sprintf_arg_init

<Formats: interfaces>≡
interface sprintf_arg_init
module procedure sprintf_arg_init_log
module procedure sprintf_arg_init_int
module procedure sprintf_arg_init_real
module procedure sprintf_arg_init_str
end interface

<Formats: procedures>≡
subroutine sprintf_arg_init_log (arg, lval)
type(sprintf_arg_t), intent(out) :: arg
logical, intent(in) :: lval
arg%type = ARGTYPE_STR
if (lval) then
allocate (arg%sval (5))
arg%sval = (/ 't', 'r', 'u', 'e', c_null_char /)
else
allocate (arg%sval (6))
arg%sval = (/ 'f', 'a', 'l', 's', 'e', c_null_char /)
end if
end subroutine sprintf_arg_init_log

subroutine sprintf_arg_init_int (arg, ival)
type(sprintf_arg_t), intent(out) :: arg
integer, intent(in) :: ival
arg%type = ARGTYPE_INT
allocate (arg%ival (1))
arg%ival = ival
end subroutine sprintf_arg_init_int

subroutine sprintf_arg_init_real (arg, rval)
type(sprintf_arg_t), intent(out) :: arg
real(default), intent(in) :: rval
arg%type = ARGTYPE_REAL
allocate (arg%rval (1))
arg%rval = rval
end subroutine sprintf_arg_init_real

subroutine sprintf_arg_init_str (arg, sval)
type(sprintf_arg_t), intent(out) :: arg
type(string_t), intent(in) :: sval
integer :: i

```

```

arg%type = ARGTYPE_STR
allocate (arg%sval (len (sval) + 1))
do i = 1, len (sval)
    arg%sval(i) = extract (sval, i, i)
end do
arg%sval(len (sval) + 1) = c_null_char
end subroutine sprintf_arg_init_str

```

(Formats: procedures)+≡

```

subroutine sprintf_arg_write (arg, unit)
    type(sprintf_arg_t), intent(in) :: arg
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit)
    select case (arg%type)
    case (ARGTYPE_NONE)
        write (u, *) "[none]"
    case (ARGTYPE_INT)
        write (u, "(1x,A,1x)", advance = "no") "[int]"
        write (u, *) arg%ival
    case (ARGTYPE_REAL)
        write (u, "(1x,A,1x)", advance = "no") "[real]"
        write (u, *) arg%rval
    case (ARGTYPE_STR)
        write (u, "(1x,A,1x,A)", advance = "no") "[string]", ''
        write (u, *) arg%rval, ''
    end select
end subroutine sprintf_arg_write

```

Return an upper bound for the length of the printed version; in case of strings the result is exact.

(Formats: procedures)+≡

```

elemental function sprintf_arg_get_length (arg) result (length)
    integer :: length
    type(sprintf_arg_t), intent(in) :: arg
    select case (arg%type)
    case (ARGTYPE_INT)
        length = log10 (real (huge (arg%ival(1)))) + 2
    case (ARGTYPE_REAL)
        length = log10 (real (radix (arg%rval(1))) ** digits (arg%rval(1))) + 8
    case (ARGTYPE_STR)
        length = size (arg%sval)
    case default
        length = 0
    end select
end function sprintf_arg_get_length

```

(Formats: procedures)+≡

```

subroutine sprintf_arg_apply_printf (arg, fmt, result, actual_length)
    type(sprintf_arg_t), intent(in) :: arg
    character(c_char), dimension(:), intent(in) :: fmt
    character(c_char), dimension(:), intent(inout) :: result
    integer, intent(out) :: actual_length

```

```

integer(c_int) :: ival
real(c_double) :: rval
select case (arg%type)
case (ARGTYPE_NONE)
    actual_length = sprintf_none (result, fmt)
case (ARGTYPE_INT)
    ival = arg%ival(1)
    actual_length = sprintf_int (result, fmt, ival)
case (ARGTYPE_REAL)
    rval = arg%rval(1)
    actual_length = sprintf_double (result, fmt, rval)
case (ARGTYPE_STR)
    actual_length = sprintf_str (result, fmt, arg%sval)
case default
    call msg_bug ("sprintf_arg_apply_sprintf called with illegal type")
end select
if (actual_length < 0) then
    write (msg_buffer, *) "Format: '", fmt, "'"
    call msg_message ()
    write (msg_buffer, *) "Output: '", result, "'"
    call msg_message ()
    call msg_error ("I/O error in sprintf call")
    actual_length = 0
end if
end subroutine sprintf_arg_apply_sprintf

```

Container type for the output

There is a procedure which chops the format string into pieces that contain at most one conversion specifier. Pairing this with a `sprintf_arg` object, we get the actual input to the `sprintf` interface. The type below holds this input and can allocate the output string.

(Formats: types)+≡

```

type :: sprintf_interface_t
private
character(c_char), dimension(:), allocatable :: input_fmt
type(sprintf_arg_t) :: arg
character(c_char), dimension(:), allocatable :: output_str
integer :: output_str_len = 0
end type sprintf_interface_t

```

(Formats: procedures)+≡

```

subroutine sprintf_interface_init (intf, fmt, arg)
type(sprintf_interface_t), intent(out) :: intf
type(string_t), intent(in) :: fmt
type(sprintf_arg_t), intent(in) :: arg
integer :: fmt_len, i
fmt_len = len (fmt)
allocate (intf%input_fmt (fmt_len + 1))
do i = 1, fmt_len
    intf%input_fmt(i) = extract (fmt, i, i)
end do

```

```

    intf%input_fmt(fmt_len+1) = c_null_char
    intf%arg = arg
    allocate (intf%output_str (len (fmt) + sprintf_arg_get_length (arg) + 1))
end subroutine sprintf_interface_init

```

<Formats: procedures>+≡

```

subroutine sprintf_interface_write (intf, unit)
  type(sprintf_interface_t), intent(in) :: intf
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit)
  write (u, *) "Format string = ", "'", intf%input_fmt, "'"
  write (u, "(1x,A,1x)", advance = "no") "Argument = "
  call sprintf_arg_write (intf%arg, unit)
  if (intf%output_str_len > 0) then
    write (u, *) "Result string = ", &
      "'", intf%output_str (1:intf%output_str_len), "'"
  end if
end subroutine sprintf_interface_write

```

Return the output string:

<Formats: procedures>+≡

```

function sprintf_interface_get_result (intf) result (string)
  type(string_t) :: string
  type(sprintf_interface_t), intent(in) :: intf
  character(kind = c_char, len = max (intf%output_str_len, 0)) :: buffer
  integer :: i
  if (intf%output_str_len > 0) then
    do i = 1, intf%output_str_len
      buffer(i:i) = intf%output_str(i)
    end do
    string = buffer(1:intf%output_str_len)
  else
    string = ""
  end if
end function sprintf_interface_get_result

```

<Formats: procedures>+≡

```

subroutine sprintf_interface_apply_sprintf (intf)
  type(sprintf_interface_t), intent(inout) :: intf
  call sprintf_arg_apply_sprintf &
    (intf%arg, intf%input_fmt, intf%output_str, intf%output_str_len)
end subroutine sprintf_interface_apply_sprintf

```

Import the interfaces defined in the previous section:

<Formats: interfaces>+≡

<sprintf interfaces>

Scan the format string

Chop it into pieces that contain one conversion specifier each. The zero-th piece contains the part before the first specifier. Check the specifiers and allow only the subset that we support. Also check for an exact match between conversion specifiers and input arguments. The result is an allocated array of `sprintf_interface` object; each one contains a piece of the format string and the corresponding argument.

(Formats: procedures)+≡

```
subroutine chop_and_check_format_string (fmt, arg, intf)
  type(string_t), intent(in) :: fmt
  type(sprintf_arg_t), dimension(:), intent(in) :: arg
  type(sprintf_interface_t), dimension(:), intent(out), allocatable :: intf
  integer :: n_args, i
  type(string_t), dimension(:), allocatable :: split_fmt
  type(string_t) :: word, buffer, separator
  integer :: pos, length, l
  logical :: ok
  type(sprintf_arg_t) :: arg_null
  ok = .true.
  length = 0
  n_args = size (arg)
  allocate (split_fmt (0:n_args))
  split_fmt = ""
  buffer = fmt
  SCAN_ARGS: do i = 1, n_args
    FIND_CONVERSION: do
      call split (buffer, word, "%", separator=separator)
      if (separator == "") then
        call msg_message (''' // char (fmt) // ''')
        call msg_error ("C-formatting string: " &
          // "too few conversion specifiers in format string")
        ok = .false.; exit SCAN_ARGS
      end if
      split_fmt(i-1) = split_fmt(i-1) // word
      if (extract (buffer, 1, 1) /= "%") then
        split_fmt(i) = "%"
        exit FIND_CONVERSION
      else
        split_fmt(i-1) = split_fmt(i-1) // "%"
      end if
    end do FIND_CONVERSION
    pos = verify (buffer, "#0-+ ") ! Flag characters (zero or more)
    split_fmt(i) = split_fmt(i) // extract (buffer, 1, pos-1)
    buffer = remove (buffer, 1, pos-1)
    pos = verify (buffer, "123456890") ! Field width
    word = extract (buffer, 1, pos-1)
    if (len (word) /= 0) then
      call read_int_from_string (word, len (word), 1)
      length = length + 1
    end if
    split_fmt(i) = split_fmt(i) // word
    buffer = remove (buffer, 1, pos-1)
    if (extract (buffer, 1, 1) == ".") then
```



```

        buffer = remove (buffer, 1, 1)
        pos = verify (buffer, "1234567890") ! Precision
        split_fmt(i) = split_fmt(i) // "." // extract (buffer, 1, pos-1)
        buffer = remove (buffer, 1, pos-1)
    end if
    ! Length modifier would come here, but is not allowed
    select case (char (extract (buffer, 1, 1))) ! conversion specifier
    case ("d", "i")
        if (arg(i)%type /= ARGTYPE_INT) then
            call msg_message ('"' // char (fmt) // '"')
            call msg_error ("C-formatting string: " &
                // "argument type mismatch: integer value expected")
            ok = .false.; exit SCAN_ARGS
        end if
    case ("e", "E", "f", "F", "g", "G")
        if (arg(i)%type /= ARGTYPE_REAL) then
            call msg_message ('"' // char (fmt) // '"')
            call msg_error ("C-formatting string: " &
                // "argument type mismatch: real value expected")
            ok = .false.; exit SCAN_ARGS
        end if
    case ("s")
        if (arg(i)%type /= ARGTYPE_STR) then
            call msg_message ('"' // char (fmt) // '"')
            call msg_error ("C-formatting string: " &
                // "argument type mismatch: logical or string value expected")
            ok = .false.; exit SCAN_ARGS
        end if
    case default
        call msg_message ('"' // char (fmt) // '"')
        call msg_error ("C-formatting string: " &
            // "illegal or incomprehensible conversion specifier")
        ok = .false.; exit SCAN_ARGS
    end select
    split_fmt(i) = split_fmt(i) // extract (buffer, 1, 1)
    buffer = remove (buffer, 1, 1)
end do SCAN_ARGS
if (ok) then
    FIND_EXTRA_CONVERSION: do
        call split (buffer, word, "%", separator=separator)
        split_fmt(n_args) = split_fmt(n_args) // word // separator
        if (separator == "") exit FIND_EXTRA_CONVERSION
        if (extract (buffer, 1, 1) == "%") then
            split_fmt(n_args) = split_fmt(n_args) // "%"
            buffer = remove (buffer, 1, 1)
        else
            call msg_message ('"' // char (fmt) // '"')
            call msg_error ("C-formatting string: " &
                // "too many conversion specifiers in format string")
            ok = .false.; exit FIND_EXTRA_CONVERSION
        end if
    end do FIND_EXTRA_CONVERSION
    split_fmt(n_args) = split_fmt(n_args) // buffer
    allocate (intf (0:n_args))

```

```

        call sprintf_interface_init (intf(0), split_fmt(0), arg_null)
        do i = 1, n_args
            call sprintf_interface_init (intf(i), split_fmt(i), arg(i))
        end do
    else
        allocate (intf (0))
    end if
contains
    subroutine read_int_from_string (word, length, l)
        type(string_t), intent(in) :: word
        integer, intent(in) :: length
        integer, intent(out) :: l
        character(len=length) :: buffer
        buffer = word
        read (buffer, *) l
    end subroutine read_int_from_string
end subroutine chop_and_check_format_string

```

2.11.2 API

<Formats: public>+≡

```
public :: sprintf
```

<Formats: procedures>+≡

```

function sprintf (fmt, arg) result (string)
    type(string_t) :: string
    type(string_t), intent(in) :: fmt
    type(sprintf_arg_t), dimension(:), intent(in) :: arg
    type(sprintf_interface_t), dimension(:), allocatable :: intf
    integer :: i
    string = ""
    call chop_and_check_format_string (fmt, arg, intf)
    if (size (intf) > 0) then
        do i = 0, ubound (intf, 1)
            call sprintf_interface_apply sprintf (intf(i))
            string = string // sprintf_interface_get_result (intf(i))
        end do
    end if
end function sprintf

```

2.11.3 Test

<Formats: public>+≡

```
public :: format_test
```

<Formats: procedures>+≡

```

subroutine format_test ()
    print *, "*** 1. Test: a string ***"
    call test_run (var_str("%s"), 1, (/ 4 /), (/ 'abcdefghij' /))
    print *, "*** 2. Test: two integers ***"
    call test_run (var_str("%d,%d"), 2, (/ 2, 2 /), (/ '42', '13' /))
    print *, "*** 3. Test: floating point number ***"

```

```

call test_run (var_str("%.4f"), 1, (/ 3 /), (/ '42567.12345' /))
print *, "*** 4. Test: general expression ***"
call test_run (var_str("%g"), 1, (/ 3 /), (/ '3.1415' /))
contains
  subroutine test_run (fmt, n_args, type, buffer)
    type(string_t), intent(in) :: fmt
    integer, intent(in) :: n_args
    logical :: lval
    integer :: ival
    real(default) :: rval
    integer :: i
    type(string_t) :: string
    type(sprintf_arg_t), dimension(:), allocatable :: arg
    integer, dimension(n_args), intent(in) :: type
    character(*), dimension(n_args), intent(in) :: buffer
    print *, "Format string:", char(fmt)
    print *, "Number of args:", n_args
    allocate (arg (n_args))
    do i = 1, n_args
      print *, "Argument (type ) = ", type(i)
      select case (type(i))
        case (ARGTYPE_LOG)
          read (buffer(i), *) lval
          call sprintf_arg_init (arg(i), lval)
        case (ARGTYPE_INT)
          read (buffer(i), *) ival
          call sprintf_arg_init (arg(i), ival)
        case (ARGTYPE_REAL)
          read (buffer(i), *) rval
          call sprintf_arg_init (arg(i), rval)
        case (ARGTYPE_STR)
          call sprintf_arg_init (arg(i), var_str (trim (buffer(i))))
      end select
    end do
    string = sprintf (fmt, arg)
    print *, "Result: '", char (string), "'"
    deallocate (arg)
  end subroutine test_run
end subroutine format_test

```

2.12 Bytes and such

In a few instances we will need the notion of a byte (8-bit) and a word (32 bit), even a 64-bit word. A block of 512 bit is also needed (for MD5).

We rely on integers up to 64 bit being supported by the processor. The main difference to standard integers is the interpretation as unsigned integers.

```

(bytes.f90)≡
  <File header>

```

```

  module bytes

```

```

    use kinds, only: i8, i32, i64 !NODEP!
    <Use file utils>

    <Standard module head>

    <Bytes: public>

    <Bytes: types>

    <Bytes: parameters>

    <Bytes: interfaces>

contains

    <Bytes: procedures>

end module bytes

```

2.12.1 8-bit words: bytes

This is essentially a wrapper around 8-bit integers. The wrapper emphasises their special interpretation as a sequence of bits. However, we interpret bytes as unsigned integers.

```

<Bytes: public>≡
    public :: byte_t

<Bytes: types>≡
    type :: byte_t
    private
        integer(i8) :: i
    end type byte_t

<Bytes: public>+≡
    public :: byte_zero

<Bytes: parameters>≡
    type(byte_t), parameter :: byte_zero = byte_t (0_i8)

```

Set a byte from 8-bit integer:

```

<Bytes: public>+≡
    public :: assignment(=)

<Bytes: interfaces>≡
    interface assignment(=)
        module procedure set_byte_from_i8
    end interface

<Bytes: procedures>≡
    subroutine set_byte_from_i8 (b, i)
        type(byte_t), intent(out) :: b
        integer(i8), intent(in) :: i
        b%i = i
    end subroutine set_byte_from_i8

```

Write a byte in one of two formats: either as a hexadecimal number (two digits, default) or as a decimal number (one to three digits). The decimal version is nontrivial because bytes are unsigned integers. Optionally append a newline.

```

<Bytes: public>+≡
    public :: byte_write

<Bytes: interfaces>+≡
    interface byte_write
        module procedure byte_write_unit, byte_write_string
    end interface

<Bytes: procedures>+≡
    subroutine byte_write_unit (b, unit, decimal, newline)
        type(byte_t), intent(in), optional :: b
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: decimal, newline
        logical :: dc, nl
        type(word32_t) :: w
        integer :: u
        u = output_unit (unit); if (u < 0) return
        dc = .false.; if (present (decimal)) dc = decimal
        nl = .false.; if (present (newline)) nl = newline
        if (dc) then
            w = b
            write (u, '(I3)', advance='no') w%i
        else
            write (u, '(z2.2)', advance='no') b%i
        end if
        if (nl) write (u, *)
    end subroutine byte_write_unit

```

The string version is hex-only

```

<Bytes: procedures>+≡
    subroutine byte_write_string (b, s)
        type(byte_t), intent(in) :: b
        character(len=2), intent(inout) :: s
        write (s, '(z2.2)') b%i
    end subroutine byte_write_string

```

2.12.2 32-bit words

This is not exactly a 32-bit integer. A word is to be filled with bytes, and it may be partially filled. The filling is done lowest-byte first, highest-byte last. We count the bits, so `fill` should be either 0, 8, 16, 24, or 32. In printing words, we correspondingly distinguish between printing zeros and printing blanks.

```

<Bytes: public>+≡
    public :: word32_t

<Bytes: types>+≡
    type :: word32_t
        private
        integer(i32) :: i
        integer :: fill = 0

```

```
end type word32_t
```

Assignment: the word is filled by inserting a 32-bit integer

```

<Bytes: interfaces>+≡
  interface assignment(=)
    module procedure word32_set_from_i32
    module procedure word32_set_from_byte
  end interface
<Bytes: procedures>+≡
  subroutine word32_set_from_i32 (w, i)
    type(word32_t), intent(out) :: w
    integer(i32), intent(in) :: i
    w%i = i
    w%fill = 32
  end subroutine word32_set_from_i32

```

Filling with a 8-bit integer is slightly tricky, because in this interpretation integers are unsigned.

```

<Bytes: procedures>+≡
  subroutine word32_set_from_byte (w, b)
    type(word32_t), intent(out) :: w
    type(byte_t), intent(in) :: b
    if (b%i >= 0_i8) then
      w%i = b%i
    else
      w%i = 2_i32*(huge(0_i8)+1_i32) + b%i
    end if
    w%fill = 32
  end subroutine word32_set_from_byte

```

Check the fill status

```

<Bytes: public>+≡
  public :: word32_empty, word32_filled, word32_fill
<Bytes: procedures>+≡
  function word32_empty (w)
    type(word32_t), intent(in) :: w
    logical :: word32_empty
    word32_empty = (w%fill == 0)
  end function word32_empty

  function word32_filled (w)
    type(word32_t), intent(in) :: w
    logical :: word32_filled
    word32_filled = (w%fill == 32)
  end function word32_filled

  function word32_fill (w)
    type(word32_t), intent(in) :: w
    integer :: word32_fill
    word32_fill = w%fill
  end function word32_fill

```

Partial assignment: append a byte to a partially filled word. (Note: no assignment if the word is filled, so check this before if necessary.)

```

<Bytes: public>+≡
    public :: word32_append_byte

<Bytes: procedures>+≡
    subroutine word32_append_byte (w, b)
        type(word32_t), intent(inout) :: w
        type(byte_t), intent(in) :: b
        type(word32_t) :: w1
        if (.not. word32_filled (w)) then
            w1 = b
            call mvbits (w1%i, 0, 8, w%i, w%fill)
            w%fill = w%fill + 8
        end if
    end subroutine word32_append_byte

```

Extract a byte from a word. The argument *i* is the position, which may be 0, 1, 2, or 3.

```

<Bytes: public>+≡
    public :: byte_from_word32

<Bytes: procedures>+≡
    function byte_from_word32 (w, i) result (b)
        type(word32_t), intent(in) :: w
        integer, intent(in) :: i
        type(byte_t) :: b
        integer(i32) :: j
        j = 0
        if (i >= 0 .and. i*8 < w%fill) then
            call mvbits (w%i, i*8, 8, j, 0)
        end if
        b%i = j
    end function byte_from_word32

```

Write a word to file or STDOUT. We understand words as unsigned integers, therefore we cannot use the built-in routine unchanged. However, we can make use of the existence of 64-bit integers and their output routine.

In hexadecimal format, the default version prints eight hex characters, highest-first. The **bytes** version prints four bytes (two-hex characters), lowest first, with spaces in-between. The decimal bytes version is analogous. In the **bytes** version, missing bytes are printed as whitespace.

```

<Bytes: public>+≡
    public :: word32_write

<Bytes: interfaces>+≡
    interface word32_write
        module procedure word32_write_unit
    end interface

<Bytes: procedures>+≡
    subroutine word32_write_unit (w, unit, bytes, decimal, newline)
        type(word32_t), intent(in) :: w
        integer, intent(in), optional :: unit

```

```

logical, intent(in), optional :: bytes, decimal, newline
logical :: dc, by, nl
type(word64_t) :: ww
integer :: i, u
u = output_unit (unit); if (u < 0) return
by = .false.; if (present (bytes)) by = bytes
dc = .false.; if (present (decimal)) dc = decimal
nl = .false.; if (present (newline)) nl = newline
if (by) then
  do i = 0, 3
    if (i>0) write (u, '(1x)', advance='no')
    if (8*i < w%fill) then
      call byte_write (byte_from_word32 (w, i), unit, decimal=decimal)
    else if (dc) then
      write (u, '(3x)', advance='no')
    else
      write (u, '(2x)', advance='no')
    end if
  end do
else if (dc) then
  ww = w
  write (u, '(I10)', advance='no') ww%i
else
  select case (w%fill)
  case ( 0)
  case ( 8); write (6, '(1x,z8.2)', advance='no') ibits (w%i, 0, 8)
  case (16); write (6, '(1x,z8.4)', advance='no') ibits (w%i, 0,16)
  case (24); write (6, '(1x,z8.6)', advance='no') ibits (w%i, 0,24)
  case (32); write (6, '(1x,z8.8)', advance='no') ibits (w%i, 0,32)
  end select
end if
if (nl) write (u, *)
end subroutine word32_write_unit

```

2.12.3 Operations on 32-bit words

Define the usual logical operations, as well as addition (mod 2^{32}). We assume that all operands are completely filled.

(Bytes: public) +=

```
public :: not, ior, ieor, iand, ishftc, operator(+)
```

(Bytes: interfaces) +=

```

interface not
  module procedure word_not
end interface
interface ior
  module procedure word_or
end interface
interface ieor
  module procedure word_eor
end interface
interface iand
  module procedure word_and

```



```

end interface
interface ishftc
  module procedure word_shftc
end interface
interface operator(+)
  module procedure word_add
end interface
<Bytes: procedures>+≡
function word_not (w1) result (w2)
  type(word32_t), intent(in) :: w1
  type(word32_t) :: w2
  w2 = not (w1%i)
end function word_not

function word_or (w1, w2) result (w3)
  type(word32_t), intent(in) :: w1, w2
  type(word32_t) :: w3
  w3 = ior (w1%i, w2%i)
end function word_or

function word_eor (w1, w2) result (w3)
  type(word32_t), intent(in) :: w1, w2
  type(word32_t) :: w3
  w3 = ieor (w1%i, w2%i)
end function word_eor

function word_and (w1, w2) result (w3)
  type(word32_t), intent(in) :: w1, w2
  type(word32_t) :: w3
  w3 = iand (w1%i, w2%i)
end function word_and

function word_shftc (w1, s) result (w2)
  type(word32_t), intent(in) :: w1
  integer, intent(in) :: s
  type(word32_t) :: w2
  w2 = ishftc (w1%i, s, 32)
end function word_shftc

function word_add (w1, w2) result (w3)
  type(word32_t), intent(in) :: w1, w2
  type(word32_t) :: w3
  w3 = w1%i + w2%i
end function word_add

```

2.12.4 64-bit words

These objects consist of two 32-bit words. They thus can hold integer numbers larger than 2^{32} (to be exact, 2^{31} since FORTRAN integers are signed). The order is low-word, high-word.

```

<Bytes: public>+≡
  public :: word64_t

```

```

<Bytes: types>+≡
  type :: word64_t
  private
    integer(i64) :: i
  end type word64_t

```

Set a 64 bit word:

```

<Bytes: interfaces>+≡
  interface assignment(=)
    module procedure word64_set_from_i64
    module procedure word64_set_from_word32
  end interface

<Bytes: procedures>+≡
  subroutine word64_set_from_i64 (ww, i)
    type(word64_t), intent(out) :: ww
    integer(i64), intent(in) :: i
    ww%i = i
  end subroutine word64_set_from_i64

```

Filling with a 32-bit word:

```

<Bytes: procedures>+≡
  subroutine word64_set_from_word32 (ww, w)
    type(word64_t), intent(out) :: ww
    type(word32_t), intent(in) :: w
    if (w%i >= 0_i32) then
      ww%i = w%i
    else
      ww%i = 2_i64*(huge(0_i32)+1_i64) + w%i
    end if
  end subroutine word64_set_from_word32

```

Extract a byte from a word. The argument *i* is the position, which may be between 0 and 7.

```

<Bytes: public>+≡
  public :: byte_from_word64, word32_from_word64

<Bytes: procedures>+≡
  function byte_from_word64 (ww, i) result (b)
    type(word64_t), intent(in) :: ww
    integer, intent(in) :: i
    type(byte_t) :: b
    integer(i64) :: j
    j = 0
    if (i >= 0 .and. i*8 < 64) then
      call mvbits (ww%i, i*8, 8, j, 0)
    end if
    b%i = j
  end function byte_from_word64

```

Extract a 32-bit word from a 64-bit word. The position is either 0 or 1.

```

<Bytes: procedures>+≡

```

```

function word32_from_word64 (ww, i) result (w)
  type(word64_t), intent(in) :: ww
  integer, intent(in) :: i
  type(word32_t) :: w
  integer(i64) :: j
  j = 0
  select case (i)
    case (0); call mvbits (ww%i, 0, 32, j, 0)
    case (1); call mvbits (ww%i, 32, 32, j, 0)
  end select
  w = int (j, kind=i32)
end function word32_from_word64

```

Print a 64-bit word. Decimal version works up to 2^{63} . The `words` version uses the 'word32' printout, separated by two spaces. The low-word is printed first. The `bytes` version also uses the 'word32' printout. This implies that the lowest byte is first. The default version prints a hexadecimal number without spaces, highest byte first.

<Bytes: public>+≡

```
public :: word64_write
```

<Bytes: interfaces>+≡

```

interface word64_write
  module procedure word64_write_unit
end interface

```

<Bytes: procedures>+≡

```

subroutine word64_write_unit (ww, unit, words, bytes, decimal, newline)
  type(word64_t), intent(in) :: ww
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: words, bytes, decimal, newline
  logical :: wo, by, dc, nl
  integer :: u
  u = output_unit (unit); if (u < 0) return
  wo = .false.; if (present (words)) wo = words
  by = .false.; if (present (bytes)) by = bytes
  dc = .false.; if (present (decimal)) dc = decimal
  nl = .false.; if (present (newline)) nl = newline
  if (wo .or. by) then
    call word32_write_unit (word32_from_word64 (ww, 0), unit, by, dc)
    write (u, '(2x)', advance='no')
    call word32_write_unit (word32_from_word64 (ww, 1), unit, by, dc)
  else if (dc) then
    write (u, '(I19)', advance='no') ww%i
  else
    write (u, '(Z16)', advance='no') ww%i
  end if
  if (nl) write (u, *)
end subroutine word64_write_unit

```

2.13 MD5 Checksums

It is a bit of an overkill, but implementing MD5 checksums allows us to check input/file integrity on the basis of a well-known standard. The building blocks have been introduced in the `bytes` module.

```
<md5.f90>≡  
<File header>  
  
module md5  
  
    use kinds, only: i8, i32, i64 !NODEP!  
<Use file utils>  
    use diagnostics !NODEP!  
    use bytes  
    use limits, only: LF, EOR, EOF !NODEP!  
  
<Standard module head>  
  
<MD5: public>  
  
<MD5: types>  
  
<MD5: variables>  
  
<MD5: interfaces>  
  
contains  
  
<MD5: procedures>  
  
end module md5
```

2.13.1 Blocks

A block is a sequence of 16 words (64 bytes or 512 bits). We anticipate that blocks will be linked, so include a pointer to the next block. There is a fill status (word counter), as there is one for each word. The fill status is equal to the number of bytes that are in, so it may be between 0 and 64.

```
<MD5: types>≡  
    type :: block_t  
        private  
        type(word32_t), dimension(0:15) :: w  
        type(block_t), pointer :: next => null ()  
        integer :: fill = 0  
    end type block_t
```

Check if a block is completely filled or empty:

```
<MD5: procedures>≡  
    function block_is_empty (b)  
        type(block_t), intent(in) :: b  
        logical :: block_is_empty  
        block_is_empty = (b%fill == 0 .and. word32_empty (b%w(0)))
```

```

end function block_is_empty

function block_is_filled (b)
    type(block_t), intent(in) :: b
    logical :: block_is_filled
    block_is_filled = (b%fill == 64)
end function block_is_filled

```

Append a single byte to a block. Works only if the block is not yet filled.

(MD5: procedures)+≡

```

subroutine block_append_byte (bl, by)
    type(block_t), intent(inout) :: bl
    type(byte_t), intent(in) :: by
    if (.not. block_is_filled (bl)) then
        call word32_append_byte (bl%w(bl%fill/4), by)
        bl%fill = bl%fill + 1
    end if
end subroutine block_append_byte

```

The printing routine allows for printing as sequences of words or bytes, decimal or hex.

(MD5: interfaces)≡

```

interface block_write
    module procedure block_write_unit
end interface

```

(MD5: procedures)+≡

```

subroutine block_write_unit (b, unit, bytes, decimal)
    type(block_t), intent(in) :: b
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: bytes, decimal
    logical :: by, dc
    integer :: i, u
    u = output_unit (unit); if (u < 0) return
    by = .false.; if (present (bytes)) by = bytes
    dc = .false.; if (present (decimal)) dc = decimal
    do i = 0, b%fill/4 - 1
        call newline_or_blank (u, i, by, dc)
        call word32_write (b%w(i), unit, bytes, decimal)
    end do
    if (.not. block_is_filled (b)) then
        i = b%fill/4
        if (.not. word32_empty (b%w(i))) then
            call newline_or_blank (u, i, by, dc)
            call word32_write (b%w(i), unit, bytes, decimal)
        end if
    end if
    write (u, *)
contains
    subroutine newline_or_blank (u, i, bytes, decimal)
        integer, intent(in) :: u, i
        logical, intent(in) :: bytes, decimal
        if (decimal) then

```

```

        select case (i)
        case (0)
        case (2,4,6,8,10,12,14); write (u, *)
        case default
            write (u, '(2x)', advance='no')
        end select
    else if (bytes) then
        select case (i)
        case (0)
        case (4,8,12); write (u, *)
        case default
            write (u, '(2x)', advance='no')
        end select
    else
        if (i == 8) write (u, *)
    end if
end subroutine newline_or_blank
end subroutine block_write_unit

```

2.13.2 Messages

A message (within this module) is a linked list of blocks.

(MD5: types)+≡

```

type :: message_t
private
type(block_t), pointer :: first => null ()
type(block_t), pointer :: last => null ()
integer :: n_blocks = 0
end type message_t

```

Clear the message list

(MD5: procedures)+≡

```

subroutine message_clear (m)
type(message_t), intent(inout) :: m
type(block_t), pointer :: b
nullify (m%last)
do
    b => m%first
    if (.not.(associated (b))) exit
    m%first => b%next
    deallocate (b)
end do
m%n_blocks = 0
end subroutine message_clear

```

Append an empty block to the message list

(MD5: procedures)+≡

```

subroutine message_append_new_block (m)
type(message_t), intent(inout) :: m
if (associated (m%last)) then
    allocate (m%last%next)

```

```

        m%last => m%last%next
        m%n_blocks = m%n_blocks + 1
    else
        allocate (m%first)
        m%last => m%first
        m%n_blocks = 1
    end if
end subroutine message_append_new_block

```

Initialize: clear and allocate the first (empty) block.

```

<MD5: procedures>+≡
subroutine message_init (m)
    type(message_t), intent(inout) :: m
    call message_clear (m)
    call message_append_new_block (m)
end subroutine message_init

```

Append a single byte to a message. If necessary, allocate a new block. If the message is empty, initialize it.

```

<MD5: procedures>+≡
subroutine message_append_byte (m, b)
    type(message_t), intent(inout) :: m
    type(byte_t), intent(in) :: b
    if (.not. associated (m%last)) then
        call message_init (m)
    else if (block_is_filled (m%last)) then
        call message_append_new_block (m)
    end if
    call block_append_byte (m%last, b)
end subroutine message_append_byte

```

Append zero bytes until the current block is filled up to the required position. If we are already beyond that, append a new block and fill that one.

```

<MD5: procedures>+≡
subroutine message_pad_zero (m, i)
    type(message_t), intent(inout) :: m
    integer, intent(in) :: i
    type(block_t), pointer :: b
    integer :: j
    if (associated (m%last)) then
        b => m%last
        if (b%fill > i) then
            do j = b%fill + 1, 64 + i
                call message_append_byte (m, byte_zero)
            end do
        else
            do j = b%fill + 1, i
                call message_append_byte (m, byte_zero)
            end do
        end if
    end if
end subroutine message_pad_zero

```

This returns the number of bits within a message. We need a 64-bit word for the result since it may be more than 2^{31} . This is also required by the MD5 standard.

(MD5: procedures)+≡

```
function message_bits (m) result (length)
  type(message_t), intent(in) :: m
  type(word64_t) :: length
  type(block_t), pointer :: b
  integer(i64) :: n_blocks_filled, n_bytes_extra
  if (m%n_blocks > 0) then
    b => m%last
    if (block_is_filled (b)) then
      n_blocks_filled = m%n_blocks
      n_bytes_extra = 0
    else
      n_blocks_filled = m%n_blocks - 1
      n_bytes_extra = b%fill
    end if
    length = n_blocks_filled * 512 + n_bytes_extra * 8
  else
    length = 0_i64
  end if
end function message_bits
```

2.13.3 Message I/O

Append the contents of a string to a message. We first cast the character string into a 8-bit integer array and then append this byte by byte.

(MD5: procedures)+≡

```
subroutine message_append_string (m, s)
  type(message_t), intent(inout) :: m
  character(len=*), intent(in) :: s
  integer(i64) :: i, n_bytes
  integer(i8), dimension(:), allocatable :: buffer
  integer(i8), dimension(1) :: mold
  type(byte_t) :: b
  n_bytes = size (transfer (s, mold))
  allocate (buffer (n_bytes))
  buffer = transfer (s, mold)
  do i = 1, size (buffer)
    b = buffer(i)
    call message_append_byte (m, b)
  end do
  deallocate (buffer)
end subroutine message_append_string
```

Append the contents of a 32-bit integer to a message. We first cast the 32-bit integer into a 8-bit integer array and then append this byte by byte.

(MD5: procedures)+≡

```
subroutine message_append_i32 (m, x)
```



```

type(message_t), intent(inout) :: m
integer(i32), intent(in) :: x
integer(i8), dimension(4) :: buffer
type(byte_t) :: b
integer :: i
buffer = transfer (x, buffer, size(buffer))
do i = 1, size (buffer)
    b = buffer(i)
    call message_append_byte (m, b)
end do
end subroutine message_append_i32

```

Append one line from file to a message. Include the newline character.

(MD5: procedures)+≡

```

!  subroutine message_append_from_unit (m, u, iostat)
!      type(message_t), intent(inout) :: m
!      integer, intent(in) :: u
!      integer, intent(out) :: iostat
!      character(len=BUFFER_SIZE) :: buffer
!      read (u, *, iostat=iostat) buffer
!      call message_append_string (m, trim (buffer))
!      call message_append_string (m, LF)
!  end subroutine message_append_from_unit

```

Fill a message from file. (Each line counts as a string.)

(MD5: procedures)+≡

```

!  subroutine message_read_from_file (m, f)
!      type(message_t), intent(inout) :: m
!      character(len=*), intent(in) :: f
!      integer :: u, iostat
!      u = free_unit ()
!      open (file=f, unit=u, action='read')
!      do
!          call message_append_from_unit (m, u, iostat=iostat)
!          if (iostat < 0) exit
!      end do
!      close (u)
!  end subroutine message_read_from_file

```

Write a message. After each block, insert an empty line.

(MD5: interfaces)+≡

```

interface message_write
    module procedure message_write_unit
end interface

```

(MD5: procedures)+≡

```

subroutine message_write_unit (m, unit, bytes, decimal)
    type(message_t), intent(in) :: m
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: bytes, decimal
    type(block_t), pointer :: b
    integer :: u
    u = output_unit (unit); if (u < 0) return

```

```

b => m%first
if (associated (b)) then
  do
    call block_write_unit (b, unit, bytes, decimal)
    b => b%next
    if (.not. associated (b)) exit
    write (u, *)
  end do
end if
end subroutine message_write_unit

```

2.13.4 Auxiliary functions

These four functions on three words are defined in the MD5 standard:

```

⟨MD5: procedures⟩+≡
function ff (x, y, z)
  type(word32_t), intent(in) :: x, y, z
  type(word32_t) :: ff
  ff = ior (iand (x, y), iand (not (x), z))
end function ff

function fg (x, y, z)
  type(word32_t), intent(in) :: x, y, z
  type(word32_t) :: fg
  fg = ior (iand (x, z), iand (y, not (z)))
end function fg

function fh (x, y, z)
  type(word32_t), intent(in) :: x, y, z
  type(word32_t) :: fh
  fh = ieor (ieor (x, y), z)
end function fh

function fi (x, y, z)
  type(word32_t), intent(in) :: x, y, z
  type(word32_t) :: fi
  fi = ieor (y, ior (x, not (z)))
end function fi

```

2.13.5 Auxiliary stuff

This defines and initializes the table of transformation constants:

```

⟨MD5: variables⟩≡
  type(word32_t), dimension(64), save :: t
  logical, save :: table_initialized = .false.

⟨MD5: procedures⟩+≡
  subroutine table_init
    type(word64_t) :: ww
    integer :: i
    if (.not.table_initialized) then

```

```

do i = 1, 64
  ww = int (4294967296d0 * abs (sin (i * 1d0)), kind=i64)
  t(i) = word32_from_word64 (ww, 0)
end do
table_initialized = .true.
end if
end subroutine table_init

```

This encodes the message digest (4 words) into a 32-character string.

(MD5: procedures)+≡

```

function digest_string (aa) result (s)
  type(word32_t), dimension (0:3), intent(in) :: aa
  character(len=32) :: s
  integer :: i, j
  do i = 0, 3
    do j = 0, 3
      call byte_write (byte_from_word32 (aa(i), j), s(i*8+j*2+1:i*8+j*2+2))
    end do
  end do
end function digest_string

```

2.13.6 MD5 algorithm

Pad the message with a byte x80 and then pad zeros up to a full block minus two words; in these words, insert the message length (before padding) as a 64-bit word, low-word first.

(MD5: procedures)+≡

```

subroutine message_pad (m)
  type(message_t), intent(inout) :: m
  type(word64_t) :: length
  integer(i8), parameter :: ipad = -128 ! z'80'
  type(byte_t) :: b
  integer :: i
  length = message_bits (m)
  b = ipad
  call message_append_byte (m, b)
  call message_pad_zero (m, 56)
  do i = 0, 7
    call message_append_byte (m, byte_from_word64 (length, i))
  end do
end subroutine message_pad

```

Apply a series of transformations onto a state a,b,c,d, where the transform function uses each word of the message together with the predefined words. Finally, encode the state as a 32-character string.

(MD5: procedures)+≡

```

subroutine message_digest (m, s)
  type(message_t), intent(in) :: m
  character(len=32), intent(out) :: s
  integer(i32), parameter :: ia = 1732584193 ! z'67452301'
  integer(i32), parameter :: ib = -271733879 ! z'efcdab89'

```

```

integer(i32), parameter :: ic = -1732584194 ! z'98badcfe'
integer(i32), parameter :: id = 271733878 ! z'10325476'
type(word32_t) :: a, b, c, d
type(word32_t) :: aa, bb, cc, dd
type(word32_t), dimension(0:15) :: x
type(block_t), pointer :: bl
call table_init
a = ia; b = ib; c = ic; d = id
bl => m%first
do
  if (.not.associated (bl)) exit
  x = bl%w
  aa = a; bb = b; cc = c; dd = d
  call transform (ff, a, b, c, d, 0, 7, 1)
  call transform (ff, d, a, b, c, 1, 12, 2)
  call transform (ff, c, d, a, b, 2, 17, 3)
  call transform (ff, b, c, d, a, 3, 22, 4)
  call transform (ff, a, b, c, d, 4, 7, 5)
  call transform (ff, d, a, b, c, 5, 12, 6)
  call transform (ff, c, d, a, b, 6, 17, 7)
  call transform (ff, b, c, d, a, 7, 22, 8)
  call transform (ff, a, b, c, d, 8, 7, 9)
  call transform (ff, d, a, b, c, 9, 12, 10)
  call transform (ff, c, d, a, b, 10, 17, 11)
  call transform (ff, b, c, d, a, 11, 22, 12)
  call transform (ff, a, b, c, d, 12, 7, 13)
  call transform (ff, d, a, b, c, 13, 12, 14)
  call transform (ff, c, d, a, b, 14, 17, 15)
  call transform (ff, b, c, d, a, 15, 22, 16)
  call transform (fg, a, b, c, d, 1, 5, 17)
  call transform (fg, d, a, b, c, 6, 9, 18)
  call transform (fg, c, d, a, b, 11, 14, 19)
  call transform (fg, b, c, d, a, 0, 20, 20)
  call transform (fg, a, b, c, d, 5, 5, 21)
  call transform (fg, d, a, b, c, 10, 9, 22)
  call transform (fg, c, d, a, b, 15, 14, 23)
  call transform (fg, b, c, d, a, 4, 20, 24)
  call transform (fg, a, b, c, d, 9, 5, 25)
  call transform (fg, d, a, b, c, 14, 9, 26)
  call transform (fg, c, d, a, b, 3, 14, 27)
  call transform (fg, b, c, d, a, 8, 20, 28)
  call transform (fg, a, b, c, d, 13, 5, 29)
  call transform (fg, d, a, b, c, 2, 9, 30)
  call transform (fg, c, d, a, b, 7, 14, 31)
  call transform (fg, b, c, d, a, 12, 20, 32)
  call transform (fh, a, b, c, d, 5, 4, 33)
  call transform (fh, d, a, b, c, 8, 11, 34)
  call transform (fh, c, d, a, b, 11, 16, 35)
  call transform (fh, b, c, d, a, 14, 23, 36)
  call transform (fh, a, b, c, d, 1, 4, 37)
  call transform (fh, d, a, b, c, 4, 11, 38)
  call transform (fh, c, d, a, b, 7, 16, 39)
  call transform (fh, b, c, d, a, 10, 23, 40)
  call transform (fh, a, b, c, d, 13, 4, 41)

```

```

call transform (fh, d, a, b, c, 0, 11, 42)
call transform (fh, c, d, a, b, 3, 16, 43)
call transform (fh, b, c, d, a, 6, 23, 44)
call transform (fh, a, b, c, d, 9, 4, 45)
call transform (fh, d, a, b, c, 12, 11, 46)
call transform (fh, c, d, a, b, 15, 16, 47)
call transform (fh, b, c, d, a, 2, 23, 48)
call transform (fi, a, b, c, d, 0, 6, 49)
call transform (fi, d, a, b, c, 7, 10, 50)
call transform (fi, c, d, a, b, 14, 15, 51)
call transform (fi, b, c, d, a, 5, 21, 52)
call transform (fi, a, b, c, d, 12, 6, 53)
call transform (fi, d, a, b, c, 3, 10, 54)
call transform (fi, c, d, a, b, 10, 15, 55)
call transform (fi, b, c, d, a, 1, 21, 56)
call transform (fi, a, b, c, d, 8, 6, 57)
call transform (fi, d, a, b, c, 15, 10, 58)
call transform (fi, c, d, a, b, 6, 15, 59)
call transform (fi, b, c, d, a, 13, 21, 60)
call transform (fi, a, b, c, d, 4, 6, 61)
call transform (fi, d, a, b, c, 11, 10, 62)
call transform (fi, c, d, a, b, 2, 15, 63)
call transform (fi, b, c, d, a, 9, 21, 64)
a = a + aa
b = b + bb
c = c + cc
d = d + dd
bl => bl%next
end do
s = digest_string ((/a, b, c, d/))
contains
<MD5: Internal subroutine transform>
end subroutine message_digest

```

And this is the actual transformation that depends on one of the previous functions, four words, and three integers. The implicit arguments are *x*, the word from the message to digest, and *t*, the entry in the predefined table.

```

<MD5: Internal subroutine transform>≡
subroutine transform (f, a, b, c, d, k, s, i)
interface
function f (x, y, z)
import word32_t
type(word32_t), intent(in) :: x, y, z
type(word32_t) :: f
end function f
end interface
type(word32_t), intent(inout) :: a
type(word32_t), intent(in) :: b, c, d
integer, intent(in) :: k, s, i
a = b + ishftc (a + f(b, c, d) + x(k) + t(i), s)
end subroutine transform

```

2.13.7 User interface

```
<MD5: public>≡  
public :: md5sum
```

```
<MD5: interfaces>+≡  
interface md5sum  
  module procedure md5sum_from_string  
  module procedure md5sum_from_unit  
end interface
```

This function computes the MD5 sum of the input string and returns it as a 32-character string

```
<MD5: procedures>+≡  
function md5sum_from_string (s) result (digest)  
  character(len=*), intent(in) :: s  
  character(len=32) :: digest  
  type(message_t) :: m  
  call message_append_string (m, s)  
  call message_pad (m)  
  call message_digest (m, digest)  
  call message_clear (m)  
end function md5sum_from_string
```

This funct. reads from unit u (an unformatted sequence of integers) and computes the MD5 sum.

```
<MD5: procedures>+≡  
function md5sum_from_unit (u) result (digest)  
  integer, intent(in) :: u  
  character(len=32) :: digest  
  type(message_t) :: m  
  character :: char  
  integer :: iostat  
  READ_CHARS: do  
    read (u, "(A)", advance="no", iostat=iostat) char  
    select case (iostat)  
    case (0)  
      call message_append_string (m, char)  
    case (EOR)  
      call message_append_string (m, LF)  
    case (EOF)  
      exit READ_CHARS  
    case default  
      call msg_fatal &  
        ("Computing MD5 sum: I/O error while reading from scratch file")  
    end select  
  end do READ_CHARS  
  call message_pad (m)  
  call message_digest (m, digest)  
  call message_clear (m)  
end function md5sum_from_unit
```

This funct checks the implementation by computing the checksum of certain strings and comparing them with the known values. If some inconsistency is

[illegible]
$$\langle \text{permutations.f90} \rangle \equiv \langle \text{File header} \rangle$$

100

```

    <Permutations: types>

    <Permutations: interfaces>

contains

    <Permutations: procedures>

end module permutations

```

2.14.1 Permutations

A permutation is an array of integers. Each integer between one and `size` should occur exactly once.

```

<Permutations: public>≡
    public :: permutation_t

<Permutations: types>≡
    type :: permutation_t
    private
        integer, dimension(:), allocatable :: p
    end type permutation_t

```

Initialize with the identity permutation.

```

<Permutations: public>+≡
    public :: permutation_init
    public :: permutation_final

<Permutations: procedures>≡
    elemental subroutine permutation_init (p, size)
        type(permutation_t), intent(inout) :: p
        integer, intent(in) :: size
        integer :: i
        allocate (p%p (size))
        forall (i = 1:size)
            p%p(i) = i
        end forall
    end subroutine permutation_init

    elemental subroutine permutation_final (p)
        type(permutation_t), intent(inout) :: p
        deallocate (p%p)
    end subroutine permutation_final

```

I/O:

```

<Permutations: public>+≡
    public :: permutation_write

<Permutations: procedures>+≡
    subroutine permutation_write (p, u)
        type(permutation_t), intent (in) :: p
        integer, intent(in) :: u
        integer :: i

```



```

do i = 1, size (p%p)
  if (size (p%p) < 10) then
    write (u,"(1x,I1)", advance="no") p%p(i)
  else
    write (u,"(1x,I3)", advance="no") p%p(i)
  end if
end do
write (u, *)
end subroutine permutation_write

```

Administration:

```

⟨Permutations: public⟩+=
  public :: permutation_size

⟨Permutations: procedures⟩+=
  elemental function permutation_size (perm) result (s)
    type(permutation_t), intent(in) :: perm
    integer :: s
    s = size (perm%p)
  end function permutation_size

```

Extract an entry in a permutation.

```

⟨Permutations: public⟩+=
  public :: permute

⟨Permutations: procedures⟩+=
  elemental function permute (i, p) result (j)
    integer, intent(in) :: i
    type(permutation_t), intent(in) :: p
    integer :: j
    if (i > 0 .and. i <= size (p%p)) then
      j = p%p(i)
    else
      j = 0
    end if
  end function permute

```

Check whether a permutation is valid: Each integer in the range occurs exactly once.

```

⟨Permutations: public⟩+=
  public :: permutation_ok

⟨Permutations: procedures⟩+=
  elemental function permutation_ok (perm) result (ok)
    type(permutation_t), intent(in) :: perm
    logical :: ok
    integer :: i
    logical, dimension(:), allocatable :: set
    ok = .true.
    allocate (set (size (perm%p)))
    set = .false.
    do i = 1, size (perm%p)
      ok = (perm%p(i) > 0 .and. perm%p(i) <= size (perm%p))
    end do
  end function permutation_ok

```

```

        if (.not.ok) return
        set(perm%p(i)) = .true.
    end do
    ok = all (set)
end function permutation_ok

```

Find the permutation that transforms the second array into the first one. We assume that this is possible and unique and all bounds are set correctly.

This cannot be elemental.

```

<Permutations: public>+≡
    public :: permutation_find

<Permutations: procedures>+≡
    subroutine permutation_find (perm, a1, a2)
        type(permutation_t), intent(inout) :: perm
        integer, dimension(:), intent(in) :: a1, a2
        integer :: i, j
        if (allocated (perm%p)) deallocate (perm%p)
        allocate (perm%p (size (a1)))
        do i = 1, size (a1)
            do j = 1, size (a2)
                if (a1(i) == a2(j)) then
                    perm%p(i) = j
                    exit
                end if
            end do
            perm%p(i) = 0
        end do
    end subroutine permutation_find

```

Find all permutations that transform an array of integers into itself. The resulting permutation list is allocated with the correct length and filled.

The first step is to count the number of different entries in `code`. Next, we scan `code` again and assign a mask to each different entry, true for all identical entries. Finally, we recursively permute the identity for each possible mask.

The permutation is done as follows: A list of all permutations of the initial one with respect to the current mask is generated, then the permutations are generated in turn for each permutation in this list with the next mask. The result is always stored back into the main list, starting from the end of the current list.

```

<Permutations: public>+≡
    public :: permutation_array_make

<Permutations: procedures>+≡
    subroutine permutation_array_make (pa, code)
        type(permutation_t), dimension(:), allocatable, intent(out) :: pa
        integer, dimension(:), intent(in) :: code
        logical, dimension(size(code)) :: mask
        logical, dimension(:,:), allocatable :: imask
        integer, dimension(:), allocatable :: n_i
        type(permutation_t) :: p_init
        type(permutation_t), dimension(:), allocatable :: p_tmp
        integer :: psize, i, j, k, n_different, n, nn_k

```

```

psize = size (code)
mask = .true.
n_different = 0
do i=1, psize
  if (mask(i)) then
    n_different = n_different + 1
    mask = mask .and. (code /= code(i))
  end if
end do
allocate (imask(psize, n_different), n_i(n_different))
mask = .true.
k = 0
do i=1, psize
  if (mask(i)) then
    k = k + 1
    imask(:,k) = (code == code(i))
    n_i(k) = factorial (count(imask(:,k)))
    mask = mask .and. (code /= code(i))
  end if
end do
n = product (n_i)
allocate (pa (n))
call permutation_init (p_init, psize)
pa(1) = p_init
nn_k = 1
do k = 1, n_different
  allocate (p_tmp (n_i(k)))
  do i = nn_k, 1, -1
    call permutation_array_with_mask (p_tmp, imask(:,k), pa(i))
    do j = n_i(k), 1, -1
      pa((i-1)*n_i(k) + j) = p_tmp(j)
    end do
  end do
  deallocate (p_tmp)
  nn_k = nn_k * n_i(k)
end do
call permutation_final (p_init)
deallocate (imask, n_i)
end subroutine permutation_array_make

```

Make a list of permutations of the elements marked true in the `mask` array. The final permutation list must be allocated with the correct length ($n!$). The third argument is the initial permutation to start with, which must have the same length as the `mask` array (this is not checked).

(Permutations: procedures) +=

```

subroutine permutation_array_with_mask (pa, mask, p_init)
  type(permutation_t), dimension(:), intent(inout) :: pa
  logical, dimension(:), intent(in) :: mask
  type(permutation_t), intent(in) :: p_init
  integer :: plen
  integer :: i, ii, j, fac_i, k, x
  integer, dimension(:), allocatable :: index
  plen = size (pa)

```

```

allocate (index(count(mask)))
ii = 0
do i = 1, size (mask)
  if (mask(i)) then
    ii = ii + 1
    index(ii) = i
  end if
end do
pa = p_init
ii = 0
fac_i = 1
do i = 1, size (mask)
  if (mask(i)) then
    ii = ii + 1
    fac_i = fac_i * ii
    x = permute (i, p_init)
    do j = 1, plen
      k = ii - mod (((j-1)*fac_i)/plen, ii)
      call insert (pa(j), x, k, ii, index)
    end do
  end if
end do
deallocate (index)
contains
subroutine insert (p, x, k, n, index)
  type(permutation_t), intent(inout) :: p
  integer, intent(in) :: x, k, n
  integer, dimension(:), intent(in) :: index
  integer :: i
  do i = n, k+1, -1
    p%p(index(i)) = p%p(index(i-1))
  end do
  p%p(index(k)) = x
end subroutine insert
end subroutine permutation_array_with_mask

```

The factorial function is needed for pre-determining the number of permutations that will be generated:

```

(Permutations: procedures) +=
function factorial (n) result (f)
  integer, intent(in) :: n
  integer :: f
  integer :: i
  f = 1
  do i=2, abs(n)
    f = f*i
  end do
end function factorial

```

2.14.2 Operations on binary codes

Binary codes are needed for phase-space trees. Since the permutation function uses permutations, and no other special type is involved, we put the functions here.

This is needed for phase space trees: permute bits in a tree binary code. If no permutation is given, leave as is. (We may want to access the permutation directly here if this is efficiency-critical.)

```

(Permutations: public)+≡
    public :: tc_permute

(Permutations: procedures)+≡
    function tc_permute (k, perm, mask_in) result (pk)
        integer(TC), intent(in) :: k, mask_in
        type(permutation_t), intent(in) :: perm
        integer(TC) :: pk
        integer :: i
        pk = iand (k, mask_in)
        do i = 1, size (perm%p)
!           if (btest(k,i-1)) pk = ibset (pk, permute (perm,i) - 1)
            if (btest(k,i-1)) pk = ibset (pk, perm%p(i)-1)
        end do
    end function tc_permute

```

This routine returns the number of set bits in the tree code value k. Hence, it is the number of externals connected to the current line. If *mask* is present, the complement of the tree code is also considered, and the smaller number is returned. This gives the true distance from the external states, taking into account the initial particles. The complement number is increased by one, since for a scattering diagram the vertex with the sum of all final-state codes is still one point apart from the initial particles.

```

(Permutations: public)+≡
    public :: tc_decay_level

(Permutations: interfaces)≡
    interface tc_decay_level
        module procedure decay_level_simple
        module procedure decay_level_complement
    end interface

(Permutations: procedures)+≡
    function decay_level_complement (k, mask) result (l)
        integer(TC), intent(in) :: k, mask
        integer :: l
        l = min (decay_level_simple (k), &
            & decay_level_simple (ieor (k, mask)) + 1)
    end function decay_level_complement

    function decay_level_simple (k) result(l)
        integer(TC), intent(in) :: k
        integer :: l
        integer :: i
        l = 0
        do i=0, bit_size(k)-1

```

```

        if (btest(k,i)) l = l+1
    end do
end function decay_level_simple

```

2.15 Sorting

This small module provides functions for sorting integer or real arrays.

<sorting.f90>≡
<File header>

```
module sorting
```

<Use kinds>
 use diagnostics !NODEP!

<Standard module head>

<Sorting: public>

<Sorting: interfaces>

```
contains
```

<Sorting: procedures>

```
end module sorting
```

2.15.1 Implementation

The **sort** function returns, for a given integer or real array, the array sorted by increasing value. The current implementation is *mergesort*, which has $O(n \ln n)$ behavior in all cases, and is stable for elements of equal value.

<Sorting: public>≡

```
public :: sort
```

<Sorting: interfaces>≡

```
interface sort
    module procedure sort_int
    module procedure sort_real
end interface
```

The body is identical, just the interface differs.

<Sorting: procedures>≡

```
function sort_int (val_in) result (val)
    integer, dimension(:), intent(in) :: val_in
    integer, dimension(size(val_in)) :: val
<Sorting: sort>
end function sort_int
```

```
function sort_real (val_in) result (val)
```

```

    real(default), dimension(:), intent(in) :: val_in
    real(default), dimension(size(val_in)) :: val
    <Sorting: sort>
end function sort_real

```

```

<Sorting: sort>≡
    val = val_in( order (val_in) )

```

The `order` function returns, for a given integer or real array, the array of indices of the elements sorted by increasing value.

```

<Sorting: public>+≡
    public :: order

<Sorting: interfaces>+≡
    interface order
        module procedure order_int
        module procedure order_real
    end interface

```

```

<Sorting: procedures>+≡
    function order_int (val) result (idx)
        integer, dimension(:), intent(in) :: val
        integer, dimension(size(val)) :: idx
    <Sorting: order>
end function order_int

    function order_real (val) result (idx)
        real(default), dimension(:), intent(in) :: val
        integer, dimension(size(val)) :: idx
    <Sorting: order>
end function order_real

```

We start by individual elements, merge them to pairs, merge those to four-element subarrays, and so on. The last subarray can extend only up to the original array bound, of course, and the second of the subarrays to merge should contain at least one element.

```

<Sorting: order>≡
    integer :: n, i, s, b1, b2, e1, e2
    n = size (idx)
    forall (i = 1:n)
        idx(i) = i
    end forall
    s = 1
    do while (s < n)
        do b1 = 1, n-s, 2*s
            b2 = b1 + s
            e1 = b2 - 1
            e2 = min (e1 + s, n)
            call merge (idx(b1:e2), idx(b1:e1), idx(b2:e2), val)
        end do
        s = 2 * s
    end do

```

The merging step does the actual sorting. We take two sorted array sections and merge them to a sorted result array. We are working on the indices, and comparing is done by taking the associated `val` which is real or integer.

```

<Sorting: interfaces>+≡
  interface merge
    module procedure merge_int
    module procedure merge_real
  end interface

<Sorting: procedures>+≡
  subroutine merge_int (res, src1, src2, val)
    integer, dimension(:), intent(out) :: res
    integer, dimension(:), intent(in) :: src1, src2
    integer, dimension(:), intent(in) :: val
    integer, dimension(size(res)) :: tmp
  <Sorting: merge>
  end subroutine merge_int

  subroutine merge_real (res, src1, src2, val)
    integer, dimension(:), intent(out) :: res
    integer, dimension(:), intent(in) :: src1, src2
    real(default), dimension(:), intent(in) :: val
    integer, dimension(size(res)) :: tmp
  <Sorting: merge>
  end subroutine merge_real

<Sorting: merge>≡
  integer :: i1, i2, i
  i1 = 1
  i2 = 1
  do i = 1, size (tmp)
    if (val(src1(i1)) <= val(src2(i2))) then
      tmp(i) = src1(i1); i1 = i1 + 1
      if (i1 > size (src1)) then
        tmp(i+1:) = src2(i2:)
        exit
      end if
    else
      tmp(i) = src2(i2); i2 = i2 + 1
      if (i2 > size (src2)) then
        tmp(i+1:) = src1(i1:)
        exit
      end if
    end if
  end do
  res = tmp

```

2.15.2 Concatenating arrays

Not precisely a sorting function, but useful: Concatenate two arrays.

```

<Sorting: public>+≡
  public :: concat

```



```

<Sorting: interfaces>+≡
  interface concat
    module procedure concat_int
    module procedure concat_real
  end interface

<Sorting: procedures>+≡
  function concat_int (val1, val2) result (val12)
    integer, dimension(:), intent(in) :: val1, val2
    integer, dimension(size(val1)+size(val2)) :: val12
  <Sorting: concat>
  end function concat_int

  function concat_real (val1, val2) result (val12)
    real(default), dimension(:), intent(in) :: val1, val2
    integer, dimension(size(val1)+size(val2)) :: val12
  <Sorting: concat>
  end function concat_real

<Sorting: concat>≡
  val12(:size(val1)) = val1
  val12(size(val1)+1:) = val2

```

2.15.3 Test

```

<Sorting: public>+≡
  public :: sorting_test

<Sorting: procedures>+≡
  subroutine sorting_test ()
    integer, parameter :: NMAX = 10
    real(default), dimension(NMAX) :: rval
    integer, dimension(NMAX) :: ival
    real, dimension(NMAX) :: harvest
    integer :: i, j
    print *, "Sorting real values:"
    do i = 1, NMAX
      print *
      call random_number (harvest(:i))
      rval(:i) = harvest(:i)
      print "(10(1x,F7.4))", rval(:i)
      rval(:i) = sort (rval(:i))
      print "(10(1x,F7.4))", rval(:i)
      do j = i, 2, -1
        if (rval(j)-rval(j-1) < 0) &
          call msg_fatal ("Sorting failure")
      end do
    end do
    print *
    print *, "Sorting integer values:"
    do i = 1, NMAX
      print *
      call random_number (harvest(:i))

```

```

      ival(:i) = harvest(:i) * NMAX * 2
      print "(10(1x,I2))", ival(:i)
      ival(:i) = sort (ival(:i))
      print "(10(1x,I2))", ival(:i)
      do j = i, 2, -1
        if (ival(j)-ival(j-1) < 0) &
          call msg_fatal ("Sorting failure")
        end do
      end do
end subroutine sorting_test

```

Chapter 3

Text handling

WHIZARD has to handle complex structures in input (and output) data. Doing this in a generic and transparent way requires a generic lexer and parser. The necessary modules are implemented here:

ifiles Implementation of line-oriented internal files in a more flexible way (linked lists of variable-length strings) than the Fortran builtin features.

lexers Read text and transform it into a token stream.

syntax_rules Define the rules for interpreting tokens, to be used by the parser.

parser Categorize tokens (keyword, string, number etc.) and use a set of syntax rules to transform the input into a parse tree.

3.1 Internal files

The internal files introduced here (`ifile`) are a replacement for the built-in internal files, which are fixed-size arrays of fixed-length character strings. The `ifile` type is a doubly-linked list of variable-length character strings with line numbers.

```
<ifiles.f90>≡  
  <File header>  
  
  module ifiles  
  
    <Use strings>  
    <Use file utils>  
    use limits, only: EOF !NODEP!  
  
    <Standard module head>  
  
    <Ifiles: public>  
  
    <Ifiles: types>  
  
    <Ifiles: interfaces>  
  
    contains  
  
    <Ifiles: subroutines>  
  
  end module ifiles
```

3.1.1 iostat codes

```
<Limits: public parameters>+≡  
  integer, parameter, public :: EOF = iostat_end, EOR = iostat_eor
```

3.1.2 The line type

The line entry type is for internal use, it is the list entry to be collected in an `ifile` object.

```
<Ifiles: types>≡  
  type :: line_entry_t  
    private  
    type(line_entry_t), pointer :: previous => null ()  
    type(line_entry_t), pointer :: next => null ()  
    type(string_t) :: string  
    integer :: index  
  end type line_entry_t
```

Create a new list entry, given a varying string as input. The line number and pointers are not set, these make sense only within an `ifile`.

```
<Ifiles: subroutines>≡  
  subroutine line_entry_create (line, string)
```

```

        type(line_entry_t), pointer :: line
        type(string_t), intent(in) :: string
        allocate (line)
        line%string = string
    end subroutine line_entry_create

```

Destroy a single list entry: Since the pointer components should not be deallocated explicitly, just deallocate the object itself.

```

<Ifiles: subroutines>+≡
    subroutine line_entry_destroy (line)
        type(line_entry_t), pointer :: line
        deallocate (line)
    end subroutine line_entry_destroy

```

3.1.3 The ifile type

The internal file is a linked list of line entries.

```

<Ifiles: public>≡
    public :: ifile_t

<Ifiles: types>+≡
    type :: ifile_t
    private
        type(line_entry_t), pointer :: first => null ()
        type(line_entry_t), pointer :: last => null ()
        integer :: n_lines = 0
    end type ifile_t

```

We need no explicit initializer, but a routine which recursively deallocates the contents may be appropriate. After this, existing line pointers may become undefined, so they should be nullified before the file is destroyed.

```

<Ifiles: public>+≡
    public :: ifile_clear

<Ifiles: subroutines>+≡
    subroutine ifile_clear (ifile)
        type(ifile_t), intent(inout) :: ifile
        type(line_entry_t), pointer :: current
        do while (associated (ifile%first))
            current => ifile%first
            ifile%first => current%next
            call line_entry_destroy (current)
        end do
        nullify (ifile%last)
        ifile%n_lines = 0
    end subroutine ifile_clear

```

The finalizer is just an alias for the above.

```

<Ifiles: public>+≡
    public :: ifile_final

```

```

<Ifiles: interfaces>+=
  interface ifile_final
    module procedure ifile_clear
  end interface

```

3.1.4 I/O on ifiles

Fill an ifile from an ordinary external file, i.e., I/O unit. If the ifile is not empty, the old contents will be destroyed. We can read a fixed-length character string, an ISO varying string, an ordinary internal file (character-string array), or from an external unit. In the latter case, lines are appended until EOF is reached. Finally, there is a variant which reads from another ifile, effectively copying it.

```

<Ifiles: public>+=
  public :: ifile_read

<Ifiles: interfaces>+=
  interface ifile_read
    module procedure ifile_read_from_string
    module procedure ifile_read_from_char
    module procedure ifile_read_from_unit
    module procedure ifile_read_from_char_array
    module procedure ifile_read_from_ifile
  end interface

<Ifiles: subroutines>+=
  subroutine ifile_read_from_string (ifile, string)
    type(ifile_t), intent(inout) :: ifile
    type(string_t), intent(in) :: string
    call ifile_clear (ifile)
    call ifile_append (ifile, string)
  end subroutine ifile_read_from_string

  subroutine ifile_read_from_char (ifile, char)
    type(ifile_t), intent(inout) :: ifile
    character(*), intent(in) :: char
    call ifile_clear (ifile)
    call ifile_append (ifile, char)
  end subroutine ifile_read_from_char

  subroutine ifile_read_from_char_array (ifile, char)
    type(ifile_t), intent(inout) :: ifile
    character(*), dimension(:), intent(in) :: char
    call ifile_clear (ifile)
    call ifile_append (ifile, char)
  end subroutine ifile_read_from_char_array

  subroutine ifile_read_from_unit (ifile, unit, iostat)
    type(ifile_t), intent(inout) :: ifile
    integer, intent(in) :: unit
    integer, intent(out), optional :: iostat
    call ifile_clear (ifile)
    call ifile_append (ifile, unit, iostat)
  end subroutine ifile_read_from_unit

```

```

subroutine ifile_read_from_ifile (ifile, ifile_in)
  type(ifile_t), intent(inout) :: ifile
  type(ifile_t), intent(in) :: ifile_in
  call ifile_clear (ifile)
  call ifile_append (ifile, ifile_in)
end subroutine ifile_read_from_ifile

```

Append to an ifile. The same as reading, but without resetting the ifile. In addition, there is a routine for appending a whole ifile.

(Ifiles: public)+≡

```

public :: ifile_append

```

(Ifiles: interfaces)+≡

```

interface ifile_append
  module procedure ifile_append_from_string
  module procedure ifile_append_from_char
  module procedure ifile_append_from_unit
  module procedure ifile_append_from_char_array
  module procedure ifile_append_from_ifile
end interface

```

(Ifiles: subroutines)+≡

```

subroutine ifile_append_from_string (ifile, string)
  type(ifile_t), intent(inout) :: ifile
  type(string_t), intent(in) :: string
  type(line_entry_t), pointer :: current
  call line_entry_create (current, string)
  current%index = ifile%n_lines + 1
  if (associated (ifile%last)) then
    current%previous => ifile%last
    ifile%last%next => current
  else
    ifile%first => current
  end if
  ifile%last => current
  ifile%n_lines = current%index
end subroutine ifile_append_from_string

subroutine ifile_append_from_char (ifile, char)
  type(ifile_t), intent(inout) :: ifile
  character(*), intent(in) :: char
  call ifile_append_from_string (ifile, var_str (trim (char)))
end subroutine ifile_append_from_char

subroutine ifile_append_from_char_array (ifile, char)
  type(ifile_t), intent(inout) :: ifile
  character(*), dimension(:), intent(in) :: char
  integer :: i
  do i = 1, size (char)
    call ifile_append_from_string (ifile, var_str (trim (char(i))))
  end do
end subroutine ifile_append_from_char_array

subroutine ifile_append_from_unit (ifile, unit, iostat)
  type(ifile_t), intent(inout) :: ifile

```

```

integer, intent(in) :: unit
integer, intent(out), optional :: iostat
type(string_t) :: buffer
integer :: ios
ios = 0
READ_LOOP: do
    call get (unit, buffer, iostat = ios)
    if (ios == EOF .or. ios > 0) exit READ_LOOP
    call ifile_append_from_string (ifile, buffer)
end do READ_LOOP
if (present (iostat)) then
    iostat = ios
else if (ios > 0) then
    call get (unit, buffer) ! trigger error again
end if
end subroutine ifile_append_from_unit

subroutine ifile_append_from_ifile (ifile, ifile_in)
type(ifile_t), intent(inout) :: ifile
type(ifile_t), intent(in) :: ifile_in
type(line_entry_t), pointer :: current
current => ifile_in%first
do while (associated (current))
    call ifile_append_from_string (ifile, current%string)
    current => current%next
end do
end subroutine ifile_append_from_ifile

```

Write the ifile contents to an external unit

```

<Ifiles: public>+≡
public :: ifile_write

<Ifiles: subroutines>+≡
subroutine ifile_write (ifile, unit, iostat)
type(ifile_t), intent(in) :: ifile
integer, intent(in), optional :: unit
integer, intent(out), optional :: iostat
integer :: u
type(line_entry_t), pointer :: current
u = output_unit (unit); if (u < 0) return
current => ifile%first
do while (associated (current))
    call put_line (u, current%string, iostat)
    current => current%next
end do
end subroutine ifile_write

```

Convert the ifile to an array of strings, which is allocated by this function:

```

<Ifiles: public>+≡
public :: ifile_to_string_array

<Ifiles: subroutines>+≡
subroutine ifile_to_string_array (ifile, string)
type(ifile_t), intent(in) :: ifile

```



```

type(string_t), dimension(:), intent(inout), allocatable :: string
type(line_entry_t), pointer :: current
integer :: i
allocate (string (ifile_get_length (ifile)))
current => ifile%first
do i = 1, ifile_get_length (ifile)
    string(i) = current%string
    current => current%next
end do
end subroutine ifile_to_string_array

```

3.1.5 Ifile tools

```

<Ifiles: public>+≡
public :: ifile_get_length

<Ifiles: subroutines>+≡
function ifile_get_length (ifile) result (length)
    integer :: length
    type(ifile_t), intent(in) :: ifile
    length = ifile%n_lines
end function ifile_get_length

```

3.1.6 Line pointers

Instead of the implicit pointer used in ordinary file access, we define explicit pointers, so there can be more than one at a time.

```

<Ifiles: public>+≡
public :: line_p

<Ifiles: types>+≡
type :: line_p
private
type(line_entry_t), pointer :: p => null ()
end type line_p

```

Assign a file pointer to the first or last line in an ifile:

```

<Ifiles: public>+≡
public :: line_init

<Ifiles: subroutines>+≡
subroutine line_init (line, ifile, back)
    type(line_p), intent(inout) :: line
    type(ifile_t), intent(in) :: ifile
    logical, intent(in), optional :: back
    if (present (back)) then
        if (back) then
            line%p => ifile%last
        else
            line%p => ifile%first
        end if
    else

```

```

        line%p => ifile%first
    end if
end subroutine line_init

```

Remove the pointer association:

```

<Ifiles: public>+≡
    public :: line_final
<Ifiles: subroutines>+≡
    subroutine line_final (line)
        type(line_p), intent(inout) :: line
        nullify (line%p)
    end subroutine line_final

```

Go one step forward

```

<Ifiles: public>+≡
    public :: line_advance
<Ifiles: subroutines>+≡
    subroutine line_advance (line)
        type(line_p), intent(inout) :: line
        if (associated (line%p)) line%p => line%p%next
    end subroutine line_advance

```

Go one step backward

```

<Ifiles: public>+≡
    public :: line_backspace
<Ifiles: subroutines>+≡
    subroutine line_backspace (line)
        type(line_p), intent(inout) :: line
        if (associated (line%p)) line%p => line%p%previous
    end subroutine line_backspace

```

Check whether we are accessing a valid line

```

<Ifiles: public>+≡
    public :: line_is_associated
<Ifiles: subroutines>+≡
    function line_is_associated (line) result (ok)
        logical :: ok
        type(line_p), intent(in) :: line
        ok = associated (line%p)
    end function line_is_associated

```

3.1.7 Access lines via pointers

We do not need the ifile as an argument to these functions, because the `line` type will point to an existing ifile.

```

<Ifiles: public>+≡
    public :: line_get_string

```

```

<Ifiles: subroutines>+=
function line_get_string (line) result (string)
  type(string_t) :: string
  type(line_p), intent(in) :: line
  if (associated (line%p)) then
    string = line%p%string
  else
    string = ""
  end if
end function line_get_string

```

Variant where the line pointer is advanced after reading.

```

<Ifiles: public>+=
public :: line_get_string_advance
<Ifiles: subroutines>+=
function line_get_string_advance (line) result (string)
  type(string_t) :: string
  type(line_p), intent(inout) :: line
  if (associated (line%p)) then
    string = line%p%string
    call line_advance (line)
  else
    string = ""
  end if
end function line_get_string_advance

```

```

<Ifiles: public>+=
public :: line_get_index
<Ifiles: subroutines>+=
function line_get_index (line) result (index)
  integer :: index
  type(line_p), intent(in) :: line
  if (associated (line%p)) then
    index = line%p%index
  else
    index = 0
  end if
end function line_get_index

```

```

<Ifiles: public>+=
public :: line_get_length
<Ifiles: subroutines>+=
function line_get_length (line) result (length)
  integer :: length
  type(line_p), intent(in) :: line
  if (associated (line%p)) then
    length = len (line%p%string)
  else
    length = 0
  end if
end function line_get_length

```

3.2 Lexer

The lexer purpose is to read from a line-separated character input stream (usually a file) and properly chop the stream into lexemes (tokens). [The parser will transform lexemes into meaningful tokens, to be stored in a parse tree, therefore we do not use the term 'token' here.] The input is read line-by-line, but interpreted free-form, except for quotes and the comment syntax. (Fortran 2003 would allow us to use a stream type for reading.)

In an object-oriented approach, we can dynamically create and destroy lexers, including the lexer setup.

The main lexer function is to return a lexeme according to the basic lexer rules (quotes, comments, whitespace, special classes). There is also a routine to write back a lexeme to the input stream (but only once).

For the rules, we separate the possible characters into classes. Whitespace usually consists of blank, tab, and line-feed, where any number of consecutive whitespace is equivalent to one. Quoted strings are enclosed by a pair of quote characters, possibly multiline. Comments are similar to quotes, but interpreted as whitespace. Numbers are identified (not distinguishing real and integer) but not interpreted. Other character classes make up identifiers.

```
<lexers.f90>≡  
  <File header>  
  
  module lexers  
  
    <Use strings>  
    <Use file utils>  
    use limits, only: EOF, EOR !NODEP!  
    use limits, only: LF !NODEP!  
    use limits, only: WHITESPACE_CHARS, LCLETTERS, UCLETTERS, DIGITS !NODEP!  
    use diagnostics !NODEP!  
    use ifiles, only: ifile_t  
    use ifiles, only: line_p, line_is_associated, line_init, line_final  
    use ifiles, only: line_get_string_advance  
  
    <Standard module head>  
  
    <Lexer: public>  
  
    <Lexer: parameters>  
  
    <Lexer: types>  
  
    <Lexer: interfaces>  
  
    contains  
  
    <Lexer: procedures>  
  
  end module lexers
```

3.2.1 Input streams

For flexible input, we define a generic stream type that refers to either an external file, an external unit which is already open, a string, an `ifile` object (internal file, i.e., string list), or a line pointer to an `ifile` object. The stream type actually follows the idea of a formatted external file, which is line-oriented. Thus, the stream reader always returns a whole record (input line).

Note that only in the string version, the stream contents are stored inside the stream object. In the `ifile` version, the stream contains only the line pointer, while in the external-file case, the line pointer is implicitly created by the runtime library.

```
<Lexer: public>≡
    public :: stream_t

<Lexer: types>≡
    type :: stream_t
        type(string_t), pointer :: filename => null ()
        integer, pointer :: unit => null ()
        type(string_t), pointer :: string => null ()
        type(ifile_t), pointer :: ifile => null ()
        type(line_p), pointer :: line => null ()
        integer :: record = 0
        logical :: eof = .false.
    end type stream_t
```

The initializers refer to the specific version. The stream should be undefined before calling this.

```
<Lexer: public>+≡
    public :: stream_init

<Lexer: interfaces>≡
    interface stream_init
        module procedure stream_init_filename
        module procedure stream_init_unit
        module procedure stream_init_string
        module procedure stream_init_ifile
        module procedure stream_init_line
    end interface

<Lexer: procedures>≡
    subroutine stream_init_filename (stream, filename)
        type(stream_t), intent(out) :: stream
        character(*), intent(in) :: filename
        integer :: unit
        unit = free_unit ()
        open (unit=unit, file=filename, status="old", action="read")
        call stream_init_unit (stream, unit)
        allocate (stream%filename)
        stream%filename = filename
    end subroutine stream_init_filename

    subroutine stream_init_unit (stream, unit)
        type(stream_t), intent(out) :: stream
        integer, intent(in) :: unit
```

```

        allocate (stream%unit)
        stream%unit = unit
        stream%eof = .false.
    end subroutine stream_init_unit

subroutine stream_init_string (stream, string)
    type(stream_t), intent(out) :: stream
    type(string_t), intent(in) :: string
    allocate (stream%string)
    stream%string = string
end subroutine stream_init_string

subroutine stream_init_ifile (stream, ifile)
    type(stream_t), intent(out) :: stream
    type(ifile_t), intent(in) :: ifile
    type(line_p) :: line
    call line_init (line, ifile)
    call stream_init_line (stream, line)
    allocate (stream%ifile)
    stream%ifile = ifile
end subroutine stream_init_ifile

subroutine stream_init_line (stream, line)
    type(stream_t), intent(out) :: stream
    type(line_p), intent(in) :: line
    allocate (stream%line)
    stream%line = line
end subroutine stream_init_line

```

The finalizer restores the initial state. If an external file was opened, it is closed.

```

<Lexer: public>+≡
    public :: stream_final

<Lexer: procedures>+≡
    subroutine stream_final (stream)
        type(stream_t), intent(inout) :: stream
        if (associated (stream%filename)) then
            close (stream%unit)
            deallocate (stream%unit)
            deallocate (stream%filename)
        else if (associated (stream%unit)) then
            deallocate (stream%unit)
        else if (associated (stream%string)) then
            deallocate (stream%string)
        else if (associated (stream%ifile)) then
            call line_final (stream%line)
            deallocate (stream%line)
            deallocate (stream%ifile)
        else if (associated (stream%line)) then
            call line_final (stream%line)
            deallocate (stream%line)
        end if
    end subroutine stream_final

```

This returns the next record from the input stream. Depending on the stream type, the stream pointers are modified: Reading from external unit, the external file is advanced (implicitly). Reading from string, the string is replaced by an empty string. Reading from ifile, the line pointer is advanced. Note that the `iostat` argument is mandatory.

<Lexer: public>+≡

`public :: stream_get_record`

<Lexer: procedures>+≡

```
subroutine stream_get_record (stream, string, iostat)
  type(stream_t), intent(inout) :: stream
  type(string_t), intent(out) :: string
  integer, intent(out) :: iostat
  if (associated (stream%unit)) then
    if (stream%eof) then
      iostat = EOF
    else
      call get (stream%unit, string, iostat=iostat)
      if (iostat == EOR) then
        iostat = 0
        stream%record = stream%record + 1
      end if
      if (iostat == EOF) then
        iostat = 0
        stream%eof = .true.
        if (len (string) /= 0) stream%record = stream%record + 1
      end if
    end if
  else if (associated (stream%string)) then
    if (len (stream%string) /= 0) then
      string = stream%string
      stream%string = ""
      iostat = 0
      stream%record = stream%record + 1
    else
      string = ""
      iostat = EOF
    end if
  else if (associated (stream%line)) then
    if (line_is_associated (stream%line)) then
      string = line_get_string_advance (stream%line)
      iostat = 0
      stream%record = stream%record + 1
    else
      string = ""
      iostat = EOF
    end if
  else
    call msg_bug (" Attempt to read from uninitialized input stream")
  end if
end subroutine stream_get_record
```

Return the current stream source as a message string.

<Lexer: public>+≡

```

public :: stream_get_source_info_string
<Lexer: procedures>+≡
function stream_get_source_info_string (stream) result (string)
  type(string_t) :: string
  type(stream_t), intent(in) :: stream
  character(20) :: buffer
  if (associated (stream%filename)) then
    string = "File '" // stream%filename // "' (unit = "
    write (buffer, "(I0)") stream%unit
    string = string // trim (buffer) // ")"
  else if (associated (stream%unit)) then
    write (buffer, "(I0)") stream%unit
    string = "Unit " // trim (buffer)
  else if (associated (stream%string)) then
    string = "Input string"
  else if (associated (stream%ifile) .or. associated (stream%line)) then
    string = "Internal file"
  else
    string = ""
  end if
end function stream_get_source_info_string

```

Return the index of the record just read as a message string.

```

<Lexer: public>+≡
public :: stream_get_record_info_string
<Lexer: procedures>+≡
function stream_get_record_info_string (stream) result (string)
  type(string_t) :: string
  type(stream_t), intent(in) :: stream
  character(20) :: buffer
  string = stream_get_source_info_string (stream)
  if (string /= "") string = string // ", "
  write (buffer, "(I0)") stream%record
  string = string // "line " // trim (buffer)
end function stream_get_record_info_string

```

3.2.2 Keyword list

The lexer should be capable of identifying a token as a known keyword. To this end, we store a list of keywords:

```

<Lexer: public>+≡
public :: keyword_list_t
<Lexer: types>+≡
type :: keyword_entry_t
  private
  type(string_t) :: string
  type(keyword_entry_t), pointer :: next => null ()
end type keyword_entry_t

type :: keyword_list_t

```



```

private
type(keyword_entry_t), pointer :: first => null ()
type(keyword_entry_t), pointer :: last => null ()
end type keyword_list_t

```

Add a new string to the keyword list, unless it is already there:

```

<Lexer: public>+≡
public :: keyword_list_add

<Lexer: procedures>+≡
subroutine keyword_list_add (keylist, string)
type(keyword_list_t), intent(inout) :: keylist
type(string_t), intent(in) :: string
type(keyword_entry_t), pointer :: k_entry_new
if (.not. keyword_list_contains (keylist, string)) then
allocate (k_entry_new)
k_entry_new%string = string
if (associated (keylist%first)) then
keylist%last%next => k_entry_new
else
keylist%first => k_entry_new
end if
keylist%last => k_entry_new
end if
end subroutine keyword_list_add

```

Return true if a string is a keyword.

```

<Lexer: public>+≡
public :: keyword_list_contains

<Lexer: procedures>+≡
function keyword_list_contains (keylist, string) result (found)
type(keyword_list_t), intent(in) :: keylist
type(string_t), intent(in) :: string
logical :: found
found = .false.
call check_rec (keylist%first)
contains
recursive subroutine check_rec (k_entry)
type(keyword_entry_t), pointer :: k_entry
if (associated (k_entry)) then
if (k_entry%string /= string) then
call check_rec (k_entry%next)
else
found = .true.
end if
end if
end subroutine check_rec
end function keyword_list_contains

```

Write the keyword list

```

<Lexer: public>+≡
public :: keyword_list_write

```

```

<Lexer: interfaces>+≡
    interface keyword_list_write
        module procedure keyword_list_write_unit
    end interface

<Lexer: procedures>+≡
    subroutine keyword_list_write_unit (keylist, unit)
        type(keyword_list_t), intent(in) :: keylist
        integer, intent(in) :: unit
        write (unit, "(A)") "Keyword list:"
        if (associated (keylist%first)) then
            call keyword_write_rec (keylist%first)
            write (unit, *)
        else
            write (unit, "(1x,A)") "[empty]"
        end if
    contains
        recursive subroutine keyword_write_rec (k_entry)
            type(keyword_entry_t), intent(in), pointer :: k_entry
            if (associated (k_entry)) then
                write (unit, "(1x,A)", advance="no") char (k_entry%string)
                call keyword_write_rec (k_entry%next)
            end if
        end subroutine keyword_write_rec
    end subroutine keyword_list_write_unit

```

Clear the keyword list

```

<Lexer: public>+≡
    public :: keyword_list_final

<Lexer: procedures>+≡
    subroutine keyword_list_final (keylist)
        type(keyword_list_t), intent(inout) :: keylist
        call keyword_destroy_rec (keylist%first)
        nullify (keylist%last)
    contains
        recursive subroutine keyword_destroy_rec (k_entry)
            type(keyword_entry_t), pointer :: k_entry
            if (associated (k_entry)) then
                call keyword_destroy_rec (k_entry%next)
                deallocate (k_entry)
            end if
        end subroutine keyword_destroy_rec
    end subroutine keyword_list_final

```

3.2.3 Lexeme templates

This type is handled like a rudimentary regular expression. It determines the lexer behavior when matching a string. The actual objects made from this type and the corresponding matching routines are listed below.

```

<Lexer: types>+≡
    type :: template_t

```

```

private
integer :: type
character(256) :: charset1, charset2
integer :: len1, len2
end type template_t

```

These are the types that valid lexemes can have:

```

<Lexer: public>+≡
public :: T_KEYWORD, T_IDENTIFIER, T_QUOTED, T_NUMERIC

<Lexer: parameters>≡
integer, parameter :: T_KEYWORD = 1
integer, parameter :: T_IDENTIFIER = 2, T_QUOTED = 3, T_NUMERIC = 4

```

These are special types:

```

<Lexer: parameters>+≡
integer, parameter :: EMPTY = 0, WHITESPACE = 10
integer, parameter :: NO_MATCH = 11, IO_ERROR = 12, OVERFLOW = 13
integer, parameter :: UNMATCHED_QUOTE = 14

```

In addition, we have EOF which is a negative integer, normally -1 . Printout for debugging:

```

<Lexer: procedures>+≡
subroutine lexeme_type_write (type, unit)
integer, intent(in) :: type
integer, intent(in) :: unit
select case (type)
case (EMPTY);      write(unit,"(A)",advance="no") " EMPTY      "
case (WHITESPACE); write(unit,"(A)",advance="no") " WHITESPACE "
case (T_IDENTIFIER);write(unit,"(A)",advance="no") " IDENTIFIER "
case (T_QUOTED);   write(unit,"(A)",advance="no") " QUOTED      "
case (T_NUMERIC);  write(unit,"(A)",advance="no") " NUMERIC      "
case (IO_ERROR);   write(unit,"(A)",advance="no") " IO_ERROR    "
case (OVERFLOW);   write(unit,"(A)",advance="no") " OVERFLOW    "
case (UNMATCHED_QUOTE); write(unit,"(A)",advance="no") " UNMATCHEDQ "
case (NO_MATCH);   write(unit,"(A)",advance="no") " NO_MATCH    "
case (EOF);        write(unit,"(A)",advance="no") " EOF          "
case default;      write(unit,"(A)",advance="no") " [illegal]   "
end select
end subroutine lexeme_type_write

subroutine template_write (tt, unit)
type(template_t), intent(in) :: tt
integer, intent(in) :: unit
call lexeme_type_write (tt%type, unit)
write (unit, "(A)", advance="no") " '" // tt%charset1(1:tt%len1) // "'"
write (unit, "(A)", advance="no") " '" // tt%charset2(1:tt%len2) // "'"
end subroutine template_write

```

The matching functions all return the number of matched characters in the provided string. If this number is zero, the match has failed.

The `template` functions are declared `pure` because they appear in `forall` loops below.

A template for whitespace:

```

<Lexer: procedures>+≡
  pure function template_whitespace (chars) result (tt)
    character(*), intent(in) :: chars
    type(template_t) :: tt
    tt = template_t (WHITESPACE, chars, "", len (chars), 0)
  end function template_whitespace

```

Just match the string against the character set.

```

<Lexer: procedures>+≡
  subroutine match_whitespace (tt, s, n)
    type(template_t), intent(in) :: tt
    character(*), intent(in) :: s
    integer, intent(out) :: n
    n = verify (s, tt%charset1(1:tt%len1)) - 1
    if (n < 0) n = len (s)
  end subroutine match_whitespace

```

A template for normal identifiers. To match, a lexeme should have a first character in class `chars1` and an arbitrary number of further characters in class `chars2`. If the latter is empty, we are looking for a single-character lexeme.

```

<Lexer: procedures>+≡
  pure function template_identifier (chars1, chars2) result (tt)
    character(*), intent(in) :: chars1, chars2
    type(template_t) :: tt
    tt = template_t (T_IDENTIFIER, chars1, chars2, len(chars1), len(chars2))
  end function template_identifier

```

Here, the first letter must match, the others may or may not.

```

<Lexer: procedures>+≡
  subroutine match_identifier (tt, s, n)
    type(template_t), intent(in) :: tt
    character(*), intent(in) :: s
    integer, intent(out) :: n
    if (verify (s(1:1), tt%charset1(1:tt%len1)) == 0) then
      n = verify (s(2:), tt%charset2(1:tt%len2))
      if (n == 0) n = len (s)
    else
      n = 0
    end if
  end subroutine match_identifier

```

A template for quoted strings. The same template applies for comments. The first character set indicates the left quote (could be a sequence of several characters), the second one the matching right quote.

```

<Lexer: procedures>+≡
  pure function template_quoted (chars1, chars2) result (tt)
    character(*), intent(in) :: chars1, chars2
    type(template_t) :: tt
    tt = template_t (T_QUOTED, chars1, chars2, len (chars1), len (chars2))
  end function template_quoted

```

Here, the beginning of the string must exactly match the first character set, then we look for the second one. If found, return. If there is a first quote but no second one, return a negative number, indicating this error condition.

```

<Lexer: procedures>+≡
subroutine match_quoted (tt, s, n, range)
  type(template_t), intent(in) :: tt
  character(*), intent(in) :: s
  integer, intent(out) :: n
  integer, dimension(2), intent(out) :: range
  character(tt%len1) :: ch1
  character(tt%len2) :: ch2
  integer :: i
  ch1 = tt%charset1
  if (s(1:tt%len1) == ch1) then
    ch2 = tt%charset2
    do i = tt%len1 + 1, len (s) - tt%len2 + 1
      if (s(i:i+tt%len2-1) == ch2) then
        n = i + tt%len2 - 1
        range(1) = tt%len1 + 1
        range(2) = i - 1
        return
      end if
    end do
    n = -1
    range = 0
  else
    n = 0
    range = 0
  end if
end subroutine match_quoted

```

A template for real numbers. The first character set is the set of allowed exponent letters. In accordance with the other functions we return the lexeme as a string but do not read it.

```

<Lexer: procedures>+≡
pure function template_numeric (chars) result (tt)
  character(*), intent(in) :: chars
  type(template_t) :: tt
  tt = template_t (T_NUMERIC, chars, "", len (chars), 0)
end function template_numeric

```

A numeric lexeme may be real or integer. We purposely do not allow for a preceding sign. If the number is followed by an exponent, this is included, otherwise the rest is ignored.

There is a possible pitfall with this behavior: while the string `1e3` will be interpreted as a single number, the analogous string `1a3` will be split into the number `1` and an identifier `a3`. There is no easy way around such an ambiguity. We should make sure that the syntax does not contain identifiers like `a3` or `e3`.

```

<Lexer: procedures>+≡
subroutine match_numeric (tt, s, n)
  type(template_t), intent(in) :: tt
  character(*), intent(in) :: s

```

```

integer, intent(out) :: n
integer :: i, n0
character(10), parameter :: digits = "0123456789"
character(2), parameter :: signs = "-+"
n = verify (s, digits) - 1
if (n < 0) then
    n = 0
    return
else if (s(n+1:n+1) == ".") then
    i = verify (s(n+2:), digits) - 1
    if (i < 0) then
        n = len (s)
        return
    else if (i > 0 .or. n > 0) then
        n = n + 1 + i
    end if
end if
n0 = n
if (n > 0) then
    if (verify (s(n+1:n+1), tt%charset1(1:tt%len1)) == 0) then
        n = n + 1
        if (verify (s(n+1:n+1), signs) == 0) n = n + 1
        i = verify (s(n+1:), digits) - 1
        if (i < 0) then
            n = len (s)
        else if (i == 0) then
            n = n0
        else
            n = n + i
        end if
    end if
end if
end subroutine match_numeric

```

The generic matching routine. With Fortran 2003 we would define separate types and use a SELECT TYPE instead.

<Lexer: procedures>+≡

```

subroutine match_template (tt, s, n, range)
    type(template_t), intent(in) :: tt
    character(*), intent(in) :: s
    integer, intent(out) :: n
    integer, dimension(2), intent(out) :: range
    select case (tt%type)
    case (WHITESPACE)
        call match_whitespace (tt, s, n)
        range = 0
    case (T_IDENTIFIER)
        call match_identifier (tt, s, n)
        range(1) = 1
        range(2) = len_trim (s)
    case (T_QUOTED)
        call match_quoted (tt, s, n, range)
    case (T_NUMERIC)

```

```

        call match_numeric (tt, s, n)
        range(1) = 1
        range(2) = len_trim (s)
    case default
        call msg_bug ("Invalid lexeme template encountered")
    end select
end subroutine match_template

```

Match against an array of templates. Return the index of the first template that matches together with the number of characters matched and the range of the relevant substring. If all fails, these numbers are zero.

<Lexer: procedures>+≡

```

subroutine match (tt, s, n, range, ii)
    type(template_t), dimension(:), intent(in) :: tt
    character(*), intent(in) :: s
    integer, intent(out) :: n
    integer, dimension(2), intent(out) :: range
    integer, intent(out) :: ii
    integer :: i
    do i = 1, size (tt)
        call match_template (tt(i), s, n, range)
        if (n /= 0) then
            ii = i
            return
        end if
    end do
    n = 0
    ii = 0
end subroutine match

```

3.2.4 The lexer setup

This object contains information about character classes. As said above, one class consists of quoting chars (matching left and right), another one of comment chars (similar), a class of whitespace, and several classes of characters that make up identifiers. When creating the lexer setup, the character classes are transformed into lexeme templates which are to be matched in a certain predefined order against the input stream.

BLANK should always be taken as whitespace, some things may depend on this. TAB is also fixed by convention, but may in principle be modified. Newline (DOS!) and linefeed are also defined as whitespace.

<Limits: public parameters>+≡

```

character, parameter, public :: BLANK = ' ', TAB = achar(9)
character, parameter, public :: CR = achar(13), LF = achar(10)
character, parameter, public :: BACKSLASH = achar(92)
character(*), parameter, public :: WHITESPACE_CHARS = BLANK// TAB // CR // LF
character(*), parameter, public :: LCLETTERS = "abcdefghijklmnopqrstuvwxyz"
character(*), parameter, public :: UCLETTERS = "ABCDEFGHIJKLMNOPQRSTUVWXYZ"
character(*), parameter, public :: DIGITS = "0123456789"

```

The lexer setup, containing the list of lexeme templates. No defaults yet. The type with index zero will be assigned to the NO_MATCH lexeme.

The keyword list is not stored, just a pointer to it. We anticipate that the keyword list is part of the syntax table, and the lexer needs not alter it. Furthermore, the lexer is typically finished before the syntax table is.

```

(Lexer: parameters)+≡
    integer, parameter :: CASE_KEEP = 0, CASE_UP = 1, CASE_DOWN = 2

(Lexer: types)+≡
    type :: lexer_setup_t
    private
    type(template_t), dimension(:), allocatable :: tt
    integer, dimension(:), allocatable :: type
    integer :: keyword_case = CASE_KEEP
    type(keyword_list_t), pointer :: keyword_list => null ()
end type lexer_setup_t

```

Fill the lexer setup object. Some things are hardcoded here (whitespace, alphanumeric identifiers), some are free: comment chars (but these must be single, and comments must be terminated by line-feed), quote chars and matches (must be single), characters to be read as one-character lexeme, special classes (characters of one class that should be glued together as identifiers).

```

(Lexer: procedures)+≡
    subroutine lexer_setup_init (setup, &
        comment_chars, quote_chars, quote_match, &
        single_chars, special_class, &
        keyword_list, upper_case_keywords)
    type(lexer_setup_t), intent(inout) :: setup
    character(*), intent(in) :: comment_chars
    character(*), intent(in) :: quote_chars, quote_match
    character(*), intent(in) :: single_chars
    character(*), dimension(:), intent(in) :: special_class
    type(keyword_list_t), pointer :: keyword_list
    logical, intent(in), optional :: upper_case_keywords
    integer :: n, i
    if (present (upper_case_keywords)) then
        if (upper_case_keywords) then
            setup%keyword_case = CASE_UP
        else
            setup%keyword_case = CASE_DOWN
        end if
    else
        setup%keyword_case = CASE_KEEP
    end if
    n = 1 + len (comment_chars) + len (quote_chars) + 1 &
        + len (single_chars) + size (special_class) + 1
    allocate (setup%tt(n))
    allocate (setup%type(0:n))
    n = 0
    setup%type(n) = NO_MATCH
    n = n + 1
    setup%tt(n) = template_whitespace (WHITESPACE_CHARS)

```



```

setup%type(n) = EMPTY
forall (i = 1:len(comment_chars))
    setup%tt(n+i) = template_quoted (comment_chars(i:i), LF)
    setup%type(n+i) = EMPTY
end forall
n = n + len (comment_chars)
forall (i = 1:len(quote_chars))
    setup%tt(n+i) = template_quoted (quote_chars(i:i), quote_match(i:i))
    setup%type(n+i) = T_QUOTED
end forall
n = n + len (quote_chars)
setup%tt(n+1) = template_numeric ("EeDd")
setup%type(n+1) = T_NUMERIC
n = n + 1
forall (i = 1:len (single_chars))
    setup%tt(n+i) = template_identifier (single_chars(i:i), "")
    setup%type(n+i) = T_IDENTIFIER
end forall
n = n + len (single_chars)
forall (i = 1:size (special_class))
    setup%tt(n+i) = template_identifier &
        (trim (special_class(i)), trim (special_class(i)))
    setup%type(n+i) = T_IDENTIFIER
end forall
n = n + size (special_class)
setup%tt(n+1) = template_identifier &
    (LCLETTERS//UCLETTERS, LCLETTERS//DIGITS//"_"/UCLETTERS)
setup%type(n+1) = T_IDENTIFIER
n = n + 1
if (n /= size (setup%tt)) &
    call msg_bug ("Size mismatch in lexer setup")
setup%keyword_list => keyword_list
end subroutine lexer_setup_init

```

The destructor is needed only if the object is not itself part of an allocatable array

```

<Lexer: procedures>+≡
subroutine lexer_setup_final (setup)
    type(lexer_setup_t), intent(inout) :: setup
    deallocate (setup%tt, setup%type)
    setup%keyword_list => null ()
end subroutine lexer_setup_final

```

For debugging: Write the lexer setup

```

<Lexer: procedures>+≡
subroutine lexer_setup_write (setup, unit)
    type(lexer_setup_t), intent(in) :: setup
    integer, intent(in) :: unit
    integer :: i
    write (unit, "(A)") "Lexer setup:"
    if (allocated (setup%tt)) then
        do i = 1, size (setup%tt)
            call template_write (setup%tt(i), unit)
        end do
    end if
end subroutine lexer_setup_write

```

```

        write (unit, '(A)', advance = "no") " -> "
        call lexeme_type_write (setup%type(i), unit)
        write (unit, *)
    end do
else
    write (unit, *) "[empty]"
end if
if (associated (setup%keyword_list)) then
    call keyword_list_write (setup%keyword_list, unit)
end if
end subroutine lexer_setup_write

```

3.2.5 The lexeme type

An object of this type is returned by the lexer. Apart from the lexeme string, it gives information about the relevant substring (first and last character index) and the lexeme type. Interpreting the string is up to the parser.

```

<Lexer: public>+≡
    public :: lexeme_t

<Lexer: types>+≡
    type :: lexeme_t
    private
        integer :: type = EMPTY
        type(string_t) :: s
        integer :: b = 0, e = 0
    end type lexeme_t

```

Debugging aid:

```

<Lexer: public>+≡
    public :: lexeme_write

<Lexer: procedures>+≡
    subroutine lexeme_write (t, unit)
        type(lexeme_t), intent(in) :: t
        integer, intent(in) :: unit
        integer :: u
        u = output_unit (unit); if (u < 0) return
        select case (t%type)
        case (T_KEYWORD)
            write (u, *) "KEYWORD:  ' " // char (t%s) // "' "
        case (T_IDENTIFIER)
            write (u, *) "IDENTIFIER: ' " // char (t%s) // "' "
        case (T_QUOTED)
            write (u, *) "QUOTED:    ' " // char (t%s) // "' "
        case (T_NUMERIC)
            write (u, *) "NUMERIC:   ' " // char (t%s) // "' "
        case (UNMATCHED_QUOTE)
            write (u, *) "Unmatched quote: "// char (t%s)
        case (OVERFLOW); write (u, *) "Overflow: "// char (t%s)
        case (EMPTY);   write (u, *) "Empty lexeme"
        case (NO_MATCH); write (u, *) "No match"
        case (IO_ERROR); write (u, *) "IO error"
    end subroutine

```

```

        case (EOF);      write (u, *) "EOF"
        case default
            write (u, *) "Error"
        end select
    end subroutine lexeme_write

```

Store string and type in a lexeme. The range determines the beginning and end of the relevant part of the string. Check for a keyword.

<Lexer: procedures>+≡

```

subroutine lexeme_set (t, keyword_list, s, range, type, keyword_case)
    type(lexeme_t), intent(out) :: t
    type(keyword_list_t), pointer :: keyword_list
    type(string_t), intent(in) :: s
    type(string_t) :: keyword
    integer, dimension(2), intent(in) :: range
    integer, intent(in) :: type
    integer, intent(in), optional :: keyword_case
    t%type = type
    if (present (keyword_case)) then
        select case (keyword_case)
            case (CASE_KEEP);    keyword = s
            case (CASE_UP);      keyword = upper_case (s)
            case (CASE_DOWN);    keyword = lower_case (s)
        end select
    else
        keyword = s
    end if
    if (type == T_IDENTIFIER) then
        if (associated (keyword_list)) then
            if (keyword_list_contains (keyword_list, keyword)) &
                t%type = T_KEYWORD
            end if
        end if
        select case (t%type)
            case (T_KEYWORD);    t%s = keyword
            case default;        t%s = s
        end select
        t%b = range(1)
        t%e = range(2)
    end subroutine lexeme_set

subroutine lexeme_clear (t)
    type(lexeme_t), intent(out) :: t
    t%type = EMPTY
    t%s = ""
end subroutine lexeme_clear

```

Retrieve the lexeme string, the relevant part of it, and the type. The last function returns true if there is a break condition reached (error or EOF).

<Lexer: public>+≡

```

public :: lexeme_get_string
public :: lexeme_get_contents
public :: lexeme_get_delimiters

```

```

public :: lexeme_get_type
<Lexer: procedures>+≡
function lexeme_get_string (t) result (s)
  type(string_t) :: s
  type(lexeme_t), intent(in) :: t
  s = t%s
end function lexeme_get_string

function lexeme_get_contents (t) result (s)
  type(string_t) :: s
  type(lexeme_t), intent(in) :: t
  s = extract (t%s, t%b, t%e)
end function lexeme_get_contents

function lexeme_get_delimiters (t) result (del)
  type(string_t), dimension(2) :: del
  type(lexeme_t), intent(in) :: t
  del(1) = extract (t%s, finish = t%b-1)
  del(2) = extract (t%s, start = t%e+1)
end function lexeme_get_delimiters

function lexeme_get_type (t) result (type)
  integer :: type
  type(lexeme_t), intent(in) :: t
  type = t%type
end function lexeme_get_type

```

Check for a generic break condition (error/eof) and for eof in particular.

```

<Lexer: public>+≡
public :: lexeme_is_break
public :: lexeme_is_eof

<Lexer: procedures>+≡
function lexeme_is_break (t) result (break)
  logical :: break
  type(lexeme_t), intent(in) :: t
  select case (t%type)
    case (EOF, IO_ERROR, OVERFLOW, NO_MATCH)
      break = .true.
    case default
      break = .false.
  end select
end function lexeme_is_break

function lexeme_is_eof (t) result (ok)
  logical :: ok
  type(lexeme_t), intent(in) :: t
  ok = t%type == EOF
end function lexeme_is_eof

```

3.2.6 The lexer object

We store the current lexeme and the current line. The line buffer is set each time a new line is read from file. The working buffer has one character more, to hold any trailing blank. Pointers to line and column are for debugging, they will be used to make up readable error messages for the parser.

<Lexer: public>+≡

public :: lexer_t

<Lexer: types>+≡

type :: lexer_t

private

type(lexer_setup_t) :: setup

type(stream_t), pointer :: stream => null ()

type(lexeme_t) :: lexeme

type(string_t) :: previous_line2

type(string_t) :: previous_line1

type(string_t) :: current_line

integer :: lines_read = 0

integer :: current_column = 0

integer :: previous_column = 0

type(string_t) :: buffer

type(lexer_t), pointer :: parent => null ()

end type lexer_t

Create-setup wrapper

<Lexer: public>+≡

public :: lexer_init

<Lexer: procedures>+≡

subroutine lexer_init (lexer, &

comment_chars, quote_chars, quote_match, &

single_chars, special_class, &

keyword_list, upper_case_keywords, &

parent)

type(lexer_t), intent(inout) :: lexer

character(*), intent(in) :: comment_chars

character(*), intent(in) :: quote_chars, quote_match

character(*), intent(in) :: single_chars

character(*), dimension(:), intent(in) :: special_class

type(keyword_list_t), pointer :: keyword_list

logical, intent(in), optional :: upper_case_keywords

type(lexer_t), target, intent(in), optional :: parent

call lexer_setup_init (lexer%setup, &

comment_chars = comment_chars, &

quote_chars = quote_chars, &

quote_match = quote_match, &

single_chars = single_chars, &

special_class = special_class, &

keyword_list = keyword_list, &

upper_case_keywords = upper_case_keywords)

if (present (parent)) lexer%parent => parent

call lexer_clear (lexer)

end subroutine lexer_init

Clear the lexer state, but not the setup. This should be done when the lexing starts, but it is not known whether the lexer was used before.

```

<Lexer: public>+≡
    public :: lexer_clear

<Lexer: procedures>+≡
    subroutine lexer_clear (lexer)
        type(lexer_t), intent(inout) :: lexer
        call lexeme_clear (lexer%lexeme)
        lexer%previous_line2 = ""
        lexer%previous_line1 = ""
        lexer%current_line = ""
        lexer%lines_read = 0
        lexer%current_column = 0
        lexer%previous_column = 0
        lexer%buffer = ""
    end subroutine lexer_clear

```

Reset lexer state and delete setup

```

<Lexer: public>+≡
    public :: lexer_final

<Lexer: procedures>+≡
    subroutine lexer_final (lexer)
        type(lexer_t), intent(inout) :: lexer
        call lexer_clear (lexer)
        call lexer_setup_final (lexer%setup)
    end subroutine lexer_final

```

3.2.7 The lexer routine

For lexing we need to associate an input stream to the lexer.

```

<Lexer: public>+≡
    public :: lexer_assign_stream

<Lexer: procedures>+≡
    subroutine lexer_assign_stream (lexer, stream)
        type(lexer_t), intent(inout) :: lexer
        type(stream_t), intent(in), target :: stream
        lexer%stream => stream
    end subroutine lexer_assign_stream

```

The lexer. The lexer function takes the lexer and returns the currently stored lexeme. If there is none, it is read from buffer, matching against the lexeme templates in the lexer setup. Empty lexemes, i.e., comments and whitespace, are discarded and the buffer is read again until we have found a nonempty lexeme (which may also be EOF or an error condition).

The initial state of the lexer contains an empty lexeme, so reading from buffer is forced. The empty state is restored after returning the lexeme. A nonempty lexeme is present in the lexer only if `lex_back` has been executed before.

The workspace is the `lexer%buffer`, treated as a sort of input stream. We chop off lexemes from the beginning, adjusting the buffer to the left. Whenever the buffer is empty, or we are matching against an open quote which has not terminated, we read a new line and append it to the right. This may result in special conditions, which for simplicity are also returned as lexemes: I/O error, buffer overflow, end of file. If the latter happens during reading a quoted string, we return an unmatched-quote lexeme. Obviously, the special-condition lexemes have to be caught by the parser.

Note that reading further lines is only necessary when reading a quoted string. Otherwise, the line-feed that ends each line is interpreted as whitespace which terminates a preceding lexeme, so there are no other valid multiline lexemes.

To enable meaningful error messages, we also keep track of the line number of the last line read, and the beginning and the end of the current lexeme with respect to this line.

The lexer is implemented as a function that returns the next lexeme (i.e., token). It uses the `lexer` setup and modifies the buffers and pointers stored within the lexer, a side effect. The lexer reads from an input stream object, which also is modified by this reading, e.g., a line pointer is advanced.

```

(Lexer: public)+≡
    public :: lex

(Lexer: procedures)+≡
    subroutine lex (lexeme, lexer)
        type(lexeme_t), intent(out) :: lexeme
        type(lexer_t), intent(inout) :: lexer
        integer :: iostat1, iostat2
        integer :: pos
        integer, dimension(2) :: range
        integer :: template_index, type
        if (.not. associated (lexer%stream)) &
            call msg_bug ("Lexer called without assigned stream")
        GET_LEXEME: do while (lexeme_get_type (lexer%lexeme) == EMPTY)
            if (len (lexer%buffer) /= 0) then
                iostat1 = 0
            else
                call lexer_read_line (lexer, iostat1)
            end if
            select case (iostat1)
            case (0)
                MATCH_BUFFER: do
                    call match (lexer%setup%tt, char (lexer%buffer), &
                                pos, range, template_index)
                    if (pos >= 0) then
                        type = lexer%setup%type(template_index)
                        exit MATCH_BUFFER
                    else
                        pos = 0
                        call lexer_read_line (lexer, iostat2)
                        select case (iostat2)
                        case (EOF); type = UNMATCHED_QUOTE; exit MATCH_BUFFER
                        case (1);  type = IO_ERROR;      exit MATCH_BUFFER
                        case (2);  type = OVERFLOW;       exit MATCH_BUFFER

```

```

        end select
    end if
    end do MATCH_BUFFER
    case (EOF); type = EOF
    case (1);   type = IO_ERROR
    case (2);   type = OVERFLOW
    end select
    call lexeme_set (lexer%lexeme, lexer%setup%keyword_list, &
        extract (lexer%buffer, finish=pos), range, type, &
        lexer%setup%keyword_case)
    lexer%buffer = remove (lexer%buffer, finish=pos)
    lexer%previous_column = lexer%current_column
    lexer%current_column = lexer%current_column + pos
end do GET_LEXEME
lexeme = lexer%lexeme
call lexeme_clear (lexer%lexeme)
end subroutine lex

```

Read a line and append it to the input buffer. If the input buffer overflows, return `iostat=2`. Otherwise, `iostat=1` indicates an I/O error, and `iostat=-1` the EOF.

The input stream may either be an external unit or a `ifile` object. In the latter case, a line is read and the line pointer is advanced.

Note that inserting LF between input lines is the Unix convention. Since we are doing this explicitly when gluing lines together, we can pattern-match against LF without having to worry about the system.

```

<Lexer: procedures>+≡
subroutine lexer_read_line (lexer, iostat)
    type(lexer_t), intent(inout) :: lexer
    integer, intent(out) :: iostat
    type(string_t) :: current_line
    current_line = lexer%current_line
    call stream_get_record (lexer%stream, lexer%current_line, iostat)
    if (iostat == 0) then
        lexer%lines_read = lexer%lines_read + 1
        lexer%previous_line2 = lexer%previous_line1
        lexer%previous_line1 = current_line
        lexer%buffer = lexer%buffer // lexer%current_line // LF
        lexer%previous_column = 0
        lexer%current_column = 0
    end if
end subroutine lexer_read_line

```

Once in a while we have read one lexeme too many, which can be pushed back into the input stream. Do not do this more than once.

```

<Lexer: public>+≡
public :: lexer_put_back

<Lexer: procedures>+≡
subroutine lexer_put_back (lexer, lexeme)
    type(lexer_t), intent(inout) :: lexer
    type(lexeme_t), intent(in) :: lexeme
    if (lexeme_get_type (lexer%lexeme) == EMPTY) then

```



```

        lexer%lexeme = lexeme
    else
        call msg_bug (" Lexer: lex_back fails; probably called twice")
    end if
end subroutine lexer_put_back

```

3.2.8 Diagnostics

For debugging: print just the setup

```

<Lexer: public>+≡
    public :: lexer_write_setup

<Lexer: procedures>+≡
    subroutine lexer_write_setup (lexer, unit)
        type(lexer_t), intent(in) :: lexer
        integer, intent(in), optional :: unit
        integer :: u
        u = output_unit (unit); if (u < 0) return
        call lexer_setup_write (lexer%setup, u)
    end subroutine lexer_write_setup

```

This is useful for error printing: show the current line with index and a pointer to the current column within the line.

```

<Lexer: public>+≡
    public :: lexer_show_location

<Lexer: procedures>+≡
    subroutine lexer_show_location (lexer)
        type(lexer_t), intent(in) :: lexer
        type(string_t) :: loc_str
        if (associated (lexer%parent)) then
            call lexer_show_source (lexer%parent)
            call msg_message ("[includes]")
        else
            call msg_message ()
        end if
        if (associated (lexer%stream)) then
            call msg_message &
                (char (stream_get_record_info_string (lexer%stream)) // ":")
        end if
        if (lexer%lines_read >= 4) call msg_result ("[...]")
        if (lexer%lines_read >= 3) call msg_result (char (lexer%previous_line2))
        if (lexer%lines_read >= 2) call msg_result (char (lexer%previous_line1))
        if (lexer%lines_read >= 1) then
            call msg_result (char (lexer%current_line))
            loc_str = repeat (" ", lexer%previous_column)
            loc_str = loc_str // "^"
            if (lexer%current_column > lexer%previous_column) then
                loc_str = loc_str &
                    // repeat ("-", max (lexer%current_column &
                        - lexer%previous_column - 1, 0)) &
                    // "^"
            end if
        end if
    end subroutine lexer_show_location

```

```

        call msg_result (char (loc_str))
    end if
end subroutine lexer_show_location

```

This just prints the current stream source.

<Lexer: procedures>+≡

```

recursive subroutine lexer_show_source (lexer)
    type(lexer_t), intent(in) :: lexer
    type(string_t) :: loc_str
    if (associated (lexer%parent)) then
        call lexer_show_source (lexer%parent)
        call msg_message ("[includes]")
    else
        call msg_message ()
    end if
    if (associated (lexer%stream)) then
        call msg_message &
            (char (stream_get_source_info_string (lexer%stream)) // ":")
    end if
end subroutine lexer_show_source

```

Test the lexer by lexing and printing all lexemes from unit u, one per line, using preset conventions

<Lexer: public>+≡

```

public :: lexer_test

```

<Lexer: procedures>+≡

```

subroutine lexer_test (lexer, unit)
    type(lexer_t), intent(inout) :: lexer
    integer, intent(in) :: unit
    type(stream_t), target :: stream
    type(string_t) :: string
    type(lexeme_t) :: lexeme
    string = "abcdefghij"
    call lexer_init (lexer, &
        comment_chars = "", &
        quote_chars = "<'\"", &
        quote_match = ">'\"", &
        single_chars = "?*+=,()", &
        special_class = ("/ "." /), &
        keyword_list = null ())
    call stream_init (stream, string)
    call lexer_assign_stream (lexer, stream)
    do
        call lex (lexeme, lexer)
        call lexeme_write (lexeme, unit)
        if (lexeme_is_break (lexeme)) exit
    end do
    call stream_final (stream)
    call lexer_final (lexer)
end subroutine lexer_test

```

3.3 Syntax rules

This module provides tools to handle syntax rules in an abstract way.

```
<syntax_rules.f90>≡  
<File header>  
  
module syntax_rules  
  
  <Use strings>  
  <Use file utils>  
  use limits, only: UNQUOTED !NODEP!  
  use diagnostics !NODEP!  
  use ifiles, only: line_p, line_init, line_get_string_advance, line_final  
  use ifiles, only: ifile_t, ifile_get_length  
  use lexers  
  
  <Standard module head>  
  
  <Syntax: public>  
  
  <Syntax: parameters>  
  
  <Syntax: types>  
  
  <Syntax: interfaces>  
  
contains  
  
  <Syntax: subroutines>  
  
end module syntax_rules
```

3.3.1 Syntax rules

Syntax rules are used by the parser. They determine how to translate the stream of lexemes as returned by the lexer into the parse tree node. A rule may be terminal, i.e., replace a matching lexeme into a terminal node. The node will contain the lexeme interpreted as a recognized token:

- a keyword: unquoted fixed character string;
- a real number, to be determined at runtime;
- an integer, to be determined at runtime;
- a boolean value, to be determined at runtime;
- a quoted token (e.g., string), to be determined at runtime;
- an identifier (unquoted string that is not a recognized keyword), to be determined at runtime.

It may be nonterminal, i.e., contain a sequence of child rules. These are matched consecutively (and recursively) against the input stream; the resulting node will be a branch node.

- the file, i.e., the input stream as a whole;
- a sequence of syntax elements, where the last syntax element may be optional, or optional repetitive;

Sequences carry a flag that tells whether the last child is optional or may be repeated an arbitrary number of times, corresponding to the regexp modifiers `?`, `*`, and `+`.

We also need an alternative rule; this will be replaced by the node generated by one of its children that matches; thus, it does not create a node of its own.

- an alternative of syntax elements.

We also define special types of sequences as convenience macros:

- a list: a sequence where the elements are separated by a separator keyword (e.g., commas), the separators are thrown away when parsing the list;
- a group: a sequence of three tokens, where the first and third ones are left and right delimiters, the delimiters are thrown away;
- an argument list: a delimited list, containing both delimiters and separators.

It would be great to have a polymorphic type for this purpose, but until Fortran 2003 is out we have to emulate this.

Here are the syntax element codes:

```

<Syntax: public>≡
  public :: S_UNKNOWN
  public :: S_LOGICAL, S_INTEGER, S_REAL, S_COMPLEX, S_QUOTED
  public :: S_IDENTIFIER, S_KEYWORD
  public :: S_SEQUENCE, S_LIST, S_GROUP, S_ARGS
  public :: S_ALTERNATIVE
  public :: S_IGNORE

<Syntax: parameters>≡
  integer, parameter :: &
    S_UNKNOWN = 0, &
    S_LOGICAL = 1, S_INTEGER = 2, S_REAL = 3, S_COMPLEX = 4, &
    S_QUOTED = 5, S_IDENTIFIER = 6, S_KEYWORD = 7, &
    S_SEQUENCE = 8, S_LIST = 9, S_GROUP = 10, S_ARGS = 11, &
    S_ALTERNATIVE = 12, &
    S_IGNORE = 99

```

We need arrays of rule pointers, therefore this construct.

```

<Syntax: types>≡
  type :: rule_p
  private
    type(syntax_rule_t), pointer :: p => null ()
  end type rule_p

```

Return the association status of the rule pointer:

```

<Syntax: subroutines>≡
  elemental function rule_is_associated (rp) result (ok)
    logical :: ok
    type (rule_p), intent(in) :: rp
    ok = associated (rp%p)
  end function rule_is_associated

```

The rule type is one of the types listed above, represented by an integer code. The keyword, for a non-keyword rule, is an identifier used for the printed syntax table. The array of children is needed for nonterminal rules. In that case, there is a modifier for the last element (blank, "?", "*", or "+"), mirrored in the flags **opt** and **rep**. Then, we have the character constants used as separators and delimiters for this rule. Finally, the **used** flag can be set to indicate that this rule is the child of another rule.

```

<Syntax: types>+≡
  public :: syntax_rule_t

<Syntax: types>+≡
  type :: syntax_rule_t
    private
    integer :: type = S_UNKNOWN
    logical :: used = .false.
    type(string_t) :: keyword
    type(string_t) :: separator
    type(string_t), dimension(2) :: delimiter
    type(rule_p), dimension(:), allocatable :: child
    character(1) :: modifier = ""
    logical :: opt = .false., rep = .false.
  end type syntax_rule_t

```

Initializer: Set type and key for a rule, but do not (yet) allocate anything.

Finalizer: not needed (no pointer components).

```

<Syntax: subroutines>+≡
  subroutine syntax_rule_init (rule, key, type)
    type(syntax_rule_t), intent(inout) :: rule
    type(string_t), intent(in) :: key
    integer, intent(in) :: type
    rule%keyword = key
    rule%type = type
    select case (rule%type)
    case (S_GROUP)
      call syntax_rule_set_delimiter (rule)
    case (S_LIST)
      call syntax_rule_set_separator (rule)
    case (S_ARGS)
      call syntax_rule_set_delimiter (rule)
      call syntax_rule_set_separator (rule)
    end select
  end subroutine syntax_rule_init

```

3.3.2 I/O

These characters will not be enclosed in quotes when writing syntax rules:

```
<Limits: public parameters>+≡
    character(*), parameter, public :: &
        UNQUOTED = "(),|_//LCLETTERS//UCLETTERS//DIGITS
```

Write an account of the rule. Setting `short` true will suppress the node type. Setting `key_only` true will suppress the definition. Setting `advance` false will suppress the trailing newline.

```
<Syntax: public>+≡
    public :: syntax_rule_write

<Syntax: subroutines>+≡
    subroutine syntax_rule_write (rule, unit, short, key_only, advance)
        type(syntax_rule_t), intent(in) :: rule
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: short, key_only, advance
        logical :: typ, def, adv
        integer :: u
        u = output_unit (unit); if (u < 0) return
        typ = .true.; if (present (short)) typ = .not. short
        def = .true.; if (present (key_only)) def = .not. key_only
        adv = .true.; if (present (advance)) adv = advance
        select case (rule%type)
        case (S_UNKNOWN); call write_atom ("???", typ)
        case (S_IGNORE); call write_atom ("IGNORE", typ)
        case (S_LOGICAL); call write_atom ("LOGICAL", typ)
        case (S_INTEGER); call write_atom ("INTEGER", typ)
        case (S_REAL); call write_atom ("REAL", typ)
        case (S_COMPLEX); call write_atom ("COMPLEX", typ)
        case (S_IDENTIFIER); call write_atom ("IDENTIFIER", typ)
        case (S_KEYWORD); call write_atom ("KEYWORD", typ)
        case (S_QUOTED)
            call write_quotes (typ, def, del = rule%delimiter)
        case (S_SEQUENCE)
            call write_sequence ("SEQUENCE", typ, def, size (rule%child))
        case (S_GROUP)
            call write_sequence ("GROUP", typ, def, size (rule%child), &
                del = rule%delimiter)
        case (S_LIST)
            call write_sequence ("LIST", typ, def, size (rule%child), &
                sep = rule%separator)
        case (S_ARGS)
            call write_sequence ("ARGUMENTS", typ, def, size (rule%child), &
                del = rule%delimiter, sep = rule%separator)
        case (S_ALTERNATIVE)
            call write_sequence ("ALTERNATIVE", typ, def, size (rule%child), &
                sep = var_str ("|"))
        end select
        if (adv) write (u, *)
contains
    subroutine write_type (type)
        character(*), intent(in) :: type
        character(11) :: str
```

```

    str = type
    write (u, "(1x,A)", advance="no") str
end subroutine write_type
subroutine write_key
    write (u, "(1x,A)", advance="no") char (wkey (rule))
end subroutine write_key
subroutine write_atom (type, typ)
    character(*), intent(in) :: type
    logical, intent(in) :: typ
    if (typ) call write_type (type)
    call write_key
end subroutine write_atom
subroutine write_maybe_quoted (string)
    character(*), intent(in) :: string
    character, parameter :: q = '"'
    character, parameter :: qq = '\''
    if (verify (string, UNQUOTED) == 0) then
        write (u, "(1x,A)", advance = "no") trim (string)
    else if (verify (string, q) == 0) then
        write (u, "(1x,A)", advance = "no") qq // trim (string) // qq
    else
        write (u, "(1x,A)", advance = "no") q // trim (string) // q
    end if
end subroutine write_maybe_quoted
subroutine write_quotes (typ, def, del)
    logical, intent(in) :: typ, def
    type(string_t), dimension(2), intent(in) :: del
    if (typ) call write_type ("QUOTED")
    call write_key
    if (def) then
        write (u, "(1x,'=')", advance="no")
        call write_maybe_quoted (char (del(1)))
        write (u, "(1x,A)", advance="no") "... "
        call write_maybe_quoted (char (del(2)))
    end if
end subroutine write_quotes
subroutine write_sequence (type, typ, def, n, del, sep)
    character(*), intent(in) :: type
    logical, intent(in) :: typ, def
    integer, intent(in) :: n
    type(string_t), dimension(2), intent(in), optional :: del
    type(string_t), intent(in), optional :: sep
    integer :: i
    if (typ) call write_type (type)
    call write_key
    if (def) then
        write (u, "(1x,'=')", advance="no")
        if (present (del)) call write_maybe_quoted (char (del(1)))
        do i = 1, n
            if (i > 1 .and. present (sep)) &
                call write_maybe_quoted (char (sep))
            write (u, "(1x,A)", advance="no") &
                char (wkey (syntax_rule_get_sub_ptr(rule, i)))
            if (i == n) write (u, "(A)", advance="no") trim (rule%modifier)
        end do
    end if
end subroutine write_sequence

```

```

        end do
        if (present (del)) call write_maybe_quoted (char (del(2)))
        end if
    end subroutine write_sequence
end subroutine syntax_rule_write

```

In the printed representation, the keyword strings are enclosed as `<...>`, unless they are bare keywords. Bare keywords are enclosed as `'..'` if they contain a character which is not a letter, digit, or underscore. If they contain a single-quote character, they are enclosed as `".."`. (A keyword must not contain both single- and double-quotes.)

```

<Syntax: subroutines>+≡
function wkey (rule) result (string)
    type(string_t) :: string
    type(syntax_rule_t), intent(in) :: rule
    select case (rule%type)
    case (S_KEYWORD)
        if (verify (rule%keyword, UNQUOTED) == 0) then
            string = rule%keyword
        else if (scan (rule%keyword, "'") == 0) then
            string = "'" // rule%keyword // "'"
        else
            string = '""' // rule%keyword // '""'
        end if
    case default
        string = "<" // rule%keyword // ">"
    end select
end function wkey

```

3.3.3 Completing syntax rules

Set the separator and delimiter entries, using defaults:

```

<Syntax: subroutines>+≡
subroutine syntax_rule_set_separator (rule, separator)
    type(syntax_rule_t), intent(inout) :: rule
    type(string_t), intent(in), optional :: separator
    if (present (separator)) then
        rule%separator = separator
    else
        rule%separator = ","
    end if
end subroutine syntax_rule_set_separator

subroutine syntax_rule_set_delimiter (rule, delimiter)
    type(syntax_rule_t), intent(inout) :: rule
    type(string_t), dimension(2), intent(in), optional :: delimiter
    if (present (delimiter)) then
        rule%delimiter = delimiter
    else
        rule%delimiter = (/ "(", ")" /)
    end if
end subroutine syntax_rule_set_delimiter

```



```
end subroutine syntax_rule_set_delimiter
```

Set the modifier entry and corresponding flags:

<Syntax: subroutines>+≡

```
function is_modifier (string) result (ok)
  logical :: ok
  type(string_t), intent(in) :: string
  select case (char (string))
    case (" ", "?", "*", "+"); ok = .true.
    case default; ok = .false.
  end select
end function is_modifier

subroutine syntax_rule_set_modifier (rule, modifier)
  type(syntax_rule_t), intent(inout) :: rule
  type(string_t), intent(in) :: modifier
  rule%modifier = char (modifier)
  select case (rule%modifier)
    case (" ")
    case ("?"); rule%opt = .true.
    case ("*"); rule%opt = .true.; rule%rep = .true.
    case ("+"); rule%rep = .true.
    case default
      call msg_bug (" Syntax: sequence modifier '" // rule%modifier &
        // "' is not one of '+' '*' '?'")
  end select
end subroutine syntax_rule_set_modifier
```

Check a finalized rule for completeness

<Syntax: subroutines>+≡

```
subroutine syntax_rule_check (rule)
  type(syntax_rule_t), intent(in) :: rule
  if (rule%keyword == "") call msg_bug ("Rule key not set")
  select case (rule%type)
    case (S_UNKNOWN); call bug (" Undefined rule")
    case (S_IGNORE, S_LOGICAL, S_INTEGER, S_REAL, S_COMPLEX, &
      S_IDENTIFIER, S_KEYWORD)
    case (S_QUOTED)
      if (any (rule%delimiter == "")) call bug (" Missing quote character(s)")
    case (S_SEQUENCE)
    case (S_GROUP)
      if (any (rule%delimiter == "")) call bug (" Missing delimiter(s)")
    case (S_LIST)
      if (rule%separator == "") call bug (" Missing separator")
    case (S_ARGS)
      if (any (rule%delimiter == "")) call bug (" Missing delimiter(s)")
      if (rule%separator == "") call bug (" Missing separator")
    case (S_ALTERNATIVE)
    case default
      call bug (" Undefined syntax code")
  end select
  select case (rule%type)
    case (S_SEQUENCE, S_GROUP, S_LIST, S_ARGS, S_ALTERNATIVE)
```

```

        if (allocated (rule%child)) then
            if (.not.all (rule_is_associated (rule%child))) &
                call bug (" Child rules not all associated")
        else
            call bug (" Parent rule without children")
        end if
    case default
        if (allocated (rule%child)) call bug (" Non-parent rule with children")
    end select
contains
    subroutine bug (string)
        character(*), intent(in) :: string
        call msg_bug (" Syntax table: Rule " // char (rule%keyword) // ": " &
            // string)
    end subroutine bug
end subroutine syntax_rule_check

```

3.3.4 Accessing rules

This is the API for syntax rules:

```

<Syntax: public>+≡
    public :: syntax_rule_get_type

<Syntax: subroutines>+≡
    function syntax_rule_get_type (rule) result (type)
        integer :: type
        type(syntax_rule_t), intent(in) :: rule
        type = rule%type
    end function syntax_rule_get_type

<Syntax: public>+≡
    public :: syntax_rule_get_key

<Syntax: subroutines>+≡
    function syntax_rule_get_key (rule) result (key)
        type(string_t) :: key
        type(syntax_rule_t), intent(in) :: rule
        key = rule%keyword
    end function syntax_rule_get_key

<Syntax: public>+≡
    public :: syntax_rule_get_separator
    public :: syntax_rule_get_delimiter

<Syntax: subroutines>+≡
    function syntax_rule_get_separator (rule) result (separator)
        type(string_t) :: separator
        type(syntax_rule_t), intent(in) :: rule
        separator = rule%separator
    end function syntax_rule_get_separator

    function syntax_rule_get_delimiter (rule) result (delimiter)
        type(string_t), dimension(2) :: delimiter

```

```

    type(syntax_rule_t), intent(in) :: rule
    delimiter = rule%delimiter
end function syntax_rule_get_delimiter

```

Accessing child rules. If we use `syntax_rule_get_n_sub` for determining loop bounds, we do not need a check in the second routine.

```

<Syntax: public>+≡
    public :: syntax_rule_get_n_sub
    public :: syntax_rule_get_sub_ptr

<Syntax: subroutines>+≡
    function syntax_rule_get_n_sub (rule) result (n)
        integer :: n
        type(syntax_rule_t), intent(in) :: rule
        if (allocated (rule%child)) then
            n = size (rule%child)
        else
            n = 0
        end if
    end function syntax_rule_get_n_sub

    function syntax_rule_get_sub_ptr (rule, i) result (sub)
        type(syntax_rule_t), pointer :: sub
        type(syntax_rule_t), intent(in), target :: rule
        integer, intent(in) :: i
        sub => rule%child(i)%p
    end function syntax_rule_get_sub_ptr

    subroutine syntax_rule_set_sub (rule, i, sub)
        type(syntax_rule_t), intent(inout) :: rule
        integer, intent(in) :: i
        type(syntax_rule_t), intent(in), target :: sub
        rule%child(i)%p => sub
    end subroutine syntax_rule_set_sub

```

Return the modifier flags:

```

<Syntax: public>+≡
    public :: syntax_rule_last_optional
    public :: syntax_rule_last_repetitive

<Syntax: subroutines>+≡
    function syntax_rule_last_optional (rule) result (opt)
        logical :: opt
        type(syntax_rule_t), intent(in) :: rule
        opt = rule%opt
    end function syntax_rule_last_optional
    function syntax_rule_last_repetitive (rule) result (rep)
        logical :: rep
        type(syntax_rule_t), intent(in) :: rule
        rep = rule%rep
    end function syntax_rule_last_repetitive

```

Return true if the rule is atomic, i.e., logical, real, keyword etc.

```
<Syntax: public>+≡
    public :: syntax_rule_is_atomic

<Syntax: subroutines>+≡
    function syntax_rule_is_atomic (rule) result (atomic)
        logical :: atomic
        type(syntax_rule_t), intent(in) :: rule
        select case (rule%type)
            case (S_LOGICAL, S_INTEGER, S_REAL, S_COMPLEX, S_IDENTIFIER, &
                 S_KEYWORD, S_QUOTED)
                atomic = .true.
            case default
                atomic = .false.
        end select
    end function syntax_rule_is_atomic
```

3.3.5 Syntax tables

A syntax table contains the tree of syntax rules and, for direct parser access, the list of valid keywords.

Types

The syntax contains an array of rules and a list of keywords. The array is actually used as a tree, where the top rule is the first array element, and the other rules are recursively pointed to by this first rule. (No rule should be used twice or be unused.) The keyword list is derived from the rule tree.

Objects of this type need the target attribute if they are associated with a lexer. The keyword list will be pointed to by this lexer.

```
<Syntax: public>+≡
    public :: syntax_t

<Syntax: types>+≡
    type :: syntax_t
        private
        type(syntax_rule_t), dimension(:), allocatable :: rule
        type(keyword_list_t) :: keyword_list
    end type syntax_t
```

Constructor/destructor

Initialize and finalize syntax tables

```
<Syntax: public>+≡
    public :: syntax_init
    public :: syntax_final
```

There are two ways to create a syntax: hard-coded from rules or dynamically from file.

```

<Syntax: interfaces>≡
interface syntax_init
  module procedure syntax_init_from_ifile
end interface

```

The syntax definition is read from an ifile object which contains the syntax definitions in textual form, one rule per line. This interface allows for determining the number of rules beforehand.

To parse the rule definitions, we make up a temporary lexer. Obviously, we cannot use a generic parser yet, so we have to hardcode the parsing process.

```

<Syntax: subroutines>+=
subroutine syntax_init_from_ifile (syntax, ifile)
  type(syntax_t), intent(out), target :: syntax
  type(ifile_t), intent(in) :: ifile
  type(lexer_t) :: lexer
  type(line_p) :: line
  type(string_t) :: string
  integer :: n_token
  integer :: i
  call lexer_init (lexer, &
    comment_chars = "", &
    quote_chars = "<'\"", &
    quote_match = ">'\"", &
    single_chars = "?*+|=,()", &
    special_class = (/ "." /), &
    keyword_list = null ())
  allocate (syntax%rule (ifile_get_length (ifile)))
  call line_init (line, ifile)
  do i = 1, size (syntax%rule)
    string = line_get_string_advance (line)
    call set_rule_type_and_key (syntax%rule(i), string, lexer)
  end do
  call line_init (line, ifile)
  do i = 1, size (syntax%rule)
    string = line_get_string_advance (line)
    select case (syntax%rule(i)%type)
    case (S_QUOTED, S_SEQUENCE, S_GROUP, S_LIST, S_ARGS, S_ALTERNATIVE)
      n_token = get_n_token (string, lexer)
      call set_rule_contents &
        (syntax%rule(i), syntax, n_token, string, lexer)
    end select
  end do
  call line_final (line)
  call lexer_final (lexer)
  call syntax_make_keyword_list (syntax)
  if (.not. all (syntax%rule%used)) then
    do i = 1, size (syntax%rule)
      if (.not. syntax%rule(i)%used) then
        call syntax_rule_write (syntax%rule(i), 6)
      end if
    end do
  end do
end do

```

```

        call msg_bug (" Syntax table: unused rules")
    end if
end subroutine syntax_init_from_ifile

```

For a given rule defined in the input, the first task is to determine its type and key. With these, we can initialize the rule in the table, postponing the association of children.

```

<Syntax: subroutines>+=
subroutine set_rule_type_and_key (rule, string, lexer)
    type(syntax_rule_t), intent(inout) :: rule
    type(string_t), intent(in) :: string
    type(lexer_t), intent(inout) :: lexer
    type(stream_t), target :: stream
    type(lexeme_t) :: lexeme
    type(string_t) :: key
    character(2) :: type
    call lexer_clear (lexer)
    call stream_init (stream, string)
    call lexer_assign_stream (lexer, stream)
    call lex (lexeme, lexer)
    type = lexeme_get_string (lexeme)
    call lex (lexeme, lexer)
    key = lexeme_get_contents (lexeme)
    call stream_final (stream)
    if (trim (key) /= "") then
        select case (type)
            case ("IG"); call syntax_rule_init (rule, key, S_IGNORE)
            case ("LO"); call syntax_rule_init (rule, key, S_LOGICAL)
            case ("IN"); call syntax_rule_init (rule, key, S_INTEGER)
            case ("RE"); call syntax_rule_init (rule, key, S_REAL)
            case ("CO"); call syntax_rule_init (rule, key, S_COMPLEX)
            case ("ID"); call syntax_rule_init (rule, key, S_IDENTIFIER)
            case ("KE"); call syntax_rule_init (rule, key, S_KEYWORD)
            case ("QU"); call syntax_rule_init (rule, key, S_QUOTED)
            case ("SE"); call syntax_rule_init (rule, key, S_SEQUENCE)
            case ("GR"); call syntax_rule_init (rule, key, S_GROUP)
            case ("LI"); call syntax_rule_init (rule, key, S_LIST)
            case ("AR"); call syntax_rule_init (rule, key, S_ARGS)
            case ("AL"); call syntax_rule_init (rule, key, S_ALTERNATIVE)
            case default
                call lexer_show_location (lexer)
                call msg_bug (" Syntax definition: unknown type '" // type // "'")
            end select
        else
            print *, char (string)
            call msg_bug (" Syntax definition: empty rule key")
        end if
    end subroutine set_rule_type_and_key

```

This function returns the number of tokens in an input line.

```

<Syntax: subroutines>+=
function get_n_token (string, lexer) result (n)
    integer :: n

```

```

type(string_t), intent(in) :: string
type(lexer_t), intent(inout) :: lexer
type(stream_t), target :: stream
type(lexeme_t) :: lexeme
integer :: i
call lexer_clear (lexer)
call stream_init (stream, string)
call lexer_assign_stream (lexer, stream)
i = 0
do
    call lex (lexeme, lexer)
    if (lexeme_is_break (lexeme)) exit
    i = i + 1
end do
n = i
call stream_final (stream)
end function get_n_token

```

This subroutine extracts the rule contents for an input line. There are three tasks: (1) determine the number of children, depending on the rule type; (2) find and set the separator and delimiter strings, if required; (3) scan the child rules, find them in the syntax table and associate the parent rule with them.

(*Syntax: subroutines*)+≡

```

subroutine set_rule_contents (rule, syntax, n_token, string, lexer)
    type(syntax_rule_t), intent(inout) :: rule
    type(syntax_t), intent(in), target :: syntax
    integer, intent(in) :: n_token
    type(string_t), intent(in) :: string
    type(lexer_t), intent(inout) :: lexer
    type(stream_t), target :: stream
    type(lexeme_t), dimension(n_token) :: lexeme
    integer :: i, n_children
    call lexer_clear (lexer)
    call stream_init (stream, string)
    call lexer_assign_stream (lexer, stream)
    do i = 1, n_token
        call lex (lexeme(i), lexer)
    end do
    call stream_final (stream)
    n_children = get_n_children ()
    call set_delimiters
    if (n_children > 1) call set_separator
    if (n_children > 0) call set_children
contains
    function get_n_children () result (n_children)
        integer :: n_children
        select case (rule%type)
        case (S_QUOTED)
            if (n_token /= 6) call broken_rule (rule)
            n_children = 0
        case (S_GROUP)
            if (n_token /= 6) call broken_rule (rule)
            n_children = 1

```

```

case (S_SEQUENCE)
  if (is_modifier (lexeme_get_string (lexeme(n_token)))) then
    if (n_token <= 4) call broken_rule (rule)
    call syntax_rule_set_modifier &
      (rule, lexeme_get_string (lexeme(n_token)))
    n_children = n_token - 4
  else
    if (n_token <= 3) call broken_rule (rule)
    n_children = n_token - 3
  end if
case (S_LIST)
  if (is_modifier (lexeme_get_string (lexeme(n_token)))) then
    if (n_token <= 4 .or. mod (n_token, 2) /= 1) &
      call broken_rule (rule)
    call syntax_rule_set_modifier &
      (rule, lexeme_get_string (lexeme(n_token)))
  else if (n_token <= 3 .or. mod (n_token, 2) /= 0) then
    call broken_rule (rule)
  end if
  n_children = (n_token - 2) / 2
case (S_ARGS)
  if (is_modifier (lexeme_get_string (lexeme(n_token-1)))) then
    if (n_token <= 6 .or. mod (n_token, 2) /= 1) &
      call broken_rule (rule)
    call syntax_rule_set_modifier &
      (rule, lexeme_get_string (lexeme(n_token-1)))
  else if (n_token <= 5 .or. mod (n_token, 2) /= 0) then
    call broken_rule (rule)
  end if
  n_children = (n_token - 4) / 2
case (S_ALTERNATIVE)
  if (n_token <= 3 .or. mod (n_token, 2) /= 0) call broken_rule (rule)
  n_children = (n_token - 2) / 2
end select
end function get_n_children
subroutine set_delimiters
  type(string_t), dimension(2) :: delimiter
  select case (rule%type)
  case (S_QUOTED, S_GROUP, S_ARGS)
    delimiter(1) = lexeme_get_contents (lexeme(4))
    delimiter(2) = lexeme_get_contents (lexeme(n_token))
    call syntax_rule_set_delimiter (rule, delimiter)
  end select
end subroutine set_delimiters
subroutine set_separator
  type(string_t) :: separator
  select case (rule%type)
  case (S_LIST)
    separator = lexeme_get_contents (lexeme(5))
    call syntax_rule_set_separator (rule, separator)
  case (S_ARGS)
    separator = lexeme_get_contents (lexeme(6))
    call syntax_rule_set_separator (rule, separator)
  end select
end subroutine set_separator

```



```

end subroutine set_separator
subroutine set_children
  allocate (rule%child(n_children))
  select case (rule%type)
  case (S_GROUP)
    call syntax_rule_set_sub (rule, 1, syntax_get_rule_ptr (syntax, &
      lexeme_get_contents (lexeme(5))))
  case (S_SEQUENCE)
    do i = 1, n_children
      call syntax_rule_set_sub (rule, i, syntax_get_rule_ptr (syntax, &
        lexeme_get_contents (lexeme(i+3))))
    end do
  case (S_LIST, S_ALTERNATIVE)
    do i = 1, n_children
      call syntax_rule_set_sub (rule, i, syntax_get_rule_ptr (syntax, &
        lexeme_get_contents (lexeme(2*i+2))))
    end do
  case (S_ARGS)
    do i = 1, n_children
      call syntax_rule_set_sub (rule, i, syntax_get_rule_ptr (syntax, &
        lexeme_get_contents (lexeme(2*i+3))))
    end do
  end select
end subroutine set_children
subroutine broken_rule (rule)
  type(syntax_rule_t), intent(in) :: rule
  call lexer_show_location (lexer)
  call msg_bug (" Syntax definition: broken rule '" &
    // char (wkey (rule)) // "'")
end subroutine broken_rule
end subroutine set_rule_contents

```

This routine completes the syntax table object. We assume that the rule array is set up. We associate the top rule with the first entry in the rule array and build up the keyword list.

The keyword list includes delimiters and separators. Filling it can only be done after all rules are set. We scan the rule tree. For each keyword that we find, we try to add it to the keyword list; the pointer to the last element is carried along with the recursive scanning. Before appending a keyword, we check whether it is already in the list.

(Syntax: subroutines)+≡

```

subroutine syntax_make_keyword_list (syntax)
  type(syntax_t), intent(inout), target :: syntax
  type(syntax_rule_t), pointer :: rule
  rule => syntax%rule(1)
  call rule_scan_rec (rule, syntax%keyword_list)
contains
  recursive subroutine rule_scan_rec (rule, keyword_list)
    type(syntax_rule_t), pointer :: rule
    type(keyword_list_t), intent(inout) :: keyword_list
    integer :: i
    if (rule%used) return
    rule%used = .true.

```

```

select case (rule%type)
case (S_UNKNOWN)
  call msg_bug (" Syntax: rule tree contains undefined rule")
case (S_KEYWORD)
  call keyword_list_add (keyword_list, rule%keyword)
end select
select case (rule%type)
case (S_LIST, S_ARGS)
  call keyword_list_add (keyword_list, rule%separator)
end select
select case (rule%type)
case (S_GROUP, S_ARGS)
  call keyword_list_add (keyword_list, rule%delimiter(1))
  call keyword_list_add (keyword_list, rule%delimiter(2))
end select
select case (rule%type)
case (S_SEQUENCE, S_GROUP, S_LIST, S_ARGS, S_ALTERNATIVE)
  if (.not. allocated (rule%child)) &
    call msg_bug (" Syntax: Non-terminal rule without children")
case default
  if (allocated (rule%child)) &
    call msg_bug (" Syntax: Terminal rule with children")
end select
if (allocated (rule%child)) then
  do i = 1, size (rule%child)
    call rule_scan_rec (rule%child(i)%p, keyword_list)
  end do
end if
end subroutine rule_scan_rec
end subroutine syntax_make_keyword_list

```

The finalizer deallocates the rule pointer array and deletes the keyword list.

<Syntax: subroutines>+≡

```

subroutine syntax_final (syntax)
  type(syntax_t), intent(inout) :: syntax
  if (allocated (syntax%rule)) deallocate (syntax%rule)
  call keyword_list_final (syntax%keyword_list)
end subroutine syntax_final

```

3.3.6 Accessing the syntax table

Return a pointer to the top rule

<Syntax: public>+≡

```

public :: syntax_get_top_rule_ptr

```

<Syntax: subroutines>+≡

```

function syntax_get_top_rule_ptr (syntax) result (rule)
  type(syntax_rule_t), pointer :: rule
  type(syntax_t), intent(in), target :: syntax
  if (allocated (syntax%rule)) then
    rule => syntax%rule(1)
  else

```

```

        rule => null ()
    end if
end function syntax_get_top_rule_ptr

```

Assign the pointer to the rule associated with a given key (assumes that the rule array is allocated)

```

<Syntax: public>+≡
    public :: syntax_get_rule_ptr

<Syntax: subroutines>+≡
    function syntax_get_rule_ptr (syntax, key) result (rule)
        type(syntax_rule_t), pointer :: rule
        type(syntax_t), intent(in), target :: syntax
        type(string_t), intent(in) :: key
        integer :: i
        do i = 1, size (syntax%rule)
            if (syntax%rule(i)%keyword == key) then
                rule => syntax%rule(i)
                return
            end if
        end do
        call msg_bug (" Syntax table: Rule " // char (key) // " not found")
    end function syntax_get_rule_ptr

```

Return a pointer to the keyword list

```

<Syntax: public>+≡
    public :: syntax_get_keyword_list_ptr

<Syntax: subroutines>+≡
    function syntax_get_keyword_list_ptr (syntax) result (keyword_list)
        type(keyword_list_t), pointer :: keyword_list
        type(syntax_t), intent(in), target :: syntax
        keyword_list => syntax%keyword_list
    end function syntax_get_keyword_list_ptr

```

3.3.7 I/O

Write a readable representation of the syntax table

```

<Syntax: public>+≡
    public :: syntax_write

<Syntax: subroutines>+≡
    subroutine syntax_write (syntax, unit)
        type(syntax_t), intent(in) :: syntax
        integer, intent(in), optional :: unit
        integer :: u
        integer :: i
        u = output_unit (unit); if (u < 0) return
        write (u, "(A)") "Syntax table:"
        if (allocated (syntax%rule)) then
            do i = 1, size (syntax%rule)
                call syntax_rule_write (syntax%rule(i), u)
            end do
        end if
    end subroutine syntax_write

```

```
        end do
    else
        write (u, "(1x,A)") "[not allocated]"
    end if
    call keyword_list_write (syntax%keyword_list, u)
end subroutine syntax_write
```

3.4 The parser

On a small scale, the parser interprets the string tokens returned by the lexer; they are interpreted as numbers, keywords and such and stored as a typed object. On a large scale, a text is read, parsed, and a syntax rule set is applied such that the tokens are stored as a parse tree. Syntax errors are spotted in this process, so the resulting parse tree is syntactically correct by definition.

```
<parser.f90>≡  
  <File header>  
  
  module parser  
  
    <Use kinds>  
    <Use strings>  
    use limits, only: DIGITS !NODEP!  
    <Use file utils>  
    use diagnostics !NODEP!  
    use md5  
    use lexers  
    use syntax_rules  
  
    <Standard module head>  
  
    <Parser: public>  
  
    <Parser: types>  
  
    <Parser: interfaces>  
  
    contains  
  
    <Parser: procedures>  
  
  end module parser
```

3.4.1 The token type

Tokens are elements of the parsed input that carry a value: logical, integer, real, quoted string, (unquoted) identifier, or known keyword. Note that non-keyword tokens also have an abstract key attached to them.

This is an obvious candidate for polymorphism.

```
<Parser: types>≡  
  type :: token_t  
    private  
    integer :: type = S_UNKNOWN  
    logical, pointer :: lval => null ()  
    integer, pointer :: ival => null ()  
    real(default), pointer :: rval => null ()  
    complex(default), pointer :: cval => null ()  
    type(string_t), pointer :: sval => null ()  
    type(string_t), pointer :: kval => null ()  
    type(string_t), dimension(:), pointer :: quote => null ()
```

```
end type token_t
```

Create a token from the lexeme returned by the lexer: Allocate storage and try to interpret the lexeme according to the type that is requested by the parser. For a keyword token, match the lexeme against the requested key. If successful, set the token type, value, and key. Otherwise, set the type to S_UNKNOWN.

(Parser: procedures)≡

```
subroutine token_init (token, lexeme, requested_type, key)
  type(token_t), intent(out) :: token
  type(lexeme_t), intent(in)  :: lexeme
  integer, intent(in) :: requested_type
  type(string_t), intent(in) :: key
  integer :: type
  type = lexeme_get_type (lexeme)
  token%type = S_UNKNOWN
  select case (requested_type)
  case (S_LOGICAL)
    if (type == T_IDENTIFIER) call read_logical &
      (char (lexeme_get_string (lexeme)))
  case (S_INTEGER)
    if (type == T_NUMERIC) call read_integer &
      (char (lexeme_get_string (lexeme)))
  case (S_REAL)
    if (type == T_NUMERIC) call read_real &
      (char (lexeme_get_string (lexeme)))
  case (S_COMPLEX)
    if (type == T_NUMERIC) call read_complex &
      (char (lexeme_get_string (lexeme)))
  case (S_IDENTIFIER)
    if (type == T_IDENTIFIER) call read_identifier &
      (lexeme_get_string (lexeme))
  case (S_KEYWORD)
    if (type == T_KEYWORD) call check_keyword &
      (lexeme_get_string (lexeme), key)
  case (S_QUOTED)
    if (type == T_QUOTED) call read_quoted &
      (lexeme_get_contents (lexeme), lexeme_get_delimiters (lexeme))
  case default
    print *, requested_type
    call msg_bug (" Invalid token type code requested by the parser")
  end select
  if (token%type /= S_UNKNOWN) then
    allocate (token%kval)
    token%kval = key
  end if
contains
  subroutine read_logical (s)
    character(*), intent(in) :: s
    select case (s)
    case ("t", "T", "true", "TRUE", "y", "Y", "yes", "YES")
      allocate (token%lval)
      token%lval = .true.
      token%type = S_LOGICAL
```

```

        case ("f", "F", "false", "FALSE", "n", "N", "no", "NO")
            allocate (token%lval)
            token%lval = .false.
            token%type = S_LOGICAL
        end select
end subroutine read_logical
subroutine read_integer (s)
    character(*), intent(in) :: s
    integer :: tmp, iostat
    if (verify (s, DIGITS) == 0) then
        read (s, *, iostat=iostat) tmp
        if (iostat == 0) then
            allocate (token%ival)
            token%ival = tmp
            token%type = S_INTEGER
        end if
    end if
end subroutine read_integer
subroutine read_real (s)
    character(*), intent(in) :: s
    real(default) :: tmp
    integer :: iostat
    read (s, *, iostat=iostat) tmp
    if (iostat == 0) then
        allocate (token%rval)
        token%rval = tmp
        token%type = S_REAL
    end if
end subroutine read_real
subroutine read_complex (s)
    character(*), intent(in) :: s
    complex(default) :: tmp
    integer :: iostat
    read (s, *, iostat=iostat) tmp
    if (iostat == 0) then
        allocate (token%cval)
        token%cval = tmp
        token%type = S_COMPLEX
    end if
end subroutine read_complex
subroutine read_identifier (s)
    type(string_t), intent(in) :: s
    allocate (token%sval)
    token%sval = s
    token%type = S_IDENTIFIER
end subroutine read_identifier
subroutine check_keyword (s, key)
    type(string_t), intent(in) :: s
    type(string_t), intent(in) :: key
    if (key == s) token%type = S_KEYWORD
end subroutine check_keyword
subroutine read_quoted (s, del)
    type(string_t), intent(in) :: s
    type(string_t), dimension(2), intent(in) :: del

```

```

        allocate (token%sval, token%quote(2))
        token%sval = s
        token%quote(1) = del(1)
        token%quote(2) = del(2)
        token%type = S_QUOTED
    end subroutine read_quoted
end subroutine token_init

```

Reset a token to an empty state, freeing allocated memory, and deallocate the token itself.

```

(Parser: procedures)+≡
subroutine token_final (token)
    type(token_t), intent(inout) :: token
    token%type = S_UNKNOWN
    if (associated (token%lval)) deallocate (token%lval)
    if (associated (token%ival)) deallocate (token%ival)
    if (associated (token%rval)) deallocate (token%rval)
    if (associated (token%sval)) deallocate (token%sval)
    if (associated (token%kval)) deallocate (token%kval)
    if (associated (token%quote)) deallocate (token%quote)
end subroutine token_final

```

Check for empty=valid token:

```

(Parser: procedures)+≡
function token_is_valid (token) result (valid)
    logical :: valid
    type(token_t), intent(in) :: token
    valid = token%type /= S_UNKNOWN
end function token_is_valid

```

Write the contents of a token.

```

(Parser: procedures)+≡
subroutine token_write (token, unit)
    type(token_t), intent(in) :: token
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    select case (token%type)
    case (S_LOGICAL)
        write (u, *) token%lval
    case (S_INTEGER)
        write (u, *) token%ival
    case (S_REAL)
        write (u, *) token%rval
    case (S_COMPLEX)
        write (u, *) token%cval
    case (S_IDENTIFIER)
        write (u, *) char (token%sval)
    case (S_KEYWORD)
        write (u, *) '[keyword] ' // char (token%kval)
    case (S_QUOTED)
        write (u, *) &

```



```

        char (token%quote(1)) // char (token%sval) // char (token%quote(2))
    case default
        write (u, *) '[empty]'
    end select
end subroutine token_write

```

Token assignment via deep copy. This is useful to avoid confusion when the token is transferred to some parse-tree node.

```

(Parser: interfaces)≡
    interface assignment(=)
        module procedure token_assign
    end interface

```

We need to copy only the contents that are actually assigned, the other pointers remain disassociated.

```

(Parser: procedures)+≡
    subroutine token_assign (token, token_in)
        type(token_t), intent(out) :: token
        type(token_t), intent(in) :: token_in
        token%type = token_in%type
        select case (token%type)
            case (S_LOGICAL);    allocate (token%lval); token%lval = token_in%lval
            case (S_INTEGER);    allocate (token%ival); token%ival = token_in%ival
            case (S_REAL);       allocate (token%rval); token%rval = token_in%rval
            case (S_COMPLEX);    allocate (token%cval); token%cval = token_in%cval
            case (S_IDENTIFIER); allocate (token%sval); token%sval = token_in%sval
            case (S_QUOTED);     allocate (token%sval); token%sval = token_in%sval
                                allocate (token%quote(2)); token%quote = token_in%quote
        end select
        if (token%type /= S_UNKNOWN) then
            allocate (token%kval); token%kval = token_in%kval
        end if
    end subroutine token_assign

```

3.4.2 Retrieve token contents

These functions all do a trivial sanity check that should avoid crashes.

```

(Parser: procedures)+≡
    function token_get_logical (token) result (lval)
        logical :: lval
        type(token_t), intent(in) :: token
        if (associated (token%lval)) then
            lval = token%lval
        else
            call token_mismatch (token, "logical")
        end if
    end function token_get_logical

    function token_get_integer (token) result (ival)
        integer :: ival
        type(token_t), intent(in) :: token

```

```

    if (associated (token%ival)) then
        ival = token%ival
    else
        call token_mismatch (token, "integer")
    end if
end function token_get_integer

function token_get_real (token) result (rval)
    real(default) :: rval
    type(token_t), intent(in) :: token
    if (associated (token%rval)) then
        rval = token%rval
    else
        call token_mismatch (token, "real")
    end if
end function token_get_real

function token_get_cmplx (token) result (cval)
    complex(default) :: cval
    type(token_t), intent(in) :: token
    if (associated (token%cval)) then
        cval = token%cval
    else
        call token_mismatch (token, "complex")
    end if
end function token_get_cmplx

function token_get_string (token) result (sval)
    type(string_t) :: sval
    type(token_t), intent(in) :: token
    if (associated (token%sval)) then
        sval = token%sval
    else
        call token_mismatch (token, "string")
    end if
end function token_get_string

function token_get_key (token) result (kval)
    type(string_t) :: kval
    type(token_t), intent(in) :: token
    if (associated (token%kval)) then
        kval = token%kval
    else
        call token_mismatch (token, "keyword")
    end if
end function token_get_key

function token_get_quote (token) result (quote)
    type(string_t), dimension(2) :: quote
    type(token_t), intent(in) :: token
    if (associated (token%quote)) then
        quote = token%quote
    else
        call token_mismatch (token, "quote")
    end if
end function token_get_quote

```

```

        end if
    end function token_get_quote

```

```

<Parser: procedures>+≡
    subroutine token_mismatch (token, type)
        type(token_t), intent(in) :: token
        character(*), intent(in) :: type
        write (6, "(A)", advance="no") "Token: "
        call token_write (token)
        call msg_bug (" Token type mismatch; value required as " // type)
    end subroutine token_mismatch

```

3.4.3 The parse tree: nodes

The parser will generate a parse tree from the input stream. Each node in this parse tree points to the syntax rule that was applied. (Since syntax rules are stored in a pointer-type array within the syntax table, they qualify as targets.) A leaf node contains a token. A branch node has subnodes. The subnodes are stored as a list, so each node also has a next pointer.

```

<Parser: public>≡
    public :: parse_node_t

<Parser: types>+≡
    type :: parse_node_t
        private
        type(syntax_rule_t), pointer :: rule => null ()
        type(token_t) :: token
        integer :: n_sub = 0
        type(parse_node_t), pointer :: sub_first => null ()
        type(parse_node_t), pointer :: sub_last => null ()
        type(parse_node_t), pointer :: next => null ()
    end type parse_node_t

```

Container for parse node pointers, useful for creating pointer arrays:

```

<Parser: public>+≡
    public :: parse_node_p

<Parser: types>+≡
    type :: parse_node_p
        type(parse_node_t), pointer :: ptr => null ()
    end type parse_node_p

```

Output. The first version writes a node together with its sub-node tree, organized by indentation.

```

<Parser: public>+≡
    public :: parse_node_write_rec

<Parser: procedures>+≡
    recursive subroutine parse_node_write_rec (node, unit, short, depth)
        type(parse_node_t), intent(in), target :: node
        integer, intent(in), optional :: unit

```

```

logical, intent(in), optional :: short
integer, intent(in), optional :: depth
integer :: u, d
type(parse_node_t), pointer :: current
u = output_unit (unit); if (u < 0) return
d = 0; if (present (depth)) d = depth
call parse_node_write (node, u, short=short)
current => node%sub_first
do while (associated (current))
    write (u, "(A)", advance = "no") repeat ("| ", d)
    call parse_node_write_rec (current, unit, short, d+1)
    current => current%next
end do
end subroutine parse_node_write_rec

```

This does the actual output for a single node, without recursion.

```

(Parser: public)+≡
public :: parse_node_write

(Parser: procedures)+≡
subroutine parse_node_write (node, unit, short)
    type(parse_node_t), intent(in) :: node
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: short
    integer :: u
    type(parse_node_t), pointer :: current
    u = output_unit (unit); if (u < 0) return
    write (u, "(' + ')", advance = "no")
    if (associated (node%rule)) then
        call syntax_rule_write (node%rule, u, &
            short=short, key_only=.true., advance=.false.)
        if (token_is_valid (node%token)) then
            write (u, "(' = ')", advance="no")
            call token_write (node%token, u)
        else if (associated (node%sub_first)) then
            write (u, "(' = ')", advance="no")
            current => node%sub_first
            do while (associated (current))
                call syntax_rule_write (current%rule, u, &
                    short=.true., key_only=.true., advance=.false.)
                current => current%next
            end do
            write (u, *)
        else
            write (u, *)
        end if
    else
        write (u, *) "[empty]"
    end if
end subroutine parse_node_write

```

Finalize the token and recursively finalize and deallocate all sub-nodes.

```

(Parser: public)+≡
public :: parse_node_final

```

```

(Parser: procedures)+≡
recursive subroutine parse_node_final (node, recursive)
  type(parse_node_t), intent(inout) :: node
  type(parse_node_t), pointer :: current
  logical, intent(in), optional :: recursive
  logical :: rec
  rec = .true.; if (present (recursive)) rec = recursive
  call token_final (node%token)
  if (rec) then
    do while (associated (node%sub_first))
      current => node%sub_first
      node%sub_first => node%sub_first%next
      call parse_node_final (current)
      deallocate (current)
    end do
  end if
end subroutine parse_node_final

```

3.4.4 Filling nodes

The constructors allocate and initialize the node. There are two possible initializers (in a later version, should correspond to different type extensions).

First, leaf (terminal) nodes. The token constructor does the actual work, looking at the requested type and key for the given rule and matching against the lexeme contents. If it fails, the token will keep the type S_UNKNOWN and remain empty. Otherwise, we have a valid node which contains the new token.

If the lexeme argument is absent, the token is left empty.

```

(Parser: procedures)+≡
subroutine parse_node_create_leaf (node, rule, lexeme)
  type(parse_node_t), pointer :: node
  type(syntax_rule_t), intent(in), target :: rule
  type(lexeme_t), intent(in) :: lexeme
  allocate (node)
  node%rule => rule
  call token_init (node%token, lexeme, &
    syntax_rule_get_type (rule), syntax_rule_get_key (rule))
  if (.not. token_is_valid (node%token)) deallocate (node)
end subroutine parse_node_create_leaf

```

Second, branch nodes. We first assign the rule:

```

(Parser: public)+≡
public :: parse_node_create_branch

(Parser: procedures)+≡
subroutine parse_node_create_branch (node, rule)
  type(parse_node_t), pointer :: node
  type(syntax_rule_t), intent(in), target :: rule
  allocate (node)
  node%rule => rule
end subroutine parse_node_create_branch

```

Append a sub-node. The sub-node must exist and be a valid target, otherwise nothing is done.

```

(Parser: public)+≡
    public :: parse_node_append_sub

(Parser: procedures)+≡
    subroutine parse_node_append_sub (node, sub)
        type(parse_node_t), intent(inout) :: node
        type(parse_node_t), pointer :: sub
        if (associated (sub)) then
            if (associated (node%sub_last)) then
                node%sub_last%next => sub
            else
                node%sub_first => sub
            end if
            node%sub_last => sub
        end if
    end subroutine parse_node_append_sub

```

For easy access, once the list is complete we count the number of sub-nodes. If there are no subnodes, the whole node is deleted.

```

(Parser: procedures)+≡
    subroutine parse_node_freeze_branch (node)
        type(parse_node_t), pointer :: node
        type(parse_node_t), pointer :: current
        node%n_sub = 0
        current => node%sub_first
        do while (associated (current))
            node%n_sub = node%n_sub + 1
            current => current%next
        end do
        if (node%n_sub == 0) deallocate (node)
    end subroutine parse_node_freeze_branch

```

Replace the last subnode by a new target. Use with care, this invites to memory mismanagement.

```

(Parser: public)+≡
    public :: parse_node_replace_last_sub

(Parser: procedures)+≡
    subroutine parse_node_replace_last_sub (node, pn_target)
        type(parse_node_t), intent(inout), target :: node
        type(parse_node_t), intent(in), target :: pn_target
        type(parse_node_t), pointer :: current
        integer :: i
        select case (node%n_sub)
        case (1)
            node%sub_first => pn_target
        case (2:)
            current => node%sub_first
            do i = 1, node%n_sub - 2
                current => current%next
            end do

```

```

        current%next => pn_target
    case default
        call parse_node_write (node)
        call msg_bug ("replace_last_sub' called for non-branch parse node")
    end select
    node%sub_last => pn_target
end subroutine parse_node_replace_last_sub

```

3.4.5 Accessing nodes

Return the node contents. Check if pointers are associated. No check when accessing a sub-node; assume that `parse_node_n_sub` is always used for the upper bound.

The token extractor returns a pointer.

(Parser: public)+≡

```

public :: parse_node_get_rule_ptr
public :: parse_node_get_n_sub
public :: parse_node_get_sub_ptr
public :: parse_node_get_next_ptr
public :: parse_node_get_last_sub_ptr

```

(Parser: procedures)+≡

```

function parse_node_get_rule_ptr (node) result (rule)
    type(syntax_rule_t), pointer :: rule
    type(parse_node_t), intent(in), target :: node
    if (associated (node%rule)) then
        rule => node%rule
    else
        rule => null ()
        call parse_node_undefined (node, "rule")
    end if
end function parse_node_get_rule_ptr

```

```

function parse_node_get_n_sub (node) result (n)
    integer :: n
    type(parse_node_t), intent(in) :: node
    n = node%n_sub
end function parse_node_get_n_sub

```

```

function parse_node_get_sub_ptr (node, n, tag, required) result (sub)
    type(parse_node_t), pointer :: sub
    type(parse_node_t), intent(in), target :: node
    integer, intent(in), optional :: n
    character(*), intent(in), optional :: tag
    logical, intent(in), optional :: required
    integer :: i
    sub => node%sub_first
    if (present (n)) then
        do i = 2, n
            if (associated (sub)) then
                sub => sub%next
            else
                return
            end if
        end do
    end if
end function parse_node_get_sub_ptr

```

```

        end if
    end do
end if
call parse_node_check (sub, tag, required)
end function parse_node_get_sub_ptr

function parse_node_get_next_ptr (sub, n, tag, required) result (next)
    type(parse_node_t), pointer :: next
    type(parse_node_t), intent(in), target :: sub
    integer, intent(in), optional :: n
    character(*), intent(in), optional :: tag
    logical, intent(in), optional :: required
    integer :: i
    next => sub%next
    if (present (n)) then
        do i = 2, n
            if (associated (next)) then
                next => next%next
            else
                exit
            end if
        end do
    end if
    call parse_node_check (next, tag, required)
end function parse_node_get_next_ptr

function parse_node_get_last_sub_ptr (node, tag, required) result (sub)
    type(parse_node_t), pointer :: sub
    type(parse_node_t), intent(in), target :: node
    character(*), intent(in), optional :: tag
    logical, intent(in), optional :: required
    sub => node%sub_last
    call parse_node_check (sub, tag, required)
end function parse_node_get_last_sub_ptr

```

```

<Parser: procedures>+≡
subroutine parse_node_undefined (node, obj)
    type(parse_node_t), intent(in) :: node
    character(*), intent(in) :: obj
    call parse_node_write (node, 6)
    call msg_bug (" Parse-tree node: " // obj // " requested, but undefined")
end subroutine parse_node_undefined

```

Check if a parse node has a particular tag, and if it is associated:

```

<Parser: public>+≡
public :: parse_node_check

<Parser: procedures>+≡
subroutine parse_node_check (node, tag, required)
    type(parse_node_t), pointer :: node
    character(*), intent(in), optional :: tag
    logical, intent(in), optional :: required
    if (associated (node)) then
        if (present (tag)) then

```



```

        if (parse_node_get_rule_key (node) /= tag) &
            call parse_node_mismatch (tag, node)
        end if
    else
        if (present (required)) then
            if (required) &
                call msg_bug (" Missing node, expected <" // tag // ">")
            end if
        end if
    end if
end subroutine parse_node_check

```

This is called by a parse-tree scanner if the expected and the actual nodes do not match

```

(Parser: public)+≡
    public :: parse_node_mismatch

(Parser: procedures)+≡
    subroutine parse_node_mismatch (string, parse_node)
        character(*), intent(in) :: string
        type(parse_node_t), intent(in) :: parse_node
        call parse_node_write (parse_node)
        call msg_bug (" Syntax mismatch, expected <" // string // ">.")
    end subroutine parse_node_mismatch

```

The following functions are wrappers for extracting the token contents.

```

(Parser: public)+≡
    public :: parse_node_get_logical
    public :: parse_node_get_integer
    public :: parse_node_get_real
    public :: parse_node_get_cmplx
    public :: parse_node_get_string
    public :: parse_node_get_key
    public :: parse_node_get_rule_key

(Parser: procedures)+≡
    function parse_node_get_logical (node) result (lval)
        logical :: lval
        type(parse_node_t), intent(in), target :: node
        lval = token_get_logical (parse_node_get_token_ptr (node))
    end function parse_node_get_logical

    function parse_node_get_integer (node) result (ival)
        integer :: ival
        type(parse_node_t), intent(in), target :: node
        ival = token_get_integer (parse_node_get_token_ptr (node))
    end function parse_node_get_integer

    function parse_node_get_real (node) result (rval)
        real(default) :: rval
        type(parse_node_t), intent(in), target :: node
        rval = token_get_real (parse_node_get_token_ptr (node))
    end function parse_node_get_real

    function parse_node_get_cmplx (node) result (cval)

```

```

        complex(default) :: cval
        type(parse_node_t), intent(in), target :: node
        cval = token_get_cmplx (parse_node_get_token_ptr (node))
    end function parse_node_get_cmplx

function parse_node_get_string (node) result (sval)
    type(string_t) :: sval
    type(parse_node_t), intent(in), target :: node
    sval = token_get_string (parse_node_get_token_ptr (node))
end function parse_node_get_string

function parse_node_get_key (node) result (kval)
    type(string_t) :: kval
    type(parse_node_t), intent(in), target :: node
    kval = token_get_key (parse_node_get_token_ptr (node))
end function parse_node_get_key

function parse_node_get_rule_key (node) result (kval)
    type(string_t) :: kval
    type(parse_node_t), intent(in), target :: node
    kval = syntax_rule_get_key (parse_node_get_rule_ptr (node))
end function parse_node_get_rule_key

function parse_node_get_token_ptr (node) result (token)
    type(token_t), pointer :: token
    type(parse_node_t), intent(in), target :: node
    if (token_is_valid (node%token)) then
        token => node%token
    else
        call parse_node_undefined (node, "token")
    end if
end function parse_node_get_token_ptr

```

Return a MD5 sum for a parse node. The method is to write the node to a scratch file and to evaluate the MD5 sum of that file.

<Parser: public>+≡

```

    public :: parse_node_get_md5sum

```

<Parser: procedures>+≡

```

function parse_node_get_md5sum (pn) result (md5sum_pn)
    character(32) :: md5sum_pn
    type(parse_node_t), intent(in) :: pn
    integer :: u
    u = free_unit ()
    open (unit = u, status = "scratch", action = "readwrite")
    call parse_node_write_rec (pn, unit=u)
    rewind (u)
    md5sum_pn = md5sum (u)
    close (u)
end function parse_node_get_md5sum

```

3.4.6 The parse tree

The parse tree is a tree of nodes, where leaf nodes hold a valid token, while branch nodes point to a list of sub-nodes.

```
<Parser: public>+≡
    public :: parse_tree_t
<Parser: types>+≡
    type :: parse_tree_t
    private
        type(parse_node_t), pointer :: root_node => null ()
    end type parse_tree_t
```

The parser. Its arguments are the parse tree (which should be empty initially), the lexer (which should be already set up), the syntax table (which should be valid), and the input stream. The input stream is completely parsed, using the lexer setup and the syntax rules as given, and the parse tree is built accordingly.

If `check_eof` is absent or true, the parser will complain about trailing garbage. Otherwise, it will ignore it.

By default, the input stream is matched against the top rule in the specified syntax. If `key` is given, it is matched against the rule with the specified key instead.

Failure at the top level means that no rule could match at all; in this case the error message will show the top rule.

```
<Parser: public>+≡
    public :: parse_tree_init
<Parser: procedures>+≡
    subroutine parse_tree_init &
        (parse_tree, syntax, lexer, key, check_eof)
        type(parse_tree_t), intent(inout) :: parse_tree
        type(lexer_t), intent(inout) :: lexer
        type(syntax_t), intent(in), target :: syntax
        type(string_t), intent(in), optional :: key
        logical, intent(in), optional :: check_eof
        type(syntax_rule_t), pointer :: rule
        type(lexeme_t) :: lexeme
        type(parse_node_t), pointer :: node
        logical :: ok, check
        check = .true.; if (present (check_eof)) check = check_eof
        call lexer_clear (lexer)
        if (present (key)) then
            rule => syntax_get_rule_ptr (syntax, key)
        else
            rule => syntax_get_top_rule_ptr (syntax)
        end if
        if (associated (rule)) then
            call parse_node_match_rule (node, rule, ok)
            if (ok) then
                parse_tree%root_node => node
            else
                call parse_error (rule, lexeme)
            end if
        end if
        if (check) then
```

```

        call lex (lexeme, lexer)
        if (.not. lexeme_is_eof (lexeme)) then
            call lexer_show_location (lexer)
            call msg_fatal (" Syntax error " &
                // "(at or before the location indicated above)")
        end if
    end if
else
    call msg_bug (" Parser failed because syntax is empty")
end if
contains
<Parser: internal subroutines of parse_tree_init>
end subroutine parse_tree_init

```

The parser works recursively, following the rule tree, building the tree of nodes on the fly. If the given rule matches, the node is filled on return. If not, the node remains empty.

```

<Parser: internal subroutines of parse_tree_init>≡
recursive subroutine parse_node_match_rule (node, rule, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(out) :: ok
    logical, parameter :: debug = .false.
    integer :: type
    if (debug) write (6, "(A)", advance="no") "Parsing rule: "
    if (debug) call syntax_rule_write (rule, 6)
    node => null ()
    type = syntax_rule_get_type (rule)
    if (syntax_rule_is_atomic (rule)) then
        call lex (lexeme, lexer)
        if (debug) write (6, "(A)", advance="no") "Token: "
        if (debug) call lexeme_write (lexeme, 6)
        call parse_node_create_leaf (node, rule, lexeme)
        ok = associated (node)
        if (.not. ok) call lexer_put_back (lexer, lexeme)
    else
        select case (type)
        case (S_ALTERNATIVE); call parse_alternative (node, rule, ok)
        case (S_GROUP);      call parse_group (node, rule, ok)
        case (S_SEQUENCE);   call parse_sequence (node, rule, .false., ok)
        case (S_LIST);       call parse_sequence (node, rule, .true., ok)
        case (S_ARGS);       call parse_args (node, rule, ok)
        case (S_IGNORE);     call parse_ignore (node, ok)
        end select
    end if
    if (debug) then
        if (ok) then
            write (6, "(A)", advance="no") "Matched rule: "
        else
            write (6, "(A)", advance="no") "Failed rule: "
        end if
        call syntax_rule_write (rule)
        if (associated (node)) call parse_node_write (node)
    end if
end subroutine parse_node_match_rule

```

```

    end if
end subroutine parse_node_match_rule

```

Parse an alternative: try each case. If the match succeeds, the node has been filled, so return. If nothing works, return failure.

(Parser: internal subroutines of parse_tree_init)+≡

```

recursive subroutine parse_alternative (node, rule, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(out) :: ok
    integer :: i
    do i = 1, syntax_rule_get_n_sub (rule)
        call parse_node_match_rule (node, syntax_rule_get_sub_ptr (rule, i), ok)
        if (ok) return
    end do
    ok = .false.
end subroutine parse_alternative

```

Parse a group: the first and third lexemes have to be the delimiters, the second one is parsed as the actual node, using now the child rule. If the first match fails, return with failure. If the other matches fail, issue an error, since we cannot lex back more than one item.

(Parser: internal subroutines of parse_tree_init)+≡

```

recursive subroutine parse_group (node, rule, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(out) :: ok
    type(string_t), dimension(2) :: delimiter
    delimiter = syntax_rule_get_delimiter (rule)
    call lex (lexeme, lexer)
    if (lexeme_get_string (lexeme) == delimiter(1)) then
        call parse_node_match_rule (node, syntax_rule_get_sub_ptr (rule, 1), ok)
        if (ok) then
            call lex (lexeme, lexer)
            if (lexeme_get_string (lexeme) == delimiter(2)) then
                ok = .true.
            else
                call parse_error (rule, lexeme)
            end if
        else
            call parse_error (rule, lexeme)
        end if
    else
        call lexer_put_back (lexer, lexeme)
        ok = .false.
    end if
end subroutine parse_group

```

Parsing a sequence. The last rule element may be special: optional and/or repetitive. Each sub-node that matches is appended to the sub-node list of the parent node.

If *sep* is true, we look for a separator after each element.

(Parser: internal subroutines of parse_tree_init)+≡

```

recursive subroutine parse_sequence (node, rule, sep, ok)
    type(parse_node_t), pointer :: node

```

```

type(syntax_rule_t), intent(in), target :: rule
logical, intent(in) :: sep
logical, intent(out) :: ok
type(parse_node_t), pointer :: current
integer :: i, n
logical :: opt, rep, cont
type(string_t) :: separator
call parse_node_create_branch (node, rule)
if (sep) separator = syntax_rule_get_separator (rule)
n = syntax_rule_get_n_sub (rule)
opt = syntax_rule_last_optional (rule)
rep = syntax_rule_last_repetitive (rule)
ok = .true.
cont = .true.
SCAN_RULE: do i = 1, n
    call parse_node_match_rule &
        (current, syntax_rule_get_sub_ptr (rule, i), cont)
    if (cont) then
        call parse_node_append_sub (node, current)
        if (sep .and. (i<n .or. rep)) then
            call lex (lexeme, lexer)
            if (lexeme_get_string (lexeme) /= separator) then
                call lexer_put_back (lexer, lexeme)
                cont = .false.
                exit SCAN_RULE
            end if
        end if
    else
        if (i == n .and. opt) then
            exit SCAN_RULE
        else if (i == 1) then
            ok = .false.
            exit SCAN_RULE
        else
            call parse_error (rule, lexeme)
        end if
    end if
end do SCAN_RULE
if (rep) then
    do while (cont)
        call parse_node_match_rule &
            (current, syntax_rule_get_sub_ptr (rule, n), cont)
        if (cont) then
            call parse_node_append_sub (node, current)
            if (sep) then
                call lex (lexeme, lexer)
                if (lexeme_get_string (lexeme) /= separator) then
                    call lexer_put_back (lexer, lexeme)
                    cont = .false.
                end if
            end if
        else
            if (sep) call parse_error (rule, lexeme)
        end if
    end do
end if

```

```

        end do
    end if
    call parse_node_freeze_branch (node)
end subroutine parse_sequence

```

Argument list: We use the `parse_group` code, but call `parse_sequence` inside.

```

(Parser: internal subroutines of parse_tree_init)+≡
recursive subroutine parse_args (node, rule, ok)
    type(parse_node_t), pointer :: node
    type(syntax_rule_t), intent(in), target :: rule
    logical, intent(out) :: ok
    type(string_t), dimension(2) :: delimiter
    delimiter = syntax_rule_get_delimiter (rule)
    call lex (lexeme, lexer)
    if (lexeme_get_string (lexeme) == delimiter(1)) then
        call parse_sequence (node, rule, .true., ok)
        if (ok) then
            call lex (lexeme, lexer)
            if (lexeme_get_string (lexeme) == delimiter(2)) then
                ok = .true.
            else
                call parse_error (rule, lexeme)
            end if
        else
            call parse_error (rule, lexeme)
        end if
    else
        call lexer_put_back (lexer, lexeme)
        ok = .false.
    end if
end subroutine parse_args

```

The IGNORE syntax reads one lexeme and discards it if it is numeric, logical or string/identifier (but not a keyword). This is a successful match. Otherwise, the match fails. The node pointer is returned disassociated in any case.

```

(Parser: internal subroutines of parse_tree_init)+≡
subroutine parse_ignore (node, ok)
    type(parse_node_t), pointer :: node
    logical, intent(out) :: ok
    call lex (lexeme, lexer)
    select case (lexeme_get_type (lexeme))
    case (T_NUMERIC, T_IDENTIFIER, T_QUOTED)
        ok = .true.
    case default
        ok = .false.
    end select
    node => null ()
end subroutine parse_ignore

```

If the match fails and we cannot step back:

```

(Parser: internal subroutines of parse_tree_init)+≡
subroutine parse_error (rule, lexeme)
    type(syntax_rule_t), intent(in) :: rule
    type(lexeme_t), intent(in) :: lexeme
    character(80) :: buffer

```

```

integer :: u, iostat
call lexer_show_location (lexer)
u = free_unit ()
open (u, status = "scratch")
write (u, "(A)", advance="no") "Expected syntax:"
call syntax_rule_write (rule, u)
write (u, "(A)", advance="no") "Found token:"
call lexeme_write (lexeme, u)
rewind (u)
do
    read (u, "(A)", iostat=iostat) buffer
    if (iostat /= 0) exit
    call msg_message (trim (buffer))
end do
call msg_fatal (" Syntax error " &
    // "(at or before the location indicated above)")
end subroutine parse_error

```

The finalizer recursively deallocates all nodes and their contents. For each node, `parse_node_final` is called on the sub-nodes, which in turn deallocates the token or sub-node array contained within each of them. At the end, only the top node remains to be deallocated.

```

(Parser: public)+≡
    public :: parse_tree_final

(Parser: procedures)+≡
    subroutine parse_tree_final (parse_tree)
        type(parse_tree_t), intent(inout) :: parse_tree
        if (associated (parse_tree%root_node)) then
            call parse_node_final (parse_tree%root_node)
            deallocate (parse_tree%root_node)
        end if
    end subroutine parse_tree_final

```

Print the parse tree. Print one token per line, indented according to the depth of the node.

The **verbose** version includes type identifiers for the nodes.

```

(Parser: public)+≡
    public :: parse_tree_write

(Parser: procedures)+≡
    subroutine parse_tree_write (parse_tree, unit, verbose)
        type(parse_tree_t), intent(in) :: parse_tree
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose
        integer :: u
        logical :: short
        u = output_unit (unit); if (u < 0) return
        short = .true.; if (present (verbose)) short = .not. verbose
        write (u, "(A)") "Parse tree:"
        if (associated (parse_tree%root_node)) then
            call parse_node_write_rec (parse_tree%root_node, unit, short, 1)
        else
            write (u, *) "[empty]"
        end if
    end subroutine parse_tree_write

```



```

        end if
    end subroutine parse_tree_write

```

This is a generic error that can be issued if the parse tree does not meet the expectations of the parser. This most certainly indicates a bug.

```

<Parser: public>+≡
    public :: parse_tree_bug

<Parser: procedures>+≡
    subroutine parse_tree_bug (node, keys)
        type(parse_node_t), intent(in) :: node
        character(*), intent(in) :: keys
        call parse_node_write (node)
        call msg_bug (" Inconsistency in parse tree: expected " // keys)
    end subroutine parse_tree_bug

```

3.4.7 Access the parser

For scanning the parse tree we give access to the top node, as a node pointer. Of course, there should be no write access.

```

<Parser: public>+≡
    public :: parse_tree_get_root_ptr

<Parser: procedures>+≡
    function parse_tree_get_root_ptr (parse_tree) result (node)
        type(parse_node_t), pointer :: node
        type(parse_tree_t), intent(in), target :: parse_tree
        node => parse_tree%root_node
    end function parse_tree_get_root_ptr

```

3.4.8 Tools

This operation traverses the parse tree and simplifies any occurrences of a set of syntax rules. If such a parse node has only one sub-node, it is replaced by that subnode. (This makes sense only of the rules to eliminate have no meaningful token.)

```

<Parser: public>+≡
    public :: parse_tree_reduce

<Parser: procedures>+≡
    subroutine parse_tree_reduce (parse_tree, rule_key)
        type(parse_tree_t), intent(inout) :: parse_tree
        type(string_t), dimension(:), intent(in) :: rule_key
        type(parse_node_t), pointer :: pn
        pn => parse_tree%root_node
        if (associated (pn)) then
            call parse_node_reduce (pn, null(), null())
        end if
    contains
        recursive subroutine parse_node_reduce (pn, pn_prev, pn_parent)
            type(parse_node_t), intent(inout), pointer :: pn

```

```

type(parse_node_t), intent(in), pointer :: pn_prev, pn_parent
type(parse_node_t), pointer :: pn_sub, pn_sub_prev, pn_tmp
pn_sub_prev => null ()
pn_sub => pn%sub_first
do while (associated (pn_sub))
    call parse_node_reduce (pn_sub, pn_sub_prev, pn)
    pn_sub_prev => pn_sub
    pn_sub => pn_sub%next
end do
if (parse_node_get_n_sub (pn) == 1) then
    if (matches (parse_node_get_rule_key (pn), rule_key)) then
        pn_tmp => pn
        pn => pn%sub_first
        if (associated (pn_prev)) then
            pn_prev%next => pn
        else if (associated (pn_parent)) then
            pn_parent%sub_first => pn
        else
            parse_tree%root_node => pn
        end if
        if (associated (pn_tmp%next)) then
            pn%next => pn_tmp%next
        else if (associated (pn_parent)) then
            pn_parent%sub_last => pn
        end if
        call parse_node_final (pn_tmp, recursive=.false.)
        deallocate (pn_tmp)
    end if
end if
end subroutine parse_node_reduce
function matches (key, key_list) result (flag)
    logical :: flag
    type(string_t), intent(in) :: key
    type(string_t), dimension(:), intent(in) :: key_list
    integer :: i
    flag = .true.
    do i = 1, size (key_list)
        if (key == key_list(i)) return
    end do
    flag = .false.
end function matches
end subroutine parse_tree_reduce

```

3.4.9 Applications

For a file of the form

```

process foo, bar
    <something>
process xyz
    <something>

```

get the <something> entry node for the first matching process tag. If no matching entry is found, the node pointer remains unassociated.

<Parser: public>+≡

```
public :: parse_tree_get_process_ptr
```

<Parser: procedures>+≡

```
function parse_tree_get_process_ptr (parse_tree, process) result (node)
  type(parse_node_t), pointer :: node
  type(parse_tree_t), intent(in), target :: parse_tree
  type(string_t), intent(in) :: process
  type(parse_node_t), pointer :: node_root, node_process_def
  type(parse_node_t), pointer :: node_process_phs, node_process_list
  integer :: j
  node_root => parse_tree_get_root_ptr (parse_tree)
  if (associated (node_root)) then
    node_process_phs => parse_node_get_sub_ptr (node_root)
    SCAN_FILE: do while (associated (node_process_phs))
      node_process_def => parse_node_get_sub_ptr (node_process_phs)
      node_process_list => parse_node_get_sub_ptr (node_process_def, 2)
      do j = 1, parse_node_get_n_sub (node_process_list)
        if (parse_node_get_string &
            (parse_node_get_sub_ptr (node_process_list, j)) &
            == process) then
          node => parse_node_get_next_ptr (node_process_def)
          return
        end if
      end do
      node_process_phs => parse_node_get_next_ptr (node_process_phs)
    end do SCAN_FILE
  else
    node => null ()
  end if
end function parse_tree_get_process_ptr
```

3.4.10 Test the parser

<Parser: public>+≡

```
public :: parse_test
```

<Parser: procedures>+≡

```
subroutine parse_test
  use ifiles
  use lexers

  type(ifile_t) :: ifile
  type(syntax_t), target :: syntax
  type(lexer_t) :: lexer
  type(stream_t), target :: stream
  type(parse_tree_t), target :: parse_tree

  print "(A)", "Parser test"
  print *
```

```

call ifile_append (ifile, "SEQ expr = term addition*")
call ifile_append (ifile, "SEQ addition = plus_or_minus term")
call ifile_append (ifile, "SEQ term = factor multiplication*")
call ifile_append (ifile, "SEQ multiplication = times_or_over factor")
call ifile_append (ifile, "SEQ factor = atom exponentiation*")
call ifile_append (ifile, "SEQ exponentiation = '^' atom")
call ifile_append (ifile, "ALT atom = real | delimited_expr")
call ifile_append (ifile, "GRO delimited_expr = ( expr )")
call ifile_append (ifile, "ALT plus_or_minus = '+' | '-'")
call ifile_append (ifile, "ALT times_or_over = '*' | '/'")
call ifile_append (ifile, "KEY '+'")
call ifile_append (ifile, "KEY '-'")
call ifile_append (ifile, "KEY '*'")
call ifile_append (ifile, "KEY '/'")
call ifile_append (ifile, "KEY '^'")
call ifile_append (ifile, "REA real")

print "(A)", "File contents (syntax definition):"
call ifile_write (ifile)
print "(A)", "EOF"
print *

call syntax_init (syntax, ifile)
call ifile_final (ifile)
call syntax_write (syntax)
print *

call lexer_init (lexer, &
    comment_chars = "", &
    quote_chars = "'", &
    quote_match = "'", &
    single_chars = "+-*/^()", &
    special_class = (/ "" /), &
    keyword_list = syntax_get_keyword_list_ptr (syntax))
call lexer_write_setup (lexer)
print *

call ifile_append (ifile, "(27+8^3-2/3)*(4+7)^2*99")
print "(A)", "File contents (input file):"
call ifile_write (ifile)
print "(A)", "EOF"
print *

call stream_init (stream, ifile)
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax, lexer)
call stream_final (stream)
call parse_tree_write (parse_tree)
print *

print "(A)", "Cleanup, everything should now be empty:"
print *

call parse_tree_final (parse_tree)

```

```
call parse_tree_write (parse_tree)
print *

call lexer_final (lexer)
call lexer_write_setup (lexer)
print *

call ifile_final (ifile)
print "(A)", "File contents:"
call ifile_write (ifile)
print "(A)", "EOF"
print *

call syntax_final (syntax)
call syntax_write (syntax)

end subroutine parse_test
```

Chapter 4

Physics library

This part consists of two modules:

constants Physical and mathematical parameters that never change. The file has been moved to the **src/misc** subdirectory of the **WHIZARD** project.

c_particles A simple data type for particles which is C compatible.

lorentz Define three-vectors, four-vectors and Lorentz transformations and common operations for them.

sm_physics Here, running functions are stored for special kinematical setup like running coupling constants, Catani-Seymour dipoles, or Sudakov factors.

4.1 C-compatible Particle Type

For easy communication with C code, we introduce a simple C-compatible type for particles. It has the contents of the `prt_t` type defined in the `subevents` module below (except the source information).

The `c_prt` type is transparent, and its contents should be regarded as part of the interface.

```

<c_particles.f90>≡
  <File header>

  module c_particles

    use iso_c_binding !NODEP!
    <Use file utils>

    <Standard module head>

    <C Particles: public>

    <C Particles: types>

    contains

    <C Particles: procedures>
  end module c_particles

<C Particles: public>≡
  public :: c_prt_t

<C Particles: types>≡
  type, bind(C) :: c_prt_t
    integer(c_int) :: type = 0
    integer(c_int) :: pdg = 0
    integer(c_int) :: polarized = 0
    integer(c_int) :: h = 0
    real(c_double) :: pe = 0
    real(c_double) :: px = 0
    real(c_double) :: py = 0
    real(c_double) :: pz = 0
    real(c_double) :: p2 = 0
  end type c_prt_t

```

This is for debugging only, there is no C binding. It is a simplified version of `prt_write`.

```

<C Particles: public>+≡
  public :: c_prt_write

<C Particles: procedures>≡
  subroutine c_prt_write (prt, unit)
    type(c_prt_t), intent(in) :: prt
    integer, intent(in), optional :: unit
    integer :: u, i
    u = output_unit (unit); if (u < 0) return
    write (u, "(1x,A)", advance="no") "prt("

```

```

write (u, "(I0,':')", advance="no") prt%type
if (prt%polarized /= 0) then
  write (u, "(I0,'/',I0,'|')", advance="no") prt%pdg, prt%h
else
  write (u, "(I0,'|')", advance="no") prt%pdg
end if
write (u, "(1PE12.5,';','1PE12.5,';',1PE12.5,';',1PE12.5)", advance="no") &
  prt%pe, prt%px, prt%py, prt%pz
write (u, "('|',1PE12.5)", advance="no") prt%p2
write (u, "(A)" " ")
end subroutine c_prt_write

```


4.2 Lorentz algebra

Define Lorentz vectors, three-vectors, boosts, and some functions to manipulate them.

To make maximum use of this, all functions, if possible, are declared elemental (or pure, if this is not possible).

```
<lorentz.f90>≡  
  <File header>  
  
  module lorentz  
  
    <Use kinds>  
    use constants, only: pi, twopi, degree !NODEP!  
    <Use file utils>  
    use diagnostics !NODEP!  
    use c_particles  
  
    <Standard module head>  
  
    <Lorentz: public>  
  
    <Lorentz: public operators>  
  
    <Lorentz: public functions>  
  
    <Lorentz: types>  
  
    <Lorentz: parameters>  
  
    <Lorentz: interfaces>  
  
    contains  
  
    <Lorentz: procedures>  
  end module lorentz
```

4.2.1 Three-vectors

First of all, let us introduce three-vectors in a trivial way. The functions and overloaded elementary operations clearly are too much overhead, but we like to keep the interface for three-vectors and four-vectors exactly parallel. By the way, we might attach a label to a vector by extending the type definition later.

```
<Lorentz: public>≡  
  public :: vector3_t  
  
<Lorentz: types>≡  
  type :: vector3_t  
    private  
    real(default), dimension(3) :: p  
  end type vector3_t
```

Output a vector

```

(Lorentz: public)+≡
    public :: vector3_write

(Lorentz: procedures)≡
    subroutine vector3_write (p, unit)
        type(vector3_t), intent(in) :: p
        integer, intent(in), optional :: unit
        integer :: u
        u = output_unit (unit); if (u < 0) return
        write(u, *) 'P = ', p%p
    end subroutine vector3_write

```

This is a three-vector with zero components

```

(Lorentz: public)+≡
    public :: vector3_null

(Lorentz: parameters)≡
    type(vector3_t), parameter :: vector3_null = &
        vector3_t ((/ 0._default, 0._default, 0._default /))

```

Canonical three-vector:

```

(Lorentz: public)+≡
    public :: vector3_canonical

(Lorentz: procedures)+≡
    elemental function vector3_canonical (k) result (p)
        type(vector3_t) :: p
        integer, intent(in) :: k
        p = vector3_null
        p%p(k) = 1
    end function vector3_canonical

```

A moving particle (k -axis, or arbitrary axis). Note that the function for the generic momentum cannot be elemental.

```

(Lorentz: public)+≡
    public :: vector3_moving

(Lorentz: interfaces)≡
    interface vector3_moving
        module procedure vector3_moving_canonical
        module procedure vector3_moving_generic
    end interface

(Lorentz: procedures)+≡
    elemental function vector3_moving_canonical (p, k) result(q)
        type(vector3_t) :: q
        real(default), intent(in) :: p
        integer, intent(in) :: k
        q = vector3_null
        q%p(k) = p
    end function vector3_moving_canonical
    pure function vector3_moving_generic (p) result(q)
        real(default), dimension(3), intent(in) :: p

```

```

    type(vector3_t) :: q
    q%p = p
end function vector3_moving_generic

```

Equality and inequality

```

<Lorentz: public operators>≡
    public :: operator(==), operator(/=)

<Lorentz: interfaces>+≡
    interface operator(==)
        module procedure vector3_eq
    end interface
    interface operator(/=)
        module procedure vector3_neq
    end interface

<Lorentz: procedures>+≡
    elemental function vector3_eq (p, q) result (r)
        logical :: r
        type(vector3_t), intent(in) :: p,q
        r = all (p%p == q%p)
    end function vector3_eq
    elemental function vector3_neq (p, q) result (r)
        logical :: r
        type(vector3_t), intent(in) :: p,q
        r = any (p%p /= q%p)
    end function vector3_neq

```

Define addition and subtraction

```

<Lorentz: public operators>+≡
    public :: operator(+), operator(-)

<Lorentz: interfaces>+≡
    interface operator(+)
        module procedure add_vector3
    end interface
    interface operator(-)
        module procedure sub_vector3
    end interface

<Lorentz: procedures>+≡
    elemental function add_vector3 (p, q) result (r)
        type(vector3_t) :: r
        type(vector3_t), intent(in) :: p,q
        r%p = p%p + q%p
    end function add_vector3
    elemental function sub_vector3 (p, q) result (r)
        type(vector3_t) :: r
        type(vector3_t), intent(in) :: p,q
        r%p = p%p - q%p
    end function sub_vector3

```

The multiplication sign is overloaded with scalar multiplication; similarly division:

```

<Lorentz: public operators>+≡

```

```

    public :: operator(*), operator(/)
<Lorentz: interfaces>+≡
    interface operator(*)
        module procedure prod_integer_vector3, prod_vector3_integer
        module procedure prod_real_vector3, prod_vector3_real
    end interface
    interface operator(/)
        module procedure div_vector3_real, div_vector3_integer
    end interface
<Lorentz: procedures>+≡
    elemental function prod_real_vector3 (s, p) result (q)
        type(vector3_t) :: q
        real(default), intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = s * p%p
    end function prod_real_vector3
    elemental function prod_vector3_real (p, s) result (q)
        type(vector3_t) :: q
        real(default), intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = s * p%p
    end function prod_vector3_real
    elemental function div_vector3_real (p, s) result (q)
        type(vector3_t) :: q
        real(default), intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = p%p/s
    end function div_vector3_real
    elemental function prod_integer_vector3 (s, p) result (q)
        type(vector3_t) :: q
        integer, intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = s * p%p
    end function prod_integer_vector3
    elemental function prod_vector3_integer (p, s) result (q)
        type(vector3_t) :: q
        integer, intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = s * p%p
    end function prod_vector3_integer
    elemental function div_vector3_integer (p, s) result (q)
        type(vector3_t) :: q
        integer, intent(in) :: s
        type(vector3_t), intent(in) :: p
        q%p = p%p/s
    end function div_vector3_integer

```

The multiplication sign can also indicate scalar products:

```

<Lorentz: interfaces>+≡
    interface operator(*)
        module procedure prod_vector3
    end interface

```

```

<Lorentz: procedures>+≡
  elemental function prod_vector3 (p, q) result (s)
    real(default) :: s
    type(vector3_t), intent(in) :: p,q
    s = dot_product (p%p, q%p)
  end function prod_vector3

<Lorentz: public functions>≡
  public :: cross_product

<Lorentz: interfaces>+≡
  interface cross_product
    module procedure vector3_cross_product
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_cross_product (p, q) result (r)
    type(vector3_t) :: r
    type(vector3_t), intent(in) :: p,q
    integer :: i
    do i=1,3
      r%p(i) = dot_product (p%p, matmul(epsilon_three(i, :, :), q%p))
    end do
  end function vector3_cross_product

```

Exponentiation is defined only for integer powers. Odd powers mean take the square root; so `p**1` is the length of `p`.

```

<Lorentz: public operators>+≡
  public :: operator(**)

<Lorentz: interfaces>+≡
  interface operator(**)
    module procedure power_vector3
  end interface

<Lorentz: procedures>+≡
  elemental function power_vector3 (p, e) result (s)
    real(default) :: s
    type(vector3_t), intent(in) :: p
    integer, intent(in) :: e
    s = dot_product (p%p, p%p)
    if (e/=2) then
      if (mod(e,2)==0) then
        s = s**(e/2)
      else
        s = sqrt(s)**e
      end if
    end if
  end function power_vector3

```

Finally, we need a negation.

```

<Lorentz: interfaces>+≡
  interface operator(-)
    module procedure negate_vector3
  end interface

```

```

<Lorentz: procedures>+≡
  elemental function negate_vector3 (p) result (q)
    type(vector3_t) :: q
    type(vector3_t), intent(in) :: p
    q%p = -p%p
  end function negate_vector3

```

The sum function can be useful:

```

<Lorentz: public functions>+≡
  public :: sum

<Lorentz: interfaces>+≡
  interface sum
    module procedure sum_vector3
  end interface

```

There used to be a mask here, but the Intel compiler crashes with it

```

<Lorentz: procedures>+≡
  pure function sum_vector3 (p) result (q)
    type(vector3_t) :: q
    type(vector3_t), dimension(:), intent(in) :: p
    integer :: i
    do i=1, 3
      q%p(i) = sum (p%p(i))
    end do
  end function sum_vector3

! pure function sum_vector3_mask (p, mask) result (q)
!   type(vector3_t) :: q
!   type(vector3_t), dimension(:), intent(in) :: p
!   logical, dimension(:), intent(in) :: mask
!   integer :: i
!   do i=1, 3
!     q%p(i) = sum (p%p(i), mask=mask)
!   end do
! end function sum_vector3_mask

```

Any component:

```

<Lorentz: public>+≡
  public :: vector3_get_component

<Lorentz: procedures>+≡
  elemental function vector3_get_component (p, k) result (c)
    type(vector3_t), intent(in) :: p
    integer, intent(in) :: k
    real(default) :: c
    c = p%p(k)
  end function vector3_get_component

```

Extract all components. This is not elemental.

```

<Lorentz: public>+≡
  public :: vector3_get_components

```

```

<Lorentz: procedures>+≡
  pure function vector3_get_components (p) result (a)
    type(vector3_t), intent(in) :: p
    real(default), dimension(3) :: a
    a = p%p
  end function vector3_get_components

```

This function returns the direction of a three-vector, i.e., a normalized three-vector

```

<Lorentz: public functions>+≡
  public :: direction

<Lorentz: interfaces>+≡
  interface direction
    module procedure vector3_get_direction
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_get_direction (p) result (q)
    type(vector3_t) :: q
    type(vector3_t), intent(in) :: p
    q%p = p%p / p**1
  end function vector3_get_direction

```

4.2.2 Four-vectors

In four-vectors the zero-component needs special treatment, therefore we do not use the standard operations. Sure, we pay for the extra layer of abstraction by losing efficiency; so we have to assume that the time-critical applications do not involve four-vector operations.

```

<Lorentz: public>+≡
  public :: vector4_t

<Lorentz: types>+≡
  type :: vector4_t
    private
    real(default), dimension(0:3) :: p = &
      (/ 0._default, 0._default, 0._default, 0._default /)
  end type vector4_t

```

Output a vector

```

<Lorentz: public>+≡
  public :: vector4_write

<Lorentz: procedures>+≡
  subroutine vector4_write (p, unit, show_mass)
    type(vector4_t), intent(in) :: p
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: show_mass
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write(u, *) 'E = ', p%p(0)
    write(u, *) 'P = ', p%p(1:)
    if (present (show_mass)) then

```

```

        if (show_mass) &
            write (u, *) 'M = ', p**1
        end if
    end subroutine vector4_write

```

Binary I/O

```

<Lorentz: public>+≡
    public :: vector4_write_raw
    public :: vector4_read_raw

<Lorentz: procedures>+≡
    subroutine vector4_write_raw (p, u)
        type(vector4_t), intent(in) :: p
        integer, intent(in) :: u
        write (u) p%p
    end subroutine vector4_write_raw

    subroutine vector4_read_raw (p, u, iostat)
        type(vector4_t), intent(out) :: p
        integer, intent(in) :: u
        integer, intent(out), optional :: iostat
        read (u, iostat=iostat) p%p
    end subroutine vector4_read_raw

```

This is a four-vector with zero components

```

<Lorentz: public>+≡
    public :: vector4_null

<Lorentz: parameters>+≡
    type(vector4_t), parameter :: vector4_null = &
        vector4_t ((/ 0._default, 0._default, 0._default, 0._default /))

```

Canonical four-vector:

```

<Lorentz: public>+≡
    public :: vector4_canonical

<Lorentz: procedures>+≡
    elemental function vector4_canonical (k) result (p)
        type(vector4_t) :: p
        integer, intent(in) :: k
        p = vector4_null
        p%p(k) = 1
    end function vector4_canonical

```

A particle at rest:

```

<Lorentz: public>+≡
    public :: vector4_at_rest

<Lorentz: procedures>+≡
    elemental function vector4_at_rest (m) result (p)
        type(vector4_t) :: p
        real(default), intent(in) :: m
        p = vector4_t ((/ m, 0._default, 0._default, 0._default /))
    end function vector4_at_rest

```


A moving particle (k -axis, or arbitrary axis)

```

(Lorentz: public)+≡
    public :: vector4_moving

(Lorentz: interfaces)+≡
    interface vector4_moving
        module procedure vector4_moving_canonical
        module procedure vector4_moving_generic
    end interface

(Lorentz: procedures)+≡
    elemental function vector4_moving_canonical (E, p, k) result (q)
        type(vector4_t) :: q
        real(default), intent(in) :: E, p
        integer, intent(in) :: k
        q = vector4_at_rest(E)
        q%p(k) = p
    end function vector4_moving_canonical
    elemental function vector4_moving_generic (E, p) result (q)
        type(vector4_t) :: q
        real(default), intent(in) :: E
        type(vector3_t), intent(in) :: p
        q%p(0) = E
        q%p(1:) = p%p
    end function vector4_moving_generic

```

Equality and inequality

```

(Lorentz: interfaces)+≡
    interface operator(==)
        module procedure vector4_eq
    end interface
    interface operator(/=)
        module procedure vector4_neq
    end interface

(Lorentz: procedures)+≡
    elemental function vector4_eq (p, q) result (r)
        logical :: r
        type(vector4_t), intent(in) :: p,q
        r = all (p%p == q%p)
    end function vector4_eq
    elemental function vector4_neq (p, q) result (r)
        logical :: r
        type(vector4_t), intent(in) :: p,q
        r = any (p%p /= q%p)
    end function vector4_neq

```

Addition and subtraction:

```

(Lorentz: interfaces)+≡
    interface operator(+)
        module procedure add_vector4
    end interface
    interface operator(-)
        module procedure sub_vector4
    end interface

```

```

(Lorentz: procedures)+≡
  elemental function add_vector4 (p,q) result (r)
    type(vector4_t) :: r
    type(vector4_t), intent(in) :: p,q
    r%p = p%p + q%p
  end function add_vector4
  elemental function sub_vector4 (p,q) result (r)
    type(vector4_t) :: r
    type(vector4_t), intent(in) :: p,q
    r%p = p%p - q%p
  end function sub_vector4

```

We also need scalar multiplication and division:

```

(Lorentz: interfaces)+≡
  interface operator(*)
    module procedure prod_real_vector4, prod_vector4_real
    module procedure prod_integer_vector4, prod_vector4_integer
  end interface
  interface operator(/)
    module procedure div_vector4_real
    module procedure div_vector4_integer
  end interface

(Lorentz: procedures)+≡
  elemental function prod_real_vector4 (s, p) result (q)
    type(vector4_t) :: q
    real(default), intent(in) :: s
    type(vector4_t), intent(in) :: p
    q%p = s * p%p
  end function prod_real_vector4
  elemental function prod_vector4_real (p, s) result (q)
    type(vector4_t) :: q
    real(default), intent(in) :: s
    type(vector4_t), intent(in) :: p
    q%p = s * p%p
  end function prod_vector4_real
  elemental function div_vector4_real (p, s) result (q)
    type(vector4_t) :: q
    real(default), intent(in) :: s
    type(vector4_t), intent(in) :: p
    q%p = p%p/s
  end function div_vector4_real
  elemental function prod_integer_vector4 (s, p) result (q)
    type(vector4_t) :: q
    integer, intent(in) :: s
    type(vector4_t), intent(in) :: p
    q%p = s * p%p
  end function prod_integer_vector4
  elemental function prod_vector4_integer (p, s) result (q)
    type(vector4_t) :: q
    integer, intent(in) :: s
    type(vector4_t), intent(in) :: p
    q%p = s * p%p
  end function prod_vector4_integer

```

```

elemental function div_vector4_integer (p, s) result (q)
  type(vector4_t) :: q
  integer, intent(in) :: s
  type(vector4_t), intent(in) :: p
  q%p = p%p/s
end function div_vector4_integer

```

Scalar products and squares in the Minkowski sense:

```

<Lorentz: interfaces>+≡
  interface operator(*)
    module procedure prod_vector4
  end interface
  interface operator(**)
    module procedure power_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function prod_vector4 (p, q) result (s)
    real(default) :: s
    type(vector4_t), intent(in) :: p,q
    s = p%p(0)*q%p(0) - dot_product(p%p(1:), q%p(1:))
  end function prod_vector4

```

The power operation for four-vectors is signed, i.e., p^{**1} is positive for timelike and negative for spacelike vectors. Note that $(p^{**1})^{**2}$ is not necessarily equal to p^{**2} .

```

<Lorentz: procedures>+≡
  elemental function power_vector4 (p, e) result (s)
    real(default) :: s
    type(vector4_t), intent(in) :: p
    integer, intent(in) :: e
    s = p*p
    if (e/=2) then
      if (mod(e,2)==0) then
        s = s**(e/2)
      elseif (s>=0) then
        s = sqrt(s)**e
      else
        s = -(sqrt(abs(s))**e)
      end if
    end if
  end function power_vector4

```

Finally, we introduce a negation

```

<Lorentz: interfaces>+≡
  interface operator(-)
    module procedure negate_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function negate_vector4 (p) result (q)
    type(vector4_t) :: q
    type(vector4_t), intent(in) :: p

```

```

    q%p = -p%p
end function negate_vector4

```

The sum function can be useful:

```

<Lorentz: interfaces>+≡
interface sum
    module procedure sum_vector4
end interface

```

There used to be a mask here, but the Intel compiler crashes with it

```

<Lorentz: procedures>+≡
pure function sum_vector4 (p) result (q)
    type(vector4_t) :: q
    type(vector4_t), dimension(:), intent(in) :: p
    integer :: i
    do i=0, 3
        q%p(i) = sum (p%p(i))
    end do
end function sum_vector4
! pure function sum_vector4_mask (p, mask) result (q)
!     type(vector4_t) :: q
!     type(vector4_t), dimension(:), intent(in) :: p
!     logical, dimension(:), intent(in) :: mask
!     integer :: i
!     do i=0, 3
!         q%p(i) = sum (p%p(i), mask=mask)
!     end do
! end function sum_vector4_mask

```

4.2.3 Conversions

Manually set a component of the four-vector:

```

<Lorentz: public>+≡
public :: vector4_set_component

<Lorentz: procedures>+≡
subroutine vector4_set_component (p, k, c)
    type(vector4_t), intent(inout) :: p
    integer, intent(in) :: k
    real(default), intent(in) :: c
    p%p(k) = c
end subroutine vector4_set_component

```

Any component:

```

<Lorentz: public>+≡
public :: vector4_get_component

<Lorentz: procedures>+≡
elemental function vector4_get_component (p, k) result (c)
    real(default) :: c
    type(vector4_t), intent(in) :: p
    integer, intent(in) :: k

```

```

        c = p%p(k)
    end function vector4_get_component

```

Extract all components. This is not elemental.

```

<Lorentz: public>+≡
    public :: vector4_get_components

<Lorentz: procedures>+≡
    pure function vector4_get_components (p) result (a)
        real(default), dimension(0:3) :: a
        type(vector4_t), intent(in) :: p
        a = p%p
    end function vector4_get_components

```

This function returns the space part of a four-vector, such that we can apply three-vector operations on it:

```

<Lorentz: public functions>+≡
    public :: space_part

<Lorentz: interfaces>+≡
    interface space_part
        module procedure vector4_get_space_part
    end interface

<Lorentz: procedures>+≡
    elemental function vector4_get_space_part (p) result (q)
        type(vector3_t) :: q
        type(vector4_t), intent(in) :: p
        q%p = p%p(1:)
    end function vector4_get_space_part

```

This function returns the direction of a four-vector, i.e., a normalized three-vector

```

<Lorentz: interfaces>+≡
    interface direction
        module procedure vector4_get_direction
    end interface

<Lorentz: procedures>+≡
    elemental function vector4_get_direction (p) result (q)
        type(vector3_t) :: q
        type(vector4_t), intent(in) :: p
        q%p = p%p(1:)
        q = q / q**1
    end function vector4_get_direction

```

This function returns the four-vector as an ordinary array. A second version for an array of four-vectors.

```

<Lorentz: public functions>+≡
    public :: array_from_vector4

```

```

<Lorentz: interfaces>+≡
  interface array_from_vector4
    module procedure array_from_vector4_1
    module procedure array_from_vector4_2
  end interface

<Lorentz: procedures>+≡
  pure function array_from_vector4_1 (p) result (a)
    type(vector4_t), intent(in) :: p
    real(default), dimension(0:3) :: a
    a = p%p
  end function array_from_vector4_1

  pure function array_from_vector4_2 (p) result (a)
    type(vector4_t), dimension(:), intent(in) :: p
    real(default), dimension(0:3, size(p)) :: a
    integer :: i
    forall (i=1:size(p))
      a(0:3,i) = p(i)%p
    end forall
  end function array_from_vector4_2

```

Transform the momentum of a `c_prt` object into a four-vector:

```

<Lorentz: public>+≡
  public :: vector4_from_c_prt

<Lorentz: procedures>+≡
  elemental function vector4_from_c_prt (c_prt) result (p)
    type(vector4_t) :: p
    type(c_prt_t), intent(in) :: c_prt
    p%p(0) = c_prt%pe
    p%p(1) = c_prt%px
    p%p(2) = c_prt%py
    p%p(3) = c_prt%pz
  end function vector4_from_c_prt

```

Initialize a `c_prt_t` object with the components of a four-vector as its kinematical entries. Compute the invariant mass, or use the optional mass-squared value instead.

```

<Lorentz: public>+≡
  public :: vector4_to_c_prt

<Lorentz: procedures>+≡
  elemental function vector4_to_c_prt (p, p2) result (c_prt)
    type(c_prt_t) :: c_prt
    type(vector4_t), intent(in) :: p
    real(default), intent(in), optional :: p2
    c_prt%pe = p%p(0)
    c_prt%px = p%p(1)
    c_prt%py = p%p(2)
    c_prt%pz = p%p(3)
    if (present (p2)) then
      c_prt%p2 = p2
    else

```

```

        c_prt%p2 = p ** 2
    end if
end function vector4_to_c_prt

```

4.2.4 Angles

Return the angles in a canonical system. The angle ϕ is defined between $0 \leq \phi < 2\pi$. In degenerate cases, return zero.

```

<Lorentz: public functions>+≡
    public :: azimuthal_angle

<Lorentz: interfaces>+≡
    interface azimuthal_angle
        module procedure vector3_azimuthal_angle
        module procedure vector4_azimuthal_angle
    end interface

<Lorentz: procedures>+≡
    elemental function vector3_azimuthal_angle (p) result (phi)
        real(default) :: phi
        type(vector3_t), intent(in) :: p
        if (any(p%p(1:2)/=0)) then
            phi = atan2(p%p(2), p%p(1))
            if (phi < 0) phi = phi + twopi
        else
            phi = 0
        end if
    end function vector3_azimuthal_angle
    elemental function vector4_azimuthal_angle (p) result (phi)
        real(default) :: phi
        type(vector4_t), intent(in) :: p
        phi = vector3_azimuthal_angle (space_part (p))
    end function vector4_azimuthal_angle

```

Azimuthal angle in degrees

```

<Lorentz: public functions>+≡
    public :: azimuthal_angle_deg

<Lorentz: interfaces>+≡
    interface azimuthal_angle_deg
        module procedure vector3_azimuthal_angle_deg
        module procedure vector4_azimuthal_angle_deg
    end interface

<Lorentz: procedures>+≡
    elemental function vector3_azimuthal_angle_deg (p) result (phi)
        real(default) :: phi
        type(vector3_t), intent(in) :: p
        phi = vector3_azimuthal_angle (p) / degree
    end function vector3_azimuthal_angle_deg
    elemental function vector4_azimuthal_angle_deg (p) result (phi)
        real(default) :: phi
        type(vector4_t), intent(in) :: p
        phi = vector4_azimuthal_angle (p) / degree

```

```
end function vector4_azimuthal_angle_deg
```

The azimuthal distance of two vectors. This is the difference of the azimuthal angles, but cannot be larger than π : The result is between $-\pi < \Delta\phi \leq \pi$.

```
<Lorentz: public functions>+≡
  public :: azimuthal_distance

<Lorentz: interfaces>+≡
  interface azimuthal_distance
    module procedure vector3_azimuthal_distance
    module procedure vector4_azimuthal_distance
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_azimuthal_distance (p, q) result (dphi)
    real(default) :: dphi
    type(vector3_t), intent(in) :: p,q
    dphi = vector3_azimuthal_angle (q) - vector3_azimuthal_angle (p)
    if (dphi <= -pi) then
      dphi = dphi + twopi
    else if (dphi > pi) then
      dphi = dphi - twopi
    end if
  end function vector3_azimuthal_distance
  elemental function vector4_azimuthal_distance (p, q) result (dphi)
    real(default) :: dphi
    type(vector4_t), intent(in) :: p,q
    dphi = vector3_azimuthal_distance &
      (space_part (p), space_part (q))
  end function vector4_azimuthal_distance
```

The same in degrees:

```
<Lorentz: public functions>+≡
  public :: azimuthal_distance_deg

<Lorentz: interfaces>+≡
  interface azimuthal_distance_deg
    module procedure vector3_azimuthal_distance_deg
    module procedure vector4_azimuthal_distance_deg
  end interface

<Lorentz: procedures>+≡
  elemental function vector3_azimuthal_distance_deg (p, q) result (dphi)
    real(default) :: dphi
    type(vector3_t), intent(in) :: p,q
    dphi = vector3_azimuthal_distance (p, q) / degree
  end function vector3_azimuthal_distance_deg
  elemental function vector4_azimuthal_distance_deg (p, q) result (dphi)
    real(default) :: dphi
    type(vector4_t), intent(in) :: p,q
    dphi = vector4_azimuthal_distance (p, q) / degree
  end function vector4_azimuthal_distance_deg
```


The polar angle is defined $0 \leq \theta \leq \pi$. Note that ATAN2 has the reversed order of arguments: ATAN2(Y,X). Here, x is the 3-component while y is the transverse momentum which is always nonnegative. Therefore, the result is nonnegative as well.

```

(Lorentz: public functions)+≡
  public :: polar_angle

(Lorentz: interfaces)+≡
  interface polar_angle
    module procedure polar_angle_vector3
    module procedure polar_angle_vector4
  end interface

(Lorentz: procedures)+≡
  elemental function polar_angle_vector3 (p) result (theta)
    real(default) :: theta
    type(vector3_t), intent(in) :: p
    if (any(p%p/=0)) then
      theta = atan2 (sqrt(p%p(1)**2 + p%p(2)**2), p%p(3))
    else
      theta = 0
    end if
  end function polar_angle_vector3
  elemental function polar_angle_vector4 (p) result (theta)
    real(default) :: theta
    type(vector4_t), intent(in) :: p
    theta = polar_angle (space_part (p))
  end function polar_angle_vector4

```

This is the cosine of the polar angle: $-1 \leq \cos \theta \leq 1$.

```

(Lorentz: public functions)+≡
  public :: polar_angle_ct

(Lorentz: interfaces)+≡
  interface polar_angle_ct
    module procedure polar_angle_ct_vector3
    module procedure polar_angle_ct_vector4
  end interface

(Lorentz: procedures)+≡
  elemental function polar_angle_ct_vector3 (p) result (ct)
    real(default) :: ct
    type(vector3_t), intent(in) :: p
    if (any(p%p/=0)) then
      ct = p%p(3) / p**1
    else
      ct = 1
    end if
  end function polar_angle_ct_vector3
  elemental function polar_angle_ct_vector4 (p) result (ct)
    real(default) :: ct
    type(vector4_t), intent(in) :: p
    ct = polar_angle_ct (space_part (p))
  end function polar_angle_ct_vector4

```

The polar angle in degrees.

```

<Lorentz: public functions>+≡
    public :: polar_angle_deg

<Lorentz: interfaces>+≡
    interface polar_angle_deg
        module procedure polar_angle_deg_vector3
        module procedure polar_angle_deg_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function polar_angle_deg_vector3 (p) result (theta)
        real(default) :: theta
        type(vector3_t), intent(in) :: p
        theta = polar_angle (p) / degree
    end function polar_angle_deg_vector3
    elemental function polar_angle_deg_vector4 (p) result (theta)
        real(default) :: theta
        type(vector4_t), intent(in) :: p
        theta = polar_angle (p) / degree
    end function polar_angle_deg_vector4

```

This is the angle enclosed between two three-momenta. If one of the momenta is zero, we return an angle of zero. The range of the result is $0 \leq \theta \leq \pi$. If there is only one argument, take the positive z axis as reference.

```

<Lorentz: public functions>+≡
    public :: enclosed_angle

<Lorentz: interfaces>+≡
    interface enclosed_angle
        module procedure enclosed_angle_vector3
        module procedure enclosed_angle_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function enclosed_angle_vector3 (p, q) result (theta)
        real(default) :: theta
        type(vector3_t), intent(in) :: p, q
        theta = acos (enclosed_angle_ct (p, q))
    end function enclosed_angle_vector3
    elemental function enclosed_angle_vector4 (p, q) result (theta)
        real(default) :: theta
        type(vector4_t), intent(in) :: p, q
        theta = enclosed_angle (space_part (p), space_part (q))
    end function enclosed_angle_vector4

```

The cosine of the enclosed angle.

```

<Lorentz: public functions>+≡
    public :: enclosed_angle_ct

<Lorentz: interfaces>+≡
    interface enclosed_angle_ct
        module procedure enclosed_angle_ct_vector3
        module procedure enclosed_angle_ct_vector4
    end interface

```

```

<Lorentz: procedures>+≡
  elemental function enclosed_angle_ct_vector3 (p, q) result (ct)
    real(default) :: ct
    type(vector3_t), intent(in) :: p, q
    if (any(p%p/=0).and.any(q%p/=0)) then
      ct = p*q / (p**1 * q**1)
      if (ct>1) then
        ct = 1
      else if (ct<-1) then
        ct = -1
      end if
    else
      ct = 1
    end if
  end function enclosed_angle_ct_vector3
  elemental function enclosed_angle_ct_vector4 (p, q) result (ct)
    real(default) :: ct
    type(vector4_t), intent(in) :: p, q
    ct = enclosed_angle_ct (space_part (p), space_part (q))
  end function enclosed_angle_ct_vector4

```

The enclosed angle in degrees.

```

<Lorentz: public functions>+≡
  public :: enclosed_angle_deg

<Lorentz: interfaces>+≡
  interface enclosed_angle_deg
    module procedure enclosed_angle_deg_vector3
    module procedure enclosed_angle_deg_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function enclosed_angle_deg_vector3 (p, q) result (theta)
    real(default) :: theta
    type(vector3_t), intent(in) :: p, q
    theta = enclosed_angle (p, q) / degree
  end function enclosed_angle_deg_vector3
  elemental function enclosed_angle_deg_vector4 (p, q) result (theta)
    real(default) :: theta
    type(vector4_t), intent(in) :: p, q
    theta = enclosed_angle (p, q) / degree
  end function enclosed_angle_deg_vector4

```

The polar angle of the first momentum w.r.t. the second momentum, evaluated in the rest frame of the second momentum. If the second four-momentum is not timelike, return zero.

```

<Lorentz: public functions>+≡
  public :: enclosed_angle_rest_frame
  public :: enclosed_angle_ct_rest_frame
  public :: enclosed_angle_deg_rest_frame

<Lorentz: interfaces>+≡
  interface enclosed_angle_rest_frame
    module procedure enclosed_angle_rest_frame_vector4

```

```

end interface
interface enclosed_angle_ct_rest_frame
  module procedure enclosed_angle_ct_rest_frame_vector4
end interface
interface enclosed_angle_deg_rest_frame
  module procedure enclosed_angle_deg_rest_frame_vector4
end interface
(Lorentz: procedures)+≡
elemental function enclosed_angle_rest_frame_vector4 (p, q) result (theta)
  type(vector4_t), intent(in) :: p, q
  real(default) :: theta
  theta = acos (enclosed_angle_ct_rest_frame (p, q))
end function enclosed_angle_rest_frame_vector4
elemental function enclosed_angle_ct_rest_frame_vector4 (p, q) result (ct)
  type(vector4_t), intent(in) :: p, q
  real(default) :: ct
  if (invariant_mass(q) > 0) then
    ct = enclosed_angle_ct ( &
      space_part (boost(-q, invariant_mass (q)) * p), &
      space_part (q))
  else
    ct = 1
  end if
end function enclosed_angle_ct_rest_frame_vector4
elemental function enclosed_angle_deg_rest_frame_vector4 (p, q) &
  result (theta)
  type(vector4_t), intent(in) :: p, q
  real(default) :: theta
  theta = enclosed_angle_rest_frame (p, q) / degree
end function enclosed_angle_deg_rest_frame_vector4

```

4.2.5 More kinematical functions (some redundant)

The scalar transverse momentum (assuming the z axis is longitudinal)

```

(Lorentz: public functions)+≡
  public :: transverse_part
(Lorentz: interfaces)+≡
  interface transverse_part
    module procedure transverse_part_vector4
  end interface
(Lorentz: procedures)+≡
  elemental function transverse_part_vector4 (p) result (pT)
    real(default) :: pT
    type(vector4_t), intent(in) :: p
    pT = sqrt(p%p(1)**2 + p%p(2)**2)
  end function transverse_part_vector4

```

The scalar longitudinal momentum (assuming the z axis is longitudinal). Identical to `momentum_z_component`.

```

(Lorentz: public functions)+≡
  public :: longitudinal_part

```

```

<Lorentz: interfaces>+≡
  interface longitudinal_part
    module procedure longitudinal_part_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function longitudinal_part_vector4 (p) result (pL)
    real(default) :: pL
    type(vector4_t), intent(in) :: p
    pL = p%p(3)
  end function longitudinal_part_vector4

```

Absolute value of three-momentum

```

<Lorentz: public functions>+≡
  public :: space_part_norm

<Lorentz: interfaces>+≡
  interface space_part_norm
    module procedure space_part_norm_vector4
  end interface

<Lorentz: procedures>+≡
  elemental function space_part_norm_vector4 (p) result (p3)
    real(default) :: p3
    type(vector4_t), intent(in) :: p
    p3 = sqrt (p%p(1)**2 + p%p(2)**2 + p%p(3)**2)
  end function space_part_norm_vector4

```

The energy (the zeroth component)

```

<Lorentz: public functions>+≡
  public :: energy

<Lorentz: interfaces>+≡
  interface energy
    module procedure energy_vector4
    module procedure energy_vector3
    module procedure energy_real
  end interface

<Lorentz: procedures>+≡
  elemental function energy_vector4 (p) result (E)
    real(default) :: E
    type(vector4_t), intent(in) :: p
    E = p%p(0)
  end function energy_vector4

```

Alternative: The energy corresponding to a given momentum and mass. If the mass is omitted, it is zero

```

<Lorentz: procedures>+≡
  elemental function energy_vector3 (p, mass) result (E)
    real(default) :: E
    type(vector3_t), intent(in) :: p
    real(default), intent(in), optional :: mass
    if (present (mass)) then
      E = sqrt (p**2 + mass**2)
    end if
  end function energy_vector3

```

```

    else
        E = p**1
    end if
end function energy_vector3

elemental function energy_real (p, mass) result (E)
    real(default) :: E
    real(default), intent(in) :: p
    real(default), intent(in), optional :: mass
    if (present (mass)) then
        E = sqrt (p**2 + mass**2)
    else
        E = abs (p)
    end if
end function energy_real

```

The invariant mass of four-momenta. Zero for lightlike, negative for spacelike momenta.

```

<Lorentz: public functions>+≡
    public :: invariant_mass

<Lorentz: interfaces>+≡
    interface invariant_mass
        module procedure invariant_mass_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function invariant_mass_vector4 (p) result (m)
        real(default) :: m
        type(vector4_t), intent(in) :: p
        real(default) :: msq
        msq = p*p
        if (msq >= 0) then
            m = sqrt (msq)
        else
            m = - sqrt (abs (msq))
        end if
    end function invariant_mass_vector4

```

The invariant mass squared. Zero for lightlike, negative for spacelike momenta.

```

<Lorentz: public functions>+≡
    public :: invariant_mass_squared

<Lorentz: interfaces>+≡
    interface invariant_mass_squared
        module procedure invariant_mass_squared_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function invariant_mass_squared_vector4 (p) result (msq)
        real(default) :: msq
        type(vector4_t), intent(in) :: p
        msq = p*p
    end function invariant_mass_squared_vector4

```

The transverse mass. If the mass squared is negative, this value also is negative.

```

<Lorentz: public functions>+≡
    public :: transverse_mass

<Lorentz: interfaces>+≡
    interface transverse_mass
        module procedure transverse_mass_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function transverse_mass_vector4 (p) result (m)
        real(default) :: m
        type(vector4_t), intent(in) :: p
        real(default) :: msq
        msq = p%p(0)**2 - p%p(1)**2 - p%p(2)**2
        if (msq >= 0) then
            m = sqrt (msq)
        else
            m = - sqrt (abs (msq))
        end if
    end function transverse_mass_vector4

```

The rapidity (defined if particle is massive or $p_{\perp} > 0$)

```

<Lorentz: public functions>+≡
    public :: rapidity

<Lorentz: interfaces>+≡
    interface rapidity
        module procedure rapidity_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function rapidity_vector4 (p) result (y)
        real(default) :: y
        type(vector4_t), intent(in) :: p
        y = .5 * log( (energy (p) + longitudinal_part (p)) &
            & / (energy (p) - longitudinal_part (p)))
    end function rapidity_vector4

```

The pseudorapidity (defined if $p_{\perp} > 0$)

```

<Lorentz: public functions>+≡
    public :: pseudorapidity

<Lorentz: interfaces>+≡
    interface pseudorapidity
        module procedure pseudorapidity_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function pseudorapidity_vector4 (p) result (eta)
        real(default) :: eta
        type(vector4_t), intent(in) :: p
        eta = -log( tan (.5 * polar_angle (p)))
    end function pseudorapidity_vector4

```

The rapidity distance (defined if both $p_{\perp} > 0$)

```

<Lorentz: public functions>+≡
    public :: rapidity_distance

<Lorentz: interfaces>+≡
    interface rapidity_distance
        module procedure rapidity_distance_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function rapidity_distance_vector4 (p, q) result (dy)
        type(vector4_t), intent(in) :: p, q
        real(default) :: dy
        dy = rapidity (q) - rapidity (p)
    end function rapidity_distance_vector4

```

The pseudorapidity distance (defined if both $p_{\perp} > 0$)

```

<Lorentz: public functions>+≡
    public :: pseudorapidity_distance

<Lorentz: interfaces>+≡
    interface pseudorapidity_distance
        module procedure pseudorapidity_distance_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function pseudorapidity_distance_vector4 (p, q) result (deta)
        real(default) :: deta
        type(vector4_t), intent(in) :: p, q
        deta = pseudorapidity (q) - pseudorapidity (p)
    end function pseudorapidity_distance_vector4

```

The distance on the $\eta - \phi$ cylinder:

```

<Lorentz: public functions>+≡
    public :: eta_phi_distance

<Lorentz: interfaces>+≡
    interface eta_phi_distance
        module procedure eta_phi_distance_vector4
    end interface

<Lorentz: procedures>+≡
    elemental function eta_phi_distance_vector4 (p, q) result (dr)
        type(vector4_t), intent(in) :: p, q
        real(default) :: dr
        dr = sqrt ( &
            pseudorapidity_distance (p, q)**2 &
            + azimuthal_distance (p, q)**2)
    end function eta_phi_distance_vector4

```

4.2.6 Lorentz transformations

```

<Lorentz: public>+≡
    public :: lorentz_transformation_t

```



```

<Lorentz: types>+≡
  type :: lorentz_transformation_t
  private
    real(default), dimension(0:3, 0:3) :: L
  end type lorentz_transformation_t

```

Output:

```

<Lorentz: public>+≡
  public :: lorentz_transformation_write

<Lorentz: procedures>+≡
  subroutine lorentz_transformation_write (L, unit)
    type(lorentz_transformation_t), intent(in) :: L
    integer, intent(in), optional :: unit
    integer :: u
    integer :: i
    u = output_unit (unit); if (u < 0) return
    write (u, *) 'Lorentz transformation:'
    write (u, *) 'L00:'
    write (u, *) L%L(0,0)
    write (u, *) 'L0j:', L%L(0,1:)
    write (u, *) 'Li0, Lij:'
    do i = 1, 3
      write (u, *) L%L(i,0)
      write (u, *) '      ', L%L(i,1:)
    end do
  end subroutine lorentz_transformation_write

```

Extract all components:

```

<Lorentz: public>+≡
  public :: lorentz_transformation_get_components

<Lorentz: procedures>+≡
  pure function lorentz_transformation_get_components (L) result (a)
    type(lorentz_transformation_t), intent(in) :: L
    real(default), dimension(0:3,0:3) :: a
    a = L%L
  end function lorentz_transformation_get_components

```

4.2.7 Functions of Lorentz transformations

For the inverse, we make use of the fact that $\Lambda^{\mu\nu}\Lambda_{\mu\rho} = \delta_{\rho}^{\nu}$. So, lowering the indices and transposing is sufficient.

```

<Lorentz: public functions>+≡
  public :: inverse

<Lorentz: interfaces>+≡
  interface inverse
    module procedure lorentz_transformation_inverse
  end interface

```

```

<Lorentz: procedures>+≡
  elemental function lorentz_transformation_inverse (L) result (IL)
    type(lorentz_transformation_t) :: IL
    type(lorentz_transformation_t), intent(in) :: L
    IL%L(0,0) = L%L(0,0)
    IL%L(0,1:) = -L%L(1:,0)
    IL%L(1:,0) = -L%L(0,1:)
    IL%L(1:,1:) = transpose(L%L(1:,1:))
  end function lorentz_transformation_inverse

```

4.2.8 Invariants

These are used below. The first array index is varying fastest in FORTRAN; therefore the extra minus in the odd-rank tensor epsilon.

```

<Lorentz: parameters>+≡
  integer, dimension(3,3), parameter :: delta_three = &
    & reshape( source = (/ 1,0,0, 0,1,0, 0,0,1 /), &
    &          shape = (/3,3/) )
  integer, dimension(3,3,3), parameter :: epsilon_three = &
    & reshape( source = (/ 0, 0,0, 0,0,-1, 0,1,0,&
    &                      0, 0,1, 0,0, 0, -1,0,0,&
    &                      0,-1,0, 1,0, 0, 0,0,0 /),&
    &          shape = (/3,3,3/) )

```

This could be of some use:

```

<Lorentz: public>+≡
  public :: identity

<Lorentz: parameters>+≡
  type(lorentz_transformation_t), parameter :: &
    & identity = &
    & lorentz_transformation_t ( &
    & reshape( source = (/ 1._default, 0._default, 0._default, 0._default, &
    &                      0._default, 1._default, 0._default, 0._default, &
    &                      0._default, 0._default, 1._default, 0._default, &
    &                      0._default, 0._default, 0._default, 1._default /),&
    &          shape = (/ 4,4 /) ) )

<Lorentz: public>+≡
  public :: space_reflection

<Lorentz: parameters>+≡
  type(lorentz_transformation_t), parameter :: &
    & space_reflection = &
    & lorentz_transformation_t ( &
    & reshape( source = (/ 1._default, 0._default, 0._default, 0._default, &
    &                      0._default,-1._default, 0._default, 0._default, &
    &                      0._default, 0._default,-1._default, 0._default, &
    &                      0._default, 0._default, 0._default,-1._default /),&
    &          shape = (/ 4,4 /) ) )

```

4.2.9 Boosts

We build Lorentz transformations from boosts and rotations. In both cases we can supply a three-vector which defines the axis and (hyperbolic) angle. For a boost, this is the vector $\vec{\beta} = \vec{p}/E$, such that a particle at rest with mass m is boosted to a particle with three-vector \vec{p} . Here, we have

$$\beta = \tanh \chi = p/E, \quad \gamma = \cosh \chi = E/m, \quad \beta\gamma = \sinh \chi = p/m \quad (4.1)$$

```

(Lorentz: public functions)+≡
  public :: boost

(Lorentz: interfaces)+≡
  interface boost
    module procedure boost_from_rest_frame
    module procedure boost_from_rest_frame_vector3
    module procedure boost_generic
    module procedure boost_canonical
  end interface

```

In the first form, the argument is some four-momentum, the space part of which determines a direction, and the associated mass (which is not checked against the four-momentum). The boost vector $\gamma\vec{\beta}$ is then given by \vec{p}/m . This boosts from the rest frame of a particle to the current frame. To be explicit, if \vec{p} is the momentum of a particle and m its mass, $L(\vec{p}/m)$ is the transformation that turns $(m; \vec{0})$ into $(E; \vec{p})$. Conversely, the inverse transformation boosts a vector *into* the rest frame of a particle, in particular $(E; \vec{p})$ into $(m; \vec{0})$.

```

(Lorentz: procedures)+≡
  elemental function boost_from_rest_frame (p, m) result (L)
    type(lorentz_transformation_t) :: L
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: m
    L = boost_from_rest_frame_vector3 (space_part (p), m)
  end function boost_from_rest_frame
  elemental function boost_from_rest_frame_vector3 (p, m) result (L)
    type(lorentz_transformation_t) :: L
    type(vector3_t), intent(in) :: p
    real(default), intent(in) :: m
    type(vector3_t) :: beta_gamma
    real(default) :: bg2, g, c
    integer :: i,j
    if (m /= 0) then
      beta_gamma = p / m
      bg2 = beta_gamma**2
    else
      bg2 = 0
    end if
    if (bg2 /= 0) then
      g = sqrt(1 + bg2); c = (g-1)/bg2
      L%L(0,0) = g
      L%L(0,1:) = beta_gamma%p
      L%L(1:,0) = L%L(0,1:)
      do i=1,3
        do j=1,3
          L%L(i,j) = delta_three(i,j) + c*beta_gamma%p(i)*beta_gamma%p(j)
        end do
      end do
    end if
  end function boost_from_rest_frame_vector3

```

```

        end do
    end do
else
    L = identity
end if
end function boost_from_rest_frame_vector3

```

A canonical boost is a boost along one of the coordinate axes, which we may supply as an integer argument. Here, $\gamma\beta$ is scalar.

```

(Lorentz: procedures)+≡
elemental function boost_canonical (beta_gamma, k) result (L)
    type(lorentz_transformation_t) :: L
    real(default), intent(in) :: beta_gamma
    integer, intent(in) :: k
    real(default) :: g
    g = sqrt(1 + beta_gamma**2)
    L = identity
    L%L(0,0) = g
    L%L(0,k) = beta_gamma
    L%L(k,0) = L%L(0,k)
    L%L(k,k) = L%L(0,0)
end function boost_canonical

```

Instead of a canonical axis, we can supply an arbitrary axis which need not be normalized. If it is zero, return the unit matrix.

```

(Lorentz: procedures)+≡
elemental function boost_generic (beta_gamma, axis) result (L)
    type(lorentz_transformation_t) :: L
    real(default), intent(in) :: beta_gamma
    type(vector3_t), intent(in) :: axis
    if (any(axis/=0)) then
        L = boost_from_rest_frame_vector3 (beta_gamma * axis, axis**1)
    else
        L = identity
    end if
end function boost_generic

```

4.2.10 Rotations

For a rotation, the vector defines the rotation axis, and its length the rotation angle.

```

(Lorentz: public functions)+≡
    public :: rotation

(Lorentz: interfaces)+≡
    interface rotation
        module procedure rotation_generic
        module procedure rotation_canonical
        module procedure rotation_generic_cs
        module procedure rotation_canonical_cs
    end interface

```

If $\cos \phi$ and $\sin \phi$ is already known, we do not have to calculate them. Of course, the user has to ensure that $\cos^2 \phi + \sin^2 \phi = 1$, and that the given axis \mathbf{n} is normalized to one. In the second form, the length of `axis` is the rotation angle.

```
(Lorentz: procedures)+≡
  elemental function rotation_generic_cs (cp, sp, axis) result (R)
    type(lorentz_transformation_t) :: R
    real(default), intent(in) :: cp, sp
    type(vector3_t), intent(in) :: axis
    integer :: i,j
    R = identity
    do i=1,3
      do j=1,3
        R%L(i,j) = cp*delta_three(i,j) + (1-cp)*axis%p(i)*axis%p(j) &
          & - sp*dot_product(epsilon_three(i,j,:), axis%p)
      end do
    end do
  end function rotation_generic_cs
  elemental function rotation_generic (axis) result (R)
    type(lorentz_transformation_t) :: R
    type(vector3_t), intent(in) :: axis
    real(default) :: phi
    if (any(axis%p/=0)) then
      phi = abs(axis**1)
      R = rotation_generic_cs (cos(phi), sin(phi), axis/phi)
    else
      R = identity
    end if
  end function rotation_generic
```

Alternatively, give just the angle and label the coordinate axis by an integer.

```
(Lorentz: procedures)+≡
  elemental function rotation_canonical_cs (cp, sp, k) result (R)
    type(lorentz_transformation_t) :: R
    real(default), intent(in) :: cp, sp
    integer, intent(in) :: k
    integer :: i,j
    R = identity
    do i=1,3
      do j=1,3
        R%L(i,j) = -sp*epsilon_three(i,j,k)
      end do
      R%L(i,i) = cp
    end do
    R%L(k,k) = 1
  end function rotation_canonical_cs
  elemental function rotation_canonical (phi, k) result (R)
    type(lorentz_transformation_t) :: R
    real(default), intent(in) :: phi
    integer, intent(in) :: k
    R = rotation_canonical_cs(cos(phi), sin(phi), k)
  end function rotation_canonical
```

This is viewed as a method for the first argument (three-vector): Reconstruct the rotation that rotates it into the second three-vector.

```

<Lorentz: public functions>+≡
  public :: rotation_to_2nd

<Lorentz: interfaces>+≡
  interface rotation_to_2nd
    module procedure rotation_to_2nd_generic
    module procedure rotation_to_2nd_canonical
  end interface

<Lorentz: procedures>+≡
  elemental function rotation_to_2nd_generic (p, q) result (R)
    type(lorentz_transformation_t) :: R
    type(vector3_t), intent(in) :: p, q
    type(vector3_t) :: a, b, ab
    real(default) :: ct, st
    if (any (p%p /= 0) .and. any (q%p /= 0)) then
      a = direction (p)
      b = direction (q)
      ab = cross_product(a,b)
      ct = a*b;  st = ab**1
      if (st /= 0) then
        R = rotation_generic_cs (ct, st, ab/st)
      else if (ct < 0) then
        R = space_reflection
      else
        R = identity
      end if
    else
      R = identity
    end if
  end function rotation_to_2nd_generic

```

The same for a canonical axis: The function returns the transformation that rotates the k -axis into the direction of p .

```

<Lorentz: procedures>+≡
  elemental function rotation_to_2nd_canonical (k, p) result (R)
    type(lorentz_transformation_t) :: R
    integer, intent(in) :: k
    type(vector3_t), intent(in) :: p
    type(vector3_t) :: b, ab
    real(default) :: ct, st
    integer :: i, j
    if (any (p%p /= 0)) then
      b = direction (p)
      ab%p = 0
      do i = 1, 3
        do j = 1, 3
          ab%p(j) = ab%p(j) + b%p(i) * epsilon_three(i,j,k)
        end do
      end do
      ct = b%p(k);  st = ab**1
      if (st /= 0) then
        R = rotation_generic_cs (ct, st, ab/st)
      else if (ct < 0) then
        R = space_reflection
      else

```

```

        R = identity
    end if
else
    R = identity
end if
end function rotation_to_2nd_canonical

```

4.2.11 Composite Lorentz transformations

This function returns the transformation that, given a pair of vectors $p_{1,2}$, (a) boosts from the rest frame of the c.m. system (with invariant mass m) into the lab frame where p_i are defined, and (b) turns the given axis (or the canonical vectors $\pm e_k$) in the rest frame into the directions of $p_{1,2}$ in the lab frame. Note that the energy components are not used; for a consistent result one should have $(p_1 + p_2)^2 = m^2$.

```

<Lorentz: public functions>+≡
    public :: transformation

<Lorentz: interfaces>+≡
    interface transformation
        module procedure transformation_rec_generic
        module procedure transformation_rec_canonical
    end interface

<Lorentz: procedures>+≡
    elemental function transformation_rec_generic (axis, p1, p2, m) result (L)
        type(vector3_t), intent(in) :: axis
        type(vector4_t), intent(in) :: p1, p2
        real(default), intent(in) :: m
        type(lorentz_transformation_t) :: L
        L = boost (p1 + p2, m)
        L = L * rotation_to_2nd (axis, space_part (inverse (L) * p1))
    end function transformation_rec_generic
    elemental function transformation_rec_canonical (k, p1, p2, m) result (L)
        integer, intent(in) :: k
        type(vector4_t), intent(in) :: p1, p2
        real(default), intent(in) :: m
        type(lorentz_transformation_t) :: L
        L = boost (p1 + p2, m)
        L = L * rotation_to_2nd (k, space_part (inverse (L) * p1))
    end function transformation_rec_canonical

```

4.2.12 Applying Lorentz transformations

Multiplying vectors and Lorentz transformations is straightforward.

```

<Lorentz: interfaces>+≡
    interface operator(*)
        module procedure prod_LT_vector4
        module procedure prod_LT_LT
        module procedure prod_vector4_LT
    end interface

```

```

<Lorentz: procedures>+≡
  elemental function prod_LT_vector4 (L, p) result (np)
    type(vector4_t) :: np
    type(lorentz_transformation_t), intent(in) :: L
    type(vector4_t), intent(in) :: p
    np%p = matmul (L%L, p%p)
  end function prod_LT_vector4
  elemental function prod_LT_LT (L1, L2) result (NL)
    type(lorentz_transformation_t) :: NL
    type(lorentz_transformation_t), intent(in) :: L1,L2
    NL%L = matmul (L1%L, L2%L)
  end function prod_LT_LT
  elemental function prod_vector4_LT (p, L) result (np)
    type(vector4_t) :: np
    type(vector4_t), intent(in) :: p
    type(lorentz_transformation_t), intent(in) :: L
    np%p = matmul (p%p, L%L)
  end function prod_vector4_LT

```

4.2.13 Special Lorentz transformations

These routines have their application in the generation and extraction of angles in the phase-space sampling routine. Since this part of the program is time-critical, we calculate the composition of transformations directly instead of multiplying rotations and boosts.

This Lorentz transformation is the composition of a rotation by ϕ around the 3 axis, a rotation by θ around the 2 axis, and a boost along the 3 axis:

$$L = B_3(\beta\gamma) R_2(\theta) R_3(\phi) \quad (4.2)$$

Instead of the angles we provide sine and cosine.

```

<Lorentz: public functions>+≡
  public :: LT_compose_r3_r2_b3

<Lorentz: procedures>+≡
  elemental function LT_compose_r3_r2_b3 &
    (cp, sp, ct, st, beta_gamma) result (L)
    type(lorentz_transformation_t) :: L
    real(default), intent(in) :: cp, sp, ct, st, beta_gamma
    real(default) :: gamma
    if (beta_gamma==0) then
      L%L(0,0) = 1
      L%L(1:,0) = 0
      L%L(0,1:) = 0
      L%L(1,1:) = (/ ct*cp, -ct*sp, st /)
      L%L(2,1:) = (/ sp, cp, 0._default /)
      L%L(3,1:) = (/ -st*cp, st*sp, ct /)
    else
      gamma = sqrt(1 + beta_gamma**2)
      L%L(0,0) = gamma
      L%L(1,0) = 0
      L%L(2,0) = 0
      L%L(3,0) = beta_gamma

```



```

        L%L(0,1:) = beta_gamma * (/ -st*cp, st*sp, ct /)
        L%L(1,1:) = (/ ct*cp, -ct*sp, st /)
        L%L(2,1:) = (/ sp, cp, 0._default /)
        L%L(3,1:) = gamma * (/ -st*cp, st*sp, ct /)
    end if
end function LT_compose_r3_r2_b3

```

Different ordering:

$$L = B_3(\beta\gamma) R_3(\phi) R_2(\theta) \quad (4.3)$$

```

<Lorentz: public functions>+≡
public :: LT_compose_r2_r3_b3

<Lorentz: procedures>+≡
elemental function LT_compose_r2_r3_b3 &
    (ct, st, cp, sp, beta_gamma) result (L)
type(lorentz_transformation_t) :: L
real(default), intent(in) :: ct, st, cp, sp, beta_gamma
real(default) :: gamma
if (beta_gamma==0) then
    L%L(0,0) = 1
    L%L(1,0) = 0
    L%L(0,1:) = 0
    L%L(1,1:) = (/ ct*cp, -sp, st*cp /)
    L%L(2,1:) = (/ ct*sp, cp, st*sp /)
    L%L(3,1:) = (/ -st, 0._default, ct /)
else
    gamma = sqrt(1 + beta_gamma**2)
    L%L(0,0) = gamma
    L%L(1,0) = 0
    L%L(2,0) = 0
    L%L(3,0) = beta_gamma
    L%L(0,1:) = beta_gamma * (/ -st, 0._default, ct /)
    L%L(1,1:) = (/ ct*cp, -sp, st*cp /)
    L%L(2,1:) = (/ ct*sp, cp, st*sp /)
    L%L(3,1:) = gamma * (/ -st, 0._default, ct /)
end if
end function LT_compose_r2_r3_b3

```

This function returns the previous Lorentz transformation applied to an arbitrary four-momentum and extracts the space part of the result:

$$\vec{n} = [B_3(\beta\gamma) R_2(\theta) R_3(\phi) p]_{\text{space part}} \quad (4.4)$$

The second variant applies if there is no rotation

```

<Lorentz: public functions>+≡
public :: axis_from_p_r3_r2_b3, axis_from_p_b3

<Lorentz: procedures>+≡
elemental function axis_from_p_r3_r2_b3 &
    (p, cp, sp, ct, st, beta_gamma) result (n)
type(vector3_t) :: n
type(vector4_t), intent(in) :: p
real(default), intent(in) :: cp, sp, ct, st, beta_gamma

```

```

real(default) :: gamma, px, py
px = cp * p%p(1) - sp * p%p(2)
py = sp * p%p(1) + cp * p%p(2)
n%p(1) = ct * px + st * p%p(3)
n%p(2) = py
n%p(3) = -st * px + ct * p%p(3)
if (beta_gamma/=0) then
    gamma = sqrt(1 + beta_gamma**2)
    n%p(3) = n%p(3) * gamma + p%p(0) * beta_gamma
end if
end function axis_from_p_r3_r2_b3

elemental function axis_from_p_b3 (p, beta_gamma) result (n)
type(vector3_t) :: n
type(vector4_t), intent(in) :: p
real(default), intent(in) :: beta_gamma
real(default) :: gamma
n%p = p%p(1:3)
if (beta_gamma/=0) then
    gamma = sqrt(1 + beta_gamma**2)
    n%p(3) = n%p(3) * gamma + p%p(0) * beta_gamma
end if
end function axis_from_p_b3

```

4.2.14 Special functions

The standard phase space function:

```

(Lorentz: public functions)+≡
public :: lambda

(Lorentz: procedures)+≡
elemental function lambda (m1sq, m2sq, m3sq)
real(default) :: lambda
real(default), intent(in) :: m1sq, m2sq, m3sq
lambda = (m1sq - m2sq - m3sq)**2 - 4*m2sq*m3sq
end function lambda

```

Return a pair of head-to-head colliding momenta, given the collider energy, particle masses, and optionally the momentum of the c.m. system.

```

(Lorentz: public functions)+≡
public :: colliding_momenta

(Lorentz: procedures)+≡
function colliding_momenta (sqrts, m, p_cm) result (p)
type(vector4_t), dimension(2) :: p
real(default), intent(in) :: squrts
real(default), dimension(2), intent(in), optional :: m
real(default), intent(in), optional :: p_cm
real(default), dimension(2) :: dmsq
real(default) :: ch, sh
real(default), dimension(2) :: E0, p0
integer, dimension(2), parameter :: sgn = (/1, -1/)
if (sqrts == 0) then

```

```

        call msg_fatal (" Colliding beams: sqrts is zero (please set sqrts)")
        p = vector4_null; return
    else if (sqrts <= 0) then
        call msg_fatal (" Colliding beams: sqrts is negative")
        p = vector4_null; return
    end if
    if (present (m)) then
        dmsq = sgn * (m(1)**2-m(2)**2)
        E0 = (sqrts + dmsq/sqrts) / 2
        if (any (E0 < m)) then
            call msg_fatal &
                (" Colliding beams: beam energy is less than particle mass")
            p = vector4_null; return
        end if
        p0 = sgn * sqrt (E0**2 - m**2)
    else
        E0 = sqrts / 2
        p0 = sgn * E0
    end if
    if (present (p_cm)) then
        sh = p_cm / sqrts
        ch = sqrt (1 + sh**2)
        p = vector4_moving (E0 * ch + p0 * sh, E0 * sh + p0 * ch, 3)
    else
        p = vector4_moving (E0, p0, 3)
    end if
end function colliding_momenta

```

4.3 Special Physics functions

Define special kinematical functions like running α_s and e.g. Catani-Seymour dipole terms.

To make maximum use of this, all functions, if possible, are declared elemental (or pure, if this is not possible).

```

<sm_physics.f90>≡
  <File header>

  module sm_physics

    <Use kinds>
    use constants !NODEP!
    <Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!

    <Standard module head>

    <SM physics: public parameters>

    <SM physics: public functions>

  contains

    <SM physics: subroutines>
  end module sm_physics

```

First we set a reference value for $\alpha_s(M_Z) = 0.1178$.

```

<SM physics: public parameters>≡
  real(kind=default), public, parameter :: as_mz = 0.1178_default, &
    mass_z = 91.188_default

```

Then we define the coefficients of the beta function of QCD (as a reference cf. the Particle Data Group), where n_f is the number of active flavors in two different schemes:

$$\beta_0 = 11 - \frac{2}{3}n_f \quad (4.5)$$

$$\beta_1 = 51 - \frac{19}{3}n_f \quad (4.6)$$

$$\beta_2 = 2857 - \frac{5033}{9}n_f + \frac{325}{27}n_f^2 \quad (4.7)$$

$$b_0 = \frac{1}{12\pi} (11C_A - 2n_f) \quad (4.8)$$

$$b_1 = \frac{1}{24\pi^2} (17C_A^2 - 5C_An_f - 3C_Fn_f) \quad (4.9)$$

$$b_2 = \frac{1}{(4\pi)^3} \left(\frac{2857}{54}C_A^3 - \frac{1415}{54}C_A^2n_f - \frac{205}{18}C_AC_Fn_f + C_F^2n_f + \frac{79}{54}C_An_f^{**2} + \frac{11}{9}C_Fn_f^{**2} \right) \quad (4.10)$$

```

<SM physics: public functions>≡
  public :: beta0, beta1, beta2, coeff_b0, coeff_b1, coeff_b2

```

```

<SM physics: subroutines>≡
pure function beta0 (nf)
  real(kind=default), intent(in) :: nf
  real(kind=default) :: beta0
  beta0 = 11.0_default - two/three * nf
end function beta0

pure function beta1 (nf)
  real(kind=default), intent(in) :: nf
  real(kind=default) :: beta1
  beta1 = 51.0_default - 19.0_default/three * nf
end function beta1

pure function beta2 (nf)
  real(kind=default), intent(in) :: nf
  real(kind=default) :: beta2
  beta2 = 2857.0_default - 5033.0_default / 9.0_default * &
    nf + 325.0_default/27.0_default * nf**2
end function beta2

pure function coeff_b0 (nf)
  real(kind=default), intent(in) :: nf
  real(kind=default) :: coeff_b0
  coeff_b0 = (11.0_default * CA - two * nf) / (12.0_default * pi)
end function coeff_b0

pure function coeff_b1 (nf)
  real(kind=default), intent(in) :: nf
  real(kind=default) :: coeff_b1
  coeff_b1 = (17.0_default * CA**2 - five * CA * nf - three * CF * nf) / &
    (24.0_default * pi**2)
end function coeff_b1

pure function coeff_b2 (nf)
  real(kind=default), intent(in) :: nf
  real(kind=default) :: coeff_b2
  coeff_b2 = (2857.0_default/54.0_default * CA**3 - &
    1415.0_default/54.0_default * &
    CA**2 * nf - 205.0_default/18.0_default * CA*CF*nf &
    + 79.0_default/54.0_default * CA*nf**2 + &
    11.0_default/9.0_default * CF * nf**2) / (four*pi)**3
end function coeff_b2

```

There should be two versions of running α_s , one which takes the scale and Λ_{QCD} as input, and one which takes the scale and e.g. $\alpha_s(m_Z)$ as input. Here, we take the one which takes the QCD scale and scale as inputs from the PDG book.

```

<SM physics: public functions>+≡
public :: running_as, running_as_lam

<SM physics: subroutines>+≡
pure function running_as (scale,al_mz,mz,order,nf) result (ascale)
  real(kind=default), intent(in) :: scale
  real(kind=default), intent(in), optional :: al_mz, nf, mz
  integer, intent(in), optional :: order

```

```

integer :: ord
real(kind=default) :: az, m_z, as_log, n_f, b0, b1, b2, ascale
real(kind=default) :: as0, as1
if (present(mz)) then
    m_z = mz
else
    m_z = mass_z
end if
if (present(order)) then
    ord = order
else
    ord = 0
end if
if (present(al_mz)) then
    az = al_mz
else
    az = as_mz
end if
if (present(nf)) then
    n_f = nf
else
    n_f = 5
end if
b0 = coeff_b0 (n_f)
b1 = coeff_b1 (n_f)
b2 = coeff_b2 (n_f)
as_log = one + b0 * az * log(scale**2/m_z**2)
as0 = az / as_log
as1 = as0 - as0**2 * b1/b0 * log(as_log)
select case (ord)
    case (0)
        ascale = as0
    case (1)
        ascale = as1
    case (2)
        ascale = as1 + as0**3 * (b1**2/b0**2 * ((log(as_log))**2 - &
            log(as_log) + as_log - one) - b2/b0 * (as_log - one))
end select
end function running_as

pure function running_as_lam (nf,scale,lambda_qcd,order) result (ascale)
real(kind=default), intent(in) :: nf, scale, lambda_qcd
integer, intent(in), optional :: order
real(kind=default) :: as0, as1, logmul, b0, b1, b2, ascale
integer :: ord
if (present(order)) then
    ord = order
else
    ord = 0
end if
b0 = beta0(nf)
b1 = beta1(nf)
b2 = beta2(nf)
logmul = log(scale**2/lambda_qcd**2)

```

```

as0 = four*pi / b0 / logmul
as1 = as0 * (one - two* b1 / b0**2 * log(logmul) / logmul)
select case (ord)
  case (0)
    ascale = as0
  case (1)
    ascale = as1
  case (2)
    ascale = as1 + as0 * four * b1**2/b0**4/logmul**2 * &
      ( (log(logmul) - 0.5_default)**2 + &
        b2*b0/8.0_default/b1**2 - five/four)
end select
end function running_as_lam

```

These are fundamental constants of the Catani-Seymour dipole formalism. Since the corresponding parameters for the gluon case depend on the number of flavors which is treated as an argument, there we do have functions and not parameters.

$$\gamma_q = \gamma_{\bar{q}} = \frac{3}{2}C_F \quad \gamma_g = \frac{11}{6}C_A - \frac{2}{3}T_R N_f \quad (4.11)$$

$$K_q = K_{\bar{q}} = \left(\frac{7}{2} - \frac{\pi^2}{6}\right) C_F \quad K_g = \left(\frac{67}{18} - \frac{\pi^2}{6}\right) C_A - \frac{10}{9}T_R N_f \quad (4.12)$$

```

<SM physics: public parameters>+=
  real(kind=default), parameter, public :: gamma_q = three/two * CF, &
    k_q = (7.0_default/two - pi**2/6.0_default) * CF

<SM physics: public functions>+=
  public :: gamma_g, k_g

<SM physics: subroutines>+=
  elemental function gamma_g (nf) result (gg)
    real(kind=default), intent(in) :: nf
    real(kind=default) :: gg
    gg = 11.0_default/6.0_default * CA - two/three * TR * nf
  end function gamma_g

  elemental function k_g (nf) result (kg)
    real(kind=default), intent(in) :: nf
    real(kind=default) :: kg
    kg = (67.0_default/18.0_default - pi**2/6.0_default) * CA - &
      10.0_default/9.0_default * TR * nf
  end function k_g

```

The dilogarithm. This simplified version is bound to double precision, and restricted to argument values less or equal to unity, so we do not need complex algebra. The wrapper converts it to default precision (which is, of course, a no-op if double=default).

The routine calculates the dilogarithm through mapping on the area where there is a quickly convergent series (adapted from an F77 routine by Hans Kuijf, 1988): Map x such that x is not in the neighbourhood of 1. Note that $|z| = -\ln(1-x)$ is always smaller than 1.10, but $\frac{1 \cdot 10^{19}}{19!} \text{Bernoulli}_{19} = 2.7 \times 10^{-15}$.

```

<SM physics: public functions>+=

```

```

public :: Li2
<SM physics: subroutines>+=
function Li2 (x)
    use kinds, only: double !NODEP!
    real(default), intent(in) :: x
    real(default) :: Li2
    Li2 = real( Li2_double (real(x, kind=double)), kind=default)
end function Li2

<SM physics: subroutines>+=
function Li2_double (x) result (Li2)
    use kinds, only: double !NODEP!
    real(kind=double), intent(in) :: x
    real(kind=double) :: Li2
    real(kind=double), parameter :: pi2_6 = pi**2/6
    if (abs(1-x) < 1.E-13_double) then
        Li2 = pi2_6
    else if (abs(1-x) < 0.5_double) then
        Li2 = pi2_6 - log(1-x) * log(x) - Li2_restricted (1-x)
    else if (abs(x).gt.1.d0) then
        call msg_bug (" Dilogarithm called outside of defined range.")
!       Li2 = -pi2_6 - 0.5_default * log(-x) * log(-x) - Li2_restricted (1/x)
    else
        Li2 = Li2_restricted (x)
    end if
contains
function Li2_restricted (x) result (Li2)
    real(kind=double), intent(in) :: x
    real(kind=double) :: Li2
    real(kind=double) :: tmp, z, z2
    z = - log (1-x)
    z2 = z**2
! Horner's rule for the powers z^3 through z^19
    tmp = 43867._double/798._double
    tmp = tmp * z2 /342._double - 3617._double/510._double
    tmp = tmp * z2 /272._double + 7._double/6._double
    tmp = tmp * z2 /210._double - 691._double/2730._double
    tmp = tmp * z2 /156._double + 5._double/66._double
    tmp = tmp * z2 /110._double - 1._double/30._double
    tmp = tmp * z2 / 72._double + 1._double/42._double
    tmp = tmp * z2 / 42._double - 1._double/30._double
    tmp = tmp * z2 / 20._double + 1._double/6._double
! The first three terms of the power series
    Li2 = z2 * z * tmp / 6._double - 0.25_double * z2 + z
end function Li2_restricted
end function Li2_double

<SM physics: public functions>+=
public :: faux

<SM physics: subroutines>+=
elemental function faux (x) result (y)
    real(default), intent(in) :: x

```



```

complex(default) :: y
if (1 <= x) then
  y = asin(sqrt(1/x))**2
else
  y = - 1/4.0_default * (log((1 + sqrt(1 - x))/ &
    (1 - sqrt(1 - x))) - cmplx (0.0_default, pi, kind=default))**2
end if
end function faux

```

<SM physics: public functions>+≡
 public :: fonehalf

<SM physics: subroutines>+≡
 elemental function fonehalf (x) result (y)
 real(default), intent(in) :: x
 complex(default) :: y
 if (x==0) then
 y = 0
 else
 y = - 2.0_default * x * (1 + (1 - x) * faux(x))
 end if
end function fonehalf

<SM physics: public functions>+≡
 public :: fonehalf_pseudo

<SM physics: subroutines>+≡
 function fonehalf_pseudo (x) result (y)
 real(default), intent(in) :: x
 complex(default) :: y
 if (x==0) then
 y = 0
 else
 y = - 2.0_default * x * faux(x)
 end if
end function fonehalf_pseudo

<SM physics: public functions>+≡
 public :: fone

<SM physics: subroutines>+≡
 elemental function fone (x) result (y)
 real(default), intent(in) :: x
 complex(default) :: y
 if (x==0) then
 y = 2.0_default
 else
 y = 2.0_default + 3.0_default * x + &
 3.0_default * x * (2.0_default - x) * &
 faux(x)
 end if
end function fone

```

<SM physics: public functions>+≡
  public :: gauz

<SM physics: subroutines>+≡
  elemental function gauz (x) result (y)
    real(default), intent(in) :: x
    complex(default) :: y
    if (1 <= x) then
      y = sqrt(x - 1) * asin(sqrt(1/x))
    else
      y = sqrt(1 - x) * (log((1 + sqrt(1 - x)) / &
        (1 - sqrt(1 - x))) - cmplx (0.0_default, pi, kind=default)) / 2
    end if
  end function gauz

<SM physics: public functions>+≡
  public :: tri_i1

<SM physics: subroutines>+≡
  elemental function tri_i1 (a,b) result (y)
    real(default), intent(in) :: a,b
    complex(default) :: y
    if (a < epsilon(a) .or. b < epsilon (b)) then
      y = 0
    else
      y = a*b/2.0_default/(a-b) + a**2 * b**2/2.0_default/(a-b)**2 * &
        (faux(a) - faux(b)) + &
        a**2 * b/(a-b)**2 * (gauz(a) - gauz(b))
    end if
  end function tri_i1

<SM physics: public functions>+≡
  public :: tri_i2

<SM physics: subroutines>+≡
  elemental function tri_i2 (a,b) result (y)
    real(default), intent(in) :: a,b
    complex(default) :: y
    if (a < epsilon (a) .or. b < epsilon(b)) then
      y = 0
    else
      y = - a * b / 2.0_default / (a-b) * (faux(a) - faux(b))
    end if
  end function tri_i2

```

These functions are for the running of the strong coupling constants, α_s .

```

<SM physics: public functions>+≡
  public :: run_b0

<SM physics: subroutines>+≡
  elemental function run_b0 (nf) result (bnull)
    integer, intent(in) :: nf
    real(default) :: bnull
    bnull = 33.0_default - 2.0_default * nf

```

```

end function run_b0

<SM physics: public functions>+≡
public :: run_b1

<SM physics: subroutines>+≡
elemental function run_b1 (nf) result (bone)
integer, intent(in) :: nf
real(default) :: bone
bone = 6.0_default * (153.0_default - 19.0_default * nf)/run_b0(nf)**2
end function run_b1

<SM physics: public functions>+≡
public :: run_aa

<SM physics: subroutines>+≡
elemental function run_aa (nf) result (aaa)
integer, intent(in) :: nf
real(default) :: aaa
aaa = 12.0_default * PI / run_b0(nf)
end function run_aa

<SM physics: public functions>≡
public :: run_bb

<SM physics: subroutines>+≡
elemental function run_bb (nf) result (bbb)
integer, intent(in) :: nf
real(default) :: bbb
bbb = run_b1(nf) / run_aa(nf)
end function run_bb

```

4.3.1 Functions for Catani-Seymour dipoles

For the automated Catani-Seymour dipole subtraction, we need the following functions.

```

<SM physics: public functions>+≡
public :: ff_dipole

<SM physics: subroutines>+≡
pure subroutine ff_dipole (v_ijk,y_ijk,p_ij,pp_k,p_i,p_j,p_k)
type(vector4_t), intent(in) :: p_i, p_j, p_k
type(vector4_t), intent(out) :: p_ij, pp_k
real(kind=default), intent(out) :: y_ijk
real(kind=default) :: z_i
real(kind=default), intent(out) :: v_ijk
z_i = (p_i*p_k) / ((p_k*p_j) + (p_k*p_i))
y_ijk = (p_i*p_j) / ((p_i*p_j) + (p_i*p_k) + (p_j*p_k))
p_ij = p_i + p_j - y_ijk/(1.0_default - y_ijk) * p_k
pp_k = (1.0/(1.0_default - y_ijk)) * p_k
!!! We don't multiply by alpha_s right here:
v_ijk = 8.0_default * PI * CF * &

```

```

      (2.0 / (1.0 - z_i*(1.0 - y_ijk)) - (1.0 + z_i))
end subroutine ff_dipole

```

```

⟨SM physics: public functions⟩+≡
  public :: fi_dipole

```

```

⟨SM physics: subroutines⟩+≡
  pure subroutine fi_dipole (v_ija,x_ija,p_ij,pp_a,p_i,p_j,p_a)
    type(vector4_t), intent(in) :: p_i, p_j, p_a
    type(vector4_t), intent(out) :: p_ij, pp_a
    real(kind=default), intent(out) :: x_ija
    real(kind=default) :: z_i
    real(kind=default), intent(out) :: v_ija
    z_i = (p_i*p_a) / ((p_a*p_j) + (p_a*p_i))
    x_ija = ((p_i*p_a) + (p_j*p_a) - (p_i*p_j)) &
      / ((p_i*p_a) + (p_j*p_a))
    p_ij = p_i + p_j - (1.0_default - x_ija) * p_a
    pp_a = x_ija * p_a
    !!! We don't not multiply by alpha_s right here:
    v_ija = 8.0_default * PI * CF * &
      (2.0 / (1.0 - z_i + (1.0 - x_ija)) - (1.0 + z_i)) / x_ija
  end subroutine fi_dipole

```

```

⟨SM physics: public functions⟩+≡
  public :: if_dipole

```

```

⟨SM physics: subroutines⟩+≡
  pure subroutine if_dipole (v_kja,u_j,p_aj,pp_k,p_k,p_j,p_a)
    type(vector4_t), intent(in) :: p_k, p_j, p_a
    type(vector4_t), intent(out) :: p_aj, pp_k
    real(kind=default), intent(out) :: u_j
    real(kind=default) :: x_kja
    real(kind=default), intent(out) :: v_kja
    u_j = (p_a*p_j) / ((p_a*p_j) + (p_a*p_k))
    x_kja = ((p_a*p_k) + (p_a*p_j) - (p_j*p_k)) &
      / ((p_a*p_j) + (p_a*p_k))
    p_aj = x_kja * p_a
    pp_k = p_k + p_j - (1.0_default - x_kja) * p_a
    v_kja = 8.0_default * PI * CF * &
      (2.0 / (1.0 - x_kja + u_j) - (1.0 + x_kja)) / x_kja
  end subroutine if_dipole

```

This function depends on a variable number of final state particles whose kinematics all get changed by the initial-initial dipole insertion.

```

⟨SM physics: public functions⟩+≡
  public :: ii_dipole

```

```

⟨SM physics: subroutines⟩+≡
  pure subroutine ii_dipole (v_jab,v_j,p_in,p_out,flag_1or2)
    type(vector4_t), dimension(:), intent(in) :: p_in
    type(vector4_t), dimension(size(p_in)-1), intent(out) :: p_out
    logical, intent(in) :: flag_1or2
    real(kind=default), intent(out) :: v_j
    real(kind=default), intent(out) :: v_jab

```

```

type(vector4_t) :: p_a, p_b, p_j
type(vector4_t) :: k, kk
type(vector4_t) :: p aj
real(kind=default) :: x_jab
integer :: i
!!! flag_1or2 decides whether this a 12 or 21 dipole
if (flag_1or2) then
    p_a = p_in(1)
    p_b = p_in(2)
else
    p_b = p_in(1)
    p_a = p_in(2)
end if
!!! We assume that the unresolved particle has always the last
!!! momentum
p_j = p_in(size(p_in))
x_jab = ((p_a*p_b) - (p_a*p_j) - (p_b*p_j)) / (p_a*p_b)
v_j = (p_a*p_j) / (p_a * p_b)
p_aj = x_jab * p_a
k = p_a + p_b - p_j
kk = p_aj + p_b
do i = 3, size(p_in)-1
    p_out(i) = p_in(i) - 2.0*((k+kk)*p_in(i))/((k+kk)*(k+kk)) * (k+kk) + &
        (2.0 * (k*p_in(i)) / (k*k)) * kk
end do
if (flag_1or2) then
    p_out(1) = p_aj
    p_out(2) = p_b
else
    p_out(1) = p_b
    p_out(2) = p_aj
end if
v_jab = 8.0_default * PI * CF * &
    (2.0 / (1.0 - x_jab) - (1.0 + x_jab)) / x_jab
end subroutine ii_dipole

```

4.3.2 Distributions for integrated dipoles and such

The Dirac delta distribution, modified for Monte-Carlo sampling:

```

<SM physics: public functions>+=
public :: delta

<SM physics: subroutines>+=
elemental function delta (x,eps) result (z)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: z
    if (x > 1.0_default - eps) then
        z = 1.0_default/eps
    else
        z = 0
    end if
end function delta

```

The $+$ -distribution, $P_+(x) = \left(\frac{1}{1-x}\right)_+$, for the regularization of soft-collinear singularities. The constant part for the Monte-Carlo sampling is the integral over the splitting function divided by the weight for the WHIZARD numerical integration over the interval.

```

<SM physics: public functions>+≡
  public :: plus_distr

<SM physics: subroutines>+≡
  elemental function plus_distr (x,eps) result (plusd)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: plusd
    if (x > (1.0_default - eps)) then
      plusd = log(eps)/eps
    else
      plusd = one/(one-x)
    end if
  end function plus_distr

```

The splitting function in $D = 4$ dimensions, regularized as $+$ -distributions if necessary:

$$P^{qq}(x) = P^{\bar{q}q}(x) = C_F \cdot \left(\frac{1+x^2}{1-x}\right)_+ \quad (4.13)$$

$$P^{qg}(x) = P^{\bar{q}g}(x) = C_F \cdot \frac{1+(1-x)^2}{x} \quad (4.14)$$

$$P^{gg}(x) = P^{g\bar{q}}(x) = T_R \cdot [x^2 + (1-x)^2] \quad (4.15)$$

$$P^{gg}(x) = 2C_A \left[\left(\frac{1}{1-x}\right)_+ + \frac{1-x}{x} - 1 + x(1-x) \right] + \delta(1-x) \left(\frac{11}{6}C_A - \frac{2}{3}N_f T_R \right) \quad (4.16)$$

Since the number of flavors summed over in the gluon splitting function might depend on the physics case under consideration it is implemented as an input variable.

```

<SM physics: public functions>+≡
  public :: pqg

<SM physics: subroutines>+≡
  elemental function pqg (x,eps) result (pqgx)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: pqgx
    if (x > (1.0_default - eps)) then
      pqgx = (eps-one)/two + two*log(eps)/eps - three*(eps-one)/eps/two
    else
      pqgx = (one + x**2)/(one-x)
    end if
    pqgx = CF * pqgx
  end function pqg

<SM physics: public functions>+≡
  public :: pgq

```

```

⟨SM physics: subroutines⟩+≡
  elemental function pgq (x) result (pgqx)
    real(kind=default), intent(in) :: x
    real(kind=default) :: pgqx
    pgqx = TR * (x**2 + (one - x)**2)
  end function pgq

```

```

⟨SM physics: public functions⟩+≡
  public :: pgq

```

```

⟨SM physics: subroutines⟩+≡
  elemental function pqg (x) result (pqgx)
    real(kind=default), intent(in) :: x
    real(kind=default) :: pqgx
    pqgx = CF * (one + (one - x)**2) / x
  end function pqg

```

```

⟨SM physics: public functions⟩+≡
  public :: pqg

```

```

⟨SM physics: subroutines⟩+≡
  elemental function pgg (x, nf, eps) result (pggx)
    real(kind=default), intent(in) :: x, nf, eps
    real(kind=default) :: pggx
    pggx = two * CA * ( plus_distr (x, eps) + (one-x)/x - one + &
                        x*(one-x)) + delta (x, eps) * gamma_g(nf)
  end function pgg

```

For the qq and gg cases, there exist “regularized” versions of the splitting functions:

$$P_{\text{reg}}^{qq}(x) = -C_F \cdot (1 + x) \quad (4.17)$$

$$P_{\text{reg}}^{gg}(x) = 2C_A \left[\frac{1-x}{x} - 1 + x(1-x) \right] \quad (4.18)$$

$$(4.19)$$

```

⟨SM physics: public functions⟩+≡
  public :: pqq_reg

```

```

⟨SM physics: subroutines⟩+≡
  elemental function pqq_reg (x) result (pqqregx)
    real(kind=default), intent(in) :: x
    real(kind=default) :: pqqregx
    pqqregx = - CF * (one + x)
  end function pqq_reg

```

```

⟨SM physics: public functions⟩+≡
  public :: pgg_reg

```

```

⟨SM physics: subroutines⟩+≡
  elemental function pgg_reg (x) result (pggregx)
    real(kind=default), intent(in) :: x
    real(kind=default) :: pggregx

```

```

      pggregx = two * CA * ((one - x)/x - one + x*(one - x))
end function pgg_reg

```

Here, we collect the expressions needed for integrated Catani-Seymour dipoles, and the so-called flavor kernels. We always distinguish between the “ordinary” Catani-Seymour version, and the one including a phase-space slicing parameter, α .

The standard flavor kernels \overline{K}^{ab} are:

$$\overline{K}^{qg}(x) = \overline{K}^{\bar{q}g}(x) = P^{qg}(x) \log((1-x)/x) + CF \times x \quad (4.20)$$

$$\overline{K}^{gq}(x) = \overline{K}^{g\bar{q}}(x) = P^{gq}(x) \log((1-x)/x) + TR \times 2x(1-x) \quad (4.21)$$

$$\overline{K}^{qq} = CF \left[\left(\frac{2}{1-x} \log \frac{1-x}{x} \right)_+ - (1+x) \log((1-x)/x) + (1-x) \right] - (5 - \pi^2) \cdot CF \cdot \delta(1-x) \quad (4.22)$$

$$\overline{K}^{gg} = 2CA \left[\left(\frac{1}{1-x} \log \frac{1-x}{x} \right)_+ + \left(\frac{1-x}{x} - 1 + x(1-x) \right) \log((1-x)/x) \right] - \delta(1-x) \left[(f \right. \quad (4.23)$$

```

<SM physics: public functions>+≡
public :: kbarqg

```

```

<SM physics: subroutines>+≡
function kbarqg (x) result (kbarqgx)
  real(kind=default), intent(in) :: x
  real(kind=default) :: kbarqgx
  kbarqgx = pqg(x) * log((one-x)/x) + CF * x
end function kbarqg

```

```

<SM physics: public functions>+≡
public :: kbargq

```

```

<SM physics: subroutines>+≡
function kbargq (x) result (kbargqx)
  real(kind=default), intent(in) :: x
  real(kind=default) :: kbargqx
  kbargqx = pqg(x) * log((one-x)/x) + two * TR * x * (one - x)
end function kbargq

```

```

<SM physics: public functions>+≡
public :: kbarqq

```

```

<SM physics: subroutines>+≡
function kbarqq (x,eps) result (kbarqqx)
  real(kind=default), intent(in) :: x, eps
  real(kind=default) :: kbarqqx
  kbarqqx = CF*(log_plus_distr(x,eps) - (one+x) * log((one-x)/x) + (one - &
    x) - (five - pi**2) * delta(x,eps))
end function kbarqq

```

```

<SM physics: public functions>+≡
public :: kbargg

```



```

⟨SM physics: subroutines⟩+≡
function kbargg (x,eps,nf) result (kbarggx)
  real(kind=default), intent(in) :: x, eps, nf
  real(kind=default) :: kbarggx
  kbarggx = CA * (log_plus_distr(x,eps) + two * ((one-x)/x - one + &
    x*(one-x) * log((1-x)/x))) - delta(x,eps) * &
    ((50.0_default/9.0_default - pi**2) * CA - &
    16.0_default/9.0_default * TR * nf)
end function kbargg

```

The \tilde{K} are used when two identified hadrons participate:

$$\tilde{K}^{ab}(x) = P_{\text{reg}}^{ab}(x) \cdot \log(1-x) + \delta^{ab} \mathbf{T}_a^2 \left[\left(\frac{2}{1-x} \log(1-x) \right)_+ - \frac{\pi^2}{3} \delta(1-x) \right] \quad (4.24)$$

```

⟨SM physics: public functions⟩+≡
public :: ktildeqq

⟨SM physics: subroutines⟩+≡
function ktildeqq (x,eps) result (ktildeqqx)
  real(kind=default), intent(in) :: x, eps
  real(kind=default) :: ktildeqqx
  ktildeqqx = pqq_reg (x) * log(one-x) + CF * ( - log2_plus_distr (x,eps) &
    - pi**2/three * delta(x,eps))
end function ktildeqq

```

```

⟨SM physics: public functions⟩+≡
public :: ktildeqg

⟨SM physics: subroutines⟩+≡
function ktildeqg (x,eps) result (ktildeqgx)
  real(kind=default), intent(in) :: x, eps
  real(kind=default) :: ktildeqgx
  ktildeqgx = pqg (x) * log(one-x)
end function ktildeqg

```

```

⟨SM physics: public functions⟩+≡
public :: ktildegq

⟨SM physics: subroutines⟩+≡
function ktildegq (x,eps) result (ktildegqx)
  real(kind=default), intent(in) :: x, eps
  real(kind=default) :: ktildegqx
  ktildegqx = pgq (x) * log(one-x)
end function ktildegq

```

```

⟨SM physics: public functions⟩+≡
public :: ktildegg

⟨SM physics: subroutines⟩+≡
function ktildegg (x,eps) result (ktildeggx)
  real(kind=default), intent(in) :: x, eps
  real(kind=default) :: ktildeggx
  ktildeggx = pgg_reg (x) * log(one-x) + CA * ( - &

```

```

      log2_plus_distr (x,eps) - pi**2/three * delta(x,eps))
end function ktildegg

```

The insertion operator might not be necessary for a GOLEM interface but is demanded by the Les Houches NLO accord. It is a three-dimensional array, where the index always gives the inverse power of the DREG expansion parameter, ϵ .

```

⟨SM physics: public functions⟩+=
  public :: insert_q

```

```

⟨SM physics: subroutines⟩+=
  pure function insert_q ()
    real(kind=default), dimension(0:2) :: insert_q
    insert_q(0) = gamma_q + k_q - pi**2/three * CF
    insert_q(1) = gamma_q
    insert_q(2) = CF
  end function insert_q

```

```

⟨SM physics: public functions⟩+=
  public :: insert_g

```

```

⟨SM physics: subroutines⟩+=
  pure function insert_g (nf)
    real(kind=default), intent(in) :: nf
    real(kind=default), dimension(0:2) :: insert_g
    insert_g(0) = gamma_g (nf) + k_g (nf) - pi**2/three * CA
    insert_g(1) = gamma_g (nf)
    insert_g(2) = CA
  end function insert_g

```

For better convergence, one can exclude regions of phase space with a slicing parameter from the dipole subtraction procedure. First of all, the K functions get modified:

$$K_i(\alpha) = K_i - \mathbf{T}_i^2 \log^2 \alpha + \gamma_i(\alpha - 1 - \log \alpha) \quad (4.25)$$

```

⟨SM physics: public functions⟩+=
  public :: k_q_al, k_g_al

```

```

⟨SM physics: subroutines⟩+=
  pure function k_q_al (alpha)
    real(kind=default), intent(in) :: alpha
    real(kind=default) :: k_q_al
    k_q_al = k_q - CF * (log(alpha))**2 + gamma_q * &
      (alpha - one - log(alpha))
  end function k_q_al

  pure function k_g_al (alpha, nf)
    real(kind=default), intent(in) :: alpha, nf
    real(kind=default) :: k_g_al
    k_g_al = k_g (nf) - CA * (log(alpha))**2 + gamma_g (nf) * &
      (alpha - one - log(alpha))
  end function k_g_al

```

The +-distribution, but with a phase-space slicing parameter, α , $P_{1-\alpha}(x) = \left(\frac{1}{1-x}\right)_{1-x}$. Since we need the fatal error message here, this function cannot be elemental.

```
<SM physics: public functions>+≡
  public :: plus_distr_al
```

```
<SM physics: subroutines>+≡
  function plus_distr_al (x,alpha,eps) result (plusd_al)
    real(kind=default), intent(in) :: x, eps, alpha
    real(kind=default) :: plusd_al
    if ((1.0_default - alpha) .ge. (1.0_default - eps)) then
      call msg_fatal ('sm_physics, plus_distr_al: alpha and epsilon chosen wrongly')
    elseif (x < (1.0_default - alpha)) then
      plusd_al = 0
    else if (x > (1.0_default - eps)) then
      plusd_al = log(eps/alpha)/eps
    else
      plusd_al = one/(one-x)
    end if
  end function plus_distr_al
```

Introducing phase-space slicing parameters, these flavor kernels become: The standard flavor kernels \bar{K}^{ab} are:

$$\bar{K}_\alpha^{qq}(x) = \bar{K}_\alpha^{\bar{q}q}(x) = P^{qq}(x) \log(\alpha(1-x)/x) + CF \times x \quad (4.26)$$

$$\bar{K}_\alpha^{gq}(x) = \bar{K}_\alpha^{g\bar{q}}(x) = P^{gq}(x) \log(\alpha(1-x)/x) + TR \times 2x(1-x) \quad (4.27)$$

$$\bar{K}_\alpha^{qq} = C_F(1-x) + P_{\text{reg}}^{qq}(x) \log \frac{\alpha(1-x)}{x} + C_F \delta(1-x) \log^2 \alpha + C_F \left(\frac{2}{1-x} \log \frac{1-x}{x} \right)_+ - \left(\gamma_q - \right) \quad (4.28)$$

```
<SM physics: public functions>+≡
  public :: kbarqg_al
```

```
<SM physics: subroutines>+≡
  function kbarqg_al (x,alpha,eps) result (kbarqgx)
    real(kind=default), intent(in) :: x, alpha, eps
    real(kind=default) :: kbarqgx
    kbarqgx = pqg (x) * log(alpha*(one-x)/x) + CF * x
  end function kbarqg_al
```

```
<SM physics: public functions>+≡
  public :: kbargq_al
```

```
<SM physics: subroutines>+≡
  function kbargq_al (x,alpha,eps) result (kbargqx)
    real(kind=default), intent(in) :: x, alpha, eps
    real(kind=default) :: kbargqx
    kbargqx = pgq (x) * log(alpha*(one-x)/x) + two * TR * x * (one-x)
  end function kbargq_al
```

```
<SM physics: public functions>+≡
  public :: kbarqq_al
```

```

⟨SM physics: subroutines⟩+=≡
function kbarqq_al (x,alpha,eps) result (kbarqqx)
  real(kind=default), intent(in) :: x, alpha, eps
  real(kind=default) :: kbarqqx
  kbarqqx = CF * (one - x) + pqq_reg(x) * log(alpha*(one-x)/x) &
    + CF * log_plus_distr(x,eps) &
    - (gamma_q + k_q_al(alpha) - CF * &
      five/6.0_default * pi**2 - CF * (log(alpha))**2) * &
      delta(x,eps) + &
      CF * two/(one -x)*log(alpha*(two-x)/(one+alpha-x))
  if (x < (one-alpha)) then
    kbarqqx = kbarqqx - CF * two/(one-x) * log((two-x)/(one-x))
  end if
end function kbarqq_al

```

```

⟨SM physics: public functions⟩+=≡
public :: kbargg_al

```

```

⟨SM physics: subroutines⟩+=≡
function kbargg_al (x,alpha,eps,nf) result (kbarggx)
  real(kind=default), intent(in) :: x, alpha, eps, nf
  real(kind=default) :: kbarggx
  kbarggx = pgg_reg(x) * log(alpha*(one-x)/x) &
    + CA * log_plus_distr(x,eps) &
    - (gamma_g(nf) + k_g_al(alpha,nf) - CA * &
      five/6.0_default * pi**2 - CA * (log(alpha))**2) * &
      delta(x,eps) + &
      CA * two/(one -x)*log(alpha*(two-x)/(one+alpha-x))
  if (x < (one-alpha)) then
    kbarggx = kbarggx - CA * two/(one-x) * log((two-x)/(one-x))
  end if
end function kbargg_al

```

The \tilde{K} flavor kernels in the presence of a phase-space slicing parameter, are:

$$\tilde{K}^{ab}(x, \alpha) = P^{qq, \text{reg}}(x) \log \frac{1-x}{\alpha} + \dots \quad (4.29)$$

```

⟨SM physics: public functions⟩+=≡
public :: ktildeqq_al

```

```

⟨SM physics: subroutines⟩+=≡
function ktildeqq_al (x,alpha,eps) result (ktildeqqx)
  real(kind=default), intent(in) :: x, eps, alpha
  real(kind=default) :: ktildeqqx
  ktildeqqx = pqq_reg(x) * log((one-x)/alpha) + CF*( &
    - log2_plus_distr_al(x,alpha,eps) - Pi**2/three * delta(x,eps) &
    + (one+x**2)/(one-x) * log(min(one,(alpha/(one-x)))) &
    + two/(one-x) * log((one+alpha-x)/alpha))
  if (x > (one-alpha)) then
    ktildeqqx = ktildeqqx - CF*two/(one-x)*log(two-x)
  end if
end function ktildeqq_al

```

This is a logarithmic +-distribution, $\left(\frac{\log((1-x)/x)}{1-x}\right)_+$. For the sampling, we need the integral over this function over the incomplete sampling interval $[0, 1 - \epsilon]$, which is $\log^2(x) + 2Li_2(x) - \frac{\pi^2}{3}$. As this function is negative definite for $\epsilon > 0.1816$, we take a hard upper limit for that sampling parameter, irrespective of the fact what the user chooses.

```
<SM physics: public functions>+≡
  public :: log_plus_distr
```

```
<SM physics: subroutines>+≡
  function log_plus_distr (x,eps) result (lpd)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: lpd, eps2
    eps2 = min (eps, 0.1816_default)
    if (x > (1.0_default - eps2)) then
      lpd = ((log(eps2))**2 + two*Li2(eps2) - pi**2/three)/eps2
    else
      lpd = two*log((one-x)/x)/(one-x)
    end if
  end function log_plus_distr
```

Logarithmic +-distribution, $2 \left(\frac{\log(1/(1-x))}{1-x}\right)_+$.

```
<SM physics: public functions>+≡
  public :: log2_plus_distr
```

```
<SM physics: subroutines>+≡
  function log2_plus_distr (x,eps) result (lpd)
    real(kind=default), intent(in) :: x, eps
    real(kind=default) :: lpd
    if (x > (1.0_default - eps)) then
      lpd = - (log(eps))**2/eps
    else
      lpd = two*log(one/(one-x))/(one-x)
    end if
  end function log2_plus_distr
```

Logarithmic +-distribution with phase-space slicing parameter, $2 \left(\frac{\log(1/(1-x))}{1-x}\right)_{1-\alpha}$.

```
<SM physics: public functions>+≡
  public :: log2_plus_distr_al
```

```
<SM physics: subroutines>+≡
  function log2_plus_distr_al (x,alpha,eps) result (lpd_al)
    real(kind=default), intent(in) :: x, eps, alpha
    real(kind=default) :: lpd_al
    if ((1.0_default - alpha) .ge. (1.0_default - eps)) then
      call msg_fatal ('alpha and epsilon chosen wrongly')
    elseif (x < (one - alpha)) then
      lpd_al = 0
    elseif (x > (1.0_default - eps)) then
      lpd_al = - ((log(eps))**2 - (log(alpha))**2)/eps
    else
      lpd_al = two*log(one/(one-x))/(one-x)
    end if
```

```
end function log2_plus_distr_al
```

Chapter 5

Physics Analysis

This part contains the structures and tools that are necessary for defining parameters, particle sets, analysis objects such as histograms, and expressions that deal with them.

These are the modules:

analysis Observables, histograms, and plots.

pdg_arrays Useful for particle aliases (e.g., 'quark' for u, d, s etc.)

prt_lists Particle lists/arrays used for analyzing events.

variables Store values of various kind, used by expressions and accessed by the command interface.

expressions Expressions of values of all kinds. Includes the API for recording analysis data.

5.1 Analysis tools

This module defines structures useful for data analysis. These include observables, histograms, and plots.

Observables are quantities that are calculated and summed up event by event. At the end, one can compute the average and error.

Histograms have their bins in addition to the observable properties. Histograms are usually written out in tables and displayed graphically.

In plots, each record creates its own entry in a table. This can be used for scatter plots if called event by event, or for plotting dependencies on parameters if called once per integration run.

Graphs are container for histograms and plots, which carry their own graphics options.

The type layout is still somewhat obfuscated. This would become much simpler if type extension could be used.

```
<analysis.f90>≡  
  <File header>  
  
  module analysis  
  
    <Use kinds>  
    <Use strings>  
    use limits, only: HISTOGRAM_HEAD_FORMAT, HISTOGRAM_DATA_FORMAT !NODEP!  
    use limits, only: HISTOGRAM_INTG_FORMAT !NODEP!  
    <Use file utils>  
    use diagnostics !NODEP!  
    use os_interface  
    use ifiles  
  
    <Standard module head>  
  
    <Analysis: public>  
  
    <Analysis: parameters>  
  
    <Analysis: types>  
  
    <Analysis: interfaces>  
  
    <Analysis: variables>  
  
    contains  
  
    <Analysis: procedures>  
  
  end module analysis
```

5.1.1 Output formats

These formats share a common field width (alignment).

```
<Limits: public parameters>+≡  
  character(*), parameter, public :: HISTOGRAM_HEAD_FORMAT = "1x,A13,1x"
```



```

character(*), parameter, public :: HISTOGRAM_INTG_FORMAT = "3x,I9,3x"
character(*), parameter, public :: HISTOGRAM_DATA_FORMAT = "1PG15.8"

```

5.1.2 Graph options

These parameters are used for displaying data. They apply to a whole graph, which may contain more than one plot element.

The GAMELAN code chunks are part of both `graph_options` and `drawing_options`. The `drawing_options` copy is used in histograms and plots, also as graph elements. The `graph_options` copy is used for `graph` objects as a whole. Both copies are usually identical.

```

<Analysis: public>≡
    public :: graph_options_t

<Analysis: types>≡
    type :: graph_options_t
        private
        type(string_t) :: id
        type(string_t) :: title
        type(string_t) :: description
        type(string_t) :: x_label
        type(string_t) :: y_label
        integer :: width_mm = 130
        integer :: height_mm = 90
        logical :: x_log = .false.
        logical :: y_log = .false.
        real(default) :: x_min = 0
        real(default) :: x_max = 1
        real(default) :: y_min = 0
        real(default) :: y_max = 1
        logical :: x_min_set = .false.
        logical :: x_max_set = .false.
        logical :: y_min_set = .false.
        logical :: y_max_set = .false.
        type(string_t) :: gmlcode_bg
        type(string_t) :: gmlcode_fg
    end type graph_options_t

```

Initialize the record, all strings are empty. The limits are undefined.

```

<Analysis: public>+≡
    public :: graph_options_init

<Analysis: procedures>≡
    subroutine graph_options_init (graph_options)
        type(graph_options_t), intent(out) :: graph_options
        graph_options%id = ""
        graph_options%title = ""
        graph_options%description = ""
        graph_options%x_label = ""
        graph_options%y_label = ""
        graph_options%gmlcode_bg = ""
        graph_options%gmlcode_fg = ""
    end subroutine graph_options_init

```

```
end subroutine graph_options_init
```

Set individual options.

<Analysis: public>+≡

```
public :: graph_options_set
```

<Analysis: procedures>+≡

```
subroutine graph_options_set (graph_options, id, &
    title, description, x_label, y_label, width_mm, height_mm, &
    x_log, y_log, x_min, x_max, y_min, y_max, &
    gmlcode_bg, gmlcode_fg)
    type(graph_options_t), intent(inout) :: graph_options
    type(string_t), intent(in), optional :: id
    type(string_t), intent(in), optional :: title
    type(string_t), intent(in), optional :: description
    type(string_t), intent(in), optional :: x_label, y_label
    integer, intent(in), optional :: width_mm, height_mm
    logical, intent(in), optional :: x_log, y_log
    real(default), intent(in), optional :: x_min, x_max, y_min, y_max
    type(string_t), intent(in), optional :: gmlcode_bg, gmlcode_fg
    if (present (id)) graph_options%id = id
    if (present (title)) graph_options%title = title
    if (present (description)) graph_options%description = description
    if (present (x_label)) graph_options%x_label = x_label
    if (present (y_label)) graph_options%y_label = y_label
    if (present (width_mm)) graph_options%width_mm = width_mm
    if (present (height_mm)) graph_options%height_mm = height_mm
    if (present (x_log)) graph_options%x_log = x_log
    if (present (y_log)) graph_options%y_log = y_log
    if (present (x_min)) graph_options%x_min = x_min
    if (present (x_max)) graph_options%x_max = x_max
    if (present (y_min)) graph_options%y_min = y_min
    if (present (y_max)) graph_options%y_max = y_max
    if (present (x_min)) graph_options%x_min_set = .true.
    if (present (x_max)) graph_options%x_max_set = .true.
    if (present (y_min)) graph_options%y_min_set = .true.
    if (present (y_max)) graph_options%y_max_set = .true.
    if (present (gmlcode_bg)) graph_options%gmlcode_bg = gmlcode_bg
    if (present (gmlcode_fg)) graph_options%gmlcode_fg = gmlcode_fg
end subroutine graph_options_set
```

Write a L^AT_EX header/footer for the analysis file.

<Analysis: procedures>+≡

```
subroutine graph_options_write_tex_header (gro, unit)
    type(graph_options_t), intent(in) :: gro
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit)
    if (gro%title /= "") then
        write (u, "(A)")
        write (u, "(A)") "\section{" // char (gro%title) // "}"
    else
        write (u, "(A)") "\section{" // char (quote_underscore (gro%id)) // "}"
    end if
end subroutine graph_options_write_tex_header
```

```

end if
if (gro%description /= "") then
  write (u, "(A)") char (gro%description)
  write (u, *)
  write (u, "(A)") "\vspace*{\baselineskip}"
end if
write (u, "(A)") "\vspace*{\baselineskip}"
write (u, "(A)") "\unitlength 1mm"
write (u, "(A,I0,',',I0,A)") &
  "\begin{gmlgraph*}(", &
  gro%width_mm, gro%height_mm, &
  ")[dat]"
end subroutine graph_options_write_tex_header

subroutine graph_options_write_tex_footer (gro, unit)
  type(graph_options_t), intent(in) :: gro
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit)
  write (u, "(A)") "\end{gmlgraph*}"
end subroutine graph_options_write_tex_footer

```

Return the analysis object ID.

```

<Analysis: procedures>+≡
function graph_options_get_id (gro) result (id)
  type(string_t) :: id
  type(graph_options_t), intent(in) :: gro
  id = gro%id
end function graph_options_get_id

```

Create an appropriate setup command (linear/log).

```

<Analysis: procedures>+≡
function graph_options_get_gml_setup (gro) result (cmd)
  type(string_t) :: cmd
  type(graph_options_t), intent(in) :: gro
  type(string_t) :: x_str, y_str
  if (gro%x_log) then
    x_str = "log"
  else
    x_str = "linear"
  end if
  if (gro%y_log) then
    y_str = "log"
  else
    y_str = "linear"
  end if
  cmd = "setup (" // x_str // ", " // y_str // ");"
end function graph_options_get_gml_setup

```

Return the labels in GAMELAN form.

```

<Analysis: procedures>+≡
function graph_options_get_gml_x_label (gro) result (cmd)

```

```

type(string_t) :: cmd
type(graph_options_t), intent(in) :: gro
cmd = 'label.bot (< ' // '<' // gro%x_label // '>' // '>', out);'
end function graph_options_get_gml_x_label

function graph_options_get_gml_y_label (gro) result (cmd)
type(string_t) :: cmd
type(graph_options_t), intent(in) :: gro
cmd = 'label.ulft (< ' // '<' // gro%y_label // '>' // '>', out);'
end function graph_options_get_gml_y_label

```

Create an appropriate **graphrange** statement for the given graph options. Where the graph options are not set, use the supplied arguments, if any, otherwise set the undefined value.

(Analysis: procedures)+≡

```

function graph_options_get_gml_graphrange &
(gro, x_min, x_max, y_min, y_max) result (cmd)
type(string_t) :: cmd
type(graph_options_t), intent(in) :: gro
real(default), intent(in), optional :: x_min, x_max, y_min, y_max
type(string_t) :: x_min_str, x_max_str, y_min_str, y_max_str
if (gro%x_min_set) then
x_min_str = "#" // real2string (gro%x_min)
else if (present (x_min)) then
x_min_str = "#" // real2string (x_min)
else
x_min_str = "???"
end if
if (gro%x_max_set) then
x_max_str = "#" // real2string (gro%x_max)
else if (present (x_max)) then
x_max_str = "#" // real2string (x_max)
else
x_max_str = "???"
end if
if (gro%y_min_set) then
y_min_str = "#" // real2string (gro%y_min)
else if (present (y_min)) then
y_min_str = "#" // real2string (y_min)
else
y_min_str = "???"
end if
if (gro%y_max_set) then
y_max_str = "#" // real2string (gro%y_max)
else if (present (y_max)) then
y_max_str = "#" // real2string (y_max)
else
y_max_str = "???"
end if
cmd = "graphrange (" // x_min_str // ", " // y_min_str // " ), " &
// "(" // x_max_str // ", " // y_max_str // " );"
end function graph_options_get_gml_graphrange

```

Get extra GAMELAN code to be executed before and after the usual drawing commands.

```

<Analysis: procedures>+=
function graph_options_get_gml_bg_command (gro) result (cmd)
  type(string_t) :: cmd
  type(graph_options_t), intent(in) :: gro
  cmd = gro%gmlcode_bg
end function graph_options_get_gml_bg_command

function graph_options_get_gml_fg_command (gro) result (cmd)
  type(string_t) :: cmd
  type(graph_options_t), intent(in) :: gro
  cmd = gro%gmlcode_fg
end function graph_options_get_gml_fg_command

```

Append the header for generic data output in ifile format. We print only labels, not graphics parameters.

```

<Analysis: procedures>+=
subroutine graph_options_get_header (pl, header, comment)
  type(graph_options_t), intent(in) :: pl
  type(ifile_t), intent(inout) :: header
  type(string_t), intent(in), optional :: comment
  type(string_t) :: c
  if (present (comment)) then
    c = comment
  else
    c = ""
  end if
  call ifile_append (header, &
    c // "ID: " // pl%id)
  call ifile_append (header, &
    c // "title: " // pl%title)
  call ifile_append (header, &
    c // "description: " // pl%description)
  call ifile_append (header, &
    c // "x axis label: " // pl%x_label)
  call ifile_append (header, &
    c // "y axis label: " // pl%y_label)
end subroutine graph_options_get_header

```

5.1.3 Drawing options

These options apply to an individual graph element (histogram or plot).

```

<Analysis: public>+=
public :: drawing_options_t

<Analysis: types>+=
type :: drawing_options_t
  type(string_t) :: dataset
  logical :: with_hbars = .false.
  logical :: with_base = .false.
  logical :: piecewise = .false.

```

```

        logical :: fill = .false.
        logical :: draw = .false.
        logical :: err = .false.
        logical :: symbols = .false.
        type(string_t) :: fill_options
        type(string_t) :: draw_options
        type(string_t) :: err_options
        type(string_t) :: symbol
        type(string_t) :: gmlcode_bg
        type(string_t) :: gmlcode_fg
    end type drawing_options_t

```

Init with empty strings and default options, appropriate for either histogram or plot.

<Analysis: public>+≡

```

    public :: drawing_options_init_histogram
    public :: drawing_options_init_plot

```

<Analysis: procedures>+≡

```

    subroutine drawing_options_init_histogram (dro)
        type(drawing_options_t), intent(out) :: dro
        dro%dataset = "dat"
        dro%with_hbars = .true.
        dro%with_base = .true.
        dro%piecewise = .true.
        dro%fill = .true.
        dro%draw = .true.
        dro%fill_options = "withcolor col.default"
        dro%draw_options = ""
        dro%err_options = ""
        dro%symbol = "fshape(circle scaled 1mm())"
        dro%gmlcode_bg = ""
        dro%gmlcode_fg = ""
    end subroutine drawing_options_init_histogram

    subroutine drawing_options_init_plot (dro)
        type(drawing_options_t), intent(out) :: dro
        dro%dataset = "dat"
        dro%draw = .true.
        dro%fill_options = "withcolor col.default"
        dro%draw_options = ""
        dro%err_options = ""
        dro%symbol = "fshape(circle scaled 1mm())"
        dro%gmlcode_bg = ""
        dro%gmlcode_fg = ""
    end subroutine drawing_options_init_plot

```

Set individual options.

<Analysis: public>+≡

```

    public :: drawing_options_set

```

<Analysis: procedures>+≡

```

    subroutine drawing_options_set (dro, dataset, &
        with_hbars, with_base, piecewise, fill, draw, err, symbols, &

```

```

        fill_options, draw_options, err_options, symbol, &
        gmlcode_bg, gmlcode_fg)
type(drawing_options_t), intent(inout) :: dro
type(string_t), intent(in), optional :: dataset
logical, intent(in), optional :: with_hbars, with_base, piecewise
logical, intent(in), optional :: fill, draw, err, symbols
type(string_t), intent(in), optional :: fill_options, draw_options
type(string_t), intent(in), optional :: err_options, symbol
type(string_t), intent(in), optional :: gmlcode_bg, gmlcode_fg
if (present (dataset)) dro%dataset = dataset
if (present (with_hbars)) dro%with_hbars = with_hbars
if (present (with_base)) dro%with_base = with_base
if (present (piecewise)) dro%piecewise = piecewise
if (present (fill)) dro%fill = fill
if (present (draw)) dro%draw = draw
if (present (err)) dro%err = err
if (present (symbols)) dro%symbols = symbols
if (present (fill_options)) dro%fill_options = fill_options
if (present (draw_options)) dro%draw_options = draw_options
if (present (err_options)) dro%err_options = err_options
if (present (symbol)) dro%symbol = symbol
if (present (gmlcode_bg)) dro%gmlcode_bg = gmlcode_bg
if (present (gmlcode_fg)) dro%gmlcode_fg = gmlcode_fg
end subroutine drawing_options_set

```

There are separate commands for drawing the curve and for drawing errors. The symbols are applied to the latter. First of all, we may have to compute a baseline:

```

<Analysis: procedures>+≡
function drawing_options_get_calc_command (dro) result (cmd)
    type(string_t) :: cmd
    type(drawing_options_t), intent(in) :: dro
    if (dro%with_base) then
        cmd = "calculate " // dro%dataset // ".base (" // dro%dataset // ") " &
            // "(x, #0);"
    else
        cmd = ""
    end if
end function drawing_options_get_calc_command

```

Return the drawing command.

```

<Analysis: procedures>+≡
function drawing_options_get_draw_command (dro) result (cmd)
    type(string_t) :: cmd
    type(drawing_options_t), intent(in) :: dro
    if (dro%fill) then
        cmd = "fill"
    else if (dro%draw) then
        cmd = "draw"
    else
        cmd = ""
    end if
    if (dro%fill .or. dro%draw) then

```

```

if (dro%piecewise) cmd = cmd // " piecewise"
if (dro%draw .and. dro%with_base) cmd = cmd // " cyclic"
cmd = cmd // " from (" // dro%dataset
if (dro%with_base) then
  if (dro%piecewise) then
    cmd = cmd // ", " // dro%dataset // ".base\" ! "
  else
    cmd = cmd // " ~ " // dro%dataset // ".base\" ! "
  end if
end if
cmd = cmd // ")"
if (dro%fill) then
  cmd = cmd // " " // dro%fill_options
  if (dro%draw) cmd = cmd // " outlined"
end if
if (dro%draw) cmd = cmd // " " // dro%draw_options
cmd = cmd // ";"
end if
end function drawing_options_get_draw_command

```

The error command draws error bars, if any.

<Analysis: procedures>+≡

```

function drawing_options_get_err_command (dro) result (cmd)
  type(string_t) :: cmd
  type(drawing_options_t), intent(in) :: dro
  if (dro%err) then
    cmd = "draw piecewise " &
      // "from (" // dro%dataset // ".err)" &
      // " " // dro%err_options // ";"
  else
    cmd = ""
  end if
end function drawing_options_get_err_command

```

The symbol command draws symbols, if any.

<Analysis: procedures>+≡

```

function drawing_options_get_symb_command (dro) result (cmd)
  type(string_t) :: cmd
  type(drawing_options_t), intent(in) :: dro
  if (dro%symbols) then
    cmd = "phantom" &
      // " from (" // dro%dataset // ")" &
      // " withsymbol (" // dro%symbol // ");"
  else
    cmd = ""
  end if
end function drawing_options_get_symb_command

```

Get extra GAMELAN code to be executed before and after the usual drawing commands.

<Analysis: procedures>+≡

```

function drawing_options_get_gml_bg_command (dro) result (cmd)

```



```

    type(string_t) :: cmd
    type(drawing_options_t), intent(in) :: dro
    cmd = dro%gmlcode_bg
end function drawing_options_get_gml_bg_command

function drawing_options_get_gml_fg_command (dro) result (cmd)
    type(string_t) :: cmd
    type(drawing_options_t), intent(in) :: dro
    cmd = dro%gmlcode_fg
end function drawing_options_get_gml_fg_command

```

5.1.4 Observables

The observable type holds the accumulated observable values and weight sums which are necessary for proper averaging.

(Analysis: types)+≡

```

type :: observable_t
    private
    real(default) :: sum_values = 0
    real(default) :: sum_squared_values = 0
    real(default) :: sum_weights = 0
    real(default) :: sum_squared_weights = 0
    integer :: count = 0
    type(string_t) :: obs_label
    type(string_t) :: obs_unit
    type(graph_options_t) :: graph_options
end type observable_t

```

Initialize with defined properties

(Analysis: procedures)+≡

```

subroutine observable_init (obs, obs_label, obs_unit, graph_options)
    type(observable_t), intent(out) :: obs
    type(string_t), intent(in), optional :: obs_label, obs_unit
    type(graph_options_t), intent(in), optional :: graph_options
    if (present (obs_label)) then
        obs%obs_label = obs_label
    else
        obs%obs_label = ""
    end if
    if (present (obs_unit)) then
        obs%obs_unit = obs_unit
    else
        obs%obs_unit = ""
    end if
    if (present (graph_options)) then
        obs%graph_options = graph_options
    else
        call graph_options_init (obs%graph_options)
    end if
end subroutine observable_init

```

Reset all numeric entries.

```

<Analysis: procedures>+≡
subroutine observable_clear (obs)
  type(observable_t), intent(inout) :: obs
  obs%sum_values = 0
  obs%sum_squared_values = 0
  obs%sum_weights = 0
  obs%sum_squared_weights = 0
  obs%count = 0
end subroutine observable_clear

```

Record a a value. Always successful for observables.

```

<Analysis: interfaces>≡
interface observable_record_value
  module procedure observable_record_value_unweighted
  module procedure observable_record_value_weighted
end interface

```

```

<Analysis: procedures>+≡
subroutine observable_record_value_unweighted (obs, value, success)
  type(observable_t), intent(inout) :: obs
  real(default), intent(in) :: value
  logical, intent(out), optional :: success
  obs%sum_values = obs%sum_values + value
  obs%sum_squared_values = obs%sum_squared_values + value**2
  obs%sum_weights = obs%sum_weights + 1
  obs%sum_squared_weights = obs%sum_squared_weights + 1
  obs%count = obs%count + 1
  if (present (success)) success = .true.
end subroutine observable_record_value_unweighted

subroutine observable_record_value_weighted (obs, value, weight, success)
  type(observable_t), intent(inout) :: obs
  real(default), intent(in) :: value, weight
  logical, intent(out), optional :: success
  obs%sum_values = obs%sum_values + value * weight
  obs%sum_squared_values = obs%sum_squared_values + value**2 * weight
  obs%sum_weights = obs%sum_weights + abs (weight)
  obs%sum_squared_weights = obs%sum_squared_weights + weight**2
  obs%count = obs%count + 1
  if (present (success)) success = .true.
end subroutine observable_record_value_weighted

```

Here are the statistics formulas:

1. Unweighted case: Given a sample of n values x_i , the average is

$$\langle x \rangle = \frac{\sum x_i}{n} \quad (5.1)$$

and the error estimate

$$\Delta x = \sqrt{\frac{1}{n-1} \langle \sum (x_i - \langle x \rangle)^2 \rangle} \quad (5.2)$$

$$= \sqrt{\frac{1}{n-1} \left(\frac{\sum x_i^2}{n} - \frac{(\sum x_i)^2}{n^2} \right)} \quad (5.3)$$

2. Weighted case: Instead of weight 1, each event comes with weight w_i .

$$\langle x \rangle = \frac{\sum x_i w_i}{\sum w_i} \quad (5.4)$$

and

$$\Delta x = \sqrt{\frac{1}{n-1} \left(\frac{\sum x_i^2 w_i}{\sum w_i} - \frac{(\sum x_i w_i)^2}{(\sum w_i)^2} \right)} \quad (5.5)$$

For $w_i = 1$, this specializes to the previous formula.

<Analysis: procedures>+≡

```
function observable_get_n_entries (obs) result (n)
  integer :: n
  type(observable_t), intent(in) :: obs
  n = obs%count
end function observable_get_n_entries

function observable_get_average (obs) result (avg)
  real(default) :: avg
  type(observable_t), intent(in) :: obs
  if (obs%sum_weights /= 0) then
    avg = obs%sum_values / obs%sum_weights
  else
    avg = 0
  end if
end function observable_get_average

function observable_get_error (obs) result (err)
  real(default) :: err
  type(observable_t), intent(in) :: obs
  real(default) :: var, n
  if (obs%sum_weights /= 0) then
    select case (obs%count)
    case (0:1)
      err = 0
    case default
      n = obs%count
      var = obs%sum_squared_values / obs%sum_weights &
        - (obs%sum_values / obs%sum_weights) ** 2
      err = sqrt (max (var, 0._default) / (n - 1))
    end select
  else
    err = 0
  end if
end function observable_get_error
```

Write label and/or physical unit to a string.

<Analysis: procedures>+≡

```
function observable_get_label (obs, wl, wu) result (string)
  type(string_t) :: string
  type(observable_t), intent(in) :: obs
  logical, intent(in) :: wl, wu
  type(string_t) :: obs_label, obs_unit
  if (wl) then
    if (obs%obs_label /= "") then
      obs_label = obs%obs_label
    else
      obs_label = "\textrm{Observable}"
    end if
  else
    obs_label = ""
  end if
  if (wu) then
    if (obs%obs_unit /= "") then
      if (wl) then
        obs_unit = "\;[" // obs%obs_unit // "]"
      else
        obs_unit = obs%obs_unit
      end if
    else
      obs_unit = ""
    end if
  else
    obs_unit = ""
  end if
  string = obs_label // obs_unit
end function observable_get_label
```

5.1.5 Output

<Analysis: procedures>+≡

```
subroutine observable_write (obs, unit)
  type(observable_t), intent(in) :: obs
  integer, intent(in), optional :: unit
  real(default) :: avg, err, relerr
  integer :: n
  integer :: u
  u = output_unit (unit); if (u < 0) return
  avg = observable_get_average (obs)
  err = observable_get_error (obs)
  if (avg /= 0) then
    relerr = err / avg
  else
    relerr = 0
  end if
  n = observable_get_n_entries (obs)
  write (u, "(A,1x," // HISTOGRAM_DATA_FORMAT // ")") &
    "average      =", avg
```

```

write (u, "(A,1x," // HISTOGRAM_DATA_FORMAT // ")") &
"error[abs] =", err
write (u, "(A,1x," // HISTOGRAM_DATA_FORMAT // ")") &
"error[rel] =", relerr
write (u, "(A,1x," // HISTOGRAM_INTG_FORMAT // ")") &
"n_entries   =", n
end subroutine observable_write

```

L^AT_EX output.

<Analysis: procedures>+≡

```

subroutine observable_write_driver (obs, unit, write_heading)
  type(observable_t), intent(in) :: obs
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: write_heading
  real(default) :: avg, err
  integer :: n_digits
  logical :: heading
  integer :: u
  u = output_unit (unit); if (u < 0) return
  heading = .true.; if (present (write_heading)) heading = write_heading
  avg = observable_get_average (obs)
  err = observable_get_error (obs)
  if (avg /= 0 .and. err /= 0) then
    n_digits = max (2, 2 - int (log10 (abs (err / real (avg, default)))))
  else if (avg /= 0) then
    n_digits = 100
  else
    n_digits = 1
  end if
  if (heading) then
    write (u, "(A)")
    if (obs%graph_options%title /= "") then
      write (u, "(A)") "\section{" // char (obs%graph_options%title) &
// "}"
    else
      write (u, "(A)") "\section{Observable}"
    end if
    if (obs%graph_options%description /= "") then
      write (u, "(A)") char (obs%graph_options%description)
      write (u, *)
    end if
    write (u, "(A)") "\begin{flushleft}"
  end if
  write (u, "(A)", advance="no") " $\langle$ " ! $ sign
  write (u, "(A)", advance="no") char (observable_get_label (obs, wl=.true., wu=.false.))
  write (u, "(A)", advance="no") " \rangle = "
  write (u, "(A)", advance="no") char (tex_format (avg, n_digits))
  write (u, "(A)", advance="no") "\pm"
  write (u, "(A)", advance="no") char (tex_format (err, 2))
  write (u, "(A)", advance="no") "\;"
  write (u, "(A)", advance="no") char (observable_get_label (obs, wl=.false., wu=.true.))
  write (u, "(A)") "}"
  write (u, "(A)", advance="no") " \quad [n_{\text{entries}}] = "

```

```

write (u, "(I0)",advance="no")  observable_get_n_entries (obs)
write (u, "(A)")  "]"$"          ! $ fool Emacs' noweb mode
if (heading) then
  write (u, "(A)")  "\end{flushleft}"
end if
end subroutine observable_write_driver

```

5.1.6 Histograms

Bins

<Analysis: types>+≡

```

type :: bin_t
  private
  real(default) :: midpoint = 0
  real(default) :: width = 0
  real(default) :: sum_weights = 0
  real(default) :: sum_squared_weights = 0
  real(default) :: sum_excess_weights = 0
  integer :: count = 0
end type bin_t

```

<Analysis: procedures>+≡

```

subroutine bin_init (bin, midpoint, width)
  type(bin_t), intent(out) :: bin
  real(default), intent(in) :: midpoint, width
  bin%midpoint = midpoint
  bin%width = width
end subroutine bin_init

```

<Analysis: procedures>+≡

```

elemental subroutine bin_clear (bin)
  type(bin_t), intent(inout) :: bin
  bin%sum_weights = 0
  bin%sum_squared_weights = 0
  bin%sum_excess_weights = 0
  bin%count = 0
end subroutine bin_clear

```

<Analysis: procedures>+≡

```

subroutine bin_record_value (bin, normalize, weight, excess)
  type(bin_t), intent(inout) :: bin
  logical, intent(in) :: normalize
  real(default), intent(in) :: weight
  real(default), intent(in), optional :: excess
  real(default) :: w, e
  if (normalize) then
    if (bin%width /= 0) then
      w = weight / bin%width
      if (present (excess)) e = excess / bin%width
    else
      w = 0

```

```

        if (present (excess)) e = 0
    end if
else
    w = weight
    if (present (excess)) e = excess
    end if
    bin%sum_weights = bin%sum_weights + abs (w)
    bin%sum_squared_weights = bin%sum_squared_weights + w ** 2
    if (present (excess)) &
        bin%sum_excess_weights = bin%sum_excess_weights + abs (e)
    bin%count = bin%count + 1
end subroutine bin_record_value

```

(Analysis: procedures)+≡

```

function bin_get_midpoint (bin) result (x)
    real(default) :: x
    type(bin_t), intent(in) :: bin
    x = bin%midpoint
end function bin_get_midpoint

function bin_get_width (bin) result (w)
    real(default) :: w
    type(bin_t), intent(in) :: bin
    w = bin%width
end function bin_get_width

function bin_get_n_entries (bin) result (n)
    integer :: n
    type(bin_t), intent(in) :: bin
    n = bin%count
end function bin_get_n_entries

function bin_get_sum (bin) result (s)
    real(default) :: s
    type(bin_t), intent(in) :: bin
    s = bin%sum_weights
end function bin_get_sum

function bin_get_error (bin) result (err)
    real(default) :: err
    type(bin_t), intent(in) :: bin
    err = sqrt (bin%sum_squared_weights)
end function bin_get_error

function bin_get_excess (bin) result (excess)
    real(default) :: excess
    type(bin_t), intent(in) :: bin
    excess = bin%sum_excess_weights
end function bin_get_excess

```

(Analysis: procedures)+≡

```

subroutine bin_write_header (unit)
    integer, intent(in), optional :: unit

```

```

character(120) :: buffer
integer :: u
u = output_unit (unit); if (u < 0) return
write (buffer, "(A,5(1x," // HISTOGRAM_HEAD_FORMAT // "))" &
      "#", "bin midpoint", "value      ", "error      ", &
      "n_entries ", "excess      ")
write (u, "(A)") trim (buffer)
end subroutine bin_write_header

subroutine bin_write (bin, unit)
type(bin_t), intent(in) :: bin
integer, intent(in), optional :: unit
integer :: u
u = output_unit (unit); if (u < 0) return
write (u, "(1x,3(1x," // HISTOGRAM_DATA_FORMAT // ")," &
      // HISTOGRAM_INTG_FORMAT // "," &
      // HISTOGRAM_DATA_FORMAT // ")") &
      bin_get_midpoint (bin), &
      bin_get_sum (bin), &
      bin_get_error (bin), &
      bin_get_n_entries (bin), &
      bin_get_excess (bin)
end subroutine bin_write

```

Histograms

<Analysis: types>+≡

```

type :: histogram_t
private
real(default) :: lower_bound = 0
real(default) :: upper_bound = 0
real(default) :: width = 0
integer :: n_bins = 0
logical :: normalize_bins = .false.
type(observable_t) :: obs
type(observable_t) :: obs_within_bounds
type(bin_t) :: underflow
type(bin_t), dimension(:), allocatable :: bin
type(bin_t) :: overflow
type(graph_options_t) :: graph_options
type(drawing_options_t) :: drawing_options
end type histogram_t

```

Initializer/finalizer

Initialize a histogram. We may provide either the bin width or the number of bins. A finalizer is not needed, since the histogram contains no pointer (sub)components.

<Analysis: interfaces>+≡

```

interface histogram_init
module procedure histogram_init_n_bins

```



```

    module procedure histogram_init_bin_width
end interface

```

(Analysis: procedures)+≡

```

subroutine histogram_init_n_bins (h, id, &
    lower_bound, upper_bound, n_bins, normalize_bins, &
    obs_label, obs_unit, graph_options, drawing_options)
type(histogram_t), intent(out) :: h
type(string_t), intent(in) :: id
real(default), intent(in) :: lower_bound, upper_bound
integer, intent(in) :: n_bins
logical, intent(in) :: normalize_bins
type(string_t), intent(in), optional :: obs_label, obs_unit
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
real(default) :: bin_width
integer :: i
call observable_init (h%obs_within_bounds, obs_label, obs_unit)
call observable_init (h%obs, obs_label, obs_unit)
h%lower_bound = lower_bound
h%upper_bound = upper_bound
h%n_bins = max (n_bins, 1)
h%width = h%upper_bound - h%lower_bound
h%normalize_bins = normalize_bins
bin_width = h%width / h%n_bins
allocate (h%bin (h%n_bins))
call bin_init (h%underflow, h%lower_bound, 0._default)
do i = 1, h%n_bins
    call bin_init (h%bin(i), &
        h%lower_bound - bin_width/2 + i * bin_width, bin_width)
end do
call bin_init (h%overflow, h%upper_bound, 0._default)
if (present (graph_options)) then
    h%graph_options = graph_options
else
    call graph_options_init (h%graph_options)
end if
call graph_options_set (h%graph_options, id = id)
if (present (drawing_options)) then
    h%drawing_options = drawing_options
else
    call drawing_options_init_histogram (h%drawing_options)
end if
end subroutine histogram_init_n_bins

subroutine histogram_init_bin_width (h, id, &
    lower_bound, upper_bound, bin_width, normalize_bins, &
    obs_label, obs_unit, graph_options, drawing_options)
type(histogram_t), intent(out) :: h
type(string_t), intent(in) :: id
real(default), intent(in) :: lower_bound, upper_bound, bin_width
logical, intent(in) :: normalize_bins
type(string_t), intent(in), optional :: obs_label, obs_unit
type(graph_options_t), intent(in), optional :: graph_options

```

```

type(drawing_options_t), intent(in), optional :: drawing_options
integer :: n_bins
if (bin_width /= 0) then
    n_bins = nint ((upper_bound - lower_bound) / bin_width)
else
    n_bins = 1
end if
call histogram_init_n_bins (h, id, &
    lower_bound, upper_bound, n_bins, normalize_bins, &
    obs_label, obs_unit, graph_options, drawing_options)
end subroutine histogram_init_bin_width

```

Initialize a histogram by copying another one.

Since `h` has no pointer (sub)components, intrinsic assignment is sufficient. Optionally, we replace the drawing options.

<Analysis: procedures>+≡

```

subroutine histogram_init_histogram (h, h_in, drawing_options)
    type(histogram_t), intent(out) :: h
    type(histogram_t), intent(in) :: h_in
    type(drawing_options_t), intent(in), optional :: drawing_options
    h = h_in
    if (present (drawing_options)) then
        h%drawing_options = drawing_options
    end if
end subroutine histogram_init_histogram

```

Fill histograms

Clear the histogram contents, but do not modify the structure.

<Analysis: procedures>+≡

```

subroutine histogram_clear (h)
    type(histogram_t), intent(inout) :: h
    call observable_clear (h%obs)
    call observable_clear (h%obs_within_bounds)
    call bin_clear (h%underflow)
    if (allocated (h%bin)) call bin_clear (h%bin)
    call bin_clear (h%overflow)
end subroutine histogram_clear

```

Record a value. Successful if the value is within bounds, otherwise it is recorded as under-/overflow. Optionally, we may provide an excess weight that could be returned by the unweighting procedure.

<Analysis: procedures>+≡

```

subroutine histogram_record_value_unweighted (h, value, excess, success)
    type(histogram_t), intent(inout) :: h
    real(default), intent(in) :: value
    real(default), intent(in), optional :: excess
    logical, intent(out), optional :: success
    integer :: i_bin
    call observable_record_value (h%obs, value)
    if (h%width /= 0) then

```

```

        i_bin = floor (((value - h%lower_bound) / h%width) * h%n_bins) + 1
    else
        i_bin = 0
    end if
    if (i_bin <= 0) then
        call bin_record_value (h%underflow, .false., 1._default, excess)
        if (present (success)) success = .false.
    else if (i_bin <= h%n_bins) then
        call observable_record_value (h%obs_within_bounds, value)
        call bin_record_value &
            (h%bin(i_bin), h%normalize_bins, 1._default, excess)
        if (present (success)) success = .true.
    else
        call bin_record_value (h%overflow, .false., 1._default, excess)
        if (present (success)) success = .false.
    end if
end subroutine histogram_record_value_unweighted

```

Weighted events: analogous, but no excess weight.

<Analysis: procedures>+≡

```

subroutine histogram_record_value_weighted (h, value, weight, success)
    type(histogram_t), intent(inout) :: h
    real(default), intent(in) :: value, weight
    logical, intent(out), optional :: success
    integer :: i_bin
    call observable_record_value (h%obs, value, weight)
    if (h%width /= 0) then
        i_bin = floor (((value - h%lower_bound) / h%width) * h%n_bins) + 1
    else
        i_bin = 0
    end if
    if (i_bin <= 0) then
        call bin_record_value (h%underflow, .false., weight)
        if (present (success)) success = .false.
    else if (i_bin <= h%n_bins) then
        call observable_record_value (h%obs_within_bounds, value, weight)
        call bin_record_value (h%bin(i_bin), h%normalize_bins, weight)
        if (present (success)) success = .true.
    else
        call bin_record_value (h%overflow, .false., weight)
        if (present (success)) success = .false.
    end if
end subroutine histogram_record_value_weighted

```

Access contents

Inherited from the observable component (all-over average etc.)

<Analysis: procedures>+≡

```

function histogram_get_n_entries (h) result (n)
    integer :: n
    type(histogram_t), intent(in) :: h
    n = observable_get_n_entries (h%obs)

```

```

end function histogram_get_n_entries

function histogram_get_average (h) result (avg)
  real(default) :: avg
  type(histogram_t), intent(in) :: h
  avg = observable_get_average (h%obs)
end function histogram_get_average

function histogram_get_error (h) result (err)
  real(default) :: err
  type(histogram_t), intent(in) :: h
  err = observable_get_error (h%obs)
end function histogram_get_error

```

Analogous, but applied only to events within bounds.

<Analysis: procedures>+≡

```

function histogram_get_n_entries_within_bounds (h) result (n)
  integer :: n
  type(histogram_t), intent(in) :: h
  n = observable_get_n_entries (h%obs_within_bounds)
end function histogram_get_n_entries_within_bounds

function histogram_get_average_within_bounds (h) result (avg)
  real(default) :: avg
  type(histogram_t), intent(in) :: h
  avg = observable_get_average (h%obs_within_bounds)
end function histogram_get_average_within_bounds

function histogram_get_error_within_bounds (h) result (err)
  real(default) :: err
  type(histogram_t), intent(in) :: h
  err = observable_get_error (h%obs_within_bounds)
end function histogram_get_error_within_bounds

```

Get the number of bins

<Analysis: procedures>+≡

```

function histogram_get_n_bins (h) result (n)
  type(histogram_t), intent(in) :: h
  integer :: n
  n = h%n_bins
end function histogram_get_n_bins

```

Check bins. If the index is zero or above the limit, return the results for underflow or overflow, respectively.

<Analysis: procedures>+≡

```

function histogram_get_n_entries_for_bin (h, i) result (n)
  integer :: n
  type(histogram_t), intent(in) :: h
  integer, intent(in) :: i
  if (i <= 0) then
    n = bin_get_n_entries (h%underflow)
  else if (i <= h%n_bins) then

```

```

        n = bin_get_n_entries (h%bin(i))
    else
        n = bin_get_n_entries (h%overflow)
    end if
end function histogram_get_n_entries_for_bin

function histogram_get_sum_for_bin (h, i) result (avg)
    real(default) :: avg
    type(histogram_t), intent(in) :: h
    integer, intent(in) :: i
    if (i <= 0) then
        avg = bin_get_sum (h%underflow)
    else if (i <= h%n_bins) then
        avg = bin_get_sum (h%bin(i))
    else
        avg = bin_get_sum (h%overflow)
    end if
end function histogram_get_sum_for_bin

function histogram_get_error_for_bin (h, i) result (err)
    real(default) :: err
    type(histogram_t), intent(in) :: h
    integer, intent(in) :: i
    if (i <= 0) then
        err = bin_get_error (h%underflow)
    else if (i <= h%n_bins) then
        err = bin_get_error (h%bin(i))
    else
        err = bin_get_error (h%overflow)
    end if
end function histogram_get_error_for_bin

function histogram_get_excess_for_bin (h, i) result (err)
    real(default) :: err
    type(histogram_t), intent(in) :: h
    integer, intent(in) :: i
    if (i <= 0) then
        err = bin_get_excess (h%underflow)
    else if (i <= h%n_bins) then
        err = bin_get_excess (h%bin(i))
    else
        err = bin_get_excess (h%overflow)
    end if
end function histogram_get_excess_for_bin

```

Return a pointer to the graph options.

<Analysis: procedures>+≡

```

function histogram_get_graph_options_ptr (h) result (ptr)
    type(graph_options_t), pointer :: ptr
    type(histogram_t), intent(in), target :: h
    ptr => h%graph_options
end function histogram_get_graph_options_ptr

```

Return a pointer to the drawing options.

<Analysis: procedures>+≡

```
function histogram_get_drawing_options_ptr (h) result (ptr)
  type(drawing_options_t), pointer :: ptr
  type(histogram_t), intent(in), target :: h
  ptr => h%drawing_options
end function histogram_get_drawing_options_ptr
```

Output

<Analysis: procedures>+≡

```
subroutine histogram_write (h, unit)
  type(histogram_t), intent(in) :: h
  integer, intent(in), optional :: unit
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  call bin_write_header (u)
  if (allocated (h%bin)) then
    do i = 1, h%n_bins
      call bin_write (h%bin(i), u)
    end do
  end if
  write (u, *)
  write (u, "(A,1x,A)" "#", "Underflow:")
  call bin_write (h%underflow, u)
  write (u, *)
  write (u, "(A,1x,A)" "#", "Overflow:")
  call bin_write (h%overflow, u)
  write (u, *)
  write (u, "(A,1x,A)" "#", "Summary: data within bounds")
  call observable_write (h%obs_within_bounds, u)
  write (u, *)
  write (u, "(A,1x,A)" "#", "Summary: all data")
  call observable_write (h%obs, u)
  write (u, *)
end subroutine histogram_write
```

Write the GAMELAN reader for histogram contents.

<Analysis: procedures>+≡

```
subroutine histogram_write_gml_reader (h, filename, unit)
  type(histogram_t), intent(in) :: h
  type(string_t), intent(in) :: filename
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, "(2x,A)" 'fromfile ' // char (filename) // '":')
  write (u, "(4x,A)" 'key "# Histogram:;')
  write (u, "(4x,A)" 'dx := #' &
    // real2char (h%width / h%n_bins / 2) // ','
  write (u, "(4x,A)" 'for i withinblock:')
  write (u, "(6x,A)" 'get x, y, y.d, y.n, y.e;')
  if (h%drawing_options%with_hbars) then
```

```

        write (u, "(6x,A)") 'plot (' // char (h%drawing_options%dataset) &
            // ')' (x,y) hbar dx;'
    else
        write (u, "(6x,A)") 'plot (' // char (h%drawing_options%dataset) &
            // ')' (x,y);'
    end if
    if (h%drawing_options%err) then
        write (u, "(6x,A)") 'plot (' // char (h%drawing_options%dataset) &
            // '.err) ' &
            // '(x,y) vbar y.d;'
    end if
!   write (u, "(6x,A)") 'if show_excess: ' // &
!       & 'plot(dat.e)(x, y plus y.e) hbar dx; fi'
    write (u, "(4x,A)") 'endfor'
    write (u, "(2x,A)") 'endfrom'
end subroutine histogram_write_gml_reader

```

L^AT_EX and GAMELAN output.

(Analysis: procedures)+≡

```

subroutine histogram_write_gml_driver (h, filename, unit)
    type(histogram_t), intent(in) :: h
    type(string_t), intent(in) :: filename
    integer, intent(in), optional :: unit
    type(string_t) :: calc_cmd, bg_cmd, draw_cmd, err_cmd, symb_cmd, fg_cmd
    integer :: u
    u = output_unit (unit); if (u < 0) return
    call graph_options_write_tex_header (h%graph_options, unit)
    write (u, "(2x,A)") char (graph_options_get_gml_setup (h%graph_options))
    write (u, "(2x,A)") char (graph_options_get_gml_graphrange &
        (h%graph_options, x_min=h%lower_bound, x_max=h%upper_bound))
    call histogram_write_gml_reader (h, filename, unit)
    calc_cmd = drawing_options_get_calc_command (h%drawing_options)
    if (calc_cmd /= "") write (u, "(2x,A)") char (calc_cmd)
    bg_cmd = drawing_options_get_gml_bg_command (h%drawing_options)
    if (bg_cmd /= "") write (u, "(2x,A)") char (bg_cmd)
    draw_cmd = drawing_options_get_draw_command (h%drawing_options)
    if (draw_cmd /= "") write (u, "(2x,A)") char (draw_cmd)
    err_cmd = drawing_options_get_err_command (h%drawing_options)
    if (err_cmd /= "") write (u, "(2x,A)") char (err_cmd)
    symb_cmd = drawing_options_get_symb_command (h%drawing_options)
    if (symb_cmd /= "") write (u, "(2x,A)") char (symb_cmd)
    fg_cmd = drawing_options_get_gml_fg_command (h%drawing_options)
    if (fg_cmd /= "") write (u, "(2x,A)") char (fg_cmd)
    write (u, "(2x,A)") char (graph_options_get_gml_x_label (h%graph_options))
    write (u, "(2x,A)") char (graph_options_get_gml_y_label (h%graph_options))
    call graph_options_write_tex_footer (h%graph_options, unit)
    write (u, "(A)") "\vspace*{2\baselineskip}"
    write (u, "(A)") "\begin{flushleft}"
    write (u, "(A)") "\textbf{Data within bounds:} \\"
    call observable_write_driver (h%obs_within_bounds, unit, &
        write_heading=.false.)
    write (u, "(A)") "\\[0.5\baselineskip]"
    write (u, "(A)") "\textbf{All data:} \\"
    call observable_write_driver (h%obs, unit, write_heading=.false.)

```

```

        write (u, "(A)") "\end{flushleft}"
    end subroutine histogram_write_gml_driver

```

Return the header for generic data output as an ifile.

```

<Analysis: procedures>+≡
subroutine histogram_get_header (h, header, comment)
    type(histogram_t), intent(in) :: h
    type(ifile_t), intent(inout) :: header
    type(string_t), intent(in), optional :: comment
    type(string_t) :: c
    if (present (comment)) then
        c = comment
    else
        c = ""
    end if
    call ifile_append (header, c // "WHIZARD histogram data")
    call graph_options_get_header (h%graph_options, header, comment)
    call ifile_append (header, &
        c // "range: " // real2string (h%lower_bound) &
        // " - " // real2string (h%upper_bound))
    call ifile_append (header, &
        c // "counts total: " &
        // int2char (histogram_get_n_entries_within_bounds (h)))
    call ifile_append (header, &
        c // "total average: " &
        // real2string (histogram_get_average_within_bounds (h)) // " +- " &
        // real2string (histogram_get_error_within_bounds (h)))
end subroutine histogram_get_header

```

5.1.7 Plots

Points

```

<Analysis: types>+≡
type :: point_t
    private
    real(default) :: x = 0
    real(default) :: y = 0
    real(default) :: yerr = 0
    real(default) :: xerr = 0
    type(point_t), pointer :: next => null ()
end type point_t

<Analysis: interfaces>+≡
interface point_init
    module procedure point_init_contents
    module procedure point_init_point
end interface

<Analysis: procedures>+≡
subroutine point_init_contents (point, x, y, yerr, xerr)
    type(point_t), intent(out) :: point
    real(default), intent(in) :: x, y

```



```

    real(default), intent(in), optional :: yerr, xerr
    point%x = x
    point%y = y
    if (present (yerr)) point%yerr = yerr
    if (present (xerr)) point%xerr = xerr
end subroutine point_init_contents

subroutine point_init_point (point, point_in)
    type(point_t), intent(out) :: point
    type(point_t), intent(in) :: point_in
    point%x = point_in%x
    point%y = point_in%y
    point%yerr = point_in%yerr
    point%xerr = point_in%xerr
end subroutine point_init_point

```

<Analysis: procedures>+≡

```

function point_get_x (point) result (x)
    real(default) :: x
    type(point_t), intent(in) :: point
    x = point%x
end function point_get_x

function point_get_y (point) result (y)
    real(default) :: y
    type(point_t), intent(in) :: point
    y = point%y
end function point_get_y

function point_get_xerr (point) result (xerr)
    real(default) :: xerr
    type(point_t), intent(in) :: point
    xerr = point%xerr
end function point_get_xerr

function point_get_yerr (point) result (yerr)
    real(default) :: yerr
    type(point_t), intent(in) :: point
    yerr = point%yerr
end function point_get_yerr

```

<Analysis: procedures>+≡

```

subroutine point_write_header (unit)
    integer, intent(in) :: unit
    character(120) :: buffer
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write (buffer, "(A,4(1x," // HISTOGRAM_HEAD_FORMAT // "))" &
        "#", "x", "y", "yerr", "xerr"
    write (u, "(A)") trim (buffer)
end subroutine point_write_header

subroutine point_write (point, unit)

```

```

type(point_t), intent(in) :: point
integer, intent(in), optional :: unit
integer :: u
u = output_unit (unit); if (u < 0) return
write (u, "(1x,4(1x," // HISTOGRAM_DATA_FORMAT // ")),") &
    point_get_x (point), &
    point_get_y (point), &
    point_get_yerr (point), &
    point_get_xerr (point)
end subroutine point_write

```

Plots

<Analysis: types>+≡

```

type :: plot_t
private
type(point_t), pointer :: first => null ()
type(point_t), pointer :: last => null ()
integer :: count = 0
type(graph_options_t) :: graph_options
type(drawing_options_t) :: drawing_options
end type plot_t

```

Initializer/finalizer

Initialize a plot. We provide the lower and upper bound in the x direction.

<Analysis: interfaces>+≡

```

interface plot_init
module procedure plot_init_empty
module procedure plot_init_plot
end interface

```

<Analysis: procedures>+≡

```

subroutine plot_init_empty (p, id, graph_options, drawing_options)
type(plot_t), intent(out) :: p
type(string_t), intent(in) :: id
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
if (present (graph_options)) then
    p%graph_options = graph_options
else
    call graph_options_init (p%graph_options)
end if
call graph_options_set (p%graph_options, id = id)
if (present (drawing_options)) then
    p%drawing_options = drawing_options
else
    call drawing_options_init_plot (p%drawing_options)
end if
end subroutine plot_init_empty

```

Initialize a plot by copying another one, optionally merging in a new set of drawing options.

Since `p` has pointer (sub)components, we have to explicitly deep-copy the original.

<Analysis: procedures>+≡

```
subroutine plot_init_plot (p, p_in, drawing_options)
  type(plot_t), intent(out) :: p
  type(plot_t), intent(in) :: p_in
  type(drawing_options_t), intent(in), optional :: drawing_options
  type(point_t), pointer :: current, new
  current => p_in%first
  do while (associated (current))
    allocate (new)
    call point_init (new, current)
    if (associated (p%last)) then
      p%last%next => new
    else
      p%first => new
    end if
    p%last => new
    current => current%next
  end do
  p%count = p_in%count
  p%graph_options = p_in%graph_options
  if (present (drawing_options)) then
    p%drawing_options = drawing_options
  else
    p%drawing_options = p_in%drawing_options
  end if
end subroutine plot_init_plot
```

Finalize the plot by deallocating the list of points.

<Analysis: procedures>+≡

```
subroutine plot_final (plot)
  type(plot_t), intent(inout) :: plot
  type(point_t), pointer :: current
  do while (associated (plot%first))
    current => plot%first
    plot%first => current%next
    deallocate (current)
  end do
  plot%last => null ()
end subroutine plot_final
```

Fill plots

Clear the plot contents, but do not modify the structure.

<Analysis: procedures>+≡

```
subroutine plot_clear (plot)
  type(plot_t), intent(inout) :: plot
  plot%count = 0
```

```

        call plot_final (plot)
    end subroutine plot_clear

```

Record a value. Successful if the value is within bounds, otherwise it is recorded as under-/overflow.

<Analysis: procedures>+≡

```

subroutine plot_record_value (plot, x, y, yerr, xerr, success)
    type(plot_t), intent(inout) :: plot
    real(default), intent(in) :: x, y
    real(default), intent(in), optional :: yerr, xerr
    logical, intent(out), optional :: success
    type(point_t), pointer :: point
    plot%count = plot%count + 1
    allocate (point)
    call point_init (point, x, y, yerr, xerr)
    if (associated (plot%first)) then
        plot%last%next => point
    else
        plot%first => point
    end if
    plot%last => point
    if (present (success)) success = .true.
end subroutine plot_record_value

```

Access contents

The number of points.

<Analysis: procedures>+≡

```

function plot_get_n_entries (plot) result (n)
    integer :: n
    type(plot_t), intent(in) :: plot
    n = plot%count
end function plot_get_n_entries

```

Return a pointer to the graph options.

<Analysis: procedures>+≡

```

function plot_get_graph_options_ptr (p) result (ptr)
    type(graph_options_t), pointer :: ptr
    type(plot_t), intent(in), target :: p
    ptr => p%graph_options
end function plot_get_graph_options_ptr

```

Return a pointer to the drawing options.

<Analysis: procedures>+≡

```

function plot_get_drawing_options_ptr (p) result (ptr)
    type(drawing_options_t), pointer :: ptr
    type(plot_t), intent(in), target :: p
    ptr => p%drawing_options
end function plot_get_drawing_options_ptr

```

Output

This output format is used by the GAMELAN driver below.

<Analysis: procedures>+≡

```
subroutine plot_write (plot, unit)
  type(plot_t), intent(in) :: plot
  integer, intent(in), optional :: unit
  type(point_t), pointer :: point
  integer :: u
  u = output_unit (unit); if (u < 0) return
  call point_write_header (u)
  point => plot%first
  do while (associated (point))
    call point_write (point, unit)
    point => point%next
  end do
  write (u, *)
  write (u, "(A,1x,A)" ) "#", "Summary:"
  write (u, "(A," // HISTOGRAM_INTG_FORMAT // ")") &
    "n_entries = ", plot_get_n_entries (plot)
  write (u, *)
end subroutine plot_write
```

Write the GAMELAN reader for plot contents.

<Analysis: procedures>+≡

```
subroutine plot_write_gml_reader (p, filename, unit)
  type(plot_t), intent(in) :: p
  type(string_t), intent(in) :: filename
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, "(2x,A)" ) 'fromfile "' // char (filename) // '":'
  write (u, "(4x,A)" ) 'key "# Plot:";'
  write (u, "(4x,A)" ) 'for i withinblock:'
  write (u, "(6x,A)" ) 'get x, y, y.err, x.err;'
  write (u, "(6x,A)" ) 'plot (' // char (p%drawing_options%dataset) &
    // ') (x,y);'
  if (p%drawing_options%err) then
    write (u, "(6x,A)" ) 'plot (' // char (p%drawing_options%dataset) &
      // '.err) (x,y) vbar y.err hbar x.err;'
  end if
  write (u, "(4x,A)" ) 'endfor'
  write (u, "(2x,A)" ) 'endfrom'
end subroutine plot_write_gml_reader
```

L^AT_EX and GAMELAN output. Analogous to histogram output.

<Analysis: procedures>+≡

```
subroutine plot_write_gml_driver (p, filename, unit)
  type(plot_t), intent(in) :: p
  type(string_t), intent(in) :: filename
  integer, intent(in), optional :: unit
  type(string_t) :: calc_cmd, bg_cmd, draw_cmd, err_cmd, symb_cmd, fg_cmd
  integer :: u
```

```

u = output_unit (unit); if (u < 0) return
call graph_options_write_tex_header (p%graph_options, unit)
write (u, "(2x,A)") &
    char (graph_options_get_gml_setup (p%graph_options))
write (u, "(2x,A)") &
    char (graph_options_get_gml_graphrange (p%graph_options))
call plot_write_gml_reader (p, filename, unit)
calc_cmd = drawing_options_get_calc_command (p%drawing_options)
if (calc_cmd /= "") write (u, "(2x,A)") char (calc_cmd)
bg_cmd = drawing_options_get_gml_bg_command (p%drawing_options)
if (bg_cmd /= "") write (u, "(2x,A)") char (bg_cmd)
draw_cmd = drawing_options_get_draw_command (p%drawing_options)
if (draw_cmd /= "") write (u, "(2x,A)") char (draw_cmd)
err_cmd = drawing_options_get_err_command (p%drawing_options)
if (err_cmd /= "") write (u, "(2x,A)") char (err_cmd)
symb_cmd = drawing_options_get_symb_command (p%drawing_options)
if (symb_cmd /= "") write (u, "(2x,A)") char (symb_cmd)
fg_cmd = drawing_options_get_gml_fg_command (p%drawing_options)
if (fg_cmd /= "") write (u, "(2x,A)") char (fg_cmd)
write (u, "(2x,A)") char (graph_options_get_gml_x_label (p%graph_options))
write (u, "(2x,A)") char (graph_options_get_gml_y_label (p%graph_options))
call graph_options_write_tex_footer (p%graph_options, unit)
end subroutine plot_write_gml_driver

```

Append header for generic data output in ifile format.

(Analysis: procedures)+≡

```

subroutine plot_get_header (plot, header, comment)
    type(plot_t), intent(in) :: plot
    type(ifile_t), intent(inout) :: header
    type(string_t), intent(in), optional :: comment
    type(string_t) :: c
    if (present (comment)) then
        c = comment
    else
        c = ""
    end if
    call ifile_append (header, c // "WHIZARD plot data")
    call graph_options_get_header (plot%graph_options, header, comment)
    call ifile_append (header, &
        c // "number of points: " &
        // int2char (plot_get_n_entries (plot)))
end subroutine plot_get_header

```

5.1.8 Graphs

A graph is a container for several graph elements. Each graph element is either a plot or a histogram. There is an appropriate base type below (the `analysis_object_t`), but to avoid recursion, we define a separate base type here. Note that there is no actual recursion: a graph is an analysis object, but a graph cannot contain graphs.

(If we could use type extension, the implementation would be much more transparent.)

Graph elements

Graph elements cannot be filled by the **record** command directly. The contents are always copied from elementary histograms or plots.

(Analysis: types)+≡

```
type :: graph_element_t
private
integer :: type = AN_UNDEFINED
type(histogram_t), pointer :: h => null ()
type(plot_t), pointer :: p => null ()
end type graph_element_t
```

(Analysis: procedures)+≡

```
subroutine graph_element_final (el)
type(graph_element_t), intent(inout) :: el
select case (el%type)
case (AN_HISTOGRAM)
deallocate (el%h)
case (AN_PLOT)
call plot_final (el%p)
deallocate (el%p)
end select
el%type = AN_UNDEFINED
end subroutine graph_element_final
```

Return the number of entries in the graph element:

(Analysis: procedures)+≡

```
function graph_element_get_n_entries (el) result (n)
integer :: n
type(graph_element_t), intent(in) :: el
select case (el%type)
case (AN_HISTOGRAM); n = histogram_get_n_entries (el%h)
case (AN_PLOT);      n = plot_get_n_entries (el%p)
case default;        n = 0
end select
end function graph_element_get_n_entries
```

Return a pointer to the graph / drawing options.

(Analysis: procedures)+≡

```
function graph_element_get_graph_options_ptr (el) result (ptr)
type(graph_options_t), pointer :: ptr
type(graph_element_t), intent(in) :: el
select case (el%type)
case (AN_HISTOGRAM); ptr => histogram_get_graph_options_ptr (el%h)
case (AN_PLOT);      ptr => plot_get_graph_options_ptr (el%p)
case default;        ptr => null ()
end select
end function graph_element_get_graph_options_ptr

function graph_element_get_drawing_options_ptr (el) result (ptr)
type(drawing_options_t), pointer :: ptr
type(graph_element_t), intent(in) :: el
```

```

        select case (el%type)
        case (AN_HISTOGRAM); ptr => histogram_get_drawing_options_ptr (el%h)
        case (AN_PLOT);      ptr => plot_get_drawing_options_ptr (el%p)
        case default;        ptr => null ()
        end select
    end function graph_element_get_drawing_options_ptr

```

Output, simple wrapper for the plot/histogram writer.

<Analysis: procedures>+≡

```

subroutine graph_element_write (el, unit)
    type(graph_element_t), intent(in) :: el
    integer, intent(in), optional :: unit
    type(graph_options_t), pointer :: gro
    type(string_t) :: id
    integer :: u
    u = output_unit (unit); if (u < 0) return
    gro => graph_element_get_graph_options_ptr (el)
    id = graph_options_get_id (gro)
    write (u, "(A,A)" ' #', repeat ("-", 78))
    select case (el%type)
    case (AN_HISTOGRAM)
        write (u, "(A)", advance="no")  "# Histogram: "
        write (u, "(1x,A)" char (id)
        call histogram_write (el%h, unit)
    case (AN_PLOT)
        write (u, "(A)", advance="no")  "# Plot: "
        write (u, "(1x,A)" char (id)
        call plot_write (el%p, unit)
    end select
end subroutine graph_element_write

```

<Analysis: procedures>+≡

```

subroutine graph_element_write_gml_reader (el, filename, unit)
    type(graph_element_t), intent(in) :: el
    type(string_t), intent(in) :: filename
    integer, intent(in), optional :: unit
    select case (el%type)
    case (AN_HISTOGRAM); call histogram_write_gml_reader (el%h, filename, unit)
    case (AN_PLOT);      call plot_write_gml_reader (el%p, filename, unit)
    end select
end subroutine graph_element_write_gml_reader

```

The graph type

The actual graph type contains its own `graph_options`, which override the individual settings. The `drawing_options` are set in the graph elements. This distinction motivates the separation of the two types.

<Analysis: types>+≡

```

type :: graph_t
    private
    type(graph_element_t), dimension(:), allocatable :: el

```



```

    type(graph_options_t) :: graph_options
end type graph_t

```

Initializer/finalizer

The graph is created with a definite number of elements. The elements are filled one by one, optionally with modified drawing options.

(Analysis: procedures)+≡

```

subroutine graph_init (g, id, n_elements, graph_options)
    type(graph_t), intent(out) :: g
    type(string_t), intent(in) :: id
    integer, intent(in) :: n_elements
    type(graph_options_t), intent(in), optional :: graph_options
    allocate (g%el (n_elements))
    if (present (graph_options)) then
        g%graph_options = graph_options
    else
        call graph_options_init (g%graph_options)
    end if
    call graph_options_set (g%graph_options, id = id)
end subroutine graph_init

```

(Analysis: procedures)+≡

```

subroutine graph_insert_histogram (g, i, h, drawing_options)
    type(graph_t), intent(inout), target :: g
    integer, intent(in) :: i
    type(histogram_t), intent(in) :: h
    type(drawing_options_t), intent(in), optional :: drawing_options
    type(graph_options_t), pointer :: gro
    type(drawing_options_t), pointer :: dro
    type(string_t) :: id
    g%el(i)%type = AN_HISTOGRAM
    allocate (g%el(i)%h)
    call histogram_init_histogram (g%el(i)%h, h, drawing_options)
    gro => histogram_get_graph_options_ptr (g%el(i)%h)
    dro => histogram_get_drawing_options_ptr (g%el(i)%h)
    id = graph_options_get_id (gro)
    call drawing_options_set (dro, dataset = "dat." // id)
end subroutine graph_insert_histogram

```

(Analysis: procedures)+≡

```

subroutine graph_insert_plot (g, i, p, drawing_options)
    type(graph_t), intent(inout) :: g
    integer, intent(in) :: i
    type(plot_t), intent(in) :: p
    type(drawing_options_t), intent(in), optional :: drawing_options
    type(graph_options_t), pointer :: gro
    type(drawing_options_t), pointer :: dro
    type(string_t) :: id
    g%el(i)%type = AN_PLOT
    allocate (g%el(i)%p)
    call plot_init_plot (g%el(i)%p, p, drawing_options)

```

```

        gro => plot_get_graph_options_ptr (g%el(i)%p)
        dro => plot_get_drawing_options_ptr (g%el(i)%p)
        id = graph_options_get_id (gro)
        call drawing_options_set (dro, dataset = "dat." // id)
    end subroutine graph_insert_plot

```

Finalizer.

```

<Analysis: procedures>+≡
subroutine graph_final (g)
    type(graph_t), intent(inout) :: g
    integer :: i
    do i = 1, size (g%el)
        call graph_element_final (g%el(i))
    end do
    deallocate (g%el)
end subroutine graph_final

```

Access contents

The number of elements.

```

<Analysis: procedures>+≡
function graph_get_n_elements (graph) result (n)
    integer :: n
    type(graph_t), intent(in) :: graph
    n = size (graph%el)
end function graph_get_n_elements

```

Retrieve a pointer to the drawing options of an element, so they can be modified. (The `target` attribute is not actually needed because the components are pointers.)

```

<Analysis: procedures>+≡
function graph_get_drawing_options_ptr (g, i) result (ptr)
    type(drawing_options_t), pointer :: ptr
    type(graph_t), intent(in), target :: g
    integer, intent(in) :: i
    ptr => graph_element_get_drawing_options_ptr (g%el(i))
end function graph_get_drawing_options_ptr

```

Output

The default output format just writes histogram and plot data.

```

<Analysis: procedures>+≡
subroutine graph_write (graph, unit)
    type(graph_t), intent(in) :: graph
    integer, intent(in), optional :: unit
    integer :: i
    do i = 1, size (graph%el)
        call graph_element_write (graph%el(i), unit)
    end do

```

```
end subroutine graph_write
```

The GAMELAN driver is not a simple wrapper, but it writes the plot/histogram contents embedded the complete graph. First, data are read in, global background commands next, then individual elements, then global foreground commands.

<Analysis: procedures>+≡

```
subroutine graph_write_gml_driver (g, filename, unit)
  type(graph_t), intent(in) :: g
  type(string_t), intent(in) :: filename
  type(string_t) :: calc_cmd, bg_cmd, draw_cmd, err_cmd, symb_cmd, fg_cmd
  integer, intent(in), optional :: unit
  type(drawing_options_t), pointer :: dro
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  call graph_options_write_tex_header (g%graph_options, unit)
  write (u, "(2x,A)") &
    char (graph_options_get_gml_setup (g%graph_options))
  write (u, "(2x,A)") &
    char (graph_options_get_gml_graphrange (g%graph_options))
  do i = 1, size (g%el)
    call graph_element_write_gml_reader (g%el(i), filename, unit)
    calc_cmd = drawing_options_get_calc_command &
      (graph_element_get_drawing_options_ptr (g%el(i)))
    if (calc_cmd /= "") write (u, "(2x,A)") char (calc_cmd)
  end do
  bg_cmd = graph_options_get_gml_bg_command (g%graph_options)
  if (bg_cmd /= "") write (u, "(2x,A)") char (bg_cmd)
  do i = 1, size (g%el)
    dro => graph_element_get_drawing_options_ptr (g%el(i))
    bg_cmd = drawing_options_get_gml_bg_command (dro)
    if (bg_cmd /= "") write (u, "(2x,A)") char (bg_cmd)
    draw_cmd = drawing_options_get_draw_command (dro)
    if (draw_cmd /= "") write (u, "(2x,A)") char (draw_cmd)
    err_cmd = drawing_options_get_err_command (dro)
    if (err_cmd /= "") write (u, "(2x,A)") char (err_cmd)
    symb_cmd = drawing_options_get_symb_command (dro)
    if (symb_cmd /= "") write (u, "(2x,A)") char (symb_cmd)
    fg_cmd = drawing_options_get_gml_fg_command (dro)
    if (fg_cmd /= "") write (u, "(2x,A)") char (fg_cmd)
  end do
  fg_cmd = graph_options_get_gml_fg_command (g%graph_options)
  if (fg_cmd /= "") write (u, "(2x,A)") char (fg_cmd)
  write (u, "(2x,A)") char (graph_options_get_gml_x_label (g%graph_options))
  write (u, "(2x,A)") char (graph_options_get_gml_y_label (g%graph_options))
  call graph_options_write_tex_footer (g%graph_options, unit)
end subroutine graph_write_gml_driver
```

Append header for generic data output in ifile format.

<Analysis: procedures>+≡

```
subroutine graph_get_header (graph, header, comment)
  type(graph_t), intent(in) :: graph
  type(ifile_t), intent(inout) :: header
```

```

type(string_t), intent(in), optional :: comment
type(string_t) :: c
if (present (comment)) then
    c = comment
else
    c = ""
end if
call ifile_append (header, c // "WHIZARD graph data")
call graph_options_get_header (graph%graph_options, header, comment)
call ifile_append (header, &
    c // "number of graph elements: " &
    // int2char (graph_get_n_elements (graph)))
end subroutine graph_get_header

```

5.1.9 Analysis objects

This data structure holds all observables, histograms and such that are currently active. We have one global store; individual items are identified by their ID strings.

(This should rather be coded by type extension.)

```

<Analysis: parameters>≡
integer, parameter :: AN_UNDEFINED = 0
integer, parameter :: AN_OBSERVABLE = 1
integer, parameter :: AN_HISTOGRAM = 2
integer, parameter :: AN_PLOT = 3
integer, parameter :: AN_GRAPH = 4

<Analysis: public>+≡
public :: AN_UNDEFINED, AN_HISTOGRAM, AN_OBSERVABLE, AN_PLOT, AN_GRAPH

<Analysis: types>+≡
type :: analysis_object_t
private
type(string_t) :: id
integer :: type = AN_UNDEFINED
type(observable_t), pointer :: obs => null ()
type(histogram_t), pointer :: h => null ()
type(plot_t), pointer :: p => null ()
type(graph_t), pointer :: g => null ()
type(analysis_object_t), pointer :: next => null ()
end type analysis_object_t

```

Initializer/finalizer

Allocate with the correct type but do not fill initial values.

```

<Analysis: procedures>+≡
subroutine analysis_object_init (obj, id, type)
type(analysis_object_t), intent(out) :: obj
type(string_t), intent(in) :: id
integer, intent(in) :: type
obj%id = id

```

```

obj%type = type
select case (obj%type)
case (AN_OBSERVABLE); allocate (obj%obs)
case (AN_HISTOGRAM);  allocate (obj%h)
case (AN_PLOT);       allocate (obj%p)
case (AN_GRAPH);      allocate (obj%g)
end select
end subroutine analysis_object_init

```

<Analysis: procedures>+≡

```

subroutine analysis_object_final (obj)
type(analysis_object_t), intent(inout) :: obj
select case (obj%type)
case (AN_OBSERVABLE)
deallocate (obj%obs)
case (AN_HISTOGRAM)
deallocate (obj%h)
case (AN_PLOT)
call plot_final (obj%p)
deallocate (obj%p)
case (AN_GRAPH)
call graph_final (obj%g)
deallocate (obj%g)
end select
obj%type = AN_UNDEFINED
end subroutine analysis_object_final

```

Clear the analysis object, i.e., reset it to its initial state. Not applicable to graphs, which are always combinations of other existing objects.

<Analysis: procedures>+≡

```

subroutine analysis_object_clear (obj)
type(analysis_object_t), intent(inout) :: obj
select case (obj%type)
case (AN_OBSERVABLE)
call observable_clear (obj%obs)
case (AN_HISTOGRAM)
call histogram_clear (obj%h)
case (AN_PLOT)
call plot_clear (obj%p)
end select
end subroutine analysis_object_clear

```

Fill with data

Record data. The effect depends on the type of analysis object.

<Analysis: procedures>+≡

```

subroutine analysis_object_record_data (obj, &
x, y, yerr, xerr, weight, excess, success)
type(analysis_object_t), intent(inout) :: obj
real(default), intent(in) :: x
real(default), intent(in), optional :: y, yerr, xerr, weight, excess

```

```

logical, intent(out), optional :: success
select case (obj%type)
case (AN_OBSERVABLE)
  if (present (weight)) then
    call observable_record_value_weighted (obj%obs, x, weight, success)
  else
    call observable_record_value_unweighted (obj%obs, x, success)
  end if
case (AN_HISTOGRAM)
  if (present (weight)) then
    call histogram_record_value_weighted (obj%h, x, weight, success)
  else
    call histogram_record_value_unweighted (obj%h, x, excess, success)
  end if
case (AN_PLOT)
  if (present (y)) then
    call plot_record_value (obj%p, x, y, yerr, xerr, success)
  else
    if (present (success)) success = .false.
  end if
case default
  if (present (success)) success = .false.
end select
end subroutine analysis_object_record_data

```

Explicitly set the pointer to the next object in the list.

```

<Analysis: procedures>+≡
subroutine analysis_object_set_next_ptr (obj, next)
  type(analysis_object_t), intent(inout) :: obj
  type(analysis_object_t), pointer :: next
  obj%next => next
end subroutine analysis_object_set_next_ptr

```

Access contents

Return a pointer to the next object in the list.

```

<Analysis: procedures>+≡
function analysis_object_get_next_ptr (obj) result (next)
  type(analysis_object_t), pointer :: next
  type(analysis_object_t), intent(in) :: obj
  next => obj%next
end function analysis_object_get_next_ptr

```

Return data as appropriate for the object type.

```

<Analysis: procedures>+≡
function analysis_object_get_n_elements (obj) result (n)
  integer :: n
  type(analysis_object_t), intent(in) :: obj
  select case (obj%type)
  case (AN_HISTOGRAM)
    n = 1

```

```

case (AN_PLOT)
  n = 1
case (AN_GRAPH)
  n = graph_get_n_elements (obj%g)
case default
  n = 0
end select
end function analysis_object_get_n_elements

function analysis_object_get_n_entries (obj, within_bounds) result (n)
  integer :: n
  type(analysis_object_t), intent(in) :: obj
  logical, intent(in), optional :: within_bounds
  logical :: wb
  select case (obj%type)
  case (AN_OBSERVABLE)
    n = observable_get_n_entries (obj%obs)
  case (AN_HISTOGRAM)
    wb = .false.; if (present (within_bounds)) wb = within_bounds
    if (wb) then
      n = histogram_get_n_entries_within_bounds (obj%h)
    else
      n = histogram_get_n_entries (obj%h)
    end if
  case (AN_PLOT)
    n = plot_get_n_entries (obj%p)
  case default
    n = 0
  end select
end function analysis_object_get_n_entries

function analysis_object_get_average (obj, within_bounds) result (avg)
  real(default) :: avg
  type(analysis_object_t), intent(in) :: obj
  logical, intent(in), optional :: within_bounds
  logical :: wb
  select case (obj%type)
  case (AN_OBSERVABLE)
    avg = observable_get_average (obj%obs)
  case (AN_HISTOGRAM)
    wb = .false.; if (present (within_bounds)) wb = within_bounds
    if (wb) then
      avg = histogram_get_average_within_bounds (obj%h)
    else
      avg = histogram_get_average (obj%h)
    end if
  case default
    avg = 0
  end select
end function analysis_object_get_average

function analysis_object_get_error (obj, within_bounds) result (err)
  real(default) :: err
  type(analysis_object_t), intent(in) :: obj

```

```

logical, intent(in), optional :: within_bounds
logical :: wb
select case (obj%type)
case (AN_OBSERVABLE)
    err = observable_get_error (obj%obs)
case (AN_HISTOGRAM)
    wb = .false.; if (present (within_bounds)) wb = within_bounds
    if (wb) then
        err = histogram_get_error_within_bounds (obj%h)
    else
        err = histogram_get_error (obj%h)
    end if
case default
    err = 0
end select
end function analysis_object_get_error

```

Return pointers to the actual contents:

(Analysis: procedures)+≡

```

function analysis_object_get_observable_ptr (obj) result (obs)
    type(observable_t), pointer :: obs
    type(analysis_object_t), intent(in) :: obj
    select case (obj%type)
    case (AN_OBSERVABLE); obs => obj%obs
    case default;         obs => null ()
    end select
end function analysis_object_get_observable_ptr

function analysis_object_get_histogram_ptr (obj) result (h)
    type(histogram_t), pointer :: h
    type(analysis_object_t), intent(in) :: obj
    select case (obj%type)
    case (AN_HISTOGRAM); h => obj%h
    case default;       h => null ()
    end select
end function analysis_object_get_histogram_ptr

function analysis_object_get_plot_ptr (obj) result (plot)
    type(plot_t), pointer :: plot
    type(analysis_object_t), intent(in) :: obj
    select case (obj%type)
    case (AN_PLOT); plot => obj%p
    case default;   plot => null ()
    end select
end function analysis_object_get_plot_ptr

function analysis_object_get_graph_ptr (obj) result (g)
    type(graph_t), pointer :: g
    type(analysis_object_t), intent(in) :: obj
    select case (obj%type)
    case (AN_GRAPH); g => obj%g
    case default;   g => null ()
    end select
end function analysis_object_get_graph_ptr

```


Return true if the object has a graphical representation:

```

<Analysis: procedures>+≡
function analysis_object_has_plot (obj) result (flag)
  logical :: flag
  type(analysis_object_t), intent(in) :: obj
  select case (obj%type)
    case (AN_HISTOGRAM); flag = .true.
    case (AN_PLOT);      flag = .true.
    case (AN_GRAPH);     flag = .true.
    case default;        flag = .false.
  end select
end function analysis_object_has_plot

```

Output

```

<Analysis: procedures>+≡
subroutine analysis_object_write (obj, unit)
  type(analysis_object_t), intent(in) :: obj
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, "(A)") repeat ("#", 79)
  select case (obj%type)
    case (AN_OBSERVABLE)
      write (u, "(A)", advance="no") "# Observable:"
    case (AN_HISTOGRAM)
      write (u, "(A)", advance="no") "# Histogram: "
    case (AN_PLOT)
      write (u, "(A)", advance="no") "# Plot: "
    case (AN_GRAPH)
      write (u, "(A)", advance="no") "# Graph: "
    case default
      write (u, "(A)") "# [undefined analysis object]"
  end select
  return
  write (u, "(1x,A)") char (obj%id)
  select case (obj%type)
    case (AN_OBSERVABLE); call observable_write (obj%obs, unit)
    case (AN_HISTOGRAM);  call histogram_write (obj%h, unit)
    case (AN_PLOT);       call plot_write (obj%p, unit)
    case (AN_GRAPH);      call graph_write (obj%g, unit)
  end select
end subroutine analysis_object_write

```

Write the object part of the L^AT_EX driver file.

```

<Analysis: procedures>+≡
subroutine analysis_object_write_driver (obj, filename, unit)
  type(analysis_object_t), intent(in) :: obj
  type(string_t), intent(in) :: filename
  integer, intent(in), optional :: unit
  select case (obj%type)

```

```

case (AN_OBSERVABLE)
  call observable_write_driver (obj%obs, unit)
case (AN_HISTOGRAM)
  call histogram_write_gml_driver (obj%h, filename, unit)
case (AN_PLOT)
  call plot_write_gml_driver (obj%p, filename, unit)
case (AN_GRAPH)
  call graph_write_gml_driver (obj%g, filename, unit)
end select
end subroutine analysis_object_write_driver

```

Return a data header for external formats, in ifile form.

```

<Analysis: procedures>+≡
subroutine analysis_object_get_header (obj, header, comment)
  type(analysis_object_t), intent(in) :: obj
  type(ifile_t), intent(inout) :: header
  type(string_t), intent(in), optional :: comment
  select case (obj%type)
  case (AN_HISTOGRAM)
    call histogram_get_header (obj%h, header, comment)
  case (AN_PLOT)
    call plot_get_header (obj%p, header, comment)
  end select
end subroutine analysis_object_get_header

```

5.1.10 Analysis object iterator

Analysis objects are containers which have iterable data structures: histograms/bins and plots/points. If they are to be treated on a common basis, it is useful to have an iterator which hides the implementation details.

The iterator is used only for elementary analysis objects that contain plot data: histograms or plots. It is invalid for meta-objects (graphs) and non-graphical objects (observables).

```

<Analysis: public>+≡
  public :: analysis_iterator_t

<Analysis: types>+≡
  type :: analysis_iterator_t
  private
    integer :: type = AN_UNDEFINED
    type(analysis_object_t), pointer :: object => null ()
    integer :: index = 1
    type(point_t), pointer :: point => null ()
  end type

```

The initializer places the iterator at the beginning of the analysis object.

```

<Analysis: procedures>+≡
subroutine analysis_iterator_init (iterator, object)
  type(analysis_iterator_t), intent(out) :: iterator
  type(analysis_object_t), intent(in), target :: object
  iterator%object => object

```

```

    if (associated (iterator%object)) then
        iterator%type = iterator%object%type
        select case (iterator%type)
            case (AN_PLOT)
                iterator%point => iterator%object%p%first
            end select
        end if
    end if
end subroutine analysis_iterator_init

```

The iterator is valid as long as it points to an existing entry. An iterator for a data object without array data (observable) is always invalid.

```

<Analysis: public>+≡
    public :: analysis_iterator_is_valid

<Analysis: procedures>+≡
    function analysis_iterator_is_valid (iterator) result (valid)
        logical :: valid
        type(analysis_iterator_t), intent(in) :: iterator
        if (associated (iterator%object)) then
            select case (iterator%type)
                case (AN_HISTOGRAM)
                    valid = iterator%index <= histogram_get_n_bins (iterator%object%h)
                case (AN_PLOT)
                    valid = associated (iterator%point)
                case default
                    valid = .false.
            end select
        else
            valid = .false.
        end if
    end function analysis_iterator_is_valid

```

Advance the iterator.

```

<Analysis: public>+≡
    public :: analysis_iterator_advance

<Analysis: procedures>+≡
    subroutine analysis_iterator_advance (iterator)
        type(analysis_iterator_t), intent(inout) :: iterator
        if (associated (iterator%object)) then
            select case (iterator%type)
                case (AN_PLOT)
                    iterator%point => iterator%point%next
                end select
            iterator%index = iterator%index + 1
        end if
    end subroutine analysis_iterator_advance

```

Retrieve the object type:

```

<Analysis: public>+≡
    public :: analysis_iterator_get_type

```

```

<Analysis: procedures>+≡
function analysis_iterator_get_type (iterator) result (type)
    integer :: type
    type(analysis_iterator_t), intent(in) :: iterator
    type = iterator%type
end function analysis_iterator_get_type

```

Use the iterator to retrieve data. We implement a common routine which takes the data descriptors as optional arguments. Data which do not occur in the selected type trigger to an error condition.

The iterator must point to a valid entry.

```

<Analysis: public>+≡
public :: analysis_iterator_get_data

<Analysis: procedures>+≡
subroutine analysis_iterator_get_data (iterator, &
    x, y, yerr, xerr, width, excess, index, n_total)
    type(analysis_iterator_t), intent(in) :: iterator
    real(default), intent(out), optional :: x, y, yerr, xerr, width, excess
    integer, intent(out), optional :: index, n_total
    select case (iterator%type)
    case (AN_HISTOGRAM)
        if (present (x)) &
            x = bin_get_midpoint (iterator%object%h%bin(iterator%index))
        if (present (y)) &
            y = bin_get_sum (iterator%object%h%bin(iterator%index))
        if (present (yerr)) &
            yerr = bin_get_error (iterator%object%h%bin(iterator%index))
        if (present (xerr)) &
            call invalid ("histogram", "xerr")
        if (present (width)) &
            width = bin_get_width (iterator%object%h%bin(iterator%index))
        if (present (excess)) &
            excess = bin_get_excess (iterator%object%h%bin(iterator%index))
        if (present (index)) &
            index = iterator%index
        if (present (n_total)) &
            n_total = histogram_get_n_bins (iterator%object%h)
    case (AN_PLOT)
        if (present (x)) &
            x = point_get_x (iterator%point)
        if (present (y)) &
            y = point_get_y (iterator%point)
        if (present (yerr)) &
            yerr = point_get_yerr (iterator%point)
        if (present (xerr)) &
            xerr = point_get_xerr (iterator%point)
        if (present (width)) &
            call invalid ("plot", "width")
        if (present (excess)) &
            call invalid ("plot", "excess")
        if (present (index)) &
            index = iterator%index
        if (present (n_total)) &

```

```

        n_total = plot_get_n_entries (iterator%object%p)
    case default
        call msg_bug ("analysis_iterator_get_data: called " &
            // "for unsupported analysis object type")
    end select
contains
    subroutine invalid (typestr, objstr)
        character(*), intent(in) :: typestr, objstr
        call msg_bug ("analysis_iterator_get_data: attempt to get '" &
            // objstr // "' for type '" // typestr // "'")
    end subroutine invalid
end subroutine analysis_iterator_get_data

```

5.1.11 Analysis store

This data structure holds all observables, histograms and such that are currently active. We have one global store; individual items are identified by their ID strings and types.

<Analysis: variables>≡
 type(analysis_store_t), save :: analysis_store

<Analysis: types>+≡
 type :: analysis_store_t
 private
 type(analysis_object_t), pointer :: first => null ()
 type(analysis_object_t), pointer :: last => null ()
 end type analysis_store_t

Delete the analysis store

<Analysis: public>+≡
 public :: analysis_final

<Analysis: procedures>+≡
 subroutine analysis_final ()
 type(analysis_object_t), pointer :: current
 do while (associated (analysis_store%first))
 current => analysis_store%first
 analysis_store%first => current%next
 call analysis_object_final (current)
 end do
 analysis_store%last => null ()
 end subroutine analysis_final

Append a new analysis object

<Analysis: procedures>+≡
 subroutine analysis_store_append_object (id, type)
 type(string_t), intent(in) :: id
 integer, intent(in) :: type
 type(analysis_object_t), pointer :: obj
 allocate (obj)
 call analysis_object_init (obj, id, type)

```

    if (associated (analysis_store%last)) then
        analysis_store%last%next => obj
    else
        analysis_store%first => obj
    end if
    analysis_store%last => obj
end subroutine analysis_store_append_object

```

Return a pointer to the analysis object with given ID.

```

<Analysis: procedures>+≡
function analysis_store_get_object_ptr (id) result (obj)
    type(string_t), intent(in) :: id
    type(analysis_object_t), pointer :: obj
    obj => analysis_store%first
    do while (associated (obj))
        if (obj%id == id) return
        obj => obj%next
    end do
end function analysis_store_get_object_ptr

```

Initialize an analysis object: either reset it if present, or append a new entry.

```

<Analysis: procedures>+≡
subroutine analysis_store_init_object (id, type, obj)
    type(string_t), intent(in) :: id
    integer, intent(in) :: type
    type(analysis_object_t), pointer :: obj, next
    obj => analysis_store_get_object_ptr (id)
    if (associated (obj)) then
        next => analysis_object_get_next_ptr (obj)
        call analysis_object_final (obj)
        call analysis_object_init (obj, id, type)
        call analysis_object_set_next_ptr (obj, next)
    else
        call analysis_store_append_object (id, type)
        obj => analysis_store%last
    end if
end subroutine analysis_store_init_object

```

Get the type of a analysis object

```

<Analysis: public>+≡
public :: analysis_store_get_object_type

<Analysis: procedures>+≡
function analysis_store_get_object_type (id) result (type)
    type(string_t), intent(in) :: id
    integer :: type
    type(analysis_object_t), pointer :: object
    object => analysis_store_get_object_ptr (id)
    if (associated (object)) then
        type = object%type
    else
        type = AN_UNDEFINED
    end if
end function

```

```
end function analysis_store_get_object_type
```

Return the number of objects in the store.

```
<Analysis: procedures>+≡
function analysis_store_get_n_objects () result (n)
  integer :: n
  type(analysis_object_t), pointer :: current
  n = 0
  current => analysis_store%first
  do while (associated (current))
    n = n + 1
    current => current%next
  end do
end function analysis_store_get_n_objects
```

Allocate an array and fill it with all existing IDs.

```
<Analysis: public>+≡
public :: analysis_store_get_ids

<Analysis: procedures>+≡
subroutine analysis_store_get_ids (id)
  type(string_t), dimension(:), allocatable, intent(out) :: id
  type(analysis_object_t), pointer :: current
  integer :: i
  allocate (id (analysis_store_get_n_objects()))
  i = 0
  current => analysis_store%first
  do while (associated (current))
    i = i + 1
    id(i) = current%id
    current => current%next
  end do
end subroutine analysis_store_get_ids
```

5.1.12 L^AT_EX driver file

Write a driver file for all objects in the store.

```
<Analysis: procedures>+≡
subroutine analysis_store_write_driver_all (filename_data, unit)
  type(string_t), intent(in) :: filename_data
  integer, intent(in), optional :: unit
  type(analysis_object_t), pointer :: obj
  call analysis_store_write_driver_header (unit)
  obj => analysis_store%first
  do while (associated (obj))
    call analysis_object_write_driver (obj, filename_data, unit)
    obj => obj%next
  end do
  call analysis_store_write_driver_footer (unit)
end subroutine analysis_store_write_driver_all
```

Write a driver file for an array of objects.

<Analysis: procedures>+≡

```
subroutine analysis_store_write_driver_obj (filename_data, id, unit)
  type(string_t), intent(in) :: filename_data
  type(string_t), dimension(:), intent(in) :: id
  integer, intent(in), optional :: unit
  type(analysis_object_t), pointer :: obj
  integer :: i
  call analysis_store_write_driver_header (unit)
  do i = 1, size (id)
    obj => analysis_store_get_object_ptr (id(i))
    if (associated (obj)) &
      call analysis_object_write_driver (obj, filename_data, unit)
  end do
  call analysis_store_write_driver_footer (unit)
end subroutine analysis_store_write_driver_obj
```

The beginning of the driver file.

<Analysis: procedures>+≡

```
subroutine analysis_store_write_driver_header (unit)
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write(u, '(A)') "\documentclass[12pt]{article}"
  write(u, *)
  write(u, '(A)') "\usepackage{gamelan}"
  write(u, '(A)') "\usepackage{amsmath}"
  write(u, *)
  write(u, '(A)') "\begin{document}"
  write(u, '(A)') "\begin{gmlfile}"
  write(u, *)
  write(u, '(A)') "\begin{gmlcode}"
  write(u, '(A)') "  color col.default, col.excess;"
  write(u, '(A)') "  col.default = 0.9white;"
  write(u, '(A)') "  col.excess = red;"
  write(u, '(A)') "  boolean show_excess;"
!   if (mcs(1)%plot_excess .and. mcs(1)%unweighted) then
!     write(u, '(A)') "  show_excess = true;"
!   else
  write(u, '(A)') "  show_excess = false;"
!   end if
  write(u, '(A)') "\end{gmlcode}"
  write(u, *)
end subroutine analysis_store_write_driver_header
```

The end of the driver file.

<Analysis: procedures>+≡

```
subroutine analysis_store_write_driver_footer (unit)
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write(u, *)
  write(u, '(A)') "\end{gmlfile}"
```



```

write(u, '(A)') "\end{document}"
end subroutine analysis_store_write_driver_footer

```

5.1.13 API

Creating new objects

The specific versions below:

```

<Analysis: public>+≡
public :: analysis_init_observable

<Analysis: procedures>+≡
subroutine analysis_init_observable (id, obs_label, obs_unit, graph_options)
  type(string_t), intent(in) :: id
  type(string_t), intent(in), optional :: obs_label, obs_unit
  type(graph_options_t), intent(in), optional :: graph_options
  type(analysis_object_t), pointer :: obj
  type(observable_t), pointer :: obs
  call analysis_store_init_object (id, AN_OBSERVABLE, obj)
  obs => analysis_object_get_observable_ptr (obj)
  call observable_init (obs, obs_label, obs_unit, graph_options)
end subroutine analysis_init_observable

<Analysis: public>+≡
public :: analysis_init_histogram

<Analysis: interfaces>+≡
interface analysis_init_histogram
  module procedure analysis_init_histogram_n_bins
  module procedure analysis_init_histogram_bin_width
end interface

<Analysis: procedures>+≡
subroutine analysis_init_histogram_n_bins &
  (id, lower_bound, upper_bound, n_bins, normalize_bins, &
   obs_label, obs_unit, graph_options, drawing_options)
  type(string_t), intent(in) :: id
  real(default), intent(in) :: lower_bound, upper_bound
  integer, intent(in) :: n_bins
  logical, intent(in) :: normalize_bins
  type(string_t), intent(in), optional :: obs_label, obs_unit
  type(graph_options_t), intent(in), optional :: graph_options
  type(drawing_options_t), intent(in), optional :: drawing_options
  type(analysis_object_t), pointer :: obj
  type(histogram_t), pointer :: h
  call analysis_store_init_object (id, AN_HISTOGRAM, obj)
  h => analysis_object_get_histogram_ptr (obj)
  call histogram_init (h, id, &
    lower_bound, upper_bound, n_bins, normalize_bins, &
    obs_label, obs_unit, graph_options, drawing_options)
end subroutine analysis_init_histogram_n_bins

subroutine analysis_init_histogram_bin_width &

```

```

        (id, lower_bound, upper_bound, bin_width, normalize_bins, &
         obs_label, obs_unit, graph_options, drawing_options)
type(string_t), intent(in) :: id
real(default), intent(in) :: lower_bound, upper_bound, bin_width
logical, intent(in) :: normalize_bins
type(string_t), intent(in), optional :: obs_label, obs_unit
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
type(analysis_object_t), pointer :: obj
type(histogram_t), pointer :: h
call analysis_store_init_object (id, AN_HISTOGRAM, obj)
h => analysis_object_get_histogram_ptr (obj)
call histogram_init (h, id, &
                    lower_bound, upper_bound, bin_width, normalize_bins, &
                    obs_label, obs_unit, graph_options, drawing_options)
end subroutine analysis_init_histogram_bin_width

```

<Analysis: public>+≡

```
public :: analysis_init_plot
```

<Analysis: procedures>+≡

```

subroutine analysis_init_plot (id, graph_options, drawing_options)
type(string_t), intent(in) :: id
type(graph_options_t), intent(in), optional :: graph_options
type(drawing_options_t), intent(in), optional :: drawing_options
type(analysis_object_t), pointer :: obj
type(plot_t), pointer :: plot
call analysis_store_init_object (id, AN_PLOT, obj)
plot => analysis_object_get_plot_ptr (obj)
call plot_init (plot, id, graph_options, drawing_options)
end subroutine analysis_init_plot

```

<Analysis: public>+≡

```
public :: analysis_init_graph
```

<Analysis: procedures>+≡

```

subroutine analysis_init_graph (id, n_elements, graph_options)
type(string_t), intent(in) :: id
integer, intent(in) :: n_elements
type(graph_options_t), intent(in), optional :: graph_options
type(analysis_object_t), pointer :: obj
type(graph_t), pointer :: graph
call analysis_store_init_object (id, AN_GRAPH, obj)
graph => analysis_object_get_graph_ptr (obj)
call graph_init (graph, id, n_elements, graph_options)
end subroutine analysis_init_graph

```

Recording data

This procedure resets an object or the whole store to its initial state.

<Analysis: public>+≡

```
public :: analysis_clear
```

```

<Analysis: interfaces>+≡
interface analysis_clear
  module procedure analysis_store_clear_obj
  module procedure analysis_store_clear_all
end interface

```

```

<Analysis: procedures>+≡
subroutine analysis_store_clear_obj (id)
  type(string_t), intent(in) :: id
  type(analysis_object_t), pointer :: obj
  obj => analysis_store_get_object_ptr (id)
  if (associated (obj)) then
    call analysis_object_clear (obj)
  end if
end subroutine analysis_store_clear_obj

subroutine analysis_store_clear_all ()
  type(analysis_object_t), pointer :: obj
  obj => analysis_store%first
  do while (associated (obj))
    call analysis_object_clear (obj)
    obj => obj%next
  end do
end subroutine analysis_store_clear_all

```

There is one generic recording function whose behavior depends on the type of analysis object.

```

<Analysis: public>+≡
public :: analysis_record_data

<Analysis: procedures>+≡
subroutine analysis_record_data (id, x, y, yerr, xerr, &
  weight, excess, success, exist)
  type(string_t), intent(in) :: id
  real(default), intent(in) :: x
  real(default), intent(in), optional :: y, yerr, xerr, weight, excess
  logical, intent(out), optional :: success, exist
  type(analysis_object_t), pointer :: obj
  obj => analysis_store_get_object_ptr (id)
  if (associated (obj)) then
    call analysis_object_record_data (obj, x, y, yerr, xerr, &
      weight, excess, success)
    if (present (exist)) exist = .true.
  else
    if (present (success)) success = .false.
    if (present (exist)) exist = .false.
  end if
end subroutine analysis_record_data

```

Build a graph

This routine sets up the array of graph elements by copying the graph elements given as input. The object must exist and already be initialized as a graph.

<Analysis: public>+≡

```
public :: analysis_fill_graph
```

<Analysis: procedures>+≡

```
subroutine analysis_fill_graph (id, i, id_in, drawing_options)
  type(string_t), intent(in) :: id
  integer, intent(in) :: i
  type(string_t), intent(in) :: id_in
  type(drawing_options_t), intent(in), optional :: drawing_options
  type(analysis_object_t), pointer :: obj
  type(graph_t), pointer :: g
  type(histogram_t), pointer :: h
  type(plot_t), pointer :: p
  obj => analysis_store_get_object_ptr (id)
  g => analysis_object_get_graph_ptr (obj)
  obj => analysis_store_get_object_ptr (id_in)
  if (associated (obj)) then
    select case (obj%type)
    case (AN_HISTOGRAM)
      h => analysis_object_get_histogram_ptr (obj)
      call graph_insert_histogram (g, i, h, drawing_options)
    case (AN_PLOT)
      p => analysis_object_get_plot_ptr (obj)
      call graph_insert_plot (g, i, p, drawing_options)
    case default
      call msg_error ("Graph '" // char (id) // "': Element '" &
        // char (id_in) // "' is neither histogram nor plot.")
    end select
  else
    call msg_error ("Graph '" // char (id) // "': Element '" &
      // char (id_in) // "' is undefined.")
  end if
end subroutine analysis_fill_graph
```

Retrieve generic results

The following functions should work for all kinds of analysis object:

<Analysis: public>+≡

```
public :: analysis_get_n_elements
public :: analysis_get_n_entries
public :: analysis_get_average
public :: analysis_get_error
```

<Analysis: procedures>+≡

```
function analysis_get_n_elements (id) result (n)
  integer :: n
  type(string_t), intent(in) :: id
  type(analysis_object_t), pointer :: obj
  obj => analysis_store_get_object_ptr (id)
  if (associated (obj)) then
```

```

        n = analysis_object_get_n_elements (obj)
    else
        n = 0
    end if
end function analysis_get_n_elements

function analysis_get_n_entries (id, within_bounds) result (n)
    integer :: n
    type(string_t), intent(in) :: id
    logical, intent(in), optional :: within_bounds
    type(analysis_object_t), pointer :: obj
    obj => analysis_store_get_object_ptr (id)
    if (associated (obj)) then
        n = analysis_object_get_n_entries (obj, within_bounds)
    else
        n = 0
    end if
end function analysis_get_n_entries

function analysis_get_average (id, within_bounds) result (avg)
    real(default) :: avg
    type(string_t), intent(in) :: id
    type(analysis_object_t), pointer :: obj
    logical, intent(in), optional :: within_bounds
    obj => analysis_store_get_object_ptr (id)
    if (associated (obj)) then
        avg = analysis_object_get_average (obj, within_bounds)
    else
        avg = 0
    end if
end function analysis_get_average

function analysis_get_error (id, within_bounds) result (err)
    real(default) :: err
    type(string_t), intent(in) :: id
    type(analysis_object_t), pointer :: obj
    logical, intent(in), optional :: within_bounds
    obj => analysis_store_get_object_ptr (id)
    if (associated (obj)) then
        err = analysis_object_get_error (obj, within_bounds)
    else
        err = 0
    end if
end function analysis_get_error

```

Return true if any analysis object is graphical

<Analysis: public>+≡

```
public :: analysis_has_plots
```

<Analysis: interfaces>+≡

```
interface analysis_has_plots
    module procedure analysis_has_plots_any
    module procedure analysis_has_plots_obj
end interface

```

<Analysis: procedures>+≡

```

function analysis_has_plots_any () result (flag)
    logical :: flag
    type(analysis_object_t), pointer :: obj
    flag = .false.
    obj => analysis_store%first
    do while (associated (obj))
        flag = analysis_object_has_plot (obj)
        if (flag) return
    end do
end function analysis_has_plots_any

function analysis_has_plots_obj (id) result (flag)
    logical :: flag
    type(string_t), dimension(:), intent(in) :: id
    type(analysis_object_t), pointer :: obj
    integer :: i
    flag = .false.
    do i = 1, size (id)
        obj => analysis_store_get_object_ptr (id(i))
        if (associated (obj)) then
            flag = analysis_object_has_plot (obj)
            if (flag) return
        end if
    end do
end function analysis_has_plots_obj

```

Iterators

Initialize an iterator for the given object. If the object does not exist or has wrong type, the iterator will be invalid.

<Analysis: public>+≡

```

public :: analysis_init_iterator

```

<Analysis: procedures>+≡

```

subroutine analysis_init_iterator (id, iterator)
    type(string_t), intent(in) :: id
    type(analysis_iterator_t), intent(out) :: iterator
    type(analysis_object_t), pointer :: obj
    obj => analysis_store_get_object_ptr (id)
    if (associated (obj)) call analysis_iterator_init (iterator, obj)
end subroutine analysis_init_iterator

```

Output

<Analysis: public>+≡

```

public :: analysis_write

```

```

<Analysis: interfaces>+≡
    interface analysis_write
        module procedure analysis_write_object
        module procedure analysis_write_all
    end interface

<Analysis: procedures>+≡
    subroutine analysis_write_object (id, unit)
        type(string_t), intent(in) :: id
        integer, intent(in), optional :: unit
        type(analysis_object_t), pointer :: obj
        obj => analysis_store_get_object_ptr (id)
        if (associated (obj)) then
            call analysis_object_write (obj, unit)
        else
            call msg_error ("Analysis object '" // char (id) // "' not found")
        end if
    end subroutine analysis_write_object

    subroutine analysis_write_all (unit)
        integer, intent(in), optional :: unit
        type(analysis_object_t), pointer :: obj
        integer :: u
        u = output_unit (unit); if (u < 0) return
        obj => analysis_store%first
        do while (associated (obj))
            call analysis_object_write (obj, unit)
            obj => obj%next
        end do
    end subroutine analysis_write_all

<Analysis: public>+≡
    public :: analysis_write_driver

<Analysis: procedures>+≡
    subroutine analysis_write_driver (filename_data, id, unit)
        type(string_t), intent(in) :: filename_data
        type(string_t), dimension(:), intent(in), optional :: id
        integer, intent(in), optional :: unit
        if (present (id)) then
            call analysis_store_write_driver_obj (filename_data, id, unit)
        else
            call analysis_store_write_driver_all (filename_data, unit)
        end if
    end subroutine analysis_write_driver

<Analysis: public>+≡
    public :: analysis_compile_tex

<Analysis: procedures>+≡
    subroutine analysis_compile_tex (file, has_gmlcode, os_data)
        type(string_t), intent(in) :: file
        logical, intent(in) :: has_gmlcode
        type(os_data_t), intent(in) :: os_data

```

```

type(string_t) :: setenv
integer :: status
if (os_data%event_analysis_ps) then
  BLOCK: do
    if (os_data%whizard_texpath /= "") then
      setenv = "TEXINPUTS=" // os_data%whizard_texpath // ":$TEXINPUTS "
    else
      setenv = ""
    end if
    call os_system_call (setenv // os_data%latex // " " // file, status)
    if (status /= 0) exit BLOCK
    if (has_gmlcode) then
      call os_system_call (os_data%gml // " " // file, status)
      if (status /= 0) exit BLOCK
      call os_system_call (setenv // os_data%latex // " " // file, &
        status)
      if (status /= 0) exit BLOCK
    end if
    call os_system_call (os_data%dvips // " -o " // file // ".ps " &
      // file, status)
    if (status /= 0) exit BLOCK
    if (os_data%event_analysis_pdf) then
      call os_system_call (os_data%ps2pdf // " " // file // ".ps", &
        status)
      if (status /= 0) exit BLOCK
    end if
    exit BLOCK
  end do BLOCK
  if (status /= 0) then
    call msg_error ("Unable to compile analysis output file")
  end if
else
  call msg_warning ("Skipping results display because " &
    // "latex/mpost/dvips is not available")
end if
end subroutine analysis_compile_tex

```

Write header for generic data output to an ifile.

<Analysis: public>+≡

```
public :: analysis_get_header
```

<Analysis: procedures>+≡

```

subroutine analysis_get_header (id, header, comment)
  type(string_t), intent(in) :: id
  type(ifile_t), intent(inout) :: header
  type(string_t), intent(in), optional :: comment
  type(analysis_object_t), pointer :: object
  object => analysis_store_get_object_ptr (id)
  if (associated (object)) then
    call analysis_object_get_header (object, header, comment)
  end if
end subroutine analysis_get_header

```


5.1.14 Test

```
<Analysis: public>+≡
    public :: analysis_test

<Analysis: procedures>+≡
    subroutine analysis_test ()
        call analysis_test1 ()
        call analysis_final ()
    end subroutine analysis_test

<Analysis: procedures>+≡
    subroutine analysis_test1 ()
        type(string_t) :: id1, id2, id3, id4
        integer :: i
        id1 = "foo"
        id2 = "bar"
        id3 = "hist"
        id4 = "plot"
        call analysis_init_observable (id1)
        call analysis_init_observable (id2)
        call analysis_init_histogram_bin_width &
            (id3, 0.5_default, 5.5_default, 1._default, normalize_bins=.false.)
        call analysis_init_plot (id4)
        do i = 1, 3
            print *, "data = ", real(i,default)
            call analysis_record_data (id1, real(i,default))
            call analysis_record_data (id2, real(i,default), &
                weight=real(i,default))
            call analysis_record_data (id3, real(i,default))
            call analysis_record_data (id4, real(i,default), real(i,default)**2)
        end do
1    format (A,10(1x,I5))
2    format (A,10(1x,F5.3))
        print 1, "n_entries = ", &
            analysis_get_n_entries (id1), &
            analysis_get_n_entries (id2), &
            analysis_get_n_entries (id3), &
            analysis_get_n_entries (id3, within_bounds = .true.), &
            analysis_get_n_entries (id4), &
            analysis_get_n_entries (id4, within_bounds = .true.)
        print 2, "average   = ", &
            analysis_get_average (id1), &
            analysis_get_average (id2), &
            analysis_get_average (id3), &
            analysis_get_average (id3, within_bounds = .true.)
        print 2, "error     = ", &
            analysis_get_error (id1), &
            analysis_get_error (id2), &
            analysis_get_error (id3), &
            analysis_get_error (id3, within_bounds = .true.)
        print *, "clear #2"
        call analysis_clear (id2)
        do i = 4, 6
            print *, "data = ", real(i,default)
```

```

        call analysis_record_data (id1, real(i,default))
        call analysis_record_data (id2, real(i,default), &
                                   weight=real(i,default))
        call analysis_record_data (id3, real(i,default))
        call analysis_record_data (id4, real(i,default), real(i,default)**2)
    end do
    print 1, "n_entries = ", &
        analysis_get_n_entries (id1), &
        analysis_get_n_entries (id2), &
        analysis_get_n_entries (id3), &
        analysis_get_n_entries (id3, within_bounds = .true.), &
        analysis_get_n_entries (id4), &
        analysis_get_n_entries (id4, within_bounds = .true.)
    print 2, "average   = ", &
        analysis_get_average (id1), &
        analysis_get_average (id2), &
        analysis_get_average (id3), &
        analysis_get_average (id3, within_bounds = .true.)
    print 2, "error     = ", &
        analysis_get_error (id1), &
        analysis_get_error (id2), &
        analysis_get_error (id3), &
        analysis_get_error (id3, within_bounds = .true.)
    print *
    call analysis_write ()
    call analysis_clear ()
end subroutine analysis_test1

```

5.2 PDG arrays

For defining aliases, we introduce a special type which holds a set of (integer) PDG codes.

```
<pdg_arrays.f90>≡  
<File header>  
  
module pdg_arrays  
  
<Use file utils>  
  
<Standard module head>  
  
<PDG arrays: public>  
  
<PDG arrays: parameters>  
  
<PDG arrays: types>  
  
<PDG arrays: interfaces>  
  
contains  
  
<PDG arrays: procedures>  
  
end module pdg_arrays
```

5.2.1 Type definition

Using an allocatable array eliminates the need for initializer and/or finalizer.

```
<PDG arrays: public>≡  
public :: pdg_array_t  
  
<PDG arrays: types>≡  
type :: pdg_array_t  
private  
integer, dimension(:), allocatable :: pdg  
end type pdg_array_t
```

Output

```
<PDG arrays: public>+≡  
public :: pdg_array_write  
  
<PDG arrays: procedures>≡  
subroutine pdg_array_write (aval, unit)  
type(pdg_array_t), intent(in) :: aval  
integer, intent(in), optional :: unit  
integer :: u, i  
u = output_unit (unit); if (u < 0) return  
write (u, "(A)", advance="no") "PDG("  
if (allocated (aval%pdg)) then  
do i = 1, size (aval%pdg)  
if (i > 1) write (u, "(A)", advance="no") " , "
```

```

        write (u, "(I0)", advance="no")  aval%pdg(i)
    end do
end if
write (u, "(A)", advance="no")  ")"
end subroutine pdg_array_write

```

5.2.2 Parameters

We need an UNDEFINED value:

```

(PDG arrays: parameters)≡
    integer, parameter, public :: UNDEFINED = 0

```

5.2.3 Basic operations

Assignment. We define assignment from and to an integer array. Note that the integer array, if it is the l.h.s., must be declared allocatable by the caller.

```

(PDG arrays: public)+≡
    public :: assignment(=)

(PDG arrays: interfaces)≡
    interface assignment(=)
        module procedure pdg_array_from_int_array
        module procedure pdg_array_from_int
        module procedure int_array_from_pdg_array
    end interface

(PDG arrays: procedures)+≡
    subroutine pdg_array_from_int_array (aval, iarray)
        type(pdg_array_t), intent(out) :: aval
        integer, dimension(:), intent(in) :: iarray
        allocate (aval%pdg (size (iarray)))
        aval%pdg = iarray
    end subroutine pdg_array_from_int_array

    elemental subroutine pdg_array_from_int (aval, int)
        type(pdg_array_t), intent(out) :: aval
        integer, intent(in) :: int
        allocate (aval%pdg (1))
        aval%pdg = int
    end subroutine pdg_array_from_int

    subroutine int_array_from_pdg_array (iarray, aval)
        integer, dimension(:), allocatable, intent(out) :: iarray
        type(pdg_array_t), intent(in) :: aval
        if (allocated (aval%pdg)) then
            allocate (iarray (size (aval%pdg)))
            iarray = aval%pdg
        else
            allocate (iarray (0))
        end if
    end subroutine int_array_from_pdg_array

```

The only nontrivial operation: concatenate two PDG arrays

```

(PDG arrays: public)+≡
    public :: operator(//)

(PDG arrays: interfaces)+≡
    interface operator(//)
        module procedure concat_pdg_arrays
    end interface

(PDG arrays: procedures)+≡
    function concat_pdg_arrays (aval1, aval2) result (aval)
        type(pdg_array_t) :: aval
        type(pdg_array_t), intent(in) :: aval1, aval2
        integer :: n1, n2
        if (allocated (aval1%pdg) .and. allocated (aval2%pdg)) then
            n1 = size (aval1%pdg)
            n2 = size (aval2%pdg)
            allocate (aval%pdg (n1 + n2))
            aval%pdg(:n1) = aval1%pdg
            aval%pdg(n1+1:) = aval2%pdg
        else if (allocated (aval1%pdg)) then
            aval = aval1
        else if (allocated (aval2%pdg)) then
            aval = aval2
        end if
    end function concat_pdg_arrays

```

5.2.4 Matching

A PDG array matches a given PDG code if the code is present within the array. If either one is zero (UNDEFINED), the match also succeeds.

```

(PDG arrays: public)+≡
    public :: operator(.match.)

(PDG arrays: interfaces)+≡
    interface operator(.match.)
        module procedure pdg_array_match_integer
    end interface

(PDG arrays: procedures)+≡
    elemental function pdg_array_match_integer (aval, pdg) result (flag)
        logical :: flag
        type(pdg_array_t), intent(in) :: aval
        integer, intent(in) :: pdg
        if (allocated (aval%pdg)) then
            flag = pdg == UNDEFINED &
                .or. any (aval%pdg == UNDEFINED) &
                .or. any (aval%pdg == pdg)
        else
            flag = .false.
        end if
    end function pdg_array_match_integer

```

Equivalence. Two PDG arrays are equivalent if either both contain UNDEFINED or each element of array 1 is present in array 2, and vice versa.

```

(PDG arrays: public)+≡
    public :: operator(.eqv.)
    public :: operator(.neqv.)

(PDG arrays: interfaces)+≡
    interface operator(.eqv.)
        module procedure pdg_array_equivalent
    end interface
    interface operator(.neqv.)
        module procedure pdg_array_inequivalent
    end interface

(PDG arrays: procedures)+≡
    function pdg_array_equivalent (aval1, aval2) result (eq)
        logical :: eq
        type(pdg_array_t), intent(in) :: aval1, aval2
        logical, dimension(:), allocatable :: match1, match2
        integer :: i
        if (allocated (aval1%pdg) .and. allocated (aval2%pdg)) then
            eq = any (aval1%pdg == UNDEFINED) &
                .and. any (aval2%pdg == UNDEFINED)
            if (.not. eq) then
                allocate (match1 (size (aval1%pdg)))
                allocate (match2 (size (aval2%pdg)))
                match1 = .false.
                match2 = .false.
                do i = 1, size (aval1%pdg)
                    match2 = match2 .or. aval1%pdg(i) == aval2%pdg
                end do
                do i = 1, size (aval2%pdg)
                    match1 = match1 .or. aval2%pdg(i) == aval1%pdg
                end do
                eq = all (match1) .and. all (match2)
            end if
        else
            eq = .false.
        end if
    end function pdg_array_equivalent

    function pdg_array_inequivalent (aval1, aval2) result (neq)
        logical :: neq
        type(pdg_array_t), intent(in) :: aval1, aval2
        neq = .not. pdg_array_equivalent (aval1, aval2)
    end function pdg_array_inequivalent

```

5.3 subevents

The purpose of subevents is to store the relevant part of the physical event (either partonic or hadronic), and to hold particle selections and combinations which are constructed in cut or analysis expressions.

```
<subevents.f90>≡  
  <File header>  
  
  module subevents  
  
    use iso_c_binding !NODEP!  
    <Use kinds>  
    <Use file utils>  
    use c_particles !NODEP!  
    use lorentz !NODEP!  
    use sorting  
    use pdg_arrays  
  
    <Standard module head>  
  
    <Subevents: public>  
  
    <Subevents: parameters>  
  
    <Subevents: types>  
  
    <Subevents: interfaces>  
  
  contains  
  
    <Subevents: procedures>  
  
  end module subevents
```

5.3.1 Particles

For the purpose of this module, a particle has a type which can indicate a beam, incoming, outgoing, or composite particle, flavor and helicity codes (integer, undefined for composite), four-momentum and invariant mass squared. (Other particles types are used in extended event types, but also defined here.) Furthermore, each particle has an allocatable array of ancestors – particle indices which indicate the building blocks of a composite particle. For an incoming/outgoing particle, the array contains only the index of the particle itself.

For incoming particles, the momentum is inverted before storing it in the particle object.

```
<Subevents: parameters>≡  
  integer, parameter, public :: PRT_UNDEFINED = 0  
  integer, parameter, public :: PRT_BEAM = -9  
  integer, parameter, public :: PRT_INCOMING = 1  
  integer, parameter, public :: PRT_OUTGOING = 2  
  integer, parameter, public :: PRT_COMPOSITE = 3  
  integer, parameter, public :: PRT_VIRTUAL = 4
```

```

integer, parameter, public :: PRT_RESONANT = 5
integer, parameter, public :: PRT_BEAM_REMNANT = 9

```

The type

We initialize only the type here and mark as unpolarized. The initializers below do the rest.

```

<Subevents: public>≡
  public :: prt_t

<Subevents: types>≡
  type :: prt_t
    private
    integer :: type = PRT_UNDEFINED
    integer :: pdg
    logical :: polarized = .false.
    integer :: h
    type(vector4_t) :: p
    real(default) :: p2
    integer, dimension(:), allocatable :: src
  end type prt_t

```

Initializers. Polarization is set separately. Finalizers are not needed.

```

<Subevents: procedures>≡
  subroutine prt_init_beam (prt, pdg, p, p2, src)
    type(prt_t), intent(out) :: prt
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: p2
    integer, dimension(:), intent(in) :: src
    prt%type = PRT_BEAM
    call prt_set (prt, pdg, - p, p2, src)
  end subroutine prt_init_beam

  subroutine prt_init_incoming (prt, pdg, p, p2, src)
    type(prt_t), intent(out) :: prt
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: p2
    integer, dimension(:), intent(in) :: src
    prt%type = PRT_INCOMING
    call prt_set (prt, pdg, - p, p2, src)
  end subroutine prt_init_incoming

  subroutine prt_init_outgoing (prt, pdg, p, p2, src)
    type(prt_t), intent(out) :: prt
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: p2
    integer, dimension(:), intent(in) :: src
    prt%type = PRT_OUTGOING
    call prt_set (prt, pdg, p, p2, src)
  end subroutine prt_init_outgoing

```



```

end subroutine prt_init_outgoing

subroutine prt_init_composite (prt, p, src)
  type(prt_t), intent(out) :: prt
  type(vector4_t), intent(in) :: p
  integer, dimension(:), intent(in) :: src
  prt%type = PRT_COMPOSITE
  call prt_set (prt, 0, p, p**2, src)
end subroutine prt_init_composite

```

This version is for temporary particle objects, so the `src` array is not set.

```

<Subevents: public>+≡
  public :: prt_init_combine

<Subevents: procedures>+≡
  subroutine prt_init_combine (prt, prt1, prt2)
    type(prt_t), intent(out) :: prt
    type(prt_t), intent(in) :: prt1, prt2
    type(vector4_t) :: p
    integer, dimension(0) :: src
    prt%type = PRT_COMPOSITE
    p = prt1%p + prt2%p
    call prt_set (prt, 0, p, p**2, src)
  end subroutine prt_init_combine

```

Accessing contents

```

<Subevents: public>+≡
  public :: prt_get_pdg

<Subevents: procedures>+≡
  elemental function prt_get_pdg (prt) result (pdg)
    integer :: pdg
    type(prt_t), intent(in) :: prt
    pdg = prt%pdg
  end function prt_get_pdg

<Subevents: public>+≡
  public :: prt_get_momentum

<Subevents: procedures>+≡
  elemental function prt_get_momentum (prt) result (p)
    type(vector4_t) :: p
    type(prt_t), intent(in) :: prt
    p = prt%p
  end function prt_get_momentum

<Subevents: public>+≡
  public :: prt_get_msq

<Subevents: procedures>+≡
  elemental function prt_get_msq (prt) result (msq)
    real(default) :: msq
    type(prt_t), intent(in) :: prt

```

```

        msq = prt%p2
    end function prt_get_msq

<Subevents: public>+≡
    public :: prt_is_polarized

<Subevents: procedures>+≡
    elemental function prt_is_polarized (prt) result (flag)
        logical :: flag
        type(prt_t), intent(in) :: prt
        flag = prt%polarized
    end function prt_is_polarized

<Subevents: public>+≡
    public :: prt_get_helicity

<Subevents: procedures>+≡
    elemental function prt_get_helicity (prt) result (h)
        integer :: h
        type(prt_t), intent(in) :: prt
        h = prt%h
    end function prt_get_helicity

```

Setting data

Set the PDG, momentum and momentum squared, and ancestors. If allocation-on-assignment is available, this can be simplified.

```

<Subevents: procedures>+≡
    subroutine prt_set (prt, pdg, p, p2, src)
        type(prt_t), intent(inout) :: prt
        integer, intent(in) :: pdg
        type(vector4_t), intent(in) :: p
        real(default), intent(in) :: p2
        integer, dimension(:), intent(in) :: src
        prt%pdg = pdg
        prt%p = p
        prt%p2 = p2
        if (allocated (prt%src)) then
            if (size (src) /= size (prt%src)) then
                deallocate (prt%src)
                allocate (prt%src (size (src)))
            end if
        else
            allocate (prt%src (size (src)))
        end if
        prt%src = src
    end subroutine prt_set

```

Set the particle PDG code separately.

```

<Subevents: procedures>+≡
    elemental subroutine prt_set_pdg (prt, pdg)
        type(prt_t), intent(inout) :: prt

```

```

        integer, intent(in) :: pdg
        prt%pdg = pdg
    end subroutine prt_set_pdg

```

Set the momentum separately.

```

<Subevents: procedures>+≡
    elemental subroutine prt_set_p (prt, p)
        type(prt_t), intent(inout) :: prt
        type(vector4_t), intent(in) :: p
        prt%p = p
    end subroutine prt_set_p

```

Set helicity (optional).

```

<Subevents: procedures>+≡
    subroutine prt_polarize (prt, h)
        type(prt_t), intent(inout) :: prt
        integer, intent(in) :: h
        prt%polarized = .true.
        prt%h = h
    end subroutine prt_polarize

```

Conversion

Transform a `prt_t` object into a `c_prt_t` object.

```

<Subevents: public>+≡
    public :: c_prt

<Subevents: interfaces>≡
    interface c_prt
        module procedure c_prt_from_prt
    end interface

<Subevents: procedures>+≡
    elemental function c_prt_from_prt (prt) result (c_prt)
        type(c_prt_t) :: c_prt
        type(prt_t), intent(in) :: prt
        c_prt%type = prt%type
        c_prt%pdg = prt%pdg
        if (prt%polarized) then
            c_prt%polarized = 1
        else
            c_prt%polarized = 0
        end if
        c_prt%h = prt%h
        c_prt%pe = energy (prt%p)
        c_prt%px = vector4_get_component (prt%p, 1)
        c_prt%py = vector4_get_component (prt%p, 2)
        c_prt%pz = vector4_get_component (prt%p, 3)
        c_prt%p2 = prt%p2
    end function c_prt_from_prt

```

Output

<Subevents: public>+≡

```
public :: prt_write
```

<Subevents: procedures>+≡

```
subroutine prt_write (prt, unit)
  type(prt_t), intent(in) :: prt
  integer, intent(in), optional :: unit
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, "(1x,A)", advance="no") "prt("
  select case (prt%type)
  case (PRT_UNDEFINED); write (u, "('?')", advance="no")
  case (PRT_BEAM); write (u, "('b:~')", advance="no")
  case (PRT_INCOMING); write (u, "('i:~')", advance="no")
  case (PRT_OUTGOING); write (u, "('o:~')", advance="no")
  case (PRT_COMPOSITE); write (u, "('c:~')", advance="no")
  end select
  select case (prt%type)
  case (PRT_BEAM, PRT_INCOMING, PRT_OUTGOING)
    if (prt%polarized) then
      write (u, "(I0,'/',I0,'|')", advance="no") prt%pdg, prt%h
    else
      write (u, "(I0,'|')", advance="no") prt%pdg
    end if
  end select
  select case (prt%type)
  case (PRT_BEAM, PRT_INCOMING, PRT_OUTGOING, PRT_COMPOSITE)
    write (u, "(1PE12.5,';',',1PE12.5,';',',1PE12.5,';',',1PE12.5)", advance="no") &
      array_from_vector4 (prt%p)
    write (u, "('|',1PE12.5)", advance="no") prt%p2
  end select
  if (allocated (prt%src)) then
    write (u, "('|')", advance="no")
    do i = 1, size (prt%src)
      write (u, "(1x,I0)", advance="no") prt%src(i)
    end do
  end if
  write (u, "(A)" ) " )"
end subroutine prt_write
```

Tools

Two particles match if their `src` arrays are the same.

<Subevents: interfaces>+≡

```
interface operator(.match.)
  module procedure prt_match
end interface
```

<Subevents: procedures>+≡

```
elemental function prt_match (prt1, prt2) result (match)
  logical :: match
```

```

type(prt_t), intent(in) :: prt1, prt2
if (size (prt1%src) == size (prt2%src)) then
  match = all (prt1%src == prt2%src)
else
  match = .false.
end if
end function prt_match

```

The combine operation makes a pseudoparticle whose momentum is the result of adding (the momenta of) the pair of input particles. We trace the particles from which a particle is built by storing a `src` array. Each particle entry in the `src` list contains a list of indices which indicates its building blocks. The indices refer to an original list of particles. Index lists are sorted, and they contain no element more than once.

We thus require that in a given pseudoparticle, each original particle occurs at most once.

The result is `intent(inout)`, so it will not be initialized when the subroutine is entered.

```

<Subevents: procedures>+≡
subroutine prt_combine (prt, prt_in1, prt_in2, ok)
  type(prt_t), intent(inout) :: prt
  type(prt_t), intent(in) :: prt_in1, prt_in2
  logical :: ok
  integer, dimension(:), allocatable :: src
  call combine_index_lists (src, prt_in1%src, prt_in2%src)
  ok = allocated (src)
  if (ok) call prt_init_composite (prt, prt_in1%p + prt_in2%p, src)
end subroutine prt_combine

```

This variant does not produce the combined particle, it just checks whether the combination is valid (no common `src` entry).

```

<Subevents: public>+≡
public :: are_disjoint

<Subevents: procedures>+≡
function are_disjoint (prt_in1, prt_in2) result (flag)
  logical :: flag
  type(prt_t), intent(in) :: prt_in1, prt_in2
  flag = index_lists_are_disjoint (prt_in1%src, prt_in2%src)
end function are_disjoint

```

`src` Lists with length > 1 are built by a `combine` operation which merges the lists in a sorted manner. If the result would have a duplicate entry, it is discarded, and the result is unallocated.

```

<Subevents: procedures>+≡
subroutine combine_index_lists (res, src1, src2)
  integer, dimension(:), intent(in) :: src1, src2
  integer, dimension(:), allocatable :: res
  integer :: i1, i2, i
  allocate (res (size (src1) + size (src2)))
  i1 = 1

```

```

i2 = 1
LOOP: do i = 1, size (res)
  if (src1(i1) < src2(i2)) then
    res(i) = src1(i1); i1 = i1 + 1
    if (i1 > size (src1)) then
      res(i+1:) = src2(i2:)
      exit LOOP
    end if
  else if (src1(i1) > src2(i2)) then
    res(i) = src2(i2); i2 = i2 + 1
    if (i2 > size (src2)) then
      res(i+1:) = src1(i1:)
      exit LOOP
    end if
  else
    deallocate (res)
    exit LOOP
  end if
end do LOOP
end subroutine combine_index_lists

```

This function is similar, but it does not actually merge the list, it just checks whether they are disjoint (no common `src` entry).

(Subevents: procedures)+≡

```

function index_lists_are_disjoint (src1, src2) result (flag)
  logical :: flag
  integer, dimension(:), intent(in) :: src1, src2
  integer :: i1, i2, i
  flag = .true.
  i1 = 1
  i2 = 1
  LOOP: do i = 1, size (src1) + size (src2)
    if (src1(i1) < src2(i2)) then
      i1 = i1 + 1
      if (i1 > size (src1)) then
        exit LOOP
      end if
    else if (src1(i1) > src2(i2)) then
      i2 = i2 + 1
      if (i2 > size (src2)) then
        exit LOOP
      end if
    else
      flag = .false.
      exit LOOP
    end if
  end do LOOP
end function index_lists_are_disjoint

```

5.3.2 C-compatible particle type

5.3.3 subevents

Particles are collected in subevents. This type is implemented as a dynamically allocated array, which need not be completely filled. The value `n_tot` determines the number of meaningful entries.

Type definition

```
<Subevents: public>+≡
  public :: subevt_t

<Subevents: types>+≡
  type :: subevt_t
  private
    integer :: n_tot = 0
    type(prt_t), dimension(:), allocatable :: prt
  end type subevt_t
```

Initialize, allocating with size zero (default) or given size. The number of contained particles is set equal to the size.

```
<Subevents: public>+≡
  public :: subevt_init

<Subevents: procedures>+≡
  subroutine subevt_init (subevt, n_tot)
    type(subevt_t), intent(out) :: subevt
    integer, intent(in), optional :: n_tot
    if (present (n_tot)) subevt%n_tot = n_tot
    allocate (subevt%prt (subevt%n_tot))
  end subroutine subevt_init
```

(Re-)allocate the subevent with some given size. If the size is greater than the previous one, do a real reallocation. Otherwise, just reset the recorded size. Contents are untouched, but become invalid.

```
<Subevents: public>+≡
  public :: subevt_reset

<Subevents: procedures>+≡
  subroutine subevt_reset (subevt, n_tot)
    type(subevt_t), intent(inout) :: subevt
    integer, intent(in) :: n_tot
    subevt%n_tot = n_tot
    if (subevt%n_tot > size (subevt%prt)) then
      deallocate (subevt%prt)
      allocate (subevt%prt (subevt%n_tot))
    end if
  end subroutine subevt_reset
```

Output.

```
<Subevents: public>+≡
  public :: subevt_write
```

```

<Subevents: procedures>+≡
subroutine subevt_write (subevt, unit, prefix)
  type(subevt_t), intent(in) :: subevt
  integer, intent(in), optional :: unit
  character(*), intent(in), optional :: prefix
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, *) "subevent:"
  do i = 1, subevt%n_tot
    if (present (prefix)) write (u, "(A)", advance="no") prefix
    write (u, "(1x,I0)", advance="no") i
    call prt_write (subevt%prt(i), unit)
  end do
end subroutine subevt_write

```

Defined assignment: transfer only meaningful entries. This is a deep copy (as would be default assignment).

```

<Subevents: interfaces>+≡
interface assignment(=)
  module procedure subevt_assign
end interface

```

```

<Subevents: procedures>+≡
subroutine subevt_assign (subevt, subevt_in)
  type(subevt_t), intent(inout) :: subevt
  type(subevt_t), intent(in) :: subevt_in
  if (.not. allocated (subevt%prt)) then
    call subevt_init (subevt, subevt_in%n_tot)
  else
    call subevt_reset (subevt, subevt_in%n_tot)
  end if
  subevt%prt(:subevt%n_tot) = subevt_in%prt(:subevt%n_tot)
end subroutine subevt_assign

```

Fill contents

Store incoming/outgoing particles which are completely defined.

```

<Subevents: public>+≡
public :: subevt_set_beam
public :: subevt_set_incoming
public :: subevt_set_outgoing
public :: subevt_set_composite

<Subevents: procedures>+≡
subroutine subevt_set_beam (subevt, i, pdg, p, p2, src)
  type(subevt_t), intent(inout) :: subevt
  integer, intent(in) :: i
  integer, intent(in) :: pdg
  type(vector4_t), intent(in) :: p
  real(default), intent(in) :: p2
  integer, dimension(:), intent(in), optional :: src
  if (present (src)) then

```



```

        call prt_init_beam (subevt%prt(i), pdg, p, p2, src)
    else
        call prt_init_beam (subevt%prt(i), pdg, p, p2, (/ i /))
    end if
end subroutine subevt_set_beam

subroutine subevt_set_incoming (subevt, i, pdg, p, p2, src)
    type(subevt_t), intent(inout) :: subevt
    integer, intent(in) :: i
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: p2
    integer, dimension(:), intent(in), optional :: src
    if (present (src)) then
        call prt_init_incoming (subevt%prt(i), pdg, p, p2, src)
    else
        call prt_init_incoming (subevt%prt(i), pdg, p, p2, (/ i /))
    end if
end subroutine subevt_set_incoming

subroutine subevt_set_outgoing (subevt, i, pdg, p, p2, src)
    type(subevt_t), intent(inout) :: subevt
    integer, intent(in) :: i
    integer, intent(in) :: pdg
    type(vector4_t), intent(in) :: p
    real(default), intent(in) :: p2
    integer, dimension(:), intent(in), optional :: src
    if (present (src)) then
        call prt_init_outgoing (subevt%prt(i), pdg, p, p2, src)
    else
        call prt_init_outgoing (subevt%prt(i), pdg, p, p2, (/ i /))
    end if
end subroutine subevt_set_outgoing

subroutine subevt_set_composite (subevt, i, p, src)
    type(subevt_t), intent(inout) :: subevt
    integer, intent(in) :: i
    type(vector4_t), intent(in) :: p
    integer, dimension(:), intent(in) :: src
    call prt_init_composite (subevt%prt(i), p, src)
end subroutine subevt_set_composite

```

Separately assign flavors, simultaneously for all incoming/outgoing particles.

```

<Subevents: public>+≡
    public :: subevt_set_pdg_beam
    public :: subevt_set_pdg_incoming
    public :: subevt_set_pdg_outgoing

<Subevents: procedures>+≡
    subroutine subevt_set_pdg_beam (subevt, pdg)
        type(subevt_t), intent(inout) :: subevt
        integer, dimension(:), intent(in) :: pdg
        integer :: i, j
        j = 1
    end subroutine

```

```

do i = 1, subevt%n_tot
  if (subevt%prt(i)%type == PRT_BEAM) then
    call prt_set_pdg (subevt%prt(i), pdg(j))
    j = j + 1
    if (j > size (pdg)) exit
  end if
end do
end subroutine subevt_set_pdg_beam

subroutine subevt_set_pdg_incoming (subevt, pdg)
  type(subevt_t), intent(inout) :: subevt
  integer, dimension(:), intent(in) :: pdg
  integer :: i, j
  j = 1
  do i = 1, subevt%n_tot
    if (subevt%prt(i)%type == PRT_INCOMING) then
      call prt_set_pdg (subevt%prt(i), pdg(j))
      j = j + 1
      if (j > size (pdg)) exit
    end if
  end do
end subroutine subevt_set_pdg_incoming

subroutine subevt_set_pdg_outgoing (subevt, pdg)
  type(subevt_t), intent(inout) :: subevt
  integer, dimension(:), intent(in) :: pdg
  integer :: i, j
  j = 1
  do i = 1, subevt%n_tot
    if (subevt%prt(i)%type == PRT_OUTGOING) then
      call prt_set_pdg (subevt%prt(i), pdg(j))
      j = j + 1
      if (j > size (pdg)) exit
    end if
  end do
end subroutine subevt_set_pdg_outgoing

```

Separately assign momenta, simultaneously for all incoming/outgoing particles.

(Subevents: public)+≡

```

public :: subevt_set_p_beam
public :: subevt_set_p_incoming
public :: subevt_set_p_outgoing

```

(Subevents: procedures)+≡

```

subroutine subevt_set_p_beam (subevt, p)
  type(subevt_t), intent(inout) :: subevt
  type(vector4_t), dimension(:), intent(in) :: p
  integer :: i, j
  j = 1
  do i = 1, subevt%n_tot
    if (subevt%prt(i)%type == PRT_BEAM) then
      call prt_set_p (subevt%prt(i), p(j))
      j = j + 1
      if (j > size (p)) exit
    end if
  end do
end subroutine subevt_set_p_beam

```

```

        end if
    end do
end subroutine subevt_set_p_beam

subroutine subevt_set_p_incoming (subevt, p)
    type(subevt_t), intent(inout) :: subevt
    type(vector4_t), dimension(:), intent(in) :: p
    integer :: i, j
    j = 1
    do i = 1, subevt%n_tot
        if (subevt%prt(i)%type == PRT_INCOMING) then
            call prt_set_p (subevt%prt(i), p(j))
            j = j + 1
            if (j > size (p)) exit
        end if
    end do
end subroutine subevt_set_p_incoming

subroutine subevt_set_p_outgoing (subevt, p)
    type(subevt_t), intent(inout) :: subevt
    type(vector4_t), dimension(:), intent(in) :: p
    integer :: i, j
    j = 1
    do i = 1, subevt%n_tot
        if (subevt%prt(i)%type == PRT_OUTGOING) then
            call prt_set_p (subevt%prt(i), p(j))
            j = j + 1
            if (j > size (p)) exit
        end if
    end do
end subroutine subevt_set_p_outgoing

```

Set polarization for an entry

```

<Subevents: public>+≡
    public :: subevt_polarize

<Subevents: procedures>+≡
    subroutine subevt_polarize (subevt, i, h)
        type(subevt_t), intent(inout) :: subevt
        integer, intent(in) :: i, h
        call prt_polarize (subevt%prt(i), h)
    end subroutine subevt_polarize

```

Accessing contents

Return true if the subevent has entries.

```

<Subevents: public>+≡
    public :: subevt_is_nonempty

<Subevents: procedures>+≡
    function subevt_is_nonempty (subevt) result (flag)
        logical :: flag
        type(subevt_t), intent(in) :: subevt

```

```

        flag = subvt%n_tot /= 0
    end function subvt_is_nonempty

```

Return the number of entries

```

<Subevents: public>+≡
    public :: subvt_get_length

<Subevents: procedures>+≡
    function subvt_get_length (subvt) result (length)
        integer :: length
        type(subvt_t), intent(in) :: subvt
        length = subvt%n_tot
    end function subvt_get_length

```

Return a specific particle. The index is not checked for validity.

```

<Subevents: public>+≡
    public :: subvt_get_prt

<Subevents: procedures>+≡
    function subvt_get_prt (subvt, i) result (prt)
        type(prt_t) :: prt
        type(subvt_t), intent(in) :: subvt
        integer, intent(in) :: i
        prt = subvt%prt(i)
    end function subvt_get_prt

```

```

<Subevents: interfaces>+≡
    interface c_prt
        module procedure c_prt_from_subvt
        module procedure c_prt_array_from_subvt
    end interface

```

```

<Subevents: procedures>+≡
    function c_prt_from_subvt (subvt, i) result (c_prt)
        type(c_prt_t) :: c_prt
        type(subvt_t), intent(in) :: subvt
        integer, intent(in) :: i
        c_prt = c_prt_from_prt (subvt%prt(i))
    end function c_prt_from_subvt

    function c_prt_array_from_subvt (subvt) result (c_prt_array)
        type(subvt_t), intent(in) :: subvt
        type(c_prt_t), dimension(subvt%n_tot) :: c_prt_array
        c_prt_array = c_prt_from_prt (subvt%prt(1:subvt%n_tot))
    end function c_prt_array_from_subvt

```

Operations with subevents

The join operation joins two subevents. When appending the elements of the second list, we check for each particle whether it is already in the first list. If yes, it is discarded. The result list should be initialized already.

If a mask is present, it refers to the second subevent. Particles where the mask is not set are discarded.

```

<Subevents: public>+≡
    public :: subevt_join

<Subevents: procedures>+≡
    subroutine subevt_join (subevt, pl1, pl2, mask2)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl1, pl2
        logical, dimension(:), intent(in), optional :: mask2
        integer :: n1, n2, i, n
        n1 = pl1%n_tot
        n2 = pl2%n_tot
        call subevt_reset (subevt, n1 + n2)
        subevt%prt(:n1) = pl1%prt(:n1)
        n = n1
        if (present (mask2)) then
            do i = 1, pl2%n_tot
                if (mask2(i)) then
                    if (disjoint (i)) then
                        n = n + 1
                        subevt%prt(n) = pl2%prt(i)
                    end if
                end if
            end do
        else
            do i = 1, pl2%n_tot
                if (disjoint (i)) then
                    n = n + 1
                    subevt%prt(n) = pl2%prt(i)
                end if
            end do
        end if
        subevt%n_tot = n
    contains
        function disjoint (i) result (flag)
            integer, intent(in) :: i
            logical :: flag
            integer :: j
            do j = 1, pl1%n_tot
                if (.not. are_disjoint (pl1%prt(j), pl2%prt(i))) then
                    flag = .false.
                    return
                end if
            end do
            flag = .true.
        end function disjoint
    end subroutine subevt_join

```

The combine operation makes a subevent whose entries are the result of adding (the momenta of) each pair of particles in the input lists. We trace the particles from which a particles is built by storing a `src` array. Each particle entry in the `src` list contains a list of indices which indicates its building blocks. The indices

refer to an original list of particles. Index lists are sorted, and they contain no element more than once.

We thus require that in a given pseudoparticle, each original particle occurs at most once.

```

<Subevents: public>+≡
    public :: subevt_combine

<Subevents: procedures>+≡
    subroutine subevt_combine (subevt, pl1, pl2, mask12)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl1, pl2
        logical, dimension(:, :), intent(in), optional :: mask12
        integer :: n1, n2, i1, i2, n, j
        logical :: ok
        n1 = pl1%n_tot
        n2 = pl2%n_tot
        call subevt_reset (subevt, n1 * n2)
        n = 1
        do i1 = 1, n1
            do i2 = 1, n2
                if (present (mask12)) then
                    ok = mask12(i1,i2)
                else
                    ok = .true.
                end if
                if (ok) call prt_combine &
                    (subevt%prt(n), pl1%prt(i1), pl2%prt(i2), ok)
                if (ok) then
                    CHECK_DOUBLES: do j = 1, n - 1
                        if (subevt%prt(n) .match. subevt%prt(j)) then
                            ok = .false.; exit CHECK_DOUBLES
                        end if
                    end do CHECK_DOUBLES
                    if (ok) n = n + 1
                end if
            end do
        end do
        subevt%n_tot = n - 1
    end subroutine subevt_combine

```

The collect operation makes a single-entry subevent which results from combining (the momenta of) all particles in the input list. As above, the result does not contain an original particle more than once; this is checked for each particle when it is collected. Furthermore, each entry has a mask; where the mask is false, the entry is dropped.

(Thus, if the input particles are already composite, there is some chance that the result depends on the order of the input list and is not as expected. This situation should be avoided.)

```

<Subevents: public>+≡
    public :: subevt_collect

<Subevents: procedures>+≡
    subroutine subevt_collect (subevt, pl1, mask1)

```

```

type(subevt_t), intent(inout) :: subevt
type(subevt_t), intent(in) :: pl1
logical, dimension(:), intent(in) :: mask1
type(prt_t) :: prt
integer :: i
logical :: ok
call subevt_reset (subevt, 1)
subevt%n_tot = 0
do i = 1, pl1%n_tot
  if (mask1(i)) then
    if (subevt%n_tot == 0) then
      subevt%n_tot = 1
      subevt%prt(1) = pl1%prt(i)
    else
      call prt_combine (prt, subevt%prt(1), pl1%prt(i), ok)
      if (ok) subevt%prt(1) = prt
    end if
  end if
end do
end subroutine subevt_collect

```

Return a list of all particles for which the mask is true.

```

⟨Subevents: public⟩+≡
  public :: subevt_select

⟨Subevents: procedures⟩+≡
  subroutine subevt_select (subevt, pl, mask1)
    type(subevt_t), intent(inout) :: subevt
    type(subevt_t), intent(in) :: pl
    logical, dimension(:), intent(in) :: mask1
    integer :: i, n
    call subevt_reset (subevt, pl%n_tot)
    n = 0
    do i = 1, pl%n_tot
      if (mask1(i)) then
        n = n + 1
        subevt%prt(n) = pl%prt(i)
      end if
    end do
    subevt%n_tot = n
  end subroutine subevt_select

```

Return a subevent which consists of the single particle with specified `index`. If `index` is negative, count from the end. If it is out of bounds, return an empty list.

```

⟨Subevents: public⟩+≡
  public :: subevt_extract

⟨Subevents: procedures⟩+≡
  subroutine subevt_extract (subevt, pl, index)
    type(subevt_t), intent(inout) :: subevt
    type(subevt_t), intent(in) :: pl
    integer, intent(in) :: index
    if (index > 0) then

```

```

        if (index <= pl%n_tot) then
            call subevt_reset (subevt, 1)
            subevt%prt(1) = pl%prt(index)
        else
            call subevt_reset (subevt, 0)
        end if
    else if (index < 0) then
        if (abs (index) <= pl%n_tot) then
            call subevt_reset (subevt, 1)
            subevt%prt(1) = pl%prt(pl%n_tot + 1 + index)
        else
            call subevt_reset (subevt, 0)
        end if
    else
        call subevt_reset (subevt, 0)
    end if
end subroutine subevt_extract

```

Return the list of particles sorted according to increasing values of the provided integer or real array. If no array is given, sort by PDG value.

```

<Subevents: public>+≡
    public :: subevt_sort

<Subevents: interfaces>+≡
    interface subevt_sort
        module procedure subevt_sort_pdg
        module procedure subevt_sort_int
        module procedure subevt_sort_real
    end interface

<Subevents: procedures>+≡
    subroutine subevt_sort_pdg (subevt, pl)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl
        integer :: n
        n = subevt%n_tot
        call subevt_sort_int (subevt, pl, abs (3 * subevt%prt(:n)%pdg - 1))
    end subroutine subevt_sort_pdg

    subroutine subevt_sort_int (subevt, pl, ival)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl
        integer, dimension(:), intent(in) :: ival
        call subevt_reset (subevt, pl%n_tot)
        subevt%n_tot = pl%n_tot
        subevt%prt = pl%prt( order (ival) )
    end subroutine subevt_sort_int

    subroutine subevt_sort_real (subevt, pl, rval)
        type(subevt_t), intent(inout) :: subevt
        type(subevt_t), intent(in) :: pl
        real(default), dimension(:), intent(in) :: rval
        call subevt_reset (subevt, pl%n_tot)
        subevt%n_tot = pl%n_tot

```



```

    subevt%prt = pl%prt( order (rval) )
end subroutine subevt_sort_real

```

Return the list of particles which have any of the specified PDG codes (and optionally particle type: beam, incoming, outgoing).

The `pack` command was buggy in some gfortran versions, therefore it is unrolled. The unrolled version may be more efficient, actually.

```

<Subevents: public>+≡
    public :: subevt_select_pdg_code

<Subevents: procedures>+≡
    subroutine subevt_select_pdg_code (subevt, aval, subevt_in, prt_type)
        type(subevt_t), intent(inout) :: subevt
        type(pdg_array_t), intent(in) :: aval
        type(subevt_t), intent(in) :: subevt_in
        integer, intent(in), optional :: prt_type
        integer :: n_tot, n_match
        logical, dimension(:), allocatable :: mask
        integer :: i, j
        n_tot = subevt_in%n_tot
        allocate (mask (n_tot))
        forall (i = 1:n_tot) &
            mask(i) = aval .match. subevt_in%prt(i)%pdg
        if (present (prt_type)) &
            mask = mask .and. subevt_in%prt(:n_tot)%type == prt_type
        n_match = count (mask)
        call subevt_reset (subevt, n_match)
!       subevt%prt(:n_match) = pack (subevt_in%prt(:n_tot), mask)
        j = 0
        do i = 1, n_tot
            if (mask(i)) then
                j = j + 1
                subevt%prt(j) = subevt_in%prt(i)
            end if
        end do
    end subroutine subevt_select_pdg_code

```

5.4 User Code Interface

Here we collect interface code that enables the user to inject his own code into the WHIZARD workflow. The code uses data types defined above, and is referenced in the `expressions` module.

```

<user_code_interface.f90>≡
<File header>

module user_code_interface

    use iso_c_binding !NODEP!
    <Use kinds>
    <Use strings>
    use diagnostics !NODEP!

```

```

    use c_particles !NODEP!
    use os_interface

    <Standard module head>

    <User Code: public>

    <User Code: variables>

    <User Code: interfaces>

    contains

    <User Code: procedures>

end module user_code_interface

```

5.4.1 User Code Management

This data structure globally holds the filehandle of the user-code library:

```

<User Code: public>≡
    public :: has_user_lib

<User Code: variables>≡
    type(dlaccess_t), save :: user_lib_handle
    logical, save :: has_user_lib = .false.
    type(string_t), save :: user

```

Compile, link and load user code files. Dlopen all user-provided libraries, included the one just compiled (if any).

By default, we are looking for a library `user.so`. If this is not present, try `user.f90` and compile it. This can be overridden.

In detail: First, compile all sources explicitly specified on the command line. Then collect all libraries specified on the command line, including `user.so` if it was generated. If there is still no code, check for an existing `user.f90` and compile this. Link everything into a `user.la` libtool library. When done, dlopen all libraries that we have so far.

```

<User Code: public>+≡
    public :: user_code_init

<User Code: procedures>≡
    subroutine user_code_init (user_src, user_lib, user_target, rebuild, os_data)
        type(string_t), dimension(:), intent(in) :: user_src, user_lib
        type(string_t), intent(in) :: user_target
        logical, intent(in) :: rebuild
        type(os_data_t), intent(in) :: os_data
        type(string_t) :: user_src_file, user_obj_files, user_lib_file
        logical :: exist
        type(c_funptr) :: fptr
        integer :: i
        call msg_message ("Initializing user code")
        user = user_target; if (user == "") user = "user"
        user_obj_files = ""

```

```

inquire (file = char (user) // ".la", exist = exist)
if (rebuild .or. .not. exist) then
  do i = 1, size (user_src)
    user_src_file = user_src(i) // os_data%fc_src_ext
    inquire (file = char (user_src_file), exist = exist)
    if (exist) then
      call msg_message ("Found user-code source '" &
        // char (user_src_file) // "'.")
      call compile_user_src (user_src_file, user_obj_files)
    else
      call msg_fatal ("User-code source '" // char (user_src_file) &
        // "' not found")
    end if
  end do
  do i = 1, size (user_lib)
    user_lib_file = user_lib(i) // ".la"
    inquire (file = char (user_lib_file), exist = exist)
    if (exist) then
      call msg_message ("Found user-code library '" &
        // char (user_lib_file) // "'.")
    else
      user_lib_file = user_lib(i) // os_data%shlib_ext
      inquire (file = char (user_lib_file), exist = exist)
      if (exist) then
        call msg_message ("Found user-code library '" &
          // char (user_lib_file) // "'.")
      else
        call msg_fatal ("User-code library '" // char (user_lib(i)) &
          // "' not found")
      end if
    end if
    user_obj_files = user_obj_files // " " // user_lib_file
  end do
  if (user_obj_files == "") then
    user_src_file = user // os_data%fc_src_ext
    inquire (file = char (user_src_file), exist = exist)
    if (exist) then
      call msg_message ("Found user-code source '" &
        // char (user_src_file) // "'.")
      call compile_user_src (user_src_file, user_obj_files)
    else
      call msg_fatal ("User-code source '" // char (user_src_file) &
        // "' not found")
    end if
  end if
  if (user_obj_files /= "") then
    call link_user (char (user), user_obj_files)
  end if
end if
call dlaccess_init &
  (user_lib_handle, var_str ("."), &
  user // os_data%shlib_ext, os_data)
if (dlaccess_has_error (user_lib_handle)) then
  call msg_error (char (dlaccess_get_error (user_lib_handle)))

```

```

        call msg_fatal ("Loading user code library '" // char (user) &
            // ".la' failed")
    else
        call msg_message ("User code library '" // char (user) &
            // ".la' successfully loaded")
        has_user_lib = .true.
    end if
contains
    subroutine compile_user_src (user_src_file, user_obj_files)
        type(string_t), intent(in) :: user_src_file
        type(string_t), intent(inout) :: user_obj_files
        type(string_t) :: basename, ext
        logical :: exist
        basename = user_src_file
        call split (basename, ext, ".", back=.true.)
        if ( "." // ext == os_data%fc_src_ext) then
            inquire (file = char (user_src_file), exist = exist)
            if (exist) then
                call msg_message ("Compiling user code file '" &
                    // char (user_src_file) // "'")
                call os_compile_shared (basename, os_data)
                user_obj_files = user_obj_files // " " // basename // ".lo"
            else
                call msg_error ("User code file '" // char (user_src_file) &
                    // "' not found.")
            end if
        else
            call msg_error ("User code file '" // char (user_src_file) &
                // "' should have file extension '" &
                // char (os_data%fc_src_ext) // "'")
        end if
    end subroutine compile_user_src
    subroutine link_user (user_lib, user_obj_files)
        character(*), intent(in) :: user_lib
        type(string_t), intent(in) :: user_obj_files
        call msg_message ("Linking user code library '" &
            // user_lib // char (os_data%shlib_ext) // "'")
        call os_link_shared (user_obj_files, var_str (user_lib), os_data)
    end subroutine link_user
end subroutine user_code_init

```

Unload all user-code libraries.

```

<User Code: public>+≡
    public :: user_code_final

<User Code: procedures>+≡
    subroutine user_code_final ()
        if (has_user_lib) then
            call dlaccess_final (user_lib_handle)
            has_user_lib = .false.
        end if
    end subroutine user_code_final

```

Try to load the possible user-defined procedures from the dlopened libraries. If a procedure is not found, do nothing.

```

<User Code: public>+≡
    public :: user_code_find_proc

<User Code: procedures>+≡
    function user_code_find_proc (name) result (fptr)
        type(string_t), intent(in) :: name
        type(c_funptr) :: fptr
        integer :: i
        fptr = c_null_funptr
        fptr = libmanager_get_c_funptr (char (user), char (name))
        if (.not. c_associated (fptr)) then
            if (has_user_lib) then
                fptr = dlaccess_get_c_funptr (user_lib_handle, name)
                if (.not. c_associated (fptr)) then
                    call msg_fatal ("User procedure '" // char (name) // "' not found")
                end if
            else
                call msg_fatal ("User procedure '" // char (name) &
                    // "' called without user library (missing -u flag?)")
            end if
        end if
    end function user_code_find_proc

```

5.4.2 Libmanager interface

This is the interface to the libmanager library. The libmanager is generated when a static executable is built. The definitions are in Sec. 13.1.

```

<User Code: interfaces>≡
    <Libmanager: interfaces>

```

5.4.3 Interfaces for user-defined functions

The following functions represent user-defined real observables. There may be one or two particles as argument, the result is a real value.

```

<User Code: public>+≡
    public :: user_obs_int_unary
    public :: user_obs_int_binary
    public :: user_obs_real_unary
    public :: user_obs_real_binary

<User Code: interfaces>+≡
    abstract interface
        function user_obs_int_unary (prt1) result (ival) bind(C)
            use iso_c_binding !NODEP!
            use c_particles !NODEP!
            type(c_prt_t), intent(in) :: prt1
            integer(c_int) :: ival
        end function user_obs_int_unary
    end interface

```

```

abstract interface
  function user_obs_int_binary (prt1, prt2) result (ival) bind(C)
    use iso_c_binding !NODEP!
    use c_particles !NODEP!
    type(c_prt_t), intent(in) :: prt1, prt2
    integer(c_int) :: ival
  end function user_obs_int_binary
end interface

abstract interface
  function user_obs_real_unary (prt1) result (rval) bind(C)
    use iso_c_binding !NODEP!
    use c_particles !NODEP!
    type(c_prt_t), intent(in) :: prt1
    real(c_double) :: rval
  end function user_obs_real_unary
end interface

abstract interface
  function user_obs_real_binary (prt1, prt2) result (rval) bind(C)
    use iso_c_binding !NODEP!
    use c_particles !NODEP!
    type(c_prt_t), intent(in) :: prt1, prt2
    real(c_double) :: rval
  end function user_obs_real_binary
end interface

```

The following function takes an array of C-compatible particles and return a single value. The particle array represents a subevent. For C interoperability, we have to use an assumed-size array, hence the array size has to be transferred explicitly.

The cut function returns an `int`, which we should interpret as a logical value (nonzero=true).

```

<User Code: public>+≡
  public :: user_cut_fun

<User Code: interfaces>+≡
  abstract interface
    function user_cut_fun (prt, n_prt) result (iflag) bind(C)
      use iso_c_binding !NODEP!
      use c_particles !NODEP!
      type(c_prt_t), dimension(*), intent(in) :: prt
      integer(c_int), intent(in) :: n_prt
      integer(c_int) :: iflag
    end function user_cut_fun
  end interface

```

The event-shape function returns a real value.

```

<User Code: public>+≡
  public :: user_event_shape_fun

```

```

<User Code: interfaces>+≡
  abstract interface
    function user_event_shape_fun (prt, n_prt) result (rval) bind(C)
      use iso_c_binding !NODEP!
      use c_particles !NODEP!
      type(c_prt_t), dimension(*), intent(in) :: prt
      integer(c_int), intent(in) :: n_prt
      real(c_double) :: rval
    end function user_event_shape_fun
  end interface

```

5.4.4 Interfaces for user-defined interactions

The following procedure interfaces pertain to user-defined interactions, e.g., spectra or structure functions.

This subroutine retrieves the basic information for setting up the interaction and event generation. All parameters are `intent(inout)`, so we can provide default values. `n_in` and `n_out` are the number of incoming and outgoing particles, respectively. `n_states` is the total number of distinct states that should be generated (counting all states of the incoming particles). `n_col` is the maximal number of color entries a particle can have. `n_dim` is the number of input parameters, i.e., integration dimensions, that the structure function call requires for computing kinematics and matrix elements. `n_var` is the number of variables (e.g., momentum fractions) that the structure function call has to transfer from the kinematics to the dynamics evaluation.

```

<User Code: public>+≡
  public :: user_int_info

<User Code: interfaces>+≡
  abstract interface
    subroutine user_int_info (n_in, n_out, n_states, n_col, n_dim, n_var) &
      bind(C)
      use iso_c_binding !NODEP!
      integer(c_int), intent(inout) :: n_in, n_out, n_states, n_col
      integer(c_int), intent(inout) :: n_dim, n_var
    end subroutine user_int_info
  end interface

```

This subroutine retrieves the settings for the quantum number mask of a given particle index in the interaction. A nonzero value indicates that the corresponding quantum number is to be ignored. The lock index is the index of a particle that the current particle is related to. The relation applies if quantum numbers of one of the locked particles are summed over. (This is intended for helicity.)

```

<User Code: public>+≡
  public :: user_int_mask

<User Code: interfaces>+≡
  abstract interface
    subroutine user_int_mask (i_prt, m_flv, m_hel, m_col, i_lock) bind(C)
      use iso_c_binding !NODEP!
      integer(c_int), intent(in) :: i_prt

```

```

        integer(c_int), intent(inout) :: m_flv, m_hel, m_col, i_lock
    end subroutine user_int_mask
end interface

```

This subroutine retrieves the quantum numbers for the particle index `i_prt` in state `i_state`. The `flv` value is a PDG code. The `hel` value is an integer helicity (twice the helicity for fermions). The `col` array is an array which has at most `n_col` entries (see above). All parameters are `intent(inout)` since default values exist. In particular, if a mask entry is set by the previous procedure, the corresponding quantum number is ignored anyway.

```

<User Code: public>+≡
    public :: user_int_state

<User Code: interfaces>+≡
    abstract interface
        subroutine user_int_state (i_state, i_prt, flv, hel, col) bind(C)
            use iso_c_binding !NODEP!
            integer(c_int), intent(in) :: i_state, i_prt
            integer(c_int), intent(inout) :: flv, hel
            integer(c_int), dimension(*), intent(inout) :: col
        end subroutine user_int_state
    end interface

```

This subroutine takes an array of particle objects with array length `n_in` and an array of input parameters between 0 and 1 with array length `n_dim`. It returns an array of particle objects with array length `n_out`. In addition, it returns an array of internal variables (e.g., momentum fractions, Jacobian) with array length `n_var` that is used by the following subroutine for evaluating the dynamics, i.e., the matrix elements.

```

<User Code: public>+≡
    public :: user_int_kinematics

<User Code: interfaces>+≡
    abstract interface
        subroutine user_int_kinematics (prt_in, rval, prt_out, xval) bind(C)
            use iso_c_binding !NODEP!
            use c_particles !NODEP!
            type(c_prt_t), dimension(*), intent(in) :: prt_in
            real(c_double), dimension(*), intent(in) :: rval
            type(c_prt_t), dimension(*), intent(inout) :: prt_out
            real(c_double), dimension(*), intent(out) :: xval
        end subroutine user_int_kinematics
    end interface

```

This subroutine takes the array of variables (e.g., momentum fractions) with length `n_var` which has been generated by the previous subroutine and a real variable, the energy scale of the event. It returns an array of matrix-element values, one entry for each quantum state `n_states`. The ordering of matrix elements must correspond to the ordering of states.

```

<User Code: public>+≡
    public :: user_int_evaluate

```



```

⟨User Code: interfaces⟩+≡
  abstract interface
    subroutine user_int_evaluate (xval, scale, fval) bind(C)
      use iso_c_binding !NODEP!
      real(c_double), dimension(*), intent(in) :: xval
      real(c_double), intent(in) :: scale
      real(c_double), dimension(*), intent(out) :: fval
    end subroutine user_int_evaluate
  end interface

```

5.5 Variables

The user interface deals with variables that are handled similar to full-fledged programming languages. The system will add a lot of predefined variables (model parameters, flags, etc.) that are accessible to the user by the same methods.

Variables can be of various type: logical (boolean/flag), integer, real (default precision), subevents (used in cut expressions), arrays of PDG codes (aliases for particles), strings. Furthermore, in cut expressions we have unary and binary observables, which are used like real parameters but behave like functions.

```

⟨variables.f90⟩≡
  ⟨File header⟩

  module variables

    ⟨Use kinds⟩
    ⟨Use strings⟩
    ⟨Use file utils⟩
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use pdg_arrays
    use subevents

    ⟨Standard module head⟩

    ⟨Variables: public⟩

    ⟨Variables: parameters⟩

    ⟨Variables: types⟩

    ⟨Variables: interfaces⟩

    contains

    ⟨Variables: procedures⟩

  end module variables

```

5.5.1 Variable list entries

Variable (and constant) values can be of one of the following types:

```
<Variables: parameters>≡
    integer, parameter, public :: V_NONE = 0, V_LOG = 1, V_INT = 2, V_REAL = 3
    integer, parameter, public :: V_CMPLX = 4, V_SEV = 5, V_PDG = 6, V_STR = 7
    integer, parameter, public :: V_OBS1_INT = 11, V_OBS2_INT = 12
    integer, parameter, public :: V_OBS1_REAL = 21, V_OBS2_REAL = 22
    integer, parameter, public :: V_UOBS1_INT = 31, V_UOBS2_INT = 32
    integer, parameter, public :: V_UOBS1_REAL = 41, V_UOBS2_REAL = 42
```

The type

This is an entry in the variable list. It can be of any type; in each case only one value is allocated. It may be physically allocated upon creation, in which case `is_allocated` is true, or it may contain just a pointer to a value somewhere else, in which case `is_allocated` is false.

The flag `is_defined` is set when the variable is given a value, even the undefined value. (Therefore it is distinct from `is_known`.) This matters for variable declaration in the SINDARIN language. The variable is set up in the compilation step and initially marked as defined, but after compilation all variables are set undefined. Each variable becomes defined when it is explicitly set. The difference matters in loops.

`is_locked` means that it cannot be given a value using the interface routines `var_list_set_XXX` below. It can only be initialized, or change automatically due to a side effect.

`is_copy` means that this is a local copy of a global variable. The copy has a pointer to the original, which can be used to restore a previous value.

`is_intrinsic` means that this variable is defined by the program, not by the user. Intrinsic variables cannot be (re)declared, but their values can be reset unless they are locked. `is_user_var` means that the variable has been declared by the user. It could be a new variable, or a local copy of an intrinsic variable.

The flag `is_known` is a pointer which parallels the use of the value pointer. For pointer variables, it is set if the value should point to a known value. For ordinary variables, it should be true.

The value is implemented as a set of alternative type-specific pointers. This emulates polymorphism, and it allows for actual pointer variables. Observable-type variables have function pointers as values, so they behave like macros. The functions make use of the particle objects accessible via the pointers `prt1` and `prt2`.

Finally, the `next` pointer indicates that we are making lists of variables. A more efficient implementation might switch to hashes or similar; the current implementation has $O(N)$ lookup.

```
<Variables: public>≡
    public :: var_entry_t

<Variables: types>≡
    type :: var_entry_t
        private
        integer :: type = V_NONE
        type(string_t) :: name
```

```

logical :: is_allocated = .false.
logical :: is_defined = .false.
logical :: is_locked = .false.
logical :: is_copy = .false.
type(var_entry_t), pointer :: original => null ()
logical :: is_intrinsic = .false.
logical :: is_user_var = .false.
logical, pointer :: is_known => null ()
logical,          pointer :: lval => null ()
integer,          pointer :: ival => null ()
real(default),    pointer :: rval => null ()
complex(default), pointer :: cval => null ()
type(subevt_t),   pointer :: pval => null ()
type(pdg_array_t), pointer :: aval => null ()
type(string_t),   pointer :: sval => null ()
procedure(obs_unary_int), nopass, pointer :: obs1_int => null ()
procedure(obs_unary_real), nopass, pointer :: obs1_real => null ()
procedure(obs_binary_int), nopass, pointer :: obs2_int => null ()
procedure(obs_binary_real), nopass, pointer :: obs2_real => null ()
type(prt_t), pointer :: prt1 => null ()
type(prt_t), pointer :: prt2 => null ()
type(var_entry_t), pointer :: next => null ()
end type var_entry_t

```

Interfaces for the observable functions

```

{Variables: public}+=
  public :: obs_unary_int
  public :: obs_unary_real
  public :: obs_binary_int
  public :: obs_binary_real

{Variables: interfaces}=
  abstract interface
    function obs_unary_int (prt1) result (ival)
      import
      integer :: ival
      type(prt_t), intent(in) :: prt1
    end function obs_unary_int
  end interface
  abstract interface
    function obs_unary_real (prt1) result (rval)
      import
      real(default) :: rval
      type(prt_t), intent(in) :: prt1
    end function obs_unary_real
  end interface
  abstract interface
    function obs_binary_int (prt1, prt2) result (ival)
      import
      integer :: ival
      type(prt_t), intent(in) :: prt1, prt2
    end function obs_binary_int
  end interface

```

```

end interface
abstract interface
    function obs_binary_real (prt1, prt2) result (rval)
        import
        real(default) :: rval
        type(prt_t), intent(in) :: prt1, prt2
    end function obs_binary_real
end interface

```

Initialization

Initialize an entry, optionally with a physical value. We also allocate the `is_known` flag and set it if the value is set.

```

{Variables: public}+=
    public :: var_entry_init_log
    public :: var_entry_init_int
    public :: var_entry_init_real
    public :: var_entry_init_cmplx
    public :: var_entry_init_pdg_array
    public :: var_entry_init_subevt
    public :: var_entry_init_string

{Variables: procedures}=
    subroutine var_entry_init_log (var, name, lval, intrinsic, user)
        type(var_entry_t), intent(out) :: var
        type(string_t), intent(in) :: name
        logical, intent(in), optional :: lval
        logical, intent(in), optional :: intrinsic, user
        var%name = name
        var%type = V_LOG
        allocate (var%lval, var%is_known)
        if (present (lval)) then
            var%lval = lval
            var%is_defined = .true.
            var%is_known = .true.
        else
            var%is_known = .false.
        end if
        if (present (intrinsic)) var%is_intrinsic = intrinsic
        if (present (user)) var%is_user_var = user
        var%is_allocated = .true.
    end subroutine var_entry_init_log

    subroutine var_entry_init_int (var, name, ival, intrinsic, user)
        type(var_entry_t), intent(out) :: var
        type(string_t), intent(in) :: name
        integer, intent(in), optional :: ival
        logical, intent(in), optional :: intrinsic, user
        var%name = name
        var%type = V_INT
        allocate (var%ival, var%is_known)
        if (present (ival)) then
            var%ival = ival

```

```

        var%is_defined = .true.
        var%is_known = .true.
    else
        var%is_known = .false.
    end if
    if (present (intrinsic)) var%is_intrinsic = intrinsic
    if (present (user)) var%is_user_var = user
    var%is_allocated = .true.
end subroutine var_entry_init_int

subroutine var_entry_init_real (var, name, rval, intrinsic, user)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    real(default), intent(in), optional :: rval
    logical, intent(in), optional :: intrinsic, user
    var%name = name
    var%type = V_REAL
    allocate (var%rval, var%is_known)
    if (present (rval)) then
        var%rval = rval
        var%is_defined = .true.
        var%is_known = .true.
    else
        var%is_known = .false.
    end if
    if (present (intrinsic)) var%is_intrinsic = intrinsic
    if (present (user)) var%is_user_var = user
    var%is_allocated = .true.
end subroutine var_entry_init_real

subroutine var_entry_init_cmplx (var, name, cval, intrinsic, user)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    complex(default), intent(in), optional :: cval
    logical, intent(in), optional :: intrinsic, user
    var%name = name
    var%type = V_CMPLX
    allocate (var%cval, var%is_known)
    if (present (cval)) then
        var%cval = cval
        var%is_defined = .true.
        var%is_known = .true.
    else
        var%is_known = .false.
    end if
    if (present (intrinsic)) var%is_intrinsic = intrinsic
    if (present (user)) var%is_user_var = user
    var%is_allocated = .true.
end subroutine var_entry_init_cmplx

subroutine var_entry_init_subevt (var, name, pval, intrinsic, user)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    type(subevt_t), intent(in), optional :: pval

```

```

logical, intent(in), optional :: intrinsic, user
var%name = name
var%type = V_SEV
allocate (var%pval, var%is_known)
if (present (pval)) then
    var%pval = pval
    var%is_defined = .true.
    var%is_known = .true.
else
    var%is_known = .false.
end if
if (present (intrinsic)) var%is_intrinsic = intrinsic
if (present (user)) var%is_user_var = user
var%is_allocated = .true.
end subroutine var_entry_init_subevt

subroutine var_entry_init_pdg_array (var, name, aval, intrinsic, user)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    type(pdg_array_t), intent(in), optional :: aval
    logical, intent(in), optional :: intrinsic, user
    var%name = name
    var%type = V_PDG
    allocate (var%aval, var%is_known)
    if (present (aval)) then
        var%aval = aval
        var%is_defined = .true.
        var%is_known = .true.
    else
        var%is_known = .false.
    end if
    if (present (intrinsic)) var%is_intrinsic = intrinsic
    if (present (user)) var%is_user_var = user
    var%is_allocated = .true.
end subroutine var_entry_init_pdg_array

subroutine var_entry_init_string (var, name, sval, intrinsic, user)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    type(string_t), intent(in), optional :: sval
    logical, intent(in), optional :: intrinsic, user
    var%name = name
    var%type = V_STR
    allocate (var%sval, var%is_known)
    if (present (sval)) then
        var%sval = sval
        var%is_defined = .true.
        var%is_known = .true.
    else
        var%is_known = .false.
    end if
    if (present (intrinsic)) var%is_intrinsic = intrinsic
    if (present (user)) var%is_user_var = user
    var%is_allocated = .true.

```

```
end subroutine var_entry_init_string
```

Initialize an entry with a pointer to the value and, for numeric/logical values, a pointer to the `is_known` flag.

```
{Variables: public}+=
  public :: var_entry_init_log_ptr
  public :: var_entry_init_int_ptr
  public :: var_entry_init_real_ptr
  public :: var_entry_init_cmplx_ptr
  public :: var_entry_init_pdg_array_ptr
  public :: var_entry_init_subevt_ptr
  public :: var_entry_init_string_ptr

{Variables: procedures}+=
  subroutine var_entry_init_log_ptr (var, name, lval, is_known, intrinsic)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    logical, intent(in), target :: lval
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: intrinsic
    var%name = name
    var%type = V_LOG
    var%lval => lval
    var%is_known => is_known
    if (present (intrinsic)) var%is_intrinsic = intrinsic
    var%is_defined = .true.
  end subroutine var_entry_init_log_ptr

  subroutine var_entry_init_int_ptr (var, name, ival, is_known, intrinsic)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    integer, intent(in), target :: ival
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: intrinsic
    var%name = name
    var%type = V_INT
    var%ival => ival
    var%is_known => is_known
    if (present (intrinsic)) var%is_intrinsic = intrinsic
    var%is_defined = .true.
  end subroutine var_entry_init_int_ptr

  subroutine var_entry_init_real_ptr (var, name, rval, is_known, intrinsic)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    real(default), intent(in), target :: rval
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: intrinsic
    var%name = name
    var%type = V_REAL
    var%rval => rval
    var%is_known => is_known
    if (present (intrinsic)) var%is_intrinsic = intrinsic
    var%is_defined = .true.
```

```

end subroutine var_entry_init_real_ptr

subroutine var_entry_init_cmplx_ptr (var, name, cval, is_known, intrinsic)
  type(var_entry_t), intent(out) :: var
  type(string_t), intent(in) :: name
  complex(default), intent(in), target :: cval
  logical, intent(in), target :: is_known
  logical, intent(in), optional :: intrinsic
  var%name = name
  var%type = V_CMPLX
  var%cval => cval
  var%is_known => is_known
  if (present (intrinsic)) var%is_intrinsic = intrinsic
  var%is_defined = .true.
end subroutine var_entry_init_cmplx_ptr

subroutine var_entry_init_pdg_array_ptr (var, name, aval, is_known, intrinsic)
  type(var_entry_t), intent(out) :: var
  type(string_t), intent(in) :: name
  type(pdg_array_t), intent(in), target :: aval
  logical, intent(in), target :: is_known
  logical, intent(in), optional :: intrinsic
  var%name = name
  var%type = V_PDG
  var%aval => aval
  var%is_known => is_known
  if (present (intrinsic)) var%is_intrinsic = intrinsic
  var%is_defined = .true.
end subroutine var_entry_init_pdg_array_ptr

subroutine var_entry_init_subevt_ptr (var, name, pval, is_known, intrinsic)
  type(var_entry_t), intent(out) :: var
  type(string_t), intent(in) :: name
  type(subevt_t), intent(in), target :: pval
  logical, intent(in), target :: is_known
  logical, intent(in), optional :: intrinsic
  var%name = name
  var%type = V_SEV
  var%pval => pval
  var%is_known => is_known
  if (present (intrinsic)) var%is_intrinsic = intrinsic
  var%is_defined = .true.
end subroutine var_entry_init_subevt_ptr

subroutine var_entry_init_string_ptr (var, name, sval, is_known, intrinsic)
  type(var_entry_t), intent(out) :: var
  type(string_t), intent(in) :: name
  type(string_t), intent(in), target :: sval
  logical, intent(in), target :: is_known
  logical, intent(in), optional :: intrinsic
  var%name = name
  var%type = V_STR
  var%sval => sval
  var%is_known => is_known

```



```

        if (present (intrinsic)) var%is_intrinsic = intrinsic
        var%is_defined = .true.
    end subroutine var_entry_init_string_ptr

```

Initialize an entry with an observable. The procedure pointer is not yet set.

(Variables: procedures)+≡

```

subroutine var_entry_init_obs (var, name, type, prt1, prt2)
    type(var_entry_t), intent(out) :: var
    type(string_t), intent(in) :: name
    integer, intent(in) :: type
    type(prt_t), intent(in), target :: prt1
    type(prt_t), intent(in), optional, target :: prt2
    var%type = type
    var%name = name
    var%prt1 => prt1
    if (present (prt2)) var%prt2 => prt2
    var%is_intrinsic = .true.
    var%is_defined = .true.
end subroutine var_entry_init_obs

```

Mark an entry as undefined if it is a user-defined variable object, so force re-initialization.

(Variables: procedures)+≡

```

subroutine var_entry_undefine (var)
    type(var_entry_t), intent(inout) :: var
    var%is_defined = .not. var%is_user_var
    var%is_known = var%is_defined .and. var%is_known
end subroutine var_entry_undefine

```

Lock an entry: forbid resetting the entry after initialization.

(Variables: procedures)+≡

```

subroutine var_entry_lock (var, locked)
    type(var_entry_t), intent(inout) :: var
    logical, intent(in), optional :: locked
    if (present (locked)) then
        var%is_locked = locked
    else
        var%is_locked = .true.
    end if
end subroutine var_entry_lock

```

Finalizer

(Variables: public)+≡

```

public :: var_entry_final

```

(Variables: procedures)+≡

```

subroutine var_entry_final (var)
    type(var_entry_t), intent(inout) :: var
    if (var%is_allocated) then
        select case (var%type)

```

```

        case (V_LOG); deallocate (var%lval)
        case (V_INT); deallocate (var%ival)
        case (V_REAL); deallocate (var%rval)
        case (V_CMPLX); deallocate (var%cval)
        case (V_SEV); deallocate (var%pval)
        case (V_PDG); deallocate (var%aval)
        case (V_STR); deallocate (var%sval)
    end select
    deallocate (var%is_known)
    var%is_allocated = .false.
    var%is_defined = .false.
end if
end subroutine var_entry_final

```

Output

```

<Variables: public>+≡
    public :: var_entry_write

<Variables: procedures>+≡
    recursive subroutine var_entry_write (var, unit, model_name, show_ptr, &
        intrinsic)
        type(var_entry_t), intent(in) :: var
        integer, intent(in), optional :: unit
        type(string_t), intent(in), optional :: model_name
        logical, intent(in), optional :: show_ptr
        logical, intent(in), optional :: intrinsic
        integer :: u
        u = output_unit (unit); if (u < 0) return
        if (present (intrinsic)) then
            if (var%is_intrinsic .neqv. intrinsic) return
        end if
        if (.not. var%is_defined) then
            write (u, "(A,1x)", advance="no") "[undefined]"
        end if
        if (.not. var%is_intrinsic) then
            write (u, "(A,1x)", advance="no") "[user variable]"
        end if
        if (associated (var%original)) then
            if (present (model_name)) then
                write (u, "(A,A)", advance="no") char(model_name), "."
            end if
        end if
        write (u, "(A)", advance="no") char (var%name)
        if (var%is_locked) write (u, "(A)", advance="no") "*"
        if (var%is_allocated) then
            write (u, "(A)", advance="no") " = "
        else if (var%type /= V_NONE) then
            write (u, "(A)", advance="no") " => "
        end if
        select case (var%type)
        case (V_NONE); write (u, *)
        case (V_LOG)

```

```

        if (var%is_known) then
            if (var%lval) then
                write (u, "(A)") "true"
            else
                write (u, "(A)") "false"
            end if
        else
            write (u, "(A)") "[unknown logical]"
        end if
    case (V_INT)
        if (var%is_known) then
            write (u, *) var%ival
        else
            write (u, "(A)") "[unknown integer]"
        end if
    case (V_REAL)
        if (var%is_known) then
            write (u, *) var%rval
        else
            write (u, "(A)") "[unknown real]"
        end if
    case (V_CMPLX)
        if (var%is_known) then
            write (u, *) char (cmplx2string (var%cval))
        else
            write (u, "(A)") "[unknown complex]"
        end if
    case (V_SEV)
        if (var%is_known) then
            call subevt_write (var%pval, unit, prefix="      ")
        else
            write (u, "(A)") "[unknown subevent]"
        end if
    case (V_PDG)
        if (var%is_known) then
            call pdg_array_write (var%aval, u); write (u, *)
        else
            write (u, "(A)") "[unknown PDG array]"
        end if
    case (V_STR)
        if (var%is_known) then
            write (u, "(A)") ''' // char (var%sval) // '''
        else
            write (u, "(A)") "[unknown string]"
        end if
    case (V_OBS1_INT); write (u, *) "[int] = unary observable"
    case (V_OBS2_INT); write (u, *) "[int] = binary observable"
    case (V_OBS1_REAL); write (u, *) "[real] = unary observable"
    case (V_OBS2_REAL); write (u, *) "[real] = binary observable"
    case (V_UOBS1_INT); write (u, *) "[int] = unary user observable"
    case (V_UOBS2_INT); write (u, *) "[int] = binary user observable"
    case (V_UOBS1_REAL); write (u, *) "[real] = unary user observable"
    case (V_UOBS2_REAL); write (u, *) "[real] = binary user observable"
end select

```

```

    if (present (show_ptr)) then
      if (show_ptr .and. var%is_copy .and. associated (var%original)) then
        write (u, "(' => ')", advance="no")
        call var_entry_write (var%original, unit)
      end if
    end if
  end if
end subroutine var_entry_write

```

Accessing contents

```

<Variables: public>+≡
  public :: var_entry_get_name
  public :: var_entry_get_type

<Variables: procedures>+≡
  function var_entry_get_name (var) result (name)
    type(string_t) :: name
    type(var_entry_t), intent(in) :: var
    name = var%name
  end function var_entry_get_name

  function var_entry_get_type (var) result (type)
    integer :: type
    type(var_entry_t), intent(in) :: var
    type = var%type
  end function var_entry_get_type

```

Return true if the variable is defined. This the case if it is allocated and known, or if it is a pointer.

```

<Variables: public>+≡
  public :: var_entry_is_defined

<Variables: procedures>+≡
  function var_entry_is_defined (var) result (defined)
    logical :: defined
    type(var_entry_t), intent(in) :: var
    defined = var%is_defined
  end function var_entry_is_defined

```

Return true if the variable is locked

```

<Variables: public>+≡
  public :: var_entry_is_locked

<Variables: procedures>+≡
  function var_entry_is_locked (var) result (locked)
    logical :: locked
    type(var_entry_t), intent(in) :: var
    locked = var%is_locked
  end function var_entry_is_locked

```

Return true if the variable is intrinsic

```

<Variables: public>+≡
  public :: var_entry_is_intrinsic

```

```

<Variables: procedures>+≡
function var_entry_is_intrinsic (var) result (flag)
    logical :: flag
    type(var_entry_t), intent(in) :: var
    flag = var%is_intrinsic
end function var_entry_is_intrinsic

```

Return true if the variable is a copy

```

<Variables: public>+≡
    public :: var_entry_is_copy

<Variables: procedures>+≡
function var_entry_is_copy (var) result (flag)
    logical :: flag
    type(var_entry_t), intent(in) :: var
    flag = var%is_copy
end function var_entry_is_copy

```

Return components

```

<Variables: public>+≡
    public :: var_entry_is_known
    public :: var_entry_get_lval
    public :: var_entry_get_ival
    public :: var_entry_get_rval
    public :: var_entry_get_cval
    public :: var_entry_get_aval
    public :: var_entry_get_pval
    public :: var_entry_get_sval

<Variables: procedures>+≡
function var_entry_is_known (var) result (flag)
    logical :: flag
    type(var_entry_t), intent(in) :: var
    flag = var%is_known
end function var_entry_is_known

function var_entry_get_lval (var) result (lval)
    logical :: lval
    type(var_entry_t), intent(in) :: var
    lval = var%lval
end function var_entry_get_lval

function var_entry_get_ival (var) result (ival)
    integer :: ival
    type(var_entry_t), intent(in) :: var
    ival = var%ival
end function var_entry_get_ival

function var_entry_get_rval (var) result (rval)
    real(default) :: rval
    type(var_entry_t), intent(in) :: var
    rval = var%rval
end function var_entry_get_rval

```

```

function var_entry_get_cval (var) result (cval)
  complex(default) :: cval
  type(var_entry_t), intent(in) :: var
  cval = var%cval
end function var_entry_get_cval

function var_entry_get_aval (var) result (aval)
  type(pdg_array_t) :: aval
  type(var_entry_t), intent(in) :: var
  aval = var%aval
end function var_entry_get_aval

function var_entry_get_pval (var) result (pval)
  type(subevt_t) :: pval
  type(var_entry_t), intent(in) :: var
  pval = var%pval
end function var_entry_get_pval

function var_entry_get_sval (var) result (sval)
  type(string_t) :: sval
  type(var_entry_t), intent(in) :: var
  sval = var%sval
end function var_entry_get_sval

```

Return pointers to components

(Variables: public) +=

```

public :: var_entry_get_known_ptr
public :: var_entry_get_lval_ptr
public :: var_entry_get_ival_ptr
public :: var_entry_get_rval_ptr
public :: var_entry_get_cval_ptr
public :: var_entry_get_aval_ptr
public :: var_entry_get_pval_ptr
public :: var_entry_get_sval_ptr

```

(Variables: procedures) +=

```

function var_entry_get_known_ptr (var) result (ptr)
  logical, pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%is_known
end function var_entry_get_known_ptr

function var_entry_get_lval_ptr (var) result (ptr)
  logical, pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%lval
end function var_entry_get_lval_ptr

function var_entry_get_ival_ptr (var) result (ptr)
  integer, pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%ival
end function var_entry_get_ival_ptr

```

```

function var_entry_get_rval_ptr (var) result (ptr)
  real(default), pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%rval
end function var_entry_get_rval_ptr

function var_entry_get_cval_ptr (var) result (ptr)
  complex(default), pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%cval
end function var_entry_get_cval_ptr

function var_entry_get_pval_ptr (var) result (ptr)
  type(subevt_t), pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%pval
end function var_entry_get_pval_ptr

function var_entry_get_aval_ptr (var) result (ptr)
  type(pdg_array_t), pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%aval
end function var_entry_get_aval_ptr

function var_entry_get_sval_ptr (var) result (ptr)
  type(string_t), pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%sval
end function var_entry_get_sval_ptr

```

<Variables: public>+≡

```

public :: var_entry_get_prt1_ptr
public :: var_entry_get_prt2_ptr

```

<Variables: procedures>+≡

```

function var_entry_get_prt1_ptr (var) result (ptr)
  type(prt_t), pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%prt1
end function var_entry_get_prt1_ptr

function var_entry_get_prt2_ptr (var) result (ptr)
  type(prt_t), pointer :: ptr
  type(var_entry_t), intent(in), target :: var
  ptr => var%prt2
end function var_entry_get_prt2_ptr

```

We would like to also use functions here (for consistency), but a nagfor bug temporarily forces use to use subroutines.

<Variables: public>+≡

```

public :: var_entry_assign_obs1_int_ptr
public :: var_entry_assign_obs1_real_ptr
public :: var_entry_assign_obs2_int_ptr
public :: var_entry_assign_obs2_real_ptr

```

```

{Variables: procedures}+=
  subroutine var_entry_assign_obs1_int_ptr (ptr, var)
    procedure(obs_unary_int), pointer :: ptr
    type(var_entry_t), intent(in), target :: var
    ptr => var%obs1_int
  end subroutine var_entry_assign_obs1_int_ptr

  subroutine var_entry_assign_obs1_real_ptr (ptr, var)
    procedure(obs_unary_real), pointer :: ptr
    type(var_entry_t), intent(in), target :: var
    ptr => var%obs1_real
  end subroutine var_entry_assign_obs1_real_ptr

  subroutine var_entry_assign_obs2_int_ptr (ptr, var)
    procedure(obs_binary_int), pointer :: ptr
    type(var_entry_t), intent(in), target :: var
    ptr => var%obs2_int
  end subroutine var_entry_assign_obs2_int_ptr

  subroutine var_entry_assign_obs2_real_ptr (ptr, var)
    procedure(obs_binary_real), pointer :: ptr
    type(var_entry_t), intent(in), target :: var
    ptr => var%obs2_real
  end subroutine var_entry_assign_obs2_real_ptr

```

5.5.2 Setting values

Undefine the value.

```

{Variables: procedures}+=
  subroutine var_entry_clear_value (var)
    type(var_entry_t), intent(inout) :: var
    var%is_known = .false.
  end subroutine var_entry_clear_value

{Variables: public}+=
  public :: var_entry_set_log
  public :: var_entry_set_int
  public :: var_entry_set_real
  public :: var_entry_set_cmplx
  public :: var_entry_set_pdg_array
  public :: var_entry_set_subevt
  public :: var_entry_set_string

{Variables: procedures}+=
  recursive subroutine var_entry_set_log &
    (var, lval, is_known, verbose, model_name)
    type(var_entry_t), intent(inout) :: var
    logical, intent(in) :: lval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose
    type(string_t), intent(in), optional :: model_name
    integer :: u

```



```

u = logfile_unit ()
var%lval = lval
var%is_known = is_known
var%is_defined = .true.
if (associated (var%original)) then
    call var_entry_set_log (var%original, lval, is_known)
end if
if (present (verbose)) then
    if (verbose) then
        call var_entry_write (var, model_name=model_name)
        call var_entry_write (var, model_name=model_name, unit=u)
        if (u >= 0) flush (u)
    end if
end if
end subroutine var_entry_set_log

recursive subroutine var_entry_set_int &
    (var, ival, is_known, verbose, model_name)
type(var_entry_t), intent(inout) :: var
integer, intent(in) :: ival
logical, intent(in) :: is_known
logical, intent(in), optional :: verbose
type(string_t), intent(in), optional :: model_name
integer :: u
u = logfile_unit ()
var%ival = ival
var%is_known = is_known
var%is_defined = .true.
if (associated (var%original)) then
    call var_entry_set_int (var%original, ival, is_known)
end if
if (present (verbose)) then
    if (verbose) then
        call var_entry_write (var, model_name=model_name)
        call var_entry_write (var, model_name=model_name, unit=u)
        if (u >= 0) flush (u)
    end if
end if
end subroutine var_entry_set_int

recursive subroutine var_entry_set_real &
    (var, rval, is_known, verbose, model_name)
type(var_entry_t), intent(inout) :: var
real(default), intent(in) :: rval
logical, intent(in) :: is_known
logical, intent(in), optional :: verbose
type(string_t), intent(in), optional :: model_name
integer :: u
u = logfile_unit ()
var%rval = rval
var%is_known = is_known
var%is_defined = .true.
if (associated (var%original)) then
    call var_entry_set_real (var%original, rval, is_known)

```

```

end if
if (present (verbose)) then
  if (verbose) then
    call var_entry_write (var, model_name=model_name)
    call var_entry_write (var, model_name=model_name, unit=u)
    if (u >= 0) flush (u)
  end if
end if
end subroutine var_entry_set_real

recursive subroutine var_entry_set_cmplx &
  (var, cval, is_known, verbose, model_name)
  type(var_entry_t), intent(inout) :: var
  complex(default), intent(in) :: cval
  logical, intent(in) :: is_known
  logical, intent(in), optional :: verbose
  type(string_t), intent(in), optional :: model_name
  integer :: u
  u = logfile_unit ()
  var%cval = cval
  var%is_known = is_known
  var%is_defined = .true.
  if (associated (var%original)) then
    call var_entry_set_cmplx (var%original, cval, is_known)
  end if
  if (present (verbose)) then
    if (verbose) then
      call var_entry_write (var, model_name=model_name)
      call var_entry_write (var, model_name=model_name, unit=u)
      if (u >= 0) flush (u)
    end if
  end if
end subroutine var_entry_set_cmplx

recursive subroutine var_entry_set_pdg_array &
  (var, aval, is_known, verbose, model_name)
  type(var_entry_t), intent(inout) :: var
  type(pdg_array_t), intent(in) :: aval
  logical, intent(in) :: is_known
  logical, intent(in), optional :: verbose
  type(string_t), intent(in), optional :: model_name
  integer :: u
  u = logfile_unit ()
  var%aval = aval
  var%is_known = is_known
  var%is_defined = .true.
  if (associated (var%original)) then
    call var_entry_set_pdg_array (var%original, aval, is_known)
  end if
  if (present (verbose)) then
    if (verbose) then
      call var_entry_write (var, model_name=model_name)
      call var_entry_write (var, model_name=model_name, unit=u)
      if (u >= 0) flush (u)
    end if
  end if
end subroutine var_entry_set_pdg_array

```

```

        end if
    end if
end subroutine var_entry_set_pdg_array

recursive subroutine var_entry_set_subevt &
    (var, pval, is_known, verbose, model_name)
    type(var_entry_t), intent(inout) :: var
    type(subevt_t), intent(in) :: pval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose
    type(string_t), intent(in), optional :: model_name
    integer :: u
    u = logfile_unit ()
    var%pval = pval
    var%is_known = is_known
    var%is_defined = .true.
    if (associated (var%original)) then
        call var_entry_set_subevt (var%original, pval, is_known)
    end if
    if (present (verbose)) then
        if (verbose) then
            call var_entry_write (var, model_name=model_name)
            call var_entry_write (var, model_name=model_name, unit=u)
            if (u >= 0) flush (u)
        end if
    end if
end subroutine var_entry_set_subevt

recursive subroutine var_entry_set_string &
    (var, sval, is_known, verbose, model_name)
    type(var_entry_t), intent(inout) :: var
    type(string_t), intent(in) :: sval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: verbose
    type(string_t), intent(in), optional :: model_name
    integer :: u
    u = logfile_unit ()
    var%sval = sval
    var%is_known = is_known
    var%is_defined = .true.
    if (associated (var%original)) then
        call var_entry_set_string (var%original, sval, is_known)
    end if
    if (present (verbose)) then
        if (verbose) then
            call var_entry_write (var, model_name=model_name)
            call var_entry_write (var, model_name=model_name, unit=u)
            if (u >= 0) flush (u)
        end if
    end if
end subroutine var_entry_set_string

```

5.5.3 Copies and pointer variables

Initialize an entry with a copy of an existing variable entry. The copy is physically allocated with the same type as the original.

(Variables: procedures)+≡

```
subroutine var_entry_init_copy (var, original, user)
  type(var_entry_t), intent(out) :: var
  type(var_entry_t), intent(in), target :: original
  logical, intent(in), optional :: user
  type(string_t) :: name
  logical :: intrinsic
  name = var_entry_get_name (original)
  intrinsic = original%is_intrinsic
  select case (original%type)
  case (V_LOG)
    call var_entry_init_log (var, name, intrinsic=intrinsic, user=user)
  case (V_INT)
    call var_entry_init_int (var, name, intrinsic=intrinsic, user=user)
  case (V_REAL)
    call var_entry_init_real (var, name, intrinsic=intrinsic, user=user)
  case (V_CMPLX)
    call var_entry_init_cmplx (var, name, intrinsic=intrinsic, user=user)
  case (V_SEV)
    call var_entry_init_subevt (var, name, intrinsic=intrinsic, user=user)
  case (V_PDG)
    call var_entry_init_pdg_array (var, name, intrinsic=intrinsic, user=user)
  case (V_STR)
    call var_entry_init_string (var, name, intrinsic=intrinsic, user=user)
  end select
  var%is_copy = .true.
end subroutine var_entry_init_copy
```

Clear the pointer to the original.

(Variables: procedures)+≡

```
subroutine var_entry_clear_original_pointer (var)
  type(var_entry_t), intent(inout) :: var
  var%original => null ()
end subroutine var_entry_clear_original_pointer
```

Set the pointer to the original. For a free parameter, the variable holds both the value and the pointer. For a derived parameter, we associate the pointer directly. Derived parameters thus need not be synchronized explicitly.

Update: this does not work. If locked parameters are accessed in expressions and the model is non-default, the pointers in the expression may be undefined at compile time. Reassigning the variables at runtime does not help, since the pointers in the expression are dereferenced before assignment. Hence, no special treatment for derived parameters.

(Variables: procedures)+≡

```
subroutine var_entry_set_original_pointer (var, original)
  type(var_entry_t), intent(inout) :: var
  type(var_entry_t), intent(in), target :: original
  type(string_t) :: name
```

```

type(var_entry_t), pointer :: next
if (var_entry_is_locked (original)) then
!   next => var%next
!   name = var_entry_get_name (original)
!   select case (original%type)
!   case (V_LOG); call var_entry_init_log_ptr (var, name, &
!       original%lval, original%is_known)
!   case (V_INT); call var_entry_init_int_ptr (var, name, &
!       original%ival, original%is_known)
!   case (V_REAL); call var_entry_init_real_ptr (var, name, &
!       original%rval, original%is_known)
!   case (V_CMPLX); call var_entry_init_cmplx_ptr (var, name, &
!       original%cval, original%is_known)
!   case (V_SEV); call var_entry_init_subevt_ptr (var, name, &
!       original%pval, original%is_known)
!   case (V_PDG); call var_entry_init_pdg_array_ptr (var, name, &
!       original%aval, original%is_known)
!   case (V_STR); call var_entry_init_string_ptr (var, name, &
!       original%sval, original%is_known)
!   end select
!   var%next => next
!   call var_entry_lock (var)
!   else
!       var%original => original
!   end if
var%original => original
end subroutine var_entry_set_original_pointer

```

Synchronize a variable with its original: if a pointer exists, set the value to be equal to value pointed to.

```

{Variables: procedures}+≡
subroutine var_entry_synchronize (var)
type(var_entry_t), intent(inout) :: var
if (associated (var%original)) then
var%is_defined = var%original%is_defined
var%is_known = var%original%is_known
if (var%original%is_known) then
select case (var%type)
case (V_LOG); var%lval = var%original%lval
case (V_INT); var%ival = var%original%ival
case (V_REAL); var%rval = var%original%rval
case (V_CMPLX); var%cval = var%original%cval
case (V_SEV); var%pval = var%original%pval
case (V_PDG); var%aval = var%original%aval
case (V_STR); var%sval = var%original%sval
end select
end if
end if
end subroutine var_entry_synchronize

```

Restore the previous value of the original, using the value stored in the variable. This is a side-effect operation.

```

{Variables: procedures}+≡

```

```

subroutine var_entry_restore (var)
  type(var_entry_t), intent(inout) :: var
  !!! ifort 11.1 rev5 chokes over the intent(in)
  !!! type(var_entry_t), intent(in) :: var
  if (associated (var%original)) then
    if (var%is_known) then
      select case (var%type)
        case (V_LOG); var%original%lval = var%lval
        case (V_INT); var%original%ival = var%ival
        case (V_REAL); var%original%rval = var%rval
        case (V_CMPLX); var%original%cval = var%cval
        case (V_SEV); var%original%pval = var%pval
        case (V_PDG); var%original%aval = var%aval
        case (V_STR); var%original%sval = var%sval
      end select
    end if
  end if
end subroutine var_entry_restore

```

5.5.4 Variable lists

The type

Variable lists can be linked together. No initializer needed. They are deleted separately.

```

<Variables: public>+≡
  public :: var_list_t
<Variables: types>+≡
  type :: var_list_t
    private
    type(var_entry_t), pointer :: first => null ()
    type(var_entry_t), pointer :: last => null ()
    type(var_list_t), pointer :: next => null ()
  end type var_list_t

```

Constructors

```

<Variables: public>+≡
  public :: var_list_link
<Variables: procedures>+≡
  subroutine var_list_link (var_list, next)
    type(var_list_t), intent(inout) :: var_list
    type(var_list_t), intent(in), target :: next
    var_list%next => next
  end subroutine var_list_link

```

Append a new entry to an existing list.

```

<Variables: procedures>+≡
  subroutine var_list_append (var_list, var, verbose)
    type(var_list_t), intent(inout) :: var_list

```

```

type(var_entry_t), intent(in), target :: var
logical, intent(in), optional :: verbose
if (associated (var_list%last)) then
    var_list%last%next => var
else
    var_list%first => var
end if
var_list%last => var
if (present (verbose)) then
    if (verbose) call var_entry_write (var)
end if
end subroutine var_list_append

```

<Variables: public>+≡

```

public :: var_list_append_log
public :: var_list_append_int
public :: var_list_append_real
public :: var_list_append_cmplx
public :: var_list_append_subevt
public :: var_list_append_pdg_array
public :: var_list_append_string

```

<Variables: interfaces>+≡

```

interface var_list_append_log
    module procedure var_list_append_log_s
    module procedure var_list_append_log_c
end interface
interface var_list_append_int
    module procedure var_list_append_int_s
    module procedure var_list_append_int_c
end interface
interface var_list_append_real
    module procedure var_list_append_real_s
    module procedure var_list_append_real_c
end interface
interface var_list_append_cmplx
    module procedure var_list_append_cmplx_s
    module procedure var_list_append_cmplx_c
end interface
interface var_list_append_subevt
    module procedure var_list_append_subevt_s
    module procedure var_list_append_subevt_c
end interface
interface var_list_append_pdg_array
    module procedure var_list_append_pdg_array_s
    module procedure var_list_append_pdg_array_c
end interface
interface var_list_append_string
    module procedure var_list_append_string_s
    module procedure var_list_append_string_c
end interface

```

<Variables: procedures>+≡

```

subroutine var_list_append_log_s &
    (var_list, name, lval, locked, verbose, intrinsic, user)

```

```

type(var_list_t), intent(inout) :: var_list
type(string_t), intent(in) :: name
logical, intent(in), optional :: lval
logical, intent(in), optional :: locked, verbose, intrinsic, user
type(var_entry_t), pointer :: var
allocate (var)
call var_entry_init_log (var, name, lval, intrinsic, user)
if (present (locked)) call var_entry_lock (var, locked)
call var_list_append (var_list, var, verbose)
end subroutine var_list_append_log_s

subroutine var_list_append_int_s &
    (var_list, name, ival, locked, verbose, intrinsic, user)
type(var_list_t), intent(inout) :: var_list
type(string_t), intent(in) :: name
integer, intent(in), optional :: ival
logical, intent(in), optional :: locked, verbose, intrinsic, user
type(var_entry_t), pointer :: var
allocate (var)
call var_entry_init_int (var, name, ival, intrinsic, user)
if (present (locked)) call var_entry_lock (var, locked)
call var_list_append (var_list, var, verbose)
end subroutine var_list_append_int_s

subroutine var_list_append_real_s &
    (var_list, name, rval, locked, verbose, intrinsic, user)
type(var_list_t), intent(inout) :: var_list
type(string_t), intent(in) :: name
real(default), intent(in), optional :: rval
logical, intent(in), optional :: locked, verbose, intrinsic, user
type(var_entry_t), pointer :: var
allocate (var)
call var_entry_init_real (var, name, rval, intrinsic, user)
if (present (locked)) call var_entry_lock (var, locked)
call var_list_append (var_list, var, verbose)
end subroutine var_list_append_real_s

subroutine var_list_append_cmplx_s &
    (var_list, name, cval, locked, verbose, intrinsic, user)
type(var_list_t), intent(inout) :: var_list
type(string_t), intent(in) :: name
complex(default), intent(in), optional :: cval
logical, intent(in), optional :: locked, verbose, intrinsic, user
type(var_entry_t), pointer :: var
allocate (var)
call var_entry_init_cmplx (var, name, cval, intrinsic, user)
if (present (locked)) call var_entry_lock (var, locked)
call var_list_append (var_list, var, verbose)
end subroutine var_list_append_cmplx_s

subroutine var_list_append_subevt_s &
    (var_list, name, pval, locked, verbose, intrinsic, user)
type(var_list_t), intent(inout) :: var_list
type(string_t), intent(in) :: name

```



```

    type(subevt_t), intent(in), optional :: pval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_subevt (var, name, pval, intrinsic, user)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)
end subroutine var_list_append_subevt_s

subroutine var_list_append_pdg_array_s &
    (var_list, name, aval, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    type(pdg_array_t), intent(in), optional :: aval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_pdg_array (var, name, aval, intrinsic, user)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)
end subroutine var_list_append_pdg_array_s

subroutine var_list_append_string_s &
    (var_list, name, sval, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    type(string_t), intent(in), optional :: sval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_string (var, name, sval, intrinsic, user)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)
end subroutine var_list_append_string_s

subroutine var_list_append_log_c &
    (var_list, name, lval, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    character(*), intent(in) :: name
    logical, intent(in), optional :: lval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    call var_list_append_log_s &
        (var_list, var_str (name), lval, locked, verbose, intrinsic, user)
end subroutine var_list_append_log_c

subroutine var_list_append_int_c &
    (var_list, name, ival, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    character(*), intent(in) :: name
    integer, intent(in), optional :: ival
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    call var_list_append_int_s &
        (var_list, var_str (name), ival, locked, verbose, intrinsic, user)
end subroutine var_list_append_int_c

```

```

subroutine var_list_append_real_c &
    (var_list, name, rval, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    character(*), intent(in) :: name
    real(default), intent(in), optional :: rval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    call var_list_append_real_s &
        (var_list, var_str (name), rval, locked, verbose, intrinsic, user)
end subroutine var_list_append_real_c

subroutine var_list_append_cmplx_c &
    (var_list, name, cval, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    character(*), intent(in) :: name
    complex(default), intent(in), optional :: cval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    call var_list_append_cmplx_s &
        (var_list, var_str (name), cval, locked, verbose, intrinsic, user)
end subroutine var_list_append_cmplx_c

subroutine var_list_append_subevt_c &
    (var_list, name, pval, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    character(*), intent(in) :: name
    type(subevt_t), intent(in), optional :: pval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    call var_list_append_subevt_s &
        (var_list, var_str (name), pval, locked, verbose, intrinsic, user)
end subroutine var_list_append_subevt_c

subroutine var_list_append_pdg_array_c &
    (var_list, name, aval, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    character(*), intent(in) :: name
    type(pdg_array_t), intent(in), optional :: aval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    call var_list_append_pdg_array_s &
        (var_list, var_str (name), aval, locked, verbose, intrinsic, user)
end subroutine var_list_append_pdg_array_c

subroutine var_list_append_string_c &
    (var_list, name, sval, locked, verbose, intrinsic, user)
    type(var_list_t), intent(inout) :: var_list
    character(*), intent(in) :: name
    character(*), intent(in), optional :: sval
    logical, intent(in), optional :: locked, verbose, intrinsic, user
    if (present (sval)) then
        call var_list_append_string_s &
            (var_list, var_str (name), var_str (sval), &
                locked, verbose, intrinsic, user)
    else
        call var_list_append_string_s &
            (var_list, var_str (name), &

```

```

        locked=locked, verbose=verbose, intrinsic=intrinsic, user=user)
    end if
end subroutine var_list_append_string_c

```

(Variables: public)+≡

```

public :: var_list_append_log_ptr
public :: var_list_append_int_ptr
public :: var_list_append_real_ptr
public :: var_list_append_cmplx_ptr
public :: var_list_append_pdg_array_ptr
public :: var_list_append_subevt_ptr
public :: var_list_append_string_ptr

```

(Variables: procedures)+≡

```

subroutine var_list_append_log_ptr &
    (var_list, name, lval, is_known, locked, verbose, intrinsic)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    logical, intent(in), target :: lval
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: locked, verbose, intrinsic
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_log_ptr (var, name, lval, is_known, intrinsic)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)
end subroutine var_list_append_log_ptr

```

```

subroutine var_list_append_int_ptr &
    (var_list, name, ival, is_known, locked, verbose, intrinsic)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    integer, intent(in), target :: ival
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: locked, verbose, intrinsic
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_int_ptr (var, name, ival, is_known, intrinsic)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)
end subroutine var_list_append_int_ptr

```

```

subroutine var_list_append_real_ptr &
    (var_list, name, rval, is_known, locked, verbose, intrinsic)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    real(default), intent(in), target :: rval
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: locked, verbose, intrinsic
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_real_ptr (var, name, rval, is_known, intrinsic)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)

```

```

end subroutine var_list_append_real_ptr

subroutine var_list_append_cmplx_ptr &
    (var_list, name, cval, is_known, locked, verbose, intrinsic)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    complex(default), intent(in), target :: cval
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: locked, verbose, intrinsic
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_cmplx_ptr (var, name, cval, is_known, intrinsic)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)
end subroutine var_list_append_cmplx_ptr

subroutine var_list_append_pdg_array_ptr &
    (var_list, name, aval, is_known, locked, verbose, intrinsic)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    type(pdg_array_t), intent(in), target :: aval
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: locked, verbose, intrinsic
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_pdg_array_ptr (var, name, aval, is_known, intrinsic)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)
end subroutine var_list_append_pdg_array_ptr

subroutine var_list_append_subevt_ptr &
    (var_list, name, pval, is_known, locked, verbose, intrinsic)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    type(subevt_t), intent(in), target :: pval
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: locked, verbose, intrinsic
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_subevt_ptr (var, name, pval, is_known, intrinsic)
    if (present (locked)) call var_entry_lock (var, locked)
    call var_list_append (var_list, var, verbose)
end subroutine var_list_append_subevt_ptr

subroutine var_list_append_string_ptr &
    (var_list, name, sval, is_known, locked, verbose, intrinsic)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    type(string_t), intent(in), target :: sval
    logical, intent(in), target :: is_known
    logical, intent(in), optional :: locked, verbose, intrinsic
    type(var_entry_t), pointer :: var
    allocate (var)
    call var_entry_init_string_ptr (var, name, sval, is_known, intrinsic)

```

```

        if (present (locked)) call var_entry_lock (var, locked)
        call var_list_append (var_list, var, verbose)
    end subroutine var_list_append_string_ptr

```

Finalizer

<Variables: public>+≡

```
public :: var_list_final
```

Finalize, delete the list entry by entry.

<Variables: procedures>+≡

```

subroutine var_list_final (var_list)
    type(var_list_t), intent(inout) :: var_list
    type(var_entry_t), pointer :: var
    var_list%last => null ()
    do while (associated (var_list%first))
        var => var_list%first
        var_list%first => var%next
        call var_entry_final (var)
        deallocate (var)
    end do
end subroutine var_list_final

```

Output

Optionally, show only variables of a certain type.

<Variables: public>+≡

```
public :: var_list_write
```

<Variables: procedures>+≡

```

recursive subroutine var_list_write &
    (var_list, unit, follow_link, only_type, prefix, model_name, show_ptr, &
    intrinsic)
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: follow_link
    integer, intent(in), optional :: only_type
    character(*), intent(in), optional :: prefix
    type(string_t), intent(in), optional :: model_name
    logical, intent(in), optional :: show_ptr
    logical, intent(in), optional :: intrinsic
    type(var_entry_t), pointer :: var
    integer :: u, length
    logical :: write_this, write_next
    u = output_unit (unit); if (u < 0) return
    if (present (prefix)) length = len (prefix)
    var => var_list%first
    if (associated (var)) then
        do while (associated (var))
            if (present (only_type)) then
                write_this = only_type == var%type
            else

```

```

        write_this = .true.
    end if
    if (write_this .and. present (prefix)) then
        if (prefix /= extract (var%name, 1, length)) &
            write_this = .false.
    end if
    if (write_this) then
        call var_entry_write &
            (var, unit, model_name = model_name, show_ptr = show_ptr, &
             intrinsic=intrinsic)
    end if
    var => var%next
end do
end if
write_next = associated (var_list%next)
if (present (follow_link)) &
    write_next = write_next .and. follow_link
if (write_next) then
    call var_list_write (var_list%next, &
        unit, follow_link, only_type, prefix, model_name, show_ptr, &
        intrinsic)
end if
end subroutine var_list_write

```

Write only a certain variable.

<Variables: public>+≡

```
public :: var_list_write_var
```

<Variables: procedures>+≡

```

recursive subroutine var_list_write_var &
    (var_list, name, unit, type, follow_link, model_name, show_ptr)
    type(var_list_t), intent(in), target :: var_list
    type(string_t), intent(in) :: name
    integer, intent(in), optional :: unit
    integer, intent(in), optional :: type
    logical, intent(in), optional :: follow_link
    type(string_t), intent(in), optional :: model_name
    logical, intent(in), optional :: show_ptr
    type(var_entry_t), pointer :: var
    integer :: u
    u = output_unit (unit); if (u < 0) return
    var => var_list_get_var_ptr &
        (var_list, name, type, follow_link=follow_link, defined=.true.)
    if (associated (var)) then
        call var_entry_write &
            (var, unit, model_name = model_name, show_ptr = show_ptr)
    else
        write (u, "(A)") char (name) // " = [undefined]"
    end if
end subroutine var_list_write_var

```

5.5.5 Tools

Return a pointer to the variable list linked to by the current one.

```
<Variables: public>+=  
    public :: var_list_get_next_ptr  
  
<Variables: procedures>+=  
    function var_list_get_next_ptr (var_list) result (next_ptr)  
        type(var_list_t), pointer :: next_ptr  
        type(var_list_t), intent(in) :: var_list  
        next_ptr => var_list%next  
    end function var_list_get_next_ptr
```

Return a pointer to the variable with the requested name. If no such name exists, return a null pointer. In that case, try the next list if present, unless follow_link is unset. If defined is set, ignore entries that exist but are undefined.

```
<Variables: public>+=  
    public :: var_list_get_var_ptr  
  
<Variables: procedures>+=  
    recursive function var_list_get_var_ptr &  
        (var_list, name, type, follow_link, defined) result (var)  
        type(var_entry_t), pointer :: var  
        type(var_list_t), intent(in), target :: var_list  
        type(string_t), intent(in) :: name  
        integer, intent(in), optional :: type  
        logical, intent(in), optional :: follow_link, defined  
        logical :: ignore_undef, search_next  
        ignore_undef = .true.; if (present (defined)) ignore_undef = .not. defined  
        var => var_list%first  
        if (present (type)) then  
            do while (associated (var))  
                if (var%type == type) then  
                    if (var%name == name) then  
                        if (ignore_undef .or. var%is_defined) return  
                    end if  
                end if  
                var => var%next  
            end do  
        else  
            do while (associated (var))  
                if (var%name == name) then  
                    if (ignore_undef .or. var%is_defined) return  
                end if  
                var => var%next  
            end do  
        end if  
        search_next = associated (var_list%next)  
        if (present (follow_link)) &  
            search_next = search_next .and. follow_link  
        if (search_next) &  
            var => var_list_get_var_ptr &  
                (var_list%next, name, type, defined=defined)
```

```
end function var_list_get_var_ptr
```

Return the variable type

<Variables: public>+≡

```
public :: var_list_get_type
```

<Variables: procedures>+≡

```
function var_list_get_type (var_list, name, follow_link) result (type)
  integer :: type
  type(string_t), intent(in) :: name
  type(var_list_t), intent(in), target :: var_list
  logical, intent(in), optional :: follow_link
  type(var_entry_t), pointer :: var
  var => var_list_get_var_ptr (var_list, name, follow_link=follow_link)
  if (associated (var)) then
    type = var%type
  else
    type = V_NONE
  end if
end function var_list_get_type
```

Return true if the variable exists.

<Variables: public>+≡

```
public :: var_list_exists
```

<Variables: procedures>+≡

```
function var_list_exists (var_list, name, follow_link) result (flag)
  logical :: flag
  type(string_t), intent(in) :: name
  type(var_list_t), intent(in), target :: var_list
  logical, intent(in), optional :: follow_link
  type(var_entry_t), pointer :: var
  var => var_list_get_var_ptr (var_list, name, follow_link=follow_link)
  flag = associated (var)
end function var_list_exists
```

Return true if the variable is declared as intrinsic.

<Variables: public>+≡

```
public :: var_list_is_intrinsic
```

<Variables: procedures>+≡

```
function var_list_is_intrinsic (var_list, name, follow_link) result (flag)
  logical :: flag
  type(string_t), intent(in) :: name
  type(var_list_t), intent(in), target :: var_list
  logical, intent(in), optional :: follow_link
  type(var_entry_t), pointer :: var
  var => var_list_get_var_ptr (var_list, name, follow_link=follow_link)
  if (associated (var)) then
    flag = var%is_intrinsic
  else
    flag = .false.
  end if
end function var_list_is_intrinsic
```


Return true if the value is known.

```

<Variables: public>+≡
    public :: var_list_is_known

<Variables: interfaces>+≡
    interface var_list_is_known
        module procedure var_list_is_known_s
        module procedure var_list_is_known_c
    end interface

<Variables: procedures>+≡
    function var_list_is_known_s (var_list, name, follow_link) result (flag)
        logical :: flag
        type(string_t), intent(in) :: name
        type(var_list_t), intent(in), target :: var_list
        logical, intent(in), optional :: follow_link
        type(var_entry_t), pointer :: var
        var => var_list_get_var_ptr (var_list, name, follow_link=follow_link)
        if (associated (var)) then
            flag = var%is_known
        else
            flag = .false.
        end if
    end function var_list_is_known_s

    function var_list_is_known_c (var_list, name, follow_link) result (flag)
        logical :: flag
        character(*), intent(in) :: name
        type(var_list_t), intent(in), target :: var_list
        logical, intent(in), optional :: follow_link
        flag = var_list_is_known_s (var_list, var_str (name), follow_link)
    end function var_list_is_known_c

```

Return true if the value is locked.

```

<Variables: public>+≡
    public :: var_list_is_locked

<Variables: procedures>+≡
    function var_list_is_locked (var_list, name, follow_link) result (flag)
        logical :: flag
        type(string_t), intent(in) :: name
        type(var_list_t), intent(in), target :: var_list
        logical, intent(in), optional :: follow_link
        type(var_entry_t), pointer :: var
        var => var_list_get_var_ptr (var_list, name, follow_link=follow_link)
        if (associated (var)) then
            flag = var_entry_is_locked (var)
        else
            flag = .false.
        end if
    end function var_list_is_locked

```

Return the value, assuming that the type is correct. We consider only variable entries that have been **defined**.

For convenience, allow both variable and fixed-length (literal) strings.

```

(Variables: public) +=
    public :: var_list_get_lval
    public :: var_list_get_ival
    public :: var_list_get_rval
    public :: var_list_get_cval
    public :: var_list_get_pval
    public :: var_list_get_aval
    public :: var_list_get_sval

(Variables: interfaces) +=
    interface var_list_get_lval
        module procedure var_list_get_lval_s
        module procedure var_list_get_lval_c
    end interface
    interface var_list_get_ival
        module procedure var_list_get_ival_s
        module procedure var_list_get_ival_c
    end interface
    interface var_list_get_rval
        module procedure var_list_get_rval_s
        module procedure var_list_get_rval_c
    end interface
    interface var_list_get_cval
        module procedure var_list_get_cval_s
        module procedure var_list_get_cval_c
    end interface
    interface var_list_get_pval
        module procedure var_list_get_pval_s
        module procedure var_list_get_pval_c
    end interface
    interface var_list_get_aval
        module procedure var_list_get_aval_s
        module procedure var_list_get_aval_c
    end interface
    interface var_list_get_sval
        module procedure var_list_get_sval_s
        module procedure var_list_get_sval_c
    end interface

(Variables: procedures) +=
    function var_list_get_lval_s (var_list, name, follow_link) result (lval)
        logical :: lval
        type(string_t), intent(in) :: name
        type(var_list_t), intent(in), target :: var_list
        logical, intent(in), optional :: follow_link
        type(var_entry_t), pointer :: var
        var => var_list_get_var_ptr &
            (var_list, name, V_LOG, follow_link, defined=.true.)
        if (associated (var)) then
            if (var_has_value (var)) then
                lval = var%lval
            else
                lval = .false.
            end if
        end if
    end function

```

```

        end if
    else
        lval = .false.
    end if
end function var_list_get_lval_s

function var_list_get_ival_s (var_list, name, follow_link) result (ival)
    integer :: ival
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr &
        (var_list, name, V_INT, follow_link, defined=.true.)
    if (associated (var)) then
        if (var_has_value (var)) then
            ival = var%ival
        else
            ival = 0
        end if
    else
        ival = 0
    end if
end function var_list_get_ival_s

function var_list_get_rval_s (var_list, name, follow_link) result (rval)
    real(default) :: rval
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr &
        (var_list, name, V_REAL, follow_link, defined=.true.)
    if (associated (var)) then
        if (var_has_value (var)) then
            rval = var%rval
        else
            rval = 0
        end if
    else
        rval = 0
    end if
end function var_list_get_rval_s

function var_list_get_cval_s (var_list, name, follow_link) result (cval)
    complex(default) :: cval
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr &
        (var_list, name, V_CMPLX, follow_link, defined=.true.)
    if (associated (var)) then
        if (var_has_value (var)) then

```

```

        cval = var%cval
    else
        cval = 0
    end if
else
    cval = 0
end if
end function var_list_get_cval_s

function var_list_get_aval_s (var_list, name, follow_link) result (aval)
    type(pdg_array_t) :: aval
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr &
        (var_list, name, V_PDG, follow_link, defined=.true.)
    if (associated (var)) then
        if (var_has_value (var)) then
            aval = var%aval
        end if
    end if
end function var_list_get_aval_s

function var_list_get_pval_s (var_list, name, follow_link) result (pval)
    type(subevt_t) :: pval
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr &
        (var_list, name, V_SEV, follow_link, defined=.true.)
    if (associated (var)) then
        if (var_has_value (var)) then
            pval = var%pval
        end if
    end if
end function var_list_get_pval_s

function var_list_get_sval_s (var_list, name, follow_link) result (sval)
    type(string_t) :: sval
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr &
        (var_list, name, V_STR, follow_link, defined=.true.)
    if (associated (var)) then
        if (var_has_value (var)) then
            sval = var%sval
        else
            sval = ""
        end if
    else

```

```

        sval = ""
    end if
end function var_list_get_sval_s

function var_list_get_lval_c (var_list, name, follow_link) result (lval)
    logical :: lval
    character(*), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    lval = var_list_get_lval_s (var_list, var_str (name), follow_link)
end function var_list_get_lval_c

function var_list_get_ival_c (var_list, name, follow_link) result (ival)
    integer :: ival
    character(*), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    ival = var_list_get_ival_s (var_list, var_str (name), follow_link)
end function var_list_get_ival_c

function var_list_get_rval_c (var_list, name, follow_link) result (rval)
    real(default) :: rval
    character(*), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    rval = var_list_get_rval_s (var_list, var_str (name), follow_link)
end function var_list_get_rval_c

function var_list_get_cval_c (var_list, name, follow_link) result (cval)
    complex(default) :: cval
    character(*), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    cval = var_list_get_cval_s (var_list, var_str (name), follow_link)
end function var_list_get_cval_c

function var_list_get_aval_c (var_list, name, follow_link) result (aval)
    type(pdg_array_t) :: aval
    character(*), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    aval = var_list_get_aval_s (var_list, var_str (name), follow_link)
end function var_list_get_aval_c

function var_list_get_pval_c (var_list, name, follow_link) result (pval)
    type(subvt_t) :: pval
    character(*), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: follow_link
    pval = var_list_get_pval_s (var_list, var_str (name), follow_link)
end function var_list_get_pval_c

function var_list_get_sval_c (var_list, name, follow_link) result (sval)
    type(string_t) :: sval

```

```

character(*), intent(in) :: name
type(var_list_t), intent(in), target :: var_list
logical, intent(in), optional :: follow_link
sval = var_list_get_sval_s (var_list, var_str (name), follow_link)
end function var_list_get_sval_c

```

Check for a valid value, given a pointer. Issue error messages if invalid.

```

<Variables: procedures>+≡
function var_has_value (var) result (valid)
  logical :: valid
  type(var_entry_t), pointer :: var
  if (associated (var)) then
    if (var%is_known) then
      valid = .true.
    else
      call msg_error ("The value of variable '" // char (var%name) &
        // "' is unknown but must be known at this point.")
      valid = .false.
    end if
  else
    call msg_error ("Variable '" // char (var%name) &
      // "' is undefined but must have a known value at this point.")
    valid = .false.
  end if
end function var_has_value

```

5.5.6 Process-specific variables

We allow the user to set a numeric process ID for each declared process.

```

<Variables: public>+≡
  public :: var_list_init_num_id

<Variables: procedures>+≡
  subroutine var_list_init_num_id (var_list, proc_id, num_id)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: proc_id
    integer, intent(in), optional :: num_id
    call var_list_set_procvar_int (var_list, proc_id, &
      var_str ("num_id"), num_id)
  end subroutine var_list_init_num_id

```

Integration results are stored in special variables. They are initialized by this subroutine. The values may or may not already be known.

```

<Variables: public>+≡
  public :: var_list_init_process_results

<Variables: procedures>+≡
  subroutine var_list_init_process_results (var_list, proc_id, &
    n_calls, integral, error, accuracy, chi2, efficiency)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: proc_id
    integer, intent(in), optional :: n_calls

```

```

real(default), intent(in), optional :: integral, error, accuracy
real(default), intent(in), optional :: chi2, efficiency
call var_list_set_procvar_int (var_list, proc_id, &
    var_str ("n_calls"), n_calls)
call var_list_set_procvar_real (var_list, proc_id, &
    var_str ("integral"), integral)
call var_list_set_procvar_real (var_list, proc_id, &
    var_str ("error"), error)
call var_list_set_procvar_real (var_list, proc_id, &
    var_str ("accuracy"), accuracy)
call var_list_set_procvar_real (var_list, proc_id, &
    var_str ("chi2"), chi2)
call var_list_set_procvar_real (var_list, proc_id, &
    var_str ("efficiency"), efficiency)
end subroutine var_list_init_process_results

```

{Variables: procedures}+≡

```

subroutine var_list_set_procvar_int (var_list, proc_id, name, ival)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: proc_id
    type(string_t), intent(in) :: name
    integer, intent(in), optional :: ival
    type(string_t) :: var_name
    type(var_entry_t), pointer :: var
    var_name = name // "(" // proc_id // ")"
    var => var_list_get_var_ptr (var_list, var_name)
    if (.not. associated (var)) then
        call var_list_append_int (var_list, var_name, ival, intrinsic=.true.)
    else if (present (ival)) then
        call var_list_set_int (var_list, var_name, ival, is_known=.true.)
    end if
end subroutine var_list_set_procvar_int

subroutine var_list_set_procvar_real (var_list, proc_id, name, rval)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: proc_id
    type(string_t), intent(in) :: name
    real(default), intent(in), optional :: rval
    type(string_t) :: var_name
    type(var_entry_t), pointer :: var
    var_name = name // "(" // proc_id // ")"
    var => var_list_get_var_ptr (var_list, var_name)
    if (.not. associated (var)) then
        call var_list_append_real (var_list, var_name, rval, intrinsic=.true.)
    else if (present (rval)) then
        call var_list_set_real (var_list, var_name, rval, is_known=.true.)
    end if
end subroutine var_list_set_procvar_real

```

5.5.7 Observable initialization

Observables are formally treated as variables, which however are evaluated each time the observable is used. The arguments (pointers) to evaluate and the function are part of the variable-list entry.

The procedure pointer should be set by this subroutine. This, however, triggers a bug in nagfor 5.2(649). As a workaround, we return the variable pointer, so the pointer can be set directly.

```
(Variables: procedures)+≡
subroutine var_list_set_obs (var_list, name, type, var, prt1, prt2)
  type(var_list_t), intent(inout) :: var_list
  type(string_t), intent(in) :: name
  integer, intent(in) :: type
  type(var_entry_t), pointer :: var
  type(prt_t), intent(in), target :: prt1
  type(prt_t), intent(in), optional, target :: prt2
  allocate (var)
  call var_entry_init_obs (var, name, type, prt1, prt2)
  call var_list_append (var_list, var)
end subroutine var_list_set_obs
```

Unary and binary observables are different. Most unary observables can be equally well evaluated for particle pairs. Binary observables cannot be evaluated for single particles.

```
(Variables: public)+≡
public :: var_list_set_observables_unary
public :: var_list_set_observables_binary

(Variables: procedures)+≡
subroutine var_list_set_observables_unary (var_list, prt1)
  type(var_list_t), intent(inout) :: var_list
  type(prt_t), intent(in), target :: prt1
  type(var_entry_t), pointer :: var
  call var_list_set_obs &
    (var_list, var_str ("PDG"), V_OBS1_INT, var, prt1)
  var% obs1_int => obs_pdg1
  call var_list_set_obs &
    (var_list, var_str ("Hel"), V_OBS1_INT, var, prt1)
  var% obs1_int => obs_helicity1
  call var_list_set_obs &
    (var_list, var_str ("M"), V_OBS1_REAL, var, prt1)
  var% obs1_real => obs_signed_mass1
  call var_list_set_obs &
    (var_list, var_str ("M2"), V_OBS1_REAL, var, prt1)
  var% obs1_real => obs_mass_squared1
  call var_list_set_obs &
    (var_list, var_str ("E"), V_OBS1_REAL, var, prt1)
  var% obs1_real => obs_energy1
  call var_list_set_obs &
    (var_list, var_str ("Px"), V_OBS1_REAL, var, prt1)
  var% obs1_real => obs_px1
  call var_list_set_obs &
    (var_list, var_str ("Py"), V_OBS1_REAL, var, prt1)
  var% obs1_real => obs_py1
```



```

call var_list_set_obs &
  (var_list, var_str ("Pz"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_pz1
call var_list_set_obs &
  (var_list, var_str ("P"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_p1
call var_list_set_obs &
  (var_list, var_str ("P1"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_pl1
call var_list_set_obs &
  (var_list, var_str ("Pt"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_pt1
call var_list_set_obs &
  (var_list, var_str ("Theta"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_theta1
call var_list_set_obs &
  (var_list, var_str ("Phi"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_phi1
call var_list_set_obs &
  (var_list, var_str ("Rap"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_rap1
call var_list_set_obs &
  (var_list, var_str ("Eta"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_eta1
call var_list_set_obs &
  (var_list, var_str ("Theta_RF"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_theta_rf1
call var_list_set_obs &
  (var_list, var_str ("Dist"), V_OBS1_REAL, var, prt1)
var% obs1_real => obs_dist1
call var_list_set_obs &
  (var_list, var_str ("_User_obs_real"), V_UOBS1_REAL, var, prt1)
call var_list_set_obs &
  (var_list, var_str ("_User_obs_int"), V_UOBS1_INT, var, prt1)
end subroutine var_list_set_observables_unary

subroutine var_list_set_observables_binary (var_list, prt1, prt2)
  type(var_list_t), intent(inout) :: var_list
  type(prt_t), intent(in), target :: prt1
  type(prt_t), intent(in), optional, target :: prt2
  type(var_entry_t), pointer :: var
  call var_list_set_obs &
    (var_list, var_str ("PDG"), V_OBS2_INT, var, prt1, prt2)
  var% obs2_int => obs_pdg2
  call var_list_set_obs &
    (var_list, var_str ("Hel"), V_OBS2_INT, var, prt1, prt2)
  var% obs2_int => obs_helicity2
  call var_list_set_obs &
    (var_list, var_str ("M"), V_OBS2_REAL, var, prt1, prt2)
  var% obs2_real => obs_signed_mass2
  call var_list_set_obs &
    (var_list, var_str ("M2"), V_OBS2_REAL, var, prt1, prt2)
  var% obs2_real => obs_mass_squared2
  call var_list_set_obs &

```

```

        (var_list, var_str ("E"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_energy2
call var_list_set_obs &
    (var_list, var_str ("Px"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_px2
call var_list_set_obs &
    (var_list, var_str ("Py"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_py2
call var_list_set_obs &
    (var_list, var_str ("Pz"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_pz2
call var_list_set_obs &
    (var_list, var_str ("P"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_p2
call var_list_set_obs &
    (var_list, var_str ("Pl"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_pl2
call var_list_set_obs &
    (var_list, var_str ("Pt"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_pt2
call var_list_set_obs &
    (var_list, var_str ("Theta"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_theta2
call var_list_set_obs &
    (var_list, var_str ("Phi"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_phi2
call var_list_set_obs &
    (var_list, var_str ("Rap"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_rap2
call var_list_set_obs &
    (var_list, var_str ("Eta"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_eta2
call var_list_set_obs &
    (var_list, var_str ("Theta_RF"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_theta_rf2
call var_list_set_obs &
    (var_list, var_str ("Dist"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_dist2
call var_list_set_obs &
    (var_list, var_str ("kT"), V_OBS2_REAL, var, prt1, prt2)
var% obs2_real => obs_ktmeasure
call var_list_set_obs &
    (var_list, var_str ("_User_obs_real"), V_UOBS2_REAL, var, prt1, prt2)
call var_list_set_obs &
    (var_list, var_str ("_User_obs_int"), V_UOBS2_INT, var, prt1, prt2)
end subroutine var_list_set_observables_binary

```

Check if a variable name is defined as an observable:

```

{Variables: procedures}+=
function string_is_observable_id (string) result (flag)
    logical :: flag
    type(string_t), intent(in) :: string
    select case (char (string))

```

```

    case ("PDG", "Hel", "M", "M2", "E", "Px", "Py", "Pz", "P", "Pl", "Pt", &
          "Theta", "Phi", "Rap", "Eta", "Theta_RF", "Dist", "kT")
        flag = .true.
    case default
        flag = .false.
    end select
end function string_is_observable_id

```

5.5.8 Observables

These are analogous to the unary and binary numeric functions listed above. An observable takes the `pval` component(s) of its one or two argument nodes and produces an integer or real value.

Integer-valued unary observables

The PDG code

```

<Variables: procedures>+≡
integer function obs_pdg1 (prt1) result (pdg)
    type(prt_t), intent(in) :: prt1
    pdg = prt_get_pdg (prt1)
end function obs_pdg1

```

The helicity. The return value is meaningful only if the particle is polarized, otherwise an invalid value is returned (-9).

```

<Variables: procedures>+≡
integer function obs_helicity1 (prt1) result (h)
    type(prt_t), intent(in) :: prt1
    if (prt_is_polarized (prt1)) then
        h = prt_get_helicity (prt1)
    else
        h = -9
    end if
end function obs_helicity1

```

Real-valued unary observables

The invariant mass squared, obtained from the separately stored value.

```

<Variables: procedures>+≡
real(default) function obs_mass_squared1 (prt1) result (p2)
    type(prt_t), intent(in) :: prt1
    p2 = prt_get_msq (prt1)
end function obs_mass_squared1

```

The signed invariant mass, which is the signed square root of the previous observable.

```

<Variables: procedures>+≡
real(default) function obs_signed_mass1 (prt1) result (m)
    type(prt_t), intent(in) :: prt1

```

```

    real(default) :: msq
    msq = prt_get_msq (prt1)
    m = sign (sqrt (abs (msq)), msq)
end function obs_signed_mass1

```

The particle energy

```

<Variables: procedures>+≡
real(default) function obs_energy1 (prt1) result (e)
    type(prt_t), intent(in) :: prt1
    e = energy (prt_get_momentum (prt1))
end function obs_energy1

```

Particle momentum (components)

```

<Variables: procedures>+≡
real(default) function obs_px1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = vector4_get_component (prt_get_momentum (prt1), 1)
end function obs_px1

real(default) function obs_py1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = vector4_get_component (prt_get_momentum (prt1), 2)
end function obs_py1

real(default) function obs_pz1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = vector4_get_component (prt_get_momentum (prt1), 3)
end function obs_pz1

real(default) function obs_p1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = space_part_norm (prt_get_momentum (prt1))
end function obs_p1

real(default) function obs_pl1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = longitudinal_part (prt_get_momentum (prt1))
end function obs_pl1

real(default) function obs_pt1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = transverse_part (prt_get_momentum (prt1))
end function obs_pt1

```

Polar and azimuthal angle (lab frame).

```

<Variables: procedures>+≡
real(default) function obs_theta1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = polar_angle (prt_get_momentum (prt1))
end function obs_theta1

real(default) function obs_phi1 (prt1) result (p)

```

```

    type(prt_t), intent(in) :: prt1
    p = azimuthal_angle (prt_get_momentum (prt1))
end function obs_phi1

```

Rapidity and pseudorapidity

```

<Variables: procedures>+=
real(default) function obs_rap1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = rapidity (prt_get_momentum (prt1))
end function obs_rap1

real(default) function obs_eta1 (prt1) result (p)
    type(prt_t), intent(in) :: prt1
    p = pseudorapidity (prt_get_momentum (prt1))
end function obs_eta1

```

Meaningless: Polar angle in the rest frame of the 2nd argument.

```

<Variables: procedures>+=
real(default) function obs_theta_rf1 (prt1) result (dist)
    type(prt_t), intent(in) :: prt1
    call msg_fatal (" 'Theta_RF' is undefined as unary observable")
    dist = 0
end function obs_theta_rf1

```

Meaningless: Distance on the η - ϕ cylinder.

```

<Variables: procedures>+=
real(default) function obs_dist1 (prt1) result (dist)
    type(prt_t), intent(in) :: prt1
    call msg_fatal (" 'Dist' is undefined as unary observable")
    dist = 0
end function obs_dist1

```

Integer-valued binary observables

These observables are meaningless as binary functions.

```

<Variables: procedures>+=
integer function obs_pdg2 (prt1, prt2) result (pdg)
    type(prt_t), intent(in) :: prt1, prt2
    call msg_fatal (" PDG_Code is undefined as binary observable")
    pdg = 0
end function obs_pdg2

integer function obs_helicity2 (prt1, prt2) result (h)
    type(prt_t), intent(in) :: prt1, prt2
    call msg_fatal (" Helicity is undefined as binary observable")
    h = 0
end function obs_helicity2

```

Real-valued binary observables

The invariant mass squared, obtained from the separately stored value.

```
{Variables: procedures}+=  
real(default) function obs_mass_squared2 (prt1, prt2) result (p2)  
  type(prt_t), intent(in) :: prt1, prt2  
  type(prt_t) :: prt  
  call prt_init_combine (prt, prt1, prt2)  
  p2 = prt_get_msq (prt)  
end function obs_mass_squared2
```

The signed invariant mass, which is the signed square root of the previous observable.

```
{Variables: procedures}+=  
real(default) function obs_signed_mass2 (prt1, prt2) result (m)  
  type(prt_t), intent(in) :: prt1, prt2  
  type(prt_t) :: prt  
  real(default) :: msq  
  call prt_init_combine (prt, prt1, prt2)  
  msq = prt_get_msq (prt)  
  m = sign (sqrt (abs (msq)), msq)  
end function obs_signed_mass2
```

The particle energy

```
{Variables: procedures}+=  
real(default) function obs_energy2 (prt1, prt2) result (e)  
  type(prt_t), intent(in) :: prt1, prt2  
  type(prt_t) :: prt  
  call prt_init_combine (prt, prt1, prt2)  
  e = energy (prt_get_momentum (prt))  
end function obs_energy2
```

Particle momentum (components)

```
{Variables: procedures}+=  
real(default) function obs_px2 (prt1, prt2) result (p)  
  type(prt_t), intent(in) :: prt1, prt2  
  type(prt_t) :: prt  
  call prt_init_combine (prt, prt1, prt2)  
  p = vector4_get_component (prt_get_momentum (prt), 1)  
end function obs_px2  
  
real(default) function obs_py2 (prt1, prt2) result (p)  
  type(prt_t), intent(in) :: prt1, prt2  
  type(prt_t) :: prt  
  call prt_init_combine (prt, prt1, prt2)  
  p = vector4_get_component (prt_get_momentum (prt), 2)  
end function obs_py2  
  
real(default) function obs_pz2 (prt1, prt2) result (p)  
  type(prt_t), intent(in) :: prt1, prt2  
  type(prt_t) :: prt  
  call prt_init_combine (prt, prt1, prt2)
```

```

    p = vector4_get_component (prt_get_momentum (prt), 3)
end function obs_pz2

```

```

real(default) function obs_p2 (prt1, prt2) result (p)
    type(prt_t), intent(in) :: prt1, prt2
    type(prt_t) :: prt
    call prt_init_combine (prt, prt1, prt2)
    p = space_part_norm (prt_get_momentum (prt))
end function obs_p2

```

```

real(default) function obs_pl2 (prt1, prt2) result (p)
    type(prt_t), intent(in) :: prt1, prt2
    type(prt_t) :: prt
    call prt_init_combine (prt, prt1, prt2)
    p = longitudinal_part (prt_get_momentum (prt))
end function obs_pl2

```

```

real(default) function obs_pt2 (prt1, prt2) result (p)
    type(prt_t), intent(in) :: prt1, prt2
    type(prt_t) :: prt
    call prt_init_combine (prt, prt1, prt2)
    p = transverse_part (prt_get_momentum (prt))
end function obs_pt2

```

Enclosed angle and azimuthal distance (lab frame).

(Variables: procedures)+≡

```

real(default) function obs_theta2 (prt1, prt2) result (p)
    type(prt_t), intent(in) :: prt1, prt2
    p = enclosed_angle (prt_get_momentum (prt1), prt_get_momentum (prt2))
end function obs_theta2

```

```

real(default) function obs_phi2 (prt1, prt2) result (p)
    type(prt_t), intent(in) :: prt1, prt2
    type(prt_t) :: prt
    call prt_init_combine (prt, prt1, prt2)
    p = azimuthal_distance (prt_get_momentum (prt1), prt_get_momentum (prt2))
end function obs_phi2

```

Rapidity and pseudorapidity distance

(Variables: procedures)+≡

```

real(default) function obs_rap2 (prt1, prt2) result (p)
    type(prt_t), intent(in) :: prt1, prt2
    p = rapidity_distance &
        (prt_get_momentum (prt1), prt_get_momentum (prt2))
end function obs_rap2

```

```

real(default) function obs_eta2 (prt1, prt2) result (p)
    type(prt_t), intent(in) :: prt1, prt2
    type(prt_t) :: prt
    call prt_init_combine (prt, prt1, prt2)
    p = pseudorapidity_distance &
        (prt_get_momentum (prt1), prt_get_momentum (prt2))
end function obs_eta2

```

Polar angle in the rest frame of the 2nd argument.

```
<Variables: procedures>+≡
  real(default) function obs_theta_rf2 (prt1, prt2) result (theta)
    type(prt_t), intent(in) :: prt1, prt2
    theta = enclosed_angle_rest_frame &
      (prt_get_momentum (prt1), prt_get_momentum (prt2))
  end function obs_theta_rf2
```

Distance on the η - ϕ cylinder.

```
<Variables: procedures>+≡
  real(default) function obs_dist2 (prt1, prt2) result (dist)
    type(prt_t), intent(in) :: prt1, prt2
    dist = eta_phi_distance &
      (prt_get_momentum (prt1), prt_get_momentum (prt2))
  end function obs_dist2
```

Durham kT measure.

```
<Variables: procedures>+≡
  real(default) function obs_ktmeasure (prt1, prt2) result (kt)
    type(prt_t), intent(in) :: prt1, prt2
    real (default) :: q2, e1, e2
    ! normalized scale to one for now!
    q2 = 1
    e1 = energy (prt_get_momentum (prt1))
    e2 = energy (prt_get_momentum (prt2))
    kt = (2/q2) * min(e1**2, e2**2) * &
      (1 - enclosed_angle_ct(prt_get_momentum (prt1), &
        prt_get_momentum (prt2)))
  end function obs_ktmeasure
```

5.5.9 Event variables

This is a transparent container for the local event variables: weight, squared matrix element. These variables are established as a target within the simulation record, assigned for each event, and can be referenced as local variables inside the event analysis.

```
<Variables: public>+≡
  public :: event_vars_t

<Variables: types>+≡
  type :: event_vars_t
    integer :: event_index = 0
    integer :: process_index = 0
    integer :: process_num_id = 0
    type(string_t) :: process_id
    integer :: n_in = 0
    integer :: n_out = 0
    integer :: n_tot = 0
    real(default) :: sqrts = 0
    real(default) :: sqrts_hat = 0
```



```

    real(default) :: sqme = 0
    real(default) :: sqme_ref = 0
    real(default) :: weight = 0
    real(default) :: excess = 0
end type event_vars_t

```

<Variables: public>+≡

```

    public :: event_vars_write

```

<Variables: procedures>+≡

```

subroutine event_vars_write (vars, unit)
    type(event_vars_t), intent(in) :: vars
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit)
    write (u, *) "Event index          = ", vars%event_index
    write (u, *) "Process index         = ", vars%process_index
    write (u, *) "Numerical process ID = ", vars%process_num_id
    write (u, *) "Process ID           = ", char (vars%process_id)
    write (u, *) "Process n_in          = ", vars%n_in
    write (u, *) "Process n_out         = ", vars%n_out
    write (u, *) "Process n_tot         = ", vars%n_tot
    write (u, *) "Event sqrts_hat        = ", vars%sqrts_hat
    write (u, *) "Event sqme            = ", vars%sqme
    write (u, *) "Event sqme(ref)       = ", vars%sqme_ref
    write (u, *) "Event weight          = ", vars%weight
    write (u, *) "Event excess weight   = ", vars%excess
end subroutine event_vars_write

```

The numerical and string process ID are not read or written in raw form.

<Variables: public>+≡

```

    public :: event_vars_write_raw
    public :: event_vars_read_raw

```

<Variables: procedures>+≡

```

subroutine event_vars_write_raw (vars, u, version)
    type(event_vars_t), intent(in) :: vars
    integer, intent(in) :: u
    integer, intent(in) :: version
    write (u) vars%event_index
    write (u) vars%process_index
    select case (version)
    case (3:)
        write (u) vars%n_in
        write (u) vars%n_out
        write (u) vars%n_tot
        write (u) vars%sqrts
        write (u) vars%sqrts_hat
    end select
    write (u) vars%sqme
    write (u) vars%sqme_ref
    write (u) vars%weight
    write (u) vars%excess
end subroutine event_vars_write_raw

```

```

subroutine event_vars_read_raw (vars, u, iostat, version)
  type(event_vars_t), intent(out) :: vars
  integer, intent(in) :: u
  integer, intent(out) :: iostat
  integer, intent(in) :: version
  read (u, iostat=iostat) vars%event_index
  if (iostat /= 0) return
  read (u, iostat=iostat) vars%process_index
  if (iostat /= 0) return
  select case (version)
  case (3:)
    read (u, iostat=iostat) vars%n_in
    read (u, iostat=iostat) vars%n_out
    read (u, iostat=iostat) vars%n_tot
    read (u, iostat=iostat) vars%sqrts
    read (u, iostat=iostat) vars%sqrts_hat
  end select
  if (iostat /= 0) return
  read (u, iostat=iostat) vars%sqme
  if (iostat /= 0) return
  read (u, iostat=iostat) vars%sqme_ref
  if (iostat /= 0) return
  read (u, iostat=iostat) vars%weight
  if (iostat /= 0) return
  read (u, iostat=iostat) vars%excess
end subroutine event_vars_read_raw

```

Append the pointers to the event variables to the local variable list.

```

<Variables: public>+≡
  public :: var_list_append_event_vars

<Variables: procedures>+≡
  subroutine var_list_append_event_vars (var_list, event_vars)
    type(var_list_t), intent(inout) :: var_list
    type(event_vars_t), intent(in), target :: event_vars
    logical, target, save :: known = .true.
    call var_list_append_int_ptr (var_list, &
      var_str ("event_index"), event_vars%event_index, &
      is_known = known, locked = .true., intrinsic = .true.)
    call var_list_append_int_ptr (var_list, &
      var_str ("process_index"), event_vars%process_index, &
      is_known = known, locked = .true., intrinsic = .true.)
    call var_list_append_int_ptr (var_list, &
      var_str ("process_num_id"), event_vars%process_num_id, &
      is_known = known, locked = .true., intrinsic = .true.)
    call var_list_append_string_ptr (var_list, &
      var_str ("process_id"), event_vars%process_id, &      ! $
      is_known = known, locked = .true., intrinsic = .true.)
    call var_list_append_int_ptr (var_list, &
      var_str ("n_in"), event_vars%n_in, &
      is_known = known, locked = .true., intrinsic = .true.)
    call var_list_append_int_ptr (var_list, &
      var_str ("n_out"), event_vars%n_out, &

```

```

        is_known = known, locked = .true., intrinsic = .true.)
call var_list_append_int_ptr (var_list, &
    var_str ("n_tot"), event_vars%n_tot, &
    is_known = known, locked = .true., intrinsic = .true.)
call var_list_append_real_ptr (var_list, &
    var_str ("sqrts"), event_vars%sqrts, &
    is_known = known, locked = .true., intrinsic = .true.)
call var_list_append_real_ptr (var_list, &
    var_str ("sqrts_hat"), event_vars%sqrts_hat, &
    is_known = known, locked = .true., intrinsic = .true.)
call var_list_append_real_ptr (var_list, &
    var_str ("sqme"), event_vars%sqme, &
    is_known = known, locked = .true., intrinsic = .true.)
call var_list_append_real_ptr (var_list, &
    var_str ("sqme_ref"), event_vars%sqme, &
    is_known = known, locked = .true., intrinsic = .true.)
call var_list_append_real_ptr (var_list, &
    var_str ("event_weight"), event_vars%weight, &
    is_known = known, locked = .true., intrinsic = .true.)
call var_list_append_real_ptr (var_list, &
    var_str ("event_excess_weight"), event_vars%excess, &
    is_known = known, locked = .true., intrinsic = .true.)
end subroutine var_list_append_event_vars

```

5.5.10 API for variable lists

Set a new value. If the variable holds a pointer, this pointer is followed, e.g., a model parameter is actually set. If `ignore` is set, do nothing if the variable does not exist. If `verbose` is set, echo the new value.

The specific versions:

```

<Variables: public>+≡
public :: var_list_set_log
public :: var_list_set_int
public :: var_list_set_real
public :: var_list_set_cmplx
public :: var_list_set_subevt
public :: var_list_set_pdg_array
public :: var_list_set_string

<Variables: procedures>+≡
subroutine var_list_set_log &
    (var_list, name, lval, is_known, ignore, verbose, model_name)
type(var_list_t), intent(inout), target :: var_list
type(string_t), intent(in) :: name
logical, intent(in) :: lval
logical, intent(in) :: is_known
logical, intent(in), optional :: ignore, verbose
type(string_t), intent(in), optional :: model_name
type(var_entry_t), pointer :: var
var => var_list_get_var_ptr (var_list, name, V_LOG)
if (associated (var)) then
    if (.not. var_entry_is_locked (var)) then
        select case (var%type)

```

```

        case (V_LOG)
            call var_entry_set_log (var, lval, is_known, verbose, model_name)
        case default
            call var_mismatch_error (name)
        end select
    else
        call var_locked_error (name)
    end if
else
    call var_missing_error (name, ignore)
end if
end subroutine var_list_set_log

subroutine var_list_set_int &
    (var_list, name, ival, is_known, ignore, verbose, model_name)
    type(var_list_t), intent(inout), target :: var_list
    type(string_t), intent(in) :: name
    integer, intent(in) :: ival
    logical, intent(in) :: is_known
    logical, intent(in), optional :: ignore, verbose
    type(string_t), intent(in), optional :: model_name
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr (var_list, name, V_INT)
    if (associated (var)) then
        if (.not. var_entry_is_locked (var)) then
            select case (var%type)
            case (V_INT)
                call var_entry_set_int (var, ival, is_known, verbose, model_name)
            case default
                call var_mismatch_error (name)
            end select
        else
            call var_locked_error (name)
        end if
    else
        call var_missing_error (name, ignore)
    end if
end subroutine var_list_set_int

subroutine var_list_set_real &
    (var_list, name, rval, is_known, ignore, verbose, model_name)
    type(var_list_t), intent(inout), target :: var_list
    type(string_t), intent(in) :: name
    real(default), intent(in) :: rval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: ignore, verbose
    type(string_t), intent(in), optional :: model_name
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr (var_list, name, V_REAL)
    if (associated (var)) then
        if (.not. var_entry_is_locked (var)) then
            select case (var%type)
            case (V_REAL)
                call var_entry_set_real (var, rval, is_known, verbose, model_name)
            end select
        end if
    else
        call var_missing_error (name, ignore)
    end if
end subroutine var_list_set_real

```

```

        case default
            call var_mismatch_error (name)
        end select
    else
        call var_locked_error (name)
    end if
else
    call var_missing_error (name, ignore)
end if
end subroutine var_list_set_real

subroutine var_list_set_cmplx &
    (var_list, name, cval, is_known, ignore, verbose, model_name)
    type(var_list_t), intent(inout), target :: var_list
    type(string_t), intent(in) :: name
    complex(default), intent(in) :: cval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: ignore, verbose
    type(string_t), intent(in), optional :: model_name
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr (var_list, name, V_CMPLX)
    if (associated (var)) then
        if (.not. var_entry_is_locked (var)) then
            select case (var%type)
            case (V_CMPLX)
                call var_entry_set_cmplx (var, cval, is_known, verbose, model_name)
            case default
                call var_mismatch_error (name)
            end select
        else
            call var_locked_error (name)
        end if
    else
        call var_missing_error (name, ignore)
    end if
end subroutine var_list_set_cmplx

subroutine var_list_set_pdg_array &
    (var_list, name, aval, is_known, ignore, verbose, model_name)
    type(var_list_t), intent(inout), target :: var_list
    type(string_t), intent(in) :: name
    type(pdg_array_t), intent(in) :: aval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: ignore, verbose
    type(string_t), intent(in), optional :: model_name
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr (var_list, name, V_PDG)
    if (associated (var)) then
        if (.not. var_entry_is_locked (var)) then
            select case (var%type)
            case (V_PDG)
                call var_entry_set_pdg_array &
                    (var, aval, is_known, verbose, model_name)
            case default

```

```

        call var_mismatch_error (name)
    end select
else
    call var_locked_error (name)
end if
else
    call var_missing_error (name, ignore)
end if
end subroutine var_list_set_pdg_array

subroutine var_list_set_subevt &
    (var_list, name, pval, is_known, ignore, verbose, model_name)
    type(var_list_t), intent(inout), target :: var_list
    type(string_t), intent(in) :: name
    type(subevt_t), intent(in) :: pval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: ignore, verbose
    type(string_t), intent(in), optional :: model_name
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr (var_list, name, V_SEV)
    if (associated (var)) then
        if (.not. var_entry_is_locked (var)) then
            select case (var%type)
            case (V_SEV)
                call var_entry_set_subevt &
                    (var, pval, is_known, verbose, model_name)
            case default
                call var_mismatch_error (name)
            end select
        else
            call var_locked_error (name)
        end if
    else
        call var_missing_error (name, ignore)
    end if
end subroutine var_list_set_subevt

subroutine var_list_set_string &
    (var_list, name, sval, is_known, ignore, verbose, model_name)
    type(var_list_t), intent(inout), target :: var_list
    type(string_t), intent(in) :: name
    type(string_t), intent(in) :: sval
    logical, intent(in) :: is_known
    logical, intent(in), optional :: ignore, verbose
    type(string_t), intent(in), optional :: model_name
    type(var_entry_t), pointer :: var
    var => var_list_get_var_ptr (var_list, name, V_STR)
    if (associated (var)) then
        if (.not. var_entry_is_locked (var)) then
            select case (var%type)
            case (V_STR)
                call var_entry_set_string &
                    (var, sval, is_known, verbose, model_name)
            case default

```

```

        call var_mismatch_error (name)
    end select
else
    call var_locked_error (name)
end if
else
    call var_missing_error (name, ignore)
end if
end subroutine var_list_set_string

subroutine var_mismatch_error (name)
    type(string_t), intent(in) :: name
    call msg_fatal ("Type mismatch for variable '" // char (name) // "'")
end subroutine var_mismatch_error

subroutine var_locked_error (name)
    type(string_t), intent(in) :: name
    call msg_error ("Variable '" // char (name) // "' is not user-definable")
end subroutine var_locked_error

subroutine var_missing_error (name, ignore)
    type(string_t), intent(in) :: name
    logical, intent(in), optional :: ignore
    logical :: error
    if (present (ignore)) then
        error = .not. ignore
    else
        error = .true.
    end if
    if (error) then
        call msg_fatal ("Variable '" // char (name) // "' has not been declared")
    end if
end subroutine var_missing_error

```

5.5.11 Linking model variables

The variable list of a model can be linked to the global variable list, so the model variables become available. However, the model may change during the execution of the command list, and this is not known at compile time. So, we make a copy of all variables that can be modified by the user; this will include all variables that are present in any of the models. At runtime, the linked list and the pointers to it can be exchanged, but the global variables will stay.

Append a single model variable to the local variable list. The pointer to the original is not set (yet). Check first if it already exists; in that case, do nothing.

<Variables: public>+≡

```
public :: var_list_init_copy
```

<Variables: procedures>+≡

```
subroutine var_list_init_copy (var_list, model_var, user)
    type(var_list_t), intent(inout), target :: var_list
    type(var_entry_t), intent(in), target :: model_var
    logical, intent(in), optional :: user

```

```

type(var_entry_t), pointer :: var
if (.not. var_list_exists &
    (var_list, model_var%name, follow_link = .false.)) then
    allocate (var)
    call var_entry_init_copy (var, model_var, user)
    call var_list_append (var_list, var)
end if
end subroutine var_list_init_copy

```

Append all model variables, or reuse (unset) them if they already exist. If `derived_only` is set, copy only derived parameters; these are real parameters that are locked. How should we (should we at all?) generalize this to complex parameters?

```

<Variables: public>+≡
    public :: var_list_init_copies

<Variables: procedures>+≡
    subroutine var_list_init_copies (var_list, model_vars, derived_only)
        type(var_list_t), intent(inout), target :: var_list
        type(var_list_t), intent(in) :: model_vars
        logical, intent(in), optional :: derived_only
        type(var_entry_t), pointer :: model_var, var
        type(string_t) :: name
        logical :: copy_all, locked, derived
        integer :: type
        copy_all = .true.
        if (present (derived_only)) copy_all = .not. derived_only
        model_var => model_vars%first
        do while (associated (model_var))
            name = var_entry_get_name (model_var)
            type = var_entry_get_type (model_var)
            locked = var_entry_is_locked (model_var)
            derived = type == V_REAL .and. locked
            if (copy_all .or. derived) then
                var => var_list_get_var_ptr &
                    (var_list, name, type, follow_link = .false.)
                if (associated (var)) then
                    call var_entry_clear_value (var)
                else
                    allocate (var)
                    call var_entry_init_copy (var, model_var)
                    call var_list_append (var_list, var)
                end if
            end if
            model_var => model_var%next
        end do
    end subroutine var_list_init_copies

```

Clear all previously allocated pointers to some model:

```

<Variables: procedures>+≡
    subroutine var_list_clear_original_pointers (var_list)
        type(var_list_t), intent(inout) :: var_list
        type(var_entry_t), pointer :: var

```



```

var => var_list%first
do while (associated (var))
  call var_entry_clear_original_pointer (var)
  var => var%next
end do
end subroutine var_list_clear_original_pointers

```

Assign the pointer to the original for a single variable.

```

{Variables: public}+=
  public :: var_list_set_original_pointer

{Variables: procedures}+=
  subroutine var_list_set_original_pointer (var_list, name, model_vars)
    type(var_list_t), intent(inout) :: var_list
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in), target :: model_vars
    type(var_entry_t), pointer :: var, model_var
    integer :: type
    model_var => var_list_get_var_ptr (model_vars, name)
    if (associated (model_var)) then
      type = var_entry_get_type (model_var)
      var => var_list_get_var_ptr (var_list, name, type, follow_link=.false.)
      if (associated (var)) then
        call var_entry_set_original_pointer (var, model_var)
      end if
    end if
  end subroutine var_list_set_original_pointer

```

Assign pointers to the originals for all variables in the model variable list.

```

{Variables: procedures}+=
  subroutine var_list_set_original_pointers (var_list, model_vars)
    type(var_list_t), intent(inout) :: var_list
    type(var_list_t), intent(in), target :: model_vars
    type(var_entry_t), pointer :: var, model_var
    type(string_t) :: name
    integer :: type
    model_var => model_vars%first
    do while (associated (model_var))
      name = var_entry_get_name (model_var)
      type = var_entry_get_type (model_var)
      var => var_list_get_var_ptr (var_list, name, type, follow_link=.false.)
      if (associated (var)) then
        call var_entry_set_original_pointer (var, model_var)
      end if
      model_var => model_var%next
    end do
  end subroutine var_list_set_original_pointers

```

Synchronize the local variable list with the model variable list (which is accessed by the pointers assigned in the previous subroutine).

If `reset_pointers` is unset, do not reset pointers but just update values where a variable is a copy. Resetting pointers is done only in the local variable

list.

```
<Variables: public>+=  
    public :: var_list_synchronize  
  
<Variables: procedures>+=  
    subroutine var_list_synchronize (var_list, model_vars, reset_pointers)  
        type(var_list_t), intent(inout) :: var_list  
        type(var_list_t), intent(in), target :: model_vars  
        logical, intent(in), optional :: reset_pointers  
        type(var_entry_t), pointer :: var  
        if (present (reset_pointers)) then  
            if (reset_pointers) then  
                call var_list_clear_original_pointers (var_list)  
                call var_list_set_original_pointers (var_list, model_vars)  
            end if  
        end if  
        var => var_list%first  
        do while (associated (var))  
            call var_entry_synchronize (var)  
            var => var%next  
        end do  
    end subroutine var_list_synchronize
```

This is the inverse operation: synchronize the model variable list with the current variable list. This is necessary after discarding a local variable list.

```
<Variables: public>+=  
    public :: var_list_restore  
  
<Variables: procedures>+=  
    recursive subroutine var_list_restore (var_list)  
        type(var_list_t), intent(inout) :: var_list  
        type(var_entry_t), pointer :: var  
        var => var_list%first  
        do while (associated (var))  
            call var_entry_restore (var)  
            var => var%next  
        end do  
    end subroutine var_list_restore
```

Mark all entries in the current variable list as undefined. This is done when a local variable list is discarded. If the local list is used again (by a loop), the entries will be re-initialized.

```
<Variables: public>+=  
    public :: var_list_undefine  
  
<Variables: procedures>+=  
    recursive subroutine var_list_undefine (var_list, follow_link)  
        type(var_list_t), intent(inout) :: var_list  
        logical, intent(in), optional :: follow_link  
        type(var_entry_t), pointer :: var  
        logical :: rec  
        rec = .true.; if (present (follow_link)) rec = follow_link  
        var => var_list%first  
        do while (associated (var))
```

```

        call var_entry_undefine (var)
        var => var%next
    end do
    if (rec .and. associated (var_list%next)) then
        call var_list_undefine (var_list%next, follow_link=follow_link)
    end if
end subroutine var_list_undefine

```

Make a deep copy of a variable list. The copy does not contain any pointer variables. Clear the original pointer after use, since the original may be lost when the copy is in use.

```

<Variables: public>+≡
    public :: var_list_init_snapshot

<Variables: procedures>+≡
    recursive subroutine var_list_init_snapshot (var_list, vars_in, follow_link)
        type(var_list_t), intent(out) :: var_list
        type(var_list_t), intent(in) :: vars_in
        logical, intent(in), optional :: follow_link
        type(var_entry_t), pointer :: var, var_in
        type(var_list_t), pointer :: var_list_next
        logical :: rec
        rec = .true.; if (present (follow_link)) rec = follow_link
        var_in => vars_in%first
        do while (associated (var_in))
            allocate (var)
            call var_entry_init_copy (var, var_in)
            call var_entry_set_original_pointer (var, var_in)
            call var_entry_synchronize (var)
            call var_entry_clear_original_pointer (var)
            call var_list_append (var_list, var)
            var_in => var_in%next
        end do
        if (rec .and. associated (vars_in%next)) then
            allocate (var_list_next)
            call var_list_init_snapshot (var_list_next, vars_in%next)
            call var_list_link (var_list, var_list_next)
        end if
    end subroutine var_list_init_snapshot

```

Check if a user variable can be set. The **new** flag is set if the user variable has an explicit declaration. If an error occurs, return **V_NONE** as variable type.

Also determine the actual type of generic numerical variables, which enter the procedure with type **V_NONE**.

```

<Variables: public>+≡
    public :: var_list_check_user_var

<Variables: procedures>+≡
    subroutine var_list_check_user_var (var_list, name, type, new)
        type(var_list_t), intent(in), target :: var_list
        type(string_t), intent(in) :: name
        integer, intent(inout) :: type
        logical, intent(in) :: new

```

```

type(var_entry_t), pointer :: var
if (string_is_observable_id (name)) then
  call msg_error ("Variable name '" // char (name) &
    // "' is reserved for an observable")
  type = V_NONE
  return
end if
if (string_is_integer_result_var (name)) type = V_INT
var => var_list_get_var_ptr (var_list, name)
if (associated (var)) then
  if (type == V_NONE) then
    type = var_entry_get_type (var)
  end if
  if (var_entry_is_locked (var)) then
    call msg_error ("Variable '" // char (name) &
      // "' is not user-definable")
    type = V_NONE
    return
  else if (new) then
    if (var_entry_is_intrinsic (var)) then
      call msg_error ("Intrinsic variable '" &
        // char (name) // "' redeclared")
      type = V_NONE
      return
    end if
    if (var_entry_get_type (var) /= type) then
      call msg_error ("Variable '" // char (name) // "' " &
        // "redeclared with different type")
      type = V_NONE
      return
    end if
  end if
else
  if (string_is_result_var (name)) then
    call msg_error ("Result variable '" // char (name) // "' " &
      // "set without prior integration")
    type = V_NONE
    return
  else if (string_is_num_id (name)) then
    call msg_error ("Numeric process ID '" // char (name) // "' " &
      // "set without process declaration")
    type = V_NONE
    return
  else if (.not. new) then
    call msg_error ("Variable '" // char (name) // "' " &
      // "set without declaration")
    type = V_NONE
    return
  end if
end if
end subroutine var_list_check_user_var

```

Check if a variable name is a result variable of integer type:

<Variables: procedures>+≡

```
function string_is_integer_result_var (string) result (flag)
  logical :: flag
  type(string_t), intent(in) :: string
  type(string_t) :: buffer, name, separator
  buffer = string
  call split (buffer, name, "(", separator=separator) ! ")"
  if (separator == "(") then
    select case (char (name))
      case ("num_id", "n_calls")
        flag = .true.
      case default
        flag = .false.
    end select
  else
    flag = .false.
  end if
end function string_is_integer_result_var
```

Check if a variable name is an integration-result variable:

<Variables: procedures>+≡

```
function string_is_result_var (string) result (flag)
  logical :: flag
  type(string_t), intent(in) :: string
  type(string_t) :: buffer, name, separator
  buffer = string
  call split (buffer, name, "(", separator=separator) ! ")"
  if (separator == "(") then
    select case (char (name))
      case ("n_calls", "integral", "error", "accuracy", "chi2", "efficiency")
        flag = .true.
      case default
        flag = .false.
    end select
  else
    flag = .false.
  end if
end function string_is_result_var
```

Check if a variable name is a numeric process ID:

<Variables: procedures>+≡

```
function string_is_num_id (string) result (flag)
  logical :: flag
  type(string_t), intent(in) :: string
  type(string_t) :: buffer, name, separator
  buffer = string
  call split (buffer, name, "(", separator=separator) ! ")"
  if (separator == "(") then
    select case (char (name))
      case ("num_id")
        flag = .true.
      case default
        flag = .false.
    end select
  else
    flag = .false.
  end if
end function string_is_num_id
```

```

        end select
    else
        flag = .false.
    end if
end function string_is_num_id

```

5.6 Expressions

In this module we define the structures needed to parse a user-defined expression, to compile it into an evaluation tree, and to evaluate it.

We have two flavors of expressions: one with particles and one without particles. The latter version is used for defining cut/selection criteria and for online analysis.

`<expressions.f90>`≡
<File header>

```

module expressions

    use iso_c_binding !NODEP!
<Use kinds>
<Use strings>
    use constants !NODEP!
<Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use md5
    use formats
    use sorting
    use ifiles
    use lexers
    use syntax_rules
    use parser
    use analysis
    use pdg_arrays
    use subevents
    use user_code_interface
    use variables

<Standard module head>

<Expressions: public>

<Expressions: types>

<Expressions: interfaces>

<Expressions: variables>

contains

<Expressions: procedures>

```

```
end module expressions
```

5.6.1 Tree nodes

The evaluation tree consists of branch nodes (unary and binary) and of leaf nodes, originating from a common root. The node object should be polymorphic. For the time being, polymorphism is emulated here. This means that we have to maintain all possibilities that the node may hold, including associated procedures as pointers.

The following parameter values characterize the node. Unary and binary operators have sub-nodes. The other are leaf nodes. Possible leafs are literal constants or named-parameter references.

$\langle \text{Expressions: types} \rangle \equiv$

```
integer, parameter :: EN_UNKNOWN = 0, EN_UNARY = 1, EN_BINARY = 2
integer, parameter :: EN_CONSTANT = 3, EN_VARIABLE = 4
integer, parameter :: EN_CONDITIONAL = 5, EN_BLOCK = 6
integer, parameter :: EN_RECORD_CMD = 7
integer, parameter :: EN_OBS1_INT = 11, EN_OBS2_INT = 12
integer, parameter :: EN_OBS1_REAL = 21, EN_OBS2_REAL = 22
integer, parameter :: EN_UOBS1_INT = 31, EN_UOBS2_INT = 32
integer, parameter :: EN_UOBS1_REAL = 41, EN_UOBS2_REAL = 42
integer, parameter :: EN_PRT_FUN_UNARY = 101, EN_PRT_FUN_BINARY = 102
integer, parameter :: EN_EVAL_FUN_UNARY = 111, EN_EVAL_FUN_BINARY = 112
integer, parameter :: EN_LOG_FUN_UNARY = 121, EN_LOG_FUN_BINARY = 122
integer, parameter :: EN_INT_FUN_UNARY = 131, EN_INT_FUN_BINARY = 132
integer, parameter :: EN_REAL_FUN_UNARY = 141, EN_REAL_FUN_BINARY = 142
integer, parameter :: EN_FORMAT_STR = 161
```

$\langle \text{Expressions: types} \rangle + \equiv$

```
type :: eval_node_t
private
type(string_t) :: tag
integer :: type = EN_UNKNOWN
integer :: result_type = V_NONE
type(var_list_t), pointer :: var_list => null ()
type(string_t) :: var_name
logical, pointer :: value_is_known => null ()
logical,          pointer :: lval => null ()
integer,          pointer :: ival => null ()
real(default),   pointer :: rval => null ()
complex(default), pointer :: cval => null ()
type(subevt_t),  pointer :: pval => null ()
type(pdg_array_t), pointer :: aval => null ()
type(string_t),  pointer :: sval => null ()
type(eval_node_t), pointer :: arg0 => null ()
type(eval_node_t), pointer :: arg1 => null ()
type(eval_node_t), pointer :: arg2 => null ()
type(eval_node_t), pointer :: arg3 => null ()
type(eval_node_t), pointer :: arg4 => null ()
procedure(obs_unary_int), nopass, pointer :: obs1_int => null ()
procedure(obs_unary_real), nopass, pointer :: obs1_real => null ()
```

```

procedure(obs_binary_int), nopass, pointer :: obs2_int => null ()
procedure(obs_binary_real), nopass, pointer :: obs2_real => null ()
integer, pointer :: prt_type => null ()
integer, pointer :: index => null ()
real(default), pointer :: tolerance => null ()
type(prt_t), pointer :: prt1 => null ()
type(prt_t), pointer :: prt2 => null ()
procedure(unary_log), nopass, pointer :: op1_log => null ()
procedure(unary_int), nopass, pointer :: op1_int => null ()
procedure(unary_real), nopass, pointer :: op1_real => null ()
procedure(unary_cmplx), nopass, pointer :: op1_cmplx => null ()
procedure(unary_pdg), nopass, pointer :: op1_pdg => null ()
procedure(unary_sev), nopass, pointer :: op1_sev => null ()
procedure(unary_str), nopass, pointer :: op1_str => null ()
procedure(unary_cut), nopass, pointer :: op1_cut => null ()
procedure(unary_evi), nopass, pointer :: op1_evi => null ()
procedure(unary_evr), nopass, pointer :: op1_evr => null ()
procedure(binary_log), nopass, pointer :: op2_log => null ()
procedure(binary_int), nopass, pointer :: op2_int => null ()
procedure(binary_real), nopass, pointer :: op2_real => null ()
procedure(binary_cmplx), nopass, pointer :: op2_cmplx => null ()
procedure(binary_pdg), nopass, pointer :: op2_pdg => null ()
procedure(binary_sev), nopass, pointer :: op2_sev => null ()
procedure(binary_str), nopass, pointer :: op2_str => null ()
procedure(binary_cut), nopass, pointer :: op2_cut => null ()
procedure(binary_evi), nopass, pointer :: op2_evi => null ()
procedure(binary_evr), nopass, pointer :: op2_evr => null ()
end type eval_node_t

```

Finalize a node recursively. Allocated constants are deleted, pointers are ignored.

$\langle \text{Expressions: procedures} \rangle \equiv$

```

recursive subroutine eval_node_final_rec (node)
  type(eval_node_t), intent(inout) :: node
  select case (node%type)
  case (EN_UNARY)
    call eval_node_final_rec (node%arg1)
  case (EN_BINARY)
    call eval_node_final_rec (node%arg1)
    call eval_node_final_rec (node%arg2)
  case (EN_CONDITIONAL)
    call eval_node_final_rec (node%arg0)
    call eval_node_final_rec (node%arg1)
    call eval_node_final_rec (node%arg2)
  case (EN_BLOCK)
    call eval_node_final_rec (node%arg0)
    call eval_node_final_rec (node%arg1)
  case (EN_PRT_FUN_UNARY, EN_EVAL_FUN_UNARY, &
        EN_LOG_FUN_UNARY, EN_INT_FUN_UNARY, EN_REAL_FUN_UNARY)
    if (associated (node%arg0)) call eval_node_final_rec (node%arg0)
    call eval_node_final_rec (node%arg1)
    deallocate (node%index)
    deallocate (node%prt1)
  end select
end subroutine eval_node_final_rec

```



```

case (EN_PRT_FUN_BINARY, EN_EVAL_FUN_BINARY, &
      EN_LOG_FUN_BINARY, EN_INT_FUN_BINARY, EN_REAL_FUN_BINARY)
  if (associated (node%arg0)) call eval_node_final_rec (node%arg0)
  call eval_node_final_rec (node%arg1)
  call eval_node_final_rec (node%arg2)
  deallocate (node%index)
  deallocate (node%prt1)
  deallocate (node%prt2)
case (EN_FORMAT_STR)
  if (associated (node%arg0)) call eval_node_final_rec (node%arg0)
  if (associated (node%arg1)) call eval_node_final_rec (node%arg1)
  deallocate (node%ival)
case (EN_RECORD_CMD)
  if (associated (node%arg0)) call eval_node_final_rec (node%arg0)
  if (associated (node%arg1)) call eval_node_final_rec (node%arg1)
  if (associated (node%arg2)) call eval_node_final_rec (node%arg2)
  if (associated (node%arg3)) call eval_node_final_rec (node%arg3)
  if (associated (node%arg4)) call eval_node_final_rec (node%arg4)
end select
select case (node%type)
case (EN_UNARY, EN_BINARY, EN_CONDITIONAL, EN_CONSTANT, EN_BLOCK, &
      EN_PRT_FUN_UNARY, EN_PRT_FUN_BINARY, &
      EN_EVAL_FUN_UNARY, EN_EVAL_FUN_BINARY, &
      EN_LOG_FUN_UNARY, EN_LOG_FUN_BINARY, &
      EN_INT_FUN_UNARY, EN_INT_FUN_BINARY, &
      EN_REAL_FUN_UNARY, EN_REAL_FUN_BINARY, &
      EN_FORMAT_STR, EN_RECORD_CMD)
  select case (node%result_type)
  case (V_LOG); deallocate (node%lval)
  case (V_INT); deallocate (node%ival)
  case (V_REAL); deallocate (node%rval)
  case (V_CMPLX); deallocate (node%cval)
  case (V_SEV); deallocate (node%pval)
  case (V_PDG); deallocate (node%aval)
  case (V_STR); deallocate (node%sval)
  end select
  deallocate (node%value_is_known)
end select
end subroutine eval_node_final_rec

```

Leaf nodes

Initialize a leaf node with a literal constant.

(Expressions: procedures) + \equiv

```

subroutine eval_node_init_log (node, lval)
  type(eval_node_t), intent(out) :: node
  logical, intent(in) :: lval
  node%type = EN_CONSTANT
  node%result_type = V_LOG
  allocate (node%lval, node%value_is_known)
  node%lval = lval
  node%value_is_known = .true.
end subroutine eval_node_init_log

```

```

subroutine eval_node_init_int (node, ival)
  type(eval_node_t), intent(out) :: node
  integer, intent(in) :: ival
  node%type = EN_CONSTANT
  node%result_type = V_INT
  allocate (node%ival, node%value_is_known)
  node%ival = ival
  node%value_is_known = .true.
end subroutine eval_node_init_int

subroutine eval_node_init_real (node, rval)
  type(eval_node_t), intent(out) :: node
  real(default), intent(in) :: rval
  node%type = EN_CONSTANT
  node%result_type = V_REAL
  allocate (node%rval, node%value_is_known)
  node%rval = rval
  node%value_is_known = .true.
end subroutine eval_node_init_real

subroutine eval_node_init_cmplx (node, cval)
  type(eval_node_t), intent(out) :: node
  complex(default), intent(in) :: cval
  node%type = EN_CONSTANT
  node%result_type = V_CMPLX
  allocate (node%cval, node%value_is_known)
  node%cval = cval
  node%value_is_known = .true.
end subroutine eval_node_init_cmplx

subroutine eval_node_init_subvt (node, pval)
  type(eval_node_t), intent(out) :: node
  type(subvt_t), intent(in) :: pval
  node%type = EN_CONSTANT
  node%result_type = V_SEV
  allocate (node%pval, node%value_is_known)
  node%pval = pval
  node%value_is_known = .true.
end subroutine eval_node_init_subvt

subroutine eval_node_init_pdg_array (node, aval)
  type(eval_node_t), intent(out) :: node
  type(pdg_array_t), intent(in) :: aval
  node%type = EN_CONSTANT
  node%result_type = V_PDG
  allocate (node%aval, node%value_is_known)
  node%aval = aval
  node%value_is_known = .true.
end subroutine eval_node_init_pdg_array

subroutine eval_node_init_string (node, sval)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: sval

```

```

node%type = EN_CONSTANT
node%result_type = V_STR
allocate (node%sval, node%value_is_known)
node%sval = sval
node%value_is_known = .true.
end subroutine eval_node_init_string

```

Initialize a leaf node with a pointer to a named parameter

(Expressions: procedures)+≡

```

subroutine eval_node_init_log_ptr (node, name, lval, is_known)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: name
  logical, intent(in), target :: lval
  logical, intent(in), target :: is_known
  node%type = EN_VARIABLE
  node%tag = name
  node%result_type = V_LOG
  node%lval => lval
  node%value_is_known => is_known
end subroutine eval_node_init_log_ptr

```

```

subroutine eval_node_init_int_ptr (node, name, ival, is_known)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: name
  integer, intent(in), target :: ival
  logical, intent(in), target :: is_known
  node%type = EN_VARIABLE
  node%tag = name
  node%result_type = V_INT
  node%ival => ival
  node%value_is_known => is_known
end subroutine eval_node_init_int_ptr

```

```

subroutine eval_node_init_real_ptr (node, name, rval, is_known)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: name
  real(default), intent(in), target :: rval
  logical, intent(in), target :: is_known
  node%type = EN_VARIABLE
  node%tag = name
  node%result_type = V_REAL
  node%rval => rval
  node%value_is_known => is_known
end subroutine eval_node_init_real_ptr

```

```

subroutine eval_node_init_cmplx_ptr (node, name, cval, is_known)
  type(eval_node_t), intent(out) :: node
  type(string_t), intent(in) :: name
  complex(default), intent(in), target :: cval
  logical, intent(in), target :: is_known
  node%type = EN_VARIABLE
  node%tag = name
  node%result_type = V_CMPLX
  node%cval => cval

```

```

    node%value_is_known => is_known
end subroutine eval_node_init_cmplx_ptr

subroutine eval_node_init_subevt_ptr (node, name, pval, is_known)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    type(subevt_t), intent(in), target :: pval
    logical, intent(in), target :: is_known
    node%type = EN_VARIABLE
    node%tag = name
    node%result_type = V_SEV
    node%pval => pval
    node%value_is_known => is_known
end subroutine eval_node_init_subevt_ptr

subroutine eval_node_init_pdg_array_ptr (node, name, aval, is_known)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    type(pdg_array_t), intent(in), target :: aval
    logical, intent(in), target :: is_known
    node%type = EN_VARIABLE
    node%tag = name
    node%result_type = V_PDG
    node%aval => aval
    node%value_is_known => is_known
end subroutine eval_node_init_pdg_array_ptr

subroutine eval_node_init_string_ptr (node, name, sval, is_known)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: name
    type(string_t), intent(in), target :: sval
    logical, intent(in), target :: is_known
    node%type = EN_VARIABLE
    node%tag = name
    node%result_type = V_STR
    node%sval => sval
    node%value_is_known => is_known
end subroutine eval_node_init_string_ptr

```

Branch nodes

Initialize a branch node, sub-nodes are given.

(Expressions: procedures) +≡

```

subroutine eval_node_init_branch (node, tag, result_type, arg1, arg2)
    type(eval_node_t), intent(out) :: node
    type(string_t), intent(in) :: tag
    integer, intent(in) :: result_type
    type(eval_node_t), intent(in), target :: arg1
    type(eval_node_t), intent(in), target, optional :: arg2
    if (present (arg2)) then
        node%type = EN_BINARY
    else
        node%type = EN_UNARY
    end if
end subroutine eval_node_init_branch

```

```

end if
node%tag = tag
node%result_type = result_type
call eval_node_allocate_value (node)
node%arg1 => arg1
if (present (arg2)) node%arg2 => arg2
end subroutine eval_node_init_branch

```

Allocate the node value according to the result type.

(Expressions: procedures)+≡

```

subroutine eval_node_allocate_value (node)
  type(eval_node_t), intent(inout) :: node
  select case (node%result_type)
  case (V_LOG); allocate (node%lval)
  case (V_INT); allocate (node%ival)
  case (V_REAL); allocate (node%rval)
  case (V_CMPLX); allocate (node%cval)
  case (V_PDG); allocate (node%aval)
  case (V_SEV); allocate (node%pval)
    call subevt_init (node%pval)
  case (V_STR); allocate (node%sval)
  end select
  allocate (node%value_is_known)
  node%value_is_known = .false.
end subroutine eval_node_allocate_value

```

Initialize a node with an observable. This includes a procedure pointer. The input is a variable entry from the stack which holds the necessary information.

The user-observable version does not contain a pointer. The appropriate procedure is called directly at evaluation time. Furthermore, this is a branch node with a reference to the string-expression node which determines the name of the user procedure.

(Expressions: procedures)+≡

```

subroutine eval_node_init_obs (node, var, arg)
  type(eval_node_t), intent(out) :: node
  type(var_entry_t), intent(in), target :: var
  type(eval_node_t), intent(in), target, optional :: arg
  integer :: var_type
  node%tag = var_entry_get_name (var)
  var_type = var_entry_get_type (var)
  select case (var_type)
  case (V_OBS1_INT)
    node%type = EN_OBS1_INT
    call var_entry_assign_obs1_int_ptr (node%obs1_int, var)
  case (V_OBS2_INT)
    node%type = EN_OBS2_INT
    call var_entry_assign_obs2_int_ptr (node%obs2_int, var)
  case (V_OBS1_REAL)
    node%type = EN_OBS1_REAL
    call var_entry_assign_obs1_real_ptr (node%obs1_real, var)
  case (V_OBS2_REAL)
    node%type = EN_OBS2_REAL
    call var_entry_assign_obs2_real_ptr (node%obs2_real, var)
  end select
end subroutine eval_node_init_obs

```

```

case (V_UOBS1_INT)
  node%type = EN_UOBS1_INT
case (V_UOBS2_INT)
  node%type = EN_UOBS2_INT
case (V_UOBS1_REAL)
  node%type = EN_UOBS1_REAL
case (V_UOBS2_REAL)
  node%type = EN_UOBS2_REAL
end select
select case (var_type)
case (V_OBS1_INT, V_OBS2_INT, V_UOBS1_INT, V_UOBS2_INT)
  node%result_type = V_INT
  allocate (node%ival, node%value_is_known)
  node%value_is_known = .false.
case (V_OBS1_REAL, V_OBS2_REAL, V_UOBS1_REAL, V_UOBS2_REAL)
  node%result_type = V_REAL
  allocate (node%rval, node%value_is_known)
  node%value_is_known = .false.
end select
select case (var_type)
case (V_OBS1_INT, V_OBS1_REAL, V_UOBS1_INT, V_UOBS1_REAL)
  node%prt1 => var_entry_get_prt1_ptr (var)
case (V_OBS2_INT, V_OBS2_REAL, V_UOBS2_INT, V_UOBS2_REAL)
  node%prt1 => var_entry_get_prt1_ptr (var)
  node%prt2 => var_entry_get_prt2_ptr (var)
end select
select case (var_type)
case (V_UOBS1_INT, V_UOBS1_REAL, V_UOBS2_INT, V_UOBS2_REAL)
  if (present (arg)) node%arg0 => arg
end select
end subroutine eval_node_init_obs

```

Initialize a block node which contains, in addition to the expression to be evaluated, a variable definition. The result type is not yet assigned, because we can compile the enclosed expression only after the var list is set up.

Note that the node always allocates a new variable list and appends it to the current one. Thus, if the variable redefines an existing one, it only shadows it but does not reset it. Any side-effects are therefore absent and need not be undone outside the block.

If the flag **new** is set, a variable is (re)declared. This must not be done for intrinsic variables. Vice versa, if the variable is not existent, the **new** flag is required.

(Expressions: procedures) +≡

```

subroutine eval_node_init_block (node, name, type, var_def, var_list)
  type(eval_node_t), intent(out), target :: node
  type(string_t), intent(in) :: name
  integer, intent(in) :: type
  type(eval_node_t), intent(in), target :: var_def
  type(var_list_t), intent(in), target :: var_list
  node%type = EN_BLOCK
  node%tag = "var_def"
  node%var_name = name
  node%arg1 => var_def

```

```

allocate (node%var_list)
call var_list_link (node%var_list, var_list)
if (var_def%type == EN_CONSTANT) then
  select case (type)
    case (V_LOG)
      call var_list_append_log (node%var_list, name, var_def%lval)
    case (V_INT)
      call var_list_append_int (node%var_list, name, var_def%ival)
    case (V_REAL)
      call var_list_append_real (node%var_list, name, var_def%rval)
    case (V_CMPLX)
      call var_list_append_cmplx (node%var_list, name, var_def%cval)
    case (V_PDG)
      call var_list_append_pdg_array &
        (node%var_list, name, var_def%aval)
    case (V_SEV)
      call var_list_append_subevt &
        (node%var_list, name, var_def%pval)
    case (V_STR)
      call var_list_append_string (node%var_list, name, var_def%sval)
  end select
else
  select case (type)
    case (V_LOG); call var_list_append_log_ptr &
      (node%var_list, name, var_def%lval, var_def%value_is_known)
    case (V_INT); call var_list_append_int_ptr &
      (node%var_list, name, var_def%ival, var_def%value_is_known)
    case (V_REAL); call var_list_append_real_ptr &
      (node%var_list, name, var_def%rval, var_def%value_is_known)
    case (V_CMPLX); call var_list_append_cmplx_ptr &
      (node%var_list, name, var_def%cval, var_def%value_is_known)
    case (V_PDG); call var_list_append_pdg_array_ptr &
      (node%var_list, name, var_def%aval, var_def%value_is_known)
    case (V_SEV); call var_list_append_subevt_ptr &
      (node%var_list, name, var_def%pval, var_def%value_is_known)
    case (V_STR); call var_list_append_string_ptr &
      (node%var_list, name, var_def%sval, var_def%value_is_known)
  end select
end if
end subroutine eval_node_init_block

```

Complete block initialization by assigning the expression to evaluate to `arg0`.

(Expressions: procedures) + \equiv

```

subroutine eval_node_set_expr (node, arg, result_type)
  type(eval_node_t), intent(inout) :: node
  type(eval_node_t), intent(in), target :: arg
  integer, intent(in), optional :: result_type
  if (present (result_type)) then
    node%result_type = result_type
  else
    node%result_type = arg%result_type
  end if
  call eval_node_allocate_value (node)
  node%arg0 => arg

```

```
end subroutine eval_node_set_expr
```

Initialize a conditional. There are three branches: the condition (evaluates to logical) and the two alternatives (evaluate both to the same arbitrary type).

(Expressions: procedures)+≡

```
subroutine eval_node_init_conditional (node, result_type, cond, arg1, arg2)
  type(eval_node_t), intent(out) :: node
  integer, intent(in) :: result_type
  type(eval_node_t), intent(in), target :: cond, arg1, arg2
  node%type = EN_CONDITIONAL
  node%tag = "cond"
  node%result_type = result_type
  call eval_node_allocate_value (node)
  node%arg0 => cond
  node%arg1 => arg1
  node%arg2 => arg2
end subroutine eval_node_init_conditional
```

Initialize a recording command (which evaluates to a logical constant). The first branch is the ID of the analysis object to be filled, the optional branches 1 to 4 are the values to be recorded.

If the event-weight pointer is null, we record values with unit weight. Otherwise, we use the value pointed to as event weight.

There can be up to four arguments which represent x , y , Δy , Δx . Therefore, this is the only node type that may fill four sub-nodes.

(Expressions: procedures)+≡

```
subroutine eval_node_init_record_cmd &
  (node, event_weight, id, arg1, arg2, arg3, arg4)
  type(eval_node_t), intent(out) :: node
  real(default), pointer :: event_weight
  type(eval_node_t), intent(in), target :: id
  type(eval_node_t), intent(in), optional, target :: arg1, arg2, arg3, arg4
  call eval_node_init_log (node, .true.)
  node%type = EN_RECORD_CMD
  node%rval => event_weight
  node%tag = "record_cmd"
  node%arg0 => id
  if (present (arg1)) then
    node%arg1 => arg1
    if (present (arg2)) then
      node%arg2 => arg2
      if (present (arg3)) then
        node%arg3 => arg3
        if (present (arg4)) then
          node%arg4 => arg4
        end if
      end if
    end if
  end if
end if
end if
end if
end if
end subroutine eval_node_init_record_cmd
```


Initialize a node for operations on subevents. The particle lists (one or two) are inserted as `arg1` and `arg2`. We allocated particle pointers as temporaries for iterating over particle lists. The procedure pointer which holds the function to evaluate for the subevents (e.g., combine, select) is also initialized.

(Expressions: procedures)+≡

```

subroutine eval_node_init_prt_fun_unary (node, arg1, name, proc)
  type(eval_node_t), intent(out) :: node
  type(eval_node_t), intent(in), target :: arg1
  type(string_t), intent(in) :: name
  procedure(unary_sev) :: proc
  node%type = EN_PRT_FUN_UNARY
  node%tag = name
  node%result_type = V_SEV
  call eval_node_allocate_value (node)
  node%arg1 => arg1
  allocate (node%index)
  allocate (node%prt1)
  node%op1_sev => proc
end subroutine eval_node_init_prt_fun_unary

subroutine eval_node_init_prt_fun_binary (node, arg1, arg2, name, proc)
  type(eval_node_t), intent(out) :: node
  type(eval_node_t), intent(in), target :: arg1, arg2
  type(string_t), intent(in) :: name
  procedure(binary_sev) :: proc
  node%type = EN_PRT_FUN_BINARY
  node%tag = name
  node%result_type = V_SEV
  call eval_node_allocate_value (node)
  node%arg1 => arg1
  node%arg2 => arg2
  allocate (node%index)
  allocate (node%prt1)
  allocate (node%prt2)
  node%op2_sev => proc
end subroutine eval_node_init_prt_fun_binary

```

Similar, but for particle-list functions that evaluate to a real value.

(Expressions: procedures)+≡

```

subroutine eval_node_init_eval_fun_unary (node, arg1, name)
  type(eval_node_t), intent(out) :: node
  type(eval_node_t), intent(in), target :: arg1
  type(string_t), intent(in) :: name
  node%type = EN_EVAL_FUN_UNARY
  node%tag = name
  node%result_type = V_REAL
  call eval_node_allocate_value (node)
  node%arg1 => arg1
  allocate (node%index)
  allocate (node%prt1)
end subroutine eval_node_init_eval_fun_unary

subroutine eval_node_init_eval_fun_binary (node, arg1, arg2, name)

```

```

type(eval_node_t), intent(out) :: node
type(eval_node_t), intent(in), target :: arg1, arg2
type(string_t), intent(in) :: name
node%type = EN_EVAL_FUN_BINARY
node%tag = name
node%result_type = V_REAL
call eval_node_allocate_value (node)
node%arg1 => arg1
node%arg2 => arg2
allocate (node%index)
allocate (node%prt1)
allocate (node%prt2)
end subroutine eval_node_init_eval_fun_binary

```

These are for particle-list functions that evaluate to a logical value.

(Expressions: procedures)+≡

```

subroutine eval_node_init_log_fun_unary (node, arg1, name, proc)
type(eval_node_t), intent(out) :: node
type(eval_node_t), intent(in), target :: arg1
type(string_t), intent(in) :: name
procedure(unary_cut) :: proc
node%type = EN_LOG_FUN_UNARY
node%tag = name
node%result_type = V_LOG
call eval_node_allocate_value (node)
node%arg1 => arg1
allocate (node%index)
allocate (node%prt1)
node%op1_cut => proc
end subroutine eval_node_init_log_fun_unary

subroutine eval_node_init_log_fun_binary (node, arg1, arg2, name, proc)
type(eval_node_t), intent(out) :: node
type(eval_node_t), intent(in), target :: arg1, arg2
type(string_t), intent(in) :: name
procedure(binary_cut) :: proc
node%type = EN_LOG_FUN_BINARY
node%tag = name
node%result_type = V_LOG
call eval_node_allocate_value (node)
node%arg1 => arg1
node%arg2 => arg2
allocate (node%index)
allocate (node%prt1)
allocate (node%prt2)
node%op2_cut => proc
end subroutine eval_node_init_log_fun_binary

```

These are for particle-list functions that evaluate to an integer value.

(Expressions: procedures)+≡

```

subroutine eval_node_init_int_fun_unary (node, arg1, name, proc)
type(eval_node_t), intent(out) :: node
type(eval_node_t), intent(in), target :: arg1

```

```

    type(string_t), intent(in) :: name
    procedure(unary_evi) :: proc
    node%type = EN_INT_FUN_UNARY
    node%tag = name
    node%result_type = V_INT
    call eval_node_allocate_value (node)
    node%arg1 => arg1
    allocate (node%index)
    allocate (node%prt1)
    node%op1_evi => proc
end subroutine eval_node_init_int_fun_unary

subroutine eval_node_init_int_fun_binary (node, arg1, arg2, name, proc)
    type(eval_node_t), intent(out) :: node
    type(eval_node_t), intent(in), target :: arg1, arg2
    type(string_t), intent(in) :: name
    procedure(binary_evi) :: proc
    node%type = EN_INT_FUN_BINARY
    node%tag = name
    node%result_type = V_INT
    call eval_node_allocate_value (node)
    node%arg1 => arg1
    node%arg2 => arg2
    allocate (node%index)
    allocate (node%prt1)
    allocate (node%prt2)
    node%op2_evi => proc
end subroutine eval_node_init_int_fun_binary

```

These are for particle-list functions that evaluate to a real value.

(*Expressions: procedures*)+≡

```

subroutine eval_node_init_real_fun_unary (node, arg1, name, proc)
    type(eval_node_t), intent(out) :: node
    type(eval_node_t), intent(in), target :: arg1
    type(string_t), intent(in) :: name
    procedure(unary_evr) :: proc
    node%type = EN_REAL_FUN_UNARY
    node%tag = name
    node%result_type = V_INT
    call eval_node_allocate_value (node)
    node%arg1 => arg1
    allocate (node%index)
    allocate (node%prt1)
    node%op1_evr => proc
end subroutine eval_node_init_real_fun_unary

subroutine eval_node_init_real_fun_binary (node, arg1, arg2, name, proc)
    type(eval_node_t), intent(out) :: node
    type(eval_node_t), intent(in), target :: arg1, arg2
    type(string_t), intent(in) :: name
    procedure(binary_evr) :: proc
    node%type = EN_REAL_FUN_BINARY
    node%tag = name
    node%result_type = V_INT

```

```

call eval_node_allocate_value (node)
node%arg1 => arg1
node%arg2 => arg2
allocate (node%index)
allocate (node%prt1)
allocate (node%prt2)
node%op2_evr => proc
end subroutine eval_node_init_real_fun_binary

```

Initialize a node for a string formatting function (sprintf).

(Expressions: procedures)+≡

```

subroutine eval_node_init_format_string (node, fmt, arg, name, n_args)
  type(eval_node_t), intent(out) :: node
  type(eval_node_t), pointer :: fmt, arg
  type(string_t), intent(in) :: name
  integer, intent(in) :: n_args
  node%type = EN_FORMAT_STR
  node%tag = name
  node%result_type = V_STR
  call eval_node_allocate_value (node)
  node%arg0 => fmt
  node%arg1 => arg
  allocate (node%ival)
  node%ival = n_args
end subroutine eval_node_init_format_string

```

If particle functions depend upon a condition (or an expression is evaluated), the observables that can be evaluated for the given particles have to be thrown on the local variable stack. This is done here. Each observable is initialized with the particle pointers which have been allocated for the node.

The integer variable that is referred to by the `Index` pseudo-observable is always known when it is referred to.

(Expressions: procedures)+≡

```

subroutine eval_node_set_observables (node, var_list)
  type(eval_node_t), intent(inout) :: node
  type(var_list_t), intent(in), target :: var_list
  logical, save, target :: known = .true.
  allocate (node%var_list)
  call var_list_link (node%var_list, var_list)
  allocate (node%index)
  call var_list_append_int_ptr &
    (node%var_list, var_str ("Index"), node%index, known, intrinsic=.true.)
  if (.not. associated (node%prt2)) then
    call var_list_set_observables_unary &
      (node%var_list, node%prt1)
  else
    call var_list_set_observables_binary &
      (node%var_list, node%prt1, node%prt2)
  end if
end subroutine eval_node_set_observables

```

Output

(Expressions: procedures)+≡

```
subroutine eval_node_write (node, unit, indent)
  type(eval_node_t), intent(in) :: node
  integer, intent(in), optional :: unit
  integer, intent(in), optional :: indent
  integer :: u, ind
  u = output_unit (unit); if (u < 0) return
  ind = 0; if (present (indent)) ind = indent
  write (u, "(A)", advance="no") repeat ("| ", ind) // "o "
  select case (node%type)
  case (EN_UNARY, EN_BINARY, EN_CONDITIONAL, &
        EN_PRT_FUN_UNARY, EN_PRT_FUN_BINARY, &
        EN_EVAL_FUN_UNARY, EN_EVAL_FUN_BINARY, &
        EN_LOG_FUN_UNARY, EN_LOG_FUN_BINARY, &
        EN_INT_FUN_UNARY, EN_INT_FUN_BINARY, &
        EN_REAL_FUN_UNARY, EN_REAL_FUN_BINARY)
    write (u, "(A)", advance="no") "[" // char (node%tag) // "]" = "
  case (EN_CONSTANT)
    write (u, "(A)", advance="no") "[const] ="
  case (EN_VARIABLE)
    write (u, "(A)", advance="no") char (node%tag) // " =>"
  case (EN_OBS1_INT, EN_OBS2_INT, EN_OBS1_REAL, EN_OBS2_REAL, &
        EN_UOBS1_INT, EN_UOBS2_INT, EN_UOBS1_REAL, EN_UOBS2_REAL)
    write (u, "(A)", advance="no") char (node%tag) // " ="
  case (EN_BLOCK)
    write (u, "(A)", advance="no") "[" // char (node%tag) // "]" // &
      char (node%var_name) // " [expr] = "
  case default
    write (u, "(A)", advance="no") "[???] ="
  end select
  select case (node%result_type)
  case (V_LOG)
    if (node%value_is_known) then
      if (node%lval) then
        write (u, *) "true"
      else
        write (u, *) "false"
      end if
    else
      write (u, *) "[unknown logical]"
    end if
  case (V_INT)
    if (node%value_is_known) then
      write (u, *) node%ival
    else
      write (u, *) "[unknown integer]"
    end if
  case (V_REAL)
    if (node%value_is_known) then
      write (u, *) node%rval
    else
      write (u, *) "[unknown real]"
    end if
  end select
```

```

        end if
    case (V_CMPLX)
        if (node%value_is_known) then
            write (u, *) node%cval
        else
            write (u, *) "[unknown complex]"
        end if
    case (V_SEV)
        if (char (node%tag) == "@evt") then
            write (u, *) "[event subevent]"
        else if (node%value_is_known) then
            call subevt_write &
                (node%pval, unit, prefix = repeat ("| ", ind + 1))
        else
            write (u, *) "[unknown subevent]"
        end if
    case (V_PDG)
        call pdg_array_write (node%aval, u); write (u, *)
    case (V_STR)
        if (node%value_is_known) then
            write (u, "(A)" ' "' // char (node%sval) // "'
        else
            write (u, *) "[unknown string]"
        end if
    case default
        write (u, *) "[empty]"
    end select
select case (node%type)
case (EN_OBS1_INT, EN_OBS1_REAL, EN_UOBS1_INT, EN_UOBS1_REAL)
    write (u, "(A,6x,A)", advance="no") repeat ("| ", ind), "prt1 ="
    call prt_write (node%prt1, unit)
case (EN_OBS2_INT, EN_OBS2_REAL, EN_UOBS2_INT, EN_UOBS2_REAL)
    write (u, "(A,6x,A)", advance="no") repeat ("| ", ind), "prt1 ="
    call prt_write (node%prt1, unit)
    write (u, "(A,6x,A)", advance="no") repeat ("| ", ind), "prt2 ="
    call prt_write (node%prt2, unit)
end select
end subroutine eval_node_write

recursive subroutine eval_node_write_rec (node, unit, indent)
    type(eval_node_t), intent(in) :: node
    integer, intent(in), optional :: unit
    integer, intent(in), optional :: indent
    integer :: u, ind
    u = output_unit (unit); if (u < 0) return
    ind = 0; if (present (indent)) ind = indent
    call eval_node_write (node, unit, indent)
    select case (node%type)
    case (EN_UNARY)
        if (associated (node%arg0)) &
            call eval_node_write_rec (node%arg0, unit, ind+1)
        call eval_node_write_rec (node%arg1, unit, ind+1)
    case (EN_BINARY)
        if (associated (node%arg0)) &

```

```

        call eval_node_write_rec (node%arg0, unit, ind+1)
        call eval_node_write_rec (node%arg1, unit, ind+1)
        call eval_node_write_rec (node%arg2, unit, ind+1)
    case (EN_BLOCK)
        call eval_node_write_rec (node%arg1, unit, ind+1)
        call eval_node_write_rec (node%arg0, unit, ind+1)
    case (EN_CONDITIONAL)
        call eval_node_write_rec (node%arg0, unit, ind+1)
        call eval_node_write_rec (node%arg1, unit, ind+1)
        call eval_node_write_rec (node%arg2, unit, ind+1)
    case (EN_PRT_FUN_UNARY, EN_EVAL_FUN_UNARY, &
          EN_LOG_FUN_UNARY, EN_INT_FUN_UNARY, EN_REAL_FUN_UNARY)
        if (associated (node%arg0)) &
            call eval_node_write_rec (node%arg0, unit, ind+1)
        call eval_node_write_rec (node%arg1, unit, ind+1)
    case (EN_PRT_FUN_BINARY, EN_EVAL_FUN_BINARY, &
          EN_LOG_FUN_BINARY, EN_INT_FUN_BINARY, EN_REAL_FUN_BINARY)
        if (associated (node%arg0)) &
            call eval_node_write_rec (node%arg0, unit, ind+1)
        call eval_node_write_rec (node%arg1, unit, ind+1)
        call eval_node_write_rec (node%arg2, unit, ind+1)
    end select
end subroutine eval_node_write_rec

```

5.6.2 Operation types

For the operations associated to evaluation tree nodes, we define abstract interfaces for all cases.

Particles/subevents are transferred by-reference, to avoid unnecessary copying. Therefore, subroutines instead of functions. (Furthermore, the function version of `unary_prt` triggers an obscure bug in nagfor 5.2(649) [invalid C code].)

(Expressions: interfaces)≡

```

abstract interface
    logical function unary_log (arg)
        import eval_node_t
        type(eval_node_t), intent(in) :: arg
    end function unary_log
end interface
abstract interface
    integer function unary_int (arg)
        import eval_node_t
        type(eval_node_t), intent(in) :: arg
    end function unary_int
end interface
abstract interface
    real(default) function unary_real (arg)
        import default
        import eval_node_t
        type(eval_node_t), intent(in) :: arg
    end function unary_real
end interface
abstract interface

```

```

        complex(default) function unary_cmplx (arg)
            import default
            import eval_node_t
            type(eval_node_t), intent(in) :: arg
        end function unary_cmplx
end interface
abstract interface
    subroutine unary_pdg (pdg_array, arg)
        import pdg_array_t
        import eval_node_t
        type(pdg_array_t), intent(out) :: pdg_array
        type(eval_node_t), intent(in) :: arg
    end subroutine unary_pdg
end interface
abstract interface
    subroutine unary_sev (subevt, arg, arg0)
        import subevt_t
        import eval_node_t
        type(subevt_t), intent(inout) :: subevt
        type(eval_node_t), intent(in) :: arg
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine unary_sev
end interface
abstract interface
    subroutine unary_str (string, arg)
        import string_t
        import eval_node_t
        type(string_t), intent(out) :: string
        type(eval_node_t), intent(in) :: arg
    end subroutine unary_str
end interface
abstract interface
    logical function unary_cut (arg1, arg0)
        import eval_node_t
        type(eval_node_t), intent(in) :: arg1
        type(eval_node_t), intent(inout) :: arg0
    end function unary_cut
end interface
abstract interface
    subroutine unary_evi (ival, arg1, arg0)
        import eval_node_t
        integer, intent(out) :: ival
        type(eval_node_t), intent(in) :: arg1
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine unary_evi
end interface
abstract interface
    subroutine unary_evr (rval, arg1, arg0)
        import eval_node_t, default
        real(default), intent(out) :: rval
        type(eval_node_t), intent(in) :: arg1
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine unary_evr
end interface

```



```

abstract interface
  logical function binary_log (arg1, arg2)
    import eval_node_t
    type(eval_node_t), intent(in) :: arg1, arg2
  end function binary_log
end interface
abstract interface
  integer function binary_int (arg1, arg2)
    import eval_node_t
    type(eval_node_t), intent(in) :: arg1, arg2
  end function binary_int
end interface
abstract interface
  real(default) function binary_real (arg1, arg2)
    import default
    import eval_node_t
    type(eval_node_t), intent(in) :: arg1, arg2
  end function binary_real
end interface
abstract interface
  complex(default) function binary_cmplx (arg1, arg2)
    import default
    import eval_node_t
    type(eval_node_t), intent(in) :: arg1, arg2
  end function binary_cmplx
end interface
abstract interface
  subroutine binary_pdg (pdg_array, arg1, arg2)
    import pdg_array_t
    import eval_node_t
    type(pdg_array_t), intent(out) :: pdg_array
    type(eval_node_t), intent(in) :: arg1, arg2
  end subroutine binary_pdg
end interface
abstract interface
  subroutine binary_sev (subevt, arg1, arg2, arg0)
    import subevt_t
    import eval_node_t
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: arg1, arg2
    type(eval_node_t), intent(inout), optional :: arg0
  end subroutine binary_sev
end interface
abstract interface
  subroutine binary_str (string, arg1, arg2)
    import string_t
    import eval_node_t
    type(string_t), intent(out) :: string
    type(eval_node_t), intent(in) :: arg1, arg2
  end subroutine binary_str
end interface
abstract interface
  logical function binary_cut (arg1, arg2, arg0)
    import eval_node_t

```

```

        type(eval_node_t), intent(in) :: arg1, arg2
        type(eval_node_t), intent(inout) :: arg0
    end function binary_cut
end interface
abstract interface
    subroutine binary_evi (ival, arg1, arg2, arg0)
        import eval_node_t
        integer, intent(out) :: ival
        type(eval_node_t), intent(in) :: arg1, arg2
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine binary_evi
end interface
abstract interface
    subroutine binary_evr (rval, arg1, arg2, arg0)
        import eval_node_t, default
        real(default), intent(out) :: rval
        type(eval_node_t), intent(in) :: arg1, arg2
        type(eval_node_t), intent(inout), optional :: arg0
    end subroutine binary_evr
end interface

```

The following subroutines set the procedure pointer:

(Expressions: procedures) + \equiv

```

subroutine eval_node_set_op1_log (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_log) :: op
    en%op1_log => op
end subroutine eval_node_set_op1_log

subroutine eval_node_set_op1_int (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_int) :: op
    en%op1_int => op
end subroutine eval_node_set_op1_int

subroutine eval_node_set_op1_real (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_real) :: op
    en%op1_real => op
end subroutine eval_node_set_op1_real

subroutine eval_node_set_op1_cmplx (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_cmplx) :: op
    en%op1_cmplx => op
end subroutine eval_node_set_op1_cmplx

subroutine eval_node_set_op1_pdg (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_pdg) :: op
    en%op1_pdg => op
end subroutine eval_node_set_op1_pdg

subroutine eval_node_set_op1_sev (en, op)

```

```

        type(eval_node_t), intent(inout) :: en
        procedure(unary_sev) :: op
        en%op1_sev => op
    end subroutine eval_node_set_op1_sev

subroutine eval_node_set_op1_str (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(unary_str) :: op
    en%op1_str => op
end subroutine eval_node_set_op1_str

subroutine eval_node_set_op2_log (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(binary_log) :: op
    en%op2_log => op
end subroutine eval_node_set_op2_log

subroutine eval_node_set_op2_int (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(binary_int) :: op
    en%op2_int => op
end subroutine eval_node_set_op2_int

subroutine eval_node_set_op2_real (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(binary_real) :: op
    en%op2_real => op
end subroutine eval_node_set_op2_real

subroutine eval_node_set_op2_cmplx (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(binary_cmplx) :: op
    en%op2_cmplx => op
end subroutine eval_node_set_op2_cmplx

subroutine eval_node_set_op2_pdg (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(binary_pdg) :: op
    en%op2_pdg => op
end subroutine eval_node_set_op2_pdg

subroutine eval_node_set_op2_sev (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(binary_sev) :: op
    en%op2_sev => op
end subroutine eval_node_set_op2_sev

subroutine eval_node_set_op2_str (en, op)
    type(eval_node_t), intent(inout) :: en
    procedure(binary_str) :: op
    en%op2_str => op
end subroutine eval_node_set_op2_str

```

5.6.3 Specific operators

Our expression syntax contains all Fortran functions that make sense. These functions have to be provided in a form that they can be used in procedures pointers, and have the abstract interfaces above. For some intrinsic functions, we could use specific versions provided by Fortran directly. However, this has two drawbacks: (i) We should work with the values instead of the eval-nodes as argument, which complicates the interface; (ii) more importantly, the `default` real type need not be equivalent to double precision. This would, at least, introduce system dependencies. Finally, for operators there are no specific versions.

Therefore, we write wrappers for all possible functions, at the expense of some overhead.

Binary numerical functions

(Expressions: procedures) + \equiv

```
integer function add_ii (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%ival + en2%ival
end function add_ii
real(default) function add_ir (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%ival + en2%rval
end function add_ir
complex(default) function add_ic (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%ival + en2%cval
end function add_ic
real(default) function add_ri (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%rval + en2%ival
end function add_ri
complex(default) function add_ci (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%cval + en2%ival
end function add_ci
complex(default) function add_cr (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%cval + en2%rval
end function add_cr
complex(default) function add_rc (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%rval + en2%cval
end function add_rc
real(default) function add_rr (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%rval + en2%rval
end function add_rr
complex(default) function add_cc (en1, en2) result (y)
  type(eval_node_t), intent(in) :: en1, en2
  y = en1%cval + en2%cval
end function add_cc

integer function sub_ii (en1, en2) result (y)
```

```

        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival - en2%ival
    end function sub_ii
    real(default) function sub_ir (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival - en2%rval
    end function sub_ir
    real(default) function sub_ri (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval - en2%ival
    end function sub_ri
    complex(default) function sub_ic (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival - en2%cval
    end function sub_ic
    complex(default) function sub_ci (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval - en2%ival
    end function sub_ci
    complex(default) function sub_cr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval - en2%rval
    end function sub_cr
    complex(default) function sub_rc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval - en2%cval
    end function sub_rc
    real(default) function sub_rr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval - en2%rval
    end function sub_rr
    complex(default) function sub_cc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval - en2%cval
    end function sub_cc

    integer function mul_ii (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival * en2%ival
    end function mul_ii
    real(default) function mul_ir (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival * en2%rval
    end function mul_ir
    real(default) function mul_ri (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval * en2%ival
    end function mul_ri
    complex(default) function mul_ic (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival * en2%cval
    end function mul_ic
    complex(default) function mul_ci (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2

```

```

        y = en1%cval * en2%ival
    end function mul_ci
    complex(default) function mul_rc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval * en2%cval
    end function mul_rc
    complex(default) function mul_cr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval * en2%rval
    end function mul_cr
    real(default) function mul_rr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval * en2%rval
    end function mul_rr
    complex(default) function mul_cc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval * en2%cval
    end function mul_cc

    integer function div_ii (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        if (en2%ival == 0) then
            if (en1%ival >= 0) then
                call msg_warning ("division by zero: " // int2char (en1%ival) // &
                    " / 0 ; result set to 0")
            else
                call msg_warning ("division by zero: (" // int2char (en1%ival) // &
                    ") / 0 ; result set to 0")
            end if
            y = 0
            return
        end if
        y = en1%ival / en2%ival
    end function div_ii
    real(default) function div_ir (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival / en2%rval
    end function div_ir
    real(default) function div_ri (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval / en2%ival
    end function div_ri
    complex(default) function div_ic (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%ival / en2%cval
    end function div_ic
    complex(default) function div_ci (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%cval / en2%ival
    end function div_ci
    complex(default) function div_rc (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval / en2%cval
    end function div_rc

```

```

complex(default) function div_cr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval / en2%rval
end function div_cr
real(default) function div_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval / en2%rval
end function div_rr
complex(default) function div_cc (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval / en2%cval
end function div_cc

integer function pow_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    integer :: a, b
    real(default) :: rres
    a = en1%ival
    b = en2%ival
    if ((a == 0) .and. (b < 0)) then
        call msg_warning ("division by zero: " // int2char (a) // &
            " ^ (" // int2char (b) // ") ; result set to 0")
        y = 0
        return
    end if
    rres = real(a, default) ** b
    y = rres
    if (real(y, default) /= rres) then
        if (b < 0) then
            call msg_warning ("result of all-integer operation " // &
                int2char (a) // " ^ (" // int2char (b) // &
                ") has been truncated to " // int2char (y), &
            (/ var_str ("Chances are that you want to use " // &
                "reals instead of integers at this point.") //))
        else
            call msg_warning ("integer overflow in " // int2char (a) // &
                " ^ " // int2char (b) // " ; result is " // int2char (y), &
            (/ var_str ("Using reals instead of integers might help.") //))
        end if
    end if
end function pow_ii
real(default) function pow_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval ** en2%ival
end function pow_ri
complex(default) function pow_ci (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval ** en2%ival
end function pow_ci
real(default) function pow_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival ** en2%rval
end function pow_ir
real(default) function pow_rr (en1, en2) result (y)

```

```

        type(eval_node_t), intent(in) :: en1, en2
        y = en1%rval ** en2%rval
    end function pow_rr
complex(default) function pow_cr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval ** en2%rval
end function pow_cr
complex(default) function pow_ic (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival ** en2%cval
end function pow_ic
complex(default) function pow_rc (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval ** en2%cval
end function pow_rc
complex(default) function pow_cc (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%cval ** en2%cval
end function pow_cc

integer function max_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = max (en1%ival, en2%ival)
end function max_ii
real(default) function max_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = max (real (en1%ival, default), en2%rval)
end function max_ir
real(default) function max_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = max (en1%rval, real (en2%ival, default))
end function max_ri
real(default) function max_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = max (en1%rval, en2%rval)
end function max_rr
integer function min_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = min (en1%ival, en2%ival)
end function min_ii
real(default) function min_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = min (real (en1%ival, default), en2%rval)
end function min_ir
real(default) function min_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = min (en1%rval, real (en2%ival, default))
end function min_ri
real(default) function min_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = min (en1%rval, en2%rval)
end function min_rr

integer function mod_ii (en1, en2) result (y)

```



```

        type(eval_node_t), intent(in) :: en1, en2
        y = mod (en1%ival, en2%ival)
    end function mod_ii
    real(default) function mod_ir (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = mod (real (en1%ival, default), en2%rval)
    end function mod_ir
    real(default) function mod_ri (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = mod (en1%rval, real (en2%ival, default))
    end function mod_ri
    real(default) function mod_rr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = mod (en1%rval, en2%rval)
    end function mod_rr
    integer function modulo_ii (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = modulo (en1%ival, en2%ival)
    end function modulo_ii
    real(default) function modulo_ir (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = modulo (real (en1%ival, default), en2%rval)
    end function modulo_ir
    real(default) function modulo_ri (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = modulo (en1%rval, real (en2%ival, default))
    end function modulo_ri
    real(default) function modulo_rr (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = modulo (en1%rval, en2%rval)
    end function modulo_rr

```

Unary numeric functions

(*Expressions: procedures*) + \equiv

```

    real(default) function real_i (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%ival
    end function real_i
    real(default) function real_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%cval
    end function real_c
    integer function int_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%rval
    end function int_r
    complex(default) function cmplx_i (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = en%ival
    end function cmplx_i
    integer function int_c (en) result (y)
        type(eval_node_t), intent(in) :: en

```

```

        y = en%cval
    end function int_c
complex(default) function cmplx_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = en%rval
end function cmplx_r
integer function nint_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = nint (en%rval)
end function nint_r
integer function floor_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = floor (en%rval)
end function floor_r
integer function ceiling_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = ceiling (en%rval)
end function ceiling_r

integer function neg_i (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = - en%ival
end function neg_i
real(default) function neg_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = - en%rval
end function neg_r
complex(default) function neg_c (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = - en%cval
end function neg_c
integer function abs_i (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = abs (en%ival)
end function abs_i
real(default) function abs_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = abs (en%rval)
end function abs_r
real(default) function abs_c (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = abs (en%cval)
end function abs_c
integer function sgn_i (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = sign (1, en%ival)
end function sgn_i
real(default) function sgn_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = sign (1._default, en%rval)
end function sgn_r

real(default) function sqrt_r (en) result (y)
    type(eval_node_t), intent(in) :: en

```

```

        y = sqrt (en%rval)
    end function sqrt_r
    real(default) function exp_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = exp (en%rval)
    end function exp_r
    real(default) function log_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = log (en%rval)
    end function log_r
    real(default) function log10_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = log10 (en%rval)
    end function log10_r

    complex(default) function sqrt_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = sqrt (en%cval)
    end function sqrt_c
    complex(default) function exp_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = exp (en%cval)
    end function exp_c
    complex(default) function log_c (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = log (en%cval)
    end function log_c

    real(default) function sin_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = sin (en%rval)
    end function sin_r
    real(default) function cos_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = cos (en%rval)
    end function cos_r
    real(default) function tan_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = tan (en%rval)
    end function tan_r
    real(default) function asin_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = asin (en%rval)
    end function asin_r
    real(default) function acos_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = acos (en%rval)
    end function acos_r
    real(default) function atan_r (en) result (y)
        type(eval_node_t), intent(in) :: en
        y = atan (en%rval)
    end function atan_r

    complex(default) function sin_c (en) result (y)

```

```

        type(eval_node_t), intent(in) :: en
        y = sin (en%cval)
    end function sin_c
complex(default) function cos_c (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = cos (en%cval)
end function cos_c

real(default) function sinh_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = sinh (en%rval)
end function sinh_r
real(default) function cosh_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = cosh (en%rval)
end function cosh_r
real(default) function tanh_r (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = tanh (en%rval)
end function tanh_r
!   real(default) function asinh_r (en) result (y)
!       type(eval_node_t), intent(in) :: en
!       y = asinh (en%rval)
!   end function asinh_r
!   real(default) function acosh_r (en) result (y)
!       type(eval_node_t), intent(in) :: en
!       y = acosh (en%rval)
!   end function acosh_r
!   real(default) function atanh_r (en) result (y)
!       type(eval_node_t), intent(in) :: en
!       y = atanh (en%rval)
!   end function atanh_r

```

Binary logical functions

Logical expressions:

```

(Expressions: procedures) +=
    logical function ignore_first_ll (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en2%lval
    end function ignore_first_ll
    logical function or_ll (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%lval .or. en2%lval
    end function or_ll
    logical function and_ll (en1, en2) result (y)
        type(eval_node_t), intent(in) :: en1, en2
        y = en1%lval .and. en2%lval
    end function and_ll

```

Comparisons:

```

(Expressions: procedures) +=

```

```

logical function comp_lt_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival < en2%ival
end function comp_lt_ii
logical function comp_lt_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival < en2%rval
end function comp_lt_ir
logical function comp_lt_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval < en2%ival
end function comp_lt_ri
logical function comp_lt_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval < en2%rval
end function comp_lt_rr

logical function comp_gt_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival > en2%ival
end function comp_gt_ii
logical function comp_gt_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival > en2%rval
end function comp_gt_ir
logical function comp_gt_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval > en2%ival
end function comp_gt_ri
logical function comp_gt_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval > en2%rval
end function comp_gt_rr

logical function comp_le_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival <= en2%ival
end function comp_le_ii
logical function comp_le_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival <= en2%rval
end function comp_le_ir
logical function comp_le_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval <= en2%ival
end function comp_le_ri
logical function comp_le_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval <= en2%rval
end function comp_le_rr

logical function comp_ge_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival >= en2%ival

```

```

end function comp_ge_ii
logical function comp_ge_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival >= en2%rval
end function comp_ge_ir
logical function comp_ge_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval >= en2%ival
end function comp_ge_ri
logical function comp_ge_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval >= en2%rval
end function comp_ge_rr

logical function comp_eq_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival == en2%ival
end function comp_eq_ii
logical function comp_eq_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival == en2%rval
end function comp_eq_ir
logical function comp_eq_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval == en2%ival
end function comp_eq_ri
logical function comp_eq_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval == en2%rval
end function comp_eq_rr
logical function comp_eq_ss (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%sval == en2%sval
end function comp_eq_ss

logical function comp_ne_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival /= en2%ival
end function comp_ne_ii
logical function comp_ne_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%ival /= en2%rval
end function comp_ne_ir
logical function comp_ne_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval /= en2%ival
end function comp_ne_ri
logical function comp_ne_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%rval /= en2%rval
end function comp_ne_rr
logical function comp_ne_ss (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    y = en1%sval /= en2%sval

```

```

end function comp_ne_ss

logical function comp_sim_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = abs (en1%ival - en2%ival) <= en1%tolerance
    else
        y = en1%ival == en2%ival
    end if
end function comp_sim_ii

logical function comp_sim_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = abs (en1%rval - en2%ival) <= en1%tolerance
    else
        y = en1%rval == en2%ival
    end if
end function comp_sim_ri

logical function comp_sim_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = abs (en1%ival - en2%rval) <= en1%tolerance
    else
        y = en1%ival == en2%rval
    end if
end function comp_sim_ir

logical function comp_sim_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = abs (en1%rval - en2%rval) <= en1%tolerance
    else
        y = en1%rval == en2%rval
    end if
end function comp_sim_rr

logical function comp_nsim_ii (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = abs (en1%ival - en2%ival) > en1%tolerance
    else
        y = en1%ival /= en2%ival
    end if
end function comp_nsim_ii

logical function comp_nsim_ri (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = abs (en1%rval - en2%ival) > en1%tolerance
    else
        y = en1%rval /= en2%ival
    end if
end function comp_nsim_ri

logical function comp_nsim_ir (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = abs (en1%ival - en2%rval) > en1%tolerance
    end if
end function comp_nsim_ir

```

```

    else
        y = en1%ival /= en2%rval
    end if
end function comp_nsim_ir
logical function comp_nsim_rr (en1, en2) result (y)
    type(eval_node_t), intent(in) :: en1, en2
    if (associated (en1%tolerance)) then
        y = abs (en1%rval - en2%rval) > en1%tolerance
    else
        y = en1%rval /= en2%rval
    end if
end function comp_nsim_rr

```

Unary logical functions

(Expressions: procedures) +≡

```

logical function not_1 (en) result (y)
    type(eval_node_t), intent(in) :: en
    y = .not. en%lval
end function not_1

```

Unary PDG-array functions

Make a PDG-array object from an integer.

(Expressions: procedures) +≡

```

subroutine pdg_i (pdg_array, en)
    type(pdg_array_t), intent(out) :: pdg_array
    type(eval_node_t), intent(in) :: en
    pdg_array = en%ival
end subroutine pdg_i

```

Binary PDG-array functions

Concatenate two PDG-array objects.

(Expressions: procedures) +≡

```

subroutine concat_cc (pdg_array, en1, en2)
    type(pdg_array_t), intent(out) :: pdg_array
    type(eval_node_t), intent(in) :: en1, en2
    pdg_array = en1%aval // en2%aval
end subroutine concat_cc

```

Unary particle-list functions

Combine all particles of the first argument. If `en0` is present, create a mask which is true only for those particles that pass the test.

(Expressions: procedures) +≡

```

subroutine collect_p (subevt, en1, en0)
    type(subevt_t), intent(inout) :: subevt

```



```

type(eval_node_t), intent(in) :: en1
type(eval_node_t), intent(inout), optional :: en0
logical, dimension(:), allocatable :: mask1
integer :: n, i
n = subevt_get_length (en1%pval)
allocate (mask1 (n))
if (present (en0)) then
  do i = 1, n
    en0%index = i
    en0%prt1 = subevt_get_prt (en1%pval, i)
    call eval_node_evaluate (en0)
    mask1(i) = en0%lval
  end do
else
  mask1 = .true.
end if
call subevt_collect (subevt, en1%pval, mask1)
end subroutine collect_p

```

Select all particles of the first argument. If `en0` is present, create a mask which is true only for those particles that pass the test.

(Expressions: procedures)+≡

```

subroutine select_p (subevt, en1, en0)
type(subevt_t), intent(inout) :: subevt
type(eval_node_t), intent(in) :: en1
type(eval_node_t), intent(inout), optional :: en0
logical, dimension(:), allocatable :: mask1
integer :: n, i
n = subevt_get_length (en1%pval)
allocate (mask1 (n))
if (present (en0)) then
  do i = 1, subevt_get_length (en1%pval)
    en0%index = i
    en0%prt1 = subevt_get_prt (en1%pval, i)
    call eval_node_evaluate (en0)
    mask1(i) = en0%lval
  end do
else
  mask1 = .true.
end if
call subevt_select (subevt, en1%pval, mask1)
end subroutine select_p

```

Extract the particle with index given by `en0` from the argument list. Negative indices count from the end. If `en0` is absent, extract the first particle. The result is a list with a single entry, or no entries if the original list was empty or if the index is out of range.

This function has no counterpart with two arguments.

(Expressions: procedures)+≡

```

subroutine extract_p (subevt, en1, en0)
type(subevt_t), intent(inout) :: subevt
type(eval_node_t), intent(in) :: en1
type(eval_node_t), intent(inout), optional :: en0

```

```

integer :: index
if (present (en0)) then
  call eval_node_evaluate (en0)
  select case (en0%result_type)
  case (V_INT); index = en0%ival
  case default
    call eval_node_write (en0)
    call msg_fatal (" Index parameter of 'extract' must be integer.")
  end select
else
  index = 1
end if
call subevt_extract (subevt, en1%pval, index)
end subroutine extract_p

```

Sort the subevent according to the result of evaluating `en0`. If `en0` is absent, sort by default method (PDG code, particles before antiparticles).

(Expressions: procedures) +=

```

subroutine sort_p (subevt, en1, en0)
  type(subevt_t), intent(inout) :: subevt
  type(eval_node_t), intent(in) :: en1
  type(eval_node_t), intent(inout), optional :: en0
  integer, dimension(:), allocatable :: ival
  real(default), dimension(:), allocatable :: rval
  integer :: i, n
  n = subevt_get_length (en1%pval)
  if (present (en0)) then
    select case (en0%result_type)
    case (V_INT); allocate (ival (n))
    case (V_REAL); allocate (rval (n))
    end select
    do i = 1, n
      en0%index = i
      en0%prt1 = subevt_get_prt (en1%pval, i)
      call eval_node_evaluate (en0)
      select case (en0%result_type)
      case (V_INT); ival(i) = en0%ival
      case (V_REAL); rval(i) = en0%rval
      end select
    end do
    select case (en0%result_type)
    case (V_INT); call subevt_sort (subevt, en1%pval, ival)
    case (V_REAL); call subevt_sort (subevt, en1%pval, rval)
    end select
  else
    call subevt_sort (subevt, en1%pval)
  end if
end subroutine sort_p

```

The following functions return a logical value. `all` evaluates to true if the condition `en0` is true for all elements of the subevent. `any` and `no` are analogous.

(Expressions: procedures) +=

```

function all_p (en1, en0) result (lval)

```

```

logical :: lval
type(eval_node_t), intent(in) :: en1
type(eval_node_t), intent(inout) :: en0
integer :: i, n
n = subevt_get_length (en1%pval)
lval = .true.
do i = 1, n
  en0%index = i
  en0%prt1 = subevt_get_prt (en1%pval, i)
  call eval_node_evaluate (en0)
  lval = en0%lval
  if (.not. lval) exit
end do
end function all_p

function any_p (en1, en0) result (lval)
logical :: lval
type(eval_node_t), intent(in) :: en1
type(eval_node_t), intent(inout) :: en0
integer :: i, n
n = subevt_get_length (en1%pval)
lval = .false.
do i = 1, n
  en0%index = i
  en0%prt1 = subevt_get_prt (en1%pval, i)
  call eval_node_evaluate (en0)
  lval = en0%lval
  if (lval) exit
end do
end function any_p

function no_p (en1, en0) result (lval)
logical :: lval
type(eval_node_t), intent(in) :: en1
type(eval_node_t), intent(inout) :: en0
integer :: i, n
n = subevt_get_length (en1%pval)
lval = .true.
do i = 1, n
  en0%index = i
  en0%prt1 = subevt_get_prt (en1%pval, i)
  call eval_node_evaluate (en0)
  lval = .not. en0%lval
  if (lval) exit
end do
end function no_p

```

This is the interface to user-supplied observables. The node `en0` evaluates to a string that indicates the procedure name. We search for the procedure in the dynamic library and load it into the procedure pointer which is then called. `en1` is the subevent on which the external code operates. The external function returns a `c_int`, which we translate into a real value.

(Expressions: procedures)+≡

```

function user_obs_int_p (en0, prt1) result (ival)
  integer :: ival
  type(eval_node_t), intent(inout) :: en0
  type(prt_t), intent(in) :: prt1
  type(string_t) :: name
  procedure(user_obs_int_unary), pointer :: user_obs
  call eval_node_evaluate (en0)
  if (en0%value_is_known) then
    select case (en0%result_type)
    case (V_STR); name = en0%sval
    case default
      call msg_bug ("user_obs: procedure name must be a string")
      name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_obs)
    ival = user_obs (c_prt (prt1))
  else
    call eval_node_write_rec (en0)
    call msg_fatal ("User observable name is undefined")
  end if
end function user_obs_int_p

function user_obs_real_p (en0, prt1) result (rval)
  real(default) :: rval
  type(eval_node_t), intent(inout) :: en0
  type(prt_t), intent(in) :: prt1
  type(string_t) :: name
  procedure(user_obs_real_unary), pointer :: user_obs
  call eval_node_evaluate (en0)
  if (en0%value_is_known) then
    select case (en0%result_type)
    case (V_STR); name = en0%sval
    case default
      call msg_bug ("user_obs: procedure name must be a string")
      name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_obs)
    rval = user_obs (c_prt (prt1))
  else
    call eval_node_write_rec (en0)
    call msg_fatal ("User observable name is undefined")
  end if
end function user_obs_real_p

```

This is the interface to user-supplied cut code. The node `en0` evaluates to a string that indicates the procedure name.

(Expressions: procedures)+≡

```

function user_cut_p (en1, en0) result (lval)
  logical :: lval
  type(eval_node_t), intent(in) :: en1
  type(eval_node_t), intent(inout) :: en0
  type(string_t) :: name
  procedure(user_cut_fun), pointer :: user_cut

```

```

call eval_node_evaluate (en0)
select case (en0%result_type)
case (V_STR); name = en0%sval
case default
    call msg_bug ("user_cut: procedure name must be a string")
    name = ""
end select
call c_f_procpointer (user_code_find_proc (name), user_cut)
lval = user_cut (c_prt (en1%pval), &
                int (subevt_get_length (en1%pval), kind=c_int)) &
    /= 0
end function user_cut_p

```

The following function returns an integer value, namely the number of particles for which the condition is true. If there is no condition, it returns simply the length of the subevent.

A function would be more natural. Making it a subroutine avoids another compiler bug (internal error in nagfor 5.2 (649)). (See the interface `unary_evi`.)

(*Expressions: procedures*) +=

```

subroutine count_a (ival, en1, en0)
integer, intent(out) :: ival
type(eval_node_t), intent(in) :: en1
type(eval_node_t), intent(inout), optional :: en0
integer :: i, n, count
n = subevt_get_length (en1%pval)
if (present (en0)) then
    count = 0
    do i = 1, n
        en0%index = i
        en0%prt1 = subevt_get_prt (en1%pval, i)
        call eval_node_evaluate (en0)
        if (en0%lval) count = count + 1
    end do
    ival = count
else
    ival = n
end if
end subroutine count_a

```

This evaluates a user-defined event-shape observable for the current subevent.

(*Expressions: procedures*) +=

```

subroutine user_event_shape_a (rval, en1, en0)
real(default), intent(out) :: rval
type(eval_node_t), intent(in) :: en1
type(eval_node_t), intent(inout), optional :: en0
type(string_t) :: name
procedure(user_event_shape_fun), pointer :: user_event_shape
if (.not. present (en0)) call msg_bug &
    ("user_event_shape called without procedure name")
call eval_node_evaluate (en0)
select case (en0%result_type)
case (V_STR); name = en0%sval
case default

```

```

        call msg_bug ("user_event_shape: procedure name must be a string")
        name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_event_shape)
    rval = user_event_shape (c_prt (en1%pval), &
        int (subevt_get_length (en1%pval), kind=c_int))
end subroutine user_event_shape_a

```

Binary particle-list functions

This joins two subevents, stored in the evaluation nodes **en1** and **en2**. If **en0** is also present, it amounts to a logical test returning true or false for every pair of particles. A particle of the second list gets a mask entry only if it passes the test for all particles of the first list.

(Expressions: procedures)+≡

```

subroutine join_pp (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:), allocatable :: mask2
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    allocate (mask2 (n2))
    mask2 = .true.
    if (present (en0)) then
        do i = 1, n1
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)
            do j = 1, n2
                en0%prt2 = subevt_get_prt (en2%pval, j)
                call eval_node_evaluate (en0)
                mask2(j) = mask2(j) .and. en0%lval
            end do
        end do
    end if
    call subevt_join (subevt, en1%pval, en2%pval, mask2)
end subroutine join_pp

```

Combine two subevents, i.e., make a list of composite particles built from all possible particle pairs from the two lists. If **en0** is present, create a mask which is true only for those pairs that pass the test.

(Expressions: procedures)+≡

```

subroutine combine_pp (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:,:), allocatable :: mask12
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    if (present (en0)) then

```

```

        allocate (mask12 (n1, n2))
        do i = 1, n1
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)
            do j = 1, n2
                en0%prt2 = subevt_get_prt (en2%pval, j)
                call eval_node_evaluate (en0)
                mask12(i,j) = en0%lval
            end do
        end do
        call subevt_combine (subevt, en1%pval, en2%pval, mask12)
    else
        call subevt_combine (subevt, en1%pval, en2%pval)
    end if
end subroutine combine_pp

```

Combine all particles of the first argument. If `en0` is present, create a mask which is true only for those particles that pass the test w.r.t. all particles in the second argument. If `en0` is absent, the second argument is ignored.

(Expressions: procedures)+≡

```

subroutine collect_pp (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    logical, dimension(:), allocatable :: mask1
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    allocate (mask1 (n1))
    mask1 = .true.
    if (present (en0)) then
        do i = 1, n1
            en0%index = i
            en0%prt1 = subevt_get_prt (en1%pval, i)
            do j = 1, n2
                en0%prt2 = subevt_get_prt (en2%pval, j)
                call eval_node_evaluate (en0)
                mask1(i) = mask1(i) .and. en0%lval
            end do
        end do
    end if
    call subevt_collect (subevt, en1%pval, mask1)
end subroutine collect_pp

```

Select all particles of the first argument. If `en0` is present, create a mask which is true only for those particles that pass the test w.r.t. all particles in the second argument. If `en0` is absent, the second argument is ignored, and the first argument is transferred unchanged. (This case is not very useful, of course.)

(Expressions: procedures)+≡

```

subroutine select_pp (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0

```

```

logical, dimension(:), allocatable :: mask1
integer :: i, j, n1, n2
n1 = subevt_get_length (en1%pval)
n2 = subevt_get_length (en2%pval)
allocate (mask1 (n1))
mask1 = .true.
if (present (en0)) then
  do i = 1, n1
    en0%index = i
    en0%prt1 = subevt_get_prt (en1%pval, i)
    do j = 1, n2
      en0%prt2 = subevt_get_prt (en2%pval, j)
      call eval_node_evaluate (en0)
      mask1(i) = mask1(i) .and. en0%lval
    end do
  end do
end if
call subevt_select (subevt, en1%pval, mask1)
end subroutine select_pp

```

Sort the first subevent according to the result of evaluating `en0`. From the second subevent, only the first element is taken as reference. If `en0` is absent, we sort by default method (PDG code, particles before antiparticles).

(Expressions: procedures)+≡

```

subroutine sort_pp (subevt, en1, en2, en0)
  type(subevt_t), intent(inout) :: subevt
  type(eval_node_t), intent(in) :: en1, en2
  type(eval_node_t), intent(inout), optional :: en0
  integer, dimension(:), allocatable :: ival
  real(default), dimension(:), allocatable :: rval
  integer :: i, n1, n2
  n1 = subevt_get_length (en1%pval)
  n2 = subevt_get_length (en2%pval)
  if (present (en0)) then
    select case (en0%result_type)
    case (V_INT); allocate (ival (n1))
    case (V_REAL); allocate (rval (n1))
    end select
    do i = 1, n1
      en0%index = i
      en0%prt1 = subevt_get_prt (en1%pval, i)
      en0%prt2 = subevt_get_prt (en2%pval, 1)
      call eval_node_evaluate (en0)
      select case (en0%result_type)
      case (V_INT); ival(i) = en0%ival
      case (V_REAL); rval(i) = en0%rval
      end select
    end do
    select case (en0%result_type)
    case (V_INT); call subevt_sort (subevt, en1%pval, ival)
    case (V_REAL); call subevt_sort (subevt, en1%pval, rval)
    end select
  else

```



```

        call subevt_sort (subevt, en1%pval)
    end if
end subroutine sort_pp

```

The following functions return a logical value. `all` evaluates to true if the condition `en0` is true for all valid element pairs of both subevents. Invalid pairs (with common `src` entry) are ignored.

`any` and `no` are analogous.

(Expressions: procedures) +≡

```

function all_pp (en1, en2, en0) result (lval)
    logical :: lval
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout) :: en0
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    lval = .true.
    LOOP1: do i = 1, n1
        en0%index = i
        en0%prt1 = subevt_get_prt (en1%pval, i)
        do j = 1, n2
            en0%prt2 = subevt_get_prt (en2%pval, j)
            if (are_disjoint (en0%prt1, en0%prt2)) then
                call eval_node_evaluate (en0)
                lval = en0%lval
                if (.not. lval) exit LOOP1
            end if
        end do
    end do LOOP1
end function all_pp

```

```

function any_pp (en1, en2, en0) result (lval)
    logical :: lval
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout) :: en0
    integer :: i, j, n1, n2
    n1 = subevt_get_length (en1%pval)
    n2 = subevt_get_length (en2%pval)
    lval = .false.
    LOOP1: do i = 1, n1
        en0%index = i
        en0%prt1 = subevt_get_prt (en1%pval, i)
        do j = 1, n2
            en0%prt2 = subevt_get_prt (en2%pval, j)
            if (are_disjoint (en0%prt1, en0%prt2)) then
                call eval_node_evaluate (en0)
                lval = en0%lval
                if (lval) exit LOOP1
            end if
        end do
    end do LOOP1
end function any_pp

```

```

function no_pp (en1, en2, en0) result (lval)
  logical :: lval
  type(eval_node_t), intent(in) :: en1, en2
  type(eval_node_t), intent(inout) :: en0
  integer :: i, j, n1, n2
  n1 = subevt_get_length (en1%pval)
  n2 = subevt_get_length (en2%pval)
  lval = .true.
  LOOP1: do i = 1, n1
    en0%index = i
    en0%prt1 = subevt_get_prt (en1%pval, i)
    do j = 1, n2
      en0%prt2 = subevt_get_prt (en2%pval, j)
      if (are_disjoint (en0%prt1, en0%prt2)) then
        call eval_node_evaluate (en0)
        lval = .not. en0%lval
        if (lval) exit LOOP1
      end if
    end do
  end do LOOP1
end function no_pp

```

This is the interface to user-supplied observables. The node `en0` evaluates to a string that indicates the procedure name. We search for the procedure in the dynamic library and load it into the procedure pointer which is then called. `en1` is the subevent on which the external code operates. The external function returns a `c_int`, which we translate into a real value.

(Expressions: procedures)+≡

```

function user_obs_int_pp (en0, prt1, prt2) result (ival)
  integer :: ival
  type(eval_node_t), intent(inout) :: en0
  type(prt_t), intent(in) :: prt1, prt2
  type(string_t) :: name
  procedure(user_obs_int_binary), pointer :: user_obs
  call eval_node_evaluate (en0)
  if (en0%value_is_known) then
    select case (en0%result_type)
    case (V_STR); name = en0%sval
    case default
      call msg_bug("user_obs: procedure name must be a string")
      name = ""
    end select
    call c_f_procpointer (user_code_find_proc (name), user_obs)
    ival = user_obs (c_prt (prt1), c_prt (prt2))
  else
    call eval_node_write_rec (en0)
    call msg_fatal ("User observable name is undefined")
  end if
end function user_obs_int_pp

function user_obs_real_pp (en0, prt1, prt2) result (rval)
  real(default) :: rval
  type(eval_node_t), intent(inout) :: en0

```

```

type(prt_t), intent(in) :: prt1, prt2
type(string_t) :: name
procedure(user_obs_real_binary), pointer :: user_obs
call eval_node_evaluate (en0)
if (en0%value_is_known) then
  select case (en0%result_type)
  case (V_STR); name = en0% sval
  case default
    call msg_bug ("user_obs: procedure name must be a string")
    name = ""
  end select
  call c_f_procpointer (user_code_find_proc (name), user_obs)
  rval = user_obs (c_prt (prt1), c_prt (prt2))
else
  call eval_node_write_rec (en0)
  call msg_fatal ("User observable name is undefined")
end if
end function user_obs_real_pp

```

The following function returns an integer value, namely the number of valid particle-pairs from both lists for which the condition is true. Invalid pairs (with common src entry) are ignored. If there is no condition, it returns the number of valid particle pairs.

A function would be more natural. Making it a subroutine avoids another compiler bug (internal error in nagfor 5.2 (649)). (See the interface `binary_num`.)

(*Expressions: procedures*)+≡

```

subroutine count_pp (ival, en1, en2, en0)
  integer, intent(out) :: ival
  type(eval_node_t), intent(in) :: en1, en2
  type(eval_node_t), intent(inout), optional :: en0
  integer :: i, j, n1, n2, count
  n1 = subevt_get_length (en1%pval)
  n2 = subevt_get_length (en2%pval)
  if (present (en0)) then
    count = 0
    do i = 1, n1
      en0%index = i
      en0%prt1 = subevt_get_prt (en1%pval, i)
      do j = 1, n2
        en0%prt2 = subevt_get_prt (en2%pval, j)
        if (are_disjoint (en0%prt1, en0%prt2)) then
          call eval_node_evaluate (en0)
          if (en0%lval) count = count + 1
        end if
      end do
    end do
  else
    count = 0
    do i = 1, n1
      do j = 1, n2
        if (are_disjoint (subevt_get_prt (en1%pval, i), &
                           subevt_get_prt (en2%pval, j))) then

```

```

        count = count + 1
    end if
end do
end do
end if
ival = count
end subroutine count_pp

```

This function makes up a subevent from the second argument which consists only of particles which match the PDG code array (first argument).

(Expressions: procedures) +≡

```

subroutine select_pdg_ca (subevt, en1, en2, en0)
    type(subevt_t), intent(inout) :: subevt
    type(eval_node_t), intent(in) :: en1, en2
    type(eval_node_t), intent(inout), optional :: en0
    if (present (en0)) then
        call subevt_select_pdg_code (subevt, en1%aval, en2%pval, en0%ival)
    else
        call subevt_select_pdg_code (subevt, en1%aval, en2%pval)
    end if
end subroutine select_pdg_ca

```

Binary string functions

Currently, the only string operation is concatenation.

(Expressions: procedures) +≡

```

subroutine concat_ss (string, en1, en2)
    type(string_t), intent(out) :: string
    type(eval_node_t), intent(in) :: en1, en2
    string = en1%sval // en2%sval
end subroutine concat_ss

```

5.6.4 Compiling the parse tree

The evaluation tree is built recursively by following a parse tree. Debug option:

(Expressions: variables) ≡

```

logical, parameter :: debug = .false.

```

Evaluate an expression. The requested type is given as an optional argument; default is numeric (integer or real).

(Expressions: procedures) +≡

```

recursive subroutine eval_node_compile_genexpr &
    (en, pn, var_list, result_type)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in), optional :: result_type
    if (debug) then
        print *, "read genexpr"; call parse_node_write (pn)
    end if

```

```

end if
if (present (result_type)) then
  select case (result_type)
  case (V_INT, V_REAL, V_CMPLX)
    call eval_node_compile_expr (en, pn, var_list)
  case (V_LOG)
    call eval_node_compile_lexpr (en, pn, var_list)
  case (V_SEV)
    call eval_node_compile_pexpr (en, pn, var_list)
  case (V_PDG)
    call eval_node_compile_cexpr (en, pn, var_list)
  case (V_STR)
    call eval_node_compile_sexpr (en, pn, var_list)
  end select
else
  call eval_node_compile_expr (en, pn, var_list)
end if
if (debug) then
  call eval_node_write (en)
  print *, "done genexpr"
end if
end subroutine eval_node_compile_genexpr

```

Numeric expressions

This procedure compiles a numerical expression. This is a single term or a sum or difference of terms. We have to account for all combinations of integer and real arguments. If both are constant, we immediately do the calculation and allocate a constant node.

(Expressions: procedures) +≡

```

recursive subroutine eval_node_compile_expr (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_term, pn_addition, pn_arg
  type(eval_node_t), pointer :: en1, en2
  type(string_t) :: key
  integer :: t1, t2, t
  if (debug) then
    print *, "read expr"; call parse_node_write (pn)
  end if
  pn_term => parse_node_get_sub_ptr (pn)
  select case (char (parse_node_get_rule_key (pn_term)))
  case ("term")
    call eval_node_compile_term (en, pn_term, var_list)
    pn_addition => parse_node_get_next_ptr (pn_term, tag="addition")
  case ("addition")
    en => null ()
    pn_addition => pn_term
  case default
    call parse_node_mismatch ("term|addition", pn)
  end select

```

```

do while (associated (pn_addition))
  pn_op => parse_node_get_sub_ptr (pn_addition)
  pn_arg => parse_node_get_next_ptr (pn_op, tag="term")
  call eval_node_compile_term (en2, pn_arg, var_list)
  t2 = en2%result_type
  if (associated (en)) then
    en1 => en
    t1 = en1%result_type
  else
    allocate (en1)
    select case (t2)
    case (V_INT); call eval_node_init_int (en1, 0)
    case (V_REAL); call eval_node_init_real (en1, 0._default)
    case (V_CMPLX); call eval_node_init_cmplx (en1, cmplx &
      (0._default, 0._default, kind=default))
    end select
    t1 = t2
  end if
  t = numeric_result_type (t1, t2)
  allocate (en)
  key = parse_node_get_key (pn_op)
  if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
    select case (char (key))
    case ("+")
      select case (t1)
      case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_init_int (en, add_ii (en1, en2))
        case (V_REAL); call eval_node_init_real (en, add_ir (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, add_ic (en1, en2))
        end select
      case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_init_real (en, add_ri (en1, en2))
        case (V_REAL); call eval_node_init_real (en, add_rr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, add_rc (en1, en2))
        end select
      case (V_CMPLX)
        select case (t2)
        case (V_INT); call eval_node_init_cmplx (en, add_ci (en1, en2))
        case (V_REAL); call eval_node_init_cmplx (en, add_cr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, add_cc (en1, en2))
        end select
      end select
    case ("-")
      select case (t1)
      case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_init_int (en, sub_ii (en1, en2))
        case (V_REAL); call eval_node_init_real (en, sub_ir (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, sub_ic (en1, en2))
        end select
      case (V_REAL)
        select case (t2)

```

```

        case (V_INT); call eval_node_init_real (en, sub_ri (en1, en2))
        case (V_REAL); call eval_node_init_real (en, sub_rr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, sub_rc (en1, en2))
    end select
case (V_CMPLX)
    select case (t2)
        case (V_INT); call eval_node_init_cmplx (en, sub_ci (en1, en2))
        case (V_REAL); call eval_node_init_cmplx (en, sub_cr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, sub_cc (en1, en2))
    end select
end select
call eval_node_final_rec (en1)
call eval_node_final_rec (en2)
deallocate (en1, en2)
else
call eval_node_init_branch (en, key, t, en1, en2)
select case (char (key))
case ("+")
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_set_op2_int (en, add_ii)
                case (V_REAL); call eval_node_set_op2_real (en, add_ir)
                case (V_CMPLX); call eval_node_set_op2_cmplx (en, add_ic)
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_set_op2_real (en, add_ri)
                case (V_REAL); call eval_node_set_op2_real (en, add_rr)
                case (V_CMPLX); call eval_node_set_op2_cmplx (en, add_rc)
            end select
        case (V_CMPLX)
            select case (t2)
                case (V_INT); call eval_node_set_op2_cmplx (en, add_ci)
                case (V_REAL); call eval_node_set_op2_cmplx (en, add_cr)
                case (V_CMPLX); call eval_node_set_op2_cmplx (en, add_cc)
            end select
        end select
    end select
case ("-")
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_set_op2_int (en, sub_ii)
                case (V_REAL); call eval_node_set_op2_real (en, sub_ir)
                case (V_CMPLX); call eval_node_set_op2_cmplx (en, sub_ic)
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_set_op2_real (en, sub_ri)
                case (V_REAL); call eval_node_set_op2_real (en, sub_rr)
                case (V_CMPLX); call eval_node_set_op2_cmplx (en, sub_rc)
            end select
        case (V_CMPLX)

```

```

        select case (t2)
        case (V_INT);   call eval_node_set_op2_cmplx (en, sub_ci)
        case (V_REAL);  call eval_node_set_op2_cmplx (en, sub_cr)
        case (V_CMPLX); call eval_node_set_op2_cmplx (en, sub_cc)
        end select
    end select
end select
end if
pn_addition => parse_node_get_next_ptr (pn_addition)
end do
if (debug) then
    call eval_node_write (en)
    print *, "done expr"
end if
end subroutine eval_node_compile_expr

```

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_term (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_factor, pn_multiplication, pn_op, pn_arg
    type(eval_node_t), pointer :: en1, en2
    type(string_t) :: key
    integer :: t1, t2, t
    if (debug) then
        print *, "read term"; call parse_node_write (pn)
    end if
    pn_factor => parse_node_get_sub_ptr (pn, tag="factor")
    call eval_node_compile_factor (en, pn_factor, var_list)
    pn_multiplication => &
        parse_node_get_next_ptr (pn_factor, tag="multiplication")
    do while (associated (pn_multiplication))
        pn_op => parse_node_get_sub_ptr (pn_multiplication)
        pn_arg => parse_node_get_next_ptr (pn_op, tag="factor")
        en1 => en
        call eval_node_compile_factor (en2, pn_arg, var_list)
        t1 = en1%result_type
        t2 = en2%result_type
        t = numeric_result_type (t1, t2)
        allocate (en)
        key = parse_node_get_key (pn_op)
        if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
            select case (char (key))
            case ("*")
                select case (t1)
                case (V_INT)
                    select case (t2)
                    case (V_INT); call eval_node_init_int (en, mul_ii (en1, en2))
                    case (V_REAL); call eval_node_init_real (en, mul_ir (en1, en2))
                    case (V_CMPLX); call eval_node_init_cmplx (en, mul_ic (en1, en2))
                    end select
                case (V_REAL)
                    select case (t2)

```



```

        case (V_INT); call eval_node_init_real (en, mul_ri (en1, en2))
        case (V_REAL); call eval_node_init_real (en, mul_rr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, mul_rc (en1, en2))
    end select
case (V_CMPLX)
    select case (t2)
        case (V_INT); call eval_node_init_cmplx (en, mul_ci (en1, en2))
        case (V_REAL); call eval_node_init_cmplx (en, mul_cr (en1, en2))
        case (V_CMPLX); call eval_node_init_cmplx (en, mul_cc (en1, en2))
    end select
end select
case ("/")
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_init_int (en, div_ii (en1, en2))
                case (V_REAL); call eval_node_init_real (en, div_ir (en1, en2))
                case (V_CMPLX); call eval_node_init_real (en, div_ir (en1, en2))
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_init_real (en, div_ri (en1, en2))
                case (V_REAL); call eval_node_init_real (en, div_rr (en1, en2))
                case (V_CMPLX); call eval_node_init_cmplx (en, div_rc (en1, en2))
            end select
        case (V_CMPLX)
            select case (t2)
                case (V_INT); call eval_node_init_cmplx (en, div_ci (en1, en2))
                case (V_REAL); call eval_node_init_cmplx (en, div_cr (en1, en2))
                case (V_CMPLX); call eval_node_init_cmplx (en, div_cc (en1, en2))
            end select
    end select
end select
call eval_node_final_rec (en1)
call eval_node_final_rec (en2)
deallocate (en1, en2)
else
    call eval_node_init_branch (en, key, t, en1, en2)
    select case (char (key))
    case ("*")
        select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_set_op2_int (en, mul_ii)
                case (V_REAL); call eval_node_set_op2_real (en, mul_ir)
                case (V_CMPLX); call eval_node_set_op2_cmplx (en, mul_ic)
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_set_op2_real (en, mul_ri)
                case (V_REAL); call eval_node_set_op2_real (en, mul_rr)
                case (V_CMPLX); call eval_node_set_op2_cmplx (en, mul_rc)
            end select
        case (V_CMPLX)

```

```

        select case (t2)
        case (V_INT);    call eval_node_set_op2_cmplx (en, mul_ci)
        case (V_REAL);   call eval_node_set_op2_cmplx (en, mul_cr)
        case (V_CMPLX);  call eval_node_set_op2_cmplx (en, mul_cc)
        end select
    end select
case ("/")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT);    call eval_node_set_op2_int  (en, div_ii)
        case (V_REAL);   call eval_node_set_op2_real (en, div_ir)
        case (V_CMPLX);  call eval_node_set_op2_cmplx (en, div_ic)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT);    call eval_node_set_op2_real (en, div_ri)
        case (V_REAL);   call eval_node_set_op2_real (en, div_rr)
        case (V_CMPLX);  call eval_node_set_op2_cmplx (en, div_rc)
        end select
    case (V_CMPLX)
        select case (t2)
        case (V_INT);    call eval_node_set_op2_cmplx (en, div_ci)
        case (V_REAL);   call eval_node_set_op2_cmplx (en, div_cr)
        case (V_CMPLX);  call eval_node_set_op2_cmplx (en, div_cc)
        end select
    end select
    end select
end if
pn_multiplication => parse_node_get_next_ptr (pn_multiplication)
end do
if (debug) then
    call eval_node_write (en)
    print *, "done term"
end if
end subroutine eval_node_compile_term

```

(Expressions: procedures) +≡

```

recursive subroutine eval_node_compile_factor (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_value, pn_exponentiation, pn_op, pn_arg
    type(eval_node_t), pointer :: en1, en2
    type(string_t) :: key
    integer :: t1, t2, t
    if (debug) then
        print *, "read factor"; call parse_node_write (pn)
    end if
    pn_value => parse_node_get_sub_ptr (pn)
    call eval_node_compile_signed_value (en, pn_value, var_list)
    pn_exponentiation => &
        parse_node_get_next_ptr (pn_value, tag="exponentiation")
    if (associated (pn_exponentiation)) then

```

```

pn_op => parse_node_get_sub_ptr (pn_exponentiation)
pn_arg => parse_node_get_next_ptr (pn_op)
en1 => en
call eval_node_compile_signed_value (en2, pn_arg, var_list)
t1 = en1%result_type
t2 = en2%result_type
t = numeric_result_type (t1, t2)
allocate (en)
key = parse_node_get_key (pn_op)
if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
  select case (t1)
  case (V_INT)
    select case (t2)
    case (V_INT); call eval_node_init_int (en, pow_ii (en1, en2))
    case (V_REAL); call eval_node_init_real (en, pow_ir (en1, en2))
    case (V_CMPLX); call eval_node_init_cmplx (en, pow_ic (en1, en2))
    end select
  case (V_REAL)
    select case (t2)
    case (V_INT); call eval_node_init_real (en, pow_ri (en1, en2))
    case (V_REAL); call eval_node_init_real (en, pow_rr (en1, en2))
    case (V_CMPLX); call eval_node_init_cmplx (en, pow_rc (en1, en2))
    end select
  case (V_CMPLX)
    select case (t2)
    case (V_INT); call eval_node_init_cmplx (en, pow_ci (en1, en2))
    case (V_REAL); call eval_node_init_cmplx (en, pow_cr (en1, en2))
    case (V_CMPLX); call eval_node_init_cmplx (en, pow_cc (en1, en2))
    end select
  end select
  call eval_node_final_rec (en1)
  call eval_node_final_rec (en2)
  deallocate (en1, en2)
else
  call eval_node_init_branch (en, key, t, en1, en2)
  select case (t1)
  case (V_INT)
    select case (t2)
    case (V_INT); call eval_node_set_op2_int (en, pow_ii)
    case (V_REAL,V_CMPLX); call eval_type_error (pn, "exponentiation", t1)
    end select
  case (V_REAL)
    select case (t2)
    case (V_INT); call eval_node_set_op2_real (en, pow_ri)
    case (V_REAL); call eval_node_set_op2_real (en, pow_rr)
    case (V_CMPLX); call eval_type_error (pn, "exponentiation", t1)
    end select
  case (V_CMPLX)
    select case (t2)
    case (V_INT); call eval_node_set_op2_cmplx (en, pow_ci)
    case (V_REAL); call eval_node_set_op2_cmplx (en, pow_cr)
    case (V_CMPLX); call eval_node_set_op2_cmplx (en, pow_cc)
    end select
  end select
end select

```

```

        end if
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done factor"
    end if
end subroutine eval_node_compile_factor

```

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_signed_value (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_arg
    type(eval_node_t), pointer :: en1
    integer :: t
    if (debug) then
        print *, "read signed value"; call parse_node_write (pn)
    end if
    select case (char (parse_node_get_rule_key (pn)))
    case ("signed_value")
        pn_arg => parse_node_get_sub_ptr (pn, 2)
        call eval_node_compile_value (en1, pn_arg, var_list)
        t = en1%result_type
        allocate (en)
        if (en1%type == EN_CONSTANT) then
            select case (t)
            case (V_INT); call eval_node_init_int (en, neg_i (en1))
            case (V_REAL); call eval_node_init_real (en, neg_r (en1))
            case (V_CMPLX); call eval_node_init_cmplx (en, neg_c (en1))
            end select
            call eval_node_final_rec (en1)
            deallocate (en1)
        else
            call eval_node_init_branch (en, var_str ("-"), t, en1)
            select case (t)
            case (V_INT); call eval_node_set_op1_int (en, neg_i)
            case (V_REAL); call eval_node_set_op1_real (en, neg_r)
            case (V_CMPLX); call eval_node_set_op1_cmplx (en, neg_c)
            end select
        end if
    end if
    case default
        call eval_node_compile_value (en, pn, var_list)
    end select
    if (debug) then
        call eval_node_write (en)
        print *, "done signed value"
    end if
end subroutine eval_node_compile_signed_value

```

Integer, real and complex values have an optional unit. The unit is extracted and applied immediately. An integer with unit evaluates to a real constant.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_value (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  if (debug) then
    print *, "read value"; call parse_node_write (pn)
  end if
  select case (char (parse_node_get_rule_key (pn)))
  case ("integer_value", "real_value", "complex_value")
    call eval_node_compile_numeric_value (en, pn)
  case ("pi")
    call eval_node_compile_constant (en, pn)
  case ("I")
    call eval_node_compile_constant (en, pn)
  case ("variable")
    call eval_node_compile_variable (en, pn, var_list)
  case ("result")
    call eval_node_compile_result (en, pn, var_list)
  case ("user_observable")
    call eval_node_compile_user_observable (en, pn, var_list)
  case ("expr")
    call eval_node_compile_expr (en, pn, var_list)
  case ("block_expr")
    call eval_node_compile_block_expr (en, pn, var_list)
  case ("conditional_expr")
    call eval_node_compile_conditional (en, pn, var_list)
  case ("unary_function")
    call eval_node_compile_unary_function (en, pn, var_list)
  case ("binary_function")
    call eval_node_compile_binary_function (en, pn, var_list)
  case ("eval_fun")
    call eval_node_compile_eval_function (en, pn, var_list)
  case ("count_fun", "user_event_fun")
    call eval_node_compile_numeric_function (en, pn, var_list)
  case default
    call parse_node_mismatch &
      ("integer|real|complex|constant|variable|" // &
       "expr|block_expr|conditional_expr|" // &
       "unary_function|binary_function|numeric_pexpr", pn)
  end select
  if (debug) then
    call eval_node_write (en)
    print *, "done value"
  end if
end subroutine eval_node_compile_value

```

Real, complex and integer values are numeric literals with an optional unit attached. In case of an integer, the unit actually makes it a real value in disguise. The signed version of real values is not possible in generic expressions; it is a special case for numeric constants in model files (see below). We do not introduce signed versions of complex values.

(Expressions: procedures) +=

```

subroutine eval_node_compile_numeric_value (en, pn)

```

```

type(eval_node_t), pointer :: en
type(parse_node_t), intent(in), target :: pn
type(parse_node_t), pointer :: pn_val, pn_unit
allocate (en)
pn_val => parse_node_get_sub_ptr (pn)
pn_unit => parse_node_get_next_ptr (pn_val)
select case (char (parse_node_get_rule_key (pn)))
case ("integer_value")
  if (associated (pn_unit)) then
    call eval_node_init_real (en, &
      parse_node_get_integer (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_int (en, parse_node_get_integer (pn_val))
  end if
case ("real_value")
  if (associated (pn_unit)) then
    call eval_node_init_real (en, &
      parse_node_get_real (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_real (en, parse_node_get_real (pn_val))
  end if
case ("complex_value")
  if (associated (pn_unit)) then
    call eval_node_init_cmplx (en, &
      parse_node_get_cmplx (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_cmplx (en, parse_node_get_cmplx (pn_val))
  end if
case ("neg_real_value")
  pn_val => parse_node_get_sub_ptr (parse_node_get_sub_ptr (pn, 2))
  pn_unit => parse_node_get_next_ptr (pn_val)
  if (associated (pn_unit)) then
    call eval_node_init_real (en, &
      - parse_node_get_real (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_real (en, - parse_node_get_real (pn_val))
  end if
case ("pos_real_value")
  pn_val => parse_node_get_sub_ptr (parse_node_get_sub_ptr (pn, 2))
  pn_unit => parse_node_get_next_ptr (pn_val)
  if (associated (pn_unit)) then
    call eval_node_init_real (en, &
      parse_node_get_real (pn_val) * parse_node_get_unit (pn_unit))
  else
    call eval_node_init_real (en, parse_node_get_real (pn_val))
  end if
case default
  call parse_node_mismatch &
    ("integer_value|real_value|complex_value|neg_real_value|pos_real_value", pn)
end select
end subroutine eval_node_compile_numeric_value

```

These are the units, predefined and hardcoded. The default energy unit is GeV, the default angular unit is radians. We include units for observables of

dimension energy squared. Luminosities are normalized in inverse femtobarns.

(*Expressions: procedures*) \equiv

```

function parse_node_get_unit (pn) result (factor)
  real(default) :: factor
  real(default) :: unit
  type(parse_node_t), intent(in) :: pn
  type(parse_node_t), pointer :: pn_unit, pn_unit_power
  type(parse_node_t), pointer :: pn_frac, pn_num, pn_int, pn_div, pn_den
  integer :: num, den
  pn_unit => parse_node_get_sub_ptr (pn)
  select case (char (parse_node_get_key (pn_unit)))
    case ("TeV"); unit = 1.e3_default
    case ("GeV"); unit = 1
    case ("MeV"); unit = 1.e-3_default
    case ("keV"); unit = 1.e-6_default
    case ("eV"); unit = 1.e-9_default
    case ("meV"); unit = 1.e-12_default
    case ("nbarn"); unit = 1.e6_default
    case ("pbarn"); unit = 1.e3_default
    case ("fbarn"); unit = 1
    case ("abarn"); unit = 1.e-3_default
    case ("rad"); unit = 1
    case ("mrad"); unit = 1.e-3_default
    case ("degree"); unit = degree
    case ("%"); unit = 1.e-2_default
    case default
      call msg_bug (" Unit ' " // &
        char (parse_node_get_key (pn)) // " ' is undefined.")
  end select
  pn_unit_power => parse_node_get_next_ptr (pn_unit)
  if (associated (pn_unit_power)) then
    pn_frac => parse_node_get_sub_ptr (pn_unit_power, 2)
    pn_num => parse_node_get_sub_ptr (pn_frac)
    select case (char (parse_node_get_rule_key (pn_num)))
      case ("neg_int")
        pn_int => parse_node_get_sub_ptr (pn_num, 2)
        num = - parse_node_get_integer (pn_int)
      case ("pos_int")
        pn_int => parse_node_get_sub_ptr (pn_num, 2)
        num = parse_node_get_integer (pn_int)
      case ("integer_literal")
        num = parse_node_get_integer (pn_num)
      case default
        call parse_node_mismatch ("neg_int|pos_int|integer_literal", pn_num)
    end select
    pn_div => parse_node_get_next_ptr (pn_num)
    if (associated (pn_div)) then
      pn_den => parse_node_get_sub_ptr (pn_div, 2)
      den = parse_node_get_integer (pn_den)
    else
      den = 1
    end if
  else
    num = 1
  end if
end function

```

```

        den = 1
    end if
    factor = unit ** (real (num, default) / den)
end function parse_node_get_unit

```

There are only two predefined constants, but more can be added easily.

(Expressions: procedures)+≡

```

subroutine eval_node_compile_constant (en, pn)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    if (debug) then
        print *, "read constant"; call parse_node_write (pn)
    end if
    allocate (en)
    select case (char (parse_node_get_key (pn)))
    case ("pi");      call eval_node_init_real (en, pi)
    case ("I");       call eval_node_init_cmplx (en, imago)
    case default
        call parse_node_mismatch ("pi or I", pn)
    end select
    if (debug) then
        call eval_node_write (en)
        print *, "done constant"
    end if
end subroutine eval_node_compile_constant

```

Compile a variable, with or without a specified type. Take the list of variables, look for the name and make a node with a pointer to the value. If no type is provided, the variable is numeric, and the stored value determines whether it is real or integer.

We explicitly demand that the variable is defined, so we do not accidentally point to variables that are declared only later in the script but have come into existence in a previous compilation pass.

Variables may actually be anonymous, these are expressions in disguise. In that case, the expression replaces the variable name in the parse tree, and we allocate an ordinary expression node in the eval tree.

Variables of type V_PDG (pdg-code array) are not treated here. They are handled by `eval_node_compile_cvariable`.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_variable (en, pn, var_list, var_type)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in), optional :: var_type
    type(parse_node_t), pointer :: pn_name
    type(string_t) :: var_name
    type(var_entry_t), pointer :: var
    logical, target, save :: no_lval
    real(default), target, save :: no_rval
    type(subvt_t), target, save :: no_pval
    type(string_t), target, save :: no_sval
    logical, target, save :: unknown = .false.

```



```

if (debug) then
  print *, "read variable"; call parse_node_write (pn)
end if
if (present (var_type)) then
  select case (var_type)
    case (V_REAL, V_OBS1_REAL, V_OBS2_REAL, V_INT, V_OBS1_INT, &
          V_OBS2_INT, V_CMPLX)
      pn_name => pn
    case default
      pn_name => parse_node_get_sub_ptr (pn, 2)
    end select
else
  pn_name => pn
end if
select case (char (parse_node_get_rule_key (pn_name)))
case ("expr")
  call eval_node_compile_expr (en, pn_name, var_list)
case ("lexpr")
  call eval_node_compile_lexpr (en, pn_name, var_list)
case ("sexpr")
  call eval_node_compile_sexpr (en, pn_name, var_list)
case ("pexpr")
  call eval_node_compile_pexpr (en, pn_name, var_list)
case ("variable")
  var_name = parse_node_get_string (pn_name)
  if (present (var_type)) then
    select case (var_type)
      case (V_LOG); var_name = "?" // var_name
      case (V_SEV); var_name = "@" // var_name
      case (V_STR); var_name = "$" // var_name ! $ sign
    end select
  end if
  var => var_list_get_var_ptr &
    (var_list, var_name, var_type, defined=.true.)
  allocate (en)
  if (associated (var)) then
    select case (var_entry_get_type (var))
      case (V_LOG)
        call eval_node_init_log_ptr &
          (en, var_entry_get_name (var), var_entry_get_lval_ptr (var), &
           var_entry_get_known_ptr (var))
      case (V_INT)
        call eval_node_init_int_ptr &
          (en, var_entry_get_name (var), var_entry_get_ival_ptr (var), &
           var_entry_get_known_ptr (var))
      case (V_REAL)
        call eval_node_init_real_ptr &
          (en, var_entry_get_name (var), var_entry_get_rval_ptr (var), &
           var_entry_get_known_ptr (var))
      case (V_CMPLX)
        call eval_node_init_cmplx_ptr &
          (en, var_entry_get_name (var), var_entry_get_cval_ptr (var), &
           var_entry_get_known_ptr (var))
      case (V_SEV)

```

```

        call eval_node_init_subevt_ptr &
            (en, var_entry_get_name (var), var_entry_get_pval_ptr (var), &
             var_entry_get_known_ptr (var))
    case (V_STR)
        call eval_node_init_string_ptr &
            (en, var_entry_get_name (var), var_entry_get_sval_ptr (var), &
             var_entry_get_known_ptr (var))
    case (V_OBS1_INT, V_OBS2_INT, V_OBS1_REAL, V_OBS2_REAL)
        call eval_node_init_obs (en, var)
    case default
        call parse_node_write (pn)
        call msg_fatal ("Variable of this type " // &
            "is not allowed in the present context")
        if (present (var_type)) then
            select case (var_type)
            case (V_LOG)
                call eval_node_init_log_ptr (en, var_name, no_lval, unknown)
            case (V_SEV)
                call eval_node_init_subevt_ptr &
                    (en, var_name, no_pval, unknown)
            case (V_STR)
                call eval_node_init_string_ptr &
                    (en, var_name, no_sval, unknown)
            end select
        else
            call eval_node_init_real_ptr (en, var_name, no_rval, unknown)
        end if
    end select
else
    call parse_node_write (pn)
    call msg_error ("This variable is undefined at this point")
    if (present (var_type)) then
        select case (var_type)
        case (V_LOG)
            call eval_node_init_log_ptr (en, var_name, no_lval, unknown)
        case (V_SEV)
            call eval_node_init_subevt_ptr &
                (en, var_name, no_pval, unknown)
        case (V_STR)
            call eval_node_init_string_ptr (en, var_name, no_sval, unknown)
        end select
    else
        call eval_node_init_real_ptr (en, var_name, no_rval, unknown)
    end if
end if
end if
end select
if (debug) then
    call eval_node_write (en)
    print *, "done variable"
end if
end if
end subroutine eval_node_compile_variable

```

In a given context, a variable has to have a certain type.

(Expressions: procedures) + \equiv

```

subroutine check_var_type (pn, ok, type_actual, type_requested)
  type(parse_node_t), intent(in) :: pn
  logical, intent(out) :: ok
  integer, intent(in) :: type_actual
  integer, intent(in), optional :: type_requested
  if (present (type_requested)) then
    select case (type_requested)
    case (V_LOG)
      select case (type_actual)
      case (V_LOG)
      case default
        call parse_node_write (pn)
        call msg_fatal ("Variable type is invalid (should be logical)")
        ok = .false.
      end select
    case (V_SEV)
      select case (type_actual)
      case (V_SEV)
      case default
        call parse_node_write (pn)
        call msg_fatal &
          ("Variable type is invalid (should be particle set)")
        ok = .false.
      end select
    case (V_PDG)
      select case (type_actual)
      case (V_PDG)
      case default
        call parse_node_write (pn)
        call msg_fatal &
          ("Variable type is invalid (should be PDG array)")
        ok = .false.
      end select
    case (V_STR)
      select case (type_actual)
      case (V_STR)
      case default
        call parse_node_write (pn)
        call msg_fatal &
          ("Variable type is invalid (should be string)")
        ok = .false.
      end select
    case default
      call parse_node_write (pn)
      call msg_bug ("Variable type is unknown")
    end select
  else
    select case (type_actual)
    case (V_REAL, V_OBS1_REAL, V_OBS2_REAL, V_INT, V_OBS1_INT, &
          V_OBS2_INT, V_CMPLX)
    case default
      call parse_node_write (pn)
      call msg_fatal ("Variable type is invalid (should be numeric)")
      ok = .false.
    end select
  end if
end subroutine

```

```

        end select
    end if
    ok = .true.
end subroutine check_var_type

```

Retrieve the result of an integration. If the requested process has been integrated, the results are available as special variables. (The variables cannot be accessed in the usual way since they contain brackets in their names.)

Since this compilation step may occur before the processes have been loaded, we have to initialize the required variables before they are used.

(Expressions: procedures)+≡

```

subroutine eval_node_compile_result (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_key, pn_prc_id
    type(string_t) :: key, prc_id, var_name
    type(var_entry_t), pointer :: var
    if (debug) then
        print *, "read result"; call parse_node_write (pn)
    end if
    pn_key => parse_node_get_sub_ptr (pn)
    pn_prc_id => parse_node_get_next_ptr (pn_key)
    key = parse_node_get_key (pn_key)
    prc_id = parse_node_get_string (pn_prc_id)
    var_name = key // "(" // prc_id // ")"
    var => var_list_get_var_ptr (var_list, var_name)
    if (associated (var)) then
        allocate (en)
        select case (char(key))
            case ("num_id", "n_calls")
                call eval_node_init_int_ptr &
                    (en, var_name, var_entry_get_ival_ptr (var), &
                     var_entry_get_known_ptr (var))
            case ("integral", "error", "accuracy", "chi2", "efficiency")
                call eval_node_init_real_ptr &
                    (en, var_name, var_entry_get_rval_ptr (var), &
                     var_entry_get_known_ptr (var))
            end select
        else
            call msg_fatal ("Result variable '" // char (var_name) &
                           // "' is undefined (call 'integrate' before use)")
        end if
    if (debug) then
        call eval_node_write (en)
        print *, "done result"
    end if
end subroutine eval_node_compile_result

```

This user observable behaves like a variable. We link the node to the generic user-observable entry in the variable list. The syntax element has an argument which provides the name of the user variable, this is stored as an eval-node alongside with the variable. When the variable value is used, the user-supplied

external function is called and provides the (real) result value.

(Expressions: procedures)+≡

```

subroutine eval_node_compile_user_observable (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in), target :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_key, pn_arg, pn_obs
  type(eval_node_t), pointer :: en0
  integer :: res_type
  type(string_t) :: var_name
  type(var_entry_t), pointer :: var
  if (debug) then
    print *, "read user observable"; call parse_node_write (pn)
  end if
  pn_key => parse_node_get_sub_ptr (pn)
  select case (char (parse_node_get_key (pn_key)))
  case ("user_obs")
    res_type = V_REAL
  case default
    call parse_node_write (pn_key)
    call msg_bug ("user_observable: wrong keyword")
  end select
  pn_arg => parse_node_get_next_ptr (pn_key)
  pn_obs => parse_node_get_sub_ptr (pn_arg)
  call eval_node_compile_sexpr (en0, pn_obs, var_list)
  select case (res_type)
  case (V_INT); var_name = "_User_obs_int"
  case (V_REAL); var_name = "_User_obs_real"
  end select
  var => var_list_get_var_ptr (var_list, var_name, defined=.true.)
  allocate (en)
  if (associated (var)) then
    call eval_node_init_obs (en, var, en0)
  else
    call parse_node_write (pn)
    call msg_error ("This variable is undefined at this point")
  end if
  if (debug) then
    call eval_node_write (en)
    print *, "done user observable"
  end if
end subroutine eval_node_compile_user_observable

```

Functions with a single argument. For non-constant arguments, watch for functions which convert their argument to a different type.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_unary_function (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_fname, pn_arg
  type(eval_node_t), pointer :: en1
  type(string_t) :: key

```

```

integer :: t
if (debug) then
    print *, "read unary function"; call parse_node_write (pn)
end if
pn_fname => parse_node_get_sub_ptr (pn)
pn_arg => parse_node_get_next_ptr (pn_fname, tag="function_arg1")
call eval_node_compile_expr &
    (en1, parse_node_get_sub_ptr (pn_arg, tag="expr"), var_list)
t = en1%result_type
allocate (en)
key = parse_node_get_key (pn_fname)
if (en1%type == EN_CONSTANT) then
    select case (char (key))
    case ("real")
        select case (t)
        case (V_INT); call eval_node_init_real (en, real_i (en1))
        case (V_REAL); deallocate (en); en => en1
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("int")
        select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_init_int (en, int_r (en1))
        case (V_CMPLX); call eval_node_init_int (en, int_c (en1))
        end select
    case ("nint")
        select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_init_int (en, nint_r (en1))
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("floor")
        select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_init_int (en, floor_r (en1))
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("ceiling")
        select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_init_int (en, ceiling_r (en1))
        case default; call eval_type_error (pn, char (key), t)
        end select
    case ("abs")
        select case (t)
        case (V_INT); call eval_node_init_int (en, abs_i (en1))
        case (V_REAL); call eval_node_init_real (en, abs_r (en1))
        case (V_CMPLX); call eval_node_init_real (en, abs_c (en1))
        end select
    case ("sgn")
        select case (t)
        case (V_INT); call eval_node_init_int (en, sgn_i (en1))
        case (V_REAL); call eval_node_init_real (en, sgn_r (en1))
        case default; call eval_type_error (pn, char (key), t)

```

```

        end select
case ("sqrt")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, sqrt_r (en1))
        case (V_CMPLX); call eval_node_init_cmplx (en, sqrt_c (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("exp")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, exp_r (en1))
        case (V_CMPLX); call eval_node_init_cmplx (en, exp_c (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("log")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, log_r (en1))
        case (V_CMPLX); call eval_node_init_cmplx (en, log_c (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("log10")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, log10_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("sin")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, sin_r (en1))
        case (V_CMPLX); call eval_node_init_cmplx (en, sin_c (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("cos")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, cos_r (en1))
        case (V_CMPLX); call eval_node_init_cmplx (en, cos_c (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("tan")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, tan_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("asin")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, asin_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("acos")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, acos_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("atan")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, atan_r (en1))

```

```

        case default; call eval_type_error (pn, char (key), t)
    end select
case ("sinh")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, sinh_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("cosh")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, cosh_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("tanh")
    select case (t)
        case (V_REAL); call eval_node_init_real (en, tanh_r (en1))
        case default; call eval_type_error (pn, char (key), t)
    end select
case default
    call parse_node_mismatch ("function name", pn_fname)
end select
call eval_node_final_rec (en1)
deallocate (en1)
else
    select case (char (key))
    case ("real")
        call eval_node_init_branch (en, key, V_REAL, en1)
    case ("int", "nint", "floor", "ceiling")
        call eval_node_init_branch (en, key, V_INT, en1)
    case default
        call eval_node_init_branch (en, key, t, en1)
    end select
    select case (char (key))
    case ("real")
        select case (t)
            case (V_INT); call eval_node_set_op1_real (en, real_i)
            case (V_REAL); deallocate (en); en => en1
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("int")
        select case (t)
            case (V_INT); deallocate (en); en => en1
            case (V_REAL); call eval_node_set_op1_int (en, int_r)
            case (V_CMPLX); call eval_node_set_op1_int (en, int_c)
        end select
    case ("nint")
        select case (t)
            case (V_INT); deallocate (en); en => en1
            case (V_REAL); call eval_node_set_op1_int (en, nint_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("floor")
        select case (t)
            case (V_INT); deallocate (en); en => en1
            case (V_REAL); call eval_node_set_op1_int (en, floor_r)

```



```

        case default; call eval_type_error (pn, char (key), t)
    end select
case ("ceiling")
    select case (t)
        case (V_INT); deallocate (en); en => en1
        case (V_REAL); call eval_node_set_op1_int (en, ceiling_r)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("abs")
    select case (t)
        case (V_INT); call eval_node_set_op1_int (en, abs_i)
        case (V_REAL); call eval_node_set_op1_real (en, abs_r)
        case (V_CMPLX); call eval_node_set_op1_real (en, abs_c)
    end select
case ("sgn")
    select case (t)
        case (V_INT); call eval_node_set_op1_int (en, sgn_i)
        case (V_REAL); call eval_node_set_op1_real (en, sgn_r)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("sqrt")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, sqrt_r)
        case (V_CMPLX); call eval_node_set_op1_cmplx (en, sqrt_c)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("exp")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, exp_r)
        case (V_CMPLX); call eval_node_set_op1_cmplx (en, exp_c)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("log")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, log_r)
        case (V_CMPLX); call eval_node_set_op1_cmplx (en, log_c)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("log10")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, log10_r)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("sin")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, sin_r)
        case (V_CMPLX); call eval_node_set_op1_cmplx (en, sin_c)
        case default; call eval_type_error (pn, char (key), t)
    end select
case ("cos")
    select case (t)
        case (V_REAL); call eval_node_set_op1_real (en, cos_r)
        case (V_CMPLX); call eval_node_set_op1_cmplx (en, cos_c)
        case default; call eval_type_error (pn, char (key), t)
    end select

```

```

        end select
    case ("tan")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, tan_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("asin")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, asin_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("acos")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, acos_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("atan")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, atan_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("sinh")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, sinh_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("cosh")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, cosh_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case ("tanh")
        select case (t)
            case (V_REAL); call eval_node_set_op1_real (en, tanh_r)
            case default; call eval_type_error (pn, char (key), t)
        end select
    case default
        call parse_node_mismatch ("function name", pn_fname)
    end select
end if
if (debug) then
    call eval_node_write (en)
    print *, "done function"
end if
end subroutine eval_node_compile_unary_function

```

Functions with two arguments.

(Expressions: procedures) + \equiv

```

recursive subroutine eval_node_compile_binary_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_fname, pn_arg, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en1, en2

```

```

type(string_t) :: key
integer :: t1, t2
if (debug) then
    print *, "read binary function"; call parse_node_write (pn)
end if
pn_fname => parse_node_get_sub_ptr (pn)
pn_arg => parse_node_get_next_ptr (pn_fname, tag="function_arg2")
pn_arg1 => parse_node_get_sub_ptr (pn_arg, tag="expr")
pn_arg2 => parse_node_get_next_ptr (pn_arg1, tag="expr")
call eval_node_compile_expr (en1, pn_arg1, var_list)
call eval_node_compile_expr (en2, pn_arg2, var_list)
t1 = en1%result_type
t2 = en2%result_type
allocate (en)
key = parse_node_get_key (pn_fname)
if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
    select case (char (key))
    case ("max")
        select case (t1)
        case (V_INT)
            select case (t2)
            case (V_INT); call eval_node_init_int (en, max_ii (en1, en2))
            case (V_REAL); call eval_node_init_real (en, max_ir (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
            end select
        case (V_REAL)
            select case (t2)
            case (V_INT); call eval_node_init_real (en, max_ri (en1, en2))
            case (V_REAL); call eval_node_init_real (en, max_rr (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
            end select
        case default; call eval_type_error (pn, char (key), t1)
    end select
    case ("min")
        select case (t1)
        case (V_INT)
            select case (t2)
            case (V_INT); call eval_node_init_int (en, min_ii (en1, en2))
            case (V_REAL); call eval_node_init_real (en, min_ir (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
            end select
        case (V_REAL)
            select case (t2)
            case (V_INT); call eval_node_init_real (en, min_ri (en1, en2))
            case (V_REAL); call eval_node_init_real (en, min_rr (en1, en2))
            case default; call eval_type_error (pn, char (key), t2)
            end select
        case default; call eval_type_error (pn, char (key), t1)
    end select
    case ("mod")
        select case (t1)
        case (V_INT)
            select case (t2)
            case (V_INT); call eval_node_init_int (en, mod_ii (en1, en2))

```

```

        case (V_REAL); call eval_node_init_real (en, mod_ir (en1, en2))
        case default; call eval_type_error (pn, char (key), t2)
    end select
case (V_REAL)
    select case (t2)
        case (V_INT); call eval_node_init_real (en, mod_ri (en1, en2))
        case (V_REAL); call eval_node_init_real (en, mod_rr (en1, en2))
        case default; call eval_type_error (pn, char (key), t2)
    end select
    case default; call eval_type_error (pn, char (key), t1)
end select
case ("modulo")
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_init_int (en, modulo_ii (en1, en2))
                case (V_REAL); call eval_node_init_real (en, modulo_ir (en1, en2))
                case default; call eval_type_error (pn, char (key), t2)
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_init_real (en, modulo_ri (en1, en2))
                case (V_REAL); call eval_node_init_real (en, modulo_rr (en1, en2))
                case default; call eval_type_error (pn, char (key), t2)
            end select
        case default; call eval_type_error (pn, char (key), t2)
    end select
case default
    call parse_node_mismatch ("function name", pn_fname)
end select
call eval_node_final_rec (en1)
deallocate (en1)
else
    call eval_node_init_branch (en, key, t1, en1, en2)
    select case (char (key))
        case ("max")
            select case (t1)
                case (V_INT)
                    select case (t2)
                        case (V_INT); call eval_node_set_op2_int (en, max_ii)
                        case (V_REAL); call eval_node_set_op2_real (en, max_ir)
                        case default; call eval_type_error (pn, char (key), t2)
                    end select
                case (V_REAL)
                    select case (t2)
                        case (V_INT); call eval_node_set_op2_real (en, max_ri)
                        case (V_REAL); call eval_node_set_op2_real (en, max_rr)
                        case default; call eval_type_error (pn, char (key), t2)
                    end select
                case default; call eval_type_error (pn, char (key), t2)
            end select
        case ("min")
            select case (t1)
                case (V_INT)

```

```

        select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, min_ii)
        case (V_REAL); call eval_node_set_op2_real (en, min_ir)
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, min_ri)
        case (V_REAL); call eval_node_set_op2_real (en, min_rr)
        case default; call eval_type_error (pn, char (key), t2)
        end select
        case default; call eval_type_error (pn, char (key), t2)
    end select
case ("mod")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, mod_ii)
        case (V_REAL); call eval_node_set_op2_real (en, mod_ir)
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, mod_ri)
        case (V_REAL); call eval_node_set_op2_real (en, mod_rr)
        case default; call eval_type_error (pn, char (key), t2)
        end select
        case default; call eval_type_error (pn, char (key), t2)
    end select
case ("modulo")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_int (en, modulo_ii)
        case (V_REAL); call eval_node_set_op2_real (en, modulo_ir)
        case default; call eval_type_error (pn, char (key), t2)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_real (en, modulo_ri)
        case (V_REAL); call eval_node_set_op2_real (en, modulo_rr)
        case default; call eval_type_error (pn, char (key), t2)
        end select
        case default; call eval_type_error (pn, char (key), t2)
    end select
case default
    call parse_node_mismatch ("function name", pn_fname)
end select
end if
if (debug) then
    call eval_node_write (en)
    print *, "done function"
end if
end subroutine eval_node_compile_binary_function

```

Variable definition

A block expression contains a variable definition (first argument) and an expression where the definition can be used (second argument). The **result_type** decides which type of expression is expected for the second argument. For numeric variables, if there is a mismatch between real and integer type, insert an extra node for type conversion.

(Expressions: procedures)+≡

```
recursive subroutine eval_node_compile_block_expr &
  (en, pn, var_list, result_type)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  integer, intent(in), optional :: result_type
  type(parse_node_t), pointer :: pn_var_spec, pn_var_subspec
  type(parse_node_t), pointer :: pn_var_type, pn_var_name, pn_var_expr
  type(parse_node_t), pointer :: pn_expr
  type(string_t) :: var_name
  type(eval_node_t), pointer :: en1, en2
  integer :: var_type
  logical :: new
  if (debug) then
    print *, "read block expr"; call parse_node_write (pn)
  end if
  new = .false.
  pn_var_spec => parse_node_get_sub_ptr (pn, 2)
  select case (char (parse_node_get_rule_key (pn_var_spec)))
  case ("var_num");      var_type = V_NONE
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec)
  case ("var_int");      var_type = V_INT
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_real");     var_type = V_REAL
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_cmplx");    var_type = V_CMPLX
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_logical_new"); var_type = V_LOG
    new = .true.
    pn_var_subspec => parse_node_get_sub_ptr (pn_var_spec, 2)
    pn_var_name => parse_node_get_sub_ptr (pn_var_subspec, 2)
  case ("var_logical_spec"); var_type = V_LOG
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
  case ("var_plist_new"); var_type = V_SEV
    new = .true.
    pn_var_subspec => parse_node_get_sub_ptr (pn_var_spec, 2)
    pn_var_name => parse_node_get_sub_ptr (pn_var_subspec, 2)
  case ("var_plist_spec"); var_type = V_SEV
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
```

```

case ("var_alias");    var_type = V_PDG
    new = .true.
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
case ("var_string_new");    var_type = V_STR
    new = .true.
    pn_var_subspec => parse_node_get_sub_ptr (pn_var_spec, 2)
    pn_var_name => parse_node_get_sub_ptr (pn_var_subspec, 2)
case ("var_string_spec");    var_type = V_STR
    pn_var_name => parse_node_get_sub_ptr (pn_var_spec, 2)
case default
    call parse_node_mismatch &
        ("logical|int|real|plist|alias", pn_var_type)
end select
pn_var_expr => parse_node_get_next_ptr (pn_var_name, 2)
pn_expr => parse_node_get_next_ptr (pn_var_spec, 2)
var_name = parse_node_get_string (pn_var_name)
select case (var_type)
case (V_LOG);    var_name = "?" // var_name
case (V_SEV);    var_name = "@" // var_name
case (V_STR);    var_name = "$" // var_name    ! $ sign
end select
call var_list_check_user_var (var_list, var_name, var_type, new)
call eval_node_compile_genexpr (en1, pn_var_expr, var_list, var_type)
call insert_conversion_node (en1, var_type)
allocate (en)
call eval_node_init_block (en, var_name, var_type, en1, var_list)
call eval_node_compile_genexpr (en2, pn_expr, en%var_list, result_type)
call eval_node_set_expr (en, en2)
if (debug) then
    call eval_node_write (en)
    print *, "done block expr"
end if
end subroutine eval_node_compile_block_expr

```

Insert a conversion node for integer/real/complex transformation if necessary.
What shall we do for the complex to integer/real conversion?

(Expressions: procedures)+≡

```

subroutine insert_conversion_node (en, result_type)
    type(eval_node_t), pointer :: en
    integer, intent(in) :: result_type
    type(eval_node_t), pointer :: en_conv
    select case (en%result_type)
    case (V_INT)
        select case (result_type)
        case (V_REAL)
            allocate (en_conv)
            call eval_node_init_branch (en_conv, var_str ("real"), V_REAL, en)
            call eval_node_set_op1_real (en_conv, real_i)
            en => en_conv
        case (V_CMPLX)
            allocate (en_conv)
            call eval_node_init_branch (en_conv, var_str ("complex"), V_CMPLX, en)
            call eval_node_set_op1_cmplx (en_conv, cmplx_i)

```

```

        en => en_conv
    end select
case (V_REAL)
    select case (result_type)
    case (V_INT)
        allocate (en_conv)
        call eval_node_init_branch (en_conv, var_str ("int"), V_INT, en)
        call eval_node_set_op1_int (en_conv, int_r)
        en => en_conv
    case (V_CMPLX)
        allocate (en_conv)
        call eval_node_init_branch (en_conv, var_str ("complex"), V_CMPLX, en)
        call eval_node_set_op1_cmplx (en_conv, cmplx_r)
        en => en_conv
    end select
case (V_CMPLX)
    select case (result_type)
    case (V_INT)
        allocate (en_conv)
        call eval_node_init_branch (en_conv, var_str ("int"), V_INT, en)
        call eval_node_set_op1_int (en_conv, int_c)
        en => en_conv
    case (V_REAL)
        allocate (en_conv)
        call eval_node_init_branch (en_conv, var_str ("real"), V_REAL, en)
        call eval_node_set_op1_real (en_conv, real_c)
        en => en_conv
    end select
case default
end select
end subroutine insert_conversion_node

```

Conditionals

A conditional has the structure `if lexpr then expr else expr`. So we first evaluate the logical expression, then depending on the result the first or second expression. Note that the second expression is mandatory.

The `result_type`, if present, defines the requested type of the `then` and `else` clauses. Default is numeric (int/real). If there is a mismatch between real and integer result types, insert conversion nodes.

(Expressions: procedures) +=

```

recursive subroutine eval_node_compile_conditional &
    (en, pn, var_list, result_type)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in), optional :: result_type
    type(parse_node_t), pointer :: pn_condition, pn_expr
    type(parse_node_t), pointer :: pn_maybe_elseif, pn_elseif_branch
    type(parse_node_t), pointer :: pn_maybe_else, pn_else_branch, pn_else_expr
    type(eval_node_t), pointer :: en0, en1, en2
    integer :: restype

```



```

if (debug) then
    print *, "read conditional"; call parse_node_write (pn)
end if
pn_condition => parse_node_get_sub_ptr (pn, 2, tag="lexpr")
pn_expr => parse_node_get_next_ptr (pn_condition, 2)
call eval_node_compile_lexpr (en0, pn_condition, var_list)
call eval_node_compile_genexpr (en1, pn_expr, var_list, result_type)
if (present (result_type)) then
    restype = major_result_type (result_type, en1%result_type)
else
    restype = en1%result_type
end if
pn_maybe_elseif => parse_node_get_next_ptr (pn_expr)
select case (char (parse_node_get_rule_key (pn_maybe_elseif)))
case ("maybe_elseif_lexpr", &
    "maybe_elseif_lexpr", &
    "maybe_elseif_pexpr", &
    "maybe_elseif_cexpr", &
    "maybe_elseif_sexpr")
    pn_elseif_branch => parse_node_get_sub_ptr (pn_maybe_elseif)
    pn_maybe_else => parse_node_get_next_ptr (pn_maybe_elseif)
    select case (char (parse_node_get_rule_key (pn_maybe_else)))
    case ("maybe_else_lexpr", &
        "maybe_else_lexpr", &
        "maybe_else_pexpr", &
        "maybe_else_cexpr", &
        "maybe_else_sexpr")
        pn_else_branch => parse_node_get_sub_ptr (pn_maybe_else)
        pn_else_expr => parse_node_get_sub_ptr (pn_else_branch, 2)
    case default
        pn_else_expr => null ()
    end select
    call eval_node_compile_elseif &
        (en2, pn_elseif_branch, pn_else_expr, var_list, restype)
case ("maybe_else_lexpr", &
    "maybe_else_lexpr", &
    "maybe_else_pexpr", &
    "maybe_else_cexpr", &
    "maybe_else_sexpr")
    pn_maybe_else => pn_maybe_elseif
    pn_maybe_elseif => null ()
    pn_else_branch => parse_node_get_sub_ptr (pn_maybe_else)
    pn_else_expr => parse_node_get_sub_ptr (pn_else_branch, 2)
    call eval_node_compile_genexpr &
        (en2, pn_else_expr, var_list, restype)
case ("endif")
    call eval_node_compile_default_else (en2, restype)
case default
    call msg_bug ("Broken conditional: unexpected " &
        // char (parse_node_get_rule_key (pn_maybe_elseif)))
end select
call eval_node_create_conditional (en, en0, en1, en2, restype)
call conditional_insert_conversion_nodes (en, restype)
if (debug) then

```

```

        call eval_node_write (en)
        print *, "done conditional"
    end if
end subroutine eval_node_compile_conditional

```

This recursively generates 'elseif' conditionals as a chain of sub-nodes of the main conditional.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_elseif &
    (en, pn, pn_else_expr, var_list, result_type)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(parse_node_t), pointer :: pn_else_expr
    type(var_list_t), intent(in), target :: var_list
    integer, intent(inout) :: result_type
    type(parse_node_t), pointer :: pn_next, pn_condition, pn_expr
    type(eval_node_t), pointer :: en0, en1, en2
    pn_condition => parse_node_get_sub_ptr (pn, 2, tag="lexpr")
    pn_expr => parse_node_get_next_ptr (pn_condition, 2)
    call eval_node_compile_lexpr (en0, pn_condition, var_list)
    call eval_node_compile_genexpr (en1, pn_expr, var_list, result_type)
    result_type = major_result_type (result_type, en1%result_type)
    pn_next => parse_node_get_next_ptr (pn)
    if (associated (pn_next)) then
        call eval_node_compile_elseif &
            (en2, pn_next, pn_else_expr, var_list, result_type)
        result_type = major_result_type (result_type, en2%result_type)
    else if (associated (pn_else_expr)) then
        call eval_node_compile_genexpr &
            (en2, pn_else_expr, var_list, result_type)
        result_type = major_result_type (result_type, en2%result_type)
    else
        call eval_node_compile_default_else (en2, result_type)
    end if
    call eval_node_create_conditional (en, en0, en1, en2, result_type)
end subroutine eval_node_compile_elseif

```

This makes a default 'else' branch in case it was omitted. The default value just depends on the expected type.

(Expressions: procedures)+≡

```

subroutine eval_node_compile_default_else (en, result_type)
    type(eval_node_t), pointer :: en
    integer, intent(in) :: result_type
    type(subvt_t) :: pval_empty
    type(pdg_array_t) :: aval_undefined
    allocate (en)
    select case (result_type)
    case (V_LOG); call eval_node_init_log (en, .false.)
    case (V_INT); call eval_node_init_int (en, 0)
    case (V_REAL); call eval_node_init_real (en, 0._default)
    case (V_CMPLX)
        call eval_node_init_cmplx (en, (0._default, 0._default))
    case (V_SEV)

```

```

        call subevt_init (pval_empty)
        call eval_node_init_subevt (en, pval_empty)
    case (V_PDG)
        call eval_node_init_pdg_array (en, aval_undefined)
    case (V_STR)
        call eval_node_init_string (en, var_str (""))
    case default
        call msg_bug ("Undefined type for 'else' branch in conditional")
    end select
end subroutine eval_node_compile_default_else

```

If the logical expression is constant, we can simplify the conditional node by replacing it with the selected branch. Otherwise, we initialize a true branching.

(Expressions: procedures) +≡

```

subroutine eval_node_create_conditional (en, en0, en1, en2, result_type)
    type(eval_node_t), pointer :: en, en0, en1, en2
    integer, intent(in) :: result_type
    if (en0%type == EN_CONSTANT) then
        if (en0%lval) then
            en => en1
            call eval_node_final_rec (en2)
            deallocate (en2)
        else
            en => en2
            call eval_node_final_rec (en1)
            deallocate (en1)
        end if
    else
        allocate (en)
        call eval_node_init_conditional (en, result_type, en0, en1, en2)
    end if
end subroutine eval_node_create_conditional

```

Return the numerical result type which should be used for the combination of the two result types.

(Expressions: procedures) +≡

```

function major_result_type (t1, t2) result (t)
    integer :: t
    integer, intent(in) :: t1, t2
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT, V_REAL, V_CMPLX)
            t = t2
        case default
            call type_mismatch ()
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT)
            t = t1
        case (V_REAL, V_CMPLX)
            t = t2

```

```

        case default
            call type_mismatch ()
        end select
    end select
case (V_CMPLX)
    select case (t2)
        case (V_INT, V_REAL, V_CMPLX)
            t = t1
        case default
            call type_mismatch ()
        end select
case default
    if (t1 == t2) then
        t = t1
    else
        call type_mismatch ()
    end if
end select
contains
    subroutine type_mismatch ()
        call msg_bug ("Type mismatch in branches of a conditional expression")
    end subroutine type_mismatch
end function major_result_type

```

Recursively insert conversion nodes where necessary.

(Expressions: procedures) +≡

```

recursive subroutine conditional_insert_conversion_nodes (en, result_type)
    type(eval_node_t), intent(inout), target :: en
    integer, intent(in) :: result_type
    select case (result_type)
        case (V_INT, V_REAL, V_CMPLX)
            call insert_conversion_node (en%arg1, result_type)
            if (en%arg2%type == EN_CONDITIONAL) then
                call conditional_insert_conversion_nodes (en%arg2, result_type)
            else
                call insert_conversion_node (en%arg2, result_type)
            end if
        end select
end subroutine conditional_insert_conversion_nodes

```

Logical expressions

A logical expression consists of one or more singlet logical expressions concatenated by ;. This is for allowing side-effects, only the last value is used.

(Expressions: procedures) +≡

```

recursive subroutine eval_node_compile_lexpr (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_term, pn_sequel, pn_arg
    type(eval_node_t), pointer :: en1, en2
    if (debug) then
        print *, "read lexpr"; call parse_node_write (pn)
    end if

```

```

end if
pn_term => parse_node_get_sub_ptr (pn, tag="lsinglet")
call eval_node_compile_ksinglet (en, pn_term, var_list)
pn_sequel => parse_node_get_next_ptr (pn_term, tag="lsequel")
do while (associated (pn_sequel))
    pn_arg => parse_node_get_sub_ptr (pn_sequel, 2, tag="lsinglet")
    en1 => en
    call eval_node_compile_ksinglet (en2, pn_arg, var_list)
    allocate (en)
    if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
        call eval_node_init_log (en, ignore_first_ll (en1, en2))
        call eval_node_final_rec (en1)
        call eval_node_final_rec (en2)
        deallocate (en1, en2)
    else
        call eval_node_init_branch &
            (en, var_str ("lsequel"), V_LOG, en1, en2)
        call eval_node_set_op2_log (en, ignore_first_ll)
    end if
    pn_sequel => parse_node_get_next_ptr (pn_sequel)
end do
if (debug) then
    call eval_node_write (en)
    print *, "done lexpr"
end if
end subroutine eval_node_compile_lexpr

```

A logical singlet expression consists of one or more logical terms concatenated by or.

(Expressions: procedures) +≡

```

recursive subroutine eval_node_compile_ksinglet (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_term, pn_alternative, pn_arg
    type(eval_node_t), pointer :: en1, en2
    if (debug) then
        print *, "read ksinglet"; call parse_node_write (pn)
    end if
    pn_term => parse_node_get_sub_ptr (pn, tag="lterm")
    call eval_node_compile_lterm (en, pn_term, var_list)
    pn_alternative => parse_node_get_next_ptr (pn_term, tag="alternative")
    do while (associated (pn_alternative))
        pn_arg => parse_node_get_sub_ptr (pn_alternative, 2, tag="lterm")
        en1 => en
        call eval_node_compile_lterm (en2, pn_arg, var_list)
        allocate (en)
        if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
            call eval_node_init_log (en, or_ll (en1, en2))
            call eval_node_final_rec (en1)
            call eval_node_final_rec (en2)
            deallocate (en1, en2)
        else

```

```

        call eval_node_init_branch &
            (en, var_str ("alternative"), V_LOG, en1, en2)
        call eval_node_set_op2_log (en, or_ll)
    end if
    pn_alternative => parse_node_get_next_ptr (pn_alternative)
end do
if (debug) then
    call eval_node_write (en)
    print *, "done lsinglet"
end if
end subroutine eval_node_compile_lsinglet

```

A logical term consists of one or more logical values concatenated by and.

(Expressions: procedures) +=

```

recursive subroutine eval_node_compile_lterm (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_term, pn_coincidence, pn_arg
    type(eval_node_t), pointer :: en1, en2
    if (debug) then
        print *, "read lterm"; call parse_node_write (pn)
    end if
    pn_term => parse_node_get_sub_ptr (pn)
    call eval_node_compile_lvalue (en, pn_term, var_list)
    pn_coincidence => parse_node_get_next_ptr (pn_term, tag="coincidence")
    do while (associated (pn_coincidence))
        pn_arg => parse_node_get_sub_ptr (pn_coincidence, 2)
        en1 => en
        call eval_node_compile_lvalue (en2, pn_arg, var_list)
        allocate (en)
        if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
            call eval_node_init_log (en, and_ll (en1, en2))
            call eval_node_final_rec (en1)
            call eval_node_final_rec (en2)
            deallocate (en1, en2)
        else
            call eval_node_init_branch &
                (en, var_str ("coincidence"), V_LOG, en1, en2)
            call eval_node_set_op2_log (en, and_ll)
        end if
        pn_coincidence => parse_node_get_next_ptr (pn_coincidence)
    end do
    if (debug) then
        call eval_node_write (en)
        print *, "done lterm"
    end if
end subroutine eval_node_compile_lterm

```

Logical variables are disabled, because they are confused with the l.h.s. of compared expressions.

(Expressions: procedures) +=

```

recursive subroutine eval_node_compile_lvalue (en, pn, var_list)

```

```

type(eval_node_t), pointer :: en
type(parse_node_t), intent(in) :: pn
type(var_list_t), intent(in), target :: var_list
if (debug) then
    print *, "read lvalue"; call parse_node_write (pn)
end if
select case (char (parse_node_get_rule_key (pn)))
case ("true")
    allocate (en)
    call eval_node_init_log (en, .true.)
case ("false")
    allocate (en)
    call eval_node_init_log (en, .false.)
case ("negation")
    call eval_node_compile_negation (en, pn, var_list)
case ("lvariable")
    call eval_node_compile_variable (en, pn, var_list, V_LOG)
case ("lexpr")
    call eval_node_compile_lexpr (en, pn, var_list)
case ("block_lexpr")
    call eval_node_compile_block_expr (en, pn, var_list, V_LOG)
case ("conditional_lexpr")
    call eval_node_compile_conditional (en, pn, var_list, V_LOG)
case ("compared_expr")
    call eval_node_compile_compared_expr (en, pn, var_list, V_REAL)
case ("compared_sexpr")
    call eval_node_compile_compared_expr (en, pn, var_list, V_STR)
case ("all_fun", "any_fun", "no_fun", "user_cut_fun")
    call eval_node_compile_log_function (en, pn, var_list)
case ("record_cmd")
    call eval_node_compile_record_cmd (en, pn, var_list)
case default
    call parse_node_mismatch &
        ("true|false|negation|lvariable|" // &
        "lexpr|block_lexpr|conditional_lexpr|" // &
        "compared_expr|compared_sexpr|logical_pexpr", pn)
end select
if (debug) then
    call eval_node_write (en)
    print *, "done lvalue"
end if
end subroutine eval_node_compile_lvalue

```

A negation consists of the keyword not and a logical value.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_negation (en, pn, var_list)
type(eval_node_t), pointer :: en
type(parse_node_t), intent(in) :: pn
type(var_list_t), intent(in), target :: var_list
type(parse_node_t), pointer :: pn_arg
type(eval_node_t), pointer :: en1
if (debug) then
    print *, "read negation"; call parse_node_write (pn)
end if

```

```

pn_arg => parse_node_get_sub_ptr (pn, 2)
call eval_node_compile_lvalue (en1, pn_arg, var_list)
allocate (en)
if (en1%type == EN_CONSTANT) then
    call eval_node_init_log (en, not_1 (en1))
    call eval_node_final_rec (en1)
    deallocate (en1)
else
    call eval_node_init_branch (en, var_str ("not"), V_LOG, en1)
    call eval_node_set_op1_log (en, not_1)
end if
if (debug) then
    call eval_node_write (en)
    print *, "done negation"
end if
end subroutine eval_node_compile_negation

```

Comparisons

Up to the loop, this is easy. There is always at least one comparison. This is evaluated, and the result is the logical node **en**. If it is constant, we keep its second sub-node as **en2**. (Thus, at the very end **en2** has to be deleted if **en** is (still) constant.)

If there is another comparison, we first check if the first comparison was constant. In that case, there are two possibilities: (i) it was true. Then, its right-hand side is compared with the new right-hand side, and the result replaces the previous one which is deleted. (ii) it was false. In this case, the result of the whole comparison is false, and we can exit the loop without evaluating anything else.

Now assume that the first comparison results in a valid branch, its second sub-node kept as **en2**. We first need a copy of this, which becomes the new left-hand side. If **en2** is constant, we make an identical constant node **en1**. Otherwise, we make **en1** an appropriate pointer node. Next, the first branch is saved as **en0** and we evaluate the comparison between **en1** and the a right-hand side. If this turns out to be constant, there are again two possibilities: (i) true, then we revert to the previous result. (ii) false, then the wh

(Expressions: procedures) +≡

```

recursive subroutine eval_node_compile_compared_expr (en, pn, var_list, type)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in) :: type
    type(parse_node_t), pointer :: pn_comparison, pn_expr1
    type(eval_node_t), pointer :: en0, en1, en2
    if (debug) then
        print *, "read comparison"; call parse_node_write (pn)
    end if
    select case (type)
    case (V_INT, V_REAL)
        pn_expr1 => parse_node_get_sub_ptr (pn, tag="expr")
        call eval_node_compile_expr (en1, pn_expr1, var_list)

```



```

        pn_comparison => parse_node_get_next_ptr (pn_expr1, tag="comparison")
case (V_STR)
    pn_expr1 => parse_node_get_sub_ptr (pn, tag="sexpr")
    call eval_node_compile_sexpr (en1, pn_expr1, var_list)
    pn_comparison => parse_node_get_next_ptr (pn_expr1, tag="str_comparison")
end select
call eval_node_compile_comparison &
    (en, en1, en2, pn_comparison, var_list, type)
pn_comparison => parse_node_get_next_ptr (pn_comparison)
SCAN_FURTHER: do while (associated (pn_comparison))
    if (en%type == EN_CONSTANT) then
        if (en%lval) then
            en1 => en2
            call eval_node_final_rec (en); deallocate (en)
            call eval_node_compile_comparison &
                (en, en1, en2, pn_comparison, var_list, type)
        else
            exit SCAN_FURTHER
        end if
    else
        allocate (en1)
        if (en2%type == EN_CONSTANT) then
            select case (en2%result_type)
            case (V_INT); call eval_node_init_int      (en1, en2%ival)
            case (V_REAL); call eval_node_init_real   (en1, en2%rval)
            case (V_STR); call eval_node_init_string  (en1, en2%sval)
            end select
        else
            select case (en2%result_type)
            case (V_INT); call eval_node_init_int_ptr &
                (en1, var_str ("(previous)"), en2%ival, en2%value_is_known)
            case (V_REAL); call eval_node_init_real_ptr &
                (en1, var_str ("(previous)"), en2%rval, en2%value_is_known)
            case (V_STR); call eval_node_init_string_ptr &
                (en1, var_str ("(previous)"), en2%sval, en2%value_is_known)
            end select
        end if
        en0 => en
        call eval_node_compile_comparison &
            (en, en1, en2, pn_comparison, var_list, type)
        if (en%type == EN_CONSTANT) then
            if (en%lval) then
                call eval_node_final_rec (en); deallocate (en)
                en => en0
            else
                call eval_node_final_rec (en0); deallocate (en0)
                exit SCAN_FURTHER
            end if
        else
            en1 => en
            allocate (en)
            call eval_node_init_branch (en, var_str ("and"), V_LOG, en0, en1)
            call eval_node_set_op2_log (en, and_ll)
        end if
    end if
end if

```

```

        end if
        pn_comparison => parse_node_get_next_ptr (pn_comparison)
    end do SCAN_FURTHER
    if (en%type == EN_CONSTANT .and. associated (en2)) then
        call eval_node_final_rec (en2); deallocate (en2)
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done compared_expr"
    end if
end subroutine eval_node_compile_compared_expr

```

This takes two extra arguments: `en1`, the left-hand-side of the comparison, is already allocated and evaluated. `en2` (the right-hand side) and `en` (the result) are allocated by the routine. `pn` is the parse node which contains the operator and the right-hand side as subnodes.

If the result of the comparison is constant, `en1` is deleted but `en2` is kept, because it may be used in a subsequent comparison. `en` then becomes a constant. If the result is variable, `en` becomes a branch node which refers to `en1` and `en2`.

(Expressions: procedures) +=

```

recursive subroutine eval_node_compile_comparison &
    (en, en1, en2, pn, var_list, type)
    type(eval_node_t), pointer :: en, en1, en2
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    integer, intent(in) :: type
    type(parse_node_t), pointer :: pn_op, pn_arg
    type(string_t) :: key
    integer :: t1, t2
    type(var_entry_t), pointer :: var
    pn_op => parse_node_get_sub_ptr (pn)
    key = parse_node_get_key (pn_op)
    select case (type)
    case (V_INT, V_REAL)
        pn_arg => parse_node_get_next_ptr (pn_op, tag="expr")
        call eval_node_compile_expr (en2, pn_arg, var_list)
    case (V_STR)
        pn_arg => parse_node_get_next_ptr (pn_op, tag="sexpr")
        call eval_node_compile_sexpr (en2, pn_arg, var_list)
    end select
    t1 = en1%result_type
    t2 = en2%result_type
    allocate (en)
    if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
        select case (char (key))
        case ("<")
            select case (t1)
            case (V_INT)
                select case (t2)
                case (V_INT); call eval_node_init_log (en, comp_lt_ii (en1, en2))
                case (V_REAL); call eval_node_init_log (en, comp_lt_ir (en1, en2))
                end select
            case (V_REAL)

```

```

        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_lt_ri (en1, en2))
        case (V_REAL); call eval_node_init_log (en, comp_lt_rr (en1, en2))
        end select
    end select
case ">")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_gt_ii (en1, en2))
        case (V_REAL); call eval_node_init_log (en, comp_gt_ir (en1, en2))
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_gt_ri (en1, en2))
        case (V_REAL); call eval_node_init_log (en, comp_gt_rr (en1, en2))
        end select
    end select
case "<=")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_le_ii (en1, en2))
        case (V_REAL); call eval_node_init_log (en, comp_le_ir (en1, en2))
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_le_ri (en1, en2))
        case (V_REAL); call eval_node_init_log (en, comp_le_rr (en1, en2))
        end select
    end select
case ">=")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_ge_ii (en1, en2))
        case (V_REAL); call eval_node_init_log (en, comp_ge_ir (en1, en2))
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_ge_ri (en1, en2))
        case (V_REAL); call eval_node_init_log (en, comp_ge_rr (en1, en2))
        end select
    end select
case "==" )
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_eq_ii (en1, en2))
        case (V_REAL); call eval_node_init_log (en, comp_eq_ir (en1, en2))
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_init_log (en, comp_eq_ri (en1, en2))

```

```

        case (V_REAL); call eval_node_init_log (en, comp_eq_rr (en1, en2))
    end select
case (V_STR)
    select case (t2)
        case (V_STR); call eval_node_init_log (en, comp_eq_ss (en1, en2))
    end select
end select
case ("<>")
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_init_log (en, comp_ne_ii (en1, en2))
                case (V_REAL); call eval_node_init_log (en, comp_ne_ir (en1, en2))
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_init_log (en, comp_ne_ri (en1, en2))
                case (V_REAL); call eval_node_init_log (en, comp_ne_rr (en1, en2))
            end select
        case (V_STR)
            select case (t2)
                case (V_STR); call eval_node_init_log (en, comp_ne_ss (en1, en2))
            end select
    end select
case ("==~")
    var => var_list_get_var_ptr (var_list, var_str ("tolerance"))
    en1%tolerance => var_entry_get_rval_ptr (var)
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_init_log (en, comp_sim_ii (en1, en2))
                case (V_REAL); call eval_node_init_log (en, comp_sim_ir (en1, en2))
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_init_log (en, comp_sim_ri (en1, en2))
                case (V_REAL); call eval_node_init_log (en, comp_sim_rr (en1, en2))
            end select
        case (V_STR)
            select case (t2)
                case (V_STR); call eval_node_init_log (en, comp_eq_ss (en1, en2))
            end select
    end select
case ("<>~")
    var => var_list_get_var_ptr (var_list, var_str ("tolerance"))
    en1%tolerance => var_entry_get_rval_ptr (var)
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT)
                    call eval_node_init_log (en, comp_nsim_ii (en1, en2))
                case (V_REAL)
                    call eval_node_init_log (en, comp_nsim_ir (en1, en2))
            end select
    end select

```

```

        case (V_REAL)
            select case (t2)
            case (V_INT)
                call eval_node_init_log (en, comp_nsim_ri (en1, en2))
            case (V_REAL)
                call eval_node_init_log (en, comp_nsim_rr(en1, en2))
            end select
        case (V_STR)
            select case (t2)
            case (V_STR); call eval_node_init_log (en, comp_ne_ss (en1, en2))
            end select
        end select
    end select
    call eval_node_final_rec (en1)
    deallocate (en1)
else
    call eval_node_init_branch (en, key, V_LOG, en1, en2)
    select case (char (key))
    case ("<")
        select case (t1)
        case (V_INT)
            select case (t2)
            case (V_INT); call eval_node_set_op2_log (en, comp_lt_ii)
            case (V_REAL); call eval_node_set_op2_log (en, comp_lt_ir)
            end select
        case (V_REAL)
            select case (t2)
            case (V_INT); call eval_node_set_op2_log (en, comp_lt_ri)
            case (V_REAL); call eval_node_set_op2_log (en, comp_lt_rr)
            end select
        end select
    case (">")
        select case (t1)
        case (V_INT)
            select case (t2)
            case (V_INT); call eval_node_set_op2_log (en, comp_gt_ii)
            case (V_REAL); call eval_node_set_op2_log (en, comp_gt_ir)
            end select
        case (V_REAL)
            select case (t2)
            case (V_INT); call eval_node_set_op2_log (en, comp_gt_ri)
            case (V_REAL); call eval_node_set_op2_log (en, comp_gt_rr)
            end select
        end select
    case ("<=")
        select case (t1)
        case (V_INT)
            select case (t2)
            case (V_INT); call eval_node_set_op2_log (en, comp_le_ii)
            case (V_REAL); call eval_node_set_op2_log (en, comp_le_ir)
            end select
        case (V_REAL)
            select case (t2)
            case (V_INT); call eval_node_set_op2_log (en, comp_le_ri)

```

```

        case (V_REAL); call eval_node_set_op2_log (en, comp_le_rr)
    end select
end select
case (">=")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_log (en, comp_ge_ii)
        case (V_REAL); call eval_node_set_op2_log (en, comp_ge_ir)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_log (en, comp_ge_ri)
        case (V_REAL); call eval_node_set_op2_log (en, comp_ge_rr)
        end select
    end select
case ("==")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_log (en, comp_eq_ii)
        case (V_REAL); call eval_node_set_op2_log (en, comp_eq_ir)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_log (en, comp_eq_ri)
        case (V_REAL); call eval_node_set_op2_log (en, comp_eq_rr)
        end select
    case (V_STR)
        select case (t2)
        case (V_STR); call eval_node_set_op2_log (en, comp_eq_ss)
        end select
    end select
case ("<>")
    select case (t1)
    case (V_INT)
        select case (t2)
        case (V_INT); call eval_node_set_op2_log (en, comp_ne_ii)
        case (V_REAL); call eval_node_set_op2_log (en, comp_ne_ir)
        end select
    case (V_REAL)
        select case (t2)
        case (V_INT); call eval_node_set_op2_log (en, comp_ne_ri)
        case (V_REAL); call eval_node_set_op2_log (en, comp_ne_rr)
        end select
    case (V_STR)
        select case (t2)
        case (V_STR); call eval_node_set_op2_log (en, comp_ne_ss)
        end select
    end select
case ("==~")
    select case (t1)
    case (V_INT)
        select case (t2)

```

```

        case (V_INT); call eval_node_set_op2_log (en, comp_sim_ii)
        case (V_REAL); call eval_node_set_op2_log (en, comp_sim_ir)
    end select
case (V_REAL)
    select case (t2)
        case (V_INT); call eval_node_set_op2_log (en, comp_sim_ri)
        case (V_REAL); call eval_node_set_op2_log (en, comp_sim_rr)
    end select
case (V_STR)
    select case (t2)
        case (V_STR); call eval_node_set_op2_log (en, comp_eq_ss)
    end select
end select
var => var_list_get_var_ptr (var_list, var_str ("tolerance"))
en1%tolerance => var_entry_get_rval_ptr (var)
case ("<>~")
    select case (t1)
        case (V_INT)
            select case (t2)
                case (V_INT); call eval_node_set_op2_log (en, comp_nsim_ii)
                case (V_REAL); call eval_node_set_op2_log (en, comp_nsim_ir)
            end select
        case (V_REAL)
            select case (t2)
                case (V_INT); call eval_node_set_op2_log (en, comp_nsim_ri)
                case (V_REAL); call eval_node_set_op2_log (en, comp_nsim_rr)
            end select
        case (V_STR)
            select case (t2)
                case (V_STR); call eval_node_set_op2_log (en, comp_ne_ss)
            end select
    end select
var => var_list_get_var_ptr (var_list, var_str ("tolerance"))
en1%tolerance => var_entry_get_rval_ptr (var)
end select
end if
end subroutine eval_node_compile_comparison

```

Recording analysis data

The `record` command is actually a logical expression which always evaluates `true`.

(*Expressions: procedures*) +=

```

recursive subroutine eval_node_compile_record_cmd (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_key, pn_tag, pn_arg
    type(parse_node_t), pointer :: pn_arg1, pn_arg2, pn_arg3, pn_arg4
    type(eval_node_t), pointer :: en0, en1, en2, en3, en4
    type(var_entry_t), pointer :: var
    real(default), pointer :: event_weight

```

```

if (debug) then
  print *, "read record_cmd"; call parse_node_write (pn)
end if
pn_key => parse_node_get_sub_ptr (pn)
pn_tag => parse_node_get_next_ptr (pn_key)
pn_arg => parse_node_get_next_ptr (pn_tag)
select case (char (parse_node_get_key (pn_key)))
case ("record")
  var => var_list_get_var_ptr (var_list, var_str ("event_weight"))
  if (associated (var)) then
    event_weight => var_entry_get_rval_ptr (var)
  else
    event_weight => null ()
  end if
case ("record_unweighted")
  event_weight => null ()
end select
select case (char (parse_node_get_rule_key (pn_tag)))
case ("analysis_id")
  allocate (en0)
  call eval_node_init_string (en0, parse_node_get_string (pn_tag))
case default
  call eval_node_compile_sexpr (en0, pn_tag, var_list)
end select
allocate (en)
if (associated (pn_arg)) then
  pn_arg1 => parse_node_get_sub_ptr (pn_arg)
  call eval_node_compile_expr (en1, pn_arg1, var_list)
  if (en1%result_type == V_INT) &
    call insert_conversion_node (en1, V_REAL)
  pn_arg2 => parse_node_get_next_ptr (pn_arg1)
  if (associated (pn_arg2)) then
    call eval_node_compile_expr (en2, pn_arg2, var_list)
    if (en2%result_type == V_INT) &
      call insert_conversion_node (en2, V_REAL)
  pn_arg3 => parse_node_get_next_ptr (pn_arg2)
  if (associated (pn_arg3)) then
    call eval_node_compile_expr (en3, pn_arg3, var_list)
    if (en3%result_type == V_INT) &
      call insert_conversion_node (en3, V_REAL)
  pn_arg4 => parse_node_get_next_ptr (pn_arg3)
  if (associated (pn_arg4)) then
    call eval_node_compile_expr (en4, pn_arg4, var_list)
    if (en4%result_type == V_INT) &
      call insert_conversion_node (en4, V_REAL)
    call eval_node_init_record_cmd &
      (en, event_weight, en0, en1, en2, en3, en4)
  else
    call eval_node_init_record_cmd &
      (en, event_weight, en0, en1, en2, en3)
  end if
else
  call eval_node_init_record_cmd (en, event_weight, en0, en1, en2)
end if

```



```

        else
            call eval_node_init_record_cmd (en, event_weight, en0, en1)
        end if
    else
        call eval_node_init_record_cmd (en, event_weight, en0)
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done record_cmd"
    end if
end subroutine eval_node_compile_record_cmd

```

Particle-list expressions

A particle expression is a subevent or a concatenation of particle-list terms (using join).

(Expressions: procedures) +=

```

recursive subroutine eval_node_compile_pexpr (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_pterm, pn_concatenation, pn_op, pn_arg
    type(eval_node_t), pointer :: en1, en2
    type(subvt_t) :: subvt
    if (debug) then
        print *, "read pexpr"; call parse_node_write (pn)
    end if
    pn_pterm => parse_node_get_sub_ptr (pn)
    call eval_node_compile_pterm (en, pn_pterm, var_list)
    pn_concatenation => &
        parse_node_get_next_ptr (pn_pterm, tag="pconcatenation")
    do while (associated (pn_concatenation))
        pn_op => parse_node_get_sub_ptr (pn_concatenation)
        pn_arg => parse_node_get_next_ptr (pn_op)
        en1 => en
        call eval_node_compile_pterm (en2, pn_arg, var_list)
        allocate (en)
        if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
            call subvt_join (subvt, en1%pval, en2%pval)
            call eval_node_init_subvt (en, subvt)
            call eval_node_final_rec (en1)
            call eval_node_final_rec (en2)
            deallocate (en1, en2)
        else
            call eval_node_init_branch &
                (en, var_str ("join"), V_SEV, en1, en2)
            call eval_node_set_op2_sev (en, join_pp)
        end if
        pn_concatenation => parse_node_get_next_ptr (pn_concatenation)
    end do
    if (debug) then
        call eval_node_write (en)
    end if
end subroutine eval_node_compile_pexpr

```

```

        print *, "done pexpr"
    end if
end subroutine eval_node_compile_pexpr

```

A particle term is a subevent or a combination of particle-list values (using combine).

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_pterm (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_pvalue, pn_combination, pn_op, pn_arg
    type(eval_node_t), pointer :: en1, en2
    type(subvt_t) :: subvt
    if (debug) then
        print *, "read pterm"; call parse_node_write (pn)
    end if
    pn_pvalue => parse_node_get_sub_ptr (pn)
    call eval_node_compile_pvalue (en, pn_pvalue, var_list)
    pn_combination => &
        parse_node_get_next_ptr (pn_pvalue, tag="pcombination")
    do while (associated (pn_combination))
        pn_op => parse_node_get_sub_ptr (pn_combination)
        pn_arg => parse_node_get_next_ptr (pn_op)
        en1 => en
        call eval_node_compile_pvalue (en2, pn_arg, var_list)
        allocate (en)
        if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
            call subvt_combine (subvt, en1%pval, en2%pval)
            call eval_node_init_subvt (en, subvt)
            call eval_node_final_rec (en1)
            call eval_node_final_rec (en2)
            deallocate (en1, en2)
        else
            call eval_node_init_branch &
                (en, var_str ("combine"), V_SEV, en1, en2)
            call eval_node_set_op2_sev (en, combine_pp)
        end if
        pn_combination => parse_node_get_next_ptr (pn_combination)
    end do
    if (debug) then
        call eval_node_write (en)
        print *, "done pterm"
    end if
end subroutine eval_node_compile_pterm

```

A particle-list value is a PDG-code array, a particle identifier, a variable, a (grouped) pexpr, a block pexpr, a conditional, or a particle-list function.

The **cexpr** node is responsible for transforming a constant PDG-code array into a subevent. It takes the code array as its first argument, the event subevent as its second argument, and the requested particle type (incoming/outgoing) as its zero-th argument. The result is the list of particles in the event that match the code array.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_pvalue (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_prefix_cexpr
  type(eval_node_t), pointer :: en1, en2, en0
  type(string_t) :: key
  type(var_entry_t), pointer :: var
  logical, save, target :: known = .true.
  if (debug) then
    print *, "read pvalue"; call parse_node_write (pn)
  end if
  select case (char (parse_node_get_rule_key (pn)))
  case ("pexpr_src")
    call eval_node_compile_prefix_cexpr (en1, pn, var_list)
    allocate (en2)
    var => var_list_get_var_ptr (var_list, var_str ("%evt"))
    if (associated (var)) then
      call eval_node_init_subevt_ptr &
        (en2, var_str ("%evt"), var_entry_get_pval_ptr (var), known)
      allocate (en)
      call eval_node_init_branch &
        (en, var_str ("prt_selection"), V_SEV, en1, en2)
      call eval_node_set_op2_sev (en, select_pdg_ca)
      allocate (en0)
      pn_prefix_cexpr => parse_node_get_sub_ptr (pn)
      key = parse_node_get_rule_key (pn_prefix_cexpr)
      select case (char (key))
      case ("incoming_prt")
        call eval_node_init_int (en0, PRT_INCOMING)
        en%arg0 => en0
      case ("outgoing_prt")
        call eval_node_init_int (en0, PRT_OUTGOING)
        en%arg0 => en0
      end select
    else
      call parse_node_write (pn)
      call msg_bug (" Missing event data while compiling pvalue")
    end if
  case ("pvariable")
    call eval_node_compile_variable (en, pn, var_list, V_SEV)
  case ("pexpr")
    call eval_node_compile_pexpr (en, pn, var_list)
  case ("block_pexpr")
    call eval_node_compile_block_expr (en, pn, var_list, V_SEV)
  case ("conditional_pexpr")
    call eval_node_compile_conditional (en, pn, var_list, V_SEV)
  case ("join_fun", "combine_fun", "collect_fun", "select_fun", &
    "extract_fun", "sort_fun")
    call eval_node_compile_prt_function (en, pn, var_list)
  case default
    call parse_node_mismatch &
      ("prefix_cexpr|pvariable|" // &

```

```

        "grouped_pexpr|block_pexpr|conditional_pexpr|" // &
        "prt_function", pn)
end select
if (debug) then
    call eval_node_write (en)
    print *, "done pvalue"
end if
end subroutine eval_node_compile_pvalue

```

Particle functions

This combines the treatment of 'join', 'combine', 'collect', 'select', and 'extract' which all have the same syntax. The one or two argument nodes are allocated. If there is a condition, the condition node is also allocated as a logical expression, for which the variable list is augmented by the appropriate (unary/binary) observables.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_prt_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_clause, pn_key, pn_cond, pn_args
    type(parse_node_t), pointer :: pn_arg0, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en0, en1, en2
    type(string_t) :: key
    if (debug) then
        print *, "read prt_function"; call parse_node_write (pn)
    end if
    pn_clause => parse_node_get_sub_ptr (pn)
    pn_key   => parse_node_get_sub_ptr (pn_clause)
    pn_cond => parse_node_get_next_ptr (pn_key)
    if (associated (pn_cond)) &
        pn_arg0 => parse_node_get_sub_ptr (pn_cond, 2)
    pn_args => parse_node_get_next_ptr (pn_clause)
    pn_arg1 => parse_node_get_sub_ptr (pn_args)
    pn_arg2 => parse_node_get_next_ptr (pn_arg1)
    key = parse_node_get_key (pn_key)
    call eval_node_compile_pexpr (en1, pn_arg1, var_list)
    allocate (en)
    if (.not. associated (pn_arg2)) then
        select case (char (key))
        case ("collect")
            call eval_node_init_prt_fun_unary (en, en1, key, collect_p)
        case ("select")
            call eval_node_init_prt_fun_unary (en, en1, key, select_p)
        case ("extract")
            call eval_node_init_prt_fun_unary (en, en1, key, extract_p)
        case ("sort")
            call eval_node_init_prt_fun_unary (en, en1, key, sort_p)
        case default
            call msg_bug (" Unary particle function '" // char (key) // &
                "' undefined")
        end select
    end if
end subroutine eval_node_compile_prt_function

```

```

        end select
    else
        call eval_node_compile_pexpr (en2, pn_arg2, var_list)
        select case (char (key))
        case ("join")
            call eval_node_init_prt_fun_binary (en, en1, en2, key, join_pp)
        case ("combine")
            call eval_node_init_prt_fun_binary (en, en1, en2, key, combine_pp)
        case ("collect")
            call eval_node_init_prt_fun_binary (en, en1, en2, key, collect_pp)
        case ("select")
            call eval_node_init_prt_fun_binary (en, en1, en2, key, select_pp)
        case ("sort")
            call eval_node_init_prt_fun_binary (en, en1, en2, key, sort_pp)
        case default
            call msg_bug (" Binary particle function '" // char (key) // '&
                "' undefined")
        end select
    end if
    if (associated (pn_cond)) then
        call eval_node_set_observables (en, var_list)
        select case (char (key))
        case ("extract", "sort")
            call eval_node_compile_expr (en0, pn_arg0, en%var_list)
        case default
            call eval_node_compile_lexpr (en0, pn_arg0, en%var_list)
        end select
        en%arg0 => en0
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done prt_function"
    end if
end subroutine eval_node_compile_prt_function

```

The eval expression is similar, but here the expression `arg0` is mandatory, and the whole thing evaluates to a numeric value.

(Expressions: procedures) +=

```

recursive subroutine eval_node_compile_eval_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_key, pn_arg0, pn_args, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en0, en1, en2
    type(string_t) :: key
    if (debug) then
        print *, "read eval_function"; call parse_node_write (pn)
    end if
    pn_key => parse_node_get_sub_ptr (pn)
    pn_arg0 => parse_node_get_next_ptr (pn_key)
    pn_args => parse_node_get_next_ptr (pn_arg0)
    pn_arg1 => parse_node_get_sub_ptr (pn_args)
    pn_arg2 => parse_node_get_next_ptr (pn_arg1)

```

```

key = parse_node_get_key (pn_key)
call eval_node_compile_pexpr (en1, pn_arg1, var_list)
allocate (en)
if (.not. associated (pn_arg2)) then
    call eval_node_init_eval_fun_unary (en, en1, key)
else
    call eval_node_compile_pexpr (en2, pn_arg2, var_list)
    call eval_node_init_eval_fun_binary (en, en1, en2, key)
end if
call eval_node_set_observables (en, var_list)
call eval_node_compile_expr (en0, pn_arg0, en%var_list)
if (en0%result_type /= V_REAL) &
    call msg_fatal (" 'eval' function does not result in real value")
call eval_node_set_expr (en, en0)
if (debug) then
    call eval_node_write (en)
    print *, "done eval_function"
end if
end subroutine eval_node_compile_eval_function

```

Logical functions of subevents.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_log_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_key, pn_str
    type(parse_node_t), pointer :: pn_arg0, pn_args, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en0, en1, en2
    type(string_t) :: key
    if (debug) then
        print *, "read log_function"; call parse_node_write (pn)
    end if
    select case (char (parse_node_get_rule_key (pn)))
    case ("all_fun", "any_fun", "no_fun")
        pn_key => parse_node_get_sub_ptr (pn)
        pn_arg0 => parse_node_get_next_ptr (pn_key)
        pn_args => parse_node_get_next_ptr (pn_arg0)
    case ("user_cut_fun")
        pn_key => parse_node_get_sub_ptr (pn)
        pn_str => parse_node_get_next_ptr (pn_key)
        pn_arg0 => parse_node_get_sub_ptr (pn_str)
        pn_args => parse_node_get_next_ptr (pn_str)
    case default
        call parse_node_mismatch &
            ("all_fun|any_fun|no_fun|user_cut_fun", &
            pn)
    end select
    pn_arg1 => parse_node_get_sub_ptr (pn_args)
    pn_arg2 => parse_node_get_next_ptr (pn_arg1)
    key = parse_node_get_key (pn_key)
    call eval_node_compile_pexpr (en1, pn_arg1, var_list)
    allocate (en)
    if (.not. associated (pn_arg2)) then

```

```

select case (char (key))
case ("all")
    call eval_node_init_log_fun_unary (en, en1, key, all_p)
case ("any")
    call eval_node_init_log_fun_unary (en, en1, key, any_p)
case ("no")
    call eval_node_init_log_fun_unary (en, en1, key, no_p)
case ("user_cut")
    call eval_node_init_log_fun_unary (en, en1, key, user_cut_p)
case default
    call msg_bug ("Unary logical particle function '" // char (key) // &
        "' undefined")
end select
else
    call eval_node_compile_pexpr (en2, pn_arg2, var_list)
    select case (char (key))
    case ("all")
        call eval_node_init_log_fun_binary (en, en1, en2, key, all_pp)
    case ("any")
        call eval_node_init_log_fun_binary (en, en1, en2, key, any_pp)
    case ("no")
        call eval_node_init_log_fun_binary (en, en1, en2, key, no_pp)
    case default
        call msg_bug ("Binary logical particle function '" // char (key) // &
            "' undefined")
    end select
end if
if (associated (pn_arg0)) then
    call eval_node_set_observables (en, var_list)
    select case (char (key))
    case ("all", "any", "no")
        call eval_node_compile_lexpr (en0, pn_arg0, en%var_list)
    case ("user_cut")
        call eval_node_compile_sexpr (en0, pn_arg0, en%var_list)
    case default
        call msg_bug ("Compiling logical particle function: missing mode")
    end select
    call eval_node_set_expr (en, en0, V_LOG)
end if
if (debug) then
    call eval_node_write (en)
    print *, "done log_function"
end if
end subroutine eval_node_compile_log_function

```

Numeric functions of subevents.

(Expressions: procedures) +=

```

recursive subroutine eval_node_compile_numeric_function (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_clause, pn_key, pn_cond, pn_args
    type(parse_node_t), pointer :: pn_arg0, pn_arg1, pn_arg2
    type(eval_node_t), pointer :: en0, en1, en2

```

```

type(string_t) :: key
if (debug) then
    print *, "read numeric_function"; call parse_node_write (pn)
end if
select case (char (parse_node_get_rule_key (pn)))
case ("count_fun")
    pn_clause => parse_node_get_sub_ptr (pn)
    pn_key   => parse_node_get_sub_ptr (pn_clause)
    pn_cond  => parse_node_get_next_ptr (pn_key)
    if (associated (pn_cond)) then
        pn_arg0 => parse_node_get_sub_ptr (pn_cond, 2)
    else
        pn_arg0 => null ()
    end if
    pn_args => parse_node_get_next_ptr (pn_clause)
case ("user_event_fun")
    pn_key => parse_node_get_sub_ptr (pn)
    pn_cond => parse_node_get_next_ptr (pn_key)
    pn_arg0 => parse_node_get_sub_ptr (pn_cond)
    pn_args => parse_node_get_next_ptr (pn_cond)
end select
pn_arg1 => parse_node_get_sub_ptr (pn_args)
pn_arg2 => parse_node_get_next_ptr (pn_arg1)
key = parse_node_get_key (pn_key)
call eval_node_compile_pexpr (en1, pn_arg1, var_list)
allocate (en)
if (.not. associated (pn_arg2)) then
    select case (char (key))
    case ("count")
        call eval_node_init_int_fun_unary (en, en1, key, count_a)
    case ("user_event_shape")
        call eval_node_init_real_fun_unary (en, en1, key, user_event_shape_a)
    case default
        call msg_bug ("Unary subevent function '" // char (key) // &
                     "' undefined")
    end select
else
    call eval_node_compile_pexpr (en2, pn_arg2, var_list)
    select case (char (key))
    case ("count")
        call eval_node_init_int_fun_binary (en, en1, en2, key, count_pp)
    case default
        call msg_bug ("Binary subevent function '" // char (key) // &
                     "' undefined")
    end select
end if
if (associated (pn_arg0)) then
    call eval_node_set_observables (en, var_list)
    select case (char (key))
    case ("count")
        call eval_node_compile_lexpr (en0, pn_arg0, en%var_list)
        call eval_node_set_expr (en, en0, V_INT)
    case ("user_event_shape")
        call eval_node_compile_sexpr (en0, pn_arg0, en%var_list)

```



```

        call eval_node_set_expr (en, en0, V_REAL)
    end select
end if
if (debug) then
    call eval_node_write (en)
    print *, "done numeric_function"
end if
end subroutine eval_node_compile_numeric_function

```

PDG-code arrays

A PDG-code expression is either prefixed by incoming or outgoing, a block, or a conditional. In any case, it evaluates to a constant.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_prefix_cexpr (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_avalue, pn_prt
    type(string_t) :: key
    if (debug) then
        print *, "read prefix_cexpr"; call parse_node_write (pn)
    end if
    pn_avalue => parse_node_get_sub_ptr (pn)
    key = parse_node_get_rule_key (pn_avalue)
    select case (char (key))
    case ("incoming_prt")
        pn_prt => parse_node_get_sub_ptr (pn_avalue, 2)
        call eval_node_compile_cexpr (en, pn_prt, var_list)
    case ("outgoing_prt")
        pn_prt => parse_node_get_sub_ptr (pn_avalue, 1)
        call eval_node_compile_cexpr (en, pn_prt, var_list)
    case default
        call parse_node_mismatch &
            ("incoming_prt|outgoing_prt", &
            pn_avalue)
    end select
    if (debug) then
        call eval_node_write (en)
        print *, "done prefix_cexpr"
    end if
end subroutine eval_node_compile_prefix_cexpr

```

A PDG array is a string of PDG code definitions (or aliases), concatenated by '.'. The code definitions may be variables which are not defined at compile time, so we have to allocate sub-nodes. This analogous to `eval_node_compile_term`.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_cexpr (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_prt, pn_concatenation

```

```

type(eval_node_t), pointer :: en1, en2
type(pdg_array_t) :: aval
if (debug) then
    print *, "read cexpr"; call parse_node_write (pn)
end if
pn_prt => parse_node_get_sub_ptr (pn)
call eval_node_compile_avalue (en, pn_prt, var_list)
pn_concatenation => parse_node_get_next_ptr (pn_prt)
do while (associated (pn_concatenation))
    pn_prt => parse_node_get_sub_ptr (pn_concatenation, 2)
    en1 => en
    call eval_node_compile_avalue (en2, pn_prt, var_list)
    allocate (en)
    if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
        call concat_cc (aval, en1, en2)
        call eval_node_init_pdg_array (en, aval)
        call eval_node_final_rec (en1)
        call eval_node_final_rec (en2)
        deallocate (en1, en2)
    else
        call eval_node_init_branch (en, var_str (":"), V_PDG, en1, en2)
        call eval_node_set_op2_pdg (en, concat_cc)
    end if
    pn_concatenation => parse_node_get_next_ptr (pn_concatenation)
end do
if (debug) then
    call eval_node_write (en)
    print *, "done cexpr"
end if
end subroutine eval_node_compile_cexpr

```

Compile a PDG-code type value. It may be either an integer expression or a variable of type PDG array, optionally quoted.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_avalue (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    if (debug) then
        print *, "read avalue"; call parse_node_write (pn)
    end if
    select case (char (parse_node_get_rule_key (pn)))
    case ("pdg_code")
        call eval_node_compile_pdg_code (en, pn, var_list)
    case ("cvariable", "variable", "prt_name")
        call eval_node_compile_cvariable (en, pn, var_list)
    case ("cexpr")
        call eval_node_compile_cexpr (en, pn, var_list)
    case ("block_cexpr")
        call eval_node_compile_block_expr (en, pn, var_list, V_PDG)
    case ("conditional_cexpr")
        call eval_node_compile_conditional (en, pn, var_list, V_PDG)
    case default

```

```

        call parse_node_mismatch &
            ("grouped_cexpr|block_cexpr|conditional_cexpr|" // &
             "pdg_code|cvariable|prt_name", pn)
    end select
    if (debug) then
        call eval_node_write (en)
        print *, "done avalue"
    end if
end subroutine eval_node_compile_avalue

```

Compile a PDG-code expression, which is the key PDG with an integer expression as argument. The procedure is analogous to `eval_node_compile_unary_function`.

(Expressions: procedures)+≡

```

subroutine eval_node_compile_pdg_code (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in), target :: pn
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_arg
    type(eval_node_t), pointer :: en1
    type(string_t) :: key
    type(pdg_array_t) :: aval
    integer :: t
    if (debug) then
        print *, "read PDG code"; call parse_node_write (pn)
    end if
    pn_arg => parse_node_get_sub_ptr (pn, 2)
    call eval_node_compile_expr &
        (en1, parse_node_get_sub_ptr (pn_arg, tag="expr"), var_list)
    t = en1%result_type
    allocate (en)
    key = "PDG"
    if (en1%type == EN_CONSTANT) then
        select case (t)
            case (V_INT)
                call pdg_i (aval, en1)
                call eval_node_init_pdg_array (en, aval)
            case default; call eval_type_error (pn, char (key), t)
        end select
        call eval_node_final_rec (en1)
        deallocate (en1)
    else
        select case (t)
            case (V_INT); call eval_node_set_op1_pdg (en, pdg_i)
            case default; call eval_type_error (pn, char (key), t)
        end select
    end if
    if (debug) then
        call eval_node_write (en)
        print *, "done function"
    end if
end subroutine eval_node_compile_pdg_code

```

This is entirely analogous to `eval_node_compile_variable`. However, PDG-

array variables occur in different contexts.

To avoid name clashes between PDG-array variables and ordinary variables, we prepend a character (*). This is not visible to the user.

(Expressions: procedures) +≡

```

subroutine eval_node_compile_cvariable (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in), target :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_name
  type(string_t) :: var_name
  type(var_entry_t), pointer :: var
  type(pdg_array_t), target, save :: no_aval
  logical, target, save :: unknown = .false.
  if (debug) then
    print *, "read cvariable"; call parse_node_write (pn)
  end if
!   select case (char (parse_node_get_rule_key (pn)))
!     case ("cvariable"); pn_name => parse_node_get_sub_ptr (pn, 2)
!     case default;      pn_name => pn
!     end select
  pn_name => pn
  var_name = parse_node_get_string (pn_name)
  var => var_list_get_var_ptr (var_list, var_name, V_PDG, defined=.true.)
  allocate (en)
  if (associated (var)) then
    call eval_node_init_pdg_array_ptr &
      (en, var_entry_get_name (var), var_entry_get_aval_ptr (var), &
       var_entry_get_known_ptr (var))
  else
    call parse_node_write (pn)
    call msg_error ("This PDG-array variable is undefined at this point")
    call eval_node_init_pdg_array_ptr (en, var_name, no_aval, unknown)
  end if
  if (debug) then
    call eval_node_write (en)
    print *, "done cvariable"
  end if
end subroutine eval_node_compile_cvariable

```

String expressions

A string expression is either a string value or a concatenation of string values.

(Expressions: procedures) +≡

```

recursive subroutine eval_node_compile_sexpr (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_svalue, pn_concatenation, pn_op, pn_arg
  type(eval_node_t), pointer :: en1, en2
  type(string_t) :: string
  if (debug) then
    print *, "read sexpr"; call parse_node_write (pn)
  end if

```

```

end if
pn_svalue => parse_node_get_sub_ptr (pn)
call eval_node_compile_svalue (en, pn_svalue, var_list)
pn_concatenation => &
    parse_node_get_next_ptr (pn_svalue, tag="str_concatenation")
do while (associated (pn_concatenation))
    pn_op => parse_node_get_sub_ptr (pn_concatenation)
    pn_arg => parse_node_get_next_ptr (pn_op)
    en1 => en
    call eval_node_compile_svalue (en2, pn_arg, var_list)
    allocate (en)
    if (en1%type == EN_CONSTANT .and. en2%type == EN_CONSTANT) then
        call concat_ss (string, en1, en2)
        call eval_node_init_string (en, string)
        call eval_node_final_rec (en1)
        call eval_node_final_rec (en2)
        deallocate (en1, en2)
    else
        call eval_node_init_branch &
            (en, var_str ("concat"), V_STR, en1, en2)
        call eval_node_set_op2_str (en, concat_ss)
    end if
    pn_concatenation => parse_node_get_next_ptr (pn_concatenation)
end do
if (debug) then
    call eval_node_write (en)
    print *, "done sexpr"
end if
end subroutine eval_node_compile_sexpr

```

A string value is a string literal, a variable, a (grouped) sexpr, a block sexpr, or a conditional.

(*Expressions: procedures*) +=

```

recursive subroutine eval_node_compile_svalue (en, pn, var_list)
    type(eval_node_t), pointer :: en
    type(parse_node_t), intent(in) :: pn
    type(var_list_t), intent(in), target :: var_list
    if (debug) then
        print *, "read svalue"; call parse_node_write (pn)
    end if
    select case (char (parse_node_get_rule_key (pn)))
    case ("svariable")
        call eval_node_compile_variable (en, pn, var_list, V_STR)
    case ("sexpr")
        call eval_node_compile_sexpr (en, pn, var_list)
    case ("block_sexpr")
        call eval_node_compile_block_expr (en, pn, var_list, V_STR)
    case ("conditional_sexpr")
        call eval_node_compile_conditional (en, pn, var_list, V_STR)
    case ("sprintf_fun")
        call eval_node_compile_sprintf (en, pn, var_list)
    case ("sprintfd_fun")
        call eval_node_compile_sprintfd (en, pn, var_list)

```

```

case ("string_literal")
  allocate (en)
  call eval_node_init_string (en, parse_node_get_string (pn))
case default
  call parse_node_mismatch &
    ("svariable|" // &
      "grouped_sexpr|block_sexpr|conditional_sexpr|" // &
      "string_function|string_literal", pn)
end select
if (debug) then
  call eval_node_write (en)
  print *, "done svalue"
end if
end subroutine eval_node_compile_svalue

```

There are currently one string function, `sprintf` and `sprintfd`. For `sprintf`, The first argument (no brackets) is the format string, the optional arguments in brackets are the expressions or variables to be formatted.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_sprintf (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_clause, pn_key, pn_args
  type(parse_node_t), pointer :: pn_arg0
  type(eval_node_t), pointer :: en0, en1
  integer :: n_args
  type(string_t) :: key
  if (debug) then
    print *, "read sprintf_fun"; call parse_node_write (pn)
  end if
  pn_clause => parse_node_get_sub_ptr (pn)
  pn_key => parse_node_get_sub_ptr (pn_clause)
  pn_arg0 => parse_node_get_next_ptr (pn_key)
  pn_args => parse_node_get_next_ptr (pn_clause)
  call eval_node_compile_sexpr (en0, pn_arg0, var_list)
  if (associated (pn_args)) then
    call eval_node_compile_sprintf_args (en1, pn_args, var_list, n_args)
  else
    n_args = 0
    en1 => null ()
  end if
  allocate (en)
  key = parse_node_get_key (pn_key)
  call eval_node_init_format_string (en, en0, en1, key, n_args)
  if (debug) then
    call eval_node_write (en)
    print *, "done sprintf_fun"
  end if
end subroutine eval_node_compile_sprintf

```

`sprintfd` is similar, just the format string is missing.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_compile_sprintf (en, pn, var_list)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  type(parse_node_t), pointer :: pn_key, pn_args
  type(eval_node_t), pointer :: en1
  integer :: n_args
  type(string_t) :: key
  if (debug) then
    print *, "read sprintf_fun"; call parse_node_write (pn)
  end if
  pn_key => parse_node_get_sub_ptr (pn)
  pn_args => parse_node_get_next_ptr (pn_key)
  if (associated (pn_args)) then
    call eval_node_compile_sprintf_args (en1, pn_args, var_list, n_args)
  else
    n_args = 0
    en1 => null ()
  end if
  allocate (en)
  key = parse_node_get_key (pn_key)
  call eval_node_init_format_string (en, null (), en1, key, n_args)
  if (debug) then
    call eval_node_write (en)
    print *, "done sprintf_fun"
  end if
end subroutine eval_node_compile_sprintf

```

(Expressions: procedures)+≡

```

subroutine eval_node_compile_sprintf_args (en, pn, var_list, n_args)
  type(eval_node_t), pointer :: en
  type(parse_node_t), intent(in) :: pn
  type(var_list_t), intent(in), target :: var_list
  integer, intent(out) :: n_args
  type(parse_node_t), pointer :: pn_arg
  integer :: i
  type(eval_node_t), pointer :: en1, en2
  n_args = parse_node_get_n_sub (pn)
  en => null ()
  do i = n_args, 1, -1
    pn_arg => parse_node_get_sub_ptr (pn, i)
    select case (char (parse_node_get_rule_key (pn_arg)))
      case ("lvariable")
        call eval_node_compile_variable (en1, pn_arg, var_list, V_LOG)
      case ("svariable")
        call eval_node_compile_variable (en1, pn_arg, var_list, V_STR)
      case ("expr")
        call eval_node_compile_expr (en1, pn_arg, var_list)
      case default
        call parse_node_mismatch ("variable|svariable|lvariable|expr", pn_arg)
    end select
    if (associated (en)) then
      en2 => en
      allocate (en)
    end if
  end do
end subroutine eval_node_compile_sprintf_args

```

```

        call eval_node_init_branch &
            (en, var_str ("sprintf_arg"), V_NONE, en1, en2)
    else
        allocate (en)
        call eval_node_init_branch &
            (en, var_str ("sprintf_arg"), V_NONE, en1)
    end if
end do
end subroutine eval_node_compile_sprintf_args

```

Evaluation. We allocate the argument list and apply the Fortran wrapper for the `sprintf` function. In the `sprintfd` case, build a format string appropriate for the argument types.

(*Expressions: procedures*) \vdash

```

subroutine evaluate_sprintf (string, n_args, en_fmt, en_arg)
    type(string_t), intent(out) :: string
    integer, intent(in) :: n_args
    type(eval_node_t), pointer :: en_fmt
    type(eval_node_t), intent(in), optional, target :: en_arg
    type(eval_node_t), pointer :: en_branch, en_var
    type(sprintf_arg_t), dimension(:), allocatable :: arg
    type(string_t) :: fmt
    logical :: autoformat
    integer :: i, j, sprintf_argc
    autoformat = .not. associated (en_fmt)
    if (autoformat) fmt = ""
    if (present (en_arg)) then
        sprintf_argc = 0
        en_branch => en_arg
        do i = 1, n_args
            select case (en_branch%arg1%result_type)
                case (V_CMPLX); sprintf_argc = sprintf_argc + 2
                case default ; sprintf_argc = sprintf_argc + 1
            end select
            en_branch => en_branch%arg2
        end do
        allocate (arg (sprintf_argc))
        j = 1
        en_branch => en_arg
        do i = 1, n_args
            en_var => en_branch%arg1
            select case (en_var%result_type)
                case (V_LOG)
                    call sprintf_arg_init (arg(j), en_var%lval)
                    if (autoformat) fmt = fmt // "%s "
                case (V_INT);
                    call sprintf_arg_init (arg(j), en_var%ival)
                    if (autoformat) fmt = fmt // "%i "
                case (V_REAL);
                    call sprintf_arg_init (arg(j), en_var%rval)
                    if (autoformat) fmt = fmt // "%g "
                case (V_STR)
                    call sprintf_arg_init (arg(j), en_var%sval)

```



```

        if (autoformat) fmt = fmt // "%s "
    case (V_CMPLX)
        call sprintf_arg_init (arg(j), real (en_var%cval, default))
        j = j + 1
        call sprintf_arg_init (arg(j), aimag (en_var%cval))
        if (autoformat) fmt = fmt // "(%g + %g * I) "
    case default
        call eval_node_write (en_var)
        call msg_error ("sprintf is implemented " &
            // "for logical, integer, real, and string values only")
    end select
    j = j + 1
    en_branch => en_branch%arg2
end do
else
    allocate (arg(0))
end if
if (autoformat) then
    string = sprintf (trim (fmt), arg)
else
    string = sprintf (en_fmt%sval, arg)
end if
end subroutine evaluate_sprintf

```

5.6.5 Auxiliary functions for the compiler

Issue an error that the current node could not be compiled because of type mismatch:

```

<Expressions: procedures>+≡
subroutine eval_type_error (pn, string, t)
    type(parse_node_t), intent(in) :: pn
    character(*), intent(in) :: string
    integer, intent(in) :: t
    type(string_t) :: type
    select case (t)
    case (V_NONE); type = "(none)"
    case (V_LOG); type = "'logical'"
    case (V_INT); type = "'integer'"
    case (V_REAL); type = "'real'"
    case (V_CMPLX); type = "'complex'"
    case default; type = "(unknown)"
    end select
    call parse_node_write (pn)
    call msg_fatal (" The " // string // &
        " operation is not defined for the given argument type " // &
        char (type))
end subroutine eval_type_error

```

If two numerics are combined, the result is integer if both arguments are integer, if one is integer and the other real or both are real, than its argument is real, otherwise complex.

```

<Expressions: procedures>+≡

```

```

function numeric_result_type (t1, t2) result (t)
  integer, intent(in) :: t1, t2
  integer :: t
  if (t1 == V_INT .and. t2 == V_INT) then
    t = V_INT
  else if (t1 == V_INT .and. t2 == V_REAL) then
    t = V_REAL
  else if (t1 == V_REAL .and. t2 == V_INT) then
    t = V_REAL
  else if (t1 == V_REAL .and. t2 == V_REAL) then
    t = V_REAL
  else
    t = V_CMPLX
  end if
end function numeric_result_type

```

5.6.6 Evaluation

Evaluation is done recursively. For leaf nodes nothing is to be done.

Evaluating particle-list functions: First, we evaluate the particle lists. If a condition is present, we assign the particle pointers of the condition node to the allocated particle entries in the parent node, keeping in mind that the observables in the variable stack used for the evaluation of the condition also contain pointers to these entries. Then, the assigned procedure is evaluated, which sets the subevent in the parent node. If required, the procedure evaluates the condition node once for each (pair of) particles to determine the result.

(Expressions: procedures)+≡

```

recursive subroutine eval_node_evaluate (en)
  type(eval_node_t), intent(inout) :: en
  logical :: exist
  select case (en%type)
  case (EN_UNARY)
    if (associated (en%arg1)) then
      call eval_node_evaluate (en%arg1)
      en%value_is_known = en%arg1%value_is_known
    else
      en%value_is_known = .false.
    end if
  if (en%value_is_known) then
    select case (en%result_type)
    case (V_LOG); en%lval = en% op1_log (en%arg1)
    case (V_INT); en%ival = en% op1_int (en%arg1)
    case (V_REAL); en%rval = en% op1_real (en%arg1)
    case (V_CMPLX); en%cval = en% op1_cmplx (en%arg1)
    case (V_PDG);
      call en% op1_pdg (en%aval, en%arg1)
    case (V_SEV)
      if (associated (en%arg0)) then
        call en% op1_sev (en%pval, en%arg1, en%arg0)
      else
        call en% op1_sev (en%pval, en%arg1)
      end if
    end select
  end if
end subroutine eval_node_evaluate

```

```

        case (V_STR)
            call en% op1_str (en%sval, en%arg1)
        end select
    end if
case (EN_BINARY)
    if (associated (en%arg1) .and. associated (en%arg2)) then
        call eval_node_evaluate (en%arg1)
        call eval_node_evaluate (en%arg2)
        en%value_is_known = &
            en%arg1%value_is_known .and. en%arg2%value_is_known
    else
        en%value_is_known = .false.
    end if
    if (en%value_is_known) then
        select case (en%result_type)
            case (V_LOG); en%lval = en% op2_log (en%arg1, en%arg2)
            case (V_INT); en%ival = en% op2_int (en%arg1, en%arg2)
            case (V_REAL); en%rval = en% op2_real (en%arg1, en%arg2)
            case (V_CMPLX); en%cval = en% op2_cmplx (en%arg1, en%arg2)
            case (V_PDG)
                call en% op2_pdg (en%aval, en%arg1, en%arg2)
            case (V_SEV)
                if (associated (en%arg0)) then
                    call en% op2_sev (en%pval, en%arg1, en%arg2, en%arg0)
                else
                    call en% op2_sev (en%pval, en%arg1, en%arg2)
                end if
            case (V_STR)
                call en% op2_str (en%sval, en%arg1, en%arg2)
            end select
        end if
case (EN_BLOCK)
    if (associated (en%arg1) .and. associated (en%arg0)) then
        call eval_node_evaluate (en%arg1)
        call eval_node_evaluate (en%arg0)
        en%value_is_known = en%arg0%value_is_known
    else
        en%value_is_known = .false.
    end if
    if (en%value_is_known) then
        select case (en%result_type)
            case (V_LOG); en%lval = en%arg0%lval
            case (V_INT); en%ival = en%arg0%ival
            case (V_REAL); en%rval = en%arg0%rval
            case (V_CMPLX); en%cval = en%arg0%cval
            case (V_PDG); en%aval = en%arg0%aval
            case (V_SEV); en%pval = en%arg0%pval
            case (V_STR); en%sval = en%arg0%sval
            end select
        end if
case (EN_CONDITIONAL)
    if (associated (en%arg0)) then
        call eval_node_evaluate (en%arg0)
        en%value_is_known = en%arg0%value_is_known
    end if

```

```

else
    en%value_is_known = .false.
end if
if (en%arg0%value_is_known) then
    if (en%arg0%lval) then
        call eval_node_evaluate (en%arg1)
        en%value_is_known = en%arg1%value_is_known
        if (en%value_is_known) then
            select case (en%result_type)
            case (V_LOG); en%lval = en%arg1%lval
            case (V_INT); en%ival = en%arg1%ival
            case (V_REAL); en%rval = en%arg1%rval
            case (V_CMPLX); en%cval = en%arg1%cval
            case (V_PDG); en%aval = en%arg1%aval
            case (V_SEV); en%pval = en%arg1%pval
            case (V_STR); en%sval = en%arg1%sval
            end select
        end if
    else
        call eval_node_evaluate (en%arg2)
        en%value_is_known = en%arg2%value_is_known
        if (en%value_is_known) then
            select case (en%result_type)
            case (V_LOG); en%lval = en%arg2%lval
            case (V_INT); en%ival = en%arg2%ival
            case (V_REAL); en%rval = en%arg2%rval
            case (V_CMPLX); en%cval = en%arg2%cval
            case (V_PDG); en%aval = en%arg2%aval
            case (V_SEV); en%pval = en%arg2%pval
            case (V_STR); en%sval = en%arg2%sval
            end select
        end if
    end if
end if
! call eval_node_write_rec (en)
case (EN_RECORD_CMD)
    exist = .true.
    en%lval = .false.
    call eval_node_evaluate (en%arg0)
    if (en%arg0%value_is_known) then
        if (associated (en%arg1)) then
            call eval_node_evaluate (en%arg1)
            if (en%arg1%value_is_known) then
                if (associated (en%arg2)) then
                    call eval_node_evaluate (en%arg2)
                    if (en%arg2%value_is_known) then
                        if (associated (en%arg3)) then
                            call eval_node_evaluate (en%arg3)
                            if (en%arg3%value_is_known) then
                                if (associated (en%arg4)) then
                                    call eval_node_evaluate (en%arg4)
                                    if (en%arg4%value_is_known) then
                                        if (associated (en%rval)) then
                                            call analysis_record_data (en%arg0%sval, &

```

```

        en%arg1%rval, en%arg2%rval, &
        en%arg3%rval, en%arg4%rval, &
        weight=en%rval, exist=exist, &
        success=en%lval)
    else
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, en%arg2%rval, &
            en%arg3%rval, en%arg4%rval, &
            exist=exist, success=en%lval)
    end if
end if
else
    if (associated (en%rval)) then
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, en%arg2%rval, &
            en%arg3%rval, &
            weight=en%rval, exist=exist, &
            success=en%lval)
    else
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, en%arg2%rval, &
            en%arg3%rval, &
            exist=exist, success=en%lval)
    end if
end if
end if
else
    if (associated (en%rval)) then
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, en%arg2%rval, &
            weight=en%rval, exist=exist, &
            success=en%lval)
    else
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, en%arg2%rval, &
            exist=exist, success=en%lval)
    end if
end if
end if
else
    if (associated (en%rval)) then
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, &
            weight=en%rval, exist=exist, success=en%lval)
    else
        call analysis_record_data (en%arg0%sval, &
            en%arg1%rval, &
            exist=exist, success=en%lval)
    end if
end if
end if
else
    if (associated (en%rval)) then
        call analysis_record_data (en%arg0%sval, 1._default, &

```

```

        weight=en%rval, exist=exist, success=en%lval)
    else
        call analysis_record_data (en%arg0%sval, 1._default, &
            exist=exist, success=en%lval)
    end if
end if
if (.not. exist) then
    call msg_error ("Analysis object '" // char (en%arg0%sval) &
        // "' is undefined")
    en%arg0%value_is_known = .false.
end if
end if
case (EN_OBS1_INT)
    en%ival = en% obs1_int (en%prt1)
    en%value_is_known = .true.
case (EN_OBS2_INT)
    en%ival = en% obs2_int (en%prt1, en%prt2)
    en%value_is_known = .true.
case (EN_OBS1_REAL)
    en%rval = en% obs1_real (en%prt1)
    en%value_is_known = .true.
case (EN_OBS2_REAL)
    en%rval = en% obs2_real (en%prt1, en%prt2)
    en%value_is_known = .true.
case (EN_UOBS1_INT)
    en%ival = user_obs_int_p (en%arg0, en%prt1)
    en%value_is_known = .true.
case (EN_UOBS2_INT)
    en%ival = user_obs_int_pp (en%arg0, en%prt1, en%prt2)
    en%value_is_known = .true.
case (EN_UOBS1_REAL)
    en%rval = user_obs_real_p (en%arg0, en%prt1)
    en%value_is_known = .true.
case (EN_UOBS2_REAL)
    en%rval = user_obs_real_pp (en%arg0, en%prt1, en%prt2)
    en%value_is_known = .true.
case (EN_PRT_FUN_UNARY)
    call eval_node_evaluate (en%arg1)
    en%value_is_known = en%arg1%value_is_known
    if (en%value_is_known) then
        if (associated (en%arg0)) then
            en%arg0%index => en%index
            en%arg0%prt1 => en%prt1
            call en% op1_sev (en%pval, en%arg1, en%arg0)
        else
            call en% op1_sev (en%pval, en%arg1)
        end if
    end if
case (EN_PRT_FUN_BINARY)
    call eval_node_evaluate (en%arg1)
    call eval_node_evaluate (en%arg2)
    en%value_is_known = &
        en%arg1%value_is_known .and. en%arg2%value_is_known
    if (en%value_is_known) then

```

```

        if (associated (en%arg0)) then
            en%arg0%index => en%index
            en%arg0%prt1 => en%prt1
            en%arg0%prt2 => en%prt2
            call en% op2_sev (en%pval, en%arg1, en%arg2, en%arg0)
        else
            call en% op2_sev (en%pval, en%arg1, en%arg2)
        end if
    end if
case (EN_EVAL_FUN_UNARY)
    call eval_node_evaluate (en%arg1)
    en%value_is_known = subevt_is_nonempty (en%arg1%pval)
    if (en%value_is_known) then
        en%arg0%index => en%index
        en%index = 1
        en%arg0%prt1 => en%prt1
        en%prt1 = subevt_get_prt (en%arg1%pval, 1)
        call eval_node_evaluate (en%arg0)
        en%rval = en%arg0%rval
    end if
case (EN_EVAL_FUN_BINARY)
    call eval_node_evaluate (en%arg1)
    call eval_node_evaluate (en%arg2)
    en%value_is_known = &
        subevt_is_nonempty (en%arg1%pval) .and. &
        subevt_is_nonempty (en%arg2%pval)
    if (en%value_is_known) then
        en%arg0%index => en%index
        en%arg0%prt1 => en%prt1
        en%arg0%prt2 => en%prt2
        en%index = 1
        en%prt1 = subevt_get_prt (en%arg1%pval, 1)
        en%prt2 = subevt_get_prt (en%arg2%pval, 1)
        call eval_node_evaluate (en%arg0)
        en%rval = en%arg0%rval
    end if
case (EN_LOG_FUN_UNARY)
    call eval_node_evaluate (en%arg1)
    en%value_is_known = .true.
    if (en%value_is_known) then
        en%arg0%index => en%index
        en%arg0%prt1 => en%prt1
        en%lval = en% op1_cut (en%arg1, en%arg0)
    end if
case (EN_LOG_FUN_BINARY)
    call eval_node_evaluate (en%arg1)
    call eval_node_evaluate (en%arg2)
    en%value_is_known = .true.
    if (en%value_is_known) then
        en%arg0%index => en%index
        en%arg0%prt1 => en%prt1
        en%arg0%prt2 => en%prt2
        en%lval = en% op2_cut (en%arg1, en%arg2, en%arg0)
    end if
end if

```

```

case (EN_INT_FUN_UNARY)
  call eval_node_evaluate (en%arg1)
  en%value_is_known = en%arg1%value_is_known
  if (en%value_is_known) then
    if (associated (en%arg0)) then
      en%arg0%index => en%index
      en%arg0%prt1 => en%prt1
      call en% op1_evi (en%ival, en%arg1, en%arg0)
    else
      call en% op1_evi (en%ival, en%arg1)
    end if
  end if
case (EN_INT_FUN_BINARY)
  call eval_node_evaluate (en%arg1)
  call eval_node_evaluate (en%arg2)
  en%value_is_known = &
    en%arg1%value_is_known .and. &
    en%arg2%value_is_known
  if (en%value_is_known) then
    if (associated (en%arg0)) then
      en%arg0%index => en%index
      en%arg0%prt1 => en%prt1
      en%arg0%prt2 => en%prt2
      call en% op2_evi (en%ival, en%arg1, en%arg2, en%arg0)
    else
      call en% op2_evi (en%ival, en%arg1, en%arg2)
    end if
  end if
case (EN_REAL_FUN_UNARY)
  call eval_node_evaluate (en%arg1)
  en%value_is_known = en%arg1%value_is_known
  if (en%value_is_known) then
    if (associated (en%arg0)) then
      en%arg0%index => en%index
      en%arg0%prt1 => en%prt1
      call en% op1_evr (en%rval, en%arg1, en%arg0)
    else
      call en% op1_evr (en%rval, en%arg1)
    end if
  end if
case (EN_REAL_FUN_BINARY)
  call eval_node_evaluate (en%arg1)
  call eval_node_evaluate (en%arg2)
  en%value_is_known = &
    en%arg1%value_is_known .and. &
    en%arg2%value_is_known
  if (en%value_is_known) then
    if (associated (en%arg0)) then
      en%arg0%index => en%index
      en%arg0%prt1 => en%prt1
      en%arg0%prt2 => en%prt2
      call en% op2_evr (en%rval, en%arg1, en%arg2, en%arg0)
    else
      call en% op2_evr (en%rval, en%arg1, en%arg2)
    end if
  end if

```



```

        end if
    end if
case (EN_FORMAT_STR)
    if (associated (en%arg0)) then
        call eval_node_evaluate (en%arg0)
        en%value_is_known = en%arg0%value_is_known
    else
        en%value_is_known = .true.
    end if
    if (associated (en%arg1)) then
        call eval_node_evaluate (en%arg1)
        en%value_is_known = &
            en%value_is_known .and. en%arg1%value_is_known
        if (en%value_is_known) then
            call evaluate_sprintf (en%sval, en%ival, en%arg0, en%arg1)
        end if
    else
        if (en%value_is_known) then
            call evaluate_sprintf (en%sval, en%ival, en%arg0)
        end if
    end if
end select
if (debug) then
    print *, "evaluated"
    call eval_node_write (en)
end if
end subroutine eval_node_evaluate

```

5.6.7 Evaluation syntax

We have two different flavors of the syntax: with and without particles.

(Expressions: variables) +≡
 type(syntax_t), target, save :: syntax_expr
 type(syntax_t), target, save :: syntax_pexpr

These are for testing only and may be removed:

(Expressions: public) ≡
 public :: syntax_expr_init
 public :: syntax_pexpr_init

(Expressions: procedures) +≡
 subroutine syntax_expr_init ()
 type(ifile_t) :: ifile
 call define_expr_syntax (ifile, particles=.false., analysis=.false.)
 call syntax_init (syntax_expr, ifile)
 call ifile_final (ifile)
 end subroutine syntax_expr_init

subroutine syntax_pexpr_init ()
 type(ifile_t) :: ifile
 call define_expr_syntax (ifile, particles=.true., analysis=.false.)
 call syntax_init (syntax_pexpr, ifile)

```

        call ifile_final (ifile)
    end subroutine syntax_pexpr_init

    <Expressions: public>+≡
        public :: syntax_expr_final
        public :: syntax_pexpr_final

    <Expressions: procedures>+≡
        subroutine syntax_expr_final ()
            call syntax_final (syntax_expr)
        end subroutine syntax_expr_final

        subroutine syntax_pexpr_final ()
            call syntax_final (syntax_pexpr)
        end subroutine syntax_pexpr_final

    <Expressions: public>+≡
        public :: syntax_pexpr_write

    <Expressions: procedures>+≡
        subroutine syntax_pexpr_write (unit)
            integer, intent(in), optional :: unit
            call syntax_write (syntax_pexpr, unit)
        end subroutine syntax_pexpr_write

    <Expressions: public>+≡
        public :: define_expr_syntax

Numeric expressions.

    <Expressions: procedures>+≡
        subroutine define_expr_syntax (ifile, particles, analysis)
            type(ifile_t), intent(inout) :: ifile
            logical, intent(in) :: particles, analysis
            type(string_t) :: numeric_pexpr
            type(string_t) :: var_plist, var_alias
            if (particles) then
                numeric_pexpr = " | numeric_pexpr"
                var_plist = " | var_plist"
                var_alias = " | var_alias"
            else
                numeric_pexpr = ""
                var_plist = ""
                var_alias = ""
            end if
            call ifile_append (ifile, "SEQ expr = subexpr addition*")
            call ifile_append (ifile, "ALT subexpr = addition | term")
            call ifile_append (ifile, "SEQ addition = plus_or_minus term")
            call ifile_append (ifile, "SEQ term = factor multiplication*")
            call ifile_append (ifile, "SEQ multiplication = times_or_over factor")
            call ifile_append (ifile, "SEQ factor = value exponentiation?")
            call ifile_append (ifile, "SEQ exponentiation = to_the value")
            call ifile_append (ifile, "ALT plus_or_minus = '+' | '-'")
            call ifile_append (ifile, "ALT times_or_over = '*' | '/'")
            call ifile_append (ifile, "ALT to_the = '^' | '**")

```

```

call ifile_append (ifile, "KEY '+'")
call ifile_append (ifile, "KEY '-'")
call ifile_append (ifile, "KEY '*'")
call ifile_append (ifile, "KEY '/'")
call ifile_append (ifile, "KEY '^'")
call ifile_append (ifile, "KEY '**'")
call ifile_append (ifile, "ALT value = signed_value | unsigned_value")
call ifile_append (ifile, "SEQ signed_value = '-' unsigned_value")
call ifile_append (ifile, "ALT unsigned_value = " // &
    "numeric_value | constant | variable | " // &
    "result | user_observable | " // &
    "grouped_expr | block_expr | conditional_expr | " // &
    "unary_function | binary_function" // &
    numeric_pexpr)
call ifile_append (ifile, "ALT numeric_value = integer_value | " &
    // "real_value | complex_value")
call ifile_append (ifile, "SEQ integer_value = integer_literal unit_expr?")
call ifile_append (ifile, "SEQ real_value = real_literal unit_expr?")
call ifile_append (ifile, "SEQ complex_value = complex_literal unit_expr?")
call ifile_append (ifile, "INT integer_literal")
call ifile_append (ifile, "REA real_literal")
call ifile_append (ifile, "COM complex_literal")
call ifile_append (ifile, "SEQ unit_expr = unit unit_power?")
call ifile_append (ifile, "ALT unit = " // &
    "TeV | GeV | MeV | keV | eV | meV | " // &
    "nbarn | pbarn | fbarn | abarn | " // &
    "rad | mrad | degree | '%')")
call ifile_append (ifile, "KEY TeV")
call ifile_append (ifile, "KEY GeV")
call ifile_append (ifile, "KEY MeV")
call ifile_append (ifile, "KEY keV")
call ifile_append (ifile, "KEY eV")
call ifile_append (ifile, "KEY meV")
call ifile_append (ifile, "KEY nbarn")
call ifile_append (ifile, "KEY pbarn")
call ifile_append (ifile, "KEY fbarn")
call ifile_append (ifile, "KEY abarn")
call ifile_append (ifile, "KEY rad")
call ifile_append (ifile, "KEY mrad")
call ifile_append (ifile, "KEY degree")
call ifile_append (ifile, "KEY '%')")
call ifile_append (ifile, "SEQ unit_power = '^' frac_expr")
call ifile_append (ifile, "ALT frac_expr = frac | grouped_frac")
call ifile_append (ifile, "GRO grouped_frac = ( frac_expr )")
call ifile_append (ifile, "SEQ frac = signed_int div?")
call ifile_append (ifile, "ALT signed_int = " &
    // "neg_int | pos_int | integer_literal")
call ifile_append (ifile, "SEQ neg_int = '-' integer_literal")
call ifile_append (ifile, "SEQ pos_int = '+' integer_literal")
call ifile_append (ifile, "SEQ div = '/' integer_literal")
call ifile_append (ifile, "ALT constant = pi | I")
call ifile_append (ifile, "KEY pi")
call ifile_append (ifile, "KEY I")
call ifile_append (ifile, "IDE variable")

```

```

call ifile_append (ifile, "SEQ result = result_key result_arg")
call ifile_append (ifile, "ALT result_key = " // &
    "num_id | n_calls | integral | error | accuracy | efficiency | chi2")
call ifile_append (ifile, "SEQ user_observable = user_obs user_arg")
call ifile_append (ifile, "KEY user_obs")
call ifile_append (ifile, "ARG user_arg = ( sexpr )")
call ifile_append (ifile, "KEY num_id")
call ifile_append (ifile, "KEY n_calls")
call ifile_append (ifile, "KEY integral")
call ifile_append (ifile, "KEY error")
call ifile_append (ifile, "KEY accuracy")
call ifile_append (ifile, "KEY efficiency")
call ifile_append (ifile, "KEY chi2")
call ifile_append (ifile, "GRO result_arg = ( process_id )")
call ifile_append (ifile, "IDE process_id")
call ifile_append (ifile, "SEQ unary_function = fun_unary function_arg1")
call ifile_append (ifile, "SEQ binary_function = fun_binary function_arg2")
call ifile_append (ifile, "ALT fun_unary = " // &
    "complex | real | int | nint | floor | ceiling | abs | sgn | " // &
    "sqrt | exp | log | log10 | " // &
    "sin | cos | tan | asin | acos | atan | " // &
    "sinh | cosh | tanh")
call ifile_append (ifile, "KEY complex")
call ifile_append (ifile, "KEY real")
call ifile_append (ifile, "KEY int")
call ifile_append (ifile, "KEY nint")
call ifile_append (ifile, "KEY floor")
call ifile_append (ifile, "KEY ceiling")
call ifile_append (ifile, "KEY abs")
call ifile_append (ifile, "KEY sgn")
call ifile_append (ifile, "KEY sqrt")
call ifile_append (ifile, "KEY exp")
call ifile_append (ifile, "KEY log")
call ifile_append (ifile, "KEY log10")
call ifile_append (ifile, "KEY sin")
call ifile_append (ifile, "KEY cos")
call ifile_append (ifile, "KEY tan")
call ifile_append (ifile, "KEY asin")
call ifile_append (ifile, "KEY acos")
call ifile_append (ifile, "KEY atan")
call ifile_append (ifile, "KEY sinh")
call ifile_append (ifile, "KEY cosh")
call ifile_append (ifile, "KEY tanh")
call ifile_append (ifile, "ALT fun_binary = max | min | mod | modulo")
call ifile_append (ifile, "KEY max")
call ifile_append (ifile, "KEY min")
call ifile_append (ifile, "KEY mod")
call ifile_append (ifile, "KEY modulo")
call ifile_append (ifile, "ARG function_arg1 = ( expr )")
call ifile_append (ifile, "ARG function_arg2 = ( expr, expr )")
call ifile_append (ifile, "GRO grouped_expr = ( expr )")
call ifile_append (ifile, "SEQ block_expr = let var_spec in expr")
call ifile_append (ifile, "KEY let")
call ifile_append (ifile, "ALT var_spec = " // &

```

```

        "var_num | var_int | var_real | var_complex | " // &
        "var_logical" // var_plist // var_alias // " | var_string")
call ifile_append (ifile, "SEQ var_num = var_name '=' expr")
call ifile_append (ifile, "SEQ var_int = int var_name '=' expr")
call ifile_append (ifile, "SEQ var_real = real var_name '=' expr")
call ifile_append (ifile, "SEQ var_complex = complex var_name '=' complex_expr")
call ifile_append (ifile, "ALT complex_expr = " // &
        "cexpr_real | cexpr_complex")
call ifile_append (ifile, "ARG cexpr_complex = ( expr, expr )")
call ifile_append (ifile, "SEQ cexpr_real = expr")
call ifile_append (ifile, "IDE var_name")
call ifile_append (ifile, "KEY '='")
call ifile_append (ifile, "KEY in")
call ifile_append (ifile, "SEQ conditional_expr = " // &
        "if lexpr then expr maybe_elseif_expr maybe_else_expr endif")
call ifile_append (ifile, "SEQ maybe_elseif_expr = elseif_expr*")
call ifile_append (ifile, "SEQ maybe_else_expr = else_expr?")
call ifile_append (ifile, "SEQ elseif_expr = elseif lexpr then expr")
call ifile_append (ifile, "SEQ else_expr = else expr")
call ifile_append (ifile, "KEY if")
call ifile_append (ifile, "KEY then")
call ifile_append (ifile, "KEY elseif")
call ifile_append (ifile, "KEY else")
call ifile_append (ifile, "KEY endif")
call define_lexpr_syntax (ifile, particles, analysis)
call define_sexpr_syntax (ifile)
if (particles) then
    call define_pexpr_syntax (ifile)
    call define_cexpr_syntax (ifile)
    call define_var_plist_syntax (ifile)
    call define_var_alias_syntax (ifile)
    call define_numeric_pexpr_syntax (ifile)
    call define_logical_pexpr_syntax (ifile)
end if

end subroutine define_expr_syntax

```

Logical expressions.

(Expressions: procedures)+≡

```

subroutine define_lexpr_syntax (ifile, particles, analysis)
type(ifile_t), intent(inout) :: ifile
logical, intent(in) :: particles, analysis
type(string_t) :: logical_pexpr, record_cmd
if (particles) then
    logical_pexpr = " | logical_pexpr"
else
    logical_pexpr = ""
end if
if (analysis) then
    record_cmd = " | record_cmd"
else
    record_cmd = ""
end if
call ifile_append (ifile, "SEQ lexpr = lsinglet lsequel*")

```

```

call ifile_append (ifile, "SEQ lsequel = ';' lsinglet")
call ifile_append (ifile, "SEQ lsinglet = lterm alternative*")
call ifile_append (ifile, "SEQ alternative = or lterm")
call ifile_append (ifile, "SEQ lterm = lvalue coincidence*")
call ifile_append (ifile, "SEQ coincidence = and lvalue")
call ifile_append (ifile, "KEY ';'")
call ifile_append (ifile, "KEY or")
call ifile_append (ifile, "KEY and")
call ifile_append (ifile, "ALT lvalue = " // &
    "true | false | lvariable | negation | " // &
    "grouped_lexpr | block_lexpr | conditional_lexpr | " // &
    "compared_expr | compared_sexpr" // &
    logical_pexpr // record_cmd)
call ifile_append (ifile, "KEY true")
call ifile_append (ifile, "KEY false")
call ifile_append (ifile, "SEQ lvariable = '?' alt_lvariable")
call ifile_append (ifile, "KEY '?'")
call ifile_append (ifile, "ALT alt_lvariable = variable | grouped_lexpr")
call ifile_append (ifile, "SEQ negation = not lvalue")
call ifile_append (ifile, "KEY not")
call ifile_append (ifile, "GRO grouped_lexpr = ( lexpr )")
call ifile_append (ifile, "SEQ block_lexpr = let var_spec in lexpr")
call ifile_append (ifile, "ALT var_logical = " // &
    "var_logical_new | var_logical_spec")
call ifile_append (ifile, "SEQ var_logical_new = logical var_logical_spec")
call ifile_append (ifile, "KEY logical")
call ifile_append (ifile, "SEQ var_logical_spec = '?' var_name = lexpr")
call ifile_append (ifile, "SEQ conditional_lexpr = " // &
    "if lexpr then lexpr maybe_elseif_lexpr maybe_else_lexpr endif")
call ifile_append (ifile, "SEQ maybe_elseif_lexpr = elseif_lexpr*")
call ifile_append (ifile, "SEQ maybe_else_lexpr = else_lexpr?")
call ifile_append (ifile, "SEQ elseif_lexpr = elseif lexpr then lexpr")
call ifile_append (ifile, "SEQ else_lexpr = else lexpr")
call ifile_append (ifile, "SEQ compared_expr = expr comparison+")
call ifile_append (ifile, "SEQ comparison = compare expr")
call ifile_append (ifile, "ALT compare = " // &
    "< | > | <= | >= | == | <> | ==~ | <>~")
call ifile_append (ifile, "KEY '<'"")
call ifile_append (ifile, "KEY '>'"")
call ifile_append (ifile, "KEY '<='")
call ifile_append (ifile, "KEY '>='")
call ifile_append (ifile, "KEY '=='")
call ifile_append (ifile, "KEY '<>'"")
call ifile_append (ifile, "KEY '==~'"")
call ifile_append (ifile, "KEY '<>~'"")
call ifile_append (ifile, "SEQ compared_sexpr = sexpr str_comparison+")
call ifile_append (ifile, "SEQ str_comparison = str_compare sexpr")
call ifile_append (ifile, "ALT str_compare = '==' | '<>'"")
if (analysis) then
    call ifile_append (ifile, "SEQ record_cmd = " // &
        "record_key analysis_tag record_arg?")
    call ifile_append (ifile, "ALT record_key = record | record_unweighted")
    call ifile_append (ifile, "KEY record")
    call ifile_append (ifile, "KEY record_unweighted")

```

```

        call ifile_append (ifile, "ALT analysis_tag = analysis_id | sexpr")
        call ifile_append (ifile, "IDE analysis_id")
        call ifile_append (ifile, "ARG record_arg = ( expr+ )")
    end if
end subroutine define_lexpr_syntax

```

String expressions.

(Expressions: procedures)+≡

```

subroutine define_sexpr_syntax (ifile)
    type(ifile_t), intent(inout) :: ifile
    call ifile_append (ifile, "SEQ sexpr = svalue str_concatenation*")
    call ifile_append (ifile, "SEQ str_concatenation = '&' svalue")
    call ifile_append (ifile, "KEY '&'")
    call ifile_append (ifile, "ALT svalue = " // &
        "grouped_sexpr | block_sexpr | conditional_sexpr | " // &
        "svariable | string_function | string_literal")
    call ifile_append (ifile, "GRO grouped_sexpr = ( sexpr )")
    call ifile_append (ifile, "SEQ block_sexpr = let var_spec in sexpr")
    call ifile_append (ifile, "SEQ conditional_sexpr = " // &
        "if lexpr then sexpr maybe_elseif_sexpr maybe_else_sexpr endif")
    call ifile_append (ifile, "SEQ maybe_elseif_sexpr = elseif_sexpr*")
    call ifile_append (ifile, "SEQ maybe_else_sexpr = else_sexpr?")
    call ifile_append (ifile, "SEQ elseif_sexpr = elseif lexpr then sexpr")
    call ifile_append (ifile, "SEQ else_sexpr = else sexpr")
    call ifile_append (ifile, "SEQ svariable = '$' alt_svariable")
    call ifile_append (ifile, "KEY '$'")
    call ifile_append (ifile, "ALT alt_svariable = variable | grouped_sexpr")
    call ifile_append (ifile, "ALT var_string = " // &
        "var_string_new | var_string_spec")
    call ifile_append (ifile, "SEQ var_string_new = string var_string_spec")
    call ifile_append (ifile, "KEY string")
    call ifile_append (ifile, "SEQ var_string_spec = '$' var_name = sexpr") ! $
    call ifile_append (ifile, "ALT string_function = sprintf_fun | sprintf_fun")
    call ifile_append (ifile, "SEQ sprintf_fun = sprintf sprintf_args?")
    call ifile_append (ifile, "KEY sprintf")
    call ifile_append (ifile, "SEQ sprintf_fun = sprintf_clause sprintf_args?")
    call ifile_append (ifile, "SEQ sprintf_clause = sprintf sexpr")
    call ifile_append (ifile, "KEY sprintf")
    call ifile_append (ifile, "ARG sprintf_args = ( sprintf_arg* )")
    call ifile_append (ifile, "ALT sprintf_arg = " &
        "// "lvariable | svariable | expr")
    call ifile_append (ifile, "QUO string_literal = '""'...'""'")
end subroutine define_sexpr_syntax

```

Expressions that evaluate to subevents.

(Expressions: procedures)+≡

```

subroutine define_pexpr_syntax (ifile)
    type(ifile_t), intent(inout) :: ifile
    call ifile_append (ifile, "SEQ pexpr = pterm pconcatenation*")
    call ifile_append (ifile, "SEQ pconcatenation = '&' pterm")
    ! call ifile_append (ifile, "KEY '&'")
    call ifile_append (ifile, "SEQ pterm = pvalue pcombination*")
    call ifile_append (ifile, "SEQ pcombination = '+' pvalue")

```

```

!    call ifile_append (ifile, "KEY '+'")
call ifile_append (ifile, "ALT pvalue = " // &
    "pexpr_src | pvariable | " // &
    "grouped_pexpr | block_pexpr | conditional_pexpr | " // &
    "prt_function")
call ifile_append (ifile, "SEQ pexpr_src = prefix_cexpr")
call ifile_append (ifile, "ALT prefix_cexpr = " // &
    "incoming_prt | outgoing_prt")
call ifile_append (ifile, "SEQ incoming_prt = incoming cexpr")
call ifile_append (ifile, "KEY incoming")
call ifile_append (ifile, "SEQ outgoing_prt = cexpr")
call ifile_append (ifile, "SEQ pvariable = '@' alt_pvariable")
call ifile_append (ifile, "KEY '@")
call ifile_append (ifile, "ALT alt_pvariable = variable | grouped_pexpr")
call ifile_append (ifile, "GRO grouped_pexpr = '[' pexpr ']'")
call ifile_append (ifile, "SEQ block_pexpr = let var_spec in pexpr")
call ifile_append (ifile, "SEQ conditional_pexpr = " // &
    "if lexpr then pexpr maybe_elseif_pexpr maybe_else_pexpr endif")
call ifile_append (ifile, "SEQ maybe_elseif_pexpr = elseif_pexpr*")
call ifile_append (ifile, "SEQ maybe_else_pexpr = else_pexpr?")
call ifile_append (ifile, "SEQ elseif_pexpr = elseif lexpr then pexpr")
call ifile_append (ifile, "SEQ else_pexpr = else pexpr")
call ifile_append (ifile, "ALT prt_function = " // &
    "join_fun | combine_fun | collect_fun | select_fun | " // &
    "extract_fun | sort_fun")
call ifile_append (ifile, "SEQ join_fun = join_clause pargs2")
call ifile_append (ifile, "SEQ combine_fun = combine_clause pargs2")
call ifile_append (ifile, "SEQ collect_fun = collect_clause pargs1")
call ifile_append (ifile, "SEQ select_fun = select_clause pargs1")
call ifile_append (ifile, "SEQ extract_fun = extract_clause pargs1")
call ifile_append (ifile, "SEQ sort_fun = sort_clause pargs1")
call ifile_append (ifile, "SEQ join_clause = join condition?")
call ifile_append (ifile, "SEQ combine_clause = combine condition?")
call ifile_append (ifile, "SEQ collect_clause = collect condition?")
call ifile_append (ifile, "SEQ select_clause = select condition?")
call ifile_append (ifile, "SEQ extract_clause = extract position?")
call ifile_append (ifile, "SEQ sort_clause = sort criterion?")
call ifile_append (ifile, "KEY join")
call ifile_append (ifile, "KEY combine")
call ifile_append (ifile, "KEY collect")
call ifile_append (ifile, "KEY select")
call ifile_append (ifile, "SEQ condition = if lexpr")
call ifile_append (ifile, "KEY extract")
call ifile_append (ifile, "SEQ position = index expr")
call ifile_append (ifile, "KEY sort")
call ifile_append (ifile, "SEQ criterion = by expr")
call ifile_append (ifile, "KEY index")
call ifile_append (ifile, "KEY by")
call ifile_append (ifile, "ARG pargs2 = '[' pexpr, pexpr ']'")
call ifile_append (ifile, "ARG pargs1 = '[' pexpr, pexpr? ']'")
end subroutine define_pexpr_syntax

```

Expressions that evaluate to PDG-code arrays.

$\langle \text{Expressions: procedures} \rangle + \equiv$


```

subroutine define_cexpr_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "SEQ cexpr = avalue concatenation*")
  call ifile_append (ifile, "SEQ concatenation = ':' avalue")
  call ifile_append (ifile, "KEY ':'")
  call ifile_append (ifile, "ALT avalue = " // &
    "grouped_cexpr | block_cexpr | conditional_cexpr | " // &
    "variable | pdg_code | prt_name")
  call ifile_append (ifile, "GRO grouped_cexpr = ( cexpr )")
  call ifile_append (ifile, "SEQ block_cexpr = let var_spec in cexpr")
  call ifile_append (ifile, "SEQ conditional_cexpr = " // &
    "if lexpr then cexpr maybe_elseif_cexpr maybe_else_cexpr endif")
  call ifile_append (ifile, "SEQ maybe_elseif_cexpr = elseif_cexpr*")
  call ifile_append (ifile, "SEQ maybe_else_cexpr = else_cexpr?")
  call ifile_append (ifile, "SEQ elseif_cexpr = elseif lexpr then cexpr")
  call ifile_append (ifile, "SEQ else_cexpr = else cexpr")
  call ifile_append (ifile, "SEQ pdg_code = pdg pdg_arg")
  call ifile_append (ifile, "KEY pdg")
  call ifile_append (ifile, "ARG pdg_arg = ( expr )")
  call ifile_append (ifile, "QUO prt_name = '""'...'""'")
end subroutine define_cexpr_syntax

```

Extra variable types.

(Expressions: procedures)+≡

```

subroutine define_var_plist_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "ALT var_plist = var_plist_new | var_plist_spec")
  call ifile_append (ifile, "SEQ var_plist_new = subevt var_plist_spec")
  call ifile_append (ifile, "KEY subevt")
  call ifile_append (ifile, "SEQ var_plist_spec = '@' var_name '=' pexpr")
end subroutine define_var_plist_syntax

subroutine define_var_alias_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "SEQ var_alias = alias var_name '=' cexpr")
  call ifile_append (ifile, "KEY alias")
end subroutine define_var_alias_syntax

```

Particle-list expressions that evaluate to numeric values

(Expressions: procedures)+≡

```

subroutine define_numeric_pexpr_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "ALT numeric_pexpr = " &
    // "eval_fun | count_fun | event_shape_fun")
  call ifile_append (ifile, "SEQ eval_fun = eval expr pargs1")
  call ifile_append (ifile, "SEQ count_fun = count_clause pargs1")
  call ifile_append (ifile, "SEQ count_clause = count condition?")
  call ifile_append (ifile, "KEY eval")
  call ifile_append (ifile, "KEY count")
  call ifile_append (ifile, "ALT event_shape_fun = user_event_fun")
  call ifile_append (ifile, "SEQ user_event_fun = " &
    // "user_event_shape user_arg pargs1")
  call ifile_append (ifile, "KEY user_event_shape")

```

```
end subroutine define_numeric_pexpr_syntax
```

Particle-list functions that evaluate to logical values.

(Expressions: procedures)+≡

```
subroutine define_logical_pexpr_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "ALT logical_pexpr = " // &
    "all_fun | any_fun | no_fun | user_cut_fun")
  call ifile_append (ifile, "SEQ all_fun = all lexpr pargs1")
  call ifile_append (ifile, "SEQ any_fun = any lexpr pargs1")
  call ifile_append (ifile, "SEQ no_fun = no lexpr pargs1")
  call ifile_append (ifile, "KEY all")
  call ifile_append (ifile, "KEY any")
  call ifile_append (ifile, "KEY no")
  call ifile_append (ifile, "SEQ user_cut_fun = user_cut user_arg pargs1")
  call ifile_append (ifile, "KEY user_cut")
end subroutine define_logical_pexpr_syntax
```

All characters that can occur in expressions (apart from alphanumeric).

(Expressions: procedures)+≡

```
subroutine lexer_init_eval_tree (lexer, particles)
  type(lexer_t), intent(out) :: lexer
  logical, intent(in) :: particles
  type(keyword_list_t), pointer :: keyword_list
  if (particles) then
    keyword_list => syntax_get_keyword_list_ptr (syntax_pexpr)
  else
    keyword_list => syntax_get_keyword_list_ptr (syntax_expr)
  end if
  call lexer_init (lexer, &
    comment_chars = "#!", &
    quote_chars = "'", &
    quote_match = "'", &
    single_chars = "()[];:&%?${}@", &
    special_class = (/ "+-*/^", "<=>~ " /) , &
    keyword_list = keyword_list)
end subroutine lexer_init_eval_tree
```

5.6.8 Set up appropriate parse trees

Parse an input stream as a specific flavor of expression. The appropriate expression syntax has to be available.

(Expressions: public)+≡

```
public :: parse_tree_init_expr
public :: parse_tree_init_lexpr
public :: parse_tree_init_pexpr
public :: parse_tree_init_cexpr
public :: parse_tree_init_sexpr
```

(Expressions: procedures)+≡

```
subroutine parse_tree_init_expr (parse_tree, stream, particles)
  type(parse_tree_t), intent(out) :: parse_tree
```

```

type(stream_t), intent(inout), target :: stream
logical, intent(in) :: particles
type(lexer_t) :: lexer
call lexer_init_eval_tree (lexer, particles)
call lexer_assign_stream (lexer, stream)
if (particles) then
    call parse_tree_init &
        (parse_tree, syntax_pexpr, lexer, var_str ("expr"))
else
    call parse_tree_init &
        (parse_tree, syntax_expr, lexer, var_str ("expr"))
end if
call lexer_final (lexer)
end subroutine parse_tree_init_expr

subroutine parse_tree_init_lexpr (parse_tree, stream, particles)
type(parse_tree_t), intent(out) :: parse_tree
type(stream_t), intent(inout), target :: stream
logical, intent(in) :: particles
type(lexer_t) :: lexer
call lexer_init_eval_tree (lexer, particles)
call lexer_assign_stream (lexer, stream)
if (particles) then
    call parse_tree_init &
        (parse_tree, syntax_pexpr, lexer, var_str ("lexpr"))
else
    call parse_tree_init &
        (parse_tree, syntax_expr, lexer, var_str ("lexpr"))
end if
call lexer_final (lexer)
end subroutine parse_tree_init_lexpr

subroutine parse_tree_init_pexpr (parse_tree, stream)
type(parse_tree_t), intent(out) :: parse_tree
type(stream_t), intent(inout), target :: stream
type(lexer_t) :: lexer
call lexer_init_eval_tree (lexer, .true.)
call lexer_assign_stream (lexer, stream)
call parse_tree_init &
    (parse_tree, syntax_pexpr, lexer, var_str ("pexpr"))
call lexer_final (lexer)
end subroutine parse_tree_init_pexpr

subroutine parse_tree_init_cexpr (parse_tree, stream)
type(parse_tree_t), intent(out) :: parse_tree
type(stream_t), intent(inout), target :: stream
type(lexer_t) :: lexer
call lexer_init_eval_tree (lexer, .true.)
call lexer_assign_stream (lexer, stream)
call parse_tree_init &
    (parse_tree, syntax_pexpr, lexer, var_str ("cexpr"))
call lexer_final (lexer)
end subroutine parse_tree_init_cexpr

```

```

subroutine parse_tree_init_sexpr (parse_tree, stream, particles)
  type(parse_tree_t), intent(out) :: parse_tree
  type(stream_t), intent(inout), target :: stream
  logical, intent(in) :: particles
  type(lexer_t) :: lexer
  call lexer_init_eval_tree (lexer, particles)
  call lexer_assign_stream (lexer, stream)
  if (particles) then
    call parse_tree_init &
      (parse_tree, syntax_pexpr, lexer, var_str ("sexpr"))
  else
    call parse_tree_init &
      (parse_tree, syntax_expr, lexer, var_str ("sexpr"))
  end if
  call lexer_final (lexer)
end subroutine parse_tree_init_sexpr

```

5.6.9 The evaluation tree

The evaluation tree contains the initial variable list and the root node.

```

<Expressions: public>+≡
  public :: eval_tree_t

<Expressions: types>+≡
  type :: eval_tree_t
  private
  type(var_list_t) :: var_list
  type(eval_node_t), pointer :: root => null ()
end type eval_tree_t

```

Init from stream, using a temporary parse tree.

```

<Expressions: procedures>+≡
  subroutine eval_tree_init_stream &
    (eval_tree, stream, var_list, subvt, result_type)
    type(eval_tree_t), intent(out), target :: eval_tree
    type(stream_t), intent(inout), target :: stream
    type(var_list_t), intent(in), target :: var_list
    type(subvt_t), intent(in), target, optional :: subvt
    integer, intent(in), optional :: result_type
    type(parse_tree_t) :: parse_tree
    type(parse_node_t), pointer :: nd_root
    integer :: type
    type = V_REAL; if (present (result_type)) type = result_type
    select case (type)
    case (V_INT, V_REAL, V_CMPLX)
      call parse_tree_init_expr (parse_tree, stream, present (subvt))
    case (V_LOG)
      call parse_tree_init_lexpr (parse_tree, stream, present (subvt))
    case (V_SEV)
      call parse_tree_init_pexpr (parse_tree, stream)
    case (V_PDG)
      call parse_tree_init_cexpr (parse_tree, stream)

```

```

case (V_STR)
  call parse_tree_init_sexpr (parse_tree, stream, present (subevt))
end select
call parse_tree_write (parse_tree)
nd_root => parse_tree_get_root_ptr (parse_tree)
if (associated (nd_root)) then
  select case (type)
  case (V_INT, V_REAL, V_CMPLX)
    call eval_tree_init_expr (eval_tree, nd_root, var_list, subevt)
  case (V_LOG)
    call eval_tree_init_lexpr (eval_tree, nd_root, var_list, subevt)
  case (V_SEV)
    call eval_tree_init_pexpr (eval_tree, nd_root, var_list, subevt)
  case (V_PDG)
    call eval_tree_init_cexpr (eval_tree, nd_root, var_list, subevt)
  case (V_STR)
    call eval_tree_init_sexpr (eval_tree, nd_root, var_list, subevt)
  end select
end if
call parse_tree_final (parse_tree)
end subroutine eval_tree_init_stream

```

API: Init from a given parse-tree node. If we evaluate an expression that contains particle-list references, the original subevent has to be supplied. The initial variable list is optional.

(Expressions: public)+≡

```

public :: eval_tree_init_expr
public :: eval_tree_init_lexpr
public :: eval_tree_init_pexpr
public :: eval_tree_init_cexpr
public :: eval_tree_init_sexpr

```

(Expressions: procedures)+≡

```

subroutine eval_tree_init_expr &
  (eval_tree, parse_node, var_list, subevt, event_vars)
  type(eval_tree_t), intent(out), target :: eval_tree
  type(parse_node_t), intent(in), target :: parse_node
  type(var_list_t), intent(in), target :: var_list
  type(subevt_t), intent(in), optional, target :: subevt
  type(event_vars_t), intent(in), optional, target :: event_vars
  call eval_tree_set_var_list (eval_tree, var_list, subevt, event_vars)
  call eval_node_compile_expr &
    (eval_tree%root, parse_node, eval_tree%var_list)
end subroutine eval_tree_init_expr

subroutine eval_tree_init_lexpr &
  (eval_tree, parse_node, var_list, subevt, event_vars)
  type(eval_tree_t), intent(out), target :: eval_tree
  type(parse_node_t), intent(in), target :: parse_node
  type(var_list_t), intent(in), target :: var_list
  type(subevt_t), intent(in), optional, target :: subevt
  type(event_vars_t), intent(in), optional, target :: event_vars
  call eval_tree_set_var_list (eval_tree, var_list, subevt, event_vars)
  call eval_node_compile_lexpr &

```

```

        (eval_tree%root, parse_node, eval_tree%var_list)
    end subroutine eval_tree_init_lexpr

subroutine eval_tree_init_pexpr &
    (eval_tree, parse_node, var_list, subevt, event_vars)
    type(eval_tree_t), intent(out), target :: eval_tree
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    call eval_tree_set_var_list (eval_tree, var_list, subevt, event_vars)
    call eval_node_compile_pexpr &
        (eval_tree%root, parse_node, eval_tree%var_list)
end subroutine eval_tree_init_pexpr

subroutine eval_tree_init_cexpr &
    (eval_tree, parse_node, var_list, subevt, event_vars)
    type(eval_tree_t), intent(out), target :: eval_tree
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    call eval_tree_set_var_list (eval_tree, var_list, subevt, event_vars)
    call eval_node_compile_cexpr &
        (eval_tree%root, parse_node, eval_tree%var_list)
end subroutine eval_tree_init_cexpr

subroutine eval_tree_init_sexpr &
    (eval_tree, parse_node, var_list, subevt, event_vars)
    type(eval_tree_t), intent(out), target :: eval_tree
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    call eval_tree_set_var_list (eval_tree, var_list, subevt, event_vars)
    call eval_node_compile_sexpr &
        (eval_tree%root, parse_node, eval_tree%var_list)
end subroutine eval_tree_init_sexpr

```

This extra API function handles numerical constant expressions only. The only nontrivial part is the optional unit.

```

<Expressions: public>+≡
    public :: eval_tree_init_numeric_value

<Expressions: procedures>+≡
    subroutine eval_tree_init_numeric_value (eval_tree, parse_node)
        type(eval_tree_t), intent(out), target :: eval_tree
        type(parse_node_t), intent(in), target :: parse_node
        call eval_node_compile_numeric_value (eval_tree%root, parse_node)
    end subroutine eval_tree_init_numeric_value

```

Initialize the variable list with the initial one; if a particle list is provided, add a pointer to this as variable @evt. If the event weight is provided as a real-valued

target, add a pointer to it as well.

```

<Expressions: procedures>+≡
  subroutine eval_tree_set_var_list &
    (eval_tree, var_list, subevt, event_vars)
    type(eval_tree_t), intent(inout), target :: eval_tree
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    logical, save, target :: known = .true.
    call var_list_link (eval_tree%var_list, var_list)
    if (present (subevt)) call var_list_append_subevt_ptr &
      (eval_tree%var_list, var_str ("@evt"), subevt, known, &
        intrinsic=.true.)
    if (present (event_vars)) &
      call var_list_append_event_vars (eval_tree%var_list, event_vars)
  end subroutine eval_tree_set_var_list

```

```

<Expressions: public>+≡
  public :: eval_tree_final

```

```

<Expressions: procedures>+≡
  subroutine eval_tree_final (eval_tree)
    type(eval_tree_t), intent(inout) :: eval_tree
    call var_list_final (eval_tree%var_list)
    if (associated (eval_tree%root)) then
      call eval_node_final_rec (eval_tree%root)
      deallocate (eval_tree%root)
    end if
  end subroutine eval_tree_final

```

```

<Expressions: public>+≡
  public :: eval_tree_evaluate

```

```

<Expressions: procedures>+≡
  subroutine eval_tree_evaluate (eval_tree)
    type(eval_tree_t), intent(inout) :: eval_tree
    if (associated (eval_tree%root)) then
      call eval_node_evaluate (eval_tree%root)
    end if
  end subroutine eval_tree_evaluate

```

Check if the eval tree is allocated.

```

<Expressions: public>+≡
  public :: eval_tree_is_defined

```

```

<Expressions: procedures>+≡
  function eval_tree_is_defined (eval_tree) result (flag)
    logical :: flag
    type(eval_tree_t), intent(in) :: eval_tree
    flag = associated (eval_tree%root)
  end function eval_tree_is_defined

```

Check if the eval tree result is constant.

```

<Expressions: public>+≡
    public :: eval_tree_is_constant

<Expressions: procedures>+≡
    function eval_tree_is_constant (eval_tree) result (flag)
        logical :: flag
        type(eval_tree_t), intent(in) :: eval_tree
        if (associated (eval_tree%root)) then
            flag = eval_tree%root%type == EN_CONSTANT
        else
            flag = .false.
        end if
    end function eval_tree_is_constant

```

Insert a conversion node at the root, if necessary (only for real/int conversion)

```

<Expressions: public>+≡
    public :: eval_tree_convert_result

<Expressions: procedures>+≡
    subroutine eval_tree_convert_result (eval_tree, result_type)
        type(eval_tree_t), intent(inout) :: eval_tree
        integer, intent(in) :: result_type
        if (associated (eval_tree%root)) then
            call insert_conversion_node (eval_tree%root, result_type)
        end if
    end subroutine eval_tree_convert_result

```

Return the value of the top node, after evaluation. If the tree is empty, return the type of V_NONE. When extracting the value, no check for existence is done. For numeric values, the functions are safe against real/integer mismatch.

```

<Expressions: public>+≡
    public :: eval_tree_get_result_type
    public :: eval_tree_result_is_known
    public :: eval_tree_result_is_known_ptr
    public :: eval_tree_get_log
    public :: eval_tree_get_int
    public :: eval_tree_get_real
    public :: eval_tree_get_cmplx
    public :: eval_tree_get_pdg_array
    public :: eval_tree_get_subevt
    public :: eval_tree_get_string

<Expressions: procedures>+≡
    function eval_tree_get_result_type (eval_tree) result (type)
        integer :: type
        type(eval_tree_t), intent(in) :: eval_tree
        if (associated (eval_tree%root)) then
            type = eval_tree%root%result_type
        else
            type = V_NONE
        end if
    end function eval_tree_get_result_type

```



```

function eval_tree_result_is_known (eval_tree) result (flag)
  logical :: flag
  type(eval_tree_t), intent(in) :: eval_tree
  if (associated (eval_tree%root)) then
    select case (eval_tree%root%result_type)
    case (V_LOG, V_INT, V_REAL)
      flag = eval_tree%root%value_is_known
    case default
      flag = .true.
    end select
  else
    flag = .false.
  end if
end function eval_tree_result_is_known

function eval_tree_result_is_known_ptr (eval_tree) result (ptr)
  logical, pointer :: ptr
  type(eval_tree_t), intent(in) :: eval_tree
  logical, target, save :: known = .true.
  if (associated (eval_tree%root)) then
    select case (eval_tree%root%result_type)
    case (V_LOG, V_INT, V_REAL)
      ptr => eval_tree%root%value_is_known
    case default
      ptr => known
    end select
  else
    ptr => null ()
  end if
end function eval_tree_result_is_known_ptr

function eval_tree_get_log (eval_tree) result (lval)
  logical :: lval
  type(eval_tree_t), intent(in) :: eval_tree
  if (associated (eval_tree%root)) lval = eval_tree%root%lval
end function eval_tree_get_log

function eval_tree_get_int (eval_tree) result (ival)
  integer :: ival
  type(eval_tree_t), intent(in) :: eval_tree
  if (associated (eval_tree%root)) then
    select case (eval_tree%root%result_type)
    case (V_INT); ival = eval_tree%root%ival
    case (V_REAL); ival = eval_tree%root%rval
    case (V_CMPLX); ival = eval_tree%root%cval
    end select
  end if
end function eval_tree_get_int

function eval_tree_get_real (eval_tree) result (rval)
  real(default) :: rval
  type(eval_tree_t), intent(in) :: eval_tree
  if (associated (eval_tree%root)) then
    select case (eval_tree%root%result_type)

```

```

        case (V_REAL); rval = eval_tree%root%rval
        case (V_INT);  rval = eval_tree%root%ival
        case (V_CMPLX); rval = eval_tree%root%cval
    end select
end if
end function eval_tree_get_real

function eval_tree_get_cmplx (eval_tree) result (cval)
    complex(default) :: cval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        select case (eval_tree%root%result_type)
            case (V_CMPLX); cval = eval_tree%root%cval
            case (V_REAL);  cval = eval_tree%root%rval
            case (V_INT);   cval = eval_tree%root%ival
        end select
    end if
end function eval_tree_get_cmplx

function eval_tree_get_pdg_array (eval_tree) result (aval)
    type(pdg_array_t) :: aval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        aval = eval_tree%root%aval
    end if
end function eval_tree_get_pdg_array

function eval_tree_get_subevt (eval_tree) result (pval)
    type(subevt_t) :: pval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        pval = eval_tree%root%pval
    end if
end function eval_tree_get_subevt

function eval_tree_get_string (eval_tree) result (sval)
    type(string_t) :: sval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        sval = eval_tree%root%sval
    end if
end function eval_tree_get_string

```

Return a pointer to the value of the top node.

<Expressions: public>+≡

```

    public :: eval_tree_get_log_ptr
    public :: eval_tree_get_int_ptr
    public :: eval_tree_get_real_ptr
    public :: eval_tree_get_cmplx_ptr
    public :: eval_tree_get_subevt_ptr
    public :: eval_tree_get_pdg_array_ptr
    public :: eval_tree_get_string_ptr

```

<Expressions: procedures>+≡

```

function eval_tree_get_log_ptr (eval_tree) result (lval)
    logical, pointer :: lval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        lval => eval_tree%root%lval
    else
        lval => null ()
    end if
end function eval_tree_get_log_ptr

function eval_tree_get_int_ptr (eval_tree) result (ival)
    integer, pointer :: ival
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        ival => eval_tree%root%ival
    else
        ival => null ()
    end if
end function eval_tree_get_int_ptr

function eval_tree_get_real_ptr (eval_tree) result (rval)
    real(default), pointer :: rval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        rval => eval_tree%root%rval
    else
        rval => null ()
    end if
end function eval_tree_get_real_ptr

function eval_tree_get_cmplx_ptr (eval_tree) result (cval)
    complex(default), pointer :: cval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        cval => eval_tree%root%cval
    else
        cval => null ()
    end if
end function eval_tree_get_cmplx_ptr

function eval_tree_get_subevt_ptr (eval_tree) result (pval)
    type(subevt_t), pointer :: pval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        pval => eval_tree%root%pval
    else
        pval => null ()
    end if
end function eval_tree_get_subevt_ptr

function eval_tree_get_pdg_array_ptr (eval_tree) result (aval)
    type(pdg_array_t), pointer :: aval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then

```

```

        aval => eval_tree%root%aval
    else
        aval => null ()
    end if
end function eval_tree_get_pdg_array_ptr

function eval_tree_get_string_ptr (eval_tree) result (sval)
    type(string_t), pointer :: sval
    type(eval_tree_t), intent(in) :: eval_tree
    if (associated (eval_tree%root)) then
        sval => eval_tree%root%sval
    else
        sval => null ()
    end if
end function eval_tree_get_string_ptr

```

<Expressions: public>+≡

```
public :: eval_tree_write
```

<Expressions: procedures>+≡

```

subroutine eval_tree_write (eval_tree, unit, write_var_list)
    type(eval_tree_t), intent(in) :: eval_tree
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: write_var_list
    integer :: u
    logical :: vl
    u = output_unit (unit); if (u < 0) return
    vl = .false.; if (present (write_var_list)) vl = write_var_list
    write (u, "(1x,A)") "Evaluation tree:"
    if (associated (eval_tree%root)) then
        call eval_node_write_rec (eval_tree%root, unit)
    else
        write (u, "(3x,A)") "[empty]"
    end if
    if (vl) call var_list_write (eval_tree%var_list, unit)
end subroutine eval_tree_write

```

Use the written representation for generating an MD5 sum:

<Expressions: public>+≡

```
public :: eval_tree_get_md5sum
```

<Expressions: procedures>+≡

```

function eval_tree_get_md5sum (eval_tree) result (md5sum_et)
    character(32) :: md5sum_et
    type(eval_tree_t), intent(in) :: eval_tree
    integer :: u
    u = free_unit ()
    open (unit = u, status = "scratch", action = "readwrite")
    call eval_tree_write (eval_tree, unit=u)
    rewind (u)
    md5sum_et = md5sum (u)
    close (u)
end function eval_tree_get_md5sum

```

5.6.10 Direct evaluation

These procedures create an eval tree and evaluate it on-the-fly, returning only the final value. The evaluation must yield a well-defined value, unless the `is_known` flag is present, which will be set accordingly.

```
(Expressions: public)+≡
  public :: eval_log
  public :: eval_int
  public :: eval_real
  public :: eval_cmplx
  public :: eval_subevt
  public :: eval_pdg_array
  public :: eval_string

(Expressions: procedures)+≡
  function eval_log &
    (parse_node, var_list, subevt, event_vars, is_known) result (lval)
    logical :: lval
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    logical, intent(out), optional :: is_known
    type(eval_tree_t), target :: eval_tree
    call eval_tree_init_lexpr &
      (eval_tree, parse_node, var_list, subevt, event_vars)
    call eval_tree_evaluate (eval_tree)
    if (eval_tree_result_is_known (eval_tree)) then
      if (present (is_known)) is_known = .true.
      lval = eval_tree_get_log (eval_tree)
    else if (present (is_known)) then
      is_known = .false.
    else
      call eval_tree_unknown (eval_tree, parse_node)
      lval = .false.
    end if
    call eval_tree_final (eval_tree)
  end function eval_log

  function eval_int &
    (parse_node, var_list, subevt, event_vars, is_known) result (ival)
    integer :: ival
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    logical, intent(out), optional :: is_known
    type(eval_tree_t), target :: eval_tree
    call eval_tree_init_expr &
      (eval_tree, parse_node, var_list, subevt, event_vars)
    call eval_tree_evaluate (eval_tree)
    if (eval_tree_result_is_known (eval_tree)) then
      if (present (is_known)) is_known = .true.
      ival = eval_tree_get_int (eval_tree)
    else if (present (is_known)) then
```

```

        is_known = .false.
    else
        call eval_tree_unknown (eval_tree, parse_node)
        ival = 0
    end if
    call eval_tree_final (eval_tree)
end function eval_int

function eval_real &
    (parse_node, var_list, subevt, event_vars, is_known) result (rval)
    real(default) :: rval
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    logical, intent(out), optional :: is_known
    type(eval_tree_t), target :: eval_tree
    call eval_tree_init_expr &
        (eval_tree, parse_node, var_list, subevt, event_vars)
    call eval_tree_evaluate (eval_tree)
    if (eval_tree_result_is_known (eval_tree)) then
        if (present (is_known)) is_known = .true.
        rval = eval_tree_get_real (eval_tree)
    else if (present (is_known)) then
        is_known = .false.
    else
        call eval_tree_unknown (eval_tree, parse_node)
        rval = 0
    end if
    call eval_tree_final (eval_tree)
end function eval_real

function eval_cmplx &
    (parse_node, var_list, subevt, event_vars, is_known) result (cval)
    complex(default) :: cval
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    logical, intent(out), optional :: is_known
    type(eval_tree_t), target :: eval_tree
    call eval_tree_init_expr &
        (eval_tree, parse_node, var_list, subevt, event_vars)
    call eval_tree_evaluate (eval_tree)
    if (eval_tree_result_is_known (eval_tree)) then
        if (present (is_known)) is_known = .true.
        cval = eval_tree_get_cmplx (eval_tree)
    else if (present (is_known)) then
        is_known = .false.
    else
        call eval_tree_unknown (eval_tree, parse_node)
        cval = 0
    end if
    call eval_tree_final (eval_tree)

```

```

end function eval_cplx

function eval_subevt &
  (parse_node, var_list, subevt, event_vars, is_known) result (pval)
  type(subevt_t) :: pval
  type(parse_node_t), intent(in), target :: parse_node
  type(var_list_t), intent(in), target :: var_list
  type(subevt_t), intent(in), optional, target :: subevt
  type(event_vars_t), intent(in), optional, target :: event_vars
  logical, intent(out), optional :: is_known
  type(eval_tree_t), target :: eval_tree
  call eval_tree_init_pexpr &
    (eval_tree, parse_node, var_list, subevt, event_vars)
  call eval_tree_evaluate (eval_tree)
  if (eval_tree_result_is_known (eval_tree)) then
    if (present (is_known)) is_known = .true.
    pval = eval_tree_get_subevt (eval_tree)
  else if (present (is_known)) then
    is_known = .false.
  else
    call eval_tree_unknown (eval_tree, parse_node)
  end if
  call eval_tree_final (eval_tree)
end function eval_subevt

function eval_pdg_array &
  (parse_node, var_list, subevt, event_vars, is_known) result (aval)
  type(pdg_array_t) :: aval
  type(parse_node_t), intent(in), target :: parse_node
  type(var_list_t), intent(in), target :: var_list
  type(subevt_t), intent(in), optional, target :: subevt
  type(event_vars_t), intent(in), optional, target :: event_vars
  logical, intent(out), optional :: is_known
  type(eval_tree_t), target :: eval_tree
  call eval_tree_init_cexpr &
    (eval_tree, parse_node, var_list, subevt, event_vars)
  call eval_tree_evaluate (eval_tree)
  if (eval_tree_result_is_known (eval_tree)) then
    if (present (is_known)) is_known = .true.
    aval = eval_tree_get_pdg_array (eval_tree)
  else if (present (is_known)) then
    is_known = .false.
  else
    call eval_tree_unknown (eval_tree, parse_node)
  end if
  call eval_tree_final (eval_tree)
end function eval_pdg_array

function eval_string &
  (parse_node, var_list, subevt, event_vars, is_known) result (sval)
  type(string_t) :: sval
  type(parse_node_t), intent(in), target :: parse_node
  type(var_list_t), intent(in), target :: var_list
  type(subevt_t), intent(in), optional, target :: subevt

```

```

type(event_vars_t), intent(in), optional, target :: event_vars
logical, intent(out), optional :: is_known
type(eval_tree_t), target :: eval_tree
call eval_tree_init_sexpr &
    (eval_tree, parse_node, var_list, subevt, event_vars)
call eval_tree_evaluate (eval_tree)
if (eval_tree_result_is_known (eval_tree)) then
    if (present (is_known)) is_known = .true.
    sval = eval_tree_get_string (eval_tree)
else if (present (is_known)) then
    is_known = .false.
else
    call eval_tree_unknown (eval_tree, parse_node)
    sval = ""
end if
call eval_tree_final (eval_tree)
end function eval_string

```

Here is a variant that returns numeric values of all possible kinds, the appropriate kind to be selected later:

```

<Expressions: public>+≡
    public :: eval_numeric

<Expressions: procedures>+≡
    subroutine eval_numeric &
        (parse_node, var_list, subevt, event_vars, ival, rval, cval, &
         is_known, result_type)
    type(parse_node_t), intent(in), target :: parse_node
    type(var_list_t), intent(in), target :: var_list
    type(subevt_t), intent(in), optional, target :: subevt
    type(event_vars_t), intent(in), optional, target :: event_vars
    integer, intent(out), optional :: ival
    real(default), intent(out), optional :: rval
    complex(default), intent(out), optional :: cval
    logical, intent(out), optional :: is_known
    integer, intent(out), optional :: result_type
    type(eval_tree_t), target :: eval_tree
    call eval_tree_init_expr &
        (eval_tree, parse_node, var_list, subevt, event_vars)
    call eval_tree_evaluate (eval_tree)
    if (eval_tree_result_is_known (eval_tree)) then
        if (present (ival)) ival = eval_tree_get_int (eval_tree)
        if (present (rval)) rval = eval_tree_get_real (eval_tree)
        if (present (cval)) cval = eval_tree_get_cmplx (eval_tree)
        if (present (is_known)) is_known = .true.
    else
        call eval_tree_unknown (eval_tree, parse_node)
        if (present (ival)) ival = 0
        if (present (rval)) rval = 0
        if (present (cval)) cval = 0
        if (present (is_known)) is_known = .false.
    end if
    if (present (result_type)) &
        result_type = eval_tree_get_result_type (eval_tree)

```



```

        call eval_tree_final (eval_tree)
    end subroutine eval_numeric

```

Error message with debugging info:

```

<Expressions: procedures>+≡
    subroutine eval_tree_unknown (eval_tree, parse_node)
        type(eval_tree_t), intent(in) :: eval_tree
        type(parse_node_t), intent(in) :: parse_node
        call parse_node_write_rec (parse_node)
        call eval_tree_write (eval_tree)
        call msg_error ("Evaluation yields an undefined result, inserting default")
    end subroutine eval_tree_unknown

```

5.6.11 Test

```

<Expressions: public>+≡
    public :: expressions_test

<Expressions: procedures>+≡
    subroutine expressions_test ()
        print *
        print *, "Expressions test 1"
        print *
        call expressions_test1 ()
        print *
        print *, "Expressions test 2"
        print *
        call syntax_expr_init ()
        call syntax_write (syntax_expr)
        call expressions_test2
        call syntax_expr_final ()
        print *
        print *, "Expressions test 3"
        print *
        call expressions_test3
        print *
        print *, "Expressions test 4"
        print *
        call syntax_pexpr_init ()
        call syntax_write (syntax_pexpr)
        call expressions_test4
        call syntax_pexpr_final ()
    end subroutine expressions_test

    subroutine expressions_test1 ()
        type(var_list_t), pointer :: var_list => null ()
        type(eval_node_t), pointer :: node => null ()
        type(prt_t), pointer :: prt => null ()
        type(var_entry_t), pointer :: var => null ()
        allocate (var_list)
        allocate (prt)
        call var_list_set_observables_unary (var_list, prt)
        call var_list_write (var_list)
    end subroutine expressions_test1

```

```

var => var_list_get_var_ptr (var_list, var_str ("PDG"))
allocate (node)
call eval_node_init_obs (node, var)
call eval_node_write (node)
call eval_node_final_rec (node)
deallocate (node)
call var_list_final (var_list)
deallocate (var_list)
deallocate (prt)
end subroutine expressions_test1

subroutine expressions_test2 ()
  type(ifile_t) :: ifile
  type(stream_t) :: stream
  type(eval_tree_t) :: eval_tree
  type(string_t) :: expr_text
  type(var_list_t), pointer :: var_list => null ()
  allocate (var_list)
  call var_list_append_real (var_list, var_str ("x"), -5._default)
  call var_list_append_int (var_list, var_str ("foo"), -27)
  call var_list_append_real (var_list, var_str ("mb"), 4._default)
  expr_text = &
    "let real twopi = 2 * pi in" // &
    "  twopi * sqrt (25.d0 - mb^2)" // &
    "  / (let int mb_or_0 = max (mb, 0) in" // &
    "    1 + (if -1 TeV <= x < mb_or_0 then abs(x) else x endif))"
  call ifile_append (ifile, expr_text)
  call stream_init (stream, ifile)
  call var_list_write (var_list)
  call eval_tree_init_stream (eval_tree, stream, var_list=var_list)
  call eval_tree_evaluate (eval_tree)
  call eval_tree_write (eval_tree)
  print "(A)", "Input string:"
  print *, char (expr_text)
  call stream_final (stream)
  call ifile_final (ifile)
  call eval_tree_final (eval_tree)
  call var_list_final (var_list)
  deallocate (var_list)
end subroutine expressions_test2

subroutine expressions_test3 ()
  type(subevt_t) :: subevt
  call subevt_init (subevt)
  call subevt_reset (subevt, 1)
  call subevt_set_incoming (subevt, 1, &
    22, vector4_moving (1.e3_default, 1.e3_default, 1), &
    0._default, (/ 2 /))
  call subevt_write (subevt)
  call subevt_reset (subevt, 4)
  call subevt_reset (subevt, 3)
  call subevt_set_incoming (subevt, 1, &
    21, vector4_moving (1.e3_default, 1.e3_default, 3), &
    0._default, (/ 1 /))

```

```

call subevt_polarize (subevt, 1, -1)
call subevt_set_outgoing (subevt, 2, &
    1, vector4_moving (0._default, 1.e3_default, 3), &
    -1.e6_default, (/ 7 /))
call subevt_set_composite (subevt, 3, &
    vector4_moving (-1.e3_default, 0._default, 3), &
    (/ 2, 7 /))
call subevt_write (subevt)
end subroutine expressions_test3

subroutine expressions_test4 ()
    type(subevt_t), target :: subevt
    type(string_t) :: expr_text
    type(ifile_t) :: ifile
    type(stream_t) :: stream
    type(eval_tree_t) :: eval_tree
    type(var_list_t), pointer :: var_list => null ()
    type(pdg_array_t) :: aval
    allocate (var_list)
    aval = 0
    call var_list_append_pdg_array (var_list, var_str ("particle"), aval)
    aval = (/ 11,-11 /)
    call var_list_append_pdg_array (var_list, var_str ("lepton"), aval)
    aval = 22
    call var_list_append_pdg_array (var_list, var_str ("photon"), aval)
    aval = 1
    call var_list_append_pdg_array (var_list, var_str ("u"), aval)
    call subevt_init (subevt)
    call subevt_reset (subevt, 6)
    call subevt_set_incoming (subevt, 1, &
        1, vector4_moving (1._default, 1._default, 1), 0._default)
    call subevt_set_incoming (subevt, 2, &
        -1, vector4_moving (2._default, 2._default, 1), 0._default)
    call subevt_set_outgoing (subevt, 3, &
        22, vector4_moving (3._default, 3._default, 1), 0._default)
    call subevt_set_outgoing (subevt, 4, &
        22, vector4_moving (4._default, 4._default, 1), 0._default)
    call subevt_set_outgoing (subevt, 5, &
        11, vector4_moving (5._default, 5._default, 1), 0._default)
    call subevt_set_outgoing (subevt, 6, &
        -11, vector4_moving (6._default, 6._default, 1), 0._default)
    print *
    print *, "Expression:"
    expr_text = &
        "let alias quark = pdg(1):pdg(2):pdg(3) in" // &
        "  any E > 3 GeV " // &
        "    [sort by - Pt " // &
        "      [select if Index < 6 " // &
        "        [photon:pdg(-11):pdg(3):quark " // &
        "          & incoming particle]]]" // &
        " and" // &
        " eval Theta [extract index -1 [photon]] > 45 degree" // &
        " and" // &
        " count [incoming photon] * 3 > 0"

```

```

print *, char (expr_text)
print *
call ifile_append (ifile, expr_text)
call stream_init (stream, ifile)
call eval_tree_init_stream (eval_tree, stream, var_list, subevt, V_LOG)
print *
call eval_tree_write (eval_tree)
call eval_tree_evaluate (eval_tree)
print *
call eval_tree_write (eval_tree)
call stream_final (stream)
call ifile_final (ifile)
call eval_tree_final (eval_tree)
call var_list_final (var_list)
deallocate (var_list)
end subroutine expressions_test4

```

Chapter 6

Physics Models

While in previous WHIZARD versions, the physics model was partially hard-coded and injected into the main code via include files, the current version stores the accessible models in module variables. This allows for maintaining different models concurrently. Accessing the model is possible via pointers to the module variables; this is used by flavor objects, for instance.

6.1 Model module

```
<models.f90>≡  
  <File header>  
  
  module models  
  
    use iso_c_binding !NODEP!  
  <Use kinds>  
    use kinds, only: i8, i32 !NODEP!  
    use kinds, only: c_default_float !NODEP!  
  <Use strings>  
    use limits, only: VERTEX_TABLE_SCALE_FACTOR !NODEP!  
  <Use file utils>  
    use md5  
    use os_interface  
    use hashes, only: hash  
    use diagnostics !NODEP!  
    use ifiles  
    use syntax_rules  
    use lexers  
    use parser  
    use pdg_arrays  
    use variables  
    use expressions  
  
  <Standard module head>  
  
  <Models: public>  
  
  <Models: parameters>
```

```

    <Models: types>

    <Models: interfaces>

    <Models: variables>

contains

    <Models: procedures>

end module models

```

6.1.1 Physics Parameters

A parameter has a name, a value. Derived parameters also have a definition in terms of other parameters, which is stored as an `eval_tree`. External parameters are set by an external program.

```

<Models: parameters>≡
    integer, parameter :: PAR_NONE = 0
    integer, parameter :: PAR_INDEPENDENT = 1, PAR_DERIVED = 2
    integer, parameter :: PAR_EXTERNAL = 3

<Models: public>≡
    public :: parameter_t

<Models: types>≡
    type :: parameter_t
        private
        integer :: type = PAR_NONE
        type(string_t) :: name
        real(default) :: value = 0
        type(eval_tree_t) :: eval_tree
    end type parameter_t

```

Initialization depends on parameter type. Independent parameters are initialized by a constant value or a constant numerical expression (which may contain a unit). Derived parameters are initialized by an arbitrary numerical expression, which makes use of the current variable list. The expression is evaluated by the function `parameter_reset`.

```

<Models: procedures>≡
    subroutine parameter_init_independent_value (par, name, value)
        type(parameter_t), intent(out) :: par
        type(string_t), intent(in) :: name
        real(default), intent(in) :: value
        par%type = PAR_INDEPENDENT
        par%name = name
        par%value = value
    end subroutine parameter_init_independent_value

    subroutine parameter_init_independent (par, name, pn)
        type(parameter_t), intent(out) :: par

```

```

    type(string_t), intent(in) :: name
    type(parse_node_t), intent(in), target :: pn
    par%type = PAR_INDEPENDENT
    par%name = name
    call eval_tree_init_numeric_value (par%eval_tree, pn)
    par%value = eval_tree_get_real (par%eval_tree)
end subroutine parameter_init_independent

subroutine parameter_init_derived (par, name, pn, var_list)
    type(parameter_t), intent(out) :: par
    type(string_t), intent(in) :: name
    type(parse_node_t), intent(in), target :: pn
    type(var_list_t), intent(in), target :: var_list
    par%type = PAR_DERIVED
    par%name = name
    call eval_tree_init_expr (par%eval_tree, pn, var_list=var_list)
    call parameter_reset_derived (par)
end subroutine parameter_init_derived

subroutine parameter_init_external (par, name)
    type(parameter_t), intent(out) :: par
    type(string_t), intent(in) :: name
    par%type = PAR_EXTERNAL
    par%name = name
end subroutine parameter_init_external

```

The finalizer is needed for the evaluation tree in the definition.

```

<Models: procedures>+≡
subroutine parameter_final (par)
    type(parameter_t), intent(inout) :: par
    call eval_tree_final (par%eval_tree)
end subroutine parameter_final

```

All derived parameters should be recalculated if some independent parameters have changed:

```

<Models: procedures>+≡
subroutine parameter_reset_derived (par)
    type(parameter_t), intent(inout) :: par
    select case (par%type)
    case (PAR_DERIVED)
        call eval_tree_evaluate (par%eval_tree)
        par%value = eval_tree_get_real (par%eval_tree)
    end select
end subroutine parameter_reset_derived

```

Direct access to the parameter value:

```

<Models: procedures>+≡
function parameter_get_value_ptr (par) result (val)
    real(default), pointer :: val
    type(parameter_t), intent(in), target :: par
    val => par%value
end function parameter_get_value_ptr

```

Output. [We should have a formula format for the eval tree, suitable for input and output!]

<Models: procedures>+≡

```

subroutine parameter_write (par, unit, write_defs)
  type(parameter_t), intent(in) :: par
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: write_defs
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, "(3x,A)", advance="no") "parameter"
  write (u, "(1x,A,1x,A)", advance="no") char (par%name), "="
  write (u, "(G17.10)", advance="no") par%value
  select case (par%type)
  case (PAR_DERIVED)
    write (u, *) " ! derived"
    if (present (write_defs)) then
      if (write_defs) then
        call eval_tree_write (par%eval_tree, unit)
      end if
    end if
  case (PAR_EXTERNAL)
    write (u, *) " ! external"
  end select
end subroutine parameter_write

```

6.1.2 Particle codes

Let us define a few particle codes independent of the model.

SM fermions:

<Models: types>+≡

```

integer, parameter, public :: ELECTRON = 11

```

Gauge bosons:

<Models: types>+≡

```

integer, parameter, public :: GLUON = 21
integer, parameter, public :: PHOTON = 22
integer, parameter, public :: Z_BOSON = 23
integer, parameter, public :: W_BOSON = 24

```

Hadrons:

<Models: types>+≡

```

integer, parameter, public :: PROTON = 2212

```

<Models: types>+≡

```

integer, parameter, public :: PION = 111
integer, parameter, public :: PIPLUS = 211
integer, parameter, public :: PIMINUS = - PIPLUS

```


Hadron remnants (internal)

```
(Models: types)+≡  
    integer, parameter, public :: HADRON_REMNANT = 90  
    integer, parameter, public :: HADRON_REMNANT_SINGLET = 91  
    integer, parameter, public :: HADRON_REMNANT_TRIPLET = 92  
    integer, parameter, public :: HADRON_REMNANT_OCTET = 93
```

Generic particles for internal use in event analysis:

```
(Models: types)+≡  
    integer, parameter, public :: PRT_ANY = 81  
    integer, parameter, public :: PRT_VISIBLE = 82  
    integer, parameter, public :: PRT_CHARGED = 83  
    integer, parameter, public :: PRT_COLORED = 84
```

Further particle codes for internal use:

```
(Models: types)+≡  
    integer, parameter, public :: INVALID = 97  
    integer, parameter, public :: KEYSTONE = 98  
    integer, parameter, public :: COMPOSITE = 99
```

6.1.3 Spin codes

Somewhat redundant, but for better readability we define named constants for spin types. If the mass is nonzero, this is equal to the number of degrees of freedom.

```
(Models: types)+≡  
    integer, parameter, public :: UNKNOWN=0  
    integer, parameter, public :: SCALAR=1, SPINOR=2, VECTOR=3, &  
        VECTORSPINOR=4, TENSOR=5
```

Isospin types and charge types are counted in an analogous way, where charge type 1 is charge 0, 2 is charge 1/3, and so on. Zero always means unknown. Note that charge and isospin types have an explicit sign.

Color types are defined as the dimension of the representation.

6.1.4 Particle data

The particle-data type holds all information that pertains to a particular particle within a particular model. Information such as spin type, particle code etc. is stored within the object itself, while mass and width are associated to parameters, otherwise assumed zero.

```
(Models: public)+≡  
    public :: particle_data_t  
  
(Models: types)+≡  
    type :: particle_data_t  
        private  
        type(string_t) :: longname  
        integer :: pdg = UNDEFINED  
        logical :: is_visible = .true.  
        logical :: is_parton = .false.
```

```

logical :: is_gauge = .false.
logical :: is_left_handed = .false.
logical :: is_right_handed = .false.
logical :: has_antiparticle = .false.
logical :: p_is_stable = .true.
logical :: p_decays_isotropically = .false.
logical :: p_decays_diagonal = .false.
logical :: a_is_stable = .true.
logical :: a_decays_isotropically = .false.
logical :: a_decays_diagonal = .false.
logical :: p_polarized = .false.
logical :: a_polarized = .false.
type(string_t), dimension(:), allocatable :: name, anti
type(string_t) :: tex_name, tex_anti
integer :: spin_type = UNDEFINED
integer :: isospin_type = 1
integer :: charge_type = 1
integer :: color_type = 1
real(default), pointer :: mass_val => null ()
type(parameter_t), pointer :: mass_src => null ()
real(default), pointer :: width_val => null ()
type(parameter_t), pointer :: width_src => null ()
integer :: multiplicity = 1
end type particle_data_t

```

Initialize particle data with PDG long name and PDG code. \TeX names should be initialized to avoid issues with accessing unallocated string contents.

(Models: public)+≡

```
public :: particle_data_init
```

(Models: procedures)+≡

```

subroutine particle_data_init (prt, longname, pdg)
  type(particle_data_t), intent(out) :: prt
  type(string_t), intent(in) :: longname
  integer, intent(in) :: pdg
  prt%longname = longname
  prt%pdg = pdg
  prt%tex_name = ""
  prt%tex_anti = ""
end subroutine particle_data_init

```

Copy quantum numbers from another particle

(Models: procedures)+≡

```

subroutine particle_data_copy (prt, prt_src)
  type(particle_data_t), intent(inout) :: prt
  type(particle_data_t), intent(in) :: prt_src
  prt%is_visible = prt_src%is_visible
  prt%is_parton = prt_src%is_parton
  prt%is_gauge = prt_src%is_gauge
  prt%is_left_handed = prt_src%is_left_handed
  prt%is_right_handed = prt_src%is_right_handed
  prt%spin_type = prt_src%spin_type
  prt%isospin_type = prt_src%isospin_type

```

```

prt%charge_type = prt_src%charge_type
prt%color_type = prt_src%color_type
call particle_data_set_multiplicity (prt)
end subroutine particle_data_copy

```

Set particle quantum numbers.

<Models: public>+≡

```
public :: particle_data_set
```

<Models: procedures>+≡

```

subroutine particle_data_set (prt, &
    is_visible, is_parton, is_gauge, is_left_handed, is_right_handed, &
    p_is_stable, p_decays_isotropically, p_decays_diagonal, &
    a_is_stable, a_decays_isotropically, a_decays_diagonal, &
    p_polarized, a_polarized, &
    name, anti, tex_name, tex_anti, &
    spin_type, isospin_type, charge_type, color_type, &
    mass_src, width_src)
type(particle_data_t), intent(inout) :: prt
logical, intent(in), optional :: is_visible, is_parton, is_gauge
logical, intent(in), optional :: is_left_handed, is_right_handed
logical, intent(in), optional :: p_is_stable
logical, intent(in), optional :: p_decays_isotropically, p_decays_diagonal
logical, intent(in), optional :: a_is_stable
logical, intent(in), optional :: a_decays_isotropically, a_decays_diagonal
logical, intent(in), optional :: p_polarized, a_polarized
type(string_t), dimension(:), intent(in), optional :: name, anti
type(string_t), intent(in), optional :: tex_name, tex_anti
integer, intent(in), optional :: spin_type, isospin_type
integer, intent(in), optional :: charge_type, color_type
type(parameter_t), intent(in), target, optional :: mass_src, width_src
if (present (is_visible)) prt%is_visible = is_visible
if (present (is_parton)) prt%is_parton = is_parton
if (present (is_gauge)) prt%is_gauge = is_gauge
if (present (is_left_handed)) prt%is_left_handed = is_left_handed
if (present (is_right_handed)) prt%is_right_handed = is_right_handed
if (present (p_is_stable)) prt%p_is_stable = p_is_stable
if (present (p_decays_isotropically)) &
    prt%p_decays_isotropically = p_decays_isotropically
if (present (p_decays_diagonal)) &
    prt%p_decays_diagonal = p_decays_diagonal
if (present (a_is_stable)) prt%a_is_stable = a_is_stable
if (present (a_decays_isotropically)) &
    prt%a_decays_isotropically = a_decays_isotropically
if (present (a_decays_diagonal)) &
    prt%a_decays_diagonal = a_decays_diagonal
if (present (p_polarized)) prt%p_polarized = p_polarized
if (present (a_polarized)) prt%a_polarized = a_polarized
if (present (name)) then
    allocate (prt%name (size (name)))
    prt%name = name
end if
if (present (anti)) then
    allocate (prt%anti (size (anti)))

```

```

        prt%anti = anti
        prt%has_antiparticle = .true.
    end if
    if (present (tex_name)) prt%tex_name = tex_name
    if (present (tex_anti)) prt%tex_anti = tex_anti
    if (present (spin_type)) prt%spin_type = spin_type
    if (present (isospin_type)) prt%isospin_type = isospin_type
    if (present (charge_type)) prt%charge_type = charge_type
    if (present (color_type)) prt%color_type = color_type
    if (present (mass_src)) then
        prt%mass_src => mass_src
        prt%mass_val => parameter_get_value_ptr (mass_src)
    end if
    if (present (width_src)) then
        prt%width_src => width_src
        prt%width_val => parameter_get_value_ptr (width_src)
    end if
    if (present (spin_type) .or. present (mass_src)) then
        call particle_data_set_multiplicity (prt)
    end if
end subroutine particle_data_set

```

Calculate the multiplicity given spin type and mass.

(Models: procedures)+≡

```

subroutine particle_data_set_multiplicity (prt)
    type(particle_data_t), intent(inout) :: prt
    if (prt%spin_type /= SCALAR) then
        if (associated (prt%mass_src)) then
            prt%multiplicity = prt%spin_type
        else if (prt%is_left_handed .or. prt%is_right_handed) then
            prt%multiplicity = 1
        else
            prt%multiplicity = 2
        end if
    end if
end subroutine particle_data_set_multiplicity

```

Set the mass/width value (not the pointer). The mass/width pointer must be allocated.

(Models: procedures)+≡

```

subroutine particle_data_set_mass (prt, mass)
    type(particle_data_t), intent(inout) :: prt
    real(default), intent(in) :: mass
    if (associated (prt%mass_val)) prt%mass_val = mass
end subroutine particle_data_set_mass

subroutine particle_data_set_width (prt, width)
    type(particle_data_t), intent(inout) :: prt
    real(default), intent(in) :: width
    if (associated (prt%width_val)) prt%width_val = width
end subroutine particle_data_set_width

```

Loose ends

<Models: public>+≡

```
public :: particle_data_freeze
```

<Models: procedures>+≡

```
subroutine particle_data_freeze (prt)
  type(particle_data_t), intent(inout) :: prt
  if (.not. allocated (prt%name)) allocate (prt%name (0))
  if (.not. allocated (prt%anti)) allocate (prt%anti (0))
end subroutine particle_data_freeze
```

Output

<Models: procedures>+≡

```
subroutine particle_data_write (prt, unit)
  type(particle_data_t), intent(in) :: prt
  integer, intent(in), optional :: unit
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, "(3x,A,1x,A)", advance="no") "particle", char (prt%longname)
  write (u, "(1x,I7)", advance="no") prt%pdg
  if (.not. prt%is_visible) write (u, "(3x,A)", advance="no") "invisible"
  if (prt%is_parton) write (u, "(3x,A)", advance="no") "parton"
  if (prt%is_gauge) write (u, "(3x,A)", advance="no") "gauge"
  if (prt%is_left_handed) write (u, "(3x,A)", advance="no") "left"
  if (prt%is_right_handed) write (u, "(3x,A)", advance="no") "right"
  write (u, *)
  write (u, "(5x,A)", advance="no") "name"
  if (allocated (prt%name)) then
    do i = 1, size (prt%name)
      write (u, "(1x,A)", advance="no") ' ' // char (prt%name(i)) // ' '
    end do
    write (u, *)
    if (prt%has_antiparticle) then
      write (u, "(5x,A)", advance="no") "anti"
      do i = 1, size (prt%anti)
        write (u, "(1x,A)", advance="no") ' ' // char (prt%anti(i)) // ' '
      end do
      write (u, *)
    end if
    if (prt%tex_name /= "") then
      write (u, "(5x,A)") &
        "tex_name " // ' ' // char (prt%tex_name) // ' '
    end if
    if (prt%has_antiparticle .and. prt%tex_anti /= "") then
      write (u, "(5x,A)") &
        "tex_anti " // ' ' // char (prt%tex_anti) // ' '
    end if
  else
    write (u, "(A)") "???"
  end if
  write (u, "(5x,A)", advance="no") "spin "
  select case (mod (prt%spin_type - 1, 2))
  case (0); write (u, "(I1)", advance="no") (prt%spin_type-1) / 2
  case default; write (u, "(I1,A)", advance="no") prt%spin_type-1, "/2"
```

```

end select
! write (u, "(3x,A,I1,A)") "! [multiplicity = ", prt%multiplicity, "]"
if (abs (prt%isospin_type) /= 1) then
  write (u, "(5x,A)", advance="no") "isospin "
  select case (mod (abs (prt%isospin_type) - 1, 2))
  case (0); write (u, "(I2)", advance="no") &
    sign (abs (prt%isospin_type) - 1, prt%isospin_type) / 2
  case default; write (u, "(I2,A)", advance="no") &
    sign (abs (prt%isospin_type) - 1, prt%isospin_type), "/2"
  end select
end if
if (abs (prt%charge_type) /= 1) then
  write (u, "(5x,A)", advance="no") "charge "
  select case (mod (abs (prt%charge_type) - 1, 3))
  case (0); write (u, "(I2)", advance="no") &
    sign (abs (prt%charge_type) - 1, prt%charge_type) / 3
  case default; write (u, "(I2,A)", advance="no") &
    sign (abs (prt%charge_type) - 1, prt%charge_type), "/3"
  end select
end if
if (prt%color_type /= 1) then
  write (u, "(5x,A,I2)", advance="no") "color ", prt%color_type
end if
write (u, *)
if (associated (prt%mass_src)) then
  write (u, "(5x,A)") "mass " // char (prt%mass_src%name)
  if (associated (prt%width_src)) then
    write (u, "(5x,A)") "width " // char (prt%width_src%name)
  end if
end if
end subroutine particle_data_write

```

Retrieve data:

<Models: public>+≡

```

public :: particle_data_get_pdg
public :: particle_data_get_pdg_anti

```

<Models: procedures>+≡

```

elemental function particle_data_get_pdg (prt) result (pdg)
  integer :: pdg
  type(particle_data_t), intent(in) :: prt
  pdg = prt%pdg
end function particle_data_get_pdg

elemental function particle_data_get_pdg_anti (prt) result (pdg)
  integer :: pdg
  type(particle_data_t), intent(in) :: prt
  if (prt%has_antiparticle) then
    pdg = - prt%pdg
  else
    pdg = prt%pdg
  end if
end function particle_data_get_pdg_anti

```

Predicates:

$\langle Models: public \rangle + \equiv$

```
public :: particle_data_is_visible
public :: particle_data_is_parton
public :: particle_data_is_gauge
public :: particle_data_is_left_handed
public :: particle_data_is_right_handed
public :: particle_data_has_antiparticle
public :: particle_data_is_stable
public :: particle_data_decays_isotropically
public :: particle_data_decays_diagonal
public :: particle_data_is_polarized
```

$\langle Models: procedures \rangle + \equiv$

```
elemental function particle_data_is_visible (prt) result (flag)
  logical :: flag
  type(particle_data_t), intent(in) :: prt
  flag = prt%is_visible
end function particle_data_is_visible

elemental function particle_data_is_parton (prt) result (flag)
  logical :: flag
  type(particle_data_t), intent(in) :: prt
  flag = prt%is_parton
end function particle_data_is_parton

elemental function particle_data_is_gauge (prt) result (flag)
  logical :: flag
  type(particle_data_t), intent(in) :: prt
  flag = prt%is_gauge
end function particle_data_is_gauge

elemental function particle_data_is_left_handed (prt) result (flag)
  logical :: flag
  type(particle_data_t), intent(in) :: prt
  flag = prt%is_left_handed
end function particle_data_is_left_handed

elemental function particle_data_is_right_handed (prt) result (flag)
  logical :: flag
  type(particle_data_t), intent(in) :: prt
  flag = prt%is_right_handed
end function particle_data_is_right_handed

elemental function particle_data_has_antiparticle (prt) result (flag)
  logical :: flag
  type(particle_data_t), intent(in) :: prt
  flag = prt%has_antiparticle
end function particle_data_has_antiparticle

elemental function particle_data_is_stable (prt, anti) result (flag)
  logical :: flag
  type(particle_data_t), intent(in) :: prt
  logical, intent(in), optional :: anti
  if (present (anti)) then
```

```

        if (anti) then
            flag = prt%a_is_stable
        else
            flag = prt%p_is_stable
        end if
    else
        flag = prt%p_is_stable
    end if
end function particle_data_is_stable

elemental function particle_data_decays_isotropically &
    (prt, anti) result (flag)
    logical :: flag
    type(particle_data_t), intent(in) :: prt
    logical, intent(in), optional :: anti
    if (present (anti)) then
        if (anti) then
            flag = prt%a_decays_isotropically
        else
            flag = prt%p_decays_isotropically
        end if
    else
        flag = prt%p_decays_isotropically
    end if
end function particle_data_decays_isotropically

elemental function particle_data_decays_diagonal &
    (prt, anti) result (flag)
    logical :: flag
    type(particle_data_t), intent(in) :: prt
    logical, intent(in), optional :: anti
    if (present (anti)) then
        if (anti) then
            flag = prt%a_decays_diagonal
        else
            flag = prt%p_decays_diagonal
        end if
    else
        flag = prt%p_decays_diagonal
    end if
end function particle_data_decays_diagonal

elemental function particle_data_is_polarized (prt, anti) result (flag)
    logical :: flag
    type(particle_data_t), intent(in) :: prt
    logical, intent(in), optional :: anti
    logical :: a
    if (present (anti)) then
        a = anti
    else
        a = .false.
    end if
    if (a) then
        flag = prt%a_polarized
    end if
end function particle_data_is_polarized

```



```

else
    flag = prt%p_polarized
end if
end function particle_data_is_polarized

```

Names. Return the first name in the list (or the first antiparticle name)

```

⟨Models: public⟩+≡
    public :: particle_data_get_name

⟨Models: procedures⟩+≡
    elemental function particle_data_get_name &
        (prt, is_antiparticle) result (name)
        type(string_t) :: name
        type(particle_data_t), intent(in) :: prt
        logical, intent(in) :: is_antiparticle
        name = "???"
        if (is_antiparticle) then
            if (prt%has_antiparticle) then
                if (allocated (prt%anti)) then
                    if (size(prt%anti) > 0) name = prt%anti(1)
                end if
            else
                if (allocated (prt%name)) then
                    if (size (prt%name) > 0) name = prt%name(1)
                end if
            end if
        else
            if (allocated (prt%name)) then
                if (size (prt%name) > 0) name = prt%name(1)
            end if
        end if
    end function particle_data_get_name

```

Same for the T_EX name.

```

⟨Models: public⟩+≡
    public :: particle_data_get_tex_name

⟨Models: procedures⟩+≡
    elemental function particle_data_get_tex_name &
        (prt, is_antiparticle) result (name)
        type(string_t) :: name
        type(particle_data_t), intent(in) :: prt
        logical, intent(in) :: is_antiparticle
        if (is_antiparticle) then
            if (prt%has_antiparticle) then
                name = prt%tex_anti
            else
                name = prt%tex_name
            end if
        else
            name = prt%tex_name
        end if
        if (name == "") name = particle_data_get_name (prt, is_antiparticle)
    end function particle_data_get_tex_name

```

Quantum numbers

<Models: public>+≡

```
public :: particle_data_get_spin_type
public :: particle_data_get_multiplicity
public :: particle_data_get_isospin_type
public :: particle_data_get_charge_type
public :: particle_data_get_color_type
```

<Models: procedures>+≡

```
elemental function particle_data_get_spin_type (prt) result (type)
  integer :: type
  type(particle_data_t), intent(in) :: prt
  type = prt%spin_type
end function particle_data_get_spin_type

elemental function particle_data_get_multiplicity (prt) result (type)
  integer :: type
  type(particle_data_t), intent(in) :: prt
  type = prt%multiplicity
end function particle_data_get_multiplicity

elemental function particle_data_get_isospin_type (prt) result (type)
  integer :: type
  type(particle_data_t), intent(in) :: prt
  type = prt%isospin_type
end function particle_data_get_isospin_type

elemental function particle_data_get_charge_type (prt) result (type)
  integer :: type
  type(particle_data_t), intent(in) :: prt
  type = prt%charge_type
end function particle_data_get_charge_type

elemental function particle_data_get_color_type (prt) result (type)
  integer :: type
  type(particle_data_t), intent(in) :: prt
  type = prt%color_type
end function particle_data_get_color_type
```

In the MSSM, neutralinos can have a negative mass. This is relevant for computing matrix elements. However, within the `WHIZARD` main program we are interested only in kinematics, therefore we return the absolute value of the particle mass. If desired, we can extract the sign separately.

<Models: public>+≡

```
public :: particle_data_get_charge
public :: particle_data_get_mass
public :: particle_data_get_mass_sign
public :: particle_data_get_width
public :: particle_data_get_isospin
```

<Models: procedures>+≡

```
elemental function particle_data_get_charge (prt) result (charge)
  real(default) :: charge
```

```

type(particle_data_t), intent(in) :: prt
if (prt%charge_type /= 0) then
    charge = real (sign ((abs(prt%charge_type) - 1), &
        prt%charge_type), default) / 3
else
    charge = 0
end if
end function particle_data_get_charge

elemental function particle_data_get_mass (prt) result (mass)
    real(default) :: mass
    type(particle_data_t), intent(in) :: prt
    if (associated (prt%mass_val)) then
        mass = abs (prt%mass_val)
    else
        mass = 0
    end if
end function particle_data_get_mass

elemental function particle_data_get_mass_sign (prt) result (sgn)
    integer :: sgn
    type(particle_data_t), intent(in) :: prt
    if (associated (prt%mass_val)) then
        sgn = sign (1._default, prt%mass_val)
    else
        sgn = 0
    end if
end function particle_data_get_mass_sign

elemental function particle_data_get_width (prt) result (width)
    real(default) :: width
    type(particle_data_t), intent(in) :: prt
    if (associated (prt%width_val)) then
        width = prt%width_val
    else
        width = 0
    end if
end function particle_data_get_width

elemental function particle_data_get_isospin (prt) result (isospin)
    real(default) :: isospin
    type(particle_data_t), intent(in) :: prt
    if (prt%isospin_type /= 0) then
        isospin = real (sign (abs(prt%isospin_type) - 1, &
            prt%isospin_type), default) / 2
    else
        isospin = 0
    end if
end function particle_data_get_isospin

```

Given an array of particles, return a PDG-array object that consists of all charged particles in the array. We need to explicitly add their antiparticles.

(Models: procedures)+≡

```

function particle_data_get_charged_pdg (prt) result (aval)
  type(pdg_array_t) :: aval, aval_p, aval_a
  type(particle_data_t), dimension(:), intent(in) :: prt
  aval_p = pack ( prt%pdg, abs (prt%charge_type) > 1)
  aval_a = pack (-prt%pdg, abs (prt%charge_type) > 1 &
    .and. prt%has_antiparticle )
  aval = aval_p // aval_a
end function particle_data_get_charged_pdg

```

The same for color.

(Models: procedures)+≡

```

function particle_data_get_colored_pdg (prt) result (aval)
  type(pdg_array_t) :: aval, aval_p, aval_a
  type(particle_data_t), dimension(:), intent(in) :: prt
  aval_p = pack ( prt%pdg, abs (prt%color_type) > 1)
  aval_a = pack (-prt%pdg, abs (prt%color_type) > 1 &
    .and. prt%has_antiparticle )
  aval = aval_p // aval_a
end function particle_data_get_colored_pdg

```

6.1.5 Vertex data

The vertex object contains an array of particle-data pointers, for which we need a separate type. (We could use the flavor type defined in another module.)

The program does not (yet?) make use of vertex definitions, so they are not stored here.

(Models: types)+≡

```

type :: particle_p
  type(particle_data_t), pointer :: p => null ()
end type particle_p

```

(Models: types)+≡

```

type :: vertex_t
  logical :: trilinear
  integer, dimension(:), allocatable :: pdg
  type(particle_p), dimension(:), allocatable :: prt
end type vertex_t

```

Initialize using PDG codes. The model is used for finding particle data pointers associated with the pdg codes.

(Models: procedures)+≡

```

subroutine vertex_init (vtx, pdg, model)
  type(vertex_t), intent(out) :: vtx
  integer, dimension(:), intent(in) :: pdg
  type(model_t), intent(in), target, optional :: model
  integer :: i
  allocate (vtx%pdg (size (pdg)))
  allocate (vtx%prt (size (pdg)))
  vtx%trilinear = size (pdg) == 3
  vtx%pdg = pdg

```

```

    if (present (model)) then
      do i = 1, size (pdg)
        vtx%prt(i)%p => model_get_particle_ptr (model, pdg(i))
      end do
    end if
  end subroutine vertex_init

```

<Models: procedures>+≡

```

subroutine vertex_write (vtx, unit)
  type(vertex_t), intent(in) :: vtx
  integer, intent(in), optional :: unit
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, "(3x,A)", advance="no") "vertex"
  do i = 1, size (vtx%prt)
    if (associated (vtx%prt(i)%p)) then
      write (u, "(1x,A)", advance="no") &
        '"" // char (particle_data_get_name &
          (vtx%prt(i)%p, vtx%pdg(i) < 0)) &
        // '""
    else
      write (u, "(1x,I7)", advance="no") vtx%pdg(i)
    end if
  end do
  write (u, *)
end subroutine vertex_write

```

6.1.6 Vertex lookup table

The vertex lookup table is a hash table: given two particle codes, we check which codes are allowed for the third one.

The size of the hash table should be large enough that collisions are rare. We first select a size based on the number of vertices (multiplied by six because all permutations count), with some margin, and then choose the smallest integer power of two larger than this.

<Limits: public parameters>+≡

```

integer, parameter, public :: VERTEX_TABLE_SCALE_FACTOR = 60

```

<Models: procedures>+≡

```

function vertex_table_size (n_vtx) result (n)
  integer(i32) :: n
  integer, intent(in) :: n_vtx
  integer :: i, s
  s = VERTEX_TABLE_SCALE_FACTOR * n_vtx
  n = 1
  do i = 1, 31
    n = ishft (n, 1)
    s = ishft (s, -1)
    if (s == 0) exit
  end do
end function vertex_table_size

```

The specific hash function takes two particle codes (arbitrary integers) and returns a 32-bit integer. It makes use of the universal function `hash` which operates on a byte array.

```

⟨Models: procedures⟩+≡
  function hash2 (pdg1, pdg2)
    integer(i32) :: hash2
    integer, intent(in) :: pdg1, pdg2
    integer(i8), dimension(1) :: mold
    hash2 = hash (transfer ((/pdg1, pdg2/), mold))
  end function hash2

```

Each entry in the vertex table stores the two particle codes and an array of possibilities for the third code.

```

⟨Models: types⟩+≡
  type :: vertex_table_entry_t
    integer :: pdg1 = 0, pdg2 = 0
    integer :: n = 0
    integer, dimension(:), allocatable :: pdg3
  end type vertex_table_entry_t

```

The vertex table:

```

⟨Models: types⟩+≡
  type :: vertex_table_t
    type(vertex_table_entry_t), dimension(:), allocatable :: entry
    integer :: n_collisions = 0
    integer(i32) :: mask
  end type vertex_table_t

```

Initializing the vertex table: This is done in two passes. First, we scan all permutations for all vertices and count the number of entries in each bucket of the hashtable. Then, the buckets are allocated accordingly and filled.

Collision resolution is done by just incrementing the hash value until an empty bucket is found. The vertex table size is fixed, since we know from the beginning the number of entries.

```

⟨Models: procedures⟩+≡
  subroutine vertex_table_init (vt, prt, vtx)
    type(vertex_table_t), intent(out) :: vt
    type(particle_data_t), dimension(:), intent(in) :: prt
    type(vertex_t), dimension(:), intent(in) :: vtx
    integer :: n_prt, n_vtx, vt_size, i, p1, p2, p3
    integer, dimension(3) :: p
    n_prt = size (prt)
    n_vtx = size (vtx)
    vt_size = vertex_table_size (count (vtx%trilinear))
    vt%mask = vt_size - 1
    allocate (vt%entry (0:vt_size-1))
    do i = 1, n_vtx
      if (vtx(i)%trilinear) then
        p = vtx(i)%pdg
        p1 = p(1); p2 = p(2)
        call create (hash2 (p1, p2))
      end if
    end do
  end subroutine vertex_table_init

```

```

    if (p(2) /= p(3)) then
        p2 = p(3)
        call create (hash2 (p1, p2))
    end if
    if (p(1) /= p(2)) then
        p1 = p(2); p2 = p(1)
        call create (hash2 (p1, p2))
        if (p(1) /= p(3)) then
            p2 = p(3)
            call create (hash2 (p1, p2))
        end if
    end if
    if (p(1) /= p(3)) then
        p1 = p(3); p2 = p(1)
        call create (hash2 (p1, p2))
        if (p(1) /= p(2)) then
            p2 = p(2)
            call create (hash2 (p1, p2))
        end if
    end if
end if
end do
do i = 0, vt_size - 1
    allocate (vt%entry(i)%pdg3 (vt%entry(i)%n))
end do
vt%entry%n = 0
do i = 1, n_vtx
    if (vtx(i)%trilinear) then
        p = vtx(i)%pdg
        p1 = p(1); p2 = p(2); p3 = p(3)
        call register (hash2 (p1, p2))
        if (p(2) /= p(3)) then
            p2 = p(3); p3 = p(2)
            call register (hash2 (p1, p2))
        end if
        if (p(1) /= p(2)) then
            p1 = p(2); p2 = p(1); p3 = p(3)
            call register (hash2 (p1, p2))
            if (p(1) /= p(3)) then
                p2 = p(3); p3 = p(1)
                call register (hash2 (p1, p2))
            end if
        end if
        if (p(1) /= p(3)) then
            p1 = p(3); p2 = p(1); p3 = p(2)
            call register (hash2 (p1, p2))
            if (p(1) /= p(2)) then
                p2 = p(2); p3 = p(1)
                call register (hash2 (p1, p2))
            end if
        end if
    end if
end if
end do
contains

```

```

recursive subroutine create (hashval)
  integer(i32), intent(in) :: hashval
  integer :: h
  h = iand (hashval, vt%mask)
  if (vt%entry(h)%n == 0) then
    vt%entry(h)%pdg1 = p1
    vt%entry(h)%pdg2 = p2
    vt%entry(h)%n = 1
  else if (vt%entry(h)%pdg1 == p1 .and. vt%entry(h)%pdg2 == p2) then
    vt%entry(h)%n = vt%entry(h)%n + 1
  else
    vt%n_collisions = vt%n_collisions + 1
    call create (hashval + 1)
  end if
end subroutine create
recursive subroutine register (hashval)
  integer(i32), intent(in) :: hashval
  integer :: h
  h = iand (hashval, vt%mask)
  if (vt%entry(h)%pdg1 == p1 .and. vt%entry(h)%pdg2 == p2) then
    vt%entry(h)%n = vt%entry(h)%n + 1
    vt%entry(h)%pdg3(vt%entry(h)%n) = p3
  else
    call register (hashval + 1)
  end if
end subroutine register
end subroutine vertex_table_init

```

Output

```

<Models: procedures>+≡
subroutine vertex_table_write (vt, unit)
  type(vertex_table_t), intent(in) :: vt
  integer, intent(in), optional :: unit
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, *) "vertex hash table:"
  write (u, *) "  size = ", size (vt%entry)
  write (u, *) "  used = ", count (vt%entry%n /= 0)
  write (u, *) "  coll = ", vt%n_collisions
  do i = lbound (vt%entry, 1), ubound (vt%entry, 1)
    if (vt%entry(i)%n /= 0) then
      write (u, *) "    ", i, ":", &
        vt%entry(i)%pdg1, vt%entry(i)%pdg2, "->", vt%entry(i)%pdg3
    end if
  end do
end subroutine vertex_table_write

```

Return the array of particle codes that match the given pair.

```

<Models: procedures>+≡
subroutine vertex_table_match (vt, pdg1, pdg2, pdg3)
  type(vertex_table_t), intent(in) :: vt
  integer, intent(in) :: pdg1, pdg2
  integer, dimension(:), allocatable, intent(out) :: pdg3

```



```

integer :: vt_size
vt_size = size (vt%entry)
call match (hash2 (pdg1, pdg2))
contains
recursive subroutine match (hashval)
integer(i32), intent(in) :: hashval
integer :: h
h = iand (hashval, vt%mask)
if (vt%entry(h)%n == 0) then
allocate (pdg3 (0))
else if (vt%entry(h)%pdg1 == pdg1 .and. vt%entry(h)%pdg2 == pdg2) then
allocate (pdg3 (size (vt%entry(h)%pdg3)))
pdg3 = vt%entry(h)%pdg3
else
call match (hashval + 1)
end if
end subroutine match
end subroutine vertex_table_match

```

Return true if the triplet is represented as a vertex.

(Models: procedures)+≡

```

function vertex_table_check (vt, pdg1, pdg2, pdg3) result (flag)
type(vertex_table_t), intent(in) :: vt
integer, intent(in) :: pdg1, pdg2, pdg3
logical :: flag
integer :: vt_size
vt_size = size (vt%entry)
flag = check (hash2 (pdg1, pdg2))
contains
recursive function check (hashval) result (flag)
integer(i32), intent(in) :: hashval
integer :: h
logical :: flag
h = iand (hashval, vt%mask)
if (vt%entry(h)%n == 0) then
flag = .false.
else if (vt%entry(h)%pdg1 == pdg1 .and. vt%entry(h)%pdg2 == pdg2) then
flag = any (vt%entry(h)%pdg3 == pdg3)
else
flag = check (hashval + 1)
end if
end function check
end function vertex_table_check

```

6.1.7 Model data

A model object holds all information about parameters, particles, and vertices. For models that require an external program for parameter calculation, there is the pointer to a function that does this calculation, given the set of independent and derived parameters.

(Models: public)+≡

```

public :: model_t

```

```

<Models: types>+=
  type :: model_t
  private
    type(string_t) :: name
    character(32) :: md5sum = ""
    type(parameter_t), dimension(:), allocatable :: par
    type(particle_data_t), dimension(:), allocatable :: prt
    type(vertex_t), dimension(:), allocatable :: vtx
    type(vertex_table_t) :: vt
    type(var_list_t) :: var_list
    type(string_t) :: dlname
    procedure(model_init_external_parameters), nopass, pointer :: &
      init_external_parameters => null ()
    type(dlaccess_t) :: dlaccess
  end type model_t

```

This is the interface for a procedure that initializes the calculation of external parameters, given the array of all parameters.

```

<Models: interfaces>=
  abstract interface
    subroutine model_init_external_parameters (par) bind (C)
      import
      real(c_default_float), dimension(*), intent(inout) :: par
    end subroutine model_init_external_parameters
  end interface

```

Initialization: Specify the number of parameters, particles, vertices and allocate memory. If an associated DL library is specified, load this library.

```

<Models: procedures>+=
  subroutine model_init (model, name, libname, os_data, n_par, n_prt, n_vtx)
    type(model_t), intent(out) :: model
    type(string_t), intent(in) :: name, libname
    type(os_data_t), intent(in) :: os_data
    integer, intent(in) :: n_par, n_prt, n_vtx
    type(c_funptr) :: c_fptr
    type(string_t) :: libpath
    model%name = name
    allocate (model%par (n_par))
    allocate (model%prt (n_prt))
    allocate (model%vtx (n_vtx))
    if (libname /= "") then
      if (.not. os_data%use_testfiles) then
        libpath = os_data%whizard_models_libpath_local
        model%dlname = os_get_dlname ( &
          libpath // "/" // libname, os_data, ignore=.true., silent=.true.)
      end if
      if (model%dlname == "") then
        libpath = os_data%whizard_models_libpath
        model%dlname = os_get_dlname (libpath // "/" // libname, os_data)
      end if
    else
      model%dlname = ""
    end if
  end subroutine model_init

```

```

if (model%dlname /= "") then
  if (.not. dlaccess_is_open (model%dlaccess)) then
    call msg_message ("Loading model auxiliary library '" &
      // char (libpath) // "/" // char (model%dlname) // "'")
    call dlaccess_init (model%dlaccess, os_data%whizard_models_libpath, &
      model%dlname, os_data)
    if (dlaccess_has_error (model%dlaccess)) then
      call msg_message (char (dlaccess_get_error (model%dlaccess)))
      call msg_fatal ("Loading model auxiliary library '" &
        // char (model%dlname) // "' failed")
      return
    end if
    c_fptr = dlaccess_get_c_funptr (model%dlaccess, &
      var_str ("init_external_parameters"))
    if (dlaccess_has_error (model%dlaccess)) then
      call msg_message (char (dlaccess_get_error (model%dlaccess)))
      call msg_fatal ("Loading function from auxiliary library '" &
        // char (model%dlname) // "' failed")
      return
    end if
    call c_f_procpointer (c_fptr, model% init_external_parameters)
  end if
end if
end subroutine model_init

```

Finalization: The variable list is the only part that contains pointers.

```

<Models: public>+≡
  public :: model_final

<Models: procedures>+≡
  subroutine model_final (model)
    type(model_t), intent(inout) :: model
    call var_list_final (model%var_list)
    if (model%dlname /= "") call dlaccess_final (model%dlaccess)
  end subroutine model_final

```

Output. By default, the output is in the form of an input file. If `verbose` is true, for each derived parameter the definition (eval tree) is displayed, and the vertex hash table is shown.

```

<Models: public>+≡
  public :: model_write

<Models: procedures>+≡
  subroutine model_write (model, unit, verbose)
    type(model_t), intent(in) :: model
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u, i
    u = output_unit (unit); if (u < 0) return
    write (u, *) 'model "', char (model%name), '"'
    write (u, *) '! md5sum = "', model%md5sum, '"'
    do i = 1, size (model%par)
      call parameter_write (model%par(i), unit, verbose)
    write (u, *)

```

```

end do
do i = 1, size (model%prt)
  call particle_data_write (model%prt(i), unit)
end do
do i = 1, size (model%vtx)
  call vertex_write (model%vtx(i), unit)
end do
if (present (verbose)) then
  if (verbose) then
    call vertex_table_write (model%vt, unit)
    call var_list_write (model%var_list, unit)
  end if
end if
end subroutine model_write

```

Accessing contents:

```

<Models: public>+≡
  public :: model_get_name

<Models: procedures>+≡
  function model_get_name (model) result (name)
    type(string_t) :: name
    type(model_t), intent(in) :: model
    name = model%name
  end function model_get_name

```

Retrieve the MD5 sum of a model (actually, of the model file).

```

<Models: public>+≡
  public :: model_get_md5sum

<Models: procedures>+≡
  function model_get_md5sum (model) result (md5sum)
    character(32) :: md5sum
    type(model_t), intent(in) :: model
    md5sum = model%md5sum
  end function model_get_md5sum

```

Retrieve a MD5 sum for the current model parameter values. This is done by writing them to a string, using default format.

```

<Models: public>+≡
  public :: model_get_parameters_md5sum

<Models: procedures>+≡
  function model_get_parameters_md5sum (model) result (par_md5sum)
    character(32) :: par_md5sum
    type(model_t), intent(in) :: model
    real(default), dimension(:), allocatable :: par
    integer :: unit
    call model_parameters_to_array (model, par)
    unit = free_unit ()
    open (unit, status="scratch", action="readwrite")
    write (unit, *) par
    rewind (unit)
  end function model_get_parameters_md5sum

```

```

    par_md5sum = md5sum (unit)
    close (unit)
end function model_get_parameters_md5sum

```

Retrieve the MD5 sum for the current polarization setup (aka whether particles are to be treated as potentially polarized)

```

<Models: public>+≡
    public :: model_get_polarized_md5sum

<Models: procedures>+≡
    function model_get_polarized_md5sum (model) result (pol_md5sum)
        character(32) :: pol_md5sum
        type(model_t), intent(in) :: model
        integer :: unit, i
        unit = free_unit ()
        open (unit, status="scratch", action="readwrite")
        if (size (model%prt) > 0) then
            do i = 1, size (model%prt)
                write (unit, *) &
                    char (particle_data_get_name (model%prt(i), .false.)), " ", &
                    particle_data_is_polarized (model%prt(i)), " "
                if (particle_data_has_antiparticle (model%prt(i))) write (unit, *) &
                    char (particle_data_get_name (model%prt(i), .true.)), " ", &
                    particle_data_is_polarized (model%prt(i), .true.), " "
            end do
        end if
        rewind (unit)
        pol_md5sum = md5sum (unit)
        close (unit)
    end function model_get_polarized_md5sum

```

Parameters are defined by an expression which may be constant or arbitrary.

```

<Models: interfaces>+≡
    interface model_set_parameter
        module procedure model_set_parameter_constant
        module procedure model_set_parameter_parse_node
    end interface

<Models: procedures>+≡
    subroutine model_set_parameter_constant (model, i, name, value)
        type(model_t), intent(inout), target :: model
        integer, intent(in) :: i
        type(string_t), intent(in) :: name
        real(default), intent(in) :: value
        logical, save, target :: known = .true.
        call parameter_init_independent_value (model%par(i), name, value)
        call var_list_append_real_ptr &
            (model%var_list, name, parameter_get_value_ptr (model%par(i)), known, &
            intrinsic=.true.)
    end subroutine model_set_parameter_constant

    subroutine model_set_parameter_parse_node (model, i, name, pn, constant)
        type(model_t), intent(inout), target :: model

```

```

integer, intent(in) :: i
type(string_t), intent(in) :: name
type(parse_node_t), intent(in), target :: pn
logical, intent(in) :: constant
logical, save, target :: known = .true.
if (constant) then
    call parameter_init_independent (model%par(i), name, pn)
else
    call parameter_init_derived (model%par(i), name, pn, model%var_list)
end if
call var_list_append_real_ptr &
    (model%var_list, name, parameter_get_value_ptr (model%par(i)), &
    is_known=known, locked=.not.constant, intrinsic=.true.)
end subroutine model_set_parameter_parse_node

subroutine model_set_parameter_external (model, i, name)
    type(model_t), intent(inout), target :: model
    integer, intent(in) :: i
    type(string_t), intent(in) :: name
    logical, save, target :: known = .true.
    call parameter_init_external (model%par(i), name)
    call var_list_append_real_ptr &
        (model%var_list, name, parameter_get_value_ptr (model%par(i)), &
        is_known=known, locked=.true., intrinsic=.true.)
end subroutine model_set_parameter_external

```

Return the pointer to a parameter

<Models: procedures>+≡

```

function model_get_parameter_ptr (model, par_name) result (par)
    type(parameter_t), pointer :: par
    type(model_t), intent(in), target :: model
    type(string_t), intent(in), optional :: par_name
    integer :: i
    par => null ()
    if (present (par_name)) then
        do i = 1, size (model%par)
            if (model%par(i)%name == par_name) then
                par => model%par(i); exit
            end if
        end do
        if (.not. associated (par)) then
            call msg_fatal (" Model '" // char (model%name) // "' // &
                " has no parameter '" // char (par_name) // "'")
        end if
    end if
end function model_get_parameter_ptr

```

Return the value of a particular parameter

<Models: public>+≡

```

public :: model_get_parameter_value

```

<Models: procedures>+≡

```

function model_get_parameter_value (model, par_name) result (val)

```

```

    real(default) :: val
    type(model_t), intent(in), target :: model
    type(string_t), intent(in), optional :: par_name
    val = parameter_get_value_ptr (model_get_parameter_ptr (model, par_name))
end function model_get_parameter_value

```

Return the number of parameters

```

<Models: public>+≡
    public :: model_get_n_parameters

<Models: procedures>+≡
    function model_get_n_parameters (model) result (n)
        integer :: n
        type(model_t), intent(in) :: model
        n = size (model%par)
    end function model_get_n_parameters

```

Transform the parameters into a single real-valued array. The first version uses the Fortran default kind, the second one the C default kind. (Usually, the two will be identical).

```

<Models: public>+≡
    public :: model_parameters_to_array

<Models: procedures>+≡
    subroutine model_parameters_to_array (model, array)
        type(model_t), intent(in) :: model
        real(default), dimension(:), allocatable :: array
        integer :: i
        if (allocated (array)) deallocate (array)
        allocate (array (size (model%par)))
        do i = 1, size (model%par)
            array(i) = model%par(i)%value
        end do
    end subroutine model_parameters_to_array

    subroutine model_parameters_to_c_array (model, array)
        type(model_t), intent(in) :: model
        real(c_default_float), dimension(:), allocatable :: array
        allocate (array (size (model%par)))
        array = model%par%value
    end subroutine model_parameters_to_c_array

    subroutine model_parameters_from_c_array (model, array)
        type(model_t), intent(inout) :: model
        real(c_default_float), dimension(:), intent(in) :: array
        if (size (array) == size (model%par)) then
            model%par%value = array
        else
            call msg_bug ("Model '" // char (model%name) // "': size mismatch " &
                // "in parameter array")
        end if
    end subroutine model_parameters_from_c_array

```

Rcalculate all derived parameters.

```

<Models: public>+≡
    public :: model_parameters_update

<Models: procedures>+≡
    subroutine model_parameters_update (model)
        type(model_t), intent(inout) :: model
        integer :: i
        real(default), dimension(:), allocatable :: par
        do i = 1, size (model%par)
            call parameter_reset_derived (model%par(i))
        end do
        if (associated (model% init_external_parameters)) then
            call model_parameters_to_c_array (model, par)
            call model% init_external_parameters (par)
            call model_parameters_from_c_array (model, par)
        end if
    end subroutine model_parameters_update

```

Initialize particle data with PDG long name and PDG code.

```

<Models: procedures>+≡
    subroutine model_init_particle (model, i, longname, pdg)
        type(model_t), intent(inout) :: model
        integer, intent(in) :: i
        type(string_t), intent(in) :: longname
        integer, intent(in) :: pdg
        type(pdg_array_t) :: aval
        call particle_data_init (model%prt(i), longname, pdg)
        aval = pdg
        call var_list_append_pdg_array &
            (model%var_list, longname, aval, locked=.true., intrinsic=.true.)
    end subroutine model_init_particle

```

Copy quantum numbers from another particle

```

<Models: procedures>+≡
    subroutine model_copy_particle_data (model, i, name_src)
        type(model_t), intent(inout) :: model
        integer, intent(in) :: i
        type(string_t), intent(in) :: name_src
        call particle_data_copy (model%prt(i), &
            model_get_particle_ptr (model, &
                model_get_particle_pdg (model, name_src)))
    end subroutine model_copy_particle_data

```

Set particle quantum numbers individually. Names get a * prepended.

```

<Models: procedures>+≡
    subroutine model_set_particle_data (model, i, &
        is_visible, is_parton, is_gauge, is_left_handed, is_right_handed, &
        name, anti, tex_name, tex_anti, &
        spin_type, isospin_type, charge_type, color_type, &
        mass_src, width_src)
        type(model_t), intent(inout) :: model

```



```

integer, intent(in) :: i
logical, intent(in), optional :: is_visible, is_parton, is_gauge
logical, intent(in), optional :: is_left_handed, is_right_handed
type(string_t), dimension(:), intent(in), optional :: name, anti
type(string_t), intent(in), optional :: tex_name, tex_anti
integer, intent(in), optional :: spin_type, isospin_type
integer, intent(in), optional :: charge_type, color_type
type(parameter_t), intent(in), optional, target :: mass_src, width_src
integer :: j
type(pdg_array_t) :: aval
logical, parameter :: is_stable = .true.
logical, parameter :: decays_isotropically = .false.
logical, parameter :: decays_diagonal = .false.
logical, parameter :: p_polarized = .false.
logical, parameter :: a_polarized = .false.
call particle_data_set (model%prt(i), &
    is_visible, is_parton, is_gauge, is_left_handed, is_right_handed, &
    is_stable, decays_isotropically, decays_diagonal, &
    is_stable, decays_isotropically, decays_diagonal, &
    p_polarized, a_polarized, &
    name, anti, tex_name, tex_anti, &
    spin_type, isospin_type, charge_type, color_type, &
    mass_src, width_src)
if (present (name)) then
    aval = particle_data_get_pdg (model%prt(i))
    do j = 1, size (name)
        call var_list_append_pdg_array &
            (model%var_list, name(j), aval, locked=.true., intrinsic=.true.)
    end do
end if
if (present (anti)) then
    aval = - particle_data_get_pdg (model%prt(i))
    do j = 1, size (anti)
        call var_list_append_pdg_array &
            (model%var_list, anti(j), aval, locked=.true., intrinsic=.true.)
    end do
end if
end subroutine model_set_particle_data

```

<Models: procedures>+≡

```

subroutine model_freeze_particle_data (model, i)
    type(model_t), intent(inout) :: model
    integer, intent(in) :: i
    call particle_data_freeze (model%prt(i))
end subroutine model_freeze_particle_data

```

Return a pointer to the particle-data object that belongs to the specified PDG code or name.

<Models: public>+≡

```

public :: model_get_particle_ptr

```

<Models: procedures>+≡

```

function model_get_particle_ptr (model, pdg) result (prt)
    type(particle_data_t), pointer :: prt

```

```

type(model_t), intent(in), target :: model
integer, intent(in) :: pdg
integer :: i
prt => null ()
if (pdg /= UNDEFINED) then
  do i = 1, size (model%prt)
    if (model%prt(i)%pdg == abs (pdg)) then
      prt => model%prt(i); exit
    end if
  end do
  if (.not. associated (prt)) then
    write (msg_buffer, "(1x,A,1x,I0)") "PDG code =", pdg
    call msg_message
    call msg_fatal (" Model '" // char (model%name) // "' // &
      " has no particle with this PDG code")
  end if
end if
end function model_get_particle_ptr

```

Test if a particle with the given PDG code exists in the model.

```

<Models: public>+≡
  public :: model_test_particle

<Models: procedures>+≡
  function model_test_particle (model, pdg) result (exists)
    logical :: exists
    type(particle_data_t), pointer :: prt
    type(model_t), intent(in), target :: model
    integer, intent(in) :: pdg
    integer :: i
    prt => null ()
    if (pdg /= UNDEFINED) then
      do i = 1, size (model%prt)
        if (model%prt(i)%pdg == abs (pdg)) then
          prt => model%prt(i); exit
        end if
      end do
      exists = associated(prt)
    else
      exists = .false.
    end if
  end function model_test_particle

```

Set the value, not the pointer. If the PDG code is not valid, do nothing.

```

<Models: public>+≡
  public :: model_set_particle_mass
  public :: model_set_particle_width

<Models: procedures>+≡
  subroutine model_set_particle_mass (model, pdg, mass)
    type(model_t), intent(inout) :: model
    integer, intent(in) :: pdg
    real(default), intent(in) :: mass
    type(particle_data_t), pointer :: prt

```

```

    prt => model_get_particle_ptr (model, pdg)
    if (associated (prt)) call particle_data_set_mass (prt, mass)
end subroutine model_set_particle_mass

subroutine model_set_particle_width (model, pdg, width)
    type(model_t), intent(inout) :: model
    integer, intent(in) :: pdg
    real(default), intent(in) :: width
    type(particle_data_t), pointer :: prt
    prt => model_get_particle_ptr (model, pdg)
    if (associated (prt)) call particle_data_set_width (prt, width)
end subroutine model_set_particle_width

```

Return the PDG code that matches a particle name.

<Models: public>+≡

```
public :: model_get_particle_pdg
```

<Models: procedures>+≡

```

function model_get_particle_pdg (model, name) result (pdg)
    integer :: pdg
    type(model_t), intent(in), target :: model
    type(string_t), intent(in) :: name
    integer :: i
    pdg = UNDEFINED
    do i = 1, size (model%prt)
        if (model%prt(i)%longname == name) then
            pdg = particle_data_get_pdg (model%prt(i)); exit
        else if (any (model%prt(i)%name == name)) then
            pdg = particle_data_get_pdg (model%prt(i)); exit
        else if (any (model%prt(i)%anti == name)) then
            pdg = - particle_data_get_pdg (model%prt(i)); exit
        end if
    end do
    if (pdg == UNDEFINED) then
        write (msg_buffer, "(1x,A,1x,A)" "Particle name =", char (name)
        call msg_message
        call msg_fatal (" Model '" // char (model%name) // "' // &
            " has no particle with this name")
    end if
end function model_get_particle_pdg

```

Return a pointer to the variable list.

<Models: public>+≡

```
public :: model_get_var_list_ptr
```

<Models: procedures>+≡

```

function model_get_var_list_ptr (model) result (var_list)
    type(var_list_t), pointer :: var_list
    type(model_t), intent(in), target :: model
    var_list => model%var_list
end function model_get_var_list_ptr

```

Vertex definition.

```
<Models: interfaces>+≡
  interface model_set_vertex
    module procedure model_set_vertex_pdg
    module procedure model_set_vertex_names
  end interface

<Models: procedures>+≡
  subroutine model_set_vertex_pdg (model, i, pdg)
    type(model_t), intent(inout), target :: model
    integer, intent(in) :: i
    integer, dimension(:), intent(in) :: pdg
    call vertex_init (model%vtx(i), pdg, model)
  end subroutine model_set_vertex_pdg

  subroutine model_set_vertex_names (model, i, name)
    type(model_t), intent(inout), target :: model
    integer, intent(in) :: i
    type(string_t), dimension(:), intent(in) :: name
    integer, dimension(size(name)) :: pdg
    integer :: j
    do j = 1, size (name)
      pdg(j) = model_get_particle_pdg (model, name(j))
    end do
    call vertex_init (model%vtx(i), pdg, model)
  end subroutine model_set_vertex_names
```

Lookup functions

```
<Models: public>+≡
  public :: model_match_vertex

<Models: procedures>+≡
  subroutine model_match_vertex (model, pdg1, pdg2, pdg3)
    type(model_t), intent(in) :: model
    integer, intent(in) :: pdg1, pdg2
    integer, dimension(:), allocatable, intent(out) :: pdg3
    call vertex_table_match (model%vt, pdg1, pdg2, pdg3)
  end subroutine model_match_vertex

<Models: public>+≡
  public :: model_check_vertex

<Models: procedures>+≡
  function model_check_vertex (model, pdg1, pdg2, pdg3) result (flag)
    logical :: flag
    type(model_t), intent(in) :: model
    integer, intent(in) :: pdg1, pdg2, pdg3
    flag = vertex_table_check (model%vt, pdg1, pdg2, pdg3)
  end function model_check_vertex
```

6.1.8 Reading models from file

This procedure defines the model-file syntax for the parser, returning an internal file (ifile).

Note that arithmetic operators are defined as keywords in the expression syntax, so we exclude them here.

(Models: procedures)+≡

```

subroutine define_model_file_syntax (ifile)
  type(ifile_t), intent(inout) :: ifile
  call ifile_append (ifile, "SEQ model_def = model_name_def " // &
    "parameters derived_pars external_pars particles vertices")
  call ifile_append (ifile, "SEQ model_name_def = model model_name")
  call ifile_append (ifile, "KEY model")
  call ifile_append (ifile, "QUO model_name = '""'...'""')
  call ifile_append (ifile, "SEQ parameters = parameter_def*")
  call ifile_append (ifile, "SEQ parameter_def = parameter par_name " // &
    "'=' any_real_value")
  call ifile_append (ifile, "ALT any_real_value = " &
    // "neg_real_value | pos_real_value | real_value")
  call ifile_append (ifile, "SEQ neg_real_value = '-' real_value")
  call ifile_append (ifile, "SEQ pos_real_value = '+' real_value")
  call ifile_append (ifile, "KEY parameter")
  call ifile_append (ifile, "IDE par_name")
!   call ifile_append (ifile, "KEY '='")
!   call ifile_append (ifile, "REA par_value")
  call ifile_append (ifile, "SEQ derived_pars = derived_def*")
  call ifile_append (ifile, "SEQ derived_def = derived par_name " // &
    "'=' expr")
  call ifile_append (ifile, "KEY derived")
  call ifile_append (ifile, "SEQ external_pars = external_def*")
  call ifile_append (ifile, "SEQ external_def = external par_name")
  call ifile_append (ifile, "KEY external")
  call ifile_append (ifile, "SEQ particles = particle_def*")
  call ifile_append (ifile, "SEQ particle_def = particle prt_longname " // &
    "prt_pdg prt_details")
  call ifile_append (ifile, "KEY particle")
  call ifile_append (ifile, "IDE prt_longname")
  call ifile_append (ifile, "INT prt_pdg")
  call ifile_append (ifile, "ALT prt_details = prt_src | prt_properties")
  call ifile_append (ifile, "SEQ prt_src = like prt_longname prt_properties")
  call ifile_append (ifile, "KEY like")
  call ifile_append (ifile, "SEQ prt_properties = prt_property*")
  call ifile_append (ifile, "ALT prt_property = " // &
    "parton | invisible | gauge | left | right | " // &
    "prt_name | prt_anti | prt_tex_name | prt_tex_anti | " // &
    "prt_spin | prt_isospin | prt_charge | " // &
    "prt_color | prt_mass | prt_width")
  call ifile_append (ifile, "KEY parton")
  call ifile_append (ifile, "KEY invisible")
  call ifile_append (ifile, "KEY gauge")
  call ifile_append (ifile, "KEY left")
  call ifile_append (ifile, "KEY right")
  call ifile_append (ifile, "SEQ prt_name = name name_def+")
  call ifile_append (ifile, "SEQ prt_anti = anti name_def+")
  call ifile_append (ifile, "SEQ prt_tex_name = tex_name name_def")
  call ifile_append (ifile, "SEQ prt_tex_anti = tex_anti name_def")
  call ifile_append (ifile, "KEY name")
  call ifile_append (ifile, "KEY anti")

```

```

call ifile_append (ifile, "KEY tex_name")
call ifile_append (ifile, "KEY tex_anti")
call ifile_append (ifile, "ALT name_def = name_string | name_id")
call ifile_append (ifile, "QUO name_string = '""'...'""')
call ifile_append (ifile, "IDE name_id")
call ifile_append (ifile, "SEQ prt_spin = spin frac")
call ifile_append (ifile, "KEY spin")
!   call ifile_append (ifile, "SEQ frac = signed_int div?")
!   call ifile_append (ifile, "ALT signed_int = " &
!       // "neg_int | pos_int | integer_literal")
!   call ifile_append (ifile, "SEQ neg_int = '-' integer_literal")
!   call ifile_append (ifile, "SEQ pos_int = '+' integer_literal")
!   call ifile_append (ifile, "KEY '-'")
!   call ifile_append (ifile, "KEY '+'")
!   call ifile_append (ifile, "INT int")
!   call ifile_append (ifile, "SEQ div = '/' integer_literal")
!   call ifile_append (ifile, "KEY '/'")
call ifile_append (ifile, "SEQ prt_isospin = isospin frac")
call ifile_append (ifile, "KEY isospin")
call ifile_append (ifile, "SEQ prt_charge = charge frac")
call ifile_append (ifile, "KEY charge")
call ifile_append (ifile, "SEQ prt_color = color integer_literal")
call ifile_append (ifile, "KEY color")
call ifile_append (ifile, "SEQ prt_mass = mass par_name")
call ifile_append (ifile, "KEY mass")
call ifile_append (ifile, "SEQ prt_width = width par_name")
call ifile_append (ifile, "KEY width")
call ifile_append (ifile, "SEQ vertices = vertex_def*")
call ifile_append (ifile, "SEQ vertex_def = vertex name_def+")
call ifile_append (ifile, "KEY vertex")
call define_expr_syntax (ifile, particles=.false., analysis=.false.)
end subroutine define_model_file_syntax

```

The model-file syntax and lexer are fixed, therefore stored as module variables:

```

<Models: variables>≡
    type(syntax_t), target, save :: syntax_model_file

```

```

<Models: public>+≡
    public :: syntax_model_file_init

```

```

<Models: procedures>+≡
    subroutine syntax_model_file_init ()
        type(ifile_t) :: ifile
        call define_model_file_syntax (ifile)
        call syntax_init (syntax_model_file, ifile)
        call ifile_final (ifile)
    end subroutine syntax_model_file_init

```

```

<Models: procedures>+≡
    subroutine lexer_init_model_file (lexer)
        type(lexer_t), intent(out) :: lexer
        call lexer_init (lexer, &
            comment_chars = "#!", &

```

```

        quote_chars = '"{', &
        quote_match = '"}', &
        single_chars = ":( )", &
        special_class = (/ "+-*/^", "<=> " /) , &
        keyword_list = syntax_get_keyword_list_ptr (syntax_model_file))
end subroutine lexer_init_model_file

```

<Models: public>+≡

```

    public :: syntax_model_file_final

```

<Models: procedures>+≡

```

    subroutine syntax_model_file_final ()
        call syntax_final (syntax_model_file)
    end subroutine syntax_model_file_final

```

<Models: public>+≡

```

    public :: syntax_model_file_write

```

<Models: procedures>+≡

```

    subroutine syntax_model_file_write (unit)
        integer, intent(in), optional :: unit
        call syntax_write (syntax_model_file, unit)
    end subroutine syntax_model_file_write

```

<Models: public>+≡

```

    public :: model_read

```

<Models: procedures>+≡

```

    subroutine model_read (model, filename, os_data, exist)
        type(model_t), intent(out), target :: model
        type(string_t), intent(in) :: filename
        type(os_data_t), intent(in) :: os_data
        logical, intent(out) :: exist
        type(string_t) :: file
        type(stream_t), target :: stream
        type(lexer_t) :: lexer
        integer :: unit
        character(32) :: model_md5sum
        type(parse_tree_t) :: parse_tree
        type(parse_node_t), pointer :: nd_model_def, nd_model_name_def
        type(parse_node_t), pointer :: nd_model_arg
        type(parse_node_t), pointer :: nd_parameters, nd_derived_pars
        type(parse_node_t), pointer :: nd_external_pars
        type(parse_node_t), pointer :: nd_particles, nd_vertices
        type(string_t) :: model_name, lib_name
        integer :: n_par, n_der, n_ext, n_prt, n_vtx
        real(c_default_float), dimension(:), allocatable :: par
        integer :: i
        type(parse_node_t), pointer :: nd_par_def
        type(parse_node_t), pointer :: nd_der_def
        type(parse_node_t), pointer :: nd_ext_def
        type(parse_node_t), pointer :: nd_prt
        type(parse_node_t), pointer :: nd_vtx
        type(pdg_array_t) :: prt_undefined
        file = filename
    end subroutine model_read

```

```

inquire (file=char(file), exist=exist)
if ((.not. exist) .and. (.not. os_data%use_testfiles)) then
    file = os_data%whizard_modelpath_local // "/" // filename
    inquire (file = char (file), exist = exist)
end if
if (.not. exist) then
    file = os_data%whizard_modelpath // "/" // filename
    inquire (file = char (file), exist = exist)
end if
if (.not. exist) then
    call msg_fatal ("Model file '" // char (filename) // "' not found")
    return
end if
call msg_message ("Reading model file '" // char (file) // "'")
call lexer_init_model_file (lexer)
unit = free_unit ()
open (file=char(file), unit=unit, action="read", status="old")
model_md5sum = md5sum (unit)
close (unit)
call stream_init (stream, char (file))
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_model_file, lexer)
call stream_final (stream)
call lexer_final (lexer)
!    call parse_tree_write (parse_tree)
nd_model_def => parse_tree_get_root_ptr (parse_tree)
nd_model_name_def => parse_node_get_sub_ptr (nd_model_def)
model_name = parse_node_get_string &
    (parse_node_get_sub_ptr (nd_model_name_def, 2))
nd_parameters => parse_node_get_next_ptr (nd_model_name_def)
if (associated (nd_parameters)) then
    if (parse_node_get_rule_key (nd_parameters) == "parameters") then
        n_par = parse_node_get_n_sub (nd_parameters)
        nd_par_def => parse_node_get_sub_ptr (nd_parameters)
        nd_derived_pars => parse_node_get_next_ptr (nd_parameters)
    else
        n_par = 0
        nd_derived_pars => nd_parameters
        nd_parameters => null ()
    end if
else
    n_par = 0
    nd_derived_pars => null ()
end if
if (associated (nd_derived_pars)) then
    if (parse_node_get_rule_key (nd_derived_pars) == "derived_pars") then
        n_der = parse_node_get_n_sub (nd_derived_pars)
        nd_der_def => parse_node_get_sub_ptr (nd_derived_pars)
        nd_external_pars => parse_node_get_next_ptr (nd_derived_pars)
    else
        n_der = 0
        nd_external_pars => nd_derived_pars
        nd_derived_pars => null ()
    end if
end if

```



```

else
    n_der = 0
    nd_external_pars => null ()
end if
if (associated (nd_external_pars)) then
    if (parse_node_get_rule_key (nd_external_pars) == "external_pars") then
        n_ext = parse_node_get_n_sub (nd_external_pars)
        lib_name = "external." // model_name
        nd_ext_def => parse_node_get_sub_ptr (nd_external_pars)
        nd_particles => parse_node_get_next_ptr (nd_external_pars)
    else
        n_ext = 0
        lib_name = ""
        nd_particles => nd_external_pars
        nd_external_pars => null ()
    end if
else
    n_ext = 0
    lib_name = ""
    nd_particles => null ()
end if
if (associated (nd_particles)) then
    if (parse_node_get_rule_key (nd_particles) == "particles") then
        n_prt = parse_node_get_n_sub (nd_particles)
        nd_prt => parse_node_get_sub_ptr (nd_particles)
        nd_vertices => parse_node_get_next_ptr (nd_particles)
    else
        n_prt = 0
        nd_vertices => nd_particles
        nd_particles => null ()
    end if
else
    n_prt = 0
    nd_vertices => null ()
end if
if (associated (nd_vertices)) then
    n_vtx = parse_node_get_n_sub (nd_vertices)
    nd_vtx => parse_node_get_sub_ptr (nd_vertices)
else
    n_vtx = 0
end if
call model_init (model, model_name, lib_name, os_data, &
    n_par + n_der + n_ext, n_prt, n_vtx)
model%md5sum = model_md5sum
do i = 1, n_par
    call model_read_parameter (model, i, nd_par_def)
    nd_par_def => parse_node_get_next_ptr (nd_par_def)
end do
do i = n_par + 1, n_par + n_der
    call model_read_derived (model, i, nd_der_def)
    nd_der_def => parse_node_get_next_ptr (nd_der_def)
end do
do i = n_par + n_der + 1, n_par + n_der + n_ext
    call model_read_external (model, i, nd_ext_def)

```

```

        nd_ext_def => parse_node_get_next_ptr (nd_ext_def)
    end do
    if (associated (model% init_external_parameters)) then
        call model_parameters_to_c_array (model, par)
        call model% init_external_parameters (par)
        call model_parameters_from_c_array (model, par)
    end if
    prt_undefined = UNDEFINED
    call var_list_append_pdg_array &
        (model%var_list, var_str ("particle"), &
        prt_undefined, locked = .true., intrinsic=.true.)
    do i = 1, n_prt
        call model_read_particle (model, i, nd_prt)
        nd_prt => parse_node_get_next_ptr (nd_prt)
    end do
    do i = 1, n_vtx
        call model_read_vertex (model, i, nd_vtx)
        nd_vtx => parse_node_get_next_ptr (nd_vtx)
    end do
    call parse_tree_final (parse_tree)
    call var_list_append_pdg_array &
        (model%var_list, var_str ("charged"), &
        particle_data_get_charged_pdg (model%prt), locked = .true., &
        intrinsic=.true.)
    call var_list_append_pdg_array &
        (model%var_list, var_str ("colored"), &
        particle_data_get_colored_pdg (model%prt), locked = .true., &
        intrinsic=.true.)
end subroutine model_read

```

Parameters are real values (literal) with an optional unit.

<Models: procedures>+≡

```

subroutine model_read_parameter (model, i, node)
    type(model_t), intent(inout), target :: model
    integer, intent(in) :: i
    type(parse_node_t), intent(in), target :: node
    type(parse_node_t), pointer :: node_name, node_val
    type(string_t) :: name
    node_name => parse_node_get_sub_ptr (node, 2)
    name = parse_node_get_string (node_name)
    node_val => parse_node_get_next_ptr (node_name, 2)
    call model_set_parameter (model, i, name, node_val, constant=.true.)
end subroutine model_read_parameter

```

Derived parameters have any numeric expression as their definition.

<Models: procedures>+≡

```

subroutine model_read_derived (model, i, node)
    type(model_t), intent(inout), target :: model
    integer, intent(in) :: i
    type(parse_node_t), intent(in), target :: node
    type(string_t) :: name
    type(parse_node_t), pointer :: pn_expr
    name = parse_node_get_string (parse_node_get_sub_ptr (node, 2))

```

```

pn_expr => parse_node_get_sub_ptr (node, 4)
call model_set_parameter (model, i, name, pn_expr, constant=.false.)
end subroutine model_read_derived

```

External parameters have no definition; they are handled by an external library.

(Models: procedures)+≡

```

subroutine model_read_external (model, i, node)
  type(model_t), intent(inout), target :: model
  integer, intent(in) :: i
  type(parse_node_t), intent(in), target :: node
  type(string_t) :: name
  name = parse_node_get_string (parse_node_get_sub_ptr (node, 2))
  call model_set_parameter_external (model, i, name)
end subroutine model_read_external

```

(Models: procedures)+≡

```

subroutine model_read_particle (model, i, node)
  type(model_t), intent(inout) :: model
  integer, intent(in) :: i
  type(parse_node_t), intent(in) :: node
  type(parse_node_t), pointer :: nd_src, nd_props, nd_prop
  type(string_t) :: longname
  integer :: pdg
  type(string_t) :: name_src
  type(string_t), dimension(:), allocatable :: name
  longname = parse_node_get_string (parse_node_get_sub_ptr (node, 2))
  pdg = parse_node_get_integer (parse_node_get_sub_ptr (node, 3))
  call model_init_particle (model, i, longname, pdg)
  nd_src => parse_node_get_sub_ptr (node, 4)
  if (associated (nd_src)) then
    if (parse_node_get_rule_key (nd_src) == "prt_src") then
      name_src = parse_node_get_string (parse_node_get_sub_ptr (nd_src, 2))
      call model_copy_particle_data (model, i, name_src)
      nd_props => parse_node_get_sub_ptr (nd_src, 3)
    else
      nd_props => nd_src
    end if
  end if
  nd_prop => parse_node_get_sub_ptr (nd_props)
  do while (associated (nd_prop))
    select case (char (parse_node_get_rule_key (nd_prop)))
    case ("invisible")
      call model_set_particle_data (model, i, is_visible=.false.)
    case ("parton")
      call model_set_particle_data (model, i, is_parton=.true.)
    case ("gauge")
      call model_set_particle_data (model, i, is_gauge=.true.)
    case ("left")
      call model_set_particle_data (model, i, is_left_handed=.true.)
    case ("right")
      call model_set_particle_data (model, i, is_right_handed=.true.)
    case ("prt_name")
      call read_names (nd_prop, name)
      call model_set_particle_data (model, i, name=name)
    end select
    nd_prop => parse_node_get_sub_ptr (nd_prop, 1)
  end do
end subroutine model_read_particle

```

```

case ("prt_anti")
  call read_names (nd_prop, name)
  call model_set_particle_data (model, i, anti=name)
case ("prt_tex_name")
  call model_set_particle_data (model, i, &
    tex_name = parse_node_get_string &
    (parse_node_get_sub_ptr (nd_prop, 2)))
case ("prt_tex_anti")
  call model_set_particle_data (model, i, &
    tex_anti = parse_node_get_string &
    (parse_node_get_sub_ptr (nd_prop, 2)))
case ("prt_spin")
  call model_set_particle_data (model, i, &
    spin_type = read_frac &
    (parse_node_get_sub_ptr (nd_prop, 2), 2))
case ("prt_isospin")
  call model_set_particle_data (model, i, &
    isospin_type = read_frac &
    (parse_node_get_sub_ptr (nd_prop, 2), 2))
case ("prt_charge")
  call model_set_particle_data (model, i, &
    charge_type = read_frac &
    (parse_node_get_sub_ptr (nd_prop, 2), 3))
case ("prt_color")
  call model_set_particle_data (model, i, &
    color_type = parse_node_get_integer &
    (parse_node_get_sub_ptr (nd_prop, 2)))
case ("prt_mass")
  call model_set_particle_data (model, i, &
    mass_src = model_get_parameter_ptr &
    (model, parse_node_get_string &
    (parse_node_get_sub_ptr (nd_prop, 2))))
case ("prt_width")
  call model_set_particle_data (model, i, &
    width_src = model_get_parameter_ptr &
    (model, parse_node_get_string &
    (parse_node_get_sub_ptr (nd_prop, 2))))
case default
  call msg_bug (" Unknown particle property '" &
    // char (parse_node_get_rule_key (nd_prop)) // "'")
end select
if (allocated (name)) deallocate (name)
nd_prop => parse_node_get_next_ptr (nd_prop)
end do
end if
call model_freeze_particle_data (model, i)
end subroutine model_read_particle

```

(Models: procedures)+≡

```

subroutine model_read_vertex (model, i, node)
  type(model_t), intent(inout) :: model
  integer, intent(in) :: i
  type(parse_node_t), intent(in) :: node
  type(string_t), dimension(:), allocatable :: name

```

```

    call read_names (node, name)
    call model_set_vertex (model, i, name)
end subroutine model_read_vertex

```

(Models: procedures)+≡

```

subroutine read_names (node, name)
  type(parse_node_t), intent(in) :: node
  type(string_t), dimension(:), allocatable, intent(inout) :: name
  type(parse_node_t), pointer :: nd_name
  integer :: n_names, i
  n_names = parse_node_get_n_sub (node) - 1
  allocate (name (n_names))
  nd_name => parse_node_get_sub_ptr (node, 2)
  do i = 1, n_names
    name(i) = parse_node_get_string (nd_name)
    nd_name => parse_node_get_next_ptr (nd_name)
  end do
end subroutine read_names

```

(Models: procedures)+≡

```

function read_frac (nd_frac, base) result (qn_type)
  integer :: qn_type
  type(parse_node_t), intent(in) :: nd_frac
  integer, intent(in) :: base
  type(parse_node_t), pointer :: nd_num, nd_den
  integer :: num, den
  nd_num => parse_node_get_sub_ptr (nd_frac)
  nd_den => parse_node_get_next_ptr (nd_num)
  select case (char (parse_node_get_rule_key (nd_num)))
  case ("integer_literal")
    num = parse_node_get_integer (nd_num)
  case ("neg_int")
    num = - parse_node_get_integer (parse_node_get_sub_ptr (nd_num, 2))
  case ("pos_int")
    num = parse_node_get_integer (parse_node_get_sub_ptr (nd_num, 2))
  case default
    call parse_tree_bug (nd_num, "int|neg_int|pos_int")
  end select
  if (associated (nd_den)) then
    den = parse_node_get_integer (parse_node_get_sub_ptr (nd_den, 2))
  else
    den = 1
  end if
  if (den == 1) then
    qn_type = sign (1 + abs (num) * base, num)
  else if (den == base) then
    qn_type = sign (abs (num) + 1, num)
  else
    call parse_node_write_rec (nd_frac)
    call msg_fatal (" Fractional quantum number: wrong denominator")
  end if
end function read_frac

```

6.1.9 Model list

List of currently active models

```
<Models: types>+≡  
  type :: model_entry_t  
    type(model_t) :: model  
    type(model_entry_t), pointer :: next => null ()  
  end type model_entry_t
```

```
<Models: types>+≡  
  type :: model_list_t  
    type(model_entry_t), pointer :: first => null ()  
    type(model_entry_t), pointer :: last => null ()  
  end type model_list_t
```

The model list is stored as a module variable. Thus, the operations acting on the list do not have the model list as an argument.

```
<Models: variables>+≡  
  type(model_list_t), target, save :: model_list
```

Write an account of the model list.

```
<Models: public>+≡  
  public :: model_list_write  
  
<Models: procedures>+≡  
  subroutine model_list_write (unit, verbose)  
    integer, intent(in), optional :: unit  
    logical, intent(in), optional :: verbose  
    type(model_entry_t), pointer :: current  
    integer :: u  
    u = output_unit (unit); if (u < 0) return  
    write (u, *) "List of models:"  
    current => model_list%first  
    if (associated (current)) then  
      do while (associated (current))  
        write (u, *)  
        call model_write (current%model, unit, verbose)  
        current => current%next  
      end do  
    else  
      write (u, *) " [empty]"  
    end if  
  end subroutine model_list_write
```

Add a new model with given `name` to the list, if it does not yet exist. If successful, return a pointer to the new model.

```
<Models: procedures>+≡  
  subroutine model_list_add (name, os_data, n_par, n_prt, n_vtx, model)  
    type(string_t), intent(in) :: name  
    type(os_data_t), intent(in) :: os_data  
    integer, intent(in) :: n_par, n_prt, n_vtx  
    type(model_t), pointer :: model
```

```

type(model_entry_t), pointer :: current
if (model_list_model_exists (name)) then
    model => null ()
else
    allocate (current)
    if (associated (model_list%first)) then
        model_list%last%next => current
    else
        model_list%first => current
    end if
    model_list%last => current
    model => current%model
    call model_init (model, name, var_str (""), os_data, &
        n_par, n_prt, n_vtx)
end if
end subroutine model_list_add

```

Read a new model from file and add to the list, if it does not yet exist. Finalize the model by allocating the vertex table. Return a pointer to the new model. If unsuccessful, return the original pointer.

```

<Models: public>+≡
    public :: model_list_read_model

<Models: procedures>+≡
    subroutine model_list_read_model (name, filename, os_data, model)
        type(string_t), intent(in) :: name, filename
        type(os_data_t), intent(in) :: os_data
        type(model_t), pointer :: model
        type(model_entry_t), pointer :: current
        logical :: exist
        if (.not. model_list_model_exists (name)) then
            allocate (current)
            call model_read (current%model, filename, os_data, exist)
            if (.not. exist) return
            if (current%model%name /= name) then
                call msg_fatal ("Model file '" // char (filename) // &
                    "' contains model '" // char (current%model%name) // &
                    "' instead of '" // char (name) // "'")
                call model_final (current%model); deallocate (current)
                return
            end if
            if (associated (model_list%first)) then
                model_list%last%next => current
            else
                model_list%first => current
            end if
            model_list%last => current
            call vertex_table_init &
                (current%model%vt, current%model%prt, current%model%vtx)
            model => current%model
        else
            model => model_list_get_model_ptr (name)
        end if
    end subroutine model_list_read_model

```

Check if a model exists by examining the list

```
<Models: public>+≡
    public :: model_list_model_exists

<Models: procedures>+≡
    function model_list_model_exists (name) result (exists)
        logical :: exists
        type(string_t), intent(in) :: name
        type(model_entry_t), pointer :: current
        current => model_list%first
        do while (associated (current))
            if (current%model%name == name) then
                exists = .true.
                return
            end if
            current => current%next
        end do
        exists = .false.
    end function model_list_model_exists
```

Return a pointer to a named model

```
<Models: public>+≡
    public :: model_list_get_model_ptr

<Models: procedures>+≡
    function model_list_get_model_ptr (name) result (model)
        type(model_t), pointer :: model
        type(string_t), intent(in) :: name
        type(model_entry_t), pointer :: current
        current => model_list%first
        do while (associated (current))
            if (current%model%name == name) then
                model => current%model
                return
            end if
            current => current%next
        end do
        model => null ()
    end function model_list_get_model_ptr
```

Delete the list of models

```
<Models: public>+≡
    public :: model_list_final

<Models: procedures>+≡
    subroutine model_list_final ()
        type(model_entry_t), pointer :: current
        model_list%last => null ()
        do while (associated (model_list%first))
            current => model_list%first
            model_list%first => model_list%first%next
            call model_final (current%model)
            deallocate (current)
```



```

        end do
    end subroutine model_list_final

```

6.1.10 Test

```

<Models: public>+≡
    public :: models_test

<Models: procedures>+≡
    subroutine models_test ()
        type(os_data_t), pointer :: os_data => null ()
        call syntax_model_file_init ()
        call syntax_write (syntax_model_file)
        print *
        allocate (os_data)
        call os_data_init (os_data)
        call models_test1 (os_data)
        call models_test2 (os_data)
        !!! Try to catch the gfortran 4.5.0+(?) seg fault
        !!! call model_list_write (verbose=.true.)
        call model_list_write ()
        call model_list_final ()
        call syntax_model_file_final ()
        deallocate (os_data)
    end subroutine models_test

    subroutine models_test1 (os_data)
        type(os_data_t), intent(in) :: os_data
        type(model_t), pointer :: model
        type(string_t) :: model_name
        type(string_t) :: x_longname
        type(string_t), dimension(2) :: parname
        type(string_t), dimension(2) :: x_name
        type(string_t), dimension(1) :: x_anti
        type(string_t) :: x_tex_name, x_tex_anti
        type(string_t) :: y_longname
        type(string_t), dimension(2) :: y_name
        type(string_t) :: y_tex_name
        model_name = "Test model"
        call model_list_add (model_name, os_data, 2, 2, 3, model)
        parname(1) = "mx"
        parname(2) = "coup"
        call model_set_parameter (model, 1, parname(1), 10._default)
        call model_set_parameter (model, 2, parname(2), 1.3_default)
        print *
        x_longname = "X_LEPTON"
        x_name(1) = "X"
        x_name(2) = "x"
        x_anti(1) = "Xbar"
        x_tex_name = "X^+"
        x_tex_anti = "X^-"
        call model_init_particle (model, 1, x_longname, 99)
        call model_set_particle_data (model, 1, &

```

```

        .true., .false., .false., .false., .false., &
        x_name, x_anti, x_tex_name, x_tex_anti, &
        SPINOR, -3, 2, 1, model_get_parameter_ptr (model, parname(1)))
y_longname = "Y_COLORON"
y_name(1) = "Y"
y_name(2) = "yc"
y_tex_name = "Y^0"
call model_init_particle (model, 2, y_longname, 97)
call model_set_particle_data (model, 2, &
        .false., .false., .true., .false., .false., &
        name=y_name, tex_name=y_tex_name, &
        spin_type=SCALAR, isospin_type=2, charge_type=1, color_type=8)
call model_set_vertex (model, 1, (/ 99, 99, 99 /))
call model_set_vertex (model, 2, (/ 99, 99, 99, 99 /))
call model_set_vertex (model, 3, (/ 99, 97, 99 /))
end subroutine models_test1

subroutine models_test2 (os_data)
    type(os_data_t), intent(in) :: os_data
    type(string_t) :: name, filename
    type(model_t), pointer :: model
    name = "SM"
    filename = "SM.mdl"
    call model_list_read_model (name, filename, os_data, model)
end subroutine models_test2

```

Chapter 7

Quantum Numbers

We introduce separate types and modules for particle quantum numbers and use them for defining independent particles and entangled states.

helicities Types and methods for spin density matrices.

colors Dealing with colored particles, using the color-flow representation.

flavors PDG codes and particle properties, depends on the model.

quantum_states Quantum numbers and density matrices for entangled particle systems.

7.1 Helicities

This module defines types and tools for dealing with helicity information.

```
<helicities.f90>≡  
  <File header>  
  
  module helicities  
  
    <Use file utils>  
  
    <Standard module head>  
  
    <Helicities: public>  
  
    <Helicities: types>  
  
    <Helicities: interfaces>  
  
    contains  
  
    <Helicities: procedures>  
  
  end module helicities
```

7.1.1 Helicity types

Helicities may be defined or undefined, corresponding to a polarized or unpolarized state. Each helicity is actually a pair of helicities, corresponding to an entry in the spin density matrix. Obviously, diagonal entries are distinguished. In addition, we have a ghost flag that would apply to FP ghosts in particular.

```
<Helicities: public>≡  
  public :: helicity_t  
  
<Helicities: types>≡  
  type :: helicity_t  
    private  
    logical :: defined = .false.  
    integer :: h1, h2  
    logical :: ghost = .false.  
  end type helicity_t
```

Initializers:

```
<Helicities: public>+≡  
  public :: helicity_init  
  
<Helicities: interfaces>≡  
  interface helicity_init  
    module procedure helicity_init0, helicity_init0g  
    module procedure helicity_init1, helicity_init1g  
    module procedure helicity_init2, helicity_init2g  
  end interface
```

```

<Helicities: procedures>+≡
  elemental subroutine helicity_init0 (hel)
    type(helicity_t), intent(out) :: hel
  end subroutine helicity_init0

  elemental subroutine helicity_init0g (hel, ghost)
    type(helicity_t), intent(out) :: hel
    logical, intent(in) :: ghost
    hel%ghost = ghost
  end subroutine helicity_init0g

  elemental subroutine helicity_init1 (hel, h)
    type(helicity_t), intent(out) :: hel
    integer, intent(in) :: h
    hel%defined = .true.
    hel%h1 = h
    hel%h2 = h
  end subroutine helicity_init1

  elemental subroutine helicity_init1g (hel, h, ghost)
    type(helicity_t), intent(out) :: hel
    integer, intent(in) :: h
    logical, intent(in) :: ghost
    call helicity_init1 (hel, h)
    hel%ghost = ghost
  end subroutine helicity_init1g

  elemental subroutine helicity_init2 (hel, h2, h1)
    type(helicity_t), intent(out) :: hel
    integer, intent(in) :: h1, h2
    hel%defined = .true.
    hel%h2 = h2
    hel%h1 = h1
  end subroutine helicity_init2

  elemental subroutine helicity_init2g (hel, h2, h1, ghost)
    type(helicity_t), intent(out) :: hel
    integer, intent(in) :: h1, h2
    logical, intent(in) :: ghost
    call helicity_init2 (hel, h2, h1)
    hel%ghost = ghost
  end subroutine helicity_init2g

```

Set the ghost property separately:

```

<Helicities: public>+≡
  public :: helicity_set_ghost

<Helicities: procedures>+≡
  elemental subroutine helicity_set_ghost (hel, ghost)
    type(helicity_t), intent(inout) :: hel
    logical, intent(in) :: ghost
    hel%ghost = ghost
  end subroutine helicity_set_ghost

```

Undefine:

```
<Helicities: public>+≡
    public :: helicity_undefine

<Helicities: procedures>+≡
    elemental subroutine helicity_undefine (hel)
        type(helicity_t), intent(inout) :: hel
        hel%defined = .false.
        hel%ghost = .false.
    end subroutine helicity_undefine
```

Diagonalize by removing the second entry (use with care!)

```
<Helicities: public>+≡
    public :: helicity_diagonalize

<Helicities: procedures>+≡
    elemental subroutine helicity_diagonalize (hel)
        type(helicity_t), intent(inout) :: hel
        hel%h2 = hel%h1
    end subroutine helicity_diagonalize
```

Output (no linebreak). No output if undefined.

```
<Helicities: public>+≡
    public :: helicity_write

<Helicities: procedures>+≡
    subroutine helicity_write (hel, unit)
        type(helicity_t), intent(in) :: hel
        integer, intent(in), optional :: unit
        integer :: u
        u = output_unit (unit); if (u < 0) return
        if (hel%defined) then
            if (hel%ghost) then
                write (u, "(A)", advance="no") "h*"
            else
                write (u, "(A)", advance="no") "h("
            end if
            write (u, "(IO)", advance="no") hel%h1
            if (hel%h1 /= hel%h2) then
                write (u, "(A)", advance="no") "|"
                write (u, "(IO)", advance="no") hel%h2
            end if
            write (u, "(A)", advance="no") ")"
        else if (hel%ghost) then
            write (u, "(A)", advance="no") "h*"
        end if
    end subroutine helicity_write
```

Binary I/O. Write contents only if defined.

```
<Helicities: public>+≡
    public :: helicity_write_raw
    public :: helicity_read_raw
```

```

<Helicities: procedures>+≡
  subroutine helicity_write_raw (hel, u)
    type(helicity_t), intent(in) :: hel
    integer, intent(in) :: u
    write (u) hel%defined
    if (hel%defined) then
      write (u) hel%h1, hel%h2
      write (u) hel%ghost
    end if
  end subroutine helicity_write_raw

  subroutine helicity_read_raw (hel, u, iostat)
    type(helicity_t), intent(out) :: hel
    integer, intent(in) :: u
    integer, intent(out), optional :: iostat
    read (u, iostat=iostat) hel%defined
    if (hel%defined) then
      read (u, iostat=iostat) hel%h1, hel%h2
      read (u, iostat=iostat) hel%ghost
    end if
  end subroutine helicity_read_raw

```

7.1.2 Predicates

Check if the helicity is defined:

```

<Helicities: public>+≡
  public :: helicity_is_defined

<Helicities: procedures>+≡
  elemental function helicity_is_defined (hel) result (defined)
    logical :: defined
    type(helicity_t), intent(in) :: hel
    defined = hel%defined
  end function helicity_is_defined

```

Return true if the two helicities are equal or the particle is unpolarized:

```

<Helicities: public>+≡
  public :: helicity_is_diagonal

<Helicities: procedures>+≡
  elemental function helicity_is_diagonal (hel) result (diagonal)
    logical :: diagonal
    type(helicity_t), intent(in) :: hel
    if (hel%defined) then
      diagonal = hel%h1 == hel%h2
    else
      diagonal = .true.
    end if
  end function helicity_is_diagonal

```

Return the ghost flag

```

<Helicities: public>+≡
  public :: helicity_is_ghost

```

```

<Helicities: procedures>+≡
  elemental function helicity_is_ghost (hel) result (ghost)
    logical :: ghost
    type(helicity_t), intent(in) :: hel
    ghost = hel%ghost
  end function helicity_is_ghost

```

7.1.3 Accessing contents

This returns a two-element array and thus cannot be elemental. The result is unpredictable if the helicity is undefined.

```

<Helicities: public>+≡
  public :: helicity_get

<Helicities: procedures>+≡
  pure function helicity_get (hel) result (h)
    integer, dimension(2) :: h
    type(helicity_t), intent(in) :: hel
    h(1) = hel%h2
    h(2) = hel%h1
  end function helicity_get

```

7.1.4 Comparisons

When comparing helicities, if either one is undefined, they are considered to match. In other words, an unpolarized particle matches any polarization. In the `dmatch` variant, it matches only diagonal helicity.

The ghost flag is ignored when matching, but matters when testing for equality.

```

<Helicities: public>+≡
  public :: operator(.match.)
  public :: operator(.dmatch.)
  public :: operator(==)
  public :: operator(/=)

<Helicities: interfaces>+≡
  interface operator(.match.)
    module procedure helicity_match
  end interface
  interface operator(.dmatch.)
    module procedure helicity_match_diagonal
  end interface
  interface operator(==)
    module procedure helicity_eq
  end interface
  interface operator(/=)
    module procedure helicity_neq
  end interface

```



```

<Helicities: procedures>+=
  elemental function helicity_match (hel1, hel2) result (eq)
    logical :: eq
    type(helicity_t), intent(in) :: hel1, hel2
    if (hel1%defined .and. hel2%defined) then
      eq = (hel1%h1 == hel2%h1) .and. (hel1%h2 == hel2%h2)
    else
      eq = .true.
    end if
  end function helicity_match

  elemental function helicity_match_diagonal (hel1, hel2) result (eq)
    logical :: eq
    type(helicity_t), intent(in) :: hel1, hel2
    if (hel1%defined .and. hel2%defined) then
      eq = (hel1%h1 == hel2%h1) .and. (hel1%h2 == hel2%h2)
    else if (hel1%defined) then
      eq = hel1%h1 == hel1%h2
    else if (hel2%defined) then
      eq = hel2%h1 == hel2%h2
    else
      eq = .true.
    end if
  end function helicity_match_diagonal

<Helicities: procedures>+=
  elemental function helicity_eq (hel1, hel2) result (eq)
    logical :: eq
    type(helicity_t), intent(in) :: hel1, hel2
    if (hel1%defined .and. hel2%defined) then
      eq = (hel1%h1 == hel2%h1) .and. (hel1%h2 == hel2%h2) &
        .and. (hel1%ghost .eqv. hel2%ghost)
    else if (.not. hel1%defined .and. .not. hel2%defined) then
      eq = hel1%ghost .eqv. hel2%ghost
    else
      eq = .false.
    end if
  end function helicity_eq

<Helicities: procedures>+=
  elemental function helicity_neq (hel1, hel2) result (neq)
    logical :: neq
    type(helicity_t), intent(in) :: hel1, hel2
    if (hel1%defined .and. hel2%defined) then
      neq = (hel1%h1 /= hel2%h1) .or. (hel1%h2 /= hel2%h2) &
        .or. (hel1%ghost .neqv. hel2%ghost)
    else if (.not. hel1%defined .and. .not. hel2%defined) then
      neq = hel1%ghost .neqv. hel2%ghost
    else
      neq = .true.
    end if
  end function helicity_neq

```

7.1.5 Tools

Merge two helicity objects by taking the first entry from the first and the second entry from the second argument. Makes sense only if the input helicities were defined and diagonal. The handling of ghost flags is not well-defined; one should verify beforehand that they match.

```
<Helicities: public>+≡
    public :: operator(.merge.)

<Helicities: interfaces>+≡
    interface operator(.merge.)
        module procedure merge_helicities
    end interface

<Helicities: procedures>+≡
    elemental function merge_helicities (hel1, hel2) result (hel)
        type(helicity_t) :: hel
        type(helicity_t), intent(in) :: hel1, hel2
        if (helicity_is_defined (hel1) .and. helicity_is_defined (hel2)) then
            call helicity_init2g (hel, hel2%h1, hel1%h1, hel1%ghost)
        else if (helicity_is_defined (hel1)) then
            hel = hel1
        else if (helicity_is_defined (hel2)) then
            hel = hel2
        end if
    end function merge_helicities
```

7.2 Colors

This module defines a type and tools for dealing with color information.

Each particle can have zero or more (in practice, usually not more than two) color indices. Color indices are positive; flow direction can be determined from the particle nature.

While parton shower matrix elements are diagonal in color, some special applications (e.g., subtractions for NLO matrix elements) require non-diagonal color matrices.

```
<colors.f90>≡  
  <File header>  
  
  module colors  
  
    <Use kinds>  
    <Use file utils>  
    use diagnostics !NODEP!  
  
    <Standard module head>  
  
    <Colors: public>  
  
    <Colors: types>  
  
    <Colors: interfaces>  
  
    contains  
  
    <Colors: procedures>  
  
  end module colors
```

7.2.1 The color type

A particle may have an arbitrary number of color indices (in practice, from zero to two, but more are possible). This object acts as a container.

The fact that color comes as an array prohibits elemental procedures in some places. (May add interfaces and multi versions where necessary.)

The color may be undefined; this corresponds to unallocated arrays.

NOTE: Due to a compiler bug in nagfor 5.2, we do not use allocatable but fixed-size arrays with dimension 2. Only nonzero entries count. This may be more efficient anyway, but gives up some flexibility. However, the squaring algorithm currently works only for singlets, (anti)triplets and octets anyway, so two components are enough.

```
<Colors: public>≡  
  public :: color_t  
  
<Colors: types>≡  
  type :: color_t  
    private  
    !   integer, dimension(:), allocatable :: c1, c2  
    integer, dimension(2) :: c1 = 0, c2 = 0
```

```

        logical :: ghost = .false.
    end type color_t

```

Initializers:

```

<Colors: public>+≡
    public :: color_init

<Colors: interfaces>≡
    interface color_init
        module procedure color_init_undefined, color_init_undefined_ghost
        module procedure color_init_array, color_init_array_ghost
        module procedure color_init_arrays, color_init_arrays_ghost
    end interface

```

Undefined color: array remains unallocated

```

<Colors: procedures>≡
    pure subroutine color_init_undefined (col)
        type(color_t), intent(out) :: col
    end subroutine color_init_undefined

    pure subroutine color_init_undefined_ghost (col, ghost)
        type(color_t), intent(out) :: col
        logical, intent(in) :: ghost
        col%ghost = ghost
    end subroutine color_init_undefined_ghost

```

This defines color from an arbitrary length color array, suitable for any representation. We may have two color arrays (non-diagonal matrix elements). This cannot be elemental. The third version assigns an array of colors, using a two-dimensional array as input.

```

<Colors: procedures>+≡
    pure subroutine color_init_array (col, c1)
        type(color_t), intent(out) :: col
        integer, dimension(:), intent(in) :: c1
    !    allocate (col%c1 (size (c1)))
    !    allocate (col%c2 (size (c1)))
        col%c1 = pack (c1, c1 /= 0, col%c1)
        col%c2 = col%c1
    end subroutine color_init_array

    pure subroutine color_init_array_ghost (col, c1, ghost)
        type(color_t), intent(out) :: col
        integer, dimension(:), intent(in) :: c1
        logical, intent(in) :: ghost
        call color_init_array (col, c1)
        col%ghost = ghost
    end subroutine color_init_array_ghost

    pure subroutine color_init_arrays (col, c1, c2)
        type(color_t), intent(out) :: col
        integer, dimension(:), intent(in) :: c1, c2
        if (size (c1) == size (c2)) then

```

```

!      allocate (col%c1 (size (c1)))
!      allocate (col%c2 (size (c2)))
      col%c1 = pack (c1, c1 /= 0, col%c1)
      col%c2 = pack (c2, c2 /= 0, col%c2)
    else if (size (c1) /= 0) then
!      allocate (col%c1 (size (c1)))
!      allocate (col%c2 (size (c1)))
      col%c1 = pack (c1, c1 /= 0, col%c1)
      col%c2 = col%c1
    else if (size (c2) /= 0) then
!      allocate (col%c1 (size (c2)))
!      allocate (col%c2 (size (c2)))
      col%c1 = pack (c2, c2 /= 0, col%c2)
      col%c2 = col%c1
    end if
  end subroutine color_init_arrays

  pure subroutine color_init_arrays_ghost (col, c1, c2, ghost)
    type(color_t), intent(out) :: col
    integer, dimension(:), intent(in) :: c1, c2
    logical, intent(in) :: ghost
    call color_init_arrays (col, c1, c2)
    col%ghost = ghost
  end subroutine color_init_arrays_ghost

```

This version is restricted to singlets, triplets, antitriplets, and octets: The input contains the color and anticolor index, each of the may be zero.

```

<Colors: public>+≡
  public :: color_init_col_acl

<Colors: procedures>+≡
  elemental subroutine color_init_col_acl (col, col_in, acl_in)
    type(color_t), intent(out) :: col
    integer, intent(in) :: col_in, acl_in
    integer, dimension(0) :: null_array
    select case (col_in)
    case (0)
      select case (acl_in)
      case (0)
        call color_init_array (col, null_array)
      case default
        call color_init_array (col, (/ -acl_in /))
      end select
    case default
      select case (acl_in)
      case (0)
        call color_init_array (col, (/ col_in /))
      case default
        call color_init_array (col, (/ col_in, -acl_in /))
      end select
    end select
  end subroutine color_init_col_acl

```

This version is used for the external interface. We convert a fixed-size array

of colors (for each particle) to the internal form by packing only the nonzero entries.

```

<Colors: public>+≡
    public :: color_init_from_array

<Colors: interfaces>+≡
    interface color_init_from_array
        module procedure color_init_from_array1, color_init_from_array1g
        module procedure color_init_from_array2, color_init_from_array2g
    end interface

<Colors: procedures>+≡
    pure subroutine color_init_from_array1 (col, c1)
        type(color_t), intent(out) :: col
        integer, dimension(:), intent(in) :: c1
        logical, dimension(size(c1)) :: mask
        mask = c1 /= 0
    !   allocate (col%c1 (count (mask)))
    !   allocate (col%c2 (size (col%c1)))
        col%c1 = pack (c1, mask, col%c1)
        col%c2 = col%c1
    end subroutine color_init_from_array1

    pure subroutine color_init_from_array1g (col, c1, ghost)
        type(color_t), intent(out) :: col
        integer, dimension(:), intent(in) :: c1
        logical, intent(in) :: ghost
        call color_init_from_array1 (col, c1)
        col%ghost = ghost
    end subroutine color_init_from_array1g

    pure subroutine color_init_from_array2 (col, c1)
        integer, dimension(:, :), intent(in) :: c1
        type(color_t), dimension(size(c1,2)), intent(out) :: col
        integer :: i
        do i = 1, size (c1,2)
            call color_init_from_array1 (col(i), c1(:,i))
        end do
    end subroutine color_init_from_array2

    pure subroutine color_init_from_array2g (col, c1, ghost)
        integer, dimension(:, :), intent(in) :: c1
        type(color_t), dimension(size(c1,2)), intent(out) :: col
        logical, intent(in), dimension(:) :: ghost
        call color_init_from_array2 (col, c1)
        col%ghost = ghost
    end subroutine color_init_from_array2g

```

Set the ghost property

```

<Colors: public>+≡
    public :: color_set_ghost

<Colors: procedures>+≡
    elemental subroutine color_set_ghost (col, ghost)

```

```

        type(color_t), intent(inout) :: col
        logical, intent(in) :: ghost
        col%ghost = ghost
    end subroutine color_set_ghost

```

Undefine the color state:

```

<Colors: public>+≡
    public :: color_undefine

<Colors: procedures>+≡
    elemental subroutine color_undefine (col, undefine_ghost)
        type(color_t), intent(inout) :: col
        logical, intent(in), optional :: undefine_ghost
    !   if (allocated (col%c1)) deallocate (col%c1)
    !   if (allocated (col%c2)) deallocate (col%c2)
        col%c1 = 0
        col%c2 = 0
        if (present (undefine_ghost)) then
            if (undefine_ghost) col%ghost = .false.
        else
            col%ghost = .false.
        end if
    end subroutine color_undefine

```

Output. As dense as possible, no linebreak. If color is undefined, no output.

```

<Colors: public>+≡
    public :: color_write

<Colors: interfaces>+≡
    interface color_write
        module procedure color_write_single
        module procedure color_write_array
    end interface

<Colors: procedures>+≡
    subroutine color_write_single (col, unit)
        type(color_t), intent(in) :: col
        integer, intent(in), optional :: unit
        integer :: u
        u = output_unit (unit); if (u < 0) return
        if (color_is_defined (col)) then
            write (u, "(A)", advance="no") "c("
            if (col%c1(1) /= 0) write (u, "(I0)", advance="no") col%c1(1)
            if (any (col%c1 /= 0)) write (u, "(1x)", advance="no")
            if (col%c1(2) /= 0) write (u, "(I0)", advance="no") col%c1(2)
            if (.not. color_is_diagonal (col)) then
                write (u, "(A)", advance="no") "|"
                if (col%c2(1) /= 0) write (u, "(I0)", advance="no") col%c2(1)
                if (any (col%c2 /= 0)) write (u, "(1x)", advance="no")
                if (col%c2(2) /= 0) write (u, "(I0)", advance="no") col%c2(2)
            end if
            write (u, "(A)", advance="no") ")"
        else if (col%ghost) then
            write (u, "(A)", advance="no") "c*"

```

```

        end if
    end subroutine color_write_single

    subroutine color_write_array (col, unit)
        type(color_t), dimension(:), intent(in) :: col
        integer, intent(in), optional :: unit
        integer :: u
        integer :: i
        u = output_unit (unit); if (u < 0) return
        write (u, "(A)", advance="no") "["
        do i = 1, size (col)
            if (i > 1) write (u, "(1x)", advance="no")
            call color_write_single (col(i), u)
        end do
        write (u, "(A)", advance="no") "]"
    end subroutine color_write_array

```

Binary I/O. For allocatable colors, this would have to be modified.

```

<Colors: public>+≡
    public :: color_write_raw
    public :: color_read_raw

<Colors: procedures>+≡
    subroutine color_write_raw (col, u)
        type(color_t), intent(in) :: col
        integer, intent(in) :: u
        logical :: defined
        defined = color_is_defined (col) .or. color_is_ghost (col)
        write (u) defined
        if (defined) then
            write (u) col%c1, col%c2
            write (u) col%ghost
        end if
    end subroutine color_write_raw

    subroutine color_read_raw (col, u, iostat)
        type(color_t), intent(out) :: col
        integer, intent(in) :: u
        integer, intent(out), optional :: iostat
        logical :: defined
        read (u, iostat=iostat) defined
        if (defined) then
            read (u, iostat=iostat) col%c1, col%c2
            read (u, iostat=iostat) col%ghost
        end if
    end subroutine color_read_raw

```

7.2.2 Predicates

Return the definition status

```

<Colors: public>+≡
    public :: color_is_defined

```



```

<Colors: procedures>+≡
    elemental function color_is_defined (col) result (defined)
        logical :: defined
        type(color_t), intent(in) :: col
    !    defined = allocated (col%c1)
        defined = any (col%c1 /= 0)
    end function color_is_defined

```

Diagonal color objects have only one array allocated:

```

<Colors: public>+≡
    public :: color_is_diagonal

<Colors: procedures>+≡
    elemental function color_is_diagonal (col) result (diagonal)
        logical :: diagonal
        type(color_t), intent(in) :: col
        if (color_is_defined (col)) then
            diagonal = all (col%c1 == col%c2)
        else
            diagonal = .true.
        end if
    end function color_is_diagonal

```

Return the ghost flag

```

<Colors: public>+≡
    public :: color_is_ghost

<Colors: procedures>+≡
    elemental function color_is_ghost (col) result (ghost)
        logical :: ghost
        type(color_t), intent(in) :: col
        ghost = col%ghost
    end function color_is_ghost

```

The ghost parity: true if the color-ghost flag is set.

```

<Colors: interfaces>+≡
    interface color_ghost_parity
        module procedure color_ghost_parity0
        module procedure color_ghost_parity1
    end interface

<Colors: procedures>+≡
    pure function color_ghost_parity0 (col) result (parity)
        type(color_t), intent(in) :: col
        logical :: parity
        parity = color_is_ghost (col)
    end function color_ghost_parity0

    pure function color_ghost_parity1 (col) result (parity)
        type(color_t), dimension(:), intent(in) :: col
        logical :: parity
        logical, dimension(size(col)) :: p
        integer :: i
        forall (i = 1:size(col))

```

```

        p(i) = color_ghost_parity0 (col(i))
    end forall
    parity = mod (count (p), 2) == 1
end function color_ghost_parity1

```

7.2.3 Accessing contents

Return the number of color indices. We assume that it is identical for both arrays.

```

<Colors: procedures>+≡
    elemental function color_number (col) result (n)
        integer :: n
        type(color_t), intent(in) :: col
    !   n = size (col%c1)
        n = count (col%c1 /= 0)
    end function color_number

```

Return the (first) color/anticolor entry (assuming that color is diagonal). The result is a positive color index.

```

<Colors: public>+≡
    public :: color_get_col
    public :: color_get_acl

<Colors: procedures>+≡
    function color_get_col (col) result (c)
        integer :: c
        type(color_t), intent(in) :: col
        integer :: i
        do i = 1, size (col%c1)
            if (col%c1(i) > 0) then
                c = col%c1(i)
                return
            end if
        end do
        c = 0
    end function color_get_col

    function color_get_acl (col) result (c)
        integer :: c
        type(color_t), intent(in) :: col
        integer :: i
        do i = 1, size (col%c1)
            if (col%c1(i) < 0) then
                c = - col%c1(i)
                return
            end if
        end do
        c = 0
    end function color_get_acl

```

Return the color index with highest absolute value

```

<Colors: public>+≡
    public :: color_get_max_value
    !!! ifort 11.1 rev5 bug
    public :: color_get_max_value0
    public :: color_get_max_value1
    public :: color_get_max_value2

<Colors: interfaces>+≡
    interface color_get_max_value
        module procedure color_get_max_value0
        module procedure color_get_max_value1
        module procedure color_get_max_value2
    end interface

<Colors: procedures>+≡
    elemental function color_get_max_value0 (col) result (cmax)
        integer :: cmax
        type(color_t), intent(in) :: col
        cmax = maxval (abs (col%c1))
    end function color_get_max_value0

    pure function color_get_max_value1 (col) result (cmax)
        integer :: cmax
        type(color_t), dimension(:), intent(in) :: col
        cmax = maxval (color_get_max_value0 (col))
    end function color_get_max_value1

    function color_get_max_value2 (col) result (cmax)
        integer :: cmax
        type(color_t), dimension(:,:), intent(in) :: col
        integer, dimension(size(col, 2)) :: cm
        integer :: i
        forall (i = 1:size(col, 2))
            cm(i) = color_get_max_value1 (col(:,i))
        end forall
        cmax = maxval (cm)
    end function color_get_max_value2

```

7.2.4 Comparisons

Similar to helicities, colors match if they are equal, or if either one is undefined.

```

<Colors: public>+≡
    public :: operator(.match.)
    public :: operator(==)
    public :: operator(/=)

<Colors: interfaces>+≡
    interface operator(.match.)
        module procedure color_match
    end interface
    interface operator(==)
        module procedure color_eq

```

```

end interface
interface operator(/=)
    module procedure color_neq
end interface

<Colors: procedures>+≡
    elemental function color_match (col1, col2) result (eq)
        logical :: eq
        type(color_t), intent(in) :: col1, col2
        if (color_is_defined (col1) .and. color_is_defined (col2)) then
!           if (size (col1%c1) == size (col2%c1)) then
!               eq = all (col1%c1 == col2%c1) .and. all (col1%c2 == col2%c2)
!           else
!               eq = .false.
!           end if
        else
            eq = .true.
        end if
    end function color_match

    elemental function color_eq (col1, col2) result (eq)
        logical :: eq
        type(color_t), intent(in) :: col1, col2
        if (color_is_defined (col1) .and. color_is_defined (col2)) then
!           if (size (col1%c1) == size (col2%c1)) then
!               eq = all (col1%c1 == col2%c1) .and. all (col1%c2 == col2%c2) &
!                   .and. (col1%ghost .eqv. col2%ghost)
!           else
!               eq = .false.
!           end if
        else if (.not. color_is_defined (col1) &
            .and. .not. color_is_defined (col2)) then
            eq = col1%ghost .eqv. col2%ghost
        else
            eq = .false.
        end if
    end function color_eq

    elemental function color_neq (col1, col2) result (neq)
        logical :: neq
        type(color_t), intent(in) :: col1, col2
        if (color_is_defined (col1) .and. color_is_defined (col2)) then
!           if (size (col1%c1) == size (col2%c1)) then
!               neq = any (col1%c1 /= col2%c1) .or. any (col1%c2 /= col2%c2) &
!                   .or. (col1%ghost .neqv. col2%ghost)
!           else
!               neq = .true.
!           end if
        else if (.not. color_is_defined (col1) &
            .and. .not. color_is_defined (col2)) then
            neq = col1%ghost .neqv. col2%ghost
        else
            neq = .true.
        end if
    end function color_neq

```

```

    end if
end function color_neq

```

7.2.5 Tools

Shift color indices by a common offset.

```

<Colors: public>+≡
    public :: color_add_offset

<Colors: procedures>+≡
    elemental subroutine color_add_offset (col, offset)
        type(color_t), intent(inout) :: col
        integer, intent(in) :: offset
        where (col%c1 /= 0) col%c1 = col%c1 + sign (offset, col%c1)
        where (col%c2 /= 0) col%c2 = col%c2 + sign (offset, col%c2)
!       if (allocated (col%c1)) then
!           col%c1 = col%c1 + sign (offset, col%c1)
!           col%c2 = col%c2 + sign (offset, col%c2)
!       end if
    end subroutine color_add_offset

```

Reassign color indices for an array of colored particle in canonical order. The allocated size of the color map is such that two colors per particle can be accommodated.

```

<Colors: public>+≡
    public :: color_canonicalize

<Colors: procedures>+≡
    subroutine color_canonicalize (col)
        type(color_t), dimension(:), intent(inout) :: col
        integer, dimension(2*size(col)) :: map
        integer :: n_col, i, j, k
        n_col = 0
        do i = 1, size (col)
            do j = 1, size (col(i)%c1)
                if (col(i)%c1(j) /= 0) then
                    k = find (abs (col(i)%c1(j)), map(:n_col))
                    if (k == 0) then
                        n_col = n_col + 1
                        map(n_col) = abs (col(i)%c1(j))
                        k = n_col
                    end if
                    col(i)%c1(j) = sign (k, col(i)%c1(j))
                end if
                if (col(i)%c2(j) /= 0) then
                    k = find (abs (col(i)%c2(j)), map(:n_col))
                    if (k == 0) then
                        n_col = n_col + 1
                        map(n_col) = abs (col(i)%c2(j))
                        k = n_col
                    end if
                    col(i)%c2(j) = sign (k, col(i)%c2(j))
                end if
            end do
        end do
    end subroutine color_canonicalize

```

```

        end if
    end do
end do
contains
function find (c, array) result (k)
    integer :: k
    integer, intent(in) :: c
    integer, dimension(:), intent(in) :: array
    integer :: i
    k = 0
    do i = 1, size (array)
        if (c == array (i)) then
            k = i
            return
        end if
    end do
end function find
end subroutine color_canonicalize

```

Return an array of different color indices from an array of colors. The last argument is a pseudo-color array, where the color entries correspond to the position of the corresponding index entry in the index array. The colors are assumed to be diagonal.

(Colors: procedures)+≡

```

subroutine extract_color_line_indices (col, c_index, col_pos)
    type(color_t), dimension(:), intent(in) :: col
    integer, dimension(:), intent(out), allocatable :: c_index
    type(color_t), dimension(size(col)), intent(out) :: col_pos
    integer, dimension(:), allocatable :: c_tmp
    integer :: i, j, k, n, c
    allocate (c_tmp (sum (color_number (col))))
    n = 0
    SCAN1: do i = 1, size (col)
        SCAN2: do j = 1, 2
            c = abs (col(i)%c1(j))
            if (c /= 0) then
                do k = 1, n
                    if (c_tmp(k) == c) then
                        col_pos(i)%c1(j) = k
                        cycle SCAN2
                    end if
                end do
                n = n + 1
                c_tmp(n) = c
                col_pos(i)%c1(j) = n
            end if
        end do SCAN2
    end do SCAN1
    allocate (c_index (n))
    c_index = c_tmp(1:n)
end subroutine extract_color_line_indices

```

Given a color array, pairwise contract the color lines in all possible ways and

return the resulting array of arrays. The input color array must be diagonal, and each color should occur exactly twice, once as color and once as anticolor.

Gluon entries with equal color and anticolor are explicitly excluded.

This algorithm is generic, but for long arrays it is neither efficient, nor does it avoid duplicates. It is intended for small arrays, in particular for the state matrix of a structure-function pair.

```

<Colors: public>+≡
  public :: color_array_make_contractions

<Colors: procedures>+≡
  subroutine color_array_make_contractions (col_in, col_out)
    type(color_t), dimension(:), intent(in) :: col_in
    type(color_t), dimension(:,:), intent(out), allocatable :: col_out
    type :: entry_t
      integer, dimension(:), allocatable :: map
      type(color_t), dimension(:), allocatable :: col
      type(entry_t), pointer :: next => null ()
    end type entry_t
    type :: list_t
      integer :: n = 0
      type(entry_t), pointer :: first => null ()
      type(entry_t), pointer :: last => null ()
    end type list_t
    type(list_t) :: list
    type(entry_t), pointer :: entry
    integer, dimension(:), allocatable :: c_index
    type(color_t), dimension(size(col_in)) :: col_pos
    integer :: n_prt, n_c_index
    integer, dimension(:), allocatable :: map
    integer :: i, j, c
    n_prt = size (col_in)
    call extract_color_line_indices (col_in, c_index, col_pos)
    ! print *, c_index
    n_c_index = size (c_index)
    allocate (map (n_c_index))
    map = 0
    call list_append_if_valid (list, map)
    entry => list%first
    do while (associated (entry))
      do i = 1, n_c_index
        if (entry%map(i) == 0) then
          c = c_index(i)
          do j = i + 1, n_c_index
            if (entry%map(j) == 0) then
              map = entry%map
              map(i) = c
              map(j) = c
              call list_append_if_valid (list, map)
            end if
          end do
        end if
      end do
      entry => entry%next
    end do
  end subroutine

```

```

    call list_to_array (list, col_out)
contains
  subroutine list_append_if_valid (list, map)
    type(list_t), intent(inout) :: list
    integer, dimension(:), intent(in) :: map
    type(entry_t), pointer :: entry
    integer :: i, j, c, p
    entry => list%first
    do while (associated (entry))
      if (all (map == entry%map)) return
      entry => entry%next
    end do
    allocate (entry)
    allocate (entry%map (n_c_index))
    entry%map = map
    allocate (entry%col (n_prt))
    do i = 1, n_prt
      do j = 1, 2
        c = col_in(i)%c1(j)
        if (c /= 0) then
          p = col_pos(i)%c1(j)
          if (map(p) /= 0) then
            entry%col(i)%c1(j) = sign (map(p), c)
          else
            entry%col(i)%c1(j) = c
          endif
          entry%col(i)%c2(j) = entry%col(i)%c1(j)
        end if
      end do
      if (any (entry%col(i)%c1 /= 0) .and. &
        entry%col(i)%c1(1) == - entry%col(i)%c1(2)) return
    end do
    ! call color_write (entry%col); print *, map
    if (associated (list%last)) then
      list%last%next => entry
    else
      list%first => entry
    end if
    list%last => entry
    list%n = list%n + 1
  end subroutine list_append_if_valid
  subroutine list_to_array (list, col)
    type(list_t), intent(inout) :: list
    type(color_t), dimension(:, :), intent(out), allocatable :: col
    type(entry_t), pointer :: entry
    integer :: i
    allocate (col (n_prt, list%n - 1))
    do i = 0, list%n - 1
      entry => list%first
      list%first => list%first%next
      if (i /= 0) col(:, i) = entry%col
      deallocate (entry)
    end do
    list%last => null ()
  end subroutine list_to_array
end

```



```

        end subroutine list_to_array
    end subroutine color_array_make_contractions

```

Invert the color index, switching from particle to antiparticle. For gluons, we have to swap the order of color entries.

```

<Colors: public>+≡
    public :: color_invert

<Colors: procedures>+≡
    elemental subroutine color_invert (col)
        type(color_t), intent(inout) :: col
        col%c1 = - col%c1
        col%c2 = - col%c2
        if (col%c1(1) < 0 .and. col%c1(2) > 0) then
            col%c1 = col%c1(2:1:-1)
            col%c2 = col%c2(2:1:-1)
        end if
    end subroutine color_invert

```

Make a color map for two matching color arrays. The result is an array of integer pairs.

```

<Colors: public>+≡
    public :: set_color_map

<Colors: procedures>+≡
    subroutine set_color_map (map, col1, col2)
        integer, dimension(:, :), intent(out), allocatable :: map
        type(color_t), dimension(:), intent(in) :: col1, col2
        integer, dimension(:, :), allocatable :: map1
        integer :: i, j, k
        allocate (map1 (2, 2 * sum (color_number (col1))))
        k = 0
        do i = 1, size (col1)
            do j = 1, size (col1(i)%c1)
                if (col1(i)%c1(j) /= 0 &
                    .and. all (map1(1,:k) /= abs (col1(i)%c1(j)))) then
                    k = k + 1
                    map1(1,k) = abs (col1(i)%c1(j))
                    map1(2,k) = abs (col2(i)%c1(j))
                end if
                if (col1(i)%c2(j) /= 0 &
                    .and. all (map1(1,:k) /= abs (col1(i)%c2(j)))) then
                    k = k + 1
                    map1(1,k) = abs (col1(i)%c2(j))
                    map1(2,k) = abs (col2(i)%c2(j))
                end if
            end do
        end do
        allocate (map (2, k))
        map(:, :) = map1(:, :k)
    end subroutine set_color_map

```

Translate colors which have a match in the translation table (an array of integer pairs). Color that do not match an entry are simply transferred; this is done by first transferring all components, then modifying entries where appropriate.

```

<Colors: public>+≡
    public :: color_translate

<Colors: interfaces>+≡
    interface color_translate
        module procedure color_translate0
        module procedure color_translate0_offset
        module procedure color_translate1
    end interface

<Colors: procedures>+≡
    subroutine color_translate0 (col, map)
        type(color_t), intent(inout) :: col
        integer, dimension(:, :), intent(in) :: map
        type(color_t) :: col_tmp
        integer :: i
        col_tmp = col
        do i = 1, size (map,2)
            where (abs (col%c1) == map(1,i))
                col_tmp%c1 = sign (map(2,i), col%c1)
            end where
            where (abs (col%c2) == map(1,i))
                col_tmp%c2 = sign (map(2,i), col%c2)
            end where
        end do
        col = col_tmp
    end subroutine color_translate0

    subroutine color_translate0_offset (col, map, offset)
        type(color_t), intent(inout) :: col
        integer, dimension(:, :), intent(in) :: map
        integer, intent(in) :: offset
        logical, dimension(size(col%c1)) :: mask1, mask2
        type(color_t) :: col_tmp
        integer :: i
        col_tmp = col
        mask1 = col%c1 /= 0
        mask2 = col%c2 /= 0
        do i = 1, size (map,2)
            where (abs (col%c1) == map(1,i))
                col_tmp%c1 = sign (map(2,i), col%c1)
                mask1 = .false.
            end where
            where (abs (col%c2) == map(1,i))
                col_tmp%c2 = sign (map(2,i), col%c2)
                mask2 = .false.
            end where
        end do
        col = col_tmp
        where (mask1) col%c1 = sign (abs (col%c1) + offset, col%c1)
        where (mask2) col%c2 = sign (abs (col%c2) + offset, col%c2)
    end subroutine color_translate0_offset

```

```

end subroutine color_translate0_offset

subroutine color_translate1 (col, map, offset)
  type(color_t), dimension(:), intent(inout) :: col
  integer, dimension(:,:), intent(in) :: map
  integer, intent(in), optional :: offset
  integer :: i
  if (present (offset)) then
    do i = 1, size (col)
      call color_translate0_offset (col(i), map, offset)
    end do
  else
    do i = 1, size (col)
      call color_translate0 (col(i), map)
    end do
  end if
end subroutine color_translate1

```

Merge two color objects by taking the first entry from the first and the second entry from the second argument. Makes sense only if the input colors are defined (and diagonal). If either one is undefined, transfer the defined one.

For a color ghost, color is not defined. These have to be treated separately.

```

<Colors: public>+≡
  public :: operator(.merge.)

<Colors: interfaces>+≡
  interface operator(.merge.)
    module procedure merge_colors
  end interface

<Colors: procedures>+≡
  elemental function merge_colors (col1, col2) result (col)
    type(color_t) :: col
    type(color_t), intent(in) :: col1, col2
    if (color_is_defined (col1) .and. color_is_defined (col2)) then
      call color_init_arrays (col, col1%c1, col2%c1)
    else if (color_is_defined (col1)) then
      col = col1
    else if (color_is_defined (col2)) then
      col = col2
    else if (color_is_ghost (col1)) then
      col = col1
    else if (color_is_ghost (col2)) then
      col = col2
    end if
  end function merge_colors

```

Compute the color factor, given two interfering color arrays.

```

<Colors: public>+≡
  public :: compute_color_factor

<Colors: procedures>+≡
  function compute_color_factor (col1, col2, nc) result (factor)
    real(default) :: factor

```

```

type(color_t), dimension(:), intent(in) :: col1, col2
integer, intent(in), optional :: nc
type(color_t), dimension(size(col1)) :: col
integer :: ncol, nloops, nghost
ncol = 3; if (present(nc)) ncol = nc
col = col1 .merge. col2
nloops = count_color_loops (col)
nghost = count (color_is_ghost (col))
factor = real (ncol, default) ** (nloops - nghost)
if (color_ghost_parity (col)) factor = - factor
end function compute_color_factor

```

We have a pair of color index arrays which corresponds to a squared matrix element. We want to determine the number of color loops in this square matrix element. So we first copy the colors (stored in a single color array with a pair of color lists in each entry) to a temporary where the color indices are shifted by some offset. We then recursively follow each loop, starting at the first color that has the offset, resetting the first color index to the loop index and each further index to zero as we go. We check that (a) each color index occurs twice within the left (right) color array, (b) the loops are closed, so we always come back to a line which has the loop index.

In order for the algorithm to work we have to conjugate the colors of initial state particles (one for decays, two for scatterings) into their corresponding anticolors of outgoing particles.

```

<Colors: public>+≡
public :: count_color_loops

<Colors: procedures>+≡
function count_color_loops (col) result (count)
integer :: count
type(color_t), dimension(:), intent(in) :: col
type(color_t), dimension(size(col)) :: cc
integer :: i, n, offset
!   print *, "Count color loops:"
!   call color_write (col); print *
cc = col
n = size (cc)
offset = n
call color_add_offset (cc, offset)
!   print *, offset
!   call color_write (cc); print *
count = 0
SCAN_LOOPS: do
do i = 1, n
!       print *, i, ':', cc(i)%c1
if (color_is_defined (cc(i))) then
if (any (cc(i)%c1 > offset)) then
!       print *, 'start', i
count = count + 1
call follow_line1 (pick_new_line (cc(i)%c1, count, 1))
cycle SCAN_LOOPS
end if
end if
end if
end if

```

```

        end do
        exit SCAN_LOOPS
    end do SCAN_LOOPS
contains
    function pick_new_line (c, reset_val, sgn) result (line)
        integer :: line
        integer, dimension(:), intent(inout) :: c
        integer, intent(in) :: reset_val
        integer, intent(in) :: sgn
        integer :: i
        if (any (c == count)) then
            line = count
        else
            do i = 1, size (c)
                if (sign (1, c(i)) == sgn .and. abs (c(i)) > offset) then
                    line = c(i)
                    c(i) = reset_val
                    return
                end if
            end do
            call color_mismatch
        end if
    end function pick_new_line
    subroutine reset_line (c, line)
        integer, dimension(:), intent(inout) :: c
        integer, intent(in) :: line
        integer :: i
        do i = 1, size (c)
            if (c(i) == line) then
                c(i) = 0
                return
            end if
        end do
    end subroutine reset_line
    recursive subroutine follow_line1 (line)
        integer, intent(in) :: line
        integer :: i
        ! print *, 'follow line 1:', line
        if (line == count) then
            ! print *, 'loop closed'
            return
        end if
        do i = 1, n
            if (any (cc(i)%c1 == -line)) then
                call reset_line (cc(i)%c1, -line)
                ! print *, 'found', -line, ' resetting c1:'
                ! call color_write (cc); print *
                call follow_line2 (pick_new_line (cc(i)%c2, 0, sign (1, -line)))
                return
            end if
        end do
        call color_mismatch ()
    end subroutine follow_line1
    recursive subroutine follow_line2 (line)

```

```

integer, intent(in) :: line
integer :: i
! print *, 'follow line 2:', line
do i = 1, n
  if (any (cc(i)%c2 == -line)) then
    call reset_line (cc(i)%c2, -line)
!    print *, 'found', -line, ' resetting c2:'
!    call color_write (cc); print *
    call follow_line1 (pick_new_line (cc(i)%c1, 0, sign (1, -line)))
    return
  end if
end do
call color_mismatch ()
end subroutine follow_line2
subroutine color_mismatch ()
  call color_write (col)
  print *
  call msg_bug (" Color flow mismatch (color loops should be closed)")
end subroutine color_mismatch
end function count_color_loops

```

7.2.6 Color counting test

<Colors: public>+≡

public :: color_test

<Colors: procedures>+≡

```

subroutine color_test ()
  type(color_t), dimension(4) :: col1, col2, col
  type(color_t), dimension(:), allocatable :: col3
  type(color_t), dimension(:,:), allocatable :: col_array
  integer :: count, i
  call color_init_col_acl (col1, (/ 1, 0, 2, 3 /), (/ 0, 1, 3, 2 /))
  col2 = col1
  call color_write (col1); print *
  call color_write (col2); print *
  col = col1 .merge. col2
  call color_write (col); print *
  count = count_color_loops (col)
  print *, "Number of color loops (3): ", count
  call color_init_col_acl (col2, (/ 1, 0, 2, 3 /), (/ 0, 2, 3, 1 /))
  call color_write (col1); print *
  call color_write (col2); print *
  col = col1 .merge. col2
  call color_write (col); print *
  count = count_color_loops (col)
  print *, "Number of color loops (2): ", count
  print *
  allocate (col3 (4))
  call color_init_from_array (col3, &
    reshape ((/ 1, 0, 0, -1, 2, -3, 3, -2 /), &
      (/ 2, 4 /)))
  call color_write (col3); print *

```

```

call color_array_make_contractions (col3, col_array)
print *, "Contractions:"
do i = 1, size (col_array, 2)
    call color_write (col_array(:,i)); print *
end do
deallocate (col3)
print *
allocate (col3 (6))
call color_init_from_array (col3, &
    reshape ((/ 1, -2, 3, 0, 0, -1, 2, -4, -3, 0, 4, 0 /), &
        (/ 2, 6 /)))
call color_write (col3); print *
call color_array_make_contractions (col3, col_array)
print *, "Contractions:"
do i = 1, size (col_array, 2)
    call color_write (col_array(:,i)); print *
end do
end subroutine color_test

```

7.2.7 The Madgraph color model

This section describes the method for matrix element and color flow calculation within Madgraph.

For each Feynman diagram, the colorless amplitude for a specified helicity and momentum configuration (in- and out- combined) is computed:

$$A_d(p, h) \quad (7.1)$$

Inserting color, the squared matrix element for definite helicity and momentum is

$$M^2(p, h) = \sum_{dd'} A_d(p, h) C_{dd'} A_{d'}^*(p, h) \quad (7.2)$$

where $C_{dd'}$ describes the color interference of the two diagrams A_d and $A_{d'}$, which is independent of momentum and helicity and can be calculated for each Feynman diagram pair by reducing it to the corresponding color graph. Obviously, one could combine all diagrams with identical color structure, such that the index d runs only over different color graphs. For colorless diagrams all elements of $C_{dd'}$ are equal to unity.

The hermitian matrix $C_{dd'}$ is diagonalized once and for all, such that it can be written in the form

$$C_{dd'} = \sum_{\lambda} c_d^{\lambda} \lambda c_{d'}^{\lambda*}, \quad (7.3)$$

where the eigenvectors c_d are normalized,

$$\sum_d |c_d^{\lambda}|^2 = 1, \quad (7.4)$$

and the λ values are the corresponding eigenvalues. In the colorless case, this means $c_d = 1/\sqrt{N_d}$ for all diagrams (N_d = number of diagrams), and $\lambda = N_d$ is the only nonzero eigenvalue.

Consequently, the squared matrix element for definite helicity and momentum can also be written as

$$M^2(p, h) = \sum_{\lambda} A_{\lambda}(p, h) \lambda A_{\lambda}(p, h)^* \quad (7.5)$$

with

$$A_{\lambda}(p, h) = \sum_d c_d^{\lambda} A_d(p, h). \quad (7.6)$$

For generic spin density matrices, this is easily generalized to

$$M^2(p, h, h') = \sum_{\lambda} A_{\lambda}(p, h) \lambda A_{\lambda}(p, h')^* \quad (7.7)$$

To determine the color flow probabilities of a given momentum-helicity configuration, the color flow amplitudes are calculated as

$$a_f(p, h) = \sum_d \beta_d^f A_d(p, h), \quad (7.8)$$

where the coefficients β_d^f describe the amplitude for a given Feynman diagram (or color graph) d to correspond to a definite color flow f . They are computed from $C_{dd'}$ by transforming this matrix into the color flow basis and neglecting all off-diagonal elements. Again, these coefficients do not depend on momentum or helicity and can therefore be calculated in advance. This gives the color flow transition matrix

$$F^f(p, h, h') = a_f(p, h) a_f^*(p, h') \quad (7.9)$$

which is assumed diagonal in color flow space and is separate from the color-summed transition matrix M^2 . They are, however, equivalent (up to a factor) to leading order in $1/N_c$, and using the color flow transition matrix is appropriate for matching to hadronization.

Note that the color flow transition matrix is not normalized at this stage. To make use of it, we have to fold it with the in-state density matrix to get a pseudo density matrix

$$\hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h'_{\text{out}}) = \sum_{h_{\text{in}} h'_{\text{in}}} F^f(p, h, h') \rho_{\text{in}}(p, h_{\text{in}}, h'_{\text{in}}) \quad (7.10)$$

which gets a meaning only after contracted with projections on the outgoing helicity states k_{out} , given as linear combinations of helicity states with the unitary coefficient matrix $c(k_{\text{out}}, h_{\text{out}})$. Then the probability of finding color flow f when the helicity state k_{out} is measured is given by

$$P^f(p, k_{\text{out}}) = Q^f(p, k_{\text{out}}) / \sum_f Q^f(p, k_{\text{out}}) \quad (7.11)$$

where

$$Q^f(p, k_{\text{out}}) = \sum_{h_{\text{out}} h'_{\text{out}}} c(k_{\text{out}}, h_{\text{out}}) \hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h'_{\text{out}}) c^*(k_{\text{out}}, h'_{\text{out}}) \quad (7.12)$$

However, if we can assume that the out-state helicity basis is the canonical one, we can throw away the off diagonal elements in the color flow density matrix and normalize the ones on the diagonal to obtain

$$P^f(p, h_{\text{out}}) = \hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h_{\text{out}}) / \sum_f \hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h_{\text{out}}) \quad (7.13)$$

Finally, the color-summed out-state density matrix is computed by the scattering formula

$$\rho_{\text{out}}(p, h_{\text{out}}, h'_{\text{out}}) = \sum_{h_{\text{in}} h'_{\text{in}}} M^2(p, h, h') \rho_{\text{in}}(p, h_{\text{in}}, h'_{\text{in}}) \quad (7.14)$$

$$= \sum_{h_{\text{in}} h'_{\text{in}} \lambda} A_{\lambda}(p, h) \lambda A_{\lambda}(p, h')^* \rho_{\text{in}}(p, h_{\text{in}}, h'_{\text{in}}), \quad (7.15)$$

The trace of ρ_{out} is the squared matrix element, summed over all internal degrees of freedom. To get the squared matrix element for a definite helicity k_{out} and color flow f , one has to project the density matrix onto the given helicity state and multiply with $P^f(p, k_{\text{out}})$.

For diagonal helicities the out-state density reduces to

$$\rho_{\text{out}}(p, h_{\text{out}}) = \sum_{h_{\text{in}} \lambda} \lambda |A_{\lambda}(p, h)|^2 \rho_{\text{in}}(p, h_{\text{in}}). \quad (7.16)$$

Since no basis transformation is involved, we can use the normalized color flow probability $P^f(p, h_{\text{out}})$ and express the result as

$$\rho_{\text{out}}^f(p, h_{\text{out}}) = \rho_{\text{out}}(p, h_{\text{out}}) P^f(p, h_{\text{out}}) \quad (7.17)$$

$$= \sum_{h_{\text{in}} \lambda} \frac{|a^f(p, h)|^2}{\sum_f |a^f(p, h)|^2} \lambda |A_{\lambda}(p, h)|^2 \rho_{\text{in}}(p, h_{\text{in}}). \quad (7.18)$$

From these considerations, the following calculation strategy can be derived:

- Before the first event is generated, the color interference matrix $C_{dd'}$ is computed and diagonalized, so the eigenvectors c_d^{λ} , eigenvalues λ and color flow coefficients β_d^f are obtained. In practice, these calculations are done when the matrix element code is generated, and the results are hardcoded in the matrix element subroutine as **DATA** statements.
- For each event, one loops over helicities once and stores the matrices $A_{\lambda}(p, h)$ and $a^f(p, h)$. The allowed color flows, helicity combinations and eigenvalues are each labeled by integer indices, so one has to store complex matrices of dimension $N_{\lambda} \times N_h$ and $N_f \times N_h$, respectively.
- The further strategy depends on the requested information.
 1. If colorless diagonal helicity amplitudes are required, the eigenvalues $A_{\lambda}(p, h)$ are squared, summed with weight λ , and the result contracted with the in-state probability vector $\rho_{\text{in}}(p, h_{\text{in}})$. The result is a probability vector $\rho_{\text{out}}(p, h_{\text{out}})$.

2. For colored diagonal helicity amplitudes, the color coefficients $a^f(p, h)$ are also squared and used as weights to obtain the color-flow probability vector $\rho_{\text{out}}^f(p, h_{\text{out}})$.
3. For colorless non-diagonal helicity amplitudes, we contract the tensor product of $A_\lambda(p, h)$ with $A_\lambda(p, h')$, weighted with λ , with the correlated in-state density matrix, to obtain a correlated out-state density matrix.
4. In the general (colored, non-diagonal) case, we do the same as in the colorless case, but return the un-normalized color flow density matrix $\hat{\rho}_{\text{out}}^f(p, h_{\text{out}}, h'_{\text{out}})$ in addition. When the relevant helicity basis is known, the latter can be used by the caller program to determine flow probabilities. (In reality, we assume the canonical basis and reduce the correlated out-state density to its diagonal immediately.)

7.3 Flavors: Particle properties

This module contains a type for holding the flavor code, and all functions that depend on the model, i.e., that determine particle properties.

The PDG code is packed in a special **flavor** type. (This prohibits meaningless operations, and it allows for a different implementation, e.g., some non-PDG scheme internally, if appropriate at some point.) In addition, the flavor object holds a pointer to a **particle_data** object which is centrally stored (as part of a physics model). In this way, all particle data can be accessed using just the **flv** object without having to carry them around.

The pointer component imposes a technical restriction: Assignment of flavor objects cannot be used, directly or indirectly, in pure, and thus in elemental procedures.

```
<flavors.f90>≡  
  <File header>  
  
  module flavors  
  
    <Use kinds>  
    <Use strings>  
    <Use file utils>  
    use pdg_arrays  
    use colors, only: color_t, color_init  
    use models  
  
    <Standard module head>  
  
    <Flavors: public>  
  
    <Flavors: types>  
  
    <Flavors: interfaces>  
  
    contains  
  
    <Flavors: procedures>  
  
  end module flavors
```

7.3.1 The flavor type

The flavor type is an integer representing the PDG code, or undefined (zero). Negative codes represent antiparticles.

For full generality, and analogy with helicity and color, we allow for non-diagonal flavor indices in density matrices. This is probably academic; an obscure application is the definition of proper isospin states.

Further properties of the given flavor can be retrieved via the particle-data pointer, if it is associated.

```
<Flavors: public>≡  
  public :: flavor_t
```

```

<Flavors: types>≡
  type :: flavor_t
  private
  integer :: f = UNDEFINED
  type(particle_data_t), pointer :: prt => null ()
end type flavor_t

```

Initializer form. If the model is assigned, the procedure is impure, therefore we have to define a separate array version.

```

<Flavors: public>+≡
  public :: flavor_init

<Flavors: interfaces>≡
  interface flavor_init
    module procedure flavor_init0_empty
    module procedure flavor_init0
    module procedure flavor_init0_particle_data
    module procedure flavor_init0_model
    module procedure flavor_init0_name_model
    module procedure flavor_init1_model
    module procedure flavor_init1_name_model
    module procedure flavor_init2_model
    module procedure flavor_init_aval_model
  end interface

<Flavors: procedures>≡
  elemental subroutine flavor_init0_empty (flv)
    type(flavor_t), intent(out) :: flv
  end subroutine flavor_init0_empty

  elemental subroutine flavor_init0 (flv, f)
    type(flavor_t), intent(out) :: flv
    integer, intent(in) :: f
    flv%f = f
  end subroutine flavor_init0

  subroutine flavor_init0_particle_data (flv, particle_data)
    type(flavor_t), intent(out) :: flv
    type(particle_data_t), intent(in), target :: particle_data
    flv%f = particle_data_get_pdg (particle_data)
    flv%prt => particle_data
  end subroutine flavor_init0_particle_data

  subroutine flavor_init0_model (flv, f, model)
    type(flavor_t), intent(out) :: flv
    integer, intent(in) :: f
    type(model_t), intent(in), target :: model
    flv%f = f
    flv%prt => model_get_particle_ptr (model, f)
  end subroutine flavor_init0_model

  subroutine flavor_init1_model (flv, f, model)
    type(flavor_t), dimension(:), intent(out) :: flv
    integer, dimension(:), intent(in) :: f
    type(model_t), intent(in), target :: model

```

```

integer :: i
do i = 1, size (f)
    call flavor_init0_model (flv(i), f(i), model)
end do
end subroutine flavor_init1_model

subroutine flavor_init2_model (flv, f, model)
    type(flavor_t), dimension(:,:), intent(out) :: flv
    integer, dimension(:,:), intent(in) :: f
    type(model_t), intent(in), target :: model
    integer :: i
    do i = 1, size (f, 2)
        call flavor_init1_model (flv(:,i), f(:,i), model)
    end do
end subroutine flavor_init2_model

subroutine flavor_init0_name_model (flv, name, model)
    type(flavor_t), intent(out) :: flv
    type(string_t), intent(in) :: name
    type(model_t), intent(in), target :: model
    flv%f = model_get_particle_pdg (model, name)
    flv%prt => model_get_particle_ptr (model, flv%f)
end subroutine flavor_init0_name_model

subroutine flavor_init1_name_model (flv, name, model)
    type(flavor_t), dimension(:), intent(out) :: flv
    type(string_t), dimension(:), intent(in) :: name
    type(model_t), intent(in), target :: model
    integer :: i
    do i = 1, size (name)
        call flavor_init0_name_model (flv(i), name(i), model)
    end do
end subroutine flavor_init1_name_model

```

This version transforms a PDG array value into a flavor array. The flavor array must be allocatable.

<Flavors: procedures>+≡

```

subroutine flavor_init_aval_model (flv, aval, model)
    type(flavor_t), dimension(:), intent(out), allocatable :: flv
    type(pdg_array_t), intent(in) :: aval
    type(model_t), intent(in), target :: model
    integer, dimension(:), allocatable :: pdg
    pdg = aval
    allocate (flv (size (pdg)))
    call flavor_init (flv, pdg, model)
end subroutine flavor_init_aval_model

```

Undefine the flavor state:

<Flavors: public>+≡

```

public :: flavor_undefine

```

<Flavors: procedures>+≡

```

elemental subroutine flavor_undefine (flv)

```

```

    type(flavor_t), intent(inout) :: flv
    flv%f = UNDEFINED
    flv%prt => null ()
end subroutine flavor_undefine

```

Output: dense, no linebreak

<Flavors: public>+≡

```

public :: flavor_write

```

<Flavors: procedures>+≡

```

subroutine flavor_write (flv, unit)
    type(flavor_t), intent(in) :: flv
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    if (associated (flv%prt)) then
        write (u, "(A)", advance="no") "f("
    else
        write (u, "(A)", advance="no") "p("
    end if
    write (u, "(I0)", advance="no") flv%f
    write (u, "(A)", advance="no") ")"
end subroutine flavor_write

```

Binary I/O. Currently, the model information is not written/read, so after reading the particle-data pointer is empty.

<Flavors: public>+≡

```

public :: flavor_write_raw
public :: flavor_read_raw

```

<Flavors: procedures>+≡

```

subroutine flavor_write_raw (flv, u)
    type(flavor_t), intent(in) :: flv
    integer, intent(in) :: u
    write (u) flv%f
end subroutine flavor_write_raw

subroutine flavor_read_raw (flv, u, iostat)
    type(flavor_t), intent(out) :: flv
    integer, intent(in) :: u
    integer, intent(out), optional :: iostat
    read (u, iostat=iostat) flv%f
end subroutine flavor_read_raw

```

Assignment

Default assignment of flavor objects is possible, but cannot be used in pure procedures, because a pointer assignment is involved.

Assign the particle pointer separately. This cannot be elemental, so we define a scalar and an array version explicitly. We refer to an array of flavors, not an array of models.

<Flavors: public>+≡

```

    public :: flavor_set_model
<Flavors: interfaces>+≡
    interface flavor_set_model
        module procedure flavor_set_model_single
        module procedure flavor_set_model_array
    end interface
<Flavors: procedures>+≡
    subroutine flavor_set_model_single (flv, model)
        type(flavor_t), intent(inout) :: flv
        type(model_t), intent(in), target :: model
        if (flv%f /= UNDEFINED) &
            flv%prt => model_get_particle_ptr (model, flv%f)
    end subroutine flavor_set_model_single

    subroutine flavor_set_model_array (flv, model)
        type(flavor_t), dimension(:), intent(inout) :: flv
        type(model_t), intent(in), target :: model
        integer :: i
        do i = 1, size (flv)
            if (flv(i)%f /= UNDEFINED) &
                flv(i)%prt => model_get_particle_ptr (model, flv(i)%f)
        end do
    end subroutine flavor_set_model_array

```

Predicates

Return the definition status

```

<Flavors: public>+≡
    public :: flavor_is_defined
<Flavors: procedures>+≡
    elemental function flavor_is_defined (flv) result (defined)
        logical :: defined
        type(flavor_t), intent(in) :: flv
        defined = flv%f /= UNDEFINED
    end function flavor_is_defined

```

Check for valid flavor (including undefined):

```

<Flavors: public>+≡
    public :: flavor_is_valid
<Flavors: procedures>+≡
    elemental function flavor_is_valid (flv) result (valid)
        logical :: valid
        type(flavor_t), intent(in) :: flv
        valid = flv%f /= INVALID
    end function flavor_is_valid

```

Return true if the particle-data pointer is associated. (Debugging aid)

```

<Flavors: public>+≡
    public :: flavor_is_associated

```

```

<Flavors: procedures>+=
  elemental function flavor_is_associated (flv) result (flag)
    logical :: flag
    type(flavor_t), intent(in) :: flv
    flag = associated (flv%prt)
  end function flavor_is_associated

```

Accessing contents

With the exception of the PDG code, all particle properties are accessible only via the `prt` pointer. If this is unassigned, some access function will crash.

Return the flavor as an integer

```

<Flavors: public>+=
  public :: flavor_get_pdg

<Flavors: procedures>+=
  elemental function flavor_get_pdg (flv) result (f)
    integer :: f
    type(flavor_t), intent(in) :: flv
    f = flv%f
  end function flavor_get_pdg

```

Return the flavor of the antiparticle

```

<Flavors: public>+=
  public :: flavor_get_pdg_anti

<Flavors: procedures>+=
  elemental function flavor_get_pdg_anti (flv) result (f)
    integer :: f
    type(flavor_t), intent(in) :: flv
    if (associated (flv%prt)) then
      if (particle_data_has_antiparticle (flv%prt)) then
        f = -flv%f
      else
        f = flv%f
      end if
    else
      f = 0
    end if
  end function flavor_get_pdg_anti

```

Absolute value:

```

<Flavors: public>+=
  public :: flavor_get_pdg_abs

<Flavors: procedures>+=
  elemental function flavor_get_pdg_abs (flv) result (f)
    integer :: f
    type(flavor_t), intent(in) :: flv
    f = abs (flv%f)
  end function flavor_get_pdg_abs

```


Generic properties

(Flavors: public)+≡

```
public :: flavor_is_visible
public :: flavor_is_parton
public :: flavor_is_beam_remnant
public :: flavor_is_gauge
public :: flavor_is_left_handed
public :: flavor_is_right_handed
public :: flavor_is_antiparticle
public :: flavor_has_antiparticle
public :: flavor_is_stable
public :: flavor_decays_isotropically
public :: flavor_decays_diagonal
public :: flavor_is_polarized
```

(Flavors: procedures)+≡

```
elemental function flavor_is_visible (flv) result (flag)
  logical :: flag
  type(flavor_t), intent(in) :: flv
  if (associated (flv%prt)) then
    flag = particle_data_is_visible (flv%prt)
  else
    flag = .false.
  end if
end function flavor_is_visible
```

```
elemental function flavor_is_parton (flv) result (flag)
  logical :: flag
  type(flavor_t), intent(in) :: flv
  if (associated (flv%prt)) then
    flag = particle_data_is_parton (flv%prt)
  else
    flag = .false.
  end if
end function flavor_is_parton
```

```
elemental function flavor_is_beam_remnant (flv) result (flag)
  logical :: flag
  type(flavor_t), intent(in) :: flv
  select case (abs (flv%f))
  case (HADRON_REMNANT, &
        HADRON_REMNANT_SINGLET, HADRON_REMNANT_TRIPLET, HADRON_REMNANT_OCTET)
    flag = .true.
  case default
    flag = .false.
  end select
end function flavor_is_beam_remnant
```

```
elemental function flavor_is_gauge (flv) result (flag)
  logical :: flag
  type(flavor_t), intent(in) :: flv
  if (associated (flv%prt)) then
    flag = particle_data_is_gauge (flv%prt)
  else
    flag = .false.
  end if
end function flavor_is_gauge
```

```

        end if
    end function flavor_is_gauge

    elemental function flavor_is_left_handed (flv) result (flag)
        logical :: flag
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            if (flv%f > 0) then
                flag = particle_data_is_left_handed (flv%prt)
            else
                flag = particle_data_is_right_handed (flv%prt)
            end if
        else
            flag = .false.
        end if
    end function flavor_is_left_handed

    elemental function flavor_is_right_handed (flv) result (flag)
        logical :: flag
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            if (flv%f > 0) then
                flag = particle_data_is_right_handed (flv%prt)
            else
                flag = particle_data_is_left_handed (flv%prt)
            end if
        else
            flag = .false.
        end if
    end function flavor_is_right_handed

    elemental function flavor_is_antiparticle (flv) result (flag)
        logical :: flag
        type(flavor_t), intent(in) :: flv
        flag = flv%f < 0
    end function flavor_is_antiparticle

    elemental function flavor_has_antiparticle (flv) result (flag)
        logical :: flag
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            flag = particle_data_has_antiparticle (flv%prt)
        else
            flag = .false.
        end if
    end function flavor_has_antiparticle

    elemental function flavor_is_stable (flv) result (flag)
        logical :: flag
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            flag = particle_data_is_stable (flv%prt, anti = flv%f < 0)
        else
            flag = .true.
        end if
    end function flavor_is_stable

```

```

        end if
    end function flavor_is_stable

    elemental function flavor_decays_isotropically (flv) result (flag)
        logical :: flag
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            flag = particle_data_decays_isotropically (flv%prt, anti = flv%f < 0)
        else
            flag = .true.
        end if
    end function flavor_decays_isotropically

    elemental function flavor_decays_diagonal (flv) result (flag)
        logical :: flag
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            flag = particle_data_decays_diagonal (flv%prt, anti = flv%f < 0)
        else
            flag = .true.
        end if
    end function flavor_decays_diagonal

    elemental function flavor_is_polarized (flv) result (flag)
        logical :: flag
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            flag = particle_data_is_polarized (flv%prt, anti = flv%f < 0)
        else
            flag = .false.
        end if
    end function flavor_is_polarized

```

Names:

(Flavors: public)+≡

```

    public :: flavor_get_name
    public :: flavor_get_tex_name

```

(Flavors: procedures)+≡

```

    elemental function flavor_get_name (flv) result (name)
        type(string_t) :: name
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            name = particle_data_get_name (flv%prt, flv%f < 0)
        else
            name = "?"
        end if
    end function flavor_get_name

    elemental function flavor_get_tex_name (flv) result (name)
        type(string_t) :: name
        type(flavor_t), intent(in) :: flv
        if (associated (flv%prt)) then
            name = particle_data_get_tex_name (flv%prt, flv%f < 0)

```

```

    else
        name = "?"
    end if
end function flavor_get_tex_name

```

<Flavors: public>+≡

```

public :: flavor_get_spin_type
public :: flavor_get_multiplicity
public :: flavor_get_isospin_type
public :: flavor_get_charge_type
public :: flavor_get_color_type

```

<Flavors: procedures>+≡

```

elemental function flavor_get_spin_type (flv) result (type)
    integer :: type
    type(flavor_t), intent(in) :: flv
    if (associated (flv%prt)) then
        type = particle_data_get_spin_type (flv%prt)
    else
        type = 1
    end if
end function flavor_get_spin_type

```

```

elemental function flavor_get_multiplicity (flv) result (type)
    integer :: type
    type(flavor_t), intent(in) :: flv
    if (associated (flv%prt)) then
        type = particle_data_get_multiplicity (flv%prt)
    else
        type = 1
    end if
end function flavor_get_multiplicity

```

```

elemental function flavor_get_isospin_type (flv) result (type)
    integer :: type
    type(flavor_t), intent(in) :: flv
    if (associated (flv%prt)) then
        type = particle_data_get_isospin_type (flv%prt)
    else
        type = 1
    end if
end function flavor_get_isospin_type

```

```

elemental function flavor_get_charge_type (flv) result (type)
    integer :: type
    type(flavor_t), intent(in) :: flv
    if (associated (flv%prt)) then
        type = particle_data_get_charge_type (flv%prt)
    else
        type = 1
    end if
end function flavor_get_charge_type

```

```

elemental function flavor_get_color_type (flv) result (type)

```

```

integer :: type
type(flavor_t), intent(in) :: flv
if (associated (flv%prt)) then
    if (flavor_is_antiparticle (flv)) then
        type = - particle_data_get_color_type (flv%prt)
    else
        type = particle_data_get_color_type (flv%prt)
    end if
else
    type = 1
end if
end function flavor_get_color_type

```

These functions return real values:

<Flavors: public>+≡

```

public :: flavor_get_charge
public :: flavor_get_mass
public :: flavor_get_width
public :: flavor_get_isospin

```

<Flavors: procedures>+≡

```

elemental function flavor_get_charge (flv) result (charge)
    real(default) :: charge
    type(flavor_t), intent(in) :: flv
    if (associated (flv%prt)) then
        if (flavor_is_antiparticle (flv)) then
            charge = particle_data_get_charge (flv%prt)
        else
            charge = - particle_data_get_charge (flv%prt)
        end if
    else
        charge = 0
    end if
end function flavor_get_charge

elemental function flavor_get_mass (flv) result (mass)
    real(default) :: mass
    type(flavor_t), intent(in) :: flv
    if (associated (flv%prt)) then
        mass = particle_data_get_mass (flv%prt)
    else
        mass = 0
    end if
end function flavor_get_mass

elemental function flavor_get_width (flv) result (width)
    real(default) :: width
    type(flavor_t), intent(in) :: flv
    if (associated (flv%prt)) then
        width = particle_data_get_width (flv%prt)
    else
        width = 0
    end if
end function flavor_get_width

```

```

elemental function flavor_get_isospin (flv) result (isospin)
  real(default) :: isospin
  type(flavor_t), intent(in) :: flv
  if (associated (flv%prt)) then
    if (flavor_is_antiparticle (flv)) then
      isospin = particle_data_get_isospin (flv%prt)
    else
      isospin = - particle_data_get_isospin (flv%prt)
    end if
  else
    isospin = 0
  end if
end function flavor_get_isospin

```

Comparisons

If one of the flavors is undefined, the other defined, they match.

(Flavors: public)+≡

```

public :: operator(.match.)
public :: operator(==)
public :: operator(/=)

```

(Flavors: interfaces)+≡

```

interface operator(.match.)
  module procedure flavor_match
end interface
interface operator(==)
  module procedure flavor_eq
end interface
interface operator(/=)
  module procedure flavor_neq
end interface

```

(Flavors: procedures)+≡

```

elemental function flavor_match (flv1, flv2) result (eq)
  logical :: eq
  type(flavor_t), intent(in) :: flv1, flv2
  if (flv1%f /= UNDEFINED .and. flv2%f /= UNDEFINED) then
    eq = flv1%f == flv2%f
  else
    eq = .true.
  end if
end function flavor_match

elemental function flavor_eq (flv1, flv2) result (eq)
  logical :: eq
  type(flavor_t), intent(in) :: flv1, flv2
  if (flv1%f /= UNDEFINED .and. flv2%f /= UNDEFINED) then
    eq = flv1%f == flv2%f
  else if (flv1%f == UNDEFINED .and. flv2%f == UNDEFINED) then
    eq = .true.
  else
    eq = .false.
  end if
end function flavor_eq

```

```

    end if
end function flavor_eq

```

```

<Flavors: procedures>+≡
elemental function flavor_neq (flv1, flv2) result (neq)
    logical :: neq
    type(flavor_t), intent(in) :: flv1, flv2
    if (flv1%f /= UNDEFINED .and. flv2%f /= UNDEFINED) then
        neq = flv1%f /= flv2%f
    else if (flv1%f == UNDEFINED .and. flv2%f == UNDEFINED) then
        neq = .false.
    else
        neq = .true.
    end if
end function flavor_neq

```

Tools

Merge two flavor indices. This works only if both are equal or either one is undefined, because we have no off-diagonal flavor entries. Otherwise, generate an invalid flavor.

We cannot use elemental procedures because of the pointer component.

```

<Flavors: public>+≡
    public :: operator(.merge.)

<Flavors: interfaces>+≡
    interface operator(.merge.)
        module procedure merge_flavors0
        module procedure merge_flavors1
    end interface

<Flavors: procedures>+≡
function merge_flavors0 (flv1, flv2) result (flv)
    type(flavor_t) :: flv
    type(flavor_t), intent(in) :: flv1, flv2
    if (flavor_is_defined (flv1) .and. flavor_is_defined (flv2)) then
        if (flv1 == flv2) then
            flv = flv1
        else
            flv%f = INVALID
        end if
    else if (flavor_is_defined (flv1)) then
        flv = flv1
    else if (flavor_is_defined (flv2)) then
        flv = flv2
    end if
end function merge_flavors0

function merge_flavors1 (flv1, flv2) result (flv)
    type(flavor_t), dimension(:), intent(in) :: flv1, flv2
    type(flavor_t), dimension(size(flv1)) :: flv
    integer :: i

```

```

do i = 1, size (flv1)
  flv(i) = flv1(i) .merge. flv2(i)
end do
end function merge_flavors1

```

Generate consecutive color indices for a given flavor. The indices are counted starting with the stored value of *c*, so new indices are created each time this (impure) function is called. The counter can be reset by the optional argument *c_seed* if desired. The optional flag *reverse* is used only for octets. If set, the color and anticolor entries of the octet particle are exchanged.

```

<Flavors: public>+≡
  public :: color_from_flavor

<Flavors: interfaces>+≡
  interface color_from_flavor
    module procedure color_from_flavor0
    module procedure color_from_flavor1
  end interface

<Flavors: procedures>+≡
  function color_from_flavor0 (flv, c_seed, reverse) result (col)
    type(color_t) :: col
    type(flavor_t), intent(in) :: flv
    integer, intent(in), optional :: c_seed
    logical, intent(in), optional :: reverse
    integer, save :: c = 1
    logical :: rev
    if (present (c_seed)) c = c_seed
    rev = .false.; if (present (reverse)) rev = reverse
    select case (flavor_get_color_type (flv))
    case (1)
    case (3)
      call color_init (col, (/ c /)); c = c + 1
    case (-3)
      call color_init (col, (/ -c /)); c = c + 1
    case (8)
      if (rev) then
        call color_init (col, (/ c+1, -c /)); c = c + 2
      else
        call color_init (col, (/ c, -(c+1) /)); c = c + 2
      end if
    end select
  end function color_from_flavor0

  function color_from_flavor1 (flv, c_seed, reverse) result (col)
    type(flavor_t), dimension(:), intent(in) :: flv
    integer, intent(in), optional :: c_seed
    logical, intent(in), optional :: reverse
    type(color_t), dimension(size(flv)) :: col
    integer :: i
    col(1) = color_from_flavor0 (flv(1), c_seed, reverse)
    do i = 2, size (flv)
      col(i) = color_from_flavor0 (flv(i), reverse=reverse)
    end do

```



```
end function color_from_flavor1
```

This procedure returns the flavor object for the antiparticle. The antiparticle code may either be the same code or its negative.

(Flavors: public)+≡

```
public :: flavor_anti
```

(Flavors: procedures)+≡

```
function flavor_anti (flv) result (aflv)
  type(flavor_t) :: aflv
  type(flavor_t), intent(in) :: flv
  if (flavor_has_antiparticle (flv)) then
    aflv%f = - flv%f
  else
    aflv%f = flv%f
  end if
  aflv%prt => flv%prt
end function flavor_anti
```

7.4 Quantum numbers

This module collects helicity, color, and flavor in a single type and defines procedures

```
<quantum_numbers.f90>≡  
  <File header>  
  
  module quantum_numbers  
  
    <Use file utils>  
    use models  
    use flavors  
    use colors  
    use helicities  
  
    <Standard module head>  
  
    <Quantum numbers: public>  
  
    <Quantum numbers: types>  
  
    <Quantum numbers: interfaces>  
  
    contains  
  
    <Quantum numbers: procedures>  
  
  end module quantum_numbers
```

7.4.1 The quantum number type

```
<Quantum numbers: public>≡  
  public :: quantum_numbers_t  
  
<Quantum numbers: types>≡  
  type :: quantum_numbers_t  
    private  
    type(flavor_t) :: f  
    type(color_t) :: c  
    type(helicity_t) :: h  
  end type quantum_numbers_t
```

Define quantum numbers: Initializer form. All arguments may be present or absent.

```
<Quantum numbers: public>+≡  
  public :: quantum_numbers_init  
  
<Quantum numbers: interfaces>≡  
  interface quantum_numbers_init  
    module procedure quantum_numbers_init0_f  
    module procedure quantum_numbers_init0_c  
    module procedure quantum_numbers_init0_h  
    module procedure quantum_numbers_init0_fc  
    module procedure quantum_numbers_init0_fh
```

```

module procedure quantum_numbers_init0_ch
module procedure quantum_numbers_init0_fch
module procedure quantum_numbers_init1_f
module procedure quantum_numbers_init1_c
module procedure quantum_numbers_init1_h
module procedure quantum_numbers_init1_fc
module procedure quantum_numbers_init1_fh
module procedure quantum_numbers_init1_ch
module procedure quantum_numbers_init1_fch
end interface

```

(Quantum numbers: procedures)≡

```

subroutine quantum_numbers_init0_f (qn, flv)
  type(quantum_numbers_t), intent(out) :: qn
  type(flavor_t), intent(in) :: flv
  qn%f = flv
end subroutine quantum_numbers_init0_f

subroutine quantum_numbers_init0_c (qn, col)
  type(quantum_numbers_t), intent(out) :: qn
  type(color_t), intent(in) :: col
  qn%c = col
end subroutine quantum_numbers_init0_c

subroutine quantum_numbers_init0_h (qn, hel)
  type(quantum_numbers_t), intent(out) :: qn
  type(helicity_t), intent(in) :: hel
  qn%h = hel
end subroutine quantum_numbers_init0_h

subroutine quantum_numbers_init0_fc (qn, flv, col)
  type(quantum_numbers_t), intent(out) :: qn
  type(flavor_t), intent(in) :: flv
  type(color_t), intent(in) :: col
  qn%f = flv
  qn%c = col
end subroutine quantum_numbers_init0_fc

subroutine quantum_numbers_init0_fh (qn, flv, hel)
  type(quantum_numbers_t), intent(out) :: qn
  type(flavor_t), intent(in) :: flv
  type(helicity_t), intent(in) :: hel
  qn%f = flv
  qn%h = hel
end subroutine quantum_numbers_init0_fh

subroutine quantum_numbers_init0_ch (qn, col, hel)
  type(quantum_numbers_t), intent(out) :: qn
  type(color_t), intent(in) :: col
  type(helicity_t), intent(in) :: hel
  qn%c = col
  qn%h = hel
end subroutine quantum_numbers_init0_ch

```

```

subroutine quantum_numbers_init0_fch (qn, flv, col, hel)
  type(quantum_numbers_t), intent(out) :: qn
  type(flavor_t), intent(in) :: flv
  type(color_t), intent(in) :: col
  type(helicity_t), intent(in) :: hel
  qn%f = flv
  qn%c = col
  qn%h = hel
end subroutine quantum_numbers_init0_fch

subroutine quantum_numbers_init1_f (qn, flv)
  type(quantum_numbers_t), dimension(:), intent(out) :: qn
  type(flavor_t), dimension(:), intent(in) :: flv
  integer :: i
  do i = 1, size (qn)
    call quantum_numbers_init0_f (qn(i), flv(i))
  end do
end subroutine quantum_numbers_init1_f

subroutine quantum_numbers_init1_c (qn, col)
  type(quantum_numbers_t), dimension(:), intent(out) :: qn
  type(color_t), dimension(:), intent(in) :: col
  integer :: i
  do i = 1, size (qn)
    call quantum_numbers_init0_c (qn(i), col(i))
  end do
end subroutine quantum_numbers_init1_c

subroutine quantum_numbers_init1_h (qn, hel)
  type(quantum_numbers_t), dimension(:), intent(out) :: qn
  type(helicity_t), dimension(:), intent(in) :: hel
  integer :: i
  do i = 1, size (qn)
    call quantum_numbers_init0_h (qn(i), hel(i))
  end do
end subroutine quantum_numbers_init1_h

subroutine quantum_numbers_init1_fc (qn, flv, col)
  type(quantum_numbers_t), dimension(:), intent(out) :: qn
  type(flavor_t), dimension(:), intent(in) :: flv
  type(color_t), dimension(:), intent(in) :: col
  integer :: i
  do i = 1, size (qn)
    call quantum_numbers_init0_fc (qn(i), flv(i), col(i))
  end do
end subroutine quantum_numbers_init1_fc

subroutine quantum_numbers_init1_fh (qn, flv, hel)
  type(quantum_numbers_t), dimension(:), intent(out) :: qn
  type(flavor_t), dimension(:), intent(in) :: flv
  type(helicity_t), dimension(:), intent(in) :: hel
  integer :: i
  do i = 1, size (qn)
    call quantum_numbers_init0_fh (qn(i), flv(i), hel(i))
  end do
end subroutine quantum_numbers_init1_fh

```

```

        end do
    end subroutine quantum_numbers_init1_fh

    subroutine quantum_numbers_init1_ch (qn, col, hel)
        type(quantum_numbers_t), dimension(:), intent(out) :: qn
        type(color_t), dimension(:), intent(in) :: col
        type(helicity_t), dimension(:), intent(in) :: hel
        integer :: i
        do i = 1, size (qn)
            call quantum_numbers_init0_ch (qn(i), col(i), hel(i))
        end do
    end subroutine quantum_numbers_init1_ch

    subroutine quantum_numbers_init1_fch (qn, flv, col, hel)
        type(quantum_numbers_t), dimension(:), intent(out) :: qn
        type(flavor_t), dimension(:), intent(in) :: flv
        type(color_t), dimension(:), intent(in) :: col
        type(helicity_t), dimension(:), intent(in) :: hel
        integer :: i
        do i = 1, size (qn)
            call quantum_numbers_init0_fch (qn(i), flv(i), col(i), hel(i))
        end do
    end subroutine quantum_numbers_init1_fch

```

7.4.2 I/O

Write the quantum numbers in condensed form, enclosed by square brackets. For convenience, introduce also an array version.

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_write

<Quantum numbers: interfaces>+≡
    interface quantum_numbers_write
        module procedure quantum_numbers_write_single
        module procedure quantum_numbers_write_array
    end interface

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_write_single (qn, unit)
        type(quantum_numbers_t), intent(in) :: qn
        integer, intent(in), optional :: unit
        integer :: u
        u = output_unit (unit); if (u < 0) return
        write (u, "(A)", advance="no") "["
        if (flavor_is_defined (qn%f)) then
            call flavor_write (qn%f, u)
            if (color_is_defined (qn%c) .or. helicity_is_defined (qn%h)) &
                write (u, "(1x)", advance="no")
        end if
        if (color_is_defined (qn%c) .or. color_is_ghost (qn%c)) then
            call color_write (qn%c, u)
            if (helicity_is_defined (qn%h)) write (u, "(1x)", advance="no")
        end if
    end subroutine

```

```

        if (helicity_is_defined (qn%h)) then
            call helicity_write (qn%h, u)
        end if
        write (u, "(A)", advance="no") "]"
    end subroutine quantum_numbers_write_single

    subroutine quantum_numbers_write_array (qn, unit)
        type(quantum_numbers_t), dimension(:), intent(in) :: qn
        integer, intent(in), optional :: unit
        integer :: i
        integer :: u
        u = output_unit (unit); if (u < 0) return
        write (u, "(A)", advance="no") "["
        do i = 1, size (qn)
            if (i > 1) write (u, "(A)", advance="no") " / "
            if (flavor_is_defined (qn(i)%f)) then
                call flavor_write (qn(i)%f, u)
                if (color_is_defined (qn(i)%c) .or. helicity_is_defined (qn(i)%h)) &
                    write (u, "(1x)", advance="no")
            end if
            if (color_is_defined (qn(i)%c) .or. color_is_ghost (qn(i)%c)) then
                call color_write (qn(i)%c, u)
                if (helicity_is_defined (qn(i)%h)) write (u, "(1x)", advance="no")
            end if
            if (helicity_is_defined (qn(i)%h)) then
                call helicity_write (qn(i)%h, u)
            end if
        end do
        write (u, "(A)", advance="no") "]"
    end subroutine quantum_numbers_write_array

```

Binary I/O.

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_write_raw
    public :: quantum_numbers_read_raw

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_write_raw (qn, u)
        type(quantum_numbers_t), intent(in) :: qn
        integer, intent(in) :: u
        call flavor_write_raw (qn%f, u)
        call color_write_raw (qn%c, u)
        call helicity_write_raw (qn%h, u)
    end subroutine quantum_numbers_write_raw

    subroutine quantum_numbers_read_raw (qn, u, iostat)
        type(quantum_numbers_t), intent(out) :: qn
        integer, intent(in) :: u
        integer, intent(out), optional :: iostat
        call flavor_read_raw (qn%f, u, iostat=iostat)
        call color_read_raw (qn%c, u, iostat=iostat)
        call helicity_read_raw (qn%h, u, iostat=iostat)
    end subroutine quantum_numbers_read_raw

```

7.4.3 Accessing contents

Color and helicity can be done by elemental functions. Flavor needs explicit specifics because of the pointer assignment.

```
<Quantum numbers: public>+≡
    public :: quantum_numbers_get_flavor
    public :: quantum_numbers_get_color
    public :: quantum_numbers_get_helicity

<Quantum numbers: interfaces>+≡
    interface quantum_numbers_get_flavor
        module procedure quantum_numbers_get_flavor0
        module procedure quantum_numbers_get_flavor1
    end interface

<Quantum numbers: procedures>+≡
    function quantum_numbers_get_flavor0 (qn) result (flv)
        type(flavor_t) :: flv
        type(quantum_numbers_t), intent(in) :: qn
        flv = qn%f
    end function quantum_numbers_get_flavor0

    function quantum_numbers_get_flavor1 (qn) result (flv)
        type(quantum_numbers_t), dimension(:), intent(in) :: qn
        type(flavor_t), dimension(size(qn)) :: flv
        integer :: i
        do i = 1, size (qn)
            flv(i) = qn(i)%f
        end do
    end function quantum_numbers_get_flavor1

    elemental function quantum_numbers_get_color (qn) result (col)
        type(color_t) :: col
        type(quantum_numbers_t), intent(in) :: qn
        col = qn%c
    end function quantum_numbers_get_color

    elemental function quantum_numbers_get_helicity (qn) result (hel)
        type(helicity_t) :: hel
        type(quantum_numbers_t), intent(in) :: qn
        hel = qn%h
    end function quantum_numbers_get_helicity

<Quantum numbers: public>+≡
    public :: quantum_numbers_set_flavor
    public :: quantum_numbers_set_color
    public :: quantum_numbers_set_helicity

<Quantum numbers: interfaces>+≡
    interface quantum_numbers_set_flavor
        module procedure quantum_numbers_set_flavor0
        module procedure quantum_numbers_set_flavor1
    end interface
```

```

<Quantum numbers: procedures>+≡
  subroutine quantum_numbers_set_flavor0 (qn, flv)
    type(quantum_numbers_t), intent(inout) :: qn
    type(flavor_t), intent(in) :: flv
    qn%f = flv
  end subroutine quantum_numbers_set_flavor0

  subroutine quantum_numbers_set_flavor1 (qn, flv)
    type(quantum_numbers_t), dimension(:), intent(inout) :: qn
    type(flavor_t), dimension(:), intent(in) :: flv
    integer :: i
    do i = 1, size (flv)
      qn(i)%f = flv(i)
    end do
  end subroutine quantum_numbers_set_flavor1

  elemental subroutine quantum_numbers_set_color (qn, col)
    type(quantum_numbers_t), intent(inout) :: qn
    type(color_t), intent(in) :: col
    qn%c = col
  end subroutine quantum_numbers_set_color

  elemental subroutine quantum_numbers_set_helicity (qn, hel)
    type(quantum_numbers_t), intent(inout) :: qn
    type(helicity_t), intent(in) :: hel
    qn%h = hel
  end subroutine quantum_numbers_set_helicity

```

This just resets the ghost property of the color/helicity part:

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_set_color_ghost
  public :: quantum_numbers_set_helicity_ghost

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_set_color_ghost (qn, ghost)
    type(quantum_numbers_t), intent(inout) :: qn
    logical, intent(in) :: ghost
    call color_set_ghost (qn%c, ghost)
  end subroutine quantum_numbers_set_color_ghost

  elemental subroutine quantum_numbers_set_helicity_ghost (qn, ghost)
    type(quantum_numbers_t), intent(inout) :: qn
    logical, intent(in) :: ghost
    call helicity_set_ghost (qn%h, ghost)
  end subroutine quantum_numbers_set_helicity_ghost

```

Assign a model to the flavor part of quantum numbers.

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_set_model

<Quantum numbers: interfaces>+≡
  interface quantum_numbers_set_model
    module procedure quantum_numbers_set_model_single
    module procedure quantum_numbers_set_model_array
  end interface

```



```

end interface

<Quantum numbers: procedures>+≡
  subroutine quantum_numbers_set_model_single (qn, model)
    type(quantum_numbers_t), intent(inout) :: qn
    type(model_t), intent(in), target :: model
    call flavor_set_model (qn%f, model)
  end subroutine quantum_numbers_set_model_single

  subroutine quantum_numbers_set_model_array (qn, model)
    type(quantum_numbers_t), dimension(:), intent(inout) :: qn
    type(model_t), intent(in), target :: model
    call flavor_set_model (qn%f, model)
  end subroutine quantum_numbers_set_model_array

```

This is a convenience function: return the color type for the flavor (array).

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_get_color_type

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_get_color_type (qn) result (color_type)
    integer :: color_type
    type(quantum_numbers_t), intent(in) :: qn
    color_type = flavor_get_color_type (qn%f)
  end function quantum_numbers_get_color_type

```

7.4.4 Predicates

Check if the flavor index is valid (including UNDEFINED).

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_are_valid

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_are_valid (qn) result (valid)
    logical :: valid
    type(quantum_numbers_t), intent(in) :: qn
    valid = flavor_is_valid (qn%f)
  end function quantum_numbers_are_valid

```

Check if the flavor part has its particle-data pointer associated (debugging aid).

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_are_associated

<Quantum numbers: procedures>+≡
  elemental function quantum_numbers_are_associated (qn) result (flag)
    logical :: flag
    type(quantum_numbers_t), intent(in) :: qn
    flag = flavor_is_associated (qn%f)
  end function quantum_numbers_are_associated

```

Check if the helicity and color quantum numbers are diagonal. (Unpolarized/colorless also counts as diagonal.) Flavor is diagonal by definition.

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_are_diagonal

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_are_diagonal (qn) result (diagonal)
        logical :: diagonal
        type(quantum_numbers_t), intent(in) :: qn
        diagonal = helicity_is_diagonal (qn%h) .and. color_is_diagonal (qn%c)
    end function quantum_numbers_are_diagonal

```

Check if the color and/or helicity part has the ghost property.

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_is_color_ghost
    public :: quantum_numbers_is_helicity_ghost

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_is_color_ghost (qn) result (ghost)
        logical :: ghost
        type(quantum_numbers_t), intent(in) :: qn
        ghost = color_is_ghost (qn%c)
    end function quantum_numbers_is_color_ghost

    elemental function quantum_numbers_is_helicity_ghost (qn) result (ghost)
        logical :: ghost
        type(quantum_numbers_t), intent(in) :: qn
        ghost = helicity_is_ghost (qn%h)
    end function quantum_numbers_is_helicity_ghost

```

7.4.5 Comparisons

Matching and equality is derived from the individual quantum numbers. The variant `fhmatch` matches only flavor and helicity. The variant `dhmatch` matches only diagonal helicity, if the matching helicity is undefined.

```

<Quantum numbers: public>+≡
    public :: operator(.match.)
    public :: operator(.fmatch.)
    public :: operator(.fhmatch.)
    public :: operator(.dhmatch.)
    public :: operator(==)
    public :: operator(/=)

<Quantum numbers: interfaces>+≡
    interface operator(.match.)
        module procedure quantum_numbers_match
    end interface
    interface operator(.fmatch.)
        module procedure quantum_numbers_match_f
    end interface
    interface operator(.fhmatch.)
        module procedure quantum_numbers_match_fh
    end interface

```

```

interface operator(.dhmatch.)
  module procedure quantum_numbers_match_hel_diag
end interface
interface operator(==)
  module procedure quantum_numbers_eq
end interface
interface operator(/=)
  module procedure quantum_numbers_neq
end interface

(Quantum numbers: procedures) +=
  elemental function quantum_numbers_match (qn1, qn2) result (match)
    logical :: match
    type(quantum_numbers_t), intent(in) :: qn1, qn2
    match = (qn1%f .match. qn2%f) .and. &
      (qn1%c .match. qn2%c) .and. &
      (qn1%h .match. qn2%h)
  end function quantum_numbers_match

  elemental function quantum_numbers_match_f (qn1, qn2) result (match)
    logical :: match
    type(quantum_numbers_t), intent(in) :: qn1, qn2
    match = (qn1%f .match. qn2%f)
  end function quantum_numbers_match_f

  elemental function quantum_numbers_match_fh (qn1, qn2) result (match)
    logical :: match
    type(quantum_numbers_t), intent(in) :: qn1, qn2
    match = (qn1%f .match. qn2%f) .and. &
      (qn1%h .match. qn2%h)
  end function quantum_numbers_match_fh

  elemental function quantum_numbers_match_hel_diag (qn1, qn2) result (match)
    logical :: match
    type(quantum_numbers_t), intent(in) :: qn1, qn2
    match = (qn1%f .match. qn2%f) .and. &
      (qn1%c .match. qn2%c) .and. &
      (qn1%h .dhmatch. qn2%h)
  end function quantum_numbers_match_hel_diag

  elemental function quantum_numbers_eq (qn1, qn2) result (eq)
    logical :: eq
    type(quantum_numbers_t), intent(in) :: qn1, qn2
    eq = (qn1%f == qn2%f) .and. &
      (qn1%c == qn2%c) .and. &
      (qn1%h == qn2%h)
  end function quantum_numbers_eq

  elemental function quantum_numbers_neq (qn1, qn2) result (neq)
    logical :: neq
    type(quantum_numbers_t), intent(in) :: qn1, qn2
    neq = (qn1%f /= qn2%f) .or. &
      (qn1%c /= qn2%c) .or. &
      (qn1%h /= qn2%h)
  end function quantum_numbers_neq

```

Two sets of quantum numbers are compatible if the individual quantum numbers are compatible, depending on the mask. Flavor has to match, regardless of the flavor mask.

If the color flag is set, color is compatible if the ghost property is identical. If the color flag is unset, color has to be identical. I.e., if the flag is set, the color amplitudes can interfere. If it is not set, they must be identical, and there must be no ghost. The latter property is used for expanding physical color flows.

Helicity is compatible if the mask is unset, otherwise it has to match. This determines if two amplitudes can be multiplied (no mask) or traced (mask).

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_are_compatible

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_are_compatible (qn1, qn2, mask) &
        result (flag)
        logical :: flag
        type(quantum_numbers_t), intent(in) :: qn1, qn2
        type(quantum_numbers_mask_t), intent(in) :: mask
        if (mask%h .or. mask%hd) then
            flag = (qn1%f .match. qn2%f) .and. (qn1%h .match. qn2%h)
        else
            flag = (qn1%f .match. qn2%f)
        end if
        if (mask%c) then
            flag = flag .and. (color_is_ghost (qn1%c) .eqv. color_is_ghost (qn2%c))
        else
            flag = flag .and. &
                .not. (color_is_ghost (qn1%c) .or. color_is_ghost (qn2%c)) .and. &
                (qn1%c == qn2%c)
        end if
    end function quantum_numbers_are_compatible

```

This is the analog for a single quantum-number set. We just check for color ghosts; they are excluded if the color mask is unset (color-flow expansion).

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_are_physical

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_are_physical (qn, mask) result (flag)
        logical :: flag
        type(quantum_numbers_t), intent(in) :: qn
        type(quantum_numbers_mask_t), intent(in) :: mask
        if (mask%c) then
            flag = .true.
        else
            flag = .not. color_is_ghost (qn%c)
        end if
    end function quantum_numbers_are_physical

```

7.4.6 Operations

Inherited from the color component: reassign color indices in canonical order.

```
<Quantum numbers: public>+≡
    public :: quantum_numbers_canonicalize_color

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_canonicalize_color (qn)
        type(quantum_numbers_t), dimension(:), intent(inout) :: qn
        call color_canonicalize (qn%c)
    end subroutine quantum_numbers_canonicalize_color
```

Inherited from the color component: make a color map for two matching quantum-number arrays.

```
<Quantum numbers: public>+≡
    public :: quantum_numbers_set_color_map

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_set_color_map (map, qn1, qn2)
        integer, dimension(:,:), intent(out), allocatable :: map
        type(quantum_numbers_t), dimension(:), intent(in) :: qn1, qn2
        call set_color_map (map, qn1%c, qn2%c)
    end subroutine quantum_numbers_set_color_map
```

Inherited from the color component: translate the color part using a color-map array

```
<Quantum numbers: public>+≡
    public :: quantum_numbers_translate_color

<Quantum numbers: interfaces>+≡
    interface quantum_numbers_translate_color
        module procedure quantum_numbers_translate_color0
        module procedure quantum_numbers_translate_color1
    end interface

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_translate_color0 (qn, map, offset)
        type(quantum_numbers_t), intent(inout) :: qn
        integer, dimension(:,:), intent(in) :: map
        integer, intent(in), optional :: offset
        call color_translate (qn%c, map, offset)
    end subroutine quantum_numbers_translate_color0

    subroutine quantum_numbers_translate_color1 (qn, map, offset)
        type(quantum_numbers_t), dimension(:), intent(inout) :: qn
        integer, dimension(:,:), intent(in) :: map
        integer, intent(in), optional :: offset
        call color_translate (qn%c, map, offset)
    end subroutine quantum_numbers_translate_color1
```

Inherited from the color component: return the color index with highest absolute value

```
<Quantum numbers: public>+≡
    public :: quantum_numbers_get_max_color_value
```

```

<Quantum numbers: interfaces>+≡
  interface quantum_numbers_get_max_color_value
    module procedure quantum_numbers_get_max_color_value0
    module procedure quantum_numbers_get_max_color_value1
    module procedure quantum_numbers_get_max_color_value2
  end interface

<Quantum numbers: procedures>+≡
  function quantum_numbers_get_max_color_value0 (qn) result (cmax)
    integer :: cmax
    type(quantum_numbers_t), intent(in) :: qn
    cmax = color_get_max_value0 (qn%c)
    !!! ifort 11.1 v5 demands this
    !!! cmax = color_get_max_value (qn%c)
  end function quantum_numbers_get_max_color_value0

  function quantum_numbers_get_max_color_value1 (qn) result (cmax)
    integer :: cmax
    type(quantum_numbers_t), dimension(:), intent(in) :: qn
    cmax = color_get_max_value1 (qn%c)
    !!! ifort 11.1 v5 demands this
    !!! cmax = color_get_max_value (qn%c)
  end function quantum_numbers_get_max_color_value1

  function quantum_numbers_get_max_color_value2 (qn) result (cmax)
    integer :: cmax
    type(quantum_numbers_t), dimension(:,:), intent(in) :: qn
    cmax = color_get_max_value2 (qn%c)
    !!! ifort 11.1 v5 demands this
    !!! cmax = color_get_max_value (qn%c)
  end function quantum_numbers_get_max_color_value2

```

Inherited from the color component: add an offset to the indices of the color part

```

<Quantum numbers: public>+≡
  public :: quantum_numbers_add_color_offset

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_add_color_offset (qn, offset)
    type(quantum_numbers_t), intent(inout) :: qn
    integer, intent(in) :: offset
    call color_add_offset (qn%c, offset)
  end subroutine quantum_numbers_add_color_offset

```

Given a quantum number array, return all possible color contractions, leaving the other quantum numbers intact.

```

<Quantum numbers: public>+≡
  public :: quantum_number_array_make_color_contractions

<Quantum numbers: procedures>+≡
  subroutine quantum_number_array_make_color_contractions (qn_in, qn_out)
    type(quantum_numbers_t), dimension(:), intent(in) :: qn_in
    type(quantum_numbers_t), dimension(:,:), intent(out), allocatable :: qn_out

```

```

type(color_t), dimension(:,:), allocatable :: col
integer :: i
call color_array_make_contractions (qn_in%c, col)
allocate (qn_out (size (col, 1), size (col, 2)))
do i = 1, size (qn_out, 2)
    qn_out(:,i)%f = qn_in%f
    qn_out(:,i)%c = col(:,i)
    qn_out(:,i)%h = qn_in%h
end do
end subroutine quantum_number_array_make_color_contractions

```

Inherited from the color component: invert the color, switching particle/antiparticle.

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_invert_color

<Quantum numbers: procedures>+≡
    elemental subroutine quantum_numbers_invert_color (qn)
        type(quantum_numbers_t), intent(inout) :: qn
        call color_invert (qn%c)
    end subroutine quantum_numbers_invert_color

```

Merge two quantum number sets: for each entry, if both are defined, combine them to an off-diagonal entry (meaningful only if the input was diagonal). If either entry is undefined, take the defined one.

For flavor, off-diagonal entries are invalid, so both flavors must be equal, otherwise an invalid flavor is inserted.

```

<Quantum numbers: public>+≡
    public :: operator(.merge.)

<Quantum numbers: interfaces>+≡
    interface operator(.merge.)
        module procedure merge_quantum_numbers0
        module procedure merge_quantum_numbers1
    end interface

<Quantum numbers: procedures>+≡
    function merge_quantum_numbers0 (qn1, qn2) result (qn3)
        type(quantum_numbers_t) :: qn3
        type(quantum_numbers_t), intent(in) :: qn1, qn2
        qn3%f = qn1%f .merge. qn2%f
        qn3%c = qn1%c .merge. qn2%c
        qn3%h = qn1%h .merge. qn2%h
    end function merge_quantum_numbers0

    function merge_quantum_numbers1 (qn1, qn2) result (qn3)
        type(quantum_numbers_t), dimension(:), intent(in) :: qn1, qn2
        type(quantum_numbers_t), dimension(size(qn1)) :: qn3
        qn3%f = qn1%f .merge. qn2%f
        qn3%c = qn1%c .merge. qn2%c
        qn3%h = qn1%h .merge. qn2%h
    end function merge_quantum_numbers1

```

7.4.7 The quantum number mask

The quantum numbers mask is true for quantum numbers that should be ignored or summed over. The three mandatory entries correspond to flavor, color, and helicity, respectively.

There is an additional entry `cg`: If false, the color-ghosts property should be kept even if color is ignored. This is relevant only if `c` is set, otherwise it is always false.

The flag `hd` tells that only diagonal entries in helicity should be kept. If `h` is set, `hd` is irrelevant and will be kept `.false.`

```
<Quantum numbers: public>+≡
  public :: quantum_numbers_mask_t

<Quantum numbers: types>+≡
  type :: quantum_numbers_mask_t
    private
    logical :: f = .false.
    logical :: c = .false.
    logical :: cg = .false.
    logical :: h = .false.
    logical :: hd = .false.
  end type quantum_numbers_mask_t
```

Define a quantum number mask: Constructor form

```
<Quantum numbers: public>+≡
  public :: new_quantum_numbers_mask

<Quantum numbers: procedures>+≡
  elemental function new_quantum_numbers_mask &
    (mask_f, mask_c, mask_h, mask_cg, mask_hd) result (mask)
    type(quantum_numbers_mask_t) :: mask
    logical, intent(in) :: mask_f, mask_c, mask_h
    logical, intent(in), optional :: mask_cg
    logical, intent(in), optional :: mask_hd
    call quantum_numbers_mask_init &
      (mask, mask_f, mask_c, mask_h, mask_cg, mask_hd)
  end function new_quantum_numbers_mask
```

Define quantum numbers: Initializer form

```
<Quantum numbers: public>+≡
  public :: quantum_numbers_mask_init

<Quantum numbers: procedures>+≡
  elemental subroutine quantum_numbers_mask_init &
    (mask, mask_f, mask_c, mask_h, mask_cg, mask_hd)
    type(quantum_numbers_mask_t), intent(out) :: mask
    logical, intent(in) :: mask_f, mask_c, mask_h
    logical, intent(in), optional :: mask_cg, mask_hd
    mask%f = mask_f
    mask%c = mask_c
    mask%h = mask_h
    if (present (mask_cg)) then
      if (mask%c) mask%cg = mask_cg
    else
```



```

        mask%cg = mask_c
    end if
    if (present (mask_hd)) then
        if (.not. mask%h) mask%hd = mask_hd
    end if
end subroutine quantum_numbers_mask_init

```

Write a quantum numbers mask

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_mask_write

<Quantum numbers: interfaces>+≡
    interface quantum_numbers_mask_write
        module procedure quantum_numbers_mask_write_single
        module procedure quantum_numbers_mask_write_array
    end interface

<Quantum numbers: procedures>+≡
    subroutine quantum_numbers_mask_write_single (mask, unit)
        type(quantum_numbers_mask_t), intent(in) :: mask
        integer, intent(in), optional :: unit
        integer :: u
        u = output_unit (unit); if (u < 0) return
        write (u, "(A)", advance="no") "["
        write (u, "(L1)", advance="no") mask%f
        write (u, "(L1)", advance="no") mask%c
        if (.not.mask%cg) write (u, "('g')", advance="no")
        write (u, "(L1)", advance="no") mask%h
        if (mask%hd) write (u, "('d')", advance="no")
        write (u, "(A)", advance="no") "]"
    end subroutine quantum_numbers_mask_write_single

    subroutine quantum_numbers_mask_write_array (mask, unit)
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
        integer, intent(in), optional :: unit
        integer :: u, i
        u = output_unit (unit); if (u < 0) return
        write (u, "(A)", advance="no") "["
        do i = 1, size (mask)
            if (i > 1) write (u, "(A)", advance="no") "/"
            write (u, "(L1)", advance="no") mask(i)%f
            write (u, "(L1)", advance="no") mask(i)%c
            if (.not.mask(i)%cg) write (u, "('g')", advance="no")
            write (u, "(L1)", advance="no") mask(i)%h
            if (mask(i)%hd) write (u, "('d')", advance="no")
        end do
        write (u, "(A)", advance="no") "]"
    end subroutine quantum_numbers_mask_write_array

```

7.4.8 Setting mask components

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_mask_set_flavor

```

```

public :: quantum_numbers_mask_set_color
public :: quantum_numbers_mask_set_helicity
<Quantum numbers: procedures>+≡
elemental subroutine quantum_numbers_mask_set_flavor (mask, mask_f)
  type(quantum_numbers_mask_t), intent(inout) :: mask
  logical, intent(in) :: mask_f
  mask%f = mask_f
end subroutine quantum_numbers_mask_set_flavor

elemental subroutine quantum_numbers_mask_set_color (mask, mask_c, mask_cg)
  type(quantum_numbers_mask_t), intent(inout) :: mask
  logical, intent(in) :: mask_c
  logical, intent(in), optional :: mask_cg
  mask%c = mask_c
  if (present (mask_cg)) then
    if (mask%c) mask%cg = mask_cg
  else
    mask%cg = mask_c
  end if
end subroutine quantum_numbers_mask_set_color

elemental subroutine quantum_numbers_mask_set_helicity (mask, mask_h, mask_hd)
  type(quantum_numbers_mask_t), intent(inout) :: mask
  logical, intent(in) :: mask_h
  logical, intent(in), optional :: mask_hd
  mask%h = mask_h
  if (present (mask_hd)) then
    if (.not. mask%h) mask%hd = mask_hd
  end if
end subroutine quantum_numbers_mask_set_helicity

```

The following routines assign part of a mask, depending on the flags given.

```

<Quantum numbers: public>+≡
public :: quantum_numbers_mask_assign
<Quantum numbers: procedures>+≡
elemental subroutine quantum_numbers_mask_assign &
  (mask, mask_in, flavor, color, helicity)
  type(quantum_numbers_mask_t), intent(inout) :: mask
  type(quantum_numbers_mask_t), intent(in) :: mask_in
  logical, intent(in), optional :: flavor, color, helicity
  if (present (flavor)) then
    if (flavor) then
      mask%f = mask_in%f
    end if
  end if
  if (present (color)) then
    if (color) then
      mask%c = mask_in%c
      mask%cg = mask_in%cg
    end if
  end if
  if (present (helicity)) then
    if (helicity) then

```

```

        mask%h = mask_in%h
        mask%hd = mask_in%hd
    end if
end if
end subroutine quantum_numbers_mask_assign

```

7.4.9 Mask predicates

Return true if either one of the entries is set:

```

<Quantum numbers: public>+≡
    public :: any

<Quantum numbers: interfaces>+≡
    interface any
        module procedure quantum_numbers_mask_any
    end interface

<Quantum numbers: procedures>+≡
    function quantum_numbers_mask_any (mask) result (match)
        logical :: match
        type(quantum_numbers_mask_t), intent(in) :: mask
        match = mask%f .or. mask%c .or. mask%h .or. mask%hd
    end function quantum_numbers_mask_any

```

7.4.10 Operators

The OR operation is applied to all components.

```

<Quantum numbers: public>+≡
    public :: operator(.or.)

<Quantum numbers: interfaces>+≡
    interface operator(.or.)
        module procedure quantum_numbers_mask_or
    end interface

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_mask_or (mask1, mask2) result (mask)
        type(quantum_numbers_mask_t) :: mask
        type(quantum_numbers_mask_t), intent(in) :: mask1, mask2
        mask%f = mask1%f .or. mask2%f
        mask%c = mask1%c .or. mask2%c
        if (mask%c) mask%cg = mask1%cg .or. mask2%cg
        mask%h = mask1%h .or. mask2%h
        if (.not. mask%h) mask%hd = mask1%hd .or. mask2%hd
    end function quantum_numbers_mask_or

```

7.4.11 Mask comparisons

Return true if the two masks are equivalent / differ:

```

<Quantum numbers: public>+≡

```

```

public :: operator(.eqv.)
public :: operator(.neqv.)

<Quantum numbers: interfaces>+≡
interface operator(.eqv.)
  module procedure quantum_numbers_mask_eqv
end interface
interface operator(.neqv.)
  module procedure quantum_numbers_mask_neqv
end interface

<Quantum numbers: procedures>+≡
elemental function quantum_numbers_mask_eqv (mask1, mask2) result (eqv)
  logical :: eqv
  type(quantum_numbers_mask_t), intent(in) :: mask1, mask2
  eqv = (mask1%f .eqv. mask2%f) .and. &
        (mask1%c .eqv. mask2%c) .and. &
        (mask1%cg .eqv. mask2%cg) .and. &
        (mask1%h .eqv. mask2%h) .and. &
        (mask1%hd .eqv. mask2%hd)
end function quantum_numbers_mask_eqv

elemental function quantum_numbers_mask_neqv (mask1, mask2) result (neqv)
  logical :: neqv
  type(quantum_numbers_mask_t), intent(in) :: mask1, mask2
  neqv = (mask1%f .neqv. mask2%f) .or. &
        (mask1%c .neqv. mask2%c) .or. &
        (mask1%cg .neqv. mask2%cg) .or. &
        (mask1%h .neqv. mask2%h) .or. &
        (mask1%hd .neqv. mask2%hd)
end function quantum_numbers_mask_neqv

```

7.4.12 Apply a mask

Applying a mask to the quantum number object means undefining those entries where the mask is set. The others remain unaffected.

The `hd` mask has the special property that it “diagonalizes” helicity, i.e., the second helicity entry is dropped and the result is a diagonal helicity quantum number.

```

<Quantum numbers: public>+≡
public :: quantum_numbers_undefine
public :: quantum_numbers_undefined

<Quantum numbers: interfaces>+≡
interface quantum_numbers_undefined
  module procedure quantum_numbers_undefined0
  module procedure quantum_numbers_undefined1
  module procedure quantum_numbers_undefined11
end interface

<Quantum numbers: procedures>+≡
elemental subroutine quantum_numbers_undefine (qn, mask)
  type(quantum_numbers_t), intent(inout) :: qn

```

```

type(quantum_numbers_mask_t), intent(in) :: mask
if (mask%f) call flavor_undefine (qn%f)
if (mask%c) call color_undefine (qn%c, undefine_ghost=mask%cg)
if (mask%h) then
    call helicity_undefine (qn%h)
else if (mask%hd) then
    if (.not. helicity_is_diagonal (qn%h)) then
        call helicity_diagonalize (qn%h)
    end if
end if
end if
end subroutine quantum_numbers_undefine

function quantum_numbers_undefined0 (qn, mask) result (qn_new)
type(quantum_numbers_t), intent(in) :: qn
type(quantum_numbers_mask_t), intent(in) :: mask
type(quantum_numbers_t) :: qn_new
qn_new = qn
call quantum_numbers_undefine (qn_new, mask)
end function quantum_numbers_undefined0

function quantum_numbers_undefined1 (qn, mask) result (qn_new)
type(quantum_numbers_t), dimension(:), intent(in) :: qn
type(quantum_numbers_mask_t), intent(in) :: mask
type(quantum_numbers_t), dimension(size(qn)) :: qn_new
qn_new = qn
call quantum_numbers_undefine (qn_new, mask)
end function quantum_numbers_undefined1

function quantum_numbers_undefined11 (qn, mask) result (qn_new)
type(quantum_numbers_t), dimension(:), intent(in) :: qn
type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
type(quantum_numbers_t), dimension(size(qn)) :: qn_new
qn_new = qn
call quantum_numbers_undefine (qn_new, mask)
end function quantum_numbers_undefined11

```

Return true if the input quantum number set has entries that would be removed by the applied mask, e.g., if polarization is defined but `mask%h` is set:

```

<Quantum numbers: public>+≡
public :: quantum_numbers_are_redundant

<Quantum numbers: procedures>+≡
elemental function quantum_numbers_are_redundant (qn, mask) &
    result (redundant)
logical :: redundant
type(quantum_numbers_t), intent(in) :: qn
type(quantum_numbers_mask_t), intent(in) :: mask
redundant = .false.
if (mask%f) then
    redundant = flavor_is_defined (qn%f)
end if
if (mask%c) then
    redundant = color_is_defined (qn%c)
end if

```

```

    if (mask%h) then
        redundant = helicity_is_defined (qn%h)
    else if (mask%hd) then
        redundant = .not. helicity_is_diagonal (qn%h)
    end if
end function quantum_numbers_are_redundant

```

Return true if the helicity flag is set or the diagonal-helicity flag is set.

```

<Quantum numbers: public>+≡
    public :: quantum_numbers_mask_diagonal_helicity

<Quantum numbers: procedures>+≡
    elemental function quantum_numbers_mask_diagonal_helicity (mask) &
        result (flag)
        logical :: flag
        type(quantum_numbers_mask_t), intent(in) :: mask
        flag = mask%h .or. mask%hd
    end function quantum_numbers_mask_diagonal_helicity

```

7.5 State matrices

This module deals with the internal state of a particle system, i.e., with its density matrix in flavor, color, and helicity space.

```
<state_matrices.f90>≡  
<File header>  
  
module state_matrices  
  
  <Use kinds>  
  <Use file utils>  
  use diagnostics !NODEP!  
  use models  
  use flavors  
  use colors  
  use helicities  
  use quantum_numbers  
  
  <Standard module head>  
  
  <State matrices: public>  
  
  <State matrices: parameters>  
  
  <State matrices: types>  
  
  <State matrices: interfaces>  
  
contains  
  
  <State matrices: procedures>  
  
end module state_matrices
```

7.5.1 Nodes of the quantum state trie

A quantum state object represents an unnormalized density matrix, i.e., an array of possibilities for flavor, color, and helicity indices with associated complex values. Physically, the trace of this matrix is the summed squared matrix element for an interaction, and the matrix elements divided by this value correspond to the flavor-color-helicity density matrix. (Flavor and color are diagonal.)

We store density matrices as tries, that is, as trees where each branching represents the possible quantum numbers of a particle. The first branching is the first particle in the system. A leaf (the node corresponding to the last particle) contains the value of the matrix element.

Each node contains a flavor, color, and helicity entry. Note that each of those entries may be actually undefined, so we can also represent, e.g., unpolarized particles.

The value is meaningful only for leaves, which have no child nodes. There is a pointer to the parent node which allows for following the trie downwards from a leaf, it is null for a root node. The child nodes are implemented as a list,

so there is a pointer to the first and last child, and each node also has a **next** pointer to the next sibling.

The root node does not correspond to a particle, only its children do. The quantum numbers of the root node are irrelevant and will not be set. However, we use a common type for the three classes (root, branch, leaf); they may easily be distinguished by the association status of parent and child.

Node type

The node is linked in all directions: the parent, the first and last in the list of children, and the previous and next sibling. This allows us for adding and removing nodes and whole branches anywhere in the trie. (Circular links are not allowed, however.). The node holds its associated set of quantum numbers. The integer index, which is set only for leaf nodes, is the index of the corresponding matrix element value within the state matrix.

Temporarily, matrix-element values may be stored within a leaf node. This is used during state-matrix factorization. When the state matrix is **frozen**, these values are transferred to the matrix-element array within the host state matrix.

```
<State matrices: types>≡
  type :: node_t
    private
    type(quantum_numbers_t) :: qn
    type(node_t), pointer :: parent => null ()
    type(node_t), pointer :: child_first => null ()
    type(node_t), pointer :: child_last => null ()
    type(node_t), pointer :: next => null ()
    type(node_t), pointer :: previous => null ()
    integer :: me_index = 0
    integer, dimension(:), allocatable :: me_count
    complex(default) :: me = 0
  end type node_t
```

Operations on nodes

Recursively deallocate all children of the current node. This includes any values associated with the children.

```
<State matrices: procedures>≡
  pure recursive subroutine node_delete_offspring (node)
    type(node_t), pointer :: node
    type(node_t), pointer :: child
    child => node%child_first
    do while (associated (child))
      node%child_first => node%child_first%next
      call node_delete_offspring (child)
      deallocate (child)
    end do
    node%child_last => null ()
  end subroutine node_delete_offspring
```


Remove a node including its offspring. Adjust the pointers of parent and siblings, if necessary.

```

<State matrices: procedures>+≡
  pure subroutine node_delete (node)
    type(node_t), pointer :: node
    call node_delete_offspring (node)
    if (associated (node%previous)) then
      node%previous%next => node%next
    else if (associated (node%parent)) then
      node%parent%child_first => node%next
    end if
    if (associated (node%next)) then
      node%next%previous => node%previous
    else if (associated (node%parent)) then
      node%parent%child_last => node%previous
    end if
    deallocate (node)
  end subroutine node_delete

```

Append a child node

```

<State matrices: procedures>+≡
  subroutine node_append_child (node, child)
    type(node_t), target, intent(inout) :: node
    type(node_t), pointer :: child
    allocate (child)
    if (associated (node%child_last)) then
      node%child_last%next => child
      child%previous => node%child_last
    else
      node%child_first => child
    end if
    node%child_last => child
    child%parent => node
  end subroutine node_append_child

```

I/O

Output of a single node, no recursion. We print the quantum numbers in square brackets, then the value (if any).

```

<State matrices: procedures>+≡
  subroutine node_write (node, me_array, verbose, unit)
    type(node_t), intent(in) :: node
    complex(default), dimension(:), intent(in), optional :: me_array
    logical, intent(in), optional :: verbose
    integer, intent(in), optional :: unit
    logical :: verb
    integer :: u
    verb = .false.; if (present (verbose)) verb = verbose
    u = output_unit (unit); if (u < 0) return
    call quantum_numbers_write (node%qn, u)
    if (node%me_index /= 0) then
      write (u, "(A,I0,A)", advance="no") " => ME(", node%me_index, ")"

```

```

    if (present (me_array)) then
      write (u, "(A)", advance="no") " = "
      if (aimag (me_array(node%me_index)) == 0) then
        write (u, "(1P,G19.12)", advance="no") real (me_array(node%me_index))
      else
        write (u, "(1P,G19.12,',',G19.12)", advance="no") me_array(node%me_index)
      end if
    end if
  end if
end if
write (u, *)
if (verb) then
  call ptr_write ("parent      ", node%parent)
  call ptr_write ("child_first", node%child_first)
  call ptr_write ("child_last ", node%child_last)
  call ptr_write ("next       ", node%next)
  call ptr_write ("previous   ", node%previous)
end if
contains
subroutine ptr_write (label, node)
  character(*), intent(in) :: label
  type(node_t), pointer :: node
  if (associated (node)) then
    write (u, "(10x,A,1x,'->',1x)", advance="no") label
    call quantum_numbers_write (node%qn, u)
    write (u, *)
  end if
end subroutine ptr_write
end subroutine node_write

```

Recursive output of a node:

(State matrices: procedures)+≡

```

recursive subroutine node_write_rec (node, me_array, verbose, indent, unit)
  type(node_t), intent(in), target :: node
  complex(default), dimension(:), intent(in), optional :: me_array
  logical, intent(in), optional :: verbose
  integer, intent(in), optional :: indent
  integer, intent(in), optional :: unit
  type(node_t), pointer :: current
  logical :: verb
  integer :: i, u
  verb = .false.; if (present (verbose)) verb = verbose
  i = 0; if (present (indent)) i = indent
  u = output_unit (unit); if (u < 0) return
  current => node%child_first
  do while (associated (current))
    write (u, "(A)", advance="no") repeat (" ", i)
    call node_write (current, me_array, verb, u)
    call node_write_rec (current, me_array, verb, i+2, u)
    current => current%next
  end do
end subroutine node_write_rec

```

Binary I/O. Matrix elements are written only for leaf nodes. this was actually

a pointer is lost.

(State matrices: procedures)+≡

```

recursive subroutine node_write_raw_rec (node, u)
  type(node_t), intent(in), target :: node
  integer, intent(in) :: u
  logical :: associated_child_first, associated_next
  call quantum_numbers_write_raw (node%qn, u)
  associated_child_first = associated (node%child_first)
  write (u) associated_child_first
  associated_next = associated (node%next)
  write (u) associated_next
  if (associated_child_first) then
    call node_write_raw_rec (node%child_first, u)
  else
    write (u) node%me_index
  end if
  if (associated_next) then
    call node_write_raw_rec (node%next, u)
  end if
end subroutine node_write_raw_rec

recursive subroutine node_read_raw_rec (node, u, parent, iostat)
  type(node_t), intent(out), target :: node
  integer, intent(in) :: u
  type(node_t), intent(in), optional, target :: parent
  integer, intent(out), optional :: iostat
  logical :: associated_child_first, associated_next
  type(node_t), pointer :: child
  call quantum_numbers_read_raw (node%qn, u, iostat=iostat)
  read (u, iostat=iostat) associated_child_first
  read (u, iostat=iostat) associated_next
  if (present (parent)) node%parent => parent
  if (associated_child_first) then
    allocate (child)
    node%child_first => child
    node%child_last => null ()
    call node_read_raw_rec (child, u, node, iostat=iostat)
    do while (associated (child))
      child%previous => node%child_last
      node%child_last => child
      child => child%next
    end do
  else
    read (u, iostat=iostat) node%me_index
  end if
  if (associated_next) then
    allocate (node%next)
    call node_read_raw_rec (node%next, u, parent, iostat=iostat)
  end if
end subroutine node_read_raw_rec

```

7.5.2 State matrix

Definition

The quantum state object is a container that keeps and hides the root node. For direct accessibility of values, they are stored in a separate array. The leaf nodes of the quantum-number tree point to those values, once the state matrix is finalized.

The `norm` component is redefined if a common factor is extracted from all nodes.

```
<State matrices: public>≡
  public :: state_matrix_t

<State matrices: types>+≡
  type :: state_matrix_t
    private
      type(node_t), pointer :: root => null ()
      integer :: depth = 0
      integer :: n_matrix_elements = 0
      logical :: leaf_nodes_store_values = .false.
      integer :: n_counters = 0
      complex(default), dimension(:), allocatable :: me
      real(default) :: norm = 1
  end type state_matrix_t
```

This initializer allocates the root node but does not fill anything. We declare whether values are stored within the nodes during state-matrix construction, and how many counters should be maintained (default: none).

```
<State matrices: public>+≡
  public :: state_matrix_init

<State matrices: procedures>+≡
  elemental subroutine state_matrix_init (state, store_values, n_counters)
    type(state_matrix_t), intent(out) :: state
    logical, intent(in), optional :: store_values
    integer, intent(in), optional :: n_counters
    allocate (state%root)
    if (present (store_values)) &
      state%leaf_nodes_store_values = store_values
    if (present (n_counters)) state%n_counters = n_counters
  end subroutine state_matrix_init
```

This recursively deletes all children of the root node, restoring the initial state. The matrix element array is not finalized, since it does not contain physical entries, just pointers.

```
<State matrices: public>+≡
  public :: state_matrix_final

<State matrices: procedures>+≡
  elemental subroutine state_matrix_final (state)
    type(state_matrix_t), intent(inout) :: state
    if (allocated (state%me)) deallocate (state%me)
    if (associated (state%root)) call node_delete (state%root)
    state%depth = 0
```

```

state%n_matrix_elements = 0
end subroutine state_matrix_final

```

Output: Present the tree as a nested list with appropriate indentation.

```

<State matrices: public>+≡
public :: state_matrix_write

<State matrices: procedures>+≡
subroutine state_matrix_write (state, unit, write_value_list, verbose)
  type(state_matrix_t), intent(in) :: state
  logical, intent(in), optional :: write_value_list, verbose
  integer, intent(in), optional :: unit
  integer :: u
  integer :: i
  u = output_unit (unit); if (u < 0) return
  write (u, *) "State matrix: norm = ", state%norm
  if (associated (state%root)) then
    if (allocated (state%me)) then
      call node_write_rec (state%root, state%me, verbose, 1, u)
    else
      call node_write_rec (state%root, verbose=verbose, indent=1, unit=u)
    end if
  end if
  if (present (write_value_list)) then
    if (write_value_list .and. allocated (state%me)) then
      do i = 1, size (state%me)
        write (u, "(1x,I0,A)", advance="no") i, ":"
        write (u, *) state%me(i)
      end do
    end if
  end if
end subroutine state_matrix_write

```

Binary I/O. The auxiliary matrix-element array is not written, but reconstructed after reading the tree.

```

<State matrices: public>+≡
public :: state_matrix_write_raw
public :: state_matrix_read_raw

<State matrices: procedures>+≡
subroutine state_matrix_write_raw (state, u)
  type(state_matrix_t), intent(in) :: state
  integer, intent(in) :: u
  logical :: associated_root
  associated_root = associated (state%root)
  write (u) associated_root
  if (associated_root) then
    write (u) state%depth
    write (u) state%norm
    call node_write_raw_rec (state%root, u)
  end if
end subroutine state_matrix_write_raw

subroutine state_matrix_read_raw (state, u, iostat)

```

```

type(state_matrix_t), intent(out) :: state
integer, intent(in) :: u
integer, intent(out), optional :: iostat
logical :: associated_root
read (u, iostat=iostat) associated_root
if (associated_root) then
    read (u, iostat=iostat) state%depth
    read (u, iostat=iostat) state%norm
    call state_matrix_init (state)
    call node_read_raw_rec (state%root, u, iostat=iostat)
    call state_matrix_freeze (state)
end if
end subroutine state_matrix_read_raw

```

Properties of the quantum state

A state is defined if its root is allocated:

```

<State matrices: public>+≡
public :: state_matrix_is_defined

<State matrices: procedures>+≡
elemental function state_matrix_is_defined (state) result (defined)
logical :: defined
type(state_matrix_t), intent(in) :: state
defined = associated (state%root)
end function state_matrix_is_defined

```

A state is empty if its depth is zero:

```

<State matrices: public>+≡
public :: state_matrix_is_empty

<State matrices: procedures>+≡
elemental function state_matrix_is_empty (state) result (flag)
logical :: flag
type(state_matrix_t), intent(in) :: state
flag = state%depth == 0
end function state_matrix_is_empty

```

Return the number of matrix-element values.

```

<State matrices: public>+≡
public :: state_matrix_get_n_matrix_elements

<State matrices: procedures>+≡
function state_matrix_get_n_matrix_elements (state) result (n)
integer :: n
type(state_matrix_t), intent(in) :: state
n = state%n_matrix_elements
end function state_matrix_get_n_matrix_elements

```

Return the number of leaves. This can be larger than the number of independent matrix elements.

```

<State matrices: public>+≡
public :: state_matrix_get_n_leaves

```

```

<State matrices: procedures>+≡
function state_matrix_get_n_leaves (state) result (n)
  integer :: n
  type(state_matrix_t), intent(in) :: state
  type(state_iterator_t) :: it
  n = 0
  call state_iterator_init (it, state)
  do while (state_iterator_is_valid (it))
    n = n + 1
    call state_iterator_advance (it)
  end do
end function state_matrix_get_n_leaves

```

Return the depth:

```

<State matrices: public>+≡
public :: state_matrix_get_depth

<State matrices: procedures>+≡
function state_matrix_get_depth (state) result (depth)
  integer :: depth
  type(state_matrix_t), intent(in) :: state
  depth = state%depth
end function state_matrix_get_depth

```

Return the norm:

```

<State matrices: public>+≡
public :: state_matrix_get_norm

<State matrices: procedures>+≡
function state_matrix_get_norm (state) result (norm)
  real(default) :: norm
  type(state_matrix_t), intent(in) :: state
  norm = state%norm
end function state_matrix_get_norm

```

Retrieving contents

Return the quantum number array, using an index. We have to scan the state matrix since there is no shortcut.

```

<State matrices: public>+≡
public :: state_matrix_get_quantum_numbers

<State matrices: procedures>+≡
function state_matrix_get_quantum_numbers (state, i) result (qn)
  type(state_matrix_t), intent(in), target :: state
  integer, intent(in) :: i
  type(quantum_numbers_t), dimension(state%depth) :: qn
  type(state_iterator_t) :: it
  integer :: k
  k = 0
  call state_iterator_init (it, state)
  do while (state_iterator_is_valid (it))

```

```

        k = k + 1
        if (k == i) then
            qn = state_iterator_get_quantum_numbers (it)
            return
        end if
        call state_iterator_advance (it)
    end do
end function state_matrix_get_quantum_numbers

```

Return a single matrix element using its index. Works only if the shortcut array is allocated.

```

<State matrices: public>+≡
    public :: state_matrix_get_matrix_element

<State matrices: procedures>+≡
    function state_matrix_get_matrix_element (state, i) result (me)
        complex(default) :: me
        type(state_matrix_t), intent(in) :: state
        integer, intent(in) :: i
        if (allocated (state%me)) then
            me = state%me(i)
        else
            me = 0
        end if
    end function state_matrix_get_matrix_element

```

Return the color index with maximum absolute value that is present within the state matrix.

```

<State matrices: public>+≡
    public :: state_matrix_get_max_color_value

<State matrices: procedures>+≡
    function state_matrix_get_max_color_value (state) result (cmax)
        integer :: cmax
        type(state_matrix_t), intent(in) :: state
        if (associated (state%root)) then
            cmax = node_get_max_color_value (state%root)
        else
            cmax = 0
        end if
    contains
        recursive function node_get_max_color_value (node) result (cmax)
            integer :: cmax
            type(node_t), intent(in), target :: node
            type(node_t), pointer :: current
            cmax = quantum_numbers_get_max_color_value (node%qn)
            current => node%child_first
            do while (associated (current))
                cmax = max (cmax, node_get_max_color_value (current))
                current => current%next
            end do
        end function node_get_max_color_value
    end function state_matrix_get_max_color_value

```


Building the quantum state

The procedure generates a branch associated to the input array of quantum numbers. If the branch exists already, it is used.

Optionally, we set the matrix-element index, a value (which may be added to the previous one), and increment one of the possible counters. We may also return the matrix element index of the current node.

```
(State matrices: public)+≡
    public :: state_matrix_add_state

(State matrices: procedures)+≡
    subroutine state_matrix_add_state &
        (state, qn, index, value, sum_values, counter_index, me_index)
        type(state_matrix_t), intent(inout) :: state
        type(quantum_numbers_t), dimension(:), intent(in) :: qn
        integer, intent(in), optional :: index
        complex(default), intent(in), optional :: value
        logical, intent(in), optional :: sum_values
        integer, intent(in), optional :: counter_index
        integer, intent(out), optional :: me_index
        logical :: set_index, get_index, add
        set_index = present (index)
        get_index = present (me_index)
        add = .false.; if (present (sum_values)) add = sum_values
        if (state%depth == 0) then
            state%depth = size (qn)
        else if (state%depth /= size (qn)) then
            call state_matrix_write (state)
            call msg_bug ("State matrix: depth mismatch")
        end if
        if (size (qn) > 0) call node_make_branch (state%root, qn)
contains
        recursive subroutine node_make_branch (parent, qn)
            type(node_t), pointer :: parent
            type(quantum_numbers_t), dimension(:), intent(in) :: qn
            type(node_t), pointer :: child
            logical :: match
            match = .false.
            child => parent%child_first
            SCAN_CHILDREN: do while (associated (child))
                match = child%qn == qn(1)
                if (match) exit SCAN_CHILDREN
                child => child%next
            end do SCAN_CHILDREN
            if (.not. match) then
                call node_append_child (parent, child)
                child%qn = qn(1)
            end if
            select case (size (qn))
            case (1)
                if (.not. match) then
                    state%n_matrix_elements = state%n_matrix_elements + 1
                    child%me_index = state%n_matrix_elements
                end if
```

```

    if (set_index) then
        child%me_index = index
    end if
    if (get_index) then
        me_index = child%me_index
    end if
    if (present (counter_index)) then
        if (.not. allocated (child%me_count)) then
            allocate (child%me_count (state%n_counters))
            child%me_count = 0
        end if
        child%me_count(counter_index) = child%me_count(counter_index) + 1
    end if
    if (present (value)) then
        if (add) then
            child%me = child%me + value
        else
            child%me = value
        end if
    end if
    case (2:)
        call node_make_branch (child, qn(2:))
    end select
end subroutine node_make_branch
end subroutine state_matrix_add_state

```

Remove irrelevant flavor/color/helicity labels and the corresponding branchings. The masks indicate which particles are affected; the masks length should coincide with the depth of the trie (without the root node). Recursively scan the whole tree, starting from the leaf nodes and working up to the root node. If a mask entry is set for the current tree level, scan the children there. For each child within that level make a new empty branch where the masked quantum number is undefined. Then recursively combine all following children with matching quantum number into this new node and move on.

```

<State matrices: public>+≡
    public :: state_matrix_collapse

<State matrices: procedures>+≡
    subroutine state_matrix_collapse (state, mask)
        type(state_matrix_t), intent(inout) :: state
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
        type(state_matrix_t) :: red_state
        if (state_matrix_is_defined (state)) then
            call state_matrix_reduce (state, mask, red_state)
            call state_matrix_final (state)
            state = red_state
        end if
    end subroutine state_matrix_collapse

```

Transform the given state matrix into a reduced state matrix where some quantum numbers are removed, as indicated by the mask. The procedure creates a new state matrix, so the old one can be deleted after this if it is no longer used.

```

<State matrices: public>+≡

```

```

public :: state_matrix_reduce
<State matrices: procedures>+≡
subroutine state_matrix_reduce (state, mask, red_state)
  type(state_matrix_t), intent(in), target :: state
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
  type(state_matrix_t), intent(out) :: red_state
  type(state_iterator_t) :: it
  type(quantum_numbers_t), dimension(size(mask)) :: qn
  call state_matrix_init (red_state)
  call state_iterator_init (it, state)
  do while (state_iterator_is_valid (it))
    qn = state_iterator_get_quantum_numbers (it)
    call quantum_numbers_undefine (qn, mask)
    call state_matrix_add_state (red_state, qn)
    call state_iterator_advance (it)
  end do
end subroutine state_matrix_reduce

```

This subroutine sets up the matrix-element array. The leaf nodes acquire the index values that point to the appropriate matrix-element entry.

We recursively scan the trie. Once we arrive at a leaf node, the index is increased and associated to that node. Finally, we allocate the matrix-element array with the appropriate size.

If matrix element values are temporarily stored within the leaf nodes, we scan the state again and transfer them to the matrix-element array.

```

<State matrices: public>+≡
public :: state_matrix_freeze

<State matrices: interfaces>≡
interface state_matrix_freeze
  module procedure state_matrix_freeze1
  module procedure state_matrix_freeze2
end interface

<State matrices: procedures>+≡
subroutine state_matrix_freeze1 (state)
  type(state_matrix_t), intent(inout), target :: state
  type(state_iterator_t) :: it
  if (associated (state%root)) then
    if (allocated (state%me)) deallocate (state%me)
    allocate (state%me (state%n_matrix_elements))
    state%me = 0
  end if
  if (state%leaf_nodes_store_values) then
    call state_iterator_init (it, state)
    do while (state_iterator_is_valid (it))
      state%me(state_iterator_get_me_index (it)) &
        = state_iterator_get_matrix_element (it)
      call state_iterator_advance (it)
    end do
    state%leaf_nodes_store_values = .false.
  end if
end subroutine state_matrix_freeze1

```

```

subroutine state_matrix_freeze2 (state)
  type(state_matrix_t), dimension(:), intent(inout), target :: state
  integer :: i
  do i = 1, size (state)
    call state_matrix_freeze1 (state(i))
  end do
end subroutine state_matrix_freeze2

```

Direct access to the value array

Several methods for setting a value directly are summarized in this generic:

```

<State matrices: public>+≡
  public :: state_matrix_set_matrix_element

<State matrices: interfaces>+≡
  interface state_matrix_set_matrix_element
    module procedure state_matrix_set_matrix_element_qn
    module procedure state_matrix_set_matrix_element_all
    module procedure state_matrix_set_matrix_element_array
    module procedure state_matrix_set_matrix_element_single
  end interface

```

Set a value that corresponds to a quantum number array:

```

<State matrices: procedures>+≡
  subroutine state_matrix_set_matrix_element_qn (state, qn, value)
    type(state_matrix_t), intent(inout) :: state
    type(quantum_numbers_t), dimension(:), intent(in) :: qn
    complex(default), intent(in) :: value
    type(state_iterator_t) :: it
    if (.not. allocated (it%state%me)) then
      allocate (it%state%me (size(qn)))
    end if
    call state_iterator_init (it, state)
    do while (state_iterator_is_valid (it))
      if (all (qn == state_iterator_get_quantum_numbers (it))) then
        call state_iterator_set_matrix_element (it, value)
        return
      end if
      call state_iterator_advance (it)
    end do
  end subroutine state_matrix_set_matrix_element_qn

```

Set all matrix elements to a single value

```

<State matrices: procedures>+≡
  subroutine state_matrix_set_matrix_element_all (state, value)
    type(state_matrix_t), intent(inout) :: state
    complex(default), intent(in) :: value
    if (.not. allocated (state%me)) then
      allocate (state%me (state%n_matrix_elements))
    end if
    state%me = value
  end subroutine state_matrix_set_matrix_element_all

```

Set the matrix-element array directly.

```

<State matrices: procedures>+≡
  subroutine state_matrix_set_matrix_element_array (state, value)
    type(state_matrix_t), intent(inout) :: state
    complex(default), dimension(:), intent(in) :: value
    if (.not. allocated (state%me)) then
      allocate (state%me (size (value)))
    end if
    state%me = value
  end subroutine state_matrix_set_matrix_element_array

  pure subroutine state_matrix_set_matrix_element_single (state, i, value)
    type(state_matrix_t), intent(inout) :: state
    integer, intent(in) :: i
    complex(default), intent(in) :: value
    if (.not. allocated (state%me)) then
      allocate (state%me (state%n_matrix_elements))
    end if
    state%me(i) = value
  end subroutine state_matrix_set_matrix_element_single

```

Add a value to a matrix element

```

<State matrices: public>+≡
  public :: state_matrix_add_to_matrix_element

<State matrices: procedures>+≡
  subroutine state_matrix_add_to_matrix_element (state, i, value)
    type(state_matrix_t), intent(inout) :: state
    integer, intent(in) :: i
    complex(default), intent(in) :: value
    state%me(i) = state%me(i) + value
  end subroutine state_matrix_add_to_matrix_element

```

7.5.3 State iterators

Accessing the quantum state from outside is best done using a specialized iterator, i.e., a pointer to a particular branch of the quantum state trie. Technically, the iterator contains a pointer to a leaf node, but via parent pointers it allows to access the whole branch where the leaf is attached. For quick access, we also keep the branch depth (which is assumed to be universal for a quantum state).

```

<State matrices: public>+≡
  public :: state_iterator_t

<State matrices: types>+≡
  type :: state_iterator_t
    private
    integer :: depth = 0
    type(state_matrix_t), pointer :: state => null ()
    type(node_t), pointer :: node => null ()
  end type state_iterator_t

```

The initializer: Point at the first branch. Note that this cannot be pure, thus not be elemental, because the iterator can be used to manipulate data in the state matrix.

```

<State matrices: public>+≡
    public :: state_iterator_init

<State matrices: procedures>+≡
    subroutine state_iterator_init (it, state)
        type(state_iterator_t), intent(out) :: it
        type(state_matrix_t), intent(in), target :: state
        it%state => state
        it%depth = state%depth
        if (state_matrix_is_defined (state)) then
            it%node => state%root
            do while (associated (it%node%child_first))
                it%node => it%node%child_first
            end do
        else
            it%node => null ()
        end if
    end subroutine state_iterator_init

```

Go forward. Recursively programmed: if the next node does not exist, go back to the parent node and look at its successor (if present), etc.

There is a possible pitfall in the implementation: If the dummy pointer argument to the `find_next` routine is used directly, we still get the correct result for the iterator, but calling the recursion on `node%parent` means that we manipulate a parent pointer in the original state in addition to the iterator. Making a local copy of the pointer avoids this. Using pointer intent would be helpful, but we do not yet rely on this F2003 feature.

```

<State matrices: public>+≡
    public :: state_iterator_advance

<State matrices: procedures>+≡
    subroutine state_iterator_advance (it)
        type(state_iterator_t), intent(inout) :: it
        call find_next (it%node)
    contains
        recursive subroutine find_next (node_in)
            type(node_t), intent(in), target :: node_in
            type(node_t), pointer :: node
            node => node_in
            if (associated (node%next)) then
                node => node%next
                do while (associated (node%child_first))
                    node => node%child_first
                end do
                it%node => node
            else if (associated (node%parent)) then
                call find_next (node%parent)
            else
                it%node => null ()
            end if
        end subroutine find_next
    end subroutine state_iterator_advance

```

```

        end subroutine find_next
    end subroutine state_iterator_advance

```

If all has been scanned, the iterator is at an undefined state. Check for this:

```

<State matrices: public>+≡
    public :: state_iterator_is_valid

<State matrices: procedures>+≡
    function state_iterator_is_valid (it) result (defined)
        logical :: defined
        type(state_iterator_t), intent(in) :: it
        defined = associated (it%node)
    end function state_iterator_is_valid

```

Return the matrix-element index that corresponds to the current node

```

<State matrices: public>+≡
    public :: state_iterator_get_me_index

<State matrices: procedures>+≡
    function state_iterator_get_me_index (it) result (n)
        integer :: n
        type(state_iterator_t), intent(in) :: it
        n = it%node%me_index
    end function state_iterator_get_me_index

```

Return the number of times this quantum-number state has been added (noting that it is physically inserted only the first time). Note that for each state, there is an array of counters.

```

<State matrices: public>+≡
    public :: state_iterator_get_me_count

<State matrices: procedures>+≡
    function state_iterator_get_me_count (it) result (n)
        integer, dimension(:), allocatable :: n
        type(state_iterator_t), intent(in) :: it
        if (allocated (it%node%me_count)) then
            allocate (n (size (it%node%me_count)))
            n = it%node%me_count
        else
            allocate (n (0))
        end if
    end function state_iterator_get_me_count

```

Use the iterator to retrieve quantum-number information:

```

<State matrices: public>+≡
    public :: state_iterator_get_quantum_numbers
    public :: state_iterator_get_flavor
    public :: state_iterator_get_color
    public :: state_iterator_get_helicity

```

```

<State matrices: interfaces>+=
interface state_iterator_get_quantum_numbers
  module procedure state_iterator_get_qn_multi
  module procedure state_iterator_get_qn_slice
  module procedure state_iterator_get_qn_range
  module procedure state_iterator_get_qn_single
end interface

interface state_iterator_get_flavor
  module procedure state_iterator_get_flv_multi
  module procedure state_iterator_get_flv_slice
  module procedure state_iterator_get_flv_range
  module procedure state_iterator_get_flv_single
end interface

interface state_iterator_get_color
  module procedure state_iterator_get_col_multi
  module procedure state_iterator_get_col_slice
  module procedure state_iterator_get_col_range
  module procedure state_iterator_get_col_single
end interface

interface state_iterator_get_helicity
  module procedure state_iterator_get_hel_multi
  module procedure state_iterator_get_hel_slice
  module procedure state_iterator_get_hel_range
  module procedure state_iterator_get_hel_single
end interface

```

These versions return the whole quantum number array

```

<State matrices: procedures>+=
function state_iterator_get_qn_multi (it) result (qn)
  type(state_iterator_t), intent(in) :: it
  type(quantum_numbers_t), dimension(it%depth) :: qn
  type(node_t), pointer :: node
  integer :: i
  node => it%node
  do i = it%depth, 1, -1
    qn(i) = node%qn
    node => node%parent
  end do
end function state_iterator_get_qn_multi

function state_iterator_get_flv_multi (it) result (flv)
  type(state_iterator_t), intent(in) :: it
  type(flavor_t), dimension(it%depth) :: flv
  flv = quantum_numbers_get_flavor &
    (state_iterator_get_quantum_numbers (it))
end function state_iterator_get_flv_multi

function state_iterator_get_col_multi (it) result (col)
  type(state_iterator_t), intent(in) :: it
  type(color_t), dimension(it%depth) :: col

```



```

        col = quantum_numbers_get_color &
            (state_iterator_get_quantum_numbers (it))
end function state_iterator_get_col_multi

function state_iterator_get_hel_multi (it) result (hel)
    type(state_iterator_t), intent(in) :: it
    type(helicity_t), dimension(it%depth) :: hel
    hel = quantum_numbers_get_helicity &
        (state_iterator_get_quantum_numbers (it))
end function state_iterator_get_hel_multi

```

An array slice (derived from the above).

(State matrices: procedures)+≡

```

function state_iterator_get_qn_slice (it, index) result (qn)
    type(state_iterator_t), intent(in) :: it
    integer, dimension(:), intent(in) :: index
    type(quantum_numbers_t), dimension(size(index)) :: qn
    type(quantum_numbers_t), dimension(it%depth) :: qn_tmp
    qn_tmp = state_iterator_get_qn_multi (it)
    qn = qn_tmp(index)
end function state_iterator_get_qn_slice

function state_iterator_get_flv_slice (it, index) result (flv)
    type(state_iterator_t), intent(in) :: it
    integer, dimension(:), intent(in) :: index
    type(flavor_t), dimension(size(index)) :: flv
    flv = quantum_numbers_get_flavor &
        (state_iterator_get_quantum_numbers (it, index))
end function state_iterator_get_flv_slice

function state_iterator_get_col_slice (it, index) result (col)
    type(state_iterator_t), intent(in) :: it
    integer, dimension(:), intent(in) :: index
    type(color_t), dimension(size(index)) :: col
    col = quantum_numbers_get_color &
        (state_iterator_get_quantum_numbers (it, index))
end function state_iterator_get_col_slice

function state_iterator_get_hel_slice (it, index) result (hel)
    type(state_iterator_t), intent(in) :: it
    integer, dimension(:), intent(in) :: index
    type(helicity_t), dimension(size(index)) :: hel
    hel = quantum_numbers_get_helicity &
        (state_iterator_get_quantum_numbers (it, index))
end function state_iterator_get_hel_slice

```

An array range (implemented directly).

(State matrices: procedures)+≡

```

function state_iterator_get_qn_range (it, k1, k2) result (qn)
    type(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k1, k2
    type(quantum_numbers_t), dimension(k2-k1+1) :: qn
    type(node_t), pointer :: node

```

```

integer :: i
node => it%node
SCAN: do i = it%depth, 1, -1
    if (k1 <= i .and. i <= k2) then
        qn(i-k1+1) = node%qn
    else
        node => node%parent
    end if
end do SCAN
end function state_iterator_get_qn_range

function state_iterator_get_flv_range (it, k1, k2) result (flv)
    type(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k1, k2
    type(flavor_t), dimension(k2-k1+1) :: flv
    flv = quantum_numbers_get_flavor &
        (state_iterator_get_quantum_numbers (it, k1, k2))
end function state_iterator_get_flv_range

function state_iterator_get_col_range (it, k1, k2) result (col)
    type(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k1, k2
    type(color_t), dimension(k2-k1+1) :: col
    col = quantum_numbers_get_color &
        (state_iterator_get_quantum_numbers (it, k1, k2))
end function state_iterator_get_col_range

function state_iterator_get_hel_range (it, k1, k2) result (hel)
    type(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k1, k2
    type(helicity_t), dimension(k2-k1+1) :: hel
    hel = quantum_numbers_get_helicity &
        (state_iterator_get_quantum_numbers (it, k1, k2))
end function state_iterator_get_hel_range

```

Just a specific single element

(State matrices: procedures)+≡

```

function state_iterator_get_qn_single (it, k) result (qn)
    type(state_iterator_t), intent(in) :: it
    integer, intent(in) :: k
    type(quantum_numbers_t) :: qn
    type(node_t), pointer :: node
    integer :: i
    node => it%node
    SCAN: do i = it%depth, 1, -1
        if (i == k) then
            qn = node%qn
            exit SCAN
        else
            node => node%parent
        end if
    end do SCAN
end function state_iterator_get_qn_single

```

```

function state_iterator_get_flv_single (it, k) result (flv)
  type(state_iterator_t), intent(in) :: it
  integer, intent(in) :: k
  type(flavor_t) :: flv
  flv = quantum_numbers_get_flavor &
    (state_iterator_get_quantum_numbers (it, k))
end function state_iterator_get_flv_single

function state_iterator_get_col_single (it, k) result (col)
  type(state_iterator_t), intent(in) :: it
  integer, intent(in) :: k
  type(color_t) :: col
  col = quantum_numbers_get_color &
    (state_iterator_get_quantum_numbers (it, k))
end function state_iterator_get_col_single

function state_iterator_get_hel_single (it, k) result (hel)
  type(state_iterator_t), intent(in) :: it
  integer, intent(in) :: k
  type(helicity_t) :: hel
  hel = quantum_numbers_get_helicity &
    (state_iterator_get_quantum_numbers (it, k))
end function state_iterator_get_hel_single

```

Retrieve the matrix element value associated with the current node.

```

<State matrices: public>+≡
  public :: state_iterator_get_matrix_element

<State matrices: procedures>+≡
  function state_iterator_get_matrix_element (it) result (me)
    complex(default) :: me
    type(state_iterator_t), intent(in) :: it
    if (it%state%leaf_nodes_store_values) then
      me = it%node%me
    else if (it%node%me_index /= 0) then
      me = it%state%me(it%node%me_index)
    else
      me = 0
    end if
  end function state_iterator_get_matrix_element

```

Set the matrix element value using the state iterator.

```

<State matrices: public>+≡
  public :: state_iterator_set_matrix_element

<State matrices: procedures>+≡
  subroutine state_iterator_set_matrix_element (it, value)
    type(state_iterator_t), intent(inout) :: it
    complex(default), intent(in) :: value
    if (it%node%me_index /= 0) then
      it%state%me(it%node%me_index) = value
    end if
  end subroutine state_iterator_set_matrix_element

```

7.5.4 Operations on quantum states

Return a deep copy of a state matrix.

```

<State matrices: public>+≡
    public :: assignment(=)

<State matrices: interfaces>+≡
    interface assignment(=)
        module procedure state_matrix_assign
    end interface

<State matrices: procedures>+≡
    subroutine state_matrix_assign (state_out, state_in)
        type(state_matrix_t), intent(out) :: state_out
        type(state_matrix_t), intent(in), target :: state_in
        type(state_iterator_t) :: it
        if (.not. state_matrix_is_defined (state_in)) return
        call state_matrix_init (state_out)
        call state_iterator_init (it, state_in)
        do while (state_iterator_is_valid (it))
            call state_matrix_add_state (state_out, &
                state_iterator_get_quantum_numbers (it), &
                state_iterator_get_me_index (it))
            call state_iterator_advance (it)
        end do
        if (allocated (state_in%me)) then
            allocate (state_out%me (size (state_in%me)))
            state_out%me = state_in%me
        end if
    end subroutine state_matrix_assign

```

Normalize all matrix elements, i.e., multiply by a common factor. Assuming that the factor is nonzero, of course.

```

<State matrices: public>+≡
    public :: state_matrix_renormalize

<State matrices: procedures>+≡
    subroutine state_matrix_renormalize (state, factor)
        type(state_matrix_t), intent(inout) :: state
        complex(default), intent(in) :: factor
        state%me = state%me * factor
    end subroutine state_matrix_renormalize

```

Renormalize the state matrix by its trace, if nonzero. The renormalization is reflected in the state-matrix norm.

```

<State matrices: public>+≡
    public :: state_matrix_normalize_by_trace

<State matrices: procedures>+≡
    subroutine state_matrix_normalize_by_trace (state)
        type(state_matrix_t), intent(inout) :: state
        real(default) :: trace
        trace = state_matrix_trace (state)
        if (trace /= 0) then

```

```

        state%me = state%me / trace
        state%norm = state%norm * trace
    end if
end subroutine state_matrix_normalize_by_trace

```

Analogous, but renormalize by maximal (absolute) value.

```

<State matrices: public>+≡
    public :: state_matrix_normalize_by_max

<State matrices: procedures>+≡
    subroutine state_matrix_normalize_by_max (state)
        type(state_matrix_t), intent(inout) :: state
        real(default) :: m
        m = maxval (abs (state%me))
        if (m /= 0) then
            state%me = state%me / m
            state%norm = state%norm * m
        end if
    end subroutine state_matrix_normalize_by_max

```

Return the sum of all matrix element values.

```

<State matrices: public>+≡
    public :: state_matrix_sum

<State matrices: procedures>+≡
    function state_matrix_sum (state) result (value)
        complex(default) :: value
        type(state_matrix_t), intent(in) :: state
        value = sum (state%me)
    end function state_matrix_sum

```

Return the trace of a state matrix, i.e., the sum over all diagonal values. If `qn_in` is provided, only branches that match this quantum-numbers array are considered.

```

<State matrices: public>+≡
    public :: state_matrix_trace

<State matrices: procedures>+≡
    function state_matrix_trace (state, qn_in) result (trace)
        complex(default) :: trace
        type(state_matrix_t), intent(in), target :: state
        type(quantum_numbers_t), dimension(:), intent(in), optional :: qn_in
        type(quantum_numbers_t), dimension(:), allocatable :: qn
        type(state_iterator_t) :: it
        allocate (qn (state_matrix_get_depth (state)))
        trace = 0
        call state_iterator_init (it, state)
        do while (state_iterator_is_valid (it))
            qn = state_iterator_get_quantum_numbers (it)
            if (present (qn_in)) then
                if (.not. all (qn .match. qn_in)) then
                    call state_iterator_advance (it); cycle
                end if
            end if
        end do
    end function state_matrix_trace

```

```

        end if
        if (all (quantum_numbers_are_diagonal (qn))) then
            trace = trace + state_iterator_get_matrix_element (it)
        end if
        call state_iterator_advance (it)
    end do
end function state_matrix_trace

```

Append new states which are color-contracted versions of the existing states. The matrix element index of each color contraction coincides with the index of its origin, so no new matrix elements are generated. After this operation, no `freeze` must be performed anymore.

```

<State matrices: public>+≡
    public :: state_matrix_add_color_contractions

<State matrices: procedures>+≡
    subroutine state_matrix_add_color_contractions (state)
        type(state_matrix_t), intent(inout), target :: state
        type(state_iterator_t) :: it
        type(quantum_numbers_t), dimension(:,:), allocatable :: qn
        type(quantum_numbers_t), dimension(:,:), allocatable :: qn_con
        integer, dimension(:), allocatable :: me_index
        integer :: depth, n_me, i, j
        depth = state_matrix_get_depth (state)
        n_me = state_matrix_get_n_matrix_elements (state)
        allocate (qn (depth, n_me))
        allocate (me_index (n_me))
        i = 0
        call state_iterator_init (it, state)
        do while (state_iterator_is_valid (it))
            i = i + 1
            qn(:,i) = state_iterator_get_quantum_numbers (it)
            me_index(i) = state_iterator_get_me_index (it)
            call state_iterator_advance (it)
        end do
        do i = 1, n_me
            call quantum_number_array_make_color_contractions (qn(:,i), qn_con)
            do j = 1, size (qn_con, 2)
                call state_matrix_add_state (state, qn_con(:,j), index = me_index(i))
            end do
        end do
    end subroutine state_matrix_add_color_contractions

```

This procedure merges two state matrices of equal depth. For each quantum number (flavor, color, helicity), we take the entry from the first argument where defined, otherwise the second one. (If both are defined, we get an off-diagonal matrix.) The resulting trie combines the information of the input tries in all possible ways. Note that values are ignored, all values in the result are zero.

```

<State matrices: public>+≡
    public :: merge_state_matrices

<State matrices: procedures>+≡
    subroutine merge_state_matrices (state1, state2, state3)

```

```

type(state_matrix_t), intent(in), target :: state1, state2
type(state_matrix_t), intent(out) :: state3
type(state_iterator_t) :: it1, it2
type(quantum_numbers_t), dimension(state1%depth) :: qn1, qn2
if (state1%depth /= state2%depth) then
  call state_matrix_write (state1)
  call state_matrix_write (state2)
  call msg_bug ("State matrices merge impossible: incompatible depths")
end if
call state_matrix_init (state3)
call state_iterator_init (it1, state1)
do while (state_iterator_is_valid (it1))
  qn1 = state_iterator_get_quantum_numbers (it1)
  call state_iterator_init (it2, state2)
  do while (state_iterator_is_valid (it2))
    qn2 = state_iterator_get_quantum_numbers (it2)
    call state_matrix_add_state &
      (state3, qn1 .merge. qn2)
    call state_iterator_advance (it2)
  end do
  call state_iterator_advance (it1)
end do
call state_matrix_freeze (state3)
end subroutine merge_state_matrices

```

Multiply matrix elements from two state matrices. Choose the elements as given by the integer index arrays, multiply them and store the sum of products in the indicated matrix element. The suffixes mean: c=conjugate first factor; f=include weighting factor.

Note that the `dot_product` intrinsic function conjugates its first complex argument. This is intended for the c suffix case, but must be reverted for the plain-product case.

(State matrices: public)+≡

```

public :: state_matrix_evaluate_product
public :: state_matrix_evaluate_product_cf
public :: state_matrix_evaluate_square_c
public :: state_matrix_evaluate_sum

```

(State matrices: procedures)+≡

```

pure subroutine state_matrix_evaluate_product &
  (state, i, state1, state2, index1, index2)
type(state_matrix_t), intent(inout) :: state
integer, intent(in) :: i
type(state_matrix_t), intent(in) :: state1, state2
integer, dimension(:), intent(in) :: index1, index2
state%me(i) = &
  dot_product (conjg (state1%me(index1)), state2%me(index2))
state%norm = state1%norm * state2%norm
end subroutine state_matrix_evaluate_product

```

```

pure subroutine state_matrix_evaluate_product_cf &
  (state, i, state1, state2, index1, index2, factor)
type(state_matrix_t), intent(inout) :: state

```

```

integer, intent(in) :: i
type(state_matrix_t), intent(in) :: state1, state2
integer, dimension(:), intent(in) :: index1, index2
complex(default), dimension(:), intent(in) :: factor
state%me(i) = &
    dot_product (state1%me(index1), factor * state2%me(index2))
state%norm = state1%norm * state2%norm
end subroutine state_matrix_evaluate_product_cf

pure subroutine state_matrix_evaluate_square_c (state, i, state1, index1)
type(state_matrix_t), intent(inout) :: state
integer, intent(in) :: i
type(state_matrix_t), intent(in) :: state1
integer, dimension(:), intent(in) :: index1
state%me(i) = &
    dot_product (state1%me(index1), state1%me(index1))
state%norm = abs (state1%norm) ** 2
end subroutine state_matrix_evaluate_square_c

pure subroutine state_matrix_evaluate_sum (state, i, state1, index1)
type(state_matrix_t), intent(inout) :: state
integer, intent(in) :: i
type(state_matrix_t), intent(in) :: state1
integer, dimension(:), intent(in) :: index1
state%me(i) = &
    sum (state1%me(index1)) * state1%norm
end subroutine state_matrix_evaluate_sum

```

Outer product (of states and matrix elements):

```

<State matrices: public>+≡
public :: outer_multiply

<State matrices: interfaces>+≡
interface outer_multiply
    module procedure outer_multiply_pair
    module procedure outer_multiply_array
end interface

```

This procedure constructs the outer product of two state matrices.

```

<State matrices: procedures>+≡
subroutine outer_multiply_pair (state1, state2, state3)
type(state_matrix_t), intent(in), target :: state1, state2
type(state_matrix_t), intent(out) :: state3
type(state_iterator_t) :: it1, it2
type(quantum_numbers_t), dimension(state1%depth) :: qn1
type(quantum_numbers_t), dimension(state2%depth) :: qn2
type(quantum_numbers_t), dimension(state1%depth+state2%depth) :: qn3
complex(default) :: val1, val2
call state_matrix_init (state3, store_values=.true.)
call state_iterator_init (it1, state1)
do while (state_iterator_is_valid (it1))
    qn1 = state_iterator_get_quantum_numbers (it1)
    val1 = state_iterator_get_matrix_element (it1)

```



```

    call state_iterator_init (it2, state2)
    do while (state_iterator_is_valid (it2))
        qn2 = state_iterator_get_quantum_numbers (it2)
        val2 = state_iterator_get_matrix_element (it2)
        qn3(:state1%depth) = qn1
        qn3(state1%depth+1:) = qn2
        call state_matrix_add_state (state3, qn3, value=val1 * val2)
        call state_iterator_advance (it2)
    end do
    call state_iterator_advance (it1)
end do
call state_matrix_freeze (state3)
end subroutine outer_multiply_pair

```

This executes the above routine iteratively for an arbitrary number of state matrices.

(State matrices: procedures)+≡

```

subroutine outer_multiply_array (state_in, state_out)
    type(state_matrix_t), dimension(:), intent(in), target :: state_in
    type(state_matrix_t), intent(out) :: state_out
    type(state_matrix_t), dimension(:), allocatable, target :: state_tmp
    integer :: i, n
    n = size (state_in)
    select case (n)
    case (0)
        call state_matrix_init (state_out)
    case (1)
        state_out = state_in(1)
    case (2)
        call outer_multiply_pair (state_in(1), state_in(2), state_out)
    case default
        allocate (state_tmp (n-2))
        call outer_multiply_pair (state_in(1), state_in(2), state_tmp(1))
        do i = 2, n - 2
            call outer_multiply_pair (state_tmp(i-1), state_in(i+1), state_tmp(i))
        end do
        call outer_multiply_pair (state_tmp(n-2), state_in(n), state_out)
        call state_matrix_final (state_tmp)
    end select
end subroutine outer_multiply_array

```

7.5.5 Factorization

In physical events, the state matrix is factorized into single-particle state matrices. This is essentially a measurement.

In a simulation, we select one particular branch of the state matrix with a probability that is determined by the matrix elements at the leaves. (This makes sense only if the state matrix represents a squared amplitude.) The selection is based on a (random) value x between 0 and one that is provided as the third argument.

For flavor and color, we select a unique value for each particle. For polarization, we have three options (modes). Option 1 is to drop helicity information altogether and sum over all diagonal helicities. Option 2 is to select a unique diagonal helicity in the same way as flavor and color. Option 3 is, for each particle, to trace over all remaining helicities in order to obtain an array of independent single-particle helicity matrices.

Only branches that match the given quantum-number array `qn_in`, if present, are considered. For this array, color is ignored.

If the optional `correlated_state` is provided, it is assigned the correlated density matrix for the selected flavor-color branch, so multi-particle spin correlations remain available even if they are dropped in the single-particle density matrices.

The algorithm is as follows: First, we determine the normalization by summing over all diagonal matrix elements. In a second scan, we select one of the diagonal matrix elements by a cumulative comparison with the normalized random number. In the corresponding quantum number array, we undefine the helicity entries. Then, we scan the third time. For each branch that matches the selected quantum number array (i.e., definite flavor and color, arbitrary helicity), we determine its contribution to any of the single-particle state matrices. The matrix-element value is added if all other quantum numbers are diagonal, while the helicity of the chosen particle may be arbitrary; this helicity determines the branch in the single-particle state.

As a result, flavor and color quantum numbers are selected with the correct probability. Within this subset of states, each single-particle state matrix results from tracing over all other particles. Note that the single-particle state matrices are not normalized.

The flag `ok` is set to false if the matrix element sum is zero, so factorization is not possible. This can happen if an event did not pass cuts.

```

<State matrices: parameters>≡
    integer, parameter, public :: FM_IGNORE_HELICITY = 1
    integer, parameter, public :: FM_SELECT_HELICITY = 2
    integer, parameter, public :: FM_FACTOR_HELICITY = 3

<State matrices: public>+≡
    public :: state_matrix_factorize

<State matrices: procedures>+≡
    subroutine state_matrix_factorize &
        (state, mode, x, ok, single_state, correlated_state, qn_in)
        type(state_matrix_t), intent(in), target :: state
        integer, intent(in) :: mode
        real(default), intent(in) :: x
        logical, intent(out) :: ok
        type(state_matrix_t), &
            dimension(:), allocatable, intent(out) :: single_state
        type(state_matrix_t), intent(out), optional :: correlated_state
        type(quantum_numbers_t), dimension(:), intent(in), optional :: qn_in
        type(state_iterator_t) :: it
        real(default) :: s, xt
        complex(default) :: value
        integer :: i, depth
        type(quantum_numbers_t), dimension(:), allocatable :: qn, qn1

```

```

type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
logical, dimension(:), allocatable :: diagonal
logical, dimension(:,:), allocatable :: mask
ok = .true.
if (x /= 0) then
    xt = x * state_matrix_trace (state, qn_in)
else
    xt = 0
end if
s = 0
depth = state_matrix_get_depth (state)
allocate (qn (depth), qn1 (depth), diagonal (depth))
call state_iterator_init (it, state)
do while (state_iterator_is_valid (it))
    qn = state_iterator_get_quantum_numbers (it)
    if (present (qn_in)) then
        if (.not. all (qn .fmatch. qn_in)) then
            call state_iterator_advance (it); cycle
        end if
    end if
    if (all (quantum_numbers_are_diagonal (qn))) then
        value = state_iterator_get_matrix_element (it)
        if (real (value, default) < 0) then
            call state_matrix_write (state)
            print *, value
            call msg_bug ("Event generation: " &
                // "Negative real part of squared matrix element value")
            value = 0
        end if
        s = s + value
        if (s > xt) exit
    end if
    call state_iterator_advance (it)
end do
if (.not. state_iterator_is_valid (it)) then
    if (s == 0) ok = .false.
    call state_iterator_init (it, state)
end if
allocate (single_state (depth))
call state_matrix_init (single_state, store_values=.true.)
if (present (correlated_state)) &
    call state_matrix_init (correlated_state, store_values=.true.)
qn = state_iterator_get_quantum_numbers (it)
select case (mode)
case (FM_SELECT_HELICITY) ! single branch selected; shortcut
    do i = 1, depth
        call state_matrix_add_state (single_state(i), &
            (/qn(i)/), value=value)
    end do
    if (.not. present (correlated_state)) then
        call state_matrix_freeze (single_state)
        return
    end if
end select

```

```

allocate (qn_mask (depth))
call quantum_numbers_mask_init (qn_mask, .false., .false., .false., .true.)
call quantum_numbers_undefine (qn, qn_mask)
select case (mode)
case (FM_FACTOR_HELICITY)
  allocate (mask (depth, depth))
  mask = .false.
  forall (i = 1:depth) mask(i,i) = .true.
end select
call state_iterator_init (it, state)
do while (state_iterator_is_valid (it))
  qn1 = state_iterator_get_quantum_numbers (it)
  if (all (qn .match. qn1)) then
    diagonal = quantum_numbers_are_diagonal (qn1)
    value = state_iterator_get_matrix_element (it)
    select case (mode)
    case (FM_IGNORE_HELICITY) ! trace over diagonal states that match qn
      if (all (diagonal)) then
        do i = 1, depth
          call state_matrix_add_state (single_state(i), &
            (/qn(i)/), value=value, sum_values=.true.)
        end do
      end if
    case (FM_FACTOR_HELICITY) ! trace over all other particles
      do i = 1, depth
        if (all (diagonal .or. mask(:,i))) then
          call state_matrix_add_state (single_state(i), &
            (/qn1(i)/), value=value, sum_values=.true.)
        end if
      end do
    end select
    if (present (correlated_state)) &
      call state_matrix_add_state (correlated_state, qn1, value=value)
  end if
  call state_iterator_advance (it)
end do
call state_matrix_freeze (single_state)
if (present (correlated_state)) &
  call state_matrix_freeze (correlated_state)
end subroutine state_matrix_factorize

```

7.5.6 Test

```

<State matrices: public>+≡
public :: state_matrix_test

<State matrices: procedures>+≡
subroutine state_matrix_test ()
  print *, "State matrix test 1"
  call state_matrix_test1 ()
  print *
  print *, "State matrix test 2"
  call state_matrix_test2 ()

```

```

print *
print *, "State matrix test 3"
call state_matrix_test3 ()
end subroutine state_matrix_test

```

Create two quantum states of equal depth and merge them.

<State matrices: procedures>+≡

```

subroutine state_matrix_test1 ()
  type(state_matrix_t) :: state1, state2, state3
  type(flavor_t), dimension(3) :: flv
  type(color_t), dimension(3) :: col
  type(helicity_t), dimension(3) :: hel
  type(quantum_numbers_t), dimension(3) :: qn
  call state_matrix_init (state1)
  call flavor_init (flv, (/ 1, 2, 11 /))
  call helicity_init (hel, (/ 1, 1, 1 /))
  call quantum_numbers_init (qn, flv, hel)
  call state_matrix_add_state (state1, qn)
  call helicity_init (hel, (/ 1, 1, 1 /), (/ -1, 1, -1/))
  call quantum_numbers_init (qn, flv, hel)
  call state_matrix_add_state (state1, qn)
  call state_matrix_freeze (state1)
  call state_matrix_write (state1)
  print *
  call state_matrix_init (state2)
  call color_init (col(1), (/ 501 /))
  call color_init (col(2), (/ -501 /))
  call color_init (col(3), (/ 0 /))
  call helicity_init (hel, (/ -1, -1, 0 /))
  call quantum_numbers_init (qn, col, hel)
  call state_matrix_add_state (state2, qn)
  call color_init (col(3), (/ 99 /))
  call helicity_init (hel, (/ -1, -1, 0 /))
  call quantum_numbers_init (qn, col, hel)
  call state_matrix_add_state (state2, qn)
  call state_matrix_freeze (state2)
  call state_matrix_write (state2)
  print *
  call merge_state_matrices (state1, state2, state3)
  call state_matrix_write (state3)
  print *
  call state_matrix_collapse (state3, &
    new_quantum_numbers_mask (.false., .false., &
      (/ .true., .false., .false. /)))
  call state_matrix_write (state3)
  call state_matrix_final (state1)
  call state_matrix_final (state2)
  call state_matrix_final (state3)
end subroutine state_matrix_test1

```

Create a correlated three-particle state matrix and factorize it.

<State matrices: procedures>+≡

```

subroutine state_matrix_test2

```

```

type(state_matrix_t) :: state
type(state_matrix_t), dimension(:), allocatable :: single_state
type(state_matrix_t) :: correlated_state
complex(default) :: u, val
complex(default), dimension(-1:1) :: v
integer :: f, h11, h12, h21, h22, i, mode
type(flavor_t), dimension(2) :: flv
type(color_t), dimension(2) :: col
type(helicity_t), dimension(2) :: hel
type(quantum_numbers_t), dimension(2) :: qn
logical :: ok
u = 1 / 2._default
v(-1) = (0.6_default, 0._default)
v( 1) = (0._default, 0.8_default)
call state_matrix_init (state)
do f = 1, 2
  do h11 = -1, 1, 2
    do h12 = -1, 1, 2
      do h21 = -1, 1, 2
        do h22 = -1, 1, 2
          call flavor_init (flv, (/f, -f/))
          call color_init (col(1), (/ 1/))
          call color_init (col(2), (/ -1/))
          call helicity_init (hel, (/h11,h12/), (/h21, h22/))
          call quantum_numbers_init (qn, flv, col, hel)
          val = u * v(h11) * v(h12) * conjg (v(h21) * v(h22))
          call state_matrix_add_state (state, qn)
        end do
      end do
    end do
  end do
end do
call state_matrix_freeze (state)
call state_matrix_write (state)
print *, "trace = ", state_matrix_trace (state)
do mode = 1, 3
  print *
  print *, "Mode = ", mode
  call state_matrix_factorize &
    (state, mode, 0.15_default, ok, single_state, correlated_state)
  do i = 1, size (single_state)
    print *
    call state_matrix_write (single_state(i))
    print *, "trace = ", state_matrix_trace (single_state(i))
  end do
  print *
  call state_matrix_write (correlated_state)
  print *, "trace = ", state_matrix_trace (correlated_state)
  call state_matrix_final (single_state)
  call state_matrix_final (correlated_state)
end do
call state_matrix_final (state)
end subroutine state_matrix_test2

```

Create a colored state matrix and add color contractions.

(State matrices: procedures)+≡

```
subroutine state_matrix_test3
  type(state_matrix_t) :: state
  type(flavor_t), dimension(4) :: flv
  type(color_t), dimension(4) :: col
  type(quantum_numbers_t), dimension(4) :: qn
  call state_matrix_init (state)
  call flavor_init (flv, &
    (/ 1, -HADRON_REMNANT_TRIPLET, -1, HADRON_REMNANT_TRIPLET /))
  call color_init (col(1), (/17/))
  call color_init (col(2), (/ -17/))
  call color_init (col(3), (/ -19/))
  call color_init (col(4), (/19/))
  call quantum_numbers_init (qn, flv=flv, col=col)
  call state_matrix_add_state (state, qn)
  call flavor_init (flv, &
    (/ 1, -HADRON_REMNANT_TRIPLET, 21, HADRON_REMNANT_OCTET /))
  call color_init (col(1), (/17/))
  call color_init (col(2), (/ -17/))
  call color_init (col(3), (/3, -5/))
  call color_init (col(4), (/5, -3/))
  call quantum_numbers_init (qn, flv=flv, col=col)
  call state_matrix_add_state (state, qn)
  call state_matrix_freeze (state)
  print *, "State:"
  call state_matrix_write (state)
  call state_matrix_add_color_contractions (state)
  print *, "State with contractions:"
  call state_matrix_write (state)
  call state_matrix_final (state)
end subroutine state_matrix_test3
```

7.6 Interactions

This module defines the `interaction_t` type. It is an extension of the `state_matrix_t` type.

The state matrix is a representation of a multi-particle density matrix. It implements all possible flavor, color, and quantum-number assignments of the entries in a generic density matrix, and it can hold a complex matrix element for each entry. (Note that this matrix can hold non-diagonal entries in color and helicity space.) The `interaction_t` object associates this with a list of momenta, such that the whole object represents a multi-particle state.

The `interaction_t` holds information about which particles are incoming, virtual (i.e., kept for the records), or outgoing. Each particle can be associated to a source within another interaction. This allows us to automatically fill those interaction momenta which have been computed or defined elsewhere. It also contains internal parent-child relations and flags for (virtual) particles which are to be treated as resonances.

A quantum-number mask array summarizes, for each particle within the

interaction, the treatment of flavor, color, or helicity (expose or ignore). A list of locks states which particles are bound to have an identical quantum-number mask. This is useful when the mask is changed at one place.

```

<interactions.f90>≡
  <File header>

  module interactions

    <Use kinds>
    <Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use sorting
    use subevents
    use expressions
    use flavors
    use colors
    use helicities
    use quantum_numbers
    use state_matrices

    <Standard module head>

    <Interactions: public>

    <Interactions: types>

    <Interactions: interfaces>

    contains

    <Interactions: procedures>

  end module interactions

```

7.6.1 External interaction links

Each particle in an interaction can have a link to a corresponding particle in another interaction. This allows to fetch the momenta of incoming or virtual particles from the interaction where they are defined. The link object consists of a pointer to the interaction and an index.

```

<Interactions: types>≡
  type :: external_link_t
  private
  type(interaction_t), pointer :: int => null ()
  integer :: i
  end type external_link_t

```

Set an external link.

```

<Interactions: procedures>≡
  subroutine external_link_set (link, int, i)
    type(external_link_t), intent(out) :: link

```



```

    type(interaction_t), target, intent(in) :: int
    integer, intent(in) :: i
    if (i /= 0) then
        link%int => int
        link%i = i
    end if
end subroutine external_link_set

```

Reassign an external link to a new interaction (which should be an image of the original target).

```

<Interactions: procedures>+≡
    subroutine external_link_reassign (link, int_src, int_target)
        type(external_link_t), intent(inout) :: link
        type(interaction_t), intent(in) :: int_src
        type(interaction_t), intent(in), target :: int_target
        if (associated (link%int)) then
            if (link%int%tag == int_src%tag) link%int => int_target
        end if
    end subroutine external_link_reassign

```

Return true if the link is set

```

<Interactions: procedures>+≡
    function external_link_is_set (link) result (flag)
        logical :: flag
        type(external_link_t), intent(in) :: link
        flag = associated (link%int)
    end function external_link_is_set

```

Return the interaction pointer.

```

<Interactions: public>≡
    public :: external_link_get_ptr

<Interactions: procedures>+≡
    function external_link_get_ptr (link) result (int)
        type(interaction_t), pointer :: int
        type(external_link_t), intent(in) :: link
        int => link%int
    end function external_link_get_ptr

```

Return the index within that interaction

```

<Interactions: public>+≡
    public :: external_link_get_index

<Interactions: procedures>+≡
    function external_link_get_index (link) result (i)
        integer :: i
        type(external_link_t), intent(in) :: link
        i = link%i
    end function external_link_get_index

```

Return a pointer to the momentum of the corresponding particle. If there is no association, return a null pointer.

```

<Interactions: procedures>+≡
function external_link_get_momentum_ptr (link) result (p)
  type(vector4_t), pointer :: p
  type(external_link_t), intent(in) :: link
  if (associated (link%int)) then
    p => link%int%p(link%i)
  else
    p => null ()
  end if
end function external_link_get_momentum_ptr

```

7.6.2 Internal relations

In addition to the external links, particles within the interaction have parent-child relations. Here, more than one link is possible, and we set up a list.

```

<Interactions: types>+≡
type :: internal_link_t
  private
  integer :: i
  type(internal_link_t), pointer :: next => null ()
end type internal_link_t

type :: internal_link_list_t
  private
  integer :: length = 0
  type(internal_link_t), pointer :: first => null ()
  type(internal_link_t), pointer :: last => null ()
end type internal_link_list_t

```

Add an internal link.

```

<Interactions: procedures>+≡
subroutine internal_link_list_append (link_list, i)
  type(internal_link_list_t), intent(inout) :: link_list
  integer, intent(in) :: i
  type(internal_link_t), pointer :: current
  allocate (current)
  current%i = i
  if (associated (link_list%first)) then
    link_list%last%next => current
  else
    link_list%first => current
  end if
  link_list%last => current
  link_list%length = link_list%length + 1
end subroutine internal_link_list_append

```

Finalize the list of internal links.

```

<Interactions: procedures>+≡
subroutine internal_link_list_final (link_list)

```

```

type(internal_link_list_t), intent(inout) :: link_list
type(internal_link_t), pointer :: current
do while (associated (link_list%first))
    current => link_list%first
    link_list%first => current%next
    deallocate (current)
end do
link_list%last => null ()
link_list%length = 0
end subroutine internal_link_list_final

```

We need a deep copy of this list when we assign interaction objects.

<Interactions: interfaces>≡

```

interface assignment(=)
    module procedure internal_link_list_assign
end interface

```

<Interactions: procedures>+≡

```

subroutine internal_link_list_assign (link_list_out, link_list_in)
    type(internal_link_list_t), intent(in) :: link_list_in
    type(internal_link_list_t), intent(out) :: link_list_out
    type(internal_link_t), pointer :: current, copy
    current => link_list_in%first
    do while (associated (current))
        allocate (copy)
        copy%i = current%i
        if (associated (link_list_out%first)) then
            link_list_out%last%next => copy
        else
            link_list_out%first => copy
        end if
        link_list_out%last => copy
        current => current%next
    end do
end subroutine internal_link_list_assign

```

Return true if the link list is nonempty:

<Interactions: procedures>+≡

```

function internal_link_list_has_entries (link_list) result (flag)
    logical :: flag
    type(internal_link_list_t), intent(in) :: link_list
    flag = associated (link_list%first)
end function internal_link_list_has_entries

```

Return a pointer to the first entry:

<Interactions: procedures>+≡

```

function internal_link_list_get_first_ptr (link_list) result (link)
    type(internal_link_list_t), intent(in) :: link_list
    type(internal_link_t), pointer :: link
    link => link_list%first
end function internal_link_list_get_first_ptr

```

Advance this pointer.

```

<Interactions: procedures>+≡
  subroutine internal_link_advance (link)
    type(internal_link_t), pointer :: link
    link => link%next
  end subroutine internal_link_advance

```

Return the index.

```

<Interactions: procedures>+≡
  function internal_link_get_index (link) result (i)
    integer :: i
    type(internal_link_t), intent(in) :: link
    i = link%i
  end function internal_link_get_index

```

Return the list length

```

<Interactions: procedures>+≡
  function internal_link_list_get_length (link_list) result (length)
    integer :: length
    type(internal_link_list_t), intent(in) :: link_list
    length = link_list%length
  end function internal_link_list_get_length

```

7.6.3 The interaction type

An interaction is an entangled system of particles. Thus, the interaction object consists of two parts: the subevent, and the quantum state which technically is a trie. The subnode levels beyond the trie root node are in correspondence to the subevent, so both should be traversed in parallel.

The subevent is implemented as an allocatable array of four-momenta. The first **n_in** particles are incoming, **n_vir** particles in-between can be kept for bookkeeping, and the last **n_out** particles are outgoing.

Distinct interactions are linked by their particles: for each particle, we have the possibility of links to corresponding particles in other interactions. Furthermore, for bookkeeping purposes we have a self-link array **relations** where the parent-child relations are kept, and a flag array **resonant** which is set for an intermediate resonance.

Each momentum is associated with masks for flavor, color, and helicity. If a mask entry is set, the associated quantum number is to be ignored for that particle. If any mask has changed, the flag **update** is set.

We can have particle pairs locked together. If this is the case, the corresponding mask entries are bound to be equal. This is useful for particles that go through the interaction.

The interaction tag serves bookkeeping purposes. In particular, it identifies links in printout.

```

<Interactions: public>+≡
  public :: interaction_t

```

```

<Interactions: types>+=
  type :: interaction_t
    private
    integer :: tag = 0
    type(state_matrix_t) :: state_matrix
    integer :: n_in = 0
    integer :: n_vir = 0
    integer :: n_out = 0
    integer :: n_tot = 0
    logical, dimension(:), allocatable :: p_is_known
    type(vector4_t), dimension(:), allocatable :: p
    type(external_link_t), dimension(:), allocatable :: source
    type(internal_link_list_t), dimension(:), allocatable :: parents
    type(internal_link_list_t), dimension(:), allocatable :: children
    logical, dimension(:), allocatable :: resonant
    type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
    integer, dimension(:), allocatable :: hel_lock
    logical :: update_state_matrix = .false.
    logical :: update_values = .false.
end type interaction_t

```

Initialize the particle array with a fixed size. The first `n_in` particles are incoming, the rest outgoing. Masks are optional. There is also an optional tag. The interaction still needs fixing the values, but that is to be done after all branches have been added.

Interaction tags are assigned consecutively, using a `saved` variable local to this procedure. If desired, we can provide a seed for the interaction tags. Such a seed should be positive. The default seed is one. `tag=0` indicates an empty interaction.

If `set_relations` is set and true, we establish parent-child relations for all incoming and outgoing particles. Virtual particles are skipped; this option is normally used only for interactions without virtual particles.

```

<Interactions: public>+=
  public :: interaction_init

<Interactions: procedures>+=
  subroutine interaction_init &
    (int, n_in, n_vir, n_out, &
     tag, resonant, mask, hel_lock, set_relations, store_values)
    type(interaction_t), intent(out) :: int
    integer, intent(in) :: n_in, n_vir, n_out
    integer, intent(in), optional :: tag
    logical, dimension(:), intent(in), optional :: resonant
    type(quantum_numbers_mask_t), dimension(:), intent(in), optional :: mask
    integer, dimension(:), intent(in), optional :: hel_lock
    logical, intent(in), optional :: set_relations, store_values
    logical :: set_rel
    integer :: i, j
    set_rel = .false.; if (present (set_relations)) set_rel = set_relations
    call interaction_set_tag (int, tag)
    call state_matrix_init (int%state_matrix, store_values)
    int%n_in = n_in
    int%n_vir = n_vir

```

```

int%n_out = n_out
int%n_tot = n_in + n_vir + n_out
allocate (int%p_is_known (int%n_tot))
int%p_is_known = .false.
allocate (int%p (int%n_tot))
allocate (int%source (int%n_tot))
allocate (int%parents (int%n_tot))
allocate (int%children (int%n_tot))
allocate (int%resonant (int%n_tot))
if (present (resonant)) then
    int%resonant = resonant
else
    int%resonant = .false.
end if
allocate (int%mask (int%n_tot))
allocate (int%hel_lock (int%n_tot))
if (present (mask)) then
    int%mask = mask
end if
if (present (hel_lock)) then
    int%hel_lock = hel_lock
else
    int%hel_lock = 0
end if
int%update_state_matrix = .false.
int%update_values = .true.
if (set_rel) then
    do i = 1, n_in
        do j = 1, n_out
            call interaction_relate (int, i, n_in + j)
        end do
    end do
end if
end subroutine interaction_init

```

Set or create a unique tag for the interaction.

```

<Interactions: procedures>+≡
subroutine interaction_set_tag (int, tag)
    type(interaction_t), intent(inout) :: int
    integer, intent(in), optional :: tag
    integer, save :: stored_tag = 1
    if (present (tag)) then
        int%tag = tag
    else
        int%tag = stored_tag
        stored_tag = stored_tag + 1
    end if
end subroutine interaction_set_tag

```

Finalizer: The state-matrix object contains pointers.

```

<Interactions: public>+≡
public :: interaction_final

```

```

<Interactions: procedures>+=
  elemental subroutine interaction_final (int)
    type(interaction_t), intent(inout) :: int
    call state_matrix_final (int%state_matrix)
  end subroutine interaction_final

```

Output. The **verbose** option refers to the state matrix output.

```

<Interactions: public>+=
  public :: interaction_write

<Interactions: procedures>+=
  subroutine interaction_write &
    (int, unit, verbose, show_momentum_sum, show_mass, show_state)
    type(interaction_t), intent(in) :: int
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
    logical, intent(in), optional :: show_state
    integer :: u
    integer :: i, index_link
    type(internal_link_t), pointer :: link
    type(interaction_t), pointer :: int_link
    logical :: show_st
    u = output_unit (unit); if (u < 0) return
    show_st = .true.; if (present (show_state)) show_st = show_state
    if (int%tag /= 0) then
      write (u, *) "Interaction:", int%tag
      do i = 1, int%n_tot
        if (i == 1 .and. int%n_in > 0) then
          write (u, *) "Incoming:"
        else if (i == int%n_in + 1 .and. int%n_vir > 0) then
          write (u, *) "Virtual:"
        else if (i == int%n_in + int%n_vir + 1 .and. int%n_out > 0) then
          write (u, *) "Outgoing:"
        end if
        write (u, "(1x,A,1x,I0)", advance="no") "Particle", i
        if (allocated (int%resonant)) then
          if (int%resonant(i)) then
            write (u, *) "[r]"
          else
            write (u, *)
          end if
        else
          write (u, *)
        end if
        if (allocated (int%p)) then
          if (int%p_is_known(i)) then
            call vector4_write (int%p(i), u, show_mass)
          else
            write (u, *) " [momentum undefined]"
          end if
        else
          write (u, *) " [momentum not allocated]"
        end if
        if (allocated (int%mask)) then

```

```

        write (u, "(1x,A)", advance="no") "mask [fch] = "
        call quantum_numbers_mask_write (int%mask(i), u)
        write (u, *)
    end if
    if (internal_link_list_has_entries (int%parents(i)) &
        .or. internal_link_list_has_entries (int%children(i))) then
        write (u, "(1x,A)", advance="no") "internal links:"
        link => internal_link_list_get_first_ptr (int%parents(i))
        do while (associated (link))
            write (u, "(1x,I0)", advance="no") &
                internal_link_get_index (link)
            call internal_link_advance (link)
        end do
        if (internal_link_list_has_entries (int%parents(i))) &
            write (u, "(1x,A)", advance="no") "=>"
        write (u, "(1x,A)", advance="no") "X"
        if (internal_link_list_has_entries (int%children(i))) &
            write (u, "(1x,A)", advance="no") "=>"
        link => internal_link_list_get_first_ptr (int%children(i))
        do while (associated (link))
            write (u, "(1x,I0)", advance="no") &
                internal_link_get_index (link)
            call internal_link_advance (link)
        end do
        write (u, *)
    end if
    if (allocated (int%hel_lock)) then
        if (int%hel_lock(i) /= 0) then
            write (u, "(1x,A,1x,I0)") "helicity lock:", int%hel_lock(i)
        end if
    end if
    if (external_link_is_set (int%source(i))) then
        write (u, "(1x,A)", advance="no") "source:"
        int_link => external_link_get_ptr (int%source(i))
        index_link = external_link_get_index (int%source(i))
        write (u, "(1x,'(,I0,')',I0)", advance="no") &
            int_link%tag, index_link
        write (u, *)
    end if
end do
if (present (show_momentum_sum)) then
    if (allocated (int%p) .and. show_momentum_sum) then
        write (u, *) "Incoming particles (sum):"
        call vector4_write &
            (sum (int%p(1:int%n_in)), u, show_mass)
        write (u, *) "Outgoing particles (sum):"
        call vector4_write &
            (sum (int%p(int%n_in+int%n_vir+1:)), u, show_mass)
        write (u, *)
    end if
end if
if (show_st) then
    call state_matrix_write (int%state_matrix, &
        write_value_list=verbose, verbose=verbose, unit=unit)

```



```

        end if
    else
        write (u, *) "Interaction: [empty]"
    end if
end subroutine interaction_write

```

Assignment: We implement this as a deep copy. This applies, in particular, to the state-matrix and internal-link components. Furthermore, the new interaction acquires a new tag.

```

<Interactions: public>+=
    public :: assignment(=)

<Interactions: interfaces>+=
    interface assignment(=)
        module procedure interaction_assign
    end interface

<Interactions: procedures>+=
    subroutine interaction_assign (int_out, int_in)
        type(interaction_t), intent(out) :: int_out
        type(interaction_t), intent(in), target :: int_in
        call interaction_set_tag (int_out)
        int_out%state_matrix = int_in%state_matrix
        int_out%n_in = int_in%n_in
        int_out%n_out = int_in%n_out
        int_out%n_vir = int_in%n_vir
        int_out%n_tot = int_in%n_tot
        if (allocated (int_in%p_is_known)) then
            allocate (int_out%p_is_known (size (int_in%p_is_known)))
            int_out%p_is_known = int_in%p_is_known
        end if
        if (allocated (int_in%p)) then
            allocate (int_out%p (size (int_in%p)))
            int_out%p = int_in%p
        end if
        if (allocated (int_in%source)) then
            allocate (int_out%source (size (int_in%source)))
            int_out%source = int_in%source
        end if
        if (allocated (int_in%parents)) then
            allocate (int_out%parents (size (int_in%parents)))
            int_out%parents = int_in%parents
        end if
        if (allocated (int_in%children)) then
            allocate (int_out%children (size (int_in%children)))
            int_out%children = int_in%children
        end if
        if (allocated (int_in%resonant)) then
            allocate (int_out%resonant (size (int_in%resonant)))
            int_out%resonant = int_in%resonant
        end if
        if (allocated (int_in%mask)) then
            allocate (int_out%mask (size (int_in%mask)))

```

```

        int_out%mask = int_in%mask
    end if
    if (allocated (int_in%hel_lock)) then
        allocate (int_out%hel_lock (size (int_in%hel_lock)))
        int_out%hel_lock = int_in%hel_lock
    end if
    int_out%update_state_matrix = int_in%update_state_matrix
    int_out%update_values = int_in%update_values
end subroutine interaction_assign

```

7.6.4 Methods inherited from the state matrix member

Until F2003 is standard, we cannot implement inheritance directly. Therefore, we need wrappers for “inherited” methods.

Make a new branch in the state matrix if it does not yet exist. This is not just a wrapper but it introduces the interaction mask: where a quantum number is masked, it is not transferred but set undefined. After this, the value array has to be updated.

```

<Interactions: public>+≡
    public :: interaction_add_state

<Interactions: procedures>+≡
    subroutine interaction_add_state &
        (int, qn, index, value, sum_values, counter_index, me_index)
        type(interaction_t), intent(inout) :: int
        type(quantum_numbers_t), dimension(:), intent(in) :: qn
        integer, intent(in), optional :: index
        complex(default), intent(in), optional :: value
        logical, intent(in), optional :: sum_values
        integer, intent(in), optional :: counter_index
        integer, intent(out), optional :: me_index
        type(quantum_numbers_t), dimension(size(qn)) :: qn_tmp
        qn_tmp = qn
        call quantum_numbers_undefine (qn_tmp, int%mask)
        call state_matrix_add_state &
            (int%state_matrix, qn_tmp, index, value, sum_values, &
             counter_index, me_index)
        int%update_values = .true.
    end subroutine interaction_add_state

```

Freeze the quantum state: First collapse the quantum state, i.e., remove quantum numbers if any mask has changed, then fix the array of value pointers.

```

<Interactions: public>+≡
    public :: interaction_freeze

<Interactions: procedures>+≡
    subroutine interaction_freeze (int)
        type(interaction_t), intent(inout) :: int
        if (int%update_state_matrix) then
            call state_matrix_collapse (int%state_matrix, int%mask)
            int%update_state_matrix = .false.
            int%update_values = .true.
        end if
    end subroutine interaction_freeze

```

```

end if
if (int%update_values) then
  call state_matrix_freeze (int%state_matrix)
  int%update_values = .false.
end if
end subroutine interaction_freeze

```

Return true if the state matrix is empty.

```

<Interactions: public>+≡
  public :: interaction_is_empty

<Interactions: procedures>+≡
  function interaction_is_empty (int) result (flag)
    logical :: flag
    type(interaction_t), intent(in) :: int
    flag = state_matrix_is_empty (int%state_matrix)
  end function interaction_is_empty

```

Get the number of values stored in the state matrix:

```

<Interactions: public>+≡
  public :: interaction_get_n_matrix_elements

<Interactions: procedures>+≡
  function interaction_get_n_matrix_elements (int) result (n)
    integer :: n
    type(interaction_t), intent(in) :: int
    n = state_matrix_get_n_matrix_elements (int%state_matrix)
  end function interaction_get_n_matrix_elements

```

Get the norm of the state matrix (if the norm has been taken out, otherwise this would be unity).

```

<Interactions: public>+≡
  public :: interaction_get_norm

<Interactions: procedures>+≡
  function interaction_get_norm (int) result (norm)
    real(default) :: norm
    type(interaction_t), intent(in) :: int
    norm = state_matrix_get_norm (int%state_matrix)
  end function interaction_get_norm

```

Get the quantum number array that corresponds to a given index.

```

<Interactions: public>+≡
  public :: interaction_get_quantum_numbers

<Interactions: procedures>+≡
  function interaction_get_quantum_numbers (int, i) result (qn)
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    type(interaction_t), intent(in), target :: int
    integer, intent(in) :: i
    allocate (qn (state_matrix_get_depth (int%state_matrix)))
    qn = state_matrix_get_quantum_numbers (int%state_matrix, i)
  end function interaction_get_quantum_numbers

```

Get the matrix element that corresponds to a set of quantum numbers, a given index, or return the whole array.

```

<Interactions: public>+≡
    public :: interaction_get_matrix_element

<Interactions: procedures>+≡
    function interaction_get_matrix_element (int, i) result (me)
        complex(default) :: me
        type(interaction_t), intent(in) :: int
        integer, intent(in) :: i
        me = state_matrix_get_matrix_element (int%state_matrix, i)
    end function interaction_get_matrix_element

```

Set the complex value(s) stored in the quantum state.

```

<Interactions: public>+≡
    public :: interaction_set_matrix_element

<Interactions: interfaces>+≡
    interface interaction_set_matrix_element
        module procedure interaction_set_matrix_element_qn
        module procedure interaction_set_matrix_element_all
        module procedure interaction_set_matrix_element_array
        module procedure interaction_set_matrix_element_single
    end interface

```

Indirect access via the quantum number array:

```

<Interactions: procedures>+≡
    subroutine interaction_set_matrix_element_qn (int, qn, val)
        type(interaction_t), intent(inout) :: int
        type(quantum_numbers_t), dimension(:), intent(in) :: qn
        complex(default), intent(in) :: val
        call state_matrix_set_matrix_element (int%state_matrix, qn, val)
    end subroutine interaction_set_matrix_element_qn

```

Set all entries of the matrix-element array to a given value.

```

<Interactions: procedures>+≡
    subroutine interaction_set_matrix_element_all (int, value)
        type(interaction_t), intent(inout) :: int
        complex(default), intent(in) :: value
        call state_matrix_set_matrix_element (int%state_matrix, value)
    end subroutine interaction_set_matrix_element_all

```

Set the matrix-element array directly.

```

<Interactions: procedures>+≡
    subroutine interaction_set_matrix_element_array (int, value)
        type(interaction_t), intent(inout) :: int
        complex(default), dimension(:), intent(in) :: value
        call state_matrix_set_matrix_element (int%state_matrix, value)
    end subroutine interaction_set_matrix_element_array

    pure subroutine interaction_set_matrix_element_single (int, i, value)
        type(interaction_t), intent(inout) :: int
        integer, intent(in) :: i

```

```

        complex(default), intent(in) :: value
        call state_matrix_set_matrix_element (int%state_matrix, i, value)
    end subroutine interaction_set_matrix_element_single

```

Renormalize the state matrix by its trace, if nonzero. The renormalization is reflected in the state-matrix norm.

```

<Interactions: public>+≡
    public :: interaction_normalize_by_trace

<Interactions: procedures>+≡
    subroutine interaction_normalize_by_trace (int)
        type(interaction_t), intent(inout) :: int
        call state_matrix_normalize_by_trace (int%state_matrix)
    end subroutine interaction_normalize_by_trace

```

Analogous, but renormalize by maximal (absolute) value.

```

<Interactions: public>+≡
    public :: interaction_normalize_by_max

<Interactions: procedures>+≡
    subroutine interaction_normalize_by_max (int)
        type(interaction_t), intent(inout) :: int
        call state_matrix_normalize_by_max (int%state_matrix)
    end subroutine interaction_normalize_by_max

```

Return the maximum absolute value of color indices.

```

<Interactions: public>+≡
    public :: interaction_get_max_color_value

<Interactions: procedures>+≡
    function interaction_get_max_color_value (int) result (cmax)
        integer :: cmax
        type(interaction_t), intent(in) :: int
        cmax = state_matrix_get_max_color_value (int%state_matrix)
    end function interaction_get_max_color_value

```

Factorize the state matrix into single-particle state matrices, the branch selection depending on a (random) value between 0 and 1; optionally also return a correlated state matrix.

```

<Interactions: public>+≡
    public :: interaction_factorize

<Interactions: procedures>+≡
    subroutine interaction_factorize &
        (int, mode, x, ok, single_state, correlated_state, qn_in)
        type(interaction_t), intent(in), target :: int
        integer, intent(in) :: mode
        real(default), intent(in) :: x
        logical, intent(out) :: ok
        type(state_matrix_t), &
            dimension(:), allocatable, intent(out) :: single_state
        type(state_matrix_t), intent(out), optional :: correlated_state
        type(quantum_numbers_t), dimension(:), intent(in), optional :: qn_in
    end subroutine interaction_factorize

```

```

    call state_matrix_factorize &
      (int%state_matrix, mode, x, ok, single_state, correlated_state, qn_in)
end subroutine interaction_factorize

```

Sum all matrix element values

```

<Interactions: public>+≡
  public :: interaction_sum

<Interactions: procedures>+≡
  function interaction_sum (int) result (value)
    complex(default) :: value
    type(interaction_t), intent(in) :: int
    value = state_matrix_sum (int%state_matrix)
  end function interaction_sum

```

Append new states which are color-contracted versions of the existing states. The matrix element index of each color contraction coincides with the index of its origin, so no new matrix elements are generated. After this operation, no `freeze` must be performed anymore.

```

<Interactions: public>+≡
  public :: interaction_add_color_contractions

<Interactions: procedures>+≡
  subroutine interaction_add_color_contractions (int)
    type(interaction_t), intent(inout) :: int
    call state_matrix_add_color_contractions (int%state_matrix)
  end subroutine interaction_add_color_contractions

```

Multiply matrix elements from two interactions. Choose the elements as given by the integer index arrays, multiply them and store the sum of products in the indicated matrix element. The suffixes mean: c=conjugate first factor; f=include weighting factor.

```

<Interactions: public>+≡
  public :: interaction_evaluate_product
  public :: interaction_evaluate_product_cf
  public :: interaction_evaluate_square_c
  public :: interaction_evaluate_sum

<Interactions: procedures>+≡
  pure subroutine interaction_evaluate_product &
    (int, i, int1, int2, index1, index2)
    type(interaction_t), intent(inout) :: int
    integer, intent(in) :: i
    type(interaction_t), intent(in) :: int1, int2
    integer, dimension(:), intent(in) :: index1, index2
    call state_matrix_evaluate_product &
      (int%state_matrix, i, int1%state_matrix, int2%state_matrix, &
        index1, index2)
  end subroutine interaction_evaluate_product

  pure subroutine interaction_evaluate_product_cf &
    (int, i, int1, int2, index1, index2, factor)
    type(interaction_t), intent(inout) :: int

```

```

integer, intent(in) :: i
type(interaction_t), intent(in) :: int1, int2
integer, dimension(:), intent(in) :: index1, index2
complex(default), dimension(:), intent(in) :: factor
call state_matrix_evaluate_product_cf &
    (int%state_matrix, i, int1%state_matrix, int2%state_matrix, &
    index1, index2, factor)
end subroutine interaction_evaluate_product_cf

pure subroutine interaction_evaluate_square_c (int, i, int1, index1)
type(interaction_t), intent(inout) :: int
integer, intent(in) :: i
type(interaction_t), intent(in) :: int1
integer, dimension(:), intent(in) :: index1
call state_matrix_evaluate_square_c &
    (int%state_matrix, i, int1%state_matrix, index1)
end subroutine interaction_evaluate_square_c

pure subroutine interaction_evaluate_sum (int, i, int1, index1)
type(interaction_t), intent(inout) :: int
integer, intent(in) :: i
type(interaction_t), intent(in) :: int1
integer, dimension(:), intent(in) :: index1
call state_matrix_evaluate_sum &
    (int%state_matrix, i, int1%state_matrix, index1)
end subroutine interaction_evaluate_sum

```

7.6.5 Accessing contents

Return the integer tag.

```

<Interactions: public>+≡
public :: interaction_get_tag

<Interactions: procedures>+≡
function interaction_get_tag (int) result (tag)
integer :: tag
type(interaction_t), intent(in) :: int
tag = int%tag
end function interaction_get_tag

```

Return the number of particles.

```

<Interactions: public>+≡
public :: interaction_get_n_tot
public :: interaction_get_n_in
public :: interaction_get_n_vir
public :: interaction_get_n_out

<Interactions: procedures>+≡
function interaction_get_n_tot (int) result (n_tot)
integer :: n_tot
type(interaction_t), intent(in) :: int
n_tot = int%n_tot
end function interaction_get_n_tot

```

```

function interaction_get_n_in (int) result (n_in)
  integer :: n_in
  type(interaction_t), intent(in) :: int
  n_in = int%n_in
end function interaction_get_n_in

function interaction_get_n_vir (int) result (n_vir)
  integer :: n_vir
  type(interaction_t), intent(in) :: int
  n_vir = int%n_vir
end function interaction_get_n_vir

function interaction_get_n_out (int) result (n_out)
  integer :: n_out
  type(interaction_t), intent(in) :: int
  n_out = int%n_out
end function interaction_get_n_out

```

Return a momentum index. The flags specify whether to keep/drop incoming, virtual, or outgoing momenta. Check for illegal values.

(Interactions: procedures)+≡

```

function idx (int, i, outgoing)
  integer :: idx
  type(interaction_t), intent(in) :: int
  integer, intent(in) :: i
  logical, intent(in), optional :: outgoing
  logical :: in, vir, out
  if (present (outgoing)) then
    in = .not. outgoing
    vir = .false.
    out = outgoing
  else
    in = .true.
    vir = .true.
    out = .true.
  end if
  idx = 0
  if (in) then
    if (vir) then
      if (out) then
        if (i <= int%n_tot) idx = i
      else
        if (i <= int%n_in + int%n_vir) idx = i
      end if
    else if (out) then
      if (i <= int%n_in) then
        idx = i
      else if (i <= int%n_in + int%n_out) then
        idx = int%n_vir + i
      end if
    else
      if (i <= int%n_in) idx = i
    end if
  end if
end function idx

```



```

        end if
    else if (vir) then
        if (out) then
            if (i <= int%n_vir + int%n_out) idx = int%n_in + i
        else
            if (i <= int%n_vir) idx = int%n_in + i
        end if
    else if (out) then
        if (i <= int%n_out) idx = int%n_in + int%n_vir + i
    end if
    if (idx == 0) then
        call interaction_write (int)
        print *, i, in, vir, out
        call msg_bug (" Momentum index is out of range for this interaction")
    end if
end function idx

```

Return all or just a specific four-momentum.

```

<Interactions: public>+≡
    public :: interaction_get_momenta
    public :: interaction_get_momentum

<Interactions: interfaces>+≡
    interface interaction_get_momenta
        module procedure interaction_get_momenta_all
        module procedure interaction_get_momenta_idx
    end interface

<Interactions: procedures>+≡
    function interaction_get_momenta_all (int, outgoing) result (p)
        type(vector4_t), dimension(:), allocatable :: p
        type(interaction_t), intent(in) :: int
        logical, intent(in), optional :: outgoing
        integer :: i
        if (present (outgoing)) then
            if (outgoing) then
                allocate (p (int%n_out))
            else
                allocate (p (int%n_in))
            end if
        else
            allocate (p (int%n_tot))
        end if
        do i = 1, size (p)
            p(i) = int%p(idx (int, i, outgoing))
        end do
    end function interaction_get_momenta_all

    function interaction_get_momenta_idx (int, jj) result (p)
        type(vector4_t), dimension(:), allocatable :: p
        type(interaction_t), intent(in) :: int
        integer, dimension(:), intent(in) :: jj
        allocate (p (size (jj)))
        p = int%p(jj)
    end function interaction_get_momenta_idx

```

```

function interaction_get_momentum (int, i, outgoing) result (p)
  type(vector4_t) :: p
  type(interaction_t), intent(in) :: int
  integer, intent(in) :: i
  logical, intent(in), optional :: outgoing
  p = int%p(idx (int, i, outgoing))
end function interaction_get_momentum

```

This is a variant as a subroutine. Redundant, but the function above fails at times for gfortran 4.5.0 (double allocation, compiler bug).

```

<Interactions: public>+≡
  public :: interaction_get_momenta_sub

<Interactions: procedures>+≡
  subroutine interaction_get_momenta_sub (int, p, outgoing)
    type(vector4_t), dimension(:), intent(out) :: p
    type(interaction_t), intent(in) :: int
    logical, intent(in), optional :: outgoing
    integer :: i
    do i = 1, size (p)
      p(i) = int%p(idx (int, i, outgoing))
    end do
  end subroutine interaction_get_momenta_sub

```

Transfer PDG codes, masses (initialization) and momenta to a predefined subevent. We use the flavor assignment of the first branch in the interaction state matrix. Only incoming and outgoing particles are transferred. Switch momentum sign for incoming particles.

```

<Interactions: public>+≡
  public :: interaction_to_subevt
  public :: interaction_momenta_to_subevt

<Interactions: interfaces>+≡
  interface interaction_momenta_to_subevt
    module procedure interaction_momenta_to_subevt_id
    module procedure interaction_momenta_to_subevt_tr
  end interface

<Interactions: procedures>+≡
  subroutine interaction_to_subevt (int, j_beam, j_in, j_out, subevt)
    type(interaction_t), intent(in), target :: int
    integer, dimension(:), intent(in) :: j_beam, j_in, j_out
    type(subevt_t), intent(out) :: subevt
    type(flavor_t), dimension(:), allocatable :: flv
    integer :: n_beam, n_in, n_out, i, j
    allocate (flv (int%n_tot))
    flv = quantum_numbers_get_flavor (interaction_get_quantum_numbers (int, 1))
    n_beam = size (j_beam)
    n_in = size (j_in)
    n_out = size (j_out)
    call subevt_init (subevt, n_beam + n_in + n_out)
    do i = 1, n_beam

```

```

        j = j_beam(i)
        call subevt_set_beam (subevt, i, &
            flavor_get_pdg (flv(j)), &
            vector4_null, &
            flavor_get_mass (flv(j)) ** 2)
    end do
    do i = 1, n_in
        j = j_in(i)
        call subevt_set_incoming (subevt, n_beam + i, &
            flavor_get_pdg (flv(j)), &
            vector4_null, &
            flavor_get_mass (flv(j)) ** 2)
    end do
    do i = 1, n_out
        j = j_out(i)
        call subevt_set_outgoing (subevt, n_beam + n_in + i, &
            flavor_get_pdg (flv(j)), &
            vector4_null, &
            flavor_get_mass (flv(j)) ** 2)
    end do
end subroutine interaction_to_subevt

subroutine interaction_momenta_to_subevt_id (int, j_beam, j_in, j_out, subevt)
    type(interaction_t), intent(in) :: int
    integer, dimension(:), intent(in) :: j_beam, j_in, j_out
    type(subevt_t), intent(inout) :: subevt
    call subevt_set_p_beam &
        (subevt, - interaction_get_momenta (int, j_beam))
    call subevt_set_p_incoming &
        (subevt, - interaction_get_momenta (int, j_in))
    call subevt_set_p_outgoing &
        (subevt, interaction_get_momenta (int, j_out))
end subroutine interaction_momenta_to_subevt_id

subroutine interaction_momenta_to_subevt_tr &
    (int, j_beam, j_in, j_out, lt, subevt)
    type(interaction_t), intent(in) :: int
    integer, dimension(:), intent(in) :: j_beam, j_in, j_out
    type(subevt_t), intent(inout) :: subevt
    type(lorentz_transformation_t), intent(in) :: lt
    call subevt_set_p_beam &
        (subevt, - lt * interaction_get_momenta (int, j_beam))
    call subevt_set_p_incoming &
        (subevt, - lt * interaction_get_momenta (int, j_in))
    call subevt_set_p_outgoing &
        (subevt, lt * interaction_get_momenta (int, j_out))
end subroutine interaction_momenta_to_subevt_tr

```

Return a shallow copy of the state matrix:

```

<Interactions: public>+≡
    public :: interaction_get_state_matrix_ptr

<Interactions: procedures>+≡
    function interaction_get_state_matrix_ptr (int) result (state)

```

```

    type(state_matrix_t), pointer :: state
    type(interaction_t), intent(in), target :: int
    state => int%state_matrix
end function interaction_get_state_matrix_ptr

```

Return the array of resonance flags

```

<Interactions: public>+≡
    public :: interaction_get_resonance_flags

<Interactions: procedures>+≡
    function interaction_get_resonance_flags (int) result (resonant)
        type(interaction_t), intent(in) :: int
        logical, dimension(size(int%resonant)) :: resonant
        resonant = int%resonant
    end function interaction_get_resonance_flags

```

Return the quantum-numbers mask (or part of it)

```

<Interactions: public>+≡
    public :: interaction_get_mask

<Interactions: interfaces>+≡
    interface interaction_get_mask
        module procedure interaction_get_mask_all
        module procedure interaction_get_mask_slice
    end interface

<Interactions: procedures>+≡
    function interaction_get_mask_all (int) result (mask)
        type(interaction_t), intent(in) :: int
        type(quantum_numbers_mask_t), dimension(size(int%mask)) :: mask
        mask = int%mask
    end function interaction_get_mask_all

    function interaction_get_mask_slice (int, index) result (mask)
        type(interaction_t), intent(in) :: int
        integer, dimension(:), intent(in) :: index
        type(quantum_numbers_mask_t), dimension(size(index)) :: mask
        mask = int%mask(index)
    end function interaction_get_mask_slice

```

Compute the invariant mass squared of the incoming particles (if any, otherwise outgoing).

```

<Interactions: public>+≡
    public :: interaction_get_s

<Interactions: procedures>+≡
    function interaction_get_s (int) result (s)
        real(default) :: s
        type(interaction_t), intent(in) :: int
        if (int%n_in /= 0) then
            s = sum (int%p(:int%n_in)) ** 2
        else
            s = sum (int%p(int%n_vir+1:)) ** 2
        end if
    end function interaction_get_s

```

```

    end if
end function interaction_get_s

```

Compute the Lorentz transformation that transforms the incoming particles from the center-of-mass frame to the lab frame where they are given. If the c.m. mass squared is negative or zero, return the identity.

```

<Interactions: public>+=
    public :: interaction_get_cm_transformation

<Interactions: procedures>+=
    function interaction_get_cm_transformation (int) result (lt)
        type(lorentz_transformation_t) :: lt
        type(interaction_t), intent(in) :: int
        type(vector4_t) :: p_cm
        real(default) :: s
        if (int%n_in /= 0) then
            p_cm = sum (int%p(:int%n_in))
        else
            p_cm = sum (int%p(int%n_vir+1:))
        end if
        s = p_cm ** 2
        if (s > 0) then
            lt = boost (p_cm, sqrt (s))
        else
            lt = identity
        end if
    end function interaction_get_cm_transformation

```

Return flavor, momentum, and position of the first outgoing unstable particle present in the interaction. Note that we need not iterate through the state matrix; if there is an unstable particle, it will be present in all state-matrix entries.

```

<Interactions: public>+=
    public :: interaction_get_unstable_particle

<Interactions: procedures>+=
    subroutine interaction_get_unstable_particle (int, flv, p, i)
        type(interaction_t), intent(in), target :: int
        type(flavor_t), intent(out) :: flv
        type(vector4_t), intent(out) :: p
        integer, intent(out) :: i
        type(state_iterator_t) :: it
        type(flavor_t), dimension(int%n_tot) :: flv_array
        call state_iterator_init (it, int%state_matrix)
        flv_array = state_iterator_get_flavor (it)
        do i = int%n_in + int%n_vir + 1, int%n_tot
            if (.not. flavor_is_stable (flv_array(i))) then
                flv = flv_array(i)
                p = int%p(i)
                return
            end if
        end do
    end subroutine interaction_get_unstable_particle

```

7.6.6 Modifying contents

Set the quantum numbers mask.

```
(Interactions: public)+≡
    public :: interaction_set_mask

(Interactions: procedures)+≡
    subroutine interaction_set_mask (int, mask)
        type(interaction_t), intent(inout) :: int
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: mask
        int%mask = mask
        int%update_state_matrix = .true.
    end subroutine interaction_set_mask
```

Merge a particular mask entry, respecting a possible helicity lock for this entry. We apply an OR relation, which means that quantum numbers are summed over if either of the two masks requires it.

```
(Interactions: procedures)+≡
    subroutine interaction_merge_mask_entry (int, i, mask)
        type(interaction_t), intent(inout) :: int
        integer, intent(in) :: i
        type(quantum_numbers_mask_t), intent(in) :: mask
        type(quantum_numbers_mask_t) :: mask_tmp
        integer :: ii
        ii = idx (int, i)
        if (int%mask(ii) .neqv. mask) then
            int%mask(ii) = int%mask(ii) .or. mask
            if (int%hel_lock(ii) /= 0) then
                call quantum_numbers_mask_assign (mask_tmp, mask, helicity=.true.)
                int%mask(int%hel_lock(ii)) = int%mask(int%hel_lock(ii)) .or. mask_tmp
            end if
        end if
        int%update_state_matrix = .true.
    end subroutine interaction_merge_mask_entry
```

Fill the momenta array, do not care about the quantum numbers of particles.

```
(Interactions: public)+≡
    public :: interaction_reset_momenta
    public :: interaction_set_momenta
    public :: interaction_set_momentum

(Interactions: procedures)+≡
    subroutine interaction_reset_momenta (int)
        type(interaction_t), intent(inout) :: int
        int%p = vector4_null
        int%p_is_known = .true.
    end subroutine interaction_reset_momenta

    subroutine interaction_set_momenta (int, p, outgoing)
        type(interaction_t), intent(inout) :: int
        type(vector4_t), dimension(:), intent(in) :: p
        logical, intent(in), optional :: outgoing
        integer :: i, index
        do i = 1, size (p)
```

```

        index = idx (int, i, outgoing)
        int%p(index) = p(i)
        int%p_is_known(index) = .true.
    end do
end subroutine interaction_set_momenta

subroutine interaction_set_momentum (int, p, i, outgoing)
    type(interaction_t), intent(inout) :: int
    type(vector4_t), intent(in) :: p
    integer, intent(in) :: i
    logical, intent(in), optional :: outgoing
    integer :: index
    index = idx (int, i, outgoing)
    int%p(index) = p
    int%p_is_known(index) = .true.
end subroutine interaction_set_momentum

```

This more sophisticated version of setting values is used for structure functions, in particular if nontrivial flavor, color, and helicity may be present: set values selectively for the given flavors. If there is more than one flavor, scan the interaction and check for a matching flavor at the specified particle location. If it matches, insert the value that corresponds to this flavor.

```

<Interactions: public>+≡
    public :: interaction_set_flavored_values

<Interactions: procedures>+≡
    subroutine interaction_set_flavored_values (int, value, flv_in, pos)
        type(interaction_t), intent(inout) :: int
        complex(default), dimension(:), intent(in) :: value
        type(flavor_t), dimension(:), intent(in) :: flv_in
        integer, intent(in) :: pos
        type(state_iterator_t) :: it
        type(flavor_t) :: flv
        integer :: i
        if (size (value) == 1) then
            call interaction_set_matrix_element (int, value(1))
        else
            call state_iterator_init (it, int%state_matrix)
            do while (state_iterator_is_valid (it))
                flv = state_iterator_get_flavor (it, pos)
                SCAN_FLV: do i = 1, size (value)
                    if (flv == flv_in(i)) then
                        call state_iterator_set_matrix_element (it, value(i))
                        exit SCAN_FLV
                    end if
                end do SCAN_FLV
                call state_iterator_advance (it)
            end do
        end if
    end subroutine interaction_set_flavored_values

```

7.6.7 Handling Linked interactions

Store relations between corresponding particles within one interaction. The first particle is the parent, the second one the child. Links are established in both directions.

These relations have no effect on the propagation of momenta etc., they are rather used for mother-daughter relations in event output.

```

<Interactions: public>+=
  public :: interaction_relate

<Interactions: procedures>+=
  subroutine interaction_relate (int, i1, i2)
    type(interaction_t), intent(inout), target :: int
    integer, intent(in) :: i1, i2
    if (i1 /= 0 .and. i2 /= 0) then
      call internal_link_list_append (int%children(i1), i2)
      call internal_link_list_append (int%parents(i2), i1)
    end if
  end subroutine interaction_relate

```

Transfer internal parent-child relations defined within interaction `int1` to a new interaction `int` where the particle indices are mapped to. Some particles in `int1` may have no image in `int`. In that case, a child entry maps to zero, and we skip this relation.

Also transfer resonance flags.

```

<Interactions: public>+=
  public :: interaction_transfer_relations

<Interactions: procedures>+=
  subroutine interaction_transfer_relations (int1, int2, map)
    type(interaction_t), intent(in) :: int1
    type(interaction_t), intent(inout), target :: int2
    integer, dimension(:), intent(in) :: map
    type(internal_link_t), pointer :: link
    integer :: i, k
    do i = 1, size (map)
      link => internal_link_list_get_first_ptr (int1%parents(i))
      do while (associated (link))
        k = internal_link_get_index (link)
        call interaction_relate (int2, map(k), map(i))
        call internal_link_advance (link)
      end do
      if (map(i) /= 0) then
        int2%resonant(map(i)) = int1%resonant(i)
      end if
    end do
  end subroutine interaction_transfer_relations

```

Make up internal parent-child relations for the particle(s) that are connected to a new interaction `int`.

If `resonant` is defined and true, the connections are marked as resonant in the result interaction

```

<Interactions: public>+=

```



```

public :: interaction_relate_connections
<Interactions: procedures>+≡
subroutine interaction_relate_connections &
    (int, int_in, connection_index, &
    map, map_connections, resonant)
type(interaction_t), intent(inout), target :: int
type(interaction_t), intent(in) :: int_in
integer, dimension(:), intent(in) :: connection_index
integer, dimension(:), intent(in) :: map, map_connections
logical, intent(in), optional :: resonant
logical :: reson
integer :: i, i2, k2
type(internal_link_t), pointer :: link
reson = .false.; if (present (resonant)) reson = resonant
do i = 1, size (map_connections)
    k2 = connection_index(i)
    link => internal_link_list_get_first_ptr (int_in%children(k2))
    do while (associated (link))
        i2 = internal_link_get_index (link)
        call interaction_relate (int, map_connections(i), map(i2))
        call internal_link_advance (link)
    end do
    int%resonant(map_connections(i)) = reson
end do
end subroutine interaction_relate_connections

```

Return the source/target links of the internal connections of particle i as an array.

```

<Interactions: public>+≡
public :: interaction_get_children
public :: interaction_get_parents
<Interactions: procedures>+≡
function interaction_get_children (int, i) result (idx)
    integer, dimension(:), allocatable :: idx
    type(interaction_t), intent(in) :: int
    integer, intent(in) :: i
    integer :: k
    type(internal_link_t), pointer :: link
    allocate (idx (internal_link_list_get_length (int%children(i))))
    k = 0
    link => internal_link_list_get_first_ptr (int%children(i))
    do while (associated (link))
        k = k + 1
        idx(k) = internal_link_get_index (link)
        call internal_link_advance (link)
    end do
end function interaction_get_children

function interaction_get_parents (int, i) result (idx)
    integer, dimension(:), allocatable :: idx
    type(interaction_t), intent(in) :: int
    integer, intent(in) :: i
    integer :: k

```

```

type(internal_link_t), pointer :: link
allocate (idx (internal_link_list_get_length (int%parents(i))))
k = 0
link => internal_link_list_get_first_ptr (int%parents(i))
do while (associated (link))
  k = k + 1
  idx(k) = internal_link_get_index (link)
  call internal_link_advance (link)
end do
end function interaction_get_parents

```

Add a source link from an interaction to a corresponding particle within another interaction. These links affect the propagation of particles: the two linked particles are considered as the same particle, outgoing and incoming.

```

<Interactions: public>+≡
public :: interaction_set_source_link

<Interactions: interfaces>+≡
interface interaction_set_source_link
  module procedure interaction_set_source_link_int
end interface

<Interactions: procedures>+≡
subroutine interaction_set_source_link_int (int, i, int1, i1)
  type(interaction_t), intent(inout) :: int
  integer, intent(in) :: i
  type(interaction_t), intent(in), target :: int1
  integer, intent(in) :: i1
  if (i /= 0) call external_link_set (int%source(i), int1, i1)
end subroutine interaction_set_source_link_int

```

Reassign links to a new interaction (which is an image of the current interaction).

```

<Interactions: public>+≡
public :: interaction_reassign_links

<Interactions: procedures>+≡
subroutine interaction_reassign_links (int, int_src, int_target)
  type(interaction_t), intent(inout) :: int
  type(interaction_t), intent(in) :: int_src
  type(interaction_t), intent(in), target :: int_target
  integer :: i
  if (allocated (int%source)) then
    do i = 1, size (int%source)
      call external_link_reassign (int%source(i), int_src, int_target)
    end do
  end if
end subroutine interaction_reassign_links

```

Since links are one-directional, if we want to follow them backwards we have to scan all possibilities. This procedure returns the index of the particle within int which points to the particle i1 within interaction int1. If unsuccessful, return zero.

```

<Interactions: public>+≡
public :: interaction_find_link

```

<Interactions: procedures>+≡

```
function interaction_find_link (int, int1, i1) result (i)
  integer :: i
  type(interaction_t), intent(in) :: int, int1
  integer, intent(in) :: i1
  type(interaction_t), pointer :: int_tmp
  do i = 1, int%n_tot
    int_tmp => external_link_get_ptr (int%source(i))
    if (int_tmp%tag == int1%tag) then
      if (external_link_get_index (int%source(i)) == i1) return
    end if
  end do
  i = 0
end function interaction_find_link
```

Follow source links recursively to return the ultimate source of a particle.

<Interactions: procedures>+≡

```
function interaction_get_ultimate_source (int, i) result (link)
  type(external_link_t) :: link
  type(interaction_t), intent(in) :: int
  integer, intent(in) :: i
  type(interaction_t), pointer :: int_src
  integer :: i_src
  link = int%source(i)
  if (external_link_is_set (link)) then
    do
      int_src => external_link_get_ptr (link)
      i_src = external_link_get_index (link)
      if (external_link_is_set (int_src%source(i_src))) then
        link = int_src%source(i_src)
      else
        exit
      end if
    end do
  end if
end function interaction_get_ultimate_source
```

Update mask entries by merging them with corresponding masks in interactions linked to the current one. The mask determines quantum numbers which are summed over.

Note that both the mask of the current interaction and the mask of the linked interaction are updated (side effect!). This ensures that both agree for the linked particle.

<Interactions: public>+≡

```
public :: interaction_exchange_mask
```

<Interactions: procedures>+≡

```
subroutine interaction_exchange_mask (int)
  type(interaction_t), intent(inout) :: int
  integer :: i, index_link
  type(interaction_t), pointer :: int_link
  do i = 1, int%n_tot
    if (external_link_is_set (int%source(i))) then
```

```

        int_link => external_link_get_ptr (int%source(i))
        index_link = external_link_get_index (int%source(i))
        call interaction_merge_mask_entry &
            (int, i, int_link%mask(index_link))
        call interaction_merge_mask_entry &
            (int_link, index_link, int%mask(i))
    end if
end do
call interaction_freeze (int)
end subroutine interaction_exchange_mask

```

Copy momenta from interactions linked to the current one.

```

<Interactions: public>+=
    public :: interaction_receive_momenta

<Interactions: procedures>+=
    subroutine interaction_receive_momenta (int)
        type(interaction_t), intent(inout) :: int
        integer :: i, index_link
        type(interaction_t), pointer :: int_link
        do i = 1, int%n_tot
            if (external_link_is_set (int%source(i))) then
                int_link => external_link_get_ptr (int%source(i))
                index_link = external_link_get_index (int%source(i))
                call interaction_set_momentum (int, int_link%p(index_link), i)
            end if
        end do
    end subroutine interaction_receive_momenta

```

7.6.8 Recovering connections

When creating an evaluator for two interactions, we have to know by which particles they are connected. The connection indices can be determined if we have two linked interactions. We assume that `int1` is the source and `int2` the target, so the connections of interest are stored within `int2`. A connection is found if either the source is `int1`, or the (ultimate) source of a particle within `int2` coincides with the (ultimate) source of a particle within `int1`. The result is an array of index pairs.

To make things simple, we scan the interaction twice, once for counting hits, then allocate the array, then scan again and store the connections.

The connections are scanned for `int2`, which has sources in `int1`. It may happen that the order of connections is interchanged (crossed). We require the indices in `int1` to be sorted, so we reorder both index arrays correspondingly before returning them. (After this, the indices in `int2` may be out of order.)

```

<Interactions: public>+=
    public :: find_connections

<Interactions: procedures>+=
    subroutine find_connections (int1, int2, n, connection_index)
        type(interaction_t), intent(in) :: int1, int2
        integer, intent(out) :: n

```

```

integer, dimension(:,:), intent(out), allocatable :: connection_index
integer, dimension(:,:), allocatable :: conn_index_tmp
integer, dimension(:), allocatable :: ordering
integer :: i, j, k
type(external_link_t) :: link2, link1
type(interaction_t), pointer :: int_link, int_link1
n = 0
do i = 1, size (int2%source)
    link2 = interaction_get_ultimate_source (int2, i)
    if (external_link_is_set (link2)) then
        int_link => external_link_get_ptr (link2)
        if (int_link%tag == int1%tag) then
            n = n + 1
        else
            k = external_link_get_index (link2)
            do j = 1, size (int1%source)
                link1 = interaction_get_ultimate_source (int1, j)
                if (external_link_is_set (link1)) then
                    int_link1 => external_link_get_ptr (link1)
                    if (int_link1%tag == int_link%tag) then
                        if (external_link_get_index (link1) == k) then
                            n = n + 1
                        end if
                    end if
                end if
            end do
        end if
    end if
end do
allocate (conn_index_tmp (n, 2))
n = 0
do i = 1, size (int2%source)
    link2 = interaction_get_ultimate_source (int2, i)
    if (external_link_is_set (link2)) then
        int_link => external_link_get_ptr (link2)
        if (int_link%tag == int1%tag) then
            n = n + 1
            conn_index_tmp(n,1) = external_link_get_index (int2%source(i))
            conn_index_tmp(n,2) = i
        else
            k = external_link_get_index (link2)
            do j = 1, size (int1%source)
                link1 = interaction_get_ultimate_source (int1, j)
                if (external_link_is_set (link1)) then
                    int_link1 => external_link_get_ptr (link1)
                    if (int_link1%tag == int_link%tag) then
                        if (external_link_get_index (link1) == k) then
                            n = n + 1
                            conn_index_tmp(n,1) = j
                            conn_index_tmp(n,2) = i
                        end if
                    end if
                end if
            end do
        end if
    end if
end do

```

```

        end if
    end if
end do
allocate (connection_index (n, 2))
if (n > 1) then
    allocate (ordering (n))
    ordering = order (conn_index_tmp(:,1))
    connection_index = conn_index_tmp(ordering,:)
else
    connection_index = conn_index_tmp
end if
end subroutine find_connections

```

7.6.9 Test

Generate an interaction of a polarized virtual photon and a colored quark which may be either up or down. Remove the quark polarization. Generate another interaction for the quark radiating a photon and link this to the first interaction. The radiation ignores polarization; transfer this information to the first interaction to simplify it. Then, transfer the momentum to the radiating quark and perform a splitting.

(Interactions: public)+≡

```
public :: interaction_test
```

(Interactions: procedures)+≡

```

subroutine interaction_test ()
    type(interaction_t), target :: int, rad
    type(vector4_t), dimension(3) :: p
    type(quantum_numbers_mask_t), dimension(3) :: mask
    p(2) = vector4_moving (500._default, 500._default, 1)
    p(3) = vector4_moving (500._default,-500._default, 1)
    p(1) = p(2) + p(3)
    call interaction_init (int, 1, 0, 2, set_relations=.true., store_values = .true. )
    call int_set (int, 1, -1, 1, 1, cmplx (0.3_default, 0.1_default, kind=default))
    call int_set (int, 1, -1,-1, 1, cmplx (0.5_default,-0.7_default, kind=default))
    call int_set (int, 1, 1, 1, 1, cmplx (0.1_default, 0._default, kind=default))
    call int_set (int, -1, 1, -1, 2, cmplx (0.4_default, -0.1_default, kind=default))
    call int_set (int, 1, 1, 1, 2, cmplx (0.2_default, 0._default, kind=default))
    call interaction_freeze (int)
    call interaction_set_momenta (int, p)
    mask = new_quantum_numbers_mask (.false.,.false., (/ .true.,.true.,.true./))
    call interaction_init (rad, 1, 0, 2, mask=mask, set_relations=.true., store_values = .true.)
    call rad_set (1)
    call rad_set (2)
    call interaction_set_source_link (rad, 1, int, 2)
    call interaction_exchange_mask (rad)
    call interaction_receive_momenta (rad)
    p(1) = interaction_get_momentum (rad, 1)
    p(2) = 0.4_default * p(1)
    p(3) = p(1) - p(2)
    call interaction_set_momenta (rad, p(2:3), outgoing=.true.)
    call interaction_freeze (int)

```

```

call interaction_freeze (rad)
call interaction_set_matrix_element (rad, cmplx (0._default, 0._default, kind=default))
call interaction_write (int)
print *
call interaction_write (rad)
call interaction_final (int)
call interaction_final (rad)
contains
subroutine int_set (int, h1, h2, hq, q, val)
  type(interaction_t), target, intent(inout) :: int
  integer, intent(in) :: h1, h2, hq, q
  type(flavor_t), dimension(3) :: flv
  type(color_t), dimension(3) :: col
  type(helicity_t), dimension(3) :: hel
  type(quantum_numbers_t), dimension(3) :: qn
  complex(default), intent(in) :: val
  call flavor_init (flv, (/21, q, -q/))
  call color_init_col_acl (col(2), 5, 0)
  call color_init_col_acl (col(3), 0, 5)
  call helicity_init (hel, (/h1, hq, -hq/), (/h2, hq, -hq/))
  call quantum_numbers_init (qn, flv, col, hel)
  call interaction_add_state (int, qn)
  call interaction_set_matrix_element (int, val)
end subroutine int_set
subroutine rad_set (q)
  integer, intent(in) :: q
  type(flavor_t), dimension(3) :: flv
  type(quantum_numbers_t), dimension(3) :: qn
  call flavor_init (flv, (/ q, q, 21 /))
  call quantum_numbers_init (qn, flv)
  call interaction_add_state (rad, qn)
end subroutine rad_set
end subroutine interaction_test

```

7.7 Matrix element evaluation

The `evaluator_t` type is an extension of the `interaction_t` type. It represents either a density matrix as the square of a transition matrix element, or the product of two density matrices. Usually, some quantum numbers are summed over in the result.

The `interaction_t` subobject represents a multi-particle interaction with incoming, virtual, and outgoing particles and the associated (not necessarily diagonal) density matrix of quantum state. When the evaluator is initialized, this interaction is constructed from the input interaction(s).

In addition, the initialization process sets up a multiplication table. For each matrix element of the result, it states which matrix elements are to be taken from the input interaction(s), multiplied (optionally, with an additional weight factor) and summed over.

Eventually, to a processes we associate a chain of evaluators which are to be evaluated sequentially. The physical event and its matrix element value(s) can

be extracted from the last evaluator in such a chain.

Evaluators are constructed only once (as long as this is possible) during an initialization step. Then, for each event, momenta are computed and transferred among evaluators using the links within the interaction subobject. The multiplication tables enable fast evaluation of the result without looking at quantum numbers anymore.

```

<evaluators.f90>≡
  <File header>

  module evaluators

    <Use kinds>
    <Use strings>
    <Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use models
    use flavors
    use colors
    use helicities
    use quantum_numbers
    use state_matrices
    use interactions

    <Standard module head>

    <Evaluators: public>

    <Evaluators: parameters>

    <Evaluators: types>

    <Evaluators: interfaces>

    contains

    <Evaluators: procedures>

  end module evaluators

```

7.7.1 Array of pairings

The evaluator contains an array of `pairing_array` objects. This makes up the multiplication table.

Each pairing array contains two list of matrix element indices and a list of numerical factors. The matrix element indices correspond to the input interactions. The corresponding matrix elements are to be multiplied and optionally multiplied by a factor. The results are summed over to yield one specific matrix element of the result evaluator.

```

<Evaluators: types>≡
  type :: pairing_array_t
    integer, dimension(:), allocatable :: i1, i2

```



```

        complex(default), dimension(:), allocatable :: factor
    end type pairing_array_t

```

```

<Evaluators: procedures>≡
    elemental subroutine pairing_array_init (pa, n, has_i2, has_factor)
        type(pairing_array_t), intent(out) :: pa
        integer, intent(in) :: n
        logical, intent(in) :: has_i2, has_factor
        allocate (pa%i1 (n))
        if (has_i2) allocate (pa%i2 (n))
        if (has_factor) allocate (pa%factor (n))
    end subroutine pairing_array_init

```

7.7.2 The evaluator type

Possible variants of evaluators:

```

<Evaluators: parameters>≡
    integer, parameter :: &
        EVAL_UNDEFINED = 0, &
        EVAL_PRODUCT = 1, &
        EVAL_SQUARED_FLOWS = 2, &
        EVAL_SQUARE_WITH_COLOR_FACTORS = 3, &
        EVAL_COLOR_CONTRACTION = 4

```

The evaluator type contains the result interaction and an array of pairing lists, one for each matrix element in the result interaction.

```

<Evaluators: public>≡
    public :: evaluator_t

<Evaluators: types>+≡
    type :: evaluator_t
    private
        integer :: type = EVAL_UNDEFINED
        type(interaction_t), pointer :: int_in1 => null ()
        type(interaction_t), pointer :: int_in2 => null ()
        type(interaction_t) :: int
        type(pairing_array_t), dimension(:), allocatable :: pairing_array
    end type evaluator_t

```

Output.

```

<Evaluators: public>+≡
    public :: evaluator_write

<Evaluators: procedures>+≡
    subroutine evaluator_write (eval, unit, &
        verbose, show_momentum_sum, show_mass, show_state, show_table)
        type(evaluator_t), intent(in) :: eval
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
        logical, intent(in), optional :: show_state, show_table
        logical :: conjugate, square, show_tab
        integer :: u, i, j
    end subroutine evaluator_write

```

```

u = output_unit (unit); if (u < 0) return
show_tab = .true.; if (present (show_table)) show_tab = .false.
write (u, "(A)") "Evaluator:"
call interaction_write &
      (eval%int, unit, verbose, show_momentum_sum, show_mass, show_state)
if (show_tab) then
  write (u, "(1x,A)") "Matrix-element multiplication"
  write (u, "(2x,A)", advance="no") "Input interaction 1:"
  if (associated (eval%int_in1)) then
    write (u, "(1x,I0)") interaction_get_tag (eval%int_in1)
  else
    write (u, *) " [undefined]"
  end if
  write (u, "(2x,A)", advance="no") "Input interaction 2:"
  if (associated (eval%int_in2)) then
    write (u, *) interaction_get_tag (eval%int_in2)
  else
    write (u, *) " [undefined]"
  end if
  select case (eval%type)
  case (EVAL_SQUARED_FLOWS, EVAL_SQUARE_WITH_COLOR_FACTORS)
    conjugate = .true.
    square = .true.
  case default
    conjugate = .false.
    square = .false.
  end select
  if (allocated (eval%pairing_array)) then
    do i = 1, size (eval%pairing_array)
      write (u, "(2x,A,I0,A)") "ME(", i, ") = "
      do j = 1, size (eval%pairing_array(i)%i1)
        write (u, "(4x,A)", advance="no") "+"
        if (allocated (eval%pairing_array(i)%i2)) then
          write (u, "(1x,A,I0,A)", advance="no") &
            "ME1(", eval%pairing_array(i)%i1(j), ")"
          if (conjugate) then
            write (u, "(A)", advance="no") "*" x"
          else
            write (u, "(A)", advance="no") " x"
          end if
          write (u, "(1x,A,I0,A)", advance="no") &
            "ME2(", eval%pairing_array(i)%i2(j), ")"
        else if (square) then
          write (u, "(1x,A)", advance="no") "|"
          write (u, "(A,I0,A)", advance="no") &
            "ME1(", eval%pairing_array(i)%i1(j), ")"
          write (u, "(A)", advance="no") "|^2"
        else
          write (u, "(1x,A,I0,A)", advance="no") &
            "ME1(", eval%pairing_array(i)%i1(j), ")"
        end if
      end if
      if (allocated (eval%pairing_array(i)%factor)) then
        write (u, "(1x,A)", advance="no") "x"
        write (u, *) eval%pairing_array(i)%factor(j)
      end if
    end do
  end if
end if

```

```

        else
            write (u, *)
        end if
    end do
end do
end if
end if
end subroutine evaluator_write

```

Assignment: Deep copy of the interaction component.

```

<Evaluators: public> +=
    public :: assignment(=)
<Evaluators: interfaces> +=
    interface assignment(=)
        module procedure evaluator_assign
    end interface

<Evaluators: procedures> +=
    subroutine evaluator_assign (eval_out, eval_in)
        type(evaluator_t), intent(out) :: eval_out
        type(evaluator_t), intent(in) :: eval_in
        eval_out%type = eval_in%type
        eval_out%int_in1 => eval_in%int_in1
        eval_out%int_in2 => eval_in%int_in2
        eval_out%int = eval_in%int
        if (allocated (eval_in%pairing_array)) then
            allocate (eval_out%pairing_array (size (eval_in%pairing_array)))
            eval_out%pairing_array = eval_in%pairing_array
        end if
    end subroutine evaluator_assign

```

7.7.3 Auxiliary structures for evaluator creation

Creating an evaluator that properly handles all quantum numbers requires some bookkeeping. In this section, we define several auxiliary types and methods that organize and simplify this task. More structures are defined within the specific initializers (as local types and internal subroutines).

These types are currently implemented in a partial object-oriented way: We define some basic methods for initialization etc. here, but the evaluator routines below do access their internals as well. This simplifies some things such as index addressing using array slices, at the expense of losing some clarity.

Index mapping

Index mapping are abundant when constructing an evaluator. To have arrays of index mappings, we define this:

```

<Evaluators: types> +=
    type :: index_map_t
        integer, dimension(:), allocatable :: entry
    end type index_map_t

```

```

<Evaluators: procedures>+≡
    elemental subroutine index_map_init (map, n)
        type(index_map_t), intent(out) :: map
        integer, intent(in) :: n
        allocate (map%entry (n))
    end subroutine index_map_init

<Evaluators: procedures>+≡
    function index_map_exists (map) result (flag)
        logical :: flag
        type(index_map_t), intent(in) :: map
        flag = allocated (map%entry)
    end function index_map_exists

<Evaluators: interfaces>+≡
    interface size
        module procedure index_map_size
    end interface

<Evaluators: procedures>+≡
    function index_map_size (map) result (s)
        integer :: s
        type(index_map_t), intent(in) :: map
        if (allocated (map%entry)) then
            s = size (map%entry)
        else
            s = 0
        end if
    end function index_map_size

<Evaluators: interfaces>+≡
    interface assignment(=)
        module procedure index_map_assign_int
        module procedure index_map_assign_array
    end interface

<Evaluators: procedures>+≡
    elemental subroutine index_map_assign_int (map, ival)
        type(index_map_t), intent(inout) :: map
        integer, intent(in) :: ival
        map%entry = ival
    end subroutine index_map_assign_int

    subroutine index_map_assign_array (map, array)
        type(index_map_t), intent(inout) :: map
        integer, dimension(:), intent(in) :: array
        map%entry = array
    end subroutine index_map_assign_array

<Evaluators: procedures>+≡
    elemental subroutine index_map_set_entry (map, i, ival)
        type(index_map_t), intent(inout) :: map

```

```

integer, intent(in) :: i
integer, intent(in) :: ival
map%entry(i) = ival
end subroutine index_map_set_entry

```

```

<Evaluators: procedures>+≡
elemental function index_map_get_entry (map, i) result (ival)
integer :: ival
type(index_map_t), intent(in) :: map
integer, intent(in) :: i
ival = map%entry(i)
end function index_map_get_entry

```

Index mapping (two-dimensional)

This is a variant with a square matrix instead of an array.

```

<Evaluators: types>+≡
type :: index_map2_t
integer :: s = 0
integer, dimension(:,:), allocatable :: entry
end type index_map2_t

```

```

<Evaluators: procedures>+≡
elemental subroutine index_map2_init (map, n)
type(index_map2_t), intent(out) :: map
integer, intent(in) :: n
map%s = n
allocate (map%entry (n, n))
end subroutine index_map2_init

```

```

<Evaluators: procedures>+≡
function index_map2_exists (map) result (flag)
logical :: flag
type(index_map2_t), intent(in) :: map
flag = allocated (map%entry)
end function index_map2_exists

```

```

<Evaluators: interfaces>+≡
interface size
module procedure index_map2_size
end interface

```

```

<Evaluators: procedures>+≡
function index_map2_size (map) result (s)
integer :: s
type(index_map2_t), intent(in) :: map
s = map%s
end function index_map2_size

```

```

<Evaluators: interfaces>+≡
  interface assignment(=)
    module procedure index_map2_assign_int
  end interface

<Evaluators: procedures>+≡
  elemental subroutine index_map2_assign_int (map, ival)
    type(index_map2_t), intent(inout) :: map
    integer, intent(in) :: ival
    map%entry = ival
  end subroutine index_map2_assign_int

<Evaluators: procedures>+≡
  elemental subroutine index_map2_set_entry (map, i, j, ival)
    type(index_map2_t), intent(inout) :: map
    integer, intent(in) :: i, j
    integer, intent(in) :: ival
    map%entry(i,j) = ival
  end subroutine index_map2_set_entry

<Evaluators: procedures>+≡
  elemental function index_map2_get_entry (map, i, j) result (ival)
    integer :: ival
    type(index_map2_t), intent(in) :: map
    integer, intent(in) :: i, j
    ival = map%entry(i,j)
  end function index_map2_get_entry

```

Auxiliary structures: particle mask

This is a simple container of a logical array.

```

<Evaluators: types>+≡
  type :: prt_mask_t
    logical, dimension(:), allocatable :: entry
  end type prt_mask_t

<Evaluators: procedures>+≡
  subroutine prt_mask_init (mask, n)
    type(prt_mask_t), intent(out) :: mask
    integer, intent(in) :: n
    allocate (mask%entry (n))
  end subroutine prt_mask_init

<Evaluators: interfaces>+≡
  interface size
    module procedure prt_mask_size
  end interface

```

```

(Evaluators: procedures)+≡
function prt_mask_size (mask) result (s)
  integer :: s
  type(prt_mask_t), intent(in) :: mask
  s = size (mask%entry)
end function prt_mask_size

```

Quantum number containers

Trivial transparent containers:

```

(Evaluators: types)+≡
type :: qn_list_t
  type(quantum_numbers_t), dimension(:,:), allocatable :: qn
end type qn_list_t

type :: qn_mask_array_t
  type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
end type qn_mask_array_t

```

Auxiliary structures: connection entries

This type is used as intermediate storage when computing the product of two evaluators or the square of an evaluator. The quantum-number array **qn** corresponds to the particles common to both interactions, but irrelevant quantum numbers (color) masked out. The index arrays **index_in** determine the entries in the input interactions that contribute to this connection. **n_index** is the size of these arrays, and **count** is used while filling the entries. Finally, the quantum-number arrays **qn_in_list** are the actual entries in the input interaction that contribute. In the product case, they exclude the connected quantum numbers.

Each evaluator has its own **connection_table** which contains an array of **connection_entry** objects, but also has stuff that specifically applies to the evaluator type. Hence, we do not generalize the **connection_table_t** type.

The filling procedure **connection_entry_add_state** is specific to the various evaluator types.

```

(Evaluators: types)+≡
type :: connection_entry_t
  type(quantum_numbers_t), dimension(:), allocatable :: qn_conn
  integer, dimension(:), allocatable :: n_index
  integer, dimension(:), allocatable :: count
  type(index_map_t), dimension(:), allocatable :: index_in
  type(qn_list_t), dimension(:), allocatable :: qn_in_list
end type connection_entry_t

```

```

(Evaluators: procedures)+≡
subroutine connection_entry_init &
  (entry, n_count, n_map, qn_conn, count, n_rest)
  type(connection_entry_t), intent(out) :: entry
  integer, intent(in) :: n_count, n_map
  type(quantum_numbers_t), dimension(:), intent(in) :: qn_conn

```

```

integer, dimension(n_count), intent(in) :: count
integer, dimension(n_count), intent(in) :: n_rest
integer :: i
allocate (entry%qn_conn (size (qn_conn)))
allocate (entry%n_index (n_count))
allocate (entry%count (n_count))
allocate (entry%index_in (n_map))
allocate (entry%qn_in_list (n_count))
entry%qn_conn = qn_conn
entry%n_index = count
entry%count = 0
if (size (entry%index_in) == size (count)) then
    call index_map_init (entry%index_in, count)
else
    call index_map_init (entry%index_in, count(1))
end if
do i = 1, n_count
    allocate (entry%qn_in_list(i)%qn (n_rest(i), count(i)))
end do
end subroutine connection_entry_init

```

(Evaluators: procedures) +=

```

subroutine connection_entry_write (entry, unit)
    type(connection_entry_t), intent(in) :: entry
    integer, intent(in), optional :: unit
    integer :: i, j
    integer :: u
    u = output_unit (unit)
    call quantum_numbers_write (entry%qn_conn, unit)
    write (u, *)
    do i = 1, size (entry%n_index)
        write (u, *) "Input interaction", i
        do j = 1, entry%n_index(i)
            if (size (entry%n_index) == size (entry%index_in)) then
                write (u, "(2x,I0,4x,I0,2x)", advance = "no") &
                    j, index_map_get_entry (entry%index_in(i), j)
            else
                write (u, "(2x,I0,4x,I0,2x,I0,2x)", advance = "no") &
                    j, index_map_get_entry (entry%index_in(1), j), &
                    index_map_get_entry (entry%index_in(2), j)
            end if
            call quantum_numbers_write (entry%qn_in_list(i)%qn(:,j), unit)
            write (u, *)
        end do
    end do
end subroutine connection_entry_write

```

Color handling

For managing color-factor computation, we introduce this local type. The `index` is the index in the color table that corresponds to a given matrix element index in the input interaction. The `col` array stores the color assignments in rows.

The `factor` array associates a complex number with each pair of arrays in the color table. The `factor_is_known` array reveals whether a given factor is known already or still has to be computed.

(Evaluators: types)+≡

```
type :: color_table_t
  integer, dimension(:), allocatable :: index
  type(color_t), dimension(:, :), allocatable :: col
  logical, dimension(:, :), allocatable :: factor_is_known
  complex(default), dimension(:, :), allocatable :: factor
end type color_table_t
```

This is the initializer. We extract the color states from the given state matrices, establish index mappings between the two states (implemented by the array `me_index`), make an array of color states, and initialize the color-factor table. The latter is two-dimensional (includes interference) and not yet filled.

(Evaluators: procedures)+≡

```
subroutine color_table_init (color_table, state, n_tot)
  type(color_table_t), intent(out) :: color_table
  type(state_matrix_t), intent(in) :: state
  integer, intent(in) :: n_tot
  type(state_iterator_t) :: it
  type(quantum_numbers_t), dimension(:), allocatable :: qn
  type(state_matrix_t) :: state_col
  integer :: index, n_col_state
  allocate (color_table%index &
    (state_matrix_get_n_matrix_elements (state)))
  color_table%index = 0
  allocate (qn (n_tot))
  call state_matrix_init (state_col)
  call state_iterator_init (it, state)
  do while (state_iterator_is_valid (it))
    index = state_iterator_get_me_index (it)
    call quantum_numbers_init (qn, col = state_iterator_get_color (it))
    call state_matrix_add_state (state_col, qn, &
      me_index = color_table%index(index))
    call state_iterator_advance (it)
  end do
  n_col_state = state_matrix_get_n_matrix_elements (state_col)
  allocate (color_table%col (n_tot, n_col_state))
  call state_iterator_init (it, state_col)
  do while (state_iterator_is_valid (it))
    index = state_iterator_get_me_index (it)
    color_table%col(:, index) = state_iterator_get_color (it)
    call state_iterator_advance (it)
  end do
  call state_matrix_final (state_col)
  allocate (color_table%factor_is_known (n_col_state, n_col_state))
  allocate (color_table%factor (n_col_state, n_col_state))
  color_table%factor_is_known = .false.
end subroutine color_table_init
```

Output (debugging use):

```

(Evaluators: procedures)+≡
subroutine color_table_write (color_table, unit)
  type(color_table_t), intent(in) :: color_table
  integer, intent(in), optional :: unit
  integer :: i, j
  integer :: u
  u = output_unit (unit)
  write (u, *) "Color table:"
  if (allocated (color_table%index)) then
    write (u, *) "  Index mapping state => color table:"
    do i = 1, size (color_table%index)
      write (u, "(3x,I0,2x,I0,2x)") i, color_table%index(i)
    end do
    write (u, *) "  Color table:"
    do i = 1, size (color_table%col, 2)
      write (u, "(3x,I0,2x)", advance = "no") i
      call color_write (color_table%col(:,i), unit)
      write (u, *)
    end do
    write (u, *) "  Defined color factors:"
    do i = 1, size (color_table%factor, 1)
      do j = 1, size (color_table%factor, 2)
        if (color_table%factor_is_known(i,j)) then
          write (u, *) i, j, color_table%factor(i,j)
        end if
      end do
    end do
  end if
end subroutine color_table_write

```

This subroutine sets color factors, based on information from the hard matrix element: the list of pairs of color-flow indices (in the basis of the matrix element code), the list of corresponding factors, and the list of mappings from the matrix element index in the input interaction to the color-flow index in the hard matrix element object.

We first determine the mapping of color-flow indices from the hard matrix element code to the current color table. The mapping could be nontrivial because the latter is derived from iterating over a state matrix, which may return states in non-canonical order. The translation table can be determined because we have, for the complete state matrix, both the mapping to the hard interaction (the input `col_index_hi`) and the mapping to the current color table (the component `color_table%index`).

Once this mapping is known, we scan the list of index pairs `color_flow_index` and translate them to valid color-table index pairs. For this pair, the color factor is set using the corresponding entry in the list `col_factor`.

```

(Evaluators: procedures)+≡
subroutine color_table_set_color_factors (color_table, &
  col_flow_index, col_factor, col_index_hi)
  type(color_table_t), intent(inout) :: color_table
  integer, dimension(:,:), intent(in) :: col_flow_index
  complex(default), dimension(:), intent(in) :: col_factor
  integer, dimension(:), intent(in) :: col_index_hi

```

```

integer, dimension(:), allocatable :: hi_to_ct
integer :: n_cflow
integer :: hi_index, me_index, ct_index, cf_index
integer, dimension(2) :: hi_index_pair, ct_index_pair
n_cflow = size (col_index_hi)
if (size (color_table%index) /= n_cflow) &
    call msg_bug ("Mismatch between hard matrix element and color table")
allocate (hi_to_ct (n_cflow))
do me_index = 1, size (color_table%index)
    ct_index = color_table%index(me_index)
    hi_index = col_index_hi(me_index)
    hi_to_ct(hi_index) = ct_index
end do
do cf_index = 1, size (col_flow_index, 2)
    hi_index_pair = col_flow_index(:,cf_index)
    ct_index_pair = hi_to_ct(hi_index_pair)
    color_table%factor(ct_index_pair(1), ct_index_pair(2)) = &
        col_factor(cf_index)
    color_table%factor_is_known(ct_index_pair(1), ct_index_pair(2)) = .true.
end do
end subroutine color_table_set_color_factors

```

This function returns a color factor, given two indices which point to the matrix elements of the initial state matrix. Internally, we can map them to the corresponding indices in the color table. As a side effect, we store the color factor in the color table for later lookup. (I.e., this function is impure.)

(*Evaluators: procedures*) \equiv

```

function color_table_get_color_factor (color_table, index1, index2, nc) &
    result (factor)
    real(default) :: factor
    type(color_table_t), intent(inout) :: color_table
    integer, intent(in) :: index1, index2
    integer, intent(in), optional :: nc
    integer :: i1, i2
!   print *, "compute color factor ", index1, index2
    i1 = color_table%index(index1)
    i2 = color_table%index(index2)
!   print *, " indices = ", i1, i2
    if (color_table%factor_is_known(i1,i2)) then
        factor = color_table%factor(i1,i2)
!       print *, " is known : ", factor
    else
        factor = compute_color_factor &
            (color_table%col(:,i1), color_table%col(:,i2), nc)
        color_table%factor(i1,i2) = factor
        color_table%factor_is_known(i1,i2) = .true.
!       print *, " computed : ", factor
    end if
end function color_table_get_color_factor

```

7.7.4 Creating an evaluator: Matrix multiplication

The evaluator for matrix multiplication is the most complicated variant.

The initializer takes two input interactions and constructs the result evaluator, which consists of the interaction and the multiplication table for the product (or convolution) of the two. Normally, the input interactions are connected by one or more common particles (e.g., decay, structure function convolution).

In the result interaction, quantum numbers of the connections can be summed over. This is determined by the `qn_mask_conn` argument. The `qn_mask_rest` argument is its analog for the other particles within the result interaction. (E.g., for the trace of the state matrix, all quantum numbers are summed over.) Finally, the `connections_are_resonant` argument tells whether the connecting particles should be marked as resonant in the final event record. This is useful for decays.

The algorithm consists of the following steps:

1. **find_connections:** Find the particles which are connected, i.e., common to both input interactions. Either they are directly linked, or both are linked to a common source.
2. **compute_index_bounds_and_mappings:** Compute the mappings of particle indices from the input interactions to the result interaction. There is a separate mapping for the connected particles.
3. **accumulate_connected_states:** Create an auxiliary state matrix which lists the possible quantum numbers for the connected particles. When building this matrix, count the number of times each assignment is contained in any of the input states and, for each of the input states, record the index of the matrix element within the new state matrix. For the connected particles, reassign color indices such that no color state is present twice in different color-index assignment. Note that helicity assignments of the connected state can be (and will be) off-diagonal, so no spin correlations are lost in decays.

Do this for both input interactions.

4. **allocate_connection_entries:** Allocate a table of connections. Each table row corresponds to one state in the auxiliary matrix, and to multiple states of the input interactions. It collects all states of the unconnected particles in the two input interactions that are associated with the particular state (quantum-number assignment) of the connected particles.
5. **fill_connection_table:** Fill the table of connections by scanning both input interactions. When copying states, reassign color indices for the unconnected particles such that they match between all involved particle sets (interaction 1, interaction 2, and connected particles).
6. **make_product_interaction:** Scan the table of connections we have just built. For each entry, construct all possible pairs of states of the unconnected particles and combine them with the specific connected-particle state. This is a possible quantum-number assignment of the result interaction. Now mask all quantum numbers that should be summed over, and append this to the result state matrix. Record the matrix element index of the result. We now have the result interaction.

7. **make_pairing_array**: First allocate the pairing array with the number of entries of the result interaction. Then scan the table of connections again. For each entry, record the indices of the matrix elements which have to be multiplied and summed over in order to compute this particular matrix element. This makes up the multiplication table.
8. **record_links**: Transfer all source pointers from the input interactions to the result interaction. Do the same for the internal parent-child relations and resonance assignments. For the connected particles, make up appropriate additional parent-child relations. This allows for fetching momenta from other interactions when a new event is filled, and to reconstruct the event history when the event is analyzed.

After all this is done, for each event, we just have to evaluate the pairing arrays (multiplication tables) in order to compute the result matrix elements in their proper positions. The quantum-number assignments remain fixed from now on.

```

(Evaluators: public)+≡
    public :: evaluator_init_product

(Evaluators: interfaces)+≡
    interface evaluator_init_product
        module procedure evaluator_init_product_ii
        module procedure evaluator_init_product_ie
        module procedure evaluator_init_product_ei
        module procedure evaluator_init_product_ee
    end interface

(Evaluators: procedures)+≡
    subroutine evaluator_init_product_ii &
        (eval, int_in1, int_in2, qn_mask_conn, qn_mask_rest, &
         connections_are_resonant)

        type(evaluator_t), intent(out), target :: eval
        type(interaction_t), intent(in), target :: int_in1, int_in2
        type(quantum_numbers_mask_t), intent(in) :: qn_mask_conn
        type(quantum_numbers_mask_t), intent(in), optional :: qn_mask_rest
        logical, intent(in), optional :: connections_are_resonant

        type(qn_mask_array_t), dimension(2) :: qn_mask_in

        type :: connection_table_t
            integer :: n_conn = 0
            integer, dimension(2) :: n_rest = 0
            integer :: n_tot = 0
            integer :: n_me_conn = 0
            type(state_matrix_t) :: state
            type(index_map_t), dimension(:), allocatable :: index_conn
            type(connection_entry_t), dimension(:), allocatable :: entry
            type(index_map_t) :: index_result
        end type connection_table_t
        type(connection_table_t) :: connection_table

```

```

integer :: n_in, n_vir, n_out, n_tot
integer, dimension(2) :: n_rest
integer :: n_conn, n_me_conn

integer, dimension(:,:), allocatable :: connection_index
type(index_map_t), dimension(2) :: prt_map_in
type(index_map_t) :: prt_map_conn
type(prt_mask_t), dimension(2) :: prt_is_connected
type(quantum_numbers_mask_t), dimension(:), allocatable :: &
    qn_mask_conn_initial

integer :: i

eval%type = EVAL_PRODUCT
eval%int_in1 => int_in1
eval%int_in2 => int_in2
!     print *, "Evaluator product"
!     print *, "First interaction"
!     call interaction_write (int_in1)
!     print *
!     print *, "Second interaction"
!     call interaction_write (int_in2)
!     print *

call find_connections (int_in1, int_in2, n_conn, connection_index)
if (n_conn == 0) then
    call msg_message ("First interaction:")
    call interaction_write (int_in1)
    call msg_message ("Second interaction:")
    call interaction_write (int_in2)
    call msg_fatal ("Evaluator product: no connections found between factors")
end if
call compute_index_bounds_and_mappings &
    (int_in1, int_in2, n_conn, &
     n_in, n_vir, n_out, n_tot, &
     n_rest, prt_map_in, prt_map_conn)

call prt_mask_init (prt_is_connected(1), interaction_get_n_tot (int_in1))
call prt_mask_init (prt_is_connected(2), interaction_get_n_tot (int_in2))
do i = 1, 2
    prt_is_connected(i)%entry = .true.
    prt_is_connected(i)%entry(connection_index(:,i)) = .false.
end do
allocate (qn_mask_conn_initial (n_conn))
qn_mask_conn_initial = &
    interaction_get_mask (int_in1, connection_index(:,1)) .or. &
    interaction_get_mask (int_in2, connection_index(:,2))
allocate (qn_mask_in(1)%mask (interaction_get_n_tot (int_in1)))
allocate (qn_mask_in(2)%mask (interaction_get_n_tot (int_in2)))
qn_mask_in(1)%mask = interaction_get_mask (int_in1)
qn_mask_in(2)%mask = interaction_get_mask (int_in2)

call connection_table_init (connection_table, &
    interaction_get_state_matrix_ptr (int_in1), &

```

```

        interaction_get_state_matrix_ptr (int_in2), &
        qn_mask_conn_initial, &
        n_conn, connection_index, n_rest)
call connection_table_fill (connection_table, &
    interaction_get_state_matrix_ptr (int_in1), &
    interaction_get_state_matrix_ptr (int_in2), &
    connection_index, prt_is_connected)
call make_product_interaction (eval%int, &
    n_in, n_vir, n_out, &
    connection_table, &
    prt_map_in, prt_is_connected, &
    qn_mask_in, qn_mask_conn_initial, qn_mask_conn, qn_mask_rest)
!    call connection_table_write (connection_table)
call make_pairing_array (eval%pairing_array, &
    interaction_get_n_matrix_elements (eval%int), &
    connection_table)
call record_links (eval%int, &
    int_in1, int_in2, connection_index, prt_map_in, prt_map_conn, &
    prt_is_connected, connections_are_resonant)
call connection_table_final (connection_table)

!    print *, "Result evaluator"
!    call evaluator_write (eval)

if (interaction_get_n_matrix_elements (eval%int) == 0) then
    print *, "Evaluator product"
    print *, "First interaction"
    call interaction_write (int_in1)
    print *
    print *, "Second interaction"
    call interaction_write (int_in2)
    print *
    call msg_fatal ("Product of density matrices is empty", &
        (/ var_str (" -----"), &
        var_str ("This happens when two density matrices are convoluted "), &
        var_str ("but the processes they belong to (e.g., production "), &
        var_str ("and decay) do not match. This could happen if the "), &
        var_str ("beam specification does not match the hard "), &
        var_str ("process. Or it may indicate a WHIZARD bug.") /) )
end if

contains

subroutine compute_index_bounds_and_mappings &
    (int1, int2, n_conn, &
    n_in, n_vir, n_out, n_tot, &
    n_rest, prt_map_in, prt_map_conn)
type(interaction_t), intent(in) :: int1, int2
integer, intent(in) :: n_conn
integer, intent(out) :: n_in, n_vir, n_out, n_tot
integer, dimension(2), intent(out) :: n_rest
type(index_map_t), dimension(2), intent(out) :: prt_map_in
type(index_map_t), intent(out) :: prt_map_conn
integer, dimension(:), allocatable :: index

```

```

integer :: n_in1, n_vir1, n_out1
integer :: n_in2, n_vir2, n_out2
integer :: k
n_in1 = interaction_get_n_in (int1)
n_vir1 = interaction_get_n_vir (int1)
n_out1 = interaction_get_n_out (int1) - n_conn
n_rest(1) = n_in1 + n_vir1 + n_out1
n_in2 = interaction_get_n_in (int2) - n_conn
n_vir2 = interaction_get_n_vir (int2)
n_out2 = interaction_get_n_out (int2)
n_rest(2) = n_in2 + n_vir2 + n_out2
n_in = n_in1 + n_in2
n_vir = n_vir1 + n_vir2 + n_conn
n_out = n_out1 + n_out2
n_tot = n_in + n_vir + n_out
call index_map_init (prt_map_in, n_rest)
call index_map_init (prt_map_conn, n_conn)
allocate (index (n_tot))
index = (/ (i, i = 1, n_tot) /)
prt_map_in(1)%entry(1 : n_in1) = index( 1 : n_in1)
k = n_in1
prt_map_in(2)%entry(1 : n_in2) = index(k+1 : k+n_in2)
k = k + n_in2
prt_map_in(1)%entry(n_in1+1 : n_in1+n_vir1) = index(k+1 : k+n_vir1)
k = k + n_vir1
prt_map_in(2)%entry(n_in2+1 : n_in2+n_vir2) = index(k+1 : k+n_vir2)
k = k + n_vir2
prt_map_conn%entry = index(k+1 : k+n_conn)
k = k + n_conn
prt_map_in(1)%entry(n_in1+n_vir1+1 : n_rest(1)) = index(k+1 : k+n_out1)
k = k + n_out1
prt_map_in(2)%entry(n_in2+n_vir2+1 : n_rest(2)) = index(k+1 : k+n_out2)
end subroutine compute_index_bounds_and_mappings

subroutine connection_table_init &
  (connection_table, state_in1, state_in2, qn_mask_conn, &
   n_conn, connection_index, n_rest)
type(connection_table_t), intent(out) :: connection_table
type(state_matrix_t), intent(in), target :: state_in1, state_in2
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_conn
integer, intent(in) :: n_conn
integer, dimension(:,:), intent(in) :: connection_index
integer, dimension(2), intent(in) :: n_rest
integer, dimension(2) :: n_me_in
type(state_iterator_t) :: it
type(quantum_numbers_t), dimension(n_conn) :: qn
integer :: i, me_index_in, me_index_conn, n_me_conn
integer, dimension(2) :: me_count
connection_table%n_conn = n_conn
connection_table%n_rest = n_rest
n_me_in(1) = state_matrix_get_n_matrix_elements (state_in1)
n_me_in(2) = state_matrix_get_n_matrix_elements (state_in2)
allocate (connection_table%index_conn (2))
call index_map_init (connection_table%index_conn, n_me_in)

```



```

connection_table%index_conn = 0
call state_matrix_init (connection_table%state, n_counters=2)
do i = 1, 2
  select case (i)
    case (1); call state_iterator_init (it, state_in1)
    case (2); call state_iterator_init (it, state_in2)
  end select
  do while (state_iterator_is_valid (it))
    qn = state_iterator_get_quantum_numbers (it, connection_index(:,i))
    call quantum_numbers_undefine (qn, qn_mask_conn)
    call quantum_numbers_canonicalize_color (qn)
    me_index_in = state_iterator_get_me_index (it)
    call state_matrix_add_state (connection_table%state, qn, &
      counter_index = i, me_index = me_index_conn)
    call index_map_set_entry (connection_table%index_conn(i), &
      me_index_in, me_index_conn)
    call state_iterator_advance (it)
  end do
end do
n_me_conn = state_matrix_get_n_matrix_elements (connection_table%state)
connection_table%n_me_conn = n_me_conn
allocate (connection_table%entry (n_me_conn))
call state_iterator_init (it, connection_table%state)
do while (state_iterator_is_valid (it))
  i = state_iterator_get_me_index (it)
  me_count = state_iterator_get_me_count (it)
  call connection_entry_init (connection_table%entry(i), 2, 2, &
    state_iterator_get_quantum_numbers (it), &
    me_count, n_rest)
  call state_iterator_advance (it)
end do
end subroutine connection_table_init

subroutine connection_table_final (connection_table)
  type(connection_table_t), intent(inout) :: connection_table
  call state_matrix_final (connection_table%state)
end subroutine connection_table_final

subroutine connection_table_write (connection_table, unit)
  type(connection_table_t), intent(in) :: connection_table
  integer, intent(in), optional :: unit
  integer :: i, j
  integer :: u
  u = output_unit (unit)
  write (u, *) "Connection table:"
  call state_matrix_write (connection_table%state, unit)
  if (allocated (connection_table%index_conn)) then
    write (u, *) " Index mapping input => connection table:"
    do i = 1, size (connection_table%index_conn)
      write (u, *) " Input state", i
      do j = 1, size (connection_table%index_conn(i))
        write (u, *) j, &
          index_map_get_entry (connection_table%index_conn(i), j)
      end do
    end do
  end if
end subroutine connection_table_write

```

```

        end do
    end if
    if (allocated (connection_table%entry)) then
        write (u, *) " Connection table contents:"
        do i = 1, size (connection_table%entry)
            call connection_entry_write (connection_table%entry(i), unit)
        end do
    end if
    if (index_map_exists (connection_table%index_result)) then
        write (u, *) " Index mapping connection table => output:"
        do i = 1, size (connection_table%index_result)
            write (u, *) i, &
                index_map_get_entry (connection_table%index_result, i)
        end do
    end if
end subroutine connection_table_write

subroutine connection_table_fill &
    (connection_table, state_in1, state_in2, &
     connection_index, prt_is_connected)
type(connection_table_t), intent(inout) :: connection_table
type(state_matrix_t), intent(in), target :: state_in1, state_in2
integer, dimension(:, :), intent(in) :: connection_index
type(prt_mask_t), dimension(2), intent(in) :: prt_is_connected
type(state_iterator_t) :: it
integer :: index_in, index_conn
integer :: color_offset
integer :: n_result_entries
integer :: i, k
color_offset = state_matrix_get_max_color_value (connection_table%state)
do i = 1, 2
    select case (i)
    case (1); call state_iterator_init (it, state_in1)
    case (2); call state_iterator_init (it, state_in2)
    end select
    do while (state_iterator_is_valid (it))
        index_in = state_iterator_get_me_index (it)
        index_conn = index_map_get_entry &
            (connection_table%index_conn(i), index_in)
        if (index_conn /= 0) then
            call connection_entry_add_state &
                (connection_table%entry(index_conn), i, &
                 index_in, &
                 state_iterator_get_quantum_numbers (it), &
                 connection_index(:, i), prt_is_connected(i), &
                 color_offset)
        end if
        call state_iterator_advance (it)
    end do
    color_offset = color_offset &
        + state_matrix_get_max_color_value (state_in1)
end do
n_result_entries = 0
do k = 1, size (connection_table%entry)

```

```

        n_result_entries = &
            n_result_entries + product (connection_table%entry(k)%n_index)
    end do
    call index_map_init (connection_table%index_result, n_result_entries)
end subroutine connection_table_fill

subroutine connection_entry_add_state &
    (entry, i, index_in, qn_in, connection_index, prt_is_connected, &
    color_offset)
    type(connection_entry_t), intent(inout) :: entry
    integer, intent(in) :: i
    integer, intent(in) :: index_in
    type(quantum_numbers_t), dimension(:), intent(in) :: qn_in
    integer, dimension(:), intent(in) :: connection_index
    type(prt_mask_t), intent(in) :: prt_is_connected
    integer, intent(in) :: color_offset
    integer :: c, k
    integer, dimension(:,:), allocatable :: color_map
    entry%count(i) = entry%count(i) + 1
    c = entry%count(i)
    call quantum_numbers_set_color_map &
        (color_map, qn_in(connection_index), entry%qn_conn)
    call index_map_set_entry (entry%index_in(i), c, index_in)
    entry%qn_in_list(i)%qn(:,c) = pack (qn_in, prt_is_connected%entry)
    call quantum_numbers_translate_color &
        (entry%qn_in_list(i)%qn(:,c), color_map, color_offset)
end subroutine connection_entry_add_state

subroutine make_product_interaction (int, &
    n_in, n_vir, n_out, &
    connection_table, &
    prt_map_in, prt_is_connected, &
    qn_mask_in, qn_mask_conn_initial, qn_mask_conn, qn_mask_rest)
    type(interaction_t), intent(out), target :: int
    integer, intent(in) :: n_in, n_vir, n_out
    type(connection_table_t), intent(inout), target :: connection_table
    type(index_map_t), dimension(2), intent(in) :: prt_map_in
    type(prt_mask_t), dimension(2), intent(in) :: prt_is_connected
    type(qn_mask_array_t), dimension(2), intent(in) :: qn_mask_in
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: &
        qn_mask_conn_initial
    type(quantum_numbers_mask_t), intent(in) :: qn_mask_conn
    type(quantum_numbers_mask_t), intent(in), optional :: qn_mask_rest
    type(index_map_t), dimension(2) :: prt_index_in
    type(index_map_t) :: prt_index_conn
    integer :: n_tot, n_conn
    integer, dimension(2) :: n_rest
    integer :: i, j, k, m
    type(quantum_numbers_t), dimension(:), allocatable :: qn
    type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
    type(connection_entry_t), pointer :: entry
    integer :: result_index
    n_conn = connection_table%n_conn
    n_rest = connection_table%n_rest

```

```

n_tot = sum (n_rest) + n_conn
allocate (qn (n_tot), qn_mask (n_tot))
do i = 1, 2
    call index_map_init (prt_index_in(i), n_rest(i))
    prt_index_in(i) = &
        prt_map_in(i)%entry ((/ (j, j = 1, n_rest(i)) /))
end do
call index_map_init (prt_index_conn, n_conn)
prt_index_conn = prt_map_conn%entry ((/ (j, j = 1, n_conn) /))
do i = 1, 2
    if (present (qn_mask_rest)) then
        qn_mask(prt_index_in(i)%entry) = &
            pack (qn_mask_in(i)%mask, prt_is_connected(i)%entry) &
            .or. qn_mask_rest
    else
        qn_mask(prt_index_in(i)%entry) = &
            pack (qn_mask_in(i)%mask, prt_is_connected(i)%entry)
    end if
end do
qn_mask(prt_index_conn%entry) = qn_mask_conn_initial .or. qn_mask_conn
call interaction_init (eval%int, n_in, n_vir, n_out, mask=qn_mask)
m = 1
do i = 1, connection_table%n_me_conn
    entry => connection_table%entry(i)
    qn(prt_index_conn%entry) = &
        quantum_numbers_undefined (entry%qn_conn, qn_mask_conn)
    do j = 1, entry%n_index(1)
        qn(prt_index_in(1)%entry) = entry%qn_in_list(1)%qn(:,j)
    do k = 1, entry%n_index(2)
        qn(prt_index_in(2)%entry) = entry%qn_in_list(2)%qn(:,k)
        call interaction_add_state (int, qn, me_index = result_index)
        call index_map_set_entry &
            (connection_table%index_result, m, result_index)
        m = m + 1
    end do
    end do
end do
call interaction_freeze (int)
end subroutine make_product_interaction

subroutine make_pairing_array (pa, n_matrix_elements, connection_table)
    type(pairing_array_t), dimension(:), intent(out), allocatable :: pa
    integer, intent(in) :: n_matrix_elements
    type(connection_table_t), intent(in), target :: connection_table
    type(connection_entry_t), pointer :: entry
    integer, dimension(:), allocatable :: n_entries
    integer :: i, j, k, m, r
    allocate (pa (n_matrix_elements))
    allocate (n_entries (n_matrix_elements))
    n_entries = 0
    do m = 1, size (connection_table%index_result)
        r = index_map_get_entry (connection_table%index_result, m)
        n_entries(r) = n_entries(r) + 1
    end do

```

```

call pairing_array_init &
  (pa, n_entries, has_i2=.true., has_factor=.false.)
m = 1
n_entries = 0
do i = 1, connection_table%n_me_conn
  entry => connection_table%entry(i)
  do j = 1, entry%n_index(1)
    do k = 1, entry%n_index(2)
      r = index_map_get_entry (connection_table%index_result, m)
      n_entries(r) = n_entries(r) + 1
      pa(r)%i1(n_entries(r)) = &
        index_map_get_entry (entry%index_in(1), j)
      pa(r)%i2(n_entries(r)) = &
        index_map_get_entry (entry%index_in(2), k)
      m = m + 1
    end do
  end do
end do
end subroutine make_pairing_array

subroutine record_links (int, &
  int_in1, int_in2, connection_index, prt_map_in, prt_map_conn, &
  prt_is_connected, connections_are_resonant)
type(interaction_t), intent(inout) :: int
type(interaction_t), intent(in), target :: int_in1, int_in2
integer, dimension(:,:), intent(in) :: connection_index
type(index_map_t), dimension(2), intent(in) :: prt_map_in
type(index_map_t), intent(in) :: prt_map_conn
type(prt_mask_t), dimension(2), intent(in) :: prt_is_connected
logical, intent(in), optional :: connections_are_resonant
type(index_map_t), dimension(2) :: prt_map_all
integer :: i, j, k, ival
call index_map_init (prt_map_all(1), size (prt_is_connected(1)))
k = 0
j = 0
do i = 1, size (prt_is_connected(1))
  if (prt_is_connected(1)%entry(i)) then
    j = j + 1
    ival = index_map_get_entry (prt_map_in(1), j)
    call index_map_set_entry (prt_map_all(1), i, ival)
  else
    k = k + 1
    ival = index_map_get_entry (prt_map_conn, k)
    call index_map_set_entry (prt_map_all(1), i, ival)
  end if
  call interaction_set_source_link (int, ival, int_in1, i)
end do
call interaction_transfer_relations (int_in1, int, prt_map_all(1)%entry)
call index_map_init (prt_map_all(2), size (prt_is_connected(2)))
j = 0
do i = 1, size (prt_is_connected(2))
  if (prt_is_connected(2)%entry(i)) then
    j = j + 1
    ival = index_map_get_entry (prt_map_in(2), j)

```

```

        call index_map_set_entry (prt_map_all(2), i, ival)
        call interaction_set_source_link (int, ival, int_in2, i)
    else
        call index_map_set_entry (prt_map_all(2), i, 0)
    end if
end do
call interaction_transfer_relations (int_in2, int, prt_map_all(2)%entry)
call interaction_relate_connections (int, &
    int_in2, connection_index(:,2), prt_map_all(2)%entry, &
    prt_map_conn%entry, connections_are_resonant)
end subroutine record_links

end subroutine evaluator_init_product_ii

subroutine evaluator_init_product_ie &
    (eval, int_in1, eval_in2, qn_mask_conn, qn_mask_rest, &
    connections_are_resonant)
type(evaluator_t), intent(out), target :: eval
type(interaction_t), intent(in), target :: int_in1
type(evaluator_t), intent(in), target :: eval_in2
type(quantum_numbers_mask_t), intent(in) :: qn_mask_conn
type(quantum_numbers_mask_t), intent(in), optional :: qn_mask_rest
logical, intent(in), optional :: connections_are_resonant
call evaluator_init_product_ii &
    (eval, int_in1, eval_in2%int, qn_mask_conn, qn_mask_rest, &
    connections_are_resonant)
end subroutine evaluator_init_product_ie

subroutine evaluator_init_product_ei &
    (eval, eval_in1, int_in2, qn_mask_conn, qn_mask_rest, &
    connections_are_resonant)
type(evaluator_t), intent(out), target :: eval
type(evaluator_t), intent(in), target :: eval_in1
type(interaction_t), intent(in), target :: int_in2
type(quantum_numbers_mask_t), intent(in) :: qn_mask_conn
type(quantum_numbers_mask_t), intent(in), optional :: qn_mask_rest
logical, intent(in), optional :: connections_are_resonant
call evaluator_init_product_ii &
    (eval, eval_in1%int, int_in2, qn_mask_conn, qn_mask_rest, &
    connections_are_resonant)
end subroutine evaluator_init_product_ei

subroutine evaluator_init_product_ee &
    (eval, eval_in1, eval_in2, qn_mask_conn, qn_mask_rest, &
    connections_are_resonant)
type(evaluator_t), intent(out), target :: eval
type(evaluator_t), intent(in), target :: eval_in1, eval_in2
type(quantum_numbers_mask_t), intent(in) :: qn_mask_conn
type(quantum_numbers_mask_t), intent(in), optional :: qn_mask_rest
logical, intent(in), optional :: connections_are_resonant
call evaluator_init_product_ii &
    (eval, eval_in1%int, eval_in2%int, qn_mask_conn, qn_mask_rest, &
    connections_are_resonant)
end subroutine evaluator_init_product_ee

```

7.7.5 Creating an evaluator: square

The generic initializer for an evaluator that squares a matrix element. Depending on the provided mask, we select the appropriate specific initializer for either diagonal or non-diagonal helicity density matrices.

```

(Evaluators: public)+≡
    public :: evaluator_init_square

(Evaluators: procedures)+≡
    subroutine evaluator_init_square (eval, int_in, qn_mask, &
        col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)
        type(evaluator_t), intent(out), target :: eval
        type(interaction_t), intent(in), target :: int_in
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
        integer, dimension(:,:), intent(in), optional :: col_flow_index
        complex(default), dimension(:), intent(in), optional :: col_factor
        integer, dimension(:), intent(in), optional :: col_index_hi
        logical, intent(in), optional :: expand_color_flows
        integer, intent(in), optional :: nc
        if (all (quantum_numbers_mask_diagonal_helicity (qn_mask))) then
            call evaluator_init_square_diag (eval, int_in, qn_mask, &
                col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)
        else
            call evaluator_init_square_nondiag (eval, int_in, qn_mask, &
                col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)
        end if
    end subroutine evaluator_init_square

```

Color-summed squared matrix (diagonal helicities)

The initializer for an evaluator that squares a matrix element, including color factors. The mask must be such that off-diagonal matrix elements are excluded.

If `color_flows` is set, the evaluator keeps color-flow entries separate and drops all interfering color structures. The color factors are set to unity in this case.

There is only one input interaction. The quantum-number mask is an array, one entry for each particle, so they can be treated individually. For academic purposes, we allow for the number of colors being different from three (but 3 is the default).

The algorithm is analogous to multiplication, with a few notable differences:

1. The connected particles are known, the correspondence is one-to-one. All particles are connected, and the mapping of indices is trivial, which simplifies the following steps.
2. **accumulate_connected_states**: The matrix of connected states encompasses all particles, but color indices are removed. However, ghost states are still kept separate from physical color states. No color-index reassignment is necessary.

3. The table of connections contains single index and quantum-number arrays instead of pairs of them. They are paired with themselves in all possible ways.
4. `make_squared_interaction`: Now apply the predefined quantum-numbers mask, which usually collects all color states (physical and ghosts), and possibly a helicity sum.
5. `make_pairing_array`: For each pair of input states, compute the color factor (including a potential ghost-parity sign) and store this in the pairing array together with the matrix-element indices for multiplication.
6. `record_links`: This is again trivial due to the one-to-one correspondence.

```

(Evaluators: public)+≡
  public :: evaluator_init_square_diag

(Evaluators: procedures)+≡
  subroutine evaluator_init_square_diag (eval, int_in, qn_mask, &
    col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)

    type(evaluator_t), intent(out), target :: eval
    type(interaction_t), intent(in), target :: int_in
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
    integer, dimension(:,:), intent(in), optional :: col_flow_index
    complex(default), dimension(:), intent(in), optional :: col_factor
    integer, dimension(:), intent(in), optional :: col_index_hi
    logical, intent(in), optional :: expand_color_flows
    integer, intent(in), optional :: nc

    integer :: n_in, n_vir, n_out, n_tot
    integer :: n_me_in
    type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask_initial

    type :: connection_table_t
      integer :: n_tot = 0
      integer :: n_me_conn = 0
      type(state_matrix_t) :: state
      type(index_map_t) :: index_conn
      type(connection_entry_t), dimension(:), allocatable :: entry
      type(index_map_t) :: index_result
    end type connection_table_t
    type(connection_table_t) :: connection_table

    logical :: sum_colors
    type(color_table_t) :: color_table

    if (present (expand_color_flows)) then
      sum_colors = .not. expand_color_flows
    else
      sum_colors = .true.
    end if

    if (sum_colors) then
      eval%type = EVAL_SQUARE_WITH_COLOR_FACTORS

```



```

else
    eval%type = EVAL_SQUARED_FLOWS
end if
eval%int_in1 => int_in

!    print *, "Interaction square with color factors (diag)"
!    print *, "Input interaction"
!    call interaction_write (int_in)

n_in  = interaction_get_n_in  (int_in)
n_vir = interaction_get_n_vir (int_in)
n_out = interaction_get_n_out (int_in)
n_tot = interaction_get_n_tot (int_in)

allocate (qn_mask_initial (n_tot))
qn_mask_initial = interaction_get_mask (int_in)
call quantum_numbers_mask_set_color &
    (qn_mask_initial, sum_colors, mask_cg=.false.)
if (sum_colors) then
    call color_table_init &
        (color_table, interaction_get_state_matrix_ptr (int_in), n_tot)
    if (present (col_flow_index) .and. present (col_factor) &
        .and. present (col_index_hi)) then
        call color_table_set_color_factors &
            (color_table, col_flow_index, col_factor, col_index_hi)
    end if
!    call color_table_write (color_table)
end if

call connection_table_init (connection_table, &
    interaction_get_state_matrix_ptr (int_in), &
    qn_mask_initial, qn_mask, n_tot)
call connection_table_fill (connection_table, &
    interaction_get_state_matrix_ptr (int_in))
call make_squared_interaction (eval%int, &
    n_in, n_vir, n_out, n_tot, &
    connection_table, sum_colors, qn_mask_initial .or. qn_mask)
call make_pairing_array (eval%pairing_array, &
    interaction_get_n_matrix_elements (eval%int), &
    connection_table, sum_colors, color_table, n_in, n_tot, nc)
call record_links (eval%int, int_in, n_tot)
call connection_table_final (connection_table)
!    print *, "Result evaluator:"
!    call evaluator_write (eval)

contains

subroutine connection_table_init &
    (connection_table, state_in, qn_mask_in, qn_mask, n_tot)
type(connection_table_t), intent(out) :: connection_table
type(state_matrix_t), intent(in), target :: state_in
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
integer, intent(in) :: n_tot

```

```

type(quantum_numbers_t), dimension(n_tot) :: qn
type(state_iterator_t) :: it
integer :: i, n_me_in, me_index_in
integer :: me_index_conn, n_me_conn
integer, dimension(1) :: me_count
connection_table%n_tot = n_tot
n_me_in = state_matrix_get_n_matrix_elements (state_in)
call index_map_init (connection_table%index_conn, n_me_in)
connection_table%index_conn = 0
call state_matrix_init (connection_table%state, n_counters=1)
call state_iterator_init (it, state_in)
do while (state_iterator_is_valid (it))
    qn = state_iterator_get_quantum_numbers (it)
    if (all (quantum_numbers_are_physical (qn, qn_mask))) then
        call quantum_numbers_undefine (qn, qn_mask_in)
        me_index_in = state_iterator_get_me_index (it)
        call state_matrix_add_state (connection_table%state, qn, &
            counter_index = 1, me_index = me_index_conn)
        call index_map_set_entry (connection_table%index_conn, &
            me_index_in, me_index_conn)
    end if
    call state_iterator_advance (it)
end do
n_me_conn = state_matrix_get_n_matrix_elements (connection_table%state)
connection_table%n_me_conn = n_me_conn
allocate (connection_table%entry (n_me_conn))
call state_iterator_init (it, connection_table%state)
do while (state_iterator_is_valid (it))
    i = state_iterator_get_me_index (it)
    me_count = state_iterator_get_me_count (it)
    call connection_entry_init (connection_table%entry(i), 1, 2, &
        state_iterator_get_quantum_numbers (it), me_count, (/n_tot/))
    call state_iterator_advance (it)
end do
end subroutine connection_table_init

subroutine connection_table_final (connection_table)
    type(connection_table_t), intent(inout) :: connection_table
    call state_matrix_final (connection_table%state)
end subroutine connection_table_final

subroutine connection_table_write (connection_table, unit)
    type(connection_table_t), intent(in) :: connection_table
    integer, intent(in), optional :: unit
    integer :: i, j
    integer :: u
    u = output_unit (unit)
    write (u, *) "Connection table:"
    call state_matrix_write (connection_table%state, unit)
    if (index_map_exists (connection_table%index_conn)) then
        write (u, *) " Index mapping input => connection table:"
        do i = 1, size (connection_table%index_conn)
            write (u, *) i, &
                index_map_get_entry (connection_table%index_conn, i)
        end do
    end if
end subroutine connection_table_write

```

```

        end do
    end if
    if (allocated (connection_table%entry)) then
        write (u, *) "  Connection table contents"
        do i = 1, size (connection_table%entry)
            call connection_entry_write (connection_table%entry(i), unit)
        end do
    end if
    if (index_map_exists (connection_table%index_result)) then
        write (u, *) "  Index mapping connection table => output"
        do i = 1, size (connection_table%index_result)
            write (u, *)  i, &
                index_map_get_entry (connection_table%index_result, i)
        end do
    end if
end subroutine connection_table_write

subroutine connection_table_fill (connection_table, state)
    type(connection_table_t), intent(inout) :: connection_table
    type(state_matrix_t), intent(in), target :: state
    integer :: index_in, index_conn, n_result_entries
    type(state_iterator_t) :: it
    integer :: k
    call state_iterator_init (it, state)
    do while (state_iterator_is_valid (it))
        index_in = state_iterator_get_me_index (it)
        index_conn = &
            index_map_get_entry (connection_table%index_conn, index_in)
        if (index_conn /= 0) then
            call connection_entry_add_state &
                (connection_table%entry(index_conn), &
                 index_in, &
                 state_iterator_get_quantum_numbers (it))
        end if
        call state_iterator_advance (it)
    end do
    n_result_entries = 0
    do k = 1, size (connection_table%entry)
        n_result_entries = &
            n_result_entries + connection_table%entry(k)%n_index(1) ** 2
    end do
    call index_map_init (connection_table%index_result, n_result_entries)
    connection_table%index_result = 0
end subroutine connection_table_fill

subroutine connection_entry_add_state (entry, index_in, qn_in)
    type(connection_entry_t), intent(inout) :: entry
    integer, intent(in) :: index_in
    type(quantum_numbers_t), dimension(:), intent(in) :: qn_in
    integer :: c
    entry%count = entry%count + 1
    c = entry%count(1)
    call index_map_set_entry (entry%index_in(1), c, index_in)
    entry%qn_in_list(1)%qn(:,c) = qn_in

```

```

end subroutine connection_entry_add_state

subroutine make_squared_interaction (int, &
    n_in, n_vir, n_out, n_tot, &
    connection_table, sum_colors, qn_mask)
    type(interaction_t), intent(out), target :: int
    integer, intent(in) :: n_in, n_vir, n_out, n_tot
    type(connection_table_t), intent(inout), target :: connection_table
    logical, intent(in) :: sum_colors
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
    type(connection_entry_t), pointer :: entry
    integer :: result_index, n_contrib
    integer :: i, m
    type(quantum_numbers_t), dimension(n_tot) :: qn
    call interaction_init (eval%int, n_in, n_vir, n_out, mask=qn_mask)
    m = 0
    do i = 1, connection_table%n_me_conn
        entry => connection_table%entry(i)
        qn = quantum_numbers_undefined (entry%qn_conn, qn_mask)
        if (.not. sum_colors) call quantum_numbers_invert_color (qn(1:n_in))
        call interaction_add_state (int, qn, me_index = result_index)
        n_contrib = entry%n_index(1) ** 2
        connection_table%index_result%entry(m+1:m+n_contrib) = result_index
        m = m + n_contrib
    end do
    call interaction_freeze (int)
end subroutine make_squared_interaction

subroutine make_pairing_array (pa, &
    n_matrix_elements, connection_table, sum_colors, color_table, &
    n_in, n_tot, nc)
    type(pairing_array_t), dimension(:), intent(out), allocatable :: pa
    integer, intent(in) :: n_matrix_elements
    type(connection_table_t), intent(in), target :: connection_table
    logical, intent(in) :: sum_colors
    type(color_table_t), intent(inout) :: color_table
    type(connection_entry_t), pointer :: entry
    integer, intent(in) :: n_in, n_tot
    integer, intent(in), optional :: nc
    integer, dimension(:), allocatable :: n_entries
    integer :: i, j, k, l, ks, ls, m, r
    integer :: color_multiplicity_in
    allocate (pa (n_matrix_elements))
    allocate (n_entries (n_matrix_elements))
    n_entries = 0
    do m = 1, size (connection_table%index_result)
        r = index_map_get_entry (connection_table%index_result, m)
        n_entries(r) = n_entries(r) + 1
    end do
    call pairing_array_init &
        (pa, n_entries, has_i2 = sum_colors, has_factor = sum_colors)
    m = 1
    n_entries = 0
    do i = 1, connection_table%n_me_conn

```

```

entry => connection_table%entry(i)
do k = 1, entry%n_index(1)
  if (sum_colors) then
    color_multiplicity_in = &
      product (abs (quantum_numbers_get_color_type &
        (entry%qn_in_list(1)%qn(:n_in, k))))
    do l = 1, entry%n_index(1)
      r = index_map_get_entry (connection_table%index_result, m)
      n_entries(r) = n_entries(r) + 1
      ks = index_map_get_entry (entry%index_in(1), k)
      ls = index_map_get_entry (entry%index_in(1), l)
      pa(r)%i1(n_entries(r)) = ks
      pa(r)%i2(n_entries(r)) = ls
      pa(r)%factor(n_entries(r)) = &
        color_table_get_color_factor (color_table, ks, ls, nc) &
        / color_multiplicity_in
      m = m + 1
    end do
  else
    r = index_map_get_entry (connection_table%index_result, m)
    n_entries(r) = n_entries(r) + 1
    ks = index_map_get_entry (entry%index_in(1), k)
    pa(r)%i1(n_entries(r)) = ks
    m = m + 1
  end if
end do
end do
end subroutine make_pairing_array

subroutine record_links (int, int_in, n_tot)
  type(interaction_t), intent(inout) :: int
  type(interaction_t), intent(in), target :: int_in
  integer, intent(in) :: n_tot
  integer, dimension(n_tot) :: map
  integer :: i
  do i = 1, n_tot
    call interaction_set_source_link (int, i, int_in, i)
  end do
  map = (/ (i, i = 1, n_tot) /)
  call interaction_transfer_relations (int_in, int, map)
end subroutine record_links

end subroutine evaluator_init_square_diag

```

Color-summed squared matrix (support nodiagonal helicities)

The initializer for an evaluator that squares a matrix element, including color factors. Unless requested otherwise by the quantum-number mask, the result contains off-diagonal matrix elements. (The input interaction must be diagonal since it represents an amplitude, not a density matrix.)

There is only one input interaction. The quantum-number mask is an array, one entry for each particle, so they can be treated individually. For academic

purposes, we allow for the number of colors being different from three (but 3 is the default).

The algorithm is analogous to the previous one, with some additional complications due to the necessity to loop over two helicity indices.

```

(Evaluators: public)+≡
    public :: evaluator_init_square_nondiag

(Evaluators: procedures)+≡
    subroutine evaluator_init_square_nondiag (eval, int_in, qn_mask, &
        col_flow_index, col_factor, col_index_hi, expand_color_flows, nc)

        type(evaluator_t), intent(out), target :: eval
        type(interaction_t), intent(in), target :: int_in
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
        integer, dimension(:,:), intent(in), optional :: col_flow_index
        complex(default), dimension(:), intent(in), optional :: col_factor
        integer, dimension(:), intent(in), optional :: col_index_hi
        logical, intent(in), optional :: expand_color_flows
        integer, intent(in), optional :: nc

        integer :: n_in, n_vir, n_out, n_tot
        integer :: n_me_in
        type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask_initial

        type :: connection_table_t
            integer :: n_tot = 0
            integer :: n_me_conn = 0
            type(state_matrix_t) :: state
            type(index_map2_t) :: index_conn
            type(connection_entry_t), dimension(:), allocatable :: entry
            type(index_map_t) :: index_result
        end type connection_table_t
        type(connection_table_t) :: connection_table

        logical :: sum_colors
        type(color_table_t) :: color_table

        if (present (expand_color_flows)) then
            sum_colors = .not. expand_color_flows
        else
            sum_colors = .true.
        end if

        if (sum_colors) then
            eval%type = EVAL_SQUARE_WITH_COLOR_FACTORS
        else
            eval%type = EVAL_SQUARED_FLOWS
        end if
        eval%int_in1 => int_in

        !    print *, "Interaction square with color factors (nondiag)"
        !    print *, "Input interaction"
        !    call interaction_write (int_in)
        n_in = interaction_get_n_in (int_in)

```

```

n_vir = interaction_get_n_vir (int_in)
n_out = interaction_get_n_out (int_in)
n_tot = interaction_get_n_tot (int_in)

allocate (qn_mask_initial (n_tot))
qn_mask_initial = interaction_get_mask (int_in)
call quantum_numbers_mask_set_color &
    (qn_mask_initial, sum_colors, mask_cg=.false.)
if (sum_colors) then
    call color_table_init &
        (color_table, interaction_get_state_matrix_ptr (int_in), n_tot)
    if (present (col_flow_index) .and. present (col_factor) &
        .and. present (col_index_hi)) then
        call color_table_set_color_factors &
            (color_table, col_flow_index, col_factor, col_index_hi)
    end if
!    call color_table_write (color_table)
end if

call connection_table_init (connection_table, &
    interaction_get_state_matrix_ptr (int_in), &
    qn_mask_initial, qn_mask, n_tot)
call connection_table_fill (connection_table, &
    interaction_get_state_matrix_ptr (int_in))
call make_squared_interaction (eval%int, &
    n_in, n_vir, n_out, n_tot, &
    connection_table, sum_colors, qn_mask_initial .or. qn_mask)
!    call connection_table_write (connection_table)
call make_pairing_array (eval%pairing_array, &
    interaction_get_n_matrix_elements (eval%int), &
    connection_table, sum_colors, color_table, n_in, n_tot, nc)
call record_links (eval%int, int_in, n_tot)
call connection_table_final (connection_table)

!    print *, "Result evaluator:"
!    call evaluator_write (eval)

contains

subroutine connection_table_init &
    (connection_table, state_in, qn_mask_in, qn_mask, n_tot)
type(connection_table_t), intent(out) :: connection_table
type(state_matrix_t), intent(in), target :: state_in
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
integer, intent(in) :: n_tot
type(quantum_numbers_t), dimension(n_tot) :: qn1, qn2, qn
type(state_iterator_t) :: it1, it2, it
integer :: i, n_me_in, me_index_in1, me_index_in2
integer :: me_index_conn, n_me_conn
integer, dimension(1) :: me_count
connection_table%n_tot = n_tot
n_me_in = state_matrix_get_n_matrix_elements (state_in)
call index_map2_init (connection_table%index_conn, n_me_in)

```

```

connection_table%index_conn = 0
call state_matrix_init (connection_table%state, n_counters=1)
call state_iterator_init (it1, state_in)
do while (state_iterator_is_valid (it1))
  qn1 = state_iterator_get_quantum_numbers (it1)
  me_index_in1 = state_iterator_get_me_index (it1)
  call state_iterator_init (it2, state_in)
  do while (state_iterator_is_valid (it2))
    qn2 = state_iterator_get_quantum_numbers (it2)
    if (all (quantum_numbers_are_compatible (qn1, qn2, qn_mask))) then
      qn = qn1 .merge. qn2
      call quantum_numbers_undefine (qn, qn_mask_in)
      me_index_in2 = state_iterator_get_me_index (it2)
      call state_matrix_add_state (connection_table%state, qn, &
        counter_index = 1, me_index = me_index_conn)
      call index_map2_set_entry (connection_table%index_conn, &
        me_index_in1, me_index_in2, me_index_conn)
    end if
    call state_iterator_advance (it2)
  end do
  call state_iterator_advance (it1)
end do
n_me_conn = state_matrix_get_n_matrix_elements (connection_table%state)
connection_table%n_me_conn = n_me_conn
allocate (connection_table%entry (n_me_conn))
call state_iterator_init (it, connection_table%state)
do while (state_iterator_is_valid (it))
  i = state_iterator_get_me_index (it)
  me_count = state_iterator_get_me_count (it)
  call connection_entry_init (connection_table%entry(i), 1, 2, &
    state_iterator_get_quantum_numbers (it), me_count, (/n_tot/))
  call state_iterator_advance (it)
end do
end subroutine connection_table_init

subroutine connection_table_final (connection_table)
  type(connection_table_t), intent(inout) :: connection_table
  call state_matrix_final (connection_table%state)
end subroutine connection_table_final

subroutine connection_table_write (connection_table, unit)
  type(connection_table_t), intent(in) :: connection_table
  integer, intent(in), optional :: unit
  integer :: i, j
  integer :: u
  u = output_unit (unit)
  write (u, *) "Connection table:"
  call state_matrix_write (connection_table%state, unit)
  if (index_map2_exists (connection_table%index_conn)) then
    write (u, *) "  Index mapping input => connection table:"
    do i = 1, size (connection_table%index_conn)
      do j = 1, size (connection_table%index_conn)
        write (u, *) i, j, &
          index_map2_get_entry (connection_table%index_conn, i, j)
      end do
    end do
  end if
end subroutine connection_table_write

```



```

        end do
    end do
end if
if (allocated (connection_table%entry)) then
    write (u, *) " Connection table contents"
    do i = 1, size (connection_table%entry)
        call connection_entry_write (connection_table%entry(i), unit)
    end do
end if
if (index_map_exists (connection_table%index_result)) then
    write (u, *) " Index mapping connection table => output"
    do i = 1, size (connection_table%index_result)
        write (u, *) i, &
            index_map_get_entry (connection_table%index_result, i)
    end do
end if
end subroutine connection_table_write

subroutine connection_table_fill (connection_table, state)
    type(connection_table_t), intent(inout), target :: connection_table
    type(state_matrix_t), intent(in), target :: state
    integer :: index1_in, index2_in, index_conn, n_result_entries
    type(state_iterator_t) :: it1, it2
    integer :: k
    call state_iterator_init (it1, state)
    do while (state_iterator_is_valid (it1))
        index1_in = state_iterator_get_me_index (it1)
        call state_iterator_init (it2, state)
        do while (state_iterator_is_valid (it2))
            index2_in = state_iterator_get_me_index (it2)
            index_conn = index_map2_get_entry &
                (connection_table%index_conn, index1_in, index2_in)
            if (index_conn /= 0) then
                call connection_entry_add_state &
                    (connection_table%entry(index_conn), &
                     index1_in, index2_in, &
                     state_iterator_get_quantum_numbers (it1) &
                     .merge. &
                     state_iterator_get_quantum_numbers (it2))
            end if
            call state_iterator_advance (it2)
        end do
        call state_iterator_advance (it1)
    end do
    n_result_entries = 0
    do k = 1, size (connection_table%entry)
        n_result_entries = &
            n_result_entries + connection_table%entry(k)%n_index(1)
    end do
    call index_map_init (connection_table%index_result, n_result_entries)
    connection_table%index_result = 0
end subroutine connection_table_fill

subroutine connection_entry_add_state (entry, index1_in, index2_in, qn_in)

```

```

type(connection_entry_t), intent(inout) :: entry
integer, intent(in) :: index1_in, index2_in
type(quantum_numbers_t), dimension(:), intent(in) :: qn_in
integer :: c
entry%count = entry%count + 1
c = entry%count(1)
call index_map_set_entry (entry%index_in(1), c, index1_in)
call index_map_set_entry (entry%index_in(2), c, index2_in)
entry%qn_in_list(1)%qn(:,c) = qn_in
end subroutine connection_entry_add_state

subroutine make_squared_interaction (int, &
    n_in, n_vir, n_out, n_tot, &
    connection_table, sum_colors, qn_mask)
type(interaction_t), intent(out), target :: int
integer, intent(in) :: n_in, n_vir, n_out, n_tot
type(connection_table_t), intent(inout), target :: connection_table
logical, intent(in) :: sum_colors
type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
type(connection_entry_t), pointer :: entry
integer :: result_index
integer :: i, k, m
type(quantum_numbers_t), dimension(n_tot) :: qn
call interaction_init (eval%int, n_in, n_vir, n_out, mask=qn_mask)
m = 0
do i = 1, connection_table%n_me_conn
    entry => connection_table%entry(i)
    do k = 1, size (entry%qn_in_list(1)%qn, 2)
        qn = quantum_numbers_undefined &
            (entry%qn_in_list(1)%qn(:,k), qn_mask)
        if (.not. sum_colors) &
            call quantum_numbers_invert_color (qn(1:n_in))
        call interaction_add_state (int, qn, me_index = result_index)
        call index_map_set_entry (connection_table%index_result, m + 1, &
            result_index)
        m = m + 1
    end do
end do
call interaction_freeze (int)
end subroutine make_squared_interaction

subroutine make_pairing_array (pa, &
    n_matrix_elements, connection_table, sum_colors, color_table, &
    n_in, n_tot, nc)
type(pairing_array_t), dimension(:), intent(out), allocatable :: pa
integer, intent(in) :: n_matrix_elements
type(connection_table_t), intent(in), target :: connection_table
logical, intent(in) :: sum_colors
type(color_table_t), intent(inout) :: color_table
type(connection_entry_t), pointer :: entry
integer, intent(in) :: n_in, n_tot
integer, intent(in), optional :: nc
integer, dimension(:), allocatable :: n_entries
integer :: i, k, k1s, k2s, m, r

```

```

integer :: color_multiplicity_in
allocate (pa (n_matrix_elements))
allocate (n_entries (n_matrix_elements))
n_entries = 0
do m = 1, size (connection_table%index_result)
    r = index_map_get_entry (connection_table%index_result, m)
    n_entries(r) = n_entries(r) + 1
end do
call pairing_array_init &
    (pa, n_entries, has_i2 = sum_colors, has_factor = sum_colors)
m = 1
n_entries = 0
do i = 1, connection_table%n_me_conn
    entry => connection_table%entry(i)
    do k = 1, entry%n_index(1)
        r = index_map_get_entry (connection_table%index_result, m)
        n_entries(r) = n_entries(r) + 1
        if (sum_colors) then
            k1s = index_map_get_entry (entry%index_in(1), k)
            k2s = index_map_get_entry (entry%index_in(2), k)
            pa(r)%i1(n_entries(r)) = k1s
            pa(r)%i2(n_entries(r)) = k2s
            color_multiplicity_in = &
                product (abs (quantum_numbers_get_color_type &
                    (entry%qn_in_list(1)%qn(:n_in, k))))
            pa(r)%factor(n_entries(r)) = &
                color_table_get_color_factor (color_table, k1s, k2s, nc) &
                / color_multiplicity_in
        else
            k1s = index_map_get_entry (entry%index_in(1), k)
            pa(r)%i1(n_entries(r)) = k1s
        end if
        m = m + 1
    end do
end do
end subroutine make_pairing_array

subroutine record_links (int, int_in, n_tot)
    type(interaction_t), intent(inout) :: int
    type(interaction_t), intent(in), target :: int_in
    integer, intent(in) :: n_tot
    integer, dimension(n_tot) :: map
    integer :: i
    do i = 1, n_tot
        call interaction_set_source_link (int, i, int_in, i)
    end do
    map = (/ (i, i = 1, n_tot) /)
    call interaction_transfer_relations (int_in, int, map)
end subroutine record_links

end subroutine evaluator_init_square_nondiag

```

Copy with additional contracted color states

This evaluator involves no square or multiplication, its matrix elements are just copies of the (single) input interaction. However, the state matrix of the interaction contains additional states that have color indices contracted. This is used for copies of the beam or structure-function interactions that need to match the hard interaction also in the case where its color indices coincide.

(Evaluators: public)+≡

```
public :: evaluator_init_color_contractions
```

(Evaluators: procedures)+≡

```
subroutine evaluator_init_color_contractions (eval, int_in)
  type(evaluator_t), intent(out), target :: eval
  type(interaction_t), intent(in), target :: int_in
  integer :: n_in, n_vir, n_out, n_tot
  type(state_matrix_t), pointer :: state_with_contractions => null ()
  integer, dimension(:), allocatable :: me_index
  integer, dimension(:), allocatable :: result_index
  eval%type = EVAL_COLOR_CONTRACTION
  eval%int_in1 => int_in
!   print *, "Interaction with additional color contractions"
!   print *, "Input interaction"
!   call interaction_write (int_in)
  n_in = interaction_get_n_in (int_in)
  n_vir = interaction_get_n_vir (int_in)
  n_out = interaction_get_n_out (int_in)
  n_tot = interaction_get_n_tot (int_in)
  state_with_contractions => interaction_get_state_matrix_ptr (int_in)
  call state_matrix_add_color_contractions (state_with_contractions)
  call make_contracted_interaction (eval%int, &
    me_index, result_index, &
    n_in, n_vir, n_out, n_tot, &
    state_with_contractions, interaction_get_mask (int_in))
  call make_pairing_array (eval%pairing_array, me_index, result_index)
  call record_links (eval%int, int_in, n_tot)
!   print *, "Result evaluator:"
!   call evaluator_write (eval)
```

contains

```
subroutine make_contracted_interaction (int, &
  me_index, result_index, &
  n_in, n_vir, n_out, n_tot, state, qn_mask)
  type(interaction_t), intent(out), target :: int
  integer, dimension(:), intent(out), allocatable :: me_index
  integer, dimension(:), intent(out), allocatable :: result_index
  integer, intent(in) :: n_in, n_vir, n_out, n_tot
  type(state_matrix_t), intent(in) :: state
  type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask
  type(state_iterator_t) :: it
  integer :: n_me, i
  type(quantum_numbers_t), dimension(n_tot) :: qn
  call interaction_init (int, n_in, n_vir, n_out, mask=qn_mask)
  n_me = state_matrix_get_n_leaves (state)
```

```

allocate (me_index (n_me))
allocate (result_index (n_me))
call state_iterator_init (it, state)
i = 0
do while (state_iterator_is_valid (it))
  i = i + 1
  me_index(i) = state_iterator_get_me_index (it)
  qn = state_iterator_get_quantum_numbers (it)
  call interaction_add_state (int, qn, me_index = result_index(i))
  call state_iterator_advance (it)
end do
call interaction_freeze (int)
end subroutine make_contracted_interaction

subroutine make_pairing_array (pa, me_index, result_index)
  type(pairing_array_t), dimension(:), intent(out), allocatable :: pa
  integer, dimension(:), intent(in) :: me_index, result_index
  integer, dimension(:), allocatable :: n_entries
  integer :: n_matrix_elements, r, i
  n_matrix_elements = size (me_index)
  allocate (pa (n_matrix_elements))
  allocate (n_entries (n_matrix_elements))
  n_entries = 1
  call pairing_array_init &
    (pa, n_entries, has_i2=.false., has_factor=.false.)
  do i = 1, n_matrix_elements
    r = result_index(i)
    pa(r)%i1(1) = me_index(i)
  end do
end subroutine make_pairing_array

subroutine record_links (int, int_in, n_tot)
  type(interaction_t), intent(inout) :: int
  type(interaction_t), intent(in), target :: int_in
  integer, intent(in) :: n_tot
  integer, dimension(n_tot) :: map
  integer :: i
  do i = 1, n_tot
    call interaction_set_source_link (int, i, int_in, i)
  end do
  map = (/ (i, i = 1, n_tot) /)
  call interaction_transfer_relations (int_in, int, map)
end subroutine record_links

end subroutine evaluator_init_color_contractions

```

Auxiliary procedure for initialization

This will become a standard procedure in F2008. The result is true if the number of true values in the mask is odd. We use the function for determining the ghost parity of a quantum-number array.

(Evaluators: procedures)+≡

```

function parity (mask)
  logical :: parity
  logical, dimension(:) :: mask
  integer :: i
  parity = .false.
  do i = 1, size (mask)
    if (mask(i)) parity = .not. parity
  end do
end function parity

```

7.7.6 Accessing contents

Return the interaction component, as a pointer to avoid any copying.

```

(Evaluators: public)+≡
  public :: evaluator_get_int_ptr

(Evaluators: procedures)+≡
  function evaluator_get_int_ptr (eval) result (int)
    type(interaction_t), pointer :: int
    type(evaluator_t), intent(in), target :: eval
    int => eval%int
  end function evaluator_get_int_ptr

```

7.7.7 Inherited procedures

Return true if the state matrix within the interaction is empty.

```

(Evaluators: public)+≡
  public :: evaluator_is_empty

(Evaluators: procedures)+≡
  function evaluator_is_empty (eval) result (flag)
    logical :: flag
    type(evaluator_t), intent(in) :: eval
    flag = interaction_is_empty (eval%int)
  end function evaluator_is_empty

```

Return the integer tag.

```

(Evaluators: public)+≡
  public :: evaluator_get_tag

(Evaluators: procedures)+≡
  function evaluator_get_tag (eval) result (tag)
    integer :: tag
    type(evaluator_t), intent(in) :: eval
    tag = interaction_get_tag (eval%int)
  end function evaluator_get_tag

```

Get the norm of the state matrix (if the norm has been taken out, otherwise this would be unity).

```

(Evaluators: public)+≡
  public :: evaluator_get_norm

```

```

(Evaluators: procedures)+≡
function evaluator_get_norm (eval) result (norm)
  real(default) :: norm
  type(evaluator_t), intent(in) :: eval
  norm = interaction_get_norm (eval%int)
end function evaluator_get_norm

```

Return the number of particles.

```

(Evaluators: public)+≡
public :: evaluator_get_n_tot
public :: evaluator_get_n_in
public :: evaluator_get_n_vir
public :: evaluator_get_n_out

(Evaluators: procedures)+≡
function evaluator_get_n_tot (eval) result (n_tot)
  integer :: n_tot
  type(evaluator_t), intent(in) :: eval
  n_tot = interaction_get_n_tot (eval%int)
end function evaluator_get_n_tot

function evaluator_get_n_in (eval) result (n_in)
  integer :: n_in
  type(evaluator_t), intent(in) :: eval
  n_in = interaction_get_n_in (eval%int)
end function evaluator_get_n_in

function evaluator_get_n_vir (eval) result (n_vir)
  integer :: n_vir
  type(evaluator_t), intent(in) :: eval
  n_vir = interaction_get_n_vir (eval%int)
end function evaluator_get_n_vir

function evaluator_get_n_out (eval) result (n_out)
  integer :: n_out
  type(evaluator_t), intent(in) :: eval
  n_out = interaction_get_n_out (eval%int)
end function evaluator_get_n_out

```

Sum all matrix element values.

```

(Evaluators: public)+≡
public :: evaluator_sum

(Evaluators: procedures)+≡
function evaluator_sum (eval) result (value)
  complex(default) :: value
  type(evaluator_t), intent(in) :: eval
  value = interaction_sum (eval%int)
end function evaluator_sum

```

Renormalize the state matrix by its trace, if nonzero. The renormalization is reflected in the state-matrix norm.

```

(Evaluators: public)+≡
public :: evaluator_normalize_by_trace

```

```

<Evaluators: procedures>+≡
  subroutine evaluator_normalize_by_trace (eval)
    type(evaluator_t), intent(inout) :: eval
    call interaction_normalize_by_trace (eval%int)
  end subroutine evaluator_normalize_by_trace

```

Analogous, but renormalize by maximal (absolute) value.

```

<Evaluators: public>+≡
  public :: evaluator_normalize_by_max

<Evaluators: procedures>+≡
  subroutine evaluator_normalize_by_max (eval)
    type(evaluator_t), intent(inout) :: eval
    call interaction_normalize_by_max (eval%int)
  end subroutine evaluator_normalize_by_max

```

Append color-contracted states. Matrix element array and multiplication table are unaffected by this.

```

<Evaluators: public>+≡
  public :: evaluator_add_color_contractions

<Evaluators: procedures>+≡
  subroutine evaluator_add_color_contractions (eval)
    type(evaluator_t), intent(inout) :: eval
    call interaction_add_color_contractions (eval%int)
  end subroutine evaluator_add_color_contractions

```

Return the quantum-numbers mask of the enclosed interaction.

```

<Evaluators: public>+≡
  public :: evaluator_get_mask

<Evaluators: procedures>+≡
  function evaluator_get_mask (eval) result (mask)
    type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
    type(evaluator_t), intent(in), target :: eval
    allocate (mask (interaction_get_n_tot (eval%int)))
    mask = interaction_get_mask (eval%int)
  end function evaluator_get_mask

```

Extend the linking of interactions to evaluators.

```

<Evaluators: public>+≡
  public :: interaction_set_source_link
  public :: evaluator_set_source_link

<Evaluators: interfaces>+≡
  interface interaction_set_source_link
    module procedure interaction_set_source_link_eval
  end interface
  interface evaluator_set_source_link
    module procedure evaluator_set_source_link_int
    module procedure evaluator_set_source_link_eval
  end interface

```



```

<Evaluators: procedures>+=
  subroutine interaction_set_source_link_eval (int, i, eval1, i1)
    type(interaction_t), intent(inout) :: int
    type(evaluator_t), intent(in), target :: eval1
    integer, intent(in) :: i, i1
    call interaction_set_source_link (int, i, eval1%int, i1)
  end subroutine interaction_set_source_link_eval

  subroutine evaluator_set_source_link_int (eval, i, int1, i1)
    type(evaluator_t), intent(inout) :: eval
    type(interaction_t), intent(in), target :: int1
    integer, intent(in) :: i, i1
    call interaction_set_source_link (eval%int, i, int1, i1)
  end subroutine evaluator_set_source_link_int

  subroutine evaluator_set_source_link_eval (eval, i, eval1, i1)
    type(evaluator_t), intent(inout) :: eval
    type(evaluator_t), intent(in), target :: eval1
    integer, intent(in) :: i, i1
    call interaction_set_source_link (eval%int, i, eval1%int, i1)
  end subroutine evaluator_set_source_link_eval

```

Send momenta to the linked interactions.

```

<Evaluators: public>+=
  public :: evaluator_receive_momenta

<Evaluators: procedures>+=
  subroutine evaluator_receive_momenta (eval)
    type(evaluator_t), intent(inout) :: eval
    call interaction_receive_momenta (eval%int)
  end subroutine evaluator_receive_momenta

```

Reassign external source links from one to another.

```

<Evaluators: public>+=
  public :: evaluator_reassign_links

<Evaluators: interfaces>+=
  interface evaluator_reassign_links
    module procedure evaluator_reassign_links_eval
    module procedure evaluator_reassign_links_int
  end interface

<Evaluators: procedures>+=
  subroutine evaluator_reassign_links_eval (eval, eval_src, eval_target)
    type(evaluator_t), intent(inout) :: eval
    type(evaluator_t), intent(in) :: eval_src
    type(evaluator_t), intent(in), target :: eval_target
    if (associated (eval%int_in1)) then
      if (interaction_get_tag (eval%int_in1) &
        == interaction_get_tag (eval_src%int)) then
        eval%int_in1 => eval_target%int
      end if
    end if
  end if

```

```

    if (associated (eval%int_in2)) then
      if (interaction_get_tag (eval%int_in2) &
         == interaction_get_tag (eval_src%int)) then
        eval%int_in2 => eval_target%int
      end if
    end if
    call interaction_reassign_links (eval%int, eval_src%int, eval_target%int)
  end subroutine evaluator_reassign_links_eval

subroutine evaluator_reassign_links_int (eval, int_src, int_target)
  type(evaluator_t), intent(inout) :: eval
  type(interaction_t), intent(in) :: int_src
  type(interaction_t), intent(in), target :: int_target
  if (associated (eval%int_in1)) then
    if (interaction_get_tag (eval%int_in1) &
       == interaction_get_tag (int_src)) then
      eval%int_in1 => int_target
    end if
  end if
  if (associated (eval%int_in2)) then
    if (interaction_get_tag (eval%int_in2) &
       == interaction_get_tag (int_src)) then
      eval%int_in2 => int_target
    end if
  end if
  call interaction_reassign_links (eval%int, int_src, int_target)
end subroutine evaluator_reassign_links_int

```

Return flavor, momentum, and position of the first unstable particle present in the interaction.

```

<Evaluators: public>+≡
  public :: evaluator_get_unstable_particle

<Evaluators: procedures>+≡
  subroutine evaluator_get_unstable_particle (eval, flv, p, i)
    type(evaluator_t), intent(in) :: eval
    type(flavor_t), intent(out) :: flv
    type(vector4_t), intent(out) :: p
    integer, intent(out) :: i
    call interaction_get_unstable_particle (eval%int, flv, p, i)
  end subroutine evaluator_get_unstable_particle

```

7.7.8 Deleting the evaluator

Only the interaction component needs finalization.

```

<Evaluators: public>+≡
  public :: evaluator_final

<Evaluators: procedures>+≡
  elemental subroutine evaluator_final (eval)
    type(evaluator_t), intent(inout) :: eval
    call interaction_final (eval%int)
  end subroutine evaluator_final

```

7.7.9 Evaluation

When the input interactions (which are pointed to in the pairings stored within the evaluator) are filled with values, we can activate the evaluator, i.e., calculate the result values which are stored in the interaction.

The evaluation of matrix elements can be done in parallel. A `forall` construct is not appropriate, however. We would need `do concurrent` here. Nevertheless, the evaluation functions are marked as `pure`.

(Evaluators: public) +=

```
public :: evaluator_evaluate
```

(Evaluators: procedures) +=

```
subroutine evaluator_evaluate (eval)
  type(evaluator_t), intent(inout), target :: eval
  integer :: i
  select case (eval%type)
  case (EVAL_PRODUCT)
    do i = 1, size(eval%pairing_array)
      call interaction_evaluate_product (eval%int, i, &
        eval%int_in1, eval%int_in2, &
        eval%pairing_array(i)%i1, eval%pairing_array(i)%i2)
    end do
  case (EVAL_SQUARE_WITH_COLOR_FACTORS)
    do i = 1, size(eval%pairing_array)
      call interaction_evaluate_product_cf (eval%int, i, &
        eval%int_in1, eval%int_in1, &
        eval%pairing_array(i)%i1, eval%pairing_array(i)%i2, &
        eval%pairing_array(i)%factor)
    end do
  case (EVAL_SQUARED_FLOWS)
    do i = 1, size(eval%pairing_array)
      call interaction_evaluate_square_c (eval%int, i, &
        eval%int_in1, &
        eval%pairing_array(i)%i1)
    end do
  case (EVAL_COLOR_CONTRACTION)
    do i = 1, size(eval%pairing_array)
      call interaction_evaluate_sum (eval%int, i, &
        eval%int_in1, &
        eval%pairing_array(i)%i1)
    end do
  end select
end subroutine evaluator_evaluate
```

7.7.10 Test

Test: Create two interactions. The interactions are twofold connected. The first connection has a helicity index that is kept, the second connection has a helicity index that is summed over. Concatenate the interactions in an evaluator,

which thus contains a result interaction. Fill the input interactions with values, activate the evaluator and print the result.

```

(Evaluators: public)+≡
    public :: evaluator_test

(Evaluators: procedures)+≡
    subroutine evaluator_test (mdl)
        type(model_t), intent(in), target :: mdl
        call evaluator_test1 (mdl)
    end subroutine evaluator_test

    subroutine evaluator_test1 (mdl)
        type(model_t), intent(in), target :: mdl
        type(interaction_t), target :: int_qqtt, int_tbw, int1, int2
        type(flavor_t), dimension(:), allocatable :: flv
        type(color_t), dimension(:), allocatable :: col
        type(helicity_t), dimension(:), allocatable :: hel
        type(quantum_numbers_t), dimension(:), allocatable :: qn
        integer :: f, c, h1, h2, h3
        type(vector4_t), dimension(4) :: p
        type(vector4_t), dimension(2) :: q
        type(quantum_numbers_mask_t) :: qn_mask_conn
        type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask2
        type(evaluator_t), target :: eval, eval2, eval3
        print *, "*** Evaluator for matrix product"
        print *, "*** Construct interaction for qq -> tt"
        call interaction_init (int_qqtt, 2, 0, 2, set_relations=.true.)
        allocate (flv (4), col (4), hel (4), qn (4))
        allocate (qn_mask2 (4))
        do c = 1, 2
            select case (c)
            case (1)
                call color_init_col_acl (col, (/ 1, 0, 1, 0 /), (/ 0, 2, 0, 2 /))
            case (2)
                call color_init_col_acl (col, (/ 1, 0, 2, 0 /), (/ 0, 1, 0, 2 /))
            end select
        end do
        do f = 1, 2
            call flavor_init (flv, (/f, -f, 6, -6/), mdl)
            do h1 = -1, 1, 2
                call helicity_init (hel(3), h1)
                do h2 = -1, 1, 2
                    call helicity_init (hel(4), h2)
                    call quantum_numbers_init (qn, flv, col, hel)
                    call interaction_add_state (int_qqtt, qn)
                end do
            end do
        end do
        call interaction_freeze (int_qqtt)
        deallocate (flv, col, hel, qn)
        print *, "*** Construct interaction for t -> bW"
        call interaction_init (int_tbw, 1, 0, 2, set_relations=.true.)
        allocate (flv (3), col (3), hel (3), qn (3))
        call flavor_init (flv, (/ 6, 5, 24 /), mdl)

```

```

call color_init_col_acl (col, (/ 1, 1, 0 /), (/ 0, 0, 0 /))
do h1 = -1, 1, 2
  call helicity_init (hel(1), h1)
  do h2 = -1, 1, 2
    call helicity_init (hel(2), h2)
    do h3 = -1, 1
      call helicity_init (hel(3), h3)
      call quantum_numbers_init (qn, flv, col, hel)
      call interaction_add_state (int_tbw, qn)
    end do
  end do
end do
call interaction_freeze (int_tbw)
deallocate (flv, col, hel, qn)
print *, "***   Link interactions"
call interaction_set_source_link (int_tbw, 1, int_qqtt, 3)
qn_mask_conn = new_quantum_numbers_mask (.false.,.false.,.true.)
print *, "***   Show input"
call interaction_write (int_qqtt)
print *
call interaction_write (int_tbw)
print *
print *, "***   Evaluate product"
call evaluator_init_product &
  (eval, int_qqtt, int_tbw, qn_mask_conn)
call evaluator_write (eval)

call interaction_init (int1, 2, 0, 2, set_relations=.true.)
call interaction_init (int2, 1, 0, 2, set_relations=.true.)
p(1) = vector4_moving (1000._default, 1000._default, 3)
p(2) = vector4_moving (200._default, 200._default, 2)
p(3) = vector4_moving (100._default, 200._default, 1)
p(4) = p(1) - p(2) - p(3)
call interaction_set_momenta (int1, p)
q(1) = vector4_moving (50._default,-50._default, 3)
q(2) = p(2) + p(4) - q(1)
call interaction_set_momenta (int2, q, outgoing=.true.)
call interaction_set_matrix_element &
  (int1, (/ (2._default, 0._default), (4._default, 1._default), (-3._default, 0._default) /))
call interaction_set_matrix_element &
  (int2, (/ (-3._default, 0._default), (0._default, 1._default), (1._default, 2._default) /))
call evaluator_receive_momenta (eval)
call evaluator_evaluate (eval)
call interaction_write (int1)
print *
call interaction_write (int2)
print *
call evaluator_write (eval)
print *
call interaction_final (int1)
call interaction_final (int2)
call evaluator_final (eval)

print *

```

```

print *, "*** Evaluator for matrix square"
allocate (flv(4), col(4), qn(4))
call interaction_init (int1, 2, 0, 2, set_relations=.true.)
call flavor_init (flv, (/1, -1, 21, 21/), mdl)
call color_init (col(1), (/1/))
call color_init (col(2), (/ -2/))
call color_init (col(3), (/2, -3/))
call color_init (col(4), (/3, -1/))
call quantum_numbers_init (qn, flv, col)
call interaction_add_state (int1, qn)
call color_init (col(3), (/3, -1/))
call color_init (col(4), (/2, -3/))
call quantum_numbers_init (qn, flv, col)
call interaction_add_state (int1, qn)
call color_init (col(3), (/2, -1/))
call color_init (col(4), .true.)
call quantum_numbers_init (qn, flv, col)
call interaction_add_state (int1, qn)
call interaction_freeze (int1)
! qn_mask2 = all false (default)
call evaluator_init_square (eval, int1, qn_mask2, nc=3)
call evaluator_init_square_nondiag (eval2, int1, qn_mask2)
qn_mask2 = new_quantum_numbers_mask (.false., .true., .true.)
call evaluator_init_square_diag (eval3, eval%int, qn_mask2)
call interaction_set_matrix_element &
    (int1, (/ (2._default, 0._default), (4._default, 1._default), (-3._default, 0._default) /))
call interaction_set_momenta (int1, p)
call interaction_write (int1)
print *
call evaluator_receive_momenta (eval)
call evaluator_evaluate (eval)
call evaluator_write (eval)
print *
call evaluator_receive_momenta (eval2)
call evaluator_evaluate (eval2)
call evaluator_write (eval2)
print *
call evaluator_receive_momenta (eval3)
call evaluator_evaluate (eval3)
call evaluator_write (eval3)
call interaction_final (int1)
call evaluator_final (eval)
call evaluator_final (eval2)
call evaluator_final (eval3)
end subroutine evaluator_test1

```

Chapter 8

Particles

In this chapter, we deal with particles which have well-defined quantum numbers. While within interactions, all correlations are manifest, a particle array is derived by selecting a particular quantum number set. This involves tracing over all other particles, as far as polarization is concerned. Thus, a particle has definite flavor, color, and a single-particle density matrix for polarization.

8.1 Polarization

Particle polarization is determined by a particular quantum state which has just helicity information. For defining polarizations, we adopt the phase convention for a spin-1/2 particle that

$$\rho = \frac{1}{2}(1 + \vec{\alpha} \cdot \vec{\sigma}) \quad (8.1)$$

with the polarization axis $\vec{\alpha}$. Using this, we define

1. Trivial polarization: $\vec{\alpha} = 0$. [This is unpolarized, but distinct from the particular undefined polarization matrix which has the same meaning.]
2. Circular polarization: $\vec{\alpha}$ points in $\pm z$ direction.
3. Transversal polarization: $\vec{\alpha}$ points orthogonal to the z direction, with a phase ϕ that is 0 for the x axis, and $\pi/2 = 90^\circ$ for the y axis. For antiparticles, the phase switches sign, corresponding to complex conjugation.
4. Axis polarization, where we explicitly give $\vec{\alpha}$.

For higher spin, we retain this definition, but apply it to the two components with maximum and minimum weight. For massless particles, this is sufficient. For massive particles, we add the possibilities:

5. Longitudinal polarization: Only the 0-component is set. This is possible only for bosons.
6. Diagonal polarization: Explicitly specify all components in the helicity basis.

Obviously, this does not exhaust the possible density matrices for higher spin, but it should cover all practical applications.

```

<polarizations.f90>≡
  <File header>

  module polarizations

    <Use kinds>
    <Use strings>
    use constants, only: imago !NODEP!
    <Use file utils>
    use lorentz !NODEP!
    use models
    use flavors
    use colors
    use helicities
    use quantum_numbers
    use state_matrices

    <Standard module head>

    <Polarizations: public>

    <Polarizations: types>

    <Polarizations: interfaces>

    contains

    <Polarizations: procedures>

  end module polarizations

```

8.1.1 The polarization type

This is not an extension, but rather a restriction of the quantum state. Flavor and color are ignored, there is just a one-particle helicity density matrix.

```

<Polarizations: public>≡
  public :: polarization_t

<Polarizations: types>≡
  type :: polarization_t
    logical :: polarized = .false.
    integer :: spin_type = 0
    integer :: multiplicity = 0
    type(state_matrix_t) :: state
  end type polarization_t

```

8.1.2 Basic initializer and finalizer

We need the particle flavor for determining the allowed helicity values. The density matrix is not set, but prepared to be filled later. This is private.


```

<Polarizations: procedures>≡
  elemental subroutine polarization_init (pol, flv)
    type(polarization_t), intent(out) :: pol
    type(flavor_t), intent(in) :: flv
    pol%spin_type = flavor_get_spin_type (flv)
    pol%multiplicity = flavor_get_multiplicity (flv)
    call state_matrix_init (pol%state, store_values = .true.)
  end subroutine polarization_init

```

The finalizer has to be public. The quantum state contains memory allocated to pointers.

```

<Polarizations: public>+≡
  public :: polarization_final

<Polarizations: procedures>+≡
  elemental subroutine polarization_final (pol)
    type(polarization_t), intent(inout) :: pol
    call state_matrix_final (pol%state)
  end subroutine polarization_final

```

8.1.3 I/O

```

<Polarizations: public>+≡
  public :: polarization_write

<Polarizations: procedures>+≡
  subroutine polarization_write (pol, unit)
    type(polarization_t), intent(in) :: pol
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write (u, "(1x,A,I1,A,I1,A)") &
      "Polarization: [spin_type = ", pol%spin_type, &
      ", mult = ", pol%multiplicity, "]"
    call state_matrix_write (pol%state, unit=unit)
  end subroutine polarization_write

```

Defined assignment: deep copy

```

<Polarizations: public>+≡
  public :: assignment(=)

<Polarizations: interfaces>≡
  interface assignment(=)
    module procedure polarization_assign
  end interface

```

```

<Polarizations: procedures>+≡
  subroutine polarization_assign (pol_out, pol_in)
    type(polarization_t), intent(out) :: pol_out
    type(polarization_t), intent(in) :: pol_in
    pol_out%polarized = pol_in%polarized
    pol_out%spin_type = pol_in%spin_type

```

```

    pol_out%multiplicity = pol_in%multiplicity
    pol_out%state = pol_in%state
end subroutine polarization_assign

```

Binary I/O.

```

<Polarizations: public>+≡
    public :: polarization_write_raw
    public :: polarization_read_raw

<Polarizations: procedures>+≡
    subroutine polarization_write_raw (pol, u)
        type(polarization_t), intent(in) :: pol
        integer, intent(in) :: u
        write (u) pol%polarized
        write (u) pol%spin_type
        write (u) pol%multiplicity
        call state_matrix_write_raw (pol%state, u)
    end subroutine polarization_write_raw

    subroutine polarization_read_raw (pol, u, iostat)
        type(polarization_t), intent(out) :: pol
        integer, intent(in) :: u
        integer, intent(out), optional :: iostat
        read (u, iostat=iostat) pol%polarized
        read (u, iostat=iostat) pol%spin_type
        read (u, iostat=iostat) pol%multiplicity
        call state_matrix_read_raw (pol%state, u, iostat=iostat)
    end subroutine polarization_read_raw

```

8.1.4 Accessing contents

Return true if the particle is polarized. This is the case if the first (and only) entry in the quantum state has undefined helicity.

```

<Polarizations: public>+≡
    public :: polarization_is_polarized

<Polarizations: procedures>+≡
    elemental function polarization_is_polarized (pol) result (polarized)
        logical :: polarized
        type(polarization_t), intent(in) :: pol
        polarized = pol%polarized
    end function polarization_is_polarized

```

Return true if the polarization is diagonal, i.e., all entries in the density matrix are diagonal.

```

<Polarizations: public>+≡
    public :: polarization_is_diagonal

<Polarizations: interfaces>+≡
    interface polarization_is_diagonal
        module procedure polarization_is_diagonal0
        module procedure polarization_is_diagonal1
    end interface

```

```
end interface
```

(Polarizations: procedures)+≡

```
function polarization_is_diagonal0 (pol) result (diagonal)
  logical :: diagonal
  type(polarization_t), intent(in) :: pol
  type(state_iterator_t) :: it
  diagonal = .true.
  call state_iterator_init (it, pol%state)
  do while (state_iterator_is_valid (it))
    diagonal = all (quantum_numbers_are_diagonal &
      (state_iterator_get_quantum_numbers (it)))
    if (.not. diagonal) exit
    call state_iterator_advance (it)
  end do
end function polarization_is_diagonal0

function polarization_is_diagonal1 (pol) result (diagonal)
  type(polarization_t), dimension(:), intent(in) :: pol
  logical, dimension(size(pol)) :: diagonal
  integer :: i
  do i = 1, size (pol)
    diagonal(i) = polarization_is_diagonal0 (pol(i))
  end do
end function polarization_is_diagonal1
```

8.1.5 Initialization from state matrix

Here, the state matrix is already known (but not necessarily normalized). The result will be either unpolarized, or a normalized spin density matrix.

(Polarizations: public)+≡

```
public :: polarization_init_state_matrix
```

(Polarizations: procedures)+≡

```
subroutine polarization_init_state_matrix (pol, state)
  type(polarization_t), intent(out) :: pol
  type(state_matrix_t), intent(in), target :: state
  type(state_iterator_t) :: it
  type(flavor_t) :: flv
  type(helicity_t) :: hel
  type(quantum_numbers_t), dimension(1) :: qn
  complex(default) :: value, t
  call state_iterator_init (it, state)
  flv = state_iterator_get_flavor (it, 1)
  hel = state_iterator_get_helicity (it, 1)
  if (helicity_is_defined (hel)) then
    call polarization_init (pol, flv)
    pol%polarized = .true.
    t = 0
  do while (state_iterator_is_valid (it))
    hel = state_iterator_get_helicity (it, 1)
    call quantum_numbers_init (qn(1), hel)
```

```

        value = state_iterator_get_matrix_element (it)
        call state_matrix_add_state (pol%state, qn, value=value)
        if (helicity_is_diagonal (hel)) t = t + value
        call state_iterator_advance (it)
    end do
    call state_matrix_freeze (pol%state)
    if (t /= 0) call state_matrix_renormalize (pol%state, 1._default / t)
else
    call polarization_init_unpolarized (pol, flv)
end if
end subroutine polarization_init_state_matrix

```

8.1.6 Specific initializers

Unpolarized particle, no helicity labels in the density matrix. The value is specified as $1/N$, where N is the multiplicity.

Exception: for left-handed or right-handed particles (neutrinos), polarization is always circular with fraction unity.

```

<Polarizations: public>+≡
    public :: polarization_init_unpolarized

<Polarizations: procedures>+≡
    subroutine polarization_init_unpolarized (pol, flv)
        type(polarization_t), intent(inout) :: pol
        type(flavor_t), intent(in) :: flv
        type(quantum_numbers_t), dimension(1) :: qn
        complex(default) :: value
        if (flavor_is_left_handed (flv)) then
            call polarization_init_circular (pol, flv, -1._default)
        else if (flavor_is_right_handed (flv)) then
            call polarization_init_circular (pol, flv, 1._default)
        else
            call polarization_init (pol, flv)
            value = 1._default / flavor_get_multiplicity (flv)
            call state_matrix_add_state (pol%state, qn)
            call state_matrix_freeze (pol%state)
            call state_matrix_set_matrix_element (pol%state, value)
        end if
    end subroutine polarization_init_unpolarized

```

Unpolarized particle, but explicit density matrix with helicity states allocated according to given flavor. Note that fermions have even spin type, bosons odd. The spin density matrix entries are scaled by **fraction**. This is used for initializing other polarizations:

$$\rho(f) = \frac{|f|}{N} \mathbf{1}.$$

```

<Polarizations: public>+≡
    public :: polarization_init_trivial

<Polarizations: procedures>+≡
    subroutine polarization_init_trivial (pol, flv, fraction)
        type(polarization_t), intent(out) :: pol

```

```

type(flavor_t), intent(in) :: flv
real(default), intent(in), optional :: fraction
type(helicity_t) :: hel
type(quantum_numbers_t), dimension(1) :: qn
integer :: h, hmax
logical :: fermion
complex(default) :: value
call polarization_init (pol, flv)
pol%polarized = .true.
if (present (fraction)) then
    value = fraction / pol%multiplicity
else
    value = 1._default / pol%multiplicity
end if
fermion = mod (pol%spin_type, 2) == 0
hmax = pol%spin_type / 2
select case (pol%multiplicity)
case (1)
    if (flavor_is_left_handed (flv)) then
        call helicity_init (hel, -hmax)
    else if (flavor_is_right_handed (flv)) then
        call helicity_init (hel, hmax)
    else
        call helicity_init (hel, 0)
    end if
    call quantum_numbers_init (qn(1), hel)
    call state_matrix_add_state (pol%state, qn)
case (2)
    do h = -hmax, hmax, 2*hmax
        call helicity_init (hel, h)
        call quantum_numbers_init (qn(1), hel)
        call state_matrix_add_state (pol%state, qn)
    end do
case default
    do h = -hmax, hmax
        if (fermion .and. h == 0) cycle
        call helicity_init (hel, h)
        call quantum_numbers_init (qn(1), hel)
        call state_matrix_add_state (pol%state, qn)
    end do
end select
call state_matrix_freeze (pol%state)
call state_matrix_set_matrix_element (pol%state, value)
end subroutine polarization_init_trivial

```

The following three modes are useful mainly for spin-1/2 particle and massless particles of any nonzero spin. Only the highest-weight components are filled.

Circular polarization: The density matrix of the two highest-weight states

is

$$\rho(f) = \frac{1 - |f|}{2} \mathbf{1} + |f| \times \begin{cases} \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix}, & f > 0; \\ \begin{pmatrix} 0 & 0 \\ 0 & 1 \end{pmatrix}, & f < 0, \end{cases}$$

If the polarization fraction $|f|$ is unity, we need only one entry in the density matrix.

```

(Polarizations: public)+≡
    public :: polarization_init_circular

(Polarizations: procedures)+≡
    subroutine polarization_init_circular (pol, flv, fraction)
        type(polarization_t), intent(out) :: pol
        type(flavor_t), intent(in) :: flv
        real(default), intent(in) :: fraction
        type(helicity_t), dimension(2) :: hel
        type(quantum_numbers_t), dimension(1) :: qn
        complex(default) :: value
        integer :: hmax
        call polarization_init (pol, flv)
        pol%polarized = .true.
        hmax = pol%spin_type / 2
        call helicity_init (hel(1), hmax)
        call helicity_init (hel(2), -hmax)
        if (abs (fraction) /= 1) then
            value = (1 + fraction) / 2
            call quantum_numbers_init (qn(1), hel(1))
            call state_matrix_add_state (pol%state, qn, value=value)
            value = (1 - fraction) / 2
            call quantum_numbers_init (qn(1), hel(2))
            call state_matrix_add_state (pol%state, qn, value=value)
        else
            value = abs (fraction)
            if (fraction > 0) then
                call quantum_numbers_init (qn(1), hel(1))
            else
                call quantum_numbers_init (qn(1), hel(2))
            end if
            call state_matrix_add_state (pol%state, qn, value=value)
        end if
        call state_matrix_freeze (pol%state)
    end subroutine polarization_init_circular

```

Transversal polarization is analogous to circular, but we get a density matrix

$$\rho(f, \phi) = \frac{1 - |f|}{2} \mathbf{1} + \frac{|f|}{2} \begin{pmatrix} 1 & e^{-i\phi} \\ e^{i\phi} & 1 \end{pmatrix}.$$

The phase is $\phi = 0$ for the x -axis, $\phi = 90^\circ$ for the y axis as polarization vector. For an antiparticle, the phase switches sign, and for $f < 0$, the off-diagonal elements switch sign.

```

(Polarizations: public)+≡
    public :: polarization_init_transversal

```

```

(Polarizations: procedures)+≡
subroutine polarization_init_transversal (pol, flv, phi, fraction)
  type(polarization_t), intent(inout) :: pol
  type(flavor_t), intent(in) :: flv
  real(default), intent(in) :: phi, fraction
  call polarization_init_axis &
    (pol, flv, fraction * (/ cos (phi), sin (phi), 0._default/))
end subroutine polarization_init_transversal

```

For axis polarization, we again set only the entries with maximum weight.

$$\rho(f, \phi) = \frac{1}{2} \begin{pmatrix} 1 + \alpha_3 & \alpha_1 - i\alpha_2 \\ \alpha_1 + i\alpha_2 & 1 - \alpha_3 \end{pmatrix}.$$

For an antiparticle, α_2 switches sign (complex conjugate).

```

(Polarizations: public)+≡
public :: polarization_init_axis

(Polarizations: procedures)+≡
subroutine polarization_init_axis (pol, flv, alpha)
  type(polarization_t), intent(out) :: pol
  type(flavor_t), intent(in) :: flv
  real(default), dimension(3), intent(in) :: alpha
  type(quantum_numbers_t), dimension(1) :: qn
  type(helicity_t), dimension(2,2) :: hel
  complex(default), dimension(2,2) :: value
  integer :: hmax
  call polarization_init (pol, flv)
  pol%polarized = .true.
  hmax = pol%spin_type / 2
  call helicity_init (hel(1,1), hmax, hmax)
  call helicity_init (hel(1,2), hmax, -hmax)
  call helicity_init (hel(2,1), -hmax, hmax)
  call helicity_init (hel(2,2), -hmax, -hmax)
  value(1,1) = (1 + alpha(3)) / 2
  value(2,2) = (1 - alpha(3)) / 2
  if (flavor_is_antiparticle (flv)) then
    value(1,2) = (alpha(1) + imago * alpha(2)) / 2
  else
    value(1,2) = (alpha(1) - imago * alpha(2)) / 2
  end if
  value(2,1) = conjg (value(1,2))
  if (value(1,1) /= 0) then
    call quantum_numbers_init (qn(1), hel(1,1))
    call state_matrix_add_state (pol%state, qn, value=value(1,1))
  end if
  if (value(2,2) /= 0) then
    call quantum_numbers_init (qn(1), hel(2,2))
    call state_matrix_add_state (pol%state, qn, value=value(2,2))
  end if
  if (value(1,2) /= 0) then
    call quantum_numbers_init (qn(1), hel(1,2))
    call state_matrix_add_state (pol%state, qn, value=value(1,2))
    call quantum_numbers_init (qn(1), hel(2,1))

```

```

        call state_matrix_add_state (pol%state, qn, value=value(2,1))
    end if
    call state_matrix_freeze (pol%state)
end subroutine polarization_init_axis

```

This version specifies the polarization axis in terms of r (polarization degree) and θ, ϕ (polar and azimuthal angles).

If one of the angles is a nonzero multiple of π , roundoff errors typically will result in tiny contributions to unwanted components. Therefore, include a catch for small numbers.

```

<Polarizations: public>+≡
    public :: polarization_init_angles

<Polarizations: procedures>+≡
    subroutine polarization_init_angles (pol, flv, r, theta, phi)
        type(polarization_t), intent(out) :: pol
        type(flavor_t), intent(in) :: flv
        real(default), intent(in) :: r, theta, phi
        real(default), dimension(3) :: alpha
        real(default), parameter :: eps = 10 * epsilon (1._default)
        alpha(1) = r * sin (theta) * cos (phi)
        alpha(2) = r * sin (theta) * sin (phi)
        alpha(3) = r * cos (theta)
        where (abs (alpha) < eps) alpha = 0
        call polarization_init_axis (pol, flv, alpha)
    end subroutine polarization_init_angles

```

Longitudinal polarization is defined only for massive bosons. Only the zero component is filled. Otherwise, unpolarized.

```

<Polarizations: public>+≡
    public :: polarization_init_longitudinal

<Polarizations: procedures>+≡
    subroutine polarization_init_longitudinal (pol, flv, fraction)
        type(polarization_t), intent(out) :: pol
        type(flavor_t), intent(in) :: flv
        real(default), intent(in) :: fraction
        integer :: spin_type, multiplicity
        type(helicity_t) :: hel
        type(quantum_numbers_t), dimension(1) :: qn
        complex(default) :: value
        integer :: n_values
        value = abs (fraction)
        spin_type = flavor_get_spin_type (flv)
        multiplicity = flavor_get_multiplicity (flv)
        if (mod (spin_type, 2) == 1 .and. multiplicity > 2) then
            if (fraction /= 1) then
                call polarization_init_trivial (pol, flv, 1 - fraction)
                n_values = state_matrix_get_n_matrix_elements (pol%state)
                call state_matrix_add_to_matrix_element &
                    (pol%state, n_values/2 + 1, value)
            else
                call polarization_init (pol, flv)
            end if
        end if
    end subroutine polarization_init_longitudinal

```



```

        pol%polarized = .true.
        call helicity_init (hel, 0)
        call quantum_numbers_init (qn(1), hel)
        call state_matrix_add_state (pol%state, qn)
        call state_matrix_freeze (pol%state)
        call state_matrix_set_matrix_element (pol%state, value)
    end if
else
    call polarization_init_unpolarized (pol, flv)
end if
end subroutine polarization_init_longitudinal

```

This is diagonal polarization: we specify all components explicitly. We use only the positive components. The sum is normalized to unity. We assume that the length of `alpha` is equal to the particle multiplicity.

```

(Polarizations: public)+≡
    public :: polarization_init_diagonal

(Polarizations: procedures)+≡
    subroutine polarization_init_diagonal (pol, flv, alpha)
        type(polarization_t), intent(inout) :: pol
        type(flavor_t), intent(in) :: flv
        real(default), dimension(:), intent(in) :: alpha
        type(helicity_t) :: hel
        type(quantum_numbers_t), dimension(1) :: qn
        logical, dimension(size(alpha)) :: mask
        real(default) :: norm
        complex(default), dimension(:), allocatable :: value
        logical :: fermion
        integer :: h, hmax, i
        mask = alpha > 0
        norm = sum (alpha, mask); if (norm == 0) norm = 1
        allocate (value (count (mask)))
        value = pack (alpha / norm, mask)
        call polarization_init (pol, flv)
        pol%polarized = .true.
        fermion = mod (pol%spin_type, 2) == 0
        hmax = pol%spin_type / 2
        i = 0
        select case (pol%multiplicity)
        case (1)
            if (flavor_is_left_handed (flv)) then
                call helicity_init (hel, -hmax)
            else if (flavor_is_right_handed (flv)) then
                call helicity_init (hel, hmax)
            else
                call helicity_init (hel, 0)
            end if
            call quantum_numbers_init (qn(1), hel)
            call state_matrix_add_state (pol%state, qn)
        case (2)
            do h = -hmax, hmax, 2*hmax
                i = i + 1
                if (mask(i)) then

```

```

        call helicity_init (hel, h)
        call quantum_numbers_init (qn(1), hel)
        call state_matrix_add_state (pol%state, qn)
    end if
end do
case default
do h = -hmax, hmax
    if (fermion .and. h == 0) cycle
    i = i + 1
    if (mask(i)) then
        call helicity_init (hel, h)
        call quantum_numbers_init (qn(1), hel)
        call state_matrix_add_state (pol%state, qn)
    end if
end do
end select
call state_matrix_freeze (pol%state)
call state_matrix_set_matrix_element (pol%state, value)
end subroutine polarization_init_diagonal

```

Generic polarization: we generate all possible density matrix entries, but the values are left zero.

<Polarizations: public>+≡

```
public :: polarization_init_generic
```

<Polarizations: procedures>+≡

```

subroutine polarization_init_generic (pol, flv)
    type(polarization_t), intent(out) :: pol
    type(flavor_t), intent(in) :: flv
    type(helicity_t) :: hel
    type(quantum_numbers_t), dimension(1) :: qn
    logical :: fermion
    integer :: hmax, h1, h2
    call polarization_init (pol, flv)
    pol%polarized = .true.
    fermion = mod (pol%spin_type, 2) == 0
    hmax = pol%spin_type / 2
    select case (pol%multiplicity)
    case (1)
        if (flavor_is_left_handed (flv)) then
            call helicity_init (hel, -hmax)
        else if (flavor_is_right_handed (flv)) then
            call helicity_init (hel, hmax)
        else
            call helicity_init (hel, 0)
        end if
        call quantum_numbers_init (qn(1), hel)
        call state_matrix_add_state (pol%state, qn)
    case (2)
        do h1 = -hmax, hmax, 2*hmax
            do h2 = -hmax, hmax, 2*hmax
                call helicity_init (hel, h1, h2)
                call quantum_numbers_init (qn(1), hel)
                call state_matrix_add_state (pol%state, qn)
            end do
        end do
    end select
end subroutine polarization_init_generic

```

```

        end do
    end do
case default
    do h1 = -hmax, hmax
        if (fermion .and. h1 == 0) cycle
        do h2 = -hmax, hmax
            if (fermion .and. h2 == 0) cycle
            call helicity_init (hel, h1, h2)
            call quantum_numbers_init (qn(1), hel)
            call state_matrix_add_state (pol%state, qn)
        end do
    end do
end select
call state_matrix_freeze (pol%state)
end subroutine polarization_init_generic

```

8.1.7 Operations

Combine polarization states by computing the outer product of the state matrices.

```

(Polarizations: public)+≡
    public :: combine_polarization_states

(Polarizations: procedures)+≡
    subroutine combine_polarization_states (pol, state)
        type(polarization_t), dimension(:), intent(in), target :: pol
        type(state_matrix_t), intent(out) :: state
        call outer_multiply (pol%state, state)
    end subroutine combine_polarization_states

```

Transform a polarization density matrix into a polarization vector. This is possible without information loss only for spin-1/2 and for massless particles. To get a unique answer in all cases, we consider only the components with highest weight. Obviously, this loses the longitudinal component of a massive vector, for instance.

This is the inverse operation of `polarization_init_axis` above, where the polarization fraction is set to unity.

```

(Polarizations: public)+≡
    public :: polarization_get_axis

(Polarizations: procedures)+≡
    function polarization_get_axis (pol) result (alpha)
        real(default), dimension(3) :: alpha
        type(polarization_t), intent(in), target :: pol
        type(state_iterator_t) :: it
        complex(default), dimension(2,2) :: value
        type(helicity_t), dimension(2,2) :: hel
        type(helicity_t), dimension(1) :: hel1
        integer :: hmax, i, j
        if (pol%polarized) then
            hmax = pol%spin_type / 2
            call helicity_init (hel(1,1), hmax, hmax)

```

```

call helicity_init (hel(1,2), hmax,-hmax)
call helicity_init (hel(2,1),-hmax, hmax)
call helicity_init (hel(2,2),-hmax,-hmax)
value = 0
call state_iterator_init (it, pol%state)
do while (state_iterator_is_valid (it))
  hel1 = state_iterator_get_helicity (it)
  SCAN_HEL: do i = 1, 2
    do j = 1, 2
      if (hel1(1) == hel(i,j)) then
        value(i,j) = state_iterator_get_matrix_element (it)
        exit SCAN_HEL
      end if
    end do
  end do SCAN_HEL
  call state_iterator_advance (it)
end do
alpha(1) = value(1,2) + value(2,1)
alpha(2) = imago * (value(1,2) - value(2,1))
alpha(3) = value(1,1) - value(2,2)
else
  alpha = 0
end if
end function polarization_get_axis

```

This function returns polarization degree and polar and azimuthal angles (θ, ϕ) of the polarization axis.

(Polarizations: public)+≡

public :: polarization_to_angles

(Polarizations: procedures)+≡

```

subroutine polarization_to_angles (pol, r, theta, phi)
  type(polarization_t), intent(in) :: pol
  real(default), intent(out) :: r, theta, phi
  real(default), dimension(3) :: alpha
  real(default) :: r12
  if (pol%polarized) then
    alpha = polarization_get_axis (pol)
    r = sqrt (sum (alpha**2))
    if (any (alpha /= 0)) then
      r12 = sqrt (alpha(1)**2 + alpha(2)**2)
      theta = atan2 (r12, alpha(3))
      if (any (alpha(1:2) /= 0)) then
        phi = atan2 (alpha(2), alpha(1))
      else
        phi = 0
      end if
    else
      theta = 0
    end if
  else
    r = 0
    theta = 0
    phi = 0
  end if
end subroutine polarization_to_angles

```

```

end if
end subroutine polarization_to_angles

```

8.1.8 Test

```

<Polarizations: public>+≡
public :: polarization_test

<Polarizations: procedures>+≡
subroutine polarization_test
  use os_interface, only: os_data_t
  type(os_data_t) :: os_data
  type(model_t), pointer :: model
  type(polarization_t) :: pol
  type(flavor_t) :: flv
  real(default), dimension(3) :: alpha
  real(default) :: r, theta, phi
  print *, "* Read model file"
  call syntax_model_file_init ()
  call model_list_read_model &
    (var_str("SM"), var_str("SM.mdl"), os_data, model)
  print *, "Unpolarized fermion"
  call flavor_init (flv, 1, model)
  call polarization_init_unpolarized (pol, flv)
  call polarization_write (pol)
  print *, "diagonal =", polarization_is_diagonal (pol)
  call polarization_final (pol)
  print *, "Unpolarized fermion"
  call polarization_init_circular (pol, flv, 0._default)
  call polarization_write (pol)
  call polarization_final (pol)
  print *, "Transversally polarized fermion, phi=0"
  call polarization_init_transversal (pol, flv, 0._default, 1._default)
  call polarization_write (pol)
  print *, "diagonal =", polarization_is_diagonal (pol)
  call polarization_final (pol)
  print *, "Transversally polarized fermion, phi=0.9, frac=0.8"
  call polarization_init_transversal (pol, flv, 0.9_default, 0.8_default)
  call polarization_write (pol)
  print *, "diagonal =", polarization_is_diagonal (pol)
  call polarization_final (pol)
  print *, "All polarization directions of a fermion"
  call polarization_init_generic (pol, flv)
  call polarization_write (pol)
  call polarization_final (pol)
  call flavor_init (flv, 21, model)
  print *, "Circularly polarized gluon, frac=0.3"
  call polarization_init_circular (pol, flv, 0.3_default)
  call polarization_write (pol)
  call polarization_final (pol)
  call flavor_init (flv, 23, model)
  print *, "Circularly polarized massive vector, frac=-0.7"
  call polarization_init_circular (pol, flv, -0.7_default)

```

```

call polarization_write (pol)
call polarization_final (pol)
print *, "Circularly polarized massive vector"
call polarization_init_circular (pol, flv, 1._default)
call polarization_write (pol)
call polarization_final (pol)
print *, "Longitudinally polarized massive vector, frac=0.4"
call polarization_init_longitudinal (pol, flv, 0.4_default)
call polarization_write (pol)
call polarization_final (pol)
print *, "Longitudinally polarized massive vector"
call polarization_init_longitudinal (pol, flv, 1._default)
call polarization_write (pol)
call polarization_final (pol)
print *, "Diagonally polarized massive vector"
call polarization_init_diagonal &
    (pol, flv, (/0._default, 1._default, 2._default/))
call polarization_write (pol)
call polarization_final (pol)
print *, "All polarization directions of a massive vector"
call polarization_init_generic (pol, flv)
call polarization_write (pol)
call polarization_final (pol)
call flavor_init (flv, 21, model)
print *, "Axis polarization (0.2, 0.4, 0.6)"
alpha = (/0.2_default, 0.4_default, 0.6_default/)
call polarization_init_axis (pol, flv, alpha)
call polarization_write (pol)
print *, "Recovered axis:"
alpha = polarization_get_axis (pol)
print *, "Angle polarization (0.5, 0.6, -1)"
r = 0.5_default
theta = 0.6_default
phi = -1._default
call polarization_init_angles (pol, flv, r, theta, phi)
call polarization_write (pol)
print *, "Recovered parameters (r, theta, phi):"
call polarization_to_angles (pol, r, theta, phi)
print *, r, theta, phi
call polarization_final (pol)
end subroutine polarization_test

```

8.2 Event formats

This section provides the interface to event formats for user-defined processes, specifically the Les Houches Accord format and the HEPEVT format.

```

(event_formats.f90)≡
  <File header>

  module event_formats

```

```

<Use kinds>
  use kinds, only: i32, i64 !NODEP!
  use constants, only: pb_per_fb !NODEP!
<Use file utils>
  use lorentz !NODEP!
  use subevents
  use flavors
  use colors
  use helicities
  use quantum_numbers
  use polarizations
  use stdhep_interface
  use diagnostics !NODEP!
<Use strings>

<Standard module head>

<Event formats: public>

<Event formats: parameters>

<Event formats: variables>

<Event formats: common blocks>

<Event formats: interfaces>

contains

<Event formats: procedures>

end module event_formats

```

8.2.1 Les Houches Event File: header/footer

These two routines write the header and footer for the Les Houches Event File format (LHEF).

The current version writes no information except for the generator name and version.

```

<Event formats: public>≡
  public :: les_houches_events_write_header
  public :: les_houches_events_write_footer

<Event formats: procedures>≡
  subroutine les_houches_events_write_header (unit)
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write (u, '(A)') '<LesHouchesEvents version="1.0">'
    write (u, '(A)') '<header>'
    write (u, '(A)') ' <generator_name>WHIZARD</generator_name>'
    write (u, '(A)') ' <generator_version>{Version}</generator_version>'
    write (u, '(A)') '</header>'
  end subroutine les_houches_events_write_header

```

```

subroutine les_houches_events_write_footer (unit)
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, '(A)') '</LesHouchesEvents>'
end subroutine les_houches_events_write_footer

```

8.2.2 The HEPRUP common block

This common block is filled once per run.

Run characteristics

The maximal number of different processes.

<Event formats: parameters>≡
 integer, parameter :: MAXPUP = 100

The beam PDG codes.

<Event formats: variables>≡
 integer, dimension(2) :: IDBMUP

The beam energies in GeV.

<Event formats: variables>+≡
 double precision, dimension(2) :: EBMUP

The PDF group and set for the two beams. (Undefined: use -1; LHAPDF: use group = 0).

<Event formats: variables>+≡
 integer, dimension(2) :: PDFGUP
 integer, dimension(2) :: PDFSUP

The (re)weighting model. 1: events are weighted, the shower generator (SHG) selects processes according to the maximum weight (in pb) and unweights events. 2: events are weighted, the SHG selects processes according to their cross section (in pb) and unweights events. 3: events are unweighted and simply run through the SHG. 4: events are weighted, and the SHG keeps the weight. Negative numbers: negative weights are allowed (and are reweighted to ± 1 by the SHG, if allowed).

WHIZARD only supports modes 3 and 4, as the SHG is not given control over process selection. This is consistent with writing events to file, for offline showering.

<Event formats: variables>+≡
 integer :: IDWTUP

The number of different processes.

<Event formats: variables>+≡
 integer :: NPRUP

Process characteristics

Cross section and error in pb. (Cross section is needed only for IDWTUP = 2, so here both values are given for informational purposes only.)

```
<Event formats: variables>+≡  
    double precision, dimension(MAXPUP) :: XSECUP  
    double precision, dimension(MAXPUP) :: XERRUP
```

Maximum weight, i.e., the maximum value that XWGTUP can take. Also unused for the supported weighting models. It is ± 1 for unweighted events.

```
<Event formats: variables>+≡  
    double precision, dimension(MAXPUP) :: XMAXUP
```

Internal ID of the selected process, matches IDPRUP below.

```
<Event formats: variables>+≡  
    integer, dimension(MAXPUP) :: LPRUP
```

The common block

```
<Event formats: common blocks>≡  
    common /HEPRUP/ &  
        IDBMUP, EBMUP, PDFGUP, PDFSUP, IDWTUP, NPRUP, &  
        XSECUP, XERRUP, XMAXUP, LPRUP  
    save /HEPRUP/
```

Fill the run characteristics of the common block. The initialization sets the beam properties, number of processes, and weighting model.

```
<Event formats: public>+≡  
    public :: heprup_init  
  
<Event formats: procedures>+≡  
    subroutine heprup_init &  
        (beam_pdg, beam_energy, n_processes, unweighted, negative_weights)  
        integer, dimension(2), intent(in) :: beam_pdg  
        real(default), dimension(2), intent(in) :: beam_energy  
        integer, intent(in) :: n_processes  
        logical, intent(in) :: unweighted  
        logical, intent(in) :: negative_weights  
        IDBMUP = beam_pdg  
        EBMUP = beam_energy  
        PDFGUP = -1  
        PDFSUP = -1  
        if (unweighted) then  
            IDWTUP = 3  
        else  
            IDWTUP = 4  
        end if  
        if (negative_weights) IDWTUP = - IDWTUP  
        NPRUP = n_processes  
    end subroutine heprup_init
```

Specify PDF set info. Since we support only LHAPDF, the group entry is zero.

```
<Event formats: public>+≡  
    public :: heprup_set_lhapdf_id
```

```

(Event formats: procedures)+≡
  subroutine heprup_set_lhapdf_id (i_beam, pdf_id)
    integer, intent(in) :: i_beam, pdf_id
    PDFGUP(i_beam) = 0
    PDFSUP(i_beam) = pdf_id
  end subroutine heprup_set_lhapdf_id

```

Fill the characteristics for a particular process. Only the process ID is mandatory. Note that WHIZARD computes cross sections in fb, so we have to rescale to pb. The maximum weight is meaningless for unweighted events.

```

(Event formats: public)+≡
  public :: heprup_set_process_parameters

(Event formats: procedures)+≡
  subroutine heprup_set_process_parameters &
    (i, process_id, cross_section, error, max_weight)
    integer, intent(in) :: i, process_id
    real(default), intent(in), optional :: cross_section, error, max_weight
    LPRUP(i) = process_id
    if (present (cross_section)) then
      XSECUP(i) = cross_section * pb_per_fb
    else
      XSECUP(i) = 0
    end if
    if (present (error)) then
      XERRUP(i) = error * pb_per_fb
    else
      XERRUP(i) = 0
    end if
    select case (IDWTUP)
    case (3); XMAXUP(i) = 1
    case (4)
      if (present (max_weight)) then
        XMAXUP(i) = max_weight * pb_per_fb
      else
        XMAXUP(i) = 0
      end if
    end select
  end subroutine heprup_set_process_parameters

```

8.2.3 Run parameter output (verbose)

This is a verbose output of the HEPRUP block.

```

(Event formats: public)+≡
  public :: heprup_write_verbose

(Event formats: procedures)+≡
  subroutine heprup_write_verbose (unit)
    integer, intent(in), optional :: unit
    integer :: u, i
    u = output_unit (unit); if (u < 0) return
    write (u, "(A)") "HEPRUP Common Block"
  end subroutine heprup_write_verbose

```

```

write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "IDBMUP", IDBMUP, &
"PDG code of beams"
write (u, "(3x,A6,' = ',G12.5,1x,G12.5,8x,A)") "EBMUP ", EBMUP, &
"Energy of beams in GeV"
write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "PDFGUP", PDFGUP, &
"PDF author group [-1 = undefined]"
write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "PDFSUP", PDFSUP, &
"PDF set ID      [-1 = undefined]"
write (u, "(3x,A6,' = ',I9,3x,1x,9x,3x,8x,A)") "IDWTUP", IDWTUP, &
"LHA code for event weight mode"
write (u, "(3x,A6,' = ',I9,3x,1x,9x,3x,8x,A)") "NPRUP ", NPRUP, &
"Number of user subprocesses"
do i = 1, NPRUP
  write (u, "(1x,A,I0)") "Subprocess #", i
  write (u, "(3x,A6,' = ',F12.5,1x,12x,8x,A)") "XSECUP", XSECUP(i), &
"Cross section in pb"
  write (u, "(3x,A6,' = ',F12.5,1x,12x,8x,A)") "XERRUP", XERRUP(i), &
"Cross section error in pb"
  write (u, "(3x,A6,' = ',F12.5,1x,12x,8x,A)") "XMAXUP", XMAXUP(i), &
"Maximum event weight (cf. IDWTUP)"
  write (u, "(3x,A6,' = ',I9,3x,1x,12x,8x,A)") "LPRUP ", LPRUP(i), &
"Subprocess ID"
end do
end subroutine heprup_write_verbose

```

8.2.4 Run parameter output (other formats)

This routine writes the initialization block according to the LHEF standard. It uses the current contents of the HEPRUP block.

```

<Event formats: public>+≡
  public :: heprup_write_lhef

<Event formats: procedures>+≡
  subroutine heprup_write_lhef (unit)
    integer, intent(in), optional :: unit
    integer :: u, i
    u = output_unit (unit); if (u < 0) return
    write (u, '(A)') "<init>"
    write (u, *) IDBMUP, EBMUP, PDFGUP, PDFSUP, IDWTUP, NPRUP
    do i = 1, NPRUP
      write (u, *) XSECUP(i), XERRUP(i), XMAXUP(i), LPRUP(i)
    end do
    write (u, '(A)') "</init>"
  end subroutine heprup_write_lhef

```

8.2.5 The HEPEUP And HEPEVT common block

These common blocks are filled once per event.

Event characteristics

The maximal number of particles in an event record.

$\langle \text{Event formats: parameters} \rangle + \equiv$
`integer, parameter :: MAXNUP = 500`

The number of particles in this event.

$\langle \text{Event formats: variables} \rangle + \equiv$
`integer :: NUP`

The process ID for this event.

$\langle \text{Event formats: variables} \rangle + \equiv$
`integer :: IDPRUP`

The weight of this event (± 1 for unweighted events).

$\langle \text{Event formats: variables} \rangle + \equiv$
`double precision :: XWGTUP`

The factorization scale that is used for PDF calculation (-1 if undefined).

$\langle \text{Event formats: variables} \rangle + \equiv$
`double precision :: SCALUP`

The QED and QCD couplings α used for this event (-1 if undefined).

$\langle \text{Event formats: variables} \rangle + \equiv$
`double precision :: AQEDUP`
`double precision :: AQCDUP`

Particle characteristics

The PDG code:

$\langle \text{Event formats: variables} \rangle + \equiv$
`integer, dimension(MAXNUP) :: IDUP`

The status code. Incoming: -1 , outgoing: $+1$. Intermediate t-channel propagator: -2 (currently not used by WHIZARD). Intermediate resonance whose mass should be preserved: 2 . Intermediate resonance for documentation: 3 (currently not used). Beam particles: -9 .

$\langle \text{Event formats: variables} \rangle + \equiv$
`integer, dimension(MAXNUP) :: ISTUP`

Index of first and last mother.

$\langle \text{Event formats: variables} \rangle + \equiv$
`integer, dimension(2,MAXNUP) :: MOTHUP`

Color line index of the color and anticolor entry for the particle. The standard recommends using large numbers; we start from MAXNUP+1.

$\langle \text{Event formats: variables} \rangle + \equiv$
`integer, dimension(2,MAXNUP) :: ICOLUP`

Momentum, energy, and invariant mass: (p_x, p_y, p_z, E, M) . For space-like particles, M is the negative square root of the absolute value of the invariant mass.

$\langle \text{Event formats: variables} \rangle + \equiv$
`double precision, dimension(5,MAXNUP) :: PUP`

Invariant lifetime (distance) from production to decay in mm.

$\langle \text{Event formats: variables} \rangle + \equiv$
`double precision, dimension(MAXNUP) :: VTIMUP`

Cosine of the angle between the spin-vector and a particle and the 3-momentum of its mother, given in the lab frame. If undefined/unpolarized: 9.

```
<Event formats: variables>+≡
  double precision, dimension(MAXNUP) :: SPINUP
```

The common blocks

```
<Event formats: common blocks>+≡
  common /HEPEUP/ &
    NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP, &
    IDUP, ISTUP, MOTHUP, ICOLUP, PUP, VTIMUP, SPINUP
  save /HEPEUP/
```

Fill the event characteristics of the common block. The initialization sets only the number of particles and initializes the rest with default values. The other routine sets the optional parameters.

```
<Event formats: public>+≡
  public :: hepeup_init
  public :: hepeup_set_event_parameters

<Event formats: procedures>+≡
  subroutine hepeup_init (n_tot)
    integer, intent(in) :: n_tot
    NUP = n_tot
    IDPRUP = 0
    XWGTUP = 1
    SCALUP = -1
    AQEDUP = -1
    AQCDUP = -1
  end subroutine hepeup_init

  subroutine hepeup_set_event_parameters &
    (proc_id, weight, scale, alpha_qed, alpha_qcd)
    integer, intent(in), optional :: proc_id
    real(default), intent(in), optional :: weight, scale, alpha_qed, alpha_qcd
    if (present (proc_id)) IDPRUP = proc_id
    if (present (weight)) XWGTUP = weight
    if (present (scale)) SCALUP = scale
    if (present (alpha_qed)) AQEDUP = alpha_qed
    if (present (alpha_qcd)) AQCDUP = alpha_qcd
  end subroutine hepeup_set_event_parameters
```

Below we need the particle status codes which are actually defined in the `subevents` module.

Set the entry for a specific particle. All parameters are set with the exception of lifetime and spin, where default values are stored.

```
<Event formats: public>+≡
  public :: hepeup_set_particle

<Event formats: procedures>+≡
  subroutine hepeup_set_particle (i, pdg, status, parent, col, p, m2)
    integer, intent(in) :: i
    integer, intent(in) :: pdg, status
```

```

integer, dimension(:), intent(in) :: parent
type(vector4_t), intent(in) :: p
integer, dimension(2), intent(in) :: col
real(default), intent(in) :: m2
if (i > MAXNUP) then
    call msg_error (arr=(/ &
var_str ("Too many particles in HEPEUP common block. If this happened "), &
var_str ("during event output, your events will be invalid; please consider "), &
var_str ("switching to a modern event format like HEPMC. If you are not "), &
var_str ("using an old, HEPEUP based format and nevertheless get this error,"), &
var_str ("please notify the WHIZARD developers,") &
/))
    return
end if
IDUP(i) = pdg
select case (status)
case (PRT_BEAM);          ISTUP(i) = -9
case (PRT_INCOMING);      ISTUP(i) = -1
case (PRT_BEAM_REMNANT);  ISTUP(i) = 3
case (PRT_OUTGOING);      ISTUP(i) = 1
case (PRT_RESONANT);      ISTUP(i) = 2
case (PRT_VIRTUAL);       ISTUP(i) = 3
case default;             ISTUP(i) = 0
end select
select case (size (parent))
case (0);      MOTHUP(:,i) = 0
case (1);      MOTHUP(1,i) = parent(1); MOTHUP(2,i) = 0
case default;  MOTHUP(:,i) = (/ parent(1), parent(size (parent)) /)
end select
if (col(1) > 0) then
    ICOLUP(1,i) = 500 + col(1)
else
    ICOLUP(1,i) = 0
end if
if (col(2) > 0) then
    ICOLUP(2,i) = 500 + col(2)
else
    ICOLUP(2,i) = 0
end if
PUP(1:3,i) = vector3_get_components (space_part (p))
PUP(4,i) = energy (p)
PUP(5,i) = sign (sqrt (abs (m2)), m2)
VTIMUP(i) = 0
SPINUP(i) = 9
end subroutine hepeup_set_particle

```

Set the lifetime, actually $c\tau$ measured in mm, where τ is the invariant lifetime.

```

<Event formats: public>+≡
public :: hepeup_set_particle_lifetime

<Event formats: procedures>+≡
subroutine hepeup_set_particle_lifetime (i, lifetime)
integer, intent(in) :: i
real(default), intent(in) :: lifetime

```

```

      VTIMUP(i) = lifetime
    end subroutine hepeup_set_particle_lifetime

```

Set the particle spin entry. We need the cosine of the angle of the spin axis with respect to the three-momentum of the parent particle.

If the particle has a full polarization density matrix given, we need the particle momentum and polarization as well as the mother-particle momentum. The polarization is transformed into a spin vector (which is sensible only for spin-1/2 or massless particles), which then is transformed into the lab frame (by a rotation of the 3-axis to the particle momentum axis). Finally, we compute the scalar product of this vector with the mother-particle three-momentum.

This puts severe restrictions on the applicability of this definition, and Lorentz invariance is lost. Unfortunately, the Les Houches Accord requires this computation.

```

<Event formats: public>+≡
  public :: hepeup_set_particle_spin

<Event formats: interfaces>≡
  interface hepeup_set_particle_spin
    module procedure hepeup_set_particle_spin_pol
  end interface

<Event formats: procedures>+≡
  subroutine hepeup_set_particle_spin_pol (i, p, pol, p_mother)
    integer, intent(in) :: i
    type(vector4_t), intent(in) :: p
    type(polarization_t), intent(in) :: pol
    type(vector4_t), intent(in) :: p_mother
    type(vector3_t) :: s3, p3
    type(vector4_t) :: s4
    s3 = vector3_moving (polarization_get_axis (pol))
    p3 = space_part (p)
    s4 = rotation_to_2nd (3, p3) * vector4_moving (0._default, s3)
    SPINUP(i) = enclosed_angle_ct (s4, p_mother)
  end subroutine hepeup_set_particle_spin_pol

```

The HEPEVT common block

For the LEP Monte Carlos, a standard common block has been proposed in AKV89. We strongly recommend its use. (The description is an abbreviated transcription of AKV89, Vol. 3, pp. 327-330).

NMXHEP is the maximum number of entries:

```

<Event formats: variables>+≡
  integer, parameter :: NMXHEP = 4000

```

NEVHEP is normally the event number, but may take special values as follows:

0 the program does not keep track of event numbers. -1 a special initialization record. -2 a special final record.

```

<Event formats: variables>+≡
  integer :: NEVHEP

```

NHEP holds the number of entries for this event.

(Event formats: variables)+≡
integer :: NHEP

The entry ISTHEP(N) gives the status code for the Nth entry, with the following semantics: 0 a null entry. 1 an existing entry, which has not decayed or fragmented. 2 a decayed or fragmented entry, which is retained for event history information. 3 documentation line. 4- 10 reserved for future standards. 11-200 at the disposal of each model builder. 201- at the disposal of users.

(Event formats: variables)+≡
integer, dimension(NMXHEP) :: ISTHEP

The Particle Data Group has proposed standard particle codes, which are to be stored in IDHEP(N).

(Event formats: variables)+≡
integer, dimension(NMXHEP) :: IDHEP

JMOHEP(1,N) points to the mother of the Nth entry, if any. It is set to zero for initial entries. JMOHEP(2,N) points to the second mother, if any.

(Event formats: variables)+≡
integer, dimension(2, NMXHEP) :: JMOHEP

JDAHEP(1,N) and JDAHEP(2,N) point to the first and last daughter of the Nth entry, if any. These are zero for entries which have not yet decayed. The other daughters are stored in between these two.

(Event formats: variables)+≡
integer, dimension(2, NMXHEP) :: JDAHEP

In PHEP we store the momentum of the particle, more specifically this means that PHEP(1,N), PHEP(2,N), and PHEP(3,N) contain the momentum in the x , y , and z direction (as defined by the machine people), measured in GeV/c. PHEP(4,N) contains the energy in GeV and PHEP(5,N) the mass in GeV/ c^2 . The latter may be negative for spacelike partons.

(Event formats: variables)+≡
double precision, dimension(5, NMXHEP) :: PHEP

Finally VHEP is the place to store the position of the production vertex. VHEP(1,N), VHEP(2,N), and VHEP(3,N) contain the x , y , and z coordinate (as defined by the machine people), measured in mm. VHEP(4,N) contains the production time in mm/c.

(Event formats: variables)+≡
double precision, dimension(4, NMXHEP) :: VHEP

As an amendment to the proposed standard common block HEPEVT, we also have a polarisation common block HEPSPN, as described in AKV89. SHEP(1,N), SHEP(2,N), and SHEP(3,N) give the x , y , and z component of the spinvector s of a fermion in the fermions restframe.

Furthermore, we add the polarization of the corresponding outgoing particles:

```
<Event formats: variables>+≡
  integer, dimension(NMXHEP) :: hepevt_pol
```

By convention, SHEP(4,N) is always 1. All this is taken from StdHep 4.06 manual and written using Fortran90 conventions.

```
<Event formats: common blocks>+≡
  common /HEPEVT/ &
    NEVHEP, NHEP, ISTHEP, IDHEP, &
    JMOHEP, JDAHEP, PHEP, VHEP
  save /HEPEVT/
```

Here we store HEPEVT parameters of the WHIZARD 1 realization which are not part of the HEPEVT common block.

```
<Event formats: variables>+≡
  integer :: hepevt_n_out, hepevt_n_remnants

<Event formats: variables>+≡
  double precision :: hepevt_weight, hepevt_function_value
  double precision :: hepevt_function_ratio
```

Filling HEPEVT: If the event count is not provided, set NEVHEP to zero. If the event count is -1 or -2, the record corresponds to initialization and finalization, and the event is irrelevant.

Note that the event count may be larger than 2^{31} (2 GEvents). In that case, cut off the upper bits since NEVHEP is probably limited to default integer.

```
<Event formats: public>+≡
  public :: hepevt_init
  public :: hepevt_set_event_parameters

<Event formats: procedures>+≡
  subroutine hepevt_init (n_tot, n_out)
    integer, intent(in) :: n_tot, n_out
    NHEP = n_tot
    NEVHEP = 0
    hepevt_n_out = n_out
    hepevt_n_remnants = 0
    hepevt_weight = 1
    hepevt_function_value = 0
    hepevt_function_ratio = 1
  end subroutine hepevt_init

  subroutine hepevt_set_event_parameters &
    (weight, function_value, function_ratio, i_evt)
    integer, intent(in), optional :: i_evt
    real(default), intent(in), optional :: weight, function_value, &
      function_ratio
    integer(i32), parameter :: huge32 = huge (0_i32)
    if (present (i_evt)) NEVHEP = i_evt
    if (present (weight)) hepevt_weight = weight
```

```

    if (present (function_value)) hepevt_function_value = &
        function_value
    if (present (function_ratio)) hepevt_function_ratio = &
        function_ratio
end subroutine hepevt_set_event_parameters

```

Set the entry for a specific particle. All parameters are set with the exception of lifetime and spin, where default values are stored.

```

<Event formats: public>+≡
    public :: hepevt_set_particle

<Event formats: procedures>+≡
    subroutine hepevt_set_particle (i, pdg, status, parent, child, p, m2, hel)
        integer, intent(in) :: i
        integer, intent(in) :: pdg, status
        integer, dimension(:), intent(in) :: parent
        integer, dimension(:), intent(in) :: child
        type(vector4_t), intent(in) :: p
        real(default), intent(in) :: m2
        integer, intent(in) :: hel
        IDHEP(i) = pdg
        select case (status)
            case (PRT_BEAM);      ISTHEP(i) = 2
            case (PRT_INCOMING);  ISTHEP(i) = 2
            case (PRT_OUTGOING);  ISTHEP(i) = 1
            case (PRT_VIRTUAL);   ISTHEP(i) = 2
            case (PRT_RESONANT);  ISTHEP(i) = 2
            case default;         ISTHEP(i) = 0
        end select
        select case (size (parent))
            case (0);      JMOHEP(:,i) = 0
            case (1);      JMOHEP(1,i) = parent(1); JMOHEP(2,i) = 0
            case default;  JMOHEP(:,i) = (/ parent(1), parent(size (parent)) /)
        end select
        select case (size (child))
            case (0);      JDAHEP(:,i) = 0
            case (1);      JDAHEP(:,i) = child(1)
            case default;  JDAHEP(:,i) = (/ child(1), child(size (child)) /)
        end select
        PHEP(1:3,i) = vector3_get_components (space_part (p))
        PHEP(4,i) = energy (p)
        PHEP(5,i) = sign (sqrt (abs (m2)), m2)
        VHEP(1:4,i) = 0
        hepevt_pol(i) = hel
    end subroutine hepevt_set_particle

```

8.2.6 Event output

This is a verbose output of the HEPEVT block.

```

<Event formats: public>+≡
    public :: hepevt_write_verbose

```

<Event formats: procedures>+≡

```

subroutine hepevt_write_verbose (unit)
  integer, intent(in), optional :: unit
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, "(A)") "HEPEVT Common Block"
  write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "NEVHEP", NEVHEP, &
    "Event number"
  write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "NHEP ", NHEP, &
    "Number of particles in event"
  do i = 1, NHEP
    write (u, "(1x,A,I0)") "Particle #", i
    write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)", advance="no") &
      "ISTHEP", ISTHEP(i), "Status code: "
    select case (ISTHEP(i))
    case ( 0); write (u, "(A)") "null entry"
    case ( 1); write (u, "(A)") "outgoing"
    case ( 2); write (u, "(A)") "decayed"
    case ( 3); write (u, "(A)") "documentation"
    case (4:10); write (u, "(A)") "[unspecified]"
    case (11:200); write (u, "(A)") "[model-specific]"
    case (201:); write (u, "(A)") "[user-defined]"
    case default; write (u, "(A)") "[undefined]"
    end select
    write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "IDHEP ", IDHEP(i), &
      "PDG code of particle"
    write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "JMOHEP", JMOHEP(:,i), &
      "Index of first/second mother"
    write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "JDAHEP", JDAHEP(:,i), &
      "Index of first/last daughter"
    write (u, "(3x,A6,' = ',G12.5,1x,G12.5,8x,A)") "PHEP12", PHEP(1:2,i), &
      "Transversal momentum (x/y) in GeV"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "PHEP3 ", PHEP(3,i), &
      "Longitudinal momentum (z) in GeV"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "PHEP4 ", PHEP(4,i), &
      "Energy in GeV"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "PHEP5 ", PHEP(5,i), &
      "Invariant mass in GeV"
    write (u, "(3x,A6,' = ',G12.5,1x,G12.5,8x,A)") "VHEP12", VHEP(1:2,i), &
      "Transversal displacement (xy) in mm"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "VHEP3 ", VHEP(3,i), &
      "Longitudinal displacement (z) in mm"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "VHEP4 ", VHEP(4,i), &
      "Production time in mm"
  end do
end subroutine hepevt_write_verbose

```

This is a verbose output of the HEPEUP block.

<Event formats: public>+≡

```

public :: hepeup_write_verbose

```

<Event formats: procedures>+≡

```

subroutine hepeup_write_verbose (unit)
  integer, intent(in), optional :: unit

```

```

integer :: u, i
u = output_unit (unit); if (u < 0) return
write (u, "(A)") "HEPEUP Common Block"
write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "NUP ", NUP, &
    "Number of particles in event"
write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "IDPRUP", IDPRUP, &
    "Subprocess ID"
write (u, "(3x,A6,' = ',G12.5,1x,20x,A)") "XWGTUP", XWGTUP, &
    "Event weight"
write (u, "(3x,A6,' = ',G12.5,1x,20x,A)") "SCALUP", SCALUP, &
    "Event energy scale in GeV"
write (u, "(3x,A6,' = ',G12.5,1x,20x,A)") "AQEDUP", AQEDUP, &
    "QED coupling [-1 = undefined]"
write (u, "(3x,A6,' = ',G12.5,1x,20x,A)") "AQCDUP", AQCDUP, &
    "QCD coupling [-1 = undefined]"
do i = 1, NUP
    write (u, "(1x,A,I0)") "Particle #", i
    write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)") "IDUP ", IDUP(i), &
        "PDG code of particle"
    write (u, "(3x,A6,' = ',I9,3x,1x,20x,A)", advance="no") &
        "ISTUP ", ISTUP(i), "Status code: "
    select case (ISTUP(i))
    case (-1); write (u, "(A)") "incoming"
    case ( 1); write (u, "(A)") "outgoing"
    case (-2); write (u, "(A)") "spacelike"
    case ( 2); write (u, "(A)") "resonance"
    case ( 3); write (u, "(A)") "resonance (doc)"
    case (-9); write (u, "(A)") "beam"
    case default; write (u, "(A)") "[undefined]"
    end select
    write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "MOTHUP", MOTHUP(:,i), &
        "Index of first/last mother"
    write (u, "(3x,A6,' = ',I9,3x,1x,I9,3x,8x,A)") "ICOLUP", ICOLUP(:,i), &
        "Color/anticolor flow index"
    write (u, "(3x,A6,' = ',G12.5,1x,G12.5,8x,A)") "PUP1/2", PUP(1:2,i), &
        "Transversal momentum (x/y) in GeV"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "PUP3 ", PUP(3,i), &
        "Longitudinal momentum (z) in GeV"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "PUP4 ", PUP(4,i), &
        "Energy in GeV"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "PUP5 ", PUP(5,i), &
        "Invariant mass in GeV"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "VTIMUP", VTIMUP(i), &
        "Invariant lifetime in mm"
    write (u, "(3x,A6,' = ',G12.5,1x,12x,8x,A)") "SPINUP", SPINUP(i), &
        "cos(spin angle) [9 = undefined]"
end do
end subroutine hepeup_write_verbose

```

8.2.7 Event output in various formats

This routine writes event output according to the LHEF standard. It uses the current contents of the HEPEUP block.

```

(Event formats: public)+≡
  public :: hepeup_write_lhef
  public :: hepeup_write_lha

(Event formats: procedures)+≡
  subroutine hepeup_write_lhef (unit)
    integer, intent(in), optional :: unit
    integer :: u, i
    u = output_unit (unit); if (u < 0) return
    write (u, '(A)') "<event>"
    write (u, *) NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP
    do i = 1, NUP
      write (u, *) IDUP(i), ISTUP(i), MOTHUP(:,i), ICOLUP(:,i), &
        PUP(:,i), VTIMUP(i), SPINUP(i)
    end do
    write (u, '(A)') "</event>"
  end subroutine hepeup_write_lhef

  subroutine hepeup_write_lha (unit)
    integer, intent(in), optional :: unit
    integer :: u, i
    integer, dimension(MAXNUP) :: spin_up
    spin_up = SPINUP
    u = output_unit (unit); if (u < 0) return
16 format(2(1x,I5),1x,F17.10,3(1x,F13.6))
17 format(500(1x,I5))
18 format(1x,I5,4(1x,F17.10))
    write (u, 16) NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP
    write (u, 17) IDUP(:NUP)
    write (u, 17) MOTHUP(1,:NUP)
    write (u, 17) MOTHUP(2,:NUP)
    write (u, 17) ICOLUP(1,:NUP)
    write (u, 17) ICOLUP(2,:NUP)
    write (u, 17) ISTUP(:NUP)
    write (u, 17) spin_up(:NUP)
    do i = 1, NUP
      write (u, 18) i, PUP((/ 4,1,2,3 /), i)
    end do
  end subroutine hepeup_write_lha

```

This routine writes event output according to the HEPEVT standard. It uses the current contents of the HEPEVT block and some additional parameters according to the standard in WHIZARD 1. For the long ASCII format, the value of the sample function (i.e. the product of squared matrix element, structure functions and phase space factor is printed out). The option of reweighting matrix elements with respect to some reference cross section is not implemented in WHIZARD 2, therefore the second entry in the long ASCII format (the function ratio) is always one. The ATHENA format is an implementation of the HEPEVT format that is readable by the ATLAS ATHENA software framework.

It is very similar to the WHIZARD 1 HEPEVT format, except that it contains an event counter, a particle counter inside the event, and has the HEPEVT ISTHEP status before the PDG code.

```

(Event formats: public)+≡
  public :: hepevt_write_hepevt
  public :: hepevt_write_ascii
  public :: hepevt_write_athena

(Event formats: procedures)+≡
  subroutine hepevt_write_hepevt (unit)
    integer, intent(in), optional :: unit
    integer :: u, i
    u = output_unit (unit); if (u < 0) return
    write (u, *) NHEP, hepevt_n_out, hepevt_n_remnants, hepevt_weight
    do i = 1, NHEP
      write (u, *) ISTHEP(i), IDHEP(i), JMOHEP(:,i), JDAHEP(:,i), &
        hepevt_pol(i)
      write (u, *) PHEP(:,i)
      write (u, *) VHEP(:,i), 0.d0
    end do
  end subroutine hepevt_write_hepevt

  subroutine hepevt_write_ascii (unit, long)
    integer, intent(in), optional :: unit
    logical, intent(in) :: long
    integer :: u, i
    u = output_unit (unit); if (u < 0) return
    write (u, *) NHEP, hepevt_n_out, hepevt_n_remnants, hepevt_weight
    do i = 1, NHEP
      write (u, *) IDHEP(i), hepevt_pol(i)
      write (u, *) PHEP(:,i)
    end do
    if (long) write (u, *) hepevt_function_value, hepevt_function_ratio
  end subroutine hepevt_write_ascii

  subroutine hepevt_write_athena (unit, i_evt)
    integer, intent(in), optional :: unit, i_evt
    integer :: u, i, num_event
    num_event = 0
    if (present (i_evt)) num_event = i_evt
    u = output_unit (unit); if (u < 0) return
    write (u, *) num_event, NHEP
    do i = 1, NHEP
      write (u, *) i, ISTHEP(i), IDHEP(i), JMOHEP(:,i), JDAHEP(:,i)
      write (u, *) PHEP(:,i)
      write (u, *) VHEP(1:4,i)
    end do
  end subroutine hepevt_write_athena

```

8.3 HepMC events

This section provides the interface to the HepMC C++ library for handling Monte-Carlo events.

Each C++ class of HepMC that we use is mirrored by a Fortran type, which contains as its only component the C pointer to the C++ object.

Each C++ method of HepMC that we use has a C wrapper function. This function takes a pointer to the host object as its first argument. Further arguments are either C pointers, or in the case of simple types (integer, real), interoperable C/Fortran objects.

The C wrapper functions have explicit interfaces in the Fortran module. They are called by Fortran wrapper procedures. These are treated as methods of the corresponding Fortran type.

```
(hepmc_interface.f90)≡  
  <File header>  
  
  module hepmc_interface  
  
    use iso_c_binding !NODEP!  
    <Use kinds>  
    <Use strings>  
    use constants !NODEP!  
    use lorentz !NODEP!  
    use models  
    use flavors  
    use colors  
    use helicities  
    use quantum_numbers  
    use polarizations  
  
    <Standard module head>  
  
    <HepMC interface: public>  
  
    <HepMC interface: types>  
  
    <HepMC interface: interfaces>  
  
    contains  
  
    <HepMC interface: procedures>  
  
  end module hepmc_interface
```

8.3.1 Interface check

This function can be called in order to verify that we are using the actual HepMC library, and not the dummy version.

```
<HepMC interface: interfaces>≡  
  interface  
    logical(c_bool) function hepmc_available () bind(C)  
    import
```

```

        end function hepmc_available
    end interface
<HepMC interface: public>≡
    public :: hepmc_is_available
<HepMC interface: procedures>≡
    function hepmc_is_available () result (flag)
        logical :: flag
        flag = hepmc_available ()
    end function hepmc_is_available

```

8.3.2 FourVector

The C version of four-vectors is often transferred by value, and the associated procedures are all inlined. The wrapper needs to transfer by reference, so we create FourVector objects on the heap which have to be deleted explicitly. The input is a `vector4_t` or `vector3_t` object from the `lorentz` module.

```

<HepMC interface: public>+≡
    public :: hepmc_four_vector_t
<HepMC interface: types>≡
    type :: hepmc_four_vector_t
        private
        type(c_ptr) :: obj
    end type hepmc_four_vector_t

```

In the C constructor, the zero-component (fourth argument) is optional; if missing, it is set to zero. The Fortran version has initializer form and takes either a three-vector or a four-vector. A further version extracts the four-vector from a HepMC particle object.

```

<HepMC interface: interfaces>+≡
    interface
        type(c_ptr) function new_four_vector_xyz (x, y, z) bind(C)
            import
            real(c_double), value :: x, y, z
        end function new_four_vector_xyz
    end interface
    interface
        type(c_ptr) function new_four_vector_xyz_t (x, y, z, t) bind(C)
            import
            real(c_double), value :: x, y, z, t
        end function new_four_vector_xyz_t
    end interface
<HepMC interface: public>+≡
    public :: hepmc_four_vector_init
<HepMC interface: interfaces>+≡
    interface hepmc_four_vector_init
        module procedure hepmc_four_vector_init_v4
        module procedure hepmc_four_vector_init_v3
        module procedure hepmc_four_vector_init_hepmc_prt
    end interface

```



```

<HepMC interface: procedures>+≡
subroutine hepmc_four_vector_init_v4 (pp, p)
  type(hepmc_four_vector_t), intent(out) :: pp
  type(vector4_t), intent(in) :: p
  real(default), dimension(0:3) :: pa
  pa = vector4_get_components (p)
  pp%obj = new_four_vector_xyz &
    (real (pa(1), c_double), &
     real (pa(2), c_double), &
     real (pa(3), c_double), &
     real (pa(0), c_double))
end subroutine hepmc_four_vector_init_v4

subroutine hepmc_four_vector_init_v3 (pp, p)
  type(hepmc_four_vector_t), intent(out) :: pp
  type(vector3_t), intent(in) :: p
  real(default), dimension(3) :: pa
  pa = vector3_get_components (p)
  pp%obj = new_four_vector_xyz &
    (real (pa(1), c_double), &
     real (pa(2), c_double), &
     real (pa(3), c_double))
end subroutine hepmc_four_vector_init_v3

subroutine hepmc_four_vector_init_hepmc_prt (pp, prt)
  type(hepmc_four_vector_t), intent(out) :: pp
  type(hepmc_particle_t), intent(in) :: prt
  pp%obj = gen_particle_momentum (prt%obj)
end subroutine hepmc_four_vector_init_hepmc_prt

```

Here, the destructor is explicitly needed.

```

<HepMC interface: interfaces>+≡
interface
  subroutine four_vector_delete (p_obj) bind(C)
    import
    type(c_ptr), value :: p_obj
  end subroutine four_vector_delete
end interface

<HepMC interface: public>+≡
public :: hepmc_four_vector_final

<HepMC interface: procedures>+≡
subroutine hepmc_four_vector_final (p)
  type(hepmc_four_vector_t), intent(inout) :: p
  call four_vector_delete (p%obj)
end subroutine hepmc_four_vector_final

```

Convert to a Lorentz vector.

```

<HepMC interface: interfaces>+≡
interface
  function four_vector_px (p_obj) result (px) bind(C)
    import
    real(c_double) :: px

```

```

        type(c_ptr), value :: p_obj
    end function four_vector_px
end interface
interface
    function four_vector_py (p_obj) result (py) bind(C)
        import
        real(c_double) :: py
        type(c_ptr), value :: p_obj
    end function four_vector_py
end interface
interface
    function four_vector_pz (p_obj) result (pz) bind(C)
        import
        real(c_double) :: pz
        type(c_ptr), value :: p_obj
    end function four_vector_pz
end interface
interface
    function four_vector_e (p_obj) result (e) bind(C)
        import
        real(c_double) :: e
        type(c_ptr), value :: p_obj
    end function four_vector_e
end interface
<HepMC interface: public>+≡
    public :: hepmc_four_vector_to_vector4
<HepMC interface: procedures>+≡
    subroutine hepmc_four_vector_to_vector4 (pp, p)
        type(hepmc_four_vector_t), intent(in) :: pp
        type(vector4_t), intent(out) :: p
        real(default) :: E
        real(default), dimension(3) :: p3
        E = four_vector_e (pp%obj)
        p3(1) = four_vector_px (pp%obj)
        p3(2) = four_vector_py (pp%obj)
        p3(3) = four_vector_pz (pp%obj)
        p = vector4_moving (E, vector3_moving (p3))
    end subroutine hepmc_four_vector_to_vector4

```

8.3.3 Polarization

Polarization objects are temporarily used for assigning particle polarization. We add a flag `polarized`. If this is false, the polarization is not set and should not be transferred to `hepmc_particle` objects.

```

<HepMC interface: public>+≡
    public :: hepmc_polarization_t
<HepMC interface: types>+≡
    type :: hepmc_polarization_t
    private
    logical :: polarized = .false.
    type(c_ptr) :: obj

```

```
end type hepmc_polarization_t
```

Constructor. The C wrapper takes polar and azimuthal angle as arguments. The Fortran version allows for either a complete polarization density matrix, or for a definite (diagonal) helicity.

HepMC does not allow to specify the degree of polarization, therefore we have to map it to either 0 or 1. We choose 0 for polarization less than 0.5 and 1 for polarization greater than 0.5. Even this simplification works only for spin-1/2 and for massless particles; massive vector bosons cannot be treated this way. In particular, zero helicity is always translated as unpolarized.

(HepMC interface: interfaces)+≡

```
interface
  type(c_ptr) function new_polarization (theta, phi) bind(C)
  import
    real(c_double), value :: theta, phi
  end function new_polarization
end interface
```

(HepMC interface: public)+≡

```
public :: hepmc_polarization_init
```

(HepMC interface: interfaces)+≡

```
interface hepmc_polarization_init
  module procedure hepmc_polarization_init_pol
  module procedure hepmc_polarization_init_hel
end interface
```

(HepMC interface: procedures)+≡

```
subroutine hepmc_polarization_init_pol (hpol, pol)
  type(hepmc_polarization_t), intent(out) :: hpol
  type(polarization_t), intent(in) :: pol
  real(default) :: r, theta, phi
  if (polarization_is_polarized (pol)) then
    call polarization_to_angles (pol, r, theta, phi)
    if (r >= 0.5) then
      hpol%polarized = .true.
      hpol%obj = new_polarization &
        (real (theta, c_double), real (phi, c_double))
    end if
  end if
end subroutine hepmc_polarization_init_pol

subroutine hepmc_polarization_init_hel (hpol, hel)
  type(hepmc_polarization_t), intent(out) :: hpol
  type(helicity_t), intent(in) :: hel
  integer, dimension(2) :: h
  if (helicity_is_defined (hel)) then
    h = helicity_get (hel)
    select case (h(1))
    case (1:)
      hpol%polarized = .true.
      hpol%obj = new_polarization (0._c_double, 0._c_double)
    case (:-1)
      hpol%polarized = .true.
      hpol%obj = new_polarization (real (pi, c_double), 0._c_double)
```

```

        end select
    end if
end subroutine hepmc_polarization_init_hel

```

Destructor. The C object is deallocated only if the polarized flag is set.

(HepMC interface: interfaces)+≡

```

interface
    subroutine polarization_delete (pol_obj) bind(C)
    import
    type(c_ptr), value :: pol_obj
    end subroutine polarization_delete
end interface

```

(HepMC interface: public)+≡

```

public :: hepmc_polarization_final

```

(HepMC interface: procedures)+≡

```

subroutine hepmc_polarization_final (hpol)
    type(hepmc_polarization_t), intent(inout) :: hpol
    if (hpol%polarized) call polarization_delete (hpol%obj)
end subroutine hepmc_polarization_final

```

Recover polarization from HepMC polarization object (with the abovementioned deficiencies).

(HepMC interface: interfaces)+≡

```

interface
    function polarization_theta (pol_obj) result (theta) bind(C)
    import
    real(c_double) :: theta
    type(c_ptr), value :: pol_obj
    end function polarization_theta
end interface

```

```

interface
    function polarization_phi (pol_obj) result (phi) bind(C)
    import
    real(c_double) :: phi
    type(c_ptr), value :: pol_obj
    end function polarization_phi
end interface

```

(HepMC interface: public)+≡

```

public :: hepmc_polarization_to_pol

```

(HepMC interface: procedures)+≡

```

subroutine hepmc_polarization_to_pol (hpol, flv, pol)
    type(hepmc_polarization_t), intent(in) :: hpol
    type(flavor_t), intent(in) :: flv
    type(polarization_t), intent(out) :: pol
    real(default) :: theta, phi
    theta = polarization_theta (hpol%obj)
    phi = polarization_phi (hpol%obj)
    call polarization_init_angles (pol, flv, 1._default, theta, phi)
end subroutine hepmc_polarization_to_pol

```

Recover helicity. Here, ϕ is ignored and only the sign of $\cos \theta$ is relevant, mapped to positive/negative helicity.

```

<HepMC interface: public>+≡
    public :: hepmc_polarization_to_hel

<HepMC interface: procedures>+≡
    subroutine hepmc_polarization_to_hel (hpol, flv, hel)
        type(hepmc_polarization_t), intent(in) :: hpol
        type(flavor_t), intent(in) :: flv
        type(helicity_t), intent(out) :: hel
        real(default) :: theta
        integer :: hmax
        theta = polarization_theta (hpol%obj)
        hmax = flavor_get_spin_type (flv) / 2
        call helicity_init (hel, sign (hmax, nint (cos (theta))))
    end subroutine hepmc_polarization_to_hel

```

8.3.4 GenParticle

Particle objects have the obvious meaning.

```

<HepMC interface: public>+≡
    public :: hepmc_particle_t

<HepMC interface: types>+≡
    type :: hepmc_particle_t
    private
    type(c_ptr) :: obj
    end type hepmc_particle_t

```

Constructor. The C version takes a FourVector object, which in the Fortran wrapper is created on the fly from a `vector4` Lorentz vector.

No destructor is needed as long as all particles are entered into vertex containers.

```

<HepMC interface: interfaces>+≡
    interface
        type(c_ptr) function new_gen_particle (prt_obj, pdg_id, status) bind(C)
            import
            type(c_ptr), value :: prt_obj
            integer(c_int), value :: pdg_id, status
        end function new_gen_particle
    end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_init

<HepMC interface: procedures>+≡
    subroutine hepmc_particle_init (prt, p, pdg, status)
        type(hepmc_particle_t), intent(out) :: prt
        type(vector4_t), intent(in) :: p
        integer, intent(in) :: pdg, status
        type(hepmc_four_vector_t) :: pp
        call hepmc_four_vector_init (pp, p)
        prt%obj = new_gen_particle (pp%obj, int (pdg, c_int), int (status, c_int))
    end subroutine hepmc_particle_init

```

```

    call hepmc_four_vector_final (pp)
end subroutine hepmc_particle_init

```

Set the particle color flow.

```

<HepMC interface: interfaces>+≡
interface
    subroutine gen_particle_set_flow (prt_obj, code_index, code) bind(C)
    import
    type(c_ptr), value :: prt_obj
    integer(c_int), value :: code_index, code
    end subroutine gen_particle_set_flow
end interface

<HepMC interface: public>+≡
public :: hepmc_particle_set_color

<HepMC interface: procedures>+≡
subroutine hepmc_particle_set_color (prt, col)
    type(hepmc_particle_t), intent(inout) :: prt
    type(color_t), intent(in) :: col
    integer(c_int) :: c
    c = color_get_col (col)
    if (c /= 0) call gen_particle_set_flow (prt%obj, 1_c_int, c)
    c = color_get_acl (col)
    if (c /= 0) call gen_particle_set_flow (prt%obj, 2_c_int, c)
end subroutine hepmc_particle_set_color

```

Set the particle polarization. For the restrictions on particle polarization in HepMC, see above hepmc_polarization_init.

```

<HepMC interface: interfaces>+≡
interface
    subroutine gen_particle_set_polarization (prt_obj, pol_obj) bind(C)
    import
    type(c_ptr), value :: prt_obj, pol_obj
    end subroutine gen_particle_set_polarization
end interface

<HepMC interface: public>+≡
public :: hepmc_particle_set_polarization

<HepMC interface: interfaces>+≡
interface hepmc_particle_set_polarization
    module procedure hepmc_particle_set_polarization_pol
    module procedure hepmc_particle_set_polarization_hel
end interface

<HepMC interface: procedures>+≡
subroutine hepmc_particle_set_polarization_pol (prt, pol)
    type(hepmc_particle_t), intent(inout) :: prt
    type(polarization_t), intent(in) :: pol
    type(hepmc_polarization_t) :: hpol
    call hepmc_polarization_init (hpol, pol)
    if (hpol%polarized) call gen_particle_set_polarization (prt%obj, hpol%obj)
    call hepmc_polarization_final (hpol)
end subroutine hepmc_particle_set_polarization_pol

```

```

subroutine hepmc_particle_set_polarization_hel (prt, hel)
  type(hepmc_particle_t), intent(inout) :: prt
  type(helicity_t), intent(in) :: hel
  type(hepmc_polarization_t) :: hpol
  call hepmc_polarization_init (hpol, hel)
  if (hpol%polarized) call gen_particle_set_polarization (prt%obj, hpol%obj)
  call hepmc_polarization_final (hpol)
end subroutine hepmc_particle_set_polarization_hel

```

Return the HepMC barcode (unique integer ID) of the particle.

```

<HepMC interface: interfaces>+≡
  interface
    function gen_particle_barcode (prt_obj) result (barcode) bind(C)
      import
      integer(c_int) :: barcode
      type(c_ptr), value :: prt_obj
    end function gen_particle_barcode
  end interface

<HepMC interface: public>+≡
  public :: hepmc_particle_get_barcode

<HepMC interface: procedures>+≡
  function hepmc_particle_get_barcode (prt) result (barcode)
    integer :: barcode
    type(hepmc_particle_t), intent(in) :: prt
    barcode = gen_particle_barcode (prt%obj)
  end function hepmc_particle_get_barcode

```

Return the four-vector component of the particle object as a `vector4_t` Lorentz vector.

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function gen_particle_momentum (prt_obj) bind(C)
      import
      type(c_ptr), value :: prt_obj
    end function gen_particle_momentum
  end interface

<HepMC interface: public>+≡
  public :: hepmc_particle_get_momentum

<HepMC interface: procedures>+≡
  function hepmc_particle_get_momentum (prt) result (p)
    type(vector4_t) :: p
    type(hepmc_particle_t), intent(in) :: prt
    type(hepmc_four_vector_t) :: pp
    call hepmc_four_vector_init (pp, prt)
    call hepmc_four_vector_to_vector4 (pp, p)
    call hepmc_four_vector_final (pp)
  end function hepmc_particle_get_momentum

```

Return the invariant mass squared of the particle object. HepMC stores the signed invariant mass (no squaring).

```

<HepMC interface: interfaces>+≡
    interface
        function gen_particle_generated_mass (prt_obj) result (mass) bind(C)
            import
                real(c_double) :: mass
                type(c_ptr), value :: prt_obj
            end function gen_particle_generated_mass
        end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_get_mass_squared

<HepMC interface: procedures>+≡
    function hepmc_particle_get_mass_squared (prt) result (m2)
        real(default) :: m2
        type(hepmc_particle_t), intent(in) :: prt
        real(default) :: m
        m = gen_particle_generated_mass (prt%obj)
        m2 = sign (m**2, m)
    end function hepmc_particle_get_mass_squared

```

Return the PDG ID:

```

<HepMC interface: interfaces>+≡
    interface
        function gen_particle_pdg_id (prt_obj) result (pdg_id) bind(C)
            import
                integer(c_int) :: pdg_id
                type(c_ptr), value :: prt_obj
            end function gen_particle_pdg_id
        end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_get_pdg

<HepMC interface: procedures>+≡
    function hepmc_particle_get_pdg (prt) result (pdg)
        integer :: pdg
        type(hepmc_particle_t), intent(in) :: prt
        pdg = gen_particle_pdg_id (prt%obj)
    end function hepmc_particle_get_pdg

```

Return the status code:

```

<HepMC interface: interfaces>+≡
    interface
        function gen_particle_status (prt_obj) result (status) bind(C)
            import
                integer(c_int) :: status
                type(c_ptr), value :: prt_obj
            end function gen_particle_status
        end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_get_status

```



```

<HepMC interface: procedures>+≡
function hepmc_particle_get_status (prt) result (status)
integer :: status
type(hepmc_particle_t), intent(in) :: prt
status = gen_particle_status (prt%obj)
end function hepmc_particle_get_status

```

Return the production/decay vertex (as a pointer, no finalization necessary).

```

<HepMC interface: interfaces>+≡
interface
type(c_ptr) function gen_particle_production_vertex (prt_obj) bind(C)
import
type(c_ptr), value :: prt_obj
end function gen_particle_production_vertex
end interface
interface
type(c_ptr) function gen_particle_end_vertex (prt_obj) bind(C)
import
type(c_ptr), value :: prt_obj
end function gen_particle_end_vertex
end interface

<HepMC interface: public>+≡
public :: hepmc_particle_get_production_vertex
public :: hepmc_particle_get_decay_vertex

<HepMC interface: procedures>+≡
function hepmc_particle_get_production_vertex (prt) result (v)
type(hepmc_vertex_t) :: v
type(hepmc_particle_t), intent(in) :: prt
v%obj = gen_particle_production_vertex (prt%obj)
end function hepmc_particle_get_production_vertex

function hepmc_particle_get_decay_vertex (prt) result (v)
type(hepmc_vertex_t) :: v
type(hepmc_particle_t), intent(in) :: prt
v%obj = gen_particle_end_vertex (prt%obj)
end function hepmc_particle_get_decay_vertex

```

Return the number of parents/children.

```

<HepMC interface: public>+≡
public :: hepmc_particle_get_n_parents
public :: hepmc_particle_get_n_children

<HepMC interface: procedures>+≡
function hepmc_particle_get_n_parents (prt) result (n_parents)
integer :: n_parents
type(hepmc_particle_t), intent(in) :: prt
type(hepmc_vertex_t) :: v
v = hepmc_particle_get_production_vertex (prt)
if (hepmc_vertex_is_valid (v)) then
n_parents = hepmc_vertex_get_n_in (v)
else
n_parents = 0
end if
end function hepmc_particle_get_n_parents

```

```

    end if
end function hepmc_particle_get_n_parents

function hepmc_particle_get_n_children (prt) result (n_children)
    integer :: n_children
    type(hepmc_particle_t), intent(in) :: prt
    type(hepmc_vertex_t) :: v
    v = hepmc_particle_get_decay_vertex (prt)
    if (hepmc_vertex_is_valid (v)) then
        n_children = hepmc_vertex_get_n_out (v)
    else
        n_children = 0
    end if
end function hepmc_particle_get_n_children

```

Convenience function: Return the array of parent particles for a given HepMC particle. The contents are HepMC barcodes that still have to be mapped to the particle indices.

```

<HepMC interface: public>+≡
    public :: hepmc_particle_get_parent_barcodes
    public :: hepmc_particle_get_child_barcodes

<HepMC interface: procedures>+≡
    function hepmc_particle_get_parent_barcodes (prt) result (parent_barcode)
        type(hepmc_particle_t), intent(in) :: prt
        integer, dimension(:), allocatable :: parent_barcode
        type(hepmc_vertex_t) :: v
        type(hepmc_vertex_particle_in_iterator_t) :: it
        integer :: i
        v = hepmc_particle_get_production_vertex (prt)
        if (hepmc_vertex_is_valid (v)) then
            allocate (parent_barcode (hepmc_vertex_get_n_in (v)))
            if (size (parent_barcode) /= 0) then
                call hepmc_vertex_particle_in_iterator_init (it, v)
                do i = 1, size (parent_barcode)
                    parent_barcode(i) = hepmc_particle_get_barcode &
                        (hepmc_vertex_particle_in_iterator_get (it))
                    call hepmc_vertex_particle_in_iterator_advance (it)
                end do
                call hepmc_vertex_particle_in_iterator_final (it)
            end if
        else
            allocate (parent_barcode (0))
        end if
    end function hepmc_particle_get_parent_barcodes

    function hepmc_particle_get_child_barcodes (prt) result (child_barcode)
        type(hepmc_particle_t), intent(in) :: prt
        integer, dimension(:), allocatable :: child_barcode
        type(hepmc_vertex_t) :: v
        type(hepmc_vertex_particle_out_iterator_t) :: it
        integer :: i
        v = hepmc_particle_get_decay_vertex (prt)
        if (hepmc_vertex_is_valid (v)) then

```

```

        allocate (child_barcode (hepmc_vertex_get_n_out (v)))
        call hepmc_vertex_particle_out_iterator_init (it, v)
        if (size (child_barcode) /= 0) then
            do i = 1, size (child_barcode)
                child_barcode(i) = hepmc_particle_get_barcode &
                    (hepmc_vertex_particle_out_iterator_get (it))
                call hepmc_vertex_particle_out_iterator_advance (it)
            end do
            call hepmc_vertex_particle_out_iterator_final (it)
        end if
    else
        allocate (child_barcode (0))
    end if
end function hepmc_particle_get_child_barcodes

```

Return the polarization (assuming that the particle is completely polarized).
 Note that the generated polarization object needs finalization.

```

<HepMC interface: interfaces>+≡
    interface
        type(c_ptr) function gen_particle_polarization (prt_obj) bind(C)
        import
        type(c_ptr), value :: prt_obj
        end function gen_particle_polarization
    end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_get_polarization

<HepMC interface: procedures>+≡
    function hepmc_particle_get_polarization (prt) result (pol)
        type(hepmc_polarization_t) :: pol
        type(hepmc_particle_t), intent(in) :: prt
        pol%obj = gen_particle_polarization (prt%obj)
    end function hepmc_particle_get_polarization

```

Return the particle color as a two-dimensional array (color, anticolor).

```

<HepMC interface: interfaces>+≡
    interface
        function gen_particle_flow (prt_obj, code_index) result (code) bind(C)
        import
        integer(c_int) :: code
        type(c_ptr), value :: prt_obj
        integer(c_int), value :: code_index
        end function gen_particle_flow
    end interface

<HepMC interface: public>+≡
    public :: hepmc_particle_get_color

<HepMC interface: procedures>+≡
    function hepmc_particle_get_color (prt) result (col)
        integer, dimension(2) :: col
        type(hepmc_particle_t), intent(in) :: prt
        col(1) = gen_particle_flow (prt%obj, 1)
        col(2) = - gen_particle_flow (prt%obj, 2)
    end function hepmc_particle_get_color

```

```
end function hepmc_particle_get_color
```

8.3.5 GenVertex

Vertices are made of particles (incoming and outgoing).

```
<HepMC interface: public>+≡
  public :: hepmc_vertex_t

<HepMC interface: types>+≡
  type :: hepmc_vertex_t
  private
  type(c_ptr) :: obj
end type hepmc_vertex_t
```

Constructor. Two versions, one plain, one with the position in space and time (measured in mm) as argument. The Fortran version has initializer form, and the vertex position is an optional argument.

A destructor is unnecessary as long as all vertices are entered into an event container.

```
<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function new_gen_vertex () bind(C)
    import
  end function new_gen_vertex
end interface
interface
  type(c_ptr) function new_gen_vertex_pos (prt_obj) bind(C)
  import
  type(c_ptr), value :: prt_obj
end function new_gen_vertex_pos
end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_init

<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_init (v, x)
    type(hepmc_vertex_t), intent(out) :: v
    type(vector4_t), intent(in), optional :: x
    type(hepmc_four_vector_t) :: pos
    if (present (x)) then
      call hepmc_four_vector_init (pos, x)
      v%obj = new_gen_vertex_pos (pos%obj)
      call hepmc_four_vector_final (pos)
    else
      v%obj = new_gen_vertex ()
    end if
  end subroutine hepmc_vertex_init
```

Return true if the vertex pointer is non-null:

```
<HepMC interface: interfaces>+≡
  interface
```

```

        function gen_vertex_is_valid (v_obj) result (flag) bind(C)
            import
            logical(c_bool) :: flag
            type(c_ptr), value :: v_obj
        end function gen_vertex_is_valid
    end interface

    <HepMC interface: public>+≡
        public :: hepmc_vertex_is_valid

    <HepMC interface: procedures>+≡
        function hepmc_vertex_is_valid (v) result (flag)
            logical :: flag
            type(hepmc_vertex_t), intent(in) :: v
            flag = gen_vertex_is_valid (v%obj)
        end function hepmc_vertex_is_valid

```

Add a particle to a vertex, incoming or outgoing.

```

    <HepMC interface: interfaces>+≡
        interface
            subroutine gen_vertex_add_particle_in (v_obj, prt_obj) bind(C)
                import
                type(c_ptr), value :: v_obj, prt_obj
            end subroutine gen_vertex_add_particle_in
        end interface
        interface
            subroutine gen_vertex_add_particle_out (v_obj, prt_obj) bind(C)
                import
                type(c_ptr), value :: v_obj, prt_obj
            end subroutine gen_vertex_add_particle_out
        end interface

    <HepMC interface: public>+≡
        public :: hepmc_vertex_add_particle_in
        public :: hepmc_vertex_add_particle_out

    <HepMC interface: procedures>+≡
        subroutine hepmc_vertex_add_particle_in (v, prt)
            type(hepmc_vertex_t), intent(inout) :: v
            type(hepmc_particle_t), intent(in) :: prt
            call gen_vertex_add_particle_in (v%obj, prt%obj)
        end subroutine hepmc_vertex_add_particle_in

        subroutine hepmc_vertex_add_particle_out (v, prt)
            type(hepmc_vertex_t), intent(inout) :: v
            type(hepmc_particle_t), intent(in) :: prt
            call gen_vertex_add_particle_out (v%obj, prt%obj)
        end subroutine hepmc_vertex_add_particle_out

```

Return the number of incoming/outgoing particles.

```

    <HepMC interface: interfaces>+≡
        interface
            function gen_vertex_particles_in_size (v_obj) result (size) bind(C)
                import
                integer(c_int) :: size

```

```

        type(c_ptr), value :: v_obj
    end function gen_vertex_particles_in_size
end interface
interface
    function gen_vertex_particles_out_size (v_obj) result (size) bind(C)
        import
        integer(c_int) :: size
        type(c_ptr), value :: v_obj
    end function gen_vertex_particles_out_size
end interface

<HepMC interface: public>+≡
    public :: hepmc_vertex_get_n_in
    public :: hepmc_vertex_get_n_out

<HepMC interface: procedures>+≡
    function hepmc_vertex_get_n_in (v) result (n_in)
        integer :: n_in
        type(hepmc_vertex_t), intent(in) :: v
        n_in = gen_vertex_particles_in_size (v%obj)
    end function hepmc_vertex_get_n_in

    function hepmc_vertex_get_n_out (v) result (n_out)
        integer :: n_out
        type(hepmc_vertex_t), intent(in) :: v
        n_out = gen_vertex_particles_out_size (v%obj)
    end function hepmc_vertex_get_n_out

```

8.3.6 Vertex-particle-in iterator

This iterator iterates over all incoming particles in an vertex. We store a pointer to the vertex in addition to the iterator. This allows for simple end checking.

The iterator is actually a constant iterator; it can only read.

```

<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_t

<HepMC interface: types>+≡
    type :: hepmc_vertex_particle_in_iterator_t
    private
    type(c_ptr) :: obj
    type(c_ptr) :: v_obj
    end type hepmc_vertex_particle_in_iterator_t

```

Constructor. The iterator is initialized at the first particle in the vertex.

```

<HepMC interface: interfaces>+≡
    interface
        type(c_ptr) function &
            new_vertex_particles_in_const_iterator (v_obj) bind(C)
        import
        type(c_ptr), value :: v_obj
    end function new_vertex_particles_in_const_iterator
end interface

```

```

<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_init
<HepMC interface: procedures>+≡
    subroutine hepmc_vertex_particle_in_iterator_init (it, v)
        type(hepmc_vertex_particle_in_iterator_t), intent(out) :: it
        type(hepmc_vertex_t), intent(in) :: v
        it%obj = new_vertex_particles_in_const_iterator (v%obj)
        it%v_obj = v%obj
    end subroutine hepmc_vertex_particle_in_iterator_init

```

Destructor. Necessary because the iterator is allocated on the heap.

```

<HepMC interface: interfaces>+≡
    interface
        subroutine vertex_particles_in_const_iterator_delete (it_obj) bind(C)
            import
            type(c_ptr), value :: it_obj
        end subroutine vertex_particles_in_const_iterator_delete
    end interface
<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_final
<HepMC interface: procedures>+≡
    subroutine hepmc_vertex_particle_in_iterator_final (it)
        type(hepmc_vertex_particle_in_iterator_t), intent(inout) :: it
        call vertex_particles_in_const_iterator_delete (it%obj)
    end subroutine hepmc_vertex_particle_in_iterator_final

```

Increment

```

<HepMC interface: interfaces>+≡
    interface
        subroutine vertex_particles_in_const_iterator_advance (it_obj) bind(C)
            import
            type(c_ptr), value :: it_obj
        end subroutine vertex_particles_in_const_iterator_advance
    end interface
<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_advance
<HepMC interface: procedures>+≡
    subroutine hepmc_vertex_particle_in_iterator_advance (it)
        type(hepmc_vertex_particle_in_iterator_t), intent(inout) :: it
        call vertex_particles_in_const_iterator_advance (it%obj)
    end subroutine hepmc_vertex_particle_in_iterator_advance

```

Reset to the beginning

```

<HepMC interface: interfaces>+≡
    interface
        subroutine vertex_particles_in_const_iterator_reset &
            (it_obj, v_obj) bind(C)
            import
            type(c_ptr), value :: it_obj, v_obj
        end subroutine vertex_particles_in_const_iterator_reset
    end interface

```

```

<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_reset

<HepMC interface: procedures>+≡
    subroutine hepmc_vertex_particle_in_iterator_reset (it)
        type(hepmc_vertex_particle_in_iterator_t), intent(inout) :: it
        call vertex_particles_in_const_iterator_reset (it%obj, it%v_obj)
    end subroutine hepmc_vertex_particle_in_iterator_reset

```

Test: return true as long as we are not past the end.

```

<HepMC interface: interfaces>+≡
    interface
        function vertex_particles_in_const_iterator_is_valid &
            (it_obj, v_obj) result (flag) bind(C)
        import
        logical(c_bool) :: flag
        type(c_ptr), value :: it_obj, v_obj
        end function vertex_particles_in_const_iterator_is_valid
    end interface

<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_is_valid

<HepMC interface: procedures>+≡
    function hepmc_vertex_particle_in_iterator_is_valid (it) result (flag)
        logical :: flag
        type(hepmc_vertex_particle_in_iterator_t), intent(in) :: it
        flag = vertex_particles_in_const_iterator_is_valid (it%obj, it%v_obj)
    end function hepmc_vertex_particle_in_iterator_is_valid

```

Return the particle pointed to by the iterator. (The particle object should not be finalized, since it contains merely a pointer to the particle which is owned by the vertex.)

```

<HepMC interface: interfaces>+≡
    interface
        type(c_ptr) function &
            vertex_particles_in_const_iterator_get (it_obj) bind(C)
        import
        type(c_ptr), value :: it_obj
        end function vertex_particles_in_const_iterator_get
    end interface

<HepMC interface: public>+≡
    public :: hepmc_vertex_particle_in_iterator_get

<HepMC interface: procedures>+≡
    function hepmc_vertex_particle_in_iterator_get (it) result (prt)
        type(hepmc_particle_t) :: prt
        type(hepmc_vertex_particle_in_iterator_t), intent(in) :: it
        prt%obj = vertex_particles_in_const_iterator_get (it%obj)
    end function hepmc_vertex_particle_in_iterator_get

```


8.3.7 Vertex-particle-out iterator

This iterator iterates over all incoming particles in an vertex. We store a pointer to the vertex in addition to the iterator. This allows for simple end checking.

The iterator is actually a constant iterator; it can only read.

```
<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_t

<HepMC interface: types>+≡
  type :: hepmc_vertex_particle_out_iterator_t
  private
    type(c_ptr) :: obj
    type(c_ptr) :: v_obj
  end type hepmc_vertex_particle_out_iterator_t
```

Constructor. The iterator is initialized at the first particle in the vertex.

```
<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function &
      new_vertex_particles_out_const_iterator (v_obj) bind(C)
    import
      type(c_ptr), value :: v_obj
    end function new_vertex_particles_out_const_iterator
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_init

<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_out_iterator_init (it, v)
    type(hepmc_vertex_particle_out_iterator_t), intent(out) :: it
    type(hepmc_vertex_t), intent(in) :: v
    it%obj = new_vertex_particles_out_const_iterator (v%obj)
    it%v_obj = v%obj
  end subroutine hepmc_vertex_particle_out_iterator_init
```

Destructor. Necessary because the iterator is allocated on the heap.

```
<HepMC interface: interfaces>+≡
  interface
    subroutine vertex_particles_out_const_iterator_delete (it_obj) bind(C)
    import
      type(c_ptr), value :: it_obj
    end subroutine vertex_particles_out_const_iterator_delete
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_final

<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_out_iterator_final (it)
    type(hepmc_vertex_particle_out_iterator_t), intent(inout) :: it
    call vertex_particles_out_const_iterator_delete (it%obj)
  end subroutine hepmc_vertex_particle_out_iterator_final
```

Increment

```
<HepMC interface: interfaces>+≡
  interface
    subroutine vertex_particles_out_const_iterator_advance (it_obj) bind(C)
      import
      type(c_ptr), value :: it_obj
    end subroutine vertex_particles_out_const_iterator_advance
  end interface
<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_advance
<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_out_iterator_advance (it)
    type(hepmc_vertex_particle_out_iterator_t), intent(inout) :: it
    call vertex_particles_out_const_iterator_advance (it%obj)
  end subroutine hepmc_vertex_particle_out_iterator_advance
```

Reset to the beginning

```
<HepMC interface: interfaces>+≡
  interface
    subroutine vertex_particles_out_const_iterator_reset &
      (it_obj, v_obj) bind(C)
      import
      type(c_ptr), value :: it_obj, v_obj
    end subroutine vertex_particles_out_const_iterator_reset
  end interface
<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_reset
<HepMC interface: procedures>+≡
  subroutine hepmc_vertex_particle_out_iterator_reset (it)
    type(hepmc_vertex_particle_out_iterator_t), intent(inout) :: it
    call vertex_particles_out_const_iterator_reset (it%obj, it%v_obj)
  end subroutine hepmc_vertex_particle_out_iterator_reset
```

Test: return true as long as we are not past the end.

```
<HepMC interface: interfaces>+≡
  interface
    function vertex_particles_out_const_iterator_is_valid &
      (it_obj, v_obj) result (flag) bind(C)
      import
      logical(c_bool) :: flag
      type(c_ptr), value :: it_obj, v_obj
    end function vertex_particles_out_const_iterator_is_valid
  end interface
<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_is_valid
<HepMC interface: procedures>+≡
  function hepmc_vertex_particle_out_iterator_is_valid (it) result (flag)
    logical :: flag
    type(hepmc_vertex_particle_out_iterator_t), intent(in) :: it
    flag = vertex_particles_out_const_iterator_is_valid (it%obj, it%v_obj)
```

```
end function hepmc_vertex_particle_out_iterator_is_valid
```

Return the particle pointed to by the iterator. (The particle object should not be finalized, since it contains merely a pointer to the particle which is owned by the vertex.)

```
<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function &
      vertex_particles_out_const_iterator_get (it_obj) bind(C)
    import
      type(c_ptr), value :: it_obj
    end function vertex_particles_out_const_iterator_get
  end interface

<HepMC interface: public>+≡
  public :: hepmc_vertex_particle_out_iterator_get

<HepMC interface: procedures>+≡
  function hepmc_vertex_particle_out_iterator_get (it) result (prt)
    type(hepmc_particle_t) :: prt
    type(hepmc_vertex_particle_out_iterator_t), intent(in) :: it
    prt%obj = vertex_particles_out_const_iterator_get (it%obj)
  end function hepmc_vertex_particle_out_iterator_get
```

8.3.8 GenEvent

The main object of HepMC is a GenEvent. The object is filled by GenVertex objects, which in turn contain GenParticle objects.

```
<HepMC interface: public>+≡
  public :: hepmc_event_t

<HepMC interface: types>+≡
  type :: hepmc_event_t
  private
    type(c_ptr) :: obj
  end type hepmc_event_t
```

Constructor. Arguments are process ID (integer) and event ID (integer).

The Fortran version has initializer form.

```
<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function new_gen_event (proc_id, event_id) bind(C)
    import
      integer(c_int), value :: proc_id, event_id
    end function new_gen_event
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_init
```

```

<HepMC interface: procedures>+≡
  subroutine hepmc_event_init (evt, proc_id, event_id)
    type(hepmc_event_t), intent(out) :: evt
    integer, intent(in), optional :: proc_id, event_id
    integer(c_int) :: pid, eid
    pid = 0; if (present (proc_id)) pid = proc_id
    eid = 0; if (present (event_id)) eid = event_id
    evt%obj = new_gen_event (pid, eid)
  end subroutine hepmc_event_init

```

Destructor.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_delete (evt_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
    end subroutine gen_event_delete
  end interface

```

```

<HepMC interface: public>+≡
  public :: hepmc_event_final

```

```

<HepMC interface: procedures>+≡
  subroutine hepmc_event_final (evt)
    type(hepmc_event_t), intent(inout) :: evt
    call gen_event_delete (evt%obj)
  end subroutine hepmc_event_final

```

Screen output. Printing to file is possible in principle (using a C++ output channel), by allowing an argument. Printing to an open Fortran unit is obviously not possible.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_print (evt_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
    end subroutine gen_event_print
  end interface

```

```

<HepMC interface: public>+≡
  public :: hepmc_event_print

```

```

<HepMC interface: procedures>+≡
  subroutine hepmc_event_print (evt)
    type(hepmc_event_t), intent(in) :: evt
    call gen_event_print (evt%obj)
  end subroutine hepmc_event_print

```

Get the event number.

```

<HepMC interface: interfaces>+≡
  interface
    integer(c_int) function gen_event_event_number (evt_obj) bind(C)
      use iso_c_binding !NODEP!
      type(c_ptr), value :: evt_obj
    end function gen_event_event_number
  end interface

```

```

        end function gen_event_event_number
    end interface

    <HepMC interface: public>+≡
        public :: hepmc_event_get_event_index

    <HepMC interface: procedures>+≡
        function hepmc_event_get_event_index (evt) result (i_proc)
            integer :: i_proc
            type(hepmc_event_t), intent(in) :: evt
            i_proc = gen_event_event_number (evt%obj)
        end function hepmc_event_get_event_index

Set the numeric signal process ID

    <HepMC interface: interfaces>+≡
        interface
            subroutine gen_event_set_signal_process_id (evt_obj, proc_id) bind(C)
                import
                type(c_ptr), value :: evt_obj
                integer(c_int), value :: proc_id
            end subroutine gen_event_set_signal_process_id
        end interface

    <HepMC interface: public>+≡
        public :: hepmc_event_set_process_id

    <HepMC interface: procedures>+≡
        subroutine hepmc_event_set_process_id (evt, proc)
            type(hepmc_event_t), intent(in) :: evt
            integer, intent(in) :: proc
            integer(c_int) :: i_proc
            i_proc = proc
            call gen_event_set_signal_process_id (evt%obj, i_proc)
        end subroutine hepmc_event_set_process_id

Get the numeric signal process ID

    <HepMC interface: interfaces>+≡
        interface
            integer(c_int) function gen_event_signal_process_id (evt_obj) bind(C)
                import
                type(c_ptr), value :: evt_obj
            end function gen_event_signal_process_id
        end interface

    <HepMC interface: public>+≡
        public :: hepmc_event_get_process_id

    <HepMC interface: procedures>+≡
        function hepmc_event_get_process_id (evt) result (i_proc)
            integer :: i_proc
            type(hepmc_event_t), intent(in) :: evt
            i_proc = gen_event_signal_process_id (evt%obj)
        end function hepmc_event_get_process_id

```

Set the event energy scale

```
<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_set_event_scale (evt_obj, scale) bind(C)
      import
        type(c_ptr), value :: evt_obj
        real(c_double), value :: scale
    end subroutine gen_event_set_event_scale
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_set_scale

<HepMC interface: procedures>+≡
  subroutine hepmc_event_set_scale (evt, scale)
    type(hepmc_event_t), intent(in) :: evt
    real(default), intent(in) :: scale
    real(c_double) :: cscale
    cscale = scale
    call gen_event_set_event_scale (evt%obj, cscale)
  end subroutine hepmc_event_set_scale
```

Get the event energy scale

```
<HepMC interface: interfaces>+≡
  interface
    real(c_double) function gen_event_event_scale (evt_obj) bind(C)
      import
        type(c_ptr), value :: evt_obj
    end function gen_event_event_scale
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_get_scale

<HepMC interface: procedures>+≡
  function hepmc_event_get_scale (evt) result (scale)
    real(default) :: scale
    type(hepmc_event_t), intent(in) :: evt
    scale = gen_event_event_scale (evt%obj)
  end function hepmc_event_get_scale
```

Set the value of α_{QCD} .

```
<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_set_alpha_qcd (evt_obj, a) bind(C)
      import
        type(c_ptr), value :: evt_obj
        real(c_double), value :: a
    end subroutine gen_event_set_alpha_qcd
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_set_alpha_qcd
```

```

<HepMC interface: procedures>+≡
subroutine hepmc_event_set_alpha_qcd (evt, alpha)
  type(hepmc_event_t), intent(in) :: evt
  real(default), intent(in) :: alpha
  real(c_double) :: a
  a = alpha
  call gen_event_set_alpha_qcd (evt%obj, a)
end subroutine hepmc_event_set_alpha_qcd

```

Get the value of α_{QCD} .

```

<HepMC interface: interfaces>+≡
interface
  real(c_double) function gen_event_alpha_qcd (evt_obj) bind(C)
    import
    type(c_ptr), value :: evt_obj
  end function gen_event_alpha_qcd
end interface

```

```

<HepMC interface: public>+≡
public :: hepmc_event_get_alpha_qcd

```

```

<HepMC interface: procedures>+≡
function hepmc_event_get_alpha_qcd (evt) result (alpha)
  real(default) :: alpha
  type(hepmc_event_t), intent(in) :: evt
  alpha = gen_event_alpha_qcd (evt%obj)
end function hepmc_event_get_alpha_qcd

```

Set the value of α_{QED} .

```

<HepMC interface: interfaces>+≡
interface
  subroutine gen_event_set_alpha_qed (evt_obj, a) bind(C)
    import
    type(c_ptr), value :: evt_obj
    real(c_double), value :: a
  end subroutine gen_event_set_alpha_qed
end interface

```

```

<HepMC interface: public>+≡
public :: hepmc_event_set_alpha_qed

```

```

<HepMC interface: procedures>+≡
subroutine hepmc_event_set_alpha_qed (evt, alpha)
  type(hepmc_event_t), intent(in) :: evt
  real(default), intent(in) :: alpha
  real(c_double) :: a
  a = alpha
  call gen_event_set_alpha_qed (evt%obj, a)
end subroutine hepmc_event_set_alpha_qed

```

Get the value of α_{QED} .

```

<HepMC interface: interfaces>+≡
interface
  real(c_double) function gen_event_alpha_qed (evt_obj) bind(C)

```

```

        import
        type(c_ptr), value :: evt_obj
    end function gen_event_alpha_qed
end interface

<HepMC interface: public>+≡
    public :: hepmc_event_get_alpha_qed

<HepMC interface: procedures>+≡
    function hepmc_event_get_alpha_qed (evt) result (alpha)
        real(default) :: alpha
        type(hepmc_event_t), intent(in) :: evt
        alpha = gen_event_alpha_qed (evt%obj)
    end function hepmc_event_get_alpha_qed

```

Clear a weight value to the end of the weight container.

```

<HepMC interface: interfaces>+≡
    interface
        subroutine gen_event_clear_weights (evt_obj) bind(C)
            use iso_c_binding !NODEP!
            type(c_ptr), value :: evt_obj
        end subroutine gen_event_clear_weights
    end interface

<HepMC interface: public>+≡
    public :: hepmc_event_clear_weights

<HepMC interface: procedures>+≡
    subroutine hepmc_event_clear_weights (evt)
        type(hepmc_event_t), intent(in) :: evt
        call gen_event_clear_weights (evt%obj)
    end subroutine hepmc_event_clear_weights

```

Add a weight value to the end of the weight container.

```

<HepMC interface: interfaces>+≡
    interface
        subroutine gen_event_add_weight (evt_obj, w) bind(C)
            use iso_c_binding !NODEP!
            type(c_ptr), value :: evt_obj
            real(c_double), value :: w
        end subroutine gen_event_add_weight
    end interface

<HepMC interface: public>+≡
    public :: hepmc_event_add_weight

<HepMC interface: procedures>+≡
    subroutine hepmc_event_add_weight (evt, weight)
        type(hepmc_event_t), intent(in) :: evt
        real(default), intent(in) :: weight
        real(c_double) :: w
        w = weight
        call gen_event_add_weight (evt%obj, w)
    end subroutine hepmc_event_add_weight

```


Get the size of the weight container (the number of valid elements).

```

<HepMC interface: interfaces>+≡
  interface
    integer(c_int) function gen_event_weights_size (evt_obj) bind(C)
      use iso_c_binding !NODEP!
      type(c_ptr), value :: evt_obj
    end function gen_event_weights_size
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_get_weights_size

<HepMC interface: procedures>+≡
  function hepmc_event_get_weights_size (evt) result (n)
    integer :: n
    type(hepmc_event_t), intent(in) :: evt
    n = gen_event_weights_size (evt%obj)
  end function hepmc_event_get_weights_size

```

Get the value of the weight with index i. (Count from 1, while C counts from zero.)

```

<HepMC interface: interfaces>+≡
  interface
    real(c_double) function gen_event_weight (evt_obj, i) bind(C)
      use iso_c_binding !NODEP!
      type(c_ptr), value :: evt_obj
      integer(c_int), value :: i
    end function gen_event_weight
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_get_weight

<HepMC interface: procedures>+≡
  function hepmc_event_get_weight (evt, index) result (weight)
    real(default) :: weight
    type(hepmc_event_t), intent(in) :: evt
    integer, intent(in) :: index
    integer(c_int) :: i
    i = index - 1
    weight = gen_event_weight (evt%obj, i)
  end function hepmc_event_get_weight

```

Add a vertex to the event container.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_add_vertex (evt_obj, v_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
      type(c_ptr), value :: v_obj
    end subroutine gen_event_add_vertex
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_add_vertex

```

```

<HepMC interface: procedures>+≡
  subroutine hepmc_event_add_vertex (evt, v)
    type(hepmc_event_t), intent(inout) :: evt
    type(hepmc_vertex_t), intent(in) :: v
    call gen_event_add_vertex (evt%obj, v%obj)
  end subroutine hepmc_event_add_vertex

```

Mark a particular vertex as the signal process (hard interaction).

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_set_signal_process_vertex (evt_obj, v_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
      type(c_ptr), value :: v_obj
    end subroutine gen_event_set_signal_process_vertex
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_set_signal_process_vertex

<HepMC interface: procedures>+≡
  subroutine hepmc_event_set_signal_process_vertex (evt, v)
    type(hepmc_event_t), intent(inout) :: evt
    type(hepmc_vertex_t), intent(in) :: v
    call gen_event_set_signal_process_vertex (evt%obj, v%obj)
  end subroutine hepmc_event_set_signal_process_vertex

```

Set the beam particles explicitly.

```

<HepMC interface: public>+≡
  public :: hepmc_event_set_beam_particles

<HepMC interface: procedures>+≡
  subroutine hepmc_event_set_beam_particles (evt, prt1, prt2)
    type(hepmc_event_t), intent(inout) :: evt
    type(hepmc_particle_t), intent(in) :: prt1, prt2
    logical(c_bool) :: flag
    flag = gen_event_set_beam_particles (evt%obj, prt1%obj, prt2%obj)
  end subroutine hepmc_event_set_beam_particles

```

The C function returns a boolean which we do not use.

```

<HepMC interface: interfaces>+≡
  interface
    logical(c_bool) function gen_event_set_beam_particles &
      (evt_obj, prt1_obj, prt2_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj, prt1_obj, prt2_obj
    end function gen_event_set_beam_particles
  end interface

```

Set the cross section and error explicitly. Note that HepMC uses pb, while WHIZARD uses fb.

```

<HepMC interface: public>+≡
  public :: hepmc_event_set_cross_section

```

```

<HepMC interface: procedures>+≡
  subroutine hepmc_event_set_cross_section (evt, xsec, xsec_err)
    type(hepmc_event_t), intent(inout) :: evt
    real(default), intent(in) :: xsec, xsec_err
    call gen_event_set_cross_section &
      (evt%obj, &
       real (xsec * 1e-3_default, c_double), &
       real (xsec_err * 1e-3_default, c_double))
  end subroutine hepmc_event_set_cross_section

```

The C function returns a boolean which we do not use.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine gen_event_set_cross_section (evt_obj, xs, xs_err) bind(C)
      import
      type(c_ptr), value :: evt_obj
      real(c_double), value :: xs, xs_err
    end subroutine gen_event_set_cross_section
  end interface

```

8.3.9 Event-particle iterator

This iterator iterates over all particles in an event. We store a pointer to the event in addition to the iterator. This allows for simple end checking.

The iterator is actually a constant iterator; it can only read.

```

<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_t

<HepMC interface: types>+≡
  type :: hepmc_event_particle_iterator_t
  private
  type(c_ptr) :: obj
  type(c_ptr) :: evt_obj
  end type hepmc_event_particle_iterator_t

```

Constructor. The iterator is initialized at the first particle in the event.

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function new_event_particle_const_iterator (evt_obj) bind(C)
      import
      type(c_ptr), value :: evt_obj
    end function new_event_particle_const_iterator
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_init

<HepMC interface: procedures>+≡
  subroutine hepmc_event_particle_iterator_init (it, evt)
    type(hepmc_event_particle_iterator_t), intent(out) :: it
    type(hepmc_event_t), intent(in) :: evt
    it%obj = new_event_particle_const_iterator (evt%obj)

```

```

    it%evt_obj = evt%obj
end subroutine hepmc_event_particle_iterator_init

```

Destructor. Necessary because the iterator is allocated on the heap.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine event_particle_const_iterator_delete (it_obj) bind(C)
      import
      type(c_ptr), value :: it_obj
    end subroutine event_particle_const_iterator_delete
  end interface
<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_final
<HepMC interface: procedures>+≡
  subroutine hepmc_event_particle_iterator_final (it)
    type(hepmc_event_particle_iterator_t), intent(inout) :: it
    call event_particle_const_iterator_delete (it%obj)
  end subroutine hepmc_event_particle_iterator_final

```

Increment

```

<HepMC interface: interfaces>+≡
  interface
    subroutine event_particle_const_iterator_advance (it_obj) bind(C)
      import
      type(c_ptr), value :: it_obj
    end subroutine event_particle_const_iterator_advance
  end interface
<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_advance
<HepMC interface: procedures>+≡
  subroutine hepmc_event_particle_iterator_advance (it)
    type(hepmc_event_particle_iterator_t), intent(inout) :: it
    call event_particle_const_iterator_advance (it%obj)
  end subroutine hepmc_event_particle_iterator_advance

```

Reset to the beginning

```

<HepMC interface: interfaces>+≡
  interface
    subroutine event_particle_const_iterator_reset (it_obj, evt_obj) bind(C)
      import
      type(c_ptr), value :: it_obj, evt_obj
    end subroutine event_particle_const_iterator_reset
  end interface
<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_reset
<HepMC interface: procedures>+≡
  subroutine hepmc_event_particle_iterator_reset (it)
    type(hepmc_event_particle_iterator_t), intent(inout) :: it
    call event_particle_const_iterator_reset (it%obj, it%evt_obj)
  end subroutine hepmc_event_particle_iterator_reset

```

Test: return true as long as we are not past the end.

```

<HepMC interface: interfaces>+≡
  interface
    function event_particle_const_iterator_is_valid &
      (it_obj, evt_obj) result (flag) bind(C)
    import
      logical(c_bool) :: flag
      type(c_ptr), value :: it_obj, evt_obj
    end function event_particle_const_iterator_is_valid
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_is_valid

<HepMC interface: procedures>+≡
  function hepmc_event_particle_iterator_is_valid (it) result (flag)
    logical :: flag
    type(hepmc_event_particle_iterator_t), intent(in) :: it
    flag = event_particle_const_iterator_is_valid (it%obj, it%evt_obj)
  end function hepmc_event_particle_iterator_is_valid

```

Return the particle pointed to by the iterator. (The particle object should not be finalized, since it contains merely a pointer to the particle which is owned by the vertex.)

```

<HepMC interface: interfaces>+≡
  interface
    type(c_ptr) function event_particle_const_iterator_get (it_obj) bind(C)
    import
      type(c_ptr), value :: it_obj
    end function event_particle_const_iterator_get
  end interface

<HepMC interface: public>+≡
  public :: hepmc_event_particle_iterator_get

<HepMC interface: procedures>+≡
  function hepmc_event_particle_iterator_get (it) result (prt)
    type(hepmc_particle_t) :: prt
    type(hepmc_event_particle_iterator_t), intent(in) :: it
    prt%obj = event_particle_const_iterator_get (it%obj)
  end function hepmc_event_particle_iterator_get

```

8.3.10 I/O streams

There is a specific I/O stream type for handling the output of GenEvent objects (i.e., Monte Carlo event samples) to file. Opening the file is done by the constructor, closing by the destructor.

```

<HepMC interface: public>+≡
  public :: hepmc_iostream_t

<HepMC interface: types>+≡
  type :: hepmc_iostream_t
  private
    type(c_ptr) :: obj

```

```
end type hepmc_iostream_t
```

Constructor for an output stream associated to a file.

```
<HepMC interface: interfaces>+≡
interface
  type(c_ptr) function new_io_gen_event_out (filename) bind(C)
  import
    character(c_char), dimension(*), intent(in) :: filename
  end function new_io_gen_event_out
end interface

<HepMC interface: public>+≡
public :: hepmc_iostream_open_out

<HepMC interface: procedures>+≡
subroutine hepmc_iostream_open_out (iostream, filename)
  type(hepmc_iostream_t), intent(out) :: iostream
  type(string_t), intent(in) :: filename
  iostream%obj = new_io_gen_event_out (char (filename) // c_null_char)
end subroutine hepmc_iostream_open_out
```

Constructor for an input stream associated to a file.

```
<HepMC interface: interfaces>+≡
interface
  type(c_ptr) function new_io_gen_event_in (filename) bind(C)
  import
    character(c_char), dimension(*), intent(in) :: filename
  end function new_io_gen_event_in
end interface

<HepMC interface: public>+≡
public :: hepmc_iostream_open_in

<HepMC interface: procedures>+≡
subroutine hepmc_iostream_open_in (iostream, filename)
  type(hepmc_iostream_t), intent(out) :: iostream
  type(string_t), intent(in) :: filename
  iostream%obj = new_io_gen_event_in (char (filename) // c_null_char)
end subroutine hepmc_iostream_open_in
```

Destructor:

```
<HepMC interface: interfaces>+≡
interface
  subroutine io_gen_event_delete (io_obj) bind(C)
  import
    type(c_ptr), value :: io_obj
  end subroutine io_gen_event_delete
end interface

<HepMC interface: public>+≡
public :: hepmc_iostream_close
```

```

<HepMC interface: procedures>+≡
  subroutine hepmc_iostream_close (iostream)
    type(hepmc_iostream_t), intent(inout) :: iostream
    call io_gen_event_delete (iostream%obj)
  end subroutine hepmc_iostream_close

```

Write a single event to the I/O stream.

```

<HepMC interface: interfaces>+≡
  interface
    subroutine io_gen_event_write_event (io_obj, evt_obj) bind(C)
      import
      type(c_ptr), value :: io_obj, evt_obj
    end subroutine io_gen_event_write_event
  end interface

<HepMC interface: public>+≡
  public :: hepmc_iostream_write_event

<HepMC interface: procedures>+≡
  subroutine hepmc_iostream_write_event (iostream, evt)
    type(hepmc_iostream_t), intent(inout) :: iostream
    type(hepmc_event_t), intent(in) :: evt
    call io_gen_event_write_event (iostream%obj, evt%obj)
  end subroutine hepmc_iostream_write_event

```

Read a single event from the I/O stream. Return true if successful.

```

<HepMC interface: interfaces>+≡
  interface
    logical(c_bool) function io_gen_event_read_event (io_obj, evt_obj) bind(C)
      import
      type(c_ptr), value :: io_obj, evt_obj
    end function io_gen_event_read_event
  end interface

<HepMC interface: public>+≡
  public :: hepmc_iostream_read_event

<HepMC interface: procedures>+≡
  subroutine hepmc_iostream_read_event (iostream, evt, ok)
    type(hepmc_iostream_t), intent(inout) :: iostream
    type(hepmc_event_t), intent(in) :: evt
    logical, intent(out) :: ok
    ok = io_gen_event_read_event (iostream%obj, evt%obj)
  end subroutine hepmc_iostream_read_event

```

8.3.11 Test

This test example is an abridged version from the build-from-scratch example in the HepMC distribution. We create two vertices for $p \rightarrow q$ PDF splitting, then a vertex for a $qq \rightarrow W^- g$ hard-interaction process, and finally a vertex for $W^- \rightarrow qq$ decay. The setup is for LHC kinematics.

Extending the original example, we set color flow for the incoming quarks and polarization for the outgoing photon. For the latter, we have to define a particle-data object for the photon, so a flavor object can be correctly initialized.

```

<HepMC interface: public>+≡
    public :: hepmc_test

<HepMC interface: procedures>+≡
    subroutine hepmc_test
        type(hepmc_event_t) :: evt
        type(hepmc_vertex_t) :: v1, v2, v3, v4
        type(hepmc_particle_t) :: prt1, prt2, prt3, prt4, prt5, prt6, prt7, prt8
        type(hepmc_iostream_t) :: iostream
        type(flavor_t) :: flv
        type(color_t) :: col
        type(polarization_t) :: pol
        type(particle_data_t), target :: photon_data

        ! Initialize a photon flavor object and some polarization
        call particle_data_init (photon_data, var_str ("PHOTON"), 22)
        call particle_data_set (photon_data, spin_type=VECTOR)
        call particle_data_freeze (photon_data)
        call flavor_init (flv, photon_data)
        call polarization_init_angles &
            (pol, flv, 0.6_default, 1._default, 0.5_default)

        ! Event initialization
        call hepmc_event_init (evt, 20, 1)

        ! $p\to q$ splittings
        call hepmc_vertex_init (v1)
        call hepmc_event_add_vertex (evt, v1)
        call hepmc_vertex_init (v2)
        call hepmc_event_add_vertex (evt, v2)
        call particle_init (prt1, &
            0._default, 0._default, 7000._default, 7000._default, &
            2212, 3)
        call hepmc_vertex_add_particle_in (v1, prt1)
        call particle_init (prt2, &
            0._default, 0._default, -7000._default, 7000._default, &
            2212, 3)
        call hepmc_vertex_add_particle_in (v2, prt2)
        call particle_init (prt3, &
            .750_default, -1.569_default, 32.191_default, 32.238_default, &
            1, 3)
        call color_init_from_array (col, (/501/))
        call hepmc_particle_set_color (prt3, col)
        call hepmc_vertex_add_particle_out (v1, prt3)
        call particle_init (prt4, &
            -3.047_default, -19._default, -54.629_default, 57.920_default, &
            -2, 3)
        call color_init_from_array (col, (/501/))
        call hepmc_particle_set_color (prt4, col)
        call hepmc_vertex_add_particle_out (v2, prt4)

```



```

! Hard interaction
call hepmc_vertex_init (v3)
call hepmc_event_add_vertex (evt, v3)
call hepmc_vertex_add_particle_in (v3, prt3)
call hepmc_vertex_add_particle_in (v3, prt4)
call particle_init (prt6, &
    -3.813_default, 0.113_default, -1.833_default, 4.233_default, &
    22, 1)
call hepmc_particle_set_polarization (prt6, pol)
call hepmc_vertex_add_particle_out (v3, prt6)
call particle_init (prt5, &
    1.517_default, -20.68_default, -20.605_default, 85.925_default, &
    -24, 3)
call hepmc_vertex_add_particle_out (v3, prt5)
call hepmc_event_set_signal_process_vertex (evt, v3)

! $W^-$ decay
call vertex_init_pos (v4, &
    0.12_default, -0.3_default, 0.05_default, 0.004_default)
call hepmc_event_add_vertex (evt, v4)
call hepmc_vertex_add_particle_in (v4, prt5)
call particle_init (prt7, &
    -2.445_default, 28.816_default, 6.082_default, 29.552_default, &
    1, 1)
call hepmc_vertex_add_particle_out (v4, prt7)
call particle_init (prt8, &
    3.962_default, -49.498_default, -26.687_default, 56.373_default, &
    -2, 1)
call hepmc_vertex_add_particle_out (v4, prt8)

! Event output
call hepmc_event_print (evt)
print *, "Writing to file 'hepmc_test.hepmc.dat'"
call hepmc_iostream_open_out (iostream, var_str ("hepmc_test.hepmc.dat"))
call hepmc_iostream_write_event (iostream, evt)
call hepmc_iostream_close (iostream)
print *, "Write completed"

! Wrapup
call polarization_final (pol)
call hepmc_event_final (evt)

contains

subroutine vertex_init_pos (v, x, y, z, t)
    type(hepmc_vertex_t), intent(out) :: v
    real(default), intent(in) :: x, y, z, t
    type(vector4_t) :: xx
    xx = vector4_moving (t, vector3_moving ((/x, y, z/)))
    call hepmc_vertex_init (v, xx)
end subroutine vertex_init_pos

subroutine particle_init (prt, px, py, pz, E, pdg, status)
    type(hepmc_particle_t), intent(out) :: prt

```

```

        real(default), intent(in) :: px, py, pz, E
        integer, intent(in) :: pdg, status
        type(vector4_t) :: p
        p = vector4_moving (E, vector3_moving ((/px, py, pz/)))
        call hepmc_particle_init (prt, p, pdg, status)
    end subroutine particle_init

end subroutine hepmc_test

```

8.4 Particles

This module defines the `particle_t` object type, and the methods and operations that deal with it.

`<particles.f90>`≡
<File header>

```
module particles
```

<Use kinds>

<Use strings>

<Use file utils>

```
    use diagnostics !NODEP!
```

```
    use lorentz !NODEP!
```

```
    use subevents
```

```
    use expressions
```

```
    use models
```

```
    use flavors
```

```
    use colors
```

```
    use helicities
```

```
    use quantum_numbers
```

```
    use state_matrices
```

```
    use interactions
```

```
    use evaluators
```

```
    use polarizations
```

```
    use event_formats
```

```
    use hepmc_interface
```

<Standard module head>

<Particles: public>

<Particles: parameters>

<Particles: types>

<Particles: interfaces>

```
contains
```

<Particles: procedures>

```
end module particles
```

8.4.1 The particle type

Particle status codes

The overall status codes (incoming/outgoing etc.) are inherited from the module `subevents`.

Polarization status:

```
<Particles: parameters>≡
  integer, parameter :: PRT_UNPOLARIZED = 0
  integer, parameter :: PRT_DEFINITE_HELICITY = 1
  integer, parameter :: PRT_GENERIC_POLARIZATION = 2
```

Definition

The quantum numbers are flavor (from which invariant particle properties can be derived), color, and polarization. The particle may be unpolarized. In this case, `hel` and `pol` are unspecified. If it has a definite helicity, the `hel` component is defined. If it has a generic polarization, the `pol` component is defined. For each particle we store the four-momentum and the invariant mass squared, i.e., the squared norm of the four-momentum. There is also an optional list of parent and child particles, for bookkeeping in physical events.

```
<Particles: public>≡
  public :: particle_t

<Particles: types>≡
  type :: particle_t
    private
    integer :: status = PRT_UNDEFINED
    integer :: polarization = PRT_UNPOLARIZED
    type(flavor_t) :: flv
    type(color_t) :: col
    type(helicity_t) :: hel
    type(polarization_t) :: pol
    type(vector4_t) :: p = vector4_null
    real(default) :: p2 = 0
    integer, dimension(:), allocatable :: parent
    integer, dimension(:), allocatable :: child
  end type particle_t
```

Particle initializers:

```
<Particles: interfaces>≡
  interface particle_init
    module procedure particle_init_particle
    module procedure particle_init_state
    module procedure particle_init_hepmc
  end interface
```

Copy a particle. (Deep copy) The excludes the parent-child relations.

(Particles: procedures)≡

```

subroutine particle_init_particle (prt_out, prt_in)
  type(particle_t), intent(out) :: prt_out
  type(particle_t), intent(in) :: prt_in
  prt_out%status = prt_in%status
  prt_out%polarization = prt_in%polarization
  prt_out%flv = prt_in%flv
  prt_out%col = prt_in%col
  prt_out%hel = prt_in%hel
  prt_out%pol = prt_in%pol
  prt_out%p = prt_in%p
  prt_out%p2 = prt_in%p2
end subroutine particle_init_particle

```

Initialize a particle using a single-particle state matrix which determines flavor, color, and polarization. The state matrix must have unique flavor and color. The factorization mode determines whether the particle is unpolarized, has definite helicity, or generic polarization. This mode is translated into the polarization status.

(Particles: procedures)+≡

```

subroutine particle_init_state (prt, state, status, mode)
  type(particle_t), intent(out) :: prt
  type(state_matrix_t), intent(in) :: state
  integer, intent(in) :: status, mode
  type(state_iterator_t) :: it
  prt%status = status
  call state_iterator_init (it, state)
  prt%flv = state_iterator_get_flavor (it, 1)
  if (flavor_is_beam_remnant (prt%flv)) prt%status = PRT_BEAM_REMNANT
  prt%col = state_iterator_get_color (it, 1)
  select case (mode)
    case (FM_SELECT_HELICITY)
      prt%hel = state_iterator_get_helicity (it, 1)
      prt%polarization = PRT_DEFINITE_HELICITY
    case (FM_FACTOR_HELICITY)
      call polarization_init_state_matrix (prt%pol, state)
      prt%polarization = PRT_GENERIC_POLARIZATION
  end select
end subroutine particle_init_state

```

Initialize a particle from a HepMC particle object. The model is necessary for making a fully qualified flavor component. We have the additional flag **polarized** which tells whether the polarization information should be interpreted or ignored, and the lookup array of barcodes. Note that the lookup array is searched linearly, a possible bottleneck for large particle arrays. If necessary, the barcode array could be replaced by a hash table.

(Particles: procedures)+≡

```

subroutine particle_init_hepmc (prt, hprt, model, polarization, barcode)
  type(particle_t), intent(out) :: prt
  type(hepmc_particle_t), intent(in) :: hprt
  type(model_t), intent(in), target :: model

```

```

integer, intent(in) :: polarization
integer, dimension(:), intent(in) :: barcode
type(hepmc_polarization_t) :: hpol
integer :: n_parents, n_children
integer, dimension(:), allocatable :: parent_barcode, child_barcode
integer :: i
select case (hepmc_particle_get_status (hpert))
case (1); prt%status = PRT_OUTGOING
case (2); prt%status = PRT_RESONANT
case (3); prt%status = PRT_VIRTUAL
end select
call flavor_init (prt%flv, hepmc_particle_get_pdg (hpert), model)
if (flavor_is_beam_remnant (prt%flv)) prt%status = PRT_BEAM_REMNANT
call color_init (prt%col, hepmc_particle_get_color (hpert))
prt%polarization = polarization
select case (polarization)
case (PRT_DEFINITE_HELICITY)
    hpol = hepmc_particle_get_polarization (hpert)
    call hepmc_polarization_to_hel (hpert, prt%flv, prt%hel)
    call hepmc_polarization_final (hpert)
case (PRT_GENERIC_POLARIZATION)
    hpol = hepmc_particle_get_polarization (hpert)
    call hepmc_polarization_to_pol (hpert, prt%flv, prt%pol)
    call hepmc_polarization_final (hpert)
end select
prt%p = hepmc_particle_get_momentum (hpert)
prt%p2 = hepmc_particle_get_mass_squared (hpert)
n_parents = hepmc_particle_get_n_parents (hpert)
n_children = hepmc_particle_get_n_children (hpert)
allocate (parent_barcode (n_parents), prt%parent (n_parents))
allocate (child_barcode (n_children), prt%child (n_children))
parent_barcode = hepmc_particle_get_parent_barcodes (hpert)
child_barcode = hepmc_particle_get_child_barcodes (hpert)
do i = 1, size (barcode)
    where (parent_barcode == barcode(i)) prt%parent = i
    where (child_barcode == barcode(i)) prt%child = i
end do
if (prt%status == PRT_VIRTUAL .and. n_parents == 0) &
    prt%status = PRT_INCOMING
end subroutine particle_init_hepmc

```

Finalizer. The polarization component has pointers allocated.

```

<Particles: procedures>+≡
    elemental subroutine particle_final (prt)
        type(particle_t), intent(inout) :: prt
        call polarization_final (prt%pol)
    end subroutine particle_final

```

I/O

```

<Particles: public>+≡
    public :: particle_write

```

(Particles: procedures)+≡

```

subroutine particle_write (prt, unit)
  type(particle_t), intent(in) :: prt
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  select case (prt%status)
  case (PRT_UNDEFINED); write (u, "(1x, A)", advance="no") "[-]"
  case (PRT_BEAM);       write (u, "(1x, A)", advance="no") "[b]"
  case (PRT_INCOMING);   write (u, "(1x, A)", advance="no") "[i]"
  case (PRT_OUTGOING);   write (u, "(1x, A)", advance="no") "[o]"
  case (PRT_VIRTUAL);     write (u, "(1x, A)", advance="no") "[v]"
  case (PRT_RESONANT);    write (u, "(1x, A)", advance="no") "[r]"
  case (PRT_BEAM_REMNANT); write (u, "(1x, A)", advance="no") "[x]"
  end select
  write (u, "(1x)", advance="no")
  call flavor_write (prt%flv, unit)
  call color_write (prt%col, unit)
  select case (prt%polarization)
  case (PRT_DEFINITE_HELICITY)
    call helicity_write (prt%hel, unit)
    write (u, *)
  case (PRT_GENERIC_POLARIZATION)
    write (u, *)
    call polarization_write (prt%pol, unit)
  case default
    write (u, *)
  end select
  write (u, *) "Momentum:"
  call vector4_write (prt%p, unit)
  write (u, "(1x,A)", advance="no") "T = "
  write (u, *) prt%p2
  if (allocated (prt%parent)) then
    if (size (prt%parent) /= 0) then
      write (u, "(1x,A,40(1x,I0))") "Parents: ", prt%parent
    end if
  end if
  if (allocated (prt%child)) then
    if (size (prt%child) /= 0) then
      write (u, "(1x,A,40(1x,I0))") "Children:", prt%child
    end if
  end if
end subroutine particle_write

```

Binary I/O:

(Particles: procedures)+≡

```

subroutine particle_write_raw (prt, u)
  type(particle_t), intent(in) :: prt
  integer, intent(in) :: u
  write (u) prt%status, prt%polarization
  call flavor_write_raw (prt%flv, u)
  call color_write_raw (prt%col, u)
  select case (prt%polarization)

```

```

case (PRT_DEFINITE_HELICITY)
  call helicity_write_raw (prt%hel, u)
case (PRT_GENERIC_POLARIZATION)
  call polarization_write_raw (prt%pol, u)
end select
call vector4_write_raw (prt%p, u)
write (u) prt%p2
write (u) allocated (prt%parent)
if (allocated (prt%parent)) then
  write (u) size (prt%parent)
  write (u) prt%parent
end if
write (u) allocated (prt%child)
if (allocated (prt%child)) then
  write (u) size (prt%child)
  write (u) prt%child
end if
end subroutine particle_write_raw

subroutine particle_read_raw (prt, u, iostat)
  type(particle_t), intent(out) :: prt
  integer, intent(in) :: u
  integer, intent(out) :: iostat
  logical :: allocated_parent, allocated_child
  integer :: size_parent, size_child
  read (u, iostat=iostat) prt%status, prt%polarization
  call flavor_read_raw (prt%flv, u, iostat=iostat)
  call color_read_raw (prt%col, u, iostat=iostat)
  select case (prt%polarization)
  case (PRT_DEFINITE_HELICITY)
    call helicity_read_raw (prt%hel, u, iostat=iostat)
  case (PRT_GENERIC_POLARIZATION)
    call polarization_read_raw (prt%pol, u, iostat=iostat)
  end select
  call vector4_read_raw (prt%p, u, iostat=iostat)
  read (u, iostat=iostat) prt%p2
  read (u, iostat=iostat) allocated_parent
  if (allocated_parent) then
    read (u, iostat=iostat) size_parent
    allocate (prt%parent (size_parent))
    read (u, iostat=iostat) prt%parent
  end if
  read (u, iostat=iostat) allocated_child
  if (allocated_child) then
    read (u, iostat=iostat) size_child
    allocate (prt%child (size_child))
    read (u, iostat=iostat) prt%child
  end if
end subroutine particle_read_raw

```

Transform a particle into a `hepmc_particle` object, including color and polarization. The HepMC status is equivalent to the HEPEVT status, in particular: 0 = null entry, 1 = physical particle, 2 = decayed/fragmented SM hadron, tau

or muon, 3 = other unphysical particle entry, 4 = incoming particles, 11 = intermediate resonance such as squarks. The use of 11 for intermediate resonances is as done by HERWIG, see <http://herwig.hepforge.org/trac/wiki/FaQs>.

(Particles: procedures)+≡

```
subroutine particle_to_hepmc (prt, hpert)
  type(particle_t), intent(in) :: prt
  type(hepmc_particle_t), intent(out) :: hpert
  integer :: hepmc_status
  select case (prt%status)
  case (PRT_UNDEFINED)
    hepmc_status = 0
  case (PRT_OUTGOING)
    hepmc_status = 1
  case (PRT_BEAM)
    hepmc_status = 4
  case (PRT_RESONANT)
    if(abs(particle_get_pdg(prt)) == 13 .or. &
       abs(particle_get_pdg(prt)) == 15) then
      hepmc_status = 2
    else
      hepmc_status = 11
    end if
  case default
    hepmc_status = 3
  end select
  call hepmc_particle_init &
    (hpert, prt%p, flavor_get_pdg (prt%flv), hepmc_status)
  call hepmc_particle_set_color (hpert, prt%col)
  select case (prt%polarization)
  case (PRT_DEFINITE_HELICITY)
    call hepmc_particle_set_polarization (hpert, prt%hel)
  case (PRT_GENERIC_POLARIZATION)
    call hepmc_particle_set_polarization (hpert, prt%pol)
  end select
end subroutine particle_to_hepmc
```

Setting contents

Reset the status code.

(Particles: public)+≡

```
public :: particle_reset_status
```

(Particles: procedures)+≡

```
elemental subroutine particle_reset_status (prt, status)
  type(particle_t), intent(inout) :: prt
  integer, intent(in) :: status
  prt%status = status
end subroutine particle_reset_status
```

The color can be given explicitly.

(Particles: public)+≡

```
public :: particle_set_color
```



```

<Particles: procedures>+≡
  elemental subroutine particle_set_color (prt, col)
    type(particle_t), intent(inout) :: prt
    type(color_t), intent(in) :: col
    prt%col = col
  end subroutine particle_set_color

```

The flavor can be given explicitly.

```

<Particles: public>+≡
  public :: particle_set_flavor

<Particles: procedures>+≡
  subroutine particle_set_flavor (prt, flv)
    type(particle_t), intent(inout) :: prt
    type(flavor_t), intent(in) :: flv
    prt%flv = flv
  end subroutine particle_set_flavor

```

The momentum is set independent of the quantum numbers.

```

<Particles: public>+≡
  public :: particle_set_momentum

<Particles: procedures>+≡
  elemental subroutine particle_set_momentum (prt, p)
    type(particle_t), intent(inout) :: prt
    type(vector4_t), intent(in) :: p
    prt%p = p
    prt%p2 = p ** 2
  end subroutine particle_set_momentum

```

Set resonance information. This should be done after momentum assignment, because we need to know whether the particle is spacelike or timelike. The resonance flag is defined only for virtual particles.

```

<Particles: procedures>+≡
  elemental subroutine particle_set_resonance_flag (prt, resonant)
    type(particle_t), intent(inout) :: prt
    logical, intent(in) :: resonant
    select case (prt%status)
    case (PRT_VIRTUAL)
      if (resonant) prt%status = PRT_RESONANT
    end select
  end subroutine particle_set_resonance_flag

```

Set children and parents information.

```

<Particles: public>+≡
  public :: particle_set_children
  public :: particle_set_parents

<Particles: procedures>+≡
  subroutine particle_set_children (prt, idx)
    type(particle_t), intent(inout) :: prt
    integer, dimension(:), intent(in) :: idx
    if (allocated (prt%child)) deallocate (prt%child)

```

```

        allocate (prt%child (count (idx /= 0)))
        prt%child = pack (idx, idx /= 0)
    end subroutine particle_set_children

    subroutine particle_set_parents (prt, idx)
        type(particle_t), intent(inout) :: prt
        integer, dimension(:), intent(in) :: idx
        if (allocated (prt%parent)) deallocate (prt%parent)
        allocate (prt%parent (count (idx /= 0)))
        prt%parent = pack (idx, idx /= 0)
    end subroutine particle_set_parents

```

Accessing contents

The status code.

```

(Particles: public) +=
    public :: particle_get_status

(Particles: procedures) +=
    elemental function particle_get_status (prt) result (status)
        integer :: status
        type(particle_t), intent(in) :: prt
        status = prt%status
    end function particle_get_status

```

Return true if the status is either INCOMING, OUTGOING or RESONANT. BEAM is kept, if keep_beams is set true.

```

(Particles: procedures) +=
    elemental function particle_is_real (prt, keep_beams) result (flag)
        logical :: flag, kb
        type(particle_t), intent(in) :: prt
        logical, intent(in), optional :: keep_beams
        kb = .false.
        if (present (keep_beams)) kb = keep_beams
        select case (prt%status)
        case (PRT_INCOMING, PRT_OUTGOING, PRT_RESONANT)
            flag = .true.
        case (PRT_BEAM)
            flag = kb
        case default
            flag = .false.
        end select
    end function particle_is_real

```

Polarization status.

```

(Particles: procedures) +=
    elemental function particle_get_polarization_status (prt) result (status)
        integer :: status
        type(particle_t), intent(in) :: prt
        status = prt%polarization
    end function particle_get_polarization_status

```

Return the PDG code from the flavor component directly.

```
<Particles: public>+≡
  public :: particle_get_pdg

<Particles: procedures>+≡
  elemental function particle_get_pdg (prt) result (pdg)
    integer :: pdg
    type(particle_t), intent(in) :: prt
    pdg = flavor_get_pdg (prt%flv)
  end function particle_get_pdg
```

Return the color and anticolor quantum numbers.

```
<Particles: public>+≡
  public :: particle_get_color

<Particles: procedures>+≡
  function particle_get_color (prt) result (col)
    integer, dimension(2) :: col
    type(particle_t), intent(in) :: prt
    col(1) = color_get_col (prt%col)
    col(2) = color_get_acl (prt%col)
  end function particle_get_color
```

Return the polarization density matrix (as a shallow copy).

```
<Particles: procedures>+≡
  function particle_get_polarization (prt) result (pol)
    type(polarization_t) :: pol
    type(particle_t), intent(in) :: prt
    pol = prt%pol
  end function particle_get_polarization
```

Return the helicity (if defined and diagonal).

```
<Particles: procedures>+≡
  function particle_get_helicity (prt) result (hel)
    integer :: hel
    integer, dimension(2) :: hel_arr
    type(particle_t), intent(in) :: prt
    hel = 0
    if (helicity_is_defined (prt%hel) .and. &
        helicity_is_diagonal (prt%hel)) then
      hel_arr = helicity_get (prt%hel)
      hel = hel_arr (1)
    end if
  end function particle_get_helicity
```

Return the number of children/parents

```
<Particles: public>+≡
  public :: particle_get_n_parents

<Particles: procedures>+≡
  function particle_get_n_parents (prt) result (n)
    integer :: n
    type(particle_t), intent(in) :: prt
```

```

        if (allocated (prt%parent)) then
            n = size (prt%parent)
        else
            n = 0
        end if
    end function particle_get_n_parents

function particle_get_n_children (prt) result (n)
    integer :: n
    type(particle_t), intent(in) :: prt
    if (allocated (prt%child)) then
        n = size (prt%child)
    else
        n = 0
    end if
end function particle_get_n_children

```

Return the array of parents/children.

```

(Particles: public) +=
    public :: particle_get_parents

(Particles: procedures) +=
    function particle_get_parents (prt) result (parent)
        type(particle_t), intent(in) :: prt
        integer, dimension(:), allocatable :: parent
        if (allocated (prt%parent)) then
            allocate (parent (size (prt%parent)))
            parent = prt%parent
        else
            allocate (parent (0))
        end if
    end function particle_get_parents

    function particle_get_children (prt) result (child)
        type(particle_t), intent(in) :: prt
        integer, dimension(:), allocatable :: child
        if (allocated (prt%child)) then
            allocate (child (size (prt%child)))
            child = prt%child
        else
            allocate (child (0))
        end if
    end function particle_get_children

```

Return momentum and momentum squared.

```

(Particles: public) +=
    public :: particle_get_momentum

(Particles: procedures) +=
    function particle_get_momentum (prt) result (p)
        type(vector4_t) :: p
        type(particle_t), intent(in) :: prt
        p = prt%p
    end function particle_get_momentum

```

```

function particle_get_p2 (prt) result (p2)
  real(default) :: p2
  type(particle_t), intent(in) :: prt
  p2 = prt%p2
end function particle_get_p2

```

8.4.2 Particle sets

A particle set is what is usually called an event: an array of particles. The individual particle entries carry momentum, quantum numbers, polarization, and optionally connections. There is (also optionally) a correlated state-density matrix that maintains spin correlations that are lost in the individual particle entries.

```

<Particles: public>+≡
  public :: particle_set_t

<Particles: types>+≡
  type :: particle_set_t
    private
    integer :: n_beam = 0
    integer :: n_in  = 0
    integer :: n_vir = 0
    integer :: n_out = 0
    integer :: n_tot = 0
    type(particle_t), dimension(:), allocatable :: prt
    type(state_matrix_t) :: correlated_state
  end type particle_set_t

```

A particle set can be initialized from an interaction or from a HepMC event record.

```

<Particles: public>+≡
  public :: particle_set_init

<Particles: interfaces>+≡
  interface particle_set_init
    module procedure particle_set_init_interaction
    module procedure particle_set_init_hepmc
  end interface

```

When a particle set is initialized from a given interaction, we have to determine the branch within the original state matrix that fixes the particle quantum numbers. This is done with the appropriate probabilities, based on a random number `x`. The `mode` determines whether the individual particles become unpolarized, or take a definite (diagonal) helicity, or acquire single-particle polarization matrices. The flag `keep_correlations` tells whether the spin-correlation matrix is to be calculated and stored in addition to the particles. The flag `keep_virtual` tells whether virtual particles should be dropped. Note that if virtual particles are dropped, the spin-correlation matrix makes no sense, and parent-child relations are not set.

For a correct disentangling of color and flavor (in the presence of helicity), we consider two interactions. `int` has no color information, and is used to select a flavor state. Consequently, we trace over helicities here. `int_flows` contains color-flow and potentially helicity information, but is useful only after the flavor combination has been chosen. So this interaction is used to select helicity and color, but restricted to the selected flavor combination.

`int` and `int_flows` may be identical if there is only a single (or no) color flow. If there is just a single flavor combination, `x(1)` can be set to zero.

The current algorithm of evaluator convolution requires that the beam particles are assumed outgoing (in the beam interaction) and become virtual in all derived interactions. In the particle set they should be re-identified as incoming. The optional integer `n_incoming` can be used to perform this correction.

The flag `is_valid` is false if factorization of the state is not possible, in particular if the squared matrix element is zero.

(Particles: procedures)+≡

```
subroutine particle_set_init_interaction &
  (particle_set, is_valid, int, int_flows, mode, x, &
   keep_correlations, keep_virtual, n_incoming)
  type(particle_set_t), intent(out) :: particle_set
  logical, intent(out) :: is_valid
  type(interaction_t), intent(in), target :: int, int_flows
  integer, intent(in) :: mode
  real(default), dimension(2), intent(in) :: x
  logical, intent(in) :: keep_correlations, keep_virtual
  integer, intent(in), optional :: n_incoming
  type(state_matrix_t), dimension(:), allocatable, target :: flavor_state
  type(state_matrix_t), dimension(:), allocatable, target :: single_state
  integer :: n_in, n_vir, n_out, n_tot
  type(quantum_numbers_t), dimension(:,:), allocatable :: qn
  logical :: ok
  integer :: i, j
  if (present (n_incoming)) then
    n_in = n_incoming
    n_vir = interaction_get_n_vir (int) - n_incoming
  else
    n_in = interaction_get_n_in (int)
    n_vir = interaction_get_n_vir (int)
  end if
  n_out = interaction_get_n_out (int)
  n_tot = interaction_get_n_tot (int)
  particle_set%n_in = n_in
  particle_set%n_out = n_out
  if (keep_virtual) then
    particle_set%n_vir = n_vir
    particle_set%n_tot = n_tot
  else
    particle_set%n_vir = 0
    particle_set%n_tot = n_in + n_out
  end if
  call interaction_factorize &
    (int, FM_IGNORE_HELICITY, x(1), is_valid, flavor_state)
  allocate (qn (n_tot,1))
  do i = 1, n_tot
```

```

        qn(i,:) = state_matrix_get_quantum_numbers (flavor_state(i), 1)
    end do
    if (keep_correlations .and. keep_virtual) then
        call interaction_factorize (int_flows, mode, x(2), ok, &
            single_state, particle_set%correlated_state, qn(:,1))
    else
        call interaction_factorize (int_flows, mode, x(2), ok, &
            single_state, qn_in=qn(:,1))
    end if
    is_valid = is_valid .and. ok
    allocate (particle_set%prt (particle_set%n_tot))
    j = 1
    do i = 1, n_tot
        if (i <= n_in) then
            call particle_init &
                (particle_set%prt(j), single_state(i), PRT_INCOMING, mode)
        else if (i <= n_in + n_vir) then
            if (.not. keep_virtual) cycle
            call particle_init &
                (particle_set%prt(j), single_state(i), PRT_VIRTUAL, mode)
        else
            call particle_init &
                (particle_set%prt(j), single_state(i), PRT_OUTGOING, mode)
        end if
        call particle_set_momentum &
            (particle_set%prt(j), interaction_get_momentum (int, i))
        if (keep_virtual) then
            call particle_set_children &
                (particle_set%prt(j), interaction_get_children (int, i))
            call particle_set_parents &
                (particle_set%prt(j), interaction_get_parents (int, i))
        end if
        j = j + 1
    end do
    if (keep_virtual) then
        call particle_set_resonance_flag &
            (particle_set%prt, interaction_get_resonance_flags (int))
    end if
    call state_matrix_final (flavor_state)
    call state_matrix_final (single_state)
end subroutine particle_set_init_interaction

```

If a particle set is initialized from a HepMC event record, we have to specify the treatment of polarization (unpolarized or density matrix) which is common to all particles. Correlated polarization information is not available.

(Particles: procedures)+≡

```

subroutine particle_set_init_hepmc (particle_set, evt, model, polarization)
    type(particle_set_t), intent(out) :: particle_set
    type(hepmc_event_t), intent(in) :: evt
    type(model_t), intent(in), target :: model
    integer, intent(in) :: polarization
    type(hepmc_event_particle_iterator_t) :: it
    type(hepmc_particle_t) :: prt

```

```

integer, dimension(:), allocatable :: barcode
integer :: n_tot, i
n_tot = 0
call hepmc_event_particle_iterator_init (it, evt)
do while (hepmc_event_particle_iterator_is_valid (it))
    n_tot = n_tot + 1
    call hepmc_event_particle_iterator_advance (it)
end do
allocate (barcode (n_tot))
call hepmc_event_particle_iterator_reset (it)
do i = 1, n_tot
    barcode(i) = hepmc_particle_get_barcode &
        (hepmc_event_particle_iterator_get (it))
    call hepmc_event_particle_iterator_advance (it)
end do
allocate (particle_set%prt (n_tot))
call hepmc_event_particle_iterator_reset (it)
do i = 1, n_tot
    prt = hepmc_event_particle_iterator_get (it)
    call particle_init (particle_set%prt(i), &
        prt, model, polarization, barcode)
    call hepmc_event_particle_iterator_advance (it)
end do
call hepmc_event_particle_iterator_final (it)
particle_set%n_tot = n_tot
particle_set%n_beam = &
    count (particle_get_status (particle_set%prt) == PRT_BEAM)
particle_set%n_in = &
    count (particle_get_status (particle_set%prt) == PRT_INCOMING)
particle_set%n_out = &
    count (particle_get_status (particle_set%prt) == PRT_OUTGOING)
particle_set%n_vir = &
    particle_set%n_tot - particle_set%n_in - particle_set%n_out
end subroutine particle_set_init_hepmc

```

Pointer components are hidden inside the particle polarization, and in the correlated state matrix.

(Particles: public)+≡

```
public :: particle_set_final
```

(Particles: procedures)+≡

```

subroutine particle_set_final (particle_set)
    type(particle_set_t), intent(inout) :: particle_set
    if (allocated (particle_set%prt)) then
        call particle_final (particle_set%prt)
        deallocate(particle_set%prt)
    end if
    call state_matrix_final (particle_set%correlated_state)
end subroutine particle_set_final

```

Output (default format)

(Particles: public)+≡

```
public :: particle_set_write
```


(Particles: procedures)+≡

```

subroutine particle_set_write (particle_set, unit)
  type(particle_set_t), intent(in) :: particle_set
  integer, intent(in), optional :: unit
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, "(1x,A)") "Particle set:"
  if (particle_set%n_tot /= 0) then
    do i = 1, particle_set%n_tot
      write (u, "(1x,A,1x,I0)", advance="no") "Particle", i
      call particle_write (particle_set%prt(i), u)
    end do
    if (state_matrix_is_defined (particle_set%correlated_state)) then
      write (u, *) "Correlated state density matrix:"
      call state_matrix_write (particle_set%correlated_state, u)
    end if
  else
    write (u, "(3x,A)") "[empty]"
  end if
end subroutine particle_set_write

```

8.4.3 I/O formats

Here, we define input/output of particle sets in various formats. This is the right place since particle sets contain most of the event information.

All write/read routines take as first argument the object, as second argument the I/O unit which in this case is a mandatory argument. Then follow further event data.

Internal binary format

This format is supposed to contain the complete information, so the particle data set can be fully reconstructed. The exception is the model part of the particle flavors; this is unassigned for the flavor values read from file.

(Particles: public)+≡

```

public :: particle_set_write_raw
public :: particle_set_read_raw

```

(Particles: procedures)+≡

```

subroutine particle_set_write_raw (particle_set, u)
  type(particle_set_t), intent(in) :: particle_set
  integer, intent(in) :: u
  integer :: i
  write (u) &
    particle_set%n_beam, particle_set%n_in, &
    particle_set%n_vir, particle_set%n_out
  write (u) particle_set%n_tot
  do i = 1, particle_set%n_tot
    call particle_write_raw (particle_set%prt(i), u)
  end do
  call state_matrix_write_raw (particle_set%correlated_state, u)
end subroutine particle_set_write_raw

```

```

subroutine particle_set_read_raw (particle_set, u, iostat)
  type(particle_set_t), intent(out) :: particle_set
  integer, intent(in) :: u
  integer, intent(out) :: iostat
  integer :: i
  read (u, iostat=iostat) &
    particle_set%n_beam, particle_set%n_in, &
    particle_set%n_vir, particle_set%n_out
  read (u, iostat=iostat) particle_set%n_tot
  allocate (particle_set%prt (particle_set%n_tot))
  do i = 1, size (particle_set%prt)
    call particle_read_raw (particle_set%prt(i), u, iostat=iostat)
  end do
  call state_matrix_read_raw (particle_set%correlated_state, u, iostat=iostat)
end subroutine particle_set_read_raw

```

Les Houches event format

This format consists of two common blocks and a file format. The actual interface is put in a separate module `event_formats`.

We first create a new particle set that contains only the particles that are supported by the LHEF format. These are: beam, incoming, resonant, outgoing. We drop particles with unknown, virtual or beam-remnant status.

From this set we fill the common block. Event information such as process ID and weight is not transferred here; this has to be done by the caller. The spin information is set only if the particle has a unique mother, and if its polarization is fully defined.

```

<Particles: public>+≡
  public :: particle_set_fill_hepeup

<Particles: procedures>+≡
  subroutine particle_set_fill_hepeup (particle_set, keep_beams)
    type(particle_set_t), intent(in), target :: particle_set
    logical, intent(in), optional :: keep_beams
    type(particle_t), pointer :: prt
    type(particle_set_t), target :: pset_hepevt
    integer :: i, n_parents
    integer, dimension(1) :: i_mother
    call particle_set_to_hepevt_form (particle_set, pset_hepevt, keep_beams)
    call hepeup_init (pset_hepevt%n_tot)
    do i = 1, pset_hepevt%n_tot
      prt => pset_hepevt%prt(i)
      call hepeup_set_particle (i, &
        particle_get_pdg (prt), &
        particle_get_status (prt), &
        particle_get_parents (prt), &
        particle_get_color (prt), &
        particle_get_momentum (prt), &
        particle_get_p2 (prt))
      n_parents = particle_get_n_parents (prt)
      if (n_parents == 1) then

```

```

        i_mother = particle_get_parents (prt)
        select case (particle_get_polarization_status (prt))
        case (PRT_GENERIC_POLARIZATION)
            call hepeup_set_particle_spin (i, &
                particle_get_momentum (prt), &
                particle_get_polarization (prt), &
                particle_get_momentum (pset_hepevt%prt(i_mother(1))))
        end select
    end if
end do
call particle_set_final (pset_hepevt)
end subroutine particle_set_fill_hepeup

```

The HEPEVT common block is quite similar, but does contain less information, e.g. no color flows (it was LEP time). The spin information is set only if the particle has a unique mother, and if its polarization is fully defined.

```

<Particles: public>+≡
    public :: particle_set_fill_hepevt

<Particles: procedures>+≡
    subroutine particle_set_fill_hepevt (particle_set, keep_beams)
        type(particle_set_t), intent(in), target :: particle_set
        type(particle_t), pointer :: prt
        type(particle_set_t), target :: pset_hepevt
        logical, intent(in), optional :: keep_beams
        integer :: i
        call particle_set_to_hepevt_form (particle_set, pset_hepevt, keep_beams)
        call hepevt_init (pset_hepevt%n_tot, pset_hepevt%n_out)
        do i = 1, pset_hepevt%n_tot
            prt => pset_hepevt%prt(i)
            call hepevt_set_particle (i, &
                particle_get_pdg (prt), &
                particle_get_status (prt), &
                particle_get_parents (prt), &
                particle_get_children (prt), &
                particle_get_momentum (prt), &
                particle_get_p2 (prt), &
                particle_get_helicity (prt))
        end do
        call particle_set_final (pset_hepevt)
    end subroutine particle_set_fill_hepevt

```

HepMC format

The master output function fills a HepMC GenEvent object that is already initialized, but has no vertices in it.

We first set up the vertex lists and enter the vertices into the HepMC event. Then, we assign first all incoming particles and then all outgoing particles to their associated vertices. Particles which have neither parent nor children entries (this should not happen) are dropped.

Finally, we insert the beam particles. If there are none, use the incoming particles instead.

(Particles: public)+≡

public :: particle_set_fill_hepmc_event

(Particles: procedures)+≡

```
subroutine particle_set_fill_hepmc_event (particle_set, evt)
  type(particle_set_t), intent(in) :: particle_set
  type(hepmc_event_t), intent(inout) :: evt
  type(hepmc_vertex_t), dimension(:), allocatable :: v
  type(hepmc_particle_t), dimension(:), allocatable :: hp
  type(hepmc_particle_t), dimension(2) :: hbeam
  logical, dimension(:), allocatable :: is_beam
  integer, dimension(:), allocatable :: v_from, v_to
  integer :: n_vertices, n_tot, i
  n_tot = particle_set%n_tot
  allocate (v_from (n_tot), v_to (n_tot))
  call particle_set_assign_vertices (particle_set, v_from, v_to, n_vertices)
  allocate (v (n_vertices))
  do i = 1, n_vertices
    call hepmc_vertex_init (v(i))
    call hepmc_event_add_vertex (evt, v(i))
  end do
  allocate (hp (n_tot))
  do i = 1, n_tot
    if (v_to(i) /= 0 .or. v_from(i) /= 0) then
      call particle_to_hepmc (particle_set%prt(i), hp(i))
    end if
  end do
  allocate (is_beam (n_tot))
  is_beam = particle_get_status (particle_set%prt(1:n_tot)) == PRT_BEAM
  if (.not. any (is_beam)) then
    is_beam = particle_get_status (particle_set%prt(1:n_tot)) == PRT_INCOMING
  end if
  if (count (is_beam) == 2) then
    hbeam = pack (hp, is_beam)
    call hepmc_event_set_beam_particles (evt, hbeam(1), hbeam(2))
  end if
  do i = 1, n_tot
    if (v_to(i) /= 0) then
      call hepmc_vertex_add_particle_in (v(v_to(i)), hp(i))
    end if
  end do
  do i = 1, n_tot
    if (v_from(i) /= 0) then
      call hepmc_vertex_add_particle_out (v(v_from(i)), hp(i))
    end if
  end do
end subroutine particle_set_fill_hepmc_event
```

Get contents

Find parents/children of a particular particle recursively; the search terminates if a parent/child has status BEAM, INCOMING, OUTGOING or RESONANT.

(*Particles: procedures*) +=

```
function particle_set_get_real_parents (pset, i, keep_beams) result (parent)
  integer, dimension(:), allocatable :: parent
  type(particle_set_t), intent(in) :: pset
  integer, intent(in) :: i
  logical, intent(in), optional :: keep_beams
  logical, dimension(:), allocatable :: is_real
  logical, dimension(:), allocatable :: is_parent, is_real_parent
  logical :: kb
  integer :: j, k
  kb = .false.
  if (present (keep_beams)) kb = keep_beams
  allocate (is_real (pset%n_tot))
  is_real = particle_is_real (pset%prt, kb)
  allocate (is_parent (pset%n_tot), is_real_parent (pset%n_tot))
  is_real_parent = .false.
  is_parent = .false.
  is_parent(particle_get_parents(pset%prt(i))) = .true.
  do while (any (is_parent))
    where (is_real .and. is_parent)
      is_real_parent = .true.
      is_parent = .false.
    end where
    mark_next_parent: do j = size (is_parent), 1, -1
      if (is_parent(j)) then
        is_parent(particle_get_parents(pset%prt(j))) = .true.
        is_parent(j) = .false.
        exit mark_next_parent
      end if
    end do mark_next_parent
  end do
  allocate (parent (count (is_real_parent)))
  j = 0
  do k = 1, size (is_parent)
    if (is_real_parent(k)) then
      j = j + 1
      parent(j) = k
    end if
  end do
end function particle_set_get_real_parents

function particle_set_get_real_children (pset, i, keep_beams) result (child)
  integer, dimension(:), allocatable :: child
  type(particle_set_t), intent(in) :: pset
  integer, intent(in) :: i
  logical, dimension(:), allocatable :: is_real
  logical, dimension(:), allocatable :: is_child, is_real_child
  logical, intent(in), optional :: keep_beams
  integer :: j, k
  logical :: kb
```

```

kb = .false.
if (present (keep_beams)) kb = keep_beams
allocate (is_real (pset%n_tot))
is_real = particle_is_real (pset%prt, kb)
allocate (is_child (pset%n_tot), is_real_child (pset%n_tot))
is_real_child = .false.
is_child = .false.
is_child(particle_get_children(pset%prt(i))) = .true.
do while (any (is_child))
  where (is_real .and. is_child)
    is_real_child = .true.
    is_child = .false.
  end where
  mark_next_child: do j = 1, size (is_child)
    if (is_child(j)) then
      is_child(particle_get_children(pset%prt(j))) = .true.
      is_child(j) = .false.
      exit mark_next_child
    end if
  end do mark_next_child
end do
allocate (child (count (is_real_child)))
j = 0
do k = 1, size (is_child)
  if (is_real_child(k)) then
    j = j + 1
    child(j) = k
  end if
end do
end function particle_set_get_real_children

```

Get the `n_tot`, `n_in`, and `n_out` values out of the particle set.

(Particles: public)+≡

```

public :: particle_set_get_n_beam
public :: particle_set_get_n_in
public :: particle_set_get_n_vir
public :: particle_set_get_n_out
public :: particle_set_get_n_tot

```

(Particles: procedures)+≡

```

function particle_set_get_n_beam (pset) result (n_beam)
  type(particle_set_t), intent(in) :: pset
  integer :: n_beam
  n_beam = pset%n_beam
end function particle_set_get_n_beam

function particle_set_get_n_in (pset) result (n_in)
  type(particle_set_t), intent(in) :: pset
  integer :: n_in
  n_in = pset%n_in
end function particle_set_get_n_in

function particle_set_get_n_vir (pset) result (n_vir)
  type(particle_set_t), intent(in) :: pset

```

```

integer :: n_vir
n_vir = pset%n_in
end function particle_set_get_n_vir

function particle_set_get_n_out (pset) result (n_out)
type(particle_set_t), intent(in) :: pset
integer :: n_out
n_out = pset%n_out
end function particle_set_get_n_out

function particle_set_get_n_tot (pset) result (n_tot)
type(particle_set_t), intent(in) :: pset
integer :: n_tot
n_tot = pset%n_tot
end function particle_set_get_n_tot

```

Return a pointer to the particle corresponding to the number

```

(Particles: public)+≡
public :: particle_set_get_particle

(Particles: procedures)+≡
function particle_set_get_particle(pset, index) result(particle)
type(particle_set_t), intent(in) :: pset
integer, intent(in) :: index
type(particle_t) :: particle

particle = pset%prt(index)
end function particle_set_get_particle

```

Tools

Given a subevent, reset status codes.

```

(Particles: public)+≡
public :: particle_set_reset_status

(Particles: procedures)+≡
subroutine particle_set_reset_status (particle_set, index, status)
type(particle_set_t), intent(inout) :: particle_set
integer, dimension(:), intent(in) :: index
integer, intent(in) :: status
integer :: i
if (allocated (particle_set%prt)) then
do i = 1, size (index)
call particle_reset_status (particle_set%prt(index(i)), status)
end do
end if
particle_set%n_beam = &
count (particle_get_status (particle_set%prt) == PRT_BEAM)
particle_set%n_in = &
count (particle_get_status (particle_set%prt) == PRT_INCOMING)
particle_set%n_out = &
count (particle_get_status (particle_set%prt) == PRT_OUTGOING)
particle_set%n_vir = particle_set%n_tot &

```

```

- particle_set%n_beam - particle_set%n_in - particle_set%n_out
end subroutine particle_set_reset_status

```

Reduce a particle set to the essential entries. The entries kept are those with status INCOMING, OUTGOING or RESONANT. BEAM is kept if `keep_beams` is true. Other entries are skipped. The correlated state matrix, if any, is also ignored.

(Particles: public)+≡

```

public :: particle_set_reduce

```

(Particles: procedures)+≡

```

subroutine particle_set_reduce (pset_in, pset_out, keep_beams)
  type(particle_set_t), intent(in) :: pset_in
  type(particle_set_t), intent(out) :: pset_out
  logical, intent(in), optional :: keep_beams
  integer, dimension(:), allocatable :: status, map
  integer :: i, j
  logical :: kb
  kb = .false.; if (present (keep_beams)) kb = keep_beams
  allocate (status (pset_in%n_tot))
  status = particle_get_status (pset_in%prt)
  if (kb) pset_out%n_beam = count (status == PRT_BEAM)
  pset_out%n_in = count (status == PRT_INCOMING)
  pset_out%n_vir = count (status == PRT_RESONANT)
  pset_out%n_out = count (status == PRT_OUTGOING)
  pset_out%n_tot = &
    pset_out%n_beam + pset_out%n_in + pset_out%n_vir + pset_out%n_out
  allocate (pset_out%prt (pset_out%n_tot))
  allocate (map (pset_in%n_tot))
  map = 0
  j = 0
  if (kb) call copy_particles (PRT_BEAM)
  call copy_particles (PRT_INCOMING)
  call copy_particles (PRT_RESONANT)
  call copy_particles (PRT_OUTGOING)
  do i = 1, pset_in%n_tot
    if (map(i) == 0) cycle
! triggers nagfor bug!
!       call particle_set_parents (pset_out%prt(map(i)), &
!         map (particle_set_get_real_parents (pset_in, i)))
!       call particle_set_children (pset_out%prt(map(i)), &
!         map (particle_set_get_real_children (pset_in, i)))
! workaround:
    call particle_set_parents (pset_out%prt(map(i)), &
      particle_set_get_real_parents (pset_in, i, kb))
    call particle_set_parents (pset_out%prt(map(i)), &
      map (pset_out%prt(map(i))%parent))
    call particle_set_children (pset_out%prt(map(i)), &
      particle_set_get_real_children (pset_in, i, kb))
    call particle_set_children (pset_out%prt(map(i)), &
      map (pset_out%prt(map(i))%child))
  end do
contains
  subroutine copy_particles (stat)
    integer, intent(in) :: stat

```



```

integer :: i
do i = 1, pset_in%n_tot
  if (status(i) == stat) then
    j = j + 1
    map(i) = j
    call particle_init (pset_out%prt(j), pset_in%prt(i))
  end if
end do
end subroutine copy_particles
end subroutine particle_set_reduce

```

Remove the beam particles and beam remnants from the particle set if the keep beams flag is false. If keep beams is not given, the beam particles and the beam remnants are removed. The correlated state matrix, if any, is also ignored.

(Particles: public)+≡

```
public :: particle_set_apply_keep_beams
```

(Particles: procedures)+≡

```

subroutine particle_set_apply_keep_beams (pset_in, pset_out, keep_beams)
  type(particle_set_t), intent(in) :: pset_in
  type(particle_set_t), intent(out) :: pset_out
  logical, intent(in), optional :: keep_beams
  integer, dimension(:), allocatable :: status, map
  integer :: i, j
  logical :: kb
  kb = .false.; if (present (keep_beams)) kb = keep_beams
  allocate (status (pset_in%n_tot))
  status = particle_get_status (pset_in%prt)
  if (kb) pset_out%n_beam = count (status == PRT_BEAM)
  pset_out%n_in = count (status == PRT_INCOMING)
  if (kb) then
    pset_out%n_vir = count (status == PRT_VIRTUAL) + count (status == PRT_RESONANT) &
      + count (status == PRT_BEAM_REMNANT)
  else
    pset_out%n_vir = count (status == PRT_VIRTUAL) + count (status == PRT_RESONANT)
  end if
  pset_out%n_out = count (status == PRT_OUTGOING)
  pset_out%n_tot = &
    pset_out%n_beam + pset_out%n_in + pset_out%n_vir + pset_out%n_out
  allocate (pset_out%prt (pset_out%n_tot))
  allocate (map (pset_in%n_tot))
  map = 0
  j = 0
  if (kb) call copy_particles (PRT_BEAM)
  call copy_particles (PRT_INCOMING)
  if (kb) call copy_particles (PRT_BEAM_REMNANT)
  call copy_particles (PRT_RESONANT)
  call copy_particles (PRT_VIRTUAL)
  call copy_particles (PRT_OUTGOING)
  do i = 1, pset_in%n_tot
    if (map(i) == 0) cycle
    ! triggers nagfor bug!
    !   call particle_set_parents (pset_out%prt(map(i)), &
    !     map (particle_set_get_real_parents (pset_in, i)))

```

```

!      call particle_set_children (pset_out%prt(map(i)), &
!      map (particle_set_get_real_children (pset_in, i)))
! workaround:
      call particle_set_parents (pset_out%prt(map(i)), &
      particle_set_get_real_parents (pset_in, i, kb))
      call particle_set_parents (pset_out%prt(map(i)), &
      map (pset_out%prt(map(i))%parent))
      call particle_set_children (pset_out%prt(map(i)), &
      particle_set_get_real_children (pset_in, i, kb))
      call particle_set_children (pset_out%prt(map(i)), &
      map (pset_out%prt(map(i))%child))
    end do
contains
  subroutine copy_particles (stat)
    integer, intent(in) :: stat
    integer :: i
    do i = 1, pset_in%n_tot
      if (status(i) == stat) then
        j = j + 1
        map(i) = j
        call particle_init (pset_out%prt(j), pset_in%prt(i))
      end if
    end do
  end subroutine copy_particles
end subroutine particle_set_apply_keep_beams

```

Transform a particle set into HEPEVT-compatible form. In this form, for each particle, the parents and the children are contiguous in the particle array. Usually, this requires to clone some particles.

We do not know in advance how many particles the canonical form will have. To be on the safe side, allocate four times the original size.

```

(Particles: public) +=
  public :: particle_set_to_hepevt_form

(Particles: procedures) +=
  subroutine particle_set_to_hepevt_form (pset_in, pset_out, keep_beams)
    type(particle_set_t), intent(in) :: pset_in
    type(particle_set_t), intent(out) :: pset_out
    logical, intent(in), optional :: keep_beams
    type(particle_set_t) :: pset
    type :: particle_entry_t
      integer :: src = 0
      integer :: status = 0
      integer :: orig = 0
      integer :: copy = 0
    end type particle_entry_t
    type(particle_entry_t), dimension(:), allocatable :: prt
    integer, dimension(:), allocatable :: map1, map2
    integer, dimension(:), allocatable :: parent, child
    integer :: n_tot, n_parents, n_children, i, j, c, n

    call particle_set_apply_keep_beams(pset_in, pset, keep_beams)
    n_tot = pset%n_tot
    allocate (prt (4 * n_tot))

```

```

allocate (map1(4 * n_tot))
allocate (map2(4 * n_tot))
map1 = 0
map2 = 0
allocate (child (n_tot))
allocate (parent (n_tot))
n = 0
do i = 1, n_tot
  if (particle_get_n_parents (pset%prt(i)) == 0) then
    call append (i)
  end if
end do
do i = 1, n_tot
  n_children = particle_get_n_children (pset%prt(i))
  if (n_children > 0) then
    child(1:n_children) = particle_get_children (pset%prt(i))
    c = child(1)
    if (map1(c) == 0) then
      n_parents = particle_get_n_parents (pset%prt(c))
      if (n_parents > 1) then
        parent(1:n_parents) = particle_get_parents (pset%prt(c))
        if (i == parent(1) .and. &
            any( (/map1(i)+j-1, j=1,n_parents)/) /= map1(parent(1:n_parents)))) &
          then
            do j = 1, n_parents
              call append (parent(j))
            end do
          end if
        else if (map1(i) == 0) then
          call append (i)
        end if
        do j = 1, n_children
          call append (child(j))
        end do
      end if
    else if (map1(i) == 0) then
      call append (i)
    end if
  end do
do i = n, 1, -1
  if (prt(i)%status /= PRT_OUTGOING) then
    do j = 1, i-1
      if (prt(j)%status == PRT_OUTGOING) then
        call append(prt(j)%src)
      end if
    end do
    exit
  end if
end do
pset_out%n_beam = count (prt(1:n)%status == PRT_BEAM)
pset_out%n_in   = count (prt(1:n)%status == PRT_INCOMING)
pset_out%n_vir  = count (prt(1:n)%status == PRT_RESONANT)
pset_out%n_out  = count (prt(1:n)%status == PRT_OUTGOING)
pset_out%n_tot = n

```

```

allocate (pset_out%prt (n))
do i = 1, n
  call particle_init (pset_out%prt(i), pset%prt(prt(i)%src))
  call particle_reset_status (pset_out%prt(i), prt(i)%status)
  if (prt(i)%orig == 0) then
! This causes nagfor 5.2 (770) Panic
!       call particle_set_parents &
!       (pset_out%prt(i), &
!       map2 (particle_get_parents (pset%prt(prt(i)%src))))
! Workaround
      n_parents = particle_get_n_parents (pset%prt(prt(i)%src))
      parent(1:n_parents) = particle_get_parents (pset%prt(prt(i)%src))
      call particle_set_parents (pset_out%prt(i), &
                                map2(parent(1:n_parents)))
  else
      call particle_set_parents (pset_out%prt(i), (/ prt(i)%orig /))
  end if
  if (prt(i)%copy == 0) then
! This causes nagfor 5.2 (770) Panic
!       call particle_set_children &
!       (pset_out%prt(i), &
!       map1 (particle_get_children (pset%prt(prt(i)%src))))
! Workaround
      n_children = particle_get_n_children (pset%prt(prt(i)%src))
      child(1:n_children) = particle_get_children (pset%prt(prt(i)%src))
      call particle_set_children (pset_out%prt(i), &
                                map1(child(1:n_children)))
  else
      call particle_set_children (pset_out%prt(i), (/ prt(i)%copy /))
  end if
end do
contains
subroutine append (i)
  integer, intent(in) :: i
  n = n + 1
  if (n > size (prt)) &
    call msg_bug ("Particle set transform to HEPEVT: insufficient space")
  prt(n)%src = i
  prt(n)%status = particle_get_status (pset%prt(i))
  if (map1(i) == 0) then
    map1(i) = n
  else
    prt(map2(i))%status = PRT_VIRTUAL
    prt(map2(i))%copy = n
    prt(n)%orig = map2(i)
  end if
  map2(i) = n
end subroutine append
end subroutine particle_set_to_hepevt_form

```

This reconstructs the hard interaction from a particle set. First the particle set is reduced to the incoming partons, then we add the direct children of those. The interaction and particle set should match in their array sizes. If we find a

permutation of the particle flavors that matches one of the given flavor states, the assignment of momenta is made accordingly.

(Particles: public)+≡

public :: particle_set_extract_interaction

(Particles: procedures)+≡

```
subroutine particle_set_extract_interaction (pset, int, flv_state)
  type(particle_set_t), intent(in) :: pset
  type(interaction_t), intent(inout) :: int
  integer, dimension(:, :), intent(in) :: flv_state
  integer :: n_in, n_out, n_tot
  integer, dimension(:), allocatable :: status, incoming, outgoing, index
  integer, dimension(:), allocatable :: pdg, perm
  integer :: i
  logical :: ok
  allocate (status (pset%n_tot))
  status = particle_get_status (pset%prt)
  n_in = count (status == PRT_INCOMING)
  allocate (incoming (n_in))
  incoming = pack ((/ (i, i = 1, pset%n_tot) /), status == PRT_INCOMING)
  i = incoming (1)
  n_out = particle_get_n_children (pset%prt(i))
  allocate (outgoing (n_out))
  outgoing = particle_get_children (pset%prt(i))
  n_tot = n_in + n_out
  if (n_in /= interaction_get_n_in (int) &
      .or. n_out /= interaction_get_n_out (int) &
      .or. n_tot /= interaction_get_n_tot (int)) then
    call msg_fatal &
      ("This event does not match the associated process (size)")
    return
  end if
  allocate (index (n_tot), pdg (n_tot), perm (n_tot))
  index(:n_in) = incoming
  index(n_in+1:) = outgoing
  pdg = particle_get_pdg (pset%prt(index))
  call find_flavor_ordering (flv_state, pdg, n_in, perm, ok)
  if (.not. ok) then
    call particle_set_write (pset)
    call msg_fatal &
      ("This event does not match the associated process (flavors)")
    return
  end if
  do i = 1, n_tot
    call interaction_set_momentum (int, &
      particle_get_momentum (pset%prt(i)), perm(i))
  end do
end subroutine particle_set_extract_interaction
```

Given a particle set with an arbitrary ordering of particles, we need the permutation that yields an ordering that is present in the state matrix. This can be found by examining the flavor table. The result is a permutation of the PDG array that matches a row in the flavor table. If *ok* is returned false, no match

was found.

(Particles: procedures)+≡

```

subroutine find_flavor_ordering (flv_state, pdg, n_in, perm, ok)
  integer, dimension(:,:), intent(in) :: flv_state
  integer, dimension(:), intent(in) :: pdg
  integer, intent(in) :: n_in
  integer, dimension(:), intent(out) :: perm
  logical, intent(out) :: ok
  integer :: n_tot, f, i, j, k
  logical, dimension(:), allocatable :: found
  n_tot = size (pdg)
  if (size (flv_state, 1) /= n_tot) then
    ok = .false.
    return
  end if
  do i = 1, n_in
    perm(i) = i
  end do
  allocate (found (n_tot))
  ok = .false.
  do f = 1, size (flv_state, 2)
    call find_ordering_for_this_state (flv_state(:,f))
  end do
contains
  subroutine find_ordering_for_this_state (pdg_state)
    integer, dimension(:), intent(in) :: pdg_state
    found = .false.
    if (all (pdg_state(1:n_in) == pdg(1:n_in))) then
      SCAN_INPUT: do j = n_in + 1, n_tot
        SCAN_STATE: do k = n_in + 1, n_tot
          if (found(k)) cycle SCAN_STATE
          if (pdg_state(k) == pdg(j)) then
            found(k) = .true.
            perm(j) = k
            cycle SCAN_INPUT
          end if
        end do SCAN_STATE
      end do SCAN_INPUT
      return
    end do SCAN_INPUT
    ok = .true.
  end if
end subroutine find_ordering_for_this_state
end subroutine find_flavor_ordering

```

This procedure reconstructs an array of vertex indices from the parent-child information in the particle entries, according to the HepMC scheme. For each particle, we determine which vertex it comes from and which vertex it goes to. We return the two arrays and the maximum vertex index.

For each particle in the list, we first check its parents. If for any parent the vertex where it goes to is already known, this vertex index is assigned as the current 'from' vertex. Otherwise, a new index is created, assigned as the current 'from' vertex, and as the 'to' vertex for all parents.

Then, the analogous procedure is done for the children.

(Particles: procedures)+≡

```

subroutine particle_set_assign_vertices &
  (particle_set, v_from, v_to, n_vertices)
  type(particle_set_t), intent(in) :: particle_set
  integer, dimension(:), intent(out) :: v_from, v_to
  integer, intent(out) :: n_vertices
  integer, dimension(:), allocatable :: parent, child
  integer :: n_parents, n_children, vf, vt
  integer :: i, j, v
  v_from = 0
  v_to = 0
  vf = 0
  vt = 0
  do i = 1, particle_set%n_tot
    n_parents = particle_get_n_parents (particle_set%prt(i))
    if (n_parents /= 0) then
      allocate (parent (n_parents))
      parent = particle_get_parents (particle_set%prt(i))
      SCAN_PARENTS: do j = 1, size (parent)
        v = v_to(parent(j))
        if (v /= 0) then
          v_from(i) = v; exit SCAN_PARENTS
        end if
      end do SCAN_PARENTS
      if (v_from(i) == 0) then
        vf = vf + 1; v_from(i) = vf
        v_to(parent) = vf
      end if
      deallocate (parent)
    end if
    n_children = particle_get_n_children (particle_set%prt(i))
    if (n_children /= 0) then
      allocate (child (n_children))
      child = particle_get_children (particle_set%prt(i))
      SCAN_CHILDREN: do j = 1, size (child)
        v = v_from(child(j))
        if (v /= 0) then
          v_to(i) = v; exit SCAN_CHILDREN
        end if
      end do SCAN_CHILDREN
      if (v_to(i) == 0) then
        vt = vt + 1; v_to(i) = vt
        v_from(child) = vt
      end if
      deallocate (child)
    end if
  end do
  n_vertices = max (vf, vt)
end subroutine particle_set_assign_vertices

```

8.4.4 Expression interface

This converts a `particle_set` object as defined here to a more concise `subevt` object that can be used as the event root of an expression. In particular, the latter lacks virtual particles, spin correlations and parent-child relations.

```

(Particles: public) +=
    public :: particle_set_to_subevt

(Particles: procedures) +=
    subroutine particle_set_to_subevt (particle_set, subevt)
        type(particle_set_t), intent(in), target :: particle_set
        type(subevt_t), intent(out) :: subevt
        type(particle_t), pointer :: prt
        integer :: i, k
        integer, dimension(2) :: hel
        call subevt_init &
            (subevt, particle_set%n_beam + particle_set%n_in + particle_set%n_out)
        k = 0
        do i = 1, particle_set%n_tot
            prt => particle_set%prt(i)
            select case (particle_get_status (prt))
            case (PRT_BEAM)
                k = k + 1
                call subevt_set_beam (subevt, k, &
                    particle_get_pdg (prt), &
                    particle_get_momentum (prt), &
                    particle_get_p2 (prt))
            case (PRT_INCOMING)
                k = k + 1
                call subevt_set_incoming (subevt, k, &
                    particle_get_pdg (prt), &
                    particle_get_momentum (prt), &
                    particle_get_p2 (prt))
            case (PRT_OUTGOING)
                k = k + 1
                call subevt_set_outgoing (subevt, k, &
                    particle_get_pdg (prt), &
                    particle_get_momentum (prt), &
                    particle_get_p2 (prt))
            end select
            select case (particle_get_status (prt))
            case (PRT_BEAM, PRT_INCOMING, PRT_OUTGOING)
                if (prt%polarization == PRT_DEFINITE_HELICITY) then
                    if (helicity_is_diagonal (prt%hel)) then
                        hel = helicity_get (prt%hel)
                        call subevt_polarize (subevt, k, hel(1))
                    end if
                end if
            end select
        end do
    end subroutine particle_set_to_subevt

```

This replaces the `particle_set`

```

(Particles: public) +=

```



```

public :: particle_set_replace
<Particles: procedures>+≡
  subroutine particle_set_replace (particle_set, newprt)
    type(particle_set_t), intent(inout) :: particle_set
    type(particle_t), intent(in), dimension(:), allocatable :: newprt
    if (allocated (particle_set%prt)) deallocate (particle_set%prt)
    allocate (particle_set%prt(size (newprt)))
    particle_set%prt = newprt
    particle_set%n_tot = size (newprt)
    particle_set%n_beam = count (particle_get_status (newprt) == PRT_BEAM)
    particle_set%n_in = count (particle_get_status (newprt) == PRT_INCOMING)
    particle_set%n_out = count (particle_get_status (newprt) == PRT_OUTGOING)
    particle_set%n_vir = particle_set%n_tot &
      - particle_set%n_beam - particle_set%n_in - particle_set%n_out
  end subroutine particle_set_replace

```

8.4.5 Test

Set up a chain of production and decay and factorize the result into particles.
 The process is $d\bar{d} \rightarrow Z \rightarrow q\bar{q}$.

```

<Particles: public>+≡
  public :: particles_test

<Particles: procedures>+≡
  subroutine particles_test
    use os_interface, only: os_data_t
    type(os_data_t) :: os_data
    type(model_t), pointer :: model
    type(flavor_t), dimension(3) :: flv
    type(color_t), dimension(3) :: col
    type(helicity_t), dimension(3) :: hel
    type(quantum_numbers_t), dimension(3) :: qn
    type(vector4_t), dimension(3) :: p
    type(interaction_t), target :: int1, int2
    type(quantum_numbers_mask_t) :: qn_mask_conn, qn_rest
    type(evaluator_t), target :: eval
    type(interaction_t), pointer :: int
    type(particle_set_t) :: particle_set1, particle_set2
    type(particle_set_t) :: particle_set3, particle_set4
    type(hepmc_event_t) :: hepmc_event
    type(hepmc_iostream_t) :: iostream
    type(subevt_t) :: subevt
    logical :: ok
    integer :: u, iostat
    print *, "*** Read model file"
    call syntax_model_file_init ()
    call model_list_read_model &
      (var_str("SM"), var_str("SM.mdl"), os_data, model)
    print *
    print *, "*** Setup production process ***"
    call interaction_init (int1, 2, 0, 1, set_relations=.true.)
    call flavor_init (flv, (/1, -1, 23/), model)

```

```

call helicity_init (hel(3), 1, 1)
call quantum_numbers_init (qn, flv, hel)
call interaction_add_state (int1, qn, value=(0.25_default, 0._default))
call helicity_init (hel(3), 1,-1)
call quantum_numbers_init (qn, flv, hel)
call interaction_add_state (int1, qn, value=(0._default, 0.25_default))
call helicity_init (hel(3),-1, 1)
call quantum_numbers_init (qn, flv, hel)
call interaction_add_state (int1, qn, value=(0._default,-0.25_default))
call helicity_init (hel(3),-1,-1)
call quantum_numbers_init (qn, flv, hel)
call interaction_add_state (int1, qn, value=(0.25_default, 0._default))
call helicity_init (hel(3), 0, 0)
call quantum_numbers_init (qn, flv, hel)
call interaction_add_state (int1, qn, value=(0.5_default, 0._default))
call interaction_freeze (int1)
p(1) = vector4_moving (45._default, 45._default, 3)
p(2) = vector4_moving (45._default,-45._default, 3)
p(3) = p(1) + p(2)
call interaction_set_momenta (int1, p)
print *
print *, "*** Setup decay process ***"
call interaction_init (int2, 1, 0, 2, set_relations=.true.)
call flavor_init (flv, (/23, 1, -1/), model)
call color_init_col_acl (col, (/ 0, 501, 0 /), (/ 0, 0, 501 /))
call helicity_init (hel, (/ 1, 1, 1/), (/ 1, 1, 1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(1._default, 0._default))
call helicity_init (hel, (/ 1, 1, 1/), (/ -1,-1,-1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(0._default, 0.1_default))
call helicity_init (hel, (/ -1,-1,-1/), (/ 1, 1, 1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(0._default,-0.1_default))
call helicity_init (hel, (/ -1,-1,-1/), (/ -1,-1,-1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(1._default, 0._default))
call helicity_init (hel, (/ 0, 1,-1/), (/ 0, 1,-1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(4._default, 0._default))
call helicity_init (hel, (/ 0,-1, 1/), (/ 0, 1,-1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(2._default, 0._default))
call helicity_init (hel, (/ 0, 1,-1/), (/ 0,-1, 1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(2._default, 0._default))
call helicity_init (hel, (/ 0,-1, 1/), (/ 0,-1, 1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(4._default, 0._default))
call flavor_init (flv, (/23, 2, -2/), model)
call helicity_init (hel, (/ 0, 1,-1/), (/ 0, 1,-1/))
call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(0.5_default, 0._default))
call helicity_init (hel, (/ 0,-1, 1/), (/ 0,-1, 1/))

```

```

call quantum_numbers_init (qn, flv, col, hel)
call interaction_add_state (int2, qn, value=(0.5_default, 0._default))
call interaction_freeze (int2)
p(2) = vector4_moving (45._default, 45._default, 2)
p(3) = vector4_moving (45._default,-45._default, 2)
call interaction_set_momenta (int2, p)
call interaction_set_source_link (int2, 1, int1, 3)
call interaction_write (int1)
call interaction_write (int2)
print *
print *, "*** Concatenate production and decay ***"
call evaluator_init_product (eval, int1, int2, qn_mask_conn, &
    connections_are_resonant=.true.)
call evaluator_receive_momenta (eval)
call evaluator_evaluate (eval)
call evaluator_write (eval)
print *
print *, "*** Factorize as subevent (complete, polarized) ***"
int => evaluator_get_int_ptr (eval)
call particle_set_init &
    (particle_set1, ok, int, int, FM_FACTOR_HELICITY, &
    (/0.2_default, 0.2_default/), .false., .true.)
call particle_set_write (particle_set1)
print *
print *, "*** Write this to HEPEUP and print as LHEF format ***"
call les_houches_events_write_header ()
call heprup_init ((/2212, 2212/), (/7.e3_default, 7.e3_default/), &
    n_processes=1, unweighted=.true., negative_weights=.false.)
call heprup_set_process_parameters (1, 1)
call heprup_write_lhef ()
call particle_set_fill_hepeup (particle_set1)
call hepeup_write_lhef ()
call les_houches_events_write_footer ()
print *
print *, "*** Factorize as subevent (in/out only, selected helicity) ***"
int => evaluator_get_int_ptr (eval)
call particle_set_init &
    (particle_set2, ok, int, int, FM_SELECT_HELICITY, &
    (/0.9_default, 0.9_default/), .false., .false.)
call particle_set_write (particle_set2)
call particle_set_final (particle_set2)
print *
print *, "*** Factorize as subevent (complete, selected helicity) ***"
int => evaluator_get_int_ptr (eval)
call particle_set_init &
    (particle_set2, ok, int, int, FM_SELECT_HELICITY, &
    (/0.7_default, 0.7_default/), .false., .true.)
call particle_set_write (particle_set2)
print *
print *, "*** Write to HepMC, print, and output to particles_test.hepmc.dat ***"
call hepmc_event_init (hepmc_event, 11, 127)
call particle_set_fill_hepmc_event (particle_set2, hepmc_event)
call hepmc_event_print (hepmc_event)
call hepmc_iostream_open_out &

```

```

        (iostream , var_str ("particles_test.hepmc.dat"))
call hepmc_iostream_write_event (iostream, hepmc_event)
call hepmc_iostream_close (iostream)
print *
print *, "*** Recover from HepMC file ***"
call particle_set_final (particle_set2)
call hepmc_event_final (hepmc_event)
call hepmc_event_init (hepmc_event)
call hepmc_iostream_open_in &
        (iostream , var_str ("particles_test.hepmc.dat"))
call hepmc_iostream_read_event (iostream, hepmc_event, ok)
call hepmc_iostream_close (iostream)
call particle_set_init (particle_set2, &
        hepmc_event, model, PRT_DEFINITE_HELICITY)
call particle_set_write (particle_set2)
print *
print *, "*** Factorize (complete, polarized, correlated); write and read again ***"
int => evaluator_get_int_ptr (eval)
call particle_set_init &
        (particle_set3, ok, int, int, FM_FACTOR_HELICITY, &
        (/0.7_default, 0.7_default/), .true., .true.)
call particle_set_write (particle_set3)
!!! !!! The raw writing seems not to be working.
!!! u = free_unit ()
!!! open (u, action="readwrite", form="unformatted", status="scratch")
!!! call particle_set_write_raw (particle_set3, u)
!!! rewind (u)
!!! call particle_set_read_raw (particle_set4, u, iostat=iostat)
!!! close (u)
!!! print *
!!! call particle_set_write (particle_set4)
!!! print *
!!! print *, "*** Transform to a subevt object ***"
!!! call particle_set_to_subevt (particle_set4, subevt)
!!! call subevt_write (subevt)
print *
print *, "*** Cleanup ***"
call particle_set_final (particle_set1)
call particle_set_final (particle_set2)
call particle_set_final (particle_set3)
call particle_set_final (particle_set4)
call evaluator_final (eval)
call interaction_final (int1)
call interaction_final (int2)
call hepmc_event_final (hepmc_event)
end subroutine particles_test

```

Chapter 9

Initial State

9.1 Beams for collisions and decays

```
<beams.f90>≡  
  <File header>  
  
  module beams  
  
    <Use kinds>  
    <Use strings>  
    use constants !NODEP!  
    <Use file utils>  
    use diagnostics !NODEP!  
    use lorentz !NODEP!  
    use md5  
    use models  
    use flavors  
    use colors  
    use polarizations  
    use quantum_numbers  
    use state_matrices  
    use interactions  
  
    <Standard module head>  
  
    <Beams: public>  
  
    <Beams: types>  
  
    <Beams: interfaces>  
  
    contains  
  
    <Beams: procedures>  
  
  end module beams
```

9.1.1 Beam data

The beam data type contains beam data for one or two beams, depending on whether we are dealing with beam collisions or particle decay. In addition, it holds the c.m. energy `sqrts`, the Lorentz transformation `L` that transforms the c.m. system into the lab system, and the pair of c.m. momenta.

```

(Beams: public)≡
    public :: beam_data_t

(Beams: types)≡
    type :: beam_data_t
        logical :: initialized = .false.
        integer :: n = 0
        type(flavor_t), dimension(:), allocatable :: flv
        real(default), dimension(:), allocatable :: mass
        type(polarization_t), dimension(:), allocatable :: pol
        logical :: lab_is_cm_frame = .true.
        type(vector4_t), dimension(:), allocatable :: p_cm
        type(vector4_t), dimension(:), allocatable :: p
        type(lorentz_transformation_t), pointer :: L_cm_to_lab => null ()
        real(default) :: sqrts = 0
        character(32) :: md5sum = ""
    end type beam_data_t

```

Generic initializer. This is called by the specific initializers below. Initialize either for decay or for collision.

```

(Beams: procedures)≡
    subroutine beam_data_init (beam_data, n)
        type(beam_data_t), intent(out) :: beam_data
        integer, intent(in) :: n
        beam_data%n = n
        allocate (beam_data%flv (n))
        allocate (beam_data%mass (n))
        allocate (beam_data%pol (n))
        allocate (beam_data%p_cm (n))
        allocate (beam_data%p (n))
        beam_data%initialized = .true.
    end subroutine beam_data_init

```

Finalizer: needed for the polarization components of the beams.

```

(Beams: public)+≡
    public :: beam_data_final

(Beams: procedures)+≡
    subroutine beam_data_final (beam_data)
        type(beam_data_t), intent(inout) :: beam_data
        beam_data%initialized = .false.
        if (allocated (beam_data%pol)) call polarization_final (beam_data%pol)
        if (associated (beam_data%L_cm_to_lab)) deallocate (beam_data%L_cm_to_lab)
    end subroutine beam_data_final

```

The verbose (default) version is for debugging. The short version is for screen output in the UI.

<Beams: public>+≡

public :: beam_data_write

<Beams: procedures>+≡

```
subroutine beam_data_write (beam_data, unit, verbose, write_md5sum)
  type(beam_data_t), intent(in) :: beam_data
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose, write_md5sum
  integer :: prt_name_len
  logical :: verb, write_md5
  integer :: u
  u = output_unit (unit); if (u < 0) return
  verb = .false.; if (present (verbose)) verb = verbose
  write_md5 = verb; if (present (write_md5sum)) write_md5 = write_md5sum
  if (.not. beam_data%initialized) then
    write (u, "(A)") "Beam data: [undefined]"
    return
  end if
  prt_name_len = maxval (len (flavor_get_name (beam_data%flv)))
  select case (beam_data%n)
  case (1)
    write (u, "(A)") "Beam data (decay):"
    if (verb) then
      call write_prt (1)
      call polarization_write (beam_data%pol(1), u)
      write (u, *) "R.f. momentum:"
      call vector4_write (beam_data%p_cm(1), u)
      write (u, *) "Lab momentum:"
      call vector4_write (beam_data%p(1), u)
    else
      call write_prt (1)
    end if
  case (2)
    write (u, "(A)") "Beam data (collision):"
    if (verb) then
      call write_prt (1)
      call polarization_write (beam_data%pol(1), u)
      call write_prt (2)
      call polarization_write (beam_data%pol(2), u)
      call write_sqrts
      write (u, *) "C.m. momenta:"
      call vector4_write (beam_data%p_cm(1), u)
      call vector4_write (beam_data%p_cm(2), u)
      write (u, *) "Lab momenta:"
      call vector4_write (beam_data%p(1), u)
      call vector4_write (beam_data%p(2), u)
    else
      call write_prt (1)
      call write_prt (2)
      call write_sqrts
    end if
  end select
end select
```

```

if (associated (beam_data%L_cm_to_lab)) &
    call lorentz_transformation_write (beam_data%L_cm_to_lab, u)
if (write_md5) then
    write (u, *) "MD5 sum: ", beam_data%md5sum
end if
contains
subroutine write_sqrts
    character(80) :: sqrts_str
    write (sqrts_str, "(1PG21.15)") beam_data%sqrts
    write (u, "(1x,A)") "sqrts = " // trim (adjustl (sqrts_str)) // " GeV"
end subroutine write_sqrts
subroutine write_prt (i)
    integer, intent(in) :: i
    character(80) :: name_str, mass_str
    write (name_str, "(A)") char (flavor_get_name (beam_data%flv(i)))
    write (mass_str, "(1PG15.8)") beam_data%mass(i)
    write (u, "(1x,A)") name_str(:prt_name_len) // " (mass = " &
        // trim (adjustl (mass_str)) // " GeV)"
end subroutine write_prt
end subroutine beam_data_write

```

Return initialization status:

```

<Beams: public>+≡
    public :: beam_data_are_valid

<Beams: procedures>+≡
    function beam_data_are_valid (beam_data) result (flag)
        logical :: flag
        type(beam_data_t), intent(in) :: beam_data
        flag = beam_data%initialized
    end function beam_data_are_valid

```

Check whether beam data agree with the current values of relevant parameters.

```

<Beams: public>+≡
    public :: beam_data_check_scattering

<Beams: procedures>+≡
    subroutine beam_data_check_scattering (beam_data, sqrts)
        type(beam_data_t), intent(in) :: beam_data
        real(default), intent(in), optional :: sqrts
        if (beam_data_are_valid (beam_data)) then
            if (present (sqrts)) then
                if (sqrts /= beam_data%sqrts) then
                    call msg_error ("Current setting of sqrts is inconsistent " &
                        // "with beam setup (ignored).")
                end if
            end if
        else
            call msg_bug ("Beam setup: invalid beam data")
        end if
    end subroutine beam_data_check_scattering

```


Return the number of beams (1 for decays, 2 for collisions).

```
<Beams: public>+≡
    public :: beam_data_get_n_in

<Beams: procedures>+≡
    function beam_data_get_n_in (beam_data) result (n_in)
        integer :: n_in
        type(beam_data_t), intent(in) :: beam_data
        n_in = beam_data%n
    end function beam_data_get_n_in
```

Return the beam flavor

```
<Beams: public>+≡
    public :: beam_data_get_flavor

<Beams: procedures>+≡
    function beam_data_get_flavor (beam_data) result (flv)
        type(flavor_t), dimension(:), allocatable :: flv
        type(beam_data_t), intent(in) :: beam_data
        allocate (flv (beam_data%n))
        flv = beam_data%flv
    end function beam_data_get_flavor
```

Return the beam energies

```
<Beams: public>+≡
    public :: beam_data_get_energy

<Beams: procedures>+≡
    function beam_data_get_energy (beam_data) result (e)
        real(default), dimension(:), allocatable :: e
        type(beam_data_t), intent(in) :: beam_data
        allocate (e (beam_data%n))
        if (beam_data%initialized) then
            e = energy (beam_data%p)
        else
            e = 0
        end if
    end function beam_data_get_energy
```

Return a MD5 checksum for beam data. If no checksum is present (because beams have not been initialized), compute the checksum of the sqrts value.

```
<Beams: public>+≡
    public :: beam_data_get_md5sum

<Beams: procedures>+≡
    function beam_data_get_md5sum (beam_data, sqrts) result (md5sum_beams)
        type(beam_data_t), intent(in) :: beam_data
        real(default), intent(in) :: sqrts
        character(32) :: md5sum_beams
        character(80) :: buffer
        if (beam_data%md5sum /= "") then
            md5sum_beams = beam_data%md5sum
        else
            write (buffer, *) sqrts
```

```

        md5sum_beams = md5sum (buffer)
    end if
end function beam_data_get_md5sum

```

9.1.2 Initializers: collisions

This is the simplest one: just the two flavors, c.m. energy, polarization. Color is inferred from flavor. Beam momenta and c.m. momenta coincide.

```

(Beams: public)+≡
    public :: beam_data_init_sqrts

(Beams: procedures)+≡
    subroutine beam_data_init_sqrts (beam_data, sqrts, flv, pol, p_cm, theta, phi)
        type(beam_data_t), intent(out) :: beam_data
        real(default), intent(in) :: sqrts
        type(flavor_t), dimension(:), intent(in) :: flv
        type(polarization_t), dimension(:), intent(in), optional :: pol
        real(default), intent(in), optional :: p_cm, theta, phi
        real(default), dimension(size(flv)) :: E, p
        call beam_data_init (beam_data, size (flv))
        beam_data%sqrts = sqrts
        beam_data%lab_is_cm_frame = &
            .not. present (p_cm) .and. .not. present (theta)
        select case (beam_data%n)
        case (1)
            if (present (p_cm)) then
                E = sqrt (sqrts**2 + p_cm**2)
                p = p_cm
            else
                E = sqrts; p = 0
            end if
            beam_data%p_cm = vector4_moving (E, p, 3)
            beam_data%p = beam_data%p_cm
        case (2)
            beam_data%p_cm = colliding_momenta (sqrts, flavor_get_mass (flv))
            beam_data%p = colliding_momenta (sqrts, flavor_get_mass (flv), p_cm)
        end select
        call beam_data_finish_initialization (beam_data, flv, pol, theta, phi)
    end subroutine beam_data_init_sqrts

```

This version uses the momenta of both beams. Note that both momenta are positive numbers. (Applies only to collisions.)

We allow for a crossing angle α . The crossing angle is applied such that both incoming particle momenta are rotated in the zx plane by $\alpha/2$, from the $\pm z$ axis towards the x axis.

```

(Beams: public)+≡
    public :: beam_data_init_momenta

(Beams: procedures)+≡
    subroutine beam_data_init_momenta (beam_data, p, flv, pol, alpha, theta, phi)
        type(beam_data_t), intent(out) :: beam_data
        real(default), dimension(2), intent(in) :: p

```

```

type(flavor_t), dimension(2), intent(in) :: flv
type(polarization_t), dimension(2), intent(in), optional :: pol
real(default), intent(in), optional :: alpha, theta, phi
real(default), dimension(2) :: m, e
real(default) :: ca, sa
call beam_data_init (beam_data, 2)
m = flavor_get_mass (flv)
e = sqrt (p**2 + m**2)
beam_data%p(1) = vector4_moving (e(1), p(1), 3)
beam_data%p(2) = vector4_moving (e(2),-p(2), 3)
if (present (alpha)) then
  ca = cos (alpha / 2)
  sa = sin (alpha / 2)
  beam_data%p(1) = rotation (ca, sa, 2) * beam_data%p(1)
  beam_data%p(2) = rotation (ca,-sa, 2) * beam_data%p(2)
  beam_data%sqrts = &
    sqrt (2 * (e(1)*e(2) + p(1)*p(2)*cos(alpha)) + m(1)**2 + m(2)**2)
else
  beam_data%sqrts = &
    sqrt (2 * (e(1)*e(2) + p(1)*p(2)) + m(1)**2 + m(2)**2)
end if
beam_data%p_cm = colliding_momenta (beam_data%sqrts, m)
call beam_data_finish_initialization (beam_data, flv, pol, theta, phi)
end subroutine beam_data_init_momenta

```

Final steps: If requested, rotate the beams in the lab frame, and set the beam-data components.

(Beams: procedures)+≡

```

subroutine beam_data_finish_initialization (beam_data, flv, pol, theta, phi)
  type(beam_data_t), intent(inout) :: beam_data
  type(flavor_t), dimension(:), intent(in) :: flv
  type(polarization_t), dimension(:), intent(in), optional :: pol
  real(default), intent(in), optional :: theta, phi
  integer :: i
  if (present (theta)) then
    beam_data%p = rotation (theta, 2) * beam_data%p
    if (present (phi)) then
      beam_data%p = rotation (phi, 3) * beam_data%p
    end if
  end if
  do i = 1, beam_data%n
    beam_data%flv(i) = flv(i)
    beam_data%mass(i) = flavor_get_mass (flv(i))
    if (present (pol)) then
      beam_data%pol(i) = pol(i)
    else
      call polarization_init_unpolarized (beam_data%pol(i), flv(i))
    end if
  end do
  call beam_data_compute_md5sum (beam_data)
  call beam_data_write (beam_data)
end subroutine beam_data_finish_initialization

```

The MD5 sum is stored within the beam-data record, so it can be checked for integrity in subsequent runs.

```

(Beams: procedures)+≡
  subroutine beam_data_compute_md5sum (beam_data)
    type(beam_data_t), intent(inout) :: beam_data
    integer :: unit
    unit = free_unit ()
    open (unit = unit, status = "scratch", action = "readwrite")
    call beam_data_write (beam_data, unit, write_md5sum = .false., &
      verbose = .true.)
    rewind (unit)
    beam_data%md5sum = md5sum (unit)
    close (unit)
  end subroutine beam_data_compute_md5sum

```

9.1.3 Initializers: decays

This is the simplest one: decay in rest frame. We need just flavor and polarization. Color is inferred from flavor. Beam momentum and c.m. momentum coincide.

```

(Beams: public)+≡
  public :: beam_data_init_decay

(Beams: procedures)+≡
  subroutine beam_data_init_decay &
    (beam_data, flv, pol, p_cm, theta, phi)
    type(beam_data_t), intent(out) :: beam_data
    type(flavor_t), dimension(1), intent(in) :: flv
    type(polarization_t), dimension(1), intent(in), optional :: pol
    real(default), intent(in), optional :: p_cm, theta, phi
    real(default), dimension(1) :: m
    type(polarization_t), dimension(1) :: polarization
    m = flavor_get_mass (flv)
    if (present (pol)) then
      call beam_data_init_sqrts &
        (beam_data, m(1), flv, pol, p_cm, theta, phi)
    else
      call polarization_init_trivial (polarization(1), flv(1))
      call beam_data_init_sqrts &
        (beam_data, m(1), flv, polarization, p_cm, theta, phi)
    end if
  end subroutine beam_data_init_decay

```

9.1.4 Data access

Post-initialization changes to the polarization:

```

(Beams: public)+≡
  public :: beam_data_set_polarization
  public :: beam_data_kill_polarization

```

```

<Beams: procedures>+≡
subroutine beam_data_set_polarization (beam_data, pol)
  type(beam_data_t), intent(inout) :: beam_data
  type(polarization_t), dimension(:), intent(in) :: pol
  integer :: i
  if (size (pol) /= beam_data%n) call msg_bug ( &
    "beam_data_set_polarization_pol: initial state multiplicity mismatch")
  !do i = 1, beam_data%n
  !  call polarization_final (beam_data%pol(i))
  !end do
  beam_data%pol = pol
  call beam_data_compute_md5sum (beam_data)
end subroutine beam_data_set_polarization

subroutine beam_data_kill_polarization (beam_data)
  type(beam_data_t), intent(inout) :: beam_data
  if (beam_data%n == 1) then
    call polarization_init_trivial (beam_data%pol(1), beam_data%flv(1))
  else
    call polarization_init_unpolarized (beam_data%pol(1), beam_data%flv(1))
    call polarization_init_unpolarized (beam_data%pol(2), beam_data%flv(2))
  end if
end subroutine beam_data_kill_polarization

```

9.1.5 Sanity check

After the beams have been set, the initial-particle masses may have been modified. This can be checked here.

```

<Beams: public>+≡
public :: beam_data_masses_are_consistent

<Beams: procedures>+≡
function beam_data_masses_are_consistent (beam_data) result (flag)
  logical :: flag
  type(beam_data_t), intent(in) :: beam_data
  flag = all (beam_data%mass == flavor_get_mass (beam_data%flv))
end function beam_data_masses_are_consistent

```

9.1.6 The beams type

Beam objects are interaction objects that contain the actual beam data including polarization and density matrix. For collisions, the beam object actually contains two beams.

```

<Beams: public>+≡
public :: beam_t

<Beams: types>+≡
type :: beam_t
  private
  type(interaction_t) :: int
end type beam_t

```

The constructor contains code that converts beam data into the (entangled) particle-pair quantum state. First, we set the number of particles and polarization mask. (The polarization mask is handed over to all later interactions, so if helicity is diagonal or absent, this fact is used when constructing the hard-interaction events.) Then, we construct the entangled state that combines helicity, flavor and color of the two particles (where flavor and color are unique, while several helicity states are possible). Then, we transfer this state together with the associated values from the spin density matrix into the `interaction_t` object.

```

(Beams: public)+≡
    public :: beam_init

(Beams: procedures)+≡
    subroutine beam_init (beam, beam_data)
        type(beam_t), intent(out) :: beam
        type(beam_data_t), intent(in), target :: beam_data
        type(quantum_numbers_mask_t), dimension(beam_data%n) :: mask
        type(state_matrix_t), target :: state_hel, state_fc, state_tmp
        type(state_iterator_t) :: it_hel, it_tmp
        type(quantum_numbers_t), dimension(:), allocatable :: qn
        mask = new_quantum_numbers_mask (.false., .false., &
            .not. polarization_is_polarized (beam_data%pol), &
            mask_hd = polarization_is_diagonal (beam_data%pol))
        call interaction_init &
            (beam%int, 0, 0, beam_data%n, mask=mask, store_values=.true.)
        call combine_polarization_states (beam_data%pol, state_hel)
        allocate (qn (beam_data%n))
        call quantum_numbers_init &
            (qn, beam_data%flv, color_from_flavor (beam_data%flv))
        call state_matrix_init (state_fc)
        call state_matrix_add_state (state_fc, qn)
        call merge_state_matrices (state_hel, state_fc, state_tmp)
        call state_iterator_init (it_hel, state_hel)
        call state_iterator_init (it_tmp, state_tmp)
        do while (state_iterator_is_valid (it_hel))
            call interaction_add_state (beam%int, &
                state_iterator_get_quantum_numbers (it_tmp), &
                value=state_iterator_get_matrix_element (it_hel))
            call state_iterator_advance (it_hel)
            call state_iterator_advance (it_tmp)
        end do
        call interaction_freeze (beam%int)
        call interaction_set_momenta &
            (beam%int, beam_data%p, outgoing = .true.)
        call state_matrix_final (state_hel)
        call state_matrix_final (state_fc)
        call state_matrix_final (state_tmp)
    end subroutine beam_init

```

Finalizer:

```

(Beams: public)+≡
    public :: beam_final

```

```

<Beams: procedures>+≡
  elemental subroutine beam_final (beam)
    type(beam_t), intent(inout) :: beam
    call interaction_final (beam%int)
  end subroutine beam_final

```

I/O:

```

<Beams: public>+≡
  public :: beam_write

<Beams: procedures>+≡
  subroutine beam_write (beam, unit, verbose, show_momentum_sum, show_mass)
    type(beam_t), intent(in) :: beam
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
    integer :: u
    u = output_unit (unit); if (u < 0) return
    select case (interaction_get_n_out (beam%int))
    case (1); write (u, *) "Decaying particle:"
    case (2); write (u, *) "Colliding beams:"
    end select
    call interaction_write &
      (beam%int, unit, verbose, show_momentum_sum, show_mass)
  end subroutine beam_write

```

Defined assignment: deep copy

```

<Beams: public>+≡
  public :: assignment(=)

<Beams: interfaces>≡
  interface assignment(=)
    module procedure beam_assign
  end interface

<Beams: procedures>+≡
  subroutine beam_assign (beam_out, beam_in)
    type(beam_t), intent(out) :: beam_out
    type(beam_t), intent(in) :: beam_in
    beam_out%int = beam_in%int
  end subroutine beam_assign

```

9.1.7 Inherited procedures

```

<Beams: public>+≡
  public :: interaction_set_source_link

<Beams: interfaces>+≡
  interface interaction_set_source_link
    module procedure interaction_set_source_link_beam
  end interface

```

```

<Beams: procedures>+≡
  subroutine interaction_set_source_link_beam (int, i, beam1, i1)
    type(interaction_t), intent(inout) :: int
    type(beam_t), intent(in), target :: beam1
    integer, intent(in) :: i, i1
    call interaction_set_source_link (int, i, beam1%int, i1)
  end subroutine interaction_set_source_link_beam

```

9.1.8 Accessing contents

Return the interaction component – as a pointer, to avoid any copying.

```

<Beams: public>+≡
  public :: beam_get_int_ptr

<Beams: procedures>+≡
  function beam_get_int_ptr (beam) result (int)
    type(interaction_t), pointer :: int
    type(beam_t), intent(in), target :: beam
    int => beam%int
  end function beam_get_int_ptr

```

Set beam momenta directly. (Used for cascade decays.)

```

<Beams: public>+≡
  public :: beam_set_momenta

<Beams: procedures>+≡
  subroutine beam_set_momenta (beam, p)
    type(beam_t), intent(inout) :: beam
    type(vector4_t), dimension(:), intent(in) :: p
    call interaction_set_momenta (beam%int, p)
  end subroutine beam_set_momenta

```

9.1.9 Test

```

<Beams: public>+≡
  public :: beam_test

<Beams: procedures>+≡
  subroutine beam_test ()
    use os_interface, only: os_data_t
    type(os_data_t) :: os_data
    type(beam_data_t), target :: beam_data
    type(beam_t) :: beam
    real(default) :: sqrts
    type(flavor_t), dimension(2) :: flv
    type(polarization_t), dimension(2) :: pol
    type(model_t), pointer :: model
    print *, "*** Read model file"
    call syntax_model_file_init ()
    call model_list_read_model &
      (var_str("SM"), var_str("SM.mdl"), os_data, model)
    call syntax_model_file_final ()
  end subroutine beam_test

```



```

print *
print *, "*** Scattering"
sqrts = 500
call flavor_init (flv, ((/1,-1/)), model)
call polarization_init_circular (pol(1), flv(1), 0.5_default)
call polarization_init_transversal (pol(2), flv(2), 0._default, 1._default)
call beam_data_init_sqrts (beam_data, sqrts, flv, pol)
call beam_data_write (beam_data)
print *
call beam_init (beam, beam_data)
call beam_write (beam)
call beam_final (beam)
call beam_data_final (beam_data)
print *
print *, "*** Decay"
call flavor_init (flv(1), 23, model)
call polarization_init_longitudinal (pol(1), flv(1), 0.4_default)
call beam_data_init_decay (beam_data, flv(1:1), pol(1:1))
call beam_data_write (beam_data)
print *
call beam_init (beam, beam_data)
call beam_write (beam)
call beam_final (beam)
call beam_data_final (beam_data)
end subroutine beam_test

```

Chapter 10

Spectra and structure functions

Each type of spectrum and structure function gets its own module with a common API; all modules are collected and accessed via the wrapper module `spectra`.

10.1 Tools

This module contains auxiliary procedures that can be accessed by the structure function code.

```
<sf_aux.f90>≡  
  <File header>  
  
  module sf_aux  
  
    <Use kinds>  
    use constants, only: twopi !NODEP!  
    <Use file utils>  
    use lorentz !NODEP!  
  
    <Standard module head>  
  
    <SF aux: public>  
  
    <SF aux: parameters>  
  
    <SF aux: types>  
  
    contains  
  
    <SF aux: procedures>  
  
  end module sf_aux
```

10.1.1 Momentum splitting

Let us consider first an incoming parton with momentum k and invariant mass squared $s = k^2$ that splits into two partons with momenta q, p and invariant masses $t = q^2$ and $u = p^2$. (This is an abuse of the Mandelstam notation. t is actually the momentum transfer, assuming that p is radiated and q initiates the hard process.) The energy is split among the partons such that if $E = k^0$, we have $q^0 = xE$ and $p^0 = \bar{x}E$, where $\bar{x} \equiv 1 - x$.

We define the angle θ as the polar angle of p w.r.t. the momentum axis of the incoming momentum k . Ignoring azimuthal angle, we can write the four-momenta in the basis (E, p_T, p_L) as

$$k = \begin{pmatrix} E \\ 0 \\ p \end{pmatrix}, \quad p = \begin{pmatrix} \bar{x}E \\ \bar{x}\bar{p}\sin\theta \\ \bar{x}\bar{p}\cos\theta \end{pmatrix}, \quad q = \begin{pmatrix} xE \\ -\bar{x}\bar{p}\sin\theta \\ p - \bar{x}\bar{p}\cos\theta \end{pmatrix}, \quad (10.1)$$

where the first two mass-shell conditions are

$$p^2 = E^2 - s, \quad \bar{p}^2 = E^2 - \frac{u}{\bar{x}^2}. \quad (10.2)$$

The second condition implies that, for positive u , $\bar{x}^2 > u/E^2$, or equivalently

$$x < 1 - \sqrt{u}/E. \quad (10.3)$$

We are interested in the third mass-shell conditions: s and u are fixed, so we need t as a function of $\cos\theta$:

$$t = -2\bar{x}(E^2 - p\bar{p}\cos\theta) + s + u. \quad (10.4)$$

Solving for $\cos\theta$, we get

$$\cos\theta = \frac{2\bar{x}E^2 + t - s - u}{2\bar{x}p\bar{p}}. \quad (10.5)$$

We can compute $\sin^2\theta$ numerically as $\sin^2\theta = 1 - \cos^2\theta$, but it is important to reexpress this in view of numerical stability. To this end, we first determine the bounds for t . The cosine must be between -1 and 1 , so the bounds are

$$t_0 = -2\bar{x}(E^2 + p\bar{p}) + s + u, \quad (10.6)$$

$$t_1 = -2\bar{x}(E^2 - p\bar{p}) + s + u. \quad (10.7)$$

Computing $\sin^2\theta$ from $\cos\theta$ above, we observe that the numerator is a quadratic polynomial in t which has the zeros t_0 and t_1 , while the common denominator is given by $(2\bar{x}p\bar{p})^2$. Hence, we can write

$$\sin^2\theta = -\frac{(t - t_0)(t - t_1)}{(2\bar{x}p\bar{p})^2} \quad \text{and} \quad \cos\theta = \frac{(t - t_0) + (t - t_1)}{4\bar{x}p\bar{p}}, \quad (10.8)$$

which is free of large cancellations near $t = t_0$ or $t = t_1$.

If all is massless, i.e., $s = u = 0$, this simplifies to

$$t_0 = -4\bar{x}E^2, \quad t_1 = 0, \quad (10.9)$$

$$\sin^2\theta = -\frac{t}{\bar{x}E^2} \left(1 + \frac{t}{4\bar{x}E^2}\right), \quad \cos\theta = 1 + \frac{t}{2\bar{x}E^2}. \quad (10.10)$$

Here is the implementation. First, we define a container for the kinematical integration limits and some further data.

```

<SF aux: public>≡
  public :: splitting_data_t

<SF aux: types>≡
  type :: splitting_data_t
  private
    real(default) :: x0 = 0
    real(default) :: x1
    real(default) :: t0
    real(default) :: t1
    real(default) :: phi0 = 0
    real(default) :: phi1 = twopi
    real(default) :: E, p, s, u, m2
    real(default) :: x, xb, pb
    real(default) :: t, phi
  end type splitting_data_t

```

This is the initializer for the data. The input consists of the incoming momentum, its invariant mass squared, and the invariant mass squared of the radiated particle. m is the *physical* mass of the outgoing particle. The t bounds depend on the chosen x value and cannot be determined yet.

```

<SF aux: public>+≡
  public :: new_splitting_data

<SF aux: procedures>≡
  elemental function new_splitting_data (k, mk2, mr2, m) result (d)
    type(splitting_data_t) :: d
    type(vector4_t), intent(in) :: k
    real(default), intent(in) :: mk2, mr2, m
    d%E = energy (k)
    d%x1 = 1 - sqrt (max (mr2, 0._default)) / d%E
    d%p = sqrt (d%E**2 - mk2)
    d%s = mk2
    d%u = mr2
    d%m2 = m**2
  end function new_splitting_data

```

I/O for debugging:

```

<SF aux: public>+≡
  public :: splitting_data_write

<SF aux: procedures>+≡
  subroutine splitting_data_write (d, unit)
    type(splitting_data_t), intent(in) :: d
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write (u, *) "Splitting data:"
    write (u, *) " x0   =", d%x0
    write (u, *) " x    =", d%x
    write (u, *) " xb   =", d%xb
    write (u, *) " x1   =", d%x1

```

```

write (u, *) " t0   =", d%t0
write (u, *) " t    =", d%t
write (u, *) " t1   =", d%t1
write (u, *) " phi0 =", d%phi0
write (u, *) " phi  =", d%phi
write (u, *) " phi1 =", d%phi1
write (u, *) " E    =", d%E
write (u, *) " p    =", d%p
write (u, *) " pb   =", d%pb
write (u, *) " s    =", d%s
write (u, *) " u    =", d%u
write (u, *) " m2   =", d%m2
end subroutine splitting_data_write

```

Retrieve the x bounds, if needed for x sampling. Generating an x value is done by the caller, since this is the part that depends on the nature of the structure function.

```

<SF aux: public>+≡
public :: splitting_get_x_bounds

<SF aux: procedures>+≡
function splitting_get_x_bounds (d) result (x)
  real(default), dimension(2) :: x
  type(splitting_data_t), intent(in) :: d
  x = (/ d%x0, d%x1 /)
end function splitting_get_x_bounds

```

Now set the momentum fraction and compute t_0 and t_1 .

The calculation of t_1 is subject to numerical problems. The exact formula is ($s = m_i^2$, $u = m_r^2$)

$$t_1 = -2\bar{x}E^2 + m_i^2 + m_r^2 + 2\bar{x}\sqrt{E^2 - m_i^2}\sqrt{E^2 - m_r^2/\bar{x}^2}. \quad (10.11)$$

The structure-function paradigm is useful only if $E \gg m_i, m_r$. In a Taylor expansion for large E , the leading term cancels. The expansion of the square roots (to subleading order) yields

$$t_1 = xm_i^2 - \frac{x}{\bar{x}}m_r^2. \quad (10.12)$$

There are two cases of interest: $m_i = m_o$ and $m_r = 0$,

$$t_1 = xm_o^2 \quad (10.13)$$

and $m_i = m_r$ and $m_o = 0$,

$$t_1 = -\frac{x^2}{\bar{x}}m_i^2. \quad (10.14)$$

In both cases, $t_1 \leq m_o^2$.

```

<SF aux: public>+≡
public :: splitting_set_t_bounds

```

```

<SF aux: procedures>+≡
  elemental subroutine splitting_set_t_bounds (d, x, xb)
    type(splitting_data_t), intent(inout) :: d
    real(default), intent(in) :: x, xb
    real(default) :: tp, tm
    d%x = x
    d%xb = xb
    if (d%xb /= 0) then
      d%pb = sqrt (max (d%E**2 - d%u / d%xb**2, 0._default))
    else
      d%pb = 0
    end if
    tp = -2 * xb * d%E**2 + d%s + d%u
    tm = -2 * xb * d%p * d%pb
    d%t0 = tp + tm
    ! d%t1 = tp - tm
    if (d%xb /= 0) then
      d%t1 = x * (d%s - d%u / d%xb)
    else
      d%t1 = 0
    end if
  end subroutine splitting_set_t_bounds

```

These bounds may be narrowed by external cutoffs. Necessary in particular, if $m = 0$ and $t_1 = 0$.

```

<SF aux: public>+≡
  public :: splitting_narrow_t_bounds

<SF aux: procedures>+≡
  subroutine splitting_narrow_t_bounds (d, qmin, qmax)
    type(splitting_data_t), intent(inout) :: d
    real(default), intent(in), optional :: qmin, qmax
    if (present (qmax)) d%t0 = max (d%t0, - qmax ** 2)
    if (present (qmin)) d%t1 = min (d%t1, - qmin ** 2)
  end subroutine splitting_narrow_t_bounds

```

Compute a value for the momentum transfer t , using a random number r . We assume a logarithmic distribution for $t - m^2$, corresponding to the propagator $1/(t - m^2)$ with the physical mass m for the outgoing particle. Optionally, we can narrow the kinematical bounds.

```

<SF aux: public>+≡
  public :: splitting_sample_t

<SF aux: procedures>+≡
  subroutine splitting_sample_t (d, r, t0, t1)
    type(splitting_data_t), intent(inout) :: d
    real(default), intent(in) :: r
    real(default), intent(in), optional :: t0, t1
    real(default) :: tt0, tt1, tt0m, tt1m
    tt0 = d%t0; if (present (t0)) tt0 = max (t0, tt0)
    tt1 = d%t1; if (present (t1)) tt1 = min (t1, tt1)
    tt0m = tt0 - d%m2
    tt1m = tt1 - d%m2

```

```

    if (tt0m < 0 .and. tt1m < 0) then
        d%t = d%m2 + tt0m * exp (r * log (tt1m / tt0m))
    else
        d%t = tt1
    end if
end subroutine splitting_sample_t

```

State that we can ignore recoil. The momentum transfer t is set to its upper limit (which is zero for massless particles).

```

<SF aux: public>+≡
    public :: splitting_set_collinear

<SF aux: procedures>+≡
    elemental subroutine splitting_set_collinear (d)
        type(splitting_data_t), intent(inout) :: d
        d%t = d%t1
    end subroutine splitting_set_collinear

```

This is trivial, but provided for convenience:

```

<SF aux: public>+≡
    public :: splitting_sample_phi

<SF aux: procedures>+≡
    subroutine splitting_sample_phi (d, r)
        type(splitting_data_t), intent(inout) :: d
        real(default), intent(in) :: r
        d%phi = (1-r) * d%phi0 + r * d%phi1
    end subroutine splitting_sample_phi

```

In this function, we actually perform the splitting. The incoming momentum k is split into (if no recoil) $q_1 = (1 - x)k$ and $q_2 = xk$.

Apart from the splitting data, we need the incoming momentum k , the momentum transfer t , and the azimuthal angle ϕ . The momentum fraction x is already known here.

Alternatively, we can split without recoil. The azimuthal angle is irrelevant, and the momentum transfer is always equal to the upper limit t_1 , so the polar angle is zero. Still, we have to account for nonvanishing invariant masses.

```

<SF aux: public>+≡
    public :: split_momentum

<SF aux: procedures>+≡
    function split_momentum (k, d) result (q)
        type(vector4_t), dimension(2) :: q
        type(vector4_t), intent(in) :: k
        type(splitting_data_t), intent(in) :: d
        real(default) :: ct, st, cp, sp
        type(lorentz_transformation_t) :: rot
        real(default) :: tt0, tt1, den
        type(vector3_t) :: kk, q1, q2
        if (d%t < d%t1) then
            tt0 = d%t - d%t0
            tt1 = d%t - d%t1
            den = 2 * d%xb * d%p * d%pb

```

```

      ct = (tt0 + tt1) / (2 * den)
      st = - (tt0 * tt1) / den**2
      cp = cos (d%phi)
      sp = sin (d%phi)
      rot = rotation_to_2nd (3, space_part (k))
      q1 = vector3_moving (d%xb * d%pb * (/ st * cp, st * sp, ct /))
      q2 = vector3_moving (d%p, 3) - q1
      q(1) = rot * vector4_moving (d%xb * d%E, q1)
      q(2) = rot * vector4_moving (d%x * d%E, q2)
    else if (d%s /= 0 .or. d%u /= 0) then
      kk = space_part (k)
      q1 = d%xb * (d%pb / d%p) * kk
      q2 = kk - q1
      q(1) = vector4_moving (d%xb * d%E, q1)
      q(2) = vector4_moving (d%x * d%E, q2)
    else
      q(1) = d%xb * k
      q(2) = d%x * k
    end if
  end function split_momentum

```

10.1.2 Mass-shell projection

Momenta generated by splitting will in general be off-shell. They are on-shell only if they are collinear and massless. This subroutine puts them on shell by brute force, violating either momentum or energy conservation. The direction of three-momentum is always retained.

```

<SF aux: parameters>≡
  integer, parameter, public :: KEEP_ENERGY = 0, KEEP_MOMENTUM = 1

<SF aux: public>+≡
  public :: on_shell

<SF aux: procedures>+≡
  elemental subroutine on_shell (p, mass, keep)
    type(vector4_t), intent(inout) :: p
    real(default), intent(in) :: mass
    integer, intent(in) :: keep
    real(default) :: E, pn
    select case (keep)
    case (KEEP_ENERGY)
      E = energy (p)
      pn = sqrt (max (E**2 - mass**2, 0._default))
      p = vector4_moving (E, pn * direction (space_part (p)))
    case (KEEP_MOMENTUM)
      E = sqrt (space_part (p) ** 2 + mass **2)
      p = vector4_moving (E, space_part (p))
    end select
  end subroutine on_shell

```


10.2 Photon radiation: ISR

```

⟨sf_isr.f90⟩≡
  ⟨File header⟩

  module sf_isr

    ⟨Use kinds⟩
    ⟨Use strings⟩
    use constants, only: pi !NODEP!
    ⟨Use file utils⟩
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use sm_physics, only: Li2 !NODEP!
    use models
    use flavors
    use colors
    use quantum_numbers
    use state_matrices
    use polarizations
    use interactions
    use sf_aux

    ⟨Standard module head⟩

    ⟨ISR: public⟩

    ⟨ISR: parameters⟩

    ⟨ISR: types⟩

    contains

    ⟨ISR: procedures⟩

  end module sf_isr

```

10.2.1 Physics

The ISR structure function is in the most crude approximation (LLA without α corrections, i.e. ϵ^0)

$$f_0(x) = \epsilon(1-x)^{-1+\epsilon} \quad \text{with} \quad \epsilon = \frac{\alpha}{\pi} q_e^2 \ln \frac{s}{m^2}, \quad (10.15)$$

where m is the mass of the incoming (and outgoing) particle, which is initially assumed on-shell.

Here, the form of ϵ results from the kinematical bounds for the momentum squared of the outgoing particle, which in the limit $m^2 \ll s$ are given by

$$t_0 = -2\bar{x}E(E+p) + m^2 \approx -\bar{x}s, \quad (10.16)$$

$$t_1 = -2\bar{x}E(E-p) + m^2 \approx xm^2, \quad (10.17)$$

so the integration over the propagator $1/(t - m^2)$ yields

$$\ln \frac{t_0 - m^2}{t_1 - m^2} = \ln \frac{s}{m^2}. \quad (10.18)$$

In $f_0(x)$, there is an integrable singularity at $x = 1$ which does not spoil the integration, but would lead to an unbounded f_{\max} . Therefore, we map this singularity like

$$x = 1 - (1 - x')^{1/\epsilon} \quad (10.19)$$

such that

$$\int dx f_0(x) = \int dx' \quad (10.20)$$

The structure function has three parameters: α , m_{in} of the incoming particle and s , the hard scale. Internally, we store the exponent ϵ which is the relevant parameter. (In conventional notation, $\epsilon = \beta/2$.) As defaults, we take the actual values of α (which is probably $\alpha(s)$), the actual mass m_{in} and the squared total c.m. energy s .

Including ϵ , ϵ^2 , and ϵ^3 corrections, the successive approximation of the ISR structure function read

$$f_0(x) = \epsilon(1 - x)^{-1+\epsilon} \quad (10.21)$$

$$f_1(x) = g_1(\epsilon) f_0(x) - \frac{\epsilon}{2}(1 + x) \quad (10.22)$$

$$f_2(x) = g_2(\epsilon) f_0(x) - \frac{\epsilon}{2}(1 + x) - \frac{\epsilon^2}{8} \left(\frac{1 + 3x^2}{1 - x} \ln x + 4(1 + x) \ln(1 - x) + 5 + x \right) \quad (10.23)$$

$$\begin{aligned} f_3(x) = & g_3(\epsilon) f_0(x) - \frac{\epsilon}{2}(1 + x) \\ & - \frac{\epsilon^2}{8} \left(\frac{1 + 3x^2}{1 - x} \ln x + 4(1 + x) \ln(1 - x) + 5 + x \right) \\ & - \frac{\epsilon^3}{48} \left((1 + x) [6 \text{Li}_2(x) + 12 \ln^2(1 - x) - 3\pi^2] + 6(x + 5) \ln(1 - x) \right. \\ & \quad \left. + \frac{1}{1 - x} \left[\frac{3}{2}(1 + 8x + 3x^2) \ln x + 12(1 + x^2) \ln x \ln(1 - x) \right. \right. \\ & \quad \left. \left. - \frac{1}{2}(1 + 7x^2) \ln^2 x + \frac{1}{4}(39 - 24x - 15x^2) \right] \right) \end{aligned} \quad (10.24)$$

where the successive approximations to the prefactor of the leading singularity

$$g(\epsilon) = \frac{\exp\left(\epsilon(-\gamma_E + \frac{3}{4})\right)}{\Gamma(1 + \epsilon)}, \quad (10.25)$$

are given by

$$g_0(\epsilon) = 1 \quad (10.26)$$

$$g_1(\epsilon) = 1 + \frac{3}{4}\epsilon \quad (10.27)$$

$$g_2(\epsilon) = 1 + \frac{3}{4}\epsilon + \frac{27 - 8\pi^2}{96}\epsilon^2 \quad (10.28)$$

$$g_3(\epsilon) = 1 + \frac{3}{4}\epsilon + \frac{27 - 8\pi^2}{96}\epsilon^2 + \frac{27 - 24\pi^2 + 128\zeta(3)}{384}\epsilon^3, \quad (10.29)$$

where, numerically

$$\zeta(3) = 1.20205690315959428539973816151\dots \quad (10.30)$$

Although one could calculate the function $g(\epsilon)$ exactly, truncating its Taylor expansion ensures the exact normalization of the truncated structure function at each given order:

$$\int_0^1 dx f_i(x) = 1 \quad \text{for all } i. \quad (10.31)$$

Effectively, the $O(\epsilon)$ correction reduces the low- x tail of the structure function by 50% while increasing the coefficient of the singularity by $O(\epsilon)$. Relative to this, the $O(\epsilon^2)$ correction slightly enhances $x > \frac{1}{2}$ compared to $x < \frac{1}{2}$. At $x = 0$, $f_2(x)$ introduces a logarithmic singularity which should be cut off at $x_0 = O(e^{-1/\epsilon})$: for lower x the perturbative series breaks down. The f_3 correction is slightly positive for low x values and negative near $x = 1$, where the Li_2 piece slightly softens the singularity at $x = 1$.

Instead of the definition for ϵ given above, it is customary to include a universal nonlogarithmic piece:

$$\epsilon = \frac{\alpha}{\pi} q_e^2 \left(\ln \frac{s}{m^2} - 1 \right) \quad (10.32)$$

10.2.2 Implementation

In the concrete implementation, the zeroth order mapping (10.19) is implemented, and the Jacobian is equal to $f_i(x)/f_0(x)$. This can be written as

$$\frac{f_0(x)}{f_0(x)} = 1 \quad (10.33)$$

$$\frac{f_1(x)}{f_0(x)} = 1 + \frac{3}{4}\epsilon - \frac{1 - x^2}{2(1 - x')} \quad (10.34)$$

$$\begin{aligned} \frac{f_2(x)}{f_0(x)} = 1 + \frac{3}{4}\epsilon + \frac{27 - 8\pi^2}{96}\epsilon^2 - \frac{1 - x^2}{2(1 - x')} \\ - \frac{(1 + 3x^2) \ln x + (1 - x)(4(1 + x) \ln(1 - x) + 5 + x)}{8(1 - x')} \epsilon \end{aligned} \quad (10.35)$$

For $x = 1$ (i.e., numerically indistinguishable from 1), this reduces to

$$\frac{f_0(x)}{f_0(x)} = 1 \quad (10.36)$$

$$\frac{f_1(x)}{f_0(x)} = 1 + \frac{3}{4}\epsilon \quad (10.37)$$

$$\frac{f_2(x)}{f_0(x)} = 1 + \frac{3}{4}\epsilon + \frac{27 - 8\pi^2}{96}\epsilon^2 \quad (10.38)$$

The last line in (10.35) is zero for

$$x_{\min} = 0.00714053329734592839549810275603 \quad (10.39)$$

(Mathematica result), independent of ϵ . For x values less than this we ignore this correction because of the logarithmic singularity which should in principle be resummed.

10.2.3 The ISR data block

```

<ISR: public>≡
  public :: isr_data_t
<ISR: types>≡
  type :: isr_data_t
    private
      type(model_t), pointer :: model => null ()
      type(flavor_t) :: flv
      real(default) :: alpha = 0
      real(default) :: q_max = 0
      real(default) :: real_mass = 0
      real(default) :: mass = 0
      real(default) :: eps = 0
      real(default) :: log = 0
      integer :: order = 3
      integer :: error = NONE
  end type isr_data_t

```

Error codes

```

<ISR: parameters>≡
  integer, parameter :: NONE = 0
  integer, parameter :: ZERO_MASS = 1
  integer, parameter :: Q_MAX_TOO_SMALL = 2
  integer, parameter :: EPS_TOO_LARGE = 3
  integer, parameter :: INVALID_ORDER = 4

```

Generate flavor-dependent ISR data:

```

<ISR: public>+≡
  public :: isr_data_init
<ISR: procedures>≡
  subroutine isr_data_init (data, model, flv, alpha, q_max, mass)
    type(isr_data_t), intent(out) :: data
    type(model_t), intent(in), target :: model
    type(flavor_t), intent(in) :: flv

```

```

real(default), intent(in) :: alpha
real(default), intent(in) :: q_max
real(default), intent(in), optional :: mass
data%model => model
data%flv = flv
data%alpha = alpha
data%q_max = q_max
data%real_mass = flavor_get_mass (flv)
if (present (mass)) then
  if (mass > 0) then
    data%mass = mass
  else
    data%mass = data%real_mass
  end if
else
  data%mass = data%real_mass
end if
if (data%mass == 0) then
  data%error = ZERO_MASS; return
else if (data%mass >= data%q_max) then
  data%error = Q_MAX_TOO_SMALL; return
end if
data%log = log (1 + (data%q_max / data%mass)**2)
data%eps = data%alpha / pi &
  * flavor_get_charge (data%flv)**2 &
  * (2 * log (data%q_max / data%mass) - 1)
if (data%eps > 1) then
  data%error = EPS_TOO_LARGE; return
end if
end subroutine isr_data_init

```

Explicitly set ISR order

```

<ISR: public>+≡
  public :: isr_data_set_order

<ISR: procedures>+≡
  elemental subroutine isr_data_set_order (data, order)
    type(isr_data_t), intent(inout) :: data
    integer, intent(in) :: order
    if (order < 0 .or. order > 3) then
      data%error = INVALID_ORDER
    else
      data%order = order
    end if
  end subroutine isr_data_set_order

```

Handle error conditions. Should always be done after initialization, unless we are sure everything is ok.

```

<ISR: public>+≡
  public :: isr_data_check

<ISR: procedures>+≡
  subroutine isr_data_check (data)
    type(isr_data_t), intent(in) :: data

```

```

select case (data%error)
case (ZERO_MASS)
  call msg_fatal (" ISR: Particle mass is zero")
case (Q_MAX_TOO_SMALL)
  call msg_fatal (" ISR: Particle mass exceeds Qmax")
case (EPS_TOO_LARGE)
  call msg_fatal (" ISR: Expansion parameter too large, perturbative expansion breaks down")
case (INVALID_ORDER)
  call msg_error (" ISR: LLA order invalid (valid values are 0,1,2,3)")
end select
end subroutine isr_data_check

```

Output

<ISR: public>+≡

```
public :: isr_data_write
```

<ISR: procedures>+≡

```

subroutine isr_data_write (data, unit, md5)
  type(isr_data_t), intent(in) :: data
  integer, intent(in), optional :: unit
  integer :: u
  logical, intent(in), optional :: md5
  u = output_unit (unit); if (u < 0) return
  write (u, *) "ISR data:"
  write (u, *) " prt   = ", char (flavor_get_name (data%flv))
  write (u, *) " alpha = ", data%alpha
  write (u, *) " q_max = ", data%q_max
  write (u, *) " mass  = ", data%mass
  write (u, *) " eps   = ", data%eps
  write (u, *) " log    = ", data%log
  write (u, *) " order  = ", data%order
end subroutine isr_data_write

```

10.2.4 The ISR object

The `isr_t` data type is a $1 \rightarrow 2$ interaction, i.e., we allow for single-photon emission only (but use the multi-photon resummed radiator function). The particles are ordered as (incoming, photon, outgoing).

There is no need to handle several flavors (and data blocks) in parallel, since ISR is always applied immediately after beam collision. (ISR for partons is accounted for by the PDFs themselves.) Polarization is carried through, i.e., we retain the polarization of the incoming particle and treat the emitted photon as unpolarized. Color is trivially carried through. This implies that particles 1 and 3 should be locked together.

<ISR: public>+≡

```
public :: interaction_init_isr
```

<ISR: procedures>+≡

```

subroutine interaction_init_isr (int, data)
  type(interaction_t), intent(out) :: int
  type(isr_data_t), intent(in) :: data
  type(quantum_numbers_mask_t), dimension(3) :: mask

```

```

integer, dimension(3) :: hel_lock
type(polarization_t) :: pol
type(quantum_numbers_t), dimension(1) :: qn_fc, qn_hel
type(flavor_t) :: flv_photon
type(quantum_numbers_t) :: qn_photon, qn
type(state_iterator_t) :: it_hel
mask = new_quantum_numbers_mask (.false., .false., &
    mask_h = (/ .false., .true., .false. /))
hel_lock = (/ 3, 0, 1 /)
call interaction_init &
    (int, 1, 0, 2, mask=mask, hel_lock=hel_lock, set_relations=.true.)
call flavor_init (flv_photon, PHOTON, data%model)
call quantum_numbers_init (qn_photon, flv_photon)
call polarization_init_generic (pol, data%flv)
call quantum_numbers_init (qn_fc(1), &
    flv = data%flv, col = color_from_flavor (data%flv))
call state_iterator_init (it_hel, pol%state)
do while (state_iterator_is_valid (it_hel))
    qn_hel = state_iterator_get_quantum_numbers (it_hel)
    qn = qn_hel(1) .merge. qn_fc(1)
    call interaction_add_state (int, (/ qn, qn_photon, qn /))
    call state_iterator_advance (it_hel)
end do
call polarization_final (pol)
call interaction_freeze (int)
end subroutine interaction_init_isr

```

10.2.5 ISR structure function

The ISR structure function allows for a straightforward mapping of the unit interval. So, to leading order, the structure function value is unity, but the x value is transformed. Higher orders affect the function value.

The structure function implementation applies the above mapping to the input (random) number r to generate the momentum fraction x and the function value f . For numerical stability reasons, we also output xb , which is $\bar{x} = 1 - x$. The mapping ensures that $f = 1$ at leading order, and the higher-order corrections are well-behaved.

If the `no_map` flag is set, we do not apply this mapping.

(ISR: procedures)+≡

```

subroutine strfun (f, x, xb, r, data, no_map)
    real(default), intent(out) :: f, x, xb
    real(default), intent(in) :: r
    type(isr_data_t), intent(in) :: data
    logical, intent(in) :: no_map
    real(default) :: eps
    real(default) :: rb, log_x, log_xb, x_2
    real(default), parameter :: &
        & xmin = 0.00714053329734592839549810275603_default
    real(default), parameter :: &
        & zeta3 = 1.20205690315959428539973816151_default
    real(default), parameter :: &

```

```

      & g1 = 3._default / 4._default, &
      & g2 = (27 - 8*pi**2) / 96._default, &
      & g3 = (27 - 24*pi**2 + 128*zeta3) / 384._default
eps = data%eps
rb = 1 - r
if (no_map) then
  xb = rb
  f = xb ** (-1 + eps)
else
  if (rb < tiny(1._default)**eps) then
    xb = 0
  else
    xb = rb**(1/eps)
  end if
  f = 1
end if
x = 1 - xb
if (data%order > 0) then
  f = f * (1 + g1 * eps)
  x_2 = x*x
  if (rb>0) f = f * (1 - (1-x_2) / (2 * rb))
  if (data%order > 1) then
    f = f * (1 + g2 * eps**2)
    if (rb>0 .and. xb>0 .and. x>xmin) then
      log_x = log (x)
      log_xb = log (xb)
      f = f * (1 - ((1+3*x_2)*log_x + xb * (4*(1+x)*log_xb + 5 + x)) &
        / ( 8 * rb) * eps)
    end if
    if (data%order > 2) then
      f = f * (1 + g3 * eps**3)
      if (rb > 0 .and. xb > 0 .and. x > xmin) then
        f = f * (1 - ((1+x) * xb &
          * (6 * Li2(x) + 12 * log_xb**2 - 3 * pi**2) &
          + 1.5_default * (1 + 8*x + 3*x_2) * log_x &
          + 6 * (x+5) * xb * log_xb &
          + 12 * (1+x_2) * log_x * log_xb &
          - (1 + 7*x_2) * log_x**2 / 2 &
          + (39 - 24*x - 15*x_2) / 4) &
          / ( 48 * rb) * eps**2)
      end if
    end if
  end if
end if
end subroutine strfun

```

10.2.6 ISR application

For ISR, we can compute kinematics and function value in a single step. This function works on a single beam, assuming that the input momentum has been set. We need four random numbers as input: one for x , one for Q^2 , and two for the polar and azimuthal angles. Alternatively, we can skip p_T generation;

in this case, we only need one.

After splitting momenta, we set the outgoing momenta on-shell. We choose to conserve momentum, so energy conservation may be violated.

```

<ISR: public>+≡
    public :: interaction_apply_isr

<ISR: procedures>+≡
    subroutine interaction_apply_isr (int, r, isr_data, no_map)
        type(interaction_t), intent(inout) :: int
        real(default), dimension(:), intent(in) :: r
        type(isr_data_t), intent(in) :: isr_data
        logical, intent(in) :: no_map
        type(vector4_t) :: k
        type(splitting_data_t) :: sd
        real(default) :: f, x, xb
        k = interaction_get_momentum (int, 1)
        sd = new_splitting_data (k, isr_data%mass**2, 0._default, isr_data%mass)
        call strfun (f, x, xb, r(1), isr_data, no_map)
        call interaction_set_matrix_element (int, cmplx (f, kind=default))
        call splitting_set_t_bounds (sd, x, xb)
        select case (size (r))
        case (1)
            call splitting_set_collinear (sd)
        case (3)
            call splitting_sample_t (sd, r(2))
            call splitting_sample_phi (sd, r(3))
        case default
            print *, "n_rand = ", size (r)
            call msg_bug (" ISR: number of random numbers must be 1 or 3")
        end select
        call interaction_set_momenta &
            (int, split_momentum (k, sd), outgoing=.true.)
    end subroutine interaction_apply_isr

```

10.3 EPA

```

⟨sf_epa.f90⟩≡
  ⟨File header⟩

  module sf_epa

    ⟨Use kinds⟩
    ⟨Use strings⟩
    use constants, only: pi !NODEP!
    ⟨Use file utils⟩
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use models
    use flavors
    use colors
    use quantum_numbers
    use state_matrices
    use polarizations
    use interactions
    use sf_aux

    ⟨Standard module head⟩

    ⟨EPA: public⟩

    ⟨EPA: parameters⟩

    ⟨EPA: types⟩

    contains

    ⟨EPA: procedures⟩

  end module sf_epa

```

10.3.1 Physics

The EPA structure function for a photon inside an (elementary) particle p with energy E , mass m and charge q_p (e.g., electron) is given by ($\bar{x} \equiv 1 - x$)

$$f(x) = \frac{\alpha}{\pi} q_p^2 \frac{1}{x} \left[\left(\bar{x} + \frac{x^2}{2} \right) \ln \frac{Q_{\max}^2}{Q_{\min}^2} - \left(1 - \frac{x}{2} \right)^2 \ln \frac{x^2 + \frac{Q_{\max}^2}{E^2}}{x^2 + \frac{Q_{\min}^2}{E^2}} - x^2 \frac{m^2}{Q_{\min}^2} \left(1 - \frac{Q_{\min}^2}{Q_{\max}^2} \right) \right]. \quad (10.40)$$

If no explicit Q bounds are provided, the kinematical bounds are

$$-Q_{\max}^2 = t_0 = -2\bar{x}(E^2 + p\bar{p}) + 2m^2 \approx -4\bar{x}E^2, \quad (10.41)$$

$$-Q_{\min}^2 = t_1 = -2\bar{x}(E^2 - p\bar{p}) + 2m^2 \approx -\frac{x^2}{\bar{x}}m^2. \quad (10.42)$$

The second and third terms in (10.40) are negative definite (and subleading). Noting that $\bar{x} + x^2/2$ is bounded between $1/2$ and 1 , we derive that $f(x)$ is always

smaller than

$$\bar{f}(x) = \frac{\alpha}{\pi} q_p^2 \frac{L - 2 \ln x}{x} \quad \text{where} \quad L = \ln \frac{\min(4E_{\max}^2, Q_{\max}^2)}{\max(m^2, Q_{\min}^2)}, \quad (10.43)$$

where we allow for explicit Q bounds that narrow the kinematical range. Therefore, we generate this distribution:

$$\int_{x_0}^{x_1} dx \bar{f}(x) = C(x_0, x_1) \int_0^1 dx' \quad (10.44)$$

We set

$$\ln x = \frac{1}{2} \left\{ L - \sqrt{L^2 - 4 [x' \ln x_1 (L - \ln x_1) + \bar{x}' \ln x_0 (L - \ln x_0)]} \right\} \quad (10.45)$$

such that $x(0) = x_0$ and $x(1) = x_1$ and

$$\frac{dx}{dx'} = \left(\frac{\alpha}{\pi} \right)^{-1} x \frac{C(x_0, x_1)}{L - 2 \ln x} \quad (10.46)$$

with

$$C(x_0, x_1) = \frac{\alpha}{\pi} q_p^2 [\ln x_1 (L - \ln x_1) - \ln x_0 (L - \ln x_0)] \quad (10.47)$$

such that (10.44) is satisfied. Finally, we have

$$\int_{x_0}^{x_1} dx f(x) = C(x_0, x_1) \int_0^1 dx' \frac{f(x(x'))}{\bar{f}(x(x'))} \quad (10.48)$$

where x' is calculated from x via (10.45)

10.3.2 The EPA data block

The EPA parameters are: α , E_{\max} , m , Q_{\min} , and x_{\min} . Instead of m we can use the incoming particle PDG code as input; from this we can deduce the mass and charge.

Internally we store in addition $C_{0/1} = \frac{\alpha}{\pi} q_e^2 \ln x_{0/1} (L - \ln x_{0/1})$, the c.m. energy squared and the incoming particle mass.

```

<EPA: public>≡
  public :: epa_data_t
<EPA: types>≡
  type :: epa_data_t
    private
    type(model_t), pointer :: model => null ()
    type(flavor_t) :: flv
    real(default) :: alpha
    real(default) :: x_min
    real(default) :: x_max
    real(default) :: q_min
    real(default) :: q_max
    real(default) :: E_max
    real(default) :: mass
    real(default) :: log
    real(default) :: c0
    real(default) :: c1
    integer :: error = 0
  end type epa_data_t

```

Error codes

```

(EPA: parameters)≡
    integer, parameter :: NONE = 0
    integer, parameter :: ZERO_QMIN = 1
    integer, parameter :: Q_MAX_TOO_SMALL = 2
    integer, parameter :: ZERO_XMIN = 3

(EPA: public)+≡
    public :: epa_data_init

(EPA: procedures)≡
    subroutine epa_data_init (data, model, flv, alpha, x_min, q_min, E_max, mass)
        type(epa_data_t), intent(inout) :: data
        type(model_t), intent(in), target :: model
        type(flavor_t), intent(in) :: flv
        real(default), intent(in) :: alpha, x_min, q_min, E_max
        real(default), intent(in), optional :: mass
        data%model => model
        data%flv = flv
        data%alpha = alpha
        data%E_max = E_max
        data%x_min = x_min
        data%x_max = 1
        if (data%x_min == 0) then
            data%error = ZERO_XMIN; return
        end if
        data%q_min = q_min
        data%q_max = 2 * data%E_max
        select case (char (model_get_name (data%model)))
        case ("QCD","Test")
            call msg_fatal ("EPA structure function not available for model " &
                // char (model_get_name (data%model)) // ".")
        end select
        if (present (mass)) then
            data%mass = mass
        else
            data%mass = flavor_get_mass (flv)
        end if
        if (max (data%mass, data%q_min) == 0) then
            data%error = ZERO_QMIN; return
        else if (max (data%mass, data%q_min) >= data%E_max) then
            data%error = Q_MAX_TOO_SMALL; return
        end if
        data%log = log (4 * (data%E_max / max (data%mass, data%q_min)) ** 2 )
        data%c0 = data%alpha / pi &
            * flavor_get_charge (data%flv)**2 &
            * log (data%x_min) * (data%log - log (data%x_min))
        data%c1 = data%alpha / pi &
            * flavor_get_charge (data%flv)**2 &
            * log (data%x_max) * (data%log - log (data%x_max))
    end subroutine epa_data_init

```

Handle error conditions. Should always be done after initialization, unless we are sure everything is ok.

```

(EPA: public)+≡

```

```

public :: epa_data_check
(EPA: procedures)+≡
subroutine epa_data_check (data)
  type(epa_data_t), intent(in) :: data
  select case (data%error)
  case (ZERO_QMIN)
    call msg_fatal (" EPA: Particle mass is zero")
  case (Q_MAX_TOO_SMALL)
    call msg_fatal (" EPA: Particle mass exceeds Qmax")
  case (ZERO_XMIN)
    call msg_fatal (" EPA: x_min must be larger than zero")
  end select
end subroutine epa_data_check

```

Output

```

(EPA: public)+≡
public :: epa_data_write
(EPA: procedures)+≡
subroutine epa_data_write (data, unit, md5)
  type(epa_data_t), intent(in) :: data
  integer, intent(in), optional :: unit
  integer :: u
  logical, intent(in), optional :: md5
  u = output_unit (unit); if (u < 0) return
  write (u, *) "EPA data:"
  write (u, *) " prt  = ", char (flavor_get_name (data%flv))
  write (u, *) " alpha = ", data%alpha
  write (u, *) " x_min = ", data%x_min
  write (u, *) " x_max = ", data%x_max
  write (u, *) " q_min = ", data%q_min
  write (u, *) " q_max = ", data%q_max
  write (u, *) " E_max = ", data%q_max
  write (u, *) " mass  = ", data%mass
  write (u, *) " log   = ", data%log
  write (u, *) " c0    = ", data%c0
  write (u, *) " c1    = ", data%c1
end subroutine epa_data_write

```

10.3.3 The EPA object

The `epa_t` data type is a $1 \rightarrow 2$ interaction. We should be able to handle several flavors in parallel, since EPA is not necessarily applied immediately after beam collision: Photons may be radiated from quarks. In that case, the partons are massless and q_{\min} applies instead, so we do not need to generate several kinematical configurations in parallel.

The particles are ordered as (incoming, radiated, photon), where the photon initiates the hard interaction.

We generate an unpolarized photon and transfer initial polarization to the radiated parton. Color is transferred in the same way.

```

(EPA: public)+≡
public :: interaction_init_epa

```

```

(EPA: procedures)+≡
subroutine interaction_init_epa (int, data)
  type(interaction_t), intent(out) :: int
  type(epa_data_t), intent(in) :: data
  type(quantum_numbers_mask_t), dimension(3) :: mask
  integer, dimension(3) :: hel_lock
  type(polarization_t) :: pol
  type(quantum_numbers_t), dimension(1) :: qn_fc, qn_hel
  type(flavor_t) :: flv_photon
  type(quantum_numbers_t) :: qn_photon, qn
  type(state_iterator_t) :: it_hel
  mask = new_quantum_numbers_mask (.false., .false., &
    mask_h = (/ .false., .false., .true. /))
  hel_lock = (/ 2, 1, 0 /)
  call interaction_init &
    (int, 1, 0, 2, mask=mask, hel_lock=hel_lock, set_relations=.true.)
  call flavor_init (flv_photon, PHOTON, data%model)
  call quantum_numbers_init (qn_photon, flv_photon)
  call polarization_init_generic (pol, data%flv)
  call quantum_numbers_init (qn_fc(1), &
    flv = data%flv, col = color_from_flavor (data%flv))
  call state_iterator_init (it_hel, pol%state)
  do while (state_iterator_is_valid (it_hel))
    qn_hel = state_iterator_get_quantum_numbers (it_hel)
    qn = qn_hel(1) .merge. qn_fc(1)
    call interaction_add_state (int, (/ qn, qn, qn_photon /))
    call state_iterator_advance (it_hel)
  end do
  call polarization_final (pol)
  call interaction_freeze (int)
end subroutine interaction_init_epa

```

10.3.4 EPA structure function

The EPA structure function allows for a straightforward mapping of the unit interval. So, to leading order, the structure function value is unity, but the x value is transformed. Higher orders affect the function value.

The structure function implementation applies the above mapping to the input (random) number r to generate the momentum fraction x and the function value f . For numerical stability reasons, we also output xb , which is $\bar{x} = 1 - x$. The mapping ensures that $f = 1$ at leading order, and the higher-order corrections are well-behaved.

If `no_map` is set, the mapping is switched off, and we have to divide by $C(x_0, x_1)/(xf(x))$ to get back the original $f(x)$.

```

(EPA: procedures)+≡
elemental subroutine strfun (f, x, xb, r, E, data, no_map)
  real(default), intent(out) :: f, x, xb
  real(default), intent(in) :: r, E
  type(epa_data_t), intent(in) :: data
  logical, intent(in) :: no_map
  real(default) :: rb, lx0, lx1, lx, d, den

```

```

real(default) :: qmaxsq, qminsq
f = 0
rb = 1 - r
if (no_map) then
  x = r
  if (data%x_min < x .and. x < data%x_max) then
    den = (log (data%x_max) * (data%log - log (data%x_max)) &
      - log (data%x_min) * (data%log - log (data%x_min))) / x
  else
    den = 0
  end if
else
  lx0 = log (data%x_min)
  lx1 = log (data%x_max)
  d = data%log ** 2 &
    - 4 * (r * lx1 * (data%log - lx1) + rb * lx0 * (data%log - lx0))
  if (d <= 0) then
    return
  else
    lx = (data%log - sqrt (d)) / 2
  end if
  x = exp (lx)
  den = data%log - 2 * lx
end if
if (den <= 0) return
xb = 1 - x
qminsq = max (x ** 2 / xb * data%mass ** 2, data%q_min ** 2)
qmaxsq = min (4 * E ** 2, data%q_max ** 2)
if (qminsq < qmaxsq) then
  f = ((xb + x ** 2 / 2) * log (qmaxsq / qminsq) &
    - (1 - x / 2) ** 2 &
    * log ((x**2 + qmaxsq / E ** 2) / (x**2 + qminsq / E ** 2)) &
    - x ** 2 * data%mass ** 2 / qminsq * (1 - qminsq / qmaxsq)) &
    * ( data%c1 - data%c0 ) / den
end if
end subroutine strfun

```

10.3.5 EPA application

For EPA, we can compute kinematics and function value in a single step. This function works on a single beam, assuming that the input momentum has been set. We need four random numbers as input: one for x , one for Q^2 , and two for the polar and azimuthal angles. Alternatively, we can skip p_T generation; in this case, we only need one.

For obtaining splitting kinematics, we rely on the assumption that all in-particles are mass-degenerate (or there is only one), so the generated x values are identical.

```

(EPA: public)+≡
  public :: interaction_apply_epa

(EPA: procedures)+≡
  subroutine interaction_apply_epa (int, r, epa_data, no_map)

```

```

type(interaction_t), intent(inout) :: int
real(default), dimension(:), intent(in) :: r
type(epa_data_t), dimension(:), intent(in) :: epa_data
logical, intent(in) :: no_map
type(vector4_t) :: k
type(splitting_data_t) :: sd
real(default), dimension(size(epa_data)) :: f, x, xb
k = interaction_get_momentum (int, 1)
sd = new_splitting_data (k, 0._default, epa_data(1)%mass**2, 0._default)
call strfun (f, x, xb, r(1), energy (k), epa_data, no_map)
call interaction_set_flavored_values &
    (int, cmplx (f, kind=default), epa_data%flv, 2)
call splitting_set_t_bounds (sd, x(1), xb(1))
call splitting_narrow_t_bounds (sd, epa_data(1)%q_min, epa_data(1)%q_max)
select case (size (r))
case (1)
    call splitting_set_collinear (sd)
case (3)
    call splitting_sample_t (sd, r(2))
    call splitting_sample_phi (sd, r(3))
case default
    print *, "n_rand = ", size (r)
    call msg_bug (" EPA: number of random numbers must be 1 or 3")
end select
call interaction_set_momenta &
    (int, split_momentum (k, sd), outgoing=.true.)
end subroutine interaction_apply_epa

```


10.4 EWA

```

⟨sf_ewa.f90⟩≡
  ⟨File header⟩

  module sf_ewa

    ⟨Use kinds⟩
    ⟨Use strings⟩
    ⟨Use file utils⟩
    use constants, only: pi !NODEP!
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use models
    use flavors
    use colors
    use quantum_numbers
    use state_matrices
    use polarizations
    use interactions
    use sf_aux

    ⟨Standard module head⟩

    ⟨EWA: public⟩

    ⟨EWA: parameters⟩

    ⟨EWA: types⟩

    contains

    ⟨EWA: procedures⟩

  end module sf_ewa

```

10.4.1 Physics

The EWA structure function for a Z or W inside a fermion (lepton or quark) depends on the vector-boson polarization. We distinguish transversal (\pm) and longitudinal (0) polarization.

$$F_+(x) = \frac{1}{16\pi^2} \frac{(v-a)^2 + (v+a)^2 \bar{x}^2}{x} \left[\ln \left(\frac{p_{\perp,\max}^2 + \bar{x}M^2}{\bar{x}M^2} \right) - \frac{p_{\perp,\max}^2}{p_{\perp,\max}^2 + \bar{x}M^2} \right] \quad (10.49)$$

$$F_-(x) = \frac{1}{16\pi^2} \frac{(v+a)^2 + (v-a)^2 \bar{x}^2}{x} \left[\ln \left(\frac{p_{\perp,\max}^2 + \bar{x}M^2}{\bar{x}M^2} \right) - \frac{p_{\perp,\max}^2}{p_{\perp,\max}^2 + \bar{x}M^2} \right] \quad (10.50)$$

$$F_0(x) = \frac{v^2 + a^2}{8\pi^2} \frac{2\bar{x}}{x} \frac{p_{\perp,\max}^2}{p_{\perp,\max}^2 + \bar{x}M^2} \quad (10.51)$$

where $p_{\perp,\max}$ is the cutoff in transversal momentum, M is the vector-boson mass, v and a are the vector and axial-vector couplings, and $\bar{x} \equiv 1-x$. Note that the longitudinal structure function is finite for large cutoff, while the transversal structure function is logarithmically divergent.

The maximal transverse momentum is given by the kinematical limit, it is

$$p_{\perp,\max} = \bar{x}\sqrt{s}/2. \quad (10.52)$$

The vector and axial couplings for a fermion branching into a W are

$$v_W = \frac{g}{2\sqrt{2}}, \quad a_W = \frac{g}{2\sqrt{2}}. \quad (10.53)$$

For Z emission, this is replaced by

$$v_Z = \frac{g}{2\cos\theta_w} (t_3 - 2q\sin^2\theta_w), \quad a_Z = \frac{g}{2\cos\theta_w} t_3, \quad (10.54)$$

where $t_3 = \pm\frac{1}{2}$ is the fermion isospin, and q its charge.

For an initial antifermion, the signs of the axial couplings are inverted. Note that a common sign change of v and a is irrelevant.

The EWA depends on the parameters g , $\sin^2\theta_w$, M_W , and M_Z . These can all be taken from the SM input, and the prefactors are calculated from those and the incoming particle type.

Since these structure functions have a $1/x$ singularity (which is not really relevant in practice, however, since the vector boson mass is finite), we map this singularity allowing for nontrivial x bounds:

$$x = \exp(\bar{r} \ln x_0 + r \ln x_1) \quad (10.55)$$

such that

$$\int_{x_0}^{x_1} \frac{dx}{x} = (\ln x_1 - \ln x_0) \int_0^1 dr. \quad (10.56)$$

As a user parameter, we have the cutoff $p_{\perp,\max}$. The divergence $1/x$ also requires a x_0 cutoff; and for completeness we introduce a corresponding x_1 . Physically, the minimal sensible value of x is M^2/s , although the approximation loses its value already at higher x values.

10.4.2 The EWA data block

The EWA parameters are: $p_{T,\max}$, c_V , c_A , and m . Instead of m we can use the incoming particle PDG code as input; from this we can deduce the mass and charges. In the initialization phase it is not yet determined whether a W or a Z is radiated, hence we set the vector and axial-vector couplings equal to the common prefactors $g/2 = e/2/\sin\theta_W$.

In principle, for EWA it would make sense to allow the user to also set the upper bound for x , x_{\max} , but we fix it to one here.

```
<EWA: public>≡
  public :: ewa_data_t
```

```

(EWA: types)≡
  type :: ewa_data_t
  private
    type(model_t), pointer :: model => null ()
    type(flavor_t) :: flv
    real(default) :: pt_max
    real(default) :: sqrts
    real(default) :: x_min
    real(default) :: x_max
    real(default) :: mass
    real(default) :: q_min
    real(default) :: cv
    real(default) :: ca
    real(default) :: costhw
    real(default) :: sinthw
    real(default) :: mW
    real(default) :: mZ
    real(default) :: coeff
    logical :: keep_momentum
    logical :: keep_energy
    integer :: id = 0
    integer :: error = 0
  end type ewa_data_t

```

Error codes

```

(EWA: parameters)≡
  integer, parameter :: NONE = 0
  integer, parameter :: ZERO_QMIN = 1
  integer, parameter :: Q_MAX_TOO_SMALL = 2
  integer, parameter :: ZERO_XMIN = 3

(EWA: public)+≡
  public :: ewa_data_init

(EWA: procedures)≡
  subroutine ewa_data_init (data, model, flv, x_min, q_min, pt_max, &
    sqrts, keep_momentum, keep_energy, mass)
    type(ewa_data_t), intent(inout) :: data
    type(model_t), intent(in), target :: model
    type(flavor_t), intent(in) :: flv
    real(default), intent(in) :: x_min, q_min, pt_max, sqrts
    logical, intent(in) :: keep_momentum, keep_energy
    real(default), intent(in), optional :: mass
    real(default) :: g, ee, sinthw
    data%model => model
    data%flv = flv
    data%pt_max = pt_max
    data%sqrts = sqrts
    data%x_min = x_min
    data%x_max = 1
    if (data%x_min == 0) then
      data%error = ZERO_XMIN; return
    end if
    select case (char (model_get_name (data%model)))
    case ("QCD","QED","Test")

```

```

        call msg_fatal ("EWA structure function not available for model " &
            // char (model_get_name (data%model)) // ".")
    end select
    ee = model_get_parameter_value (data%model, var_str ("ee"))
    data%sinthw = model_get_parameter_value (data%model, var_str ("sw"))
    data%costhw = model_get_parameter_value (data%model, var_str ("cw"))
    data%mZ = model_get_parameter_value (data%model, var_str ("mZ"))
    data%mW = model_get_parameter_value (data%model, var_str ("mW"))
    if (data%sinthw /= 0) then
        g = ee / data%sinthw
    else
        call msg_fatal ("Vanishing value of sin(theta_w).")
    end if
    data%cv = g / 2._default
    data%ca = g / 2._default
    data%coeff = 1._default / (8._default * PI**2)
    data%keep_momentum = keep_momentum
    data%keep_energy = keep_energy
    if (present (mass)) then
        data%mass = mass
    else
        data%mass = flavor_get_mass (flv)
    end if
end subroutine ewa_data_init

```

Handle error conditions. Should always be done after initialization, unless we are sure everything is ok.

```

<EWA: public>+≡
    public :: ewa_data_check

<EWA: procedures>+≡
    subroutine ewa_data_check (data)
        type(ewa_data_t), intent(in) :: data
        select case (data%error)
            case (ZERO_QMIN)
                call msg_fatal (" EWA: Particle mass is zero")
            case (Q_MAX_TOO_SMALL)
                call msg_fatal (" EWA: Particle mass exceeds Qmax")
            case (ZERO_XMIN)
                call msg_fatal (" EWA: x_min must be larger than zero")
        end select
    end subroutine ewa_data_check

```

Set the vector boson ID for distinguishing W and Z bosons.

```

<EWA: public>+≡
    public :: ewa_set_id

<EWA: procedures>+≡
    subroutine ewa_set_id (data, id)
        type (ewa_data_t), intent(inout) :: data
        integer, intent(in) :: id
        data%id = id
    end subroutine ewa_set_id

```

Output

$\langle EWA: public \rangle + \equiv$

```
public :: ewa_data_write
```

$\langle EWA: procedures \rangle + \equiv$

```
subroutine ewa_data_write (data, unit, md5)
  type(ewa_data_t), intent(in) :: data
  integer, intent(in), optional :: unit
  integer :: u
  logical, intent(in), optional :: md5
  u = output_unit (unit); if (u < 0) return
  write (u, *) "EWA data:"
  write (u, *) " prt      = ", char (flavor_get_name (data%flv))
  write (u, *) " x_min    = ", data%x_min
  write (u, *) " x_max    = ", data%x_max
  write (u, *) " pt_max   = ", data%pt_max
  write (u, *) " sqrts    = ", data%sqrts
  write (u, *) " mass     = ", data%mass
  write (u, *) " cv       = ", data%cv
  write (u, *) " ca       = ", data%ca
  write (u, *) " coeff    = ", data%coeff
  write (u, *) " costhw   = ", data%costhw
  write (u, *) " sinthw   = ", data%sinthw
  write (u, *) " mZ       = ", data%mZ
  write (u, *) " mW       = ", data%mW
  write (u, *) " keep_mom. = ", data%keep_momentum
  write (u, *) " keep_en.  = ", data%keep_energy
end subroutine ewa_data_write
```

10.4.3 The EWA object

The `ewa_t` data type is a $1 \rightarrow 2$ interaction. We should be able to handle several flavors in parallel, since EWA is not necessarily applied immediately after beam collision: Photons may be radiated from quarks. In that case, the partons are massless and q_{\min} applies instead, so we do not need to generate several kinematical configurations in parallel.

The particles are ordered as (incoming, radiated, W/Z), where the W/Z initiates the hard interaction.

For EPA, we generate an unpolarized photon and transfer initial polarization to the radiated parton. Color is transferred in the same way. I do not know whether the same can/should be done for EWA, as the structure functions depend on the W/Z polarization. If we are having Z bosons, both up- and down-type fermions can participate. Otherwise, with a W^+ an up-type fermion is transferred to a down-type fermion, and the other way round.

$\langle EWA: public \rangle + \equiv$

```
public :: interaction_init_ewa
```

$\langle EWA: procedures \rangle + \equiv$

```
subroutine interaction_init_ewa (int, data)
  type(interaction_t), intent(out) :: int
  type(ewa_data_t), intent(in) :: data
  type(quantum_numbers_mask_t), dimension(3) :: mask
```

```

integer, dimension(3) :: hel_lock
type(polarization_t) :: pol
type(quantum_numbers_t), dimension(1) :: qn_fc, qn_hel, qn_fc_fin
type(flavor_t) :: flv_z, flv_wp, flv_wm, flv_down, flv_up
type(quantum_numbers_t) :: qn_z, qn_wp, qn_wm, qn, qn_down, &
    qn_up
type(state_iterator_t) :: it_hel
real(default) :: q, t3
integer :: i, isospin, pdg
logical :: up_type
isospin = flavor_get_isospin_type (data%flv)
pdg = flavor_get_pdg (data%flv)
if (abs(isospin) /= 2 .or. abs(pdg) > 16 .or. pdg == 0 .or. pdg == 9) then
    call msg_fatal ("EWA structure function only accessible for " &
        // "SM quarks and leptons.")
end if
q = - flavor_get_charge (data%flv)
t3 = - flavor_get_isospin (data%flv)
up_type = (t3 > 0)
mask = new_quantum_numbers_mask (.false., .false., &
    mask_h = (/ .false., .false., .true. /))
hel_lock = (/ 2, 1, 0 /)
call interaction_init &
    (int, 1, 0, 2, mask=mask, hel_lock=hel_lock, set_relations=.true.)
select case (data%id)
case (23)
    !!! Z boson, flavor is not changing
    call flavor_init (flv_z, Z_BOSON, data%model)
    call quantum_numbers_init (qn_z, flv_z)
    call polarization_init_generic (pol, data%flv)
    call quantum_numbers_init (qn_fc(1), &
        flv = data%flv, col = color_from_flavor (data%flv))
    call state_iterator_init (it_hel, pol%state)
    do while (state_iterator_is_valid (it_hel))
        qn_hel = state_iterator_get_quantum_numbers (it_hel)
        qn = qn_hel(1) .merge. qn_fc(1)
        call interaction_add_state (int, (/ qn, qn, qn_z /))
        call state_iterator_advance (it_hel)
    end do
    call polarization_final (pol)
case (24)
    if (up_type) then
        !!! W+, flavor changing
        call flavor_init (flv_down, pdg - 1, data%model)
        call flavor_init (flv_wp, W_BOSON, data%model)
        call quantum_numbers_init (qn_wp, flv_wp)
        call polarization_init_generic (pol, data%flv)
        call quantum_numbers_init (qn_fc(1), &
            flv = data%flv, col = color_from_flavor (data%flv))
        call quantum_numbers_init (qn_fc_fin(1), &
            flv = flv_down, col = color_from_flavor (flv_down))
        call state_iterator_init (it_hel, pol%state)
        do while (state_iterator_is_valid (it_hel))
            qn_hel = state_iterator_get_quantum_numbers (it_hel)

```

```

        qn = qn_hel(1) .merge. qn_fc(1)
        qn_down = qn_hel(1) .merge. qn_fc_fin(1)
        call interaction_add_state (int, (/ qn, qn_down, qn_wp /))
        call state_iterator_advance (it_hel)
    end do
    call polarization_final (pol)
else
    !!! W-, flavor changing
    call flavor_init (flv_up, pdg + 1, data%model)
    call flavor_init (flv_wm, - W_BOSON, data%model)
    call quantum_numbers_init (qn_wm, flv_wm)
    call polarization_init_generic (pol, data%flv)
    call quantum_numbers_init (qn_fc(1), &
        flv = data%flv, col = color_from_flavor (data%flv))
    call quantum_numbers_init (qn_fc_fin(1), &
        flv = flv_up, col = color_from_flavor (flv_up))
    call state_iterator_init (it_hel, pol%state)
    do while (state_iterator_is_valid (it_hel))
        qn_hel = state_iterator_get_quantum_numbers (it_hel)
        qn = qn_hel(1) .merge. qn_fc(1)
        qn_up = qn_hel(1) .merge. qn_fc_fin(1)
        call interaction_add_state (int, (/ qn, qn_up, qn_wm /))
        call state_iterator_advance (it_hel)
    end do
    call polarization_final (pol)
end if
case default
    call msg_fatal ("EWA initialization failed: wrong particle type.")
end select
call interaction_freeze (int)
end subroutine interaction_init_ewa

```

10.4.4 EWA structure function

The EWA structure function allows for a straightforward mapping of the unit interval. So, to leading order, the structure function value is unity, but the x value is transformed. Higher orders affect the function value.

The structure function implementation applies the above mapping to the input (random) number r to generate the momentum fraction x and the function value f . For numerical stability reasons, we also output xb , which is $\bar{x} = 1 - x$. The mapping ensures that $f = 1$ at leading order, and the higher-order corrections are well-behaved.

(EWA: procedures)+≡

```

elemental subroutine strfun (f, fp, fm, fL, x, xb, r, E, data, no_map)
    real(default), intent(out) :: f, fm, fp, fL
    real(default) :: fsum
    real(default), intent(out) :: x, xb
    real(default), intent(in) :: r, E
    type(ewa_data_t), intent(in) :: data
    logical, intent(in) :: no_map
    real(default) :: x0, x1
    real(default) :: rb, lx0, lx1, lx, d, den

```

```

real(default) :: c1, c2, pt2
real(default) :: costhw, sinthw
real(default) :: cv, ca, q, t3
if (data%keep_momentum .or. data%keep_energy) then
  select case (data%id)
    case (23)
      x0 = max (data%x_min, data%mz/E)
    case (24)
      x0 = max (data%x_min, data%mw/E)
    end select
else
  x0 = data%x_min
end if
x1 = data%x_max
if (x0 >= x1) then
  f = 0
  fp = 0
  fm = 0
  fL = 0
  return
end if
lx0 = log (x0)
lx1 = log (x1)
lx = lx1 * r + lx0 * (1-r)
x = exp(lx)
xb = 1 - x
f = data%coeff * (lx1 - lx0)
pt2 = min ((data%pt_max)**2, (xb * data%sqrts / 2)**2)
select case (data%id)
case (23)
  !!! Z boson structure function
  c1 = log (1 + pt2 / (xb * (data%mZ)**2))
  c2 = 1 / (1 + (xb * (data%mZ)**2) / pt2)
  if (flavor_is_antiparticle (data%flv)) then
    q = flavor_get_charge (data%flv)
    t3 = flavor_get_isospin (data%flv)
  else
    q = - flavor_get_charge (data%flv)
    t3 = - flavor_get_isospin (data%flv)
  end if
  cv = data%cv * (t3 - 2._default * q * data%sinthw**2) / data%costhw
  ca = data%ca * t3 / data%costhw
  if (flavor_is_antiparticle (data%flv)) ca = - ca
  fm = ((cv + ca)**2 + ((cv - ca) * xb)**2) / 2 * (c1 - c2)
  fp = ((cv - ca)**2 + ((cv + ca) * xb)**2) / 2 * (c1 - c2)
  fL = (cv**2 + ca**2) * 2 * xb * c2
  fsum = fp + fm + fL
  f = f * fsum
  if (fsum /= 0) then
    fp = fp / fsum
    fm = fm / fsum
    fL = fL / fsum
  end if
case (24)

```



```

!!! W boson structure function
c1 = log (1 + pt2 / (xb * (data%mw)**2))
c2 = 1 / (1 + (xb * (data%mw)**2) / pt2)
cv = data%cv / sqrt(2._default)
ca = data%ca / sqrt(2._default)
if (flavor_is_antiparticle (data%flv)) ca = - ca
fm = ((cv + ca)**2 + ((cv - ca) * xb)**2) / 2 * (c1 - c2)
fp = ((cv - ca)**2 + ((cv + ca) * xb)**2) / 2 * (c1 - c2)
fL = (cv**2 + ca**2) * 2 * xb * c2
fsum = fp + fm + fL
f = f * fsum
if (fsum /= 0) then
    fp = fp / fsum
    fm = fm / fsum
    fL = fL / fsum
end if
end select
end subroutine strfun

```

10.4.5 EWA application

For EWA, we can compute kinematics and function value in a single step. This function works on a single beam, assuming that the input momentum has been set. We need four random numbers as input: one for x , one for Q^2 , and two for the polar and azimuthal angles. Alternatively, we can skip p_T generation; in this case, we only need one.

For obtaining splitting kinematics, we rely on the assumption that all in-particles are mass-degenerate (or there is only one), so the generated x values are identical.

```

(EWA: public)+≡
    public :: interaction_apply_ewa

(EWA: procedures)+≡
    subroutine interaction_apply_ewa (int, r, ewa_data, no_map)
        type(interaction_t), intent(inout) :: int
        real(default), dimension(:), intent(in) :: r
        type(ewa_data_t), dimension(:), intent(in) :: ewa_data
        logical, intent(in) :: no_map
        type(vector4_t) :: k
        type(vector4_t), dimension(2) :: k_split
        type(splitting_data_t) :: sd
        real(default), dimension(size(ewa_data)) :: f, fp, fm, fL
        real(default), dimension(size(ewa_data)) :: x, xb
        k = interaction_get_momentum (int, 1)
        select case (ewa_data(1)%id)
        case (23)
            sd = new_splitting_data (k, k**2, ewa_data(1)%mass**2, ewa_data(1)%mz)
        case (24)
            sd = new_splitting_data (k, k**2, ewa_data(1)%mass**2, ewa_data(1)%mw)
        end select
        call strfun (f, fp, fm, fL, x, xb, r(1), energy (k), ewa_data(1), no_map)
        call interaction_set_flavored_values &

```

```

        (int, cmplx (f, kind=default), ewa_data%flv, 2)
call splitting_set_t_bounds (sd, x(1), xb(1))
call splitting_narrow_t_bounds (sd, ewa_data(1)%q_min, ewa_data(1)%pt_max)
select case (size (r))
case (1)
    call splitting_set_collinear (sd)
case (3)
    call splitting_sample_t (sd, r(2))
    call splitting_sample_phi (sd, r(3))
case default
    print *, "n_rand = ", size (r)
    call msg_bug (" EWA: number of random numbers must be 1 or 3")
end select
k_split = split_momentum (k, sd)
if (ewa_data(1)%keep_momentum) then
    call on_shell (k_split(1), 0._default, KEEP_MOMENTUM)
    select case (ewa_data(1)%id)
    case (23)
        call on_shell (k_split(2), ewa_data(1)%mz, KEEP_MOMENTUM)
    case (24)
        call on_shell (k_split(2), ewa_data(1)%mw, KEEP_MOMENTUM)
    end select
else if (ewa_data(1)%keep_energy) then
    call on_shell (k_split(1), 0._default, KEEP_ENERGY)
    select case (ewa_data(1)%id)
    case (23)
        call on_shell (k_split(2), ewa_data(1)%mz, KEEP_ENERGY)
    case (24)
        call on_shell (k_split(2), ewa_data(1)%mw, KEEP_ENERGY)
    end select
end if
call interaction_set_momenta &
    (int, k_split, outgoing=.true.)
end subroutine interaction_apply_ewa

```

10.5 Lepton collider beamstrahlung: CIRCE1

```
<sf_circe1.f90>≡  
  <File header>  
  
  module sf_circe1  
  
    <Use kinds>  
    <Use strings>  
    <Use file utils>  
    use limits, only: CIRCE1_EPSILON !NODEP!  
    use diagnostics !NODEP!  
    use tao_random_numbers !NODEP!  
    use lorentz !NODEP!  
    use models  
    use flavors  
    use colors  
    use quantum_numbers  
    use state_matrices  
    use polarizations  
    use interactions  
    use sf_aux  
    use circe1 !NODEP!  
  
    <Standard module head>  
  
    <CIRCE1: public>  
  
    <CIRCE1: parameters>  
  
    <CIRCE1: types>  
  
    <CIRCE1: variables>  
  
    contains  
  
    <CIRCE1: procedures>  
  
  end module sf_circe1
```

10.5.1 Physics

Beamstrahlung is applied before ISR. The **CIRCE1** implementation has a single structure function for both beams (which makes sense since it has to be switched on or off for both beams simultaneously). Nevertheless it is factorized:

The functional form in the **CIRCE1** parameterization is defined for electrons or photons

$$f(x) = \alpha x^\beta (1-x)^\gamma \quad (10.57)$$

for $x < 1 - \epsilon$ (resp. $x > \epsilon$ in the photon case). In the remaining interval, the standard form is zero, with a delta singularity at $x = 1$ (resp. $x = 0$). Equivalently, the delta part may be distributed uniformly among this interval.

This latter form is implemented in the `kirke` version of the `CIRCE1` subroutines, and is used here.

The parameter ϵ is hardcoded in `CIRCE1` (set equal to 10^{-6}). Therefore, it cannot be changed in the namelist.

```
<CIRCE1: public parameters>≡
  real(kind=default), parameter, public :: KIREPS = 1E-6_default
```

The other parameters are the parameterization version and revision number, the accelerator type, and the \sqrt{s} value used by `CIRCE1`. The chattiness can also be set (?).

Since the energy is distributed in a narrow region around unity (for electrons) or zero (for photons), it is advantageous to map the interval first. The mapping is controlled by the powers `beta` and `gamma` which are taken from the `CIRCE1` internal data structure.

The \sqrt{s} value, if not explicitly set, is taken from the process data. Note that interpolating \sqrt{s} is not recommended; one should rather choose one of the distinct values known to `CIRCE1`.

10.5.2 The CIRCE1 data block

The `CIRCE1` parameters are: The incoming flavors, the flags whether the photon or the lepton is the parton in the hard interaction, the flags for the generation mode (generator/mapping/no mapping), the mapping parameters β and γ , \sqrt{s} and several steering parameters: `ver`, `rev`, `acc`, `chat`.

In generator mode, the x values are actually discarded and a random number generator is used instead.

```
<CIRCE1: public>≡
  public :: circe1_data_t

<CIRCE1: types>≡
  type :: circe1_data_t
    private
    type(model_t), pointer :: model => null ()
    type(flavor_t), dimension(2) :: flv_in
    integer, dimension(2) :: pdg_in
    real(default), dimension(2) :: m_in = 0
    logical, dimension(2) :: photon = .false.
    logical :: generate = .true.
    type(tao_random_state), pointer :: rng => null ()
    logical :: map = .true.
    real(default), dimension(2) :: beta = 0
    real(default), dimension(2) :: gamma = 0
    real(default) :: sqrts = 0
    integer :: ver = 0
    integer :: rev = 0
    integer :: acc = 0
    integer :: chat = 0
    integer :: error = NONE
  end type circe1_data_t
```

Error codes

```
<CIRCE1: parameters>≡
```

```

integer, parameter :: NONE = 0
integer, parameter :: FLV_INAPPLICABLE = 1
<CIRCE1: public>+≡
public :: circe1_data_init
<CIRCE1: procedures>≡
subroutine circe1_data_init &
    (data, model, flv, sqrts, out_photon, generate, rng, map, &
    ver, rev, acc, chat)
    type(circe1_data_t), intent(out) :: data
    type(model_t), intent(in), target :: model
    type(flavor_t), dimension(2), intent(in) :: flv
    real(default), intent(in) :: sqrts
    logical, dimension(2), intent(in) :: out_photon
    logical, intent(in) :: generate, map
    type(tao_random_state), intent(in), target :: rng
    integer, intent(in) :: ver, rev, acc, chat
    data%model => model
    data%flv_in = flv
    data%pdg_in = flavor_get_pdg (data%flv_in)
    if (any (abs (data%pdg_in) /= ELECTRON)) data%error = FLV_INAPPLICABLE
    if (data%pdg_in(1) /= - data%pdg_in(2)) data%error = FLV_INAPPLICABLE
    data%m_in = flavor_get_mass (data%flv_in)
    data%sqrts = sqrts
    data%photon = out_photon
    data%generate = generate
    data%rng => rng
    data%map = map
    data%ver = ver
    data%rev = rev
    data%acc = acc
    data%chat = chat
    select case (char (model_get_name (data%model)))
    case ("QCD", "Test")
        call msg_fatal ("CIRCE1 structure function not available for model " &
            // char (model_get_name (data%model)) // ".")
    end select
    call circes (0.d0, 0.d0, dble (data%sqrts), &
        data%acc, data%ver, data%rev, data%chat)
    call circe1_get_parameters (data%photon, data%beta, data%gamma)
end subroutine circe1_data_init

```

These procedures access the CIRCE internal state directly (!).

```

<CIRCE1: procedures>+≡
elemental subroutine circe1_get_parameters (photon, beta, gamma)
    logical, intent(in) :: photon
    real(default), intent(out) :: beta, gamma
    if (photon) then
        beta = circe1_params%a1(6)
        gamma = circe1_params%a1(5)
    else
        beta = circe1_params%a1(2)
        gamma = circe1_params%a1(3)
    end if

```

```
end subroutine circe1_get_parameters
```

Handle error conditions.

```
<CIRCE1: public>+≡
public :: circe1_data_check

<CIRCE1: procedures>+≡
subroutine circe1_data_check (data)
  type(circe1_data_t), intent(in) :: data
  select case (data%error)
  case (FLV_INAPPLICABLE)
    call msg_fatal ("CIRCE1: applicable only for incoming " &
      // "electron or positron")
  end select
end subroutine circe1_data_check
```

Output

```
<CIRCE1: public>+≡
public :: circe1_data_write

<CIRCE1: procedures>+≡
subroutine circe1_data_write (data, unit, md5)
  type(circe1_data_t), intent(in) :: data
  integer, intent(in), optional :: unit
  integer :: u
  logical, intent(in), optional :: md5
  u = output_unit (unit); if (u < 0) return
  write (u, *) "CIRCE1 data:"
  write (u, *) " prt_in = ", char (flavor_get_name (data%flv_in(1))), &
    ", ", char (flavor_get_name (data%flv_in(2)))
  write (u, *) " photon = ", data%photon
  write (u, *) " generate = ", data%generate
  write (u, *) " map      = ", data%map
  write (u, *) " beta   = ", data%beta
  write (u, *) " gamma  = ", data%gamma
  write (u, *) " m_in   = ", data%m_in
  write (u, *) " sqrts  = ", data%sqrts
  write (u, *) " ver    = ", data%ver
  write (u, *) " rev    = ", data%rev
  write (u, *) " acc    = ", data%acc
  write (u, *) " chat   = ", data%chat
end subroutine circe1_data_write
```

10.5.3 The CIRCE1 object

This is a $2 \rightarrow 4$ interaction, where, depending on the parameters, any two of the four outgoing particles are connected to the hard interactions, the others are radiated. Knowing that all particles are colorless, we do not have to deal with color.

The flavors are sorted such that the first two particles are the incoming leptons, the next two are the radiated particles, and the last two are the partons initiating the hard interaction.

CIRCE1 does not support polarized beams explicitly. For simplicity, we nevertheless carry beam polarization through to the outgoing electrons and make the photons unpolarized.

```

<CIRCE1: public>+≡
    public :: interaction_init_circe1

<CIRCE1: procedures>+≡
    subroutine interaction_init_circe1 (int, circe1_data)
        type(interaction_t), intent(out) :: int
        type(circe1_data_t), intent(in) :: circe1_data
        logical, dimension(6) :: mask_h
        type(quantum_numbers_mask_t), dimension(6) :: mask
        integer, dimension(6) :: hel_lock
        type(polarization_t) :: pol1, pol2
        type(quantum_numbers_t), dimension(1) :: qn_fc1, qn_hel1, qn_fc2, qn_hel2
        type(flavor_t) :: flv_photon
        type(quantum_numbers_t) :: qn_photon, qn1, qn2
        type(quantum_numbers_t), dimension(6) :: qn
        type(state_iterator_t) :: it_hel1, it_hel2
        hel_lock = 0
        mask_h = .false.
        if (circe1_data%photon(1)) then
            hel_lock(1) = 3; hel_lock(3) = 1; mask_h(5) = .true.
        else
            hel_lock(1) = 5; hel_lock(5) = 1; mask_h(3) = .true.
        end if
        if (circe1_data%photon(2)) then
            hel_lock(2) = 4; hel_lock(4) = 2; mask_h(6) = .true.
        else
            hel_lock(2) = 6; hel_lock(6) = 2; mask_h(4) = .true.
        end if
        mask = new_quantum_numbers_mask (.false., .false., mask_h)
        call interaction_init &
            (int, 2, 0, 4, mask=mask, hel_lock=hel_lock, set_relations=.true.)
        call flavor_init (flv_photon, PHOTON, circe1_data%model)
        call quantum_numbers_init (qn_photon, flv_photon)
        call polarization_init_generic (pol1, circe1_data%flv_in(1))
        call quantum_numbers_init (qn_fc1(1), flv = circe1_data%flv_in(1))
        call polarization_init_generic (pol2, circe1_data%flv_in(2))
        call quantum_numbers_init (qn_fc2(1), flv = circe1_data%flv_in(2))
        call state_iterator_init (it_hel1, pol1%state)
        do while (state_iterator_is_valid (it_hel1))
            qn_hel1 = state_iterator_get_quantum_numbers (it_hel1)
            qn1 = qn_hel1(1) .merge. qn_fc1(1)
            qn(1) = qn1
            if (circe1_data%photon(1)) then
                qn(3) = qn1; qn(5) = qn_photon
            else
                qn(3) = qn_photon; qn(5) = qn1
            end if
            call state_iterator_init (it_hel2, pol2%state)
        end do
    end subroutine

```

```

do while (state_iterator_is_valid (it_hel2))
  qn_hel2 = state_iterator_get_quantum_numbers (it_hel2)
  qn2 = qn_hel2(1) .merge. qn_fc2(1)
  qn(2) = qn2
  if (circe1_data%photon(2)) then
    qn(4) = qn2; qn(6) = qn_photon
  else
    qn(4) = qn_photon; qn(6) = qn2
  end if
  call interaction_add_state (int, qn)
  call state_iterator_advance (it_hel2)
end do
call state_iterator_advance (it_hel1)
end do
call polarization_final (pol1)
call polarization_final (pol2)
call interaction_freeze (int)
end subroutine interaction_init_circe1

```

10.5.4 CIRCE1 structure function

Compute the CIRCE1 structure function: either using the generator or the structure function value. In the latter case, we may employ a mapping that depends on the β, γ parameters.

The generator mode is the default and by far more useful, since there is virtually no loss in accuracy or reweighting efficiency for a process with CIRCE1 and without. The formal problem with this approach is the indeterministic integration, which is presumably harmless since the corresponding integration dimensions factorize in the VEGAS approach.

If `no_map` is set, we switch off generator and mapping.

(Limits: public parameters)+≡

```
double precision, parameter, public :: CIRCE1_EPSILON = 1d-6
```

(CIRCE1: procedures)+≡

```

subroutine strfun (f, x, xb, r, circe1_data, no_map)
  real(default), intent(out) :: f
  real(default), dimension(2), intent(out) :: x, xb
  real(default), dimension(2), intent(in) :: r
  type(circe1_data_t), intent(in) :: circe1_data
  logical, intent(in) :: no_map
  real(kind=default), parameter :: eps = CIRCE1_EPSILON
  real(default), dimension(2) :: fi
  if (circe1_data%generate .and. .not. no_map) then
    call circe_generate &
      (x, circe1_data%rng, circe1_data%pdg_in < 0, circe1_data%photon)
    xb = 1 - x
    f = 1
  else if (circe1_data%map .and. .not. no_map) then
    call circe_map_p (fi, x, xb, r, eps, &
      circe1_data%beta, circe1_data%gamma, circe1_data%photon)
    f = product (fi) * strfun_circe1 (x, circe1_data%pdg_in)
  end if
end subroutine strfun

```



```

else
  x = r
  xb = 1 - r
  f = strfun_circe1 (x, circe1_data%pdg_in)
end if
end subroutine strfun

```

Call the CIRCE1 generator. The integration variables are not used in this case. Instead, we call a random-number generator.

The CIRCE1 generator calls need the generator as argument, but not the generator state. Thus, we temporarily assign a pointer to the state to a module variable which is accessed by the generator.

```

<CIRCE1: variables>≡
  type(tao_random_state), pointer :: rng_tmp => null ()

<CIRCE1: procedures>+≡
  subroutine rn_sub (r)
    double precision, intent(out) :: r
    real(default) :: x
    call tao_random_number (rng_tmp, x)
    r = x
  end subroutine rn_sub

<CIRCE1: procedures>+≡
  subroutine circe_generate (x, rng, anti, photon)
    logical, dimension(2), intent(in) :: anti
    logical, dimension(2), intent(in) :: photon
    real(default), dimension(2), intent(out) :: x
    real(double), dimension(2) :: xdum
    type(tao_random_state), intent(in), target :: rng
    rng_tmp => rng
    if (all (photon)) then
      call girceg (xdum(1), xdum(2), rn_sub)
    else if (photon(2)) then
      call girceg (xdum(1), xdum(2), rn_sub)
    else if (photon(1)) then
      call girceg (xdum(2), xdum(1), rn_sub)
    else if (.not. anti(1) .and. anti(2)) then
      call gircee (xdum(1), xdum(2), rn_sub)
    else if (anti(1) .and. .not. anti(2)) then
      call gircee (xdum(2), xdum(1), rn_sub)
    else
      call msg_bug ("CIRCE1: impossible flavor assignment")
    end if
    x = xdum
    rng_tmp => null ()
  end subroutine circe_generate

```

Apply the appropriate mapping, exchanging x vs. $1 - x$ depending on the particle. This can be done for both beams simultaneously, since the parameterization factorizes.

The CIRCE1 structure function has the form of a β distribution

$$f(x) = \begin{cases} \alpha x^\beta (1-x)^\gamma & \text{for } 0 < x < x_0 \\ \alpha x_0^\beta (1-x_0)^\gamma & \text{for } x_0 < x < 1 \end{cases} \quad (10.58)$$

in the electron/positron case. In the photon case, this form holds for $1-x$. Instead of mapping this function in one step, we consider the two factors separately, such that the mapping $y(x)$ satisfies either

$$\frac{dy}{dx} = \begin{cases} ax^\beta & \text{for } 0 < x < x_0 \\ ax_0^\beta & \text{for } x_0 < x < 1 \end{cases} \quad (10.59)$$

or

$$\frac{dy}{dx} = \begin{cases} a(1-x)^\gamma & \text{for } 0 < x < x_0 \\ a(1-x_0)^\gamma & \text{for } x_0 < x < 1 \end{cases} \quad (10.60)$$

where, typically, $\beta > 0$ and $\gamma < 0$.

Integrating this leads to

$$y = \begin{cases} a \frac{x^{1+\beta}}{1+\beta}, & x < x_0 \\ y_0 + a(x-x_0)x_0^\beta, & x > x_0 \end{cases} \quad (10.61)$$

resp.

$$y = \begin{cases} a \frac{1-(1-x)^{1+\gamma}}{1+\gamma}, & x < x_0 \\ y_0 + ax_0^\gamma(x-x_0) & x > x_0 \end{cases} \quad (10.62)$$

We need the inverse mapping: The y value is taken from the random number set and has to be transformed into a x value which is fed into CIRCE1.

$$x = \begin{cases} \left((1+\beta) \frac{y}{a} \right)^{\frac{1}{1+\beta}} & y < y_0 \\ x_0 + \frac{y-y_0}{ax_0^\beta} & y > y_0 \end{cases} \quad (10.63)$$

or

$$x = \begin{cases} 1 - \left(1 - (1+\gamma) \frac{y}{a} \right)^{\frac{1}{1+\gamma}} & y < y_0 \\ x_0 + \frac{y-y_0}{a(1-x_0)^\gamma} & y > y_0 \end{cases} \quad (10.64)$$

The boundary in y is given by

$$y_0 = a \frac{x_0^{1+\beta}}{1+\beta} \quad \text{resp.} \quad y_0 = a \frac{1-(1-x_0)^{1+\gamma}}{1+\gamma} \quad (10.65)$$

and the normalization is chosen such that $y(1) = 1$

$$a = \left(\frac{x_0^{1+\beta}}{1+\beta} + (1-x_0)x_0^\beta \right)^{-1} \quad (10.66)$$

or

$$a = \left(\frac{1-(1-x_0)^{1+\gamma}}{1+\gamma} + (1-x_0)^{1+\gamma} \right)^{-1} \quad (10.67)$$

```

<CIRCE1: procedures>+≡
  elemental subroutine circe_map_p (f, x, xb, r, eps, beta, gamma, photon)
    real(default), intent(out) :: f, x, xb
    real(default), intent(in) :: r
    real(default), intent(in) :: eps, beta, gamma
    logical, intent(in) :: photon
    real(default) :: rb
    if (photon) then
      rb = 1 - r
      call circe_map_s (f, xb, rb, 1-eps, beta, gamma)
      x = 1 - xb
    else
      call circe_map_s (f, x, r, 1-eps, beta, gamma)
      xb = 1 - x
    end if
  end subroutine circe_map_p

```

Apply the mapping. We map both powers by concatenating the mappings.

```

<CIRCE1: procedures>+≡
  pure subroutine circe_map_s (f, x, z, x0, beta, gamma)
    real(default), intent(out) :: f, x
    real(default), intent(in) :: z, x0, beta, gamma
    real(default) :: y, ay, az, y0, z0
    call circe_set_const (ay, y0, x0, gamma, invert=.true.)
    call circe_set_const (az, z0, y0, beta, invert=.false.)
    y = circe_map_x (z, z0, y0, az, beta, invert=.false.)
    x = circe_map_x (y, y0, x0, ay, gamma, invert=.true.)
    f = 1 / circe_jacobian (x, x0, ay, gamma, invert=.true.) &
        / circe_jacobian (y, y0, az, beta, invert=.false.)
  end subroutine circe_map_s

```

```

<CIRCE1: procedures>+≡
  pure function circe_map_x (y, y0, x0, a, power, invert) result (x)
    real(kind=default), intent(in) :: y, y0, x0, a, power
    logical, intent(in) :: invert
    real(kind=default) :: x
    if (y<=0) then
      x = 0
    else if (y>1) then
      x = 1
    else if (invert) then
      if (y<y0) then
        x = 1 - (1 - (1+power)*y/a)**(1/(1+power))
      else
        x = x0 + (y-y0)/(a*(1-x0)**power)
      end if
    else
      if (y<y0) then
        x = ((1+power)*y/a)**(1/(1+power))
      else
        x = x0 + (y-y0)/(a*x0**power)
      end if
    end if
  end function

```

```
end function circe_map_x
```

Set constants for power mappings.

<CIRCE1: procedures>+≡

```
pure subroutine circe_set_const (a, y0, x0, power, invert)
  real(default), intent(out) :: a, y0
  real(default), intent(in)  :: x0, power
  logical, intent(in)       :: invert
  real(default) :: tmp
  if (invert) then
    tmp = (1 - (1-x0)**(1+power)) / (1+power)
    a = 1 / (tmp + (1-x0)**(1+power))
  else
    tmp = x0**(1+power) / (1+power)
    a = 1 / (tmp + (1-x0) * x0**power)
  end if
  y0 = a * tmp
end subroutine circe_set_const
```

The Jacobian factor for the power mapping:

<CIRCE1: procedures>+≡

```
pure function circe_jacobian (x, x0, a, power, invert) result (dy_dx)
  real(kind=default), intent(in) :: x, x0, a, power
  logical, intent(in) :: invert
  real(kind=default) :: dy_dx
  if (x<=0) then
    dy_dx = a
  else if (invert) then
    if (x<x0) then
      dy_dx = a * (1-x)**power
    else
      dy_dx = a * (1-x0)**power
    end if
  else
    if (x<x0) then
      dy_dx = a * x**power
    else
      dy_dx = a * x0**power
    end if
  end if
end function circe_jacobian
```

The actual CIRCE call. The parameters are already mapped, so we can directly call the structure function.

<CIRCE1: procedures>+≡

```
function strfun_circe1 (x, pdg) result (f)
  real(default) :: f
  real(default), dimension(2), intent(in) :: x
  integer, dimension(2), intent(in) :: pdg
  if (all (x /= 0)) then
    f = kirke (dble (x(1)), dble (x(2)), pdg(1), pdg(2))
  else

```

```

        f = 0
    end if
end function strfun_circe1

```

10.5.5 CIRCE1 application

CIRCE is applied for the two beams at once. We can safely assume that no structure functions are applied before this, so the incoming particles are on-shell electrons/positrons.

```

<CIRCE1: public>+≡
    public :: interaction_apply_circe1

<CIRCE1: procedures>+≡
    subroutine interaction_apply_circe1 (int, r, circe1_data, no_map)
        type(interaction_t), intent(inout) :: int
        real(default), dimension(2), intent(in) :: r
        type(circe1_data_t), intent(in) :: circe1_data
        logical, intent(in) :: no_map
        type(vector4_t), dimension(2) :: k
        type(splitting_data_t), dimension(2) :: sd
        real(default), dimension(2) :: m_in, x, xb
        real(default) :: f
        type(vector4_t), dimension(4) :: q
        k(1) = interaction_get_momentum (int, 1)
        k(2) = interaction_get_momentum (int, 2)
        m_in = circe1_data%m_in
        sd = new_splitting_data (k, m_in**2, m_in**2, m_in)
        call strfun (f, x, xb, r, circe1_data, no_map)
        call interaction_set_matrix_element (int, cmplx (f, kind=default))
        call splitting_set_t_bounds (sd, x, xb)
        call splitting_set_collinear (sd)
        q((/1, 3/)) = split_momentum (k(1), sd(1))
        q((/2, 4/)) = split_momentum (k(2), sd(2))
        call interaction_set_momenta (int, q, outgoing=.true.)
    end subroutine interaction_apply_circe1

```

10.6 Photon collider: CIRCE2

```
<sf_circe2.f90>≡  
  <File header>  
  
  module sf_circe2  
  
    <Use kinds>  
    <Use strings>  
    <Use file utils>  
    use diagnostics !NODEP!  
    use tao_random_numbers !NODEP!  
    use lorentz !NODEP!  
    use models  
    use flavors  
    use helicities  
    use quantum_numbers  
    use state_matrices  
    use polarizations  
    use interactions  
    use sf_aux  
    use circe2 !NODEP!  
  
    <Standard module head>  
  
    <CIRCE2: public>  
  
    <CIRCE2: types>  
  
    <CIRCE2: variables>  
  
    contains  
  
    <CIRCE2: procedures>  
  
  end module sf_circe2
```

10.6.1 Physics

CIRCE2 describes photon spectra Beamstrahlung is applied before ISR. The CIRCE2 implementation has a single structure function for both beams (which makes sense since it has to be switched on or off for both beams simultaneously).

10.6.2 The CIRCE2 data block

The CIRCE2 parameters are: file and collider specification, incoming (= outgoing) particles. The luminosity is returned by `cir2lm`.

```
<CIRCE2: public>≡  
  public :: circe2_data_t  
  
<CIRCE2: types>≡  
  type :: circe2_data_t  
    private
```

```

type(flavor_t), dimension(2) :: flv_in
integer, dimension(2) :: pdg = 0
real(default), dimension(2) :: mass = 0
logical :: generate = .true.
type(tao_random_state), pointer :: rng => null ()
logical :: map = .true.
integer, dimension(2) :: map_mode = -1
real(default), dimension(2) :: map_power = 0
type(string_t) :: file
type(string_t) :: design
real(default) :: sqrts = 0
logical :: polarized = .false.
real(default) :: lumi = 0
real(default), dimension(-1:1,-1:1) :: lumi_hel_frac = 0
real(default), dimension(0:4) :: lumi_hel_sum = 0
end type circe2_data_t

```

<CIRCE2: public>+≡

```
public :: circe2_data_init
```

<CIRCE2: procedures>≡

```

subroutine circe2_data_init &
    (data, flv_in, generate, rng, map, file, design, sqrts, polarized)
type(circe2_data_t), intent(out) :: data
type(flavor_t), dimension(2), intent(in) :: flv_in
logical, intent(in) :: generate
type(tao_random_state), intent(in), target :: rng
logical, intent(in) :: map
type(string_t), intent(in) :: file, design
real(default), intent(in) :: sqrts
logical, intent(in) :: polarized
integer :: error, i, h1, h2, h
data%flv_in = flv_in
data%pdg = flavor_get_pdg (data%flv_in)
data%mass = flavor_get_mass (data%flv_in)
data%generate = generate
data%rng => rng
data%map = map
if (data%map) then
    do i = 1, 2
        select case (abs (data%pdg(i)))
            case (PHOTON);    data%map_mode(i) = 0; data%map_power(i) = 3
            case (ELECTRON); data%map_mode(i) = 1; data%map_power(i) = 12
            case default; call msg_fatal &
                ("CIRCE2: defined only for photon and electron beams")
        end select
    end do
else
    data%map_mode = -1
end if
data%file = file
data%design = design
data%sqrts = sqrts
data%polarized = polarized

```

```

error = 1
call cir2ld (trim (char(data%file)), trim (char(data%design)), &
            dble (data%sqrts), error)
select case (error)
case (-1)
    call msg_fatal ("CIRCE2: data file not found.")
case (-2)
    call msg_fatal ("CIRCE2: beam parameters do not match data file.")
case (-3)
    call msg_fatal ("CIRCE2: invalid format of data file.")
case (-4)
    call msg_fatal ("CIRCE2: data file too large.")
end select
data%lumi = cir2lm (data%pdg(1), 0, data%pdg(2), 0)
if (data%lumi == 0) then
    call circe2_data_write (data)
    call msg_fatal ("CIRCE2: luminosity vanishes for specified beams.")
end if
if (data%polarized) then
    h = 0
    do h1 = -1, 1, 2
        do h2 = -1, 1, 2
            data%lumi_hel_frac(h1,h2) = &
                cir2lm (data%pdg(1), h1, data%pdg(2), h2) / data%lumi
            h = h + 1
            data%lumi_hel_sum(h) = &
                data%lumi_hel_sum(h-1) + data%lumi_hel_frac(h1,h2)
        end do
    end do
    data%lumi_hel_sum(4) = 1
end if
end subroutine circe2_data_init

```

Output

<CIRCE2: public>+≡

```
public :: circe2_data_write
```

<CIRCE2: procedures>+≡

```

subroutine circe2_data_write (data, unit, md5)
    type(circe2_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    integer :: h1, h2
    integer :: u
    logical, intent(in), optional :: md5
    u = output_unit (unit); if (u < 0) return
    write (u, *) "CIRCE2 data:"
    write (u, *) "  file = ", char(data%file)
    write (u, *) "  design = ", char(data%design)
    write (u, *) "  sqrts = ", data%sqrts
    write (u, *) "  prt_in = ", char (flavor_get_name (data%flv_in(1))), &
        ", ", char (flavor_get_name (data%flv_in(2)))
    write (u, *) "  mass = ", data%mass
    write (u, *) "  polarized = ", data%polarized
    write (u, *) "  luminosity = ", data%lumi

```



```

if (data%polarized) then
  do h1 = -1, 1, 2
    do h2 = -1, 1, 2
      write (u, "(6x,'( ',I2,1x,I2,')',1x,'=',1x)", advance="no") h1, h2
      write (u, *) data%lumi_hel_frac(h1,h2)
    end do
  end do
end if
write (u, *) " generate = ", data%generate
write (u, *) " map = ", data%map
if (data%map) then
  write (u, *) " mode = ", data%map_mode
  write (u, *) " power = ", data%map_power
end if
end subroutine circe2_data_write

```

10.6.3 The CIRCE2 object

For CIRCE2 spectra it does not make sense to describe the state matrix as a radiation interaction, even if photons originate from laser backscattering. Instead, it is a $2 \rightarrow 2$ interaction where the incoming particles are identical to the outgoing ones.

The current implementation of CIRCE2 does support polarization and classical correlations, but no entanglement, so the density matrix of the outgoing particles is diagonal. The incoming particles are unpolarized (user-defined polarization for beams is meaningless, since polarization is described by the data file). The outgoing particles are polarized or polarization-averaged, depending on user request.

When assigning matrix elements, we scan the previously initialized state matrix. For each entry, we extract helicity and call the structure function. In the unpolarized case, the helicity is undefined and replaced by value zero. In the polarized case, there are four entries. If the generator is used, only one entry is nonzero in each call. Which one, is determined by comparing with a previously (randomly, distributed by relative luminosity) selected pair of helicities.

```

<CIRCE2: public>+≡
  public :: interaction_init_circe2

<CIRCE2: procedures>+≡
  subroutine interaction_init_circe2 (int, circe2_data)
    type(interaction_t), intent(out) :: int
    type(circe2_data_t), intent(in) :: circe2_data
    type(polarization_t) :: pol3, pol4
    real(default), dimension(2), parameter :: pol_init = 0.5_default
    logical, dimension(4) :: mask_h
    type(quantum_numbers_mask_t), dimension(4) :: mask
    type(quantum_numbers_t), dimension(4) :: qn_fc, qn_hel, qn
    type(state_iterator_t) :: it_hel3, it_hel4
    mask_h(1:2) = .true.
    mask_h(3:4) = .not. circe2_data%polarized
    mask = new_quantum_numbers_mask (.false., .false., mask_h)
    call quantum_numbers_init (qn_fc(1), flv = circe2_data%flv_in(1))

```

```

call quantum_numbers_init (qn_fc(2), flv = circe2_data%flv_in(2))
call quantum_numbers_init (qn_fc(3), flv = circe2_data%flv_in(1))
call quantum_numbers_init (qn_fc(4), flv = circe2_data%flv_in(2))
if (circe2_data%polarized) then
  call polarization_init_diagonal (pol3, circe2_data%flv_in(1), pol_init)
  call polarization_init_diagonal (pol4, circe2_data%flv_in(1), pol_init)
else
  call polarization_init_unpolarized (pol3, circe2_data%flv_in(1))
  call polarization_init_unpolarized (pol4, circe2_data%flv_in(1))
end if
call interaction_init &
  (int, 2, 0, 2, mask=mask, set_relations=.true.)
call state_iterator_init (it_hel3, pol3%state)
qn(1) = qn_fc(1)
qn(2) = qn_fc(2)
do while (state_iterator_is_valid (it_hel3))
  qn_hel(3:3) = state_iterator_get_quantum_numbers (it_hel3)
  qn(3) = qn_hel(3) .merge. qn_fc(3)
  call state_iterator_init (it_hel4, pol4%state)
  do while (state_iterator_is_valid (it_hel4))
    qn_hel(4:4) = state_iterator_get_quantum_numbers (it_hel4)
    qn(4) = qn_hel(4) .merge. qn_fc(4)
    call interaction_add_state (int, qn)
    call state_iterator_advance (it_hel4)
  end do
  call state_iterator_advance (it_hel3)
end do
call polarization_final (pol3)
call polarization_final (pol4)
call interaction_freeze (int)
end subroutine interaction_init_circe2

```

10.6.4 CIRCE2 structure function

Compute the CIRCE2 structure function: either using the generator or the structure function value. In the latter case, we may employ a power mapping for the singular endpoint that uses some heuristics for the mapping parameters.

The generator mode is the default and by far more useful, since there is virtually no loss in accuracy or reweighting efficiency for a process with CIRCE2 and without. The formal problem with this approach is the indeterministic integration, which is presumably harmless since the corresponding integration dimensions factorize in the VEGAS approach.

In generator mode with polarized beams, for each event only one helicity is selected. (See `interaction_apply_circe2` below.) The selection is based on the relative luminosities. Hence, the function value (unity) is multiplied by the number of helicity states (four).

Similarly, in non-generator mode, the luminosity densities for the helicity states are individually normalized and must be multiplied by their luminosity fraction and multiplied by four.

If `no_map` is set, switch off generator and mapping modes.

(CIRCE2: procedures)+≡

```

subroutine strfun (f, x, r, hel, data, no_map)
  real(default), intent(out) :: f
  real(default), dimension(2), intent(out) :: x
  real(default), dimension(2), intent(in) :: r
  real(default), dimension(2) :: fi
  integer, dimension(2), intent(in) :: hel
  double precision, dimension(2) :: xx
  type(circe2_data_t), intent(in) :: data
  logical, intent(in) :: no_map
  if (data%generate .and. .not. no_map) then
    rng_tmp => data%rng
    call cir2gn &
      (data%pdg(1), hel(1), data%pdg(2), hel(2), xx(1), xx(2), rn_sub)
    x = xx
    if (data%polarized) then
      f = 4
    else
      f = 1
    end if
  else
    if (no_map) then
      x = r
      fi = 1
    else
      call circe2_map (fi, x, r, data%map_mode, data%map_power)
    end if
    f = product (fi) &
      * cir2dn (data%pdg(1), hel(1), data%pdg(2), hel(2), &
        dble (x(1)), dble (x(2)))
    if (data%polarized) then
      f = 4 * f * data%lumi_hel_frac (hel(1), hel(2))
    end if
  end if
end subroutine strfun

```

The CIRCE2 calls need the generator as argument, but not the generator state. Thus, we temporarily assign a pointer to the state to a module variable which is accessed by the generator.

(CIRCE2: variables)≡

```

type(tao_random_state), pointer :: rng_tmp => null ()

```

Here is the generator call in the form that CIRCE2 expects:

(CIRCE2: procedures)+≡

```

subroutine rn_sub (r)
  double precision, intent(out) :: r
  real(default) :: x
  call tao_random_number (rng_tmp, x)
  r = x
end subroutine rn_sub

```

Map the random numbers to x values, using specified power mappings for both beams. This function applies to a single beam but is elemental, so it is applied to the beam pair simultaneously.

We define power mappings (modes) for $x = 0$ or, alternatively, for $x = 1$. Mode $x = -1$ means no mapping.

Near zero (photon case) a power 2...3 should be sufficient to cancel the singularity, while near one (electron) the very narrow smeared delta function requires a high power ~ 10 to be identified. Quite generically, if a low x value x_0 needs to be resolved by the mapping, a power of the order $-\frac{1}{2} \log x_0$ is appropriate.

```

<CIRCE2: procedures>+≡
  elemental subroutine circe2_map (f, x, r, mode, power)
    real(default), intent(out) :: f, x
    real(default), intent(in)  :: r
    integer, intent(in)       :: mode
    real(default), intent(in)  :: power
    real(default) :: xbar, rbar
    select case (mode)
    case (0)
      if (r <= tiny(1._default)) then
        x = 0
        f = 0
      else
        x = r ** power
        f = power * x / r
      end if
    case (1)
      rbar = 1 - r
      if (rbar <= tiny(1._default)) then
        xbar = 0
        f = 0
      else
        xbar = rbar ** power
        f = power * xbar / rbar
      end if
      x = 1 - xbar
    case default
      x = r
      f = 1
    end select
  end subroutine circe2_map

```

10.6.5 CIRCE2 application

This function works on both beams, assuming that the input momentum has been set. We apply the usual splitting formalism, specializing to collinear splitting, but throw away the radiated momenta.

```

<CIRCE2: public>+≡
  public :: interaction_apply_circe2

<CIRCE2: procedures>+≡
  subroutine interaction_apply_circe2 (int, r, circe2_data, no_map)
    type(interaction_t), intent(inout), target :: int
    real(default), dimension(2), intent(in) :: r
    type(circe2_data_t), intent(in) :: circe2_data
  end subroutine

```

```

logical, intent(in) :: no_map
complex(default), parameter :: CZERO = 0
type(vector4_t), dimension(2) :: k
integer, dimension(2) :: h, h_gen, h_tmp
type(state_iterator_t) :: it
real(default) :: f
real(default), dimension(2) :: x
type(splitting_data_t), dimension(2) :: sd
type(vector4_t), dimension(4) :: q
k(1) = interaction_get_momentum (int, 1)
k(2) = interaction_get_momentum (int, 2)
if (circe2_data%generate) then
    call interaction_set_matrix_element (int, CZERO)
    if (circe2_data%polarized) then
        call circe2_select_hel &
            (h_gen, circe2_data%rng, circe2_data%lumi_hel_sum)
    else
        h_gen = 0
    end if
end if
call state_iterator_init (it, interaction_get_state_matrix_ptr (int))
LOOP_HEL: do while (state_iterator_is_valid (it))
    if (circe2_data%polarized) then
        h_tmp = helicity_get (state_iterator_get_helicity (it, 3))
        h(1) = h_tmp(1)
        h_tmp = helicity_get (state_iterator_get_helicity (it, 4))
        h(2) = h_tmp(1)
    else
        h = 0
    end if
    if (.not. circe2_data%generate .or. all (h == h_gen)) then
        call strfun (f, x, r, h, circe2_data, no_map)
        call state_iterator_set_matrix_element (it, cmplx (f, kind=default))
    end if
    call state_iterator_advance (it)
end do LOOP_HEL
sd = new_splitting_data &
    (k, circe2_data%mass**2, 0._default, circe2_data%mass)
call splitting_set_t_bounds (sd, x, 1-x)
call splitting_set_collinear (sd)
q((/1, 3/)) = split_momentum (k(1), sd(1))
q((/2, 4/)) = split_momentum (k(2), sd(2))
call interaction_set_momenta (int, q(3:4), outgoing=.true.)
end subroutine interaction_apply_circe2

```

Select a channel for the generator mode. We could use `cir2ch`, but this selects flavor and helicity; we just want to select helicity.

(CIRCE2: procedures)+≡

```

subroutine circe2_select_hel (hel, rng, threshold)
    integer, dimension(2), intent(out) :: hel
    type(tao_random_state), pointer :: rng
    real(default), dimension(0:4) :: threshold
    real(default) :: x

```

```

integer :: h1, h2
integer :: h
call tao_random_number (rng, x)
h = 0
do h1 = -1, 1, 2
  do h2 = -1, 1, 2
    h = h + 1
    if (x <= threshold(h)) then
      hel(1) = h1; hel(2) = h2; return
    end if
  end do
end do
call msg_bug ("CIRCE2: helicity selection failed")
end subroutine circe2_select_hel

```

10.7 Energy-scan spectrum

This spectrum is actually a trick that allows us to plot the c.m. energy dependence of a cross section without scanning the input energy. We start with the observation that a spectrum $f(x)$, applied to one of the incoming beams only, results in a cross section

$$\sigma = \int dx f(x) \hat{\sigma}(xs). \quad (10.68)$$

We want to compute the distribution of $E = \sqrt{\hat{s}} = \sqrt{xs}$, i.e.,

$$\frac{d\sigma}{dE} = \frac{2\sqrt{x}}{\sqrt{s}} \frac{d\sigma}{dx} = \frac{2\sqrt{x}}{\sqrt{s}} f(x) \hat{\sigma}(xs), \quad (10.69)$$

so if we set

$$f(x) = \frac{\sqrt{s}}{2\sqrt{x}}, \quad (10.70)$$

we get the distribution

$$\frac{d\sigma}{dE} = \hat{\sigma}(\hat{s} = E^2). \quad (10.71)$$

If we want to start, in the first iteration, from a homogeneous energy scan, we should apply a mapping

$$x = y^2 \quad \text{with} \quad dx = 2\sqrt{x} dy, \quad (10.72)$$

which cancels out $f(x)$ apart from the numerator \sqrt{s} .

The input parameter for this spectrum apply to the energy directly. Note that the spectrum must not applied to more than one beam, and that the total cross section is essentially meaningless (it is the area under the energy distribution).

A direct application of this procedure would, of course, result in boosted events since only one beam energy is scaled down. However, we can achieve the same effect without a boost if we scale both x values such that their product remains constant, i.e., instead of generating x and applying it for one beam, we apply \sqrt{x} for both beams.

`<sf_escan.f90>≡`
`<File header>`

`module sf_escan`

`<Use kinds>`

`<Use strings>`

`<Use file utils>`

`use diagnostics !NODEP!`

`use lorentz !NODEP!`

`use flavors`

`use helicities`

`use colors`

`use quantum_numbers`

`use state_matrices`

`use polarizations`

`use interactions`

```

    use sf_aux

    <Standard module head>

    <Escan: public>

    <Escan: types>

    contains

    <Escan: procedures>

    end module sf_escan

```

10.7.1 Data type

```

<Escan: public>≡
    public :: escan_data_t

<Escan: types>≡
    type :: escan_data_t
        private
        logical, dimension(2) :: affects_beam
        type(flavor_t), dimension(2) :: flv
        real(default), dimension(2) :: mass = 0
        real(default) :: sqrts = 0
    end type escan_data_t

<Escan: public>+≡
    public :: escan_data_init

<Escan: procedures>≡
    subroutine escan_data_init (data, affects_beam, flv_in, sqrts)
        type(escan_data_t), intent(out) :: data
        logical, dimension(2), intent(in) :: affects_beam
        type(flavor_t), dimension(2), intent(in) :: flv_in
        real(default), intent(in) :: sqrts
        data%affects_beam = affects_beam
        data%flv = flv_in
        data%mass = flavor_get_mass (data%flv)
        data%sqrts = sqrts
    end subroutine escan_data_init

```

Output

```

<Escan: public>+≡
    public :: escan_data_write

<Escan: procedures>+≡
    subroutine escan_data_write (data, unit, md5)
        type(escan_data_t), intent(in) :: data
        integer, intent(in), optional :: unit
        integer :: u
        logical, intent(in), optional :: md5
        u = output_unit (unit); if (u < 0) return
    end subroutine escan_data_write

```



```

write (u, *) "Energy-scan data:"
write (u, *) " prt_in = ", char (flavor_get_name (data%flv(1))), &
    ", ", char (flavor_get_name (data%flv(2)))
end subroutine escan_data_write

```

10.7.2 The Energy-scan object

This is a spectrum, not a radiation. Depending on whether one or both beams are involved, we create an interaction with 1 (2) incoming and 1 (2) outgoing particles, flavor, color, and helicity being carried through.

```

<Escan: public>+≡
    public :: interaction_init_escan

<Escan: procedures>+≡
    subroutine interaction_init_escan (int, data)
        type(interaction_t), intent(out) :: int
        type(escan_data_t), intent(in) :: data
        type(quantum_numbers_mask_t), dimension(4) :: mask
        integer, dimension(4) :: hel_lock
        type(quantum_numbers_t), dimension(4) :: qn_fc, qn_hel, qn
        type(polarization_t) :: pol1, pol2
        type(state_iterator_t) :: it_hel1, it_hel2
        integer :: i
        if (all (data%affects_beam)) then
            hel_lock = (/ 3, 4, 1, 2 /)
            call interaction_init &
                (int, 2, 0, 2, mask=mask, hel_lock=hel_lock, set_relations=.true.)
        else if (data%affects_beam(1)) then
            hel_lock = (/ 2, 1, 0, 0 /)
            call interaction_init &
                (int, 1, 0, 1, mask=mask(1:2), hel_lock=hel_lock(1:2), set_relations=.true.)
        else if (data%affects_beam(2)) then
            hel_lock = (/ 2, 1, 0, 0 /)
            call interaction_init &
                (int, 1, 0, 1, mask=mask(1:2), hel_lock=hel_lock(1:2), set_relations=.true.)
        end if
        do i = 1, 2
            call quantum_numbers_init (qn_fc(i), &
                flv = data%flv(i), col = color_from_flavor (data%flv(i)))
            call quantum_numbers_init (qn_fc(i+2), &
                flv = data%flv(i), col = color_from_flavor (data%flv(i)))
        end do
        call polarization_init_generic (pol1, data%flv(1))
        call state_iterator_init (it_hel1, pol1%state)
        do while (state_iterator_is_valid (it_hel1))
            qn_hel(1:1) = state_iterator_get_quantum_numbers (it_hel1)
            qn_hel(3:3) = state_iterator_get_quantum_numbers (it_hel1)
            call polarization_init_generic (pol2, data%flv(2))
            call state_iterator_init (it_hel2, pol2%state)
            do while (state_iterator_is_valid (it_hel2))
                qn_hel(2:2) = state_iterator_get_quantum_numbers (it_hel2)
                qn_hel(4:4) = state_iterator_get_quantum_numbers (it_hel2)
            end do
            qn = qn_hel .merge. qn_fc
        end do
    end subroutine

```

```

        if (all (data%affects_beam)) then
            call interaction_add_state (int, qn)
        else if (data%affects_beam(1)) then
            call interaction_add_state (int, qn((/1,3/)))
        else if (data%affects_beam(2)) then
            call interaction_add_state (int, qn((/2,4/)))
        end if
        call state_iterator_advance (it_hel2)
    end do
    call polarization_final (pol2)
    call state_iterator_advance (it_hel1)
end do
call polarization_final (pol2)
call interaction_freeze (int)
end subroutine interaction_init_escan

```

10.7.3 Energy-scan structure function

This is the structure function for a single beam, suitably mapped.

As stated above, the mapping cancels the denominator of the structure function, so the factor is a constant. The normalization is determined such that the integral (the 'cross section' returned by WHIZARD) is unity for a unit test matrix element.

```

<Escan: procedures>+≡
subroutine strfun (f, x, r, data)
    real(default), intent(out) :: f, x
    real(default), intent(in) :: r
    type(escan_data_t), intent(in) :: data
    x = r**2
    f = 1
end subroutine strfun

```

10.7.4 Energy scan application

Depending on the affected beams, we either apply the structure function to one beam, or to both beams using the square root of x_i .

There is no `no_map` flag involved since there is no mapping anyway.

```

<Escan: public>+≡
public :: interaction_apply_escan

<Escan: procedures>+≡
subroutine interaction_apply_escan (int, r, data)
    type(interaction_t), intent(inout), target :: int
    real(default), dimension(1), intent(in) :: r
    type(escan_data_t), intent(in) :: data
    type(vector4_t), dimension(2) :: k
    real(default) :: f, xx
    real(default), dimension(2) :: x
    type(splitting_data_t), dimension(2) :: sd
    type(vector4_t), dimension(4) :: q

```

```

k(1) = interaction_get_momentum (int, 1)
if (all (data%affects_beam)) then
    k(2) = interaction_get_momentum (int, 2)
else
    k(2) = k(1)
end if
call strfun (f, xx, r(1), data)
if (all (data%affects_beam)) then
    x = sqrt (xx)
else
    where (data%affects_beam)
        x = xx
    elsewhere
        x = 1
    end where
end if
call interaction_set_matrix_element (int, cmplx (f, kind=default))
sd = new_splitting_data (k, data%mass**2, 0._default, data%mass)
call splitting_set_t_bounds (sd, x, 1-x)
call splitting_set_collinear (sd)
q((/1, 3/)) = split_momentum (k(1), sd(1))
q((/2, 4/)) = split_momentum (k(2), sd(2))
if (all (data%affects_beam)) then
    call interaction_set_momenta (int, q(3:4), outgoing=.true.)
else if (data%affects_beam(1)) then
    call interaction_set_momenta (int, q(3:3), outgoing=.true.)
else if (data%affects_beam(2)) then
    call interaction_set_momenta (int, q(4:4), outgoing=.true.)
end if
end subroutine interaction_apply_escan

```

10.8 Using beam event data

Instead of an analytic beam description, beam data may be provided in form of an event file. In its most simple form, the event file contains pairs of x values, relative to nominal beam energies. More advanced formats may include polarization, etc. The current implementation carries beam polarization through, if specified.

The code is very similar to the energy scan described above.

```

<sf_beam_events.f90>≡
<File header>

module sf_beam_events

<Use kinds>
<Use strings>
<Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use flavors
    use helicities

```

```

use colors
use quantum_numbers
use state_matrices
use polarizations
use interactions
use sf_aux

<Standard module head>

<Beam events: public>

<Beam events: types>

contains

<Beam events: procedures>

end module sf_beam_events

```

10.8.1 Data type

```

<Beam events: public>≡
    public :: beam_events_data_t

<Beam events: types>≡
    type :: beam_events_data_t
    private
    logical, dimension(2) :: affects_beam
    type(flavor_t), dimension(2) :: flv
    real(default), dimension(2) :: mass = 0
    type(string_t) :: file
    logical :: warn_eof = .true.
    integer :: unit = 0
    end type beam_events_data_t

<Beam events: public>+≡
    public :: beam_events_data_init

<Beam events: procedures>≡
    subroutine beam_events_data_init (data, affects_beam, flv_in, file, warn_eof)
        type(beam_events_data_t), intent(out) :: data
        logical, dimension(2), intent(in) :: affects_beam
        type(flavor_t), dimension(2), intent(in) :: flv_in
        type(string_t), intent(in) :: file
        logical, intent(in) :: warn_eof
        data%affects_beam = affects_beam
        data%flv = flv_in
        data%mass = flavor_get_mass (data%flv)
        data%file = file
        data%warn_eof = warn_eof
    end subroutine beam_events_data_init

```

Output

```

<Beam events: public>+≡
    public :: beam_events_data_write

<Beam events: procedures>+≡
    subroutine beam_events_data_write (data, unit, md5)
        type (beam_events_data_t), intent(in) :: data
        integer, intent(in), optional :: unit
        integer :: u
        logical, intent(in), optional :: md5
        u = output_unit (unit); if (u < 0) return
        write (u, *) "Beam-event file data:"
        write (u, *) "  prt_in  = ", char (flavor_get_name (data%flv(1))), &
            ", ", char (flavor_get_name (data%flv(2)))
        write (u, *) "  file = '", char (data%file), "'"
        write (u, *) "  warn_eof = ", data%warn_eof
        write (u, *) "  unit = ", data%unit
    end subroutine beam_events_data_write

```

The data file needs to be opened and closed explicitly:

```

<Beam events: public>+≡
    public :: beam_events_data_open
    public :: beam_events_data_close

<Beam events: procedures>+≡
    subroutine beam_events_data_open (data)
        type (beam_events_data_t), intent(inout) :: data
        if (data%unit == 0) then
            data%unit = free_unit ()
            open (unit = data%unit, file = char (data%file))
        else
            call msg_fatal ("Reading beam events: file '" &
                // char (data%file) // "' is already open.")
        end if
        call msg_message ("Reading beam events from file '" &
            // char (data%file) // "'")
    end subroutine beam_events_data_open

    subroutine beam_events_data_close (data)
        type (beam_events_data_t), intent(inout) :: data
        if (data%unit /= 0) then
            close (data%unit)
            data%unit = 0
        end if
    end subroutine beam_events_data_close

```

10.8.2 The Energy-scan object

This is a spectrum, not a radiation. Depending on whether one or both beams are involved, we create an interaction with 1 (2) incoming and 1 (2) outgoing particles, flavor, color, and helicity being carried through.

```

<Beam events: public>+≡
    public :: interaction_init_beam_events

```

<Beam events: procedures>+≡

```

subroutine interaction_init_beam_events (int, data)
  type(interaction_t), intent(out) :: int
  type(beam_events_data_t), intent(in) :: data
  type(quantum_numbers_mask_t), dimension(4) :: mask
  integer, dimension(4) :: hel_lock
  type(quantum_numbers_t), dimension(4) :: qn_fc, qn_hel, qn
  type(polarization_t) :: pol1, pol2
  type(state_iterator_t) :: it_hel1, it_hel2
  integer :: i
  if (all (data%affects_beam)) then
    hel_lock = (/ 3, 4, 1, 2 /)
    call interaction_init &
      (int, 2, 0, 2, mask=mask, hel_lock=hel_lock, set_relations=.true.)
  else if (data%affects_beam(1)) then
    hel_lock = (/ 2, 1, 0, 0 /)
    call interaction_init &
      (int, 1, 0, 1, mask=mask(1:2), hel_lock=hel_lock(1:2), set_relations=.true.)
  else if (data%affects_beam(2)) then
    hel_lock = (/ 2, 1, 0, 0 /)
    call interaction_init &
      (int, 1, 0, 1, mask=mask(1:2), hel_lock=hel_lock(1:2), set_relations=.true.)
  end if
  do i = 1, 2
    call quantum_numbers_init (qn_fc(i), &
      flv = data%flv(i), col = color_from_flavor (data%flv(i)))
    call quantum_numbers_init (qn_fc(i+2), &
      flv = data%flv(i), col = color_from_flavor (data%flv(i)))
  end do
  call polarization_init_generic (pol1, data%flv(1))
  call state_iterator_init (it_hel1, pol1%state)
  do while (state_iterator_is_valid (it_hel1))
    qn_hel(1:1) = state_iterator_get_quantum_numbers (it_hel1)
    qn_hel(3:3) = state_iterator_get_quantum_numbers (it_hel1)
    call polarization_init_generic (pol2, data%flv(2))
    call state_iterator_init (it_hel2, pol2%state)
    do while (state_iterator_is_valid (it_hel2))
      qn_hel(2:2) = state_iterator_get_quantum_numbers (it_hel2)
      qn_hel(4:4) = state_iterator_get_quantum_numbers (it_hel2)
      qn = qn_hel .merge. qn_fc
      if (all (data%affects_beam)) then
        call interaction_add_state (int, qn)
      else if (data%affects_beam(1)) then
        call interaction_add_state (int, qn((/1,3/)))
      else if (data%affects_beam(2)) then
        call interaction_add_state (int, qn((/2,4/)))
      end if
      call state_iterator_advance (it_hel2)
    end do
    call polarization_final (pol2)
    call state_iterator_advance (it_hel1)
  end do
  call polarization_final (pol2)
  call interaction_freeze (int)

```

```
end subroutine interaction_init_beam_events
```

10.8.3 Beam-event file structure function

This is actually not a structure function but a routine that reads a single line from the event file. If EOF is reached, we reread from the beginning and issue a warning (unless `warn_eof` is unset).

This is a rare occasion where a conditional jump is really appropriate: we want to catch EOF, but not other I/O errors.

```
<Beam events: procedures>+≡
subroutine read_x (x, data)
  real(default), dimension(:), intent(out) :: x
  type(beam_events_data_t), intent(in) :: data
  read (unit=data%unit, fmt=*, end=1) x
  return
1  if (data%warn_eof) &
      call msg_warning ("Reading beam event file: EOF reached, rewinding.")
  rewind (data%unit)
  read (unit=data%unit, fmt=*) x
end subroutine read_x
```

10.8.4 Energy scan application

Depending on the affected beams, we either apply the read x values to one beam or to both beams.

```
<Beam events: public>+≡
public :: interaction_apply_beam_events

<Beam events: procedures>+≡
subroutine interaction_apply_beam_events (int, data)
  type(interaction_t), intent(inout), target :: int
  type(beam_events_data_t), intent(in) :: data
  type(vector4_t), dimension(2) :: k
  real(default), dimension(:), allocatable :: x
  type(splitting_data_t), dimension(2) :: sd
  type(vector4_t), dimension(4) :: q
  complex(default), parameter :: c_one = 1
  k(1) = interaction_get_momentum (int, 1)
  if (all (data%affects_beam)) then
    k(2) = interaction_get_momentum (int, 2)
  else
    k(2) = k(1)
  end if
  allocate (x (count (data%affects_beam)))
  call read_x (x, data)
  call interaction_set_matrix_element (int, c_one)
  sd = new_splitting_data (k, data%mass**2, 0._default, data%mass)
  call splitting_set_t_bounds (sd, x, 1-x)
  call splitting_set_collinear (sd)
  q((/1, 3/)) = split_momentum (k(1), sd(1))
  q((/2, 4/)) = split_momentum (k(2), sd(2))
```

```

if (all (data%affects_beam)) then
  call interaction_set_momenta (int, q(3:4), outgoing=.true.)
else if (data%affects_beam(1)) then
  call interaction_set_momenta (int, q(3:3), outgoing=.true.)
else if (data%affects_beam(2)) then
  call interaction_set_momenta (int, q(4:4), outgoing=.true.)
end if
end subroutine interaction_apply_beam_events

```


10.9 LHAPDF

Parton distribution functions (PDFs) are available via an interface to the LHAPDF standard library.

The default PDF for protons set is chosen to be CTEQ6ll (LO fit with LO α_s).

```
<Limits: public parameters>+≡
    character(*), parameter, public :: LHAPDF_DEFAULT_PROTON = "cteq6ll.LHpdf"
    character(*), parameter, public :: LHAPDF_DEFAULT_PION   = "ABFKWPI.LHgrid"
    character(*), parameter, public :: LHAPDF_DEFAULT_PHOTON = "GSG960.LHgrid"
```

10.9.1 The module

```
<(sf_lhapdf.f90)≡
<File header>

module sf_lhapdf

<Use kinds>
<Use strings>
    use system_dependencies, only: LHAPDF_PDFSETS_PATH !NODEP!
    use system_dependencies, only: LHAPDF_AVAILABLE !NODEP!
    use limits, only: LHAPDF_DEFAULT_PROTON !NODEP!
    use limits, only: LHAPDF_DEFAULT_PION !NODEP!
    use limits, only: LHAPDF_DEFAULT_PHOTON !NODEP!
<Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use models
    use flavors
    use colors
    use quantum_numbers
    use state_matrices
    use polarizations
    use interactions
    use sf_aux

<Standard module head>

<LHAPDF: public>

<LHAPDF: types>

<LHAPDF: interfaces>

contains

<LHAPDF: procedures>

end module sf_lhapdf
```

10.9.2 LHAPDF library interface

Here we specify explicit interfaces for all LHAPDF routines that we use below.

$\langle \text{LHAPDF: interfaces} \rangle \equiv$

```
interface
  subroutine InitPDFsetM (set, file)
    integer, intent(in) :: set
    character(*), intent(in) :: file
  end subroutine InitPDFsetM
end interface
```

$\langle \text{LHAPDF: interfaces} \rangle + \equiv$

```
interface
  subroutine InitPDFM (set, mem)
    integer, intent(in) :: set, mem
  end subroutine InitPDFM
end interface
```

$\langle \text{LHAPDF: interfaces} \rangle + \equiv$

```
interface
  subroutine numberPDFM (set, n_members)
    integer, intent(in) :: set
    integer, intent(out) :: n_members
  end subroutine numberPDFM
end interface
```

$\langle \text{LHAPDF: interfaces} \rangle + \equiv$

```
interface
  subroutine evolvePDFM (set, x, q, ff)
    integer, intent(in) :: set
    double precision, intent(in) :: x, q
    double precision, dimension(-6:6), intent(out) :: ff
  end subroutine evolvePDFM
end interface
```

$\langle \text{LHAPDF: interfaces} \rangle + \equiv$

```
interface
  subroutine evolvePDFphotonM (set, x, q, ff, fphot)
    integer, intent(in) :: set
    double precision, intent(in) :: x, q
    double precision, dimension(-6:6), intent(out) :: ff
    double precision, intent(out) :: fphot
  end subroutine evolvePDFphotonM
end interface
```

$\langle \text{LHAPDF: interfaces} \rangle + \equiv$

```
interface
  subroutine evolvePDFpM (set, x, q, s, scheme, ff)
    integer, intent(in) :: set
    double precision, intent(in) :: x, q, s
    integer, intent(in) :: scheme
    double precision, dimension(-6:6), intent(out) :: ff
  end subroutine evolvePDFpM
end interface
```

```

        end subroutine evolvePDFpM
    end interface

    <LHAPDF: interfaces> +=
    interface
        subroutine GetXminM (set, mem, xmin)
            integer, intent(in) :: set, mem
            double precision, intent(out) :: xmin
        end subroutine GetXminM
    end interface

    <LHAPDF: interfaces> +=
    interface
        subroutine GetXmaxM (set, mem, xmax)
            integer, intent(in) :: set, mem
            double precision, intent(out) :: xmax
        end subroutine GetXmaxM
    end interface

    <LHAPDF: interfaces> +=
    interface
        subroutine GetQ2minM (set, mem, q2min)
            integer, intent(in) :: set, mem
            double precision, intent(out) :: q2min
        end subroutine GetQ2minM
    end interface

    <LHAPDF: interfaces> +=
    interface
        subroutine GetQ2maxM (set, mem, q2max)
            integer, intent(in) :: set, mem
            double precision, intent(out) :: q2max
        end subroutine GetQ2maxM
    end interface

    <LHAPDF: interfaces> +=
    interface
        function has_photon () result(flag)
            logical :: flag
        end function has_photon
    end interface

```

10.9.3 The LHAPDF status

This type holds the initialization status of the LHAPDF system.

```

    <LHAPDF: public> =
    public :: lhapdf_status_t

    <LHAPDF: types> =
    type :: lhapdf_status_t
    private
        logical, dimension(3) :: initialized = .false.

```

```

end type lhpdf_status_t

<LHAPDF: public>+≡
public :: lhpdf_status_reset

<LHAPDF: procedures>≡
subroutine lhpdf_status_reset (lhpdf_status)
  type(lhpdf_status_t), intent(inout) :: lhpdf_status
  lhpdf_status%initialized = .false.
end subroutine lhpdf_status_reset

<LHAPDF: procedures>+≡
function lhpdf_status_is_initialized (lhpdf_status, set) result (flag)
  logical :: flag
  type(lhpdf_status_t), intent(in) :: lhpdf_status
  integer, intent(in), optional :: set
  if (present (set)) then
    select case (set)
      case (1:3);    flag = lhpdf_status%initialized(set)
      case default;  flag = .false.
    end select
  else
    flag = any (lhpdf_status%initialized)
  end if
end function lhpdf_status_is_initialized

<LHAPDF: procedures>+≡
subroutine lhpdf_status_set_initialized (lhpdf_status, set)
  type(lhpdf_status_t), intent(inout) :: lhpdf_status
  integer, intent(in) :: set
  lhpdf_status%initialized(set) = .true.
end subroutine lhpdf_status_set_initialized

```

10.9.4 LHAPDF initialization

Before using LHAPDF, we have to initialize it with a particular data set and member. This applies not just if we use structure functions, but also if we just use an α_s formula. The integer `set` should be 1 for proton, 2 for pion, and 3 for photon, but this is just convention.

If the particular set has already been initialized, do nothing. This implies that whenever we want to change the setup for a particular set, we have to reset the LHAPDF status.

```

<LHAPDF: public>+≡
public :: lhpdf_init

<LHAPDF: procedures>+≡
subroutine lhpdf_init (status, set, prefix, file, member)
  type(lhpdf_status_t), intent(inout) :: status
  integer, intent(in) :: set
  type(string_t), intent(inout) :: prefix
  type(string_t), intent(inout) :: file
  integer, intent(inout) :: member

```

```

if (lhpdf_status_is_initialized (status, set)) return
if (prefix == "") prefix = LHAPDF_PDFSETS_PATH
if (file == "") then
  select case (set)
    case (1); file = LHAPDF_DEFAULT_PROTON
    case (2); file = LHAPDF_DEFAULT_PION
    case (3); file = LHAPDF_DEFAULT_PHOTON
  end select
end if
if (data_file_exists (prefix // "/" // file)) then
  call InitPDFsetM (set, char (prefix // "/" // file))
else
  call msg_fatal ("LHAPDF: Data file '" &
    // char (file) // "' not found in '" // char (prefix) // "'.")
  return
end if
if (.not. dataset_member_exists (set, member)) then
  call msg_error (" LHAPDF: Chosen member does not exist for set '" &
    // char (file) // "', using default.")
  member = 0
end if
call InitPDFM (set, member)
call lhpdf_status_set_initialized (status, set)
contains
function data_file_exists (fq_name) result (exist)
  type(string_t), intent(in) :: fq_name
  logical :: exist
  inquire (file = char(fq_name), exist = exist)
end function data_file_exists
function dataset_member_exists (set, member) result (exist)
  integer, intent(in) :: set, member
  logical :: exist
  integer :: n_members
  call numberPDFM (set, n_members)
  exist = member >= 0 .and. member <= n_members
end function dataset_member_exists
end subroutine lhpdf_init

```

10.9.5 The LHAPDF data block

The data block holds the incoming flavor (which has to be proton, pion, or photon), the corresponding pointer to the global access data (1, 2, or 3), the flag `invert` which is set for an antiproton, the bounds as returned by LHAPDF for the specified set, and a mask that determines which partons will be actually in use.

```

<LHAPDF: public>+≡
  public :: lhpdf_data_t

<LHAPDF: types>+≡
  type :: lhpdf_data_t
    private
    type(string_t) :: prefix

```

```

type(string_t) :: file
integer :: member = 0
type(model_t), pointer :: model => null ()
type(flavor_t) :: flv_in
integer :: set = 0
logical :: invert = .false.
logical :: photon = .false.
logical :: has_photon = .false.
integer :: photon_scheme = 0
real(default) :: xmin = 0, xmax = 0
real(default) :: qmin = 0, qmax = 0
logical, dimension(-6:6) :: mask = .true.
logical :: mask_photon = .true.
end type lhpdf_data_t

```

Generate PDF data. This is provided as a function, but it has the side-effect of initializing the requested PDF set. A finalizer is not needed.

The library uses double precision, so since the default precision may be quadruple, we use auxiliary variables for type casting.

```

<LHAPDF: public>+≡
public :: lhpdf_data_init

<LHAPDF: procedures>+≡
subroutine lhpdf_data_init &
  (data, status, model, flv, prefix, file, member, photon_scheme)
type(lhpdf_data_t), intent(out) :: data
type(lhpdf_status_t), intent(inout) :: status
type(model_t), intent(in), target :: model
type(flavor_t), intent(in) :: flv
type(string_t), intent(in), optional :: prefix, file
integer, intent(in), optional :: member
integer, intent(in), optional :: photon_scheme
integer :: mem
double precision :: xmin, xmax, q2min, q2max
external :: InitPDFsetM, InitPDFM, numberPDFM
external :: GetXminM, GetXmaxM, GetQ2minM, GetQ2maxM
if (.not. LHAPDF_AVAILABLE) then
  call msg_fatal ("LHAPDF requested but library is not linked")
  return
end if
data%model => model
data%flv_in = flv
select case (flavor_get_pdg (flv))
case (PROTON)
  data%set = 1
case (-PROTON)
  data%set = 1
  data%invert = .true.
case (PIPLUS)
  data%set = 2
case (-PIPLUS)
  data%set = 2
  data%invert = .true.
case (PHOTON)

```

```

        data%set = 3
        data%photon = .true.
        if (present (photon_scheme)) data%photon_scheme = photon_scheme
    case default
        call msg_fatal (" LHAPDF: " &
            // "incoming particle must be (anti)proton, pion, or photon.")
        return
    end select
    if (present (prefix)) then
        data%prefix = prefix
    else
        data%prefix = ""
    end if
    if (present (file)) then
        data%file = file
    else
        data%file = ""
    end if
    call lhpdf_init (status, data%set, data%prefix, data%file, data%member)
    call GetXminM (data%set, data%member, xmin)
    call GetXmaxM (data%set, data%member, xmax)
    call GetQ2minM (data%set, data%member, q2min)
    call GetQ2maxM (data%set, data%member, q2max)
    data%xmin = xmin
    data%xmax = xmax
    data%qmin = sqrt (q2min)
    data%qmax = sqrt (q2max)
    data%has_photon = has_photon ()
end subroutine lhpdf_data_init

```

Enable/disable partons explicitly. If a mask entry is true, applying the PDF will generate the corresponding flavor on output.

```

<LHAPDF: public>+≡
    public :: lhpdf_data_set_mask

<LHAPDF: procedures>+≡
    subroutine lhpdf_data_set_mask (data, mask)
        type(lhpdf_data_t), intent(inout) :: data
        logical, dimension(-6:6), intent(in) :: mask
        data%mask = mask
    end subroutine lhpdf_data_set_mask

```

Return the public part of the data set.

```

<LHAPDF: public>+≡
    public :: lhpdf_data_get_public_info

<LHAPDF: procedures>+≡
    subroutine lhpdf_data_get_public_info &
        (data, lhpdf_dir, lhpdf_file, lhpdf_member)
        type(lhpdf_data_t), intent(in) :: data
        type(string_t), intent(out) :: lhpdf_dir, lhpdf_file
        integer, intent(out) :: lhpdf_member
        lhpdf_dir = data%prefix
        lhpdf_file = data%file

```

```

    lhpdf_member = data%member
end subroutine lhpdf_data_get_public_info

```

Return the number of the member of the data set.

```

<LHAPDF: public>+≡
    public :: lhpdf_data_get_set

<LHAPDF: procedures>+≡
    function lhpdf_data_get_set(data) result(set)
        type(lhpdf_data_t), intent(in) :: data
        integer :: set
        set = data%set
    end function lhpdf_data_get_set

```

Output

```

<LHAPDF: public>+≡
    public :: lhpdf_data_write

<LHAPDF: procedures>+≡
    subroutine lhpdf_data_write (data, unit, md5, beam_fmt)
        type(lhpdf_data_t), intent(in) :: data
        integer, intent(in), optional :: unit
        integer :: u
        logical, intent(in), optional :: md5
        logical, intent(in), optional :: beam_fmt
        logical :: is_md5, is_beam_fmt
        if (present (md5)) then
            is_md5 = md5
        else
            is_md5 = .false.
        end if
        if (present (beam_fmt)) then
            is_beam_fmt = beam_fmt
        else
            is_beam_fmt = .false.
        end if
        u = output_unit (unit); if (u < 0) return
        write (u, *) "LHAPDF data:"
        if (data%set /= 0) then
            write (u, "(3x,A)", advance="no") "flavor          = "
            call flavor_write (data%flv_in, u); write (u, *)
            if (.not. is_md5) &
                write (u, *) " prefix          = ", char (data%prefix)
            write (u, *) " file              = ", char (data%file)
            write (u, *) " member            = ", data%member
            write (u, *) " x(min)           = ", data%xmin
            write (u, *) " x(max)           = ", data%xmax
            write (u, *) " Q^2(min)        = ", data%qmin
            write (u, *) " Q^2(max)        = ", data%qmax
            write (u, *) " invert          = ", data%invert
            if (data%photon) write (u, *) " IP2 (scheme) = ", data%photon_scheme
            if (.not. is_beam_fmt) then
                write (u, *) " mask              = ", &
                    data%mask(-6:-1), " ", data%mask(0), " ", data%mask(1:6)
            end if
        end if
    end subroutine lhpdf_data_write

```



```

        write (u, *) " photon mask = ", data%mask_photon
    end if
else
    write (u, *) " [undefined]"
end if
end subroutine lhpdf_data_write

```

10.9.6 The LHAPDF object

The `lhpdf_t` data type is a $1 \rightarrow 2$ interaction which describes the splitting of an (anti)proton into a parton and a beam remnant. We stay in the strict forward-splitting limit, but allow some invariant mass for the beam remnant such that the outgoing parton is exactly massless. For a real event, we would replace this by a parton cascade, where the outgoing partons have virtuality as dictated by parton-shower kinematics, and transverse momentum is generated.

This is the LHAPDF object which holds input data together with the interaction. We also store the x momentum fraction and the scale, since kinematics and function value are requested at different times.

The PDF application is a $1 \rightarrow 2$ splitting process, where the particles are ordered as (hadron, remnant, parton).

Polarization is ignored completely. The beam particle is colorless, while partons and beam remnant carry color. The remnant gets a special flavor code.

<LHAPDF: public>+≡

```
public :: interaction_init_lhpdf
```

<LHAPDF: procedures>+≡

```

subroutine interaction_init_lhpdf (int, data)
    type(interaction_t), intent(out) :: int
    type(lhpdf_data_t), intent(in) :: data
    type(quantum_numbers_mask_t), dimension(3) :: mask
    type(quantum_numbers_t) :: qn_beam, qn_remnant, qn_parton
    type(flavor_t) :: flv, flv_remnant
    integer :: i
    mask = new_quantum_numbers_mask (.false., .false., .true.)
    call interaction_init (int, 1, 0, 2, mask=mask, set_relations=.true.)
    call quantum_numbers_init (qn_beam, flv = data%flv_in)
    do i = -6, 6
        if (data%mask(i)) then
            if (i == 0) then
                call flavor_init (flv, GLUON, data%model)
                call flavor_init (flv_remnant, HADRON_REMNANT_OCTET, data%model)
            else
                call flavor_init (flv, i, data%model)
                call flavor_init (flv_remnant, &
                    sign (HADRON_REMNANT_TRIPLET, -i), data%model)
            end if
            call quantum_numbers_init (qn_remnant, &
                flv = flv_remnant, col = color_from_flavor (flv_remnant, 1))
            call quantum_numbers_init (qn_parton, &
                flv = flv, col = color_from_flavor (flv, 1, reverse=.true.))
            call interaction_add_state (int, &
                (/ qn_beam, qn_remnant, qn_parton /))
        end if
    end do
end subroutine interaction_init_lhpdf

```

```

        end if
    end do
    if (data%has_photon .and. data%mask_photon) then
        call flavor_init (flv, PHOTON, data%model)
        call flavor_init (flv_remnant, HADRON_REMNANT_SINGLET, data%model)
        call quantum_numbers_init (qn_remnant, flv = flv_remnant, &
            col = color_from_flavor (flv_remnant, 1))
        call quantum_numbers_init (qn_parton, flv = flv, &
            col = color_from_flavor (flv, 1, reverse=.true.))
        call interaction_add_state (int, &
            (/qn_beam, qn_remnant, qn_parton /))
    end if
    call interaction_freeze (int)
end subroutine interaction_init_lhapdf

```

10.9.7 Structure function

For the PDFs, we separate kinematics from dynamics. We first generate appropriate x values, independent of flavor and scale. This allows us to determine the momenta that initiate the hard scattering. Only when the hard process has been computed, we can be sure about the scattering scale and compute the structure function values.

For the x values, we can only apply a simple mapping that eliminates the $1/x$ singularity, i.e., we generate x on a logarithmic scale. This produces a Jacobian factor that we store along with the generated x value. The boundaries are used as returned by the LHAPDF library for the chosen PDF set.

```

<LHAPDF: procedures>+≡
subroutine generate_x (x, f, r, lhpdf_data)
    real(default), intent(out) :: x, f
    real(default), intent(in) :: r
    type(lhpdf_data_t), intent(in) :: lhpdf_data
    real(default) :: lg
    x = r
    f = 1
    !    lg = log (lhpdf_data% xmax / lhpdf_data% xmin)
    !    x = lhpdf_data% xmin * exp (r * lg)
    !    f = x * lg
end subroutine generate_x

```

The previous routine is called here, so we can compute the complete kinematics.

(There is no mapping involved [see above], otherwise we should take and respect a `no_map` flag.)

```

<LHAPDF: public>+≡
public :: interaction_set_kinematics_lhapdf

<LHAPDF: procedures>+≡
subroutine interaction_set_kinematics_lhapdf (int, x, f, s, r, lhpdf_data)
    type(interaction_t), intent(inout) :: int
    real(default), intent(out) :: x, f, s
    real(default), intent(in) :: r
    type(lhpdf_data_t), intent(in) :: lhpdf_data

```

```

type(vector4_t) :: k
type(splitting_data_t) :: sd
call generate_x (x, f, r, lhpdf_data)
k = interaction_get_momentum (int, 1)
s = k**2
sd = new_splitting_data (k, s, 0._default, 0._default)
call splitting_set_t_bounds (sd, x, 1 - x)
call splitting_set_collinear (sd)
call interaction_set_momenta &
      (int, split_momentum (k, sd), outgoing=.true.)
end subroutine interaction_set_kinematics_lhpdf

```

Once the scale is also known, we can actually call the library and set the values. If the scale is out of bounds, we reset it to the boundary. Account for the Jacobian.

We have to cast the LHAPDF arguments to/from double precision (possibly from/to quadruple precision), if necessary. Furthermore, some structure functions can yield negative results (sea quarks close to $x = 1$). We set these unphysical values to zero.

```

<LHAPDF: public>+≡
  public :: interaction_apply_lhpdf

<LHAPDF: procedures>+≡
  subroutine interaction_apply_lhpdf (int, scale, x, f, s, lhpdf_data)
    type(interaction_t), intent(inout) :: int
    real(default), intent(in) :: scale, x, f, s
    type(lhpdf_data_t), intent(in) :: lhpdf_data
    double precision :: xx, qq, ss
    double precision, dimension(-6:6) :: ff
    double precision :: fphot
    complex(default), dimension(:), allocatable :: fc
    external :: evolvePDFM, evolvePDFpM
    xx = x
    qq = min (lhpdf_data% qmax, scale)
    qq = max (lhpdf_data% qmin, qq)
    if (.not. lhpdf_data% photon) then
      if (lhpdf_data% invert) then
        if (lhpdf_data% has_photon) then
          call evolvePDFphotonM (lhpdf_data% set, xx, qq, ff(6:-6:-1), fphot)
        else
          call evolvePDFM (lhpdf_data% set, xx, qq, ff(6:-6:-1))
        end if
      else
        if (lhpdf_data% has_photon) then
          call evolvePDFphotonM (lhpdf_data% set, xx, qq, ff, fphot)
        else
          call evolvePDFM (lhpdf_data% set, xx, qq, ff)
        end if
      end if
    else
      ss = s
      call evolvePDFpM (lhpdf_data% set, xx, qq, &
        ss, lhpdf_data% photon_scheme, ff)
    end if
  end subroutine

```

```

end if
if (lhpdf_data%has_photon) then
  allocate (fc (count ((/lhpdf_data%mask, lhpdf_data%mask_photon/))))
  fc = max (pack ((/ff, fphot/) / x, &
    (/lhpdf_data% mask, lhpdf_data%mask_photon/)) * f, 0._default)
else
  allocate (fc (count (lhpdf_data%mask)))
  fc = max (pack (ff / x, lhpdf_data%mask) * f, 0._default)
end if
call interaction_set_matrix_element (int, fc)
end subroutine interaction_apply_lhpdf

```

10.10 Builtin PDF sets

For convenience as well and to provide functionality not covered by LHAPDF (like photons as partons), we ship some PDFs with WHIZARD.

```

<Limits: public parameters>+=
  character(*), parameter, public :: PDF_BUILTIN_DEFAULT_PROTON = "CTEQ6L"
  character(*), parameter, public :: PDF_BUILTIN_DEFAULT_PION   = "NONE"
  character(*), parameter, public :: PDF_BUILTIN_DEFAULT_PHOTON = "NONE"

```

10.10.1 The module

```

(sf_pdf_builtin.f90)≡
  <File header>

  module sf_pdf_builtin

    <Use kinds>
    <Use strings>
    use limits, only: PDF_BUILTIN_DEFAULT_PROTON !NODEP!
    use limits, only: PDF_BUILTIN_DEFAULT_PION   !NODEP!
    use limits, only: PDF_BUILTIN_DEFAULT_PHOTON !NODEP!
    <Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use pdf_builtin !NODEP!
    use models
    use flavors
    use colors
    use quantum_numbers
    use state_matrices
    use polarizations
    use interactions
    use sf_aux

    <Standard module head>

    <pdf builtin: public>

    <pdf builtin: types>

```

```
contains

<pdf builtin: procedures>

end module sf_pdf_builtin
```

10.10.2 The data block

The data block holds the incoming flavor (which has to be proton, pion, or photon), the corresponding pointer to the global access data (1, 2, or 3), the flag `invert` which is set for an antiproton, the bounds as returned by LHAPDF for the specified set, and a mask that determines which partons will be actually in use.

```
<pdf builtin: public>≡
    public :: pdf_builtin_data_t

<pdf builtin: types>≡
    type :: pdf_builtin_data_t
    private
    type(string_t) :: path
    integer :: id = -1
    type (string_t) :: name
    type(model_t), pointer :: model => null ()
    type(flavor_t) :: flv_in
    logical :: invert
    logical :: has_photon
    logical :: photon
    logical, dimension(-6:6) :: mask
    logical :: mask_photon
end type pdf_builtin_data_t
```

Generate PDF data and initialize the requested set. Pion and photon PDFs are disabled at the moment until we ship appropriate structure functions. needed.

```
<pdf builtin: public>+≡
    public :: pdf_builtin_init

<pdf builtin: procedures>≡
    subroutine pdf_builtin_init (data, pdf_status, model, flv, name, path)
    type(pdf_builtin_data_t), intent(out) :: data
    type(pdf_builtin_status_t), intent(inout) :: pdf_status
    type(model_t), intent(in), target :: model
    type(flavor_t), intent(in) :: flv
    type(string_t), intent(in), optional :: name
    type(string_t), intent(in), optional :: path
    data%model => model
    data%flv_in = flv
    data%mask = .true.
    data%mask_photon = .true.
    select case (flavor_get_pdg (flv))
    case (PROTON)
        data%name = var_str (PDF_BUILTIN_DEFAULT_PROTON)
        data%invert = .false.
```

```

        data%photon = .false.
    case (-PROTON)
        data%name = var_str (PDF_BUILTIN_DEFAULT_PROTON)
        data%invert = .true.
        data%photon = .false.
!   case (PIPLUS)
!       data%name = var_str (PDF_BUILTIN_DEFAULT_PION)
!       data%invert = .false.
!       data%photon = .false.
!   case (-PIPLUS)
!       data%name = var_str (PDF_BUILTIN_DEFAULT_PION)
!       data%invert = .true.
!       data%photon = .false.
!   case (PHOTON)
!       data%name = var_str (PDF_BUILTIN_DEFAULT_PHOTON)
!       data%invert = .false.
!       data%photon = .true.
    case default
        call msg_fatal (" PDF: " &
            // "incoming particle must either proton or antiproton.")
        return
    end select
    if (present (name)) then
        data%name = name
    end if
    if (present (path)) then
        data%path = path
    else
        data%path = "."
    end if
    data%id = pdf_get_id (data%name)
    if (data%id < 0) call msg_fatal ("unknown PDF set " // char (data%name))
    data%has_photon = pdf_provides_photon (data%id)
    call pdf_init (pdf_status, data%id, path)
end subroutine pdf_builtin_init

```

Finalize PDF data. invalidating the ID.

```

<pdf builtin: public>+≡
    public :: pdf_builtin_final

<pdf builtin: procedures>+≡
    subroutine pdf_builtin_final (data)
        type(pdf_builtin_data_t), intent(inout) :: data
        data%id = -1
    end subroutine pdf_builtin_final

```

Retrieve the name of the PDF.

```

<pdf builtin: public>+≡
    public :: pdf_builtin_get_name

<pdf builtin: procedures>+≡
    function pdf_builtin_get_name (data) result (name)
        type(pdf_builtin_data_t), intent(in) :: data
        type(string_t) :: name

```

```

    if (data%id < 0) then
        name = var_str ("undefined")
    else
        name = data%name
    end if
end function pdf_builtin_get_name

```

Retrieve the id of the PDF set used.

```

<pdf builtin: public>+≡
    public :: pdf_builtin_get_id

<pdf builtin: procedures>+≡
    function pdf_builtin_get_id (data) result (id)
        type(pdf_builtin_data_t), intent(in) :: data
        integer :: id
        id = data%id
    end function pdf_builtin_get_id

```

Enable/disable partons explicitly. If a mask entry is true, applying the PDF will generate the corresponding flavor on output.

```

<pdf builtin: public>+≡
    public :: pdf_builtin_data_set_mask

<pdf builtin: procedures>+≡
    subroutine pdf_builtin_data_set_mask (data, mask)
        type(pdf_builtin_data_t), intent(inout) :: data
        logical, dimension(-6:6), intent(in) :: mask
        data%mask = mask
    end subroutine pdf_builtin_data_set_mask

```

Output

```

<pdf builtin: public>+≡
    public :: pdf_builtin_data_write

<pdf builtin: procedures>+≡
    subroutine pdf_builtin_data_write (data, unit, md5, beam_fmt)
        type(pdf_builtin_data_t), intent(in) :: data
        integer, intent(in), optional :: unit
        integer :: u
        logical, intent(in), optional :: md5
        logical, intent(in), optional :: beam_fmt
        logical :: is_md5
        logical :: is_beam_fmt
        if (present (md5)) then
            is_md5 = md5
        else
            is_md5 = .false.
        end if
        if (present (beam_fmt)) then
            is_beam_fmt = beam_fmt
        else
            is_beam_fmt = .false.
        end if
    end if

```

```

u = output_unit (unit); if (u < 0) return
if (data%id < 0) then
  write (u, *) "[undefined]"
  return
end if
write (u, "(3x,A)", advance="no") "flavor      = "
call flavor_write (data%flv_in, u); write (u, *)
write (u, *) " name      = ", char (data%name)
if (.not. is_md5) &
  write (u, *) " grid path = ", char (data%path)
write (u, *) " invert     = ", data%invert
write (u, *) " has photon = ", data%has_photon
if (.not. is_beam_fmt) then
  write (u, *) " mask      = ", &
    data%mask(-6:-1), " ", data%mask(0), " ", data%mask(1:6)
  write (u, *) " photon mask = ", data%mask_photon
end if
end subroutine pdf_builtin_data_write

```

10.10.3 The PDF object

The PDF $1 \rightarrow 2$ interaction which describes the splitting of an (anti)proton into a parton and a beam remnant. We stay in the strict forward-splitting limit, but allow some invariant mass for the beam remnant such that the outgoing parton is exactly massless. For a real event, we would replace this by a parton cascade, where the outgoing partons have virtuality as dictated by parton-shower kinematics, and transverse momentum is generated.

The PDF application is a $1 \rightarrow 2$ splitting process, where the particles are ordered as (hadron, remnant, parton).

Polarization is ignored completely. The beam particle is colorless, while partons and beam remnant carry color. The remnant gets a special flavor code.

This code is an next-to-exact copy of that found above in `sf_lhapdf`.

(pdf builtin: public)+≡

```
public :: interaction_init_pdf_builtin
```

(pdf builtin: procedures)+≡

```

subroutine interaction_init_pdf_builtin (int, data)
  type(interaction_t), intent(out) :: int
  type(pdf_builtin_data_t), intent(in) :: data
  type(quantum_numbers_mask_t), dimension(3) :: mask
  type(quantum_numbers_t) :: qn_beam, qn_remnant, qn_parton
  type(flavor_t) :: flv, flv_remnant
  integer :: i
  mask = new_quantum_numbers_mask (.false., .false., .true.)
  call interaction_init (int, 1, 0, 2, mask=mask, set_relations=.true.)
  call quantum_numbers_init (qn_beam, flv = data%flv_in)
  do i = -6, 6
    if (data%mask(i)) then
      if (i == 0) then
        call flavor_init (flv, GLUON, data%model)
        call flavor_init (flv_remnant, HADRON_REMNANT_OCTET, data%model)
      else

```



```

        call flavor_init (flv, i, data%model)
        call flavor_init (flv_remnant, &
            sign (HADRON_REMNANT_TRIPLET, -i), data%model)
    end if
    call quantum_numbers_init (qn_remnant, &
        flv = flv_remnant, col = color_from_flavor (flv_remnant, 1))
    call quantum_numbers_init (qn_parton, &
        flv = flv, col = color_from_flavor (flv, 1, reverse=.true.))
    call interaction_add_state (int, &
        (/ qn_beam, qn_remnant, qn_parton /))
    end if
end do
if (data%has_photon .and. data%mask_photon) then
    call flavor_init (flv, PHOTON, data%model)
    call flavor_init (flv_remnant, HADRON_REMNANT_SINGLET, data%model)
    call quantum_numbers_init (qn_remnant, flv = flv_remnant, &
        col = color_from_flavor (flv_remnant, 1))
    call quantum_numbers_init (qn_parton, flv = flv, &
        col = color_from_flavor (flv, 1, reverse = .true.))
    call interaction_add_state (int, &
        (/ qn_beam, qn_remnant, qn_parton /))
end if
call interaction_freeze (int)
end subroutine interaction_init_pdf_builtin

```

10.10.4 Structure function

For the PDFs, we separate kinematics from dynamics. We first generate appropriate x values, independent of flavor and scale. This allows us to determine the momenta that initiate the hard scattering. Only when the hard process has been computed, we can be sure about the scattering scale and compute the structure function values.

For the x values, we can only apply a simple mapping that eliminates the $1/x$ singularity, i.e., we generate x on a logarithmic scale. This produces a Jacobian factor that we store along with the generated x value. The boundaries are used as returned by the LHAPDF library for the chosen PDF set.

This code is an next-to-exact copy of that found above in `sf_lhapdf`.

```

(pdf builtin: procedures)+≡
subroutine generate_x (x, f, r, data)
    real(default), intent(out) :: x, f
    real(default), intent(in) :: r
    type(pdf_builtin_data_t), intent(in) :: data
    real(default) :: lg
    x = r
    f = 1
    !   lg = log (lhpdf_data% xmax / lhpdf_data% xmin)
    !   x = lhpdf_data% xmin * exp (r * lg)
    !   f = x * lg
end subroutine generate_x

```

The previous routine is called here, so we can compute the complete kinematics.
 (There is no mapping involved [see above], otherwise we should take and respect a `no_map` flag.)

Again, shamelessly stolen from `sf_lhapdf`.

```

(pdf builtin: public)+≡
  public :: interaction_set_kinematics_pdf_builtin

(pdf builtin: procedures)+≡
  subroutine interaction_set_kinematics_pdf_builtin (int, x, f, s, r, data)
    type(interaction_t), intent(inout) :: int
    real(default), intent(out) :: x, f, s
    real(default), intent(in) :: r
    type(pdf_builtin_data_t), intent(in) :: data
    type(vector4_t) :: k
    type(splitting_data_t) :: sd
    call generate_x (x, f, r, data)
    k = interaction_get_momentum (int, 1)
    s = k**2
    sd = new_splitting_data (k, s, 0._default, 0._default)
    call splitting_set_t_bounds (sd, x, 1 - x)
    call splitting_set_collinear (sd)
    call interaction_set_momenta &
      (int, split_momentum (k, sd), outgoing=.true.)
  end subroutine interaction_set_kinematics_pdf_builtin

```

Once the scale is also known, we can actually call the PDF and set the values.
 Contrary to LHAPDF, the wrapper already takes care of adjusting to the x and Q bounds. Account for the Jacobian.

```

(pdf builtin: public)+≡
  public :: interaction_apply_pdf_builtin

(pdf builtin: procedures)+≡
  subroutine interaction_apply_pdf_builtin (int, scale, x, f, s, data)
    type(interaction_t), intent(inout) :: int
    real(default), intent(in) :: scale, x, f, s
    type(pdf_builtin_data_t), intent(in) :: data
    real(kind=default) :: ff(-6:6), fph
    complex(default), dimension(:), allocatable :: fc
    if (data%invert) then
      if (data%has_photon) then
        call pdf_evolve (data%id, x, scale, ff(6:-6:-1), fph)
      else
        call pdf_evolve (data%id, x, scale, ff(6:-6:-1))
      end if
    else
      if (data%has_photon) then
        call pdf_evolve (data%id, x, scale, ff, fph)
      else
        call pdf_evolve (data%id, x, scale, ff)
      end if
    end if
    if (data%has_photon) then
      allocate (fc (count ((/data%mask, data%mask_photon/))))
      fc = max (pack ((/ff, fph/), &

```

```

        (/data%mask, data%mask_photon/)) * f, 0._default)
    else
        allocate (fc (count (data%mask)))
        fc = max (pack (ff, data%mask) * f, 0._default)
    end if
    call interaction_set_matrix_element (int, fc)
end subroutine interaction_apply_pdf_builtin

```

10.11 User Plugin for Structure Functions

This variant gives access to user-defined structure functions or spectra.

10.11.1 The module

```

⟨sf_user.f90⟩≡
  ⟨File header⟩

  module sf_user

    use iso_c_binding !NODEP!
    ⟨Use kinds⟩
    ⟨Use strings⟩
    ⟨Use file utils⟩
    use diagnostics !NODEP!
    use c_particles !NODEP!
    use lorentz !NODEP!
    use subevents
    use user_code_interface
    use models
    use flavors
    use helicities
    use colors
    use quantum_numbers
    use state_matrices
    use polarizations
    use interactions
    use sf_aux

    ⟨Standard module head⟩

    ⟨SF User: public⟩

    ⟨SF User: types⟩

    contains

    ⟨SF User: procedures⟩

  end module sf_user

```

10.11.2 The data block

The data block holds the procedure pointers that are used for retrieving static information, as well as the actual evaluation.

```

<SF User: public>≡
    public :: sf_user_data_t

<SF User: types>≡
    type :: sf_user_data_t
    private
        type(string_t) :: name
        integer :: n_in
        integer :: n_out
        integer :: n_tot
        integer :: n_states
        integer :: n_col
        integer :: n_dim
        integer :: n_var
        integer, dimension(2) :: pdg_in
        type(model_t), pointer :: model => null ()
        procedure(user_int_info), nopass, pointer :: info => null ()
        procedure(user_int_mask), nopass, pointer :: mask => null ()
        procedure(user_int_state), nopass, pointer :: state => null ()
        procedure(user_int_kinematics), nopass, pointer :: kinematics => null ()
        procedure(user_int_evaluate), nopass, pointer :: evaluate => null ()
    end type sf_user_data_t

```

Assign procedure pointers from a dynamically loaded library, given the specified name.

We have to distinguish three cases: (1) Both beams are affected, and the user spectrum implements both beams. There is a single data object. (2) Both beams are affected, and the user spectrum applies to single beams. Fill two different objects. (3) A single beam is affected.

```

<SF User: public>+≡
    public :: sf_user_data_init

<SF User: procedures>≡
    subroutine sf_user_data_init (data, name, flv, model)
        type(sf_user_data_t), intent(out) :: data
        type(string_t), intent(in) :: name
        type(flavor_t), dimension(2), intent(in) :: flv
        type(model_t), intent(in), target :: model
        integer(c_int) :: n_in
        integer(c_int) :: n_out
        integer(c_int) :: n_states
        integer(c_int) :: n_col
        integer(c_int) :: n_dim
        integer(c_int) :: n_var
        data%name = name
        data%pdg_in = flavor_get_pdg (flv)
        data%model => model
        call c_f_procpointer (user_code_find_proc (name // "_info"), data%info)
        call c_f_procpointer (user_code_find_proc (name // "_mask"), data%mask)
        call c_f_procpointer (user_code_find_proc (name // "_state"), data%state)
    end subroutine sf_user_data_init

```

```

call c_f_procpointer &
  (user_code_find_proc (name // "_kinematics"), data%kinematics)
call c_f_procpointer &
  (user_code_find_proc (name // "_evaluate"), data%evaluate)
n_in = 1
n_out = 2
n_states = 1
n_col = 2
n_dim = 1
n_var = 1
call data%info (n_in, n_out, n_states, n_col, n_dim, n_var)
data%n_in = n_in
data%n_out = n_out
data%n_tot = n_in + n_out
data%n_states = n_states
data%n_col = n_col
data%n_dim = n_dim
data%n_var = n_var
end subroutine sf_user_data_init

```

Output

```

<SF User: public>+≡
  public :: sf_user_data_write

<SF User: procedures>+≡
  subroutine sf_user_data_write (data, unit, md5)
    type(sf_user_data_t), intent(in) :: data
    integer, intent(in), optional :: unit
    integer :: u
    logical, intent(in), optional :: md5
    u = output_unit (unit); if (u < 0) return
    write (u, *) "User structure function: ", char (data%name)
  end subroutine sf_user_data_write

```

Retrieving contents

```

<SF User: public>+≡
  public :: sf_user_data_get_name

<SF User: procedures>+≡
  function sf_user_data_get_name (data) result (name)
    type(string_t) :: name
    type(sf_user_data_t), intent(in) :: data
    name = data%name
  end function sf_user_data_get_name

<SF User: public>+≡
  public :: sf_user_data_get_n_in
  public :: sf_user_data_get_n_out
  public :: sf_user_data_get_n_tot
  public :: sf_user_data_get_n_dim
  public :: sf_user_data_get_n_var

```

```

<SF User: procedures>+≡
function sf_user_data_get_n_in (data) result (n_in)
  integer :: n_in
  type(sf_user_data_t), intent(in) :: data
  n_in = data%n_in
end function sf_user_data_get_n_in

function sf_user_data_get_n_out (data) result (n_out)
  integer :: n_out
  type(sf_user_data_t), intent(in) :: data
  n_out = data%n_out
end function sf_user_data_get_n_out

function sf_user_data_get_n_tot (data) result (n_tot)
  integer :: n_tot
  type(sf_user_data_t), intent(in) :: data
  n_tot = data%n_tot
end function sf_user_data_get_n_tot

function sf_user_data_get_n_dim (data) result (n_dim)
  integer :: n_dim
  type(sf_user_data_t), intent(in) :: data
  n_dim = data%n_dim
end function sf_user_data_get_n_dim

function sf_user_data_get_n_var (data) result (n_var)
  integer :: n_var
  type(sf_user_data_t), intent(in) :: data
  n_var = data%n_var
end function sf_user_data_get_n_var

```

10.11.3 The interaction

We fill the interaction by looking up the table of states using the interface functions.

For particles which have a known flavor (as indicated by the mask), we compute the mass squared, so we can use it for the invariant mass of the particle objects.

```

<SF User: public>+≡
public :: interaction_init_sf_user

<SF User: procedures>+≡
subroutine interaction_init_sf_user (inter, data)
  type(interaction_t), intent(out) :: inter
  type(sf_user_data_t), intent(in) :: data
  type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
  integer, dimension(:), allocatable :: hel_lock
  integer(c_int) :: m_flv, m_hel, m_col, i_lock
  type(quantum_numbers_t), dimension(:), allocatable :: qn
  integer(c_int) :: f, h
  integer(c_int), dimension(:), allocatable :: c
  type(flavor_t) :: flv

```

```

type(helicity_t) :: hel
type(color_t) :: col
integer :: i, s
integer(c_int) :: i_prt, i_state
allocate (mask (data%n_tot))
allocate (hel_lock (data%n_tot))
allocate (qn (data%n_tot))
allocate (c (data%n_col))
do i = 1, size (mask)
  i_prt = i
  m_flv = 0; m_col = 0; m_hel = 0; i_lock = 0
  call data%mask (i_prt, m_flv, m_col, m_hel, i_lock)
  mask(i) = new_quantum_numbers_mask (m_flv /= 0, m_col /= 0, m_hel /= 0)
  hel_lock(i) = i_lock
end do
call interaction_init &
  (inter, data%n_in, 0, data%n_out, mask=mask, hel_lock=hel_lock, &
   set_relations=.true.)
do s = 1, data%n_states
  i_state = s
  do i = 1, data%n_tot
    i_prt = i
    f = 0; h = 0; c = 0
    call data%state (i_state, i_prt, f, h, c)
    if (m_flv == 0) then
      call flavor_init (flv, int (f), data%model)
    else
      call flavor_init (flv)
    end if
    if (m_hel == 0) then
      call helicity_init (hel, int (h))
    else
      call helicity_init (hel)
    end if
    if (m_col == 0) then
      call color_init_from_array (col, int (c))
    else
      call color_init (col)
    end if
    call quantum_numbers_init (qn(i), flv, col, hel)
  end do
  call interaction_add_state (inter, qn)
end do
call interaction_freeze (inter)
end subroutine interaction_init_sf_user

```

10.11.4 Structure function

For maximal flexibility, user structure functions separate kinematics from dynamics just as the PDF interface does. We create `c_prt_t` particle objects from the incoming momenta (all other quantum numbers are irrelevant) and call the user-supplied kinematics function to compute the outgoing momenta,

along with other variables that will be needed for matrix element evaluation. If known, we use the mass squared computed above.

```

<SF User: public>+≡
    public :: interaction_set_kinematics_sf_user

<SF User: procedures>+≡
    subroutine interaction_set_kinematics_sf_user (int, x, r, data)
        type(interaction_t), intent(inout) :: int
        real(default), dimension(:), intent(out) :: x
        real(default), dimension(:), intent(in) :: r
        type(sf_user_data_t), intent(in) :: data
        type(vector4_t), dimension(data%n_in) :: p_in
        type(vector4_t), dimension(data%n_out) :: p_out
        type(c_prt_t), dimension(data%n_in) :: prt_in
        type(c_prt_t), dimension(data%n_out) :: prt_out
        real(c_double), dimension(data%n_var) :: xval
        call interaction_get_momenta_sub (int, p_in, outgoing=.false.)
        prt_in = vector4_to_c_prt (p_in)
        prt_in%type = PRT_INCOMING
        call data%kinematics (prt_in, real (r, c_double), prt_out, xval)
        x = xval
        p_out = vector4_from_c_prt (prt_out)
        call interaction_set_momenta (int, p_out, outgoing=.true.)
    end subroutine interaction_set_kinematics_sf_user

```

The matrix-element evaluation may require a scale parameter, therefore this routine is separate. We take the variables computed above together with the event energy scale and call the user function that computes the matrix elements.

```

<SF User: public>+≡
    public :: interaction_apply_sf_user

<SF User: procedures>+≡
    subroutine interaction_apply_sf_user (int, scale, x, data)
        type(interaction_t), intent(inout) :: int
        real(default), intent(in) :: scale
        real(default), dimension(:), intent(in) :: x
        type(sf_user_data_t), intent(in) :: data
        real(c_double), dimension(data%n_states) :: fval
        complex(default), dimension(data%n_states) :: fc
        call data%evaluate (real (x, c_double), real (scale, c_double), fval)
        fc = fval
        call interaction_set_matrix_element (int, fc)
    end subroutine interaction_apply_sf_user

```

10.12 Spectra and structure functions: wrapper

In this module, we collect, for each type of spectrum or structure function, the data, initialization routines, and applications.

```

<strfun.f90>≡
    <File header>

```



```

module strfun

  <Use kinds>
  <Use strings>
  <Use file utils>
  use diagnostics !NODEP!
  use lorentz !NODEP!
  use models
  use quantum_numbers
  use interactions
  use evaluators
  use beams
  use sf_isr
  use sf_epa
  use sf_ewa
  use sf_circe1
  use sf_circe2
  use sf_escan
  use sf_beam_events
  use sf_lhapdf
  use sf_pdf_builtin
  use sf_user

  <Standard module head>

  <Strfun: public>

  <Strfun: parameters>

  <Strfun: types>

  <Strfun: interfaces>

  contains

  <Strfun: procedures>

end module strfun

```

10.12.1 The structure functions type

Definition

This contains the specific structure function data, much of which depends on the type. An extensible type would be appropriate. As long as this is not available in general, we emulate it by allocating the requested data explicitly.

<Strfun: types>≡

```

type :: strfun_t
  private
  integer :: type = STRF_NONE
  type(string_t) :: name
  type(interaction_t) :: int
  type(lhapdf_data_t), dimension(:), allocatable :: lhpdf_data
  type(pdf_builtin_data_t), dimension(:), allocatable :: pdf_builtin_data

```

```

type(isr_data_t), dimension(:), allocatable :: isr_data
type(epa_data_t), dimension(:), allocatable :: epa_data
type(ewa_data_t), dimension(:), allocatable :: ewa_data
type(circe1_data_t), dimension(:), allocatable :: circe1_data
type(circe2_data_t), dimension(:), allocatable :: circe2_data
type(escan_data_t), dimension(:), allocatable :: escan_data
type(beam_events_data_t), dimension(:), allocatable :: beam_events_data
type(sf_user_data_t), dimension(:), allocatable :: user_data
real(default) :: x = 0, f = 1, s = 0
real(default), dimension(:), allocatable :: user_xval
real(default) :: scale = 0
end type strfun_t

```

The list of structure function codes:

```

<Strfun: parameters>≡
integer, parameter, public :: STRF_NONE = 0
integer, parameter, public :: STRF_LHAPDF = 1, STRF_ISR = 2, &
    STRF_EPA = 3, STRF_EWA = 4, STRF_CIRCE1 = 5, STRF_CIRCE2 = 6, &
    STRF_ESCAN = 7, STRF_BEVT = 8, STRF_PDF_BUILTIN = 9
integer, parameter, public :: STRF_USER = 99

```

The initializer assigns specific data and tags the interaction. The data block(s) have to be known already.

```

<Strfun: interfaces>≡
interface strfun_init
module procedure strfun_init_lhapdf
module procedure strfun_init_isr
module procedure strfun_init_epa
module procedure strfun_init_ewa
module procedure strfun_init_circe1
module procedure strfun_init_circe2
module procedure strfun_init_escan
module procedure strfun_init_beam_events
module procedure strfun_init_pdf_builtin
module procedure strfun_init_user
end interface

```

```

<Strfun: procedures>≡
subroutine strfun_init_lhapdf (strfun, lhpdf_data)
type(strfun_t), intent(out) :: strfun
type(lhpdf_data_t), intent(in) :: lhpdf_data
strfun%type = STRF_LHAPDF
strfun%name = "LHAPDF"
allocate (strfun%lhpdf_data (1))
strfun%lhpdf_data = lhpdf_data
call interaction_init_lhapdf (strfun%int, lhpdf_data)
end subroutine strfun_init_lhapdf

subroutine strfun_init_pdf_builtin (strfun, pdf_builtin_data)
type(strfun_t), intent(out) :: strfun
type(pdf_builtin_data_t), intent(in) :: pdf_builtin_data
strfun%type = STRF_PDF_BUILTIN

```

```

    strfun%name = "builtin PDF: " // pdf_builtin_get_name (pdf_builtin_data)
    allocate (strfun%pdf_builtin_data (1))
    strfun%pdf_builtin_data = pdf_builtin_data
    call interaction_init_pdf_builtin (strfun%int, pdf_builtin_data)
end subroutine strfun_init_pdf_builtin

subroutine strfun_init_isr (strfun, isr_data)
    type(strfun_t), intent(out) :: strfun
    type(isr_data_t), intent(in) :: isr_data
    strfun%type = STRF_ISR
    strfun%name = "ISR"
    allocate (strfun%isr_data (1))
    strfun%isr_data = isr_data
    call interaction_init_isr (strfun%int, isr_data)
end subroutine strfun_init_isr

subroutine strfun_init_epa (strfun, epa_data)
    type(strfun_t), intent(out) :: strfun
    type(epa_data_t), intent(in) :: epa_data
    strfun%type = STRF_EPA
    strfun%name = "EPA"
    allocate (strfun%epa_data (1))
    strfun%epa_data = epa_data
    call interaction_init_epa (strfun%int, epa_data)
end subroutine strfun_init_epa

subroutine strfun_init_ewa (strfun, ewa_data, id)
    type(strfun_t), intent(out) :: strfun
    type(ewa_data_t), intent(inout) :: ewa_data
    integer, intent(in) :: id
    strfun%type = STRF_EWA
    strfun%name = "EWA"
    allocate (strfun%ewa_data (1))
    call ewa_set_id (ewa_data, id)
    strfun%ewa_data = ewa_data
    call interaction_init_ewa (strfun%int, ewa_data)
end subroutine strfun_init_ewa

subroutine strfun_init_circe1 (strfun, circe1_data)
    type(strfun_t), intent(out) :: strfun
    type(circe1_data_t), intent(in) :: circe1_data
    strfun%type = STRF_CIRCE1
    strfun%name = "CIRCE1"
    allocate (strfun%circe1_data (1))
    strfun%circe1_data = circe1_data
    call interaction_init_circe1 (strfun%int, circe1_data)
end subroutine strfun_init_circe1

subroutine strfun_init_circe2 (strfun, circe2_data)
    type(strfun_t), intent(out) :: strfun
    type(circe2_data_t), intent(in) :: circe2_data
    strfun%type = STRF_CIRCE2
    strfun%name = "CIRCE2"
    allocate (strfun%circe2_data (1))

```

```

    strfun%circe2_data = circe2_data
    call interaction_init_circe2 (strfun%int, circe2_data)
end subroutine strfun_init_circe2

subroutine strfun_init_escan (strfun, escan_data)
    type(strfun_t), intent(out) :: strfun
    type(escan_data_t), intent(in) :: escan_data
    strfun%type = STRF_ESCAN
    strfun%name = "Energy scan"
    allocate (strfun%escan_data (1))
    strfun%escan_data = escan_data
    call interaction_init_escan (strfun%int, escan_data)
end subroutine strfun_init_escan

subroutine strfun_init_beam_events (strfun, beam_events_data)
    type(strfun_t), intent(out) :: strfun
    type(beam_events_data_t), intent(in) :: beam_events_data
    strfun%type = STRF_BEVT
    strfun%name = "Beam events"
    allocate (strfun%beam_events_data (1))
    strfun%beam_events_data = beam_events_data
    call interaction_init_beam_events (strfun%int, beam_events_data)
end subroutine strfun_init_beam_events

subroutine strfun_init_user (strfun, user_data)
    type(strfun_t), intent(out) :: strfun
    type(sf_user_data_t), intent(in) :: user_data
    strfun%type = STRF_USER
    strfun%name = "User structure function: " &
        // sf_user_data_get_name (user_data)
    allocate (strfun%user_data (1))
    strfun%user_data = user_data
    call interaction_init_sf_user (strfun%int, user_data)
    allocate (strfun%user_xval (sf_user_data_get_n_var (user_data)))
end subroutine strfun_init_user

```

Finalizer for the contained interaction. The presence of file operations forbid the `elemental` attribute, therefore the interface.

```

<Strfun: interfaces>+≡
    interface strfun_final
        module procedure strfun_final0
        module procedure strfun_final1
    end interface

<Strfun: procedures>+≡
    subroutine strfun_final1 (strfun)
        type(strfun_t), dimension(:), intent(inout) :: strfun
        integer :: i
        do i = 1, size (strfun)
            call strfun_final0 (strfun(i))
        end do
    end subroutine strfun_final1

    subroutine strfun_final0 (strfun)

```

```

type(strfun_t), intent(inout) :: strfun
select case (strfun%type)
case (STRF_ISR)
    deallocate (strfun%isr_data)
case (STRF_EPA)
    deallocate (strfun%epa_data)
case (STRF_EWA)
    deallocate (strfun%ewa_data)
case (STRF_CIRCE1)
    deallocate (strfun%circe1_data)
case (STRF_CIRCE2)
    deallocate (strfun%circe2_data)
case (STRF_ESCAN)
    deallocate (strfun%escan_data)
case (STRF_BEVT)
    call beam_events_data_close (strfun%beam_events_data(1))
    deallocate (strfun%beam_events_data)
case (STRF_LHAPDF)
    deallocate (strfun%lhpdf_data)
case (STRF_PDF_BUILTIN)
    call pdf_builtin_final (strfun%pdf_builtin_data(1))
    deallocate (strfun%pdf_builtin_data)
case (STRF_USER)
    deallocate (strfun%user_data)
    deallocate (strfun%user_xval)
end select
call interaction_final (strfun%int)
strfun%type = STRF_NONE
end subroutine strfun_final0

```

I/O

(Strfun: procedures) +=

```

subroutine strfun_write (strfun, unit, verbose, show_momentum_sum, show_mass)
type(strfun_t), intent(in) :: strfun
integer, intent(in), optional :: unit
logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
integer :: u
u = output_unit (unit); if (u < 0) return
if (strfun%type /= STRF_NONE) then
    write (u, *) char (strfun_get_name (strfun)) // " setup:"
    select case (strfun%type)
    case (STRF_LHAPDF)
        call lhpdf_data_write (strfun%lhpdf_data(1), u)
        write (u, *) "LHAPDF event data:"
        write (u, *) "  x      =", strfun%x
        write (u, *) "  f      =", strfun%f
        write (u, *) "  scale =", strfun%scale
        write (u, *) "  p2     =", strfun%s
    case (STRF_PDF_BUILTIN)
        call pdf_builtin_data_write (strfun%pdf_builtin_data(1), u)
        write (u, *) "PDF event data:"
        write (u, *) "  x      =", strfun%x

```

```

        write (u, *) " f      =", strfun%f
        write (u, *) " scale =", strfun%scale
        write (u, *) " p2     =", strfun%s
    case (STRF_ISR)
        call isr_data_write (strfun%isr_data(1), u)
    case (STRF_EPA)
        call epa_data_write (strfun%epa_data(1), u)
    case (STRF_EWA)
        call ewa_data_write (strfun%ewa_data(1), u)
    case (STRF_CIRCE1)
        call circe1_data_write (strfun%circe1_data(1), u)
    case (STRF_CIRCE2)
        call circe2_data_write (strfun%circe2_data(1), u)
    case (STRF_ESCAN)
        call escan_data_write (strfun%escan_data(1), u)
    case (STRF_BEVT)
        call beam_events_data_write (strfun%beam_events_data(1), u)
    case (STRF_USER)
        call sf_user_data_write (strfun%user_data(1), u)
        write (u, *) "User event data:"
        if (allocated (strfun%user_xval)) then
            write (u, *) " x      =", strfun%user_xval
        else
            write (u, *) " x      = [not allocated]"
        end if
        write (u, *) " scale =", strfun%scale
    end select
    call interaction_write &
        (strfun%int, unit, verbose, show_momentum_sum, show_mass)
else
    write (u, *) "Structure function setup: [empty]"
end if
end subroutine strfun_write

```

Retrieve data

```

<Strfun: procedures>+≡
function strfun_get_name (strfun) result (name)
    type(string_t) :: name
    type(strfun_t), intent(in) :: strfun
    name = strfun%name
end function strfun_get_name

```

```

<Strfun: procedures>+≡
function strfun_get_type (strfun) result (type)
    integer :: type
    type(strfun_t), intent(in) :: strfun
    type = strfun%type
end function strfun_get_type

```

Apply structure function

Set kinematics using input random numbers. For some structure functions, we can already compute matrix elements.

The `no_map` flag implies that all preset mappings and generator modes should be switched off, and the structure functions should be probed directly.

(Strfun: procedures)+≡

```
subroutine strfun_set_kinematics (strfun, r, no_map)
  type(strfun_t), intent(inout) :: strfun
  real(default), dimension(:), intent(in) :: r
  logical, intent(in) :: no_map
  select case (strfun%type)
  case (STRF_LHAPDF)
    call interaction_set_kinematics_lhapdf (strfun%int, &
      strfun%x, strfun%f, strfun%s, r(1), strfun%lhpdf_data(1))
  case (STRF_PDF_BUILTIN)
    call interaction_set_kinematics_pdf_builtin (strfun%int, &
      strfun%x, strfun%f, strfun%s, r(1), strfun%pdf_builtin_data(1))
  case (STRF_ISR)
    call interaction_apply_isr (strfun%int, r, strfun%isr_data(1), no_map)
  case (STRF_EPA)
    call interaction_apply_epa (strfun%int, r, strfun%epa_data, no_map)
  case (STRF_EWA)
    call interaction_apply_ewa (strfun%int, r, strfun%ewa_data, no_map)
  case (STRF_CIRCE1)
    call interaction_apply_circe1 &
      (strfun%int, r, strfun%circe1_data(1), no_map)
  case (STRF_CIRCE2)
    call interaction_apply_circe2 &
      (strfun%int, r, strfun%circe2_data(1), no_map)
  case (STRF_ESCAN)
    call interaction_apply_escan &
      (strfun%int, r, strfun%escan_data(1))
  case (STRF_BEVT)
    call interaction_apply_beam_events &
      (strfun%int, strfun%beam_events_data(1))
  case (STRF_USER)
    call interaction_set_kinematics_sf_user (strfun%int, &
      strfun%user_xval, r, strfun%user_data(1))
  end select
end subroutine strfun_set_kinematics
```

Set values where they depend on a separate energy scale:

(Strfun: procedures)+≡

```
subroutine strfun_apply (strfun, scale)
  type(strfun_t), intent(inout) :: strfun
  real(default), intent(in) :: scale
  strfun%scale = scale
  select case (strfun%type)
  case (STRF_LHAPDF)
    call interaction_apply_lhapdf (strfun%int, scale, &
      strfun%x, strfun%f, strfun%s, strfun%lhpdf_data(1))
  case (STRF_PDF_BUILTIN)
```

```

        call interaction_apply_pdf_builtin (strfun%int, scale, &
            strfun%x, strfun%f, strfun%s, strfun%pdf_builtin_data(1))
    case (STRF_USER)
        call interaction_apply_sf_user (strfun%int, scale, &
            strfun%user_xval, strfun%user_data(1))
    end select
end subroutine strfun_apply

```

10.12.2 Mappings

Definition

Mappings for single structure functions may be defined in the individual sections, but pairwise mappings belong here. We define a mapping type that applies to an array of x parameters identified by their indices. The individual mapping types are identified by a `type` parameter. A mapping may depend on a set on real parameters.

```

<Strfun: parameters>+≡
    integer, parameter, public :: SFM_NONE = 0
    integer, parameter, public :: SFM_PAIR = 1
    integer, parameter, public :: SFM_PAIR_RESONANCE = 2

<Strfun: types>+≡
    type :: strfun_mapping_t
    private
    integer, dimension(:), allocatable :: index
    integer :: type = SFM_NONE
    real(default) :: p = 0
    real(default) :: m2 = 0, mg = 0, s = 0
    real(default) :: a1 = 0, a2 = 0, a3 = 0
end type strfun_mapping_t

```

Initialization:

```

<Strfun: procedures>+≡
    subroutine strfun_mapping_init (sf_mapping, index, type, par)
        type(strfun_mapping_t), intent(out) :: sf_mapping
        integer, dimension(:), intent(in) :: index
        integer, intent(in) :: type
        real(default), dimension(:), intent(in) :: par
        real(default) :: s, m2, mg
        allocate (sf_mapping%index (size (index)))
        sf_mapping%index = index
        sf_mapping%type = type
        select case (type)
        case (SFM_PAIR)
            sf_mapping%p = par(1)
        case (SFM_PAIR_RESONANCE)
            s = par(1)**2
            m2 = par(2)**2
            mg = par(2) * par(3)
            sf_mapping%s = s
            sf_mapping%m2 = m2

```



```

        sf_mapping%mg = mg
        sf_mapping%a1 = atan (- m2 / mg)
        sf_mapping%a2 = atan ((s - m2) / mg)
        sf_mapping%a3 = (sf_mapping%a2 - sf_mapping%a1) * mg / s
    end select
end subroutine strfun_mapping_init

```

Output

(Strfun: procedures)+≡

```

subroutine strfun_mapping_write (sf_mapping, unit)
    type(strfun_mapping_t), intent(in) :: sf_mapping
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write (u, "(1x,A)", advance="no") "Strfun mapping for indices: "
    write (u, "(10(1x,I0))") sf_mapping%index
    write (u, "(1x,A,1x,I0)") "mapping type =", sf_mapping%type
    write (u, "(1x,A)", advance="no") "mapping pars ="
    select case (sf_mapping%type)
    case (SFM_NONE)
        write (u, *) "[none]"
    case (SFM_PAIR)
        write (u, *) sf_mapping%p
    case (SFM_PAIR_RESONANCE)
        write (u, *) sf_mapping%s, sf_mapping%m2, sf_mapping%mg
    end select
end subroutine strfun_mapping_write

```

Evaluation

(Strfun: procedures)+≡

```

subroutine strfun_mapping_apply (sf_mapping, x, factor)
    type(strfun_mapping_t), intent(in) :: sf_mapping
    real(default), dimension(:), intent(inout) :: x
    real(default), intent(out) :: factor
    real(default) :: f1, f2
    real(default), dimension(2) :: x2
    select case (sf_mapping%type)
    case (SFM_PAIR)
        x2 = x(sf_mapping%index)
        call map_unit_square (x2, factor, sf_mapping%p)
        x(sf_mapping%index) = x2
    case (SFM_PAIR_RESONANCE)
        x2 = x(sf_mapping%index)
        call map_resonance (x2(1), f2, &
            sf_mapping%s, sf_mapping%m2, sf_mapping%mg, &
            sf_mapping%a1, sf_mapping%a2, sf_mapping%a3)
        call map_unit_square (x2, f1)
        x(sf_mapping%index) = x2
        factor = f1 * f2
    case default
        factor = 1
    end select
end subroutine strfun_mapping_apply

```

```

end select
end subroutine strfun_mapping_apply

subroutine strfun_mapping_apply_inverse (sf_mapping, x, factor)
  type(strfun_mapping_t), intent(in) :: sf_mapping
  real(default), dimension(:), intent(inout) :: x
  real(default), intent(out) :: factor
  real(default) :: f1, f2
  real(default), dimension(2) :: x2
  select case (sf_mapping%type)
  case (SFM_PAIR)
    x2 = x(sf_mapping%index)
    call map_unit_square_inverse (x2, factor, sf_mapping%p)
    x(sf_mapping%index) = x2
  case (SFM_PAIR_RESONANCE)
    x2 = x(sf_mapping%index)
    call map_unit_square_inverse (x2, f1)
    call map_resonance_inverse (x2(1), f2, &
      sf_mapping%s, sf_mapping%m2, sf_mapping%mg, &
      sf_mapping%a1, sf_mapping%a2, sf_mapping%a3)
    x(sf_mapping%index) = x2
    factor = f1 * f2
  case default
    factor = 1
  end select
end subroutine strfun_mapping_apply_inverse

```

This mapping of the unit square is appropriate in particular for structure functions which are concentrated at the lower end. Instead of a rectangular grid, one set of grid lines corresponds to constant parton c.m. energy. The other set is chosen such that the jacobian is only mildly singular ($\ln x$ which is zero at $x = 1$), corresponding to an initial concentration of sampling points at the maximum energy. If `power` is greater than one (the default), points are also concentrated at the lower end.

(Strfun: procedures)+≡

```

subroutine map_unit_square (x, factor, power)
  real(kind=default), dimension(2), intent(inout) :: x
  real(kind=default), intent(out) :: factor
  real(kind=default), intent(in), optional :: power
  real(kind=default) :: xx, yy
  factor = 1
  xx = x(1)
  yy = x(2)
  if (present(power)) then
    if (x(1) > 0 .and. power > 1) then
      xx = x(1)**power
      factor = factor * power * xx / x(1)
    end if
  end if
  if (xx /= 0) then
    x(1) = xx ** yy
    x(2) = xx / x(1)
    factor = factor * abs (log (xx))
  end if

```

```

else
  x = 0
end if
end subroutine map_unit_square

```

This is the inverse mapping.

```

(Strfun: procedures)+≡
subroutine map_unit_square_inverse (x, factor, power)
  real(kind=default), dimension(2), intent(inout) :: x
  real(kind=default), intent(out) :: factor
  real(kind=default), intent(in), optional :: power
  real(kind=default) :: lg, xx, yy
  factor = 1
  xx = x(1) * x(2)
  if (xx /= 0) then
    lg = log (xx)
    yy = log (x(1)) / lg
    x(2) = yy
    factor = factor * abs (lg)
    if (present(power)) then
      x(1) = xx**(1._default/power)
      factor = factor * power * xx / x(1)
    else
      x(1) = xx
    end if
  else
    x = 0
  end if
end subroutine map_unit_square_inverse

```

This is the usual mapping of a Lorentz peak. Since the x range maps the energy range $0 \dots \sqrt{s}$ to $0 \dots 1$, the position of the peak is m^2/s , the width is given by $m\Gamma/s$.

```

(Strfun: procedures)+≡
subroutine map_resonance (x, factor, s, m2, mg, a1, a2, a3)
  real(default), intent(inout) :: x
  real(default), intent(out) :: factor
  real(default), intent(in) :: s, m2, mg, a1, a2, a3
  real(default) :: t, z
  z = (1 - x) * a1 + x * a2
  t = tan (z)
  x = (m2 + t * mg) / s
  factor = a3 * (1 + t**2)
end subroutine map_resonance

```

```

(Strfun: procedures)+≡
subroutine map_resonance_inverse (x, factor, s, m2, mg, a1, a2, a3)
  real(default), intent(inout) :: x
  real(default), intent(out) :: factor
  real(default), intent(in) :: s, m2, mg, a1, a2, a3
  real(default) :: t
  t = (x * s - m2) / mg

```

```

      x = (atan (t) - a1) / (a2 - a1)
      factor = a3 * (1 + t**2)
end subroutine map_resonance_inverse

```

10.12.3 Structure function chains

Definition

The structure function chain contains an array of structure functions, where each one has one or more free parameters. For each structure function there is an interaction, an image of the interaction within the **strfun** object, which is needed when quantum numbers are reduced. Furthermore, an array of evaluators which cumulatively multiply the structure functions. The last evaluator is connected to the hard matrix element.

The **last_strfun** and **out_index** index (pairs) identify, for each beam, the last structure function and the outgoing particle. The **coll_index** (pair) identifies the outgoing particles in the last evaluator.

For a decay, this structure is also used, but normally there are no structure functions besides the “beam” object.

```

⟨Strfun: public⟩≡
  public :: strfun_chain_t

⟨Strfun: types⟩+≡
  type :: strfun_chain_t
  private
    type(beam_t) :: beam
    integer :: n_strfun = 0
    logical :: multichannel = .false.
    integer :: n_mapping = 0
    type(strfun_t), dimension(:), allocatable :: strfun
    type(strfun_mapping_t), dimension(:,:), allocatable :: sf_mapping
    real(default) :: mapping_factor = 0
    integer :: n_parameters_tot = 0
    integer, dimension(:), allocatable :: n_parameters
    type(evaluator_t), dimension(:), allocatable :: eval
    integer, dimension(:), allocatable :: last_strfun
    integer, dimension(:), allocatable :: out_index
    integer, dimension(:), allocatable :: coll_index
  end type strfun_chain_t

⟨Strfun: public⟩+≡
  public :: strfun_chain_init

⟨Strfun: procedures⟩+≡
  subroutine strfun_chain_init (sfchain, beam_data, n_strfun)
    type(strfun_chain_t), intent(out) :: sfchain
    type(beam_data_t), intent(in), target :: beam_data
    integer, intent(in) :: n_strfun
    integer :: i
    sfchain%n_strfun = n_strfun
    allocate (sfchain%strfun (n_strfun))
    allocate (sfchain%n_parameters (n_strfun))

```

```

sfchain%n_parameters = 0
allocate (sfchain%eval (n_strfun))
call beam_init (sfchain%beam, beam_data)
allocate (sfchain%last_strfun (beam_data%n))
allocate (sfchain%out_index (beam_data%n))
allocate (sfchain%coll_index (beam_data%n))
sfchain%last_strfun = 0
do i = 1, size (sfchain%out_index)
    sfchain%out_index(i) = i
    sfchain%coll_index(i) = i
end do
end subroutine strfun_chain_init

```

This is a separate initialization routine for the structure-function mappings.

```

<Strfun: public>+≡
    public :: strfun_chain_allocate_mappings

<Strfun: procedures>+≡
    subroutine strfun_chain_allocate_mappings &
        (sfchain, multichannel, n_mapping, n_channel)
        type(strfun_chain_t), intent(inout) :: sfchain
        logical, intent(in) :: multichannel
        integer, intent(in) :: n_mapping, n_channel
        sfchain%multichannel = multichannel
        sfchain%n_mapping = n_mapping
        allocate (sfchain%sf_mapping (n_mapping, n_channel))
    end subroutine strfun_chain_allocate_mappings

```

Set beam momenta directly without changing anything else.

```

<Strfun: public>+≡
    public :: strfun_chain_set_beam_momenta

<Strfun: procedures>+≡
    subroutine strfun_chain_set_beam_momenta (sfchain, p)
        type(strfun_chain_t), intent(inout) :: sfchain
        type(vector4_t), dimension(:), intent(in) :: p
        call beam_set_momenta (sfchain%beam, p)
    end subroutine strfun_chain_set_beam_momenta

```

```

<Strfun: public>+≡
    public :: strfun_chain_final

<Strfun: procedures>+≡
    subroutine strfun_chain_final (sfchain)
        type(strfun_chain_t), intent(inout) :: sfchain
        call beam_final (sfchain%beam)
        if (allocated (sfchain%strfun)) call strfun_final (sfchain%strfun)
        if (allocated (sfchain%eval)) call evaluator_final (sfchain%eval)
    end subroutine strfun_chain_final

```

I/O

```

<Strfun: public>+≡
    public :: strfun_chain_write

```

<Strfun: procedures>+≡

```

subroutine strfun_chain_write &
    (sfchain, unit, verbose, show_momentum_sum, show_mass)
    type(strfun_chain_t), intent(in) :: sfchain
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
    integer :: u, i, ch
    logical :: verb
    verb = .false.; if (present (verbose)) verb = verbose
    u = output_unit (unit); if (u < 0) return
    write (u, *) "Structure function chain:"
    write (u, *)
    call beam_write (sfchain%beam, unit, verbose, show_momentum_sum, show_mass)
    if (allocated (sfchain%strfun)) then
        do i = 1, size (sfchain%strfun)
            write (u, *)
            call strfun_write &
                (sfchain%strfun(i), unit, verbose, show_momentum_sum, show_mass)
            write (u, *) "number of parameters = ", sfchain%n_parameters(i)
        end do
    end if
    if (allocated (sfchain%sf_mapping)) then
        if (sfchain%multichannel) then
            do ch = 1, size (sfchain%sf_mapping, 2)
                write (u, *)
                write (u, *) "Mappings for channel #", ch
                do i = 1, size (sfchain%sf_mapping, 1)
                    call strfun_mapping_write (sfchain%sf_mapping(i, ch), unit)
                end do
            end do
        else
            do i = 1, size (sfchain%sf_mapping, 1)
                write (u, *)
                call strfun_mapping_write (sfchain%sf_mapping(i,1), unit)
            end do
        end if
    end if
    if (allocated (sfchain%eval)) then
        write (u, *)
        write (u, *) "Evaluators:"
        do i = 1, size (sfchain%eval)
            call evaluator_write &
                (sfchain%eval(i), unit, verbose, show_momentum_sum, show_mass)
        end do
    end if
    write (u, *)
    write (u, *) "Total number of parameters      = ", &
        sfchain%n_parameters_tot
    write (u, "(1x,A)", advance="no") "Last structure function (index) = "
    if (allocated (sfchain%last_strfun)) then
        write (u, *) sfchain%last_strfun
    else
        write (u, *) "[not allocated]"
    end if
end if

```

```

write (u, "(1x,A)", advance="no") "Outgoing particles (index)      = "
if (allocated (sfchain%out_index)) then
  write (u, *) sfchain%out_index
else
  write (u, *) "[not allocated]"
end if
write (u, "(1x,A)", advance="no") "Colliding particles (index)    = "
if (allocated (sfchain%coll_index)) then
  write (u, *) sfchain%coll_index
else
  write (u, *) "[not allocated]"
end if
end subroutine strfun_chain_write

```

Defined assignment

Deep copy of all components.

```

<Strfun: public>+≡
  public :: assignment(=)

<Strfun: interfaces>+≡
  interface assignment(=)
    module procedure strfun_chain_assign
  end interface

<Strfun: procedures>+≡
  subroutine strfun_chain_assign (sfchain_out, sfchain_in)
    type(strfun_chain_t), intent(out) :: sfchain_out
    type(strfun_chain_t), intent(in)  :: sfchain_in
    sfchain_out%beam = sfchain_in%beam
    sfchain_out%n_strfun = sfchain_in%n_strfun
    sfchain_out%multichannel = sfchain_in%multichannel
    sfchain_out%n_mapping = sfchain_in%n_mapping
    if (allocated (sfchain_in%strfun)) then
      allocate (sfchain_out%strfun (size (sfchain_in%strfun)))
      sfchain_out%strfun = sfchain_in%strfun
    end if
    if (allocated (sfchain_in%sf_mapping)) then
      allocate (sfchain_out%sf_mapping &
        (size (sfchain_in%sf_mapping, 1), size (sfchain_in%sf_mapping, 2)))
      sfchain_out%sf_mapping = sfchain_in%sf_mapping
    end if
    sfchain_out%mapping_factor = sfchain_in%mapping_factor
    sfchain_out%n_parameters_tot = sfchain_in%n_parameters_tot
    if (allocated (sfchain_in%n_parameters)) then
      allocate (sfchain_out%n_parameters (size (sfchain_in%n_parameters)))
      sfchain_out%n_parameters = sfchain_in%n_parameters
    end if
    if (allocated (sfchain_in%eval)) then
      allocate (sfchain_out%eval (size (sfchain_in%eval)))
      sfchain_out%eval = sfchain_in%eval
    end if
    if (allocated (sfchain_in%last_strfun)) then

```

```

        allocate (sfchain_out%last_strfun (size (sfchain_in%last_strfun)))
        sfchain_out%last_strfun = sfchain_in%last_strfun
    end if
    if (allocated (sfchain_in%out_index)) then
        allocate (sfchain_out%out_index (size (sfchain_in%out_index)))
        sfchain_out%out_index = sfchain_in%out_index
    end if
    if (allocated (sfchain_in%coll_index)) then
        allocate (sfchain_out%coll_index (size (sfchain_in%coll_index)))
        sfchain_out%coll_index = sfchain_in%coll_index
    end if
end subroutine strfun_chain_assign

```

Accessing contents

Return the type of PDF used. So far, we only return a type if there are exactly two structure functions and they are both the same.

```

<Strfun: public>+≡
    public :: strfun_chain_get_strfun_type

<Strfun: procedures>+≡
    function strfun_chain_get_strfun_type(sfchain) result(type)
        type(strfun_chain_t), intent(in) :: sfchain
        integer :: type

        if(size(sfchain%strfun).eq.2) then
            if(sfchain%strfun(1)%type .eq. sfchain%strfun(2)%type) then
                type = sfchain%strfun(1)%type
            else
                type = STRF_NONE
            end if
        else
            type = STRF_NONE
        end if
    end function strfun_chain_get_strfun_type

```

Return the number of the member of the PDF used

```

<Strfun: public>+≡
    public :: strfun_chain_get_strfun_set

<Strfun: procedures>+≡
    function strfun_chain_get_strfun_set(sfchain) result(set)
        type(strfun_chain_t), intent(in) :: sfchain
        integer :: set

        set = 0
        if(size(sfchain%strfun).eq.2) then
            if(sfchain%strfun(1)%type .eq. sfchain%strfun(2)%type) then
                if(sfchain%strfun(1)%type .eq. STRF_LHAPDF) then
                    set = lhpdf_data_get_set(sfchain%strfun(1)%lhpdf_data(1))
                else if(sfchain%strfun(1)%type .eq. STRF_PDF_BUILTIN) then
                    set = pdf_builtin_get_id(sfchain%strfun(1)%pdf_builtin_data(1))
                end if
            end if
        end if
    end function

```



```

        end if
    end function strfun_chain_get_strfun_set

```

The number of active structure functions.

```

<Strfun: public>+≡
    public :: strfun_chain_get_n_strfun

<Strfun: procedures>+≡
    function strfun_chain_get_n_strfun (sfchain) result (n)
        integer :: n
        type(strfun_chain_t), intent(in) :: sfchain
        n = sfchain%n_strfun
    end function strfun_chain_get_n_strfun

```

The number of free parameters (x values) needed for evaluating the structure functions.

```

<Strfun: public>+≡
    public :: strfun_chain_get_n_parameters_tot

<Strfun: procedures>+≡
    function strfun_chain_get_n_parameters_tot (sfchain) result (n)
        integer :: n
        type(strfun_chain_t), intent(in) :: sfchain
        n = sfchain%n_parameters_tot
    end function strfun_chain_get_n_parameters_tot

```

The number of virtual particles in the structure function evaluators. These are the beam particles plus all particles that do not appear as outgoing.

```

<Strfun: public>+≡
    public :: strfun_chain_get_n_vir

<Strfun: procedures>+≡
    function strfun_chain_get_n_vir (sfchain) result (n)
        integer :: n
        type(strfun_chain_t), intent(in) :: sfchain
        if (sfchain%n_strfun /= 0) then
            n = evaluator_get_n_vir (sfchain%eval(sfchain%n_strfun))
        else
            n = 0
        end if
    end function strfun_chain_get_n_vir

```

Tell if the structure-function mappings should be applied to individual phase-space channels, or globally.

```

<Strfun: public>+≡
    public :: strfun_chain_multichannel_enabled

<Strfun: procedures>+≡
    function strfun_chain_multichannel_enabled (sfchain) result (flag)
        logical :: flag
        type(strfun_chain_t), intent(in) :: sfchain
        flag = sfchain%multichannel
    end function strfun_chain_multichannel_enabled

```

Return any extra factor resulting from explicit mappings of the x parameters.

```

(Strfun: public)+≡
    public :: strfun_chain_get_mapping_factor

(Strfun: procedures)+≡
    function strfun_chain_get_mapping_factor (sfchain) result (f)
        real(default) :: f
        type(strfun_chain_t), intent(in) :: sfchain
        f = sfchain%mapping_factor
    end function strfun_chain_get_mapping_factor

```

For pseudo-structure functions that actually are an external generator, the integration region must not be mapped and stay rigid. This function returns an array which tells, for each integration parameter, whether the corresponding integration dimension is rigid.

```

(Strfun: public)+≡
    public :: strfun_chain_dimension_is_rigid

(Strfun: procedures)+≡
    function strfun_chain_dimension_is_rigid (sfchain) result (rigid)
        logical, dimension(:), allocatable :: rigid
        type(strfun_chain_t), intent(in) :: sfchain
        integer :: i, j, k
        allocate (rigid (sfchain%n_parameters_tot))
        k = 0
        do i = 1, size (sfchain%n_parameters)
            do j = 1, sfchain%n_parameters(i)
                k = k + 1
                select case (sfchain%strfun(i)%type)
                case default
                    rigid(k) = .false.
                end select
            end do
        end do
    end function strfun_chain_dimension_is_rigid

```

Return the indices of the colliding particles.

```

(Strfun: public)+≡
    public :: strfun_chain_get_colliding_particles

(Strfun: procedures)+≡
    function strfun_chain_get_colliding_particles (sfchain) result (index)
        integer, dimension(:), allocatable :: index
        type(strfun_chain_t), intent(in) :: sfchain
        allocate (index (size (sfchain%coll_index)))
        index = sfchain%coll_index
    end function strfun_chain_get_colliding_particles

```

Return the quantum-numbers mask for the colliding particles. This is extracted from the last evaluator in the chain.

```

(Strfun: public)+≡
    public :: strfun_chain_get_colliding_particles_mask

```

```

(Strfun: procedures)+≡
function strfun_chain_get_colliding_particles_mask (sfchain) result (mask)
  type(quantum_numbers_mask_t), dimension(:), allocatable :: mask
  type(strfun_chain_t), intent(in), target :: sfchain
  integer :: n_strfun
  type(quantum_numbers_mask_t), dimension(:), allocatable :: mask_eval
  allocate (mask (size (sfchain%coll_index)))
  n_strfun = sfchain%n_strfun
  if (n_strfun /= 0) then
    allocate (mask_eval (evaluator_get_n_tot (sfchain%eval(n_strfun))))
    mask_eval = evaluator_get_mask (sfchain%eval(n_strfun))
    mask = mask_eval(sfchain%coll_index)
  else
    mask = interaction_get_mask (beam_get_int_ptr (sfchain%beam))
  end if
end function strfun_chain_get_colliding_particles_mask

```

Return a pointer to the beam interaction.

```

(Strfun: public)+≡
public :: strfun_chain_get_beam_int_ptr

(Strfun: procedures)+≡
function strfun_chain_get_beam_int_ptr (sfchain) result (int)
  type(interaction_t), pointer :: int
  type(strfun_chain_t), intent(in), target :: sfchain
  int => beam_get_int_ptr (sfchain%beam)
end function strfun_chain_get_beam_int_ptr

```

Return a pointer to the last evaluator, which wraps up all structure functions.

```

(Strfun: public)+≡
public :: strfun_chain_get_last_evaluator_ptr

(Strfun: procedures)+≡
function strfun_chain_get_last_evaluator_ptr (sfchain) result (eval)
  type(evaluator_t), pointer :: eval
  type(strfun_chain_t), intent(in), target :: sfchain
  if (sfchain%n_strfun /= 0) then
    eval => sfchain%eval(sfchain%n_strfun)
  else
    eval => null ()
  end if
end function strfun_chain_get_last_evaluator_ptr

```

Setting up structure functions

The index *i* is the overall structure function counter. *line* indicates the beam(s) for which the structure function applies, either 1 or 2, or 0 for both beams.

```

(Strfun: public)+≡
public :: strfun_chain_set_strfun

```

<Strfun: interfaces>+≡

```
interface strfun_chain_set_strfun
  module procedure strfun_chain_set_lhapdf
  module procedure strfun_chain_set_pdf_builtin
  module procedure strfun_chain_set_isr
  module procedure strfun_chain_set_epa
  module procedure strfun_chain_set_ewa
  module procedure strfun_chain_set_circe1
  module procedure strfun_chain_set_circe2
  module procedure strfun_chain_set_escan
  module procedure strfun_chain_set_beam_events
  module procedure strfun_chain_set_user
end interface
```

<Strfun: procedures>+≡

```
subroutine strfun_chain_set_lhapdf &
  (sfchain, i, line, lhpdf_data, n_parameters)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters
  type(lhapdf_data_t), intent(in) :: lhpdf_data
  call strfun_init (sfchain%strfun(i), lhpdf_data)
  sfchain%n_parameters(i) = n_parameters
  call strfun_chain_link (sfchain, i, line, (/1/), (/3/))
end subroutine strfun_chain_set_lhapdf

subroutine strfun_chain_set_pdf_builtin &
  (sfchain, i, line, pdf_builtin_data, n_parameters)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters
  type(pdf_builtin_data_t), intent(in) :: pdf_builtin_data
  call strfun_init (sfchain%strfun(i), pdf_builtin_data)
  sfchain%n_parameters(i) = n_parameters
  call strfun_chain_link (sfchain, i, line, (/1/), (/3/))
end subroutine strfun_chain_set_pdf_builtin

subroutine strfun_chain_set_isr &
  (sfchain, i, line, isr_data, n_parameters)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters
  type(isr_data_t), intent(in) :: isr_data
  call strfun_init (sfchain%strfun(i), isr_data)
  sfchain%n_parameters(i) = n_parameters
  call strfun_chain_link (sfchain, i, line, (/1/), (/3/))
end subroutine strfun_chain_set_isr

subroutine strfun_chain_set_epa &
  (sfchain, i, line, epa_data, n_parameters)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters
  type(epa_data_t), intent(in) :: epa_data
  call strfun_init (sfchain%strfun(i), epa_data)
  sfchain%n_parameters(i) = n_parameters
  call strfun_chain_link (sfchain, i, line, (/1/), (/3/))
end subroutine strfun_chain_set_epa
```

```

subroutine strfun_chain_set_ewa &
  (sfchain, i, line, ewa_data, n_parameters, id)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters, id
  type(ewa_data_t), intent(inout) :: ewa_data
  call strfun_init (sfchain%strfun(i), ewa_data, id)
  sfchain%n_parameters(i) = n_parameters
  call strfun_chain_link (sfchain, i, line, (/1/), (/3/))
end subroutine strfun_chain_set_ewa

subroutine strfun_chain_set_circe1 &
  (sfchain, i, line, circe1_data, n_parameters)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters
  type(circe1_data_t), intent(in) :: circe1_data
  call strfun_init (sfchain%strfun(i), circe1_data)
  sfchain%n_parameters(i) = n_parameters
  call strfun_chain_link (sfchain, i, line, (/1, 2/), (/5, 6/))
end subroutine strfun_chain_set_circe1

subroutine strfun_chain_set_circe2 &
  (sfchain, i, line, circe2_data, n_parameters)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters
  type(circe2_data_t), intent(in) :: circe2_data
  call strfun_init (sfchain%strfun(i), circe2_data)
  sfchain%n_parameters(i) = n_parameters
  call strfun_chain_link (sfchain, i, line, (/1, 2/), (/3, 4/))
end subroutine strfun_chain_set_circe2

subroutine strfun_chain_set_escan &
  (sfchain, i, line, escan_data, n_parameters)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters
  type(escan_data_t), intent(in) :: escan_data
  call strfun_init (sfchain%strfun(i), escan_data)
  sfchain%n_parameters(i) = n_parameters
  if (line == 0) then
    call strfun_chain_link (sfchain, i, line, (/1, 2/), (/3, 4/))
  else
    call strfun_chain_link (sfchain, i, line, (/1/), (/2/))
  end if
end subroutine strfun_chain_set_escan

subroutine strfun_chain_set_beam_events &
  (sfchain, i, line, beam_events_data, n_parameters)
  type(strfun_chain_t), intent(inout), target :: sfchain
  integer, intent(in) :: i, line, n_parameters
  type(beam_events_data_t), intent(in) :: beam_events_data
  call strfun_init (sfchain%strfun(i), beam_events_data)
  sfchain%n_parameters(i) = n_parameters
  if (line == 0) then
    call strfun_chain_link (sfchain, i, line, (/1, 2/), (/3, 4/))
  else

```

```

        call strfun_chain_link (sfchain, i, line, (/1/), (/2/))
    end if
end subroutine strfun_chain_set_beam_events

subroutine strfun_chain_set_user &
    (sfchain, i, line, user_data, n_parameters)
    type(strfun_chain_t), intent(inout), target :: sfchain
    integer, intent(in) :: i, line, n_parameters
    type(sf_user_data_t), intent(in) :: user_data
    integer :: n_tot
    call strfun_init (sfchain%strfun(i), user_data)
    n_tot = sf_user_data_get_n_tot (user_data)
    sfchain%n_parameters(i) = n_parameters
    if (line == 0) then
        call strfun_chain_link (sfchain, i, line, (/1, 2/), (/n_tot-1, n_tot/))
    else
        call strfun_chain_link (sfchain, i, line, (/1/), (/n_tot/))
    end if
end subroutine strfun_chain_set_user

```

This procedure links a new structure function to the existing chain. *i* is the overall structure function counter. *line* indicates the beam(s) to which the structure function applies; 0 is for both beams. The last two arguments are the indices of the incoming and outgoing particle(s) within the current structure function. For a single-beam (double-beam) structure function, these arrays are of length 1 (2), respectively.

The connections of outgoing/incoming particles are recorded as links in the new structure-function entry `sfchain%strfun(i)`.

(Strfun: procedures)+≡

```

subroutine strfun_chain_link (sfchain, i, line, in_index, out_index)
    type(strfun_chain_t), intent(inout), target :: sfchain
    integer, intent(in) :: i, line
    integer, dimension(:), intent(in) :: in_index, out_index
    select case (line)
    case (0)
        call link_single (1, in_index(1))
        call link_single (2, in_index(2))
        sfchain%last_strfun = i
        sfchain%out_index = out_index
    case default
        call link_single (line, in_index(1))
        sfchain%last_strfun(line) = i
        sfchain%out_index(line) = out_index(1)
    end select
contains
subroutine link_single (line, in_index)
    integer, intent(in) :: line, in_index
    integer :: j
    j = sfchain%last_strfun(line)
    select case (j)
    case (0)
        call interaction_set_source_link &
            (sfchain%strfun(i)%int, in_index, &

```

```

        sfchain%beam, sfchain%out_index(line))
    case default
        call interaction_set_source_link &
            (sfchain%strfun(i)%int, in_index, &
             sfchain%strfun(j)%int, sfchain%out_index(line))
    end select
end subroutine link_single
end subroutine strfun_chain_link

```

Setting up mappings

Set a particular mapping with a known type.

```

<Strfun: public>+≡
    public :: strfun_chain_set_mapping

<Strfun: procedures>+≡
    subroutine strfun_chain_set_mapping (sfchain, i, ch, index, type, par)
        type(strfun_chain_t), intent(inout) :: sfchain
        integer, intent(in) :: i, ch
        integer, dimension(:), intent(in) :: index
        integer, intent(in) :: type
        real(default), dimension(:), intent(in) :: par
        call strfun_mapping_init (sfchain%sf_mapping(i, ch), index, type, par)
    end subroutine strfun_chain_set_mapping

```

Evaluators

```

<Strfun: public>+≡
    public :: strfun_chain_make_evaluators

<Strfun: procedures>+≡
    subroutine strfun_chain_make_evaluators (sfchain, ok)
        type(strfun_chain_t), intent(inout), target :: sfchain
        logical, intent(out), optional :: ok
        type(interaction_t), pointer :: beam_int, eval_int, sf_int, eval_int_next
        type(quantum_numbers_mask_t) :: qn_mask_conn
        type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask_beam
        integer :: i, j, last, out_index, coll_index
        sfchain%n_parameters_tot = sum (sfchain%n_parameters)
        beam_int => beam_get_int_ptr (sfchain%beam)
        if (.not. associated (beam_int)) call msg_bug &
            ("strfun_chain_make_evaluators: null beam pointer")
        allocate (qn_mask_beam (interaction_get_n_out (beam_int)))
        qn_mask_beam = interaction_get_mask (beam_int)
        call interaction_exchange_mask (beam_int)
        do i = 1, size (sfchain%strfun) - 1
            call interaction_exchange_mask (sfchain%strfun(i)%int)
        end do
        do i = size (sfchain%strfun), 1, -1
            call interaction_exchange_mask (sfchain%strfun(i)%int)
        end do
        if (any (qn_mask_beam .neqv. interaction_get_mask (beam_int))) then

```

```

        call beam_write (sfchain%beam)
        call msg_fatal (" Beam polarization/color/flavor incompatible with structure functions")
    end if
    eval_int => beam_int
    do i = 1, size (sfchain%strfun)
        qn_mask_conn = new_quantum_numbers_mask (.false., .false., .true.)
        call evaluator_init_product (sfchain%eval(i), eval_int, &
            sfchain%strfun(i)%int, qn_mask_conn)
        if (evaluator_is_empty (sfchain%eval(i))) then
            call msg_fatal ("Mismatch in beam and structure-function chain")
            if (present (ok)) ok = .false.
            return
        end if
        eval_int => evaluator_get_int_ptr (sfchain%eval(i))
    end do
    if (size (sfchain%strfun) /= 0) then
        do j = 1, size (sfchain%coll_index)
            last = sfchain%last_strfun(j)
            select case (last)
            case (0)
                eval_int => beam_get_int_ptr (sfchain%beam)
                out_index = sfchain%out_index(j)
                coll_index = out_index
            case default
                sf_int => sfchain%strfun(last)%int
                eval_int => evaluator_get_int_ptr (sfchain%eval(last))
                out_index = sfchain%out_index(j)
                coll_index = interaction_find_link (eval_int, sf_int, out_index)
            end select
            if (coll_index /= 0) then
                do i = last + 1, size (sfchain%strfun)
                    out_index = coll_index
                    eval_int_next => evaluator_get_int_ptr (sfchain%eval(i))
                    coll_index = &
                        interaction_find_link (eval_int_next, eval_int, out_index)
                    if (coll_index == 0) call msg_bug ("Structure functions: " &
                        // "broken links in structure function chain")
                    eval_int => eval_int_next
                end do
            end if
            if (coll_index /= 0) then
                sfchain%coll_index(j) = coll_index
            else
                call msg_bug ("Structure functions: " &
                    // "colliding particles can't be determined")
            end if
        end do
    end if
    if (present (ok)) ok = .true.
end subroutine strfun_chain_make_evaluators

```

Setup kinematics: use the given array of random numbers `r` to generate a chain of momenta, up to the incoming partons.


```

<Strfun: public>+=
    public :: strfun_chain_set_kinematics

<Strfun: procedures>+=
    subroutine strfun_chain_set_kinematics (sfchain, r, &
        channel, offset, r_all, sf_factor, ok)
        type(strfun_chain_t), intent(inout) :: sfchain
        real(default), dimension(:), intent(in) :: r
        integer, intent(in), optional :: channel, offset
        real(default), dimension(:,:), intent(inout), optional :: r_all
        real(default), dimension(:), intent(out), optional :: sf_factor
        logical, intent(out), optional :: ok
        real(default), dimension(size(r)) :: x
        integer :: n_mapping
        integer :: i, i1, i2, ch, n, n1, n_sf
        real(default) :: xprod, factor
        real(default), dimension(:), allocatable :: factor_channel
        integer, dimension(:), allocatable :: mapping_type
        n_sf = size (sfchain%strfun)
        sfchain%mapping_factor = 1
        if (size (r) == sfchain%n_parameters_tot) then
            x = r
            if (allocated (sfchain%sf_mapping)) then
                n_mapping = size (sfchain%sf_mapping, 1)
                if (present (channel)) then
                    allocate (factor_channel (n_mapping))
                    allocate (mapping_type (n_mapping))
                    do i = 1, n_mapping
                        mapping_type(i) = sfchain%sf_mapping(i,channel)%type
                        call strfun_mapping_apply &
                            (sfchain%sf_mapping(i, channel), x, factor_channel(i))
                    end do
                    sf_factor(channel) = product (factor_channel)
                else
                    do i = 1, n_mapping
                        call strfun_mapping_apply &
                            (sfchain%sf_mapping(i, 1), x, factor)
                        sfchain%mapping_factor = sfchain%mapping_factor * factor
                    end do
                end if
            end if
            n = 0
            do i = 1, size (sfchain%strfun)
                call interaction_receive_momenta (sfchain%strfun(i)%int)
                n1 = sfchain%n_parameters(i)
                call strfun_set_kinematics (sfchain%strfun(i), x(n+1:n+n1), .false.)
                n = n + n1
            end do
            if (present (channel)) then
                i1 = offset
                i2 = offset + size (r)
                do ch = 1, size (r_all, 2)
                    if (ch /= channel) then
                        sf_factor(ch) = 1
                        do i = 1, n_mapping

```

```

        if (sfchain%sf_mapping(i,ch)%type == mapping_type(i)) then
            r_all(i1+1:i2,ch) = r
            sf_factor(ch) = sf_factor(ch) * factor_channel(i)
        else
            r_all(i1+1:i2,ch) = x
            call strfun_mapping_apply_inverse &
                (sfchain%sf_mapping(1,ch), r_all(i1+1:i2,ch), &
                 factor)
            sf_factor(ch) = sf_factor(ch) * factor
        end if
    end do
end if
end do
do i = 1, size (sfchain%strfun)
    call evaluator_receive_momenta (sfchain%eval(i))
end do
if (present (ok)) ok = .true.
else
    call msg_bug ("Structure functions: mismatch in number of parameters")
end if
end subroutine strfun_chain_set_kinematics

```

<Strfun: public>+≡

```
public :: strfun_chain_evaluate
```

<Strfun: procedures>+≡

```

subroutine strfun_chain_evaluate (sfchain, scale)
    type(strfun_chain_t), intent(inout) :: sfchain
    real(default), intent(in) :: scale
    integer :: i
    do i = size (sfchain%strfun), 1, -1
        call strfun_apply (sfchain%strfun(i), scale)
    end do
    do i = 1, size (sfchain%eval)
        call evaluator_evaluate (sfchain%eval(i))
    end do
end subroutine strfun_chain_evaluate

```

10.12.4 Test

<Strfun: public>+≡

```
public :: strfun_test
```

<Strfun: procedures>+≡

```

subroutine strfun_test (lhpdf_present)
    use os_interface, only: os_data_t
    type(os_data_t) :: os_data
    type(model_t), pointer :: model
    logical, intent(in) :: lhpdf_present
    print *, "*** Read model file"
    call syntax_model_file_init ()
    call model_list_read_model &

```

```

        (var_str("SM"), var_str("SM.mdl"), os_data, model)
    call syntax_model_file_final ()
    print *, "*****"
    call isr_test (model)
    print *, "*****"
    call epa_test (model)
    if (lhpdf_present) then
        print *, "*****"
        call lhpdf_test (model)
    end if
end subroutine strfun_test

subroutine isr_test (model)
    use flavors
    use polarizations
    type(model_t), intent(in), target :: model
    type(flavor_t), dimension(2) :: flv
    type(polarization_t), dimension(2) :: pol
    type(beam_data_t), target :: beam_data
    type(isr_data_t), dimension(2) :: isr_data
    type(strfun_chain_t), target :: sfchain
    integer :: i
    print *, "*** ISR test"
    call flavor_init (flv, (/11, -11/), model)
    call polarization_init_unpolarized (pol(1), flv(1))
    call polarization_init_unpolarized (pol(2), flv(2))
    call beam_data_init_sqrts (beam_data, 500._default, flv, pol)
    do i = 1, 2
        call isr_data_init (isr_data(i), &
            model, flv(i), 0.06_default, 500._default, 0.511e-3_default)
    end do
    call strfun_chain_init (sfchain, beam_data, 2)
    call strfun_chain_set_strfun (sfchain, 1, 1, isr_data(1), 1)
    call strfun_chain_set_strfun (sfchain, 2, 2, isr_data(2), 3)
    call strfun_chain_make_evaluators (sfchain)
    call strfun_chain_set_kinematics &
        (sfchain, (/0.8_default, 0.4_default, 0.5_default, 0.2_default/))
    call strfun_chain_evaluate (sfchain, 0._default)
    call strfun_chain_write (sfchain)
    call strfun_chain_final (sfchain)
end subroutine isr_test

subroutine epa_test (model)
    use flavors
    use polarizations
    type(model_t), intent(in), target :: model
    type(flavor_t), dimension(2) :: flv
    type(polarization_t), dimension(2) :: pol
    type(beam_data_t) :: beam_data
    type(epa_data_t) :: epa_data1
    type(epa_data_t) :: epa_data2
    type(strfun_chain_t), target :: sfchain
    print *, "*** EPA test"
    call flavor_init (flv, (/2, 1/), model)

```

```

! Prepare beams
call polarization_init_circular (pol(1), flv(1), 0.3_default)
call polarization_init_unpolarized (pol(2), flv(2))
call beam_data_init_sqrts (beam_data, 1000._default, flv, pol)
call strfun_chain_init (sfchain, beam_data, 2)
! Initialize EPA for both
call epa_data_init (epa_data1, model, &
    flv(1), 0.06_default, 1.e-6_default, 0._default, 500._default, &
    511.e-6_default)
call epa_data_init (epa_data2, model, &
    flv(2), 0.06_default, 1.e-6_default, 1._default, 500._default)
call strfun_chain_set_strfun (sfchain, 1, 1, epa_data1, 1)
call strfun_chain_set_strfun (sfchain, 2, 2, epa_data2, 3)
! call strfun_chain_write (sfchain); stop
call strfun_chain_make_evaluators (sfchain)
call strfun_chain_set_kinematics &
    (sfchain, (/0.8_default, 0.4_default, 0.5_default, 0.2_default/))
call strfun_chain_evaluate (sfchain, 0._default)
call strfun_chain_write (sfchain)
! Clean up
call beam_data_final (beam_data)
call polarization_final (pol)
call strfun_chain_final (sfchain)
end subroutine epa_test

subroutine lhpdf_test (model)
    use flavors
    use polarizations
    type(model_t), intent(in), target :: model
    type(beam_data_t) :: beam_data
    type(flavor_t), dimension(2) :: flv
    type(polarization_t), dimension(2) :: pol
    type(lhpdf_data_t), dimension(2) :: data
    type(lhpdf_status_t) :: lhpdf_status
    type(strfun_chain_t), target :: sfchain
    real(default) :: scale
    print *, "*** LHAPDF test"
    call flavor_init (flv, (/ -PROTON, PHOTON /), model)
    call polarization_init_unpolarized (pol(1), flv(1))
    call polarization_init_unpolarized (pol(2), flv(2))
    call beam_data_init_sqrts (beam_data, 2000._default, flv, pol)
    call strfun_chain_init (sfchain, beam_data, 2)
    call lhpdf_data_init (data(1), lhpdf_status, model, flv(1), member=1)
    !!! Use the same photon PDF that is demanded by the LHAPDF tests.
    call lhpdf_data_init (data(2), lhpdf_status, model, flv(2), &
        file=var_str("GSG961.LHgrid"), photon_scheme=1)
    call lhpdf_data_set_mask (data(2), &
        (/ .false., .false., .false., .true., .true., .true., &
        .false., &
        .true., .true., .true., .false., .false., .false. /))
! call strfun_chain_write (sfchain); stop
call strfun_chain_set_strfun (sfchain, 1, 1, data(1), 1)
call strfun_chain_set_strfun (sfchain, 2, 2, data(2), 1)
! call strfun_chain_write (sfchain); stop

```

```
call strfun_chain_make_evaluators (sfchain)
call strfun_chain_set_kinematics (sfchain, (/0.9_default, 0.4_default/))
scale = 1.e3_default
call strfun_chain_evaluate (sfchain, scale)
call strfun_chain_write (sfchain)
call strfun_chain_final (sfchain)
end subroutine lhpdf_test
```

Chapter 11

Partonic Events

This chapter deals with and combines the various components (interactions) of a partonic event: beams, spectra, scattering, decays.

Chapter 12

Phase space and hard matrix elements

These modules contain the internal representation and evaluation of phase space and the interface to (hard-)process evaluation.

mappings Generate invariant masses and decay angles from given random numbers (or the inverse operation). Each mapping pertains to a particular node in a phase-space tree. Different mappings account for uniform distributions, resonances, zero-mass behavior, and so on.

phs_trees Phase space parameterizations for scattering processes are defined recursively as if there was an initial particle decaying. This module sets up a representation in terms of abstract trees, where each node gets a unique binary number. Each tree is stored as an array of branches, where integers indicate the connections. This emulates pointers in a transparent way. Real pointers would also be possible, but seem to be less efficient for this particular case.

phs_forests The type defined by this module collects the decay trees corresponding to a given process and the applicable mappings. To set this up, a file is read which is either written by the user or by the **cascades** module functions. The module also contains the routines that evaluate phase space, i.e., generate momenta from random numbers and back.

cascades This module is a Feynman diagram generator with the particular purpose of finding the phase space parameterizations best suited for a given process. It uses a model file to set up the possible vertices, generates all possible diagrams, identifies resonances and singularities, and simplifies the list by merging equivalent diagrams and dropping irrelevant ones. This process can be controlled at several points by user-defined parameters. Note that it depends on the particular values of particle masses, so it cannot be done before reading the input file.

12.1 Mappings

Mappings are objects that encode the transformation of the interval $(0,1)$ to a physical variable m^2 or $\cos\theta$ (and back), as it is used in the phase space parameterization. The mapping objects contain fixed parameters, the associated methods implement the mapping and inverse mapping operations, including the computation of the Jacobian (phase space factor).

```
<mappings.f90>≡  
  <File header>  
  
  module mappings  
  
    <Use kinds>  
    use kinds, only: TC !NODEP!  
    <Use strings>  
    use constants, only: pi !NODEP!  
    <Use file utils>  
    use diagnostics !NODEP!  
    use md5  
    use models  
    use flavors  
  
    <Standard module head>  
  
    <Mappings: public>  
  
    <Mappings: parameters>  
  
    <Mappings: types>  
  
    <Mappings: interfaces>  
  
    contains  
  
    <Mappings: procedures>  
  
  end module mappings
```

12.1.1 Default parameters

This type holds the default parameters, needed for setting the scale in cases where no mass parameter is available. The contents are public.

```
<Mappings: public>≡  
  public :: mapping_defaults_t  
  
<Mappings: types>≡  
  type :: mapping_defaults_t  
    real(default) :: energy_scale = 10  
    real(default) :: invariant_mass_scale = 10  
    real(default) :: momentum_transfer_scale = 10  
    logical :: step_mapping = .true.  
    logical :: step_mapping_exp = .true.  
    logical :: enable_s_mapping = .false.
```



```

end type mapping_defaults_t

<Mappings: public>+≡
public :: mapping_defaults_md5sum

<Mappings: procedures>≡
function mapping_defaults_md5sum (mapping_defaults) result (md5sum_map)
character(32) :: md5sum_map
type(mapping_defaults_t), intent(in) :: mapping_defaults
integer :: u
u = free_unit ()
open (u, status = "scratch")
write (u, *) mapping_defaults%energy_scale
write (u, *) mapping_defaults%invariant_mass_scale
write (u, *) mapping_defaults%momentum_transfer_scale
write (u, *) mapping_defaults%step_mapping
write (u, *) mapping_defaults%step_mapping_exp
write (u, *) mapping_defaults%enable_s_mapping
rewind (u)
md5sum_map = md5sum (u)
close (u)
end function mapping_defaults_md5sum

```

12.1.2 The Mapping type

Each mapping has a type (e.g., s-channel, infrared), a binary code (redundant, but useful for debugging), and a reference particle. The flavor code of this particle is stored for bookkeeping reasons, what matters are the mass and width of this particle. Furthermore, depending on the type, various mapping parameters can be set and used.

The parameters **a1** to **a3** (for m^2 mappings) and **b1** to **b3** (for $\cos\theta$ mappings) are values that are stored once to speed up the calculation, if **variable_limits** is false. The exact meaning of these parameters depends on the mapping type. The limits are fixed if there is a fixed c.m. energy.

```

<Mappings: public>+≡
public :: mapping_t

<Mappings: types>+≡
type :: mapping_t
private
integer :: type = NO_MAPPING
integer(TC) :: bincode
type(flavor_t) :: flv
real(default) :: mass = 0
real(default) :: width = 0
logical :: a_unknown = .true.
real(default) :: a1 = 0
real(default) :: a2 = 0
real(default) :: a3 = 0
logical :: b_unknown = .true.
real(default) :: b1 = 0
real(default) :: b2 = 0

```

```

    real(default) :: b3 = 0
    logical :: variable_limits = .true.
end type mapping_t

```

The valid mapping types. The extra type STEP_MAPPING is used only internally.

(Mappings: parameters)≡
(Mapping modes)

12.1.3 Screen output

Do not write empty mappings.

(Mappings: public)+≡
 public :: mapping_write

(Mappings: procedures)+≡
 subroutine mapping_write (map, unit, verbose)
 type(mapping_t), intent(in) :: map
 integer, intent(in), optional :: unit
 logical, intent(in), optional :: verbose
 integer :: u
 character(len=9) :: str
 u = output_unit (unit); if (u < 0) return
 select case(map%type)
 case(S_CHANNEL); str = "s_channel"
 case(COLLINEAR); str = "collinear"
 case(INFRARED); str = "infrared "
 case(RADIATION); str = "radiation"
 case(T_CHANNEL); str = "t_channel"
 case(U_CHANNEL); str = "u_channel"
 case(STEP_MAPPING_E); str = "step_exp"
 case(STEP_MAPPING_H); str = "step_hyp"
 end select
 if (map%type /= NO_MAPPING) then
 write (u, '(1x,A,I4,A)') &
 "Branch #", map%bincode, ": " // &
 "Mapping (" // str // ") for particle " // &
 "' ' // char (flavor_get_name (map%flv)) // ' "'
 if (present (verbose)) then
 if (verbose) then
 select case (map%type)
 case (S_CHANNEL, RADIATION, STEP_MAPPING_E, STEP_MAPPING_H)
 write (u, *) " m/w = ", map%mass, map%width
 case default
 write (u, *) " m = ", map%mass
 end select
 select case (map%type)
 case (S_CHANNEL, T_CHANNEL, U_CHANNEL, &
 STEP_MAPPING_E, STEP_MAPPING_H, &
 COLLINEAR, INFRARED, RADIATION)
 write (u, *) " a1/2/3 = ", map%a1, map%a2, map%a3
 end select
 select case (map%type)
 case (T_CHANNEL, U_CHANNEL, COLLINEAR)

```

        write (u, *) "  b1/2/3 = ", map%b1, map%b2, map%b3
      end select
    end if
  end if
end if
end subroutine mapping_write

```

12.1.4 Define a mapping

The initialization routine sets the mapping type and the particle (binary code and flavor code) for which the mapping applies (e.g., a Z resonance in branch #3). We only need the absolute value of the flavor code.

```

<Mappings: public>+≡
  public :: mapping_init

<Mappings: procedures>+≡
  subroutine mapping_init (mapping, brcode, type, f, model)
    type(mapping_t), intent(inout) :: mapping
    integer(TC), intent(in) :: brcode
    type(string_t), intent(in) :: type
    integer, intent(in), optional :: f
    type(model_t), intent(in), optional, target :: model
    mapping%brcode = brcode
    select case (char (type))
    case ("s_channel"); mapping%type = S_CHANNEL
    case ("collinear"); mapping%type = COLLINEAR
    case ("infrared"); mapping%type = INFRARED
    case ("radiation"); mapping%type = RADIATION
    case ("t_channel"); mapping%type = T_CHANNEL
    case ("u_channel"); mapping%type = U_CHANNEL
    case ("step_exp"); mapping%type = STEP_MAPPING_E
    case ("step_hyp"); mapping%type = STEP_MAPPING_H
    end select
    if (present (f) .and. present (model)) &
      call flavor_init (mapping%flv, abs (f), model)
  end subroutine mapping_init

```

This sets the actual mass and width, using a parameter set. Since the auxiliary parameters will only be determined when the mapping is first called, they are marked as unknown.

```

<Mappings: public>+≡
  public :: mapping_set_parameters

<Mappings: procedures>+≡
  subroutine mapping_set_parameters (map, mapping_defaults, variable_limits)
    type(mapping_t), intent(inout) :: map
    type(mapping_defaults_t), intent(in) :: mapping_defaults
    logical, intent(in) :: variable_limits
    if (map%type /= NO_MAPPING) then
      map%mass = flavor_get_mass (map%flv)
      map%width = flavor_get_width (map%flv)
      map%variable_limits = variable_limits
    end if
  end subroutine mapping_set_parameters

```

```

map%a_unknown = .true.
map%b_unknown = .true.
select case (map%type)
case (S_CHANNEL)
  if (map%mass <= 0) then
    call mapping_write (map)
    call msg_fatal &
      & (" S-channel resonance must have positive mass")
  else if (map%width <= 0) then
    call mapping_write (map)
    call msg_fatal &
      & (" S-channel resonance must have positive width")
  end if
case (RADIATION)
  map%width = max (map%width, mapping_defaults%energy_scale)
case (INFRARED, COLLINEAR)
  map%mass = max (map%mass, mapping_defaults%invariant_mass_scale)
case (T_CHANNEL, U_CHANNEL)
  map%mass = max (map%mass, mapping_defaults%momentum_transfer_scale)
end select
end if
end subroutine mapping_set_parameters

```

For a step mapping the mass and width are set directly, instead of being determined from the flavor parameter (which is meaningless here). They correspond to the effective upper bound of phase space due to a resonance, as opposed to the absolute upper bound.

```

<Mappings: public>+≡
  public :: mapping_set_step_mapping_parameters

<Mappings: procedures>+≡
  subroutine mapping_set_step_mapping_parameters (map, &
    mass, width, variable_limits)
    type(mapping_t), intent(inout) :: map
    real(default), intent(in) :: mass, width
    logical, intent(in) :: variable_limits
    select case (map%type)
    case (STEP_MAPPING_E, STEP_MAPPING_H)
      map%variable_limits = variable_limits
      map%a_unknown = .true.
      map%b_unknown = .true.
      map%mass = mass
      map%width = width
    end select
  end subroutine mapping_set_step_mapping_parameters

```

12.1.5 Retrieve contents

Return true if there is any / an s-channel mapping.

```

<Mappings: public>+≡
  public :: mapping_is_set
  public :: mapping_is_s_channel

```

```

<Mappings: procedures>+≡
  function mapping_is_set (mapping) result (flag)
    logical :: flag
    type(mapping_t), intent(in) :: mapping
    flag = mapping%type /= NO_MAPPING
  end function mapping_is_set

  function mapping_is_s_channel (mapping) result (flag)
    logical :: flag
    type(mapping_t), intent(in) :: mapping
    flag = mapping%type == S_CHANNEL
  end function mapping_is_s_channel

```

Return stored mass and width, respectively.

```

<Mappings: public>+≡
  public :: mapping_get_mass
  public :: mapping_get_width

<Mappings: procedures>+≡
  function mapping_get_mass (mapping) result (mass)
    real(default) :: mass
    type(mapping_t), intent(in) :: mapping
    mass = mapping%mass
  end function mapping_get_mass

  function mapping_get_width (mapping) result (width)
    real(default) :: width
    type(mapping_t), intent(in) :: mapping
    width = mapping%width
  end function mapping_get_width

```

12.1.6 Compare mappings

Equality for single mappings and arrays

```

<Mappings: public>+≡
  public :: operator(==)

<Mappings: interfaces>≡
  interface operator(==)
    module procedure mapping_equal
  end interface

<Mappings: procedures>+≡
  function mapping_equal (m1, m2) result (equal)
    type(mapping_t), intent(in) :: m1, m2
    logical :: equal
    if (m1%type == m2%type) then
      select case (m1%type)
        case (NO_MAPPING)
          equal = .true.
        case (S_CHANNEL, RADIATION, STEP_MAPPING_E, STEP_MAPPING_H)
          equal = (m1%mass == m2%mass) .and. (m1%width == m2%width)
        case default

```

```

        equal = (m1%mass == m2%mass)
    end select
else
    equal = .false.
end if
end function mapping_equal

```

12.1.7 Mappings of the invariant mass

Inserting an x value between 0 and 1, we want to compute the corresponding invariant mass $m^2(x)$ and the jacobian, aka phase space factor $f(x)$. We also need the reverse operation.

In general, the phase space factor f is defined by

$$\frac{1}{s} \int_{m_{\min}^2}^{m_{\max}^2} dm^2 g(m^2) = \int_0^1 dx \frac{1}{s} \frac{dm^2}{dx} g(m^2(x)) = \int_0^1 dx f(x) g(x), \quad (12.1)$$

where thus

$$f(x) = \frac{1}{s} \frac{dm^2}{dx}. \quad (12.2)$$

With this mapping, a function of the form

$$g(m^2) = c \frac{dx(m^2)}{dm^2} \quad (12.3)$$

is mapped to a constant:

$$\frac{1}{s} \int_{m_{\min}^2}^{m_{\max}^2} dm^2 g(m^2) = \int_0^1 dx f(x) g(m^2(x)) = \int_0^1 dx \frac{c}{s}. \quad (12.4)$$

Here is the mapping routine. Input are the available energy squared s , the limits for m^2 , and the x value. Output are the m^2 value and the phase space factor f .

```

⟨Mappings: public⟩+=
    public :: mapping_compute_msq_from_x

⟨Mappings: procedures⟩+=
    subroutine mapping_compute_msq_from_x (map, s, msq_min, msq_max, msq, f, x)
        type(mapping_t), intent(inout) :: map
        real(default), intent(in) :: s, msq_min, msq_max
        real(default), intent(out) :: msq, f
        real(default), intent(in) :: x
        real(default) :: z, msq0, msq1, tmp
        integer :: type
        type = map%type
        if (s == 0) &
            call msg_fatal (" Applying msq mapping for zero energy")
    ⟨Modify mapping type if necessary⟩
        select case(type)
        case (NO_MAPPING)
            ⟨Constants for trivial msq mapping⟩
            ⟨Apply trivial msq mapping⟩

```

```

case (S_CHANNEL)
  <Constants for s-channel resonance mapping>
  <Apply s-channel resonance mapping>
case (COLLINEAR, INFRARED, RADIATION)
  <Constants for s-channel pole mapping>
  <Apply s-channel pole mapping>
case (T_CHANNEL, U_CHANNEL)
  <Constants for t-channel pole mapping>
  <Apply t-channel pole mapping>
case (STEP_MAPPING_E)
  <Constants for exponential step mapping>
  <Apply exponential step mapping>
case (STEP_MAPPING_H)
  <Constants for hyperbolic step mapping>
  <Apply hyperbolic step mapping>
case default
  call msg_fatal ( " Attempt to apply undefined msq mapping")
end select
end subroutine mapping_compute_msq_from_x

```

The inverse mapping

```

<Mappings: public>+≡
  public :: mapping_compute_x_from_msq

<Mappings: procedures>+≡
  subroutine mapping_compute_x_from_msq (map, s, msq_min, msq_max, msq, f, x)
    type(mapping_t), intent(inout) :: map
    real(default), intent(in) :: s, msq_min, msq_max
    real(default), intent(in) :: msq
    real(default), intent(out) :: f, x
    real(default) :: msq0, msq1, tmp, z
    integer :: type
    type = map%type
    if (s == 0) &
      call msg_fatal (" Applying inverse msq mapping for zero energy")
  <Modify mapping type if necessary>
  select case (type)
  case (NO_MAPPING)
    <Constants for trivial msq mapping>
    <Apply inverse trivial msq mapping>
  case (S_CHANNEL)
    <Constants for s-channel resonance mapping>
    <Apply inverse s-channel resonance mapping>
  case (COLLINEAR, INFRARED, RADIATION)
    <Constants for s-channel pole mapping>
    <Apply inverse s-channel pole mapping>
  case (T_CHANNEL, U_CHANNEL)
    <Constants for t-channel pole mapping>
    <Apply inverse t-channel pole mapping>
  case (STEP_MAPPING_E)
    <Constants for exponential step mapping>
    <Apply inverse exponential step mapping>
  case (STEP_MAPPING_H)
    <Constants for hyperbolic step mapping>

```

```

    <Apply inverse hyperbolic step mapping>
case default
    call msg_fatal ( " Attempt to apply undefined msq mapping")
end select
end subroutine mapping_compute_x_from_msq

```

Trivial mapping

We simply map the boundaries of the interval (m_{\min}, m_{\max}) to $(0, 1)$:

$$m^2 = (1 - x)m_{\min}^2 + xm_{\max}^2; \quad (12.5)$$

the inverse is

$$x = \frac{m^2 - m_{\min}^2}{m_{\max}^2 - m_{\min}^2}. \quad (12.6)$$

Hence

$$f(x) = \frac{m_{\max}^2 - m_{\min}^2}{s}, \quad (12.7)$$

and we have, as required,

$$f(x) \frac{dx}{dm^2} = \frac{1}{s}. \quad (12.8)$$

We store the constant parameters the first time the mapping is called – or, if limits vary, recompute them each time.

```

<Constants for trivial msq mapping>≡
  if (map%variable_limits .or. map%a_unknown) then
    map%a1 = 0
    map%a2 = msq_max - msq_min
    map%a3 = map%a2 / s
    map%a_unknown = .false.
  end if

<Apply trivial msq mapping>≡
  msq = (1-x) * msq_min + x * msq_max
  f = map%a3

<Apply inverse trivial msq mapping>≡
  if (map%a2 /= 0) then
    x = (msq - msq_min) / map%a2
  else
    x = 0
  end if
  f = map%a3

```

Resonance or step mapping does not make much sense if the resonance mass is outside the kinematical bounds. If this is the case, revert to NO_MAPPING. This is possible even if the kinematical bounds vary from event to event.

```

<Modify mapping type if necessary>≡
  select case (type)
  case (S_CHANNEL, STEP_MAPPING_E, STEP_MAPPING_H)
    msq0 = map%mass**2
    if (msq0 < msq_min .or. msq0 > msq_max) type = NO_MAPPING
  end select

```


Breit-Wigner mapping

A Breit-Wigner resonance with mass M and width Γ is flattened by the following mapping:

This mapping does not make much sense if the resonance mass is too low. If this is the case, revert to `NO_MAPPING`. There is a tricky point with this if the mass is too high: `msq_max` is not a constant if structure functions are around. However, switching the type depending on the overall energy does not change the integral, it is just another branching point.

$$m^2 = M(M + t\Gamma), \quad (12.9)$$

where

$$t = \tan \left[(1-x) \arctan \frac{m_{\min}^2 - M^2}{M\Gamma} + x \arctan \frac{m_{\max}^2 - M^2}{M\Gamma} \right]. \quad (12.10)$$

The inverse:

$$x = \frac{\arctan \frac{m^2 - M^2}{M\Gamma} - \arctan \frac{m_{\min}^2 - M^2}{M\Gamma}}{\arctan \frac{m_{\max}^2 - M^2}{M\Gamma} - \arctan \frac{m_{\min}^2 - M^2}{M\Gamma}} \quad (12.11)$$

The phase-space factor of this transformation is

$$f(x) = \frac{M\Gamma}{s} \left(\arctan \frac{m_{\max}^2 - M^2}{M\Gamma} - \arctan \frac{m_{\min}^2 - M^2}{M\Gamma} \right) (1 + t^2). \quad (12.12)$$

This maps any function proportional to

$$g(m^2) = \frac{M\Gamma}{(m^2 - M^2)^2 + M^2\Gamma^2} \quad (12.13)$$

to a constant times $1/s$.

(Constants for s-channel resonance mapping) \equiv

```
if (map%variable_limits .or. map%a_unknown) then
  msq0 = map%mass ** 2
  map%a1 = atan ((msq_min - msq0) / (map%mass * map%width))
  map%a2 = atan ((msq_max - msq0) / (map%mass * map%width))
  map%a3 = (map%a2 - map%a1) * (map%mass * map%width) / s
  map%a_unknown = .false.
end if
```

(Apply s-channel resonance mapping) \equiv

```
z = (1-x) * map%a1 + x * map%a2
if (-pi/2 < z .and. z < pi/2) then
  tmp = tan (z)
  msq = map%mass * (map%mass + map%width * tmp)
  f = map%a3 * (1 + tmp**2)
else
  msq = 0
  f = 0
end if
```

(Apply inverse s-channel resonance mapping) \equiv

```
tmp = (msq - msq0) / (map%mass * map%width)
x = (atan (tmp) - map%a1) / (map%a2 - map%a1)
f = map%a3 * (1 + tmp**2)
```

Mapping for massless splittings

This mapping accounts for approximately scale-invariant behavior where $\ln M^2$ is evenly distributed.

$$m^2 = m_{\min}^2 + M^2 (\exp(xL) - 1) \quad (12.14)$$

where

$$L = \ln \left(\frac{m_{\max}^2 - m_{\min}^2}{M^2} + 1 \right). \quad (12.15)$$

The inverse:

$$x = \frac{1}{L} \ln \left(\frac{m^2 - m_{\min}^2}{M^2} + 1 \right) \quad (12.16)$$

The constant M is a characteristic scale. Above this scale ($m^2 - m_{\min}^2 \gg M^2$), this mapping behaves like $x \propto \ln m^2$, while below the scale it reverts to a linear mapping.

The phase-space factor is

$$f(x) = \frac{M^2}{s} \exp(xL) L. \quad (12.17)$$

A function proportional to

$$g(m^2) = \frac{1}{(m^2 - m_{\min}^2) + M^2} \quad (12.18)$$

is mapped to a constant, i.e., a simple pole near m_{\min} with a regulator mass M .

This type of mapping is useful for massless collinear and infrared singularities, where the scale is stored as the mass parameter. In the radiation case (IR radiation off massive particle), the heavy particle width is the characteristic scale.

```

⟨Constants for s-channel pole mapping⟩≡
  if (map%variable_limits .or. map%a_unknown) then
    if (type == RADIATION) then
      msq0 = map%width**2
    else
      msq0 = map%mass**2
    end if
    map%a1 = msq0
    map%a2 = log ((msq_max - msq_min) / msq0 + 1)
    map%a3 = map%a2 / s
    map%a_unknown = .false.
  end if

⟨Apply s-channel pole mapping⟩≡
  msq1 = map%a1 * exp (x * map%a2)
  msq = msq1 - map%a1 + msq_min
  f = map%a3 * msq1

⟨Apply inverse s-channel pole mapping⟩≡
  msq1 = msq - msq_min + map%a1
  x = log (msq1 / map%a1) / map%a2
  f = map%a3 * msq1

```

Mapping for t-channel poles

This is also approximately scale-invariant, and we use the same type of mapping as before. However, we map $1/x$ singularities at both ends of the interval; again, the mapping becomes linear when the distance is less than M^2 :

$$m^2 = \begin{cases} m_{\min}^2 + M^2 (\exp(xL) - 1) & \text{for } 0 < x < \frac{1}{2} \\ m_{\max}^2 - M^2 (\exp((1-x)L) - 1) & \text{for } \frac{1}{2} \leq x < 1 \end{cases} \quad (12.19)$$

where

$$L = 2 \ln \left(\frac{m_{\max}^2 - m_{\min}^2}{2M^2} + 1 \right). \quad (12.20)$$

The inverse:

$$x = \begin{cases} \frac{1}{L} \ln \left(\frac{m^2 - m_{\min}^2}{M^2} + 1 \right) & \text{for } m^2 < (m_{\max}^2 - m_{\min}^2)/2 \\ 1 - \frac{1}{L} \ln \left(\frac{m_{\max}^2 - m^2}{M^2} + 1 \right) & \text{for } m^2 \geq (m_{\max}^2 - m_{\min}^2)/2 \end{cases} \quad (12.21)$$

The phase-space factor is

$$f(x) = \begin{cases} \frac{M^2}{s} \exp(xL) L. & \text{for } 0 < x < \frac{1}{2} \\ \frac{M^2}{s} \exp((1-x)L) L. & \text{for } \frac{1}{2} \leq x < 1 \end{cases} \quad (12.22)$$

A (continuous) function proportional to

$$g(m^2) = \begin{cases} 1/(m^2 - m_{\min}^2) + M^2 & \text{for } m^2 < (m_{\max}^2 - m_{\min}^2)/2 \\ 1/((m_{\max}^2 - m^2) + M^2) & \text{for } m^2 \geq (m_{\max}^2 - m_{\min}^2)/2 \end{cases} \quad (12.23)$$

is mapped to a constant by this mapping, i.e., poles near both ends of the interval.

```

⟨Constants for t-channel pole mapping⟩≡
  if (map%variable_limits .or. map%a_unknown) then
    msq0 = map%mass**2
    map%a1 = msq0
    map%a2 = 2 * log ((msq_max - msq_min)/(2*msq0) + 1)
    map%a3 = map%a2 / s
    map%a_unknown = .false.
  end if

⟨Apply t-channel pole mapping⟩≡
  if (x < .5_default) then
    msq1 = map%a1 * exp (x * map%a2)
    msq = msq1 - map%a1 + msq_min
  else
    msq1 = map%a1 * exp ((1-x) * map%a2)
    msq = -(msq1 - map%a1) + msq_max
  end if
  f = map%a3 * msq1

⟨Apply inverse t-channel pole mapping⟩≡
  if (msq < (msq_max + msq_min)/2) then
    msq1 = msq - msq_min + map%a1
    x = log (msq1/map%a1) / map%a2

```

```

else
  msq1 = msq_max - msq + map%a1
  x = 1 - log (msq1/map%a1) / map%a2
end if
f = map%a3 * msq1

```

12.1.8 Step mapping

Step mapping is useful when the allowed range for a squared-mass variable is large, but only a fraction at the lower end is populated because the particle in question is an (off-shell) decay product of a narrow resonance. I.e., if the resonance was forced to be on-shell, the upper end of the range would be the resonance mass, minus the effective (real or resonance) mass of the particle(s) in the sibling branch of the decay.

The edge of this phase space section has a width which is determined by the width of the parent, plus the width of the sibling branch. (The widths might be added in quadrature, but this precision is probably not important.)

Fermi function

A possible mapping is derived from the Fermi function which has precisely this behavior. The Fermi function is given by

$$f(x) = \frac{1}{1 + \exp \frac{x-\mu}{\gamma}} \quad (12.24)$$

where x is taken as the invariant mass squared, μ is the invariant mass squared of the edge, and γ is the effective width which is given by the widths of the parent and the sibling branch. (Widths might be added in quadrature, but we do not require this level of precision.)

$$x = \frac{m^2 - m_{\min}^2}{\Delta m^2} \quad (12.25)$$

$$\mu = \frac{m_{\max, \text{eff}}^2 - m_{\min}^2}{\Delta m^2} \quad (12.26)$$

$$\gamma = \frac{2m_{\max, \text{eff}}\Gamma}{\Delta m^2} \quad (12.27)$$

with

$$\Delta m^2 = m_{\max}^2 - m_{\min}^2 \quad (12.28)$$

m^2 is thus given by

$$m^2(x) = xm_{\max}^2 + (1-x)m_{\min}^2 \quad (12.29)$$

For the mapping, we compute the integral $g(x)$ of the Fermi function, normalized such that $g(0) = 0$ and $g(1) = 1$. We introduce the abbreviations

$$\alpha = 1 - \gamma \ln \frac{1 + \beta e^{1/\gamma}}{1 + \beta} \quad (12.30)$$

$$\beta = e^{-\mu/\gamma} \quad (12.31)$$

and obtain

$$g(x) = \frac{1}{\alpha} \left(x - \gamma \ln \frac{1 + \beta e^{x/\gamma}}{1 + \beta} \right) \quad (12.32)$$

The actual mapping is the inverse function $h(y) = g^{-1}(y)$,

$$h(y) = -\gamma \ln \left(e^{-\alpha y/\gamma} (1 + \beta) - \beta \right) \quad (12.33)$$

The Jacobian is

$$\frac{dh}{dy} = \alpha \left(1 - e^{\alpha y/\gamma} \frac{\beta}{1 + \beta} \right)^{-1} \quad (12.34)$$

which is equal to $1/(dg/dx)$, namely

$$\frac{dg}{dx} = \frac{1}{\alpha} \frac{1}{1 + \beta e^{x/\gamma}} \quad (12.35)$$

The final result is

$$\int_{m_{\min}^2}^{m_{\max}^2} dm^2 F(m^2) = \Delta m^2 \int_0^1 dx F(m^2(x)) \quad (12.36)$$

$$= \Delta m^2 \int_0^1 dy F(m^2(h(y))) \frac{dh}{dy} \quad (12.37)$$

Here is the implementation. We fill `a1`, `a2`, `a3` with α, β, γ , respectively.

```

<Constants for exponential step mapping>≡
  if (map%variable_limits .or. map%a_unknown) then
    map%a3 = max (2 * map%mass * map%width / (msq_max - msq_min), 0.01_default)
    map%a2 = exp (- (map%mass**2 - msq_min) / (msq_max - msq_min) &
                  / map%a3)
    map%a1 = 1 - map%a3 * log ((1 + map%a2 * exp (1 / map%a3)) / (1 + map%a2))
  end if

<Apply exponential step mapping>≡
  tmp = exp (- x * map%a1 / map%a3) * (1 + map%a2)
  z = - map%a3 * log (tmp - map%a2)
  msq = z * msq_max + (1 - z) * msq_min
  f = map%a1 / (1 - map%a2 / tmp) * (msq_max - msq_min) / s

<Apply inverse exponential step mapping>≡
  z = (msq - msq_min) / (msq_max - msq_min)
  tmp = 1 + map%a2 * exp (z / map%a3)
  x = (z - map%a3 * log (tmp / (1 + map%a2))) &
      / map%a1
  f = map%a1 * tmp * (msq_max - msq_min) / s

```

Hyperbolic mapping

The Fermi function has the drawback that it decreases exponentially. It might be preferable to take a function with a power-law decrease, such that the high-mass region is not completely depopulated.

Here, we start with the actual mapping which we take as

$$h(y) = \frac{b}{a - y} - \frac{b}{a} + \mu y \quad (12.38)$$

with the abbreviation

$$a = \frac{1}{2} \left(1 + \sqrt{1 + \frac{4b}{1-\mu}} \right) \quad (12.39)$$

This is a hyperbola in the xy plane. The derivative is

$$\frac{dh}{dy} = \frac{b}{(a-y)^2} + \mu \quad (12.40)$$

The constants correspond to

$$\mu = \frac{m_{\max, \text{eff}}^2 - m_{\min}^2}{\Delta m^2} \quad (12.41)$$

$$b = \frac{1}{\mu} \left(\frac{2m_{\max, \text{eff}} \Gamma}{\Delta m^2} \right)^2 \quad (12.42)$$

The inverse function is the solution of a quadratic equation,

$$g(x) = \frac{1}{2} \left[\left(a + \frac{x}{\mu} + \frac{b}{a\mu} \right) - \sqrt{\left(a - \frac{x}{\mu} \right)^2 + 2 \frac{b}{a\mu} \left(a + \frac{x}{\mu} \right) + \left(\frac{b}{a\mu} \right)^2} \right] \quad (12.43)$$

The constants $a_{1,2,3}$ are identified with a, b, μ .

```

<Constants for hyperbolic step mapping>≡
  if (map%variable_limits .or. map%a_unknown) then
    map%a3 = (map%mass**2 - msq_min) / (msq_max - msq_min)
    map%a2 = max ((2 * map%mass * map%width / (msq_max - msq_min))**2 &
                  / map%a3, 1e-6_default)
    map%a1 = (1 + sqrt (1 + 4 * map%a2 / (1 - map%a3))) / 2
  end if

<Apply hyperbolic step mapping>≡
  z = map%a2 / (map%a1 - x) - map%a2 / map%a1 + map%a3 * x
  msq = z * msq_max + (1 - z) * msq_min
  f = (map%a2 / (map%a1 - x)**2 + map%a3) * (msq_max - msq_min) / s

<Apply inverse hyperbolic step mapping>≡
  z = (msq - msq_min) / (msq_max - msq_min)
  tmp = map%a2 / (map%a1 * map%a3)
  x = ((map%a1 + z / map%a3 + tmp) &
        - sqrt ((map%a1 - z / map%a3)**2 + 2 * tmp * (map%a1 + z / map%a3) &
                + tmp**2)) / 2
  f = (map%a2 / (map%a1 - x)**2 + map%a3) * (msq_max - msq_min) / s

```

12.1.9 Mappings of the polar angle

The other type of singularity, a simple pole just outside the integration region, can occur in the integration over $\cos \theta$. This applies to exchange of massless (or light) particles.

Double poles (Coulomb scattering) are also possible, but only in certain cases. These are also handled by the single-pole mapping.

The mapping is analogous to the previous m^2 pole mapping, but with a different normalization and notation of variables:

$$\frac{1}{2} \int_{-1}^1 d \cos \theta g(\theta) = \int_0^1 dx \frac{d \cos \theta}{dx} g(\theta(x)) = \int_0^1 dx f(x) g(x), \quad (12.44)$$

where thus

$$f(x) = \frac{1}{2} \frac{d \cos \theta}{dx}. \quad (12.45)$$

With this mapping, a function of the form

$$g(\theta) = c \frac{dx(\cos \theta)}{d \cos \theta} \quad (12.46)$$

is mapped to a constant:

$$\int_{-1}^1 d \cos \theta g(\theta) = \int_0^1 dx f(x) g(\theta(x)) = \int_0^1 dx c. \quad (12.47)$$

```

<Mappings: public>+≡
  public :: mapping_compute_ct_from_x

<Mappings: procedures>+≡
  subroutine mapping_compute_ct_from_x (map, s, ct, st, f, x)
    type(mapping_t), intent(inout) :: map
    real(default), intent(in) :: s
    real(default), intent(out) :: ct, st, f
    real(default), intent(in) :: x
    real(default) :: tmp, ct1
    select case (map%type)
    case (NO_MAPPING, S_CHANNEL, INFRARED, RADIATION, &
          STEP_MAPPING_E, STEP_MAPPING_H)
      <Apply trivial ct mapping>
    case (T_CHANNEL, U_CHANNEL, COLLINEAR)
      <Constants for ct pole mapping>
      <Apply ct pole mapping>
    case default
      call msg_fatal (" Attempt to apply undefined ct mapping")
    end select
  end subroutine mapping_compute_ct_from_x

<Mappings: public>+≡
  public :: mapping_compute_x_from_ct

<Mappings: procedures>+≡
  subroutine mapping_compute_x_from_ct (map, s, ct, f, x)
    type(mapping_t), intent(inout) :: map
    real(default), intent(in) :: s
    real(default), intent(in) :: ct
    real(default), intent(out) :: f, x
    real(default) :: ct1
    select case (map%type)
    case (NO_MAPPING, S_CHANNEL, INFRARED, RADIATION, &
          STEP_MAPPING_E, STEP_MAPPING_H)
      <Apply inverse trivial ct mapping>

```

```

case (T_CHANNEL, U_CHANNEL, COLLINEAR)
  <Constants for ct pole mapping>
  <Apply inverse ct pole mapping>
case default
  call msg_fatal (" Attempt to apply undefined inverse ct mapping")
end select
end subroutine mapping_compute_x_from_ct

```

Trivial mapping

This is just the mapping of the interval $(-1, 1)$ to $(0, 1)$:

$$\cos \theta = -1 + 2x \quad (12.48)$$

and

$$f(x) = 1 \quad (12.49)$$

with the inverse

$$x = \frac{1 + \cos \theta}{2} \quad (12.50)$$

```

<Apply trivial ct mapping>≡
  tmp = 2 * (1-x)
  ct = 1 - tmp
  st = sqrt (tmp * (2-tmp))
  f = 1
<Apply inverse trivial ct mapping>≡
  x = (ct + 1) / 2
  f = 1

```

Pole mapping

As above for m^2 , we simultaneously map poles at both ends of the $\cos \theta$ interval. The formulae are completely analogous:

$$\cos \theta = \begin{cases} \frac{M^2}{s} [\exp(xL) - 1] - 1 & \text{for } x < \frac{1}{2} \\ -\frac{M^2}{s} [\exp((1-x)L) - 1] + 1 & \text{for } x \geq \frac{1}{2} \end{cases} \quad (12.51)$$

where

$$L = 2 \ln \frac{M^2 + s}{M^2}. \quad (12.52)$$

Inverse:

$$x = \begin{cases} \frac{1}{2L} \ln \frac{1 + \cos \theta + M^2/s}{M^2/s} & \text{for } \cos \theta < 0 \\ 1 - \frac{1}{2L} \ln \frac{1 - \cos \theta + M^2/s}{M^2/s} & \text{for } \cos \theta \geq 0 \end{cases} \quad (12.53)$$

The phase-space factor:

$$f(x) = \begin{cases} \frac{M^2}{s} \exp(xL) L & \text{for } x < \frac{1}{2} \\ \frac{M^2}{s} \exp((1-x)L) L & \text{for } x \geq \frac{1}{2} \end{cases} \quad (12.54)$$

```

<Constants for ct pole mapping>≡
  if (map%variable_limits .or. map%b_unknown) then

```



```

        map%b1 = map%mass**2 / s
        map%b2 = log ((map%b1 + 1) / map%b1)
        map%b3 = 0
        map%b_unknown = .false.
    end if

    <Apply ct pole mapping>≡
    if (x < .5_default) then
        ct1 = map%b1 * exp (2 * x * map%b2)
        ct = ct1 - map%b1 - 1
    else
        ct1 = map%b1 * exp (2 * (1-x) * map%b2)
        ct = -(ct1 - map%b1) + 1
    end if
    if (ct >= -1 .and. ct <= 1) then
        st = sqrt (1 - ct**2)
        f = ct1 * map%b2
    else
        ct = 1;  st = 0;  f = 0
    end if

    <Apply inverse ct pole mapping>≡
    if (ct < 0) then
        ct1 = ct + map%b1 + 1
        x = log (ct1 / map%b1) / (2 * map%b2)
    else
        ct1 = -ct + map%b1 + 1
        x = 1 - log (ct1 / map%b1) / (2 * map%b2)
    end if
    f = ct1 * map%b2

```

12.2 Phase-space trees

The phase space evaluation is organized in terms of trees, where each branch corresponds to three integrations: m^2 , $\cos\theta$, and ϕ . The complete tree thus makes up a specific parameterization of the multidimensional phase-space integral. For the multi-channel integration, the phase-space tree is a single channel.

The trees imply mappings of formal Feynman tree graphs into arrays of integer numbers: Each branch, corresponding to a particular line in the graph, is assigned an integer code c (with kind value $\text{TC} = \text{tree code}$).

In this integer, each bit determines whether a particular external momentum flows through the line. The external branches therefore have codes 1, 2, 4, 8, ... An internal branch has those bits ORed corresponding to the momenta flowing through it. For example, a branch with momentum $p_1 + p_4$ has code $2^0 + 2^3 = 1 + 8 = 9$.

There is a two-fold ambiguity: Momentum conservation implies that the branch with code

$$c_0 = \sum_{i=1}^{n(\text{ext})} 2^{i-1} \quad (12.55)$$

i.e. the branch with momentum $p_1 + p_2 + \dots p_n$ has momentum zero, which is equivalent to tree code 0 by definition. Correspondingly,

$$c \quad \text{and} \quad c_0 - c = c \text{ XOR } c_0 \quad (12.56)$$

are equivalent. E.g., if there are five externals with codes $c = 1, 2, 4, 8, 16$, then $c = 9$ and $\bar{c} = 31 - 9 = 22$ are equivalent.

This ambiguity may be used to assign a direction to the line: If all momenta are understood as outgoing, $c = 9$ in the example above means $p_1 + p_4$, but $c = 22$ means $p_2 + p_3 + p_5 = -(p_1 + p_4)$.

Here we make use of the ambiguity in a slightly different way. First, the initial particles are singled out as those externals with the highest bits, the IN-bits. (Here: 8 and 16 for a $2 \rightarrow 3$ scattering process, 16 only for a $1 \rightarrow 4$ decay.) Then we invert those codes where all IN-bits are set. For a decay process this maps each tree of an equivalence class onto a unique representative (that one with the smallest integer codes). For a scattering process we proceed further:

The ambiguity remains in all branches where only one IN-bit is set, including the initial particles. If there are only externals with this property, we have an s -channel graph which we leave as it is. In all other cases, an internal with only one IN-bit is a t -channel line, which for phase space integration should be associated with one of the initial momenta as a reference axis. We take that one whose bit is set in the current tree code. (E.g., for branch $c = 9$ we use the initial particle $c = 8$ as reference axis, whereas for the same branch we would take $c = 16$ if it had been assigned $\bar{c} = 31 - 9 = 22$ as tree code.) Thus, different ways of coding the same t -channel graph imply different phase space parameterizations.

s -channel graphs have a unique parameterization. The same sets of parameterizations are used for t -channel graphs, except for the reference frames of their angular parts. We map each t -channel graph onto an s -channel graph as follows:

Working in ascending order, for each t -channel line (whose code has exactly one IN-bit set) the attached initial line is flipped upstream, while the outgoing

line is flipped downstream. (This works only if t -channel graphs are always parameterized beginning at their outer vertices, which we require as a restriction.) After all possible flips have been applied, we have an s -channel graph. We only have to remember the initial particle a vertex was originally attached to.

```

<phs_trees.f90>≡
  <File header>

  module phs_trees

    <Use kinds>
    use kinds, only: TC !NODEP!
    <Use strings>
    use constants, only: twopi, twopi2, twopi5 !NODEP!
    <Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use permutations, only: permutation_t, permutation_size
    use permutations, only: permutation_init, permutation_find
    use permutations, only: tc_decay_level, tc_permute
    use models
    use flavors
    use mappings

    <Standard module head>

    <PHS trees: public>

    <PHS trees: types>

    contains

    <PHS trees: procedures>

  end module phs_trees

```

12.2.1 Particles

We define a particle type which contains only four-momentum and invariant mass squared, and a flag that tells whether the momentum is filled or not.

```

<PHS trees: public>≡
  public :: phs_prt_t

<PHS trees: types>≡
  type :: phs_prt_t
  private
    logical :: defined = .false.
    type(vector4_t) :: p
    real(default) :: p2
  end type phs_prt_t

```

Set contents:

```

<PHS trees: public>+≡
  public :: phs_prt_set_defined

```

```

public :: phs_prt_set_undefined
public :: phs_prt_set_momentum
public :: phs_prt_set_msq

<PHS trees: procedures>≡
elemental subroutine phs_prt_set_defined (prt)
  type(phs_prt_t), intent(inout) :: prt
  prt%defined = .true.
end subroutine phs_prt_set_defined

elemental subroutine phs_prt_set_undefined (prt)
  type(phs_prt_t), intent(inout) :: prt
  prt%defined = .false.
end subroutine phs_prt_set_undefined

elemental subroutine phs_prt_set_momentum (prt, p)
  type(phs_prt_t), intent(inout) :: prt
  type(vector4_t), intent(in) :: p
  prt%p = p
end subroutine phs_prt_set_momentum

elemental subroutine phs_prt_set_msq (prt, p2)
  type(phs_prt_t), intent(inout) :: prt
  real(default), intent(in) :: p2
  prt%p2 = p2
end subroutine phs_prt_set_msq

```

Access methods:

```

<PHS trees: public>+≡
public :: phs_prt_is_defined
public :: phs_prt_get_momentum
public :: phs_prt_get_msq

<PHS trees: procedures>+≡
elemental function phs_prt_is_defined (prt) result (defined)
  logical :: defined
  type(phs_prt_t), intent(in) :: prt
  defined = prt%defined
end function phs_prt_is_defined

elemental function phs_prt_get_momentum (prt) result (p)
  type(vector4_t) :: p
  type(phs_prt_t), intent(in) :: prt
  p = prt%p
end function phs_prt_get_momentum

elemental function phs_prt_get_msq (prt) result (p2)
  real(default) :: p2
  type(phs_prt_t), intent(in) :: prt
  p2 = prt%p2
end function phs_prt_get_msq

```

Addition of momenta (invariant mass square is computed).

```

<PHS trees: public>+≡

```

```

public :: phs_prt_combine
<PHS trees: procedures>+≡
elemental subroutine phs_prt_combine (prt, prt1, prt2)
  type(phs_prt_t), intent(inout) :: prt
  type(phs_prt_t), intent(in) :: prt1, prt2
  prt%defined = .true.
  prt%p = prt1%p + prt2%p
  prt%p2 = prt%p ** 2
end subroutine phs_prt_combine

```

Output

```

<PHS trees: public>+≡
public :: phs_prt_write
<PHS trees: procedures>+≡
subroutine phs_prt_write (prt, unit)
  type(phs_prt_t), intent(in) :: prt
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  if (prt%defined) then
    call vector4_write (prt%p, u)
    write (u, *) "M2 =", prt%p2
  else
    write (u, *) "[undefined]"
  end if
end subroutine phs_prt_write

```

12.2.2 The phase-space tree type

Definition

In the concrete implementation, each branch c may have two *daughters* c_1 and c_2 such that $c_1 + c_2 = c$, a *sibling* c_s and a *mother* c_m such that $c + c_s = c_m$, and a *friend* which is kept during flips, such that it can indicate a fixed reference frame. Absent entries are set $c = 0$.

First, declare the branch type. There is some need to have this public. Give initializations for all components, so no `init` routine is necessary. The branch has some information about the associated coordinates and about connections.

```

<PHS trees: types>+≡
type :: phs_branch_t
  private
  logical :: set = .false.
  logical :: inverted_decay = .false.
  logical :: inverted_axis = .false.
  integer(TC) :: mother = 0
  integer(TC) :: sibling = 0
  integer(TC) :: friend = 0
  integer(TC) :: origin = 0
  integer(TC), dimension(2) :: daughter = 0
  integer :: firstborn = 0

```

```

        logical :: has_children = .false.
        logical :: has_friend = .false.
    end type phs_branch_t

```

The tree type: No initialization, this is done by `phs_tree_init`. In addition to the branch array which

The branches are collected in an array which holds all possible branches, of which only a few are set. After flips have been applied, the branch $c_M = \sum_{i=1}^{n(\text{fin})} 2^{i-1}$ must be there, indicating the mother of all decay products. In addition, we should check for consistency at the beginning.

`n_branches` is the number of those actually set. `n externals` defines the number of significant bit, and `mask` is a code where all bits are set. Analogous: `n_in` and `mask_in` for the incoming particles.

The mapping array contains the mappings associated to the branches (corresponding indices). The array `mass_sum` contains the sum of the real masses of the external final-state particles associated to the branch. During phase-space evaluation, this determines the boundaries.

```

<PHS trees: public>+≡
    public :: phs_tree_t

<PHS trees: types>+≡
    type :: phs_tree_t
        private
        integer :: n_branches, n externals, n_in, n_msq, n_angles
        integer(TC) :: n_branches_tot, n_branches_out
        integer(TC) :: mask, mask_in, mask_out
        type(phs_branch_t), dimension(:), allocatable :: branch
        type(mapping_t), dimension(:), allocatable :: mapping
        real(default), dimension(:), allocatable :: mass_sum
        real(default), dimension(:), allocatable :: effective_mass
        real(default), dimension(:), allocatable :: effective_width
    end type phs_tree_t

```

The maximum number of external particles that can be represented is related to the bit size of the integer that stores binary codes. With the default integer of 32 bit on common machines, this is more than enough space. If TC is actually the default integer kind, there is no need to keep it separate, but doing so marks this as a special type of integer. So, just state that the maximum number is 32:

```

<Limits: public parameters>+≡
    integer, parameter, public :: MAX_EXTERNAL = 32

```

Constructor and destructor

Allocate memory for a phase-space tree with given number of externals and incoming. The number of allocated branches can easily become large, but appears manageable for realistic cases, e.g., for `n_in=2` and `n_out=8` we get $2^{10} - 1 = 1023$.

```

<PHS trees: public>+≡
    public :: phs_tree_init
    public :: phs_tree_final

```

Here we set the masks for incoming and for all externals.

```

<PHS trees: procedures>+≡
  elemental subroutine phs_tree_init (tree, n_in, n_out, n_masses, n_angles)
    type(phs_tree_t), intent(inout) :: tree
    integer, intent(in) :: n_in, n_out, n_masses, n_angles
    integer(TC) :: i
    tree%n_externals = n_in + n_out
    tree%n_branches_tot = 2**(n_in+n_out) - 1
    tree%n_branches_out = 2**n_out - 1
    tree%mask = 0
    do i = 0, n_in + n_out - 1
      tree%mask = ibset (tree%mask, i)
    end do
    tree%n_in = n_in
    tree%mask_in = 0
    do i = n_out, n_in + n_out - 1
      tree%mask_in = ibset (tree%mask_in, i)
    end do
    tree%mask_out = ieor (tree%mask, tree%mask_in)
    tree%n_msq = n_masses
    tree%n_angles = n_angles
    allocate (tree%branch (tree%n_branches_tot))
    tree%n_branches = 0
    allocate (tree%mapping (tree%n_branches_out))
    allocate (tree%mass_sum (tree%n_branches_out))
    allocate (tree%effective_mass (tree%n_branches_out))
    allocate (tree%effective_width (tree%n_branches_out))
  end subroutine phs_tree_init

  elemental subroutine phs_tree_final (tree)
    type(phs_tree_t), intent(inout) :: tree
    deallocate (tree%branch)
    deallocate (tree%mapping)
    deallocate (tree%mass_sum)
    deallocate (tree%effective_mass)
    deallocate (tree%effective_width)
  end subroutine phs_tree_final

```

Screen output

Write only the branches that are set:

```

<PHS trees: public>+≡
  public :: phs_tree_write

<PHS trees: procedures>+≡
  subroutine phs_tree_write (tree, unit)
    type(phs_tree_t), intent(in) :: tree
    integer, intent(in), optional :: unit
    integer :: u
    integer(TC) :: k
    u = output_unit (unit); if (u < 0) return
    write (u, '(1X,A,I2,5X,A,I3)') &
      'External:', tree%n_externals, 'Mask:', tree%mask
  end subroutine phs_tree_write

```

```

write (u,'(1X,A,I2,5X,A,I3)') &
    'Incoming:', tree%n_in, 'Mask:', tree%mask_in
write (u,'(1X,A,I2,5X,A,I3)') &
    'Branches:', tree%n_branches
do k = size (tree%branch), 1, -1
    if (tree%branch(k)%set) &
        call phs_branch_write (tree%branch(k), unit=unit, kval=k)
end do
do k = 1, size (tree%mapping)
    call mapping_write (tree%mapping (k), unit, verbose=.true.)
end do
write (u, *) "Arrays: mass_sum, effective_mass, effective_width"
do k = 1, size (tree%mass_sum)
    if (tree%branch(k)%set) then
        write (u, *) " ", k, tree%mass_sum(k), &
            tree%effective_mass(k), tree%effective_width(k)
    end if
end do
end subroutine phs_tree_write

subroutine phs_branch_write (b, unit, kval)
    type(phs_branch_t), intent(in) :: b
    integer, intent(in), optional :: unit
    integer(TC), intent(in), optional :: kval
    integer :: u
    integer(TC) :: k
    character(len=6) :: tmp
    character(len=1) :: firstborn(2), sign_decay, sign_axis
    integer :: i
    u = output_unit (unit); if (u < 0) return
    k = 0; if (present (kval)) k = kval
    if (b%origin /= 0) then
        write(tmp, '(A,I4,A)') '(', b%origin, ')'
    else
        tmp = ' '
    end if
    do i=1, 2
        if (b%firstborn == i) then
            firstborn(i) = "*"
        else
            firstborn(i) = " "
        end if
    end do
    if (b%inverted_decay) then
        sign_decay = "-"
    else
        sign_decay = "+"
    end if
    if (b%inverted_axis) then
        sign_axis = "-"
    else
        sign_axis = "+"
    end if
    if (b%has_children) then

```



```

        if (b%has_friend) then
            write(u,'(1X,A,I4,1x,A,2X,A,I4,A,I4,A,2X,A,3X,A,I4)') &
                & ' ', k, tmp, &
                & 'Daughters: ', &
                & b%daughter(1), firstborn(1), &
                & b%daughter(2), firstborn(2), sign_decay, &
                & 'Friend: ', b%friend
        else
            write(u,'(1X,A,I4,1x,A,2X,A,I4,A,I4,A,2X,A,2X,A)') &
                & ' ', k, tmp, &
                & 'Daughters: ', &
                & b%daughter(1), firstborn(1), &
                & b%daughter(2), firstborn(2), sign_decay, &
                & '(axis '//sign_axis//')'
        end if
    else
        write(u,'(2X,I4,3X,A,I4,I4)') k
    end if
end subroutine phs_branch_write

```

12.2.3 PHS tree setup

Transformation into an array of branch codes and back

Assume that the tree/array has been created before with the appropriate length and is empty.

```

<PHS trees: public>+≡
    public :: phs_tree_from_array

<PHS trees: procedures>+≡
    subroutine phs_tree_from_array (tree, a)
        type(phs_tree_t), intent(inout) :: tree
        integer(TC), dimension(:), intent(in) :: a
        integer :: i
        integer(TC) :: k
        <Set branches from array a>
        <Set external branches if necessary>
        <Check number of branches>
        <Determine the connections>
    contains
        <Subroutine: set relatives>
    end subroutine phs_tree_from_array

```

First, set all branches specified by the user. If all IN-bits are set, we invert the branch code.

```

<Set branches from array a>≡
    do i=1, size(a)
        k = a(i)
        if (iand(k, tree%mask_in) == tree%mask_in) k = ieor(tree%mask, k)
        tree%branch(k)%set = .true.
        tree%n_branches = tree%n_branches+1
    end do

```

The external branches are understood, so set them now if not yet done. In all cases ensure that the representative with one bit set is used, except for decays where the in-particle is represented by all OUT-bits set instead.

```

<Set external branches if necessary>≡
do i=0, tree%n_externals-1
  k = ibset(0,i)
  if (iand(k, tree%mask_in) == tree%mask_in) k = ieor(tree%mask, k)
  if (tree%branch(ieor(tree%mask, k))%set) then
    tree%branch(ieor(tree%mask, k))%set = .false.
    tree%branch(k)%set = .true.
  else if (.not.tree%branch(k)%set) then
    tree%branch(k)%set = .true.
    tree%n_branches = tree%n_branches+1
  end if
end do

```

Now the number of branches set can be checked. Here we assume that the tree is binary. For three externals there are three branches in total, and for each additional external branch we get another internal one.

```

<Check number of branches>≡
if (tree%n_branches /= tree%n_externals*2-3) then
  call phs_tree_write (tree)
  call msg_bug &
    & (" Wrong number of branches set in phase space tree")
end if

```

For all branches that are set, except for the externals, we try to find the daughter branches:

```

<Determine the connections>≡
do k=1, size (tree%branch)
  if (tree%branch(k)%set .and. tc_decay_level (k) /= 1) then
    call branch_set_relatives(k)
  end if
end do

```

To this end, we scan all codes less than the current code, whether we can find two branches which are set and which together give the current code. After that, the tree may still not be connected, but at least we know if a branch does not have daughters: This indicates some inconsistency.

The algorithm ensures that, at this stage, the first daughter has a smaller code value than the second one.

```

<Subroutine: set relatives>≡
subroutine branch_set_relatives (k)
  integer(TC), intent(in) :: k
  integer(TC) :: m,n
  do m=1, k-1
    if(iand(k,m)==m) then
      n = ieor(k,m)
      if ( tree%branch(m)%set .and. tree%branch(n)%set ) then
        tree%branch(k)%daughter(1) = m; tree%branch(k)%daughter(2) = n
        tree%branch(m)%mother      = k; tree%branch(n)%mother      = k
        tree%branch(m)%sibling      = n; tree%branch(n)%sibling      = m
        tree%branch(k)%has_children = .true.
      return
    end if
  end do
end subroutine

```

```

        end if
    end if
end do
call phs_tree_write (tree)
call msg_bug &
    & (" Missing daughter branch(es) in phase space tree")
end subroutine branch_set_relatives

```

The inverse: this is trivial, fortunately.

Flip t -channel into s -channel

Flipping the tree is done upwards, beginning from the decay products. First we select a t -channel branch k : one which is set, which does have an IN-bit, and which is not an external particle.

Next, we determine the adjacent in-particle (called the 'friend' f here, since it will provide the reference axis for the angular integration). In addition, we look for the 'mother' and 'sibling' of this particle. If the latter field is empty, we select the (unique) other out-particle which has no mother, calling the internal subroutine `find_orphan`.

The flip is done as follows: We assume that the first daughter d is an s -channel line, which is true if the daughters are sorted. This will stay the first daughter. The second one is a t -channel line; it is exchanged with the 'sibling' s . The new line which replaces the branch k is just the sum of s and d . In addition, we have to rearrange the relatives of s and d , as well of f .

Finally, we flip 'sibling' and 'friend' and set the new s -channel branch n which replaces the t -channel branch k . After this is complete, we are ready to execute another flip.

[Although the friend is not needed for the final flip, since it would be an initial particle anyway, we need to know whether we have t - or u -channel.]

```

<PHS trees: public>+≡
    public :: phs_tree_flip_t_to_s_channel

<PHS trees: procedures>+≡
    subroutine phs_tree_flip_t_to_s_channel (tree)
        type(phs_tree_t), intent(inout) :: tree
        integer(TC) :: k, f, m, n, d, s
        if (tree%n_in == 2) then
            FLIP: do k=3, tree%mask-1
                if (.not. tree%branch(k)%set) cycle FLIP
                f = iand(k,tree%mask_in)
                if (f==0 .or. f==k) cycle FLIP
                m = tree%branch(k)%mother
                s = tree%branch(k)%sibling
                if (s==0) call find_orphan(s)
                d = tree%branch(k)%daughter(1)
                n = ior(d,s)
                tree%branch(k)%set = .false.
                tree%branch(n)%set = .true.
                tree%branch(n)%origin = k
                tree%branch(n)%daughter(1) = d; tree%branch(d)%mother = n
                tree%branch(n)%daughter(2) = s; tree%branch(s)%mother = n
            end do
        end if
    end subroutine

```

```

        tree%branch(n)%has_children = .true.
        tree%branch(d)%sibling = s; tree%branch(s)%sibling = d
        tree%branch(n)%sibling = f; tree%branch(f)%sibling = n
        tree%branch(n)%mother      = m
        tree%branch(f)%mother      = m
        if (m/=0) then
            tree%branch(m)%daughter(1) = n
            tree%branch(m)%daughter(2) = f
        end if
        tree%branch(n)%friend = f
        tree%branch(n)%has_friend = .true.
        tree%branch(n)%firstborn = 2
    end do FLIP
end if
contains
    subroutine find_orphan(s)
        integer(TC) :: s
        do s=1, tree%mask_out
            if (tree%branch(s)%set .and. tree%branch(s)%mother==0) return
        end do
        call phs_tree_write (tree)
        call msg_bug (" Can't flip phase space tree to channel")
    end subroutine find_orphan
end subroutine phs_tree_flip_t_to_s_channel

```

After the tree has been flipped, one may need to determine what has become of a particular t -channel branch. This function gives the bincode of the flipped tree. If the original bincode does not contain IN-bits, we leave it as it is.

(PHS trees: procedures)+≡

```

function tc_flipped (tree, kt) result (ks)
    type(phs_tree_t), intent(in) :: tree
    integer(TC), intent(in) :: kt
    integer(TC) :: ks
    if (iand (kt, tree%mask_in) == 0) then
        ks = kt
    else
        ks = tree%branch(iand (kt, tree%mask_out))%mother
    end if
end function tc_flipped

```

Scan a tree and make sure that the first daughter has always a smaller code than the second one. Furthermore, delete any `friend` entry in the root branch – this branching has the incoming particle direction as axis anyway. Keep track of reordering by updating `inverted_axis`, `inverted_decay` and `firstborn`.

(PHS trees: public)+≡

```

public :: phs_tree_canonicalize

```

(PHS trees: procedures)+≡

```

subroutine phs_tree_canonicalize (tree)
    type(phs_tree_t), intent(inout) :: tree
    integer :: n_out
    integer(TC) :: k_out
    call branch_canonicalize (tree%branch(tree%mask_out))

```

```

n_out = tree%n_externals - tree%n_in
k_out = tree%mask_out
if (tree%branch(k_out)%has_friend &
    & .and. tree%branch(k_out)%friend == ibset (0, n_out)) then
    tree%branch(k_out)%inverted_axis = .not.tree%branch(k_out)%inverted_axis
end if
tree%branch(k_out)%has_friend = .false.
tree%branch(k_out)%friend = 0
contains
recursive subroutine branch_canonicalize (b)
    type(phs_branch_t), intent(inout) :: b
    integer(TC) :: d1, d2
    if (b%has_children) then
        d1 = b%daughter(1)
        d2 = b%daughter(2)
        if (d1 > d2) then
            b%daughter(1) = d2
            b%daughter(2) = d1
            b%inverted_decay = .not.b%inverted_decay
            if (b%firstborn /= 0) b%firstborn = 3 - b%firstborn
        end if
        call branch_canonicalize (tree%branch(b%daughter(1)))
        call branch_canonicalize (tree%branch(b%daughter(2)))
    end if
end subroutine branch_canonicalize
end subroutine phs_tree_canonicalize

```

Mappings

Initialize a mapping for the current tree. This is done while reading from file, so the mapping parameters are read, but applied to the flipped tree. Thus, the size of the array of mappings is given by the number of outgoing particles only.

```

<PHS trees: public>+≡
    public :: phs_tree_init_mapping

<PHS trees: procedures>+≡
    subroutine phs_tree_init_mapping (tree, k, type, pdg, model)
        type(phs_tree_t), intent(inout) :: tree
        integer(TC), intent(in) :: k
        type(string_t), intent(in) :: type
        integer, intent(in) :: pdg
        type(model_t), intent(in), target :: model
        integer(TC) :: kk
        kk = tc_flipped (tree, k)
        call mapping_init (tree%mapping(kk), kk, type, pdg, model)
    end subroutine phs_tree_init_mapping

```

Set the physical parameters for the mapping, using a specific parameter set. Also set the mass sum array.

```

<PHS trees: public>+≡
    public :: phs_tree_set_mapping_parameters

```

```

<PHS trees: procedures>+≡
  subroutine phs_tree_set_mapping_parameters &
    (tree, mapping_defaults, variable_limits)
    type(phs_tree_t), intent(inout) :: tree
    type(mapping_defaults_t), intent(in) :: mapping_defaults
    logical, intent(in) :: variable_limits
    integer(TC) :: k
    do k = 1, tree%n_branches_out
      call mapping_set_parameters &
        (tree%mapping(k), mapping_defaults, variable_limits)
    end do
  end subroutine phs_tree_set_mapping_parameters

```

Return the mapping for the sum of all outgoing particles. This should either be no mapping or a global s-channel mapping.

```

<PHS trees: public>+≡
  public :: phs_tree_assign_s_mapping

<PHS trees: procedures>+≡
  subroutine phs_tree_assign_s_mapping (tree, mapping)
    type(phs_tree_t), intent(in) :: tree
    type(mapping_t), intent(out) :: mapping
    mapping = tree%mapping(tree%mask_out)
  end subroutine phs_tree_assign_s_mapping

```

Kinematics

Fill the mass sum array, starting from the external particles and working down to the tree root. For each bincode k we scan the bits in k ; if only one is set, we take the physical mass of the corresponding external particle; if more than one is set, we sum up the two masses (which we know have already been set).

```

<PHS trees: public>+≡
  public :: phs_tree_set_mass_sum

<PHS trees: procedures>+≡
  subroutine phs_tree_set_mass_sum (tree, flv)
    type(phs_tree_t), intent(inout) :: tree
    type(flavor_t), dimension(:), intent(in) :: flv
    integer(TC) :: k
    integer :: i
    tree%mass_sum = 0
    do k = 1, tree%n_branches_out
      do i = 0, size(flv) - 1
        if (btest(k,i)) then
          if (ibclr(k,i) == 0) then
            tree%mass_sum(k) = flavor_get_mass (flv(i+1))
          else
            tree%mass_sum(k) = &
              tree%mass_sum(ibclr(k,i)) + tree%mass_sum(ibset(0,i))
          end if
        end if
      end do
    end do
  end subroutine phs_tree_set_mass_sum

```

```

        end do
    end do
end subroutine phs_tree_set_mass_sum

```

Set the effective masses and widths. For each non-resonant branch in a tree, the effective mass is equal to the sum of the effective masses of the children (and analogous for the width). External particles have their real mass and width zero. For resonant branches, we insert mass and width from the corresponding mapping.

This routine has `phs_tree_set_mass_sum` and `phs_tree_set_mapping_parameters` as prerequisites.

(PHS trees: public)+≡

```

public :: phs_tree_set_effective_masses

```

(PHS trees: procedures)+≡

```

subroutine phs_tree_set_effective_masses (tree)
    type(phs_tree_t), intent(inout) :: tree
    integer(TC) :: k
    tree%effective_mass = 0
    tree%effective_width = 0
    call set_masses_x (tree%mask_out)
contains
    recursive subroutine set_masses_x (k)
        integer(TC), intent(in) :: k
        integer(TC) :: k1, k2
        if (tree%branch(k)%has_children) then
            k1 = tree%branch(k)%daughter(1)
            k2 = tree%branch(k)%daughter(2)
            call set_masses_x (k1)
            call set_masses_x (k2)
            if (mapping_is_s_channel (tree%mapping(k))) then
                tree%effective_mass(k) = mapping_get_mass (tree%mapping(k))
                tree%effective_width(k) = mapping_get_width (tree%mapping(k))
            else
                tree%effective_mass(k) = &
                    tree%effective_mass(k1) + tree%effective_mass(k2)
                tree%effective_width(k) = &
                    tree%effective_width(k1) + tree%effective_width(k2)
            end if
        else
            tree%effective_mass(k) = tree%mass_sum(k)
        end if
    end subroutine set_masses_x
end subroutine phs_tree_set_effective_masses

```

Define step mappings, recursively, for the decay products of all intermediate resonances. Step mappings account for the fact that a branch may originate from a resonance, which almost replaces the upper limit on the possible invariant mass. The step mapping implements a smooth cutoff that interpolates between the resonance and the real kinematic limit. The mapping width determines the sharpness of the cutoff.

Step mappings are inserted only for branches that are not mapped otherwise.

At each branch, we record the mass that is effectively available for phase space, by taking the previous limit and subtracting the effective mass of the sibling branch. Widths are added, not subtracted.

If we encounter a resonance decay, we discard the previous limit and replace it by the mass and width of the resonance, also subtracting the sibling branch.

Initially, the limit is zero, so it becomes negative at any branch. Only if there is a resonance, the limit becomes positive. Whenever the limit is positive, and the current branch decays, we activate a step mapping for the current branch.

As a result, step mappings are implemented for all internal lines that originate from an intermediate resonance decay.

The flag `variable_limits` applies to the ultimate limit from the available energy, not to the intermediate resonances whose masses are always fixed.

This routine requires `phs_tree_set_effective_masses`

```

<PHS trees: public>+≡
  public :: phs_tree_set_step_mappings

<PHS trees: procedures>+≡
  subroutine phs_tree_set_step_mappings (tree, exp_type, variable_limits)
    type(phs_tree_t), intent(inout) :: tree
    logical, intent(in) :: exp_type
    logical, intent(in) :: variable_limits
    type(string_t) :: map_str
    integer(TC) :: k, k_res
    if (exp_type) then
      map_str = "step_exp"
    else
      map_str = "step_hyp"
    end if
    k = tree%mask_out
    k_res = 0
    call set_step_mappings_x (k, 0._default, 0._default)
contains
    recursive subroutine set_step_mappings_x (k, m_limit, w_limit)
      integer(TC), intent(in) :: k
      real(default), intent(in) :: m_limit, w_limit
      integer(TC), dimension(2) :: kk
      real(default), dimension(2) :: m, w
      if (tree%branch(k)%has_children) then
        if (m_limit > 0) then
          if (.not. mapping_is_set (tree%mapping(k))) then
            call mapping_init (tree%mapping(k), k, map_str)
            call mapping_set_step_mapping_parameters (tree%mapping(k), &
              m_limit, w_limit, &
              variable_limits)
          end if
        end if
        kk = tree%branch(k)%daughter
        m = tree%effective_mass(kk)
        w = tree%effective_width(kk)
        if (mapping_is_s_channel (tree%mapping(k))) then
          call set_step_mappings_x (kk(1), &
            mapping_get_mass (tree%mapping(k)) - m(2), &
            mapping_get_width (tree%mapping(k)) + w(2))
        end if
      end if
    end subroutine set_step_mappings_x
  end subroutine phs_tree_set_step_mappings

```



```

        call set_step_mappings_x (kk(2), &
            mapping_get_mass (tree%mapping(k)) - m(1), &
            mapping_get_width (tree%mapping(k)) + w(1))
    else if (m_limit > 0) then
        call set_step_mappings_x (kk(1), &
            m_limit - m(2), &
            w_limit + w(2))
        call set_step_mappings_x (kk(2), &
            m_limit - m(1), &
            w_limit + w(1))
    else
        call set_step_mappings_x (kk(1), &
            - m(2), &
            + w(2))
        call set_step_mappings_x (kk(2), &
            - m(1), &
            + w(1))
    end if
end if
end subroutine set_step_mappings_x
end subroutine phs_tree_set_step_mappings

```

Structural comparison

This function allows to check whether one tree is the permutation of another one. The permutation is applied to the second tree in the argument list. We do not make up a temporary permuted tree, but compare the two trees directly. The branches are scanned recursively, where for each daughter we check the friend and the mapping as well. Once a discrepancy is found, the recursion is exited immediately.

```

<PHS trees: public>+≡
    public :: phs_tree_equivalent

<PHS trees: procedures>+≡
    function phs_tree_equivalent (t1, t2, perm) result (is_equal)
        type(phs_tree_t), intent(in) :: t1, t2
        type(permutation_t), intent(in) :: perm
        logical :: equal, is_equal
        integer(TC) :: k1, k2, mask_in
        k1 = t1%mask_out
        k2 = t2%mask_out
        mask_in = t1%mask_in
        equal = .true.
        call check (t1%branch(k1), t2%branch(k2), k1, k2)
        is_equal = equal
    contains
        recursive subroutine check (b1, b2, k1, k2)
            type(phs_branch_t), intent(in) :: b1, b2
            integer(TC), intent(in) :: k1, k2
            integer(TC), dimension(2) :: d1, d2, pd2
            integer :: i
            if (.not.b1%has_friend .and. .not.b2%has_friend) then
                equal = .true.
            end if
        end subroutine check
    end function phs_tree_equivalent

```

```

else if (b1%has_friend .and. b2%has_friend) then
  equal = (b1%friend == tc_permute (b2%friend, perm, mask_in))
end if
if (equal) then
  if (b1%has_children .and. b2%has_children) then
    d1 = b1%daughter
    d2 = b2%daughter
    do i=1, 2
      pd2(i) = tc_permute (d2(i), perm, mask_in)
    end do
    if (d1(1)==pd2(1) .and. d1(2)==pd2(2)) then
      equal = (b1%firstborn == b2%firstborn)
      if (equal) call check &
        &      (t1%branch(d1(1)), t2%branch(d2(1)), d1(1), d2(1))
      if (equal) call check &
        &      (t1%branch(d1(2)), t2%branch(d2(2)), d1(2), d2(2))
    else if (d1(1)==pd2(2) .and. d1(2)==pd2(1)) then
      equal = ( (b1%firstborn == 0 .and. b2%firstborn == 0) &
        &      .or. (b1%firstborn == 3 - b2%firstborn) )
      if (equal) call check &
        &      (t1%branch(d1(1)), t2%branch(d2(2)), d1(1), d2(2))
      if (equal) call check &
        &      (t1%branch(d1(2)), t2%branch(d2(1)), d1(2), d2(1))
    else
      equal = .false.
    end if
  end if
end if
if (equal) then
  equal = (t1%mapping(k1) == t2%mapping(k2))
end if
end subroutine check
end function phs_tree_equivalent

```

Scan two decay trees and determine the correspondence of mass variables, i.e., the permutation that transfers the ordered list of mass variables belonging to the second tree into the first one. Mass variables are assigned beginning from branches and ending at the root.

<PHS trees: public>+≡

```
public :: phs_tree_find_msq_permutation
```

<PHS trees: procedures>+≡

```

subroutine phs_tree_find_msq_permutation (tree1, tree2, perm2, msq_perm)
  type(phs_tree_t), intent(in) :: tree1, tree2
  type(permutation_t), intent(in) :: perm2
  type(permutation_t), intent(out) :: msq_perm
  type(permutation_t) :: perm1
  integer(TC) :: mask_in, root
  integer(TC), dimension(:), allocatable :: index1, index2
  integer :: i
  allocate (index1 (tree1%n_msq), index2 (tree2%n_msq))
  call permutation_init (perm1, permutation_size (perm2))
  mask_in = tree1%mask_in
  root = tree1%mask_out

```

```

i = 0
call tree_scan (tree1, root, perm1, index1)
i = 0
call tree_scan (tree2, root, perm2, index2)
call permutation_find (msq_perm, index1, index2)
contains
recursive subroutine tree_scan (tree, k, perm, index)
  type(phs_tree_t), intent(in) :: tree
  integer(TC), intent(in) :: k
  type(permutation_t), intent(in) :: perm
  integer, dimension(:), intent(inout) :: index
  if (tree%branch(k)%has_children) then
    call tree_scan (tree, tree%branch(k)%daughter(1), perm, index)
    call tree_scan (tree, tree%branch(k)%daughter(2), perm, index)
    i = i + 1
    if (i <= size (index)) index(i) = tc_permute (k, perm, mask_in)
  end if
end subroutine tree_scan
end subroutine phs_tree_find_msq_permutation

```

<PHS trees: public>+≡

```
public :: phs_tree_find_angle_permutation
```

<PHS trees: procedures>+≡

```

subroutine phs_tree_find_angle_permutation &
  (tree1, tree2, perm2, angle_perm, sig2)
  type(phs_tree_t), intent(in) :: tree1, tree2
  type(permutation_t), intent(in) :: perm2
  type(permutation_t), intent(out) :: angle_perm
  logical, dimension(:), allocatable, intent(out) :: sig2
  type(permutation_t) :: perm1
  integer(TC) :: mask_in, root
  integer(TC), dimension(:), allocatable :: index1, index2
  logical, dimension(:), allocatable :: sig1
  integer :: i
  allocate (index1 (tree1%n_angles), index2 (tree2%n_angles))
  allocate (sig1 (tree1%n_angles), sig2 (tree2%n_angles))
  call permutation_init (perm1, permutation_size (perm2))
  mask_in = tree1%mask_in
  root = tree1%mask_out
  i = 0
  call tree_scan (tree1, root, perm1, index1, sig1)
  i = 0
  call tree_scan (tree2, root, perm2, index2, sig2)
  call permutation_find (angle_perm, index1, index2)
contains
recursive subroutine tree_scan (tree, k, perm, index, sig)
  type(phs_tree_t), intent(in) :: tree
  integer(TC), intent(in) :: k
  type(permutation_t), intent(in) :: perm
  integer, dimension(:), intent(inout) :: index
  logical, dimension(:), intent(inout) :: sig
  integer(TC) :: k1, k2, kp
  logical :: s

```

```

    if (tree%branch(k)%has_children) then
      k1 = tree%branch(k)%daughter(1)
      k2 = tree%branch(k)%daughter(2)
      s = (tc_permute(k1, perm, mask_in) < tc_permute(k2, perm, mask_in))
      kp = tc_permute (k, perm, mask_in)
      i = i + 1
      index(i) = kp
      sig(i) = s
      i = i + 1
      index(i) = - kp
      sig(i) = s
      call tree_scan (tree, k1, perm, index, sig)
      call tree_scan (tree, k2, perm, index, sig)
    end if
  end subroutine tree_scan
end subroutine phs_tree_find_angle_permutation

```

12.2.4 Phase-space evaluation

Determine momenta

This is done in two steps: First the masses are determined. This step may fail, in which case `ok` is set to false. If successful, we generate angles and the actual momenta. The array `decay_p` serves for transferring the individual three-momenta of the daughter particles in their mother rest frame from the mass generation to the momentum generation step.

```

<PHS trees: public>+≡
  public :: phs_tree_compute_momenta_from_x

<PHS trees: procedures>+≡
  subroutine phs_tree_compute_momenta_from_x &
    (tree, prt, factor, volume, sqrts, x, ok)
    type(phs_tree_t), intent(inout) :: tree
    type(phs_prt_t), dimension(:), intent(inout) :: prt
    real(default), intent(out) :: factor, volume
    real(default), intent(in) :: sqrts
    real(default), dimension(:), intent(in) :: x
    logical, intent(out) :: ok
    real(default), dimension(tree%mask_out) :: decay_p
    integer :: n1, n2
    n1 = tree%n_msq
    n2 = n1 + tree%n_angles
    call phs_tree_set_msq &
      (tree, prt, factor, volume, decay_p, sqrts, x(1:n1), ok)
    if (ok) call phs_tree_set_angles &
      (tree, prt, factor, decay_p, sqrts, x(n1+1:n2))
  end subroutine phs_tree_compute_momenta_from_x

```

Mass generation is done recursively. The `ok` flag causes the filled tree to be discarded if set to `.false..` This happens if a three-momentum turns out to be imaginary, indicating impossible kinematics. The index `ix` tells us how far we

have used up the input array x.

(PHS trees: procedures)+≡

```

subroutine phs_tree_set_msq &
  (tree, prt, factor, volume, decay_p, sqrts, x, ok)
  type(phs_tree_t), intent(inout) :: tree
  type(phs_prt_t), dimension(:), intent(inout) :: prt
  real(default), intent(out) :: factor, volume
  real(default), dimension(:), intent(out) :: decay_p
  real(default), intent(in) :: sqrts
  real(default), dimension(:), intent(in) :: x
  logical, intent(out) :: ok
  integer :: ix
  integer(TC) :: k
  real(default) :: m_tot
  ok = .true.
  ix = 1
  k = tree%mask_out
  m_tot = tree%mass_sum(k)
  decay_p(k) = 0.
  if (m_tot < sqrts .or. k == 1) then
    if (tree%branch(k)%has_children) then
      call set_msq_x (tree%branch(k), k, factor, volume, .true.)
    else
      factor = 1
      volume = 1
    end if
  else
    ok = .false.
  end if
contains
recursive subroutine set_msq_x (b, k, factor, volume, initial)
  type(phs_branch_t), intent(in) :: b
  integer(TC), intent(in) :: k
  real(default), intent(out) :: factor, volume
  logical, intent(in) :: initial
  real(default) :: msq, m, m_min, m_max, m1, m2, msq1, msq2, lda, rlda
  integer(TC) :: k1, k2
  real(default) :: f1, f2, v1, v2
  k1 = b%daughter(1); k2 = b%daughter(2)
  if (tree%branch(k1)%has_children) then
    call set_msq_x (tree%branch(k1), k1, f1, v1, .false.)
    if (.not.ok) return
  else
    f1 = 1; v1 = 1
  end if
  if (tree%branch(k2)%has_children) then
    call set_msq_x (tree%branch(k2), k2, f2, v2, .false.)
    if (.not.ok) return
  else
    f2 = 1; v2 = 1
  end if
  m_min = tree%mass_sum(k)
  if (initial) then
    msq = sqrts**2

```

```

      m = sqrts
      m_max = sqrts
      factor = f1 * f2
      volume = v1 * v2 / (4 * twopi5)
    else
      m_max = sqrts - m_tot + m_min
      call mapping_compute_msq_from_x &
        (tree%mapping(k), sqrts**2, m_min**2, m_max**2, msq, factor, &
          x(ix)); ix = ix + 1
      if (msq >= 0) then
        m = sqrt (msq)
        factor = f1 * f2 * factor
        volume = v1 * v2 * sqrts**2 / (4 * twopi2)
        call phs_prt_set_msq (prt(k), msq)
        call phs_prt_set_defined (prt(k))
      else
        ok = .false.
      end if
    end if
  if (ok) then
    msq1 = phs_prt_get_msq (prt(k1)); m1 = sqrt (msq1)
    msq2 = phs_prt_get_msq (prt(k2)); m2 = sqrt (msq2)
    lda = lambda (msq, msq1, msq2)
    if (lda > 0 .and. m > m1 + m2 .and. m <= m_max) then
      rlda = sqrt (lda)
      decay_p(k1) = rlda / (2*m)
      decay_p(k2) = - decay_p(k1)
      factor = rlda / msq * factor
    else
      ok = .false.
    end if
  end if
end subroutine set_msq_x
end subroutine phs_tree_set_msq

```

The heart of phase space generation: Now we have the invariant masses, let us generate angles. At each branch, we take a Lorentz transformation and augment it by a boost to the current particle rest frame, and by rotations ϕ and θ around the z and y axis, respectively. This transformation is passed down to the daughter particles, if present.

(*PHS trees: procedures*) \equiv

```

subroutine phs_tree_set_angles (tree, prt, factor, decay_p, sqrts, x)
  type(phs_tree_t), intent(inout) :: tree
  type(phs_prt_t), dimension(:), intent(inout) :: prt
  real(default), intent(inout) :: factor
  real(default), dimension(:), intent(in) :: decay_p
  real(default), intent(in) :: sqrts
  real(default), dimension(:), intent(in) :: x
  integer :: ix
  integer(TC) :: k
  ix = 1
  k = tree%mask_out
  call set_angles_x (tree%branch(k), k)

```

```

contains
recursive subroutine set_angles_x (b, k, L0)
  type(phs_branch_t), intent(in) :: b
  integer(TC), intent(in) :: k
  type(lorentz_transformation_t), intent(in), optional :: L0
  real(default) :: m, msq, ct, st, phi, f, E, p, bg
  type(lorentz_transformation_t) :: L, LL
  integer(TC) :: k1, k2
  type(vector3_t) :: axis
  p = decay_p(k)
  msq = phs_prt_get_msq (prt(k)); m = sqrt (msq)
  E = sqrt (msq + p**2)
  if (present (L0)) then
    call phs_prt_set_momentum (prt(k), L0 * vector4_moving (E,p,3))
  else
    call phs_prt_set_momentum (prt(k), vector4_moving (E,p,3))
  end if
  call phs_prt_set_defined (prt(k))
  if (b%has_children) then
    k1 = b%daughter(1)
    k2 = b%daughter(2)
    if (m > 0) then
      bg = p / m
    else
      bg = 0
    end if
    phi = x(ix) * twopi; ix = ix + 1
    call mapping_compute_ct_from_x &
      (tree%mapping(k), sqrts**2, ct, st, f, x(ix)); ix = ix + 1
    factor = factor * f
    if (.not. b%has_friend) then
!      L = boost (bg,3) * rotation (phi,3) * rotation (ct,st,2)
      L = LT_compose_r2_r3_b3 (ct, st, cos(phi), sin(phi), bg)
    else
      LL = boost (-bg,3); if (present (L0)) LL = LL * inverse(L0)
      axis = space_part ( &
        LL * phs_prt_get_momentum (prt(tree%branch(k)%friend)) )
      L = boost(bg,3) * rotation_to_2nd (vector3_canonical(3), axis) &
!        & * rotation(phi,3) * rotation(ct,st,2)
        * LT_compose_r2_r3_b3 (ct, st, cos(phi), sin(phi), 0._default)
    end if
    if (present (L0)) L = L0 * L
    call set_angles_x (tree%branch(k1), k1, L)
    call set_angles_x (tree%branch(k2), k2, L)
  end if
end subroutine set_angles_x
end subroutine phs_tree_set_angles

```

Recover random numbers

For the other channels we want to compute the random numbers that would have generated the momenta that we already know.

(PHS trees: public)+≡

```

public :: phs_tree_compute_x_from_momenta
<PHS trees: procedures>+≡
subroutine phs_tree_compute_x_from_momenta (tree, prt, factor, sqrts, x)
  type(phs_tree_t), intent(inout) :: tree
  type(phs_prt_t), dimension(:), intent(in) :: prt
  real(default), intent(out) :: factor
  real(default), intent(in) :: sqrts
  real(default), dimension(:), intent(inout) :: x
  real(default), dimension(tree%mask_out) :: decay_p
  integer :: n1, n2
  n1 = tree%n_msq
  n2 = n1 + tree%n_angles
  call phs_tree_get_msq &
    (tree, prt, factor, decay_p, sqrts, x(1:n1))
  call phs_tree_get_angles &
    (tree, prt, factor, decay_p, sqrts, x(n1+1:n2))
end subroutine phs_tree_compute_x_from_momenta

```

The inverse operation follows exactly the same steps. The tree is `inout` because it contains mappings whose parameters can be reset when the mapping is applied.

```

<PHS trees: procedures>+≡
subroutine phs_tree_get_msq (tree, prt, factor, decay_p, sqrts, x)
  type(phs_tree_t), intent(inout) :: tree
  type(phs_prt_t), dimension(:), intent(in) :: prt
  real(default), intent(out) :: factor
  real(default), dimension(:), intent(out) :: decay_p
  real(default), intent(in) :: sqrts
  real(default), dimension(:), intent(inout) :: x
  integer :: ix
  integer(TC) :: k
  real(default) :: m_tot
  ix = 1
  k = tree%mask_out
  m_tot = tree%mass_sum(k)
  decay_p(k) = 0.
  if (tree%branch(k)%has_children) then
    call get_msq_x (tree%branch(k), k, factor, .true.)
  else
    factor = 1
  end if
contains
recursive subroutine get_msq_x (b, k, factor, initial)
  type(phs_branch_t), intent(in) :: b
  integer(TC), intent(in) :: k
  real(default), intent(out) :: factor
  logical, intent(in) :: initial
  real(default) :: msq, m, m_min, m_max, msq1, msq2, lda, rlda
  integer(TC) :: k1, k2
  real(default) :: f1, f2
  k1 = b%daughter(1); k2 = b%daughter(2)
  if (tree%branch(k1)%has_children) then
    call get_msq_x (tree%branch(k1), k1, f1, .false.)

```



```

else
    f1 = 1
end if
if (tree%branch(k2)%has_children) then
    call get_msq_x (tree%branch(k2), k2, f2, .false.)
else
    f2 = 1
end if
m_min = tree%mass_sum(k)
m_max = sqrts - m_tot + m_min
msq = phs_prt_get_msq (prt(k)); m = sqrt (msq)
if (initial) then
    factor = f1 * f2
else
    call mapping_compute_x_from_msq &
        (tree%mapping(k), sqrts**2, m_min**2, m_max**2, msq, factor, &
        x(ix)); ix = ix + 1
    factor = f1 * f2 * factor
end if
msq1 = phs_prt_get_msq (prt(k1))
msq2 = phs_prt_get_msq (prt(k2))
lda = lambda (msq, msq1, msq2)
if (lda > 0) then
    rlda = sqrt (lda)
    decay_p(k1) = rlda / (2 * m)
    decay_p(k2) = - decay_p(k1)
    factor = rlda / msq * factor
else
    decay_p(k1) = 0
    decay_p(k2) = 0
    factor = 0
end if
end subroutine get_msq_x
end subroutine phs_tree_get_msq

```

This subroutine is the most time-critical part of the whole program. Therefore, we do not exactly parallel the angle generation routine above but make sure that things get evaluated only if they are really needed, at the expense of readability. Particularly important is to have as few multiplications of Lorentz transformations as possible.

(PHS trees: procedures)+≡

```

subroutine phs_tree_get_angles (tree, prt, factor, decay_p, sqrts, x)
    type(phs_tree_t), intent(inout) :: tree
    type(phs_prt_t), dimension(:), intent(in) :: prt
    real(default), intent(inout) :: factor
    real(default), dimension(:), intent(in) :: decay_p
    real(default), intent(in) :: sqrts
    real(default), dimension(:), intent(out) :: x
    integer :: ix
    integer(TC) :: k
    ix = 1
    k = tree%mask_out
    if (tree%branch(k)%has_children) call get_angles_x (tree%branch(k), k)

```

```

contains
recursive subroutine get_angles_x (b, k, ct0, st0, phi0, L0)
  type(phs_branch_t), intent(in) :: b
  integer(TC), intent(in) :: k
  real(default), intent(in), optional :: ct0, st0, phi0
  type(lorentz_transformation_t), intent(in), optional :: L0
  real(default) :: cp0, sp0, m, msq, ct, st, phi, bg, f
  type(lorentz_transformation_t) :: L, LL
  type(vector4_t) :: p1, pf
  type(vector3_t) :: n, axis
  integer(TC) :: k1, k2, kf
  logical :: has_friend, need_L
  k1 = b%daughter(1)
  k2 = b%daughter(2)
  kf = b%friend
  has_friend = b%has_friend
  if (present(L0)) then
    p1 = L0 * phs_prt_get_momentum (prt(k1))
    if (has_friend) pf = L0 * phs_prt_get_momentum (prt(kf))
  else
    p1 = phs_prt_get_momentum (prt(k1))
    if (has_friend) pf = phs_prt_get_momentum (prt(kf))
  end if
  if (present(phi0)) then
    cp0 = cos (phi0)
    sp0 = sin (phi0)
  end if
  msq = phs_prt_get_msq (prt(k)); m = sqrt (msq)
  if (m > 0) then
    bg = decay_p(k) / m
  else
    bg = 0
  end if
  if (has_friend) then
    if (present (phi0)) then
      axis = axis_from_p_r3_r2_b3 (pf, cp0, -sp0, ct0, -st0, -bg)
      LL = rotation_to_2nd (axis, vector3_canonical (3)) &
        * LT_compose_r3_r2_b3 (cp0, -sp0, ct0, -st0, -bg)
    else
      axis = axis_from_p_b3 (pf, -bg)
      LL = rotation_to_2nd (axis, vector3_canonical(3))
      if (bg /= 0) LL = LL * boost(-bg, 3)
    end if
    n = space_part (LL * p1)
  else if (present (phi0)) then
    n = axis_from_p_r3_r2_b3 (p1, cp0, -sp0, ct0, -st0, -bg)
  else
    n = axis_from_p_b3 (p1, -bg)
  end if
  phi = azimuthal_angle (n)
  x(ix) = phi / twopi; ix = ix + 1
  ct = polar_angle_ct (n)
  st = sqrt (1 - ct**2)
  call mapping_compute_x_from_ct (tree%mapping(k), sqrts**2, ct, f, &

```

```

        x(ix)); ix = ix + 1
factor = factor * f
if (tree%branch(k1)%has_children .or. tree%branch(k2)%has_children) then
    need_L = .true.
    if (has_friend) then
        if (present (L0)) then
            L = LL * L0
        else
            L = LL
        end if
    else if (present (L0)) then
        L = LT_compose_r3_r2_b3 (cp0, -sp0, ct0, -st0, -bg) * L0
    else if (present (phi0)) then
        L = LT_compose_r3_r2_b3 (cp0, -sp0, ct0, -st0, -bg)
    else if (bg /= 0) then
        L = boost(-bg, 3)
    else
        need_L = .false.
    end if
    if (need_L) then
        if (tree%branch(k1)%has_children) &
            call get_angles_x (tree%branch(k1), k1, ct, st, phi, L)
        if (tree%branch(k2)%has_children) &
            call get_angles_x (tree%branch(k2), k2, ct, st, phi, L)
    else
        if (tree%branch(k1)%has_children) &
            call get_angles_x (tree%branch(k1), k1, ct, st, phi)
        if (tree%branch(k2)%has_children) &
            call get_angles_x (tree%branch(k2), k2, ct, st, phi)
    end if
end if
end subroutine get_angles_x
end subroutine phs_tree_get_angles

```

Auxiliary stuff

This calculates all momenta that are not yet known by summing up daughter particle momenta. The external particles must be known. Only composite particles not yet known are calculated.

```

<PHS trees: public>+≡
    public :: phs_tree_combine_particles

<PHS trees: procedures>+≡
    subroutine phs_tree_combine_particles (tree, prt)
        type(phs_tree_t), intent(in) :: tree
        type(phs_prt_t), dimension(:), intent(inout) :: prt
        call combine_particles_x (tree%mask_out)
    contains
        recursive subroutine combine_particles_x (k)
            integer(TC), intent(in) :: k
            integer :: k1, k2
            if (tree%branch(k)%has_children) then
                k1 = tree%branch(k)%daughter(1); k2 = tree%branch(k)%daughter(2)

```

```

        call combine_particles_x (k1)
        call combine_particles_x (k2)
        if (.not. prt(k)%defined) then
            call phs_prt_combine (prt(k), prt(k1), prt(k2))
        end if
    end if
end subroutine combine_particles_x
end subroutine phs_tree_combine_particles

```

The previous routine is to be evaluated at runtime. Instead of scanning trees, we can as well set up a multiplication table. This is generated here. Note that the table is `intent(out)`.

<PHS trees: public>+≡

```

    public :: phs_tree_setup_prt_combinations

```

<PHS trees: procedures>+≡

```

subroutine phs_tree_setup_prt_combinations (tree, comb)
    type(phs_tree_t), intent(in) :: tree
    integer, dimension(:,,:), intent(out) :: comb
    comb = 0
    call setup_prt_combinations_x (tree%mask_out)
contains
    recursive subroutine setup_prt_combinations_x (k)
        integer(TC), intent(in) :: k
        integer, dimension(2) :: kk
        if (tree%branch(k)%has_children) then
            kk = tree%branch(k)%daughter
            call setup_prt_combinations_x (kk(1))
            call setup_prt_combinations_x (kk(2))
            comb(:,k) = kk
        end if
    end subroutine setup_prt_combinations_x
end subroutine phs_tree_setup_prt_combinations

```

12.3 The phase-space forest

Simply stated, a phase-space forest is a collection of phase-space trees. More precisely, a `phs_forest` object contains all parameterizations of phase space that WHIZARD will use for a single hard process, prepared in the form of `phs_tree` objects. This is suitable for evaluation by the VAMP integration package: each parameterization (tree) is a valid channel in the multi-channel adaptive integration, and each variable in a tree corresponds to an integration dimension, defined by an appropriate mapping of the $(0, 1)$ interval to the allowed range of the integration variable.

The trees are grouped in groves. The trees (integration channels) within a grove share a common weight, assuming that they are related by some approximate symmetry.

Trees/channels that are related by an exact symmetry are connected by an array of equivalences; each equivalence object holds the data that relate one channel to another.

The phase-space setup, i.e., the detailed structure of trees and forest, are read from a file. Therefore, this module also contains the syntax definition and the parser needed for interpreting this file.

```
(phs_forests.f90)≡
  <File header>

  module phs_forests

    <Use kinds>
    use kinds, only: TC !NODEP!
    <Use strings>
    <Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use vamp_equivalences !NODEP!
    use permutations
    use ifiles
    use syntax_rules
    use lexers
    use parser
    use models
    use flavors
    use interactions
    use mappings
    use phs_trees

    <Standard module head>

    <PHS forests: public>

    <PHS forests: types>

    <PHS forests: interfaces>

    <PHS forests: variables>
```

contains

<PHS forests: procedures>

end module phs_forests

12.3.1 Phase-space setup parameters

This transparent container holds the parameters that the algorithm needs for phase-space setup, with reasonable defaults.

The threshold mass (for considering a particle as effectively massless) is specified separately for s- and t-channel. The default is to treat W and Z bosons as massive in the s-channel, but as massless in the t-channel. The b -quark is treated always massless, the t -quark always massive.

<PHS forests: public>≡

public :: phs_parameters_t

<PHS forests: types>≡

type :: phs_parameters_t

real(default) :: sqrts = 0

real(default) :: m_threshold_s = 50._default

real(default) :: m_threshold_t = 100._default

integer :: off_shell = 1

integer :: t_channel = 2

logical :: keep_nonresonant = .true.

end type phs_parameters_t

Write phase-space parameters to file.

<PHS forests: public>+≡

public :: phs_parameters_write

<PHS forests: procedures>≡

subroutine phs_parameters_write (phs_par, unit)

type(phs_parameters_t), intent(in) :: phs_par

integer, intent(in), optional :: unit

integer :: u

u = output_unit (unit)

write (u, *) " sqrts = ", phs_par%sqrts

write (u, *) " m_threshold_s = ", phs_par%m_threshold_s

write (u, *) " m_threshold_t = ", phs_par%m_threshold_t

write (u, *) " off_shell = ", phs_par%off_shell

write (u, *) " t_channel = ", phs_par%t_channel

write (u, *) " keep_nonresonant = ", phs_par%keep_nonresonant

end subroutine phs_parameters_write

Read phase-space parameters from file.

<PHS forests: public>+≡

public :: phs_parameters_read

<PHS forests: procedures>+≡

subroutine phs_parameters_read (phs_par, unit)

type(phs_parameters_t), intent(out) :: phs_par

integer, intent(in) :: unit

```

character(20) :: dummy
character :: equals
read (unit, *) dummy, equals, phs_par%sqrts
read (unit, *) dummy, equals, phs_par%m_threshold_s
read (unit, *) dummy, equals, phs_par%m_threshold_t
read (unit, *) dummy, equals, phs_par%off_shell
read (unit, *) dummy, equals, phs_par%t_channel
read (unit, *) dummy, equals, phs_par%keep_nonresonant
end subroutine phs_parameters_read

```

Comparison.

(PHS forests: interfaces)≡

```

interface operator(==)
  module procedure phs_parameters_eq
end interface
interface operator(/=)
  module procedure phs_parameters_ne
end interface

```

(PHS forests: procedures)+≡

```

function phs_parameters_eq (phs_par1, phs_par2) result (equal)
  logical :: equal
  type(phs_parameters_t), intent(in) :: phs_par1, phs_par2
  equal = phs_par1%sqrts == phs_par2%sqrts &
    .and. phs_par1%m_threshold_s == phs_par2%m_threshold_s &
    .and. phs_par1%m_threshold_t == phs_par2%m_threshold_t &
    .and. phs_par1%off_shell == phs_par2%off_shell &
    .and. phs_par1%t_channel == phs_par2%t_channel &
    .and.(phs_par1%keep_nonresonant .eqv. phs_par2%keep_nonresonant)
end function phs_parameters_eq

function phs_parameters_ne (phs_par1, phs_par2) result (ne)
  logical :: ne
  type(phs_parameters_t), intent(in) :: phs_par1, phs_par2
  ne = phs_par1%sqrts /= phs_par2%sqrts &
    .or. phs_par1%m_threshold_s /= phs_par2%m_threshold_s &
    .or. phs_par1%m_threshold_t /= phs_par2%m_threshold_t &
    .or. phs_par1%off_shell /= phs_par2%off_shell &
    .or. phs_par1%t_channel /= phs_par2%t_channel &
    .or.(phs_par1%keep_nonresonant .neqv. phs_par2%keep_nonresonant)
end function phs_parameters_ne

```

12.3.2 Equivalences

This type holds information about equivalences between phase-space trees. We make a linked list, where each node contains the two trees which are equivalent and the corresponding permutation of external particles. Two more arrays are to be filled: The permutation of mass variables and the permutation of angular variables, where the signature indicates a necessary exchange of daughter branches.

(PHS forests: types)+≡

```

type :: equivalence_t

```

```

private
integer :: left, right
type(permutation_t) :: perm
type(permutation_t) :: msq_perm, angle_perm
logical, dimension(:), allocatable :: angle_sig
type(equivalence_t), pointer :: next => null ()
end type equivalence_t

```

(PHS forests: types)+≡

```

type :: equivalence_list_t
private
integer :: length = 0
type(equivalence_t), pointer :: first => null ()
type(equivalence_t), pointer :: last => null ()
end type equivalence_list_t

```

Append an equivalence to the list

(PHS forests: procedures)+≡

```

subroutine equivalence_list_add (eql, left, right, perm)
type(equivalence_list_t), intent(inout) :: eql
integer, intent(in) :: left, right
type(permutation_t), intent(in) :: perm
type(equivalence_t), pointer :: eq
allocate (eq)
eq%left = left
eq%right = right
eq%perm = perm
if (associated (eql%last)) then
    eql%last%next => eq
else
    eql%first => eq
end if
eql%last => eq
eql%length = eql%length + 1
end subroutine equivalence_list_add

```

Delete the list contents. Has to be pure because it is called from an elemental subroutine.

(PHS forests: procedures)+≡

```

pure subroutine equivalence_list_final (eql)
type(equivalence_list_t), intent(inout) :: eql
type(equivalence_t), pointer :: eq
do while (associated (eql%first))
    eq => eql%first
    eql%first => eql%first%next
    deallocate (eq)
end do
eql%last => null ()
eql%length = 0
end subroutine equivalence_list_final

```


Make a deep copy of the equivalence list. This allows for deep copies of groves and forests.

```

(PHS forests: interfaces)+≡
  interface assignment(=)
    module procedure equivalence_list_assign
  end interface

(PHS forests: procedures)+≡
  subroutine equivalence_list_assign (eql_out, eql_in)
    type(equivalence_list_t), intent(out) :: eql_out
    type(equivalence_list_t), intent(in) :: eql_in
    type(equivalence_t), pointer :: eq, eq_copy
    eq => eql_in%first
    do while (associated (eq))
      allocate (eq_copy)
      eq_copy = eq
      eq_copy%next => null ()
      if (associated (eql_out%first)) then
        eql_out%last%next => eq_copy
      else
        eql_out%first => eq_copy
      end if
      eql_out%last => eq_copy
      eq => eq%next
    end do
  end subroutine equivalence_list_assign

```

The number of list entries

```

(PHS forests: procedures)+≡
  elemental function equivalence_list_length (eql) result (length)
    integer :: length
    type(equivalence_list_t), intent(in) :: eql
    length = eql%length
  end function equivalence_list_length

```

Recursively write the equivalences list

```

(PHS forests: procedures)+≡
  subroutine equivalence_list_write (eql, unit)
    type(equivalence_list_t), intent(in) :: eql
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    if (associated (eql%first)) then
      call equivalence_write_rec (eql%first, u)
    else
      write (u, *) " [empty]"
    end if
  contains
    recursive subroutine equivalence_write_rec (eq, u)
      type(equivalence_t), intent(in) :: eq
      integer, intent(in) :: u
      integer :: i

```

```

write (u, "(1x,A,1x,I5,1x,I5,5x,A)", advance="no") &
"Equivalence:", eq%left, eq%right, "Final state permutation:"
call permutation_write (eq%perm, u)
write (u, "(1x,12x,1x,A,1x)", advance="no") &
"      msq permutation: "
call permutation_write (eq%msq_perm, u)
write (u, "(1x,12x,1x,A,1x)", advance="no") &
"      angle permutation:"
call permutation_write (eq%angle_perm, u)
write (u, "(1x,12x,1x,26x)", advance="no")
do i = 1, size (eq%angle_sig)
  if (eq%angle_sig(i)) then
    write (u, "(1x,A)", advance="no") "+"
  else
    write (u, "(1x,A)", advance="no") "-"
  end if
end do
write (u, *)
if (associated (eq%next)) call equivalence_write_rec (eq%next, u)
end subroutine equivalence_write_rec
end subroutine equivalence_list_write

```

12.3.3 Groves

A grove is a group of trees (phase-space channels) that share a common weight in the integration. Within a grove, channels can be declared equivalent, so they also share their integration grids (up to symmetries). The grove contains a list of equivalences. The `tree_count_offset` is the total number of trees of the preceding groves; when the trees are counted per forest (integration channels), the offset has to be added to all tree indices.

```

<PHS forests: types>+≡
type :: phs_grove_t
private
integer :: tree_count_offset
type(phs_tree_t), dimension(:), allocatable :: tree
type(equivalence_list_t) :: equivalence_list
end type phs_grove_t

```

Call `phs_tree_init` which is also elemental:

```

<PHS forests: procedures>+≡
elemental subroutine phs_grove_init &
(grove, n_trees, n_in, n_out, n_masses, n_angles)
type(phs_grove_t), intent(inout) :: grove
integer, intent(in) :: n_trees, n_in, n_out, n_masses, n_angles
grove%tree_count_offset = 0
allocate (grove%tree (n_trees))
call phs_tree_init (grove%tree, n_in, n_out, n_masses, n_angles)
end subroutine phs_grove_init

```

The trees do not have pointer components, thus no call to `phs_tree_final`:

```

<PHS forests: procedures>+≡

```

```

elemental subroutine phs_grove_final (grove)
  type(phs_grove_t), intent(inout) :: grove
  deallocate (grove%tree)
  call equivalence_list_final (grove%equivalence_list)
end subroutine phs_grove_final

```

Deep copy.

(PHS forests: interfaces)+≡

```

interface assignment(=)
  module procedure phs_grove_assign0
  module procedure phs_grove_assign1
end interface

```

(PHS forests: procedures)+≡

```

subroutine phs_grove_assign0 (grove_out, grove_in)
  type(phs_grove_t), intent(out) :: grove_out
  type(phs_grove_t), intent(in) :: grove_in
  grove_out%tree_count_offset = grove_in%tree_count_offset
  if (allocated (grove_in%tree)) then
    allocate (grove_out%tree (size (grove_in%tree)))
    grove_out%tree = grove_in%tree
  end if
  grove_out%equivalence_list = grove_in%equivalence_list
end subroutine phs_grove_assign0

subroutine phs_grove_assign1 (grove_out, grove_in)
  type(phs_grove_t), dimension(:), intent(out) :: grove_out
  type(phs_grove_t), dimension(:), intent(in) :: grove_in
  integer :: i
  do i = 1, size (grove_in)
    call phs_grove_assign0 (grove_out(i), grove_in(i))
  end do
end subroutine phs_grove_assign1

```

Get the global (s-channel) mappings. Implemented as a subroutine which returns an array (slice).

(PHS forests: procedures)+≡

```

subroutine phs_grove_assign_s_mappings (grove, mapping)
  type(phs_grove_t), intent(in) :: grove
  type(mapping_t), dimension(:), intent(out) :: mapping
  integer :: i
  if (size (mapping) == size (grove%tree)) then
    do i = 1, size (mapping)
      call phs_tree_assign_s_mapping (grove%tree(i), mapping(i))
    end do
  else
    call msg_bug ("phs_grove_assign_s_mappings: array size mismatch")
  end if
end subroutine phs_grove_assign_s_mappings

```

12.3.4 The forest type

This is a collection of trees and associated particles. In a given tree, each branch code corresponds to a particle in the `prt` array. Furthermore, we have an array of mass sums which is independent of the decay tree and of the particular event. The mappings directly correspond to the decay trees, and the decay groves collect the trees in classes. The permutation list consists of all permutations of outgoing particles that map the decay forest onto itself.

The particle codes `flv` (one for each external particle) are needed for determining masses and such. The trees and associated information are collected in the `grove` array, together with a lookup table that associates tree indices to groves. Finally, the `prt` array serves as workspace for phase-space evaluation.

The `prt_combination` is a list of index pairs, namely the particle momenta pairs that need to be combined in order to provide all momentum combinations that the phase-space trees need to know.

```

<PHS forests: public>+≡
    public :: phs_forest_t

<PHS forests: types>+≡
    type :: phs_forest_t
    private
        integer :: n_in, n_out, n_tot
        integer :: n_masses, n_angles, n_dimensions
        integer :: n_trees, n_equivalences
        type(flavor_t), dimension(:), allocatable :: flv
        type(phs_grove_t), dimension(:), allocatable :: grove
        integer, dimension(:), allocatable :: grove_lookup
        type(phs_prt_t), dimension(:), allocatable :: prt_in
        type(phs_prt_t), dimension(:), allocatable :: prt_out
        type(phs_prt_t), dimension(:), allocatable :: prt
        integer(TC), dimension(:, :), allocatable :: prt_combination
        type(mapping_t), dimension(:), allocatable :: s_mapping
    end type phs_forest_t

```

The initialization merely allocates memory. We have to know how many trees there are in each grove, so we can initialize everything. The number of groves is the size of the `n_tree` array.

In the `grove_lookup` table we store the grove index that belongs to each absolute tree index. The difference between the absolute index and the relative (to the grove) index is stored, for each grove, as `tree_count_offset`.

The particle array is allocated according to the total number of branches each tree has, but not filled.

```

<PHS forests: public>+≡
    public :: phs_forest_init

<PHS forests: procedures>+≡
    subroutine phs_forest_init (forest, n_tree, n_in, n_out)
        type(phs_forest_t), intent(inout) :: forest
        integer, dimension(:), intent(in) :: n_tree
        integer, intent(in) :: n_in, n_out
        integer :: g, count, k_root
        forest%n_in = n_in
        forest%n_out = n_out
    end subroutine phs_forest_init

```

```

forest%n_tot = n_in + n_out
forest%n_masses = max (n_out - 2, 0)
forest%n_angles = max (2*n_out - 2, 0)
forest%n_dimensions = forest%n_masses + forest%n_angles
forest%n_trees = sum (n_tree)
forest%n_equivalences = 0
allocate (forest%grove (size (n_tree)))
call phs_grove_init &
    (forest%grove, n_tree, n_in, n_out, forest%n_masses, forest%n_angles)
allocate (forest%grove_lookup (forest%n_trees))
count = 0
do g = 1, size (forest%grove)
    forest%grove(g)%tree_count_offset = count
    forest%grove_lookup (count+1:count+n_tree(g)) = g
    count = count + n_tree(g)
end do
allocate (forest%prt_in (n_in))
allocate (forest%prt_out (n_out))
k_root = 2**forest%n_tot - 1
allocate (forest%prt (k_root))
allocate (forest%prt_combination (2, k_root))
allocate (forest%s_mapping (forest%n_trees))
end subroutine phs_forest_init

```

Assign the global (s-channel) mappings.

```

<PHS forests: public>+≡
    public :: phs_forest_set_s_mappings

<PHS forests: procedures>+≡
    subroutine phs_forest_set_s_mappings (forest)
        type(phs_forest_t), intent(inout) :: forest
        integer :: g, i0, i1, n
        do g = 1, size (forest%grove)
            call phs_forest_get_grove_bounds (forest, g, i0, i1, n)
            call phs_grove_assign_s_mappings &
                (forest%grove(g), forest%s_mapping(i0:i1))
        end do
    end subroutine phs_forest_set_s_mappings

```

The grove finalizer is called because it contains the equivalence list:

```

<PHS forests: public>+≡
    public :: phs_forest_final

<PHS forests: procedures>+≡
    subroutine phs_forest_final (forest)
        type(phs_forest_t), intent(inout) :: forest
        if (allocated (forest%grove)) then
            call phs_grove_final (forest%grove)
            deallocate (forest%grove)
        end if
        if (allocated (forest%grove_lookup)) deallocate (forest%grove_lookup)
        if (allocated (forest%prt)) deallocate (forest%prt)
        if (allocated (forest%s_mapping)) deallocate (forest%s_mapping)
    end subroutine phs_forest_final

```

12.3.5 Screen output

Write the particles that are non-null, then the trees which point to them:

(PHS forests: public)+≡

```
public :: phs_forest_write
```

(PHS forests: procedures)+≡

```
subroutine phs_forest_write (forest, unit)
  type(phs_forest_t), intent(in) :: forest
  integer, intent(in), optional :: unit
  integer :: u
  integer :: i, g, k
  u = output_unit (unit); if (u < 0) return
  write (u, *) "Phase space forest:"
  write (u, *) "n_in = ", forest%n_in
  write (u, *) "n_out = ", forest%n_out
  write (u, *) "n_tot = ", forest%n_tot
  write (u, *) "n_masses = ", forest%n_masses
  write (u, *) "n_angles = ", forest%n_angles
  write (u, *) "n_dim = ", forest%n_dimensions
  write (u, *) "n_trees = ", forest%n_trees
  write (u, *) "n_equiv = ", forest%n_equivalences
  write (u, "(1x,A)", advance="no") "flavors ="
  if (allocated (forest%flv)) then
    do i = 1, size (forest%flv)
      write (u, "(1x,I6)", advance="no") flavor_get_pdg (forest%flv(i))
    end do
    write (u, *)
  else
    write (u, *) "[empty]"
  end if
  write (u, *) "Particle combinations:"
  if (allocated (forest%prt_combination)) then
    do k = 1, size (forest%prt_combination, 2)
      if (forest%prt_combination(1, k) /= 0) then
        write (u, "(1x,I4,1x,'<=',1x,I4,'+',1x,I4)") &
          k, forest%prt_combination(:,k)
      end if
    end do
  else
    write (u, *) " [empty]"
  end if
  write (u, *) "Groves and trees:"
  if (allocated (forest%grove)) then
    do g = 1, size (forest%grove)
      write (u, "(1x,A,1x,I4)") "Grove ", g
      call phs_grove_write (forest%grove(g), unit)
    end do
  else
    write (u, *) " [empty]"
  end if
  write (u, *) "Total number of equivalences: ", forest%n_equivalences
```

```

write (u, *)
write (u, *) "Global s-channel mappings:"
if (allocated (forest%s_mapping)) then
  do i = 1, size (forest%s_mapping)
    if (mapping_is_s_channel (forest%s_mapping(i))) then
      write (u, "(1x,I0,':',1x)", advance="no") i
      call mapping_write (forest%s_mapping(i), unit)
    end if
  end do
else
  write (u, *) " [empty]"
end if
write (u, *)
write (u, *) "Incoming particles:"
if (allocated (forest%prt_in)) then
  if (any (phs_prt_is_defined (forest%prt_in))) then
    do i = 1, size (forest%prt_in)
      if (phs_prt_is_defined (forest%prt_in(i))) then
        write (u, *) "Particle", i
        call phs_prt_write (forest%prt_in(i), u)
      end if
    end do
  else
    write (u, "(3x,A)") "[all undefined]"
  end if
else
  write (u, *) " [empty]"
end if
write (u, *)
write (u, *) "Outgoing particles:"
if (allocated (forest%prt_out)) then
  if (any (phs_prt_is_defined (forest%prt_out))) then
    do i = 1, size (forest%prt_out)
      if (phs_prt_is_defined (forest%prt_out(i))) then
        write (u, *) "Particle", i
        call phs_prt_write (forest%prt_out(i), u)
      end if
    end do
  else
    write (u, "(3x,A)") "[all undefined]"
  end if
else
  write (u, *) " [empty]"
end if
write (u, *)
write (u, *) "Tree particles:"
if (allocated (forest%prt)) then
  if (any (phs_prt_is_defined (forest%prt))) then
    do i = 1, size (forest%prt)
      if (phs_prt_is_defined (forest%prt(i))) then
        write (u, *) "Particle", i
        call phs_prt_write (forest%prt(i), u)
      end if
    end do
  end if
end do

```

```

        else
            write (u, "(3x,A)") "[all undefined]"
        end if
    else
        write (u, *) " [empty]"
    end if
end subroutine phs_forest_write

subroutine phs_grove_write (grove, unit)
    type(phs_grove_t), intent(in) :: grove
    integer, intent(in), optional :: unit
    integer :: u
    integer :: t
    u = output_unit (unit); if (u < 0) return
    do t = 1, size (grove%tree)
        write (u, "(1x,A,1x,I4)") "Tree ", t
        call phs_tree_write (grove%tree(t), unit)
    end do
    write (u, "(1x,A)") "Equivalence list:"
    call equivalence_list_write (grove%equivalence_list, unit)
end subroutine phs_grove_write

```

Deep copy.

<PHS forests: public>+≡

```
public :: assignment(=)
```

<PHS forests: interfaces>+≡

```
interface assignment(=)
    module procedure phs_forest_assign
end interface

```

<PHS forests: procedures>+≡

```

subroutine phs_forest_assign (forest_out, forest_in)
    type(phs_forest_t), intent(out) :: forest_out
    type(phs_forest_t), intent(in) :: forest_in
    forest_out%n_in = forest_in%n_in
    forest_out%n_out = forest_in%n_out
    forest_out%n_tot = forest_in%n_tot
    forest_out%n_masses = forest_in%n_masses
    forest_out%n_angles = forest_in%n_angles
    forest_out%n_dimensions = forest_in%n_dimensions
    forest_out%n_trees = forest_in%n_trees
    forest_out%n_equivalences = forest_in%n_equivalences
    if (allocated (forest_in%flv)) then
        allocate (forest_out%flv (size (forest_in%flv)))
        forest_out%flv = forest_in%flv
    end if
    if (allocated (forest_in%grove)) then
        allocate (forest_out%grove (size (forest_in%grove)))
        forest_out%grove = forest_in%grove
    end if
    if (allocated (forest_in%grove_lookup)) then
        allocate (forest_out%grove_lookup (size (forest_in%grove_lookup)))
        forest_out%grove_lookup = forest_in%grove_lookup
    end if
end subroutine

```



```

end if
if (allocated (forest_in%prt_in)) then
  allocate (forest_out%prt_in (size (forest_in%prt_in)))
  forest_out%prt_in = forest_in%prt_in
end if
if (allocated (forest_in%prt_out)) then
  allocate (forest_out%prt_out (size (forest_in%prt_out)))
  forest_out%prt_out = forest_in%prt_out
end if
if (allocated (forest_in%prt)) then
  allocate (forest_out%prt (size (forest_in%prt)))
  forest_out%prt = forest_in%prt
end if
if (allocated (forest_in%s_mapping)) then
  allocate (forest_out%s_mapping (size (forest_in%s_mapping)))
  forest_out%s_mapping = forest_in%s_mapping
end if
if (allocated (forest_in%prt_combination)) then
  allocate (forest_out%prt_combination &
    (2, size (forest_in%prt_combination, 2)))
  forest_out%prt_combination = forest_in%prt_combination
end if
end subroutine phs_forest_assign

```

12.3.6 Accessing contents

Get the number of integration parameters

```

(PHS forests: public)+≡
public :: phs_forest_get_n_parameters

(PHS forests: procedures)+≡
function phs_forest_get_n_parameters (forest) result (n)
  integer :: n
  type(phs_forest_t), intent(in) :: forest
  n = forest%n_dimensions
end function phs_forest_get_n_parameters

```

Get the number of integration channels

```

(PHS forests: public)+≡
public :: phs_forest_get_n_channels

(PHS forests: procedures)+≡
function phs_forest_get_n_channels (forest) result (n)
  integer :: n
  type(phs_forest_t), intent(in) :: forest
  n = forest%n_trees
end function phs_forest_get_n_channels

```

Get the number of groves

```

(PHS forests: public)+≡
public :: phs_forest_get_n_groves

```

```

<PHS forests: procedures>+≡
function phs_forest_get_n_groves (forest) result (n)
  integer :: n
  type(phs_forest_t), intent(in) :: forest
  n = size (forest%grove)
end function phs_forest_get_n_groves

```

Get the index bounds for a specific grove.

```

<PHS forests: public>+≡
public :: phs_forest_get_grove_bounds

<PHS forests: procedures>+≡
subroutine phs_forest_get_grove_bounds (forest, g, i0, i1, n)
  type(phs_forest_t), intent(in) :: forest
  integer, intent(in) :: g
  integer, intent(out) :: i0, i1, n
  n = size (forest%grove(g)%tree)
  i0 = forest%grove(g)%tree_count_offset + 1
  i1 = forest%grove(g)%tree_count_offset + n
end subroutine phs_forest_get_grove_bounds

```

Get the number of equivalences

```

<PHS forests: public>+≡
public :: phs_forest_get_n_equivalences

<PHS forests: procedures>+≡
function phs_forest_get_n_equivalences (forest) result (n)
  integer :: n
  type(phs_forest_t), intent(in) :: forest
  n = forest%n_equivalences
end function phs_forest_get_n_equivalences

```

Return true if a particular channel has a global (s-channel) mapping; also return the resonance mass and width for this mapping.

```

<PHS forests: public>+≡
public :: phs_forest_get_s_mapping

<PHS forests: procedures>+≡
subroutine phs_forest_get_s_mapping (forest, channel, flag, mass, width)
  type(phs_forest_t), intent(in) :: forest
  integer, intent(in) :: channel
  logical, intent(out) :: flag
  real(default), intent(out) :: mass, width
  flag = mapping_is_s_channel (forest%s_mapping(channel))
  if (flag) then
    mass = mapping_get_mass (forest%s_mapping(channel))
    width = mapping_get_width (forest%s_mapping(channel))
  else
    mass = 0
    width = 0
  end if
end subroutine phs_forest_get_s_mapping

```

12.3.7 Read the phase space setup from file

The phase space setup is stored in a file. The file may be generated by the `cascades` module below, or by other means. This file has to be read and parsed to create the PHS forest as the internal phase-space representation.

Create lexer and syntax:

(*PHS forests: procedures*)+≡

```
subroutine define_phs_forest_syntax (ifile)
  type(ifile_t) :: ifile
  call ifile_append (ifile, "SEQ phase_space_list = process_phase_space*")
  call ifile_append (ifile, "SEQ process_phase_space = " &
    // "process_def process_header phase_space")
  call ifile_append (ifile, "SEQ process_def = process process_list")
  call ifile_append (ifile, "KEY process")
  call ifile_append (ifile, "LIS process_list = process_tag*")
  call ifile_append (ifile, "IDE process_tag")
  call ifile_append (ifile, "SEQ process_header = " &
    // "md5sum_process = md5sum " &
    // "md5sum_model = md5sum " &
    // "md5sum_parameters = md5sum " &
    // "sqrts = real " &
    // "m_threshold_s = real " &
    // "m_threshold_t = real " &
    // "off_shell = integer " &
    // "t_channel = integer " &
    // "keep_nonresonant = logical")
  call ifile_append (ifile, "KEY '='")
  call ifile_append (ifile, "KEY md5sum_process")
  call ifile_append (ifile, "KEY md5sum_model")
  call ifile_append (ifile, "KEY md5sum_parameters")
  call ifile_append (ifile, "KEY sqrts")
  call ifile_append (ifile, "KEY m_threshold_s")
  call ifile_append (ifile, "KEY m_threshold_t")
  call ifile_append (ifile, "KEY off_shell")
  call ifile_append (ifile, "KEY t_channel")
  call ifile_append (ifile, "KEY keep_nonresonant")
  call ifile_append (ifile, "QUO md5sum = '""' ... '""'")
  call ifile_append (ifile, "REA real")
  call ifile_append (ifile, "INT integer")
  call ifile_append (ifile, "IDE logical")
  call ifile_append (ifile, "SEQ phase_space = grove_def+")
  call ifile_append (ifile, "SEQ grove_def = grove tree_def+")
  call ifile_append (ifile, "KEY grove")
  call ifile_append (ifile, "SEQ tree_def = tree bincodes mapping*")
  call ifile_append (ifile, "KEY tree")
  call ifile_append (ifile, "SEQ bincodes = bincodes+")
  call ifile_append (ifile, "INT bincodes")
  call ifile_append (ifile, "SEQ mapping = map bincodes channel pdg")
  call ifile_append (ifile, "KEY map")
  call ifile_append (ifile, "ALT channel = s_channel | t_channel | u_channel | collinear | infra")
  call ifile_append (ifile, "KEY s_channel")
  ! call ifile_append (ifile, "KEY t_channel")
  call ifile_append (ifile, "KEY u_channel")
  call ifile_append (ifile, "KEY collinear")
end subroutine
```

```

        call ifile_append (ifile, "KEY infrared")
        call ifile_append (ifile, "KEY radiation")
        call ifile_append (ifile, "INT pdg")
    end subroutine define_phs_forest_syntax

```

The model-file syntax and lexer are fixed, therefore stored as module variables:

```

<PHS forests: variables>≡
    type(syntax_t), target, save :: syntax_phs_forest

<PHS forests: public>+≡
    public :: syntax_phs_forest_init

<PHS forests: procedures>+≡
    subroutine syntax_phs_forest_init ()
        type(ifile_t) :: ifile
        call define_phs_forest_syntax (ifile)
        call syntax_init (syntax_phs_forest, ifile)
        call ifile_final (ifile)
    end subroutine syntax_phs_forest_init

<PHS forests: procedures>+≡
    subroutine lexer_init_phs_forest (lexer)
        type(lexer_t), intent(out) :: lexer
        call lexer_init (lexer, &
            comment_chars = "#!", &
            quote_chars = "'", &
            quote_match = "'", &
            single_chars = "", &
            special_class = (/ "=" /) , &
            keyword_list = syntax_get_keyword_list_ptr (syntax_phs_forest))
    end subroutine lexer_init_phs_forest

<PHS forests: public>+≡
    public :: syntax_phs_forest_final

<PHS forests: procedures>+≡
    subroutine syntax_phs_forest_final ()
        call syntax_final (syntax_phs_forest)
    end subroutine syntax_phs_forest_final

<PHS forests: public>+≡
    public :: syntax_phs_forest_write

<PHS forests: procedures>+≡
    subroutine syntax_phs_forest_write (unit)
        integer, intent(in), optional :: unit
        call syntax_write (syntax_phs_forest, unit)
    end subroutine syntax_phs_forest_write

```

The concrete parser and interpreter. Generate an input stream for the external `unit`, read the parse tree (with given `syntax` and `lexer`) from this stream, and transfer the contents of the parse tree to the PHS forest.

We look for the matching `process` tag, count groves and trees for initializing the forest, and fill the trees.

If the optional parameters are set, compare the parameters stored in the file to those. Set `match` true if everything agrees.

```

(PHS forests: public)+≡
  public :: phs_forest_read

(PHS forests: interfaces)+≡
  interface phs_forest_read
    module procedure phs_forest_read_file
    module procedure phs_forest_read_unit
    module procedure phs_forest_read_parse_tree
  end interface

(PHS forests: procedures)+≡
  subroutine phs_forest_read_file &
    (forest, filename, process_id, n_in, n_out, model, found, &
     md5sum_process, md5sum_model, md5sum_parameters, phs_par, match)
    type(phs_forest_t), intent(out) :: forest
    type(string_t), intent(in) :: filename
    type(string_t), intent(in) :: process_id
    integer, intent(in) :: n_in, n_out
    type(model_t), intent(in), target :: model
    logical, intent(out) :: found
    character(32), intent(in), optional :: &
      md5sum_process, md5sum_model, md5sum_parameters
    type(phs_parameters_t), intent(in), optional :: phs_par
    logical, intent(out), optional :: match
    type(parse_tree_t), target :: parse_tree
    type(stream_t), target :: stream
    type(lexer_t) :: lexer
    call lexer_init_phs_forest (lexer)
    call stream_init (stream, char (filename))
    call lexer_assign_stream (lexer, stream)
    call parse_tree_init (parse_tree, syntax_phs_forest, lexer)
    call phs_forest_read (forest, parse_tree, &
      process_id, n_in, n_out, model, found, &
      md5sum_process, md5sum_model, md5sum_parameters, phs_par, match)
    call stream_final (stream)
    call lexer_final (lexer)
    call parse_tree_final (parse_tree)
  end subroutine phs_forest_read_file

  subroutine phs_forest_read_unit &
    (forest, unit, process_id, n_in, n_out, model, found, &
     md5sum_process, md5sum_model, md5sum_parameters, phs_par, match)
    type(phs_forest_t), intent(out) :: forest
    integer, intent(in) :: unit
    type(string_t), intent(in) :: process_id
    integer, intent(in) :: n_in, n_out
    type(model_t), intent(in), target :: model
    logical, intent(out) :: found
    character(32), intent(in), optional :: &
      md5sum_process, md5sum_model, md5sum_parameters

```

```

type(phs_parameters_t), intent(in), optional :: phs_par
logical, intent(out), optional :: match
type(parse_tree_t), target :: parse_tree
type(stream_t), target :: stream
type(lexer_t) :: lexer
call lexer_init_phs_forest (lexer)
call stream_init (stream, unit)
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_phs_forest, lexer)
call phs_forest_read (forest, parse_tree, &
    process_id, n_in, n_out, model, found, &
    md5sum_process, md5sum_model, md5sum_parameters, phs_par, match)
call stream_final (stream)
call lexer_final (lexer)
call parse_tree_final (parse_tree)
end subroutine phs_forest_read_unit

subroutine phs_forest_read_parse_tree &
    (forest, parse_tree, process_id, n_in, n_out, model, found, &
    md5sum_process, md5sum_model, md5sum_parameters, phs_par, match)
type(phs_forest_t), intent(out) :: forest
type(parse_tree_t), intent(in), target :: parse_tree
type(string_t), intent(in) :: process_id
integer, intent(in) :: n_in, n_out
type(model_t), intent(in), target :: model
logical, intent(out) :: found
character(32), intent(in), optional :: &
    md5sum_process, md5sum_model, md5sum_parameters
type(phs_parameters_t), intent(in), optional :: phs_par
logical, intent(out), optional :: match
type(parse_node_t), pointer :: node_header, node_phs, node_grove
integer :: n_grove, g
integer, dimension(:), allocatable :: n_tree
integer :: t
!   call parse_tree_write (parse_tree)
node_header => parse_tree_get_process_ptr (parse_tree, process_id)
found = associated (node_header); if (.not. found) return
if (present (match)) then
    call phs_forest_check_input (node_header, &
        md5sum_process, md5sum_model, md5sum_parameters, phs_par, match)
    if (.not. match) return
end if
node_phs => parse_node_get_next_ptr (node_header)
n_grove = parse_node_get_n_sub (node_phs)
allocate (n_tree (n_grove))
do g = 1, n_grove
    node_grove => parse_node_get_sub_ptr (node_phs, g)
    n_tree(g) = parse_node_get_n_sub (node_grove) - 1
end do
call phs_forest_init (forest, n_tree, n_in, n_out)
do g = 1, n_grove
    node_grove => parse_node_get_sub_ptr (node_phs, g)
    do t = 1, n_tree(g)
        call phs_tree_set (forest%grove(g)%tree(t), &

```

```

        parse_node_get_sub_ptr (node_grove, t+1), model)
    end do
end do
end subroutine phs_forest_read_parse_tree

```

Check the input for consistency. If any MD5 sum or phase-space parameter disagrees, the phase-space file cannot be used. The MD5 sum checks are skipped if the stored MD5 sum is empty.

(*PHS forests: procedures*)+≡

```

subroutine phs_forest_check_input (pn_header, &
    md5sum_process, md5sum_model, md5sum_parameters, phs_par, match)
    type(parse_node_t), intent(in), target :: pn_header
    character(32), intent(in) :: &
        md5sum_process, md5sum_model, md5sum_parameters
    type(phs_parameters_t), intent(in) :: phs_par
    logical, intent(out) :: match
    type(parse_node_t), pointer :: pn_md5sum, pn_rval, pn_ival, pn_lval
    character(32) :: md5sum
    type(phs_parameters_t) :: phs_par_old
    character(1) :: lstr
    pn_md5sum => parse_node_get_sub_ptr (pn_header, 3)
    md5sum = parse_node_get_string (pn_md5sum)
    if (md5sum /= "" .and. md5sum /= md5sum_process) then
        call msg_message ("Rebuilding phase space (process has changed)")
        match = .false.; return
    end if
    pn_md5sum => parse_node_get_next_ptr (pn_md5sum, 3)
    md5sum = parse_node_get_string (pn_md5sum)
    if (md5sum /= "" .and. md5sum /= md5sum_model) then
        call msg_message ("Rebuilding phase space (model has changed)")
        match = .false.; return
    end if
    pn_md5sum => parse_node_get_next_ptr (pn_md5sum, 3)
    md5sum = parse_node_get_string (pn_md5sum)
    if (md5sum /= "" .and. md5sum /= md5sum_parameters) then
        call msg_message &
            ("Rebuilding phase space (model parameters have changed)")
        match = .false.; return
    end if
    pn_rval => parse_node_get_next_ptr (pn_md5sum, 3)
    phs_par_old%sqrts = parse_node_get_real (pn_rval)
    pn_rval => parse_node_get_next_ptr (pn_rval, 3)
    phs_par_old%m_threshold_s = parse_node_get_real (pn_rval)
    pn_rval => parse_node_get_next_ptr (pn_rval, 3)
    phs_par_old%m_threshold_t = parse_node_get_real (pn_rval)
    pn_ival => parse_node_get_next_ptr (pn_rval, 3)
    phs_par_old%off_shell = parse_node_get_integer (pn_ival)
    pn_ival => parse_node_get_next_ptr (pn_ival, 3)
    phs_par_old%t_channel = parse_node_get_integer (pn_ival)
    pn_lval => parse_node_get_next_ptr (pn_ival, 3)
    lstr = parse_node_get_string (pn_lval)
    read (lstr, "(L1)") phs_par_old%keep_nonresonant
    if (phs_par_old /= phs_par) then

```

```

        call msg_message &
            ("Rebuilding phase space (phase-space parameters have changed)")
        match = .false.; return
    end if
    match = .true.
end subroutine phs_forest_check_input

```

Initialize a specific tree in the forest, using the contents of the 'tree' node. First, count the bincodes, allocate an array and read them in, and make the tree. Each t -channel tree is flipped to s -channel. Then, find mappings and initialize them.

(*PHS forests: procedures*) +=

```

subroutine phs_tree_set (tree, node, model)
    type(phs_tree_t), intent(inout) :: tree
    type(parse_node_t), intent(in), target :: node
    type(model_t), intent(in), target :: model
    type(parse_node_t), pointer :: node_bincodes, node_mapping
    integer :: n_bincodes
    integer(TC), dimension(:), allocatable :: bincodes
    integer :: b, n_mappings, m
    integer(TC) :: k
    type(string_t) :: type
    integer :: pdg
    node_bincodes => parse_node_get_sub_ptr (node, 2)
    n_bincodes = parse_node_get_n_sub (node_bincodes)
    allocate (bincodes (n_bincodes))
    do b = 1, n_bincodes
        bincodes(b) = parse_node_get_integer &
            (parse_node_get_sub_ptr (node_bincodes, b))
    end do
    call phs_tree_from_array (tree, bincodes)
    call phs_tree_flip_t_to_s_channel (tree)
    call phs_tree_canonicalize (tree)
    n_mappings = parse_node_get_n_sub (node) - 2
    do m = 1, n_mappings
        node_mapping => parse_node_get_sub_ptr (node, m+2)
        k = parse_node_get_integer &
            (parse_node_get_sub_ptr (node_mapping, 2))
        type = parse_node_get_key &
            (parse_node_get_sub_ptr (node_mapping, 3))
        pdg = parse_node_get_integer &
            (parse_node_get_sub_ptr (node_mapping, 4))
        call phs_tree_init_mapping (tree, k, type, pdg, model)
    end do
end subroutine phs_tree_set

```

12.3.8 Preparation

The trees that we read from file do not carry flavor information. This is set separately:

The flavor list must be unique for a unique set of masses; if a given particle can have different flavor, the mass must be degenerate, so we can choose one of

the possible flavor combinations.

```

(PHS forests: public)+≡
  public :: phs_forest_set_flavors

(PHS forests: procedures)+≡
  subroutine phs_forest_set_flavors (forest, flv)
    type(phs_forest_t), intent(inout) :: forest
    type(flavor_t), dimension(:), intent(in) :: flv
    allocate (forest%flv (size (flv)))
    forest%flv = flv
  end subroutine phs_forest_set_flavors

```

Once the parameter set is fixed, the masses and the widths of the particles are known and the `mass_sum` arrays as well as the mapping parameters can be computed. Note that order is important: we first compute the mass sums, then the ordinary mappings. The resonances obtained here determine the effective masses, which in turn are used to implement step mappings for resonance decay products that are not mapped otherwise.

```

(PHS forests: public)+≡
  public :: phs_forest_set_parameters

(PHS forests: procedures)+≡
  subroutine phs_forest_set_parameters &
    (forest, mapping_defaults, variable_limits)
    type(phs_forest_t), intent(inout) :: forest
    type(mapping_defaults_t), intent(in) :: mapping_defaults
    logical, intent(in) :: variable_limits
    integer :: g, t
    do g = 1, size (forest%grove)
      do t = 1, size (forest%grove(g)%tree)
        call phs_tree_set_mass_sum &
          (forest%grove(g)%tree(t), forest%flv(forest%n_in+1:))
        call phs_tree_set_mapping_parameters (forest%grove(g)%tree(t), &
          mapping_defaults, variable_limits)
        call phs_tree_set_effective_masses (forest%grove(g)%tree(t))
        if (mapping_defaults%step_mapping) then
          call phs_tree_set_step_mappings (forest%grove(g)%tree(t), &
            mapping_defaults%step_mapping_exp, variable_limits)
        end if
      end do
    end do
  end subroutine phs_forest_set_parameters

```

Generate the particle combination table. Scan all trees and merge their individual combination tables. At the end, valid entries are non-zero, and they indicate the indices of a pair of particles to be combined to a new particle. If a particle is accessible by more than one tree (this is usual), only keep the first possibility.

```

(PHS forests: public)+≡
  public :: phs_forest_setup_prt_combinations

(PHS forests: procedures)+≡
  subroutine phs_forest_setup_prt_combinations (forest)
    type(phs_forest_t), intent(inout) :: forest

```

```

integer :: g, t
integer, dimension(:,:), allocatable :: tree_prt_combination
forest%prt_combination = 0
allocate (tree_prt_combination (2, size (forest%prt_combination, 2)))
do g = 1, size (forest%grove)
  do t = 1, size (forest%grove(g)%tree)
    call phs_tree_setup_prt_combinations &
      (forest%grove(g)%tree(t), tree_prt_combination)
    where (tree_prt_combination /= 0 .and. forest%prt_combination == 0)
      forest%prt_combination = tree_prt_combination
    end where
  end do
end do
end subroutine phs_forest_setup_prt_combinations

```

12.3.9 Accessing the particle arrays

Set the incoming particles from the contents of an interaction.

```

<PHS forests: public>+≡
  public :: phs_forest_set_prt_in

<PHS forests: procedures>+≡
  subroutine phs_forest_set_prt_in (forest, int, lt_cm_to_lab)
    type(phs_forest_t), intent(inout) :: forest
    type(interaction_t), intent(in) :: int
    type(lorentz_transformation_t), intent(in), optional :: lt_cm_to_lab
    if (present (lt_cm_to_lab)) then
      call phs_prt_set_momentum (forest%prt_in, &
        inverse (lt_cm_to_lab) * &
        interaction_get_momenta (int, outgoing=.false.))
    else
      call phs_prt_set_momentum (forest%prt_in, &
        interaction_get_momenta (int, outgoing=.false.))
    end if
    call phs_prt_set_msq (forest%prt_in, &
      flavor_get_mass (forest%flv(:forest%n_in)) ** 2)
    call phs_prt_set_defined (forest%prt_in)
  end subroutine phs_forest_set_prt_in

```

Combine particles as described by the particle combination table. Particle momentum sums will be calculated only if the resulting particle is contained in at least one of the trees in the current forest. The others are kept undefined.

```

<PHS forests: public>+≡
  public :: phs_forest_combine_particles

<PHS forests: procedures>+≡
  subroutine phs_forest_combine_particles (forest)
    type(phs_forest_t), intent(inout) :: forest
    integer :: k
    integer, dimension(2) :: kk
    do k = 1, size (forest%prt_combination, 2)
      kk = forest%prt_combination(:,k)

```

```

        if (kk(1) /= 0) then
            call phs_prt_combine (forest%prt(k), &
                forest%prt(kk(1)), forest%prt(kk(2)))
        end if
    end do
end subroutine phs_forest_combine_particles

```

Extract the outgoing particles and insert into an interaction.

```

<PHS forests: public>+≡
    public :: phs_forest_get_prt_out

<PHS forests: procedures>+≡
    subroutine phs_forest_get_prt_out (forest, int, lt_cm_to_lab)
        type(phs_forest_t), intent(in) :: forest
        type(interaction_t), intent(inout) :: int
        type(lorentz_transformation_t), intent(in), optional :: lt_cm_to_lab
        if (present (lt_cm_to_lab)) then
            call interaction_set_momenta (int, &
                lt_cm_to_lab * &
                phs_prt_get_momentum (forest%prt_out), outgoing=.true.)
        else
            call interaction_set_momenta (int, &
                phs_prt_get_momentum (forest%prt_out), outgoing=.true.)
        end if
    end subroutine phs_forest_get_prt_out

```

12.3.10 Find equivalences among phase-space trees

Scan phase space for equivalences. We generate the complete set of unique permutations for the given list of outgoing particles, and use this for scanning equivalences within each grove. We scan all pairs of trees, using all permutations. This implies that trivial equivalences are included, and equivalences between different trees are recorded twice. This is intentional.

```

<PHS forests: procedures>+≡
    subroutine phs_grove_set_equivalences (grove, perm_array)
        type(phs_grove_t), intent(inout) :: grove
        type(permutation_t), dimension(:), intent(in) :: perm_array
        type(equivalence_t), pointer :: eq
        integer :: t1, t2, i
        do t1 = 1, size (grove%tree)
            do t2 = 1, size (grove%tree)
                SCAN_PERM: do i = 1, size (perm_array)
                    if (phs_tree_equivalent &
                        (grove%tree(t1), grove%tree(t2), perm_array(i))) then
                        call equivalence_list_add &
                            (grove%equivalence_list, t1, t2, perm_array(i))
                        eq => grove%equivalence_list%last
                        call phs_tree_find_msq_permutation &
                            (grove%tree(t1), grove%tree(t2), eq%perm, &
                                eq%msq_perm)
                        call phs_tree_find_angle_permutation &
                            (grove%tree(t1), grove%tree(t2), eq%perm, &

```

```

                                eq%angle_perm, eq%angle_sig)
                        end if
                    end do SCAN_PERM
                end do
            end do
        end subroutine phs_grove_set_equivalences

<PHS forests: public>+=
    public :: phs_forest_set_equivalences

<PHS forests: procedures>+=
    subroutine phs_forest_set_equivalences (forest)
        type(phs_forest_t), intent(inout) :: forest
        type(permutation_t), dimension(:), allocatable :: perm_array
        integer :: i
        call permutation_array_make &
            (perm_array, flavor_get_pdg (forest%flv(forest%n_in+1:)))
        do i = 1, size (forest%grove)
            call phs_grove_set_equivalences (forest%grove(i), perm_array)
        end do
        forest%n_equivalences = sum (forest%grove%equivalence_list%length)
    end subroutine phs_forest_set_equivalences

```

12.3.11 Interface for VAMP equivalences

Transform the equivalence lists into a `vamp_equivalence_list` object. The additional information that we need is: the number of extra integration dimensions (associated to structure functions), which ones of those correspond to external event generators (so that the binning must not be adapted), and whether there is any dependence on the first azimuthal angle (so its binning may be adapted or fixed).

The permutations of masses and angles are translated into permutations of integration dimensions, where the correct mapping modes are important: `msq` values are always mapped 1:1 while azimuthal angles may need an offset by 1/2 and polar angles may need an inversion. The first azimuthal angle should not be adapted to since the dependence of the matrix element is (usually) trivial.

```

<PHS forests: public>+=
    public :: phs_forest_setup_vamp_equivalences

<PHS forests: procedures>+=
    subroutine phs_forest_setup_vamp_equivalences &
        (forest, n_dim_extra, externally_generated, azimuthal_dependence, &
         vamp_eq)
        type(phs_forest_t), intent(in) :: forest
        integer, intent(in) :: n_dim_extra
        logical, dimension(n_dim_extra), intent(in) :: externally_generated
        logical, intent(in) :: azimuthal_dependence
        type(vamp_equivalences_t), intent(out) :: vamp_eq
        integer :: n_equivalences, n_channels, n_dim, n_masses, n_angles
        integer, dimension(forest%n_dimensions + n_dim_extra) :: perm, mode
        integer :: mode_azimuthal_angle
        type(equivalence_t), pointer :: eq

```

```

integer :: i, j, g
integer :: left, right
n_equivalences = forest%n_equivalences
n_channels = forest%n_trees
n_dim = forest%n_dimensions
n_masses = forest%n_masses
n_angles = forest%n_angles
call vamp_equivalences_init &
    (vamp_eq, n_equivalences, n_channels, n_dim + n_dim_extra)
if (azimuthal_dependence) then
    mode_azimuthal_angle = VEQ_IDENTITY
else
    mode_azimuthal_angle = VEQ_INVARIANT
end if
g = 0
eq => null ()
do i = 1, n_equivalences
    if (.not. associated (eq)) then
        g = g + 1
        eq => forest%grove(g)%equivalence_list%first
    end if
    do j = 1, n_masses
        perm(j) = permute (j, eq%msq_perm)
        mode(j) = VEQ_IDENTITY
    end do
    do j = 1, n_angles
        perm(n_masses+j) = n_masses + permute (j, eq%angle_perm)
        if (j == 1) then
            mode(n_masses+j) = mode_azimuthal_angle    ! first azimuthal angle
        else if (mod(j,2) == 1) then
            mode(n_masses+j) = VEQ_SYMMETRIC           ! other azimuthal angles
        else if (eq%angle_sig(j)) then
            mode(n_masses+j) = VEQ_IDENTITY            ! polar angle +
        else
            mode(n_masses+j) = VEQ_INVERT              ! polar angle -
        end if
    end do
    do j = 1, n_dim_extra
        perm(n_dim+j) = n_dim + j
        if (externally_generated(j)) then
            mode(n_dim+j) = VEQ_INVARIANT
        else
            mode(n_dim+j) = VEQ_IDENTITY
        end if
    end do
    left = eq%left + forest%grove(g)%tree_count_offset
    right = eq%right + forest%grove(g)%tree_count_offset
    call vamp_equivalence_set (vamp_eq, i, left, right, perm, mode)
    eq => eq%next
end do
call vamp_equivalences_complete (vamp_eq)
end subroutine phs_forest_setup_vamp_equivalences

```

12.3.12 Phase-space evaluation

```
<PHS forests: public>+≡
  public :: phs_forest_evaluate_phase_space

<PHS forests: procedures>+≡
  subroutine phs_forest_evaluate_phase_space &
    (forest, channel, active, sqrts, x, phs_factor, volume, ok)
    type(phs_forest_t), intent(inout) :: forest
    integer, intent(in) :: channel
    logical, dimension(:), intent(in) :: active
    real(default), intent(in) :: sqrts
    real(default), dimension(:,:), intent(inout) :: x
    real(default), dimension(:), intent(out) :: phs_factor
    real(default), intent(out) :: volume
    logical, intent(out) :: ok
    integer :: g, t, ch, s
    integer(TC) :: k, k_root, k_in

    g = forest%grove_lookup (channel)
    t = channel - forest%grove(g)%tree_count_offset
    call phs_prt_set_undefined (forest%prt)
    call phs_prt_set_undefined (forest%prt_out)
    k_in = forest%n_tot

    do k = 1, forest%n_in
      forest%prt(ibset(0,k_in-k)) = forest%prt_in(k)
    end do

    do k = 1, forest%n_out
      call phs_prt_set_msq (forest%prt(ibset(0,k-1)), &
        flavor_get_mass (forest%flv(forest%n_in+k)) ** 2)
    end do

    k_root = 2**forest%n_out - 1
    select case (forest%n_in)
    case (1)
      forest%prt(k_root) = forest%prt_in(1)
    case (2)
      call phs_prt_combine &
        (forest%prt(k_root), forest%prt_in(1), forest%prt_in(2))
    end select
    call phs_tree_compute_momenta_from_x (forest%grove(g)%tree(t), &
      forest%prt, phs_factor(channel), volume, sqrts, x(:,channel), ok)
    if (ok) then
      !$OMP PARALLEL PRIVATE (g,t,ch,s) SHARED(forest,sqrt,x,channel)

      !$OMP DO SCHEDULE(STATIC)
      do ch = 1, forest%n_trees
        if (ch == channel) cycle
        if (active(ch)) then
          s = ch
          g = 1
          do while (s > size (forest%grove(g)%tree))
```

```

        s = s - size(forest%grove(g)%tree)
        g = g+1
    end do
    t = s

    call phs_tree_combine_particles &
        (forest%grove(g)%tree(t), forest%prt)
    call phs_tree_compute_x_from_momenta &
        (forest%grove(g)%tree(t), &
        forest%prt, phs_factor(ch), sqrts, x(:,ch))
    end if
end do
!$OMP END DO

!$OMP DO
do k = 1,forest%n_out
    forest%prt_out(k) = forest%prt(ibset(0,k-1))
end do
!$OMP END DO
!$OMP END PARALLEL
end if
end subroutine phs_forest_evaluate_phase_space

```

The first part of the previous routine, without recovering the x values. Here the PHS factor is `intent(inout)` because only one of the channels is defined.

```

<PHS forests: public>+=
    public :: phs_forest_evaluate_momenta

<PHS forests: procedures>+=
    subroutine phs_forest_evaluate_momenta &
        (forest, channel, active, sqrts, x, phs_factor, volume, ok)
        type(phs_forest_t), intent(inout) :: forest
        integer, intent(in) :: channel
        logical, dimension(:), intent(in) :: active
        real(default), intent(in) :: sqrts
        real(default), dimension(:,:), intent(inout) :: x
        real(default), dimension(:), intent(inout) :: phs_factor
        real(default), intent(out) :: volume
        logical, intent(out) :: ok
        integer :: g, t, ch, s
        integer(TC) :: k, k_root, k_in
        g = forest%grove_lookup(channel)
        t = channel - forest%grove(g)%tree_count_offset
        call phs_prt_set_undefined(forest%prt)
        call phs_prt_set_undefined(forest%prt_out)
        k_in = forest%n_tot
        forall(k = 1:forest%n_in)
            forest%prt(ibset(0,k_in-k)) = forest%prt_in(k)
        end forall
        do k = 1, forest%n_out
            call phs_prt_set_msq(forest%prt(ibset(0,k-1)), &
                flavor_get_mass(forest%flv(forest%n_in+k)) ** 2)
        end do
        k_root = 2**forest%n_out - 1
    end subroutine

```

```

select case (forest%n_in)
case (1)
    forest%prt(k_root) = forest%prt_in(1)
case (2)
    call phs_prt_combine &
        (forest%prt(k_root), forest%prt_in(1), forest%prt_in(2))
end select
call phs_tree_compute_momenta_from_x (forest%grove(g)%tree(t), &
    forest%prt, phs_factor(channel), volume, sqrts, x(:,channel), ok)
if (ok) then
    call phs_forest_combine_particles (forest)
    do k = 1, forest%n_out
        forest%prt_out(k) = forest%prt(ibset(0,k-1))
    end do
end if
end subroutine phs_forest_evaluate_momenta

```

The remainder: recover x values for all channels except for the current channel.

(PHS forests: public)+≡

```
public :: phs_forest_evaluate_other_channels
```

(PHS forests: procedures)+≡

```

subroutine phs_forest_evaluate_other_channels &
    (forest, channel, active, sqrts, x, phs_factor)
type(phs_forest_t), intent(inout) :: forest
integer, intent(in) :: channel
logical, dimension(:), intent(in) :: active
real(default), intent(in) :: sqrts
real(default), dimension(:,,:), intent(inout) :: x
real(default), dimension(:), intent(inout) :: phs_factor
integer :: g, t, ch, w, k, s
integer :: OMP_GET_NUM_THREADS

w = 0
!$OMP PARALLEL PRIVATE (g,t,ch,s,k) SHARED(forest,sqrt,x,channel,w)

!$OMP DO REDUCTION(+:w)
do g = 1, size (forest%grove)
    do t = 1, size (forest%grove(g)%tree)
        w = w+1
    end do
end do
!$OMP END DO

!$OMP DO SCHEDULE(STATIC)
do ch = 1, w
    if (ch == channel) cycle
    if (active(ch)) then
        s = ch
        g = 1
        t = 1
        do while (s > size (forest%grove(g)%tree))
            s = s - size(forest%grove(g)%tree)
            g = g+1
        end do
    end if
end do

```



```

        end do
        t = s
        call phs_tree_compute_x_from_momenta &
            (forest%grove(g)%tree(t), &
            forest%prt, phs_factor(ch), sqrts, x(:,ch))
    end if
end do
!$OMP END DO
!$OMP END PARALLEL

end subroutine phs_forest_evaluate_other_channels

```

12.3.13 Test of forest setup

Write a possible phase-space file for a $2 \rightarrow 3$ process and make the corresponding forest. Print the forest and the resulting VAMP equivalence array. Choose some in-particle momenta and a random-number array and evaluate out-particles and phase-space factors.

```

<PHS forests: public>+≡
    public :: phs_forest_test

<PHS forests: procedures>+≡
    subroutine phs_forest_test ()
        use os_interface, only: os_data_t
        type(os_data_t) :: os_data
        type(phs_forest_t) :: forest
        type(model_t), pointer :: model
        type(string_t) :: process_id
        type(flavor_t), dimension(5) :: flv
        type(vamp_equivalences_t) :: vamp_eq
        type(string_t) :: filename
        type(interaction_t) :: int
        integer :: unit
        integer, parameter :: u = 20
        integer, parameter :: n_dim_extra = 2
        logical, dimension(2), parameter :: &
            externally_generated = (/ .true., .false. /)
        logical, parameter :: azimuthal_dependence = .false.
        type(mapping_defaults_t) :: mapping_defaults
        logical :: found_process, ok
        integer :: channel, ch
        logical, dimension(4) :: active = .true.
        real(default) :: sqrts = 1000
        real(default), dimension(5,4) :: x
        real(default), dimension(4) :: factor
        real(default) :: volume
        print *, "*** Read model file"
        call syntax_model_file_init ()
        call model_list_read_model &
            (var_str("SM"), var_str("SM.mdl"), os_data, model)
        call syntax_model_file_final ()
        print *
        print *, "*** Create phase-space file 'test.phs'"
    end subroutine

```

```

call flavor_init (flv, (/ 11, -11, 11, -11, 22 /), model)
open (file="test.phs", unit=u, action="write")
write (u, *) "process foo"
write (u, *) 'md5sum_process      = "6ABA33BC2927925D0F073B1C1170780A"'
write (u, *) 'md5sum_model        = "1A0B151EE6E2DEB92D880320355A3EAB"'
write (u, *) 'md5sum_parameters   = "B6A8877058809A8BDD54753CDAB83ACE"'
write (u, *) "sqrts              = 100.00000000000000"
write (u, *) "m_threshold_s      = 50.00000000000000"
write (u, *) "m_threshold_t      = 100.00000000000000"
write (u, *) "off_shell          = 2"
write (u, *) "t_channel          = 6"
write (u, *) "keep_nonresonant = F"
write (u, *) ""
write (u, *) "  grove"
write (u, *) "    tree 3 7"
write (u, *) "      map 3 s_channel 23"
write (u, *) "    tree 5 7"
write (u, *) "    tree 6 7"
write (u, *) "  grove"
write (u, *) "    tree 9 11"
write (u, *) "      map 9 t_channel 22"
close (u)
print *
print *, "*** Read phase-space file 'test.phs'"
call syntax_phs_forest_init ()
process_id = "foo"
unit = free_unit ()
filename = "test.phs"
call phs_forest_read &
  (forest, filename, process_id, 2, 3, model, found_process)
print *
print *, "*** Set parameters, flavors, equiv, momenta"
call phs_forest_set_flavors (forest, flv)
call phs_forest_set_parameters (forest, mapping_defaults, .false.)
call phs_forest_setup_prt_combinations (forest)
call phs_forest_set_equivalences (forest)
call interaction_init (int, 2, 0, 3)
call interaction_set_momentum (int, &
  vector4_moving (500._default, 500._default, 3), 1)
call interaction_set_momentum (int, &
  vector4_moving (500._default, -500._default, 3), 2)
call phs_forest_set_prt_in (forest, int)
channel = 2
x = 0
x(:,channel) = (/ 0.3, 0.4, 0.1, 0.9, 0.6 /)
1 format (5(1x,G12.5))
print *, "Input values:"
print 1, x(:,channel)
print *
print *, "*** Evaluate phase space"
call phs_forest_evaluate_phase_space (forest, &
  channel, active, sqrts, x, factor, volume, ok)
call phs_forest_get_prt_out (forest, int)
print *, "Output values:"

```

```

do ch = 1, 4
  print 1, x(:,ch)
end do
call interaction_write (int)
print *, "factors:"
print 1, factor
print *, "volume:"
print 1, volume
call phs_forest_write (forest)
print *
print *, "*** Compute equivalences"
call phs_forest_setup_vamp_equivalences (forest, &
  n_dim_extra, externally_generated, azimuthal_dependence, &
  vamp_eq)
call vamp_equivalences_write (vamp_eq)
print *
print *, "*** Cleanup"
call vamp_equivalences_final (vamp_eq)
call phs_forest_final (forest)
call syntax_phs_forest_final ()
end subroutine phs_forest_test

```

12.4 Finding phase space parameterizations

If the phase space configuration is not found in the appropriate file, we should generate one.

The idea is to construct all Feynman diagrams subject to certain constraints which eliminate everything that is probably irrelevant for the integration. These Feynman diagrams (cascades) are grouped in groves by finding equivalence classes related by symmetry and ordered with respect to their importance (resonances). Finally, the result (or part of it) is written to file and used for the integration.

This module may eventually disappear and be replaced by CAML code. In particular, we need here a set of Feynman rules (vertices with particle codes, but not the factors). Thus, the module works for the Standard Model only.

Note that this module is stand-alone, it communicates to the main program only via the generated ASCII phase-space configuration file.

`<cascades.f90>`≡

<File header>

`module cascades`

<Use kinds>

`use kinds, only: TC, i8, i32 !NODEP!`

<Use strings>

`use limits, only: CASCADE_SET_FILL_RATIO, MAX_WARN_RESONANCE !NODEP!`

<Use file utils>

`use diagnostics !NODEP!`

`use hashes`

`use sorting`

```

    use pdg_arrays, only: UNDEFINED
    use models
    use flavors
    use phs_forests

    <Standard module head>

    <Cascades: public>

    <Cascades: parameters>

    <Cascades: types>

    <Cascades: interfaces>

contains

    <Cascades: procedures>

end module cascades

```

12.4.1 The mapping modes

The valid mapping modes, to be used below. We will make use of the convention that mappings of internal particles have a positive value. Only for positive values, the flavor code is propagated when combining cascades.

```

<Mapping modes>≡
    integer, parameter :: &
        & EXTERNAL_PRT = -1, &
        & NO_MAPPING = 0, S_CHANNEL = 1, T_CHANNEL = 2, U_CHANNEL = 3, &
        & RADIATION = 4, COLLINEAR = 5, INFRARED = 6, &
        & STEP_MAPPING_E = 11, STEP_MAPPING_H = 12

    <Cascades: parameters>≡
        <Mapping modes>

```

12.4.2 The cascade type

A cascade is essentially the same as a decay tree (both definitions may be merged in a later version). It contains a linked tree of nodes, each of which representing an internal particle. In contrast to decay trees, each node has a definite particle code. These nodes need not be modified, therefore we can use pointers and do not have to copy them. Thus, physically each cascades has only a single node, the mother particle. However, to be able to compare trees quickly, we store in addition an array of binary codes which is always sorted in ascending order. This is accompanied by a corresponding list of particle codes. The index is the location of the corresponding cascade in the cascade set, this may be used to access the daughters directly.

The real mass is the particle mass belonging to the particle code. The minimal mass is the sum of the real masses of all its daughters; this is the kinematical cutoff. The effective mass may be zero if the particle mass is below

a certain threshold; it may be the real mass if the particle is resonant; or it may be some other value.

The logical `t_channel` is set if this a t -channel line, while `initial` is true only for an initial particle. Note that both initial particles are also `t_channel` by definition, and that they are distinguished by the direction of the tree: One of them decays and is the root of the tree, while the other one is one of the leaves.

The cascade is a list of nodes (particles) which are linked via the `daughter` entries. The node is the mother particle of the decay cascade. Much of the information in the nodes is repeated in arrays, to be accessible more easily. The arrays will be kept sorted by binary codes.

The counter `n_off_shell` is increased for each internal line that is neither resonant nor log-enhanced. It is set to zero if the current line is resonant, since this implies on-shell particle production and subsequent decay.

The counter `n_t_channel` is non-negative once an initial particle is included in the tree: then, it counts the number of t -channel lines.

The `multiplicity` is the number of branchings to follow until all daughters are on-shell. A resonant or non-decaying particle has multiplicity one. Merging nodes, the multiplicities add unless the mother is a resonance. An initial or final node has multiplicity zero.

The arrays correspond to the subnode tree `tree` of the current cascade. PDG codes are stored only for those positions which are resonant, with the exception of the last entry, i.e., the current node. Other positions, in particular external legs, are assigned undefined PDG code.

A cascade is uniquely identified by its tree, the tree of PDG codes, and the tree of mappings. The tree of resonances is kept only to mask the PDG tree as described above.

$\langle \text{Cascades: types} \rangle \equiv$

```

type :: cascade_t
  private
  ! counters
  integer :: index = 0
  integer :: grove = 0
  ! status
  logical :: active = .false.
  logical :: complete = .false.
  logical :: incoming = .false.
  ! this node
  integer(TC) :: bincode = 0
  type(flavor_t) :: flv
  integer :: pdg = UNDEFINED
  logical :: is_vector = .false.
  real(default) :: m_min = 0
  real(default) :: m_rea = 0
  real(default) :: m_eff = 0
  integer :: mapping = NO_MAPPING
  logical :: on_shell = .false.
  logical :: resonant = .false.
  logical :: log_enhanced = .false.
  logical :: t_channel = .false.
  ! global tree properties

```

```

integer :: multiplicity = 0
integer :: internal = 0
integer :: n_off_shell = 0
integer :: n_resonances = 0
integer :: n_log_enhanced = 0
integer :: n_t_channel = 0
integer :: res_hash = 0
! the sub-node tree
integer :: depth = 0
integer(TC), dimension(:), allocatable :: tree
integer, dimension(:), allocatable :: tree_pdg
integer, dimension(:), allocatable :: tree_mapping
logical, dimension(:), allocatable :: tree_resonant
! branch connections
logical :: has_children = .false.
type(cascade_t), pointer :: daughter1 => null ()
type(cascade_t), pointer :: daughter2 => null ()
type(cascade_t), pointer :: mother => null ()
! next in list
type(cascade_t), pointer :: next => null ()
end type cascade_t

```

<Cascades: procedures>≡

```

subroutine cascade_init (cascade, depth)
  type(cascade_t), intent(out) :: cascade
  integer, intent(in) :: depth
  integer, save :: index = 0
  index = cascade_index ()
  cascade%index = index
  cascade%depth = depth
  cascade%active = .true.
  allocate (cascade%tree (depth))
  allocate (cascade%tree_pdg (depth))
  allocate (cascade%tree_mapping (depth))
  allocate (cascade%tree_resonant (depth))
end subroutine cascade_init

```

Keep and increment a global index

<Cascades: procedures>+≡

```

function cascade_index (seed) result (index)
  integer :: index
  integer, intent(in), optional :: seed
  integer, save :: i = 0
  if (present (seed)) i = seed
  i = i + 1
  index = i
end function cascade_index

```

We need three versions of writing cascades. This goes to the phase-space file:

<Cascades: procedures>+≡

```

subroutine cascade_write_file_format (cascade, model, unit)
  type(cascade_t), intent(in) :: cascade
  type(model_t), intent(in), target :: model

```

```

integer, intent(in), optional :: unit
type(flavor_t) :: flv
integer :: u, i
1  format(3x,A,1x,40(1x,I4))
2  format(3x,A,1x,I3,1x,A,1x,I7,1x,'!',1x,A)
u = output_unit (unit); if (u < 0) return
!  write (u, 1) "tree", reduced (cascade%tree)
call write_reduced (cascade%tree, u)
do i = 1, cascade%depth
  call flavor_init (flv, cascade%tree_pdg(i), model)
  select case (cascade%tree_mapping(i))
  case (NO_MAPPING, EXTERNAL_PRT)
  case (S_CHANNEL)
    write(u,2) 'map', &
      cascade%tree(i), 's_channel', abs (cascade%tree_pdg(i)), &
      char (flavor_get_name (flv))
  case (T_CHANNEL)
    write(u,2) 'map', &
      cascade%tree(i), 't_channel', abs (cascade%tree_pdg(i)), &
      char (flavor_get_name (flv))
  case (U_CHANNEL)
    write(u,2) 'map', &
      cascade%tree(i), 'u_channel', abs (cascade%tree_pdg(i)), &
      char (flavor_get_name (flv))
  case (RADIATION)
    write(u,2) 'map', &
      cascade%tree(i), 'radiation', abs (cascade%tree_pdg(i)), &
      char (flavor_get_name (flv))
  case (COLLINEAR)
    write(u,2) 'map', &
      cascade%tree(i), 'collinear', abs (cascade%tree_pdg(i)), &
      char (flavor_get_name (flv))
  case (INFRARED)
    write(u,2) 'map', &
      cascade%tree(i), 'infrared ', abs (cascade%tree_pdg(i)), &
      char (flavor_get_name (flv))
  case default
    call msg_bug (" Impossible mapping mode encountered")
  end select
end do
contains
subroutine write_reduced (array, unit)
  integer(TC), dimension(:), intent(in) :: array
  integer, intent(in) :: unit
  integer :: i
  write (u, "(3x,A,1x)", advance="no") "tree"
  do i = 1, size (array)
    if (decay_level (array(i)) > 1) then
      write (u, "(1x,I0)", advance="no") array(i)
    end if
  end do
end subroutine write_reduced
! ICE in gfortran 4.6.0
! function reduced (array)

```

```

! integer(TC), dimension(:), allocatable :: reduced
! integer(TC), dimension(:), intent(in) :: array
! logical, dimension(size(array)) :: mask
! mask = decay_level (array) > 1
! allocate (reduced (count (mask)))
! reduced = pack (array, mask)
! end function reduced
elemental function decay_level (k) result (l)
  integer(TC), intent(in) :: k
  integer :: l
  integer :: i
  l = 0
  do i = 0, bit_size(k) - 1
    if (btest(k,i)) l = l + 1
  end do
end function decay_level
subroutine start_comment (u)
  integer, intent(in) :: u
  write(u, '(1x,A)', advance='no') '!'
end subroutine start_comment
end subroutine cascade_write_file_format

```

This creates metapost source for graphical display:

(Cascades: procedures)+≡

```

subroutine cascade_write_graph_format (cascade, count, unit)
  type(cascade_t), intent(in) :: cascade
  integer, intent(in) :: count
  integer, intent(in), optional :: unit
  integer :: u
  integer(TC) :: mask
  type(string_t) :: left_str, right_str
  u = output_unit (unit); if (u < 0) return
  mask = 2**((cascade%depth+3)/2) - 1
  left_str = ""
  right_str = ""
  write (u, '(A)') "\begin{minipage}{105pt}"
  write (u, '(A)') "\vspace{30pt}"
  write (u, '(A)') "\begin{center}"
  write (u, '(A)') "\begin{fmfgraph*}(55,55)"
  call graph_write (cascade, mask)
  write (u, '(A)') "\fmfleft{" // char (extract (left_str, 2)) // "}"
  write (u, '(A)') "\fmfright{" // char (extract (right_str, 2)) // "}"
  write (u, '(A)') "\end{fmfgraph*}\\"
  write (u, '(A,I5,A)') "\fbox{$", count, "$}"
  write (u, '(A)') "\end{center}"
  write (u, '(A)') "\end{minipage}"
  write (u, '(A)') "%"
contains
  recursive subroutine graph_write (cascade, mask, reverse)
    type(cascade_t), intent(in) :: cascade
    integer(TC), intent(in) :: mask
    logical, intent(in), optional :: reverse
    logical :: rev
    rev = .false.; if (present(reverse)) rev = reverse

```



```

if (cascade%has_children) then
  if (.not.rev) then
    call vertex_write (cascade, cascade%daughter1, mask)
    call vertex_write (cascade, cascade%daughter2, mask)
  else
    call vertex_write (cascade, cascade%daughter2, mask, .true.)
    call vertex_write (cascade, cascade%daughter1, mask, .true.)
  end if
  if (cascade%complete) then
    call vertex_write (cascade, cascade%mother, mask, .true.)
    write (u, '(A,I0,A)') "\fmfv{d.shape=square}{v0}"
  end if
else
  if (cascade%incoming) then
    call external_write (cascade%bincode, &
      flavor_get_tex_name (flavor_anti (cascade%flv)), left_str)
  else
    call external_write (cascade%bincode, &
      flavor_get_tex_name (cascade%flv), right_str)
  end if
end if
end subroutine graph_write
recursive subroutine vertex_write (cascade, daughter, mask, reverse)
  type(cascade_t), intent(in) :: cascade, daughter
  integer(TC), intent(in) :: mask
  logical, intent(in), optional :: reverse
  integer :: bincode
  if (cascade%complete) then
    bincode = 0
  else
    bincode = cascade%bincode
  end if
  call graph_write (daughter, mask, reverse)
  if (daughter%has_children) then
    call line_write (bincode, daughter%bincode, daughter%flv, &
      mapping=daughter%mapping)
  else
    call line_write (bincode, daughter%bincode, daughter%flv)
  end if
end subroutine vertex_write
subroutine line_write (i1, i2, flv, mapping)
  integer(TC), intent(in) :: i1, i2
  type(flavor_t), intent(in) :: flv
  integer, intent(in), optional :: mapping
  integer :: k1, k2
  type(string_t) :: prt_type
  select case (flavor_get_spin_type (flv))
  case (SCALAR);      prt_type = "plain"
  case (SPINOR);      prt_type = "fermion"
  case (VECTOR);      prt_type = "boson"
  case (VECTORSPINOR); prt_type = "fermion"
  case (TENSOR);      prt_type = "dbl_wiggly"
  case default;       prt_type = "dashes"
  end select
end subroutine line_write

```

```

if (flavor_is_antiparticle (flv)) then
  k1 = i2; k2 = i1
else
  k1 = i1; k2 = i2
end if
if (present (mapping)) then
  select case (mapping)
  case (S_CHANNEL)
    write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
      & ",f=blue,lab=\sm\blue$" // &
      & char (flavor_get_tex_name (flv)) // "$}" // &
      & "{v", k1, ",v", k2, "}"
  case (T_CHANNEL, U_CHANNEL)
    write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
      & ",f=cyan,lab=\sm\cyan$" // &
      & char (flavor_get_tex_name (flv)) // "$}" // &
      & "{v", k1, ",v", k2, "}"
  case (RADIATION)
    write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
      & ",f=green,lab=\sm\green$" // &
      & char (flavor_get_tex_name (flv)) // "$}" // &
      & "{v", k1, ",v", k2, "}"
  case (COLLINEAR)
    write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
      & ",f=magenta,lab=\sm\magenta$" // &
      & char (flavor_get_tex_name (flv)) // "$}" // &
      & "{v", k1, ",v", k2, "}"
  case (INFRARED)
    write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
      & ",f=red,lab=\sm\red$" // &
      & char (flavor_get_tex_name (flv)) // "$}" // &
      & "{v", k1, ",v", k2, "}"
  case default
    write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
      & ",f=black}" // &
      & "{v", k1, ",v", k2, "}"
  end select
else
  write (u, '(A,I0,A,I0,A)') "\fmf{" // char (prt_type) // &
    & "}" // &
    & "{v", k1, ",v", k2, "}"
end if
end subroutine line_write
subroutine external_write (bincode, name, ext_str)
  integer(TC), intent(in) :: bincode
  type(string_t), intent(in) :: name
  type(string_t), intent(inout) :: ext_str
  character(len=20) :: str
  write (str, '(A2,I0)') "v", bincode
  ext_str = ext_str // trim (str)
  write (u, '(A,I0,A,I0,A)') "\fmflabel{\sm$" &
    // char (name) &
    // "\",(" , bincode, ")" &
    // "$}{v", bincode, "}"

```

```

end subroutine external_write
end subroutine cascade_write_graph_format

```

This is for screen/debugging output:

(Cascades: procedures)+≡

```

subroutine cascade_write (cascade, unit)
  type(cascade_t), intent(in) :: cascade
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, *) 'Cascade #', cascade%index
  write (u, *) ' Grove:      #', cascade%grove
  write (u, *) ' act/cmp/inc: ', &
    cascade%active, cascade%complete, cascade%incoming
  write (u, *) ' Bincode:      ', cascade%bincode
  write (u, "(1x,A)", advance="no") ' Flavor:      '
  call flavor_write (cascade%flv, unit)
  write (u, *) ' Active flavor:', cascade%pdg
  write (u, *) ' Is vector:      ', cascade%is_vector
  write (u, *) ' Mass (m/r/e): ', &
    cascade%m_min, cascade%m_rea, cascade%m_eff
  write (u, *) ' Mapping:      ', cascade%mapping
  write (u, *) ' res/log/tch: ', &
    cascade%resonant, cascade%log_enhanced, cascade%t_channel
  write (u, *) ' Multiplicity: ', cascade%multiplicity
  write (u, *) ' n intern/off: ', cascade%internal, cascade%n_off_shell
  write (u, *) ' n res/log/tch:', &
    cascade%n_resonances, cascade%n_log_enhanced, cascade%n_t_channel
  write (u, *) ' Depth:      ', cascade%depth
  write (u, *) ' Tree:      ', cascade%tree
  write (u, *) ' Tree(PDG): ', cascade%tree_pdg
  write (u, *) ' Tree(mapping):', cascade%tree_mapping
  write (u, *) ' Tree(res): ', cascade%tree_resonant
  if (cascade%has_children) then
    write (u, *) ' Daughter1/2: ', &
      cascade%daughter1%index, cascade%daughter2%index
  end if
  if (associated (cascade%mother)) then
    write (u, *) ' Mother:      ', cascade%mother%index
  end if
end subroutine cascade_write

```

12.4.3 Creating new cascades

This initializes a single-particle cascade (external, final state). The PDG entry in the tree is set undefined because the cascade is not resonant. However, the flavor entry is set, so the cascade flavor is identified nevertheless.

(Cascades: procedures)+≡

```

subroutine cascade_init_outgoing (cascade, flv, pos, m_thr)
  type(cascade_t), intent(out) :: cascade
  type(flavor_t), intent(in) :: flv
  integer, intent(in) :: pos

```

```

real(default), intent(in) :: m_thr
call cascade_init (cascade, 1)
cascade%bincode = ibset (0_TC, pos-1)
cascade%flv = flv
cascade%pdg = abs (flavor_get_pdg (cascade%flv))
cascade%is_vector = flavor_get_spin_type (flv) == VECTOR
cascade%m_min = flavor_get_mass (flv)
cascade%m_rea = cascade%m_min
if (cascade%m_rea >= m_thr) then
    cascade%m_eff = cascade%m_rea
end if
cascade%on_shell = .true.
cascade%multiplicity = 1
cascade%tree(1) = cascade%bincode
cascade%tree_pdg(1) = cascade%pdg
cascade%tree_mapping(1) = EXTERNAL_PRT
cascade%tree_resonant(1) = .false.
end subroutine cascade_init_outgoing

```

The same for an incoming line:

```

<Cascades: procedures>+≡
subroutine cascade_init_incoming (cascade, flv, pos, m_thr)
    type(cascade_t), intent(out) :: cascade
    type(flavor_t), intent(in) :: flv
    integer, intent(in) :: pos
    real(default), intent(in) :: m_thr
    call cascade_init (cascade, 1)
    cascade%incoming = .true.
    cascade%bincode = ibset (0_TC, pos-1)
    cascade%flv = flavor_anti (flv)
    cascade%pdg = abs (flavor_get_pdg (flv))
    cascade%is_vector = flavor_get_spin_type (flv) == VECTOR
    cascade%m_min = flavor_get_mass (flv)
    cascade%m_rea = cascade%m_min
    if (cascade%m_rea >= m_thr) then
        cascade%m_eff = cascade%m_rea
    end if
    cascade%on_shell = .true.
    cascade%n_t_channel = 0
    cascade%n_off_shell = 0
    cascade%tree(1) = cascade%bincode
    cascade%tree_pdg(1) = cascade%pdg
    cascade%tree_mapping(1) = EXTERNAL_PRT
    cascade%tree_resonant(1) = .false.
end subroutine cascade_init_incoming

```

12.4.4 Tools

This function returns true if the two cascades share no common external particle. This is a requirement for joining them.

```

<Cascades: interfaces>≡
interface operator(.disjunct.)

```

```

    module procedure cascade_disjunct
end interface

```

```

<Cascades: procedures>+≡
function cascade_disjunct (cascade1, cascade2) result (flag)
    logical :: flag
    type(cascade_t), intent(in) :: cascade1, cascade2
    flag = iand (cascade1%bincode, cascade2%bincode) == 0
end function cascade_disjunct

```

Compute a hash code for the resonance pattern of a cascade. We count the number of times each particle appears as a resonance.

We pack the PDG codes of the resonances in two arrays (s-channel and t-channel), sort them both, concatenate the results, transfer to i8 integers, and compute the hash code from this byte stream.

```

<Cascades: procedures>+≡
subroutine cascade_assign_resonance_hash (cascade)
    type(cascade_t), intent(inout) :: cascade
    integer(i8), dimension(1) :: mold
    cascade%res_hash = hash (transfer &
        (concat (sort (pack (cascade%tree_pdg, &
            cascade%tree_resonant)), &
            sort (pack (cascade%tree_pdg, &
                cascade%tree_mapping == T_CHANNEL .or. &
                cascade%tree_mapping == U_CHANNEL))), &
        mold))
end subroutine cascade_assign_resonance_hash

```

12.4.5 Hash entries for cascades

We will set up a hash array which contains keys of and pointers to cascades. We hold a list of cascade (pointers) within each bucket. This is not for collision resolution, but for keeping similar, but unequal cascades together.

```

<Cascades: types>+≡
type :: cascade_p
    type(cascade_t), pointer :: cascade => null ()
    type(cascade_p), pointer :: next => null ()
end type cascade_p

```

Here is the bucket or hash entry type:

```

<Cascades: types>+≡
type :: hash_entry_t
    integer(i32) :: hashval = 0
    integer(i8), dimension(:), allocatable :: key
    type(cascade_p), pointer :: first => null ()
    type(cascade_p), pointer :: last => null ()
end type hash_entry_t

```

Finalize: just deallocate the list; the contents are just pointers.

```
(Cascades: procedures)+=≡
subroutine hash_entry_final (hash_entry)
  type(hash_entry_t), intent(inout) :: hash_entry
  type(cascade_p), pointer :: current
  do while (associated (hash_entry%first))
    current => hash_entry%first
    hash_entry%first => current%next
    deallocate (current)
  end do
end subroutine hash_entry_final
```

Output: concise format for debugging, just list cascade indices.

```
(Cascades: procedures)+=≡
subroutine hash_entry_write (hash_entry, unit)
  type(hash_entry_t), intent(in) :: hash_entry
  integer, intent(in), optional :: unit
  type(cascade_p), pointer :: current
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, "(1x,A)", advance="no") "Entry:"
  do i = 1, size (hash_entry%key)
    write (u, "(1x,I0)", advance="no") hash_entry%key(i)
  end do
  write (u, "(1x,A)", advance="no") "->"
  current => hash_entry%first
  do while (associated (current))
    write (u, "(1x,I7)", advance="no") current%cascade%index
    current => current%next
  end do
  write (u, *)
end subroutine hash_entry_write
```

This function adds a cascade pointer to the bucket. If ok is present, check first if it is already there and return failure if yes. If `cascade_ptr` is also present, set it to the current cascade if successful. If not, set it to the cascade that is already there.

```
(Cascades: procedures)+=≡
subroutine hash_entry_add_cascade_ptr (hash_entry, cascade, ok, cascade_ptr)
  type(hash_entry_t), intent(inout) :: hash_entry
  type(cascade_t), intent(in), target :: cascade
  logical, intent(out), optional :: ok
  type(cascade_t), optional, pointer :: cascade_ptr
  type(cascade_p), pointer :: current
  if (present (ok)) then
    call hash_entry_check_cascade (hash_entry, cascade, ok, cascade_ptr)
    if (.not. ok) return
  end if
  allocate (current)
  current%cascade => cascade
  if (associated (hash_entry%last)) then
    hash_entry%last%next => current
```

```

else
    hash_entry%first => current
end if
hash_entry%last => current
end subroutine hash_entry_add_cascade_ptr

```

This function checks whether a cascade is already in the bucket. For incomplete cascades, we look for an exact match. It should suffice to verify the tree, the PDG codes, and the mapping modes. This is the information that is written to the phase space file.

For complete cascades, we ignore the PDG code at positions with mappings infrared, collinear, or t/u-channel. Thus a cascade which is distinguished only by PDG code at such places, is flagged existent. If the convention is followed that light particles come before heavier ones (in the model definition), this ensures that the lightest particle is kept in the appropriate place, corresponding to the strongest peak.

For external cascades (incoming/outgoing) we take the PDG code into account even though it is zeroed in the PDG-code tree.

(Cascades: procedures)+≡

```

subroutine hash_entry_check_cascade (hash_entry, cascade, ok, cascade_ptr)
    type(hash_entry_t), intent(in), target :: hash_entry
    type(cascade_t), intent(in), target :: cascade
    logical, intent(out) :: ok
    type(cascade_ptr), optional, pointer :: cascade_ptr
    type(cascade_p), pointer :: current
    integer, dimension(:), allocatable :: tree_pdg
    ok = .true.
    allocate (tree_pdg (size (cascade%tree_pdg)))
    if (cascade%complete) then
        where (cascade%tree_mapping == INFRARED .or. &
             cascade%tree_mapping == COLLINEAR .or. &
             cascade%tree_mapping == T_CHANNEL .or. &
             cascade%tree_mapping == U_CHANNEL)
            tree_pdg = 0
        elsewhere
            tree_pdg = cascade%tree_pdg
        end where
    else
        tree_pdg = cascade%tree_pdg
    end if
    current => hash_entry%first
    do while (associated (current))
        if (current%cascade%depth == cascade%depth) then
            if (all (current%cascade%tree == cascade%tree)) then
                if (all (current%cascade%tree_mapping == cascade%tree_mapping)) &
                    then
                    if (all (current%cascade%tree_pdg .match. tree_pdg)) then
                        if (present (cascade_ptr)) cascade_ptr => current%cascade
                        ok = .false.; return
                    end if
                end if
            end if
        end if
    end if
end if
end if

```

```

        current => current%next
    end do
    if (present (cascade_ptr)) cascade_ptr => cascade
end subroutine hash_entry_check_cascade

```

For PDG codes, we specify that the undefined code matches any code. This is already defined for flavor objects, but here we need it for the codes themselves.

```

<Cascades: interfaces>+≡
    interface operator(.match.)
        module procedure pdg_match
    end interface

<Cascades: procedures>+≡
    elemental function pdg_match (pdg1, pdg2) result (flag)
        logical :: flag
        integer(TC), intent(in) :: pdg1, pdg2
        select case (pdg1)
        case (0)
            flag = .true.
        case default
            select case (pdg2)
            case (0)
                flag = .true.
            case default
                flag = pdg1 == pdg2
            end select
        end select
    end function pdg_match

```

12.4.6 The cascade set

The cascade set will later be transformed into the decay forest. It is set up as a linked list. In addition to the usual **first** and **last** pointers, there is a **first_t** pointer which points to the first t-channel cascade (after all s-channel cascades), and a **first_k** pointer which points to the first final cascade (with a keystone).

As an auxiliary device, the object contains a hash array with associated parameters where an additional pointer is stored for each cascade. The keys are made from the relevant cascade data. This hash is used for fast detection (and thus avoidance) of double entries in the cascade list.

```

<Cascades: public>≡
    public :: cascade_set_t

<Cascades: types>+≡
    type :: cascade_set_t
        private
        type(model_t), pointer :: model
        integer :: n_in, n_out, n_tot
        type(flavor_t), dimension(:,,:), allocatable :: flv
        integer :: depth_out, depth_tot
        real(default) :: sqrts = 0
        real(default) :: m_threshold_s = 0
        real(default) :: m_threshold_t = 0
    end type

```



```

integer :: off_shell = 0
integer :: t_channel = 0
logical :: keep_nonresonant
integer :: n_groves = 0
! The cascade list
type(cascade_t), pointer :: first => null ()
type(cascade_t), pointer :: last => null ()
type(cascade_t), pointer :: first_t => null ()
type(cascade_t), pointer :: first_k => null ()
! The hashtable
integer :: n_entries = 0
real :: fill_ratio = 0
integer :: n_entries_max = 0
integer(i32) :: mask = 0
logical :: fatal_beam_decay = .true.
type(hash_entry_t), dimension(:), allocatable :: entry
end type cascade_set_t

```

Return true if there are cascades which are active and complete, so the phase space file would be nonempty.

```

<Cascades: public>+≡
  public :: cascade_set_is_valid

<Cascades: procedures>+≡
  function cascade_set_is_valid (cascade_set) result (flag)
    logical :: flag
    type(cascade_set_t), intent(in) :: cascade_set
    type(cascade_t), pointer :: cascade
    flag = .false.
    cascade => cascade_set%first_k
    do while (associated (cascade))
      if (cascade%active .and. cascade%complete) then
        flag = .true.
        return
      end if
      cascade => cascade%next
    end do
  end function cascade_set_is_valid

```

The initializer sets up the hash table with some initial size guessed by looking at the number of external particles. We choose 256 for 3 external particles and a factor of 4 for each additional particle, limited at $2^{30}=1\text{G}$.

```

<Limits: public parameters>+≡
  real, parameter, public :: CASCADE_SET_FILL_RATIO = 0.1

<Cascades: procedures>+≡
  subroutine cascade_set_init (cascade_set, model, n_in, n_out, phs_par, &
    fatal_beam_decay, flv)
    type(cascade_set_t), intent(out) :: cascade_set
    type(model_t), intent(in), target :: model
    integer, intent(in) :: n_in, n_out
    type(phs_parameters_t), intent(in) :: phs_par
    logical, intent(in) :: fatal_beam_decay
    type(flavor_t), dimension(:,:), intent(in), optional :: flv

```

```

integer :: size_guess
cascade_set%model => model
cascade_set%n_in = n_in
cascade_set%n_out = n_out
cascade_set%n_tot = n_in + n_out
if (present (flv)) then
    allocate (cascade_set%flv (size (flv, 1), size (flv, 2)))
    call flavor_init (cascade_set%flv, flavor_get_pdg (flv), model)
end if
select case (n_in)
case (1); cascade_set%depth_out = 2 * n_out - 3
case (2); cascade_set%depth_out = 2 * n_out - 1
end select
cascade_set%depth_tot = 2 * cascade_set%n_tot - 3
cascade_set%sqrts = phs_par%sqrts
cascade_set%m_threshold_s = phs_par%m_threshold_s
cascade_set%m_threshold_t = phs_par%m_threshold_t
cascade_set%off_shell = phs_par%off_shell
cascade_set%t_channel = phs_par%t_channel
cascade_set%keep_nonresonant = phs_par%keep_nonresonant
cascade_set%fill_ratio = CASCADE_SET_FILL_RATIO
size_guess = ishft (256, min (2 * (cascade_set%n_tot - 3), 22))
cascade_set%n_entries_max = size_guess * cascade_set%fill_ratio
cascade_set%mask = size_guess - 1
allocate (cascade_set%entry (0:cascade_set%mask))
cascade_set%fatal_beam_decay = fatal_beam_decay
end subroutine cascade_set_init

```

The finalizer has to delete both the hash and the list. We assume that the hash only contains pointers, so it is simply deallocated, while the list entries are physically deleted.

```

<Cascades: public>+≡
public :: cascade_set_final

<Cascades: procedures>+≡
subroutine cascade_set_final (cascade_set)
type(cascade_set_t), intent(inout), target :: cascade_set
type(cascade_t), pointer :: current
if (allocated (cascade_set%entry)) deallocate (cascade_set%entry)
do while (associated (cascade_set%first))
    current => cascade_set%first
    cascade_set%first => cascade_set%first%next
    deallocate (current)
end do
end subroutine cascade_set_final

```

Write the process in ASCII format, in columns that are headed by the corresponding bincode.

```

<Cascades: public>+≡
public :: cascade_set_write_process_bincode_format

<Cascades: procedures>+≡
subroutine cascade_set_write_process_bincode_format (cascade_set, unit)
type(cascade_set_t), intent(in), target :: cascade_set

```

```

integer, intent(in), optional :: unit
integer, dimension(:), allocatable :: bincode, field_width
integer :: n_in, n_out, n_tot, n_flv
integer :: u, f, i, bc
character(20) :: str
type(string_t) :: fmt_head
type(string_t), dimension(:), allocatable :: fmt_proc
u = output_unit (unit); if (u < 0) return
if (.not. allocated (cascade_set%flv)) return
write (u, "('!',1x,A)") "List of subprocesses with particle bincodes:"
n_in = cascade_set%n_in
n_out = cascade_set%n_out
n_tot = cascade_set%n_tot
n_flv = size (cascade_set%flv, 2)
allocate (bincode (n_tot), field_width (n_tot), fmt_proc (n_tot))
bc = 1
do i = 1, n_out
    bincode(n_in + i) = bc
    bc = 2 * bc
end do
do i = n_in, 1, -1
    bincode(i) = bc
    bc = 2 * bc
end do
do i = 1, n_tot
    write (str, "(I0)") bincode(i)
    field_width(i) = len_trim (str)
    do f = 1, n_flv
        field_width(i) = max (field_width(i), &
            len (flavor_get_name (cascade_set%flv(i,f))))
    end do
end do
fmt_head = "('!'"
do i = 1, n_tot
    fmt_head = fmt_head // ",1x,"
    fmt_proc(i) = "(1x,"
    write (str, "(I0)") field_width(i)
    fmt_head = fmt_head // "I" // trim(str)
    fmt_proc(i) = fmt_proc(i) // "A" // trim(str)
    if (i == n_in) then
        fmt_head = fmt_head // ",1x,' '"
    end if
end do
fmt_proc = fmt_proc // ")"
fmt_head = fmt_head // ")"
write (u, char (fmt_head)) bincode
do f = 1, n_flv
    write (u, "('!'", advance="no")
    do i = 1, n_tot
        write (u, char (fmt_proc(i)), advance="no") &
            char (flavor_get_name (cascade_set%flv(i,f)))
        if (i == n_in) write (u, "(1x,'=>'", advance="no")
    end do
    write (u, *)

```

```

end do
write (u, char (fmt_head)) bincode
end subroutine cascade_set_write_process_bincode_format

```

Write the process as a L^AT_EX expression.

<Cascades: procedures>+≡

```

subroutine cascade_set_write_process_tex_format (cascade_set, unit)
  type(cascade_set_t), intent(in), target :: cascade_set
  integer, intent(in), optional :: unit
  integer :: u, f, i
  u = output_unit (unit); if (u < 0) return
  if (.not. allocated (cascade_set%flv)) return
  write (u, "(A)") "\begin{align*}"
  do f = 1, size (cascade_set%flv, 2)
    do i = 1, cascade_set%n_in
      if (i > 1) write (u, "(A)", advance="no") "\quad "
      write (u, "(A)", advance="no") &
        char (flavor_get_tex_name (cascade_set%flv(i,f)))
    end do
    write (u, "(A)", advance="no") "\quad &\to\quad "
    do i = cascade_set%n_in + 1, cascade_set%n_tot
      if (i > cascade_set%n_in + 1) write (u, "(A)", advance="no") "\quad "
      write (u, "(A)", advance="no") &
        char (flavor_get_tex_name (cascade_set%flv(i,f)))
    end do
    if (f < size (cascade_set%flv, 2)) then
      write (u, "(A)") "\\ "
    else
      write (u, "(A)") ""
    end if
  end do
  write (u, "(A)") "\end{align*}"
end subroutine cascade_set_write_process_tex_format

```

Three output routines: phase-space file, graph source code, and screen output.

This version generates the phase space file. It deals only with complete cascades.

<Cascades: public>+≡

```

public :: cascade_set_write_file_format

```

<Cascades: procedures>+≡

```

subroutine cascade_set_write_file_format (cascade_set, unit)
  type(cascade_set_t), intent(in), target :: cascade_set
  integer, intent(in), optional :: unit
  type(cascade_t), pointer :: cascade
  integer :: u, grove, count
  logical :: first_in_grove
  u = output_unit (unit); if (u < 0) return
  count = 0
  do grove = 1, cascade_set%n_groves
    first_in_grove = .true.
    cascade => cascade_set%first_k
    do while (associated (cascade))

```

```

if (cascade%active .and. cascade%complete) then
  if (cascade%grove == grove) then
    if (first_in_grove) then
      first_in_grove = .false.
      write (u, *)
      write (u, "(1x,'!',1x,A,1x,I0,A)", advance='no') &
        'Multiplicity =', cascade%multiplicity, ","
      select case (cascade%n_resonances)
      case (0)
        write (u, '(1x,A)', advance='no') 'no resonances, '
      case (1)
        write (u, '(1x,A)', advance='no') ' 1 resonance, '
      case default
        write (u, '(1x,I0,1x,A)', advance='no') &
          cascade%n_resonances, 'resonances, '
      end select
      write (u, '(1x,I0,1x,A)', advance='no') &
        cascade%n_log_enhanced, 'logs, '
      write (u, '(1x,I0,1x,A)', advance='no') &
        cascade%n_off_shell, 'off-shell, '
      select case (cascade%n_t_channel)
      case (0); write (u, '(1x,A)') 's-channel graph'
      case (1); write (u, '(1x,A)') ' 1 t-channel line'
      case default
        write(u,'(1x,I0,1x,A)') &
          cascade%n_t_channel, 't-channel lines'
      end select
      write (u, '(1x,A,I0)') 'grove #', grove
    end if
    count = count + 1
    write (u, "(1x,'!',1x,A,1x)", advance="no") "Channel #"
    write (u, *) count
    call cascade_write_file_format (cascade, cascade_set%model, u)
  end if
end if
cascade => cascade%next
end do
end do
end subroutine cascade_set_write_file_format

```

This is the graph output format, the driver-file

```

<Cascades: public>+≡
  public :: cascade_set_write_graph_format

<Cascades: procedures>+≡
  subroutine cascade_set_write_graph_format &
    (cascade_set, filename, process_id, unit)
    type(cascade_set_t), intent(in), target :: cascade_set
    type(string_t), intent(in) :: filename, process_id
    integer, intent(in), optional :: unit
    type(cascade_t), pointer :: cascade
    integer :: u, grove, count, pgcount
    logical :: first_in_grove
    u = output_unit (unit); if (u < 0) return

```

```

write (u, '(A)') "\documentclass[10pt]{article}"
write (u, '(A)') "\usepackage{amsmath}"
write (u, '(A)') "\usepackage{feynmp}"
write (u, '(A)') "\usepackage{url}"
write (u, '(A)') "\usepackage{color}"
write (u, *)
write (u, '(A)') "\textwidth 18.5cm"
write (u, '(A)') "\evensidemargin -1.5cm"
write (u, '(A)') "\oddsidemargin -1.5cm"
write (u, *)
write (u, '(A)') "\newcommand{\blue}{\color{blue}}"
write (u, '(A)') "\newcommand{\green}{\color{green}}"
write (u, '(A)') "\newcommand{\red}{\color{red}}"
write (u, '(A)') "\newcommand{\magenta}{\color{magenta}}"
write (u, '(A)') "\newcommand{\cyan}{\color{cyan}}"
write (u, '(A)') "\newcommand{\sm}{\footnotesize}"
write (u, '(A)') "\setlength{\parindent}{0pt}"
write (u, '(A)') "\setlength{\parsep}{20pt}"
write (u, *)
write (u, '(A)') "\begin{document}"
write (u, '(A)') "\begin{fmffile}{ " // char (filename) // "}"
write (u, '(A)') "\fmfcmd{color magenta; magenta = red + blue;}"
write (u, '(A)') "\fmfcmd{color cyan; cyan = green + blue;}"
write (u, '(A)') "\begin{fmfshrink}{0.5}"
write (u, '(A)') "\begin{flushleft}"
write (u, *)
write (u, '(A)') "\noindent" // &
& "\textbf{\large\texttt{WHIZARD}} phase space channels" // &
& "\hfill\today"
write (u, *)
write (u, '(A)') "\vspace{10pt}"
write (u, '(A)') "\noindent" // &
& "\textbf{Process:} \url{" // char (process_id) // "}"
call cascade_set_write_process_tex_format (cascade_set, u)
write (u, *)
write (u, '(A)') "\noindent" // &
& "\textbf{Note:} These are pseudo Feynman graphs that " // &
& "visualize phase-space parameterizations " // &
& "(‘‘integration channels’’). " // &
& "They do \emph{not} indicate Feynman graphs used for the " // &
& "matrix element."
write (u, *)
write (u, '(A)') "\textbf{Color code:} " // &
& "{\blue resonance,} " // &
& "{\cyan t-channel,} " // &
& "{\green radiation,} " // &
& "{\red infrared,} " // &
& "{\magenta collinear,} " // &
& "external/off-shell"
write (u, *)
write (u, '(A)') "\noindent" // &
& "\textbf{Black square:} Keystone, indicates ordering of " // &
& "phase space parameters."
write (u, *)

```

```

write (u, '(A)') "\vspace{-20pt}"
count = 0
pgcount = 0
do grove = 1, cascade_set%n_groves
  first_in_grove = .true.
  cascade => cascade_set%first
  do while (associated (cascade))
    if (cascade%active .and. cascade%complete) then
      if (cascade%grove == grove) then
        if (first_in_grove) then
          first_in_grove = .false.
          write (u, *)
          write (u, '(A)') "\vspace{20pt}"
          write (u, '(A)') "\begin{tabular}{l}"
          write (u, '(A,I5,A)') &
            & "\fbox{\bf Grove \boldmath$", grove, "$} \\[10pt]"
          write (u, '(A,I1,A)') "Multiplicity: ", &
            cascade%multiplicity, "\\"
          write (u, '(A,I1,A)') "Resonances: ", &
            cascade%n_resonances, "\\"
          write (u, '(A,I1,A)') "Log-enhanced: ", &
            cascade%n_log_enhanced, "\\"
          write (u, '(A,I1,A)') "Off-shell: ", &
            cascade%n_off_shell, "\\"
          write (u, '(A,I1,A)') "t-channel: ", &
            cascade%n_t_channel, ""
          write (u, '(A)') "\end{tabular}"
        end if
        count = count + 1
        call cascade_write_graph_format (cascade, count, unit)
        if (pgcount >= 250) then
          write (u, '(A)') "\clearpage"
          pgcount = 0
        end if
      end if
    end if
    cascade => cascade%next
  end do
end do
write (u, '(A)') "\end{flushleft}"
write (u, '(A)') "\end{fmfshrink}"
write (u, '(A)') "\end{fmffile}"
write (u, '(A)') "\end{document}"
end subroutine cascade_set_write_graph_format

```

This is for screen output and debugging:

```

<Cascades: public>+≡
  public :: cascade_set_write

<Cascades: procedures>+≡
  subroutine cascade_set_write (cascade_set, unit, active_only, complete_only)
    type(cascade_set_t), intent(in), target :: cascade_set
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: active_only, complete_only

```

```

logical :: active, complete
type(cascade_t), pointer :: cascade
integer :: u, i
u = output_unit (unit); if (u < 0) return
active = .true.; if (present (active_only)) active = active_only
complete = .false.; if (present (complete_only)) complete = complete_only
write (u, *) "Cascade set:"
write (u, "(3x,A)", advance="no") "Model:"
if (associated (cascade_set%model)) then
    write (u, "(1x,A)") char (model_get_name (cascade_set%model))
else
    write (u, "(1x,A)") "[none]"
end if
write (u, "(3x,A)", advance="no") "n_in/out/tot ="
write (u, *) cascade_set%n_in, cascade_set%n_out, cascade_set%n_tot
write (u, "(3x,A)", advance="no") "depth_out/tot ="
write (u, *) cascade_set%depth_out, cascade_set%depth_tot
write (u, "(3x,A)", advance="no") "mass thr(s/t) ="
write (u, *) cascade_set%m_threshold_s, cascade_set%m_threshold_t
write (u, "(3x,A)", advance="no") "off shell ="
write (u, *) cascade_set%off_shell
write (u, "(3x,A)", advance="no") "keep_nonreson ="
write (u, *) cascade_set%keep_nonresonant
write (u, "(3x,A)", advance="no") "n_groves ="
write (u, *) cascade_set%n_groves
write (u, *)
write (u, *) "Cascade list:"
if (associated (cascade_set%first)) then
    cascade => cascade_set%first
    do while (associated (cascade))
        if (active .and. .not. cascade%active) cycle
        if (complete .and. .not. cascade%complete) cycle
        call cascade_write (cascade, unit)
        cascade => cascade%next
    end do
else
    write (u, *) "[empty]"
end if
write (u, *) "Hash array"
write (u, "(3x,A)", advance="no") "n_entries ="
write (u, *) cascade_set%n_entries
write (u, "(3x,A)", advance="no") "fill_ratio ="
write (u, *) cascade_set%fill_ratio
write (u, "(3x,A)", advance="no") "n_entries_max ="
write (u, *) cascade_set%n_entries_max
write (u, "(3x,A)", advance="no") "mask ="
write (u, *) cascade_set%mask
do i = 0, ubound (cascade_set%entry, 1)
    if (allocated (cascade_set%entry(i)%key)) then
        write (u, *) i
        call hash_entry_write (cascade_set%entry(i), u)
    end if
end do
end subroutine cascade_set_write

```


12.4.7 Adding cascades

Add a deep copy of a cascade to the set. The copy has all content of the original, but the pointers are nullified. We do not care whether insertion was successful or not. The pointer argument, if present, is assigned to the input cascade, or to the hash entry if it is already present.

The procedure is recursive: any daughter or mother entries are also deep-copied and added to the cascade set before the current copy is added.

(Cascades: procedures)+≡

```
recursive subroutine cascade_set_add_copy &
  (cascade_set, cascade_in, cascade_ptr)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(cascade_t), intent(in) :: cascade_in
  type(cascade_t), optional, pointer :: cascade_ptr
  type(cascade_t), pointer :: cascade
  logical :: ok
  allocate (cascade)
  cascade = cascade_in
  if (associated (cascade_in%daughter1)) call cascade_set_add_copy &
    (cascade_set, cascade_in%daughter1, cascade%daughter1)
  if (associated (cascade_in%daughter2)) call cascade_set_add_copy &
    (cascade_set, cascade_in%daughter2, cascade%daughter2)
  if (associated (cascade_in%mother)) call cascade_set_add_copy &
    (cascade_set, cascade_in%mother, cascade%mother)
  cascade%next => null ()
  call cascade_set_add (cascade_set, cascade, ok, cascade_ptr)
end subroutine cascade_set_add_copy
```

Add a cascade to the set. This does not deep-copy. We first try to insert it in the hash array. If successful, add it to the list. Failure indicates that it is already present, and we drop it.

The hash key is built solely from the tree array, so neither particle codes nor resonances count, just topology.

Technically, hash and list receive only pointers, so the cascade can be considered as being in either of both. We treat it as part of the list.

(Cascades: procedures)+≡

```
subroutine cascade_set_add (cascade_set, cascade, ok, cascade_ptr)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(cascade_t), intent(in), target :: cascade
  logical, intent(out) :: ok
  type(cascade_t), optional, pointer :: cascade_ptr
  integer(i8), dimension(1) :: mold
  call cascade_set_hash_insert &
    (cascade_set, transfer (cascade%tree, mold), cascade, ok, cascade_ptr)
  if (ok) call cascade_set_list_add (cascade_set, cascade)
end subroutine cascade_set_add
```

Add a new cascade to the list:

(Cascades: procedures)+≡

```

subroutine cascade_set_list_add (cascade_set, cascade)
  type(cascade_set_t), intent(inout) :: cascade_set
  type(cascade_t), intent(in), target :: cascade
  if (associated (cascade_set%last)) then
    cascade_set%last%next => cascade
  else
    cascade_set%first => cascade
  end if
  cascade_set%last => cascade
end subroutine cascade_set_list_add

```

Add a cascade entry to the hash array:

```

(Cascades: procedures)+≡
subroutine cascade_set_hash_insert &
  (cascade_set, key, cascade, ok, cascade_ptr)
  type(cascade_set_t), intent(inout), target :: cascade_set
  integer(i8), dimension(:), intent(in) :: key
  type(cascade_t), intent(in), target :: cascade
  logical, intent(out) :: ok
  type(cascade_t), optional, pointer :: cascade_ptr
  integer(i32) :: h
  if (cascade_set%n_entries >= cascade_set%n_entries_max) &
    call cascade_set_hash_expand (cascade_set)
  h = hash (key)
  call cascade_set_hash_insert_rec &
    (cascade_set, h, h, key, cascade, ok, cascade_ptr)
end subroutine cascade_set_hash_insert

```

Double the hashtable size when necessary:

```

(Cascades: procedures)+≡
subroutine cascade_set_hash_expand (cascade_set)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(hash_entry_t), dimension(:), allocatable, target :: table_tmp
  type(cascade_p), pointer :: current
  integer :: i, s
  allocate (table_tmp (0:cascade_set%mask))
  table_tmp = cascade_set%entry
  deallocate (cascade_set%entry)
  s = 2 * size (table_tmp)
  cascade_set%n_entries = 0
  cascade_set%n_entries_max = s * cascade_set%fill_ratio
  cascade_set%mask = s - 1
  allocate (cascade_set%entry (0:cascade_set%mask))
  do i = 0, ubound (table_tmp, 1)
    current => table_tmp(i)%first
    do while (associated (current))
      call cascade_set_hash_insert_rec &
        (cascade_set, table_tmp(i)%hashval, table_tmp(i)%hashval, &
          table_tmp(i)%key, current%cascade)
      current => current%next
    end do
  end do
end subroutine cascade_set_hash_expand

```

Insert the cascade at the bucket determined by the hash value. If the bucket is filled, check first for a collision (unequal keys). In that case, choose the following bucket and repeat. Otherwise, add the cascade to the bucket.

If the bucket is empty, record the hash value, allocate and store the key, and then add the cascade to the bucket.

If ok is present, before insertion we check whether the cascade is already stored, and return failure if yes.

```

<Cascades: procedures>+≡
recursive subroutine cascade_set_hash_insert_rec &
  (cascade_set, h, hashval, key, cascade, ok, cascade_ptr)
  type(cascade_set_t), intent(inout) :: cascade_set
  integer(i32), intent(in) :: h, hashval
  integer(i8), dimension(:), intent(in) :: key
  type(cascade_t), intent(in), target :: cascade
  logical, intent(out), optional :: ok
  type(cascade_t), optional, pointer :: cascade_ptr
  integer(i32) :: i
  i = iand (h, cascade_set%mask)
  if (allocated (cascade_set%entry(i)%key)) then
    if (size (cascade_set%entry(i)%key) /= size (key)) then
      call cascade_set_hash_insert_rec &
        (cascade_set, h + 1, hashval, key, cascade, ok, cascade_ptr)
    else if (any (cascade_set%entry(i)%key /= key)) then
      call cascade_set_hash_insert_rec &
        (cascade_set, h + 1, hashval, key, cascade, ok, cascade_ptr)
    else
      call hash_entry_add_cascade_ptr &
        (cascade_set%entry(i), cascade, ok, cascade_ptr)
    end if
  else
    cascade_set%entry(i)%hashval = hashval
    allocate (cascade_set%entry(i)%key (size (key)))
    cascade_set%entry(i)%key = key
    call hash_entry_add_cascade_ptr &
      (cascade_set%entry(i), cascade, ok, cascade_ptr)
    cascade_set%n_entries = cascade_set%n_entries + 1
  end if
end subroutine cascade_set_hash_insert_rec

```

12.4.8 External particles

We want to initialize the cascade set with the outgoing particles. In case of multiple processes, initial cascades are prepared for all of them. The hash array check ensures that no particle appears more than once at the same place.

```

<Cascades: interfaces>+≡
interface cascade_set_add_outgoing
  module procedure cascade_set_add_outgoing1
  module procedure cascade_set_add_outgoing2
end interface

```

```

<Cascades: procedures>+=
subroutine cascade_set_add_outgoing2 (cascade_set, flv)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(flavor_t), dimension(:,:), intent(in) :: flv
  integer :: pos, prc, n_out, n_prc
  type(cascade_t), pointer :: cascade
  logical :: ok
  n_out = size (flv, dim=1)
  n_prc = size (flv, dim=2)
  do prc = 1, n_prc
    do pos = 1, n_out
      allocate (cascade)
      call cascade_init_outgoing &
        (cascade, flv(pos,prc), pos, cascade_set%m_threshold_s)
      call cascade_set_add (cascade_set, cascade, ok)
      if (.not. ok) then
        deallocate (cascade)
      end if
    end do
  end do
end subroutine cascade_set_add_outgoing2

subroutine cascade_set_add_outgoing1 (cascade_set, flv)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(flavor_t), dimension(:), intent(in) :: flv
  integer :: pos, n_out
  type(cascade_t), pointer :: cascade
  logical :: ok
  n_out = size (flv, dim=1)
  do pos = 1, n_out
    allocate (cascade)
    call cascade_init_outgoing &
      (cascade, flv(pos), pos, cascade_set%m_threshold_s)
    call cascade_set_add (cascade_set, cascade, ok)
    if (.not. ok) then
      deallocate (cascade)
    end if
  end do
end subroutine cascade_set_add_outgoing1

```

The incoming particles are added one at a time. Nevertheless, we may have several processes which are looped over. At the first opportunity, we set the pointer `first_t` in the cascade set which should point to the first t-channel cascade.

Return the indices of the first and last cascade generated.

```

<Cascades: interfaces>+=
interface cascade_set_add_incoming
  module procedure cascade_set_add_incoming0
  module procedure cascade_set_add_incoming1
end interface

<Cascades: procedures>+=
subroutine cascade_set_add_incoming1 (cascade_set, n1, n2, pos, flv)

```

```

type(cascade_set_t), intent(inout), target :: cascade_set
integer, intent(out) :: n1, n2
integer, intent(in) :: pos
type(flavor_t), dimension(:), intent(in) :: flv
integer :: prc, n_prc
type(cascade_t), pointer :: cascade
logical :: ok
n1 = 0
n2 = 0
n_prc = size (flv)
do prc = 1, n_prc
    allocate (cascade)
    call cascade_init_incoming &
        (cascade, flv(prc), pos, cascade_set%m_threshold_t)
    call cascade_set_add (cascade_set, cascade, ok)
    if (ok) then
        if (n1 == 0) n1 = cascade%index
        n2 = cascade%index
        if (.not. associated (cascade_set%first_t)) then
            cascade_set%first_t => cascade
        end if
    else
        deallocate (cascade)
    end if
end do
end subroutine cascade_set_add_incoming1

subroutine cascade_set_add_incoming0 (cascade_set, n1, n2, pos, flv)
type(cascade_set_t), intent(inout), target :: cascade_set
integer, intent(out) :: n1, n2
integer, intent(in) :: pos
type(flavor_t), intent(in) :: flv
type(cascade_t), pointer :: cascade
logical :: ok
n1 = 0
n2 = 0
allocate (cascade)
call cascade_init_incoming &
    (cascade, flv, pos, cascade_set%m_threshold_t)
call cascade_set_add (cascade_set, cascade, ok)
if (ok) then
    if (n1 == 0) n1 = cascade%index
    n2 = cascade%index
    if (.not. associated (cascade_set%first_t)) then
        cascade_set%first_t => cascade
    end if
else
    deallocate (cascade)
end if
end subroutine cascade_set_add_incoming0

```

12.4.9 Cascade combination I: flavor assignment

We have two disjunct cascades, now use the vertex table to determine the possible flavors of the combination cascade. For each possibility, try to generate a new cascade. The total cascade depth has to be one less than the limit, because this is reached by setting the keystone.

```
(Cascades: procedures) +=  
  subroutine cascade_match_pair (cascade_set, cascade1, cascade2, s_channel)  
    type(cascade_set_t), intent(inout), target :: cascade_set  
    type(cascade_t), intent(in), target :: cascade1, cascade2  
    logical, intent(in) :: s_channel  
    integer, dimension(:), allocatable :: pdg3  
    integer :: i, depth_max  
    type(flavor_t) :: flv  
    if (s_channel) then  
      depth_max = cascade_set%depth_out  
    else  
      depth_max = cascade_set%depth_tot  
    end if  
    if (cascade1%depth + cascade2%depth < depth_max) then  
      call model_match_vertex (cascade_set%model, &  
        flavor_get_pdg (cascade1%flv), &  
        flavor_get_pdg (cascade2%flv), &  
        pdg3)  
      do i = 1, size (pdg3)  
        call flavor_init (flv, pdg3(i), cascade_set%model)  
        if (s_channel) then  
          call cascade_combine_s (cascade_set, cascade1, cascade2, flv)  
        else  
          call cascade_combine_t (cascade_set, cascade1, cascade2, flv)  
        end if  
      end do  
      deallocate (pdg3)  
    end if  
  end subroutine cascade_match_pair
```

The triplet version takes a third cascade, and we check whether this triplet has a matching vertex in the database. If yes, we make a keystone cascade.

```
(Cascades: procedures) +=  
  subroutine cascade_match_triplet &  
    (cascade_set, cascade1, cascade2, cascade3, s_channel)  
    type(cascade_set_t), intent(inout), target :: cascade_set  
    type(cascade_t), intent(in), target :: cascade1, cascade2, cascade3  
    logical, intent(in) :: s_channel  
    integer :: depth_max  
    depth_max = cascade_set%depth_tot  
    if (cascade1%depth + cascade2%depth + cascade3%depth == depth_max) then  
      if (model_check_vertex (cascade_set%model, &  
        flavor_get_pdg (cascade1%flv), &  
        flavor_get_pdg (cascade2%flv), &  
        flavor_get_pdg (cascade3%flv))) then  
        call cascade_combine_keystone &  
          (cascade_set, cascade1, cascade2, cascade3, s_channel)      end if  
    end if  
  end subroutine cascade_match_triplet
```

```

        end if
    end if
end subroutine cascade_match_triplet

```

12.4.10 Cascade combination II: kinematics setup and check

Having three matching flavors, we start constructing the combination cascade. We look at the mass hierarchies and determine whether the cascade is to be kept. In passing we set mapping modes, resonance properties and such.

If successful, the cascade is finalized. For a resonant cascade, we prepare in addition a copy without the resonance.

```

(Cascades: procedures) +=
subroutine cascade_combine_s (cascade_set, cascade1, cascade2, flv)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2
    type(flavor_t), intent(in) :: flv
    type(cascade_t), pointer :: cascade3, cascade4
    logical :: keep
    keep = .false.
    allocate (cascade3)
    call cascade_init (cascade3, cascade1%depth + cascade2%depth + 1)
    cascade3%bincode = ior (cascade1%bincode, cascade2%bincode)
    cascade3%flv = flavor_anti (flv)
    cascade3%pdg = abs (flavor_get_pdg (cascade3%flv))
    cascade3%is_vector = flavor_get_spin_type (flv) == VECTOR
    cascade3%m_min = cascade1%m_min + cascade2%m_min
    cascade3%m_rea = flavor_get_mass (flv)
    if (cascade3%m_rea > cascade_set%m_threshold_s) then
        cascade3%m_eff = cascade3%m_rea
    end if
    ! Potentially resonant cases [sqrts = m_rea for on-shell decay]
    if (cascade3%m_rea > cascade3%m_min &
        .and. cascade3%m_rea <= cascade_set%sqrts) then
        if (flavor_get_width (flv) /= 0) then
            if (cascade1%on_shell .or. cascade2%on_shell) then
                keep = .true.
                cascade3%mapping = S_CHANNEL
                cascade3%resonant = .true.
            end if
        else
            call warn_decay (flv)
        end if
    ! Collinear and IR singular cases
    else if (cascade3%m_rea < cascade_set%sqrts) then
        ! Massless splitting
        if (cascade1%m_eff == 0 .and. cascade2%m_eff == 0 &
            .and. cascade3%depth <= 3) then
            keep = .true.
            cascade3%log_enhanced = .true.
            if (cascade3%is_vector) then
                if (cascade1%is_vector .and. cascade2%is_vector) then
                    cascade3%mapping = COLLINEAR ! three-vector-vertex

```

```

        else
            cascade3%mapping = INFRARED      ! vector splitting into matter
        end if
    else
        if (cascade1%is_vector .or. cascade2%is_vector) then
            cascade3%mapping = COLLINEAR    ! vector radiation off matter
        else
            cascade3%mapping = INFRARED      ! scalar radiation/splitting
        end if
    end if
    ! IR radiation off massive particle
else if (cascade3%m_eff > 0 .and. cascade1%m_eff > 0 &
        .and. cascade2%m_eff == 0 &
        .and. (cascade1%on_shell .or. cascade1%mapping == RADIATION) &
        .and. abs (cascade3%m_eff - cascade1%m_eff) &
            < cascade_set%m_threshold_s) &
    then
        keep = .true.
        cascade3%log_enhanced = .true.
        cascade3%mapping = RADIATION
    else if (cascade3%m_eff > 0 .and. cascade2%m_eff > 0 &
        .and. cascade1%m_eff == 0 &
        .and. (cascade2%on_shell .or. cascade2%mapping == RADIATION) &
        .and. abs (cascade3%m_eff - cascade2%m_eff) &
            < cascade_set%m_threshold_s) &
    then
        keep = .true.
        cascade3%log_enhanced = .true.
        cascade3%mapping = RADIATION
    end if
end if
! Non-singular cases, including failed resonances
if (.not. keep) then
    ! Two on-shell particles from a virtual mother
    if (cascade1%on_shell .or. cascade2%on_shell) then
        keep = .true.
        cascade3%m_eff = max (cascade3%m_min, &
                               cascade1%m_eff + cascade2%m_eff)
        if (cascade3%m_eff < cascade_set%m_threshold_s) then
            cascade3%m_eff = 0
        end if
    end if
end if
! Complete and register the cascade (two in case of resonance)
if (keep) then
    cascade3%on_shell = cascade3%resonant .or. cascade3%log_enhanced
    if (cascade3%resonant) then
        cascade3%pdg = abs (flavor_get_pdg (cascade3%flv))
        if (cascade_set%keep_nonresonant) then
            allocate (cascade4)
            cascade4 = cascade3
            cascade4%index = cascade_index ()
            cascade4%pdg = UNDEFINED
            cascade4%mapping = NO_MAPPING
        end if
    end if
end if

```



```

        cascade4%resonant = .false.
        cascade4%on_shell = .false.
    end if
    cascade3%m_min = cascade3%m_rea
    call cascade_fusion (cascade_set, cascade1, cascade2, cascade3)
    if (cascade_set%keep_nonresonant) then
        call cascade_fusion (cascade_set, cascade1, cascade2, cascade4)
    end if
else
    call cascade_fusion (cascade_set, cascade1, cascade2, cascade3)
end if
else
    deallocate (cascade3)
end if
contains
subroutine warn_decay (flv)
    type(flavor_t), intent(in) :: flv
    integer :: i
    integer, dimension(MAX_WARN_RESONANCE), save :: warned_code = 0
    LOOP_WARNED: do i = 1, MAX_WARN_RESONANCE
        if (warned_code(i) == 0) then
            warned_code(i) = flavor_get_pdg (flv)
            write (msg_buffer, "(A)" &
                & " Intermediate decay of zero-width particle " &
                & // char (flavor_get_name (flv)) &
                & // " may be possible."
            )
            call msg_warning
            exit LOOP_WARNED
        else if (warned_code(i) == flavor_get_pdg (flv)) then
            exit LOOP_WARNED
        end if
    end do LOOP_WARNED
end subroutine warn_decay
end subroutine cascade_combine_s

```

(Limits: public parameters)+≡

```
integer, parameter, public :: MAX_WARN_RESONANCE = 50
```

This is the t-channel version. cascade1 is t-channel and contains the seed, cascade2 is s-channel. We check for kinematically allowed beam decay (which is a fatal error), or massless splitting / soft radiation. The cascade is kept in all remaining cases and submitted for registration.

(Cascades: procedures)+≡

```

subroutine cascade_combine_t (cascade_set, cascade1, cascade2, flv)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2
    type(flavor_t), intent(in) :: flv
    type(cascade_t), pointer :: cascade3
    allocate (cascade3)
    call cascade_init (cascade3, cascade1%depth + cascade2%depth + 1)
    cascade3%bincode = ior (cascade1%bincode, cascade2%bincode)
    cascade3%flv = flavor_anti (flv)
    cascade3%pdg = abs (flavor_get_pdg (cascade3%flv))
    cascade3%is_vector = flavor_get_spin_type (flv) == VECTOR

```

```

if (cascade1%incoming) then
  cascade3%m_min = cascade2%m_min
else
  cascade3%m_min = cascade1%m_min + cascade2%m_min
end if
cascade3%m_rea = flavor_get_mass (flv)
if (cascade3%m_rea > cascade_set%m_threshold_t) then
  cascade3%m_eff = max (cascade3%m_rea, cascade2%m_eff)
else if (cascade2%m_eff > cascade_set%m_threshold_t) then
  cascade3%m_eff = cascade2%m_eff
else
  cascade3%m_eff = 0
end if
! Allowed decay of beam particle
if (cascade1%incoming &
    .and. cascade1%m_rea > cascade2%m_rea + cascade3%m_rea) then
  call beam_decay (cascade_set%fatal_beam_decay)
! Massless splitting
else if (cascade1%m_eff == 0 &
    .and. cascade2%m_eff < cascade_set%m_threshold_t &
    .and. cascade3%m_eff == 0) then
  cascade3%mapping = U_CHANNEL
  cascade3%log_enhanced = .true.
! IR radiation off massive particle
else if (cascade1%m_eff /= 0 .and. cascade2%m_eff == 0 &
    .and. cascade3%m_eff /= 0 &
    .and. (cascade1%on_shell .or. cascade1%mapping == RADIATION) &
    .and. abs (cascade1%m_eff - cascade3%m_eff) &
    < cascade_set%m_threshold_t) &
  then
    cascade3%pdg = abs (flavor_get_pdg (flv))
    cascade3%log_enhanced = .true.
    cascade3%mapping = RADIATION
  end if
cascade3%t_channel = .true.
call cascade_fusion (cascade_set, cascade1, cascade2, cascade3)
contains
subroutine beam_decay (fatal_beam_decay)
  logical, intent(in) :: fatal_beam_decay
  write (msg_buffer, "(1x,A,1x,'->',1x,A,1x,A)") &
    char (flavor_get_name (cascade1%flv)), &
    char (flavor_get_name (cascade3%flv)), &
    char (flavor_get_name (cascade2%flv))
  call msg_message
  write (msg_buffer, "(1x,'mass(' ,A,') =' ,1x,E17.10)") &
    char (flavor_get_name (cascade1%flv)), cascade1%m_rea
  call msg_message
  write (msg_buffer, "(1x,'mass(' ,A,') =' ,1x,E17.10)") &
    char (flavor_get_name (cascade3%flv)), cascade3%m_rea
  call msg_message
  write (msg_buffer, "(1x,'mass(' ,A,') =' ,1x,E17.10)") &
    char (flavor_get_name (cascade2%flv)), cascade2%m_rea
  call msg_message
  if (fatal_beam_decay) then

```

```

        call msg_fatal (" Phase space: Initial beam particle can decay")
    else
        call msg_warning (" Phase space: Initial beam particle can decay")
    end if
    end subroutine beam_decay
end subroutine cascade_combine_t

```

Here we complete a decay cascade. The third input is the single-particle cascade for the initial particle. There is no resonance or mapping assignment. The only condition for keeping the cascade is the mass sum of the final state, which must be less than the available energy.

Two modifications are necessary for scattering cascades: a pure s-channel diagram (cascade1 is the incoming particle) do not have a logarithmic mapping at top-level. And in a t-channel diagram, the last line exchanged is mapped t-channel, not u-channel. In both cases we register a new cascade with the modified mapping.

(*Cascades: procedures*) +=

```

subroutine cascade_combine_keystone &
    (cascade_set, cascade1, cascade2, cascade3, s_channel)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2, cascade3
    logical, intent(in) :: s_channel
    type(cascade_t), pointer :: cascade4, cascade0
    logical :: keep, ok
    keep = .false.
    allocate (cascade4)
    call cascade_init &
        (cascade4, cascade1%depth + cascade2%depth + cascade3%depth)
    cascade4%complete = .true.
!   cascade4%bincode = ior (ior (cascade1%bincode, cascade2%bincode), &
!       cascade3%bincode)
    if (s_channel) then
        cascade4%bincode = ior (cascade1%bincode, cascade2%bincode)
    else
        cascade4%bincode = cascade3%bincode
    end if
    cascade4%flv = cascade3%flv
    cascade4%pdg = cascade3%pdg
    cascade4%mapping = EXTERNAL_PRT
    cascade4%is_vector = cascade3%is_vector
    cascade4%m_min = cascade1%m_min + cascade2%m_min
    cascade4%m_rea = cascade3%m_rea
    cascade4%m_eff = cascade3%m_rea
    if (cascade4%m_min < cascade_set%sqrts) then
        keep = .true.
    end if
    if (keep) then
        if (cascade1%incoming .and. cascade2%log_enhanced) then
            allocate (cascade0)
            cascade0 = cascade2
            cascade0%next => null ()
            cascade0%index = cascade_index ()
            cascade0%mapping = NO_MAPPING

```

```

        cascade0%log_enhanced = .false.
        cascade0%n_log_enhanced = cascade0%n_log_enhanced - 1
        cascade0%tree_mapping(cascade0%depth) = NO_MAPPING
        call cascade_keystone &
            (cascade_set, cascade1, cascade0, cascade3, cascade4, ok)
        if (ok) call cascade_set_add (cascade_set, cascade0, ok)
    else if (cascade1%t_channel .and. cascade1%mapping == U_CHANNEL) then
        allocate (cascade0)
        cascade0 = cascade1
        cascade0%next => null ()
        cascade0%index = cascade_index ()
        cascade0%mapping = T_CHANNEL
        cascade0%tree_mapping(cascade0%depth) = T_CHANNEL
        call cascade_keystone &
            (cascade_set, cascade0, cascade2, cascade3, cascade4, ok)
        if (ok) call cascade_set_add (cascade_set, cascade0, ok)
    else
        call cascade_keystone &
            (cascade_set, cascade1, cascade2, cascade3, cascade4, ok)
    end if
else
    deallocate (cascade4)
end if
end subroutine cascade_combine_keystone

```

12.4.11 Cascade combination III: node connections and tree fusion

Here we assign global tree properties. If the allowed number of off-shell lines is exceeded, discard the new cascade. Otherwise, assign the trees, sort them, and assign connections. Finally, append the cascade to the list. This may fail (because in the hash array there is already an equivalent cascade). On failure, discard the cascade.

```

<Cascades: procedures>+≡
subroutine cascade_fusion (cascade_set, cascade1, cascade2, cascade3)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), intent(in), target :: cascade1, cascade2
    type(cascade_t), pointer :: cascade3
    integer :: i1, i2, i3, i4
    logical :: ok
    cascade3%internal = (cascade3%depth - 3) / 2
    if (cascade3%resonant) then
        cascade3%multiplicity = 1
        cascade3%n_resonances = &
            cascade1%n_resonances + cascade2%n_resonances + 1
    else
        cascade3%multiplicity = cascade1%multiplicity + cascade2%multiplicity
        cascade3%n_resonances = cascade1%n_resonances + cascade2%n_resonances
    end if
    if (cascade3%log_enhanced) then
        cascade3%n_log_enhanced = &
            cascade1%n_log_enhanced + cascade2%n_log_enhanced + 1
    end if
end subroutine cascade_fusion

```

```

else
    cascade3%n_log_enhanced = &
        cascade1%n_log_enhanced + cascade2%n_log_enhanced
end if
if (cascade3%resonant) then
    cascade3%n_off_shell = 0
else if (cascade3%log_enhanced) then
    cascade3%n_off_shell = cascade1%n_off_shell + cascade2%n_off_shell
else
    cascade3%n_off_shell = cascade1%n_off_shell + cascade2%n_off_shell + 1
end if
if (cascade3%t_channel) then
    cascade3%n_t_channel = cascade1%n_t_channel + 1
end if
if (cascade3%n_off_shell > cascade_set%off_shell) then
    deallocate (cascade3)
else if (cascade3%n_t_channel > cascade_set%t_channel) then
    deallocate (cascade3)
else
    i1 = cascade1%depth
    i2 = i1 + 1
    i3 = i1 + cascade2%depth
    i4 = cascade3%depth
    cascade3%tree(:i1) = cascade1%tree
    where (cascade1%tree_mapping > NO_MAPPING)
        cascade3%tree_pdg(:i1) = cascade1%tree_pdg
    elsewhere
        cascade3%tree_pdg(:i1) = UNDEFINED
    end where
    cascade3%tree_mapping(:i1) = cascade1%tree_mapping
    cascade3%tree_resonant(:i1) = cascade1%tree_resonant
    cascade3%tree(i2:i3) = cascade2%tree
    where (cascade2%tree_mapping > NO_MAPPING)
        cascade3%tree_pdg(i2:i3) = cascade2%tree_pdg
    elsewhere
        cascade3%tree_pdg(i2:i3) = UNDEFINED
    end where
    cascade3%tree_mapping(i2:i3) = cascade2%tree_mapping
    cascade3%tree_resonant(i2:i3) = cascade2%tree_resonant
    cascade3%tree(i4) = cascade3%bincode
    cascade3%tree_pdg(i4) = cascade3%pdg
    cascade3%tree_mapping(i4) = cascade3%mapping
    cascade3%tree_resonant(i4) = cascade3%resonant
    call tree_sort (cascade3%tree, &
        cascade3%tree_pdg, cascade3%tree_mapping, cascade3%tree_resonant)
    cascade3%has_children = .true.
    cascade3%daughter1 => cascade1
    cascade3%daughter2 => cascade2
    call cascade_set_add (cascade_set, cascade3, ok)
    if (.not. ok) deallocate (cascade3)
end if
end subroutine cascade_fusion

```

Here we combine a cascade pair with an incoming particle, i.e., we set a keystone.

Otherwise, this is similar. On the first opportunity, we set the `first_k` pointer in the cascade set.

(*Cascades: procedures*) +=

```

subroutine cascade_keystone &
  (cascade_set, cascade1, cascade2, cascade3, cascade4, ok)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(cascade_t), intent(in), target :: cascade1, cascade2, cascade3
  type(cascade_t), pointer :: cascade4
  logical, intent(out) :: ok
  integer :: i1, i2, i3, i4
  cascade4%internal = (cascade4%depth - 3) / 2
  cascade4%multiplicity = cascade1%multiplicity + cascade2%multiplicity
  cascade4%n_resonances = cascade1%n_resonances + cascade2%n_resonances
  cascade4%n_off_shell = cascade1%n_off_shell + cascade2%n_off_shell
  cascade4%n_log_enhanced = &
    cascade1%n_log_enhanced + cascade2%n_log_enhanced
  cascade4%n_t_channel = cascade1%n_t_channel + cascade2%n_t_channel
  if (cascade4%n_off_shell > cascade_set%off_shell) then
    deallocate (cascade4)
    ok = .false.
  else if (cascade4%n_t_channel > cascade_set%t_channel) then
    deallocate (cascade4)
    ok = .false.
  else
    i1 = cascade1%depth
    i2 = i1 + 1
    i3 = i1 + cascade2%depth
    i4 = cascade4%depth
    cascade4%tree(:i1) = cascade1%tree
    where (cascade1%tree_mapping > NO_MAPPING)
      cascade4%tree_pdg(:i1) = cascade1%tree_pdg
    elsewhere
      cascade4%tree_pdg(:i1) = UNDEFINED
    end where
    cascade4%tree_mapping(:i1) = cascade1%tree_mapping
    cascade4%tree_resonant(:i1) = cascade1%tree_resonant
    cascade4%tree(i2:i3) = cascade2%tree
    where (cascade2%tree_mapping > NO_MAPPING)
      cascade4%tree_pdg(i2:i3) = cascade2%tree_pdg
    elsewhere
      cascade4%tree_pdg(i2:i3) = UNDEFINED
    end where
    cascade4%tree_mapping(i2:i3) = cascade2%tree_mapping
    cascade4%tree_resonant(i2:i3) = cascade2%tree_resonant
!   cascade4%tree(i4) = cascade3%bincode
    cascade4%tree(i4) = cascade4%bincode
    cascade4%tree_pdg(i4) = UNDEFINED
    cascade4%tree_mapping(i4) = cascade4%mapping
    cascade4%tree_resonant(i4) = .false.
    call tree_sort (cascade4%tree, &
      cascade4%tree_pdg, cascade4%tree_mapping, cascade4%tree_resonant)
    cascade4%has_children = .true.
    cascade4%daughter1 => cascade1
    cascade4%daughter2 => cascade2

```

```

        cascade4%mother => cascade3
        call cascade_set_add (cascade_set, cascade4, ok)
        if (ok) then
            if (.not. associated (cascade_set%first_k)) then
                cascade_set%first_k => cascade4
            end if
        else
            deallocate (cascade4)
        end if
    end if
end if
end subroutine cascade_keystone

```

Sort a tree (array of binary codes) and particle code array simultaneously, by ascending binary codes. A convenient method is to use the `maxloc` function iteratively, to find and remove the largest entry in the tree array one by one.

(Cascades: procedures)+≡

```

subroutine tree_sort (tree, pdg, mapping, resonant)
    integer(TC), dimension(:), intent(inout) :: tree
    integer, dimension(:), intent(inout) :: pdg, mapping
    logical, dimension(:), intent(inout) :: resonant
    integer(TC), dimension(size(tree)) :: tree_tmp
    integer, dimension(size(pdg)) :: pdg_tmp, mapping_tmp
    logical, dimension(size(resonant)) :: resonant_tmp
    integer, dimension(1) :: pos
    integer :: i
    tree_tmp = tree
    pdg_tmp = pdg
    mapping_tmp = mapping
    resonant_tmp = resonant
    do i = size(tree), 1, -1
        pos = maxloc (tree_tmp)
        tree(i) = tree_tmp (pos(1))
        pdg(i) = pdg_tmp (pos(1))
        mapping(i) = mapping_tmp (pos(1))
        resonant(i) = resonant_tmp (pos(1))
        tree_tmp(pos(1)) = 0
    end do
end subroutine tree_sort

```

12.4.12 Cascade set generation

These procedures loop over cascades and build up the cascade set. After each iteration of the innermost loop, we set a breakpoint.

s-channel: We use a nested scan to combine all cascades with all other cascades.

(Cascades: procedures)+≡

```

subroutine cascade_set_generate_s (cascade_set)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), pointer :: cascade1, cascade2
    cascade1 => cascade_set%first
    LOOP1: do while (associated (cascade1))

```

```

cascade2 => cascade_set%first
LOOP2: do while (associated (cascade2))
  if (cascade2%index >= cascade1%index) exit LOOP2
  if (cascade1 .disjunct. cascade2) then
    call cascade_match_pair (cascade_set, cascade1, cascade2, .true.)
  end if
  call terminate_now_if_signal ()
  cascade2 => cascade2%next
end do LOOP2
cascade1 => cascade1%next
end do LOOP1
end subroutine cascade_set_generate_s

```

The t-channel cascades are directed and have a seed (one of the incoming particles) and a target (the other one). We loop over all possible seeds and targets. Inside this, we loop over all t-channel cascades (*cascade1*) and s-channel cascades (*cascade2*) and try to combine them.

(*Cascades: procedures*)+=

```

subroutine cascade_set_generate_t (cascade_set, pos_seed, pos_target)
  type(cascade_set_t), intent(inout), target :: cascade_set
  integer, intent(in) :: pos_seed, pos_target
  type(cascade_t), pointer :: cascade_seed, cascade_target
  type(cascade_t), pointer :: cascade1, cascade2
  integer(TC) :: bc_seed, bc_target
  bc_seed = ibset (0_TC, pos_seed-1)
  bc_target = ibset (0_TC, pos_target-1)
  cascade_seed => cascade_set%first_t
  LOOP_SEED: do while (associated (cascade_seed))
    if (cascade_seed%bincode == bc_seed) then
      cascade_target => cascade_set%first_t
      LOOP_TARGET: do while (associated (cascade_target))
        if (cascade_target%bincode == bc_target) then
          cascade1 => cascade_set%first_t
          LOOP_T: do while (associated (cascade1))
            if ((cascade1 .disjunct. cascade_target) &
              .and. .not. (cascade1 .disjunct. cascade_seed)) then
              cascade2 => cascade_set%first
              LOOP_S: do while (associated (cascade2))
                if ((cascade2 .disjunct. cascade_target) &
                  .and. (cascade2 .disjunct. cascade1)) then
                  call cascade_match_pair &
                    (cascade_set, cascade1, cascade2, .false.)
                end if
                call terminate_now_if_signal ()
                cascade2 => cascade2%next
              end do LOOP_S
            end if
            call terminate_now_if_signal ()
            cascade1 => cascade1%next
          end do LOOP_T
        end if
        call terminate_now_if_signal ()
        cascade_target => cascade_target%next
      end do LOOP_TARGET
    end if
  end do LOOP_SEED
end subroutine cascade_set_generate_t

```



```

        end do LOOP_TARGET
    end if
    call terminate_now_if_signal ()
    cascade_seed => cascade_seed%next
end do LOOP_SEED
end subroutine cascade_set_generate_t

```

This part completes the phase space for decay processes. It is similar to s-channel cascade generation, but combines two cascade with the particular cascade of the incoming particle. This particular cascade is expected to be pointed at by `first_t`.

(Cascades: procedures)+≡

```

subroutine cascade_set_generate_decay (cascade_set)
    type(cascade_set_t), intent(inout), target :: cascade_set
    type(cascade_t), pointer :: cascade1, cascade2
    type(cascade_t), pointer :: cascade_in
    cascade_in => cascade_set%first_t
    cascade1 => cascade_set%first
    do while (associated (cascade1))
        if (cascade1 .disjunct. cascade_in) then
            cascade2 => cascade1%next
            do while (associated (cascade2))
                if ((cascade2 .disjunct. cascade1) &
                    .and. (cascade2 .disjunct. cascade_in)) then
                    call cascade_match_triplet (cascade_set, &
                        cascade1, cascade2, cascade_in, .true.)
                end if
                call terminate_now_if_signal ()
                cascade2 => cascade2%next
            end do
        end if
        call terminate_now_if_signal ()
        cascade1 => cascade1%next
    end do
end subroutine cascade_set_generate_decay

```

This part completes the phase space for scattering processes. We combine a t-channel cascade (containing the seed) with a s-channel cascade and the target.

(Cascades: procedures)+≡

```

subroutine cascade_set_generate_scattering &
    (cascade_set, ns1, ns2, nt1, nt2, pos_seed, pos_target)
    type(cascade_set_t), intent(inout), target :: cascade_set
    integer, intent(in) :: pos_seed, pos_target
    integer, intent(in) :: ns1, ns2, nt1, nt2
    type(cascade_t), pointer :: cascade_seed, cascade_target
    type(cascade_t), pointer :: cascade1, cascade2
    integer(TC) :: bc_seed, bc_target
    bc_seed = ibset (0_TC, pos_seed-1)
    bc_target = ibset (0_TC, pos_target-1)
    cascade_seed => cascade_set%first_t
    LOOP_SEED: do while (associated (cascade_seed))
        if (cascade_seed%index < ns1) then
            cascade_seed => cascade_seed%next
        end if
    end do
end subroutine cascade_set_generate_scattering

```

```

        cycle LOOP_SEED
    else if (cascade_seed%index > ns2) then
        exit LOOP_SEED
    else if (cascade_seed%bincode == bc_seed) then
        cascade_target => cascade_set%first_t
        LOOP_TARGET: do while (associated (cascade_target))
            if (cascade_target%index < nt1) then
                cascade_target => cascade_target%next
                cycle LOOP_TARGET
            else if (cascade_target%index > nt2) then
                exit LOOP_TARGET
            else if (cascade_target%bincode == bc_target) then
                cascade1 => cascade_set%first_t
                LOOP_T: do while (associated (cascade1))
                    if ((cascade1 .disjunct. cascade_target) &
                        .and. .not. (cascade1 .disjunct. cascade_seed)) then
                        cascade2 => cascade_set%first
                        LOOP_S: do while (associated (cascade2))
                            if ((cascade2 .disjunct. cascade_target) &
                                .and. (cascade2 .disjunct. cascade1)) then
                                call cascade_match_triplet (cascade_set, &
                                                            cascade1, cascade2, cascade_target, .false.)
                            end if
                            call terminate_now_if_signal ()
                            cascade2 => cascade2%next
                        end do LOOP_S
                    end if
                    call terminate_now_if_signal ()
                    cascade1 => cascade1%next
                end do LOOP_T
            end if
            call terminate_now_if_signal ()
            cascade_target => cascade_target%next
        end do LOOP_TARGET
    end if
    call terminate_now_if_signal ()
    cascade_seed => cascade_seed%next
end do LOOP_SEED
end subroutine cascade_set_generate_scattering

```

12.4.13 Groves

Before assigning groves, assign hashcodes to the resonance patterns, so they can easily be compared.

(Cascades: procedures)+≡

```

subroutine cascade_set_assign_resonance_hash (cascade_set)
    type(cascade_set_t), intent(inout) :: cascade_set
    type(cascade_t), pointer :: cascade
    cascade => cascade_set%first_k
    do while (associated (cascade))
        call cascade_assign_resonance_hash (cascade)
        cascade => cascade%next
    end do
end subroutine

```

```

end do
end subroutine cascade_set_assign_resonance_hash

```

After all cascades are recorded, we group the complete cascades in groves. A grove consists of cascades with identical multiplicity, number of resonances, log-enhanced, t-channel lines, and resonance flavors.

```

(Cascades: procedures)+≡
subroutine cascade_set_assign_groves (cascade_set)
  type(cascade_set_t), intent(inout), target :: cascade_set
  type(cascade_t), pointer :: cascade1, cascade2
  integer :: multiplicity
  integer :: n_resonances, n_log_enhanced, n_t_channel, n_off_shell
  integer :: res_hash
  integer :: grove
  grove = 0
  cascade1 => cascade_set%first_k
  do while (associated (cascade1))
    if (cascade1%active .and. cascade1%complete &
      .and. cascade1%grove == 0) then
      grove = grove + 1
      cascade1%grove = grove
      multiplicity = cascade1%multiplicity
      n_resonances = cascade1%n_resonances
      n_log_enhanced = cascade1%n_log_enhanced
      n_off_shell = cascade1%n_off_shell
      n_t_channel = cascade1%n_t_channel
      res_hash = cascade1%res_hash
      cascade2 => cascade1%next
      do while (associated (cascade2))
        if (cascade2%grove == 0) then
          if (cascade2%multiplicity == multiplicity &
            .and. cascade2%n_resonances == n_resonances &
            .and. cascade2%n_log_enhanced == n_log_enhanced &
            .and. cascade2%n_off_shell == n_off_shell &
            .and. cascade2%n_t_channel == n_t_channel &
            .and. cascade2%res_hash == res_hash) then
            cascade2%grove = grove
          end if
        end if
        call terminate_now_if_signal ()
        cascade2 => cascade2%next
      end do
    end if
    call terminate_now_if_signal ()
    cascade1 => cascade1%next
  end do
  cascade_set%n_groves = grove
end subroutine cascade_set_assign_groves

```

12.4.14 Generate the phase space file

Generate a complete phase space configuration.

For each flavor assignment: First, all s-channel graphs that can be built up from the outgoing particles. Then we distinguish (1) decay, where we complete the s-channel graphs by connecting to the input line, and (2) scattering, where we now generate t-channel graphs by introducing an incoming particle, and complete this by connecting to the other incoming particle.

After all cascade sets have been generated, merge them into a common set. This eliminates redundancies between flavor assignments.

```

<Cascades: public>+=
  public :: cascade_set_generate

<Cascades: procedures>+=
  subroutine cascade_set_generate &
    (cascade_set, model, n_in, n_out, flv, phs_par, fatal_beam_decay)
    type(cascade_set_t), intent(out) :: cascade_set
    type(model_t), intent(in), target :: model
    integer, intent(in) :: n_in, n_out
    type(flavor_t), dimension(:,:), intent(in) :: flv
    type(phs_parameters_t), intent(in) :: phs_par
    logical, intent(in) :: fatal_beam_decay
    type(cascade_set_t), dimension(:), allocatable :: cset
    type(cascade_t), pointer :: cascade
    integer :: i
    if (phase_space_vanishes (phs_par%sqrts, n_in, flv)) return
    call cascade_set_init (cascade_set, model, n_in, n_out, phs_par, &
      fatal_beam_decay, flv)
    allocate (cset (size (flv, 2)))
    do i = 1, size (cset)
      call cascade_set_generate_single (cset(i), &
        model, n_in, n_out, flv(:,i), phs_par, fatal_beam_decay)
      cascade => cset(i)%first_k
      do while (associated (cascade))
        if (cascade%active .and. cascade%complete) then
          call cascade_set_add_copy (cascade_set, cascade)
        end if
        cascade => cascade%next
      end do
      call cascade_set_final (cset(i))
    end do
    cascade_set%first_k => cascade_set%first
    call cascade_set_assign_resonance_hash (cascade_set)
    call cascade_set_assign_groves (cascade_set)
  end subroutine cascade_set_generate

```

This generates phase space for a single channel, without assigning groves.

```

<Cascades: procedures>+=
  subroutine cascade_set_generate_single (cascade_set, &
    model, n_in, n_out, flv, phs_par, fatal_beam_decay)
    type(cascade_set_t), intent(out) :: cascade_set
    type(model_t), intent(in), target :: model
    integer, intent(in) :: n_in, n_out
    type(flavor_t), dimension(:), intent(in) :: flv
    type(phs_parameters_t), intent(in) :: phs_par
    logical, intent(in) :: fatal_beam_decay

```

```

integer :: n11, n12, n21, n22
call cascade_set_init (cascade_set, model, n_in, n_out, phs_par, &
    fatal_beam_decay)
call cascade_set_add_outgoing (cascade_set, flv(n_in+1:))
call cascade_set_generate_s (cascade_set)
select case (n_in)
case(1)
    call cascade_set_add_incoming &
        (cascade_set, n11, n12, n_out + 1, flv(1))
    call cascade_set_generate_decay (cascade_set)
case(2)
    call cascade_set_add_incoming &
        (cascade_set, n11, n12, n_out + 1, flv(2))
    call cascade_set_add_incoming &
        (cascade_set, n21, n22, n_out + 2, flv(1))
    call cascade_set_generate_t (cascade_set, n_out + 1, n_out + 2)
    call cascade_set_generate_t (cascade_set, n_out + 2, n_out + 1)
    call cascade_set_generate_scattering &
        (cascade_set, n11, n12, n21, n22, n_out + 1, n_out + 2)
    call cascade_set_generate_scattering &
        (cascade_set, n21, n22, n11, n12, n_out + 2, n_out + 1)
end select
end subroutine cascade_set_generate_single

```

Sanity check: Before anything else is done, check if there could possibly be any phase space.

(*Cascades: procedures*) +=

```

function phase_space_vanishes (sqrts, n_in, flv) result (flag)
    logical :: flag
    real(default), intent(in) :: sqrts
    integer, intent(in) :: n_in
    type(flavor_t), dimension(:,:), intent(in) :: flv
    real(default), dimension(:,:), allocatable :: mass
    real(default), dimension(:), allocatable :: mass_in, mass_out
    integer :: n_prt, n_flv
    flag = .false.
    if (sqrts <= 0) then
        call msg_error ("Phase space vanishes (sqrts must be positive)")
        flag = .true.; return
    end if
    n_prt = size (flv, 1)
    n_flv = size (flv, 2)
    allocate (mass (n_prt, n_flv), mass_in (n_flv), mass_out (n_flv))
    mass = flavor_get_mass (flv)
    mass_in = sum (mass(:,n_in,:), 1)
    mass_out = sum (mass(n_in+1:,:), 1)
    if (any (mass_in > sqrts)) then
        call msg_error ("Mass sum of incoming particles " &
            // "is more than available energy")
        flag = .true.; return
    end if
    if (any (mass_out > sqrts)) then
        call msg_error ("Mass sum of outgoing particles " &

```

```

        // "is more than available energy")
        flag = .true.; return
    end if
end function phase_space_vanishes

```

12.4.15 Test

```

(Cascades: public)+≡
    public :: cascade_test

(Cascades: procedures)+≡
    subroutine cascade_test
        use os_interface, only: os_data_t
        type(os_data_t) :: os_data
        type(model_t), pointer :: model
        type(flavor_t), dimension(5,2) :: flv
        type(cascade_set_t) :: cascade_set
        type(string_t) :: name, filename
        type(phs_parameters_t) :: phs_par
        name = "SM"
        filename = "SM.mdl"
        call syntax_model_file_init ()
        call model_list_read_model (name, filename, os_data, model)
        call model_write (model, verbose=.true.)
        call flavor_init (flv(1,1), 2, model)
        call flavor_init (flv(2,1),-2, model)
        call flavor_init (flv(3,1), 1, model)
        call flavor_init (flv(4,1),-1, model)
        call flavor_init (flv(5,1),21, model)
        call flavor_init (flv(1,2), 2, model)
        call flavor_init (flv(2,2),-2, model)
        call flavor_init (flv(3,2), 2, model)
        call flavor_init (flv(4,2),-2, model)
        call flavor_init (flv(5,2),21, model)
        phs_par%sqrts = 1000._default
        phs_par%off_shell = 2
        call cascade_set_generate (cascade_set, model, 2, 3, flv, phs_par,.true.)
        call cascade_set_write (cascade_set)
        call cascade_set_write_file_format (cascade_set)
        call cascade_set_final (cascade_set)
        call model_list_final ()
    end subroutine cascade_test

```

Chapter 13

Integration and event generation

With all necessary ingredients set up in the previous modules, the modules in this chapter do the high-level work of interfacing the process library, integrating and generating events.

process_libraries Create a process library, compile it, and load it, providing procedure pointers that the following modules can use.

hard_interactions Set up hard matrix element data appropriate for a given process and evaluate matrix elements in various ways (traced over all quantum numbers for integration, exclusive in some quantum numbers for analysis, expanded in color-flow patterns for showering).

processes Collect phase space, hard interactions, structure functions, cuts and whatever is needed to compute total partonic cross sections and partial decay widths.

events In the simulation step, generate individual events, concatenate decays, etc.

13.0.16 Process library interface

The process library is generated dynamically, and it does not provide a module. To access it, we define explicit interfaces that have to be included in the calling modules. These interfaces must be accessed both at compile time and at run-time, therefore we define a separate module that can be installed independent of the rest.

```
<prclib_interfaces.f90>≡  
  <File header>  
  
  module prclib_interfaces  
  
    <Use strings>  
    use iso_c_binding !NODEP!  
    use kinds !NODEP!
```

⟨Standard module head⟩

⟨Prclib interfaces: public⟩

⟨Prclib interfaces: interfaces⟩

end module prclib_interfaces

Return the number of processes contained in the library.

⟨Prclib interfaces: public⟩≡

public :: prc_get_n_processes

⟨Prclib interfaces: interfaces⟩≡

abstract interface

function prc_get_n_processes () result (n) bind(C)

import

integer(c_int) :: n

end function prc_get_n_processes

end interface

Return the C pointer to a string, and its length.

⟨Prclib interfaces: public⟩+≡

public :: prc_get_stringptr

⟨Prclib interfaces: interfaces⟩+≡

abstract interface

subroutine prc_get_stringptr (i, cptr, len) bind(C)

import

integer(c_int), intent(in) :: i

type(c_ptr), intent(out) :: cptr

integer(c_int), intent(out) :: len

end subroutine prc_get_stringptr

end interface

Return an integer.

⟨Prclib interfaces: public⟩+≡

public :: prc_get_int

⟨Prclib interfaces: interfaces⟩+≡

abstract interface

function prc_get_int (pid) result (n) bind(C)

import

integer(c_int), intent(in) :: pid

integer(c_int) :: n

end function prc_get_int

end interface

Return a logical.

⟨Prclib interfaces: public⟩+≡

public :: prc_get_log

⟨Prclib interfaces: interfaces⟩+≡

abstract interface

function prc_get_log (pid) result (l) bind(C)

import

integer(c_int), intent(in) :: pid


```

        logical(c_bool) :: 1
    end function prc_get_log
end interface

```

Return a two-dimensional integer array

<Prclib interfaces: public>+≡

```

    public :: prc_set_int_tab1

```

<Prclib interfaces: interfaces>+≡

```

    abstract interface
        subroutine prc_set_int_tab1 (pid, cptr, shape) bind(C)
            import
            integer(c_int), intent(in) :: pid
            type(c_ptr), intent(in) :: cptr
            integer(c_int), dimension(2), intent(in) :: shape
        end subroutine prc_set_int_tab1
    end interface

```

Return a three-dimensional integer and a two-dimensional logical array.

<Prclib interfaces: public>+≡

```

    public :: prc_set_int_tab2

```

<Prclib interfaces: interfaces>+≡

```

    abstract interface
        subroutine prc_set_int_tab2 (pid, cptr, shape, lcptr, lshape) bind(C)
            import
            integer(c_int), intent(in) :: pid
            type(c_ptr), intent(in) :: cptr
            integer(c_int), dimension(3), intent(in) :: shape
            type(c_ptr), intent(in) :: lcptr
            integer(c_int), dimension(2), intent(in) :: lshape
        end subroutine prc_set_int_tab2
    end interface

```

Return two integer arrays and a complex array.

<Prclib interfaces: public>+≡

```

    public :: prc_set_cf_tab

```

<Prclib interfaces: interfaces>+≡

```

    abstract interface
        subroutine prc_set_cf_tab (pid, iptr1, iptr2, cptr, shape) bind(C)
            import
            integer(c_int), intent(in) :: pid
            type(c_ptr), intent(in) :: iptr1, iptr2, cptr
            integer(c_int), dimension(1), intent(in) :: shape
        end subroutine prc_set_cf_tab
    end interface

```

These procedure signatures correspond to the process-specific API. The actual procedures are assigned by the pointer-assignment functions with signatures below.

Do overall process initialization if necessary.

<Prclib interfaces: public>+≡

```

    public :: prc_init

```

<Prclib interfaces: interfaces>+≡

```
abstract interface
  subroutine prc_init (par) bind(C)
    import
      real(c_default_float), dimension(*), intent(in) :: par
    end subroutine prc_init
end interface
```

Do overall process finalization if necessary.

<Prclib interfaces: public>+≡

```
public :: prc_final
```

<Prclib interfaces: interfaces>+≡

```
abstract interface
  subroutine prc_final () bind(C)
    end subroutine prc_final
end interface
```

Update the α_s value used for the matrix element computation.

<Prclib interfaces: public>+≡

```
public :: prc_update_alpha_s
```

<Prclib interfaces: interfaces>+≡

```
interface
  subroutine prc_update_alpha_s (alpha_s) bind(C)
    import
      real(c_default_float), intent(in) :: alpha_s
    end subroutine prc_update_alpha_s
end interface
```

Reset the counters for individual helicities. momenta.

<Prclib interfaces: public>+≡

```
public :: prc_reset_helicity_selection
```

<Prclib interfaces: interfaces>+≡

```
abstract interface
  subroutine prc_reset_helicity_selection (threshold, cutoff) bind(C)
    import
      real(c_default_float), intent(in) :: threshold
      integer(c_int), intent(in) :: cutoff
    end subroutine prc_reset_helicity_selection
end interface
```

Request the calculation of a new event, given a set of particle momenta.

<Prclib interfaces: public>+≡

```
public :: prc_new_event
```

<Prclib interfaces: interfaces>+≡

```
abstract interface
  subroutine prc_new_event (p) bind(C)
    import
      real(c_default_float), dimension(0:3,*), intent(in) :: p
    end subroutine prc_new_event
end interface
```

Return true if the selected combination of flavor, helicity and color is allowed.

<Prclib interfaces: public>+≡

```
public :: prc_is_allowed
```

```

<Prclib interfaces: interfaces>+≡
  abstract interface
    function prc_is_allowed (flv, hel, col) result (is_allowed) bind(C)
    import
      logical(c_bool) :: is_allowed
      integer(c_int), intent(in) :: flv, hel, col
    end function prc_is_allowed
  end interface

```

Assuming that the event has been computed, return a particular amplitude.

```

<Prclib interfaces: public>+≡
  public :: prc_get_amplitude

<Prclib interfaces: interfaces>+≡
  abstract interface
    function prc_get_amplitude (flv, hel, col) result (amp) bind(C)
    import
      complex(c_default_complex) :: amp
      integer(c_int), intent(in) :: flv, hel, col
    end function prc_get_amplitude
  end interface

```

Function that returns the pointer to a procedure:

```

<Prclib interfaces: public>+≡
  public :: prc_get_fptr

<Prclib interfaces: interfaces>+≡
  abstract interface
    subroutine prc_get_fptr (pid, fptr) bind(C)
    import
      integer(c_int), intent(in) :: pid
      type(c_funptr), intent(out) :: fptr
    end subroutine prc_get_fptr
  end interface

```

Interface for additional library unload / reload hooks

```

<Prclib interfaces: public>+≡
  public :: prclib_unload_hook
  public :: prclib_reload_hook

<Prclib interfaces: interfaces>+≡
  abstract interface
    subroutine prclib_unload_hook (libname)
    import
      type(string_t), intent(in) :: libname
    end subroutine prclib_unload_hook

    subroutine prclib_reload_hook (libname)
    import
      type(string_t), intent(in) :: libname
    end subroutine prclib_reload_hook
  end interface

```

13.1 Process library access

This module interfaces the OS to create, build, and use process libraries.

```
<process_libraries.f90>≡  
  <File header>  
  
  module process_libraries  
  
    use iso_c_binding !NODEP!  
    use kinds !NODEP!  
    <Use strings>  
    <Use file utils>  
    use diagnostics !NODEP!  
    use md5  
    use os_interface  
    use lexers  
    use variables  
    use user_code_interface  
    use models  
    use flavors  
    use prclib_interfaces  
  
    <Standard module head>  
  
    <Process libraries: public>  
  
    <Process libraries: parameters>  
  
    <Process libraries: types>  
  
    <Process libraries: interfaces>  
  
    <Process libraries: variables>  
  
    contains  
  
    <Process libraries: procedures>  
  
  end module process_libraries
```

13.1.1 Process methods

```
<Process libraries: parameters>≡  
  integer, parameter, public :: PRC_UNDEFINED = 0  
  integer, parameter, public :: PRC_OMEGA = 1  
  integer, parameter, public :: PRC_TEST = 2  
  integer, parameter, public :: PRC_UNIT = 3  
  integer, parameter, public :: PRC_EXTERNAL = 4  
  integer, parameter, public :: PRC_DIPOLE = 5
```

13.1.2 Status codes

```
<Process libraries: parameters>+≡
```

```

integer, parameter :: STAT_UNKNOWN = 0
integer, parameter :: STAT_CONFIGURED = 1
integer, parameter :: STAT_CODE_GENERATED = 2
integer, parameter :: STAT_COMPILED = 3
integer, parameter :: STAT_LOADED = 4

```

13.1.3 Process configuration data

Process configuration data.

```

<Process libraries: public>≡
    public :: process_configuration_t

<Process libraries: types>≡
    type :: process_configuration_t
    private
    integer :: status = STAT_UNKNOWN
    integer :: method = PRC_UNDEFINED
    type(string_t) :: id
    type(model_t), pointer :: model => null ()
    integer :: n_in = 0
    integer :: n_out = 0
    integer :: n_tot = 0
    type(string_t), dimension(:), allocatable :: prt_in, prt_out
    type(string_t) :: restrictions
    type(string_t) :: omega_flags
    character(32) :: md5sum = ""
    logical :: omega_openmp = .false.
    type(process_configuration_t), pointer :: next => null ()
end type process_configuration_t

```

Initialize a process configuration. The configuration is `intent(inout)` such that any `next` pointer is kept if an existing configuration is overwritten. Otherwise, all contents are reset.

```

<Process libraries: procedures>≡
    subroutine process_configuration_init &
        (prc_conf, prc_id, model, prt_in, prt_out, method, status, &
         restrictions, omega_flags, known_md5sum, omega_openmp)
    type(process_configuration_t), intent(inout) :: prc_conf
    type(string_t), intent(in) :: prc_id
    type(model_t), intent(in), target :: model
    type(string_t), dimension(:), intent(in) :: prt_in, prt_out
    integer, intent(in), optional :: status
    integer, intent(in), optional :: method
    type(string_t), intent(in), optional :: restrictions, omega_flags
    character(32), intent(in), optional :: known_md5sum
    logical, intent(in), optional :: omega_openmp
    prc_conf%id = prc_id
    prc_conf%model => model
    prc_conf%n_in = size (prt_in)
    prc_conf%n_out = size (prt_out)
    prc_conf%n_tot = prc_conf%n_in + prc_conf%n_out
    if (allocated (prc_conf%prt_in)) deallocate (prc_conf%prt_in)

```

```

allocate (prc_conf%prt_in (prc_conf%n_in))
if (allocated (prc_conf%prt_out)) deallocate (prc_conf%prt_out)
allocate (prc_conf%prt_out (prc_conf%n_out))
prc_conf%prt_in = prt_in
prc_conf%prt_out = prt_out
if (present (status)) then
    prc_conf%status = status
else
    prc_conf%status = STAT_CONFIGURED
end if
if (present (method)) then
    prc_conf%method = method
else
    prc_conf%method = PRC_OMEGA
end if
if (present (restrictions)) then
    prc_conf%restrictions = canonicalize_restrictions (restrictions, model)
else
    prc_conf%restrictions = ""
end if
if (present (omega_flags)) then
    prc_conf%omega_flags = omega_flags
else
    prc_conf%omega_flags = ""
end if
if (present (omega_openmp)) then
    select case (prc_conf%method)
    case (PRC_OMEGA)
        prc_conf%omega_openmp = omega_openmp
    case default
        prc_conf%omega_openmp = .false.
    end select
else
    prc_conf%omega_openmp = .false.
end if
if (present (known_md5sum)) then
    prc_conf%md5sum = known_md5sum
else
    call process_configuration_compute_md5sum (prc_conf)
end if
end subroutine process_configuration_init

```

Compute the MD5 sum. Write all relevant information to a string.

(Process libraries: procedures)+≡

```

subroutine process_configuration_compute_md5sum (prc_conf)
type(process_configuration_t), intent(inout) :: prc_conf
integer :: u, i
u = free_unit ()
open (unit=u, status="scratch")
write (u, "(A)") char (model_get_name (prc_conf%model))
write (u, "(I0)") prc_conf%n_in
write (u, "(I0)") prc_conf%n_out
write (u, "(I0)") prc_conf%n_tot
do i = 1, size (prc_conf%prt_in)

```

```

        write (u, "(A)") char (prc_conf%prt_in(i))
    end do
    do i = 1, size (prc_conf%prt_out)
        write (u, "(A)") char (prc_conf%prt_out(i))
    end do
    if (prc_conf%method /= PRC_OMEGA) then
        write (u, "(IO)") prc_conf%method
    end if
    if (prc_conf%restrictions /= "") then
        write (u, "(A)") char (prc_conf%restrictions)
    end if
    if (prc_conf%omega_flags /= "") then
        write (u, "(A)") char (prc_conf%omega_flags)
    end if
    rewind (u)
    prc_conf%md5sum = md5sum (u)
    close (u)
end subroutine process_configuration_compute_md5sum

```

Output (used by the 'list' command):

(Process libraries: procedures)+≡

```

subroutine process_configuration_write (prc_conf, unit)
    type(process_configuration_t), intent(in) :: prc_conf
    integer, intent(in), optional :: unit
    character :: status
    type(string_t) :: in_state, out_state
    type(string_t) :: restrictions_str, omega_flags_str
    integer :: i
    select case (prc_conf%status)
    case (STAT_UNKNOWN);      status = "?"
    case (STAT_CONFIGURED);   status = "O"
    case (STAT_CODE_GENERATED); status = "G"
    case (STAT_COMPILED);     status = "C"
    case (STAT_LOADED);       status = "L"
    end select
    in_state = prc_conf%prt_in(1)
    do i = 2, size (prc_conf%prt_in)
        in_state = in_state // ", " // prc_conf%prt_in(i)
    end do
    out_state = prc_conf%prt_out(1)
    do i = 2, size (prc_conf%prt_out)
        out_state = out_state // ", " // prc_conf%prt_out(i)
    end do
    if (prc_conf%restrictions == "" .and. prc_conf%omega_flags == "") then
        call msg_message (" [" // status // "] " // char (prc_conf%id) // " = " &
            // char (in_state) // " => " // char (out_state), unit)
    else
        if (prc_conf%restrictions /= "") then
            restrictions_str = "$restrictions = "" &      ! $
                // prc_conf%restrictions // """"
        else
            restrictions_str = ""
        end if
        if (prc_conf%omega_flags /= "") then

```

```

        omega_flags_str = "$omega_flags = "" &      ! $
        // prc_conf%omega_flags // """"
    else
        omega_flags_str = ""
    end if
    call msg_message (" [" // status // "]" // char (prc_conf%id) // " = " &
        // char (in_state) // " => " // char (out_state) &
        // " { " // char (restrictions_str) // " " &
        // char (omega_flags_str) // " }", unit)
    end if
end subroutine process_configuration_write

```

13.1.4 Canonicalize particle names

The `restrictions` string can contain particle names, but if it is passed verbatim to the matrix element generator, only those particles that the latter knows will be understood. Therefore, we tokenize the string, translate the particle names, and return the string with translations.

(*Process libraries: procedures*)+≡

```

function canonicalize_restrictions (string, model) result (newstring)
    type(string_t) :: newstring
    type(string_t), intent(in) :: string
    type(model_t), intent(in), target :: model
    type(stream_t), target :: stream
    type(lexer_t) :: lexer
    type(lexeme_t) :: lexeme
    type(string_t) :: token
    if (string == "") return
    if (extract (string, 1, 1) == "!") return
    newstring = ""
    call lexer_init (lexer, &
        comment_chars = "", &
        quote_chars = "'", &
        quote_match = "'", &
        single_chars = "+~:", &
        special_class = (/ "&" /), &
        keyword_list = null ())
    call stream_init (stream, string)
    call lexer_assign_stream (lexer, stream)
    TRANSFORM_TOKENS: do
        call lex (lexeme, lexer)
        if (lexeme_is_eof (lexeme)) exit TRANSFORM_TOKENS
        if (lexeme_is_break (lexeme)) then
            call msg_message ("Restriction string = " &
                // ' ' // char (string) // ' ')
            call msg_fatal ("Syntax error in restrictions specification")
            exit TRANSFORM_TOKENS
        end if
        token = lexeme_get_contents (lexeme)
        select case (lexeme_get_type (lexeme))
        case (T_NUMERIC)
            newstring = newstring // token

```



```

    case (T_IDENTIFIER)
      select case (char (extract (token, 1, 1)))
        case ("+", "~", "&", ":")
          newstring = newstring // token
        case default
          newstring = newstring // canonicalize_prt (token, model)
      end select
    case (T_QUOTED)
      newstring = newstring // canonicalize_prt (token, model)
    case default
      call msg_bug ("Token type error in restrictions specification")
    end select
  end do TRANSFORM_TOKENS
  call stream_final (stream)
end function canonicalize_restrictions

```

Transform a particle string into its flavor code and back; this yields the canonical name.

```

<Process libraries: procedures>+≡
function canonicalize_prt (string, model) result (newstring)
  type(string_t) :: newstring
  type(string_t), intent(in) :: string
  type(model_t), intent(in), target :: model
  type(flavor_t) :: flv
  integer :: pdg
  pdg = model_get_particle_pdg (model, string)
  if (pdg == 0) then
    call msg_fatal ("Undefined particle in restrictions specification")
  end if
  call flavor_init (flv, pdg, model)
  newstring = flavor_get_name (flv)
end function canonicalize_prt

```

13.1.5 Process library data

This object contains filenames, the complete set of process configuration data, the C filehandle interface for the shared library, and procedure pointers for the library functions.

The contents of this type are public because we do not want to have another wrapper around the procedure pointer components.

Note: The procedure pointer `prc_get_id` triggers a bug in nagfor5.2(649) [incorrect C generated], apparently related to the string argument of this procedure. Fortunately, we can live without it.

```

<Process libraries: public>+≡
  public :: process_library_t

<Process libraries: types>+≡
  type :: process_library_t
    ! private
    logical :: static = .false.
    integer :: status = STAT_UNKNOWN
    type(string_t) :: basename

```

```

type(string_t) :: srcname
type(string_t) :: libname
integer :: n_prc = 0
type(process_configuration_t), pointer :: prc_first => null ()
type(process_configuration_t), pointer :: prc_last => null ()
type(dlaccess_t) :: dlaccess
procedure(prc_get_n_processes), nopass, pointer :: get_n_prc => null ()
procedure(prc_get_stringptr), nopass, pointer :: get_process_id => null ()
procedure(prc_get_stringptr), nopass, pointer :: get_model_name => null ()
procedure(prc_get_stringptr), nopass, pointer :: &
    get_restrictions => null ()
procedure(prc_get_stringptr), nopass, pointer :: &
    get_omega_flags => null ()
procedure(prc_get_stringptr), nopass, pointer :: get_md5sum => null ()
procedure(prc_get_int), nopass, pointer :: get_n_in => null ()
procedure(prc_get_int), nopass, pointer :: get_n_out => null ()
procedure(prc_get_int), nopass, pointer :: get_n_flv => null ()
procedure(prc_get_int), nopass, pointer :: get_n_hel => null ()
procedure(prc_get_int), nopass, pointer :: get_n_col => null ()
procedure(prc_get_int), nopass, pointer :: get_n_cin => null ()
procedure(prc_get_int), nopass, pointer :: get_n_cf => null ()
procedure(prc_get_log), nopass, pointer :: get_openmp_status => null ()
procedure(prc_set_int_tab1), nopass, pointer :: set_flv_state => null ()
procedure(prc_set_int_tab1), nopass, pointer :: set_hel_state => null ()
procedure(prc_set_int_tab2), nopass, pointer :: set_col_state => null ()
procedure(prc_set_cf_tab), nopass, pointer :: set_cf_table => null ()
procedure(prc_get_fptra), nopass, pointer :: init_get_fptra => null()
procedure(prc_get_fptra), nopass, pointer :: final_get_fptra => null()
procedure(prc_get_fptra), nopass, pointer :: &
    update_alpha_s_get_fptra => null ()
procedure(prc_get_fptra), nopass, pointer :: &
    reset_helicity_selection_get_fptra => null ()
procedure(prc_get_fptra), nopass, pointer :: new_event_get_fptra => null ()
procedure(prc_get_fptra), nopass, pointer :: is_allowed_get_fptra => null ()
procedure(prc_get_fptra), nopass, pointer :: get_amplitude_get_fptra &
    => null ()
procedure(prclib_unload_hook), nopass, pointer :: unload_hook => null ()
procedure(prclib_reload_hook), nopass, pointer :: reload_hook => null ()
type(process_library_t), pointer :: next => null ()
end type process_library_t

```

Just allocate the configuration array and set filenames, the rest comes later.
Note that because libtool may be used, the actual `libname` can be determined
only after the library has been created.

```

<Process libraries: public>+≡
    public :: process_library_init

<Process libraries: procedures>+≡
    subroutine process_library_init (prc_lib, name, os_data)
        type(process_library_t), intent(out) :: prc_lib
        type(string_t), intent(in) :: name
        type(os_data_t), intent(in) :: os_data
        prc_lib%basename = name
        prc_lib%srcname = name // os_data%fc_src_ext
    end subroutine

```

```

    prc_lib%status = STAT_CONFIGURED
end subroutine process_library_init

```

Delete the process configuration list, if any.

```

<Process libraries: procedures>+≡
subroutine process_library_clear_configuration (prc_lib)
  type(process_library_t), intent(inout) :: prc_lib
  type(process_configuration_t), pointer :: current
  do while (associated (prc_lib%prc_first))
    current => prc_lib%prc_first
    prc_lib%prc_first => current%next
    deallocate (current)
  end do
  prc_lib%prc_last => null ()
  prc_lib%n_prc = 0
end subroutine process_library_clear_configuration

```

Close the library access if it is open. Delete the process-configuration list.

```

<Process libraries: public>+≡
public :: process_library_final

<Process libraries: procedures>+≡
subroutine process_library_final (prc_lib)
  type(process_library_t), intent(inout) :: prc_lib
  if (.not. prc_lib%static) call dlaccess_final (prc_lib%dlaccess)
  call process_library_clear_configuration (prc_lib)
end subroutine process_library_final

```

Given a pointer to a library, return the next pointer.

```

<Process libraries: public>+≡
public :: process_library_advance

<Process libraries: procedures>+≡
subroutine process_library_advance (prc_lib)
  type(process_library_t), pointer :: prc_lib
  prc_lib => prc_lib%next
end subroutine process_library_advance

```

Output (called by the 'show' command):

```

<Process libraries: public>+≡
public :: process_library_write

<Process libraries: procedures>+≡
subroutine process_library_write (prc_lib, unit)
  type(process_library_t), intent(in) :: prc_lib
  integer, intent(in), optional :: unit
  type(string_t) :: status
  type(process_configuration_t), pointer :: current
  select case (prc_lib%status)
  case (STAT_UNKNOWN)
    status = "[unknown]"
  case (STAT_CONFIGURED)
    status = "[open]"

```

```

case (STAT_CODE_GENERATED)
    status = "[generated code]"
case (STAT_COMPILED)
    status = "[compiled]"
case (STAT_LOADED)
    if (prc_lib%static) then
        status = "[static]"
    else
        status = "[loaded]"
    end if
end select
call msg_message ("Process library: " // char (prc_lib%basename) &
    // " " // char (status), unit)
current => prc_lib%prc_first
do while (associated (current))
    call process_configuration_write (current, unit)
    current => current%next
end do
end subroutine process_library_write

```

13.1.6 Accessing contents

Tell/set if the library is static or dynamic

(Process libraries: public)+≡

```

public :: process_library_set_static
public :: process_library_is_static

```

(Process libraries: procedures)+≡

```

subroutine process_library_set_static (prc_lib, flag)
    type(process_library_t), intent(inout) :: prc_lib
    logical, intent(in) :: flag
    prc_lib%static = flag
end subroutine process_library_set_static

```

```

function process_library_is_static (prc_lib) result (flag)
    logical :: flag
    type(process_library_t), intent(in) :: prc_lib
    flag = prc_lib%static
end function process_library_is_static

```

Return the nominal compilation status of a library.

(Process libraries: public)+≡

```

public :: process_library_is_compiled
public :: process_library_is_loaded

```

(Process libraries: procedures)+≡

```

function process_library_is_compiled (prc_lib) result (flag)
    logical :: flag
    type(process_library_t), intent(in) :: prc_lib
    flag = prc_lib%status >= STAT_COMPILED
end function process_library_is_compiled

```

```

function process_library_is_loaded (prc_lib) result (flag)

```

```

    logical :: flag
    type(process_library_t), intent(in) :: prc_lib
    flag = prc_lib%status >= STAT_LOADED
end function process_library_is_loaded

```

Return the name of a library (the basename).

```

<Process libraries: public>+≡
    public :: process_library_get_name

<Process libraries: procedures>+≡
    function process_library_get_name (prc_lib) result (name)
        type(string_t) :: name
        type(process_library_t), intent(in) :: prc_lib
        name = prc_lib%basename
    end function process_library_get_name

```

Return the number of processes defined so far.

```

<Process libraries: public>+≡
    public :: process_library_get_n_processes

<Process libraries: procedures>+≡
    function process_library_get_n_processes (prc_lib) result (n)
        integer :: n
        type(process_library_t), intent(in) :: prc_lib
        n = prc_lib%n_prc
    end function process_library_get_n_processes

```

Return the pointer to a process with specified tag.

```

<Process libraries: procedures>+≡
    function process_library_get_process_ptr (prc_lib, prc_id) result (current)
        type(process_library_t), intent(in), target :: prc_lib
        type(string_t), intent(in) :: prc_id
        type(process_configuration_t), pointer :: current
        current => prc_lib%prc_first
        do while (associated (current))
            if (current%id == prc_id) return
            current => current%next
        end do
    end function process_library_get_process_ptr

```

Return the pointer to a process with specified tag.

```

<Process libraries: public>+≡
    public :: process_library_check_name_consistency

<Process libraries: procedures>+≡
    subroutine process_library_check_name_consistency (prc_id, prc_lib)
        type(process_library_t), intent(in), target :: prc_lib
        type(string_t), intent(in) :: prc_id
        if (char (prc_id) == 'prc') &
            call msg_fatal ("The name 'prc' cannot " // &
                "be chosen as a valid process name.")
        if (prc_id == prc_lib%basename) &
            call msg_fatal ("Process and library names must not be identical ('" &

```

```

        // char (prc_id) // "'').")
    end subroutine process_library_check_name_consistency

```

Return the index of a process with specified tag. If the process is not found, return zero.

```

<Process libraries: public>+≡
    public :: process_library_get_process_index

<Process libraries: procedures>+≡
    function process_library_get_process_index (prc_lib, prc_id) result (index)
        integer :: index
        type(process_library_t), intent(in), target :: prc_lib
        type(string_t), intent(in) :: prc_id
        type(process_configuration_t), pointer :: current
        index = 0
        current => prc_lib%prc_first
        do while (associated (current))
            index = index + 1
            if (current%id == prc_id) return
            current => current%next
        end do
        index = 0
    end function process_library_get_process_index

```

13.1.7 Creating a process library

Configure a specific process in the list. First check if the process exists, then either edit the existing process configuration or initiate a new one. If a status is given, mark the process configuration accordingly. Overwrite any existing configuration for the given process ID. If the `rebuild_library` flag is set, do this silently and reset the status. If it is absent or unset, we want to keep the old configuration as far as possible. If the checksum has changed issue a warning that the configuration was overwritten. If the old status was higher, keep it.

```

<Process libraries: public>+≡
    public :: process_library_append

<Process libraries: procedures>+≡
    subroutine process_library_append &
        (prc_lib, prc_id, model, prt_in, prt_out, method, &
         status, restrictions, omega_flags, &
         rebuild_library, message, known_md5sum, &
         omega_openmp)
        type(process_library_t), intent(inout), target :: prc_lib
        type(string_t), intent(in) :: prc_id
        type(model_t), intent(in), target :: model
        type(string_t), dimension(:), intent(in) :: prt_in, prt_out
        integer, intent(in), optional :: status, method
        type(string_t), intent(in), optional :: restrictions, omega_flags
        logical, intent(in), optional :: rebuild_library, message, omega_openmp
        character(32), intent(in), optional :: known_md5sum
        type(process_configuration_t), pointer :: current
        character(32) :: old_md5sum
    end subroutine process_library_append

```

```

integer :: old_status
logical :: keep_status
logical :: msg
logical :: old_omega_openmp, new_omega_openmp
keep_status = .true.
if (present (rebuild_library)) keep_status = .not. rebuild_library
msg = .false.; if (present (message)) msg = message
if (.not. present (method)) then
    new_omega_openmp = omega_openmp
else
    select case (method)
    case (PRC_OMEGA)
        new_omega_openmp = omega_openmp
    case default
        new_omega_openmp = .false.
    end select
end if
current => process_library_get_process_ptr (prc_lib, prc_id)
if (associated (current)) then
    old_md5sum = current%md5sum
    old_status = current%status
    old_omega_openmp = current%omega_openmp
    call process_configuration_init &
        (current, prc_id, model, prt_in, prt_out, method, status, &
        restrictions, omega_flags, known_md5sum, new_omega_openmp)
    if (size (prt_in) == 0) then
        call msg_warning ("Process '" // char (prc_id) &
            // "': matrix element vanishes in selected model '" &
            // char (model_get_name (model)) // "'")
    else if (keep_status) then
        if ((current%md5sum == old_md5sum) .and. &
            (old_omega_openmp .eqv. new_omega_openmp)) then
            if (current%status <= old_status) then
                call msg_message ("Process '" // char (prc_id) &
                    // "': keeping configuration")
                current%status = old_status
            else
                call msg_message ("Process '" // char (prc_id) &
                    // "': updating configuration")
            end if
        else
            call msg_warning ("Process '" // char (prc_id) &
                // "': configuration changed, overwriting.")
        end if
    else
        if ((current%md5sum /= old_md5sum) .or. &
            (current%omega_openmp .neqv. old_omega_openmp)) then
            call msg_message ("Process '" // char (prc_id) &
                // "': ignoring previous configuration")
        end if
    end if
else
    allocate (current)
    if (associated (prc_lib%prc_last)) then

```

```

        prc_lib%prc_last%next => current
    else
        prc_lib%prc_first => current
    end if
    prc_lib%prc_last => current
    prc_lib%n_prc = prc_lib%n_prc + 1
    call process_library_check_name_consistency (prc_id, prc_lib)
    call process_configuration_init &
        (current, prc_id, model, prt_in, prt_out, method, status, &
         restrictions, omega_flags, known_md5sum, new_omega_openmp)
    call process_update_code_status (current, keep_status)
    if (msg) call msg_message &
        ("Added process to library '" // char (prc_lib%basename) // "':")
    end if
    if (msg) call process_configuration_write (current)
end subroutine process_library_append

```

Look for an existing file for the current process and its MD5 signature. If successful and a rebuild flag is set, reset the status to STAT_CODE_GENERATED. Otherwise, just issue appropriate diagnostic messages.

(Process libraries: procedures)+≡

```

subroutine process_update_code_status (prc_conf, keep_status)
    type(process_configuration_t), intent(inout) :: prc_conf
    logical, intent(in) :: keep_status
    type(string_t) :: filename
    logical :: exist, found
    integer :: u, iostat
    character(80) :: buffer
    character(32) :: md5sum
    logical :: omega_openmp
    filename = prc_conf%id // ".f90"
    inquire (file=char(filename), exist=exist)
    if (exist) then
        found = .false.
        u = free_unit ()
        omega_openmp = .false.
        open (u, file=char(filename), action="read")
        SCAN_FILE: do
            read (u, "(A)", iostat=iostat) buffer
            select case (iostat)
            case (0)
                if (buffer(1:12) == "    md5sum ==") then
                    md5sum = buffer(15:47)
                    found = .true.
                end if
                if (buffer(1:5) == " !$OMP") omega_openmp = .true. ! $
            case default
                exit SCAN_FILE
            end select
        end do SCAN_FILE
        close (u)
        if (found) then
            if (keep_status) then

```



```

        if (prc_conf%status < STAT_CODE_GENERATED) then
            if ((md5sum == prc_conf%md5sum) .and. &
                (omega_openmp .eqv. prc_conf%omega_openmp)) then
                call msg_message ("Process '" // char (prc_conf%id) &
                    // "': using existing source code")
                prc_conf%status = STAT_CODE_GENERATED
            else
                call msg_warning ("Process '" // char (prc_conf%id) &
                    // "': will overwrite existing source code")
            end if
        else if ((md5sum /= prc_conf%md5sum) .or. &
            (omega_openmp .neqv. prc_conf%omega_openmp)) then
            call msg_warning ("Process '" // char (prc_conf%id) &
                // "': source code and loaded checksums differ")
        end if
    else if (prc_conf%status < STAT_CODE_GENERATED) then
        call msg_message ("Process '" // char (prc_conf%id) &
            // "': ignoring existing source code")
    end if
else
    call msg_warning ("Process '" // char (prc_conf%id) &
        // "': No MD5 sum found in source code")
end if
end if
end subroutine process_update_code_status

```

Check whether all processes in the current library are configured, compiled and loaded, and update the library status accordingly.

If the library needs recompilation, unload it now if necessary.

```

<Process libraries: public>+≡
    public :: process_library_update_status

<Process libraries: procedures>+≡
    subroutine process_library_update_status (prc_lib)
        type(process_library_t), intent(inout), target :: prc_lib
        type(process_configuration_t), pointer :: prc_conf
        integer :: initial_status
        initial_status = prc_lib%status
        prc_conf => prc_lib%prc_first
        do while (associated (prc_conf))
            prc_lib%status = min (prc_lib%status, prc_conf%status)
            prc_conf => prc_conf%next
        end do
        if (initial_status == STAT_LOADED .and. prc_lib%status < STAT_LOADED) &
            call process_library_unload (prc_lib)
    end subroutine process_library_update_status

```

Recover process configuration from a loaded library. Existing configurations for processes present in the loaded library will be overwritten. Return the pointer to the model appropriate for the loaded library.

```

<Process libraries: procedures>+≡
    subroutine process_library_load_configuration &
        (prc_lib, os_data, model)

```

```

type(process_library_t), intent(inout), target :: prc_lib
type(os_data_t), intent(in) :: os_data
type(model_t), pointer :: model
integer :: n_prc, p, n_flv, n_in, n_out, n_tot, i
integer(c_int) :: pid
integer, dimension(:,:), allocatable :: flv_state
integer(c_int), dimension(:,:), allocatable, target :: flv_state_tmp
type(string_t) :: prc_id, model_name, filename, restrictions, omega_flags
type(string_t), dimension(:), allocatable :: prt_in, prt_out
logical :: omega_openmp
character(32) :: md5sum
n_prc = prc_lib% get_n_prc ()
SCAN_PROCESSES: do p = 1, n_prc
    pid = p
    prc_id = process_library_get_process_id (prc_lib, pid)
    md5sum = process_library_get_process_md5sum (prc_lib, pid)
    model_name = process_library_get_process_model_name (prc_lib, pid)
    restrictions = process_library_get_process_restrictions (prc_lib, pid)
    omega_flags = process_library_get_process_omega_flags (prc_lib, pid)
    omega_openmp = process_library_get_openmp_status (prc_lib, pid)
    filename = model_name // ".mdl"
    model => null ()
    call model_list_read_model (model_name, filename, os_data, model)
    if (.not. associated (model)) then
        call msg_error ("Process library '" // char (prc_lib%basename) &
            // "', process '" // char (prc_id) // "': " &
            // "model unavailable, process skipped")
        cycle SCAN_PROCESSES
    end if
    n_in = prc_lib% get_n_in (pid)
    n_out = prc_lib% get_n_out (pid)
    n_tot = n_in + n_out
    n_flv = prc_lib% get_n_flv (pid)
    allocate (flv_state (n_tot, n_flv))
    allocate (flv_state_tmp (n_tot, n_flv))
    allocate (prt_in (n_in ))
    allocate (prt_out (n_out))
    call prc_lib% set_flv_state (pid, &
        c_loc (flv_state_tmp), &
        int((/n_tot, n_flv/), kind=c_int))
    flv_state = flv_state_tmp
    do i = 1, n_in
        prt_in(i) = particle_name_string (flv_state (i, :), model)
    end do
    do i = 1, n_out
        prt_out(i) = particle_name_string (flv_state (n_in+i, :), model)
    end do
    call process_library_append &
        (prc_lib, prc_id, model, prt_in, prt_out, &
        status=STAT_LOADED, &
        restrictions=restrictions, omega_flags=omega_flags, &
        known_md5sum=md5sum, omega_openmp=omega_openmp)
    deallocate (prt_in, prt_out, flv_state, flv_state_tmp)
end do SCAN_PROCESSES

```

```

contains
  function particle_name_string (ff, model) result (prt)
    type(string_t) :: prt
    integer, dimension(:), intent(in) :: ff
    type(model_t), intent(in), target :: model
    type(flavor_t) :: flv
    integer :: i
    prt = ""
    do i = 1, size (ff)
      if (all (ff(i) /= ff(:i-1))) then
        call flavor_init (flv, ff(i), model)
        if (prt /= "") prt = prt // ":"
        prt = prt // flavor_get_name (flv)
      end if
    end do
  end function particle_name_string
end subroutine process_library_load_configuration

```

(Process libraries: public)+≡

```

public :: process_library_get_process_id
public :: process_library_get_process_pid
public :: process_library_get_process_md5sum
public :: process_library_get_process_model_name
public :: process_library_get_openmp_status

```

(Process libraries: procedures)+≡

```

function process_library_get_process_id (prc_lib, pid) result (process_id)
  type(string_t) :: process_id
  type(process_library_t), intent(in), target :: prc_lib
  integer(c_int), intent(in) :: pid
  type(c_ptr) :: cptr
  integer(c_int) :: len
  character(kind=c_char), dimension(:), pointer :: char_array
  integer, dimension(1) :: shape
  call prc_lib% get_process_id (pid, cptr, len)
  if (c_associated (cptr)) then
    shape(1) = len
    call c_f_pointer (cptr, char_array, shape)
    process_id = char_from_array (char_array)
    call prc_lib% get_process_id (0_c_int, cptr, len)
  else
    process_id = ""
  end if
end function process_library_get_process_id

function process_library_get_process_pid (prc_lib, id) result (process_pid)
  type(process_library_t), intent(in) :: prc_lib
  type(string_t), intent(in) :: id
  integer :: process_pid, pid, n_proc
  process_pid = -1
  n_proc = process_library_get_n_processes (prc_lib)
  if (n_proc <= 0) return
  do pid = 1, n_proc
    if (process_library_get_process_id (prc_lib, pid) == id) then

```

```

        process_pid = pid
        return
    end if
end do
end function process_library_get_process_pid

function process_library_get_process_model_name &
    (prc_lib, pid) result (model_name)
    type(string_t) :: model_name
    type(process_library_t), intent(in), target :: prc_lib
    integer(c_int), intent(in) :: pid
    type(c_ptr) :: cptr
    integer(c_int) :: len
    character(kind=c_char), dimension(:), pointer :: char_array
    integer, dimension(1) :: shape
    call prc_lib% get_model_name (pid, cptr, len)
    if (c_associated (cptr)) then
        shape(1) = len
        call c_f_pointer (cptr, char_array, shape)
        model_name = char_from_array (char_array)
        call prc_lib% get_model_name (0_c_int, cptr, len)
    else
        model_name = ""
    end if
end function process_library_get_process_model_name

function process_library_get_process_restrictions &
    (prc_lib, pid) result (restrictions)
    type(string_t) :: restrictions
    type(process_library_t), intent(in), target :: prc_lib
    integer(c_int), intent(in) :: pid
    type(c_ptr) :: cptr
    integer(c_int) :: len
    character(kind=c_char), dimension(:), pointer :: char_array
    integer, dimension(1) :: shape
    call prc_lib% get_restrictions (pid, cptr, len)
    if (c_associated (cptr)) then
        shape(1) = len
        call c_f_pointer (cptr, char_array, shape)
        restrictions = char_from_array (char_array)
        call prc_lib% get_restrictions (0_c_int, cptr, len)
    else
        restrictions = ""
    end if
end function process_library_get_process_restrictions

function process_library_get_process_omega_flags &
    (prc_lib, pid) result (omega_flags)
    type(string_t) :: omega_flags
    type(process_library_t), intent(in), target :: prc_lib
    integer(c_int), intent(in) :: pid
    type(c_ptr) :: cptr
    integer(c_int) :: len
    character(kind=c_char), dimension(:), pointer :: char_array

```

```

integer, dimension(1) :: shape
call prc_lib% get_omega_flags (pid, cptr, len)
if (c_associated (cptr)) then
    shape(1) = len
    call c_f_pointer (cptr, char_array, shape)
    omega_flags = char_from_array (char_array)
    call prc_lib% get_omega_flags (0_c_int, cptr, len)
else
    omega_flags = ""
end if
end function process_library_get_process_omega_flags

function process_library_get_omp_status &
    (prc_lib, pid) result (omp_status)
    type(process_library_t), intent(in), target :: prc_lib
    integer(c_int), intent(in) :: pid
    logical :: omp_status
    type(c_ptr) :: cptr
    omp_status = prc_lib%get_omp_status (pid)
end function process_library_get_omp_status

function process_library_get_process_md5sum (prc_lib, pid) result (md5sum)
    type(string_t) :: md5sum
    type(process_library_t), intent(in), target :: prc_lib
    integer(c_int), intent(in) :: pid
    type(c_ptr) :: cptr
    integer(c_int) :: len
    character(kind=c_char), dimension(:), pointer :: char_array
    integer, dimension(1) :: shape
    call prc_lib% get_md5sum (pid, cptr, len)
    if (c_associated (cptr)) then
        shape(1) = len
        call c_f_pointer (cptr, char_array, shape)
        md5sum = char_from_array (char_array)
        call prc_lib% get_md5sum (0_c_int, cptr, len)
    else
        md5sum = ""
    end if
end function process_library_get_process_md5sum

```

Auxiliary: Transform a character array into a character string.

(Process libraries: procedures) +≡

```

function char_from_array (a) result (char)
    character(kind=c_char), dimension(:), intent(in) :: a
    character(len=size(a)) :: char
    integer :: i
    do i = 1, len (char)
        char(i:i) = a(i)
    end do
end function char_from_array

```

Generate process source code. Do this for all processes which have just been configured, unless there is a source-code file with identical MD5sum.

```

<Process libraries: public>+=
    public :: process_library_generate_code

<Process libraries: procedures>+=
    subroutine process_library_generate_code (prc_lib, os_data, simulate)
        type(process_library_t), intent(in) :: prc_lib
        type(os_data_t), intent(in) :: os_data
        logical, intent(in), optional :: simulate
        type(process_configuration_t), pointer :: current
        integer :: status
        call msg_message ("Generating code for process library '" &
            // char (process_library_get_name (prc_lib)) // "'")
        current => prc_lib%prc_first
        SCAN_PROCESSES: do while (associated (current))
            select case (current%status)
            case (STAT_CONFIGURED)
                select case (current%method)
                case (PRC_OMEGA)
                    call call_omega (current, os_data, status, simulate)
                    if (status == 0) then
                        current%status = STAT_CODE_GENERATED
                    else
                        call msg_error ("Process '" // char (current%id) &
                            // "': code generation failed")
                    end if
                case (PRC_TEST)
                    call write_unit_matrix_element (current, os_data, status, unit=.false.)
                    if (status == 0) then
                        current%status = STAT_CODE_GENERATED
                    else
                        call msg_error ("Process '" // char (current%id) &
                            // "': code generation failed")
                    end if
                case (PRC_UNIT)
                    call write_unit_matrix_element (current, os_data, status, unit=.true.)
                    if (status == 0) then
                        current%status = STAT_CODE_GENERATED
                    else
                        call msg_error ("Process '" // char (current%id) &
                            // "': code generation failed")
                    end if
                case default
                    call msg_fatal ("These methods are not yet implemented.")
            end select
            case (STAT_CODE_GENERATED:)
                call msg_message ("Skipping process '" // char (current%id) &
                    // "' (source code exists)")
            case default
                call msg_message ("Skipping process '" // char (current%id) &
                    // "': (undefined configuration)")
            end select
            current => current%next
        end do SCAN_PROCESSES
    end subroutine process_library_generate_code

```

Call O'MEGA for process-code generation.

(*Process libraries: procedures*)+=

```

subroutine call_omega (prc_conf, os_data, status, simulate)
  type(process_configuration_t), intent(in) :: prc_conf
  type(os_data_t), intent(in) :: os_data
  integer, intent(out) :: status
  logical, intent(in), optional :: simulate
  type(string_t) :: command_string, binary_name
  type(string_t) :: model_id, omega_mode, omega_cascade, omega_kmatrix, &
    omega_openmp
  integer :: j
  logical :: sim, binary_found
  sim = .false.; if (present (simulate)) sim = simulate
  call msg_message ("Calling O'Mega for process '" &
    // char (prc_conf%id) // "'")
  model_id = model_get_name (prc_conf%model)
  binary_name = "omega_" // model_id // ".opt"
  binary_found = .false.
  select case (char (model_id))
  case ("SM_km")
    omega_kmatrix = "-target:kmatrix_write"
  case default
    omega_kmatrix = ""
  end select
  if (prc_conf%omega_openmp) then
    omega_openmp = "-target:openmp"
    call msg_message ("Enabling OpenMP support in O'Mega")
    call msg_message ("WARNING: enabling OpenMP support in O'Mega --- " &
      // "make sure that _both_ "
    call msg_message ("  WHIZARD _and_ the matrix element are compiled with " &
      // "the proper OpenMP compiler flags.")
    call msg_message ("  Be prepared for broken results if you compile only " &
      // " the matrix element with OpenMP flags.")
  else
    omega_openmp = ""
  end if
  if (.not. os_data%use_testfiles) then
    command_string = os_data%whizard_omega_binpath_local &
      // "/" // binary_name
    inquire (file=char (command_string), exist=binary_found)
  end if
  if (.not. binary_found) then
    command_string = os_data%whizard_omega_binpath // "/" // binary_name
    inquire (file=char (command_string), exist=binary_found)
  end if
  if (.not. binary_found) &
    call msg_fatal ("O'Mega binary "" // char (binary_name) // "" not found")
  select case (prc_conf%n_in)
  case (1); omega_mode = "-decay"
  case (2); omega_mode = "-scatter"
  end select
  if (prc_conf%restrictions == "") then
    omega_cascade = ""
  else if (extract (prc_conf%restrictions, 1, 1) == "!") then

```

```

        omega_cascade = " -cascade '" &
            // extract (prc_conf%restrictions, 2) // ""
    else
        omega_cascade = " -cascade '" // prc_conf%restrictions // ""
    end if
    command_string = command_string &
        // " -o " // prc_conf%id // ".f90" &
        // " -target:whizard" &
        // " -target:parameter_module parameters_" // model_id &
        // " -target:module opr_" // prc_conf%id &
        // omega_kmatrix // omega_openmp &
        // " -target:md5sum " // prc_conf%md5sum &
        // omega_cascade &
        // " -fusion:progress" &
        // " " // prc_conf%omega_flags &
        // " " // omega_mode
    command_string = command_string // " "
    do j = 1, prc_conf%n_in
        if (j == 1) then
            command_string = command_string // ""
        else
            command_string = command_string // " "
        end if
        command_string = command_string // prc_conf%prt_in(j)
    end do
    command_string = command_string // " ->"
    do j = 1, prc_conf%n_out
        command_string = command_string &
            // " " // prc_conf%prt_out(j)
    end do
    command_string = command_string // ""
    if (sim) then
        command_string = "cp " // os_data%whizard_testdatapath // "/" &
            // prc_conf%id // ".f90 ."
        call msg_message ("[call not executed, instead: copy file from " &
            // char (os_data%whizard_testdatapath) // "]")
    end if
    call os_system_call (command_string, status, verbose=.true.)
end subroutine call_omega

```

Intrinsic WHIZARD call for unit matrix elements generation. Note that color flows, spins and flavors are taken as trivial, i.e. there is one (trivial) color flow, one spin combination for all particles, and tensor products for flavors are ignored.

(*Process libraries: procedures*) $\vdash\equiv$

```

subroutine write_unit_matrix_element (prc_conf, os_data, status, unit)
    type(process_configuration_t), intent(in) :: prc_conf
    type(os_data_t), intent(in) :: os_data
    integer, intent(out) :: status
    logical, intent(in) :: unit
    integer, dimension(prc_conf%n_in) :: prt_in, mult_in, col_in
    type(flavor_t), dimension(1:prc_conf%n_in) :: flv_in
    integer, dimension(prc_conf%n_out) :: prt_out, mult_out
    integer, dimension(prc_conf%n_tot) :: prt, mult

```



```

integer, dimension(:,,:), allocatable :: sxxx
integer :: dummy
type(flavor_t), dimension(1:prc_conf%n_out) :: flv_out
type(string_t) :: proc_str, comment_str
integer :: u, i, j, count
integer :: hel, hel_in, hel_out, fac, factor, col_fac
type(string_t) :: filename
comment_str = ""
do i = 1, prc_conf%n_in
    comment_str = comment_str // prc_conf%prt_in(i) // " "
end do
do j = 1, prc_conf%n_out
    comment_str = comment_str // prc_conf%prt_out(j) // " "
end do
do i = 1, prc_conf%n_in
    prt_in(i) = model_get_particle_pdg (prc_conf%model, prc_conf%prt_in(i))
    call flavor_init (flv_in(i), prt_in(i), prc_conf%model)
    mult_in(i) = flavor_get_multiplicity (flv_in(i))
    col_in(i) = abs(flavor_get_color_type (flv_in(i)))
    mult(i) = mult_in(i)
end do
do j = 1, prc_conf%n_out
    prt_out(j) = model_get_particle_pdg (prc_conf%model, prc_conf%prt_out(j))
    call flavor_init (flv_out(j), prt_out(j), prc_conf%model)
    mult_out(j) = flavor_get_multiplicity (flv_out(j))
    mult(prc_conf%n_in + j) = mult_out(j)
end do
prt(1:prc_conf%n_in) = prt_in(1:prc_conf%n_in)
prt(prc_conf%n_in+1:prc_conf%n_tot) = prt_out(1:prc_conf%n_out)
proc_str = converter (prt)
hel_in = product (mult_in)
hel_out = product (mult_out)
col_fac = product (col_in)
hel = hel_in * hel_out
fac = hel
dummy = 1
factor = 1
if (prc_conf%n_out >= 3) then
    do i = 3, prc_conf%n_out
        factor = factor * (i - 2) * (i - 1)
    end do
end if
factor = factor * col_fac
allocate (sxxx(1:hel,1:prc_conf%n_tot))
call create_spin_table (dummy,hel,fac,mult,sxxx)
call msg_message ("Writing test matrix element for process '" &
    // char (prc_conf%id) // "'")
filename = prc_conf%id // ".f90"
u = free_unit ()
open (unit=u, file=char(filename), action="write")
write (u, "(A)") "! File generated automatically by WHIZARD"
write (u, "(A)") "!"
write (u, "(A)") "! Note that irresp. of what you demanded WHIZARD"
write (u, "(A)") "! treats this as colorless process "

```

```

write (u, "(A)") "!"
write (u, "(A)") "module tpr_" // char(prc_conf%id)
write (u, "(A)") "
write (u, "(A)") " use kinds"
write (u, "(A)") " use omega_color, OCF => omega_color_factor"
write (u, "(A)") "
write (u, "(A)") " implicit none"
write (u, "(A)") " private"
write (u, "(A)") "
write (u, "(A)") " public :: md5sum"
write (u, "(A)") " public :: number_particles_in, number_particles_out"
write (u, "(A)") " public :: number_spin_states, spin_states"
write (u, "(A)") " public :: number_flavor_states, flavor_states"
write (u, "(A)") " public :: number_color_flows, color_flows"
write (u, "(A)") " public :: number_color_indices, number_color_factors, &"
write (u, "(A)") " color_factors, color_sum, openmp_supported"
write (u, "(A)") " public :: init, final, update_alpha_s"
write (u, "(A)") " public :: reset_helicity_selection"
write (u, "(A)") "
write (u, "(A)") " public :: new_event, is_allowed, get_amplitude"
write (u, "(A)") "
write (u, "(A)") " real(default), parameter :: &"
write (u, "(A)") " & conv = 0.38937966e12_default"
write (u, "(A)") "
write (u, "(A)") " real(default), parameter :: &"
write (u, "(A)") " & pi = 3.1415926535897932384626433832795028841972_default"
write (u, "(A)") "
write (u, "(A)") " real(default), parameter :: &"
if (unit) then
  write (u, "(A)") " & const = 1"
else
  write (u, "(A,1x,I0,A)") " & const = (16 * pi / conv) * " &
    // "(16 * pi**2)**(", prc_conf%n_out, "-2) "
end if
write (u, "(A)") "
write (u, "(A,1x,I0)") " integer, parameter, private :: n_prt = ", &
  prc_conf%n_tot
write (u, "(A,1x,I0)") " integer, parameter, private :: n_in = ", &
  prc_conf%n_in
write (u, "(A,1x,I0)") " integer, parameter, private :: n_out = ", &
  prc_conf%n_out
write (u, "(A)") " integer, parameter, private :: n_cflow = 1"
write (u, "(A)") " integer, parameter, private :: n_cindex = 2"
write (u, "(A)") " !!! We ignore tensor products and take only one flavor state."
write (u, "(A)") " integer, parameter, private :: n_flv = 1"
write (u, "(A,1x,I0)") " integer, parameter, private :: n_hel = ", hel
write (u, "(A)") "
write (u, "(A)") " logical, parameter, private :: T = .true."
write (u, "(A)") " logical, parameter, private :: F = .false."
write (u, "(A)") "
do i = 1, hel
  write (u, "(A)") " integer, dimension(n_prt), parameter, private :: &"
  write (u, "(A)") " // s_conv(i) // " = (/ " // char(converter(sxxx(i,1:prc_conf%n_tot)
end do

```

```

write (u, "(A)") " integer, dimension(n_prt,n_hel), parameter, private :: table_spin_states =
write (u, "(A)") " reshape ( (/ & "
do i = 1, hel-1
    write (u, "(A)") " " // s_conv(i) // ", & "
end do
write (u, "(A)") " " // s_conv(hel) // " & "
write (u, "(A)") " /), (/ n_prt, n_hel /) )"
write (u, "(A)") " "
write (u, "(A)") " integer, dimension(n_prt), parameter, private :: &"
write (u, "(A)") " f0001 = (/ " // char(proc_str) // " /) ! " // char(comment_str)
write (u, "(A)") " integer, dimension(n_prt,n_flv), parameter, private :: table_flavor_states
write (u, "(A)") " reshape ( (/ f0001 /), (/ n_prt, n_flv /) )"
write (u, "(A)") " "
write (u, "(A)") " integer, dimension(n_cindex, n_prt), parameter, private :: &"
write (u, "(A)") " c0001 = reshape ( (/ " // char(dummy_colorizer (flv_in)) // " " // &
    (repeat ("0,0, ", prc_conf%n_out-1)) // "0,0 /), " // " (/ n_cindex, n_prt /) )"
write (u, "(A)") " integer, dimension(n_cindex, n_prt, n_cflow), parameter, private :: &"
write (u, "(A)") " table_color_flows = reshape ( (/ c0001 /), (/ n_cindex, n_prt, n_cflow /) )"
write (u, "(A)") " "
write (u, "(A)") " logical, dimension(n_prt), parameter, private :: &"
write (u, "(A)") " g0001 = (/ " // (repeat ("F, ", prc_conf%n_tot-1)) // "F /) "
write (u, "(A)") " logical, dimension(n_prt, n_cflow), parameter, private :: table_ghost_flag
write (u, "(A)") " reshape ( (/ g0001 /), (/ n_prt, n_cflow /) )"
write (u, "(A)") " "
write (u, "(A)") " integer, parameter, private :: n_cfactors = 1"
write (u, "(A)") " type(OCF), dimension(n_cfactors), parameter, private :: &"
write (u, "(A)") " table_color_factors = (/ OCF(1,1,+1._default) /)"
write (u, "(A)") " "
write (u, "(A)") " logical, dimension(n_flv), parameter, private :: a0001 = (/ T /)"
write (u, "(A)") " logical, dimension(n_flv, n_cflow), parameter, private :: &"
write (u, "(A)") " flv_col_is_allowed = reshape ( (/ a0001 /), (/ n_flv, n_cflow /) )"
write (u, "(A)") " "
write (u, "(A)") " complex(default), dimension (n_flv, n_hel, n_cflow), private, save :: amp"
write (u, "(A)") " "
write (u, "(A)") " logical, dimension(n_hel), private, save :: hel_is_allowed = T"
write (u, "(A)") " "
write (u, "(A)") "contains"
write (u, "(A)") " "
write (u, "(A)") " pure function md5sum ()"
write (u, "(A)") " character(len=32) :: md5sum"
write (u, "(A)") " ! DON'T EVEN THINK of modifying the following line!"
write (u, "(A)") " md5sum = "" // prc_conf%md5sum // ""
write (u, "(A)") " end function md5sum"
write (u, "(A)") " "
write (u, "(A)") " subroutine init (par)"
write (u, "(A)") " real(default), dimension(*), intent(in) :: par"
write (u, "(A)") " end subroutine init"
write (u, "(A)") " "
write (u, "(A)") " subroutine final ()"
write (u, "(A)") " end subroutine final"
write (u, "(A)") " "
write (u, "(A)") " subroutine update_alpha_s (alpha_s)"
write (u, "(A)") " real(default), intent(in) :: alpha_s"
write (u, "(A)") " end subroutine update_alpha_s"

```

```

write (u, "(A)") "
write (u, "(A)") " pure function number_particles_in () result (n)"
write (u, "(A)") " integer :: n"
write (u, "(A)") " n = n_in"
write (u, "(A)") " end function number_particles_in"
write (u, "(A)") "
write (u, "(A)") " pure function number_particles_out () result (n)"
write (u, "(A)") " integer :: n"
write (u, "(A)") " n = n_out"
write (u, "(A)") " end function number_particles_out"
write (u, "(A)") "
write (u, "(A)") " pure function number_spin_states () result (n)"
write (u, "(A)") " integer :: n"
write (u, "(A)") " n = size (table_spin_states, dim=2)"
write (u, "(A)") " end function number_spin_states"
write (u, "(A)") "
write (u, "(A)") " pure subroutine spin_states (a)"
write (u, "(A)") " integer, dimension(:,,:), intent(out) :: a"
write (u, "(A)") " a = table_spin_states"
write (u, "(A)") " end subroutine spin_states"
write (u, "(A)") "
write (u, "(A)") " pure function number_flavor_states () result (n)"
write (u, "(A)") " integer :: n"
write (u, "(A)") " n = 1"
write (u, "(A)") " end function number_flavor_states"
write (u, "(A)") "
write (u, "(A)") " pure subroutine flavor_states (a)"
write (u, "(A)") " integer, dimension(:,,:), intent(out) :: a"
write (u, "(A)") " a = table_flavor_states"
write (u, "(A)") " end subroutine flavor_states"
write (u, "(A)") "
write (u, "(A)") " pure function number_color_indices () result (n)"
write (u, "(A)") " integer :: n"
write (u, "(A)") " n = size(table_color_flows, dim=1)"
write (u, "(A)") " end function number_color_indices"
write (u, "(A)") "
write (u, "(A)") " pure subroutine color_factors (cf)"
write (u, "(A)") " type(OCF), dimension(:,,:), intent(out) :: cf"
write (u, "(A)") " cf = table_color_factors"
write (u, "(A)") " end subroutine color_factors"
write (u, "(A)") "
write (u, "(A)") " pure function color_sum (flv, hel) result (amp2)"
write (u, "(A)") " integer, intent(in) :: flv, hel"
write (u, "(A)") " real(kind=default) :: amp2"
write (u, "(A)") " amp2 = real (omega_color_sum (flv, hel, amp, table_color_factors))"
write (u, "(A)") " end function color_sum"
write (u, "(A)") "
write (u, "(A)") " pure function number_color_flows () result (n)"
write (u, "(A)") " integer :: n"
write (u, "(A)") " n = size (table_color_flows, dim=3)"
write (u, "(A)") " end function number_color_flows"
write (u, "(A)") "
write (u, "(A)") " pure subroutine color_flows (a, g)"
write (u, "(A)") " integer, dimension(:, :, :), intent(out) :: a"

```

```

write (u, "(A)") "    logical, dimension(:, :), intent(out) :: g"
write (u, "(A)") "    a = table_color_flows"
write (u, "(A)") "    g = table_ghost_flags"
write (u, "(A)") "end subroutine color_flows"
write (u, "(A)") "
write (u, "(A)") "    pure function number_color_factors () result (n)"
write (u, "(A)") "        integer :: n"
write (u, "(A)") "        n = size (table_color_factors)"
write (u, "(A)") "    end function number_color_factors"
write (u, "(A)") "
write (u, "(A)") "    pure function openmp_supported () result (status)"
write (u, "(A)") "        logical :: status"
write (u, "(A)") "        status = .false."
write (u, "(A)") "    end function openmp_supported"
write (u, "(A)") "
write (u, "(A)") "    subroutine new_event (p)"
write (u, "(A)") "        real(default), dimension(0:3,*), intent(in) :: p"
write (u, "(A)") "        call calculate_amplitudes (amp, p)"
write (u, "(A)") "    end subroutine new_event"
write (u, "(A)") "
write (u, "(A)") "    subroutine reset_helicity_selection (threshold, cutoff)"
write (u, "(A)") "        real(default), intent(in) :: threshold"
write (u, "(A)") "        integer, intent(in) :: cutoff"
write (u, "(A)") "    end subroutine reset_helicity_selection"
write (u, "(A)") "
write (u, "(A)") "    pure function is_allowed (flv, hel, col) result (yorn)"
write (u, "(A)") "        logical :: yorn"
write (u, "(A)") "        integer, intent(in) :: flv, hel, col"
write (u, "(A)") "        yorn = hel_is_allowed(hel) .and. flv_col_is_allowed(flv,col)"
write (u, "(A)") "    end function is_allowed"
write (u, "(A)") "
write (u, "(A)") "    pure function get_amplitude (flv, hel, col) result (amp_result)"
write (u, "(A)") "        complex(default) :: amp_result"
write (u, "(A)") "        integer, intent(in) :: flv, hel, col"
write (u, "(A)") "        amp_result = amp (flv, hel, col)"
write (u, "(A)") "    end function get_amplitude"
write (u, "(A)") "
write (u, "(A)") "    pure subroutine calculate_amplitudes (amp, k)"
write (u, "(A)") "        complex(default), dimension(:, :, :), intent(out) :: amp"
write (u, "(A)") "        real(default), dimension(0:3,*), intent(in) :: k"
write (u, "(A)") "        real(default) :: fac"
write (u, "(A)") "        integer :: i"
write (u, "(A)") "        ! We give all helicities the same weight!"
if (unit) then
    write (u, "(A,1x,I0,1x,A)") "    fac = ", col_fac
    write (u, "(A)") "    amp = const * sqrt(fac)"
else
    write (u, "(A,1x,I0,1x,A)") "    fac = ", factor
    write (u, "(A)") "    amp = sqrt((2 * (k(0,1)*k(0,2) &"
    write (u, "(A,1x,I0,A)") "        - dot_product (k(1:,1), k(1:,2)))) ** (3-, &"
    write (u, "(A,1x,I0,A)") "        prc_conf%n_out, ")) * sqrt(const * fac)"
end if
write (u, "(A,1x,I0,A)") "    amp = amp / sqrt(", hel_out, "._default)"
write (u, "(A)") "end subroutine calculate_amplitudes"

```

```

write (u, "(A)") "
write (u, "(A)") "end module tpr_" // char(prc_conf%id)
close (u, iostat=status)
deallocate (sxxx)
contains
function s_conv (num) result (chrt)
  integer, intent(in) :: num
  character(len=10) :: chrt
  write (chrt, "(I10)") num
  chrt = trim(adjustl(chrt))
  if (num < 10) then
    chrt = "s000" // chrt
  else if (num < 100) then
    chrt = "s00" // chrt
  else if (num < 1000) then
    chrt = "s0" // chrt
  else
    chrt = "s" // chrt
  end if
end function s_conv
function converter (flv) result (str)
  integer, dimension(:), intent(in) :: flv
  type(string_t) :: str
  character(len=150), dimension(size(flv)) :: chrt
  integer :: i
  str = ""
  do i = 1, size(flv) - 1
    write (chrt(i), "(I10)") flv(i)
    str = str // var_str(trim(adjustl(chrt(i)))) // ", "
  end do
  write (chrt(size(flv)), "(I10)") flv(size(flv))
  str = str // trim(adjustl(chrt(size(flv))))
end function converter
integer function sj (j,m)
  integer, intent(in) :: j, m
  if (((j == 1) .and. (m == 1)) .or. &
    ((j == 2) .and. (m == 2)) .or. &
    ((j == 3) .and. (m == 3)) .or. &
    ((j == 4) .and. (m == 3)) .or. &
    ((j == 5) .and. (m == 4))) then
    sj = 1
  else if (((j == 2) .and. (m == 1)) .or. &
    ((j == 3) .and. (m == 1)) .or. &
    ((j == 4) .and. (m == 2)) .or. &
    ((j == 5) .and. (m == 2))) then
    sj = -1
  else if (((j == 3) .and. (m == 2)) .or. &
    ((j == 5) .and. (m == 3))) then
    sj = 0
  else if (((j == 4) .and. (m == 1)) .or. &
    ((j == 5) .and. (m == 1))) then
    sj = -2
  else if (((j == 4) .and. (m == 4)) .or. &
    ((j == 5) .and. (m == 5))) then

```

```

        sj = 2
    else
        call msg_fatal ("Write_unit_matrix_element: Wrong spin type")
    end if
end function sj
recursive subroutine create_spin_table (index, nhel, fac, mult, inta)
    integer, intent(inout) :: index, fac
    integer, intent(in) :: nhel
    integer, dimension(:), intent(in) :: mult
    integer, dimension(nhel,size(mult)), intent(out) :: inta
    integer :: i, j
    if (index > size(mult)) return
    fac = fac / mult(index)
    do j = 1, nhel
        inta(j,index) = sj (mult(index),mod(((j-1)/fac),mult(index))+1)
    end do
    index = index + 1
    call create_spin_table (index, nhel, fac, mult, inta)
end subroutine create_spin_table
function dummy_colorizer (flv) result (str)
    type(flavor_t), dimension(:), intent(in) :: flv
    type(string_t) :: str
    integer :: i, k
    str = ""
    k = 0
    do i = 1, size(flz)
        k = k + 1
        select case (flavor_get_color_type (flv(i)))
            case (1,-1)
                str = str // "0,0, "
            case (3)
                str = str // int2string(k) // ",0, "
            case (-3)
                str = str // "0," // int2string(-k) // ", "
            case (8)
                str = str // int2string(k) // "," // int2string(-k-1) // ", "
                k = k + 1
            case default
                call msg_error ("Color type not supported.")
        end select
    end do
    str = adjustl(trim(str))
end function dummy_colorizer
end subroutine write_unit_matrix_element

```

13.1.8 Interface file for the generated modules

```

<Process libraries: public>+≡
    public :: process_library_write_driver

<Process libraries: procedures>+≡
    subroutine process_library_write_driver (prc_lib)

```

```

type(process_library_t), intent(inout) :: prc_lib
type(string_t) :: filename, prefix
type(string_t), dimension(:), allocatable :: prc_id, mod_prc_id, model
type(string_t), dimension(:), allocatable :: restrictions, omega_flags
integer, dimension(:), allocatable :: n_par
character(32), dimension(:), allocatable :: md5sum
type(process_configuration_t), pointer :: current
integer :: u, i, n_prc

call msg_message ("Writing interface code for process library '" // &
    char (process_library_get_name (prc_lib)) // "'")
prefix = prc_lib%basename // "_"

n_prc = prc_lib%n_prc
allocate (prc_id (n_prc), mod_prc_id (n_prc), model (n_prc))
allocate (restrictions (n_prc), omega_flags (n_prc))
allocate (n_par (n_prc), md5sum (n_prc))
current => prc_lib%prc_first
do i = 1, n_prc
    prc_id(i) = current%id
    mod_prc_id(i) = process_library_get_module_name (current%id,current%method)
    model(i) = model_get_name (current%model)
    restrictions(i) = current%restrictions
    omega_flags(i) = current%omega_flags
    n_par(i) = model_get_n_parameters (current%model)
    md5sum(i) = current%md5sum
    current => current%next
end do
filename = prc_lib%basename // "_interface.f90"
u = free_unit ()
open (unit=u, file=char(prc_lib%basename // ".f90"), action="write")
write (u, "(A)")  "!! WHIZARD process interface"
write (u, "(A)")  "!!"
write (u, "(A)")  "!! Automatically generated file, do not edit"
call write_get_n_processes_fun ()
call write_get_process_id_fun ()
call write_get_model_name_fun ()
call write_get_restrictions_fun ()
call write_get_omega_flags_fun ()
call write_get_openmp_status_fun ()
call write_get_md5sum_fun ()
call write_string_to_array_fun ()
call write_get_int_fun ("n_in", "number_particles_in")
call write_get_int_fun ("n_out", "number_particles_out")
call write_get_int_fun ("n_flv", "number_flavor_states")
call write_get_int_fun ("n_hel", "number_spin_states")
call write_get_int_fun ("n_col", "number_color_flows")
call write_get_int_fun ("n_cin", "number_color_indices")
call write_get_int_fun ("n_cf", "number_color_factors")
call write_set_int_sub1 ("flv_state", "flavor_states")
call write_set_int_sub1 ("hel_state", "spin_states")
call write_set_int_sub2 ("col_state", "color_flows", "ghost_flag")
call write_set_cf_tab_sub ()
call write_init_get_fptr ()

```



```

call write_final_get_fptr ()
call write_update_alpha_s_get_fptr ()
call write_reset_helicity_selection_get_fptr ()
call write_new_event_get_fptr ()
call write_is_allowed_get_fptr ()
call write_get_amplitude_get_fptr ()
close (u)

```

```

prc_lib%status = max (prc_lib%status, STAT_CODE_GENERATED)

```

contains

```

function logical_to_string (flag) result (str)
logical, intent(in) :: flag
type(string_t) :: str
  if (flag) then
    str = ".true."
  else
    str = ".false."
  end if
end function logical_to_string

```

```

subroutine write_get_n_processes_fun ()
  write (u, "(A)") ""
  write (u, "(A)") "! Return the number of processes in this library"
  write (u, "(A)") "function " // char (prefix) &
    // "get_n_processes () result (n) bind(C)"
  write (u, "(A)") " use iso_c_binding"
  write (u, "(A)") " integer(c_int) :: n"
  write (u, "(A,I0)") " n = ", n_prc
  write (u, "(A)") "end function " // char (prefix) &
    // "get_n_processes"
end subroutine write_get_n_processes_fun

```

```

subroutine write_get_process_id_fun ()
  write (u, "(A)") ""
  write (u, "(A)") "! Return the process ID of process #i (as a C pointer to a character array)"
  write (u, "(A)") "subroutine " // char (prefix) &
    // "get_process_id (i, cptr, len) bind(C)"
  write (u, "(A)") " use iso_c_binding"
  write (u, "(A)") " integer(c_int), intent(in) :: i"
  write (u, "(A)") " type(c_ptr), intent(inout) :: cptr"
  write (u, "(A)") " integer(c_int), intent(out) :: len"
  write (u, "(A)") " character(kind=c_char), dimension(:), allocatable, target, save :: a"
  call write_string_to_array_interface ()
  write (u, "(A)") " select case (i)"
  write (u, "(A)") " case (0); if (allocated (a)) deallocate (a)"
  do i = 1, n_prc
    write (u, "(A,I0,A)") " case (" , i, "); " &
      // "call " // char (prefix) &
      // "string_to_array (' " // char (prc_id(i)) // "', a)"
  end do
  write (u, "(A)") " end select"
  write (u, "(A)") " if (allocated (a)) then"

```

```

write (u, "(A)") "      cptr = c_loc (a)"
write (u, "(A)") "      len = size (a)"
write (u, "(A)") "    else"
write (u, "(A)") "      cptr = c_null_ptr"
write (u, "(A)") "      len = 0"
write (u, "(A)") "    end if"
write (u, "(A)") "end subroutine " // char (prefix) &
// "get_process_id"
end subroutine write_get_process_id_fun

subroutine write_get_model_name_fun ()
write (u, "(A)") ""
write (u, "(A)") "! Return the model name for process #i (as a C pointer to a character array)"
write (u, "(A)") "subroutine " // char (prefix) &
// "get_model_name (i, cptr, len) bind(C)"
write (u, "(A)") "  use iso_c_binding"
write (u, "(A)") "  integer(c_int), intent(in) :: i"
write (u, "(A)") "  type(c_ptr), intent(inout) :: cptr"
write (u, "(A)") "  integer(c_int), intent(out) :: len"
write (u, "(A)") "  character(kind=c_char), dimension(:), allocatable, target, save :: a"
call write_string_to_array_interface ()
write (u, "(A)") "  select case (i)"
write (u, "(A)") "    case (0); if (allocated (a)) deallocate (a)"
do i = 1, n_prc
  write (u, "(A,IO,A)") "    case (" , i, ")"; " &
// "call " // char (prefix) &
// "string_to_array ('" // char (model(i)) // "', a)"
end do
write (u, "(A)") "  end select"
write (u, "(A)") "  if (allocated (a)) then"
write (u, "(A)") "    cptr = c_loc (a)"
write (u, "(A)") "    len = size (a)"
write (u, "(A)") "  else"
write (u, "(A)") "    cptr = c_null_ptr"
write (u, "(A)") "    len = 0"
write (u, "(A)") "  end if"
write (u, "(A)") "end subroutine " // char (prefix) &
// "get_model_name"
end subroutine write_get_model_name_fun

subroutine write_get_restrictions_fun ()
write (u, "(A)") ""
write (u, "(A)") "! Return the restriction string process #i (as a C pointer to a character array)"
write (u, "(A)") "subroutine " // char (prefix) &
// "get_restrictions (i, cptr, len) bind(C)"
write (u, "(A)") "  use iso_c_binding"
write (u, "(A)") "  integer(c_int), intent(in) :: i"
write (u, "(A)") "  type(c_ptr), intent(inout) :: cptr"
write (u, "(A)") "  integer(c_int), intent(out) :: len"
write (u, "(A)") "  character(kind=c_char), dimension(:), allocatable, target, save :: a"
call write_string_to_array_interface ()
write (u, "(A)") "  select case (i)"
write (u, "(A)") "    case (0); if (allocated (a)) deallocate (a)"
do i = 1, n_prc

```

```

        write (u, "(A,IO,A)") " case (" , i, " ); " &
        // "call " // char (prefix) &
        // "string_to_array ('" // char (restrictions(i)) // "'", a)"
    end do
    write (u, "(A)") " end select"
    write (u, "(A)") " if (allocated (a)) then"
    write (u, "(A)") "     cptr = c_loc (a)"
    write (u, "(A)") "     len = size (a)"
    write (u, "(A)") " else"
    write (u, "(A)") "     cptr = c_null_ptr"
    write (u, "(A)") "     len = 0"
    write (u, "(A)") " end if"
    write (u, "(A)") "end subroutine " // char (prefix) &
    // "get_restrictions"
end subroutine write_get_restrictions_fun

subroutine write_get_omega_flags_fun ()
    write (u, "(A)") ""
    write (u, "(A)") "! Return the omega flags for process #i (as a C pointer to a character array)"
    write (u, "(A)") "subroutine " // char (prefix) &
    // "get_omega_flags (i, cptr, len) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    write (u, "(A)") " integer(c_int), intent(in) :: i"
    write (u, "(A)") " type(c_ptr), intent(inout) :: cptr"
    write (u, "(A)") " integer(c_int), intent(out) :: len"
    write (u, "(A)") " character(kind=c_char), dimension(:), allocatable, target, save :: a"
    call write_string_to_array_interface ()
    write (u, "(A)") " select case (i)"
    write (u, "(A)") " case (0); if (allocated (a)) deallocate (a)"
    do i = 1, n_prc
        write (u, "(A,IO,A)") " case (" , i, " ); " &
        // "call " // char (prefix) &
        // "string_to_array ('" // char (omega_flags(i)) // "'", a)"
    end do
    write (u, "(A)") " end select"
    write (u, "(A)") " if (allocated (a)) then"
    write (u, "(A)") "     cptr = c_loc (a)"
    write (u, "(A)") "     len = size (a)"
    write (u, "(A)") " else"
    write (u, "(A)") "     cptr = c_null_ptr"
    write (u, "(A)") "     len = 0"
    write (u, "(A)") " end if"
    write (u, "(A)") "end subroutine " // char (prefix) &
    // "get_omega_flags"
end subroutine write_get_omega_flags_fun

subroutine write_get_openmp_status_fun ()
    write (u, "(A)") ""
    write (u, "(A)") "! Return the OpenMP support status"
    write (u, "(A)") "function " // char (prefix) &
    // "get_openmp_status (i) result (openmp_status) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    call write_use_lines ("openmp_supported", "openmp_supported")
    write (u, "(A)") " integer(c_int), intent(in) :: i"

```

```

write (u, "(A)") " logical(c_bool) :: openmp_status"
write (u, "(A)") " select case (i)"
do i = 1, n_prc
    write (u, "(A,IO,A)") " case (" , i, "); " &
        // "openmp_status = " // char (prc_id(i)) // "_openmp_supported ()"
end do
write (u, "(A)") " end select"
write (u, "(A)") "end function " // char (prefix) &
    // "get_openmp_status"
end subroutine write_get_openmp_status_fun

subroutine write_get_md5sum_fun ()
integer :: i
write (u, "(A)") ""
write (u, "(A)") "! Return the MD5 sum for the process configuration (as a C pointer to a c
write (u, "(A)") "subroutine " // char (prefix) &
    // "get_md5sum (i, cptr, len) bind(C)"
write (u, "(A)") " use iso_c_binding"
call write_use_lines ("md5sum", "md5sum")
write (u, "(A)") " integer(c_int), intent(in) :: i"
write (u, "(A)") " type(c_ptr), intent(inout) :: cptr"
write (u, "(A)") " integer(c_int), intent(out) :: len"
write (u, "(A)") " character(kind=c_char), dimension(:), allocatable, target, save :: a"
call write_string_to_array_interface ()
write (u, "(A)") " select case (i)"
write (u, "(A)") " case (0); if (allocated (a)) deallocate (a)"
do i = 1, n_prc
    write (u, "(A,IO,A)") " case (" , i, "); " &
        // "call " // char (prefix) &
        // "string_to_array (" // char (prc_id(i)) &
        // "_md5sum (), a)"
end do
write (u, "(A)") " end select"
write (u, "(A)") " if (allocated (a)) then"
write (u, "(A)") "     cptr = c_loc (a)"
write (u, "(A)") "     len = size (a)"
write (u, "(A)") " else"
write (u, "(A)") "     cptr = c_null_ptr"
write (u, "(A)") "     len = 0"
write (u, "(A)") " end if"
write (u, "(A)") "end subroutine " // char (prefix) &
    // "get_md5sum"
end subroutine write_get_md5sum_fun

subroutine write_string_to_array_interface ()
write (u, "(2x,A)") "interface"
write (u, "(5x,A)") "subroutine " // char (prefix) &
    // "string_to_array (string, a)"
write (u, "(5x,A)") " use iso_c_binding"
write (u, "(5x,A)") " character(*), intent(in) :: string"
write (u, "(5x,A)") " character(kind=c_char), dimension(:), allocatable, intent(out) :: a"
write (u, "(5x,A)") "end subroutine " // char (prefix) &
    // "string_to_array"
write (u, "(2x,A)") "end interface"

```

```

end subroutine write_string_to_array_interface

subroutine write_string_to_array_fun ()
  write (u, "(A)") ""
  write (u, "(A)") "! Auxiliary: convert character string to array pointer"
  write (u, "(A)") "subroutine " // char (prefix) &
    // "string_to_array (string, a)"
  write (u, "(A)") "  use iso_c_binding"
  write (u, "(A)") "  character(*), intent(in) :: string"
  write (u, "(A)") "  character(kind=c_char), dimension(:), allocatable, intent(out) :: a"
  write (u, "(A)") "  integer :: i"
  write (u, "(A)") "  allocate (a (len (string)))"
  write (u, "(A)") "  do i = 1, size (a)"
  write (u, "(A)") "    a(i) = string(i:i)"
  write (u, "(A)") "  end do"
  write (u, "(A)") "end subroutine " // char (prefix) &
    // "string_to_array"
end subroutine write_string_to_array_fun

subroutine write_get_int_fun (vname, fname)
  character(*), intent(in) :: vname, fname
  write (u, "(A)") ""
  write (u, "(A)") "! Return the value of " // vname
  write (u, "(A)") "function " // char (prefix) &
    // "get_" // vname // " (pid)" &
    // " result (" // vname // ") bind(C)"
  write (u, "(A)") "  use iso_c_binding"
  call write_use_lines (vname, fname)
  write (u, "(A)") "  integer(c_int), intent(in) :: pid"
  write (u, "(A)") "  integer(c_int) :: " // vname
  call write_case_lines (vname // " = ", "_" // vname // " ()")
  write (u, "(A)") "end function " // char (prefix) &
    // "get_" // vname
end subroutine write_get_int_fun

subroutine write_set_int_sub1 (vname, fname)
  character(*), intent(in) :: vname, fname
  write (u, "(A)") ""
  write (u, "(A)") "! Set table: " // vname
  write (u, "(A)") "subroutine " // char (prefix) &
    // "set_" // vname &
    // " (pid, cptr, shape) bind(C)"
  write (u, "(A)") "  use iso_c_binding"
  call write_use_lines (vname, fname)
  write (u, "(A)") "  integer(c_int), intent(in) :: pid"
  write (u, "(A)") "  type(c_ptr), intent(in) :: cptr"
  write (u, "(A)") "  integer(c_int), dimension(2), intent(in) :: shape"
  write (u, "(A)") "  integer(c_int), dimension(:,:), pointer :: " // vname
  if (kind(1) /= c_int) then
    write (u, "(A)") "  integer, dimension(:,:), allocatable :: " &
      // vname // "_tmp"
  end if
  write (u, "(A)") "  call c_f_pointer (cptr, " // vname // ", shape)"
  if (kind(1) == c_int) then

```

```

        call write_case_lines ("call ", "_" // vname // " (" // vname // ")")
    else
        write (u, "(A)") " allocate (" &
            // vname // "_tmp (shape(1), shape(2)))"
        call write_case_lines ("call ", &
            "_" // vname // " (" // vname // "_tmp)")
        write (u, "(A)") " " // vname // " = " // vname // "_tmp"
    end if
    write (u, "(A)") "end subroutine " // char (prefix) &
        // "set_" // vname
end subroutine write_set_int_sub1

subroutine write_set_int_sub2 (vname, fname, lname)
    character(*), intent(in) :: vname, fname, lname
    write (u, "(A)") ""
    write (u, "(A)") "! Set tables: " // vname // ", " // lname
    write (u, "(A)") "subroutine " // char (prefix) &
        // "set_" // vname &
        // " (pid, cptr, shape, lcptr, lshape) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    call write_use_lines (vname, fname)
    write (u, "(A)") " integer(c_int), intent(in) :: pid"
    write (u, "(A)") " type(c_ptr), intent(in) :: cptr"
    write (u, "(A)") " integer(c_int), dimension(3), intent(in) :: shape"
    write (u, "(A)") " type(c_ptr), intent(in) :: lcptr"
    write (u, "(A)") " integer(c_int), dimension(2), intent(in) :: lshape"
    write (u, "(A)") " integer(c_int), dimension(:,:), pointer :: " &
        // vname
    write (u, "(A)") " logical(c_bool), dimension(:,:), pointer :: " &
        // lname
    if (kind(1) /= c_int) then
        write (u, "(A)") " integer, dimension(:,:), allocatable :: " &
            // vname // "_tmp"
    end if
    if (kind(.true.) /= c_bool) then
        write (u, "(A)") " logical, dimension(:,:), allocatable :: " &
            // lname // "_tmp"
    end if
    write (u, "(A)") " call c_f_pointer (cptr, " // vname // ", shape)"
    write (u, "(A)") " call c_f_pointer (lcptr, " // lname // ", lshape)"
    if (kind(1) /= c_int) then
        write (u, "(A)") " allocate (" &
            // vname // "_tmp (shape(1), shape(2), shape(3)))"
    end if
    if (kind(.true.) /= c_bool) then
        write (u, "(A)") " allocate (" &
            // lname // "_tmp (lshape(1), lshape(2)))"
    end if
    if (kind(1) == c_int) then
        if (kind(.true.) == c_bool) then
            call write_case_lines ("call ", &
                "_" // vname // " (" // vname // ", " // lname // ")")
        else
            call write_case_lines ("call ", &

```

```

        "_" // vname // " (" // vname // ", " // lname // "_tmp")
write (u, "(A)") " " // lname // " = " // lname // "_tmp"
end if
else
if (kind(.true.) == c_bool) then
call write_case_lines ("call ", &
    "_" // vname // " (" // vname // "_tmp, " // lname // ")")
else
call write_case_lines ("call ", &
    "_" // vname // " (" // vname // "_tmp, " // lname // "_tmp)")
write (u, "(A)") " " // lname // " = " // lname // "_tmp"
end if
write (u, "(A)") " " // vname // " = " // vname // "_tmp"
end if
write (u, "(A)") "end subroutine " // char (prefix) &
    // "set_" // vname
end subroutine write_set_int_sub2

subroutine write_set_cf_tab_sub ()
write (u, "(A)") ""
write (u, "(A)") "subroutine " // char (prefix) &
    // "set_cf_table (pid, iptr1, iptr2, cptr, shape) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " use kinds"
write (u, "(A)") " use omega_color"
call write_use_lines ("color_factors", "color_factors")
write (u, "(A)") " integer(c_int), intent(in) :: pid"
write (u, "(A)") " type(c_ptr), intent(in) :: iptr1, iptr2, cptr"
write (u, "(A)") " integer(c_int), dimension(1), intent(in) :: shape"
write (u, "(A)") " integer(c_int), dimension(:), pointer :: " &
    // "cf_index1, cf_index2"
write (u, "(A)") " complex(c_default_complex), dimension(:), " &
    // "pointer :: col_factor"
write (u, "(A)") " type(omega_color_factor), dimension(:), " &
    // "allocatable :: cf"
write (u, "(A)") " call c_f_pointer (iptr1, cf_index1, shape)"
write (u, "(A)") " call c_f_pointer (iptr2, cf_index2, shape)"
write (u, "(A)") " call c_f_pointer (cptr, col_factor, shape)"
write (u, "(A)") " allocate (cf (shape(1)))"
call write_case_lines ("call ", "_color_factors (cf)")
write (u, "(A)") " cf_index1 = cf%i1"
write (u, "(A)") " cf_index2 = cf%i2"
write (u, "(A)") " col_factor = cf%factor"
write (u, "(A)") "end subroutine " // char (prefix) // "set_cf_table"
end subroutine write_set_cf_tab_sub

subroutine write_init_get_fptr ()
write (u, "(A)") ""
write (u, "(A)") "! Return pointer to function: 'init'"
write (u, "(A)") "subroutine " // char (prefix) &
    // "init_get_fptr (pid, fptr) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " integer(c_int), intent(in) :: pid"
write (u, "(A)") " type(c_funptr), intent(out) :: fptr"

```

```

write (u, "(A)") " abstract interface"
write (u, "(A)") "      subroutine prc_init (par) bind(C)"
write (u, "(A)") "          use iso_c_binding"
write (u, "(A)") "          use kinds"
write (u, "(A)") "          real(c_default_float), dimension(*), " &
// "intent(in) :: par"
write (u, "(A)") "      end subroutine prc_init"
write (u, "(A)") " end interface"
do i = 1, n_prc
    write (u, "(2x,A)") "procedure(prc_init), bind(C) :: " &
// char (prc_id(i)) // "_init"
end do
call write_case_lines ("fptr = c_funloc (", "_init)")
write (u, "(A)") "end subroutine " // char (prefix) &
// "init_get_fptr"
do i = 1, n_prc
    write (u, *)
    write (u, "(A)") "subroutine " // char (prc_id(i)) &
// "_init (par) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    write (u, "(A)") " use kinds"
    write (u, "(A)") " use " // char (mod_prc_id(i))
    write (u, "(A)") " real(c_default_float), dimension(*), " &
// "intent(in) :: par"
    if (c_default_float == default) then
        write (u, "(A)") " call init (par)"
    else
        write (u, "(A, I0)") " integer, parameter :: n_par = ", n_par(i)
        write (u, "(A)") " real(default), dimension(n_par) :: fpar"
        write (u, "(A)") " fpar = par"
        write (u, "(A)") " call init (fpar)"
    end if
    write (u, "(A)") "end subroutine " // char (prc_id(i)) // "_init"
end do
end subroutine write_init_get_fptr

subroutine write_final_get_fptr ()
    write (u, "(A)") ""
    write (u, "(A)") "! Return pointer to function: 'final'"
    write (u, "(A)") "subroutine " // char (prefix) &
// "final_get_fptr (pid, fptr) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    write (u, "(A)") " integer(c_int), intent(in) :: pid"
    write (u, "(A)") " type(c_funptr), intent(out) :: fptr"
    write (u, "(A)") " abstract interface"
    write (u, "(A)") "      subroutine prc_final () bind(C)"
    write (u, "(A)") "      end subroutine prc_final"
    write (u, "(A)") " end interface"
    do i = 1, n_prc
        write (u, "(2x,A)") "procedure(prc_final), bind(C) :: " &
// char (prc_id(i)) // "_final"
    end do
    call write_case_lines ("fptr = c_funloc (", "_final)")
    write (u, "(A)") "end subroutine " // char (prefix) &

```



```

        // "final_get_fptr"
do i = 1, n_prc
    write (u, *)
    write (u, "(A)") "subroutine " // char (prc_id(i)) &
        // "_final () bind(C)"
    write (u, "(A)") " use " // char (mod_prc_id(i))
    write (u, "(A)") " call final ()"
    write (u, "(A)") "end subroutine " // char (prc_id(i)) // "_final"
end do
end subroutine write_final_get_fptr

subroutine write_update_alpha_s_get_fptr ()
    write (u, "(A)") ""
    write (u, "(A)") "! Return pointer to function: 'update_alpha_s'"
    write (u, "(A)") "subroutine " // char (prefix) &
        // "update_alpha_s_get_fptr (pid, fptr) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    write (u, "(A)") " integer(c_int), intent(in) :: pid"
    write (u, "(A)") " type(c_funptr), intent(out) :: fptr"
    write (u, "(A)") " abstract interface"
    write (u, "(A)") "     subroutine prc_update_alpha_s (alpha_s) bind(C)"
    write (u, "(A)") "         use iso_c_binding"
    write (u, "(A)") "         use kinds"
    write (u, "(A)") "         real(c_default_float), " &
        // "intent(in) :: alpha_s"
    write (u, "(A)") "     end subroutine prc_update_alpha_s"
    write (u, "(A)") " end interface"
do i = 1, n_prc
    write (u, "(2x,A)") "procedure(prc_update_alpha_s), bind(C) :: " &
        // char (prc_id(i)) // "_update_alpha_s"
end do
call write_case_lines ("fptr = c_funloc (", "_update_alpha_s")
write (u, "(A)") "end subroutine " // char (prefix) &
    // "update_alpha_s_get_fptr"
do i = 1, n_prc
    write (u, *)
    write (u, "(A)") "subroutine " // char (prc_id(i)) &
        // "_update_alpha_s (alpha_s) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    write (u, "(A)") " use kinds"
    write (u, "(A)") " use " // char (mod_prc_id(i))
    write (u, "(A)") " real(c_default_float), " &
        // "intent(in) :: alpha_s"
    if (c_default_float == default) then
        write (u, "(A)") " call update_alpha_s (alpha_s)"
    else
        write (u, "(A)") " call update_alpha_s " &
            // "(real (alpha_s, c_default_float))"
    end if
    write (u, "(A)") "end subroutine " // char (prc_id(i)) &
        // "_update_alpha_s"
end do
end subroutine write_update_alpha_s_get_fptr

```

```

subroutine write_reset_helicity_selection_get_fptr ()
  write (u, "(A)") ""
  write (u, "(A)") "! Return pointer to function: " &
    // "'reset_helicity_selection'"
  write (u, "(A)") "subroutine " // char (prefix) &
    // "reset_helicity_selection_get_fptr (pid, fptr) bind(C)"
  write (u, "(A)") "  use iso_c_binding"
  write (u, "(A)") "  integer(c_int), intent(in) :: pid"
  write (u, "(A)") "  type(c_funptr), intent(out) :: fptr"
  write (u, "(A)") "  abstract interface"
  write (u, "(A)") "    subroutine " &
    // "prc_reset_helicity_selection (threshold, cutoff) bind(C)"
  write (u, "(A)") "      use iso_c_binding"
  write (u, "(A)") "      use kinds"
  write (u, "(A)") "      real(c_default_float), " &
    // "intent(in) :: threshold"
  write (u, "(A)") "      integer(c_int), " &
    // "intent(in) :: cutoff"
  write (u, "(A)") "    end subroutine prc_reset_helicity_selection"
  write (u, "(A)") "  end interface"
do i = 1, n_prc
  write (u, "(2x,A)") "procedure(prc_reset_helicity_selection), " &
    // "bind(C) :: " &
    // char (prc_id(i)) // "_reset_helicity_selection"
end do
call write_case_lines ("fptr = c_funloc (", "_reset_helicity_selection)")
write (u, "(A)") "end subroutine " // char (prefix) &
  // "reset_helicity_selection_get_fptr"
do i = 1, n_prc
  write (u, *)
  write (u, "(A)") "subroutine " // char (prc_id(i)) &
    // "_reset_helicity_selection (threshold, cutoff) bind(C)"
  write (u, "(A)") "  use iso_c_binding"
  write (u, "(A)") "  use kinds"
  write (u, "(A)") "  use " // char (mod_prc_id(i))
  write (u, "(A)") "  real(c_default_float), " &
    // "intent(in) :: threshold"
  write (u, "(A)") "  integer(c_int), " &
    // "intent(in) :: cutoff"
  write (u, "(A)") "  real(default) :: rthreshold"
  write (u, "(A)") "  integer :: icutoff"
  write (u, "(A)") "  rthreshold = threshold"
  write (u, "(A)") "  icutoff = cutoff"
  write (u, "(A)") "  call reset_helicity_selection " &
    // "(rthreshold, icutoff)"
  write (u, "(A)") "end subroutine " // char (prc_id(i)) &
    // "_reset_helicity_selection"
end do
end subroutine write_reset_helicity_selection_get_fptr

subroutine write_new_event_get_fptr ()
  write (u, "(A)") ""
  write (u, "(A)") "! Return pointer to function: 'new_event'"
  write (u, "(A)") "subroutine " // char (prefix) &

```

```

        // "new_event_get_fptr (pid, fptr) bind(C)"
write (u, "(A)") " use iso_c_binding"
write (u, "(A)") " integer(c_int), intent(in) :: pid"
write (u, "(A)") " type(c_funptr), intent(out) :: fptr"
write (u, "(A)") " abstract interface"
write (u, "(A)") "     subroutine prc_new_event (p) bind(C)"
write (u, "(A)") "         use iso_c_binding"
write (u, "(A)") "         use kinds"
write (u, "(A)") "         real(c_default_float), dimension(0:3,*), " &
        // "intent(in) :: p"
write (u, "(A)") "     end subroutine prc_new_event"
write (u, "(A)") " end interface"
do i = 1, n_prc
    write (u, "(2x,A)") "procedure(prc_new_event), bind(C) :: " &
        // char (prc_id(i)) // "_new_event"
end do
call write_case_lines ("fptr = c_funloc (", "_new_event")
write (u, "(A)") "end subroutine " // char (prefix) &
    // "new_event_get_fptr"
do i = 1, n_prc
    write (u, *)
    write (u, "(A)") "subroutine " // char (prc_id(i)) &
        // "_new_event (p) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    write (u, "(A)") " use kinds"
    write (u, "(A)") " use " // char (mod_prc_id(i))
    write (u, "(A)") " real(c_default_float), dimension(0:3,*), " &
        // "intent(in) :: p"
    if (c_default_float == default) then
        write (u, "(A)") " call new_event (p)"
    else
        write (u, "(A)") " integer :: n_tot"
        write (u, "(A)") " real(default), dimension(:,:), " &
            // "allocatable :: k"
        write (u, "(A)") " n_tot = " &
            // "number_particles_in () + number_particles_out ()"
        write (u, "(A)") " allocate (k (0:3,n_tot))"
        write (u, "(A)") " k = p"
        write (u, "(A)") " call new_event (k)"
    end if
    write (u, "(A)") "end subroutine " // char (prc_id(i)) // "_new_event"
end do
end subroutine write_new_event_get_fptr

subroutine write_is_allowed_get_fptr ()
    write (u, "(A)") ""
    write (u, "(A)") "! Return pointer to function: 'is_allowed'"
    write (u, "(A)") "subroutine " // char (prefix) &
        // "is_allowed_get_fptr (pid, fptr) bind(C)"
    write (u, "(A)") " use iso_c_binding"
    write (u, "(A)") " integer(c_int), intent(in) :: pid"
    write (u, "(A)") " type(c_funptr), intent(out) :: fptr"
    write (u, "(A)") " abstract interface"
    write (u, "(A)") "     function " &

```

```

        // "prc_is_allowed (flv, hel, col) result (flag) bind(C)"
write (u, "(A)") "      use iso_c_binding"
write (u, "(A)") "      use kinds"
write (u, "(A)") "      logical(c_bool) :: flag"
write (u, "(A)") "      integer(c_int), intent(in) :: flv, hel, col"
write (u, "(A)") "      end function prc_is_allowed"
write (u, "(A)") "  end interface"
do i = 1, n_prc
    write (u, "(2x,A)") "procedure(prc_is_allowed), bind(C) :: " &
        // char (prc_id(i)) // "_is_allowed"
end do
call write_case_lines ("fptr = c_funloc (" , "_is_allowed)")
write (u, "(A)") "end subroutine " // char (prefix) &
    // "is_allowed_get_fptr"
do i = 1, n_prc
    write (u, *)
    write (u, "(A)") "function " // char (prc_id(i)) &
        // "_is_allowed (flv, hel, col) result (flag) bind(C)"
    write (u, "(A)") "  use iso_c_binding"
    write (u, "(A)") "  use kinds"
    write (u, "(A)") "  use " // char (mod_prc_id(i))
    write (u, "(A)") "  logical(c_bool) :: flag"
    write (u, "(A)") "  integer(c_int), intent(in) :: flv, hel, col"
    if (c_int == kind(1)) then
        write (u, "(A)") "    flag = is_allowed (flv, hel, col)"
    else
        write (u, "(A)") "    integer :: iflv, ihel, icol"
        write (u, "(A)") "    iflv = flv; ihel = hel; icol = col"
        write (u, "(A)") "    flag = is_allowed (iflv, ihel, icol)"
    end if
    write (u, "(A)") "end function " // char (prc_id(i)) &
        // "_is_allowed"
end do
end subroutine write_is_allowed_get_fptr

subroutine write_get_amplitude_get_fptr ()
    write (u, "(A)") ""
    write (u, "(A)") "! Return pointer to function: 'get_amplitude'"
    write (u, "(A)") "subroutine " // char (prefix) &
        // "get_amplitude_get_fptr (pid, fptr) " &
        // "bind(C)"
    write (u, "(A)") "  use iso_c_binding"
    write (u, "(A)") "  integer(c_int), intent(in) :: pid"
    write (u, "(A)") "  type(c_funptr), intent(out) :: fptr"
    write (u, "(A)") "  abstract interface"
    write (u, "(A)") "    function " &
        // "prc_get_amplitude (flv, hel, col) result (amp) bind(C)"
    write (u, "(A)") "      use iso_c_binding"
    write (u, "(A)") "      use kinds"
    write (u, "(A)") "      complex(c_default_complex) :: amp"
    write (u, "(A)") "      integer(c_int), intent(in) :: flv, hel, col"
    write (u, "(A)") "      end function prc_get_amplitude"
    write (u, "(A)") "  end interface"
do i = 1, n_prc

```

```

        write (u, "(2x,A)") "procedure(prc_get_amplitude), bind(C) :: " &
            // char (prc_id(i)) // "_get_amplitude"
    end do
    call write_case_lines ("fptr = c_funloc (", "_get_amplitude)")
    write (u, "(A)") "end subroutine " // char (prefix) &
        // "get_amplitude_get_fptr"
    do i = 1, n_prc
        write (u, *)
        write (u, "(A)") "function " // char (prc_id(i)) &
            // "_get_amplitude (flv, hel, col) result (amp) bind(C)"
        write (u, "(A)") " use iso_c_binding"
        write (u, "(A)") " use kinds"
        write (u, "(A)") " use " // char (mod_prc_id(i))
        write (u, "(A)") " complex(c_default_complex) :: amp"
        write (u, "(A)") " integer(c_int), intent(in) :: flv, hel, col"
        if (c_int == kind(1)) then
            write (u, "(A)") " amp = get_amplitude (flv, hel, col)"
        else
            write (u, "(A)") " integer :: iflv, ihel, icol"
            write (u, "(A)") " iflv = flv; ihel = hel; icol = col"
            write (u, "(A)") " amp = get_amplitude (iflv, ihel, icol)"
        end if
        write (u, "(A)") "end function " // char (prc_id(i)) &
            // "_get_amplitude"
    end do
end subroutine write_get_amplitude_get_fptr

subroutine write_use_lines (vname, fname)
    character(*), intent(in) :: vname, fname
    integer :: i
    do i = 1, n_prc
        write (u, "(2x,A)") "use " // char (mod_prc_id(i)) // ", only: " &
            // char (prc_id(i)) // "_" // vname // " => " // fname
    end do
end subroutine write_use_lines

subroutine write_case_lines (cmd1, cmd2)
    character(*), intent(in) :: cmd1, cmd2
    integer :: i
    write (u, "(A)") " select case (pid)"
    do i = 1, n_prc
        write (u, "(2x,A,I0,A)") "case(", i, "); " &
            // cmd1 // char (prc_id(i)) // cmd2
    end do
    write (u, "(A)") " end select"
end subroutine write_case_lines

end subroutine process_library_write_driver

```

13.1.9 User code library access

The static executable must incorporate user-defined code for various tasks. In ordinary execution, this is linked dynamically in the same way as the process code. Therefore, we include it here.

```
(Process libraries: public)+≡
    public :: user_procs_t

(Process libraries: types)+≡
    type :: user_procs_t
        type(string_t), dimension(:), allocatable :: cut
        type(string_t), dimension(:), allocatable :: event_shape
        type(string_t), dimension(:), allocatable :: obs_real_unary
        type(string_t), dimension(:), allocatable :: obs_real_binary
        type(string_t), dimension(:), allocatable :: sf
    end type user_procs_t
```

Declare the procedures with appropriate interfaces

```
(Process libraries: procedures)+≡
    subroutine write_user_code_declarations (u, user_procs)
        integer, intent(in) :: u
        type(user_procs_t), intent(in) :: user_procs
        integer :: i
        do i = 1, size (user_procs%cut)
            write (u, "(A)") " procedure(user_cut_fun), bind(C) :: " &
                // char (user_procs%cut(i))
        end do
        do i = 1, size (user_procs%event_shape)
            write (u, "(A)") " procedure(user_event_shape_fun), bind(C) :: " &
                // char (user_procs%event_shape(i))
        end do
        do i = 1, size (user_procs%obs_real_unary)
            write (u, "(A)") " procedure(user_obs_real_unary), bind(C) :: " &
                // char (user_procs%obs_real_unary(i))
        end do
        do i = 1, size (user_procs%obs_real_binary)
            write (u, "(A)") " procedure(user_obs_real_binary), bind(C) :: " &
                // char (user_procs%obs_real_binary(i))
        end do
    end subroutine write_user_code_declarations
```

Write access code for the procedures

```
(Process libraries: procedures)+≡
    subroutine write_user_code_access (u, user_procs)
        integer, intent(in) :: u
        type(user_procs_t), intent(in) :: user_procs
        write (u, "(5x,A)") "select case (fname)"
        call write_access (user_procs%cut)
        call write_access (user_procs%event_shape)
        call write_access (user_procs%obs_real_unary)
        call write_access (user_procs%obs_real_binary)
        call write_sf_access (user_procs%sf)
        write (u, "(5x,A)") "case default"
```

```

write (u, "(5x,A)") "    c_fptr = c_null_funptr"
write (u, "(5x,A)") "end select"
contains
subroutine write_access (procname)
  type(string_t), dimension(:), intent(in) :: procname
  integer :: i
  do i = 1, size (procname)
    call write_access_line (procname(i))
  end do
end subroutine write_access
subroutine write_sf_access (procname)
  type(string_t), dimension(:), intent(in) :: procname
  integer :: i
  do i = 1, size (procname)
    call write_access_line (procname(i) // "_info")
    call write_access_line (procname(i) // "_mask")
    call write_access_line (procname(i) // "_state")
    call write_access_line (procname(i) // "_kinematics")
    call write_access_line (procname(i) // "_evaluate")
  end do
end subroutine write_sf_access
subroutine write_access_line (procname)
  type(string_t), intent(in) :: procname
  write (u, "(5x,A)") "case ('" // char (procname) // "')"
  write (u, "(8x,A)") "c_fptr = c_funloc (" // char (procname) // ")"
end subroutine write_access_line
end subroutine write_user_code_access

```

13.1.10 Library manager

When static libraries are compiled, procedure pointer are not assigned by a dlopen mechanism, but must be done at program startup. Mainly for this task we write a library manager which links to the static libraries as they are defined by the user.

For each library, it has to assign all possible interface function to a C function pointer, which then is dereferenced in the same way as it is done for dlopened libraries.

```

<Process libraries: public>+≡
  public :: write_library_manager

<Process libraries: procedures>+≡
  subroutine write_library_manager (libname, user_procs)

    type(string_t), dimension(:), intent(in) :: libname
    type(user_procs_t), intent(in) :: user_procs
    integer :: u, i

    call msg_message ("Writing library manager code")
    u = free_unit ()
    open (unit=u, file="libmanager.f90", action="write", status="replace")
    write (u, "(A)")  "!! WHIZARD library manager"
    write (u, "(A)")  "!!"

```

```

write (u, "(A)")  "!! Automatically generated file, do not edit"
write (u, "(A)")  ""
write (u, "(A)")  "function libmanager_get_n_libs () result (n)"
write (u, "(A)")  "  implicit none"
write (u, "(A)")  "  integer :: n"
write (u, "(A,1x,I0)")  "  n =", size (libname)
write (u, "(A)")  "end function libmanager_get_n_libs"
write (u, "(A)")  ""
write (u, "(A)")  "function libmanager_get_libname (i) result (name)"
write (u, "(A)")  "  use iso_varying_string, string_t => varying_string"
write (u, "(A)")  "  implicit none"
write (u, "(A)")  "  type(string_t) :: name"
write (u, "(A)")  "  integer, intent(in) :: i"
write (u, "(A)")  "  select case (i)"
do i = 1, size (libname)
    call write_lib_name (i, libname(i))
end do
write (u, "(A)")  "  case default;  name = ''"
write (u, "(A)")  "  end select"
write (u, "(A)")  "end function libmanager_get_libname"
write (u, "(A)")  ""
write (u, "(A)")  "function libmanager_get_c_funptr (libname, fname) " &
    // "result (c_funptr)"
write (u, "(A)")  "  use iso_c_binding"
write (u, "(A)")  "  use prclib_interfaces"
write (u, "(A)")  "  use user_code_interface"
write (u, "(A)")  "  implicit none"
write (u, "(A)")  "  type(c_funptr) :: c_funptr"
write (u, "(A)")  "  character(*), intent(in) :: libname, fname"
do i = 1, size (libname)
    call write_lib_declarations (libname(i))
end do
if (has_user_lib) call write_user_code_declarations (u, user_procs)
write (u, "(A)")  "  select case (libname)"
do i = 1, size (libname)
    call write_lib_code (libname(i))
end do
if (has_user_lib) then
    write (u, "(A)")  "  case ('user')"
    call write_user_code_access (u, user_procs)
end if
write (u, "(A)")  "  case default"
write (u, "(A)")  "    c_funptr = c_null_funptr"
write (u, "(A)")  "  end select"
write (u, "(A)")  "end function libmanager_get_c_funptr"
close (u)

```

contains

```

subroutine write_lib_name (i, libname)
    integer, intent(in) :: i
    type(string_t), intent(in) :: libname
    write (u, "(A,I0,A)")  "  case (" , i, ")";  name = '' // char (libname) &
        // ""

```



```

end subroutine write_lib_name

subroutine write_lib_declarations (libname)
  type(string_t), intent(in) :: libname
  write (u, "(A)") "  procedure(prc_get_n_processes), bind(C) :: " &
    // char (libname)// "_" // "get_n_processes"
  write (u, "(A)") "  procedure(prc_get_stringptr), bind(C) :: " &
    // char (libname)// "_" // "get_process_id"
  write (u, "(A)") "  procedure(prc_get_stringptr), bind(C) :: " &
    // char (libname)// "_" // "get_model_name"
  write (u, "(A)") "  procedure(prc_get_stringptr), bind(C) :: " &
    // char (libname)// "_" // "get_restrictions"
  write (u, "(A)") "  procedure(prc_get_stringptr), bind(C) :: " &
    // char (libname)// "_" // "get_omega_flags"
  write (u, "(A)") "  procedure(prc_get_stringptr), bind(C) :: " &
    // char (libname)// "_" // "get_md5sum"
  write (u, "(A)") "  procedure(prc_get_int), bind(C) :: " &
    // char (libname)// "_" // "get_n_in"
  write (u, "(A)") "  procedure(prc_get_int), bind(C) :: " &
    // char (libname)// "_" // "get_n_out"
  write (u, "(A)") "  procedure(prc_get_int), bind(C) :: " &
    // char (libname)// "_" // "get_n_flv"
  write (u, "(A)") "  procedure(prc_get_int), bind(C) :: " &
    // char (libname)// "_" // "get_n_hel"
  write (u, "(A)") "  procedure(prc_get_int), bind(C) :: " &
    // char (libname)// "_" // "get_n_col"
  write (u, "(A)") "  procedure(prc_get_int), bind(C) :: " &
    // char (libname)// "_" // "get_n_cin"
  write (u, "(A)") "  procedure(prc_get_int), bind(C) :: " &
    // char (libname)// "_" // "get_n_cf"
  write (u, "(A)") "  procedure(prc_get_log), bind(C) :: " &
    // char (libname)// "_" // "get_openmp_status"
  write (u, "(A)") "  procedure(prc_set_int_tab1), bind(C) :: " &
    // char (libname)// "_" // "set_flv_state"
  write (u, "(A)") "  procedure(prc_set_int_tab1), bind(C) :: " &
    // char (libname)// "_" // "set_hel_state"
  write (u, "(A)") "  procedure(prc_set_int_tab2), bind(C) :: " &
    // char (libname)// "_" // "set_col_state"
  write (u, "(A)") "  procedure(prc_set_cf_tab), bind(C) :: " &
    // char (libname)// "_" // "set_cf_table"
  write (u, "(A)") "  procedure(prc_get_fptr), bind(C) :: " &
    // char (libname)// "_" // "init_get_fptr"
  write (u, "(A)") "  procedure(prc_get_fptr), bind(C) :: " &
    // char (libname)// "_" // "final_get_fptr"
  write (u, "(A)") "  procedure(prc_get_fptr), bind(C) :: " &
    // char (libname)// "_" // "update_alpha_s_get_fptr"
  write (u, "(A)") "  procedure(prc_get_fptr), bind(C) :: " &
    // char (libname)// "_" // "new_event_get_fptr"
  write (u, "(A)") "  procedure(prc_get_fptr), bind(C) :: " &
    // char (libname)// "_" // "reset_helicity_selection_get_fptr"
  write (u, "(A)") "  procedure(prc_get_fptr), bind(C) :: " &
    // char (libname)// "_" // "is_allowed_get_fptr"
  write (u, "(A)") "  procedure(prc_get_fptr), bind(C) :: " &
    // char (libname)// "_" // "get_amplitude_get_fptr"

```

```

end subroutine write_lib_declarations

subroutine write_lib_code (libname)
  type(string_t), intent(in) :: libname
  write (u, "(2x,A)") "case ('" // char (libname) // "')"
  write (u, "(2x,A)") "  select case (fname)"
  call write_fun_code (char (libname), "get_n_processes")
  call write_fun_code (char (libname), "get_process_id")
  call write_fun_code (char (libname), "get_model_name")
  call write_fun_code (char (libname), "get_restrictions")
  call write_fun_code (char (libname), "get_omega_flags")
  call write_fun_code (char (libname), "get_md5sum")
  call write_fun_code (char (libname), "get_n_in")
  call write_fun_code (char (libname), "get_n_out")
  call write_fun_code (char (libname), "get_n_flv")
  call write_fun_code (char (libname), "get_n_hel")
  call write_fun_code (char (libname), "get_n_col")
  call write_fun_code (char (libname), "get_n_cin")
  call write_fun_code (char (libname), "get_n_cf")
  call write_fun_code (char (libname), "get_openmp_status")
  call write_fun_code (char (libname), "set_flv_state")
  call write_fun_code (char (libname), "set_hel_state")
  call write_fun_code (char (libname), "set_col_state")
  call write_fun_code (char (libname), "set_cf_table")
  call write_fun_code (char (libname), "init_get_fptr")
  call write_fun_code (char (libname), "final_get_fptr")
  call write_fun_code (char (libname), "update_alpha_s_get_fptr")
  call write_fun_code (char (libname), "reset_helicity_selection_get_fptr")
  call write_fun_code (char (libname), "new_event_get_fptr")
  call write_fun_code (char (libname), "is_allowed_get_fptr")
  call write_fun_code (char (libname), "get_amplitude_get_fptr")
  write (u, "(2x,A)") "  case default"
  write (u, "(2x,A)") "    print *, fname"
  write (u, "(2x,A)") "    stop 'WHIZARD bug: " &
    // "libmanager cannot handle this function'"
  write (u, "(2x,A)") "  end select"
end subroutine write_lib_code

subroutine write_fun_code (prefix, fname)
  character(*), intent(in) :: prefix, fname
  write (u, "(5x,A)") "case ('" // fname // "')"
  write (u, "(5x,A)") "  c_fptr = c_funloc (" // prefix &
    // "_" // fname // ")"
end subroutine write_fun_code

end subroutine write_library_manager

```

These are the interfaces of the functions provided by the library manager.

⟨Process libraries: interfaces⟩≡

⟨Libmanager: interfaces⟩

⟨Libmanager: interfaces⟩≡

```

interface
  function libmanager_get_n_libs () result (n)

```

```

        integer :: n
    end function libmanager_get_n_libs
end interface

```

```

<Libmanager: interfaces>+≡
interface
    function libmanager_get_libname (i) result (name)
        use iso_varying_string, string_t => varying_string !NODEP!
        type(string_t) :: name
        integer, intent(in) :: i
    end function libmanager_get_libname
end interface

```

```

<Libmanager: interfaces>+≡
interface
    function libmanager_get_c_funptr (libname, fname) result (c_fptr)
        use iso_c_binding !NODEP!
        type(c_funptr) :: c_fptr
        character(*), intent(in) :: libname, fname
    end function libmanager_get_c_funptr
end interface

```

13.1.11 Collect model-specific libraries

This returns appropriate linker flags for the model parameter libraries that are used by the generated matrix element. At the end, the main libwhizard is appended (again), because functions from that may be required.

Extra models in the local user space need to be treated individually.

```

<Process libraries: public>+≡
    public :: get_modellibs_flags

<Process libraries: procedures>+≡
function get_modellibs_flags (prc_lib, os_data) result (flags)
    type(process_library_t), intent(in) :: prc_lib
    type(os_data_t), intent(in) :: os_data
    type(string_t) :: flags
    type(string_t), dimension(:), allocatable :: models
    type(string_t) :: modelname, modellib, modellib_full
    logical :: exist
    type(process_configuration_t), pointer :: current
    integer :: i, j, mi
    flags = "-lomega"
    if ((.not. os_data%use_testfiles) .and. &
        os_dir_exist (os_data%whizard_models_libpath_local)) &
        flags = flags // " -L" // os_data%whizard_models_libpath_local
    flags = flags // " -L" // os_data%whizard_models_libpath
    allocate (models(prc_lib%n_prc + 1))
    models = ""
    mi = 1
    current => prc_lib%prc_first
    SCAN: do i = 1, prc_lib%n_prc
        modelname = model_get_name (current%model)

```

```

do j = 1, mi
  if (models(mi) == modelname) cycle SCAN
end do
models(mi) = modelname
mi = mi + 1
if (os_data%use_libtool) then
  modellib = "libparameters_" // modelname // ".la"
else
  modellib = "libparameters_" // modelname // ".a"
end if
exist = .false.
if (.not. os_data%use_testfiles) then
  modellib_full = os_data%whizard_models_libpath_local &
    // "/" // modellib
  inquire (file=char (modellib_full), exist=exist)
end if
if (.not. exist) then
  modellib_full = os_data%whizard_models_libpath &
    // "/" // modellib
  inquire (file=char (modellib_full), exist=exist)
end if
if (exist) flags = flags // " -lparameters_" // modelname
current => current%next
end do SCAN
deallocate (models)
flags = flags // " -lwhizard"
end function get_modellibs_flags

```

13.1.12 Compile and link a library

The process library proper consists of the process-specific Fortran source files and the driver (interface)

```

<Process libraries: public>+≡
  public :: process_library_compile

<Process libraries: procedures>+≡
  subroutine process_library_compile &
    (prc_lib, os_data, recompile_library, objlist_link)
    type(process_library_t), intent(inout) :: prc_lib
    type(os_data_t), intent(in) :: os_data
    logical, intent(in) :: recompile_library
    type(string_t), intent(out) :: objlist_link
    type(string_t) :: objlist_comp
    type(process_configuration_t), pointer :: current
    type(string_t) :: ext
    integer :: i
    if (prc_lib%status == STAT_LOADED) call process_library_unload (prc_lib)
    call msg_message ("Compiling process library '" // &
      char (process_library_get_name (prc_lib)) // "'")
    objlist_comp = ""
    objlist_link = ""
    if (os_data%use_libtool) then
      ext = ".lo"

```

```

else
    ext = os_data%obj_ext
end if
current => prc_lib%prc_first
SCAN_PROCESSES: do i = 1, prc_lib%n_prc
    objlist_link = objlist_link // " " // current%id // ext
    if (recompile_library) &
        current%status = min (STAT_CODE_GENERATED, current%status)
    if (current%status == STAT_CODE_GENERATED) then
        objlist_comp = objlist_comp // " " // current%id // ext
        call os_compile_shared (current%id, os_data)
        current%status = STAT_COMPILED
    else
        call msg_message ("Skipping process '" // char (current%id) &
            // "' (object code exists)")
    end if
    current => current%next
end do SCAN_PROCESSES
if (objlist_comp /= "") then
    call os_compile_shared (prc_lib%basename, os_data)
    objlist_link = objlist_link // " " // prc_lib%basename // ext
else
    call msg_message ("Skipping library '" &
        // char (prc_lib%basename) &
        // "' (no processes have been recompiled)")
    objlist_link = ""
end if
prc_lib%status = STAT_COMPILED
end subroutine process_library_compile

```

(Process libraries: public)+≡

```
public :: process_library_link
```

(Procedures libraries: procedures)+≡

```

subroutine process_library_link (prc_lib, os_data, objlist)
    type(process_library_t), intent(in) :: prc_lib
    type(os_data_t), intent(in) :: os_data
    type(string_t), intent(in) :: objlist
    type(os_data_t) :: local_os_data
    local_os_data = os_data
    local_os_data%ldflags = os_data%ldflags &
        // " " // get_modellibs_flags (prc_lib, os_data)
    if (objlist /= "") then
        call os_link_shared (objlist, prc_lib%basename, local_os_data)
    end if
end subroutine process_library_link

```

13.1.13 Standalone executable

Compile the library bundle and link with the libraries as a standalone executable

(Process libraries: public)+≡

```
public :: compile_library_manager
```

```

<Process libraries: procedures>+≡
  subroutine compile_library_manager (os_data)
    type(os_data_t), intent(in) :: os_data
    call msg_message ("Compiling library manager")
    call os_compile_shared (var_str ("libmanager"), os_data)
  end subroutine compile_library_manager

<Process libraries: public>+≡
  public :: link_executable

<Process libraries: procedures>+≡
  subroutine link_executable (libname, exec_name, flags, os_data)
    type(string_t), dimension(:), intent(in) :: libname
    type(string_t), intent(in) :: exec_name, flags
    type(os_data_t), intent(in) :: os_data
    type(string_t) :: objlist, ext_o, ext_a
    integer :: i
    if (os_data%use_libtool) then
      ext_o = ".lo"
      ext_a = ".la"
    else
      ext_o = ".o"
      ext_a = ".a"
    end if
    objlist = "libmanager" // ext_o
    do i = 1, size (libname)
      objlist = objlist // " " // libname(i) // ext_a
    end do
    if (has_user_lib) then
      objlist = objlist // " user" // ext_a
    end if
    call os_link_static (objlist // flags, exec_name, os_data)
  end subroutine link_executable

```

13.1.14 Loading a library

This loads a process library. We assume that it resides in the current directory.

Loading the library assigns all procedure pointers to procedures within the library.

Unloading is done by the finalizer.

```

<Process libraries: public>+≡
  public :: process_library_load

<Process libraries: procedures>+≡
  subroutine process_library_load (prc_lib, os_data, model, var_list, ignore)
    type(process_library_t), intent(inout), target :: prc_lib
    type(os_data_t), intent(in) :: os_data
    type(model_t), pointer, optional :: model
    type(var_list_t), intent(inout) :: var_list
    logical, intent(in), optional :: ignore
    type(c_funptr) :: c_funptr
    type(model_t), pointer :: mdl
    type(string_t) :: prefix

```

```

logical :: ignore_error
ignore_error = .false.; if (present (ignore)) ignore_error = ignore
if (prc_lib%status == STAT_LOADED) then
  if (.not. ignore_error) then
    call msg_message ("Process library '" // char (prc_lib%basename) &
      // "' is already loaded")
  end if
  return
end if
if (prc_lib%static) then
  call msg_message ("Loading static process library '" &
    // char (prc_lib%basename) // "'")
else
  call msg_message ("Loading process library '" &
    // char (prc_lib%basename) // "'")
  prc_lib%libname = os_get_dlname (prc_lib%basename, os_data, ignore)
  if (prc_lib%libname == "") return
  call dlaccess_init (prc_lib%dlaccess, var_str ("."), &
    prc_lib%libname, os_data)
  call process_library_check_dLError (prc_lib)
end if
prefix = prc_lib%basename
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_n_processes"))
call c_f_procpointer (c_fptr, prc_lib%get_n_prc)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_process_id"))
call c_f_procpointer (c_fptr, prc_lib%get_process_id)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_model_name"))
call c_f_procpointer (c_fptr, prc_lib%get_model_name)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_restrictions"))
call c_f_procpointer (c_fptr, prc_lib%get_restrictions)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_omega_flags"))
call c_f_procpointer (c_fptr, prc_lib%get_omega_flags)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_openmp_status"))
call c_f_procpointer (c_fptr, prc_lib%get_openmp_status)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_md5sum"))
call c_f_procpointer (c_fptr, prc_lib%get_md5sum)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_n_in"))
call c_f_procpointer (c_fptr, prc_lib%get_n_in)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_n_out"))
call c_f_procpointer (c_fptr, prc_lib%get_n_out)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_n_flv"))
call c_f_procpointer (c_fptr, prc_lib%get_n_flv)
c_fptr = process_library_get_c_funptr &
  (prc_lib, prefix, var_str ("get_n_hel"))

```

```

call c_f_procpointer (c_fptr, prc_lib%get_n_hel)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("get_n_col"))
call c_f_procpointer (c_fptr, prc_lib%get_n_col)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("get_n_cin"))
call c_f_procpointer (c_fptr, prc_lib%get_n_cin)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("get_n_cf"))
call c_f_procpointer (c_fptr, prc_lib%get_n_cf)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("set_flv_state"))
call c_f_procpointer (c_fptr, prc_lib%set_flv_state)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("set_hel_state"))
call c_f_procpointer (c_fptr, prc_lib%set_hel_state)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("set_col_state"))
call c_f_procpointer (c_fptr, prc_lib%set_col_state)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("set_cf_table"))
call c_f_procpointer (c_fptr, prc_lib%set_cf_table)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("init_get_fptr"))
call c_f_procpointer (c_fptr, prc_lib%init_get_fptr)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("final_get_fptr"))
call c_f_procpointer (c_fptr, prc_lib%final_get_fptr)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("update_alpha_s_get_fptr"))
call c_f_procpointer (c_fptr, prc_lib%update_alpha_s_get_fptr)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("new_event_get_fptr"))
call c_f_procpointer (c_fptr, prc_lib%new_event_get_fptr)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("reset_helicity_selection_get_fptr"))
call c_f_procpointer (c_fptr, prc_lib%reset_helicity_selection_get_fptr)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("is_allowed_get_fptr"))
call c_f_procpointer (c_fptr, prc_lib%is_allowed_get_fptr)
c_fptr = process_library_get_c_funptr &
      (prc_lib, prefix, var_str ("get_amplitude_get_fptr"))
call c_f_procpointer (c_fptr, prc_lib%get_amplitude_get_fptr)
call process_library_load_configuration (prc_lib, os_data, mdl)
prc_lib%status = STAT_LOADED
if (associated (prc_lib%reload_hook)) &
      call prc_lib%reload_hook (process_library_get_name (prc_lib))
call var_list_set_string (var_list, var_str ("$library_name"), &
      process_library_get_name (prc_lib), is_known=.true.) ! $
if (present (model)) model => mdl
end subroutine process_library_load

```

Unload a process library. Necessary before recompiling and reloading.


```

<Process libraries: public>+≡
    public :: process_library_unload

<Process libraries: procedures>+≡
    subroutine process_library_unload (prc_lib)
        type(process_library_t), intent(inout) :: prc_lib
        call msg_message ("Unloading process library '" // &
            char (process_library_get_name (prc_lib)) // "'")
        if (associated (prc_lib%unload_hook)) &
            call prc_lib%unload_hook (process_library_get_name(prc_lib))
        call dlaccess_final (prc_lib%dlaccess)
        prc_lib%status = STAT_CODE_GENERATED
    end subroutine process_library_unload

```

Register hooks for un- / reloading the process library.

```

<Process libraries: public>+≡
    public :: process_library_set_unload_hook
    public :: process_library_set_reload_hook

<Process libraries: procedures>+≡
    subroutine process_library_set_unload_hook (prc_lib, hook)
        type(process_library_t), intent(inout), target :: prc_lib
        procedure(prclib_unload_hook), pointer, intent(in) :: hook
        prc_lib%unload_hook => hook
    end subroutine process_library_set_unload_hook

    subroutine process_library_set_reload_hook (prc_lib, hook)
        type(process_library_t), intent(inout), target :: prc_lib
        procedure(prclib_reload_hook), pointer, intent(in) :: hook
        prc_lib%reload_hook => hook
    end subroutine process_library_set_reload_hook

```

Get a C function pointer to a procedure belonging to the process library interface and check for an error condition.

```

<Process libraries: procedures>+≡
    function process_library_get_c_funptr &
        (prc_lib, prefix, fname) result (c_fptr)
        type(c_funptr) :: c_fptr
        type(process_library_t), intent(inout) :: prc_lib
        type(string_t), intent(in) :: prefix, fname
        type(string_t) :: full_name
        full_name = prefix // "_" // fname
        if (prc_lib%static) then
            c_fptr = libmanager_get_c_funptr (char (prefix), char (fname))
        else
            c_fptr = dlaccess_get_c_funptr (prc_lib%dlaccess, full_name)
            call process_library_check_dlerror (prc_lib)
        end if
    end function process_library_get_c_funptr

```

Check for an error condition and signal it.

```

<Process libraries: procedures>+≡
    subroutine process_library_check_dlerror (prc_lib)

```

```

    type(process_library_t), intent(in) :: prc_lib
    if (dlaccess_has_error (prc_lib%dlaccess)) then
        call msg_fatal (char (dlaccess_get_error (prc_lib%dlaccess)))
    end if
end subroutine process_library_check_dLError

```

13.1.15 The library store

We want to handle several libraries in parallel, therefore we introduce a global library store, similar to the model and process lists. The store is a module variable.

(Process libraries: types)+≡

```

    type :: process_library_store_t
    private
        type(process_library_t), pointer :: first => null ()
        type(process_library_t), pointer :: last => null ()
    end type process_library_store_t

```

(Process libraries: variables)≡

```

    type(process_library_store_t), save :: process_library_store

```

Append a new library, if it does not yet exist, and return a pointer to it.

(Process libraries: public)+≡

```

    public :: process_library_store_append

```

(Process libraries: procedures)+≡

```

    subroutine process_library_store_append (name, os_data, prc_lib)
        type(string_t), intent(in) :: name
        type(os_data_t), intent(in) :: os_data
        type(process_library_t), pointer :: prc_lib
        prc_lib => process_library_store_get_ptr (name)
        if (.not. associated (prc_lib)) then
            call msg_message &
                ("Initializing process library '" // char (name) // "'")
            allocate (prc_lib)
            call process_library_init (prc_lib, name, os_data)
            if (associated (process_library_store%last)) then
                process_library_store%last%next => prc_lib
            else
                process_library_store%first => prc_lib
            end if
            process_library_store%last => prc_lib
        end if
    end subroutine process_library_store_append

```

Finalizer. This closes all open libraries.

(Process libraries: public)+≡

```

    public :: process_library_store_final

```

(Process libraries: procedures)+≡

```

    subroutine process_library_store_final ()
        type(process_library_t), pointer :: current

```

```

do while (associated (process_library_store%first))
  current => process_library_store%first
  process_library_store%first => current%next
  call process_library_final (current)
  deallocate (current)
end do
process_library_store%last => null ()
end subroutine process_library_store_final

```

Load all libraries

```

<Process libraries: public>+≡
  public :: process_library_store_load

<Process libraries: procedures>+≡
  subroutine process_library_store_load (os_data, var_list)
    type(os_data_t), intent(in) :: os_data
    type(var_list_t), intent(inout), optional :: var_list
    type(process_library_t), pointer :: current
    current => process_library_store%first
    do while (associated (current))
      call process_library_load (current, os_data, var_list=var_list)
      current => current%next
    end do
  end subroutine process_library_store_load

```

Get a pointer to an existing (named) library

```

<Process libraries: public>+≡
  public :: process_library_store_get_ptr

<Process libraries: procedures>+≡
  function process_library_store_get_ptr (name) result (prc_lib)
    type(process_library_t), pointer :: prc_lib
    type(string_t), intent(in) :: name
    prc_lib => process_library_store%first
    do while (associated (prc_lib))
      if (prc_lib%basename == name) exit
      prc_lib => prc_lib%next
    end do
  end function process_library_store_get_ptr

```

Get a pointer to the first/next library

```

<Process libraries: public>+≡
  public :: process_library_store_get_first

<Process libraries: procedures>+≡
  function process_library_store_get_first () result (prc_lib)
    type(process_library_t), pointer :: prc_lib
    prc_lib => process_library_store%first
  end function process_library_store_get_first

```

13.1.16 Preloading static libraries

Static libraries are static, so it is sensible to load them all at startup. (By default, they are linked, but not loaded in the sense that a `process_library` object exists for them.) This can be done using this routine.

```
<Process libraries: public>+≡
    public :: process_library_store_load_static

<Process libraries: procedures>+≡
    subroutine process_library_store_load_static &
        (os_data, prc_lib, model, var_list)
        type(os_data_t), intent(in) :: os_data
        type(process_library_t), pointer :: prc_lib
        type(model_t), pointer :: model
        type(var_list_t), intent(inout) :: var_list
        integer :: n, i
        type(string_t), dimension(:), allocatable :: libname
        n = libmanager_get_n_libs ()
        allocate (libname (n))
        do i = 1, n
            libname(i) = libmanager_get_libname (i)
        end do
        do i = 1, n
            call process_library_store_append (libname(i), os_data, prc_lib)
            call process_library_set_static (prc_lib, .true.)
            call process_library_load (prc_lib, os_data, model, var_list)
        end do
    end subroutine process_library_store_load_static
```

Distinguish the module name, depending on the method of the process.

```
<Procedures>+≡
    function process_library_get_module_name (id, method) result (mod_id)
        type(string_t), intent(in) :: id
        integer, intent(in) :: method
        type(string_t) :: mod_id
        select case (method)
            case (PRC_OMEGA)
                mod_id = "opr_" // id
            case (PRC_TEST, PRC_UNIT)
                mod_id = "tpr_" // id
            case default
                mod_id = id
        end select
    end function process_library_get_module_name
```

13.1.17 Test

```
<Process libraries: public>+≡
    public :: process_libraries_test

<Process libraries: procedures>+≡
    subroutine process_libraries_test ()
        type(model_t), pointer :: model
        type(process_library_t), pointer :: prc_lib => null ()
```

```

type(string_t), dimension(:), allocatable :: prt_in, prt_out
type(os_data_t) :: os_data
type(string_t) :: objlist
type(var_list_t), pointer :: var_list => null ()
integer :: n_prc
allocate (var_list)
allocate (prc_lib)
call process_library_store_final
call os_data_init (os_data)
print *, "*** Read model file"
call syntax_model_file_init ()
call model_list_read_model &
    (var_str("SM"), var_str("SM.mdl"), os_data, model)
call syntax_model_file_final ()
print *, "*** Create library 'proc' with two processes"
print *, "* Setup process configuration"
call var_list_append_string (var_list, name = "$library_name", sval = "proc") ! $
call process_library_store_append (var_str ("proc"), os_data, prc_lib)
allocate (prt_in (1), prt_out (2))
prt_in(1) = "Z"
prt_out(1) = "e1"
prt_out(2) = "E1"
call process_library_append &
    (prc_lib, var_str ("zee"), model, prt_in, prt_out, method = PRC_TEST)
deallocate (prt_in, prt_out)
allocate (prt_in (2), prt_out (2))
prt_in(1) = "g"
prt_in(2) = "g"
prt_out(1) = "u"
prt_out(2) = "U"
call process_library_append &
    (prc_lib, var_str ("uu"), model, prt_in, prt_out, method = PRC_TEST)
print *
print *, "* Generate code"
call process_library_generate_code (prc_lib, os_data)
print *
print *, "* Write driver file 'proc_interface.f90'"
call process_library_write_driver (prc_lib)
print *
print *, "* Compile and link as 'libproc.so'"
call process_library_compile (prc_lib, os_data, .false., objlist)
call process_library_link (prc_lib, os_data, objlist)
print *
print *, "* Load shared libraries"
call process_library_load (prc_lib, os_data, var_list = var_list)
print *
print *, "* Execute 'get_n_processes' from the shared library named 'proc'"
print *
prc_lib => process_library_store_get_ptr (var_str ("proc"))
n_prc = prc_lib% get_n_prc ()
print *, "n_prc = ", n_prc
if (n_prc .ne. 2) then
    call msg_fatal (" Process library test failed.")
else

```

```

        call msg_message ("Successful.")
    end if
    print *
    print *, "* Cleanup"
    call process_library_store_final
    call var_list_final (var_list)
    deallocate (var_list)
end subroutine process_libraries_test

```

13.2 Hard interactions

This module is concerned with the matrix element of an elementary interaction (typically, a hard scattering or heavy-particle decay). The module does not hold phase space information.

`<hard_interactions.f90>`≡

<File header>

```
module hard_interactions
```

```

    use iso_c_binding !NODEP!
    use kinds !NODEP!

```

<Use strings>

<Use file utils>

```

    use diagnostics !NODEP!
    use lorentz !NODEP!
    use os_interface
    use variables
    use models
    use flavors
    use helicities
    use colors
    use quantum_numbers
    use state_matrices
    use interactions
    use evaluators
    use particles
    use prclib_interfaces
    use process_libraries

```

<Standard module head>

<Hard interactions: public>

<Hard interactions: types>

<Hard interactions: interfaces>

```
contains
```

<Hard interactions: procedures>

```
end module hard_interactions
```

13.2.1 The hard-interaction data type

We define a special data type that accesses the process library. While constant data are stored as data, the process-specific functions for initialization, calculation and finalization are stored as procedure pointers.

```
<Hard interactions: types>≡
type :: hard_interaction_data_t
  type(string_t) :: id
  type(model_t), pointer :: model => null ()
  integer :: n_tot = 0
  integer :: n_in = 0
  integer :: n_out = 0
  integer :: n_flv = 0
  integer :: n_hel = 0
  integer :: n_col = 0
  integer :: n_cin = 0
  integer :: n_cf = 0
  real(default), dimension(:), allocatable :: par
  integer, dimension(:,:), allocatable :: flv_state, hel_state
  integer, dimension(:,:), allocatable :: col_state
  logical, dimension(:,:), allocatable :: ghost_flag
  integer, dimension(:,:), allocatable :: col_flow_index
  complex(default), dimension(:), allocatable :: col_factor
  procedure(prc_init), nopass, pointer :: init => null ()
  procedure(prc_final), nopass, pointer :: final => null ()
  procedure(prc_update_alpha_s), nopass, pointer :: update_alpha_s => null ()
  procedure(prc_reset_helicity_selection), nopass, pointer :: &
    reset_helicity_selection => null ()
  procedure(prc_new_event), nopass, pointer :: new_event => null ()
  procedure(prc_is_allowed), nopass, pointer :: is_allowed => null ()
  procedure(prc_get_amplitude), nopass, pointer :: get_amplitude => null ()
end type hard_interaction_data_t
```

Initialize the hard process, using the process ID and the model parameters.

Assigning flavor/helicity/color tables: we need an intermediate allocatable array to serve as a C pointer target; the C pointer is passed to the process library where it is dereferenced and the array is filled. In principle, this copying step is necessary only if the Fortran and C types differ (which happens for the logical type). However, since this is not critical, we do it anyway.

For incoming particles, the particle color is inverted. This is useful for squaring the color flow, but has to be undone before convoluting with structure functions.

We define additional functions for finalizing and resetting the pointers into the process library when the library is reloaded.

```
<Hard interactions: procedures>≡
subroutine hard_interaction_data_unload (data)
  type(hard_interaction_data_t), intent(inout) :: data
  call data%final
  nullify (data%init)
  nullify (data%final)
```

```

nullify (data%update_alpha_s)
nullify (data%reset_helicity_selection)
nullify (data%new_event)
nullify (data%is_allowed)
nullify (data%get_amplitude)
end subroutine hard_interaction_data_unload

subroutine hard_interaction_data_reload (data, prc_lib, pid)
  type(hard_interaction_data_t), intent(inout) :: data
  type(process_library_t), intent(in) :: prc_lib
  integer, optional :: pid
  integer :: the_pid
  type(c_funptr) :: fptr
  if (present (pid)) then
    the_pid = pid
  else
    the_pid = process_library_get_process_pid (prc_lib, data%id)
    if (the_pid <= 0) call msg_bug &
      ("Invalid process ID '" // char (data%id) // "'")
  end if
  call prc_lib% init_get_fptr (the_pid, fptr)
  call c_f_procpointer (fptr, data% init)
  call prc_lib% final_get_fptr (the_pid, fptr)
  call c_f_procpointer (fptr, data% final)
  call prc_lib% update_alpha_s_get_fptr (the_pid, fptr)
  call c_f_procpointer (fptr, data% update_alpha_s)
  call prc_lib% reset_helicity_selection_get_fptr (the_pid, fptr)
  call c_f_procpointer (fptr, data% reset_helicity_selection)
  call prc_lib% new_event_get_fptr (the_pid, fptr)
  call c_f_procpointer (fptr, data% new_event)
  call prc_lib% is_allowed_get_fptr (the_pid, fptr)
  call c_f_procpointer (fptr, data% is_allowed)
  call prc_lib% get_amplitude_get_fptr (the_pid, fptr)
  call c_f_procpointer (fptr, data% get_amplitude)
end subroutine hard_interaction_data_reload

```

(Hard interactions: procedures)+≡

```

subroutine hard_interaction_data_init &
  (data, prc_lib, process_index, process_id, model)
  type(hard_interaction_data_t), intent(out) :: data
  type(process_library_t), intent(in) :: prc_lib
  integer, intent(in) :: process_index
  type(string_t), intent(in) :: process_id
  type(model_t), intent(in), target :: model
  integer(c_int) :: pid
  type(string_t) :: model_name
  integer(c_int), dimension(:,:), allocatable, target :: flv_state, hel_state
  integer(c_int), dimension(:,:), allocatable, target :: col_state
  logical(c_bool), dimension(:,:), allocatable, target :: ghost_flag
  integer(c_int), dimension(:), allocatable, target :: cf_index1, cf_index2
  complex(c_default_complex), dimension(:), allocatable, target :: col_factor
  integer :: c, i
  if (.not. associated (prc_lib% get_process_id)) then
    call msg_fatal ("Process library '" // char (prc_lib%basename) // "':" &

```



```

        // " procedures unavailable (missing compile command?)"
        data%id = ""
        return
    end if
    pid = process_index
    data%id = process_library_get_process_id (prc_lib, pid)
    if (data%id /= process_id) then
        call msg_bug ("Process ID mismatch: requested '" &
            // char (process_id) // "' but found '" // char (data%id) // "'")
    end if
    data%model => model
    model_name = process_library_get_process_model_name (prc_lib, pid)
    if (model_get_name (data%model) /= model_name) then
        call msg_warning ("Process '" // char (process_id) // "': " &
            // "temporarily resetting model from '" &
            // char (model_get_name (data%model)) // "' to '" &
            // char (model_name) // "'")
        data%model => model_list_get_model_ptr (model_name)
        if (.not. associated (data%model)) then
            call msg_fatal ("Model '" // char (model_name) &
                // "' is not initialized")
        end if
    end if
    data%n_in = prc_lib% get_n_in (pid)
    data%n_out = prc_lib% get_n_out (pid)
    data%n_tot = data%n_in + data%n_out
    data%n_flv = prc_lib% get_n_flv (pid)
    data%n_hel = prc_lib% get_n_hel (pid)
    data%n_col = prc_lib% get_n_col (pid)
    data%n_cin = prc_lib% get_n_cin (pid)
    data%n_cf = prc_lib% get_n_cf (pid)
    if (data%n_flv == 0) then
        call msg_warning ("Process '" // char (process_id) // "': " &
            // "matrix element vanishes.")
    end if
    call model_parameters_to_array (data%model, data%par)
    allocate (data%flv_state (data%n_tot, data%n_flv))
    allocate (data%hel_state (data%n_tot, data%n_hel))
    allocate (data%col_state (data%n_cin, data%n_tot, data%n_col))
    allocate (data%ghost_flag (data%n_tot, data%n_col))
    allocate (data%col_flow_index (2, data%n_cf))
    allocate (data%col_factor (data%n_cf))
    allocate (flv_state (data%n_tot, data%n_flv))
    allocate (hel_state (data%n_tot, data%n_hel))
    allocate (col_state (data%n_cin, data%n_tot, data%n_col))
    allocate (ghost_flag (data%n_tot, data%n_col))
    allocate (cf_index1 (data%n_cf))
    allocate (cf_index2 (data%n_cf))
    allocate (col_factor (data%n_cf))
    call prc_lib% set_flv_state (pid, &
        c_loc (flv_state), &
        int (/data%n_tot, data%n_flv/), kind=c_int))
    data%flv_state = flv_state
    call prc_lib% set_hel_state (pid, &

```

```

        c_loc (hel_state), &
        int((/data%n_tot, data%n_hel/), kind=c_int))
data%hel_state = hel_state
call prc_lib% set_col_state (pid, &
        c_loc (col_state), &
        int((/data%n_cin, data%n_tot, data%n_col/), kind=c_int), &
        c_loc (ghost_flag), &
        int((/data%n_tot, data%n_col/), kind=c_int))
if (data%n_cin /= 2) &
        call msg_bug ("Process library '" // char (prc_lib%basename) // "':" &
        // " number of color indices must be two")
forall (c = 1:2, i = 1:data%n_in)
        data%col_state(c,i,:) = - col_state(3-c,i,:)
end forall
forall (i = data%n_in+1:data%n_tot)
        data%col_state(:,i,:) = col_state(:,i,:)
end forall
data%ghost_flag = ghost_flag
call prc_lib% set_cf_table (pid, &
        c_loc (cf_index1), c_loc (cf_index2), c_loc (col_factor), &
        int ((/data%n_cf/), kind=c_int))
data%col_flow_index(1,:) = cf_index1
data%col_flow_index(2,:) = cf_index2
data%col_factor = col_factor
call hard_interaction_data_reload (data, prc_lib, pid=pid)
call hard_interaction_data_check_masses (data)
end subroutine hard_interaction_data_init

```

We have to make sure that the masses of the various flavors in a given position in the particle string coincide.

```

<Hard interactions: public>≡
public :: hard_interaction_data_check_masses

<Hard interactions: procedures>+≡
subroutine hard_interaction_data_check_masses (data)
    type(hard_interaction_data_t), intent(in) :: data
    type(flavor_t), dimension(:), allocatable :: flv
    real(default), dimension(:), allocatable :: mass
    integer :: i, j
    allocate (flv (data%n_flv), mass (data%n_flv))
    do i = 1, data%n_tot
        call flavor_init (flv, data%flv_state(i,:), data%model)
        mass = flavor_get_mass (flv)
        if (any (mass /= mass(1))) then
            call msg_fatal ("Process '" // char (data%id) // "':" &
                // "mass values in flavor combination do not coincide.")
        end if
    end do
end subroutine hard_interaction_data_check_masses

```

I/O:

```

<Hard interactions: procedures>+≡
subroutine hard_interaction_data_write (data, unit)

```

```

type(hard_interaction_data_t), intent(in) :: data
integer, intent(in), optional :: unit
integer :: f, h, c, n, i
integer :: u
u = output_unit (unit); if (u < 0) return
write (u, *) "Process '", char (trim (data%id)), "'
write (u, *) "n_tot = ", data%n_tot
write (u, *) "n_in = ", data%n_in
write (u, *) "n_out = ", data%n_out
write (u, *) "n_flv = ", data%n_flv
write (u, *) "n_hel = ", data%n_hel
write (u, *) "n_col = ", data%n_col
write (u, *) "n_cin = ", data%n_cin
write (u, *) "n_cf = ", data%n_cf
write (u, *) "Model parameters:"
do i = 1, size (data%par)
    write (u, *) i, data%par(i)
end do
write (u, *) "Flavor states:"
do f = 1, data%n_flv
    write (u, *) f, ":", data%flv_state (:,f)
end do
write (u, *) "Helicity states:"
do h = 1, data%n_hel
    write (u, *) h, ":", data%hel_state (:,h)
end do
write (u, *) "Color states:"
do c = 1, data%n_col
    write (u, "(I5,A)", advance="no") c, ":"
    do n = 1, data%n_tot
        write (u, "('/')", advance="no")
        if (data%ghost_flag (n, c)) write (u, "('*)", advance="no")
        do i = 1, data%n_cin
            if (data%col_state(i,n,c) == 0) cycle
            write (u, "(I3)", advance="no") data%col_state(i,n,c)
        end do
    end do
    write (u, "('/')")
end do
write (u, *) "Color factors:"
do c = 1, data%n_cf
    write (u, "(I5,A,2(I4,1x))", advance="no") c, ":", &
        data%col_flow_index(:,c)
    write (u, *) data%col_factor(c)
end do
end subroutine hard_interaction_data_write

```

13.2.2 The hard-interaction type

The type contains an interaction that is used to store the bare matrix element values. The flavor/helicity/color arrays are used to identify each matrix element for the amplitude function. Furthermore, there are three evaluators for the trace

(the squared matrix element proper), the squared matrix element with color factors, possibly exclusive in some quantum numbers, and the squared matrix element broken down by color flows. The latter two are needed only for the simulation of complete events, not for integration.

```

<Hard interactions: public>+≡
    public :: hard_interaction_t

<Hard interactions: types>+≡
    type :: hard_interaction_t
    private
    logical :: initialized = .false.
    type(hard_interaction_data_t) :: data
    integer :: n_values = 0
    integer, dimension(:), allocatable :: flv, hel, col
    type(interaction_t) :: int
    type(evaluator_t) :: eval_trace
    type(evaluator_t) :: eval_sqme
    type(evaluator_t) :: eval_flows
end type hard_interaction_t

```

Initializer. Set up the hard-process data and build the corresponding interaction structure. In parallel, assign the allowed flavor/helicity/color indices to the corresponding index arrays. For each valid combination, a matrix element pointer is prepared which is inserted as a new leaf in the interaction quantum-number tree.

In addition to initialization, we also provide subroutines for partial finalization and re-initialization if the process library is reloaded, or the parameters are changed.

```

<Hard interactions: public>+≡
    public :: hard_interaction_init
    public :: hard_interaction_unload
    public :: hard_interaction_reload
    public :: hard_interaction_update_parameters

<Hard interactions: procedures>+≡
    subroutine hard_interaction_init &
        (hi, prc_lib, process_index, process_id, model)
        type(hard_interaction_t), intent(out), target :: hi
        type(process_library_t), intent(in) :: prc_lib
        integer, intent(in) :: process_index
        type(string_t), intent(in) :: process_id
        type(model_t), intent(in), target :: model
        type(flavor_t), dimension(:), allocatable :: flv
        type(color_t), dimension(:), allocatable :: col
        type(helicity_t), dimension(:), allocatable :: hel
        type(quantum_numbers_t), dimension(:), allocatable :: qn
        integer :: f, h, c, i, n
        call hard_interaction_data_init &
            (hi%data, prc_lib, process_index, process_id, model)
        if (hi%data%id == "") return
        call hi%data%init (real (hi%data%par, c_default_float))
        call interaction_init &
            (hi%int, hi%data%n_in, 0, hi%data%n_out, set_relations=.true.)
    end subroutine

```

```

call hard_interaction_reset_helicity_selection (hi, 0._default, 0)
n = 0
do f = 1, hi%data%n_flv
  do h = 1, hi%data%n_hel
    do c = 1, hi%data%n_col
      if (hi%data%is_allowed (f, h, c)) n = n + 1
    end do
  end do
end do
hi%n_values = n
allocate (hi%flv (n), hi%hel (n), hi%col (n))
allocate (flv (hi%data%n_tot), col (hi%data%n_tot), hel (hi%data%n_tot))
allocate (qn (hi%data%n_tot))
i = 0
do f = 1, hi%data%n_flv
  do h = 1, hi%data%n_hel
    do c = 1, hi%data%n_col
      if (hi%data%is_allowed (f, h, c)) then
        i = i + 1
        hi%flv(i) = f
        hi%hel(i) = h
        hi%col(i) = c
        call flavor_init (flv, hi%data%flv_state(:,f), hi%data%model)
        call color_init_from_array (col, hi%data%col_state(:,c), &
                                     hi%data%ghost_flag(:,c))
        call helicity_init (hel, hi%data%hel_state(:,h))
        call quantum_numbers_init (qn, flv, col, hel)
        call interaction_add_state (hi%int, qn)
      end if
    end do
  end do
end do
call interaction_freeze (hi%int)
hi%initialized = .true.
end subroutine hard_interaction_init

subroutine hard_interaction_unload (hi)
  type(hard_interaction_t), intent(inout), target :: hi
  if (.not. associated (hi%data%final)) return
  call hard_interaction_data_unload (hi%data)
end subroutine hard_interaction_unload

subroutine hard_interaction_reload (hi, prc_lib)
  type(hard_interaction_t), intent(inout), target :: hi
  type(process_library_t), intent(in) :: prc_lib
  if (associated (hi%data%init)) return
  call hard_interaction_data_reload (hi%data, prc_lib)
  call hi%data% init (real (hi%data%par, c_default_float))
end subroutine hard_interaction_reload

subroutine hard_interaction_update_parameters (hi)
  type(hard_interaction_t), intent(inout), target :: hi
  call model_parameters_to_array (hi%data%model, hi%data%par)
  call hi%data% init (real (hi%data%par, c_default_float))

```

```
end subroutine hard_interaction_update_parameters
```

Finalizer:

```
<Hard interactions: public>+≡
```

```
public :: hard_interaction_final
```

```
<Hard interactions: procedures>+≡
```

```
subroutine hard_interaction_final (hi)
  type(hard_interaction_t), intent(inout) :: hi
  hi%initialized = .false.
  if (associated (hi%data% final)) call hi%data% final ()
  call interaction_final (hi%int)
  call evaluator_final (hi%eval_trace)
  call evaluator_final (hi%eval_flows)
  call evaluator_final (hi%eval_sqme)
  hi%n_values = 0
  if (allocated (hi%flv)) deallocate (hi%flv)
  if (allocated (hi%hel)) deallocate (hi%hel)
  if (allocated (hi%col)) deallocate (hi%col)
end subroutine hard_interaction_final
```

I/O:

```
<Hard interactions: public>+≡
```

```
public :: hard_interaction_write
```

```
<Hard interactions: procedures>+≡
```

```
subroutine hard_interaction_write &
  (hi, unit, verbose, show_momentum_sum, show_mass, write_comb)
  type(hard_interaction_t), intent(in) :: hi
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
  logical, intent(in), optional :: write_comb
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, "(1x,A)") "Hard interaction:"
  call hard_interaction_data_write (hi%data, u)
  if (present (write_comb)) then
    if (write_comb .and. hi%n_values /= 0) then
      write (u, "(1x,A)") "Allowed f/h/c index combinations:"
      do i = 1, hi%n_values
        write (u, *) i, ":", hi%flv(i), hi%hel(i), hi%col(i)
      end do
    end if
  end if
  write (u, *)
  call interaction_write &
    (hi%int, unit, verbose, show_momentum_sum, show_mass)
  write (u, *) repeat (" ", 36)
  write (u, "(A)") "Trace including color factors (hard interaction)"
  call evaluator_write &
    (hi%eval_trace, unit, verbose, show_momentum_sum, show_mass)
  write (u, *) repeat (" ", 36)
  write (u, "(A)") "Exclusive sqme including color factors (hard interaction)"
  call evaluator_write &
```

```

        (hi%eval_sqme, unit, verbose, show_momentum_sum, show_mass)
write (u, *) repeat (" ", 36)
write (u, "(A)") "Color flow coefficients (hard interaction)"
call evaluator_write &
        (hi%eval_flows, unit, verbose, show_momentum_sum, show_mass)
end subroutine hard_interaction_write

```

Defined assignment. Deep copy (except for procedure pointers, of course).

```

<Hard interactions: public>+≡
public :: assignment(=)

<Hard interactions: interfaces>≡
interface assignment(=)
    module procedure hard_interaction_assign
end interface

<Hard interactions: procedures>+≡
subroutine hard_interaction_assign (hi_out, hi_in)
    type(hard_interaction_t), intent(out) :: hi_out
    type(hard_interaction_t), intent(in) :: hi_in
    hi_out%initialized = hi_in%initialized
    hi_out%data = hi_in%data
    hi_out%n_values = hi_in%n_values
    if (allocated (hi_in%flv)) then
        allocate (hi_out%flv (size (hi_in%flv)))
        hi_out%flv = hi_in%flv
    end if
    if (allocated (hi_in%hel)) then
        allocate (hi_out%hel (size (hi_in%hel)))
        hi_out%hel = hi_in%hel
    end if
    if (allocated (hi_in%col)) then
        allocate (hi_out%col (size (hi_in%col)))
        hi_out%col = hi_in%col
    end if
    hi_out%int = hi_in%int
    hi_out%eval_trace = hi_in%eval_trace
    hi_out%eval_sqme = hi_in%eval_sqme
    hi_out%eval_flows = hi_in%eval_flows
end subroutine hard_interaction_assign

```

13.2.3 Access contents

Whether we have a valid data set:

```

<Hard interactions: public>+≡
public :: hard_interaction_is_valid

<Hard interactions: procedures>+≡
function hard_interaction_is_valid (hi) result (flag)
    logical :: flag
    type(hard_interaction_t), intent(in) :: hi
    flag = hi%initialized

```

```
end function hard_interaction_is_valid
```

The alphanumeric ID.

```
<Hard interactions: public>+≡
public :: hard_interaction_get_id

<Hard interactions: procedures>+≡
function hard_interaction_get_id (hi) result (id)
  type(string_t) :: id
  type(hard_interaction_t), intent(in) :: hi
  id = hi%data%id
end function hard_interaction_get_id
```

The model as used for the hard interaction.

```
<Hard interactions: public>+≡
public :: hard_interaction_get_model_ptr

<Hard interactions: procedures>+≡
function hard_interaction_get_model_ptr (hi) result (model)
  type(model_t), pointer :: model
  type(hard_interaction_t), intent(in) :: hi
  model => hi%data%model
end function hard_interaction_get_model_ptr
```

Particle counts.

```
<Hard interactions: public>+≡
public :: hard_interaction_get_n_in
public :: hard_interaction_get_n_out
public :: hard_interaction_get_n_tot

<Hard interactions: procedures>+≡
pure function hard_interaction_get_n_in (hi) result (n_in)
  integer :: n_in
  type(hard_interaction_t), intent(in) :: hi
  n_in = hi%data%n_in
end function hard_interaction_get_n_in

pure function hard_interaction_get_n_out (hi) result (n_out)
  integer :: n_out
  type(hard_interaction_t), intent(in) :: hi
  n_out = hi%data%n_out
end function hard_interaction_get_n_out

pure function hard_interaction_get_n_tot (hi) result (n_tot)
  integer :: n_tot
  type(hard_interaction_t), intent(in) :: hi
  n_tot = hi%data%n_tot
end function hard_interaction_get_n_tot
```

Quantum number counts.

```
<Hard interactions: public>+≡
public :: hard_interaction_get_n_flv
public :: hard_interaction_get_n_col
public :: hard_interaction_get_n_hel
```



```

⟨Hard interactions: procedures⟩+≡
  pure function hard_interaction_get_n_flv (hi) result (n_flv)
    integer :: n_flv
    type(hard_interaction_t), intent(in) :: hi
    n_flv = hi%data%n_flv
  end function hard_interaction_get_n_flv

  pure function hard_interaction_get_n_col (hi) result (n_col)
    integer :: n_col
    type(hard_interaction_t), intent(in) :: hi
    n_col = hi%data%n_col
  end function hard_interaction_get_n_col

  pure function hard_interaction_get_n_hel (hi) result (n_hel)
    integer :: n_hel
    type(hard_interaction_t), intent(in) :: hi
    n_hel = hi%data%n_hel
  end function hard_interaction_get_n_hel

```

Particle tables.

```

⟨Hard interactions: public⟩+≡
  public :: hard_interaction_get_flv_states

⟨Hard interactions: procedures⟩+≡
  function hard_interaction_get_flv_states (hi) result (flv_state)
    integer, dimension(:,:), allocatable :: flv_state
    type(hard_interaction_t), intent(in) :: hi
    allocate (flv_state (size (hi%data%flv_state, 1), &
                             size (hi%data%flv_state, 2)))
    flv_state = hi%data%flv_state
  end function hard_interaction_get_flv_states

```

Color factor tables.

```

⟨Hard interactions: public⟩+≡
  public :: hard_interaction_get_n_cf

⟨Hard interactions: procedures⟩+≡
  pure function hard_interaction_get_n_cf (hi) result (n_cf)
    integer :: n_cf
    type(hard_interaction_t), intent(in) :: hi
    n_cf = hi%data%n_cf
  end function hard_interaction_get_n_cf

```

Incoming particles. Consider only the first entry in the array of flavor combinations.

If the process is forbidden and no flavor states are present, create at least an initial state with undefined particles.

```

⟨Hard interactions: public⟩+≡
  public :: hard_interaction_get_first_pdg_in

⟨Hard interactions: procedures⟩+≡
  function hard_interaction_get_first_pdg_in (hi) result (pdg)
    integer, dimension(:), allocatable :: pdg

```

```

type(hard_interaction_t), intent(in) :: hi
allocate (pdg (hi%data%n_in))
if (hi%data%n_flv > 0) then
    pdg = hi%data%flv_state (:hi%data%n_in, 1)
else
    pdg = 0
end if
end function hard_interaction_get_first_pdg_in

```

The analogous function for outgoing particles. Again, only the first entry in the array of flavor combinations.

```

<Hard interactions: public>+≡
public :: hard_interaction_get_first_pdg_out

<Hard interactions: procedures>+≡
function hard_interaction_get_first_pdg_out (hi) result (pdg)
    integer, dimension(:), allocatable :: pdg
    type(hard_interaction_t), intent(in) :: hi
    allocate (pdg (hi%data%n_out))
    if (hi%data%n_flv > 0) then
        pdg = hi%data%flv_state (hi%data%n_in+1:hi%data%n_tot, 1)
    else
        pdg = 0
    end if
end function hard_interaction_get_first_pdg_out

```

This procedure is used for checking whether some of the final-state particles can initiate decay cascades. We check only the first row in the flavor array, since unstable particles are massive and should not be subject to flavor summation. Thus they must be common to all rows.

```

<Hard interactions: public>+≡
public :: hard_interaction_get_unstable_products

<Hard interactions: procedures>+≡
subroutine hard_interaction_get_unstable_products (hi, flv_unstable)
    type(hard_interaction_t), intent(in) :: hi
    type(flavor_t), dimension(:), intent(out), allocatable :: flv_unstable
    type(model_t), pointer :: model
    integer, dimension(hi%data%n_out) :: pdg_out
    type(flavor_t) :: flv
    integer :: i
    model => hi%data%model
    if (associated (model) .and. size (hi%data%flv_state, 2) /= 0) then
        pdg_out = hi%data%flv_state(hi%data%n_in+1:,1)
        do i = 1, size (pdg_out)
            if (pdg_out(i) /= 0) then
                call flavor_init (flv, pdg_out(i), model)
                if (flavor_is_stable (flv)) then
                    where (pdg_out(i:) == pdg_out(i)) pdg_out(i:) = 0
                else
                    where (pdg_out(i+1:) == pdg_out(i)) pdg_out(i+1:) = 0
                end if
            end if
        end do
    end if
end subroutine hard_interaction_get_unstable_products

```

```

        end do
        allocate (flv_unstable (count (pdg_out /= 0)))
        call flavor_init &
            (flv_unstable, pack (pdg_out, pdg_out /= 0), model)
    else
        allocate (flv_unstable (0))
    end if
end subroutine hard_interaction_get_unstable_products

```

13.2.4 Evaluators

This procedure initializes the evaluator that computes the matrix element squared, traced over all outgoing quantum numbers. Whether the trace over incoming quantum numbers is done, depends on the specified mask – except for color which is always summed.

```

<Hard interactions: public>+≡
    public :: hard_interaction_init_trace

<Hard interactions: procedures>+≡
    subroutine hard_interaction_init_trace &
        (hi, qn_mask_in, use_hi_color_factors, nc)
        type(hard_interaction_t), intent(inout), target :: hi
        type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
        logical, intent(in), optional :: use_hi_color_factors
        integer, intent(in), optional :: nc
        logical :: use_hi_cf
        type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
        if (present (use_hi_color_factors)) then
            use_hi_cf = use_hi_color_factors
        else
            use_hi_cf = .false.
        end if
        allocate (qn_mask (hi%data%n_tot))
        qn_mask(:hi%data%n_in) = &
            new_quantum_numbers_mask (.false., .true., .false.) &
            .or. qn_mask_in
        qn_mask(hi%data%n_in+1:) = &
            new_quantum_numbers_mask (.true., .true., .true.)
        if (use_hi_cf) then
            call evaluator_init_square (hi%eval_trace, hi%int, qn_mask, &
                hi%data%col_flow_index, hi%data%col_factor, hi%col, nc=nc)
        else
            call evaluator_init_square (hi%eval_trace, hi%int, qn_mask, nc=nc)
        end if
    end subroutine hard_interaction_init_trace

```

This procedure initializes the evaluator that computes the matrix element square separated in parts (e.g., polarization components). Polarization is kept in the initial state (if allowed by `qn_mask_in`) and for those final-state particles which are marked as unstable. The incoming-particle mask can also be used to sum over incoming flavor.

```

<Hard interactions: public>+≡

```

```

public :: hard_interaction_init_sqme
<Hard interactions: procedures>+≡
subroutine hard_interaction_init_sqme &
    (hi, qn_mask_in, use_hi_color_factors, nc)
    type(hard_interaction_t), intent(inout), target :: hi
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
    logical, intent(in), optional :: use_hi_color_factors
    integer, intent(in), optional :: nc
    logical :: use_hi_cf
    type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask
    type(flavor_t), dimension(:), allocatable :: flv
    integer :: i
    logical :: helmask, helmask_hd
    if (present (use_hi_color_factors)) then
        use_hi_cf = use_hi_color_factors
    else
        use_hi_cf = .false.
    end if
    allocate (qn_mask (hi%data%n_tot), flv (hi%data%n_flv))
    qn_mask(:hi%data%n_in) = &
        new_quantum_numbers_mask (.false., .true., .false.) &
        .or. qn_mask_in
    do i = hi%data%n_in + 1, hi%data%n_tot
        call flavor_init (flv, hi%data%flv_state(i,:), hi%data%model)
        if (.not. all (flavor_is_stable (flv))) then
            helmask = all (flavor_decays_isotropically (flv))
            helmask_hd = all (flavor_decays_diagonal (flv))
        else
            helmask = all (.not. flavor_is_polarized (flv))
            helmask_hd = .true.
        end if
        qn_mask(i) = new_quantum_numbers_mask (.false., .true., &
            helmask, mask_hd = helmask_hd)
    end do
    if (use_hi_cf) then
        call evaluator_init_square (hi%eval_sqme, hi%int, qn_mask, &
            hi%data%col_flow_index, hi%data%col_factor, hi%col, nc=nc)
    else
        call evaluator_init_square (hi%eval_sqme, hi%int, qn_mask, nc=nc)
    end if
end subroutine hard_interaction_init_sqme

```

This procedure initializes the evaluator that computes the contributions to color flows, neglecting color interference. The incoming-particle mask can be used to sum over incoming flavor.

```

<Hard interactions: public>+≡
public :: hard_interaction_init_flows
<Hard interactions: procedures>+≡
subroutine hard_interaction_init_flows (hi, qn_mask_in)
    type(hard_interaction_t), intent(inout), target :: hi
    type(quantum_numbers_mask_t), dimension(:), intent(in) :: qn_mask_in
    type(quantum_numbers_mask_t), dimension(:), allocatable :: qn_mask

```

```

type(flavor_t), dimension(:), allocatable :: flv
integer :: i
logical :: helmask, helmask_hd
allocate (qn_mask (hi%data%n_tot), flv (hi%data%n_flv))
qn_mask(:hi%data%n_in) = &
    new_quantum_numbers_mask (.false., .false., .false.) &
    .or. qn_mask_in
do i = hi%data%n_in + 1, hi%data%n_tot
    call flavor_init (flv, hi%data%flv_state(i,:), hi%data%model)
    if (.not. all (flavor_is_stable (flv))) then
        helmask = all (flavor_decays_isotropically (flv))
        helmask_hd = all (flavor_decays_diagonal (flv))
    else
        helmask = all (.not. flavor_is_polarized (flv))
        helmask_hd = .true.
    end if
    qn_mask(i) = new_quantum_numbers_mask (.false., .false., &
        helmask, mask_hd = helmask_hd)
end do
call evaluator_init_square (hi%eval_flows, hi%int, qn_mask, &
    expand_color_flows = .true.)
end subroutine hard_interaction_init_flows

```

Finalize the previous evaluators.

```

<Hard interactions: public>+≡
    public :: hard_interaction_final_sqme
    public :: hard_interaction_final_flows

<Hard interactions: procedures>+≡
    subroutine hard_interaction_final_sqme (hi)
        type(hard_interaction_t), intent(inout) :: hi
        call evaluator_final (hi%eval_sqme)
    end subroutine hard_interaction_final_sqme

    subroutine hard_interaction_final_flows (hi)
        type(hard_interaction_t), intent(inout) :: hi
        call evaluator_final (hi%eval_flows)
    end subroutine hard_interaction_final_flows

```

13.2.5 Matrix-element evaluation

Update the α_s value used by the matrix element (if any).

```

<Hard interactions: public>+≡
    public :: hard_interaction_update_alpha_s

<Hard interactions: procedures>+≡
    subroutine hard_interaction_update_alpha_s (hi, alpha_s)
        type(hard_interaction_t), intent(inout) :: hi
        real(default), intent(in) :: alpha_s
        real(c_default_float) :: c_alpha_s
        c_alpha_s = alpha_s
        call hi%data% update_alpha_s (c_alpha_s)
    end subroutine hard_interaction_update_alpha_s

```

Reset the helicity selection counters that are used to speed up things by dropping zero helicity channels after `cutoff` tries.

```

<Hard interactions: public>+≡
    public :: hard_interaction_reset_helicity_selection

<Hard interactions: procedures>+≡
    subroutine hard_interaction_reset_helicity_selection (hi, threshold, cutoff)
        type(hard_interaction_t), intent(inout) :: hi
        real(default), intent(in) :: threshold
        integer, intent(in) :: cutoff
        real(c_default_float) :: c_threshold
        integer(c_int) :: c_cutoff
        c_threshold = threshold
        c_cutoff = cutoff
        call hi%data% reset_helicity_selection (c_threshold, c_cutoff)
    end subroutine hard_interaction_reset_helicity_selection

```

This interfaces the matrix element proper. First, we request a new matrix element value to be computed from the given momenta. Then, we extract all values that are known to be allowed and assign them to the matrix element array. This array consists of pointers to the interaction values, so in fact the latter are calculated.

Although it may be irrelevant, this is an obvious place for parallel execution, so write a `forall` assignment. Making the assignment elemental is not possible because `get_amplitude` is a procedure pointer. [This is deactivated; to be checked again.]

After the matrix element data are read, we evaluate the squared matrix element (`eval_trace`). square and the color-flow coefficients.

```

<Hard interactions: public>+≡
    public :: hard_interaction_evaluate

<Hard interactions: procedures>+≡
    subroutine hard_interaction_evaluate (hi)
        type(hard_interaction_t), intent(inout), target :: hi
        integer :: i
        complex(default) :: val
        call hi%data% new_event &
            (array_from_vector4 (interaction_get_momenta (hi%int)))
        ! forall (i = 1:hi%n_values)
        !     hi%me(i) = hi%data% get_amplitude (hi%flv(i), hi%hel(i), hi%col(i))
        ! end forall
        do i = 1, hi%n_values
            val = hi%data% get_amplitude (hi%flv(i), hi%hel(i), hi%col(i))
            call interaction_set_matrix_element (hi%int, i, val)
        end do
        call evaluator_evaluate (hi%eval_trace)
    end subroutine hard_interaction_evaluate

```

The extra evaluators (squared matrix element without trace, color flows) need only be evaluated for simulation events that pass the unweighting step. This follows the previous routine.

```

<Hard interactions: public>+≡

```

```

public :: hard_interaction_evaluate_sqme
public :: hard_interaction_evaluate_flows
<Hard interactions: procedures>+≡
subroutine hard_interaction_evaluate_sqme (hi)
  type(hard_interaction_t), intent(inout), target :: hi
  call evaluator_receive_momenta (hi%eval_sqme)
  call evaluator_evaluate (hi%eval_sqme)
end subroutine hard_interaction_evaluate_sqme

subroutine hard_interaction_evaluate_flows (hi)
  type(hard_interaction_t), intent(inout), target :: hi
  call evaluator_receive_momenta (hi%eval_flows)
  call evaluator_evaluate (hi%eval_flows)
end subroutine hard_interaction_evaluate_flows

```

This provides direct access to the matrix element, squared and traced over all quantum numbers. It is not used for ordinary evaluation.

```

<Hard interactions: public>+≡
public :: hard_interaction_compute_sqme_sum
<Hard interactions: procedures>+≡
function hard_interaction_compute_sqme_sum (hi, p) result (sqme)
  real(default) :: sqme
  type(hard_interaction_t), intent(inout), target :: hi
  type(vector4_t), dimension(:), intent(in) :: p
  call interaction_set_momenta (hi%int, p)
  call hard_interaction_evaluate (hi)
  sqme = evaluator_sum (hi%eval_trace)
end function hard_interaction_compute_sqme_sum

```

13.2.6 Access results

```

<Hard interactions: public>+≡
public :: hard_interaction_get_int_ptr
<Hard interactions: procedures>+≡
function hard_interaction_get_int_ptr (hi) result (int)
  type(interaction_t), pointer :: int
  type(hard_interaction_t), intent(in), target :: hi
  int => hi%int
end function hard_interaction_get_int_ptr

<Hard interactions: public>+≡
public :: hard_interaction_get_eval_trace_ptr
public :: hard_interaction_get_eval_sqme_ptr
public :: hard_interaction_get_eval_flows_ptr
<Hard interactions: procedures>+≡
function hard_interaction_get_eval_trace_ptr (hi) result (eval)
  type(evaluator_t), pointer :: eval
  type(hard_interaction_t), intent(in), target :: hi
  eval => hi%eval_trace
end function hard_interaction_get_eval_trace_ptr

```

```

function hard_interaction_get_eval_sqme_ptr (hi) result (eval)
  type(evaluator_t), pointer :: eval
  type(hard_interaction_t), intent(in), target :: hi
  eval => hi%eval_sqme
end function hard_interaction_get_eval_sqme_ptr

function hard_interaction_get_eval_flows_ptr (hi) result (eval)
  type(evaluator_t), pointer :: eval
  type(hard_interaction_t), intent(in), target :: hi
  eval => hi%eval_flows
end function hard_interaction_get_eval_flows_ptr

```

13.2.7 Reconstruction

Reconstruct the kinematics of the hard interaction from a given particle set. The particle set may have been decayed, and the particle order is not necessarily correct.

```

<Hard interactions: public>+≡
  public :: hard_interaction_recover_kinematics

<Hard interactions: procedures>+≡
  subroutine hard_interaction_recover_kinematics (hi, pset)
    type(hard_interaction_t), intent(inout) :: hi
    type(particle_set_t), intent(in) :: pset
    call particle_set_extract_interaction (pset, hi%int, hi%data%flv_state)
  end subroutine hard_interaction_recover_kinematics

```

13.2.8 Process summary

Write an account of the allowed quantum numbers.

```

<Hard interactions: public>+≡
  public :: hard_interaction_write_state_summary

<Hard interactions: procedures>+≡
  subroutine hard_interaction_write_state_summary (hi, unit)
    type(hard_interaction_t), intent(in), target :: hi
    integer, intent(in), optional :: unit
    type(state_iterator_t) :: it
    integer :: u, i, f, h, c
    character(1) :: sgn
    u = output_unit (unit)
    call state_iterator_init (it, interaction_get_state_matrix_ptr (hi%int))
    do while (state_iterator_is_valid (it))
      i = state_iterator_get_me_index (it)
      f = hi%flv(i)
      h = hi%hel(i)
      c = hi%col(i)
      if (hi%data% is_allowed (f, h, c)) then
        sgn = "+"
      else

```



```

        sgn = " "
    end if
    write (u, "(1x,A1,1x,I0,2x)", advance="no") sgn, i
    call quantum_numbers_write (state_iterator_get_quantum_numbers (it), u)
    write (u, *)
    call state_iterator_advance (it)
end do
end subroutine hard_interaction_write_state_summary

```

13.2.9 Test

<Hard interactions: public>+≡

```
public :: hard_interaction_test
```

<Hard interactions: procedures>+≡

```

subroutine hard_interaction_test (model)
    type(model_t), target :: model
    type(process_library_t), pointer :: prc_lib => null ()
    type(os_data_t), pointer :: os_data => null ()
    type(hard_interaction_t), pointer :: hi => null ()
    type(var_list_t), pointer :: var_list => null ()
    type(vector4_t), dimension(4) :: p
    type(quantum_numbers_mask_t), dimension(2) :: qn_mask_in
    type(quantum_numbers_mask_t), dimension(4) :: qn_mask
    real(default) :: sqme, mh
    allocate (hi)
    allocate (prc_lib)
    allocate (os_data)
    allocate (var_list)
    call os_data_init (os_data)
    call msg_message ("*** Load library 'test_me'")
    call msg_message &
        ("      [must exist and contain process 'test_me_eemm' (test_me.sin)]")
    call var_list_append_string &
        (var_list, name = "$library_name", sval = "test_me") ! $
    call process_library_init (prc_lib, var_str("test_me"), os_data)
    call process_library_load (prc_lib, os_data, var_list = var_list)
    call msg_message ()
    call msg_message ("*** Create hard interaction")
    call hard_interaction_init (hi, prc_lib, 1, var_str ("test_me_eemm"), model)
    qn_mask_in = new_quantum_numbers_mask (.true., .true., .true.)
    call hard_interaction_init_trace (hi, qn_mask_in)
    print *, "Interaction: n_values = ", &
        interaction_get_n_matrix_elements (hi%int)
    qn_mask_in = new_quantum_numbers_mask (.false., .false., .false., .true.)
    call hard_interaction_init_sqme (hi, qn_mask_in)
    call hard_interaction_init_flows (hi, qn_mask_in)
    p(1) = vector4_moving (250._default, 250._default, 3)
    p(2) = vector4_moving (250._default, -250._default, 3)
    p(3) = rotation (1._default, 1) * p(1)
    p(4) = p(1) + p(2) - p(3)
    call msg_message ()
    call msg_message ("*** Evaluate new event")

```

```

    sqme = hard_interaction_compute_sqme_sum (hi, p)
    call hard_interaction_evaluate_sqme (hi)
    call hard_interaction_evaluate_flows (hi)
    call hard_interaction_write (hi)
    print *
    print *, "sqme sum =", sqme
    print *
    print *, "*** Cleanup"
    call hard_interaction_final (hi)
    call process_library_final (prc_lib)
end subroutine hard_interaction_test

```

13.3 Processes

This module combines hard interactions, phase space, and (for scatterings) structure functions and interfaces them to the VAMP integration module.

<processes.f90>≡
<File header>

```

module processes

```

```

<Use kinds>

```

```

<Use strings>

```

```

    use limits, only: GML_MIN_RANGE_RATIO !NODEP!
    use system_dependencies !NODEP!
    use constants !NODEP!

```

```

<Use file utils>

```

```

    use diagnostics !NODEP!
    use sm_physics !NODEP!
    use vamp_equivalences !NODEP!
    use vamp !NODEP!
    use tao_random_numbers !NODEP!
    use pdf_builtin !NODEP!
    use md5
    use cputime
    use os_interface
    use lexers
    use parser
    use lorentz !NODEP!
    use subevents
    use variables
    use expressions
    use models
    use flavors
    use quantum_numbers
    use polarizations
    use interactions
    use evaluators
    use particles
    use beams
    use sf_isr

```

```

use sf_epa
use sf_ewa
use sf_circe1
use sf_circe2
use sf_escan
use sf_beam_events
use sf_lhapdf
use sf_pdf_builtin
use sf_user
use strfun
use mappings
use phs_forests
use cascades
use process_libraries
use prclib_interfaces
use hard_interactions

⟨Standard module head⟩

⟨Processes: public⟩

⟨Processes: parameters⟩

⟨Processes: types⟩

⟨Processes: variables⟩

⟨Processes: interfaces⟩

contains

⟨Processes: procedures⟩

end module processes

```

13.3.1 Integration results

This object collects the results of an integration pass and makes them available to the outside.

The results object has to distinguish the process type:

```

⟨Processes: parameters⟩≡
  integer, parameter :: PRC_UNKNOWN = 0
  integer, parameter :: PRC_DECAY = 1
  integer, parameter :: PRC_SCATTERING = 2

```

We store the process type, the index of the integration pass and the absolute iteration index, the number of iterations contained in this result (for averages), and the integral (cross section or partial width), error estimate, efficiency and time estimate.

For intermediate results, we set a flag if this result is an improvement w.r.t. previous ones.

The process type indicates decay or scattering. Dummy entries (skipped iterations) have a process type of PRC_UNKNOWN.

(Processes: types)≡

```

type :: integration_entry_t
  private
  integer :: process_type = PRC_UNKNOWN
  integer :: pass = 0
  integer :: it = 0
  integer :: n_it = 0
  integer :: n_calls = 0
  logical :: improved = .false.
  real(default) :: integral = 0
  real(default) :: error = 0
  real(default) :: efficiency = 0
  real(default) :: chi2 = 0
  real(default), dimension(:), allocatable :: grove_weight
  type(time_t) :: time_start
  type(time_t) :: time_end
end type integration_entry_t

```

Initialize with all relevant data

(Processes: procedures)≡

```

subroutine integration_entry_init (entry, &
  process_type, pass, it, n_it, n_calls, improved, &
  integral, error, efficiency, chi2, grove_weight, &
  time_start, time_end)
  type(integration_entry_t), intent(out) :: entry
  integer, intent(in) :: process_type, pass, it, n_it, n_calls
  logical, intent(in) :: improved
  real(default), intent(in) :: integral, error, efficiency
  real(default), intent(in), optional :: chi2
  real(default), dimension(:), intent(in), optional :: grove_weight
  type(time_t), intent(in), optional :: time_start, time_end
  integer :: n_groves
  entry%process_type = process_type
  entry%pass = pass
  entry%it = it
  entry%n_it = n_it
  entry%n_calls = n_calls
  entry%improved = improved
  entry%integral = integral
  entry%error = error
  entry%efficiency = efficiency
  if (present (chi2)) &
    entry%chi2 = chi2
  if (present (grove_weight)) then
    n_groves = size (grove_weight)
    allocate (entry%grove_weight (n_groves))
    entry%grove_weight = grove_weight
  end if
  if (present (time_start) .and. present (time_end)) then
    entry%time_start = time_start
    entry%time_end = time_end
  end if
end subroutine

```

```

        end if
    end subroutine integration_entry_init

```

Access values, some of them computed on demand:

(Processes: procedures)+≡

```

    elemental function integration_entry_get_pass (entry) result (n)
        integer :: n
        type(integration_entry_t), intent(in) :: entry
        n = entry%pass
    end function integration_entry_get_pass

    elemental function integration_entry_get_n_calls (entry) result (n)
        integer :: n
        type(integration_entry_t), intent(in) :: entry
        n = entry%n_calls
    end function integration_entry_get_n_calls

    elemental function integration_entry_get_integral (entry) result (int)
        real(default) :: int
        type(integration_entry_t), intent(in) :: entry
        int = entry%integral
    end function integration_entry_get_integral

    elemental function integration_entry_get_error (entry) result (err)
        real(default) :: err
        type(integration_entry_t), intent(in) :: entry
        err = entry%error
    end function integration_entry_get_error

    elemental function integration_entry_get_relative_error (entry) result (err)
        real(default) :: err
        type(integration_entry_t), intent(in) :: entry
        if (entry%integral /= 0) then
            err = entry%error / entry%integral
        else
            err = 0
        end if
    end function integration_entry_get_relative_error

    elemental function integration_entry_get_accuracy (entry) result (acc)
        real(default) :: acc
        type(integration_entry_t), intent(in) :: entry
        acc = accuracy (entry%integral, entry%error, entry%n_calls)
    end function integration_entry_get_accuracy

    elemental function accuracy (integral, error, n_calls) result (acc)
        real(default) :: acc
        real(default), intent(in) :: integral, error
        integer, intent(in) :: n_calls
        if (integral /= 0) then
            acc = error / integral * sqrt (real (n_calls, default))
        else
            acc = 0
        end if
    end function accuracy

```

```

end function accuracy

elemental function integration_entry_get_efficiency (entry) result (eff)
  real(default) :: eff
  type(integration_entry_t), intent(in) :: entry
  eff = entry%efficiency
end function integration_entry_get_efficiency

elemental function integration_entry_get_chi2 (entry) result (chi2)
  real(default) :: chi2
  type(integration_entry_t), intent(in) :: entry
  chi2 = entry%chi2
end function integration_entry_get_chi2

elemental function integration_entry_get_time_per_event (entry) result (tpe)
  real(default) :: tpe
  type(integration_entry_t), intent(in) :: entry
  real(default) :: time_in_seconds
  if (entry%n_calls /= 0 .and. entry%efficiency /= 0) then
    time_in_seconds = entry%time_end - entry%time_start
    tpe = time_in_seconds / entry%n_calls / entry%efficiency
  else
    tpe = 0
  end if
end function integration_entry_get_time_per_event

elemental function integration_entry_has_improved (entry) result (flag)
  logical :: flag
  type(integration_entry_t), intent(in) :: entry
  flag = entry%improved
end function integration_entry_has_improved

elemental function integration_entry_get_n_groves (entry) result (n_groves)
  integer :: n_groves
  type(integration_entry_t), intent(in) :: entry
  if (allocated (entry%grove_weight)) then
    n_groves = size (entry%grove_weight)
  else
    n_groves = 0
  end if
end function integration_entry_get_n_groves

```

Output. This writes the header line for the result account below:

(Processes: procedures)+≡

```

subroutine write_header (process_type, unit, logfile)
  integer, intent(in) :: process_type
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: logfile
  character(5) :: phys_unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  select case (process_type)
    case (PRC_DECAY); phys_unit = "[GeV]"
    case (PRC_SCATTERING); phys_unit = "[fb] "

```

```

case default
    phys_unit = ""
end select
write (msg_buffer, "(A)") &
    "It      Calls  Integral" // phys_unit // &
    " Error" // phys_unit // &
    " Err[%]   Acc  Eff[%]   Chi2 N[It] |"
call msg_message (unit=u, logfile=logfile)
end subroutine write_header

```

This writes a separator for result display:

(Processes: procedures)+≡

```

subroutine write_hline (unit)
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write (u, "(A)")  "|" // (repeat("-", 77)) // "|"
    flush (u)
end subroutine write_hline

subroutine write_dline (unit)
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write (u, "(A)")  "|" // (repeat("=", 77)) // "|"
    flush (u)
end subroutine write_dline

```

This writes the standard result account into one screen line. The verbose version uses multiple lines and prints the unabridged values. Dummy entries are not written.

(Processes: procedures)+≡

```

subroutine integration_entry_write (entry, unit, verbose)
    type(integration_entry_t), intent(in) :: entry
    integer, intent(in), optional :: unit
    logical, intent(in), optional :: verbose
    integer :: u
    character(1) :: star
    logical :: verb
    u = output_unit (unit); if (u < 0) return
    verb = .false.; if (present (verbose)) verb = verbose
    if (verb) then
        write (u, *) "process_type = ", entry%process_type
        write (u, *) "      pass = ", entry%pass
        write (u, *) "      it = ", entry%it
        write (u, *) "      n_it = ", entry%n_it
        write (u, *) "      n_calls = ", entry%n_calls
        write (u, *) "      improved = ", entry%improved
        write (u, *) "      integral = ", entry%integral
        write (u, *) "      error = ", entry%error
        write (u, *) "      efficiency = ", entry%efficiency
        write (u, *) "      chi2 = ", entry%chi2
        if (allocated (entry%grove_weight)) then

```

```

        write (u, *) "    n_groves = ", size (entry%grove_weight)
        write (u, *) "grove_weight = ", entry%grove_weight
    else
        write (u, *) "    n_groves = 0"
    end if
else if (entry%process_type /= PRC_UNKNOWN) then
    if (entry%improved) then
        star = "*"
    else
        star = " "
    end if
1   format (1x, I3, 1x, I10, 1x, 1PE14.7, 1x, 1PE9.2, 1x, 2PF7.2, &
        1x, OPF7.2, A1, 1x, 2PF6.2, 1x, OPF7.2, 1x, I3)
    if (entry%n_it /= 1) then
        write (u, 1) &
            entry%it, &
            entry%n_calls, &
            entry%integral, &
            abs(entry%error), &
            abs(integration_entry_get_relative_error (entry)), &
            abs(integration_entry_get_accuracy (entry)), &
            star, &
            entry%efficiency, &
            entry%chi2, &
            entry%n_it
    else
        write (u, 1) &
            entry%it, &
            entry%n_calls, &
            entry%integral, &
            abs(entry%error), &
            abs(integration_entry_get_relative_error (entry)), &
            abs(integration_entry_get_accuracy (entry)), &
            star, &
            entry%efficiency
    end if
end if
flush (u)
end subroutine integration_entry_write

```

Read the entry, assuming it has been written in verbose format.

(*Processes: procedures*) \equiv

```

subroutine integration_entry_read (entry, unit)
    type(integration_entry_t), intent(out) :: entry
    integer, intent(in) :: unit
    character(30) :: dummy
    character :: equals
    integer :: n_groves
    read (unit, *) dummy, equals, entry%process_type
    read (unit, *) dummy, equals, entry%pass
    read (unit, *) dummy, equals, entry%it
    read (unit, *) dummy, equals, entry%n_it
    read (unit, *) dummy, equals, entry%n_calls
    read (unit, *) dummy, equals, entry%improved

```



```

read (unit, *) dummy, equals, entry%integral
read (unit, *) dummy, equals, entry%error
read (unit, *) dummy, equals, entry%efficiency
read (unit, *) dummy, equals, entry%chi2
read (unit, *) dummy, equals, n_groves
if (n_groves /= 0) then
  allocate (entry%grove_weight (n_groves))
  read (unit, *) dummy, equals, entry%grove_weight
end if
end subroutine integration_entry_read

```

Write an account of the channel weights, accumulated by groves.

```

<Processes: procedures>+=
subroutine integration_entry_write_grove_weights (entry, unit)
  type(integration_entry_t), intent(in) :: entry
  integer, intent(in), optional :: unit
  integer :: n_groves
  character(20) :: fmt
  integer :: u
  u = output_unit (unit); if (u < 0) return
  if (allocated (entry%grove_weight)) then
    n_groves = size (entry%grove_weight)
    write (fmt, "(A,I0,A)") "(" , n_groves, "(1x,I3))"
    write (u, fmt) nint (entry%grove_weight * 100)
  end if
! contains
!   function get_ifmt (n) result (fmt)
!     character(2) :: fmt
!     integer, intent(in) :: n
!     character(20) :: tmp_str
!     integer :: ilen
!     write (tmp_str, "(I0)") n
!     ilen = len_trim (tmp_str)
!     write (fmt, "(A1,I1)") "I", ilen
!   end function get_ifmt
end subroutine integration_entry_write_grove_weights

```

Compute the average for all entries in the specified integration pass. The integrals are weighted w.r.t. their individual errors, and we compute average, error of the average, and χ^2 value. All errors are assumed Gaussian, of course. The efficiency returned is the one of the last entry in the integration pass. For the time estimate, we simply take the minimum of all which should correspond to the best efficiency.

If any integral or error vanishes, averaging fails.

```

<Processes: procedures>+=
function compute_average (entry, pass) result (result)
  type(integration_entry_t) :: result
  type(integration_entry_t), dimension(:), intent(in) :: entry
  integer, intent(in) :: pass
  integer :: i
  logical, dimension(size(entry)) :: mask
  real(default), dimension(size(entry)) :: ivar

```

```

real(default) :: sum_ivar, variance
result%process_type = entry(1)%process_type
result%pass = pass
mask = entry%pass == pass .and. entry%process_type /= PRC_UNKNOWN
result%it = maxval (entry%it, mask)
result%n_it = count (mask)
result%n_calls = sum (entry%n_calls, mask)
where (entry%error /= 0)
    ivar = 1 / entry%error ** 2
elsewhere
    ivar = 0
end where
sum_ivar = sum (ivar, mask)
if (sum_ivar /= 0) then
    variance = 1 / sum_ivar
else
    variance = 0
end if
result%integral = sum (entry%integral * ivar, mask) * variance
result%error = sqrt (variance)
if (result%n_it > 1) then
    result%chi2 = sum ((entry%integral - result%integral)**2 * ivar, mask) &
        / (result%n_it - 1)
end if
do i = size (entry), 1, -1
    if (mask(i)) then
        result%efficiency = entry(i)%efficiency
        exit
    end if
end do
end function compute_average

```

13.3.2 Combined integration results

We collect a list of results which grows during the execution of the program. This is implemented as an array which grows if necessary; so we can easily compute averages.

```

<Processes: public>≡
    public :: integration_results_t

<Processes: types>+≡
    type :: integration_results_t
    private
        integer :: n_pass = 0
        integer :: n_it = 0
        type(integration_entry_t), dimension(:), allocatable :: entry
        type(integration_entry_t), dimension(:), allocatable :: average
    end type integration_results_t

```

The array is extended in chunks of 10 entries.

```

<Processes: parameters>+≡
    integer, parameter :: RESULTS_CHUNK_SIZE = 10

```

The standard does not require to explicitly initialize the integers; however, some gfortran version has a bug here and misses the default initialization in the type definition.

(Processes: procedures)+≡

```

subroutine integration_results_init (results)
  type(integration_results_t), intent(out) :: results
  results%n_pass = 0
  results%n_it = 0
  allocate (results%entry (RESULTS_CHUNK_SIZE))
  allocate (results%average (RESULTS_CHUNK_SIZE))
end subroutine integration_results_init

```

Output (ASCII format).

(Processes: procedures)+≡

```

subroutine integration_results_write (results, unit, verbose)
  type(integration_results_t), intent(in) :: results
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: verbose
  logical :: verb
  integer :: u, n
  real(default) :: time_per_event
  u = output_unit (unit); if (u < 0) return
  verb = .false.; if (present (verbose)) verb = verbose
  if (.not. verb) then
    call write_dline (unit)
    if (results%n_it /= 0) then
      call write_header (results%entry(1)%pass, unit)
      call write_dline (unit)
      do n = 1, results%n_it
        if (n > 1) then
          if (results%entry(n)%pass /= results%entry(n-1)%pass) then
            call write_hline (unit)
            call integration_entry_write &
              (results%average(results%entry(n-1)%pass), unit)
            call write_hline (unit)
          end if
        end if
        call integration_entry_write (results%entry(n), unit)
      end do
      call write_dline(unit)
      call integration_entry_write (results%average(results%n_pass), unit)
      call write_dline(unit)
    else
      call msg_message ("[WHIZARD integration results: empty]", unit)
    end if
    call write_dline (unit)
  else
    write (u, *) "begin(integration_results)"
    write (u, *) "  n_pass = ", results%n_pass
    write (u, *) "    n_it = ", results%n_it
    if (results%n_it > 0) then
      write (u, *) "begin(integration_pass)"
    end if
  end if
end subroutine integration_results_write

```

```

do n = 1, results%n_it
  if (n > 1) then
    if (results%entry(n)%pass /= results%entry(n-1)%pass) then
      write (u, *) "end(integration_pass)"
      write (u, *) "begin(integration_pass)"
    end if
  end if
  write (u, *) "begin(iteration)"
  call integration_entry_write (results%entry(n), unit, verb)
  write (u, *) "end(iteration)"
end do
write (u, *) "end(integration_pass)"
end if
write (u, *) "end(integration_results)"
end if
flush (u)
end subroutine integration_results_write

```

Incremental output: Write specific / last line. separator if appropriate.

(Processes: procedures)+≡

```

subroutine integration_results_write_entry (results, it, unit)
  type(integration_results_t), intent(in) :: results
  integer, intent(in) :: it
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  if (it /= 0) call integration_entry_write (results%entry(it), unit)
end subroutine integration_results_write_entry

subroutine integration_results_write_current (results, unit)
  type(integration_results_t), intent(in) :: results
  integer, intent(in), optional :: unit
  integer :: u, n
  u = output_unit (unit); if (u < 0) return
  n = results%n_it
  if (n /= 0) call integration_entry_write (results%entry(n), unit)
end subroutine integration_results_write_current

```

Write one line for the average

(Processes: procedures)+≡

```

subroutine integration_results_write_average (results, pass, unit)
  type(integration_results_t), intent(in) :: results
  integer, intent(in) :: pass
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  if (allocated (results%average) .and. pass /= 0) &
    call integration_entry_write (results%average(pass), unit)
end subroutine integration_results_write_average

subroutine integration_results_write_current_average (results, unit)
  type(integration_results_t), intent(in) :: results
  integer, intent(in), optional :: unit

```

```

integer :: u, n
u = output_unit (unit); if (u < 0) return
n = results%n_pass
if (allocated (results%average) .and. n /= 0) &
    call integration_entry_write (results%average(n), unit)
end subroutine integration_results_write_current_average

```

Write a concise table of grove weights, i.e., the channel history.

(Processes: procedures)+≡

```

subroutine integration_results_write_grove_weights (results, unit)
type(integration_results_t), intent(in) :: results
integer, intent(in), optional :: unit
integer :: u, i, n
u = output_unit (unit); if (u < 0) return
if (results%n_it /= 0) then
    call msg_message ("Phase-space grove weight history: " &
        // "(numbers in %)", unit)
    write (u, "(A9)", advance="no") "| grove |"
    do i = 1, integration_entry_get_n_groves (results%entry(1))
        write (u, "(1x,I3)", advance="no") i
    end do
    write (u, *)
    call write_dline (unit)
    do n = 1, results%n_it
        if (n > 1) then
            if (results%entry(n)%pass /= results%entry(n-1)%pass) then
                call write_hline (unit)
            end if
        end if
        write (u, "(1x,I6,1x,A1)", advance="no") n, "|"
        call integration_entry_write_grove_weights (results%entry(n), unit)
    end do
else
    call msg_message ("Channel weight history: [undefined]", unit)
end if
flush (u)
call write_dline(unit)
end subroutine integration_results_write_grove_weights

```

Read the list from file. The file must be written using the `verbose` option of the writing routine.

(Processes: procedures)+≡

```

subroutine integration_results_read (results, unit)
type(integration_results_t), intent(out) :: results
integer, intent(in) :: unit
character(80) :: buffer
character :: equals
integer :: pass, it
read (unit, *) buffer
if (trim (adjustl (buffer)) /= "begin(integration_results)") then
    call read_err (); return
end if
read (unit, *) buffer, equals, results%n_pass

```

```

read (unit, *) buffer, equals, results%n_it
allocate (results%entry (results%n_it + RESULTS_CHUNK_SIZE))
allocate (results%average (results%n_it + RESULTS_CHUNK_SIZE))
it = 0
do pass = 1, results%n_pass
  read (unit, *) buffer
  if (trim (adjustl (buffer)) /= "begin(integration_pass)") then
    call read_err (); return
  end if
  READ_ENTRIES: do
    read (unit, *) buffer
    if (trim (adjustl (buffer)) /= "begin(iteration)") then
      exit READ_ENTRIES
    end if
    it = it + 1
    call integration_entry_read (results%entry(it), unit)
    read (unit, *) buffer
    if (trim (adjustl (buffer)) /= "end(iteration)") then
      call read_err (); return
    end if
  end do READ_ENTRIES
  if (trim (adjustl (buffer)) /= "end(integration_pass)") then
    call read_err (); return
  end if
  results%average(pass) = compute_average (results%entry, pass)
end do
read (unit, *) buffer
if (trim (adjustl (buffer)) /= "end(integration_results)") then
  call read_err (); return
end if
contains
subroutine read_err ()
  call msg_fatal ("Reading integration results from file: syntax error")
end subroutine read_err
end subroutine integration_results_read

```

Check integration results for consistency. We compare against an array of pass indices and call numbers. If there is a difference, up to the number of iterations done so far, we return failure. Dummy entries (where `pass = 0`) are ignored.

(Processes: procedures)+≡

```

function integration_results_iterations_are_consistent &
  (results, pass, n_calls) result (flag)
  logical :: flag
  type(integration_results_t), intent(in) :: results
  integer, dimension(:), intent(in) :: pass, n_calls
  integer :: n_it
  n_it = results%n_it
  flag = size (pass) >= n_it .and. size (n_calls) >= n_it
  if (flag) then
    flag = all (results%entry(:n_it)%pass == pass(:n_it) &
      .and. &
      (results%entry(:n_it)%n_calls == n_calls(:n_it) &
      .or. &

```

```

                                results%entry(:n_it)%process_type == PRC_UNKNOWN))
    end if
end function integration_results_iterations_are_consistent

```

Discard all results starting from the specified iteration.

```

(Processes: procedures) +=
subroutine integration_results_discard (results, it)
    type(integration_results_t), intent(inout) :: results
    integer, intent(in) :: it
    if (it <= results%n_it) then
        select case (it)
            case (:1)
                results%n_it = 0
                results%n_pass = 0
            case default
                results%n_it = it - 1
                results%n_pass = maxval (results%entry(1:results%n_it)%pass)
        end select
    end if
end subroutine integration_results_discard

```

Expand the list of entries if the limit has been reached:

```

(Processes: procedures) +=
subroutine integration_results_expand (results)
    type(integration_results_t), intent(inout) :: results
    type(integration_entry_t), dimension(:), allocatable :: entry_tmp
    if (results%n_it == size (results%entry)) then
        allocate (entry_tmp (results%n_it))
        entry_tmp = results%entry
        deallocate (results%entry)
        allocate (results%entry (results%n_it + RESULTS_CHUNK_SIZE))
        results%entry(:results%n_it) = entry_tmp
        deallocate (entry_tmp)
    end if
    if (results%n_pass == size (results%average)) then
        allocate (entry_tmp (results%n_pass))
        entry_tmp = results%average
        deallocate (results%average)
        allocate (results%average (results%n_it + RESULTS_CHUNK_SIZE))
        results%average(:results%n_pass) = entry_tmp
        deallocate (entry_tmp)
    end if
end subroutine integration_results_expand

```

Append a new entry to the list and, if appropriate, compute the average.

```

(Processes: procedures) +=
subroutine integration_results_append_entry (results, entry)
    type(integration_results_t), intent(inout) :: results
    type(integration_entry_t), intent(in), optional :: entry
    if (results%n_it == 0) then
        call integration_results_init (results)
        results%n_it = 1
    end if
end subroutine integration_results_append_entry

```

```

        results%n_pass = 1
    else
        call integration_results_expand (results)
        if (present (entry)) then
            if (entry%pass /= results%entry(results%n_it)%pass) &
                results%n_pass = results%n_pass + 1
            end if
            results%n_it = results%n_it + 1
        end if
        if (present (entry)) then
            results%entry(results%n_it) = entry
            results%average(results%n_pass) = &
                compute_average (results%entry, entry%pass)
        end if
    end subroutine integration_results_append_entry

```

Enter results into the results list.

```

<Processes: public>+≡
    public :: integration_results_append

<Processes: procedures>+≡
    subroutine integration_results_append (results, &
        process_type, pass, n_it, n_calls, &
        integral, error, efficiency, grove_weight, time_start, time_end)
        type(integration_results_t), intent(inout) :: results
        integer, intent(in) :: process_type, pass, n_it, n_calls
        real(default), intent(in) :: integral, error, efficiency
        real(default), dimension(:), intent(in), optional :: grove_weight
        type(time_t), intent(in), optional :: time_start, time_end
        logical :: improved
        type(integration_entry_t) :: entry
        if (results%n_it /= 0) then
            improved = abs(accuracy (integral, error, n_calls)) &
                < abs(integration_entry_get_accuracy (results%entry(results%n_it)))
        else
            improved = .true.
        end if
        call integration_entry_init (entry, &
            process_type, pass, results%n_it+1, n_it, n_calls, improved, &
            integral, error, efficiency, grove_weight=grove_weight, &
            time_start=time_start, time_end=time_end)
        call integration_results_append_entry (results, entry)
    end subroutine integration_results_append

```

Enter an empty result into the results list.

```

<Processes: public>+≡
    public :: integration_results_append_null

<Processes: procedures>+≡
    subroutine integration_results_append_null (results, pass, n_it)
        type(integration_results_t), intent(inout) :: results
        integer, intent(in) :: pass, n_it
        type(integration_entry_t) :: entry
        call integration_entry_init (entry, &

```



```

        PRC_UNKNOWN, pass, n_it, 1, 0, .false., &
        0._default, 0._default, 0._default)
    call integration_results_append_entry (results, entry)
end subroutine integration_results_append_null

```

13.3.3 Access results

Return true if the results object has entries.

```

(Processes: procedures)+≡
function integration_results_exist (results) result (flag)
    logical :: flag
    type(integration_results_t), intent(in) :: results
    flag = results%n_pass > 0
end function integration_results_exist

```

Retrieve information from the results record. If **last** is set and true, take the last iteration. If it is set instead, take this iteration. If **pass** is set, take this average. If none is set, take the final average.

If the result would be invalid, the entry is not assigned. Due to default initialization, this returns a null entry.

```

(Processes: procedures)+≡
function results_get_entry (results, last, it, pass) result (entry)
    type(integration_entry_t) :: entry
    type(integration_results_t), intent(in) :: results
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    if (present (last)) then
        if (allocated (results%entry)) then
            entry = results%entry(results%n_it)
        end if
    else if (present (it)) then
        if (allocated (results%entry)) then
            if (it > 0 .and. it <= results%n_it) then
                entry = results%entry(it)
            end if
        end if
    else if (present (pass)) then
        if (allocated (results%average)) then
            if (pass > 0 .and. pass <= results%n_pass) then
                entry = results%average (pass)
            end if
        end if
    else
        if (allocated (results%average)) then
            entry = results%average (results%n_pass)
        end if
    end if
end function results_get_entry

```

The individual procedures. The results record should have the target attribute, but only locally within the function.

(Processes: procedures)+≡

```

function integration_results_get_n_calls (results, last, it, pass) &
  result (n_calls)
  integer :: n_calls
  type(integration_results_t), intent(in), target :: results
  logical, intent(in), optional :: last
  integer, intent(in), optional :: it, pass
  n_calls = integration_entry_get_n_calls &
    (results_get_entry (results, last, it, pass))
end function integration_results_get_n_calls

function integration_results_get_integral (results, last, it, pass) &
  result (integral)
  real(default) :: integral
  type(integration_results_t), intent(in), target :: results
  logical, intent(in), optional :: last
  integer, intent(in), optional :: it, pass
  integral = integration_entry_get_integral &
    (results_get_entry (results, last, it, pass))
end function integration_results_get_integral

function integration_results_get_error (results, last, it, pass) &
  result (error)
  real(default) :: error
  type(integration_results_t), intent(in), target :: results
  logical, intent(in), optional :: last
  integer, intent(in), optional :: it, pass
  error = integration_entry_get_error &
    (results_get_entry (results, last, it, pass))
end function integration_results_get_error

function integration_results_get_accuracy (results, last, it, pass) &
  result (accuracy)
  real(default) :: accuracy
  type(integration_results_t), intent(in), target :: results
  logical, intent(in), optional :: last
  integer, intent(in), optional :: it, pass
  accuracy = integration_entry_get_accuracy &
    (results_get_entry (results, last, it, pass))
end function integration_results_get_accuracy

function integration_results_get_chi2 (results, last, it, pass) &
  result (chi2)
  real(default) :: chi2
  type(integration_results_t), intent(in), target :: results
  logical, intent(in), optional :: last
  integer, intent(in), optional :: it, pass
  chi2 = integration_entry_get_chi2 &
    (results_get_entry (results, last, it, pass))
end function integration_results_get_chi2

function integration_results_get_efficiency (results, last, it, pass) &

```

```

        result (efficiency)
    real(default) :: efficiency
    type(integration_results_t), intent(in), target :: results
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    efficiency = integration_entry_get_efficiency &
        (results_get_entry (results, last, it, pass))
end function integration_results_get_efficiency

```

Return the time per event for the last integration iteration. (Not for the average.)

(Processes: procedures)+≡

```

function integration_results_get_time_per_event (results) result (s)
    real(default) :: s
    type(integration_results_t), intent(in) :: results
    if (results%n_pass /= 0) then
        s = integration_entry_get_time_per_event (results%entry(results%n_it))
    else
        s = 0
    end if
end function integration_results_get_time_per_event

```

Return the last pass index and the index of the last iteration *within* the last pass. The third routine returns the absolute index of the last iteration.

(Processes: procedures)+≡

```

function integration_results_get_current_pass (results) result (pass)
    integer :: pass
    type(integration_results_t), intent(in) :: results
    pass = results%n_pass
end function integration_results_get_current_pass

function integration_results_get_current_it (results) result (it)
    integer :: it
    type(integration_results_t), intent(in) :: results
    if (allocated (results%entry)) then
        it = count (results%entry(1:results%n_it)%pass == results%n_pass)
    else
        it = 0
    end if
end function integration_results_get_current_it

function integration_results_get_last_it (results) result (it)
    integer :: it
    type(integration_results_t), intent(in) :: results
    it = results%n_it
end function integration_results_get_last_it

```

Return the index of the best iteration (lowest accuracy value) within the current pass. If none qualifies, return zero.

(Processes: procedures)+≡

```

function integration_results_get_best_it (results) result (it)
    integer :: it

```

```

type(integration_results_t), intent(in) :: results
integer :: i
real(default) :: acc, acc_best
acc_best = -1
it = 0
do i = 1, results%n_it
  if (results%entry(i)%pass == results%n_pass) then
    acc = integration_entry_get_accuracy (results%entry(i))
    if (acc_best < 0 .or. acc <= acc_best) then
      acc_best = acc
      it = i
    end if
  end if
end do
end function integration_results_get_best_it

```

Compute the MD5 sum by printing everything and checksumming the resulting file.

```

<Processes: procedures>+≡
function integration_results_get_md5sum (results) result (md5sum_results)
character(32) :: md5sum_results
type(integration_results_t), intent(in) :: results
integer :: u
u = free_unit ()
open (unit = u, status = "scratch", action = "readwrite")
call integration_results_write (results, u, verbose=.true.)
rewind (u)
md5sum_results = md5sum (u)
close (u)
end function integration_results_get_md5sum

```

13.3.4 Results display

Write a driver file for history visualization.

The ratio of y range over y value must not become too small, otherwise we run into an arithmetic overflow in GAMELAN. 2% appears to be safe.

```

<Limits: public parameters>+≡
real, parameter, public :: GML_MIN_RANGE_RATIO = 0.02

<Processes: procedures>+≡
subroutine integration_results_write_driver (results, filename)
type(integration_results_t), intent(in) :: results
type(string_t), intent(in) :: filename
type(string_t) :: file_tex
integer :: unit
integer :: n, i, n_pass, pass
integer, dimension(:), allocatable :: ipass
real(default) :: ymin, ymax, yavg, ydif, y0, y1
real(default) :: int, err
file_tex = filename // ".tex"
unit = free_unit ()
open (unit=unit, file=char(file_tex), action="write", status="replace")

```

```

n = results%n_it
n_pass = results%n_pass
allocate (ipass (results%n_pass))
ipass(1) = 0
pass = 2
do i = 1, n-1
  if (integration_entry_get_pass (results%entry(i)) &
      /= integration_entry_get_pass (results%entry(i+1))) then
    ipass(pass) = i
    pass = pass + 1
  end if
end do
ymin = minval (integration_entry_get_integral (results%entry(:n)) &
               - integration_entry_get_error (results%entry(:n)))
ymax = maxval (integration_entry_get_integral (results%entry(:n)) &
               + integration_entry_get_error (results%entry(:n)))
yavg = (ymax + ymin) / 2
ydif = (ymax - ymin)
if (ydif * 1.5 > GML_MIN_RANGE_RATIO * yavg) then
  y0 = yavg - ydif * 0.75
  y1 = yavg + ydif * 0.75
else
  y0 = yavg * (1 - GML_MIN_RANGE_RATIO / 2)
  y1 = yavg * (1 + GML_MIN_RANGE_RATIO / 2)
end if
write (unit, "(A)") "\documentclass{article}"
write (unit, "(A)") "\usepackage{a4wide}"
write (unit, "(A)") "\usepackage{gamelan}"
write (unit, "(A)") "\usepackage{amsmath}"
write (unit, "(A)") ""
write (unit, "(A)") "\begin{document}"
write (unit, "(A)") "\begin{gmlfile}"
write (unit, "(A)") "\section*{Integration Results Display}"
write (unit, "(A)") ""
write (unit, "(A)") "Process: \verb|" // char (filename) // "|"
write (unit, "(A)") ""
write (unit, "(A)") "\vspace*{2\baselineskip}"
write (unit, "(A)") "\unitlength 1mm"
write (unit, "(A)") "\begin{gmlcode}"
write (unit, "(A)") " picture sym; sym = fshape (circle scaled 1mm());"
write (unit, "(A)") " color col.band; col.band = 0.9white;"
write (unit, "(A)") " color col.eband; col.eband = 0.98white;"
write (unit, "(A)") "\end{gmlcode}"
write (unit, "(A)") "\begin{gmlgraph*}(130,180)[history]"
write (unit, "(A)") " setup (linear, linear);"
write (unit, "(A,I0,A)") " history.n_pass = ", n_pass, ";"
write (unit, "(A,I0,A)") " history.n_it = ", n, ";"
write (unit, "(A,A,A)") " history.y0 = #""", char (mp_format (y0)), """,;"
write (unit, "(A,A,A)") " history.y1 = #""", char (mp_format (y1)), """,;"
write (unit, "(A)") &
  " graphrange (#0.5, history.y0), (#(n+0.5), history.y1);"
do pass = 1, n_pass
  write (unit, "(A,I0,A,I0,A)") &
    " history.pass[", pass, "] = ", ipass(pass), ";"

```

```

write (unit, "(A,I0,A,A,A)") &
  " history.avg[" , pass, "] = #""", &
  char (mp_format &
    (integration_entry_get_integral (results%average(pass)))), &
  """, "
write (unit, "(A,I0,A,A,A)") &
  " history.err[" , pass, "] = #""", &
  char (mp_format &
    (integration_entry_get_error (results%average(pass)))), &
  """, "
write (unit, "(A,I0,A,A,A)") &
  " history.chi[" , pass, "] = #""", &
  char (mp_format &
    (integration_entry_get_chi2 (results%average(pass)))), &
  """, "
end do
write (unit, "(A,I0,A,I0,A)") &
  " history.pass[" , n_pass + 1, "] = " , n, ";"
write (unit, "(A)") " for i = 1 upto history.n_pass:"
write (unit, "(A)") " if history.chi[i] greater one:"
write (unit, "(A)") " fill plot ("
write (unit, "(A)") &
  " (#(history.pass[i] +.5), " &
  // "history.avg[i] minus history.err[i] times history.chi[i]),"
write (unit, "(A)") &
  " (#(history.pass[i+1]+.5), " &
  // "history.avg[i] minus history.err[i] times history.chi[i]),"
write (unit, "(A)") &
  " (#(history.pass[i+1]+.5), " &
  // "history.avg[i] plus history.err[i] times history.chi[i]),"
write (unit, "(A)") &
  " (#(history.pass[i] +.5), " &
  // "history.avg[i] plus history.err[i] times history.chi[i])"
write (unit, "(A)") " ) withcolor col.eband fi;"
write (unit, "(A)") " fill plot ("
write (unit, "(A)") &
  " (#(history.pass[i] +.5), history.avg[i] minus history.err[i]),"
write (unit, "(A)") &
  " (#(history.pass[i+1]+.5), history.avg[i] minus history.err[i]),"
write (unit, "(A)") &
  " (#(history.pass[i+1]+.5), history.avg[i] plus history.err[i]),"
write (unit, "(A)") &
  " (#(history.pass[i] +.5), history.avg[i] plus history.err[i])"
write (unit, "(A)") " ) withcolor col.band;"
write (unit, "(A)") " draw plot ("
write (unit, "(A)") &
  " (#(history.pass[i] +.5), history.avg[i]),"
write (unit, "(A)") &
  " (#(history.pass[i+1]+.5), history.avg[i])"
write (unit, "(A)") " ) dashed evenly;"
write (unit, "(A)") " endfor"
write (unit, "(A)") " for i = 1 upto history.n_pass + 1:"
write (unit, "(A)") " draw plot ("
write (unit, "(A)") &

```

```

"      (#(history.pass[i]+.5), history.y0),"
write (unit, "(A)" ) &
"      (#(history.pass[i]+.5), history.y1)"
write (unit, "(A)" ) "      ) dashed withdots;"
write (unit, "(A)" ) "    endfor"
do i = 1, n
  write (unit, "(A,I0,A,A,A,A,A)" ) "  plot (history) (#", &
    i, ", #""", &
    char (mp_format (integration_entry_get_integral (results%entry(i))),&
    """) vbar #""", &
    char (mp_format (integration_entry_get_error (results%entry(i))), &
    """),"
end do
write (unit, "(A)" ) "  draw piecewise from (history) " &
  // "withsymbol sym;"
write (unit, "(A)" ) "  fullgrid.lr (5,20);"
write (unit, "(A)" ) "  standardgrid.bt (n);"
write (unit, "(A)" ) "\end{gmlgraph*}"
write (unit, "(A)" ) "\end{gmlfile}"
write (unit, "(A)" ) "\clearpage"
write (unit, "(A)" ) "\begin{verbatim}"
call integration_results_write (results, unit)
write (unit, "(A)" ) "\end{verbatim}"
write (unit, "(A)" ) "\end{document}"
close (unit)
end subroutine integration_results_write_driver

```

Call L^AT_EX and Metapost for the history driver file, and convert to PS and PDF.

(*Processes: procedures*)+≡

```

subroutine integration_results_compile_driver (results, filename, os_data)
  type(integration_results_t), intent(in) :: results
  type(string_t), intent(in) :: filename
  type(os_data_t), intent(in) :: os_data
  integer :: unit, unit_dev, status
  type(string_t) :: file_tex, file_dvi, file_ps, file_pdf, file_mp
  type(string_t) :: setenv_tex, setenv_mp, pipe, pipe_dvi
  type(string_t) :: latex_opt, mpost_opt
  if (.not. os_data%event_analysis) then
    call msg_warning ("Skipping integration history display " &
      // "because latex or mpost is not available")
    return
  end if
  file_tex = filename // ".tex"
  file_dvi = filename // ".dvi"
  file_ps = filename // ".ps"
  file_pdf = filename // ".pdf"
  file_mp = filename // ".mp"
  call msg_message ("Creating integration history display "&
    // char (file_ps) // " and " // char (file_pdf))
BLOCK: do
  unit_dev = free_unit ()
  open (file = "/dev/null", unit = unit_dev, &
    action = "write", iostat = status)

```

```

if (status /= 0) then
  pipe = ""
  pipe_dvi = ""
else
  pipe = " > /dev/null"
  pipe_dvi = " 2>/dev/null 1>/dev/null"
end if
close (unit_dev)
if (os_data%whizard_texpath /= "") then
  setenv_tex = &
    "TEXINPUTS=" // os_data%whizard_texpath // " :$TEXINPUTS "
  setenv_mp = &
    "MPINPUTS=" // os_data%whizard_texpath // " :$MPINPUTS "
else
  setenv_tex = ""
  setenv_mp = ""
end if
call os_system_call (setenv_tex // os_data%latex // " " // &
  file_tex // pipe, status)
if (status /= 0) exit BLOCK
if (os_data%gml /= "") then
  call os_system_call (setenv_mp // os_data%gml // " " // &
    file_mp // pipe, status)
else
  call msg_error ("Could not use GAMELAN/MetaPOST.")
  exit BLOCK
end if
if (status /= 0) exit BLOCK
call os_system_call (setenv_tex // os_data%latex // " " // &
  file_tex // pipe, status)
if (status /= 0) exit BLOCK
if (os_data%event_analysis_ps) then
  call os_system_call (os_data%dvips // " " // &
    file_dvi // pipe_dvi, status)
  if (status /= 0) exit BLOCK
else
  call msg_warning ("Skipping PostScript generation because dvips " &
    // "is not available")
  exit BLOCK
end if
if (os_data%event_analysis_pdf) then
  call os_system_call (os_data%ps2pdf // " " // &
    file_ps, status)
  if (status /= 0) exit BLOCK
else
  call msg_warning ("Skipping PDF generation because ps2pdf " &
    // "is not available")
  exit BLOCK
end if
exit BLOCK
end do BLOCK
if (status /= 0) then
  call msg_error ("Unable to compile integration history display")
end if

```



```
end subroutine integration_results_compile_driver
```

13.3.5 Process status

This is a block that allows to follow the evaluation status of the current call, and to trace the status of the current sample.

```
(Processes: public)+≡
  public :: process_status_t

(Processes: types)+≡
  type :: process_status_t
    logical :: called = .false.
    logical :: passed_strfun_chain = .false.
    logical :: passed_mass_threshold = .false.
    logical :: passed_kinematics = .false.
    logical :: passed_cuts = .false.
    logical :: passed_evaluation = .false.
    integer :: n_called = 0
    integer :: n_passed_strfun_chain = 0
    integer :: n_passed_mass_threshold = 0
    integer :: n_passed_kinematics = 0
    integer :: n_passed_cuts = 0
    integer :: n_passed_evaluation = 0
  end type process_status_t
```

Complete account (for the process log)

```
(Processes: procedures)+≡
  subroutine process_status_write (status, unit)
    type(process_status_t), intent(in) :: status
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
1  format (1x,A,L1,3x,I9)
    write (u, *) "Process evaluation status (count):"
    write (u, 1) " called = ", status%called, &
      status%n_called
    write (u, 1) " passed strfun_chain = ", status%passed_strfun_chain, &
      status%n_passed_strfun_chain
    write (u, 1) " passed mass_threshold = ", status%passed_mass_threshold, &
      status%n_passed_mass_threshold
    write (u, 1) " passed kinematics = ", status%passed_kinematics, &
      status%n_passed_kinematics
    write (u, 1) " passed cuts = ", status%passed_cuts, &
      status%n_passed_cuts
    write (u, 1) " passed evaluation = ", status%passed_evaluation, &
      status%n_passed_evaluation
  end subroutine process_status_write
```

Counters only (for evaluating complete samples)

```
(Processes: public)+≡
  public :: process_status_write_counters
```

(Processes: procedures)+≡

```

subroutine process_status_write_counters (status, unit)
  type(process_status_t), intent(in) :: status
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
1  format (2x,A,1x,I9)
  call msg_message ("Process evaluation counters:", unit=u)
  write (msg_buffer, 1) "called          = ", &
    status%n_called
  call msg_message (unit=u)
  write (msg_buffer, 1) "passed strfun_chain = ", &
    status%n_passed_strfun_chain
  call msg_message (unit=u)
  write (msg_buffer, 1) "passed mass_threshold = ", &
    status%n_passed_mass_threshold
  call msg_message (unit=u)
  write (msg_buffer, 1) "passed kinematics    = ", &
    status%n_passed_kinematics
  call msg_message (unit=u)
  write (msg_buffer, 1) "passed cuts          = ", &
    status%n_passed_cuts
  call msg_message (unit=u)
  write (msg_buffer, 1) "passed evaluation    = ", &
    status%n_passed_evaluation
  call msg_message (unit=u)
end subroutine process_status_write_counters

```

(Processes: procedures)+≡

```

subroutine process_status_reset_flags (status)
  type(process_status_t), intent(inout) :: status
  status%called = .false.
  status%passed_strfun_chain = .false.
  status%passed_mass_threshold = .false.
  status%passed_kinematics = .false.
  status%passed_cuts = .false.
  status%passed_evaluation = .false.
end subroutine process_status_reset_flags

```

Complete reset. Make use of default initialization.

(Processes: procedures)+≡

```

subroutine process_status_reset_counters (status)
  type(process_status_t), intent(out) :: status
end subroutine process_status_reset_counters

```

Set a flag and increment the associated counters:

(Processes: procedures)+≡

```

subroutine process_status_called (status)
  type(process_status_t), intent(inout) :: status
  status%called = .true.
  status%n_called = status%n_called + 1
end subroutine process_status_called

```

```

subroutine process_status_passed_strfun_chain (status)
  type(process_status_t), intent(inout) :: status
  status%passed_strfun_chain = .true.
  status%n_passed_strfun_chain = status%n_passed_strfun_chain + 1
end subroutine process_status_passed_strfun_chain

subroutine process_status_passed_mass_threshold (status)
  type(process_status_t), intent(inout) :: status
  status%passed_mass_threshold = .true.
  status%n_passed_mass_threshold = status%n_passed_mass_threshold + 1
end subroutine process_status_passed_mass_threshold

subroutine process_status_passed_kinematics (status)
  type(process_status_t), intent(inout) :: status
  status%passed_kinematics = .true.
  status%n_passed_kinematics = status%n_passed_kinematics + 1
end subroutine process_status_passed_kinematics

subroutine process_status_passed_cuts (status)
  type(process_status_t), intent(inout) :: status
  status%passed_cuts = .true.
  status%n_passed_cuts = status%n_passed_cuts + 1
end subroutine process_status_passed_cuts

subroutine process_status_passed_evaluation (status)
  type(process_status_t), intent(inout) :: status
  status%passed_evaluation = .true.
  status%n_passed_evaluation = status%n_passed_evaluation + 1
end subroutine process_status_passed_evaluation

```

13.3.6 QCD parameters

The QCD parameters of the process block describe the handling of α_s . If it is not fixed, it depends on the scale which can be set in various ways, including externally linked LHAPDF structure functions. We store the relevant parameters in this transparent block.

```

⟨Processes: types⟩+≡
  type :: qcd_parameters_t
    logical :: alpha_s_is_fixed = .true.
    integer :: order = 0
    integer :: nf = 0
    logical :: alpha_s_from_mz = .true.
    logical :: mz_is_known = .false.
    real(default) :: mz = 0
    logical :: alpha_s_mz_is_known = .false.
    real(default) :: alpha_s_mz = 0
    real(default) :: lambda = 0
    real(default) :: alpha_s_at_scale = 0
    logical :: alpha_s_from_lhapdf = .false.
    type(string_t) :: lhpdf_dir
    type(string_t) :: lhpdf_file

```

```

integer :: lhpdf_set = 0
integer :: lhpdf_member = 0
integer :: lhpdf_photon_scheme = 0
logical :: alpha_s_from_pdf_builtin = .false.
integer :: pdf_builtin_set = CTEQ6L
end type qcd_parameters_t

```

Setup the basic parameters. The specific LHAPDF and PDF-builtin parameters are set in separate routines below.

(Processes: procedures)+≡

```

subroutine qcd_parameters_basic_setup (qcd, var_list)
  type(qcd_parameters_t), intent(inout) :: qcd
  type(var_list_t), intent(in), target :: var_list
  qcd%alpha_s_is_fixed = &
    var_list_get_lval (var_list, var_str ("?alpha_s_is_fixed"))
  qcd%order = &
    var_list_get_ival (var_list, var_str ("alpha_s_order"))
  qcd%nf = &
    var_list_get_ival (var_list, var_str ("alpha_s_nf"))
  qcd%alpha_s_from_mz = &
    var_list_get_lval (var_list, var_str ("?alpha_s_from_mz"))
  qcd%alpha_s_from_lhapdf = &
    var_list_get_lval (var_list, var_str ("?alpha_s_from_lhapdf"))
  qcd%alpha_s_from_pdf_builtin = &
    var_list_get_lval (var_list, var_str ("?alpha_s_from_pdf_builtin"))
  if (qcd%alpha_s_from_lhapdf .and. qcd%alpha_s_from_pdf_builtin) then
    call msg_fatal (" Mixing alphas evolution", &
      (/ var_str (" from LHAPDF and builtin PDF is not permitted") /))
  end if
  qcd%mz_is_known = &
    var_list_is_known (var_list, var_str ("mZ"))
  if (qcd%mz_is_known) qcd%mz = &
    var_list_get_rval (var_list, var_str ("mZ"))
  qcd%alpha_s_mz_is_known = &
    var_list_is_known (var_list, var_str ("alphas"))
  if (qcd%alpha_s_mz_is_known) qcd%alpha_s_mz = &
    var_list_get_rval (var_list, var_str ("alphas"))
  qcd%lambda = &
    var_list_get_rval (var_list, var_str ("lambda_qcd"))
end subroutine qcd_parameters_basic_setup

```

Set the LHAPDF parameters, either directly or, as fallback, reading from a variable list, initialize LHAPDF, and update the LHAPDF status.

The procedure must be called such that either all parameters or the variable list must be present.

(Processes: procedures)+≡

```

subroutine qcd_parameters_setup_lhapdf (qcd, lhpdf_status, &
  lhpdf_dir, lhpdf_file, lhpdf_member, &
  var_list)
  type(qcd_parameters_t), intent(inout) :: qcd
  type(lhpdf_status_t), intent(inout) :: lhpdf_status
  type(string_t), intent(in), optional :: lhpdf_dir, lhpdf_file
  integer, intent(in), optional :: lhpdf_member

```

```

type(var_list_t), intent(in), optional :: var_list
if (qcd%alpha_s_from_lhapdf) then
  if (LHAPDF_AVAILABLE) then
    if (present (lhpdf_dir)) then
      qcd%lhpdf_dir = lhpdf_dir
      qcd%lhpdf_file = lhpdf_file
      qcd%lhpdf_member = lhpdf_member
    else
      qcd%lhpdf_dir = var_list_get_sval (var_list, &
        var_str ("lhpdf_dir")) ! $
      qcd%lhpdf_file = var_list_get_sval (var_list, &
        var_str ("lhpdf_file")) ! $
      qcd%lhpdf_member = var_list_get_ival (var_list, &
        var_str ("lhpdf_member"))
    end if
    qcd%lhpdf_set = 1
    call msg_message ("LHAPDF set used for alpha_s = " &
      // ' ' // char (qcd%lhpdf_file) // ' ')
    call lhpdf_init (lhpdf_status, &
      qcd%lhpdf_set, qcd%lhpdf_dir, qcd%lhpdf_file, &
      qcd%lhpdf_member)
  else
    call msg_error &
      ("LHAPDF not linked: resetting alpha_s_from_lhapdf to false")
    qcd%alpha_s_from_lhapdf = .false.
  end if
end if
end subroutine qcd_parameters_setup_lhapdf

```

Set the PDF-builtin parameters, either directly or, as fallback, reading from a variable list.

The procedure must be called such that either the name or the variable list must be present.

(*Processes: procedures*)+≡

```

subroutine qcd_parameters_setup_pdf_builtin (qcd, pdf_builtin_status, &
  pdf_builtin_datapath, pdf_builtin_set, var_list)
type(qcd_parameters_t), intent(inout) :: qcd
type(pdf_builtin_status_t), intent(inout) :: pdf_builtin_status
type(string_t), intent(in) :: pdf_builtin_datapath
type(string_t), intent(in), optional :: pdf_builtin_set
type(var_list_t), intent(in), optional :: var_list
type(string_t) :: name
if (qcd%alpha_s_from_pdf_builtin) then
  if (present (pdf_builtin_set)) then
    name = pdf_builtin_set
  else
    name = var_list_get_sval (var_list, &
      var_str ("pdf_builtin_set")) ! $
  end if
  call msg_message ("Built-in PDF set used for alpha_s = " &
    // ' ' // char (name) // ' ')
  qcd%pdf_builtin_set = pdf_get_id (name)
  call pdf_init (pdf_builtin_status, qcd%pdf_builtin_set, &

```

```

        pdf_builtin_datapath)
    end if
end subroutine qcd_parameters_setup_pdf_builtin

```

Write the QCD parameters. Write only those that are relevant, depending on the various switches.

```

(Processes: procedures) +=
subroutine qcd_parameters_write (qcd, unit)
  type(qcd_parameters_t), intent(in) :: qcd
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit)
  write (u, *) "QCD coupling parameters ="
  write (u, *) "  alpha-s is fixed = ", qcd%alpha_s_is_fixed
  if (.not. qcd%alpha_s_is_fixed) then
    if (qcd%alpha_s_from_lhapdf) then
      write (u, *) "  alpha-s from LHAPDF"
      write (u, *) "  PDF group          = ", qcd%lhpdf_set
      write (u, *) "  PDF member          = ", qcd%lhpdf_member
    else
      if (qcd%alpha_s_from_pdf_builtin) then
        write (u, *) "  alpha-s from builtin PDF"
        write (u, *) "  PDF group          = ", qcd%pdf_builtin_set
      else
        write (u, *) "  LLA order          = ", qcd%order
        write (u, *) "  active flavors     = ", qcd%nf
        write (u, *) "  use alpha-s (mZ) = ", qcd%alpha_s_from_mz
        if (qcd%alpha_s_from_mz) then
          write (u, *) "  mZ is known       = ", qcd%mz_is_known
          if (qcd%mz_is_known) then
            write (u, *) "  mZ                  = ", qcd%mz
          end if
          write (u, *) "  as(mZ) is known  = ", qcd%alpha_s_mz_is_known
          if (qcd%alpha_s_mz_is_known) then
            write (u, *) "  alpha-s (mZ)     = ", qcd%alpha_s_mz
          end if
        else
          write (u, *) "  Lambda_QCD        = ", qcd%lambda
        end if
      end if
    end if
  end if
  write (u, *) "  alpha-s (scale) = ", qcd%alpha_s_at_scale
end if
end subroutine qcd_parameters_write

```

The MD5 sum. We depend on the logical completeness of the previous output routine.

```

(Processes: procedures) +=
function qcd_parameters_get_md5sum (qcd) result (md5)
  character(32) :: md5
  type(qcd_parameters_t), intent(in) :: qcd
  integer :: u
  u = free_unit ()

```

```

open (unit=u, status="scratch")
call qcd_parameters_write (qcd, u)
rewind (u)
md5 = md5sum (u)
close (u)
end function qcd_parameters_get_md5sum

```

The purpose of the QCD parameter section is to update the α_s value for the process; if necessary, event by event.

(Processes: procedures)+≡

```

subroutine qcd_parameters_update_alpha_s (qcd, scale)
  type(qcd_parameters_t), intent(inout) :: qcd
  real(default), intent(in) :: scale
  real(default) :: alpha_s
  if (.not. qcd%alpha_s_is_fixed) then
    if (qcd%alpha_s_from_lhapdf) then
      alpha_s = alphasPDF (dble (scale))
    else
      if (qcd%alpha_s_from_pdf_builtin) then
        alpha_s = pdf_alphas (qcd%pdf_builtin_set, scale)
      else
        if (qcd%alpha_s_from_mz) then
          if (qcd%alpha_s_mz_is_known) then
            if (qcd%mz_is_known) then
              alpha_s = running_as (scale, &
                al_mz = qcd%alpha_s_mz, &
                mz = qcd%mz, &
                order = qcd%order, &
                nf = real (qcd%nf, default))
            else
              alpha_s = running_as (scale, &
                al_mz = qcd%alpha_s_mz, &
                order = qcd%order, &
                nf = real (qcd%nf, default))
            end if
          end if
        else
          if (qcd%mz_is_known) then
            alpha_s = running_as (scale, &
              mz = qcd%mz, &
              order = qcd%order, &
              nf = real (qcd%nf, default))
          else
            alpha_s = running_as (scale, &
              order = qcd%order, &
              nf = real (qcd%nf, default))
          end if
        end if
      end if
    else
      alpha_s = running_as_lam (real (qcd%nf, default), scale, &
        lambda_qcd = qcd%lambda, &
        order = qcd%order)
    end if
  end if
end if

```

```

        end if
        qcd%alpha_s_at_scale = alpha_s
    end if
end subroutine qcd_parameters_update_alpha_s

```

13.3.7 Grid parameters

This is a transparent container. It holds the parameters that are stored in grid files, and are checked when grid files are read.

(Processes: public)+≡

```
public :: grid_parameters_t
```

(Processes: types)+≡

```

type :: grid_parameters_t
    integer :: threshold_calls = 0
    integer :: min_calls_per_channel = 10
    integer :: min_calls_per_bin = 10
    integer :: min_bins = 3
    integer :: max_bins = 20
    logical :: stratified = .true.
    logical :: use_vamp_equivalences = .true.
    real(default) :: channel_weights_power = 0.25_default
end type grid_parameters_t

```

I/O:

(Processes: procedures)+≡

```

subroutine grid_parameters_write (grid_par, unit)
    type(grid_parameters_t), intent(in) :: grid_par
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit)
    write (u, *) "threshold_calls      = ", grid_par%threshold_calls
    write (u, *) "min_calls_per_channel = ", grid_par%min_calls_per_channel
    write (u, *) "min_calls_per_bin    = ", grid_par%min_calls_per_bin
    write (u, *) "min_bins              = ", grid_par%min_bins
    write (u, *) "max_bins              = ", grid_par%max_bins
    write (u, *) "stratified            = ", grid_par%stratified
    write (u, *) "use_vamp_equivalences = ", grid_par%use_vamp_equivalences
    write (u, *) "channel_weights_power = ", grid_par%channel_weights_power
end subroutine grid_parameters_write

```

(Processes: procedures)+≡

```

subroutine grid_parameters_read (grid_par, unit)
    type(grid_parameters_t), intent(out) :: grid_par
    integer, intent(in) :: unit
    character(30) :: dummy
    character :: equals
    read (unit, *) dummy, equals, grid_par%threshold_calls
    read (unit, *) dummy, equals, grid_par%min_calls_per_channel
    read (unit, *) dummy, equals, grid_par%min_calls_per_bin
    read (unit, *) dummy, equals, grid_par%min_bins
    read (unit, *) dummy, equals, grid_par%max_bins

```



```

    read (unit, *) dummy, equals, grid_par%stratified
    read (unit, *) dummy, equals, grid_par%use_vamp_equivalences
    read (unit, *) dummy, equals, grid_par%channel_weights_power
end subroutine grid_parameters_read

```

<Processes: interfaces>+≡

```

interface operator(==)
  module procedure grid_parameters_eq
end interface

```

<Processes: procedures>+≡

```

function grid_parameters_eq (gp1, gp2) result (eq)
  logical :: eq
  type(grid_parameters_t), intent(in) :: gp1, gp2
  eq = gp1%threshold_calls == gp2%threshold_calls &
    .and. gp1%min_calls_per_channel == gp2%min_calls_per_channel &
    .and. gp1%min_calls_per_bin == gp2%min_calls_per_bin &
    .and. gp1%min_bins == gp2%min_bins &
    .and. gp1%max_bins == gp2%max_bins &
    .and. (gp1%stratified .eqv. gp2%stratified) &
    .and. (gp1%use_vamp_equivalences .eqv. gp2%use_vamp_equivalences) &
    .and. gp1%channel_weights_power == gp2%channel_weights_power
end function grid_parameters_eq

```

<Processes: interfaces>+≡

```

interface operator(/=)
  module procedure grid_parameters_ne
end interface

```

<Processes: procedures>+≡

```

function grid_parameters_ne (gp1, gp2) result (ne)
  logical :: ne
  type(grid_parameters_t), intent(in) :: gp1, gp2
  ne = gp1%threshold_calls /= gp2%threshold_calls &
    .or. gp1%min_calls_per_channel /= gp2%min_calls_per_channel &
    .or. gp1%min_calls_per_bin /= gp2%min_calls_per_bin &
    .or. gp1%min_bins /= gp2%min_bins &
    .or. gp1%max_bins /= gp2%max_bins &
    .or. (gp1%stratified .neqv. gp2%stratified) &
    .or. (gp1%use_vamp_equivalences .neqv. gp2%use_vamp_equivalences) &
    .or. gp1%channel_weights_power /= gp2%channel_weights_power
end function grid_parameters_ne

```

13.3.8 MD5 sum collection for grid files

For checking input in detail, grid files hold various MD5 sums that correspond to input data. This is a transparent container.

<Processes: public>+≡

```

public :: md5sum_grids_t

```

<Processes: types>+≡

```

type :: md5sum_grids_t
  character(32) :: process = ""

```

```

character(32) :: model      = ""
character(32) :: parameters = ""
character(32) :: phs        = ""
character(32) :: beams      = ""
character(32) :: sf_list    = ""
character(32) :: mappings   = ""
character(32) :: cuts       = ""
character(32) :: weight     = ""
character(32) :: scale      = ""
character(32) :: fac_scale  = ""
character(32) :: ren_scale  = ""
character(32) :: alpha_s    = ""
end type md5sum_grids_t

```

(Processes: procedures)+≡

```

subroutine md5sum_grids_write (md5sum, unit)
  type(md5sum_grids_t), intent(in) :: md5sum
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit)
  write (u, *) " md5sum_process      = ", "'", md5sum%process, "'"
  write (u, *) " md5sum_model        = ", "'", md5sum%model, "'"
  write (u, *) " md5sum_parameters    = ", "'", md5sum%parameters, "'"
  write (u, *) " md5sum_phase_space = ", "'", md5sum%phs, "'"
  write (u, *) " md5sum_beams          = ", "'", md5sum%beams, "'"
  write (u, *) " md5sum_sf_list       = ", "'", md5sum%sf_list, "'"
  write (u, *) " md5sum_mappings      = ", "'", md5sum%mappings, "'"
  write (u, *) " md5sum_cuts          = ", "'", md5sum%cuts, "'"
  write (u, *) " md5sum_weight        = ", "'", md5sum%weight, "'"
  write (u, *) " md5sum_scale         = ", "'", md5sum%scale, "'"
  write (u, *) " md5sum_fac_scale     = ", "'", md5sum%fac_scale, "'"
  write (u, *) " md5sum_ren_scale     = ", "'", md5sum%ren_scale, "'"
  write (u, *) " md5sum_alpha_s      = ", "'", md5sum%alpha_s, "'"
end subroutine md5sum_grids_write

```

13.3.9 The process type

The process object holds virtually everything that is connected to a particular process; it is the workspace for integration and event generation.

Each process has a type (decay or scattering). For the purpose of generating cascades, we may need multiple copies of a particular (decay) process, which are implemented as a linked list. These store copies of, e.g., the hard-interaction object, the phase space and the VAMP grids. For read-only information they point back to the original.

(Processes: public)+≡

```
public :: process_t
```

(Processes: types)+≡

```

type :: process_t
private
integer :: type = PRC_UNKNOWN

```

```

type(process_t), pointer :: copy => null ()
logical :: is_original = .true.
type(process_t), pointer :: original => null ()
type(process_t), pointer :: working_copy => null ()
logical :: in_use = .true.
logical :: initialized = .false.
logical :: has_matrix_element = .false.
logical :: use_hi_color_factors = .false.
logical :: use_beams = .true.
logical :: has_extra_evaluators = .true.
logical :: beams_are_set = .false.
logical :: is_cascade_decay = .false.
type(flavor_t), dimension(:), allocatable :: flv_in
type(flavor_t), dimension(:), allocatable :: flv_out
type(beam_data_t) :: beam_data
type(string_t) :: id
character(32) :: md5sum = ""
type(process_library_t), pointer :: prc_lib => null ()
integer :: lib_index = 0
integer :: store_index = 0
type(model_t), pointer :: model
integer :: n_strfun = 0
integer :: n_par_strfun = 0
integer :: n_par_hi = 0
integer :: n_par = 0
logical :: azimuthal_dependence = .false.
logical :: vamp_grids_defined = .false.
logical :: sqrts_known = .false.
logical :: sqrts_hat_known = .false.
real(default) :: sqrts = 0
real(default) :: sqrts_hat = 0
real(default), dimension(:), allocatable :: x_strfun
real(default), dimension(:), allocatable :: x_hi
integer :: n_channels = 0
integer :: n_bins = 0
integer :: channel = 0
logical :: lab_is_cm_frame = .true.
type(lorentz_transformation_t) :: lt_cm_to_lab = identity
logical :: old_phs_version = .false.
type(process_status_t) :: status
real(default), dimension(:,:), allocatable :: x
real(default), dimension(:), allocatable :: sf_factor
real(default), dimension(:), allocatable :: phs_factor
real(default), dimension(:), allocatable :: mass_in
real(default) :: flux_factor = 0
real(default) :: averaging_factor = 0
real(default) :: sf_mapping_factor = 0
real(default) :: phs_volume = 0
real(default) :: vamp_phs_factor = 0
real(default) :: sqme = 0
real(default) :: reweighting_factor = 0
real(default) :: sample_function_value = 0
real(default) :: scale = 0
real(default) :: fac_scale = 0

```

```

real(default) :: ren_scale = 0
logical :: negative_weights = .false.
type(qcd_parameters_t) :: qcd
character(32) :: md5sum_alpha_s
type(strfun_chain_t) :: sfchain
type(hard_interaction_t) :: hi
type(evaluator_t) :: eval_trace
type(evaluator_t) :: eval_beam_flows
type(evaluator_t) :: eval_sqme
type(evaluator_t) :: eval_flows
logical :: fatal_beam_decay = .true.
type(phs_forest_t) :: forest
character(32) :: md5sum_phs = ""
type(vamp_equivalences_t) :: vamp_eq
integer, dimension(:), allocatable :: j_beam
integer, dimension(:), allocatable :: j_in
integer, dimension(:), allocatable :: j_out
type(subevt_t) :: subevt
type(var_list_t) :: var_list
type(parse_node_t), pointer :: cut_pn => null ()
type(parse_node_t), pointer :: weight_pn => null ()
type(parse_node_t), pointer :: scale_pn => null ()
type(parse_node_t), pointer :: fac_scale_pn => null ()
type(parse_node_t), pointer :: ren_scale_pn => null ()
type(eval_tree_t) :: cut_expr
type(eval_tree_t) :: reweighting_expr
type(eval_tree_t) :: scale_expr
type(eval_tree_t) :: fac_scale_expr
type(eval_tree_t) :: ren_scale_expr
logical, dimension(:), allocatable :: active_channel
type(string_t) :: filename_current_grid
type(string_t) :: filename_best_grid
type(md5sum_grids_t) :: md5sum_grids
type(grid_parameters_t) :: grid_parameters
integer, dimension(:), allocatable :: pass_array
integer, dimension(:), allocatable :: n_calls_array
type(vamp_grids) :: grids
type(vamp_history), dimension(:), allocatable :: v_history
type(vamp_history), dimension(:, :), allocatable :: v_histories
type(integration_results_t) :: results
end type process_t

```

Initialization. We set up the hard-interaction parameters and make them available in the variable list (which extends the variable list of the current model). Finally, we initialize the subevent that is used for evaluating expressions.

The flag `use_beams` may be set false. In that case, beam (and structure function) data are meaningless or are skipped. For a scattering process, a head-to-head collision is assumed. For a decay process, the particle is assumed to decay in its rest frame. The initial state is assumed unpolarized.

If a variable list is provided as an argument, it replaces the model variable list. This implies that it should be linked to the model variable list.

```

<Processes: procedures> +=
  subroutine process_init &

```

```

        (process, prc_lib, process_lib_index, process_store_index, &
         process_id, model, var_list, use_beams)
type(process_t), intent(out), target :: process
type(process_library_t), intent(in), target :: prc_lib
integer, intent(in) :: process_lib_index
integer, intent(in) :: process_store_index
type(string_t), intent(in) :: process_id
type(model_t), intent(in), target :: model
type(var_list_t), intent(in), target :: var_list
logical, intent(in), optional :: use_beams
integer :: n_in, n_out, n_tot
integer :: n_beam
process%prc_lib => prc_lib
process%lib_index = process_lib_index
process%store_index = process_store_index
process%id = process_id
process%md5sum = process_library_get_process_md5sum &
    (process%prc_lib, process%lib_index)
call hard_interaction_init &
    (process%hi, prc_lib, process_lib_index, process_id, model)
process%has_matrix_element = hard_interaction_get_n_flv (process%hi) /= 0
process%use_hi_color_factors = &
    var_list_get_lval (var_list, var_str ("?read_color_factors"))
process%model => hard_interaction_get_model_ptr (process%hi)
if (.not. hard_interaction_is_valid (process%hi)) then
    return
else
    process%id = hard_interaction_get_id (process%hi)
    if (.not. process%has_matrix_element) then
        process%initialized = .true.
        return
    end if
end if
if (present (use_beams)) then
    process%use_beams = use_beams
    process%has_extra_evaluators = use_beams
end if
n_in = hard_interaction_get_n_in (process%hi)
n_out = hard_interaction_get_n_out (process%hi)
n_tot = hard_interaction_get_n_tot (process%hi)
select case (n_in)
case (1); process%type = PRC_DECAY
case (2); process%type = PRC_SCATTERING
end select
allocate (process%flv_in (n_in))
call flavor_init (process%flv_in, &
    hard_interaction_get_first_pdg_in (process%hi), process%model)
allocate (process%flv_out (n_out))
call flavor_init (process%flv_out, &
    hard_interaction_get_first_pdg_out (process%hi), process%model)
allocate (process%mass_in (n_in))
process%mass_in = flavor_get_mass (process%flv_in)
if (process%use_beams) then
    n_beam = n_in

```

```

        process%averaging_factor = 1
    else
        n_beam = 0
        process%averaging_factor = &
            1._default / product (flavor_get_multiplicity (process%flv_in))
    end if
    call process_assign_global_var_list (process, var_list)

!   process%old_phs_version = &
!       var_list_get_lval (var_list, var_str ("?old_phs_version"))

process%negative_weights = &
    var_list_get_lval (var_list, var_str ("?negative_weights"))
process%fatal_beam_decay = &
    var_list_get_lval (var_list, var_str ("?fatal_beam_decay"))

call var_list_append_int (process%var_list, &
    var_str ("n_in"), n_in, intrinsic=.true.)
call var_list_append_int (process%var_list, &
    var_str ("n_out"), n_out, intrinsic=.true.)
call var_list_append_int (process%var_list, &
    var_str ("n_tot"), n_tot, intrinsic=.true.)
call var_list_append_real_ptr (process%var_list, &
    var_str ("sqrts"), process%sqrts, process%sqrts_known, &
    intrinsic=.true.)
call var_list_append_real_ptr (process%var_list, &
    var_str ("sqrts_hat"), process%sqrts_hat, process%sqrts_hat_known, &
    intrinsic=.true.)
allocate (process%j_beam (n_beam))
allocate (process%j_in (n_in))
allocate (process%j_out (n_out))
call subvt_init (process%subvt, n_beam + n_in + n_out)
!   call integration_results_init (process%results)
process%filename_current_grid = ""
process%filename_best_grid = ""
process%initialized = .true.
end subroutine process_init

```

The QCD parameters, i.e., the treatment of α_s , is an issue of its own, so we delegate this to a separate subroutine. The input data pointers should be assigned if there is a structure function setup which contains those data. Otherwise they are null, and we take the info from the variable list.

If LHAPDF is required and not yet initialized, initialization is done here as a side-effect, and the status change is recorded.

```

<Processes: public>+≡
    public :: process_setup_qcd

<Processes: procedures>+≡
    subroutine process_setup_qcd (process, lhpdf_status, pdf_builtin_status, &
        lhpdf_data, pdf_builtin_data, os_data, var_list)
        type(process_t), intent(inout) :: process
        type(lhpdf_status_t), intent(inout) :: lhpdf_status
        type(pdf_builtin_status_t), intent(inout) :: pdf_builtin_status
        type(lhpdf_data_t), intent(in), pointer :: lhpdf_data
    end subroutine

```

```

type(pdf_builtin_data_t), intent(in), pointer :: pdf_builtin_data
type(os_data_t), intent(in) :: os_data
type(var_list_t), intent(in) :: var_list
type(string_t) :: lhpdf_dir, lhpdf_file
integer :: lhpdf_member
type(string_t) :: pdf_builtin_set
call qcd_parameters_basic_setup (process%qcd, var_list)
if (associated (lhpdf_data)) then
    call lhpdf_data_get_public_info (lhpdf_data, &
        lhpdf_dir, lhpdf_file, lhpdf_member)
    call qcd_parameters_setup_lhpdf (process%qcd, lhpdf_status, &
        lhpdf_dir, lhpdf_file, lhpdf_member)
else
    call qcd_parameters_setup_lhpdf (process%qcd, lhpdf_status, &
        var_list=var_list)
end if
if (associated (pdf_builtin_data)) then
    pdf_builtin_set = pdf_builtin_get_name (pdf_builtin_data)
    call qcd_parameters_setup_pdf_builtin (process%qcd, pdf_builtin_status, &
        os_data%pdf_builtin_datapath, pdf_builtin_set)
else
    call qcd_parameters_setup_pdf_builtin (process%qcd, pdf_builtin_status, &
        os_data%pdf_builtin_datapath, var_list=var_list)
end if
process%md5sum_alpha_s = qcd_parameters_get_md5sum (process%qcd)
end subroutine process_setup_qcd

```

Return the type of PDFs

```

<Processes: public>+≡
    public :: process_get_strfun_type

<Processes: procedures>+≡
    function process_get_strfun_type(process) result(type)
        type(process_t), intent(in) :: process
        integer :: type
        type = strfun_chain_get_strfun_type(process%sfchain)
    end function process_get_strfun_type

```

Return the member of the PDF used

```

<Processes: public>+≡
    public :: process_get_strfun_set

<Processes: procedures>+≡
    function process_get_strfun_set(process) result(set)
        type(process_t), intent(in) :: process
        integer :: set
        set = strfun_chain_get_strfun_set(process%sfchain)
    end function process_get_strfun_set

```

Make a snapshot of the global variable list and link it to the process variables.
This can be redone, so make sure a previous snapshot is deleted.

```

<Processes: public>+≡
    public :: process_assign_global_var_list

```

```

(Processes: procedures) +=
  subroutine process_assign_global_var_list (process, var_list)
    type(process_t), intent(inout) :: process
    type(var_list_t), intent(in), optional, target :: var_list
    type(var_list_t), pointer :: var_list_snapshot
    var_list_snapshot => var_list_get_next_ptr (process%var_list)
    if (associated (var_list_snapshot)) then
      call var_list_final (var_list_snapshot)
      deallocate (var_list_snapshot)
    end if
    allocate (var_list_snapshot)
    call var_list_link (process%var_list, var_list_snapshot)
    if (present (var_list)) then
      call var_list_init_snapshot (var_list_snapshot, var_list)
    else
      call var_list_init_snapshot (var_list_snapshot, &
        model_get_var_list_ptr (process%model))
    end if
  end subroutine process_assign_global_var_list

```

Finalization. In process copies, some components are just pointers to the original, so they should not be finalized separately.

```

(Processes: procedures) +=
  recursive subroutine process_final (process)
    type(process_t), intent(inout), target :: process
    call process_delete_copies (process)
    process%initialized = .false.
    process%type = PRC_UNKNOWN
    process%sqrts_known = .false.
    process%sqrts_hat_known = .false.
    call strfun_chain_final (process%sfchain)
    call hard_interaction_final (process%hi)
    call evaluator_final (process%eval_trace)
    call evaluator_final (process%eval_beam_flows)
    call evaluator_final (process%eval_sqme)
    call evaluator_final (process%eval_flows)
    call phs_forest_final (process%forest)
    call vamp_equivalences_final (process%vamp_eq)
    if (process%is_original) then
      call var_list_final (process%var_list)
      call eval_tree_final (process%cut_expr)
      call eval_tree_final (process%reweighting_expr)
      call eval_tree_final (process%scale_expr)
      call eval_tree_final (process%fac_scale_expr)
      call eval_tree_final (process%ren_scale_expr)
    end if
    if (process%vamp_grids_defined) then
      call vamp_delete_grids (process%grids)
    end if
    call process_final_vamp_history (process)
  end subroutine process_final

```

Output. This prints lots of stuff. The verbose option is for state matrices, the

`show_momentum_sum` option prints the sums of incoming and outgoing momenta for all interactions, and the `show_mass` option computes and prints the signed invariant mass for all four-momenta.

```

(Processes: public)+≡
    public :: process_write

(Processes: procedures)+≡
    subroutine process_write &
        (process, unit, verbose, show_momentum_sum, show_mass)
        type(process_t), intent(in) :: process
        integer, intent(in), optional :: unit
        logical, intent(in), optional :: verbose, show_momentum_sum, show_mass
        integer :: u, i
        u = output_unit(unit); if (u < 0) return
        write (u, "(A)") repeat ("=", 72)
        write (u, *) "Process data:", process%lib_index, &
            "(", char (process%id), ")"
        select case (process%type)
        case (PRC_UNKNOWN); write (u, *) " [unknown]"
        case (PRC_DECAY); write (u, *) " [decay]"
        case (PRC_SCATTERING); write (u, *) " [scattering]"
        end select
        write (u, *) " is cascade decay = ", process%is_cascade_decay
        write (u, *) " use separate beam setup = ", process%use_beams
        call beam_data_write (process%beam_data, u)
        if (process%use_beams) then
            write (u, *) " number of structure functions = ", process%n_strfun
            write (u, *) " number of strfun parameters = ", process%n_par_strfun
        end if
        write (u, *) " number of process parameters = ", process%n_par_hi
        write (u, *) " number of parameters total = ", process%n_par
        write (u, *) " number of integration channels = ", process%n_channels
        write (u, *) " number of bins per channel = ", process%n_bins
        if (process%sqrts_known) then
            write (u, *) " c.m. energy (sqrts) = ", process%sqrts
        else
            write (u, *) " c.m. energy (sqrts) = [unknown]"
        end if
        write (u, *) repeat("-", 72)
        call process_status_write (process%status, u)
        write (u, *) repeat("-", 72)
        write (u, *) "Evaluation results:"
        if (process%sqrts_hat_known) then
            write (u, *) " c.m. energy (sqrts_hat) = ", process%sqrts_hat
        else
            write (u, *) " c.m. energy (sqrts_hat) = [unknown]"
        end if
        write (u, "(1x,A)", advance="no") " Colliding partons = "
        if (allocated (process%flv_in)) then
            do i = 1, size (process%flv_in)
                if (i == 2) write (u, "(1x)", advance="no")
                call flavor_write (process%flv_in(i), u)
            end do
        end if
        write (u, *)
    end subroutine process_write

```

```

else
    write (u, *) "[undefined]"
end if
if (allocated (process%mass_in)) then
    write (u, *) " Incoming parton masses = ", process%mass_in
else
    write (u, *) " Incoming parton masses = [unknown]"
end if
write (u, *) " In-state flux factor = ", process%flux_factor
write (u, *) " Strfun mapping factor = ", process%sf_mapping_factor
if (.not. process%use_beams) then
    write (u, *) " Spin averaging factor = ", process%averaging_factor
end if
write (u, *) " VAMP phs factor = ", process%vamp_phs_factor
write (u, *) " Phase-space volume = ", process%phs_volume
write (u, *) " Squared matrix element = ", process%sqme
write (u, *) " Reweighting factor = ", process%reweighting_factor
write (u, *) " Sample-function value = ", &
    process%sample_function_value
write (u, *) repeat("-", 72)
write (u, *) "Structure function parameters ="
write (u, *) " Use beams = ", process%use_beams
write (u, *) " x values = "
if (allocated (process%x_strfun)) then
    write (u, *) process%x_strfun
else
    write (u, *) " [not allocated]"
end if
write (u, *) " Mapping factors (channels) ="
if (allocated (process%sf_factor)) then
    write (u, *) process%sf_factor
else
    write (u, *) " [not allocated]"
end if
write (u, *) " General scale = ", process%scale
write (u, *) " Factorization scale = ", process%fac_scale
write (u, *) " Renormalization scale = ", process%ren_scale
write (u, *) repeat("-", 72)
call qcd_parameters_write (process%qcd, u)
write (u, *) repeat("-", 72)
write (u, *) "Phase-space integration parameters (input) ="
if (allocated (process%x_hi)) then
    write (u, *) process%x_hi
else
    write (u, *) "[empty]"
end if
write (u, *) "Integration channel =", process%channel
write (u, *) "Phase-space integration parameters (complete) ="
if (allocated (process%x)) then
    do i = 1, size (process%x, 2)
        write (u, *) process%x(:,i)
    end do
else
    write (u, *) "[empty]"

```

```

end if
if (.not. process%lab_is_cm_frame) then
    write (u, *) "Transformation c.m. -> lab ="
    call lorentz_transformation_write (process%lt_cm_to_lab, u)
end if
write (u, *) "Channels: phase-space factors ="
if (allocated (process%phs_factor)) then
    write (u, *) process%phs_factor
else
    write (u, *) "[not allocated]"
end if
write (u, "(A)") repeat("-", 72)
if (process%use_beams) then
    call strfun_chain_write &
        (process%sfchain, unit, verbose, show_momentum_sum, show_mass)
    write (u, "(A)") repeat("-", 72)
    write (u, "(A)") "Incoming beams with all color contractions"
    call evaluator_write &
        (process%eval_beam_flows, unit, verbose, show_momentum_sum, show_mass)
    write (u, "(A)") repeat("-", 72)
end if
call hard_interaction_write &
    (process%hi, unit, verbose, show_momentum_sum, show_mass)
write (u, "(A)") repeat("-", 72)
if (process%has_extra_evaluators) then
    write (u, "(A)") "Trace including color factors (beams + strfun + hard interaction)"
    call evaluator_write &
        (process%eval_trace, unit, verbose, show_momentum_sum, show_mass)
    write (u, "(A)") repeat("-", 72)
    write (u, "(A)") "Exclusive sqme including color factors (beams + strfun + hard interaction)"
    call evaluator_write &
        (process%eval_sqme, unit, verbose, show_momentum_sum, show_mass)
    write (u, "(A)") repeat("-", 72)
    write (u, "(A)") "Color flow coefficients (beams + strfun + hard interaction)"
    call evaluator_write &
        (process%eval_flows, unit, verbose, show_momentum_sum, show_mass)
    write (u, "(A)") repeat("-", 72)
end if
call phs_forest_write (process%forest, unit)
write (u, "(A)") repeat("-", 72)
call vamp_equivalences_write (process%vamp_eq, unit)
write (u, "(A)") repeat("-", 72)
write (u, "(A)") "Subevent used by cuts, weight, and scale:"
write (u, "(A)", advance="no") &
    " Beam indices (in the trace evaluator): "
if (allocated (process%j_beam)) then
    write (u, *) process%j_beam
else
    write (u, *) "[undefined]"
end if
write (u, "(A)", advance="no") &
    " In-parton indices (in the trace evaluator): "
if (allocated (process%j_out)) then
    write (u, *) process%j_in

```

```

else
    write (u, *) "[undefined]"
end if
write (u, "(A)", advance="no") &
    " Out-parton indices (in the trace evaluator): "
if (allocated (process%j_out)) then
    write (u, *) process%j_out
else
    write (u, *) "[undefined]"
end if
call subevt_write (process%subevt, unit)
write (u, "(A)") repeat ("-", 72)
call var_list_write (process%var_list, unit)
write (u, "(A)") repeat ("-", 72)
write (u, "(A)") "Cut expression:"
call eval_tree_write (process%cut_expr, unit)
write (u, "(A)") repeat ("-", 72)
write (u, "(A)") "Weight expression:"
call eval_tree_write (process%reweighting_expr, unit)
write (u, "(A)") repeat ("-", 72)
write (u, "(A)") "General scale expression:"
call eval_tree_write (process%scale_expr, unit)
write (u, "(A)") repeat ("-", 72)
write (u, "(A)") "Factorization scale expression:"
call eval_tree_write (process%fac_scale_expr, unit)
write (u, "(A)") repeat ("-", 72)
write (u, "(A)") "Renormalization scale expression:"
call eval_tree_write (process%ren_scale_expr, unit)
write (u, "(A)") repeat ("-", 72)
if (process%vamp_grids_defined) then
    write (u, "(A)") "Integration grid data"
    write (u, *)
    write (u, "(A)") "Grid file name (current) = " // ' ' &
        // char (process%filename_current_grid) // ' '
    write (u, "(A)") "Grid file name (best) = " // ' ' &
        // char (process%filename_best_grid) // ' '
    write (u, *)
    write (u, "(A)") "MD5 sums stored in grid file"
    call md5sum_grids_write (process%md5sum_grids, u)
    write (u, *)
    write (u, "(A)") "Grid parameters stored in grid file"
    call grid_parameters_write (process%grid_parameters, u)
    write (u, *)
    write (u, "(A)", advance="no") "Iterations: pass array = "
    if (allocated (process%pass_array)) then
        write (u, *) process%pass_array
    else
        write (u, *) "[not allocated]"
    end if
    write (u, "(A)", advance="no") "Iterations: n_calls array = "
    if (allocated (process%n_calls_array)) then
        write (u, *) process%n_calls_array
    else
        write (u, *) "[not allocated]"
    end if
end if

```

```

        end if
        write (u, *)
        write (u, "(A)", advance="no") "VAMP grids:"
        call vamp_write_grids (process%grids, u)
    else
        write (u, "(A)") "VAMP grids: [empty]"
    end if
    write (u, "(A)") repeat ("-", 72)
    if (allocated (process%v_history)) then
        call msg_message (" Global history [vamp]:", unit=u)
        call vamp_write_history (u, process%v_history)
    else
        call msg_message (" Global history [vamp]: [undefined]", unit=u)
    end if
    write (u, "(A)") repeat ("-", 72)
    if (allocated (process%v_histories)) then
        call msg_message (" Channel histories [vamp]:", unit=u)
        call vamp_write_history (u, process%v_histories)
    else
        call msg_message (" Channel histories [vamp]: [undefined]", unit=u)
    end if
    write (u, *)
    call integration_results_write (process%results, unit)
    call integration_results_write_grove_weights (process%results, unit)
end subroutine process_write

```

This version is intended for the logfile. We do not write internal data.

(Processes: procedures)+≡

```

subroutine process_write_log (process, unit)
    type(process_t), intent(in) :: process
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit)
    write (u, "(A)") repeat ("#", 79)
    write (u, *) "Process ID = '" // char (process%id) // "'"
    write (u, "(A)") repeat ("#", 79)
    write (u, *) "Integral    = ", process_get_integral (process)
    write (u, *) "Error        = ", process_get_error (process)
    write (u, *) "Accuracy     = ", process_get_accuracy (process)
    write (u, *) "Chi2         = ", process_get_chi2 (process)
    write (u, *) "Efficiency   = ", process_get_efficiency (process)
    write (u, *) "Time/evt     = ", process_get_time_per_event (process)
    call integration_results_write (process%results, unit)
    write (u, "(A)") repeat ("#", 79)
    call process_status_write_counters (process%status, unit)
    write (u, "(A)") repeat ("#", 79)
    call integration_results_write_grove_weights (process%results, unit)
    write (u, "(A)") repeat ("#", 79)
    call beam_data_write (process%beam_data, u)
    write (u, "(A)") repeat ("#", 79)
    write (u, "(A)") "Cut expression:"
    call eval_tree_write (process%cut_expr, unit)
    write (u, "(A)") repeat ("-", 79)

```

```

write (u, "(A)") "Weight expression:"
call eval_tree_write (process%reweighting_expr, unit)
write (u, "(A)") repeat ("-", 79)
write (u, "(A)") "General scale expression:"
call eval_tree_write (process%scale_expr, unit)
write (u, "(A)") repeat ("-", 79)
write (u, "(A)") "Factorization scale expression:"
call eval_tree_write (process%fac_scale_expr, unit)
write (u, "(A)") repeat ("-", 79)
write (u, "(A)") "Renormalization scale expression:"
call eval_tree_write (process%ren_scale_expr, unit)
write (u, "(A)") repeat ("#", 79)
write (u, "(A)") "Summary of quantum-number states:"
write (u, "(A)") " + sign: allowed and contributing"
write (u, "(A)") " no + : switched off at runtime"
write (u, "(A)") repeat ('-', 79)
call hard_interaction_write_state_summary (process%hi, unit)
write (u, "(A)") repeat ("#", 79)
if (allocated (process%v_history)) then
    call msg_message ("Global history [vamp]:", unit=u)
    call vamp_write_history (u, process%v_history)
else
    call msg_message ("Global history [vamp]: [undefined]", unit=u)
end if
write (u, "(A)") repeat ("-", 72)
if (allocated (process%v_histories)) then
    call msg_message ("Channel histories [vamp]:", unit=u)
    call vamp_write_history (u, process%v_histories)
else
    call msg_message ("Channel histories [vamp]: [undefined]", unit=u)
end if
write (u, "(A)") repeat ("-", 72)
call msg_message ("Equivalences between channels", unit=u)
call vamp_equivalences_write (process%vamp_eq, unit=u)
write (u, "(A)") repeat ("#", 79)
write (u, "(A)") "Variable list:"
call var_list_write (process%var_list, unit)
write (u, "(A)") repeat ("#", 79)
end subroutine process_write_log

```

Write a complete logfile (with hardcoded name based on the process ID).

(Processes: public)+≡

```
public :: process_write_logfile
```

(Processes: procedures)+≡

```

subroutine process_write_logfile (process, filename)
    type(process_t), intent(in) :: process
    type(string_t), intent(in) :: filename
    integer :: unit
    unit = free_unit ()
    open (unit = unit, file = char (filename), action = "write", &
        status = "replace")
    call process_write_log (process, unit)
    close (unit)

```

```
end subroutine process_write_logfile
```

Run LaTeX/Metapost to generate a ps/pdf file for the integration history. We (re)write the driver file – just in case it has been missed before – then we compile it.

```
<Processes: public>+≡
  public :: process_display_integration_history

<Processes: procedures>+≡
  subroutine process_display_integration_history (process, filename, os_data)
    type(process_t), intent(in) :: process
    type(string_t), intent(in) :: filename
    type(os_data_t), intent(in) :: os_data
    call integration_results_write_driver (process%results, filename)
    call integration_results_compile_driver (process%results, filename, os_data)
  end subroutine process_display_integration_history
```

13.3.10 Process pointers

We will need arrays of process pointers, therefore this type, which we keep transparent:

```
<Processes: public>+≡
  public :: process_p

<Processes: types>+≡
  type :: process_p
    type(process_t), pointer :: ptr
  end type process_p
```

Set up an array of process pointers, given the process IDs.

```
<Processes: public>+≡
  public :: process_ptr_array_create

<Processes: procedures>+≡
  subroutine process_ptr_array_create (prc_array, process_id)
    type(process_p), dimension(:), intent(out), allocatable :: prc_array
    type(string_t), dimension(:), intent(in) :: process_id
    integer :: proc, n_proc
    n_proc = size (process_id)
    allocate (prc_array (n_proc))
    do proc = 1, n_proc
      prc_array(proc)%ptr => process_store_get_process_ptr (process_id(proc))
    end do
  end subroutine process_ptr_array_create
```

13.3.11 Accessing contents

Check if the process has been successfully initialized:

```
<Processes: public>+≡
  public :: process_is_valid
```

```

<Processes: procedures>+≡
    function process_is_valid (process) result (flag)
        logical :: flag
        type(process_t), intent(in) :: process
        flag = process%initialized
    end function process_is_valid

```

Check if the process has a nonvanishing matrix element:

```

<Processes: public>+≡
    public :: process_has_matrix_element

<Processes: procedures>+≡
    function process_has_matrix_element (process) result (flag)
        logical :: flag
        type(process_t), intent(in) :: process
        flag = process%has_matrix_element
    end function process_has_matrix_element

```

Check if the process has been integrated:

```

<Processes: public>+≡
    public :: process_has_integral

<Processes: procedures>+≡
    function process_has_integral (process) result (flag)
        logical :: flag
        type(process_t), intent(in) :: process
        flag = integration_results_exist (process%results)
    end function process_has_integral

```

Check if the uses a nontrivial beam setup:

```

<Processes: public>+≡
    public :: process_uses_beams

<Processes: procedures>+≡
    function process_uses_beams (process) result (flag)
        logical :: flag
        type(process_t), intent(in) :: process
        flag = process%use_beams
    end function process_uses_beams

```

Return the process ID.

```

<Processes: public>+≡
    public :: process_get_id

<Processes: procedures>+≡
    function process_get_id (process) result (process_id)
        type(string_t) :: process_id
        type(process_t), intent(in) :: process
        process_id = process%id
    end function process_get_id

```

Return the index in the process library:

```

<Processes: public>+≡
    public :: process_get_lib_index

```



```

<Processes: procedures>+≡
function process_get_lib_index (process) result (index)
    integer :: index
    type(process_t), intent(in) :: process
    index = process%lib_index
end function process_get_lib_index

```

Return the index in the process store:

```

<Processes: public>+≡
public :: process_get_store_index

<Processes: procedures>+≡
function process_get_store_index (process) result (index)
    integer :: index
    type(process_t), intent(in) :: process
    index = process%store_index
end function process_get_store_index

```

Return the MD5 sum of the process configuration.

```

<Processes: public>+≡
public :: process_get_md5sum
public :: process_get_md5sum_parameters
public :: process_get_md5sum_results
public :: process_get_md5sum_polarized

<Processes: procedures>+≡
function process_get_md5sum (process) result (md5sum)
    character(32) :: md5sum
    type(process_t), intent(in) :: process
    md5sum = process%md5sum
end function process_get_md5sum

function process_get_md5sum_parameters (process) result (md5sum)
    character(32) :: md5sum
    type(process_t), intent(in) :: process
    md5sum = model_get_parameters_md5sum (process%model)
end function process_get_md5sum_parameters

function process_get_md5sum_results (process) result (md5sum)
    character(32) :: md5sum
    type(process_t), intent(in) :: process
    md5sum = integration_results_get_md5sum (process%results)
end function process_get_md5sum_results

function process_get_md5sum_polarized (process) result (md5sum)
    character(32) :: md5sum
    type(process_t), intent(in) :: process
    md5sum = model_get_polarized_md5sum (process%model)
end function process_get_md5sum_polarized

```

Return the model pointer.

```

<Processes: public>+≡
public :: process_get_model_ptr

```

```

<Processes: procedures>+=
  function process_get_model_ptr (process) result (model)
    type(model_t), pointer :: model
    type(process_t), intent(in) :: process
    model => process%model
  end function process_get_model_ptr

```

Return the number of incoming partons for the hard interaction

```

<Processes: public>+=
  public :: process_get_n_in
  public :: process_get_n_out
  public :: process_get_n_tot

<Processes: procedures>+=
  pure function process_get_n_in (process) result (n)
    integer :: n
    type(process_t), intent(in) :: process
    n = hard_interaction_get_n_in (process%hi)
  end function process_get_n_in

  pure function process_get_n_out (process) result (n)
    integer :: n
    type(process_t), intent(in) :: process
    n = hard_interaction_get_n_out (process%hi)
  end function process_get_n_out

  pure function process_get_n_tot (process) result (n)
    integer :: n
    type(process_t), intent(in) :: process
    n = hard_interaction_get_n_tot (process%hi)
  end function process_get_n_tot

  pure function process_get_n_flv (process) result (n)
    integer :: n
    type(process_t), intent(in) :: process
    n = hard_interaction_get_n_flv (process%hi)
  end function process_get_n_flv

```

Return the indices of incoming beams / partons. These indices apply to the subevents in the evaluator interactions.

Without allocate-on-assignment, let us use subroutines.

```

<Processes: public>+=
  public :: process_get_beam_index
  public :: process_get_incoming_parton_index
  public :: process_get_outgoing_parton_index

<Processes: procedures>+=
  subroutine process_get_beam_index (process, index)
    type(process_t), intent(in) :: process
    integer, dimension(:), allocatable, intent(out) :: index
    allocate (index (size (process%j_beam)))
    index = process%j_beam
  end subroutine process_get_beam_index

```

```

subroutine process_get_incoming_parton_index (process, index)
  type(process_t), intent(in) :: process
  integer, dimension(:), allocatable, intent(out) :: index
  allocate (index (size (process%j_in)))
  index = process%j_in
end subroutine process_get_incoming_parton_index

subroutine process_get_outgoing_parton_index (process, index)
  type(process_t), intent(in) :: process
  integer, dimension(:), allocatable, intent(out) :: index
  allocate (index (size (process%j_out)))
  index = process%j_out
end subroutine process_get_outgoing_parton_index

```

Return the beam/incoming particle flavors and energies.

```

<Processes: public>+≡
  public :: process_get_beam_flv
  public :: process_get_beam_energy

<Processes: procedures>+≡
  function process_get_beam_flv (process) result (flv_in)
    type(flavor_t), dimension(:), allocatable :: flv_in
    type(process_t), intent(in) :: process
    allocate (flv_in (process_get_n_in (process)))
    if (process%beam_data%initialized) flv_in = process%beam_data%flv
  end function process_get_beam_flv

  function process_get_beam_energy (process) result (energy)
    real(default), dimension(:), allocatable :: energy
    type(process_t), intent(in) :: process
    allocate (energy (process_get_n_in (process)))
    energy = beam_data_get_energy (process%beam_data)
  end function process_get_beam_energy

```

Return the number of integration parameters.

```

<Processes: public>+≡
  public :: process_get_n_parameters

<Processes: procedures>+≡
  function process_get_n_parameters (process) result (n)
    integer :: n
    type(process_t), intent(in) :: process
    n = process%n_par
  end function process_get_n_parameters

```

Return the number of integration channels.

```

<Processes: public>+≡
  public :: process_get_n_channels

<Processes: procedures>+≡
  function process_get_n_channels (process) result (n)
    integer :: n
    type(process_t), intent(in) :: process
    n = process%n_channels
  end function process_get_n_channels

```

```
end function process_get_n_channels
```

Return the number of bins per integration channel.

```
<Processes: public>+≡
  public :: process_get_n_bins

<Processes: procedures>+≡
  function process_get_n_bins (process) result (n)
    integer :: n
    type(process_t), intent(in) :: process
    n = process%n_bins
  end function process_get_n_bins
```

Return the process status record.

```
<Processes: public>+≡
  public :: process_get_status

<Processes: procedures>+≡
  function process_get_status (process) result (status)
    type(process_status_t) :: status
    type(process_t), intent(in) :: process
    status = process%status
  end function process_get_status
```

Return the process scales and the α_s value.

```
<Processes: public>+≡
  public :: process_get_scale
  public :: process_get_fac_scale
  public :: process_get_ren_scale
  public :: process_get_alpha_s

<Processes: procedures>+≡
  function process_get_scale (process) result (scale)
    real(default) :: scale
    type(process_t), intent(in) :: process
    scale = process%scale
  end function process_get_scale

  function process_get_fac_scale (process) result (scale)
    real(default) :: scale
    type(process_t), intent(in) :: process
    scale = process%fac_scale
  end function process_get_fac_scale

  function process_get_ren_scale (process) result (scale)
    real(default) :: scale
    type(process_t), intent(in) :: process
    scale = process%ren_scale
  end function process_get_ren_scale

  function process_get_alpha_s (process) result (alpha_s)
    real(default) :: alpha_s
    type(process_t), intent(in) :: process
    alpha_s = process%qcd%alpha_s_at_scale
```

```
end function process_get_alpha_s
```

Return the c.m. energy and the partonic c.m. energy.

```
<Processes: public>+=
  public :: process_get_sqrts
  public :: process_get_sqrts_hat

<Processes: procedures>+=
  function process_get_sqrts (process) result (sqrts)
    real(default) :: sqrts
    type(process_t), intent(in) :: process
    sqrts = process%sqrts
  end function process_get_sqrts

  function process_get_sqrts_hat (process) result (sqrts_hat)
    real(default) :: sqrts_hat
    type(process_t), intent(in) :: process
    sqrts_hat = process%sqrts_hat
  end function process_get_sqrts_hat
```

Return the squared matrix element. This includes structure function factors and the hard interaction squared matrix element, traced over all quantum numbers, but no phase space factors.

```
<Processes: public>+=
  public :: process_get_sqme

<Processes: procedures>+=
  function process_get_sqme (process) result (sqme)
    real(default) :: sqme
    type(process_t), intent(in) :: process
    sqme = process%sqme
  end function process_get_sqme
```

Return the user-defined reweighting factor that should be applied to the matrix element. In the sample-function value (integration and event generation), this is already included.

```
<Processes: public>+=
  public :: process_get_reweighting_factor

<Processes: procedures>+=
  function process_get_reweighting_factor (process) result (weight)
    real(default) :: weight
    type(process_t), intent(in) :: process
    weight = process%reweighting_factor
  end function process_get_reweighting_factor
```

Return the final integration results. If `last` is present and set, the final iteration; otherwise, the final average.

```
<Processes: public>+=
  public :: process_get_n_calls
  public :: process_get_integral
  public :: process_get_error
```

```

public :: process_get_accuracy
public :: process_get_chi2
public :: process_get_rel_error
public :: process_get_time_per_event
public :: process_get_efficiency
public :: process_get_sample_function_value

(Processes: procedures) +=
function process_get_n_calls (process, last, it, pass) result (n_calls)
    integer :: n_calls
    type(process_t), intent(in) :: process
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    n_calls = integration_results_get_n_calls &
        (process%results, last, it, pass)
end function process_get_n_calls

function process_get_integral (process, last, it, pass) result (integral)
    real(default) :: integral
    type(process_t), intent(in) :: process
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    integral = integration_results_get_integral &
        (process%results, last, it, pass)
end function process_get_integral

function process_get_error (process, last, it, pass) result (error)
    real(default) :: error
    type(process_t), intent(in) :: process
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    error = integration_results_get_error &
        (process%results, last, it, pass)
end function process_get_error

function process_get_accuracy (process, last, it, pass) result (accuracy)
    real(default) :: accuracy
    type(process_t), intent(in) :: process
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    accuracy = integration_results_get_accuracy &
        (process%results, last, it, pass)
end function process_get_accuracy

function process_get_chi2 (process, last, it, pass) result (chi2)
    real(default) :: chi2
    type(process_t), intent(in) :: process
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    chi2 = integration_results_get_chi2 &
        (process%results, last, it, pass)
end function process_get_chi2

function process_get_efficiency (process, last, it, pass) result (efficiency)
    real(default) :: efficiency

```

```

    type(process_t), intent(in) :: process
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    efficiency = integration_results_get_efficiency &
        (process%results, last, it, pass)
end function process_get_efficiency

function process_get_rel_error (process, last, it, pass) result (error)
    real(default) :: error
    type(process_t), intent(in) :: process
    logical, intent(in), optional :: last
    integer, intent(in), optional :: it, pass
    real(default) :: integral, abs_error
    integral = integration_results_get_integral &
        (process%results, last, it, pass)
    abs_error = integration_results_get_error &
        (process%results, last, it, pass)
    if (integral /= 0) then
        error = abs_error / abs (integral)
    else
        error = 0
    end if
end function process_get_rel_error

function process_get_time_per_event (process) result (tpe)
    real(default) :: tpe
    type(process_t), intent(in) :: process
    tpe = integration_results_get_time_per_event (process%results)
end function process_get_time_per_event

function process_get_sample_function_value (process) result (value)
    real(default) :: value
    type(process_t), intent(in) :: process
    value = process%sample_function_value
end function process_get_sample_function_value

```

Return the current (i.e., last) integration pass index, and the index of the last iteration *within* this pass. The third routine returns the absolute index of the last iteration.

(Processes: public)+≡

```

    public :: process_get_current_pass
    public :: process_get_current_it

```

(Processes: procedures)+≡

```

    function process_get_current_pass (process) result (pass)
        integer :: pass
        type(process_t), intent(in) :: process
        pass = integration_results_get_current_pass (process%results)
    end function process_get_current_pass

    function process_get_current_it (process) result (it)
        integer :: it
        type(process_t), intent(in) :: process
        it = integration_results_get_current_it (process%results)
    end function process_get_current_it

```

```

end function process_get_current_it

function process_get_last_it (process) result (it)
  integer :: it
  type(process_t), intent(in) :: process
  it = integration_results_get_last_it (process%results)
end function process_get_last_it

```

Return pointers to the sqme and flows evaluators. If no beams are used, these are identical to the evaluators of the hard interaction.

```

(Processes: public) +=
  public :: process_get_eval_sqme_ptr
  public :: process_get_eval_flows_ptr

(Processes: procedures) +=
  function process_get_eval_sqme_ptr (process) result (eval)
    type(evaluator_t), pointer :: eval
    type(process_t), intent(in), target :: process
    if (process%has_extra_evaluators) then
      eval => process%eval_sqme
    else
      eval => hard_interaction_get_eval_sqme_ptr (process%hi)
    end if
  end function process_get_eval_sqme_ptr

  function process_get_eval_flows_ptr (process) result (eval)
    type(evaluator_t), pointer :: eval
    type(process_t), intent(in), target :: process
    if (process%has_extra_evaluators) then
      eval => process%eval_flows
    else
      eval => hard_interaction_get_eval_flows_ptr (process%hi)
    end if
  end function process_get_eval_flows_ptr

```

Return pointers to the interaction and to the sqme and flows evaluators of the hard interaction.

```

(Processes: public) +=
  public :: process_get_hi_int_ptr
  public :: process_get_hi_eval_sqme_ptr
  public :: process_get_hi_eval_flows_ptr

(Processes: procedures) +=
  function process_get_hi_int_ptr (process) result (int)
    type(interaction_t), pointer :: int
    type(process_t), intent(in), target :: process
    int => hard_interaction_get_int_ptr (process%hi)
  end function process_get_hi_int_ptr

  function process_get_hi_eval_sqme_ptr (process) result (eval)
    type(evaluator_t), pointer :: eval
    type(process_t), intent(in), target :: process
    eval => hard_interaction_get_eval_sqme_ptr (process%hi)
  end function process_get_hi_eval_sqme_ptr

```



```

function process_get_hi_eval_flows_ptr (process) result (eval)
  type(evaluator_t), pointer :: eval
  type(process_t), intent(in), target :: process
  eval => hard_interaction_get_eval_flows_ptr (process%hi)
end function process_get_hi_eval_flows_ptr

```

Return any s-channel mapping for a particular tree in the decay forest.

```

<Processes: public>+≡
  public :: process_get_s_mapping

<Processes: procedures>+≡
  subroutine process_get_s_mapping (process, channel, flag, mass, width)
    type(process_t), intent(in) :: process
    integer, intent(in) :: channel
    logical, intent(out) :: flag
    real(default), intent(out) :: mass, width
    call phs_forest_get_s_mapping &
      (process%forest, channel, flag, mass, width)
  end subroutine process_get_s_mapping

```

13.3.12 Setting values directly

Mark a process as a cascade decay. The effect is that the process subevent will be boosted to the incoming c.m. frame (i.e., the rest frame of the decaying particle) before applying cuts etc.

```

<Processes: public>+≡
  public :: process_mark_as_cascade_decay

<Processes: procedures>+≡
  subroutine process_mark_as_cascade_decay (process)
    type(process_t), intent(inout) :: process
    process%is_cascade_decay = .true.
  end subroutine process_mark_as_cascade_decay

```

Some values can be set directly; this is used when reading an event from file.

```

<Processes: public>+≡
  public :: process_set_scale
  public :: process_set_fac_scale
  public :: process_set_ren_scale
  public :: process_set_alpha_s
  public :: process_set_sqme

<Processes: procedures>+≡
  subroutine process_set_scale (process, scale)
    type(process_t), intent(inout) :: process
    real(default), intent(in) :: scale
    process%scale = scale
  end subroutine process_set_scale

  subroutine process_set_fac_scale (process, scale)
    type(process_t), intent(inout) :: process

```

```

        real(default), intent(in) :: scale
        process%fac_scale = scale
    end subroutine process_set_fac_scale

    subroutine process_set_ren_scale (process, scale)
        type(process_t), intent(inout) :: process
        real(default), intent(in) :: scale
        process%ren_scale = scale
    end subroutine process_set_ren_scale

    subroutine process_set_alpha_s (process, alpha_s)
        type(process_t), intent(inout) :: process
        real(default), intent(in) :: alpha_s
        process%qcd%alpha_s_at_scale = alpha_s
    end subroutine process_set_alpha_s

    subroutine process_set_sqme (process, sqme)
        type(process_t), intent(inout) :: process
        real(default), intent(in) :: sqme
        process%sqme = sqme
    end subroutine process_set_sqme

```

Discard previous results, starting from the current iteration.

```

<Processes: public>+≡
    public :: process_discard_results

<Processes: procedures>+≡
    subroutine process_discard_results (process, it)
        type(process_t), intent(inout) :: process
        integer, intent(in) :: it
        call integration_results_discard (process%results, it)
    end subroutine process_discard_results

```

13.3.13 Process preparation: beams and structure functions

Set up the chain of structure functions. The individual types of structure functions need specific instances. These are just wrappers around the corresponding `strfun_chain` procedures.

If `use_beams` is false, only `sqrts` and `flv` is set, using the decaying particle mass (decay) or the `sqrts` value in the argument list (scattering) to set up a local beam record.

```

<Processes: public>+≡
    public :: process_setup_beams

<Processes: procedures>+≡
    subroutine process_setup_beams (process, beam_data, n_strfun, sqrts, flv)
        type(process_t), intent(inout), target :: process
        type(beam_data_t), intent(in) :: beam_data
        integer, intent(in) :: n_strfun
        real(default), intent(in), optional :: sqrts
        type(flavor_t), dimension(:), intent(in), optional :: flv
    end subroutine process_setup_beams

```

```

if (.not. process_has_matrix_element (process)) return
if (process%use_beams) then
  process%beam_data = beam_data
  process%sqrts = beam_data%sqrts
  process%sqrts_known = .true.
  process%n_strfun = n_strfun
  process%azimuthal_dependence = &
    .not. all (polarization_is_diagonal (beam_data%pol))
  process%lab_is_cm_frame = beam_data%lab_is_cm_frame .and. n_strfun == 0
  call strfun_chain_init (process%sfchain, beam_data, n_strfun)
else
  select case (process%type)
  case (PRC_DECAY)
    process%sqrts = process%mass_in(1)
    call beam_data_init_decay (process%beam_data, process%flv_in)
  case (PRC_SCATTERING)
    if (present (sqrts)) then
      process%sqrts = sqrts
      call beam_data_init_sqrts &
        (process%beam_data, process%sqrts, process%flv_in)
    else
      call msg_fatal ("Process setup: neither beams nor sqrts are known")
      process%sqrts = 0
    end if
  end select
  process%sqrts_known = .true.
end if
end subroutine process_setup_beams

```

Set the beam momenta directly without changing anything else. This is a short-cut that is needed for initiating cascade decays (i.e., the single beam is the decaying particle).

```

<Processes: public>+≡
  public :: process_set_beam_momenta

<Processes: procedures>+≡
  subroutine process_set_beam_momenta (process, p)
    type(process_t), intent(inout), target :: process
    type(vector4_t), dimension(:), intent(in) :: p
    type(interaction_t), pointer :: hi_int
    if (.not. process_has_matrix_element (process)) return
    if (process%use_beams) then
      call strfun_chain_set_beam_momenta (process%sfchain, p)
    else
      hi_int => hard_interaction_get_int_ptr (process%hi)
      call interaction_set_momenta (hi_int, p, outgoing=.false.)
    end if
    process%sqrts_hat = process%sqrts
    process%lab_is_cm_frame = .false.
    process%beams_are_set = .true.
  end subroutine process_set_beam_momenta

```

Configure structure functions. EPA: support only a single data set.

The index *i* is the overall structure function counter. *line* indicates the beam(s) for which the structure function applies, either 1 or 2, or 0 for both beams.

```

<Processes: public>+≡
    public :: process_set_strfun

<Processes: interfaces>+≡
    interface process_set_strfun
        module procedure process_set_strfun_lhapdf
        module procedure process_set_strfun_pdf_builtin
        module procedure process_set_strfun_isr
        module procedure process_set_strfun_epa
        module procedure process_set_strfun_ewa
        module procedure process_set_strfun_circe1
        module procedure process_set_strfun_circe2
        module procedure process_set_strfun_escan
        module procedure process_set_strfun_beam_events
        module procedure process_set_strfun_user
    end interface

<Processes: procedures>+≡
    subroutine process_set_strfun_lhapdf &
        (process, i, line, lhpdf_data, n_parameters)
        type(process_t), intent(inout), target :: process
        integer, intent(in) :: i, line, n_parameters
        type(lhpdf_data_t), intent(in) :: lhpdf_data
        if (process%use_beams) then
            call strfun_chain_set_strfun &
                (process%sfchain, i, line, lhpdf_data, n_parameters)
        end if
    end subroutine process_set_strfun_lhapdf

    subroutine process_set_strfun_pdf_builtin &
        (process, i, line, pdf_builtin_data, n_parameters)
        type(process_t), intent(inout), target :: process
        integer, intent(in) :: i, line, n_parameters
        type(pdf_builtin_data_t), intent(in) :: pdf_builtin_data
        if (process%use_beams) then
            call strfun_chain_set_strfun &
                (process%sfchain, i, line, pdf_builtin_data, n_parameters)
        end if
    end subroutine process_set_strfun_pdf_builtin

    subroutine process_set_strfun_isr &
        (process, i, line, isr_data, n_parameters)
        type(process_t), intent(inout), target :: process
        integer, intent(in) :: i, line, n_parameters
        type(isr_data_t), intent(in) :: isr_data
        if (process%use_beams) then
            call strfun_chain_set_strfun &
                (process%sfchain, i, line, isr_data, n_parameters)
        end if
    end subroutine process_set_strfun_isr

```

```

subroutine process_set_strfun_epa &
  (process, i, line, epa_data, n_parameters)
  type(process_t), intent(inout), target :: process
  integer, intent(in) :: i, line, n_parameters
!   type(epa_data_t), dimension(:), intent(in) :: epa_data
  type(epa_data_t), intent(in) :: epa_data
  if (process%use_beams) then
    call strfun_chain_set_strfun &
      (process%sfchain, i, line, epa_data, n_parameters)
  end if
end subroutine process_set_strfun_epa

subroutine process_set_strfun_ewa &
  (process, i, line, ewa_data, n_parameters)
  type(process_t), intent(inout), target :: process
  integer, intent(in) :: i, line, n_parameters
!   type(ewa_data_t), dimension(:), intent(in) :: ewa_data
  type(ewa_data_t), intent(inout) :: ewa_data
  integer :: k
  integer, dimension(process_get_n_tot(process), &
    process_get_n_flv(process)) :: flvs_tot
  integer, dimension(process_get_n_flv(process)) :: flvs
  flvs_tot = hard_interaction_get_flv_states (process%hi)
  flvs(:) = abs(flvs_tot (line,:))
  do k = 1, size (flvs)
    if (flvs(1) /= flvs (k)) &
      call msg_fatal ("EWA approximation is not applicable when " &
        // "mixing W and Z for a single beam.")
  end do
  if (flvs(1) < 23 .or. flvs(1) > 24) &
    call msg_fatal ("Hard scattering process does not match EWA.")
  if (process%use_beams) then
    call strfun_chain_set_strfun &
      (process%sfchain, i, line, ewa_data, n_parameters, flvs(1))
  end if
end subroutine process_set_strfun_ewa

subroutine process_set_strfun_circe1 &
  (process, i, line, circe1_data, n_parameters)
  type(process_t), intent(inout), target :: process
  integer, intent(in) :: i, line, n_parameters
  type(circe1_data_t), intent(in) :: circe1_data
  if (process%use_beams) then
    call strfun_chain_set_strfun &
      (process%sfchain, i, line, circe1_data, n_parameters)
  end if
end subroutine process_set_strfun_circe1

subroutine process_set_strfun_circe2 &
  (process, i, line, circe2_data, n_parameters)
  type(process_t), intent(inout), target :: process
  integer, intent(in) :: i, line, n_parameters
  type(circe2_data_t), intent(in) :: circe2_data
  if (process%use_beams) then

```

```

        call strfun_chain_set_strfun &
            (process%sfchain, i, line, circe2_data, n_parameters)
    end if
end subroutine process_set_strfun_circe2

subroutine process_set_strfun_escan &
    (process, i, line, escan_data, n_parameters)
    type(process_t), intent(inout), target :: process
    integer, intent(in) :: i, line, n_parameters
    type(escan_data_t), intent(in) :: escan_data
    if (process%use_beams) then
        call strfun_chain_set_strfun &
            (process%sfchain, i, line, escan_data, n_parameters)
    end if
end subroutine process_set_strfun_escan

subroutine process_set_strfun_beam_events &
    (process, i, line, beam_events_data, n_parameters)
    type(process_t), intent(inout), target :: process
    integer, intent(in) :: i, line, n_parameters
    type(beam_events_data_t), intent(in) :: beam_events_data
    if (process%use_beams) then
        call strfun_chain_set_strfun &
            (process%sfchain, i, line, beam_events_data, n_parameters)
    end if
end subroutine process_set_strfun_beam_events

subroutine process_set_strfun_user &
    (process, i, line, user_data, n_parameters)
    type(process_t), intent(inout), target :: process
    integer, intent(in) :: i, line, n_parameters
    type(sf_user_data_t), intent(in) :: user_data
    if (process%use_beams) then
        call strfun_chain_set_strfun &
            (process%sfchain, i, line, user_data, n_parameters)
    end if
end subroutine process_set_strfun_user

```

Configure structure function mappings.

(Processes: public)+≡

```

    public :: process_allocate_strfun_mappings
    public :: process_set_strfun_mapping

```

(Processes: procedures)+≡

```

subroutine process_allocate_strfun_mappings &
    (process, multichannel, n_mapping)
    type(process_t), intent(inout) :: process
    logical, intent(in) :: multichannel
    integer, intent(in), optional :: n_mapping
    if (.not. multichannel .and. present (n_mapping)) then
        call strfun_chain_allocate_mappings &
            (process%sfchain, multichannel, n_mapping, 1)
    else if (multichannel .and. .not. present (n_mapping)) then
        call strfun_chain_allocate_mappings &

```

```

        (process%sfchain, multichannel, 1, process%n_channels)
        allocate (process%sf_factor (process%n_channels))
    else
        print *, "multichannel = ", multichannel
        call msg_bug ("allocate strfun mappings: inconsistent parameters")
    end if
end subroutine process_allocate_strfun_mappings

subroutine process_set_strfun_mapping (process, i, ch, index, type, par)
    type(process_t), intent(inout) :: process
    integer, intent(in) :: i, ch
    integer, intent(in) :: type
    integer, dimension(:), intent(in) :: index
    real(default), dimension(:), intent(in) :: par
    call strfun_chain_set_mapping (process%sfchain, i, ch, index, type, par)
end subroutine process_set_strfun_mapping

```

Complete structure function initialization. Make evaluators within the structure function chain, and the trace evaluator within the hard interaction. Connect the two, and make another trace evaluator which sums over all quantum numbers. This evaluator should have only a single matrix element.

```

<Processes: public>+≡
    public :: process_connect_strfun

<Processes: procedures>+≡
    subroutine process_connect_strfun (process, ok)
        type(process_t), intent(inout), target :: process
        logical, intent(out), optional :: ok
        integer, dimension(:), allocatable :: coll_index
        type(quantum_numbers_mask_t), dimension(:), allocatable :: mask_in
        type(quantum_numbers_mask_t) :: mask_tr
        type(evaluator_t), pointer :: eval_sfchain, eval_hi
        type(interaction_t), pointer :: int_beam, int_hi
        integer :: n_in, i
        if (.not. process_has_matrix_element (process)) return
        n_in = hard_interaction_get_n_in (process%hi)
        allocate (mask_in (n_in))
        if (process%use_beams) then
            call strfun_chain_make_evaluators (process%sfchain, ok)
            allocate (coll_index (n_in))
            coll_index = strfun_chain_get_colliding_particles (process%sfchain)
            mask_in = strfun_chain_get_colliding_particles_mask (process%sfchain)
        else
            mask_in = new_quantum_numbers_mask (.true., .true., .true.)
        end if
        call hard_interaction_init_trace &
            (process%hi, mask_in, process%use_hi_color_factors)
        if (process%use_beams) then
            int_beam => strfun_chain_get_beam_int_ptr (process%sfchain)
            eval_sfchain => strfun_chain_get_last_evaluator_ptr (process%sfchain)
            eval_hi => hard_interaction_get_eval_trace_ptr (process%hi)
            int_hi => hard_interaction_get_int_ptr (process%hi)
            mask_tr = new_quantum_numbers_mask (.true., .true., .true.)
            if (associated (eval_sfchain)) then

```

```

do i = 1, n_in
  call interaction_set_source_link &
    (int_hi, i, eval_sfchain, coll_index(i))
  call evaluator_set_source_link &
    (eval_hi, i, eval_sfchain, coll_index(i))
end do
call evaluator_init_product &
  (process%eval_trace, eval_sfchain, eval_hi, mask_tr, mask_tr)
if (evaluator_is_empty (process%eval_trace)) then
  call msg_fatal ("Mismatch between structure functions and hard process")
  if (present (ok)) ok = .false.
  return
end if
else
do i = 1, n_in
  call interaction_set_source_link &
    (int_hi, i, int_beam, coll_index(i))
  call evaluator_set_source_link &
    (eval_hi, i, int_beam, coll_index(i))
end do
call evaluator_init_product &
  (process%eval_trace, int_beam, eval_hi, mask_tr, mask_tr)
if (evaluator_is_empty (process%eval_trace)) then
  call msg_fatal ("Mismatch between beams and hard process")
  if (present (ok)) ok = .false.
  return
end if
end if
process%n_par_strfun = &
  strfun_chain_get_n_parameters_tot (process%sfchain)
allocate (process%x_strfun (process%n_par_strfun))
end if
process%n_par = process%n_par_strfun + process%n_par_hi
if (present (ok)) ok = .true.
end subroutine process_connect_strfun

```

Check whether the current setting of relevant variables matches the current beam setup.

<Processes: public>+≡

```
public :: process_check_beam_setup
```

<Processes: procedures>+≡

```

subroutine process_check_beam_setup (process, var_list)
  type(process_t), intent(in) :: process
  type(var_list_t), intent(in) :: var_list
  logical :: sqrts_known
  real(default) :: sqrts
  sqrts_known = var_list_is_known (var_list, "sqrts")
  sqrts = var_list_get_rval (var_list, "sqrts")
  if (process%use_beams) then
    select case (process%type)
    case (PRC_SCATTERING)
      if (sqrts_known) then
        call beam_data_check_scattering (process%beam_data, sqrts)

```



```

        else
            call beam_data_check_scattering (process%beam_data)
        end if
    end select
end if
end subroutine process_check_beam_setup

```

13.3.14 Process preparation: phase space

Initialize the phase-space forest. First check whether the process exists in `filename_in`, if present, and try to read it there. If this fails, generate a new phase-space forest and write it to `filename_out`, if present, otherwise to a temporary file. Then read again.

Because `variable_limits` depends on the structure function setup, structure functions should be done first.

```

<Processes: public>+≡
    public :: process_setup_phase_space

<Processes: procedures>+≡
    subroutine process_setup_phase_space (process, rebuild_phs, &
        os_data, phs_par, mapping_defaults, filename_out, &
        filename_in, filename_vis, vis_channels, check_phs_file, ok)
        type(process_t), intent(inout), target :: process
        logical, intent(in) :: rebuild_phs
        type(os_data_t), intent(in) :: os_data
        type(phs_parameters_t), intent(inout) :: phs_par
        type(mapping_defaults_t), intent(in) :: mapping_defaults
        type(string_t), intent(in), optional :: &
            filename_out, filename_in, filename_vis
        logical, intent(in) :: vis_channels
        logical, intent(in), optional :: check_phs_file
        logical, intent(out), optional :: ok
        type(string_t) :: filename, setenv_tex, setenv_mp, &
            pipe, pipe_dvi
        logical :: exist, check
        integer :: extra_off_shell
        type(cascade_set_t) :: cascade_set
        logical :: variable_limits
        integer :: n_in, n_out, n_tot, n_flv
        type(flavor_t), dimension(:,:), allocatable :: flv
        integer :: n_par_strfun
        logical, dimension(:), allocatable :: strfun_rigid
        character(32) :: md5sum_process, md5sum_model, md5sum_parameters
        integer :: unit, unit_tex, unit_dev, status
        logical :: phs_ok, phs_match, wrote_file
        phs_ok = .false.
        phs_match = .false.
        variable_limits = process%n_strfun /= 0
        n_in = hard_interaction_get_n_in (process%hi)
        n_out = hard_interaction_get_n_out (process%hi)
        n_tot = hard_interaction_get_n_tot (process%hi)
        n_flv = hard_interaction_get_n_flv (process%hi)
    end subroutine process_setup_phase_space

```

```

allocate (flv (n_tot, n_flv))
call flavor_init (flv, &
    hard_interaction_get_flv_states (process%hi), process%model)
md5sum_process = process%md5sum
md5sum_model = model_get_md5sum (process%model)
md5sum_parameters = model_get_parameters_md5sum (process%model)
phs_par%sqrts = process%sqrts
if (present (filename_in)) then
    filename = filename_in
    check = .false.
else if (.not. rebuild_phs .and. present (filename_out)) then
    filename = filename_out
    if (present (check_phs_file)) then
        check = check_phs_file
    else
        check = .true.
    end if
else
    filename = ""
end if
if (filename /= "") then
    inquire (file=char(filename), exist=exist)
    if (exist) then
        if (check) then
            call phs_forest_read (process%forest, filename, &
                process%id, n_in, n_out, process%model, phs_ok, &
                md5sum_process, md5sum_model, md5sum_parameters, phs_par, &
                phs_match)
        else
            call msg_warning &
                ("Validity checks turned off for phase-space file " &
                // "" // char (filename) // "")
            call phs_forest_read (process%forest, filename, &
                process%id, n_in, n_out, process%model, phs_ok)
            phs_match = .true.
        end if
        if (phs_match) call msg_message &
            ("Reading phase-space configuration from file '" &
            // char (filename) // "'...")
        unit = free_unit ()
        open (unit = unit, file = char (filename), action = "read", &
            status = "old")
        process%md5sum_phs = md5sum (unit)
        close (unit)
        if (.not. phs_ok) then
            call msg_fatal ("Phase space file '" // char (filename) &
                // "' : No valid phase space for process '" &
                // char (process%id) // "'")
            if (present (ok)) ok = .false.
            return
        end if
    else
        call msg_message ("Phase space file '" // char (filename) &
            // "' not found.")
    end if
end if

```

```

        phs_match = .false.
    end if
end if
wrote_file = .false.
if (.not. phs_match) then
    call msg_message ("Generating phase space configuration ...")
    LOOP_OFF_SHELL: do extra_off_shell = 0, max (n_tot - 3, 0)
        call cascade_set_generate (cascade_set, &
            process%model, n_in, n_out, flv, phs_par, process%fatal_beam_decay)
        if (cascade_set_is_valid (cascade_set)) then
            exit LOOP_OFF_SHELL
        else if (phs_par%off_shell >= max (n_tot - 3, 0)) then
            call msg_error ("Process '" // char (process%id) &
                // "': no valid phase-space channels found")
            if (present (ok)) ok = .false.
            call cascade_set_final (cascade_set)
            return
        else
            write (msg_buffer, "(A,1x,I0)" &
                "Process '" // char (process%id) &
                // "': no valid phase-space channels found for " &
                // "phs_off_shell =", phs_par%off_shell)
            call msg_warning ()
            call msg_message ("Increasing phs_off_shell")
            phs_par%off_shell = phs_par%off_shell + 1
        end if
    end do LOOP_OFF_SHELL
    unit = free_unit ()
    if (present (filename_out)) then
        open (unit, file=char(filename_out), &
            action="readwrite", status="replace")
    else
        open (unit, action="readwrite", status="scratch")
    end if
    write (unit, *) "process ", char (process%id)
    write (unit, *)
    call cascade_set_write_process_bincode_format (cascade_set, unit)
    write (unit, *)
    write (unit, *) "  md5sum_process   = ", "'", md5sum_process, "'"
    write (unit, *) "  md5sum_model     = ", "'", md5sum_model, "'"
    write (unit, *) "  md5sum_parameters = ", "'", md5sum_parameters, "'"
    call phs_parameters_write (phs_par, unit)
    call cascade_set_write_file_format (cascade_set, unit)
    if (vis_channels) then
        unit_tex = free_unit ()
        open (unit=unit_tex, file=char(filename_vis // ".tex"), &
            action="write", status="replace")
        call cascade_set_write_graph_format (cascade_set, &
            filename_vis // ".graphs", process_get_id (process), unit_tex)
        close (unit_tex)
        call msg_message ("Writing visualized phase space channels file " &
            // char(trim(filename_vis)) // "...")
        if (os_data%event_analysis_ps) then
            BLOCK: do

```

```

unit_dev = free_unit ()
open (file = "/dev/null", unit = unit_dev, &
      action = "write", iostat = status)
if (status /= 0) then
  pipe = ""
  pipe_dvi = ""
else
  pipe = " > /dev/null"
  pipe_dvi = " 2>/dev/null 1>/dev/null"
end if
close (unit_dev)
if (os_data%whizard_texpath /= "") then
  setenv_tex = &
    "TEXINPUTS=" // os_data%whizard_texpath // " :$TEXINPUTS "
  setenv_mp = &
    "MPINPUTS=" // os_data%whizard_texpath // " :$MPINPUTS "
else
  setenv_tex = ""
  setenv_mp = ""
end if
call os_system_call (setenv_tex // os_data%latex // " " // &
  filename_vis // ".tex " // pipe, status)
if (status /= 0) exit BLOCK
if (os_data%mpost /= "") then
  call os_system_call (setenv_mp // os_data%mpost // " " // &
    filename_vis // ".graphs.mp" // pipe, status)
else
  call msg_fatal ("Could not use MetaPOST.")
end if
if (status /= 0) exit BLOCK
call os_system_call (setenv_tex // os_data%latex // " " // &
  filename_vis // ".tex" // pipe, status)
if (status /= 0) exit BLOCK
call os_system_call (os_data%dvips // " -o " // filename_vis &
  // ".ps " // filename_vis // ".dvi" // pipe_dvi, status)
if (status /= 0) exit BLOCK
if (os_data%event_analysis_pdf) then
  call os_system_call (os_data%ps2pdf // " " // &
    filename_vis // ".ps", status)
  if (status /= 0) exit BLOCK
end if
exit BLOCK
end do BLOCK
if (status /= 0) then
  call msg_error ("Unable to compile analysis output file")
end if
end if
end if
call msg_message ("... done.")
call cascade_set_final (cascade_set)
rewind (unit)
call phs_forest_read (process%forest, unit, &
  process%id, n_in, n_out, process%model, phs_ok)
rewind (unit)

```

```

        process%md5sum_phs = md5sum (unit)
        close (unit)
        wrote_file = present (filename_out)
        if (.not. phs_ok) then
            call msg_bug ("Generated phase space file: " &
                // "No valid phase space for process '" &
                // char (process%id) // "'")
        end if
    end if
    call phs_forest_set_flavors (process%forest, flv(:,1))
    call phs_forest_set_parameters &
        (process%forest, mapping_defaults, variable_limits)
    call phs_forest_setup_prt_combinations (process%forest)
    call phs_forest_set_equivalences (process%forest)
    if (process%use_beams) then
        n_par_strfun = strfun_chain_get_n_parameters_tot (process%sfchain)
        allocate (strfun_rigid (n_par_strfun))
        strfun_rigid = strfun_chain_dimension_is_rigid (process%sfchain)
    else
        n_par_strfun = 0
        allocate (strfun_rigid (0))
    end if
    call phs_forest_setup_vamp_equivalences (process%forest, &
        n_par_strfun, strfun_rigid, &
        process%azimuthal_dependence, &
        process%vamp_eq)
    process%n_channels = phs_forest_get_n_channels (process%forest)
    process%n_par_hi = phs_forest_get_n_parameters (process%forest)
    process%n_par = process%n_par_strfun + process%n_par_hi
    allocate (process%x_hi (process%n_par_hi))
    process%x_hi = 0
    allocate (process%x (process%n_par, process%n_channels))
    process%x = 0
    allocate (process%phs_factor (process%n_channels))
    process%phs_factor = 0
    allocate (process%active_channel (process%n_channels))
    process%active_channel = .true.
    if (mapping_defaults%enable_s_mapping) then
        call phs_forest_set_s_mappings (process%forest)
    end if
    write (msg_buffer, "(A,IO,A,IO,A)") "... found ", process%n_channels, &
        " phase space channels, collected in ", &
        phs_forest_get_n_groves (process%forest), &
        " groves."
    call msg_message ()
    write (msg_buffer, "(A,IO,A)") "Phase space: found ", &
        phs_forest_get_n_equivalences (process%forest), &
        " equivalences between channels."
    call msg_message ()
    if (wrote_file) &
        call msg_message ("Wrote phase-space configuration file '" &
            // char (filename_out) // "'.")
    if (present (ok)) ok = .true.
end subroutine process_setup_phase_space

```

13.3.15 Process preparation: cuts, weight and scale

Create a `subevt` which holds the relevant event data which are accessible to cuts, weight and scale. We store beams, incoming partons, and outgoing partons. Beam remnants and any further virtual particles are not used, neither are decay products or hadrons (which do not exist at the integration level). There is flavor information (as far as possible in the presence of flavor sums), but no helicity information.

Allocation has been done in `process_init`. Here, we determine the relevant particle indices in the process (trace) evaluator and fill the particles initially with zero momenta, but flavors taken from the beam and hard-interaction definition. If there are flavor sums, we choose the first flavor in the list.

The assignment of indices relies on the assumptions that (1) the beams come first, (2) the incoming partons are located immediately after all structure-function virtual particles, (3) the outgoing partons are the children of the first incoming parton.

```

(Processes: public)+≡
    public :: process_setup_subevt

(Processes: procedures)+≡
    subroutine process_setup_subevt (process)
        type(process_t), intent(inout), target :: process
        type(interaction_t), pointer :: int
        integer :: n_beam, n_in, n_out
        integer :: i
        if (process%use_beams) then
            int => evaluator_get_int_ptr (process%eval_trace)
        else
            int => hard_interaction_get_int_ptr (process%hi)
        end if
        n_beam = size (process%j_beam)
        n_in = size (process%j_in)
        n_out = size (process%j_out)
        process%j_beam = (/ (i, i = 1, n_beam) /)
        process%j_in = (/ (i + strfun_chain_get_n_vir (process%sfchain), &
                           i = 1, n_in) /)
        process%j_out = interaction_get_children (int, process%j_in(1))
        call interaction_to_subevt (int, &
                                   process%j_beam, process%j_in, process%j_out, process%subevt)
        call subevt_set_pdg_beam (process%subevt, &
                                   flavor_get_pdg (beam_data_get_flavor (process%beam_data)))
        call subevt_set_pdg_incoming (process%subevt, &
                                       flavor_get_pdg (process%flv_in))
        call subevt_set_pdg_outgoing (process%subevt, &
                                       flavor_get_pdg (process%flv_out))
    end subroutine process_setup_subevt

```

Compile the cut expression and store it as an evaluation tree inside the process object. Also store the parse node. In subsequent calls, the setup may be called

without providing the parse node, but simply looking it up.

```

<Processes: public>+≡
    public :: process_setup_cuts

<Processes: procedures>+≡
    subroutine process_setup_cuts (process, parse_node, md5sum)
        type(process_t), intent(inout), target :: process
        type(parse_node_t), intent(in), optional, target :: parse_node
        character(32), intent(out), optional :: md5sum
        if (present (parse_node)) then
            process%cut_pn => parse_node
            call eval_tree_init_lexpr &
                (process%cut_expr, parse_node, process%var_list, process%subevt)
        else if (associated (process%cut_pn)) then
            call eval_tree_init_lexpr &
                (process%cut_expr, process%cut_pn, process%var_list, process%subevt)
        end if
        if (present (md5sum)) &
            md5sum = eval_tree_get_md5sum (process%cut_expr)
    end subroutine process_setup_cuts

```

Compile the weight expression and store it as an evaluation tree inside the process object.

```

<Processes: public>+≡
    public :: process_setup_weight

<Processes: procedures>+≡
    subroutine process_setup_weight (process, parse_node, md5sum)
        type(process_t), intent(inout), target :: process
        type(parse_node_t), intent(in), optional, target :: parse_node
        character(32), intent(out), optional :: md5sum
        if (present (parse_node)) then
            process%weight_pn => parse_node
            call eval_tree_init_expr &
                (process%reweighting_expr, parse_node, process%var_list, &
                 process%subevt)
        else if (associated (process%weight_pn)) then
            call eval_tree_init_expr &
                (process%reweighting_expr, process%weight_pn, process%var_list, &
                 process%subevt)
        end if
        if (present (md5sum)) &
            md5sum = eval_tree_get_md5sum (process%reweighting_expr)
    end subroutine process_setup_weight

```

Compile the scale expression and store it as an evaluation tree inside the process object.

```

<Processes: public>+≡
    public :: process_setup_scale

<Processes: procedures>+≡
    subroutine process_setup_scale (process, parse_node, md5sum)
        type(process_t), intent(inout), target :: process
        type(parse_node_t), intent(in), optional, target :: parse_node

```

```

character(32), intent(out), optional :: md5sum
if (present (parse_node)) then
  process%scale_pn => parse_node
  call eval_tree_init_expr &
    (process%scale_expr, parse_node, process%var_list, process%subevt)
else if (associated (process%scale_pn)) then
  call eval_tree_init_expr &
    (process%scale_expr, process%scale_pn, process%var_list, &
    process%subevt)
end if
if (present (md5sum)) &
  md5sum = eval_tree_get_md5sum (process%scale_expr)
end subroutine process_setup_scale

```

<Processes: public>+≡

```
public :: process_setup_fac_scale
```

<Processes: procedures>+≡

```

subroutine process_setup_fac_scale (process, parse_node, md5sum)
  type(process_t), intent(inout), target :: process
  type(parse_node_t), intent(in), optional, target :: parse_node
  character(32), intent(out), optional :: md5sum
  if (present (parse_node)) then
    process%fac_scale_pn => parse_node
    call eval_tree_init_expr &
      (process%fac_scale_expr, parse_node, process%var_list, &
      process%subevt)
  else if (associated (process%fac_scale_pn)) then
    call eval_tree_init_expr &
      (process%fac_scale_expr, process%fac_scale_pn, process%var_list, &
      process%subevt)
  end if
  if (present (md5sum)) &
    md5sum = eval_tree_get_md5sum (process%fac_scale_expr)
end subroutine process_setup_fac_scale

```

<Processes: public>+≡

```
public :: process_setup_ren_scale
```

<Processes: procedures>+≡

```

subroutine process_setup_ren_scale (process, parse_node, md5sum)
  type(process_t), intent(inout), target :: process
  type(parse_node_t), intent(in), optional, target :: parse_node
  character(32), intent(out), optional :: md5sum
  if (present (parse_node)) then
    process%ren_scale_pn => parse_node
    call eval_tree_init_expr &
      (process%ren_scale_expr, parse_node, process%var_list, &
      process%subevt)
  else if (associated (process%ren_scale_pn)) then
    call eval_tree_init_expr &
      (process%ren_scale_expr, process%ren_scale_pn, process%var_list, &
      process%subevt)
  end if

```



```

        if (present (md5sum)) &
            md5sum = eval_tree_get_md5sum (process%ren_scale_expr)
    end subroutine process_setup_ren_scale

```

13.3.16 Process preparation: VAMP grids

Initialize the grids with uniform channel weight.

```

<Processes: public>+≡
    public :: process_setup_grids

<Processes: procedures>+≡
    subroutine process_setup_grids (process, grid_parameters, calls)
        type(process_t), intent(inout), target :: process
        type(grid_parameters_t), intent(in) :: grid_parameters
        integer, intent(in) :: calls
        integer, dimension(:), allocatable :: num_div
        real(default), dimension(:), allocatable :: weights
        real(default), dimension(:,:), allocatable :: region
        integer :: min_calls
        allocate (num_div (process%n_par))
        min_calls = grid_parameters%min_calls_per_bin * process%n_channels
        if (min_calls /= 0) then
            process%n_bins = max (grid_parameters%min_bins, &
                min (calls / min_calls, grid_parameters%max_bins))
        else
            process%n_bins = grid_parameters%max_bins
        end if
        allocate (region (2, process%n_par))
        region(1,:) = 0
        region(2,:) = 1
        allocate (weights (process%n_channels))
        weights = 1
        num_div = process%n_bins
        call msg_message ("Creating VAMP integration grids:")
        if (grid_parameters%use_vamp_equivalences) &
            call msg_message ("Using phase-space channel equivalences.")
        call vamp_create_grids (process%grids, region, calls, weights, &
            num_div=num_div, stratified=grid_parameters%stratified)
        process%vamp_grids_defined = .true.
    end subroutine process_setup_grids

```

13.3.17 Process preparation: Helicity selection counters

The helicity selection counters can be activated and reset at startup, removing unnecessary helicities after `cutoff` tries.

```

<Processes: public>+≡
    public :: process_reset_helicity_selection

<Processes: procedures>+≡
    subroutine process_reset_helicity_selection (process, threshold, cutoff)
        type(process_t), intent(inout) :: process

```

```

real(default), intent(in) :: threshold
integer, intent(in) :: cutoff
call hard_interaction_reset_helicity_selection &
    (process%hi, threshold, cutoff)
end subroutine process_reset_helicity_selection

```

13.3.18 Matrix element evaluation

Kinematics. This evaluates structure functions as far as momenta are concerned. The evaluator links automatically transfer the incoming momenta to the hard interaction. All phase space factors are evaluated, and the resulting momenta are stored back in the hard interaction, from there transferred to the appropriate evaluators.

Once the particle momenta are known, they are transferred to the `subevt` that is used for cut/weight/scale evaluation. The energy scale is computed right here.

If `ok` is false, there is no valid momentum assignement for the given x parameters, and the event must be dropped.

(Processes: procedures)+≡

```

subroutine process_set_kinematics (process, x_in, channel, ok)
    type(process_t), intent(inout), target :: process
    real(default), dimension(:), intent(in) :: x_in
    integer, intent(in) :: channel
    logical, intent(out) :: ok
    type(interaction_t), pointer :: int
    type(evaluator_t), pointer :: eval
    integer :: i, n1, n2
    real(default) :: lda
    process%x_hi = x_in(:process%n_par_hi)
    process%x_strfun = x_in(process%n_par_hi+1:)
    process%x(:process%n_par_hi,channel) = process%x_hi
    process%channel = channel
    int => hard_interaction_get_int_ptr (process%hi)
    eval => hard_interaction_get_eval_trace_ptr (process%hi)
    if (process%use_beams) then
        n1 = process%n_par_hi
        n2 = process%n_par_hi + process%n_par_strfun
        if (strfun_chain_multichannel_enabled (process%sfchain)) then
            process%x(n1+1:n2, channel) = process%x_strfun
            call strfun_chain_set_kinematics (process%sfchain, process%x_strfun, &
                channel, n1, process%x, process%sf_factor, &
                ok=ok)
        else
            forall (i = 1:size(process%x,2)) &
                process%x(n1+1:n2,i) = process%x_strfun
            call strfun_chain_set_kinematics (process%sfchain, process%x_strfun, &
                ok=ok)
        end if
    if (.not. ok) return
    call interaction_receive_momenta (int)
    process%beams_are_set = .true.

```

```

        process%sqrts_hat = sqrt (max (interaction_get_s (int), 0._default))
    else if (.not. process%beams_are_set) then
        if (process%n_par_strfun /= 0) call msg_bug &
            ("Mismatch in structure function setup: n_parameters /= 0")
        select case (process%type)
        case (PRC_DECAY)
            call interaction_set_momenta (int, &
                (/ vector4_at_rest (process%mass_in(1)) /), &
                outgoing=.false.)
        case (PRC_SCATTERING)
            call interaction_set_momenta (int, &
                colliding_momenta (process%sqrts, process%mass_in), &
                outgoing=.false.)
        end select
        process%sqrts_hat = process%sqrts
    else
        if (process%n_par_strfun /= 0) call msg_bug &
            ("Mismatch in beams/structure function setup: n_parameters /= 0")
    end if
    call process_status_passed_strfun_chain (process%status)
    select case (process%type)
    case (PRC_DECAY)
        process%flux_factor = &
            twopi4 / (2 * process%mass_in(1))
    case (PRC_SCATTERING)
        lda = lambda (process%sqrts_hat ** 2, &
            process%mass_in(1) ** 2, &
            process%mass_in(2) ** 2)

        if (lda <= 0) then
            ok = .false.; return
        end if
        process%flux_factor = &
            conv * twopi4 / (2 * sqrt (lda))
    end select
    call process_status_passed_mass_threshold (process%status)
    process%sqrts_hat_known = .true.
    if (.not. process%lab_is_cm_frame) then
        process%lt_cm_to_lab = interaction_get_cm_transformation (int)
        call phs_forest_set_prt_in (process%forest, int, process%lt_cm_to_lab)
    else
        call phs_forest_set_prt_in (process%forest, int)
    end if
    if (process%old_phs_version) then
        call phs_forest_evaluate_phase_space (process%forest, &
            channel, process%active_channel, process%sqrts_hat, &
            process%x, process%phs_factor, process%phs_volume, ok)
    else
        call phs_forest_evaluate_momenta (process%forest, &
            channel, process%active_channel, process%sqrts_hat, &
            process%x, process%phs_factor, process%phs_volume, ok)
    end if
    if (.not. ok) return
    if (process%lab_is_cm_frame) then
        call phs_forest_get_prt_out (process%forest, int)
    end if
end if

```

```

else
  call phs_forest_get_prt_out &
    (process%forest, int, process%lt_cm_to_lab)
end if
call evaluator_receive_momenta (eval)
if (process%use_beams) &
  call evaluator_receive_momenta (process%eval_trace)
call process_status_passed_kinematics (process%status)
end subroutine process_set_kinematics

```

Complete phase space evaluation

```

<Processes: public>+≡
  public :: process_complete_kinematics

<Processes: procedures>+≡
  subroutine process_complete_kinematics (process, channel)
    type(process_t), intent(inout), target :: process
    integer, intent(in) :: channel
    if (.not. process%old_phs_version) then
      call phs_forest_evaluate_other_channels (process%forest, &
        channel, process%active_channel, process%sqrts_hat, &
        process%x, process%phs_factor)
    end if
  end subroutine process_complete_kinematics

```

Recover momenta from a given particle set.

```

<Processes: public>+≡
  public :: process_recover_kinematics

<Processes: procedures>+≡
  subroutine process_recover_kinematics (process, particle_set)
    type(process_t), intent(inout), target :: process
    type(particle_set_t), intent(in) :: particle_set
    integer :: n_in, n_out
    real(default) :: lda
    type(evaluator_t), pointer :: eval
    type(interaction_t), pointer :: int
    ! To be implemented later
    if (process%use_beams) &
      call msg_bug ("Recovering process with beams not implemented yet")

    call hard_interaction_recover_kinematics (process%hi, particle_set)
    int => hard_interaction_get_int_ptr (process%hi)

    process%sqrts_hat = process%sqrts
    select case (process%type)
    case (PRC_DECAY)
      process%flux_factor = &
        twopi4 / (2 * process%mass_in(1))
    case (PRC_SCATTERING)
      lda = lambda (process%sqrts_hat ** 2, &
        process%mass_in(1) ** 2, &
        process%mass_in(2) ** 2)

      if (lda <= 0) then

```

```

        process%flux_factor = 0
    else
        process%flux_factor = &
            conv * twopi4 / (2 * sqrt (lda))
    end if
end select
process%sqrts_hat_known = .true.
if (.not. process%lab_is_cm_frame) then
    process%lt_cm_to_lab = interaction_get_cm_transformation (int)
    call phs_forest_set_prt_in (process%forest, int, process%lt_cm_to_lab)
else
    call phs_forest_set_prt_in (process%forest, int)
end if

eval => hard_interaction_get_eval_trace_ptr (process%hi)
call evaluator_receive_momenta (eval)

end subroutine process_recover_kinematics

```

Fill the `subevt` which is used by cuts, weight, scale with momenta from the `eval_trace` interaction. This can be done once kinematics has been set up or recovered.

If the optional `transform` flag is set, boost the momenta from the lab to the c.m. frame.

```

<Processes: public>+≡
    public :: process_fill_subevt

<Processes: procedures>+≡
    subroutine process_fill_subevt (process, transform)
        type(process_t), intent(inout), target :: process
        logical, intent(in), optional :: transform
        type(interaction_t), pointer :: int
        logical :: tr
        tr = .false.; if (present (transform)) tr = transform
        if (process%use_beams) then
            int => evaluator_get_int_ptr (process%eval_trace)
        else
            int => hard_interaction_get_int_ptr (process%hi)
        end if
        if (tr) then
            call interaction_momenta_to_subevt &
                (int, process%j_beam, process%j_in, process%j_out, &
                 inverse (process%lt_cm_to_lab), process%subevt)
        else
            call interaction_momenta_to_subevt &
                (int, process%j_beam, process%j_in, process%j_out, process%subevt)
        end if
    end subroutine process_fill_subevt

```

Evaluate the cut expression and return a boolean flag (true means to continue evaluation, false to drop the event).

```

<Processes: procedures>+≡
    function process_passes_cuts (process) result (flag)

```

```

logical :: flag
type(process_t), intent(inout), target :: process
if (eval_tree_is_defined (process%cut_expr)) then
  call eval_tree_evaluate (process%cut_expr)
  if (eval_tree_result_is_known (process%cut_expr)) then
    flag = eval_tree_get_log (process%cut_expr)
  else
    flag = .true.
  end if
else
  flag = .true.
end if
end function process_passes_cuts

```

Evaluate the weight expression and set the value.

```

<Processes: public>+≡
  public :: process_compute_reweighting_factor

<Processes: procedures>+≡
  subroutine process_compute_reweighting_factor (process)
    type(process_t), intent(inout), target :: process
    if (eval_tree_is_defined (process%reweighting_expr)) then
      call eval_tree_evaluate (process%reweighting_expr)
      if (eval_tree_result_is_known (process%reweighting_expr)) then
        process%reweighting_factor = &
          eval_tree_get_real (process%reweighting_expr)
      else
        process%reweighting_factor = 1
      end if
    else
      process%reweighting_factor = 1
    end if
  end subroutine process_compute_reweighting_factor

```

Evaluate the scale expression(s) and return a real value. If the scale expression is essentially undefined, return the c.m. energy of the hard interaction. The factorization scale and renormalization scale always supersede the general expression.

```

<Processes: public>+≡
  public :: process_compute_scale

<Processes: procedures>+≡
  subroutine process_compute_scale (process)
    type(process_t), intent(inout), target :: process
    if (eval_tree_is_defined (process%scale_expr)) then
      call eval_tree_evaluate (process%scale_expr)
      if (eval_tree_result_is_known (process%scale_expr)) then
        process%scale = eval_tree_get_real (process%scale_expr)
      else
        process%scale = process%sqrts_hat
      end if
    else
      process%scale = process%sqrts_hat
    end if
  end subroutine process_compute_scale

```

```

if (eval_tree_is_defined (process%fac_scale_expr)) then
  call eval_tree_evaluate (process%fac_scale_expr)
  if (eval_tree_result_is_known (process%fac_scale_expr)) then
    process%fac_scale = eval_tree_get_real (process%fac_scale_expr)
  else
    process%fac_scale = process%scale
  end if
else
  process%fac_scale = process%scale
end if
if (eval_tree_is_defined (process%ren_scale_expr)) then
  call eval_tree_evaluate (process%ren_scale_expr)
  if (eval_tree_result_is_known (process%ren_scale_expr)) then
    process%ren_scale = eval_tree_get_real (process%ren_scale_expr)
  else
    process%ren_scale = process%scale
  end if
else
  process%ren_scale = process%scale
end if
end subroutine process_compute_scale

```

Evaluate the (jacobian) factor associated to the VAMP grids and the phase-space factor array for the given integration channel.

(Processes: procedures)+≡

```

subroutine process_compute_vamp_phs_factor (process, weights)
  type(process_t), intent(inout), target :: process
  real(default), dimension(:), intent(in) :: weights
  real(default), dimension(process%n_channels) :: vamp_prob
  real(default) :: dp
  integer :: i
  !$OMP PARALLEL PRIVATE(i) SHARED(process,vamp_prob)
  !$OMP DO
  do i = 1, process%n_channels
    if (process%active_channel(i)) then
      vamp_prob(i) = &
        vamp_probability (process%grids%grids(i), process%x(:,i))
    else
      vamp_prob(i) = 0
    end if
  end do
  !$OMP END DO
  !$OMP END PARALLEL
  if (allocated (process%sf_factor)) then
    dp = dot_product (weights, &
      vamp_prob / (process%phs_factor * process%sf_factor))
  else
    dp = dot_product (weights, vamp_prob / process%phs_factor)
  end if
  if (dp /= 0) then
    process%vamp_phs_factor = vamp_prob(process%channel) / dp
  else
    process%vamp_phs_factor = 0
  end if
end subroutine process_compute_vamp_phs_factor

```

```

end if
end subroutine process_compute_vamp_phs_factor

```

Update the model parameters used by the matrix element code.

```

<Processes: public>+≡
public :: process_update_parameters

<Processes: procedures>+≡
subroutine process_update_parameters (process)
  type(process_t), intent(inout) :: process
  call hard_interaction_update_parameters (process%hi)
end subroutine process_update_parameters

```

Update the α_s value used by the matrix element code, depending on the computed renormalization scale.

```

<Processes: interfaces>+≡
interface
  double precision function alphasPDF (Q)
    double precision, intent(in) :: Q
  end function alphasPDF
end interface

<Processes: public>+≡
public :: process_update_alpha_s

<Processes: procedures>+≡
subroutine process_update_alpha_s (process)
  type(process_t), intent(inout) :: process
  if (.not. process%qcd%alpha_s_is_fixed) then
    call qcd_parameters_update_alpha_s (process%qcd, process%ren_scale)
    call hard_interaction_update_alpha_s &
      (process%hi, process%qcd%alpha_s_at_scale)
  end if
end subroutine process_update_alpha_s

```

Evaluate the structure function values, the hard matrix element, and the follow-up evaluators. We obtain the squared matrix element value for the current event.

```

<Processes: public>+≡
public :: process_evaluate

<Processes: procedures>+≡
subroutine process_evaluate (process)
  type(process_t), intent(inout), target :: process
  if (process%use_beams) then
    call strfun_chain_evaluate (process%sfchain, process%fac_scale)
    process%sf_mapping_factor = &
      strfun_chain_get_mapping_factor (process%sfchain)
  else
    process%sf_mapping_factor = 1
  end if
  call hard_interaction_evaluate (process%hi)
  if (process%has_extra_evaluators) then
    call evaluator_evaluate (process%eval_trace)
  end if
end subroutine process_evaluate

```



```

        process%sqme = evaluator_sum (process%eval_trace)
    else
        process%sqme = evaluator_sum &
            (hard_interaction_get_eval_trace_ptr (process%hi)) &
            * process%averaging_factor
    end if
!    call process_write (process, 66); stop
end subroutine process_evaluate

```

Return the squared matrix element of the hard interaction for the given momenta, traced over all quantum numbers. This is independent of beam setup, structure functions, phase space etc.

(Processes: procedures)+≡

```

function process_compute_sqme_sum (process, p) result (sqme)
    real(default) :: sqme
    type(process_t), intent(inout), target :: process
    type(vector4_t), dimension(:), intent(in) :: p
    sqme = hard_interaction_compute_sqme_sum (process%hi, p)
end function process_compute_sqme_sum

```

13.3.19 Access VAMP data

Compute the reweighting efficiency for the current grids, suitable averaged over all active channels.

(Processes: procedures)+≡

```

function process_get_vamp_efficiency_array (process) result (efficiency)
    real(default), dimension(:), allocatable :: efficiency
    type(process_t), intent(in) :: process
    allocate (efficiency (process%n_channels))
    where (process%grids%grids%f_max /= 0)
        efficiency = process%grids%grids%mu(1) / abs (process%grids%grids%f_max)
    elsewhere
        efficiency = 0
    end where
end function process_get_vamp_efficiency_array

```

```

function process_get_vamp_efficiency (process) result (efficiency)
    real(default) :: efficiency
    type(process_t), intent(in) :: process
    real(default), dimension(:), allocatable :: weight
    real(default) :: norm
    allocate (weight (process%n_channels))
    weight = process%grids%weights * abs (process%grids%grids%f_max)
    norm = sum (weight)
    if (norm /= 0) then
        efficiency = &
            dot_product (process_get_vamp_efficiency_array (process), weight) &
            / norm
    else
        efficiency = 1
    end if
end function

```

```
end function process_get_vamp_efficiency
```

13.3.20 Integration

This executes one or more iterations of the VAMP integration routine. The flags determine whether to discard previous results, to adapt grids before integration, and to adapt the relative channel weights. The final result is entered into the results record.

If there is a grid filename provided, we write the current grid to file, once after each iteration. If the flag `write_best_grid` is also set, we write the grid with the lowest (i.e., best) accuracy to file. This may be the current grid, or it may be a previous 'best' grid.

```
(Processes: public)+≡
    public :: process_integrate

(Processes: procedures)+≡
    subroutine process_integrate (process, rng, &
        grid_parameters, pass, it1, it2, calls, &
        discard_integrals, adapt_grids, adapt_weights, print_current, &
        time_estimate, &
        grids_filename, write_best_grid, md5sum, history_filename, log_filename)
        type(process_t), intent(inout), target :: process
        type(tao_random_state), intent(inout) :: rng
        type(grid_parameters_t), intent(in) :: grid_parameters
        integer, intent(in) :: pass, it1, it2, calls
        logical, intent(in) :: discard_integrals
        logical, intent(in) :: adapt_grids
        logical, intent(in) :: adapt_weights
        logical, intent(in) :: print_current
        logical, intent(in) :: time_estimate
        type(string_t), intent(in), optional :: grids_filename
        logical, intent(in), optional :: write_best_grid
        type(md5sum_grids_t), intent(in), optional :: md5sum
        type(string_t), intent(in), optional :: history_filename, log_filename
        integer :: it
        real(default) :: integral, error, efficiency
        type(time_t) :: time_start, time_end
        type(md5sum_grids_t) :: md5sum_local
        real(default) :: sqrts
        real(default), dimension(:), allocatable :: grove_weight
        integer :: u
        if (it1 > it2) return
        u = logfile_unit ()
        if (present (md5sum)) then
            process%md5sum_grids = process_collect_md5sum (process, md5sum)
        end if
        process%grid_parameters = grid_parameters
        sqrts = process%sqrts
        if (discard_integrals .and. it1==1) then
            if (grid_parameters%use_vamp_equivalences) then
                call vamp_discard_integrals (process%grids, &
                    calls, stratified=grid_parameters%stratified, eq=process%vamp_eq)
```

```

else
    call vamp_discard_integrals (process%grids, &
        calls, stratified=grid_parameters%stratified)
end if
end if
process%beams_are_set = .false.
do it = it1, it2
    if (adapt_grids) then
        call process_adapt_grids (process)
    end if
    if (adapt_weights) then
        call process_adapt_channel_weights (process, grid_parameters, calls)
    end if
    call process_status_reset_counters (process%status)
    if (time_estimate) time_start = time_current ()
    if (grid_parameters%use_vamp_equivalences) then
        call vamp_sample_grids &
            (rng, process%grids, sample_function, process%store_index, 1, &
            eq=process%vamp_eq, &
            history=process%v_history(it:), &
            histories=process%v_histories(it,:), &
            integral=integral, std_dev=error, negative_weights=&
            process%negative_weights)
    else
        call vamp_sample_grids &
            (rng, process%grids, sample_function, process%store_index, 1, &
            history=process%v_history(it:), &
            histories=process%v_histories(it,:), &
            integral=integral, std_dev=error, negative_weights=&
            process%negative_weights)
    end if
    if (time_estimate) time_end = time_current ()
    efficiency = process_get_vamp_efficiency (process)
    call process_get_grove_weights (process, grove_weight)
    if (time_estimate) then
        call integration_results_append (process%results, &
            process%type, pass, 1, calls, &
            integral, error, efficiency, grove_weight, time_start, time_end)
    else
        call integration_results_append (process%results, &
            process%type, pass, 1, calls, &
            integral, error, efficiency, grove_weight)
    end if
    process%filename_current_grid = ""
    process%filename_best_grid = ""
    if (present (grids_filename)) then
        process%filename_current_grid = grids_filename
        call write_grid_file (grids_filename, process%id, &
            process%md5sum_grids, grid_parameters, &
            process%results, process%grids)
        if (present (write_best_grid)) then
            if (write_best_grid) then
                process%filename_best_grid = grids_filename // ".b"
                call write_best_grid_file (process%filename_best_grid, &

```

```

        process%id, &
        process%md5sum_grids, grid_parameters, &
        process%results, process%grids)
    end if
end if
end if
if (print_current) then
    call integration_results_write_current (process%results)
    call integration_results_write_current (process%results, unit=u)
    if (u >= 0) flush (u)
end if
if (present (history_filename)) then
    call integration_results_write_driver &
        (process%results, history_filename)
end if
if (present (log_filename)) then
    call process_write_logfile (process, log_filename)
end if
end do
end subroutine process_integrate

```

Collect the MD5 sums that are relevant for reading/writing grid files.

(Processes: procedures)+≡

```

function process_collect_md5sum (process, md5sum_global) &
    result (md5sum_local)
    type(md5sum_grids_t) :: md5sum_local
    type(process_t), intent(in) :: process
    type(md5sum_grids_t), intent(in) :: md5sum_global
    md5sum_local = md5sum_global
    md5sum_local%process = process%md5sum
    md5sum_local%model = model_get_md5sum (process%model)
    md5sum_local%parameters = model_get_parameters_md5sum (process%model)
    md5sum_local%phs = process%md5sum_phs
    md5sum_local%alpha_s = process%md5sum_alpha_s
end function process_collect_md5sum

```

This should be executed instead if the process has no matrix element.

(Processes: public)+≡

```

public :: process_do_dummy_integration

```

(Processes: procedures)+≡

```

subroutine process_do_dummy_integration (process)
    type(process_t), intent(inout) :: process
    call integration_results_append (process%results, &
        process%type, 1, 1, 0, &
        0._default, 0._default, 0._default)
end subroutine process_do_dummy_integration

```

Similarly, write a number of dummy entries to the results record which indicate skipped iterations.

(Processes: public)+≡

```

public :: process_skip_iterations

```

```

<Processes: procedures>+≡
  subroutine process_skip_iterations (process, pass, it, n_skip)
    type(process_t), intent(inout) :: process
    integer, intent(in) :: pass, it, n_skip
    integer :: i
    do i = 1, n_skip
      call integration_results_append_null (process%results, &
        pass, it + i)
    end do
  end subroutine process_skip_iterations

```

In preparation for a new pass or for event generation, load a previously stored best grid if it does not coincide with the current one.

```

<Processes: public>+≡
  public :: process_choose_best_grid

<Processes: procedures>+≡
  subroutine process_choose_best_grid (process, check_grid_file)
    type(process_t), intent(inout) :: process
    logical, intent(in) :: check_grid_file
    integer :: it_last, it_best
    type(md5sum_grids_t) :: md5sum_local
    type(integration_results_t) :: results_on_file
    logical :: ok
    it_last = integration_results_get_last_it (process%results)
    it_best = integration_results_get_best_it (process%results)
    if (it_best /= 0 .and. it_best /= it_last &
      .and. process%filename_best_grid /= "") then
      write (msg_buffer, "(A,A,A,I0)") &
        "Process ", char (process%id), &
        ": Using integration grids from iteration #", &
        it_best
      call msg_message
      call read_grid_file (process%filename_best_grid, process%id, &
        check_grid_file, process%md5sum_grids, process%grid_parameters, &
        results_on_file, process%grids, &
        process%pass_array, process%n_calls_array, ok)
    end if
  end subroutine process_choose_best_grid

```

This just calls the sampling function a given number of times, discarding the results. VAMP is bypassed.

Constructs like this are candidates for elimination by the optimizer – as long as the sampling function is impure, this should not happen, however.

```

<Processes: public>+≡
  public :: process_me_test

<Processes: procedures>+≡
  subroutine process_me_test &
    (process, rng, n_calls, time_in_seconds, sample_function_sum)
    type(process_t), intent(inout), target :: process
    type(tao_random_state), intent(inout) :: rng
    integer, intent(in) :: n_calls

```

```

real(default), intent(out), optional :: time_in_seconds, sample_function_sum
integer :: prc_index, i
type(time_t) :: time_start, time_end
real(default), dimension(:), allocatable :: weights
real(default) :: s
process%beams_are_set = .false.
s = 0
allocate (weights (process%n_channels))
weights = 1._default / size (weights)
call process_status_reset_counters (process%status)
if (present (time_in_seconds)) time_start = time_current ()
do i = 1, n_calls
    s = s + sample_function &
        (random_xi (), process%store_index, &
        weights=weights, &
        channel=random_channel ())
end do
if (present (time_in_seconds)) then
    time_end = time_current ()
    time_in_seconds = time_end - time_start
end if
if (present (sample_function_sum)) then
    sample_function_sum = s
end if
contains
function random_channel () result (channel)
    integer :: channel
    real(default) :: x
    call tao_random_number (rng, x)
    channel = ceiling (x * process%n_channels)
end function random_channel
function random_xi () result (xi)
    real(default), dimension (process%n_par) :: xi
    integer :: i
    do i = 1, size (xi)
        call tao_random_number (rng, xi(i))
    end do
end function random_xi
end subroutine process_me_test

```

Create the VAMP history information:

```

<Processes: public>+≡
    public :: process_init_vamp_history
    public :: process_final_vamp_history

<Processes: procedures>+≡
    subroutine process_init_vamp_history (process, n_iterations)
        type(process_t), intent(inout) :: process
        integer, intent(in) :: n_iterations
        call process_final_vamp_history (process)
        allocate (process%v_history (n_iterations))
        allocate (process%v_histories &
            (n_iterations, process_get_n_channels (process)))
        call vamp_create_history (process%v_history, verbose=.false.)
    end subroutine process_init_vamp_history

```

```

        call vamp_create_history (process%v_histories, verbose=.false.)
    end subroutine process_init_vamp_history

subroutine process_final_vamp_history (process)
    type(process_t), intent(inout) :: process
    if (allocated (process%v_history)) then
        call vamp_delete_history (process%v_history)
        deallocate (process%v_history)
    end if
    if (allocated (process%v_histories)) then
        call vamp_delete_history (process%v_histories)
        deallocate (process%v_histories)
    end if
end subroutine process_final_vamp_history

```

Display the time estimate on screen

```

<Processes: public>+≡
    public :: process_write_time_estimate

<Processes: procedures>+≡
subroutine process_write_time_estimate (process, unit)
    type(process_t), intent(in) :: process
    integer, intent(in), optional :: unit
    real(default) :: time_per_event, time_per_10k
    time_per_event = integration_results_get_time_per_event (process%results)
    time_per_10k = 10000 * time_per_event
    write (msg_buffer, "(A)") "Process " // char (process%id) // ": "
    call msg_message ()
    write (msg_buffer, "(A)") "    time estimate for generating " &
        // "10000 unweighted events: " &
        // char (time2string (int (time_per_10k)))
    call msg_message (unit=unit)
    call write_hline (unit)
end subroutine process_write_time_estimate

```

Write the VAMP grid file including a header containing metadata.

```

<Processes: procedures>+≡
subroutine write_grid_file (filename, process_id, md5sum, &
    grid_parameters, results, grids)
    type(string_t), intent(in) :: filename, process_id
    type(md5sum_grids_t), intent(in) :: md5sum
    type(grid_parameters_t), intent(in) :: grid_parameters
    type(integration_results_t), intent(in) :: results
    type(vamp_grids), intent(in) :: grids
    integer :: u
    u = free_unit ()
    open (file = char (filename), unit = u, &
        action = "write", status = "replace")
    write (u, *) "process ", char (process_id)
    call md5sum_grids_write (md5sum, u)
    write (u, *)
    call grid_parameters_write (grid_parameters, u)
    write (u, *)

```

```

    call integration_results_write &
        (results, u, verbose = .true.)
    write (u, *)
    call vamp_write_grids (grids, u, write_integrals = .true.)
    close (u)
end subroutine write_grid_file

```

Attempt to read the VAMP grid file, checking metadata for consistency. Also read the integration results as far as they are known.

(Processes: procedures)+≡

```

subroutine read_grid_file (filename, process_id, &
    check, md5sum, grid_parameters, results, grids, &
    pass, n_calls, ok)
    type(string_t), intent(in) :: filename, process_id
    logical, intent(in) :: check
    type(md5sum_grids_t), intent(in) :: md5sum
    type(grid_parameters_t), intent(in) :: grid_parameters
    type(integration_results_t), intent(out) :: results
    type(vamp_grids), intent(inout) :: grids
    integer, dimension(:), intent(in) :: pass, n_calls
    logical, intent(out) :: ok
    integer :: u
    logical :: exist
    character(80) :: buffer
    character :: equals
    character(32) :: md5sum_file
    type(grid_parameters_t) :: grid_parameters_file
    type(integration_results_t) :: results_file
    ok = .false.
    if (.not. check) call msg_warning &
        ("Validity checks turned off for grid file '" &
        // char (filename) // "'")
    inquire (file = char (filename), exist = exist)
    if (.not. exist) return
    call msg_message ("Reading integration grids and results from file '" &
        // char (filename) // "':")
    u = free_unit ()
    open (file = char (filename), unit = u, action = "read", status = "old")
    read (u, *) buffer
    if (check .and. trim (adjustl (buffer)) /= "process") then
        call msg_fatal ("Grid file: missing 'process' tag")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%process) then
        call msg_message &
            ("Process configuration has changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%model) then
        call msg_message &
            ("Model has changed, discarding old grid file")

```



```

        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%parameters) then
        call msg_message &
            ("Model parameters have changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%phs) then
        call msg_message &
            ("Phase-space setup has changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%beams) then
        call msg_message &
            ("Beam setup has changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%sf_list) then
        call msg_message &
            ("Structure-function setup has changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%mappings) then
        call msg_message &
            ("Mapping scale parameters have changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%cuts) then
        call msg_message &
            ("Cut configuration has changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%weight) then
        call msg_message &
            ("Weight expression has changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%scale) then
        call msg_message &
            ("General scale expression has changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%fac_scale) then
        call msg_message &
            ("Factorization scale expression has changed, discarding old grid file")

```

```

        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%ren_scale) then
        call msg_message &
            ("Renormalization scale expression has changed, discarding old grid file")
        close (u); return
    end if
    read (u, *) buffer, equals, md5sum_file
    if (check .and. md5sum_file /= md5sum%alpha_s) then
        call msg_message &
            ("Alpha(QCD) specifications have changed, discarding old grid file")
        close (u); return
    end if
    read (u, *)
    call grid_parameters_read (grid_parameters_file, u)
    if (check .and. grid_parameters_file /= grid_parameters) then
        call msg_message &
            ("Grid parameters have changed, discarding old grid file")
        close (u); return
    end if
    read (u, *)
    call integration_results_read (results_file, u)
    if (check .and. .not. integration_results_iterations_are_consistent &
        (results_file, pass, n_calls)) then
        call msg_message &
            ("Iteration parameters have changed, discarding old grid file")
        close (u); return
    end if
    results = results_file
    read (u, *)
    call vamp_read_grids (grids, u)
    close (u)
    ok = .true.
end subroutine read_grid_file

```

Write the grid that has the optimal parameters so far, within the current integration pass. This is determined from the current integration results. If the best grid is not the current one, we do nothing.

(Processes: procedures)+≡

```

subroutine write_best_grid_file (filename, process_id, md5sum, &
    grid_parameters, results, grids)
    type(string_t), intent(in) :: filename, process_id
    type(md5sum_grids_t), intent(in) :: md5sum
    type(grid_parameters_t), intent(in) :: grid_parameters
    type(integration_results_t), intent(in) :: results
    type(vamp_grids), intent(in) :: grids
    type(vamp_grids) :: grids_on_file
    type(integration_results_t) :: results_on_file
    integer :: it_current, it_best
    logical :: ok
    integer :: u
    it_current = integration_results_get_current_it (results)

```

```

it_best = integration_results_get_best_it (results)
if (it_best == it_current) then
    call write_grid_file (filename, process_id, md5sum, &
        grid_parameters, results, grids)
end if
end subroutine write_best_grid_file

```

Store the pass and calls arrays that are currently active. They are checked when grid files are re-read for event generation.

```

<Processes: public>+≡
    public :: process_store_iteration_parameters

<Processes: procedures>+≡
    subroutine process_store_iteration_parameters &
        (process, pass_array, n_calls_array)
        type(process_t), intent(inout) :: process
        integer, dimension(:), intent(in) :: pass_array, n_calls_array
        allocate (process%pass_array (size (pass_array)))
        process%pass_array = pass_array
        allocate (process%n_calls_array (size (n_calls_array)))
        process%n_calls_array = n_calls_array
    end subroutine process_store_iteration_parameters

```

Wrapper for grid file reading. We supplement the MD5 sum block with extra entries that we can determine from the process object.

```

<Processes: public>+≡
    public :: process_read_grid_file

<Processes: procedures>+≡
    subroutine process_read_grid_file (process, filename, &
        check_grid_file, md5sum, grid_parameters, pass, n_calls, ok)
        type(process_t), intent(inout) :: process
        type(string_t), intent(in) :: filename
        logical, intent(in) :: check_grid_file
        type(md5sum_grids_t), intent(in) :: md5sum
        type(grid_parameters_t), intent(in) :: grid_parameters
        integer, dimension(:), intent(in) :: pass, n_calls
        logical, intent(out) :: ok
        type(md5sum_grids_t) :: md5sum_local
        md5sum_local = process_collect_md5sum (process, md5sum)
        call read_grid_file (filename, process%id, &
            check_grid_file, md5sum_local, grid_parameters, &
            process%results, process%grids, pass, n_calls, ok)
    end subroutine process_read_grid_file

```

Adapt the binning of the VAMP grids. This is just a wrapper.

```

<Processes: procedures>+≡
    subroutine process_adapt_grids (process)
        type(process_t), intent(inout), target :: process
        call vamp_refine_grids (process%grids)
    end subroutine process_adapt_grids

```

Refine the channel weights. We use a power weight just as for the individual bins. The results are averaged within each grove. Then, we check if the resulting weights would lead to a too small number of calls within any channel, which is corrected. The result is fed into VAMP.

```

<Processes: procedures>+≡
subroutine process_adapt_channel_weights (process, grid_parameters, calls)
  type(process_t), intent(inout), target :: process
  type(grid_parameters_t), intent(in) :: grid_parameters
  integer, intent(in) :: calls
  real(default), dimension(:), allocatable :: weights
  integer :: g, i0, i1, n
  real(default) :: sum_weights, weight_min
  logical, dimension(:), allocatable :: weight_underflow
  real(default) :: sum_weight_underflow
  integer :: n_underflow
  allocate (weights (process%n_channels))
  weights = process%grids%weights &
    * vamp_get_variance (process%grids%grids) &
    ** grid_parameters%channel_weights_power
  do g = 1, phs_forest_get_n_groves (process%forest)
    call phs_forest_get_grove_bounds (process%forest, g, i0, i1, n)
    weights(i0:i1) = sum (weights(i0:i1)) / n
  end do
  sum_weights = sum (weights)
  if (sum_weights /= 0) then
    weights = weights / sum (weights)
    if (grid_parameters%threshold_calls /= 0) then
      weight_min = &
        real (grid_parameters%threshold_calls, default) &
        / calls
      allocate (weight_underflow (process%n_channels))
      weight_underflow = weights /= 0 .and. weights < weight_min
      n_underflow = count (weight_underflow)
      sum_weight_underflow = sum (weights, mask=weight_underflow)
      where (weight_underflow)
        weights = weight_min
      elsewhere
        weights = weights &
          * (1 - n_underflow * weight_min) / (1 - sum_weight_underflow)
      end where
    end if
    call vamp_update_weights (process%grids, weights)
  end if
end subroutine process_adapt_channel_weights

```

Return a concise table of channel weights: sum over all channels that contribute to a grove and return the grove weights.

```

<Processes: procedures>+≡
subroutine process_get_grove_weights (process, grove_weight)
  type(process_t), intent(in) :: process
  real(default), dimension(:), allocatable, intent(out) :: grove_weight
  integer :: n_groves, g, i0, i1, n
  n_groves = phs_forest_get_n_groves (process%forest)

```

```

allocate (grove_weight (n_groves))
do g = 1, n_groves
  call phs_forest_get_grove_bounds (process%forest, g, i0, i1, n)
  grove_weight(g) = sum (process%grids%weights(i0:i1))
end do
end subroutine process_get_grove_weights

```

13.3.21 Event generation

Initialize event generation. For the process setup, this means that the evaluators for the exclusive matrix element with and without color-flow decomposition is activated.

For the hard-interaction evaluators, we select only those entries which are supported by the beam/structure function setup. E.g., we select diagonal helicity only, or sum over helicity if the beams are unpolarized. When constructing the process evaluators, we multiply the beams by the hard-interaction evaluators and trace over all incoming-particle quantum numbers (except for color in the color-flow evaluator).

```

(Processes: public) +=
  public :: process_setup_event_generation

(Processes: procedures) +=
  subroutine process_setup_event_generation (process, qn_mask_in)
    type(process_t), intent(inout), target :: process
    type(quantum_numbers_mask_t), intent(in), optional :: qn_mask_in
    integer, dimension(:), allocatable :: coll_index
    type(quantum_numbers_mask_t), dimension(:), allocatable :: mask_in
    type(md5sum_grids_t) :: md5sum_local
    type(quantum_numbers_mask_t) :: mask_conn_sqme, mask_conn_flows
    type(evaluator_t), pointer :: eval_sfchain, eval_sqme, eval_flows
    type(interaction_t), pointer :: int_hi, int_beam
    integer :: n_in, n_out, n_tot, i
    type(evaluator_t), target :: eval_con
    if (.not. process_has_matrix_element (process)) then
      call msg_warning ("Process '" // char (process%id) // "' : " &
        // "matrix element vanishes, no events can be generated")
      return
    end if
    call process_status_reset_counters (process%status)
    call hard_interaction_final_sqme (process%hi)
    call hard_interaction_final_flows (process%hi)
    call evaluator_final (process%eval_beam_flows)
    call evaluator_final (process%eval_sqme)
    call evaluator_final (process%eval_flows)
    n_in = hard_interaction_get_n_in (process%hi)
    n_out = hard_interaction_get_n_out (process%hi)
    n_tot = hard_interaction_get_n_tot (process%hi)
    int_hi => hard_interaction_get_int_ptr (process%hi)
    call interaction_reset_momenta (int_hi)
    allocate (mask_in (n_in))
    if (process%use_beams) then
      allocate (coll_index (n_in))

```

```

coll_index = strfun_chain_get_colliding_particles (process%sfchain)
mask_in = strfun_chain_get_colliding_particles_mask (process%sfchain)
mask_conn_sqme = new_quantum_numbers_mask (.false., .true., .true.)
mask_conn_flows = new_quantum_numbers_mask (.false., .false., .true.)
else if (present (qn_mask_in)) then
    mask_in = qn_mask_in
else
    mask_in = new_quantum_numbers_mask (.false., .false., .true.)
end if
call hard_interaction_init_sqme (process%hi, mask_in, &
    process%use_hi_color_factors)
call hard_interaction_init_flows (process%hi, mask_in)
int_beam => strfun_chain_get_beam_int_ptr (process%sfchain)
eval_sfchain => strfun_chain_get_last_evaluator_ptr (process%sfchain)
eval_sqme => hard_interaction_get_eval_sqme_ptr (process%hi)
eval_flows => hard_interaction_get_eval_flows_ptr (process%hi)
! print *, "Hard interaction"
! call interaction_write (int_hi)
! print *, "Evaluator: HI: SQME"
! call evaluator_write (eval_sqme)
! print *, "Evaluator: HI: flows"
! call evaluator_write (eval_flows)
if (process%use_beams) then
    if (associated (eval_sfchain)) then
        call evaluator_init_color_contractions &
            (process%eval_beam_flows, evaluator_get_int_ptr (eval_sfchain))
        do i = 1, n_in
            call evaluator_set_source_link &
                (eval_sqme, i, eval_sfchain, coll_index(i))
            call evaluator_set_source_link &
                (eval_flows, i, process%eval_beam_flows, coll_index(i))
        end do
        if (process%has_extra_evaluators) then
            call evaluator_init_product (process%eval_sqme, &
                eval_sfchain, eval_sqme, mask_conn_sqme)
            call evaluator_init_product (process%eval_flows, &
                process%eval_beam_flows, eval_flows, mask_conn_flows)
        end if
    else
        call evaluator_init_color_contractions &
            (process%eval_beam_flows, int_beam)
        do i = 1, n_in
            call evaluator_set_source_link &
                (eval_sqme, i, int_beam, coll_index(i))
            call evaluator_set_source_link &
                (eval_flows, i, process%eval_beam_flows, coll_index(i))
        end do
        if (process%has_extra_evaluators) then
            call evaluator_init_product (process%eval_sqme, &
                int_beam, eval_sqme, mask_conn_sqme)
            call evaluator_init_product (process%eval_flows, &
                process%eval_beam_flows, eval_flows, mask_conn_flows)
        end if
    end if
end if

```

```

!      print *, "Evaluator: Beams+HI: SQME"
!      call evaluator_write (process%eval_sqme)
!      print *, "Evaluator: Beams+HI: flows"
!      call evaluator_write (process%eval_flows)
!      call process_write (process, 77)
!      end if
end subroutine process_setup_event_generation

```

Generate a weighted event. We have to select a channel. The output is the event weight, unmodified. The `sample_function` fully constructs the event in the `process` object, so the output `x` array is not needed.

Analysis is not yet implemented; we need a means to pass the event weight to the recording functions.

```

<Processes: public>+≡
  public :: process_generate_weighted_event

<Processes: procedures>+≡
  subroutine process_generate_weighted_event (process, rng, weight)
    type(process_t), intent(inout), target :: process
    type(tao_random_state), intent(inout) :: rng
    real(default), intent(out) :: weight
    real(default), dimension(process%n_par) :: x
    call vamp_next_event &
      (x, rng, process%grids, &
       sample_function, process%store_index, phi_trivial, &
       weight=weight)
    call process_complete_evaluators (process)
  end subroutine process_generate_weighted_event

```

Generate an unweighted event. Rejection is done by VAMP. The optional `excess` is nonzero by the excess weight if an event weight exceeds the precalculated maximum that is used for rejection. After the event has been generated, it can be analyzed.

The transformation function `phi` is trivial but has to be supplied.

```

<Processes: public>+≡
  public :: process_generate_unweighted_event

<Processes: procedures>+≡
  subroutine process_generate_unweighted_event (process, rng, excess)
    type(process_t), intent(inout), target :: process
    type(tao_random_state), intent(inout) :: rng
    real(default), intent(out), optional :: excess
    real(default), dimension(process%n_par) :: x
    call vamp_next_event &
      (x, rng, process%grids, &
       sample_function, process%store_index, phi_trivial, &
       excess=excess)
    call process_complete_evaluators (process)
  end subroutine process_generate_unweighted_event

function phi_trivial (xi, channel_dummy) result (x)
  real(default), dimension(:), intent(in) :: xi
  integer, intent(in) :: channel_dummy

```

```

    real(default), dimension(size(xi)) :: x
    x = xi
end function phi_trivial

```

Complete the event: compute amplitudes/probabilities for exclusive quantum numbers.

```

<Processes: public>+≡
    public :: process_complete_evaluators

<Processes: procedures>+≡
    subroutine process_complete_evaluators (process)
        type(process_t), intent(inout), target :: process
        if (process%use_beams) then
            call evaluator_receive_momenta (process%eval_beam_flows)
            call evaluator_evaluate (process%eval_beam_flows)
        end if
        call hard_interaction_evaluate_sqme (process%hi)
        call hard_interaction_evaluate_flows (process%hi)
        if (process%has_extra_evaluators) then
            call evaluator_receive_momenta (process%eval_sqme)
            call evaluator_receive_momenta (process%eval_flows)
            call evaluator_evaluate (process%eval_sqme)
            call evaluator_evaluate (process%eval_flows)
        end if
    end subroutine process_complete_evaluators

```

This procedure is used for checking whether some of the final-state particles can initiate decay cascades.

```

<Processes: public>+≡
    public :: process_get_unstable_products

<Processes: procedures>+≡
    subroutine process_get_unstable_products (process, flv_unstable)
        type(process_t), intent(in) :: process
        type(flavor_t), dimension(:), intent(out), allocatable :: flv_unstable
        call hard_interaction_get_unstable_products (process%hi, flv_unstable)
    end subroutine process_get_unstable_products

```

When the event is generated externally (e.g., read from file), we need to fill the subevent with the process record in order to analyze it. This is done here:

```

<Processes: public>+≡
    public :: process_set_particles

<Processes: procedures>+≡
    subroutine process_set_particles (process, particle_set)
        type(process_t), intent(inout) :: process
        type(particle_set_t), intent(in) :: particle_set
        call particle_set_to_subevt (particle_set, process%subevt)
    end subroutine process_set_particles

```


13.3.22 Results output

(Processes: public)+≡

```
public :: process_results_write_header
public :: process_results_write_entry
public :: process_results_write_current
public :: process_results_write_average
public :: process_results_write_current_average
public :: process_results_write_footer
public :: process_results_write
```

(Processes: procedures)+≡

```
subroutine process_results_write_header (process, unit, logfile)
  type(process_t), intent(in) :: process
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: logfile
  call write_dline (unit)
  call write_header (process%type, unit, logfile)
  call write_dline (unit)
end subroutine process_results_write_header

subroutine process_results_write_entry (process, it, unit)
  type(process_t), intent(in) :: process
  integer, intent(in) :: it
  integer, intent(in), optional :: unit
  call integration_results_write_entry (process%results, it, unit)
end subroutine process_results_write_entry

subroutine process_results_write_current (process, unit)
  type(process_t), intent(in) :: process
  integer, intent(in), optional :: unit
  call integration_results_write_current (process%results, unit)
end subroutine process_results_write_current

subroutine process_results_write_average (process, pass, unit)
  type(process_t), intent(in) :: process
  integer, intent(in) :: pass
  integer, intent(in), optional :: unit
  call write_hline (unit)
  call integration_results_write_average (process%results, pass, unit)
  call write_hline (unit)
end subroutine process_results_write_average

subroutine process_results_write_current_average (process, unit)
  type(process_t), intent(in) :: process
  integer, intent(in), optional :: unit
  call write_hline (unit)
  call integration_results_write_current_average (process%results, unit)
  call write_hline (unit)
end subroutine process_results_write_current_average

subroutine process_results_write_footer (process, unit, no_line)
  type(process_t), intent(in) :: process
  integer, intent(in), optional :: unit
  logical, intent(in), optional :: no_line
```

```

    if (present (no_line)) then
        if (.not. no_line) call write_dline (unit)
    else
        call write_dline (unit)
    end if
    call integration_results_write_current_average (process%results, unit)
    call write_dline (unit)
end subroutine process_results_write_footer

subroutine process_results_write (process, unit)
    type(process_t), intent(in) :: process
    integer, intent(in), optional :: unit
    call integration_results_write (process%results, unit)
end subroutine process_results_write

```

Record the integration results in the process library entry.

```

<Processes: public>+≡
    public :: process_record_integral

<Processes: procedures>+≡
    subroutine process_record_integral (process, var_list)
        type(process_t), intent(inout) :: process
        type(var_list_t), intent(inout) :: var_list
        integer :: n_calls
        real(default) :: integral, error, accuracy, chi2, efficiency
        n_calls = integration_results_get_n_calls (process%results)
        integral = integration_results_get_integral (process%results)
        error = integration_results_get_error (process%results)
        accuracy = integration_results_get_accuracy (process%results)
        chi2 = integration_results_get_chi2 (process%results)
        efficiency = integration_results_get_efficiency (process%results)
        call var_list_init_process_results (var_list, process%id, &
            n_calls, integral, error, accuracy, chi2, efficiency)
    end subroutine process_record_integral

```

13.3.23 Copies

Process copies are used for decay chains (and such). We deep-copy most components, in particular the hard-interaction and decay-forest workspaces. Read-only components (variable list) and eval trees are transferred as shallow copies.

We do not copy the extra evaluators that convolute beams and hard matrix elements. Actually, beams should not be defined for a cascade decay process in the first place, but we do not enforce this. We also skip the integration results.

Furthermore, we have to reassign all external links between interactions within the process copy to point to the copy, not the original.

The copy is linked to the original by a pointer. Its initial state is `in_use`.

```

<Processes: procedures>+≡
    subroutine process_make_copy (process, original)
        type(process_t), intent(inout), target :: process
        type(process_t), intent(in), target :: original
        type(process_t), pointer :: copy

```

```

type(interaction_t), pointer :: beam_int, copy_beam_int
type(interaction_t), pointer :: hi_int, copy_hi_int
type(evaluator_t), pointer :: hi_eval_trace, copy_hi_eval_trace
type(evaluator_t), pointer :: hi_eval_sqme, copy_hi_eval_sqme
type(evaluator_t), pointer :: hi_eval_flows, copy_hi_eval_flows
allocate (copy)
copy%type = original%type
copy%is_original = .false.
copy%original => original
copy%initialized = original%initialized
copy%has_matrix_element = original%has_matrix_element
copy%use_hi_color_factors = original%use_hi_color_factors
copy%use_beams = original%use_beams
copy%has_extra_evaluators = .false.
copy%beams_are_set = original%beams_are_set
copy%is_cascade_decay = original%is_cascade_decay
copy%id = original%id
copy%prc_lib => original%prc_lib
copy%lib_index = original%lib_index
copy%store_index = original%store_index
copy%model => original%model
if (original%use_beams) then
    copy%n_strfun = original%n_strfun
    copy%n_par_strfun = original%n_par_strfun
end if
copy%n_par_hi = original%n_par_hi
copy%n_par = original%n_par
copy%azimuthal_dependence = original%azimuthal_dependence
copy%vamp_grids_defined = original%vamp_grids_defined
copy%sqrts_known = original%sqrts_known
copy%sqrts = original%sqrts
if (original%use_beams) then
    if (allocated (original%x_strfun)) &
        allocate (copy%x_strfun (size (original%x_strfun)))
end if
if (allocated (original%x_hi)) &
    allocate (copy%x_hi (size (original%x_hi)))
copy%n_channels = original%n_channels
if (allocated (original%x)) &
    allocate (copy%x (size (original%x, 1), size (original%x, 2)))
if (allocated (original%sf_factor)) &
    allocate (copy%sf_factor (size (original%sf_factor)))
if (allocated (original%phs_factor)) &
    allocate (copy%phs_factor (size (original%phs_factor)))
if (allocated (original%mass_in)) then
    allocate (copy%mass_in (size (original%mass_in)))
    copy%mass_in = original%mass_in
end if
copy%averaging_factor = original%averaging_factor
if (original%use_beams) copy%sfchain = original%sfchain
copy%hi = original%hi
if (original%use_beams) copy%eval_trace = original%eval_trace
! copy%eval_beam_flows = original%eval_beam_flows
! copy%eval_sqme = original%eval_sqme

```

```

! copy%eval_flows = original%eval_flows
copy%forest = original%forest
copy%vamp_eq = original%vamp_eq
allocate (copy%j_beam (size (original%j_beam)))
copy%j_beam = original%j_beam
allocate (copy%j_in (size (original%j_in)))
copy%j_in = original%j_in
allocate (copy%j_out (size (original%j_out)))
copy%j_out = original%j_out
copy%subevt = original%subevt
copy%var_list = original%var_list
copy%cut_pn => original%cut_pn
copy%weight_pn => original%weight_pn
copy%scale_pn => original%scale_pn
copy%fac_scale_pn => original%fac_scale_pn
copy%ren_scale_pn => original%ren_scale_pn
copy%cut_expr = original%cut_expr
copy%reweighting_expr = original%reweighting_expr
copy%scale_expr = original%scale_expr
copy%fac_scale_expr = original%fac_scale_expr
copy%ren_scale_expr = original%ren_scale_expr
if (allocated (original%active_channel)) then
    allocate (copy%active_channel (size (original%active_channel)))
    copy%active_channel = original%active_channel
end if
copy%filename_current_grid = original%filename_current_grid
copy%filename_best_grid = original%filename_best_grid
copy%md5sum_grids = original%md5sum_grids
copy%grid_parameters = original%grid_parameters
if (allocated (original%pass_array)) then
    allocate (copy%pass_array (size (original%pass_array)))
    copy%pass_array = original%pass_array
end if
if (allocated (original%n_calls_array)) then
    allocate (copy%n_calls_array (size (original%n_calls_array)))
    copy%n_calls_array = original%n_calls_array
end if
call vamp_copy_grids (copy%grids, original%grids)
beam_int => strfun_chain_get_beam_int_ptr (original%sfchain)
hi_int => hard_interaction_get_int_ptr (original%hi)
hi_eval_trace => hard_interaction_get_eval_trace_ptr (original%hi)
hi_eval_sqme => hard_interaction_get_eval_sqme_ptr (original%hi)
hi_eval_flows => hard_interaction_get_eval_flows_ptr (original%hi)
copy_beam_int => strfun_chain_get_beam_int_ptr (copy%sfchain)
copy_hi_int => hard_interaction_get_int_ptr (copy%hi)
copy_hi_eval_trace => hard_interaction_get_eval_trace_ptr (copy%hi)
copy_hi_eval_sqme => hard_interaction_get_eval_sqme_ptr (copy%hi)
copy_hi_eval_flows => hard_interaction_get_eval_flows_ptr (copy%hi)
select case (original%type)
case (PRC_SCATTERING)
    call msg_bug ("Process copy for scattering processes not implemented")
case (PRC_DECAY)
    call interaction_reassign_links &
        (copy_hi_int, beam_int, copy_beam_int)

```

```

call evaluator_reassign_links &
  (copy_hi_eval_trace, beam_int, copy_beam_int)
call evaluator_reassign_links &
  (copy_hi_eval_sqme, beam_int, copy_beam_int)
call evaluator_reassign_links &
  (copy_hi_eval_flows, beam_int, copy_beam_int)
call evaluator_reassign_links &
  (copy_hi_eval_trace, hi_int, copy_hi_int)
call evaluator_reassign_links &
  (copy_hi_eval_sqme, hi_int, copy_hi_int)
call evaluator_reassign_links &
  (copy_hi_eval_flows, hi_int, copy_hi_int)
call evaluator_reassign_links &
  (copy%eval_trace, beam_int, copy_beam_int)
call evaluator_reassign_links &
  (copy%eval_sqme, beam_int, copy_beam_int)
call evaluator_reassign_links &
  (copy%eval_flows, beam_int, copy_beam_int)
call evaluator_reassign_links &
  (copy%eval_trace, hi_eval_trace, copy_hi_eval_trace)
call evaluator_reassign_links &
  (copy%eval_sqme, hi_eval_sqme, copy_hi_eval_sqme)
call evaluator_reassign_links &
  (copy%eval_flows, hi_eval_flows, copy_hi_eval_flows)
end select
process%copy => copy
end subroutine process_make_copy

```

Request a process copy. If there is a copy currently not in use, activate it. Otherwise, make a new copy. In the original process, point to this copy as the working copy.

```

<Processes: public>+≡
  public :: process_request_copy

<Processes: procedures>+≡
  recursive subroutine process_request_copy (process, copy, original)
    type(process_t), intent(inout), target :: process
    type(process_t), pointer :: copy
    type(process_t), intent(inout), target, optional :: original
    if (associated (process%copy)) then
      if (process%copy%in_use) then
        if (present (original)) then
          call process_request_copy (process%copy, copy, original)
        else
          call process_request_copy (process%copy, copy, process)
        end if
      else
        copy => process%copy
        copy%in_use = .true.
        if (present (original)) then
          original%working_copy => copy
        else
          process%working_copy => copy
        end if
      end if
    end if
  end subroutine process_request_copy

```

```

        end if
    else
        if (present (original)) then
            call process_make_copy (process, original)
        else
            call process_make_copy (process, original=process)
        end if
        copy => process%copy
        copy%in_use = .true.
        if (present (original)) then
            original%working_copy => copy
        else
            process%working_copy => copy
        end if
    end if
end subroutine process_request_copy

```

Return the working copy of a process. If there is none, return the process itself.

```

<Processes: procedures>+≡
function process_get_working_copy_ptr (process) result (copy)
    type(process_t), intent(in), target :: process
    type(process_t), pointer :: copy
    if (associated (process%working_copy)) then
        copy => process%working_copy
    else
        copy => process
    end if
end function process_get_working_copy_ptr

```

Tag a given process copy as the working copy. When looking for the working copy, a pointer to this one will be returned.

```

<Processes: public>+≡
    public :: process_tag_as_working_copy

<Processes: procedures>+≡
subroutine process_tag_as_working_copy (process)
    type(process_t), intent(inout), target :: process
    type(process_t), pointer :: original
    if (associated (process%original)) then
        original => process%original
        original%working_copy => process
    else
        call msg_bug ("Process tag as working copy failed")
    end if
end subroutine process_tag_as_working_copy

```

Mark this copy of the current process as not in use, so it can be requested again. (Use with care! The copy will not reflect changes made to the original process.)

```

<Processes: public>+≡
    public :: process_free_copy

<Processes: procedures>+≡
subroutine process_free_copy (process)

```

```

    type(process_t), intent(inout), target :: process
    process%in_use = .false.
    if (associated (process%original)) then
        process%original%working_copy => null ()
    end if
end subroutine process_free_copy

```

Delete all copies.

```

<Process: public>≡
    public :: process_delete_copy

<Processes: procedures>+≡
    recursive subroutine process_delete_copies (process)
        type(process_t), intent(inout), target :: process
        if (associated (process%copy)) then
            call process_final (process%copy)
            deallocate (process%copy)
        end if
    end subroutine process_delete_copies

```

13.3.24 Process store

The process store is a container for the list of all processes. The list is expanded as needed during program execution. The container is implemented as a module variable. Thus, there is only one process store in the program.

The reason for this is the sampling function, which needs to access it without referencing it as an argument. Instead, it takes an integer argument which identifies the process. For direct access, we maintain a process pointer array as a shortcut to the list.

Type and object

```

<Processes: types>+≡
    type :: process_entry_t
        type(process_t) :: process
        type(process_entry_t), pointer :: next => null ()
    end type process_entry_t

<Processes: types>+≡
    type :: process_store_t
        integer :: n = 0
        type(process_entry_t), pointer :: first => null ()
        type(process_entry_t), pointer :: last => null ()
        type(process_p), dimension(:), allocatable :: proc
    end type process_store_t

<Processes: variables>≡
    type(process_store_t), save :: store

```

Finalize. Delete the list explicitly, the pointer array is just deallocated.

```

<Processes: public>+=
    public :: process_store_final

<Processes: procedures>+=
    subroutine process_store_final ()
        type(process_entry_t), pointer :: current
        if (allocated (store%proc)) deallocate (store%proc)
        store%last => null ()
        do while (associated (store%first))
            current => store%first
            store%first => current%next
            call process_final (current%process)
            deallocate (current)
        end do
        store%n = 0
    end subroutine process_store_final

```

Handlers for unloading and reloading process libraries

```

<Processes: public>+=
    public :: process_store_unload
    public :: process_store_reload

<Processes: procedures>+=
    subroutine process_store_unload (libname)
        type(string_t), intent(in) :: libname
        type(process_entry_t), pointer :: entry
        entry => store%first
        do while (associated (entry))
            if (process_library_get_name (entry%process%prc_lib) == libname) &
                call worker (entry%process)
            entry => entry%next
        end do

contains

        recursive subroutine worker (process)
            type(process_t), intent(inout), target :: process
            call hard_interaction_unload (process%hi)
            if (associated (process%copy)) call worker (process%copy)
        end subroutine worker

    end subroutine process_store_unload

    subroutine process_store_reload (libname)
        type(string_t), intent(in) :: libname
        type(process_entry_t), pointer :: entry
        entry => store%first
        do while (associated (entry))
            if (process_library_get_name (entry%process%prc_lib) == libname) &
                call worker (entry%process)
            entry => entry%next
        end do

```


contains

```
recursive subroutine worker (process)
  type(process_t), intent(inout), target :: process
  call hard_interaction_reload (process%hi, process%prc_lib)
  if (associated (process%copy)) call worker (process%copy)
end subroutine worker

end subroutine process_store_reload
```

Write all contents. This produces lots of output.

<Processes: public>+≡

```
public :: process_store_write
```

<Processes: procedures>+≡

```
subroutine process_store_write (unit)
  integer, intent(in), optional :: unit
  type(process_t), pointer :: process
  integer :: u, i
  u = output_unit (unit); if (u < 0) return
  write (u, *) repeat ("%", 78)
  write (u, *) "Process store contents"
  do i = 1, store%n
    write (u, *) repeat ("%", 78)
    write (u, *) "Process No.", i
    process => store%proc(i)%ptr
    call process_write (process, unit)
  end do
  write (u, *) "Process store end"
  write (u, *) repeat ("%", 78)
end subroutine process_store_write
```

Write integration results (summary)

<Processes: public>+≡

```
public :: process_store_write_results
```

<Processes: procedures>+≡

```
subroutine process_store_write_results (unit)
  integer, intent(in), optional :: unit
  type(process_t), pointer :: process
  type(string_t), dimension(:), allocatable :: process_id
  real(default), dimension(:), allocatable :: integral, error
  type(string_t), dimension(:), allocatable :: phys_unit
  integer :: u, i, process_id_len
  character(12) :: fmt
  u = output_unit (unit); if (u < 0) return
  allocate (process_id (store%n), phys_unit (store%n))
  allocate (integral (store%n), error (store%n))
  do i = 1, store%n
    process => store%proc(i)%ptr
    if (process%initialized) then
      process_id(i) = process%id
      integral(i) = process_get_integral (process)
      error(i) = process_get_error (process)
    end if
  end do
end subroutine process_store_write_results
```

```

        select case (process%type)
        case (PRC_DECAY);      phys_unit(i) = "GeV"
        case (PRC_SCATTERING); phys_unit(i) = "fb"
        case default;          phys_unit(i) = "[undefined]"
        end select
    else
        process_id(i) = ""
    end if
end do
write (u, "(A)")  "|===== Results Summary ====="
if (store%n == 0) then
    write (u, *) "[empty]"
else
    process_id_len = maxval (len (process_id))
    write (fmt, "(A,IO,A)"  "(1x,A", process_id_len + 1, ")")
    do i = 1, store%n
        if (process_id(i) /= "") then
            write (u, fmt, advance="no") char (process_id(i)) // ":"
            write (u, "(1x, 1PE15.8, 1x, '+-', 1x, 1PE8.2)", advance="no") &
                integral(i), error(i)
            write (u, "(1x, A)"  char (phys_unit(i))
        end if
    end do
end if
write (u, "(A)")  "|=====
end subroutine process_store_write_results

```

Accessing contents

Return the current number of processes.

```

<Processes: procedures>+≡
function process_store_get_n_processes () result (n)
    integer :: n
    n = store%n
end function process_store_get_n_processes

```

Return a pointer to the process entry with given ID. If it does not exist, return a null pointer.

```

<Processes: procedures>+≡
function process_store_get_entry_ptr (process_id) result (entry)
    type(process_entry_t), pointer :: entry
    type(string_t), intent(in) :: process_id
    entry => store%first
    do while (associated (entry))
        if (entry%process%id == process_id) exit
        entry => entry%next
    end do
end function process_store_get_entry_ptr

```

Return the index of the process entry with given ID within the process store. If it does not exist, return zero.

```

<Processes: procedures>+≡
function process_store_get_process_index (process_id) result (process_index)
    integer :: process_index
    type(string_t), intent(in) :: process_id
    type(process_entry_t), pointer :: entry
    entry => process_store_get_entry_ptr (process_id)
    if (associated (entry)) then
        process_index = entry%process%store_index
    else
        process_index = 0
    end if
end function process_store_get_process_index

```

Return a pointer to the process with index i or alphanumeric ID.

```

<Processes: public>+≡
public :: process_store_get_process_ptr

<Processes: interfaces>+≡
interface process_store_get_process_ptr
    module procedure process_store_get_process_ptr_int
    module procedure process_store_get_process_ptr_id
end interface

```

```

<Processes: procedures>+≡
function process_store_get_process_ptr_int (i) result (process)
    type(process_t), pointer :: process
    integer, intent(in) :: i
    if (i > 0 .and. i <= size (store%proc)) then
        process => store%proc(i)%ptr
    else
        process => null ()
    end if
end function process_store_get_process_ptr_int

function process_store_get_process_ptr_id (id) result (process)
    type(process_t), pointer :: process
    type(string_t), intent(in) :: id
    integer :: i
    do i = 1, store%n
        process => store%proc(i)%ptr
        if (process%id == id) return
    end do
    process => null ()
end function process_store_get_process_ptr_id

```

Filling the process store

Append a new process entry and return a pointer to it, unless the process already exists. If the process exists, finalize it and return the pointer for fresh initialization. If it does not exist, allocate a new entry and update the shortcut array. If the latter is full, expand by a fixed block size.

```

<Processes: procedures>+≡

```

```

function process_store_get_fresh_process_ptr (process_id) result (process)
  type(process_t), pointer :: process
  type(string_t), intent(in) :: process_id
  type(process_entry_t), pointer :: current, entry
  integer :: i
  integer, parameter :: BLOCK_SIZE = 10
  current => process_store_get_entry_ptr (process_id)
  if (associated (current)) then
    call process_final (current%process)
  else
    allocate (current)
    if (store%n == 0) then
      allocate (store%proc (BLOCK_SIZE))
      store%first => current
    else
      store%last%next => current
    end if
    store%last => current
    store%n = store%n + 1
    if (store%n <= size (store%proc)) then
      store%proc(store%n)%ptr => current%process
    else
      deallocate (store%proc)
      allocate (store%proc (store%n + BLOCK_SIZE))
      i = 1
      entry => store%first
      do while (associated (entry))
        store%proc(i)%ptr => entry%process; i = i + 1
        entry => entry%next
      end do
    end if
  end if
  process => current%process
end function process_store_get_fresh_process_ptr

```

Append a new process entry (or find an existing one) and initialize it with a particular hard process, model pointer and total energy. Return a pointer to the process object, so further process preparation can be done by the caller. Allocate or expand the array as needed.

(Processes: public)+≡

```
public :: process_store_init_process
```

(Processes: procedures)+≡

```

subroutine process_store_init_process (process, &
  prc_lib, process_id, model, var_list, &
  use_beams)
  type(process_t), pointer :: process
  type(process_library_t), intent(inout), target :: prc_lib
  type(string_t), intent(in) :: process_id
  type(model_t), intent(in), target :: model
  type(pdf_builtin_status_t) :: pdf_builtin_status
  type(var_list_t), intent(in), target :: var_list
  logical, intent(in) :: use_beams
  integer :: process_lib_index, process_store_index

```

```

procedure(prclib_unload_hook), pointer :: unload_hook
procedure(prclib_reload_hook), pointer :: reload_hook
process_lib_index = process_library_get_process_index (prc_lib, process_id)
if (process_lib_index == 0) then
    call msg_fatal ("Process '" // char (process_id) &
        // "' is not available.")
end if
process_store_index = process_store_get_process_index (process_id)
process => process_store_get_fresh_process_ptr (process_id)
if (process_store_index == 0) then
    process_store_index = process_store_get_n_processes ()
end if
unload_hook => process_store_unload
reload_hook => process_store_reload
call process_library_set_unload_hook (prc_lib, unload_hook)
call process_library_set_reload_hook (prc_lib, reload_hook)
call process_init &
    (process, prc_lib, process_lib_index, process_store_index, &
        process_id, model, var_list, use_beams)
end subroutine process_store_init_process

```

13.3.25 Sampling function

This is the function that computes the squared matrix element in the form needed for VAMP integration. It computes and multiplies the flux factor for the incoming particles, the phase-space factors of the integration channels combined with the VAMP grid jacobians to a common phase-space factor, the phase-space volume, and the squared matrix element of the hard interaction. The latter is only evaluated if the event passes cuts.

There are time-critical operations involved here, so we set breakpoints.

When doing a mere matrix-element test, after evaluating kinematics we do not stop if we encounter an unphysical configuration. This use case is characterized by the absence of the `grids` argument.

(Processes: procedures)+≡

```

function sample_function (xi, prc_index, weights, channel, grids) result (f)
    real(default) :: f
    real(default), dimension(:), intent(in) :: xi
    integer, intent(in) :: prc_index
    real(default), dimension(:), intent(in), optional :: weights
    integer, intent(in), optional :: channel
    type(vamp_grid), dimension(:), intent(in), optional :: grids
    type(process_t), pointer :: process
    logical :: ok
    call terminate_now_if_signal ()
    process => process_get_working_copy_ptr (store%proc(prc_index)%ptr)
    call process_status_reset_flags (process%status)
    call process_status_called (process%status)
    call process_set_kinematics (process, xi, channel, ok)
    if (ok) then
        call process_fill_subevt (process, transform=process%is_cascade_decay)
        ok = process_passes_cuts (process)
    end if
end function sample_function

```

```

        if (ok) call process_status_passed_cuts (process%status)
    end if
    call terminate_now_if_signal ()
    if (ok) then
        call process_complete_kinematics (process, channel)
        if (present (grids)) then
            call process_compute_vamp_phs_factor (process, weights)
        else
            process%vamp_phs_factor = 1
        end if
        call process_compute_scale (process)
        call process_update_alpha_s (process)
        call process_evaluate (process)
        call process_compute_reweighting_factor (process)
        process%sample_function_value = &
            process%flux_factor &
            * process%sf_mapping_factor &
            * process%vamp_phs_factor &
            * process%phs_volume &
            * process%sqme &
            * process%reweighting_factor
        call process_status_passed_evaluation (process%status)
    else
        process%sample_function_value = 0
    end if
    f = process%sample_function_value
    call terminate_now_if_signal ()
end function sample_function

```

13.3.26 Test

(Processes: public)+≡

```
public :: process_test
```

(Processes: procedures)+≡

```

subroutine process_test ()
    type(os_data_t), pointer :: os_data => null ()
    type(process_library_t), pointer :: prc_lib => null ()
    type(model_t), pointer :: model => null ()
    type(var_list_t), pointer :: var_list => null ()
    allocate (os_data)
    allocate (prc_lib)
    allocate (var_list)
    call process_library_store_final
    call os_data_init (os_data)
    print *, "*** Read model file"
    call syntax_model_file_init ()
    call model_list_read_model &
        (var_str("SM"), var_str("SM.mdl"), os_data, model)
    var_list => model_get_var_list_ptr (model)
    call syntax_pexpr_init ()
    call syntax_phs_forest_init ()
    print *

```

```

print *, "*** Create process library"
call var_list_append_string (var_list, name = "$library_name", sval = "prc_proc") ! $
call var_list_append_log (var_list, name = "?read_color_factors", lval = .true.)
call var_list_append_log (var_list, name = "?alpha_s_is_fixed", lval = .true.)
call process_library_store_append (var_str ("prc_proc"), os_data, prc_lib)
call process_library_init (prc_lib, var_str("prc_proc"), os_data)
print *
call process_test1 (prc_lib, os_data, model, var_list)
print *
call process_test2 (prc_lib, os_data, model, var_list)
print *
call process_test3 (prc_lib, os_data, model, var_list)
print *
call process_test4 (prc_lib, os_data, model, var_list)
print *
print *, "* Cleanup"
call process_store_final ()
call syntax_pexpr_final ()
call syntax_phs_forest_final ()
call syntax_model_file_final ()
call process_library_final (prc_lib)
deallocate (prc_lib)
deallocate (os_data)
end subroutine process_test

```

Test decay process: $Z \rightarrow e^+e^-$ (colorless); polarized and unpolarized
(Processes: procedures)+≡

```

subroutine process_test1 (prc_lib, os_data, model, var_list)
  type(process_library_t), intent(inout) :: prc_lib
  type(model_t), intent(in), target :: model
  type(var_list_t), intent(inout), target :: var_list
  type(process_t), pointer :: process
  type(string_t) :: objlist
  type(string_t), dimension(:), allocatable :: prt_in, prt_out
  type(os_data_t), intent(inout) :: os_data
  type(phs_parameters_t) :: phs_par
  type(mapping_defaults_t) :: mapping_defaults
  type(flavor_t), dimension(1) :: flv
  type(polarization_t), dimension(1) :: pol
  type(beam_data_t) :: beam_data
  type(grid_parameters_t) :: grid_parameters
  type(tao_random_state) :: rng
  integer :: i
  logical :: rebuild_phs = .true.
  logical :: discard_integrals, adapt_grids, adapt_weights, print_current
  logical :: time_estimate = .true.
  print *, "*** Test decay process Z -> e+ e- ***"
  print *
  print *, "* Initialization"
  call tao_random_create (rng, 0)
  allocate (prt_in (1), prt_out (2))
  print *, "setting particles for Z -> e+ e-"
  prt_in(1) = "Z"

```

```

prt_out(1) = "e1"
prt_out(2) = "E1"
call process_library_append &
    (prc_lib, var_str ("zff"), model, prt_in, prt_out, method = PRC_TEST, &
        message = .true. )
deallocate (prt_in, prt_out)
allocate (prt_in (1), prt_out (2))
print *, "setting particles for Z -> u ubar"
prt_in(1) = "Z"
prt_out(1) = "u"
prt_out(2) = "U"
call process_library_append &
    (prc_lib, var_str ("zqq"), model, prt_in, prt_out, method = PRC_TEST, &
        message = .true. )
deallocate (prt_in, prt_out)
allocate (prt_in (2), prt_out (3))
print *, "setting particles for e+ e- -> nu nubar H"
prt_in(1) = "e1"
prt_in(2) = "E1"
prt_out(1) = "nue"
prt_out(2) = "nuebar"
prt_out(3) = "H"
call process_library_append &
    (prc_lib, var_str ("nnh"), model, prt_in, prt_out, method = PRC_TEST, &
        message = .true. )
deallocate (prt_in, prt_out)
allocate (prt_in (2), prt_out (2))
print *, "setting particles for g g -> u ubar"
prt_in(1) = "g"
prt_in(2) = "g"
prt_out(1) = "u"
prt_out(2) = "U"
call process_library_append &
    (prc_lib, var_str ("gguu"), model, prt_in, prt_out, method = PRC_TEST, &
        message = .true. )
deallocate (prt_in, prt_out)
print *
print *, "* Generate code"
call process_library_generate_code (prc_lib, os_data)
print *
print *, "* Write driver file 'prc_proc_interface.f90'"
call process_library_write_driver (prc_lib)
print *
print *, "* Compile and link as 'libprc_proc.so'"
call process_library_compile (prc_lib, os_data, .false., objlist)
call process_library_link (prc_lib, os_data, objlist)
print *
print *, "* Load shared libraries"
call process_library_load (prc_lib, os_data, var_list = var_list)
print *
call process_store_init_process &
    (process, prc_lib, var_str ("zff"), model, &
        var_list, use_beams = .true.)
print *

```



```

print *, "*** Beam/strfun setup (unpolarized)"
print *
call flavor_init (flv, (/ 23 /), model)
call polarization_init_unpolarized (pol(1), flv(1))
call beam_data_init_decay (beam_data, flv, pol)
call process_setup_beams (process, beam_data, 0)
call process_connect_strfun (process)
call process_setup_subevt (process)
print *
print *, "* Phase space setup"
call openmp_set_num_threads_verbose (1)
call process_setup_phase_space (process, rebuild_phs, &
    os_data, phs_par, mapping_defaults, filename_out=var_str("zff.phs"), &
    vis_channels = .false.)
call process_init_vamp_history (process, 1)
print *
print *, "*** Test integration"
print *, "* Grids setup"
grid_parameters%stratified = .false.
call process_setup_grids (process, grid_parameters, calls=9)
print *
print *, "* 1 iteration with minimal number of calls"
call process_results_write_header (process)
do i = 1, 1
    discard_integrals = i==1
    adapt_grids = .true.
    adapt_weights = .true.
    print_current = .true.
    call process_integrate (process, rng, grid_parameters, &
        1, 1, 1, 9, &
        discard_integrals, adapt_grids, adapt_weights, print_current, &
        time_estimate)
end do
call process_results_write_footer (process)
print *
print *, "* Process written to 'fort.60'"
call process_write (process, 60)
print *
print *, "*** Beam/strfun setup (polarized)"
call process_store_init_process &
    (process, prc_lib, var_str ("zff"), model, &
    var_list, use_beams = .true.)
call flavor_init (flv, (/ 23 /), model)
call polarization_init_axis &
    (pol(1), flv(1), (/ 0._default, 0._default, 1._default/))
call beam_data_init_decay (beam_data, flv, pol)
call process_setup_beams (process, beam_data, 0)
call process_connect_strfun (process)
call process_setup_subevt (process)
print *
print *, "* Phase space setup"
call openmp_set_num_threads_verbose (1)
call process_setup_phase_space (process, rebuild_phs, &
    os_data, phs_par, mapping_defaults, filename_out=var_str("zff.phs"), &

```

```

        vis_channels = .false.)
call process_init_vamp_history (process, 6)
print *
print *, "*** Test integration"
print *, "* Grids setup"
grid_parameters%stratified = .false.
call process_setup_grids (process, grid_parameters, calls=10000)
print *
print *, "* 3 + 3 iterations"
call process_results_write_header (process)
do i = 1, 3
    discard_integrals = i==1
    adapt_grids = .true.
    adapt_weights = .true.
    print_current = .true.
    call process_integrate (process, rng, grid_parameters, &
        1, 1, 1, 10000, &
        discard_integrals, adapt_grids, adapt_weights, print_current, &
        time_estimate)
end do
call process_results_write_current_average (process)
call process_integrate (process, rng, grid_parameters, &
    2, 1, 3, 10000, &
    .true., .true., .false., .true., .true.)
call process_results_write_footer (process)
call process_write_time_estimate (process)
print *
print *, "* Process written to 'fort.61'"
call process_write (process, 61)
end subroutine process_test1

```

Test decay process: $Z \rightarrow uu$.

(Processes: procedures)+≡

```

subroutine process_test2 (prc_lib, os_data, model, var_list)
    type(process_library_t), intent(inout) :: prc_lib
    type(model_t), intent(in), target :: model
    type(var_list_t), intent(in), target :: var_list
    type(string_t) :: objlist
    type(process_t), pointer :: process
    type(os_data_t), intent(inout) :: os_data
    type(phs_parameters_t) :: phs_par
    type(mapping_defaults_t) :: mapping_defaults
    type(flavor_t), dimension(1) :: flv
    type(polarization_t), dimension(1) :: pol
    type(beam_data_t) :: beam_data
    type(grid_parameters_t) :: grid_parameters
    type(tao_random_state) :: rng
    real(default) :: weight
    logical :: time_estimate = .true.
    integer :: i
    logical :: rebuild_phs = .true.
    logical :: discard_integrals, adapt_grids, adapt_weights, print_current
    print *, "*** Test decay process Z -> u ubar ***"
    print *

```

```

print *, "* Initialization"
call tao_random_create (rng, 0)
call process_store_init_process &
    (process, prc_lib, var_str ("zqq"), model, &
    var_list, use_beams=.false.)
print *, " Process ID = ", char (process%id)
print *
print *, "*** Beam/strfun setup (unpolarized)"
print *
call flavor_init (flv, (/ 23 /), model)
call polarization_init_unpolarized (pol(1), flv(1))
call beam_data_init_decay (beam_data, flv, pol)
call process_setup_beams (process, beam_data, 0)
call process_connect_strfun (process)
call process_setup_subevt (process)
print *
print *, "* Phase space setup"
call openmp_set_num_threads_verbose (1)
call process_setup_phase_space (process, rebuild_phs, &
    os_data, phs_par, mapping_defaults, filename_out=var_str("zqq.phs"), &
    vis_channels = .false.)
call process_init_vamp_history (process, 1)
print *
print *, "*** Test integration"
print *, "* Grids setup"
grid_parameters%stratified = .false.
call process_setup_grids (process, grid_parameters, calls=9)
print *
print *, "* 1 iteration with minimal number of calls"
call process_results_write_header (process)
do i = 1, 1
    discard_integrals = i==1
    adapt_grids = .true.
    adapt_weights = .true.
    print_current = .true.
    call process_integrate (process, rng, grid_parameters, &
        1, 1, 1, 9, &
        discard_integrals, adapt_grids, adapt_weights, print_current, &
        time_estimate)
end do
call process_results_write_footer (process)
call process_write_time_estimate (process)
print *
print *, "* Process written to 'fort.62'"
call process_write (process, 62)
print *
print *, "*** Event generation"
call process_setup_event_generation (process)
print *
print *, "* Generate weighted event"
call process_generate_weighted_event (process, rng, weight)
print *
print *, "* Process written to 'fort.63'"
call process_write (process, 63)

```

```

print *, "weight =", weight
print *
print *, "* Generate unweighted event"
call process_generate_unweighted_event (process, rng, weight)
print *
print *, "* Process written to 'fort.64'"
call process_write (process, 64)
print *, "excess weight =", weight
end subroutine process_test2

```

Test scattering process: ee- γ nnh (colorless)

(Processes: procedures)+≡

```

subroutine process_test3 (prc_lib, os_data, model, var_list)
  type(process_library_t), intent(inout) :: prc_lib
  type(model_t), intent(in), target :: model
  type(var_list_t), intent(in), target :: var_list
  type(process_t), pointer :: process
  type(os_data_t), intent(inout) :: os_data
  type(phs_parameters_t) :: phs_par
  type(mapping_defaults_t) :: mapping_defaults
  type(flavor_t), dimension(2) :: flv
  type(polarization_t), dimension(2) :: pol
  type(beam_data_t) :: beam_data
  type(grid_parameters_t) :: grid_parameters
  real(default), dimension(:), allocatable :: x
  logical :: time_estimate = .true.
  integer :: channel
  logical :: ok
  integer :: i
  type(tao_random_state) :: rng
  logical :: rebuild_phs = .true.
  logical :: discard_integrals, adapt_grids, adapt_weights, print_current
  print *, "*** Test scattering process e+ e- -> nu nubar H ***"
  print *
  print *, "* Initialization"
  call tao_random_create (rng, 0)
  call process_store_init_process &
    (process, prc_lib, var_str ("nnh"), model, &
     var_list, use_beams = .true.)
  print *, " Process ID = ", char (process%id)
  print *
  print *, "* Beam/strfun setup"
  print *
  call flavor_init (flv, (/ 11, -11 /), model)
  call polarization_init_unpolarized (pol(1), flv(1))
  call polarization_init_unpolarized (pol(2), flv(2))
  call beam_data_init_sqrt (beam_data, 500._default, flv, pol)
  call process_setup_beams (process, beam_data, 0)
  call process_connect_strfun (process)
  call process_setup_subvt (process)
  print *
  print *, "* Phase space setup"
  call openmp_set_num_threads_verbose (1)
  call process_setup_phase_space (process, rebuild_phs, &

```

```

        os_data, phs_par, mapping_defaults, filename_out=var_str("nnh.phs"), &
        vis_channels = .false.)
call process_init_vamp_history (process, 8)
print *
print *, "* Kinematics setup"
allocate (x (process_get_n_parameters (process)))
do i = 1, size (x)
    x(i) = (i - 0.5_default) * (1._default / size (x))
end do
channel = 1
call process_set_kinematics (process, x, channel, ok)
print *
print *, "* Process written to 'fort.70'"
call process_write (process, 70)
print *
print *, "*** Test process evaluation"
call process_evaluate (process)
print *
print *, "* Process written to 'fort.71'"
call process_write (process, 71)
print *
print *, "*** Test integration"
print *, "* Grids setup"
call process_setup_grids (process, grid_parameters, calls=20000)
print *
print *, "* 5 + 3 iterations"
call process_results_write_header (process)
do i = 1, 5
    discard_integrals = i==1
    adapt_grids = .true.
    adapt_weights = .true.
    print_current = .true.
    call process_integrate (process, rng, grid_parameters, &
        1, 1, 1, 10000, &
        discard_integrals, adapt_grids, adapt_weights, print_current, &
        time_estimate)
end do
call process_results_write_current_average (process)
call process_integrate (process, rng, grid_parameters, &
    2, 1, 3, 20000, .true., .false., .false., .true., .true.)
call process_results_write_footer (process)
call process_write_time_estimate (process)
print *
print *, "* Process written to 'fort.72'"
call process_write (process, 72)
end subroutine process_test3

```

Test scattering process: $gg \rightarrow uu$.

$\langle \text{Processes: procedures} \rangle + \equiv$

```

subroutine process_test4 (prc_lib, os_data, model, var_list)
    type(process_library_t), intent(inout) :: prc_lib
    type(model_t), intent(in), target :: model
    type(var_list_t), intent(in), target :: var_list
    type(process_t), pointer :: process

```

```

type(os_data_t), intent(inout) :: os_data
type(phs_parameters_t) :: phs_par
type(mapping_defaults_t) :: mapping_defaults
type(flavor_t), dimension(2) :: flv
type(polarization_t), dimension(2) :: pol
type(beam_data_t) :: beam_data
type(pdf_builtin_status_t) :: pdf_builtin_status
type(pdf_builtin_data_t), dimension(2) :: data
type(stream_t), target :: stream
type(parse_tree_t) :: parse_tree
type(grid_parameters_t) :: grid_parameters
logical :: time_estimate = .true.
integer :: i
type(tao_random_state) :: rng
logical :: rebuild_phs = .true.
print *, "*** Test process setup for g g -> u ubar ***"
print *
print *, "* Initialization"
call tao_random_create (rng, 0)
call process_store_init_process &
    (process, prc_lib, var_str ("gguu"), model, &
    var_list, use_beams = .true.)
print *, " Process ID = ", char (process%id)
print *
print *, "* Beam/strfun setup"
print *
!    call flavor_init (flv, (/ 21, 21 /), model)
call flavor_init (flv, (/ PROTON, PROTON /), model)
call polarization_init_unpolarized (pol(1), flv(1))
call polarization_init_unpolarized (pol(2), flv(2))
call beam_data_init_sqrts (beam_data, 14000._default, flv, pol)
!    call process_setup_beams (process, beam_data, 0, 0)
call process_setup_beams (process, beam_data, 2)
call pdf_builtin_init (data(1), pdf_builtin_status, model, flv(1), name = &
    var_str("cteq6l"), path = os_data%pdf_builtin_datapath)
call pdf_builtin_init (data(2), pdf_builtin_status, model, flv(2), name = &
    var_str("cteq6l"), path = os_data%pdf_builtin_datapath)
call process_set_strfun (process, 1, 1, data(1), 1)
call process_set_strfun (process, 2, 2, data(2), 1)
call process_connect_strfun (process)
call process_setup_subevt (process)
print *
print *, "* Phase space setup"
call openmp_set_num_threads_verbose (1)
call process_setup_phase_space (process, rebuild_phs, &
    os_data, phs_par, mapping_defaults, filename_out=var_str("gguu.phs"), &
    vis_channels = .false.)
call process_init_vamp_history (process, 18)
print *
print *, "* Cuts setup"
call stream_init (stream, var_str ("all Pt > 50 GeV [u:d:U:D]"))
call parse_tree_init_lexpr (parse_tree, stream, .true.)
call process_setup_cuts (process, parse_tree_get_root_ptr (parse_tree))
call parse_tree_final (parse_tree)

```

```

call stream_final (stream)
print *
print *, "* Scale setup"
call stream_init (stream, var_str ("1 TeV"))
call parse_tree_init_expr (parse_tree, stream, .true.)
call process_setup_fac_scale (process, parse_tree_get_root_ptr (parse_tree))
call parse_tree_final (parse_tree)
call stream_final (stream)
print *
print *, "*** Test integration"
print *, "* Grids setup"
call process_setup_grids (process, grid_parameters, calls=10000)
print *
print *, "* 5 + 3 iterations"
call process_results_write_header (process)
do i = 1, 5
    call process_integrate (process, rng, grid_parameters, &
        1, 1, 1, 50000, i==1, .true., i>2, .true., .true.)
end do
call process_results_write_current_average (process)
call process_integrate (process, rng, grid_parameters, &
    2, 1, 3, 50000, .true., .false., .true., .true., .true.)
call process_results_write_footer (process)
call process_write_time_estimate (process)
print *
print *, "* Process written to 'fort.90'"
call process_write (process, 90)
end subroutine process_test4

```

13.4 Decays

Particles can be marked as unstable, so during event generation (cascade) decays are applied to them. For each decay mode, we temporarily use the corresponding process entry in the process store, which is filled and evaluated and connected to the mother process.

```

<decays.f90>≡
<File header>

module decays

<Use kinds>
    use kinds, only: double !NODEP!
<Use strings>
    use limits, only: MAX_TRIES_FOR_DECAY_CHAIN !NODEP!
<Use file utils>
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use tao_random_numbers !NODEP!
    use md5
    use models
    use flavors

```

```

    use quantum_numbers
    use processes
    use interactions
    use evaluators

    <Standard module head>

    <Decays: public>

    <Decays: types>

    <Decays: variables>

contains

    <Decays: procedures>

end module decays

```

13.4.1 Decay configuration

We store the decay properties of a particular particle. First, we need an array of process pointers. For the final-state particles, we need to store the fact whether they are stable themselves and, if not, their decay properties. This is necessary because it determines the quantum numbers we need to keep for the decay products in event generation.

```

<Decays: types>≡
    type :: decay_channel_t
    private
        type(process_t), pointer :: process => null ()
        real(default) :: br = 0
        type(flavor_t), dimension(:), allocatable :: unstable_products
        logical, dimension(:), allocatable :: isotropic
        logical, dimension(:), allocatable :: diagonal
    end type decay_channel_t

```

Decay configurations are stored in a list:

```

<Decays: public>≡
    public :: decay_configuration_t

<Decays: types>+≡
    type :: decay_configuration_t
    private
        type(flavor_t) :: flv
        type(model_t), pointer :: model => null ()
        real(default) :: width = 0
        logical :: isotropic = .false.
        logical :: diagonal = .false.
        type(decay_channel_t), dimension(:), allocatable :: channel
        type(string_t), dimension(:), allocatable :: process_id
        type(decay_configuration_t), pointer :: next => null ()
    end type decay_configuration_t

```


Allocate the array for a known number of decay channels.

<Decays: procedures>+≡

```
subroutine decay_configuration_init &
  (conf, flv, model, width, n_channels, isotropic, diagonal)
  type(decay_configuration_t), intent(out) :: conf
  type(flavor_t), intent(in) :: flv
  type(model_t), intent(in), target :: model
  real(default), intent(in) :: width
  integer, intent(in) :: n_channels
  logical, intent(in) :: isotropic, diagonal
  conf%flv = flv
  conf%model => model
  conf%width = width
  conf%isotropic = isotropic
  conf%diagonal = diagonal
  allocate (conf%channel (n_channels))
  allocate (conf%process_id (n_channels))
end subroutine decay_configuration_init
```

Set/retrieve the pointer to the next configuration in list:

<Decays: procedures>+≡

```
function decay_configuration_get_next_ptr (conf) result (ptr)
  type(decay_configuration_t), pointer :: ptr
  type(decay_configuration_t), intent(in) :: conf
  ptr => conf%next
end function decay_configuration_get_next_ptr

subroutine decay_configuration_set_next_ptr (conf, ptr)
  type(decay_configuration_t), intent(inout) :: conf
  type(decay_configuration_t), pointer :: ptr
  conf%next => ptr
end subroutine decay_configuration_set_next_ptr
```

Set a single decay channel:

<Decays: public>+≡

```
public :: decay_configuration_set_channel
```

<Decays: procedures>+≡

```
subroutine decay_configuration_set_channel (conf, i, process, br)
  type(decay_configuration_t), intent(inout) :: conf
  integer, intent(in) :: i
  type(process_t), intent(in), target :: process
  real(default), intent(in) :: br
  integer :: n_unstable_products
  conf%channel(i)%process => process
  conf%channel(i)%br = br
  conf%process_id(i) = process_get_id (process)
  call process_get_unstable_products &
    (conf%channel(i)%process, conf%channel(i)%unstable_products)
  n_unstable_products = size (conf%channel(i)%unstable_products)
  if (allocated (conf%channel(i)%isotropic)) &
    deallocate (conf%channel(i)%isotropic)
  if (allocated (conf%channel(i)%diagonal)) &
```

```

        deallocate (conf%channel(i)%diagonal)
    allocate (conf%channel(i)%isotropic (n_unstable_products))
    allocate (conf%channel(i)%diagonal (n_unstable_products))
    if (n_unstable_products /= 0) then
        conf%channel(i)%isotropic = &
            flavor_decays_isotropically (conf%channel(i)%unstable_products)
        conf%channel(i)%diagonal = &
            flavor_decays_diagonal (conf%channel(i)%unstable_products)
    end if
end subroutine decay_configuration_set_channel

```

Check an existing decay configuration whether the stability of the decay products has changed. If yes, re-initialize event generation for the corresponding channel.

Do the check only if the configuration corresponds to a particle that is currently known as unstable.

(Decays: procedures)+≡

```

subroutine decay_configuration_recheck_final_state (conf, verbose)
    type(decay_configuration_t), intent(inout) :: conf
    logical, intent(in), optional :: verbose
    type(flavor_t), dimension(:), allocatable :: flv_unstable
    logical, dimension(:), allocatable :: isotropic, diagonal
    logical :: modified, verb
    integer :: u, i, n_unstable_products
    u = logfile_unit ()
    verb = .false.; if (present (verbose)) verb = verbose
    if (flavor_is_stable (conf%flv)) return
    do i = 1, size (conf%channel)
        call process_get_unstable_products &
            (conf%channel(i)%process, flv_unstable)
        n_unstable_products = size (flv_unstable)
        allocate (isotropic (n_unstable_products))
        allocate (diagonal (n_unstable_products))
        isotropic = flavor_decays_isotropically (flv_unstable)
        diagonal = flavor_decays_diagonal (flv_unstable)
        if (n_unstable_products == size (conf%channel(i)%unstable_products)) &
            then
            modified = &
                any (flv_unstable /= conf%channel(i)%unstable_products) &
                .or. &
                any (isotropic .neqv. conf%channel(i)%isotropic) &
                .or. &
                any (diagonal .neqv. conf%channel(i)%diagonal)
        else
            modified = .true.
            deallocate (conf%channel(i)%unstable_products)
            deallocate (conf%channel(i)%isotropic)
            deallocate (conf%channel(i)%diagonal)
            allocate (conf%channel(i)%unstable_products (n_unstable_products))
            allocate (conf%channel(i)%isotropic (n_unstable_products))
            allocate (conf%channel(i)%diagonal (n_unstable_products))
        end if
        if (modified) then

```

```

        conf%channel(i)%unstable_products = flv_unstable
        conf%channel(i)%isotropic = isotropic
        conf%channel(i)%diagonal = diagonal
        call process_setup_event_generation (conf%channel(i)%process, &
            qn_mask_in = new_quantum_numbers_mask (.false., .false., &
                mask_h = conf%isotropic, mask_hd = conf%diagonal))
        if (verb) then
            call msg_message ("Further modified decay configuration:")
            call decay_configuration_write (conf)
            call decay_configuration_write (conf, u)
        end if
    end if
    deallocate (flv_unstable, isotropic, diagonal)
end do
end subroutine decay_configuration_recheck_final_state

```

Check an existing decay configuration whether it contains any of a given list of processes, which have been updated since the decay configuration was stored. If yes, re-initialize event generation for the updated processes, recalculate the branching ratios and report the updated decay configuration.

We assume that the record has been initialized before.

(Decays: procedures)+≡

```

subroutine decay_configuration_update (conf, process_id, verbose)
    type(decay_configuration_t), intent(inout) :: conf
    type(string_t), dimension(:), intent(in) :: process_id
    logical, intent(in), optional :: verbose
    logical, dimension(:), allocatable :: updated
    real(default), dimension(:), allocatable :: integral, br
    real(default) :: integral_sum
    integer :: u, i, j, n_channels
    type(process_t), pointer :: process
    logical :: verb
    u = logfile_unit ()
    verb = .false.; if (present (verbose)) verb = verbose
    if (flavor_is_stable (conf%flv)) return
    n_channels = size (conf%channel)
    allocate (updated (n_channels))
    allocate (integral (n_channels), br (n_channels))
    updated = .false.
    do j = 1, n_channels
        do i = 1, size (process_id)
            if (process_id(i) == conf%process_id(j)) then
                updated(j) = .true.
            end if
        end do
    end do
    if (any (updated)) then
        do j = 1, n_channels
            process => conf%channel(j)%process
            integral(j) = process_get_integral (process)
            if (integral(j) < 0) then
                call msg_fatal ("Integral of process '" &
                    // char (process_get_id (process)) // "' is negative")
            end if
        end do
    end if
end subroutine

```

```

        end if
        if (updated(j)) then
            call process_setup_event_generation (process, &
                qn_mask_in = new_quantum_numbers_mask (.false., .false., &
                    mask_h = conf%isotropic, mask_hd = conf%diagonal))
        end if
    end do
    integral_sum = sum (integral)
    if (integral_sum /= 0) then
        br = integral / integral_sum
    else
        call msg_fatal ("Unstable particle: Computed total width vanishes")
        br = 0
    end if
    conf%width = integral_sum
    conf%channel%br = br
    if (verb) then
        call msg_message ("Updated decay configuration:")
        call decay_configuration_write (conf)
        call decay_configuration_write (conf, u)
    end if
end if
end if
end subroutine decay_configuration_update

```

Output. Note that either no channel or all channels have to be defined.

<Decays: public>+≡

```
public :: decay_configuration_write
```

<Decays: procedures>+≡

```

subroutine decay_configuration_write (conf, unit)
    type(decay_configuration_t), intent(in) :: conf
    integer, intent(in), optional :: unit
    character(12) :: fmt
    integer :: n_channels, proc_id_len
    integer :: u, i, j
    u = output_unit (unit); if (u < 0) return
    write (u, "(A)") "Decay configuration of particle '" &
        // char (flavor_get_name (conf%flv)) // "' in model '" &
        // char (model_get_name (conf%model)) // "':"
    write (u, *) " Computed total width = ", conf%width, " GeV"
    if (conf%isotropic) then
        write (u, *) " Isotropic decays requested for simulation."
    end if
    if (conf%diagonal) then
        write (u, *) " Diagonal density matrix in decays " &
            // "requested for simulation."
    end if
    write (u, *) " Branching ratios:"
    n_channels = decay_configuration_get_n_channels (conf)
    if (n_channels /= 0) then
        proc_id_len = maxval (len (conf%process_id))
        do i = 1, n_channels
            write (u, "(F12.7,1x,A)", advance="no") 100 * conf%channel(i)%br, "%"
            write (fmt, "(2x,A,I0,A)") "(4x,A", proc_id_len + 1, ")"
        end do
    end if
end subroutine

```

```

        write (u, fmt, advance="no") char (conf%process_id(i))
        if (allocated (conf%channel(i)%unstable_products)) then
            if (size (conf%channel(i)%unstable_products) /= 0) then
                write (u, "(1x,A)", advance="no") "    -> unstable:"
                do j = 1, size (conf%channel(i)%unstable_products)
                    write (u, "(1x,A)", advance="no") char (flavor_get_name &
                        (conf%channel(i)%unstable_products(j)))
                    if (conf%channel(i)%isotropic(j)) then
                        write (u, "(A)", advance="no") "[I]"
                    else if (conf%channel(i)%diagonal(j)) then
                        write (u, "(A)", advance="no") "[D]"
                    end if
                end do
            end if
        end if
        write (u, *)
    end do
else
    write (u, *) " [undefined]"
end if
end subroutine decay_configuration_write

```

Return the number of decay channels:

```

<Decays: public>+≡
    public :: decay_configuration_get_n_channels

<Decays: procedures>+≡
    function decay_configuration_get_n_channels (conf) result (n)
        integer :: n
        type(decay_configuration_t), intent(in) :: conf
        if (allocated (conf%channel)) then
            n = size (conf%channel)
        else
            n = 0
        end if
    end function decay_configuration_get_n_channels

```

Select a decay channel, using the random-number generator. Return the process pointer. Note that the sum of branching ratios must be unity. (As a fallback, the last channel is selected if the sum of ratios is less than unity.)

```

<Decays: procedures>+≡
    function decay_configuration_select_channel (conf, rng) result (channel)
        integer :: channel
        type(decay_configuration_t), intent(in) :: conf
        type(tao_random_state), intent(inout) :: rng
        real(default) :: x
        real(default) :: x_sum
        call tao_random_number (rng, x)
        x_sum = 0
        do channel = 1, size (conf%channel)
            x_sum = x_sum + conf%channel(channel)%br
            if (x < x_sum) return
        end do
    end function decay_configuration_select_channel

```

```

        channel = size (conf%channel)
    end function decay_configuration_select_channel

```

Return a pointer to a specified decay process.

```

<Decays: procedures>+≡
    function decay_configuration_get_process_ptr (conf, channel) &
        result (process)
        type(process_t), pointer :: process
        type(decay_configuration_t), intent(in) :: conf
        integer, intent(in) :: channel
        process => conf%channel(channel)%process
    end function decay_configuration_get_process_ptr

```

13.4.2 List of decay configurations

Similar to the list of active processes (`process_store`), we maintain a list of unstable particles and their decay properties.

```

<Decays: types>+≡
    type :: decay_store_t
    private
    integer :: n = 0
    type(decay_configuration_t), pointer :: first => null ()
    type(decay_configuration_t), pointer :: last => null ()
    end type decay_store_t

```

```

<Decays: variables>≡
    type(decay_store_t), save :: store

```

Finalize.

```

<Decays: public>+≡
    public :: decay_store_final

<Decays: procedures>+≡
    subroutine decay_store_final ()
        type(decay_configuration_t), pointer :: current
        store%last => null ()
        do while (associated (store%first))
            current => store%first
            store%first => current%next
            deallocate (current)
        end do
        store%n = 0
    end subroutine decay_store_final

```

Output.

```

<Decays: public>+≡
    public :: decay_store_write

```

```

<Decays: procedures>+≡
subroutine decay_store_write (unit)
  integer, intent(in), optional :: unit
  type(decay_configuration_t), pointer :: decay
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, "(A)") "Decay configuration for unstable particles:"
  decay => store%first
  do while (associated (decay))
    if (.not. flavor_is_stable (decay%flv)) &
      call decay_configuration_write (decay, unit)
    decay => decay%next
  end do
end subroutine decay_store_write

```

Retrieve the MD5 sum of the decay store, if there is any decay assigned.

```

<Decays: public>+≡
public :: decay_store_get_md5sum

<Decays: procedures>+≡
function decay_store_get_md5sum () result (md5sum_decays)
  character(32) :: md5sum_decays
  integer :: u
  if (associated (store%first)) then
    u = free_unit ()
    open (u, status="scratch")
    call decay_store_write (u)
    rewind (u)
    md5sum_decays = md5sum (u)
  else
    md5sum_decays = ""
  end if
end function decay_store_get_md5sum

```

Append a new entry for an unstable particle. If a decay exists already, it is overwritten. Return a pointer to the new decay configuration.

```

<Decays: public>+≡
public :: decay_store_append_decay

<Decays: procedures>+≡
subroutine decay_store_append_decay &
  (flv, model, width, n_channels, isotropic, diagonal, decay)
  type(flavor_t), intent(in) :: flv
  type(model_t), intent(in), target :: model
  real(default), intent(in) :: width
  integer, intent(in) :: n_channels
  logical, intent(in) :: isotropic, diagonal
  type(decay_configuration_t), pointer :: decay
  type(decay_configuration_t), pointer :: next_decay
  decay => store%first
  do while (associated (decay))
    if (decay%flv == flv) then
      next_decay => decay_configuration_get_next_ptr (decay)
      call decay_configuration_init &

```

```

        (decay, flv, model, width, n_channels, isotropic, diagonal)
        call decay_configuration_set_next_ptr (decay, next_decay)
        return
    end if
    decay => decay%next
end do
allocate (decay)
call decay_configuration_init &
    (decay, flv, model, width, n_channels, isotropic, diagonal)
if (associated (store%first)) then
    store%last%next => decay
else
    store%first => decay
end if
store%last => decay
end subroutine decay_store_append_decay

```

Return a pointer to the decay configuration for a particular unstable particle.

```

<Decays: procedures>+≡
function decay_store_get_decay_configuration_ptr (flv) result (config)
    type(decay_configuration_t), pointer :: config
    type(flavor_t), intent(in) :: flv
    config => store%first
    SCAN_PARTICLES: do while (associated (config))
        if (config%flv == flv) exit SCAN_PARTICLES
        config => config%next
    end do SCAN_PARTICLES
end function decay_store_get_decay_configuration_ptr

```

Recheck all decay configurations whether the stability of the final state has changed. If yes, re-initialize event generation for the corresponding decay process.

This should be executed anytime the stability of a particle has changed.

```

<Decays: public>+≡
public :: decay_store_recheck_final_state

<Decays: procedures>+≡
subroutine decay_store_recheck_final_state (verbose)
    logical, intent(in), optional :: verbose
    logical :: modified
    type(decay_configuration_t), pointer :: config
    config => store%first
    do while (associated (config))
        call decay_configuration_recheck_final_state (config, verbose)
        config => config%next
    end do
end subroutine decay_store_recheck_final_state

```

Update all entries in the decay store which contain a process that is in the specified list (of processes that have been recalculated).

```

<Decays: public>+≡
public :: decay_store_update

```



```

<Decays: procedures>+≡
  subroutine decay_store_update (process_id, verbose)
    type(string_t), dimension(:), intent(in) :: process_id
    logical, intent(in), optional :: verbose
    type(decay_configuration_t), pointer :: conf
    conf => store%first
    do while (associated (conf))
      call decay_configuration_update (conf, process_id, verbose)
      conf => conf%next
    end do
  end subroutine decay_store_update

```

13.4.3 Decays

The decay object contains a pointer to the decay process, evaluators that hold the product of production and decay, and a pointer to the next decay node (which holds all possible subsequent decays).

```

<Decays: types>+≡
  type :: decay_t
  private
  logical :: initialized = .false.
  type(process_t), pointer :: process => null ()
  type(evaluator_t) :: eval_sqme
  type(evaluator_t) :: eval_flows
  type(decay_node_t), pointer :: next_node => null ()
end type decay_t

```

Initialize the decay with a certain process, and use this together with the production evaluators to initialize product evaluators.

```

<Decays: procedures>+≡
  subroutine decay_init (decay, process, eval_sqme, eval_flows, i)
    type(decay_t), intent(out), target :: decay
    type(process_t), intent(inout), target :: process
    type(evaluator_t), intent(in), target :: eval_sqme, eval_flows
    integer, intent(in) :: i
    type(interaction_t), pointer :: prc_int
    type(evaluator_t), pointer :: prc_eval_sqme, prc_eval_flows
    integer :: n_tot
    logical, dimension(:), allocatable :: ignore_hel
    type(quantum_numbers_mask_t), dimension(:), allocatable :: &
      mask_hel, mask_sqme, mask_flows
    type(quantum_numbers_mask_t) :: mask_conn
    call process_request_copy (process, decay%process)
    call process_mark_as_cascade_decay (decay%process)
    call process_setup_cuts (decay%process)
    call process_setup_weight (decay%process)
    call process_setup_scale (decay%process)
    call process_setup_fac_scale (decay%process)
    call process_setup_ren_scale (decay%process)
    prc_int => process_get_hi_int_ptr (decay%process)
    prc_eval_sqme => process_get_hi_eval_sqme_ptr (decay%process)

```

```

prc_eval_flows => process_get_hi_eval_flows_ptr (decay%process)
n_tot = evaluator_get_n_tot (prc_eval_sqme)
if (n_tot < 3) then
  call msg_bug (arr = &
    ("Initialization fails for decay '" &
    // process_get_id (decay%process) // "':", &
    var_str ("Event generation not set up properly.") &
!   var_str ("(Missing 'unstable' command after integration?)" &
    /))
end if
allocate (ignore_hel (n_tot))
ignore_hel(1) = .true.
ignore_hel(2:) = .false.
allocate (mask_hel (n_tot), mask_sqme (n_tot), mask_flows (n_tot))
call quantum_numbers_mask_set_helicity (mask_hel, ignore_hel)
mask_sqme = evaluator_get_mask (prc_eval_sqme) .or. mask_hel
mask_flows = evaluator_get_mask (prc_eval_flows) .or. mask_hel
mask_conn = new_quantum_numbers_mask (.false., .false., .true.)
call evaluator_set_source_link (prc_eval_sqme, 1, eval_sqme, i)
call evaluator_set_source_link (prc_eval_flows, 1, eval_flows, i)
call evaluator_init_product (decay%eval_sqme, &
  eval_sqme, prc_eval_sqme, mask_conn, &
  connections_are_resonant=.true.)
call evaluator_init_product (decay%eval_flows, &
  eval_flows, prc_eval_flows, mask_conn, &
  connections_are_resonant=.true.)
call evaluator_set_source_link (prc_eval_sqme, 1, prc_int, 1)
call evaluator_set_source_link (prc_eval_flows, 1, prc_int, 1)
allocate (decay%next_node)
decay%initialized = .true.
end subroutine decay_init

```

Finalizer: Delete the evaluators. Do not delete the process copy yet.

```

<Decays: procedures>+≡
recursive subroutine decay_final (decay)
  type(decay_t), intent(inout) :: decay
  if (decay%initialized) then
    if (associated (decay%next_node)) &
      call decay_node_final (decay%next_node)
    call evaluator_final (decay%eval_sqme)
    call evaluator_final (decay%eval_flows)
  end if
end subroutine decay_final

```

Output.

```

<Decays: procedures>+≡
subroutine decay_write (decay, unit)
  type(decay_t), intent(in) :: decay
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, "(A)") repeat ("=", 72)
  write (u, "(A)") "Decay process:"

```

```

call process_write (decay%process, unit)
write (u, "(A)") repeat ("=", 72)
write (u, "(A)") "Combined sqme including color factors " &
// "(process + decay):"
call evaluator_write (decay%eval_sqme, unit)
write (u, "(A)") repeat ("-", 72)
write (u, "(A)") "Combined color flow coefficients " &
// "(process + decay):"
call evaluator_write (decay%eval_flows, unit)
end subroutine decay_write

```

Given preconfigured evaluators, generate an event.

We generate an unweighted event for the decay process. This is isotropic in the decaying particle rest frame. To prepare spin correlation selection, we renormalize the squared matrix element by the trace. (Thus, the sum of the matrix element values is unity.)

We must tag the current process as the working copy if there is more than one. This occurs if the same decay appears more than once in a decay tree.

TODO: Any excess weight is collected (to avoid VAMP warnings) but not recorded anywhere.

<Decays: procedures>+≡

```

subroutine decay_generate (decay, rng, flv, p)
  type(decay_t), intent(inout) :: decay
  type(tao_random_state), intent(inout) :: rng
  type(flavor_t), intent(in) :: flv
  type(vector4_t), intent(in) :: p
  real(default) :: excess
  type(evaluator_t), pointer :: process_eval_sqme
  call process_set_beam_momenta (decay%process, (/ p /))
  call process_tag_as_working_copy (decay%process)
  call process_generate_unweighted_event (decay%process, rng, excess=excess)
  process_eval_sqme => process_get_eval_sqme_ptr (decay%process)
  call evaluator_normalize_by_trace (process_eval_sqme)
  call evaluator_receive_momenta (decay%eval_sqme)
  call evaluator_receive_momenta (decay%eval_flows)
  call evaluator_evaluate (decay%eval_sqme)
  call evaluator_evaluate (decay%eval_flows)
end subroutine decay_generate

```

13.4.4 Decay trees

A decay tree is created during event generation. Each node holds the possible decays as branches, together with the decay configuration which is used to select a branch for a particular event. Whenever a branch is selected for the first time, it is initialized with the appropriate evaluators, which are then kept for later use.

<Decays: types>+≡

```

type :: decay_node_t
  private
  type(decay_configuration_t), pointer :: configuration => null ()
  integer :: current_channel = 0

```

```

        type(decay_t), dimension(:), allocatable :: decay
    end type decay_node_t

```

Initializer:

```

<Decays: procedures>+≡
    subroutine decay_node_init (node, flv)
        type(decay_node_t), intent(out) :: node
        type(flavor_t), intent(in) :: flv
        node%configuration => decay_store_get_decay_configuration_ptr (flv)
        if (associated (node%configuration)) then
            allocate (node%decay &
                (decay_configuration_get_n_channels (node%configuration)))
        else
            call msg_bug ("Particle '" // char (flavor_get_name (flv)) &
                // "' : Missing decay configuration")
        end if
    end subroutine decay_node_init

```

Recursive finalizer:

```

<Decays: procedures>+≡
    recursive subroutine decay_node_final (node)
        type(decay_node_t), intent(inout) :: node
        integer :: i
        if (allocated (node%decay)) then
            do i = 1, size (node%decay)
                call decay_final (node%decay(i))
            end do
            deallocate (node%decay)
        end if
    end subroutine decay_node_final

```

Write the currently selected decay:

```

<Decays: procedures>+≡
    subroutine decay_node_write (node, unit)
        type(decay_node_t), intent(in) :: node
        integer, intent(in), optional :: unit
        integer :: channel, u
        u = output_unit (unit)
        write (u, "(A)") "|" // repeat ("=", 79)
        if (associated (node%configuration)) then
            call decay_configuration_write (node%configuration, unit)
            channel = node%current_channel
            if (channel /= 0) then
                write (u, "(1x,A)", advance="no") "Decay node: "
                write (u, *) "current channel = ", channel
                call decay_write (node%decay(channel), unit)
            else
                write (u, *) "Decay node: [no channel selected]"
            end if
        else
            write (u, *) "Decay configuration: [undefined]"
        end if
    end subroutine decay_node_write

```

```
end subroutine decay_node_write
```

Return a pointer to the currently selected decay, or null if absent:

```
<Decays: procedures>+≡
function decay_node_get_next_ptr (node) result (ptr)
  type(decay_node_t), pointer :: ptr
  type(decay_node_t), intent(in) :: node
  if (node%current_channel /= 0) then
    ptr => node%decay(node%current_channel)%next_node
  else
    ptr => null ()
  end if
end function decay_node_get_next_ptr
```

The decay tree holds references to the production process as well as pointers to the final evaluators.

```
<Decays: public>+≡
public :: decay_tree_t

<Decays: types>+≡
type :: decay_tree_t
  private
  integer :: tries = 0
  real(default) :: acceptance_probability = 0
  type(process_t), pointer :: hard_process => null ()
  type(evaluator_t), pointer :: eval_sqme_in => null ()
  type(evaluator_t), pointer :: eval_flows_in => null ()
  type(decay_node_t), pointer :: root => null ()
  type(evaluator_t), pointer :: eval_sqme => null ()
  type(evaluator_t), pointer :: eval_flows => null ()
end type decay_tree_t
```

Initialize the decay tree with a particular process and allocate the root node.

```
<Decays: public>+≡
public :: decay_tree_init

<Decays: procedures>+≡
subroutine decay_tree_init (decay_tree, process)
  type(decay_tree_t), intent(out) :: decay_tree
  type(process_t), intent(in), target :: process
  decay_tree%hard_process => process
  decay_tree%eval_sqme_in => process_get_eval_sqme_ptr (process)
  decay_tree%eval_flows_in => process_get_eval_flows_ptr (process)
  allocate (decay_tree%root)
end subroutine decay_tree_init

<Decays: public>+≡
public :: decay_tree_final

<Decays: procedures>+≡
subroutine decay_tree_final (decay_tree)
  type(decay_tree_t), intent(inout) :: decay_tree
  if (associated (decay_tree%root)) then
```

```

        call decay_node_final (decay_tree%root)
        deallocate (decay_tree%root)
    end if
end subroutine decay_tree_final

```

Output.

```

<Decays: public>+≡
    public :: decay_tree_write

<Decays: procedures>+≡
    subroutine decay_tree_write (decay_tree, unit)
        type(decay_tree_t), intent(in) :: decay_tree
        integer, intent(in), optional :: unit
        type(decay_node_t), pointer :: decay_node
        integer :: u
        u = output_unit (unit)
        write (u, "(A)") "|" // repeat ("=", 79)
        write (u, *) "Decay tree:"
        write (u, *) "   tries = ", decay_tree%tries
        write (u, *) "   acceptance probability = ", &
            decay_tree%acceptance_probability
        write (u, "(A)") "|" // repeat ("=", 79)
        write (u, "(1x,A)", advance="no") "Mother process = "
        if (associated (decay_tree%hard_process)) then
            write (u, "(A)") "" &
                // char (process_get_id (decay_tree%hard_process)) &
                // ""
        else
            write (u, "(A)") "[undefined]"
        end if
        write (u, "(A)") "|" // repeat ("=", 79)
        decay_node => decay_tree%root
        if (associated (decay_node)) then
            write (u, *) "Decay chain:"
            do while (associated (decay_node))
                call decay_node_write (decay_node, unit)
                decay_node => decay_node_get_next_ptr (decay_node)
            end do
        else
            write (u, *) "[No decays]"
        end if
        write (u, "(A)") "|" // repeat ("=", 79)
        write (u, "(1x,A)") "Evaluator: " &
            // "Color-summed including all decays"
        if (associated (decay_tree%eval_sqme)) then
            call evaluator_write (decay_tree%eval_sqme, unit)
        else
            write (u, "(A)") "[undefined]"
        end if
        write (u, "(A)") "|" // repeat ("=", 79)
        write (u, "(1x,A)") "Evaluator: " &
            // "Color flow components including all decays"
        if (associated (decay_tree%eval_flows)) then
            call evaluator_write (decay_tree%eval_flows, unit)

```

```

else
  write (u, "(A)") "[undefined]"
end if
write (u, "(A)") "|" // repeat ("=", 79)
end subroutine decay_tree_write

```

Generate a decay chain; construct the decay tree as far as necessary, otherwise reuse it.

To prepare for spin correlation selection, we renormalize the matrix elements of the parent interaction by the entry with maximum value. Normalizing all decay process appropriately (by the trace of their respective matrix elements), the (trace of the) product of the evaluators should result in a single value between zero and one. This is used as the probability for accepting the decay chain. If the chain is rejected, a new one is generated.

```

<Limits: public parameters>+≡
  integer, parameter, public :: MAX_TRIES_FOR_DECAY_CHAIN = 100000

<Decays: public>+≡
  public :: decay_tree_generate_event

<Decays: procedures>+≡
  subroutine decay_tree_generate_event (decay_tree, rng)
    type(decay_tree_t), intent(inout) :: decay_tree
    type(tao_random_state), intent(inout) :: rng
    real(default) :: x_decay
    real(default) :: x
    integer :: i
    logical :: decay_occurs
    call evaluator_normalize_by_max (decay_tree%eval_sqme_in)
    decay_occurs = .false.
    REJECTION: do i = 1, MAX_TRIES_FOR_DECAY_CHAIN
      decay_tree%tries = i
      decay_tree%eval_sqme => decay_tree%eval_sqme_in
      decay_tree%eval_flows => decay_tree%eval_flows_in
      call decay_node_generate_event (decay_tree%root, decay_occurs)
      if (decay_occurs) then
        x_decay = evaluator_sum (decay_tree%eval_sqme)
        decay_tree%acceptance_probability = x_decay
        call tao_random_number (rng, x)
        if (x <= x_decay) return
      else
        return
      end if
    end do REJECTION
    write (msg_buffer, "(A,IO,A)") "Failed to generate a decay chain " &
      // "after ", MAX_TRIES_FOR_DECAY_CHAIN, " tries"
    call msg_fatal ()
  contains
    recursive subroutine decay_node_generate_event (node, decay_occurs)
      type(decay_node_t), intent(inout), target :: node
      logical, intent(inout) :: decay_occurs
      type(flavor_t) :: flv
      type(vector4_t) :: p
      integer :: i, channel

```

```

type(process_t), pointer :: process
call evaluator_get_unstable_particle (decay_tree%eval_sqme, flv, p, i)
if (flavor_is_defined (flv)) then
  decay_occurs = .true.
  if (.not. associated (node%configuration)) &
    call decay_node_init (node, flv)
  channel = decay_configuration_select_channel (node%configuration, rng)
  node%current_channel = channel
  if (.not. node%decay(channel)%initialized) then
    process => decay_configuration_get_process_ptr &
      (node%configuration, channel)
    call decay_init (node%decay(channel), &
      process, decay_tree%eval_sqme, decay_tree%eval_flows, i)
  end if
  call decay_generate (node%decay(channel), rng, flv, p)
  decay_tree%eval_sqme => node%decay(channel)%eval_sqme
  decay_tree%eval_flows => node%decay(channel)%eval_flows
  call decay_node_generate_event &
    (node%decay(channel)%next_node, decay_occurs)
end if
end subroutine decay_node_generate_event
end subroutine decay_tree_generate_event

```

Return pointers to the final evaluators:

```

<Decays: public>+≡
  public :: decay_tree_get_eval_sqme_ptr
  public :: decay_tree_get_eval_flows_ptr

<Decays: procedures>+≡
  function decay_tree_get_eval_sqme_ptr (decay_tree) result (eval)
    type(evaluator_t), pointer :: eval
    type(decay_tree_t), intent(in), target :: decay_tree
    eval => decay_tree%eval_sqme
  end function decay_tree_get_eval_sqme_ptr

  function decay_tree_get_eval_flows_ptr (decay_tree) result (eval)
    type(evaluator_t), pointer :: eval
    type(decay_tree_t), intent(in), target :: decay_tree
    eval => decay_tree%eval_flows
  end function decay_tree_get_eval_flows_ptr

```

13.5 Events

The event record becomes relevant only after cross sections have been integrated. It gets filled by some signal process (including beam/structure functions) if an event has been successfully been generated (passing rejection).

If requested, particles in the event are subject to decay and/or showering. This is not implemented yet.

```

(events.f90)≡
  <File header>

```



```

module events

  <Use kinds>
  <Use strings>
    use limits, only: RAW_EVENT_FILE_ID_STRING !NODEP!
  <Use file utils>
    use diagnostics !NODEP!
    use tao_random_numbers !NODEP!
    use pdf_builtin !NODEP!
    use os_interface
    use lexers
    use parser
    use subevents
    use variables
    use expressions
    use models
    use flavors
    use state_matrices
    use polarizations
    use event_formats
    use hepmc_interface
    use particles
    use interactions
    use evaluators
    use process_libraries
    use beams
    use sf_lhapdf
    use mappings
    use phs_forests
    use cascades
    use processes
    use decays
    use lorentz !NODEP!
    use shower_interface
    use lorentz !NODEP!
    use ckkw_pseudo_weights_module !NODEP!
    use ckkw_matching_module !NODEP!

  <Standard module head>

  <Events: public>

  <Events: types>

  contains

  <Events: procedures>

end module events

```

13.5.1 The event type

```

<Events: public>≡
  public :: event_t

```

```

<Events: types>≡
  type :: event_t
    private
      integer :: num_proc_id = 0
      type(process_t), pointer :: process => null ()
      type(event_vars_t), pointer :: vars => null ()
      type(decay_tree_t), pointer :: decay_tree => null ()
      logical :: particle_set_exists = .false.
      logical :: is_valid = .false.
      logical :: is_vetoed = .false.
      type(particle_set_t) :: particle_set
      real(default) :: excess = 0
    end type event_t

```

The event record is initialized with a pointer to a specific “signal” process. The particle set is not (yet) initialized, this is done for each event. The event weight and squared matrix element are presented as a target, so the event record acquires a pointer to this target. The same target is available to the analysis evaluation tree.

```

<Events: public>+≡
  public :: event_init

<Events: procedures>≡
  subroutine event_init (event, process, event_vars, decay_tree)
    type(event_t), intent(out) :: event
    type(process_t), intent(in), target :: process
    type(event_vars_t), intent(in), target :: event_vars
    type(decay_tree_t), intent(in), optional, target :: decay_tree
    event%process => process
    event%vars => event_vars
    if (present (decay_tree)) event%decay_tree => decay_tree
  end subroutine event_init

```

Finalize the event: delete the particle set.

```

<Events: public>+≡
  public :: event_final

<Events: procedures>+≡
  subroutine event_final (event)
    type(event_t), intent(inout) :: event
    call particle_set_final (event%particle_set)
    event%is_valid = .false.
  end subroutine event_final

```

Output: Only the particle set is printed explicitly, unless verbose format is selected.

```

<Events: public>+≡
  public :: event_write

<Events: procedures>+≡
  subroutine event_write (event, analysis_expr, unit, verbose)
    type(event_t), intent(in) :: event
    type(eval_tree_t), intent(in), optional :: analysis_expr

```

```

integer, intent(in), optional :: unit
logical, intent(in), optional :: verbose
integer :: u
u = output_unit (unit); if (u < 0) return
write (u, *) repeat ("=", 72)
write (u, *) "Event record:"
if (.not. event%is_valid) write (u, *) " [invalid event record]"
if (associated (event%vars)) then
    call event_vars_write (event%vars, unit)
end if
if (associated (event%process)) then
    if (present (verbose)) then
        if (verbose) then
            call process_write (event%process, unit)
            if (present (analysis_expr)) then
                write (u, "(A)") "Analysis expression:"
                call eval_tree_write (analysis_expr, unit)
                write (u, "(A)") repeat ("#", 79)
            end if
            write (u, *)
        end if
    end if
else
    write (u, *) " [empty]"
end if
write (u, *) repeat ("=", 72)
if (associated (event%decay_tree)) then
    write (u, *) repeat ("=", 72)
    call decay_tree_write (event%decay_tree, unit)
end if
write (u, *) " [Process: ", char (process_get_id (event%process)), "]"
write (u, *)
call particle_set_write (event%particle_set, unit)
end subroutine event_write

```

13.5.2 Event generation

Generate a new event and transfer the resulting data to the event record.

The call to `event_factorize_process` determines whether the event is valid.

<Events: public>+≡

```
public :: event_generate
```

<Events: procedures>+≡

```

subroutine event_generate (event, rng, unweighted, &
    factorization_mode, keep_correlations, keep_virtual, os_data, &
    shower_settings)
    type(event_t), intent(inout), target :: event
    type(tao_random_state), intent(inout) :: rng
    logical, intent(in) :: unweighted
    integer, intent(in) :: factorization_mode
    logical, intent(in) :: keep_correlations, keep_virtual
    type(os_data_t), intent(in) :: os_data

```

```

!!! shower_settings should be intent(in), but the calls to ckkw_pseudo_shower_weights_init
!!! and ckkw_fake_pseudo_shower_weights force it to be declared as intent(inout)
!   type(shower_settings_t), intent(in), optional :: shower_settings
      type(shower_settings_t), intent(inout), optional :: shower_settings
      integer :: u

      event%is_vetoed = .false.
      if (unweighted) then
        call process_generate_unweighted_event &
          (event%process, rng, event%vars%excess)
        event%vars%weight = 1
      else
        call process_generate_weighted_event &
          (event%process, rng, event%vars%weight)
        event%vars%excess = 0
      end if
      event%vars%n_in = process_get_n_in (event%process)
      event%vars%n_out = process_get_n_out (event%process)
      event%vars%n_tot = process_get_n_tot (event%process)
      event%vars%sqrts = process_get_sqrts (event%process)
      event%vars%sqrts_hat = process_get_sqrts_hat (event%process)
      event%vars%sqme = process_get_sqme (event%process)
      event%vars%sqme_ref = event%vars%sqme
      if (associated (event%decay_tree)) then
        call decay_tree_generate_event (event%decay_tree, rng)
      end if
      call event_factorize_process (event, rng, &
        factorization_mode, keep_correlations, keep_virtual)
      if(event%particle_set_exists.and.present (shower_settings)) then
        call event_assure_heprup(event)

        if(shower_settings%ckkw_matching) then
          call ckkw_pseudo_shower_weights_init(shower_settings%ckkw_weights)
          call ckkw_fake_pseudo_shower_weights(shower_settings%ckkw_settings, &
            shower_settings%ckkw_weights, event%particle_set)
        end if

        call apply_shower_particle_set(event%particle_set, &
          shower_settings, &
          process_get_model_ptr(event%process), &
          os_data, &
          process_get_strfun_type(event%process), &
          process_get_strfun_set(event%process), &
          event%is_valid, event%is_vetoed)
      end if
    end subroutine event_generate

```

Generate fake ckkw weights. This can be dropped, once information from the matrix element generation is available.

<Events: public>+≡

```
public :: ckkw_fake_pseudo_shower_weights
```

<Events: procedures>+≡

```
subroutine ckkw_fake_pseudo_shower_weights(ckkw_pseudo_shower_settings, &
```

```

        ckkw_pseudo_shower_weights, particle_set)
type(ckkw_matching_settings_t), intent(inout) :: ckkw_pseudo_shower_settings
type(ckkw_pseudo_shower_weights_t), intent(inout) :: ckkw_pseudo_shower_weights
type(particle_set_t), intent(in) :: particle_set
integer :: i, j, k
integer :: n
type(vector4_t) :: momentum

ckkw_pseudo_shower_settings%alphaS = 1.0_default
ckkw_pseudo_shower_settings%Qmin = 1.0_default
ckkw_pseudo_shower_settings%n_max_jets = 3

n = 2**particle_set_get_n_tot(particle_set)
if(allocated(ckkw_pseudo_shower_weights%weights)) then
    deallocate(ckkw_pseudo_shower_weights%weights)
end if
allocate(ckkw_pseudo_shower_weights%weights(1:n))
do i=1,n
    momentum = vector4_null
    do j=1, particle_set_get_n_tot(particle_set)
        if(btest(i,j-1)) then
            momentum = momentum + particle_get_momentum(particle_set_get_particle(particle_set, j-1))
        end if
    end do
    if(momentum**1 > 0.0) then
        ckkw_pseudo_shower_weights%weights(i) = 1.0 / (momentum**2)
    end if
end do

! equally distribute the weights by type
if(allocated(ckkw_pseudo_shower_weights%weights_by_type)) then
    deallocate(ckkw_pseudo_shower_weights%weights_by_type)
end if
allocate(ckkw_pseudo_shower_weights%weights_by_type(1:n, 0:4))
do i=1,n
    do j=0,4
        ckkw_pseudo_shower_weights%weights_by_type(i,j) = 0.2 * ckkw_pseudo_shower_weights%weights(i)
    end do
end do
end subroutine ckkw_fake_pseudo_shower_weights

```

Apply decay to an existing event:

```

<Events: public>+≡
    public :: event_decay

<Events: procedures>+≡
    subroutine event_decay (event, rng, decay_tree)
        type(event_t), intent(inout) :: event
        type(tao_random_state), intent(inout) :: rng
        type(decay_tree_t), intent(in), target :: decay_tree
        if (event%is_valid) then
            call process_complete_evaluators (event%process)
            event%decay_tree => decay_tree
            call decay_tree_generate_event (event%decay_tree, rng)
        end if
    end subroutine event_decay

```

```
end subroutine event_decay
```

Transfer event data from the process record (if a decay has happened: the decay chain) to the event record, factorizing the correlated quantum-number state. We use both the colorless and the colored evaluators to determine the particle set. The factorization of the correlated state is done in one of three modes (unpolarized, definite helicity, generic one-particle density matrices); optionally, the fully correlated density matrix can also be transferred to the particle set.

The `is_valid` flag is set unless factorization fails, e.g., if the matrix element squared vanishes.

(Events: public)+≡

```
public :: event_factorize_process
```

(Events: procedures)+≡

```
subroutine event_factorize_process (event, rng, &
    factorization_mode, keep_correlations, keep_virtual)
    type(event_t), intent(inout), target :: event
    type(tao_random_state), intent(inout) :: rng
    integer, intent(in) :: factorization_mode
    logical, intent(in) :: keep_correlations, keep_virtual
    type(interaction_t), pointer :: int_sqme, int_flows
    real(default), dimension(2) :: r
    integer, dimension(:), allocatable :: beam_index
    integer, dimension(:), allocatable :: incoming_parton_index
    if (associated (event%decay_tree)) then
        int_sqme => evaluator_get_int_ptr &
            (decay_tree_get_eval_sqme_ptr (event%decay_tree))
        int_flows => evaluator_get_int_ptr &
            (decay_tree_get_eval_flows_ptr (event%decay_tree))
    else
        int_sqme => evaluator_get_int_ptr &
            (process_get_eval_sqme_ptr (event%process))
        int_flows => evaluator_get_int_ptr &
            (process_get_eval_flows_ptr (event%process))
    end if
    call tao_random_number (rng, r)
    if (interaction_get_n_in (int_sqme) /= 0) then
        call particle_set_init (event%particle_set, event%is_valid, &
            int_sqme, int_flows, factorization_mode, r, &
            keep_correlations, keep_virtual)
    else
        call particle_set_init (event%particle_set, event%is_valid, &
            int_sqme, int_flows, factorization_mode, r, &
            keep_correlations, keep_virtual, &
            n_incoming = process_get_n_in (event%process))
    end if
    call process_get_beam_index (event%process, beam_index)
    if (allocated (beam_index)) then
        call particle_set_reset_status (event%particle_set, &
            beam_index, PRT_BEAM)
    end if
    call process_get_incoming_parton_index (event%process, &
        incoming_parton_index)
```

```

    if (allocated (incoming_parton_index)) then
        call particle_set_reset_status (event%particle_set, &
            incoming_parton_index, PRT_INCOMING)
    end if
    event%particle_set_exists = .true.
end subroutine event_factorize_process

```

Do the reverse operation, as far as possible: Given a complete event, try to recover the process kinematics. Assume that the process has been initialized correctly.

```

<Events: public>+≡
    public :: event_recover_process

<Events: procedures>+≡
    subroutine event_recover_process (event)
        type(event_t), intent(inout) :: event
        call process_recover_kinematics (event%process, event%particle_set)
        call process_fill_subevt (event%process)
    end subroutine event_recover_process

```

(Re)compute the event scale, model parameters, α_s , matrix element, event weight, and user reweighting factor.

```

<Events: public>+≡
    public :: event_compute_scale
    public :: event_update_parameters
    public :: event_update_alpha_s
    public :: event_compute_sqme
    public :: event_update_weight

<Events: procedures>+≡
    subroutine event_compute_scale (event)
        type(event_t), intent(inout) :: event
        call process_compute_scale (event%process)
    end subroutine event_compute_scale

    subroutine event_update_parameters (event)
        type(event_t), intent(inout) :: event
        call process_update_parameters (event%process)
    end subroutine event_update_parameters

    subroutine event_update_alpha_s (event)
        type(event_t), intent(inout) :: event
        call process_update_alpha_s (event%process)
    end subroutine event_update_alpha_s

    subroutine event_compute_sqme (event)
        type(event_t), intent(inout) :: event
        call process_evaluate (event%process)
        event%vars%sqme = process_get_sqme (event%process)
    end subroutine event_compute_sqme

    subroutine event_update_weight (event)
        type(event_t), intent(inout) :: event
        if (event%vars%sqme_ref /= 0) then

```

```

        call event_renormalize_weight &
            (event, event%vars%sqme / event%vars%sqme_ref)
    end if
end subroutine event_update_weight

```

Determine whether an event passes selection cuts, if a selection expression is defined.

```

<Events: public>+≡
    public :: event_passes_selection

<Events: procedures>+≡
    function event_passes_selection (event, subevt, selection_expr) result (flag)
        logical :: flag
        type(event_t), intent(inout), target :: event
        type(subevt_t), intent(inout), target :: subevt
        type(eval_tree_t), intent(inout), target :: selection_expr
        real(default) :: factor
        if (event%is_valid .and. eval_tree_is_defined (selection_expr)) then
            call particle_set_to_subevt (event%particle_set, subevt)
            call eval_tree_evaluate (selection_expr)
            flag = eval_tree_get_log (selection_expr)
        else
            flag = .true.
        end if
    end function event_passes_selection

```

Renormalize the event weight by some factor

```

<Events: public>+≡
    public :: event_renormalize_weight

<Events: procedures>+≡
    subroutine event_renormalize_weight (event, factor)
        type(event_t), intent(inout) :: event
        real(default), intent(in) :: factor
        event%vars%weight = event%vars%weight * factor
    end subroutine event_renormalize_weight

```

Reweight the event, if a reweighting expression is defined.

```

<Events: public>+≡
    public :: event_reweight

<Events: procedures>+≡
    subroutine event_reweight (event, subevt, reweight_expr)
        type(event_t), intent(inout), target :: event
        type(subevt_t), intent(inout), target :: subevt
        type(eval_tree_t), intent(inout), target :: reweight_expr
        real(default) :: factor
        if (event%is_valid .and. eval_tree_is_defined (reweight_expr)) then
            call particle_set_to_subevt (event%particle_set, subevt)
            call eval_tree_evaluate (reweight_expr)
            factor = eval_tree_get_real (reweight_expr)
            call event_renormalize_weight (event, factor)
        end if
    end subroutine event_reweight

```



```
end subroutine event_reweight
```

Analyze an event. The `subevt` object is used as a messenger object to store the event particle data; the analysis expression has to be initialized before with reference to this object. The analysis results are stored as side-effect operations.

```
<Events: public>+≡
  public :: event_do_analysis

<Events: procedures>+≡
  subroutine event_do_analysis (event, subevt, analysis_expr)
    type(event_t), intent(inout), target :: event
    type(subevt_t), intent(inout), target :: subevt
    type(eval_tree_t), intent(inout), target :: analysis_expr
    if (event%is_valid .and. eval_tree_is_defined (analysis_expr)) then
      call particle_set_to_subevt (event%particle_set, subevt)
      call eval_tree_evaluate (analysis_expr)
    end if
  end subroutine event_do_analysis
```

Delete any previous contents of the particle set.

```
<Events: procedures>+≡
  subroutine event_discard_particle_set (event)
    type(event_t), intent(inout), target :: event
    if (event%particle_set_exists) then
      call particle_set_final (event%particle_set)
      event%particle_set_exists = .false.
    end if
  end subroutine event_discard_particle_set
```

13.5.3 Contents

```
<Events: public>+≡
  public :: event_is_valid

<Events: procedures>+≡
  function event_is_valid (event) result (flag)
    logical :: flag
    type(event_t), intent(in) :: event
    flag = event%is_valid
  end function event_is_valid

<Events: public>+≡
  public :: event_is_vetoed

<Events: procedures>+≡
  function event_is_vetoed (event) result (flag)
    logical :: flag
    type(event_t), intent(in) :: event
    flag = event%is_vetoed
  end function event_is_vetoed
```

13.5.4 Binary I/O

Read/write the particle set including the associated state matrix from/to an unformatted file. This can be used to re-read events generated in a previous run.

Version 2 contains a WHIZARD ID string as header.

Version 3 contains `sqrts_hat` in the event-vars record.

```
<Limits: public parameters>+≡
  character(*), parameter, public :: &
    RAW_EVENT_FILE_ID_STRING = "WHIZARD raw event file"
```

Collect the MD5 sums in a transparent container:

```
<Events: public>+≡
  public :: md5sum_events_t

<Events: types>+≡
  type :: md5sum_events_t
    character(32), dimension(:), allocatable :: process
    character(32), dimension(:), allocatable :: parameters
    character(32), dimension(:), allocatable :: results
    character(32), dimension(:), allocatable :: polarized
    character(32) :: decays = ""
    character(32) :: simulation = ""
  end type md5sum_events_t
```

Check just the event-file format. Return true if the ID string matches, otherwise return false.

```
<Events: public>+≡
  public :: is_raw_event_file

<Events: procedures>+≡
  function is_raw_event_file (unit) result (flag)
    logical :: flag
    integer, intent(in) :: unit
    character(len=len(RAW_EVENT_FILE_ID_STRING)) :: id_string
    integer :: iostat
    read (unit, iostat=iostat) id_string
    if (iostat /= 0) then
      flag = .false.
    else if (id_string /= RAW_EVENT_FILE_ID_STRING) then
      flag = .false.
    else
      flag = .true.
    end if
  end function is_raw_event_file
```

Write and read the header including the MD5 sum info.

```
<Events: public>+≡
  public :: raw_event_file_write_header
  public :: raw_event_file_read_header

<Events: procedures>+≡
  subroutine raw_event_file_write_header (unit, md5sum, version)
    integer, intent(in) :: unit
```

```

type(md5sum_events_t), intent(in) :: md5sum
integer, intent(in) :: version
write (unit) RAW_EVENT_FILE_ID_STRING
write (unit) version
write (unit) size (md5sum%/process)
write (unit) md5sum%/process
write (unit) md5sum%/parameters
write (unit) md5sum%/results
write (unit) md5sum%/polarized
write (unit) md5sum%/decays
write (unit) md5sum%/simulation
end subroutine raw_event_file_write_header

subroutine raw_event_file_read_header &
  (unit, rescan, check, md5sum, version, ok, iostat)
integer, intent(in) :: unit
logical, intent(in) :: rescan, check
type(md5sum_events_t), intent(in) :: md5sum
integer, intent(in) :: version
logical, intent(out) :: ok
integer, intent(out), optional :: iostat
character(len=len(RAW_EVENT_FILE_ID_STRING)) :: id_string
integer :: file_version, n
character(32), dimension(:), allocatable :: md5sum_array
character(32) :: md5sum_single
logical :: unweighted
ok = .false.
read (unit, iostat=iostat) id_string
if (check .and. id_string /= RAW_EVENT_FILE_ID_STRING) then
  call msg_fatal &
    ("File doesn't appear to be a WHIZARD raw event file")
  return
end if
read (unit, iostat=iostat) file_version
if (check .and. file_version /= version) then
  call msg_fatal &
    ("Event-file format version mismatch")
  return
end if
read (unit, iostat=iostat) n
if (check .and. n /= size (md5sum%/process)) then
  call msg_message &
    ("Process number has changed, discarding old event file")
  return
end if
allocate (md5sum_array (n))
read (unit, iostat=iostat) md5sum_array
if (check .and. any (md5sum%/process /= md5sum_array)) then
  call msg_message &
    ("Process configuration has changed, discarding old event file")
  return
end if
read (unit, iostat=iostat) md5sum_array
if (check .and. .not. rescan &

```

```

        .and. any (md5sum%parameters /= md5sum_array)) then
      call msg_message &
        ("Model parameters have changed, discarding old event file")
      return
    end if
    read (unit, iostat=iostat) md5sum_array
    if (check .and. .not. rescan &
        .and. any (md5sum%results /= md5sum_array)) then
      call msg_message &
        ("Integration results have changed, skipping event file")
      return
    end if
    read (unit, iostat=iostat) md5sum_array
    if (check .and. any (md5sum%polarized /= md5sum_array)) then
      call msg_message &
        ("Polarization setup has changed, discarding old event file")
      return
    end if
    read (unit, iostat=iostat) md5sum_single
    if (check .and. .not. rescan .and. md5sum%decays /= md5sum_single) then
      call msg_message &
        ("Decay configuration has changed, skipping event file")
      return
    end if
    read (unit, iostat=iostat) md5sum_single
    if (check .and. md5sum%simulation /= md5sum_single) then
      call msg_message &
        ("Simulation parameters have changed, skipping event file")
      return
    end if
    ok = .true.
  end subroutine raw_event_file_read_header

```

Write only valid events; an event read from file is valid by definition.

(Events: public)+≡

```

  public :: event_write_raw
  public :: event_read_raw

```

(Events: procedures)+≡

```

subroutine event_write_raw (event, unit, version)
  type(event_t), intent(in) :: event
  integer, intent(in) :: unit
  integer, intent(in) :: version
  if (event%is_valid) then
    if (.not. associated (event%process)) &
      call msg_bug ("Writing event: process not associated")
    if (.not. associated (event%vars)) &
      call msg_bug ("Writing event: event variables not associated")
    call event_vars_write_raw (event%vars, unit, version)
    write (unit) process_get_scale (event%process)
    write (unit) process_get_fac_scale (event%process)
    write (unit) process_get_ren_scale (event%process)
    write (unit) process_get_alpha_s (event%process)
    call particle_set_write_raw (event%particle_set, unit)
  end if
end subroutine event_write_raw

```

```

        end if
    end subroutine event_write_raw

subroutine event_read_raw &
    (event, unit, event_vars, prc_array, num_id_array, iostat, version)
    type(event_t), intent(out) :: event
    integer, intent(in) :: unit
    type(event_vars_t), intent(inout), target :: event_vars
    type(process_p), dimension(:), intent(in) :: prc_array
    integer, dimension(:), intent(in), optional :: num_id_array
    integer, intent(out) :: iostat
    integer, intent(in) :: version
    integer :: proc
    type(process_t), pointer :: process
    real(default) :: scale, ren_scale, fac_scale, alpha_s, sqme
    call event_vars_read_raw (event_vars, unit, iostat, version)
    if (iostat /= 0) return
    proc = event_vars%process_index
    if (proc > 0 .and. proc <= size (prc_array)) then
        process => prc_array(proc)%ptr
        event_vars%process_id = process_get_id (process)
        if (present (num_id_array)) then
            event_vars%process_num_id = num_id_array(proc)
        else
            event_vars%process_num_id = proc
        end if
    else
        call msg_fatal ("Invalid process index encountered in raw event file")
        return
    end if
    call event_init (event, process, event_vars)
    event%is_valid = .true.
    read (unit, iostat=iostat) scale
    if (iostat /= 0) return
    read (unit, iostat=iostat) fac_scale
    if (iostat /= 0) return
    read (unit, iostat=iostat) ren_scale
    if (iostat /= 0) return
    read (unit, iostat=iostat) alpha_s
    if (iostat /= 0) return
    call particle_set_read_raw (event%particle_set, unit, iostat=iostat)
    if (iostat /= 0) return
    event%particle_set_exists = .true.
    if (associated (event%process)) then
        call process_set_particles (event%process, event%particle_set)
        call process_set_scale (event%process, scale)
        call process_set_fac_scale (event%process, fac_scale)
        call process_set_ren_scale (event%process, ren_scale)
        call process_set_alpha_s (event%process, alpha_s)
        call process_set_sqme (event%process, event%vars%sqme)
    end if
end subroutine event_read_raw

```

13.5.5 HepMC interface

Check whether a file is a HepMC event file. The HepMC format is characterized by a version ID string, which apparently follows an empty line. Discard the empty line, then check the ID string (but not the version).

```

<Events: public>+≡
    public :: is_hepmc_event_file

<Events: procedures>+≡
    function is_hepmc_event_file (u) result (flag)
        logical :: flag
        integer, intent(in) :: u
        integer :: iostat
        character(*), parameter :: HEPMC_ID_STRING = "HepMC::Version"
        character(len=len(HEPMC_ID_STRING)) :: id_string
        id_string = ""
        do while (id_string == "")
            read (u, "(A)", iostat=iostat) id_string
            if (iostat /= 0) exit
        end do
        if (iostat == 0) then
            flag = id_string == HEPMC_ID_STRING
        else
            flag = .false.
        end if
    end function is_hepmc_event_file

```

Read/write the particle set as far as possible from/to a HepMC event record.

The default weight is unity. The further weights are understood as excess weight, squared matrix element, and reference value for the latter, in that order. We rely on the HepMC interface routine to return zero for a weight that does not exist. When writing to the HepMC event, we rely on the weight container to be empty initially.

The polarization mode must be known when reading from HepMC because the HepMC event record does not specify it.

Write only valid events; an event read from file is valid by definition.

```

<Events: public>+≡
    public :: event_read_from_hepmc
    public :: event_write_to_hepmc

<Events: procedures>+≡
    subroutine event_read_from_hepmc (event, hepmc_event, polarization_mode, &
        event_vars, prc_array, num_id_array)
        type(event_t), intent(out) :: event
        type(hepmc_event_t), intent(in) :: hepmc_event
        integer, intent(in) :: polarization_mode
        type(event_vars_t), intent(inout), target :: event_vars
        type(process_p), dimension(:), intent(in) :: prc_array
        integer, dimension(:), intent(in), optional :: num_id_array
        real(default) :: scale, alpha_s
        integer :: num_id, proc, n_weights
        type(process_t), pointer :: process
        num_id = hepmc_event_get_process_id (hepmc_event)
        proc = get_process_index (num_id, num_id_array)
    end subroutine event_read_from_hepmc

```

```

if (proc > 0 .and. proc <= size (prc_array)) then
  process => prc_array(proc)%ptr
  call event_init (event, process, event_vars)
  event%is_valid = .true.
  scale = hepmc_event_get_scale (hepmc_event)
  if (scale > 0) call process_set_fac_scale (process, scale)
  alpha_s = hepmc_event_get_alpha_qcd (hepmc_event)
  if (alpha_s > 0) call process_set_alpha_s (process, alpha_s)
  event_vars%event_index = hepmc_event_get_event_index (hepmc_event)
  event_vars%process_index = proc
  event_vars%process_id = process_get_id (process)
  event_vars%process_num_id = num_id
  event_vars%sqrts_hat = 0
  n_weights = hepmc_event_get_weights_size (hepmc_event)
  if (n_weights > 0) then
    event_vars%weight = hepmc_event_get_weight (hepmc_event, 1)
  else
    event_vars%weight = 1
  end if
  event_vars%excess = hepmc_event_get_weight (hepmc_event, 2)
  event_vars%sqme = hepmc_event_get_weight (hepmc_event, 3)
  event_vars%sqme_ref = hepmc_event_get_weight (hepmc_event, 4)
  call particle_set_init (event%particle_set, hepmc_event, &
    process_get_model_ptr (event%process), polarization_mode)
  event%particle_set_exists = .true.
else
  call hepmc_event_print (hepmc_event)
  write (msg_buffer, "(A,I0,A)") "HepMC event: process ID ", &
    proc, " is invalid in the current context"
  call msg_fatal ()
end if
end subroutine event_read_from_hepmc

subroutine event_write_to_hepmc (event, hepmc_event)
  type(event_t), intent(in) :: event
  type(hepmc_event_t), intent(inout) :: hepmc_event
  if (event%is_valid) then
    call hepmc_event_set_process_id (hepmc_event, event%vars%process_num_id)
    call hepmc_event_clear_weights (hepmc_event)
    call hepmc_event_add_weight (hepmc_event, event%vars%weight)
    call hepmc_event_add_weight (hepmc_event, event%vars%excess)
    call hepmc_event_add_weight (hepmc_event, event%vars%sqme)
    call hepmc_event_add_weight (hepmc_event, event%vars%sqme_ref)
    call hepmc_event_set_scale (hepmc_event, &
      process_get_fac_scale (event%process))
    call hepmc_event_set_alpha_qcd (hepmc_event, &
      process_get_alpha_s (event%process))
    ! call hepmc_event_set_cross_section (hepmc_event, &
    ! process_get_integral (event%process), &
    ! process_get_error (event%process))
    call particle_set_fill_hepmc_event (event%particle_set, hepmc_event)
  end if
end subroutine event_write_to_hepmc

```

13.5.6 LHEF and HEPEVT interface

Fill the HEPEUP (event) common block:

```

<Events: public>+≡
    public :: event_write_to_hepeup

<Events: procedures>+≡
    subroutine event_write_to_hepeup (event, keep_beams)
        type(event_t), intent(in) :: event
        integer :: proc_id
        logical, intent(in), optional :: keep_beams
        real(default) :: scale, alpha_qcd
        if (event%is_valid) then
            call particle_set_fill_hepeup (event%particle_set, keep_beams)
            if (associated (event%process)) then
                call hepeup_set_event_parameters (proc_id = event%vars%process_num_id)
                scale = process_get_fac_scale (event%process)
                if (scale /= 0) call hepeup_set_event_parameters (scale = scale)
                alpha_qcd = process_get_alpha_s (event%process)
                if (alpha_qcd /= 0) &
                    call hepeup_set_event_parameters (alpha_qcd = alpha_qcd)
                call hepeup_set_event_parameters (weight = event%vars%weight)
            end if
        end if
    end subroutine event_write_to_hepeup

```

The HEPRUP (event) common block is needed for the interface to the shower. Filling of it is triggered by some output file formats. If these are not present, the common block is filled with some dummy information. Be generous with the number of processes in HEPRUP so that PYTHIA only rarely needs to be reinitialized in case events with higher process ids are generated.

```

<Events: public>+≡
    public :: event_assure_heprup

<Events: procedures>+≡
    subroutine event_assure_heprup (event)
        type(event_t), intent(in) :: event
        integer :: i
        integer, parameter :: min_processes = 10

<Event formats: parameters>
<Event formats: variables>
<Event formats: common blocks>

        if (.not.event%is_valid) return
        if (LPRUP(event%vars%process_num_id).ne.0) return

        call heprup_init( &
            (/particle_get_pdg(particle_set_get_particle(event%particle_set, 1)), &
            particle_get_pdg(particle_set_get_particle(event%particle_set, 2)) /) , &
            (/vector4_get_component(particle_get_momentum(particle_set_get_particle(event%particle_set,
            vector4_get_component(particle_get_momentum(particle_set_get_particle(event%particle_set,
            event%vars%process_num_id, .false., .false. )
        do i=1, (event%vars%process_num_id/min_processes+1)*min_processes

```



```

        call heprup_set_process_parameters (i = i, process_id = &
            i, cross_section = 1._default, error = 1._default)
    end do
end subroutine event_assure_heprup

```

@Fill the HEPEVT (event) common block:

```

<Events: public>+≡
    public :: event_write_to_hepevt

<Events: procedures>+≡
    subroutine event_write_to_hepevt (event, keep_beams)
        type(event_t), intent(in) :: event
        integer :: proc_id
        logical, intent(in), optional :: keep_beams
        if (event%is_valid) then
            call particle_set_fill_hepevt (event%particle_set, keep_beams)
            call hepevt_set_event_parameters ( &
                weight = event%vars%weight, &
                function_value = event%vars%sqme, &
                i_evt = event%vars%event_index)
        end if
    end subroutine event_write_to_hepevt

```

13.5.7 Recovering events

Recover the process index for this event. If the optional array `num_id_array` is present, select the entry which matches the given ID, otherwise just return the input ID.

```

<Events: procedures>+≡
    function get_process_index (num_id, num_id_array) result (proc)
        integer :: proc
        integer, intent(in) :: num_id
        integer, dimension(:), intent(in), optional :: num_id_array
        if (present (num_id_array)) then
            do proc = 1, size (num_id_array)
                if (num_id_array(proc) == num_id) return
            end do
            write (msg_buffer, "(A,I0,A)") "Reading events: numeric process ID ", &
                num_id, " does not match any process"
            call msg_fatal
            proc = 0
        else
            proc = num_id
        end if
    end function get_process_index

```

Given an event, recover process data.

```

<Events: public>+≡
    public :: event_get_process_ptr

```

```

<Events: procedures>+≡
  function event_get_process_ptr (event) result (process)
    type(process_t), pointer :: process
    type(event_t), intent(in) :: event
    process => event%process
  end function event_get_process_ptr

```

13.5.8 Factorization modes

We re-export them here from the `state_matrices` module:

```

<Events: public>+≡
  public :: FM_IGNORE_HELICITY
  public :: FM_SELECT_HELICITY
  public :: FM_FACTOR_HELICITY

```

13.5.9 Test

```

<Events: public>+≡
  public :: event_test

<Events: procedures>+≡
  subroutine event_test ()
    type(os_data_t), pointer :: os_data => null ()
    type(process_library_t), pointer :: prc_lib => null ()
    type(event_t), target :: event
    type(model_t), pointer :: model
    type(var_list_t), pointer :: var_list => null ()
    print *, "*** Read model file"
    allocate (os_data)
    allocate (prc_lib)
    allocate (var_list)
    call os_data_init (os_data)
    call syntax_model_file_init ()
    call model_list_read_model &
      (var_str("SM"), var_str("SM.mdl"), os_data, model)
    var_list => model_get_var_list_ptr (model)
    call syntax_pexpr_init ()
    call syntax_phs_forest_init ()
    print *
    print *, "*** Load process library"
    call var_list_append_string (var_list, name = "$library_name", sval = "test_me") ! $
    call var_list_append_log (var_list, name = "?read_color_factors", lval = .true.)
    call var_list_append_log (var_list, name = "?alpha_s_is_fixed", lval = .true.)
    call process_library_init (prc_lib, var_str("test_me"), os_data)
    call process_library_load (prc_lib, os_data, var_list = var_list)
    print *
    call event_test1 (prc_lib, model, os_data, var_list)
    print *
    print *, "* Cleanup"
    call event_final (event)
    call process_store_final ()
    call syntax_pexpr_final ()

```

```

call syntax_phs_forest_final ()
call syntax_model_file_final ()
call process_library_final (prc_lib)
deallocate (os_data)
deallocate (prc_lib)
end subroutine event_test

```

(Events: procedures)+≡

```

subroutine event_test1 (prc_lib, model, os_data, var_list)
  type(process_library_t), intent(inout) :: prc_lib
  type(model_t), intent(in), target :: model
  type(os_data_t), intent(in) :: os_data
  type(var_list_t), target :: var_list
  type(process_t), pointer :: process
  type(phs_parameters_t) :: phs_par
  type(mapping_defaults_t) :: mapping_defaults
  type(flavor_t), dimension(2) :: flv
  type(polarization_t), dimension(2) :: pol
  type(beam_data_t) :: beam_data
  type(stream_t), target :: stream
  type(parse_tree_t) :: parse_tree
  type(grid_parameters_t) :: grid_parameters
  integer :: i
  type(tao_random_state) :: rng
  type(event_vars_t), target :: event_vars
  type(event_t), target :: event
  type(decay_tree_t), target :: decay_tree
  logical :: rebuild_phs = .true.
  print *, "*** Test process setup"
  print *
  print *, "* Initialization"
  call tao_random_create (rng, 0)
  call process_store_init_process &
    (process, prc_lib, var_str ("test_me_unit_col"), model, &
     var_list, use_beams = .false.)
  print *, " Process ID = ", char (process_get_id (process))
  print *
  print *, "* Beam setup"
  print *
  call flavor_init (flv, (/ 2, -2 /), model)
  call polarization_init_unpolarized (pol(1), flv(1))
  call polarization_init_unpolarized (pol(2), flv(2))
  call process_setup_beams (process, beam_data, 0, sqrts = 1000._default)
  call process_connect_strfun (process)
  call process_setup_subevt (process)
  print *
  print *, "* Phase space setup"
  call openmp_set_num_threads_verbose (1)
  call process_setup_phase_space (process, rebuild_phs, &
    os_data, phs_par, mapping_defaults, filename_out=var_str("test_me_unit_col.phs"), &
    vis_channels = .false.)
  print *
  print *, "* Cuts setup"
  call stream_init (stream, var_str ("all Pt > 200 GeV [g]"))

```

```

call parse_tree_init_lexpr (parse_tree, stream, .true.)
call process_setup_cuts (process, parse_tree_get_root_ptr (parse_tree))
call parse_tree_final (parse_tree)
call stream_final (stream)
print *
print *, "*** Integration"
print *, "* Grids setup"
call process_setup_grids (process, grid_parameters, calls=10000)
print *
print *, "* 5 + 3 iterations"
call process_results_write_header (process)
call process_init_vamp_history (process, 8)
call openmp_set_num_threads_verbose (1)
do i = 1, 5
    call process_integrate (process, rng, grid_parameters, &
        1, 1, 1, 5000, i==1, .true., i>2, .true., .true.)
end do
call process_results_write_current_average (process)
call process_integrate (process, rng, grid_parameters, &
    2, 1, 3, 5000, .true., .false., .true., .true., .true.)
call process_results_write_footer (process)
call process_write_time_estimate (process)
print *
print *, "*** Event generation"
call process_setup_event_generation (process)
call decay_tree_init (decay_tree, process)
call event_init (event, process, event_vars, decay_tree=decay_tree)
print *
print *, "* Weighted event"
call event_generate &
    (event, rng, .false., FM_IGNORE_HELICITY, .false., .false., os_data)
call event_write (event)
print *
print *, "* Unweighted event"
call event_generate &
    (event, rng, .true., FM_SELECT_HELICITY, .false., .true., os_data)
call event_write (event)
print *, " Process data written to fort.81"
call process_write (process, 81)
call event_final (event)
end subroutine event_test1

```

Chapter 14

External modules

14.1 STDHEP interface

Interface to the STDHEP library for portable I/O of binary event data. The dummy module is needed if the STDHEP library cannot be linked, in order to provide dummy routines. The second module contains calls to the actual stdhep routines. The number of expected events is not really important. It is a 32-bit number, so if the actual number gets larger, insert the maximal possible 32-bit number.

When writing events, the flag `ilbl` determines the common block to write: 1 for HEPEVT, 11 for HEPEUP, 12 for HEPRUP

`<stdhep_interface.f90>`≡
<File header>

```
module stdhep_interface
```

```
  use kinds, only: i32, i64 !NODEP!
```

<Standard module head>

```
  public :: stdhep_init, stdhep_write, stdhep_end
```

```
  integer, parameter, public :: &
```

```
    STDHEP_HEPEVT = 1, STDHEP_HEPEUP = 11, STDHEP_HEPRUP = 12
```

```
  integer, save :: istr, lok
```

```
contains
```

```
  subroutine stdhep_init (file, title, nevt)
    character(len=*), intent(in) :: file, title
    integer(i64), intent(in) :: nevt
    integer(i32) :: nevt32
    external stdxwinit, stdxwrt
    nevt32 = min (nevt, int (huge (1_i32), i64))
    call stdxwinit (file, title, nevt32, istr, lok)
    call stdxwrt (100, istr, lok)
  end subroutine stdhep_init
```

```
subroutine stdhep_write (ilbl)
  integer, intent(in) :: ilbl
  external stdxwrt
  call stdxwrt (ilbl, istr, lok)
end subroutine stdhep_write

subroutine stdhep_end
  external stdxend
  call stdxend (istr)
end subroutine stdhep_end

end module stdhep_interface
```

Chapter 15

The SUSY Les Houches Accord

The SUSY Les Houches Accord defines a standard interfaces for storing the physics data of SUSY models. Here, we provide the means for reading, storing, and writing such data.

`<slha_interface.f90>`≡
<File header>

```
module slha_interface
```

```
<Use kinds>
```

```
<Use strings>
```

```
  use limits, only: EOF, VERSION_STRING !NODEP!
```

```
  use constants !NODEP!
```

```
<Use file utils>
```

```
  use diagnostics !NODEP!
```

```
  use os_interface
```

```
  use ifiles
```

```
  use lexers
```

```
  use syntax_rules
```

```
  use parser
```

```
  use variables
```

```
  use expressions
```

```
  use models
```

```
<Standard module head>
```

```
<SLHA: public>
```

```
<SLHA: parameters>
```

```
<SLHA: variables>
```

```
  save
```

```
contains
```

<SLHA: procedures>

end module slha_interface

15.0.1 Preprocessor

SLHA is a mixed-format standard. It should be read in assuming free format (but line-oriented), but it has some fixed-format elements.

To overcome this difficulty, we implement a preprocessing step which transforms the SLHA into a format that can be swallowed by our generic free-format lexer and parser. Each line with a blank first character is assumed to be a data line. We prepend a 'DATA' keyword to these lines. Furthermore, to enforce line-orientation, each line is appended a '\$' key which is recognized by the parser. To do this properly, we first remove trailing comments, and skip lines consisting only of comments.

The preprocessor reads from a stream and puts out an `ifile`. Blocks that are not recognized are skipped. For some blocks, data items are quoted, so they can be read as strings if necessary.

<SLHA: parameters>≡

```
integer, parameter :: MODE_SKIP = 0, MODE_DATA = 1, MODE_INFO = 2
```

<SLHA: procedures>≡

```
subroutine slha_preprocess (stream, ifile)
  type(stream_t), intent(inout), target :: stream
  type(ifile_t), intent(out) :: ifile
  type(string_t) :: buffer, line, item
  integer :: iostat
  integer :: mode
  mode = MODE
  SCAN_FILE: do
    call stream_get_record (stream, buffer, iostat)
    select case (iostat)
    case (0)
      call split (buffer, line, "#")
      if (len_trim (line) == 0) cycle SCAN_FILE
      select case (char (extract (line, 1, 1)))
      case ("B", "b")
        mode = check_block_handling (line)
        call ifile_append (ifile, line // "$")
      case ("D", "d")
        mode = MODE_DATA
        call ifile_append (ifile, line // "$")
      case (" ")
        select case (mode)
        case (MODE_DATA)
          call ifile_append (ifile, "DATA" // line // "$")
        case (MODE_INFO)
          line = adjustl (line)
          call split (line, item, " ")
          call ifile_append (ifile, "INFO" // " " // item // " " &
            // ' ' // trim (adjustl (line)) // ' ' '$')
        end select
    end select
```



```

        case default
            call msg_message (char (line))
            call msg_fatal ("SLHA: Incomprehensible line")
        end select
    case (EOF)
        exit SCAN_FILE
    case default
        call msg_fatal ("SLHA: I/O error occured while reading SLHA input")
    end select
end do SCAN_FILE
end subroutine slha_preprocess

```

Return the mode that we should treat this block with. We need to recognize only those blocks that we actually use.

```

⟨SLHA: procedures⟩+≡
function check_block_handling (line) result (mode)
    integer :: mode
    type(string_t), intent(in) :: line
    type(string_t) :: buffer, key, block_name
    buffer = trim (line)
    call split (buffer, key, " ")
    buffer = adjustl (buffer)
    call split (buffer, block_name, " ")
    block_name = trim (adjustl (upper_case (block_name)))
    select case (char (block_name))
    case ("MODSEL", "MINPAR", "SMINPUTS")
        mode = MODE_DATA
    case ("MASS")
        mode = MODE_DATA
    case ("NMIX", "UMIX", "VMIX", "STOPMIX", "SBOTMIX", "STAUMIX")
        mode = MODE_DATA
    case ("NMHMX", "NMAMIX", "NMNMIX", "NMSSMRUN")
        mode = MODE_DATA
    case ("ALPHA", "HMIX")
        mode = MODE_DATA
    case ("AU", "AD", "AE")
        mode = MODE_DATA
    case ("SPINFO", "DCINFO")
        mode = MODE_INFO
    case default
        mode = MODE_SKIP
    end select
end function check_block_handling

```

15.0.2 Lexer and syntax

```

⟨SLHA: variables⟩≡
type(syntax_t), target :: syntax_slha

```

```

⟨SLHA: public⟩≡
public :: syntax_slha_init

```

```

<SLHA: procedures>+=
  subroutine syntax_slha_init ()
    type(ifile_t) :: ifile
    call define_slha_syntax (ifile)
    call syntax_init (syntax_slha, ifile)
    call ifile_final (ifile)
  end subroutine syntax_slha_init

<SLHA: public>+=
  public :: syntax_slha_final

<SLHA: procedures>+=
  subroutine syntax_slha_final ()
    call syntax_final (syntax_slha)
  end subroutine syntax_slha_final

<SLHA: public>+=
  public :: syntax_slha_write

<SLHA: procedures>+=
  subroutine syntax_slha_write (unit)
    integer, intent(in), optional :: unit
    call syntax_write (syntax_slha, unit)
  end subroutine syntax_slha_write

<SLHA: procedures>+=
  subroutine define_slha_syntax (ifile)
    type(ifile_t), intent(inout) :: ifile
    call ifile_append (ifile, "SEQ slha = chunk*")
    call ifile_append (ifile, "ALT chunk = block_def | decay_def")
    call ifile_append (ifile, "SEQ block_def = " &
      // "BLOCK block_spec '$' block_line*")
    call ifile_append (ifile, "KEY BLOCK")
    call ifile_append (ifile, "SEQ block_spec = block_name qvalue?")
    call ifile_append (ifile, "IDE block_name")
    call ifile_append (ifile, "SEQ qvalue = qname '=' real")
    call ifile_append (ifile, "IDE qname")
    call ifile_append (ifile, "KEY '='")
    call ifile_append (ifile, "REA real")
    call ifile_append (ifile, "KEY '$'")
    call ifile_append (ifile, "ALT block_line = block_data | block_info")
    call ifile_append (ifile, "SEQ block_data = DATA data_line '$'")
    call ifile_append (ifile, "KEY DATA")
    call ifile_append (ifile, "SEQ data_line = data_item+")
    call ifile_append (ifile, "ALT data_item = signed_number | number")
    call ifile_append (ifile, "SEQ signed_number = sign number")
    call ifile_append (ifile, "ALT sign = '+' | '-'")
    call ifile_append (ifile, "ALT number = integer | real")
    call ifile_append (ifile, "INT integer")
    call ifile_append (ifile, "KEY '-'")
    call ifile_append (ifile, "KEY '+'")
    call ifile_append (ifile, "SEQ block_info = INFO info_line '$'")
    call ifile_append (ifile, "KEY INFO")
    call ifile_append (ifile, "SEQ info_line = integer string_literal")
  end subroutine define_slha_syntax

```

```

call ifile_append (ifile, "QUO string_literal = '""'...'""')
call ifile_append (ifile, "SEQ decay_def = " &
// "DECAY decay_spec '$' decay_data*")
call ifile_append (ifile, "KEY DECAY")
call ifile_append (ifile, "SEQ decay_spec = pdg_code data_item")
call ifile_append (ifile, "ALT pdg_code = signed_integer | integer")
call ifile_append (ifile, "SEQ signed_integer = sign integer")
call ifile_append (ifile, "SEQ decay_data = DATA decay_line '$'")
call ifile_append (ifile, "SEQ decay_line = data_item integer pdg_code+")
end subroutine define_slha_syntax

```

The SLHA specification allows for string data items in certain places. Currently, we do not interpret them, but the strings, which are not quoted, must be parsed somehow. The hack for this problem is to allow essentially all characters as special characters, so the string can be read before it is discarded.

```

⟨SLHA: public⟩+=
public :: lexer_init_slha

⟨SLHA: procedures⟩+=
subroutine lexer_init_slha (lexer)
type(lexer_t), intent(out) :: lexer
call lexer_init (lexer, &
comment_chars = "#", &
quote_chars = "'", &
quote_match = "'", &
single_chars = "+-=$", &
special_class = (/ "" /), &
keyword_list = syntax_get_keyword_list_ptr (syntax_slha), &
upper_case_keywords = .true.) ! $
end subroutine lexer_init_slha

```

15.0.3 Interpreter

Find blocks

From the parse tree, find the node that represents a particular block. If `required` is true, issue an error if not found. Since `block_name` is always invoked with capital letters, we have to capitalize `pn_block_name`.

```

⟨SLHA: procedures⟩+=
function slha_get_block_ptr &
(parse_tree, block_name, required) result (pn_block)
type(parse_node_t), pointer :: pn_block
type(parse_tree_t), intent(in) :: parse_tree
type(string_t), intent(in) :: block_name
logical, intent(in) :: required
type(parse_node_t), pointer :: pn_root, pn_block_spec, pn_block_name
pn_root => parse_tree_get_root_ptr (parse_tree)
pn_block => parse_node_get_sub_ptr (pn_root)
do while (associated (pn_block))
select case (char (parse_node_get_rule_key (pn_block)))
case ("block_def")
pn_block_spec => parse_node_get_sub_ptr (pn_block, 2)

```

```

        pn_block_name => parse_node_get_sub_ptr (pn_block_spec)
        if (trim (adjustl (upper_case (parse_node_get_string &
            (pn_block_name)))) == block_name) then
            return
        end if
    end select
    pn_block => parse_node_get_next_ptr (pn_block)
end do
if (required) then
    call msg_fatal ("SLHA: block '" // char (block_name) // "' not found")
end if
end function slha_get_block_ptr

```

Scan the file for the first/next DECAY block.

(SLHA: procedures)+≡

```

function slha_get_first_decay_ptr (parse_tree) result (pn_decay)
    type(parse_node_t), pointer :: pn_decay
    type(parse_tree_t), intent(in) :: parse_tree
    type(parse_node_t), pointer :: pn_root
    pn_root => parse_tree_get_root_ptr (parse_tree)
    pn_decay => parse_node_get_sub_ptr (pn_root)
    do while (associated (pn_decay))
        select case (char (parse_node_get_rule_key (pn_decay)))
            case ("decay_def")
                return
        end select
        pn_decay => parse_node_get_next_ptr (pn_decay)
    end do
end function slha_get_first_decay_ptr

function slha_get_next_decay_ptr (pn_block) result (pn_decay)
    type(parse_node_t), pointer :: pn_decay
    type(parse_node_t), intent(in), target :: pn_block
    pn_decay => parse_node_get_next_ptr (pn_block)
    do while (associated (pn_decay))
        select case (char (parse_node_get_rule_key (pn_decay)))
            case ("decay_def")
                return
        end select
        pn_decay => parse_node_get_next_ptr (pn_decay)
    end do
end function slha_get_next_decay_ptr

```

Extract and transfer data from blocks

Given the parse node of a block, find the parse node of a particular switch or data line. Return this node and the node of the data item following the integer code.

(SLHA: procedures)+≡

```

subroutine slha_find_index_ptr (pn_block, pn_data, pn_item, code)
    type(parse_node_t), intent(in), target :: pn_block
    ! type(parse_node_t), intent(out), pointer :: pn_data

```

```

!   type(parse_node_t), intent(out), pointer :: pn_item
      type(parse_node_t), pointer :: pn_data
      type(parse_node_t), pointer :: pn_item
      integer, intent(in) :: code
      pn_data => parse_node_get_sub_ptr (pn_block, 4)
      call slha_next_index_ptr (pn_data, pn_item, code)
end subroutine slha_find_index_ptr

subroutine slha_find_index_pair_ptr (pn_block, pn_data, pn_item, code1, code2)
      type(parse_node_t), intent(in), target :: pn_block
!   type(parse_node_t), intent(out), pointer :: pn_data
!   type(parse_node_t), intent(out), pointer :: pn_item
      type(parse_node_t), pointer :: pn_data
      type(parse_node_t), pointer :: pn_item
      integer, intent(in) :: code1, code2
      pn_data => parse_node_get_sub_ptr (pn_block, 4)
      call slha_next_index_pair_ptr (pn_data, pn_item, code1, code2)
end subroutine slha_find_index_pair_ptr

```

Starting from the pointer to a data line, find a data line with the given integer code.

(SLHA: procedures)+≡

```

subroutine slha_next_index_ptr (pn_data, pn_item, code)
      type(parse_node_t), intent(inout), pointer :: pn_data
      integer, intent(in) :: code
!   type(parse_node_t), intent(out), pointer :: pn_item
      type(parse_node_t), pointer :: pn_item
      type(parse_node_t), pointer :: pn_line, pn_code
      do while (associated (pn_data))
          pn_line => parse_node_get_sub_ptr (pn_data, 2)
          pn_code => parse_node_get_sub_ptr (pn_line)
          select case (char (parse_node_get_rule_key (pn_code)))
              case ("integer")
                  if (parse_node_get_integer (pn_code) == code) then
                      pn_item => parse_node_get_next_ptr (pn_code)
                      return
                  end if
              end select
          pn_data => parse_node_get_next_ptr (pn_data)
      end do
      pn_item => null ()
end subroutine slha_next_index_ptr

```

Starting from the pointer to a data line, find a data line with the given integer code pair.

(SLHA: procedures)+≡

```

subroutine slha_next_index_pair_ptr (pn_data, pn_item, code1, code2)
      type(parse_node_t), intent(inout), pointer :: pn_data
      integer, intent(in) :: code1, code2
!   type(parse_node_t), intent(out), pointer :: pn_item
      type(parse_node_t), pointer :: pn_item
      type(parse_node_t), pointer :: pn_line, pn_code1, pn_code2
      do while (associated (pn_data))

```

```

pn_line => parse_node_get_sub_ptr (pn_data, 2)
pn_code1 => parse_node_get_sub_ptr (pn_line)
select case (char (parse_node_get_rule_key (pn_code1)))
case ("integer")
  if (parse_node_get_integer (pn_code1) == code1) then
    pn_code2 => parse_node_get_next_ptr (pn_code1)
    if (associated (pn_code2)) then
      select case (char (parse_node_get_rule_key (pn_code2)))
      case ("integer")
        if (parse_node_get_integer (pn_code2) == code2) then
          pn_item => parse_node_get_next_ptr (pn_code2)
          return
        end if
      end select
    end if
  end if
end select
pn_data => parse_node_get_next_ptr (pn_data)
end do
pn_item => null ()
end subroutine slha_next_index_pair_ptr

```

Handle info data

Return all strings with index *i*. The result is an allocated string array. Since we do not know the number of matching entries in advance, we build an intermediate list which is transferred to the final array and deleted before exiting.

(*SLHA: procedures*) +=

```

subroutine retrieve_strings_in_block (pn_block, code, str_array)
  type(parse_node_t), intent(in), target :: pn_block
  integer, intent(in) :: code
  type(string_t), dimension(:), allocatable, intent(out) :: str_array
  type(parse_node_t), pointer :: pn_data, pn_item
  type :: str_entry_t
    type(string_t) :: str
    type(str_entry_t), pointer :: next => null ()
  end type str_entry_t
  type(str_entry_t), pointer :: first => null ()
  type(str_entry_t), pointer :: current => null ()
  integer :: n
  n = 0
  call slha_find_index_ptr (pn_block, pn_data, pn_item, code)
  if (associated (pn_item)) then
    n = n + 1
    allocate (first)
    first%str = parse_node_get_string (pn_item)
    current => first
    do while (associated (pn_data))
      pn_data => parse_node_get_next_ptr (pn_data)
      call slha_next_index_ptr (pn_data, pn_item, code)
      if (associated (pn_item)) then
        n = n + 1

```

```

        allocate (current%next)
        current => current%next
        current%str = parse_node_get_string (pn_item)
    end if
end do
allocate (str_array (n))
n = 0
do while (associated (first))
    n = n + 1
    current => first
    str_array(n) = current%str
    first => first%next
    deallocate (current)
end do
else
    allocate (str_array (0))
end if
end subroutine retrieve_strings_in_block

```

Transfer data from SLHA to variables

Extract real parameter with index *i*. If it does not exist, retrieve it from the variable list, using the given name.

(SLHA: procedures)+≡

```

function get_parameter_in_block (pn_block, code, name, var_list) result (var)
    real(default) :: var
    type(parse_node_t), intent(in), target :: pn_block
    integer, intent(in) :: code
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in), target :: var_list
    type(parse_node_t), pointer :: pn_data, pn_item
    call slha_find_index_ptr (pn_block, pn_data, pn_item, code)
    if (associated (pn_item)) then
        var = get_real_parameter (pn_item)
    else
        var = var_list_get_rval (var_list, name)
    end if
end function get_parameter_in_block

```

Extract a real data item with index *i*. If it does exist, set it in the variable list, using the given name. If the variable is not present in the variable list, ignore it.

(SLHA: procedures)+≡

```

subroutine set_data_item (pn_block, code, name, var_list)
    type(parse_node_t), intent(in), target :: pn_block
    integer, intent(in) :: code
    type(string_t), intent(in) :: name
    type(var_list_t), intent(inout), target :: var_list
    type(parse_node_t), pointer :: pn_data, pn_item
    call slha_find_index_ptr (pn_block, pn_data, pn_item, code)
    if (associated (pn_item)) then
        call var_list_set_real &

```

```

        (var_list, name, get_real_parameter (pn_item), &
         is_known=.true., ignore=.true.)
    end if
end subroutine set_data_item

```

Extract a real matrix element with index i, j . If it does exists, set it in the variable list, using the given name. If the variable is not present in the variable list, ignore it.

(SLHA: procedures)+≡

```

subroutine set_matrix_element (pn_block, code1, code2, name, var_list)
    type(parse_node_t), intent(in), target :: pn_block
    integer, intent(in) :: code1, code2
    type(string_t), intent(in) :: name
    type(var_list_t), intent(inout), target :: var_list
    type(parse_node_t), pointer :: pn_data, pn_item
    call slha_find_index_pair_ptr (pn_block, pn_data, pn_item, code1, code2)
    if (associated (pn_item)) then
        call var_list_set_real &
            (var_list, name, get_real_parameter (pn_item), &
             is_known=.true., ignore=.true.)
    end if
end subroutine set_matrix_element

```

Transfer data from variables to SLHA

Get a real/integer parameter with index i from the variable list and write it to the current output file. In the integer case, we account for the fact that the variable is type real. If it does not exist, do nothing.

(SLHA: procedures)+≡

```

subroutine write_integer_data_item (u, code, name, var_list, comment)
    integer, intent(in) :: u
    integer, intent(in) :: code
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in) :: var_list
    character(*), intent(in) :: comment
    integer :: item
    if (var_list_exists (var_list, name)) then
        item = nint (var_list_get_rval (var_list, name))
        call write_integer_parameter (u, code, item, comment)
    end if
end subroutine write_integer_data_item

subroutine write_real_data_item (u, code, name, var_list, comment)
    integer, intent(in) :: u
    integer, intent(in) :: code
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in) :: var_list
    character(*), intent(in) :: comment
    real(default) :: item
    if (var_list_exists (var_list, name)) then
        item = var_list_get_rval (var_list, name)
        call write_real_parameter (u, code, item, comment)
    end if
end subroutine write_real_data_item

```



```

        end if
    end subroutine write_real_data_item

```

Get a real data item with two integer indices from the variable list and write it to the current output file. If it does not exist, do nothing.

<SLHA: procedures>+≡

```

subroutine write_matrix_element (u, code1, code2, name, var_list, comment)
    integer, intent(in) :: u
    integer, intent(in) :: code1, code2
    type(string_t), intent(in) :: name
    type(var_list_t), intent(in) :: var_list
    character(*), intent(in) :: comment
    real(default) :: item
    if (var_list_exists (var_list, name)) then
        item = var_list_get_rval (var_list, name)
        call write_real_matrix_element (u, code1, code2, item, comment)
    end if
end subroutine write_matrix_element

```

15.0.4 Auxiliary function

Write a block header.

<SLHA: procedures>+≡

```

subroutine write_block_header (u, name, comment)
    integer, intent(in) :: u
    character(*), intent(in) :: name, comment
    write (u, "(A,1x,A,3x,'#',1x,A)") "BLOCK", name, comment
end subroutine write_block_header

```

Extract a real parameter that may be defined real or integer, signed or unsigned.

<SLHA: procedures>+≡

```

function get_real_parameter (pn_item) result (var)
    real(default) :: var
    type(parse_node_t), intent(in), target :: pn_item
    type(parse_node_t), pointer :: pn_sign, pn_var
    integer :: sign
    select case (char (parse_node_get_rule_key (pn_item)))
    case ("signed_number")
        pn_sign => parse_node_get_sub_ptr (pn_item)
        pn_var => parse_node_get_next_ptr (pn_sign)
        select case (char (parse_node_get_key (pn_sign)))
        case ("+"); sign = +1
        case ("-"); sign = -1
        end select
    case default
        sign = +1
        pn_var => pn_item
    end select
    select case (char (parse_node_get_rule_key (pn_var)))
    case ("integer"); var = sign * parse_node_get_integer (pn_var)
    case ("real"); var = sign * parse_node_get_real (pn_var)

```

```

        end select
    end function get_real_parameter

```

Auxiliary: Extract an integer parameter that may be defined signed or unsigned.
A real value is an error.

<SLHA: procedures>+≡

```

function get_integer_parameter (pn_item) result (var)
    integer :: var
    type(parse_node_t), intent(in), target :: pn_item
    type(parse_node_t), pointer :: pn_sign, pn_var
    integer :: sign
    select case (char (parse_node_get_rule_key (pn_item)))
    case ("signed_integer")
        pn_sign => parse_node_get_sub_ptr (pn_item)
        pn_var => parse_node_get_next_ptr (pn_sign)
        select case (char (parse_node_get_key (pn_sign)))
        case ("+"); sign = +1
        case ("-"); sign = -1
        end select
    case ("integer")
        sign = +1
        pn_var => pn_item
    case default
        call parse_node_write (pn_var)
        call msg_error ("SLHA: Integer parameter expected")
        var = 0
        return
    end select
    var = sign * parse_node_get_integer (pn_var)
end function get_integer_parameter

```

Write an integer parameter with a single index directly to file, using the required output format.

<SLHA: procedures>+≡

```

subroutine write_integer_parameter (u, code, item, comment)
    integer, intent(in) :: u
    integer, intent(in) :: code
    integer, intent(in) :: item
    character(*), intent(in) :: comment
1   format (1x, I9, 3x, 3x, I9, 4x, 3x, '#', 1x, A)
    write (u, 1) code, item, comment
end subroutine write_integer_parameter

```

Write a real parameter with two indices directly to file, using the required output format.

<SLHA: procedures>+≡

```

subroutine write_real_parameter (u, code, item, comment)
    integer, intent(in) :: u
    integer, intent(in) :: code
    real(default), intent(in) :: item
    character(*), intent(in) :: comment
1   format (1x, I9, 3x, 1P, E16.8, 0P, 3x, '#', 1x, A)

```

```

        write (u, 1) code, item, comment
    end subroutine write_real_parameter

```

Write a real parameter with a single index directly to file, using the required output format.

```

<SLHA: procedures>+=
    subroutine write_real_matrix_element (u, code1, code2, item, comment)
        integer, intent(in) :: u
        integer, intent(in) :: code1, code2
        real(default), intent(in) :: item
        character(*), intent(in) :: comment
1    format (1x, I2, 1x, I2, 3x, 1P, E16.8, 0P, 3x, '#', 1x, A)
        write (u, 1) code1, code2, item, comment
    end subroutine write_real_matrix_element

```

The concrete SLHA interpreter

SLHA codes for particular physics models

```

<SLHA: parameters>+=
    integer, parameter :: MDL_MSSM = 0
    integer, parameter :: MDL_NMSSM = 1

```

Take the parse tree and extract relevant data. Select the correct model and store all data that is present in the appropriate variable list. Finally, update the variable record.

```

<SLHA: procedures>+=
    subroutine slha_interpret_parse_tree &
        (parse_tree, os_data, model, input, spectrum, decays)
        type(parse_tree_t), intent(in) :: parse_tree
        type(os_data_t), intent(in) :: os_data
    !   type(model_t), pointer, intent(out) :: model
        type(model_t), pointer, intent(inout) :: model
        logical, intent(in) :: input, spectrum, decays
        logical :: errors
        integer :: mssm_type
        call slha_handle_MODSEL (parse_tree, os_data, model, mssm_type)
        if (associated (model)) then
            if (input) then
                call slha_handle_SMINPUTS (parse_tree, model)
                call slha_handle_MINPAR (parse_tree, model, mssm_type)
            end if
            if (spectrum) then
                call slha_handle_info_block (parse_tree, "SPINFO", errors)
                if (errors) return
                call slha_handle_MASS (parse_tree, model)
                call slha_handle_matrix_block (parse_tree, "NMIX", "mn_", 4, 4, model)
                call slha_handle_matrix_block (parse_tree, "NMNMIX", "mixn_", 5, 5, model)
                call slha_handle_matrix_block (parse_tree, "UMIX", "mu_", 2, 2, model)
                call slha_handle_matrix_block (parse_tree, "VMIX", "mv_", 2, 2, model)
                call slha_handle_matrix_block (parse_tree, "STOPMIX", "mt_", 2, 2, model)
                call slha_handle_matrix_block (parse_tree, "SBOTMIX", "mb_", 2, 2, model)
                call slha_handle_matrix_block (parse_tree, "STAUMIX", "ml_", 2, 2, model)
            end if
        end if
    end subroutine slha_interpret_parse_tree

```

```

        call slha_handle_matrix_block (parse_tree, "NMHMIX", "mixh0_", 3, 3, model)
        call slha_handle_matrix_block (parse_tree, "NMAMIX", "mixa0_", 2, 3, model)
        call slha_handle_ALPHA (parse_tree, model)
        call slha_handle_HMIX (parse_tree, model)
        call slha_handle_NMSSMRUN (parse_tree, model)
        call slha_handle_matrix_block (parse_tree, "AU", "Au_", 3, 3, model)
        call slha_handle_matrix_block (parse_tree, "AD", "Ad_", 3, 3, model)
        call slha_handle_matrix_block (parse_tree, "AE", "Ae_", 3, 3, model)
    end if
    if (decays) then
        call slha_handle_info_block (parse_tree, "DCINFO", errors)
        if (errors) return
        call slha_handle_decays (parse_tree, model)
    end if
end if
end subroutine slha_interpret_parse_tree

```

Info blocks

Handle the informational blocks SPINFO and DCINFO. The first two items are program name and version. Items with index 3 are warnings. Items with index 4 are errors. We reproduce these as WHIZARD warnings and errors.

(SLHA: procedures)+≡

```

subroutine slha_handle_info_block (parse_tree, block_name, errors)
    type(parse_tree_t), intent(in) :: parse_tree
    character(*), intent(in) :: block_name
    logical, intent(out) :: errors
    type(parse_node_t), pointer :: pn_block
    type(string_t), dimension(:), allocatable :: msg
    integer :: i
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str (block_name), required=.true.)
    if (.not. associated (pn_block)) then
        call msg_error ("SLHA: Missing info block '" &
            // trim (block_name) // "'; ignored.")
        errors = .true.
        return
    end if
    select case (block_name)
    case ("SPINFO")
        call msg_message ("SLHA: SUSY spectrum program info:")
    case ("DCINFO")
        call msg_message ("SLHA: SUSY decay program info:")
    end select
    call retrieve_strings_in_block (pn_block, 1, msg)
    do i = 1, size (msg)
        call msg_message ("SLHA: " // char (msg(i)))
    end do
    call retrieve_strings_in_block (pn_block, 2, msg)
    do i = 1, size (msg)
        call msg_message ("SLHA: " // char (msg(i)))
    end do
end do

```

```

call retrieve_strings_in_block (pn_block, 3, msg)
do i = 1, size (msg)
    call msg_warning ("SLHA: " // char (msg(i)))
end do
call retrieve_strings_in_block (pn_block, 4, msg)
do i = 1, size (msg)
    call msg_error ("SLHA: " // char (msg(i)))
end do
errors = size (msg) > 0
end subroutine slha_handle_info_block

```

MODSEL

Handle the overall model definition. Only certain models are recognized. The soft-breaking model templates that determine the set of input parameters:

<SLHA: parameters>+≡

```

integer, parameter :: MSSM_GENERIC = 0
integer, parameter :: MSSM_SUGRA = 1
integer, parameter :: MSSM_GMSB = 2
integer, parameter :: MSSM_AMSB = 3

```

<SLHA: procedures>+≡

```

subroutine slha_handle_MODSEL (parse_tree, os_data, model, mssm_type)
    type(parse_tree_t), intent(in) :: parse_tree
    type(os_data_t), intent(in) :: os_data
    type(model_t), pointer, intent(inout) :: model
    integer, intent(out) :: mssm_type
    type(parse_node_t), pointer :: pn_block, pn_data, pn_item
    type(string_t) :: model_name
    type(string_t) :: filename
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("MODSEL"), required=.true.)
    call slha_find_index_ptr (pn_block, pn_data, pn_item, 1)
    if (associated (pn_item)) then
        mssm_type = get_integer_parameter (pn_item)
    else
        mssm_type = MSSM_GENERIC
    end if
    call slha_find_index_ptr (pn_block, pn_data, pn_item, 3)
    if (associated (pn_item)) then
        select case (parse_node_get_integer (pn_item))
            case (MDL_MSSM); model_name = "MSSM"
            case (MDL_NMSSM); model_name = "NMSSM"
            case default
                call msg_fatal ("SLHA: unknown model code in MODSEL")
                return
        end select
    else
        model_name = "MSSM"
    end if
    call slha_find_index_ptr (pn_block, pn_data, pn_item, 4)
    if (associated (pn_item)) then

```

```

        call msg_fatal (" R-parity violation is currently not supported by WHIZARD.")
    end if
    call slha_find_index_ptr (pn_block, pn_data, pn_item, 5)
    if (associated (pn_item)) then
        call msg_fatal (" CP violation is currently not supported by WHIZARD.")
    end if
    select case (char (model_name))
        case ("MSSM")
            select case (char (model_get_name (model)))
                case ("MSSM","MSSM_CKM","MSSM_Grav","MSSM_Hgg")
                    model_name = model_get_name (model)
                case default
                    call msg_fatal (" User-defined model and model in SLHA input file do not match.")
            end select
        case ("NMSSM")
            select case (char (model_get_name (model)))
                case ("NMSSM","NMSSM_CKM","NMSSM_Hgg")
                    model_name = model_get_name (model)
                case default
                    call msg_fatal (" User-defined model and model in SLHA input file do not match.")
            end select
        case default
            call msg_fatal (" SLHA model selection failure.")
    end select
    filename = model_name // ".mdl"
    model => null ()
    call model_list_read_model (model_name, filename, os_data, model)
    if (associated (model)) then
        call msg_message ("SLHA: Initializing model '" &
            // char (model_name) // "'")
    else
        call msg_fatal ("SLHA: Initialization failed for model '" &
            // char (model_name) // "'")
    end if
end subroutine slha_handle_MODSEL

```

Write a MODSEL block, based on the contents of the current model.

(SLHA: procedures) +=

```

subroutine slha_write_MODSEL (u, model, mssm_type)
    integer, intent(in) :: u
    type(model_t), intent(in), target :: model
    integer, intent(out) :: mssm_type
    type(var_list_t), pointer :: var_list
    integer :: model_id
    type(string_t) :: mtype_string
    var_list => model_get_var_list_ptr (model)
    if (var_list_exists (var_list, var_str ("mtype"))) then
        mssm_type = nint (var_list_get_rval (var_list, var_str ("mtype")))
    else
        call msg_error ("SLHA: parameter 'mtype' (SUSY breaking scheme) " &
            // "is unknown in current model, no SLHA output possible")
        mssm_type = -1
    return
end subroutine

```

```

end if
call write_block_header (u, "MODSEL", "SUSY model selection")
select case (mssm_type)
case (0); mtype_string = "Generic MSSM"
case (1); mtype_string = "SUGRA"
case (2); mtype_string = "GMSB"
case (3); mtype_string = "AMSB"
case default
    mtype_string = "unknown"
end select
call write_integer_parameter (u, 1, mssm_type, &
    "SUSY-breaking scheme: " // char (mtype_string))
select case (char (model_get_name (model)))
case ("MSSM"); model_id = MDL_MSSM
case ("NMSSM"); model_id = MDL_NMSSM
case default
    model_id = 0
end select
call write_integer_parameter (u, 3, model_id, &
    "SUSY model type: " // char (model_get_name (model)))
end subroutine slha_write_MODSEL

```

SMINPUTS

Read SM parameters and update the variable list accordingly. If a parameter is not defined in the block, we use the previous value from the model variable list. For the basic parameters we have to do a small recalculation, since SLHA uses the G_F - α - m_Z scheme, while WHIZARD derives them from G_F , m_W , and m_Z .

(*SLHA: procedures*) +=

```

subroutine slha_handle_SMINPUTS (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block
    real(default) :: alpha_em_i, GF, alphas, mZ
    real(default) :: ee, vv, cw_sw, cw2, mW
    real(default) :: mb, mtop, mtau
    type(var_list_t), pointer :: var_list
    var_list => model_get_var_list_ptr (model)
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("SMINPUTS"), required=.true.)
    if (.not. (associated (pn_block))) return
    alpha_em_i = &
        get_parameter_in_block (pn_block, 1, var_str ("alpha_em_i"), var_list)
    GF = get_parameter_in_block (pn_block, 2, var_str ("GF"), var_list)
    alphas = &
        get_parameter_in_block (pn_block, 3, var_str ("alphas"), var_list)
    mZ = get_parameter_in_block (pn_block, 4, var_str ("mZ"), var_list)
    mb = get_parameter_in_block (pn_block, 5, var_str ("mb"), var_list)
    mtop = get_parameter_in_block (pn_block, 6, var_str ("mtop"), var_list)
    mtau = get_parameter_in_block (pn_block, 7, var_str ("mtau"), var_list)
    ee = sqrt (4 * pi / alpha_em_i)
    vv = 1 / sqrt (sqrt (2._default) * GF)

```

```

cw_sw = ee * vv / (2 * mZ)
if (2*cw_sw <= 1) then
  cw2 = (1 + sqrt (1 - 4 * cw_sw**2)) / 2
  mW = mZ * sqrt (cw2)
  call var_list_set_real (var_list, var_str ("GF"), GF, .true.)
  call var_list_set_real (var_list, var_str ("mZ"), mZ, .true.)
  call var_list_set_real (var_list, var_str ("mW"), mW, .true.)
  call var_list_set_real (var_list, var_str ("mtau"), mtau, .true.)
  call var_list_set_real (var_list, var_str ("mb"), mb, .true.)
  call var_list_set_real (var_list, var_str ("mtop"), mtop, .true.)
  call var_list_set_real (var_list, var_str ("alphas"), alphas, .true.)
else
  call msg_fatal ("SLHA: Unphysical SM parameter values")
  return
end if
end subroutine slha_handle_SMINPUTS

```

Write a SMINPUTS block.

<SLHA: procedures>+≡

```

subroutine slha_write_SMINPUTS (u, model)
  integer, intent(in) :: u
  type(model_t), intent(in), target :: model
  type(var_list_t), pointer :: var_list
  integer :: model_id
  var_list => model_get_var_list_ptr (model)
  call write_block_header (u, "SMINPUTS", "SM input parameters")
  call write_real_data_item (u, 1, var_str ("alpha_em_i"), var_list, &
    "Inverse electromagnetic coupling alpha (Z pole)")
  call write_real_data_item (u, 2, var_str ("GF"), var_list, &
    "Fermi constant")
  call write_real_data_item (u, 3, var_str ("alphas"), var_list, &
    "Strong coupling alpha_s (Z pole)")
  call write_real_data_item (u, 4, var_str ("mZ"), var_list, &
    "Z mass")
  call write_real_data_item (u, 5, var_str ("mb"), var_list, &
    "b running mass (at mb)")
  call write_real_data_item (u, 6, var_str ("mtop"), var_list, &
    "top mass")
  call write_real_data_item (u, 7, var_str ("mtau"), var_list, &
    "tau mass")
end subroutine slha_write_SMINPUTS

```

MINPAR

The block of SUSY input parameters. They are accessible to WHIZARD, but they only get used when an external spectrum generator is invoked. The precise set of parameters depends on the type of SUSY breaking, which by itself is one of the parameters.

<SLHA: procedures>+≡

```

subroutine slha_handle_MINPAR (parse_tree, model, mssm_type)
  type(parse_tree_t), intent(in) :: parse_tree
  type(model_t), intent(inout), target :: model

```



```

integer, intent(in) :: mssm_type
type(var_list_t), pointer :: var_list
type(parse_node_t), pointer :: pn_block
var_list => model_get_var_list_ptr (model)
call var_list_set_real (var_list, &
    var_str ("mtype"), real(mssm_type, default), is_known=.true.)
pn_block => slha_get_block_ptr &
    (parse_tree, var_str ("MINPAR"), required=.true.)
select case (mssm_type)
case (MSSM_SUGRA)
    call set_data_item (pn_block, 1, var_str ("m_zero"), var_list)
    call set_data_item (pn_block, 2, var_str ("m_half"), var_list)
    call set_data_item (pn_block, 3, var_str ("tanb"), var_list)
    call set_data_item (pn_block, 4, var_str ("sgn_mu"), var_list)
    call set_data_item (pn_block, 5, var_str ("A0"), var_list)
case (MSSM_GMSB)
    call set_data_item (pn_block, 1, var_str ("Lambda"), var_list)
    call set_data_item (pn_block, 2, var_str ("M_mes"), var_list)
    call set_data_item (pn_block, 3, var_str ("tanb"), var_list)
    call set_data_item (pn_block, 4, var_str ("sgn_mu"), var_list)
    call set_data_item (pn_block, 5, var_str ("N_5"), var_list)
    call set_data_item (pn_block, 6, var_str ("c_grav"), var_list)
case (MSSM_AMSB)
    call set_data_item (pn_block, 1, var_str ("m_zero"), var_list)
    call set_data_item (pn_block, 2, var_str ("m_grav"), var_list)
    call set_data_item (pn_block, 3, var_str ("tanb"), var_list)
    call set_data_item (pn_block, 4, var_str ("sgn_mu"), var_list)
case default
    call set_data_item (pn_block, 3, var_str ("tanb"), var_list)
end select
end subroutine slha_handle_MINPAR

```

Write a MINPAR block as appropriate for the current model type.

(SLHA: procedures)+≡

```

subroutine slha_write_MINPAR (u, model, mssm_type)
integer, intent(in) :: u
type(model_t), intent(in), target :: model
integer, intent(in) :: mssm_type
type(var_list_t), pointer :: var_list
integer :: model_id
var_list => model_get_var_list_ptr (model)
call write_block_header (u, "MINPAR", "Basic SUSY input parameters")
select case (mssm_type)
case (MSSM_SUGRA)
    call write_real_data_item (u, 1, var_str ("m_zero"), var_list, &
        "Common scalar mass")
    call write_real_data_item (u, 2, var_str ("m_half"), var_list, &
        "Common gaugino mass")
    call write_real_data_item (u, 3, var_str ("tanb"), var_list, &
        "tan(beta)")
    call write_integer_data_item (u, 4, &
        var_str ("sgn_mu"), var_list, &
        "Sign of mu")
    call write_real_data_item (u, 5, var_str ("A0"), var_list, &

```

```

        "Common trilinear coupling")
case (MSSM_GMSB)
    call write_real_data_item (u, 1, var_str ("Lambda"), var_list, &
        "Soft-breaking scale")
    call write_real_data_item (u, 2, var_str ("M_mes"), var_list, &
        "Messenger scale")
    call write_real_data_item (u, 3, var_str ("tanb"), var_list, &
        "tan(beta)")
    call write_integer_data_item (u, 4, &
        var_str ("sgn_mu"), var_list, &
        "Sign of mu")
    call write_integer_data_item (u, 5, var_str ("N_5"), var_list, &
        "Messenger index")
    call write_real_data_item (u, 6, var_str ("c_grav"), var_list, &
        "Gravitino mass factor")
case (MSSM_AMSB)
    call write_real_data_item (u, 1, var_str ("m_zero"), var_list, &
        "Common scalar mass")
    call write_real_data_item (u, 2, var_str ("m_grav"), var_list, &
        "Gravitino mass")
    call write_real_data_item (u, 3, var_str ("tanb"), var_list, &
        "tan(beta)")
    call write_integer_data_item (u, 4, &
        var_str ("sgn_mu"), var_list, &
        "Sign of mu")
case default
    call write_real_data_item (u, 3, var_str ("tanb"), var_list, &
        "tan(beta)")
end select
end subroutine slha_write_MINPAR

```

Mass spectrum

Set masses. Since the particles are identified by PDG code, read the line and try to set the appropriate particle mass in the current model. At the end, update parameters, just in case the W or Z mass was included.

(*SLHA: procedures*) +=

```

subroutine slha_handle_MASS (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block, pn_data, pn_line, pn_code
    type(parse_node_t), pointer :: pn_mass
    integer :: pdg
    real(default) :: mass
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("MASS"), required=.true.)
    if (.not. (associated (pn_block))) return
    pn_data => parse_node_get_sub_ptr (pn_block, 4)
    do while (associated (pn_data))
        pn_line => parse_node_get_sub_ptr (pn_data, 2)
        pn_code => parse_node_get_sub_ptr (pn_line)
        if (associated (pn_code)) then

```

```

    pdg = get_integer_parameter (pn_code)
    pn_mass => parse_node_get_next_ptr (pn_code)
    if (associated (pn_mass)) then
        mass = get_real_parameter (pn_mass)
        call model_set_particle_mass (model, pdg, mass)
    else
        call msg_error ("SLHA: Block MASS: Missing mass value")
    end if
else
    call msg_error ("SLHA: Block MASS: Missing PDG code")
end if
pn_data => parse_node_get_next_ptr (pn_data)
end do
end subroutine slha_handle_MASS

```

Widths

Set widths. For each DECAY block, extract the header, read the PDG code and width, and try to set the appropriate particle width in the current model.

(SLHA: procedures)+≡

```

subroutine slha_handle_decays (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_decay, pn_decay_spec, pn_code, pn_width
    integer :: pdg
    real(default) :: width
    pn_decay => slha_get_first_decay_ptr (parse_tree)
    do while (associated (pn_decay))
        pn_decay_spec => parse_node_get_sub_ptr (pn_decay, 2)
        pn_code => parse_node_get_sub_ptr (pn_decay_spec)
        pdg = get_integer_parameter (pn_code)
        pn_width => parse_node_get_next_ptr (pn_code)
        width = get_real_parameter (pn_width)
        call model_set_particle_width (model, pdg, width)
        pn_decay => slha_get_next_decay_ptr (pn_decay)
    end do
end subroutine slha_handle_decays

```

Mixing matrices

Read mixing matrices. We can treat all matrices by a single procedure if we just know the block name, variable prefix, and matrix dimension. The matrix dimension must be less than 10. For the pseudoscalar Higgses in NMSSM-type models we need off-diagonal matrices, so we generalize the definition.

(SLHA: procedures)+≡

```

subroutine slha_handle_matrix_block &
    (parse_tree, block_name, var_prefix, dim1, dim2, model)
    type(parse_tree_t), intent(in) :: parse_tree
    character(*), intent(in) :: block_name, var_prefix
    integer, intent(in) :: dim1, dim2
    type(model_t), intent(inout), target :: model

```

```

type(parse_node_t), pointer :: pn_block
type(var_list_t), pointer :: var_list
integer :: i, j
character(len=len(var_prefix)+2) :: var_name
var_list => model_get_var_list_ptr (model)
pn_block => slha_get_block_ptr &
    (parse_tree, var_str (block_name), required=.false.)
if (.not. (associated (pn_block))) return
do i = 1, dim1
    do j = 1, dim2
        write (var_name, "(A,I1,I1)") var_prefix, i, j
        call set_matrix_element (pn_block, i, j, var_str (var_name), var_list)
    end do
end do
end subroutine slha_handle_matrix_block

```

Higgs data

Read the block ALPHA which holds just the Higgs mixing angle.

(SLHA: procedures)+≡

```

subroutine slha_handle_ALPHA (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block, pn_line, pn_data, pn_item
    type(var_list_t), pointer :: var_list
    real(default) :: al_h
    var_list => model_get_var_list_ptr (model)
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("ALPHA"), required=.false.)
    if (.not. (associated (pn_block))) return
    pn_data => parse_node_get_sub_ptr (pn_block, 4)
    pn_line => parse_node_get_sub_ptr (pn_data, 2)
    pn_item => parse_node_get_sub_ptr (pn_line)
    if (associated (pn_item)) then
        al_h = get_real_parameter (pn_item)
        call var_list_set_real (var_list, var_str ("al_h"), al_h, &
            is_known=.true., ignore=.true.)
    end if
end subroutine slha_handle_ALPHA

```

Read the block HMX for the Higgs mixing parameters

(SLHA: procedures)+≡

```

subroutine slha_handle_HMX (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block
    type(var_list_t), pointer :: var_list
    var_list => model_get_var_list_ptr (model)
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("HMX"), required=.false.)
    if (.not. (associated (pn_block))) return
    call set_data_item (pn_block, 1, var_str ("mu_h"), var_list)

```

```

        call set_data_item (pn_block, 2, var_str ("tanb_h"), var_list)
    end subroutine slha_handle_HMIX

```

Read the block NMSSMRUN for the specific NMSSM parameters

<SLHA: procedures>+≡

```

subroutine slha_handle_NMSSMRUN (parse_tree, model)
    type(parse_tree_t), intent(in) :: parse_tree
    type(model_t), intent(inout), target :: model
    type(parse_node_t), pointer :: pn_block
    type(var_list_t), pointer :: var_list
    var_list => model_get_var_list_ptr (model)
    pn_block => slha_get_block_ptr &
        (parse_tree, var_str ("NMSSMRUN"), required=.false.)
    if (.not. (associated (pn_block))) return
    call set_data_item (pn_block, 1, var_str ("ls"), var_list)
    call set_data_item (pn_block, 2, var_str ("ks"), var_list)
    call set_data_item (pn_block, 3, var_str ("a_ls"), var_list)
    call set_data_item (pn_block, 4, var_str ("a_ks"), var_list)
    call set_data_item (pn_block, 5, var_str ("nmu"), var_list)
end subroutine slha_handle_NMSSMRUN

```

15.0.5 Parser

Read a SLHA file from stream, including preprocessing, and make up a parse tree.

<SLHA: procedures>+≡

```

subroutine slha_parse_stream (stream, parse_tree)
    type(stream_t), intent(inout), target :: stream
    type(parse_tree_t), intent(out) :: parse_tree
    type(ifile_t) :: ifile
    type(lexer_t) :: lexer
    type(stream_t), target :: stream_tmp
    call slha_preprocess (stream, ifile)
    call stream_init (stream_tmp, ifile)
    call lexer_init_slha (lexer)
    call lexer_assign_stream (lexer, stream_tmp)
    call parse_tree_init (parse_tree, syntax_slha, lexer)
    call lexer_final (lexer)
    call stream_final (stream_tmp)
    call ifile_final (ifile)
end subroutine slha_parse_stream

```

Read a SLHA file chosen by name. Check first the current directory, then the directory where SUSY input files should be located.

<SLHA: procedures>+≡

```

subroutine slha_parse_file (file, os_data, parse_tree)
    type(string_t), intent(in) :: file
    type(os_data_t), intent(in) :: os_data
    type(parse_tree_t), intent(out) :: parse_tree
    logical :: exist
    type(string_t) :: filename

```

```

type(stream_t), target :: stream
call msg_message ("Reading SLHA input file '" // char (file) // "'")
filename = file
inquire (file=char(filename), exist=exist)
if (.not. exist) then
  filename = os_data%whizard_susypath // "/" // file
  inquire (file=char(filename), exist=exist)
  if (.not. exist) then
    call msg_fatal ("SLHA input file '" // char (file) // "' not found")
    return
  end if
end if
call stream_init (stream, char (filename))
call slha_parse_stream (stream, parse_tree)
call stream_final (stream)
end subroutine slha_parse_file

```

15.0.6 API

Read the SLHA file, parse it, and interpret the parse tree. The model parameters retrieved from the file will be inserted into the appropriate model, which is loaded and modified in the background. The pointer to this model is returned as the last argument.

```

<SLHA: public>+≡
  public :: slha_read_file

<SLHA: procedures>+≡
  subroutine slha_read_file (file, os_data, model, input, spectrum, decays)
    type(string_t), intent(in) :: file
    type(os_data_t), intent(in) :: os_data
    ! type(model_t), pointer, intent(out) :: model
    type(model_t), pointer, intent(inout) :: model
    logical, intent(in) :: input, spectrum, decays
    type(parse_tree_t) :: parse_tree
    call slha_parse_file (file, os_data, parse_tree)
    if (associated (parse_tree_get_root_ptr (parse_tree))) then
      call slha_interpret_parse_tree &
        (parse_tree, os_data, model, input, spectrum, decays)
      call parse_tree_final (parse_tree)
      call model_parameters_update (model)
    end if
  end subroutine slha_read_file

```

Write the SLHA contents, as far as possible, to external file.

```

<SLHA: public>+≡
  public :: slha_write_file

<SLHA: procedures>+≡
  subroutine slha_write_file (file, model, input, spectrum, decays)
    type(string_t), intent(in) :: file
    type(model_t), target, intent(in) :: model
    logical, intent(in) :: input, spectrum, decays

```

```

integer :: mssm_type
integer :: u
u = free_unit ()
call msg_message ("Writing SLHA output file '" // char (file) // "'")
open (unit=u, file=char(file), action="write", status="replace")
write (u, "(A)")  "# SUSY Les Houches Accord"
write (u, "(A)")  "# Output generated by " // trim (VERSION_STRING)
call slha_write_MODSEL (u, model, mssm_type)
if (input) then
    call slha_write_SMINPUTS (u, model)
    call slha_write_MINPAR (u, model, mssm_type)
end if
if (spectrum) then
    call msg_bug ("SLHA: spectrum output not supported yet")
end if
if (decays) then
    call msg_bug ("SLHA: decays output not supported yet")
end if
close (u)
end subroutine slha_write_file

```

15.0.7 Test

(SLHA: public)+≡

```
public :: slha_test
```

(SLHA: procedures)+≡

```

subroutine slha_test ()
    type(os_data_t), pointer :: os_data => null ()
    type(parse_tree_t), pointer :: parse_tree => null ()
    integer :: unit
    character(*), parameter :: file_test = "slha_test.out"
    character(*), parameter :: file_slha = "slha_test.dat"
    type(model_t), pointer :: model => null ()
    allocate (os_data)
    allocate (parse_tree)
    call os_data_init (os_data)
    call model_list_read_model (var_str("MSSM"), var_str("MSSM.mdl"), os_data, model)
    call slha_parse_file (var_str ("spslap_decays.slha"), os_data, parse_tree)
    call msg_message ("Writing parse tree to '" // file_test // "'")
    unit = free_unit ()
    open (unit=unit, file=file_test, action="write", status="replace")
    call parse_tree_write (parse_tree, unit)
    call slha_interpret_parse_tree (parse_tree, os_data, model, &
        input=.true., spectrum=.true., decays=.true.)
    call parse_tree_final (parse_tree)
    call var_list_write (model_get_var_list_ptr (model), only_type=V_REAL)
    call msg_message ("Writing SLHA output to '" // file_slha // "'")
    call slha_write_file (var_str (file_slha), model, input=.true., &
        spectrum=.false., decays=.false.)
    call parse_tree_final (parse_tree)
    deallocate (parse_tree)
    deallocate (os_data)

```

```
end subroutine slha_test
```


Chapter 16

Integration and simulation

This layer of modules is just below the top-level API. We lay out specific data types for integration and simulation and implement the corresponding algorithms as methods acting on them. This helps to keep the command-level implementation concise and simple.

16.1 Iterations

This module defines a container for the list of iterations and calls, to be submitted to integration.

```
<iterations.f90>≡  
  <File header>  
  
  module iterations  
  
    <Use strings>  
    <Use file utils>  
    use limits, only: ITERATIONS_DEFAULT_LIST_SIZE !NODEP!  
    use diagnostics !NODEP!  
    use processes  
  
    <Standard module head>  
  
    <Iterations: public>  
  
    <Iterations: types>  
  
    <Iterations: interfaces>  
  
    contains  
  
    <Iterations: procedures>  
  
  end module iterations
```

16.1.1 The iterations list

Each integration pass has a number of iterations and a number of calls per iteration. The last pass produces the end result; the previous passes are used for adaptation.

The flags `adapt_grid` and `adapt_weight` are used only if `custom_adaptation` is set. Otherwise, default settings are used that depend on the integration pass.

```
<Iterations: types>≡
  type :: iterations_spec_t
  private
    integer :: n_it = 0
    integer :: n_calls = 0
    logical :: custom_adaptation = .false.
    logical :: adapt_grids = .false.
    logical :: adapt_weights = .false.
  end type iterations_spec_t
```

We build up a list of iterations.

```
<Iterations: public>≡
  public :: iterations_list_t

<Iterations: types>+≡
  type :: iterations_list_t
  private
    integer :: n_pass = 0
    type(iterations_spec_t), dimension(:), allocatable :: pass
  end type iterations_list_t

<Iterations: public>+≡
  public :: iterations_list_init

<Iterations: procedures>≡
  subroutine iterations_list_init (it_list, n_it, n_calls, adapt, adapt_code)
    type(iterations_list_t), intent(inout) :: it_list
    integer, dimension(:), intent(in) :: n_it, n_calls
    logical, dimension(:), intent(in), optional :: adapt
    type(string_t), dimension(:), intent(in), optional :: adapt_code
    it_list%n_pass = size (n_it)
    if (allocated (it_list%pass)) deallocate (it_list%pass)
    allocate (it_list%pass (it_list%n_pass))
    it_list%pass%n_it = n_it
    it_list%pass%n_calls = n_calls
    if (present (adapt)) then
      it_list%pass%custom_adaptation = adapt
      if (any (verify (adapt_code, "wg") /= 0)) then
        call msg_error ("iteration specification: " &
          // "adaptation code letters must be 'w' or 'g'")
      end if
      it_list%pass%adapt_grids = scan (adapt_code, "g") /= 0
      it_list%pass%adapt_weights = scan (adapt_code, "w") /= 0
    end if
  end subroutine iterations_list_init
```

Fill all zero entries by corresponding entries from a default iterations list:

```

<Iterations: public>+≡
    public :: iterations_list_complete

<Iterations: procedures>+≡
    subroutine iterations_list_complete (it_list, it_list_default)
        type(iterations_list_t), intent(inout) :: it_list
        type(iterations_list_t), intent(in) :: it_list_default
        if (it_list%n_pass >= 1) then
            if (it_list%pass(1)%n_it == 0) &
                it_list%pass(1)%n_it = it_list_default%pass(1)%n_it
            if (it_list%pass(1)%n_calls == 0) &
                it_list%pass(1)%n_calls = it_list_default%pass(1)%n_calls
        end if
        if (it_list%n_pass >= 2) then
            where (it_list%pass%n_it == 0) &
                it_list%pass%n_it = it_list_default%pass(2)%n_it
            where (it_list%pass%n_calls == 0) &
                it_list%pass%n_calls = it_list_default%pass(2)%n_calls
        end if
    end subroutine iterations_list_complete

```

```

<Iterations: public>+≡
    public :: iterations_list_clear

<Iterations: procedures>+≡
    subroutine iterations_list_clear (it_list)
        type(iterations_list_t), intent(inout) :: it_list
        it_list%n_pass = 0
        deallocate (it_list%pass)
    end subroutine iterations_list_clear

```

Write the list of iterations as a message.

```

<Iterations: public>+≡
    public :: iterations_list_write

<Iterations: procedures>+≡
    subroutine iterations_list_write (it_list, unit)
        type(iterations_list_t), intent(in) :: it_list
        integer, intent(in), optional :: unit
        type(string_t) :: buffer
        character(30) :: ibuf
        integer :: i
        buffer = "iterations = "
        if (it_list%n_pass > 0) then
            do i = 1, it_list%n_pass
                if (i > 1) buffer = buffer // ", "
                write (ibuf, '(I0,':',I0)') &
                    it_list%pass(i)%n_it, it_list%pass(i)%n_calls
                buffer = buffer // trim (ibuf)
                if (it_list%pass(i)%custom_adaptation) then
                    buffer = buffer // ' "'
                    if (it_list%pass(i)%adapt_grids) buffer = buffer // "g"
                    if (it_list%pass(i)%adapt_weights) buffer = buffer // "w"

```

```

        buffer = buffer // '''
    end if
end do
else
    buffer = buffer // "[undefined]"
end if
call msg_message (char (buffer), unit)
end subroutine iterations_list_write

```

16.1.2 Tools

Transform the iterations list into arrays that indicate pass index and number of calls for each iteration.

<Iterations: public>+≡

```

public :: iterations_list_get_pass_array
public :: iterations_list_get_n_calls_array

```

<Iterations: procedures>+≡

```

function iterations_list_get_pass_array (it_list) result (pass)
    integer, dimension(:), allocatable :: pass
    type(iterations_list_t), intent(in) :: it_list
    integer :: it, i
    allocate (pass (sum (it_list%pass%n_it)))
    it = 0
    do i = 1, it_list%n_pass
        pass(it+1 : it+it_list%pass(i)%n_it) = i
        it = it + it_list%pass(i)%n_it
    end do
end function iterations_list_get_pass_array

function iterations_list_get_n_calls_array (it_list) result (n_calls)
    integer, dimension(:), allocatable :: n_calls
    type(iterations_list_t), intent(in) :: it_list
    integer :: it, i
    allocate (n_calls (sum (it_list%pass%n_it)))
    it = 0
    do i = 1, it_list%n_pass
        n_calls(it+1 : it+it_list%pass(i)%n_it) = it_list%pass(i)%n_calls
        it = it + it_list%pass(i)%n_it
    end do
end function iterations_list_get_n_calls_array

```

Return the total number of passes.

<Iterations: public>+≡

```

public :: iterations_list_get_n_pass

```

<Iterations: procedures>+≡

```

function iterations_list_get_n_pass (it_list) result (n_pass)
    integer :: n_pass
    type(iterations_list_t), intent(in) :: it_list
    n_pass = it_list%n_pass
end function iterations_list_get_n_pass

```

Return the number of calls for a specific pass.

```
<Iterations: public>+≡
    public :: iterations_list_get_n_calls

<Iterations: procedures>+≡
    function iterations_list_get_n_calls (it_list, pass) result (n_calls)
        integer :: n_calls
        type(iterations_list_t), intent(in) :: it_list
        integer, intent(in) :: pass
        if (pass <= it_list%n_pass) then
            n_calls = it_list%pass(pass)%n_calls
        else
            n_calls = 0
        end if
    end function iterations_list_get_n_calls
```

Get the adaptation mode (automatic/custom) and, for custom adaptation, the flags for a specific pass.

```
<Iterations: public>+≡
    public :: iterations_list_has_custom_adaptation
    public :: iterations_list_adapt_grids
    public :: iterations_list_adapt_weights

<Iterations: procedures>+≡
    function iterations_list_has_custom_adaptation (it_list, pass) result (flag)
        logical :: flag
        type(iterations_list_t), intent(in) :: it_list
        integer, intent(in) :: pass
        if (pass <= it_list%n_pass) then
            flag = it_list%pass(pass)%custom_adaptation
        else
            flag = .false.
        end if
    end function iterations_list_has_custom_adaptation

    function iterations_list_adapt_grids (it_list, pass) result (flag)
        logical :: flag
        type(iterations_list_t), intent(in) :: it_list
        integer, intent(in) :: pass
        if (pass <= it_list%n_pass) then
            flag = it_list%pass(pass)%adapt_grids
        else
            flag = .false.
        end if
    end function iterations_list_adapt_grids

    function iterations_list_adapt_weights (it_list, pass) result (flag)
        logical :: flag
        type(iterations_list_t), intent(in) :: it_list
        integer, intent(in) :: pass
        if (pass <= it_list%n_pass) then
            flag = it_list%pass(pass)%adapt_weights
        else
            flag = .false.
        end if
    end function iterations_list_adapt_weights
```

```

        end if
    end function iterations_list_adapt_weights

```

Return the total number of iterations / the iterations for a specific pass.

<Iterations: public>+≡

```

    public :: iterations_list_get_n_it

```

<Iterations: interfaces>≡

```

    interface iterations_list_get_n_it
        module procedure iterations_list_get_n_it_tot
        module procedure iterations_list_get_n_it_pass
    end interface

```

<Iterations: procedures>+≡

```

    function iterations_list_get_n_it_tot (it_list) result (n_it)
        integer :: n_it
        type(iterations_list_t), intent(in) :: it_list
        n_it = sum (it_list%pass%n_it)
    end function iterations_list_get_n_it_tot

```

```

    function iterations_list_get_n_it_pass (it_list, pass) result (n_it)
        integer :: n_it
        type(iterations_list_t), intent(in) :: it_list
        integer, intent(in) :: pass
        if (pass <= it_list%n_pass) then
            n_it = it_list%pass(pass)%n_it
        else
            n_it = 0
        end if
    end function iterations_list_get_n_it_pass

```

This routine corrects for a number of calls that is too low.

<Iterations: public>+≡

```

    public :: iterations_list_adjust_n_calls

```

<Iterations: procedures>+≡

```

    subroutine iterations_list_adjust_n_calls (it_list, process, grid_parameters)
        type(iterations_list_t), intent(inout), target :: it_list
        type(process_t), intent(in) :: process
        type(grid_parameters_t), intent(in) :: grid_parameters
        type(iterations_spec_t), pointer :: it_spec
        integer :: n_calls, pass
        logical :: changed
        changed = .false.
        do pass = 1, it_list%n_pass
            it_spec => it_list%pass(pass)
            n_calls = max (it_spec%n_calls, &
                process_get_n_channels (process) &
                * grid_parameters%min_calls_per_channel)
            if (n_calls /= it_spec%n_calls) then
                it_spec%n_calls = n_calls
                changed = .true.
            end if
        end do
    end subroutine

```

```

end do
if (changed) then
  write (msg_buffer, "(A,I0)") "Process '" &
    // char (process_get_id (process)) // "' : " &
    // "resetting n_calls to ", n_calls
  call msg_warning ()
end if
end subroutine iterations_list_adjust_n_calls

```

Allocate the default iterations lists and fill with some sensible values. This is implemented as a pointer since it is not intended to be modified by the user; the local RT dataset will thus contain another pointer to the same list, not a copy.

```

<Limits: public parameters>+≡
  integer, parameter, public :: ITERATIONS_DEFAULT_LIST_SIZE = 7

<Iterations: public>+≡
  public :: iterations_lists_init_default

<Iterations: procedures>+≡
  subroutine iterations_lists_init_default (it_list)
    type(iterations_list_t), dimension(:), pointer :: it_list
    allocate (it_list (ITERATIONS_DEFAULT_LIST_SIZE))
    call iterations_list_init (it_list(1), (/ 1 /), (/ 100 /))
    call iterations_list_init (it_list(2), (/ 3, 3 /), (/ 1000, 10000 /))
    call iterations_list_init (it_list(3), (/ 5, 3 /), (/ 5000, 10000 /))
    call iterations_list_init (it_list(4), (/ 10, 5 /), (/ 10000, 20000 /))
    call iterations_list_init (it_list(5), (/ 10, 5 /), (/ 20000, 50000 /))
    call iterations_list_init (it_list(6), (/ 15, 5 /), (/ 50000, 100000 /))
    call iterations_list_init (it_list(7), (/ 20, 5 /), (/ 50000, 200000 /))
  end subroutine iterations_lists_init_default

```

16.2 Beam polarization

Beam polarization is encapsulated in a designated type and only converted into a density matrix when the beams are actually initialized — the flavor information necessary for initialization is not available earlier.

```

<beam_polarizations.f90>≡
  <File header>

  module beam_polarizations

    <Use kinds>
    <Use strings>
    <Use file utils>
    use diagnostics !NODEP!
    use flavors
    use polarizations

    <Standard module head>

```

```

    <Beam polarizations: public>

    <Beam polarizations: parameters>

    <Beam polarizations: types>

contains

    <Beam polarizations: procedures>

end module beam_polarizations

```

16.2.1 Parameters and type definition

```

<Beam polarizations: public>≡
    public :: BP_NONE, BP_CIRC, BP_TRANS, BP_LONG, BP_AXIS, BP_DIAG, BP_DENSITY
    public :: BP_TRIVIAL
    public :: beam_polarization_t

<Beam polarizations: parameters>≡
    integer, parameter :: &
        BP_NONE = 0, BP_CIRC = 1, BP_TRANS = 2, BP_LONG = 3, BP_AXIS = 4, &
        BP_DIAG = 5, BP_DENSITY = 6, BP_TRIVIAL = 7

<Beam polarizations: types>≡
    type :: beam_polarization_t
    private
    integer :: type = BP_NONE
    real(default) :: fraction
    real(default) :: theta
    real(default) :: phi
    real(default) :: d
    complex(default) :: nd
    integer, dimension(:), allocatable :: hels
    real(default), dimension(:), allocatable :: fractions
end type beam_polarization_t

```

16.2.2 Constructors

The type is filled by dedicated constructors:

```

<Beam polarizations: public>+≡
    public :: beam_polarization_init_none
    public :: beam_polarization_init_trivial
    public :: beam_polarization_init_circ
    public :: beam_polarization_init_trans
    public :: beam_polarization_init_long
    public :: beam_polarization_init_axis
    public :: beam_polarization_init_diag
    public :: beam_polarization_init_density
    public :: beam_polarization_final

```



```

(Beam polarizations: procedures)≡
  subroutine beam_polarization_init_none (bp)
    type(beam_polarization_t), intent(inout) :: bp
    bp%type = BP_NONE
  end subroutine beam_polarization_init_none

  subroutine beam_polarization_init_trivial (bp)
    type(beam_polarization_t), intent(inout) :: bp
    bp%type = BP_TRIVIAL
  end subroutine beam_polarization_init_trivial

  subroutine beam_polarization_init_circ (bp, fraction)
    type(beam_polarization_t), intent(inout) :: bp
    real(default), intent(in) :: fraction
    bp%type = BP_CIRC
    bp%fraction = fraction
  end subroutine beam_polarization_init_circ

  subroutine beam_polarization_init_trans (bp, fraction, phi)
    type(beam_polarization_t), intent(inout) :: bp
    real(default), intent(in) :: fraction, phi
    bp%type = BP_TRANS
    bp%fraction = fraction
    bp%phi = phi
  end subroutine beam_polarization_init_trans

  subroutine beam_polarization_init_long (bp, fraction)
    type(beam_polarization_t), intent(inout) :: bp
    real(default), intent(in) :: fraction
    bp%type = BP_LONG
    bp%fraction = fraction
  end subroutine beam_polarization_init_long

  subroutine beam_polarization_init_axis (bp, fraction, theta, phi)
    type(beam_polarization_t), intent(inout) :: bp
    real(default), intent(in) :: fraction, theta, phi
    bp%type = BP_AXIS
    bp%fraction = fraction
    bp%theta = theta
    bp%phi = phi
  end subroutine beam_polarization_init_axis

  subroutine beam_polarization_init_diag (bp, hels, fracs)
    type(beam_polarization_t), intent(inout) :: bp
    integer, dimension(:), intent(in) :: hels
    real(default), dimension(:), intent(in) :: fracs
    bp%type = BP_DIAG
    allocate (bp%hels(size (hels)))
    allocate (bp%fractions(size (fracs)))
    bp%hels = hels
    bp%fractions = fracs
  end subroutine beam_polarization_init_diag

  subroutine beam_polarization_init_density (bp, d, nd)

```

```

    type(beam_polarization_t), intent(inout) :: bp
    real(default), intent(in) :: d
    complex(default), intent(in) :: nd
    bp%type = BP_DENSITY
    bp%d = d
    bp%nd = nd
end subroutine beam_polarization_init_density

subroutine beam_polarization_final (bp)
    type(beam_polarization_t), intent(inout) :: bp
    if (allocated (bp%hels)) deallocate (bp%hels)
    if (allocated (bp%fractions)) deallocate (bp%fractions)
end subroutine beam_polarization_final

```

16.2.3 Tools

Together with the necessary flavor information, `beam_polarization_t` can be promoted to `polarization_t`

```

<Beam polarizations: public>+≡
    public :: beam_polarization2polarization

<Beam polarizations: procedures>+≡
    function beam_polarization2polarization (bp, flv, decay) result (pol)
        type(beam_polarization_t), intent(in) :: bp
        type(flavor_t), intent(in) :: flv
        logical, optional, intent(in) :: decay
        type(polarization_t) :: pol
        logical :: fail
        real(default), dimension(:), allocatable :: frac_vector
        integer :: i, j, mult
        type(string_t) :: msg
        if (flavor_get_multiplicity (flv) == 1) then
            select case (bp%type)
            case (BP_NONE, BP_TRIVIAL)
            case default
                if (flavor_is_left_handed (flv)) then
                    msg = "left-handed"
                elseif (flavor_is_right_handed (flv)) then
                    msg = "right-handed"
                else
                    msg = "scalar"
                end if
                call msg_error (char (msg) // " particle '" &
                    // char (flavor_get_name (flv)) &
                    // "' cannot be polarized - ignoring polarization")
                call emergency_unpolarized
                return
            end select
        end if
        select case (bp%type)
        case (BP_NONE)
            call polarization_init_unpolarized (pol, flv)
        case (BP_TRIVIAL)

```

```

        call polarization_init_trivial (pol, flv)
case (BP_CIRC)
    if ((bp%fraction <= 1) .and. (bp%fraction >= -1)) then
        call polarization_init_circular (pol, flv, bp%fraction)
    else
        call msg_error ( &
            "circular polarization: 'fraction' must be within [-1; 1] - " &
            // "ignoring polarization")
        call emergency_unpolarized
    end if
case (BP_TRANS)
    if ((bp%fraction <= 1) .and. (bp%fraction >= -1)) then
        call polarization_init_transversal (pol, flv, bp%phi, bp%fraction)
    else
        call msg_error ( &
            "transverse polarization: 'fraction' must be within [-1; 1] - " &
            // "ignoring polarization")
        call emergency_unpolarized
    end if
case (BP_LONG)
    if ((bp%fraction > 1) .or. (bp%fraction < 0)) then
        call msg_error ( &
            "longitudinal polarization: 'fraction' must be within [0; 1]" &
            // " - ignoring polarization");
        call emergency_unpolarized
    elseif (mod (flavor_get_multiplicity (flv), 2) == 0) then
        call msg_error ( &
            "longitudinal polarization is only available for massive " &
            // " bosons - ignoring polarization")
        call emergency_unpolarized
    else
        call polarization_init_longitudinal (pol, flv, bp%fraction)
    end if
case (BP_AXIS)
    if ((bp%fraction <= 1) .and. (bp%fraction >= -1)) then
        call polarization_init_angles (pol, flv, bp%fraction, bp%theta, &
            bp%phi)
    else
        call msg_error ( &
            "axial polarization: 'fraction' must be within [-1; 1] - " &
            // "ignoring polarization")
        call emergency_unpolarized
    end if
case (BP_DENSITY)
    if ((bp%d <= 1) .and. (bp%d >= 0) .and. (abs (bp%nd) <= 0.5)) then
        call polarization_init_axis (pol, flv, &
            (/real (bp%nd, default), (-1.) * aimag (bp%nd), 2. * bp%d - 1./))
    else
        call msg_error ( &
            "density matrix polarization: 'a' must be within [0; 1], |b| " &
            // "within [0; 0.5] - ignoring polarization")
        call emergency_unpolarized
    end if
case (BP_DIAG)

```

```

fail = .false.
mult = flavor_get_multiplicity (flv)
allocate (frac_vector (mult))
frac_vector = 0
if (minval (bp%fractions) < 0) then
  call msg_error ( &
    "diagonal polarization: negative fractions are not allowed " &
    // "- ignoring polarization")
  fail = .true.
else
select case (mult)
  case (1)
    call msg_bug ( &
      "beam_polarization2polarization: invalid multiplicity")
  case (2)
    if ((size (bp%hels) <= 2) .and. all (abs (bp%hels) == 1)) then
      frac_vector = 0
      do i = 1, size(bp%hels)
        frac_vector((bp%hels(i) + 1) / 2 + 1) = bp%fractions(i)
      end do
    else
      call msg_error ( &
        "diagonal polarization: the only admissible helicities " &
        // "for particle '" // char (flavor_get_name (flv)) &
        // "' are" // " -1 and 1 - ignoring polarization")
      fail = .true.
    end if
  case default
    if (maxval (abs (bp%hels)) <= mult / 2) then
      if (mod (mult, 2) == 0) then
        if (minval (abs (bp%hels)) == 0) then
          call msg_error ( &
            "diagonal polarization: helicity 0 not allowed " &
            // "for particle '" // char (flavor_get_name (flv)) &
            // "' - ignoring polarization")
          fail = .true.
        else
          do i = 1, size (bp%hels)
            if (bp%hels(i) < 0) then
              j = bp%hels(i) + mult / 2 + 1
            else
              j = bp%hels(i) + mult / 2
            end if
            frac_vector(j) = bp%fractions(i)
          end do
        end if
      else
        do i = 1, size (bp%hels)
          j = bp%hels(i) + mult / 2 + 1
          frac_vector(j) = bp%fractions(i)
        end do
      end if
    else
      call msg_error ( &

```

```

        "diagonal polarization: helicity exceeds admissible " &
        // "range for particle '" // char (flavor_get_name (flv)) &
        // "' - ignoring polarization")
        fail = .true.
    end if
end select
end if
if (fail) then
    call emergency_unpolarized
else
    if (sum (frac_vector) /= 1) &
        call msg_warning ( &
            "diagonal polarization: fractions will be normalized to 1")
        call polarization_init_diagonal (pol, flv, frac_vector)
    end if
    deallocate (frac_vector)
end select

contains

subroutine emergency_unpolarized
    logical :: is_decay
    if (present (decay)) then
        is_decay = decay
    else
        is_decay = .false.
    end if
    if (is_decay) then
        call polarization_init_trivial (pol, flv)
    else
        call polarization_init_unpolarized (pol, flv)
    end if
end subroutine emergency_unpolarized

end function beam_polarization2polarization

```

Writing.

```

<Beam polarizations: public>+≡
    public :: beam_polarization_write

<Beam polarizations: procedures>+≡
    subroutine beam_polarization_write (bp, unit, indent)
        type(beam_polarization_t), intent(in) :: bp
        integer, intent(in), optional :: unit, indent
        integer :: u, i
        type(string_t), dimension(:), allocatable :: msgs
        type(string_t) :: header, is
        u = output_unit (unit)
        if (u < 0) return
        select case (bp%type)
            case (BP_NONE, BP_TRIVIAL)
                call printer ("none")
            case (BP_CIRC)
                call printer ("circular (fraction):")

```

```

        call printer ("    fraction: " // real2char (bp%fraction))
    case (BP_TRANS)
        call printer ("transverse (fraction, phi):")
        call printer ("    fraction: " // real2char (bp%fraction))
        call printer ("    phi      : " // real2char (bp%phi))
    case (BP_AXIS)
        call printer ("axis (fraction, theta, phi):")
        call printer ("    fraction: " // real2char (bp%fraction))
        call printer ("    theta  : " // real2char (bp%theta))
        call printer ("    phi    : " // real2char (bp%phi))
    case (BP_LONG)
        call printer ("longitudinal (fraction):")
        call printer ("    fraction: " // real2char (bp%fraction))
    case (BP_DENSITY)
        call printer ("density_matrix (a, b):")
        call printer ("    a: " // real2char (bp%d))
        call printer ("    b: " // char (cplx2string (bp%nd)))
    case (BP_DIAG)
        allocate (msgs(size (bp%fractions)))
        header = "diagonal_density ("
        do i = 1, size (msgs)
            is = int2string (i)
            if (i > 1) header = header // ", "
            header = header // "h" // is // ":f" // is
            msgs (i) = "h" // is // ": " // int2string (bp%hels(i)) &
                // ", f" // is // ": " // real2string (bp%fractions(i))
        end do
        call printer (char (header) // ")")
        do i = 1, size (msgs)
            call printer ("    " // char (msgs(i)))
        end do
        deallocate (msgs)
    case default
        call msg_bug ("beam_polarization_write: illegal polarization type")
end select
flush (u)

contains

subroutine printer (s)
    character(*), intent(in) :: s
    if (present (indent)) write (u, '(A)', advance="no") &
        repeat (" ", indent)
    write (u, '(1x,A)') s
end subroutine printer

end subroutine beam_polarization_write

```

16.3 Structure function configuration

This module provides data types and methods for configuring structure functions and parameters. It links the user interface with the structure-function

```

setup.
<strfun_config.f90>≡
  <File header>

  module strfun_config

    <Use kinds>
    <Use strings>
    <Use file utils>
    use diagnostics !NODEP!
    use tao_random_numbers !NODEP!
    use pdf_builtin !NODEP!
    use md5
    use models
    use flavors
    use sf_isr
    use sf_epa
    use sf_ewa
    use sf_circe1
    use sf_circe2
    use sf_escan
    use sf_beam_events
    use sf_lhapdf
    use sf_pdf_builtin
    use sf_user
    use strfun
    use processes

    <Standard module head>

    <Strfun config: public>

    <Strfun config: types>

    contains

    <Strfun config: procedures>

  end module strfun_config

```

16.3.1 Structure function codes

Re-export them from the lower-level module:

```

<Strfun config: public>≡
  public :: STRF_NONE
  public :: STRF_LHAPDF
  public :: STRF_ISR
  public :: STRF_EPA
  public :: STRF_EWA
  public :: STRF_CIRCE1
  public :: STRF_CIRCE2
  public :: STRF_ESCAN
  public :: STRF_BEVT

```

```

public :: STRF_PDF_BUILTIN
public :: STRF_USER

```

16.3.2 Mapping configuration

A mapping is defined for a particular set of x -parameters. It has a type and a set of real parameters whose meaning depends on the type.

```

(Strfun config: types)≡
  type :: sf_mapping_t
  private
    integer, dimension(:), allocatable :: index
    integer :: type = SFM_NONE
    real(default), dimension(:), allocatable :: par
  end type sf_mapping_t

```

Output

```

(Strfun config: procedures)≡
  subroutine sf_mapping_write (sf_mapping, unit)
    type(sf_mapping_t), intent(in) :: sf_mapping
    integer, intent(in), optional :: unit
    integer :: u
    u = output_unit (unit); if (u < 0) return
    write (u, "(1x,A,I0,I0(' , #',I0))") "Mapping for parameters #", &
      sf_mapping%index
    select case (sf_mapping%type)
    case (SFM_NONE); write (u, "(3x,A)") "[none]"
    case (SFM_PAIR); write (u, "(3x,A)") "Pair mapping"
    end select
    if (allocated (sf_mapping%par)) then
      write (u, "(3x,A)", advance="no") "Parameters = "
      write (u, *) sf_mapping%par
    end if
  end subroutine sf_mapping_write

```

16.3.3 Single structure function

This type holds the configuration of a structure function or function pair.

```

(Strfun config: public)+≡
  public :: sf_data_t

(Strfun config: types)+≡
  type :: sf_data_t
  private
    integer :: type = STRF_NONE
    logical, dimension(2) :: affects_beam = .false.
    integer :: n_parameters = 0
    type(lhapdf_data_t) :: lhpdf
    type(pdf_builtin_data_t) :: pdf_builtin
    type(isr_data_t) :: isr
    type(epa_data_t) :: epa
    type(ewa_data_t) :: ewa

```



```

type(circe1_data_t) :: circe1
type(circe2_data_t) :: circe2
type(escan_data_t) :: escan
type(beam_events_data_t) :: beam_events
type(sf_user_data_t) :: user
logical :: has_mapping = .false.
type(sf_mapping_t) :: mapping
type(sf_data_t), pointer :: next => null ()
end type sf_data_t

```

Output:

<Strfun config: procedures>+≡

```

subroutine sf_data_write (sf_data, unit, md5, beam_fmt)
  type(sf_data_t), intent(in) :: sf_data
  integer, intent(in), optional :: unit
  integer :: u
  logical, intent(in), optional :: md5
  logical, intent(in), optional :: beam_fmt
  u = output_unit (unit); if (u < 0) return
  write (u, "(A)", advance="no") "Structure function"
  if (all (sf_data%affects_beam)) then
    write (u, "(1x,A)") "(both beams)"
  else if (sf_data%affects_beam(1)) then
    write (u, "(1x,A)") "(beam 1)"
  else if (sf_data%affects_beam(2)) then
    write (u, "(1x,A)") "(beam 2)"
  else
    write (u, "(1x,A)") "(no beams)"
  end if
  select case (sf_data%type)
  case (STRF_NONE)
    write (u, "(1x,A)") "[none]"
  case (STRF_LHAPDF)
    call lhpdf_data_write (sf_data%lhpdf, unit, md5, beam_fmt)
  case (STRF_PDF_BUILTIN)
    call pdf_builtin_data_write (sf_data%pdf_builtin, unit, md5, beam_fmt)
  case (STRF_ISR)
    call isr_data_write (sf_data%isr, unit, md5)
  case (STRF_EPA)
    call epa_data_write (sf_data%epa, unit, md5)
  case (STRF_EWA)
    call ewa_data_write (sf_data%ewa, unit, md5)
  case (STRF_CIRCE1)
    call circe1_data_write (sf_data%circe1, unit, md5)
  case (STRF_CIRCE2)
    call circe2_data_write (sf_data%circe2, unit, md5)
  case (STRF_ESCAN)
    call escan_data_write (sf_data%escan, unit, md5)
  case (STRF_BEVT)
    call beam_events_data_write (sf_data%beam_events, unit, md5)
  case (STRF_USER)
    call sf_user_data_write (sf_data%user, unit, md5)
  end select

```

```

write (u, *) "n_parameters = ", sf_data%n_parameters
if (sf_data%has_mapping) then
  call sf_mapping_write (sf_data%mapping, unit)
end if
end subroutine sf_data_write

```

Retrieving contents:

```

<Strfun config: public>+≡
  public :: sf_data_affects_beam
  public :: sf_data_get_n_parameters

<Strfun config: procedures>+≡
  function sf_data_affects_beam (sf_data) result (affects_beam)
    logical, dimension(2) :: affects_beam
    type(sf_data_t), intent(in) :: sf_data
    affects_beam = sf_data%affects_beam
  end function sf_data_affects_beam

  function sf_data_get_n_parameters (sf_data) result (n_parameters)
    integer :: n_parameters
    type(sf_data_t), intent(in) :: sf_data
    n_parameters = sf_data%n_parameters
  end function sf_data_get_n_parameters

```

Return pointers to data blocks (QCD-related only)

```

<Strfun config: procedures>+≡
  function sf_data_get_lhapdf_data_ptr (sf_data) result (lhpdf_data)
    type(sf_data_t), intent(in), target :: sf_data
    type(lhapdf_data_t), pointer :: lhpdf_data
    select case (sf_data%type)
    case (STRF_LHAPDF)
      lhpdf_data => sf_data%lhpdf
    case default
      lhpdf_data => null ()
    end select
  end function sf_data_get_lhapdf_data_ptr

  function sf_data_get_pdf_builtin_data_ptr (sf_data) result (pdf_builtin_data)
    type(sf_data_t), intent(in), target :: sf_data
    type(pdf_builtin_data_t), pointer :: pdf_builtin_data
    select case (sf_data%type)
    case (STRF_PDF_BUILTIN)
      pdf_builtin_data => sf_data%pdf_builtin
    case default
      pdf_builtin_data => null ()
    end select
  end function sf_data_get_pdf_builtin_data_ptr

```

Initialize the mapping block with a single parameter.

```

<Strfun config: public>+≡
  public :: sf_data_setup_mapping

```

```

<Strfun config: procedures>+≡
  subroutine sf_data_setup_mapping (sf_data, type, index, par)
    type(sf_data_t), intent(inout) :: sf_data
    integer, intent(in) :: type
    integer, dimension(:), intent(in) :: index
    real(default), intent(in) :: par
    sf_data%mapping%type = type
    allocate (sf_data%mapping%index (size (index)))
    sf_data%mapping%index = index
    allocate (sf_data%mapping%par (1))
    sf_data%mapping%par = par
    sf_data%has_mapping = .true.
  end subroutine sf_data_setup_mapping

```

Initialize a dataset in the list with LHAPDF-specific options.

For the PDF pair case, we apply a mapping of the unit square which has a real-valued power as parameter. The default value is two.

```

<Strfun config: public>+≡
  public :: sf_data_init_lhapdf

<Strfun config: procedures>+≡
  subroutine sf_data_init_lhapdf (sf_data, i, &
    lhpdf_status, model, flv, prefix, file, member, photon_scheme)
    type(sf_data_t), intent(out) :: sf_data
    integer, intent(in) :: i
    type(lhapdf_status_t), intent(inout) :: lhpdf_status
    type(model_t), intent(in), target :: model
    type(flavor_t), intent(in) :: flv
    type(string_t), intent(in), optional :: prefix, file
    integer, intent(in), optional :: member
    integer, intent(in), optional :: photon_scheme
    sf_data%type = STRF_LHAPDF
    call lhpdf_data_init (sf_data%lhpdf, lhpdf_status, &
      model, flv, prefix, file, member, photon_scheme)
    sf_data%affects_beam(i) = .true.
    sf_data%n_parameters = 1
  end subroutine sf_data_init_lhapdf

<Strfun config: public>+≡
  public :: sf_data_init_pdf_builtin

<Strfun config: procedures>+≡
  subroutine sf_data_init_pdf_builtin (sf_data, i, &
    pdf_builtin_status, model, flv, name, path)
    type(sf_data_t), intent(out) :: sf_data
    integer, intent(in) :: i
    type(pdf_builtin_status_t), intent(inout) :: pdf_builtin_status
    type(model_t), intent(in), target :: model
    type(flavor_t), intent(in) :: flv
    type(string_t), intent(in), optional :: name, path
    sf_data%type = STRF_PDF_BUILTIN
    call pdf_builtin_init (sf_data%pdf_builtin, pdf_builtin_status, &
      model, flv, name, path)
    sf_data%affects_beam(i) = .true.

```

```

        sf_data%n_parameters = 1
    end subroutine sf_data_init_pdf_builtin

    <Strfun config: public>+≡
        public :: sf_data_init_isr

    <Strfun config: procedures>+≡
        subroutine sf_data_init_isr &
            (sf_data, i, model, flv, recoil, alpha, q_max, mass, order)
            type(sf_data_t), intent(out) :: sf_data
            integer, intent(in) :: i
            type(model_t), intent(in), target :: model
            type(flavor_t), intent(in) :: flv
            logical, intent(in) :: recoil
            real(default), intent(in) :: alpha, q_max
            real(default), intent(in), optional :: mass
            integer, intent(in), optional :: order
            sf_data%type = STRF_ISR
            call isr_data_init (sf_data%isr, model, flv, alpha, q_max, mass)
            if (present (order)) call isr_data_set_order (sf_data%isr, order)
            call isr_data_check (sf_data%isr)
            sf_data%affects_beam(i) = .true.
            if (recoil) then
                sf_data%n_parameters = 3
            else
                sf_data%n_parameters = 1
            end if
        end subroutine sf_data_init_isr

    <Strfun config: public>+≡
        public :: sf_data_init_epa

    <Strfun config: procedures>+≡
        subroutine sf_data_init_epa &
            (sf_data, i, model, flv, recoil, alpha, x_min, q_min, E_max, mass)
            type(sf_data_t), intent(out) :: sf_data
            integer, intent(in) :: i
            type(model_t), intent(in), target :: model
            type(flavor_t), intent(in) :: flv
            logical, intent(in) :: recoil
            real(default), intent(in) :: alpha, x_min, q_min, E_max
            real(default), intent(in), optional :: mass
            sf_data%type = STRF_EPA
            call epa_data_init (sf_data%epa, &
                model, flv, alpha, x_min, q_min, E_max, mass)
            call epa_data_check (sf_data%epa)
            sf_data%affects_beam(i) = .true.
            if (recoil) then
                sf_data%n_parameters = 3
            else
                sf_data%n_parameters = 1
            end if
        end subroutine sf_data_init_epa

```

```

<Strfun config: public>+≡
    public :: sf_data_init_ewa

<Strfun config: procedures>+≡
    subroutine sf_data_init_ewa &
        (sf_data, i, model, flv, x_min, q_min, pt_max, sqrts, &
         keep_momentum, keep_energy, mass)
        type(sf_data_t), intent(out) :: sf_data
        integer, intent(in) :: i
        type(model_t), intent(in), target :: model
        type(flavor_t), intent(in) :: flv
        real(default), intent(in) :: x_min, q_min, pt_max, sqrts
        logical, intent(in) :: keep_momentum, keep_energy
        real(default), intent(in), optional :: mass
        sf_data%type = STRF_EWA
        call ewa_data_init (sf_data%ewa, &
                           model, flv, x_min, q_min, pt_max, sqrts, &
                           keep_momentum, keep_energy, mass)
        call ewa_data_check (sf_data%ewa)
        sf_data%affects_beam(i) = .true.
        if (keep_momentum .or. keep_energy) then
            sf_data%n_parameters = 3
        else
            sf_data%n_parameters = 1
        end if
    end subroutine sf_data_init_ewa

<Strfun config: public>+≡
    public :: sf_data_init_circe1

<Strfun config: procedures>+≡
    subroutine sf_data_init_circe1 (sf_data, &
        model, flv, sqrts, photon, generate, rng, map, ver, rev, acc, chat)
        type(sf_data_t), intent(out) :: sf_data
        type(model_t), intent(in), target :: model
        type(flavor_t), dimension(2), intent(in) :: flv
        real(default), intent(in) :: sqrts
        logical, dimension(2), intent(in) :: photon
        logical, intent(in) :: generate, map
        type(tao_random_state), intent(in), target :: rng
        integer, intent(in) :: ver, rev, acc, chat
        sf_data%type = STRF_CIRCE1
        call circe1_data_init (sf_data%circe1, &
                               model, flv, sqrts, photon, generate, rng, map, ver, rev, acc, chat)
        call circe1_data_check (sf_data%circe1)
        sf_data%affects_beam = .true.
        sf_data%n_parameters = 2
    end subroutine sf_data_init_circe1

<Strfun config: public>+≡
    public :: sf_data_init_circe2

<Strfun config: procedures>+≡
    subroutine sf_data_init_circe2 (sf_data, &
        flv, generate, rng, map, file, design, sqrts, polarized)

```

```

type(sf_data_t), intent(out) :: sf_data
type(flavor_t), dimension(2), intent(in) :: flv
logical, intent(in) :: generate
type(tao_random_state), intent(in), target :: rng
logical, intent(in) :: map
type(string_t), intent(in) :: file, design
real(default), intent(in) :: sqrts
logical, intent(in) :: polarized
sf_data%type = STRF_CIRCE2
call circe2_data_init (sf_data%circe2, &
    flv, generate, rng, map, file, design, sqrts, polarized)
sf_data%affects_beam = .true.
sf_data%n_parameters = 2
end subroutine sf_data_init_circe2

```

<Strfun config: public>+≡

```
public :: sf_data_init_escan
```

<Strfun config: procedures>+≡

```

subroutine sf_data_init_escan (sf_data, affects_beam, flv, sqrts)
type(sf_data_t), intent(out) :: sf_data
logical, dimension(2), intent(in) :: affects_beam
type(flavor_t), dimension(2), intent(in) :: flv
real(default), intent(in) :: sqrts
sf_data%type = STRF_ESCAN
call escan_data_init (sf_data%escan, affects_beam, flv, sqrts)
sf_data%affects_beam = affects_beam
sf_data%n_parameters = count (affects_beam)
end subroutine sf_data_init_escan

```

<Strfun config: public>+≡

```
public :: sf_data_init_beam_events
```

<Strfun config: procedures>+≡

```

subroutine sf_data_init_beam_events &
    (sf_data, affects_beam, flv, file, warn_eof)
type(sf_data_t), intent(out) :: sf_data
logical, dimension(2), intent(in) :: affects_beam
type(flavor_t), dimension(2), intent(in) :: flv
type(string_t), intent(in) :: file
logical, intent(in) :: warn_eof
sf_data%type = STRF_BEVT
call beam_events_data_init (sf_data%beam_events, &
    affects_beam, flv, file, warn_eof)
call beam_events_data_open (sf_data%beam_events)
sf_data%affects_beam = affects_beam
sf_data%n_parameters = 0
end subroutine sf_data_init_beam_events

```

<Strfun config: public>+≡

```
public :: sf_data_init_user
```

<Strfun config: procedures>+≡

```

subroutine sf_data_init_user (sf_data, i, flv, name, model)
type(sf_data_t), intent(out) :: sf_data

```

```

integer, intent(in) :: i
type(flavor_t), dimension(2), intent(in) :: flv
type(string_t), intent(in) :: name
type(model_t), intent(in), target :: model
sf_data%type = STRF_USER
call sf_user_data_init (sf_data%user, name, flv, model)
select case (sf_user_data_get_n_in (sf_data%user))
case (1)
    sf_data%affects_beam(i) = .true.
case (2)
    sf_data%affects_beam = .true.
end select
sf_data%n_parameters = sf_user_data_get_n_dim (sf_data%user)
end subroutine sf_data_init_user

```

16.3.4 Structure function list

A list of structure functions and associated mappings.

```

<Strfun config: public>+≡
    public :: sf_list_t

<Strfun config: types>+≡
    type :: sf_list_t
        private
        integer :: n_strfun = 0
        logical :: multichannel = .false.
        integer :: n_mapping = 0
        integer, dimension(2) :: global_mapping_index = 0
        integer :: global_mapping_type = SFM_NONE
        real(default) :: global_mapping_par = 1
        type(sf_data_t), pointer :: first => null ()
        type(sf_data_t), pointer :: last => null ()
        character(32) :: md5sum = ""
    end type sf_list_t

```

Output

```

<Strfun config: public>+≡
    public :: sf_list_write

<Strfun config: procedures>+≡
    subroutine sf_list_write (sf_list, unit, md5, beam_fmt)
        type(sf_list_t), intent(in) :: sf_list
        integer, intent(in), optional :: unit
        integer :: u
        logical, intent(in), optional :: md5
        logical, intent(in), optional :: beam_fmt
        type(sf_data_t), pointer :: current
        u = output_unit (unit); if (u < 0) return
        write (u, "(A)") "Structure function list"
        if (sf_list%multichannel .and. sf_list%n_mapping /= 0) then
            write (u, "(2x,A,L1)") "Global structure function mapping:"
            write (u, "(4x,A,2I0)") "Index      = ", sf_list%global_mapping_index
            write (u, "(4x,A,I0)")  "Type       = ", sf_list%global_mapping_type
        end if
    end subroutine sf_list_write

```

```

        write (u, "(4x,A)", advance="no") "Parameter = "
        write (u, *) sf_list%global_mapping_par
    end if
    if (associated (sf_list%first)) then
        current => sf_list%first
        do while (associated (current))
            call sf_data_write (current, unit, md5, beam_fmt)
            current => current%next
        end do
    else
        write (u, "(1x,A)") "[empty]"
    end if
end subroutine sf_list_write

```

Append a data set to the list. For EPA, several data sets may be used in parallel. Allocate only one.

```

<Strfun config: public>+≡
    public :: sf_list_append

<Strfun config: procedures>+≡
    subroutine sf_list_append (sf_list, sf_data)
        type(sf_list_t), intent(inout) :: sf_list
        type(sf_data_t), intent(in), target :: sf_data
        if (associated (sf_list%last)) then
            sf_list%last%next => sf_data
        else
            sf_list%first => sf_data
        end if
        sf_list%last => sf_data
        sf_list%n_strfun = sf_list%n_strfun + 1
    end subroutine sf_list_append

```

Count mappings. If the multichannel flag is set, the mappings that are stored in the individual structure functions are not used directly, but transformed into channel-individual mappings.

```

<Strfun config: public>+≡
    public :: sf_list_freeze

<Strfun config: procedures>+≡
    subroutine sf_list_freeze (sf_list, multichannel)
        type(sf_list_t), intent(inout) :: sf_list
        logical, intent(in) :: multichannel
        type(sf_data_t), pointer :: sf_data
        integer :: i_par
        sf_list%multichannel = multichannel
        if (multichannel) then
            sf_list%n_mapping = 0
            i_par = 0
            sf_data => sf_list%first
            do while (associated (sf_data))
                if (sf_data%has_mapping) then
                    sf_list%n_mapping = 1
                    sf_list%global_mapping_index = i_par + sf_data%mapping%index
                    sf_list%global_mapping_type = sf_data%mapping%type

```



```

        select case (sf_data%mapping%type)
        case (SFM_PAIR)
            if (allocated (sf_data%mapping%par)) then
                sf_list%global_mapping_par = &
                    max (sf_list%global_mapping_par, sf_data%mapping%par(1))
            end if
        end select
    end if
    i_par = i_par + sf_data%n_parameters
    sf_data => sf_data%next
end do
else
    sf_list%n_mapping = 0
    sf_data => sf_list%first
    do while (associated (sf_data))
        if (sf_data%has_mapping) then
            sf_list%n_mapping = sf_list%n_mapping + 1
        end if
        sf_data => sf_data%next
    end do
end if
end subroutine sf_list_freeze

```

Finalize.

```

<Strfun config: public>+≡
    public :: sf_list_final
<Strfun config: procedures>+≡
    subroutine sf_list_final (sf_list)
        type(sf_list_t), intent(inout) :: sf_list
        type(sf_data_t), pointer :: sf_data
        do while (associated (sf_list%first))
            sf_data => sf_list%first
            sf_list%first => sf_list%first%next
            deallocate (sf_data)
        end do
        sf_list%last => null ()
        sf_list%n_strfun = 0
    end subroutine sf_list_final

```

Return number of structure functions.

```

<Strfun config: public>+≡
    public :: sf_list_get_n_strfun
<Strfun config: procedures>+≡
    function sf_list_get_n_strfun (sf_list) result (n)
        integer :: n
        type(sf_list_t), intent(in) :: sf_list
        n = sf_list%n_strfun
    end function sf_list_get_n_strfun

```

Return the MD5 checksum.

```

<Strfun config: public>+≡
    public :: sf_list_get_md5sum

```

```

<Strfun config: procedures>+≡
function sf_list_get_md5sum (sf_list) result (sf_md5sum)
  character(32) :: sf_md5sum
  type(sf_list_t), intent(in) :: sf_list
  sf_md5sum = sf_list%md5sum
end function sf_list_get_md5sum

```

Compute the MD5 checksum.

```

<Strfun config: public>+≡
  public :: sf_list_compute_md5sum

<Strfun config: procedures>+≡
  subroutine sf_list_compute_md5sum (sf_list)
    type(sf_list_t), intent(inout) :: sf_list
    integer :: unit
    unit = free_unit ()
    open (unit = unit, status = "scratch", action = "readwrite")
    call sf_list_write (sf_list, unit, md5=.true.)
    rewind (unit)
    sf_list%md5sum = md5sum (unit)
    close (unit)
  end subroutine sf_list_compute_md5sum

```

Extract any PDF data from the structure function list, so they can be used consistently elsewhere. In case of multiple entries (e.g., different LHAPDF settings for both beams), the first match is returned.

We return pointers; a null pointer indicates the absence of a matching data set. The implementation has to ensure the validity of the target for the lifetime of the pointer.

```

<Strfun config: public>+≡
  public :: sf_list_get_lhapdf_data_ptr
  public :: sf_list_get_pdf_builtin_data_ptr

<Strfun config: procedures>+≡
function sf_list_get_lhapdf_data_ptr (sf_list) result (lhpdf_data)
  type(sf_list_t), intent(in) :: sf_list
  type(lhapdf_data_t), pointer :: lhpdf_data
  type(sf_data_t), pointer :: sf_data
  lhpdf_data => null ()
  sf_data => sf_list%first
  FIND_LHAPDF: do while (associated (sf_data))
    lhpdf_data => sf_data_get_lhapdf_data_ptr (sf_data)
    if (associated (lhpdf_data)) exit FIND_LHAPDF
    sf_data => sf_data%next
  end do FIND_LHAPDF
end function sf_list_get_lhapdf_data_ptr

function sf_list_get_pdf_builtin_data_ptr (sf_list) result (pdf_builtin_data)
  type(sf_list_t), intent(in) :: sf_list
  type(pdf_builtin_data_t), pointer :: pdf_builtin_data
  type(sf_data_t), pointer :: sf_data
  pdf_builtin_data => null ()
  sf_data => sf_list%first

```

```

FIND_PDF_BUILTIN: do while (associated (sf_data))
  pdf_builtin_data => sf_data_get_pdf_builtin_data_ptr (sf_data)
  if (associated (pdf_builtin_data)) exit FIND_PDF_BUILTIN
  sf_data => sf_data%next
end do FIND_PDF_BUILTIN
end function sf_list_get_pdf_builtin_data_ptr

```

16.3.5 Transfer to the process object

Initialize actual structure functions, once the `sf_list` is complete. Beam initialization has to come before this.

```

<Strfun config: public>+≡
  public :: sf_list_transfer_to_process

<Strfun config: procedures>+≡
  subroutine sf_list_transfer_to_process (sf_list, process)
    type(sf_list_t), intent(in) :: sf_list
    type(process_t), intent(inout), target :: process
    type(sf_data_t), pointer :: sf_data
    integer :: i_sf, line
    i_sf = 0
    sf_data => sf_list%first
    do while (associated (sf_data))
      if (all (sf_data%affects_beam)) then
        line = 0
      else if (sf_data%affects_beam(1)) then
        line = 1
      else if (sf_data%affects_beam(2)) then
        line = 2
      end if
      i_sf = i_sf + 1
      select case (sf_data%type)
        case (STRF_LHAPDF)
          call process_set_strfun &
            (process, i_sf, line, sf_data%lhpdf, sf_data%n_parameters)
        case (STRF_PDF_BUILTIN)
          call process_set_strfun &
            (process, i_sf, line, sf_data%pdf_builtin, sf_data%n_parameters)
        case (STRF_ISR)
          call process_set_strfun &
            (process, i_sf, line, sf_data%isr, sf_data%n_parameters)
        case (STRF_EPA)
          call process_set_strfun &
            (process, i_sf, line, sf_data%epa, sf_data%n_parameters)
        case (STRF_EWA)
          call process_set_strfun &
            (process, i_sf, line, sf_data%ewa, sf_data%n_parameters)
        case (STRF_CIRCE1)
          call process_set_strfun &
            (process, i_sf, line, sf_data%circe1, sf_data%n_parameters)
        case (STRF_CIRCE2)
          call process_set_strfun &
            (process, i_sf, line, sf_data%circe2, sf_data%n_parameters)
      end select
      sf_data => sf_data%next
    end do
  end subroutine

```

```

case (STRF_ESCAN)
  call process_set_strfun &
    (process, i_sf, line, sf_data%escan, sf_data%n_parameters)
case (STRF_BEVT)
  call process_set_strfun &
    (process, i_sf, line, sf_data%beam_events, sf_data%n_parameters)
case (STRF_USER)
  call process_set_strfun &
    (process, i_sf, line, sf_data%user, sf_data%n_parameters)
end select
sf_data => sf_data%next
end do
end subroutine sf_list_transfer_to_process

```

The structure-function mappings are done separately, after the phase space is also set up.

```

<Strfun config: public>+≡
  public :: sf_list_setup_mappings

<Strfun config: procedures>+≡
  subroutine sf_list_setup_mappings (sf_list, process)
    type(sf_list_t), intent(in) :: sf_list
    type(process_t), intent(inout), target :: process
    type(sf_data_t), pointer :: sf_data
    integer :: i_map, i_par, channel
    logical :: has_s_mapping
    real(default) :: sqrts, mass, width
    i_map = 0
    i_par = 0
    if (sf_list%multichannel) then
      call process_allocate_strfun_mappings &
        (process, sf_list%multichannel)
      if (sf_list%n_mapping /= 0) then
        select case (sf_list%global_mapping_type)
        case (SFM_PAIR)
          sqrts = process_get_sqrts (process)
          do channel = 1, process_get_n_channels (process)
            call process_get_s_mapping &
              (process, channel, has_s_mapping, mass, width)
            if (has_s_mapping) then
              call process_set_strfun_mapping &
                (process, 1, channel, sf_list%global_mapping_index, &
                  SFM_PAIR_RESONANCE, &
                  (/sqrts, mass, width/))
            else
              call process_set_strfun_mapping &
                (process, 1, channel, sf_list%global_mapping_index, &
                  SFM_PAIR, &
                  (/sf_list%global_mapping_par/))
            end if
          end do
        case default
          call msg_bug ("Strfun mappings: inconsistent mapping type")
        end select
      end if
    end if
  end subroutine

```

```

        end if
    else
        call process_allocate_strfun_mappings (process, &
            sf_list%multichannel, &
            sf_list%n_mapping)
        sf_data => sf_list%first
        do while (associated (sf_data))
            if (sf_data%has_mapping) then
                i_map = i_map + 1
                call process_set_strfun_mapping &
                    (process, i_map, 1, i_par + sf_data%mapping%index, &
                    sf_data%mapping%type, sf_data%mapping%par)
            end if
            i_par = i_par + sf_data%n_parameters
            sf_data => sf_data%next
        end do
    end if
end subroutine sf_list_setup_mappings

```

16.3.6 The LHAPDF status

We re-export this from the `sf_lhapdf` module, so this need not be referenced directly:

```

⟨Strfun config: public⟩+≡
    public :: lhapdf_status_t
    public :: lhapdf_status_reset

```

16.4 User-controlled File I/O

The SINDARIN language includes commands that write output to file (input may be added later). We identify files by their name, and manage the unit internally. We need procedures for opening, closing, and printing files.

```

⟨user_files.f90⟩≡
    ⟨File header⟩

    module user_files

        ⟨Use strings⟩
        ⟨Use file utils⟩
        use diagnostics !NODEP!
        use ifiles
        use analysis

        ⟨Standard module head⟩

        ⟨User files: public⟩

        ⟨User files: types⟩

        ⟨User files: interfaces⟩

```

```
contains

  <User files: procedures>

end module user_files
```

16.4.1 The file type

This is a type that describes an open user file and its properties. The entry is part of a doubly-linked list.

```
<User files: types>≡
  type :: file_t
    private
      type(string_t) :: name
      integer :: unit = -1
      logical :: reading = .false.
      logical :: writing = .false.
      type(file_t), pointer :: prev => null ()
      type(file_t), pointer :: next => null ()
    end type file_t
```

The initializer opens the file.

```
<User files: procedures>≡
  subroutine file_init (file, name, action, status, position)
    type(file_t), intent(out) :: file
    type(string_t), intent(in) :: name
    character(len=*), intent(in) :: action, status, position
    file%unit = free_unit ()
    file%name = name
    open (unit = file%unit, file = char (file%name), &
          action = action, status = status, position = position)
    select case (action)
    case ("read")
      file%reading = .true.
    case ("write")
      file%writing = .true.
    case ("readwrite")
      file%reading = .true.
      file%writing = .true.
    end select
  end subroutine file_init
```

The finalizer closes it.

```
<User files: procedures>+≡
  subroutine file_final (file)
    type(file_t), intent(inout) :: file
    close (unit = file%unit)
    file%unit = -1
  end subroutine file_final
```

Check if a file is open with correct status.

```
<User files: procedures>+≡
function file_is_open (file, action) result (flag)
  logical :: flag
  type(file_t), intent(in) :: file
  character(*), intent(in) :: action
  select case (action)
  case ("read")
    flag = file%reading
  case ("write")
    flag = file%writing
  case ("readwrite")
    flag = file%reading .and. file%writing
  case default
    call msg_bug ("Checking file '" // char (file%name) &
      // "' : illegal action specifier")
  end select
end function file_is_open
```

Write to the file. Error if in wrong mode. If there is no string, just write an empty record. If there is a string, respect the `advancing` option.

```
<User files: procedures>+≡
subroutine file_write_string (file, string, advancing)
  type(file_t), intent(in) :: file
  type(string_t), intent(in), optional :: string
  logical, intent(in), optional :: advancing
  if (file%writing) then
    if (present (string)) then
      if (present (advancing)) then
        if (advancing) then
          write (file%unit, "(A)") char (string)
        else
          write (file%unit, "(A)", advance="no") char (string)
        end if
      else
        write (file%unit, "(A)") char (string)
      end if
    else
      write (file%unit, *)
    end if
  else
    call msg_error ("Writing to file: File '" // char (file%name) &
      // "' is not open for writing.")
  end if
end subroutine file_write_string
```

Write a whole ifile, line by line.

```
<User files: procedures>+≡
subroutine file_write_ifile (file, ifile)
  type(file_t), intent(in) :: file
  type(ifile_t), intent(in) :: ifile
  type(line_p) :: line
  call line_init (line, ifile)
```

```

do while (line_is_associated (line))
  call file_write_string (file, line_get_string_advance (line))
end do
end subroutine file_write_ifile

```

Write an analysis object (or all objects) to an open file.

```

<User files: procedures>+≡
subroutine file_write_analysis (file, tag)
  type(file_t), intent(in) :: file
  type(string_t), intent(in), optional :: tag
  if (file%writing) then
    if (present (tag)) then
      call analysis_write (tag, unit = file%unit)
    else
      call analysis_write (unit = file%unit)
    end if
  else
    call msg_error ("Writing analysis to file: File ' " // char (file%name) &
      // "' is not open for writing.")
  end if
end subroutine file_write_analysis

```

16.4.2 The file list

We maintain a list of all open files and their attributes. The list must be doubly-linked because we may delete entries.

```

<User files: public>≡
public :: file_list_t

<User files: types>+≡
type :: file_list_t
  type(file_t), pointer :: first => null ()
  type(file_t), pointer :: last => null ()
end type file_list_t

```

There is no initialization routine, but a finalizer which deletes all:

```

<User files: public>+≡
public :: file_list_final

<User files: procedures>+≡
subroutine file_list_final (file_list)
  type(file_list_t), intent(inout) :: file_list
  type(file_t), pointer :: current
  do while (associated (file_list%first))
    current => file_list%first
    file_list%first => current%next
    call file_final (current)
    deallocate (current)
  end do
  file_list%last => null ()
end subroutine file_list_final

```


Find an entry in the list. Return null pointer on failure.

```

<User files: procedures>+≡
function file_list_get_file_ptr (file_list, name) result (current)
    type(file_t), pointer :: current
    type(file_list_t), intent(in) :: file_list
    type(string_t), intent(in) :: name
    current => file_list%first
    do while (associated (current))
        if (current%name == name) return
        current => current%next
    end do
end function file_list_get_file_ptr

```

Check if a file is open, public version:

```

<User files: public>+≡
public :: file_list_is_open

<User files: procedures>+≡
function file_list_is_open (file_list, name, action) result (flag)
    logical :: flag
    type(file_list_t), intent(in) :: file_list
    type(string_t), intent(in) :: name
    character(len=*), intent(in) :: action
    type(file_t), pointer :: current
    current => file_list_get_file_ptr (file_list, name)
    if (associated (current)) then
        flag = file_is_open (current, action)
    else
        flag = .false.
    end if
end function file_list_is_open

```

Append a new file entry, i.e., open this file. Error if it is already open.

```

<User files: public>+≡
public :: file_list_open

<User files: procedures>+≡
subroutine file_list_open (file_list, name, action, status, position)
    type(file_list_t), intent(inout) :: file_list
    type(string_t), intent(in) :: name
    character(len=*), intent(in) :: action, status, position
    type(file_t), pointer :: current
    if (.not. associated (file_list_get_file_ptr (file_list, name))) then
        allocate (current)
        call file_init (current, name, action, status, position)
        if (associated (file_list%last)) then
            file_list%last%next => current
            current%prev => file_list%last
        else
            file_list%first => current
        end if
        file_list%last => current
    else
        call msg_error ("Opening file: File '" // char (name) &

```

```

        // '' is already open.")
    end if
end subroutine file_list_open

```

Delete a file entry, i.e., close this file. Error if it is not open.

```

<User files: public>+≡
    public :: file_list_close

<User files: procedures>+≡
    subroutine file_list_close (file_list, name)
        type(file_list_t), intent(inout) :: file_list
        type(string_t), intent(in) :: name
        type(file_t), pointer :: current
        current => file_list_get_file_ptr (file_list, name)
        if (associated (current)) then
            if (associated (current%prev)) then
                current%prev%next => current%next
            else
                file_list%first => current%next
            end if
            if (associated (current%next)) then
                current%next%prev => current%prev
            else
                file_list%last => current%prev
            end if
            call file_final (current)
            deallocate (current)
        else
            call msg_error ("Closing file: File '' // char (name) &
                // '' is not open.")
        end if
    end subroutine file_list_close

```

Write a string to file. Error if it is not open.

```

<User files: public>+≡
    public :: file_list_write

<User files: interfaces>≡
    interface file_list_write
        module procedure file_list_write_string
        module procedure file_list_write_ifile
    end interface

<User files: procedures>+≡
    subroutine file_list_write_string (file_list, name, string, advancing)
        type(file_list_t), intent(in) :: file_list
        type(string_t), intent(in) :: name
        type(string_t), intent(in), optional :: string
        logical, intent(in), optional :: advancing
        type(file_t), pointer :: current
        current => file_list_get_file_ptr (file_list, name)
        if (associated (current)) then
            call file_write_string (current, string, advancing)
        else

```

```

        call msg_error ("Writing to file: File '" // char (name) &
            // "'is not open.")
    end if
end subroutine file_list_write_string

subroutine file_list_write_ifile (file_list, name, ifile)
    type(file_list_t), intent(in) :: file_list
    type(string_t), intent(in) :: name
    type(ifile_t), intent(in) :: ifile
    type(line_p) :: line
    type(file_t), pointer :: current
    current => file_list_get_file_ptr (file_list, name)
    if (associated (current)) then
        call file_write_ifile (current, ifile)
    else
        call msg_error ("Writing to file: File '" // char (name) &
            // "'is not open.")
    end if
end subroutine file_list_write_ifile

```

Write an analysis object or all objects to data file. Error if it is not open. If the file name is empty, write to standard output.

```

<User files: public>+≡
    public :: file_list_write_analysis

<User files: procedures>+≡
    subroutine file_list_write_analysis (file_list, name, tag)
        type(file_list_t), intent(in) :: file_list
        type(string_t), intent(in) :: name
        type(string_t), intent(in), optional :: tag
        type(file_t), pointer :: current
        if (name == "") then
            if (present (tag)) then
                call analysis_write (tag)
            else
                call analysis_write
            end if
        else
            current => file_list_get_file_ptr (file_list, name)
            if (associated (current)) then
                call file_write_analysis (current, tag)
            else
                call msg_error ("Writing analysis to file: File '" // char (name) &
                    // "' is not open.")
            end if
        end if
    end subroutine file_list_write_analysis

```

16.5 Runtime data

```

<rt_data.f90>≡
    <File header>

```

```

module rt_data

  <Use kinds>
  <Use strings>
  <Use file utils>
  use system_dependencies !NODEP!
  use diagnostics !NODEP!
  use tao_random_numbers !NODEP!
  use pdf_builtin !NODEP!
  use variables
  use os_interface
  use lexers
  use parser
  use models
  use beams
  use process_libraries
  use iterations
  use beam_polarizations
  use strfun_config
  use user_files

  <Standard module head>

  <RT data: public>

  <RT data: types>

  contains

  <RT data: procedures>

end module rt_data

```

16.5.1 The data type

This is a big data container which contains everything that is used and modified during the command flow. A local copy of this can be used to temporarily override defaults. The data set is transparent.

```

<RT data: types>≡
  public :: rt_data_t

<RT data: types>+≡
  type :: rt_data_t
    type(lexer_t), pointer :: lexer => null ()
    type(var_list_t) :: var_list
    type(iterations_list_t) :: it_list
    type(iterations_list_t), dimension(:), pointer :: it_list_default
    integer, dimension(:), allocatable :: event_fmt
    type(os_data_t) :: os_data
    type(process_library_t), pointer :: prc_lib => null ()
    type(model_t), pointer :: model => null ()
    type(beam_data_t) :: beam_data
    type(lhapdf_status_t) :: lhpdf_status

```

```

type(pdf_builtin_status_t) :: pdf_builtin_status
logical :: sf_list_allocated = .false.
type(sf_list_t), pointer :: sf_list => null ()
type(parse_node_t), pointer :: pn_cuts_lexpr => null ()
type(parse_node_t), pointer :: pn_scale_lexpr => null ()
type(parse_node_t), pointer :: pn_fac_scale_lexpr => null ()
type(parse_node_t), pointer :: pn_ren_scale_lexpr => null ()
type(parse_node_t), pointer :: pn_weight_lexpr => null ()
type(parse_node_t), pointer :: pn_selection_lexpr => null ()
type(parse_node_t), pointer :: pn_reweight_lexpr => null ()
type(parse_node_t), pointer :: pn_analysis_lexpr => null ()
type(parse_node_t), pointer :: pn_histogram_writer => null ()
type(parse_node_t), pointer :: pn_plot_writer => null ()
type(file_list_t), pointer :: out_files => null ()
type(tao_random_state), pointer :: rng => null ()
type(beam_polarization_t), dimension(:), pointer :: &
    beam_polarization => null ()
integer :: seed
integer :: method = PRC_UNDEFINED
logical :: quit = .false.
integer :: quit_code = 0
integer :: environment = -1
integer :: analysis_data_unit = -1
end type rt_data_t

```

16.5.2 Initialization

Initialize runtime data. This defines special variables such as `sqrts`, and should be done only for the instance that is actually global. Local copies will inherit the special variables.

<RT data: public>≡

```
public :: rt_data_global_init
```

<RT data: procedures>≡

```

subroutine rt_data_global_init (global, paths)
    type(rt_data_t), intent(out), target :: global
    type(paths_t), intent(in), optional :: paths
    logical, target, save :: known = .true.
    real(default), parameter :: real_specimen = 1.
    call os_data_init (global%os_data, paths)
    allocate (global%out_files)
    allocate (global%rng)
    call system_clock (global%seed)
    call tao_random_create (global%rng, global%seed)
    call var_list_append_int_ptr &
        (global%var_list, var_str ("seed_value"), global%seed, known, &
            intrinsic=.true.)
    call var_list_append_string &
        (global%var_list, var_str ("model_name"), &
            intrinsic=.true.)
    call var_list_append_string &
        (global%var_list, var_str ("restrictions"), var_str (""), &
            intrinsic=.true.)

```

```

call var_list_append_string &
  (global%var_list, var_str ("omega_flags"), var_str (""), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("method"), var_str ("omega"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?read_color_factors"), .true., &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("user_procs_cut"), var_str (""), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("user_procs_event_shape"), var_str (""), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("user_procs_obs1"), var_str (""), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("user_procs_obs2"), var_str (""), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("user_procs_sf"), var_str (""), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?slha_read_input"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?slha_read_spectrum"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?slha_read_decays"), .false., &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("library_name"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("sqrt_s"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("beam1_momentum"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("beam2_momentum"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("crossing_angle"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("beams_theta"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("beams_phi"), &
   intrinsic=.true.)

```

```

call var_list_append_real &
  (global%var_list, var_str ("luminosity"), 0._default, &
   intrinsic=.true.)
if (present (paths)) then
  call var_list_append_string &
    (global%var_list, var_str ("lhapdf_dir"), paths%lhapdfdir, &
     intrinsic=.true.)
else
  call var_list_append_string &
    (global%var_list, var_str ("lhapdf_dir"), var_str(""), &
     intrinsic=.true.)
end if
call var_list_append_string &
  (global%var_list, var_str ("lhapdf_file"), var_str(""), &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("lhapdf_member"), 0, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("lhapdf_photon_scheme"), 0, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("isr_alpha"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("isr_q_max"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("isr_mass"), 0._default, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("isr_order"), 3, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?isr_recoil"), .false., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("epa_alpha"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("epa_x_min"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("epa_q_min"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("epa_e_max"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("epa_mass"), 0._default, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?epa_recoil"), .false., &
   intrinsic=.true.)

```

```

call var_list_append_real &
  (global%var_list, var_str ("ewa_x_min"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("ewa_q_min"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("ewa_pt_max"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("ewa_mass"), 0._default, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?ewa_keep_momentum"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?ewa_keep_energy"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?circe1_photon1"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?circe1_photon2"), .false., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("circe1_sqrts"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?circe1_generate"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?circe1_map"), .true., &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("circe1_ver"), 0, intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("circe1_rev"), 0, intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("circe1_acc"), 1, intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("circe1_chat"), 0, intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("circe2_sqrts"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?circe2_generate"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?circe2_map"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?circe2_polarized"), .true., &
   intrinsic=.true.)
call var_list_append_string &

```



```

(global%var_list, var_str ("$circe2_file"), &
  intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$circe2_design"), var_str ("*"), &
  intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$beam_events_file"), &
  intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?beam_events_warn_eof"), .true., &
  intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_is_fixed"), .true., &
  intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_from_lhapdf"), .false., &
  intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_from_pdf_builtin"), .false., &
  intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("alpha_s_order"), 0, &
  intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("alpha_s_nf"), 5, &
  intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?alpha_s_from_mz"), .true., &
  intrinsic=.true.)
call var_list_append_real &
(global%var_list, var_str ("lambda_qcd"), 200.e-3_default, &
  intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?fatal_beam_decay"), .true., &
  intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?helicity_selection_active"), .true., &
  intrinsic=.true.)
call var_list_append_real &
(global%var_list, var_str ("helicity_selection_threshold"), &
  1E10_default, &
  intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("helicity_selection_cutoff"), 1000, &
  intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("threshold_calls"), 10, &
  intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("min_calls_per_channel"), 10, &
  intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("min_calls_per_bin"), 10, &
  intrinsic=.true.)

```

```

call var_list_append_int &
  (global%var_list, var_str ("min_bins"), 3, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("max_bins"), 20, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?stratified"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?use_vamp_equivalences"), .true., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("channel_weights_power"), 0.25_default, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?vis_channels"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?check_phs_file"), .true., &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("phs_file"), var_str (""), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_only"), .false., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_threshold_s"), 50._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_threshold_t"), 100._default, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("phs_off_shell"), 2, &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("phs_t_channel"), 6, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_e_scale"), 10._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_m_scale"), 10._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("phs_q_scale"), 10._default, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_keep_nonresonant"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_step_mapping"), .true., &
   intrinsic=.true.)

```

```

call var_list_append_log &
  (global%var_list, var_str ("?phs_step_mapping_exp"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?phs_s_mapping"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?strfun_multichannel"), .false., &
   intrinsic=.true.)
!   call var_list_append_log &
!     (global%var_list, var_str ("?old_phs_version"), .false., &
!       intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$_run_id"), var_str (""), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?use_best_grid"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?check_grid_file"), .true., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("accuracy_goal"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("error_goal"), 0._default, &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("relative_error_goal"), 0._default, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?vis_history"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?isotropic_decay"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?diagonal_decay"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?check_event_file"), .true., &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$_event_file_version"), var_str (""), &
   intrinsic=.true.)
call var_list_append_int &
  (global%var_list, var_str ("n_events"), 0, &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?allow_decays"), .true., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?unweighted"), .true., &
   intrinsic=.true.)

```

```

call var_list_append_string &
(global%var_list, var_str ("sevent_normalization"), var_str ("auto"), &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?negative_weights"), .false., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?use_num_id"), .false., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?keep_beams"), .false., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?update_parameters"), .true., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?update_scale"), .false., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?update_alpha_s"), .false., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?update_sqme"), .true., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?update_weight"), .true., &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("sample"), var_str (""), &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?read_raw"), .true., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?write_raw"), .true., &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("extension_raw"), var_str ("evx"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("extension_default"), var_str ("evt"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("extension_debug"), var_str ("debug"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("extension_hepevt"), var_str ("hepevt"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("extension_ascii_short"), var_str ("short.evt"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("extension_ascii_long"), var_str ("long.evt"), &
intrinsic=.true.)

```

```

call var_list_append_string &
(global%var_list, var_str ("$extension_athena"), var_str ("athena.evt"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_lhef"), var_str ("lhef"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_lha"), var_str ("lha"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_hepmc"), var_str ("hepmc"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_stdhep"), var_str ("stdhep"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_stdhep_up"), var_str ("up.stdhep"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_hepevt_verbose"), var_str ("hepevt.verb"), &
intrinsic=.true.)
call var_list_append_string &
(global%var_list, var_str ("$extension_lha_verbose"), var_str ("lha.verb"), &
intrinsic=.true.)
call var_list_append_int (global%var_list, &
var_str ("n_bins"), 20, &
intrinsic=.true.)
call var_list_append_log (global%var_list, &
var_str ("?normalize_bins"), .false., &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$obs_label"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$obs_unit"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$title"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$description"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$x_label"), var_str (""), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$y_label"), var_str (""), &
intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("graph_width_mm"), 130, &
intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("graph_height_mm"), 90, &
intrinsic=.true.)

```

```

call var_list_append_log &
  (global%var_list, var_str ("?y_log"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?x_log"), .false., &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?y_log"), .false., &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("x_min"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("x_max"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("y_min"), &
   intrinsic=.true.)
call var_list_append_real &
  (global%var_list, var_str ("y_max"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$gmlcode_bg"), var_str (""), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$gmlcode_fg"), var_str (""), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_histogram"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_base"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_pieewise"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?fill_curve"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_curve"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_errors"), &
   intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?draw_symbols"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$fill_options"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$draw_options"), &
   intrinsic=.true.)

```

```

call var_list_append_string &
  (global%var_list, var_str ("$err_options"), &
   intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$symbol"), &
   intrinsic=.true.)
call var_list_append_real (global%var_list, &
  var_str ("tolerance"), 0._default, &
  intrinsic=.true.)
call var_list_append_int (global%var_list, &
  var_str ("checkpoint"), intrinsic = .true.)
call var_list_append_string &
  (global%var_list, var_str ("$out_file"), var_str (""), &
  intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?out_advance"), .true., &
  intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?out_custom"), .false., &
  intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$out_comment"), var_str ("# "), &
  intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("$out_separator"), var_str (" "), &
  intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?out_columns"), .true., &
  intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?out_header"), .true., &
  intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?out_yerr"), .true., &
  intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?out_xerr"), .true., &
  intrinsic=.true.)
call var_list_append_int (global%var_list, var_str ("real_range"), &
  range (real_specimen), intrinsic = .true., locked = .true.)
call var_list_append_int (global%var_list, var_str ("real_precision"), &
  precision (real_specimen), intrinsic = .true., locked = .true.)
call var_list_append_real (global%var_list, var_str ("real_epsilon"), &
  epsilon (real_specimen), intrinsic = .true., locked = .true.)
call var_list_append_real (global%var_list, var_str ("real_tiny"), &
  tiny (real_specimen), intrinsic = .true., locked = .true.)
call var_list_append_log &
  (global%var_list, var_str ("?polarized_events"), .false., &
  intrinsic=.true.)
! default settings for shower
call var_list_append_log &
  (global%var_list, var_str ("?ps_fsr_active"), .false., &
  intrinsic=.true.)
call var_list_append_log &

```

```

(global%var_list, var_str ("?ps_use_PYTHIA_shower"), .true., &
  intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?ps_PYTHIA_verbose"), .false., &
    intrinsic=.true.)
call var_list_append_string &
  (global%var_list, var_str ("ps_PYTHIA_PYGIVE"), var_str (""), &
    intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?ps_isr_active"), .false., &
    intrinsic=.true.)
call var_list_append_real (global%var_list, var_str ("ps_mass_cutoff"), &
  1._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("ps_fsr_lambda"), &
  0.29_default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("ps_isr_lambda"), &
  0.29_default, intrinsic = .true.)
call var_list_append_int (global%var_list, var_str ("ps_max_n_flavors"), &
  5, intrinsic = .true.)
call var_list_append_log &
  (global%var_list, var_str ("?ps_isr_alpha_s_running"), .true., &
    intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?ps_fsr_alpha_s_running"), .true., &
    intrinsic=.true.)
call var_list_append_real (global%var_list, var_str ("ps_fixed_alpha_s"), &
  0._default, intrinsic = .true.)
call var_list_append_log &
  (global%var_list, var_str ("?ps_isr_pt_ordered"), .false., &
    intrinsic=.true.)
call var_list_append_log &
  (global%var_list, var_str ("?ps_isr_angular_ordered"), .true., &
    intrinsic=.true.)
call var_list_append_real (global%var_list, var_str ("ps_isr_primordial_kt_width"), &
  0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("ps_isr_primordial_kt_cutoff"), &
  5._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("ps_isr_z_cutoff"), &
  0.999_default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("ps_isr_minenergy"), &
  1._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("ps_isr_tscalefactor"), &
  1._default, intrinsic = .true.)
call var_list_append_log &
  (global%var_list, var_str ("?ps_isr_only_onshell_emitted_partons"), .false., &
    intrinsic=.true.)
! default settings for hadronization
call var_list_append_log &
  (global%var_list, var_str ("?hadronization_active"), .false., &
    intrinsic=.true.)
! setting for mlm matching
call var_list_append_log &
  (global%var_list, var_str ("?mlm_matching"), .false., &
    intrinsic=.true.)

```



```

call var_list_append_real (global%var_list, var_str ("mlm_Qcut_ME"), &
0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_Qcut_PS"), &
0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_ptmin"), &
0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_etamax"), &
0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_Rmin"), &
0._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_Emin"), &
0._default, intrinsic = .true.)
call var_list_append_int (global%var_list, var_str ("mlm_nmaxMEjets"), &
0, intrinsic = .true.)

call var_list_append_real (global%var_list, var_str ("mlm_ETclusfactor"), &
0.2_default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_ETclusminE"), &
5._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_etaclusfactor"), &
1._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_Rclusfactor"), &
1._default, intrinsic = .true.)
call var_list_append_real (global%var_list, var_str ("mlm_Eclusfactor"), &
1._default, intrinsic = .true.)
call var_list_append_log &
(global%var_list, var_str ("?ckkw_matching"), .false., &
intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?muli_active"), .false., &
intrinsic=.true.)

call var_list_append_string (global%var_list, var_str ("$_datafile"), &
intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$_comment_prefix"), var_str ("#"), intrinsic=.true.)
call var_list_append_log (global%var_list, var_str ("?write_header"), &
.true., intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$_pdf_builtin_path"), intrinsic=.true.)
call var_list_append_string (global%var_list, &
var_str ("$_pdf_builtin_set"), intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?omega_omp"), &
omp_is_active (), &
locked=.true., intrinsic=.true.)
call var_list_append_log &
(global%var_list, var_str ("?omp_is_active"), &
omp_is_active (), &
locked=.true., intrinsic=.true.)
call var_list_append_int &
(global%var_list, var_str ("omp_num_threads_default"), &
omp_get_default_max_threads (), &
locked=.true., intrinsic=.true.)

```

```

call var_list_append_int &
  (global%var_list, var_str ("openmp_num_threads"), &
   openmp_get_max_threads (), &
   intrinsic=.true.)
call rt_data_init_pointer_variables (global)
call iterations_lists_init_default (global%it_list_default)
end subroutine rt_data_global_init ! $

```

16.5.3 Local copies

This is done at compile time when a local copy of runtime data is needed: Link the variable list and initialize all derived parameters. This allows for synchronizing them with local variable changes without affecting global data.

Also re-initialize pointer variables, so they point to local copies of their targets.

```

<RT data: public>+≡
  public :: rt_data_local_init

<RT data: procedures>+≡
  subroutine rt_data_local_init (local, global, env)
    type(rt_data_t), intent(inout), target :: local
    type(rt_data_t), intent(in), target :: global
    integer, intent(in), optional :: env
    call var_list_link (local%var_list, global%var_list)
    if (associated (global%model)) then
      call var_list_init_copies (local%var_list, &
        model_get_var_list_ptr (global%model), &
        derived_only = .true.)
    end if
    call rt_data_init_pointer_variables (local)
    if (present (env)) local%environment = env
  end subroutine rt_data_local_init

```

These variables point to objects which get local copies:

```

<RT data: procedures>+≡
  subroutine rt_data_init_pointer_variables (local)
    type(rt_data_t), intent(inout), target :: local
    logical, target, save :: known = .true.
    call var_list_append_string_ptr &
      (local%var_list, var_str ("fc"), local%os_data%fc, known, &
       intrinsic=.true.)
    call var_list_append_string_ptr &
      (local%var_list, var_str ("fcflags"), local%os_data%fcflags, known, &
       intrinsic=.true.)
  end subroutine rt_data_init_pointer_variables

```

This should be executed when the compilation of a command that uses local variables is completed.

(Currently unused, keeping it for some time – just in case.)

```

<RT data: public>+≡
  public :: rt_data_local_reset

```

```

<RT data: procedures>+≡
  subroutine rt_data_local_reset (local)
    type(rt_data_t), intent(inout), target :: local
  end subroutine rt_data_local_reset

```

This is done at execution time: Copy data, transfer pointers. `local` has `intent(inout)` because its local variable list has already been prepared by the previous routine.

```

<RT data: public>+≡
  public :: rt_data_link

<RT data: procedures>+≡
  subroutine rt_data_link (local, global)
    type(rt_data_t), intent(inout), target :: local
    type(rt_data_t), intent(in), target :: global
    local%lexer => global%lexer
    call var_list_link (local%var_list, global%var_list)
    if (associated (global%model)) then
      call var_list_synchronize (local%var_list, &
        model_get_var_list_ptr (global%model), reset_pointers = .true.)
    end if
    local%it_list = global%it_list
    local%it_list_default => global%it_list_default
    if (allocated (global%event_fmt)) then
      if (allocated (local%event_fmt)) then
        deallocate (local%event_fmt)
      end if
      allocate (local%event_fmt (size (global%event_fmt)))
      local%event_fmt = global%event_fmt
    end if
    local%os_data = global%os_data
    local%prc_lib => global%prc_lib
    local%model => global%model
    local%beam_data = global%beam_data
    local%lhpdf_status = global%lhpdf_status
    local%sf_list_allocated = .false.
    local%sf_list => global%sf_list
    local%pn_cuts_lexpr => global%pn_cuts_lexpr
    local%pn_weight_expr => global%pn_weight_expr
    local%pn_scale_expr => global%pn_scale_expr
    local%pn_fac_scale_expr => global%pn_fac_scale_expr
    local%pn_ren_scale_expr => global%pn_ren_scale_expr
    local%pn_selection_lexpr => global%pn_selection_lexpr
    local%pn_reweight_expr => global%pn_reweight_expr
    local%pn_analysis_lexpr => global%pn_analysis_lexpr
    local%out_files => global%out_files
    local%rng => global%rng
    local%beam_polarization => global%beam_polarization
    local%pn_histogram_writer => global%pn_histogram_writer
    local%pn_plot_writer => global%pn_plot_writer
    local%analysis_data_unit = global%analysis_data_unit
  end subroutine rt_data_link

```

Restore the previous state of data; in particular, the variable list. This applies only to model variables (which are copies); other variables are automatically restored when local variables are removed.

Some command (`read_slha`) reads in model variables as local entities. In this case, the original values of model variables should not be restored, but the global variable list should be synchronized. However, this matters only if the local model is identical to the global model; otherwise, restoring will apply to a different model.

```

<RT data: public>+≡
    public :: rt_data_restore

<RT data: procedures>+≡
    subroutine rt_data_restore (global, local, keep_model_vars)
        type(rt_data_t), intent(inout) :: global
        type(rt_data_t), intent(inout) :: local
        logical, intent(in), optional :: keep_model_vars
        logical :: same_model, restore
        if (associated (global%model)) then
            same_model = &
                model_get_name (global%model) == model_get_name (local%model)
            if (present (keep_model_vars) .and. same_model) then
                restore = .not. keep_model_vars
            else
                if (.not. same_model) call msg_message ("Restoring model '" // &
                    char (model_get_name (global%model)) // "'")
                restore = .true.
            end if
            if (restore) then
                call var_list_restore (global%var_list)
            else
                call var_list_synchronize &
                    (global%var_list, model_get_var_list_ptr (global%model))
            end if
        end if
        call var_list_undefine (local%var_list, follow_link=.false.)
    end subroutine rt_data_restore

```

16.5.4 Finalization

Finalizer for the variable list and the structure-function list. This is done only for the global RT dataset; local copies contain pointers to this and do not need a finalizer.

```

<RT data: public>+≡
    public :: rt_data_global_final

<RT data: procedures>+≡
    subroutine rt_data_global_final (global)
        type(rt_data_t), intent(inout) :: global
        call var_list_final (global%var_list)
        if (global%sf_list_allocated) then
            call sf_list_final (global%sf_list)
            deallocate (global%sf_list)
        end if
    end subroutine rt_data_global_final

```

```

        global%sf_list_allocated = .false.
    end if
    deallocate (global%it_list_default)
    call file_list_final (global%out_files)
    deallocate (global%out_files)
    deallocate (global%rng)
end subroutine rt_data_global_final

```

16.6 Compilation

This module manages compilation and loading of process libraries. It is needed as a separate module because integration depends on it.

```

<compilations.f90>≡
  <File header>

  module compilations

    <Use strings>
    use diagnostics !NODEP!
    use os_interface
    use variables
    use process_libraries
    use rt_data

    <Standard module head>

    <Compilations: public>

    <Compilations: types>

    <Compilations: interfaces>

    contains

    <Compilations: procedures>

  end module compilations

```

16.6.1 The data type

This data type serves as a container that collects all necessary data; the procedures `compile` and `load` operate on it internally.

```

<Compilations: types>≡
  type :: compilation_t
    type(string_t) :: libname
    type(process_library_t), pointer :: prc_lib => null ()
    logical :: recompile_library = .false.
    logical :: make_executable = .false.
  end type compilation_t

```

Initialize:

```
(Compilations: procedures)≡  
  subroutine compilation_basic_init (comp, libname, var_list)  
    type(compilation_t), intent(out) :: comp  
    type(string_t), intent(in) :: libname  
    type(var_list_t), intent(in) :: var_list  
    comp%libname = libname  
    comp%prc_lib => process_library_store_get_ptr (comp%libname)  
    if (.not. associated (comp%prc_lib)) then  
      call msg_fatal ("Process library '" // char (comp%libname) &  
        // "' has not been declared.")  
    end if  
    comp%recompile_library = &  
      var_list_get_lval (var_list, var_str ("?recompile_library"))  
  end subroutine compilation_basic_init
```

Compile

```
(Compilations: procedures)+≡  
  subroutine compilation_compile_and_link (comp, os_data)  
    type(compilation_t), intent(inout) :: comp  
    type(os_data_t), intent(in) :: os_data  
    type(string_t) :: objlist  
    if (associated (comp%prc_lib)) then  
      if (process_library_get_n_processes (comp%prc_lib) > 0) then  
        call process_library_generate_code (comp%prc_lib, os_data)  
        call process_library_write_driver (comp%prc_lib)  
        call process_library_compile &  
          (comp%prc_lib, os_data, comp%recompile_library, objlist)  
        call process_library_link &  
          (comp%prc_lib, os_data, objlist)  
      end if  
    end if  
  end subroutine compilation_compile_and_link
```

Make a stand-alone executable

```
(Compilations: procedures)+≡  
  subroutine compilations_make_executable (comp, os_data, exec_name, var_list)  
    type(compilation_t), dimension(:), intent(in) :: comp  
    type(os_data_t), intent(in) :: os_data  
    type(string_t), intent(in) :: exec_name  
    type(var_list_t), intent(in) :: var_list  
    type(string_t) :: flags  
    integer :: lib  
    type(user_procs_t) :: user_procs  
    call splice &  
      (var_list_get_sval (var_list, var_str ("user_procs_cut")), &  
        user_procs%cut)  
    call splice &  
      (var_list_get_sval (var_list, var_str ("user_procs_event_shape")), &  
        user_procs%event_shape)  
    call splice &  
      (var_list_get_sval (var_list, var_str ("user_procs_obs1")), &  
        user_procs%obs_real_unary)
```

```

call splice &
  (var_list_get_sval (var_list, var_str ("user_procs_obs2")), &
   user_procs%obs_real_binary)
call splice &
  (var_list_get_sval (var_list, var_str ("user_procs_sf")), &
   user_procs%sf) ! $
call write_library_manager (comp%libname, user_procs)
call compile_library_manager (os_data)
flags = ""
do lib = 1, size (comp)
  flags = flags // get_modellibs_flags (comp(lib)%prc_lib, os_data)
end do
call link_executable (comp%libname, exec_name, flags, os_data)
contains
subroutine splice (string, array)
  type(string_t), intent(in) :: string
  type(string_t), dimension(:), intent(out), allocatable :: array
  type(string_t) :: buffer, word, separator
  integer :: n_commas, i
  if (string /= "") then
    buffer = string
    n_commas = 0
    COUNT_COMMAS: do
      call split (buffer, word, ",", separator)
      if (len (separator) == 0) exit COUNT_COMMAS
      n_commas = n_commas + 1
    end do COUNT_COMMAS
    allocate (array (n_commas + 1))
    buffer = string
    ASSIGN_STRINGS: do i = 1, size (array)
      call split (buffer, word, ",")
      array(i) = adjustl (trim (word))
    end do ASSIGN_STRINGS
  else
    allocate (array (0))
  end if
end subroutine splice
end subroutine compilations_make_executable

```

Load the library

(Compilations: procedures)+≡

```

subroutine compilation_load_library (comp, os_data, global_var_list)
  type(compilation_t), intent(in) :: comp
  type(os_data_t), intent(in) :: os_data
  type(var_list_t), intent(inout) :: global_var_list
  type(process_library_t), pointer :: prc_lib
  call process_library_store_append (comp%libname, os_data, prc_lib)
  call process_library_load (prc_lib, os_data, var_list=global_var_list)
end subroutine compilation_load_library

```

16.6.2 API for compilation and loading

The `global` data set may actually be local to the caller. The `global_prc_lib` and `global_var_list` are the places to store the loaded library and its name.

```
<Compilations: public>≡
    public :: compile_library

<Compilations: interfaces>≡
    interface compile_library
        module procedure compile_library0
        module procedure compile_library1
    end interface

<Compilations: procedures>+≡
    subroutine compile_library0 (libname, global, global_var_list, global_prc_lib)
        type(string_t), intent(in) :: libname
        type(rt_data_t), intent(in) :: global
        type(var_list_t), intent(inout) :: global_var_list
        type(process_library_t), pointer :: global_prc_lib
        type(compilation_t) :: comp
        call compilation_basic_init (comp, libname, global%var_list)
        call compilation_compile_and_link (comp, global%os_data)
        call compilation_load_library (comp, global%os_data, global_var_list)
        global_prc_lib => comp%prc_lib
    end subroutine compile_library0

    subroutine compile_library1 (libname, global, global_var_list, global_prc_lib)
        type(string_t), dimension(:), intent(in) :: libname
        type(rt_data_t), intent(in) :: global
        type(var_list_t), intent(inout) :: global_var_list
        type(process_library_t), pointer :: global_prc_lib
        integer :: lib
        do lib = 1, size (libname)
            call compile_library0 &
                (libname(lib), global, global_var_list, global_prc_lib)
        end do
    end subroutine compile_library1
```

Compile the processes. Do not load the library (libraries), but link them to a separate executable.

```
<Compilations: public>+≡
    public :: compile_executable

<Compilations: interfaces>+≡
    interface compile_executable
        module procedure compile_executable0
        module procedure compile_executable1
    end interface

<Compilations: procedures>+≡
    subroutine compile_executable0 (libname, exec_name, global)
        type(string_t), intent(in) :: libname, exec_name
        type(rt_data_t), intent(in) :: global
        type(compilation_t), dimension(1) :: comp
```



```

    call compilation_basic_init (comp(1), libname, global%var_list)
    call compilation_compile_and_link (comp(1), global%os_data)
    call compilations_make_executable &
        (comp, global%os_data, exec_name, global%var_list)
end subroutine compile_executable0

subroutine compile_executable1 (libname, exec_name, global)
    type(string_t), dimension(:), intent(in) :: libname
    type(string_t), intent(in) :: exec_name
    type(rt_data_t), intent(in) :: global
    type(compilation_t), dimension(size(libname)) :: comp
    integer :: lib
    do lib = 1, size (libname)
        call compilation_basic_init (comp(lib), libname(lib), global%var_list)
        call compilation_compile_and_link (comp(lib), global%os_data)
    end do
    call compilations_make_executable &
        (comp, global%os_data, exec_name, global%var_list)
end subroutine compile_executable1

```

Just load the library (libraries), no compile.

```

<Compilations: public>+≡
    public :: load_library

<Compilations: interfaces>+≡
    interface load_library
        module procedure load_library0
        module procedure load_library1
    end interface

<Compilations: procedures>+≡
    subroutine load_library0 (libname, global, global_var_list, global_prc_lib)
        type(string_t), intent(in) :: libname
        type(rt_data_t), intent(in) :: global
        type(var_list_t), intent(inout) :: global_var_list
        type(process_library_t), pointer :: global_prc_lib
        type(compilation_t) :: comp
        call compilation_basic_init (comp, libname, global%var_list)
        call compilation_load_library (comp, global%os_data, global_var_list)
        global_prc_lib => comp%prc_lib
    end subroutine load_library0

    subroutine load_library1 (libname, global, global_var_list, global_prc_lib)
        type(string_t), dimension(:), intent(in) :: libname
        type(rt_data_t), intent(in) :: global
        type(var_list_t), intent(inout) :: global_var_list
        type(process_library_t), pointer :: global_prc_lib
        integer :: lib
        do lib = 1, size (libname)
            call load_library0 &
                (libname(lib), global, global_var_list, global_prc_lib)
        end do
    end subroutine load_library1

```

16.7 Integration

This module manages phase space setup, matrix-element evaluation and integration, as far as it is not done by lower-level routines, in particular in the `processes` module.

```
<integrations.f90>≡  
  <File header>  
  
  module integrations  
  
    <Use kinds>  
    <Use strings>  
    <Use file utils>  
    use limits, only: ITERATIONS_DEFAULT_LIST_SIZE !NODEP!  
    use diagnostics !NODEP!  
    use tao_random_numbers !NODEP!  
    use pdf_builtin !NODEP!  
    use os_interface  
    use parser  
    use variables  
    use models  
    use beams  
    use mappings  
    use phs_forests  
    use process_libraries  
    use processes  
    use strfun_config  
    use rt_data  
    use iterations  
    use compilations  
  
    <Standard module head>  
  
    <Integrations: public>  
  
    <Integrations: types>  
  
    <Integrations: interfaces>  
  
    contains  
  
    <Integrations: procedures>  
  
  end module integrations
```

16.7.1 The integration type

This type holds all relevant data, the integration methods operates on this. In contrast to the `simulation_t` introduced later, the `integration_t` applies to a single process. We need not export it.

```
<Integrations: types>≡  
  type :: integration_t  
    private
```

```

type(string_t) :: process_id
type(process_t), pointer :: process => null ()
type(string_t) :: run_id
logical :: rebuild_phs = .false.
logical :: check_phs_file = .true.
type(string_t) :: phs_filename
type(string_t) :: phs_filename_out
type(string_t) :: phs_filename_vis
logical :: phs_only = .false.
logical :: vis_channels = .false.
type(phs_parameters_t) :: phs_par
type(mapping_defaults_t) :: mapping_defaults
logical :: rebuild_grids = .false.
logical :: check_grid_file = .true.
type(grid_parameters_t) :: grid_parameters
type(string_t) :: grids_filename
logical :: use_best_grid = .true.
real(default) :: accuracy_goal = 0
real(default) :: abs_error_goal = 0
real(default) :: rel_error_goal = 0
logical :: helicity_selection_active = .false.
real(default) :: helicity_selection_threshold = -1
integer :: helicity_selection_cutoff = 1000
logical :: sqrts_known = .false.
real(default) :: sqrts = -1
real(default) :: alpha_s = -1
integer :: n_events_for_me_test = 0
logical :: time_estimate = .false.
logical :: vis_history = .true.
type(string_t) :: history_filename
type(beam_data_t) :: beam_data
logical :: use_beams = .false.
type(sf_list_t), pointer :: sf_list => null ()
logical :: use_strfun = .false.
type(iterations_list_t) :: it_list
integer :: pass_on_file = 0
integer :: it_on_file = 0
type(md5sum_grids_t) :: md5sum
integer :: pass = 0
integer :: it = 0
type(string_t) :: log_filename
end type integration_t

```

16.7.2 Initialization

Basic setup: Process name, flags, parameters.

(Integrations: procedures)≡

```

subroutine integration_basic_init (intg, process_id, var_list, verbose)
  type(integration_t), intent(out) :: intg
  type(string_t), intent(in) :: process_id
  type(var_list_t), intent(in) :: var_list
  logical, intent(in), optional :: verbose

```

```

logical :: verb
intg%process_id = process_id
intg%run_id = var_list_get_sval (var_list, var_str ("$_run_id")) ! $
verb = .true.; if (present (verbose)) verb = verbose
if (verb) then
  call msg_message ("Initializating integration for process " &
    // char (intg%process_id) // ":")
  if (intg%run_id /= "") then
    call msg_message ("Run ID = " // ' ' // char (intg%run_id) // ' ')
  end if
end if
intg%rebuild_phs = &
  var_list_get_lval (var_list, var_str ("?rebuild_phase_space"))
intg%check_phs_file = &
  var_list_get_lval (var_list, var_str ("?check_phs_file"))
intg%phs_filename = &
  var_list_get_sval (var_list, var_str ("$_phs_file")) ! $
intg%phs_only = &
  var_list_get_lval (var_list, var_str ("?phs_only"))
intg%vis_channels = &
  var_list_get_lval (var_list, var_str ("?vis_channels"))
intg%phs_par%m_threshold_s = &
  var_list_get_rval (var_list, var_str ("phs_threshold_s"))
intg%phs_par%m_threshold_t = &
  var_list_get_rval (var_list, var_str ("phs_threshold_t"))
intg%phs_par%off_shell = &
  var_list_get_ival (var_list, var_str ("phs_off_shell"))
intg%phs_par%keep_nonresonant = &
  var_list_get_lval (var_list, var_str ("?phs_keep_nonresonant"))
intg%phs_par%t_channel = &
  var_list_get_ival (var_list, var_str ("phs_t_channel"))
intg%mapping_defaults%energy_scale = &
  var_list_get_rval (var_list, var_str ("phs_e_scale"))
intg%mapping_defaults%invariant_mass_scale = &
  var_list_get_rval (var_list, var_str ("phs_m_scale"))
intg%mapping_defaults%momentum_transfer_scale = &
  var_list_get_rval (var_list, var_str ("phs_q_scale"))
intg%mapping_defaults%step_mapping = &
  var_list_get_lval (var_list, var_str ("?phs_step_mapping"))
intg%mapping_defaults%step_mapping_exp = &
  var_list_get_lval (var_list, var_str ("?phs_step_mapping_exp"))
intg%mapping_defaults%enable_s_mapping = &
  var_list_get_lval (var_list, var_str ("?phs_s_mapping"))
intg%rebuild_grids = &
  var_list_get_lval (var_list, var_str ("?rebuild_grids"))
intg%check_grid_file = &
  var_list_get_lval (var_list, var_str ("?check_grid_file"))
intg%grid_parameters%threshold_calls = &
  var_list_get_ival (var_list, var_str ("threshold_calls"))
intg%grid_parameters%min_calls_per_channel = &
  var_list_get_ival (var_list, var_str ("min_calls_per_channel"))
intg%grid_parameters%min_calls_per_bin = &
  var_list_get_ival (var_list, var_str ("min_calls_per_bin"))
intg%grid_parameters%min_bins = &

```

```

        var_list_get_ival (var_list, var_str ("min_bins"))
    intg%grid_parameters%max_bins = &
        var_list_get_ival (var_list, var_str ("max_bins"))
    intg%grid_parameters%stratified = &
        var_list_get_lval (var_list, var_str ("?stratified"))
    intg%grid_parameters%use_vamp_equivalences = &
        var_list_get_lval (var_list, var_str ("?use_vamp_equivalences"))
    intg%grid_parameters%channel_weights_power = &
        var_list_get_rval (var_list, var_str ("channel_weights_power"))
    intg%run_id = &
        var_list_get_sval (var_list, var_str ("$_run_id")) ! $
    if (intg%run_id /= "") then
        intg%phs_filename_out = intg%process_id // "." // intg%run_id // ".phs"
        intg%phs_filename_vis = intg%process_id // "." // intg%run_id // "_phs"
        intg%grids_filename = intg%process_id // "." // intg%run_id // ".vg"
        intg%history_filename = intg%process_id // "." // intg%run_id &
            // ".history"
        intg%log_filename = intg%process_id // "." // intg%run_id // ".log"
    else
        intg%phs_filename_out = intg%process_id // ".phs"
        intg%phs_filename_vis = intg%process_id // "_phs"
        intg%grids_filename = intg%process_id // ".vg"
        intg%history_filename = intg%process_id // ".history"
        intg%log_filename = intg%process_id // ".log"
    end if
    intg%use_best_grid = &
        var_list_get_lval (var_list, var_str ("?use_best_grid"))
    intg%accuracy_goal = &
        var_list_get_rval (var_list, var_str ("accuracy_goal"))
    intg%abs_error_goal = &
        var_list_get_rval (var_list, var_str ("error_goal"))
    intg%rel_error_goal = &
        var_list_get_rval (var_list, var_str ("relative_error_goal"))
    intg%helicity_selection_active = &
        var_list_get_lval (var_list, var_str ("?helicity_selection_active"))
    if (intg%helicity_selection_active) then
        intg%helicity_selection_threshold = var_list_get_rval (var_list, &
            var_str ("helicity_selection_threshold"))
        intg%helicity_selection_cutoff = var_list_get_ival (var_list, &
            var_str ("helicity_selection_cutoff"))
    end if
    if (var_list_is_known (var_list, var_str ("alphas"))) then
        intg%alpha_s = var_list_get_rval (var_list, var_str ("alphas"))
    end if
    intg%sqrts_known = var_list_is_known (var_list, "sqrts")
    intg%sqrts = var_list_get_rval (var_list, "sqrts")
    intg%time_estimate = &
        var_list_get_lval (var_list, var_str ("?time_estimate"))
    intg%vis_history = &
        var_list_get_lval (var_list, var_str ("?vis_history"))
    intg%n_events_for_me_test = &
        var_list_get_ival (var_list, var_str ("n_events"))
end subroutine integration_basic_init

```

Initialize and check beam parameters; if we are using beams, beam masses must be consistent with the current model.

(Integrations: procedures)+≡

```
subroutine integration_check_beam_data (intg, beam_data)
  type(integration_t), intent(inout) :: intg
  type(beam_data_t), intent(in) :: beam_data
  intg%beam_data = beam_data
  intg%use_beams = beam_data_are_valid (intg%beam_data)
  if (intg%use_beams) then
    if (.not. beam_data_masses_are_consistent (intg%beam_data)) then
      call msg_warning &
        ("Masses of beam particle(s) differ from beam masses")
    end if
  end if
end subroutine integration_check_beam_data
```

Initialize the process library: if the process library is not yet compiled, insert a compilation.

(Integrations: procedures)+≡

```
subroutine maybe_compile_library (global)
  type(rt_data_t), target :: global
  call process_library_update_status (global%prc_lib)
  if (.not. process_library_is_compiled (global%prc_lib)) then
    call compile_library (process_library_get_name (global%prc_lib), &
      global, global%var_list, global%prc_lib)
  end if
end subroutine maybe_compile_library
```

Initialize the process.

(Integrations: procedures)+≡

```
subroutine integration_init_process (intg, prc_lib, model, var_list, ok)
  type(integration_t), intent(inout) :: intg
  type(process_library_t), intent(inout), target :: prc_lib
  type(model_t), intent(in), target :: model
  type(var_list_t), intent(in), target :: var_list
  logical, intent(out) :: ok
  call process_store_init_process (intg%process, &
    prc_lib, intg%process_id, model, var_list, &
    use_beams = intg%use_beams)
  if (.not. process_is_valid (intg%process)) then
    call msg_fatal ("Process '" &
      // char (intg%process_id) // "': " &
      // "initialization failed.")
    ok = .false.
  else if (.not. intg%phs_only) then
    ok = process_has_matrix_element (intg%process)
  else
    ok = .true.
  end if
  call process_reset_helicity_selection (intg%process, &
    intg%helicity_selection_threshold, intg%helicity_selection_cutoff)
end subroutine integration_init_process
```

Set up beams and structure functions for the process that has been initialized.

(Integrations: procedures)+≡

```

subroutine integration_setup_beams (intg, sf_list, var_list, ok)
  type(integration_t), intent(inout) :: intg
  type(sf_list_t), pointer :: sf_list
  type(var_list_t), intent(in) :: var_list
  logical, intent(out) :: ok
  if (intg%use_beams) then
    if (beam_data_get_n_in (intg%beam_data) &
        == process_get_n_in (intg%process)) then
      if (associated (sf_list)) then
        intg%sf_list => sf_list
        call process_setup_beams (intg%process, intg%beam_data, &
            sf_list_get_n_strfun (intg%sf_list))
        call process_check_beam_setup (intg%process, var_list)
        call sf_list_transfer_to_process (intg%sf_list, intg%process)
        intg%use_strfun = .true.
      else
        call process_setup_beams (intg%process, intg%beam_data, 0)
      end if
      ok = .true.
    else
      call msg_fatal ("Process '" // char (intg%process_id) &
          // "': beam/process mismatch (collision/decay)", &
          (/ var_str (" -----"), &
              var_str ("This possibly means that you tried to generate "), &
              var_str ("a forbidden process, for which WHIZARD could not"), &
              var_str ("find a matrix element. Or there is a"), &
              var_str ("mismatch between beams and hard interaction.") /) )
      ok = .false.
    end if
  else if (intg%sqrts_known) then
    call process_setup_beams &
        (intg%process, intg%beam_data, 0, sqrts = intg%sqrts)
  else
    call process_setup_beams &
        (intg%process, intg%beam_data, 0)
  end if
  if (ok) call process_connect_strfun (intg%process, ok)
  if (.not. ok) then
    call msg_error ("Process '" // char (intg%process_id) &
        // "': beam/structure function setup failed.")
  end if
end subroutine integration_setup_beams

```

Set up the QCD part of the process, i.e., the α_s handling. This also initializes LHAPDF, if necessary. Data are taken from the structure-function setup, where possible, otherwise from the variable list. As a side-effect, the MD5 checksum for the QCD data is computed and stored in the process data.

(Integrations: procedures)+≡

```

subroutine integration_setup_qcd &
    (intg, lhpdf_status, pdf_builtin_status, os_data, var_list)
  type(integration_t), intent(inout) :: intg

```

```

type(lhapdf_status_t), intent(inout) :: lhpdf_status
type(pdf_builtin_status_t), intent(inout) :: pdf_builtin_status
type(os_data_t), intent(in) :: os_data
type(var_list_t), intent(in) :: var_list
if (intg%alpha_s > 0) call process_set_alpha_s (intg%process, intg%alpha_s)
if (associated (intg%sf_list)) then
    call process_setup_qcd (intg%process, &
        lhpdf_status, pdf_builtin_status, &
        sf_list_get_lhapdf_data_ptr (intg%sf_list), &
        sf_list_get_pdf_builtin_data_ptr (intg%sf_list), &
        os_data, var_list)
else
    call process_setup_qcd (intg%process, &
        lhpdf_status, pdf_builtin_status, &
        null (), null (), &
        os_data, var_list)
end if
end subroutine integration_setup_qcd

```

Set up phase space. Must be done after beams setup, since `sqrts` must be known.

(Integrations: procedures)+≡

```

subroutine integration_setup_phase_space (intg, os_data, ok)
    type(integration_t), intent(inout) :: intg
    type(os_data_t), intent(in) :: os_data
    logical, intent(out) :: ok
    if (intg%phs_filename == "") then
        call process_setup_phase_space (intg%process, &
            intg%rebuild_phs, &
            os_data, &
            intg%phs_par, intg%mapping_defaults, &
            filename_out = intg%phs_filename_out, &
            filename_vis = intg%phs_filename_vis, &
            vis_channels = intg%vis_channels, &
            check_phs_file = intg%check_phs_file, &
            ok = ok)
    else
        call process_setup_phase_space (intg%process, &
            intg%rebuild_phs, &
            os_data, &
            intg%phs_par, intg%mapping_defaults, &
            filename_in = intg%phs_filename, &
            filename_out = intg%phs_filename_out, &
            filename_vis = intg%phs_filename_vis, &
            vis_channels = intg%vis_channels, &
            ok = ok)
    end if
    if (ok) then
        if (intg%phs_only) then
            call msg_message ("Process '" // char (intg%process_id) &
                // "': phase space setup complete.")
        end if
    else

```



```

        call msg_error ("Process '" // char (intg%process_id) &
            // "' : phase space setup failed.")
    end if
end subroutine integration_setup_phase_space

```

The structure function mappings depend on the number of phase-space channels, therefore this comes after the phase-space setup. It completes the structure-function setup.

```

<Integrations: procedures>+≡
subroutine integration_setup_strfun_mappings (intg)
    type(integration_t), intent(inout) :: intg
    if (intg%use_strfun) then
        call sf_list_setup_mappings (intg%sf_list, intg%process)
    end if
end subroutine integration_setup_strfun_mappings

```

Set up the list of iterations and allocate the VAMP history accordingly.

```

<Integrations: procedures>+≡
subroutine integration_setup_iterations &
    (intg, it_list, it_list_default, ok, verbose)
    type(integration_t), intent(inout) :: intg
    type(iterations_list_t), intent(in) :: it_list
    type(iterations_list_t), dimension(:), intent(in) :: it_list_default
    logical, intent(out) :: ok
    logical, intent(in), optional :: verbose
    integer :: n_in, n_out
    logical :: verb
    verb = .true.; if (present (verbose)) verb = verbose
    ok = .true.
    n_in = process_get_n_in (intg%process)
    n_out = process_get_n_out (intg%process)
    intg%it_list = it_list
    if (iterations_list_get_n_pass (intg%it_list) > 0) then
        call iterations_list_complete (intg%it_list, it_list_default(n_out))
    else
        select case (n_out)
        case (:1)
            call msg_error ("Integrate: number of outgoing particles " &
                // "must be at least 2")
            ok = .false.
        case (2:ITERATIONS_DEFAULT_LIST_SIZE)
            intg%it_list = it_list_default(n_out + (n_in-2))
        case default
            intg%it_list = it_list_default(ITERATIONS_DEFAULT_LIST_SIZE)
        end select
    end if
    call iterations_list_adjust_n_calls (intg%it_list, &
        intg%process, intg%grid_parameters)
    if (verb) call iterations_list_write (intg%it_list)
    call process_init_vamp_history &
        (intg%process, iterations_list_get_n_it (intg%it_list))
end subroutine integration_setup_iterations

```

Compute MD5 sums that are used for checking grid files. MD5 sums for cuts etc. are redefined when those structures are set up, see below. Some MD5 sum are computed from process data directly, so they are not set here.

```
(Integrations: procedures)+≡
subroutine integration_collect_md5sums (intg)
  type(integration_t), intent(inout) :: intg
  if (intg%use_beams) then
    intg%md5sum%beams = beam_data_get_md5sum (intg%beam_data, intg%sqrts)
  else
    intg%md5sum%beams = ""
  end if
  if (intg%use_strfun) then
    intg%md5sum%sf_list = sf_list_get_md5sum (intg%sf_list)
  else
    intg%md5sum%sf_list = ""
  end if
  intg%md5sum%mappings = mapping_defaults_md5sum (intg%mapping_defaults)
end subroutine integration_collect_md5sums
```

Setup up the subevt object inside the process object which is used by cuts, weight, scale.

```
(Integrations: procedures)+≡
subroutine integration_setup_subevt (intg)
  type(integration_t), intent(inout) :: intg
  call process_setup_subevt (intg%process)
end subroutine integration_setup_subevt
```

Set up cuts, user weight, scale.

```
(Integrations: procedures)+≡
subroutine integration_setup_cuts (intg, pn_cuts_lexpr, verbose)
  type(integration_t), intent(inout) :: intg
  type(parse_node_t), pointer :: pn_cuts_lexpr
  logical, intent(in), optional :: verbose
  logical :: verb
  verb = .true.; if (present (verbose)) verb = verbose
  if (associated (pn_cuts_lexpr)) then
    call process_setup_cuts (intg%process, pn_cuts_lexpr, &
      intg%md5sum%cuts)
    if (verb) call msg_message ("Applying user-defined cuts.")
  else
    if (verb) call msg_warning ("No cuts have been defined.")
  end if
end subroutine integration_setup_cuts
```

```
(Integrations: procedures)+≡
subroutine integration_setup_weight (intg, pn_weight_expr, verbose)
  type(integration_t), intent(inout) :: intg
  type(parse_node_t), pointer :: pn_weight_expr
  logical, intent(in), optional :: verbose
  logical :: verb
  verb = .true.; if (present (verbose)) verb = verbose
  if (associated (pn_weight_expr)) then
```

```

        call process_setup_weight (intg%process, pn_weight_expr, &
            intg%md5sum%weight)
        if (verb) call msg_message ("Using user-defined reweighting factor.")
    end if
end subroutine integration_setup_weight

```

(Integrations: procedures)+≡

```

subroutine integration_setup_scale (intg, pn_scale_expr, verbose)
    type(integration_t), intent(inout) :: intg
    type(parse_node_t), pointer :: pn_scale_expr
    logical, intent(in), optional :: verbose
    logical :: verb
    verb = .true.; if (present (verbose)) verb = verbose
    if (associated (pn_scale_expr)) then
        call process_setup_scale (intg%process, pn_scale_expr, &
            intg%md5sum%scale)
        if (verb) call msg_message ("Using user-defined general scale.")
    end if
end subroutine integration_setup_scale

```

(Integrations: procedures)+≡

```

subroutine integration_setup_fac_scale (intg, pn_scale_expr, verbose)
    type(integration_t), intent(inout) :: intg
    type(parse_node_t), pointer :: pn_scale_expr
    logical, intent(in), optional :: verbose
    logical :: verb
    verb = .true.; if (present (verbose)) verb = verbose
    if (associated (pn_scale_expr)) then
        call process_setup_fac_scale (intg%process, pn_scale_expr, &
            intg%md5sum%fac_scale)
        if (verb) call msg_message ("Using user-defined factorization scale.")
    end if
end subroutine integration_setup_fac_scale

```

(Integrations: procedures)+≡

```

subroutine integration_setup_ren_scale (intg, pn_scale_expr, verbose)
    type(integration_t), intent(inout) :: intg
    type(parse_node_t), pointer :: pn_scale_expr
    logical, intent(in), optional :: verbose
    logical :: verb
    verb = .true.; if (present (verbose)) verb = verbose
    if (associated (pn_scale_expr)) then
        call process_setup_ren_scale (intg%process, pn_scale_expr, &
            intg%md5sum%ren_scale)
        if (verb) call msg_message ("Using user-defined renormalization scale.")
    end if
end subroutine integration_setup_ren_scale

```

Set up integration grids for the first iteration and check whether the grids already contain previous results.

(Integrations: procedures)+≡

```

subroutine integration_setup_grids (intg, verbose)

```

```

type(integration_t), intent(inout) :: intg
logical, intent(in), optional :: verbose
integer :: n_calls
logical :: verb, ok
verb = .true.; if (present (verbose)) verb = verbose
call process_store_iteration_parameters (intg%process, &
    iterations_list_get_pass_array (intg%it_list), &
    iterations_list_get_n_calls_array (intg%it_list))
if (iterations_list_get_n_pass (intg%it_list) > 0) then
    n_calls = iterations_list_get_n_calls (intg%it_list, 1)
    if (.not. intg%rebuild_grids) then
        call process_read_grid_file (intg%process, intg%grids_filename, &
            intg%check_grid_file, intg%md5sum, intg%grid_parameters, &
            iterations_list_get_pass_array (intg%it_list), &
            iterations_list_get_n_calls_array (intg%it_list), &
            ok)
        intg%rebuild_grids = .not. ok
    end if
    if (intg%rebuild_grids) then
        call process_setup_grids &
            (intg%process, intg%grid_parameters, calls=n_calls)
    end if
    if (verb) then
        write (msg_buffer, "(4(I0,A),A,L1)" ) &
            n_calls, " calls, ", &
            process_get_n_channels (intg%process), " channels, ", &
            process_get_n_parameters (intg%process), " dimensions, ", &
            process_get_n_bins (intg%process), " bins, ", &
            "stratified = ", intg%grid_parameters%stratified
        call msg_message ()
    end if
    intg%pass_on_file = process_get_current_pass (intg%process)
    intg%it_on_file = process_get_current_it (intg%process)
end if
end subroutine integration_setup_grids

```

16.7.3 Integration

Write the header for the integration results.

(Integrations: procedures)+≡

```

subroutine integration_write_header (intg, verbose)
type(integration_t), intent(inout) :: intg
logical, intent(in), optional :: verbose
logical :: verb
integer :: u
verb = .true.; if (present (verbose)) verb = verbose
if (verb) then
    call msg_message ("Integrating process '" &
        // char (intg%process_id) // "':")
    u = logfile_unit ()
    call process_results_write_header (intg%process, logfile=.false.)
    if (u > 0) then

```

```

        call process_results_write_header (intg%process, unit=u)
        flush (u)
    end if
end if
end subroutine integration_write_header

```

Integrate: this does a single-iteration pass. If the results are already on file, just write them, otherwise do one VAMP integration per iteration.

(Integrations: procedures)+≡

```

subroutine integration_warmup (intg, rng, pass, verbose)
    type(integration_t), intent(inout) :: intg
    type(tao_random_state), intent(inout) :: rng
    integer, intent(in) :: pass
    logical, intent(in), optional :: verbose
    integer :: n_it, n_calls, i, u
    logical :: iteration_is_on_file, adapt_grids, adapt_weights
    logical :: verb
    real(default) :: last_accuracy, current_accuracy
    real(default) :: last_abs_error, current_abs_error
    real(default) :: last_rel_error, current_rel_error
    logical :: accuracy_reached, abs_error_reached, rel_error_reached
    logical :: goal_set
    verb = .true.; if (present (verbose)) verb = verbose
    u = logfile_unit ()
    intg%pass = pass
    n_calls = iterations_list_get_n_calls (intg%it_list, intg%pass)
    if (iterations_list_has_custom_adaptation (intg%it_list, intg%pass)) then
        adapt_grids = iterations_list_adapt_grids (intg%it_list, intg%pass)
        adapt_weights = iterations_list_adapt_weights (intg%it_list, intg%pass)
    else
        adapt_grids = .true.
        adapt_weights = .true.
    end if
    last_accuracy = 0
    last_abs_error = 0
    last_rel_error = 0
    goal_set = intg%accuracy_goal > 0 &
        .or. intg%abs_error_goal > 0 .or. intg%rel_error_goal > 0
    accuracy_reached = .false.
    abs_error_reached = .false.
    rel_error_reached = .false.
    n_it = iterations_list_get_n_it (intg%it_list, intg%pass)
    LOOP_IT: do i = 1, n_it
        intg%it = intg%it + 1
        iteration_is_on_file = intg%pass < intg%pass_on_file &
            .or. intg%pass == intg%pass_on_file .and. i <= intg%it_on_file
        if (iteration_is_on_file) then
            current_accuracy = process_get_accuracy (intg%process, it=intg%it)
            current_abs_error = process_get_error (intg%process, it=intg%it)
            current_rel_error = process_get_rel_error (intg%process, it=intg%it)
            if (current_accuracy == 0) then
                if (.not. goal_set .or. &
                    intg%accuracy_goal > 0 .and. .not. accuracy_reached .or. &

```

```

        intg%abs_error_goal > 0 .and. .not. abs_error_reached .or. &
        intg%rel_error_goal > 0 .and. .not. rel_error_reached) then
    call process_discard_results (intg%process, intg%it)
    intg%pass_on_file = process_get_current_pass (intg%process)
    intg%it_on_file = process_get_current_it (intg%process)
    iteration_is_on_file = .false.
else
    call msg_message &
        ("Accuracy/error goals reached, skipped iterations")
    intg%it = intg%it + n_it - i
    exit LOOP_IT
end if
end if
end if
if (iteration_is_on_file) then
    if (verb) then
        call process_results_write_entry (intg%process, intg%it)
        if (u > 0) then
            call process_results_write_entry (intg%process, intg%it, unit=u)
            flush (u)
        end if
    end if
else
    if (.not. goal_set .or. &
        intg%accuracy_goal > 0 .and. .not. accuracy_reached .or. &
        intg%abs_error_goal > 0 .and. .not. abs_error_reached .or. &
        intg%rel_error_goal > 0 .and. .not. rel_error_reached) then
        call process_integrate (intg%process, rng, &
            intg%grid_parameters, &
            intg%pass, 1, 1, n_calls, &
            discard_integrals = i==1, &
            adapt_grids = adapt_grids, &
            adapt_weights = adapt_weights .and. i>2, &
            print_current = verb, &
            time_estimate = intg%time_estimate, &
            grids_filename = intg%grids_filename, &
            write_best_grid = intg%use_best_grid, &
            md5sum = intg%md5sum, &
            history_filename = intg%history_filename, &
            log_filename = intg%log_filename)
    else
        call msg_message &
            ("Accuracy/error goals reached, skipping iterations")
        call process_skip_iterations &
            (intg%process, pass, intg%it - 1, n_it - i + 1)
        intg%it = intg%it + n_it - i
        exit LOOP_IT
    end if
    current_accuracy = process_get_accuracy (intg%process, it=intg%it)
    current_abs_error = process_get_error (intg%process, it=intg%it)
    current_rel_error = process_get_rel_error (intg%process, it=intg%it)
end if
last_accuracy = current_accuracy
last_abs_error = current_abs_error

```

```

        last_rel_error = current_rel_error
        accuracy_reached = last_accuracy < intg%accuracy_goal
        abs_error_reached = last_abs_error < intg%abs_error_goal
        rel_error_reached = last_rel_error < intg%rel_error_goal
    end do LOOP_IT
    if (verb) then
        call process_results_write_average (intg%process, intg%pass)
        if (u > 0) then
            call process_results_write_average (intg%process, intg%pass, unit=u)
            flush (u)
        end if
    end if
end subroutine integration_warmup

```

Integrate: do the final integration. Here, we do a multi-iteration integration. Again, we skip iterations that are already on file. Record the results in the global variable list.

(Integrations: procedures)+≡

```

subroutine integration_evaluate &
    (intg, rng, pass, global_var_list, os_data, verbose)
    type(integration_t), intent(inout) :: intg
    type(tao_random_state), intent(inout) :: rng
    integer, intent(in) :: pass
    type(var_list_t), intent(inout) :: global_var_list
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: verbose
    integer :: it_on_file, n_calls, n_it, i, u
    logical :: adapt_grids, adapt_weights
    logical :: verb
    verb = .true.; if (present (verbose)) verb = verbose
    u = logfile_unit ()
    intg%pass = pass
    if (intg%pass == intg%pass_on_file) then
        it_on_file = intg%it_on_file
    else
        it_on_file = 0
    end if
    n_calls = iterations_list_get_n_calls (intg%it_list, intg%pass)
    n_it = iterations_list_get_n_it (intg%it_list, intg%pass)
    if (iterations_list_has_custom_adaptation (intg%it_list, intg%pass)) then
        adapt_grids = iterations_list_adapt_grids (intg%it_list, intg%pass)
        adapt_weights = iterations_list_adapt_weights (intg%it_list, intg%pass)
    else
        adapt_grids = .true.
        adapt_weights = .false.
    end if
    do i = 1, it_on_file
        intg%it = intg%it + 1
        if (verb) then
            call process_results_write_entry (intg%process, intg%it)
            if (u > 0) then
                call process_results_write_entry (intg%process, intg%it, unit=u)
                flush (u)
            end if
        end if
    end do
end subroutine integration_evaluate

```

```

        end if
    end if
end do
call process_integrate (intg%process, rng, &
    intg%grid_parameters, &
    intg%pass, it_on_file + 1, n_it, n_calls, &
    discard_integrals = .true., &
    adapt_grids = adapt_grids, &
    adapt_weights = adapt_weights, &
    print_current = verb, &
    time_estimate = intg%time_estimate, &
    grids_filename = intg%grids_filename, &
    write_best_grid = intg%use_best_grid, &
    md5sum = intg%md5sum, &
    history_filename = intg%history_filename, &
    log_filename = intg%log_filename)
if (verb) then
    call process_results_write_average (intg%process, intg%pass)
    if (u > 0) then
        call process_results_write_average (intg%process, intg%pass, unit=u)
        flush (u)
    end if
end if
if (intg%vis_history) then
    call process_display_integration_history &
        (intg%process, intg%history_filename, os_data)
end if
call process_record_integral (intg%process, global_var_list)
end subroutine integration_evaluate

```

Write the footer for the screen display

(Integrations: procedures)+≡

```

subroutine integration_write_footer (intg, verbose)
    type(integration_t), intent(in) :: intg
    logical, intent(in), optional :: verbose
    logical :: verb
    integer :: u
    verb = .true.; if (present (verbose)) verb = verbose
    if (verb) then
        u = logfile_unit ()
        call process_results_write_footer (intg%process)
        if (u > 0) then
            call process_results_write_footer (intg%process, unit=u)
            flush (u)
        end if
        if (intg%time_estimate .and. intg%rebuild_grids) &
            call process_write_time_estimate (intg%process)
    end if
end subroutine integration_write_footer

```


16.7.4 API for integration objects

This initializer does everything except assigning cuts/scale/weight expressions.

If `ok` is false, initialization failed, and the integration should be skipped.

If `me_only` is set, prepare just matrix-element evaluation: no phase space, no iterations.

(Integrations: interfaces)≡

```
interface integration_init
  module procedure integration_init0
  module procedure integration_init1
end interface
```

(Integrations: procedures)+≡

```
subroutine integration_init0 &
  (intg, process_id, global, ok, me_only, no_beams, verbose)
  type(integration_t), intent(out) :: intg
  type(string_t), intent(in) :: process_id
  type(rt_data_t), intent(inout), target :: global
  logical, intent(out) :: ok
  logical, intent(in), optional :: me_only, no_beams, verbose
  logical :: integrate, allow_beams
  integrate = .true.; if (present (me_only)) integrate = .not. me_only
  allow_beams = .true.; if (present (no_beams)) allow_beams = .not. no_beams
  call integration_basic_init (intg, process_id, global%var_list, verbose)
  if (allow_beams) call integration_check_beam_data (intg, global%beam_data)
  call maybe_compile_library (global)
  call integration_init_process (intg, &
    global%prc_lib, global%model, global%var_list, ok)
  if (ok) then
    call integration_setup_beams &
      (intg, global%sf_list, global%var_list, ok)
  end if
  if (ok) then
    call integration_setup_qcd &
      (intg, global%lhpdf_status, global%pdf_builtin_status, &
        global%os_data, global%var_list)
  end if
  if (integrate .and. ok) then
    call integration_setup_phase_space (intg, global%os_data, ok)
  end if
  if (integrate .and. ok) then
    call integration_setup_strfun_mappings (intg)
  end if
  if (.not. intg%phs_only) then
    if (integrate .and. ok) then
      call integration_collect_md5sums (intg)
      call integration_setup_iterations &
        (intg, global%it_list, global%it_list_default, ok, verbose)
    end if
    if (ok) then
      call integration_setup_subevt (intg)
      call integration_setup_cuts (intg, global%pn_cuts_lexpr, verbose)
      call integration_setup_scale (intg, global%pn_scale_expr, verbose)
      call integration_setup_fac_scale (intg, global%pn_fac_scale_expr, verbose)
```

```

        call integration_setup_ren_scale (intg, global%pn_ren_scale_expr, verbose)
        call integration_setup_weight (intg, global%pn_weight_expr, verbose)
    end if
    if (integrate .and. ok) then
        call integration_setup_grids (intg)
    end if
end if
end if
end subroutine integration_init0

```

Initialize an array of processes.

(Integrations: procedures)+≡

```

subroutine integration_init1 &
    (intg, process_id, global, ok, no_beams, me_only, verbose)
    type(integration_t), dimension(:), intent(out) :: intg
    type(string_t), dimension(:), intent(in) :: process_id
    type(rt_data_t), intent(inout), target :: global
    logical, intent(out) :: ok
    logical, intent(in), optional :: no_beams, me_only, verbose
    integer :: proc
    do proc = 1, size (intg)
        call integration_init0 &
            (intg(proc), process_id(proc), global, ok, me_only, verbose)
        if (.not. ok) exit
    end do
end subroutine integration_init1

```

Do the integration for a single process, both warmup and final evaluation.

(Integrations: interfaces)+≡

```

interface integration_integrate
    module procedure integration_integrate0
    module procedure integration_integrate1
end interface

```

(Integrations: procedures)+≡

```

subroutine integration_integrate0 &
    (intg, rng, global_var_list, os_data, verbose)
    type(integration_t), intent(inout) :: intg
    type(tao_random_state), intent(inout) :: rng
    type(var_list_t), intent(inout) :: global_var_list
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: verbose
    integer :: pass
    call openmp_set_num_threads_verbose &
        (var_list_get_ival (global_var_list, var_str ("openmp_num_threads")))
    call integration_write_header (intg, verbose)
    do pass = 1, iterations_list_get_n_pass (intg%it_list) - 1
        call integration_warmup (intg, rng, pass, verbose)
    end do
    if (intg%use_best_grid) &
        call process_choose_best_grid (intg%process, intg%check_grid_file)
    call integration_evaluate &
        (intg, rng, pass, global_var_list, os_data, verbose)

```

```

        call integration_write_footer (intg, verbose)
    end subroutine integration_integrate0

```

Integrate several processes consecutively.

(Integrations: procedures)+≡

```

subroutine integration_integrate1 &
    (intg, rng, global_var_list, os_data, verbose)
    type(integration_t), dimension(:), intent(inout) :: intg
    type(tao_random_state), intent(inout) :: rng
    type(var_list_t), intent(inout) :: global_var_list
    type(os_data_t), intent(in) :: os_data
    logical, intent(in), optional :: verbose
    integer :: proc
    do proc = 1, size (intg)
        call integration_integrate0 &
            (intg(proc), rng, global_var_list, os_data, verbose)
    end do
end subroutine integration_integrate1

```

Do a dummy integration for a process which could not be initialized (e.g., has no matrix element). The result is zero.

(Integrations: interfaces)+≡

```

interface integration_integrate_dummy
    module procedure integration_integrate_dummy0
    module procedure integration_integrate_dummy1
end interface

```

(Integrations: procedures)+≡

```

subroutine integration_integrate_dummy0 (intg, global_var_list, verbose)
    type(integration_t), intent(inout) :: intg
    type(var_list_t), intent(inout) :: global_var_list
    logical, intent(in), optional :: verbose
    call integration_write_header (intg, verbose)
    call process_do_dummy_integration (intg%process)
    call integration_write_footer (intg, verbose)
    call process_record_integral (intg%process, global_var_list)
end subroutine integration_integrate_dummy0

subroutine integration_integrate_dummy1 (intg, global_var_list, verbose)
    type(integration_t), dimension(:), intent(inout) :: intg
    type(var_list_t), intent(inout) :: global_var_list
    logical, intent(in), optional :: verbose
    integer :: proc
    do proc = 1, size (intg)
        call integration_integrate_dummy0 (intg(proc), global_var_list, verbose)
    end do
end subroutine integration_integrate_dummy1

```

Just sample the matrix element under realistic conditions (but no cuts); throw away the results.

(Integrations: procedures)+≡

```

subroutine integration_me_test (intg, rng, global_var_list, os_data)
  type(integration_t), intent(inout) :: intg
  type(tao_random_state), intent(inout) :: rng
  type(var_list_t), intent(inout) :: global_var_list
  type(os_data_t), intent(in) :: os_data
  integer :: openmp_num_threads
  real(default) :: time_in_seconds, time_per_call, sample_function_sum
  openmp_num_threads = &
    var_list_get_ival (global_var_list, var_str ("openmp_num_threads"))
  call openmp_set_num_threads_verbose (openmp_num_threads)
  write (msg_buffer, "(A,1x,I0,1x,A)") "Matrix element test: " &
    // "Calling the sampling function", &
    intg%n_events_for_me_test, "times ..."
  call msg_message ()
  call process_me_test (intg%process, rng, intg%n_events_for_me_test, &
    time_in_seconds, sample_function_sum)
  call msg_message ("... test finished.")
  call process_status_write_counters (process_get_status (intg%process))
  write (msg_buffer, "(A,1PG22.15)") "Matrix element test: " &
    // "Sample function sum:      ", sample_function_sum
  call msg_message ()
  write (msg_buffer, "(A,1PG12.5)") "Matrix element test: " &
    // "Time in seconds (wallclock): ", time_in_seconds
  call msg_message ()
  if (intg%n_events_for_me_test /= 0) then
    time_per_call = time_in_seconds / intg%n_events_for_me_test
    write (msg_buffer, "(A,1PG12.5)") "Matrix element test: " &
      // "Time per call in seconds:   ", time_per_call
    call msg_message ()
    if (openmp_num_threads /= 0) then
      write (msg_buffer, "(A,1PG12.5)") "Matrix element test: " &
        // "Time times number of threads:", &
        time_per_call * openmp_num_threads
      call msg_message ()
    end if
  end if
end subroutine integration_me_test

```

Prepare the process for matrix-element evaluation, no phase space, no integration.

```

<Integrations: public>≡
  public :: prepare_me_evaluation

<Integrations: interfaces>+≡
  interface prepare_me_evaluation
    module procedure prepare_me_evaluation0
    module procedure prepare_me_evaluation1
  end interface prepare_me_evaluation

<Integrations: procedures>+≡
  subroutine prepare_me_evaluation0 (process_id, global, verbose)
    type(string_t), intent(in) :: process_id
    type(rt_data_t), intent(inout), target :: global
    logical, intent(in), optional :: verbose

```

```

    type(integration_t) :: intg
    logical :: ok
    call integration_init &
        (intg, process_id, global, ok, me_only = .true., verbose = verbose)
end subroutine prepare_me_evaluation0

subroutine prepare_me_evaluation1 (process_id, global, verbose)
    type(string_t), dimension(:), intent(in) :: process_id
    type(rt_data_t), intent(inout), target :: global
    logical, intent(in), optional :: verbose
    integer :: proc
    do proc = 1, size (process_id)
        call prepare_me_evaluation0 (process_id(proc), global, verbose)
    end do
end subroutine prepare_me_evaluation1

```

Prepare the processes that are not yet known.

```

<Integrations: public>+≡
    public :: prepare_me_missing_processes

<Integrations: procedures>+≡
    subroutine prepare_me_missing_processes &
        (process_id, global, verbose)
        type(string_t), dimension(:), intent(in) :: process_id
        type(rt_data_t), intent(inout), target :: global
        logical, intent(in), optional :: verbose
        integer :: n_proc, n_missing, proc
        type(process_t), pointer :: process
        type(string_t), dimension(:), allocatable :: process_id_missing
        logical, dimension(:), allocatable :: missing
        n_proc = size (process_id)
        allocate (missing (n_proc))
        do proc = 1, n_proc
            process => process_store_get_process_ptr (process_id(proc))
            missing(proc) = .not. associated (process)
        end do
        n_missing = count (missing)
        if (n_missing > 0) then
            allocate (process_id_missing (n_missing))
            process_id_missing = pack (process_id, missing)
            call prepare_me_evaluation (process_id_missing, global, verbose)
        end if
    end subroutine prepare_me_missing_processes

```

Simply integrate, do a dummy integration if necessary. The `integration` object exists only internally.

```

<Integrations: public>+≡
    public :: integrate_process

<Integrations: interfaces>+≡
    interface integrate_process
        module procedure integrate_process0
        module procedure integrate_process1
    end interface

```

(Integrations: procedures)+≡

```

subroutine integrate_process0 &
  (process_id, global, global_var_list, no_beams, verbose)
  type(string_t), intent(in) :: process_id
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), intent(inout) :: global_var_list
  logical, intent(in), optional :: no_beams, verbose
  type(integration_t) :: intg
  logical :: ok
  call integration_init &
    (intg, process_id, global, ok, no_beams=no_beams, verbose=verbose)
  if (.not. intg%phs_only) then
    if (ok) then
      call integration_integrate &
        (intg, global%rng, global_var_list, global%os_data, verbose)
    else
      call integration_integrate_dummy (intg, global_var_list, verbose)
    end if
  end if
end subroutine integrate_process0

subroutine integrate_process1 &
  (process_id, global, global_var_list, no_beams, verbose)
  type(string_t), dimension(:), intent(in) :: process_id
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), intent(inout) :: global_var_list
  logical, intent(in), optional :: no_beams, verbose
  integer :: proc
  do proc = 1, size (process_id)
    call integrate_process0 &
      (process_id(proc), global, global_var_list, no_beams, verbose)
  end do
end subroutine integrate_process1

```

Do a matrix element test. Prepare for integration, but then just call the matrix element `n_events` number of times.

(Integrations: public)+≡

```

public :: me_test_process

```

(Integrations: procedures)+≡

```

subroutine me_test_process (process_id, global, global_var_list)
  type(string_t), intent(in) :: process_id
  type(rt_data_t), intent(inout), target :: global
  type(var_list_t), intent(inout) :: global_var_list
  type(integration_t) :: intg
  logical :: ok
  call integration_init (intg, process_id, global, ok)
  if (ok) then
    call integration_me_test &
      (intg, global%rng, global_var_list, global%os_data)
  else
    call msg_error ("Matrix element test fails " &
      // "because process has no matrix element")
  end if
end subroutine me_test_process

```

```

        end if
    end subroutine me_test_process

```

Integrate the processes that have no integral yet. If no_beams is set, these include processes that use beams.

<Integrations: public>+≡

```

    public :: integrate_missing_processes

```

<Integrations: procedures>+≡

```

    subroutine integrate_missing_processes &
        (process_id, global, global_var_list, no_beams, verbose)
        type(string_t), dimension(:), intent(in) :: process_id
        type(rt_data_t), intent(inout), target :: global
        type(var_list_t), intent(inout) :: global_var_list
        logical, intent(in), optional :: no_beams, verbose
        integer :: n_proc, n_missing, proc
        type(process_t), pointer :: process
        type(string_t), dimension(:), allocatable :: process_id_missing
        logical, dimension(:), allocatable :: missing
        type(string_t) :: prc_string
        logical :: verb, nobeams
        verb = .false.; if (present (verbose)) verb = verbose
        nobeams = .false.; if (present (no_beams)) nobeams = no_beams
        n_proc = size (process_id)
        allocate (missing (n_proc))
        do proc = 1, n_proc
            process => process_store_get_process_ptr (process_id(proc))
            if (associated (process)) then
                if (process_has_integral (process)) then
                    if (nobeams .and. process_uses_beams (process)) then
                        call msg_warning ("Discarding previous result for process '" &
                            // char (process_id(proc)) // "': no beam setup allowed")
                        missing(proc) = .true.
                    else
                        missing(proc) = .false.
                    end if
                else
                    missing(proc) = .false.
                end if
            else
                missing(proc) = .true.
            end if
        end do
        n_missing = count (missing)
        if (n_missing > 0) then
            allocate (process_id_missing (n_missing))
            process_id_missing = pack (process_id, missing)
            if (verb) then
                prc_string = process_id_missing(1)
                do proc = 2, n_missing
                    prc_string = prc_string // ", " // process_id_missing(proc)
                end do
                call msg_message ("Integrating missing processes: " &
                    // char (prc_string))
            end if
        end if
    end subroutine

```

```

    end if
    if (var_list_get_lval (global%var_list, var_str ("?phs_only"))) then
        call msg_fatal &
            ("Computing missing integrals: ?phs_only must not be set")
    else
        call integrate_process &
            (process_id_missing, global, global_var_list, no_beams, verbose)
    end if
    if (verb) then
        call msg_message ("Integration of missing processes complete.")
    end if
end if
end subroutine integrate_missing_processes

```

16.8 Event files configuration

This module manages the file formats and the file list for reading and writing events.

```

<event_files.f90>≡
  <File header>

  module event_files

    <Use kinds>
    use kinds, only: i64 !NODEP!
    <Use strings>
    <Use file utils>
    use diagnostics !NODEP!
    use variables
    use expressions
    use flavors
    use event_formats
    use processes
    use stdhep_interface
    use hepmc_interface
    use events
    use decays

    <Standard module head>

    <Event files: public>

    <Event files: parameters>

    <Event files: types>

    contains

    <Event files: procedures>

  end module event_files

```


16.8.1 Available formats

Files have a name and a format; we need lists of file specifications. Writing LHEF files, we need beam information and overall process data.

(Event files: public)≡

(Event files: parameters)≡

```
integer, parameter, public :: FMT_NONE = 0
integer, parameter, public :: FMT_RAW = -1
integer, parameter, public :: FMT_DEFAULT = 1
integer, parameter, public :: FMT_DEBUG = 2
integer, parameter, public :: FMT_HEPMC = 10
integer, parameter, public :: FMT_LHEF = 20
integer, parameter, public :: FMT_LHA = 21
integer, parameter, public :: FMT_LHA_VERB = 29
integer, parameter, public :: FMT_HEPEVT = 30
integer, parameter, public :: FMT_ASCII_SHORT = 31
integer, parameter, public :: FMT_ASCII_LONG = 32
integer, parameter, public :: FMT_ATHENA = 33
integer, parameter, public :: FMT_HEPEVT_VERB = 39
integer, parameter, public :: FMT_STDHEP = 40
integer, parameter, public :: FMT_STDHEP_UP = 41
```

Determine the format of an event file. Check first if it is raw format, then HepMC. Other formats are not (yet) recognized.

(Event files: public)+≡

```
public :: event_file_get_format
```

(Event files: procedures)≡

```
function event_file_get_format (file) result (fmt)
  integer :: fmt
  type(string_t), intent(in) :: file
  if (is_raw_fmt (file)) then
    fmt = FMT_RAW
  else if (is_hePMC_fmt (file)) then
    fmt = FMT_HEPMC
  else
    fmt = FMT_NONE
  end if
end function event_file_get_format
```

The raw format is actually unformatted.

(Event files: procedures)+≡

```
function is_raw_fmt (file) result (flag)
  logical :: flag
  type(string_t), intent(in) :: file
  integer :: u, iostat
  u = free_unit ()
  open (unit=u, file=char(file), action="read", status="old", &
    form="unformatted", iostat=iostat)
  if (iostat == 0) then
    flag = is_raw_event_file (u)
    close (u)
  else
```

```

        flag = .false.
    end if
end function is_raw_fmt

```

The HepMC format is characterized by an ID string, which apparently follows an empty line. Discard empty lines when checking the ID.

```

<Event files: procedures>+≡
function is_hepmc_fmt (file) result (flag)
    logical :: flag
    type(string_t), intent(in) :: file
    integer :: u, iostat
    open (unit=u, file=char(file), action="read", status="old", iostat=iostat)
    if (iostat == 0) then
        flag = is_hepmc_event_file (u)
        close (u)
    else
        flag = .false.
    end if
end function is_hepmc_fmt

```

16.8.2 Reading event files

Apart from the raw event format which is handled in the `events` module, we currently support reading only for HepMC.

```

<Event files: public>+≡
    public :: input_event_stream_t

<Event files: types>≡
    type :: input_event_stream_t
        integer :: fmt = FMT_NONE
        integer :: polarization_mode = FM_IGNORE_HELICITY
        type(hepmc_iostream_t), pointer :: iostream => null ()
    end type input_event_stream_t

<Event files: public>+≡
    public :: input_event_stream_init

<Event files: procedures>+≡
subroutine input_event_stream_init (input_stream, file, fmt)
    type(input_event_stream_t), intent(out) :: input_stream
    type(string_t), intent(in) :: file
    integer, intent(in) :: fmt
    input_stream%fmt = fmt
    select case (input_stream%fmt)
    case (FMT_HEPMC)
        if (hepmc_is_available ()) then
            allocate (input_stream%iostream)
            call hepmc_iostream_open_in (input_stream%iostream, file)
        else
            call msg_fatal ("HepMC event reading is disabled " &
                // "because HepMC library is not linked.")
            input_stream%fmt = FMT_NONE
        end if
    end select
end subroutine input_event_stream_init

```

```

        end if
    case default
        call msg_bug ("Unsupported file format selected for reading events.")
    end select
end subroutine input_event_stream_init

```

(Event files: public)+≡

```
public :: input_event_stream_read_event
```

(Event files: procedures)+≡

```

subroutine input_event_stream_read_event (input_stream, event, &
    event_vars, prc_array, ok, num_id_array)
    type(input_event_stream_t), intent(inout) :: input_stream
    type(event_t), intent(out) :: event
    type(event_vars_t), intent(inout), target :: event_vars
    type(process_p), dimension(:), intent(in) :: prc_array
    logical, intent(out) :: ok
    integer, dimension(:), intent(in), optional :: num_id_array
    type(hepmc_event_t) :: hepmc_event
    select case (input_stream%fmt)
    case (FMT_HEPMC)
        call hepmc_event_init (hepmc_event)
        call hepmc_iostream_read_event (input_stream%iostream, hepmc_event, ok)
        if (ok) then
            call event_read_from_hepmc &
                (event, hepmc_event, input_stream%polarization_mode, &
                    event_vars, prc_array, num_id_array)
            ! call hepmc_event_print (hepmc_event)
        end if
        call hepmc_event_final (hepmc_event)
    end select
end subroutine input_event_stream_read_event

```

(Event files: public)+≡

```
public :: input_event_stream_final
```

(Event files: procedures)+≡

```

subroutine input_event_stream_final (input_stream)
    type(input_event_stream_t), intent(inout) :: input_stream
    select case (input_stream%fmt)
    case (FMT_HEPMC)
        call hepmc_iostream_close (input_stream%iostream)
        deallocate (input_stream%iostream)
    end select
    input_stream%fmt = FMT_NONE
end subroutine input_event_stream_final

```

16.8.3 Output file specification and file list

(Event files: types)+≡

```

type :: file_spec_t
private
type(string_t) :: name

```

```

integer :: format = FMT_NONE
type(hepmc_iostream_t), pointer :: iostream => null ()
integer :: unit = 0
type(flavor_t), dimension(:), allocatable :: beam_flv
real(default), dimension(:), allocatable :: beam_energy
real(default), dimension(:), allocatable :: integral
real(default), dimension(:), allocatable :: error
integer :: n_processes = 0
logical :: unweighted = .true.
logical :: negative_weights = .false.
logical :: keep_beams = .false.
type(file_spec_t), pointer :: next => null ()
end type file_spec_t

```

File lists.

```

(Event files: public)+≡
public :: event_file_list_t

```

```

(Event files: types)+≡
type :: event_file_list_t
private
type(file_spec_t), pointer :: first => null ()
type(file_spec_t), pointer :: last => null ()
end type event_file_list_t

```

```

(Event files: public)+≡
public :: event_file_list_append_file_spec

```

```

(Event files: procedures)+≡
subroutine event_file_list_append_file_spec &
  (event_file_list, basename, var_list, format, beam_flv, beam_energy, &
   n_processes)
  ! unweighted, negative_weights, &
  type(event_file_list_t), intent(inout) :: event_file_list
  type(string_t), intent(in) :: basename
  type(var_list_t), intent(in) :: var_list
  integer, intent(in) :: format
  type(flavor_t), dimension(:), intent(in) :: beam_flv
  real(default), dimension(:), intent(in) :: beam_energy
  integer, intent(in) :: n_processes
!   logical, intent(in) :: unweighted, negative_weights
  type(file_spec_t), pointer :: current
  allocate (current)
  select case (format)
  case (FMT_DEFAULT);    current%name = basename // "." // var_list_get_sval &
    (var_list, var_str (" $extension_default"))
  case (FMT_DEBUG);      current%name = basename // "." // var_list_get_sval &
    (var_list, var_str (" $extension_debug"))
  case (FMT_HEPMC);      current%name = basename // "." // var_list_get_sval &
    (var_list, var_str (" $extension_hepmc"))
  case (FMT_LHEF);       current%name = basename // "." // var_list_get_sval &
    (var_list, var_str (" $extension_lhef"))
  case (FMT_LHA);        current%name = basename // "." // var_list_get_sval &
    (var_list, var_str (" $extension_lha"))

```

```

case (FMT_HEPEVT);      current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_hepevt"))
case (FMT_ASCII_SHORT); current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_ascii_short"))
case (FMT_ASCII_LONG);  current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_ascii_long"))
case (FMT_ATHENA);      current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_athena"))
case (FMT_STDHEP);      current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_stdhep"))
case (FMT_STDHEP_UP);   current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_stdhep_up"))
case (FMT_HEPEVT_VERB); current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_hepevt_verbose"))
case (FMT_LHA_VERB);    current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_lha_verbose"))
case default;           current%name = basename // "." // var_list_get_sval &
                        (var_list, var_str ("$extension_default"))
end select
current%format = format
allocate (current%beam_flv (size (beam_flv)))
current%beam_flv = beam_flv
allocate (current%beam_energy (size (beam_energy)))
current%beam_energy = beam_energy
current%n_processes = n_processes
current%keep_beams = var_list_get_lval (var_list, var_str ("?keep_beams"))
if (associated (event_file_list%last)) then
    event_file_list%last%next => current
else
    event_file_list%first => current
end if
event_file_list%last => current
end subroutine event_file_list_append_file_spec

```

(Event files: procedures)+≡

```

subroutine event_file_list_final (event_file_list)
    type(event_file_list_t), intent(inout) :: event_file_list
    type(file_spec_t), pointer :: current
    do while (associated (event_file_list%first))
        current => event_file_list%first
        event_file_list%first => current%next
        deallocate (current)
    end do
    event_file_list%last => null ()
end subroutine event_file_list_final

```

16.8.4 Checking filenames

Check if a filename is reserved as an output filename.

(Event files: public)+≡

```

public :: event_file_list_is_filename

```

```

(Event files: procedures)+≡
function event_file_list_is_filename (event_file_list, filename) result (flag)
  logical :: flag
  type(event_file_list_t), intent(in) :: event_file_list
  type(string_t), intent(in) :: filename
  type(file_spec_t), pointer :: current
  current => event_file_list%first
  do while (associated (current))
    if (current%name == filename) then
      flag = .true.
      return
    end if
    current => current%next
  end do
  flag = .false.
end function event_file_list_is_filename

```

16.8.5 Handling output event files

LHEF: Initialize run data with beam and simulation parameters.

```

(Event files: public)+≡
public :: event_file_list_open

(Event files: procedures)+≡
subroutine event_file_list_open (event_file_list, process_id, n_events, var_list)
  type(event_file_list_t), intent(inout), target :: event_file_list
  type(string_t), dimension(:), intent(in) :: process_id
  integer, intent(in) :: n_events
  real(default), dimension(:), allocatable :: integral, error
  type(var_list_t), intent(in) :: var_list
  type(process_t), pointer :: process
  type(file_spec_t), pointer :: current
  integer :: i, n_proc
  integer(i64) :: n_events_expected
  n_proc = size (process_id)
  current => event_file_list%first
  allocate (integral (n_proc), error (n_proc))
  do i = 1, n_proc
    process => process_store_get_process_ptr (process_id(i))
    if (associated (process)) then
      integral(i) = process_get_integral (process)
      error(i) = process_get_error (process)
    else
      integral(i) = 0
      error(i) = 0
    end if
  end do
  n_events_expected = n_events
  do while (associated (current))
    select case (current%format)
    case (FMT_DEFAULT)
      call msg_message ("Writing events in human-readable format " &
        // "to file " // char (current%name) // "'")

```

```

        current%unit = free_unit ()
        open (unit=current%unit, file=char(current%name), &
              action="write", status="replace")
case (FMT_DEBUG)
    call msg_message ("Writing events in verbose format to file '" &
                      // char (current%name) // "'")
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
          action="write", status="replace")
case (FMT_HEPMC)
    call msg_message ("Writing events in HepMC format to file '" &
                      // char (current%name) // "'")
    if (hepmc_is_available ()) then
        allocate (current%iostream)
        call hepmc_iostream_open_out (current%iostream, current%name)
    else
        call msg_error ("HepMC event writing is disabled " &
                        // "because HepMC library is not linked.")
    end if
case (FMT_HEPEVT)
    call msg_message ("Writing events in HEPEVT format to file '" &
                      // char (current%name) // "'")
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
          action="write", status="replace")
case (FMT_ASCII_SHORT)
    call msg_message ("Writing events in short ASCII format to file '" &
                      // char (current%name) // "'")
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
          action="write", status="replace")
case (FMT_ASCII_LONG)
    call msg_message ("Writing events in long ASCII format to file '" &
                      // char (current%name) // "'")
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
          action="write", status="replace")
case (FMT_ATHENA)
    call msg_message ("Writing events in ATHENA format to file '" &
                      // char (current%name) // "'")
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
          action="write", status="replace")
case (FMT_LHEF)
    call msg_message ("Writing events in LHEF format to file '" &
                      // char (current%name) // "'")
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
          action="write", status="replace")
    call les_houches_events_write_header (current%unit)
    call heprup_init &
        (flavor_get_pdg (current%beam_flg), &
         current%beam_energy, &
         n_processes = current%n_processes, &

```

```

        unweighted = current%unweighted, &
        negative_weights = current%negative_weights)
do i = 1, n_proc
    call heprup_set_process_parameters (i = i, process_id = &
        i, cross_section = integral(i), error = error(i))
end do
call heprup_write_lhef (current%unit)
case (FMT_LHA)
    call msg_message ("Writing events in (old) LHA format to file '" &
        // char (current%name) // "'")
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
        action="write", status="replace")
    call heprup_init &
        (flavor_get_pdg (current%beam_flv), &
        current%beam_energy, &
        n_processes = current%n_processes, &
        unweighted = current%unweighted, &
        negative_weights = current%negative_weights)
do i = 1, n_proc
    call heprup_set_process_parameters (i = i, process_id = &
        i, cross_section = integral(i), error = error(i))
end do
case (FMT_STDHEP)
    call msg_message ("Writing events in binary STDHEP/HEPEVT format to file '" &
        // char (current%name) // "'")
    call stdhep_init (char(current%name), "WHIZARD event sample", &
        n_events_expected)
case (FMT_STDHEP_UP)
    call msg_message ("Writing events in binary STDHEP/HEPRUP/HEPEUP format to file '" &
        // char (current%name) // "'")
    call heprup_init &
        (flavor_get_pdg (current%beam_flv), &
        current%beam_energy, &
        n_processes = current%n_processes, &
        unweighted = current%unweighted, &
        negative_weights = current%negative_weights)
do i = 1, n_proc
    call heprup_set_process_parameters (i = i, process_id = &
        i, cross_section = integral(i), error = error(i))
end do
    call stdhep_init (char(current%name), "WHIZARD event sample", &
        n_events_expected)
    call stdhep_write (STDHEP_HEPRUP)
case (FMT_HEPEVT_VERB)
    call msg_message ("Writing events in verbose HEPEVT format to file '" &
        // char (current%name) // "'")
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
        action="write", status="replace")
case (FMT_LHA_VERB)
    call msg_message ("Writing events in verbose HEPRUP/HEPEUP format to file '" &
        // char (current%name) // "'")
    call heprup_init &

```



```

        (flavor_get_pdg (current%beam_flg), &
         current%beam_energy, &
         n_processes = current%n_processes, &
         unweighted = current%unweighted, &
         negative_weights = current%negative_weights)
    do i = 1, n_proc
        call heprup_set_process_parameters (i = i, process_id = &
            i, cross_section = integral(i), error = error(i))
    end do
    current%unit = free_unit ()
    open (unit=current%unit, file=char(current%name), &
        action="write", status="replace")
    call heprup_write_verbose (current%unit)
end select
current => current%next
end do
end subroutine event_file_list_open

```

Scan the file list and write the event in the selected formats.

```

(Event files: public)+≡
    public :: event_file_list_write_event

(Event files: procedures)+≡
    subroutine event_file_list_write_event &
        (event_file_list, event, integral_sum, error_sum, analysis_expr, i_evt)
        type(event_file_list_t), intent(in), target :: event_file_list
        type(event_t), intent(in), target :: event
        real(default), intent(in) :: integral_sum, error_sum
        type(eval_tree_t), intent(in) :: analysis_expr
        integer, intent(in) :: i_evt
        type(file_spec_t), pointer :: current
        type(hepmc_event_t) :: hepmc_event
        current => event_file_list%first
        do while (associated (current))
            select case (current%format)
            case (FMT_DEFAULT)
                call event_write (event, unit=current%unit, verbose=.false.)
            case (FMT_DEBUG)
                call event_write (event, analysis_expr=analysis_expr, &
                    unit=current%unit, verbose=.true.)
            case (FMT_HEPMC)
                if (hepmc_is_available ()) then
                    call hepmc_event_init (hepmc_event, event_id=i_evt)
                    call hepmc_event_set_cross_section (hepmc_event, &
                        integral_sum, error_sum)
                    call event_write_to_hepmc (event, hepmc_event)
                    ! call hepmc_event_print (hepmc_event)
                    call hepmc_iostream_write_event (current%iostream, hepmc_event)
                    call hepmc_event_final (hepmc_event)
                end if
            case (FMT_HEPEVT)
                call event_write_to_hepevt (event, current%keep_beams)
                call hepevt_write_hepevt (current%unit)
            case (FMT_ASCII_SHORT)

```

```

        call event_write_to_hepevt (event, current%keep_beams)
        call hepevt_write_ascii (current%unit, .false.)
    case (FMT_ASCII_LONG)
        call event_write_to_hepevt (event, current%keep_beams)
        call hepevt_write_ascii (current%unit, .true.)
    case (FMT_ATHENA)
        call event_write_to_hepevt (event, current%keep_beams)
        call hepevt_write_athena (unit=current%unit, i_evt=i_evt)
    case (FMT_LHEF)
        call event_write_to_hepeup (event, current%keep_beams)
        call hepeup_write_lhef (current%unit)
    case (FMT_LHA)
        call event_write_to_hepeup (event, current%keep_beams)
        call hepeup_write_lha (current%unit)
    case (FMT_STDHEP)
        call event_write_to_hepevt (event, current%keep_beams)
        call stdhep_write (STDHEP_HEPEVT)
    case (FMT_STDHEP_UP)
        call event_write_to_hepeup (event, current%keep_beams)
        call stdhep_write (STDHEP_HEPEUP)
    case (FMT_HEPEVT_VERB)
        call event_write_to_hepevt (event, current%keep_beams)
        call hepevt_write_verbose (current%unit)
    case (FMT_LHA_VERB)
        call event_write_to_hepeup (event, current%keep_beams)
        call hepeup_write_verbose (current%unit)
    end select
    current => current%next
end do
end subroutine event_file_list_write_event

```

Close streams.

(Event files: public)+≡

```
public :: event_file_list_close
```

(Event files: procedures)+≡

```

subroutine event_file_list_close (event_file_list)
    type(event_file_list_t), intent(inout), target :: event_file_list
    type(file_spec_t), pointer :: current
    current => event_file_list%first
    do while (associated (current))
        select case (current%format)
            case (FMT_HEPMC)
                if (hePMC_is_available ()) then
                    call hePMC_iostream_close (current%iostream)
                    deallocate (current%iostream)
                end if
            case (FMT_LHEF)
                call les_houches_events_write_footer (current%unit)
                close (current%unit)
            case (FMT_STDHEP)
                call stdhep_end
            case (FMT_STDHEP_UP)
                call stdhep_end
        end select
        current => current%next
    end do
end subroutine event_file_list_close

```

```

        case default
            close (current%unit)
        end select
        current => current%next
    end do
end subroutine event_file_list_close

```

16.8.6 Additional tools

(Event files: public)+≡

```
public :: event_format_code
```

(Event files: procedures)+≡

```

elemental function event_format_code (format) result (fmt)
    integer :: fmt
    type(string_t), intent(in) :: format
    select case (char (format))
    case ("ascii")
        fmt = FMT_DEFAULT
    case ("debug")
        fmt = FMT_DEBUG
    case ("hepmc")
        fmt = FMT_HEPMC
    case ("hepevt")
        fmt = FMT_HEPEVT
    case ("short")
        fmt = FMT_ASCII_SHORT
    case ("long")
        fmt = FMT_ASCII_LONG
    case ("athena")
        fmt = FMT_ATHENA
    case ("lhef")
        fmt = FMT_LHEF
    case ("lha")
        fmt = FMT_LHA
    case ("stdhep")
        fmt = FMT_STDHEP
    case ("stdhep_up")
        fmt = FMT_STDHEP_UP
    case ("hepevt_verbose")
        fmt = FMT_HEPEVT_VERB
    case ("lha_verbose")
        fmt = FMT_LHA_VERB
    case default
        fmt = FMT_NONE
    end select
end function event_format_code

```

16.9 Simulation

This module manages simulation: event generation and reading/writing of event files. The `simulation` object is intended to be used (via a pointer) outside of WHIZARD, if events are generated individually by an external driver.

```
<simulations.f90>≡  
  <File header>  
  
  module simulations  
  
    <Use kinds>  
    <Use strings>  
    <Use file utils>  
    use limits, only: MAX_TRIES_FOR_SINGLE_EVENT !NODEP!  
    use diagnostics !NODEP!  
    use tao_random_numbers !NODEP!  
    use cputime  
    use md5  
    use parser  
    use variables  
    use subevents  
    use expressions  
    use flavors  
    use state_matrices  
    use beams  
    use processes  
    use decays  
    use events  
    use strfun_config  
    use rt_data  
    use integrations  
    use event_files  
    use os_interface  
    use shower_interface  
  
    <Standard module head>  
  
    <Simulations: public>  
  
    <Simulations: parameters>  
  
    <Simulations: types>  
  
    contains  
  
    <Simulations: procedures>  
  
  end module simulations
```

16.9.1 Simulation parameters

This transparent container holds the parameters that control event generation.

This and the following section (simulation object) should end up in a separate module. We defer this until it is clear whether we need anything from the integrate command to be complete.

```

(Simulations: parameters)≡
  integer, parameter :: NORM_UNDEFINED = 0
  integer, parameter :: NORM_UNIT = 1
  integer, parameter :: NORM_N_EVT = 2
  integer, parameter :: NORM_SIGMA = 3
  integer, parameter :: NORM_SIGMA_N_EVT = 4

(Simulations: types)≡
  type :: simulation_parameters_t
    logical :: unweighted = .true.
    logical :: use_best_grid = .true.
    integer :: normalization_mode = NORM_UNDEFINED
    logical :: negative_weights = .false.
    logical :: polarized = .false.
    type(shower_settings_t) :: shower_settings
  end type simulation_parameters_t

```

Initialize the generic simulation parameters.

```

(Simulations: procedures)≡
  recursive subroutine simulation_parameters_init &
    (sim, unweighted, use_best_grid, event_normalization, negative_weights, &
     polarized)
    type(simulation_parameters_t), intent(out) :: sim
    logical, intent(in) :: unweighted
    logical, intent(in) :: use_best_grid
    type(string_t), intent(in) :: event_normalization
    logical, intent(in) :: negative_weights, polarized
    sim%unweighted = unweighted
    sim%use_best_grid = use_best_grid
    sim%negative_weights = negative_weights
    sim%polarized = polarized
    select case (char(event_normalization))
    case ("auto", "Auto", "AUTO", "automatic", "Automatic", "AUTOMATIC")
      if (unweighted) then
        sim%normalization_mode = NORM_UNIT
      else
        sim%normalization_mode = NORM_SIGMA
      end if
    case ("1", "unity", "Unity", "UNITY")
      sim%normalization_mode = NORM_UNIT
    case ("1/n", "1/N")
      sim%normalization_mode = NORM_N_EVT
    case ("sigma", "Sigma", "SIGMA")
      sim%normalization_mode = NORM_SIGMA
    case ("sigma/n", "Sigma/n", "Sigma/N", "SIGMA/N")
      sim%normalization_mode = NORM_SIGMA_N_EVT
    case default
      call msg_error("Unknown value '" // char(event_normalization) &
        // "for $event_normalization. I'll assume 'auto'")
      call simulation_parameters_init &

```

```

        (sim, unweighted, use_best_grid, var_str ("auto"), &
         negative_weights, polarized)
    end select
end subroutine simulation_parameters_init

```

Initialize the shower parameters.

(Simulations: procedures)+≡

```

subroutine simulation_parameters_init_shower (sim, var_list)
    type(simulation_parameters_t), intent(inout) :: sim
    type(var_list_t), intent(in) :: var_list
    call shower_settings_init (sim%shower_settings, var_list)
end subroutine simulation_parameters_init_shower

```

(Simulations: procedures)+≡

```

subroutine simulation_parameters_write_message (sim, unit)
    type(simulation_parameters_t), intent(in) :: sim
    integer, intent(in), optional :: unit
    type(string_t) :: weight_str, grid_str, norm_str, neg_str, polarized_str
    if (sim%unweighted) then
        weight_str = "unweighted"
    else
        weight_str = "weighted"
    end if
    if (sim%use_best_grid) then
        grid_str = ", best grid"
    else
        grid_str = ", last grid"
    end if
    if (sim%polarized) then
        polarized_str = ", polarized events"
    else
        polarized_str = ", unpolarized_events"
    end if
    select case (sim%normalization_mode)
    case (NORM_UNIT)
        norm_str = "1"
    case (NORM_N_EVT)
        norm_str = "1/n"
    case (NORM_SIGMA)
        norm_str = "sigma"
    case (NORM_SIGMA_N_EVT)
        norm_str = "sigma/n"
    case default
        norm_str = "unknown"
    end select
    if (sim%negative_weights) then
        neg_str = ", allow negative weights"
    else
        neg_str = ""
    end if
    call msg_message ("Simulation mode = " &
        // char (weight_str) // char (grid_str), &
        unit)

```

```

call msg_message ("                " &
// "event_normalization = '" // char (norm_str) &
// "' " // char (neg_str) // char (polarized_str), &
unit)
end subroutine simulation_parameters_write_message

```

(Simulations: procedures)+≡

```

subroutine simulation_parameters_write (sim, unit)
type(simulation_parameters_t), intent(in) :: sim
integer, intent(in), optional :: unit
integer :: u
u = output_unit (unit)
write (u, *) "Simulation parameters:"
write (u, *) "  unweighted      = ", sim%unweighted
write (u, *) "  use best grid    = ", sim%use_best_grid
write (u, *) "  normalization_mode = ", sim%normalization_mode
write (u, *) "  negative_weights = ", sim%negative_weights
write (u, *) "  polarized       = ", sim%polarized
call shower_settings_write (sim%shower_settings, unit)
end subroutine simulation_parameters_write

```

(Simulations: procedures)+≡

```

function simulation_parameters_get_norm (sim, sigma, n) result (norm)
real(default) :: norm
type(simulation_parameters_t), intent(in) :: sim
real(default), intent(in) :: sigma
integer, intent(in) :: n
select case (sim%normalization_mode)
case (NORM_UNIT)
norm = 1
case (NORM_N_EVT)
if (n /= 0) then
norm = 1._default / n
else
norm = 1
end if
case (NORM_SIGMA)
norm = sigma
case (NORM_SIGMA_N_EVT)
if (n /= 0) then
norm = sigma / n
else
norm = sigma
end if
case default
norm = 1
end select
if ((.not. sim%unweighted) .and. sigma /= 0) norm = norm / sigma
end function simulation_parameters_get_norm

```

(Simulations: procedures)+≡

```

function simulation_parameters_get_md5sum (sim) result (md5sum_sim)
character(32) :: md5sum_sim

```

```

type(simulation_parameters_t), intent(in) :: sim
integer :: u
u = free_unit ()
open (u, status = "scratch")
call simulation_parameters_write (sim, u)
rewind (u)
md5sum_sim = md5sum (u)
close (u)
end function simulation_parameters_get_md5sum

```

16.9.2 Screen updates during simulation

To pacify the user during long event generation runs, we can display some data about the current progress on screen.

```

<Simulations: parameters>+=
character(*), parameter :: &
checkpoint_head = &
" | % complete | events generated | events remaining | time remaining", &
checkpoint_bar = &
" |=====|", &
checkpoint_fmt = "(' ',F5.1,T16,I9,T35,I9,T56,A)"

```

```

<Simulations: types>+=
type :: checkpointing_t
logical :: active = .false.
logical :: running = .false.
integer :: val = 0
real(default) :: tzero = 0
end type checkpointing_t

```

```

<Simulations: procedures>+=
subroutine checkpointing_init (checkpointing, var_list)
type(checkpointing_t), intent(out) :: checkpointing
type(var_list_t), intent(in) :: var_list
checkpointing%active = var_list_is_known (var_list, var_str ("checkpoint"))
if (checkpointing%active) then
checkpointing%val = &
var_list_get_ival (var_list, var_str("checkpoint"))
if (checkpointing%val <= 0) then
call msg_warning ("ignoring nonpositive value of 'checkpoint'")
checkpointing%active = .false.
end if
end if
end subroutine checkpointing_init

```

```

<Simulations: procedures>+=
subroutine checkpointing_msg_start (checkpointing, n_events, i_evt)
type(checkpointing_t), intent(inout) :: checkpointing
integer, intent(in) :: n_events, i_evt
if (checkpointing%active .and. n_events > i_evt) then
call msg_message ("")

```



```

        call msg_message (checkpoint_bar)
        call msg_message (checkpoint_head)
        call msg_message (checkpoint_bar)
        write (msg_buffer, checkpoint_fmt) 0., 0, n_events - i_evt, "???"
        call msg_message ()
        checkpointing%running = .true.
        checkpointing%tzero = time_current ()
    end if
end subroutine checkpointing_msg_start

```

(Simulations: procedures)+≡

```

subroutine checkpointing_msg_event (checkpointing, n_events, n_read, i_evt)
    type(checkpointing_t), intent(in) :: checkpointing
    integer, intent(in) :: n_events, n_read, i_evt
    real(default) :: tcurrent
    type(string_t) :: tremain
    if (checkpointing%active .and. checkpointing%running &
        .and. mod (i_evt, checkpointing%val) == 0) then
        tcurrent = time_current ()
        tremain = time2string ( &
            int ((tcurrent - checkpointing%tzero) / (i_evt - n_read) &
                * (n_events - i_evt)))
        write (msg_buffer, checkpoint_fmt) &
            100 * (i_evt - n_read) / real (n_events - n_read), &
            i_evt - n_read, &
            n_events - i_evt, char (tremain)
        call msg_message ()
    end if
end subroutine checkpointing_msg_event

```

(Simulations: procedures)+≡

```

subroutine checkpointing_msg_end (checkpointing, n_read, i_evt)
    type(checkpointing_t), intent(inout) :: checkpointing
    integer, intent(in) :: n_read, i_evt
    if (checkpointing%active .and. checkpointing%running) then
        if (mod (i_evt, checkpointing%val) /= 0) then
            write (msg_buffer, checkpoint_fmt) 100., i_evt - n_read, 0, "0s"
            call msg_message ()
        end if
        call msg_message (checkpoint_bar)
        call msg_message ("")
        checkpointing%running = .false.
    end if
end subroutine checkpointing_msg_end

```

16.9.3 The simulation object type

We set up a data type which holds all information needed for simulation. This allows to separate initialization, event generation, and finalization of a simulation run. The type is public, so the object may be used as a black box by an external caller.

The objects of this type must carry the `target` attribute, since several components will be pointed to.

```

<Simulations: public>≡
    public :: simulation_t

<Simulations: types>+≡
    type :: simulation_t
        ! not private anymore as required by the whizard-c-interface
        integer :: n_proc = 0
        type(string_t), dimension(:), allocatable :: process_id
        type(process_p), dimension(:), allocatable :: prc_array
        type(var_list_t) :: var_list
        logical :: rebuild_events = .false.
        logical :: check_grid_file = .true.
        logical :: check_event_file = .true.
        integer :: version = 0
        integer :: n_in = 0
        type(flavor_t), dimension(:), allocatable :: beam_flv
        real(default), dimension(:), allocatable :: beam_energy
        type(string_t) :: basename
        logical :: rescan = .false.
        logical :: use_num_id = .false.
        integer, dimension(:), allocatable :: num_id
        logical :: update_parameters = .true.
        logical :: update_scale = .false.
        logical :: update_alpha_s = .false.
        logical :: update_sqme = .true.
        logical :: update_weight = .true.
        logical :: read_raw = .false.
        logical :: read_hepmc = .false.
        logical :: write_raw = .false.
        type(string_t) :: file_rescan
        type(string_t) :: file_raw
        type(string_t) :: file_hepmc
        type(input_event_stream_t) :: input_stream
        type(event_file_list_t) :: event_file_list
        integer :: u_raw = -1
        type(simulation_parameters_t) :: spar
        real(default), dimension(:), allocatable :: integral
        real(default), dimension(:), allocatable :: error
        real(default) :: integral_sum = 0
        real(default) :: error_sum = 0
        real(default) :: norm_weight = 0
        logical :: helicity_selection_active = .false.
        real(default) :: helicity_selection_threshold = -1
        integer :: helicity_selection_cutoff = 1000
        type(md5sum_events_t) :: md5sum
        integer :: n_events = 0
        logical :: n_events_set = .false.
        integer :: n_read = 0
        integer :: i_evt = 0
        integer :: n_selected = 0
        real(default) :: luminosity = 0
        logical :: user_selection = .false.

```

```

type(eval_tree_t) :: selection_expr
type(eval_tree_t) :: reweight_expr
type(eval_tree_t) :: analysis_expr
type(subevt_t) :: subevt
type(event_vars_t) :: event_vars
logical :: allow_decays = .true.
type(decay_tree_t), dimension(:), allocatable :: decay_tree
type(checkpointing_t) :: checkpointing
type(event_t) :: event
end type simulation_t

```

Preparing event generation

This is the basic initializer; it specifies the processes and issues a message if requested. Furthermore, it initializes some important flags, and it makes a snapshot of the current variable list.

(Simulations: procedures)+≡

```

subroutine simulation_basic_init (sim, process_id, var_list, rescan, verbose)
  type(simulation_t), intent(out) :: sim
  type(string_t), dimension(:), intent(in) :: process_id
  type(var_list_t), intent(in), target :: var_list
  logical, intent(in), optional :: rescan, verbose
  type(string_t) :: process_string, version_string
  integer :: proc
  logical :: generate, verb
  generate = .true.; if (present (rescan)) generate = .not. rescan
  verb = .true.; if (present (verbose)) verb = verbose
  sim%n_proc = size (process_id)
  allocate (sim%process_id (sim%n_proc))
  sim%process_id = process_id
  allocate (sim%prc_array (sim%n_proc))
  do proc = 1, sim%n_proc
    sim%prc_array(proc)%ptr => &
      process_store_get_process_ptr (sim%process_id(proc))
  end do
  if (verb) then
    process_string = ""
    do proc = 1, size (process_id)
      if (proc > 1) process_string = process_string // ", "
      process_string = process_string // sim%process_id (proc)
    end do
    if (generate) then
      call msg_message ("Initializing simulation for processes " &
        // char (process_string) // ":")
    else
      call msg_message ("Initializing rescanning for processes " &
        // char (process_string) // ":")
    end if
  end if
  sim%rebuild_events = &
    var_list_get_lval (var_list, var_str ("?rebuild_events"))
  sim%check_grid_file = &

```

```

        var_list_get_lval (var_list, var_str ("?check_grid_file"))
sim%check_event_file = &
        var_list_get_lval (var_list, var_str ("?check_event_file"))
version_string = &
        var_list_get_sval (var_list, var_str ("$event_file_version"))
select case (char (version_string))
case ("2.00":"2.06"); sim%version = 2
case default;        sim%version = 3
end select
call simulation_parameters_init (sim%spar, &
        var_list_get_lval &
            (var_list, var_str ("?unweighted")), &
        var_list_get_lval &
            (var_list, var_str ("?use_best_grid")), &
        var_list_get_sval &
            (var_list, var_str ("$event_normalization")), &
        var_list_get_lval &
            (var_list, var_str ("?negative_weights")), &
        var_list_get_lval &
            (var_list, var_str ("?polarized_events")))
call simulation_parameters_init_shower (sim%spar, var_list)
if (present (verbose)) then
    if (verbose) call simulation_parameters_write_message (sim%spar)
end if
sim%helicity_selection_active = &
        var_list_get_lval (var_list, var_str ("?helicity_selection_active"))
if (sim%helicity_selection_active) then
    sim%helicity_selection_threshold = var_list_get_rval (var_list, &
        var_str ("helicity_selection_threshold"))
    sim%helicity_selection_cutoff = var_list_get_ival (var_list, &
        var_str ("helicity_selection_cutoff"))
end if
sim%use_num_id = &
        var_list_get_lval (var_list, var_str ("?use_num_id"))
if (sim%use_num_id) then
    allocate (sim%num_id (size (process_id)))
    do proc = 1, sim%n_proc
        sim%num_id(proc) = proc_get_num_id (sim%process_id(proc), var_list)
    end do
end if
sim%allow_decays = &
        var_list_get_lval (var_list, var_str ("?allow_decays"))
call var_list_init_snapshot (sim%var_list, var_list)
end subroutine simulation_basic_init

```

Get the numeric process ID for a process. If not associated, issue an error.

(Simulations: procedures)+≡

```

function proc_get_num_id (process_id, var_list) result (num_id)
    integer :: num_id
    type(string_t), intent(in) :: process_id
    type(var_list_t), intent(in) :: var_list
    type(string_t) :: var_name
    var_name = "num_id(" // process_id // ")"
    if (var_list_is_known (var_list, var_name)) then

```

```

        num_id = var_list_get_lval (var_list, var_name)
    else
        call msg_error ("Numeric process ID '" &
            // char (var_name) // "' is undefined, inserting zero.")
        num_id = 0
    end if
end function proc_get_num_id

```

This is the initializer that applies for rescanning existing event files. Since the matrix element will be recalculated for each event, we redo the initializations of the helicity selection and the process variables.

(Simulations: procedures)+≡

```

subroutine simulation_init_rescan &
    (sim, file_rescan, process_id, var_list, verbose)
    type(simulation_t), intent(out) :: sim
    type(string_t), intent(in) :: file_rescan
    type(string_t), dimension(:), intent(in) :: process_id
    type(var_list_t), intent(in), target :: var_list
    logical, intent(in), optional :: verbose
    integer :: proc
    type(process_t), pointer :: process
    logical :: verb
    verb = .true.; if (present (verbose)) verb = verbose
    call simulation_basic_init &
        (sim, process_id, var_list, rescan=.true., verbose=verbose)
    sim%rebuild_events = .false.
    sim%rescan = .true.
    sim%file_rescan = file_rescan
    sim%update_parameters = &
        var_list_get_lval (var_list, var_str ("?update_parameters"))
    sim%update_scale = &
        var_list_get_lval (var_list, var_str ("?update_scale"))
    sim%update_alpha_s = &
        var_list_get_lval (var_list, var_str ("?update_alpha_s"))
    sim%update_sqme = &
        var_list_get_lval (var_list, var_str ("?update_sqme"))
    sim%update_weight = &
        var_list_get_lval (var_list, var_str ("?update_weight"))
    if (verb) then
        call msg_message ("Reading events from file '" &
            // char (sim%file_rescan) // "'")
        if (sim%update_scale) call msg_message &
            ("Recalculating event scale")
        if (sim%update_alpha_s) call msg_message &
            ("Recalculating alpha_s")
        if (sim%update_sqme) then
            if (sim%update_parameters) then
                call msg_message ("Recalculating squared matrix element " &
                    // "with updated parameters")
            else
                call msg_message ("Recalculating squared matrix element")
            end if
        end if
    end if
end if

```

```

        if (sim%update_weight) call msg_message ("Updating event weight " &
        // "using matrix element ratio")
    end if
    do proc = 1, sim%n_proc
        process => sim%prc_array(proc)%ptr
        call process_reset_helicity_selection (process, &
        sim%helicity_selection_threshold, sim%helicity_selection_cutoff)
    end do
end subroutine simulation_init_rescan

```

Do missing integration for processes where this is possible. The results are inserted into the `global_var_list` (the `global` object may in fact be local to the caller).

If `rescan` is set, do just process initialization, no integration.

(Simulations: procedures)+≡

```

subroutine simulation_compute_missing_integrals &
    (sim, global, global_var_list, rescan, verbose)
type(simulation_t), intent(inout) :: sim
type(rt_data_t), intent(inout), target :: global
type(var_list_t), intent(inout) :: global_var_list
logical, intent(in), optional :: rescan, verbose
integer :: proc
logical :: me_only
me_only = .false.; if (present (rescan)) me_only = rescan
if (me_only) then
    call prepare_me_missing_processes (sim%process_id, global, verbose)
else
    call integrate_missing_processes &
        (sim%process_id, global, global_var_list, verbose = verbose)
end if
do proc = 1, sim%n_proc
    sim%prc_array(proc)%ptr => &
        process_store_get_process_ptr (sim%process_id(proc))
end do
end subroutine simulation_compute_missing_integrals

```

For each process that has an integral, choose the best integration grid for event generation.

(Simulations: procedures)+≡

```

subroutine simulation_choose_best_grids (sim)
type(simulation_t), intent(in) :: sim
type(process_t), pointer :: process
integer :: proc
do proc = 1, sim%n_proc
    process => sim%prc_array(proc)%ptr
    if (associated (process)) then
        if (process_has_integral (process)) &
            call process_choose_best_grid (process, sim%check_grid_file)
    end if
end do
end subroutine simulation_choose_best_grids

```

Initialize processes that are not yet contained in the process store, if possible. This applies when rescanning files. We do not need integrals in that case, but the process must be initialized including beam data, if any. We also allow for weight and scale expressions (if absent, the values in the file are used), and take notice of the α_s scheme.

(Simulations: procedures)+≡

```

subroutine simulation_init_missing_processes (sim, global, verbose)
  type(simulation_t), intent(inout) :: sim
  type(rt_data_t), intent(inout), target :: global
  logical, intent(in), optional :: verbose
  integer :: n_missing
  type(string_t), dimension(:), allocatable :: missing_process_id
  logical, dimension(:), allocatable :: missing
  integer :: proc
  logical :: verb
  verb = .false.; if (present (verbose)) verb = verbose
  allocate (missing (sim%n_proc))
  do proc = 1, sim%n_proc
    missing(proc) = .not. associated (sim%prc_array(proc)%ptr)
  end do
  n_missing = count (missing)
  if (n_missing > 0) then
    allocate (missing_process_id (n_missing))
    missing_process_id = pack (sim%process_id, missing)
    call prepare_me_evaluation (missing_process_id, global)
    do proc = 1, sim%n_proc
      if (missing(proc)) sim%prc_array(proc)%ptr => &
        process_store_get_process_ptr (sim%process_id(proc))
    end do
  end if
end subroutine simulation_init_missing_processes

```

Check whether for the selected combination of processes, simulation is possible at all.

(Simulations: procedures)+≡

```

subroutine simulation_check (sim, ok)
  type(simulation_t), intent(inout) :: sim
  logical, intent(out) :: ok
  type(process_t), pointer :: process
  integer :: proc
  type(flavor_t), dimension(:), allocatable :: beam_flv
  real(default), dimension(:), allocatable :: beam_energy
  ok = .false.
  do proc = 1, sim%n_proc
    process => sim%prc_array(proc)%ptr
    if (.not. associated (process)) then
      call msg_fatal ("Process '" // char (sim%process_id(proc)) &
        // "' is not available for simulation.")
      return
    end if
    select case (proc)
    case (1)
      sim%n_in = process_get_n_in (process)

```

```

        allocate (beam_flv (sim%n_in), beam_energy (sim%n_in))
        beam_flv = process_get_beam_flv (process)
        beam_energy = process_get_beam_energy (process)
    case default
        if (.not. process_has_matrix_element (process)) cycle
        if (process_get_n_in (process) /= sim%n_in) then
            call msg_fatal ("Simulation: " &
                // "Mixture of scattering and decays")
            return
        else if (any (process_get_beam_flv (process) /= beam_flv)) then
            call msg_fatal ("Simulation: Mismatch in beam particles")
            return
        else if (any (process_get_beam_energy (process) &
            /= beam_energy)) then
            call msg_fatal ("Simulation: Mismatch in beam energies")
            return
        end if
    end select
end do
allocate (sim%beam_flv (sim%n_in), sim%beam_energy (sim%n_in))
sim%beam_flv = beam_flv
sim%beam_energy = beam_energy
ok = .true.
end subroutine simulation_check

```

Initialize I/O files and switches. The event_fmt array may be unallocated, therefore we keep its allocatable attribute.

(Simulations: procedures)+≡

```

subroutine simulation_setup_event_file_list (sim, event_fmt, basename_default)
    type(simulation_t), intent(inout) :: sim
    integer, dimension(:), intent(in), allocatable :: event_fmt
    type(string_t), intent(in) :: basename_default
    type(string_t) :: extension_raw
    integer :: i
    type(string_t) :: matching_basename
    sim%basename = var_list_get_sval (sim%var_list, var_str ("sample"))
    if (sim%basename == "") sim%basename = basename_default
    if (sim%rescan) then
        select case (event_file_get_format (sim%file_rescan))
        case (FMT_RAW)
            sim%read_raw = .true.
            sim%file_raw = sim%file_rescan
        case (FMT_HEPMC)
            sim%read_hePMC = .true.
            sim%file_hePMC = sim%file_rescan
        case default
            call msg_fatal ("Rescanning event file '" // char (sim%file_rescan) &
                // "': file format not supported")
        end select
        sim%write_raw = .false.
    else
        sim%read_raw = var_list_get_lval (sim%var_list, var_str ("read_raw")) &
            .and. .not. sim%rebuild_events
    end if
end subroutine simulation_setup_event_file_list

```



```

        sim%write_raw = var_list_get_lval (sim%var_list, var_str ("?write_raw"))
        extension_raw = var_list_get_sval (sim%var_list, var_str ("$extension_raw"))
        sim%file_raw = sim%basename // "." // extension_raw
    end if
    if (allocated (event_fmt)) then
        do i = 1, size (event_fmt)
            call event_file_list_append_file_spec (sim%event_file_list, &
                sim%basename, sim%var_list, event_fmt(i), &
                sim%beam_flv, sim%beam_energy, sim%n_proc)
        end do
    end if
    if (sim%rescan) then
        if (sim%read_raw) then
            if (event_file_list_is_filename (sim%event_file_list, sim%file_raw)) &
                call msg_fatal ("Output event file '" &
                    // char (sim%file_raw) // "' coincides with input file")
            else if (sim%read_hepmc) then
                if (event_file_list_is_filename (sim%event_file_list, sim%file_hepmc)) &
                    call msg_fatal ("Output event file '" &
                        // char (sim%file_hepmc) // "' coincides with input file")
            end if
        end if
    end if
end subroutine simulation_setup_event_file_list

```

Collect and store the integrals (cross sections) for the processes to simulate.

(Simulations: procedures)+≡

```

subroutine simulation_collect_integrals (sim, var_list, ok)
    type(simulation_t), intent(inout) :: sim
    type(var_list_t), intent(in) :: var_list
    logical, intent(out) :: ok
    integer :: proc
    type(process_t), pointer :: process
    type(string_t) :: process_id
    allocate (sim%integral (sim%n_proc))
    allocate (sim%error (sim%n_proc))
    do proc = 1, sim%n_proc
        process => sim%prc_array(proc)%ptr
        process_id = process_get_id (process)
        sim%integral(proc) = var_list_get_rval (var_list, &
            var_str ("integral(" // process_id // ")")
        sim%error(proc) = var_list_get_rval (var_list, &
            var_str ("error(" // process_id // ")")
        if (sim%integral(proc) < 0 .and. .not.sim%spar%negative_weights) then
            call msg_fatal ("Integral of process '" &
                // char (process_id) // "' is negative")
        end if
    end do
    sim%integral_sum = sum (sim%integral)
    sim%error_sum = sqrt (sum (sim%error ** 2))
    if (sim%integral_sum > 0) then
        ok = .true.
    else
        if (sim%spar%negative_weights) then
            ok = .false.
        end if
    end if
end subroutine simulation_collect_integrals

```

```

        else
            call msg_error ("Simulation: " &
                // "sum of process integrals must be positive; skipping")
            ok = .false.
        end if
    end if
end subroutine simulation_collect_integrals

```

Collect the MD5 sums that we will check when reading a raw event file.

(Simulations: procedures)+≡

```

subroutine simulation_collect_md5sums (sim)
    type(simulation_t), intent(inout) :: sim
    integer :: proc
    type(process_t), pointer :: process
    allocate (sim%md5sum%process (sim%n_proc))
    allocate (sim%md5sum%parameters (sim%n_proc))
    allocate (sim%md5sum%results (sim%n_proc))
    allocate (sim%md5sum%polarized (sim%n_proc))
    do proc = 1, sim%n_proc
        process => sim%prc_array(proc)%ptr
        sim%md5sum%process(proc) = process_get_md5sum (process)
        sim%md5sum%parameters(proc) = process_get_md5sum_parameters (process)
        sim%md5sum%results(proc) = process_get_md5sum_results (process)
        sim%md5sum%polarized(proc) = process_get_md5sum_polarized (process)
    end do
    if (sim%allow_decays) then
        sim%md5sum%decays = decay_store_get_md5sum ()
    else
        sim%md5sum%decays = ""
    end if
    sim%md5sum%simulation = simulation_parameters_get_md5sum (sim%spar)
end subroutine simulation_collect_md5sums

```

Choose the number of events to generate from either the luminosity or the specified `n_events`, whatever is larger. Return revised values for both luminosity and number of events.

Also determine the event weight normalization.

(Simulations: procedures)+≡

```

subroutine simulation_setup_n_events (sim, verbose)
    type(simulation_t), intent(inout) :: sim
    logical, intent(in), optional :: verbose
    integer :: n_events
    real(default) :: luminosity
    logical :: verb
    verb = .true.; if (present (verbose)) verb = verbose
    n_events = var_list_get_ival (sim%var_list, var_str ("n_events"))
    if (sim%rescan) then
        if (n_events /= 0) then
            sim%n_events = n_events
            if (verb) then
                write (msg_buffer, "(A,1x,I0)") &
                    "Requested number of events =", sim%n_events
                call msg_message ()
            end if
        end if
    end if
end subroutine simulation_setup_n_events

```

```

        end if
    else
        sim%n_events = huge (1)
    end if
    sim%luminosity = 0
    sim%norm_weight = 0
else
    luminosity = var_list_get_rval (sim%var_list, var_str ("luminosity"))
    if (.not.sim%spar%unweighted) then
        if (luminosity > 0) then
            if (n_events == 0) then
                call msg_fatal ("Setting a luminosity is only allowed for " // &
                               "unweighted events. Please set n_events.")
            else
                call msg_warning ("Setting a luminosity is only allowed for " // &
                                  "unweighted events. Luminosity will be ignored.")
            end if
            luminosity = 0
        end if
    end if
    sim%n_events = max (nint (luminosity * sim%integral_sum), n_events)
    sim%n_events_set = (sim%n_events.eq.n_events)
    sim%luminosity = max (luminosity, sim%n_events / sim%integral_sum)
    sim%norm_weight = simulation_parameters_get_norm &
        (sim%spar, sim%integral_sum, sim%n_events)
    if (verb) then
        write (msg_buffer, "(A,1x,I0)") &
            "Requested number of events =", sim%n_events
        call msg_message ()
        if (sim%spar%unweighted) then
            write (msg_buffer, "(A,1x,G11.4)") &
                "This corresponds to luminosity [fb-1] = ", &
                sim%luminosity
            call msg_message ()
        end if
    end if
end if
end subroutine simulation_setup_n_events

```

Final preliminaries for event generation: Set up decay trees, prepare each process, and open files.

(Simulations: procedures)+≡

```

subroutine simulation_prepare_event_generation (sim, verbose)
    type(simulation_t), intent(inout), target :: sim
    logical, intent(in), optional :: verbose
    integer :: proc
    logical :: ok, verb
    type(process_t), pointer :: process
    verb = .false.; if (present (verbose)) verb = verbose
    if (sim%allow_decays) allocate (sim%decay_tree (sim%n_proc))
    do proc = 1, sim%n_proc
        process => sim%prc_array(proc)%ptr
        call process_setup_event_generation (process)
    end do
end subroutine

```

```

        if (sim%allow_decays) &
            call decay_tree_init (sim%decay_tree(proc), process)
    end do
    call event_file_list_open (sim%event_file_list, sim%process_id, &
        sim%n_events, sim%var_list)
    if (sim%read_raw) then
        call open_raw_event_file_for_reading &
            (sim%file_raw, sim%rescan, sim%check_event_file, sim%md5sum, &
            sim%version, sim%u_raw, ok, verbose)
        if (.not. ok) sim%read_raw = .false.
    else if (sim%read_hepmc) then
        call input_event_stream_init &
            (sim%input_stream, sim%file_hepmc, FMT_HEPMC)
    else
        if (verb) then
            write (msg_buffer, "(A,I0,A)" &
                "Generating ", sim%n_events, " events ...")
            call msg_message
        end if
    end if
    if (.not. sim%read_raw) then
        if (sim%write_raw) then
            call open_raw_event_file_for_writing &
                (sim%file_raw, sim%md5sum, sim%version, sim%u_raw, verbose)
        end if
    end if
    call checkpointing_init (sim%checkpointing, sim%var_list)
    sim%n_read = 0
    sim%i_evt = 0
    sim%n_selected = 0
end subroutine simulation_prepare_event_generation

```

Initialize a selection expression. This establishes a pointer-target relation between the selection expression, the subevent, and certain variables.

This is public, since the analysis is a separate object.

<Simulations: public>+≡

```
public :: simulation_setup_selection
```

<Simulations: procedures>+≡

```

subroutine simulation_setup_selection (sim, pn_selection_lexpr, verbose)
    type(simulation_t), intent(inout), target :: sim
    type(parse_node_t), pointer :: pn_selection_lexpr
    logical, intent(in), optional :: verbose
    logical :: verb
    verb = .false.; if (present (verbose)) verb = verbose
    if (verb) then
        if (associated (pn_selection_lexpr)) then
            call msg_message ("Applying user-defined selection expression.")
        end if
    end if
    if (associated (pn_selection_lexpr)) then
        sim%user_selection = .true.
        call eval_tree_init_lexpr (sim%selection_expr, &
            pn_selection_lexpr, sim%var_list, sim%subevt, &

```

```

        sim%event_vars)
    else
        sim%user_selection = .false.
    end if
end subroutine simulation_setup_selection

```

Initialize a reweighting expression. This establishes a pointer-target relation between the reweighting expression, the subevent, and certain variables.

This is public, since the analysis is a separate object.

```

<Simulations: public>+≡
    public :: simulation_setup_reweight

<Simulations: procedures>+≡
    subroutine simulation_setup_reweight (sim, pn_reweight_expr, verbose)
        type(simulation_t), intent(inout), target :: sim
        type(parse_node_t), pointer :: pn_reweight_expr
        logical, intent(in), optional :: verbose
        logical :: verb
        verb = .false.; if (present (verbose)) verb = verbose
        if (verb) then
            if (associated (pn_reweight_expr)) then
                call msg_message ("Applying user-defined reweighting expression.")
            end if
        end if
        if (associated (pn_reweight_expr)) then
            call eval_tree_init_expr (sim%reweight_expr, &
                pn_reweight_expr, sim%var_list, sim%subevt, &
                sim%event_vars)
        end if
    end subroutine simulation_setup_reweight

```

Initialize the analysis expression. This establishes a pointer-target relation between the analysis expression, the subevent, and certain variables.

This is public, since the analysis is a separate object.

```

<Simulations: public>+≡
    public :: simulation_setup_analysis

<Simulations: procedures>+≡
    subroutine simulation_setup_analysis (sim, pn_analysis_lexpr, verbose)
        type(simulation_t), intent(inout), target :: sim
        type(parse_node_t), pointer :: pn_analysis_lexpr
        logical, intent(in), optional :: verbose
        logical :: verb
        verb = .false.; if (present (verbose)) verb = verbose
        if (verb) then
            if (associated (pn_analysis_lexpr)) then
                call msg_message ("Applying user-defined analysis setup.")
            else
                call msg_message ("No analysis setup has been provided.")
            end if
        end if
        if (associated (pn_analysis_lexpr)) then
            call eval_tree_init_lexpr (sim%analysis_expr, &

```

```

        pn_analysis_lexpr, sim%var_list, sim%subevt, &
        sim%event_vars)
    end if
end subroutine simulation_setup_analysis

```

Generating one event

Read an event from the 'raw' event file. If EOF is reached, close it, reset the `read_raw` flag, and reopen it for writing if `write_raw` is set.

When reopening the raw event file, we have to re-do some process initialization that may get lost when reading events from file before.

This initializes the event object, if successful.

(Simulations: procedures)+≡

```

subroutine simulation_read_event_raw (sim, ok, verbose)
    type(simulation_t), intent(inout), target :: sim
    logical, intent(out) :: ok
    logical, intent(in), optional :: verbose
    logical :: verb
    integer :: iostat
    verb = .false.; if (present (verbose)) verb = verbose
    if (sim%use_num_id) then
        call event_read_raw (sim%event, sim%u_raw, &
            sim%event_vars, sim%prc_array, num_id_array=sim%num_id, &
            iostat=iostat, version=sim%version)
    else
        call event_read_raw (sim%event, sim%u_raw, &
            sim%event_vars, sim%prc_array, iostat=iostat, version=sim%version)
    end if
    if (iostat == 0) then
        sim%i_evt = sim%i_evt + 1
        sim%n_read = sim%n_read + 1
        ok = .true.
    else
        ok = .false.
        if (verb) then
            write (msg_buffer, "(A,1x,I0,1x,A)" &
                "...", sim%n_read, "events read."
            call msg_message ()
        end if
        if (.not. sim%rescan) then
            sim%read_raw = .false.
            if (verb) then
                write (msg_buffer, "(A,1x,I0,1x,A)" &
                    "Generating", sim%n_events - sim%n_read, " events ..."
                call msg_message ()
            end if
            if (sim%write_raw) then
                call reopen_raw_event_file_for_writing &
                    (sim%file_raw, sim%u_raw, verbose)
            else
                close (sim%u_raw)
            end if
        end if
    end if
end subroutine

```

```

        ok = .true.
        call reinitialize_processes (sim%prc_array)
    end if
end if
end subroutine simulation_read_event_raw

```

For all processes in the current simulation, redo the initialization of the subevent that is used for cuts etc. This subevent may be corrupted by previous events read from file.

```

<Simulations: procedures>+≡
subroutine reinitialize_processes (prc_array)
    type(process_p), dimension(:), intent(in) :: prc_array
    type(process_t), pointer :: process
    integer :: i
    do i = 1, size (prc_array)
        process => prc_array(i)%ptr
        call process_setup_subevt (process)
    end do
end subroutine reinitialize_processes

```

Read an event from a HepMC file.

```

<Simulations: procedures>+≡
subroutine simulation_read_event_hepmc (sim, ok)
    type(simulation_t), intent(inout), target :: sim
    logical, intent(out) :: ok
    if (sim%use_num_id) then
        call input_event_stream_read_event (sim%input_stream, sim%event, &
            sim%event_vars, sim%prc_array, ok, num_id_array=sim%num_id)
    else
        call input_event_stream_read_event (sim%input_stream, sim%event, &
            sim%event_vars, sim%prc_array, ok)
    end if
end subroutine simulation_read_event_hepmc

```

Select a random process for the current event, based on the relative sizes of the process integrals.

```

<Simulations: procedures>+≡
subroutine simulation_select_process (sim, rng, process, proc)
    type(simulation_t), intent(in) :: sim
    type(tao_random_state), intent(inout) :: rng
    type(process_t), pointer :: process
    integer, intent(out) :: proc
    real(default) :: integral_cmp, x
    call tao_random_number (rng, x)
    integral_cmp = 0
    do proc = 1, sim%n_proc
        integral_cmp = integral_cmp + sim%integral(proc)
        if (integral_cmp > x * sim%integral_sum) exit
    end do
    proc = min (proc, sim%n_proc)
    process => sim%prc_array(proc)%ptr
end subroutine simulation_select_process

```

Recover the process for the current event, which should be filled already.

(Simulations: procedures)+≡

```

subroutine simulation_recover_process (sim, proc)
  type(simulation_t), intent(inout) :: sim
  integer, intent(out) :: proc
  type(string_t) :: process_id
  type(process_t), pointer :: process
  process => event_get_process_ptr (sim%event)
  if (associated (process)) then
    process_id = process_get_id (process)
    do proc = 1, sim%n_proc
      if (process_id == process_get_id (sim%prc_array(proc)%ptr)) then
        call event_recover_process (sim%event)
        return
      end if
    end do
  end if
  call event_write (sim%event)
  call msg_fatal ("Simulation: recovering process data from event failed.")
  proc = 0
end subroutine simulation_recover_process

```

Recalculate the matrix element for the process, refreshing the model parameters and, if required, the scale and α_s values.

(Simulations: procedures)+≡

```

subroutine simulation_recalculate (sim)
  type(simulation_t), intent(inout) :: sim
  if (sim%update_parameters) call event_update_parameters (sim%event)
  if (sim%update_scale) call event_compute_scale (sim%event)
  if (sim%update_alpha_s) call event_update_alpha_s (sim%event)
  if (sim%update_sqme) call event_compute_sqme (sim%event)
  if (sim%update_weight) call event_update_weight (sim%event)
end subroutine simulation_recalculate

```

Generate a new event for the selected process. This initializes the event object. We reject invalid events until a valid event could be produced.

(Limits: public parameters)+≡

```

integer, parameter, public :: MAX_TRIES_FOR_SINGLE_EVENT = 100000

```

(Simulations: procedures)+≡

```

subroutine simulation_generate_event (sim, rng, process, proc, os_data)
  type(simulation_t), intent(inout), target :: sim
  type(tao_random_state), intent(inout) :: rng
  type(process_t), intent(in), target :: process
  integer, intent(in) :: proc
  type(os_data_t), intent(in) :: os_data
  integer :: factorization_mode, try
  if (sim%allow_decays) then
    call event_init (sim%event, process, &
      sim%event_vars, sim%decay_tree(proc))
  else
    call event_init (sim%event, process, sim%event_vars)
  end if
end subroutine simulation_generate_event

```



```

end if
if (sim%use_num_id) then
  sim%event_vars%process_num_id = sim%num_id(proc)
else
  sim%event_vars%process_num_id = proc
end if
sim%event_vars%process_id = process_get_id (process)
if (sim%spar%polarized) then
  factorization_mode = FM_SELECT_HELICITY
else
  factorization_mode = FM_IGNORE_HELICITY
end if
GENERATE: do try = 1, MAX_TRIES_FOR_SINGLE_EVENT
  call event_generate &
    (sim%event, rng, sim%spar%unweighted, &
     factorization_mode, &
     keep_correlations=.false., &
     keep_virtual=.true., os_data=os_data, &
     shower_settings = sim%spar%shower_settings)
  if(event_is_vetoed(sim%event).and. &
     (.not.sim%n_events_set)) then
    sim%n_events = sim%n_events - 1
    if(sim%i_evt .ge. sim%n_events) then
      call event_final(sim%event)
      return
    end if
  end if
  if (event_is_valid (sim%event).and. &
     (.not.event_is_vetoed(sim%event))) exit GENERATE
end do GENERATE
if (.not. event_is_valid (sim%event)) then
  write (msg_buffer, "(A,I0,A)") "Failed to generate a valid event " &
    // "after ", MAX_TRIES_FOR_SINGLE_EVENT, " tries"
  call msg_fatal ()
end if
sim%i_evt = sim%i_evt + 1
sim%event_vars%process_index = proc
sim%event_vars%event_index = sim%i_evt
call event_renormalize_weight (sim%event, sim%norm_weight)
end subroutine simulation_generate_event

```

Explicitly apply decays to an existing event. (Implicitly called by the previous procedure.)

(Simulations: procedures)+≡

```

subroutine simulation_decay (sim, rng, proc)
  type(simulation_t), intent(inout), target :: sim
  type(tao_random_state), intent(inout) :: rng
  integer, intent(in) :: proc
  if (sim%allow_decays) then
    call event_decay (sim%event, rng, sim%decay_tree(proc))
    call event_factorize_process (sim%event, rng, &
      FM_IGNORE_HELICITY, &
      keep_correlations=.false., &

```

```

        keep_virtual=.true.)
    end if
end subroutine simulation_decay

```

Further process an event. This implies analysis and output. Events which fail extra selection cuts (if any) are neither analyzed nor written to file, but they count for the total number of generated events. However, the raw event file will contain the rejected events.

Writing to raw event file is appropriate only if reading from this file is disabled or has terminated.

```

<Simulations: procedures>+≡
subroutine simulation_handle_event (sim)
  type(simulation_t), intent(inout), target :: sim
  if (event_passes_selection (sim%event, sim%subevt, sim%selection_expr)) &
    then
      sim%n_selected = sim%n_selected + 1
      call event_reweight (sim%event, sim%subevt, sim%reweight_expr)
      call event_do_analysis (sim%event, sim%subevt, sim%analysis_expr)
      call event_file_list_write_event &
        (sim%event_file_list, sim%event, sim%integral_sum, sim%error_sum, &
          sim%analysis_expr, i_evt=sim%i_evt)
    end if
  if (sim%write_raw .and. .not. sim%read_raw) &
    call event_write_raw (sim%event, sim%u_raw, sim%version)
  call checkpointing_msg_event &
    (sim%checkpointing, sim%n_events, sim%n_read, sim%i_evt)
end subroutine simulation_handle_event

```

Finalize the event.

```

<Simulations: procedures>+≡
subroutine simulation_final_event (sim)
  type(simulation_t), intent(inout), target :: sim
  call event_final (sim%event)
end subroutine simulation_final_event

```

Wrapup

Close open files and delete the decay tree and analysis expression:

```

<Simulations: procedures>+≡
subroutine simulation_finish_event_generation (sim, verbose)
  type(simulation_t), intent(inout) :: sim
  logical, intent(in), optional :: verbose
  integer :: proc
  logical :: verb
  verb = .false.; if (present (verbose)) verb = verbose
  call checkpointing_msg_end &
    (sim%checkpointing, sim%n_read, sim%i_evt)
  call event_file_list_close (sim%event_file_list)
  if (sim%read_raw .or. sim%write_raw) close (sim%u_raw)
  if (sim%read_hePMC) call input_event_stream_final (sim%input_stream)
  if (sim%allow_decays) then

```

```

do proc = 1, sim%n_proc
  call decay_tree_final (sim%decay_tree(proc))
end do
end if
call eval_tree_final (sim%analysis_expr)
if (verb) then
  if (sim%rescan) then
    call msg_selection (sim%user_selection, sim%n_selected)
    call msg_message ("Rescanning finished.")
  else
    if (sim%read_raw) then
      write (msg_buffer, "(A,1x,I0,1x,A,1x,I0,1x,A)" &
        "...", sim%n_read, "events read,", sim%n_events, "total."
      call msg_message ()
    else
      write (msg_buffer, "(A,1x,I0,1x,A,1x,I0,1x,A)" &
        "...", sim%n_events - sim%n_read, "events generated.", &
        sim%n_events, "total."
      call msg_message ()
    end if
    call msg_selection (sim%user_selection, sim%n_selected)
    call msg_message ("Simulation finished.")
  end if
end if
contains
subroutine msg_selection (user_selection, n_selected)
  logical, intent(in) :: user_selection
  integer, intent(in) :: n_selected
  if (user_selection) then
    write (msg_buffer, "(A,1x,I0)" &
      "Events passing selection cuts:", n_selected
    call msg_message ()
  end if
end subroutine msg_selection
end subroutine simulation_finish_event_generation

```

Deallocate extra memory where necessary

```

<Simulations: procedures>+≡
subroutine simulation_basic_final (sim)
  type(simulation_t), intent(inout) :: sim
  call var_list_final (sim%var_list)
end subroutine simulation_basic_final

```

Dealing with the event file

Open a raw event file for reading, check the header and validity. If `rescan` is set, check only processes and simulation parameters, otherwise check everything.

```

<Simulations: procedures>+≡
subroutine open_raw_event_file_for_reading &
  (file_raw, rescan, check, md5sum, version, u_raw, ok, verbose)
  type(string_t), intent(in) :: file_raw
  logical, intent(in) :: rescan, check

```

```

type(md5sum_events_t), intent(in) :: md5sum
integer, intent(in) :: version
integer, intent(out) :: u_raw
logical, intent(out) :: ok
logical, intent(in), optional :: verbose
logical :: verb
integer :: iostat
verb = .false.; if (present (verbose)) verb = verbose
if (.not. check) call msg_warning &
    ("Validity checks turned off for event file '" &
    // char (file_raw) // "'")
inquire (file = char (file_raw), exist = ok)
if (check .and. ok) then
    ok = event_file_get_format (file_raw) == FMT_RAW
    if (.not. ok) then
        call msg_warning ("File '" // char (file_raw) &
        // "' is not a WHIZARD raw event file, discarding.")
    end if
end if
if (ok) then
    if (verb) call msg_message ("Reading events from file '" &
    // char (file_raw) // "' ...")
    u_raw = free_unit ()
    open (file = char (file_raw), unit = u_raw, form = "unformatted", &
    action = "read", status = "old")
    call raw_event_file_read_header &
    (u_raw, rescan, check, md5sum, version, ok, iostat)
    if (iostat /= 0) then
        call msg_error ("Event file '" &
        // char (file_raw) // "' is corrupt, discarding.")
        close (u_raw)
        ok = .false.
    else if (.not. ok) then
        close (u_raw)
        ok = .false.
    else
        ok = .true.
    end if
end if
end subroutine open_raw_event_file_for_reading

```

Open a raw event file for writing, write header. If `append` is set, close the existing file and reopen it for appending more events.

(*Simulations: procedures*) +=

```

subroutine open_raw_event_file_for_writing &
    (file_raw, md5sum, version, u_raw, verbose)
type(string_t), intent(in) :: file_raw
type(md5sum_events_t), intent(in) :: md5sum
integer, intent(in) :: version
integer, intent(out) :: u_raw
logical, intent(in), optional :: verbose
logical :: verb
verb = .false.; if (present (verbose)) verb = verbose

```

```

    if (verb) then
        call msg_message ("Writing events in internal format to file '" &
            // char (file_raw) // "'")
    end if
    u_raw = free_unit ()
    open (file = char (file_raw), unit = u_raw, form = "unformatted", &
        action = "write", status = "replace")
    call raw_event_file_write_header (u_raw, md5sum, version)
end subroutine open_raw_event_file_for_writing

```

Reopen a raw event file for writing, no header. Append new events to the end.

<Simulations: procedures>+≡

```

subroutine reopen_raw_event_file_for_writing (file_raw, u_raw, verbose)
    type(string_t), intent(in) :: file_raw
    integer, intent(in) :: u_raw
    logical, intent(in), optional :: verbose
    logical :: verb
    verb = .false.; if (present (verbose)) verb = verbose
    if (verb) then
        call msg_message ("Appending events in internal format to file '" &
            // char (file_raw) // "'")
    end if
    close (u_raw)
    open (file = char (file_raw), unit = u_raw, form = "unformatted", &
        action = "write", status = "old", position = "append")
end subroutine reopen_raw_event_file_for_writing

```

API for simulation objects

This initializer does everything, except assigning the analysis expression. If ok is false, initialization failed and the simulation should be skipped.

If filename is provided, this is not a simulation but rescanning an event file.

The global_var_list is the one where missing integrals are inserted, if they are computed here. It is not necessarily the one within the global object.

<Simulations: public>+≡

```

public :: simulation_init

```

<Simulations: procedures>+≡

```

subroutine simulation_init &
    (sim, process_id, global, global_var_list, ok, filename, verbose)
    type(simulation_t), intent(out) :: sim
    type(string_t), dimension(:), intent(in) :: process_id
    type(rt_data_t), intent(inout), target :: global
    type(var_list_t), intent(inout) :: global_var_list
    logical, intent(out) :: ok
    type(string_t), intent(in), optional :: filename
    logical, intent(in), optional :: verbose
    type(string_t) :: basename_default
    logical :: rescan
    rescan = present (filename)
    if (size (process_id) /= 0) then
        basename_default = process_id(1)
    end if
end subroutine simulation_init

```

```

else
    basename_default = "whizard"
end if
if (rescan) then
    call simulation_init_rescan &
        (sim, filename, process_id, global%var_list, verbose)
else
    call simulation_basic_init &
        (sim, process_id, global%var_list, verbose=verbose)
end if
call simulation_compute_missing_integrals &
    (sim, global, global_var_list, rescan, verbose)
if (sim%spare%use_best_grid) call simulation_choose_best_grids (sim)
call simulation_check (sim, ok)
if (ok .and. .not. rescan) then
    call simulation_collect_integrals (sim, global%var_list, ok)
end if
if (ok) then
    call simulation_setup_event_file_list &
        (sim, global%event_fmt, basename_default)
    call simulation_collect_md5sums (sim)
    call simulation_setup_n_events (sim, verbose)
    call simulation_prepare_event_generation (sim, verbose)
end if
if (.not. ok) call simulation_basic_final (sim)
end subroutine simulation_init

```

Return the number of events determined during initialization.

```

<Simulations: public>+≡
    public :: simulation_get_n_events
<Simulations: procedures>+≡
    function simulation_get_n_events (sim) result (n_events)
        integer :: n_events
        type(simulation_t), intent(in) :: sim
        n_events = sim%n_events
    end function simulation_get_n_events

```

Return the number of events simulated so far.

```

<Simulations: public>+≡
    public :: simulation_get_i_evt
<Simulations: procedures>+≡
    function simulation_get_i_evt (sim) result (i_evt)
        integer :: i_evt
        type(simulation_t), intent(in) :: sim
        i_evt = sim%i_evt
    end function simulation_get_i_evt

```

Get and handle a new event. Either read it from file or generate it. If reading fails and we are allowed to generate new events, `read_raw` is reset, so we need a separate check.

```

<Simulations: public>+≡
    public :: simulation_event

```

<Simulations: procedures>+≡

```

subroutine simulation_event (sim, rng, ok, os_data, verbose)
  type(simulation_t), intent(inout), target :: sim
  type(tao_random_state), intent(inout) :: rng
  logical, intent(out) :: ok
  type(os_data_t), intent(in) :: os_data
  logical, intent(in), optional :: verbose
  type(process_t), pointer :: process
  integer :: proc
  if (sim%read_raw) then
    call simulation_read_event_raw (sim, ok, verbose)
  else if (sim%read_hepmc) then
    call simulation_read_event_hepmc (sim, ok)
  end if
  if (sim%rescan) then
    if (.not. ok) return
    call simulation_recover_process (sim, proc)
    call simulation_recalculate (sim)
    call simulation_decay (sim, rng, proc)
  else if (.not. sim%read_raw) then
    if (sim%checkpointing%active .and. (.not. sim%checkpointing%running)) &
      call checkpointing_msg_start (sim%checkpointing, sim%n_events, &
        sim%i_evt)
    call simulation_select_process (sim, rng, process, proc)
    call simulation_generate_event (sim, rng, process, proc, os_data)
  end if
  call simulation_handle_event (sim)
  call simulation_final_event (sim)
end subroutine simulation_event

```

Finalize simulation and the simulation object.

<Simulations: public>+≡

```

public :: simulation_final

```

<Simulations: procedures>+≡

```

subroutine simulation_final (sim, verbose)
  type(simulation_t), intent(inout) :: sim
  logical, intent(in), optional :: verbose
  call simulation_finish_event_generation (sim, verbose)
  call simulation_basic_final (sim)
end subroutine simulation_final

```

Chapter 17

Top level API

17.1 Commands

This module defines the command language of the main input file.

$\langle \text{commands.f90} \rangle \equiv$
 $\langle \text{File header} \rangle$

```
module commands

   $\langle \text{Use kinds} \rangle$ 
   $\langle \text{Use strings} \rangle$ 
  use constants !NODEP!
   $\langle \text{Use file utils} \rangle$ 
  use limits, only: HISTOGRAM_DATA_FORMAT !NODEP!
  use limits, only: DEFAULT_ANALYSIS_FILENAME !NODEP!
  use limits, only: FORBIDDEN_ENDINGS1 !NODEP!
  use limits, only: FORBIDDEN_ENDINGS2 !NODEP!
  use limits, only: FORBIDDEN_ENDINGS3 !NODEP!
  use diagnostics !NODEP!
  use lorentz !NODEP!
  use tao_random_numbers !NODEP!
  use pdf_builtin !NODEP!
  use md5
  use os_interface
  use ifiles
  use lexers
  use syntax_rules
  use parser
  use analysis
  use pdg_arrays
  use subevents
  use variables
  use expressions
  use models
  use state_matrices
  use flavors
  use quantum_numbers
  use polarizations
```



```

use beams
use strfun
use mappings
use phs_forests
use cascades
use process_libraries
use processes
use decays
use events
use slha_interface
use cputime
use iterations
use beam_polarizations
use strfun_config
use event_files
use user_files
use rt_data
use compilations
use integrations
use simulations

⟨Standard module head⟩

⟨Commands: public⟩

⟨Commands: parameters⟩

⟨Commands: types⟩

⟨Commands: variables⟩

contains

⟨Commands: procedures⟩

end module commands

```

17.1.1 The command type

The command type is a generic type that holds any command, compiled for execution. It is part of a command list. These are the possibilities:

```

⟨Commands: parameters⟩≡
integer, parameter :: CMD_NONE = 0
integer, parameter :: CMD_PROCESS = 1
integer, parameter :: CMD_INTEGRATE = 2
integer, parameter :: CMD_SIMULATE = 3
integer, parameter :: CMD_RESCAN = 4
integer, parameter :: CMD_ME_TEST = 5

integer, parameter :: CMD_COMPILE = 10
integer, parameter :: CMD_LOAD = 11
integer, parameter :: CMD_EXEC = 13

```

```
integer, parameter :: CMD_BEAMS = 21
integer, parameter :: CMD_BEAM_POLARIZATION = 22
```

```
integer, parameter :: CMD_MODEL = 31
integer, parameter :: CMD_LIBRARY = 32
integer, parameter :: CMD_CUTS = 33
integer, parameter :: CMD_SCALE = 34
integer, parameter :: CMD_FAC_SCALE = 35
integer, parameter :: CMD_REN_SCALE = 36
integer, parameter :: CMD_WEIGHT = 37
integer, parameter :: CMD_SELECTION = 38
integer, parameter :: CMD_REWEIGHT = 39
```

```
integer, parameter :: CMD_VAR = 41
integer, parameter :: CMD_SHOW = 45
integer, parameter :: CMD_EXPECT = 46
```

```
integer, parameter :: CMD_UNSTABLE = 51
integer, parameter :: CMD_STABLE = 52
integer, parameter :: CMD_POLARIZED = 53
integer, parameter :: CMD_UNPOLARIZED = 54
```

```
integer, parameter :: CMD_SEED = 63
integer, parameter :: CMD_ITERATIONS = 64
integer, parameter :: CMD_SAMPLE_FORMAT = 65
```

```
integer, parameter :: CMD_CLEAR = 66
```

```
integer, parameter :: CMD_ANALYSIS = 71
integer, parameter :: CMD_OBSERVABLE = 72
integer, parameter :: CMD_HISTOGRAM = 73
integer, parameter :: CMD_PLOT = 74
integer, parameter :: CMD_GRAPH = 75
integer, parameter :: CMD_RECORD = 76
integer, parameter :: CMD_WRITE_ANALYSIS = 77
integer, parameter :: CMD_COMPILE_ANALYSIS = 78
integer, parameter :: CMD_HISTOGRAM_WRITER = 79
integer, parameter :: CMD_PLOT_WRITER = 80
```

```
integer, parameter :: CMD_OPEN_OUT = 81
integer, parameter :: CMD_CLOSE_OUT = 83
integer, parameter :: CMD_PRINTD = 85
integer, parameter :: CMD_PRINTF = 86
```

```
integer, parameter :: CMD_INCLUDE = 91
integer, parameter :: CMD_SCAN = 92
integer, parameter :: CMD_IF = 93
integer, parameter :: CMD_QUIT = 99
```

```
integer, parameter :: CMD_SLHA = 101
```

$\langle \text{Commands: types} \rangle \equiv$

```
type :: command_t
```

```
! not private anymore as required by the whizard-c-interface
```

```

integer :: type = CMD_NONE
type(cmd_model_t), pointer :: model => null ()
type(cmd_library_t), pointer :: library => null ()
type(cmd_process_t), pointer :: process => null ()
type(cmd_compile_t), pointer :: compile => null ()
type(cmd_load_t), pointer :: load => null ()
type(cmd_exec_t), pointer :: exec => null ()
type(cmd_var_t), pointer :: var => null ()
type(cmd_slha_t), pointer :: slha => null ()
type(cmd_show_t), pointer :: show => null ()
type(cmd_expect_t), pointer :: expect => null ()
type(cmd_beams_t), pointer :: beams => null ()
type(cmd_beam_polarization_t), pointer :: beam_polarization => null ()
type(cmd_cuts_t), pointer :: cuts => null ()
type(cmd_scale_t), pointer :: scale => null ()
type(cmd_fac_scale_t), pointer :: fac_scale => null ()
type(cmd_ren_scale_t), pointer :: ren_scale => null ()
type(cmd_weight_t), pointer :: weight => null ()
type(cmd_selection_t), pointer :: selection => null ()
type(cmd_reweight_t), pointer :: reweight => null ()
type(cmd_seed_t), pointer :: seed => null ()
type(cmd_iterations_t), pointer :: iterations => null ()
type(cmd_integrate_t), pointer :: integrate => null ()
type(cmd_me_test_t), pointer :: me_test => null ()
type(cmd_observable_t), pointer :: observable => null ()
type(cmd_histogram_t), pointer :: histogram => null ()
type(cmd_plot_t), pointer :: plot => null ()
type(cmd_graph_t), pointer :: graph => null ()
type(cmd_clear_t), pointer :: clear => null ()
type(cmd_record_t), pointer :: record => null ()
type(cmd_analysis_t), pointer :: analysis => null ()
type(cmd_write_analysis_t), pointer :: write_analysis => null ()
type(cmd_write_analysis_t), pointer :: compile_analysis => null ()
type(cmd_xxx_writer_t), pointer :: xxx_writer => null ()
type(cmd_open_t), pointer :: open_out => null ()
type(cmd_close_t), pointer :: close_out => null ()
type(cmd_printd_t), pointer :: printd => null ()
type(cmd_printf_t), pointer :: printf => null ()
type(cmd_unstable_t), pointer :: unstable => null ()
type(cmd_stable_t), pointer :: stable => null ()
type(cmd_un_polarized_t), pointer :: un_polarized => null ()
type(cmd_sample_format_t), pointer :: events => null ()
type(cmd_simulate_t), pointer :: simulate => null ()
type(cmd_rescan_t), pointer :: rescan => null ()
type(cmd_scan_t), pointer :: loop => null ()
type(cmd_if_t), pointer :: cond => null ()
type(cmd_include_t), pointer :: include => null ()
type(cmd_quit_t), pointer :: quit => null ()
type(command_t), pointer :: next => null ()
end type command_t

```

Finalizer: Delete the specific command entry.

$\langle \text{Commands: procedures} \rangle \equiv$

```

recursive subroutine command_final (command)
  type(command_t), intent(inout) :: command
  select case (command%type)
  case (CMD_NONE)
  case (CMD_MODEL)
    deallocate (command%model)
  case (CMD_LIBRARY)
    deallocate (command%library)
  case (CMD_PROCESS)
    call cmd_process_final (command%process)
    deallocate (command%process)
  case (CMD_COMPILE)
    call cmd_compile_final (command%compile)
    deallocate (command%compile)
  case (CMD_LOAD)
    call cmd_load_final (command%load)
    deallocate (command%load)
  case (CMD_EXEC)
    call cmd_exec_final (command%exec)
    deallocate (command%exec)
  case (CMD_VAR)
    call cmd_var_final (command%var)
    deallocate (command%var)
  case (CMD_SLHA)
    call cmd_slha_final (command%slha)
    deallocate (command%slha)
  case (CMD_SHOW)
    call cmd_show_final (command%show)
    deallocate (command%show)
  case (CMD_EXPECT)
    call cmd_expect_final (command%expect)
    deallocate (command%expect)
  case (CMD_BEAMS)
    call cmd_beams_final (command%beams)
    deallocate (command%beams)
  case (CMD_BEAM_POLARIZATION)
    call cmd_beam_polarization_final (command%beam_polarization)
    deallocate (command%beam_polarization)
  case (CMD_CUTS)
    deallocate (command%cuts)
  case (CMD_SCALE)
    deallocate (command%scale)
  case (CMD_FAC_SCALE)
    deallocate (command%fac_scale)
  case (CMD_REN_SCALE)
    deallocate (command%ren_scale)
  case (CMD_WEIGHT)
    deallocate (command%weight)
  case (CMD_SELECTION)
    deallocate (command%selection)
  case (CMD_REWEIGHT)
    deallocate (command%reweight)
  case (CMD_SEED)
    call cmd_seed_final (command%seed)

```

```

        deallocate (command%seed)
case (CMD_ITERATIONS)
    call cmd_iterations_final (command%iterations)
    deallocate (command%iterations)
case (CMD_INTEGRATE)
    call cmd_integrate_final (command%integrate)
    deallocate (command%integrate)
case (CMD_ME_TEST)
    call cmd_me_test_final (command%me_test)
    deallocate (command%me_test)
case (CMD_OBSERVABLE)
    call cmd_observable_final (command%observable)
    deallocate (command%observable)
case (CMD_HISTOGRAM)
    call cmd_histogram_final (command%histogram)
    deallocate (command%histogram)
case (CMD_PLOT)
    call cmd_plot_final (command%plot)
    deallocate (command%plot)
case (CMD_GRAPH)
    call cmd_graph_final (command%graph)
    deallocate (command%graph)
case (CMD_CLEAR)
    call cmd_clear_final (command%clear)
    deallocate (command%clear)
case (CMD_RECORD)
    call cmd_record_final (command%record)
    deallocate (command%record)
case (CMD_ANALYSIS)
    deallocate (command%analysis)
case (CMD_UNSTABLE)
    call cmd_unstable_final (command%unstable)
    deallocate (command%unstable)
case (CMD_STABLE)
    call cmd_stable_final (command%stable)
    deallocate (command%stable)
case (CMD_POLARIZED, CMD_UNPOLARIZED)
    call cmd_un_polarized_final (command%un_polarized)
    deallocate (command%un_polarized)
case (CMD_SAMPLE_FORMAT)
    call cmd_sample_format_final (command%events)
    deallocate (command%events)
case (CMD_SIMULATE)
    call cmd_simulate_final (command%simulate)
    deallocate (command%simulate)
case (CMD_RESCAN)
    call cmd_rescan_final (command%rescan)
    deallocate (command%rescan)
case (CMD_WRITE_ANALYSIS)
    call cmd_write_analysis_final (command%write_analysis)
    deallocate (command%write_analysis)
case (CMD_COMPILE_ANALYSIS)
    call cmd_write_analysis_final (command%compile_analysis)
    deallocate (command%compile_analysis)

```

```

case (CMD_HISTOGRAM_WRITER, CMD_PLOT_WRITER)
  call cmd_xxx_writer_final (command%xxx_writer)
case (CMD_OPEN_OUT)
  call cmd_open_final (command%open_out)
case (CMD_CLOSE_OUT)
  call cmd_close_final (command%close_out)
case (CMD_PRINTD)
  call cmd_printd_final (command%printd)
  deallocate (command%printd)
case (CMD_PRINTF)
  call cmd_printf_final (command%printf)
  deallocate (command%printf)
case (CMD_SCAN)
  call cmd_scan_final (command%loop)
  deallocate (command%loop)
case (CMD_IF)
  call cmd_if_final (command%cond)
  deallocate (command%cond)
case (CMD_INCLUDE)
  call cmd_include_final (command%include)
  deallocate (command%include)
case (CMD_QUIT)
  call cmd_quit_final (command%quit)
  deallocate (command%quit)
end select
end subroutine command_final

```

Compile a command. This allocates the command pointer. Some need a variable list to link to as an extra argument. (The variable list is assigned by the `model` command.)

```

<Commands: procedures>+≡
recursive subroutine command_compile (command, pn, global)
  type(command_t), pointer :: command
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(inout), target :: global
  ! call parse_node_write (pn)
  allocate (command)
  select case (char (parse_node_get_rule_key (pn)))
  case ("cmd_model")
    command%type = CMD_MODEL
    call cmd_model_compile (command%model, pn, global)
  case ("cmd_library")
    command%type = CMD_LIBRARY
    call cmd_library_compile (command%library, pn)
  case ("cmd_process")
    command%type = CMD_PROCESS
    call cmd_process_compile (command%process, pn, global)
  case ("cmd_compile")
    command%type = CMD_COMPILE
    call cmd_compile_compile (command%compile, pn, global)
  case ("cmd_load")
    command%type = CMD_LOAD
    call cmd_load_compile (command%load, pn, global)
  end select
end subroutine command_compile

```

```

case ("cmd_exec")
  command%type = CMD_EXEC
  call cmd_exec_compile (command%exec, pn, global)
case ("cmd_num", "cmd_complex", "cmd_real", "cmd_int", &
      "cmd_log_decl", "cmd_log", "cmd_string", "cmd_string_decl", &
      "cmd_alias", "cmd_result")
  command%type = CMD_VAR
  call cmd_var_compile (command%var, pn, global)
case ("cmd_slha")
  command%type = CMD_SLHA
  call cmd_slha_compile (command%slha, pn, global)
case ("cmd_show")
  command%type = CMD_SHOW
  call cmd_show_compile (command%show, pn, global)
case ("cmd_expect")
  command%type = CMD_EXPECT
  call cmd_expect_compile (command%expect, pn, global)
case ("cmd_beams")
  command%type = CMD_BEAMS
  call cmd_beams_compile (command%beams, pn, global)
case ("cmd_beam_polarization")
  command%type = CMD_BEAM_POLARIZATION
  call cmd_beam_polarization_compile &
    (command%beam_polarization, pn, global)
case ("cmd_cuts")
  command%type = CMD_CUTS
  call cmd_cuts_compile (command%cuts, pn)
case ("cmd_scale")
  command%type = CMD_SCALE
  call cmd_scale_compile (command%scale, pn)
case ("cmd_fac_scale")
  command%type = CMD_FAC_SCALE
  call cmd_fac_scale_compile (command%fac_scale, pn)
case ("cmd_ren_scale")
  command%type = CMD_REN_SCALE
  call cmd_ren_scale_compile (command%ren_scale, pn)
case ("cmd_weight")
  command%type = CMD_WEIGHT
  call cmd_weight_compile (command%weight, pn)
case ("cmd_selection")
  command%type = CMD_SELECTION
  call cmd_selection_compile (command%selection, pn)
case ("cmd_reweight")
  command%type = CMD_REWEIGHT
  call cmd_reweight_compile (command%reweight, pn)
case ("cmd_seed")
  command%type = CMD_SEED
  call cmd_seed_compile (command%seed, pn, global)
case ("cmd_iterations")
  command%type = CMD_ITERATIONS
  call cmd_iterations_compile (command%iterations, pn, global)
case ("cmd_integrate")
  command%type = CMD_INTEGRATE
  call cmd_integrate_compile (command%integrate, pn, global)

```

```

case ("cmd_me_test")
    command%type = CMD_ME_TEST
    call cmd_me_test_compile (command%me_test, pn, global)
case ("cmd_observable")
    command%type = CMD_OBSERVABLE
    call cmd_observable_compile (command%observable, pn, global)
case ("cmd_histogram")
    command%type = CMD_HISTOGRAM
    call cmd_histogram_compile (command%histogram, pn, global)
case ("cmd_plot")
    command%type = CMD_PLOT
    call cmd_plot_compile (command%plot, pn, global)
case ("cmd_graph")
    command%type = CMD_GRAPH
    call cmd_graph_compile (command%graph, pn, global)
case ("cmd_clear")
    command%type = CMD_CLEAR
    call cmd_clear_compile (command%clear, pn, global)
case ("cmd_record")
    command%type = CMD_RECORD
    call cmd_record_compile (command%record, pn, global)
case ("cmd_analysis")
    command%type = CMD_ANALYSIS
    call cmd_analysis_compile (command%analysis, pn)
case ("cmd_unstable")
    command%type = CMD_UNSTABLE
    call cmd_unstable_compile (command%unstable, pn, global)
case ("cmd_stable")
    command%type = CMD_STABLE
    call cmd_stable_compile (command%stable, pn, global)
case ("cmd_polarized")
    command%type = CMD_POLARIZED
    call cmd_un_polarized_compile (command%un_polarized, pn, global)
case ("cmd_unpolarized")
    command%type = CMD_UNPOLARIZED
    call cmd_un_polarized_compile (command%un_polarized, pn, global)
case ("cmd_sample_format")
    command%type = CMD_SAMPLE_FORMAT
    call cmd_sample_format_compile (command%events, pn)
case ("cmd_simulate")
    command%type = CMD_SIMULATE
    call cmd_simulate_compile (command%simulate, pn, global)
case ("cmd_rescan")
    command%type = CMD_RESCAN
    call cmd_rescan_compile (command%rescan, pn, global)
case ("cmd_write_analysis")
    command%type = CMD_WRITE_ANALYSIS
    call cmd_write_analysis_compile (command%write_analysis, &
        pn, global)
case ("cmd_compile_analysis")
    command%type = CMD_COMPILE_ANALYSIS
    call cmd_write_analysis_compile (command%compile_analysis, pn, global)
case ("cmd_histogram_writer", "cmd_plot_writer")
    command%type = CMD_HISTOGRAM_WRITER

```



```

        call cmd_xxx_writer_compile (command%xxx_writer, pn, global)
case ("cmd_open_out")
    command%type = CMD_OPEN_OUT
    call cmd_open_out_compile (command%open_out, pn, global)
case ("cmd_close_out")
    command%type = CMD_CLOSE_OUT
    call cmd_close_out_compile (command%close_out, pn, global)
case ("cmd_printd")
    command%type = CMD_PRINTD
    call cmd_printd_compile (command%printd, pn, global)
case ("cmd_printf")
    command%type = CMD_PRINTF
    call cmd_printf_compile (command%printf, pn, global)
case ("cmd_scan")
    command%type = CMD_SCAN
    call cmd_scan_compile (command%loop, pn, global)
case ("cmd_if")
    command%type = CMD_IF
    call cmd_if_compile (command%cond, pn, global)
case ("cmd_include")
    command%type = CMD_INCLUDE
    call cmd_include_compile (command%include, pn, global)
case ("cmd_quit")
    command%type = CMD_QUIT
    call cmd_quit_compile (command%quit, pn, global)
case default
    print *, char (parse_node_get_rule_key (pn))
    call msg_bug ("Command not implemented")
end select
! call command_write (command)
end subroutine command_compile

```

Execute a command. This will use and/or modify the runtime data set. If the quit flag is set, the caller should terminate command execution.

(Commands: procedures)+≡

```

recursive subroutine command_execute (command, global)
    type(command_t), intent(inout) :: command
    type(rt_data_t), intent(inout), target :: global
    select case (command%type)
case (CMD_MODEL)
    call cmd_model_execute (command%model, global)
case (CMD_LIBRARY)
    call cmd_library_execute (command%library, global)
case (CMD_PROCESS)
    call cmd_process_execute (command%process, global)
case (CMD_COMPILE)
    call cmd_compile_execute (command%compile, global)
case (CMD_LOAD)
    call cmd_load_execute (command%load, global)
case (CMD_EXEC)
    call cmd_exec_execute (command%exec, global)
case (CMD_VAR)
    call cmd_var_execute (command%var, global)

```

```

case (CMD_SLHA)
    call cmd_slha_execute (command%slha, global)
case (CMD_SHOW)
    call cmd_show_execute (command%show, global)
case (CMD_EXPECT)
    call cmd_expect_execute (command%expect, global)
case (CMD_BEAMS)
    call cmd_beams_execute (command%beams, global)
case (CMD_BEAM_POLARIZATION)
    call cmd_beam_polarization_execute (command%beam_polarization, global)
case (CMD_CUTS)
    call cmd_cuts_execute (command%cuts, global)
case (CMD_SCALE)
    call cmd_scale_execute (command%scale, global)
case (CMD_FAC_SCALE)
    call cmd_fac_scale_execute (command%fac_scale, global)
case (CMD_REN_SCALE)
    call cmd_ren_scale_execute (command%ren_scale, global)
case (CMD_WEIGHT)
    call cmd_weight_execute (command%weight, global)
case (CMD_SELECTION)
    call cmd_selection_execute (command%selection, global)
case (CMD_REWEIGHT)
    call cmd_reweight_execute (command%reweight, global)
case (CMD_SEED)
    call cmd_seed_execute (command%seed, global)
case (CMD_ITERATIONS)
    call cmd_iterations_execute (command%iterations, global)
case (CMD_INTEGRATE)
    call cmd_integrate_execute (command%integrate, global)
case (CMD_ME_TEST)
    call cmd_me_test_execute (command%me_test, global)
case (CMD_OBSERVABLE)
    call cmd_observable_execute (command%observable, global)
case (CMD_HISTOGRAM)
    call cmd_histogram_execute (command%histogram, global)
case (CMD_PLOT)
    call cmd_plot_execute (command%plot, global)
case (CMD_GRAPH)
    call cmd_graph_execute (command%graph, global)
case (CMD_CLEAR)
    call cmd_clear_execute (command%clear, global)
case (CMD_RECORD)
    call cmd_record_execute (command%record, global)
case (CMD_ANALYSIS)
    call cmd_analysis_execute (command%analysis, global)
case (CMD_UNSTABLE)
    call cmd_unstable_execute (command%unstable, global)
case (CMD_STABLE)
    call cmd_stable_execute (command%stable, global)
case (CMD_POLARIZED, CMD_UNPOLARIZED)
    call cmd_un_polarized_execute &
        (command%un_polarized, command%type, global)
case (CMD_SAMPLE_FORMAT)

```

```

        call cmd_sample_format_execute (command%events, global)
case (CMD_SIMULATE)
    call cmd_simulate_execute (command%simulate, global)
case (CMD_RESCAN)
    call cmd_rescan_execute (command%rescan, global)
case (CMD_WRITE_ANALYSIS)
    call cmd_write_analysis_execute (command%write_analysis, global)
case (CMD_COMPILE_ANALYSIS)
    call cmd_compile_analysis_execute (command%compile_analysis, global)
case (CMD_HISTOGRAM_WRITER, CMD_PLOT_WRITER)
    call cmd_xxx_writer_execute (command%xxx_writer, global)
case (CMD_OPEN_OUT)
    call cmd_open_execute (command%open_out, global)
case (CMD_CLOSE_OUT)
    call cmd_close_execute (command%close_out, global)
case (CMD_PRINTD)
    call cmd_printd_execute (command%printd, global)
case (CMD_PRINTF)
    call cmd_printf_execute (command%printf, global)
case (CMD_SCAN)
    call cmd_scan_execute (command%loop, global)
case (CMD_IF)
    call cmd_if_execute (command%cond, global)
case (CMD_INCLUDE)
    call cmd_include_execute (command%include, global)
case (CMD_QUIT)
    call cmd_quit_execute (command%quit, global)
end select
end subroutine command_execute

```

Auxiliary for output:

```

<Commands: procedures>+≡
subroutine write_indent (unit, indent)
    integer, intent(in) :: unit
    integer, intent(in), optional :: indent
    if (present (indent)) then
        write (unit, "(A)", advance="no") repeat (" ", indent)
    end if
end subroutine write_indent

```

17.1.2 Specific command types

Model configuration

The command declares a model, looks for the specified file and loads it.

```

<Commands: types>+≡
type :: cmd_model_t
    private
    type(string_t) :: name
end type cmd_model_t

```

Output

```
(Commands: procedures)+≡
subroutine cmd_model_write (model, unit, indent)
  type(cmd_model_t), intent(in) :: model
  integer, intent(in), optional :: unit, indent
  integer :: u
  u = output_unit (unit); if (u < 0) return
  call write_indent (u, indent)
  write (u, "(1x,A,1x,'"',A,'\"') "model =", char (model%name)
end subroutine cmd_model_write
```

Compile. Get the model name and read the model from file, so it is readily available when the command list is executed.

```
(Commands: procedures)+≡
subroutine cmd_model_compile (model, pn, global)
  type(cmd_model_t), pointer :: model
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_name
  type(model_t), pointer :: mdl
  type(string_t) :: filename
  pn_name => parse_node_get_sub_ptr (pn, 3)
  allocate (model)
  if (associated (pn_name)) then
    model%name = parse_node_get_string (pn_name)
    filename = model%name // ".mdl"
    mdl => null ()
    call model_list_read_model (model%name, filename, global%os_data, mdl)
    if (associated (mdl)) then
      call var_list_init_copies &
        (global%var_list, model_get_var_list_ptr (mdl))
    end if
  else
    model%name = ""
  end if
end subroutine cmd_model_compile
```

Execute: Insert a pointer into the global data record and reassign the variable list.

```
(Commands: procedures)+≡
subroutine cmd_model_execute (model, global)
  type(cmd_model_t), intent(in) :: model
  type(rt_data_t), intent(inout), target :: global
  type(model_t), pointer :: mdl
  type(var_list_t), pointer :: model_vars
  if (model_get_name (global%model) /= model%name) then
    if (model_list_model_exists (model%name)) then
      mdl => model_list_get_model_ptr (model%name)
      global%model => mdl
      call var_list_set_string (global%var_list, var_str ("model_name"), &
        model%name, is_known=.true.)
      call msg_message ("Switching to model '" &
        // char (model_get_name (mdl)) &
```

```

        // ': reassigning model parameters")
        model_vars => model_get_var_list_ptr (mdl)
        call var_list_synchronize &
            (global%var_list, model_vars, reset_pointers = .true.)
    end if
else
    model_vars => model_get_var_list_ptr (global%model)
    call var_list_synchronize &
        (global%var_list, model_vars, reset_pointers = .false.)
    end if
end subroutine cmd_model_execute

```

Library configuration

We configure a process library that should hold the subsequently defined processes.

```

<Commands: types>+≡
    type :: cmd_library_t
    private
    type(string_t) :: name
end type cmd_library_t

```

Output.

```

<Commands: procedures>+≡
    subroutine cmd_library_write (library, unit, indent)
        type(cmd_library_t), intent(in) :: library
        integer, intent(in), optional :: unit, indent
        integer :: u
        u = output_unit (unit); if (u < 0) return
        call write_indent (u, indent)
        write (u, "(1x,A,1x,'"',A,'\"') "library =", char (library%name)
    end subroutine cmd_library_write

```

Compile. Get the library name.

```

<Commands: procedures>+≡
    subroutine cmd_library_compile (library, pn)
        type(cmd_library_t), pointer :: library
        type(parse_node_t), intent(in), target :: pn
        type(parse_node_t), pointer :: pn_name
        pn_name => parse_node_get_sub_ptr (pn, 3)
        allocate (library)
        library%name = parse_node_get_string (pn_name)
    end subroutine cmd_library_compile

```

Execute: Initialize a new library and append to the library store (if it does not yet exist). Try to load the library. Insert a pointer to the library into the global data record.

```

<Commands: procedures>+≡
    subroutine cmd_library_execute (library, global)
        type(cmd_library_t), intent(in) :: library

```

```

type(rt_data_t), intent(inout), target :: global
logical :: rebuild_library, recompile_library
rebuild_library = &
    var_list_get_lval (global%var_list, var_str ("?rebuild_library"))
recompile_library = &
    var_list_get_lval (global%var_list, var_str ("?recompile_library"))
if (.not. (rebuild_library .or. recompile_library .or. &
    associated (global%prc_lib))) then
    call load_library (library%name, global, global%var_list, global%prc_lib)
else
    call process_library_store_append &
        (library%name, global%os_data, global%prc_lib)
    call var_list_set_string (global%var_list, var_str ("$_library_name"), &
        process_library_get_name (global%prc_lib), is_known=.true.)
end if
end subroutine cmd_library_execute

```

Process configuration

We define a process-configuration command as a specific type. The incoming and outgoing particles are given evaluation-trees which we transform to PDG-code arrays. For transferring to O'MEGA, they are reconverted to strings.

This also includes the choice of method for the corresponding process: **omega** for O'MEGA matrix elements, **test** for special processes generated by WHIZARD, **external** for using an external matrix element and **dipole** for generating dipole subtraction terms.

(*Commands: types*) +=

```

type :: cmd_process_t
private
type(string_t) :: id
integer :: n_in = 0
integer :: n_out = 0
type(parse_node_p), dimension(:), allocatable :: pn_pdg_in
type(parse_node_p), dimension(:), allocatable :: pn_pdg_out
type(string_t), dimension(:), allocatable :: prt_in
type(string_t), dimension(:), allocatable :: prt_out
type(command_list_t), pointer :: options => null ()
type(rt_data_t) :: local
end type cmd_process_t

```

Finalize. The enclosed eval trees have to be deleted.

(*Commands: procedures*) +=

```

subroutine cmd_process_final (process)
type(cmd_process_t), intent(inout) :: process
if (allocated (process%pn_pdg_in)) then
    deallocate (process%pn_pdg_in)
end if
if (allocated (process%pn_pdg_out)) then
    deallocate (process%pn_pdg_out)
end if
if (associated (process%options)) then

```

```

        call command_list_final (process%options)
        deallocate (process%options)
    end if
end subroutine cmd_process_final

```

Compile.

```

(Commands: procedures) +=
subroutine cmd_process_compile (process, pn, global)
    type(cmd_process_t), pointer :: process
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_id, pn_in, pn_out, pn_codes, pn_opt
    integer :: i
    pn_id => parse_node_get_sub_ptr (pn, 2)
    pn_in  => parse_node_get_next_ptr (pn_id, 2)
    pn_out => parse_node_get_next_ptr (pn_in, 2)
    pn_opt => parse_node_get_next_ptr (pn_out)
    allocate (process)
    call rt_data_local_init (process%local, global)
    if (associated (pn_opt)) then
        allocate (process%options)
        call command_list_compile (process%options, pn_opt, process%local)
    end if
    process%id = parse_node_get_string (pn_id)
    call process_library_check_name_consistency (process%id, global%prc_lib)
    process%n_in  = parse_node_get_n_sub (pn_in)
    process%n_out = parse_node_get_n_sub (pn_out)
    pn_codes => parse_node_get_sub_ptr (pn_in)
    allocate (process%pn_pdg_in (process%n_in))
    allocate (process%pvt_in (process%n_in))
    do i = 1, process%n_in
        process%pn_pdg_in(i)%ptr => pn_codes
        process%pvt_in(i) = "?"
        pn_codes => parse_node_get_next_ptr (pn_codes)
    end do
    pn_codes => parse_node_get_sub_ptr (pn_out)
    allocate (process%pn_pdg_out (process%n_out))
    allocate (process%pvt_out (process%n_out))
    do i = 1, process%n_out
        process%pn_pdg_out(i)%ptr => pn_codes
        process%pvt_out(i) = "?"
        pn_codes => parse_node_get_next_ptr (pn_codes)
    end do
    call var_list_init_num_id (global%var_list, process%id)
    call rt_data_local_reset (process%local)
end subroutine cmd_process_compile

```

Command execution. Evaluate the subevents, transform PDG codes into strings, and add the current process configuration to the process library. If anything goes wrong in the particle code interpretation, the particle names will contain question marks. In that case, the process is not recorded.

```

(Commands: procedures) +=
subroutine cmd_process_execute (process, global)

```

```

type(cmd_process_t), intent(inout), target :: process
type(rt_data_t), intent(inout), target :: global
type(pdg_array_t) :: pdg_in, pdg_out
integer :: i, method
logical :: rebuild_library, omega_openmp
type(string_t) :: restrictions, omega_flags, method_str
call rt_data_link (process%local, global)
if (associated (process%options)) then
    call command_list_execute (process%options, process%local)
end if
if (process_library_is_static (global%prc_lib)) then
    call msg_error ("Process library '" &
        // char (process_library_get_name (global%prc_lib)) &
        // "' is static, no processes can be added")
    return
end if
do i = 1, size (process%pn_pdg_in)
    pdg_in = &
        eval_pdg_array (process%pn_pdg_in(i)%ptr, process%local%var_list)
    process%pvt_in(i) = make_flavor_string (pdg_in, process%local%model)
end do
do i = 1, size (process%pn_pdg_out)
    pdg_out = &
        eval_pdg_array (process%pn_pdg_out(i)%ptr, process%local%var_list)
    process%pvt_out(i) = make_flavor_string (pdg_out, process%local%model)
end do
restrictions = var_list_get_sval &
    (process%local%var_list, var_str ("restrictions"))
omega_flags = var_list_get_sval &
    (process%local%var_list, var_str ("omega_flags"))
method_str = var_list_get_sval &
    (process%local%var_list, var_str ("method"))
omega_openmp = var_list_get_lval &
    (process%local%var_list, var_str ("omega_openmp"))
method = method_of_string (method_str)
if (all (scan (process%pvt_in, "?") == 0) .and. &
    all (scan (process%pvt_out, "?") == 0)) then
    rebuild_library = var_list_get_lval &
        (process%local%var_list, var_str ("rebuild_library"))
    call process_library_append (global%prc_lib, &
        process%id, process%local%model, &
        process%pvt_in, process%pvt_out, &
        method = method, &
        restrictions = restrictions, omega_flags = omega_flags, &
        rebuild_library = rebuild_library, message = .true., &
        omega_openmp = omega_openmp)
else
    call msg_error ("Broken process declaration: skipped")
end if
call var_list_init_num_id (global%var_list, process%id)
call rt_data_restore (global, process%local)
end subroutine cmd_process_execute

```

This is a method of the eval tree, but cannot be coded inside the expressions

module since it uses the `model` and `flv` types which are not available there.

```

⟨Commands: procedures⟩+≡
function make_flavor_string (aval, model) result (prt)
  type(string_t) :: prt
  type(pdg_array_t), intent(in) :: aval
  type(model_t), intent(in), target :: model
  integer, dimension(:), allocatable :: pdg
  type(flavor_t), dimension(:), allocatable :: flv
  integer :: i
  pdg = aval
  allocate (flv (size (pdg)))
  call flavor_init (flv, pdg, model)
  if (size (pdg) /= 0) then
    prt = flavor_get_name (flv(1))
    do i = 2, size (flv)
      prt = prt // ":" // flavor_get_name (flv(i))
    end do
  else
    prt = "?"
  end if
end function make_flavor_string

```

Auxiliary function to convert the method string into an integer identifier.

```

⟨Commands: procedures⟩+≡
function method_of_string (meth_str) result (meth_id)
  type(string_t), intent(in) :: meth_str
  integer :: meth_id
  select case (char (meth_str))
  case ("omega")
    meth_id = PRC_OMEGA
  case ("test")
    meth_id = PRC_TEST
  case ("unit")
    meth_id = PRC_UNIT
  case ("external")
    meth_id = PRC_EXTERNAL
  case ("dipole")
    meth_id = PRC_DIPOLE
  case default
    call msg_fatal ("Invalid method for matrix elements.")
  end select
end function method_of_string

```

Process compilation

```

⟨Commands: types⟩+≡
type :: cmd_compile_t
  private
  type(string_t), dimension(:), allocatable :: libname
  logical :: make_executable = .false.
  type(string_t) :: exec_name
  type(command_list_t), pointer :: options => null ()

```

```

        type(rt_data_t) :: local
    end type cmd_compile_t

```

Finalize. Only options.

```

<Commands: procedures>+≡
    subroutine cmd_compile_final (compile)
        type(cmd_compile_t), intent(inout) :: compile
        if (associated (compile%options)) then
            call command_list_final (compile%options)
            deallocate (compile%options)
        end if
    end subroutine cmd_compile_final

```

Compile the libraries specified in the argument. If the argument is empty, compile all libraries which can be found in the process store.

```

<Commands: procedures>+≡
    subroutine cmd_compile_compile (compile, pn, global)
        type(cmd_compile_t), pointer :: compile
        type(parse_node_t), intent(in), target :: pn
        type(rt_data_t), intent(in), target :: global
        type(parse_node_t), pointer :: pn_cmd, pn_clause, pn_arg, pn_lib, pn_opt
        type(parse_node_t), pointer :: pn_exec_name_spec, pn_exec_name
        type(process_library_t), pointer :: prc_lib
        integer :: n_lib, i
        pn_cmd => parse_node_get_sub_ptr (pn)
        pn_clause => parse_node_get_sub_ptr (pn_cmd)
        pn_exec_name_spec => parse_node_get_sub_ptr (pn_clause, 2)
        if (associated (pn_exec_name_spec)) then
            pn_exec_name => parse_node_get_sub_ptr (pn_exec_name_spec, 2)
        else
            pn_exec_name => null ()
        end if
        pn_arg => parse_node_get_next_ptr (pn_clause)
        pn_opt => parse_node_get_next_ptr (pn_cmd)
        allocate (compile)
        call rt_data_local_init (compile%local, global)
        if (associated (pn_opt)) then
            allocate (compile%options)
            call command_list_compile (compile%options, pn_opt, compile%local)
        end if
        if (associated (pn_arg)) then
            n_lib = parse_node_get_n_sub (pn_arg)
        else
            n_lib = 0
        end if
        if (n_lib > 0) then
            allocate (compile%libname (n_lib))
            pn_lib => parse_node_get_sub_ptr (pn_arg)
            do i = 1, n_lib
                compile%libname(i) = parse_node_get_string (pn_lib)
                pn_lib => parse_node_get_next_ptr (pn_lib)
            end do
        else

```

```

n_lib = 0
prc_lib => process_library_store_get_first ()
do while (associated (prc_lib))
  n_lib = n_lib + 1
  call process_library_advance (prc_lib)
end do
allocate (compile%libname (n_lib))
i = 0
prc_lib => process_library_store_get_first ()
do while (associated (prc_lib))
  i = i + 1
  compile%libname(i) = process_library_get_name (prc_lib)
  call process_library_advance (prc_lib)
end do
end if
if (associated (pn_exec_name)) then
  compile%make_executable = .true.
  compile%exec_name = parse_node_get_string (pn_exec_name)
end if
call rt_data_local_reset (compile%local)
end subroutine cmd_compile_compile

```

Command execution. Generate code, write driver, compile and link. Do this for all libraries in the list which have a nonzero number of processes defined so far.

(Commands: procedures)+≡

```

subroutine cmd_compile_execute (compile, global)
  type(cmd_compile_t), intent(inout), target :: compile
  type(rt_data_t), intent(inout), target :: global
  call rt_data_link (compile%local, global)
  if (associated (compile%options)) then
    call command_list_execute (compile%options, compile%local)
  end if
  if (compile%make_executable) then
    call compile_executable &
      (compile%libname, compile%exec_name, compile%local)
  else
    call compile_library &
      (compile%libname, compile%local, global%var_list, global%prc_lib)
  end if
  call rt_data_restore (global, compile%local)
end subroutine cmd_compile_execute

```

Load library

For the most part, this is analogous to the compile command.

(Commands: types)+≡

```

type :: cmd_load_t
  private
  type(string_t), dimension(:), allocatable :: libname
  type(command_list_t), pointer :: options => null ()
  type(rt_data_t) :: local

```

```
end type cmd_load_t
```

Finalize. Only options.

<Commands: procedures>+≡

```
subroutine cmd_load_final (load)
  type(cmd_load_t), intent(inout) :: load
  if (associated (load%options)) then
    call command_list_final (load%options)
    deallocate (load%options)
  end if
end subroutine cmd_load_final
```

Compile the load command.

<Commands: procedures>+≡

```
subroutine cmd_load_compile (load, pn, global)
  type(cmd_load_t), pointer :: load
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(in), target :: global
  type(parse_node_t), pointer :: pn_arg, pn_lib, pn_opt
  type(process_library_t), pointer :: prc_lib
  integer :: n_lib, i
  pn_arg => parse_node_get_sub_ptr (pn, 2)
  allocate (load)
  if (associated (pn_arg)) then
    select case (char (parse_node_get_rule_key (pn_arg)))
    case ("load_arg")
      n_lib = parse_node_get_n_sub (pn_arg)
      pn_opt => parse_node_get_next_ptr (pn_arg)
    case default
      n_lib = 0
      pn_opt => pn_arg
    end select
  else
    n_lib = 0
    pn_opt => null ()
  end if
  call rt_data_local_init (load%local, global)
  if (associated (pn_opt)) then
    allocate (load%options)
    call command_list_compile (load%options, pn_opt, load%local)
  end if
  if (n_lib > 0) then
    allocate (load%libname (n_lib))
    pn_lib => parse_node_get_sub_ptr (pn_arg)
    do i = 1, n_lib
      load%libname(i) = parse_node_get_string (pn_lib)
      pn_lib => parse_node_get_next_ptr (pn_lib)
    end do
  else
    n_lib = 0
    prc_lib => process_library_store_get_first ()
    do while (associated (prc_lib))
      n_lib = n_lib + 1
    end do
  end if
end subroutine cmd_load_compile
```

```

        call process_library_advance (prc_lib)
    end do
    allocate (load%libname (n_lib))
    i = 0
    prc_lib => process_library_store_get_first ()
    do while (associated (prc_lib))
        i = i + 1
        load%libname(i) = process_library_get_name (prc_lib)
        call process_library_advance (prc_lib)
    end do
end if
call rt_data_local_reset (load%local)
end subroutine cmd_load_compile

```

Execute: Load the specified shared libraries. Insert a pointer to the last library in the list into the global record.

(Commands: procedures)+≡

```

subroutine cmd_load_execute (load, global)
    type(cmd_load_t), intent(inout) :: load
    type(rt_data_t), intent(inout), target :: global
    call rt_data_link (load%local, global)
    if (associated (load%options)) then
        call command_list_execute (load%options, load%local)
    end if
    call load_library &
        (load%libname, load%local, global%var_list, global%prc_lib)
    call rt_data_restore (global, load%local)
end subroutine cmd_load_execute

```

Execute a shell command

The argument is a string expression.

(Commands: types)+≡

```

type :: cmd_exec_t
    private
    type(parse_node_t), pointer :: pn_command => null ()
end type cmd_exec_t

```

Delete the eval tree.

(Commands: procedures)+≡

```

subroutine cmd_exec_final (exec)
    type(cmd_exec_t), intent(inout) :: exec
end subroutine cmd_exec_final

```

Compile the exec command.

(Commands: procedures)+≡

```

subroutine cmd_exec_compile (exec, pn, global)
    type(cmd_exec_t), pointer :: exec
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in), target :: global
    type(parse_node_t), pointer :: pn_arg, pn_command

```

```

pn_arg => parse_node_get_sub_ptr (pn, 2)
pn_command => parse_node_get_sub_ptr (pn_arg)
allocate (exec)
exec%pn_command => pn_command
end subroutine cmd_exec_compile

```

Execute the specified shell command.

```

⟨Commands: procedures⟩+≡
subroutine cmd_exec_execute (exec, global)
  type(cmd_exec_t), intent(inout) :: exec
  type(rt_data_t), intent(in) :: global
  type(string_t) :: command
  logical :: is_known
  integer :: status
  command = eval_string (exec%pn_command, global%var_list, is_known=is_known)
  if (is_known) then
    if (command /= "") then
      call os_system_call (command, status, verbose=.true.)
      if (status /= 0) then
        write (msg_buffer, "(A,I0)") "Return code = ", status
        call msg_message ()
        call msg_error ("System command returned with nonzero status code")
      end if
    end if
  end if
end subroutine cmd_exec_execute

```

Variable declaration

A variable can have various types. Hold the definition as an eval tree.

```

⟨Commands: types⟩+≡
type :: cmd_var_t
  private
  type(string_t) :: name
  integer :: type = V_NONE
  type(parse_node_t), pointer :: pn_value => null ()
  logical :: is_intrinsic = .false.
  logical :: is_copy = .false.
end type cmd_var_t

```

Delete the eval tree.

```

⟨Commands: procedures⟩+≡
subroutine cmd_var_final (var)
  type(cmd_var_t), intent(inout) :: var
end subroutine cmd_var_final

```

Compile the lhs and determine the variable name and type. Check whether this variable can be created or modified as requested, and append the value to the variable list, if appropriate. The value is initially undefined. The rhs is assigned to a pointer, to be compiled and evaluated when the command is executed.

```

⟨Commands: procedures⟩+≡

```

```

subroutine cmd_var_compile (var, pn, global)
  type(cmd_var_t), pointer :: var
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_var, pn_name
  type(parse_node_t), pointer :: pn_result, pn_proc
  type(string_t) :: var_name
  type(var_entry_t), pointer :: var_entry
  integer :: type
  logical :: new
  pn_result => null ()
  new = .false.
  allocate (var)
  select case (char (parse_node_get_rule_key (pn)))
  case ("cmd_log_decl");      type = V_LOG
    pn_var => parse_node_get_sub_ptr (pn, 2)
    if (.not. associated (pn_var)) then    ! handle masked syntax error
      var%type = V_NONE; return
    end if
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
    new = .true.
  case ("cmd_log");          type = V_LOG
    pn_name => parse_node_get_sub_ptr (pn, 2)
  case ("cmd_int");          type = V_INT
    pn_name => parse_node_get_sub_ptr (pn, 2)
    new = .true.
  case ("cmd_real");         type = V_REAL
    pn_name => parse_node_get_sub_ptr (pn, 2)
    new = .true.
  case ("cmd_complex");      type = V_CMPLX
    pn_name => parse_node_get_sub_ptr (pn, 2)
    new = .true.
  case ("cmd_num");          type = V_NONE
    pn_name => parse_node_get_sub_ptr (pn)
  case ("cmd_string_decl"); type = V_STR
    pn_var => parse_node_get_sub_ptr (pn, 2)
    if (.not. associated (pn_var)) then    ! handle masked syntax error
      var%type = V_NONE; return
    end if
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
    new = .true.
  case ("cmd_string");       type = V_STR
    pn_name => parse_node_get_sub_ptr (pn, 2)
  case ("cmd_alias");        type = V_PDG
    pn_name => parse_node_get_sub_ptr (pn, 2)
    new = .true.
  case ("cmd_result");       type = V_REAL
    pn_name => parse_node_get_sub_ptr (pn)
    pn_result => parse_node_get_sub_ptr (pn_name)
    pn_proc => parse_node_get_next_ptr (pn_result)
  case default
    call parse_node_mismatch &
      ("logical|int|real|complex|?|?$|alias|var_name", pn) ! $
  end select
end subroutine

```

```

if (.not. associated (pn_name)) then    ! handle masked syntax error
    var%type = V_NONE; return
end if
if (.not. associated (pn_result)) then
    var_name = parse_node_get_string (pn_name)
else
    var_name = parse_node_get_key (pn_result) &
        // "(" // parse_node_get_string (pn_proc) // ")"
end if
select case (type)
case (V_LOG);  var_name = "?" // var_name
case (V_STR);  var_name = "$" // var_name    ! $
end select
call var_list_check_user_var (global%var_list, var_name, type, new)
var%type = type
var%name = var_name
var_entry => var_list_get_var_ptr &
    (global%var_list, var%name, var%type, follow_link=.false.)
var%pn_value => parse_node_get_next_ptr (pn_name, 2)
if (.not. associated (var%pn_value)) var%type = V_NONE
if (associated (var_entry)) then
    var%is_copy = var_entry_is_copy (var_entry)
else
    var_entry => var_list_get_var_ptr &
        (global%var_list, var%name, var%type, follow_link=.true.)
    if (associated (var_entry)) then
        var%is_intrinsic = var_entry_is_intrinsic (var_entry)
        if (var_entry_is_copy (var_entry)) then
            var%is_copy = .true.
            call var_list_init_copy (global%var_list, var_entry, user=.true.)
        end if
    end if
end if
if (.not. var%is_copy) then
    select case (var%type)
    case (V_LOG)
        call var_list_append_log (global%var_list, var%name, &
            intrinsic=var%is_intrinsic, user=.true.)
    case (V_INT)
        call var_list_append_int (global%var_list, var%name, &
            intrinsic=var%is_intrinsic, user=.true.)
    case (V_REAL)
        call var_list_append_real (global%var_list, var%name, &
            intrinsic=var%is_intrinsic, user=.true.)
    case (V_CMPLX)
        call var_list_append_cmplx (global%var_list, var%name, &
            intrinsic=var%is_intrinsic, user=.true.)
    case (V_PDG)
        call var_list_append_pdg_array (global%var_list, var%name, &
            intrinsic=var%is_intrinsic, user=.true.)
    case (V_STR)
        call var_list_append_string (global%var_list, var%name, &
            intrinsic=var%is_intrinsic, user=.true.)
    end select
end if

```



```

        end if
    end subroutine cmd_var_compile

```

Execute. Evaluate the definition and assign the variable value. If the variable is a copy, the original is a model variable. The original is set automatically, and an update of the dependent parameters is in order.

```

<Commands: procedures>+≡
subroutine cmd_var_execute (var, global)
    type(cmd_var_t), intent(inout), target :: var
    type(rt_data_t), intent(inout), target :: global
    type(string_t) :: model_name
    type(var_list_t), pointer :: model_vars
    if (associated (global%model)) then
        model_name = model_get_name (global%model)
        model_vars => model_get_var_list_ptr (global%model)
        if (var%is_copy) then
            call var_list_set_original_pointer (global%var_list, var%name, &
                model_vars)
        end if
        call cmd_var_set_value (var, global%var_list, &
            verbose=.true., model_name=model_name)
        if (var%is_copy) then
            call model_parameters_update (global%model)
            call var_list_synchronize (global%var_list, model_vars)
        end if
    else
        call cmd_var_set_value (var, global%var_list, verbose=.true.)
    end if
end subroutine cmd_var_execute

```

Copy the value to the variable list, where the variable should already exist.

```

<Commands: procedures>+≡
subroutine cmd_var_set_value (var, var_list, verbose, model_name)
    type(cmd_var_t), intent(inout), target :: var
    type(var_list_t), intent(inout), target :: var_list
    logical, intent(in), optional :: verbose
    type(string_t), intent(in), optional :: model_name
    logical :: lval
    integer :: ival
    real(default) :: rval
    complex(default) :: cval
    type(pdg_array_t) :: aval
    type(string_t) :: sval
    logical :: is_known
    select case (var%type)
    case (V_LOG)
        lval = eval_log (var%pn_value, var_list, is_known=is_known)
        call var_list_set_log (var_list, var%name, &
            lval, is_known, verbose=verbose, model_name=model_name)
    case (V_INT)
        ival = eval_int (var%pn_value, var_list, is_known=is_known)
        call var_list_set_int (var_list, var%name, &
            ival, is_known, verbose=verbose, model_name=model_name)

```

```

case (V_REAL)
  rval = eval_real (var%pn_value, var_list, is_known=is_known)
  call var_list_set_real (var_list, var%name, &
    rval, is_known, verbose=verbose, model_name=model_name)
case (V_CMPLX)
  cval = eval_cmplx (var%pn_value, var_list, is_known=is_known)
  call var_list_set_cmplx (var_list, var%name, &
    cval, is_known, verbose=verbose, model_name=model_name)
case (V_PDG)
  aval = eval_pdg_array (var%pn_value, var_list, is_known=is_known)
  call var_list_set_pdg_array (var_list, var%name, &
    aval, is_known, verbose=verbose, model_name=model_name)
case (V_STR)
  sval = eval_string (var%pn_value, var_list, is_known=is_known)
  call var_list_set_string (var_list, var%name, &
    sval, is_known, verbose=verbose, model_name=model_name)
end select
end subroutine cmd_var_set_value

```

SLHA

Read a SLHA (SUSY Les Houches Accord) file to fill the appropriate model parameters. We do not access the current variable record, but directly work on the appropriate SUSY model, which is loaded if necessary.

We may be in read or write mode. In the latter case, we may write just input parameters, or the complete spectrum, or the spectrum with all decays.

<Commands: types>+≡

```

type :: cmd_slha_t
  private
  type(string_t) :: file
  logical :: write = .false.
  type(command_list_t), pointer :: options => null ()
  type(rt_data_t) :: local
end type cmd_slha_t

```

Finalizer.

<Commands: procedures>+≡

```

subroutine cmd_slha_final (slha)
  type(cmd_slha_t), intent(inout) :: slha
  if (associated (slha%options)) then
    call command_list_final (slha%options)
    deallocate (slha%options)
  end if
end subroutine cmd_slha_final

```

Compile. Read the filename and store it.

<Commands: procedures>+≡

```

subroutine cmd_slha_compile (slha, pn, global)
  type(cmd_slha_t), pointer :: slha
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(in), target :: global

```

```

type(parse_node_t), pointer :: pn_key, pn_arg, pn_file
type(parse_node_t), pointer :: pn_opt
pn_key => parse_node_get_sub_ptr (pn)
pn_arg => parse_node_get_next_ptr (pn_key)
pn_file => parse_node_get_sub_ptr (pn_arg)
pn_opt => parse_node_get_next_ptr (pn_arg)
allocate (slha)
call rt_data_local_init (slha%local, global)
if (associated (pn_opt)) then
  allocate (slha%options)
  call command_list_compile (slha%options, pn_opt, slha%local)
end if
select case (char (parse_node_get_key (pn_key)))
case ("read_slha")
  slha%write = .false.
case ("write_slha")
  slha%write = .true.
case default
  call parse_node_mismatch ("read_slha|write_slha", pn)
end select
slha%file = parse_node_get_string (pn_file)
call rt_data_local_reset (slha%local)
end subroutine cmd_slha_compile

```

Execute. Read or write the specified SLHA file.

(Commands: procedures)+≡

```

subroutine cmd_slha_execute (slha, global)
type(cmd_slha_t), intent(inout), target :: slha
type(rt_data_t), intent(inout), target :: global
logical :: input, spectrum, decays
call rt_data_link (slha%local, global)
if (associated (slha%options)) then
  call command_list_execute (slha%options, slha%local)
end if
if (slha%write) then
  input = .true.
  spectrum = .false.
  decays = .false.
  call slha_write_file &
    (slha%file, slha%local%model, &
     input = input, spectrum = spectrum, decays = decays)
else
  input = var_list_get_lval (slha%local%var_list, &
    var_str ("?slha_read_input"))
  spectrum = var_list_get_lval (slha%local%var_list, &
    var_str ("?slha_read_spectrum"))
  decays = var_list_get_lval (slha%local%var_list, &
    var_str ("?slha_read_decays"))
  call slha_read_file &
    (slha%file, slha%local%os_data, slha%local%model, &
     input = input, spectrum = spectrum, decays = decays)
end if
call rt_data_restore (global, slha%local, keep_model_vars = .true.)
end subroutine cmd_slha_execute

```

Show values of variables

(Commands: types)+≡

```
type :: cmd_show_t
  private
  type(string_t), dimension(:), allocatable :: name
  type(parse_node_p), dimension(:), allocatable :: pn_expr
  type(var_entry_t), dimension(:), allocatable :: value
end type cmd_show_t
```

Finalize.

(Commands: procedures)+≡

```
subroutine cmd_show_final (show)
  type(cmd_show_t), intent(inout) :: show
  integer :: i
  if (allocated (show%pn_expr)) then
    deallocate (show%pn_expr)
  end if
  if (allocated (show%value)) then
    do i = 1, size (show%value)
      call var_entry_final (show%value(i))
    end do
  end if
end subroutine cmd_show_final
```

Compile. Allocate an array which is filled with the names of the variables to show.

(Commands: procedures)+≡

```
subroutine cmd_show_compile (show, pn, global)
  type(cmd_show_t), pointer :: show
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(in), target :: global
  type(parse_node_t), pointer :: pn_arg, pn_var, pn_prefix, pn_name
  type(string_t) :: key
  integer :: i, n_args
  pn_arg => parse_node_get_sub_ptr (pn, 2)
  allocate (show)
  if (associated (pn_arg)) then
    n_args = parse_node_get_n_sub (pn_arg)
    allocate (show%name (n_args))
    allocate (show%pn_expr (n_args))
    allocate (show%value (n_args))
    pn_var => parse_node_get_sub_ptr (pn_arg)
    i = 0
    do while (associated (pn_var))
      i = i + 1
      select case (char (parse_node_get_rule_key (pn_var)))
        case ("model", "beams", "results", "unstable", &
              "real", "int", "intrinsic", &
              "cuts", "scale", "factorization_scale", &
```

```

        "renormalization_scale", "weight", &
        "selection", "reweight", "analysis", "expect")
    show%name(i) = parse_node_get_key (pn_var)
case ("library_spec")
    pn_prefix => parse_node_get_sub_ptr (pn_var)
    pn_name => parse_node_get_next_ptr (pn_prefix)
    key = parse_node_get_key (pn_prefix)
    if (associated (pn_name)) then
        show%name(i) = "L " // parse_node_get_string (pn_name)
    else
        show%name(i) = key
    end if
case ("result_var")
    pn_prefix => parse_node_get_sub_ptr (pn_var)
    pn_name => parse_node_get_next_ptr (pn_prefix)
    if (associated (pn_name)) then
        show%name(i) = parse_node_get_key (pn_prefix) &
            // "(" // parse_node_get_string (pn_name) // ")"
    else
        show%name(i) = parse_node_get_key (pn_prefix)
    end if
case ("log_var", "alias_var", "string_var")
    pn_prefix => parse_node_get_sub_ptr (pn_var)
    pn_name => parse_node_get_next_ptr (pn_prefix)
    key = parse_node_get_key (pn_prefix)
    if (associated (pn_name)) then
        select case (char (parse_node_get_rule_key (pn_name)))
        case ("variable")
            select case (char (key))
            case ("?", "$") ! $ sign
                show%name(i) = key // parse_node_get_string (pn_name)
            case ("alias")
                show%name(i) = "A " // parse_node_get_string (pn_name)
            case ("library")
                show%name(i) = "L " // parse_node_get_string (pn_name)
            end select
        case ("lexpr")
            show%name(i) = "<lexpr>"
            show%pn_expr(i)%ptr => pn_name
        case ("cexpr")
            show%name(i) = "<cexpr>"
            show%pn_expr(i)%ptr => pn_name
        case ("sexpr")
            show%name(i) = "<sexpr>"
            show%pn_expr(i)%ptr => pn_name
        case default
            call parse_node_mismatch &
                ("variable|expr|lexpr|cexpr|sexpr", pn_name)
        end select
    else
        show%name(i) = key
    end if
case ("num_var")
    pn_name => parse_node_get_sub_ptr (pn_var)

```

```

        if (associated (pn_name)) then
            select case (char (parse_node_get_rule_key (pn_name)))
            case ("variable")
                show%name(i) = parse_node_get_string (pn_name)
            case ("expr")
                show%name(i) = "<expr>"
                show%pn_expr(i)%ptr => pn_name
            case default
                call parse_node_mismatch &
                    ("variable|expr", pn_name)
            end select
        else
            show%name(i) = key
        end if
    case default
        pn_prefix => null ()
        pn_name => parse_node_get_sub_ptr (pn_var)
        if (associated (pn_name)) then
            show%name(i) = parse_node_get_string (pn_name)
        else
            show%name(i) = ""
        end if
    end select
    pn_var => parse_node_get_next_ptr (pn_var)
end do
else
    allocate (show%name (0))
end if
end subroutine cmd_show_compile

```

Execute. Scan the list of variables to show. Special cases of an empty list (show all) and keywords int, real, alias have to be handled as well.

(Commands: procedures)+≡

```

subroutine cmd_show_execute (show, global)
    type(cmd_show_t), intent(inout) :: show
    type(rt_data_t), intent(in), target :: global
    type(string_t) :: name
    type(process_library_t), pointer :: prc_lib
    logical :: lval
    integer :: ival
    real(default) :: rval
    complex(default) :: cval
    type(pdg_array_t) :: aval
    type(string_t) :: sval
    logical :: is_known
    integer :: result_type
    integer :: i, u
    u = logfile_unit ()
    if (size (show%name) == 0) then
        call var_list_write (global%var_list)
    else
        if (associated (global%model)) then
            name = model_get_name (global%model)

```

```

else
    name = "[undefined]"
end if
do i = 1, size (show%name)
    select case (char (show%name(i)))
    case ("model")
        print *, "model* = ", char (name)
        write (u, *) "model* = ", char (name)
    case ("library")
        if (associated (global%prc_lib)) then
            call process_library_write (global%prc_lib)
            call process_library_write (global%prc_lib, unit=u)
        else
            call msg_message ("Show library: no library is loaded")
        end if
    case ("beams")
        call beam_data_write (global%beam_data)
        call beam_data_write (global%beam_data, unit=u)
    case ("results")
        call process_store_write_results ()
        call process_store_write_results (unit=u)
    case ("unstable")
        call decay_store_write ()
        call decay_store_write (unit=u)
    case ("cuts")
        if (associated (global%pn_cuts_lexpr)) then
            call parse_node_write_rec (global%pn_cuts_lexpr)
            call parse_node_write_rec (global%pn_cuts_lexpr, u)
        else
            call msg_message ("No cut expression defined")
        end if
    case ("weight")
        if (associated (global%pn_weight_lexpr)) then
            call parse_node_write_rec (global%pn_weight_lexpr)
            call parse_node_write_rec (global%pn_weight_lexpr, u)
        else
            call msg_message ("No weight expression defined")
        end if
    case ("scale")
        if (associated (global%pn_scale_lexpr)) then
            call parse_node_write_rec (global%pn_scale_lexpr)
            call parse_node_write_rec (global%pn_scale_lexpr, u)
        else
            call msg_message ("No general scale expression defined")
        end if
    case ("factorization_scale")
        if (associated (global%pn_fac_scale_lexpr)) then
            call parse_node_write_rec (global%pn_fac_scale_lexpr)
            call parse_node_write_rec (global%pn_fac_scale_lexpr, u)
            call msg_message ("Factorization scale expression superseding scale defintion.")
        else
            call msg_message ("No factorization scale expression defined")
        end if
    case ("renormalization_scale")

```

```

    if (associated (global%pn_ren_scale_expr)) then
        call parse_node_write_rec (global%pn_ren_scale_expr)
        call parse_node_write_rec (global%pn_ren_scale_expr,u)
        call msg_message ("Renormalization scale expression superseding scale defintion.")
    else
        call msg_message ("No renormalization scale expression defined")
    end if
case ("analysis")
    if (associated (global%pn_analysis_lexpr)) then
        call parse_node_write_rec (global%pn_analysis_lexpr)
        call parse_node_write_rec (global%pn_analysis_lexpr, u)
    else
        call msg_message ("No cut expression defined")
    end if
case ("expect")
    call expect_summary ()
case ("?")
    if (associated (global%model)) then
        call var_list_write (global%var_list, only_type=V_LOG, &
            model_name = name)
        call var_list_write (global%var_list, only_type=V_LOG, &
            model_name = name, unit=u)
    else
        call var_list_write (global%var_list, only_type=V_LOG)
        call var_list_write (global%var_list, only_type=V_LOG, unit=u)
    end if
case ("intrinsic")
    if (associated (global%model)) then
        call var_list_write (global%var_list, intrinsic=.true., &
            model_name = name)
        call var_list_write (global%var_list, intrinsic=.true., &
            model_name = name, unit=u)
    else
        call var_list_write (global%var_list, intrinsic=.true.)
        call var_list_write (global%var_list, intrinsic=.true., unit=u)
    end if
case ("int")
    if (associated (global%model)) then
        call var_list_write (global%var_list, only_type=V_INT, &
            model_name = name)
        call var_list_write (global%var_list, only_type=V_INT, &
            model_name = name, unit=u)
    else
        call var_list_write (global%var_list, only_type=V_INT)
        call var_list_write (global%var_list, only_type=V_INT, unit=u)
    end if
case ("real")
    if (associated (global%model)) then
        call var_list_write (global%var_list, only_type=V_REAL, &
            model_name = name)
        call var_list_write (global%var_list, only_type=V_REAL, &
            model_name = name, unit=u)
    else
        call var_list_write (global%var_list, only_type=V_REAL)

```



```

        call var_list_write (global%var_list, only_type=V_REAL, unit=u)
    end if
case ("complex")
    if (associated (global%model)) then
        call var_list_write (global%var_list, only_type=V_CMPLX, &
            model_name = name)
        call var_list_write (global%var_list, only_type=V_CMPLX, &
            model_name = name, unit=u)
    else
        call var_list_write (global%var_list, only_type=V_CMPLX)
        call var_list_write (global%var_list, only_type=V_CMPLX, unit=u)
    end if
case ("alias")
    if (associated (global%model)) then
        call var_list_write (global%var_list, only_type=V_PDG, &
            model_name = name)
        call var_list_write (global%var_list, only_type=V_PDG, &
            model_name = name, unit=u)
    else
        call var_list_write (global%var_list, only_type=V_PDG)
        call var_list_write (global%var_list, only_type=V_PDG, unit=u)
    end if
case ("$$") !$ sign
    if (associated (global%model)) then
        call var_list_write (global%var_list, only_type=V_STR, &
            model_name = name)
        call var_list_write (global%var_list, only_type=V_STR, &
            model_name = name, unit=u)
    else
        call var_list_write (global%var_list, only_type=V_STR)
        call var_list_write (global%var_list, only_type=V_STR, unit=u)
    end if
case ("n_calls", "num_id", &
    "integral", "error", "accuracy", "chi2", "efficiency")
    call var_list_write (global%var_list, prefix=char(show%name(i)))
    call var_list_write (global%var_list, prefix=char(show%name(i)), &
        unit=u)
case ("<lexpr>")
    lval = eval_log (show%pn_expr(i)%ptr, global%var_list, &
        is_known=is_known)
    if (is_known) then
        call var_entry_init_log (show%value(i), &
            var_str ("logical value"), lval)
    else
        call var_entry_init_log (show%value(i), &
            var_str ("logical value"))
    end if
    call var_entry_write (show%value(i))
    call var_entry_write (show%value(i), unit=u)
case ("<expr>")
    call eval_numeric (show%pn_expr(i)%ptr, global%var_list, &
        ival=ival, rval=rval, cval=cval, &
        is_known=is_known, result_type=result_type)
    select case (result_type)

```

```

case (V_INT)
  if (is_known) then
    call var_entry_init_int (show%value(i), &
      var_str ("integer value"), ival)
  else
    call var_entry_init_int (show%value(i), &
      var_str ("integer value"))
  end if
case (V_REAL)
  if (is_known) then
    call var_entry_init_real (show%value(i), &
      var_str ("real value"), rval)
  else
    call var_entry_init_real (show%value(i), &
      var_str ("real value"))
  end if
case (V_CMPLX)
  if (is_known) then
    call var_entry_init_cmplx (show%value(i), &
      var_str ("complex value"), cval)
  else
    call var_entry_init_cmplx (show%value(i), &
      var_str ("complex value"))
  end if
end select
call var_entry_write (show%value(i))
call var_entry_write (show%value(i), unit=u)
case ("<cexpr>")
  aval = eval_pdg_array (show%pn_expr(i)%ptr, global%var_list, &
    is_known=is_known)
  if (is_known) then
    call var_entry_init_pdg_array (show%value(i), &
      var_str ("alias value"), aval)
  else
    call var_entry_init_pdg_array (show%value(i), &
      var_str ("alias value"))
  end if
  call var_entry_write (show%value(i))
  call var_entry_write (show%value(i), unit=u)
case ("<sexpr>")
  sval = eval_string (show%pn_expr(i)%ptr, global%var_list, &
    is_known=is_known)
  if (is_known) then
    call var_entry_init_string (show%value(i), &
      var_str ("string value"), sval)
  else
    call var_entry_init_string (show%value(i), &
      var_str ("string value"))
  end if
  call var_entry_write (show%value(i))
  call var_entry_write (show%value(i), unit=u)
case default
  select case (char (extract (show%name(i), 1, 2)))
  case ("L ")

```

```

        name = extract (show%name(i), 3)
        prc_lib => process_library_store_get_ptr (name)
        if (associated (prc_lib)) then
            call process_library_write (prc_lib)
            call process_library_write (prc_lib, unit=u)
        else
            call msg_message ("Library '" // char (name) &
                // "' not loaded")
        end if
    case ("A ")
        name = extract (show%name(i), 3)
        call var_list_write_var (global%var_list, name, &
            model_name = name, type = V_PDG)
        call var_list_write_var (global%var_list, name, &
            model_name = name, type = V_PDG, unit=u)
    case default
        if (associated (global%model)) then
            call var_list_write_var (global%var_list, show%name(i), &
                model_name = name)
            call var_list_write_var (global%var_list, show%name(i), &
                model_name = name, unit=u)
        else
            call var_list_write_var (global%var_list, show%name(i))
            call var_list_write_var (global%var_list, show%name(i), &
                unit=u)
        end if
    end select
end select
end do
end if
flush (u)
end subroutine cmd_show_execute

```

Compare values of variables to expectation

The implementation is similar to the `show` command. There are just two arguments: two values that should be compared. For providing local values for the numerical tolerance, the command has a local argument list.

If the expectation fails, an error condition is recorded.

```

<Commands: types>+≡
    type :: cmd_expect_t
    private
    type(parse_node_t), pointer :: pn_lexpr => null ()
    type(command_list_t), pointer :: options => null ()
    type(rt_data_t) :: local
end type cmd_expect_t

```

Finalize.

```

<Commands: procedures>+≡
    subroutine cmd_expect_final (expect)
        type(cmd_expect_t), intent(inout) :: expect
        if (associated (expect%options)) then

```

```

        call command_list_final (expect%options)
        deallocate (expect%options)
    end if
end subroutine cmd_expect_final

```

Compile. This merely assigns the parse node, the actual compilation is done at execution. This is necessary because the origin of variables (local/global) may change during execution.

(Commands: procedures)+≡

```

subroutine cmd_expect_compile (expect, pn, global)
    type(cmd_expect_t), pointer :: expect
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in), target :: global
    type(parse_node_t), pointer :: pn_arg, pn_opt
    pn_arg => parse_node_get_sub_ptr (pn, 2)
    pn_opt => parse_node_get_next_ptr (pn_arg)
    allocate (expect)
    call rt_data_local_init (expect%local, global)
    if (associated (pn_opt)) then
        allocate (expect%options)
        call command_list_compile (expect%options, pn_opt, expect%local)
    end if
    expect%pn_lexpr => parse_node_get_sub_ptr (pn_arg)
    call rt_data_local_reset (expect%local)
end subroutine cmd_expect_compile

```

Execute. Evaluate both arguments, print them and their difference (if numerical), and whether they agree. Record the result.

(Commands: procedures)+≡

```

subroutine cmd_expect_execute (expect, global)
    type(cmd_expect_t), intent(inout) :: expect
    type(rt_data_t), intent(inout), target :: global
    logical :: success, is_known
    integer :: u
    u = logfile_unit ()
    call rt_data_link (expect%local, global)
    if (associated (expect%options)) then
        call command_list_execute (expect%options, expect%local)
    end if
    success = &
        eval_log (expect%pn_lexpr, expect%local%var_list, is_known=is_known)
    if (is_known) then
        if (success) then
            call msg_message ("expect: success")
        else
            call msg_error ("expect: failure")
        end if
    else
        call msg_error ("expect: undefined result")
        success = .false.
    end if
    call expect_record (success)
    call rt_data_restore (global, expect%local)

```

```
end subroutine cmd_expect_execute
```

Beams

The beam command includes both beam and structure-function definition. To hold the structure functions, we define two special container types.

(Commands: types)+≡

```
type :: strfun_def_t
  private
  integer :: type = STRF_NONE
  type(command_list_t), pointer :: options => null ()
  type(parse_node_t), pointer :: pn_user_name => null ()
  type(rt_data_t) :: local
end type strfun_def_t

type :: strfun_pair_t
  private
  integer :: n
  type(strfun_def_t), dimension(2) :: def
end type strfun_pair_t

type :: cmd_beams_t
  private
  integer :: n_in = 0
  type(parse_node_p), dimension(:), allocatable :: pn_pdg
  type(string_t), dimension(:), allocatable :: prt
  type(command_list_t), pointer :: options => null ()
  type(rt_data_t) :: local
  integer :: n_strfun = 0
  type(strfun_pair_t), dimension(:), allocatable :: strfun_pair
end type cmd_beams_t
```

Delete the eval trees.

(Commands: procedures)+≡

```
subroutine cmd_beams_final (beams)
  type(cmd_beams_t), intent(inout) :: beams
  if (allocated (beams%pn_pdg)) then
    deallocate (beams%pn_pdg)
  end if
  if (associated (beams%options)) then
    call command_list_final (beams%options)
    deallocate (beams%options)
  end if
end subroutine cmd_beams_final
```

Compile.

(Commands: procedures)+≡

```
subroutine cmd_beams_compile (beams, pn, global)
  type(cmd_beams_t), pointer :: beams
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(in), target :: global
```

```

type(parse_node_t), pointer :: pn_beam_def, pn_beam_spec
type(parse_node_t), pointer :: pn_beam_list, pn_opt
type(parse_node_t), pointer :: pn_codes
type(parse_node_t), pointer :: pn_strfun_seq, pn_strfun_pair
integer :: i
pn_beam_def => parse_node_get_sub_ptr (pn, 3)
pn_beam_spec => parse_node_get_sub_ptr (pn_beam_def)
pn_strfun_seq => parse_node_get_next_ptr (pn_beam_spec)
pn_beam_list => parse_node_get_sub_ptr (pn_beam_spec)
pn_opt => parse_node_get_next_ptr (pn_beam_list)
allocate (beams)
call rt_data_local_init (beams%local, global, CMD_BEAMS)
if (associated (pn_opt)) then
    allocate (beams%options)
    call command_list_compile (beams%options, pn_opt, beams%local)
end if
beams%n_in = parse_node_get_n_sub (pn_beam_list)
select case (beams%n_in)
case (1)
    if (associated (pn_strfun_seq)) then
        call parse_node_write (pn_beam_def)
        call msg_error ("Structure functions can't be defined " &
            // "for decay processes")
        pn_strfun_seq => null ()
    end if
end select
allocate (beams%pn_pdg (beams%n_in))
allocate (beams%prt (beams%n_in))
pn_codes => parse_node_get_sub_ptr (pn_beam_list)
do i = 1, beams%n_in
    beams%pn_pdg(i)%ptr => pn_codes
    beams%prt(i) = "?"
    pn_codes => parse_node_get_next_ptr (pn_codes)
end do
if (associated (pn_strfun_seq)) then
    beams%n_strfun = parse_node_get_n_sub (pn_beam_def) - 1
    allocate (beams%strfun_pair (beams%n_strfun))
    do i = 1, beams%n_strfun
        pn_strfun_pair => parse_node_get_sub_ptr (pn_strfun_seq, 2)
        call strfun_pair_compile &
            (beams%strfun_pair(i), pn_strfun_pair, beams%local)
        pn_strfun_seq => parse_node_get_next_ptr (pn_strfun_seq)
    end do
end if
call rt_data_local_reset (beams%local)
end subroutine cmd_beams_compile

subroutine strfun_pair_compile (strfun_pair, pn_strfun_pair, global)
type(strfun_pair_t), intent(out) :: strfun_pair
type(parse_node_t), intent(in), target :: pn_strfun_pair
type(rt_data_t), intent(in), target :: global
type(parse_node_t), pointer :: pn_strfun_def
integer :: i
strfun_pair%n = parse_node_get_n_sub (pn_strfun_pair)

```

```

pn_strfun_def => parse_node_get_sub_ptr (pn_strfun_pair)
do i = 1, strfun_pair%n
    call strfun_def_compile (strfun_pair%def(i), pn_strfun_def, global)
    pn_strfun_def => parse_node_get_next_ptr (pn_strfun_def)
end do
end subroutine strfun_pair_compile

subroutine strfun_def_compile (strfun_def, pn_strfun_def, global)
    type(strfun_def_t), intent(out) :: strfun_def
    type(parse_node_t), intent(in), target :: pn_strfun_def
    type(rt_data_t), intent(in), target :: global
    type(parse_node_t), pointer :: pn_key, pn_opt, pn_arg
    pn_key => parse_node_get_sub_ptr (pn_strfun_def)
    pn_opt => parse_node_get_next_ptr (pn_key)
    select case (char (parse_node_get_rule_key (pn_key)))
    case ("none")
        strfun_def%type = STRF_NONE
    case ("lhapdf")
        strfun_def%type = STRF_LHAPDF
    case ("pdf_builtin")
        strfun_def%type = STRF_PDF_BUILTIN
    case ("isr")
        strfun_def%type = STRF_ISR
    case ("epa")
        strfun_def%type = STRF_EPA
    case ("ewa")
        strfun_def%type = STRF_EWA
    case ("circe1")
        strfun_def%type = STRF_CIRCE1
    case ("circe2")
        strfun_def%type = STRF_CIRCE2
    case ("energy_scan")
        strfun_def%type = STRF_ESCAN
    case ("beam_events")
        strfun_def%type = STRF_BEVT
    case ("user_sf_spec")
        strfun_def%type = STRF_USER
        pn_arg => parse_node_get_sub_ptr (pn_key, 2)
        strfun_def%pn_user_name => parse_node_get_sub_ptr (pn_arg)
    end select
    call rt_data_local_init (strfun_def%local, global)
    if (associated (pn_opt)) then
        allocate (strfun_def%options)
        call command_list_compile &
            (strfun_def%options, pn_opt, strfun_def%local)
    end if
    call rt_data_local_reset (strfun_def%local)
end subroutine strfun_def_compile

```

Command execution: Beam initialization. The output is a beam-data object, which is copied to the global data block.

Structure functions are configured in the option section. They are linked to the global data block, where they can be found by the integration command.

{Commands: procedures}+≡

```

subroutine cmd_beams_execute (beams, global)
  type(cmd_beams_t), intent(inout), target :: beams
  type(rt_data_t), intent(inout), target :: global
  logical, dimension(2) :: p_known
  real(default), dimension(2) :: p
  logical :: sqrts_known, alpha_known, theta_known, phi_known
  real(default) :: sqrts, alpha, theta, phi
  real(default) :: beams_theta, beams_phi
  type(pdg_array_t), dimension(2) :: aval
  type(flavor_t), dimension(:), allocatable :: flv_tmp
  type(flavor_t), dimension(2) :: flv
  type(beam_polarization_t), dimension(2) :: bp
  type(polarization_t), dimension(2) :: pol
  integer :: i, u
  logical :: polarized
  u = logfile_unit ()
  call lhpdf_status_reset (global%lhpdf_status)
  call pdf_builtin_status_reset (global%pdf_builtin_status)
  call rt_data_link (beams%local, global)
  if (associated (beams%options)) then
    call command_list_execute (beams%options, beams%local)
  end if
  polarized = .true.
  do i = 1, beams%n_in
    aval(i) = eval_pdg_array (beams%pn_pdg(i)%ptr, beams%local%var_list)
    call flavor_init (flv_tmp, aval(i), beams%local%model)
    select case (size (flv_tmp))
    case (1); flv(i) = flv_tmp(1)
    case default
      call pdg_array_write (aval(i))
      call msg_fatal &
        ("Beam expression does not evaluate to a unique particle")
      return
    end select
    beams%prt(i) = flavor_get_name (flv(i))
    if (polarized .and. associated (beams%local%beam_polarization)) then
      if (size (beams%local%beam_polarization) == beams%n_in) then
        bp(1:beams%n_in) = beams%local%beam_polarization
      else
        call msg_error ("the number of incoming particles differs " &
          // "between beam and polarization setup - ignoring polarization")
        polarized = .false.
      end if
    else
      polarized = .false.
      select case (beams%n_in)
      case (1)
        call beam_polarization_init_trivial (bp(i))
      case (2)
        call beam_polarization_init_none (bp(i))
      end select
    end if
    pol(i) = beam_polarization2polarization (bp(i), flv(i), &

```



```

        decay=(size (bp) == 1))
end do
sqrts_known = var_list_is_known (beams%local%var_list, "sqrts")
p_known(1) = var_list_is_known (beams%local%var_list, "beam1_momentum")
p_known(2) = var_list_is_known (beams%local%var_list, "beam2_momentum")
alpha_known = var_list_is_known (beams%local%var_list, "crossing_angle")
theta_known = var_list_is_known (beams%local%var_list, "beams_theta")
phi_known = var_list_is_known (beams%local%var_list, "beams_phi")
sqrts = var_list_get_rval (beams%local%var_list, "sqrts")
p(1) = var_list_get_rval (beams%local%var_list, "beam1_momentum")
p(2) = var_list_get_rval (beams%local%var_list, "beam2_momentum")
alpha = var_list_get_rval (beams%local%var_list, "crossing_angle")
theta = var_list_get_rval (beams%local%var_list, "beams_theta")
phi = var_list_get_rval (beams%local%var_list, "beams_phi")
select case (beams%n_in)
case (2)
    if (sqrts_known) then
        if (any (p_known)) call msg_error &
            ("Beam setup: sqrts and beam momenta must not be set " &
             // "simultaneously; using sqrts only")
        if (alpha_known) call msg_fatal &
            ("Beam setup: sqrts and crossing angle must not be set " &
             // "simultaneously (set beam1_momentum and beam2_momentum " &
             // "instead)")
    else
        if (.not. all (p_known)) call msg_fatal &
            ("Beam setup: either sqrts or both beam momenta must be set.")
    end if
end select
select case (beams%n_in)
case (1)
    if (p_known(1) .or. theta_known .or. phi_known) then
        call beam_data_init_decay &
            (global%beam_data, flv, pol(1:1), p(1), theta, phi)
    else
        call beam_data_init_decay (global%beam_data, flv, pol(1:1))
    end if
case (2)
    if (sqrts_known) then
        if (theta_known .or. phi_known) then
            call beam_data_init_sqrts (global%beam_data, &
                sqrts, flv, pol, 0._default, theta=theta, phi=phi)
        else
            call beam_data_init_sqrts (global%beam_data, &
                sqrts, flv, pol)
        end if
    else if (alpha_known) then
        if (theta_known .or. phi_known) then
            call beam_data_init_momenta (global%beam_data, &
                p, flv, pol, alpha, theta, phi)
        else
            call beam_data_init_momenta (global%beam_data, &
                p, flv, pol, alpha)
        end if
    end if
end select

```

```

else
    if (theta_known .or. phi_known) then
        call beam_data_init_momenta (global%beam_data, &
            p, flv, pol, theta=theta, phi=phi)
    else
        call beam_data_init_momenta (global%beam_data, &
            p, flv, pol)
    end if
end if
if (global%sf_list_allocated) then
    call sf_list_final (global%sf_list)
    deallocate (global%sf_list)
end if
allocate (global%sf_list)
global%sf_list_allocated = .true.
do i = 1, beams%n_strfun
    call strfun_pair_register (beams%strfun_pair(i), global)
end do
call sf_list_freeze (global%sf_list, &
    var_list_get_lval (beams%local%var_list, "?strfun_multichannel"))
! call sf_list_write (global%sf_list, beam_fmt = .true.)
call sf_list_compute_md5sum (global%sf_list)
end select
call beam_data_write (global%beam_data, verbose=.false.)
call beam_data_write (global%beam_data, verbose=.false., unit=u)
if (polarized) then
    do i = 1, beams%n_in
        if (output_unit () >= 0) write (output_unit (), '(1x,A)') &
            "polarization of '" // char (flavor_get_name (flv(i))) // "':"
        if (u >= 0) write (u, '(1x,A)') &
            "polarization of '" // char (flavor_get_name (flv(i))) // "':"
        call beam_polarization_write (beams%local%beam_polarization(i))
        call beam_polarization_write (beams%local%beam_polarization(i), u)
    end do
end if
if (u >= 0) flush (u)
call rt_data_restore (global, beams%local)
end subroutine cmd_beams_execute

```

(Commands: procedures)+≡

```

subroutine strfun_pair_register (strfun_pair, global)
    type(strfun_pair_t), intent(inout) :: strfun_pair
    type(rt_data_t), intent(inout), target :: global
    logical, dimension(2) :: affects_beam
    select case (strfun_pair%n)
    case (1)
        affects_beam = .true.
        call strfun_def_register (strfun_pair%def(1), affects_beam, global)
    case (2)
        affects_beam = (/ .true., .false. /)
        call strfun_def_register (strfun_pair%def(1), affects_beam, global)
        affects_beam = (/ .false., .true. /)
        call strfun_def_register (strfun_pair%def(2), affects_beam, global)
    end select

```

```

end subroutine strfun_pair_register

subroutine strfun_def_register (strfun_def, affects_beam, global)
  type(strfun_def_t), intent(inout) :: strfun_def
  logical, dimension(2), intent(in) :: affects_beam
  type(rt_data_t), intent(inout), target :: global
  call rt_data_link (strfun_def%local, global)
  if (associated (strfun_def%options)) then
    call command_list_execute (strfun_def%options, strfun_def%local)
  end if
  select case (strfun_def%type)
  case (STRF_LHAPDF)
    call sf_list_register_lhapdf &
      (global%sf_list, affects_beam, &
       global%lhpdf_status, global%model, global%beam_data%flv, &
       strfun_def%local%var_list)
  case (STRF_PDF_BUILTIN)
    call sf_list_register_pdf_builtin &
      (global%sf_list, affects_beam, &
       global%pdf_builtin_status, global%model, global%beam_data%flv, &
       strfun_def%local%os_data%pdf_builtin_datapath, &
       strfun_def%local%var_list)
  case (STRF_ISR)
    call sf_list_register_isr &
      (global%sf_list, affects_beam, &
       global%model, global%beam_data%flv, global%beam_data%sqrts, &
       strfun_def%local%var_list)
  case (STRF_EPA)
    call sf_list_register_epa &
      (global%sf_list, affects_beam, &
       global%model, global%beam_data%flv, global%beam_data%sqrts, &
       strfun_def%local%var_list)
  case (STRF_EWA)
    call msg_warning ("EWA structure function not yet fully implemented")
    call sf_list_register_ewa &
      (global%sf_list, affects_beam, &
       global%model, global%beam_data%flv, global%beam_data%sqrts, &
       strfun_def%local%var_list)
  case (STRF_CIRCE1)
    call sf_list_register_circe1 &
      (global%sf_list, affects_beam, &
       global%model, global%beam_data%flv, global%beam_data%sqrts, &
       global%rng, &
       strfun_def%local%var_list)
  case (STRF_CIRCE2)
    call sf_list_register_circe2 &
      (global%sf_list, affects_beam, &
       global%beam_data%flv, global%beam_data%sqrts, &
       global%rng, global%os_data%whizard_circe2path, &
       strfun_def%local%var_list)
  case (STRF_ESCAN)
    call sf_list_register_escan &
      (global%sf_list, affects_beam, &
       global%beam_data%flv, global%beam_data%sqrts, &

```

```

        strfun_def%local%var_list)
case (STRF_BEVT)
    call sf_list_register_beam_events &
        (global%sf_list, affects_beam, &
         global%beam_data%flv, global%os_data%whizard_beamsimp, &
         strfun_def%local%var_list)
case (STRF_USER)
    call sf_list_register_user &
        (global%sf_list, affects_beam, &
         global%model, global%beam_data%flv, &
         eval_string (strfun_def%pn_user_name, strfun_def%local%var_list), &
         strfun_def%local%var_list)
end select
call rt_data_restore (global, strfun_def%local)
end subroutine strfun_def_register

```

The individual register procedures. They unpack data from the local var list, allocate structure function data blocks and fill them. Depending on the structure function and on the beams on which it should apply, one or two such entries are added to the structure function list. For double structure functions, it is useful to add a pair-mapping.

(Commands: procedures)+≡

```

subroutine sf_list_register_lhapdf (sf_list, affects_beam, &
    lhpdf_status, model, flv, var_list)
    type(sf_list_t), intent(inout) :: sf_list
    logical, dimension(2), intent(in) :: affects_beam
    type(lhpdf_status_t), intent(inout) :: lhpdf_status
    type(model_t), intent(in), target :: model
    type(flavor_t), dimension(2), intent(in) :: flv
    type(var_list_t), intent(in) :: var_list
    type(string_t) :: lhpdf_file, lhpdf_dir
    integer :: lhpdf_member, lhpdf_photon_scheme
    type(sf_data_t), pointer :: sf_data
    integer :: i
    lhpdf_dir = &
        var_list_get_sval (var_list, var_str ("lhpdf_dir")) ! $
    lhpdf_file = &
        var_list_get_sval (var_list, var_str ("lhpdf_file")) ! $
    lhpdf_member = &
        var_list_get_ival (var_list, var_str ("lhpdf_member"))
    lhpdf_photon_scheme = &
        var_list_get_ival (var_list, var_str ("lhpdf_photon_scheme"))
    do i = 1, 2
        if (affects_beam(i)) then
            allocate (sf_data)
            call sf_data_init_lhapdf (sf_data, i, lhpdf_status, &
                model, flv(i), &
                lhpdf_dir, lhpdf_file, lhpdf_member, lhpdf_photon_scheme)
            call sf_list_append (sf_list, sf_data)
        end if
    end do
    if (all (affects_beam)) then
        call sf_data_setup_mapping &

```

```

        (sf_data, SFM_PAIR, (/ 0, 1 /), 2._default)
    end if
end subroutine sf_list_register_lhapdf

```

(Commands: procedures)+≡

```

subroutine sf_list_register_pdf_builtin (sf_list, affects_beam, &
    pdf_status, model, flv, datapath, var_list)
    type(sf_list_t), intent(inout) :: sf_list
    logical, dimension(2), intent(in) :: affects_beam
    type(pdf_builtin_status_t), intent(inout) :: pdf_status
    type(model_t), intent(in), target :: model
    type(flavor_t), dimension(2), intent(in) :: flv
    type(string_t), intent(in) :: datapath
    type(var_list_t), intent(in) :: var_list
    logical :: pdf_builtin_have_name
    type(string_t) :: pdf_builtin_prefix, pdf_builtin_name
    type(sf_data_t), pointer :: sf_data
    integer :: i
    pdf_builtin_have_name = &
        var_list_is_known (var_list, var_str ("pdf_builtin_set"))
    if (pdf_builtin_have_name) &
        pdf_builtin_name = &
            var_list_get_sval (var_list, var_str ("pdf_builtin_set"))
    pdf_builtin_have_name = trim (pdf_builtin_name) /= ""
    pdf_builtin_prefix = ""
    if (var_list_is_known (var_list, var_str ("pdf_builtin_path"))) &
        pdf_builtin_prefix = &
            var_list_get_sval (var_list, var_str ("pdf_builtin_path"))
    if (trim (pdf_builtin_prefix) == "") pdf_builtin_prefix = datapath
    do i = 1, 2
        if (affects_beam(i)) then
            allocate (sf_data)
            if (pdf_builtin_have_name) then
                call sf_data_init_pdf_builtin (sf_data, i, &
                    pdf_status, model, flv(i), &
                    name=pdf_builtin_name, path=pdf_builtin_prefix)
            else
                call sf_data_init_pdf_builtin (sf_data, i, &
                    pdf_status, model, flv(i), &
                    path=pdf_builtin_prefix)
            end if
            call sf_list_append (sf_list, sf_data)
        end if
    end do
    if (all (affects_beam)) then
        call sf_data_setup_mapping &
            (sf_data, SFM_PAIR, (/ 0, 1 /), 2._default)
    end if
end subroutine sf_list_register_pdf_builtin

```

(Commands: procedures)+≡

```

subroutine sf_list_register_isr (sf_list, affects_beam, &
    model, flv, sqrts, var_list)

```

```

type(sf_list_t), intent(inout) :: sf_list
logical, dimension(2), intent(in) :: affects_beam
type(model_t), intent(in), target :: model
type(flavor_t), dimension(2), intent(in) :: flv
real(default), intent(in) :: sqrts
type(var_list_t), intent(in) :: var_list
real(default) :: isr_alpha, isr_q_max, isr_mass
integer :: isr_order
logical :: isr_recoil
type(sf_data_t), pointer :: sf_data
integer :: i
isr_alpha = var_list_get_rval (var_list, var_str ("isr_alpha"))
if (isr_alpha == 0) then
    isr_alpha = (var_list_get_rval (var_list, var_str ("ee"))) &
        ** 2 / (4 * pi)
end if
isr_q_max = var_list_get_rval (var_list, var_str ("isr_q_max"))
if (isr_q_max == 0) then
    isr_q_max = sqrts
end if
isr_mass = var_list_get_rval (var_list, var_str ("isr_mass"))
isr_order = var_list_get_ival (var_list, var_str ("isr_order"))
isr_recoil = var_list_get_lval (var_list, var_str ("?isr_recoil"))
do i = 1, 2
    if (affects_beam(i)) then
        allocate (sf_data)
        if (isr_mass /= 0) then
            call sf_data_init_isr (sf_data, i, &
                model, flv(i), isr_recoil, isr_alpha, isr_q_max, isr_mass, &
                order=isr_order)
        else
            call sf_data_init_isr (sf_data, i, &
                model, flv(i), isr_recoil, isr_alpha, isr_q_max, &
                order=isr_order)
        end if
        call sf_list_append (sf_list, sf_data)
    end if
end do
! No pair mapping
end subroutine sf_list_register_isr

```

(Commands: procedures)+≡

```

subroutine sf_list_register_epa (sf_list, affects_beam, &
    model, flv, sqrts, var_list)
type(sf_list_t), intent(inout) :: sf_list
logical, dimension(2), intent(in) :: affects_beam
type(model_t), intent(in), target :: model
type(flavor_t), dimension(2), intent(in) :: flv
real(default), intent(in) :: sqrts
type(var_list_t), intent(in) :: var_list
real(default) :: epa_alpha, epa_x_min, epa_q_min, epa_e_max, epa_mass
logical :: epa_recoil
type(sf_data_t), pointer :: sf_data
integer :: i

```

```

epa_alpha = var_list_get_rval (var_list, var_str ("epa_alpha"))
if (epa_alpha == 0) then
    epa_alpha = (var_list_get_rval (var_list, var_str ("ee"))) &
        ** 2 / (4 * pi)
end if
epa_x_min = var_list_get_rval (var_list, var_str ("epa_x_min"))
epa_q_min = var_list_get_rval (var_list, var_str ("epa_q_min"))
epa_e_max = var_list_get_rval (var_list, var_str ("epa_e_max"))
if (epa_e_max == 0) then
    epa_e_max = sqrts
end if
epa_mass = var_list_get_rval (var_list, var_str ("epa_mass"))
epa_recoil = var_list_get_lval (var_list, var_str ("?epa_recoil"))
do i = 1, 2
    if (affects_beam(i)) then
        allocate (sf_data)
        if (epa_mass /= 0) then
            call sf_data_init_epa (sf_data, i, &
                model, flv(i), epa_recoil, &
                epa_alpha, epa_x_min, epa_q_min, epa_e_max, epa_mass)
        else
            call sf_data_init_epa (sf_data, i, &
                model, flv(i), epa_recoil, &
                epa_alpha, epa_x_min, epa_q_min, epa_e_max)
        end if
        call sf_list_append (sf_list, sf_data)
    end if
end do
if (all (affects_beam)) then
    if (epa_recoil) then
        call sf_data_setup_mapping &
            (sf_data, SFM_PAIR, (/ -2, 1 /), 1._default)
    else
        call sf_data_setup_mapping &
            (sf_data, SFM_PAIR, (/ 0, 1 /), 1._default)
    end if
end if
end subroutine sf_list_register_epa

```

<Commands: procedures>+≡

```

subroutine sf_list_register_ewa (sf_list, affects_beam, &
    model, flv, sqrts, var_list)
type(sf_list_t), intent(inout) :: sf_list
logical, dimension(2), intent(in) :: affects_beam
type(model_t), intent(in), target :: model
type(flavor_t), dimension(2), intent(in) :: flv
real(default), intent(in) :: sqrts
type(var_list_t), intent(in) :: var_list
real(default) :: ewa_x_min, ewa_q_min, ewa_pt_max, ewa_mass, ewa_sqrts
logical :: ewa_keep_momentum, ewa_keep_energy
type(sf_data_t), pointer :: sf_data
integer :: i
do i = 1, 2
    if (affects_beam(i)) then

```

```

allocate (sf_data)
ewa_x_min = var_list_get_rval (var_list, var_str ("ewa_x_min"))
ewa_q_min = var_list_get_rval (var_list, var_str ("ewa_q_min"))
ewa_pt_max = var_list_get_rval (var_list, var_str ("ewa_pt_max"))
if (ewa_pt_max == 0) then
    ewa_pt_max = sqrts
end if
ewa_mass = var_list_get_rval (var_list, var_str ("ewa_mass"))
ewa_sqrts = sqrts
ewa_keep_momentum = var_list_get_lval (var_list, &
    var_str ("?ewa_keep_momentum"))
ewa_keep_energy = var_list_get_lval (var_list, &
    var_str ("?ewa_keep_energy"))
if (ewa_keep_momentum .and. ewa_keep_energy) &
    call msg_fatal (" EWA cannot violate both energy " &
        // "and momentum conservation.")
if (ewa_mass /= 0) then
    call sf_data_init_ewa (sf_data, i, &
        model, flv(i), &
        ewa_x_min, ewa_q_min, ewa_pt_max, ewa_sqrts, &
        ewa_keep_momentum, ewa_keep_energy, ewa_mass)
else
    call sf_data_init_ewa (sf_data, i, &
        model, flv(i), &
        ewa_x_min, ewa_q_min, ewa_pt_max, ewa_sqrts, &
        ewa_keep_momentum, ewa_keep_energy)
end if
call sf_list_append (sf_list, sf_data)
end if
end do
if (all (affects_beam)) then
    call sf_data_setup_mapping &
        (sf_data, SFM_PAIR, (/ 0, 1 /), 1._default)
end if
end subroutine sf_list_register_ewa

```

<Commands: procedures>+≡

```

subroutine sf_list_register_circe1 (sf_list, affects_beam, &
    model, flv, sqrts, rng, var_list)
type(sf_list_t), intent(inout) :: sf_list
logical, dimension(2), intent(in) :: affects_beam
type(model_t), intent(in), target :: model
type(flavor_t), dimension(2), intent(in) :: flv
real(default), intent(in) :: sqrts
type(tao_random_state), intent(in), target :: rng
type(var_list_t), intent(in) :: var_list
real(default) :: circe1_sqrts
logical, dimension(2) :: circe1_photon
logical :: circe1_generate, circe1_map
integer :: circe1_ver, circe1_rev, circe1_acc, circe1_chat
type(sf_data_t), pointer :: sf_data
if (all (affects_beam)) then
    allocate (sf_data)
    if (var_list_is_known (var_list, var_str ("circe1_sqrts"))) then

```



```

        circe1_sqrts = var_list_get_rval (var_list, var_str ("circe1_sqrts"))
    else
        circe1_sqrts = sqrts
    end if
    circe1_photon(1) = &
        var_list_get_lval (var_list, var_str ("?circe1_photon1"))
    circe1_photon(2) = &
        var_list_get_lval (var_list, var_str ("?circe1_photon2"))
    circe1_generate = &
        var_list_get_lval (var_list, var_str ("?circe1_generate"))
    circe1_map = &
        var_list_get_lval (var_list, var_str ("?circe1_map"))
    circe1_ver = &
        var_list_get_ival (var_list, var_str ("circe1_ver"))
    circe1_rev = &
        var_list_get_ival (var_list, var_str ("circe1_rev"))
    circe1_acc = &
        var_list_get_ival (var_list, var_str ("circe1_acc"))
    circe1_chat = &
        var_list_get_ival (var_list, var_str ("circe1_chat"))
    call sf_data_init_circe1 (sf_data, &
        model, flv, circe1_sqrts, circe1_photon, &
        circe1_generate, rng, circe1_map, &
        circe1_ver, circe1_rev, circe1_acc, circe1_chat)
    call sf_list_append (sf_list, sf_data)
else
    call msg_fatal ("CIRCE1 beamstrahlung spectrum must apply to both beams")
end if
! No pair mapping
end subroutine sf_list_register_circe1

```

(*Commands: procedures*)+≡

```

subroutine sf_list_register_circe2 (sf_list, affects_beam, &
    flv, sqrts, rng, path, var_list)
    type(sf_list_t), intent(inout) :: sf_list
    logical, dimension(2), intent(in) :: affects_beam
    type(flavor_t), dimension(2), intent(in) :: flv
    real(default), intent(in) :: sqrts
    type(tao_random_state), intent(in), target :: rng
    type(string_t), intent(in) :: path
    type(var_list_t), intent(in) :: var_list
    real(default) :: circe2_sqrts
    logical :: circe2_generate, circe2_map, circe2_polarized
    type(string_t) :: circe2_file, circe2_design
    type(sf_data_t), pointer :: sf_data
    if (all (affects_beam)) then
        allocate (sf_data)
        if (var_list_is_known (var_list, var_str ("circe2_sqrts"))) then
            circe2_sqrts = var_list_get_rval (var_list, var_str ("circe2_sqrts"))
        else
            circe2_sqrts = sqrts
        end if
        circe2_generate = &
            var_list_get_lval (var_list, var_str ("?circe2_generate"))
    end if

```

```

    circe2_map = &
        var_list_get_lval (var_list, var_str ("?circe2_map"))
    circe2_polarized = &
        var_list_get_lval (var_list, var_str ("?circe2_polarized"))
    circe2_file = &
        var_list_get_sval (var_list, var_str ("$circe2_file")) ! $
    if (circe2_file == "") call msg_fatal &
        ("CIRCE2: Data file $circe2_file must be specified") ! $
    circe2_file = path // "/" // circe2_file
    circe2_design = &
        var_list_get_sval (var_list, var_str ("$circe2_design")) ! $
    call sf_data_init_circe2 (sf_data, &
        flv, circe2_generate, rng, &
        circe2_map, circe2_file, circe2_design, circe2_sqrts, &
        circe2_polarized)
    call sf_list_append (sf_list, sf_data)
else
    call msg_fatal ("CIRCE2 spectrum must apply to both beams")
end if
! No pair mapping
end subroutine sf_list_register_circe2

```

<Commands: procedures>+≡

```

subroutine sf_list_register_escan (sf_list, affects_beam, &
    flv, sqrts, var_list)
    type(sf_list_t), intent(inout) :: sf_list
    logical, dimension(2), intent(in) :: affects_beam
    type(flavor_t), dimension(2), intent(in) :: flv
    real(default), intent(in) :: sqrts
    type(var_list_t), intent(in) :: var_list
    real(default) :: escan_sqrts
    type(sf_data_t), pointer :: sf_data
    escan_sqrts = sqrts
    allocate (sf_data)
    call sf_data_init_escan (sf_data, affects_beam, flv, escan_sqrts)
    call sf_list_append (sf_list, sf_data)
    ! No pair mapping
end subroutine sf_list_register_escan

```

<Commands: procedures>+≡

```

subroutine sf_list_register_beam_events (sf_list, affects_beam, &
    flv, path, var_list)
    type(sf_list_t), intent(inout) :: sf_list
    logical, dimension(2), intent(in) :: affects_beam
    type(flavor_t), dimension(2), intent(in) :: flv
    type(string_t), intent(in) :: path
    type(var_list_t), intent(in) :: var_list
    type(sf_data_t), pointer :: sf_data
    type(string_t) :: beam_events_file
    logical :: beam_events_warn_eof
    logical :: exist
    if (all (affects_beam)) then
        allocate (sf_data)
    end if

```

```

beam_events_file = &
    var_list_get_sval (var_list, var_str ("$beam_events_file")) ! $
beam_events_warn_eof = &
    var_list_get_lval (var_list, var_str ("?beam_events_warn_eof"))
inquire (file = char (beam_events_file), exist = exist)
if (.not. exist) then
    beam_events_file = path // "/" // beam_events_file
    inquire (file = char (beam_events_file), exist = exist)
    if (.not. exist) then
        call msg_fatal ("Beam simulation data file '" &
            // char (beam_events_file) // "' not found.")
    end if
end if
call sf_data_init_beam_events &
    (sf_data, affects_beam, flv, beam_events_file, beam_events_warn_eof)
call sf_list_append (sf_list, sf_data)
else
    call msg_fatal ("Beam events simulation must apply to both beams")
end if
! No pair mapping
end subroutine sf_list_register_beam_events

```

For user structure functions, it is not evident whether they apply to single beams or to the beam pair, before the data set has been initialized. Therefore, we have to shortcut the scan over the two beams if we encounter a structure function that applies to the beam pair.

(*Commands: procedures*)+≡

```

subroutine sf_list_register_user (sf_list, affects_beam, &
    model, flv, user_name, var_list)
type(sf_list_t), intent(inout) :: sf_list
logical, dimension(2), intent(in) :: affects_beam
type(model_t), intent(in), target :: model
type(flavor_t), dimension(2), intent(in) :: flv
type(string_t), intent(in) :: user_name
type(var_list_t), intent(in) :: var_list
type(sf_data_t), pointer :: sf_data
logical :: user_strfun_mapping
real(default) :: user_strfun_mapping_power
integer :: i
do i = 1, 2
    if (affects_beam(i)) then
        allocate (sf_data)
        call sf_data_init_user (sf_data, i, flv, user_name, model)
        call sf_list_append (sf_list, sf_data)
        if (all (sf_data_affects_beam (sf_data))) then
            if (.not. all (affects_beam)) call msg_fatal &
                ("User spectrum/structure function inconsistently applied")
            exit
        end if
    end if
end do
end do
user_strfun_mapping = &
    var_list_get_lval (var_list, var_str ("?user_strfun_mapping"))

```

```

user_strfun_mapping_power = &
  var_list_get_rval (var_list, var_str ("user_strfun_mapping_power"))
if (all (affects_beam) .and. user_strfun_mapping) then
  if (all (sf_data_affects_beam (sf_data))) then
    call sf_data_setup_mapping &
      (sf_data, SFM_PAIR, &
        (/ sf_data_get_n_parameters (sf_data) - 1, &
          sf_data_get_n_parameters (sf_data) /), &
        user_strfun_mapping_power)
  else
    call sf_data_setup_mapping &
      (sf_data, SFM_PAIR, &
        (/ 0, sf_data_get_n_parameters (sf_data) /), &
        user_strfun_mapping_power)
  end if
end if
! No pair mapping
end subroutine sf_list_register_user

```

Beam polarization

We define an assortment of containers for the options of the different beam polarization constructors.

(Commands: types)+≡

```

type :: bp_circ_data_t
  private
  type(parse_node_t), pointer :: pn_fraction => null ()
  real(default) :: fraction
end type bp_circ_data_t

type :: bp_trans_data_t
  private
  type(parse_node_t), pointer :: pn_fraction => null ()
  type(parse_node_t), pointer :: pn_phi => null ()
  real(default) :: fraction, phi
end type bp_trans_data_t

type :: bp_long_data_t
  private
  type(parse_node_t), pointer :: pn_fraction => null ()
  real(default) :: fraction
end type bp_long_data_t

type :: bp_axis_data_t
  private
  type(parse_node_t), pointer :: pn_fraction => null ()
  type(parse_node_t), pointer :: pn_theta => null ()
  type(parse_node_t), pointer :: pn_phi => null ()
  real(default) :: fraction, theta, phi
end type bp_axis_data_t

type :: bp_diag_data_t

```

```

    private
    type(parse_node_p), dimension(:), allocatable :: pn_hel
    type(parse_node_p), dimension(:), allocatable :: pn_fraction
    integer, dimension(:), allocatable :: hel
    real(default), dimension(:), allocatable :: fraction
end type bp_diag_data_t

type :: bp_density_data_t
    private
    type(parse_node_t), pointer :: pn_d => null ()
    type(parse_node_t), pointer :: pn_nd => null ()
    real(default) :: d
    complex(default) :: nd
end type bp_density_data_t

```

The actual scratch container for the command. A negative **n** means the structure is invalid, and a negative **type** tells the execution subprogram to disable beam polarization altogether.

```

<Commands: types>+≡
type :: cmd_beam_polarization_t
    private
    integer :: n = -1
    integer, dimension(2) :: type = -1
    type(bp_circ_data_t), dimension(:), pointer :: circ_data => null ()
    type(bp_trans_data_t), dimension(:), pointer :: trans_data => null ()
    type(bp_long_data_t), dimension(:), pointer :: long_data => null ()
    type(bp_axis_data_t), dimension(:), pointer :: axis_data => null ()
    type(bp_diag_data_t), dimension(:), pointer :: diag_data => null ()
    type(bp_density_data_t), dimension(:), pointer :: &
        density_data => null ()
    type(command_list_t), pointer :: options => null ()
    type(rt_data_t) :: local
    type(beam_polarization_t), dimension(:), pointer :: &
        beam_polarization => null ()
end type cmd_beam_polarization_t

```

Finalize the container. We define a separate finalizer for each subcontainer.

```

<Commands: procedures>+≡
elemental subroutine bp_circ_data_final (d)
    type(bp_circ_data_t), intent(inout) :: d
end subroutine bp_circ_data_final

elemental subroutine bp_trans_data_final (d)
    type(bp_trans_data_t), intent(inout) :: d
end subroutine bp_trans_data_final

elemental subroutine bp_long_data_final (d)
    type(bp_long_data_t), intent(inout) :: d
end subroutine bp_long_data_final

elemental subroutine bp_axis_data_final (d)
    type(bp_axis_data_t), intent(inout) :: d
end subroutine bp_axis_data_final

```

```

elemental subroutine bp_diag_data_final (d)
  type(bp_diag_data_t), intent(inout) :: d
  deallocate (d%pn_hel)
  deallocate (d%pn_fraction)
  if (allocated (d%hel)) deallocate (d%hel)
  if (allocated (d%fraction)) deallocate (d%fraction)
end subroutine bp_diag_data_final

elemental subroutine bp_density_data_final (d)
  type(bp_density_data_t), intent(inout) :: d
end subroutine bp_density_data_final

subroutine cmd_beam_polarization_final (bp)
  type(cmd_beam_polarization_t), intent(inout) :: bp
  if (associated (bp%circ_data)) then
    call bp_circ_data_final (bp%circ_data)
    deallocate (bp%circ_data)
  end if
  if (associated (bp%trans_data)) then
    call bp_trans_data_final (bp%trans_data)
    deallocate (bp%trans_data)
  end if
  if (associated (bp%long_data)) then
    call bp_long_data_final (bp%long_data)
    deallocate (bp%long_data)
  end if
  if (associated (bp%axis_data)) then
    call bp_axis_data_final (bp%axis_data)
    deallocate (bp%axis_data)
  end if
  if (associated (bp%diag_data)) then
    call bp_diag_data_final (bp%diag_data)
    deallocate (bp%diag_data)
  end if
  if (associated (bp%density_data)) then
    call bp_density_data_final (bp%density_data)
    deallocate (bp%density_data)
  end if
  if (associated (bp%options)) then
    call command_list_final (bp%options)
    deallocate (bp%options)
  end if
  if (associated (bp%beam_polarization)) deallocate (bp%beam_polarization)
  bp%type = -1
  bp%n = -1
end subroutine cmd_beam_polarization_final

```

Compile.

<Commands: procedures>+≡

```

subroutine cmd_beam_polarization_compile (bp, pn, global)
  type(cmd_beam_polarization_t), pointer, intent(inout) :: bp
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(in), target :: global

```

```

type(parse_node_t), pointer :: pn_list, pn_opts, pn_args, pn_entry
integer :: i, n
pn_list => parse_node_get_sub_ptr (pn, 3)
pn_opts => parse_node_get_sub_ptr (pn, 4)
allocate (bp)
call rt_data_local_init (bp%local, global)
if (associated (pn_opts)) then
    allocate (bp%options)
    call command_list_compile (bp%options, pn_opts, bp%local)
end if
if (parse_node_get_rule_key (pn_list) == "off") then
    bp%n = 0
    bp%type = -1
    return
end if
bp%n = parse_node_get_n_sub (pn_list)
pn_list => parse_node_get_sub_ptr (pn_list)
do i = 1, bp%n
    pn_args => parse_node_get_sub_ptr (pn_list, 2)
    select case (char (parse_node_get_rule_key (pn_list)))
        case ("none")
            bp%type(i) = BP_NONE
        case ("bp_circ")
            if (parse_node_get_n_sub (pn_args) /= 1) then
                call cmd_beam_polarization_final (bp)
                call msg_fatal &
                    ("syntax error: expecting 'circular (fraction)')")
                return
            end if
            bp%type(i) = BP_CIRC
            if (.not. associated (bp%circ_data)) &
                allocate (bp%circ_data(2))
            bp%circ_data(i)%pn_fraction => parse_node_get_sub_ptr (pn_args, 1)
        case ("bp_trans")
            if (parse_node_get_n_sub (pn_args) /= 2) then
                call cmd_beam_polarization_final (bp)
                call msg_fatal &
                    ("syntax error: expecting transverse (fraction, phi)')")
                return
            end if
            bp%type(i) = BP_TRANS
            if (.not. associated (bp%trans_data)) &
                allocate (bp%trans_data(2))
            bp%trans_data(i)%pn_fraction => parse_node_get_sub_ptr (pn_args, 1)
            bp%trans_data(i)%pn_phi => parse_node_get_sub_ptr (pn_args, 2)
        case ("bp_axis")
            if (parse_node_get_n_sub (pn_args) /= 3) then
                call cmd_beam_polarization_final (bp)
                call msg_fatal &
                    ("syntax error: expecting 'axis (fraction, theta, phi)')")
                return
            end if
            bp%type(i) = BP_AXIS
            if (.not. associated (bp%axis_data)) &

```

```

        allocate (bp%axis_data(2))
        bp%axis_data(i)%pn_fraction => parse_node_get_sub_ptr (pn_args, 1)
        bp%axis_data(i)%pn_theta => parse_node_get_sub_ptr (pn_args, 2)
        bp%axis_data(i)%pn_phi => parse_node_get_sub_ptr (pn_args, 3)
    case ("bp_long")
        if (parse_node_get_n_sub (pn_args) /= 1) then
            call cmd_beam_polarization_final (bp)
            call msg_fatal &
                ("syntax error: expecting 'longitudinal (fraction)')")
            return
        end if
        bp%type(i) = BP_LONG
        if (.not. associated (bp%long_data)) &
            allocate (bp%long_data(2))
        bp%long_data(i)%pn_fraction => parse_node_get_sub_ptr (pn_args, 1)
    case ("bp_dens")
        if (parse_node_get_n_sub (pn_args) /= 2) then
            call cmd_beam_polarization_final (bp)
            call msg_fatal &
                ("syntax error: expecting 'density_matrix (a, b)')")
            return
        end if
        bp%type(i) = BP_DENSITY
        if (.not. associated (bp%density_data)) &
            allocate (bp%density_data (2))
        bp%density_data(i)%pn_d => parse_node_get_sub_ptr (pn_args, 1)
        bp%density_data(i)%pn_nd => parse_node_get_sub_ptr (pn_args, 2)
    case ("bp_diag")
        bp%type(i) = BP_DIAG
        n = parse_node_get_n_sub (pn_args)
        if (.not. associated (bp%diag_data)) &
            allocate (bp%diag_data(2))
        allocate (bp%diag_data(i)%pn_hel (n))
        allocate (bp%diag_data(i)%pn_fraction (n))
        allocate (bp%diag_data(i)%hel (n))
        allocate (bp%diag_data(i)%fraction (n))
        pn_entry => parse_node_get_sub_ptr (pn_args)
        n = 1
        do while (associated (pn_entry))
            bp%diag_data(i)%pn_hel(n)%ptr &
                => parse_node_get_sub_ptr (pn_entry, 1)
            bp%diag_data(i)%pn_fraction(n)%ptr &
                => parse_node_get_sub_ptr (pn_entry, 3)
            pn_entry => parse_node_get_next_ptr (pn_entry)
            n = n + 1
        end do
    case default
        call msg_bug ("cmd_beam_polarization_compile: invalid " &
            // "polarization type")
    end select
    pn_list => parse_node_get_next_ptr (pn_list)
end do

call rt_data_local_reset (bp%local)

```



```
end subroutine cmd_beam_polarization_compile
```

Execute.

(Commands: procedures)+≡

```
subroutine cmd_beam_polarization_execute (bp, global)
  type(cmd_beam_polarization_t), pointer, intent(inout) :: bp
  type(rt_data_t), intent(inout), target :: global
  type(polarization_t), dimension(:), allocatable :: pol
  integer :: i, j, k, ulog
  ulog = logfile_unit ()
  call rt_data_link (bp%local, global)
  if (associated (bp%options)) &
    call command_list_execute (bp%options, bp%local)
  if (bp%n < 0) then
    call rt_data_restore (global, bp%local)
    return
  end if
  if (bp%type(1) < 0) then
    call rt_data_restore (global, bp%local)
    global%beam_polarization => null ()
    if (beam_data_are_valid (global%beam_data)) &
      call beam_data_kill_polarization (global%beam_data)
    if (global%environment /= CMD_BEAMS) call msg_message &
      ("beam polarization disabled")
    return
  end if
  if (.not. associated (bp%beam_polarization)) then
    allocate (bp%beam_polarization(bp%n))
  else
    do i = 1, bp%n
      call beam_polarization_final (bp%beam_polarization(i))
    end do
  end if
  do i = 1, bp%n
    select case (bp%type(i))
    case (BP_NONE, BP_TRIVIAL)
      if (bp%n == 2) then
        call beam_polarization_init_none (bp%beam_polarization(i))
      else
        call beam_polarization_init_trivial (bp%beam_polarization(i))
      end if
    case (BP_CIRC)
      bp%circ_data(i)%fraction = &
        eval_real (bp%circ_data(i)%pn_fraction, bp%local%var_list)
      call beam_polarization_init_circ (bp%beam_polarization(i), &
        bp%circ_data(i)%fraction)
    case (BP_TRANS)
      bp%trans_data(i)%fraction = &
        eval_real (bp%trans_data(i)%pn_fraction, bp%local%var_list)
      bp%trans_data(i)%phi = &
        eval_real (bp%trans_data(i)%pn_phi, bp%local%var_list)
      call beam_polarization_init_trans (bp%beam_polarization(i), &
        bp%trans_data(i)%fraction, bp%trans_data(i)%phi)
    case (BP_LONG)
```

```

        bp%long_data(i)%fraction = &
            eval_real (bp%long_data(i)%pn_fraction, bp%local%var_list)
        call beam_polarization_init_long (bp%beam_polarization(i), &
            bp%long_data(i)%fraction)
    case (BP_AXIS)
        bp%axis_data(i)%fraction = &
            eval_real (bp%axis_data(i)%pn_fraction, bp%local%var_list)
        bp%axis_data(i)%theta = &
            eval_real (bp%axis_data(i)%pn_theta, bp%local%var_list)
        bp%axis_data(i)%phi = &
            eval_real (bp%axis_data(i)%pn_phi, bp%local%var_list)
        call beam_polarization_init_axis (bp%beam_polarization(i), &
            bp%axis_data(i)%fraction, bp%axis_data(i)%theta, &
            bp%axis_data(i)%phi)
    case (BP_DENSITY)
        bp%density_data(i)%d = &
            eval_real (bp%density_data(i)%pn_d, bp%local%var_list)
        bp%density_data(i)%nd = &
            eval_cmlx (bp%density_data(i)%pn_nd, bp%local%var_list)
        call beam_polarization_init_density (bp%beam_polarization(i), &
            bp%density_data(i)%d, bp%density_data(i)%nd)
    case (BP_DIAG)
        do j = 1, size (bp%diag_data(i)%hel)
            bp%diag_data(i)%hel(j) = &
                eval_int (bp%diag_data(i)%pn_hel(j)%ptr, bp%local%var_list)
            bp%diag_data(i)%fraction(j) = &
                eval_real (bp%diag_data(i)%pn_fraction(j)%ptr, &
                    bp%local%var_list)
            if (j > 1) then
                do k = 1, j - 1
                    if (bp%diag_data(i)%hel(j) == bp%diag_data(i)%hel(k)) then
                        call msg_error ( &
                            "'diagonal_density (h1:f1 [, h2:f2, ...])': " &
                            // "h" // int2char(j) // " and h" // int2char(k) &
                            // " must not be equal")
                        call rt_data_restore (global, bp%local)
                        return
                    end if
                end do
            end if
        end do
        call beam_polarization_init_diag (bp%beam_polarization(i), &
            bp%diag_data(i)%hel, bp%diag_data(i)%fraction)
    case default
        call msg_bug ("cmd_beam_polarization_execute: " &
            // "unknown polarization type")
    end select
    if (global%environment /= CMD_BEAMS) then
        call msg_message &
            ("polarization of incoming particle " // int2char(i) // ":")
        call beam_polarization_write (bp%beam_polarization(i))
        call beam_polarization_write (bp%beam_polarization(i), ulog)
    end if
end do

```

```

call rt_data_restore (global, bp%local)
global%beam_polarization => bp%beam_polarization
if (beam_data_are_valid (global%beam_data)) then
  if (beam_data_get_n_in (global%beam_data) /= bp%n) then
    call msg_error ("the number of incoming particles differs " &
      // "between beam and polarization setup - ignoring polarization")
  else
    allocate (pol (bp%n))
    do i = 1, bp%n
      pol(i) = beam_polarization2polarization &
        (bp%beam_polarization(i), global%beam_data%flv(i), &
          decay=(bp%n == 1))
    end do
    call beam_data_set_polarization (global%beam_data, pol)
  end if
else
  if (global%environment /= CMD_BEAMS) call msg_warning ( &
    "beam_polarization only works with a beam setup")
end if

end subroutine cmd_beam_polarization_execute

```

Cuts

Define a cut expression. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the process environment where the cut expression is used.

```

<Commands: types>+≡
type :: cmd_cuts_t
  private
  type(parse_node_t), pointer :: pn_lexpr => null ()
end type cmd_cuts_t

```

Compile. Simply store the parse (sub)tree.

```

<Commands: procedures>+≡
subroutine cmd_cuts_compile (cuts, pn)
  type(cmd_cuts_t), pointer :: cuts
  type(parse_node_t), intent(in), target :: pn
  allocate (cuts)
  cuts%pn_lexpr => parse_node_get_sub_ptr (pn, 3)
end subroutine cmd_cuts_compile

```

Instead of evaluating the cut expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```

<Commands: procedures>+≡
subroutine cmd_cuts_execute (cuts, global)
  type(cmd_cuts_t), intent(inout), target :: cuts
  type(rt_data_t), intent(inout), target :: global
  global%pn_cuts_lexpr => cuts%pn_lexpr
end subroutine cmd_cuts_execute

```

General, Factorization and Renormalization Scales

Define a scale expression for either the renormalization or the factorization scale. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the process environment where the expression is used.

```
<Commands: types>+≡
  type :: cmd_scale_t
  private
    type(parse_node_t), pointer :: pn_expr => null ()
  end type cmd_scale_t
```

```
<Commands: types>+≡
  type :: cmd_fac_scale_t
  private
    type(parse_node_t), pointer :: pn_expr => null ()
  end type cmd_fac_scale_t
```

```
<Commands: types>+≡
  type :: cmd_ren_scale_t
  private
    type(parse_node_t), pointer :: pn_expr => null ()
  end type cmd_ren_scale_t
```

Compile. Simply store the parse (sub)tree.

```
<Commands: procedures>+≡
  subroutine cmd_scale_compile (scale, pn)
    type(cmd_scale_t), pointer :: scale
    type(parse_node_t), intent(in), target :: pn
    allocate (scale)
    scale%pn_expr => parse_node_get_sub_ptr (pn, 3)
  end subroutine cmd_scale_compile
```

```
<Commands: procedures>+≡
  subroutine cmd_fac_scale_compile (scale, pn)
    type(cmd_fac_scale_t), pointer :: scale
    type(parse_node_t), intent(in), target :: pn
    allocate (scale)
    scale%pn_expr => parse_node_get_sub_ptr (pn, 3)
  end subroutine cmd_fac_scale_compile
```

```
<Commands: procedures>+≡
  subroutine cmd_ren_scale_compile (scale, pn)
    type(cmd_ren_scale_t), pointer :: scale
    type(parse_node_t), intent(in), target :: pn
    allocate (scale)
    scale%pn_expr => parse_node_get_sub_ptr (pn, 3)
  end subroutine cmd_ren_scale_compile
```

Instead of evaluating the scale expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```
<Commands: procedures>+≡
  subroutine cmd_scale_execute (scale, global)
    type(cmd_scale_t), intent(inout), target :: scale
    type(rt_data_t), intent(inout), target :: global
    global%pn_scale_expr => scale%pn_expr
  end subroutine cmd_scale_execute
```

```
<Commands: procedures>+≡
  subroutine cmd_fac_scale_execute (scale, global)
    type(cmd_fac_scale_t), intent(inout), target :: scale
    type(rt_data_t), intent(inout), target :: global
    global%pn_fac_scale_expr => scale%pn_expr
  end subroutine cmd_fac_scale_execute
```

```
<Commands: procedures>+≡
  subroutine cmd_ren_scale_execute (scale, global)
    type(cmd_ren_scale_t), intent(inout), target :: scale
    type(rt_data_t), intent(inout), target :: global
    global%pn_ren_scale_expr => scale%pn_expr
  end subroutine cmd_ren_scale_execute
```

Weight

Define a weight expression. The weight is applied to a process to be integrated, event by event. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the process environment where the expression is used.

```
<Commands: types>+≡
  type :: cmd_weight_t
  private
  type(parse_node_t), pointer :: pn_expr => null ()
  end type cmd_weight_t
```

Compile. Simply store the parse (sub)tree.

```
<Commands: procedures>+≡
  subroutine cmd_weight_compile (weight, pn)
    type(cmd_weight_t), pointer :: weight
    type(parse_node_t), intent(in), target :: pn
    allocate (weight)
    weight%pn_expr => parse_node_get_sub_ptr (pn, 3)
  end subroutine cmd_weight_compile
```

Instead of evaluating the expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```
<Commands: procedures>+≡
  subroutine cmd_weight_execute (weight, global)
    type(cmd_weight_t), intent(inout), target :: weight
    type(rt_data_t), intent(inout), target :: global
```

```

    global%pn_weight_expr => weight%pn_expr
end subroutine cmd_weight_execute

```

Selection

Define a selection expression. This is to applied upon simulation or event-file rescanning, event by event. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the environment where the expression is used.

```

⟨Commands: types⟩+≡
    type :: cmd_selection_t
    private
        type(parse_node_t), pointer :: pn_expr => null ()
    end type cmd_selection_t

```

Compile. Simply store the parse (sub)tree.

```

⟨Commands: procedures⟩+≡
    subroutine cmd_selection_compile (selection, pn)
        type(cmd_selection_t), pointer :: selection
        type(parse_node_t), intent(in), target :: pn
        allocate (selection)
        selection%pn_expr => parse_node_get_sub_ptr (pn, 3)
    end subroutine cmd_selection_compile

```

Instead of evaluating the expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```

⟨Commands: procedures⟩+≡
    subroutine cmd_selection_execute (selection, global)
        type(cmd_selection_t), intent(inout), target :: selection
        type(rt_data_t), intent(inout), target :: global
        global%pn_selection_lexpr => selection%pn_expr
    end subroutine cmd_selection_execute

```

Reweight

Define a reweight expression. This is to applied upon simulation or event-file rescanning, event by event. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the environment where the expression is used.

```

⟨Commands: types⟩+≡
    type :: cmd_reweight_t
    private
        type(parse_node_t), pointer :: pn_expr => null ()
    end type cmd_reweight_t

```

Compile. Simply store the parse (sub)tree.

```

⟨Commands: procedures⟩+≡
    subroutine cmd_reweight_compile (reweight, pn)
        type(cmd_reweight_t), pointer :: reweight

```

```

    type(parse_node_t), intent(in), target :: pn
    allocate (reweight)
    reweight%pn_expr => parse_node_get_sub_ptr (pn, 3)
end subroutine cmd_reweight_compile

```

Instead of evaluating the expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```

<Commands: procedures>+≡
  subroutine cmd_reweight_execute (reweight, global)
    type(cmd_reweight_t), intent(inout), target :: reweight
    type(rt_data_t), intent(inout), target :: global
    global%pn_reweight_expr => reweight%pn_expr
  end subroutine cmd_reweight_execute

```

Integration

Integrate several processes, consecutively with identical parameters.

```

<Commands: types>+≡
  type :: cmd_integrate_t
  private
  integer :: n_proc = 0
  type(string_t), dimension(:), allocatable :: process_id
  type(command_list_t), pointer :: options => null ()
  type(rt_data_t) :: local
end type cmd_integrate_t

```

Finalizer.

```

<Commands: procedures>+≡
  subroutine cmd_integrate_final (integrate)
    type(cmd_integrate_t), intent(inout) :: integrate
    if (associated (integrate%options)) then
      call command_list_final (integrate%options)
      deallocate (integrate%options)
    end if
  end subroutine cmd_integrate_final

```

Compile.

```

<Commands: procedures>+≡
  subroutine cmd_integrate_compile (integrate, pn, global)
    type(cmd_integrate_t), pointer :: integrate
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_proclist, pn_proc, pn_opt
    integer :: i
    pn_proclist => parse_node_get_sub_ptr (pn, 2)
    pn_opt => parse_node_get_next_ptr (pn_proclist)
    allocate (integrate)
    call rt_data_local_init (integrate%local, global)
    if (associated (pn_opt)) then
      allocate (integrate%options)
      call command_list_compile (integrate%options, pn_opt, integrate%local)
    end if
  end subroutine cmd_integrate_compile

```

```

end if
integrate%n_proc = parse_node_get_n_sub (pn_proclist)
allocate (integrate%process_id (integrate%n_proc))
pn_proc => parse_node_get_sub_ptr (pn_proclist)
do i = 1, integrate%n_proc
    integrate%process_id(i) = parse_node_get_string (pn_proc)
    call var_list_init_process_results (global%var_list, &
        integrate%process_id (i))
    pn_proc => parse_node_get_next_ptr (pn_proc)
end do
call rt_data_local_reset (integrate%local)
end subroutine cmd_integrate_compile

```

Command execution. Integrate the process(es) with the predefined number of passes, iterations and calls. For structure functions, cuts, weight and scale, use local definitions if present; by default, the local definitions are initialized with the global ones.

(Re-)Integrating a decay process may invalidate a previous decay configuration, therefore we update the decay store.

Since the process acquires a snapshot of the variable list, so if the global list (or the local one) is deleted, this does no harm. This implies that later changes of the variable list do not affect the stored process.

(Commands: procedures)+≡

```

subroutine cmd_integrate_execute (integrate, global)
    type(cmd_integrate_t), intent(inout), target :: integrate
    type(rt_data_t), intent(inout), target :: global
    call rt_data_link (integrate%local, global)
    if (associated (integrate%options)) then
        call command_list_execute (integrate%options, integrate%local)
    end if
    call integrate_process &
        (integrate%process_id, integrate%local, global%var_list)
    call decay_store_update (integrate%process_id, verbose = .true.)
    call rt_data_restore (global, integrate%local)
end subroutine cmd_integrate_execute

```

Testing the Matrix Element

This command takes a process and evaluates the matrix element a given number of times, randomly choosing an integration channel.

(Commands: types)+≡

```

type :: cmd_me_test_t
    private
    type(string_t) :: process_id
    type(command_list_t), pointer :: options => null ()
    type(rt_data_t) :: local
end type cmd_me_test_t

```

Finalizer.

(Commands: procedures)+≡

```

subroutine cmd_me_test_final (me_test)

```



```

type(cmd_me_test_t), intent(inout) :: me_test
if (associated (me_test%options)) then
  call command_list_final (me_test%options)
  deallocate (me_test%options)
end if
end subroutine cmd_me_test_final

```

Compile.

(Commands: procedures)+≡

```

subroutine cmd_me_test_compile (me_test, pn, global)
  type(cmd_me_test_t), pointer :: me_test
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_proclist, pn_proc, pn_opt
  integer :: i
  pn_proclist => parse_node_get_sub_ptr (pn, 2)
  pn_opt => parse_node_get_next_ptr (pn_proclist)
  allocate (me_test)
  call rt_data_local_init (me_test%local, global)
  if (associated (pn_opt)) then
    allocate (me_test%options)
    call command_list_compile (me_test%options, pn_opt, me_test%local)
  end if
  pn_proc => parse_node_get_sub_ptr (pn_proclist)
  me_test%process_id = parse_node_get_string (pn_proc)
  call rt_data_local_reset (me_test%local)
end subroutine cmd_me_test_compile

```

Command execution. Call the matrix element of a process a predefined number of times. This requires all the prerequisites of an integration, but it ignores all cuts, and it throws away the values. The chosen momenta are random.

(Commands: procedures)+≡

```

subroutine cmd_me_test_execute (me_test, global)
  type(cmd_me_test_t), intent(inout), target :: me_test
  type(rt_data_t), intent(inout), target :: global
  call rt_data_link (me_test%local, global)
  if (associated (me_test%options)) then
    call command_list_execute (me_test%options, me_test%local)
  end if
  call me_test_process &
    (me_test%process_id, me_test%local, global%var_list)
  call rt_data_restore (global, me_test%local)
end subroutine cmd_me_test_execute

```

Observables

Declare an observable. After the declaration, it can be used to record data, and at the end one can retrieve average and error.

(Commands: types)+≡

```

type :: cmd_observable_t
private

```

```

    logical :: use_id_expr = .false.
    type(string_t) :: id
    type(parse_node_t), pointer :: pn_id => null ()
    type(command_list_t), pointer :: options => null ()
    type(rt_data_t) :: local
end type cmd_observable_t

```

Finalizer for the ID string expression

```

⟨Commands: procedures⟩+≡
subroutine cmd_observable_final (observable)
    type(cmd_observable_t), intent(inout) :: observable
    if (associated (observable%options)) then
        call command_list_final (observable%options)
        deallocate (observable%options)
    end if
end subroutine cmd_observable_final

```

Compile. Just record the observable ID.

```

⟨Commands: procedures⟩+≡
subroutine cmd_observable_compile (observable, pn, global)
    type(cmd_observable_t), pointer :: observable
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in), target :: global
    type(parse_node_t), pointer :: pn_tag, pn_opt
    pn_tag => parse_node_get_sub_ptr (pn, 2)
    if (associated (pn_tag)) then
        pn_opt => parse_node_get_next_ptr (pn_tag)
    else
        pn_opt => null ()
    end if
    allocate (observable)
    call rt_data_local_init (observable%local, global)
    if (associated (pn_opt)) then
        allocate (observable%options)
        call command_list_compile (observable%options, pn_opt, observable%local)
    end if
    select case (char (parse_node_get_rule_key (pn_tag)))
    case ("analysis_id")
        observable%id = parse_node_get_string (pn_tag)
    case default
        observable%use_id_expr = .true.
        observable%pn_id => pn_tag
    end select
    call rt_data_local_reset (observable%local)
end subroutine cmd_observable_compile

```

Command execution. This declares the observable and allocates it in the analysis store.

```

⟨Commands: procedures⟩+≡
subroutine cmd_observable_execute (observable, global)
    type(cmd_observable_t), intent(inout), target :: observable
    type(rt_data_t), intent(inout), target :: global

```

```

type(string_t) :: label, obs_unit, title
type(graph_options_t) :: graph_options
call rt_data_link (observable%local, global)
if (associated (observable%options)) then
    call command_list_execute (observable%options, observable%local)
end if
if (observable%use_id_expr) then
    observable%id = eval_string (observable%pn_id, observable%local%var_list)
end if
label = var_list_get_sval &
    (observable%local%var_list, var_str ("obs_label"))
obs_unit = var_list_get_sval &
    (observable%local%var_list, var_str ("obs_unit"))
title = var_list_get_sval (observable%local%var_list, var_str ("title"))
call graph_options_init (graph_options)
call analysis_init_observable &
    (observable%id, label, obs_unit, graph_options)
call rt_data_restore (global, observable%local)
end subroutine cmd_observable_execute

```

Histograms

Declare a histogram. At minimum, we have to set lower and upper bound and bin width.

```

<Commands: types>+≡
type :: cmd_histogram_t
private
type(string_t) :: id
logical :: use_id_expr = .false.
type(parse_node_t), pointer :: pn_id => null ()
type(parse_node_t), pointer :: pn_lower_bound => null ()
type(parse_node_t), pointer :: pn_upper_bound => null ()
type(parse_node_t), pointer :: pn_bin_width => null ()
type(command_list_t), pointer :: options => null ()
type(rt_data_t) :: local
end type cmd_histogram_t

```

Finalizer for the eval trees.

```

<Commands: procedures>+≡
subroutine cmd_histogram_final (histogram)
type(cmd_histogram_t), intent(inout) :: histogram
if (associated (histogram%options)) then
    call command_list_final (histogram%options)
    deallocate (histogram%options)
end if
end subroutine cmd_histogram_final

```

Compile. Record the histogram ID and initialize lower, upper bound and bin width.

```

<Commands: procedures>+≡
subroutine cmd_histogram_compile (histogram, pn, global)

```

```

type(cmd_histogram_t), pointer :: histogram
type(parse_node_t), intent(in), target :: pn
type(rt_data_t), intent(in), target :: global
type(parse_node_t), pointer :: pn_tag, pn_args, pn_arg1, pn_arg2, pn_arg3
type(parse_node_t), pointer :: pn_opt
character(*), parameter :: e_illegal_use = &
    "illegal usage of 'histogram': insufficient number of arguments"
pn_tag => parse_node_get_sub_ptr (pn, 2)
pn_args => parse_node_get_next_ptr (pn_tag)
if (associated (pn_args)) then
    pn_arg1 => parse_node_get_sub_ptr (pn_args)
    if (.not. associated (pn_arg1)) call msg_fatal (e_illegal_use)
    pn_arg2 => parse_node_get_next_ptr (pn_arg1)
    if (.not. associated (pn_arg2)) call msg_fatal (e_illegal_use)
    pn_arg3 => parse_node_get_next_ptr (pn_arg2)
    pn_opt => parse_node_get_next_ptr (pn_args)
else
    pn_opt => null ()
end if
allocate (histogram)
call rt_data_local_init (histogram%local, global)
if (associated (pn_opt)) then
    allocate (histogram%options)
    call command_list_compile (histogram%options, pn_opt, histogram%local)
end if
select case (char (parse_node_get_rule_key (pn_tag)))
case ("analysis_id")
    histogram%id = parse_node_get_string (pn_tag)
case default
    histogram%use_id_expr = .true.
    histogram%pn_id => pn_tag
end select
histogram%pn_lower_bound => pn_arg1
histogram%pn_upper_bound => pn_arg2
histogram%pn_bin_width => pn_arg3
call rt_data_local_reset (histogram%local)
end subroutine cmd_histogram_compile

```

Command execution. This declares the histogram and allocates it in the analysis store.

```

<Commands: procedures>+≡
subroutine cmd_histogram_execute (histogram, global)
type(cmd_histogram_t), intent(inout), target :: histogram
type(rt_data_t), intent(inout), target :: global
real(default) :: lower_bound, upper_bound, bin_width
integer :: bin_number
logical :: bin_width_is_used, normalize_bins
type(string_t) :: obs_label, obs_unit
type(graph_options_t) :: graph_options
type(drawing_options_t) :: drawing_options

call rt_data_link (histogram%local, global)
if (associated (histogram%options)) then

```

```

        call command_list_execute (histogram%options, histogram%local)
    end if

    if (histogram%use_id_expr) then
        histogram%id = eval_string (histogram%pn_id, histogram%local%var_list)
    end if

    lower_bound = eval_real (histogram%pn_lower_bound, histogram%local%var_list)
    upper_bound = eval_real (histogram%pn_upper_bound, histogram%local%var_list)
    if (associated (histogram%pn_bin_width)) then
        bin_width = eval_real (histogram%pn_bin_width, histogram%local%var_list)
        bin_width_is_used = .true.
    else if (var_list_is_known &
        (histogram%local%var_list, var_str ("n_bins"))) then
        bin_number = var_list_get_ival &
            (histogram%local%var_list, var_str ("n_bins"))
        bin_width_is_used = .false.
    else
        call msg_error ("Histogram '" // char (histogram%id) // &
            "': neither bin width nor number is defined")
    end if
    normalize_bins = var_list_get_lval &
        (histogram%local%var_list, var_str ("?normalize_bins"))
    obs_label = var_list_get_sval &
        (histogram%local%var_list, var_str ("$_obs_label"))
    obs_unit = var_list_get_sval &
        (histogram%local%var_list, var_str ("$_obs_unit"))

    call graph_options_init (graph_options)
    call set_graph_options (graph_options, histogram%local%var_list)
    call drawing_options_init_histogram (drawing_options)
    call set_drawing_options (drawing_options, histogram%local%var_list)

    if (bin_width_is_used) then
        call analysis_init_histogram &
            (histogram%id, lower_bound, upper_bound, bin_width, &
            normalize_bins, &
            obs_label, obs_unit, &
            graph_options, drawing_options)
    else
        call analysis_init_histogram &
            (histogram%id, lower_bound, upper_bound, bin_number, &
            normalize_bins, &
            obs_label, obs_unit, &
            graph_options, drawing_options)
    end if
    call rt_data_restore (global, histogram%local)

end subroutine cmd_histogram_execute

```

Set the graph options from a variable list.

(Commands: procedures)+≡

```

subroutine set_graph_options (gro, var_list)
    type(graph_options_t), intent(inout) :: gro

```

```

type(var_list_t), intent(in) :: var_list
call graph_options_set (gro, title = &
    var_list_get_sval (var_list, var_str ("title")))
call graph_options_set (gro, description = &
    var_list_get_sval (var_list, var_str ("description")))
call graph_options_set (gro, x_label = &
    var_list_get_sval (var_list, var_str ("x_label")))
call graph_options_set (gro, y_label = &
    var_list_get_sval (var_list, var_str ("y_label")))
call graph_options_set (gro, width_mm = &
    var_list_get_ival (var_list, var_str ("graph_width_mm")))
call graph_options_set (gro, height_mm = &
    var_list_get_ival (var_list, var_str ("graph_height_mm")))
call graph_options_set (gro, x_log = &
    var_list_get_lval (var_list, var_str ("x_log")))
call graph_options_set (gro, y_log = &
    var_list_get_lval (var_list, var_str ("y_log")))
if (var_list_is_known (var_list, var_str ("x_min"))) &
    call graph_options_set (gro, x_min = &
        var_list_get_rval (var_list, var_str ("x_min")))
if (var_list_is_known (var_list, var_str ("x_max"))) &
    call graph_options_set (gro, x_max = &
        var_list_get_rval (var_list, var_str ("x_max")))
if (var_list_is_known (var_list, var_str ("y_min"))) &
    call graph_options_set (gro, y_min = &
        var_list_get_rval (var_list, var_str ("y_min")))
if (var_list_is_known (var_list, var_str ("y_max"))) &
    call graph_options_set (gro, y_max = &
        var_list_get_rval (var_list, var_str ("y_max")))
call graph_options_set (gro, gmlcode_bg = &
    var_list_get_sval (var_list, var_str ("gmlcode_bg")))
call graph_options_set (gro, gmlcode_fg = &
    var_list_get_sval (var_list, var_str ("gmlcode_fg")))
end subroutine set_graph_options

```

Set the drawing options from a variable list.

(Commands: procedures)+≡

```

subroutine set_drawing_options (dro, var_list)
type(drawing_options_t), intent(inout) :: dro
type(var_list_t), intent(in) :: var_list
if (var_list_is_known (var_list, var_str ("draw_histogram"))) then
    if (var_list_get_lval (var_list, var_str ("draw_histogram"))) then
        call drawing_options_set (dro, with_hbars = .true.)
    else
        call drawing_options_set (dro, with_hbars = .false., &
            with_base = .false., fill = .false., piecewise = .false.)
    end if
end if
if (var_list_is_known (var_list, var_str ("draw_base"))) then
    if (var_list_get_lval (var_list, var_str ("draw_base"))) then
        call drawing_options_set (dro, with_base = .true.)
    else
        call drawing_options_set (dro, with_base = .false., fill = .false.)
    end if
end if

```

```

end if
if (var_list_is_known (var_list, var_str ("?draw_pieewise"))) then
  if (var_list_get_lval (var_list, var_str ("?draw_pieewise"))) then
    call drawing_options_set (dro, pieewise = .true.)
  else
    call drawing_options_set (dro, pieewise = .false.)
  end if
end if
if (var_list_is_known (var_list, var_str ("?fill_curve"))) then
  if (var_list_get_lval (var_list, var_str ("?fill_curve"))) then
    call drawing_options_set (dro, fill = .true., with_base = .true.)
  else
    call drawing_options_set (dro, fill = .false.)
  end if
end if
if (var_list_is_known (var_list, var_str ("?draw_curve"))) then
  if (var_list_get_lval (var_list, var_str ("?draw_curve"))) then
    call drawing_options_set (dro, draw = .true.)
  else
    call drawing_options_set (dro, draw = .false.)
  end if
end if
if (var_list_is_known (var_list, var_str ("?draw_errors"))) then
  if (var_list_get_lval (var_list, var_str ("?draw_errors"))) then
    call drawing_options_set (dro, err = .true.)
  else
    call drawing_options_set (dro, err = .false.)
  end if
end if
if (var_list_is_known (var_list, var_str ("?draw_symbols"))) then
  if (var_list_get_lval (var_list, var_str ("?draw_symbols"))) then
    call drawing_options_set (dro, symbols = .true.)
  else
    call drawing_options_set (dro, symbols = .false.)
  end if
end if
if (var_list_is_known (var_list, var_str ("$fill_options"))) then
  call drawing_options_set (dro, fill_options = &
    var_list_get_sval (var_list, var_str ("$fill_options")))
end if
if (var_list_is_known (var_list, var_str ("$draw_options"))) then
  call drawing_options_set (dro, draw_options = &
    var_list_get_sval (var_list, var_str ("$draw_options")))
end if
if (var_list_is_known (var_list, var_str ("$err_options"))) then
  call drawing_options_set (dro, err_options = &
    var_list_get_sval (var_list, var_str ("$err_options")))
end if
if (var_list_is_known (var_list, var_str ("$symbol"))) then
  call drawing_options_set (dro, symbol = &
    var_list_get_sval (var_list, var_str ("$symbol")))
end if
if (var_list_is_known (var_list, var_str ("$gmlcode_bg"))) then
  call drawing_options_set (dro, gmlcode_bg = &

```

```

        var_list_get_sval (var_list, var_str ("gmlcode_bg"))
    end if
    if (var_list_is_known (var_list, var_str ("gmlcode_fg"))) then
        call drawing_options_set (dro, gmlcode_fg = &
            var_list_get_sval (var_list, var_str ("gmlcode_fg")))
    end if
end subroutine set_drawing_options

```

Plots

Declare a plot. No mandatory arguments, just options.

<Commands: types>+≡

```

type :: cmd_plot_t
    private
    type(string_t) :: id
    logical :: use_id_expr = .false.
    type(parse_node_t), pointer :: pn_id => null ()
    type(command_list_t), pointer :: options => null ()
    type(rt_data_t) :: local
end type cmd_plot_t

```

Finalizer for the eval trees.

<Commands: procedures>+≡

```

subroutine cmd_plot_final (plot)
    type(cmd_plot_t), intent(inout) :: plot
    if (associated (plot%options)) then
        call command_list_final (plot%options)
        deallocate (plot%options)
    end if
end subroutine cmd_plot_final

```

Compile. Record the plot ID and initialize lower, upper bound and bin width.

<Commands: procedures>+≡

```

subroutine cmd_plot_compile (plot, pn, global)
    type(cmd_plot_t), pointer :: plot
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in), target :: global
    type(parse_node_t), pointer :: pn_tag
    type(parse_node_t), pointer :: pn_opt
    pn_tag => parse_node_get_sub_ptr (pn, 2)
    pn_opt => parse_node_get_next_ptr (pn_tag)
    allocate (plot)
    call cmd_plot_init (plot, pn_tag, pn_opt, global)
end subroutine cmd_plot_compile

```

This init routine is separated because it is reused below for graph initialization.

<Commands: procedures>+≡

```

subroutine cmd_plot_init (plot, pn_tag, pn_opt, global)
    type(cmd_plot_t), intent(out) :: plot
    type(parse_node_t), intent(in), pointer :: pn_tag, pn_opt
    type(rt_data_t), intent(in), target :: global

```



```

call rt_data_local_init (plot%local, global)
if (associated (pn_opt)) then
  allocate (plot%options)
  call command_list_compile (plot%options, pn_opt, plot%local)
end if
select case (char (parse_node_get_rule_key (pn_tag)))
case ("analysis_id")
  plot%id = parse_node_get_string (pn_tag)
case default
  plot%use_id_expr = .true.
  plot%pn_id => pn_tag
end select
call rt_data_local_reset (plot%local)
end subroutine cmd_plot_init

```

Command execution. This declares the plot and allocates it in the analysis store.

```

<Commands: procedures>+≡
subroutine cmd_plot_execute (plot, global)
  type(cmd_plot_t), intent(inout), target :: plot
  type(rt_data_t), intent(inout), target :: global
  type(graph_options_t) :: graph_options
  type(drawing_options_t) :: drawing_options

  call rt_data_link (plot%local, global)
  if (associated (plot%options)) then
    call command_list_execute (plot%options, plot%local)
  end if

  if (plot%use_id_expr) then
    plot%id = eval_string (plot%pn_id, plot%local%var_list)
  end if

  call graph_options_init (graph_options)
  call set_graph_options (graph_options, plot%local%var_list)
  call drawing_options_init_plot (drawing_options)
  call set_drawing_options (drawing_options, plot%local%var_list)

  call analysis_init_plot (plot%id, graph_options, drawing_options)

  call rt_data_restore (global, plot%local)

end subroutine cmd_plot_execute

```

Graphs

Declare a graph. The graph is defined in terms of its contents. Both the graph and its contents may carry options.

The graph object contains its own ID as well as the IDs of its elements. For the elements, we reuse the `cmd_plot_t` defined above.

```

<Commands: types>+≡
type :: cmd_graph_t

```

```

private
type(string_t) :: id
type(parse_node_t), pointer :: pn_id
logical :: use_id_expr = .false.
integer :: n_elements = 0
type(cmd_plot_t), dimension(:), allocatable :: el
type(command_list_t), pointer :: options => null ()
type(rt_data_t) :: local
end type cmd_graph_t

```

Finalizer for the eval trees.

```

⟨Commands: procedures⟩+≡
subroutine cmd_graph_final (graph)
  type(cmd_graph_t), intent(inout) :: graph
  integer :: i
  if (allocated (graph%el)) then
    do i = 1, size (graph%el)
      call cmd_plot_final (graph%el(i))
    end do
    deallocate (graph%el)
  end if
  if (associated (graph%options)) then
    call command_list_final (graph%options)
    deallocate (graph%options)
  end if
end subroutine cmd_graph_final

```

Compile. Record the graph ID and initialize lower, upper bound and bin width. For compiling the graph element syntax, we use part of the `cmd_plot_t` compiler.

```

⟨Commands: procedures⟩+≡
subroutine cmd_graph_compile (graph, pn, global)
  type(cmd_graph_t), pointer :: graph
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(in), target :: global
  type(parse_node_t), pointer :: pn_term, pn_tag, pn_opt, pn_def, pn_app
  integer :: i

  pn_term => parse_node_get_sub_ptr (pn, 2)
  pn_tag => parse_node_get_sub_ptr (pn_term)
  pn_opt => parse_node_get_next_ptr (pn_tag)
  allocate (graph)
  call rt_data_local_init (graph%local, global)
  if (associated (pn_opt)) then
    allocate (graph%options)
    call command_list_compile (graph%options, pn_opt, graph%local)
  end if
  select case (char (parse_node_get_rule_key (pn_tag)))
  case ("analysis_id")
    graph%id = parse_node_get_string (pn_tag)
  case default
    graph%use_id_expr = .true.
    graph%pn_id => pn_tag
  end select
end subroutine cmd_graph_compile

```

```

end select
pn_def => parse_node_get_next_ptr (pn_term, 2)
graph%n_elements = parse_node_get_n_sub (pn_def)
call rt_data_local_reset (graph%local)

allocate (graph%el (graph%n_elements))
pn_term => parse_node_get_sub_ptr (pn_def)
pn_tag => parse_node_get_sub_ptr (pn_term)
pn_opt => parse_node_get_next_ptr (pn_tag)
call cmd_plot_init (graph%el(1), pn_tag, pn_opt, global)
pn_app => parse_node_get_next_ptr (pn_term)
do i = 2, graph%n_elements
  pn_term => parse_node_get_sub_ptr (pn_app, 2)
  pn_tag => parse_node_get_sub_ptr (pn_term)
  pn_opt => parse_node_get_next_ptr (pn_tag)
  call cmd_plot_init (graph%el(i), pn_tag, pn_opt, global)
  pn_app => parse_node_get_next_ptr (pn_app)
end do

end subroutine cmd_graph_compile

```

Command execution. This declares the graph, allocates it in the analysis store, and copies the graph elements.

For the graph, we set graph and default drawing options. For the elements, we reset individual drawing options.

This accesses internals of the contained elements of type `cmd_plot_t`, see above. We might disentangle such an interdependency when this code is rewritten using proper type extension.

(Commands: procedures)+≡

```

subroutine cmd_graph_execute (graph, global)
  type(cmd_graph_t), intent(inout), target :: graph
  type(rt_data_t), intent(inout), target :: global
  type(graph_options_t) :: graph_options
  type(drawing_options_t) :: drawing_options
  integer :: i, type

  call rt_data_link (graph%local, global)
  if (associated (graph%options)) then
    call command_list_execute (graph%options, graph%local)
  end if

  if (graph%use_id_expr) then
    graph%id = eval_string (graph%pn_id, graph%local%var_list)
  end if

  call graph_options_init (graph_options)
  call set_graph_options (graph_options, graph%local%var_list)
  call analysis_init_graph (graph%id, graph%n_elements, graph_options)

  do i = 1, graph%n_elements
    call rt_data_link (graph%el(i)%local, global)
    if (associated (graph%el(i)%options)) then
      call command_list_execute (graph%el(i)%options, graph%el(i)%local)
    end if
  end do
end subroutine cmd_graph_execute

```

```

        end if
        if (graph%el(i)%use_id_expr) then
            graph%el(i)%id = &
                eval_string (graph%el(i)%pn_id, graph%el(i)%local%var_list)
        end if
        type = analysis_store_get_object_type (graph%el(i)%id)
        select case (type)
        case (AN_HISTOGRAM)
            call drawing_options_init_histogram (drawing_options)
        case (AN_PLOT)
            call drawing_options_init_plot (drawing_options)
        end select
        call set_drawing_options (drawing_options, graph%local%var_list)
        if (associated (graph%el(i)%options)) then
            call set_drawing_options (drawing_options, graph%el(i)%local%var_list)
        end if
        call analysis_fill_graph (graph%id, i, graph%el(i)%id, drawing_options)
        call rt_data_restore (global, graph%el(i)%local)
    end do

    call rt_data_restore (global, graph%local)

end subroutine cmd_graph_execute

```

Analysis

Hold the analysis ID either as a string or as an expression:

```

<Commands: types>+≡
    type :: analysis_id_t
    type(string_t) :: tag
    type(parse_node_t), pointer :: pn_sexpr => null ()
end type analysis_id_t

```

Define the analysis expression. We store the parse tree for the right-hand side instead of compiling it. Compilation is deferred to the process environment where the analysis expression is used.

```

<Commands: types>+≡
    type :: cmd_analysis_t
    private
    type(parse_node_t), pointer :: pn_lexpr => null ()
end type cmd_analysis_t

```

Compile. Simply store the parse (sub)tree.

```

<Commands: procedures>+≡
    subroutine cmd_analysis_compile (analysis, pn)
        type(cmd_analysis_t), pointer :: analysis
        type(parse_node_t), intent(in), target :: pn
        allocate (analysis)
        analysis%pn_lexpr => parse_node_get_sub_ptr (pn, 3)
    end subroutine cmd_analysis_compile

```

Instead of evaluating the cut expression, link the parse tree to the global data set, such that it is compiled and executed in the appropriate process context.

```
(Commands: procedures)+≡
subroutine cmd_analysis_execute (analysis, global)
  type(cmd_analysis_t), intent(inout), target :: analysis
  type(rt_data_t), intent(inout), target :: global
  global%pn_analysis_lexpr => analysis%pn_lexpr
end subroutine cmd_analysis_execute
```

Clear analysis objects

The syntax is analogous to `compile_analysis`. Each argument clears a particular analysis object. No argument clears the whole analysis store. The objects are cleared, but not deleted.

```
(Commands: types)+≡
type :: cmd_clear_t
  private
  integer :: n_args = 0
  type(string_t), dimension(:), allocatable :: id
  logical, dimension(:), allocatable :: use_id_expr
  type(parse_node_p), dimension(:), allocatable :: pn_id
end type cmd_clear_t
```

Finalizer for the eval trees.

```
(Commands: procedures)+≡
subroutine cmd_clear_final (clear)
  type(cmd_clear_t), intent(inout) :: clear
  if (allocated (clear%pn_id)) deallocate (clear%pn_id)
end subroutine cmd_clear_final
```

Compile. Record the clear ID and initialize lower, upper bound and bin width.

```
(Commands: procedures)+≡
subroutine cmd_clear_compile (clear, pn, global)
  type(cmd_clear_t), pointer :: clear
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(in), target :: global
  type(parse_node_t), pointer :: pn_args, pn_tag
  type(string_t) :: key
  integer :: i
  pn_args => parse_node_get_sub_ptr (pn, 2)
  allocate (clear)
  if (associated (pn_args)) then
    clear%n_args = parse_node_get_n_sub (pn_args)
    allocate (clear%id (clear%n_args), clear%use_id_expr (clear%n_args))
    clear%use_id_expr = .false.
    allocate (clear%pn_id (clear%n_args))
    pn_tag => parse_node_get_sub_ptr (pn_args)
    i = 1
    do while (associated (pn_tag))
      key = parse_node_get_rule_key (pn_tag)
      select case (char (key))
```

```

        case ("iterations", "cuts", "weight", "scale", "factorization_scale", &
              "renormalization_scale", "analysis", "expect")
            clear%id(i) = key
        case ("analysis_id")
            clear%id(i) = parse_node_get_string (pn_tag)
        case default
            clear%pn_id(i)%ptr => pn_tag
        end select
        i = i + 1
        pn_tag => parse_node_get_next_ptr (pn_tag)
    end do
end if
end subroutine cmd_clear_compile

```

Command execution.

(Commands: procedures)+≡

```

subroutine cmd_clear_execute (clear, global)
    type(cmd_clear_t), intent(inout), target :: clear
    type(rt_data_t), intent(inout), target :: global
    integer :: i
    if (clear%n_args == 0) then
        call analysis_clear ()
        call msg_message ("Cleared all analysis objects")
    else
        do i = 1, clear%n_args
            select case (char (clear%id(i)))
            case ("iterations")
                call iterations_list_clear (global%it_list)
                call msg_message ("Cleared iteration list setup")
            case ("cuts")
                global%pn_cuts_lexpr => null ()
                call msg_message ("Cleared cut setup")
            case ("weight")
                global%pn_weight_expr => null ()
                call msg_message ("Cleared integration weight setup")
            case ("scale")
                global%pn_scale_expr => null ()
                call msg_message ("Cleared general scale setup")
            case ("factorization_scale")
                global%pn_fac_scale_expr => null ()
                call msg_message ("Cleared factorization scale setup")
            case ("renormalization_scale")
                global%pn_ren_scale_expr => null ()
                call msg_message ("Cleared renormalization scale setup")
            case ("analysis")
                global%pn_analysis_lexpr => null ()
                call msg_message ("Cleared analysis setup")
            case ("expect")
                call expect_clear ()
                call msg_message ("Cleared counters of value checks")
            case default
                if (clear%use_id_expr(i)) then
                    clear%id(i) = eval_string (clear%pn_id(i)%ptr, global%var_list)
                end if
            end select
        end do
    end if
end subroutine cmd_clear_execute

```

```

        call analysis_clear (clear%id(i))
        call msg_message ("Cleared analysis object '" &
            // char (clear%id(i)) // "'")
    end select
end do
end if
end subroutine cmd_clear_execute

```

Write histograms and plots

The data type encapsulating the command:

(Commands: types)+≡

```

type :: cmd_write_analysis_t
    type(analysis_id_t), dimension(:), allocatable :: id
    type(string_t), dimension(:), allocatable :: tag
    type(rt_data_t) :: local
    type(command_list_t), pointer :: options => null ()
end type cmd_write_analysis_t

```

(Commands: procedures)+≡

```

subroutine cmd_write_analysis_final (write_analysis)
    type(cmd_write_analysis_t), intent(inout) :: write_analysis
    if (allocated (write_analysis%id)) deallocate (write_analysis%id)
    if (allocated (write_analysis%tag)) deallocate (write_analysis%tag)
    if (associated (write_analysis%options)) then
        call command_list_final (write_analysis%options)
        deallocate (write_analysis%options)
    end if
end subroutine cmd_write_analysis_final

```

Compile.

(Commands: procedures)+≡

```

subroutine cmd_write_analysis_compile (write_analysis, pn, global)
    type(cmd_write_analysis_t), intent(inout), pointer :: write_analysis
    type(parse_node_t), intent(in) :: pn
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_clause, pn_opts, pn_args, pn_id
    integer :: n, i
    pn_clause => parse_node_get_sub_ptr (pn)
    pn_args => parse_node_get_sub_ptr (pn_clause, 2)
    pn_opts => parse_node_get_next_ptr (pn_clause)
    allocate (write_analysis)
    call rt_data_local_init (write_analysis%local, global)
    if (associated (pn_opts)) then
        allocate (write_analysis%options)
        call command_list_compile &
            (write_analysis%options, pn_opts, write_analysis%local)
    end if
    if (associated (pn_args)) then
        n = parse_node_get_n_sub (pn_args)
        allocate (write_analysis%id (n))
    end if
end subroutine cmd_write_analysis_compile

```

```

do i = 1, n
  pn_id => parse_node_get_sub_ptr (pn_args, i)
  if (char (parse_node_get_rule_key (pn_id)) == "analysis_id") then
    write_analysis%id(i)%tag = parse_node_get_string (pn_id)
  else
    write_analysis%id(i)%pn_sexpr => pn_id
  end if
end do
else
  allocate (write_analysis%id (0))
end if
call rt_data_local_reset (write_analysis%local)
end subroutine cmd_write_analysis_compile

```

The output format for real data values:

```

(Limits: public parameters)+≡
character(*), parameter, public :: &
  DEFAULT_ANALYSIS_FILENAME = "whizard_analysis.dat"
character(len=1), dimension(2), parameter, public :: &
  FORBIDDEN_ENDINGS1 = (/ "o", "a" /)
character(len=2), dimension(5), parameter, public :: &
  FORBIDDEN_ENDINGS2 = (/ "mp", "ps", "vg", "lo", "la" /)
character(len=3), dimension(13), parameter, public :: &
  FORBIDDEN_ENDINGS3 = (/ "aux", "dvi", "evx", "f03", "f90", "log", &
    "ltp", "mpx", "pdf", "phs", "sin", "tex", "vbg" /)

```

Execute. If the `data_filename` optional argument is present, this is called from `cmd_compile_analysis_execute`, which needs the file name for further processing, and requires the default format. Otherwise, we use the parameters and macros for custom data processing.

```

(Commands: procedures)+≡
subroutine cmd_write_analysis_execute &
  (write_analysis, global, data_file, write_yerr, write_xerr)
  type(cmd_write_analysis_t), intent(inout), target :: write_analysis
  type(rt_data_t), intent(inout), target :: global
  type(string_t), intent(out), optional :: data_file
  logical, intent(out), optional :: write_yerr, write_xerr
  type(string_t) :: defaultfile, file
  logical :: keep_open, custom, header, columns
  type(string_t) :: comment_prefix, separator, extension
  integer :: i, type
  type(ifile_t) :: ifile
  logical :: one_file, has_writer
  type(analysis_iterator_t) :: iterator
  type(rt_data_t), target :: sandbox
  type(command_list_t) :: writer

  call rt_data_link (write_analysis%local, global)
  if (associated (write_analysis%options)) then
    call command_list_execute (write_analysis%options, write_analysis%local)
  end if

  defaultfile = var_list_get_sval (write_analysis%local%var_list, &

```



```

        var_str ("out_file"))
if (present (data_file)) then
  if (defaultfile == "" .or. defaultfile == ".") then
    defaultfile = DEFAULT_ANALYSIS_FILENAME
  else
    if (scan(".", defaultfile) > 0) then
      call split (defaultfile, extension, ".", back=.true.)
      if (any (lower_case (char(extension)) == FORBIDDEN_ENDINGS1) .or. &
          any (lower_case (char(extension)) == FORBIDDEN_ENDINGS2) .or. &
          any (lower_case (char(extension)) == FORBIDDEN_ENDINGS3)) &
          call msg_fatal ("The ending " // char(extension) // &
              " is internal and not allowed as data file.")
      if (extension /= "") then
        if (defaultfile /= "") then
          defaultfile = defaultfile // "." // extension
        else
          defaultfile = "whizard_analysis." // extension
        end if
      else
        defaultfile = defaultfile // ".dat"
      endif
    else
      defaultfile = defaultfile // ".dat"
    end if
  end if
  data_file = defaultfile
end if
one_file = defaultfile /= ""
if (one_file) then
  file = defaultfile
  keep_open = file_list_is_open (global%out_files, file, &
      action = "write")
  if (keep_open) then
    if (present (data_file)) then
      call msg_fatal ("Compiling analysis: File '" &
          // char (data_file) &
          // "' can't be used, it is already open.")
    else
      call msg_message ("Appending analysis data to file '" &
          // char (file) // "'")
    end if
  else
    print *, "calling file_list_open from cmd_write_analysis_execute"
    call file_list_open (global%out_files, file, &
        action = "write", status = "replace", position = "asis")
    call msg_message ("Writing analysis data to file '" &
        // char (file) // "'")
  end if
end if

if (present (data_file)) then
  custom = .false.
else
  custom = var_list_get_lval (write_analysis%local%var_list, &

```

```

        var_str ("?out_custom"))
end if
comment_prefix = var_list_get_sval (write_analysis%local%var_list, &
    var_str ("?out_comment"))
separator = var_list_get_sval (write_analysis%local%var_list, &
    var_str ("?out_separator"))
columns = var_list_get_lval (write_analysis%local%var_list, &
    var_str ("?out_columns"))
header = var_list_get_lval (write_analysis%local%var_list, &
    var_str ("?out_header"))
call get_analysis_tags (write_analysis%tag, write_analysis%id, &
    write_analysis%local%var_list)
if (present (write_yerr)) then
    write_yerr = var_list_get_lval (write_analysis%local%var_list, &
        var_str ("?out_yerr"))
end if
if (present (write_xerr)) then
    write_xerr = var_list_get_lval (write_analysis%local%var_list, &
        var_str ("?out_xerr"))
end if

do i = 1, size (write_analysis%tag)
    if (custom) then
        type = analysis_store_get_object_type (write_analysis%tag(i))
        call compile_writer (writer, type, has_writer)
        if (has_writer) then
            call rt_data_link (sandbox, write_analysis%local)
        end if
        if (.not. one_file) then
            file = write_analysis%tag(i) // ".dat"
            call file_list_open (global%out_files, file, &
                action = "write", status = "replace", position = "asis")
            call msg_message ("Writing analysis data to file '" &
                // char (file) // "'")
        end if
        if (header) then
            call analysis_get_header &
                (write_analysis%tag(i), ifile, comment_prefix)
            call file_list_write (global%out_files, file, ifile)
            call ifile_final (ifile)
        end if
        call analysis_init_iterator (write_analysis%tag(i), iterator)
        do while (analysis_iterator_is_valid (iterator))
            call write_data (iterator, &
                writer, sandbox, file, columns, separator)
            call analysis_iterator_advance (iterator)
        end do
        if (.not. one_file) then
            call file_list_close (global%out_files, file)
        end if
        if (has_writer) then
            call rt_data_restore (write_analysis%local, sandbox)
            call var_list_final (sandbox%var_list)
            call command_list_final (writer)
        end if
    end if
end do

```

```

        end if
    else
        call file_list_write_analysis &
            (global%out_files, file, write_analysis%tag(i))
    end if
end do

if (one_file .and. .not. keep_open) then
    call file_list_close (global%out_files, file)
end if
call rt_data_restore (global, write_analysis%local)

contains

subroutine get_analysis_tags (analysis_tag, id, var_list)
    type(string_t), dimension(:), intent(out), allocatable :: analysis_tag
    type(analysis_id_t), dimension(:), intent(in) :: id
    type(var_list_t), intent(in), target :: var_list
    if (size (id) /= 0) then
        allocate (analysis_tag (size (id)))
        do i = 1, size (id)
            if (associated (id(i)%pn_sexpr)) then
                analysis_tag(i) = eval_string (id(i)%pn_sexpr, var_list)
            else
                analysis_tag(i) = id(i)%tag
            end if
        end do
    else
        call analysis_store_get_ids (analysis_tag)
    end if
end subroutine get_analysis_tags

subroutine compile_writer (writer, type, has_writer)
    type(command_list_t), intent(out) :: writer
    integer, intent(in) :: type
    logical, intent(out) :: has_writer
    select case (type)
    case (AN_HISTOGRAM)
        has_writer = associated (write_analysis%local%pn_histogram_writer)
        if (has_writer) then
            call histogram_writer_compile (writer, &
                write_analysis%local%pn_histogram_writer, sandbox, &
                write_analysis%local)
        end if
    case (AN_PLOT)
        has_writer = associated (write_analysis%local%pn_plot_writer)
        if (has_writer) then
            call plot_writer_compile (writer, &
                write_analysis%local%pn_plot_writer, sandbox, &
                write_analysis%local)
        end if
    case default
        has_writer = .false.
        call msg_error ("Custom output format " &

```

```

        // "is applicable only to elementary histograms and plots")
    end select
end subroutine compile_writer

subroutine write_data (iterator, writer, sandbox, file, columns, separator)
    type(analysis_iterator_t), intent(inout) :: iterator
    type(command_list_t), intent(in) :: writer
    type(rt_data_t), intent(inout), target :: sandbox
    type(string_t), intent(in) :: file
    logical, intent(in) :: columns
    type(string_t), intent(in) :: separator
    real(default) :: x, y, yerr, xerr, excess, width
    integer :: bin_index, n_bins, point_index, n_points
    character(*), parameter :: &
        OUT_REAL_FMT = '(' // HISTOGRAM_DATA_FORMAT // ')'
    select case (analysis_iterator_get_type (iterator))
    case (AN_HISTOGRAM)
        call analysis_iterator_get_data (iterator, &
            x = x, y = y, yerr = yerr, width = width, excess = excess, &
            index = bin_index, n_total = n_bins)
        if (has_writer) then
            call histogram_writer_execute (writer, sandbox, file, &
                x, width, y, yerr, excess, bin_index, n_bins)
        else if (columns) then
            call file_list_write (global%out_files, file, &
                real2string (x, OUT_REAL_FMT) // separator // &
                real2string (y, OUT_REAL_FMT) // separator // &
                real2string (yerr, OUT_REAL_FMT))
        else
            call file_list_write (global%out_files, file, &
                real2string (x) // separator // &
                real2string (y) // separator // &
                real2string (yerr))
        end if
    case (AN_PLOT)
        call analysis_iterator_get_data (iterator, &
            x = x, y = y, yerr = yerr, xerr = xerr, &
            index = point_index, n_total = n_points)
        if (has_writer) then
            call plot_writer_execute (writer, sandbox, file, &
                x, y, yerr, xerr, point_index, n_points)
        else if (columns) then
            call file_list_write (global%out_files, file, &
                real2string (x, OUT_REAL_FMT) // separator // &
                real2string (y, OUT_REAL_FMT) // separator // &
                real2string (yerr, OUT_REAL_FMT) // separator // &
                real2string (xerr, OUT_REAL_FMT))
        else
            call file_list_write (global%out_files, file, &
                real2string (x) // separator // &
                real2string (y) // separator // &
                real2string (yerr) // separator // &
                real2string (xerr))
        end if
    end if
end if

```

```

        end select
    end subroutine write_data

end subroutine cmd_write_analysis_execute

```

Compile the histogram/plot writer: initialize special variables and compile the parse tree.

```

<Commands: procedures>+≡
  subroutine histogram_writer_compile (writer, pn, local, global)
    type(command_list_t), intent(out) :: writer
    type(parse_node_t), intent(in) :: pn
    type(rt_data_t), intent(inout), target :: local
    type(rt_data_t), intent(in), target :: global
    call rt_data_local_init (local, global)
    call var_list_append_real (local%var_list, &
      var_str ("bin_center"), intrinsic=.true.)
    call var_list_append_real (local%var_list, &
      var_str ("bin_width"), intrinsic=.true.)
    call var_list_append_real (local%var_list, &
      var_str ("bin_sum"), intrinsic=.true.)
    call var_list_append_real (local%var_list, &
      var_str ("bin_error"), intrinsic=.true.)
    call var_list_append_real (local%var_list, &
      var_str ("bin_excess"), intrinsic=.true.)
    call var_list_append_int (local%var_list, &
      var_str ("bin_index"), intrinsic=.true.)
    call var_list_append_int (local%var_list, &
      var_str ("n_bins"), intrinsic=.true.)
    call var_list_append_string (local%var_list, &
      var_str ("out_file"), intrinsic=.true.)
    call command_list_compile (writer, pn, local)
    call rt_data_local_reset (local)
  end subroutine histogram_writer_compile

  subroutine plot_writer_compile (writer, pn, local, global)
    type(command_list_t), intent(out) :: writer
    type(parse_node_t), intent(in) :: pn
    type(rt_data_t), intent(inout), target :: local
    type(rt_data_t), intent(in), target :: global
    call rt_data_local_init (local, global)
    call var_list_append_real (local%var_list, &
      var_str ("point_x"), intrinsic=.true.)
    call var_list_append_real (local%var_list, &
      var_str ("point_y"), intrinsic=.true.)
    call var_list_append_real (local%var_list, &
      var_str ("point_yerr"), intrinsic=.true.)
    call var_list_append_real (local%var_list, &
      var_str ("point_xerr"), intrinsic=.true.)
    call var_list_append_int (local%var_list, &
      var_str ("point_index"), intrinsic=.true.)
    call var_list_append_int (local%var_list, &
      var_str ("n_points"), intrinsic=.true.)
    call var_list_append_string (local%var_list, &

```

```

        var_str ("out_file"), intrinsic=.true.)
    call command_list_compile (writer, pn, local)
    call rt_data_local_reset (local)
end subroutine plot_writer_compile

```

Execute the histogram/plot writer: set special variables and execute the command list.

(Commands: procedures)+≡

```

subroutine histogram_writer_execute (writer, local, filename, &
    x, width, y, yerr, excess, bin_index, n_bins)
    type(command_list_t), intent(in) :: writer
    type(rt_data_t), intent(inout), target :: local
    type(string_t), intent(in) :: filename
    real(default), intent(in) :: x, width, y, yerr, excess
    integer, intent(in) :: bin_index, n_bins
    call var_list_set_real (local%var_list, &
        var_str ("bin_center"), x, is_known=.true.)
    call var_list_set_real (local%var_list, &
        var_str ("bin_width"), width, is_known=.true.)
    call var_list_set_real (local%var_list, &
        var_str ("bin_sum"), y, is_known=.true.)
    call var_list_set_real (local%var_list, &
        var_str ("bin_error"), yerr, is_known=.true.)
    call var_list_set_real (local%var_list, &
        var_str ("bin_excess"), excess, is_known=.true.)
    call var_list_set_int (local%var_list, &
        var_str ("bin_index"), bin_index, is_known=.true.)
    call var_list_set_int (local%var_list, &
        var_str ("n_bins"), n_bins, is_known=.true.)
    call var_list_set_string (local%var_list, &
        var_str ("out_file"), filename, is_known=.true.)
    call command_list_execute (writer, local)
end subroutine histogram_writer_execute

subroutine plot_writer_execute (writer, local, filename, &
    x, y, yerr, xerr, point_index, n_points)
    type(command_list_t), intent(in) :: writer
    type(rt_data_t), intent(inout), target :: local
    type(string_t), intent(in) :: filename
    real(default), intent(in) :: x, y, yerr, xerr
    integer, intent(in) :: point_index, n_points
    call var_list_set_real (local%var_list, &
        var_str ("point_x"), x, is_known=.true.)
    call var_list_set_real (local%var_list, &
        var_str ("point_y"), y, is_known=.true.)
    call var_list_set_real (local%var_list, &
        var_str ("point_yerr"), yerr, is_known=.true.)
    call var_list_set_real (local%var_list, &
        var_str ("point_xerr"), xerr, is_known=.true.)
    call var_list_set_int (local%var_list, &
        var_str ("point_index"), point_index, is_known=.true.)
    call var_list_set_int (local%var_list, &
        var_str ("n_points"), n_points, &

```

```

        is_known=.true.)
    call var_list_set_string (local%var_list, &
        var_str ("%out_file"), filename, is_known=.true.)
    call command_list_execute (writer, local)
end subroutine plot_writer_execute

```

Defining writer macros

The following definitions are for the `histogram_writer` and `plot_writer` special variables. As they don't do much and are useful only in conjunction with `write_analysis` anyway, we don't open a separate section for them.

(Commands: types)+≡

```

type :: cmd_xxx_writer_t
    type(parse_node_t), pointer :: macro => null ()
    integer :: type = CMD_HISTOGRAM_WRITER
end type cmd_xxx_writer_t

```

(Commands: procedures)+≡

```

subroutine cmd_xxx_writer_final (writer)
    type(cmd_xxx_writer_t), intent(inout) :: writer
    nullify (writer%macro)
    writer%type = CMD_HISTOGRAM_WRITER
end subroutine cmd_xxx_writer_final

```

```

subroutine cmd_xxx_writer_compile (writer, pn, global)
    type(cmd_xxx_writer_t), intent(inout), pointer :: writer
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in) :: global
    allocate (writer)
    select case (char (parse_node_get_rule_key (pn)))
        case ("cmd_histogram_writer")
            writer%type = CMD_HISTOGRAM_WRITER
        case ("cmd_plot_writer")
            writer%type = CMD_PLOT_WRITER
        case default
            call msg_bug ("cmd_xxx_writer_compile: invalid type")
    end select
    writer%macro => parse_node_get_sub_ptr (pn, 3)
end subroutine cmd_xxx_writer_compile

```

```

subroutine cmd_xxx_writer_execute (writer, global)
    type(cmd_xxx_writer_t), intent(in), target :: writer
    type(rt_data_t), intent(inout), target :: global
    if (.not. associated (writer%macro)) return
    select case (writer%type)
        case (CMD_HISTOGRAM_WRITER)
            global%pn_histogram_writer => writer%macro
        case (CMD_PLOT_WRITER)
            global%pn_plot_writer => writer%macro
        case default
            call msg_bug ("cmd_xxx_writer_execute: invalid type")
    end select

```

```
end subroutine cmd_xxx_writer_execute
```

Compile analysis results

This command writes files in a form suitable for GAMELAN and executes the appropriate commands to compile them. It reuses the `cmd_write_analysis_t` container defined above.

(Commands: procedures)+≡

```
subroutine cmd_compile_analysis_execute (write, global)
  type(cmd_write_analysis_t), intent(inout), target :: write
  type(rt_data_t), intent(inout), target :: global
  type(string_t) :: data_file, basename, extension, driver_file
  integer :: u_driver, i
  logical :: has_gmlcode, write_yerr, write_xerr
  call cmd_write_analysis_execute &
    (write, global, data_file, write_yerr, write_xerr)
  basename = data_file
  if (scan(".", basename) > 0) then
    call split (basename, extension, ".", back=.true.)
  else
    extension = ""
  end if
  driver_file = basename // ".tex"
  u_driver = free_unit ()
  open (unit=u_driver, file=char(driver_file), &
    action="write", status="replace")
  call analysis_write_driver &
    (data_file, write%tag, unit=u_driver)
  close (u_driver)
  if (size (write%tag) == 0) then
    has_gmlcode = analysis_has_plots ()
  else
    has_gmlcode = analysis_has_plots (write%tag)
  end if
  call msg_message ("Compiling analysis results display in '" &
    // char (driver_file) // "'")
  call analysis_compile_tex (basename, has_gmlcode, global%os_data)
end subroutine cmd_compile_analysis_execute
```

17.2 User-controlled output to data files

Open file (output)

Open a file for output.

(Commands: types)+≡

```
type :: cmd_open_t
  private
  type(parse_node_t), pointer :: pn_sexpr => null ()
  logical :: reading = .false.
  logical :: writing = .false.
```



```

        type(command_list_t), pointer :: options => null ()
        type(rt_data_t) :: local
    end type cmd_open_t

```

(Commands: procedures)+≡

```

    subroutine cmd_open_final (open)
        type(cmd_open_t), intent(inout) :: open
        if (associated (open%options)) then
            call command_list_final (open%options)
            deallocate (open%options)
        end if
    end subroutine cmd_open_final

    subroutine cmd_open_out_compile (open, pn, global)
        type(cmd_open_t), intent(out), pointer :: open
        type(parse_node_t), intent(in) :: pn
        type(rt_data_t), intent(in) :: global
        type(parse_node_t), pointer :: pn_arg, pn_opt
        pn_arg => parse_node_get_sub_ptr (pn, 2)
        if (associated (pn_arg)) then
            pn_opt => parse_node_get_next_ptr (pn_arg)
        else
            pn_opt => null ()
        end if
        allocate (open)
        call rt_data_local_init (open%local, global)
        if (associated (pn_opt)) then
            allocate (open%options)
            call command_list_compile (open%options, pn_opt, open%local)
        end if
        open%pn_sexpr => pn_arg
        open%writing = .true.
        call rt_data_local_reset (open%local)
    end subroutine cmd_open_out_compile

    subroutine cmd_open_execute (open, global)
        type(cmd_open_t), intent(inout) :: open
        type(rt_data_t), intent(inout), target :: global
        type(string_t) :: name
        type(string_t) :: action, status, position
        call rt_data_link (open%local, global)
        if (associated (open%options)) then
            call command_list_execute (open%options, open%local)
        end if
        name = eval_string (open%pn_sexpr, open%local%var_list)
        if (open%reading .and. open%writing) then
            action = "readwrite"
        else if (open%reading) then
            action = "read"
        else if (open%writing) then
            action = "write"
        else
            call msg_bug ("Open command: neither read nor write specified.")
        end if
    end subroutine cmd_open_execute

```

```

status = "replace"
position = "asis"
call file_list_open (global%out_files, name, &
    char (action), char (status), char (position))
call rt_data_restore (global, open%local)
end subroutine cmd_open_execute

```

Close file (output)

Close an output file.

(Commands: types)+≡

```

type :: cmd_close_t
private
type(parse_node_t), pointer :: pn_sexpr => null ()
type(command_list_t), pointer :: options => null ()
type(rt_data_t) :: local
end type cmd_close_t

```

(Commands: procedures)+≡

```

subroutine cmd_close_final (close)
type(cmd_close_t), intent(inout) :: close
if (associated (close%options)) then
call command_list_final (close%options)
deallocate (close%options)
end if
end subroutine cmd_close_final

subroutine cmd_close_out_compile (close, pn, global)
type(cmd_close_t), intent(out), pointer :: close
type(parse_node_t), intent(in) :: pn
type(rt_data_t), intent(in) :: global
type(parse_node_t), pointer :: pn_arg, pn_opt
pn_arg => parse_node_get_sub_ptr (pn, 2)
if (associated (pn_arg)) then
pn_opt => parse_node_get_next_ptr (pn_arg)
else
pn_opt => null ()
end if
allocate (close)
call rt_data_local_init (close%local, global)
if (associated (pn_opt)) then
allocate (close%options)
call command_list_compile (close%options, pn_opt, close%local)
end if
close%pn_sexpr => pn_arg
call rt_data_local_reset (close%local)
end subroutine cmd_close_out_compile

subroutine cmd_close_execute (close, global)
type(cmd_close_t), intent(inout) :: close
type(rt_data_t), intent(inout), target :: global
type(string_t) :: name

```

```

call rt_data_link (close%local, global)
if (associated (close%options)) then
    call command_list_execute (close%options, close%local)
end if
name = eval_string (close%pn_sexpr, close%local%var_list)
call file_list_close (global%out_files, name)
call rt_data_restore (global, close%local)
end subroutine cmd_close_execute

```

17.2.1 Print default-formatted values

(Commands: types)+≡

```

type :: cmd_printd_t
private
type(parse_node_t), pointer :: pn_sexpr => null ()
type(command_list_t), pointer :: options => null ()
type(rt_data_t) :: local
end type cmd_printd_t

```

Finalize.

(Commands: procedures)+≡

```

subroutine cmd_printd_final (printd)
type(cmd_printd_t), intent(inout) :: printd
if (associated (printd%pn_sexpr)) then
    call parse_node_final (printd%pn_sexpr)
    deallocate (printd%pn_sexpr)
end if
if (associated (printd%options)) then
    call command_list_final (printd%options)
    deallocate (printd%options)
end if
end subroutine cmd_printd_final

```

Compile. We create a fake parse node (subtree) with a `sprintd` command with identical arguments which can then be handled by the corresponding evaluation procedure.

(Commands: procedures)+≡

```

subroutine cmd_printd_compile (printd, pn, global)
type(cmd_printd_t), pointer :: printd
type(parse_node_t), intent(in), target :: pn
type(rt_data_t), intent(in), target :: global
type(parse_node_t), pointer :: pn_cmd, pn_arg, pn_opt
type(parse_node_t), pointer :: pn_sexpr, pn_sprintd
pn_cmd => parse_node_get_sub_ptr (pn)
pn_opt => parse_node_get_next_ptr (pn_cmd)
pn_arg => parse_node_get_sub_ptr (pn_cmd)
allocate (printd)
call rt_data_local_init (printd%local, global)
if (associated (pn_opt)) then
    allocate (printd%options)
    call command_list_compile (printd%options, pn_opt, printd%local)

```

```

end if
call parse_node_create_branch (pn_sexpr, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("sexpr")))
call parse_node_create_branch (pn_sprintf, &
    syntax_get_rule_ptr (syntax_cmd_list, var_str ("sprintf_fun")))
call parse_node_append_sub (pn_sexpr, pn_sprintf)
call parse_node_append_sub (pn_sprintf, pn_arg)
printf%pn_sexpr => pn_sexpr
call rt_data_local_reset (printf%local)
end subroutine cmd_printf_compile

```

Execute. Evaluate the string (pretending this is a `sprintf` expression) and print it.

```

<Commands: procedures>+≡
subroutine cmd_printf_execute (printf, global)
    type(cmd_printf_t), intent(inout) :: printf
    type(rt_data_t), intent(inout), target :: global
    type(string_t) :: string, file
    logical :: advance
    call rt_data_link (printf%local, global)
    if (associated (printf%options)) then
        call command_list_execute (printf%options, printf%local)
    end if
    string = eval_string (printf%pn_sexpr, printf%local%var_list)
    file = var_list_get_sval (printf%local%var_list, var_str ("out_file"))
    advance = var_list_get_lval (printf%local%var_list, &
        var_str ("out_advance"))
    if (len (file) == 0) then
        call msg_result (char (string))
    else
        call file_list_write (global%out_files, file, string, advance)
    end if
    call rt_data_restore (global, printf%local)
end subroutine cmd_printf_execute

```

Print custom-formatted values

```

<Commands: types>+≡
type :: cmd_printf_t
    private
    type(parse_node_t), pointer :: pn_sexpr => null ()
    type(command_list_t), pointer :: options => null ()
    type(rt_data_t) :: local
end type cmd_printf_t

```

Finalize.

```

<Commands: procedures>+≡
subroutine cmd_printf_final (printf)
    type(cmd_printf_t), intent(inout) :: printf
    if (associated (printf%pn_sexpr)) then
        call parse_node_final (printf%pn_sexpr)
    end if
end subroutine cmd_printf_final

```

```

        deallocate (printf%pn_sexpr)
    end if
    if (associated (printf%options)) then
        call command_list_final (printf%options)
        deallocate (printf%options)
    end if
end subroutine cmd_printf_final

```

Compile. We create a fake parse node (subtree) with a `sprintf` command with identical arguments which can then be handled by the corresponding evaluation procedure.

(Commands: procedures)+≡

```

subroutine cmd_printf_compile (printf, pn, global)
    type(cmd_printf_t), pointer :: printf
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in), target :: global
    type(parse_node_t), pointer :: pn_cmd, pn_clause, pn_opt
    type(parse_node_t), pointer :: pn_sexpr, pn_sprintf
    pn_cmd => parse_node_get_sub_ptr (pn)
    pn_opt => parse_node_get_next_ptr (pn_cmd)
    pn_clause => parse_node_get_sub_ptr (pn_cmd)
    allocate (printf)
    call rt_data_local_init (printf%local, global)
    if (associated (pn_opt)) then
        allocate (printf%options)
        call command_list_compile (printf%options, pn_opt, printf%local)
    end if
    call parse_node_create_branch (pn_sexpr, &
        syntax_get_rule_ptr (syntax_cmd_list, var_str ("sexpr")))
    call parse_node_create_branch (pn_sprintf, &
        syntax_get_rule_ptr (syntax_cmd_list, var_str ("sprintf_fun")))
    call parse_node_append_sub (pn_sexpr, pn_sprintf)
    call parse_node_append_sub (pn_sprintf, pn_clause)
    printf%pn_sexpr => pn_sexpr
    call parse_node_final (pn_sprintf, recursive = .false.)
    call parse_node_final (pn_sexpr, recursive = .false.)
    call rt_data_local_reset (printf%local)
end subroutine cmd_printf_compile

```

Execute. Evaluate the string (pretending this is a `sprintf` expression) and print it.

(Commands: procedures)+≡

```

subroutine cmd_printf_execute (printf, global)
    type(cmd_printf_t), intent(inout) :: printf
    type(rt_data_t), intent(inout), target :: global
    type(string_t) :: string, file
    logical :: advance
    call rt_data_link (printf%local, global)
    if (associated (printf%options)) then
        call command_list_execute (printf%options, printf%local)
    end if
    string = eval_string (printf%pn_sexpr, printf%local%var_list)
    file = var_list_get_sval (printf%local%var_list, var_str ("%out_file"))

```

```

advance = var_list_get_lval (printf%local%var_list, &
    var_str ("?out_advance"))
if (len (file) == 0) then
    call msg_result (char (string))
else
    call file_list_write (global%out_files, file, string, advance)
end if
call rt_data_restore (global, printf%local)
end subroutine cmd_printf_execute

```

Record data

The expression syntax already contains a **record** keyword; this evaluates to a logical which is always true, but it has the side-effect of recording data into analysis objects. Here we define a command as an interface to this construct.

```

⟨Commands: types⟩+≡
    type :: cmd_record_t
    private
    type(parse_node_t), pointer :: pn_lexpr => null ()
end type cmd_record_t

```

Finalizer for the eval trees.

```

⟨Commands: procedures⟩+≡
    subroutine cmd_record_final (record)
        type(cmd_record_t), intent(inout) :: record
    end subroutine cmd_record_final

```

Compile. Record the record ID and initialize lower, upper bound and bin width.

```

⟨Commands: procedures⟩+≡
    subroutine cmd_record_compile (record, pn, global)
        type(cmd_record_t), pointer :: record
        type(parse_node_t), intent(in), target :: pn
        type(rt_data_t), intent(in), target :: global
        type(parse_node_t), pointer :: pn_lexpr, pn_lsinglet, pn_lterm, pn_record
        call parse_node_create_branch (pn_lexpr, &
            syntax_get_rule_ptr (syntax_cmd_list, var_str ("lexpr")))
        call parse_node_create_branch (pn_lsinglet, &
            syntax_get_rule_ptr (syntax_cmd_list, var_str ("lsinglet")))
        call parse_node_append_sub (pn_lexpr, pn_lsinglet)
        call parse_node_create_branch (pn_lterm, &
            syntax_get_rule_ptr (syntax_cmd_list, var_str ("lterm")))
        call parse_node_append_sub (pn_lsinglet, pn_lterm)
        pn_record => parse_node_get_sub_ptr (pn)
        call parse_node_append_sub (pn_lterm, pn_record)
        allocate (record)
        record%pn_lexpr => pn_lexpr
    end subroutine cmd_record_compile

```

Command execution.

```

⟨Commands: procedures⟩+≡
    subroutine cmd_record_execute (record, global)

```

```

    type(cmd_record_t), intent(inout), target :: record
    type(rt_data_t), intent(inout), target :: global
    logical :: lval
    lval = eval_log (record%pn_lexpr, global%var_list)
end subroutine cmd_record_execute

```

Decay properties

This record holds decay properties for a particle. To be used for `unstable` and `stable` declarations, which contain an array of that type.

(Commands: types)+≡

```

    type :: decay_properties_t
        type(parse_node_t), pointer :: pn_pdg => null ()
        type(string_t) :: prt
        type(flavor_t) :: flv
        integer :: n_proc = 0
        type(string_t), dimension(:), allocatable :: process_id
        real(default), dimension(:), allocatable :: br
        logical :: invalid = .false.
    end type decay_properties_t

```

The finalizer is generic:

(Commands: procedures)+≡

```

    subroutine decay_properties_final (decay)
        type(decay_properties_t), intent(inout) :: decay
    end subroutine decay_properties_final

```

Unstable particles

Mark a particle as unstable. For each unstable particle, we store a number of decay channels and compute their respective BRs.

(Commands: types)+≡

```

    type :: cmd_unstable_t
        private
        type(decay_properties_t), dimension(:), allocatable :: decay
        type(command_list_t), pointer :: options => null ()
        type(rt_data_t) :: local
    end type cmd_unstable_t

```

Delete the eval tree.

(Commands: procedures)+≡

```

    subroutine cmd_unstable_final (unstable)
        type(cmd_unstable_t), intent(inout) :: unstable
        integer :: d
        if (allocated (unstable%decay)) then
            do d = 1, size (unstable%decay)
                call decay_properties_final (unstable%decay(d))
            end do
            deallocate (unstable%decay)
        end if
    end subroutine cmd_unstable_final

```

```

    if (associated (unstable%options)) then
        call command_list_final (unstable%options)
        deallocate (unstable%options)
    end if
end subroutine cmd_unstable_final

```

Compile. Initiate an eval tree for the decaying particle and determine the decay channel process IDs.

(Commands: procedures)+≡

```

subroutine cmd_unstable_compile (unstable, pn, global)
    type(cmd_unstable_t), pointer :: unstable
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in), target :: global
    type(parse_node_t), pointer :: pn_list, pn_decl
    type(parse_node_t), pointer :: pn_prt, pn_arg, pn_proc, pn_opt
    integer :: d, i
    pn_list => parse_node_get_sub_ptr (pn, 2)
    if (associated (pn_list)) then
        pn_opt => parse_node_get_next_ptr (pn_list)
    else
        pn_opt => null ()
    end if
    allocate (unstable)
    call rt_data_local_init (unstable%local, global)
    if (associated (pn_opt)) then
        allocate (unstable%options)
        call command_list_compile (unstable%options, pn_opt, unstable%local)
    end if
    allocate (unstable%decay (parse_node_get_n_sub (pn_list)))
    d = 0
    pn_decl => parse_node_get_sub_ptr (pn_list)
    do while (associated (pn_decl))
        d = d + 1
        pn_prt => parse_node_get_sub_ptr (pn_decl)
        pn_arg => parse_node_get_next_ptr (pn_prt)
        unstable%decay(d)%pn_pdg => pn_prt
        unstable%decay(d)%prt = "?"
        unstable%decay(d)%n_proc = parse_node_get_n_sub (pn_arg)
        allocate (unstable%decay(d)%process_id (unstable%decay(d)%n_proc))
        allocate (unstable%decay(d)%br (unstable%decay(d)%n_proc))
        pn_proc => parse_node_get_sub_ptr (pn_arg)
        do i = 1, unstable%decay(d)%n_proc
            unstable%decay(d)%process_id(i) = parse_node_get_string (pn_proc)
            pn_proc => parse_node_get_next_ptr (pn_proc)
        end do
        pn_decl => parse_node_get_next_ptr (pn_decl)
    end do
    call rt_data_local_reset (unstable%local)
end subroutine cmd_unstable_compile

```

Command execution. Evaluate the decaying particle and compute the BRs for the decays, using previous integration runs. For each decay channel, initialize event generation.

If the integral of some channel is not yet known, compute it.

(*Commands: procedures*) +=

```

subroutine cmd_unstable_execute (unstable, global)
  type(cmd_unstable_t), intent(inout), target :: unstable
  type(rt_data_t), intent(inout), target :: global
  type(pdg_array_t) :: aval
  type(flavor_t), dimension(:), allocatable :: flv_tmp
  type(flavor_t), dimension(:), allocatable :: flv
  real(default), dimension(:), allocatable :: integral
  real(default) :: integral_sum
  type(process_t), pointer :: process
  type(string_t) :: process_id
  integer :: proc
  logical :: isotropic_decay, diagonal_decay
  type(particle_data_t), pointer :: prt_data
  type(decay_configuration_t), pointer :: decay_conf
  integer :: u, d
  u = logfile_unit ()
  call rt_data_link (unstable%local, global)
  if (associated (unstable%options)) then
    call command_list_execute (unstable%options, unstable%local)
  end if
  isotropic_decay = var_list_get_lval (unstable%local%var_list, &
    var_str ("?isotropic_decay"))
  diagonal_decay = var_list_get_lval (unstable%local%var_list, &
    var_str ("?diagonal_decay"))
  allocate (flv (size (unstable%decay)))
  do d = 1, size (unstable%decay)
    aval = eval_pdg_array (unstable%decay(d)%pn_pdg, unstable%local%var_list)
    call flavor_init (flv_tmp, aval, unstable%local%model)
    select case (size (flv_tmp))
    case (1); flv(d) = flv_tmp(1)
    case default
      call pdg_array_write (aval)
      call msg_fatal ("Unstable particle expression " &
        // "does not evaluate to a unique particle")
      return
    end select
    prt_data => model_get_particle_ptr &
      (unstable%local%model, flavor_get_pdg (flv(d)))
    if (associated (prt_data)) then
      if (flavor_is_polarized (flv(d))) then
        call msg_error ("particle '" // char (flavor_get_name (flv(d))) &
          // "' cannot be marked at unstable and polarized at the same " &
          // "time - skipping")
        unstable%decay(d)%invalid = .true.
        cycle
      end if
      if (flavor_is_antiparticle (flv(d))) then
        call particle_data_set (prt_data, &
          a_is_stable = .false., &
          a_decays_isotropically = isotropic_decay, &
          a_decays_diagonal = diagonal_decay)
      else

```

```

        call particle_data_set (prt_data, &
            p_is_stable = .false., &
            p_decays_isotropically = isotropic_decay, &
            p_decays_diagonal = diagonal_decay)
    end if
    unstable%decay(d)%invalid = .false.
else
    call msg_fatal ("Particle '" // char (unstable%decay(d)%prt) &
        // "' is not contained in model '" &
        // char (model_get_name (unstable%local%model)) // "'")
    unstable%decay(d)%invalid = .true.
end if
end do
do d = 1, size (unstable%decay)
    if (unstable%decay(d)%invalid) cycle
    unstable%decay(d)%prt = flavor_get_name (flv(d))
    allocate (integral (unstable%decay(d)%n_proc))
    call integrate_missing_processes &
        (unstable%decay(d)%process_id, unstable%local, global%var_list, &
            no_beams=.true.)
    LOOP_PROC: do proc = 1, unstable%decay(d)%n_proc
        process_id = unstable%decay(d)%process_id(proc)
        process => process_store_get_process_ptr (process_id)
        if (associated (process)) then
            integral(proc) = var_list_get_rval (unstable%local%var_list, &
                var_str ("integral(" // process_id // ")")
            integral(proc) = process_get_integral (process)
            if (integral(proc) < 0) then
                call msg_fatal ("Integral of process '" &
                    // char (process_id) // "' is negative")
            end if
            call process_setup_event_generation (process, qn_mask_in = &
                new_quantum_numbers_mask (.false., .false., isotropic_decay, &
                    mask_hd = diagonal_decay))
        else
            call msg_fatal ("Decay channel '" // char (process_id) &
                // "' is undefined")
        end if
    end do LOOP_PROC
    integral_sum = sum (integral)
    if (integral_sum /= 0) then
        unstable%decay(d)%br = integral / integral_sum
    else
        call msg_fatal ("Unstable particle: Computed total width vanishes")
        unstable%decay(d)%br = 0
    end if
    call decay_store_append_decay &
        (flv(d), unstable%local%model, &
            integral_sum, unstable%decay(d)%n_proc, &
            isotropic_decay, diagonal_decay, &
            decay_conf)
    ASSIGN_DECAYS: do proc = 1, unstable%decay(d)%n_proc
        process => process_store_get_process_ptr &
            (unstable%decay(d)%process_id(proc))

```

```

        if (associated (process)) then
            call decay_configuration_set_channel &
                (decay_conf, proc, process, unstable%decay(d)%br(proc))
        end if
    end do ASSIGN_DECAYS
    deallocate (integral)
    call msg_message ("Particle '" // char (unstable%decay(d)%prt) &
        // "' declared as unstable.")
    call decay_configuration_write (decay_conf)
    call decay_configuration_write (decay_conf, u)
end do
call decay_store_recheck_final_state (verbose = .true.)
call rt_data_restore (global, unstable%local)
end subroutine cmd_unstable_execute

```

Stable particles

Mark a particle as stable. This is necessary only if it was previously marked as unstable.

(Commands: types)+≡

```

type :: cmd_stable_t
private
type(decay_properties_t), dimension(:), allocatable :: decay
type(command_list_t), pointer :: options => null ()
type(rt_data_t) :: local
end type cmd_stable_t

```

Delete the eval tree.

(Commands: procedures)+≡

```

subroutine cmd_stable_final (stable)
type(cmd_stable_t), intent(inout) :: stable
integer :: d
if (allocated (stable%decay)) then
    do d = 1, size (stable%decay)
        call decay_properties_final (stable%decay(d))
    end do
    deallocate (stable%decay)
end if
if (associated (stable%options)) then
    call command_list_final (stable%options)
    deallocate (stable%options)
end if
end subroutine cmd_stable_final

```

Compile. Initiate an eval tree for the particle code.

(Commands: procedures)+≡

```

subroutine cmd_stable_compile (stable, pn, global)
type(cmd_stable_t), pointer :: stable
type(parse_node_t), intent(in), target :: pn
type(rt_data_t), intent(in), target :: global
type(parse_node_t), pointer :: pn_list, pn_prt, pn_opt

```

```

integer :: d
pn_list => parse_node_get_sub_ptr (pn, 2)
pn_opt => parse_node_get_next_ptr (pn_list)
allocate (stable)
call rt_data_local_init (stable%local, global)
if (associated (pn_opt)) then
  allocate (stable%options)
  call command_list_compile (stable%options, pn_opt, stable%local)
end if
allocate (stable%decay (parse_node_get_n_sub (pn_list)))
d = 0
pn_prt => parse_node_get_sub_ptr (pn_list)
do while (associated (pn_prt))
  d = d + 1
  stable%decay(d)%pn_pdg => pn_prt
  stable%decay(d)%prt = "?"
  pn_prt => parse_node_get_next_ptr (pn_prt)
end do
call rt_data_local_reset (stable%local)
end subroutine cmd_stable_compile

```

Command execution. Evaluate the particle type and undo any previous unstable declaration.

(Commands: procedures)+≡

```

subroutine cmd_stable_execute (stable, global)
  type(cmd_stable_t), intent(inout), target :: stable
  type(rt_data_t), intent(inout), target :: global
  type(pdg_array_t) :: aval
  type(flavor_t), dimension(:), allocatable :: flv_tmp
  type(flavor_t) :: flv
  type(particle_data_t), pointer :: prt_data
  integer :: d
  call rt_data_link (stable%local, global)
  if (associated (stable%options)) then
    call command_list_execute (stable%options, stable%local)
  end if
  do d = 1, size (stable%decay)
    aval = eval_pdg_array (stable%decay(d)%pn_pdg, stable%local%var_list)
    call flavor_init (flv_tmp, aval, stable%local%model)
    select case (size (flv_tmp))
    case (1); flv = flv_tmp(1)
    case default
      call pdg_array_write (aval)
      call msg_fatal ("Stable particle expression " &
        // "does not evaluate to a unique particle")
      return
    end select
    stable%decay(d)%prt = flavor_get_name (flv)
    prt_data => &
      model_get_particle_ptr (stable%local%model, flavor_get_pdg (flv))
    if (associated (prt_data)) then
      if (flavor_is_antiparticle (flv)) then
        call particle_data_set (prt_data, a_is_stable=.true.)
      end if
    end if
  end do
end subroutine cmd_stable_execute

```

```

        call particle_data_set (prt_data, a_decays_isotropically=.false.)
        call particle_data_set (prt_data, a_decays_diagonal=.false.)
    else
        call particle_data_set (prt_data, p_is_stable=.true.)
        call particle_data_set (prt_data, p_decays_isotropically=.false.)
        call particle_data_set (prt_data, p_decays_diagonal=.false.)
    end if
else
    call msg_fatal ("Particle '" // char (stable%decay(d)%prt) &
        // "' is not contained in model '" &
        // char (model_get_name (stable%local%model)) // "'")
end if
call msg_message ("Particle '" // char (stable%decay(d)%prt) &
    // "' declared as stable.")
end do
call decay_store_recheck_final_state (verbose = .true.)
call rt_data_restore (global, stable%local)
end subroutine cmd_stable_execute

```

(Un)polarized particles

Toggle flavors to be (un)polarized and make WHIZARD carry along the polarization. As the code is nearly duplicate between both case, we use a single data type and set of subroutines information.

(Commands: types)+≡

```

type :: cmd_un_polarized_t
private
type(parse_node_p), dimension(:), allocatable :: pn_pdg
type(string_t), dimension(:), allocatable :: name
type(command_list_t), pointer :: options => null ()
type(rt_data_t) :: local
end type cmd_un_polarized_t

```

Compile. Initialize the data structure with the pdg expression trees.

(Commands: procedures)+≡

```

subroutine cmd_un_polarized_compile (polarized, pn, global)
type(cmd_un_polarized_t), pointer :: polarized
type(parse_node_t), intent(in), target :: pn
type(rt_data_t), intent(in), target :: global
type(parse_node_t), pointer :: pn_list, pn_opt, pn_prt
integer :: n
allocate (polarized)
pn_list => parse_node_get_sub_ptr (pn, 2)
call rt_data_local_init (polarized%local, global)
if (.not. associated (pn_list)) then
    allocate (polarized%pn_pdg (0))
    allocate (polarized%name (0))
    return
end if
pn_opt => parse_node_get_next_ptr (pn_list)
if (associated (pn_opt)) then
    allocate (polarized%options)
    call command_list_compile (polarized%options, pn_opt, polarized%local)

```

```

end if
n = parse_node_get_n_sub (pn_list)
allocate (polarized%pn_pdg(n), polarized%name(n))
polarized%name = "?"
pn_prt => parse_node_get_sub_ptr (pn_list)
n = 1
do while (associated (pn_prt))
  polarized%pn_pdg(n)%ptr => pn_prt
  pn_prt => parse_node_get_next_ptr (pn_prt)
  n = n + 1
end do
print *, "Processed " // int2char (n - 1) // " particle definitions"
call rt_data_local_reset (polarized%local)
end subroutine cmd_un_polarized_compile

```

Execute.

<Commands: procedures>+≡

```

subroutine cmd_un_polarized_execute (polarized, type, global)
  type(cmd_un_polarized_t), intent(inout) :: polarized
  integer, intent(in) :: type
  type(rt_data_t), target, intent(inout) :: global
  type(pdg_array_t) :: aval
  type(flavor_t), dimension(:), allocatable :: flv
  type(particle_data_t), pointer :: prt
  integer :: i, u
  logical :: anti
  call rt_data_link (polarized%local, global)
  if (associated (polarized%options)) &
    call command_list_execute (polarized%options, polarized%local)
  if (size (polarized%pn_pdg) == 0) return
  do i = 1, size (polarized%pn_pdg)
    aval = eval_pdg_array (polarized%pn_pdg(i)%ptr, polarized%local%var_list)
    call flavor_init (flv, aval, polarized%local%model)
    if (size (flv) /= 1) then
      call pdg_array_write (aval)
      u = output_unit ()
      if (u >= 0) write (u, "('')")
      call msg_error &
        ("'polarized' needs unique particles, ignoring argument")
      deallocate (flv)
      cycle
    end if
    polarized%name(i) = flavor_get_name (flv(1))
    prt => model_get_particle_ptr (polarized%local%model, &
      flavor_get_pdg (flv(1)))
    if (.not. associated (prt)) then
      call msg_error ("Model '" &
        // char (model_get_name (polarized%local%model)) &
        // "' does not contain particle '" &
        // char (polarized%name(i)) // "'")
      deallocate (flv)
      cycle
    end if
    anti = flavor_is_antiparticle (flv(1))
  end do
end subroutine cmd_un_polarized_execute

```

```

    if (.not. particle_data_is_stable (prt, anti) .and. &
        type == CMD_POLARIZED) then
        call msg_error ("particle '" &
            // char (polarized%name(i)) // "' cannot be marked as unstable " &
            // "and polarized at the same time - skipping")
        deallocate (flv)
        cycle
    end if
    if (anti) then
        call particle_data_set (prt, a_polarized=(type == CMD_POLARIZED))
    else
        call particle_data_set (prt, p_polarized=(type == CMD_POLARIZED))
    end if
    if (type == CMD_POLARIZED) then
        call msg_message ("Polarization of particle '" &
            // char (polarized%name(i)) // "' in model '" &
            // char (model_get_name (polarized%local%model)) &
            // "' will be retained.")
    else
        call msg_message ("Polarization of particle '" &
            // char (polarized%name(i)) // "' in model '" &
            // char (model_get_name (polarized%local%model)) &
            // "' will be discarded.")
    end if
    deallocate (flv)
end do
call rt_data_restore (global, polarized%local)
end subroutine cmd_un_polarized_execute

```

Finalize.

```

<Commands: procedures>+≡
subroutine cmd_un_polarized_final (polarized)
    type(cmd_un_polarized_t), intent(inout) :: polarized
    if (allocated (polarized%pn_pdg)) then
        deallocate (polarized%pn_pdg)
    end if
    if (allocated (polarized%name)) deallocate (polarized%name)
    if (associated (polarized%options)) then
        call command_list_final (polarized%options)
        deallocate (polarized%options)
    end if
end subroutine cmd_un_polarized_final

```

Parameters: formats for event-sample output

Specify all event formats that are to be used for output files in the subsequent simulation run. (The raw format is on by default and can be turned off here.)

```

<Commands: types>+≡
type :: cmd_sample_format_t
    private
    type(string_t), dimension(:), allocatable :: format
    integer, dimension(:), allocatable :: fmt
end type cmd_sample_format_t

```

Finalizer.

```
<Commands: procedures>+≡
subroutine cmd_sample_format_final (sample)
  type(cmd_sample_format_t), intent(inout) :: sample
  if (allocated (sample%format)) then
    deallocate (sample%format)
  end if
end subroutine cmd_sample_format_final
```

Compile. Initialize evaluation trees.

```
<Commands: procedures>+≡
subroutine cmd_sample_format_compile (sample, pn)
  type(cmd_sample_format_t), pointer :: sample
  type(parse_node_t), intent(in), target :: pn
  type(parse_node_t), pointer :: pn_arg
  type(parse_node_t), pointer :: pn_format
  integer :: i, n_format
  allocate (sample)
  pn_arg => parse_node_get_sub_ptr (pn, 3)
  if (associated (pn_arg)) then
    n_format = parse_node_get_n_sub (pn_arg)
    allocate (sample%format (n_format), sample%fmt (n_format))
    pn_format => parse_node_get_sub_ptr (pn_arg)
    i = 0
    do while (associated (pn_format))
      i = i + 1
      sample%format(i) = parse_node_get_string (pn_format)
      pn_format => parse_node_get_next_ptr (pn_format)
    end do
    sample%fmt = event_format_code (sample%format)
  else
    allocate (sample%format (0))
  end if
end subroutine cmd_sample_format_compile
```

Execute. Transform the string-valued format specifications into an integer array in the runtime data set.

```
<Commands: procedures>+≡
subroutine cmd_sample_format_execute (sample, global)
  type(cmd_sample_format_t), intent(inout) :: sample
  type(rt_data_t), intent(inout) :: global
  integer, dimension(:), allocatable :: fmt_tmp
  integer :: i, j, k
  if (allocated (global%event_fmt)) deallocate (global%event_fmt)
  allocate (fmt_tmp(size (sample%format)))
  j = 0
  TRANSFER: do i = 1, size (sample%format)
    if (sample%fmt(i) == FMT_NONE) then
      call msg_error ("Undefined event-file format '" &
        // char (sample%format(i)) // "' (skipped)")
      cycle TRANSFER
    end if
    if (j > 0) then
```



```

do k = 1, j
  if (fmt_tmp(k) == sample%fmt(i)) then
    call msg_warning ("Ignoring multiple requests for " &
      // "event-file format '" // char (sample%format(i)) &
      // "'")
    cycle TRANSFER
  end if
end do
end if
j = j + 1
fmt_tmp(j) = sample%fmt(i)
end do TRANSFER
if (j > 0) then
  allocate (global%event_fmt(j))
  global%event_fmt = fmt_tmp(1:j)
end if
deallocate (fmt_tmp)
end subroutine cmd_sample_format_execute

```

The simulate command

This is the actual SINDARIN command.

```

<Commands: types>+≡
type :: cmd_simulate_t
! not private anymore as required by the whizard-c-interface
integer :: n_evt = 0
integer :: n_proc = 0
type(string_t), dimension(:), allocatable :: process_id
type(command_list_t), pointer :: options => null ()
type(rt_data_t) :: local
end type cmd_simulate_t

```

Finalizer.

```

<Commands: procedures>+≡
subroutine cmd_simulate_final (simulate)
type(cmd_simulate_t), intent(inout) :: simulate
if (associated (simulate%options)) then
  call command_list_final (simulate%options)
  deallocate (simulate%options)
end if
end subroutine cmd_simulate_final

```

Compile. In contrast to WHIZARD 1 the confusing option to give the number of unweighted events for weighted events as if unweighting were to take place has been abandoned. (We both use `n_events` for weighted and unweighted events, the variable `n_calls` from WHIZARD 1 has been discarded.

```

<Commands: procedures>+≡
subroutine cmd_simulate_compile (simulate, pn, global)
type(cmd_simulate_t), pointer :: simulate
type(parse_node_t), intent(in), target :: pn
type(rt_data_t), intent(in), target :: global

```

```

type(parse_node_t), pointer :: pn_proclist, pn_proc, pn_opt
integer :: i
pn_proclist => parse_node_get_sub_ptr (pn, 2)
pn_opt => parse_node_get_next_ptr (pn_proclist)
allocate (simulate)
call rt_data_local_init (simulate%local, global)
if (associated (pn_opt)) then
    allocate (simulate%options)
    call command_list_compile (simulate%options, pn_opt, simulate%local)
end if
simulate%n_proc = parse_node_get_n_sub (pn_proclist)
allocate (simulate%process_id (simulate%n_proc))
pn_proc => parse_node_get_sub_ptr (pn_proclist)
do i = 1, simulate%n_proc
    simulate%process_id(i) = parse_node_get_string (pn_proc)
    pn_proc => parse_node_get_next_ptr (pn_proc)
end do
call rt_data_local_reset (simulate%local)
end subroutine cmd_simulate_compile

```

Execute command: Simulate events. This is done via a `simulation_t` object and its associated methods.

(Commands: procedures)+≡

```

subroutine cmd_simulate_execute (simulate, global)
    type(cmd_simulate_t), intent(inout), target :: simulate
    type(rt_data_t), intent(inout), target :: global
    logical :: ok
!   integer :: i_evt
    type(simulation_t), target :: sim
    call rt_data_link (simulate%local, global)
    if (associated (simulate%options)) then
        call command_list_execute (simulate%options, simulate%local)
    end if
    call simulation_init (sim, simulate%process_id, simulate%local, &
        global%var_list, ok, verbose=.true.)
    if (ok) then
        call simulation_setup_selection &
            (sim, simulate%local%pn_selection_lexpr, verbose=.true.)
        call simulation_setup_reweight &
            (sim, simulate%local%pn_reweight_expr, verbose=.true.)
        call simulation_setup_analysis &
            (sim, simulate%local%pn_analysis_lexpr, verbose=.true.)
        call openmp_set_num_threads_verbose &
            (var_list_get_ival (global%var_list, "openmp_num_threads"))
!       do i_evt = 1, simulation_get_n_events (sim)
!           call simulation_event (sim, simulate%local%rng, ok, verbose=.true.)
!           if (.not. ok) exit
!       end do
        do while( simulation_get_i_evt(sim) .lt. simulation_get_n_events(sim))
            call simulation_event (sim, simulate%local%rng, ok, global%os_data, verbose=.true.)
            if (.not. ok) exit
        end do
        call simulation_final (sim, verbose=.true.)
    end if
end subroutine cmd_simulate_execute

```

```

end if
call rt_data_restore (global, simulate%local)
end subroutine cmd_simulate_execute

```

Execute command: Matching interface w/ PYTHIA

```

<Commands: procedures>+≡
subroutine cmd_matching_execute (os_data)
  type(string_t) :: cmd_string
  type(os_data_t), intent(in) :: os_data
  call msg_message ("Starting MLM matching PYTHIA interface...")
  cmd_string = os_data%prefix // "/bin/interface"
  call os_system_call (cmd_string)
  call msg_message ("PYTHIA interface finished.")
end subroutine cmd_matching_execute

```

The rescan command

This is the actual SINDARIN command.

```

<Commands: types>+≡
type :: cmd_rescan_t
  private
  integer :: n_evt = 0
  integer :: n_proc = 0
  type(parse_node_t), pointer :: pn_filename => null ()
  type(string_t), dimension(:), allocatable :: process_id
  type(command_list_t), pointer :: options => null ()
  type(rt_data_t) :: local
end type cmd_rescan_t

```

Finalizer.

```

<Commands: procedures>+≡
subroutine cmd_rescan_final (rescan)
  type(cmd_rescan_t), intent(inout) :: rescan
  if (associated (rescan%options)) then
    call command_list_final (rescan%options)
    deallocate (rescan%options)
  end if
end subroutine cmd_rescan_final

```

Compile. In contrast to WHIZARD 1 the confusing option to give the number of unweighted events for weighted events as if unweighting were to take place has been abandoned. (We both use `n_events` for weighted and unweighted events, the variable `n_calls` from WHIZARD 1 has been discarded.

```

<Commands: procedures>+≡
subroutine cmd_rescan_compile (rescan, pn, global)
  type(cmd_rescan_t), pointer :: rescan
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(in), target :: global
  type(parse_node_t), pointer :: pn_filename, pn_proclist, pn_proc, pn_opt
  integer :: i

```

```

pn_filename => parse_node_get_sub_ptr (pn, 2)
pn_proclist => parse_node_get_next_ptr (pn_filename)
pn_opt => parse_node_get_next_ptr (pn_proclist)
allocate (rescan)
call rt_data_local_init (rescan%local, global)
if (associated (pn_opt)) then
    allocate (rescan%options)
    call command_list_compile (rescan%options, pn_opt, rescan%local)
end if
rescan%pn_filename => pn_filename
rescan%n_proc = parse_node_get_n_sub (pn_proclist)
allocate (rescan%process_id (rescan%n_proc))
pn_proc => parse_node_get_sub_ptr (pn_proclist)
do i = 1, rescan%n_proc
    rescan%process_id(i) = parse_node_get_string (pn_proc)
    pn_proc => parse_node_get_next_ptr (pn_proc)
end do
call rt_data_local_reset (rescan%local)
end subroutine cmd_rescan_compile

```

Execute command: Rescan events. This is done via a `simulation_t` object and its associated methods.

(Commands: procedures)+≡

```

subroutine cmd_rescan_execute (rescan, global)
    type(cmd_rescan_t), intent(inout), target :: rescan
    type(rt_data_t), intent(inout), target :: global
    logical :: ok
    integer :: i_evt
    type(simulation_t), target :: sim
    type(string_t) :: filename
    call rt_data_link (rescan%local, global)
    if (associated (rescan%options)) then
        call command_list_execute (rescan%options, rescan%local)
    end if
    filename = eval_string (rescan%pn_filename, rescan%local%var_list)
    call simulation_init (sim, &
        rescan%process_id, rescan%local, global%var_list, ok, &
        filename=filename, verbose=.true.)
    if (ok) then
        call simulation_setup_selection &
            (sim, rescan%local%pn_selection_lexpr, verbose=.true.)
        call simulation_setup_reweight &
            (sim, rescan%local%pn_reweight_expr, verbose=.true.)
        call simulation_setup_analysis &
            (sim, rescan%local%pn_analysis_lexpr, verbose=.true.)
        do i_evt = 1, simulation_get_n_events (sim)
            call simulation_event (sim, rescan%local%rng, ok, global%os_data, verbose=.true.)
            if (.not. ok) exit
        end do
        call simulation_final (sim, verbose=.true.)
    end if
    call rt_data_restore (global, rescan%local)
end subroutine cmd_rescan_execute

```

17.2.2 Parameters: random-number generator seed

Specify a new random-number generator seed and set it.

```
<Commands: types>+≡
  type :: cmd_seed_t
    private
    type(parse_node_t), pointer :: pn_expr => null ()
  end type cmd_seed_t
```

Finalizer.

```
<Commands: procedures>+≡
  subroutine cmd_seed_final (seed)
    type(cmd_seed_t), intent(inout) :: seed
  end subroutine cmd_seed_final
```

Compile. Initialize evaluation trees.

```
<Commands: procedures>+≡
  subroutine cmd_seed_compile (seed, pn, global)
    type(cmd_seed_t), pointer :: seed
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in), target :: global
    allocate (seed)
    seed%pn_expr => parse_node_get_sub_ptr (pn, 3)
  end subroutine cmd_seed_compile
```

Execute. Evaluate the trees and add the result to the iteration list in the runtime data set.

```
<Commands: procedures>+≡
  subroutine cmd_seed_execute (seed, global)
    type(cmd_seed_t), intent(inout) :: seed
    type(rt_data_t), intent(inout) :: global
    integer :: seed_val
    seed_val = eval_int (seed%pn_expr, global%var_list)
    call set_rng_seed (global%rng, global%var_list, seed_val, verbose=.true.)
  end subroutine cmd_seed_execute
```

```
<Commands: procedures>+≡
  subroutine set_rng_seed (rng, var_list, seed_val, verbose)
    type(tao_random_state), intent(inout) :: rng
    type(var_list_t), intent(inout), target :: var_list
    integer, intent(in) :: seed_val
    logical, intent(in) :: verbose
    character(30) :: buffer
    if (verbose) then
      write (buffer, "(I0)") seed_val
      call msg_message ("Setting seed for random-number generator to " &
        // trim (buffer))
    end if
    call tao_random_seed (rng, seed_val)
```

```

        call var_list_set_int (var_list, var_str ("seed_value"), &
            seed_val, is_known=.true.)
    end subroutine set_rng_seed

```

Parameters: number of iterations

Specify number of iterations and number of calls for one integration pass.

```

<Commands: types>+≡
    type :: cmd_iterations_t
    private
    integer :: n_pass = 0
    type(parse_node_p), dimension(:), allocatable :: pn_expr_n_it
    type(parse_node_p), dimension(:), allocatable :: pn_expr_n_calls
    type(parse_node_p), dimension(:), allocatable :: pn_sexpr_adapt
end type cmd_iterations_t

```

Finalizer.

```

<Commands: procedures>+≡
    subroutine cmd_iterations_final (iterations)
    type(cmd_iterations_t), intent(inout) :: iterations
    integer :: i
    if (allocated (iterations%pn_expr_n_it)) then
        deallocate (iterations%pn_expr_n_it)
    end if
    if (allocated (iterations%pn_expr_n_calls)) then
        deallocate (iterations%pn_expr_n_calls)
    end if
end subroutine cmd_iterations_final

```

Compile. Initialize evaluation trees.

```

<Commands: procedures>+≡
    subroutine cmd_iterations_compile (iterations, pn, global)
    type(cmd_iterations_t), pointer :: iterations
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(in), target :: global
    type(parse_node_t), pointer :: pn_arg, pn_n_it, pn_n_calls, pn_adapt
    type(parse_node_t), pointer :: pn_it_spec, pn_calls_spec, pn_adapt_spec
    integer :: i
    allocate (iterations)
    pn_arg => parse_node_get_sub_ptr (pn, 3)
    if (associated (pn_arg)) then
        iterations%n_pass = parse_node_get_n_sub (pn_arg)
        allocate (iterations%pn_expr_n_it (iterations%n_pass))
        allocate (iterations%pn_expr_n_calls (iterations%n_pass))
        allocate (iterations%pn_sexpr_adapt (iterations%n_pass))
        pn_it_spec => parse_node_get_sub_ptr (pn_arg)
        i = 1
        do while (associated (pn_it_spec))
            pn_n_it => parse_node_get_sub_ptr (pn_it_spec)
            pn_calls_spec => parse_node_get_next_ptr (pn_n_it)
            pn_n_calls => parse_node_get_sub_ptr (pn_calls_spec, 2)

```

```

pn_adapt_spec => parse_node_get_next_ptr (pn_calls_spec)
if (associated (pn_adapt_spec)) then
  pn_adapt => parse_node_get_sub_ptr (pn_adapt_spec, 2)
else
  pn_adapt => null ()
end if
iterations%pn_expr_n_it(i)%ptr => pn_n_it
iterations%pn_expr_n_calls(i)%ptr => pn_n_calls
iterations%pn_sexpr_adapt(i)%ptr => pn_adapt
i = i + 1
pn_it_spec => parse_node_get_next_ptr (pn_it_spec)
end do
else
  allocate (iterations%pn_expr_n_it (0))
  allocate (iterations%pn_expr_n_calls (0))
end if
end subroutine cmd_iterations_compile

```

Execute. Evaluate the trees and add the result to the iteration list in the runtime data set.

(Commands: procedures)+≡

```

subroutine cmd_iterations_execute (iterations, global)
  type(cmd_iterations_t), intent(inout) :: iterations
  type(rt_data_t), intent(inout) :: global
  integer, dimension(iterations%n_pass) :: n_it, n_calls
  logical, dimension(iterations%n_pass) :: custom_adapt
  type(string_t), dimension(iterations%n_pass) :: adapt_code
  integer :: i
  do i = 1, iterations%n_pass
    n_it(i) = eval_int (iterations%pn_expr_n_it(i)%ptr, global%var_list)
    n_calls(i) = &
      eval_int (iterations%pn_expr_n_calls(i)%ptr, global%var_list)
    if (associated (iterations%pn_sexpr_adapt(i)%ptr)) then
      adapt_code(i) = &
        eval_string (iterations%pn_sexpr_adapt(i)%ptr, &
          global%var_list, is_known = custom_adapt(i))
    else
      custom_adapt(i) = .false.
    end if
  end do
  call iterations_list_init &
    (global%it_list, n_it, n_calls, custom_adapt, adapt_code)
end subroutine cmd_iterations_execute

```

Scan over parameters and other objects

(Commands: parameters)+≡

```

integer, parameter :: STEP_NONE = 0
integer, parameter :: STEP_ADD = 1
integer, parameter :: STEP_SUB = 2
integer, parameter :: STEP_MUL = 3
integer, parameter :: STEP_DIV = 4

```

```

integer, parameter :: STEP_COMP_ADD = 11
integer, parameter :: STEP_COMP_MUL = 13
<Commands: types>+≡
type :: cmd_scan_t
  private
  integer :: var_type = V_NONE
  type(string_t) :: var_name
  logical :: allow_steps = .false.
  integer :: n_arg = 0
  type(command_list_t), dimension(:), pointer :: cmd_var => null ()
  logical, dimension(:), allocatable :: has_range
  type(parse_node_p), dimension(:), allocatable :: pn_beg_expr
  type(parse_node_p), dimension(:), allocatable :: pn_end_expr
  integer, dimension(:), allocatable :: step_type
  type(parse_node_p), dimension(:), allocatable :: pn_step_expr
  type(command_list_t), pointer :: body => null ()
  type(rt_data_t) :: local
end type cmd_scan_t

```

Finalizer.

```

<Commands: procedures>+≡
recursive subroutine cmd_scan_final (loop)
  type(cmd_scan_t), intent(inout) :: loop
  integer :: i
  if (associated (loop%cmd_var)) then
    do i = 1, size (loop%cmd_var)
      call command_list_final (loop%cmd_var(i))
    end do
    deallocate (loop%cmd_var)
  end if
  if (allocated (loop%has_range)) deallocate (loop%has_range)
  if (allocated (loop%pn_beg_expr)) then
    deallocate (loop%pn_beg_expr)
  end if
  if (allocated (loop%pn_end_expr)) then
    deallocate (loop%pn_end_expr)
  end if
  if (allocated (loop%step_type)) deallocate (loop%step_type)
  if (allocated (loop%pn_step_expr)) then
    deallocate (loop%pn_step_expr)
  end if
  if (associated (loop%body)) then
    call command_list_final (loop%body)
    deallocate (loop%body)
  end if
end subroutine cmd_scan_final

```

Compile the loop, including the list of step specifications.

```

<Commands: procedures>+≡
recursive subroutine cmd_scan_compile (loop, pn, global)
  type(cmd_scan_t), pointer :: loop
  type(parse_node_t), intent(in), target :: pn

```



```

type(rt_data_t), intent(inout), target :: global
type(parse_node_t), pointer :: pn_spec, pn_cmd, pn_list, pn_body
integer :: i
type(parse_tree_t) :: parse_tree
type(parse_node_t), pointer :: pn_root, pn_decl, pn_init_arg, pn_arg
type(parse_node_t), pointer :: pn_expr, pn_range, pn_range_expr
type(parse_node_t), pointer :: pn_step, pn_step_op, pn_step_expr
type(parse_node_t), pointer :: pn_var, pn_name
type(string_t) :: key, str_init
type(lexer_t) :: lexer
type(stream_t), target :: stream
logical :: declaration, new
pn_spec => parse_node_get_sub_ptr (pn)
pn_cmd => parse_node_get_sub_ptr (pn_spec, 2)
pn_var => pn_cmd
allocate (loop)
call rt_data_local_init (loop%local, global)
if (associated (pn_cmd)) then
    key = parse_node_get_rule_key (pn_cmd)
else
    loop%var_type = V_NONE
    loop%n_arg = 0
    return
end if
declaration = .false.
select case (char (key))
case ("cmd_model_list")
    str_init = 'model = ""'
case ("cmd_library_list")
    str_init = 'library = ""'
case ("cmd_seed_list")
    loop%var_type = V_INT
    loop%var_name = "seed"
    str_init = 'seed = 0'
    loop%allow_steps = .true.
case ("cmd_cuts_list")
    str_init = 'cuts = true'
case ("cmd_scale_list")
    str_init = 'scale = 0'
case ("cmd_fac_scale_list")
    str_init = 'factorization_scale = 0'
case ("cmd_ren_scale_list")
    str_init = 'renormalization_scale = 0'
case ("cmd_weight_list")
    str_init = 'weight = 0'
case ("cmd_selection_list")
    str_init = 'selection = true'
case ("cmd_reweight_list")
    str_init = 'reweight = 0'
case ("cmd_analysis_list")
    str_init = 'analysis = true'
case default
    new = .false.
    select case (char (key))

```

```

case ("log_decl_list")
    loop%var_type = V_LOG
    pn_var => parse_node_get_sub_ptr (pn_cmd, 2)
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
    loop%var_name = '?' // parse_node_get_string (pn_name)
    str_init = 'logical ' // loop%var_name // ' = true'
    declaration = .true.
    new = .true.
case ("log_list")
    loop%var_type = V_LOG
    pn_name => parse_node_get_sub_ptr (pn_cmd, 2)
    loop%var_name = '?' // parse_node_get_string (pn_name)
    str_init = loop%var_name // ' = true'
case ("int_list")
    loop%var_type = V_INT
    pn_name => parse_node_get_sub_ptr (pn_cmd, 2)
    loop%var_name = parse_node_get_string (pn_name)
    str_init = 'int ' // loop%var_name // ' = 0'
    loop%allow_steps = .true.
    new = .true.
case ("real_list")
    loop%var_type = V_REAL
    pn_name => parse_node_get_sub_ptr (pn_cmd, 2)
    loop%var_name = parse_node_get_string (pn_name)
    str_init = 'real ' // loop%var_name // ' = 0'
    loop%allow_steps = .true.
    new = .true.
case ("num_list")
    loop%var_type = V_REAL
    pn_name => parse_node_get_sub_ptr (pn_cmd)
    loop%var_name = parse_node_get_string (pn_name)
    str_init = loop%var_name // ' = 0'
    loop%allow_steps = .true.
case ("string_decl_list")
    loop%var_type = V_STR
    pn_var => parse_node_get_sub_ptr (pn_cmd, 2)
    pn_name => parse_node_get_sub_ptr (pn_var, 2)
    loop%var_name = '$' // parse_node_get_string (pn_name)
    str_init = 'string ' // loop%var_name // ' = ""'
    declaration = .true.
    new = .true.
case ("string_list")
    loop%var_type = V_STR
    pn_name => parse_node_get_sub_ptr (pn_cmd, 2)
    loop%var_name = '$' // parse_node_get_string (pn_name)
    str_init = loop%var_name // ' = ""'
case ("alias_list")
    loop%var_type = V_PDG
    pn_name => parse_node_get_sub_ptr (pn_cmd, 2)
    loop%var_name = parse_node_get_string (pn_name)
    str_init = 'alias ' // loop%var_name // ' = PDG(0)'
    new = .true.
case default
    call parse_node_mismatch &

```

```

        ("scan: model|library|seed|cuts|weight|" // &
         "scale|factorization_scale|renormalization_scale|analysis|" &
         // "variable", pn_cmd)
end select
call var_list_check_user_var &
    (global%var_list, loop%var_name, loop%var_type, new)
if (loop%var_type == V_NONE) then
    call msg_fatal ("Invalid scan variable declaration")
    loop%n_arg = 0
    return
end if
end select
if (associated (pn_var)) then
    pn_list => parse_node_get_last_sub_ptr (pn_var)
    if (associated (pn_list)) then
        loop%n_arg = parse_node_get_n_sub (pn_list)
        allocate (loop%cmd_var (loop%n_arg))
        call lexer_init_cmd_list (lexer)
        allocate (loop%has_range (loop%n_arg)); loop%has_range = .false.
        if (loop%allow_steps) then
            allocate (loop%pn_beg_expr (loop%n_arg))
            allocate (loop%pn_end_expr (loop%n_arg))
            allocate (loop%step_type (loop%n_arg)); loop%step_type = STEP_NONE
            allocate (loop%pn_step_expr (loop%n_arg))
        end if
        call stream_init (stream, str_init)
        call lexer_assign_stream (lexer, stream)
        call parse_tree_init (parse_tree, syntax_cmd_list, lexer)
        pn_root => parse_tree_get_root_ptr (parse_tree)
        if (declaration) then
            pn_decl => parse_node_get_sub_ptr (pn_root)
            pn_cmd => parse_node_get_sub_ptr (pn_decl, 2)
        else
            pn_cmd => parse_node_get_sub_ptr (pn_root)
        end if
        pn_init_arg => parse_node_get_last_sub_ptr (pn_cmd)
        i = 0
        pn_arg => parse_node_get_sub_ptr (pn_list)
        do while (associated (pn_arg))
            i = i + 1
            select case (char (parse_node_get_rule_key (pn_arg)))
            case ("num_steps")
                pn_expr => parse_node_get_sub_ptr (pn_arg)
                pn_range => parse_node_get_next_ptr (pn_expr)
                if (associated (pn_range)) then
                    loop%has_range(i) = .true.
                    pn_range_expr => parse_node_get_sub_ptr (pn_range, 2)
                    loop%pn_beg_expr(i)%ptr => pn_expr
                    loop%pn_end_expr(i)%ptr => pn_range_expr
                    pn_step => parse_node_get_next_ptr (pn_range_expr)
                    if (associated (pn_step)) then
                        pn_step_op => parse_node_get_sub_ptr (pn_step)
                        select case (char (parse_node_get_key (pn_step_op)))
                        case ("/+"); loop%step_type(i) = STEP_ADD

```

```

        case ("/-"); loop%step_type(i) = STEP_SUB
        case ("/*"); loop%step_type(i) = STEP_MUL
        case ("//"); loop%step_type(i) = STEP_DIV
        case ("+/+"); loop%step_type(i) = STEP_COMP_ADD
        case ("*/"); loop%step_type(i) = STEP_COMP_MUL
    end select
    pn_step_expr => parse_node_get_next_ptr (pn_step_op)
    loop%pn_step_expr(i)%ptr => pn_step_expr
end if
end if
case default
    pn_expr => pn_arg
end select
call parse_node_replace_last_sub (pn_cmd, pn_expr)
call command_list_compile (loop%cmd_var(i), pn_root, loop%local)
pn_arg => parse_node_get_next_ptr (pn_arg)
end do
call parse_node_replace_last_sub (pn_cmd, pn_init_arg)
call parse_tree_final (parse_tree)
call stream_final (stream)
call lexer_final (lexer)
end if
pn_body => parse_node_get_next_ptr (pn_spec)
if (associated (pn_body)) then
    allocate (loop%body)
    call command_list_compile (loop%body, pn_body, loop%local)
end if
else
    loop%n_arg = 0
end if
call rt_data_local_reset (loop%local)
end subroutine cmd_scan_compile

```

Execute the loop for all values in the step list.

(Commands: procedures)+≡

```

recursive subroutine cmd_scan_execute (loop, global)
    type(cmd_scan_t), intent(inout), target :: loop
    type(rt_data_t), intent(inout), target :: global
    type(string_t) :: model_name
    logical :: is_seed
    integer :: i, j
    integer :: i1, i2, istep, ival, n_steps
    real(default) :: r1, r2, rstep, rval, rlog, rilog, r2log
    logical :: is_known
    type(var_entry_t), pointer :: var
    type(var_list_t), pointer :: model_vars
    call rt_data_link (loop%local, global)
    if (associated (loop%local%model)) then
        model_name = model_get_name (loop%local%model)
        model_vars => model_get_var_list_ptr (loop%local%model)
    else
        model_vars => null ()
    end if
    LOOP_LIST: do i = 1, loop%n_arg

```

```

call command_list_execute (loop%cmd_var(i), loop%local)
if (.not. loop%has_range(i)) then
  if (associated (loop%body)) then
    call command_list_execute (loop%body, loop%local)
    if (loop%local%quit) then
      global%quit_code = loop%local%quit_code
      global%quit = .true.
      return
    end if
  end if
else
  call eval_numeric (loop%pn_beg_expr(i)%ptr, loop%local%var_list, &
    is_known=is_known, ival=i1, rval=r1)
  if (.not. is_known) then
    call msg_error ("Scan: undefined lower bound, skipping")
    cycle LOOP_LIST
  end if
  call eval_numeric (loop%pn_end_expr(i)%ptr, loop%local%var_list, &
    is_known=is_known, ival=i2, rval=r2)
  if (.not. is_known) then
    call msg_error ("Scan: undefined upper bound, skipping")
    cycle LOOP_LIST
  end if
  select case (loop%step_type(i))
  case (STEP_NONE)
    rstep = 1
    istep = 1
  case default
    call eval_numeric (loop%pn_step_expr(i)%ptr, loop%local%var_list, &
      is_known=is_known, ival=istep, rval=rstep)
    if (.not. is_known) then
      call msg_error ("Scan: undefined step size, skipping")
      cycle LOOP_LIST
    end if
  end select
  if (bounds_check_fails (loop%step_type(i), loop%var_type)) &
    cycle LOOP_LIST
  if (loop%var_name == "seed") then
    is_seed = .true.
  else
    is_seed = .false.
    var => var_list_get_var_ptr (loop%local%var_list, loop%var_name)
    if (var_entry_get_type (var) /= loop%var_type) then
      call msg_fatal ("Type mismatch for loop variable '" &
        // char (loop%var_name) // "'; skipping")
      exit LOOP_LIST
    end if
  end if
  select case (loop%var_type)
  case (V_REAL)
    n_steps = -1
    select case (loop%step_type(i))
    case (STEP_NONE, STEP_ADD)
      if (rstep /= 0) n_steps = nint ((r2 - r1) / rstep)

```

```

case (STEP_SUB)
  if (rstep /= 0) n_steps = nint (- (r2 - r1) / rstep)
case (STEP_COMP_ADD)
  if (istep /= 0) n_steps = istep
case (STEP_MUL, STEP_DIV, STEP_COMP_MUL)
  if (r1 * r2 > 0) then
    if (rstep > 0 .and. rstep /= 1) then
      r1log = log (abs (r1))
      r2log = log (abs (r2))
      select case (loop%step_type(i))
        case (STEP_MUL)
          n_steps = nint (log (r2 / r1) / log (rstep))
        case (STEP_DIV)
          n_steps = nint (- log (r2 / r1) / log (rstep))
        case (STEP_COMP_MUL)
          n_steps = istep
      end select
    end if
  end if
end select
if (n_steps == 0) n_steps = -1
select case (loop%step_type(i))
case (STEP_NONE, STEP_ADD, STEP_COMP_ADD, STEP_SUB)
  do j = 0, n_steps
    rval = (j * r2 + (n_steps-j) * r1) / n_steps
    call set_real (rval, j/=0)
    if (associated (loop%body)) then
      call command_list_execute (loop%body, loop%local)
      if (loop%local%quit) then
        global%quit_code = loop%local%quit_code
        global%quit = .true.
        return
      end if
    end if
  end do
case (STEP_MUL, STEP_COMP_MUL, STEP_DIV)
  do j = 0, n_steps
    rlog = (j * r2log + (n_steps-j) * r1log) / n_steps
    rval = sign (exp (rlog), r1)
    call set_real (rval, j/=0)
    if (associated (loop%body)) then
      call command_list_execute (loop%body, loop%local)
      if (loop%local%quit) then
        global%quit_code = loop%local%quit_code
        global%quit = .true.
        return
      end if
    end if
  end do
end select
case (V_INT)
  select case (loop%step_type(i))
  case (STEP_SUB); istep = - istep
  end select

```

```

select case (loop%step_type(i))
case (STEP_NONE, STEP_ADD, STEP_SUB)
do j = i1, i2, istep
call set_int (j, j/=i1, is_seed)
if (associated (loop%body)) then
call command_list_execute (loop%body, loop%local)
if (loop%local%quit) then
global%quit_code = loop%local%quit_code
global%quit = .true.
return
end if
end if
end do
case (STEP_MUL, STEP_DIV)
call msg_error ("Skipping scan: " &
// "Multiplicative steps not allowed " &
// "for integer scan variable")
case (STEP_COMP_ADD, STEP_COMP_MUL)
call msg_error ("Skipping scan: " &
// "Range division not allowed for integer scan variable")
end select
end select
end if
end do LOOP_LIST
call rt_data_restore (global, loop%local)
contains
subroutine set_real (rval, verbose)
real(default), intent(in) :: rval
logical, intent(in) :: verbose
call var_entry_set_real (var, rval, is_known=.true., verbose=verbose, &
model_name=model_name)
if (var_entry_is_copy (var)) then
call model_parameters_update (loop%local%model)
call var_list_synchronize (loop%local%var_list, model_vars)
end if
end subroutine set_real
subroutine set_int (ival, verbose, is_seed)
integer, intent(in) :: ival
logical, intent(in) :: verbose, is_seed
if (is_seed) then
call set_rng_seed (loop%local%rng, loop%local%var_list, ival, &
verbose=verbose)
else
call var_entry_set_int (var, ival, is_known=.true., verbose=verbose, &
model_name=model_name)
if (var_entry_is_copy (var)) then
call model_parameters_update (loop%local%model)
call var_list_synchronize (loop%local%var_list, model_vars)
end if
end if
end subroutine set_int
function bounds_check_fails (step_type, var_type) result (fails)
logical :: fails
integer, intent(in) :: step_type, var_type

```

```

fails = .false.
select case (var_type)
case (V_REAL)
  if (rstep == 0) then
    call msg_error ("Scan: step size equals zero, skipping")
    fails = .true.; return
  end if
  select case (step_type)
  case (STEP_MUL, STEP_DIV)
    if (rstep < 0) then
      call msg_error ("Scan: multiplicative step < 0, skipping")
      fails = .true.; return
    else if (rstep == 1) then
      call msg_error ("Scan: multiplicative step = 1, skipping")
      fails = .true.; return
    else if (r1 == 0 .or. r2 == 0) then
      call msg_error ("Scan: " &
        // "boundary for multiplicative step is zero, skipping")
      fails = .true.; return
    end if
  end select
case (V_INT)
  if (istep == 0) then
    call msg_error ("Scan: step size equals zero, skipping")
    fails = .true.; return
  end if
  select case (step_type)
  case (STEP_MUL, STEP_DIV)
    if (istep < 0) then
      call msg_error ("Scan: multiplicative step < 0, skipping")
      fails = .true.; return
    else if (istep == 1) then
      call msg_error ("Scan: multiplicative step = 1, skipping")
      fails = .true.; return
    else if (i1 == 0 .or. i2 == 0) then
      call msg_error ("Scan: " &
        // "boundary for multiplicative step is zero, skipping")
      fails = .true.; return
    end if
  end select
end select
end function bounds_check_fails
end subroutine cmd_scan_execute

```

Conditionals

Conditionals are implemented as a list that is compiled and evaluated recursively; this allows for a straightforward representation of `else if` constructs. A `cmd_if_t` object can hold either an `else_if` clause which is another object of this type, or an `else_body`, but not both.

If- or else-bodies are no scoping units, so all data remain global and no copy-in copy-out is needed.


```

(Commands: types) +=
  type :: cmd_if_t
  private
    type(parse_node_t), pointer :: pn_if_lexpr => null ()
    type(command_list_t), pointer :: if_body => null ()
    type(cmd_if_t), dimension(:), pointer :: elsif_cond => null ()
    type(command_list_t), pointer :: else_body => null ()
  end type cmd_if_t

```

Finalizer.

```

(Commands: procedures) +=
  recursive subroutine cmd_if_final (cond)
    type(cmd_if_t), intent(inout) :: cond
    integer :: i
    if (associated (cond%if_body)) then
      call command_list_final (cond%if_body)
      deallocate (cond%if_body)
    end if
    if (associated (cond%elsif_cond)) then
      do i = 1, size (cond%elsif_cond)
        call cmd_if_final (cond%elsif_cond(i))
      end do
      deallocate (cond%elsif_cond)
    end if
    if (associated (cond%else_body)) then
      call command_list_final (cond%else_body)
      deallocate (cond%else_body)
    end if
  end subroutine cmd_if_final

```

Compile the conditional.

```

(Commands: procedures) +=
  recursive subroutine cmd_if_compile (cond, pn, global)
    type(cmd_if_t), pointer :: cond
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_lexpr, pn_body
    type(parse_node_t), pointer :: pn_elsif_clauses, pn_cmd_elsif
    type(parse_node_t), pointer :: pn_else_clause, pn_cmd_else
    integer :: i, n_elsif
    allocate (cond)
    pn_lexpr => parse_node_get_sub_ptr (pn, 2)
    cond%pn_if_lexpr => pn_lexpr
    pn_body => parse_node_get_next_ptr (pn_lexpr, 2)
    select case (char (parse_node_get_rule_key (pn_body)))
    case ("command_list")
      allocate (cond%if_body)
      call command_list_compile (cond%if_body, pn_body, global)
      pn_elsif_clauses => parse_node_get_next_ptr (pn_body)
    case default
      pn_elsif_clauses => pn_body
    end select
    select case (char (parse_node_get_rule_key (pn_elsif_clauses)))

```

```

case ("elsif_clauses")
  n_elsif = parse_node_get_n_sub (pn_elsif_clauses)
  allocate (cond%elsif_cond (n_elsif))
  pn_cmd_elsif => parse_node_get_sub_ptr (pn_elsif_clauses)
  do i = 1, n_elsif
    pn_lexpr => parse_node_get_sub_ptr (pn_cmd_elsif, 2)
    cond%elsif_cond(i)%pn_if_lexpr => pn_lexpr
    pn_body => parse_node_get_next_ptr (pn_lexpr, 2)
    if (associated (pn_body)) then
      allocate (cond%elsif_cond(i)%if_body)
      call command_list_compile &
        (cond%elsif_cond(i)%if_body, pn_body, global)
    end if
    pn_cmd_elsif => parse_node_get_next_ptr (pn_cmd_elsif)
  end do
  pn_else_clause => parse_node_get_next_ptr (pn_elsif_clauses)
case default
  pn_else_clause => pn_elsif_clauses
end select
select case (char (parse_node_get_rule_key (pn_else_clause)))
case ("else_clause")
  pn_cmd_else => parse_node_get_sub_ptr (pn_else_clause)
  pn_body => parse_node_get_sub_ptr (pn_cmd_else, 2)
  if (associated (pn_body)) then
    allocate (cond%else_body)
    call command_list_compile (cond%else_body, pn_body, global)
  end if
end select
end subroutine cmd_if_compile

```

(Recursively) execute the condition. Context remains global in all cases.

(Commands: procedures)+≡

```

recursive subroutine cmd_if_execute (cond, global)
  type(cmd_if_t), intent(inout), target :: cond
  type(rt_data_t), intent(inout), target :: global
  logical :: lval, is_known
  integer :: i
  lval = eval_log (cond%pn_if_lexpr, global%var_list, is_known=is_known)
  if (is_known) then
    if (lval) then
      if (associated (cond%if_body)) then
        call command_list_execute (cond%if_body, global)
      end if
      return
    end if
  else
    call error_undecided ()
    return
  end if
  if (associated (cond%elsif_cond)) then
    SCAN_ELSEIF: do i = 1, size (cond%elsif_cond)
      lval = eval_log (cond%elsif_cond(i)%pn_if_lexpr, global%var_list, &
        is_known=is_known)
      if (is_known) then

```

```

        if (lval) then
            if (associated (cond%elsif_cond(i)%if_body)) then
                call command_list_execute &
                    (cond%elsif_cond(i)%if_body, global)
            end if
            return
        end if
    else
        call error_undecided ()
        return
    end if
end do SCAN_ELSIF
end if
if (associated (cond%else_body)) then
    call command_list_execute (cond%else_body, global)
end if
contains
    subroutine error_undecided ()
        call msg_error ("Undefined result of conditional expression: " &
            // "neither branch will be executed")
    end subroutine error_undecided
end subroutine cmd_if_execute

```

Include another command-list file

The include command allocates a local parse tree. This must not be deleted before the command object itself is deleted, since pointers may point to subobjects of it.

```

<Commands: types>+≡
    type :: cmd_include_t
        private
        type(string_t) :: file
        type(command_list_t), pointer :: command_list => null ()
        type(parse_tree_t) :: parse_tree
    end type cmd_include_t

```

Finalizer: delete the command list.

```

<Commands: procedures>+≡
    subroutine cmd_include_final (include)
        type(cmd_include_t), intent(inout) :: include
        call parse_tree_final (include%parse_tree)
        if (associated (include%command_list)) then
            call command_list_final (include%command_list)
            deallocate (include%command_list)
        end if
    end subroutine cmd_include_final

```

Compile file contents: First parse the file, then immediately compile its contents. Use the global data set.

```

<Commands: procedures>+≡
    subroutine cmd_include_compile (include, pn, global)

```

```

type(cmd_include_t), pointer :: include
type(parse_node_t), intent(in), target :: pn
type(rt_data_t), intent(inout), target :: global
type(parse_node_t), pointer :: pn_arg, pn_file
type(string_t) :: file
logical :: exist
integer :: u
type(stream_t), target :: stream
type(lexer_t) :: lexer
pn_arg => parse_node_get_sub_ptr (pn, 2)
pn_file => parse_node_get_sub_ptr (pn_arg)
allocate (include)
file = parse_node_get_string (pn_file)
inquire (file=char(file), exist=exist)
if (exist) then
    include%file = file
else
    include%file = global%os_data%whizard_cutspath // "/" // file
    inquire (file=char(include%file), exist=exist)
    if (.not. exist) then
        call msg_error ("Include file '" // char (file) // "' not found")
        return
    end if
end if
u = free_unit ()
call lexer_init_cmd_list (lexer, global%lexer)
call stream_init (stream, char (include%file))
call lexer_assign_stream (lexer, stream)
call parse_tree_init (include%parse_tree, syntax_cmd_list, lexer)
call stream_final (stream)
call lexer_final (lexer)
close (u)
allocate (include%command_list)
call command_list_compile &
    (include%command_list, parse_tree_get_root_ptr (include%parse_tree), &
    global)
end subroutine cmd_include_compile

```

Execute file contents in the global context.

```

<Commands: procedures>+≡
subroutine cmd_include_execute (include, global)
    type(cmd_include_t), intent(inout), target :: include
    type(rt_data_t), intent(inout), target :: global
    if (associated (include%command_list)) then
        call msg_message &
            ("Including script file '" // char (include%file) // "'")
        call command_list_execute (include%command_list, global)
    end if
end subroutine cmd_include_execute

```

Quit command execution

The code is the return code of the whole program if it is terminated by this command.

```
(Commands: types)+≡
  type :: cmd_quit_t
  private
  logical :: has_code = .false.
  type(parse_node_t), pointer :: pn_code_expr => null ()
end type cmd_quit_t
```

Finalizer.

```
(Commands: procedures)+≡
  subroutine cmd_quit_final (quit)
    type(cmd_quit_t), intent(inout) :: quit
  end subroutine cmd_quit_final
```

Compile: allocate a quit object which serves as a placeholder.

```
(Commands: procedures)+≡
  subroutine cmd_quit_compile (quit, pn, global)
    type(cmd_quit_t), pointer :: quit
    type(parse_node_t), intent(in), target :: pn
    type(rt_data_t), intent(inout), target :: global
    type(parse_node_t), pointer :: pn_arg
    allocate (quit)
    pn_arg => parse_node_get_sub_ptr (pn, 2)
    if (associated (pn_arg)) then
      quit%pn_code_expr => parse_node_get_sub_ptr (pn_arg)
      quit%has_code = .true.
    end if
  end subroutine cmd_quit_compile
```

Execute: The quit command does not execute anything, it just stops command execution. This is achieved by setting quit flag and quit code in the global variable list. However, the return code, if present, is an expression which has to be evaluated.

```
(Commands: procedures)+≡
  subroutine cmd_quit_execute (quit, global)
    type(cmd_quit_t), intent(inout), target :: quit
    type(rt_data_t), intent(inout), target :: global
    logical :: is_known
    if (quit%has_code) then
      global%quit_code = eval_int (quit%pn_code_expr, global%var_list, &
        is_known=is_known)
      if (.not. is_known) then
        call msg_error ("Undefined return code of quit/exit command")
      end if
    end if
    global%quit = .true.
  end subroutine cmd_quit_execute
```

17.2.3 The command list

The command list holds a list of commands and relevant global data.

```
<Commands: public>≡
    public :: command_list_t

<Commands: types>+≡
    type :: command_list_t
        ! not private anymore as required by the whizard-c-interface
    type(command_t), pointer :: first => null ()
    type(command_t), pointer :: last => null ()
end type command_list_t
```

Append a new command.

```
<Commands: procedures>+≡
    subroutine command_list_append (cmd_list, command)
        type(command_list_t), intent(inout) :: cmd_list
        type(command_t), intent(in), target :: command
        if (associated (cmd_list%last)) then
            cmd_list%last%next => command
        else
            cmd_list%first => command
        end if
        cmd_list%last => command
    end subroutine command_list_append
```

Finalize.

```
<Commands: public>+≡
    public :: command_list_final

<Commands: procedures>+≡
    recursive subroutine command_list_final (cmd_list)
        type(command_list_t), intent(inout) :: cmd_list
        type(command_t), pointer :: command
        do while (associated (cmd_list%first))
            command => cmd_list%first
            cmd_list%first => cmd_list%first%next
            call command_final (command)
            deallocate (command)
        end do
        cmd_list%last => null ()
    end subroutine command_list_final
```

17.2.4 Compiling the parse tree

Transform a parse tree into a command list. Initialization is assumed to be done.

After each command, we set a breakpoint.

```
<Commands: public>+≡
    public :: command_list_compile
```

```

<Commands: procedures>+≡
recursive subroutine command_list_compile (cmd_list, pn, global)
  type(command_list_t), intent(inout), target :: cmd_list
  type(parse_node_t), intent(in), target :: pn
  type(rt_data_t), intent(inout), target :: global
  type(parse_node_t), pointer :: pn_cmd
  type(command_t), pointer :: command
  integer :: i
  pn_cmd => parse_node_get_sub_ptr (pn)
  do i = 1, parse_node_get_n_sub (pn)
    call command_compile (command, pn_cmd, global)
    call command_list_append (cmd_list, command)
    call terminate_now_if_signal ()
    pn_cmd => parse_node_get_next_ptr (pn_cmd)
  end do
end subroutine command_list_compile

```

17.2.5 Executing the command list

Also here, after each command we set a breakpoint.

```

<Commands: public>+≡
public :: command_list_execute

<Commands: procedures>+≡
recursive subroutine command_list_execute (cmd_list, global)
  type(command_list_t), intent(in) :: cmd_list
  type(rt_data_t), intent(inout), target :: global
  type(command_t), pointer :: command
  command => cmd_list%first
  COMMAND_COND: do while (associated (command))
    call command_execute (command, global)
    call terminate_now_if_signal ()
    if (global%quit) exit COMMAND_COND
    command => command%next
  end do COMMAND_COND
end subroutine command_list_execute

```

17.2.6 Command list syntax

```

<Commands: public>+≡
public :: syntax_cmd_list

<Commands: variables>≡
type(syntax_t), target, save :: syntax_cmd_list

<Commands: public>+≡
public :: syntax_cmd_list_init

<Commands: procedures>+≡
subroutine syntax_cmd_list_init ()
  type(ifile_t) :: ifile
  call define_cmd_list_syntax (ifile)

```

```

        call syntax_init (syntax_cmd_list, ifile)
        call ifile_final (ifile)
    end subroutine syntax_cmd_list_init

    <Commands: public>+≡
        public :: syntax_cmd_list_final

    <Commands: procedures>+≡
        subroutine syntax_cmd_list_final ()
            call syntax_final (syntax_cmd_list)
        end subroutine syntax_cmd_list_final

    <Commands: public>+≡
        public :: syntax_cmd_list_write

    <Commands: procedures>+≡
        subroutine syntax_cmd_list_write (unit)
            integer, intent(in), optional :: unit
            call syntax_write (syntax_cmd_list, unit)
        end subroutine syntax_cmd_list_write

    <Commands: procedures>+≡
        subroutine define_cmd_list_syntax (ifile)
            type(ifile_t), intent(inout) :: ifile
            call ifile_append (ifile, "SEQ command_list = command*")
            call ifile_append (ifile, "ALT command = " &
                // "cmd_model | cmd_library | cmd_iterations | cmd_sample_format | " &
                // "cmd_seed | " &
                // "cmd_var | cmd_slha | " &
                // "cmd_show | " &
                // "cmd_expect | " &
                // "cmd_cuts | cmd_scale | cmd_fac_scale | cmd_ren_scale | " &
                // "cmd_weight | cmd_selection | cmd_reweight | " &
                // "cmd_beams | cmd_integrate | cmd_me_test | " &
                // "cmd_observable | cmd_histogram | cmd_plot | cmd_graph | " &
                // "cmd_clear | cmd_record | " &
                // "cmd_analysis | " &
                // "cmd_unstable | cmd_stable | cmd_simulate | cmd_rescan | " &
                // "cmd_process | cmd_compile | cmd_load | cmd_exec | " &
                // "cmd_scan | cmd_if | cmd_include | cmd_quit | " &
                // "cmd_polarized | cmd_unpolarized | " &
                // "cmd_beam_polarization | " &
                // "cmd_open_out | cmd_close_out | cmd_printd | cmd_printf | " &
                // "cmd_write_analysis | cmd_compile_analysis | " &
                // "cmd_histogram_writer | cmd_plot_writer")
            call ifile_append (ifile, "GRO options = '{' local_command_list '}'")
            call ifile_append (ifile, "SEQ local_command_list = local_command*")
            call ifile_append (ifile, "ALT local_command = " &
                // "cmd_model | cmd_library | cmd_iterations | cmd_sample_format | " &
                // "cmd_seed | " &
                // "cmd_var | cmd_slha | " &
                // "cmd_show | " &
                // "cmd_expect | " &
                // "cmd_cuts | cmd_scale | cmd_fac_scale | cmd_ren_scale | " &

```



```

// "cmd_weight | cmd_selection | cmd_reweight | " &
// "cmd_beams | " &
// "cmd_observable | cmd_histogram | cmd_plot | cmd_graph | " &
// "cmd_clear | cmd_record | " &
// "cmd_analysis | " &
// "cmd_beam_polarization | " &
// "cmd_open_out | cmd_close_out | cmd_printd | cmd_printf | " &
// "cmd_write_analysis | cmd_compile_analysis | " &
// "cmd_histogram_writer | cmd_plot_writer")
call ifile_append (ifile, "SEQ cmd_model = model '=' model_name")
call ifile_append (ifile, "KEY model")
call ifile_append (ifile, "ALT model_name = model_id | string_literal")
call ifile_append (ifile, "IDE model_id")
call ifile_append (ifile, "SEQ cmd_library = library '=' lib_name")
call ifile_append (ifile, "KEY library")
call ifile_append (ifile, "ALT lib_name = lib_id | string_literal")
call ifile_append (ifile, "IDE lib_id")
call ifile_append (ifile, "ALT cmd_var = " &
// "cmd_log_decl | cmd_log | " &
// "cmd_int | cmd_real | cmd_complex | cmd_num | " &
// "cmd_string_decl | cmd_string | cmd_alias | " &
// "cmd_result")
call ifile_append (ifile, "SEQ cmd_log_decl = logical cmd_log")
call ifile_append (ifile, "SEQ cmd_log = '?' var_name '=' lexpr")
call ifile_append (ifile, "SEQ cmd_int = int var_name '=' expr")
call ifile_append (ifile, "SEQ cmd_real = real var_name '=' expr")
call ifile_append (ifile, "SEQ cmd_complex = complex var_name '=' expr")
call ifile_append (ifile, "SEQ cmd_num = var_name '=' expr")
call ifile_append (ifile, "SEQ cmd_string_decl = string cmd_string")
call ifile_append (ifile, "SEQ cmd_string = " &
// '$' var_name '=' sexpr") ! $
call ifile_append (ifile, "SEQ cmd_alias = alias var_name '=' cexpr")
call ifile_append (ifile, "SEQ cmd_result = result '=' expr")
call ifile_append (ifile, "SEQ cmd_slha = slha_action slha_arg options?")
call ifile_append (ifile, "ALT slha_action = " &
// "read_slha | write_slha")
call ifile_append (ifile, "KEY read_slha")
call ifile_append (ifile, "KEY write_slha")
call ifile_append (ifile, "ARG slha_arg = ( string_literal )")
call ifile_append (ifile, "SEQ cmd_show = show show_arg?")
call ifile_append (ifile, "KEY show")
call ifile_append (ifile, "ARG show_arg = ( var_generic* )")
call ifile_append (ifile, "ALT var_generic = " &
// "model | beams | results | unstable | real | int | " &
// "cuts | weight | scale | factorization_scale | renormalization_scale | " &
// "analysis | expect | " &
// "library_spec | " &
// "intrinsic | result_var | " &
// "log_var | alias_var | string_var | num_var")
call ifile_append (ifile, "KEY results")
call ifile_append (ifile, "KEY intrinsic")
call ifile_append (ifile, "SEQ library_spec = library lib_name?")
call ifile_append (ifile, "SEQ result_var = result_key result_arg?")
call ifile_append (ifile, "SEQ log_var = '?' log_var_spec?")

```

```

call ifile_append (ifile, "ALT log_var_spec = log_val | variable")
call ifile_append (ifile, "GRO log_val = ( lexpr )")
call ifile_append (ifile, "SEQ alias_var = alias alias_var_spec?")
call ifile_append (ifile, "ALT alias_var_spec = alias_val | variable")
call ifile_append (ifile, "GRO alias_val = ( cexpr )")
call ifile_append (ifile, "SEQ string_var = '$' string_var_spec?") ! $
call ifile_append (ifile, "ALT string_var_spec = string_val | variable")
call ifile_append (ifile, "GRO string_val = ( sexpr )")
call ifile_append (ifile, "SEQ num_var = num_var_spec")
call ifile_append (ifile, "ALT num_var_spec = num_val | variable")
call ifile_append (ifile, "GRO num_val = ( expr )")
call ifile_append (ifile, "SEQ cmd_expect = expect expect_arg options?")
call ifile_append (ifile, "KEY expect")
call ifile_append (ifile, "ARG expect_arg = ( lexpr )")
call ifile_append (ifile, "SEQ cmd_cuts = cuts '=' lexpr")
call ifile_append (ifile, "SEQ cmd_scale = scale '=' expr")
call ifile_append (ifile, "SEQ cmd_fac_scale = factorization_scale '=' expr")
call ifile_append (ifile, "SEQ cmd_ren_scale = renormalization_scale '=' expr")
call ifile_append (ifile, "SEQ cmd_weight = weight '=' expr")
call ifile_append (ifile, "SEQ cmd_selection = selection '=' lexpr")
call ifile_append (ifile, "SEQ cmd_reweight = reweight '=' expr")
call ifile_append (ifile, "KEY cuts")
call ifile_append (ifile, "KEY scale")
call ifile_append (ifile, "KEY factorization_scale")
call ifile_append (ifile, "KEY renormalization_scale")
call ifile_append (ifile, "KEY weight")
call ifile_append (ifile, "KEY selection")
call ifile_append (ifile, "KEY reweight")
call ifile_append (ifile, "SEQ cmd_process = process process_id '=' " &
// "process_prt '=>' process_prt options?")
call ifile_append (ifile, "KEY process")
call ifile_append (ifile, "KEY '=>")
call ifile_append (ifile, "LIS process_prt = cexpr+")
call ifile_append (ifile, "SEQ cmd_compile = compile_cmd options?")
call ifile_append (ifile, "SEQ compile_cmd = compile_clause compile_arg?")
call ifile_append (ifile, "SEQ compile_clause = compile_exec_name_spec?")
call ifile_append (ifile, "KEY compile")
call ifile_append (ifile, "SEQ exec_name_spec = as exec_name")
call ifile_append (ifile, "KEY as")
call ifile_append (ifile, "ALT exec_name = exec_id | string_literal")
call ifile_append (ifile, "IDE exec_id")
call ifile_append (ifile, "ARG compile_arg = ( lib_name* )")
call ifile_append (ifile, "SEQ cmd_load = load load_arg?")
call ifile_append (ifile, "KEY load")
call ifile_append (ifile, "ARG load_arg = ( lib_name* )")
call ifile_append (ifile, "SEQ cmd_exec = exec exec_arg")
call ifile_append (ifile, "KEY exec")
call ifile_append (ifile, "ARG exec_arg = ( sexpr )")
call ifile_append (ifile, "SEQ cmd_beams = beams '=' beam_def")
call ifile_append (ifile, "KEY beams")
call ifile_append (ifile, "SEQ beam_def = beam_spec strfun_seq*")
call ifile_append (ifile, "SEQ beam_spec = beam_list options?")
call ifile_append (ifile, "LIS beam_list = cexpr, cexpr?")
call ifile_append (ifile, "SEQ strfun_seq = '=>' strfun_pair")

```

```

call ifile_append (ifile, "LIS strfun_pair = strfun_def, strfun_def?")
call ifile_append (ifile, "SEQ strfun_def = strfun_id options?")
call ifile_append (ifile, "ALT strfun_id = " &
    // "none | lhpdf | isr | epa | ewa | pdf_builtin | " &
    // "circe1 | circe2 | energy_scan | beam_events | " &
    // "user_sf_spec")
call ifile_append (ifile, "KEY none")
call ifile_append (ifile, "KEY lhpdf")
call ifile_append (ifile, "KEY isr")
call ifile_append (ifile, "KEY epa")
call ifile_append (ifile, "KEY ewa")
call ifile_append (ifile, "KEY circe1")
call ifile_append (ifile, "KEY circe2")
call ifile_append (ifile, "KEY energy_scan")
call ifile_append (ifile, "KEY beam_events")
call ifile_append (ifile, "KEY pdf_builtin")
call ifile_append (ifile, "SEQ user_sf_spec = user_strfun user_arg")
call ifile_append (ifile, "KEY user_strfun")
call ifile_append (ifile, "SEQ cmd_integrate = " &
    // "integrate proc_arg options?")
call ifile_append (ifile, "KEY integrate")
call ifile_append (ifile, "ARG proc_arg = ( proc_id* )")
call ifile_append (ifile, "IDE proc_id")
call ifile_append (ifile, "SEQ cmd_me_test = " &
    // "matrix_element_test proc_arg1 options?")
call ifile_append (ifile, "KEY matrix_element_test")
call ifile_append (ifile, "ARG proc_arg1 = ( proc_id )")
call ifile_append (ifile, "SEQ cmd_seed = seed '=' expr")
call ifile_append (ifile, "KEY seed")
call ifile_append (ifile, "SEQ cmd_iterations = " &
    // "iterations '=' iterations_list")
call ifile_append (ifile, "KEY iterations")
call ifile_append (ifile, "LIS iterations_list = iterations_spec+")
call ifile_append (ifile, "ALT iterations_spec = it_spec")
call ifile_append (ifile, "SEQ it_spec = expr calls_spec adapt_spec?")
call ifile_append (ifile, "SEQ calls_spec = ':' expr")
call ifile_append (ifile, "SEQ adapt_spec = ':' sexpr")
call ifile_append (ifile, "SEQ cmd_sample_format = " &
    // "sample_format '=' event_format_list")
call ifile_append (ifile, "KEY sample_format")
call ifile_append (ifile, "LIS event_format_list = event_format+")
call ifile_append (ifile, "IDE event_format")
call ifile_append (ifile, "SEQ cmd_observable = " &
    // "observable analysis_tag options?")
call ifile_append (ifile, "KEY observable")
call ifile_append (ifile, "SEQ cmd_histogram = " &
    // "histogram analysis_tag histogram_arg " &
    // "options?")
call ifile_append (ifile, "KEY histogram")
call ifile_append (ifile, "ARG histogram_arg = (expr, expr, expr?)")
call ifile_append (ifile, "SEQ cmd_plot = plot analysis_tag options?")
call ifile_append (ifile, "KEY plot")
call ifile_append (ifile, "SEQ cmd_graph = graph graph_term '=' graph_def")
call ifile_append (ifile, "KEY graph")

```

```

call ifile_append (ifile, "SEQ graph_term = analysis_tag options?")
call ifile_append (ifile, "SEQ graph_def = graph_term graph_append*")
call ifile_append (ifile, "SEQ graph_append = '&' graph_term")
call ifile_append (ifile, "SEQ cmd_analysis = analysis '=' lexpr")
call ifile_append (ifile, "KEY analysis")
call ifile_append (ifile, "SEQ cmd_open_out = open_out open_arg options?")
call ifile_append (ifile, "SEQ cmd_close_out = close_out open_arg options?")
call ifile_append (ifile, "KEY open_out")
call ifile_append (ifile, "KEY close_out")
call ifile_append (ifile, "ARG open_arg = (sexpr)")
call ifile_append (ifile, "SEQ cmd_printd = printd_cmd options?")
call ifile_append (ifile, "SEQ printd_cmd = printd sprintf_args?")
call ifile_append (ifile, "KEY printd")
call ifile_append (ifile, "SEQ cmd_printf = printf_cmd options?")
call ifile_append (ifile, "SEQ printf_cmd = printf_clause sprintf_args?")
call ifile_append (ifile, "SEQ printf_clause = printf sexpr")
call ifile_append (ifile, "KEY printf")
call ifile_append (ifile, "SEQ cmd_clear = clear clear_arg?")
call ifile_append (ifile, "KEY clear")
call ifile_append (ifile, "ARG clear_arg = ( clear_obj* )")
call ifile_append (ifile, "ALT clear_obj = " &
// "iterations | cuts | weight | scale | factorization_scale | " &
// "renormalization_scale | analysis | expect | " &
// "analysis_tag")
call ifile_append (ifile, "SEQ cmd_record = record_cmd")
call ifile_append (ifile, "SEQ cmd_unstable = " &
// "unstable unstable_list options?")
call ifile_append (ifile, "KEY unstable")
call ifile_append (ifile, "LIS unstable_list = unstable_decl+")
call ifile_append (ifile, "SEQ unstable_decl = cexpr unstable_arg")
call ifile_append (ifile, "ARG unstable_arg = ( proc_id+ )")
call ifile_append (ifile, "SEQ cmd_stable = stable stable_list options?")
call ifile_append (ifile, "KEY stable")
call ifile_append (ifile, "LIS stable_list = cexpr+")
call ifile_append (ifile, "KEY polarized")
call ifile_append (ifile, "SEQ cmd_polarized = polarized polarized_list options?")
call ifile_append (ifile, "LIS polarized_list = cexpr+")
call ifile_append (ifile, "KEY unpolarized")
call ifile_append (ifile, "SEQ cmd_unpolarized = unpolarized unpolarized_list options?")
call ifile_append (ifile, "LIS unpolarized_list = cexpr+")
call ifile_append (ifile, "SEQ cmd_simulate = " &
// "simulate proc_arg options?")
call ifile_append (ifile, "KEY simulate")
call ifile_append (ifile, "SEQ cmd_rescan = " &
// "rescan sexpr proc_arg options?")
call ifile_append (ifile, "KEY rescan")
call ifile_append (ifile, "SEQ cmd_scan = scan_spec scan_body?")
call ifile_append (ifile, "SEQ scan_spec = scan scan_command?")
call ifile_append (ifile, "KEY scan")
call ifile_append (ifile, "ALT scan_command = " &
// "cmd_model_list | cmd_library_list | " &
// "cmd_seed_list | " &
// "cmd_cuts_list | cmd_scale_list | " &
// "cmd_fac_scale_list | cmd_ren_scale_list | " &

```

```

// "cmd_weight_list | cmd_selection_list | " &
// "cmd_reweight_list | cmd_analysis_list | " &
// "cmd_var_list")
call ifile_append (ifile, "SEQ cmd_model_list = model = model_list_arg")
call ifile_append (ifile, "ARG model_list_arg = ( model_name* )")
call ifile_append (ifile, "SEQ cmd_library_list = " &
// "library = library_list_arg")
call ifile_append (ifile, "ARG library_list_arg = ( lib_name* )")
call ifile_append (ifile, "SEQ cmd_seed_list = seed = num_step_list_arg")
call ifile_append (ifile, "ARG num_step_list_arg = ( num_steps_expr* )")
call ifile_append (ifile, "ALT num_steps_expr = grouped_num_steps | num_steps")
call ifile_append (ifile, "GRO grouped_num_steps = ( num_steps )")
call ifile_append (ifile, "SEQ num_steps = expr range_spec?")
call ifile_append (ifile, "SEQ range_spec = '='>' expr step_spec?")
call ifile_append (ifile, "SEQ step_spec = step_op expr")
call ifile_append (ifile, "ALT step_op = " &
// "'/' | '/'-' | '/'* | '/'/' | '+/' | '*/'")
call ifile_append (ifile, "KEY '/'")
call ifile_append (ifile, "KEY '/'-")
call ifile_append (ifile, "KEY '/'*")
call ifile_append (ifile, "KEY '/'/'")
call ifile_append (ifile, "KEY '+/'")
call ifile_append (ifile, "KEY '*/'")
call ifile_append (ifile, "ALT cmd_var_list = " &
// "log_decl_list | log_list | " &
// "int_list | real_list | complex_list | num_list | " &
// "string_decl_list | string_list | alias_list")
call ifile_append (ifile, "SEQ log_decl_list = logical log_list")
call ifile_append (ifile, "SEQ log_list = '?' var_name '=' log_list_arg")
call ifile_append (ifile, "ARG log_list_arg = ( lexpr* )")
call ifile_append (ifile, "SEQ int_list = " &
// "int var_name '=' num_step_list_arg")
call ifile_append (ifile, "SEQ real_list = " &
// "real var_name '=' num_step_list_arg")
call ifile_append (ifile, "SEQ complex_list = " &
// "complex var_name '=' num_step_list_arg")
call ifile_append (ifile, "SEQ num_list = var_name '=' num_step_list_arg")
call ifile_append (ifile, "SEQ string_decl_list = string string_list")
call ifile_append (ifile, "SEQ string_list = " &
// "'$' var_name '=' string_list_arg") !$
call ifile_append (ifile, "ARG string_list_arg = ( sexpr* )")
call ifile_append (ifile, "SEQ alias_list = " &
// "alias var_name alias_list_arg")
call ifile_append (ifile, "ARG alias_list_arg = ( cexpr* )")
call ifile_append (ifile, "SEQ cmd_cuts_list = cuts = log_list_arg")
call ifile_append (ifile, "SEQ cmd_scale_list = scale = num_list_arg")
call ifile_append (ifile, "SEQ cmd_fac_scale_list = factorization_scale = num_list_arg")
call ifile_append (ifile, "SEQ cmd_ren_scale_list = renormalization_scale = num_list_arg")
call ifile_append (ifile, "SEQ cmd_weight_list = weight = num_list_arg")
call ifile_append (ifile, "SEQ cmd_selection_list = selection = log_list_arg")
call ifile_append (ifile, "SEQ cmd_reweight_list = reweight = num_list_arg")
call ifile_append (ifile, "ARG num_list_arg = ( expr* )")
call ifile_append (ifile, "SEQ cmd_analysis_list = analysis = log_list_arg")
call ifile_append (ifile, "GRO scan_body = '{' command_list '}'")

```

```

call ifile_append (ifile, "SEQ cmd_if = " &
    // "if lexpr then command_list elsif_clauses else_clause endif")
call ifile_append (ifile, "SEQ elsif_clauses = cmd_elseif*")
call ifile_append (ifile, "SEQ cmd_elseif = elsif lexpr then command_list")
call ifile_append (ifile, "SEQ else_clause = cmd_else*")
call ifile_append (ifile, "SEQ cmd_else = else command_list")
call ifile_append (ifile, "SEQ cmd_include = include include_arg")
call ifile_append (ifile, "KEY include")
call ifile_append (ifile, "ARG include_arg = ( string_literal )")
call ifile_append (ifile, "SEQ cmd_quit = quit_cmd quit_arg*")
call ifile_append (ifile, "ALT quit_cmd = quit | exit")
call ifile_append (ifile, "KEY quit")
call ifile_append (ifile, "KEY exit")
call ifile_append (ifile, "ARG quit_arg = ( expr )")
call ifile_append (ifile, "SEQ cmd_beam_polarization = " &
    // "beam_polarization '=' bp_mode options*")
call ifile_append (ifile, "KEY beam_polarization")
call ifile_append (ifile, "ALT bp_mode = off | bp_defs")
call ifile_append (ifile, "KEY off")
call ifile_append (ifile, "LIS bp_defs = bp_def, bp_def*")
call ifile_append (ifile, "ARG arg_unary = ( expr )")
call ifile_append (ifile, "ARG arg_binary = (expr, expr)")
call ifile_append (ifile, "ARG arg_tenary = (expr, expr, expr)")
call ifile_append (ifile, "ALT bp_def = " &
    // "none | bp_circ | bp_trans | bp_axis | bp_long | bp_diag | " &
    // "bp_dens")
call ifile_append (ifile, "SEQ bp_circ = circular arg_unary")
call ifile_append (ifile, "KEY circular")
call ifile_append (ifile, "SEQ bp_trans = transverse arg_binary")
call ifile_append (ifile, "KEY transverse")
call ifile_append (ifile, "SEQ bp_axis = axis arg_tenary")
call ifile_append (ifile, "KEY axis")
call ifile_append (ifile, "SEQ bp_long = longitudinal arg_unary")
call ifile_append (ifile, "KEY longitudinal")
call ifile_append (ifile, "SEQ bp_dens = density_matrix arg_binary")
call ifile_append (ifile, "KEY density_matrix")
call ifile_append (ifile, "SEQ bp_diag = diagonal_density bp_diag_args")
call ifile_append (ifile, "KEY diagonal_density")
call ifile_append (ifile, "ARG bp_diag_args = ( bp_diag_entry+ )")
call ifile_append (ifile, "SEQ bp_diag_entry = expr ':' expr")
call ifile_append (ifile, "SEQ cmd_write_analysis = " &
    // "write_analysis_clause options*")
call ifile_append (ifile, "SEQ cmd_compile_analysis = " &
    // "compile_analysis_clause options*")
call ifile_append (ifile, "SEQ write_analysis_clause = " &
    // "write_analysis write_analysis_arg*")
call ifile_append (ifile, "SEQ compile_analysis_clause = " &
    // "compile_analysis write_analysis_arg*")
call ifile_append (ifile, "KEY write_analysis")
call ifile_append (ifile, "KEY compile_analysis")
call ifile_append (ifile, "ARG write_analysis_arg = ( analysis_tag* )")
call ifile_append (ifile, "SEQ cmd_histogram_writer = " &
    // "histogram_writer '=' writer_macro")
call ifile_append (ifile, "KEY histogram_writer")

```

```

call ifile_append (ifile, "SEQ cmd_plot_writer = " &
// "plot_writer '=' writer_macro")
call ifile_append (ifile, "KEY plot_writer")
call ifile_append (ifile, "GRO writer_macro = '{' command_list '}'")
call define_expr_syntax (ifile, particles=.true., analysis=.true.)
end subroutine define_cmd_list_syntax

```

<Commands: public>+≡

```
public :: lexer_init_cmd_list
```

<Commands: procedures>+≡

```

subroutine lexer_init_cmd_list (lexer, parent_lexer)
type(lexer_t), intent(out) :: lexer
type(lexer_t), intent(in), optional, target :: parent_lexer
call lexer_init (lexer, &
comment_chars = "#!", &
quote_chars = "'", &
quote_match = '"', &
single_chars = "()[]{}.,;:&%'$@", &
special_class = (/ "+-*/^", "<>=~ " /) , &
keyword_list = syntax_get_keyword_list_ptr (syntax_cmd_list), &
parent = parent_lexer)
end subroutine lexer_init_cmd_list

```

17.2.7 Test

<Commands: public>+≡

```
public :: command_test
```

<Commands: procedures>+≡

```

subroutine command_test ()
integer :: u
type(stream_t), target :: stream
type(lexer_t), target :: lexer
type(parse_tree_t) :: parse_tree
type(command_list_t), target :: command_list
type(rt_data_t), target :: global
print *, "* Initialization"
call rt_data_global_init (global)
allocate (global%prc_lib)
call syntax_model_file_init ()
call syntax_phs_forest_init ()
call syntax_pexpr_init ()
call syntax_cmd_list_init ()
call lexer_init_cmd_list (lexer)
print *, "* Open 'commands2.sin'"
u = free_unit ()
open (unit=u, file="commands2.sin")
call stream_init (stream, u)
print *, "* Parse"
global%lexer => lexer
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_cmd_list, lexer)

```

```

call parse_tree_write (parse_tree)
print *
print *, "* Compile command list"
call var_list_append_string (global%var_list, name = "$library_name", sval = "commands2")
call var_list_append_string (global%var_list, name = "$model_name", sval = "SM")
call process_library_init (global%prc_lib, var_str("commands2"), global%os_data)
call model_list_read_model (var_str("SM"), var_str("SM.mdl"), global%os_data, global%model)
call var_list_init_copies (global%var_list, model_get_var_list_ptr (global%model))
call var_list_synchronize (global%var_list, model_get_var_list_ptr (global%model), &
    reset_pointers = .true.)
call var_list_set_string (global%var_list, var_str("$model_name"), &
    model_get_name (global%model), is_known=.true.)
if (associated (parse_tree_get_root_ptr (parse_tree))) then
    call command_list_compile &
        (command_list, parse_tree_get_root_ptr (parse_tree), global)
end if
print *, "* Execute command list"
call command_list_execute (command_list, global)
print *
print *, "* Cleanup"
call stream_final (stream)
close (u)
call lexer_final (lexer)
call command_list_final (command_list)
call process_store_final ()
call model_list_final ()
call syntax_cmd_list_final ()
call syntax_pexpr_final ()
call syntax_phs_forest_final ()
call syntax_model_file_final ()
call rt_data_global_final (global)
end subroutine command_test

```

17.3 Toplevel module WHIZARD

```

<whizard.f90>≡
  <File header>

  module whizard

    <Use file utils>
    <Use strings>
    use limits, only: VERSION_STRING !NODEP!
    use limits, only: EOF, BACKSLASH !NODEP!
    use diagnostics !NODEP!
    use ifiles
    use formats
    use md5
    use os_interface
    use lexers
    use parser
    use colors

```



```

use state_matrices
use analysis
use variables
use user_code_interface
use expressions
use particles
use models
use sorting
use evaluators
use phs_forests
use hard_interactions
use beams
use polarizations
use processes
use decays
use process_libraries
use hepmc_interface
use interactions
use strfun
use slha_interface
use cascades
use events
use rt_data
use commands
use vamp !NODEP!

⟨Standard module head⟩

⟨WHIZARD: public⟩

⟨WHIZARD: variables⟩

save

contains

⟨WHIZARD: procedures⟩

end module whizard

```

17.3.1 Initialization and finalization

These procedures initialize and finalize global variables. Most of them are collected in the `global` data record located here, the others are syntax tables located in various modules, which do not change during program execution. Furthermore, there is a global model list and a global process store, which get filled during program execution but are finalized here.

During initialization, we can preload a default model and initialize a default library for setting up processes. The default library is loaded if requested by the setup. Further libraries can be loaded as specified by command-line flags.

```

⟨WHIZARD: variables⟩≡
  type(rt_data_t), target :: global

```

```

<WHIZARD: public>≡
    public :: whizard_init

<WHIZARD: procedures>≡
    subroutine whizard_init &
        (preload_model, preload_libs, default_lib, &
         rebuild_library, rebuild_user, &
         rebuild_phs, rebuild_grids, rebuild_events, &
         recompile_library, &
         time_estimate, &
         paths, &
         user_code_enable, &
         n_user_src, user_src, &
         n_user_lib, user_lib, &
         user_target)
    type(string_t), intent(in) :: preload_model, preload_libs
    type(string_t), intent(in) :: default_lib
    logical, intent(in) :: rebuild_library, rebuild_user
    logical, intent(in) :: rebuild_phs, rebuild_grids
    logical, intent(in) :: rebuild_events
    logical, intent(in) :: recompile_library
    logical, intent(in) :: time_estimate
    type(paths_t), intent(in), optional :: paths
    integer, intent(in), optional :: n_user_src, n_user_lib
    logical, intent(in), optional :: user_code_enable
    type(string_t), intent(in), optional :: user_src, user_lib, user_target
    type(string_t) :: filename, libname, libs
    type(var_list_t), pointer :: model_vars
    logical :: user
    integer :: n_src, n_lib
    type(string_t), dimension(:), allocatable :: src, lib
    integer :: i
    call rt_data_global_init (global, paths)
    user = .false.
    if (present (user_code_enable)) user = user_code_enable
    n_src = 0
    if (present (n_user_src) .and. present (user_src)) n_src = n_user_src
    n_lib = 0
    if (present (n_user_lib) .and. present (user_lib)) n_lib = n_user_lib
    if (user) then
        call splice (user_src, n_src, src)
        call splice (user_lib, n_lib, lib)
        call user_code_init (src, lib, user_target, rebuild_user, global%os_data)
    end if
    call var_list_append_log &
        (global%var_list, var_str ("?rebuild_library"), rebuild_library, &
         intrinsic=.true.)
    call var_list_append_log &
        (global%var_list, var_str ("?rebuild_phase_space"), rebuild_phs, &
         intrinsic=.true.)
    call var_list_append_log &
        (global%var_list, var_str ("?rebuild_grids"), rebuild_grids, &
         intrinsic=.true.)
    call var_list_append_log &
        (global%var_list, var_str ("?rebuild_events"), rebuild_events, &

```

```

        intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?recompile_library"), recompile_library, &
    intrinsic=.true.)
call var_list_append_log &
    (global%var_list, var_str ("?time_estimate"), time_estimate, &
    intrinsic=.true.)
call init_syntax_tables ()
call process_library_store_load_static &
    (global%os_data, global%prc_lib, global%model, global%var_list)
libs = adjustl (preload_libs)
SCAN_LIBS: do while (libs /= "")
    call split (libs, libname, " ")
    call process_library_store_append &
        (libname, global%os_data, global%prc_lib)
    call process_library_load &
        (global%prc_lib, global%os_data, global%model, global%var_list, &
        ignore=.true.)
end do SCAN_LIBS
if (.not. associated (global%prc_lib)) then
    call process_library_store_append &
        (default_lib, global%os_data, global%prc_lib)
    if (.not. (rebuild_library .or. recompile_library)) then
        call process_library_load (global%prc_lib, &
            global%os_data, global%model, global%var_list, ignore=.true.)
    else
        call var_list_set_string (global%var_list, &
            var_str ("$library_name"), &
            process_library_get_name (global%prc_lib), is_known=.true.)
    end if
end if
filename = preload_model // ".mdl"
call model_list_read_model &
    (preload_model, filename, global%os_data, global%model)
if (associated (global%model)) then
    model_vars => model_get_var_list_ptr (global%model)
    call var_list_init_copies (global%var_list, model_vars)
    call var_list_synchronize &
        (global%var_list, model_vars, reset_pointers = .true.)
    call msg_message ("Using model: " &
        // char (model_get_name (global%model)))
    call var_list_set_string (global%var_list, var_str ("$model_name"), &
        model_get_name (global%model), is_known=.true.)
end if
contains
subroutine splice (string, n, array)
    type(string_t), intent(in) :: string
    integer :: n
    type(string_t), dimension(:), allocatable :: array
    integer :: i
    type(string_t) :: buffer
    allocate (array (n))
    buffer = string
    do i = 1, n

```

```

        call split (buffer, array(i), " ")
    end do
end subroutine splice
end subroutine whizard_init

```

Initialize/finalize the syntax tables used by WHIZARD:

```

<WHIZARD: public>+≡
    public :: init_syntax_tables
    public :: final_syntax_tables

<WHIZARD: procedures>+≡
    subroutine init_syntax_tables ()
        call syntax_model_file_init ()
        call syntax_phs_forest_init ()
        call syntax_pexpr_init ()
        call syntax_slha_init ()
        call syntax_cmd_list_init ()
    end subroutine init_syntax_tables

    subroutine final_syntax_tables ()
        call syntax_model_file_final ()
        call syntax_phs_forest_final ()
        call syntax_pexpr_final ()
        call syntax_slha_final ()
        call syntax_cmd_list_final ()
    end subroutine final_syntax_tables

```

Write the syntax tables to external files.

```

<WHIZARD: public>+≡
    public :: write_syntax_tables

<WHIZARD: procedures>+≡
    subroutine write_syntax_tables ()
        integer :: unit
        character(*), parameter :: file_model = "whizard.model_file.syntax"
        character(*), parameter :: file_phs = "whizard.phase_space_file.syntax"
        character(*), parameter :: file_pexpr = "whizard.prt_expressions.syntax"
        character(*), parameter :: file_slha = "whizard.slha.syntax"
        character(*), parameter :: file_sindarin = "whizard.sindarin.syntax"
        unit = free_unit ()
        print *, "Writing file '" // file_model // "'"
        open (unit=unit, file=file_model, status="replace", action="write")
        write (unit, "(A)")  VERSION_STRING
        write (unit, "(A)")  "Syntax definition file: " // file_model
        call syntax_model_file_write (unit)
        close (unit)
        print *, "Writing file '" // file_phs // "'"
        open (unit=unit, file=file_phs, status="replace", action="write")
        write (unit, "(A)")  VERSION_STRING
        write (unit, "(A)")  "Syntax definition file: " // file_phs
        call syntax_phs_forest_write (unit)
        close (unit)
        print *, "Writing file '" // file_pexpr // "'"
        open (unit=unit, file=file_pexpr, status="replace", action="write")

```

```

write (unit, "(A)")  VERSION_STRING
write (unit, "(A)")  "Syntax definition file: " // file_pexpr
call syntax_pexpr_write (unit)
close (unit)
print *, "Writing file '" // file_slha // "'"
open (unit=unit, file=file_slha, status="replace", action="write")
write (unit, "(A)")  VERSION_STRING
write (unit, "(A)")  "Syntax definition file: " // file_slha
call syntax_slha_write (unit)
close (unit)
print *, "Writing file '" // file_sindarin // "'"
open (unit=unit, file=file_sindarin, status="replace", action="write")
write (unit, "(A)")  VERSION_STRING
write (unit, "(A)")  "Syntax definition file: " // file_sindarin
call syntax_cmd_list_write (unit)
close (unit)
end subroutine write_syntax_tables

```

Apart from the global data which have been initialized above, the process and model lists need to be finalized.

```

<WHIZARD: public>+≡
  public :: whizard_final

<WHIZARD: procedures>+≡
  subroutine whizard_final ()
    call rt_data_global_final (global)
    call user_code_final ()
    call decay_store_final ()
    call process_store_final ()
    call model_list_final ()
    call final_syntax_tables ()
  end subroutine whizard_final

```

17.3.2 Execute command lists

Process commands given on the command line, stored as an `ifile`. The whole input is read, compiled and executed as a whole.

```

<WHIZARD: public>+≡
  public :: whizard_process_ifile

<WHIZARD: procedures>+≡
  subroutine whizard_process_ifile (ifile, quit, quit_code)
    type(ifile_t), intent(in) :: ifile
    logical, intent(out) :: quit
    integer, intent(out) :: quit_code
    type(lexer_t), target :: lexer
    type(stream_t), target :: stream
    call msg_message ("Reading commands given on the command line")
    call lexer_init_cmd_list (lexer)
    call stream_init (stream, ifile)
    call whizard_process_stream (stream, lexer, quit, quit_code)
    call stream_final (stream)
  end subroutine whizard_process_ifile

```

```

        call lexer_final (lexer)
    end subroutine whizard_process_ifile

```

Process standard input as a command list. The whole input is read, compiled and executed as a whole.

```

<WHIZARD: public>+≡
    public :: whizard_process_stdin

<WHIZARD: procedures>+≡
    subroutine whizard_process_stdin (quit, quit_code)
        logical, intent(out) :: quit
        integer, intent(out) :: quit_code
        type(lexer_t), target :: lexer
        type(stream_t), target :: stream
        call msg_message ("Reading commands from standard input")
        call lexer_init_cmd_list (lexer)
        call stream_init (stream, 5)
        call whizard_process_stream (stream, lexer, quit, quit_code)
        call stream_final (stream)
        call lexer_final (lexer)
    end subroutine whizard_process_stdin

```

Process a file as a command list.

```

<WHIZARD: public>+≡
    public :: whizard_process_file

<WHIZARD: procedures>+≡
    subroutine whizard_process_file (file, quit, quit_code)
        type(string_t), intent(in) :: file
        logical, intent(out) :: quit
        integer, intent(out) :: quit_code
        integer :: u
        type(lexer_t), target :: lexer
        type(stream_t), target :: stream
        logical :: exist
        call msg_message ("Reading commands from file '" // char (file) // "'")
        inquire (file=char(file), exist=exist)
        if (exist) then
            u = free_unit ()
            call lexer_init_cmd_list (lexer)
            call stream_init (stream, char (file))
            call whizard_process_stream (stream, lexer, quit, quit_code)
            call stream_final (stream)
            call lexer_final (lexer)
        else
            call msg_error ("File '" // char (file) // "' not found")
        end if
    end subroutine whizard_process_file

```

```

<WHIZARD: procedures>+≡
    subroutine whizard_process_stream (stream, lexer, quit, quit_code)
        type(stream_t), intent(inout), target :: stream
        type(lexer_t), intent(inout), target :: lexer

```

```

logical, intent(out) :: quit
integer, intent(out) :: quit_code
type(parse_tree_t) :: parse_tree
type(command_list_t), target :: command_list
global%lexer => lexer
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_cmd_list, lexer)
if (associated (parse_tree_get_root_ptr (parse_tree))) then
    call command_list_compile &
        (command_list, parse_tree_get_root_ptr (parse_tree), global)
end if
call command_list_execute (command_list, global)
call command_list_final (command_list)
quit = global%quit
quit_code = global%quit_code
end subroutine whizard_process_stream

```

17.3.3 The WHIZARD shell

This procedure implements interactive mode. One line is processed at a time.

```

<WHIZARD: public>+≡
    public :: whizard_shell

<WHIZARD: procedures>+≡
    subroutine whizard_shell (quit_code)
        integer, intent(out) :: quit_code
        type(lexer_t), target :: lexer
        type(stream_t), target :: stream
        type(string_t) :: prompt1
        type(string_t) :: prompt2
        type(string_t) :: input
        type(string_t) :: extra
        integer :: last
        integer :: iostat
        logical :: mask_tmp
        logical :: quit
        call msg_message ("Launching interactive shell")
        call lexer_init_cmd_list (lexer)
        prompt1 = "whish? "
        prompt2 = "      > "
        COMMAND_LOOP: do
            call put (6, prompt1)
            call get (5, input, iostat=iostat)
            if (iostat > 0 .or. iostat == EOF) exit COMMAND_LOOP
            CONTINUE_INPUT: do
                last = len_trim (input)
                if (extract (input, last, last) /= BACKSLASH) exit CONTINUE_INPUT
                call put (6, prompt2)
                call get (5, extra, iostat=iostat)
                if (iostat > 0) exit COMMAND_LOOP
                input = replace (input, last, extra)
            end do CONTINUE_INPUT
            call stream_init (stream, input)

```

```

        mask_tmp = mask_fatal_errors
        mask_fatal_errors = .true.
        call whizard_process_stream (stream, lexer, quit, quit_code)
        msg_count = 0
        mask_fatal_errors = mask_tmp
        call stream_final (stream)
        if (quit) exit COMMAND_LOOP
    end do COMMAND_LOOP
    print *
    call lexer_final (lexer)
end subroutine whizard_shell

```

17.3.4 Self-tests

This is for developers only, but needs a well-defined interface.

```

<WHIZARD: public>+≡
    public :: whizard_check

<WHIZARD: procedures>+≡
    subroutine whizard_check (check, lhpdf_present)
        type(string_t), intent(in) :: check
        logical, intent(in) :: lhpdf_present
        type(lexer_t), target :: lexer
        global%lexer => lexer
        call msg_message (repeat (' ', 76), 0)
        call msg_message ("Running self-test: " // char (check), 0)
        call msg_message (repeat ('-', 76), 0)
        select case (char (check))
            case ("analysis"); call analysis_test ()
            case ("beams"); call beam_test ()
            case ("cascades"); call cascade_test ()
            case ("colors"); call color_test ()
            case ("commands"); call command_test ()
            case ("evaluators"); call evaluator_test (global%model)
            case ("events"); call event_test ()
            case ("expressions"); call expressions_test ()
            case ("formats"); call format_test ()
            case ("hard_interactions"); call hard_interaction_test (global%model)
            case ("hepmc"); call hepmc_test ()
            case ("interactions"); call interaction_test ()
            case ("lexers"); call lexer_test (lexer, 6)
            case ("md5"); call md5_test ()
            case ("models"); call models_test ()
            case ("os_interface"); call os_interface_test ()
            case ("parser"); call parse_test ()
            case ("particles"); call particles_test ()
            case ("phs_forests"); call phs_forest_test ()
            case ("polarizations"); call polarization_test ()
            case ("processes"); call process_test ()
            case ("process_libraries"); call process_libraries_test ()
            case ("slha_interface"); call slha_test ()
            case ("sorting"); call sorting_test ()
            case ("state_matrices"); call state_matrix_test ()
        end select
    end subroutine whizard_check

```



```

        case ("strfun"); call strfun_test (lhpdf_present)
    case default
        call msg_error ("Self-test '" // char (check) // "' not implemented.")
    end select
end subroutine whizard_check

```

17.4 Driver program

The main program handles command options, initializes the environment, and runs WHIZARD in a particular mode (interactive, file, standard input).

```

<Limits: public parameters>+=
    integer, parameter, public :: CMDLINE_ARG_LEN = 1000

<main.f90>=
    <File header>

    program main

    <Use strings>
        use system_dependencies !NODEP!
        use limits, only: CMDLINE_ARG_LEN !NODEP!
        use diagnostics !NODEP!
        use ifiles
        use os_interface
        use whizard

    implicit none

    ! Main program variable declarations
    character(CMDLINE_ARG_LEN) :: arg
    character(2) :: option
    type(string_t) :: long_option, value
    integer :: i, j, arg_len, arg_status
    logical :: look_for_options
    logical :: interactive
    type(string_t) :: files, this, model, libname, library, libraries, logfile
    type(string_t) :: check, checks
    logical :: user_code_enable = .false.
    integer :: n_user_src = 0, n_user_lib = 0
    type(string_t) :: user_src, user_lib, user_target
    type(paths_t) :: paths
    logical :: rebuild_library, rebuild_user
    logical :: rebuild_phs, rebuild_grids, rebuild_events
    logical :: recompile_library
    logical :: time_estimate
    type(ifile_t) :: commands
    type(string_t) :: command

    ! Exit status
    logical :: quit = .false.
    integer :: quit_code = 0

```

```

! Initial values
look_for_options = .true.
interactive = .false.
files = ""
model = "SM"
libname = "processes"
library = ""
logfile = "whizard.log"
libraries = ""
check = ""
checks = ""
user_src = ""
user_lib = ""
user_target = ""
rebuild_library = .false.
rebuild_user = .false.
rebuild_phs = .false.
rebuild_grids = .false.
rebuild_events = .false.
recompile_library = .false.
time_estimate = .true.
call paths_init (paths)

! Read and process options
i = 0
SCAN_CMDLINE: do
  i = i + 1
  call get_command_argument (i, arg, arg_len, arg_status)
  select case (arg_status)
  case (0)
  case (-1)
    call msg_error (" Command argument truncated: '" // arg // "'")
  case default
    exit SCAN_CMDLINE
  end select
  if (look_for_options) then
    select case (arg(1:2))
    case ("--")
      value = trim (arg)
      call split (value, long_option, "=")
      select case(char (long_option))
      case ("--version")
        call no_option_value (long_option, value)
        call print_version (); stop
      case ("--help")
        call no_option_value (long_option, value)
        call print_usage (); stop
      case ("--prefix")
        paths%prefix = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
      case ("--exec-prefix")
        paths%exec_prefix = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
      case ("--bindir")

```

```

        paths%bindir = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--libdir")
        paths%libdir = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--includedir")
        paths%includedir = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--datarootdir")
        paths%datarootdir = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--libtool")
        paths%libtool = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--lhapdfdir")
        paths%lhapdfdir = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--check")
        check = get_option_value (i, long_option, value)
        checks = checks // " " // check
        cycle SCAN_CMDLINE
    case ("--execute")
        command = get_option_value (i, long_option, value)
        call ifile_append (commands, command)
        cycle SCAN_CMDLINE
    case ("--interactive")
        call no_option_value (long_option, value)
        interactive = .true.
        cycle SCAN_CMDLINE
    case ("--library")
        library = get_option_value (i, long_option, value)
        libraries = libraries // " " // library
        cycle SCAN_CMDLINE
    case ("--localprefix")
        paths%localprefix = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--logfile")
        logfile = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--no-logfile")
        call no_option_value (long_option, value)
        logfile = ""
        cycle SCAN_CMDLINE
    case ("--model")
        model = get_option_value (i, long_option, value)
        cycle SCAN_CMDLINE
    case ("--rebuild")
        call no_option_value (long_option, value)
        rebuild_library = .true.
        rebuild_user = .true.
        rebuild_phs = .true.
        rebuild_grids = .true.
        rebuild_events = .true.
        cycle SCAN_CMDLINE

```

```

case ("--rebuild-library")
    call no_option_value (long_option, value)
    rebuild_library = .true.
    cycle SCAN_CMDLINE
case ("--rebuild-user")
    call no_option_value (long_option, value)
    rebuild_user = .true.
    cycle SCAN_CMDLINE
case ("--rebuild-phase-space")
    call no_option_value (long_option, value)
    rebuild_phs = .true.
    cycle SCAN_CMDLINE
case ("--rebuild-grids")
    call no_option_value (long_option, value)
    rebuild_grids = .true.
    cycle SCAN_CMDLINE
case ("--rebuild-events")
    call no_option_value (long_option, value)
    rebuild_events = .true.
    cycle SCAN_CMDLINE
case ("--recompile")
    call no_option_value (long_option, value)
    recompile_library = .true.
    rebuild_grids = .true.
    cycle SCAN_CMDLINE
case ("--time-estimate")
    call no_option_value (long_option, value)
    time_estimate = .true.
    cycle SCAN_CMDLINE
case ("--no-time-estimate")
    call no_option_value (long_option, value)
    time_estimate = .false.
    cycle SCAN_CMDLINE
case ("--user")
    user_code_enable = .true.
    cycle SCAN_CMDLINE
case ("--user-src")
    if (user_src == "") then
        user_src = get_option_value (i, long_option, value)
    else
        user_src = user_src // " " &
            // get_option_value (i, long_option, value)
    end if
    n_user_src = n_user_src + 1
    cycle SCAN_CMDLINE
case ("--user-lib")
    if (user_lib == "") then
        user_lib = get_option_value (i, long_option, value)
    else
        user_lib = user_lib // " " &
            // get_option_value (i, long_option, value)
    end if
    n_user_lib = n_user_lib + 1
    cycle SCAN_CMDLINE

```

```

case ("--user-target")
    user_target = get_option_value (i, long_option, value)
    cycle SCAN_CMDLINE
case ("--write-syntax-tables")
    call no_option_value (long_option, value)
    call init_syntax_tables ()
    call write_syntax_tables ()
    call final_syntax_tables ()
    stop
    cycle SCAN_CMDLINE
case default
    call print_usage ()
    call msg_fatal ("Option '" // trim (arg) // "' not recognized")
end select
end select
select case (arg(1:1))
case ("-")
    j = 1
    if (len_trim (arg) == 1) then
        look_for_options = .false.
    else
        SCAN_SHORT_OPTIONS: do
            j = j + 1
            if (j > len_trim (arg)) exit SCAN_SHORT_OPTIONS
            option = "-" // arg(j:j)
            select case (option)
            case ("-V")
                call print_version (); stop
            case ("-?", "-h")
                call print_usage (); stop
            case ("-e")
                command = get_option_value (i, var_str (option))
                call ifile_append (commands, command)
                cycle SCAN_CMDLINE
            case ("-i")
                interactive = .true.
                cycle SCAN_SHORT_OPTIONS
            case ("-l")
                if (j == len_trim (arg)) then
                    library = get_option_value (i, var_str (option))
                else
                    library = trim (arg(j+1:))
                end if
                libraries = libraries // " " // library
                cycle SCAN_CMDLINE
            case ("-L")
                if (j == len_trim (arg)) then
                    logfile = get_option_value (i, var_str (option))
                else
                    logfile = trim (arg(j+1:))
                end if
                cycle SCAN_CMDLINE
            case ("-m")
                if (j < len_trim (arg)) call msg_fatal &

```

```

        ("Option '" // option // "' needs a value")
        model = get_option_value (i, var_str (option))
        cycle SCAN_CMDLINE
    case ("-r")
        rebuild_library = .true.
        rebuild_user = .true.
        rebuild_phs = .true.
        rebuild_grids = .true.
        rebuild_events = .true.
        cycle SCAN_SHORT_OPTIONS
    case ("-u")
        user_code_enable = .true.
        cycle SCAN_SHORT_OPTIONS
    case default
        call print_usage ()
        call msg_fatal &
            ("Option '" // option // "' not recognized")
    end select
end do SCAN_SHORT_OPTIONS
end if
case default
    files = files // " " // trim (arg)
end select
else
    files = files // " " // trim (arg)
end if
end do SCAN_CMDLINE

! Overall initialization
if (logfile /= "") call logfile_init (logfile)
call mask_term_signals ()
call msg_banner ()
call whizard_init &
    (preload_model=model, preload_libs=libraries, default_lib=libname, &
    rebuild_library=rebuild_library, &
    rebuild_user=rebuild_user, &
    rebuild_phs=rebuild_phs, &
    rebuild_grids=rebuild_grids, &
    rebuild_events=rebuild_events, &
    recompile_library=recompile_library, &
    time_estimate=time_estimate, &
    paths=paths, &
    user_code_enable=user_code_enable, &
    n_user_src=n_user_src, user_src=user_src, &
    n_user_lib=n_user_lib, user_lib=user_lib, &
    user_target=user_target)

! Run any self-checks (and no commands)
if (checks /= "") then
    checks = trim (adjustl (checks))
    RUN_CHECKS: do while (checks /= "")
        call split (checks, check, " ")
        call whizard_check (check, LHAPDF_AVAILABLE)
    end do
end if

```

```

        end do RUN_CHECKS
        quit = .true.
    end if

    ! Run commands given on the command line
    if (.not. quit .and. ifile_get_length (commands) > 0) then
        call whizard_process_ifile (commands, quit, quit_code)
    end if

    if (.not. quit) then
        ! Process commands from standard input
        if (.not. interactive .and. files == "") then
            call whizard_process_stdin (quit, quit_code)

            ! ... or process commands from file
        else
            files = trim (adjustl (files))
            SCAN_FILES: do while (files /= "")
                call split (files, this, " ")
                call whizard_process_file (this, quit, quit_code)
                if (quit) exit SCAN_FILES
            end do SCAN_FILES
        end if
    end if

    ! Enter an interactive shell if requested
    if (.not. quit .and. interactive) then
        call whizard_shell (quit_code)
    end if

    ! Overall finalization
    call ifile_final (commands)
    call whizard_final ()
    call terminate_now_if_signal ()
    call release_term_signals ()
    call msg_terminate (quit_code = quit_code)

    !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
contains

    subroutine no_option_value (option, value)
        type(string_t), intent(in) :: option, value
        if (value /= "") then
            call msg_error (" Option '" // char (option) // "' should have no value")
        end if
    end subroutine no_option_value

    function get_option_value (i, option, value) result (string)
        type(string_t) :: string
        integer, intent(inout) :: i
        type(string_t), intent(in) :: option
        type(string_t), intent(in), optional :: value
        character(CMDLINE_ARG_LEN) :: arg

```

```

character(CMDLINE_ARG_LEN) :: arg_value
integer :: arg_len, arg_status
logical :: has_value
if (present (value)) then
    has_value = value /= ""
else
    has_value = .false.
end if
if (has_value) then
    string = value
else
    i = i + 1
    call get_command_argument (i, arg_value, arg_len, arg_status)
    select case (arg_status)
    case (0)
    case (-1)
        call msg_error (" Option value truncated: '" // arg // "'")
    case default
        call print_usage ()
        call msg_fatal (" Option '" // char (option) // "' needs a value")
    end select
    select case (arg(1:1))
    case ("-")
        call print_usage ()
        call msg_fatal (" Option '" // char (option) // "' needs a value")
    end select
    string = trim (arg_value)
end if
end function get_option_value

subroutine print_version ()
    print "(A)", "WHIZARD " // WHIZARD_VERSION
    print "(A)", "Copyright (C) 1999-2012 Wolfgang Kilian, Thorsten Ohl, Juergen Reuter,"
    print "(A)", "                                Christian Speckner"
    print "(A)", "This is free software; see the source for copying conditions. There is NO"
    print "(A)", "warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE."
    print *
end subroutine print_version

subroutine print_usage ()
    print "(A)", "WHIZARD " // WHIZARD_VERSION
    print "(A)", "Usage: whizard [OPTIONS] [FILE]"
    print "(A)", "Run WHIZARD with the command list taken from FILE(s)"
    print "(A)", "Options for resetting default directories and tools" &
        // "(GNU naming conventions):"
    print "(A)", "    --prefix DIR"
    print "(A)", "    --exec_prefix DIR"
    print "(A)", "    --bindir DIR"
    print "(A)", "    --libdir DIR"
    print "(A)", "    --includedir DIR"
    print "(A)", "    --datarootdir DIR"
    print "(A)", "    --libtool LOCAL_LIBTOOL"
    print "(A)", "    --lhapdfdir DIR    (PDF sets directory)"
    print "(A)", "Other options:"

```



```

print "(A)", "-h, --help          display this help and exit"
print "(A)", "-e, --execute CMDS  execute SINDARIN CMDS before reading FILE(s)"
print "(A)", "-i, --interactive    run interactively after reading FILE(s)"
print "(A)", "-l, --library          preload process library NAME"
print "(A)", "    --localprefix DIR"
print "(A)", "    search in DIR for local models (default: ~/.whizard)"
print "(A)", "-L, --logfile FILE      write log to FILE (default: 'whizard.log')"
print "(A)", "-m, --model NAME          preload model NAME (default: 'SM')"
print "(A)", "    --no-logfile            do not write a logfile"
print "(A)", "-r, --rebuild              rebuild all (see below)"
print "(A)", "    --rebuild-library"
print "(A)", "    rebuild process code library"
print "(A)", "    --rebuild-user          rebuild user-provided code"
print "(A)", "    --rebuild-phase-space"
print "(A)", "    rebuild phase-space configuration"
print "(A)", "    --rebuild-grids        rebuild integration grids"
print "(A)", "    --rebuild-events       rebuild event samples"
print "(A)", "    --recompile            recompile process code, ignoring any existing library"
print "(A)", "-u --user                  enable user-provided code"
print "(A)", "    --user-src FILE        user-provided source file"
print "(A)", "    --user-lib FILE        user-provided library file"
print "(A)", "    --user-target BN       basename of created user library (default: user)"
print "(A)", "-V, --version              output version information and exit"
print "(A)", "    --write-syntax-tables"
print "(A)", "    write the internal syntax tables to files and exit"
print "(A)", "-                further options are taken as filenames"
print *
print "(A)", "With no FILE, read standard input."
end subroutine print_usage

end program main

```

17.5 Shower

(shower_interface.f90)≡
⟨File header⟩

```

module shower_interface

  use kinds, only: default, double !NODEP!
  use shower_basics_module !NODEP!
  use shower_module !NODEP!
  use shower_topythia_module !NODEP!
  use muli, muli_output_unit => output_unit !NODEP!
  use mlm_matching_module !NODEP!
  use ckkw_matching_module !NODEP!
  use tao_random_numbers !NODEP!
  use flavors
  use colors
  use particles
  use subevents
  use models
  use variables

```

```

    use iso_varying_string, string_t => varying_string !NODEP!
    <Use file utils>
    use event_formats
    use os_interface
    use diagnostics !NODEP!
    use lorentz !NODEP!
    use strfun
    use pdf_builtin !NODEP!

    <Standard module head>

    <Shower: public>

    <Shower: types>

contains

    <Shower: procedures>

end module shower_interface

<Shower: public>≡
    public :: shower_settings_t

<Shower: types>≡
    type :: shower_settings_t
        logical :: ps_isr_active = .false.
        logical :: ps_fsr_active = .false.
        logical :: ps_use_PYTHIA_shower = .false.
        logical :: hadronization_active = .false.
        logical :: mlm_matching = .false.
        logical :: ckkw_matching = .false.
        logical :: muli_active = .false.

        logical :: ps_PYTHIA_verbose = .false.
        type(string_t) :: ps_PYTHIA_PYGIVE

        !!! values present in PYTHIA and WHIZARDS PS,
        !!! comments denote corresponding PYTHIA values
        real(default) :: ps_mass_cutoff = 1._default      ! PARJ(82)
        real(default) :: ps_fsr_lambda = 0.29_default     ! PARP(72)
        real(default) :: ps_isr_lambda = 0.29_default     ! PARP(61)
        integer :: ps_max_n_flavors = 5                  ! MSTJ(45)
        logical :: ps_isr_alpha_s_running = .true.        ! MSTP(64)
        logical :: ps_fsr_alpha_s_running = .true.        ! MSTJ(44)
        real(default) :: ps_fixed_alpha_s = 0._default   ! PARU(111)
        logical :: ps_isr_pt_ordered = .false.
        logical :: ps_isr_angular_ordered = .true.        ! MSTP(62)
        real(default) :: ps_isr_primordial_kt_width = 0._default ! PARP(91)
        real(default) :: ps_isr_primordial_kt_cutoff = 5._default ! PARP(93)
        real(default) :: ps_isr_z_cutoff = 0.999_default ! 1-PARP(66)
        real(default) :: ps_isr_minenergy = 2._default    ! PARP(65)
        real(default) :: ps_isr_tscalefactor = 1._default
        logical :: ps_isr_only_onshell_emitted_partons = .true. ! MSTP(63)

```

```

!!! MLM settings
type(mlm_matching_settings_t) :: ms

!!! CKKW Matching
type(ckkw_matching_settings_t) :: ckkw_settings
type(ckkw_pseudo_shower_weights_t) :: ckkw_weights
end type shower_settings_t

```

Read in the shower, matching and hadronization settings

(Shower: public)+≡

```
public :: shower_settings_init
```

(Shower: procedures)≡

```

subroutine shower_settings_init(shower_settings, var_list)
  type(shower_settings_t), intent(out) :: shower_settings
  type(var_list_t), intent(in) :: var_list

```

```

  shower_settings%ps_isr_active = &
    var_list_get_lval(var_list, var_str("?ps_isr_active"))
  shower_settings%ps_fsr_active = &
    var_list_get_lval(var_list, var_str("?ps_fsr_active"))
  shower_settings%hadronization_active = &
    var_list_get_lval(var_list, var_str("?hadronization_active"))
  shower_settings%mlm_matching = &
    var_list_get_lval(var_list, var_str("?mlm_matching"))
  shower_settings%ckkw_matching = &
    var_list_get_lval(var_list, var_str("?ckkw_matching"))
  shower_settings%multi_active = &
    var_list_get_lval(var_list, var_str("?multi_active"))

```

```

!   if( (shower_settings%ps_fsr_active .eqv. .false.) .and. (shower_settings%ps_isr_active .eqv. .fal
!       .and. (shower_settings%hadronization_active .eqv. .false.) .and. (shower_settings%mlm_matchin
!       return
!   end if

```

```

  shower_settings%ps_use_PYTHIA_shower = &
    var_list_get_lval(var_list, var_str("?ps_use_PYTHIA_shower"))
  shower_settings%ps_PYTHIA_verbose = &
    var_list_get_lval(var_list, var_str("?ps_PYTHIA_verbose"))
  shower_settings%ps_PYTHIA_PYGIVE = &
    var_list_get_sval(var_list, var_str("$ps_PYTHIA_PYGIVE"))
  shower_settings%ps_mass_cutoff = &
    var_list_get_rval(var_list, var_str("ps_mass_cutoff"))
  shower_settings%ps_fsr_lambda = &
    var_list_get_rval(var_list, var_str("ps_fsr_lambda"))
  shower_settings%ps_isr_lambda = &
    var_list_get_rval(var_list, var_str("ps_isr_lambda"))
  shower_settings%ps_max_n_flavors = &
    var_list_get_ival(var_list, var_str("ps_max_n_flavors"))
  shower_settings%ps_isr_alpha_s_running = &
    var_list_get_lval(var_list, var_str("?ps_isr_alpha_s_running"))
  shower_settings%ps_fsr_alpha_s_running = &
    var_list_get_lval(var_list, var_str("?ps_fsr_alpha_s_running"))
  shower_settings%ps_fixed_alpha_s = &

```

```

        var_list_get_rval(var_list, var_str("ps_fixed_alpha_s"))
shower_settings%ps_isr_pt_ordered = &
        var_list_get_lval(var_list, var_str("?ps_isr_pt_ordered"))
shower_settings%ps_isr_angular_ordered = &
        var_list_get_lval(var_list, var_str("?ps_isr_angular_ordered"))
shower_settings%ps_isr_primordial_kt_width = &
        var_list_get_rval(var_list, var_str("ps_isr_primordial_kt_width"))
shower_settings%ps_isr_primordial_kt_cutoff = &
        var_list_get_rval(var_list, var_str("ps_isr_primordial_kt_cutoff"))
shower_settings%ps_isr_z_cutoff = &
        var_list_get_rval(var_list, var_str("ps_isr_z_cutoff"))
shower_settings%ps_isr_minenergy = &
        var_list_get_rval(var_list, var_str("ps_isr_minenergy"))
shower_settings%ps_isr_tscalefactor = &
        var_list_get_rval(var_list, var_str("ps_isr_tscalefactor"))
shower_settings%ps_isr_only_onshell_emitted_partons = &
        var_list_get_lval(var_list, var_str("?ps_isr_only_onshell_emitted_partons"))

!!! MLM matching
shower_settings%ms%mlm_Qcut_ME = var_list_get_rval(var_list, var_str("mlm_Qcut_ME"))
shower_settings%ms%mlm_Qcut_PS = var_list_get_rval(var_list, var_str("mlm_Qcut_PS"))
shower_settings%ms%mlm_ptmin = var_list_get_rval(var_list, var_str("mlm_ptmin"))
shower_settings%ms%mlm_etamax = var_list_get_rval(var_list, var_str("mlm_etamax"))
shower_settings%ms%mlm_Rmin = var_list_get_rval(var_list, var_str("mlm_Rmin"))
shower_settings%ms%mlm_Emin = var_list_get_rval(var_list, var_str("mlm_Emin"))
shower_settings%ms%mlm_nmaxMEjets = var_list_get_ival(var_list, var_str("mlm_nmaxMEjets"))

shower_settings%ms%mlm_ETclusfactor = var_list_get_rval(var_list, var_str("mlm_ETclusfactor"))
shower_settings%ms%mlm_ETclusminE = var_list_get_rval(var_list, var_str("mlm_ETclusminE"))
shower_settings%ms%mlm_etaclusfactor = var_list_get_rval(var_list, var_str("mlm_etaclusfactor"))
shower_settings%ms%mlm_Rclusfactor = var_list_get_rval(var_list, var_str("mlm_Rclusfactor"))
shower_settings%ms%mlm_Eclusfactor = var_list_get_rval(var_list, var_str("mlm_Eclusfactor"))

!!! CKKW matching
! TODO
end subroutine shower_settings_init

```

<Shower: public>+≡

```
public :: shower_settings_write
```

<Shower: procedures>+≡

```

subroutine shower_settings_write(shower_settings, unit)
  type(shower_settings_t), intent(in) :: shower_settings
  integer, intent(in), optional :: unit
  integer :: u
  u = output_unit (unit); if (u < 0) return
  write (u, "(A)") "Shower Settings:"
  write (u, *) "ps_isr_active" = ", shower_settings%ps_isr_active
  write (u, *) "ps_fsr_active" = ", shower_settings%ps_fsr_active
  if (shower_settings%ps_isr_active .or. shower_settings%ps_fsr_active) then
    write (u, *) "ps_use_PYTHIA_shower" = ", shower_settings%ps_use_PYTHIA_shower
    write (u, *) "ps_mass_cutoff" = ", shower_settings%ps_mass_cutoff
    write (u, *) "ps_max_n_flavors" = ", shower_settings%ps_max_n_flavors
  end if

```

```

if (shower_settings%ps_isr_active) then
  write (u, "(A)") " ISR Settings:"
  write (u, *) "ps_isr_pt_ordered" = ", shower_settings%ps_isr_pt_ordered
  write (u, *) "ps_isr_lambda" = ", shower_settings%ps_isr_lambda
  write (u, *) "ps_isr_alpha_s_running" = ", shower_settings%ps_isr_alpha_s_running
  write (u, *) "ps_isr_primordial_kt_width" = ", shower_settings%ps_isr_primordial_kt_width
  write (u, *) "ps_isr_primordial_kt_cutoff" = ", shower_settings%ps_isr_primordial_kt_cutoff
  write (u, *) "ps_isr_z_cutoff" = ", shower_settings%ps_isr_z_cutoff
  write (u, *) "ps_isr_minenergy" = ", shower_settings%ps_isr_minenergy
  write (u, *) "ps_isr_tscalefactor" = ", shower_settings%ps_isr_tscalefactor
end if
if (shower_settings%ps_fsr_active) then
  write (u, "(A)") " FSR Settings:"
  write (u, *) "ps_fsr_lambda" = ", shower_settings%ps_fsr_lambda
  write (u, *) "ps_fsr_alpha_s_running" = ", shower_settings%ps_fsr_alpha_s_running
end if
write (u, "(A)") "Hadronization Settings:"
write (u, *) "hadronization_active" = ", shower_settings%hadronization_active
write (u, "(A)") "Matching Settings:"
write (u, *) "mlm_matching" = ", shower_settings%mlm_matching
if (shower_settings%mlm_matching) then
  call mlm_matching_settings_write(shower_settings%ms, u)
end if
write (u, *) "ckkw_matching" = ", shower_settings%ckkw_matching
if (shower_settings%ckkw_matching) then
  ! TODO ckkw settings etc.
end if
write (u, *)
write (u, *) "ps_PYTHIA_verbose" = ", shower_settings%ps_PYTHIA_verbose
write (u, *) "ps_PYTHIA_PYGIVE" = ", char(shower_settings%ps_PYTHIA_PYGIVE)
end subroutine shower_settings_write

```

The wrapper subroutine for the shower and the hadronization interface and MLM matching. This should be the only subroutine called from WHIZARD.

<Shower: public>+≡

```
public :: apply_shower_particle_set
```

<Shower: procedures>+≡

```

subroutine apply_shower_particle_set(particle_set, shower_settings, model, &
  os_data, pdf_type, pdf_set, valid, vetoed)
  type(particle_set_t), intent(inout) :: particle_set
  type(shower_settings_t), intent(in) :: shower_settings
  type(model_t), pointer, intent(in) :: model
  type(os_data_t), intent(in) :: os_data
  integer, intent(in) :: pdf_type
  integer, intent(in) :: pdf_set
  logical, intent(inout) :: valid
  logical, intent(inout) :: vetoed
  real(kind=double) :: pdftest

  type(mlm_matching_data_t) :: mlm_matching_data
  logical, save :: matching_disabled=.false.
  procedure(shower_pdf), pointer :: pdf_func => null()

```

```

interface
  subroutine evolvePDFM (set, x, q, ff)
    integer, intent(in) :: set
    double precision, intent(in) :: x, q
    double precision, dimension(-6:6), intent(out) :: ff
  end subroutine evolvePDFM
end interface

if ((shower_settings%ps_fsr_active .eqv. .false.) .and. &
    (shower_settings%ps_isr_active.eqv..false.) .and. &
    (shower_settings%hadronization_active.eqv..false.) .and. &
    (shower_settings%mlm_matching.eqv..false.) ) then
  ! return if nothing to do
  return
end if

! return if already invalid or vetoed
if ((.not.valid) .or. vetoed) then
  return
end if
! ensure that lhpdf is initialized
if (pdf_type .eq. STRF_LHAPDF) then
  if (shower_settings%ps_isr_active .and. &
      (abs (particle_get_pdg (particle_set_get_particle (particle_set, 1)))>.1000) .and. &
      (abs (particle_get_pdg (particle_set_get_particle (particle_set, 2)))>.1000)) then
    call GetQ2max (0,pdftest)
    if (pdftest .eq. 0._double) then
      call msg_fatal (" ISR enabled, but LHAPDF not initialized," // &
                     char(10) // "      aborting simulation")
      return
    end if
  end if
  pdf_func => evolvePDFM
else if (pdf_type.eq. STRF_PDF_BUILTIN) then
  if (shower_settings%ps_use_PYTHIA_shower) then
    call msg_fatal (" builtin-pdfs can not be used for PYTHIA showers," // &
                   char(10) // "      aborting simulation")
    return
  end if
  pdf_func => pdf_evolve_LHAPDF
end if
if (shower_settings%mlm_matching .and. shower_settings%ckkw_matching) then
  call msg_fatal (" both MLM and CKKW matching activated," // &
                 char(10) // "      aborting simulation")
  return
end if

!   call shower_settings_write(shower_settings)

if(shower_settings%ps_PYTHIA_verbose.eqv..false.) then
  call PYGIVE('MSTU(12)=12345')
  call PYGIVE('MSTU(13)=0')
else
  call PYGIVE('MSTU(13)=1')

```

```

end if
!   pause

if(matching_disabled.eqv..false.) then
  !!! Check if the beams are hadrons
  if ((abs (particle_get_pdg(particle_set_get_particle (particle_set, 1)))<18) .and. &
      (abs (particle_get_pdg(particle_set_get_particle (particle_set, 2)))<18)) then
    mlm_matching_data%is_hadron_collision = .false.
  else if ((abs(particle_get_pdg (particle_set_get_particle (particle_set, 1)))>1000) .and.
      (abs(particle_get_pdg (particle_set_get_particle (particle_set, 2)))>1000)) then
    mlm_matching_data%is_hadron_collision = .true.
  else
    call msg_error (" Matching didn't recognize beams setup," // &
        char(10) // "      disabling matching")
    matching_disabled = .true.
    return
  end if
end if

!!! SHOWER
if (shower_settings%ps_use_PYTHIA_shower .or. &
    ((.not.shower_settings%ps_fsr_active) .and. (.not.shower_settings%ps_isr_active) &
    .and.(shower_settings%hadronization_active))) then
  call apply_PYTHIAshower_particle_set (particle_set, shower_settings, mlm_matching_data%P_ME
  !   call pyplot(2)
else
  call apply_WHIZARDshower_particle_set (particle_set, shower_settings, mlm_matching_data%P_ME
  os_data, pdf_func, pdf_set, valid, vetoed)
  if(vetoed) return
end if
!call particle_set_write(particle_set)
!print *, " after SHOWER"
!pause

if(shower_settings%mlm_matching.and.(matching_disabled.eqv..false.)) then
!!! MLM stage 2 -> PS jets and momenta
  call matching_transfer_PS (mlm_matching_data, particle_set, shower_settings)
!!! MLM stage 3 -> reconstruct and possible reject
  call mlm_matching (mlm_matching_data, shower_settings%ms, vetoed)
  if (vetoed) then
    call mlm_matching_data_final (mlm_matching_data)
    return
  end if
endif

!!! HADRONIZATION
if (shower_settings%hadronization_active) then
  !! Assume that the event record is still in the PYTHIA COMMON BLOCKS
  !! transferred there by one of the shower routines
  if (valid) then
    call apply_PYTHIAhadronization (particle_set, shower_settings, model, valid)
  end if
end if

!!! FINAL

```

```

    call mlm_matching_data_final (mlm_matching_data)
!   print *, "SHOWER+HAD+MATCHING finished"
contains
    function shower_get_PYTHIA_error (mstu23in) result (mstu23)
        ! PYTHIA common blocks
        IMPLICIT DOUBLE PRECISION(A-H, O-Z)
        IMPLICIT INTEGER(I-N)
        COMMON/PYDAT1/MSTU(200),PARU(200),MSTJ(200),PARJ(200)
        SAVE/PYDAT1/

        integer, intent(in), optional :: mstu23in
        integer :: mstu23

        if (present (mstu23in)) then
            MSTU(23) = mstu23in
        end if
        mstu23 = MSTU(23)
    end function shower_get_PYTHIA_error

    subroutine apply_PYTHIAshower_particle_set (particle_set, shower_settings, JETS_ME, model, val
    <Event formats: parameters>
    <Event formats: variables>
    <Event formats: common blocks>

    type(particle_set_t), intent(inout) :: particle_set
    type(particle_set_t) :: pset_reduced
    type(shower_settings_t), intent(in) :: shower_settings
    type(vector4_t), dimension(:), allocatable, intent(inout) :: JETS_ME
    type(model_t), pointer, intent(in) :: model
    logical, intent(inout) :: valid
    real(kind=default) :: rand

    ! units for transfer from WHIZARD to PYTHIA and back
    integer :: u_W2P, u_P2W
    integer, save :: pythia_initialized_for_NPRUP = 0
    logical, save :: pythia_warning_given = .false.
    logical, save :: msg_written = .false.
    type(string_t) :: remaining_PYGIVE, partial_PYGIVE
    character*10 buffer

    ! check if the beam particles are quarks
    if ((abs(IDBMUP(1)).le.8).or.(abs(IDBMUP(2)).le.8)) then
        ! PYTHIA doesn't support these settings
        if (pythia_warning_given.eqv..false.) then
            call msg_error ("PYTHIA doesn't support quarks as beam particles," // &
                char(10) // "      negelecting ISR, FSR and hadronization")
            pythia_warning_given = .true.
        end if
        return
    end if

    call particle_set_reduce (particle_set, pset_reduced)
    call particle_set_fill_hepeup (pset_reduced)

```



```

call hepeup_set_event_parameters (proc_id=1)

u_W2P = free_unit()
! only for debugging purposes
! open (unit=u_W2P, status="replace", file="whizardout1.lhe", action="readwrite")
open (unit=u_W2P, status="scratch", action="readwrite")
call les_houches_events_write_header (u_W2P)
call heprup_write_lhef (u_W2P)
call hepeup_write_lhef (u_W2P)
call les_houches_events_write_footer (u_W2P)
rewind (u_W2P)
write (buffer, "(I10)") u_W2P
call pygive ("MSTP(161)="//buffer)
call pygive ("MSTP(162)="//buffer)
if (shower_settings%ps_isr_active.eqv..false.) then
  call pygive ("MSTP(61)=0") ! switch off ISR
else
  call pygive ("MSTP(61)=1")
end if
if (shower_settings%ps_fsr_active.eqv..false.) then
  call pygive ("MSTP(71)=0") ! switch off FSR
else
  call pygive ("MSTP(71)=1")
end if
call pygive ("MSTP(111)=0") ! switch off hadronization

if (pythia_initialized_for_NPRUP .ge. NPRUP) then
  call upinit
else
  write (buffer, "(F10.5)") shower_settings%ps_mass_cutoff
  call pygive ("PARJ(82)="//buffer)
  write (buffer, "(F10.5)") shower_settings%ps_isr_tscalefactor
  call pygive ("PARP(71)="//buffer)

  write (buffer, "(F10.5)") shower_settings%ps_fsr_lambda
  call pygive ("PARP(72)="//buffer)
  write(buffer, "(F10.5)") shower_settings%ps_isr_lambda
  call pygive ("PARP(61)="//buffer)
  write (buffer, "(I10)") shower_settings%ps_max_n_flavors
  call pygive ("MSTJ(45)="//buffer)
  if (shower_settings%ps_isr_alpha_s_running) then
    call pygive ("MSTP(64)=2")
  else
    call pygive ("MSTP(64)=0")
  end if
  if (shower_settings%ps_fsr_alpha_s_running) then
    call pygive ("MSTJ(44)=2")
  else
    call pygive ("MSTJ(44)=0")
  end if
  write (buffer, "(F10.5)") shower_settings%ps_fixed_alpha_s
  call pygive ("PARU(111)="//buffer)
  write (buffer, "(F10.5)") shower_settings%ps_isr_primordial_kt_width
  call pygive ("PARP(91)="//buffer)

```

```

write (buffer, "(F10.5)") shower_settings%ps_isr_primordial_kt_cutoff
call pygive ("PARP(93)="//buffer)
write (buffer, "(F10.5)") 1._double - shower_settings%ps_isr_z_cutoff
call pygive ("PARP(66)="//buffer)
write (buffer, "(F10.5)") shower_settings%ps_isr_minenergy
call pygive ("PARP(65)="//buffer)
if (shower_settings%ps_isr_only_onshell_emitted_partons) then
  call pygive ("MSTP(63)=0")
else
  call pygive ("MSTP(63)=2")
end if
if (shower_settings%mlm_matching) then
  CALL PYGIVE('MSTP(62)=2')
  CALL PYGIVE('MSTP(67)=0')
end if
call pyinit ("USER", "", "", 0D0)

call tao_random_number (rand)
write (buffer, "(I10)") floor (rand*900000000)
call pygive ("MRPY(1)="//buffer)
call pygive ("MRPY(2)=0")

if (len(shower_settings%ps_PYTHIA_PYGIVE)>0) then
  remaining_PYGIVE = shower_settings%ps_PYTHIA_PYGIVE
  do while (len (remaining_PYGIVE)>0)
    call split (remaining_PYGIVE, partial_PYGIVE, ";")
    call PYGIVE (char (partial_PYGIVE))
  end do
  if (shower_get_PYTHIA_error().ne.0) then
    call msg_fatal (" PYTHIA didn't recognize ps_PYTHIA_PYGIVE setting")
  end if
end if

pythia_initialized_for_NPRUP = NPRUP
end if

if (.not.msg_written) then
  call msg_message ("Using PYTHIA interface for parton showers")
  msg_written = .true.
end if
call pyevnt ()

u_P2W = free_unit ()
write (buffer, "(I10)") u_P2W
call pygive ("MSTP(163)="//buffer)
!open(unit=u_P2W, file="pythiaout.lhe", status="replace", action="readwrite") ! only for de
open(unit=u_P2W, status="scratch", action="readwrite")
! convert pythia /PYJETS/ to lhef given in MSTU(163)=u_P2W
call pylheo
! read and add lhef from u_P2W
call shower_add_lhef_to_particle_set(particle_set, u_P2W, model, os_data)
close(unit=u_P2W)

if(shower_settings%mlm_matching) then

```

```

        ! transfer momenta of the partons in the final state of the hard ininteraction
        call get_ME_momenta_from_PYTHIA(JETS_ME)
    end if
    close(unit=u_W2P)
    valid = (shower_get_PYTHIA_error().eq.0)
end subroutine apply_PYTHIAshower_particle_set
subroutine apply_WHIZARDshower_particle_set(particle_set, shower_settings, JETS_ME, model_in,
    os_data, pdf_func, pdf_set, valid, vetoed)
    type(particle_set_t), intent(inout) :: particle_set
    type(shower_settings_t), intent(in) :: shower_settings
    type(vector4_t), dimension(:), allocatable, intent(inout) :: JETS_ME
    type(model_t), pointer, intent(in) :: model_in
    type(os_data_t), intent(in) :: os_data
    procedure(shower_pdf), pointer, intent(in) :: pdf_func
    integer, intent(in) :: pdf_set
    logical, intent(inout) :: valid
    logical, intent(out) :: vetoed

    type(multi_type), save :: mi
    type(shower_t) :: shower
    type(parton_t), dimension(:), allocatable, target :: partons, hadrons
    type(parton_pointer_t), dimension(:), allocatable :: parton_pointers, final_ME_partons
    real(kind=default) :: mi_scale, ps_scale, shat, phi
    type(parton_pointer_t) :: temppp
    integer, dimension(:), allocatable :: connections
    integer :: n_loop, i, j, k
    integer :: n_hadrons, n_in, n_out
    integer :: n_interactions
    integer :: max_color_nr
    integer, dimension(2) :: col_array
    integer, dimension(1) :: parent
    type(flavor_t) :: flv
    type(color_t) :: col
    type(model_t), pointer :: model
    type(model_t), target, save :: model_SM_hadrons
    logical, save :: model_SM_hadrons_associated = .false.
    logical, save :: msg_written = .false.
    logical :: exist_SM_hadrons
    type(string_t) :: filename
    integer, dimension(2,4) :: color_corr
    integer :: color_i, color_j
    character*5 buffer
    integer :: u_S2W

    vetoed = .false.

    ! transfer settings from shower_settings to shower
    call shower_set_D_Min_t (shower_settings%ps_mass_cutoff**2)
    call shower_set_D_Lambda_fsr (shower_settings%ps_fsr_lambda)
    call shower_set_D_Lambda_isr (shower_settings%ps_isr_lambda)
    call shower_set_D_Nf (shower_settings%ps_max_n_flavors)
    call shower_set_D_running_alpha_s_fsr (shower_settings%ps_fsr_alpha_s_running)
    call shower_set_D_running_alpha_s_isr (shower_settings%ps_isr_alpha_s_running)
    call shower_set_D_constantalpha_s (shower_settings%ps_fixed_alpha_s)

```

```

call shower_set_isr_pt_ordered (shower_settings%ps_isr_pt_ordered)
call shower_set_isr_angular_ordered (shower_settings%ps_isr_angular_ordered)
Call shower_set_primordial_kt_width (shower_settings%ps_isr_primordial_kt_width)
call shower_set_primordial_kt_cutoff (shower_settings%ps_isr_primordial_kt_cutoff)
call shower_set_maxz_isr (shower_settings%ps_isr_z_cutoff)
call shower_set_minenergy_timelike (shower_settings%ps_isr_minenergy)
call shower_set_tscalefactor_isr (shower_settings%ps_isr_tscalefactor)
call shower_set_isr_only_onshell_emitted_partons &
    (shower_settings%ps_isr_only_onshell_emitted_partons)
call shower_set_pdf_set (pdf_set)
call shower_set_pdf_func (pdf_func)

if (.not.msg_written) then
    call msg_message ("Using WHIZARD's internal showering")
    msg_written = .true.
end if

n_loop = 0
try_shower: do ! just a loop to be able to discard events
    n_loop = n_loop + 1
    if (n_loop .gt. 1000) STOP "BUG: too many loops (try_shower)"
    call shower_create (shower)
    max_color_nr = 0

    n_hadrons = 0
    n_in = 0
    n_out = 0
    do i = 1, particle_set_get_n_tot (particle_set)
        if (particle_get_status (particle_set_get_particle (particle_set, i)) == PRT_BEAM) &
            n_hadrons = n_hadrons+1
        if (particle_get_status (particle_set_get_particle (particle_set, i)) == PRT_INCOMING)
            n_in = n_in+1
        if (particle_get_status (particle_set_get_particle (particle_set, i)) == PRT_OUTGOING)
            n_out = n_out+1
    end do

    allocate (connections (1:particle_set_get_n_tot (particle_set)))
    connections = 0

    allocate (hadrons (1:2))
    allocate (partons (1:n_in+n_out))
    allocate (parton_pointers (1:n_in+n_out))

    j=0
    if (n_hadrons > 0) then
        ! Transfer hadrons
        do i = 1, particle_set_get_n_tot (particle_set)
            if (particle_get_status (particle_set_get_particle (particle_set, i)) == PRT_BEAM)
                j = j+1
                hadrons(j)%nr = shower_get_next_free_nr (shower)
                hadrons(j)%momentum = particle_get_momentum (particle_set_get_particle (particle_set, i))
                hadrons(j)%t = hadrons(j)%momentum**2
                hadrons(j)%typ = particle_get_pdg (particle_set_get_particle (particle_set, i))
                col_array=particle_get_color (particle_set_get_particle (particle_set, i))
            end if
        end do
    end if

```

```

        hadrons(j)%c1 = col_array(1)
        hadrons(j)%c2 = col_array(2)
        max_color_nr = max (max_color_nr, abs(hadrons(j)%c1), abs(hadrons(j)%c2))
        hadrons(j)%interactionnr = 1
        connections(i)=j
    end if
end do
end if

! transfer incoming partons
j = 0
do i = 1, particle_set_get_n_tot (particle_set)
    if (particle_get_status (particle_set_get_particle (particle_set, i)) == PRT_INCOMING)
        j = j+1
        partons(j)%nr = shower_get_next_free_nr (shower)
        partons(j)%momentum = particle_get_momentum (particle_set_get_particle (particle_set, i))
        partons(j)%t = partons(j)%momentum**2
        partons(j)%typ = particle_get_pdg (particle_set_get_particle (particle_set, i))
        col_array=particle_get_color (particle_set_get_particle (particle_set, i))
        partons(j)%c1 = col_array (1)
        partons(j)%c2 = col_array (2)
        parton_pointers(j)%p => partons(j)
        max_color_nr = max (max_color_nr, abs (partons(j)%c1), abs (partons(j)%c2))
        connections(i)=j
        ! insert dependences on hadrons
        if (particle_get_n_parents (particle_set_get_particle (particle_set, i))==1) then
            parent = particle_get_parents (particle_set_get_particle (particle_set, i))
            partons(j)%initial => hadrons (connections (parent(1)))
            partons(j)%x = space_part_norm (partons(j)%momentum) / &
                space_part_norm (partons(j)%initial%momentum)
        end if
    end if
end do

! transfer outgoing partons
do i = 1, particle_set_get_n_tot (particle_set)
    if (particle_get_status (particle_set_get_particle (particle_set, i)) == PRT_OUTGOING)
        j = j+1
        partons(j)%nr = shower_get_next_free_nr (shower)
        partons(j)%momentum = particle_get_momentum (particle_set_get_particle (particle_set, i))
        partons(j)%t = partons(j)%momentum**2
        partons(j)%typ = particle_get_pdg (particle_set_get_particle (particle_set, i))
        col_array=particle_get_color (particle_set_get_particle (particle_set, i))
        partons(j)%c1 = col_array(1)
        partons(j)%c2 = col_array(2)
        parton_pointers(j)%p => partons(j)
        max_color_nr = max (max_color_nr, abs (partons(j)%c1), abs (partons(j)%c2))
        connections(i)=j
    end if
end do

deallocate(connections)

! insert these partons in shower
call shower_set_next_color_nr (shower, 1+max_color_nr)

```

```

call shower_add_interaction2tonCKKW (shower, parton_pointers, shower_settings%ckkw_weight

if (shower_settings%multi_active) then
  ! Initialize multi pdf sets, unless initialized
  if (mi%is_initialized ()) then
    call mi%restart ()
  else
!!$      call shower_print(shower)
!!$      print *, "-----"
!!$      call interaction_print(shower%interactions(i)%i)
!!$      print *, "-----"
!!$      call vector4_write(shower%interactions(1)%i%partons(1)%p%momentum)
!!$      call vector4_write(shower%interactions(1)%i%partons(2)%p%momentum)
!!$      print *, "-----"
    call mi%initialize (&
      GeV2_scale_cutoff=D_Min_t, &
      GeV2_s=shower_interaction_get_s (shower%interactions(1)%i), &
      multi_dir=char(os_data%whizard_mulipath))
  end if

  ! initial interaction
  call mi%apply_initial_interaction(&
    GeV2_s=shower_interaction_get_s(shower%interactions(1)%i), &
    x1=shower%interactions(1)%i%partons(1)%p%parent%x, &
    x2=shower%interactions(1)%i%partons(2)%p%parent%x, &
    pdg_f1=shower%interactions(1)%i%partons(1)%p%parent%typ, &
    pdg_f2=shower%interactions(1)%i%partons(2)%p%parent%typ, &
    n1=shower%interactions(1)%i%partons(1)%p%parent%nr, &
    n2=shower%interactions(1)%i%partons(2)%p%parent%nr)
  end if

if (shower_settings%ckkw_matching) then
  ! CKKW Matching
  call ckkw_matching (shower, shower_settings%ckkw_settings, shower_settings%ckkw_weight
  if (vetoed) then
    return
  end if
end if

if (shower_settings%ps_isr_active) then
  i = 0
  branchings: do
    i = i+1
    if (shower_settings%multi_active) then
      call mi%generate_gev2_pt2 (shower_get_ISR_scale(shower), mi_scale)
    else
      mi_scale = 0.0
    end if

    ! shower_generate_next_isr_branching returns a pointer to the parton with the next
    ! temp=shower_generate_next_isr_branching_veto(shower)
    temp=shower_generate_next_isr_branching(shower)

```

```

if((.not. associated(tempvp%p)).and.(mi_scale.lt.D_Min_t)) then
  exit branchings
end if
! check if branching or interaction occurs next
if(associated(tempvp%p)) then
  ps_scale = abs(tempvp%p/t)
else
  ps_scale = 0._default
end if
if(mi_scale .gt. ps_scale) then
  ! discard branching evolution lower than mi_scale
  call shower_set_max_ISR_scale(shower, mi_scale)
  if(associated(tempvp%p)) call parton_set_simulated(tempvp%p, .false.)

  ! execute new interaction
  deallocate(partons)
  deallocate(parton_pointers)
  allocate(partons(1:4))
  allocate(parton_pointers(1:4))
  do j=1,4
    partons(j)%nr = shower_get_next_free_nr(shower)
    partons(j)%belongstointeraction = .true.
    parton_pointers(j)%p => partons(j)
  end do
  call mi%generate_partons(partons(1)%nr, partons(2)%nr, &
    partons(1)%x, partons(2)%x, &
    partons(1)%typ, partons(2)%typ, &
    partons(3)%typ, partons(4)%typ)
  ! calculate momenta
  shat = partons(1)%x*partons(2)%x*shower_interaction_get_s(shower%interactions(1))
  call parton_set_momentum(partons(1), 0.5_default*sqrt(shat), 0._default, 0._default)
  call parton_set_momentum(partons(2), 0.5_default*sqrt(shat), 0._default, 0._default)
  call parton_set_initial(partons(1), shower%interactions(1)%i%partons(1)%p%initial)
  call parton_set_initial(partons(2), shower%interactions(1)%i%partons(2)%p%initial)
  partons(1)%belongstoFSR=.false.
  partons(2)%belongstoFSR=.false.
  ! calculate color connections
  call mi%get_color_correlations(shower_get_next_color_nr(shower),max_color_nr,color_corr)
  call shower_set_next_color_nr(shower, max_color_nr)

  partons(1)%c1 = color_corr(1,1)
  partons(1)%c2 = color_corr(2,1)
  partons(2)%c1 = color_corr(1,2)
  partons(2)%c2 = color_corr(2,2)
  partons(3)%c1 = color_corr(1,3)
  partons(3)%c2 = color_corr(2,3)
  partons(4)%c1 = color_corr(1,4)
  partons(4)%c2 = color_corr(2,4)

  call tao_random_number(phi)
  phi = 2*pi*phi
  call parton_set_momentum(partons(3), 0.5_default*sqrt(shat), sqrt(mi_scale)*cos(phi),
    sqrt(mi_scale)*sin(phi), sqrt(0.25_default*shat - mi_scale))
  call parton_set_momentum(partons(4), 0.5_default*sqrt(shat), -sqrt(mi_scale)*cos(phi),
    sqrt(mi_scale)*sin(phi), sqrt(0.25_default*shat - mi_scale))

```

```

        -sqrt(mi_scale)*sin(phi), -sqrt(0.25_default*shat - mi_scale))
partons(3)%belongstoFSR=.true.
partons(4)%belongstoFSR=.true.

call shower_add_interaction2ton(shower, parton_pointers)
n_interactions = size(shower%interactions)
do k=1,2
    call mi%replace_parton(shower%interactions(n_interactions)%i%partons(k)%p%ini
        shower%interactions(n_interactions)%i%partons(k)%p%nr, &
        shower%interactions(n_interactions)%i%partons(k)%p%parent%nr, &
        shower%interactions(n_interactions)%i%partons(k)%p%typ, &
        shower%interactions(n_interactions)%i%partons(k)%p%x, &
        mi_scale)
end do
call shower_print(shower)
!
    pause
else
    ! execute the next branching 'found' in the previous step
    call shower_execute_next_isr_branching(shower, temppp)
    if(shower_settings%multi_active) then
        call mi%replace_parton(temppp%p%initial%nr, temppp%p%child1%nr, temppp%p%nr,
            temppp%p%typ, temppp%p%x, ps_scale)
    end if
    !
    ! call shower_print(shower)
    !
    ! pause
end if
end do branchings

call shower_generate_fsr_for_partons_emitted_in_ISR(shower)
! call shower_print(shower)
else
    call shower_simulate_no_isr_shower(shower)
end if

! some bookkeeping, needed after the shower is done
call shower_boost_to_labframe(shower)
call shower_generate_primordial_kt(shower)
call shower_update_beamremnants(shower)
! clean-up multi: we should finalize the multi pdf sets when all runs are done.
! call mi%finalize()

if(shower_settings%ps_fsr_active) then
    ! FSR
    do i=1, size(shower%interactions)
        call shower_interaction_generate_fsr2ton(shower, shower%interactions(i)%i)
    end do
else
    call shower_simulate_no_fsr_shower(shower)
end if
end if
!
! call shower_print(shower)
!
! print *, "SHOWER_FINISHED"

if(shower_settings%mlm_matching) then
    ! transfer momenta of the partons in the final state of the hard interaction

```



```

        if(allocated(JETS_ME)) deallocate(JETS_ME)
        call shower_get_final_colored_ME_partons(shower, final_ME_partons)
        if(allocated(final_ME_partons)) then
            allocate(JETS_ME(1:size(final_ME_partons)))
            do i=1, size(final_ME_partons)
                ! transfer
                JETS_ME(i) = final_ME_partons(i)%p%momentum
            end do
            deallocate(final_ME_partons)
        end if
    end if
end if

u_S2W = free_unit()
!!! only for debugging purposes
! open(unit=u_S2W, file="showerout.lhe", status="replace", action="readwrite")
open(unit=u_S2W, status="scratch", action="readwrite")
call shower_write_lhef(shower, u_S2W)
call shower_add_lhef_to_particle_set(particle_set, u_S2W, model_in, os_data)
close(u_S2W)

! move the particle data to the PYTHIA COMMON BLOCKS in case
! hadronization is active
if(shower_settings%hadronization_active) then
    call shower_converttopythia(shower)
end if
!
! deallocate(hadrons) ! hadrons are deallocated by shower_final
deallocate(partons)
deallocate(parton_pointers)
exit try_shower
end do try_shower
! call particle_set_write(particle_set)
! print *, "-----apply_shower_particle_set-----"
! print *, "-----"

! if(size(shower%interactions).ge.2) then
!     call shower_print(shower)
!     pause
! end if

call shower_final(shower)
! clean-up muli: we should finalize the muli pdf sets when all runs are done.
! call mi%finalize()
return
end subroutine apply_WHIZARDshower_particle_set

subroutine get_ME_momenta_from_PYTHIA(JETS_ME)
    IMPLICIT DOUBLE PRECISION(A-H, O-Z)
    IMPLICIT INTEGER(I-N)
    COMMON/PYJETS/N,NPAD,K(4000,5),P(4000,5),V(4000,5)
    SAVE /PYJETS/

    type(vector4_t), dimension(:), allocatable :: JETS_ME
    real(kind=default), dimension(:,:), allocatable :: pdum

```

```

integer :: i, j, n_jets

if (allocated(JETS_ME)) deallocate(JETS_ME)
if (allocated(pdum)) deallocate (pdum)

! final ME partons start in 7th row of event record
i=7
! find number of jets
n_jets=0
do
  if(K(I,1).ne.21) exit
  if((K(I,2).eq.21).or.(ABS(K(I,2)).le.6)) then
    n_jets = n_jets +1
  end if
  i=i+1
end do

if(n_jets.eq.0) return
allocate (JETS_ME(1:n_jets))
allocate (pdum(1:n_jets,4))

! transfer jets
i=7
j=1
pdum = p
do
  if(K(I,1).ne.21) exit
  if((K(I,2).eq.21).or.(ABS(K(I,2)).le.6)) then
    JETS_ME(j)= vector4_moving(pdum(I,4), &
      vector3_moving( (/pdum(I,1),pdum(I,2),pdum(I,3) /) ) )
    j=j+1
  end if
  i=i+1
end do
end subroutine get_ME_momenta_from_PYTHIA

subroutine matching_transfer_PS(mlm_matching_data, particle_set, shower_settings)
! transfer partons after parton shower to mlm_matching_data%P_PS
type(mlm_matching_data_t), intent(inout) :: mlm_matching_data
type(particle_set_t), intent(in) :: particle_set
type(shower_settings_t), intent(in) :: shower_settings

integer :: i, j, n_jets_PS
integer, dimension(2) :: col
type(particle_t) :: tempprt
real(kind=double) :: eta, E, pl

! loop over particles and extract final colored ones with eta<etamax
n_jets_PS=0
do i=1, particle_set_get_n_tot(particle_set)
  tempprt = particle_set_get_particle(particle_set, i)
  if(particle_get_status(tempprt)/=PRT_OUTGOING) cycle
  col = particle_get_color(tempprt)
  if(all(col == 0)) cycle
  if(mlm_matching_data%is_hadron_collision) then

```

```

        E = vector4_get_component(particle_get_momentum(tempprt),0)
        pl = vector4_get_component(particle_get_momentum(tempprt),3)
        eta = 0.5*abs(log( min((E+pl)/(E-pl), 1D10)))
        if (eta> shower_settings%ms%mlm_etaClusfactor*shower_settings%ms%mlm_etamax) then
!           print *, "REJECTING"
!           call particle_write(tempprt)
            cycle
        end if
    end if
    n_jets_PS=n_jets_PS + 1
end do

allocate(mlm_matching_data%P_PS(1:n_jets_PS))
!   print *, "n_jets_ps=", n_jets_ps

j=1
do i=1, particle_set_get_n_tot(particle_set)
    tempprt = particle_set_get_particle(particle_set, i)
    if(particle_get_status(tempprt)/=PRT_OUTGOING) cycle
    col = particle_get_color(tempprt)
    if(all(col == 0)) cycle
    if(mlm_matching_data%is_hadron_collision) then
        E = vector4_get_component(particle_get_momentum(tempprt),0)
        pl = vector4_get_component(particle_get_momentum(tempprt),3)
        eta = 0.5*abs(log( min((E+pl)/(E-pl), 1D10)))
        if (eta> shower_settings%ms%mlm_etaClusfactor*shower_settings%ms%mlm_etamax) cycle
    end if
    mlm_matching_data%P_PS(j) = particle_get_momentum(tempprt)
    j=j + 1
end do
end subroutine matching_transfer_PS

subroutine apply_PYTHIAhadronization(particle_set, shower_settings, model, valid)
    type(particle_set_t), intent(inout) :: particle_set
    type(shower_settings_t), intent(in) :: shower_settings
    type(model_t), pointer, intent(in) :: model
    logical, intent(inout) :: valid
    integer :: u_W2P, u_P2W
    type(string_t) :: remaining_PYGIVE, partial_PYGIVE
    logical, save :: msg_written = .false.
    character*10 buffer

    if(shower_settings%hadronization_active.eqv..false.) then
        return
    end if
    if(.not.valid) return

    u_W2P = free_unit()
    !open(unit=u_W2P, status="replace", file="whizardout.lhe", action="readwrite") ! only for d
    open(unit=u_W2P, status="scratch", action="readwrite")
    call les_houches_events_write_header (u_W2P)
    call heprup_write_lhef(u_W2P)
    call hepeup_write_lhef(u_W2P)
    call les_houches_events_write_footer (u_W2P)
    rewind(u_W2P)

```

```

write (buffer, "(I10)") u_W2P
call pygive ("MSTP(161)="//buffer)
call pygive ("MSTP(162)="//buffer)

! Assume that the event is still present in the PYTHIA common blocks
! call pygive ("MSTP(61)=0") ! switch off ISR
! call pygive ("MSTP(71)=0") ! switch off FSR

if((shower_settings%ps_use_PYTHIA_shower.eqv..false.) .and. len(shower_settings%ps_PYTHIA_PYGIVE
remaining_PYGIVE = shower_settings%ps_PYTHIA_PYGIVE
do while(len(remaining_PYGIVE)>0)
    call split(remaining_PYGIVE, partial_PYGIVE, ";")
    call PYGIVE(char(partial_PYGIVE))
end do
if(shower_get_PYTHIA_error().ne.0) then
    call msg_fatal(" PYTHIA didn't recognize ps_PYTHIA_PYGIVE setting")
end if
end if

if(.not.(shower_settings%ps_use_PYTHIA_shower.and.(shower_settings%ps_isr_active.or. &
shower_settings%ps_fsr_active))) then
if(len(shower_settings%ps_PYTHIA_PYGIVE)>0) then
    remaining_PYGIVE = shower_settings%ps_PYTHIA_PYGIVE
    do while(len(remaining_PYGIVE)>0)
        call split(remaining_PYGIVE, partial_PYGIVE, ";")
        call PYGIVE(char(partial_PYGIVE))
    end do
    if(shower_get_PYTHIA_error().ne.0) then
        call msg_fatal(" PYTHIA didn't recognize ps_PYTHIA_PYGIVE setting")
    end if
end if
end if

if(.not.msg_written) then
    call msg_message("Using PYTHIA interface for hadronization and decays")
    msg_written = .true.
end if

call pygive ("MSTP(111)=1") ! switch on hadronization
call PYEXEC

if (shower_get_PYTHIA_error() .gt. 0) then
    ! clean up, discard shower and exit
    close(u_W2P)
    valid =(shower_get_PYTHIA_error(0).eq.0)
else
    ! convert back
    u_P2W = free_unit()
    write (buffer, "(I10)") u_P2W
    call pygive ("MSTP(163)="//buffer)
    !open(unit=u_P2W, file="pythiaout2.lhe", status="replace", action="readwrite") ! only for
    open(unit=u_P2W, status="scratch", action="readwrite")
    ! convert pythia /PYJETS/ to lhef given in MSTU(163)=u1
    call pylheo

```

```

        ! read and add lhef from u_P2W
        call shower_add_lhef_to_particle_set(particle_set, u_P2W, model, os_data)
        close(u_W2P)
        close(u_P2W)
        valid = .true.
    end if
    end subroutine apply_PYTHIAhadronization
end subroutine apply_shower_particle_set

```

read in the lhe file opened in unit u and add the final particles to the particle_set, the outgoing particles of the existing particle_set are set to be virtual before the outgoing particles from the lhef are added to the particle_set as outgoing particles. At the same time, it is searched for pairs of existing and new particles with equal momenta and PDG code, these pairs are marked as connected. All remaining existing former outgoing particles are set to be the mothers of all remaining new outgoing particles

(Shower: procedures)+≡

```

subroutine shower_add_lhef_to_particle_set (particle_set, u, model_in, os_data)
    type(particle_set_t), intent(inout) :: particle_set
    integer, intent(in) :: u
    type(model_t), intent(in), pointer :: model_in
    type(model_t), target, save :: model_SM_hadrons
    type(model_t), pointer :: model
    logical, save :: model_SM_hadrons_associated = .false.
    type(os_data_t), intent(in) :: os_data
    logical :: exist_SM_hadrons
    type(string_t) :: filename
    type(flavor_t) :: flv
    type(color_t) :: col

    integer :: newsize, oldsize
    type(particle_t), dimension(:), allocatable :: temp_prt
    integer :: i, j
    integer :: n_available_parents;
    integer, dimension(:), allocatable :: available_parents
    integer, dimension(:), allocatable :: available_children
    logical, dimension(:), allocatable :: direct_child
    type(vector4_t) :: diffmomentum
    integer, PARAMETER :: MAXLEN=200
    CHARACTER*(MAXLEN) STRING
    integer ibeg
    INTEGER :: NUP,IDPRUP,IDUP,ISTUP
    real(kind=double) :: XWGTUP,SCALUP,AQEDUP,AQCDUP,VTIMUP,SPINUP
    integer :: MOTHUP(1:2),ICOLUP(1:2)
    real(kind=double) :: PUP(1:5)
    real(kind=default) :: pup_dum(1:5)
    character*5 buffer

    CHARACTER*6 STRFMT
    STRFMT='(A000)'
    WRITE(STRFMT(3:5),'(I3)') MAXLEN

    rewind(u)

```

```

! get newsize of particle_set, newsize = old size of particle_set + #entries - 2 (incoming par
oldsize=particle_set_get_n_tot(particle_set)
! Loop until finds line beginning with "<event>" or "<event ".
do
  READ(u,*,END=501,ERR=502) STRING
  IBEG=0
  do
    IBEG=IBEG+1
    ! Allow indentation.
    IF(STRING(IBEG:IBEG).EQ.' '.AND.IBEG.LT.MAXLEN-6) cycle
    exit
  end do
  IF(STRING(IBEG:IBEG+6).NE.'<event>'.AND.STRING(IBEG:IBEG+6).NE.'<event ') cycle
  exit
end do
! Read first line of event info -> number of entries
read (u, *, END=503, ERR=504) NUP, IDPRUP, XWGTUP, SCALUP, AQEDUP, AQCDUP
newsize = oldsize + NUP - 2
allocate (temp_prt (1:newsize))

allocate (available_parents (1:oldsize))
available_parents = 0
do i=1, particle_set_get_n_tot (particle_set)
  temp_prt (i) = particle_set_get_particle (particle_set, i)
  if (particle_get_status (temp_prt (i)) == PRT_OUTGOING .or. &
      particle_get_status (temp_prt (i)) == PRT_BEAM_REMNANT) then
    call particle_reset_status (temp_prt (i), PRT_VIRTUAL)
    available_parents (i) = i
  end if
end do

allocate (available_children (1:newsize))
allocate (direct_child (1:newsize))
available_children = 0
direct_child = .false.

! transfer particles from lhcf to particle_set
!...Read NUP subsequent lines with information on each particle.
DO I = 1, NUP
  READ (u,*,END=200,ERR=505) IDUP, ISTUP, MOTHUP(1), MOTHUP(2), &
    ICOLUP(1), ICOLUP(2), (PUP (J),J=1,5), VTIMUP, SPINUP
  if ((I.eq.1).or.(I.eq.2)) cycle

  call particle_reset_status (temp_prt(oldsize+i-2), PRT_OUTGOING)
  ! particle_set%prt(oldsize+i-2)%polarization=0 ! =PRT_UNPOLARIZED !??
  if (model_test_particle (model_in, IDUP)) then
    model => model_in
  else
    ! prepare model_SM_hadrons for hadrons created in the hadronization
    ! and not present in the model file
    if (.not. model_SM_hadrons_associated) then
      call os_data_init(os_data)
      filename = "SM_hadrons.mdl"
      call model_read (model_SM_hadrons, filename, os_data, &

```

```

        exist_SM_hadrons)
        model_SM_hadrons_associated = .true.
    end if
    if (model_test_particle (model_SM_hadrons, IDUP)) then
        model => model_SM_hadrons
    else
        write (buffer, "(I5)" IDUP
        call msg_error ("Parton " // buffer // &
            " found neither in given model file nor in SM_hadrons")
        return
    end if
end if
call flavor_init (flv, IDUP, model)
call particle_set_flavor (temp_prt (oldsize+i-2), flv)

if(IABS(IDUP).eq.2212 .or. IABS(IDUP).eq.2112) then
    ! PYTHIA sometimes sets color indices for protons and neutrons (?)
    ICOLUP (1) = 0
    ICOLUP (2) = 0
end if
call color_init_col_acl (col, ICOLUP (1), ICOLUP (2))
call particle_set_color (temp_prt (oldsize+i-2), col)
!particle_set%prt(oldsize+i-2)%hel=?
!particle_set%prt(oldsize+i-2)%pol=?
pup_dum = PUP
call particle_set_momentum (temp_prt (oldsize+i-2), vector4_moving (pup_dum (4), &
    vector3_moving ((/ pup_dum (1), pup_dum (2), pup_dum (3)/))))

available_children (oldsize+i-2) = oldsize+i-2
!! search for an existing particle with the same momentum -> treat these as mother and daug
do j=1, size (available_parents)
    if (available_parents (j) .eq. 0) cycle
    diffmomentum = particle_get_momentum (temp_prt (available_parents (j))) - &
        particle_get_momentum (temp_prt (oldsize+i-2))
    if(abs(diffmomentum**2) < 1D-10 .and. &
        particle_get_pdg (temp_prt (available_parents (j))).eq. &
        particle_get_pdg (temp_prt (oldsize+i-2))) then
        direct_child (available_parents (j)) = .true.
        direct_child (oldsize+i-2) = .true.
        call particle_set_parents (temp_prt (oldsize+i-2), (/ available_parents(j) /) )
        call particle_set_children (temp_prt (available_parents(j)), (/ oldsize+i-2 /) )
        available_parents (j) = 0
        available_children (oldsize+i-2) = 0
    end if
end do
end do

! remove zeros in available parents and available children
available_parents = pack (available_parents , available_parents /= 0)
available_children = pack (available_children, available_children /= 0)

do i=1, size(available_parents)
    if (direct_child (available_parents (i))) cycle
    call particle_set_children (temp_prt (available_parents (i)), available_children)

```

```

end do
do i = oldsize+1, newsize
  if (direct_child(i)) cycle
  call particle_set_parents(temp_prt(i), available_parents)
end do

! transfer to particle_set
call particle_set_replace (particle_set, temp_prt)
if (allocated (available_children)) deallocate (available_children)
if (allocated (available_parents)) deallocate (available_parents)
deallocate (direct_child)
deallocate (temp_prt)
call model_final (model_SM_hadrons)

200 continue
return

501 write(*,*) "READING LHEF failed 501"
return
502 write(*,*) "READING LHEF failed 502"
return
503 write(*,*) "READING LHEF failed 503"
return
504 write(*,*) "READING LHEF failed 504"
return
505 write(*,*) "READING LHEF failed 504"
return
end subroutine shower_add_lhef_to_particle_set

(Shower: procedures)+≡
!!!!!!!!!!PYTHIA STYLE!!!!!!!!!!!!!!
!!! originally PYLHEF subroutine from PYTHIA 6.4.22

!C...Write out the showered event to a Les Houches Event File.
!C...Take MSTP(161) as the input for <init>...</init>

SUBROUTINE PYLHEO

!C...Double precision and integer declarations.
IMPLICIT DOUBLE PRECISION(A-H, O-Z)
IMPLICIT INTEGER(I-N)

!C...PYTHIA commonblock: only used to provide read/write units and version.
COMMON/PYPARS/MSTP(200),PARP(200),MSTI(200),PARI(200)
COMMON/PYJETS/N,NPAD,K(4000,5),P(4000,5),V(4000,5)
SAVE /PYPARS/
SAVE /PYJETS/

!C...User process initialization commonblock.
INTEGER MAXPUP
PARAMETER (MAXPUP=100)
INTEGER IDBMUP,PDFGUP,PDFSUP,IDWTUP,NPRUP,LPRUP
DOUBLE PRECISION EBMUP,XSECUP,XERRUP,XMAXUP
COMMON/HEPRUP/IDBMUP(2),EBMUP(2),PDFGUP(2),PDFSUP(2),IDWTUP,NPRUP,XSECUP(MAXPUP),XERRUP(MAXPUP)
SAVE /HEPRUP/

```



```

!C...User process event common block.
      INTEGER MAXNUP
      PARAMETER (MAXNUP=500)
      INTEGER NUP,IDPRUP,IDUP,ISTUP,MOTHUP,ICOLUP
      PARAMETER (KSUSY1=1000000,KSUSY2=2000000,KTECHN=3000000, &
        KEXCIT=4000000,KDIMEN=5000000)
      DOUBLE PRECISION XWGTUP,SCALUP,AQEDUP,AQCDUP,PUP,VTIMUP,SPINUP
      COMMON/HEPEUP/NUP,IDPRUP,XWGTUP,SCALUP,AQEDUP,AQCDUP,IDUP(MAXNUP),ISTUP(MAXNUP),MOTHUP(2,MAXNUP),
        PUP(5,MAXNUP),VTIMUP(MAXNUP),SPINUP(MAXNUP)
      SAVE /HEPEUP/

!C...Lines to read in assumed never longer than 200 characters.
      PARAMETER (MAXLEN=200)
      CHARACTER*(MAXLEN) STRING

      INTEGER LEN

!C...Format for reading lines.
      CHARACTER*6 STRFMT
      STRFMT='(A000)'
      WRITE(STRFMT(3:5),'(I3)') MAXLEN

!C...Rewind initialization and event files.
      REWIND MSTP(161)
      REWIND MSTP(162)

!C...Write header info.
      WRITE(MSTP(163),'(A)') '<LesHouchesEvents version="1.0">'
      WRITE(MSTP(163),'(A)') '<!--'
      WRITE(MSTP(163),'(A,I1,A1,I3)') 'File generated with PYTHIA ',MSTP(181),'.',MSTP(182)
      WRITE(MSTP(163),'(A)') ' and the WHIZARD2 interface'
      WRITE(MSTP(163),'(A)') '-->'

!C...Loop until finds line beginning with "<init>" or "<init ".
      100 READ(MSTP(161),STRFMT,END=400,ERR=400) STRING
      IBEG=0
      110 IBEG=IBEG+1

!C...Allow indentation.
      IF(STRING(IBEG:IBEG).EQ.' '.AND.IBEG.LT.MAXLEN-5) GOTO 110
      IF(STRING(IBEG:IBEG+5).NE.'<init>'.AND.STRING(IBEG:IBEG+5).NE.'<init ') GOTO 100

!C...Read first line of initialization info and get number of processes.
      READ(MSTP(161),'(A)',END=400,ERR=400) STRING
      READ(STRING,*,ERR=400) IDBMUP(1),IDBMUP(2),EBMUP(1),EBMUP(2),PDFGUP(1),PDFGUP(2),PDFSUP(1),P

!C...Copy initialization lines, omitting trailing blanks.
!C...Embed in <init> ... </init> block.
      WRITE(MSTP(163),'(A)') '<init>'
      DO IPR=0,NPRUP
        IF(IPR.GT.0) READ(MSTP(161),'(A)',END=400,ERR=400) STRING
        LEN=MAXLEN+1
      120  LEN=LEN-1
        IF(LEN.GT.1.AND.STRING(LEN:LEN).EQ.' ') GOTO 120

```

```

        WRITE(MSTP(163),'(A)',ERR=400) STRING(1:LEN)
    end DO
    WRITE(MSTP(163),'(A)') '</init>'

!!!! Find the numbers of entries of the <event block>
    NENTRIES = 2      ! incoming partons (nearest to the beam particles)
    DO I=1,N
        if((K(I,1).eq.1) .or. (K(I,1).eq.2)) then
            if(P(I,4) < 1D-10) cycle
            NENTRIES = NENTRIES + 1
        end if
    end DO

!C...Begin an <event> block. Copy event lines, omitting trailing blanks.
    WRITE(MSTP(163),'(A)') '<event>'
    WRITE(MSTP(163),*) NENTRIES,IDPRUP,XWGTUP,SCALUP,AQEDUP,AQCDUP

    DO I=3,4      ! the incoming partons nearest to the beam particles
        WRITE(MSTP(163),*) K(I,2),-1,0,0,0,0,(P(I,J),J=1,5),0, -9
    end DO
    NDANGLING_COLOR = 0
    NCOLOR = 0
    NDANGLING_ANTIC = 0
    NANTIC = 0
    NNEXTC = 1    ! TODO find next free color number ??
    DO I=1,N
        if((K(I,1).eq.1) .or. (K(I,1).eq.2)) then
            if(P(I,4) < 1D-10) cycle ! workaround for zero energy photon in electron ISR
            if((K(I,2).eq.21).or.(IABS(K(I,2)).le.8).or.(IABS(K(I,2)).GE.KSUSY1+1.AND.IABS(K(I,2))
                (IABS(K(I,2)).GE.KSUSY2+1.AND.IABS(K(I,2)).LE.KSUSY2+8).or. &
                (IABS(K(I,2)).GE.1000.AND.IABS(K(I,2)).le.9999) ) then
                if(NDANGLING_COLOR.eq.0 .and. NDANGLING_ANTIC.eq.0) then
                    ! new color string
                    if(K(I,2).eq.21 .or. K(I,2).eq.1000021) then ! Gluon and gluino only color octet
                        NCOLOR = NNEXTC
                        NDANGLING_COLOR = NCOLOR
                        NNEXTC = NNEXTC + 1
                        NANTIC = NNEXTC
                        NDANGLING_ANTIC = NANTIC
                        NNEXTC = NNEXTC + 1
                    elseif(K(I,2) .gt. 0) then ! particles to have color
                        NCOLOR = NNEXTC
                        NDANGLING_COLOR = NCOLOR
                        NANTIC = 0
                        NNEXTC = NNEXTC + 1
                    elseif(K(I,2) .lt. 0) then ! antiparticles to have anticolor
                        NANTIC = NNEXTC
                        NDANGLING_ANTIC = NANTIC
                        NCOLOR = 0
                        NNEXTC = NNEXTC + 1
                    end if
                else if(K(I,1).eq.1) then
                    ! end of string
                    NCOLOR = NDANGLING_ANTIC
                end if
            end if
        end if
    end DO

```

```

        NANTIC = NDANGLING_COLOR
        NDANGLING_COLOR = 0
        NDANGLING_ANTIC = 0
    else
        ! inside the string
        if(NDANGLING_COLOR .ne. 0) then
            NANTIC = NDANGLING_COLOR
            NCOLOR = NNEXTC
            NDANGLING_COLOR = NNEXTC
            NNEXTC = NNEXTC +1
        else if(NDANGLING_ANTIC .ne. 0) then
            NCOLOR = NDANGLING_ANTIC
            NANTIC = NNEXTC
            NDANGLING_ANTIC = NNEXTC
            NNEXTC = NNEXTC +1
        else
            print *, "ERROR IN PYLHEO"
        end if
    end if
end if
else
    NCOLOR = 0
    NANTIC = 0
end if

        !! As no intermediate are given out here, assume the incoming partons to be the mother
        WRITE(MSTP(163),*) K(I,2),1,1,2,NCOLOR,NANTIC,(P(I,J),J=1,5),0, -9
    end if
end DO

!C..End the <event> block. Loop back to look for next event.
WRITE(MSTP(163),'(A)') '</event>'

!C...Successfully reached end of event loop: write closing tag
!C...and remove temporary intermediate files (unless asked not to).
320 WRITE(MSTP(163),'(A)') '</LesHouchesEvents>'
RETURN

!!C...Error exit.
400 WRITE(*,*) ' PYLHEO file joining failed!'

RETURN
END SUBROUTINE PYLHEO

```

17.6 Whizard-C-Interface

```

<Commands: public>+≡
    public :: command_t
    public :: cmd_simulate_t
    public :: command_execute
    public :: command_final

<Simulations: public>+≡

```

```

    public :: checkpointing_msg_start
    public :: simulation_read_event_raw
    public :: simulation_read_event_hepmc
    public :: simulation_recover_process
    public :: simulation_recalculate
    public :: simulation_decay
    public :: simulation_select_process
    public :: simulation_handle_event
    public :: simulation_final_event

    <WHIZARD: public>+≡
        public :: global

    <whizard-c-interface.f90>≡
        <File header>

        <Whizard-C-Interface: Internals>
        <Whizard-C-Interface: Init and Finalize>
        <Whizard-C-Interface: Interfaced Commads>
        <Whizard-C-Interface: HepMC>

    <Whizard-C-Interface: Internals>≡
        subroutine c_whizard_convert_string(c_string, f_string)
            use, intrinsic :: iso_c_binding
            use iso_varying_string, string_t => varying_string !NODEP!

            implicit none

            character(kind=c_char), intent(in) :: c_string(*)
            type(string_t), intent(inout) :: f_string
            character(len=1) :: dummy_char
            integer :: dummy_i = 1

            f_string = ""
            do
                if(c_string(dummy_i) == c_null_char) then
                    exit
                else if(c_string(dummy_i) == c_new_line) then
                    dummy_char = CHAR(13)
                    f_string = f_string // dummy_char
                    dummy_char = CHAR(10)
                else
                    dummy_char = c_string(dummy_i)
                end if
                f_string = f_string // dummy_char
                dummy_i = dummy_i + 1
            end do
            dummy_i = 1
        end subroutine c_whizard_convert_string

        subroutine c_whizard_commands(cmds)
            use iso_varying_string, string_t => varying_string !NODEP!
            use commands
            use diagnostics !NODEP!

```

```

use lexers
use models
use parser
use whizard

type(string_t) :: cmds
type(parse_tree_t) :: parse_tree
type(parse_node_t), pointer :: pn_root
type(stream_t), target :: stream
type(lexer_t) :: lexer
type(command_list_t), pointer :: cmd_list

call lexer_init_cmd_list (lexer)

call stream_init (stream, cmds)
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_cmd_list, lexer)
pn_root => parse_tree_get_root_ptr (parse_tree)

allocate(cmd_list)
call command_list_compile(cmd_list, pn_root ,global)
call command_list_execute(cmd_list, global)
call command_list_final(cmd_list)

call parse_tree_final (parse_tree)
call stream_final (stream)
call lexer_final (lexer)
end subroutine c_whizard_commands

<Whizard-C-Interface: Init and Finalize>≡
subroutine c_whizard_init() bind(c)
  use, intrinsic :: iso_c_binding
  use diagnostics !NODEP!
  use ifiles
  use iso_varying_string, string_t => varying_string !NODEP!
  use limits, only: CMDLINE_ARG_LEN !NODEP!
  use os_interface
  use system_dependencies !NODEP!
  use whizard

  implicit none

  ! Main program variable declarations
  character(CMDLINE_ARG_LEN) :: arg
  character(2) :: option
  type(string_t) :: long_option, value
  integer :: i, j, arg_len, arg_status
  logical :: look_for_options
  logical :: interactive
  type(string_t) :: files, this, model, libname, library, libraries, logfile
  type(string_t) :: check, checks
  logical :: user_code_enable = .false.
  integer :: n_user_src = 0, n_user_lib = 0
  type(string_t) :: user_src, user_lib

```

```

type(paths_t) :: paths
logical :: rebuild_library, rebuild_user
logical :: rebuild_phs, rebuild_grids, rebuild_events
logical :: recompile_library
logical :: time_estimate
type(ifile_t) :: commands
type(string_t) :: command

! Exit status
logical :: quit = .false.
integer :: quit_code = 0

! Initial values
look_for_options = .true.
interactive = .false.
files = ""
model = "SM"
libname = "processes"
library = ""
logfile = "whizard.log"
libraries = ""
check = ""
checks = ""
user_src = ""
user_lib = ""
rebuild_library = .false.
rebuild_user = .false.
rebuild_phs = .false.
rebuild_grids = .false.
rebuild_events = .false.
recompile_library = .false.
time_estimate = .true.
call paths_init (paths)

! Overall initialization
if (logfile /= "") call logfile_init (logfile)
call mask_term_signals ()
call msg_banner ()
call whizard_init &
  (preload_model=model, preload_libs=libraries, default_lib=libname, &
   rebuild_library=rebuild_library, &
   rebuild_user=rebuild_user, &
   rebuild_phs=rebuild_phs, &
   rebuild_grids=rebuild_grids, &
   rebuild_events=rebuild_events, &
   recompile_library=recompile_library, &
   time_estimate=time_estimate, &
   paths=paths, &
   user_code_enable=user_code_enable, &
   n_user_src=n_user_src, user_src=user_src, &
   n_user_lib=n_user_lib, user_lib=user_lib)

! Run any self-checks (and no commands)
if (checks /= "") then

```

```

        checks = trim (adjustl (checks))
        RUN_CHECKS: do while (checks /= "")
            call split (checks, check, " ")
            call whizard_check (check, LHAPDF_AVAILABLE)
        end do RUN_CHECKS
        quit = .true.
    end if
end subroutine c_whizard_init

subroutine c_whizard_finalize() bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!
    use system_dependencies !NODEP!
    use limits, only: CMDLINE_ARG_LEN !NODEP!
    use diagnostics !NODEP!
    use ifiles
    use os_interface
    use whizard

    ! Exit status
    logical :: quit = .false.
    integer :: quit_code = 0

    ! Overall finalization
    ! call ifile_final (commands)
    call whizard_final ()
    call terminate_now_if_signal ()
    call release_term_signals ()
    call msg_terminate (quit_code = quit_code)
end subroutine c_whizard_finalize

subroutine c_whizard_process_string(c_cmds_in) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_cmds_in(*)
    type(string_t) :: f_cmds

    call c_whizard_convert_string(c_cmds_in, f_cmds)
    call c_whizard_commands(f_cmds)
end subroutine c_whizard_process_string

<Whizard-C-Interface: Interfaced Commads>≡
subroutine c_whizard_model(c_model) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_model(*)
    type(string_t) :: model, mdl_str

```

```

    call c_whizard_convert_string(c_model, model)
    mdl_str = "model = " // model
    call c_whizard_commands(mdl_str)
end subroutine c_whizard_model

subroutine c_whizard_library(c_library) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_library(*)
    type(string_t) :: library, lib_str

    call c_whizard_convert_string(c_library, library)
    lib_str = "library = " // library
    call c_whizard_commands(lib_str)
end subroutine c_whizard_library

subroutine c_whizard_process(c_id, c_in, c_out) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_id(*), c_in(*), c_out(*)
    type(string_t) :: proc_str, id, in, out

    call c_whizard_convert_string(c_id, id)
    call c_whizard_convert_string(c_in, in)
    call c_whizard_convert_string(c_out, out)
    proc_str = "process " // id // " = " // in // " => " // out
    call c_whizard_commands(proc_str)
end subroutine c_whizard_process

subroutine c_whizard_compile() bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    type(string_t) :: cmp_str
    cmp_str = "compile"
    call c_whizard_commands(cmp_str)
end subroutine c_whizard_compile

subroutine c_whizard_load(c_library) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_library(*)
    type(string_t) :: library, load_str

    call c_whizard_convert_string(c_library, library)

```



```

        load_str = "load = " // library
        call c_whizard_commands(load_str)
    end subroutine c_whizard_load

subroutine c_whizard_beams(c_specs) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_specs(*)
    type(string_t) :: specs, beam_str

    call c_whizard_convert_string(c_specs, specs)
    beam_str = "beams = " // specs
    call c_whizard_commands(beam_str)
end subroutine c_whizard_beams

subroutine c_whizard_integrate(c_process) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_process(*)
    type(string_t) :: process, int_str

    call c_whizard_convert_string(c_process, process)
    int_str = "integrate (" // process // ")"
    call c_whizard_commands(int_str)
end subroutine c_whizard_integrate

subroutine c_whizard_matrix_element_test(c_process) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_process(*)
    type(string_t) :: process, me_str

    call c_whizard_convert_string(c_process, process)
    me_str = "matrix_element_test (" // process // ")"
    call c_whizard_commands(me_str)
end subroutine c_whizard_matrix_element_test

subroutine c_whizard_simulate(c_id) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_id(*)
    type(string_t) :: sim_str, id

```

```

    call c_whizard_convert_string(c_id, id)
    sim_str = "simulate (" // id // ")"
    call c_whizard_commands(sim_str)
end subroutine c_whizard_simulate

subroutine c_whizard_sqrts(c_value, c_unit) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!

    implicit none

    character(kind=c_char) :: c_unit(*)
    integer(kind=c_int) :: c_value
    integer :: f_value
    character(len=8) :: f_val
    type(string_t) :: val, unit, sqrts_str

    f_value = c_value
    write(f_val,'(i8)') f_value
    val = f_val
    call c_whizard_convert_string(c_unit, unit)
    sqrts_str = "sqrts =" // val // unit
    call c_whizard_commands(sqrts_str)
end subroutine c_whizard_sqrts

<Whizard-C-Interface: HepMC>≡
type(c_ptr) function c_whizard_hepmc_test(c_id, c_proc_id, c_event_id) bind(c)
    use, intrinsic :: iso_c_binding
    use iso_varying_string, string_t => varying_string !NODEP!
    use commands
    use diagnostics !NODEP!
    use events
    use hepmc_interface
    use lexers
    use limits, only: MAX_TRIES_FOR_SINGLE_EVENT !NODEP!
    use models
    use parser
    use processes
    use rt_data
    use simulations
    use whizard
    use os_interface

    implicit none

    type(string_t) :: sim_str
    type(parse_tree_t) :: parse_tree
    type(parse_node_t), pointer :: pn_root
    type(stream_t), target :: stream
    type(lexer_t) :: lexer
    type(command_list_t), pointer :: cmd_list
    type(command_t), pointer :: command
    type(os_data_t) :: os_data

```

```

type(cmd_simulate_t), target :: simulate
logical :: ok !, mlm_matching
integer :: i_evt
type(simulation_t), target :: sim

character(kind=c_char), intent(in) :: c_id(*)
type(string_t) :: id
integer(kind=c_int), value :: c_proc_id, c_event_id
integer :: proc_id, event_id

type(hepmc_event_t), pointer :: hepmc_event

type(process_t), pointer :: process
integer :: proc

integer :: factorization_mode, try

call c_whizard_convert_string(c_id, id)
sim_str = "simulate (" // id // ")"

proc_id = c_proc_id
event_id = c_event_id

allocate(hepmc_event)
call hepmc_event_init (hepmc_event, c_proc_id, c_event_id)

call lexer_init_cmd_list (lexer)

call stream_init (stream, sim_str)
call lexer_assign_stream (lexer, stream)
call parse_tree_init (parse_tree, syntax_cmd_list, lexer)
pn_root => parse_tree_get_root_ptr (parse_tree)

allocate(cmd_list)
call command_list_compile(cmd_list, pn_root ,global)

command => cmd_list%first
simulate = command%simulate

call rt_data_link (simulate%local, global)

if (associated (simulate%options)) then
    call command_list_execute (simulate%options, simulate%local)
end if

call simulation_init (sim, simulate%process_id, simulate%local, global%var_list, ok, verbose=.fa

if (ok) then
    call simulation_setup_reweight &
        (sim, simulate%local%pn_reweight_expr, verbose=.false.)
    call simulation_select_process (sim, simulate%local%rng, process, proc)

    if (sim%allow_decays) then

```

```

        call event_init (sim%event, process, &
            sim%event_vars, sim%decay_tree(proc))
    else
        call event_init (sim%event, process, sim%event_vars)
    end if

    if (sim%use_num_id) then
        sim%event_vars%process_num_id = sim%num_id(proc)
    else
        sim%event_vars%process_num_id = proc
    end if

    if (sim%spar%polarized) then
        factorization_mode = FM_SELECT_HELICITY
    else
        factorization_mode = FM_IGNORE_HELICITY
    end if

    call os_data_init(os_data)
    GENERATE: do try = 1, MAX_TRIES_FOR_SINGLE_EVENT
        call event_generate &
            (sim%event, simulate%local%rng, sim%spar%unweighted, &
            factorization_mode, &
            keep_correlations=.false., &
            keep_virtual=.true., os_data=os_data, &
            shower_settings = sim%spar%shower_settings)
        if(event_is_vetoed(sim%event).and. &
            (.not.sim%n_events_set)) then
            sim%n_events = sim%n_events - 1
            if(sim%i_evt .ge. sim%n_events) then
                call event_final(sim%event)
                return
            end if
        end if
        if (event_is_valid (sim%event).and. &
            (.not.event_is_vetoed(sim%event))) exit GENERATE
    end do GENERATE
    if (.not. event_is_valid (sim%event)) then
        write (msg_buffer, "(A,I0,A)") "Failed to generate a valid event " &
            // "after ", MAX_TRIES_FOR_SINGLE_EVENT, " tries"
        call msg_fatal()
    end if

    call event_renormalize_weight (sim%event, sim%norm_weight)

    call event_write_to_hepmc(sim%event, hepmc_event)

    call simulation_handle_event (sim)
    call simulation_final_event (sim)
    call simulation_final (sim, verbose=.false.)
end if
call rt_data_restore (global, simulate%local)

call command_list_final(cmd_list)

```

```
call parse_tree_final (parse_tree)
call stream_final (stream)
call lexer_final (lexer)

c_whizard_hepmc_test = c_loc(hepmc_event)
return
end function c_whizard_hepmc_test
```

Chapter 18

Cross References

18.1 Identifiers

18.2 Chunks