

VAMP, Version 1.0: Vegas AMPlified: Anisotropy, Multi-channel sampling and Parallelization

Thorsten Ohl^{1,2}

Darmstadt University of Technology
Schloßgartenstr. 9
D-64289 Darmstadt
Germany

IKDA 98/??
hep-ph/yymmnnn
October 1999

DRAFT: September 17, 2012

¹e-mail: ohl@hep.tu-darmstadt.de

²Supported by Bundesministerium für Bildung, Wissenschaft, Forschung und Technologie, Germany.

Abstract

We present an new implementation of the classic Vegas algorithm for adaptive multi-dimensional Monte Carlo integration in Fortran95. This implementation improves the performance for a large class of integrands, supporting stratified sampling in higher dimensions through automatic identification of the directions of largest variation. This implementation also supports multi channel sampling with individual adaptive grids. Sampling can be performed in parallel on workstation clusters and other parallel hardware.

Revision Control

```
prelude.nw 314 2010-04-17 20:32:33Z ohl
divisions.nw 314 2010-04-17 20:32:33Z ohl
vamp.nw 317 2010-04-18 00:31:03Z ohl
vampi.nw 314 2010-04-17 20:32:33Z ohl
vamp_test.nw 314 2010-04-17 20:32:33Z ohl
vamp_test0.nw 314 2010-04-17 20:32:33Z ohl
application.nw 314 2010-04-17 20:32:33Z ohl
kinds.nw 314 2010-04-17 20:32:33Z ohl
constants.nw 314 2010-04-17 20:32:33Z ohl
exceptions.nw 314 2010-04-17 20:32:33Z ohl
specfun.nw 314 2010-04-17 20:32:33Z ohl
vamp_stat.nw 314 2010-04-17 20:32:33Z ohl
histograms.nw 314 2010-04-17 20:32:33Z ohl
utils.nw 314 2010-04-17 20:32:33Z ohl
linalg.nw 314 2010-04-17 20:32:33Z ohl
products.nw 314 2010-04-17 20:32:33Z ohl
kinematics.nw 314 2010-04-17 20:32:33Z ohl
coordinates.nw 314 2010-04-17 20:32:33Z ohl
mpi90.nw 314 2010-04-17 20:32:33Z ohl
pmep.nw 314 2010-04-17 20:32:33Z ohl
postlude.nw 314 2010-04-17 20:32:33Z ohl
```

CONTENTS

1	INTRODUCTION	1
2	ALGORITHMS	3
2.1	<i>Importance Sampling</i>	4
2.2	<i>Stratified Sampling</i>	5
2.3	<i>Vegas</i>	6
2.3.1	<i>Vegas' Inflexibility</i>	6
2.3.2	<i>Vegas' Dark Side</i>	7
2.4	<i>Multi Channel Sampling</i>	7
2.5	<i>Revolving</i>	8
2.6	<i>Parallelization</i>	8
2.6.1	<i>Multilinear Structure of the Sampling Algorithm</i>	8
2.6.2	<i>State and Message Passing</i>	13
2.6.3	<i>Random Numbers</i>	13
2.6.4	<i>Practice</i>	14
3	DESIGN TRADE OFFS	19
3.1	<i>Programming Language</i>	20
4	USAGE	21
4.1	<i>Basic Usage</i>	21
4.1.1	<i>Basic Example</i>	22
4.2	<i>Advanced Usage</i>	24
4.2.1	<i>Types</i>	25
4.2.2	<i>Shared Arguments</i>	25
4.2.3	<i>Single Channel Procedures</i>	27
4.2.4	<i>Inout/Output and Marshling</i>	28
4.2.5	<i>Multi Channel Procedures</i>	31
4.2.6	<i>Event Generation</i>	34
4.2.7	<i>Parallelization</i>	34
4.2.8	<i>Diagnostics</i>	35

4.2.9	<i>Other Procedures</i>	36
4.2.10	<i>(Currently) Undocumented Procedures</i>	36
5	IMPLEMENTATION	37
5.1	<i>The Abstract Datatype division</i>	37
5.1.1	<i>Creation, Manipulation & Injection</i>	38
5.1.2	<i>Grid Refinement</i>	44
5.1.3	<i>Probability Density</i>	48
5.1.4	<i>Quadrupole</i>	49
5.1.5	<i>Forking and Joining</i>	49
5.1.6	<i>Inquiry</i>	57
5.1.7	<i>Diagnostics</i>	58
5.1.8	<i>I/O</i>	61
5.1.9	<i>Marshaling</i>	66
5.1.10	<i>Boring Copying and Deleting of Objects</i>	69
5.2	<i>The Abstract Datatype <code>vamp_grid</code></i>	70
5.2.1	<i>Initialization</i>	77
5.2.2	<i>Sampling</i>	85
5.2.3	<i>Forking and Joining</i>	95
5.2.4	<i>Parallel Execution</i>	102
5.2.5	<i>Diagnostics</i>	105
5.2.6	<i>Multi Channel</i>	111
5.2.7	<i>Mapping</i>	125
5.2.8	<i>Event Generation</i>	133
5.2.9	<i>Convenience Routines</i>	138
5.2.10	<i>I/O</i>	142
5.2.11	<i>Marshaling</i>	156
5.2.12	<i>Boring Copying and Deleting of Objects</i>	162
5.3	<i>Interface to MPI</i>	165
5.3.1	<i>Parallel Execution</i>	166
5.3.2	<i>Event Generation</i>	180
5.3.3	<i>I/O</i>	182
5.3.4	<i>Communicating Grids</i>	184
6	SELF TEST	190
6.1	<i>No Mapping Mode</i>	190
6.1.1	<i>Serial Test</i>	190
6.1.2	<i>Parallel Test</i>	200
6.1.3	<i>Output</i>	202
6.2	<i>Mapped Mode</i>	202
6.2.1	<i>Serial Test</i>	202

<i>6.2.2 Parallel Test</i>	218
<i>6.2.3 Output</i>	219
7 APPLICATION	220
<i>7.1 Cross section</i>	220
A CONSTANTS	243
<i>A.1 Kinds</i>	243
<i>A.2 Mathematical and Physical Constants</i>	243
B ERRORS AND EXCEPTIONS	245
C THE ART OF RANDOM NUMBERS	249
<i>C.1 Application Program Interface</i>	249
<i>C.2 Low Level Routines</i>	252
<i>C.2.1 Generation of 30-bit Random Numbers</i>	252
<i>C.2.2 Initialization of 30-bit Random Numbers</i>	253
<i>C.2.3 Generation of 52-bit Random Numbers</i>	257
<i>C.2.4 Initialization of 52-bit Random Numbers</i>	257
<i>C.3 The State</i>	259
<i>C.3.1 Creation</i>	259
<i>C.3.2 Destruction</i>	261
<i>C.3.3 Copying</i>	262
<i>C.3.4 Flushing</i>	263
<i>C.3.5 Input and Output</i>	263
<i>C.3.6 Marshaling and Unmarshaling</i>	268
<i>C.4 High Level Routines</i>	271
<i>C.4.1 Single Random Numbers</i>	272
<i>C.4.2 Arrays of Random Numbers</i>	274
<i>C.4.3 Procedures With Explicit <code>tao_random_state</code></i>	276
<i>C.4.4 Static Procedures</i>	277
<i>C.4.5 Generic Procedures</i>	278
<i>C.4.6 Luxury</i>	279
<i>C.5 Testing</i>	281
<i>C.5.1 30-bit</i>	281
<i>C.5.2 52-bit</i>	283
<i>C.5.3 Test Program</i>	284
D SPECIAL FUNCTIONS	285
<i>D.1 Test</i>	287
E STATISTICS	290

F HISTOGRAMMING	293
G MISCELLANEOUS UTILITIES	303
<i>G.1 Memory Management</i>	303
<i>G.2 Sorting</i>	306
<i>G.3 Mathematics</i>	309
<i>G.4 I/O</i>	311
H LINEAR ALGEBRA	312
<i>H.1 LU Decomposition</i>	312
<i>H.2 Determinant</i>	315
<i>H.3 Diagonalization</i>	315
<i>H.4 Test</i>	320
I PRODUCTS	322
J KINEMATICS	323
<i>J.1 Lorentz Transformations</i>	323
<i>J.2 Massive Phase Space</i>	325
<i>J.3 Massive 3-Particle Phase Space Revisited</i>	328
<i>J.4 Massless n-Particle Phase Space: RAMBO</i>	331
<i>J.5 Tests</i>	332
K COORDINATES	335
<i>K.1 Angular Spherical Coordinates</i>	335
<i>K.2 Trigonometric Spherical Coordinates</i>	339
<i>K.3 Surface of a Sphere</i>	342
L IDIOMATIC FORTRAN90 INTERFACE FOR MPI	343
<i>L.1 Basics</i>	343
<i>L.2 Point to Point</i>	346
<i>L.3 Collective Communication</i>	352
M POOR MAN'S ELEMENTAL PROCEDURES	357
<i>M.1 m4 Macros</i>	357
<i>M.2 Miscellaneous Utilities</i>	358
<i>M.3 Errors and Exceptions</i>	360
<i>M.4 The Abstract Datatype <code>division</code></i>	360
<i>M.5 The Abstract Datatype <code>vamp_grid</code></i>	368

N IDEAS	373
<i>N.1 Toolbox for Interactive Optimization</i>	373
<i>N.2 Partially Non-Factorized Importance Sampling</i>	373
<i>N.3 Correlated Importance Sampling (?)</i>	373
<i>N.4 Align Coordinate System (i.e. the grid) with Singularities (or the hot region)</i>	374
<i>N.5 Automagic Multi Channel</i>	374
O CROSS REFERENCES	375
<i>O.1 Identifiers</i>	375
<i>O.2 Refinements</i>	395

Program Summary:

- **Title of program:** VAMP, Version 1.0 (October 1999)
- **Program obtainable** by anonymous `ftp` from the host `crunch.ikp.physik.th-darmstadt.de` in the directory `pub/ohl/vamp`.
- **Licensing provisions:** Free software under the GNU General Public License.
- **Programming language used:** Fortran95 [8] (Fortran90 [7] and F [13] versions available as well)
- **Number of program lines in distributed program, including test data, etc.:** ≈ 4300 (excluding comments)
- **Computer/Operating System:** Any with a Fortran95 (or Fortran90 or F) programming environment.
- **Memory required to execute with typical data:** Negligible on the scale of typical applications calling the library.
- **Typical running time:** A small fraction (typically a few percent) of the running time of applications calling the library.
- **Purpose of program:**
- **Nature of physical problem:**
- **Method of solution:**
- **Keywords:** adaptive integration, event generation, parallel processing

—1— INTRODUCTION

We present a reimplementation of the classic Vegas [1, 2] algorithm for adaptive multi-dimensional integration in Fortran95 [8, 12]¹. The purpose of this reimplementation is two-fold: for pedagogical reasons it is useful to employ Fortran95 features (in particular the array language) together with literate programming [4] for expressing the algorithm more concisely and more transparently. On the other hand we use a Fortran95 abstract type to separate the state from the functions. This allows multiple instances of Vegas with different adaptions to run in parallel and in paves the road for a more parallelizable implementation.

The variable names are more in line with [1] than with [2] or with [16, 17, 18], which is almost identical to [2].

Copyleft

Mention the GNU General Public License (maybe we can switch to the GNU Library General Public License)

¹ *Copyleft notice 1*≡

```
! Copyright (C) 1998 by Thorsten Ohl <ohl@hep.tu-darmstadt.de>
!
! VAMP is free software; you can redistribute it and/or modify it
! under the terms of the GNU General Public License as published by
! the Free Software Foundation; either version 2, or (at your option)
! any later version.
!
! VAMP is distributed in the hope that it will be useful, but
! WITHOUT ANY WARRANTY; without even the implied warranty of
```

¹Fully functional versions conforming to preceding Fortran standard [7], High Performance Fortran (HPF) [9, 10, 14], and to the Fortran90 subset F [13] are available as well. A translation to the obsolete FORTRAN77 standard [6] is possible in principle, but extremely tedious and error prone if the full functionality shall be preserved.

```
! MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
! GNU General Public License for more details.
!
! You should have received a copy of the GNU General Public License
! along with this program; if not, write to the Free Software
! Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

Mention that the tangled sources are not the preferred form of distribution:

2 *<Copyleft notice 1>+≡*

```
! This version of the source code of vamp has no comments and
! can be hard to understand, modify, and improve. You should have
! received a copy of the literate ‘noweb’ sources of vamp that
! contain the documentation in full detail.
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
```

—2— ALGORITHMS

 The notation has to be synchronized with [3]!

We establish some notation to allow a concise discussion. Notation:

$$\text{expectation: } E(f) = \frac{1}{|\mathcal{D}|} \int_{\mathcal{D}} dx f(x) \quad (2.1a)$$

$$\text{variance: } V(f) = E(f^2) - (E(f))^2 \quad (2.1b)$$

$$\text{estimate of expectation (average): } \langle X|f \rangle = \frac{1}{|X|} \sum_{x \in X} f(x) \quad (2.1c)$$

$$\text{estimate of variance: } \sigma_X^2(f) = \frac{1}{|X|-1} (\langle X|f^2 \rangle - \langle X|f \rangle^2) \quad (2.1d)$$

Where $|X|$ is the size of the point set and $|\mathcal{D}| = \int_{\mathcal{D}} dx$ the size of the integration region. If $\mathcal{E}(\langle f \rangle)$ denotes the ensemble average of $\langle X|f \rangle$ over random point sets X with $|X| = N$, we have for expectation and variance

$$\mathcal{E}(\langle f \rangle) = E(f) \quad (2.2a)$$

$$\mathcal{E}(\sigma^2(f)) = V(f) \quad (2.2b)$$

and the ensemble variance of the expectation is also given by the variance

$$\mathcal{V}(\langle f \rangle) = \frac{1}{N} V(f) \quad (2.2c)$$

Therefore, it can be estimated from $\sigma_X^2(f)$. Below, we will also use the notation \mathcal{E}_g for the ensemble average over random point sets X_g with probability distribution g . We will write $E_g(f) = E(fg)$ as well.

2.1 Importance Sampling

If, instead of uniformly distributed points X , we use points X_g distributed according to a probability density g , we can easily keep the expectation constant

$$\mathcal{E}_g(\langle f \rangle) = E_g\left(\frac{f}{g}\right) = E(f) \quad (2.3)$$

while the variance transforms non-trivially

$$\mathcal{V}_g(\langle f \rangle) = \frac{1}{N} V_g\left(\frac{f}{g}\right) = \frac{1}{N} \left(E_g\left(\frac{f^2}{g^2}\right) - \left(E_g\left(\frac{f}{g}\right)\right)^2 \right) \quad (2.4)$$

and the error is minimized when f/g is constant, i.e. g is a good approximation of f . The non-trivial problem is to find a g that can be generated efficiently and is a good approximation at the same time.

One of the more popular approaches is to use a mapping ϕ of the integration domain

$$\begin{aligned} \phi : \mathcal{D} &\rightarrow \Delta \\ x &\mapsto \xi = \phi(x) \end{aligned} \quad (2.5)$$

In the new coordinates, the distribution is multiplied by the Jacobian of the inverse map ϕ^{-1} :

$$\int_{\mathcal{D}} dx f(\phi(x)) = \int_{\Delta} d\xi J_{\phi^{-1}}(\xi) f(\xi) \quad (2.6)$$

A familiar example is given by the map

$$\begin{aligned} \phi : [0, 1] &\rightarrow \mathbf{R} \\ x &\mapsto \xi = x^0 + a \cdot \tan\left(\left(x - \frac{1}{2}\right)\pi\right) \end{aligned} \quad (2.7)$$

with the inverse $\phi^{-1}(\xi) = \text{atan}((\xi - x_0)/a)/\pi + 1/2$ and the corresponding Jacobian reproducing a resonance

$$J_{\phi^{-1}}(\xi) = \frac{d\phi^{-1}(\xi)}{d\xi} = \frac{a}{\pi} \frac{1}{(\xi - x^0)^2 + a^2} \quad (2.8)$$

Obviously, this works only for a few special distributions. Fortunately, we can combine several of these mappings to build efficient integration algorithms, as will be explained in section 2.4 below. Another approach is to construct the approximation numerically, by appropriate binning of the integration domain (cf. [1, 2, 19]). The most popular technique for this will be discussed below in section 2.3.

2.2 Stratified Sampling

The technique of importance sampling concentrates the sampling points in the region where the contribution to the integrand is largest. Alternatively we can also concentrate the sampling points in the region where the contribution to the variance is largest.

If we divide the sampling region \mathcal{D} into n disjoint subregions \mathcal{D}^i

$$\mathcal{D} = \bigcup_{i=1}^n \mathcal{D}^i, \quad \mathcal{D}^i \cap \mathcal{D}^j = \emptyset \quad (i \neq j) \quad (2.9)$$

a new estimator is

 Bzzzt! Wrong. These multi-channel formulae are incorrect for partitions and must be fixed.

$$\overline{\langle X | f \rangle} = \sum_{i=1}^n \frac{N_i}{N} \langle X_{\theta_i} | f \rangle \quad (2.10)$$

where

$$\theta_i(x) = \begin{cases} 1 & \text{for } x \in \mathcal{D}^i \\ 0 & \text{for } x \notin \mathcal{D}^i \end{cases} \quad (2.11)$$

and

$$\sum_{i=1}^n N_i = N \quad (2.12)$$

since the expectation is linear

$$\mathcal{E}(\overline{\langle f \rangle}) = \sum_{i=1}^n \frac{N_i}{N} \mathcal{E}_{\theta_i}(\langle f \rangle) = \sum_{i=1}^n \frac{N_i}{N} E_{\theta_i}(f) = \sum_{i=1}^n \frac{N_i}{N} E(f \theta_i) = E(f) \quad (2.13)$$

On the other hand, the variance of the estimator $\overline{\langle X | f \rangle}$ is

$$\mathcal{V}(\overline{\langle f \rangle}) = \sum_{i=1}^n \frac{N_i}{N} \mathcal{V}_{\theta_i}(\langle f \rangle) \quad (2.14)$$

This is minimized for

$$N_i \propto \sqrt{V(f \cdot \theta_{\mathcal{D}^i})} \quad (2.15)$$

as a simple variation of $\mathcal{V}(\overline{\langle f \rangle})$ shows.




Figure 2.1: `vegas` grid structure for non-stratified sampling (left) and for genuinely stratified sampling (right), which is used in low dimensions. N.B.: the grid and the weight functions $p_{1,2}$ are only in qualitative agreement.




Figure 2.2: One-dimensional illustration of the `vegas` grid structure for pseudo stratified sampling, which is used in high dimensions.

2.3 Vegas

Under construction!

2.3.1 Vegas' Inflexibility

The classic implementation of the Vegas algorithm [1, 2] treats all dimensions alike. This constraint allows a very concise FORTRAN77-style coding of the algorithm, but there is no theoretical reason for having the same number of divisions in each direction. On the contrary, under these circumstances, even a dimension in which the integrand is rather smooth will contribute to the exponential blow-up of cells for stratified sampling. It is obviously beneficial to use a finer grid in those directions in which the fluctuations are stronger, while a coarser grid will suffice in the other directions.

One small step along this line is implemented in Version 5.0 of the package BASES/SPRING [19], where one set of “wild” variables is separated from “smooth” variables [20].

The present reimplementation of the Vegas algorithm allows the application to choose the number of divisions in each direction freely. The routines that reshape the grid accept an integer array with the number of divisions as an optional argument `num_div`. It is easy to construct examples in which the careful use of this feature reduces the variance significantly.

Currently, no attempt is made for automatic optimization of the number of divisions. One reasonable approach is to monitor Vegas’ grid adjustments and to increase the number of division in those directions where Vegas’ keeps adjusting because of fluctuations. For each direction, a numerical measure of these fluctuations is given by the spread in the m_i . The total number of cells can be kept constant by reducing the number of divisions in the other directions appropriately. Thus

$$n_{\text{div},j} \rightarrow \frac{Q_j n_{\text{div},j}}{\left(\prod_j Q_j\right)^{1/n_{\text{dim}}}} \quad (2.16)$$

where we have used the damped standard deviation

$$Q_j = \left(\sqrt{\text{Var}(\{m\}_j)} \right)^\alpha \quad (2.17)$$

instead of the spread.

2.3.2 Vegas’ Dark Side

 Under construction!

A partial solution of this problem will be presented in section 2.5.

2.4 Multi Channel Sampling

Even if Vegas performs well for a large class of integrands, many important applications do not lead to a factorizable distribution. The class of integrands that can be integrated efficiently by Vegas can be enlarged substantially by using multi channel methods. The new class will include almost all integrals appearing in high energy physics simulations.

 The first version of this section is now obsolete. Consult [3] instead.

2.5 Revolving

 Under construction!

2.6 Parallelization

Traditionally, parallel processing has not played a large rôle in simulations for high energy physics. A natural and trivial method of utilizing many processors will run many instances of the same (serial) program with different values of the input parameters in parallel. Typical matrix elements and phase space integrals offer few opportunities for small scale parallelization.

On the other hand, parameter fitting has become possible recently for observables involving a phase space integration. In this case, fast evaluation of the integral is essential and parallel execution becomes an interesting option.

A different approach to parallelizing Vegas has been presented recently [21].

2.6.1 Multilinear Structure of the Sampling Algorithm

In order to discuss the problems with parallelizing adaptive integration algorithms and to present solutions, it helps to introduce some mathematical notation. A sampling S is a map from the space π of point sets and the space F of functions to the real (or complex) numbers

$$\begin{aligned} S : \pi \times F &\rightarrow \mathbf{R} \\ (p, f) &\mapsto I = S(p, f) \end{aligned}$$

For our purposes, we have to be more specific about the nature of the point set. In general, the point set will be characterized by a sequence of pseudo random numbers $\rho \in R$ and by one or more grids $G \in \Gamma$ used for importance or stratified sampling. A simple sampling

$$\begin{aligned} S_0 : R \times \Gamma \times A \times F \times \mathbf{R} \times \mathbf{R} &\rightarrow R \times \Gamma \times A \times F \times \mathbf{R} \times \mathbf{R} \\ (\rho, G, a, f, \mu_1, \mu_2) &\mapsto (\rho', G, a', f, \mu'_1, \mu'_2) = S_0(\rho, G, a, f, \mu_1, \mu_2) \end{aligned} \tag{2.18}$$

estimates the n -th moments $\mu'_n \in \mathbf{R}$ of the function $f \in F$. The integral and its standard deviation can be derived easily from the moments

$$I = \mu_1 \tag{2.19a}$$

$$\sigma^2 = \frac{1}{N-1} (\mu_2 - \mu_1^2) \tag{2.19b}$$

while the latter are more convenient for the following discussion. In addition, S_0 collects auxiliary information to be used in the grid refinement, denoted by $a \in A$. The unchanged arguments G and f have been added to the result of S_0 in (2.18), so that S_0 has identical domain and codomain and can therefore be iterated. Previous estimates μ_n may be used in the estimation of μ'_n , but a particular S_0 is free to ignore them as well. Using a little notational freedom, we augment \mathbf{R} and A with a special value \cdot , which will always be discarded by S_0 .

In an adaptive integration algorithm, there is also a refinement operation $r : \Gamma \times A \rightarrow \Gamma$ that can be extended naturally to the codomain of S_0

$$\begin{aligned} r : R \times \Gamma \times A \times F \times \mathbf{R} \times \mathbf{R} &\rightarrow R \times \Gamma \times A \times F \times \mathbf{R} \times \mathbf{R} \\ (\rho, G, a, f, \mu_1, \mu_2) &\mapsto (\rho, G', a, f, \mu_1, \mu_2) = r(\rho, G, a, f, \mu_1, \mu_2) \end{aligned} \quad (2.20)$$

so that $S = rS_0$ is well defined and we can specify n -step adaptive sampling as

$$S_n = S_0(rS_0)^n \quad (2.21)$$

Since, in a typical application, only the estimate of the integral and the standard deviation are used, a projection can be applied to the result of S_n :

$$\begin{aligned} P : R \times \Gamma \times A \times F \times \mathbf{R} \times \mathbf{R} &\rightarrow \mathbf{R} \times \mathbf{R} \\ (\rho, G, a, f, \mu_1, \mu_2) &\mapsto (I, \sigma) \end{aligned} \quad (2.22)$$

Then

$$(I, \sigma) = PS_0(rS_0)^n(\rho, G_0, \cdot, f, \cdot, \cdot) \quad (2.23)$$

and a good refinement prescription r , such as Vegas, will minimize the σ .

For parallelization, it is crucial to find a division of S_n or any part of it into *independent* pieces that can be evaluated in parallel. In order to be effective, r has to be applied to *all* of a and therefore a synchronization of G before and after r is appropriately. Furthermore, r usually uses only a tiny fraction of the CPU time and it makes little sense to invest a lot of effort into parallelizing it beyond what the Fortran compiler can infer from array notation. On the other hand, S_0 can be parallelized naturally, because all operations are linear, including the computation of a . We only have to make sure that the cost of communicating the results of S_0 and r back and forth during the computation of S_n do not offset any performance gain from parallel processing.

When we construct a decomposition of S_0 and proof that it does not change the results, i.e.

$$S_0 = \iota S_0 \phi \quad (2.24)$$

where ϕ is a forking operation and ι is a joining operation, we are faced with the technical problem of a parallel random number source ρ . As made explicit in (2.18), S_0 changes the state of the random number general ρ , demanding *identical* results therefore imposes a strict ordering on the operations and defeats parallelization. It is possible to devise implementations of S_0 and ρ that circumvent this problem by distributing subsequences of ρ in such a way among processes that results do not depend on the number of parallel processes.

However, a reordering of the random number sequence will only change the result by the statistical error, as long as the scale of the allowed reorderings is *bounded* and much smaller than the period of the random number generator ¹. Below, we will therefore use the notation $x \approx y$ for “equal for an appropriate finite reordering of the ρ used in calculating x and y ”. For our purposes, the relation $x \approx y$ is strong enough and allows simple and efficient implementations.

Since S_0 is essentially a summation, it is natural to expect a linear structure

$$\bigoplus_i S_0(\rho_i, G_i, a_i, f, \mu_{1,i}, \mu_{2,i}) \approx S_0(\rho, G, a, f, \mu_1, \mu_2) \quad (2.25a)$$

where

$$\rho = \bigoplus_i \rho_i \quad (2.25b)$$

$$G = \bigoplus_i G_i \quad (2.25c)$$

$$a = \bigoplus_i a_i \quad (2.25d)$$

$$\mu_n = \bigoplus_i \mu_{n,i} \quad (2.25e)$$

for appropriate definitions of “ \oplus ”. For the moments, we have standard addition

$$\mu_{n,1} \oplus \mu_{n,2} = \mu_{n,1} + \mu_{n,2} \quad (2.26)$$

and since we only demand equality up to reordering, we only need that the ρ_i are statistically independent. This leaves us with G and a and we have to discuss importance sampling and stratified sampling separately.

¹Arbitrary reorderings on the scale of the period of the random number generators could select constant sequences and have to be forbidden.

Importance Sampling

In the case of naive Monte Carlo and importance sampling the natural decomposition of G is to take j copies of the same grid G/j which is identical to G , each with one j -th of the total sampling points. As long as the a are linear themselves, we can add them up just like the moments

$$a_1 \oplus a_2 = a_1 + a_2 \quad (2.27)$$

and we have found a decomposition (2.25). In the case of Vegas, the a_i are sums of function values at the sampling points. Thus they are obviously linear and this approach is applicable to Vegas in the importance sampling mode.

Stratified Sampling

The situation is more complicated in the case of stratified sampling. The first complication is that in pure stratified sampling there are only two sampling points per cell. Splitting the grid in two pieces as above provide only a very limited amount of parallelization. The second complication is that the a are no longer linear, since they correspond to a sampling of the variance per cell and no longer of function values themselves.

However, as long as the samplings contribute to disjoint bins only, we can still “add” the variances by combining bins. The solution is therefore to divide the grid into disjoint bins along the divisions of the stratification grid and to assign a set of bins to each processor.

Finer decompositions will incur higher communications costs and other resource utilization. An implementation based on PVM is described in [21], which minimizes the overhead by running identical copies of the grid G on each processor. Since most of the time is usually spent in function evaluations, it makes sense to run a full S_0 on each processor, skipping function evaluations everywhere but in the region assigned to the processor. This is a neat trick, which is unfortunately tied to the computational model of message passing systems such as PVM and MPI [11]. More general paradigms can not be supported since the separation of the state for the processors is not explicit (it is implicit in the separated address space of the PVM or MPI processes).

However, it is possible to implement (2.25) directly in an efficient manner. This is based on the observation that the grid G used by Vegas is factorized into divisions D^j for each dimension

$$G = \bigotimes_{j=1}^{n_{\text{dim}}} D^j \quad (2.28)$$

and decompositions of the D^j induce decompositions of G

$$\begin{aligned} G_1 \oplus G_2 &= \left(\bigotimes_{j=1}^{i-1} D^j \otimes D_1^i \otimes \bigotimes_{i=j+1}^{n_{\text{dim}}} D^j \right) \oplus \left(\bigotimes_{j=1}^{i-1} D^j \otimes D_2^i \otimes \bigotimes_{i=j+1}^{n_{\text{dim}}} D^j \right) \\ &= \bigotimes_{j=1}^{i-1} D^j \otimes (D_1^i \oplus D_2^i) \otimes \bigotimes_{j=i+1}^{n_{\text{dim}}} D^j \end{aligned} \quad (2.29)$$

We can translate (2.29) directly to code that performs the decomposition $D^i = D_1^i \oplus D_2^i$ discussed below and simply duplicates the other divisions $D^{j \neq i}$. A decomposition along multiple dimensions is implemented by a recursive application of (2.29).

In Vegas, the auxiliary information a inherits a factorization similar to the grid (2.28)

$$a = (d^1, \dots, d^{n_{\text{dim}}}) \quad (2.30)$$

but not a multilinear structure. Instead, *as long as the decomposition respects the stratification grid*, we find the in place of (2.29)

$$a_1 \oplus a_2 = (d_1^1 + d_2^1, \dots, d_1^i \oplus d_2^i, \dots, d_1^{n_{\text{dim}}} + d_2^{n_{\text{dim}}}) \quad (2.31)$$

with “+” denoting the standard addition of the bin contents and “ \oplus ” denoting the aggregation of disjoint bins. If the decomposition of the division would break up cells of the stratification grid (2.31) would be incorrect, because, as discussed above, the variance is not linear.

Now it remains to find a decomposition

$$D^i = D_1^i \oplus D_2^i \quad (2.32)$$

for both the pure stratification mode and the pseudo stratification mode of vegas (cf. figure 2.1). In the pure stratification mode, the stratification grid is strictly finer than the adaptive grid and we can decompose along either of them immediately. Technically, a decomposition along the coarser of the two is straightforward. Since the adaptive grid already has more than 25 bins, a decomposition along the stratification grid makes no practical sense and the decomposition along the adaptive grid has been implemented. The sampling algorithm S_0 can be applied *unchanged* to the individual grids resulting from the decomposition.

For pseudo stratified sampling (cf. figure 2.2), the situation is more complicated, because the adaptive and the stratification grid do not share bin boundaries. Since Vegas does *not* use the variance in this mode, it would be theoretically possible to decompose along the adaptive grid and to mimic the




Figure 2.3: Forking one dimension d of a grid into three parts $ds(1)$, $ds(2)$, and $ds(3)$. The picture illustrates the most complex case of pseudo stratified sampling (cf. fig. 2.2).

incomplete bins of the stratification grid in the sampling algorithm. However, this would be a technical complication, destroying the universality of S_0 . Therefore, the adaptive grid is subdivided in a first step in

$$\text{lcm} \left(\frac{\text{lcm}(n_f, n_g)}{n_f}, n_x \right) \quad (2.33)$$

bins,² such that the adaptive grid is strictly finer than the stratification grid. This procedure is shown in figure 2.3.

2.6.2 State and Message Passing

2.6.3 Random Numbers

In the parallel example sitting on top of MPI [11] takes advantage of the ability of Knuth's generator [15] to generate statistically independent subse-

²The coarsest grid covering the division of n_g bins into n_f forks has $n_g / \text{gcd}(n_f, n_g) = \text{lcm}(n_f, n_g) / n_f$ bins per fork.

quences. However, since the state of the random number generator is explicit in all procedure calls, other means of obtaining subsequences can be implemented in a trivial wrapper.

The results of the parallel example will depend on the number of processors, because this effects the subsequences being used. Of course, the variation will be compatible with the statistical error. It must be stressed that the results are deterministic for a given number of processors and a given set of random number generator seeds. Since parallel computing environments allow to fix the number of processors, debugging of exceptional conditions is possible.

2.6.4 Practice

In this section we show three implementations of S_n : one serial, and two parallel, based on HPF [9, 10, 14] and MPI [11], respectively. From these examples, it should be obvious how to adapt VAMP to other parallel computing paradigms.

Serial

Here is a bare bones serial version of S_n , for comparison with the parallel versions below. The real implementation of `vamp_sample_grid` in the module `vamp` includes some error handling, diagnostics and the projection P (cf. (2.22)):

14 ⟨Serial implementation of $S_n = S_0(rS_0)^n$ 14⟩≡

```

subroutine vamp_sample_grid (rng, g, iterations, func)
    type(tao_random_state), intent(inout) :: rng
    type(vamp_grid), intent(inout) :: g
    integer, intent(in) :: iterations
    <Interface declaration for func 22>
    integer :: iteration
    iterate: do iteration = 1, iterations
        call vamp_sample_grid0 (rng, g, func)
        call vamp_refine_grid (g)
    end do iterate
end subroutine vamp_sample_grid

```

HPF

The HPF version of S_n is based on decomposing the grid `g` as described in section 2.6.1 and lining up the components in an array `gs`. The elements of `gs` can then be processed in parallel. This version can be compiled with any

Fortran compiler and a more complete version of this procedure (including error handling, diagnostics and the projection P) is included with VAMP as `vamp_sample_grid_parallel` in the module `vamp`. This way, the algorithm can be tested on a serial machine, but there will obviously be no performance gain.

Instead of one random number generator state `rng`, it takes an array consisting of one state per processor. These `rng(:)` are assumed to be initialized, such that the resulting sequences are statistically independent. For this purpose, Knuth's random number generator [15] is most convenient and is included with VAMP (see the example on page 16). Before each S_0 , the procedure `vamp_distribute_work` determines a good decomposition of the grid `d` into `size(rng)` pieces. This decomposition is encoded in the array `d` where `d(1,:)` holds the dimensions along which to split the grid and `d(2,:)` holds the corresponding number of divisions. Using this information, the grid is decomposed by `vamp_fork_grid`. The HPF compiler will then distribute the `!hpfs` independent loop among the processors. Finally, `vamp_join_grid` gathers the results.

15 *(Parallel implementation of $S_n = S_0(rS_0)^n$ (HPF) 15)≡*

```

subroutine vamp_sample_grid_hpf (rng, g, iterations, func)
    type(tao_random_state), dimension(:), intent(inout) :: rng
    type(vamp_grid), intent(inout) :: g
    integer, intent(in) :: iterations
    <Interface declaration for func 22>
    type(vamp_grid), dimension(:), allocatable :: gs, gx
    !hpfs processors p(number_of_processors())
    !hpfs distribute gs(cyclic(1)) onto p
    integer, dimension(:, :, ), pointer :: d
    integer :: iteration, num_workers
    iterate: do iteration = 1, iterations
        call vamp_distribute_work (size (rng), vamp_rigid_divisions (g), d)
        num_workers = max (1, product (d(2,:)))
        if (num_workers > 1) then
            allocate (gs(num_workers), gx(vamp_fork_grid_joints (d)))
            call vamp_create_empty_grid (gs)
            call vamp_fork_grid (g, gs, gx, d)
            !hpfs independent
            do i = 1, num_workers
                call vamp_sample_grid0 (rng(i), gs(i), func)
            end do
            call vamp_join_grid (g, gs, gx, d)
            call vamp_delete_grid (gs)
            deallocate (gs, gx)
        end if
    end iterate

```

```

    else
        call vamp_sample_grid0 (rng(1), g, func)
    end if
    call vamp_refine_grid (g)
end do iterate
end subroutine vamp_sample_grid_hp

```

Since `vamp_sample_grid0` performs the bulk of the computation, an almost linear speedup with the number of processors can be achieved, if `vamp_distribute_work` finds a good decomposition of the grid. The version of `vamp_distribute_work` distributed with VAMP does a good job in most cases, but will not be able to use all processors if their number is a prime number larger than the number of divisions in the stratification grid. Therefore it can be beneficial to tune `vamp_distribute_work` to specific hardware. Furthermore, using a finer stratification grid can improve performance.

For definiteness, here is an example of how to set up the array of random number generators for HPF. Note that this simple seeding procedure only guarantees statistically independent sequences with Knuth's random number generator [15] and will fail with other approaches.

16 <Parallel usage of $S_n = S_0(rS_0)^n$ (HPF) 16>≡

```

type(tao_random_state), dimension(:), allocatable :: rngs
!hpfs$ processors p(number_of_processors())
!hpfs$ distribute gs(cyclic(1)) onto p
integer :: i, seed
! ...
allocate (rngs(number_of_processors()))
seed = 42 ! can be read from a file, of course ...
!hpfs$ independent
do i = 1, size (rngs)
    call tao_random_create (rngs(i), seed + i)
end do
! ...
call vamp_sample_grid_hp (rngs, g, 6, func)
! ...

```

MPI

The MPI version is more low level, because we have to keep track of message passing ourselves. Note that we have made this synchronization points explicit with three `if ... then ... else ... end if` blocks: forking, sampling, and joining. These blocks could be merged (without any performance gain) at the expense of readability. We assume that `rng` has been initialized

in each process such that the sequences are again statistically independent.

17 *(Parallel implementation of $S_n = S_0(rS_0)^n$ (MPI) 17)*≡

```

subroutine vamp_sample_grid_mpi (rng, g, iterations, func)
    type(tao_random_state), dimension(:), intent(inout) :: rng
    type(vamp_grid), intent(inout) :: g
    integer, intent(in) :: iterations
    <Interface declaration for func 22>
    type(vamp_grid), dimension(:), allocatable :: gs, gx
    integer, dimension(:, :, ), pointer :: d
    integer :: num_proc, proc_id, iteration, num_workers
    call mpi90_size (num_proc)
    call mpi90_rank (proc_id)
    iterate: do iteration = 1, iterations
        if (proc_id == 0) then
            call vamp_distribute_work (num_proc, vamp_rigid_divisions (g), d)
            num_workers = max (1, product (d(2,:)))
        end if
        call mpi90_broadcast (num_workers, 0)
        if (proc_id == 0) then
            allocate (gs(num_workers), gx(vamp_fork_grid_joints (d)))
            call vamp_create_empty_grid (gs)
            call vamp_fork_grid (g, gs, gx, d)
            do i = 2, num_workers
                call vamp_send_grid (gs(i), i-1, 0)
            end do
        else if (proc_id < num_workers) then
            call vamp_receive_grid (g, 0, 0)
        end if
        if (proc_id == 0) then
            if (num_workers > 1) then
                call vamp_sample_grid0 (rng, gs(1), func)
            else
                call vamp_sample_grid0 (rng, g, func)
            end if
        else if (proc_id < num_workers) then
            call vamp_sample_grid0 (rng, g, func)
        end if
        if (proc_id == 0) then
            do i = 2, num_workers
                call vamp_receive_grid (gs(i), i-1, 0)
            end do
            call vamp_join_grid (g, gs, gx, d)
            call vamp_delete_grid (gs)
        end if
    end do
end subroutine

```

```
    deallocate (gs, gx)
    call vamp_refine_grid (g)
    else if (proc_id < num_workers) then
        call vamp_send_grid (g, 0, 0)
    end if
end do iterate
end subroutine vamp_sample_grid_mpi
```

A more complete version of this procedure is included with VAMP as well, this time as `vamp_sample_grid` in the MPI support module `vampi`.

—3— DESIGN TRADE OFFS

There have been three competing design goals for vegas, that are not fully compatible and had to be reconciled with compromises:

- *Ease-Of-Use*: few procedures, few arguments.
- *Parallelizability*: statelessness
- *Performance and Flexibility*: rich interface, functionality.

In fact, parallelizability and ease-of-use are complementary. A parallelizable implementation has to expose *all* the internal state. In our case, this includes the state of the random number generator and the adaptive grid. A simple interface would hide such details from the user.

The modern language features introduced to Fortran in 1990 [7] allows to reconcile these competing goals. Two abstract data types `vamp_state` and `tao_random_state` hide the details of the implementation from the user and encapsulate the two states in just two variables.

Another problem with parallelizability arised from the lack of a general exception mechanism in Fortran. The Fortran90 standard [8] forbids *any* input/output (even to the terminal) as well as `stop` statements in parallelizable (`pure`) procedures. This precludes simple approaches to monitoring and error handling. In Vegas we use a simple hand crafted exception mechanism (see chapter B) for communicating error conditions to the out layers of the applications. Unfortunately this requires the explicit passing of state in argument lists.

An unfortunate consequence of the similar approach to monitoring is that monitoring is *not* possible during execution. Instead, intermediate results can only be examined after a parallelized section of code has completed.

3.1 Programming Language

We have chosen to implement VAMP in Fortran90/95, which some might consider a questionable choice today. Nevertheless, we are convinced that Fortran90/95 (with all its weaknesses) is, by a wide margin, the right tool for the job.

Let us consider the alternatives

- FORTRAN77 is still the dominant language in high energy physics and all running experiment's software environments are based on it. However, the standard [6] is obsolete now and the successors [7, 8] have added many desirable features, while retaining almost all of FORTRAN77 as a subset.
- C/C++ appears to be the most popular programming language in industry and among young high energy physicists. Large experiments have taken a bold move and are basing their software environment on C++.
- Typed higher order functional programming languages (ML, Haskell, etc.) are a very promising development. Unfortunately, there is not yet enough industry support for high performance optimizing compilers. While the performance penalty of these languages is not as high as commonly believed (research compilers, which do not perform extensive processor specific optimizations, result in code that runs by a factor of two or three slower than equivalent Fortran code), it is relevant for long running, computing intensive applications. In addition, these languages are syntactically and idiomatically very different from Fortran and C. Another implementation of VAMP in ML will be undertaken for research purposes to investigate new algorithms that can only be expressed awkwardly in Fortran, but we do not expect it to gain immediate popularity.

—4— USAGE

4.1 Basic Usage

```
type(vamp_grid)

subroutine vamp_create_grid (g, domain [, num_calls] [, exc])
    Create a fresh grid for the integration domain
    
$$\mathcal{D} = [D_{1,1}, D_{2,1}] \times [D_{1,2}, D_{2,2}] \times \dots \times [D_{1,n}, D_{2,n}] \quad (4.1)$$

    dropping all accumulated results. This function must not be called twice on the first argument, without an intervening vamp_delete_grid. If the variable num_calls is given, it will be the number of sampling points per iteration for the call to vamp_sample_grid.
```

```
subroutine vamp_delete_grid (g [, exc])
subroutine vamp_discard_integral (g [, num_calls] [, exc])
    Keep the current optimized grid, but drop the accumulated results for the integral (value and errors). If the variable num_calls is given, it will be the new number of sampling points per iteration for the calls to vamp_sample_grid.
```

```
subroutine vamp_reshape_grid (g [, num_calls] [, exc])
    Keep the current optimized grid and the accumulated results for the integral (value and errors). The variable num_calls is the new number of sampling points per iteration for the calls to vamp_sample_grid.
```

```
subroutine vamp_sample_grid (rng, g, func, iterations
    [, integral] [, std_dev] [, avg_chi2] [, exc] [, history])
```

Sample the function `func` using the grid `g` for `iterations` iterations and optimize the grid after each iteration. The results are returned in `integral`, `std_dev` and `avg_chi2`. The random number generator uses and updates the state stored in `rng`. The explicit random number state is inconvenient, but required for parallelizability.

```
subroutine vamp_integrate (rng, g, func, calls [, integral]
[, std_dev] [, avg_chi2] [, exc] [, history])
```

This is a wrapper around the above routines, that is steered by a `integer, dimension(2,:)` array `calls`. For each `i`, there will be `calls(1,i)` iterations with `calls(2,i)` sampling points.

```
subroutine vamp_integrate (rng, domain, func, calls
[, integral] [, std_dev] [, avg_chi2] [, exc] [, history])
```

A second specific form of `vamp_integrate`. This one keeps a private grid and provides the shortest—and most inflexible—calling sequence.

22 *⟨Interface declaration for func 22⟩*≡

```
interface
    pure function func (xi, prc_index, weights, channel, grids) result (f)
        use kinds
        use vamp_grid_type !NODEP!
        real(kind=default), dimension(:), intent(in) :: xi
        integer, intent(in) :: prc_index
        real(kind=default), dimension(:), intent(in), optional :: weights
        integer, intent(in), optional :: channel
        type(vamp_grid), dimension(:), intent(in), optional :: grids
        real(kind=default) :: f
    end function func
end interface
```

4.1.1 Basic Example

In Fortran95, the function to be sampled *must* be `pure`, i.e. have no side effects to allow parallelization. The optional arguments `weights` and `channel` *must* be declared to allow the compiler to verify the interface, but they are ignored during basic use. Their use for multi channel sampling will be explained below. Here's a Gaussian

$$f(x) = e^{-\frac{1}{2} \sum_i x_i^2} \quad (4.2)$$

```

23a <basic.f90 23a>≡
  module basic_fct
    use kinds
    implicit none
    private
    public :: fct
  contains
    function fct (x, weights, channel) result (f_x)
      real(kind=default), dimension(:), intent(in) :: x
      real(kind=default), dimension(:), intent(in), optional :: weights
      integer, intent(in), optional :: channel
      real(kind=default) :: f_x
      f_x = exp (-0.5 * sum (x*x))
    end function fct
  end module basic_fct

```

In the main program, we need to import five modules. The customary module `kinds` defines `double` as the kind for double precision floating point numbers. The module `exceptions` provides simple error handling support (parallelizable routines are not allowed to issue error messages themselves, but must pass them along). The module `tao_random_numbers` hosts the random number generator used and `vamp` is the adaptive interation module proper. Finally, the application module `basic_fct` has to be imported as well.

```

23b <basic.f90 23a>+≡
  program basic
    use kinds
    use exceptions
    use tao_random_numbers
    use vamp
    use basic_fct
    implicit none

```

Then we define four variables for an error message, the random number generator state and the adaptive integration grid. We also declare a variable for holding the integration domain and variables for returning the result. In this case we integrate the 7-dimensional hypercube.

```

23c <basic.f90 23a>+≡
  type(exception) :: exc
  type(tao_random_state) :: rng
  type(vamp_grid) :: grid
  real(kind=default), dimension(2,7) :: domain
  real(kind=default) :: integral, error, chi2
  domain(1,:) = -1.0
  domain(2,:) = 1.0

```

Initialize and seed the random number generator. Initialize the grid for 10 000 sampling points.

24a `<basic.f90 23a>+≡`

```
call tao_random_create (rng, seed=0)
call clear_exception (exc)
call vamp_create_grid (grid, domain, num_calls=10000, exc=exc)
call handle_exception (exc)
```

Warm up the grid in six low statistics iterations. Clear the error status before and check it after the sampling.

24b `<basic.f90 23a>+≡`

```
call clear_exception (exc)
call vamp_sample_grid (rng, grid, fct, 6, exc=exc)
call handle_exception (exc)
```

Throw away the intermediate results and reshape the grid for 100 000 sampling points—keeping the adapted grid—and do four iterations of a higher statistics integration

24c `<basic.f90 23a>+≡`

```
call clear_exception (exc)
call vamp_discard_integral (grid, num_calls=100000, exc=exc)
call handle_exception (exc)
call clear_exception (exc)
call vamp_sample_grid (rng, grid, fct, 4, integral, error, chi2, exc=exc)
call handle_exception (exc)
print *, "integral = ", integral, "+/-", error, " (chi^2 = ", chi2, ")"
end program basic
```

Since this is the most common use, there is a convenience routine available and the following code snippet is equivalent:

24d `(Alternative to basic.f90 24d)≡`

```
integer, dimension(2,2) :: calls
calls(:,1) = (/ 6, 10000 /)
calls(:,2) = (/ 4, 100000 /)
call clear_exception (exc)
call vamp_integrate (rng, domain, fct, calls, integral, error, chi2, exc=exc)
call handle_exception (exc)
```

4.2 Advanced Usage



Caveat emptor: no magic of literate programming can guarantee that the following remains in sync with the implementation. This has to be maintained manually.

All `real` variables are declared as `real(kind=default)` in the source and the variable `double` is imported from the module `kinds` (see appendix A.1). The representation of real numbers can therefore be changed by changing `double` in `kinds`.

4.2.1 Types

```
type(vamp_grid)
type(vamp_grids)
type(vamp_history)
type(exception)
  (from module exceptions)
```

4.2.2 Shared Arguments

Arguments keep their name across procedures, in order to make the Fortran90 keyword interface consistent.

`real, intent(in) :: accuracy`

Terminate S_n after $n' < n$ iterations, if relative error is smaller than `accuracy`. Specifically, the terminatio condition is

$$\frac{\text{std_dev}}{\text{integral}} < \text{accuracy} \quad (4.3)$$

`real, intent(out) :: avg_chi2`

The average χ^2 of the iterations.

`integer, intent(in) :: channel`

Call `func` with this optional argument. Multi channel sampling uses this to emulate arrays of functions

`logical, intent(in) :: covariance`

Collect covariance data.

`type(exception), intent(inout) :: exc`

Exceptional conditions are reported in `exc`.

`type(vamp_grid), intent(inout) :: g`

Unless otherwise noted, `g` denotes the active sampling grid in the documentation below.

```
type(vamp_histories), dimension(:), intent(inout) ::  
    histories
```

Diagnostic information for multi channel sampling.

```
type(vamp_history), dimension(:), intent(inout) ::  
    history
```

Diagnostic information for single channel sampling or summary of multi channel sampling.

```
real, intent(out) :: integral
```

The current best estimate of the integral.

```
integer, intent(in) :: iterations
```

```
real, dimension(:, :, :), intent(in) :: map
```

```
integer, intent(in) :: num_calls
```

The number of sampling points.

```
integer, dimension(:), intent(in) :: num_div
```

Number of divisions of the adaptive grid in each dimension.

```
logical, intent(in) :: quadrupole
```

Allow “quadrupole oscillations” of the sampling grid (cf. section 2.3.1).

```
type(tao_random_state), intent(inout) :: rng
```

Unless otherwise noted, `rng` denotes the source of random numbers used for sampling in the documentation below.

```
real, intent(out) :: std_dev
```

The current best estimate of the error on the integral.

```
logical, intent(in) :: stratified
```

Try to use stratified sampling.

```
real(kind=default), dimension(:), intent(in) :: weights
```

...

4.2.3 Single Channel Procedures

```
subroutine vamp_create_grid (g, domain, num_calls
    [, quadrupole] [, stratified] [, covariance] [, map] [, exc])
    real, dimension(:, :, :), intent(in) :: domain

subroutine vamp_create_empty_grid (g)

subroutine vamp_discard_integral (g [, num_calls]
    [, stratified] [, quadrupole] [, covariance] [, exc])

subroutine vamp_reshape_grid (g [, num_calls] [, num_div]
    [, stratified] [, quadrupole] [, covariance] [, exc])

subroutine vamp_sample_grid (rng, g, func, iterations
    [, integral] [, std_dev] [, avg_chi2] [, accuracy] [, channel]
    [, weights] [, exc] [, history])

    func

 $S_n$  with  $n = \text{iterations}$ 

subroutine vamp_sample_grid0 (rng, g, func, [, channel]
    [, weights] [, exc])

    func

 $S_0$ 

subroutine vamp_refine_grid (g, [, exc])
    r

subroutine vamp_average_iterations (g, iteration, integral,
    std_dev, avg_chi2)

    integer, intent(in) :: iteration
    Number of iterations so far (needed for  $\chi^2$ ).

subroutine vamp_integrate (g, func, calls [, integral]
    [, std_dev] [, avg_chi2] [, accuracy] [, covariance])

    type(vamp_grid), intent(inout) :: g
    func
```

```

integer, dimension(:, :, ), intent(in) :: calls

subroutine vamp_integrate (region, func, calls [, integral]
[, std_dev] [, avg_chi2] [, stratified] [, accuracy] [, pancake]
[, cigar])

real, dimension(:, :, ), intent(in) :: region
func

integer, dimension(:, :, ), intent(in) :: calls
integer, intent(in) :: pancake
integer, intent(in) :: cigar

subroutine vamp_copy_grid (lhs, rhs)

type(vamp_grid), intent(inout) :: lhs
type(vamp_grid), intent(in) :: rhs

subroutine vamp_delete_grid (g)

type(vamp_grid), intent(inout) :: g

```

4.2.4 Inout/Output and Marshling

```

subroutine vamp_write_grid (g, [ , ... ])

type(vamp_grid), intent(inout) :: g

subroutine vamp_read_grid (g, [ , ... ])

type(vamp_grid), intent(inout) :: g

subroutine vamp_write_grids (g, [ , ... ])

type(vamp_grids), intent(inout) :: g

subroutine vamp_read_grids (g, [ , ... ])

type(vamp_grids), intent(inout) :: g

pure subroutine vamp_marshall_grid (g, integer_buffer,
double_buffer)

```

```

type(vamp_grid), intent(in) :: g
integer, dimension(:), intent(inout) :::
integer_buffer
real(kind=default), dimension(:), intent(inout)
:: double_buffer

```

Marshal the grid `g` in the integer array `integer_buffer` and the real array `double_buffer`, which must have at least the sizes obtained from call `vamp_marshal_grid_size (g, integer_size, double_size)`.

 Note that we can not use the `transfer` intrinsic function for marshalling types that contain pointers that substitute for allocatable array components. `transfer` would copy the pointers in this case and not where they point to!

```

pure subroutine vamp_marshal_grid_size (g, integer_size,
double_size)

type(vamp_grid), intent(in) :: g
integer :: words

```

Compute the sizes of the arrays required for marshaling the grid `g`.

```

pure subroutine vamp_unmarshal_grid (g, integer_buffer,
double_buffer)

type(vamp_grid), intent(inout) :: g
integer, dimension(:), intent(in) :::
integer_buffer
real(kind=default), dimension(:), intent(in) :::
double_buffer

```

Marshaling and unmarshaling need to use two separate buffers for integers and floating point numbers. In a homogeneous network, the intrinsic procedure `transfer` could be used to store the floating point numbers in the integer array. In a heterogeneous network this will fail. However, message passing environments provide methods for sending floating point numbers. For example, here's how to send a grid from process 0 to process 1 in MPI [11]

29 ⟨MPI communication example 29⟩≡
call `vamp_marshal_grid_size (g, isize, dsize)`

```

allocate (ibuf(isize), dbuf(dsize))
call mpi_comm_rank (MPI_COMM_WORLD, proc_id, errno)
select case (proc_id)
  case (0)
    call vamp_marshal_grid (g, ibuf, dbuf)
    call mpi_send (ibuf, size (ibuf), MPI_INTEGER, &
                  1, 1, MPI_COMM_WORLD, errno)
    call mpi_send (dbuf, size (dbuf), MPI_DOUBLE_PRECISION, &
                  1, 2, MPI_COMM_WORLD, errno)
  case (1)
    call mpi_recv (ibuf, size (ibuf), MPI_INTEGER, &
                  0, 1, MPI_COMM_WORLD, status, errno)
    call mpi_recv (dbuf, size (dbuf), MPI_DOUBLE_PRECISION, &
                  0, 2, MPI_COMM_WORLD, status, errno)
    call vamp_unmarshal_grid (g, ibuf, dbuf)
end select

```

assuming that `double` is such that `MPI_DOUBLE_PRECISION` corresponds to `real(kind=default)`. The module `vampi` provides two high level functions `vamp_send_grid` and `vamp_receive_grid` that handle the low level details:

30 *<MPI communication example' 30>*

```

call mpi_comm_rank (MPI_COMM_WORLD, proc_id, errno)
select case (proc_id)
  case (0)
    call vamp_send_grid (g, 1, 0)
  case (1)
    call vamp_receive_grid (g, 0, 0)
end select

subroutine vamp_marshal_history_size (g, [, ...])
  type(vamp_grid), intent(inout) :: g

subroutine vamp_marshal_history (g, [, ...])
  type(vamp_grid), intent(inout) :: g

subroutine vamp_unmarshal_history (g, [, ...])
  type(vamp_grid), intent(inout) :: g

```

4.2.5 Multi Channel Procedures

$$g \circ \phi_i = \left| \frac{\partial \phi_i}{\partial x} \right|^{-1} \left(\alpha_i g_i + \sum_{\substack{j=1 \\ j \neq i}}^{N_c} \alpha_j (g_j \circ \pi_{ij}) \left| \frac{\partial \pi_{ij}}{\partial x} \right| \right). \quad (4.4)$$

31a *(Interface declaration for phi 31a)≡*

```
interface
    pure function phi (xi, channel) result (x)
        use kinds
        real(kind=default), dimension(:), intent(in) :: xi
        integer, intent(in) :: channel
        real(kind=default), dimension(size(xi)) :: x
    end function phi
end interface
```

31b *(Interface declaration for ihp 31b)≡*

```
interface
    pure function ihp (x, channel) result (xi)
        use kinds
        real(kind=default), dimension(:), intent(in) :: x
        integer, intent(in) :: channel
        real(kind=default), dimension(size(x)) :: xi
    end function ihp
end interface
```

31c *(Interface declaration for jacobian 31c)≡*

```
interface
    pure function jacobian (x, prc_index, channel) result (j)
        use kinds
        use vamp_grid_type !NODEP!
        real(kind=default), dimension(:), intent(in) :: x
        integer, intent(in) :: prc_index
        integer, intent(in) :: channel
        real(kind=default) :: j
    end function jacobian
end interface
```

```
function vamp_multi_channel (func, phi, ihp, jacobian, x,
                           weights1, grids)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:), intent(in) :: weights
```

```

integer, intent(in) :: channel
type(vamp_grid), dimension(:), intent(in) :: grids

function vamp_multi_channel0 (func, phi, jacobian, x,
                           weights1)

    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:), intent(in) :: weights
    integer, intent(in) :: channel

subroutine vamp_check_jacobian (rng, n, channel, region,
                               delta, [ x_delta])

    type(tao_random_state), intent(inout) :: rng
    integer, intent(in) :: n
    integer, intent(in) :: channel
    real(kind=default), dimension(:,:,), intent(in) :: region
    real(kind=default), intent(out) :: delta
    real(kind=default), dimension(:), intent(out),
      optional :: x_delta

```

Verify that

$$g(\phi(x)) = \frac{1}{|\frac{\partial \phi}{\partial x}|(x)} \quad (4.5)$$

```

subroutine vamp_copy_grids (lhs, rhs)

    type(vamp_grids), intent(inout) :: lhs
    type(vamp_grids), intent(in) :: rhs

subroutine vamp_delete_grids (g)

    type(vamp_grids), intent(inout) :: g

subroutine vamp_create_grids (g, domain, num_calls, weights
                           [, maps] [, stratified])

```

```

type(vamp_grids), intent(inout) :: g
real, dimension(:, :, ), intent(in) :: domain
integer, intent(in) :: num_calls
real, dimension(:, ), intent(in) :: weights
real, dimension(:, :, :, ), intent(in) :: maps

subroutine vamp_create_empty_grids (g)

type(vamp_grids), intent(inout) :: g

subroutine vamp_discard_integrals (g [, num_calls]
[, stratified])

type(vamp_grids), intent(inout) :: g
integer, intent(in) :: num_calls

subroutine vamp_refine_weights (g [, power)

type(vamp_grids), intent(inout) :: g
real, intent(in) :: power

subroutine vamp_update_weights (g, weights [, num_calls]
[, stratified])

type(vamp_grids), intent(inout) :: g
real, dimension(:, ), intent(in) :: weights
integer, intent(in) :: num_calls

subroutine vamp_reshape_grids (g, num_calls [, stratified])

type(vamp_grids), intent(inout) :: g
integer, intent(in) :: num_calls

subroutine vamp_reduce_channels (g, [,...])

type(vamp_grid), intent(inout) :: g

subroutine vamp_sample_grids (g, func, iterations [, integral]
[, std_dev] [, accuracy] [, covariance] [, variance])

```

```

type(vamp_grids), intent(inout) :: g
func
integer, intent(in) :: iterations

function vamp_sum_channels (x, weights, func)

real, dimension(:), intent(in) :: x
real, dimension(:), intent(in) :: weights
func

```

4.2.6 Event Generation

```

subroutine vamp_next_event (g, [ , ...])
subroutine vamp_warmup_grid (g, [ , ...])

type(vamp_grid), intent(inout) :: g
func
integer, intent(in) :: iterations

subroutine vamp_warmup_grids (g, [ , ...])

type(vamp_grids), intent(inout) :: g
func
integer, intent(in) :: iterations

```

4.2.7 Parallelization

```

subroutine vamp_fork_grid (g, [ , ...])
type(vamp_grid), intent(inout) :: g

subroutine vamp_join_grid (g, [ , ...])
type(vamp_grid), intent(inout) :: g

subroutine vamp_fork_grid_joints (g, [ , ...])

```

```

type(vamp_grid), intent(inout) :: g

subroutine vamp_sample_grid_parallel (g, [,...])
    type(vamp_grid), intent(inout) :: g

subroutine vamp_distribute_work (g, [,...])
    type(vamp_grid), intent(inout) :: g

```

4.2.8 Diagnostics

```

subroutine vamp_create_history (g, [,...])
    type(vamp_grid), intent(inout) :: g

subroutine vamp_copy_history (g, [,...])
    type(vamp_grid), intent(inout) :: g

subroutine vamp_delete_history (g, [,...])
    type(vamp_grid), intent(inout) :: g

subroutine vamp_terminate_history (g, [,...])
    type(vamp_grid), intent(inout) :: g

subroutine vamp_get_history (g, [,...])
    type(vamp_grid), intent(inout) :: g

subroutine vamp_get_history_single (g, [,...])
    type(vamp_grid), intent(inout) :: g

subroutine vamp_print_history (g, [,...])
    type(vamp_grid), intent(inout) :: g

```

 Discuss why the value of the integral in each channel differs.

4.2.9 Other Procedures

```
subroutine vamp_rigid_divisions (g, [,...])  
    type(vamp_grid), intent(inout) :: g  
  
function vamp_get_covariance (g, [,...])  
    type(vamp_grid), intent(inout) :: g  
  
subroutine vamp_nullify_covariance (g, [,...])  
    type(vamp_grid), intent(inout) :: g  
  
function vamp_get_variance (g, [,...])  
    type(vamp_grid), intent(inout) :: g  
  
subroutine vamp_nullify_variance (g, [,...])  
    type(vamp_grid), intent(inout) :: g
```

4.2.10 (Currently) Undocumented Procedures

```
subroutine (...,[,...])  
function (...,[,...])
```

—5—

IMPLEMENTATION

5.1 The Abstract Datatype *division*

```
37a  <divisions.f90 37a>≡
      ! divisions.f90 --
      <Copyleft notice 1>
      module divisions
        use kinds
        use exceptions
        use vamp_stat
        use utils
        use iso_fortran_env
        implicit none
        private
        <Declaration of divisions procedures 38a>
        <Interfaces of divisions procedures 61b>
        <Variables in divisions 46a>
        <Declaration of divisions types 37b>
        <Constants in divisions 65a>
        character(len=*), public, parameter :: DIVISIONS_RCS_ID = &
          "$Id: divisions.nw 314 2010-04-17 20:32:33Z ohl $"
        contains
        <Implementation of divisions procedures 38b>
      end module divisions
```

 vamp_apply_equivalences from vamp accesses %variance ...

```
37b  <Declaration of divisions types 37b>≡
      type, public :: division_t
      !   private
      !!! Avoiding a g95 bug
```

```

    real(kind=default), dimension(:), pointer :: x => null ()
    real(kind=default), dimension(:), pointer :: integral => null ()
    real(kind=default), dimension(:), pointer &
                                :: variance => null ()
!
!       public :: variance => null ()
! real(kind=default), dimension(:), pointer :: efficiency => null ()
    real(kind=default) :: x_min, x_max
    real(kind=default) :: x_min_true, x_max_true
    real(kind=default) :: dx, dxg
    integer :: ng = 0
    logical :: stratified = .true.
end type division_t

```

5.1.1 Creation, Manipulation & Injection

38a *(Declaration of divisions procedures 38a)*≡

```

public :: create_division, create_empty_division
public :: copy_division, delete_division
public :: set_rigid_division, reshape_division

```

38b *(Implementation of divisions procedures 38b)*≡

```

elemental subroutine create_division &
    (d, x_min, x_max, x_min_true, x_max_true)
    type(division_t), intent(out) :: d
    real(kind=default), intent(in) :: x_min, x_max
    real(kind=default), intent(in), optional :: x_min_true, x_max_true
    allocate (d%x(0:1), d%integral(1), d%variance(1))
!
! allocate (d%efficiency(1))
    d%x(0) = 0.0
    d%x(1) = 1.0
    d%x_min = x_min
    d%x_max = x_max
    d%dx = d%x_max - d%x_min
    d%stratified = .false.
    d%ng = 1
    d%dxg = 1.0 / d%ng
    if (present (x_min_true)) then
        d%x_min_true = x_min_true
    else
        d%x_min_true = x_min
    end if
    if (present (x_max_true)) then
        d%x_max_true = x_max_true
    end if

```

```

    else
        d%x_max_true = x_max
    end if
end subroutine create_division

```

39a *(Implementation of divisions procedures 38b)* +≡

```

elemental subroutine create_empty_division (d)
    type(division_t), intent(out) :: d
    nullify (d%x, d%integral, d%variance)
! nullify (d%efficiency)
end subroutine create_empty_division

```

39b *(Implementation of divisions procedures 38b)* +≡

```

elemental subroutine set_rigid_division (d, ng)
    type(division_t), intent(inout) :: d
    integer, intent(in) :: ng
    d%stratified = ng > 1
    d%ng = ng
    d%dxg = real (ubound (d%x, dim=1), kind=default) / d%ng
end subroutine set_rigid_division

```

$$dxg = \frac{n_{\text{div}}}{n_g} \quad (5.1)$$

such that $0 < \text{cell} \cdot dxg < n_{\text{div}}$

39c *(Implementation of divisions procedures 38b)* +≡

```

elemental subroutine reshape_division (d, max_num_div, ng, use_variance)
    type(division_t), intent(inout) :: d
    integer, intent(in) :: max_num_div
    integer, intent(in), optional :: ng
    logical, intent(in), optional :: use_variance
    real(kind=default), dimension(:), allocatable :: old_x, m
    integer :: num_div, equ_per_adap
    if (present (ng)) then
        if (max_num_div > 1) then
            d%stratified = ng > 1
        else
            d%stratified = .false.
        end if
    else
        d%stratified = .false.
    end if
    if (d%stratified) then

```

```

d%ng = ng
    ⟨Initialize stratified sampling 42⟩
else
    num_div = max_num_div
    d%ng = 1
end if
d%dxg = real (num_div, kind=default) / d%ng
allocate (old_x(0:ubound(d%x,dim=1)), m(ubound(d%x,dim=1)))
old_x = d%x
    ⟨Set m to (1,1,...) or to rebinning weights from d%variance 40a⟩
    ⟨Resize arrays, iff necessary 40b⟩
d%x = rebin (m, old_x, num_div)
deallocate (old_x, m)
end subroutine reshape_division

```

40a ⟨Set m to (1,1,...) or to rebinning weights from d%variance 40a⟩≡

```

if (present (use_variance)) then
    if (use_variance) then
        m = rebinning_weights (d%variance)
    else
        m = 1.0
    end if
else
    m = 1.0
end if

```

40b ⟨Resize arrays, iff necessary 40b⟩≡

```

if (ubound (d%x, dim=1) /= num_div) then
    deallocate (d%x, d%integral, d%variance)
! deallocate (d%efficiency)
    allocate (d%x(0:num_div), d%integral(num_div), d%variance(num_div))
! allocate (d%efficiency(num_div))
end if

```

Genuinely stratified sampling will superimpose an equidistant grid on the adaptive grid, as shown in figure 5.2. Obviously, this is only possible when the number of cells of the stratification grid is large enough, specifically when $n_g \geq n_{\text{div}}^{\min} = n_{\text{div}}^{\max}/2 = 25$. This condition can be met by a high number of sampling points or by a low dimensionality of the integration region (cf. table 5.1).

For a low number of sampling points and high dimensions, genuinely stratified sampling is impossible, because we would have to reduce the number n_{div} of adaptive divisions too far. Instead, we keep **stratified** false which will tell the integration routine not to concentrate the grid in the regions where




Figure 5.1: `vegas` grid structure for non-stratified sampling. N.B.: the grid and the weight functions $p_{1,2}$ are only in qualitative agreement.




Figure 5.2: `vegas` grid structure for genuinely stratified sampling, which is used in low dimensions. N.B.: the grid and the weight functions $p_{1,2}$ are only in qualitative agreement.

n_{dim}	$N_{\text{calls}}^{\max}(n_g = 25)$
2	$1 \cdot 10^3$
3	$3 \cdot 10^4$
4	$8 \cdot 10^5$
5	$2 \cdot 10^7$
6	$5 \cdot 10^8$

Table 5.1: To stratify or not to stratify.

the contribution to the error is largest, but to use importance sampling, i. e. concentrating the grid in the regions where the contribution to the value is largest.

In this case, the rigid grid is much coarser than the adaptive grid and furthermore, the boundaries of the cells overlap in general. The interplay of the two grids during the sampling process is shown in figure 5.3.

First we determine the (integer) number k of equidistant divisions of an adaptive cell for at most n_{div}^{\max} divisions of the adaptive grid

$$k = \left\lfloor \frac{n_g}{n_{\text{div}}^{\max}} \right\rfloor + 1 \quad (5.2a)$$

and the corresponding number n_{div} of adaptive divisions

$$n_{\text{div}} = \left\lfloor \frac{n_g}{k} \right\rfloor \quad (5.2b)$$

Finally, adjust n_g to an exact multiple of n_{div}

$$n_g = k \cdot n_{\text{div}} \quad (5.2c)$$

```
42  <Initialize stratified sampling 42>≡
    if (d%ng >= max_num_div / 2) then
        d%stratified = .true.
        equ_per_adap = d%ng / max_num_div + 1
        num_div = d%ng / equ_per_adap
        if (num_div < 2) then
            d%stratified = .false.
            num_div = 2
            d%ng = 1
        else if (mod (num_div,2) == 1) then
            num_div = num_div - 1
            d%ng = equ_per_adap * num_div
        else
```




Figure 5.3: One-dimensional illustration of the `vegas` grid structure for pseudo stratified sampling, which is used in high dimensions.

```

d%ng = equ_per_adap * num_div
end if
else
  d%stratified = .false.
  num_div = max_num_div
  d%ng = 1
end if

```

Figure 5.3 on page 43 is a one-dimensional illustration of the sampling algorithm. In each cell of the rigid equidistant grid, two random points are selected (or N_{calls} in the not stratified case). For each point, the corresponding cell and relative coordinate in the adaptive grid is found, *as if the adaptive grid was equidistant* (upper arrow). Then this point is mapped according to the adapted grid (lower arrow) and the proper Jacobians are applied to the weight.

$$\prod_{j=1}^n (x_i^j - x_{i-1}^j) \cdot N^n = \text{Vol}(\text{cell}') \cdot \frac{1}{\text{Vol}(\text{cell})} = \frac{1}{p(x_i^j)} \quad (5.3)$$

43a *⟨Declaration of divisions procedures 38a⟩+≡*
`public :: inject_division, inject_division_short`

43b *⟨Implementation of divisions procedures 38b⟩+≡*
`elemental subroutine inject_division (d, r, cell, x, x_mid, idx, wgt)
 type(division_t), intent(in) :: d
 real(kind=default), intent(in) :: r
 integer, intent(in) :: cell
 real(kind=default), intent(out) :: x, x_mid
 integer, intent(out) :: idx
 real(kind=default), intent(out) :: wgt
 real(kind=default) :: delta_x, xi
 integer :: i
 xi = (cell - r) * d%dxg + 1.0`

```

<Set i, delta_x, x, and wgt from xi 44a>
idx = i
x_mid = d%x_min + 0.5 * (d%x(i-1) + d%x(i)) * d%dx
end subroutine inject_division

44a <Set i, delta_x, x, and wgt from xi 44a>≡
      i = max (min (int (xi), ubound (d%x, dim=1)), 1)
      delta_x = d%x(i) - d%x(i-1)
      x = d%x_min + (d%x(i-1) + (xi - i) * delta_x) * d%dx
      wgt = delta_x * ubound (d%x, dim=1)

44b <Implementation of divisions procedures 38b>+≡
      elemental subroutine inject_division_short (d, r, x, idx, wgt)
          type(division_t), intent(in) :: d
          real(kind=default), intent(in) :: r
          integer, intent(out) :: idx
          real(kind=default), intent(out) :: x, wgt
          real(kind=default) :: delta_x, xi
          integer :: i
          xi = r * ubound (d%x, dim=1) + 1.0
          <Set i, delta_x, x, and wgt from xi 44a>
          idx = i
      end subroutine inject_division_short

```

5.1.2 Grid Refinement

```

44c <Declaration of divisions procedures 38a>+≡
      public :: record_integral, record_variance, clear_integral_and_variance
      ! public :: record_efficiency

44d <Implementation of divisions procedures 38b>+≡
      elemental subroutine record_integral (d, i, f)
          type(division_t), intent(inout) :: d
          integer, intent(in) :: i
          real(kind=default), intent(in) :: f
          d%integral(i) = d%integral(i) + f
          if (.not. d%stratified) then
              d%variance(i) = d%variance(i) + f*f
          end if
      end subroutine record_integral

```

45a *<Implementation of divisions procedures 38b>+≡*

```
elemental subroutine record_variance (d, i, var_f)
    type(division_t), intent(inout) :: d
    integer, intent(in) :: i
    real(kind=default), intent(in) :: var_f
    if (d%stratified) then
        d%variance(i) = d%variance(i) + var_f
    end if
end subroutine record_variance
```

45b *<Implementation of divisions procedures (removed from WHIZARD) 45b>≡*

```
elemental subroutine record_efficiency (d, i, eff)
    type(division_t), intent(inout) :: d
    integer, intent(in) :: i
    real(kind=default), intent(in) :: eff
    ! d%efficiency(i) = d%efficiency(i) + eff
end subroutine record_efficiency
```

45c *<Implementation of divisions procedures 38b>+≡*

```
elemental subroutine clear_integral_and_variance (d)
    type(division_t), intent(inout) :: d
    d%integral = 0.0
    d%variance = 0.0
    ! d%efficiency = 0.0
end subroutine clear_integral_and_variance
```

45d *<Declaration of divisions procedures 38a>+≡*

```
public :: refine_division
```

45e *<Implementation of divisions procedures 38b>+≡*

```
elemental subroutine refine_division (d)
    type(division_t), intent(inout) :: d
    character(len=*), parameter :: FN = "refine_division"
    d%x = rebin (rebinning_weights (d%variance), d%x, size (d%variance))
end subroutine refine_division
```

Smooth the $d_i = \bar{f}_i \Delta x_i$

$$\begin{aligned}
d_1 &\rightarrow \frac{1}{2}(d_1 + d_2) \\
d_2 &\rightarrow \frac{1}{3}(d_1 + d_2 + d_3) \\
&\dots \\
d_{n-1} &\rightarrow \frac{1}{3}(d_{n-2} + d_{n-1} + d_n) \\
d_n &\rightarrow \frac{1}{2}(d_{n-1} + d_n)
\end{aligned} \tag{5.4}$$

As long as the initial `num_div` ≥ 6 , we know that `num_div` ≥ 3 .

46a *(Variables in divisions 46a)* \equiv
`integer, private, parameter :: MIN_NUM_DIV = 3`

Here the Fortran90 array notation really shines, but we have to handle the cases `nd` ≤ 2 specially, because the `quadrupole` option can lead to small `nd`s. The equivalent Fortran77 code [2] is orders of magnitude less obvious¹. Also protect against vanishing d_i that will blow up the logarithm.

$$m_i = \left(\frac{\sum_j \bar{f}_j \Delta x_j}{\ln \left(\frac{\sum_j \bar{f}_j \Delta x_j}{\sum_j \bar{f}_j \Delta x_j} \right)} - 1 \right)^\alpha \tag{5.5}$$

46b *(Implementation of divisions procedures 38b)* \equiv
`pure function rebinning_weights (d) result (m)`
`real(kind=default), dimension(:), intent(in) :: d`
`real(kind=default), dimension(size(d)) :: m`
`real(kind=default), dimension(size(d)) :: smooth_d`
`real(kind=default), parameter :: ALPHA = 1.5`
`integer :: nd`
(Bail out if any (d == NaN) 47b)
`nd = size (d)`
`if (nd > 2) then`
`smooth_d(1) = (d(1) + d(2)) / 2.0`
`smooth_d(2:nd-1) = (d(1:nd-2) + d(2:nd-1) + d(3:nd)) / 3.0`
`smooth_d(nd) = (d(nd-1) + d(nd)) / 2.0`
`else`
`smooth_d = d`
`end if`
`if (all (smooth_d < tiny (1.0_default))) then`

¹Some old timers call this a feature, however.

```

    m = 1.0_default
else
    smooth_d = smooth_d / sum (smooth_d)
    where (smooth_d < tiny (1.0_default))
        smooth_d = tiny (1.0_default)
    end where
    where (smooth_d /= 1._default)
        m = ((smooth_d - 1.0) / (log (smooth_d)))**ALPHA
    elsewhere
        m = 1.0_default
    endwhere
end if
end function rebinning_weights

```

47a ⟨Declaration of divisions procedures 38a⟩+≡
private :: rebinning_weights

 The NaN test is probably not portable:

47b ⟨Bail out if any (d == NaN) 47b⟩≡
if (any (d /= d)) then
 m = 1.0
 return
end if

Take a binning x and return a new binning with num_div bins with the m homogeneously distributed:

47c ⟨Implementation of divisions procedures 38b⟩+≡
pure function rebin (m, x, num_div) result (x_new)
 real(kind=default), dimension(:), intent(in) :: m
 real(kind=default), dimension(0:), intent(in) :: x
 integer, intent(in) :: num_div
 real(kind=default), dimension(0:num_div) :: x_new
 integer :: i, k
 real(kind=default) :: step, delta
 step = sum (m) / num_div
 k = 0
 delta = 0.0
 x_new(0) = x(0)
 do i = 1, num_div - 1
 ⟨Increment k until $\sum m_k \geq \Delta$ and keep the surplus in δ 48b⟩
 ⟨Interpolate the new x_i from x_k and δ 48c⟩
 end do
 x_new(num_div) = 1.0
end function rebin




Figure 5.4: Typical weights used in the rebinning algorithm.

48a *(Declaration of divisions procedures 38a)* +≡
private :: rebin

We increment k until another Δ (a. k. a. **step**) of the integral has been accumulated (cf. figure 5.4). The mismatch will be corrected below.

48b *(Increment k until $\sum m_k \geq \Delta$ and keep the surplus in δ 48b)* +≡
do

```
    if (step <= delta) then
        exit
    end if
    k = k + 1
    delta = delta + m(k)
end do
delta = delta - step
```

48c *(Interpolate the new x_i from x_k and δ 48c)* +≡
x_new(i) = x(k) - (x(k) - x(k-1)) * delta / m(k)

5.1.3 Probability Density

48d *(Declaration of divisions procedures 38a)* +≡
public :: probability

$$\xi = \frac{x - x_{\min}}{x_{\max} - x_{\min}} \in [0, 1] \quad (5.6)$$

and

$$\int_{x_{\min}}^{x_{\max}} dx p(x) = 1 \quad (5.7)$$

48e *(Implementation of divisions procedures 38b)* +≡
elemental function probability (d, x) result (p)
type(division_t), intent(in) :: d
real(kind=default), intent(in) :: x

```

real(kind=default) :: p
real(kind=default) :: xi
integer :: hi, mid, lo
xi = (x - d%x_min) / d%dx
if ((xi >= 0) .and. (xi <= 1)) then
    lo = lbound (d%x, dim=1)
    hi = ubound (d%x, dim=1)
    bracket: do
        if (lo >= hi - 1) then
            p = 1.0 / (ubound (d%x, dim=1) * d%dx * (d%x(hi) - d%x(hi-1)))
            return
        end if
        mid = (hi + lo) / 2
        if (xi > d%x(mid)) then
            lo = mid
        else
            hi = mid
        end if
    end do bracket
else
    p = 0
end if
end function probability

```

5.1.4 Quadrupole

49a *(Declaration of divisions procedures 38a)* +≡

```
public :: quadrupole_division
```

49b *(Implementation of divisions procedures 38b)* +≡

```
elemental function quadrupole_division (d) result (q)
    type(division_t), intent(in) :: d
    real(kind=default) :: q
    !!!   q = value_spread_percent (rebinning_weights (d%variance))
    q = standard_deviation_percent (rebinning_weights (d%variance))
end function quadrupole_division
```

5.1.5 Forking and Joining

The goal is to split a division in such a way, that we can later sample the pieces separately and combine the results.

49c *(Declaration of divisions procedures 38a)* +≡

```
public :: fork_division, join_division, sum_division
```

 Caveat emptor: splitting divisions can lead to `num_div < 3` and the application *must not* try to refine such grids before merging them again!

50a *Implementation of divisions procedures 38b* +≡

```

pure subroutine fork_division (d, ds, sum_calls, num_calls, exc)
    type/division_t/, intent(in) :: d
    type/division_t/, dimension(:), intent(inout) :: ds
    integer, intent(in) :: sum_calls
    integer, dimension(:), intent(inout) :: num_calls
    type(exception), intent(inout), optional :: exc
    character(len=*), parameter :: FN = "fork_division"
    integer, dimension(size(ds)) :: n0, n1
    integer, dimension(0:size(ds)) :: n, ds_ng
    integer :: i, j, num_div, num_forks, nx
    real(kind=default), dimension(:, allocatable :: d_x, d_integral, d_variance
! real(kind=default), dimension(:, allocatable :: d_efficiency
    num_div = ubound(d%x, dim=1)
    num_forks = size(ds)
    if (d%ng == 1) then
        <Fork an importance sampling division 51a>
    else if (num_div >= num_forks) then
        if (modulo(d%ng, num_div) == 0) then
            <Fork a pure stratified sampling division 52b>
        else
            <Fork a pseudo stratified sampling division 54a>
        end if
    else
        if (present(exc)) then
            call raise_exception (exc, EXC_FATAL, FN, "internal error")
        end if
        num_calls = 0
    end if
end subroutine fork_division

```

50b *Implementation of divisions procedures 38b* +≡

```

pure subroutine join_division (d, ds, exc)
    type/division_t/, intent(inout) :: d
    type/division_t/, dimension(:), intent(in) :: ds
    type(exception), intent(inout), optional :: exc
    character(len=*), parameter :: FN = "join_division"
    integer, dimension(size(ds)) :: n0, n1
    integer, dimension(0:size(ds)) :: n, ds_ng
    integer :: i, j, num_div, num_forks, nx
    real(kind=default), dimension(:, allocatable :: d_x, d_integral, d_variance

```

```

! real(kind=default), dimension(:), allocatable :: d_efficiency
num_div = ubound(d%x, dim=1)
num_forks = size(ds)
if (d%ng == 1) then
    <Join importance sampling divisions 51b>
else if (num_div >= num_forks) then
    if (modulo(d%ng, num_div) == 0) then
        <Join pure stratified sampling divisions 52c>
    else
        <Join pseudo stratified sampling divisions 54b>
    end if
else
    if (present(exc)) then
        call raise_exception(exc, EXC_FATAL, FN, "internal error")
    end if
end if
end subroutine join_division

```

Importance Sampling

Importance sampling ($d\%ng == 1$) is trivial, since we can just sample `size(ds)` copies of the same grid with (almost) the same number of points

51a \langle Fork an importance sampling division 51a $\rangle \equiv$

```

if (d%stratified) then
    call raise_exception(exc, EXC_FATAL, FN, &
                        "ng == 1 incompatible w/ stratification")
else
    call copy_division(ds, d)
    num_calls(2:) = ceiling(real(sum_calls) / num_forks)
    num_calls(1) = sum_calls - sum(num_calls(2:))
end if

```

and sum up the results in the end:

51b \langle Join importance sampling divisions 51b $\rangle \equiv$

```

call sum_division(d, ds)

```

Note, however, that this is only legitimate as long as $d\%ng == 1$ implies `d%stratified == .false.`, because otherwise the sampling code would be incorrect (cf. `var_f` on page 89).

Stratified Sampling

For stratified sampling, we have to work a little harder, because there are just two points per cell and we have to slice along the lines of the stratification

grid. Actually, we are slicing along the adaptive grid, since it has a reasonable size. Slicing along the stratification grid could be done using the method below. However, in this case *very* large adaptive grids would be shipped from one process to the other and the communication costs will outweigh the gains from parallel processing.

```

52a <Setup to fork a pure stratified sampling division 52a>≡
      n = (num_div * (/ (j, j=0,num_forks) /)) / num_forks
      n0(1:num_forks) = n(0:num_forks-1)
      n1(1:num_forks) = n(1:num_forks)

52b <Fork a pure stratified sampling division 52b>≡
      <Setup to fork a pure stratified sampling division 52a>
      do i = 1, num_forks
          call copy_array_pointer (ds(i)%x, d%x(n0(i):n1(i)), lb = 0)
          call copy_array_pointer (ds(i)%integral, d%integral(n0(i)+1:n1(i)))
          call copy_array_pointer (ds(i)%variance, d%variance(n0(i)+1:n1(i)))
!       call copy_array_pointer (ds(i)%efficiency, d%efficiency(n0(i)+1:n1(i)))
          ds(i)%x = (ds(i)%x - ds(i)%x(0)) / (d%x(n1(i)) - d%x(n0(i)))
      end do
      ds%x_min = d%x_min + d%dx * d%x(n0)
      ds%x_max = d%x_min + d%dx * d%x(n1)
      ds%dx = ds%x_max - ds%x_min
      ds%x_min_true = d%x_min_true
      ds%x_max_true = d%x_max_true
      ds%stratified = d%stratified
      ds%ng = (d%ng * (n1 - n0)) / num_div
      num_calls = sum_calls ! this is a misnomer, it remains “calls per cell” here
      ds%dxg = real (n1 - n0, kind=default) / ds%ng

Joining is the exact inverse, but we’re only interested in d%integral and
d%variance for the grid refinement:

52c <Join pure stratified sampling divisions 52c>≡
      <Setup to fork a pure stratified sampling division 52a>
      do i = 1, num_forks
          d%integral(n0(i)+1:n1(i)) = ds(i)%integral
          d%variance(n0(i)+1:n1(i)) = ds(i)%variance
!       d%efficiency(n0(i)+1:n1(i)) = ds(i)%efficiency
      end do

```




Figure 5.5: Forking one dimension d of a grid into three parts $ds(1)$, $ds(2)$, and $ds(3)$. The picture illustrates the most complex case of pseudo stratified sampling (cf. fig. 5.3).

Pseudo Stratified Sampling

The coarsest grid covering the division of n_g bins into n_f forks has $n_g / \gcd(n_f, n_g) = \text{lcm}(n_f, n_g) / n_f$ bins per fork. Therefore, we need

$$\text{lcm} \left(\frac{\text{lcm}(n_f, n_g)}{n_f}, n_x \right) \quad (5.8)$$

divisions of the adaptive grid (if n_x is the number of bins in the original adaptive grid).

Life would be much easier, if we knew that n_f divides n_g . However, this is hard to maintain in real life applications. We can try to achieve this if possible, but the algorithms must be prepared to handle the general case.

53 *{Setup to fork a pseudo stratified sampling division 53}*

```

nx = lcm (d%ng / gcd (num_forks, d%ng), num_div)
ds_ng = (d%ng * (/ (j, j=0,num_forks) /)) / num_forks
n = (nx * ds_ng) / d%ng
n0(1:num_forks) = n(0:num_forks-1)
n1(1:num_forks) = n(1:num_forks)

```

54a *(Fork a pseudo stratified sampling division 54a)≡*
(Setup to fork a pseudo stratified sampling division 53)
`allocate (d_x(0:nx), d_integral(nx), d_variance(nx))
! allocate (d_efficiency(nx))
call subdivide (d_x, d%x)
call distribute (d_integral, d%integral)
call distribute (d_variance, d%variance)
! call distribute (d_efficiency, d%efficiency)
do i = 1, num_forks
call copy_array_pointer (ds(i)%x, d_x(n0(i):n1(i)), lb = 0)
call copy_array_pointer (ds(i)%integral, d_integral(n0(i)+1:n1(i)))
call copy_array_pointer (ds(i)%variance, d_variance(n0(i)+1:n1(i)))
! call copy_array_pointer (ds(i)%efficiency, d_efficiency(n0(i)+1:n1(i)))
ds(i)%x = (ds(i)%x - ds(i)%x(0)) / (d_x(n1(i)) - d_x(n0(i)))
end do
ds%x_min = d%x_min + d%dx * d_x(n0)
ds%x_max = d%x_min + d%dx * d_x(n1)
ds%dx = ds%x_max - ds%x_min
ds%x_min_true = d%x_min_true
ds%x_max_true = d%x_max_true
ds%stratified = d%stratified
ds%ng = ds_ng(1:num_forks) - ds_ng(0:num_forks-1)
num_calls = sum_calls ! this is a misnomer, it remains “calls per cell” here
ds%dxg = real (n1 - n0, kind=default) / ds%ng
deallocate (d_x, d_integral, d_variance)
! deallocate (d_efficiency)`

54b *(Join pseudo stratified sampling divisions 54b)≡*
(Setup to fork a pseudo stratified sampling division 53)
`allocate (d_x(0:nx), d_integral(nx), d_variance(nx))
! allocate (d_efficiency(nx))
do i = 1, num_forks
d_integral(n0(i)+1:n1(i)) = ds(i)%integral
d_variance(n0(i)+1:n1(i)) = ds(i)%variance
! d_efficiency(n0(i)+1:n1(i)) = ds(i)%efficiency
end do
call collect (d%integral, d_integral)
call collect (d%variance, d_variance)
! call collect (d%efficiency, d_efficiency)
deallocate (d_x, d_integral, d_variance)
! deallocate (d_efficiency)`

54c *(Declaration of divisions procedures 38a)++≡*
`private :: subdivide
private :: distribute`

```

private :: collect

55a <Implementation of divisions procedures 38b>+≡
pure subroutine subdivide (x, x0)
    real(kind=default), dimension(0::), intent(inout) :: x
    real(kind=default), dimension(0::), intent(in) :: x0
    integer :: i, n, n0
    n0 = ubound (x0, dim=1)
    n = ubound (x, dim=1) / n0
    x(0) = x0(0)
    do i = 1, n
        x(i::n) = x0(0:n0-1) * real (n - i) / n + x0(1:n0) * real (i) / n
    end do
end subroutine subdivide

55b <Implementation of divisions procedures 38b>+≡
pure subroutine distribute (x, x0)
    real(kind=default), dimension(:, ), intent(inout) :: x
    real(kind=default), dimension(:, ), intent(in) :: x0
    integer :: i, n
    n = ubound (x, dim=1) / ubound (x0, dim=1)
    do i = 1, n
        x(i::n) = x0 / n
    end do
end subroutine distribute

55c <Implementation of divisions procedures 38b>+≡
pure subroutine collect (x0, x)
    real(kind=default), dimension(:, ), intent(inout) :: x0
    real(kind=default), dimension(:, ), intent(in) :: x
    integer :: i, n, n0
    n0 = ubound (x0, dim=1)
    n = ubound (x, dim=1) / n0
    do i = 1, n0
        x0(i) = sum (x((i-1)*n+1:i*n))
    end do
end subroutine collect

```

Trivia

```

55d <Implementation of divisions procedures 38b>+≡
pure subroutine sum_division (d, ds)
    type/division_t/, intent(inout) :: d
    type/division_t/, dimension(:, ), intent(in) :: ds
    integer :: i

```

```

d%integral = 0.0
d%variance = 0.0
! d%efficiency = 0.0
do i = 1, size (ds)
    d%integral = d%integral + ds(i)%integral
    d%variance = d%variance + ds(i)%variance
!    d%efficiency = d%efficiency + ds(i)%efficiency
end do
end subroutine sum_division

56a <Declaration of divisions procedures 38a>+≡
public :: debug_division
public :: dump_division

56b <Implementation of divisions procedures 38b>+≡
subroutine debug_division (d, prefix)
type(division_t), intent(in) :: d
character(len=*), intent(in) :: prefix
print "(1x,a,2(a,1x,i3,1x,f10.7))", prefix, ": d%x: ", &
lbound(d%x,dim=1), d%x(lbound(d%x,dim=1)), &
" ... ", &
ubound(d%x,dim=1), d%x(ubound(d%x,dim=1))
print "(1x,a,2(a,1x,i3,1x,f10.7))", prefix, ": d%i: ", &
lbound(d%integral,dim=1), d%integral(lbound(d%integral,dim=1)), &
" ... ", &
ubound(d%integral,dim=1), d%integral(ubound(d%integral,dim=1))
print "(1x,a,2(a,1x,i3,1x,f10.7))", prefix, ": d%v: ", &
lbound(d%variance,dim=1), d%variance(lbound(d%variance,dim=1)), &
" ... ", &
ubound(d%variance,dim=1), d%variance(ubound(d%variance,dim=1))
! print "(1x,a,2(a,1x,i3,1x,f10.7))", prefix, ": d%e: ", &
!     lbound(d%efficiency,dim=1), d%efficiency(lbound(d%efficiency,dim=1)), &
!     " ... ", &
!     ubound(d%efficiency,dim=1), d%efficiency(ubound(d%efficiency,dim=1))
end subroutine debug_division

56c <Implementation of divisions procedures 38b>+≡
subroutine dump_division (d, prefix)
type(division_t), intent(in) :: d
character(len=*), intent(in) :: prefix
! print "(2(1x,a),100(1x,f10.7))", prefix, ":x: ", d%x
print "(2(1x,a),100(1x,f10.7))", prefix, ":x: ", d%x(1:)
print "(2(1x,a),100(1x,e10.3))", prefix, ":i: ", d%integral
print "(2(1x,a),100(1x,e10.3))", prefix, ":v: ", d%variance
! print "(2(1x,a),100(1x,e10.3))", prefix, ":e: ", d%efficiency

```

```
end subroutine dump_division
```

5.1.6 Inquiry

Trivial, but necessary for making divisions an abstract data type:

- 57a *<Declaration of divisions procedures 38a>+≡*
 public :: inside_division, stratified_division
 public :: volume_division, rigid_division, adaptive_division
- 57b *<Implementation of divisions procedures 38b>+≡*
 elemental function inside_division (d, x) result (theta)
 type(division_t), intent(in) :: d
 real(kind=default), intent(in) :: x
 logical :: theta
 theta = (x >= d%x_min_true) .and. (x <= d%x_max_true)
 end function inside_division
- 57c *<Implementation of divisions procedures 38b>+≡*
 elemental function stratified_division (d) result (yorn)
 type(division_t), intent(in) :: d
 logical :: yorn
 yorn = d%stratified
 end function stratified_division
- 57d *<Implementation of divisions procedures 38b>+≡*
 elemental function volume_division (d) result (vol)
 type(division_t), intent(in) :: d
 real(kind=default) :: vol
 vol = d%dx
 end function volume_division
- 57e *<Implementation of divisions procedures 38b>+≡*
 elemental function rigid_division (d) result (n)
 type(division_t), intent(in) :: d
 integer :: n
 n = d%ng
 end function rigid_division
- 57f *<Implementation of divisions procedures 38b>+≡*
 elemental function adaptive_division (d) result (n)
 type(division_t), intent(in) :: d
 integer :: n
 n = ubound (d%x, dim=1)
 end function adaptive_division

5.1.7 Diagnostics

- 58a *<Declaration of divisions types 37b>+≡*
- ```
type, public :: div_history
 private
 logical :: stratified
 integer :: ng, num_div
 real(kind=default) :: x_min, x_max, x_min_true, x_max_true
 real(kind=default) :: &
 spread_f_p, stddev_f_p, spread_p, stddev_p, spread_m, stddev_m
end type div_history
```
- 58b *<Declaration of divisions procedures 38a>+≡*
- ```
public :: copy_history, summarize_division
```
- 58c *<Implementation of divisions procedures 38b>+≡*
- ```
elemental function summarize_division (d) result (s)
 type/division_t, intent(in) :: d
 type/div_history) :: s
 real(kind=default), dimension(:), allocatable :: p, m
 allocate (p(ubound(d%x, dim=1)), m(ubound(d%x, dim=1)))
 p = probabilities (d%x)
 m = rebinning_weights (d%variance)
 s%ng = d%ng
 s%num_div = ubound (d%x, dim=1)
 s%stratified = d%stratified
 s%x_min = d%x_min
 s%x_max = d%x_max
 s%x_min_true = d%x_min_true
 s%x_max_true = d%x_max_true
 s%spread_f_p = value_spread_percent (d%integral)
 s%stddev_f_p = standard_deviation_percent (d%integral)
 s%spread_p = value_spread_percent (p)
 s%stddev_p = standard_deviation_percent (p)
 s%spread_m = value_spread_percent (m)
 s%stddev_m = standard_deviation_percent (m)
 deallocate (p, m)
end function summarize_division
```
- 58d *<Declaration of divisions procedures 38a>+≡*
- ```
private :: probabilities
```
- 58e *<Implementation of divisions procedures 38b>+≡*
- ```
pure function probabilities (x) result (p)
 real(kind=default), dimension(0:), intent(in) :: x
 real(kind=default), dimension(ubound(x, dim=1)) :: p
```

```

 integer :: num_div
 num_div = ubound (x, dim=1)
 p = 1.0 / (x(1:num_div) - x(0:num_div-1))
 p = p / sum(p)
end function probabilities

59a <Implementation of divisions procedures 38b>+≡
subroutine print_history (h, tag)
 type(div_history), dimension(:), intent(in) :: h
 character(len=*), intent(in), optional :: tag
 call write_history (output_unit, h, tag)
 flush (output_unit)
end subroutine print_history

59b <Implementation of divisions procedures 38b>+≡
subroutine write_history (u, h, tag)
 integer, intent(in) :: u
 type(div_history), dimension(:), intent(in) :: h
 character(len=*), intent(in), optional :: tag
 character(len=BUFFER_SIZE) :: pfx
 character(len=1) :: s
 integer :: i
 if (present (tag)) then
 pfx = tag
 else
 pfx = "[vamp]"
 end if
 if ((minval (h%x_min) == maxval (h%x_min)) &
 .and. (minval (h%x_max) == maxval (h%x_max))) then
 write (u, "(1X,A11,1X,2X,1X,2(E10.3,A4,E10.3,A7))") pfx, &
 h(1)%x_min, " <= ", h(1)%x_min_true, &
 " < x < ", h(1)%x_max_true, " <= ", h(1)%x_max
 else
 do i = 1, size (h)
 write (u, "(1X,A11,1X,I2,1X,2(E10.3,A4,E10.3,A7))") pfx, &
 i, h(i)%x_min, " <= ", h(i)%x_min_true, &
 " < x < ", h(i)%x_max_true, " <= ", h(i)%x_max
 end do
 end if
 write (u, "(1X,A11,1X,A2,2(1X,A3),A1,6(1X,A8))") pfx, &
 "it", "nd", "ng", "", &
 "spr(f/p)", "dev(f/p)", "spr(m)", "dev(m)", "spr(p)", "dev(p)"
iterations: do i = 1, size (h)
 if (h(i)%stratified) then
 s = "*"

```

```

 else
 s = ""
 end if
 write (u, "(1X,A11,1X,I2,2(1X,I3),A1,6(1X,F7.2,A1))") pfx, &
 i, h(i)%num_div, h(i)%ng, s, &
 h(i)%spread_f_p, "%", h(i)%stddev_f_p, "%", &
 h(i)%spread_m, "%", h(i)%stddev_m, "%", &
 h(i)%spread_p, "%", h(i)%stddev_p, "%"
 end do iterations
 flush (u)
 end subroutine write_history

60a <Variables in divisions 46a>+≡
 integer, private, parameter :: BUFFER_SIZE = 50

60b <Declaration of divisions procedures 38a>+≡
 public :: print_history, write_history

60c <Declaration of divisions procedures (removed from WHIZARD) 60c>≡
 public :: division_x, division_integral
 public :: division_variance, division_efficiency

60d <Implementation of divisions procedures (removed from WHIZARD) 45b>+≡
 pure subroutine division_x (x, d)
 real(kind=default), dimension(:), pointer :: x
 type(division_t), intent(in) :: d
 call copy_array_pointer (x, d%x, 0)
 end subroutine division_x

60e <Implementation of divisions procedures (removed from WHIZARD) 45b>+≡
 pure subroutine division_integral (integral, d)
 real(kind=default), dimension(:), pointer :: integral
 type(division_t), intent(in) :: d
 call copy_array_pointer (integral, d%integral)
 end subroutine division_integral

60f <Implementation of divisions procedures (removed from WHIZARD) 45b>+≡
 pure subroutine division_variance (variance, d)
 real(kind=default), dimension(:), pointer :: variance
 type(division_t), intent(in) :: d
 call copy_array_pointer (variance, d%variance, 0)
 end subroutine division_variance

60g <Implementation of divisions procedures (removed from WHIZARD) 45b>+≡
 pure subroutine division_efficiency (eff, d)
 real(kind=default), dimension(:), pointer :: eff
 type(division_t), intent(in) :: d

```

```

 call copy_array_pointer (eff, d%efficiency, 0)
end subroutine division_efficiency

```

### 5.1.8 I/O

61a <*Declaration of divisions procedures 38a*>+≡

```

public :: write_division
private :: write_division_unit, write_division_name
public :: read_division
private :: read_division_unit, read_division_name
public :: write_division_raw
private :: write_division_raw_unit, write_division_raw_name
public :: read_division_raw
private :: read_division_raw_unit, read_division_raw_name

```

61b <*Interfaces of divisions procedures 61b*>≡

```

interface write_division
 module procedure write_division_unit, write_division_name
end interface
interface read_division
 module procedure read_division_unit, read_division_name
end interface
interface write_division_raw
 module procedure write_division_raw_unit, write_division_raw_name
end interface
interface read_division_raw
 module procedure read_division_raw_unit, read_division_raw_name
end interface

```

It makes no sense to read or write d%integral, d%variance, and d%efficiency, because they are only used during sampling.

61c <*Implementation of divisions procedures 38b*>+≡

```

subroutine write_division_unit (d, unit, write_integrals)
 type(division_t), intent(in) :: d
 integer, intent(in) :: unit
 logical, intent(in), optional :: write_integrals
 logical :: write_integrals0
 integer :: i
 write_integrals0 = .false.
 if (present(write_integrals)) write_integrals0 = write_integrals
 write (unit = unit, fmt = descr_fmt) "begin type(division_t) :: d"
 write (unit = unit, fmt = integer_fmt) "ubound(d%x,1) = ", ubound (d%x, dim=1)
 write (unit = unit, fmt = integer_fmt) "d%ng = ", d%ng
 write (unit = unit, fmt = logical_fmt) "d%stratified = ", d%stratified

```

```

 write (unit = unit, fmt = double_fmt) "d%dx = ", d%dx
 write (unit = unit, fmt = double_fmt) "d%dxg = ", d%dxg
 write (unit = unit, fmt = double_fmt) "d%x_min = ", d%x_min
 write (unit = unit, fmt = double_fmt) "d%x_max = ", d%x_max
 write (unit = unit, fmt = double_fmt) "d%x_min_true = ", d%x_min_true
 write (unit = unit, fmt = double_fmt) "d%x_max_true = ", d%x_max_true
 write (unit = unit, fmt = descr_fmt) "begin d%x"
 do i = 0, ubound (d%x, dim=1)
 if (write_integrals0 .and. i /= 0) then
 write (unit = unit, fmt = double_array_fmt) &
 i, d%x(i), d%integral(i), d%variance(i)
 else
 write (unit = unit, fmt = double_array_fmt) i, d%x(i)
 end if
 end do
 write (unit = unit, fmt = descr_fmt) "end d%x"
 write (unit = unit, fmt = descr_fmt) "end type(division_t)"
end subroutine write_division_unit

```

62a ⟨Variables in divisions 46a⟩+≡

```

character(len=*), parameter, private :: &
 descr_fmt = "(1x,a)", &
 integer_fmt = "(1x,a15,1x,i15)", &
 logical_fmt = "(1x,a15,1x,l1)", &
 double_fmt = "(1x,a15,1x,e30.22)", &
 double_array_fmt = "(1x,i15,1x,3(e30.22))"
```

62b ⟨Implementation of divisions procedures 38b⟩+≡

```

subroutine read_division_unit (d, unit, read_integrals)
 type(division_t), intent(inout) :: d
 integer, intent(in) :: unit
 logical, intent(in), optional :: read_integrals
 logical :: read_integrals0
 integer :: i, idum, num_div
 character(len=80) :: chdum
 read_integrals0 = .false.
 if (present(read_integrals)) read_integrals0 = read_integrals
 read (unit = unit, fmt = descr_fmt) chdum
 read (unit = unit, fmt = integer_fmt) chdum, num_div
 ⟨Insure that ubound (d%x, dim=1) == num_div 63a⟩
 read (unit = unit, fmt = integer_fmt) chdum, d%ng
 read (unit = unit, fmt = logical_fmt) chdum, d%stratified
 read (unit = unit, fmt = double_fmt) chdum, d%dx
 read (unit = unit, fmt = double_fmt) chdum, d%dxg
 read (unit = unit, fmt = double_fmt) chdum, d%x_min
```

```

read (unit = unit, fmt = double_fmt) chdum, d%x_max
read (unit = unit, fmt = double_fmt) chdum, d%x_min_true
read (unit = unit, fmt = double_fmt) chdum, d%x_max_true
read (unit = unit, fmt = descr_fmt) chdum
do i = 0, ubound (d%x, dim=1)
 if (read_integrals0 .and. i /= 0) then
 read (unit = unit, fmt = double_array_fmt) &
 & idum, d%x(i), d%integral(i), d%variance(i)
 else
 read (unit = unit, fmt = double_array_fmt) idum, d%x(i)
 end if
end do
read (unit = unit, fmt = descr_fmt) chdum
read (unit = unit, fmt = descr_fmt) chdum
if (.not.read_integrals0) then
 d%integral = 0.0
 d%variance = 0.0
! d%efficiency = 0.0
end if
end subroutine read_division_unit

```

 What happened to d%efficiency?

- 63a *(Insure that ubound (d%x, dim=1) == num\_div 63a)≡*
- ```

if (associated (d%x)) then
    if (ubound (d%x, dim=1) /= num_div) then
        deallocate (d%x, d%integral, d%variance)
!    deallocate (d%efficiency)
        allocate (d%x(0:num_div), d%integral(num_div), d%variance(num_div))
!    allocate (d%efficiency(num_div))
    end if
else
    allocate (d%x(0:num_div), d%integral(num_div), d%variance(num_div))
!    allocate (d%efficiency(num_div))
end if

```
- 63b *(Implementation of divisions procedures 38b)≡*
- ```

subroutine write_division_name (d, name, write_integrals)
 type/division_t/, intent(in) :: d
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: write_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "write", status = "replace", file = name)

```

```

 call write_division_unit (d, unit, write_integrals)
 close (unit = unit)
end subroutine write_division_name

64a <Implementation of divisions procedures 38b>+≡
subroutine read_division_name (d, name, read_integrals)
 type(division_t), intent(inout) :: d
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: read_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "read", status = "old", file = name)
 call read_division_unit (d, unit, read_integrals)
 close (unit = unit)
end subroutine read_division_name

64b <Implementation of divisions procedures 38b>+≡
subroutine write_division_raw_unit (d, unit, write_integrals)
 type(division_t), intent(in) :: d
 integer, intent(in) :: unit
 logical, intent(in), optional :: write_integrals
 logical :: write_integrals0
 integer :: i
 write_integrals0 = .false.
 if (present(write_integrals)) write_integrals0 = write_integrals
 write (unit = unit) MAGIC_DIVISION_BEGIN
 write (unit = unit) ubound (d%x, dim=1)
 write (unit = unit) d%ng
 write (unit = unit) d%stratified
 write (unit = unit) d%dx
 write (unit = unit) d%dxg
 write (unit = unit) d%x_min
 write (unit = unit) d%x_max
 write (unit = unit) d%x_min_true
 write (unit = unit) d%x_max_true
 do i = 0, ubound (d%x, dim=1)
 if (write_integrals0 .and. i/=0) then
 write (unit = unit) d%x(i), d%integral(i), d%variance(i)
 else
 write (unit = unit) d%x(i)
 end if
 end do
 write (unit = unit) MAGIC_DIVISION_END
end subroutine write_division_raw_unit

```

```

65a <Constants in divisions 65a>≡
 integer, parameter, private :: MAGIC_DIVISION = 11111111
 integer, parameter, private :: MAGIC_DIVISION_BEGIN = MAGIC_DIVISION + 1
 integer, parameter, private :: MAGIC_DIVISION_END = MAGIC_DIVISION + 2

65b <Implementation of divisions procedures 38b>+≡
 subroutine read_division_raw_unit (d, unit, read_integrals)
 type(division_t), intent(inout) :: d
 integer, intent(in) :: unit
 logical, intent(in), optional :: read_integrals
 logical :: read_integrals0
 integer :: i, num_div, magic
 character(len=*), parameter :: FN = "read_division_raw_unit"
 read_integrals0 = .false.
 if (present(read_integrals)) read_integrals0 = read_integrals
 read (unit = unit) magic
 if (magic /= MAGIC_DIVISION_BEGIN) then
 print *, FN, " fatal: expecting magic ", MAGIC_DIVISION_BEGIN, &
 ", found ", magic
 stop
 end if
 read (unit = unit) num_div
 <Insure that ubound (d%x, dim=1) == num_div 63a>
 read (unit = unit) d%ng
 read (unit = unit) d%stratified
 read (unit = unit) d%dx
 read (unit = unit) d%dxg
 read (unit = unit) d%x_min
 read (unit = unit) d%x_max
 read (unit = unit) d%x_min_true
 read (unit = unit) d%x_max_true
 do i = 0, ubound (d%x, dim=1)
 if (read_integrals0 .and. i/=0) then
 read (unit = unit) d%x(i), d%integral(i), d%variance(i)
 else
 read (unit = unit) d%x(i)
 end if
 end do
 if (.not.read_integrals0) then
 d%integral = 0.0
 d%variance = 0.0
 ! d%efficiency = 0.0
 end if
 read (unit = unit) magic

```

```

if (magic /= MAGIC_DIVISION_END) then
 print *, FN, " fatal: expecting magic ", MAGIC_DIVISION_END, &
 ", found ", magic
 stop
end if
end subroutine read_division_raw_unit

66a <Implementation of divisions procedures 38b>+≡
subroutine write_division_raw_name (d, name, write_integrals)
 type(division_t), intent(in) :: d
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: write_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "write", status = "replace", &
 form = "unformatted", file = name)
 call write_division_unit (d, unit, write_integrals)
 close (unit = unit)
end subroutine write_division_raw_name

66b <Implementation of divisions procedures 38b>+≡
subroutine read_division_raw_name (d, name, read_integrals)
 type(division_t), intent(inout) :: d
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: read_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "read", status = "old", &
 form = "unformatted", file = name)
 call read_division_unit (d, unit, read_integrals)
 close (unit = unit)
end subroutine read_division_raw_name

```

### 5.1.9 Marshaling

Note that we can not use the `transfer` intrinsic function for marshalling types that contain pointers that substitute for allocatable array components. `transfer` will copy the pointers in this case and not where they point to!

```

66c <Declaration of divisions procedures 38a>+≡
 public :: marshal_division_size, marshal_division, unmarshal_division

66d <Implementation of divisions procedures 38b>+≡
 pure subroutine marshal_division (d, ibuf, dbuf)
 type(division_t), intent(in) :: d

```

```

integer, dimension(:), intent(inout) :: ibuf
real(kind=default), dimension(:), intent(inout) :: dbuf
integer :: num_div
num_div = ubound (d%x, dim=1)
ibuf(1) = d%ng
ibuf(2) = num_div
if (d%stratified) then
 ibuf(3) = 1
else
 ibuf(3) = 0
end if
dbuf(1) = d%x_min
dbuf(2) = d%x_max
dbuf(3) = d%x_min_true
dbuf(4) = d%x_max_true
dbuf(5) = d%dx
dbuf(6) = d%dxg
dbuf(7:7+num_div) = d%x
dbuf(8+ num_div:7+2*num_div) = d%integral
dbuf(8+2*num_div:7+3*num_div) = d%variance
! dbuf(8+3*num_div:7+4*num_div) = d%efficiency
end subroutine marshal_division

```

67a <Implementation of divisions procedures 38b>+≡

```

pure subroutine marshal_division_size (d, iwords, dwords)
 type/division_t/, intent(in) :: d
 integer, intent(out) :: iwords, dwords
 iwords = 3
 dwords = 7 + 3 * ubound (d%x, dim=1)
! dwords = 7 + 4 * ubound (d%x, dim=1)
end subroutine marshal_division_size

```

67b <Implementation of divisions procedures 38b>+≡

```

pure subroutine unmarshal_division (d, ibuf, dbuf)
 type/division_t/, intent(inout) :: d
 integer, dimension(:), intent(in) :: ibuf
 real(kind=default), dimension(:), intent(in) :: dbuf
 integer :: num_div
 d%ng = ibuf(1)
 num_div = ibuf(2)
 d%stratified = ibuf(3) /= 0
 d%x_min = dbuf(1)
 d%x_max = dbuf(2)
 d%x_min_true = dbuf(3)
 d%x_max_true = dbuf(4)

```

```

d%dx =dbuf(5)
d%dxg =dbuf(6)
<Insure that ubound (d%x, dim=1) == num_div 63a>
d%x =dbuf(7:7+num_div)
d%integral =dbuf(8+ num_div:7+2*num_div)
d%variance =dbuf(8+2*num_div:7+3*num_div)
! d%efficiency =dbuf(8+3*num_div:7+4*num_div)
end subroutine unmarshal_division

68a <Declaration of divisions procedures 38a>+≡
 public :: marshal_div_history_size, marshal_div_history, unmarshal_div_history

68b <Implementation of divisions procedures 38b>+≡
 pure subroutine marshal_div_history (h, ibuf, dbuf)
 type(div_history), intent(in) :: h
 integer, dimension(:), intent(inout) :: ibuf
 real(kind=default), dimension(:), intent(inout) :: dbuf
 ibuf(1) = h%ng
 ibuf(2) = h%num_div
 if (h%stratified) then
 ibuf(3) = 1
 else
 ibuf(3) = 0
 end if
 dbuf(1) = h%x_min
 dbuf(2) = h%x_max
 dbuf(3) = h%x_min_true
 dbuf(4) = h%x_max_true
 dbuf(5) = h%spread_f_p
 dbuf(6) = h%stddev_f_p
 dbuf(7) = h%spread_p
 dbuf(8) = h%stddev_p
 dbuf(9) = h%spread_m
 dbuf(10) = h%stddev_m
 end subroutine marshal_div_history

68c <Implementation of divisions procedures 38b>+≡
 pure subroutine marshal_div_history_size (h, iwords, dwords)
 type(div_history), intent(in) :: h
 integer, intent(out) :: iwords, dwords
 iwords = 3
 dwords = 10
 end subroutine marshal_div_history_size

68d <Implementation of divisions procedures 38b>+≡
 pure subroutine unmarshal_div_history (h, ibuf, dbuf)

```

```

type(div_history), intent(inout) :: h
integer, dimension(:), intent(in) :: ibuf
real(kind=default), dimension(:), intent(in) :: dbuf
h%ng = ibuf(1)
h%num_div = ibuf(2)
h%stratified = ibuf(3) /= 0
h%x_min = dbuf(1)
h%x_max = dbuf(2)
h%x_min_true = dbuf(3)
h%x_max_true = dbuf(4)
h%spread_f_p = dbuf(5)
h%stddev_f_p = dbuf(6)
h%spread_p = dbuf(7)
h%stddev_p = dbuf(8)
h%spread_m = dbuf(9)
h%stddev_m = dbuf(10)
end subroutine unmarshal_div_history

```

### 5.1.10 Boring Copying and Deleting of Objects

69 <Implementation of divisions procedures 38b>+≡

```

elemental subroutine copy_division (lhs, rhs)
 type/division_t/, intent(inout) :: lhs
 type/division_t/, intent(in) :: rhs
 if (associated (rhs%x)) then
 call copy_array_pointer (lhs%x, rhs%x, lb = 0)
 else if (associated (lhs%x)) then
 deallocate (lhs%x)
 end if
 if (associated (rhs%integral)) then
 call copy_array_pointer (lhs%integral, rhs%integral)
 else if (associated (lhs%integral)) then
 deallocate (lhs%integral)
 end if
 if (associated (rhs%variance)) then
 call copy_array_pointer (lhs%variance, rhs%variance)
 else if (associated (lhs%variance)) then
 deallocate (lhs%variance)
 end if
! if (associated (rhs%efficiency)) then
! call copy_array_pointer (lhs%efficiency, rhs%efficiency)
! else if (associated (lhs%efficiency)) then
! deallocate (lhs%efficiency)

```

```

! end if
lhs%dx = rhs%dx
lhs%dxg = rhs%dxg
lhs%x_min = rhs%x_min
lhs%x_max = rhs%x_max
lhs%x_min_true = rhs%x_min_true
lhs%x_max_true = rhs%x_max_true
lhs%ng = rhs%ng
lhs%stratified = rhs%stratified
end subroutine copy_division

```

70a <Implementation of divisions procedures 38b>+≡

```

elemental subroutine delete_division (d)
 type/division_t/, intent(inout) :: d
 if (associated (d%x)) then
 deallocate (d%x, d%integral, d%variance)
! deallocate (d%efficiency)
 end if
end subroutine delete_division

```

70b <Implementation of divisions procedures 38b>+≡

```

elemental subroutine copy_history (lhs, rhs)
 type/div_history/, intent(out) :: lhs
 type/div_history/, intent(in) :: rhs
 lhs%stratified = rhs%stratified
 lhs%ng = rhs%ng
 lhs%num_div = rhs%num_div
 lhs%x_min = rhs%x_min
 lhs%x_max = rhs%x_max
 lhs%x_min_true = rhs%x_min_true
 lhs%x_max_true = rhs%x_max_true
 lhs%spread_f_p = rhs%spread_f_p
 lhs%stddev_f_p = rhs%stddev_f_p
 lhs%spread_p = rhs%spread_p
 lhs%stddev_p = rhs%stddev_p
 lhs%spread_m = rhs%spread_m
 lhs%stddev_m = rhs%stddev_m
end subroutine copy_history

```

## 5.2 The Abstract Datatype *vamp\_grid*

70c <*vamp.f90* 70c>≡

```
! vamp.f90 --
⟨Copyleft notice 1⟩
```

 NAG f95 requires this split. Check with the Fortran community, if it is really necessary, or a bug! The problem is that this split forces us to expose the components of `vamp_grid`.

**NB:** with the introduction of `vamp_equivaleces`, this question has (probably) become academic.

71a ⟨vamp.f90 70c⟩+≡

```
module vamp_grid_type
 use kinds
 use divisions
 private
 ⟨Declaration of vamp_grid_type types 76b⟩
end module vamp_grid_type
```

 By WK for WHIZARD.

71b ⟨vamp.f90 70c⟩+≡

```
module vamp_equivaleces
 use kinds
 use divisions
 use vamp_grid_type !NODEP!
 implicit none
 private
 ⟨Declaration of vamp_equivaleces procedures 72d⟩
 ⟨Constants in vamp_equivaleces 72b⟩
 ⟨Declaration of vamp_equivaleces types 71c⟩
 character(len=*), public, parameter :: VAMP_EQUIVALECES_RCS_ID = &
 "$Id: vamp.nw 317 2010-04-18 00:31:03Z ohl $"
contains
 ⟨Implementation of vamp_equivaleces procedures 72c⟩
end module vamp_equivaleces
```

71c ⟨Declaration of vamp\_equivaleces types 71c⟩≡

```
type, public :: vamp_equivalece_t
 integer :: left, right
 integer, dimension(:), allocatable :: permutation
 integer, dimension(:), allocatable :: mode
end type vamp_equivalece_t
```

72a *(Declaration of vamp\_equivalences types 71c)* +≡  
 type, public :: vamp\_equivalences\_t  
     type(vamp\_equivivalence\_t), dimension(:), allocatable :: eq  
     integer :: n\_eq, n\_ch  
     integer, dimension(:), allocatable :: pointer  
     logical, dimension(:), allocatable :: independent  
     integer, dimension(:), allocatable :: equivalent\_to\_ch  
     integer, dimension(:), allocatable :: multiplicity  
     integer, dimension(:), allocatable :: symmetry  
     logical, dimension(:, :), allocatable :: div\_is\_invariant  
 end type vamp\_equivalences\_t

72b *(Constants in vamp\_equivalences 72b)* ≡  
 integer, parameter, public :: &  
     VEQ\_IDENTITY = 0, VEQ\_INVERT = 1, VEQ\_SYMMETRIC = 2, VEQ\_INVARIANT = 3

72c *(Implementation of vamp\_equivalences procedures 72c)* ≡  
 subroutine vamp\_equivivalence\_init (eq, n\_dim)  
     type(vamp\_equivivalence\_t), intent(inout) :: eq  
     integer, intent(in) :: n\_dim  
     allocate (eq%permutation(n\_dim), eq%mode(n\_dim))  
 end subroutine vamp\_equivivalence\_init

72d *(Declaration of vamp\_equivalences procedures 72d)* ≡  
 public :: vamp\_equivalences\_init

72e *(Implementation of vamp\_equivalences procedures 72c)* +≡  
 subroutine vamp\_equivalences\_init (eq, n\_eq, n\_ch, n\_dim)  
     type(vamp\_equivalences\_t), intent(inout) :: eq  
     integer, intent(in) :: n\_eq, n\_ch, n\_dim  
     integer :: i  
     eq%n\_eq = n\_eq  
     eq%n\_ch = n\_ch  
     allocate (eq%eq(n\_eq))  
     allocate (eq%pointer(n\_ch+1))  
     do i=1, n\_eq  
         call vamp\_equivivalence\_init (eq%eq(i), n\_dim)  
     end do  
     allocate (eq%independent(n\_ch), eq%equivalent\_to\_ch(n\_ch))  
     allocate (eq%multiplicity(n\_ch), eq%symmetry(n\_ch))  
     allocate (eq%div\_is\_invariant(n\_ch, n\_dim))  
     eq%independent = .true.  
     eq%equivalent\_to\_ch = 0  
     eq%multiplicity = 0  
     eq%symmetry = 0  
     eq%div\_is\_invariant = .false.

```

 end subroutine vamp_equivalences_init

73a <Implementation of vamp_equivalences procedures 72c>+≡
 subroutine vamp_equivalence_final (eq)
 type(vamp_equivalence_t), intent(inout) :: eq
 deallocate (eq%permutation, eq%mode)
 end subroutine vamp_equivalence_final

73b <Declaration of vamp_equivalences procedures 72d>+≡
 public :: vamp_equivalences_final

73c <Implementation of vamp_equivalences procedures 72c>+≡
 subroutine vamp_equivalences_final (eq)
 type(vamp_equivalences_t), intent(inout) :: eq
 ! integer :: i
 ! do i=1, eq%n_eq
 ! call vamp_equivalence_final (eq%eq(i))
 ! end do
 if (allocated (eq%eq)) deallocate (eq%eq)
 if (allocated (eq%pointer)) deallocate (eq%pointer)
 if (allocated (eq%multiplicity)) deallocate (eq%multiplicity)
 if (allocated (eq%symmetry)) deallocate (eq%symmetry)
 if (allocated (eq%independent)) deallocate (eq%independent)
 if (allocated (eq%equivalent_to_ch)) deallocate (eq%equivalent_to_ch)
 if (allocated (eq%div_is_invariant)) deallocate (eq%div_is_invariant)
 eq%n_eq = 0
 eq%n_ch = 0
 end subroutine vamp_equivalences_final

73d <Implementation of vamp_equivalences procedures 72c>+≡
 subroutine vamp_equivalence_write (eq, unit)
 integer, intent(in), optional :: unit
 integer :: u
 type(vamp_equivalence_t), intent(in) :: eq
 u = 6; if (present (unit)) u = unit
 write (u, "(1x,A,2(1x,I4))") "Equivalent channels:", eq%left, eq%right
 write (u, "(1x,A,25(1x,I2))") " Permutation:", eq%permutation
 write (u, "(1x,A,25(1x,I2))") " Mode: ", eq%mode
 end subroutine vamp_equivalence_write

73e <Declaration of vamp_equivalences procedures 72d>+≡
 public :: vamp_equivalences_write

73f <Implementation of vamp_equivalences procedures 72c>+≡
 subroutine vamp_equivalences_write (eq, unit)
 type(vamp_equivalences_t), intent(in) :: eq
 integer, intent(in), optional :: unit

```

```

integer :: u
integer :: ch, i
u = 6; if (present (unit)) u = unit
write (u, *) "Inequivalent channels:"
do ch=1, eq%n_ch
 if (eq%independent(ch)) then
 write (u, *) " Channel", ch, ":", &
 & " Mult. =", eq%multiplicity(ch), &
 & " Symm. =", eq%symmetry(ch), &
 & " Invar.:", eq%div_is_invariant(ch,:)
 end if
end do
write (u, *) "Equivalence list:"
if (allocated (eq%eq)) then
 do i=1, size (eq%eq)
 call vamp_equivalence_write (eq%eq(i), u)
 end do
else
 write (u, *) "[not allocated]"
end if
end subroutine vamp_equivalences_write

```

74a <*Declaration of vamp\_equivalences procedures 72d*>+≡  
 public :: vamp\_equivalence\_set

74b <*Implementation of vamp\_equivalences procedures 72c*>+≡  
 subroutine vamp\_equivalence\_set (eq, i, left, right, perm, mode)  
 type(vamp\_equivalences\_t), intent(inout) :: eq  
 integer, intent(in) :: i  
 integer, intent(in) :: left, right  
 integer, dimension(:), intent(in) :: perm, mode  
 eq%eq(i)%left = left  
 eq%eq(i)%right = right  
 eq%eq(i)%permutation = perm  
 eq%eq(i)%mode = mode  
 end subroutine vamp\_equivalence\_set

74c <*Declaration of vamp\_equivalences procedures 72d*>+≡  
 public :: vamp\_equivalences\_complete

74d <*Implementation of vamp\_equivalences procedures 72c*>+≡  
 subroutine vamp\_equivalences\_complete (eq)  
 type(vamp\_equivalences\_t), intent(inout) :: eq  
 integer :: i, ch  
 ch = 0  
 do i=1, eq%n\_eq

```

 if (ch /= eq%eq(i)%left) then
 ch = eq%eq(i)%left
 eq%pointer(ch) = i
 end if
 end do
 eq%pointer(ch+1) = eq%n_eq + 1
 do ch=1, eq%n_ch
 call set_multiplicities (eq%eq(eq%pointer(ch):eq%pointer(ch+1)-1))
 end do
! call write (6, eq)
contains
 subroutine set_multiplicities (eq_ch)
 type(vamp_equivalence_t), dimension(:), intent(in) :: eq_ch
 integer :: i
 if (.not. all(eq_ch%left == ch) .or. eq_ch(1)%right > ch) then
 do i = 1, size (eq_ch)
 call vamp_equivalence_write (eq_ch(i))
 end do
 stop "VAMP: Equivalences: Something's wrong with equivalence ordering"
 end if
 eq%symmetry(ch) = count (eq_ch%right == ch)
 if (mod (size(eq_ch), eq%symmetry(ch)) /= 0) then
 do i = 1, size (eq_ch)
 call vamp_equivalence_write (eq_ch(i))
 end do
 stop "VAMP: Equivalences: Something's wrong with permutation count"
 end if
 eq%multiplicity(ch) = size (eq_ch) / eq%symmetry(ch)
 eq%independent(ch) = all (eq_ch%right >= ch)
 eq%equivalent_to_ch(ch) = eq_ch(1)%right
 eq%div_isInvariant(ch,:) = eq_ch(1)%mode == VEQ_INVARIANT
 end subroutine set_multiplicities
end subroutine vamp_equivalences_complete

```

75 <vamp.f90 70c>+≡

```

module vamp_rest
 use kinds
 use utils
 use exceptions
 use divisions
 use tao_random_numbers
 use vamp_stat
 use linalg
 use iso_fortran_env

```

```

use vamp_grid_type !NODEP!
use vamp_equivalences !NODEP!
implicit none
private
<Declaration of vamp procedures 77a>
<Interfaces of vamp procedures 94c>
<Constants in vamp 151a>
<Declaration of vamp types 105a>
<Variables in vamp 78a>
character(len=*), public, parameter :: VAMP_RCS_ID = &
 "$Id: vamp.nw 317 2010-04-18 00:31:03Z ohl $"
contains
 <Implementation of vamp procedures 77c>
end module vamp_rest

```

76a <vamp.f90 70c>+≡

```

module vamp
 use vamp_grid_type !NODEP!
 use vamp_rest !NODEP!
 use vamp_equivalences !NODEP!
 public
end module vamp

```

N.B.: In Fortran95 we will be able to give default initializations to components of the type. In particular, we can use the `null()` intrinsic to initialize the pointers to a disassociated state. Until then, the user *must* call the initializer `vamp_create_grid` himself or herself, because we can't check for the allocation status of the pointers in Fortran90 or F.

 Augment this datatype by `real(kind=default), dimension(2) :: mu_plus,`  
`mu_minus` to record positive and negative weight separately, so that we  
can estimate the efficiency for reweighting from indefinite weights to  
 $\{+1, -1\}$ .

76b <*Declaration of vamp\_grid\_type types 76b*>≡

```

type, public :: vamp_grid
 ! private ! forced by use association in interface
 type(division_t), dimension(:), pointer :: div => null()
 real(kind=default), dimension(:, :), pointer :: map => null()
 real(kind=default), dimension(:, :), pointer :: mu_x => null()
 real(kind=default), dimension(:, :), pointer :: sum_mu_x => null()
 real(kind=default), dimension(:, :), pointer :: mu_xx => null()
 real(kind=default), dimension(:, :), pointer :: sum_mu_xx => null()
 real(kind=default), dimension(2) :: mu
 real(kind=default) :: sum_integral, sum_weights, sum_chi2

```

```

real(kind=default) :: calls, dv2g, jacobi
real(kind=default) :: f_min, f_max
real(kind=default) :: mu_gi, sum_mu_gi
integer, dimension(:), pointer :: num_div => null ()
integer :: num_calls, calls_per_cell
logical :: stratified = .true.
logical :: all_stratified = .true.
logical :: quadrupole = .false.
logical :: independent
integer :: equivalent_to_ch, multiplicity
end type vamp_grid

```

**77a** *(Declaration of vamp procedures 77a)*≡  
`public :: vamp_copy_grid, vamp_delete_grid`

### 5.2.1 Initialization

**77b** *(Declaration of vamp procedures 77a)*+≡  
`public :: vamp_create_grid, vamp_create_empty_grid`

Create a fresh grid for the integration domain

$$\mathcal{D} = [D_{1,1}, D_{2,1}] \times [D_{1,2}, D_{2,2}] \times \dots \times [D_{1,n}, D_{2,n}] \quad (5.9)$$

dropping all accumulated results. This function *must not* be called twice on the first argument, without an intervening `vamp_delete_grid`. If the second variable is given, it will be the number of sampling points for the call to `vamp_sample_grid`.

**77c** *(Implementation of vamp procedures 77c)*≡  
`pure subroutine vamp_create_grid &`  
 `(g, domain, num_calls, num_div, &`  
 `stratified, quadrupole, covariance, map, exc)`  
 `type(vamp_grid), intent(inout) :: g`  
 `real(kind=default), dimension(:, :, :), intent(in) :: domain`  
 `integer, intent(in) :: num_calls`  
 `integer, dimension(:, :), intent(in), optional :: num_div`  
 `logical, intent(in), optional :: stratified, quadrupole, covariance`  
 `real(kind=default), dimension(:, :, :), intent(in), optional :: map`  
 `type(exception), intent(inout), optional :: exc`  
 `character(len=*), parameter :: FN = "vamp_create_grid"`  
 `real(kind=default), dimension(size(domain, dim=2)) :: &`  
 `x_min, x_max, x_min_true, x_max_true`  
 `integer :: ndim`  
 `ndim = size (domain, dim=2)`

```

allocate (g%div(ndim), g%num_div(ndim))
x_min = domain(1,:)
x_max = domain(2,:)
if (present (map)) then
 allocate (g%map(ndim,ndim))
 g%map = map
 x_min_true = x_min
 x_max_true = x_max
 call map_domain (g%map, x_min_true, x_max_true, x_min, x_max)
 call create_division (g%div, x_min, x_max, x_min_true, x_max_true)
else
 nullify (g%map)
 call create_division (g%div, x_min, x_max)
end if
g%num_calls = num_calls
if (present (num_div)) then
 g%num_div = num_div
else
 g%num_div = NUM_DIV_DEFAULT
end if
g%stratified = .true.
g%quadrupole = .false.
g%independent = .true.
g%equivalent_to_ch = 0
g%multiplicity = 1
nullify (g%mu_x, g%mu_xx, g%sum_mu_x, g%sum_mu_xx)
call vamp_discard_integral &
 (g, num_calls, num_div, stratified, quadrupole, covariance, exc)
end subroutine vamp_create_grid

```

Below, we assume that  $\text{NUM\_DIV\_DEFAULT} \geq 6$ , but we will never go that low anyway.

78a *(Variables in vamp 78a)≡*

```
integer, private, parameter :: NUM_DIV_DEFAULT = 20
```

Given a linear map  $M$ , find a domain  $\mathcal{D}_0$  such that

$$\mathcal{D} \subset M\mathcal{D}_0 \quad (5.10)$$

78b *(Declaration of vamp procedures 77a)++≡*

```
private :: map_domain
```

If we can assume that  $M$  is orthogonal  $M^{-1} = M^T$ , then we just have to rotate  $\mathcal{D}$  and determine the maximal and minimal extension of the corners:

$$\mathcal{D}_0^T = \overline{\mathcal{D}^T M} \quad (5.11)$$

The corners are just the powerset of the maximal and minimal extension in each coordinate. It is determined most easily with binary counting:

79a *(Implementation of vamp procedures 77c)*+≡

```
pure subroutine map_domain (map, true_xmin, true_xmax, xmin, xmax)
 real(kind=default), dimension(:,:), intent(in) :: map
 real(kind=default), dimension(:,), intent(in) :: true_xmin, true_xmax
 real(kind=default), dimension(:,), intent(out) :: xmin, xmax
 real(kind=default), dimension(2**size(xmin),size(xmin)) :: corners
 integer, dimension(size(xmin)) :: zero_to_n
 integer :: j, ndim, perm
 ndim = size (xmin)
 zero_to_n = (/ (j, j=0,ndim-1) /)
 do perm = 1, 2**ndim
 corners (perm,:) = &
 merge (true_xmin, true_xmax, btest (perm-1, zero_to_n))
 end do
 corners = matmul (corners, map)
 xmin = minval (corners, dim=1)
 xmax = maxval (corners, dim=1)
end subroutine map_domain
```

79b *(Implementation of vamp procedures 77c)*+≡

```
elemental subroutine vamp_create_empty_grid (g)
 type(vamp_grid), intent(inout) :: g
 nullify (g%div, g%num_div, g%map, g%mu_x, g%mu_xx, g%sum_mu_x, g%sum_mu_xx)
end subroutine vamp_create_empty_grid
```

79c *(Declaration of vamp procedures 77a)*+≡

```
public :: vamp_discard_integral
```

Keep the current optimized grid, but drop the accumulated results for the integral (value and errors). Iff the second variable is given, it will be the new number of sampling points for the next call to `vamp_sample_grid`.

79d *(Implementation of vamp procedures 77c)*+≡

```
pure subroutine vamp_discard_integral &
 (g, num_calls, num_div, stratified, quadrupole, covariance, exc, &
 & independent, equivalent_to_ch, multiplicity)
 type(vamp_grid), intent(inout) :: g
 integer, intent(in), optional :: num_calls
 integer, dimension(:,), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole, covariance
 type(exception), intent(inout), optional :: exc
 logical, intent(in), optional :: independent
 integer, intent(in), optional :: equivalent_to_ch, multiplicity
 character(len=*), parameter :: FN = "vamp_discard_integral"
```

```

g%mu = 0.0
g%mu_gi = 0.0
g%sum_integral = 0.0
g%sum_weights = 0.0
g%sum_chi2 = 0.0
g%sum_mu_gi = 0.0
if (associated (g%sum_mu_x)) then
 g%sum_mu_x = 0.0
 g%sum_mu_xx = 0.0
end if
call set_grid_options (g, num_calls, num_div, stratified, quadrupole, &
 independent, equivalent_to_ch, multiplicity)
if ((present (num_calls)) &
 .or. (present (num_div)) &
 .or. (present (stratified)) &
 .or. (present (quadrupole)) &
 .or. (present (covariance))) then
 call vamp_reshape_grid &
 (g, g%num_calls, g%num_div, &
 g%stratified, g%quadrupole, covariance, exc)
end if
end subroutine vamp_discard_integral
80a <Declaration of vamp procedures 77a>+≡
 private :: set_grid_options
80b <Implementation of vamp procedures 77c>+≡
 pure subroutine set_grid_options &
 (g, num_calls, num_div, stratified, quadrupole, &
 independent, equivalent_to_ch, multiplicity)
 type(vamp_grid), intent(inout) :: g
 integer, intent(in), optional :: num_calls
 integer, dimension(:), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole
 logical, intent(in), optional :: independent
 integer, intent(in), optional :: equivalent_to_ch, multiplicity
 if (present (num_calls)) then
 g%num_calls = num_calls
 end if
 if (present (num_div)) then
 g%num_div = num_div
 end if
 if (present (stratified)) then
 g%stratified = stratified
 end if

```

```

if (present (quadrupole)) then
 g%quadrupole = quadrupole
end if
if (present (independent)) then
 g%independent = independent
end if
if (present (equivalent_to_ch)) then
 g%equivalent_to_ch = equivalent_to_ch
end if
if (present (multiplicity)) then
 g%multiplicity = multiplicity
end if
end subroutine set_grid_options

```

### *Setting Up the Initial Grid*

Keep the current optimized grid and the accumulated results for the integral (value and errors). The second variable will be the new number of sampling points for the next call to `vamp_sample_grid`.

81   *Implementation of vamp procedures 77c* +≡

```

pure subroutine vamp_reshape_grid_internal &
 (g, num_calls, num_div, &
 stratified, quadrupole, covariance, exc, use_variance, &
 independent, equivalent_to_ch, multiplicity)
type(vamp_grid), intent(inout) :: g
integer, intent(in), optional :: num_calls
integer, dimension(:), intent(in), optional :: num_div
logical, intent(in), optional :: stratified, quadrupole, covariance
type(exception), intent(inout), optional :: exc
logical, intent(in), optional :: use_variance
logical, intent(in), optional :: independent
integer, intent(in), optional :: equivalent_to_ch, multiplicity
integer :: ndim, num_cells
integer, dimension(size(g%div)) :: ng
character(len=*), parameter :: FN = "vamp_reshape_grid_internal"
ndim = size (g%div)
call set_grid_options &
 (g, num_calls, num_div, stratified, quadrupole, &
 & independent, equivalent_to_ch, multiplicity)
<Adjust grid and other state for new num_calls 83a>
g%all_stratified = all (stratified_division (g%div))
if (present (covariance)) then
 ndim = size (g%div)

```

```

 if (covariance .and. (.not. associated (g%mu_x))) then
 allocate (g%mu_x(ndim), g%mu_xx(ndim,ndim))
 allocate (g%sum_mu_x(ndim), g%sum_mu_xx(ndim,ndim))
 g%sum_mu_x = 0.0
 g%sum_mu_xx = 0.0
 else if ((.not. covariance) .and. (associated (g%mu_x))) then
 deallocate (g%mu_x, g%mu_xx, g%sum_mu_x, g%sum_mu_xx)
 end if
end if
end subroutine vamp_reshape_grid_internal

```

The `use_variance` argument is too dangerous for careless users, because the variance in the divisions will contain garbage before sampling and after reshaping. Build a fence with another routine.

- 82a *(Declaration of vamp procedures 77a)*+≡
 

```

private :: vamp_reshape_grid_internal
public :: vamp_reshape_grid

```
- 82b *(Implementation of vamp procedures 77c)*+≡
 

```

pure subroutine vamp_reshape_grid &
 (g, num_calls, num_div, stratified, quadrupole, covariance, exc, &
 independent, equivalent_to_ch, multiplicity)
 type(vamp_grid), intent(inout) :: g
 integer, intent(in), optional :: num_calls
 integer, dimension(:), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole, covariance
 type(exception), intent(inout), optional :: exc
 logical, intent(in), optional :: independent
 integer, intent(in), optional :: equivalent_to_ch, multiplicity
 call vamp_reshape_grid_internal &
 (g, num_calls, num_div, stratified, quadrupole, covariance, &
 exc, use_variance = .false., &
 independent=independent, equivalent_to_ch=equivalent_to_ch, &
 multiplicity=multiplicity)
end subroutine vamp_reshape_grid

```

`vegas` operates in three different modes, which are chosen according to explicit user requests and to the relation of the requested number of sampling points to the dimensionality of the integration domain.

The simplest case is when the user has overwritten the default of stratified sampling with the optional argument `stratified` in the call to `vamp_create_grid`. Then sample points will be chosen randomly with equal probability in each cell of the adaptive grid, as displayed in figure 5.1.

The implementation is actually shared with the stratified case described below, by pretending that there is just a single stratification cell. The number

of divisions for the adaptive grid is set to a compile time maximum value.

If the user has agreed on stratified sampling then there are two cases, depending on the dimensionality of the integration region and the number of sample points. First we determine the number of divisions  $n_g$  (i.e. `ng`) of the rigid grid such that there will be two sampling points per cell.

$$N_{\text{calls}} = 2 \cdot (n_g)^{n_{\text{dim}}} \quad (5.12)$$

The additional optional argument  $\hat{n}_g$  specifies an anisotropy in the shape

$$n_{g,j} = \frac{\hat{n}_{g,j}}{\left(\prod_j \hat{n}_{g,j}\right)^{1/n_{\text{dim}}}} \left(\frac{N}{2}\right)^{1/n_{\text{dim}}} \quad (5.13)$$

NB:

$$\prod_j n_{g,j} = \frac{N}{2} \quad (5.14)$$

```
83a <Adjust grid and other state for new num_calls 83a>≡
 if (g%stratified) then
 ng = (g%num_calls / 2.0 + 0.25)**(1.0/ndim)
 ! ng = ng * real (g%num_div, kind=default) &
 ! / (product (real (g%num_div, kind=default)))**(1.0/ndim)
 else
 ng = 1
 end if
 call reshape_division (g%div, g%num_div, ng, use_variance)
 call clear_integral_and_variance (g%div)
 num_cells = product (rigid_division (g%div))
 g%calls_per_cell = max (g%num_calls / num_cells, 2)
 g%calls = real (g%calls_per_cell) * real (num_cells)
 jacobi = J = Volume
 N_calls
 (5.15)
```

and

$$\text{dv2g} = \frac{N_{\text{calls}}^2 ((\Delta x)^{n_{\text{dim}}})^2}{N_{\text{calls/cell}}^2 (N_{\text{calls/cell}} - 1)} = \frac{\left(\frac{N_{\text{calls}}}{N_{\text{cells}}}\right)^2}{N_{\text{calls/cell}}^2 (N_{\text{calls/cell}} - 1)} \quad (5.16)$$

```
83b <Adjust grid and other state for new num_calls 83a>+≡
 g%jacobi = product (volume_division (g%div)) / g%calls
 g%dv2g = (g%calls / num_cells)**2 &
 / g%calls_per_cell / g%calls_per_cell / (g%calls_per_cell - 1.0)
```

84a *(Adjust grid and other state for new num\_calls 83a)*+≡  
call vamp\_nullify\_f\_limits (g)

When the grid is refined or reshaped, the recorded minimum and maximum of the sampling function should be nullified:

84b *(Declaration of vamp procedures 77a)*+≡  
public :: vamp\_nullify\_f\_limits

84c *(Implementation of vamp procedures 77c)*+≡  
elemental subroutine vamp\_nullify\_f\_limits (g)  
type(vamp\_grid), intent(inout) :: g  
g%f\_min = 1.0  
g%f\_max = 0.0  
end subroutine vamp\_nullify\_f\_limits

84d *(Declaration of vamp procedures 77a)*+≡  
public :: vamp\_rigid\_divisions  
public :: vamp\_get\_covariance, vamp\_nullify\_covariance  
public :: vamp\_get\_variance, vamp\_nullify\_variance

84e *(Implementation of vamp procedures 77c)*+≡  
pure function vamp\_rigid\_divisions (g) result (ng)  
type(vamp\_grid), intent(in) :: g  
integer, dimension(size(g%div)) :: ng  
ng = rigid\_division (g%div)  
end function vamp\_rigid\_divisions

84f *(Implementation of vamp procedures 77c)*+≡  
pure function vamp\_get\_covariance (g) result (cov)  
type(vamp\_grid), intent(in) :: g  
real(kind=default), dimension(size(g%div),size(g%div)) :: cov  
if (associated (g%mu\_x)) then  
if (abs (g%sum\_weights) <= tiny (cov(1,1))) then  
where (g%sum\_mu\_xx == 0.0\_default)  
cov = 0.0  
elsewhere  
cov = huge (cov(1,1))  
endwhere  
else  
cov = g%sum\_mu\_xx / g%sum\_weights &  
- outer\_product (g%sum\_mu\_x, g%sum\_mu\_x) / g%sum\_weights\*\*2  
end if  
else  
cov = 0.0  
end if  
end function vamp\_get\_covariance

85a *(Implementation of vamp procedures 77c)*+≡

```

elemental subroutine vamp_nullify_covariance (g)
 type(vamp_grid), intent(inout) :: g
 if (associated (g%mu_x)) then
 g%sum_mu_x = 0
 g%sum_mu_xx = 0
 end if
end subroutine vamp_nullify_covariance
```

85b *(Implementation of vamp procedures 77c)*+≡

```

elemental function vamp_get_variance (g) result (v)
 type(vamp_grid), intent(in) :: g
 real(kind=default) :: v
 if (abs (g%sum_weights) <= tiny (v)) then
 if (g%sum_mu_gi == 0.0_default) then
 v = 0.0
 else
 v = huge (v)
 end if
 else
 v = g%sum_mu_gi / g%sum_weights
 end if
end function vamp_get_variance
```

85c *(Implementation of vamp procedures 77c)*+≡

```

elemental subroutine vamp_nullify_variance (g)
 type(vamp_grid), intent(inout) :: g
 g%sum_mu_gi = 0
end subroutine vamp_nullify_variance
```

### 5.2.2 Sampling

85d *(Declaration of vamp procedures 77a)*+≡

```

public :: vamp_sample_grid
public :: vamp_sample_grid0
public :: vamp_refine_grid
public :: vamp_refine_grids
```

*Simple Non-Adaptive Sampling:  $S_0$*

85e *(Implementation of vamp procedures 77c)*+≡

```

pure subroutine vamp_sample_grid0 (
 rng, g, func, prc_index, channel, weights, grids, exc, &
 negative_weights)
```

```

type(tao_random_state), intent(inout) :: rng
type(vamp_grid), intent(inout) :: g
integer, intent(in) :: prc_index
integer, intent(in), optional :: channel
real(kind=default), dimension(:), intent(in), optional :: weights
type(vamp_grid), dimension(:), intent(in), optional :: grids
type(exception), intent(inout), optional :: exc
<Interface declaration for func 22>
character(len=*), parameter :: FN = "vamp_sample_grid0"
logical, intent(in), optional :: negative_weights
<Local variables in vamp_sample_grid0 87a>
integer :: ndim
logical :: neg_w
ndim = size (g%div)
neg_w = .false.
if (present (negative_weights)) neg_w = negative_weights
<Check optional arguments in vamp_sample_grid0 90a>
<Reset counters in vamp_sample_grid0 86b>
loop_over_cells: do
 <Sample calls_per_cell points in the current cell 87c>
 <Collect integration and grid optimization data for current cell 89a>
 <Count up cell, exit if done 86a>
end do loop_over_cells
<Collect results of vamp_sample_grid0 89b>
end subroutine vamp_sample_grid0

```

Count cells like a  $n_g$ -ary number—i.e.  $(1, \dots, 1, 1)$ ,  $(1, \dots, 1, 2)$ ,  $\dots$ ,  $(1, \dots, 1, n_g)$ ,  $(1, \dots, 2, 1)$ ,  $\dots$ ,  $(n_g, \dots, n_g, n_g - 1)$ ,  $(n_g, \dots, n_g, n_g)$ —and terminate when all (cell == 1) again.

86a <Count up cell, exit if done 86a>≡

```

do j = ndim, 1, -1
 cell(j) = modulo (cell(j), rigid_division (g%div(j))) + 1
 if (cell(j) /= 1) then
 cycle loop_over_cells
 end if
end do
exit loop_over_cells

```

86b <Reset counters in vamp\_sample\_grid0 86b>≡

```

g%mu = 0.0
cell = 1
call clear_integral_and_variance (g%div)
if (associated (g%mu_x)) then

```

```

g%mu_x = 0.0
g%mu_xx = 0.0
end if
if (present (channel)) then
 g%mu_gi = 0.0
end if

87a <Local variables in vamp_sample_grid0 87a>≡
 real(kind=default), parameter :: &
 eps = tiny (1._default) / epsilon (1._default)
 character(len=6) :: buffer

87b <Local variables in vamp_sample_grid0 87a>+≡
 integer :: j, k
 integer, dimension(size(g%div)) :: cell

87c <Sample calls_per_cell points in the current cell 87c>≡
 sum_f = 0.0
 sum_f2 = 0.0
 do k = 1, g%calls_per_cell
 <Get x in the current cell 87d>
 <f = wgt * func (x, weights, channel), iff x inside true_domain 88a>
 <Collect integration and grid optimization data for x from f 88b>
 end do

```

We are using the generic procedure `tao_random_number` from the `tao_random_numbers` module for generating an array of uniform deviates. A better alternative would be to pass the random number generator as an argument to `vamp_sample_grid`. Unfortunately, it is not possible to pass *generic* procedures in Fortran90, Fortran95, or F. While we could export a specific procedure from `tao_random_numbers`, a more serious problem is that we have to pass the state `rng` of the random number generator as a `tao_random_state` anyway and we have to hardcode the random number generator anyway.

```

87d <Get x in the current cell 87d>≡
 call tao_random_number (rng, r)
 call inject_division (g%div, real (r, kind=default), &
 cell, x, x_mid, ia, wgts)
 wgt = g%jacobi * product (wgts)
 if (associated (g%map)) then
 x = matmul (g%map, x)
 end if

```

This somewhat contorted nested `if` constructs allow to minimize the number of calls to `func`. This is useful, since `func` is the most expensive part of real world applications. Also `func` might be singular outside of `true_domain`.

The original `vegas` used to call `f = wgt * func (x, wgt)` below to allow `func` to use `wgt` (i.e.  $1/p(x)$ ) for integrating another function at the same time. This form of “parallelism” relies on side effects and is therefore impossible with pure functions. Consequently, it is not supported in the current implementation.

```

88a <f = wgt * func (x, weights, channel), iff x inside true_domain 88a>≡
 if (associated (g%map)) then
 if (all (inside_division (g%div, x))) then
 f = wgt * func (x, prc_index, weights, channel, grids)
 else
 f = 0.0
 end if
 else
 f = wgt * func (x, prc_index, weights, channel, grids)
 end if

88b <Collect integration and grid optimization data for x from f 88b>≡
 if (g%f_min > g%f_max) then
 g%f_min = f * g%calls
 g%f_max = f * g%calls
 else if (f * g%calls < g%f_min) then
 g%f_min = f * g%calls
 else if (f * g%calls > g%f_max) then
 g%f_max = f * g%calls
 end if

88c <Collect integration and grid optimization data for x from f 88b>+≡
 f2 = f * f
 sum_f = sum_f + f
 sum_f2 = sum_f2 + f2
 call record_integral (g%div, ia, f)
 ! call record_efficiency (g%div, ia, f/g%f_max)
 if ((associated (g%mu_x)) .and. (.not. g%all_stratified)) then
 g%mu_x = g%mu_x + x * f
 g%mu_xx = g%mu_xx + outer_product (x, x) * f
 end if
 if (present (channel)) then
 g%mu_gi = g%mu_gi + f2
 end if

88d <Local variables in vamp_sample_grid0 87a>+≡
 real(kind=default) :: wgt, f, f2, sum_f, sum_f2, var_f
 real(kind=default), dimension(size(g%div)):: x, x_mid, wgts
 real(kind=default), dimension(size(g%div)):: r
 integer, dimension(size(g%div)) :: ia

```

$$\sigma^2 \cdot N_{\text{calls}/\text{cell}}^2 (N_{\text{calls}/\text{cell}} - 1) = \text{var}(f) = N^2 \sigma^2 \left( \left\langle \frac{f^2}{p} \right\rangle - \langle f \rangle^2 \right) \quad (5.17)$$

89a  $\langle \text{Collect integration and grid optimization data for current cell } 89a \rangle \equiv$

```

var_f = sum_f2 * g%calls_per_cell - sum_f**2
if (var_f <= 0.0) then
 var_f = tiny (1.0_default)
end if
g%mu = g%mu + (/ sum_f, var_f /)
call record_variance (g%div, ia, var_f)
if ((associated (g%mu_x)) .and. g%all_stratified) then
 if (associated (g%map)) then
 x_mid = matmul (g%map, x_mid)
 end if
 g%mu_x = g%mu_x + x_mid * var_f
 g%mu_xx = g%mu_xx + outer_product (x_mid, x_mid) * var_f
end if

```

$$\sigma^2 = \frac{\left(\frac{N_{\text{calls}}}{N_{\text{cells}}}\right)^2}{N_{\text{calls}/\text{cell}}^2 (N_{\text{calls}/\text{cell}} - 1)} \sum_{\text{cells}} \sigma_{\text{cell}}^2 \cdot N_{\text{calls}/\text{cell}}^2 (N_{\text{calls}/\text{cell}} - 1) \quad (5.18)$$

where the  $N_{\text{calls}}^2$  cancels the corresponding factor in the Jacobian and the  $N_{\text{cells}}^{-2}$  is the result of stratification.

89b  $\langle \text{Collect results of vamp_sample_grid0 } 89b \rangle \equiv$

```

g%mu(2) = g%mu(2) * g%dv2g
if (g%mu(2) < eps * max (g%mu(1)**2, 1._default)) then
 g%mu(2) = eps * max (g%mu(1)**2, 1._default)
end if

```

89c  $\langle \text{Collect results of vamp_sample_grid0 } 89b \rangle + \equiv$

```

if (g%mu(1)>0) then
 g%sum_integral = g%sum_integral + g%mu(1) / g%mu(2)
 g%sum_weights = g%sum_weights + 1.0 / g%mu(2)
 g%sum_chi2 = g%sum_chi2 + g%mu(1)**2 / g%mu(2)
 if (associated (g%mu_x)) then
 if (g%all_stratified) then
 g%mu_x = g%mu_x / g%mu(2)
 g%mu_xx = g%mu_xx / g%mu(2)
 else
 g%mu_x = g%mu_x / g%mu(1)
 g%mu_xx = g%mu_xx / g%mu(1)
 end if
 g%sum_mu_x = g%sum_mu_x + g%mu_x / g%mu(2)
 g%sum_mu_xx = g%sum_mu_xx + g%mu_xx / g%mu(2)
 end if
end if

```

```

 end if
 if (present (channel)) then
 g%sum_mu_gi = g%sum_mu_gi + g%mu_gi / g%mu(2)
 end if
 else if (neg_w) then
 g%sum_integral = g%sum_integral + g%mu(1) / g%mu(2)
 g%sum_weights = g%sum_weights + 1.0 / g%mu(2)
 g%sum_chi2 = g%sum_chi2 + g%mu(1)**2 / g%mu(2)
 if (associated (g%mu_x)) then
 if (g%all_stratified) then
 g%mu_x = g%mu_x / g%mu(2)
 g%mu_xx = g%mu_xx / g%mu(2)
 else
 g%mu_x = g%mu_x / g%mu(1)
 g%mu_xx = g%mu_xx / g%mu(1)
 end if
 g%sum_mu_x = g%sum_mu_x + g%mu_x / g%mu(2)
 g%sum_mu_xx = g%sum_mu_xx + g%mu_xx / g%mu(2)
 end if
 if (present (channel)) then
 g%sum_mu_gi = g%sum_mu_gi + g%mu_gi / g%mu(2)
 end if
 else
 if (present(channel) .and. g%mu(1)==0) then
 write (buffer, "(I6)") channel
 call raise_exception (exc, EXC_WARN, "! vamp", &
 "Function identically zero in channel " // buffer)
 else if (present(channel) .and. g%mu(1)<0) then
 write (buffer, "(I6)") channel
 call raise_exception (exc, EXC_ERROR, "! vamp", &
 "Negative integral in channel " // buffer)
 end if
 g%sum_integral = 0
 g%sum_chi2 = 0
 g%sum_weights = 0
 end if

```

90a ⟨Check optional arguments in vamp\_sample\_grid0 90a⟩≡  
 if (present (channel) .neqv. present (weights)) then  
 call raise\_exception (exc, EXC\_FATAL, FN, &  
 "channel and weights required together")  
 return  
 end if

90b ⟨Declaration of vamp procedures 77a⟩+≡

```

public :: vamp_probability

91a <Implementation of vamp procedures 77c>+≡
pure function vamp_probability (g, x) result (p)
 type(vamp_grid), intent(in) :: g
 real(kind=default), dimension(:), intent(in) :: x
 real(kind=default) :: p
 p = product (probability (g%div, x))
end function vamp_probability

z %variance should be private to division

91b <Implementation of vamp procedures 77c>+≡
subroutine vamp_apply_equivalences (g, eq)
 type(vamp_grids), intent(inout) :: g
 type(vamp_equivalences_t), intent(in) :: eq
 integer :: n_ch, n_dim, nb, i, ch, ch_src, dim, dim_src
 integer, dimension(:, :, :), allocatable :: n_bin
 real(kind=default), dimension(:, :, :, :), allocatable :: var_tmp
 n_ch = size (g%grids)
 if (n_ch == 0) return
 n_dim = size (g%grids(1)%div)
 allocate (n_bin(n_ch, n_dim))
 do ch = 1, n_ch
 do dim = 1, n_dim
 n_bin(ch, dim) = size (g%grids(ch)%div(dim)%variance)
 end do
 end do
 allocate (var_tmp (maxval(n_bin), n_dim, n_ch))
 var_tmp = 0
 do i=1, eq%n_eq
 ch = eq%eq(i)%left
 ch_src = eq%eq(i)%right
 do dim=1, n_dim
 nb = n_bin(ch_src, dim)
 dim_src = eq%eq(i)%permutation(dim)
 select case (eq%eq(i)%mode(dim))
 case (VEQ_IDENTITY)
 var_tmp(:nb,dim,ch) = var_tmp(:nb,dim,ch) &
 & + g%grids(ch_src)%div(dim_src)%variance
 case (VEQ_INVERT)
 var_tmp(:nb,dim,ch) = var_tmp(:nb,dim,ch) &
 & + g%grids(ch_src)%div(dim_src)%variance(nb:1:-1)
 case (VEQ_SYMMETRIC)

```

```

 var_tmp(:nb,dim,ch) = var_tmp(:nb,dim,ch) &
 & + g%grids(ch_src)%div(dim_src)%variance / 2 &
 & + g%grids(ch_src)%div(dim_src)%variance(nb:1:-1)/2
 case (VEQ_INVARIANT)
 var_tmp(:nb,dim,ch) = 1
 end select
 end do
end do
do ch=1, n_ch
 do dim=1, n_dim
 g%grids(ch)%div(dim)%variance = var_tmp(:n_bin(ch, dim),dim,ch)
 end do
end do
deallocate (var_tmp)
deallocate (n_bin)
end subroutine vamp_apply_equivalences

```

*Grid Refinement: r*

$$n_{\text{div},j} \rightarrow \frac{Q_j n_{\text{div},j}}{\left(\prod_j Q_j\right)^{1/n_{\text{dim}}}} \quad (5.19)$$

where

$$Q_j = \left( \sqrt{\text{Var}(\{m\}_j)} \right)^\alpha \quad (5.20)$$

92    *Implementation of vamp procedures 77c* +≡

```

pure subroutine vamp_refine_grid (g, exc)
 type(vamp_grid), intent(inout) :: g
 type(exception), intent(inout), optional :: exc
 real(kind=default), dimension(size(g%div)) :: quad
 integer :: ndim
 if (g%quadrupole) then
 ndim = size (g%div)
 quad = (quadrupole_division (g%div)**QUAD_POWER
 call vamp_reshape_grid_internal &
 (g, use_variance = .true., exc = exc, &
 num_div = int (quad / product (quad)**(1.0/ndim) * g%num_div))
 else
 call refine_division (g%div)
 call vamp_nullify_f_limits (g)
 end if
end subroutine vamp_refine_grid

```

```

93a <Implementation of vamp procedures 77c>+≡
 subroutine vamp_refine_grids (g)
 type(vamp_grids), intent(inout) :: g
 integer :: ch
 do ch=1, size(g%grids)
 call refine_division (g%grids(ch)%div)
 call vamp_nullify_f_limits (g%grids(ch))
 end do
 end subroutine vamp_refine_grids

93b <Variables in vamp 78a>+≡
 real(kind=default), private, parameter :: QUAD_POWER = 0.5_default

```

$$\text{Adaptive Sampling: } S_n = S_0(rS_0)^n$$

```

93c <Implementation of vamp procedures 77c>+≡
 pure subroutine vamp_sample_grid &
 (rng, g, func, prc_index, iterations, &
 integral, std_dev, avg_chi2, accuracy, &
 channel, weights, grids, exc, history)
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grid), intent(inout) :: g
 integer, intent(in) :: prc_index
 integer, intent(in) :: iterations
 real(kind=default), intent(out), optional :: integral, std_dev, avg_chi2
 real(kind=default), intent(in), optional :: accuracy
 integer, intent(in), optional :: channel
 real(kind=default), dimension(:), intent(in), optional :: weights
 type(vamp_grid), dimension(:), intent(in), optional :: grids
 type(exception), intent(inout), optional :: exc
 type(vamp_history), dimension(:), intent(inout), optional :: history
 <Interface declaration for func 22>
 character(len=*), parameter :: FN = "vamp_sample_grid"
 real(kind=default) :: local_integral, local_std_dev, local_avg_chi2
 integer :: iteration, ndim
 ndim = size (g%div)
 iterate: do iteration = 1, iterations
 call vamp_sample_grid0 &
 (rng, g, func, prc_index, channel, weights, grids, exc)
 call vamp_average_iterations &
 (g, iteration, local_integral, local_std_dev, local_avg_chi2)
 <Trace results of vamp_sample_grid 105b>
 <Exit iterate if accuracy has been reached 95b>
 if (iteration < iterations) call vamp_refine_grid (g)

```

```

 end do iterate
 <Copy results of vamp_sample_grid to dummy variables 95a>
end subroutine vamp_sample_grid

```

Assuming that the iterations have been statistically independent, we can combine them with the usual formulae.

$$\bar{I} = \sigma_I^2 \sum_i \frac{I_i}{\sigma_i^2} \quad (5.21a)$$

$$\frac{1}{\sigma_I^2} = \sum_i \frac{1}{\sigma_i^2} \quad (5.21b)$$

$$\chi^2 = \sum_i \frac{(I_i - \bar{I})^2}{\sigma_i^2} = \sum_i \frac{I_i^2}{\sigma_i^2} - \bar{I} \sum_i \frac{I_i}{\sigma_i^2} \quad (5.21c)$$

```

94a <Implementation of vamp procedures 77c>+≡
 elemental subroutine vamp_average_iterations_grid &
 (g, iteration, integral, std_dev, avg_chi2)
 type(vamp_grid), intent(in) :: g
 integer, intent(in) :: iteration
 real(kind=default), intent(out) :: integral, std_dev, avg_chi2
 real(kind=default), parameter :: eps = 1000 * epsilon (1._default)
 if (g%sum_weights>0) then
 integral = g%sum_integral / g%sum_weights
 std_dev = sqrt (1.0 / g%sum_weights)
 avg_chi2 = &
 max ((g%sum_chi2 - g%sum_integral * integral) / (iteration-0.99), &
 0.0_default)
 if (avg_chi2 < eps * g%sum_chi2) avg_chi2 = 0
 else
 integral = 0
 std_dev = 0
 avg_chi2 = 0
 end if
 end subroutine vamp_average_iterations_grid

94b <Declaration of vamp procedures 77a>+≡
 public :: vamp_average_iterations
 private :: vamp_average_iterations_grid

94c <Interfaces of vamp procedures 94c>≡
 interface vamp_average_iterations
 module procedure vamp_average_iterations_grid
 end interface

```

Lepage suggests [1] to reweight the contributions as in the following improved formulae, which we might implement as an option later.

$$\bar{I} = \frac{1}{\left(\sum_i \frac{I_i^2}{\sigma_i^2}\right)^2} \sum_i I_i \frac{I_i^2}{\sigma_i^2} \quad (5.22a)$$

$$\frac{1}{\sigma_I^2} = \frac{1}{(\bar{I})^2} \sum_i \frac{I_i^2}{\sigma_i^2} \quad (5.22b)$$

$$\chi^2 = \sum_i \frac{(I_i - \bar{I})^2}{(\bar{I})^2} \frac{I_i^2}{\sigma_i^2} \quad (5.22c)$$

Iff possible, copy the result to the caller's variables:

95a *(Copy results of vamp\_sample\_grid to dummy variables 95a)≡*

```

if (present (integral)) then
 integral = local_integral
end if
if (present (std_dev)) then
 std_dev = local_std_dev
end if
if (present (avg_chi2)) then
 avg_chi2 = local_avg_chi2
end if

```

95b *(Exit iterate if accuracy has been reached 95b)≡*

```

if (present (accuracy)) then
 if (local_std_dev <= accuracy * local_integral) then
 call raise_exception (exc, EXC_INFO, FN, &
 "requested accuracy reached")
 exit iterate
 end if
end if

```

### 5.2.3 Forking and Joining

95c *(Declaration of vamp procedures 77a)≡*

```

public :: vamp_fork_grid
private :: vamp_fork_grid_single, vamp_fork_grid_multi
public :: vamp_join_grid
private :: vamp_join_grid_single, vamp_join_grid_multi

```

95d *(Interfaces of vamp procedures 94c)≡*

```

interface vamp_fork_grid
 module procedure vamp_fork_grid_single, vamp_fork_grid_multi

```

```

 end interface
 interface vamp_join_grid
 module procedure vamp_join_grid_single, vamp_join_grid_multi
 end interface

```

Caveat emptor: splitting divisions can lead to `num_div < 3` and the application must not try to refine such grids before merging them again! `d == 0` is special.

96a *(Implementation of `vamp` procedures 77c)* +≡

```

pure subroutine vamp_fork_grid_single (g, gs, d, exc)
 type(vamp_grid), intent(in) :: g
 type(vamp_grid), dimension(:), intent(inout) :: gs
 integer, intent(in) :: d
 type(exception), intent(inout), optional :: exc
 character(len=*), parameter :: FN = "vamp_fork_grid_single"
 type(division_t), dimension(:), allocatable :: d_tmp
 integer :: i, j, num_grids, num_div, ndim, num_cells
 num_grids = size (gs)
 ndim = size (g%div)
 <Allocate or resize the divisions 98c>
 do j = 1, ndim
 if (j == d) then
 <call fork_division (g%div(j), gs%div(j), g%calls_per_cell, ...) 97d>
 else
 <call copy_division (gs%div(j), g%div(j)) 98b>
 end if
 end do
 if (d == 0) then
 <Handle g%calls_per_cell for d == 0 96b>
 end if
 <Copy the rest of g to the gs 96c>
end subroutine vamp_fork_grid_single

```

Divide the sampling points among identical grids

96b *(Handle `g%calls_per_cell` for `d == 0` 96b)* ≡

```

if (any (stratified_division (g%div))) then
 call raise_exception (exc, EXC_FATAL, FN, &
 "d == 0 incompatible w/ stratification")
else
 gs(2:)%calls_per_cell = ceiling (real (g%calls_per_cell) / num_grids)
 gs(1)%calls_per_cell = g%calls_per_cell - sum (gs(2:)%calls_per_cell)
end if

```

96c *(Copy the rest of g to the gs 96c)* ≡

```

do i = 1, num_grids

```

```

call copy_array_pointer (gs(i)%num_div, g%num_div)
if (associated (g%map)) then
 call copy_array_pointer (gs(i)%map, g%map)
end if
if (associated (g%mu_x)) then
 call create_array_pointer (gs(i)%mu_x, ndim)
 call create_array_pointer (gs(i)%sum_mu_x, ndim)
 call create_array_pointer (gs(i)%mu_xx, (/ ndim, ndim /))
 call create_array_pointer (gs(i)%sum_mu_xx, (/ ndim, ndim /))
end if
end do

```

Reset results

97a *(Copy the rest of g to the gs 96c)*+≡

```

gs%mu(1) = 0.0
gs%mu(2) = 0.0
gs%sum_integral = 0.0
gs%sum_weights = 0.0
gs%sum_chi2 = 0.0
gs%mu_gi = 0.0
gs%sum_mu_gi = 0.0

```

97b *(Copy the rest of g to the gs 96c)*+≡

```

gs%stratified = g%stratified
gs%all_stratified = g%all_stratified
gs%quadrupole = g%quadrupole

```

97c *(Copy the rest of g to the gs 96c)*+≡

```

do i = 1, num_grids
 num_cells = product (rigid_division (gs(i)%div))
 gs(i)%calls = gs(i)%calls_per_cell * num_cells
 gs(i)%num_calls = gs(i)%calls
 gs(i)%jacobi = product (volume_division (gs(i)%div)) / gs(i)%calls
 gs(i)%dv2g = (gs(i)%calls / num_cells)**2 &
 / gs(i)%calls_per_cell / gs(i)%calls_per_cell / (gs(i)%calls_per_cell - 1.0)
end do
gs%f_min = g%f_min * (gs%jacobi * gs%calls) / (g%jacobi * g%calls)
gs%f_max = g%f_max * (gs%jacobi * gs%calls) / (g%jacobi * g%calls)

```

This could be self-explaining, if the standard would allow .... Note that we can get away with copying just the pointers, because `fork_division` does the dirty work for the memory management.

97d *(call fork\_division (g%div(j), gs%div(j), g%calls\_per\_cell, ...) 97d)*≡

```

allocate (d_tmp(num_grids))
do i = 1, num_grids

```

```

 d_tmp(i) = gs(i)%div(j)
 end do
 call fork_division (g%div(j), d_tmp, g%calls_per_cell, gs%calls_per_cell, exc)
 do i = 1, num_grids
 gs(i)%div(j) = d_tmp(i)
 end do
 deallocate (d_tmp)
 <Bail out if exception exc raised 98a>
98a <Bail out if exception exc raised 98a>≡
 if (present (exc)) then
 if (exc%level > EXC_WARN) then
 return
 end if
 end if
We have to do a deep copy ($gs(i)\%div(j) = g\%div(j)$ does not suffice),
because copy_division handles the memory management.
98b <call copy_division (gs%div(j), g%div(j)) 98b>≡
 do i = 1, num_grids
 call copy_division (gs(i)\%div(j), g\%div(j))
 end do
98c <Allocate or resize the divisions 98c>≡
 num_div = size (g%div)
 do i = 1, size (gs)
 if (associated (gs(i)\%div)) then
 if (size (gs(i)\%div) /= num_div) then
 allocate (gs(i)\%div(num_div))
 call create_empty_division (gs(i)\%div)
 end if
 else
 allocate (gs(i)\%div(num_div))
 call create_empty_division (gs(i)\%div)
 end if
 end do
98d <Implementation of vamp procedures 77c>+≡
 pure subroutine vamp_join_grid_single (g, gs, d, exc)
 type(vamp_grid), intent(inout) :: g
 type(vamp_grid), dimension(:), intent(inout) :: gs
 integer, intent(in) :: d
 type(exception), intent(inout), optional :: exc
 type(division_t), dimension(:), allocatable :: d_tmp
 integer :: i, j, num_grids
 num_grids = size (gs)

```

```

do j = 1, size (g%div)
 if (j == d) then
 <call join_division (g%div(j), gs%div(j)) 99a>
 else
 <call sum_division (g%div(j), gs%div(j)) 99b>
 end if
end do
<Combine the rest of gs onto g 99c>
end subroutine vamp_join_grid_single

99a <call join_division (g%div(j), gs%div(j)) 99a>≡
 allocate (d_tmp(num_grids))
 do i = 1, num_grids
 d_tmp(i) = gs(i)%div(j)
 end do
 call join_division (g%div(j), d_tmp, exc)
 deallocate (d_tmp)
 <Bail out if exception exc raised 98a>

99b <call sum_division (g%div(j), gs%div(j)) 99b>≡
 allocate (d_tmp(num_grids))
 do i = 1, num_grids
 d_tmp(i) = gs(i)%div(j)
 end do
 call sum_division (g%div(j), d_tmp)
 deallocate (d_tmp)

99c <Combine the rest of gs onto g 99c>≡
 g%f_min = minval (gs%f_min * (g%jacobi * g%calls) / (gs%jacobi * gs%calls))
 g%f_max = maxval (gs%f_max * (g%jacobi * g%calls) / (gs%jacobi * gs%calls))
 g%mu(1) = sum (gs%mu(1))
 g%mu(2) = sum (gs%mu(2))
 g%mu_gi = sum (gs%mu_gi)
 g%sum_mu_gi = g%sum_mu_gi + g%mu_gi / g%mu(2)
 g%sum_integral = g%sum_integral + g%mu(1) / g%mu(2)
 g%sum_chi2 = g%sum_chi2 + g%mu(1)**2 / g%mu(2)
 g%sum_weights = g%sum_weights + 1.0 / g%mu(2)
 if (associated (g%mu_x)) then
 do i = 1, num_grids
 g%mu_x = g%mu_x + gs(i)%mu_x
 g%mu_xx = g%mu_xx + gs(i)%mu_xx
 end do
 g%sum_mu_x = g%sum_mu_x + g%mu_x / g%mu(2)
 g%sum_mu_xx = g%sum_mu_xx + g%mu_xx / g%mu(2)
 end if

```

The following is made a little bit hairy by the fact that `vamp_fork_grid` can't join grids onto a non-existing grid<sup>2</sup> therefore we have to keep a tree of joints. Maybe it would be the right thing to handle this tree of joints as a tree with pointers, but since we need the leaves flattened anyway (as food for multiple `vamp_sample_grid`) we use a similar storage layout for the joints.

100a *(Idioms 100a)≡*

```
type(vamp_grid), dimension(:), allocatable :: gx
integer, dimension(:, :,), allocatable :: dim
...
allocate (gx(vamp_fork_grid_joints (dim)))
call vamp_fork_grid (g, gs, gx, dim, exc)
...
call vamp_join_grid (g, gs, gx, dim, exc)
```

100b *(Implementation of vamp procedures 77c)≡*

```
pure recursive subroutine vamp_fork_grid_multi (g, gs, gx, d, exc)
 type(vamp_grid), intent(in) :: g
 type(vamp_grid), dimension(:), intent(inout) :: gs, gx
 integer, dimension(:, :,), intent(in) :: d
 type(exception), intent(inout), optional :: exc
 character(len=*), parameter :: FN = "vamp_fork_grid_multi"
 integer :: i, offset, stride, joints_offset, joints_stride
 select case (size (d, dim=2))
 case (0)
 return
 case (1)
 call vamp_fork_grid_single (g, gs, d(1,1), exc)
 case default
 offset = 1
 stride = product (d(2,2:))
 joints_offset = 1 + d(2,1)
 joints_stride = vamp_fork_grid_joints (d(:,2:))
 call vamp_create_empty_grid (gx(1:d(2,1)))
 call vamp_fork_grid_single (g, gx(1:d(2,1)), d(1,1), exc)
 do i = 1, d(2,1)
 call vamp_fork_grid_multi &
 (gx(i), gs(offset:offset+stride-1), &
 gx(joints_offset:joints_offset+joints_stride-1), &
 d(:,2:), exc)
 offset = offset + stride
 joints_offset = joints_offset + joints_stride
 end do
 end select
```

---

<sup>2</sup>It would be possible to make it possible by changing many things under the hood, but it doesn't really make sense, anyway.

```

 end do
 end select
end subroutine vamp_fork_grid_multi

101a <Declaration of vamp procedures 77a>+≡
public :: vamp_fork_grid_joints

$$\sum_{n=1}^{N-1} \prod_{i_n=1}^n d_{i_n} = d_1(1 + d_2(1 + d_3(1 + \dots (1 + d_{N-1}) \dots))) \quad (5.23)$$

101b <Implementation of vamp procedures 77c>+≡
pure function vamp_fork_grid_joints (d) result (s)
 integer, dimension(:, :,), intent(in) :: d
 integer :: s
 integer :: i
 s = 0
 do i = size (d, dim=2) - 1, 1, -1
 s = (s + 1) * d(2,i)
 end do
end function vamp_fork_grid_joints

101c <Implementation of vamp procedures 77c>+≡
pure recursive subroutine vamp_join_grid_multi (g, gs, gx, d, exc)
 type(vamp_grid), intent(inout) :: g
 type(vamp_grid), dimension(:,), intent(inout) :: gs, gx
 integer, dimension(:, :,), intent(in) :: d
 type(exception), intent(inout), optional :: exc
 character(len=*), parameter :: FN = "vamp_join_grid_multi"
 integer :: i, offset, stride, joints_offset, joints_stride
 select case (size (d, dim=2))
 case (0)
 return
 case (1)
 call vamp_join_grid_single (g, gs, d(1,1), exc)
 case default
 offset = 1
 stride = product (d(2,2:))
 joints_offset = 1 + d(2,1)
 joints_stride = vamp_fork_grid_joints (d(:,2:))
 do i = 1, d(2,1)
 call vamp_join_grid_multi &
 (gx(i), gs(offset:offset+stride-1), &
 gx(joints_offset:joints_offset+joints_stride-1), &
 d(:,2:), exc)
 offset = offset + stride
 end do
 end select
end subroutine vamp_join_grid_multi

```

```

 joints_offset = joints_offset + joints_stride
 end do
 call vamp_join_grid_single (g, gx(1:d(2,1)), d(1,1), exc)
 call vamp_delete_grid (gx(1:d(2,1)))
end select
end subroutine vamp_join_grid_multi

```

#### 5.2.4 Parallel Execution

102a ⟨Declaration of vamp procedures 77a⟩+≡

```

public :: vamp_sample_grid_parallel
public :: vamp_distribute_work

```

HPF [9, 10, 14]:

102b ⟨Implementation of vamp procedures 77c⟩+≡

```

subroutine vamp_sample_grid_parallel &
 (rng, g, func, prc_index, iterations, &
 integral, std_dev, avg_chi2, accuracy, &
 channel, weights, grids, exc, history)
type(tao_random_state), dimension(:), intent(inout) :: rng
type(vamp_grid), intent(inout) :: g
integer, intent(in) :: prc_index
integer, intent(in) :: iterations
real(kind=default), intent(out), optional :: integral, std_dev, avg_chi2
real(kind=default), intent(in), optional :: accuracy
integer, intent(in), optional :: channel
real(kind=default), dimension(:), intent(in), optional :: weights
type(vamp_grid), dimension(:), intent(in), optional :: grids
type(exception), intent(inout), optional :: exc
type(vamp_history), dimension(:), intent(inout), optional :: history
⟨Interface declaration for func 22⟩
character(len=*), parameter :: FN = "vamp_sample_grid_parallel"
real(kind=default) :: local_integral, local_std_dev, local_avg_chi2
type(exception), dimension(size(rng)) :: excs
type(vamp_grid), dimension(:), allocatable :: gs, gx
!hpf$ processors p(number_of_processors())
!hpf$ distribute gs(cyclic(1)) onto p
integer, dimension(:, :,), pointer :: d
integer :: iteration, i
integer :: num_workers
nullify (d)
call clear_exception (excs)
iterate: do iteration = 1, iterations

```

```

call vamp_distribute_work (size (rng), vamp_rigid_divisions (g), d)
num_workers = max (1, product (d(2,:)))
if (num_workers > 1) then
 allocate (gs(num_workers), gx(vamp_fork_grid_joints (d)))
 call vamp_create_empty_grid (gs)
 ! vamp_fork_grid is certainly not local. Speed freaks might
 ! want to tune it to the processor topology, but the gain will be small.
 call vamp_fork_grid (g, gs, gx, d, exc)
 !hpfs$ independent
 do i = 1, num_workers
 call vamp_sample_grid0 &
 (rng(i), gs(i), func, prc_index, &
 channel, weights, grids, exc)
 end do
 <Gather exceptions in vamp_sample_grid_parallel 103a>
 call vamp_join_grid (g, gs, gx, d, exc)
 call vamp_delete_grid (gs)
 deallocate (gs, gx)
else
 call vamp_sample_grid0 &
 (rng(1), g, func, prc_index, channel, weights, grids, exc)
end if
<Bail out if exception exc raised 98a>
call vamp_average_iterations &
 (g, iteration, local_integral, local_std_dev, local_avg_chi2)
<Trace results of vamp_sample_grid 105b>
<Exit iterate if accuracy has been reached 95b>
 if (iteration < iterations) call vamp_refine_grid (g)
end do iterate
deallocate (d)
<Copy results of vamp_sample_grid to dummy variables 95a>
end subroutine vamp_sample_grid_parallel

```

103a <Gather exceptions in vamp\_sample\_grid\_parallel 103a>≡  
`if ((present (exc)) .and. (any (excs(1:num_workers)%level > 0))) then  
 call gather_exceptions (exc, excs(1:num_workers))  
end if`

We could sort  $d$  such that (5.23) is minimized

$$d_1 \leq d_2 \leq \dots \leq d_N \quad (5.24)$$

but the gain will be negligible.

103b <Implementation of vamp procedures 77c>+≡  
`pure subroutine vamp_distribute_work (num_workers, ng, d)`

```

integer, intent(in) :: num_workers
integer, dimension(:), intent(in) :: ng
integer, dimension(:, :,), pointer :: d
integer, dimension(32) :: factors
integer :: n, num_factors, i, j
integer, dimension(size(ng)) :: num_forks
integer :: nfork
try: do n = num_workers, 1, -1
 call factorize (n, factors, num_factors)
 num_forks = 1
 do i = num_factors, 1, -1
 j = sum (maxloc (ng / num_forks))
 nfork = num_forks(j) * factors(i)
 if (nfork <= ng(j)) then
 num_forks(j) = nfork
 else
 cycle try
 end if
 end do
 <Accept distribution among n workers 104a>
end do try
end subroutine vamp_distribute_work

```

104a <Accept distribution among n workers 104a>≡

```

j = count (num_forks > 1)
if (associated (d)) then
 if (size (d, dim = 2) /= j) then
 deallocate (d)
 allocate (d(2,j))
 end if
else
 allocate (d(2,j))
end if

```

104b <Accept distribution among n workers 104a>+≡

```

j = 1
do i = 1, size (ng)
 if (num_forks(i) > 1) then
 d(:,j) = (/ i, num_forks(i) /)
 j = j + 1
 end if
end do
return

```

### 5.2.5 Diagnostics

- 105a *(Declaration of vamp types 105a)*≡
- ```

type, public :: vamp_history
    private
        real(kind=default) :: &
            integral, std_dev, avg_integral, avg_std_dev, avg_chi2, f_min, f_max
    integer :: calls
    logical :: stratified
    logical :: verbose
    type(div_history), dimension(:), pointer :: div => null ()
end type vamp_history

```
- 105b *(Trace results of vamp_sample_grid 105b)*≡
- ```

if (present (history)) then
 if (iteration <= size (history)) then
 call vamp_get_history &
 (history(iteration), g, local_integral, local_std_dev, &
 local_avg_chi2)
 else
 call raise_exception (exc, EXC_WARN, FN, "history too short")
 end if
 call vamp_terminate_history (history(iteration+1:))
end if

```
- 105c *(Declaration of vamp procedures 77a)*+≡
- ```

public :: vamp_create_history, vamp_copy_history, vamp_delete_history
public :: vamp_terminate_history
public :: vamp_get_history, vamp_get_history_single

```
- 105d *(Interfaces of vamp procedures 94c)*+≡
- ```

interface vamp_get_history
 module procedure vamp_get_history_single
end interface

```
- 105e *(Implementation of vamp procedures 77c)*+≡
- ```

elemental subroutine vamp_create_history (h, ndim, verbose)
    type(vamp_history), intent(out) :: h
    integer, intent(in), optional :: ndim
    logical, intent(in), optional :: verbose
    if (present (verbose)) then
        h%verbose = verbose
    else
        h%verbose = .false.
    end if
    h%calls = 0.0

```

```

    if (h%verbose .and. (present (ndim))) then
        if (associated (h%div)) then
            deallocate (h%div)
        end if
        allocate (h%div(ndim))
    end if
end subroutine vamp_create_history

106a <Implementation of vamp procedures 77c>+≡
    elemental subroutine vamp_terminate_history (h)
        type(vamp_history), intent(inout) :: h
        h%calls = 0.0
    end subroutine vamp_terminate_history

106b <Implementation of vamp procedures 77c>+≡
    pure subroutine vamp_get_history_single (h, g, integral, std_dev, avg_chi2)
        type(vamp_history), intent(inout) :: h
        type(vamp_grid), intent(in) :: g
        real(kind=default), intent(in) :: integral, std_dev, avg_chi2
        h%calls = g%calls
        h%stratified = g%all_stratified
        h%integral = g%mu(1)
        h%std_dev = sqrt (g%mu(2))
        h%avg_integral = integral
        h%avg_std_dev = std_dev
        h%avg_chi2 = avg_chi2
        h%f_min = g%f_min
        h%f_max = g%f_max
        if (h%verbose) then
            <Adjust h%div iff necessary 106c>
            call copy_history (h%div, summarize_division (g%div))
        end if
    end subroutine vamp_get_history_single

106c <Adjust h%div iff necessary 106c>≡
    if (associated (h%div)) then
        if (size (h%div) /= size (g%div)) then
            deallocate (h%div)
            allocate (h%div(size(g%div)))
        end if
    else
        allocate (h%div(size(g%div)))
    end if

106d <Declaration of vamp procedures 77a>+≡
    public :: vamp_print_history, vamp_write_history

```

```

private :: vamp_print_one_history, vamp_print_histories
! private :: vamp_write_one_history, vamp_write_histories

107a <Interfaces of vamp procedures 94c>+≡
interface vamp_print_history
    module procedure vamp_print_one_history, vamp_print_histories
end interface
interface vamp_write_history
    module procedure vamp_write_one_history_unit, vamp_write_histories_unit
end interface

107b <Implementation of vamp procedures 77c>+≡
subroutine vamp_print_one_history (h, tag)
    type(vamp_history), dimension(:), intent(in) :: h
    character(len=*), intent(in), optional :: tag
    type(div_history), dimension(:), allocatable :: h_tmp
    character(len=BUFFER_SIZE) :: pfx
    character(len=1) :: s
    integer :: i, imax, j
    if (present (tag)) then
        pfx = tag
    else
        pfx = "[vamp]"
    end if
    print "(1X,A78)", repeat ("-", 78)
    print "(1X,A8,1X,A2,A9,A1,1X,A11,1X,8X,1X, " &
           // "1X,A13,1X,8X,1X,A5,1X,A5)", &
    pfx, "it", "#calls", "", "integral", "average", "chi2", "eff."
    imax = size (h)
    iterations: do i = 1, imax
        if (h(i)%calls <= 0) then
            imax = i - 1
            exit iterations
        end if
        ! *JR: Skip zero channel
        if (h(i)%f_max==0) cycle
        if (h(i)%stratified) then
            s = "*"
        else
            s = ""
        end if
        print "(1X,A8,1X,I2,I9,A1,1X,E11.4,A1,E8.2,A1, " &
               // "1X,E13.6,A1,E8.2,A1,F5.1,1X,F5.3)", pfx, &
        i, h(i)%calls, s, h(i)%integral, "(", h(i)%std_dev, ")", &
        h(i)%avg_integral, "(", h(i)%avg_std_dev, ")", h(i)%avg_chi2, &

```

```

        h(i)%integral / h(i)%f_max
    end do iterations
    print "(1X,A78)", repeat ("-", 78)
    if (all (h%verbose) .and. (imax >= 1)) then
        if (associated (h(1)%div)) then
            allocate (h_tmp(imax))
            dimensions: do j = 1, size (h(1)%div)
                do i = 1, imax
                    call copy_history (h_tmp(i), h(i)%div(j))
                end do
                if (present (tag)) then
                    write (unit = pfx, fmt = "(A,A1,I2.2)") &
                        trim (tag(1:min(len_trim(tag),8))), "#", j
                else
                    write (unit = pfx, fmt = "(A,A1,I2.2)") "[vamp]", "#", j
                end if
                call print_history (h_tmp, tag = pfx)
                print "(1X,A78)", repeat ("-", 78)
            end do dimensions
            deallocate (h_tmp)
        end if
    end if
    flush (output_unit)
end subroutine vamp_print_one_history

```

108a <*Variables in vamp 78a*>+≡

```
integer, private, parameter :: BUFFER_SIZE = 50
```

108b <*Implementation of vamp procedures 77c*>+≡

```

subroutine vamp_print_histories (h, tag)
    type(vamp_history), dimension(:, :, ), intent(in) :: h
    character(len=*), intent(in), optional :: tag
    character(len=BUFFER_SIZE) :: pfx
    integer :: i
    print "(1X,A78)", repeat ("=", 78)
    channels: do i = 1, size (h, dim=2)
        if (present (tag)) then
            write (unit = pfx, fmt = "(A4,A1,I3.3)") tag, "#", i
        else
            write (unit = pfx, fmt = "(A4,A1,I3.3)") "chan", "#", i
        end if
        call vamp_print_one_history (h(:,i), pfx)
    end do channels
    print "(1X,A78)", repeat ("=", 78)
    flush (output_unit)

```

```
end subroutine vamp_print_histories
```

 WK

109 <Implementation of vamp procedures 77c>+≡

```
subroutine vamp_write_one_history_unit (u, h, tag)
    integer, intent(in) :: u
    type(vamp_history), dimension(:), intent(in) :: h
    character(len=*), intent(in), optional :: tag
    type(div_history), dimension(:), allocatable :: h_tmp
    character(len=BUFFER_SIZE) :: pfx
    character(len=1) :: s
    integer :: i, imax, j
    if (present (tag)) then
        pfx = tag
    else
        pfx = "[vamp]"
    end if
    write (u, "(1X,A78)") repeat ("-", 78)
    write (u, "(1X,A8,1X,A2,A9,A1,1X,A11,1X,8X,1X," &
        // "1X,A13,1X,8X,1X,A5,1X,A5)") &
        pfx, "it", "#calls", "", "integral", "average", "chi2", "eff."
    imax = size (h)
    iterations: do i = 1, imax
        if (h(i)%calls <= 0) then
            imax = i - 1
            exit iterations
        end if
        ! *WK: Skip zero channel
        if (h(i)%f_max==0) cycle
        if (h(i)%stratified) then
            s = "*"
        else
            s = ""
        end if
        write (u, "(1X,A8,1X,I2,I9,A1,1X,E11.4,A1,E8.2,A1," &
            // "1X,E13.6,A1,E8.2,A1,F5.1,1X,F5.3)") pfx, &
            i, h(i)%calls, s, h(i)%integral, "(", h(i)%std_dev, ")", &
            h(i)%avg_integral, "(", h(i)%avg_std_dev, ")", h(i)%avg_chi2, &
            h(i)%integral / h(i)%f_max
    end do iterations
    write (u, "(1X,A78)") repeat ("-", 78)
    if (all (h%verbose) .and. (imax >= 1)) then
        if (associated (h(1)%div)) then
```

```

allocate (h_tmp(imax))
dimensions: do j = 1, size (h(1)%div)
    do i = 1, imax
        call copy_history (h_tmp(i), h(i)%div(j))
    end do
    if (present (tag)) then
        write (unit = pfx, fmt = "(A,A1,I2.2)" ) &
            trim (tag(1:min(len_trim(tag),8))), "#", j
    else
        write (unit = pfx, fmt = "(A,A1,I2.2)" ) "[vamp]", "#", j
    end if
    call write_history (u, h_tmp, tag = pfx)
    print "(1X,A78)", repeat ("-", 78)
end do dimensions
deallocate (h_tmp)
end if
end if
flush (u)
end subroutine vamp_write_one_history_unit
subroutine vamp_write_histories_unit (u, h, tag)
    integer, intent(in) :: u
    type(vamp_history), dimension(:, :, ), intent(in) :: h
    character(len=*), intent(in), optional :: tag
    character(len=BUFFER_SIZE) :: pfx
    integer :: i
    write (u, "(1X,A78)" ) repeat ("=", 78)
    channels: do i = 1, size (h, dim=2)
        if (present (tag)) then
            write (unit = pfx, fmt = "(A4,A1,I3.3)" ) tag, "#", i
        else
            write (unit = pfx, fmt = "(A4,A1,I3.3)" ) "chan", "#", i
        end if
        call vamp_write_one_history_unit (u, h(:, i), pfx)
    end do channels
    write (u, "(1X,A78)" ) repeat ("=", 78)
    flush (u)
end subroutine vamp_write_histories_unit

```

5.2.6 Multi Channel

[22]

$$g(x) = \sum_i \alpha_i g_i(x) \quad (5.25a)$$

$$w(x) = \frac{f(x)}{g(x)} \quad (5.25b)$$

We want to minimize the variance $W(\alpha)$ with the subsidiary condition $\sum_i \alpha_i = 1$. We introduce a Lagrange multiplier λ :

$$\tilde{W}(\alpha) = W(\alpha) + \lambda \left(\sum_i \alpha_i - 1 \right) \quad (5.26)$$

Therefore...

$$W_i(\alpha) = -\frac{\partial}{\partial \alpha_i} W(\alpha) = \int dx g_i(x)(w(x))^2 \approx \left\langle \frac{g_i(x)}{g(x)} (w(x))^2 \right\rangle \quad (5.27)$$

 Here it *really* hurts that **Fortran** has no *first-class* functions. The following can be expressed much more elegantly in a functional programming language with *first-class* functions, currying and closures. **Fortran** makes it extra painful since not even procedure pointers are supported. This puts extra burden on the users of this library.

Note that the components of **vamp_grids** are not protected. However, this is not a license for application programs to access it. Only Other libraries (e.g. for parallel processing, like **vampi**) should do so.

111a *(Declaration of vamp types 105a)+≡*

```
type, public :: vamp_grids
  !!! private ! used by vampi
  real(kind=default), dimension(:), pointer :: weights => null ()
  type(vamp_grid), dimension(:), pointer :: grids => null ()
  integer, dimension(:), pointer :: num_calls => null ()
  real(kind=default) :: sum_chi2, sum_integral, sum_weights
end type vamp_grids
```

$$g \circ \phi_i = \left| \frac{\partial \phi_i}{\partial x} \right|^{-1} \left(\alpha_i g_i + \sum_{\substack{j=1 \\ j \neq i}}^{N_c} \alpha_j (g_j \circ \pi_{ij}) \left| \frac{\partial \pi_{ij}}{\partial x} \right| \right). \quad (5.28)$$

111b *(Declaration of vamp procedures 77a)+≡*

```
public :: vamp_multi_channel, vamp_multi_channel0
```

112a *(Implementation of vamp procedures 77c)*+≡

```
pure function vamp_multi_channel &
    (func, prc_index, phi, ihp, jacobian, x, weights, channel, grids) result (w_x)
    integer, intent(in) :: prc_index
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:), intent(in) :: weights
    integer, intent(in) :: channel
    type(vamp_grid), dimension(:), intent(in) :: grids
    <Interface declaration for func 22>
    <Interface declaration for phi 31a>
    <Interface declaration for ihp 31b>
    <Interface declaration for jacobian 31c>
    real(kind=default) :: w_x
    integer :: i
    real(kind=default), dimension(size(x)) :: phi_x
    real(kind=default), dimension(size(weights)) :: g_phi_x, g_pi_x
    phi_x = phi (x, channel)
    do i = 1, size (weights)
        if (i == channel) then
            g_pi_x(i) = vamp_probability (grids(i), x)
        else
            g_pi_x(i) = vamp_probability (grids(i), ihp (phi_x, i))
        end if
    end do
    do i = 1, size (weights)
        g_phi_x(i) = g_pi_x(i) / g_pi_x(channel) * jacobian (phi_x, prc_index, i)
    end do
    w_x = func (phi_x, prc_index, weights, channel, grids) &
        / dot_product (weights, g_phi_x)
end function vamp_multi_channel
```

112b *(Implementation of vamp procedures 77c)*+≡

```
pure function vamp_multi_channel10 &
    (func, prc_index, phi, jacobian, x, weights, channel) result (w_x)
    integer, intent(in) :: prc_index
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:), intent(in) :: weights
    integer, intent(in) :: channel
    <Interface declaration for func 22>
    <Interface declaration for phi 31a>
    <Interface declaration for jacobian 31c>
    real(kind=default) :: w_x
    real(kind=default), dimension(size(x)) :: x_prime
    real(kind=default), dimension(size(weights)) :: g_phi_x
```

```

integer :: i
x_prime = phi (x, channel)
do i = 1, size (weights)
    g_phi_x(i) = jacobian (x_prime, prc_index, i)
end do
w_x = func (x_prime, prc_index) / dot_product (weights, g_phi_x)
end function vamp_multi_channel0

```

 WK

113a *<Declaration of vamp procedures 77a>+≡*

```
public :: vamp_jacobian, vamp_check_jacobian
```

113b *<Implementation of vamp procedures 77c>+≡*

```

pure subroutine vamp_jacobian (phi, channel, x, region, jacobian, delta_x)
    integer, intent(in) :: channel
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:, :), intent(in) :: region
    real(kind=default), intent(out) :: jacobian
    real(kind=default), intent(in), optional :: delta_x
    interface
        function phi (xi, channel) result (x)
            use kinds
            real(kind=default), dimension(:), intent(in) :: xi
            integer, intent(in) :: channel
            real(kind=default), dimension(size(xi)) :: x
        end function phi
    end interface
    real(kind=default), dimension(size(x)) :: x_min, x_max
    real(kind=default), dimension(size(x)) :: x_plus, x_minus
    real(kind=default), dimension(size(x),size(x)) :: d_phi
    real(kind=default), parameter :: &
        dx_default = 10.0_default**(-precision(jacobian)/3)
    real(kind=default) :: dx
    integer :: j
    if (present (delta_x)) then
        dx = delta_x
    else
        dx = dx_default
    end if
    x_min = region(1,:)
    x_max = region(2,:)
    x_minus = max (x_min, x)
    x_plus = min (x_max, x)

```

```

do j = 1, size (x)
    x_minus(j) = max (x_min(j), x(j) - dx)
    x_plus(j) = min (x_max(j), x(j) + dx)
    d_phi(:,j) = (phi (x_plus, channel) - phi (x_minus, channel)) &
        / (x_plus(j) - x_minus(j))
    x_minus(j) = max (x_min(j), x(j))
    x_plus(j) = min (x_max(j), x(j))
end do
call determinant (d_phi, jacobian)
jacobian = abs (jacobian)
end subroutine vamp_jacobian

```

$$g(\phi(x)) = \frac{1}{|\frac{\partial \phi}{\partial x}|(x)} \quad (5.29)$$

114 <Implementation of vamp procedures 77c>+≡

```

pure subroutine vamp_check_jacobian &
    (rng, n, func, prc_index, phi, channel, region, delta, x_delta)
type(tao_random_state), intent(inout) :: rng
integer, intent(in) :: n
integer, intent(in) :: prc_index
integer, intent(in) :: channel
real(kind=default), dimension(:, :, ), intent(in) :: region
real(kind=default), intent(out) :: delta
real(kind=default), dimension(:, ), intent(out), optional :: x_delta
<Interface declaration for func 22>
<Interface declaration for phi 31a>
real(kind=default), dimension(size(region, dim=2)) :: x, r
real(kind=default) :: jac, d
real(kind=default), dimension(0) :: wgts
integer :: i
delta = 0.0
do i = 1, max (1, n)
    call tao_random_number (rng, r)
    x = region(1,:) + (region(2,:) - region(1,:)) * r
    call vamp_jacobian (phi, channel, x, region, jac)
    d = func (phi (x, channel), prc_index, wgts, channel) * jac &
        - 1.0_default
    if (abs (d) >= abs (delta)) then
        delta = d
        if (present (x_delta)) then
            x_delta = x
        end if
    end if
end do

```

```
    end subroutine vamp_check_jacobian
```

This is a subroutine to comply with F's rules, otherwise, we would code it as a function.

115a *(Declaration of vamp procedures (removed from WHIZARD) 115a)*≡
 private :: numeric_jacobian

115b *(Implementation of vamp procedures (removed from WHIZARD) 115b)*≡
 pure subroutine numeric_jacobian (phi, channel, x, region, jacobian, delta_x)
 integer, intent(in) :: channel
 real(kind=default), dimension(:), intent(in) :: x
 real(kind=default), dimension(:, :,), intent(in) :: region
 real(kind=default), intent(out) :: jacobian
 real(kind=default), intent(in), optional :: delta_x
 <Interface declaration for phi 31a>
 real(kind=default), dimension(size(x)) :: x_min, x_max
 real(kind=default), dimension(size(x)) :: x_plus, x_minus
 real(kind=default), dimension(size(x), size(x)) :: d_phi
 real(kind=default), parameter :: &
 dx_default = 10.0_default**(-precision(jacobian)/3)
 real(kind=default) :: dx
 integer :: j
 if (present (delta_x)) then
 dx = delta_x
 else
 dx = dx_default
 end if
 x_min = region(1,:)
 x_max = region(2,:)
 x_minus = max (x_min, x)
 x_plus = min (x_max, x)
 do j = 1, size (x)
 x_minus(j) = max (x_min(j), x(j) - dx)
 x_plus(j) = min (x_max(j), x(j) + dx)
 d_phi(:, j) = (phi (x_plus, channel) - phi (x_minus, channel)) &
 / (x_plus(j) - x_minus(j))
 x_minus(j) = max (x_min(j), x(j))
 x_plus(j) = min (x_max(j), x(j))
 end do
 call determinant (d_phi, jacobian)
 jacobian = abs (jacobian)
 end subroutine numeric_jacobian

115c *(Declaration of vamp procedures 77a)*+≡
 public :: vamp_create_grids, vamp_create_empty_grids

```
public :: vamp_copy_grids, vamp_delete_grids
```

The rules for optional arguments forces us to handle special cases, because we can't just pass a array section of an optional array as an actual argument (cf. 12.4.1.5(4) in [8]) even if the dummy argument is optional itself.

- 116a *Implementation of vamp procedures 77c*+≡
- ```
pure subroutine vamp_create_grids &
 (g, domain, num_calls, weights, maps, num_div, &
 stratified, quadrupole, exc)
 type(vamp_grids), intent(inout) :: g
 real(kind=default), dimension(:,:), intent(in) :: domain
 integer, intent(in) :: num_calls
 real(kind=default), dimension(:,), intent(in) :: weights
 real(kind=default), dimension(:,:,:), intent(in), optional :: maps
 integer, dimension(:,), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole
 type(exception), intent(inout), optional :: exc
 character(len=*), parameter :: FN = "vamp_create_grids"
 integer :: ch, nch
 nch = size (weights)
 allocate (g%grids(nch), g%weights(nch), g%num_calls(nch))
 g%weights = weights / sum (weights)
 g%num_calls = g%weights * num_calls
 do ch = 1, size (g%grids)
 if (present (maps)) then
 call vamp_create_grid &
 (g%grids(ch), domain, g%num_calls(ch), num_div, &
 stratified, quadrupole, map = maps(:,:,ch), exc = exc)
 else
 call vamp_create_grid &
 (g%grids(ch), domain, g%num_calls(ch), num_div, &
 stratified, quadrupole, exc = exc)
 end if
 end do
 g%sum_integral = 0.0
 g%sum_chi2 = 0.0
 g%sum_weights = 0.0
end subroutine vamp_create_grids
```
- 116b *Implementation of vamp procedures 77c*+≡
- ```
pure subroutine vamp_create_empty_grids (g)
    type(vamp_grids), intent(inout) :: g
    nullify (g%grids, g%weights, g%num_calls)
end subroutine vamp_create_empty_grids
```

117a *(Declaration of vamp procedures 77a)*+≡
 public :: vamp_discard_integrals

117b *(Implementation of vamp procedures 77c)*+≡
 pure subroutine vamp_discard_integrals &
 (g, num_calls, num_div, stratified, quadrupole, exc, eq)
 type(vamp_grids), intent(inout) :: g
 integer, intent(in), optional :: num_calls
 integer, dimension(:), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole
 type(exception), intent(inout), optional :: exc
 type(vamp_equivalences_t), intent(in), optional :: eq
 integer :: ch
 character(len=*), parameter :: FN = "vamp_discard_integrals"
 g%sum_integral = 0.0
 g%sum_weights = 0.0
 g%sum_chi2 = 0.0
 do ch = 1, size (g%grids)
 call vamp_discard_integral (g%grids(ch))
 end do
 if (present (num_calls)) then
 call vamp_reshape_grids &
 (g, num_calls, num_div, stratified, quadrupole, exc, eq)
 end if
 end subroutine vamp_discard_integrals

117c *(Declaration of vamp procedures 77a)*+≡
 public :: vamp_update_weights

We must discard the accumulated integrals, because the weight function $w = f / \sum_i \alpha_i g_i$ changes:

117d *(Implementation of vamp procedures 77c)*+≡
 pure subroutine vamp_update_weights &
 (g, weights, num_calls, num_div, stratified, quadrupole, exc)
 type(vamp_grids), intent(inout) :: g
 real(kind=default), dimension(:), intent(in) :: weights
 integer, intent(in), optional :: num_calls
 integer, dimension(:), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole
 type(exception), intent(inout), optional :: exc
 character(len=*), parameter :: FN = "vamp_update_weights"
 if (sum (weights) > 0) then
 g%weights = weights / sum (weights)
 else
 g%weights = 1._default / size(g%weights)

```

    end if
    if (present (num_calls)) then
        call vamp_discard_integrals (g, num_calls, num_div, &
                                     stratified, quadrupole, exc)
    else
        call vamp_discard_integrals (g, sum (g%num_calls), num_div, &
                                     stratified, quadrupole, exc)
    end if
end subroutine vamp_update_weights

118a <Declaration of vamp procedures 77a>+≡
public :: vamp_reshape_grids

118b <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_reshape_grids &
    (g, num_calls, num_div, stratified, quadrupole, exc, eq)
    type(vamp_grids), intent(inout) :: g
    integer, intent(in) :: num_calls
    integer, dimension(:), intent(in), optional :: num_div
    logical, intent(in), optional :: stratified, quadrupole
    type(exception), intent(inout), optional :: exc
    type(vamp_equivalences_t), intent(in), optional :: eq
    integer, dimension(size(g%grids(1)%num_div)) :: num_div_new
    integer :: ch
    character(len=*), parameter :: FN = "vamp_reshape_grids"
    g%num_calls = g%weights * num_calls
    do ch = 1, size (g%grids)
        if (g%num_calls(ch) >= 2) then
            if (present (eq)) then
                if (present (num_div)) then
                    num_div_new = num_div
                else
                    num_div_new = g%grids(ch)%num_div
                end if
                where (eq%div_isInvariant(ch,:))
                    num_div_new = 1
                end where
                call vamp_reshape_grid (g%grids(ch), g%num_calls(ch), &
                                      num_div_new, stratified, quadrupole, exc = exc, &
                                      independent = eq%independent(ch), &
                                      equivalent_to_ch = eq%equivalent_to_ch(ch), &
                                      multiplicity = eq%multiplicity(ch))
            else
                call vamp_reshape_grid (g%grids(ch), g%num_calls(ch), &
                                      num_div, stratified, quadrupole, exc = exc)
            end if
        end if
    end do
end subroutine vamp_reshape_grids

```

```

        end if
    else
        g%num_calls(ch) = 0
    end if
end do
end subroutine vamp_reshape_grids

```

119a *<Declaration of vamp procedures 77a>+≡*
`public :: vamp_sample_grids`

Even if `g%num_calls` is derived from `g%weights`, we must *not* use the latter, allow for integer arithmetic in `g%num_calls`.

119b *<Implementation of vamp procedures 77c>+≡*
`pure subroutine vamp_sample_grids &`
`(rng, g, func, prc_index, iterations, integral, std_dev, avg_chi2, &`
`accuracy, history, histories, exc, eq, warn_error, negative_weights)`
`type(tao_random_state), intent(inout) :: rng`
`type(vamp_grids), intent(inout) :: g`
`integer, intent(in) :: prc_index`
`integer, intent(in) :: iterations`
`real(kind=default), intent(out), optional :: integral, std_dev, avg_chi2`
`real(kind=default), intent(in), optional :: accuracy`
`type(vamp_history), dimension(:), intent(inout), optional :: history`
`type(vamp_history), dimension(:, :), intent(inout), optional :: histories`
`type(exception), intent(inout), optional :: exc`
`type(vamp_equivalences_t), intent(in), optional :: eq`
`logical, intent(in), optional :: warn_error, negative_weights`
<Interface declaration for func 22>
`integer :: ch, iteration`
`logical :: neg_w`
`type(exception), dimension(size(g%grids)) :: excs`
`logical, dimension(size(g%grids)) :: active`
`real(kind=default), dimension(size(g%grids)) :: weights, integrals, std_devs`
`real(kind=default) :: local_integral, local_std_dev, local_avg_chi2`
`character(len=*), parameter :: FN = "vamp_sample_grids"`
`integrals = 0`
`std_devs = 0`
`neg_w = .false.`
`if (present (negative_weights)) neg_w = negative_weights`
`active = (g%num_calls >= 2)`
`where (active)`
 `weights = g%num_calls`
`elsewhere`
 `weights = 0.0`

```

endwhere
if (sum (weights) /= 0) weights = weights / sum (weights)
call clear_exception (excs)
iterate: do iteration = 1, iterations
    do ch = 1, size (g%grids)
        if (active(ch)) then
            call vamp_discard_integral (g%grids(ch))
            (Sample the grid g%grids(ch) 120)
        else
            call vamp_nullify_variance (g%grids(ch))
            call vamp_nullify_covariance (g%grids(ch))
        end if
    end do
    if (present(eq)) call vamp_apply_equivalences (g, eq)
    if (iteration < iterations) then
        do ch = 1, size (g%grids)
            active(ch) = (integrals(ch) /= 0)
            if (active(ch)) then
                call vamp_refine_grid (g%grids(ch))
            end if
        end do
    end if
    if (present (exc) .and. (any (excs%level > 0))) then
        call gather_exceptions (exc, excs)
    !       return
    end if
    call vamp_reduce_channels (g, integrals, std_devs, active)
    call vamp_average_iterations &
        (g, iteration, local_integral, local_std_dev, local_avg_chi2)
        (Trace results of vamp_sample_grids 123b)
        (Exit iterate if accuracy has been reached 95b)
    end do iterate
    (Copy results of vamp_sample_grid to dummy variables 95a)
end subroutine vamp_sample_grids

```

We must refine the grids after *all* grids have been sampled, therefore we use `vamp_sample_grid0` instead of `vamp_sample_grid`:

120 *(Sample the grid g%grids(ch) 120)≡*
`call vamp_sample_grid0 &`
 `(rng, g%grids(ch), func, prc_index, &`
 `ch, weights, g%grids, excs(ch), neg_w)`
`if (present (exc) .and. present (warn_error)) then`
 `if (warn_error) call handle_exception (excs(ch))`

```

    end if
    call vamp_average_iterations &
        (g%grids(ch), iteration, integrals(ch), std_devs(ch), local_avg_chi2)
if (present (histories)) then
    if (iteration <= ubound (histories, dim=1)) then
        call vamp_get_history &
            (histories(iteration,ch), g%grids(ch), &
            integrals(ch), std_devs(ch), local_avg_chi2)
    else
        call raise_exception (exc, EXC_WARN, FN, "history too short")
    end if
    call vamp_terminate_history (histories(iteration+1:,ch))
end if

```

121a *(Declaration of vamp procedures 77a)* +≡

```
public :: vamp_reduce_channels
```

$$I = \frac{1}{N} \sum_c N_c I_c \quad (5.30a)$$

$$\sigma^2 = \frac{1}{N^2} \sum_c N_c^2 \sigma_c^2 \quad (5.30b)$$

$$N = \sum_c N_c \quad (5.30c)$$

where (5.30b) is actually

$$\sigma^2 = \frac{1}{N} (\mu_2 - \mu_1^2) = \frac{1}{N} \left(\frac{1}{N} \sum_c N_c \mu_{2,c} - I^2 \right) = \frac{1}{N} \left(\frac{1}{N} \sum_c (N_c^2 \sigma_c^2 + N_c I_c^2) - I^2 \right)$$

but the latter form suffers from numerical instability and (5.30b) is thus preferred.

121b *(Implementation of vamp procedures 77c)* +≡

```

pure subroutine vamp_reduce_channels (g, integrals, std_devs, active)
    type(vamp_grids), intent(inout) :: g
    real(kind=default), dimension(:), intent(in) :: integrals, std_devs
    logical, dimension(:), intent(in) :: active
    real(kind=default) :: this_integral, this_weight, total_calls
    real(kind=default) :: total_variance
    if (.not.any(active)) return
    total_calls = sum (g%num_calls, mask=active)
    if (total_calls > 0) then
        this_integral = sum (g%num_calls * integrals, mask=active) / total_calls
    end if
end subroutine

```

```

        else
            this_integral = 0
        end if
        total_variance = sum ((g%num_calls*std_devs)**2, mask=active)
        if (total_variance > 0) then
            this_weight = total_calls**2 / total_variance
        else
            this_weight = 0
        end if
        g%sum_weights = g%sum_weights + this_weight
        g%sum_integral = g%sum_integral + this_weight * this_integral
        g%sum_chi2 = g%sum_chi2 + this_weight * this_integral**2
    end subroutine vamp_reduce_channels

122a <Declaration of vamp procedures 77a>+≡
    public :: vamp_refine_weights

122b <Implementation of vamp procedures 77c>+≡
    elemental subroutine vamp_average_iterations_grids &
        (g, iteration, integral, std_dev, avg_chi2)
    type(vamp_grids), intent(in) :: g
    integer, intent(in) :: iteration
    real(kind=default), intent(out) :: integral, std_dev, avg_chi2
    real(kind=default), parameter :: eps = 1000 * epsilon (1._default)
    if (g%sum_weights>0) then
        integral = g%sum_integral / g%sum_weights
        std_dev = sqrt (1.0 / g%sum_weights)
        avg_chi2 = &
            max ((g%sum_chi2 - g%sum_integral * integral) / (iteration-0.99), &
            0.0_default)
        if (avg_chi2 < eps * g%sum_chi2)  avg_chi2 = 0
    else
        integral = 0
        std_dev = 0
        avg_chi2 = 0
    end if
    end subroutine vamp_average_iterations_grids

122c <Declaration of vamp procedures 77a>+≡
    private :: vamp_average_iterations_grids

122d <Interfaces of vamp procedures 94c>+≡
    interface vamp_average_iterations
        module procedure  vamp_average_iterations_grids
    end interface

```

$$\alpha_i \rightarrow \alpha_i \sqrt{V_i} \quad (5.31)$$

- 123a *(Implementation of vamp procedures 77c)*+≡
- ```
pure subroutine vamp_refine_weights (g, power)
 type(vamp_grids), intent(inout) :: g
 real(kind=default), intent(in), optional :: power
 real(kind=default) :: local_power
 real(kind=default), parameter :: DEFAULT_POWER = 0.5_default
 if (present (power)) then
 local_power = power
 else
 local_power = DEFAULT_POWER
 end if
 call vamp_update_weights &
 (g, g%weights * vamp_get_variance (g%grids) ** local_power)
end subroutine vamp_refine_weights
```
- 123b *(Trace results of vamp\_sample\_grids 123b)*≡
- ```
if (present (history)) then
    if (iteration <= size (history)) then
        call vamp_get_history &
            (history(iteration), g, local_integral, local_std_dev, &
            local_avg_chi2)
    else
        call raise_exception (exc, EXC_WARN, FN, "history too short")
    end if
    call vamp_terminate_history (history(iteration+1:))
end if
```
- 123c *(Declaration of vamp procedures 77a)*+≡
- ```
private :: vamp_get_history_multi
```
- 123d *(Interfaces of vamp procedures 94c)*+≡
- ```
interface vamp_get_history
    module procedure vamp_get_history_multi
end interface
```
- 123e *(Implementation of vamp procedures 77c)*+≡
- ```
pure subroutine vamp_get_history_multi (h, g, integral, std_dev, avg_chi2)
 type(vamp_history), intent(inout) :: h
 type(vamp_grids), intent(in) :: g
 real(kind=default), intent(in) :: integral, std_dev, avg_chi2
 h%calls = sum (g%grids%calls)
 h%stratified = all (g%grids%all_stratified)
 h%integral = 0.0
 h%std_dev = 0.0
```

```

h%avg_integral = integral
h%avg_std_dev = std_dev
h%avg_chi2 = avg_chi2
h%f_min = 0.0
h%f_max = huge (h%f_max)
if (h%verbose) then
 h%verbose = .false.
 if (associated (h%div)) then
 deallocate (h%div)
 end if
end if
end subroutine vamp_get_history_multi

```

 WK

124a <*Declaration of vamp procedures 77a*>+≡  
 public :: vamp\_sum\_channels

124b <*Implementation of vamp procedures 77c*>+≡  
 pure function vamp\_sum\_channels (x, weights, func, prc\_index, grids) result (g)  
 real(kind=default), dimension(:), intent(in) :: x, weights  
 integer, intent(in) :: prc\_index  
 type(vamp\_grid), dimension(:), intent(in), optional :: grids  
 interface  
 function func (xi, prc\_index, weights, channel, grids) result (f)  
 use kinds  
 use vamp\_grid\_type !NODEP!  
 real(kind=default), dimension(:), intent(in) :: xi  
 integer, intent(in) :: prc\_index  
 real(kind=default), dimension(:), intent(in), optional :: weights  
 integer, intent(in), optional :: channel  
 type(vamp\_grid), dimension(:), intent(in), optional :: grids  
 real(kind=default) :: f  
 end function func  
 end interface  
 real(kind=default) :: g  
 integer :: ch  
 g = 0.0  
 do ch = 1, size (weights)  
 g = g + weights(ch) \* func (x, prc\_index, weights, ch, grids)
 end do
end function vamp\_sum\_channels

### 5.2.7 Mapping

 This section is still under construction. The basic algorithm is in place, but the heuristics have not been developed yet.

The most naive approach is to use the rotation matrix  $R$  that diagonalizes the covariance  $C$ :

$$R_{ij} = (v_j)_i \quad (5.32)$$

where

$$Cv_j = \lambda_j v_j \quad (5.33)$$

with the eigenvalues  $\{\lambda_j\}$  and eigenvectors  $\{v_j\}$ . Then

$$R^T C R = \text{diag}(\lambda_1, \dots) \quad (5.34)$$

After call `diagonalize_real_symmetric (cov, evals, evecs)`, we have `evals(j) = λ_j` and `evecs(:,j) = v_j`. This is equivalent with `evecs(i,j) = R_ij`.

This approach will not work in high dimensions, however. In general,  $R$  will *not* leave most of the axes invariant, even if the covariance matrix is almost isotropic in these directions. In this case the benefit from the rotation is rather small and offset by the negative effects from the misalignment of the integration region.

A better strategy is to find the axis of the original coordinate system around which a rotation is most beneficial. There are two extreme cases:

- “pancake”: one eigenvalue much smaller than the others
- “cigar”: one eigenvalue much larger than the others

Actually, instead of rotating around a specific axis, we can as well diagonalize in a subspace. Empirically, rotation around an axis is better than diagonalizing in a two-dimensional subspace, but diagonalizing in a three-dimensional subspace can be even better.

125a *(Declaration of vamp procedures 77a)* +≡  
`public :: select_rotation_axis`  
`public :: select_rotation_subspace`

125b *(Set iv to the index of the optimal eigenvector 125b)* +≡  
`if (num_pancake > 0) then`  
 `print *, "FORCED PANCAKE: ", num_pancake`  
 `iv = sum (minloc (evals))`  
`else if (num_cigar > 0) then`  
 `print *, "FORCED CIGAR: ", num_cigar`

```

 iv = sum (maxloc (evals))
 else
 call more_pancake_than_cigar (evals, like_pancake)
 if (like_pancake) then
 iv = sum (minloc (evals))
 else
 iv = sum (maxloc (evals))
 end if
 end if

```

126a *(Implementation of vamp procedures 77c)* +≡

```

subroutine more_pancake_than_cigar (eval, yes_or_no)
 real(kind=default), dimension(:,), intent(in) :: eval
 logical, intent(out) :: yes_or_no
 integer, parameter :: N_CL = 2
 real(kind=default), dimension(size(eval)) :: evals
 real(kind=default), dimension(N_CL) :: cluster_pos
 integer, dimension(N_CL,2) :: clusters
 evals = eval
 call sort (evals)
 call condense (evals, cluster_pos, clusters)
 print *, clusters(1,2) - clusters(1,1) + 1, "small EVs: ", &
 evals(clusters(1,1):clusters(1,2))
 print *, clusters(2,2) - clusters(2,1) + 1, "large EVs: ", &
 evals(clusters(2,1):clusters(2,2))
 if ((clusters(1,2) - clusters(1,1)) &
 < (clusters(2,2) - clusters(2,1))) then
 print *, " => PANCAKE!"
 yes_or_no = .true.
 else
 print *, " => CIGAR!"
 yes_or_no = .false.
 end if
end subroutine more_pancake_than_cigar

```

126b *(Declaration of vamp procedures 77a)* +≡

```

private :: more_pancake_than_cigar

```

In both cases, we can rotate in the plane  $P_{ij}$  closest to eigenvector corresponding to the the singled out eigenvalue. This plane is given by

$$\max_{i \neq i'} \sqrt{(v_j)_i^2 + (v_j)_{i'}^2} \quad (5.35)$$

which is simply found by looking for the two largest  $|(v_j)_i|$ :<sup>3</sup>

127a *(Set i(1), i(2) to the axes of the optimal plane 127a)*≡

```
abs_evec = abs (evecs(:,iv))
i(1) = sum (maxloc (abs_evec))
abs_evec(i(1)) = -1.0
i(2) = sum (maxloc (abs_evec))
```

The following is cute, but unfortunately broken, since it fails for degenerate eigenvalues:

127b *(Set i(1), i(2) to the axes of the optimal plane (broken!) 127b)*≡

```
abs_evec = abs (evecs(:,iv))
i(1) = sum (maxloc (abs_evec))
i(2) = sum (maxloc (abs_evec, mask = abs_evec < abs_evec(i(1))))
```

127c *(Set i(1), i(2) to the axes of the optimal plane 127a)*+≡

```
print *, iv, evals(iv), " => ", evecs(:,iv)
print *, i(1), abs_evec(i(1)), " ", " , i(2), abs_evec(i(2))
print *, i(1), evecs(i(1),iv), " ", " , i(2), evecs(i(2),iv)
```

127d *(Get cos θ and sin θ from evecs 127d)*≡

```
cos_theta = evecs(i(1),iv)
sin_theta = evecs(i(2),iv)
norm = 1.0 / sqrt (cos_theta**2 + sin_theta**2)
cos_theta = cos_theta * norm
sin_theta = sin_theta * norm
```

$$\hat{R}(\theta; i, j) = \begin{pmatrix} 1 & & & & \\ & \ddots & & & \\ & & \cos \theta & \dots & -\sin \theta \\ & & \vdots & 1 & \vdots \\ & & \sin \theta & \dots & \cos \theta \\ & & & & \ddots \\ & & & & 1 \end{pmatrix} \quad (5.36)$$

127e *(Construct  $\hat{R}(\theta; i, j)$  127e)*≡

```
call unit (r)
r(i(1),i) = (/ cos_theta, - sin_theta /)
r(i(2),i) = (/ sin_theta, cos_theta /)
```

127f *(Implementation of vamp procedures 77c)*+≡

```
subroutine select_rotation_axis (cov, r, pancake, cigar)
 real(kind=default), dimension(:, :), intent(in) :: cov
 real(kind=default), dimension(:, :), intent(out) :: r
```

---

<sup>3</sup>The `sum` intrinsic is a convenient Fortran90 trick for turning the rank-one array with one element returned by `maxloc` into its value. It has no semantic significance.

```

 integer, intent(in), optional :: pancake, cigar
 integer :: num_pancake, num_cigar
 logical :: like_pancake
 real(kind=default), dimension(size(cov,dim=1),size(cov,dim=2)) :: evecs
 real(kind=default), dimension(size(cov,dim=1)) :: evals, abs_evec
 integer :: iv
 integer, dimension(2) :: i
 real(kind=default) :: cos_theta, sin_theta, norm
 <Handle optional pancake and cigar 128a>
 call diagonalize_real_symmetric (cov, evals, evecs)
 <Set iv to the index of the optimal eigenvector 125b>
 <Set i(1), i(2) to the axes of the optimal plane 127a>
 <Get cos θ and sin θ from evecs 127d>
 <Construct $\hat{R}(\theta; i, j)$ 127e>
end subroutine select_rotation_axis

```

128a <Handle optional pancake and cigar 128a>≡

```

 if (present (pancake)) then
 num_pancake = pancake
 else
 num_pancake = -1
 endif
 if (present (cigar)) then
 num_cigar = cigar
 else
 num_cigar = -1
 endif

```

Here's a less efficient version that can be easily generalized to more than two dimension, however:

128b <Implementation of vamp procedures 77c>+≡

```

subroutine select_subspace_explicit (cov, r, subspace)
 real(kind=default), dimension(:, :,), intent(in) :: cov
 real(kind=default), dimension(:, :,), intent(out) :: r
 integer, dimension(:), intent(in) :: subspace
 real(kind=default), dimension(size(subspace)) :: eval_sub
 real(kind=default), dimension(size(subspace), size(subspace)) :: &
 cov_sub, evec_sub
 cov_sub = cov(subspace, subspace)
 call diagonalize_real_symmetric (cov_sub, eval_sub, evec_sub)
 call unit (r)
 r(subspace, subspace) = evec_sub
end subroutine select_subspace_explicit

```

128c <Implementation of vamp procedures 77c>+≡

```

subroutine select_subspace_guess (cov, r, ndim, pancake, cigar)
 real(kind=default), dimension(:,:), intent(in) :: cov
 real(kind=default), dimension(:,:), intent(out) :: r
 integer, intent(in) :: ndim
 integer, intent(in), optional :: pancake, cigar
 integer :: num_pancake, num_cigar
 logical :: like_pancake
 real(kind=default), dimension(size(cov,dim=1),size(cov,dim=2)) :: evecs
 real(kind=default), dimension(size(cov,dim=1)) :: evals, abs_evec
 integer :: iv, i
 integer, dimension(ndim) :: subspace
 <Handle optional pancake and cigar 128a>
 call diagonalize_real_symmetric (cov, evals, evecs)
 <Set iv to the index of the optimal eigenvector 125b>
 <Set subspace to the axes of the optimal plane 129a>
 call select_subspace_explicit (cov, r, subspace)
end subroutine select_subspace_guess

```

129a <*Set subspace to the axes of the optimal plane 129a*>≡

```

abs_evec = abs (evecs(:,iv))
subspace(1) = sum (maxloc (abs_evec))
do i = 2, ndim
 abs_evec(subspace(i-1)) = -1.0
 subspace(i) = sum (maxloc (abs_evec))
end do

```

129b <*Interfaces of vamp procedures 94c*>+≡

```

interface select_rotation_subspace
 module procedure select_subspace_explicit, select_subspace_guess
end interface

```

129c <*Declaration of vamp procedures 77a*>+≡

```

private :: select_subspace_explicit
private :: select_subspace_guess

```

129d <*Declaration of vamp procedures 77a*>+≡

```

public :: vamp_print_covariance

```

129e <*Implementation of vamp procedures 77c*>+≡

```

subroutine vamp_print_covariance (cov)
 real(kind=default), dimension(:,:), intent(in) :: cov
 real(kind=default), dimension(size(cov,dim=1)) :: &
 evals, abs_evals, tmp
 real(kind=default), dimension(size(cov,dim=1),size(cov,dim=2)) :: &
 evecs, abs_evecs
 integer, dimension(size(cov,dim=1)) :: idx

```

```

integer :: i, i_max, j
i_max = size (evals)
call diagonalize_real_symmetric (cov, evals, evecs)
call sort (evals, evecs)
abs_evals = abs (evals)
abs_evecs = abs (evecs)
print "(1X,A78)", repeat ("-", 78)
print "(1X,A)", "Eigenvalues and eigenvectors:"
print "(1X,A78)", repeat ("-", 78)
do i = 1, i_max
 print "(1X,I2,A1,1X,E11.4,1X,A1,10(10(1X,F5.2)/,18X))", &
 i, ":", evals(i), "|", evecs(:,i)
end do
print "(1X,A78)", repeat ("-", 78)
print "(1X,A)", "Approximate subspaces:"
print "(1X,A78)", repeat ("-", 78)
do i = 1, i_max
 idx = (/ (j, j=1,i_max) /)
 tmp = abs_evecs(:,i)
 call sort (tmp, idx, reverse = .true.)
 print "(1X,I2,A1,1X,E11.4,1X,A1,10(1X,I5))", &
 i, ":", evals(i), "|", idx(1:min(10,size(idx)))
 print "(17X,A1,10(1X,F5.2))", &
 "|", evecs(idx(1:min(10,size(idx))),i)
end do
print "(1X,A78)", repeat ("-", 78)
end subroutine vamp_print_covariance

```

### *Condensing Eigenvalues*

In order to decide whether we have a “pancake” or a “cigar”, we have to classify the eigenvalues of the covariance matrix. We do this by condensing the  $n_{\text{dim}}$  eigenvalues into  $n_{\text{cl}} \ll n_{\text{dim}}$  clusters.

130   *(Declaration of vamp procedures 77a)* +≡

```

! private :: condense
public :: condense

```

The rough description is as follows: in each step, combine the nearest neighbours (according to an appropriate metric) to form a smaller set. This is an extremely simplified, discretized modeling of molecules condensing under the influence of some potential.

 If there’s not a clean separation, this algorithm is certainly chaotic and we need to apply some form of damping!

131a  $\langle$ Initialize clusters 131a $\rangle \equiv$

```
cl_pos = x
cl_num = size (cl_pos)
cl = spread ((/ (i, i=1,cl_num) /), dim = 2, ncopies = 2)
```

It appears that the logarithmic metric

$$d_0(x, y) = \left| \log \left( \frac{x}{y} \right) \right| \quad (5.37a)$$

performs better than the linear metric

$$d_1(x, y) = |x - y| \quad (5.37b)$$

since the latter won't separate very small eigenvalues from the bulk. Another option is

$$d_\alpha(x, y) = |x^\alpha - y^\alpha| \quad (5.37c)$$

with  $\alpha \neq 1$ , in particular  $\alpha \approx -1$ . I haven't studied it yet, though.

 but I should perform more empirical studies to determine whether the logarithmic or the linear metric is more appropriate in realistic cases.

131b  $\langle$ Join closest clusters 131b $\rangle \equiv$

```
if (linear_metric) then
 gap = sum (minloc (cl_pos(2:cl_num) - cl_pos(1:cl_num-1)))
else
 gap = sum (minloc (cl_pos(2:cl_num) / cl_pos(1:cl_num-1)))
end if
wgt0 = cl(gap,2) - cl(gap,1) + 1
wgt1 = cl(gap+1,2) - cl(gap+1,1) + 1
cl_pos(gap) = (wgt0 * cl_pos(gap) + wgt1 * cl_pos(gap+1)) / (wgt0 + wgt1)
cl(gap,2) = cl(gap+1,2)
```

131c  $\langle$ Join closest clusters 131b $\rangle + \equiv$

```
cl_pos(gap+1:cl_num-1) = cl_pos(gap+2:cl_num)
cl(gap+1:cl_num-1,:) = cl(gap+2:cl_num,:)
```

131d  $\langle$ Implementation of vmp procedures 77c $\rangle + \equiv$

```
subroutine condense (x, cluster_pos, clusters, linear)
 real(kind=default), dimension(:), intent(in) :: x
 real(kind=default), dimension(:), intent(out) :: cluster_pos
 integer, dimension(:, :), intent(out) :: clusters
 logical, intent(in), optional :: linear
```

```

logical :: linear_metric
real(kind=default), dimension(size(x)) :: cl_pos
real(kind=default) :: wgt0, wgt1
integer :: cl_num
integer, dimension(size(x),2) :: cl
integer :: i, gap
linear_metric = .false.
if (present (linear)) then
 linear_metric = linear
end if
<Initialize clusters 131a>
do cl_num = size (cl_pos), size (cluster_pos) + 1, -1
 <Join closest clusters 131b>
 print *, cl_num, ": action = ", condense_action (x, cl)
end do
cluster_pos = cl_pos(1:cl_num)
clusters = cl(1:cl_num,:)
end subroutine condense

```

132a <*Declaration of vamp procedures 77a*>+≡

```

! private :: condense_action
public :: condense_action

```

$$S = \sum_{c \in \text{clusters}} \text{var}^{\frac{\alpha}{2}}(c) \quad (5.38)$$

132b <*Implementation of vamp procedures 77c*>+≡

```

function condense_action (positions, clusters) result (s)
 real(kind=default), dimension(:,), intent(in) :: positions
 integer, dimension(:, :,), intent(in) :: clusters
 real(kind=default) :: s
 integer :: i
 integer, parameter :: POWER = 2
 s = 0
 do i = 1, size (clusters, dim = 1)
 s = s + standard_deviation (positions(clusters(i,1) &
 :clusters(i,2))) ** POWER
 end do
end function condense_action

```

132c <ctest.f90 132c>≡

```

program ctest
use kinds
use utils
use vamp_stat
use tao_random_numbers

```

```

use vamp
implicit none
integer, parameter :: N = 16, NC = 2
real(kind=default), dimension(N) :: eval
real(kind=default), dimension(NC) :: cluster_pos
integer, dimension(NC,2) :: clusters
integer :: i
call tao_random_number (eval)
call sort (eval)
print *, eval
eval(1:N/2) = 0.95*eval(1:N/2)
eval(N/2+1:N) = 1.0 - 0.95*(1.0 - eval(N/2+1:N))
print *, eval
call condense (eval, cluster_pos, clusters, linear=.true.)
do i = 1, NC
 print "(I2,A,F5.2,A,I2,A,I2,A,A,F5.2,A,F5.2,A,32F5.2)", &
 i, ": ", cluster_pos(i), &
 "[", clusters(i,1), "-", clusters(i,2), "]", &
 "[", eval(clusters(i,1)), " - ", eval(clusters(i,2)), "]", &
 eval(clusters(i,1)+1:clusters(i,2)) &
 - eval(clusters(i,1):clusters(i,2)-1)
 print *, average (eval(clusters(i,1):clusters(i,2))), "+/-", &
 standard_deviation (eval(clusters(i,1):clusters(i,2)))
end do
end program ctest

```

### 5.2.8 Event Generation

Automagically adaptive tools are not always appropriate for unweighted event generation, but we can give it a try.

133a *(Declaration of vamp procedures 77a)*+≡

```
public :: vamp_next_event
```

133b *(Interfaces of vamp procedures 94c)*+≡

```
interface vamp_next_event
 module procedure vamp_next_event_single, vamp_next_event_multi
end interface
```

133c *(Declaration of vamp procedures 77a)*+≡

```
private :: vamp_next_event_single, vamp_next_event_multi
```

Both event generation routines operate in two modes, depending on whether the optional argument **weight** is present.

133d *(Implementation of vamp procedures 77c)*+≡

```

pure subroutine vamp_next_event_single &
 (x, rng, g, func, prc_index, &
 weight, channel, weights, grids, exc)
 real(kind=default), dimension(:), intent(out) :: x
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grid), intent(inout) :: g
 real(kind=default), intent(out), optional :: weight
 integer, intent(in) :: prc_index
 integer, intent(in), optional :: channel
 real(kind=default), dimension(:), intent(in), optional :: weights
 type(vamp_grid), dimension(:), intent(in), optional :: grids
 type(exception), intent(inout), optional :: exc
 <Interface declaration for func 22>
 character(len=*), parameter :: FN = "vamp_next_event_single"
 real(kind=default), dimension(size(g%div)):: wgts
 real(kind=default), dimension(size(g%div)):: r
 integer, dimension(size(g%div)):: ia
 real(kind=default) :: f, wgt
 real(kind=default) :: r0
 rejection: do
 <Choose a x and calculate f(x) 134a>
 if (present (weight)) then
 <Unconditionally accept weighted event 134b>
 else
 <Maybe accept unweighted event 134c>
 end if
 end do rejection
end subroutine vamp_next_event_single

```

134a <Choose a x and calculate f(x) 134a>≡  
call tao\_random\_number (rng, r)  
call inject\_division\_short (g%div, real(r, kind=default), x, ia, wgts)  
wgt = g%jacobi \* product (wgts)  
wgt = g%calls \* wgt ! the calling procedure will divide by #calls  
if (associated (g%map)) then  
 x = matmul (g%map, x)  
end if  
(f = wgt \* func (x, weights, channel), iff x inside true\_domain 88a)  
! call record\_efficiency (g%div, ia, f/g%f\_max)

134b <Unconditionally accept weighted event 134b>≡  
weight = f  
exit rejection

134c <Maybe accept unweighted event 134c>≡

```

if (f > g%f_max) then
 g%f_max = f
 call raise_exception (exc, EXC_WARN, FN, "weight > 1")
 exit rejection
end if
call tao_random_number (rng, r0)
if (r0 * g%f_max <= f) then
 exit rejection
end if

```

We know that `g%weights` are normalized: `sum (g%weights) == 1.0`. The basic formula for multi channel sampling is

$$f(x) = \sum_i \alpha_i g_i(x) w(x) \quad (5.39)$$

with  $w(x) = f(x)/g(x) = f(x)/\sum_i \alpha_i g_i(x)$  and  $\sum_i \alpha_i = 1$ . The non-trivial problem is that the adaptive grid is different in each channel, so we can't just reject on  $w(x)$ .

**135** *<Implementation of vamp procedures 77c>+≡*

```

pure subroutine vamp_next_event_multi &
 (x, rng, g, func, prc_index, phi, weight, excess, exc)
 real(kind=default), dimension(:), intent(out) :: x
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grids), intent(inout) :: g
 integer, intent(in) :: prc_index
 real(kind=default), intent(out), optional :: weight
 real(kind=default), intent(out), optional :: excess
 type(exception), intent(inout), optional :: exc
 <Interface declaration for func 22>
 <Interface declaration for phi 31a>
 character(len=*), parameter :: FN = "vamp_next_event_multi"
 real(kind=default), dimension(size(x)) :: xi
 real(kind=default) :: r, wgt
 real(kind=default), dimension(size(g%weights)) :: weights
 integer :: channel
 <weights: $\alpha_i \rightarrow w_{\max,i} \alpha_i$ 136a>
 rejection: do
 <Select channel from weights 136b>
 call vamp_next_event_single &
 (xi, rng, g%grids(channel), func, prc_index, wgt, &
 channel, g%weights, g%grids, exc)
 if (present (weight)) then
 <Unconditionally accept weighted multi channel event 136c>

```

```

 else
 (Maybe accept unweighted multi channel event 136d)
 end if
end do rejection
x = phi (xi, channel)
end subroutine vamp_next_event_multi

```

We can either reject with the weights

$$\frac{w_i(x)}{\max_i \max_x w_i(x)} \quad (5.40)$$

after using the apriori weights  $\alpha_i$  to select a channel  $i$  or we can reject with the weights

$$\frac{w_i(x)}{\max_x w_i(x)} \quad (5.41)$$

after using the apriori weights  $\alpha_i(\max_x w_i(x)) / (\max_i \max_x w_i(x))$ . The latter method is more efficient if the  $\max_x w_i(x)$  have a wide spread.

- 136a *{weights:  $\alpha_i \rightarrow w_{\max,i} \alpha_i$  136a}*≡
 

```

 if (any (g%grids%f_max > 0)) then
 weights = g%weights * g%grids%f_max
 else
 weights = g%weights
 end if
 weights = weights / sum (weights)

```
- 136b *{Select channel from weights 136b}*≡
 

```

 call tao_random_number (rng, r)
 select_channel: do channel = 1, size (g%weights)
 r = r - weights(channel)
 if (r <= 0.0) then
 exit select_channel
 end if
 end do select_channel
 channel = min (channel, size (g%weights)) ! for r = 1 and rounding errors

```
- 136c *{Unconditionally accept weighted multi channel event 136c}*≡
 

```

 weight = wgt * g%weights(channel) / weights(channel)
 exit rejection

```
- 136d *{Maybe accept unweighted multi channel event 136d}*≡
 

```

 if (wgt > g%grids(channel)%f_max) then
 if (present(excess)) then
 excess = wgt/g%grids(channel)%f_max - 1
 else

```

```

! call raise_exception (exc, EXC_WARN, FN, "weight > 1")
 print *, "weight > 1 (", wgt/g%grids(channel)%f_max, &
 & ") in channel ", channel

 end if
! exit rejection
else
 if (present(excess)) excess = 0
end if
call tao_random_number (rng, r)
if (r * g%grids(channel)%f_max <= wgt) then
 exit rejection
end if

```

137a *⟨Maybe accept unweighted multi channel event (old version) 137a⟩* $\equiv$

```

if (wgt > g%grids(channel)%f_max) then
 g%grids(channel)%f_max = wgt
 ⟨weights: $\alpha_i \rightarrow w_{\max,i}\alpha_i$ 136a⟩
 call raise_exception (exc, EXC_WARN, FN, "weight > 1")
 exit rejection
end if
call tao_random_number (rng, r)
if (r * g%grids(channel)%f_max <= wgt) then
 exit rejection
end if

```

Using `vamp_sample_grid (g, ...)` to warm up the grid `g` has a somewhat subtle problem: the minimum and maximum weights `g%f_min` and `g%f_max` refer to the grid *before* the final refinement. One could require an additional `vamp_sample_grid0 (g, ...)`, but users are likely to forget such technical details. A better solution is a wrapper `vamp_warmup_grid (g, ...)` that drops the final refinement transparently.

137b *⟨Declaration of vamp procedures 77a⟩* $\dagger\equiv$

```

public :: vamp_warmup_grid, vamp_warmup_grids

```

137c *⟨Implementation of vamp procedures 77c⟩* $\dagger\equiv$

```

pure subroutine vamp_warmup_grid &
 (rng, g, func, prc_index, iterations, exc, history)
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grid), intent(inout) :: g
 integer, intent(in) :: prc_index
 integer, intent(in) :: iterations
 type(exception), intent(inout), optional :: exc
 type(vamp_history), dimension(:), intent(inout), optional :: history
 ⟨Interface declaration for func 22⟩

```

```

call vamp_sample_grid &
 (rng, g, func, prc_index, &
 iterations - 1, exc = exc, history = history)
call vamp_sample_grid0 (rng, g, func, prc_index, exc = exc)
end subroutine vamp_warmup_grid

```

 WHERE ... END WHERE alert!

138a *(Implementation of vamp procedures 77c)*+≡

```

pure subroutine vamp_warmup_grids &
 (rng, g, func, prc_index, iterations, history, histories, exc)
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grids), intent(inout) :: g
 integer, intent(in) :: prc_index
 integer, intent(in) :: iterations
 type(vamp_history), dimension(:), intent(inout), optional :: history
 type(vamp_history), dimension(:, :), intent(inout), optional :: histories
 type(exception), intent(inout), optional :: exc
 <Interface declaration for func 22>
 integer :: ch
 logical, dimension(size(g%grids)) :: active
 real(kind=default), dimension(size(g%grids)) :: weights
 active = (g%num_calls >= 2)
 where (active)
 weights = g%num_calls
 elsewhere
 weights = 0.0
 end where
 weights = weights / sum (weights)
 call vamp_sample_grids (rng, g, func, prc_index, iterations - 1, &
 exc = exc, history = history, histories = histories)
 do ch = 1, size (g%grids)
 if (g%grids(ch)%num_calls >= 2) then
 call vamp_sample_grid0 &
 (rng, g%grids(ch), func, prc_index, &
 ch, weights, g%grids, exc = exc)
 end if
 end do
end subroutine vamp_warmup_grids

```

### 5.2.9 Convenience Routines

138b *(Declaration of vamp procedures 77a)*+≡

```

public :: vamp_integrate
private :: vamp_integrate_grid, vamp_integrate_region

139a <Interfaces of vamp procedures 94c>+≡
 interface vamp_integrate
 module procedure vamp_integrate_grid, vamp_integrate_region
 end interface

139b <Implementation of vamp procedures 77c>+≡
 pure subroutine vamp_integrate_grid &
 (rng, g, func, prc_index, calls, integral, std_dev, avg_chi2, num_div, &
 stratified, quadrupole, accuracy, exc, history)
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grid), intent(inout) :: g
 integer, intent(in) :: prc_index
 integer, dimension(:, :,), intent(in) :: calls
 real(kind=default), intent(out), optional :: integral, std_dev, avg_chi2
 integer, dimension(:,), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole
 real(kind=default), intent(in), optional :: accuracy
 type(exception), intent(inout), optional :: exc
 type(vamp_history), dimension(:,), intent(inout), optional :: history
 <Interface declaration for func 22>
 character(len=*), parameter :: FN = "vamp_integrate_grid"
 integer :: step, last_step, it
 last_step = size(calls, dim = 2)
 it = 1
 do step = 1, last_step - 1
 call vamp_discard_integral (g, calls(2,step), num_div, &
 stratified, quadrupole, exc = exc)
 call vamp_sample_grid (rng, g, func, prc_index, calls(1,step), &
 exc = exc, history = history(it:))
 <Bail out if exception exc raised 98a>
 it = it + calls(1,step)
 end do
 call vamp_discard_integral (g, calls(2,last_step), exc = exc)
 call vamp_sample_grid (rng, g, func, prc_index, calls(1,last_step), &
 integral, std_dev, avg_chi2, accuracy, exc = exc, &
 history = history(it:))
 end subroutine vamp_integrate_grid

139c <Implementation of vamp procedures 77c>+≡
 pure subroutine vamp_integrate_region &
 (rng, region, func, prc_index, calls, &
 integral, std_dev, avg_chi2, num_div, &

```

```

 stratified, quadrupole, accuracy, map, covariance, exc, history)
type(tao_random_state), intent(inout) :: rng
real(kind=default), dimension(:, :,), intent(in) :: region
integer, intent(in) :: prc_index
integer, dimension(:, :,), intent(in) :: calls
real(kind=default), intent(out), optional :: integral, std_dev, avg_chi2
integer, dimension(:,), intent(in), optional :: num_div
logical, intent(in), optional :: stratified, quadrupole
real(kind=default), intent(in), optional :: accuracy
real(kind=default), dimension(:, :,), intent(in), optional :: map
real(kind=default), dimension(:, :,), intent(out), optional :: covariance
type(exception), intent(inout), optional :: exc
type(vamp_history), dimension(:,), intent(inout), optional :: history
<Interface declaration for func 22>
character(len=*), parameter :: FN = "vamp_integrate_region"
type(vamp_grid) :: g
call vamp_create_grid &
(g, region, calls(2,1), num_div, &
stratified, quadrupole, present (covariance), map, exc)
call vamp_integrate_grid &
(rng, g, func, prc_index, calls, &
integral, std_dev, avg_chi2, num_div, &
accuracy = accuracy, exc = exc, history = history)
if (present (covariance)) then
covariance = vamp_get_covariance (g)
end if
call vamp_delete_grid (g)
end subroutine vamp_integrate_region

```

140a <*Declaration of vamp procedures 77a*>+≡

```

public :: vamp_integrate
private :: vamp_integrate_region

```

140b <*Interfaces of vamp procedures 94c*>+≡

```

interface vamp_integrate
 module procedure vamp_integrate_region
end interface

```

140c <*Implementation of vamp procedures 77c*>+≡

```

subroutine vamp_integrate_region &
(rng, region, func, prc_index, calls, integral, std_dev, avg_chi2, &
num_div, stratified, quadrupole, accuracy, pancake, cigar, &
exc, history)
type(tao_random_state), intent(inout) :: rng
real(kind=default), dimension(:, :,), intent(in) :: region

```

```

integer, intent(in) :: prc_index
integer, dimension(:,:,:), intent(in) :: calls
real(kind=default), intent(out), optional :: integral, std_dev, avg_chi2
integer, dimension(:), intent(in), optional :: num_div
logical, intent(in), optional :: stratified, quadrupole
real(kind=default), intent(in), optional :: accuracy
integer, intent(in), optional :: pancake, cigar
type(exception), intent(inout), optional :: exc
type(vamp_history), dimension(:), intent(inout), optional :: history
<Interface declaration for func 22>
real(kind=default), dimension(size(region,dim=2)) :: eval
real(kind=default), dimension(size(region,dim=2),size(region,dim=2)) :: evec
type(vamp_grid) :: g
integer :: step, last_step, it
it = 1
call vamp_create_grid &
 (g, region, calls(2,1,1), num_div, &
 stratified, quadrupole, covariance = .true., exc = exc)
call vamp_integrate_grid &
 (rng, g, func, prc_index, calls(:,:,1), num_div = num_div, &
 exc = exc, history = history(it:))
<Bail out if exception exc raised 98a>
it = it + sum (calls(1,:,:))
last_step = size (calls, dim = 3)
do step = 2, last_step - 1
 call diagonalize_real_symmetric (vamp_get_covariance(g), eval, evec)
 call sort (eval, evec)
 call select_rotation_axis (vamp_get_covariance(g), evec, pancake, cigar)
 call vamp_delete_grid (g)
 call vamp_create_grid &
 (g, region, calls(2,1,step), num_div, stratified, quadrupole, &
 covariance = .true., map = evec, exc = exc)
 call vamp_integrate_grid &
 (rng, g, func, prc_index, calls(:,:,step), num_div = num_div, &
 exc = exc, history = history(it:))
<Bail out if exception exc raised 98a>
 it = it + sum (calls(1,:,step))
end do
call diagonalize_real_symmetric (vamp_get_covariance(g), eval, evec)
call sort (eval, evec)
call select_rotation_axis (vamp_get_covariance(g), evec, pancake, cigar)
call vamp_delete_grid (g)
call vamp_create_grid &

```

```

(g, region, calls(2,1,last_step), num_div, stratified, quadrupole, &
 covariance = .true., map = evec, exc = exc)
call vamp_integrate_grid &
(rng, g, func, prc_index, calls(:,:,last_step), &
 integral, std_dev, avg_chi2, &
 num_div = num_div, exc = exc, history = history(it:))
call vamp_delete_grid (g)
end subroutine vamp_integrate_x_region

```

### 5.2.10 I/O

142a *(Declaration of vamp procedures 77a)*+≡

```

public :: vamp_write_grid
private :: write_grid_unit, write_grid_name
public :: vamp_read_grid
private :: read_grid_unit, read_grid_name
public :: vamp_write_grids
private :: write_grids_unit, write_grids_name
public :: vamp_read_grids
private :: read_grids_unit, read_grids_name

```

142b *(Declaration of vamp procedures 77a)*+≡

```

public :: vamp_read_grids_raw
private :: read_grids_raw_unit, read_grids_raw_name
public :: vamp_read_grid_raw
private :: read_grid_raw_unit, read_grid_raw_name
public :: vamp_write_grids_raw
private :: write_grids_raw_unit, write_grids_raw_name
public :: vamp_write_grid_raw
private :: write_grid_raw_unit, write_grid_raw_name

```

142c *(Interfaces of vamp procedures 94c)*+≡

```

interface vamp_write_grid
 module procedure write_grid_unit, write_grid_name
end interface
interface vamp_read_grid
 module procedure read_grid_unit, read_grid_name
end interface
interface vamp_write_grids
 module procedure write_grids_unit, write_grids_name
end interface
interface vamp_read_grids
 module procedure read_grids_unit, read_grids_name
end interface

```

143a *(Interfaces of vamp procedures 94c)* +≡

```

interface vamp_write_grid_raw
 module procedure write_grid_raw_unit, write_grid_raw_name
end interface

interface vamp_read_grid_raw
 module procedure read_grid_raw_unit, read_grid_raw_name
end interface

interface vamp_write_grids_raw
 module procedure write_grids_raw_unit, write_grids_raw_name
end interface

interface vamp_read_grids_raw
 module procedure read_grids_raw_unit, read_grids_raw_name
end interface

```

143b *(Implementation of vamp procedures 77c)* +≡

```

subroutine write_grid_unit (g, unit, write_integrals)
 type(vamp_grid), intent(in) :: g
 integer, intent(in) :: unit
 logical, intent(in), optional :: write_integrals
 integer :: i, j

 write (unit = unit, fmt = descr_fmt) "begin type(vamp_grid) :: g"
 write (unit = unit, fmt = integer_fmt) "size (g%div) = ", size (g%div)
 write (unit = unit, fmt = integer_fmt) "num_calls = ", g%num_calls
 write (unit = unit, fmt = integer_fmt) "calls_per_cell = ", g%calls_per_cell
 write (unit = unit, fmt = logical_fmt) "stratified = ", g%stratified
 write (unit = unit, fmt = logical_fmt) "all_stratified = ", g%all_stratified
 write (unit = unit, fmt = logical_fmt) "quadrupole = ", g%quadrupole
 write (unit = unit, fmt = double_fmt) "mu(1) = ", g%mu(1)
 write (unit = unit, fmt = double_fmt) "mu(2) = ", g%mu(2)
 write (unit = unit, fmt = double_fmt) "sum_integral = ", g%sum_integral
 write (unit = unit, fmt = double_fmt) "sum_weights = ", g%sum_weights
 write (unit = unit, fmt = double_fmt) "sum_chi2 = ", g%sum_chi2
 write (unit = unit, fmt = double_fmt) "calls = ", g%calls
 write (unit = unit, fmt = double_fmt) "dv2g = ", g%dv2g
 write (unit = unit, fmt = double_fmt) "jacobi = ", g%jacobi
 write (unit = unit, fmt = double_fmt) "f_min = ", g%f_min
 write (unit = unit, fmt = double_fmt) "f_max = ", g%f_max
 write (unit = unit, fmt = double_fmt) "mu_gi = ", g%mu_gi
 write (unit = unit, fmt = double_fmt) "sum_mu_gi = ", g%sum_mu_gi
 write (unit = unit, fmt = descr_fmt) "begin g%num_div"
 do i = 1, size (g%div)
 write (unit = unit, fmt = integer_array_fmt) i, g%num_div(i)
 end do
 write (unit = unit, fmt = descr_fmt) "end g%num_div"

```

```

 write (unit = unit, fmt = descr_fmt) "begin g%div"
 do i = 1, size (g%div)
 call write_division (g%div(i), unit, write_integrals)
 end do
 write (unit = unit, fmt = descr_fmt) "end g%div"
 if (associated (g%map)) then
 write (unit = unit, fmt = descr_fmt) "begin g%map"
 do i = 1, size (g%div)
 do j = 1, size (g%div)
 write (unit = unit, fmt = double_array2_fmt) i, j, g%map(i,j)
 end do
 end do
 write (unit = unit, fmt = descr_fmt) "end g%map"
 else
 write (unit = unit, fmt = descr_fmt) "empty g%map"
 end if
 if (associated (g%mu_x)) then
 write (unit = unit, fmt = descr_fmt) "begin g%mu_x"
 do i = 1, size (g%div)
 write (unit = unit, fmt = double_array_fmt) i, g%mu_x(i)
 write (unit = unit, fmt = double_array_fmt) i, g%sum_mu_x(i)
 do j = 1, size (g%div)
 write (unit = unit, fmt = double_array2_fmt) i, j, g%mu_xx(i,j)
 write (unit = unit, fmt = double_array2_fmt) i, j, g%sum_mu_xx(i,j)
 end do
 end do
 write (unit = unit, fmt = descr_fmt) "end g%mu_x"
 else
 write (unit = unit, fmt = descr_fmt) "empty g%mu_x"
 end if
 write (unit = unit, fmt = descr_fmt) "end type(vamp_grid)"
end subroutine write_grid_unit

```

144a ⟨Variables in vamp 78a⟩+≡

```

character(len=*), parameter, private :: &
 descr_fmt = "(1x,a)", &
 integer_fmt = "(1x,a17,1x,i15)", &
 integer_array_fmt = "(1x,i17,1x,i15)", &
 logical_fmt = "(1x,a17,1x,l1)", &
 double_fmt = "(1x,a17,1x,e30.22)", &
 double_array_fmt = "(1x,i17,1x,e30.22)", &
 double_array2_fmt = "(2(1x,i8),1x,e30.22)"

```

144b ⟨Implementation of vamp procedures 77c⟩+≡

```

subroutine read_grid_unit (g, unit, read_integrals)

```

```

type(vamp_grid), intent(inout) :: g
integer, intent(in) :: unit
logical, intent(in), optional :: read_integrals
character(len=*), parameter :: FN = "vamp_read_grid"
character(len=80) :: chdum
integer :: ndim, i, j, idum, jdum
read (unit = unit, fmt = descr_fmt) chdum
read (unit = unit, fmt = integer_fmt) chdum, ndim
<Ensure that size (g%div) == ndim 146a>
call create_array_pointer (g%num_div, ndim)
read (unit = unit, fmt = integer_fmt) chdum, g%num_calls
read (unit = unit, fmt = integer_fmt) chdum, g%calls_per_cell
read (unit = unit, fmt = logical_fmt) chdum, g%stratified
read (unit = unit, fmt = logical_fmt) chdum, g%all_stratified
read (unit = unit, fmt = logical_fmt) chdum, g%quadrupole
read (unit = unit, fmt = double_fmt) chdum, g%mu(1)
read (unit = unit, fmt = double_fmt) chdum, g%mu(2)
read (unit = unit, fmt = double_fmt) chdum, g%sum_integral
read (unit = unit, fmt = double_fmt) chdum, g%sum_weights
read (unit = unit, fmt = double_fmt) chdum, g%sum_chi2
read (unit = unit, fmt = double_fmt) chdum, g%calls
read (unit = unit, fmt = double_fmt) chdum, g%dv2g
read (unit = unit, fmt = double_fmt) chdum, g%jacobi
read (unit = unit, fmt = double_fmt) chdum, g%f_min
read (unit = unit, fmt = double_fmt) chdum, g%f_max
read (unit = unit, fmt = double_fmt) chdum, g%mu_gi
read (unit = unit, fmt = double_fmt) chdum, g%sum_mu_gi
read (unit = unit, fmt = descr_fmt) chdum
do i = 1, size (g%div)
 read (unit = unit, fmt = integer_array_fmt) idum, g%num_div(i)
end do
read (unit = unit, fmt = descr_fmt) chdum
read (unit = unit, fmt = descr_fmt) chdum
do i = 1, size (g%div)
 call read_division (g%div(i), unit, read_integrals)
end do
read (unit = unit, fmt = descr_fmt) chdum
read (unit = unit, fmt = descr_fmt) chdum
if (chdum == "begin g%map") then
 call create_array_pointer (g%map, (/ ndim, ndim /))
 do i = 1, size (g%div)
 do j = 1, size (g%div)
 read (unit = unit, fmt = double_array2_fmt) idum, jdum, g%map(i,j)

```

```

 end do
 end do
 read (unit = unit, fmt = descr_fmt) chdum
else
 <Insure that associated (g%map) == .false. 146b>
end if
read (unit = unit, fmt = descr_fmt) chdum
if (chdum == "begin g%mu_x") then
 call create_array_pointer (g%mu_x, ndim)
 call create_array_pointer (g%sum_mu_x, ndim)
 call create_array_pointer (g%mu_xx, (/ ndim, ndim /))
 call create_array_pointer (g%sum_mu_xx, (/ ndim, ndim /))
do i = 1, size (g%div)
 read (unit = unit, fmt = double_array_fmt) idum, jdum, g%mu_x(i)
 read (unit = unit, fmt = double_array_fmt) idum, jdum, g%sum_mu_x(i)
 do j = 1, size (g%div)
 read (unit = unit, fmt = double_array2_fmt) &
 idum, jdum, g%mu_xx(i,j)
 read (unit = unit, fmt = double_array2_fmt) &
 idum, jdum, g%sum_mu_xx(i,j)
 end do
end do
read (unit = unit, fmt = descr_fmt) chdum
else
 <Insure that associated (g%mu_x) == .false. 147a>
end if
read (unit = unit, fmt = descr_fmt) chdum
end subroutine read_grid_unit

```

146a <Insure that size (g%div) == ndim 146a>≡

```

 if (associated (g%div)) then
 if (size (g%div) /= ndim) then
 call delete_division (g%div)
 deallocate (g%div)
 allocate (g%div(ndim))
 call create_empty_division (g%div)
 end if
 else
 allocate (g%div(ndim))
 call create_empty_division (g%div)
 end if

```

146b <Insure that associated (g%map) == .false. 146b>≡

```

 if (associated (g%map)) then
 deallocate (g%map)

```

```

 end if

147a <Insure that associated (g%mu_x) == .false. 147a>≡
 if (associated (g%mu_x)) then
 deallocate (g%mu_x)
 end if
 if (associated (g%mu_xx)) then
 deallocate (g%mu_xx)
 end if
 if (associated (g%sum_mu_x)) then
 deallocate (g%sum_mu_x)
 end if
 if (associated (g%sum_mu_xx)) then
 deallocate (g%sum_mu_xx)
 end if

147b <Implementation of vamp procedures 77c>+≡
 subroutine write_grid_name (g, name, write_integrals)
 type(vamp_grid), intent(inout) :: g
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: write_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "write", status = "replace", file = name)
 call write_grid_unit (g, unit, write_integrals)
 close (unit = unit)
 end subroutine write_grid_name

147c <Implementation of vamp procedures 77c>+≡
 subroutine read_grid_name (g, name, read_integrals)
 type(vamp_grid), intent(inout) :: g
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: read_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "read", status = "old", file = name)
 call read_grid_unit (g, unit, read_integrals)
 close (unit = unit)
 end subroutine read_grid_name

147d <Implementation of vamp procedures 77c>+≡
 subroutine write_grids_unit (g, unit, write_integrals)
 type(vamp_grids), intent(in) :: g
 integer, intent(in) :: unit
 logical, intent(in), optional :: write_integrals
 integer :: i

```

```

write (unit = unit, fmt = descr_fmt) "begin type(vamp_grids) :: g"
write (unit = unit, fmt = integer_fmt) "size (g%grids) = ", size (g%grids)
write (unit = unit, fmt = double_fmt) "sum_integral = ", g%sum_integral
write (unit = unit, fmt = double_fmt) "sum_weights = ", g%sum_weights
write (unit = unit, fmt = double_fmt) "sum_chi2 = ", g%sum_chi2
write (unit = unit, fmt = descr_fmt) "begin g%weights"
do i = 1, size (g%grids)
 write (unit = unit, fmt = double_array_fmt) i, g%weights(i)
end do
write (unit = unit, fmt = descr_fmt) "end g%weights"
write (unit = unit, fmt = descr_fmt) "begin g%num_calls"
do i = 1, size (g%grids)
 write (unit = unit, fmt = integer_array_fmt) i, g%num_calls(i)
end do
write (unit = unit, fmt = descr_fmt) "end g%num_calls"
write (unit = unit, fmt = descr_fmt) "begin g%grids"
do i = 1, size (g%grids)
 call write_grid_unit (g%grids(i), unit, write_integrals)
end do
write (unit = unit, fmt = descr_fmt) "end g%grids"
write (unit = unit, fmt = descr_fmt) "end type(vamp_grids)"
end subroutine write_grids_unit

```

148 <Implementation of vamp procedures 77c>+≡

```

subroutine read_grids_unit (g, unit, read_integrals)
 type(vamp_grids), intent(inout) :: g
 integer, intent(in) :: unit
 logical, intent(in), optional :: read_integrals
 character(len=*), parameter :: FN = "vamp_read_grids"
 character(len=80) :: chdum
 integer :: i, nch, idum
 read (unit = unit, fmt = descr_fmt) chdum
 read (unit = unit, fmt = integer_fmt) chdum, nch
 if (associated (g%grids)) then
 if (size (g%grids) /= nch) then
 call vamp_delete_grid (g%grids)
 deallocate (g%grids, g%weights, g%num_calls)
 allocate (g%grids(nch), g%weights(nch), g%num_calls(nch))
 call vamp_create_empty_grid (g%grids)
 end if
 else
 allocate (g%grids(nch), g%weights(nch), g%num_calls(nch))
 call vamp_create_empty_grid (g%grids)
 end if

```

```

read (unit = unit, fmt = double_fmt) chdum, g%sum_integral
read (unit = unit, fmt = double_fmt) chdum, g%sum_weights
read (unit = unit, fmt = double_fmt) chdum, g%sum_chi2
read (unit = unit, fmt = descr_fmt) chdum
do i = 1, nch
 read (unit = unit, fmt = double_array_fmt) idum, g%weights(i)
end do
read (unit = unit, fmt = descr_fmt) chdum
read (unit = unit, fmt = descr_fmt) chdum
do i = 1, nch
 read (unit = unit, fmt = integer_array_fmt) idum, g%num_calls(i)
end do
read (unit = unit, fmt = descr_fmt) chdum
read (unit = unit, fmt = descr_fmt) chdum
do i = 1, nch
 call read_grid_unit (g%grids(i), unit, read_integrals)
end do
read (unit = unit, fmt = descr_fmt) chdum
read (unit = unit, fmt = descr_fmt) chdum
end subroutine read_grids_unit

```

149a *(Implementation of vamp procedures 77c)*+≡

```

subroutine write_grids_name (g, name, write_integrals)
 type(vamp_grids), intent(inout) :: g
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: write_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "write", status = "replace", file = name)
 call write_grids_unit (g, unit, write_integrals)
 close (unit = unit)
end subroutine write_grids_name

```

149b *(Implementation of vamp procedures 77c)*+≡

```

subroutine read_grids_name (g, name, read_integrals)
 type(vamp_grids), intent(inout) :: g
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: read_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "read", status = "old", file = name)
 call read_grids_unit (g, unit, read_integrals)
 close (unit = unit)
end subroutine read_grids_name

```

150 <Implementation of vamp procedures 77c>+≡

```

subroutine write_grid_raw_unit (g, unit, write_integrals)
 type(vamp_grid), intent(in) :: g
 integer, intent(in) :: unit
 logical, intent(in), optional :: write_integrals
 integer :: i, j
 write (unit = unit) MAGIC_GRID_BEGIN
 write (unit = unit) size (g%div)
 write (unit = unit) g%num_calls
 write (unit = unit) g%calls_per_cell
 write (unit = unit) g%stratified
 write (unit = unit) g%all_stratified
 write (unit = unit) g%quadrupole
 write (unit = unit) g%mu(1)
 write (unit = unit) g%mu(2)
 write (unit = unit) g%sum_integral
 write (unit = unit) g%sum_weights
 write (unit = unit) g%sum_chi2
 write (unit = unit) g%calls
 write (unit = unit) g%dv2g
 write (unit = unit) g%jacobi
 write (unit = unit) g%f_min
 write (unit = unit) g%f_max
 write (unit = unit) g%mu_gi
 write (unit = unit) g%sum_mu_gi
 do i = 1, size (g%div)
 write (unit = unit) g%num_div(i)
 end do
 do i = 1, size (g%div)
 call write_division_raw (g%div(i), unit, write_integrals)
 end do
 if (associated (g%map)) then
 write (unit = unit) MAGIC_GRID_MAP
 do i = 1, size (g%div)
 do j = 1, size (g%div)
 write (unit = unit) g%map(i,j)
 end do
 end do
 else
 write (unit = unit) MAGIC_GRID_EMPTY
 end if
 if (associated (g%mu_x)) then
 write (unit = unit) MAGIC_GRID_MU_X
 end if
end subroutine

```

```

do i = 1, size (g%div)
 write (unit = unit) g%mu_x(i)
 write (unit = unit) g%sum_mu_x(i)
 do j = 1, size (g%div)
 write (unit = unit) g%mu_xx(i,j)
 write (unit = unit) g%sum_mu_xx(i,j)
 end do
end do
else
 write (unit = unit) MAGIC_GRID_EMPTY
end if
write (unit = unit) MAGIC_GRID_END
end subroutine write_grid_raw_unit

```

151a *(Constants in vamp 151a)*≡

```

integer, parameter, private :: MAGIC_GRID = 22222222
integer, parameter, private :: MAGIC_GRID_BEGIN = MAGIC_GRID + 1
integer, parameter, private :: MAGIC_GRID_END = MAGIC_GRID + 2
integer, parameter, private :: MAGIC_GRID_EMPTY = MAGIC_GRID + 3
integer, parameter, private :: MAGIC_GRID_MAP = MAGIC_GRID + 4
integer, parameter, private :: MAGIC_GRID_MU_X = MAGIC_GRID + 5

```

151b *(Implementation of vamp procedures 77c)*+≡

```

subroutine read_grid_raw_unit (g, unit, read_integrals)
 type(vamp_grid), intent(inout) :: g
 integer, intent(in) :: unit
 logical, intent(in), optional :: read_integrals
 character(len=*), parameter :: FN = "vamp_read_raw_grid"
 integer :: ndim, i, j, magic
 read (unit = unit) magic
 if (magic /= MAGIC_GRID_BEGIN) then
 print *, FN, " fatal: expecting magic ", MAGIC_GRID_BEGIN, &
 ", found ", magic
 stop
 end if
 read (unit = unit) ndim
 <Insure that size (g%div) == ndim 146a>
 call create_array_pointer (g%num_div, ndim)
 read (unit = unit) g%num_calls
 read (unit = unit) g%calls_per_cell
 read (unit = unit) g%stratified
 read (unit = unit) g%all_stratified
 read (unit = unit) g%quadrupole
 read (unit = unit) g%mu(1)
 read (unit = unit) g%mu(2)

```

```

read (unit = unit) g%sum_integral
read (unit = unit) g%sum_weights
read (unit = unit) g%sum_chi2
read (unit = unit) g%calls
read (unit = unit) g%dv2g
read (unit = unit) g%jacobi
read (unit = unit) g%f_min
read (unit = unit) g%f_max
read (unit = unit) g%mu_gi
read (unit = unit) g%sum_mu_gi
do i = 1, size (g%div)
 read (unit = unit) g%num_div(i)
end do
do i = 1, size (g%div)
 call read_division_raw (g%div(i), unit, read_integrals)
end do
read (unit = unit) magic
if (magic == MAGIC_GRID_MAP) then
 call create_array_pointer (g%map, (/ ndim, ndim /))
 do i = 1, size (g%div)
 do j = 1, size (g%div)
 read (unit = unit) g%map(i,j)
 end do
 end do
else if (magic == MAGIC_GRID_EMPTY) then
 <Insure that associated (g%map) == .false. 146b>
else
 print *, FN, " fatal: expecting magic ", MAGIC_GRID_EMPTY, &
 " or ", MAGIC_GRID_MAP, ", found ", magic
 stop
end if
read (unit = unit) magic
if (magic == MAGIC_GRID_MU_X) then
 call create_array_pointer (g%mu_x, ndim)
 call create_array_pointer (g%sum_mu_x, ndim)
 call create_array_pointer (g%mu_xx, (/ ndim, ndim /))
 call create_array_pointer (g%sum_mu_xx, (/ ndim, ndim /))
 do i = 1, size (g%div)
 read (unit = unit) g%mu_x(i)
 read (unit = unit) g%sum_mu_x(i)
 do j = 1, size (g%div)
 read (unit = unit) g%mu_xx(i,j)
 read (unit = unit) g%sum_mu_xx(i,j)

```

```

 end do
 end do
else if (magic == MAGIC_GRID_EMPTY) then
 (Ensure that associated (g%mu_x) == .false. 147a)
else
 print *, FN, " fatal: expecting magic ", MAGIC_GRID_EMPTY, &
 " or ", MAGIC_GRID_MU_X, ", found ", magic
 stop
end if
read (unit = unit) magic
if (magic /= MAGIC_GRID_END) then
 print *, FN, " fatal: expecting magic ", MAGIC_GRID_END, &
 " found ", magic
 stop
end if
end subroutine read_grid_raw_unit

```

153a <Implementation of vamp procedures 77c>+≡

```

subroutine write_grid_raw_name (g, name, write_integrals)
 type(vamp_grid), intent(inout) :: g
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: write_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "write", status = "replace", &
 form = "unformatted", file = name)
 call write_grid_raw_unit (g, unit, write_integrals)
 close (unit = unit)
end subroutine write_grid_raw_name

```

153b <Implementation of vamp procedures 77c>+≡

```

subroutine read_grid_raw_name (g, name, read_integrals)
 type(vamp_grid), intent(inout) :: g
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: read_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "read", status = "old", &
 form = "unformatted", file = name)
 call read_grid_raw_unit (g, unit, read_integrals)
 close (unit = unit)
end subroutine read_grid_raw_name

```

153c <Implementation of vamp procedures 77c>+≡

```

subroutine write_grids_raw_unit (g, unit, write_integrals)

```

```

type(vamp_grids), intent(in) :: g
integer, intent(in) :: unit
logical, intent(in), optional :: write_integrals
integer :: i
write (unit = unit) MAGIC_GRIDS_BEGIN
write (unit = unit) size (g%grids)
write (unit = unit) g%sum_integral
write (unit = unit) g%sum_weights
write (unit = unit) g%sum_chi2
do i = 1, size (g%grids)
 write (unit = unit) g%weights(i)
end do
do i = 1, size (g%grids)
 write (unit = unit) g%num_calls(i)
end do
do i = 1, size (g%grids)
 call write_grid_raw_unit (g%grids(i), unit, write_integrals)
end do
write (unit = unit) MAGIC_GRIDS_END
end subroutine write_grids_raw_unit

```

154a <Constants in vamp 151a>+≡

```

integer, parameter, private :: MAGIC_GRIDS = 33333333
integer, parameter, private :: MAGIC_GRIDS_BEGIN = MAGIC_GRIDS + 1
integer, parameter, private :: MAGIC_GRIDS_END = MAGIC_GRIDS + 2

```

154b <Implementation of vamp procedures 77c>+≡

```

subroutine read_grids_raw_unit (g, unit, read_integrals)
 type(vamp_grids), intent(inout) :: g
 integer, intent(in) :: unit
 logical, intent(in), optional :: read_integrals
 character(len=*), parameter :: FN = "vamp_read_grids_raw"
 integer :: i, nch, magic
 read (unit = unit) magic
 if (magic /= MAGIC_GRIDS_BEGIN) then
 print *, FN, " fatal: expecting magic ", MAGIC_GRIDS_BEGIN, &
 " found ", magic
 stop
 end if
 read (unit = unit) nch
 if (associated (g%grids)) then
 if (size (g%grids) /= nch) then
 call vamp_delete_grid (g%grids)
 deallocate (g%grids, g%weights, g%num_calls)
 allocate (g%grids(nch), g%weights(nch), g%num_calls(nch))

```

```

 call vamp_create_empty_grid (g%grids)
 end if
else
 allocate (g%grids(nch), g%weights(nch), g%num_calls(nch))
 call vamp_create_empty_grid (g%grids)
end if
read (unit = unit) g%sum_integral
read (unit = unit) g%sum_weights
read (unit = unit) g%sum_chi2
do i = 1, nch
 read (unit = unit) g%weights(i)
end do
do i = 1, nch
 read (unit = unit) g%num_calls(i)
end do
do i = 1, nch
 call read_grid_raw_unit (g%grids(i), unit, read_integrals)
end do
read (unit = unit) magic
if (magic /= MAGIC_GRIDS_END) then
 print *, FN, " fatal: expecting magic ", MAGIC_GRIDS_END, &
 " found ", magic
 stop
end if
end subroutine read_grids_raw_unit

```

155a <Implementation of vamp procedures 77c>+≡

```

subroutine write_grids_raw_name (g, name, write_integrals)
 type(vamp_grids), intent(inout) :: g
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: write_integrals
 integer :: unit
 call find_free_unit (unit)
 open (unit = unit, action = "write", status = "replace", &
 form = "unformatted", file = name)
 call write_grids_raw_unit (g, unit, write_integrals)
 close (unit = unit)
end subroutine write_grids_raw_name

```

155b <Implementation of vamp procedures 77c>+≡

```

subroutine read_grids_raw_name (g, name, read_integrals)
 type(vamp_grids), intent(inout) :: g
 character(len=*), intent(in) :: name
 logical, intent(in), optional :: read_integrals
 integer :: unit

```

```

call find_free_unit (unit)
open (unit = unit, action = "read", status = "old", &
 form = "unformatted", file = name)
call read_grids_raw_unit (g, unit, read_integrals)
close (unit = unit)
end subroutine read_grids_raw_name

```

### 5.2.11 Marshaling

156a *(Declaration of vamp procedures 77a)*+≡  
 public :: vamp\_marshal\_grid\_size, vamp\_marshal\_grid, vamp\_unmarshal\_grid

156b *(Implementation of vamp procedures 77c)*+≡  
 pure subroutine vamp\_marshal\_grid (g, ibuf, dbuf)  
   type(vamp\_grid), intent(in) :: g  
   integer, dimension(:), intent(inout) :: ibuf  
   real(kind=default), dimension(:), intent(inout) :: dbuf  
   integer :: i, iwords, dwords, iidx, didx, ndim  
   ndim = size (g%div)  
   ibuf(1) = g%num\_calls  
   ibuf(2) = g%calls\_per\_cell  
   ibuf(3) = ndim  
   if (g%stratified) then  
     ibuf(4) = 1  
   else  
     ibuf(4) = 0  
   end if  
   if (g%all\_stratified) then  
     ibuf(5) = 1  
   else  
     ibuf(5) = 0  
   end if  
   if (g%quadrupole) then  
     ibuf(6) = 1  
   else  
     ibuf(6) = 0  
   end if  
   dbuf(1:2) = g%mu  
   dbuf(3) = g%sum\_integral  
   dbuf(4) = g%sum\_weights  
   dbuf(5) = g%sum\_chi2  
   dbuf(6) = g%calls  
   dbuf(7) = g%dv2g

```

dbuf(8) = g%jacobi
dbuf(9) = g%f_min
dbuf(10) = g%f_max
dbuf(11) = g%mu_gi
dbuf(12) = g%sum_mu_gi
ibuf(7:6+ndim) = g%num_div
iidx = 7 + ndim
didx = 13
do i = 1, ndim
 call marshal_division_size (g%div(i), iwords, dwords)
 ibuf(iidx) = iwords
 ibuf(iidx+1) = dwords
 iidx = iidx + 2
 call marshal_division (g%div(i), ibuf(iidx:iidx-1+iwords), &
 dbuf(didx:didx-1+dwords))
 iidx = iidx + iwords
 didx = didx + dwords
end do
if (associated (g%map)) then
 ibuf(iidx) = 1
 dbuf(didx:didx-1+ndim**2) = reshape (g%map, (/ ndim**2 /))
 didx = didx + ndim**2
else
 ibuf(iidx) = 0
end if
iidx = iidx + 1
if (associated (g%mu_x)) then
 ibuf(iidx) = 1
 dbuf(didx:didx-1+ndim) = g%mu_x
 didx = didx + ndim
 dbuf(didx:didx-1+ndim) = g%sum_mu_x
 didx = didx + ndim
 dbuf(didx:didx-1+ndim**2) = reshape (g%mu_xx, (/ ndim**2 /))
 didx = didx + ndim**2
 dbuf(didx:didx-1+ndim**2) = reshape (g%sum_mu_xx, (/ ndim**2 /))
 didx = didx + ndim**2
else
 ibuf(iidx) = 0
end if
iidx = iidx + 1
end subroutine vamp_marshall_grid

```

157 ⟨Implementation of vamp procedures 77c⟩+≡

```
pure subroutine vamp_marshall_grid_size (g, iwords, dwords)
```

```

type(vamp_grid), intent(in) :: g
integer, intent(out) :: iwords, dwords
integer :: i, ndim, iw, dw
ndim = size (g%div)
iwords = 6 + ndim
dwords = 12
do i = 1, ndim
 call marshal_division_size (g%div(i), iw, dw)
 iwords = iwords + 2 + iw
 dwords = dwords + dw
end do
iwords = iwords + 1
if (associated (g%map)) then
 dwords = dwords + ndim**2
end if
iwords = iwords + 1
if (associated (g%mu_x)) then
 dwords = dwords + 2 * (ndim + ndim**2)
end if
end subroutine vamp_marshal_grid_size

```

158 <Implementation of vamp procedures 77c>+≡

```

pure subroutine vamp_unmarshal_grid (g, ibuf, dbuf)
 type(vamp_grid), intent(inout) :: g
 integer, dimension(:), intent(in) :: ibuf
 real(kind=default), dimension(:), intent(in) :: dbuf
 integer :: i, iwords, dwords, iidx, didx, ndim
 g%num_calls = ibuf(1)
 g%calls_per_cell = ibuf(2)
 ndim = ibuf(3)
 g%stratified = ibuf(4) /= 0
 g%all_stratified = ibuf(5) /= 0
 g%quadrupole = ibuf(6) /= 0
 g%mu = dbuf(1:2)
 g%sum_integral = dbuf(3)
 g%sum_weights = dbuf(4)
 g%sum_chi2 = dbuf(5)
 g%calls = dbuf(6)
 g%dv2g = dbuf(7)
 g%jacobi = dbuf(8)
 g%f_min = dbuf(9)
 g%f_max = dbuf(10)
 g%mu_gi = dbuf(11)
 g%sum_mu_gi = dbuf(12)

```

```

call copy_array_pointer (g%num_div, ibuf(7:6+ndim))
 <Insure that size (g%div) == ndim 146a>
 iidx = 7 + ndim
 didx = 13
 do i = 1, ndim
 iwords = ibuf(iidx)
 dwords = ibuf(iidx+1)
 iidx = iidx + 2
 call unmarshal_division (g%div(i), ibuf(iidx:iidx-1+iwords), &
 dbuf(didx:didx-1+dwords))

 iidx = iidx + iwords
 didx = didx + dwords
 end do
 if (ibuf(iidx) > 0) then
 call copy_array_pointer &
 (g%map, reshape (dbuf(didx:didx-1+ibuf(iidx)), (/ ndim, ndim /)))
 didx = didx + ibuf(iidx)
 else
 <Insure that associated (g%map) == .false. 146b>
 end if
 iidx = iidx + 1
 if (ibuf(iidx) > 0) then
 call copy_array_pointer (g%mu_x, dbuf(didx:didx-1+ndim))
 didx = didx + ndim
 call copy_array_pointer (g%sum_mu_x, dbuf(didx:didx-1+ndim))
 didx = didx + ndim
 call copy_array_pointer &
 (g%mu_xx, reshape (dbuf(didx:didx-1+ndim**2), (/ ndim, ndim /)))
 didx = didx + ndim**2
 call copy_array_pointer &
 (g%sum_mu_xx, reshape (dbuf(didx:didx-1+ndim**2), (/ ndim, ndim /)))
 didx = didx + ndim**2
 else
 <Insure that associated (g%mu_x) == .false. 147a>
 end if
 iidx = iidx + 1
end subroutine vamp_unmarshal_grid

159a <Declaration of vamp procedures 77a>+≡
public :: vamp_marshal_history_size, vamp_marshal_history
public :: vamp_unmarshal_history

159b <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_marshal_history (h, ibuf, dbuf)
 type(vamp_history), intent(in) :: h

```

```

integer, dimension(:), intent(inout) :: ibuf
real(kind=default), dimension(:), intent(inout) :: dbuf
integer :: j, ndim, iidx, didx, iwords, dwords
if (h%verbose .and. (associated (h%div))) then
 ndim = size (h%div)
else
 ndim = 0
end if
ibuf(1) = ndim
ibuf(2) = h%calls
if (h%stratified) then
 ibuf(3) = 1
else
 ibuf(3) = 0
end if
dbuf(1) = h%integral
dbuf(2) = h%std_dev
dbuf(3) = h%avg_integral
dbuf(4) = h%avg_std_dev
dbuf(5) = h%avg_chi2
dbuf(6) = h%f_min
dbuf(7) = h%f_max
iidx = 4
didx = 8
do j = 1, ndim
 call marshal_div_history_size (h%div(j), iwords, dwords)
 ibuf(iidx) = iwords
 ibuf(iidx+1) = dwords
 iidx = iidx + 2
 call marshal_div_history (h%div(j), ibuf(iidx:iidx-1+iwords), &
 dbuf(didx:didx-1+dwords))
 iidx = iidx + iwords
 didx = didx + dwords
end do
end subroutine vamp_marshal_history

```

160 <Implementation of vamp procedures 77c>+≡

```

pure subroutine vamp_marshal_history_size (h, iwords, dwords)
 type(vamp_history), intent(in) :: h
 integer, intent(out) :: iwords, dwords
 integer :: i, ndim, iw, dw
 if (h%verbose .and. (associated (h%div))) then
 ndim = size (h%div)
 else

```

```

 ndim = 0
end if
iwords = 3
dwords = 7
do i = 1, ndim
 call marshal_div_history_size (h%div(i), iw, dw)
 iwords = iwords + 2 + iw
 dwords = dwords + dw
end do
end subroutine vamp_marshal_history_size

161 <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_unmarshal_history (h, ibuf, dbuf)
 type(vamp_history), intent(inout) :: h
 integer, dimension(:), intent(in) :: ibuf
 real(kind=default), dimension(:), intent(in) :: dbuf
 integer :: j, ndim, iidx, didx, iwords, dwords
 ndim = ibuf(1)
 h%calls = ibuf(2)
 h%stratified = ibuf(3) /= 0
 h%integral = dbuf(1)
 h%std_dev = dbuf(2)
 h%avg_integral = dbuf(3)
 h%avg_std_dev = dbuf(4)
 h%avg_chi2 = dbuf(5)
 h%f_min = dbuf(6)
 h%f_max = dbuf(7)
 if (ndim > 0) then
 if (associated (h%div)) then
 if (size (h%div) /= ndim) then
 deallocate (h%div)
 allocate (h%div(ndim))
 end if
 else
 allocate (h%div(ndim))
 end if
 iidx = 4
 didx = 8
 do j = 1, ndim
 iwords = ibuf(iidx)
 dwords = ibuf(iidx+1)
 iidx = iidx + 2
 call unmarshal_div_history (h%div(j), ibuf(iidx:iidx-1+iwords), &
 dbuf(didx:didx-1+dwords))
 end do
 end if
end subroutine vamp_unmarshal_history

```

```

 iidx = iidx + iwords
 didx = didx + dwords
 end do
end if
end subroutine vamp_unmarshal_history

```

### 5.2.12 Boring Copying and Deleting of Objects

162 {Implementation of `vamp` procedures 77c}+≡

```

elemental subroutine vamp_copy_grid (lhs, rhs)
 type(vamp_grid), intent(inout) :: lhs
 type(vamp_grid), intent(in) :: rhs
 integer :: ndim
 ndim = size (rhs%div)
 lhs%mu = rhs%mu
 lhs%sum_integral = rhs%sum_integral
 lhs%sum_weights = rhs%sum_weights
 lhs%sum_chi2 = rhs%sum_chi2
 lhs%calls = rhs%calls
 lhs%num_calls = rhs%num_calls
 call copy_array_pointer (lhs%num_div, rhs%num_div)
 lhs%dv2g = rhs%dv2g
 lhs%jacobi = rhs%jacobi
 lhs%f_min = rhs%f_min
 lhs%f_max = rhs%f_max
 lhs%mu_gi = rhs%mu_gi
 lhs%sum_mu_gi = rhs%sum_mu_gi
 lhs%calls_per_cell = rhs%calls_per_cell
 lhs%stratified = rhs%stratified
 lhs%all_stratified = rhs%all_stratified
 lhs%quadrupole = rhs%quadrupole
 if (associated (lhs%div)) then
 if (size (lhs%div) /= ndim) then
 call delete_division (lhs%div)
 deallocate (lhs%div)
 allocate (lhs%div(ndim))
 end if
 else
 allocate (lhs%div(ndim))
 end if
 call copy_division (lhs%div, rhs%div)
 if (associated (rhs%map)) then
 call copy_array_pointer (lhs%map, rhs%map)
 end if
end subroutine vamp_copy_grid

```

```

else if (associated (lhs%map)) then
 deallocate (lhs%map)
end if
if (associated (rhs%mu_x)) then
 call copy_array_pointer (lhs%mu_x, rhs%mu_x)
 call copy_array_pointer (lhs%mu_xx, rhs%mu_xx)
 call copy_array_pointer (lhs%sum_mu_x, rhs%sum_mu_x)
 call copy_array_pointer (lhs%sum_mu_xx, rhs%sum_mu_xx)
else if (associated (lhs%mu_x)) then
 deallocate (lhs%mu_x, lhs%mu_xx, lhs%sum_mu_x, lhs%sum_mu_xx)
end if
end subroutine vamp_copy_grid

```

163a <Implementation of vamp procedures 77c>+≡

```

elemental subroutine vamp_delete_grid (g)
 type(vamp_grid), intent(inout) :: g
 if (associated (g%div)) then
 call delete_division (g%div)
 deallocate (g%div, g%num_div)
 end if
 if (associated (g%map)) then
 deallocate (g%map)
 end if
 if (associated (g%mu_x)) then
 deallocate (g%mu_x, g%mu_xx, g%sum_mu_x, g%sum_mu_xx)
 end if
end subroutine vamp_delete_grid

```

163b <Implementation of vamp procedures 77c>+≡

```

elemental subroutine vamp_copy_grids (lhs, rhs)
 type(vamp_grids), intent(inout) :: lhs
 type(vamp_grids), intent(in) :: rhs
 integer :: nch
 nch = size (rhs%grids)
 lhs%sum_integral = rhs%sum_integral
 lhs%sum_chi2 = rhs%sum_chi2
 lhs%sum_weights = rhs%sum_weights
 if (associated (lhs%grids)) then
 if (size (lhs%grids) /= nch) then
 deallocate (lhs%grids)
 allocate (lhs%grids(nch))
 call vamp_create_empty_grid (lhs%grids(nch))
 end if
 else

```

```

 allocate (lhs%grids(nch))
 call vamp_create_empty_grid (lhs%grids(nch))
end if
call vamp_copy_grid (lhs%grids, rhs%grids)
call copy_array_pointer (lhs%weights, rhs%weights)
call copy_array_pointer (lhs%num_calls, rhs%num_calls)
end subroutine vamp_copy_grids

164a <Implementation of vamp procedures 77c>+≡
elemental subroutine vamp_delete_grids (g)
type(vamp_grids), intent(inout) :: g
if (associated (g%grids)) then
 call vamp_delete_grid (g%grids)
 deallocate (g%weights, g%grids, g%num_calls)
end if
end subroutine vamp_delete_grids

164b <Implementation of vamp procedures 77c>+≡
elemental subroutine vamp_copy_history (lhs, rhs)
type(vamp_history), intent(inout) :: lhs
type(vamp_history), intent(in) :: rhs
lhs%calls = rhs%calls
lhs%stratified = rhs%stratified
lhs%verbose = rhs%verbose
lhs%integral = rhs%integral
lhs%std_dev = rhs%std_dev
lhs%avg_integral = rhs%avg_integral
lhs%avg_std_dev = rhs%avg_std_dev
lhs%avg_chi2 = rhs%avg_chi2
lhs%f_min = rhs%f_min
lhs%f_max = rhs%f_max
if (rhs%verbose) then
 if (associated (lhs%div)) then
 if (size (lhs%div) /= size (rhs%div)) then
 deallocate (lhs%div)
 allocate (lhs%div(size(rhs%div)))
 end if
 else
 allocate (lhs%div(size(rhs%div)))
 end if
 call copy_history (lhs%div, rhs%div)
end if
end subroutine vamp_copy_history

```

165a *<Implementation of vamp procedures 77c>*+≡

```

elemental subroutine vamp_delete_history (h)
 type(vamp_history), intent(inout) :: h
 if (associated (h%div)) then
 deallocate (h%div)
 end if
end subroutine vamp_delete_history

```

### 5.3 Interface to MPI

The module `vamp` makes no specific assumptions about the hardware and software supporting parallel execution. In this section, we present a specific example of a parallel implementation of multi channel sampling using the message passing paradigm.

The modules `vamp_serial_mpi` and `vamp_parallel_mpi` are not intended to be used directly by application programs. For this purpose, the module `vampi` is provided. `vamp_serial_mpi` is identical to `vamp`, but some types, procedures and variables are renamed so that `vamp_parallel_mpi` can redefine them:

165b *<vampi.f90 165b>*≡

```

! vampi.f90 --
<Copyleft notice 1>
module vamp_serial_mpi
 use vamp, &
 <vamp0_* => vamp_* 166c>
 VAMPO_RCS_ID => VAMP_RCS_ID
 public
end module vamp_serial_mpi

```

`vamp_parallel_mpi` contains the non trivial MPI code and will be discussed in detail below.

165c *<vampi.f90 165b>*+≡

```

module vamp_parallel_mpi
 use kinds
 use utils
 use tao_random_numbers
 use exceptions
 use mpi90
 use divisions
 use vamp_serial_mpi !NODEP!
 use iso_fortran_env

```

```

implicit none
private
<Declaration of vampi procedures 166b>
<Interfaces of vampi procedures 170d>
<Parameters in vampi 167a>
<Declaration of vampi types 171b>
character(len=*), public, parameter :: VAMPI_RCS_ID = &
 "$Id: vampi.nw 314 2010-04-17 20:32:33Z ohl $"
contains
 <Implementation of vampi procedures 166d>
end module vamp_parallel_mpi

```

vampi is now a plug-in replacement for vamp and *must not* be used together with vamp:

166a <vampi.f90 165b>+≡

```

module vampi
 use vamp_serial_mpi !NODEP!
 use vamp_parallel_mpi !NODEP!
 public
end module vampi

```

### 5.3.1 Parallel Execution

#### Single Channel

166b <Declaration of vampi procedures 166b>≡

```

public :: vamp_create_grid
public :: vamp_discard_integral
public :: vamp_reshape_grid
public :: vamp_sample_grid
public :: vamp_delete_grid

```

166c <vamp0\_\* => vamp\_\* 166c>≡

```

vamp0_create_grid => vamp_create_grid, &
vamp0_discard_integral => vamp_discard_integral, &
vamp0_reshape_grid => vamp_reshape_grid, &
vamp0_sample_grid => vamp_sample_grid, &
vamp0_delete_grid => vamp_delete_grid, &

```

166d <Implementation of vampi procedures 166d>≡

```

subroutine vamp_create_grid &
 (g, domain, num_calls, num_div, &
 stratified, quadrupole, covariance, map, exc)
 type(vamp_grid), intent(inout) :: g

```

```

real(kind=default), dimension(:,:), intent(in) :: domain
integer, intent(in) :: num_calls
integer, dimension(:), intent(in), optional :: num_div
logical, intent(in), optional :: stratified, quadrupole, covariance
real(kind=default), dimension(:,:), intent(in), optional :: map
type(exception), intent(inout), optional :: exc
integer :: proc_id
call mpi90_rank (proc_id)
if (proc_id == VAMP_ROOT) then
 call vamp0_create_grid &
 (g, domain, num_calls, num_div, &
 stratified, quadrupole, covariance, map, exc)
else
 call vamp_create_empty_grid (g)
end if
end subroutine vamp_create_grid

167a <Parameters in vmpi 167a>≡
 integer, public, parameter :: VAMP_ROOT = 0

167b <Implementation of vmpi procedures 166d>+≡
 subroutine vamp_discard_integral &
 (g, num_calls, num_div, stratified, quadrupole, covariance, exc)
 type(vamp_grid), intent(inout) :: g
 integer, intent(in), optional :: num_calls
 integer, dimension(:), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole, covariance
 type(exception), intent(inout), optional :: exc
 integer :: proc_id
 call mpi90_rank (proc_id)
 if (proc_id == VAMP_ROOT) then
 call vamp0_discard_integral &
 (g, num_calls, num_div, stratified, quadrupole, covariance, exc)
 end if
end subroutine vamp_discard_integral

167c <Implementation of vmpi procedures 166d>+≡
 subroutine vamp_reshape_grid &
 (g, num_calls, num_div, stratified, quadrupole, covariance, exc)
 type(vamp_grid), intent(inout) :: g
 integer, intent(in), optional :: num_calls
 integer, dimension(:), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole, covariance
 type(exception), intent(inout), optional :: exc
 integer :: proc_id

```

```

call mpi90_rank (proc_id)
if (proc_id == VAMP_ROOT) then
 call vamp0_reshape_grid &
 (g, num_calls, num_div, stratified, quadrupole, covariance, exc)
end if
end subroutine vamp_reshape_grid

```

NB: grids has to have intent(inout) because we will call vamp\_broadcast\_grid on it.

168 <Implementation of vampi procedures 166d>+≡

```

subroutine vamp_sample_grid &
 (rng, g, func, iterations, integral, std_dev, avg_chi2, accuracy, &
 channel, weights, grids, exc, history)
type(tao_random_state), intent(inout) :: rng
type(vamp_grid), intent(inout) :: g
integer, intent(in) :: iterations
real(kind=default), intent(out), optional :: integral, std_dev, avg_chi2
real(kind=default), intent(in), optional :: accuracy
integer, intent(in), optional :: channel
real(kind=default), dimension(:,), intent(in), optional :: weights
type(vamp_grid), dimension(:,), intent(inout), optional :: grids
type(exception), intent(inout), optional :: exc
type(vamp_history), dimension(:,), intent(inout), optional :: history
<Interface declaration for func 22>
character(len=*), parameter :: FN = "vamp_sample_grid"
real(kind=default) :: local_integral, local_std_dev, local_avg_chi2
type(vamp_grid), dimension(:,), allocatable :: gs, gx
integer, dimension(:, :,), pointer :: d
integer :: iteration, i
integer :: num_proc, proc_id, num_workers
nullify (d)
call mpi90_size (num_proc)
call mpi90_rank (proc_id)
iterate: do iteration = 1, iterations
 if (proc_id == VAMP_ROOT) then
 call vamp_distribute_work (num_proc, vamp_rigid_divisions (g), d)
 num_workers = max (1, product (d(2,:)))
 end if
 call mpi90_broadcast (num_workers, VAMP_ROOT)
 if ((present (grids)) .and. (num_workers > 1)) then
 call vamp_broadcast_grid (grids, VAMP_ROOT)
 end if
 if (proc_id == VAMP_ROOT) then
 allocate (gs(num_workers), gx(vamp_fork_grid_joints (d)))
 end if
end do iterate

```

```

call vamp_create_empty_grid (gs)
call vamp_fork_grid (g, gs, gx, d, exc)
do i = 2, num_workers
 call vamp_send_grid (gs(i), i-1, 0)
end do
else if (proc_id < num_workers) then
 call vamp_receive_grid (g, VAMP_ROOT, 0)
end if
if (proc_id == VAMP_ROOT) then
 if (num_workers > 1) then
 call vamp_sample_grid0 &
 (rng, gs(1), func, channel, weights, grids, exc)
 else
 call vamp_sample_grid0 &
 (rng, g, func, channel, weights, grids, exc)
 end if
else if (proc_id < num_workers) then
 call vamp_sample_grid0 &
 (rng, g, func, channel, weights, grids, exc)
end if
if (proc_id == VAMP_ROOT) then
 do i = 2, num_workers
 call vamp_receive_grid (gs(i), i-1, 0)
 end do
 call vamp_join_grid (g, gs, gx, d, exc)
 call vamp0_delete_grid (gs)
 deallocate (gs, gx)
 call vamp_refine_grid (g)
 call vamp_average_iterations &
 (g, iteration, local_integral, local_std_dev, local_avg_chi2)
 if (present (history)) then
 if (iteration <= size (history)) then
 call vamp_get_history &
 (history(iteration), g, &
 local_integral, local_std_dev, local_avg_chi2)
 else
 call raise_exception (exc, EXC_WARN, FN, "history too short")
 end if
 call vamp_terminate_history (history(iteration+1:))
 end if
 if (present (accuracy)) then
 if (local_std_dev <= accuracy * local_integral) then
 call raise_exception (exc, EXC_INFO, FN, &

```

```

 "requested accuracy reached")
 exit iterate
 end if
end if
else if (proc_id < num_workers) then
 call vamp_send_grid (g, VAMP_ROOT, 0)
end if
end do iterate
if (proc_id == VAMP_ROOT) then
 deallocate (d)
 if (present (integral)) then
 integral = local_integral
 end if
 if (present (std_dev)) then
 std_dev = local_std_dev
 end if
 if (present (avg_chi2)) then
 avg_chi2 = local_avg_chi2
 end if
end if
end subroutine vamp_sample_grid

```

- 170a *<Implementation of vampi procedures 166d>*+≡  
 subroutine vamp\_delete\_grid (g)  
 type(vamp\_grid), intent(inout) :: g  
 integer :: proc\_id  
 call mpi90\_rank (proc\_id)  
 if (proc\_id == VAMP\_ROOT) then  
 call vamp0\_reshape\_grid (g)
 end if
end subroutine vamp\_delete\_grid
- 170b *<Declaration of vampi procedures 166b>*+≡  
 public :: vamp\_print\_history  
 private :: vamp\_print\_one\_history, vamp\_print\_histories
- 170c *<vamp0\_\* => vamp\_\* 166c>*+≡  
 vamp0\_print\_history => vamp\_print\_history, &
- 170d *<Interfaces of vampi procedures 170d>*≡  
 interface vamp\_print\_history  
 module procedure vamp\_print\_one\_history, vamp\_print\_histories
 end interface
- 170e *<Implementation of vampi procedures 166d>*+≡  
 subroutine vamp\_print\_one\_history (h, tag)

```

type(vamp_history), dimension(:), intent(in) :: h
character(len=*), intent(in), optional :: tag
integer :: proc_id
call mpi90_rank (proc_id)
if (proc_id == VAMP_ROOT) then
 call vamp0_print_history (h, tag)
end if
end subroutine vamp_print_one_history

```

171a <Implementation of vmpi procedures 166d>+≡

```

subroutine vamp_print_histories (h, tag)
type(vamp_history), dimension(:,:), intent(in) :: h
character(len=*), intent(in), optional :: tag
integer :: proc_id
call mpi90_rank (proc_id)
if (proc_id == VAMP_ROOT) then
 call vamp0_print_history (h, tag)
end if
end subroutine vamp_print_histories

```

### *Multi Channel*

171b <Declaration of vmpi types 171b>≡

```

type, public :: vamp_grids
!!! private
type(vamp0_grids) :: g0
logical, dimension(:,), pointer :: active
integer, dimension(:,), pointer :: proc
real(kind=default), dimension(:,), pointer :: integrals, std_devs
end type vamp_grids

```

171c <vamp0\_\* => vamp\_\* 166c>+≡

```
vamp0_grids => vamp_grids, &
```

Partially duplicate the API of vamp:

171d <Declaration of vmpi procedures 166b>+≡

```

public :: vamp_create_grids
public :: vamp_discard_integrals
public :: vamp_update_weights
public :: vamp_refine_weights
public :: vamp_delete_grids
public :: vamp_sample_grids

```

171e <vamp0\_\* => vamp\_\* 166c>+≡

```
vamp0_create_grids => vamp_create_grids, &
```

```

vamp0_discard_integrals => vamp_discard_integrals, &
vamp0_update_weights => vamp_update_weights, &
vamp0_refine_weights => vamp_refine_weights, &
vamp0_delete_grids => vamp_delete_grids, &
vamp0_sample_grids => vamp_sample_grids, &

```

Call `vamp_create_grids` just like the serial version. It will create the actual grids on the root processor and create stubs on the other processors

172a *(Implementation of vampi procedures 166d) +≡*

```

subroutine vamp_create_grids (g, domain, num_calls, weights, maps, &
 num_div, stratified, quadrupole, exc)
 type(vamp_grids), intent(inout) :: g
 real(kind=default), dimension(:, :, :), intent(in) :: domain
 integer, intent(in) :: num_calls
 real(kind=default), dimension(:, :), intent(in) :: weights
 real(kind=default), dimension(:, :, :, :), intent(in), optional :: maps
 integer, dimension(:, :), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole
 type(exception), intent(inout), optional :: exc
 integer :: proc_id, nch
 call mpi90_rank (proc_id)
 nch = size (weights)
 allocate (g%active(nch), g%proc(nch), g%integrals(nch), g%std_devs(nch))
 if (proc_id == VAMP_ROOT) then
 call vamp0_create_grids (g%g0, domain, num_calls, weights, maps, &
 num_div, stratified, quadrupole, exc)
 else
 allocate (g%g0%grids(nch), g%g0%weights(nch), g%g0%num_calls(nch))
 call vamp_create_empty_grid (g%g0%grids)
 end if
end subroutine vamp_create_grids

```

172b *(Implementation of vampi procedures 166d) +≡*

```

subroutine vamp_discard_integrals &
 (g, num_calls, num_div, stratified, quadrupole, exc)
 type(vamp_grids), intent(inout) :: g
 integer, intent(in), optional :: num_calls
 integer, dimension(:, :), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole
 type(exception), intent(inout), optional :: exc
 integer :: proc_id
 call mpi90_rank (proc_id)
 if (proc_id == VAMP_ROOT) then
 call vamp0_discard_integrals &

```

```

 (g%g0, num_calls, num_div, stratified, quadrupole, exc)
 end if
end subroutine vamp_discard_integrals

173a <Implementation of vampi procedures 166d>+≡
subroutine vamp_update_weights &
 (g, weights, num_calls, num_div, stratified, quadrupole, exc)
 type(vamp_grids), intent(inout) :: g
 real(kind=default), dimension(:), intent(in) :: weights
 integer, intent(in), optional :: num_calls
 integer, dimension(:), intent(in), optional :: num_div
 logical, intent(in), optional :: stratified, quadrupole
 type(exception), intent(inout), optional :: exc
 integer :: proc_id
 call mpi90_rank (proc_id)
 if (proc_id == VAMP_ROOT) then
 call vamp0_update_weights &
 (g%g0, weights, num_calls, num_div, stratified, quadrupole, exc)
 end if
end subroutine vamp_update_weights

173b <Implementation of vampi procedures 166d>+≡
subroutine vamp_refine_weights (g, power)
 type(vamp_grids), intent(inout) :: g
 real(kind=default), intent(in), optional :: power
 integer :: proc_id
 call mpi90_rank (proc_id)
 if (proc_id == VAMP_ROOT) then
 call vamp0_refine_weights (g%g0, power)
 end if
end subroutine vamp_refine_weights

173c <Implementation of vampi procedures 166d>+≡
subroutine vamp_delete_grids (g)
 type(vamp_grids), intent(inout) :: g
 character(len=*), parameter :: FN = "vamp_delete_grids"
 deallocate (g%active, g%proc, g%integrals, g%std_devs)
 call vamp0_delete_grids (g%g0)
end subroutine vamp_delete_grids

Call vamp_sample_grids just like vamp0_sample_grids.

173d <Implementation of vampi procedures 166d>+≡
subroutine vamp_sample_grids &
 (rng, g, func, iterations, integral, std_dev, avg_chi2, &
 accuracy, history, histories, exc)
 type(tao_random_state), intent(inout) :: rng

```

```

type(vamp_grids), intent(inout) :: g
integer, intent(in) :: iterations
real(kind=default), intent(out), optional :: integral, std_dev, avg_chi2
real(kind=default), intent(in), optional :: accuracy
type(vamp_history), dimension(:), intent(inout), optional :: history
type(vamp_history), dimension(:,:,1), intent(inout), optional :: histories
type(exception), intent(inout), optional :: exc
<Interface declaration for func 22>
character(len=*), parameter :: FN = "vamp_sample_grids"
integer :: num_proc, proc_id, nch, ch, iteration
real(kind=default), dimension(size(g%g0%weights)) :: weights
real(kind=default) :: local_integral, local_std_dev, local_avg_chi2
real(kind=default) :: current_accuracy, waste
logical :: distribute_complete_grids
call mpi90_size (num_proc)
call mpi90_rank (proc_id)
nch = size (g%g0%weights)
if (proc_id == VAMP_ROOT) then
 g%active = (g%g0%num_calls >= 2)
 where (g%active)
 weights = g%g0%num_calls
 elsewhere
 weights = 0.0
 endwhere
 weights = weights / sum (weights)
 call schedule (weights, num_proc, g%proc, waste)
 distribute_complete_grids = (waste <= VAMP_MAX_WASTE)
end if
call mpi90_broadcast (weights, VAMP_ROOT)
call mpi90_broadcast (g%active, VAMP_ROOT)
call mpi90_broadcast (distribute_complete_grids, VAMP_ROOT)
if (distribute_complete_grids) then
 call mpi90_broadcast (g%proc, VAMP_ROOT)
end if
iterate: do iteration = 1, iterations
 if (distribute_complete_grids) then
 call vamp_broadcast_grid (g%g0%grids, VAMP_ROOT)
 <Distribute complete grids among processes 175b>
 else
 <Distribute each grid among processes 179b>
 end if
 <Exit iterate if accuracy has been reached (MPI) 178a>
end do iterate

```

```

 <Copy results of vamp_sample_grids to dummy variables 177e>
end subroutine vamp_sample_grids

```

Setting VAMP\_MAX\_WASTE to 1 disables the splitting of grids, which doesn't work yet.

175a <Parameters in vampi 167a>+≡  
`real(kind=default), private, parameter :: VAMP_MAX_WASTE = 1.0  
! real(kind=default), private, parameter :: VAMP_MAX_WASTE = 0.3`

175b <Distribute complete grids among processes 175b>≡  
`do ch = 1, nch  
 if (g%active(ch)) then  
 if (proc_id == g%proc(ch)) then  
 call vamp0_discard_integral (g%g0%grids(ch))  
 <Sample g%g0%grids(ch) 175d>  
 end if  
 else  
 call vamp_nullify_variance (g%g0%grids(ch))  
 call vamp_nullify_covariance (g%g0%grids(ch))  
 end if  
end do`

Refine the grids after *all* grids have been sampled:

175c <Distribute complete grids among processes 175b>+≡  
`do ch = 1, nch  
 if (g%active(ch) .and. (proc_id == g%proc(ch))) then  
 call vamp_refine_grid (g%g0%grids(ch))  
 if (proc_id /= VAMP_ROOT) then  
 <Ship the result for channel #ch back to the root 176c>  
 end if  
 end if  
end do`

therefore we use `vamp_sample_grid0` instead of `vamp0_sample_grid`:

175d <Sample g%g0%grids(ch) 175d>≡  
`call vamp_sample_grid0 &  
 (rng, g%g0%grids(ch), func, ch, weights, g%g0%grids, exc)  
call vamp_average_iterations &  
 (g%g0%grids(ch), iteration, g%integrals(ch), g%std_devs(ch), local_avg_chi2)  
if (present (histories)) then  
 if (iteration <= ubound (histories, dim=1)) then  
 call vamp_get_history &  
 (histories(iteration,ch), g%g0%grids(ch), &  
 g%integrals(ch), g%std_devs(ch), local_avg_chi2)  
 else`

```

 call raise_exception (exc, EXC_WARN, FN, "history too short")
 end if
 call vamp_terminate_history (histories(iteration+1:,ch))
end if

176a <Distribute complete grids among processes 175b>+≡
if (proc_id == VAMP_ROOT) then
 do ch = 1, nch
 if (g%active(ch) .and. (g%proc(ch) /= proc_id)) then
 (Receive the result for channel #ch at the root 177a)
 end if
 end do
call vamp_reduce_channels (g%g0, g%integrals, g%std_devs, g%active)
call vamp_average_iterations &
 (g%g0, iteration, local_integral, local_std_dev, local_avg_chi2)
if (present (history)) then
 if (iteration <= size (history)) then
 call vamp_get_history &
 (history(iteration), g%g0, local_integral, local_std_dev, &
 local_avg_chi2)
 else
 call raise_exception (exc, EXC_WARN, FN, "history too short")
 end if
 call vamp_terminate_history (history(iteration+1:))
end if
end if

```

This would be cheaper than `vamp_broadcast_grid`, but we need the latter to support the adaptive multi channel sampling:

```

176b <Ship g%g0%grids from the root to the assigned processor 176b>≡
do ch = 1, nch
 if (g%active(ch) .and. (g%proc(ch) /= VAMP_ROOT)) then
 if (proc_id == VAMP_ROOT) then
 call vamp_send_grid &
 (g%g0%grids(ch), g%proc(ch), object (ch, TAG_GRID))
 else if (proc_id == g%proc(ch)) then
 call vamp_receive_grid &
 (g%g0%grids(ch), VAMP_ROOT, object (ch, TAG_GRID))
 end if
 end if
end do

176c <Ship the result for channel #ch back to the root 176c>≡
call mpi90_send (g%integrals(ch), VAMP_ROOT, object (ch, TAG_INTEGRAL))
call mpi90_send (g%std_devs(ch), VAMP_ROOT, object (ch, TAG_STD_DEV))

```

```

call vamp_send_grid (g%g0%grids(ch), VAMP_ROOT, object (ch, TAG_GRID))
if (present (histories)) then
 call vamp_send_history &
 (histories(iteration,ch), VAMP_ROOT, object (ch, TAG_HISTORY))
end if

177a <Receive the result for channel #ch at the root 177a>≡
 call mpi90_receive (g%integrals(ch), g%proc(ch), object (ch, TAG_INTEGRAL))
 call mpi90_receive (g%std_devs(ch), g%proc(ch), object (ch, TAG_STD_DEV))
 call vamp_receive_grid (g%g0%grids(ch), g%proc(ch), object (ch, TAG_GRID))
 if (present (histories)) then
 call vamp_receive_history &
 (histories(iteration,ch), g%proc(ch), object (ch, TAG_HISTORY))
 end if

177b <Declaration of vmpi procedures 166b>+≡
 private :: object

177c <Implementation of vmpi procedures 166d>+≡
 pure function object (ch, obj) result (tag)
 integer, intent(in) :: ch, obj
 integer :: tag
 tag = 100 * ch + obj
 end function object

177d <Parameters in vmpi 167a>+≡
 integer, public, parameter :: &
 TAG_INTEGRAL = 1, &
 TAG_STD_DEV = 2, &
 TAG_GRID = 3, &
 TAG_HISTORY = 6, &
 TAG_NEXT_FREE = 9

177e <Copy results of vamp_sample_grids to dummy variables 177e>≡
 if (present (integral)) then
 call mpi90_broadcast (local_integral, VAMP_ROOT)
 integral = local_integral
 end if
 if (present (std_dev)) then
 call mpi90_broadcast (local_std_dev, VAMP_ROOT)
 std_dev = local_std_dev
 end if
 if (present (avg_chi2)) then
 call mpi90_broadcast (local_avg_chi2, VAMP_ROOT)
 avg_chi2 = local_avg_chi2
 end if

```

178a *(Exit iterate if accuracy has been reached (MPI) 178a)*≡

```

if (present (accuracy)) then
 if (proc_id == VAMP_ROOT) then
 current_accuracy = local_std_dev / local_integral
 end if
 call mpi90_broadcast (current_accuracy, VAMP_ROOT)
 if (current_accuracy <= accuracy) then
 call raise_exception (exc, EXC_INFO, FN, &
 "requested accuracy reached")
 exit iterate
 end if
end if

```

A very simple minded scheduler: maximizes processor utilization and, does not pay attention to communication costs.

178b *(Declaration of vmpi procedures 166b)*+≡

```

private :: schedule

```

We disfavor the root process a little bit (by starting up with a fake filling ratio of 10%) so that it is likely to be ready to answer all communication requests.

178c *(Implementation of vmpi procedures 166d)*+≡

```

pure subroutine schedule (jobs, num_procs, assign, waste)
 real(kind=default), dimension(:), intent(in) :: jobs
 integer, intent(in) :: num_procs
 integer, dimension(:), intent(out) :: assign
 real(kind=default), intent(out), optional :: waste
 integer, dimension(size(jobs)) :: idx
 real(kind=default), dimension(size(jobs)) :: sjobs
 real(kind=default), dimension(num_procs) :: fill
 integer :: job, proc
 sjobs = jobs / sum (jobs) * num_procs
 idx = (/ (job, job = 1, size(jobs)) /)
 call sort (sjobs, idx, reverse = .true.)
 fill = 0.0
 fill(VAMP_ROOT+1) = 0.1
 do job = 1, size (sjobs)
 proc = sum (minloc (fill))
 fill(proc) = fill(proc) + sjobs(job)
 assign(idx(job)) = proc - 1
 end do
 <Estimate waste of processor time 179a>
end subroutine schedule

```

Assuming equivalent processors and uniform computation costs, the waste is

given by the fraction of the time that it spent by the other processors waiting for the processor with the biggest assignment:

179a *(Estimate waste of processor time 179a)*≡  
 if (present (waste)) then  
     waste = 1.0 - sum (fill) / (num\_procs \* maxval (fill))  
 end if

Accordingly, if the waste caused by distributing only complete grids, we switch to splitting the grids, just like in single channel sampling. This is *not* the default, because the communication costs are measurably higher for many grids and many processors.

 This version is broken!

179b *(Distribute each grid among processes 179b)*≡  
 do ch = 1, size (g%g0%grids)  
 if (g%active(ch)) then  
     call vamp\_discard\_integral (g%g0%grids(ch))  
     if (present (histories)) then  
         call vamp\_sample\_grid &  
             (rng, g%g0%grids(ch), func, 1, g%integrals(ch), g%std\_devs(ch), &  
             channel = ch, weights = weights, grids = g%g0%grids, &  
             history = histories(iteration:iteration,ch))  
     else  
         call vamp\_sample\_grid &  
             (rng, g%g0%grids(ch), func, 1, g%integrals(ch), g%std\_devs(ch), &  
             channel = ch, weights = weights, grids = g%g0%grids)  
     end if  
 else  
     if (proc\_id == VAMP\_ROOT) then  
         call vamp\_nullify\_variance (g%g0%grids(ch))  
         call vamp\_nullify\_covariance (g%g0%grids(ch))  
     end if  
 end if  
 end do  
 if (proc\_id == VAMP\_ROOT) then  
     call vamp\_reduce\_channels (g%g0, g%integrals, g%std\_devs, g%active)  
     call vamp\_average\_iterations &  
         (g%g0, iteration, local\_integral, local\_std\_dev, local\_avg\_chi2)  
 if (present (history)) then  
     if (iteration <= size (history)) then  
         call vamp\_get\_history &  
             (history(iteration), g%g0, local\_integral, local\_std\_dev, &  
             local\_avg\_chi2)

```

 else
 call raise_exception (exc, EXC_WARN, FN, "history too short")
 end if
 call vamp_terminate_history (history(iteration+1:))
 end if
end if

```

### 5.3.2 Event Generation

This is currently only a syntactical translation ...

- 180a *<Declaration of vampi procedures 166b>+≡*

```

public :: vamp_warmup_grid
public :: vamp_warmup_grids
public :: vamp_next_event
private :: vamp_next_event_single, vamp_next_event_multi

```
- 180b *<vamp0\_\* => vamp\_\* 166c>+≡*

```

vamp0_warmup_grid => vamp_warmup_grid, &
vamp0_warmup_grids => vamp_warmup_grids, &
vamp0_next_event => vamp_next_event, &

```
- 180c *<Interfaces of vampi procedures 170d>+≡*

```

interface vamp_next_event
 module procedure vamp_next_event_single, vamp_next_event_multi
end interface

```
- 180d *<Implementation of vampi procedures 166d>+≡*

```

subroutine vamp_next_event_single &
 (x, rng, g, func, weight, channel, weights, grids, exc)
 real(kind=default), dimension(:), intent(out) :: x
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grid), intent(inout) :: g
 real(kind=default), intent(out), optional :: weight
 integer, intent(in), optional :: channel
 real(kind=default), dimension(:), intent(in), optional :: weights
 type(vamp_grid), dimension(:), intent(in), optional :: grids
 type(exception), intent(inout), optional :: exc
 <Interface declaration for func 22>
 integer :: proc_id
 call mpi90_rank (proc_id)
 if (proc_id == VAMP_ROOT) then
 call vamp0_next_event &
 (x, rng, g, func, weight, channel, weights, grids, exc)
 end if
end subroutine vamp_next_event_single

```

```

181a <Implementation of vmpi procedures 166d>+≡
 subroutine vamp_next_event_multi (x, rng, g, func, phi, weight, exc)
 real(kind=default), dimension(:), intent(out) :: x
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grids), intent(inout) :: g
 real(kind=default), intent(out), optional :: weight
 type(exception), intent(inout), optional :: exc
 <Interface declaration for func 22>
 <Interface declaration for phi 31a>
 integer :: proc_id
 call mpi90_rank (proc_id)
 if (proc_id == VAMP_ROOT) then
 call vamp0_next_event (x, rng, g%g0, func, phi, weight, exc)
 end if
 end subroutine vamp_next_event_multi

181b <Implementation of vmpi procedures 166d>+≡
 subroutine vamp_warmup_grid (rng, g, func, iterations, exc, history)
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grid), intent(inout) :: g
 integer, intent(in) :: iterations
 type(exception), intent(inout), optional :: exc
 type(vamp_history), dimension(:), intent(inout), optional :: history
 <Interface declaration for func 22>
 call vamp_sample_grid &
 (rng, g, func, iterations - 1, exc = exc, history = history)
 call vamp_sample_grid0 (rng, g, func, exc = exc)
 end subroutine vamp_warmup_grid

181c <Implementation of vmpi procedures 166d>+≡
 subroutine vamp_warmup_grids &
 (rng, g, func, iterations, history, histories, exc)
 type(tao_random_state), intent(inout) :: rng
 type(vamp_grids), intent(inout) :: g
 integer, intent(in) :: iterations
 type(vamp_history), dimension(:), intent(inout), optional :: history
 type(vamp_history), dimension(:, :), intent(inout), optional :: histories
 type(exception), intent(inout), optional :: exc
 <Interface declaration for func 22>
 integer :: ch
 call vamp0_sample_grids (rng, g%g0, func, iterations - 1, exc = exc, &
 history = history, histories = histories)
 do ch = 1, size (g%g0%grids)
 ! if (g%g0%grids(ch)%num_calls >= 2) then
 call vamp_sample_grid0 (rng, g%g0%grids(ch), func, exc = exc)

```

```

 ! end if
end do
end subroutine vamp_warmup_grids

```

### 5.3.3 I/O

- 182a *(Declaration of vampi procedures 166b)*+≡
- ```

public :: vamp_write_grid, vamp_read_grid
private :: write_grid_unit, write_grid_name
private :: read_grid_unit, read_grid_name

```
- 182b *(vamp0_* => vamp_** 166c*)*+≡
- ```

vamp0_write_grid => vamp_write_grid, &
vamp0_read_grid => vamp_read_grid, &

```
- 182c *(Interfaces of vampi procedures 170d)*+≡
- ```

interface vamp_write_grid
    module procedure write_grid_unit, write_grid_name
end interface
interface vamp_read_grid
    module procedure read_grid_unit, read_grid_name
end interface

```
- 182d *(Implementation of vampi procedures 166d)*+≡
- ```

subroutine write_grid_unit (g, unit)
 type(vamp_grid), intent(in) :: g
 integer, intent(in) :: unit
 integer :: proc_id
 call mpi90_rank (proc_id)
 if (proc_id == VAMP_ROOT) then
 call vamp0_write_grid (g, unit)
 end if
end subroutine write_grid_unit

```
- 182e *(Implementation of vampi procedures 166d)*+≡
- ```

subroutine read_grid_unit (g, unit)
    type(vamp_grid), intent(inout) :: g
    integer, intent(in) :: unit
    integer :: proc_id
    call mpi90_rank (proc_id)
    if (proc_id == VAMP_ROOT) then
        call vamp0_read_grid (g, unit)
    end if
end subroutine read_grid_unit

```

183a *(Implementation of vampi procedures 166d)*+≡

```

subroutine write_grid_name (g, name)
    type(vamp_grid), intent(inout) :: g
    character(len=*), intent(in) :: name
    integer :: proc_id
    call mpi90_rank (proc_id)
    if (proc_id == VAMP_ROOT) then
        call vamp0_write_grid (g, name)
    end if
end subroutine write_grid_name
```

183b *(Implementation of vampi procedures 166d)*+≡

```

subroutine read_grid_name (g, name)
    type(vamp_grid), intent(inout) :: g
    character(len=*), intent(in) :: name
    integer :: proc_id
    call mpi90_rank (proc_id)
    if (proc_id == VAMP_ROOT) then
        call vamp0_read_grid (g, name)
    end if
end subroutine read_grid_name
```

183c *(Declaration of vampi procedures 166b)*+≡

```

public :: vamp_write_grids, vamp_read_grids
private :: write_grids_unit, write_grids_name
private :: read_grids_unit, read_grids_name
```

183d *(vamp0_* => vamp_** 166c*)*+≡

```

vamp0_write_grids => vamp_write_grids, &
vamp0_read_grids => vamp_read_grids, &
```

183e *(Interfaces of vampi procedures 170d)*+≡

```

interface vamp_write_grids
    module procedure write_grids_unit, write_grids_name
end interface
interface vamp_read_grids
    module procedure read_grids_unit, read_grids_name
end interface
```

183f *(Implementation of vampi procedures 166d)*+≡

```

subroutine write_grids_unit (g, unit)
    type(vamp_grids), intent(in) :: g
    integer, intent(in) :: unit
    integer :: proc_id
    call mpi90_rank (proc_id)
```

```

    if (proc_id == VAMP_ROOT) then
        call vamp0_write_grids (g%g0, unit)
    end if
end subroutine write_grids_unit

```

184a *(Implementation of vampi procedures 166d)*+≡

```

subroutine read_grids_unit (g, unit)
    type(vamp_grids), intent(inout) :: g
    integer, intent(in) :: unit
    integer :: proc_id
    call mpi90_rank (proc_id)
    if (proc_id == VAMP_ROOT) then
        call vamp0_read_grids (g%g0, unit)
    end if
end subroutine read_grids_unit

```

184b *(Implementation of vampi procedures 166d)*+≡

```

subroutine write_grids_name (g, name)
    type(vamp_grids), intent(inout) :: g
    character(len=*), intent(in) :: name
    integer :: proc_id
    call mpi90_rank (proc_id)
    if (proc_id == VAMP_ROOT) then
        call vamp0_write_grids (g%g0, name)
    end if
end subroutine write_grids_name

```

184c *(Implementation of vampi procedures 166d)*+≡

```

subroutine read_grids_name (g, name)
    type(vamp_grids), intent(inout) :: g
    character(len=*), intent(in) :: name
    integer :: proc_id
    call mpi90_rank (proc_id)
    if (proc_id == VAMP_ROOT) then
        call vamp0_read_grids (g%g0, name)
    end if
end subroutine read_grids_name

```

5.3.4 Communicating Grids

184d *(Declaration of vampi procedures 166b)*+≡

```

public :: vamp_send_grid

```

```

public :: vamp_receive_grid
public :: vamp_broadcast_grid
public :: vamp_broadcast_grids

```

-  The next two are still kludged. Nicer implementations with one message less per call below, but MPICH does funny things during `mpi_get_count`, which is called by `mpi90_receive_pointer`.

Caveat: this `vamp_send_grid` uses *three* tags: `tag`, `tag+1` and `tag+2`:

185a *<Implementation of vampi procedures 166d>+≡*

```

subroutine vamp_send_grid (g, target, tag, domain, error)
    type(vamp_grid), intent(in) :: g
    integer, intent(in) :: target, tag
    integer, intent(in), optional :: domain
    integer, intent(out), optional :: error
    integer, dimension(2) :: words
    integer, dimension(:, ), allocatable :: ibuf
    real(kind=default), dimension(:, ), allocatable :: dbuf
    call vamp_marshal_grid_size (g, words(1), words(2))
    allocate (ibuf(words(1)), dbuf(words(2)))
    call vamp_marshal_grid (g, ibuf, dbuf)
    call mpi90_send (words, target, tag, domain, error)
    call mpi90_send (ibuf, target, tag+1, domain, error)
    call mpi90_send (dbuf, target, tag+2, domain, error)
    deallocate (ibuf, dbuf)
end subroutine vamp_send_grid

```

185b *<Implementation of vampi procedures 166d>+≡*

```

subroutine vamp_receive_grid (g, source, tag, domain, status, error)
    type(vamp_grid), intent(inout) :: g
    integer, intent(in) :: source, tag
    integer, intent(in), optional :: domain
    type(mpi90_status), intent(out), optional :: status
    integer, intent(out), optional :: error
    integer, dimension(2) :: words
    integer, dimension(:, ), allocatable :: ibuf
    real(kind=default), dimension(:, ), allocatable :: dbuf
    call mpi90_receive (words, source, tag, domain, status, error)
    allocate (ibuf(words(1)), dbuf(words(2)))
    call mpi90_receive (ibuf, source, tag+1, domain, status, error)
    call mpi90_receive (dbuf, source, tag+2, domain, status, error)
    call vamp_unmarshal_grid (g, ibuf, dbuf)
    deallocate (ibuf, dbuf)

```

```
end subroutine vamp_receive_grid
```

Caveat: the real `vamp_send_grid` uses *two* tags: `tag` and `tag+1`:

186a *(Implementation of vampi procedures (doesn't work with MPICH yet) 186a)*≡
 subroutine vamp_send_grid (g, target, tag, domain, error)
 type(vamp_grid), intent(in) :: g
 integer, intent(in) :: target, tag
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 integer :: iwords, dwords
 integer, dimension(:), allocatable :: ibuf
 real(kind=default), dimension(:), allocatable :: dbuf
 call vamp_marshal_grid_size (g, iwords, dwords)
 allocate (ibuf(iwords), dbuf(dwords))
 call vamp_marshal_grid (g, ibuf, dbuf)
 call mpi90_send (ibuf, target, tag, domain, error)
 call mpi90_send (dbuf, target, tag+1, domain, error)
 deallocate (ibuf, dbuf)
 end subroutine vamp_send_grid

⌚ There's something wrong with MPICH: if I call `mpi90_receive_pointer` in the opposite order, the low level call to `mpi_get_count` bombs for no apparent reason!

⌚ There are also funky things going on with tag: `mpi90_receive_pointer` should leave it alone, but ...

186b *(Implementation of vampi procedures (doesn't work with MPICH yet) 186a)*+≡
 subroutine vamp_receive_grid (g, source, tag, domain, status, error)
 type(vamp_grid), intent(inout) :: g
 integer, intent(in) :: source, tag
 integer, intent(in), optional :: domain
 type(mpi90_status), intent(out), optional :: status
 integer, intent(out), optional :: error
 integer, dimension(:), pointer :: ibuf
 real(kind=default), dimension(:), pointer :: dbuf
 nullify (ibuf, dbuf)
 call mpi90_receive_pointer (dbuf, source, tag+1, domain, status, error)
 call mpi90_receive_pointer (ibuf, source, tag, domain, status, error)
 call vamp_unmarshal_grid (g, ibuf, dbuf)
 deallocate (ibuf, dbuf)
 end subroutine vamp_receive_grid

This if not a good idea, with respect to communication costs. For SMP machines, it appears to be negligible however.

- 187a *<Interfaces of vampi procedures 170d>+≡*
- ```
interface vamp_broadcast_grid
 module procedure &
 vamp_broadcast_one_grid, vamp_broadcast_many_grids
end interface
```
- 187b *<Implementation of vampi procedures 166d>+≡*
- ```
subroutine vamp_broadcast_one_grid (g, root, domain, error)
    type(vamp_grid), intent(inout) :: g
    integer, intent(in) :: root
    integer, intent(in), optional :: domain
    integer, intent(out), optional :: error
    integer, dimension(:), allocatable :: ibuf
    real(kind=default), dimension(:), allocatable :: dbuf
    integer :: iwords, dwords, me
    call mpi90_rank (me)
    if (me == root) then
        call vamp_marshal_grid_size (g, iwords, dwords)
    end if
    call mpi90_broadcast (iwords, root, domain, error)
    call mpi90_broadcast (dwords, root, domain, error)
    allocate (ibuf(iwords), dbuf(dwords))
    if (me == root) then
        call vamp_marshal_grid (g, ibuf, dbuf)
    end if
    call mpi90_broadcast (ibuf, root, domain, error)
    call mpi90_broadcast (dbuf, root, domain, error)
    if (me /= root) then
        call vamp_unmarshal_grid (g, ibuf, dbuf)
    end if
    deallocate (ibuf, dbuf)
end subroutine vamp_broadcast_one_grid
```
- 187c *<Implementation of vampi procedures 166d>+≡*
- ```
subroutine vamp_broadcast_many_grids (g, root, domain, error)
 type(vamp_grid), dimension(:,), intent(inout) :: g
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 integer :: i
 do i = 1, size(g)
```

```

 call vamp_broadcast_one_grid (g(i), root, domain, error)
 end do
end subroutine vamp_broadcast_many_grids

```

188a *<Implementation of vampi procedures 166d>+≡*

```

subroutine vamp_broadcast_grids (g, root, domain, error)
 type(vamp0_grids), intent(inout) :: g
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 integer :: nch, me
 call mpi90_broadcast (g%sum_chi2, root, domain, error)
 call mpi90_broadcast (g%sum_integral, root, domain, error)
 call mpi90_broadcast (g%sum_weights, root, domain, error)
 call mpi90_rank (me)
 if (me == root) then
 nch = size (g%grids)
 end if
 call mpi90_broadcast (nch, root, domain, error)
 if (me /= root) then
 if (associated (g%grids)) then
 if (size (g%grids) /= nch) then
 call vamp0_delete_grid (g%grids)
 deallocate (g%grids, g%weights, g%num_calls)
 allocate (g%grids(nch), g%weights(nch), g%num_calls(nch))
 call vamp_create_empty_grid (g%grids)
 end if
 else
 allocate (g%grids(nch), g%weights(nch), g%num_calls(nch))
 call vamp_create_empty_grid (g%grids)
 end if
 end if
 call vamp_broadcast_grid (g%grids, root, domain, error)
 call mpi90_broadcast (g%weights, root, domain, error)
 call mpi90_broadcast (g%num_calls, root, domain, error)
end subroutine vamp_broadcast_grids

```

188b *<Declaration of vampi procedures 166b>+≡*

```

public :: vamp_send_history
public :: vamp_receive_history

```

188c *<Implementation of vampi procedures 166d>+≡*

```

subroutine vamp_send_history (g, target, tag, domain, error)

```

```

type(vamp_history), intent(in) :: g
integer, intent(in) :: target, tag
integer, intent(in), optional :: domain
integer, intent(out), optional :: error
integer, dimension(2) :: words
integer, dimension(:), allocatable :: ibuf
real(kind=default), dimension(:), allocatable :: dbuf
call vamp_marshal_history_size (g, words(1), words(2))
allocate (ibuf(words(1)), dbuf(words(2)))
call vamp_marshal_history (g, ibuf, dbuf)
call mpi90_send (words, target, tag, domain, error)
call mpi90_send (ibuf, target, tag+1, domain, error)
call mpi90_send (dbuf, target, tag+2, domain, error)
deallocate (ibuf, dbuf)
end subroutine vamp_send_history

```

189 <*Implementation of vampi procedures 166d*>+≡

```

subroutine vamp_receive_history (g, source, tag, domain, status, error)
type(vamp_history), intent(inout) :: g
integer, intent(in) :: source, tag
integer, intent(in), optional :: domain
type(MPI_Status), intent(out), optional :: status
integer, intent(out), optional :: error
integer, dimension(2) :: words
integer, dimension(:), allocatable :: ibuf
real(kind=default), dimension(:), allocatable :: dbuf
call mpi90_receive (words, source, tag, domain, status, error)
allocate (ibuf(words(1)), dbuf(words(2)))
call mpi90_receive (ibuf, source, tag+1, domain, status, error)
call mpi90_receive (dbuf, source, tag+2, domain, status, error)
call vamp_unmarshal_history (g, ibuf, dbuf)
deallocate (ibuf, dbuf)
end subroutine vamp_receive_history

```

# —6—

## SELF TEST

### 6.1 No Mapping Mode

In this chapter we perform a test of the major features of Vamp. A function with many peaks is integrated with the traditional Vegas algorithm, using a multi-channel approach and in parallel. The function is constructed to have a known analytical integral (which is chosen to be one) in order to be able to gauge the accuracy of the result and error estimate.

#### 6.1.1 Serial Test

```
190a <vamp_test.f90 190a>≡
 ! vamp_test.f90 --
 <Copyleft notice 1>
 <Module vamp_test_functions 190b>
 <Module vamp_tests 194b>

190b <Module vamp_test_functions 190b>≡
 module vamp_test_functions
 use kinds
 use constants, only: PI
 use coordinates
 use vamp, only: vamp_grid, vamp_multi_channel
 implicit none
 private
 public :: f, j, phi, ihp, w
 public :: lorentzian
 private :: lorentzian_normalized
 real(kind=default), public :: width
 contains
 <Implementation of vamp_test_functions procedures 191a>
 end module vamp_test_functions
```

$$\int_{x_1}^{x_2} dx \frac{1}{(x - x_0)^2 + a^2} = \frac{1}{a} \left( \text{atan} \left( \frac{x_2 - x_0}{a} \right) - \text{atan} \left( \frac{x_1 - x_0}{a} \right) \right) = N(x_0, x_1, x_2, a) \quad (6.1)$$

191a *Implementation of vamp\_test\_functions procedures 191a*≡

```
pure function lorentzian_normalized (x, x0, x1, x2, a) result (f)
 real(kind=default), intent(in) :: x, x0, x1, x2, a
 real(kind=default) :: f
 if (x1 <= x .and. x <= x2) then
 f = 1 / ((x - x0)**2 + a**2) &
 * a / (atan2 (x2 - x0, a) - atan2 (x1 - x0, a))
 else
 f = 0
 end if
end function lorentzian_normalized
```

$$\int d^n x f(x) = \int d\Omega_n r^{n-1} dr f(x) = 1 \quad (6.2)$$

191b *Implementation of vamp\_test\_functions procedures 191a*+≡

```
pure function lorentzian (x, x0, x1, x2, r0, a) result (f)
 real(kind=default), dimension(:), intent(in) :: x, x0, x1, x2
 real(kind=default), intent(in) :: r0, a
 real(kind=default) :: f
 real(kind=default) :: r, r1, r2
 integer :: n
 n = size (x)
 if (n > 1) then
 r = sqrt (dot_product (x-x0, x-x0))
 r1 = 0.4_default
 r2 = min (minval (x2-x0), minval (x0-x1))
 if (r1 <= r .and. r <= r2) then
 f = lorentzian_normalized (r, r0, r1, r2, a) * r**(-n) / surface (n)
 else
 f = 0
 end if
 else
 f = lorentzian_normalized (x(1), x0(1), x1(1), x2(1), a)
 endif
end function lorentzian
```

191c *Implementation of vamp\_test\_functions procedures 191a*+≡

```
pure function f (x, prc_index, weights, channel, grids) result (f_x)
 real(kind=default), dimension(:), intent(in) :: x
 integer, intent(in) :: prc_index
 real(kind=default), dimension(:), intent(in), optional :: weights
```

```

integer, intent(in), optional :: channel
type(vamp_grid), dimension(:), intent(in), optional :: grids
real(kind=default) :: f_x
real(kind=default), dimension(size(x)) :: minus_one, plus_one, zero, w_i, f_i
integer :: n, i
n = size(x)
minus_one = -1
zero = 0
plus_one = 1
w_i = 1
do i = 1, n
 if (all (abs (x(i+1:)) <= 1)) then
 f_i = lorentzian (x(1:i), zero(1:i), minus_one(1:i), plus_one(1:i), &
 0.7_default, width) &
 / 2.0_default** (n-i)
 else
 f_i = 0
 end if
end do
f_x = dot_product (w_i, f_i) / sum (w_i)
end function f

```

192 <Implementation of vamp\_test\_functions procedures 191a>+≡

```

pure function phi (xi, channel) result (x)
 real(kind=default), dimension(:), intent(in) :: xi
 integer, intent(in) :: channel
 real(kind=default), dimension(size(xi)) :: x
 real(kind=default) :: r
 real(kind=default), dimension(0) :: dummy
 integer :: n
 n = size(x)
 if (channel == 1) then
 x = xi
 else if (channel == 2) then
 r = (xi(1) + 1) / 2 * sqrt (2.0_default)
 x(1:2) = spherical_cos_to_cartesian (r, PI * xi(2), dummy)
 x(3:) = xi(3:)
 else if (channel < n) then
 r = (xi(1) + 1) / 2 * sqrt (real (channel, kind=default))
 x(1:channel) = spherical_cos_to_cartesian (r, PI * xi(2), xi(3:channel))
 x(channel+1:) = xi(channel+1:)
 else if (channel == n) then
 r = (xi(1) + 1) / 2 * sqrt (real (channel, kind=default))
 x = spherical_cos_to_cartesian (r, PI * xi(2), xi(3:))
 end if
end function phi

```

```

 else
 x = 0
 end if
 end function phi

193a <Implementation of vamp_test_functions procedures 191a>+≡
pure function ihp (x, channel) result (xi)
 real(kind=default), dimension(:), intent(in) :: x
 integer, intent(in) :: channel
 real(kind=default), dimension(size(x)) :: xi
 real(kind=default) :: r, phi
 integer :: n
 n = size(x)
 if (channel == 1) then
 xi = x
 else if (channel == 2) then
 call cartesian_to_spherical_cos (x(1:2), r, phi)
 xi(1) = 2 * r / sqrt (2.0_default) - 1
 xi(2) = phi / PI
 xi(3:) = x(3:)
 else if (channel < n) then
 call cartesian_to_spherical_cos (x(1:channel), r, phi, xi(3:channel))
 xi(1) = 2 * r / sqrt (real (channel, kind=default)) - 1
 xi(2) = phi / PI
 xi(channel+1:) = x(channel+1:)
 else if (channel == n) then
 call cartesian_to_spherical_cos (x, r, phi, xi(3:))
 xi(1) = 2 * r / sqrt (real (channel, kind=default)) - 1
 xi(2) = phi / PI
 else
 xi = 0
 end if
end function ihp

193b <Implementation of vamp_test_functions procedures 191a>+≡
pure function j (x, prc_index, channel) result (j_x)
 real(kind=default), dimension(:), intent(in) :: x
 integer, intent(in) :: prc_index
 integer, intent(in) :: channel
 real(kind=default) :: j_x
 if (channel == 1) then
 j_x = 1
 else if (channel > 1) then
 j_x = 2 / sqrt (real (channel, kind=default)) ! 1/|dr/dξ₁|
 j_x = j_x / PI ! 1/|dφ/dξ₂|

```

```

 j_x = j_x * cartesian_to_spherical_cos_j (x(1:channel))
 else
 j_x = 0
 end if
end function j

194a <Implementation of vamp_test_functions procedures 191a>+≡
pure function w (x, prc_index, weights, channel, grids) result (w_x)
 real(kind=default), dimension(:), intent(in) :: x
 integer, intent(in) :: prc_index
 real(kind=default), dimension(:), intent(in), optional :: weights
 integer, intent(in), optional :: channel
 type(vamp_grid), dimension(:), intent(in), optional :: grids
 real(kind=default) :: w_x
 w_x = vamp_multi_channel (f, prc_index, phi, ihp, j, x, weights, channel, grids)
end function w

194b <Module vamp_tests 194b>≡
module vamp_tests
 use kinds
 use exceptions
 use histograms
 use tao_random_numbers
 use coordinates
 use vamp
 use vamp_test_functions !NODEP!
 implicit none
 private
 <Declaration of procedures in vamp_tests 194c>
contains
 <Implementation of procedures in vamp_tests 195a>
end module vamp_tests

```

### *Verification*

```

194c <Declaration of procedures in vamp_tests 194c>≡
 ! public :: check_jacobians, check_inverses, check_inverses3
 public :: check_inverses, check_inverses3

194d <Implementation of procedures in vamp_tests (broken?) 194d>≡
 subroutine check_jacobians (rng, region, weights, samples)
 type(tao_random_state), intent(inout) :: rng
 real(kind=default), dimension(:, :), intent(in) :: region
 real(kind=default), dimension(:,), intent(in) :: weights
 integer, intent(in) :: samples

```

```

real(kind=default), dimension(size(region,dim=2)) :: x
real(kind=default) :: d
integer :: ch
integer, parameter :: prc_index = 1
do ch = 1, size(weights)
 call vamp_check_jacobian (rng, samples, j, prc_index, phi, ch, region, d, x)
 print *, "channel", ch, ": delta(j)/j=", real(d), ", @x=", real (x)
end do
end subroutine check_jacobians

```

195a <Implementation of procedures in vamp\_tests 195a>≡

```

subroutine check_inverses (rng, region, weights, samples)
 type(tao_random_state), intent(inout) :: rng
 real(kind=default), dimension(:, :,), intent(in) :: region
 real(kind=default), dimension(:,), intent(in) :: weights
 integer, intent(in) :: samples
 real(kind=default), dimension(size(region,dim=2)) :: x1, x2, x_dx
 real(kind=default) :: dx, dx_max
 integer :: ch, i
 dx_max = 0
 x_dx = 0
 do ch = 1, size(weights)
 do i = 1, samples
 call tao_random_number (rng, x1)
 x2 = ihp (phi (x1, ch), ch)
 dx = sqrt (dot_product (x1-x2, x1-x2))
 if (dx > dx_max) then
 dx_max = dx
 x_dx = x1
 end if
 end do
 print *, "channel", ch, ": |x-x|=", real(dx), ", @x=", real (x_dx)
 end do
end subroutine check_inverses

```

195b <Implementation of procedures in vamp\_tests 195a>+≡

```

subroutine check_inverses3 (rng, region, samples)
 type(tao_random_state), intent(inout) :: rng
 real(kind=default), dimension(:, :,), intent(in) :: region
 integer, intent(in) :: samples
 real(kind=default), dimension(size(region,dim=2)) :: x1, x2, x_dx, x_dj
 real(kind=default) :: r, phi, jac, caj, dx, dx_max, dj, dj_max
 real(kind=default), dimension(size(x1)-2) :: cos_theta
 integer :: i
 dx_max = 0

```

```

x_dx = 0
dj_max = 0
x_dj = 0
do i = 1, samples
 call tao_random_number (rng, x1)
 call cartesian_to_spherical_cos_2 (x1, r, phi, cos_theta, jac)
 call spherical_cos_to_cartesian_2 (r, phi, cos_theta, x2, caj)
 dx = sqrt (dot_product (x1-x2, x1-x2))
 dj = jac*caj - 1
 if (dx > dx_max) then
 dx_max = dx
 x_dx = x1
 end if
 if (dj > dj_max) then
 dj_max = dj
 x_dj = x1
 end if
end do
print *, "channel 3 : j*j-1=", real(dj), ", @x=", real (x_dj)
print *, "channel 3 : |x-x|=", real(dx), ", @x=", real (x_dx)
end subroutine check_inverses3

```

### *Integration*

- 196a *(Declaration of procedures in vamp\_tests 194c)*+≡  
     public :: single\_channel, multi\_channel
- 196b *(Implementation of procedures in vamp\_tests 195a)*+≡  
     subroutine single\_channel (rng, region, samples, iterations, &  
         integral, standard\_dev, chi\_squared)  
         type(tao\_random\_state), intent(inout) :: rng  
         real(kind=default), dimension(:, :, ), intent(in) :: region  
         integer, dimension(:), intent(in) :: samples, iterations  
         real(kind=default), intent(out) :: integral, standard\_dev, chi\_squared  
         type(vamp\_grid) :: gr  
         type(vamp\_history), dimension(iterations(1)+iterations(2)) :: history  
         integer, parameter :: PRC\_INDEX = 1  
         call vamp\_create\_history (history)  
         call vamp\_create\_grid (gr, region, samples(1))  
         call vamp\_sample\_grid (rng, gr, f, PRC\_INDEX, iterations(1), history = history)  
         call vamp\_discard\_integral (gr, samples(2))  
         call vamp\_sample\_grid &  
             (rng, gr, f, PRC\_INDEX, iterations(2), &  
             integral, standard\_dev, chi\_squared, &

```

 history = history(iterations(1)+1:))
call vamp_write_grid (gr, "vamp_test.grid")
call vamp_delete_grid (gr)
call vamp_print_history (history, "single")
call vamp_delete_history (history)
end subroutine single_channel

197a <Implementation of procedures in vamp_tests 195a>+≡
subroutine multi_channel (rng, region, weights, samples, iterations, powers, &
 integral, standard_dev, chi_squared)
 type(tao_random_state), intent(inout) :: rng
 real(kind=default), dimension(:, :,), intent(in) :: region
 real(kind=default), dimension(:,), intent(inout) :: weights
 integer, dimension(:,), intent(in) :: samples, iterations
 real(kind=default), dimension(:,), intent(in) :: powers
 real(kind=default), intent(out) :: integral, standard_dev, chi_squared
 type(vamp_grids) :: grs
 <Body of multi_channel 197b>
end subroutine multi_channel

197b <Body of multi_channel 197b>≡
type(vamp_history), dimension(iterations(1)+iterations(2)+size(powers)-1) :: &
 history
type(vamp_history), dimension(size(history), size(weights)) :: histories
integer :: it, nit
integer, parameter :: PRC_INDEX = 1
nit = size (powers)
call vamp_create_history (history)
call vamp_create_history (histories)
call vamp_create_grids (grs, region, samples(1), weights)
call vamp_sample_grids (rng, grs, w, PRC_INDEX, iterations(1) - 1, &
 history = history, histories = histories)
call vamp_print_history (history, "multi")
call vamp_print_history (histories, "multi")
do it = 1, nit
 call vamp_sample_grids (rng, grs, w, PRC_INDEX, 1, &
 history = history(iterations(1)+it-1:), &
 histories = histories(iterations(1)+it-1:,:))
 call vamp_print_history (history(iterations(1)+it-1:), "multi")
 call vamp_print_history (histories(iterations(1)+it-1:,:), "multi")
 call vamp_refine_weights (grs, powers(it))
end do
call vamp_discard_integrals (grs, samples(2))
call vamp_sample_grids &
 (rng, grs, w, PRC_INDEX, iterations(2), &

```

```

integral, standard_dev, chi_squared, &
history = history(iterations(1)+nit,:), &
histories = histories(iterations(1)+nit,:,:))
call vamp_print_history (history(iterations(1)+nit,:), "multi")
call vamp_print_history (histories(iterations(1)+nit,:,:), "multi")
call vamp_write_grids (grs, "vamp_test.grids")
call vamp_delete_grids (grs)
call vamp_print_history (history, "multi")
call vamp_print_history (histories, "multi")
call vamp_delete_history (history)
call vamp_delete_history (histories)

```

*Input/Output*

198a ⟨Declaration of procedures in vamp\_tests 194c⟩+≡

```
public :: print_results
```

198b ⟨Implementation of procedures in vamp\_tests 195a⟩+≡

```

subroutine print_results (prefix, prev_ticks, &
 integral, std_dev, chi2, acceptable, failures)
character(len=*), intent(in) :: prefix
integer, intent(in) :: prev_ticks
real(kind=default), intent(in) :: integral, std_dev, chi2, acceptable
integer, intent(inout) :: failures
integer :: ticks, ticks_per_second
real(kind=default) :: pull
call system_clock (ticks, ticks_per_second)
pull = (integral - 1) / std_dev
print "(1X,A,A,F6.2,A)", prefix, &
 ": time = ", real (ticks - prev_ticks) / ticks_per_second, " secs"
print *, prefix, ": int, err, chi2: ", &
 real (integral), real (std_dev), real (chi2)
if (abs (pull) > acceptable) then
 failures = failures + 1
 print *, prefix, ": unacceptable pull:", real (pull)
else
 print *, prefix, ": acceptable pull:", real (pull)
end if
end subroutine print_results

```

*Main Program*

198c ⟨vamp\_test.f90 190a⟩+≡

```
program vamp_test
```

```

use kinds
use tao_random_numbers
use coordinates
use divisions, only: DIVISIONS_RCS_ID
use vamp
use vamp_test_functions !NODEP!
use vamp_tests !NODEP!
implicit none
integer :: start_ticks
integer, dimension(2) :: iterations, samples
real(kind=default), dimension(2,5) :: region
real(kind=default), dimension(5) :: weight_vector
real(kind=default), dimension(10) :: powers
real(kind=default) :: single_integral, single_standard_dev, single_chi_squared
real(kind=default) :: multi_integral, multi_standard_dev, multi_chi_squared
type(tao_random_state) :: rng
real(kind=default), parameter :: ACCEPTABLE = 4
integer :: failures
failures = 0
call tao_random_create (rng, 0)
call system_clock (start_ticks)
call tao_random_seed (rng, start_ticks)
iterations = (/ 4, 3 /)
samples = (/ 20000, 200000 /)
region(1,:) = -1.0
region(2,:) = 1.0
width = 0.0001
print *, "Starting VAMP 1.0 self test..."
print *, "serial code"
print *, VAMP_RCS_ID
print *, DIVISIONS_RCS_ID
call system_clock (start_ticks)
call single_channel (rng, region, samples, iterations, &
 single_integral, single_standard_dev, single_chi_squared)
call print_results ("SINGLE", start_ticks, &
 single_integral, single_standard_dev, single_chi_squared, &
 10*ACCEPTABLE, failures)
weight_vector = 1
powers = 0.25_default
call system_clock (start_ticks)
call multi_channel (rng, region, weight_vector, samples, iterations, &
 powers, multi_integral, multi_standard_dev, multi_chi_squared)
call print_results ("MULTI", start_ticks, &

```

```

 multi_integral, multi_standard_dev, multi_chi_squared, &
 ACCEPTABLE, failures)
call system_clock (start_ticks)
! call check_jacobians (rng, region, weight_vector, samples(1))
call check_inverses (rng, region, weight_vector, samples(1))
call check_inverses3 (rng, region, samples(1))
if (failures == 0) then
 stop 0
else if (failures == 1) then
 stop 1
else
 stop 2
end if
end program vamp_test

```

### 6.1.2 Parallel Test

200a <vampi\_test.f90 200a>≡  
   ! vampi\_test.f90 --  
   ⟨Copyleft notice 1⟩  
   ⟨Module vamp\_test\_functions 190b⟩

The following is identical to vamp\_tests, except for use vampi:

200b <vampi\_test.f90 200a>+≡  
   module vampi\_tests  
     use kinds  
     use exceptions  
     use histograms  
     use tao\_random\_numbers  
     use coordinates  
     use vampi  
     use vamp\_test\_functions !NODEP!  
     implicit none  
     private  
       ⟨Declaration of procedures in vampi\_tests 194c⟩  
     contains  
       ⟨Implementation of procedures in vampi\_tests 195a⟩  
     end module vampi\_tests

200c <vampi\_test.f90 200a>+≡  
   program vampi\_test  
     use kinds  
     use tao\_random\_numbers  
     use coordinates

```

use divisions, only: DIVISIONS_RCS_ID
use vamp, only: VAMP_RCS_ID
use vampi
use mpi90
use vamp_test_functions !NODEP!
use vampi_tests !NODEP!
implicit none
integer :: num_proc, proc_id, start_ticks
logical :: perform_io
integer, dimension(2) :: iterations, samples
real(kind=default), dimension(2,5) :: region
real(kind=default), dimension(5) :: weight_vector
real(kind=default), dimension(10) :: powers
real(kind=default) :: single_integral, single_standard_dev, single_chi_squared
real(kind=default) :: multi_integral, multi_standard_dev, multi_chi_squared
type(tao_random_state) :: rng
integer :: iostat, command
character(len=72) :: command_line
integer, parameter :: &
 CMD_ERROR = -1, CMD_END = 0, &
 CMD_NOP = 1, CMD_SINGLE = 2, CMD_MULTI = 3, CMD_CHECK = 4
call tao_random_create (rng, 0)
call mpi90_init ()
call mpi90_size (num_proc)
call mpi90_rank (proc_id)
perform_io = (proc_id == 0)
call system_clock (start_ticks)
call tao_random_seed (rng, start_ticks + proc_id)
iterations = (/ 4, 3 /)
samples = (/ 20000, 200000 /)
samples = (/ 200000, 2000000 /)
region(1,:) = -1.0
region(2,:) = 1.0
width = 0.0001
if (perform_io) then
 print *, "Starting VAMP 1.0 self test..."
 if (num_proc > 1) then
 print *, "parallel code running on ", num_proc, " processors"
 else
 print *, "parallel code running serially"
 end if
 print *, VAMP_RCS_ID
 print *, VAMPI_RCS_ID

```

```

 print *, DIVISIONS_RCS_ID
end if
command_loop: do
 <Parse the commandline in vamp_test and set command (never defined)>
 call mpi90_broadcast (command, 0)
 call system_clock (start_ticks)
 select case (command)
 <Execute command in vamp_test (never defined)>
 case (CMD_END)
 exit command_loop
 case (CMD_NOP)
 ! do nothing
 case (CMD_ERROR)
 ! do nothing
 end select
 end do command_loop
 call mpi90_finalize ()
end program vampi_test

```

### 6.1.3 Output

202a ⟨vamp\_test.out 202a⟩≡

## 6.2 Mapped Mode

In this chapter we perform a test of the major features of Vamp. A function with many peaks is integrated with the traditional Vegas algorithm, using a multi-channel approach and in parallel. The function is constructed to have a known analytical integral (which is chosen to be one) in order to be able to gauge the accuracy of the result and error estimate.

### 6.2.1 Serial Test

202b ⟨vamp\_test0.f90 202b⟩≡  
! vamp\_test0.f90 --  
⟨Copyleft notice 1⟩  
⟨Module vamp\_test0\_functions 203⟩

### Single Channel

The functions to be integrated are shared by the serial and the parallel incarnation of the code.

```
203 <Module vamp_test0_functions 203>≡
 module vamp_test0_functions
 use kinds
 use vamp, only: vamp_grid, vamp_multi_channel0
 implicit none
 private
 public :: f, g, phi, w
 public :: create_sample, delete_sample
 private :: f0, psi, g0, f_norm
 real(kind=default), dimension(:), allocatable, private :: c, x_min, x_max
 real(kind=default), dimension(:,:,:,:), allocatable, public :: x0, gamma
 contains
 <Implementation of vamp_test0_functions procedures 204a>
 end module vamp_test0_functions
```

We start from a model of  $n_p$  interfering resonances in one variable (cf. section ??)

$$f_0(x|x_{\min}, x_{\max}, x_0, \gamma) = \frac{1}{N(x_{\min}, x_{\max}, x_0, \gamma)} \left| \sum_{p=1}^{n_p} \frac{1}{x - x_{0,p} + i\gamma_p} \right|^2 \quad (6.3)$$

where

$$N(x_{\min}, x_{\max}, x_0, \gamma) = \int_{x_{\min}}^{x_{\max}} dx \left| \sum_{p=1}^{n_p} \frac{1}{x - x_{0,p} + i\gamma_p} \right|^2 \quad (6.4)$$

such that

$$\int_{x_{\min}}^{x_{\max}} dx f_0(x|x_{\min}, x_{\max}, x_0, \gamma) = 1 \quad (6.5)$$

NB: the  $N(x_{\min}, x_{\max}, x_0, \gamma)$  should be calculated once and tabulated to save processing time, but we are lazy here.

$$\begin{aligned} N(x_{\min}, x_{\max}, x_0, \gamma) &= \sum_{p=1}^{n_p} \int_{x_{\min}}^{x_{\max}} dx \left| \frac{1}{x - x_{0,p} + i\gamma_p} \right|^2 \\ &\quad + 2 \operatorname{Re} \sum_{p=1}^{n_p} \sum_{q=1}^{n_p} \int_{x_{\min}}^{x_{\max}} dx \frac{1}{x - x_{0,p} + i\gamma_p} \frac{1}{x - x_{0,q} - i\gamma_q} \end{aligned} \quad (6.6)$$

204a *(Implementation of vamp\_test0\_functions procedures 204a)*≡

```

pure function f0 (x, x_min, x_max, x0, g) result (f_x)
 real(kind=default), intent(in) :: x, x_min, x_max
 real(kind=default), dimension(:), intent(in) :: x0, g
 real(kind=default) :: f_x
 complex(kind=default) :: amp
 real(kind=default) :: norm
 integer :: i, j
 amp = sum (1.0 / cmplx (x - x0, g, kind=default))
 norm = 0
 do i = 1, size (x0)
 norm = norm + f_norm (x_min, x_max, x0(i), g(i), x0(i), g(i))
 do j = i + 1, size (x0)
 norm = norm + 2 * f_norm (x_min, x_max, x0(i), g(i), x0(j), g(j))
 end do
 end do
 f_x = amp * conjg (amp) / norm
end function f0

```

$$\int_{x_{\min}}^{x_{\max}} dx \frac{1}{x - x_{0,p} + i\gamma_p} \frac{1}{x - x_{0,q} - i\gamma_q} = \frac{1}{x_{0,p} - x_{0,q} - i\gamma_p - i\gamma_q} \left( \ln \left( \frac{x_{\max} - x_{0,p} + i\gamma_p}{x_{\min} - x_{0,p} + i\gamma_p} \right) - \ln \left( \frac{x_{\max} - x_{0,q} - i\gamma_q}{x_{\min} - x_{0,q} - i\gamma_q} \right) \right) \quad (6.7)$$

Don't even think of merging the logarithms: it will screw up the Riemann sheet.

204b *(Implementation of vamp\_test0\_functions procedures 204a)*+≡

```

pure function f_norm (x_min, x_max, x0p, gp, x0q, gq) &
 result (norm)
 real(kind=default), intent(in) :: x_min, x_max, x0p, gp, x0q, gq
 real(kind=default) :: norm
 norm = real ((log (cmplx (x_max - x0p, gp, kind=default) &
 / cmplx (x_min - x0p, gp, kind=default)) &
 - log (cmplx (x_max - x0q, - gq, kind=default) &
 / cmplx (x_min - x0q, - gq, kind=default))) &
 / cmplx (x0p - x0q, - gp - gq, kind=default), &
 kind=default)
end function f_norm

```

Since we want to be able to do the integral of  $f$  analytically, it is most

convenient to take a weighted sum of products:

$$f(x_1, \dots, x_{n_d} | x_{\min}, x_{\max}, x_0, \gamma) = \frac{1}{\sum_{i=1}^{n_c} c_i} \sum_{i=1}^{n_c} c_i \prod_{j=1}^{n_d} f_0(x_j | x_{\min,j}, x_{\max,j}, x_{0,ij}, \gamma_{ij}) \quad (6.8)$$

Each summand is factorized and therefore very easily integrated by Vegas. A non-trivial sum is more realistic in this respect.

- 205a *Implementation of vamp\_test0\_functions procedures 204a* +≡
- ```

pure function f (x, prc_index, weights, channel, grids) result (f_x)
    real(kind=default), dimension(:), intent(in) :: x
    integer, intent(in) :: prc_index
    real(kind=default), dimension(:), intent(in), optional :: weights
    integer, intent(in), optional :: channel
    type(vamp_grid), dimension(:), intent(in), optional :: grids
    real(kind=default) :: f_x
    real(kind=default) :: fi_x
    integer :: i, j
    f_x = 0.0
    do i = 1, size (c)
        fi_x = 1.0
        do j = 1, size (x)
            if (all (gamma(:,i,j) > 0)) then
                fi_x = fi_x * f0 (x(j), x_min(j), x_max(j), &
                    x0(:,i,j), gamma(:,i,j))
            else
                fi_x = fi_x / (x_max(j) - x_min(j))
            end if
        end do
        f_x = f_x + c(i) * fi_x
    end do
    f_x = f_x / sum (c)
end function f

```
- 205b *Implementation of vamp_test0_functions procedures 204a* +≡
- ```

subroutine delete_sample ()
 deallocate (c, x_min, x_max, x0, gamma)
end subroutine delete_sample

```
- 205c *Implementation of vamp\_test0\_functions procedures 204a* +≡
- ```

subroutine create_sample (num_poles, weights, region)
    integer, intent(in) :: num_poles
    real(kind=default), dimension(:), intent(in) :: weights

```

```

real(kind=default), dimension(:,:), intent(in) :: region
integer :: nd, nc
nd = size (region, dim=2)
nc = size (weights)
allocate (c(nc), x_min(nd), x_max(nd))
allocate (x0(num_poles,nc,nd), gamma(num_poles,nc,nd))
x_min = region(1,:)
x_max = region(2,:)
c = weights
end subroutine create_sample

```

Multi Channel

We start from the usual mapping for Lorentzian peaks

$$\begin{aligned} \psi(x_{\min}, x_{\max}, x_0, \gamma) : [x_{\min}, x_{\max}] &\rightarrow [x_{\min}, x_{\max}] \\ \xi \mapsto x = \psi(\xi | x_{\min}, x_{\max}, x_0, \gamma) \end{aligned} \quad (6.9)$$

where

$$\begin{aligned} \psi(\xi | x_{\min}, x_{\max}, x_0, \gamma) = x_0 + \\ \gamma \cdot \tan \left(\frac{\xi - x_{\min}}{x_{\max} - x_{\min}} \cdot \atan \frac{x_{\max} - x_0}{\gamma} - \frac{x_{\max} - \xi}{x_{\max} - x_{\min}} \cdot \atan \frac{x_0 - x_{\min}}{\gamma} \right) \end{aligned} \quad (6.10)$$

206 *Implementation of vamp_test0_functions procedures 204a>+≡*

```

pure function psi (xi, x_min, x_max, x0, gamma) result (x)
    real(kind=default), intent(in) :: xi, x_min, x_max, x0, gamma
    real(kind=default) :: x
    x = x0 + gamma &
        * tan (((xi - x_min) * atan ((x_max - x0) / gamma) &
        - (x_max - xi) * atan ((x0 - x_min) / gamma)) &
        / (x_max - x_min))
end function psi

```

The inverse mapping is

$$\begin{aligned} \psi^{-1}(x_{\min}, x_{\max}, x_0, \gamma) : [x_{\min}, x_{\max}] &\rightarrow [x_{\min}, x_{\max}] \\ x \mapsto \xi = \psi^{-1}(x | x_{\min}, x_{\max}, x_0, \gamma) \end{aligned} \quad (6.11)$$

with

$$\begin{aligned} \psi^{-1}(x | x_{\min}, x_{\max}, x_0, \gamma) = \\ \frac{x_{\max}(\atan \frac{x_0 - x_{\min}}{\gamma} + \atan \frac{x - x_0}{\gamma}) + x_{\min}(\atan \frac{x_{\max} - x_0}{\gamma} + \atan \frac{x_0 - x}{\gamma})}{\atan \frac{x_{\max} - x_0}{\gamma} + \atan \frac{x_0 - x_{\min}}{\gamma}} \end{aligned} \quad (6.12)$$

with Jacobian

$$\frac{d(\psi^{-1}(x|x_{\min}, x_{\max}, x_0, \gamma))}{dx} = \frac{x_{\max} - x_{\min}}{\tan \frac{x_{\max} - x_0}{\gamma} + \tan \frac{x_0 - x_{\min}}{\gamma}} \frac{\gamma}{(x - x_0)^2 + \gamma^2} \quad (6.13)$$

207a *(Implementation of vamp_test0_functions procedures 204a) +≡*

```
pure function g0 (x, x_min, x_max, x0, gamma) result (g_x)
    real(kind=default), intent(in) :: x, x_min, x_max, x0, gamma
    real(kind=default) :: g_x
    g_x = gamma / (atan ((x_max - x0) / gamma) - atan ((x_min - x0) / gamma)) &
        * (x_max - x_min) / ((x - x0)**2 + gamma**2)
end function g0
```

The function f has $n_c n_p^{n_d}$ peaks and we need a channel for each one, plus a constant function for the background. We encode the position on the grid linearly:

207b *(Decode channel into ch and p(:) 207b) +≡*

```
ch = channel - 1
do j = 1, size (x)
    p(j) = 1 + modulo (ch, np)
    ch = ch / np
end do
ch = ch + 1
```

The map ϕ is the direct product of ψ s:

207c *(Implementation of vamp_test0_functions procedures 204a) +≡*

```
pure function phi (xi, channel) result (x)
    real(kind=default), dimension(:, intent(in) :: xi
    integer, intent(in) :: channel
    real(kind=default), dimension(size(xi)) :: x
    integer, dimension(size(xi)) :: p
    integer :: j, ch, np, nch, nd, channels
    np = size (x0, dim = 1)
    nch = size (x0, dim = 2)
    nd = size (x0, dim = 3)
    channels = nch * np**nd
    if (channel >= 1 .and. channel <= channels) then
        <Decode channel into ch and p(:) 207b>
        do j = 1, size (xi)
            if (all (gamma(:,ch,j) > 0)) then
                x(j) = psi (xi(j), x_min(j), x_max(j), &
                    x0(p(j),ch,j), gamma(p(j),ch,j))
            else
                x = xi
            end if
        end do
    else
        x = xi
    end if
end function phi
```

```

        end if
    end do
else if (channel == channels + 1) then
    x = xi
else
    x = 0
end if
end function phi

```

similarly for the Jacobians:

- 208a *(Implementation of vamp_test0_functions procedures 204a)*+≡
- ```

pure recursive function g (x, prc_index, channel) result (g_x)
 real(kind=default), dimension(:), intent(in) :: x
 integer, intent(in) :: prc_index
 integer, intent(in) :: channel
 real(kind=default) :: g_x
 integer, dimension(size(x)) :: p
 integer :: j, ch, np, nch, nd, channels
 np = size (x0, dim = 1)
 nch = size (x0, dim = 2)
 nd = size (x0, dim = 3)
 channels = nch * np**nd
 if (channel >= 1 .and. channel <= channels) then
 <Decode channel into ch and p(:) 207b>
 g_x = 1.0
 do j = 1, size (x)
 if (all (gamma(:,ch,j) > 0)) then
 g_x = g_x * g0 (x(j), x_min(j), x_max(j), &
 x0(p(j),ch,j), gamma(p(j),ch,j))
 end if
 end do
 else if (channel == channels + 1) then
 g_x = 1.0
 else
 g_x = 0
 end if
end function g

```
- 208b *(Implementation of vamp\_test0\_functions procedures 204a)*+≡
- ```

pure function w (x, prc_index, weights, channel, grids) result (w_x)
    real(kind=default), dimension(:), intent(in) :: x
    integer, intent(in) :: prc_index
    real(kind=default), dimension(:), intent(in), optional :: weights
    integer, intent(in), optional :: channel

```

```

type(vamp_grid), dimension(:), intent(in), optional :: grids
real(kind=default) :: w_x
w_x = vamp_multi_channel0 (f, prc_index, phi, g, x, weights, channel)
end function w

```

Driver Routines

209a <vamp_test0.f90 202b>+≡

```

module vamp_tests0
    <Modules used by vamp_tests0 209b>
    use vamp
    implicit none
    private
    <Declaration of procedures in vamp_tests0 210a>
contains
    <Implementation of procedures in vamp_tests0 210b>
end module vamp_tests0

```

209b <Modules used by vamp_tests0 209b>≡

```

use kinds
use exceptions
use histograms
use tao_random_numbers
use vamp_test0_functions !NODEP !

```

Verification

209c <Declaration of procedures in vamp_tests0 (broken?) 209c>≡

```

public :: check_jacobians

```

209d <Implementation of procedures in vamp_tests0 (broken?) 209d>≡

```

subroutine check_jacobians (do_print, region, samples, rng)
    logical, intent(in) :: do_print
    real(kind=default), dimension(:, :, :), intent(in) :: region
    integer, dimension(:, :), intent(in) :: samples
    type(tao_random_state), intent(inout) :: rng
    real(kind=default), dimension(size(region, dim=2)) :: x
    real(kind=default) :: d
    integer :: ch
    do ch = 1, size(x, dim=2) * size(x, dim=1)**size(x, dim=3) + 1
        call vamp_check_jacobian (rng, samples(1), g, phi, ch, region, d, x)
        if (do_print) then
            print *, ch, ": ", d, ", x = ", real (x)
        end if

```

```

    end do
end subroutine check_jacobians
```

Integration

```

210a <Declaration of procedures in vamp_tests0 210a>≡
      public :: single_channel, multi_channel

210b <Implementation of procedures in vamp_tests0 210b>≡
      subroutine single_channel (do_print, region, iterations, samples, rng, &
          acceptable, failures)
          logical, intent(in) :: do_print
          real(kind=default), dimension(:, :, ), intent(in) :: region
          integer, dimension(:, ), intent(in) :: iterations, samples
          type(tao_random_state), intent(inout) :: rng
          real(kind=default), intent(in) :: acceptable
          integer, intent(inout) :: failures
          type(vamp_grid) :: gr
          type(vamp_history), dimension(iterations(1)+iterations(2)) :: history
          real(kind=default) :: integral, standard_dev, chi_squared, pull
          integer, parameter :: PRC_INDEX = 1
          call vamp_create_history (history)
          call vamp_create_grid (gr, region, samples(1))
          call vamp_sample_grid (rng, gr, f, PRC_INDEX, iterations(1), history = history)
          call vamp_discard_integral (gr, samples(2))
          call vamp_sample_grid &
              (rng, gr, f, PRC_INDEX, iterations(2), &
              integral, standard_dev, chi_squared, &
              history = history(iterations(1)+1:))
          call vamp_write_grid (gr, "vamp_test0.grid")
          call vamp_delete_grid (gr)
          call vamp_print_history (history, "single")
          call vamp_delete_history (history)
          pull = (integral - 1) / standard_dev
          if (do_print) then
              print *, "    int, err, chi2:", integral, standard_dev, chi_squared
          end if
          if (abs (pull) > acceptable) then
              failures = failures + 1
              print *, " unacceptable pull:", pull
          else
              print *, "    acceptable pull:", pull
          end if
      end subroutine single_channel
```

```

211a <Implementation of procedures in vamp_tests0 210b>+≡
    subroutine multi_channel (do_print, region, iterations, samples, rng, &
        acceptable, failures)
        logical, intent(in) :: do_print
        real(kind=default), dimension(:, :, :), intent(in) :: region
        integer, dimension(:, :), intent(in) :: iterations, samples
        type(tao_random_state), intent(inout) :: rng
        real(kind=default), intent(in) :: acceptable
        type(vamp_grids) :: grs
        integer, intent(inout) :: failures
        <Body of multi_channel 197b>
    end subroutine multi_channel

211b <Body of multi_channel 197b>+≡
    real(kind=default), &
        dimension(size(x0, dim=2)*size(x0, dim=1)**size(x0, dim=3)+1) :: &
        weight_vector
    type(vamp_history), dimension(iterations(1)+iterations(2)+4) :: history
    type(vamp_history), dimension(size(history), size(weight_vector)) :: histories
    real(kind=default) :: integral, standard_dev, chi_squared, pull
    integer :: it
    integer, parameter :: PRC_INDEX = 1
    weight_vector = 1.0
    call vamp_create_history (history)
    call vamp_create_history (histories)
    call vamp_create_grids (grs, region, samples(1), weight_vector)
    call vamp_sample_grids (rng, grs, w, PRC_INDEX, iterations(1) - 1, &
        history = history, histories = histories)
    do it = 1, 5
        call vamp_sample_grids (rng, grs, w, PRC_INDEX, 1, &
            history = history(iterations(1)+it-1:), &
            histories = histories(iterations(1)+it-1:, :))
        call vamp_refine_weights (grs)
    end do
    call vamp_discard_integrals (grs, samples(2))
    call vamp_sample_grids &
        (rng, grs, w, PRC_INDEX, iterations(2), &
        integral, standard_dev, chi_squared, &
        history = history(iterations(1)+5:), &
        histories = histories(iterations(1)+5:, :))
    call vamp_write_grids (grs, "vamp_test0.grids")
    call vamp_delete_grids (grs)
    call vamp_print_history (history, "multi")
    call vamp_print_history (histories, "multi")

```

```

call vamp_delete_history (history)
call vamp_delete_history (histories)
if (do_print) then
    print *, integral, standard_dev, chi_squared
end if
pull = (integral - 1) / standard_dev
if (abs (pull) > acceptable) then
    failures = failures + 1
    print *, " unacceptable pull:", pull
else
    print *, " acceptable pull:", pull
end if

```

Event Generation

212a *(Declaration of procedures in vamp_tests0 210a)* +≡

```

public :: single_channel_generator, multi_channel_generator

```

212b *(Implementation of procedures in vamp_tests0 210b)* +≡

```

subroutine single_channel_generator (do_print, region, iterations, samples, rng)
    logical, intent(in) :: do_print
    real(kind=default), dimension(:,:,:), intent(in) :: region
    integer, dimension(:, :), intent(in) :: iterations, samples
    type(tao_random_state), intent(inout) :: rng
    type(vamp_grid) :: gr
    type(vamp_history), dimension(iterations(1)+iterations(2)) :: history
    type(histogram) :: unweighted, reweighted, weighted, weights
    type(exception) :: exc
    real(kind=default) :: weight, integral, standard_dev
    integer :: i
    real(kind=default), dimension(size(region,dim=2)) :: x
    integer, parameter :: PRC_INDEX = 1
    call vamp_create_grid (gr, region, samples(1))
    call vamp_sample_grid (rng, gr, f, PRC_INDEX, iterations(1), history = history)
    call vamp_discard_integral (gr, samples(2))
    call vamp_warmup_grid &
        (rng, gr, f, PRC_INDEX, iterations(2), history = history(iterations(1)+1:))
    call vamp_print_history (history, "single")
    call vamp_delete_history (history)
    call create_histogram (unweighted, region(1,1), region(2,1), 100)
    call create_histogram (reweighted, region(1,1), region(2,1), 100)
    call create_histogram (weighted, region(1,1), region(2,1), 100)
    call create_histogram (weights, 0.0_default, 10.0_default, 100)
    ! do i = 1, 1000000

```

```

do i = 1, 100
    call clear_exception (exc)
    call vamp_next_event (x, rng, gr, f, PRC_INDEX, exc = exc)
    call handle_exception (exc)
    call fill_histogram (unweighted, x(1))
    call fill_histogram (reweighted, x(1), 1.0_default / f (x, PRC_INDEX))
end do
integral = 0.0
standard_dev = 0.0
do i = 1, 10000
    call clear_exception (exc)
    call vamp_next_event (x, rng, gr, f, PRC_INDEX, weight, exc = exc)
    call handle_exception (exc)
    call fill_histogram (weighted, x(1), weight / f (x, PRC_INDEX))
    call fill_histogram (weights, x(1), weight)
    integral = integral + weight
    standard_dev = standard_dev + weight**2
end do
if (do_print) then
    print *, integral / (i-1), sqrt (standard_dev) / (i-1)
    call write_histogram (unweighted, "u_s.d")
    call write_histogram (reweighted, "r_s.d")
    call write_histogram (weighted, "w_s.d")
    call write_histogram (weights, "ws_s.d")
end if
call delete_histogram (unweighted)
call delete_histogram (reweighted)
call delete_histogram (weighted)
call delete_histogram (weights)
call vamp_delete_grid (gr)
end subroutine single_channel_generator

```

213 <Implementation of procedures in vamp_tests0 210b>+≡

```

subroutine multi_channel_generator (do_print, region, iterations, samples, rng)
    logical, intent(in) :: do_print
    real(kind=default), dimension(:, :, :), intent(in) :: region
    integer, dimension(:, :), intent(in) :: iterations, samples
    type(tao_random_state), intent(inout) :: rng
    type(vamp_grids) :: grs
    real(kind=default), &
        dimension(size(x0, dim=2)*size(x0, dim=1)**size(x0, dim=3)+1) :: &
        weight_vector
    type(vamp_history), dimension(iterations(1)+iterations(2)+4) :: history
    type(vamp_history), dimension(size(history), size(weight_vector)) :: histories

```

```

type(histogram) :: unweighted, reweighted, weighted, weights
type(exception) :: exc
real(kind=default) :: weight, integral, standard_dev
real(kind=default), dimension(size(region,dim=2)) :: x
character(len=5) :: pfx
integer :: it, i, j
integer, parameter :: PRC_INDEX = 1
weight_vector = 1.0
call vamp_create_history (history)
call vamp_create_history (histories)
call vamp_create_grids (grs, region, samples(1), weight_vector)
call vamp_sample_grids (rng, grs, w, PRC_INDEX, iterations(1) - 1, &
                        history = history, histories = histories)
do it = 1, 5
    call vamp_sample_grids (rng, grs, w, PRC_INDEX, 1, &
                            history = history(iterations(1)+it-1:), &
                            histories = histories(iterations(1)+it-1:, :))
    call vamp_refine_weights (grs)
end do
call vamp_discard_integrals (grs, samples(2))
call vamp_warmup_grids &
    (rng, grs, w, PRC_INDEX, iterations(2), &
     history = history(iterations(1)+5:), &
     histories = histories(iterations(1)+5:, :))
call vamp_print_history (history, "multi")
call vamp_print_history (histories, "multi")
call vamp_delete_history (history)
call vamp_delete_history (histories)
!!! do i = 1, size (grs%grids)
!!!   do j = 1, size (grs%grids(i)%div)
!!!     write (pfx, "(I2.2,'/',I2.2)") i, j
!!!     call dump_division (grs%grids(i)%div(j), pfx)
!!!   end do
!!! end do
call create_histogram (unweighted, region(1,1), region(2,1), 100)
call create_histogram (reweighted, region(1,1), region(2,1), 100)
call create_histogram (weighted, region(1,1), region(2,1), 100)
call create_histogram (weights, 0.0_default, 10.0_default, 100)
! do i = 1, 1000000
do i = 1, 100
    call clear_exception (exc)
    call vamp_next_event (x, rng, grs, f, PRC_INDEX, phi, exc = exc)
    call handle_exception (exc)

```

```

    call fill_histogram (unweighted, x(1))
    call fill_histogram (reweighted, x(1), 1.0_default / f (x, PRC_INDEX))
end do
integral = 0.0
standard_dev = 0.0
do i = 1, 10000
    call clear_exception (exc)
    call vamp_next_event (x, rng, grs, f, PRC_INDEX, phi, weight, exc = exc)
    call handle_exception (exc)
    call fill_histogram (weighted, x(1), weight / f (x, PRC_INDEX))
    call fill_histogram (weights, x(1), weight)
    integral = integral + weight
    standard_dev = standard_dev + weight**2
end do
if (do_print) then
    print *, integral / (i-1), sqrt (standard_dev) / (i-1)
    call write_histogram (unweighted, "u_m.d")
    call write_histogram (reweighted, "r_m.d")
    call write_histogram (weighted, "w_m.d")
    call write_histogram (weights, "ws_m.d")
end if
call delete_histogram (unweighted)
call delete_histogram (reweighted)
call delete_histogram (weighted)
call delete_histogram (weights)
call vamp_delete_grids (grs)
end subroutine multi_channel_generator

```

Main Program

215 <vamp_test0.f90 202b>+≡

```

program vamp_test0
    <Modules used by vamp_test0 217c>
    implicit none
    <Variables in vamp_test0 217a>
    do_print = .true.
    print *, "Starting VAMP 1.0 self test..."
    print *, "serial code"
    print *, VAMP_RCS_ID
    print *, DIVISIONS_RCS_ID
    call tao_random_create (rng, 0)
    call system_clock (ticks0)
    call tao_random_seed (rng, ticks0)

```

```

⟨Set up integrand and region in vamp_test0 217e⟩
⟨Execute tests in vamp_test0 216a⟩
⟨Cleanup in vamp_test0 217f⟩
if (failures == 0) then
    stop 0
else if (failures == 1) then
    stop 1
else
    stop 2
end if
end program vamp_test0

```

216a ⟨Execute tests in vamp_test0 216a⟩≡

```

failures = 0
call system_clock (ticks0)
call single_channel (do_print, region, iterations, samples, rng, 10*ACCEPTABLE, failures)
call system_clock (ticks, ticks_per_second)
print "(1X,A,F6.2,A)", &
      "time = ", real (ticks - ticks0) / ticks_per_second, " secs"

```

216b ⟨Execute tests in vamp_test0 216a⟩+≡

```

call system_clock (ticks0)
call single_channel_generator &
    (do_print, region, iterations, samples, rng)
call system_clock (ticks, ticks_per_second)
print "(1X,A,F6.2,A)", &
      "time = ", real (ticks - ticks0) / ticks_per_second, " secs"

```

216c ⟨Execute tests in vamp_test0 216a⟩+≡

```

call system_clock (ticks0)
call multi_channel (do_print, region, iterations, samples, rng, ACCEPTABLE, failures)
call system_clock (ticks, ticks_per_second)
print "(1X,A,F6.2,A)", &
      "time = ", real (ticks - ticks0) / ticks_per_second, " secs"

```

216d ⟨Execute tests in vamp_test0 216a⟩+≡

```

call system_clock (ticks0)
call multi_channel_generator &
    (do_print, region, iterations, samples, rng)
call system_clock (ticks, ticks_per_second)
print "(1X,A,F6.2,A)", &
      "time = ", real (ticks - ticks0) / ticks_per_second, " secs"

```

216e ⟨Execute tests in vamp_test0 216a⟩+≡

```

call system_clock (ticks0)
! call check_jacobians (do_print, region, samples, rng)

```

```

call system_clock (ticks, ticks_per_second)
print "(1X,A,F6.2,A)", &
      "time = ", real (ticks - ticks0) / ticks_per_second, " secs"

217a <Variables in vamp_test0 217a>≡
      logical :: do_print

217b <Execute command 217b>≡

217c <Modules used by vamp_test0 217c>≡
      use kinds
      use tao_random_numbers
      use divisions, only: DIVISIONS_RCS_ID
      use vamp, only: VAMP_RCS_ID
      use vamp_test0_functions !NODEP!
      use vamp_tests0 !NODEP!

217d <Variables in vamp_test0 217a>+≡
      integer :: i, j, ticks, ticks_per_second, ticks0
      integer, dimension(2) :: iterations, samples
      real(kind=default), dimension(:, :, :), allocatable :: region
      type(tao_random_state) :: rng
      real(kind=default), parameter :: ACCEPTABLE = 4
      integer :: failures

217e <Set up integrand and region in vamp_test0 217e>≡
      iterations = (/ 4, 3 /)
      samples = (/ 10000, 50000 /)
      allocate (region(2,2))
      region(1,:) = -1.0
      region(2,:) = 2.0
      call create_sample &
            (num_poles = 2, weights = (/ 1.0_default, 2.0_default /), region = region)
      do i = 1, size (x0, dim=2)
          do j = 1, size (x0, dim=3)
              call tao_random_number (rng, x0(:, i, j))
          end do
      end do
      gamma = 0.001
      x0(1, :, :) = 0.2
      x0(2, :, :) = 0.8

217f <Cleanup in vamp_test0 217f>≡
      call delete_sample ()
      deallocate (region)

```

6.2.2 Parallel Test

```

218a <vampi_test0.f90 218a>≡
    ! vampi_test0.f90 --
    <Copyleft notice 1>
    <Module vamp_test0_functions 203>
module vamp_tests0
    <Modules used by vamp_tests0 209b>
    use vampi
    use mpi90
    implicit none
    private
    <Declaration of procedures in vamp_tests0 210a>
contains
    <Implementation of procedures in vamp_tests0 210b>
end module vamp_tests0

218b <vampi_test0.f90 218a>+≡
program vampi_test0
    <Modules used by vampi_test0 217c>
    use mpi90
    use vampi, only: VAMPI_RCS_ID
    implicit none
    <Variables in vampi_test0 217a>
    integer :: num_proc, proc_id
    call mpi90_init ()
    call mpi90_size (num_proc)
    call mpi90_rank (proc_id)
    if (proc_id == 0) then
        do_print = .true.
        print *, "Starting VAMP 1.0 self test..."
        if (num_proc > 1) then
            print *, "parallel code running on ", num_proc, " processors"
        else
            print *, "parallel code running serially"
        end if
        print *, VAMP_RCS_ID
        print *, VAMPI_RCS_ID
        print *, DIVISIONS_RCS_ID
    else
        do_print = .false.
    end if
    call tao_random_create (rng, 0)
    call system_clock (ticks0)

```

```

call tao_random_seed (rng, ticks0 + proc_id)
⟨Set up integrand and region in vamp_test0 217e⟩
call mpi90_broadcast (x0, 0)
call mpi90_broadcast (gamma, 0)
command_loop: do
    if (proc_id == 0) then
        ⟨Read command line and decode it as command (never defined)⟩
    end if
    call mpi90_broadcast (command, 0)
    call system_clock (ticks0)
⟨Execute command 217b⟩
    call system_clock (ticks, ticks_per_second)
    if (proc_id == 0) then
        print "(1X,A,F6.2,A)", &
              "time = ", real (ticks - ticks0) / ticks_per_second, " secs"
    end if
end do command_loop
⟨Cleanup in vamp_test0 217f⟩
call mpi90_finalize ()
if (proc_id == 0) then
    print *, "bye."
end if
end program vampi_test0

```

6.2.3 Output

219 ⟨vamp_test0.out 219⟩≡

—7—

APPLICATION

7.1 Cross section

```
220a <application.f90 220a>≡
    ! application.f90 --
    <Copyleft notice 1>
  module cross_section
    use kinds
    use constants
    use utils
    use kinematics
    use tao_random_numbers
    use products, only: dot
    use helicity
    use vamp, only: vamp_grid, vamp_probability
    implicit none
    private
    <Declaration of cross_section procedures 221d>
    <Types in cross_section 226c>
    <Variables in cross_section 220b>
  contains
    <Implementation of cross_section procedures 222a>
  end module cross_section

220b <Variables in cross_section 220b>≡
      real(kind=default), private, parameter :: &
        MA_0 = 0.0, &
        MB_0 = 0.0, &
        M1_0 = 0.0, &
        M2_0 = 0.0, &
        M3_0 = 0.0, &
```

```

S_0 = 200.0 ** 2

221a <XXX Variables in cross_section 221a>≡
    real(kind=default), private, parameter :: &
        MA_0 = 0.01, &
        MB_0 = 0.01, &
        M1_0 = 0.01, &
        M2_0 = 0.01, &
        M3_0 = 0.01, &
        S_0 = 200.0 ** 2

221b <XXX Variables in cross_section 221a>+≡
    real(kind=default), private, parameter :: &
        S1_MIN_0 = 0.0 ** 2, &
        S2_MIN_0 = 0.0 ** 2, &
        S3_MIN_0 = 0.0 ** 2, &
        T1_MIN_0 = 0.0 ** 2, &
        T2_MIN_0 = 0.0 ** 2

221c <Variables in cross_section 220b>+≡
    real(kind=default), private, parameter :: &
        S1_MIN_0 = 1.0 ** 2, &
        S2_MIN_0 = 1.0 ** 2, &
        S3_MIN_0 = 1.0 ** 2, &
        T1_MIN_0 = 10.0 ** 2, &
        T2_MIN_0 = 10.0 ** 2

221d <Declaration of cross_section procedures 221d>≡
    private :: cuts

221e <XXX Implementation of cross_section procedures 221e>≡
    pure function cuts (k1, k2, p1, p2, q) result (inside)
        real(kind=default), dimension(0:), intent(in) :: k1, k2, p1, p2, q
        logical :: inside
        inside = (abs (dot (k1 - q, k1 - q)) >= T1_MIN_0) &
            .and. (abs (dot (k2 - q, k2 - q)) >= T2_MIN_0) &
            .and. (abs (dot (p1 + q, p1 + q)) >= S1_MIN_0) &
            .and. (abs (dot (p2 + q, p2 + q)) >= S2_MIN_0) &
            .and. (abs (dot (p1 + p2, p1 + p2)) >= S3_MIN_0)
    end function cuts

221f <Variables in cross_section 220b>+≡
    real(kind=default), private, parameter :: &

```

```

E_MIN = 1.0, &
COSTH_SEP_MAX = 0.99, &
COSTH_BEAM_MAX = 0.99

```

222a *⟨Implementation of cross_section procedures 222a⟩*≡

```

pure function cuts (k1, k2, p1, p2, q) result (inside)
    real(kind=default), dimension(0:), intent(in) :: k1, k2, p1, p2, q
    logical :: inside
    real(kind=default), dimension(3) :: p1n, p2n, qn
    inside = .false.
    if ((p1(0) < E_MIN) .or. (p2(0) < E_MIN) .or. (q(0) < E_MIN)) then
        return
    end if
    p1n = p1(1:3) / sqrt (dot_product (p1(1:3), p1(1:3)))
    p2n = p2(1:3) / sqrt (dot_product (p2(1:3), p2(1:3)))
    qn = q(1:3) / sqrt (dot_product (q(1:3), q(1:3)))
    if ((abs (qn(3)) > COSTH_BEAM_MAX) &
        .or. (abs (p1n(3)) > COSTH_BEAM_MAX)&
        .or. (abs (p2n(3)) > COSTH_BEAM_MAX)) then
        return
    end if
    if (dot_product (p1n, qn) > COSTH_SEP_MAX) then
        return
    end if
    if (dot_product (p2n, qn) > COSTH_SEP_MAX) then
        return
    end if
    if (dot_product (p1n, p2n) > COSTH_SEP_MAX) then
        return
    end if
    inside = .true.
end function cuts

```

222b *⟨Implementation of cross_section procedures 222a⟩*+≡

```

function xsect (k1, k2, p1, p2, q) result (xs)
    real(kind=default), dimension(0:), intent(in) :: k1, k2, p1, p2, q
    real(kind=default) :: xs
    complex(kind=default), dimension(-1:1,-1:1,-1:1,-1:1,-1:1) :: amp
    !!! xs = 1.0_double / phase_space_volume (3, k1(0) + k2(0))
    !!! xs = 1.0_double / dot (p1 + q, p1 + q) &
    !!!         + 1.0_double / dot (p2 + q, p2 + q)
    !!! return
    amp = nneeg (k1, k2, p1, p2, q)

```

```

xs = sum (amp(-1:1:2,-1:1:2,-1:1:2,-1:1:2,-1:1:2) &
           * conjg (amp(-1:1:2,-1:1:2,-1:1:2,-1:1:2,-1:1:2)))
end function xsect

```

223a \langle Declaration of cross_section procedures 221d $\rangle \equiv$

```

private :: xsect
phi : [0, 1] $^{\otimes 5} \rightarrow [(m_2 + m_3)^2, (\sqrt{s} - m_1)^2] \otimes [t_1^{\min}(s_2), t_1^{\max}(s_2)]$ 
           $\otimes [0, 2\pi] \otimes [-1, 1] \otimes [0, 2\pi]$ 
(x1, ..., x5)  $\mapsto (s_2, t_1, \phi, \cos \theta_3, \phi_3)$ 
           $= (s_2(x_1), x_2 t_1^{\max}(s_2) + (1 - x_2) t_1^{\min}(s_2), 2\pi x_3, 2x_4 - 1, 2\pi x_5)$ 

```

(7.1)

where

$$t_1^{\max/\min}(s_2) = m_a^2 + m_b^2 - \frac{(s + m_a^2 - m_b^2)(s - s_2 + m_1^2) \mp \sqrt{\lambda(s, m_a^2, m_b^2)\lambda(s, s_2, m_1^2)}}{2s}$$

(7.2)

223b \langle Set (s₂, t₁, φ, cos θ₃, φ₃) from (x₁, ..., x₅) 223b $\rangle \equiv$

```

! s2_min = S1_MIN_0
s2_min = (m2 + m3)**2
s2_max = (sqrt(s) - m1)**2
s2 = s2_max * x(1) + s2_min * (1 - x(1))
t1_min = ma**2 + m1**2 - ((s + ma**2 - mb**2) * (s - s2 + m1**2) &
                           + sqrt(lambda(s, ma**2, mb**2) * lambda(s, s2, m1**2))) / (2*s)
t1_max = ma**2 + m1**2 - ((s + ma**2 - mb**2) * (s - s2 + m1**2) &
                           - sqrt(lambda(s, ma**2, mb**2) * lambda(s, s2, m1**2))) / (2*s)
t1 = t1_max * x(2) + t1_min * (1 - x(2))
phi = 2*PI * x(3)
cos_theta3 = 2 * x(4) - 1
phi3 = 2*PI * x(5)

```

223c \langle Set (s₂, t₁, φ, cos θ₃, φ₃) from (x₁, ..., x₅) (massless case) 223c $\rangle \equiv$

```

! s2_min = S1_MIN_0
s2_min = 0
s2_max = s
s2 = s2_max * x(1) + s2_min * (1 - x(1))
t1_min = - (s - s2)
t1_max = 0
t1 = t1_max * x(2) + t1_min * (1 - x(2))
phi = 2*PI * x(3)
cos_theta3 = 2 * x(4) - 1
phi3 = 2*PI * x(5)

```

$$J_\phi(x_1, \dots, x_5) = \begin{vmatrix} \frac{\partial s_2}{\partial x_1} & \frac{\partial t_1}{\partial x_1} \\ \frac{\partial s_2}{\partial x_2} & \frac{\partial t_1}{\partial x_2} \end{vmatrix} \cdot 8\pi^2 \quad (7.3)$$

i.e.

$$J_\phi(x_1, \dots, x_5) = 8\pi^2 \cdot \left| \frac{ds_2}{dx_1} \right| \cdot (t_1^{\max}(s_2) - t_1^{\min}(s_2)) \quad (7.4)$$

224a \langle Adjust Jacobian 224a $\rangle \equiv$

```
p%jacobian = p%jacobian &
* (8.0 * PI**2 * (s2_max - s2_min) * (t1_max - t1_min))
```

224b \langle Implementation of cross_section procedures 222a $\rangle + \equiv$

```
pure function phase_space (x, channel) result (p)
  real(kind=default), dimension(:), intent(in) :: x
  integer, intent(in) :: channel
  type(LIPS3) :: p
  real(kind=default) :: &
    ma, mb, m1, m2, m3, s, t1, s2, phi, cos_theta3, phi3
  real(kind=default) :: s2_min, s2_max, t1_min, t1_max
  s = S_0
   $\langle m_a \leftrightarrow m_b, m_1 \leftrightarrow m_2 \text{ for channel } \#1 \text{ 224c} \rangle$ 
   $\langle \text{Set } (s_2, t_1, \phi, \cos \theta_3, \phi_3) \text{ from } (x_1, \dots, x_5) \text{ 223b} \rangle$ 
  p = two_to_three (s, t1, s2, phi, cos_theta3, phi3, ma, mb, m1, m2, m3)
   $\langle$  Adjust Jacobian 224a  $\rangle$ 
   $\langle p_1 \leftrightarrow p_2 \text{ for channel } \#2 \text{ 225a} \rangle$ 
end function phase_space
```

224c $\langle m_a \leftrightarrow m_b, m_1 \leftrightarrow m_2 \text{ for channel } \#1 \text{ 224c} \rangle \equiv$

```
select case (channel)
case (1)
  ma = MA_0
  mb = MB_0
  m1 = M1_0
  m2 = M2_0
  m3 = M3_0
case (2)
  ma = MB_0
  mb = MA_0
  m1 = M2_0
  m2 = M1_0
  m3 = M3_0
case (3)
  ma = MA_0
  mb = MB_0
  m1 = M3_0
```

```

m2 = M2_0
m3 = M1_0
case default
    ma = MA_0
    mb = MB_0
    m1 = M1_0
    m2 = M2_0
    m3 = M3_0
end select

225a <p1 ↔ p2 for channel #2 225a>≡
    select case (channel)
        case (1)
            ! OK
        case (2)
            call swap (p%p(1,:), p%p(2,:))
        case (3)
            call swap (p%p(1,:), p%p(3,:))
        case default
            ! OK
    end select

225b <Declaration of cross_section procedures 221d>+≡
    private :: jacobian

225c <Implementation of cross_section procedures 222a>+≡
    pure function jacobian (k1, k2, p1, p2, q) result (jac)
        real(kind=default), dimension(0:), intent(in) :: k1, k2, p1, p2, q
        real(kind=default) :: jac
        real(kind=default) :: ma_2, mb_2, m1_2, m2_2, m3_2
        real(kind=default) :: s, s2, s2_min, s2_max, t1_min, t1_max
        ma_2 = max (dot (k1, k1), 0.0_double)
        mb_2 = max (dot (k2, k2), 0.0_double)
        m1_2 = max (dot (p1, p1), 0.0_double)
        m2_2 = max (dot (p2, p2), 0.0_double)
        m3_2 = max (dot (q, q), 0.0_double)
        s = dot (k1 + k2, k1 + k2)
        s2 = dot (p2 + q, p2 + q)
        ! s2_min = S1_MIN_0
        s2_min = (sqrt (m2_2) + sqrt (m3_2))**2
        s2_max = (sqrt (s) - sqrt (m1_2))**2
        t1_min = ma_2 + m1_2 - ((s + ma_2 - mb_2) * (s - s2 + m1_2) &
                               + sqrt (lambda (s, ma_2, mb_2) * lambda (s, s2, m1_2))) / (2*s)
        t1_max = ma_2 + m1_2 - ((s + ma_2 - mb_2) * (s - s2 + m1_2) &
                               - sqrt (lambda (s, ma_2, mb_2) * lambda (s, s2, m1_2))) / (2*s)

```

```

jac = 1.0 / ((2*PI)**5 * 32 * s2) &
    * sqrt (lambda (s2, m2_2, m3_2) / lambda (s, ma_2, mb_2)) &
    * (8.0 * PI**2 * (s2_max - s2_min) * (t1_max - t1_min))
end function jacobian

226a <Declaration of cross_section procedures 221d>+≡
    private :: phase_space, phase_space_massless

226b <Implementation of cross_section procedures 222a>+≡
    pure function phase_space_massless (x, channel) result (p)
        real(kind=default), dimension(:), intent(in) :: x
        integer, intent(in) :: channel
        type(LIPS3) :: p
        real(kind=default) :: s, t1, s2, phi, cos_theta3, phi3
        real(kind=default) :: s2_min, s2_max, t1_min, t1_max
        s = S_0
        <Set (s2, t1, φ, cos θ3, φ3) from (x1, ..., x5) (massless case) 223c>
        p = two_to_three (s, t1, s2, phi, cos_theta3, phi3)
        <Adjust Jacobian 224a>
        <p1 ↔ p2 for channel #2 225a>
    end function phase_space_massless

226c <Types in cross_section 226c>≡
    type, public :: LIPS3_m5i2a3
        ! private
        real(kind=default) :: ma, mb, m1, m2, m3
        real(kind=default) :: s, s2, t1
        real(kind=default) :: phi, cos_theta3, phi3
        real(kind=default) :: jacobian
    end type LIPS3_m5i2a3

226d <Types in cross_section 226c>+≡
    type, public :: x5
        ! private
        real(kind=default), dimension(5) :: x
        real(kind=default) :: jacobian
    end type x5

226e <Declaration of cross_section procedures 221d>+≡
    private :: invariants_from_p, invariants_to_p
    private :: invariants_from_x, invariants_to_x

226f <Implementation of cross_section procedures 222a>+≡
    pure function invariants_from_p (p, k1, k2) result (q)
        type(LIPS3), intent(in) :: p

```

```

real(kind=default), dimension(0:), intent(in) :: k1, k2
type(LIPS3_m5i2a3) :: q
real(kind=default) :: ma_2, mb_2, m1_2, m2_2, m3_2
real(kind=default), dimension(0:3) :: k1k2, p2p3, k1p1, p3_23
k1k2 = k1 + k2
k1p1 = - k1 + p%p(1,:)
p2p3 = p%p(2,:) + p%p(3,:)
ma_2 = max (dot (k1, k1), 0.0_double)
mb_2 = max (dot (k2, k2), 0.0_double)
m1_2 = max (dot (p%p(1,:), p%p(1,:)), 0.0_double)
m2_2 = max (dot (p%p(2,:), p%p(2,:)), 0.0_double)
m3_2 = max (dot (p%p(3,:), p%p(3,:)), 0.0_double)
q%ma = sqrt (ma_2)
q%mb = sqrt (mb_2)
q%m1 = sqrt (m1_2)
q%m2 = sqrt (m2_2)
q%m3 = sqrt (m3_2)
q%s = dot (k1k2, k1k2)
q%s2 = dot (p2p3, p2p3)
q%t1 = dot (k1p1, k1p1)
q%phi = atan2 (p%p(1,2), p%p(1,1))
if (q%phi < 0) then
    q%phi = q%phi + 2*PI
end if
p3_23 = boost_momentum (p%p(3,:), p2p3)
q%cos_theta3 = p3_23(3) / sqrt (dot_product (p3_23(1:3), p3_23(1:3)))
q%phi3 = atan2 (p3_23(2), p3_23(1))
if (q%phi3 < 0) then
    q%phi3 = q%phi3 + 2*PI
end if
q%jacobian = 1.0 / ((2*PI)**5 * 32 * q%s2) &
    * sqrt (lambda (q%s2, m2_2, m3_2) / lambda (q%s, ma_2, mb_2))
end function invariants_from_p

```

227a ⟨Implementation of cross_section procedures 222a⟩+≡

```

pure function invariants_to_p (p) result (q)
    type(LIPS3_m5i2a3), intent(in) :: p
    type(LIPS3) :: q
    q = two_to_three (p%s, p%t1, p%s2, p%phi, p%cos_theta3, p%phi3)
    q%jacobian = q%jacobian * p%jacobian
end function invariants_to_p

```

227b ⟨Implementation of cross_section procedures 222a⟩+≡

```

pure function invariants_from_x (x, s, ma, mb, m1, m2, m3) result (p)
  real(kind=default), dimension(:), intent(in) :: x
  real(kind=default), intent(in) :: s, ma, mb, m1, m2, m3
  type(LIPS3_m5i2a3) :: p
  real(kind=default) :: s2_min, s2_max, t1_min, t1_max
  p%ma = ma
  p%mb = mb
  p%m1 = m1
  p%m2 = m2
  p%m3 = m3
  p%s = s
  s2_min = (p%m2 + p%m3)**2
  s2_max = (sqrt (p%s) - p%m1)**2
  p%s2 = s2_max * x(1) + s2_min * (1 - x(1))
  t1_min = p%ma**2 + p%m1**2 &
            - ((p%s + p%ma**2 - p%mb**2) * (p%s - p%s2 + p%m1**2) &
                + sqrt (lambda (p%s, p%ma**2, p%mb**2) &
                         * lambda (p%s, p%s2, p%m1**2))) / (2*p%s)
  t1_max = p%ma**2 + p%m1**2 &
            - ((p%s + p%ma**2 - p%mb**2) * (p%s - p%s2 + p%m1**2) &
                - sqrt (lambda (p%s, p%ma**2, p%mb**2) &
                         * lambda (p%s, p%s2, p%m1**2))) / (2*p%s)
  p%t1 = t1_max * x(2) + t1_min * (1 - x(2))
  p%phi = 2*PI * x(3)
  p%cos_theta3 = 2 * x(4) - 1
  p%phi3 = 2*PI * x(5)
  p%jacobian = 8*PI**2 * (s2_max - s2_min) * (t1_max - t1_min)
end function invariants_from_x

```

228 *(Implementation of cross_section procedures 222a)* +≡

```

pure function invariants_to_x (p) result (x)
  type(LIPS3_m5i2a3), intent(in) :: p
  type(x5) :: x
  real(kind=default) :: s2_min, s2_max, t1_min, t1_max
  s2_min = (p%m2 + p%m3)**2
  s2_max = (sqrt (p%s) - p%m1)**2
  t1_min = p%ma**2 + p%m1**2 &
            - ((p%s + p%ma**2 - p%mb**2) * (p%s - p%s2 + p%m1**2) &
                + sqrt (lambda (p%s, p%ma**2, p%mb**2) &
                         * lambda (p%s, p%s2, p%m1**2))) / (2*p%s)
  t1_max = p%ma**2 + p%m1**2 &
            - ((p%s + p%ma**2 - p%mb**2) * (p%s - p%s2 + p%m1**2) &
                - sqrt (lambda (p%s, p%ma**2, p%mb**2) &
                         * lambda (p%s, p%s2, p%m1**2)))

```

```

        * lambda (p%s, p%s2, p%m1**2)) / (2*p%s)
x%x(1) = (p%s2 - s2_min) / (s2_max - s2_min)
x%x(2) = (p%t1 - t1_min) / (t1_max - t1_min)
x%x(3) = p%phi / (2*PI)
x%x(4) = (p%cos_theta3 + 1) / 2
x%x(5) = p%phi3 / (2*PI)
x%jacobian = p%jacobian * 8*PI**2 * (s2_max - s2_min) * (t1_max - t1_min)
end function invariants_to_x

```

229a *⟨Declaration of cross_section procedures 221d⟩+≡*

```
public :: sigma, sigma_raw, sigma_massless
```

229b *⟨Implementation of cross_section procedures 222a⟩+≡*

```

function sigma (x, weights, channel, grids) result (xs)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:), intent(in), optional :: weights
    integer, intent(in), optional :: channel
    type(vamp_grid), dimension(:), intent(in), optional :: grids
    real(kind=default) :: xs
    real(kind=default), dimension(2,0:3) :: k
    type(LIPS3) :: p
    k(1,:) = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
    k(2,:) = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
    if (present (channel)) then
        p = phase_space (x, channel)
    else
        p = phase_space (x, 0)
    end if
    if (cuts (k(1,:), k(2,:), p%p(1,:), p%p(2,:), p%p(3,:))) then
        xs = xsect (k(1,:), k(2,:), p%p(1,:), p%p(2,:), p%p(3,:)) &
            * jacobian (k(1,:), k(2,:), p%p(1,:), p%p(2,:), p%p(3,:))
        !!! * p%jacobian
    else
        xs = 0.0
    end if
end function sigma

```

229c *⟨Implementation of cross_section procedures 222a⟩+≡*

```

function sigma_raw (k1, k2, p1, p2, q) result (xs)
    real(kind=default), dimension(0:), intent(in) :: k1, k2, p1, p2, q
    real(kind=default) :: xs
    if (cuts (k1, k2, p1, p2, q)) then
        xs = xsect (k1, k2, p1, p2, q)
    end if
end function sigma_raw

```

```

    else
        xs = 0.0
    end if
end function sigma_raw

```

230a *(Implementation of cross_section procedures 222a)* +≡


```

function sigma_massless (x, weights, channel, grids) result (xs)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:), intent(in), optional :: weights
    integer, intent(in), optional :: channel
    type(vamp_grid), dimension(:), intent(in), optional :: grids
    real(kind=default) :: xs
    real(kind=default), dimension(2,0:3) :: k
    type(LIPS3) :: p
    k(1,:) = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
    k(2,:) = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
    p = phase_space_massless (x, 0)
    if (cuts (k(1,:), k(2,:), p%p(1,:), p%p(2,:), p%p(3,:))) then
        xs = xsect (k(1,:), k(2,:), p%p(1,:), p%p(2,:), p%p(3,:)) &
              * p%jacobian
    else
        xs = 0.0
    end if
end function sigma_massless

```

230b *(Declaration of cross_section procedures 221d)* +≡

```
public :: w
```



230c *(Implementation of cross_section procedures 222a)* +≡

```

function w (x, weights, channel, grids) result (w_x)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:), intent(in), optional :: weights
    integer, intent(in), optional :: channel
    type(vamp_grid), dimension(:), intent(in), optional :: grids
    real(kind=default) :: w_x
    real(kind=default), dimension(size(weights)) :: g_x

```

```

real(kind=default), dimension(2,0:3) :: k
type(LIPS3) :: p
integer :: ch
if (present (channel)) then
    ch = channel
else
    ch = 0
end if
k(1,:) = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
k(2,:) = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
p = phase_space (x, abs (ch))
g_x(1) = 1.0_double / jacobian (k(1,:), k(2,:), p%p(1,:), p%p(2,:), p%p(3,:))
g_x(2) = 1.0_double / jacobian (k(1,:), k(2,:), p%p(2,:), p%p(1,:), p%p(3,:))
g_x(3) = 1.0_double / jacobian (k(1,:), k(2,:), p%p(3,:), p%p(2,:), p%p(1,:))
if (ch > 0) then
    w_x = sigma_raw (k(1,:), k(2,:), p%p(1,:), p%p(2,:), p%p(3,:)) &
        / sum (weights * g_x)
else if (ch < 0) then
    w_x = g_x(-ch) / sum (weights * g_x)
else
    w_x = -1
end if
end function w

```

231 ⟨Implementation of cross_section procedures 222a⟩+≡

```

function sigma_rambo (x, weights, channel, grids) result (xs)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), dimension(:), intent(in), optional :: weights
    integer, intent(in), optional :: channel
    type(vamp_grid), dimension(:), intent(in), optional :: grids
    real(kind=default) :: xs
    real(kind=default), dimension(2,0:3) :: k
    real(kind=default), dimension(3,0:3) :: p
    k(1,:) = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
    k(2,:) = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
    p = massless_isotropic_decay (sum (k(:,0)), reshape (x, (/ 3, 4 /)))
    if (cuts (k(1,:), k(2,:), p(1,:), p(2,:), p(3,:))) then
        xs = xsect (k(1,:), k(2,:), p(1,:), p(2,:), p(3,:)) &
            * phase_space_volume (size (p, dim = 1), sum (k(:,0))))
    else
        xs = 0.0
    end if
end function sigma_rambo

```

```

232a <Declaration of cross_section procedures 221d>+≡
      public :: sigma_rambo

232b <Declaration of cross_section procedures 221d>+≡
      public :: check_kinematics
      private :: print_LIPS3_m5i2a3

232c <Implementation of cross_section procedures 222a>+≡
      subroutine check_kinematics (rng)
          type(tao_random_state), intent(inout) :: rng
          real(kind=default), dimension(5) :: x
          real(kind=default), dimension(0:3) :: k1, k2
          type(x5) :: x1, x2
          type(LIPS3) :: p1, p2
          type(LIPS3_m5i2a3) :: q, q1, q2
          k1 = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
          k2 = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
          call tao_random_number (rng, x)
          q = invariants_from_x (x, S_0, MA_0, MB_0, M1_0, M2_0, M3_0)
          p1 = invariants_to_p (q)
          q1 = invariants_from_p (p1, k1, k2)
          p2 = phase_space (x, 1)
          q2 = invariants_from_p (p2, k1, k2)
          x1 = invariants_to_x (q1)
          x2 = invariants_to_x (q2)
          print *, p1%jacobian, p2%jacobian, x1%jacobian, x2%jacobian
          call print_lips3_m5i2a3 (q)
          call print_lips3_m5i2a3 (q1)
          call print_lips3_m5i2a3 (q2)
      end subroutine check_kinematics

232d <Implementation of cross_section procedures 222a>+≡
      subroutine print_LIPS3_m5i2a3 (p)
          type(LIPS3_m5i2a3), intent(in) :: p
          print "(1x,5('m',a1,'=',e9.2,' '))", &
              'a', p%ma, 'b', p%mb, '1', p%m1, '2', p%m2, '3', p%m3
          print "(1x,'s=',e9.2,' s2=',e9.2,' t1=',e9.2)", &
              p%s, p%s2, p%t1
          print "(1x,'phi=',e9.2,' cos(theta)=',e9.2,' phi2=',e9.2)", &
              p%phi, p%cos_theta3, p%phi3
          print "(1x,'j=',e9.2)", &
              p%jacobian
      end subroutine print_LIPS3_m5i2a3

```

233a *(Declaration of cross_section procedures 221d)* +≡

```

    public :: phi12, phi21, phi1, phi2
    public :: g12, g21, g1, g2

```

233b *(Implementation of cross_section procedures 222a)* +≡

```

    pure function phi12 (x1, dummy) result (x2)
        real(kind=default), dimension(:, intent(in) :: x1
        integer, intent(in) :: dummy
        real(kind=default), dimension(size(x1)) :: x2
        type(LIPS3) :: p1, p2
        type(LIPS3_m5i2a3) :: q1, q2
        type(x5) :: x52
        real(kind=default), dimension(0:3) :: k1, k2
        k1 = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
        k2 = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
        q1 = invariants_from_x (x1, S_0, MA_0, MB_0, M1_0, M2_0, M3_0)
        p1 = invariants_to_p (q1)
        p2%p(1,:) = p1%p(2,:)
        p2%p(2,:) = p1%p(1,:)
        p2%p(3,:) = p1%p(3,:)
        if (dummy < 0) then
            q2 = invariants_from_p (p2, k2, k1)
        else
            q2 = invariants_from_p (p2, k1, k2)
        end if
        x52 = invariants_to_x (q2)
        x2 = x52%x
    end function phi12

```

233c *(Implementation of cross_section procedures 222a)* +≡

```

    pure function phi21 (x2, dummy) result (x1)
        real(kind=default), dimension(:, intent(in) :: x2
        integer, intent(in) :: dummy
        real(kind=default), dimension(size(x2)) :: x1
        type(LIPS3) :: p1, p2
        type(LIPS3_m5i2a3) :: q1, q2
        type(x5) :: x51
        real(kind=default), dimension(0:3) :: k1, k2
        k1 = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
        k2 = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
        q2 = invariants_from_x (x2, S_0, MA_0, MB_0, M2_0, M1_0, M3_0)
        p2 = invariants_to_p (q2)
        p1%p(1,:) = p2%p(2,:)
        p1%p(2,:) = p2%p(1,:)

```

```

p1%p(3,:) = p2%p(3,:)
if (dummy < 0) then
    q1 = invariants_from_p (p1, k2, k1)
else
    q1 = invariants_from_p (p1, k1, k2)
end if
x51 = invariants_to_x (q1)
x1 = x51%x
end function phi21

```

234a *Implementation of cross_section procedures 222a* +≡

```

pure function phi1 (x1) result (p1)
    real(kind=default), dimension(:), intent(in) :: x1
    type(LIPS3) :: p1
    type(LIPS3_m5i2a3) :: q1
    q1 = invariants_from_x (x1, S_0, MA_0, MB_0, M1_0, M2_0, M3_0)
    p1 = invariants_to_p (q1)
end function phi1

```

234b *Implementation of cross_section procedures 222a* +≡

```

pure function phi2 (x2) result (p2)
    real(kind=default), dimension(:), intent(in) :: x2
    type(LIPS3) :: p2
    type(LIPS3_m5i2a3) :: q2
    q2 = invariants_from_x (x2, S_0, MA_0, MB_0, M2_0, M1_0, M3_0)
    p2 = invariants_to_p (q2)
end function phi2

```

234c *Implementation of cross_section procedures 222a* +≡

```

pure function g12 (x1) result (g)
    real(kind=default), dimension(:), intent(in) :: x1
    real(kind=default) :: g
    type(LIPS3) :: p1, p2
    type(LIPS3_m5i2a3) :: q1, q2
    type(x5) :: x52
    real(kind=default), dimension(0:3) :: k1, k2
    k1 = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
    k2 = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
    q1 = invariants_from_x (x1, S_0, MA_0, MB_0, M1_0, M2_0, M3_0)
    p1 = invariants_to_p (q1)
    p2%p(1,:) = p1%p(2,:)
    p2%p(2,:) = p1%p(1,:)

```

```

p2%p(3,:) = p1%p(3,:)
q2 = invariants_from_p (p2, k2, k1)
x52 = invariants_to_x (q2)
g = x52%jacobian / p1%jacobian
end function g12

```

235a *⟨Implementation of cross_section procedures 222a⟩+≡*

```

pure function g21 (x2) result (g)
    real(kind=default), dimension(:), intent(in) :: x2
    real(kind=default) :: g
    type(LIPS3) :: p1, p2
    type(LIPS3_m5i2a3) :: q1, q2
    type(x5) :: x51
    real(kind=default), dimension(0:3) :: k1, k2
    k1 = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
    k2 = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
    q2 = invariants_from_x (x2, S_0, MA_0, MB_0, M2_0, M1_0, M3_0)
    p2 = invariants_to_p (q2)
    p1%p(1,:) = p2%p(2,:)
    p1%p(2,:) = p2%p(1,:)
    p1%p(3,:) = p2%p(3,:)
    q1 = invariants_from_p (p1, k2, k1)
    x51 = invariants_to_x (q1)
    g = x51%jacobian / p2%jacobian
end function g21

```

235b *⟨Implementation of cross_section procedures 222a⟩+≡*

```

pure function g1 (x1) result (g)
    real(kind=default), dimension(:), intent(in) :: x1
    real(kind=default) :: g
    type(LIPS3) :: p1
    type(LIPS3_m5i2a3) :: q1
    q1 = invariants_from_x (x1, S_0, MA_0, MB_0, M1_0, M2_0, M3_0)
    p1 = invariants_to_p (q1)
    g = 1 / p1%jacobian
end function g1

```

235c *⟨Implementation of cross_section procedures 222a⟩+≡*

```

pure function g2 (x2) result (g)
    real(kind=default), dimension(:), intent(in) :: x2
    real(kind=default) :: g
    type(LIPS3) :: p2

```

```

type(LIPS3_m5i2a3) :: q2
q2 = invariants_from_x (x2, S_0, MA_0, MB_0, M2_0, M1_0, M3_0)
p2 = invariants_to_p (q2)
g = 1 / p2%jacobian
end function g2

236a <Declaration of cross_section procedures 221d>+≡
    public :: wx
236b <Implementation of cross_section procedures 222a>+≡
    function wx (x, weights, channel, grids) result (w_x)
        real(kind=default), dimension(:, intent(in) :: x
        real(kind=default), dimension(:, intent(in) :: weights
        integer, intent(in) :: channel
        type(vamp_grid), dimension(:, intent(in) :: grids
        real(kind=default) :: w_x
        real(kind=default), dimension(size(weights)) :: g_x, p_q
        real(kind=default), dimension(size(x)) :: x1, x2
        real(kind=default), dimension(2,0:3) :: k
        type(LIPS3) :: q
        k(1,:) = (/ 100.0_double, 0.0_double, 0.0_double, 100.0_double /)
        k(2,:) = (/ 100.0_double, 0.0_double, 0.0_double, -100.0_double /)
        select case (abs (channel))
        case (1)
            x1 = x
            x2 = phi12 (x, 0)
            q = phi1 (x1)
        case (2)
            x1 = phi21 (x, 0)
            x2 = x
            q = phi2 (x2)
        end select
        p_q(1) = vamp_probability (grids(1), x1)
        p_q(2) = vamp_probability (grids(2), x2)
        g_x(1) = p_q(1) * g1 (x1)
        g_x(2) = p_q(2) * g2 (x2)
        g_x = g_x / p_q(abs(channel))
        if (channel > 0) then
            w_x = sigma_raw (k(1,:), k(2,:), q%p(1,:), q%p(2,:), q%p(3,:)) &
                / dot_product (weights, g_x)
        else if (channel < 0) then
            w_x = vamp_probability (grids(-channel), x) / dot_product (weights, g_x)
        else
            w_x = 0
        end if
    end function wx

```

```

        end if
    end function wx

237 <application.f90 220a>+≡
program application
    use kinds
    use utils
    use vampi
    use mpi90
    use linalg
    use exceptions
    use kinematics, only: phase_space_volume
    use cross_section !NODEP!
    use tao_random_numbers
    implicit none
    type(vamp_grid) :: gr
    type(vamp_grids) :: grs
    real(kind=default), dimension(:,:,:), allocatable :: region
    real(kind=default) :: integral, standard_dev, chi_squared
    real(kind=default) :: &
        single_integral, single_standard_dev, &
        rambo_integral, rambo_standard_dev
    real(kind=default), dimension(2) :: weight_vector
    integer, dimension(2) :: calls, iterations
    type(vamp_history), dimension(100) :: history
    type(vamp_history), dimension(100,size(weight_vector)) :: histories
    type(exception) :: exc
    type(tao_random_state) :: rng
    real(kind=default), dimension(5) :: x
    real(kind=default) :: jac
    integer :: i
    integer :: num_proc, proc_id, ticks, ticks0, ticks_per_second, command
    character(len=72) :: command_line
    integer, parameter :: &
        CMD_SINGLE = 1, &
        CMD_MULTI = 2, &
        CMD_ROTATING = 3, &
        CMD_RAMBO = 4, &
        CMD_COMPARE = 5, &
        CMD_MASSLESS = 6, &
        CMD_ERROR = 0
    call mpi90_init ()
    call mpi90_size (num_proc)

```

```

call mpi90_rank (proc_id)
call system_clock (ticks0)
call tao_random_create (rng, 0)
call tao_random_seed (rng, ticks0 + proc_id)
!!! call tao_random_seed (rng, proc_id)
call vamp_create_history (history, verbose = .true.)
call vamp_create_history (histories, verbose = .true.)
iterations = (/ 3, 4 /)
calls = (/ 10000, 100000 /)
if (proc_id == 0) then
    read *, command_line
    if (command_line == "single") then
        command = CMD_SINGLE
    else if (command_line == "multi") then
        command = CMD_MULTI
    else if (command_line == "rotating") then
        command = CMD_ROTATING
    else if (command_line == "rambo") then
        command = CMD_RAMBO
    else if (command_line == "compare") then
        command = CMD_COMPARE
    else if (command_line == "massless") then
        command = CMD_MASSLESS
    else
        command = CMD_ERROR
    end if
end if
call mpi90_broadcast (command, 0)
call system_clock (ticks0)
select case (command)
case (CMD_SINGLE)
    <Application in single channel mode 240a>
case (CMD_MASSLESS)
    <Application in massless single channel mode 240b>
case (CMD_MULTI)
    <Application in multi channel mode 241>
case (CMD_ROTATING)
    allocate (region(2,5))
    region(1,:) = 0.0
    region(2,:) = 1.0
    if (proc_id == 0) then
        print *, "rotating N/A yet ..."
    end if

```

```

case (CMD_RAMBO)
  <Application in Rambo mode 242>
case (CMD_COMPARE)
  <Application in single channel mode 240a>
  single_integral = integral
  single_standard_dev = standard_dev
  <Application in Rambo mode 242>
  if (proc_id == 0) then
    rambo_integral = integral
    rambo_standard_dev = standard_dev
    integral = &
      (single_integral / single_standard_dev**2 &
       + rambo_integral / rambo_standard_dev**2) &
      / (1.0_double / single_standard_dev**2 &
       + 1.0_double / rambo_standard_dev**2)
    standard_dev = 1.0_double &
      / sqrt (1.0_double / single_standard_dev**2 &
              + 1.0_double / rambo_standard_dev**2)
    chi_squared = &
      ((single_integral - integral)**2 / single_standard_dev**2) &
      + ((rambo_integral - integral)**2 / rambo_standard_dev**2)
    print *, "S&R:      ", integral, standard_dev, chi_squared
  end if
case default
  if (proc_id == 0) then
    print *, "???: ", command
    !!! TO BE REMOVED !!!
    call check_kinematics (rng)
    allocate (region(2,5))
    region(1,:) = 0
    region(2,:) = 1
    do i = 1, 10
      call tao_random_number (rng, x)
      call vamp_jacobian (phi12, 0, x, region, jac)
      print *, "12:  ", jac, 1 / g12 (x), jac * g12 (x) - 1
      call vamp_jacobian (phi21, 0, x, region, jac)
      print *, "21:  ", jac, 1 / g21 (x), jac * g21 (x) - 1
      print *, "1:   ", real(x)
      print *, "2:   ", real(phi12(phi21(x,0),0))
      print *, "2':  ", real(phi12(phi21(x,-1),-1))
      print *, "3:   ", real(phi21(phi12(x,0),0))
      print *, "3':  ", real(phi21(phi12(x,-1),-1))
      print *, "2-1: ", real(phi12(phi21(x,0),0) - x)

```

```

        print *, "3-1: ", real(phi12(phi12(x,0),0) - x)
        print *, "a:   ", real(phi12(x,0))
        print *, "a':  ", real(phi12(x,-1))
        print *, "b:   ", real(phi21(x,0))
        print *, "b':  ", real(phi21(x,-1))
    end do
    deallocate (region)
    ! do i = 2, 5
    !   print *, i, phase_space_volume (i, 200.0_double)
    ! end do
    end if
end select
if (proc_id == 0) then
    call system_clock (ticks, ticks_per_second)
    print "(1X,A,F8.2,A)", &
        "time = ", real (ticks - ticks0) / ticks_per_second, " secs"
end if
call mpi90_finalize ()
end program application

```

240a <Application in single channel mode 240a>≡

```

allocate (region(2,5))
region(1,:) = 0.0
region(2,:) = 1.0
call vamp_create_grid (gr, region, calls(1))
call clear_exception (exc)
call vamp_sample_grid &
    (rng, gr, sigma, iterations(1), history = history, exc = exc)
call handle_exception (exc)
call vamp_discard_integral (gr, calls(2))
call vamp_sample_grid &
    (rng, gr, sigma, iterations(2), &
     integral, standard_dev, chi_squared, &
     history = history(iterations(1)+1:), exc = exc)
call handle_exception (exc)
call vamp_print_history (history, "single")
if (proc_id == 0) then
    print *, "SINGLE: ", integral, standard_dev, chi_squared
end if
call vamp_write_grid (gr, "application.grid")
call vamp_delete_grid (gr)
deallocate (region)

```

240b <Application in massless single channel mode 240b>≡

```
allocate (region(2,5))
```

```

region(1,:) = 0.0
region(2,:) = 1.0
call vamp_create_grid (gr, region, calls(1))
call clear_exception (exc)
call vamp_sample_grid &
    (rng, gr, sigma_massless, iterations(1), history = history, exc = exc)
call handle_exception (exc)
call vamp_discard_integral (gr, calls(2))
call vamp_sample_grid &
    (rng, gr, sigma_massless, iterations(2), &
     integral, standard_dev, chi_squared, &
     history = history(iterations(1)+1:), exc = exc)
call handle_exception (exc)
call vamp_print_history (history, "single")
if (proc_id == 0) then
    print *, "M=0:      ", integral, standard_dev, chi_squared
end if
call vamp_write_grid (gr, "application.grid")
call vamp_delete_grid (gr)
deallocate (region)

```

241 ⟨Application in multi channel mode 241⟩≡

```

allocate (region(2,5))
region(1,:) = 0.0
region(2,:) = 1.0
weight_vector = 1.0
if (proc_id == 0) then
    read *, weight_vector
end if
call mpi90_broadcast (weight_vector, 0)
weight_vector = weight_vector / sum (weight_vector)
call vamp_create_grids (grs, region, calls(1), weight_vector)
do i = 1, 3
    call clear_exception (exc)
    call vamp_sample_grids &
        (rng, grs, wx, iterations(1), &
         history = history(1+(i-1)*iterations(1):), &
         histories = histories(1+(i-1)*iterations(1):,:), exc = exc)
    call handle_exception (exc)
    call vamp_refine_weights (grs)
end do
call vamp_discard_integrals (grs, calls(2))
call vamp_sample_grids &
    (rng, grs, wx, iterations(2), &

```

```

        integral, standard_dev, chi_squared, &
        history = history(3*iterations(1)+1:), &
        histories = histories(3*iterations(1)+1:,:), exc = exc)
call handle_exception (exc)
call vamp_print_history (history, "multi")
call vamp_print_history (histories, "multi")
if (proc_id == 0) then
    print *, "MULTI: ", integral, standard_dev, chi_squared
end if
call vamp_write_grids (grs, "application.grids")
call vamp_delete_grids (grs)
deallocate (region)

```

242 <Application in Rambo mode 242>≡

```

allocate (region(2,12))
region(1,:) = 0.0
region(2,:) = 1.0
call vamp_create_grid (gr, region, calls(1))
call clear_exception (exc)
call vamp_sample_grid &
    (rng, gr, sigma_rambo, iterations(1), history = history, exc = exc)
call handle_exception (exc)
call vamp_discard_integral (gr, calls(2))
call vamp_sample_grid &
    (rng, gr, sigma_rambo, iterations(2), &
     integral, standard_dev, chi_squared, &
     history = history(iterations(1)+1:), exc = exc)
call handle_exception (exc)
call vamp_print_history (history, "rambo")
if (proc_id == 0) then
    print *, "RAMBO: ", integral, standard_dev, chi_squared
end if
call vamp_delete_grid (gr)
deallocate (region)

```

—A— CONSTANTS

A.1 Kinds

This borders on overkill, but it is the most portable way to get double precision in standard Fortran without relying on `kind (1.0D0)`. Currently, it is possible to change `double` to any other supported real kind. The MPI interface is a potential trouble source for such things, however.

```
243a <vamp_kinds.f90 243a>≡
      ! vamp_kinds.f90 --
      <Copyleft notice 1>
      module kinds
          implicit none
          integer, parameter, private :: single = &
              & selected_real_kind (precision(1.0), range(1.0))
          integer, parameter, private :: double = &
              & selected_real_kind (precision(1.0_single) + 1, range(1.0_single) + 1)
          integer, parameter, private :: quadruple = &
              & selected_real_kind (precision (1.0_double) + 1, range (1.0_double))
          integer, parameter, public :: default = double
          character(len=*), public, parameter :: KINDS_RCS_ID = &
              "$Id: kinds.nw 314 2010-04-17 20:32:33Z ohl $"
      end module kinds
```

A.2 Mathematical and Physical Constants

```
243b <constants.f90 243b>≡
      ! constants.f90 --
      <Copyleft notice 1>
```

```
module constants
  use kinds
  implicit none
  private
  real(kind=default), public, parameter :: &
    PI = 3.1415926535897932384626433832795028841972_default
  character(len=*), public, parameter :: CONSTANTS_RCS_ID = &
    "$Id: constants.nw 314 2010-04-17 20:32:33Z ohl $"
end module constants
```

—B— ERRORS AND EXCEPTIONS

Fortran95 does not allow *any* I/O in pure and elemental procedures, not even output to the unit *. A stop statement is verboten as well. Therefore we have to use condition codes

```
245a <exceptions.f90 245a>≡
    ! exceptions.f90 --
    <Copyleft notice 1>
    module exceptions
        use kinds
        implicit none
        private
        <Declaration of exceptions procedures 246b>
        <Interfaces of exceptions procedures 360d>
        <Variables in exceptions 245c>
        <Declaration of exceptions types 245b>
        character(len=*), public, parameter :: EXCEPTIONS_RCS_ID = &
            "$Id: exceptions.nw 314 2010-04-17 20:32:33Z ohl $"
    contains
        <Implementation of exceptions procedures 246c>
    end module exceptions

245b <Declaration of exceptions types 245b>≡
    type, public :: exception
        integer :: level = EXC_NONE
        character(len=NAME_LENGTH) :: message = ""
        character(len=NAME_LENGTH) :: origin = ""
    end type exception

245c <Variables in exceptions 245c>≡
    integer, public, parameter :: &
        EXC_NONE = 0, &
        EXC_INFO = 1, &
        EXC_WARN = 2, &
```

```

    EXC_ERROR = 3, &
    EXC_FATAL = 4

246a  <Variables in exceptions 245c>+≡
    integer, private, parameter :: EXC_DEFAULT = EXC_ERROR
    integer, private, parameter :: NAME_LENGTH = 64

246b  <Declaration of exceptions procedures 246b>≡
    public :: handle_exception

246c  <Implementation of exceptions procedures 246c>≡
    subroutine handle_exception (exc)
        type(exception), intent(inout) :: exc
        character(len=10) :: name
        if (exc%level > 0) then
            select case (exc%level)
                case (EXC_NONE)
                    name = "(none)"
                case (EXC_INFO)
                    name = "info"
                case (EXC_WARN)
                    name = "warning"
                case (EXC_ERROR)
                    name = "error"
                case (EXC_FATAL)
                    name = "fatal"
                case default
                    name = "invalid"
            end select
            print *, trim (exc%origin), ": ", trim(name), ": ", trim (exc%message)
            if (exc%level >= EXC_FATAL) then
                print *, "terminated."
                stop
            end if
        end if
    end subroutine handle_exception

246d  <Declaration of exceptions procedures 246b>+≡
    public :: raise_exception, clear_exception, gather_exceptions

Raise an exception, but don't overwrite the messages in exc if it holds a more
severe exception. This way we can accumulate error codes across procedure
calls. We have exc optional to simplify life for the calling procedures, which
might have it optional themselves.

246e  <Implementation of exceptions procedures 246c>+≡
    elemental subroutine raise_exception (exc, level, origin, message)

```

```

type(exception), intent(inout), optional :: exc
integer, intent(in), optional :: level
character(len=*), intent(in), optional :: origin, message
integer :: local_level
if (present (exc)) then
    if (present (level)) then
        local_level = level
    else
        local_level = EXC_DEFAULT
    end if
    if (exc%level < local_level) then
        exc%level = local_level
        if (present (origin)) then
            exc%origin = origin
        else
            exc%origin = "[vamp]"
        end if
        if (present (message)) then
            exc%message = message
        else
            exc%message = "[vamp]"
        end if
    end if
end if
end subroutine raise_exception

```

247a ⟨Implementation of exceptions procedures 246c⟩+≡

```

elemental subroutine clear_exception (exc)
    type(exception), intent(inout) :: exc
    exc%level = 0
    exc%message = ""
    exc%origin = ""
end subroutine clear_exception

```

247b ⟨Implementation of exceptions procedures 246c⟩+≡

```

pure subroutine gather_exceptions (exc, excs)
    type(exception), intent(inout) :: exc
    type(exception), dimension(:), intent(in) :: excs
    integer :: i
    i = sum (maxloc (excs%level))
    if (exc%level < excs(i)%level) then
        call raise_exception (exc, excs(i)%level, excs(i)%origin, &
                             excs(i)%message)
    end if
end subroutine gather_exceptions

```

Here's how to use `gather_exceptions`. `elemental_procedure`

248 *⟨Idioms 100a⟩+≡*

```
call clear_exception (excs)
call elemental_procedure_1 (y, x, excs)
call elemental_procedure_2 (b, a, excs)
if (any (excs%level > 0)) then
    call gather_exceptions (exc, excs)
    return
end if
```

—C— THE ART OF RANDOM NUMBERS

Volume two of Donald E. Knuth' *The Art of Computer Programming* [15] has always been celebrated as a prime reference for random number generation. Recently, the third edition has been published and it contains a gem of a *portable* random number generator. It generates 30-bit integers with the following desirable properties

- they pass all the tests from George Marsaglia's “diehard” suite of tests for random number generators [23] (but see [15] for a caveat regarding the “birthday-spacing” test)
- they can be generated with portable signed 32-bit arithmetic (Fortran can't do unsigned arithmetic)
- it is faster than other lagged Fibonacci generators
- it can create at least $2^{30} - 2$ independent sequences

We implement the improved versions available as FORTRAN77 code from

<http://www-cs-faculty.stanford.edu/~uno/programs.html#rng>

that contain a streamlined seeding alorithm with better independence of substreams.

C.1 Application Program Interface

A function returning single reals and integers. Note that the static version without the `tao_random_state` argument does not require initialization. It will behave as if `call tao_random_seed(0)` had been executed. On the other hand, the parallelizable version with the explicit `tao_random_state` will fail if none of the `tao_random_create` have been called for the state. (This is a deficiency of Fortran90 that can be fixed in Fortran95).

249 *<API documentation 249>*+≡
call tao_random_number (r)
call tao_random_number (s, r)

The state of the random number generator comes in two variaties: buffered and raw. The former is much more efficient, but it can be beneficial to flush the buffers and to pass only the raw state in order to save of interprocess communication (IPC) costs.

250a *<API documentation 249>*+≡
type(tao_random_state) :: s
type(tao_random_raw_state) :: rs

Subroutines filling arrays of reals and integers:

250b *<API documentation 249>*+≡
call tao_random_number (a, num = n)
call tao_random_number (s, a, num = n)

Subroutine for changing the seed:

250c *<API documentation 249>*+≡
call tao_random_seed (seed = seed)
call tao_random_seed (s, seed = seed)

Subroutine for changing the luxury. Per default, use all random numbers:

250d *<API documentation 249>*+≡
call tao_random_luxury ()
call tao_random_luxury (s)

With an integer argument, use the first n of each fill of the buffer:

250e *<API documentation 249>*+≡
call tao_random_luxury (n)
call tao_random_luxury (s, n)

With a floating point argument, use that fraction of each fill of the buffer:

250f *<API documentation 249>*+≡
call tao_random_luxury (x)
call tao_random_luxury (s, x)

Create a tao_random_state

250g *<API documentation 249>*+≡
call tao_random_create (s, seed, buffer_size = buffer_size)
call tao_random_create (s, raw_state, buffer_size = buffer_size)
call tao_random_create (s, state)

Create a tao_random_raw_state

250h *<API documentation 249>*+≡
call tao_random_create (rs, seed)
call tao_random_create (rs, raw_state)
call tao_random_create (rs, state)

Destroy a `tao_random_state` or `tao_random_raw_state`

251a *(API documentation 249)*+≡
 call `tao_random_destroy` (`s`)

Copy `tao_random_state` and `tao_random_raw_state` in all four combinations

251b *(API documentation 249)*+≡
 call `tao_random_copy` (`lhs`, `rhs`)
 `lhs` = `rhs`

251c *(API documentation 249)*+≡
 call `tao_random_flush` (`s`)

251d *(API documentation 249)*+≡
 call `tao_random_read` (`s`, `unit`)
 call `tao_random_write` (`s`, `unit`)

251e *(API documentation 249)*+≡
 call `tao_random_test` (`name` = `name`)

Here is a sample application of random number states:

251f *(API documentation 249)*+≡
 subroutine `threads` (`args`, `y`, `state`)
 real, dimension(:), intent(in) :: `args`
 real, dimension(:), intent(out) :: `y`
 type(`tao_random_state`) :: `state`
 integer :: `seed`
 type(`tao_random_raw_state`), dimension(size(`y`)) :: `states`
 integer :: `s`
 call `tao_random_number` (`state`, `seed`)
 call `tao_random_create` (`states`, (/ (`s`, `s=seed,size(y)-1`) /))
 `y` = `thread` (`args`, `states`)
 end function `thread`

In this example, we could equivalently pass an integer seed, instead of `raw_state`. But in more complicated cases it can be beneficial to have the option of reusing `raw_state` in the calling routine.

251g *(API documentation 249)*+≡
 elemental function `thread` (`arg`, `raw_state`) result (`y`)
 real, dimension, intent(in) :: `arg`
 type(`tao_random_raw_state`) :: `raw_state`
 real :: `y`
 type(`tao_random_state`) :: `state`
 real :: `r`
 call `tao_random_create` (`state`, `raw_state`)
 do

```

...
call tao_random_number (state, r)
...
end do
end function thread
```

C.2 Low Level Routines

Here the low level routines are *much* more interesting than the high level routines. The latter contain a lot of duplication (made necessary by Fortran's lack of parametric polymorphism) and consist mostly of bookkeeping. We will therefore start with the former.

C.2.1 Generation of 30-bit Random Numbers

The generator is a subtractive lagged Fibonacci

$$X_j = (X_{j-K} - X_{j-L}) \mod 2^{30} \quad (\text{C.1})$$

with lags $K = 100$ and $L = 37$.

252a $\langle \text{Parameters in } \text{tao_random_numbers 252a} \rangle \equiv$
 $\text{integer, parameter, private :: K = 100, L = 37}$

Other good choices for K and L are (cf. [15], table 1 in section 3.2.2, p. 29)

252b $\langle \text{Parameters in } \text{tao_random_numbers (alternatives) 252b} \rangle \equiv$
 $\text{integer, parameter, private :: K = 55, L = 24}$
 $\text{integer, parameter, private :: K = 89, L = 38}$
 $\text{integer, parameter, private :: K = 100, L = 37}$
 $\text{integer, parameter, private :: K = 127, L = 30}$
 $\text{integer, parameter, private :: K = 258, L = 83}$
 $\text{integer, parameter, private :: K = 378, L = 107}$
 $\text{integer, parameter, private :: K = 607, L = 273}$

A modulus of 2^{30} is the largest we can handle in *portable* (i.e. *signed*) 32-bit arithmetic

252c $\langle \text{Variables in 30-bit } \text{tao_random_numbers 252c} \rangle \equiv$
 $\text{integer(kind=tao_i32), parameter, private :: M = 2**30}$

`generate` fills the array a_1, \dots, a_n with random integers $0 \leq a_i < 2^{30}$. We *must* have at least $n \geq K$. Higher values don't change the results, but make `generate` more efficient (about a factor of two, asymptotically). For $K = 100$, DEK recommends $n \geq 1000$. Best results are obtained using the first 100

random numbers out of 1009. Let's therefore use 1009 as a default buffer size. The user can call `tao_random_luxury` (100) him/herself:

253a *(Parameters in tao_random_numbers 252a)* +≡
`integer, parameter, private :: DEFAULT_BUFFER_SIZE = 1009`

Since users are not expected to call `generate` directly, we do *not* check for $n \geq K$ and assume that the caller knows what (s)he's doing ...

253b *(Implementation of 30-bit tao_random_numbers 253b)* ≡
`pure subroutine generate (a, state)`
 `integer(kind=tao_i32), dimension(:), intent(inout) :: a, state`
 `integer :: j, n`
 `n = size (a)`
 `<Load a and refresh state 253d>`
 `end subroutine generate`

253c *(Declaration of tao_random_numbers 253c)* ≡
`private :: generate`
`state(1:K) is already set up properly:`

253d *(Load a and refresh state 253d)* ≡
`a(1:K) = state(1:K)`

The remaining $n - K$ random numbers can be gotten directly from the recursion (C.1). Note that Fortran90's `modulo` intrinsic does the right thing, since it guarantees (unlike Fortran77's `mod`) that $0 \leq \text{modulo}(a, m) < a$ if $m > 0$.

253e *(Load a and refresh state 253d)* +≡
`do j = K+1, n`
 `a(j) = modulo (a(j-K) - a(j-L), M)`
`end do`

Do the recursion (C.1) K more times to prepare `state(1:K)` for the next invocation of `generate`.

253f *(Load a and refresh state 253d)* +≡
`state(1:L) = modulo (a(n+1-K:n+L-K) - a(n+1-L:n), M)`
`do j = L+1, K`
 `state(j) = modulo (a(n+j-K) - state(j-L), M)`
`end do`

C.2.2 Initialization of 30-bit Random Numbers

The non-trivial and most beautiful part is the algorithm to initialize the random number generator state `state` with the first K numbers. I haven't studied algebra over finite fields in sufficient depth to consider the mathematics behind it straightforward. The commentary below is rather verbose

and reflects my understanding of DEK's rather terse remarks (solution to exercise 3.6-9 [15]).

254a *(Implementation of tao_random_numbers 254a)* \equiv

```
subroutine seed_static (seed)
    integer, optional, intent(in) :: seed
    call seed_stateless (s_state, seed)
    s_virginal = .false.
    s_last = size (s_buffer)
end subroutine seed_static
```

The static version of tao_random_raw_state:

254b *(Variables in 30-bit tao_random_numbers 252c)* \equiv

```
integer(kind=tao_i32), dimension(K), save, private :: s_state
logical, save, private :: s_virginal = .true.
```

254c *(Implementation of tao_random_numbers 254a)* \equiv

```
elemental subroutine seed_raw_state (s, seed)
    type(tao_random_raw_state), intent(inout) :: s
    integer, optional, intent(in) :: seed
    call seed_stateless (s%x, seed)
end subroutine seed_raw_state
```

254d *(Implementation of tao_random_numbers 254a)* \equiv

```
elemental subroutine seed_state (s, seed)
    type(tao_random_state), intent(inout) :: s
    integer, optional, intent(in) :: seed
    call seed_raw_state (s%state, seed)
    s%last = size (s%buffer)
end subroutine seed_state
```

This incarnation of the procedure is pure.

254e *(Implementation of 30-bit tao_random_numbers 253b)* \equiv

```
pure subroutine seed_stateless (state, seed)
    integer(kind=tao_i32), dimension(:), intent(out) :: state
    integer, optional, intent(in) :: seed
    <Parameters local to tao_random_seed 255a>
    integer :: seed_value, j, s, t
    integer(kind=tao_i32), dimension(2*K-1) :: x
    <Set up seed_value from seed or DEFAULT_SEED 255c>
    <Bootstrap the x buffer 255d>
    <Set up s and t 255f>
do
    <p(z)  $\rightarrow$  p(z)2 (modulo zK + zL + 1) 256a>
    <p(z)  $\rightarrow$  zp(z) (modulo zK + zL + 1) 256c>
    <Shift s or t and exit if t  $\leq$  0 256d>
```

```

    end do
    <Fill state from x 256e>
    <Warm up state 256f>
end subroutine seed_stateless

```

Any default will do

255a <Parameters local to tao_random_seed 255a>≡
 integer, parameter :: DEFAULT_SEED = 0

These must not be changed:

255b <Parameters local to tao_random_seed 255a>+≡
 integer, parameter :: MAX_SEED = 2**30 - 3
 integer, parameter :: TT = 70

255c <Set up seed_value from seed or DEFAULT_SEED 255c>≡
 if (present (seed)) then
 seed_value = modulo (seed, MAX_SEED + 1)
 else
 seed_value = DEFAULT_SEED
 end if

Fill the array x_1, \dots, x_K with even integers, shifted cyclically by 29 bits.

255d <Bootstrap the x buffer 255d>≡
 s = seed_value - modulo (seed_value, 2) + 2
 do j = 1, K
 x(j) = s
 s = 2*s
 if (s >= M) then
 s = s - M + 2
 end if
 end do
 x(K+1:2*K-1) = 0

Make x_2 (and only x_2) odd:

255e <Bootstrap the x buffer 255d>+≡
 x(2) = x(2) + 1

255f <Set up s and t 255f>≡
 s = seed_value
 t = TT - 1

Consider the polynomial

$$p(z) = \sum_{n=1}^K x_n z^{n-1} = x_K z^{K-1} + \dots + x_2 z + x_1 \quad (\text{C.2})$$

We have $p(z)^2 = p(z^2) \pmod{2}$ because cross terms have an even coefficient and $x_n^2 = x_n \pmod{2}$. Therefore we can square the polynomial by shifting the coefficients. The coefficients for $n > K$ will be reduced.

256a $\langle p(z) \rightarrow p(z)^2 \text{ (modulo } z^K + z^L + 1) \text{ 256a} \rangle \equiv$
 $x(3:2*K-1:2) = x(2:K)$
 $x(2:2*K-2:2) = 0$

Let's return to the coefficients for $n > K$ generated by the shifting above. Subtract $z^n(z^K + z^L + 1) = z^n z^K(1 + z^{-(K-L)} + z^{-K})$. The coefficient of $z^n z^K$ is left alone, because it doesn't belong to $p(z)$ anyway.

256b $\langle p(z) \rightarrow p(z)^2 \text{ (modulo } z^K + z^L + 1) \text{ 256a} \rangle + \equiv$
 $\text{do } j = 2*K-1, K+1, -1$
 $x(j-(K-L)) = \text{modulo } (x(j-(K-L))-x(j), M)$
 $x(j-K) = \text{modulo } (x(j-K)-x(j), M)$
 end do

256c $\langle p(z) \rightarrow zp(z) \text{ (modulo } z^K + z^L + 1) \text{ 256c} \rangle \equiv$
 $\text{if } (\text{modulo } (s, 2) == 1) \text{ then}$
 $x(2:K+1) = x(1:K)$
 $x(1) = x(K+1)$
 $x(L+1) = \text{modulo } (x(L+1) - x(K+1), M)$
 end if

256d $\langle \text{Shift s or t and exit if } t \leq 0 \text{ 256d} \rangle \equiv$
 $\text{if } (s /= 0) \text{ then}$
 $s = s / 2$
 else
 $t = t - 1$
 end if
 $\text{if } (t <= 0) \text{ then}$
 exit
 end if

256e $\langle \text{Fill state from x 256e} \rangle \equiv$
 $\text{state}(1:K-L) = x(L+1:K)$
 $\text{state}(K-L+1:K) = x(1:L)$

256f $\langle \text{Warm up state 256f} \rangle \equiv$
 $\text{do } j = 1, 10$
 $\text{call generate (x, state)}$
 end do

256g $\langle \text{Interfaces of tao_random_numbers 256g} \rangle \equiv$
 $\text{interface tao_random_seed}$
 $\text{module procedure } \langle \text{Specific procedures for tao_random_seed 257b} \rangle$
 end interface

257a *<Declaration of tao_random_numbers 253c>+≡*
 private :: <Specific procedures for tao_random_seed 257b>
 257b *<Specific procedures for tao_random_seed 257b>≡*
 seed_static, seed_state, seed_raw_state

C.2.3 Generation of 52-bit Random Numbers

$$X_j = (X_{j-K} + X_{j-L}) \mod 1 \quad (\text{C.3})$$

257c *<Variables in 52-bit tao_random_numbers 257c>≡*
 real(kind=tao_r64), parameter, private :: M = 1.0_tao_r64

The state of the internal routines

257d *<Variables in 52-bit tao_random_numbers 257c>+≡*
 real(kind=tao_r64), dimension(K), save, private :: s_state
 logical, save, private :: s_virginal = .true.

257e *<Implementation of 52-bit tao_random_numbers 257e>≡*
 pure subroutine generate (a, state)
 real(kind=tao_r64), dimension(:), intent(inout) :: a
 real(kind=tao_r64), dimension(:), intent(inout) :: state
 integer :: j, n
 n = size (a)
 <Load 52-bit a and refresh state 257f>
 end subroutine generate

That's almost identical to the 30-bit version, except that the relative sign is flipped:

257f *<Load 52-bit a and refresh state 257f>≡*
 a(1:K) = state(1:K)
 do j = K+1, n
 a(j) = modulo (a(j-K) + a(j-L), M)
 end do
 state(1:L) = modulo (a(n+1-K:n+L-K) + a(n+1-L:n), M)
 do j = L+1, K
 state(j) = modulo (a(n+j-K) + state(j-L), M)
 end do

C.2.4 Initialization of 52-bit Random Numbers

This incarnation of the procedure is *pure*.

257g *<Implementation of 52-bit tao_random_numbers 257e>+≡*
 pure subroutine seed_stateless (state, seed)
 real(kind=tao_r64), dimension(:), intent(out) :: state

```

integer, optional, intent(in) :: seed
  <Parameters local to tao_random_seed 255a>
  <Variables local to 52-bit tao_random_seed 258b>
  <Set up seed_value from seed or DEFAULT_SEED 255c>
  <Bootstrap the 52-bit x buffer 258d>
  <Set up s and t 255f>
  do
    <52-bit  $p(z) \rightarrow p(z)^2 \pmod{z^K + z^L + 1}$  258f>
    <52-bit  $p(z) \rightarrow zp(z) \pmod{z^K + z^L + 1}$  259a>
    <Shift s or t and exit if t  $\leq 0$  256d>
  end do
  <Fill state from x 256e>
  <Warm up state 256f>
end subroutine seed_stateless

258a <Declaration of tao_random_numbers 253c>+≡
      private :: seed_stateless

258b <Variables local to 52-bit tao_random_seed 258b>≡
      real(kind=tao_r64), parameter :: ULP = 2.0_tao_r64**(-52)

258c <Variables local to 52-bit tao_random_seed 258b>+≡
      real(kind=tao_r64), dimension(2*K-1) :: x
      real(kind=tao_r64) :: ss
      integer :: seed_value, t, s, j

258d <Bootstrap the 52-bit x buffer 258d>≡
      ss = 2*ULP * (seed_value + 2)
      do j = 1, K
        x(j) = ss
        ss = 2*ss
        if (ss >= 1) then
          ss = ss - 1 + 2*ULP
        end if
      end do
      x(K+1:2*K-1) = 0.0

258e <Bootstrap the 52-bit x buffer 258d>+≡
      x(2) = x(2) + ULP

258f <52-bit  $p(z) \rightarrow p(z)^2 \pmod{z^K + z^L + 1}$  258f>≡
      x(3:2*K-1:2) = x(2:K)
      x(2:2*K-2:2) = 0

This works because 2*K-1 is odd

258g <52-bit  $p(z) \rightarrow p(z)^2 \pmod{z^K + z^L + 1}$  258f>+≡
      do j = 2*K-1, K+1, -1

```

```

x(j-(K-L)) = modulo (x(j-(K-L)) + x(j), M)
x(j-K) = modulo (x(j-K) + x(j), M)
end do
259a <52-bit p(z) → zp(z) (modulo  $z^K + z^L + 1$ ) 259a>≡
    if (modulo (s, 2) == 1) THEN
        x(2:K+1) = x(1:K)
        x(1) = x(K+1)
        x(L+1) = modulo (x(L+1) + x(K+1), M)
    end if

```

C.3 The State

```

259b <Declaration of 30-bit tao_random_numbers types 259b>≡
    type, public :: tao_random_raw_state
        private
        integer(kind=tao_i32), dimension(K) :: x
    end type tao_random_raw_state

259c <Declaration of 30-bit tao_random_numbers types 259b>+≡
    type, public :: tao_random_state
        private
        type(tao_random_raw_state) :: state
        integer(kind=tao_i32), dimension(:), pointer :: buffer => null ()
        integer :: buffer_end, last
    end type tao_random_state

259d <Declaration of 52-bit tao_random_numbers types 259d>≡
    type, public :: tao_random_raw_state
        private
        real(kind=tao_r64), dimension(K) :: x
    end type tao_random_raw_state

259e <Declaration of 52-bit tao_random_numbers types 259d>+≡
    type, public :: tao_random_state
        private
        type(tao_random_raw_state) :: state
        real(kind=tao_r64), dimension(:), pointer :: buffer => null ()
        integer :: buffer_end, last
    end type tao_random_state

```

C.3.1 Creation

259f <Interfaces of tao_random_numbers 256g>+≡

```

interface tao_random_create
    module procedure <Specific procedures for tao_random_create 260b>
end interface

260a <Declaration of tao_random_numbers 253c>+≡
    private :: <Specific procedures for tao_random_create 260b>

260b <Specific procedures for tao_random_create 260b>≡
    create_state_from_seed, create_raw_state_from_seed, &
    create_state_from_state, create_raw_state_from_state, &
    create_state_from_raw_state, create_raw_state_from_raw_st

There are no procedures for copying the state of the static generator to or
from an explicit tao_random_state. Users needing this functionality can be
expected to handle explicit states anyway. Since the direction of the copying
can not be obvious from the type of the argument, such functions would spoil
the simplicity of the generic procedure interface.

260c <Implementation of tao_random_numbers 254a>+≡
    elemental subroutine create_state_from_seed (s, seed, buffer_size)
        type(tao_random_state), intent(out) :: s
        integer, intent(in) :: seed
        integer, intent(in), optional :: buffer_size
        call create_raw_state_from_seed (s%state, seed)
        if (present (buffer_size)) then
            s%buffer_end = max (buffer_size, K)
        else
            s%buffer_end = DEFAULT_BUFFER_SIZE
        end if
        allocate (s%buffer(s%buffer_end))
        call tao_random_flush (s)
    end subroutine create_state_from_seed

260d <Implementation of tao_random_numbers 254a>+≡
    elemental subroutine create_state_from_state (s, state)
        type(tao_random_state), intent(out) :: s
        type(tao_random_state), intent(in) :: state
        call create_raw_state_from_raw_st (s%state, state%state)
        allocate (s%buffer(size(state%buffer)))
        call tao_random_copy (s, state)
    end subroutine create_state_from_state

260e <Implementation of tao_random_numbers 254a>+≡
    elemental subroutine create_state_from_raw_state &
        (s, raw_state, buffer_size)
        type(tao_random_state), intent(out) :: s
        type(tao_random_raw_state), intent(in) :: raw_state

```

```

    integer, intent(in), optional :: buffer_size
    call create_raw_state_from_raw_st (s%state, raw_state)
    if (present (buffer_size)) then
        s%buffer_end = max (buffer_size, K)
    else
        s%buffer_end = DEFAULT_BUFFER_SIZE
    end if
    allocate (s%buffer(s%buffer_end))
    call tao_random_flush (s)
end subroutine create_state_from_raw_state

261a <Implementation of tao_random_numbers 254a>+≡
elemental subroutine create_raw_state_from_seed (s, seed)
    type(tao_random_raw_state), intent(out) :: s
    integer, intent(in) :: seed
    call seed_raw_state (s, seed)
end subroutine create_raw_state_from_seed

261b <Implementation of tao_random_numbers 254a>+≡
elemental subroutine create_raw_state_from_state (s, state)
    type(tao_random_raw_state), intent(out) :: s
    type(tao_random_state), intent(in) :: state
    call copy_state_to_raw_state (s, state)
end subroutine create_raw_state_from_state

261c <Implementation of tao_random_numbers 254a>+≡
elemental subroutine create_raw_state_from_raw_st (s, raw_state)
    type(tao_random_raw_state), intent(out) :: s
    type(tao_random_raw_state), intent(in) :: raw_state
    call copy_raw_state (s, raw_state)
end subroutine create_raw_state_from_raw_st

```

C.3.2 Destruction

```

261d <Interfaces of tao_random_numbers 256g>+≡
interface tao_random_destroy
    module procedure destroy_state, destroy_raw_state
end interface

261e <Declaration of tao_random_numbers 253c>+≡
private :: destroy_state, destroy_raw_state

261f <Implementation of tao_random_numbers 254a>+≡
elemental subroutine destroy_state (s)
    type(tao_random_state), intent(inout) :: s
    deallocate (s%buffer)

```

```
    end subroutine destroy_state
```

Currently, this is a no-op, but we might need a non-trivial destruction method in the future

262a *Implementation of tao_random_numbers 254a*+≡
 elemental subroutine destroy_raw_state (s)
 type(tao_random_raw_state), intent(inout) :: s
 end subroutine destroy_raw_state

C.3.3 Copying

262b *Interfaces of tao_random_numbers 256g*+≡
 interface tao_random_copy
 module procedure <Specific procedures for tao_random_copy 262e>
 end interface

262c *Interfaces of tao_random_numbers 256g*+≡
 interface assignment(=)
 module procedure <Specific procedures for tao_random_copy 262e>
 end interface

262d *Declaration of tao_random_numbers 253c*+≡
 public :: assignment(=)
 private :: <Specific procedures for tao_random_copy 262e>

262e *Specific procedures for tao_random_copy 262e*≡
 copy_state, copy_raw_state, &
 copy_raw_state_to_state, copy_state_to_raw_state

262f *Implementation of tao_random_numbers 254a*+≡
 elemental subroutine copy_state (lhs, rhs)
 type(tao_random_state), intent(inout) :: lhs
 type(tao_random_state), intent(in) :: rhs
 call copy_raw_state (lhs%state, rhs%state)
 if (size (lhs%buffer) /= size (rhs%buffer)) then
 deallocate (lhs%buffer)
 allocate (lhs%buffer(size(rhs%buffer)))
 end if
 lhs%buffer = rhs%buffer
 lhs%buffer_end = rhs%buffer_end
 lhs%last = rhs%last
 end subroutine copy_state

262g *Implementation of tao_random_numbers 254a*+≡
 elemental subroutine copy_raw_state (lhs, rhs)
 type(tao_random_raw_state), intent(out) :: lhs

```

    type(tao_random_raw_state), intent(in) :: rhs
    lhs%x = rhs%x
end subroutine copy_raw_state

263a <Implementation of tao_random_numbers 254a>+≡
    elemental subroutine copy_raw_state_to_state (lhs, rhs)
        type(tao_random_state), intent(inout) :: lhs
        type(tao_random_raw_state), intent(in) :: rhs
        call copy_raw_state (lhs%state, rhs)
        call tao_random_flush (lhs)
    end subroutine copy_raw_state_to_state

263b <Implementation of tao_random_numbers 254a>+≡
    elemental subroutine copy_state_to_raw_state (lhs, rhs)
        type(tao_random_raw_state), intent(out) :: lhs
        type(tao_random_state), intent(in) :: rhs
        call copy_raw_state (lhs, rhs%state)
    end subroutine copy_state_to_raw_state

```

C.3.4 Flushing

```

263c <Implementation of tao_random_numbers 254a>+≡
    elemental subroutine tao_random_flush (s)
        type(tao_random_state), intent(inout) :: s
        s%last = size (s%buffer)
    end subroutine tao_random_flush

```

C.3.5 Input and Output

```

263d <Interfaces of tao_random_numbers 256g>+≡
    interface tao_random_write
        module procedure &
            write_state_unit, write_state_name, &
            write_raw_state_unit, write_raw_state_name
    end interface

263e <Declaration of tao_random_numbers 253c>+≡
    private :: write_state_unit, write_state_name
    private :: write_raw_state_unit, write_raw_state_name

263f <Interfaces of tao_random_numbers 256g>+≡
    interface tao_random_read
        module procedure &
            read_state_unit, read_state_name, &
            read_raw_state_unit, read_raw_state_name
    end interface

```

```

    end interface

264a <Declaration of tao_random_numbers 253c>+≡
    private :: read_state_unit, read_state_name
    private :: read_raw_state_unit, read_raw_state_name

264b <Implementation of tao_random_numbers 254a>+≡
    subroutine write_state_unit (s, unit)
        type(tao_random_state), intent(in) :: s
        integer, intent(in) :: unit
        write (unit = unit, fmt = *) "BEGIN TAO_RANDOM_STATE"
        call write_raw_state_unit (s%state, unit)
        write (unit = unit, fmt = "(2(1x,a16,1x,i10/),1x,a16,1x,i10)") &
            "BUFFER_SIZE", size (s%buffer), &
            "BUFFER_END", s%buffer_end, &
            "LAST", s%last
        write (unit = unit, fmt = *) "BEGIN BUFFER"
        call write_state_array (s%buffer, unit)
        write (unit = unit, fmt = *) "END BUFFER"
        write (unit = unit, fmt = *) "END TAO_RANDOM_STATE"
    end subroutine write_state_unit

264c <Implementation of tao_random_numbers 254a>+≡
    subroutine read_state_unit (s, unit)
        type(tao_random_state), intent(inout) :: s
        integer, intent(in) :: unit
        integer :: buffer_size
        read (unit = unit, fmt = *)
        call read_raw_state_unit (s%state, unit)
        read (unit = unit, fmt = "(2(1x,16x,1x,i10/),1x,16x,1x,i10)") &
            buffer_size, s%buffer_end, s%last
        read (unit = unit, fmt = *)
        if (buffer_size /= size (s%buffer)) then
            deallocate (s%buffer)
            allocate (s%buffer(buffer_size))
        end if
        call read_state_array (s%buffer, unit)
        read (unit = unit, fmt = *)
        read (unit = unit, fmt = *)
    end subroutine read_state_unit

264d <Implementation of tao_random_numbers 254a>+≡
    subroutine write_raw_state_unit (s, unit)
        type(tao_random_raw_state), intent(in) :: s
        integer, intent(in) :: unit
        write (unit = unit, fmt = *) "BEGIN TAO_RANDOM_RAW_STATE"

```

```

        call write_state_array (s%x, unit)
        write (unit = unit, fmt = *) "END TAO_RANDOM_RAW_STATE"
    end subroutine write_raw_state_unit

265a <Implementation of tao_random_numbers 254a>+≡
    subroutine read_raw_state_unit (s, unit)
        type(tao_random_raw_state), intent(inout) :: s
        integer, intent(in) :: unit
        read (unit = unit, fmt = *)
        call read_state_array (s%x, unit)
        read (unit = unit, fmt = *)
    end subroutine read_raw_state_unit

265b <Implementation of 30-bit tao_random_numbers 253b>+≡
    subroutine write_state_array (a, unit)
        integer(kind=tao_i32), dimension(:), intent(in) :: a
        integer, intent(in) :: unit
        integer :: i
        do i = 1, size (a)
            write (unit = unit, fmt = "(1x,i10,1x,i10)") i, a(i)
        end do
    end subroutine write_state_array

265c <Declaration of 30-bit tao_random_numbers 265c>≡
    private :: write_state_array

265d <Implementation of 30-bit tao_random_numbers 253b>+≡
    subroutine read_state_array (a, unit)
        integer(kind=tao_i32), dimension(:), intent(inout) :: a
        integer, intent(in) :: unit
        integer :: i, idum
        do i = 1, size (a)
            read (unit = unit, fmt = *) idum, a(i)
        end do
    end subroutine read_state_array

265e <Declaration of 30-bit tao_random_numbers 265c>+≡
    private :: read_state_array

Reading and writing 52-bit floating point numbers accurately is beyond most
Fortran runtime libraries. Their job is simplified considerably if we rescale
by  $2^{52}$  before writing. Then the temptation to truncate will not be as over-
whelming as before ...

265f <Implementation of 52-bit tao_random_numbers 257e>+≡
    subroutine write_state_array (a, unit)
        real(kind=tao_r64), dimension(:), intent(in) :: a
        integer, intent(in) :: unit

```

```

    integer :: i
    do i = 1, size (a)
        write (unit = unit, fmt = "(1x,i10,1x,f30.0)") i, 2.0_tao_r64**52 * a(i)
    end do
end subroutine write_state_array

266a <Declaration of 52-bit tao_random_numbers 266a>≡
    private :: write_state_array

266b <Implementation of 52-bit tao_random_numbers 257e>+≡
    subroutine read_state_array (a, unit)
        real(kind=tao_r64), dimension(:), intent(inout) :: a
        integer, intent(in) :: unit
        real(kind=tao_r64) :: x
        integer :: i, idum
        do i = 1, size (a)
            read (unit = unit, fmt = *) idum, x
            a(i) = 2.0_tao_r64**(-52) * x
        end do
    end subroutine read_state_array

266c <Declaration of 52-bit tao_random_numbers 266a>+≡
    private :: read_state_array

266d <Implementation of tao_random_numbers 254a>+≡
    subroutine find_free_unit (u, iostat)
        integer, intent(out) :: u
        integer, intent(out), optional :: iostat
        logical :: exists, is_open
        integer :: i, status
        do i = MIN_UNIT, MAX_UNIT
            inquire (unit = i, exist = exists, opened = is_open, &
                     iostat = status)
            if (status == 0) then
                if (exists .and. .not. is_open) then
                    u = i
                    if (present (iostat)) then
                        iostat = 0
                    end if
                    return
                end if
            end if
        end do
        if (present (iostat)) then
            iostat = -1
        end if
    end subroutine find_free_unit

```

```

        u = -1
end subroutine find_free_unit

267a <Variables in tao_random_numbers 267a>≡
    integer, parameter, private :: MIN_UNIT = 11, MAX_UNIT = 99

267b <Declaration of tao_random_numbers 253c>+≡
    private :: find_free_unit

267c <Implementation of tao_random_numbers 254a>+≡
    subroutine write_state_name (s, name)
        type(tao_random_state), intent(in) :: s
        character(len=*), intent(in) :: name
        integer :: unit
        call find_free_unit (unit)
        open (unit = unit, action = "write", status = "replace", file = name)
        call write_state_unit (s, unit)
        close (unit = unit)
    end subroutine write_state_name

267d <Implementation of tao_random_numbers 254a>+≡
    subroutine write_raw_state_name (s, name)
        type(tao_random_raw_state), intent(in) :: s
        character(len=*), intent(in) :: name
        integer :: unit
        call find_free_unit (unit)
        open (unit = unit, action = "write", status = "replace", file = name)
        call write_raw_state_unit (s, unit)
        close (unit = unit)
    end subroutine write_raw_state_name

267e <Implementation of tao_random_numbers 254a>+≡
    subroutine read_state_name (s, name)
        type(tao_random_state), intent(inout) :: s
        character(len=*), intent(in) :: name
        integer :: unit
        call find_free_unit (unit)
        open (unit = unit, action = "read", status = "old", file = name)
        call read_state_unit (s, unit)
        close (unit = unit)
    end subroutine read_state_name

267f <Implementation of tao_random_numbers 254a>+≡
    subroutine read_raw_state_name (s, name)
        type(tao_random_raw_state), intent(inout) :: s
        character(len=*), intent(in) :: name

```

```

integer :: unit
call find_free_unit (unit)
open (unit = unit, action = "read", status = "old", file = name)
call read_raw_state_unit (s, unit)
close (unit = unit)
end subroutine read_raw_state_name

```

C.3.6 Marshaling and Unmarshaling

Note that we can not use the `transfer` intrinsic function for marshalling types that contain pointers that substitute for allocatable array components. `transfer` will copy the pointers in this case and not where they point to!

- 268a *<Interfaces of tao_random_numbers 256g>+≡*
- ```

interface tao_random_marshal_size
 module procedure marshal_state_size, marshal_raw_state_size
end interface
interface tao_random_marshal
 module procedure marshal_state, marshal_raw_state
end interface
interface tao_random_unmarshal
 module procedure unmarshal_state, unmarshal_raw_state
end interface

```
- 268b *<Declaration of tao\_random\_numbers 253c>+≡*
- ```

public :: tao_random_marshal
private :: marshal_state, marshal_raw_state
public :: tao_random_marshal_size
private :: marshal_state_size, marshal_raw_state_size
public :: tao_random_unmarshal
private :: unmarshal_state, unmarshal_raw_state

```
- 268c *<Implementation of 30-bit tao_random_numbers 253b>+≡*
- ```

pure subroutine marshal_state (s, ibuf, dbuf)
 type(tao_random_state), intent(in) :: s
 integer, dimension(:), intent(inout) :: ibuf
 real(kind=tao_r64), dimension(:), intent(inout) :: dbuf
 integer :: buf_size
 buf_size = size (s%buffer)
 ibuf(1) = s%buffer_end
 ibuf(2) = s%last
 ibuf(3) = buf_size
 ibuf(4:3+buf_size) = s%buffer
 call marshal_raw_state (s%state, ibuf(4+buf_size:), dbuf)
end subroutine marshal_state

```

269a *(Implementation of 30-bit tao\_random\_numbers 253b)*+≡

```

pure subroutine marshal_state_size (s, iwords, dwords)
 type(tao_random_state), intent(in) :: s
 integer, intent(out) :: iwords, dwords
 call marshal_raw_state_size (s%state, iwords, dwords)
 iwords = iwords + 3 + size (s%buffer)
end subroutine marshal_state_size
```

269b *(Implementation of 30-bit tao\_random\_numbers 253b)*+≡

```

pure subroutine unmarshal_state (s, ibuf, dbuf)
 type(tao_random_state), intent(inout) :: s
 integer, dimension(:), intent(in) :: ibuf
 real(kind=tao_r64), dimension(:), intent(in) :: dbuf
 integer :: buf_size
 s%buffer_end = ibuf(1)
 s%last = ibuf(2)
 buf_size = ibuf(3)
 s%buffer = ibuf(4:3+buf_size)
 call unmarshal_raw_state (s%state, ibuf(4+buf_size:), dbuf)
end subroutine unmarshal_state
```

269c *(Implementation of 30-bit tao\_random\_numbers 253b)*+≡

```

pure subroutine marshal_raw_state (s, ibuf, dbuf)
 type(tao_random_raw_state), intent(in) :: s
 integer, dimension(:), intent(inout) :: ibuf
 real(kind=tao_r64), dimension(:), intent(inout) :: dbuf
 ibuf(1) = size (s%x)
 ibuf(2:1+size(s%x)) = s%x
end subroutine marshal_raw_state
```

269d *(Implementation of 30-bit tao\_random\_numbers 253b)*+≡

```

pure subroutine marshal_raw_state_size (s, iwords, dwords)
 type(tao_random_raw_state), intent(in) :: s
 integer, intent(out) :: iwords, dwords
 iwords = 1 + size (s%x)
 dwords = 0
end subroutine marshal_raw_state_size
```

269e *(Implementation of 30-bit tao\_random\_numbers 253b)*+≡

```

pure subroutine unmarshal_raw_state (s, ibuf, dbuf)
 type(tao_random_raw_state), intent(inout) :: s
 integer, dimension(:), intent(in) :: ibuf
 real(kind=tao_r64), dimension(:), intent(in) :: dbuf
 integer :: buf_size
 buf_size = ibuf(1)
 s%x = ibuf(2:1+buf_size)
```

```

 end subroutine unmarshal_raw_state

270a <Implementation of 52-bit tao_random_numbers 257e>+≡
 pure subroutine marshal_state (s, ibuf, dbuf)
 type(tao_random_state), intent(in) :: s
 integer, dimension(:), intent(inout) :: ibuf
 real(kind=tao_r64), dimension(:), intent(inout) :: dbuf
 integer :: buf_size
 buf_size = size (s%buffer)
 ibuf(1) = s%buffer_end
 ibuf(2) = s%last
 ibuf(3) = buf_size
 dbuf(1:buf_size) = s%buffer
 call marshal_raw_state (s%state, ibuf(4:), dbuf(buf_size+1:))
 end subroutine marshal_state

270b <Implementation of 52-bit tao_random_numbers 257e>+≡
 pure subroutine marshal_state_size (s, iwords, dwords)
 type(tao_random_state), intent(in) :: s
 integer, intent(out) :: iwords, dwords
 call marshal_raw_state_size (s%state, iwords, dwords)
 iwords = iwords + 3
 dwords = dwords + size(s%buffer)
 end subroutine marshal_state_size

270c <Implementation of 52-bit tao_random_numbers 257e>+≡
 pure subroutine unmarshal_state (s, ibuf, dbuf)
 type(tao_random_state), intent(inout) :: s
 integer, dimension(:), intent(in) :: ibuf
 real(kind=tao_r64), dimension(:), intent(in) :: dbuf
 integer :: buf_size
 s%buffer_end = ibuf(1)
 s%last = ibuf(2)
 buf_size = ibuf(3)
 s%buffer = dbuf(1:buf_size)
 call unmarshal_raw_state (s%state, ibuf(4:), dbuf(buf_size+1:))
 end subroutine unmarshal_state

270d <Implementation of 52-bit tao_random_numbers 257e>+≡
 pure subroutine marshal_raw_state (s, ibuf, dbuf)
 type(tao_random_raw_state), intent(in) :: s
 integer, dimension(:), intent(inout) :: ibuf
 real(kind=tao_r64), dimension(:), intent(inout) :: dbuf
 ibuf(1) = size (s%x)
 dbuf(1:size(s%x)) = s%x
 end subroutine marshal_raw_state

```

271a *(Implementation of 52-bit tao\_random\_numbers 257e)*+≡

```

pure subroutine marshal_raw_state_size (s, iwords, dwords)
 type(tao_random_raw_state), intent(in) :: s
 integer, intent(out) :: iwords, dwords
 iwords = 1
 dwords = size (s%x)
end subroutine marshal_raw_state_size
```

271b *(Implementation of 52-bit tao\_random\_numbers 257e)*+≡

```

pure subroutine unmarshal_raw_state (s, ibuf, dbuf)
 type(tao_random_raw_state), intent(inout) :: s
 integer, dimension(:), intent(in) :: ibuf
 real(kind=tao_r64), dimension(:), intent(in) :: dbuf
 integer :: buf_size
 buf_size = ibuf(1)
 s%x = dbuf(1:buf_size)
end subroutine unmarshal_raw_state
```

## C.4 High Level Routines

271c *(tao\_random\_numbers.f90 271c)*≡

```

! tao_random_numbers.f90 --
(Copyleft notice 1)
module tao_random_numbers
 use kinds
 implicit none
 integer, parameter, private :: tao_i32 = selected_int_kind (9)
 integer, parameter, private :: tao_r64 = selected_real_kind (15)
(Declaration of tao_random_numbers 253c)
(Declaration of 30-bit tao_random_numbers 265c)
(Interfaces of tao_random_numbers 256g)
(Interfaces of 30-bit tao_random_numbers 278e)
(Parameters in tao_random_numbers 252a)
(Variables in tao_random_numbers 267a)
(Variables in 30-bit tao_random_numbers 252c)
(Declaration of 30-bit tao_random_numbers types 259b)
 character(len=*), public, parameter :: TAO_RANDOM_NUMBERS_RCS_ID = &
 "$Id: tao_random_numbers.nw 314 2010-04-17 20:32:33Z ohl $"
contains
 (Implementation of tao_random_numbers 254a)
 (Implementation of 30-bit tao_random_numbers 253b)
end module tao_random_numbers
```

272a <tao52\_random\_numbers.f90 272a>≡

```

! tao52_random_numbers.f90 --
<Copyleft notice 1>
module tao52_random_numbers
 use kinds
 implicit none
 integer, parameter, private :: tao_i32 = selected_int_kind (9)
 integer, parameter, private :: tao_r64 = selected_real_kind (15)
 <Declaration of tao_random_numbers 253c>
 <Declaration of 52-bit tao_random_numbers 266a>
 <Interfaces of tao_random_numbers 256g>
 <Interfaces of 52-bit tao_random_numbers 279c>
 <Parameters in tao_random_numbers 252a>
 <Variables in tao_random_numbers 267a>
 <Variables in 52-bit tao_random_numbers 257c>
 <Declaration of 52-bit tao_random_numbers types 259d>
 character(len=*), public, parameter :: TA052_RANDOM_NUMBERS_RCS_ID = &
 "$Id: tao_random_numbers.nw 314 2010-04-17 20:32:33Z ohl $"
contains
 <Implementation of tao_random_numbers 254a>
 <Implementation of 52-bit tao_random_numbers 257e>
end module tao52_random_numbers

```

Ten functions are exported

272b <Declaration of tao\_random\_numbers 253c>+≡

```

public :: tao_random_number
public :: tao_random_seed
public :: tao_random_create
public :: tao_random_destroy
public :: tao_random_copy
public :: tao_random_read
public :: tao_random_write
public :: tao_random_flush
! public :: tao_random_luxury
public :: tao_random_test

```

#### C.4.1 Single Random Numbers

A random integer  $r$  with  $0 \leq r < 2^{30} = 1073741824$ :

272c <Implementation of 30-bit tao\_random\_numbers 253b>+≡

```

pure subroutine integer_stateless &
 (state, buffer, buffer_end, last, r)
 integer(kind=tao_i32), dimension(:), intent(inout) :: state, buffer

```

```

 integer, intent(in) :: buffer_end
 integer, intent(inout) :: last
 integer, intent(out) :: r
 integer, parameter :: NORM = 1
 <Body of tao_random_* 273a>
end subroutine integer_stateless

273a <Body of tao_random_* 273a>≡
 <Step last and reload buffer iff necessary 273c>
 r = NORM * buffer(last)

```

The low level routine `generate` will fill an array  $a_1, \dots, a_n$ , which will be consumed and refilled like an input buffer. We need at least  $n \geq K$  for the call to `generate`.

```

273b <Variables in 30-bit tao_random_numbers 252c>+≡
 integer(kind=tao_i32), dimension(DEFAULT_BUFFER_SIZE), save, private :: s_buffer
 integer, save, private :: s_buffer_end = size (s_buffer)
 integer, save, private :: s_last = size (s_buffer)

```

Increment the index `last` and reload the array `buffer`, iff this buffer is exhausted. Throughout these routines, `last` will point to random number that has just been consumed. For the array filling routines below, this is simpler than pointing to the next waiting number.

```

273c <Step last and reload buffer iff necessary 273c>≡
 last = last + 1
 if (last > buffer_end) then
 call generate (buffer, state)
 last = 1
 end if

```

A random real  $r \in [0, 1]$ . This is almost identical to `tao_random_integer`, but we duplicate the code to avoid the function call overhead for speed.

```

273d <Implementation of 30-bit tao_random_numbers 253b>+≡
 pure subroutine real_stateless (state, buffer, buffer_end, last, r)
 integer(kind=tao_i32), dimension(:), intent(inout) :: state, buffer
 integer, intent(in) :: buffer_end
 integer, intent(inout) :: last
 real(kind=default), intent(out) :: r
 real(kind=default), parameter :: NORM = 1.0_default / M
 <Body of tao_random_* 273a>
 end subroutine real_stateless

```

A random real  $r \in [0, 1]$ .

```

273e <Implementation of 52-bit tao_random_numbers 257e>+≡
 pure subroutine real_stateless (state, buffer, buffer_end, last, r)
 real(kind=tao_r64), dimension(:), intent(inout) :: state, buffer

```

```

 integer, intent(in) :: buffer_end
 integer, intent(inout) :: last
 real(kind=default), intent(out) :: r
 integer, parameter :: NORM = 1
 <Body of tao_random_* 273a>
end subroutine real_stateless

```

The low level routine `generate` will fill an array  $a_1, \dots, a_N$ , which will be consumed and refilled like an input buffer.

274a <*Variables in 52-bit tao\_random\_numbers 257c*>+≡  
`real(kind=tao_r64), dimension(DEFAULT_BUFFER_SIZE), save, private :: s_buffer
integer, save, private :: s_buffer_end = size (s_buffer)
integer, save, private :: s_last = size (s_buffer)`

#### C.4.2 Arrays of Random Numbers

Fill the array  $j_1, \dots, j_\nu$  with random integers  $0 \leq j_i < 2^{30} = 1073741824$ . This has to be done such that the underlying array length in `generate` is transparent to the user. At the same time we want to avoid the overhead of calling `tao_random_real`  $\nu$  times.

274b <*Implementation of 30-bit tao\_random\_numbers 253b*>+≡  
`pure subroutine integer_array_stateless &
 (state, buffer, buffer_end, last, v, num)
 integer(kind=tao_i32), dimension(:), intent(inout) :: state, buffer
 integer, intent(in) :: buffer_end
 integer, intent(inout) :: last
 integer, dimension(:), intent(out) :: v
 integer, optional, intent(in) :: num
 integer, parameter :: NORM = 1
 <Body of tao_random_*_array 274c>
end subroutine integer_array_stateless`

274c <*Body of tao\_random\_\*\_array 274c*>≡  
`integer :: nu, done, todo, chunk
<Set nu to num or size(v) 275a>
<Prepare array buffer and done, todo, chunk 275b>
v(1:chunk) = NORM * buffer(last+1:last+chunk)
do
 <Update last, done and todo and set new chunk 275c>
 <Reload buffer or exit 275d>
 v(done+1:done+chunk) = NORM * buffer(1:chunk)
end do`

275a *[Set nu to num or size\(v\) 275a](#)*≡  
 if (present (num)) then  
     nu = num  
 else  
     nu = size (v)  
 end if

last is used as an offset into the buffer buffer, as usual. done is an offset into the target. We still have to process all nu numbers. The first chunk can only use what's left in the buffer.

275b *[Prepare array buffer and done, todo, chunk 275b](#)*≡  
 if (last >= buffer\_end) then  
     call generate (buffer, state)  
     last = 0  
 end if  
 done = 0  
 todo = nu  
 chunk = min (todo, buffer\_end - last)

This logic is a bit weird, but after the first chunk, todo will either vanish (in which case we're done) or we have consumed all of the buffer and must reload. In any case we can pretend that the next chunk can use the whole buffer.

275c *[Update last, done and todo and set new chunk 275c](#)*≡  
 last = last + chunk  
 done = done + chunk  
 todo = todo - chunk  
 chunk = min (todo, buffer\_end)

275d *[Reload buffer or exit 275d](#)*≡  
 if (chunk <= 0) then  
     exit  
 end if  
 call generate (buffer, state)  
 last = 0

275e *[Implementation of 30-bit tao\\_random\\_numbers 253b](#)*+≡  
 pure subroutine real\_array\_stateless &  
     (state, buffer, buffer\_end, last, v, num)  
 integer(kind=tao\_i32), dimension(:), intent(inout) :: state, buffer  
 integer, intent(in) :: buffer\_end  
 integer, intent(inout) :: last  
 real(kind=default), dimension(:), intent(out) :: v  
 integer, optional, intent(in) :: num  
 real(kind=default), parameter :: NORM = 1.0\_default / M

```

 <Body of tao_random_*_array 274c>
end subroutine real_array_stateless

```

Fill the array  $v_1, \dots, v_\nu$  with uniform deviates  $v_i \in [0, 1)$ .

276a *<Implementation of 52-bit tao\_random\_numbers 257e>+≡*

```

pure subroutine real_array_stateless &
 (state, buffer, buffer_end, last, v, num)
 real(kind=tao_r64), dimension(:), intent(inout) :: state, buffer
 integer, intent(in) :: buffer_end
 integer, intent(inout) :: last
 real(kind=default), dimension(:), intent(out) :: v
 integer, optional, intent(in) :: num
 integer, parameter :: NORM = 1
 <Body of tao_random_*_array 274c>
end subroutine real_array_stateless

```

#### C.4.3 Procedures With Explicit *tao\_random\_state*

Unfortunately, this is very boring, but Fortran's lack of parametric polymorphism forces this duplication on us:

276b *<Implementation of 30-bit tao\_random\_numbers 253b>+≡*

```

elemental subroutine integer_state (s, r)
 type(tao_random_state), intent(inout) :: s
 integer, intent(out) :: r
 call integer_stateless (s%state%x, s%buffer, s%buffer_end, s%last, r)
end subroutine integer_state

```

276c *<Implementation of 30-bit tao\_random\_numbers 253b>+≡*

```

elemental subroutine real_state (s, r)
 type(tao_random_state), intent(inout) :: s
 real(kind=default), intent(out) :: r
 call real_stateless (s%state%x, s%buffer, s%buffer_end, s%last, r)
end subroutine real_state

```

276d *<Implementation of 52-bit tao\_random\_numbers 257e>+≡*

```

elemental subroutine real_state (s, r)
 type(tao_random_state), intent(inout) :: s
 real(kind=default), intent(out) :: r
 call real_stateless (s%state%x, s%buffer, s%buffer_end, s%last, r)
end subroutine real_state

```

276e *<Implementation of 30-bit tao\_random\_numbers 253b>+≡*

```

pure subroutine integer_array_state (s, v, num)
 type(tao_random_state), intent(inout) :: s
 integer, dimension(:), intent(out) :: v

```

```

 integer, optional, intent(in) :: num
 call integer_array_stateless &
 (s%state%x, s%buffer, s%buffer_end, s%last, v, num)
 end subroutine integer_array_state

277a <Implementation of 30-bit tao_random_numbers 253b>+≡
 pure subroutine real_array_state (s, v, num)
 type(tao_random_state), intent(inout) :: s
 real(kind=default), dimension(:), intent(out) :: v
 integer, optional, intent(in) :: num
 call real_array_stateless &
 (s%state%x, s%buffer, s%buffer_end, s%last, v, num)
 end subroutine real_array_state

277b <Implementation of 52-bit tao_random_numbers 257e>+≡
 pure subroutine real_array_state (s, v, num)
 type(tao_random_state), intent(inout) :: s
 real(kind=default), dimension(:), intent(out) :: v
 integer, optional, intent(in) :: num
 call real_array_stateless &
 (s%state%x, s%buffer, s%buffer_end, s%last, v, num)
 end subroutine real_array_state

```

#### C.4.4 Static Procedures

First make sure that `tao_random_seed` has been called to initialize the generator state:

```

277c <Initialize a virginal random number generator 277c>≡
 if (s_virginal) then
 call tao_random_seed ()
 end if

277d <Implementation of 30-bit tao_random_numbers 253b>+≡
 subroutine integer_static (r)
 integer, intent(out) :: r
 <Initialize a virginal random number generator 277c>
 call integer_stateless (s_state, s_buffer, s_buffer_end, s_last, r)
 end subroutine integer_static

277e <Implementation of 30-bit tao_random_numbers 253b>+≡
 subroutine real_static (r)
 real(kind=default), intent(out) :: r
 <Initialize a virginal random number generator 277c>
 call real_stateless (s_state, s_buffer, s_buffer_end, s_last, r)
 end subroutine real_static

```

278a *Implementation of 52-bit tao\_random\_numbers 257e* +≡  
 subroutine real\_static (r)  
   real(kind=default), intent(out) :: r  
   *Initialize a virginal random number generator 277c*  
   call real\_stateless (s\_state, s\_buffer, s\_buffer\_end, s\_last, r)  
 end subroutine real\_static

278b *Implementation of 30-bit tao\_random\_numbers 253b* +≡  
 subroutine integer\_array\_static (v, num)  
   integer, dimension(:), intent(out) :: v  
   integer, optional, intent(in) :: num  
   *Initialize a virginal random number generator 277c*  
   call integer\_array\_stateless &  
     (s\_state, s\_buffer, s\_buffer\_end, s\_last, v, num)  
 end subroutine integer\_array\_static

278c *Implementation of 30-bit tao\_random\_numbers 253b* +≡  
 subroutine real\_array\_static (v, num)  
   real(kind=default), dimension(:), intent(out) :: v  
   integer, optional, intent(in) :: num  
   *Initialize a virginal random number generator 277c*  
   call real\_array\_stateless &  
     (s\_state, s\_buffer, s\_buffer\_end, s\_last, v, num)  
 end subroutine real\_array\_static

278d *Implementation of 52-bit tao\_random\_numbers 257e* +≡  
 subroutine real\_array\_static (v, num)  
   real(kind=default), dimension(:), intent(out) :: v  
   integer, optional, intent(in) :: num  
   *Initialize a virginal random number generator 277c*  
   call real\_array\_stateless &  
     (s\_state, s\_buffer, s\_buffer\_end, s\_last, v, num)  
 end subroutine real\_array\_static

#### C.4.5 Generic Procedures

278e *Interfaces of 30-bit tao\_random\_numbers 278e* ≡  
 interface tao\_random\_number  
   module procedure *Specific procedures for 30-bit tao\_random\_number 278f*  
 end interface

278f *Specific procedures for 30-bit tao\_random\_number 278f* ≡  
 integer\_static, integer\_state, &  
 integer\_array\_static, integer\_array\_state, &  
 real\_static, real\_state, real\_array\_static, real\_array\_state

These are not exported

- 279a *⟨Declaration of 30-bit tao\_random\_numbers 265c⟩+≡*  
private :: &  
    integer\_stateless, integer\_array\_stateless, &  
    real\_stateless, real\_array\_stateless
- 279b *⟨Declaration of 30-bit tao\_random\_numbers 265c⟩+≡*  
private :: ⟨Specific procedures for 30-bit tao\_random\_number 278f⟩
- 279c *⟨Interfaces of 52-bit tao\_random\_numbers 279c⟩≡*  
interface tao\_random\_number  
    module procedure ⟨Specific procedures for 52-bit tao\_random\_number 279d⟩  
end interface
- 279d *⟨Specific procedures for 52-bit tao\_random\_number 279d⟩≡*  
    real\_static, real\_state, real\_array\_static, real\_array\_state
- Thes are not exported
- 279e *⟨Declaration of 52-bit tao\_random\_numbers 266a⟩+≡*  
private :: real\_stateless, real\_array\_stateless
- 279f *⟨Declaration of 52-bit tao\_random\_numbers 266a⟩+≡*  
private :: ⟨Specific procedures for 52-bit tao\_random\_number 279d⟩

#### C.4.6 Luxury

- 279g *⟨Implementation of tao\_random\_numbers 254a⟩+≡*  
pure subroutine luxury\_stateless &  
    (buffer\_size, buffer\_end, last, consumption)  
    integer, intent(in) :: buffer\_size  
    integer, intent(inout) :: buffer\_end  
    integer, intent(inout) :: last  
    integer, intent(in) :: consumption  
    if (consumption >= 1 .and. consumption <= buffer\_size) then  
        buffer\_end = consumption  
        last = min (last, buffer\_end)  
    else  
        !!! print \*, "tao\_random\_luxury: ", "invalid consumption ", &  
        !!!       consumption, ", not in [ 1,", buffer\_size, ".]"  
        buffer\_end = buffer\_size  
    end if  
end subroutine luxury\_stateless
- 279h *⟨Implementation of tao\_random\_numbers 254a⟩+≡*  
elemental subroutine luxury\_state (s)  
    type(tao\_random\_state), intent(inout) :: s

```

 call luxury_state_integer (s, size (s%buffer))
 end subroutine luxury_state

280a <Implementation of tao_random_numbers 254a>+≡
 elemental subroutine luxury_state_integer (s, consumption)
 type(tao_random_state), intent(inout) :: s
 integer, intent(in) :: consumption
 call luxury_stateless (size (s%buffer), s%buffer_end, s%last, consumption)
 end subroutine luxury_state_integer

280b <Implementation of tao_random_numbers 254a>+≡
 elemental subroutine luxury_state_real (s, consumption)
 type(tao_random_state), intent(inout) :: s
 real(kind=default), intent(in) :: consumption
 call luxury_state_integer (s, int (consumption * size (s%buffer)))
 end subroutine luxury_state_real

280c <Implementation of tao_random_numbers 254a>+≡
 subroutine luxury_static ()
 <Initialize a virginal random number generator 277c>
 call luxury_static_integer (size (s_buffer))
 end subroutine luxury_static

280d <Implementation of tao_random_numbers 254a>+≡
 subroutine luxury_static_integer (consumption)
 integer, intent(in) :: consumption
 <Initialize a virginal random number generator 277c>
 call luxury_stateless (size (s_buffer), s_buffer_end, s_last, consumption)
 end subroutine luxury_static_integer

280e <Implementation of tao_random_numbers 254a>+≡
 subroutine luxury_static_real (consumption)
 real(kind=default), intent(in) :: consumption
 <Initialize a virginal random number generator 277c>
 call luxury_static_integer (int (consumption * size (s_buffer)))
 end subroutine luxury_static_real

280f <Interfaces of tao_random_numbers (unused luxury) 280f>≡
 interface tao_random_luxury
 module procedure <Specific procedures for tao_random_luxury 281a>
 end interface

280g <Declaration of tao_random_numbers (unused luxury) 280g>≡
 private :: luxury_stateless

280h <Declaration of tao_random_numbers (unused luxury) 280g>+≡
 private :: <Specific procedures for tao_random_luxury 281a>

```

281a *(Specific procedures for tao\_random\_luxury 281a)*≡  
 luxury\_static, luxury\_state, &  
 luxury\_static\_integer, luxury\_state\_integer, &  
 luxury\_static\_real, luxury\_state\_real

## C.5 Testing

### C.5.1 30-bit

281b *(Implementation of 30-bit tao\_random\_numbers 253b)*+≡  
 subroutine tao\_random\_test (name)  
 character(len=\*), optional, intent(in) :: name  
 character (len = \*), parameter :: &  
 OK = "(1x,i10,' is ok.')", &  
 NOT\_OK = "(1x,i10,' is not ok, (expected ',i10,')!')"  
*(Parameters in tao\_random\_test 281c)*  
 integer, parameter :: &  
 A\_2027082 = 995235265  
 integer, dimension(N) :: a  
 type(tao\_random\_state) :: s, t  
 integer, dimension(:), allocatable :: ibuf  
 real(kind=tao\_r64), dimension(:), allocatable :: dbuf  
 integer :: i, ibuf\_size, dbuf\_size  
 print \*, TAO\_RANDOM\_NUMBERS\_RCS\_ID  
 print \*, "testing the 30-bit tao\_random\_numbers ..."  
*(Perform simple tests of tao\_random\_numbers 281d)*  
*(Perform more tests of tao\_random\_numbers 282c)*  
 end subroutine tao\_random\_test

281c *(Parameters in tao\_random\_test 281c)*≡  
 integer, parameter :: &  
 SEED = 310952, &  
 N = 2009, M = 1009, &  
 N\_SHORT = 1984

DEK's "official" test expects  $a_{1009 \cdot 2009+1} = a_{2027082} = 995235265$ :

281d *(Perform simple tests of tao\_random\_numbers 281d)*≡  
 ! call tao\_random\_luxury ()  
 call tao\_random\_seed (SEED)  
 do i = 1, N+1  
     call tao\_random\_number (a, M)  
 end do

```

⟨Test a(1) = A_2027082 282a⟩
282a ⟨Test a(1) = A_2027082 282a⟩≡
 if (a(1) == A_2027082) then
 print OK, a(1)
 else
 print NOT_OK, a(1), A_2027082
 stop 1
 end if

```

Deja vu all over again, but 2027081 is factored the other way around this time

```

282b ⟨Perform simple tests of tao_random_numbers 281d⟩+≡
 call tao_random_seed (SEED)
 do i = 1, M+1
 call tao_random_number (a)
 end do
 ⟨Test a(1) = A_2027082 282a⟩

```

Now checkpoint the random number generator after  $N_{\text{short}} \cdot M$  numbers

```

282c ⟨Perform more tests of tao_random_numbers 282c⟩≡
 print *, "testing the stateless stuff ..."
 call tao_random_create (s, SEED)
 do i = 1, N_SHORT
 call tao_random_number (s, a, M)
 end do
 call tao_random_create (t, s)
 do i = 1, N+1 - N_SHORT
 call tao_random_number (s, a, M)
 end do
 ⟨Test a(1) = A_2027082 282a⟩

```

and restart the saved generator

```

282d ⟨Perform more tests of tao_random_numbers 282c⟩+≡
 do i = 1, N+1 - N_SHORT
 call tao_random_number (t, a, M)
 end do
 ⟨Test a(1) = A_2027082 282a⟩

```

The same story again, but this time saving the copy to a file

```

282e ⟨Perform more tests of tao_random_numbers 282c⟩+≡
 if (present (name)) then
 print *, "testing I/O ..."
 call tao_random_seed (s, SEED)
 do i = 1, N_SHORT
 call tao_random_number (s, a, M)

```

```

 end do
 call tao_random_write (s, name)
 do i = 1, N+1 - N_SHORT
 call tao_random_number (s, a, M)
 end do
 ⟨Test a(1) = A_2027082 282a⟩
 call tao_random_read (s, name)
 do i = 1, N+1 - N_SHORT
 call tao_random_number (s, a, M)
 end do
 ⟨Test a(1) = A_2027082 282a⟩
end if

```

And finally using marshaling/unmarshaling:

283a ⟨Perform more tests of tao\_random\_numbers 282c⟩+≡

```

print *, "testing marshaling/unmarshaling ..."
call tao_random_seed (s, SEED)
do i = 1, N_SHORT
 call tao_random_number (s, a, M)
end do
call tao_random_marshal_size (s, ibuf_size, dbuf_size)
allocate (ibuf(ibuf_size), dbuf(dbuf_size))
call tao_random_marshal (s, ibuf, dbuf)
do i = 1, N+1 - N_SHORT
 call tao_random_number (s, a, M)
end do
⟨Test a(1) = A_2027082 282a⟩
call tao_random_unmarshal (s, ibuf, dbuf)
do i = 1, N+1 - N_SHORT
 call tao_random_number (s, a, M)
end do
⟨Test a(1) = A_2027082 282a⟩

```

### C.5.2 52-bit

DEK's "official" test expects  $x_{1009 \cdot 2009+1} = x_{2027082} = 0.36410514377569680455$ :

283b ⟨Implementation of 52-bit tao\_random\_numbers 257e⟩+≡

```

subroutine tao_random_test (name)
 character(len=*), optional, intent(in) :: name
 character(len=*), parameter :: &
 OK = "(1x,f22.20,' is ok.')", &
 NOT_OK = "(1x,f22.20,' is not ok, (A_2027082 ,f22.20,)!)"
 ⟨Parameters in tao_random_test 281c⟩

```

```

real(kind=default), parameter :: &
 A_2027082 = 0.36410514377569680455_default
real(kind=default), dimension(N) :: a
type(tao_random_state) :: s, t
integer, dimension(:), allocatable :: ibuf
real(kind=tao_r64), dimension(:), allocatable ::dbuf
integer :: i, ibuf_size, dbuf_size
print *, TAO52_RANDOM_NUMBERS_RCS_ID
print *, "testing the 52-bit tao_random_numbers ..."
<Perform simple tests of tao_random_numbers 281d>
<Perform more tests of tao_random_numbers 282c>
end subroutine tao_random_test

```

### C.5.3 Test Program

```

284 <tao_test.f90 284>≡
program tao_test
 use tao_random_numbers, only: test30 => tao_random_test
 use tao52_random_numbers, only: test52 => tao_random_test
 implicit none
 call test30 ("tmp.tao")
 call test52 ("tmp.tao")
 stop 0
end program tao_test

```

# —D— SPECIAL FUNCTIONS

```

285a <specfun.f90 285a>≡
 ! specfun.f90 --
 <Copyleft notice 1>
 module specfun
 use kinds
 ! use constants
 implicit none
 private
 <Declaration of specfun procedures 285b>
 character(len=*), public, parameter :: SPECFUN_RCS_ID = &
 "$Id: specfun.nw 314 2010-04-17 20:32:33Z ohl $"
 !WK:
 real(kind=default), public, parameter :: &
 PI = 3.1415926535897932384626433832795028841972_default
 contains
 <Implementation of specfun procedures 286c>
 end module specfun

```

The algorithm is stolen from the FORTRAN version in routine C303 of the CERN library [24]. It has an accuracy which is approximately one digit less than machine precision.

285b <Declaration of specfun procedures 285b>≡  
`public :: gamma`

The so-called reflection formula is used for negative arguments:

$$\Gamma(x)\Gamma(1-x) = \frac{\pi}{\sin \pi x} \quad (\text{D.1})$$

Here's the identity transformation that pulls the argument of  $\Gamma$  into [3, 4]:

$$\Gamma(u) = \begin{cases} (u-1)\Gamma(u-1) & \text{for } u > 4 \\ \frac{1}{u}\Gamma(u+1) & \text{for } u < 3 \end{cases} \quad (\text{D.2})$$

286a *(Pull u into the intervall [3, 4] 286a)*≡

```

f = 1
if (u < 3) then
 do i = 1, int (4 - u)
 f = f / u
 u = u + 1
 end do
else
 do i = 1, int (u - 3)
 u = u - 1
 f = f * u
 end do
end if

```

A Chebyshev approximation for  $\Gamma(x)$  is used after mapping  $x \in [3, 4]$  linearly to  $h \in [-1, 1]$ . The series is evaluated by Clenshaw's recurrence formula:

$$\begin{aligned}
d_m &= d_{m+1} = 0 \\
d_j &= 2xd_{j+1} - d_{j+2} + c_j \text{ for } 0 < j < m-1 \\
f(x) &= d_0 = xd_1 - d_2 + \frac{1}{2}c_0
\end{aligned} \tag{D.3}$$

286b *(Clenshaw's recurrence formula 286b)*≡

```

alpha = 2*g
b1 = 0
b2 = 0
do i = 15, 0, -1
 b0 = c(i) + alpha * b1 - b2
 b2 = b1
 b1 = b0
end do
g = f * (b0 - g * b2)

```

Note that we're assuming that  $c(0)$  is in fact  $c_0/2$ . This is for compatibility with the CERN library routines.

286c *(Implementation of specfun procedures 286c)*≡

```

pure function gamma (x) result (g)
 real(kind=default), intent(in) :: x
 real(kind=default) :: g
 integer :: i
 real(kind=default) :: u, f, alpha, b0, b1, b2
 real(kind=default), dimension(0:15), parameter :: &
 c = <c0/2, c1, c2, ..., c15 for $\Gamma(x)$ 287a>
 u = x
 if (u <= 0.0) then

```

```

if (u == int (u)) then
 g = huge (g)
 return
else
 u = 1 - u
end if
endif
⟨Pull u into the intervall [3,4] 286a⟩
g = 2*u - 7
⟨Clenshaw's recurrence formula 286b⟩
if (x < 0) then
 g = PI / (sin (PI * x) * g)
end if
end function gamma

```

287a ⟨ $c_0/2, c_1, c_2, \dots, c_{15}$  for  $\Gamma(x)$  287a⟩≡  
 (/ 3.65738772508338244\_default, &  
 1.95754345666126827\_default, &  
 0.33829711382616039\_default, &  
 0.04208951276557549\_default, &  
 0.00428765048212909\_default, &  
 0.00036521216929462\_default, &  
 0.00002740064222642\_default, &  
 0.00000181240233365\_default, &  
 0.00000010965775866\_default, &  
 0.00000000598718405\_default, &  
 0.00000000030769081\_default, &  
 0.00000000001431793\_default, &  
 0.0000000000065109\_default, &  
 0.0000000000002596\_default, &  
 0.0000000000000111\_default, &  
 0.0000000000000004\_default /)

## D.1 Test

287b ⟨stest.f90 287b⟩≡  
 ! stest.f90 --  
 ⟨Copyleft notice 1⟩
 module stest\_functions
 use kinds
 use constants
 use specfun

```

private
 <Declaration of stest_functions procedures 288a>
contains
 <Implementation of stest_functions procedures 288b>
end module stest_functions

288a <Declaration of stest_functions procedures 288a>≡
 public :: gauss_multiplication
Gauss' multiplication formula can serve as a non-trivial test

$$\Gamma(nx) = (2\pi)^{(1-n)/2} n^{nx-1/2} \prod_{k=0}^{n-1} \Gamma(x + k/n) \quad (D.4)$$

288b <Implementation of stest_functions procedures 288b>≡
 pure function gauss_multiplication (x, n) result (delta)
 real(kind=default), intent(in) :: x
 integer, intent(in) :: n
 real(kind=default) :: delta
 real(kind=default) :: gxn
 integer :: k
 gxn = (2*PI)**(0.5_double*(1-n)) * n**(n*x-0.5_double)
 do k = 0, n - 1
 gxn = gxn * gamma (x + real (k, kind=default) / n)
 end do
 delta = abs ((gamma (n*x) - gxn) / gamma (n*x))
 end function gauss_multiplication

288c <stest.f90 287b>+≡
 program stest
 use kinds
 use specfun
 use stest_functions !NODEP!
 implicit none
 integer :: i, steps
 real(kind=default) :: x, g, xmin, xmax
 xmin = -4.5
 xmax = 4.5
 steps = 100 ! 9
 do i = 0, steps
 x = xmin + ((xmax - xmin) / real (steps)) * i
 print "(f6.3,4(1x,e9.2))", x, &
 gauss_multiplication (x, 2), &
 gauss_multiplication (x, 3), &
 gauss_multiplication (x, 4), &
```

```
 gauss_multiplication (x, 5)
end do
end program stest
```

# —E— STATISTICS

290a <vamp\_stat.f90 290a>≡  
! vamp\_stat.f90 --  
<*Copyleft notice 1*>  
module vamp\_stat  
use kinds  
implicit none  
private  
<*Declaration of vamp\_stat procedures 290b*>  
character(len=\*), public, parameter :: VAMP\_STAT\_RCS\_ID = &  
"\$\$Id: vamp\_stat.nw 314 2010-04-17 20:32:33Z ohl \$"  
contains  
<*Implementation of vamp\_stat procedures 290c*>  
end module vamp\_stat

290b <*Declaration of vamp\_stat procedures 290b*>≡  
public :: average, standard\_deviation, value\_spread  
$$\text{avg}(X) = \frac{1}{|X|} \sum_{x \in X} x \quad (\text{E.1})$$

290c <*Implementation of vamp\_stat procedures 290c*>≡  
pure function average (x) result (a)  
real(kind=default), dimension(:), intent(in) :: x  
real(kind=default) :: a  
integer :: n  
n = size (x)  
if (n == 0) then  
a = 0.0  
else  
a = sum (x) / n  
end if  
end function average

$$\text{stddev}(X) = \frac{1}{|X| - 1} \sum_{x \in X} (x - \text{avg}(X))^2 = \frac{1}{|X| - 1} \left( \frac{1}{|X|} \sum_{x \in X} x^2 - (\text{avg}(X))^2 \right) \quad (\text{E.2})$$

291a *(Implementation of vamp\_stat procedures 290c)* +≡

```

pure function standard_deviation (x) result (s)
 real(kind=default), dimension(:), intent(in) :: x
 real(kind=default) :: s
 integer :: n
 n = size (x)
 if (n < 2) then
 s = huge (s)
 else
 s = sqrt (max ((sum (x**2) / n - (average (x))**2) / (n - 1), &
 0.0_default))
 end if
end function standard_deviation
spread(X) = max(x) - min(x) (E.3)
```

291b *(Implementation of vamp\_stat procedures 290c)* +≡

```

pure function value_spread (x) result (s)
 real(kind=default), dimension(:), intent(in) :: x
 real(kind=default) :: s
 s = maxval(x) - minval(x)
end function value_spread
```

291c *(Declaration of vamp\_stat procedures 290b)* +≡

```

public :: standard_deviation_percent, value_spread_percent
```

291d *(Implementation of vamp\_stat procedures 290c)* +≡

```

pure function standard_deviation_percent (x) result (s)
 real(kind=default), dimension(:), intent(in) :: x
 real(kind=default) :: s
 real(kind=default) :: abs_avg
 abs_avg = abs (average (x))
 if (abs_avg <= tiny (abs_avg)) then
 s = huge (s)
 else
 s = 100.0 * standard_deviation (x) / abs_avg
 end if
end function standard_deviation_percent
```

291e *(Implementation of vamp\_stat procedures 290c)* +≡

```

pure function value_spread_percent (x) result (s)
 real(kind=default), dimension(:), intent(in) :: x
```

```
real(kind=default) :: s
real(kind=default) :: abs_avg
abs_avg = abs (average (x))
if (abs_avg <= tiny (abs_avg)) then
 s = huge (s)
else
 s = 100.0 * value_spread (x) / abs_avg
end if
end function value_spread_percent
```

# —F— HISTOGRAMMING

⌚ Merged WK's improvements for WHIZARD. TODO *after* merging:

1. `bins3` is a bad undescriptive name
2. `bins3` should be added to `histogram2`
3. `write_histogram2_unit` for symmetry.

⌚ There's almost no sanity checking. If you call one of these functions on a histogram that has not been initialized, you loose. — *Big time.*

293a `<histograms.f90 293a>`≡

```
! histograms.f90 --
⟨Copyleft notice 1⟩
module histograms
 use kinds
 use utils, only: find_free_unit
 implicit none
 private
 ⟨Declaration of histograms procedures 294b⟩
 ⟨Interfaces of histograms procedures 294c⟩
 ⟨Variables in histograms 294e⟩
 ⟨Declaration of histograms types 293b⟩
 character(len=*), public, parameter :: HISTOGRAMS_RCS_ID = &
 "$Id: histograms.nw 314 2010-04-17 20:32:33Z ohl $"
contains
 ⟨Implementation of histograms procedures 294f⟩
end module histograms
```

293b `<Declaration of histograms types 293b>`≡

```
type, public :: histogram
 private
 integer :: n_bins
 real(kind=default) :: x_min, x_max
```

```

 real(kind=default), dimension(:), pointer :: bins => null ()
 real(kind=default), dimension(:), pointer :: bins2 => null ()
 real(kind=default), dimension(:), pointer :: bins3 => null ()
end type histogram

294a <Declaration of histograms types 293b>+≡
type, public :: histogram2
private
integer, dimension(2) :: n_bins
real(kind=default), dimension(2) :: x_min, x_max
real(kind=default), dimension(:, :), pointer :: bins => null ()
real(kind=default), dimension(:, :), pointer :: bins2 => null ()
end type histogram2

294b <Declaration of histograms procedures 294b>≡
public :: create_histogram
public :: fill_histogram
public :: delete_histogram
public :: write_histogram

294c <Interfaces of histograms procedures 294c>≡
interface create_histogram
 module procedure create_histogram1, create_histogram2
end interface
interface fill_histogram
 module procedure fill_histogram1, fill_histogram2s, fill_histogram2v
end interface
interface delete_histogram
 module procedure delete_histogram1, delete_histogram2
end interface
interface write_histogram
 module procedure write_histogram1, write_histogram2
 module procedure write_histogram1_unit
 end interface
end interface

294d <Declaration of histograms procedures 294b>+≡
private :: create_histogram1, create_histogram2
private :: fill_histogram1, fill_histogram2s, fill_histogram2v
private :: delete_histogram1, delete_histogram2
private :: write_histogram1, write_histogram2

294e <Variables in histograms 294e>≡
integer, parameter, private :: N_BINS_DEFAULT = 10

294f <Implementation of histograms procedures 294f>≡
elemental subroutine create_histogram1 (h, x_min, x_max, nb)
 type(histogram), intent(out) :: h

```

```

real(kind=default), intent(in) :: x_min, x_max
integer, intent(in), optional :: nb
if (present (nb)) then
 h%n_bins = nb
else
 h%n_bins = N_BINS_DEFAULT
end if
h%x_min = x_min
h%x_max = x_max
allocate (h%bins(0:h%n_bins+1), h%bins2(0:h%n_bins+1))
h%bins = 0
h%bins2 = 0
allocate (h%bins3(0:h%n_bins+1))
h%bins3 = 0
end subroutine create_histogram1

```

295a <Implementation of histograms procedures 294f>+≡

```

pure subroutine create_histogram2 (h, x_min, x_max, nb)
 type(histogram2), intent(out) :: h
 real(kind=default), dimension(:), intent(in) :: x_min, x_max
 integer, intent(in), dimension(:), optional :: nb
 if (present (nb)) then
 h%n_bins = nb
 else
 h%n_bins = N_BINS_DEFAULT
 end if
 h%x_min = x_min
 h%x_max = x_max
 allocate (h%bins(0:h%n_bins(1)+1,0:h%n_bins(1)+1), &
 h%bins2(0:h%n_bins(2)+1,0:h%n_bins(2)+1))
 h%bins = 0
 h%bins2 = 0
end subroutine create_histogram2

```

295b <Implementation of histograms procedures 294f>+≡

```

elemental subroutine fill_histogram1 (h, x, weight, excess)
 type(histogram), intent(inout) :: h
 real(kind=default), intent(in) :: x
 real(kind=default), intent(in), optional :: weight
 real(kind=default), intent(in), optional :: excess
 integer :: i
 if (x < h%x_min) then
 i = 0
 else if (x > h%x_max) then
 i = h%n_bins + 1
 end if
 if (present (weight)) then
 h%bins(i) = h%bins(i) + weight
 else if (present (excess)) then
 h%bins(i) = h%bins(i) + excess
 end if
end elemental subroutine fill_histogram1

```

```

 else
 i = 1 + h%n_bins * (x - h%x_min) / (h%x_max - h%x_min)
!WK! i = min (max (i, 0), h%n_bins + 1)
 end if
 if (present (weight)) then
 h%bins(i) = h%bins(i) + weight
 h%bins2(i) = h%bins2(i) + weight*weight
 else
 h%bins(i) = h%bins(i) + 1
 h%bins2(i) = h%bins2(i) + 1
 end if
 if (present (excess)) h%bins3(i) = h%bins3(i) + excess
end subroutine fill_histogram1

```

296a *(Implementation of histograms procedures 294f)*+≡

```

elemental subroutine fill_histogram2s (h, x1, x2, weight)
 type(histogram2), intent(inout) :: h
 real(kind=default), intent(in) :: x1, x2
 real(kind=default), intent(in), optional :: weight
 call fill_histogram2v (h, (/ x1, x2 /), weight)
end subroutine fill_histogram2s

```

296b *(Implementation of histograms procedures 294f)*+≡

```

pure subroutine fill_histogram2v (h, x, weight)
 type(histogram2), intent(inout) :: h
 real(kind=default), dimension(:), intent(in) :: x
 real(kind=default), intent(in), optional :: weight
 integer, dimension(2) :: i
 i = 1 + h%n_bins * (x - h%x_min) / (h%x_max - h%x_min)
 i = min (max (i, 0), h%n_bins + 1)
 if (present (weight)) then
 h%bins(i(1),i(2)) = h%bins(i(1),i(2)) + weight
 h%bins2(i(1),i(2)) = h%bins2(i(1),i(2)) + weight*weight
 else
 h%bins(i(1),i(2)) = h%bins(i(1),i(2)) + 1
 h%bins2(i(1),i(2)) = h%bins2(i(1),i(2)) + 1
 end if
end subroutine fill_histogram2v

```

296c *(Implementation of histograms procedures 294f)*+≡

```

elemental subroutine delete_histogram1 (h)
 type(histogram), intent(inout) :: h
 deallocate (h%bins, h%bins2)
 deallocate (h%bins3)
end subroutine delete_histogram1

```

```

297a <Implementation of histograms procedures 294f>+≡
 elemental subroutine delete_histogram2 (h)
 type(histogram2), intent(inout) :: h
 deallocate (h%bins, h%bins2)
 end subroutine delete_histogram2

297b <Implementation of histograms procedures 294f>+≡
 subroutine write_histogram1 (h, name, over)
 type(histogram), intent(in) :: h
 character(len=*), intent(in), optional :: name
 logical, intent(in), optional :: over
 integer :: i, iounit
 if (present (name)) then
 call find_free_unit (iounit)
 if (iounit > 0) then
 open (unit = iounit, action = "write", status = "replace", &
 file = name)
 if (present (over)) then
 if (over) then
 write (unit = iounit, fmt = *) &
 "underflow", h%bins(0), sqrt (h%bins2(0))
 end if
 end if
 do i = 1, h%n_bins
 write (unit = iounit, fmt = *) &
 midpoint (h, i), h%bins(i), sqrt (h%bins2(i))
 end do
 if (present (over)) then
 if (over) then
 write (unit = iounit, fmt = *) &
 "overflow", h%bins(h%n_bins+1), &
 sqrt (h%bins2(h%n_bins+1))
 end if
 end if
 close (unit = iounit)
 else
 print *, "write_histogram: Can't find a free unit!"
 end if
 else
 if (present (over)) then
 if (over) then
 print *, "underflow", h%bins(0), sqrt (h%bins2(0))
 end if
 end if
 end if

```

```

do i = 1, h%n_bins
 print *, midpoint (h, i), h%bins(i), sqrt (h%bins2(i))
end do
if (present (over)) then
 if (over) then
 print *, "overflow", h%bins(h%n_bins+1), &
 sqrt (h%bins2(h%n_bins+1))
 end if
end if
end if
end subroutine write_histogram1

```

298a <*Declaration of histograms procedures 294b*>+≡  
*!WK!* public :: write\_histogram1\_unit

 I don't like the format statement with the line number. Use a character constant instead (after we have merged with WHIZARD's branch).

298b <*Implementation of histograms procedures 294f*>+≡

```

subroutine write_histogram1_unit (h, iounit, over, show_excess)
 type(histogram), intent(in) :: h
 integer, intent(in) :: iounit
 logical, intent(in), optional :: over, show_excess
 integer :: i
 logical :: show_exc
 show_exc = .false.; if (present(show_excess)) show_exc = show_excess
 if (present (over)) then
 if (over) then
 if (show_exc) then
 write (unit = iounit, fmt = 1) &
 "underflow", h%bins(0), sqrt (h%bins2(0)), h%bins3(0)
 else
 write (unit = iounit, fmt = 1) &
 "underflow", h%bins(0), sqrt (h%bins2(0))
 end if
 end if
 end if
 do i = 1, h%n_bins
 if (show_exc) then
 write (unit = iounit, fmt = 1) &
 midpoint (h, i), h%bins(i), sqrt (h%bins2(i)), h%bins3(i)
 else
 write (unit = iounit, fmt = 1) &
 midpoint (h, i), h%bins(i), sqrt (h%bins2(i))
 end if
 end do
end subroutine write_histogram1_unit

```

```

 end if
 end do
 if (present (over)) then
 if (over) then
 if (show_exc) then
 write (unit = iounit, fmt = 1) &
 "overflow", h%bins(h%n_bins+1), &
 sqrt (h%bins2(h%n_bins+1)), &
 h%bins3(h%n_bins+1)
 else
 write (unit = iounit, fmt = 1) &
 "overflow", h%bins(h%n_bins+1), &
 sqrt (h%bins2(h%n_bins+1))
 end if
 end if
 end if
 end if
 1 format (1x,4(G16.9,2x))
end subroutine write_histogram1_unit

```

299a *<Declaration of histograms procedures 294b>*+≡

```
private :: midpoint
```

299b *<Interfaces of histograms procedures 294c>*+≡

```
interface midpoint
 module procedure midpoint1, midpoint2
end interface
```

299c *<Declaration of histograms procedures 294b>*+≡

```
private :: midpoint1, midpoint2
```

299d *<Implementation of histograms procedures 294f>*+≡

```
elemental function midpoint1 (h, bin) result (x)
 type(histogram), intent(in) :: h
 integer, intent(in) :: bin
 real(kind=default) :: x
 x = h%x_min + (h%x_max - h%x_min) * (bin - 0.5) / h%n_bins
end function midpoint1
```

299e *<Implementation of histograms procedures 294f>*+≡

```
elemental function midpoint2 (h, bin, d) result (x)
 type(histogram2), intent(in) :: h
 integer, intent(in) :: bin, d
 real(kind=default) :: x
 x = h%x_min(d) + (h%x_max(d) - h%x_min(d)) * (bin - 0.5) / h%n_bins(d)
end function midpoint2
```

300 <Implementation of histograms procedures 294f>+≡

```

subroutine write_histogram2 (h, name, over)
 type(histogram2), intent(in) :: h
 character(len=*), intent(in), optional :: name
 logical, intent(in), optional :: over
 integer :: i1, i2, iounit
 if (present (name)) then
 call find_free_unit (iounit)
 if (iounit > 0) then
 open (unit = iounit, action = "write", status = "replace", &
 file = name)
 if (present (over)) then
 if (over) then
 write (unit = iounit, fmt = *) &
 "double underflow", h%bins(0,0), sqrt (h%bins2(0,0))
 do i2 = 1, h%n_bins(2)
 write (unit = iounit, fmt = *) &
 "x1 underflow", midpoint (h, i2, 2), &
 h%bins(0,i2), sqrt (h%bins2(0,i2))
 end do
 do i1 = 1, h%n_bins(1)
 write (unit = iounit, fmt = *) &
 "x2 underflow", midpoint (h, i1, 1), &
 h%bins(i1,0), sqrt (h%bins2(i1,0))
 end do
 end if
 end if
 do i1 = 1, h%n_bins(1)
 do i2 = 1, h%n_bins(2)
 write (unit = iounit, fmt = *) &
 midpoint (h, i1, 1), midpoint (h, i2, 2), &
 h%bins(i1,i2), sqrt (h%bins2(i1,i2))
 end do
 end do
 if (present (over)) then
 if (over) then
 do i2 = 1, h%n_bins(2)
 write (unit = iounit, fmt = *) &
 "x1 overflow", midpoint (h, i2, 2), &
 h%bins(h%n_bins(1)+1,i2), &
 sqrt (h%bins2(h%n_bins(1)+1,i2))
 end do
 do i1 = 1, h%n_bins(1)

```

```

 write (unit = iounit, fmt = *) &
 "x2 overflow", midpoint (h, i1, 1), &
 h%bins(i1,h%n_bins(2)+1), &
 sqrt (h%bins2(i1,h%n_bins(2)+1))
 end do
 write (unit = iounit, fmt = *) "double overflow", &
 h%bins(h%n_bins(1)+1,h%n_bins(2)+1), &
 sqrt (h%bins2(h%n_bins(1)+1,h%n_bins(2)+1))
 end if
end if
close (unit = iounit)
else
 print *, "write_histogram: Can't find a free unit!"
end if
else
if (present (over)) then
 if (over) then
 print *, "double underflow", h%bins(0,0), sqrt (h%bins2(0,0))
 do i2 = 1, h%n_bins(2)
 print *, "x1 underflow", midpoint (h, i2, 2), &
 h%bins(0,i2), sqrt (h%bins2(0,i2))
 end do
 do i1 = 1, h%n_bins(1)
 print *, "x2 underflow", midpoint (h, i1, 1), &
 h%bins(i1,0), sqrt (h%bins2(i1,0))
 end do
 end if
end if
do i1 = 1, h%n_bins(1)
 do i2 = 1, h%n_bins(2)
 print *, midpoint (h, i1, 1), midpoint (h, i2, 2), &
 h%bins(i1,i2), sqrt (h%bins2(i1,i2))
 end do
end do
if (present (over)) then
 if (over) then
 do i2 = 1, h%n_bins(2)
 print *, "x1 overflow", midpoint (h, i2, 2), &
 h%bins(h%n_bins(1)+1,i2), &
 sqrt (h%bins2(h%n_bins(1)+1,i2))
 end do
 do i1 = 1, h%n_bins(1)
 print *, "x2 overflow", midpoint (h, i1, 1), &

```

```
 h%bins(i1,h%n_bins(2)+1), &
 sqrt (h%bins2(i1,h%n_bins(2)+1))
end do
print *, "double overflow", &
 h%bins(h%n_bins(1)+1,h%n_bins(2)+1), &
 sqrt (h%bins2(h%n_bins(1)+1,h%n_bins(2)+1))
end if
end if
end if
end subroutine write_histogram2
```

# —G— MISCELLANEOUS UTILITIES

303a <utils.f90 303a>≡  
  ! utils.f90 --  
  ⟨Copyleft notice 1⟩  
  module utils  
    use kinds  
    implicit none  
    private  
    ⟨Declaration of utils procedures 303b⟩  
    ⟨Parameters in utils 310c⟩  
    ⟨Variables in utils 311b⟩  
    ⟨Interfaces of utils procedures 303c⟩  
    character(len=\*), public, parameter :: UTILS\_RCS\_ID = &  
      "\$Id: utils.nw 314 2010-04-17 20:32:33Z ohl \$"  
    contains  
      ⟨Implementation of utils procedures 304c⟩  
  end module utils

## G.1 Memory Management

303b <Declaration of utils procedures 303b>≡  
  public :: create\_array\_pointer  
  private :: create\_integer\_array\_pointer  
  private :: create\_real\_array\_pointer  
  private :: create\_integer\_array2\_pointer  
  private :: create\_real\_array2\_pointer

303c <Interfaces of utils procedures 303c>≡  
  interface create\_array\_pointer  
    module procedure &  
      create\_integer\_array\_pointer, &

```

 create_real_array_pointer, &
 create_integer_array2_pointer, &
 create_real_array2_pointer
 end interface

304a <Body of create_*_array_pointer 304a>≡
 if (associated (lhs)) then
 if (size (lhs) /= n) then
 deallocate (lhs)
 if (present (lb)) then
 allocate (lhs(lb:n+lb-1))
 else
 allocate (lhs(n))
 end if
 end if
 else
 if (present (lb)) then
 allocate (lhs(lb:n+lb-1))
 else
 allocate (lhs(n))
 end if
 end if
 lhs = 0

304b <Body of create_*_array2_pointer 304b>≡
 if (associated (lhs)) then
 if (any (ubound (lhs) /= n)) then
 deallocate (lhs)
 if (present (lb)) then
 allocate (lhs(lb(1):n(1)+lb(1)-1,lb(2):n(2)+lb(2)-1))
 else
 allocate (lhs(n(1),n(2)))
 end if
 end if
 else
 if (present (lb)) then
 allocate (lhs(lb(1):n(1)+lb(1)-1,lb(2):n(2)+lb(2)-1))
 else
 allocate (lhs(n(1),n(2)))
 end if
 end if
 lhs = 0

304c <Implementation of utils procedures 304c>≡
 pure subroutine create_integer_array_pointer (lhs, n, lb)

```

```

 integer, dimension(:), pointer :: lhs
 integer, intent(in) :: n
 integer, intent(in), optional :: lb
 <Body of create_*_array_pointer 304a>
end subroutine create_integer_array_pointer

305a <Implementation of utils procedures 304c>+≡
pure subroutine create_real_array_pointer (lhs, n, lb)
 real(kind=default), dimension(:), pointer :: lhs
 integer, intent(in) :: n
 integer, intent(in), optional :: lb
 <Body of create_*_array_pointer 304a>
end subroutine create_real_array_pointer

305b <Implementation of utils procedures 304c>+≡
pure subroutine create_integer_array2_pointer (lhs, n, lb)
 integer, dimension(:, :,), pointer :: lhs
 integer, dimension(:,), intent(in) :: n
 integer, dimension(:,), intent(in), optional :: lb
 <Body of create_*_array2_pointer 304b>
end subroutine create_integer_array2_pointer

305c <Implementation of utils procedures 304c>+≡
pure subroutine create_real_array2_pointer (lhs, n, lb)
 real(kind=default), dimension(:, :,), pointer :: lhs
 integer, dimension(:,), intent(in) :: n
 integer, dimension(:,), intent(in), optional :: lb
 <Body of create_*_array2_pointer 304b>
end subroutine create_real_array2_pointer

Copy an allocatable array component of a derived type, reshaping the target
if necessary. The target can be disassociated, but its association must not
be undefined.

305d <Declaration of utils procedures 303b>+≡
public :: copy_array_pointer
private :: copy_integer_array_pointer
private :: copy_real_array_pointer
private :: copy_integer_array2_pointer
private :: copy_real_array2_pointer

305e <Interfaces of utils procedures 303c>+≡
interface copy_array_pointer
 module procedure &
 copy_integer_array_pointer, &
 copy_real_array_pointer, &
 copy_integer_array2_pointer, &

```

```

 copy_real_array2_pointer
 end interface

306a <Implementation of utils procedures 304c>+≡
 pure subroutine copy_integer_array_pointer (lhs, rhs, lb)
 integer, dimension(:), pointer :: lhs
 integer, dimension(:), intent(in) :: rhs
 integer, intent(in), optional :: lb
 call create_integer_array_pointer (lhs, size (rhs), lb)
 lhs = rhs
 end subroutine copy_integer_array_pointer

306b <Implementation of utils procedures 304c>+≡
 pure subroutine copy_real_array_pointer (lhs, rhs, lb)
 real(kind=default), dimension(:), pointer :: lhs
 real(kind=default), dimension(:), intent(in) :: rhs
 integer, intent(in), optional :: lb
 call create_real_array_pointer (lhs, size (rhs), lb)
 lhs = rhs
 end subroutine copy_real_array_pointer

306c <Implementation of utils procedures 304c>+≡
 pure subroutine copy_integer_array2_pointer (lhs, rhs, lb)
 integer, dimension(:, :,), pointer :: lhs
 integer, dimension(:, :,), intent(in) :: rhs
 integer, dimension(:,), intent(in), optional :: lb
 call create_integer_array2_pointer &
 (lhs, (/ size (rhs, dim=1), size (rhs, dim=2) /), lb)
 lhs = rhs
 end subroutine copy_integer_array2_pointer

306d <Implementation of utils procedures 304c>+≡
 pure subroutine copy_real_array2_pointer (lhs, rhs, lb)
 real(kind=default), dimension(:, :,), pointer :: lhs
 real(kind=default), dimension(:, :,), intent(in) :: rhs
 integer, dimension(:,), intent(in), optional :: lb
 call create_real_array2_pointer &
 (lhs, (/ size (rhs, dim=1), size (rhs, dim=2) /), lb)
 lhs = rhs
 end subroutine copy_real_array2_pointer

```

## G.2 Sorting

306e <Declaration of utils procedures 303b>+≡  
 public :: swap

```

 private :: swap_integer, swap_real
307a <Interfaces of utils procedures 303c>+≡
 interface swap
 module procedure swap_integer, swap_real
 end interface

307b <Implementation of utils procedures 304c>+≡
 elemental subroutine swap_integer (a, b)
 integer, intent(inout) :: a, b
 integer :: tmp
 tmp = a
 a = b
 b = tmp
 end subroutine swap_integer

307c <Implementation of utils procedures 304c>+≡
 elemental subroutine swap_real (a, b)
 real(kind=default), intent(inout) :: a, b
 real(kind=default) :: tmp
 tmp = a
 a = b
 b = tmp
 end subroutine swap_real

```

Straight insertion:

```

307d <Implementation of utils procedures 304c>+≡
 pure subroutine sort_real (key, reverse)
 real(kind=default), dimension(:), intent(inout) :: key
 logical, intent(in), optional :: reverse
 logical :: rev
 integer :: i, j
 <Set rev to reverse or .false. 307e>
 do i = 1, size (key) - 1
 <Set j to minloc(key) 308a>
 if (j /= i) then
 call swap (key(i), key(j))
 end if
 end do
 end subroutine sort_real

307e <Set rev to reverse or .false. 307e>≡
 if (present (reverse)) then
 rev = reverse
 else
 rev = .false.
 end if

```

```

308a <Set j to minloc(key) 308a>≡
 if (rev) then
 j = sum (maxloc (key(i:))) + i - 1
 else
 j = sum (minloc (key(i:))) + i - 1
 end if

308b <Implementation of utils procedures 304c>+≡
 pure subroutine sort_real_and_real_array (key, table, reverse)
 real(kind=default), dimension(:), intent(inout) :: key
 real(kind=default), dimension(:, :), intent(inout) :: table
 logical, intent(in), optional :: reverse
 logical :: rev
 integer :: i, j
 <Set rev to reverse or .false. 307e>
 do i = 1, size (key) - 1
 <Set j to minloc(key) 308a>
 if (j /= i) then
 call swap (key(i), key(j))
 call swap (table(:, i), table(:, j))
 end if
 end do
 end subroutine sort_real_and_real_array

308c <Implementation of utils procedures 304c>+≡
 pure subroutine sort_real_and_integer (key, table, reverse)
 real(kind=default), dimension(:), intent(inout) :: key
 integer, dimension(:), intent(inout) :: table
 logical, intent(in), optional :: reverse
 logical :: rev
 integer :: i, j
 <Set rev to reverse or .false. 307e>
 do i = 1, size (key) - 1
 <Set j to minloc(key) 308a>
 if (j /= i) then
 call swap (key(i), key(j))
 call swap (table(i), table(j))
 end if
 end do
 end subroutine sort_real_and_integer

308d <Declaration of utils procedures 303b>+≡
 public :: sort
 private :: sort_real, sort_real_and_real_array, sort_real_and_integer

```

309a *<Interfaces of utils procedures 303c>+≡*

```
interface sort
 module procedure &
 sort_real, sort_real_and_real_array, &
 sort_real_and_integer
end interface
```

## G.3 Mathematics

309b *<Declaration of utils procedures 303b>+≡*

```
public :: outer_product
```

Admittedly, one has to get used to this notation for the tensor product:

309c *<Implementation of utils procedures 304c>+≡*

```
pure function outer_product (x, y) result (xy)
 real(kind=default), dimension(:,), intent(in) :: x, y
 real(kind=default), dimension(size(x),size(y)) :: xy
 xy = spread (x, dim=2, ncopies=size(y)) &
 * spread (y, dim=1, ncopies=size(x))
end function outer_product
```

Greatest common divisor and least common multiple

309d *<Declaration of utils procedures 303b>+≡*

```
public :: factorize, gcd, lcm
private :: gcd_internal
```

For our purposes, a straightforward implementation of Euclid's algorithm suffices:

309e *<Implementation of utils procedures 304c>+≡*

```
pure recursive function gcd_internal (m, n) result (gcd_m_n)
 integer, intent(in) :: m, n
 integer :: gcd_m_n
 if (n <= 0) then
 gcd_m_n = m
 else
 gcd_m_n = gcd_internal (n, modulo (m, n))
 end if
end function gcd_internal
```

Wrap an elemental procedure around the recursive procedure:

309f *<Implementation of utils procedures 304c>+≡*

```
elemental function gcd (m, n) result (gcd_m_n)
 integer, intent(in) :: m, n
 integer :: gcd_m_n
```

```

 gcd_m_n = gcd_internal (m, n)
end function gcd

```

As long as  $m \cdot n$  does not overflow, we can use  $\text{gcd}(m, n) \text{lcm}(m, n) = mn$ :

310a *(Implementation of utils procedures 304c)* $\equiv$

```

elemental function lcm (m, n) result (lcm_m_n)
 integer, intent(in) :: m, n
 integer :: lcm_m_n
 lcm_m_n = (m * n) / gcd (m, n)
end function lcm

```

A very simple minded factorization procedure, that is not fool proof at all. It maintains  $n == \text{product}(\text{factors}(1:i))$ , however, and will work in all cases of practical relevance.

310b *(Implementation of utils procedures 304c)* $\equiv$

```

pure subroutine factorize (n, factors, i)
 integer, intent(in) :: n
 integer, dimension(:), intent(out) :: factors
 integer, intent(out) :: i
 integer :: nn, p
 nn = n
 i = 0
 do p = 1, size (PRIMES)
 try: do
 if (modulo (nn, PRIMES(p)) == 0) then
 i = i + 1
 factors(i) = PRIMES(p)
 nn = nn / PRIMES(p)
 if (i >= size (factors)) then
 factors(i) = nn
 return
 end if
 else
 exit try
 end if
 end do try
 if (nn == 1) then
 return
 end if
 end do
end subroutine factorize

```

310c *(Parameters in utils 310c)* $\equiv$

```

integer, dimension(13), parameter, private :: &
 PRIMES = (/ 2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41 /)

```

## G.4 I/O

311a *(Declaration of utils procedures 303b)*+≡  
    public :: find\_free\_unit

311b *(Variables in utils 311b)*≡  
    integer, parameter, private :: MIN\_UNIT = 11, MAX\_UNIT = 99

311c *(Implementation of utils procedures 304c)*+≡  
    subroutine find\_free\_unit (u, iostat)  
        integer, intent(out) :: u  
        integer, intent(out), optional :: iostat  
        logical :: exists, is\_open  
        integer :: i, status  
        do i = MIN\_UNIT, MAX\_UNIT  
            inquire (unit = i, exist = exists, opened = is\_open, &  
                      iostat = status)  
            if (status == 0) then  
                if (exists .and. .not. is\_open) then  
                    u = i  
                    if (present (iostat)) then  
                        iostat = 0  
                    end if  
                    return  
                end if  
            end if  
        end do  
        if (present (iostat)) then  
            iostat = -1  
        end if  
        u = -1  
    end subroutine find\_free\_unit

# —H— LINEAR ALGEBRA

```

312a <linalg.f90 312a>≡
 ! linalg.f90 --
 <Copyleft notice 1>
 module linalg
 use kinds
 use utils
 implicit none
 private
 <Declaration of linalg procedures 312b>
 character(len=*), public, parameter :: LINALG_RCS_ID = &
 "$Id: linalg.nw 314 2010-04-17 20:32:33Z ohl $"
 contains
 <Implementation of linalg procedures 313>
 end module linalg

```

## *H.1 LU Decomposition*

```

312b <Declaration of linalg procedures 312b>≡
 public :: lu_decompose

```

$$A = LU \tag{H.1a}$$

In more detail

$$\begin{pmatrix} a_{11} & a_{12} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \vdots & \vdots & \vdots & \vdots \\ a_{n1} & a_{n2} & \dots & a_{nn} \end{pmatrix} = \begin{pmatrix} 1 & 0 & \dots & 0 \\ l_{21} & 1 & \dots & 0 \\ \vdots & \vdots & \vdots & \vdots \\ l_{n1} & l_{n2} & \dots & 1 \end{pmatrix} \begin{pmatrix} u_{11} & u_{12} & \dots & u_{1n} \\ 0 & u_{22} & \dots & u_{2n} \\ \vdots & \vdots & \vdots & \vdots \\ 0 & 0 & \dots & u_{nn} \end{pmatrix} \tag{H.1b}$$

Rewriting (H.1) in block matrix notation

$$\begin{pmatrix} a_{11} & a_{1\cdot} \\ a_{\cdot 1} & A \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ l_{\cdot 1} & L \end{pmatrix} \begin{pmatrix} u_{11} & u_{1\cdot} \\ 0 & U \end{pmatrix} = \begin{pmatrix} u_{11} & u_{1\cdot} \\ l_{\cdot 1}u_{11} & l_{\cdot 1} \otimes u_{1\cdot} + LU \end{pmatrix} \quad (\text{H.2})$$

we can solve it easily

$$u_{11} = a_{11} \quad (\text{H.3a})$$

$$u_{1\cdot} = a_{1\cdot} \quad (\text{H.3b})$$

$$l_{\cdot 1} = \frac{a_{\cdot 1}}{a_{11}} \quad (\text{H.3c})$$

$$LU = A - \frac{a_{\cdot 1} \otimes a_{1\cdot}}{a_{11}} \quad (\text{H.3d})$$

and (H.3c) and (H.3d) define a simple iterative algorithm if we work from the outside in. It just remains to add pivoting.

313 *Implementation of linalg procedures 313*≡

```

pure subroutine lu_decompose (a, pivots, eps, l, u)
 real(kind=default), dimension(:, :,), intent(inout) :: a
 integer, dimension(:), intent(out), optional :: pivots
 real(kind=default), intent(out), optional :: eps
 real(kind=default), dimension(:, :,), intent(out), optional :: l, u
 real(kind=default), dimension(size(a, dim=1)) :: vv
 integer, dimension(size(a, dim=1)) :: p
 integer :: j, pivot
 <eps = 1 314a>
 vv = maxval (abs (a), dim=2)
 if (any (vv == 0.0)) then
 a = 0.0
 <pivots = 0 and eps = 0 314c>
 return
 end if
 vv = 1.0 / vv
 do j = 1, size (a, dim=1)
 pivot = j - 1 + sum (maxloc (vv(j:) * abs (a(j:, j))))
 if (j /= pivot) then
 call swap (a(pivot, :), a(j, :))
 <eps = - eps 314b>
 vv(pivot) = vv(j)
 end if
 p(j) = pivot
 if (a(j, j) == 0.0) then
 a(j, j) = tiny (a(j, j))
 end if
 end do

```

```

 end if
 a(j+1:,j) = a(j+1:,j) / a(j,j)
 a(j+1:,j+1:) &
 = a(j+1:,j+1:) - outer_product (a(j+1:,j), a(j,j+1:))
end do
<Return optional arguments in lu_decompose 314d>
end subroutine lu_decompose

314a <eps = 1 314a>≡
 if (present (eps)) then
 eps = 1.0
 end if

314b <eps = - eps 314b>≡
 if (present (eps)) then
 eps = - eps
 end if

314c <pivots = 0 and eps = 0 314c>≡
 if (present (pivots)) then
 pivots = 0
 end if
 if (present (eps)) then
 eps = 0
 end if

314d <Return optional arguments in lu_decompose 314d>≡
 if (present (pivots)) then
 pivots = p
 end if
 if (present (l)) then
 do j = 1, size (a, dim=1)
 l(1:j-1,j) = 0.0
 l(j,j) = 1.0
 l(j+1:,j) = a(j+1:,j)
 end do
 do j = size (a, dim=1), 1, -1
 call swap (l(j,:), l(p(j),:))
 end do
 end if
 if (present (u)) then
 do j = 1, size (a, dim=1)
 u(1:j,j) = a(1:j,j)
 u(j+1:,j) = 0.0
 end do
 end if

```

## H.2 Determinant

315a *(Declaration of linalg procedures 312b)* +≡  
 public :: determinant

This is a subroutine to comply with F's rules, otherwise, we would code it as a function.

315b *(Implementation of linalg procedures 313)* +≡  
 pure subroutine determinant (a, det)  
 real(kind=default), dimension(:, :), intent(in) :: a  
 real(kind=default), intent(out) :: det  
 real(kind=default), dimension(size(a, dim=1), size(a, dim=2)) :: lu  
 integer :: i  
 lu = a  
 call lu\_decompose (lu, eps = det)  
 do i = 1, size (a, dim = 1)  
 det = det \* lu(i,i)  
 end do  
 end subroutine determinant

## H.3 Diagonalization

The code is an implementation of the algorithm presented in [16, 17], but independent from the code presented in [18] to avoid legal problems.

A Jacobi rotation around the angle  $\phi$  in row  $p$  and column  $q$

$$P(\phi; p, q) = \begin{pmatrix} 1 & & & & \\ & \ddots & & & \\ & & \cos \phi & \cdots & \sin \phi \\ & & \vdots & 1 & \vdots \\ & & -\sin \phi & \cdots & \cos \phi \\ & & & & \ddots \\ & & & & 1 \end{pmatrix} \quad (\text{H.4})$$

results in

$$A' = P^T(\phi; p, q) \cdot A \cdot P(\phi; p, q) = \begin{pmatrix} & A'_{1p} & A'_{1q} \\ & \vdots & \vdots \\ A'_{p1} & \cdots & A'_{pq} & \cdots & A'_{pq} & \cdots & A'_{pn} \\ & \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ A'_{q1} & \cdots & A'_{qp} & \cdots & A'_{qq} & \cdots & A'_{qn} \\ & \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ & A'_{np} & & A'_{nq} & & & \end{pmatrix} \quad (\text{H.5})$$

316a *(Declaration of linalg procedures 312b)* +≡  
 public :: diagonalize\_real\_symmetric

316b *(Implementation of linalg procedures 313)* +≡  
 pure subroutine diagonalize\_real\_symmetric (a, eval, evec, num\_rot)  
 real(kind=default), dimension(:, :, ), intent(in) :: a  
 real(kind=default), dimension(:), intent(out) :: eval  
 real(kind=default), dimension(:, :, ), intent(out) :: evec  
 integer, intent(out), optional :: num\_rot  
 real(kind=default), dimension(size(a, dim=1), size(a, dim=2)) :: aa  
 real(kind=default) :: off\_diagonal\_norm, threshold, &  
 c, g, h, s, t, tau, cot\_2phi  
 logical, dimension(size(eval), size(eval)) :: upper\_triangle  
 integer, dimension(size(eval)) :: one\_to\_ndim  
 integer :: p, q, ndim, j, sweep  
 integer, parameter :: MAX\_SWEEPS = 50  
 ndim = size (eval)  
 one\_to\_ndim = (/ (j, j=1,ndim) /)  
 upper\_triangle = &  
 spread (one\_to\_ndim, dim=1, ncopies=ndim) &  
 > spread (one\_to\_ndim, dim=2, ncopies=ndim)  
 aa = a  
 call unit (evec)  
*(Initialize num\_rot 319e)*  
 sweeps: do sweep = 1, MAX\_SWEEPS  
 off\_diagonal\_norm = sum (abs (aa), mask=upper\_triangle)  
 if (off\_diagonal\_norm == 0.0) then  
 eval = diag (aa)  
 return  
 end if  
 if (sweep < 4) then  
 threshold = 0.2 \* off\_diagonal\_norm / ndim\*\*2  
 else

```

 threshold = 0.0
 end if
 do p = 1, ndim - 1
 do q = p + 1, ndim
 ⟨Perform the Jacobi rotation resulting in $A'_{pq} = 0$ 317⟩
 end do
 end do
end do sweeps
if (present (num_rot)) then
 num_rot = -1
end if
!!! print *, "linalg::diagonalize_real_symmetric: exceeded sweep count"
end subroutine diagonalize_real_symmetric

317 ⟨Perform the Jacobi rotation resulting in $A'_{pq} = 0$ 317⟩≡
g = 100 * abs (aa (p,q))
if ((sweep > 4) &
 .and. (g <= min (spacing (aa(p,p)), spacing (aa(q,q))))) then
 aa(p,q) = 0.0
else if (abs (aa(p,q)) > threshold) then
 ⟨Determine ϕ for the Jacobi rotation $P(\phi; p, q)$ with $A'_{pq} = 0$ 318a⟩
 ⟨ $A' = P^T(\phi; p, q) \cdot A \cdot P(\phi; p, q)$ 318c⟩
 ⟨ $V' = V \cdot P(\phi; p, q)$ 319d⟩
 ⟨Update num_rot 319f⟩
end if

```

We want

$$A'_{pq} = (c^2 - s^2)A_{pq} + sc(A_{pp} - A_{qq}) = 0 \quad (\text{H.6})$$

and therefore

$$\cot 2\phi = \frac{1 - \tan^2 \phi}{2 \tan \phi} = \frac{\cos^2 \phi - \sin^2 \phi}{2 \sin \phi \cos \phi} = \frac{A_{pp} - A_{qq}}{2A_{pq}} \quad (\text{H.7})$$

i.e. with  $t = \tan \phi = s/c$

$$t^2 + 2t \cot 2\phi - 1 = 0 \quad (\text{H.8})$$

This quadratic equation has the roots

$$t = -\cot 2\phi \pm \sqrt{1 + \cot^2 2\phi} = \frac{\epsilon(\cot 2\phi)}{|\cot 2\phi| \pm \epsilon(\cot 2\phi)\sqrt{1 + \cot^2 2\phi}} \quad (\text{H.9})$$

and the smaller in magnitude of these is

$$t = \frac{\epsilon(\cot 2\phi)}{|\cot 2\phi| + \sqrt{1 + \cot^2 2\phi}} \quad (\text{H.10})$$

and since  $|t| \leq 1$ , it corresponds to  $|\phi| \leq \pi/4$ . For very large  $\cot 2\phi$  we will use

$$t = \frac{1}{2 \cot 2\phi} = \frac{A_{pq}}{A_{pp} - A_{qq}} \quad (\text{H.11})$$

$$h = A_{qq} - A_{pp} \quad (\text{H.12})$$

318a  $\langle$  Determine  $\phi$  for the Jacobi rotation  $P(\phi; p, q)$  with  $A'_{pq} = 0$  318a  $\rangle \equiv$

```

h = aa(q,q) - aa(p,p)
if (g <= spacing (h)) then
 t = aa(p,q) / h
else
 cot_2phi = 0.5 * h / aa(p,q)
 t = sign (1.0_default, cot_2phi) &
 / (abs (cot_2phi) + sqrt (1.0 + cot_2phi**2))
end if

```

Trivia

$$\cos^2 \phi = \frac{\cos^2 \phi}{\cos^2 \phi + \sin^2 \phi} = \frac{1}{1 + \tan^2 \phi} \quad (\text{H.13a})$$

$$\sin \phi = \tan \phi \cos \phi \quad (\text{H.13b})$$

$$\tau \sin \phi = \frac{\sin^2}{1 + \cos \phi} = \frac{1 - \cos^2}{1 + \cos \phi} = 1 - \cos \phi \quad (\text{H.13c})$$

318b  $\langle$  Determine  $\phi$  for the Jacobi rotation  $P(\phi; p, q)$  with  $A'_{pq} = 0$  318a  $\rangle + \equiv$

```

c = 1.0 / sqrt (1.0 + t**2)
s = t * c
tau = s / (1.0 + c)
A'_{pp} = c^2 A_{pp} + s^2 A_{qq} - 2scA_{pq} = A_{pp} - tA_{pq}
A'_{qq} = s^2 A_{pp} + c^2 A_{qq} + 2scA_{pq} = A_{qq} + tA_{pq}
A'_{pq} = (c^2 - s^2)A_{pq} + sc(A_{pp} - A_{qq})

```

318c  $\langle A' = P^T(\phi; p, q) \cdot A \cdot P(\phi; p, q)$  318c  $\rangle \equiv$

```

aa(p,p) = aa(p,p) - t * aa(p,q)
aa(q,q) = aa(q,q) + t * aa(p,q)
aa(p,q) = 0.0

```

$$\begin{aligned}
r \neq p < q \neq r : A'_{rp} &= cA_{rp} - sA_{rq} \\
A'_{rq} &= sA_{rp} + cA_{rq}
\end{aligned} \quad (\text{H.15})$$

Here's how we cover the upper triangular region using array notation:

$$\begin{pmatrix} & a(1:p-1,p) & & a(1:p-1,q) & \\ \dots & A_{pq} & a(p,p+1:q-1) & A_{pq} & a(p,q+1:ndim) \\ & \vdots & & a(p+1:q-1,q) & \\ \dots & A_{qp} & \dots & A_{qq} & a(q,q+1:ndim) \\ & \vdots & & \vdots & \end{pmatrix} \quad (\text{H.16})$$

319a  $\langle A' = P^T(\phi; p, q) \cdot A \cdot P(\phi; p, q) \text{ 318c} \rangle + \equiv$   
 call jacobi\_rotation (s, tau, aa(1:p-1,p), aa(1:p-1,q))  
 call jacobi\_rotation (s, tau, aa(p,p+1:q-1), aa(p+1:q-1,q))  
 call jacobi\_rotation (s, tau, aa(p,q+1:ndim), aa(q,q+1:ndim))

Using (H.13c), we can write the rotation as a perturbation:

$$\begin{aligned} V'_p &= cV_p - sV_q = V_p - s(V_q + \tau V_p) \\ V'_q &= sV_p + cV_q = V_q + s(V_p - \tau V_q) \end{aligned} \quad (\text{H.17})$$

319b  $\langle \text{Implementation of linalg procedures 313} \rangle + \equiv$   
 pure subroutine jacobi\_rotation (s, tau, vp, vq)  
 real(kind=default), intent(in) :: s, tau  
 real(kind=default), dimension(:), intent(inout) :: vp, vq  
 real(kind=default), dimension(size(vp)) :: vp\_tmp  
 vp\_tmp = vp  
 vp = vp - s \* (vq + tau \* vp)  
 vq = vq + s \* (vp\_tmp - tau \* vq)  
 end subroutine jacobi\_rotation

319c  $\langle \text{Declaration of linalg procedures 312b} \rangle + \equiv$   
 private :: jacobi\_rotation

319d  $\langle V' = V \cdot P(\phi; p, q) \text{ 319d} \rangle \equiv$   
 call jacobi\_rotation (s, tau, evec(:,p), evec(:,q))

319e  $\langle \text{Initialize num\_rot 319e} \rangle \equiv$   
 if (present (num\_rot)) then  
     num\_rot = 0  
 end if

319f  $\langle \text{Update num\_rot 319f} \rangle \equiv$   
 if (present (num\_rot)) then  
     num\_rot = num\_rot + 1  
 end if

320a *⟨Implementation of linalg procedures 313⟩*+≡

```

pure subroutine unit (u)
 real(kind=default), dimension(:, :,), intent(out) :: u
 integer :: i
 u = 0.0
 do i = 1, min (size (u, dim = 1), size (u, dim = 2))
 u(i,i) = 1.0
 end do
end subroutine unit
```

320b *⟨Implementation of linalg procedures 313⟩*+≡

```

pure function diag (a) result (d)
 real(kind=default), dimension(:, :,), intent(in) :: a
 real(kind=default), dimension(min(size(a,dim=1),size(a,dim=2))) :: d
 integer :: i
 do i = 1, min (size (a, dim = 1), size (a, dim = 2))
 d(i) = a(i,i)
 end do
end function diag
```

320c *⟨Declaration of linalg procedures 312b⟩*+≡

```

public :: unit, diag
```

## H.4 Test

320d *⟨la\_sample.f90 320d⟩*≡

```

! la_sample.f90 --
⟨Copyleft notice 1⟩
program la_sample
 use kinds
 use utils
 use tao_random_numbers
 use linalg
 implicit none
 integer, parameter :: N = 200
 real(kind=default), dimension(N,N) :: a, evec, a0, l, u, NAG_bug
 real(kind=default), dimension(N) :: b, eval
 real(kind=default) :: d
 integer :: i
 call system_clock (i)
 call tao_random_seed (i)
 print *, i
 do i = 1, N
```

```

 call tao_random_number (a(:,i))
end do
NAG_bug = (a + transpose (a)) / 2
a = NAG_bug
a0 = a
call lu_decompose (a, l=l, u=u)
a = matmul (l, u)
print *, maxval (abs(a-a0))
call determinant (a, d)
print *, d
call diagonalize_real_symmetric (a, eval, evec)
print *, product (eval)
stop
call sort (eval, evec)
do i = 1, N
 b = matmul (a, evec(:,i)) - eval(i) * evec(:,i)
 write (unit = *, fmt = "(A,I3, 2(A,E11.4))") &
 "eval #", i, " = ", eval(i), ", |(A-lambda)V|_infty = ", &
 maxval (abs(b)) / maxval (abs(evec(:,i)))
end do
end program la_sample

```

# —I— PRODUCTS

```
322 <products.f90 322>≡
 ! products.f90 --
 <Copyleft notice 1>
 module products
 use kinds
 implicit none
 private
 public :: dot, sp, spc
 character(len=*), public, parameter :: PRODUCTS_RCS_ID = &
 "$Id: products.nw 314 2010-04-17 20:32:33Z ohl $"
 contains
 pure function dot (p, q) result (pq)
 real(kind=default), dimension(0:), intent(in) :: p, q
 real(kind=default) :: pq
 pq = p(0)*q(0) - dot_product (p(1:), q(1:))
 end function dot
 pure function sp (p, q) result (sppq)
 real(kind=default), dimension(0:), intent(in) :: p, q
 complex(kind=default) :: sppq
 sppq = cmplx (p(2), p(3)) * sqrt ((q(0)-q(1))/(p(0)-p(1))) &
 - cmplx (q(2), q(3)) * sqrt ((p(0)-p(1))/(q(0)-q(1)))
 end function sp
 pure function spc (p, q) result (spcpq)
 real(kind=default), dimension(0:), intent(in) :: p, q
 complex(kind=default) :: spcpq
 spcpq = conjg (sp (p, q))
 end function spc
 end module products
```

# —J— KINEMATICS

```
323a <kinematics.f90 323a>≡
 ! kinematics.f90 --
 <Copyleft notice 1>
 module kinematics
 use kinds
 use constants
 use products, only: dot
 use specfun, only: gamma
 implicit none
 private
 <Declaration of kinematics procedures 323b>
 <Interfaces of kinematics procedures 323c>
 <Declaration of kinematics types 325g>
 character(len=*), public, parameter :: KINEMATICS_RCS_ID = &
 "$Id: kinematics.nw 314 2010-04-17 20:32:33Z ohl $"
contains
 <Implementation of kinematics procedures 324a>
end module kinematics
```

## J.1 Lorentz Transformations

```
323b <Declaration of kinematics procedures 323b>≡
 public :: boost_velocity
 private :: boost_one_velocity, boost_many_velocity
 public :: boost_momentum
 private :: boost_one_momentum, boost_many_momentum
323c <Interfaces of kinematics procedures 323c>≡
 interface boost_velocity
 module procedure boost_one_velocity, boost_many_velocity
```

```

end interface
interface boost_momentum
 module procedure boost_one_momentum, boost_many_momentum
end interface

```

Boost a four vector  $p$  to the inertial frame moving with the velocity  $\beta$ :

$$p'_0 = \gamma (p_0 - \vec{\beta} \vec{p}) \quad (\text{J.1a})$$

$$\vec{p}' = \gamma (\vec{p}_{\parallel} - \vec{\beta} p_0) + \vec{p}_{\perp} \quad (\text{J.1b})$$

with  $\gamma = 1/\sqrt{1 - \vec{\beta}^2}$ ,  $\vec{p}_{\parallel} = \vec{\beta}(\vec{\beta} \vec{p})/\vec{\beta}^2$  and  $\vec{p}_{\perp} = \vec{p} - \vec{p}_{\parallel}$ . Using  $1/\vec{\beta}^2 = \gamma^2/(\gamma + 1) \cdot 1/(\gamma - 1)$  and  $\vec{b} = \gamma \vec{\beta}$  this can be rewritten as

$$p'_0 = \gamma p_0 - \vec{b} \vec{p} \quad (\text{J.2a})$$

$$\vec{p}' = \vec{p} + \left( \frac{\vec{b} \vec{p}}{\gamma + 1} - p_0 \right) \vec{b} \quad (\text{J.2b})$$

**324a** *(Implementation of kinematics procedures 324a)≡*

```

pure function boost_one_velocity (p, beta) result (p_prime)
 real(kind=default), dimension(0:), intent(in) :: p
 real(kind=default), dimension(1:), intent(in) :: beta
 real(kind=default), dimension(0:3) :: p_prime
 real(kind=default), dimension(1:3) :: b
 real(kind=default) :: gamma, b_dot_p
 gamma = 1.0 / sqrt (1.0 - dot_product (beta, beta))
 b = gamma * beta
 b_dot_p = dot_product (b, p(1:3))
 p_prime(0) = gamma * p(0) - b_dot_p
 p_prime(1:3) = p(1:3) + (b_dot_p / (1.0 + gamma) - p(0)) * b
end function boost_one_velocity

```

**324b** *(Implementation of kinematics procedures 324a)+≡*

```

pure function boost_many_velocity (p, beta) result (p_prime)
 real(kind=default), dimension(:,0:), intent(in) :: p
 real(kind=default), dimension(1:), intent(in) :: beta
 real(kind=default), dimension(size(p,dim=1),0:3) :: p_prime
 integer :: i
 do i = 1, size (p, dim=1)
 p_prime(i,:) = boost_one_velocity (p(i,:), beta)
 end do
end function boost_many_velocity

```

Boost a four vector  $p$  to the rest frame of the four vector  $q$ . The velocity is  $\vec{\beta} = \vec{q}/|q_0|$ :

- 325a *(Implementation of kinematics procedures 324a)* +≡
- ```
pure function boost_one_momentum (p, q) result (p_prime)
    real(kind=default), dimension(0::), intent(in) :: p, q
    real(kind=default), dimension(0:3) :: p_prime
    p_prime = boost_velocity (p, q(1:3) / abs (q(0)))
end function boost_one_momentum
```
- 325b *(Implementation of kinematics procedures 324a)* +≡
- ```
pure function boost_many_momentum (p, q) result (p_prime)
 real(kind=default), dimension(:,0::), intent(in) :: p
 real(kind=default), dimension(0::), intent(in) :: q
 real(kind=default), dimension(size(p,dim=1),0:3) :: p_prime
 p_prime = boost_many_velocity (p, q(1:3) / abs (q(0)))
end function boost_many_momentum
```

## J.2 Massive Phase Space

$$\lambda(a, b, c) = a^2 + b^2 + c^2 - 2ab - 2bc - 2ca = (a - b - c)^2 - 4bc \quad (\text{J.3})$$

and permutations

- 325c *(Implementation of kinematics procedures 324a)* +≡
- ```
pure function lambda (a, b, c) result (lam)
    real(kind=default), intent(in) :: a, b, c
    real(kind=default) :: lam
    lam = a**2 + b**2 + c**2 - 2*(a*b + b*c + c*a)
end function lambda
```
- 325d *(Declaration of kinematics procedures 323b)* +≡
- ```
public :: lambda
```
- 325e *(Declaration of kinematics procedures 323b)* +≡
- ```
public :: two_to_three
private :: two_to_three_massive, two_to_three_massless
```
- 325f *(Interfaces of kinematics procedures 323c)* +≡
- ```
interface two_to_three
 module procedure two_to_three_massive, two_to_three_massless
end interface
```
- 325g *(Declaration of kinematics types 325g)* ≡
- ```
type, public :: LIPS3
    real(kind=default), dimension(3,0:3) :: p
    real(kind=default) :: jacobian
end type LIPS3
```

$$dLIPS_3 = \int \frac{d^3\vec{p}_1}{(2\pi)^3 2E_1} \frac{d^3\vec{p}_2}{(2\pi)^3 2E_2} \frac{d^3\vec{p}_3}{(2\pi)^3 2E_3} (2\pi)^4 \delta^4(p_1 + p_2 + p_3 - p_a - p_b) \quad (J.4)$$

The jacobian is given by

$$dLIPS_3 = \frac{1}{(2\pi)^5} \int d\phi dt_1 ds_2 d\Omega_3^{[23]} \frac{1}{32\sqrt{ss_2}} \frac{|\vec{p}_3^{[23]}|}{|\vec{p}_a^{[ab]}|} \quad (J.5)$$

where $\vec{p}_i^{[jk]}$ denotes the momentum of particle i in the center of mass system of particles j and k .

326a *(Implementation of kinematics procedures 324a) +≡*

```

pure function two_to_three_massive &
    (s, t1, s2, phi, cos_theta3, phi3, ma, mb, m1, m2, m3) result (p)
    real(kind=default), intent(in) :: s, t1, s2, phi, cos_theta3, phi3, ma, mb, m1, m2, m3
    type(LIPS3) :: p
    real(kind=default), dimension(0:3) :: p23
    real(kind=default) :: Ea, pa_abs, E1, p1_abs, p3_abs, cos_theta
    pa_abs = sqrt (lambda (s, ma**2, mb**2) / (4 * s))
    Ea = sqrt (ma**2 + pa_abs**2)
    p1_abs = sqrt (lambda (s, m1**2, s2) / (4 * s))
    E1 = sqrt (m1**2 + p1_abs**2)
    p3_abs = sqrt (lambda (s2, m2**2, m3**2) / (4 * s2))
    p%jacobian = 1.0 / (2*PI)**5 * (p3_abs / pa_abs) / (32 * sqrt (s * s2))
    cos_theta = (t1 - ma**2 - m1**2 + 2*Ea*E1) / (2*pa_abs*p1_abs)
    p%p(1,1:3) = polar_to_cartesian (p1_abs, cos_theta, phi)
    p%p(1,0) = on_shell (p%p(1,:), m1)
    p23(1:3) = - p%p(1,1:3)
    p23(0) = on_shell (p23, sqrt (s2))
    p%p(3:2:-1,:) = one_to_two (p23, cos_theta3, phi3, m3, m2)
end function two_to_three_massive

```

A specialized version for massless particles can be faster, because the kinematics is simpler:

326b *(Implementation of kinematics procedures 324a) +≡*

```

pure function two_to_three_massless (s, t1, s2, phi, cos_theta3, phi3) &
    result (p)
    real(kind=default), intent(in) :: s, t1, s2, phi, cos_theta3, phi3
    type(LIPS3) :: p
    real(kind=default), dimension(0:3) :: p23
    real(kind=default) :: pa_abs, p1_abs, p3_abs, cos_theta
    pa_abs = sqrt (s) / 2
    p1_abs = (s - s2) / (2 * sqrt (s))

```

```

p3_abs = sqrt (s2) / 2
p%jacobian = 1.0 / ((2*PI)**5 * 32 * s)
cos_theta = 1 + t1 / (2*pa_abs*p1_abs)
p%p(1,0) = p1_abs
p%p(1,1:3) = polar_to_cartesian (p1_abs, cos_theta, phi)
p23(1:3) = - p%p(1,1:3)
p23(0) = on_shell (p23, sqrt (s2))
p%p(3:2:-1,:) = one_to_two (p23, cos_theta3, phi3)
end function two_to_three_massless

327a <Declaration of kinematics procedures 323b>+≡
public :: one_to_two
private :: one_to_two_massive, one_to_two_massless

327b <Interfaces of kinematics procedures 323c>+≡
interface one_to_two
  module procedure one_to_two_massive, one_to_two_massless
end interface

327c <Implementation of kinematics procedures 324a>+≡
pure function one_to_two_massive (p12, cos_theta, phi, m1, m2) result (p)
  real(kind=default), dimension(0:), intent(in) :: p12
  real(kind=default), intent(in) :: cos_theta, phi, m1, m2
  real(kind=default), dimension(2,0:3) :: p
  real(kind=default) :: s, p1_abs
  s = dot (p12, p12)
  p1_abs = sqrt (lambda (s, m1**2, m2**2) / (4 * s))
  p(1,1:3) = polar_to_cartesian (p1_abs, cos_theta, phi)
  p(2,1:3) = - p(1,1:3)
  p(1,0) = on_shell (p(1,:), m1)
  p(2,0) = on_shell (p(2,:), m2)
  p = boost_momentum (p, - p12)
end function one_to_two_massive

327d <Implementation of kinematics procedures 324a>+≡
pure function one_to_two_massless (p12, cos_theta, phi) result (p)
  real(kind=default), dimension(0:), intent(in) :: p12
  real(kind=default), intent(in) :: cos_theta, phi
  real(kind=default), dimension(2,0:3) :: p
  real(kind=default) :: p1_abs
  p1_abs = sqrt (dot (p12, p12)) / 2
  p(1,0) = p1_abs
  p(1,1:3) = polar_to_cartesian (p1_abs, cos_theta, phi)
  p(2,0) = p1_abs
  p(2,1:3) = - p(1,1:3)
  p = boost_momentum (p, - p12)

```

```

    end function one_to_two_massless
328a <Declaration of kinematics procedures 323b>+≡
    public :: polar_to_cartesian, on_shell
328b <Implementation of kinematics procedures 324a>+≡
    pure function polar_to_cartesian (v_abs, cos_theta, phi) result (v)
        real(kind=default), intent(in) :: v_abs, cos_theta, phi
        real(kind=default), dimension(3) :: v
        real(kind=default) :: sin_phi, cos_phi, sin_theta
        sin_theta = sqrt (1.0 - cos_theta**2)
        cos_phi = cos (phi)
        sin_phi = sin (phi)
        v = (/ sin_theta * cos_phi, sin_theta * sin_phi, cos_theta /) * v_abs
    end function polar_to_cartesian
328c <Implementation of kinematics procedures 324a>+≡
    pure function on_shell (p, m) result (E)
        real(kind=default), dimension(0:), intent(in) :: p
        real(kind=default), intent(in) :: m
        real(kind=default) :: E
        E = sqrt (m**2 + dot_product (p(1:3), p(1:3)))
    end function on_shell

```

J.3 Massive 3-Particle Phase Space Revisited

$$\begin{array}{ccccc}
 U_1 & \xrightarrow{\xi_1} & P_1 & \xrightarrow{\phi_1} & M \\
 \pi_U \downarrow & & \downarrow \pi_P & & \parallel \\
 U_2 & \xrightarrow{\xi_2} & P_2 & \xrightarrow{\phi_2} & M
 \end{array} \tag{J.6}$$

$$\begin{array}{ccccc}
 U_1 & \xrightarrow{\xi} & P_1 & \xrightarrow{\phi} & M \\
 \pi_U \downarrow & & \downarrow \pi_P & & \downarrow \pi \\
 U_2 & \xrightarrow{\xi} & P_2 & \xrightarrow{\phi} & M
 \end{array} \tag{J.7}$$

```

328d <kinematics.f90 323a>+≡
module phase_space
    use kinds
    use constants
    use kinematics !NODEP!
    use tao_random_numbers
    implicit none
    private

```

```

⟨Declaration of phase_space procedures 330b⟩
⟨Interfaces of phase_space procedures 330c⟩
⟨Declaration of phase_space types 329a⟩
character(len=*), public, parameter :: PHASE_SPACE_RCS_ID = &
    "$Id: kinematics.nw 314 2010-04-17 20:32:33Z ohl $"
contains
    ⟨Implementation of phase_space procedures 330d⟩
end module phase_space
    LIPS3_unit : [0, 1]5

```

(J.8)

329a ⟨Declaration of phase_space types 329a⟩≡
 type, public :: LIPS3_unit
 real(kind=default), dimension(5) :: x
 real(kind=default) :: s
 real(kind=default), dimension(2) :: mass_in
 real(kind=default), dimension(3) :: mass_out
 real(kind=default) :: jacobian
 end type LIPS3_unit

329b ⟨Declaration of phase_space types 329a⟩+≡
 type, public :: LIPS3_unit_massless
 real(kind=default), dimension(5) :: x
 real(kind=default) :: s
 real(kind=default) :: jacobian
 end type LIPS3_unit_massless
 LIPS3_s2_t1_angles : (s₂, t₁, φ, cos θ₃, φ₃)

(J.9)

329c ⟨Declaration of phase_space types 329a⟩+≡
 type, public :: LIPS3_s2_t1_angles
 real(kind=default) :: s₂, t₁, φ, cos_theta3, phi3
 real(kind=default) :: s
 real(kind=default), dimension(2) :: mass_in
 real(kind=default), dimension(3) :: mass_out
 real(kind=default) :: jacobian
 end type LIPS3_s2_t1_angles

329d ⟨Declaration of phase_space types 329a⟩+≡
 type, public :: LIPS3_s2_t1_angles_massless
 real(kind=default) :: s₂, t₁, φ, cos_theta3, phi3
 real(kind=default) :: s
 real(kind=default) :: jacobian
 end type LIPS3_s2_t1_angles_massless
 LIPS3_momenta : (p₁, p₂, p₃)

(J.10)

329e ⟨Declaration of phase_space types 329a⟩+≡

```

type, public :: LIPS3_momenta
    real(kind=default), dimension(0:3,3) :: p
    real(kind=default) :: s
    real(kind=default), dimension(2) :: mass_in
    real(kind=default), dimension(3) :: mass_out
    real(kind=default) :: jacobian
end type LIPS3_momenta

330a <Declaration of phase_space types 329a>+≡
type, public :: LIPS3_momenta_massless
    real(kind=default), dimension(0:3,3) :: p
    real(kind=default) :: s
    real(kind=default) :: jacobian
end type LIPS3_momenta_massless

330b <Declaration of phase_space procedures 330b>≡
public :: random_LIPS3
private :: random_LIPS3_unit, random_LIPS3_unit_massless

330c <Interfaces of phase_space procedures 330c>≡
interface random_LIPS3
    module procedure random_LIPS3_unit, random_LIPS3_unit_massless
end interface

330d <Implementation of phase_space procedures 330d>≡
pure subroutine random_LIPS3_unit (rng, lips)
    type(tao_random_state), intent(inout) :: rng
    type(LIPS3_unit), intent(inout) :: lips
    call tao_random_number (rng, lips%x)
    lips%jacobian = 1
end subroutine random_LIPS3_unit

330e <Implementation of phase_space procedures 330d>+≡
pure subroutine random_LIPS3_unit_massless (rng, lips)
    type(tao_random_state), intent(inout) :: rng
    type(LIPS3_unit_massless), intent(inout) :: lips
    call tao_random_number (rng, lips%x)
    lips%jacobian = 1
end subroutine random_LIPS3_unit_massless

330f <Declaration of phase_space procedures 330b>+≡
private :: LIPS3_unit_to_s2_t1_angles, LIPS3_unit_to_s2_t1_angles_m0

330g <(Unused) Interfaces of phase_space procedures 330g>≡
interface assignment(=)
    module procedure &
        LIPS3_unit_to_s2_t1_angles, LIPS3_unit_to_s2_t1_angles_m0
end interface

```

331a *(Implementation of phase_space procedures 330d)*+≡

```
pure subroutine LIPS3_unit_to_s2_t1_angles (s2_t1_angles, unit)
    type(LIPS3_s2_t1_angles), intent(out) :: s2_t1_angles
    type(LIPS3_unit), intent(in) :: unit
end subroutine LIPS3_unit_to_s2_t1_angles
```

331b *(Implementation of phase_space procedures 330d)*+≡

```
pure subroutine LIPS3_unit_to_s2_t1_angles_m0 (s2_t1_angles, unit)
    type(LIPS3_s2_t1_angles_massless), intent(out) :: s2_t1_angles
    type(LIPS3_unit_massless), intent(in) :: unit
end subroutine LIPS3_unit_to_s2_t1_angles_m0
```

J.4 Massless n-Particle Phase Space: RAMBO

331c *(Declaration of kinematics procedures 323b)*+≡

```
public :: massless_isotropic_decay
```

The massless RAMBO algorithm [25]:

331d *(Implementation of kinematics procedures 324a)*+≡

```
pure function massless_isotropic_decay (roots, ran) result (p)
    real (kind=default), intent(in) :: roots
    real (kind=default), dimension(:, :, :), intent(in) :: ran
    real (kind=default), dimension(size(ran, dim=1), 0:3) :: p
    real (kind=default), dimension(size(ran, dim=1), 0:3) :: q
    real (kind=default), dimension(0:3) :: qsum
    real (kind=default) :: cos_theta, sin_theta, phi, qabs, x, r, z
    integer :: k
    <Generate isotropic null vectors 331e>
    <Boost and rescale the vectors 332a>
end function massless_isotropic_decay
```

Generate a xe^{-x} distribution for $q(k, 0)$

331e *(Generate isotropic null vectors 331e)*≡

```
do k = 1, size (p, dim = 1)
    q(k,0) = - log (ran(k,1) * ran(k,2))
    cos_theta = 2 * ran(k,3) - 1
    sin_theta = sqrt (1 - cos_theta**2)
    phi = 2 * PI * ran(k,4)
    q(k,1) = q(k,0) * sin_theta * cos (phi)
    q(k,2) = q(k,0) * sin_theta * sin (phi)
    q(k,3) = q(k,0) * cos_theta
enddo
```

The proof that the Jacobian of the transformation vanishes can be found in [25]. The transformation is really a Lorentz boost (as can be seen easily).

332a *(Boost and rescale the vectors 332a)* \equiv

```

qsum = sum (q, dim = 1)
qabs = sqrt (dot (qsum, qsum))
x = roots / qabs
do k = 1, size (p, dim = 1)
    r = dot (q(k,:), qsum) / qabs
    z = (q(k,0) + r) / (qsum(0) + qabs)
    p(k,1:3) = x * (q(k,1:3) - qsum(1:3) * z)
    p(k,0) = x * r
enddo

```

332b *(Declaration of kinematics procedures 323b)* \equiv

```
public :: phase_space_volume
```

$$V_n(s) = \frac{1}{8\pi} \frac{n-1}{(\Gamma(n))^2} \left(\frac{s}{16\pi^2} \right)^{n-2} \quad (\text{J.11})$$

332c *(Implementation of kinematics procedures 324a)* \equiv

```

pure function phase_space_volume (n, roots) result (volume)
    integer, intent(in) :: n
    real (kind=default), intent(in) :: roots
    real (kind=default) :: volume
    real (kind=default) :: nd
    nd = n
    volume = (nd - 1) / (8*PI * (gamma (nd))**2) * (roots / (4*PI))**(2*n-4)
end function phase_space_volume

```

J.5 Tests

332d *(ktest.f90 332d)* \equiv

```

program ktest
    use kinds
    use constants
    use products
    use kinematics
    use tao_random_numbers
    implicit none
    real(kind=default) :: &
        ma, mb, m1, m2, m3, s, t1, s2, phi, cos_theta3, phi3
    real(kind=default) :: t1_min, t1_max
    real(kind=default), dimension(5) :: r
    type(LIPS3) :: p

```

```

integer :: i
character(len=*), parameter :: fmt = "(A,4(1X,E12.5))"
ma = 1.0
mb = 1.0
m1 = 10.0
m2 = 20.0
m3 = 30.0
s = 100.0 ** 2
do i = 1, 10
    call tao_random_number (r)
    s2 = (r(1) * (sqrt (s) - m1) + (1 - r(1)) * (m2 + m3)) ** 2
    t1_max = ma**2 + m1**2 - ((s + ma**2 - mb**2) * (s - s2 + m1**2) &
        + sqrt (lambda (s, ma**2, mb**2) * lambda (s, s2, m1**2))) / (2*s)
    t1_min = ma**2 + m1**2 - ((s + ma**2 - mb**2) * (s - s2 + m1**2) &
        - sqrt (lambda (s, ma**2, mb**2) * lambda (s, s2, m1**2))) / (2*s)
    t1 = r(2) * t1_max + (1 - r(2)) * t1_min
    phi = 2*PI * r(3)
    cos_theta3 = 2 * r(4) - 1
    phi3 = 2*PI * r(5)
    p = two_to_three (s, t1, s2, phi, cos_theta3, phi3, ma, mb, m1, m2, m3)
    print fmt, "p1      = ", p%p(1,:)
    print fmt, "p2      = ", p%p(2,:)
    print fmt, "p3      = ", p%p(3,:)
    print fmt, "p1,2,3^2 = ", dot (p%p(1,:), p%p(1,:)), &
        dot (p%p(2,:), p%p(2,:)), dot (p%p(3,:), p%p(3,:))
    print fmt, "sum(p)   = ", p%p(1,:) + p%p(2,:) + p%p(3,:)
    print fmt, "|J|      = ", p%jacobian
end do
end program ktest

```

 Trivial check for typos, should be removed from the finalized program!

333 ⟨Trivial ktest.f90 333⟩≡

```

program ktest
    use kinds
    use constants
    use products
    use kinematics
    use tao_random_numbers
    implicit none
    real(kind=default), dimension(0:3) :: p, q, p_prime, p0
    real(kind=default) :: m
    character(len=*), parameter :: fmt = "(A,4(1X,E12.5))"
    integer :: i

```

```

do i = 1, 5
    if (i == 1) then
        p = (/ 1.0_double, 0.0_double, 0.0_double, 0.0_double /)
        m = 1.0
    else
        call tao_random_number (p)
        m = sqrt (PI)
    end if
    call tao_random_number (q(1:3))
    q(0) = sqrt (m**2 + dot_product (q(1:3), q(1:3)))
    p_prime = boost_momentum (p, q)
    print fmt, "p      = ", p
    print fmt, "q      = ", q
    print fmt, "p'     = ", p_prime
    print fmt, "p^2    = ", dot (p, p)
    print fmt, "p'^2   = ", dot (p_prime, p_prime)
    if (dot (p, p) > 0.0) then
        p0 = boost_momentum (p, p)
        print fmt, "p0     = ", p0
        print fmt, "p0^2   = ", dot (p0, p0)
    end if
end do
end program ktest

```

—K—

COORDINATES

```

335  <coordinates.f90 335>≡
      ! coordinates.f90 --
      <Copyleft notice 1>
      module coordinates
        use kinds
        use constants, only: PI
        use specfun, only: gamma
        implicit none
        private
        <Declaration of coordinates procedures 336a>
      contains
        <Implementation of coordinates procedures 336b>
      end module coordinates

```

K.1 Angular Spherical Coordinates

$$\begin{aligned}
 x_n &= r \cos \theta_{n-2} \\
 x_{n-1} &= r \sin \theta_{n-2} \cos \theta_{n-3} \\
 &\dots \\
 x_3 &= r \sin \theta_{n-2} \sin \theta_{n-3} \cdots \cos \theta_1 \\
 x_2 &= r \sin \theta_{n-2} \sin \theta_{n-3} \cdots \sin \theta_1 \cos \phi \\
 x_1 &= r \sin \theta_{n-2} \sin \theta_{n-3} \cdots \sin \theta_1 \sin \phi
 \end{aligned} \tag{K.1}$$

and

$$J = r^{n-1} \prod_{i=1}^{n-2} (\sin \theta_i)^i \tag{K.2}$$

We can minimize the number of multiplications by computing the products

$$P_j = \prod_{i=j}^{n-2} \sin \theta_i \quad (\text{K.3})$$

Then

$$\begin{aligned} x_n &= r \cos \theta_{n-2} \\ x_{n-1} &= r P_{n-2} \cos \theta_{n-3} \\ &\dots \\ x_3 &= r P_2 \cos \theta_1 \\ x_2 &= r P_1 \cos \phi \\ x_1 &= r P_1 \sin \phi \end{aligned} \quad (\text{K.4})$$

and

$$J = r^{n-1} \prod_{i=1}^{n-2} P_i \quad (\text{K.5})$$

Note that $\theta_i \in [0, \pi]$ and $\phi \in [0, 2\pi]$ or $\phi \in [-\pi, \pi]$. Therefore $\sin \theta_i \geq 0$ and

$$\sin \theta_i = \sqrt{1 - \cos^2 \theta_i} \quad (\text{K.6})$$

which is not true for ϕ . Since `sqrt` is typically much faster than `sin` and `cos`, we use (K.6) where ever possible.

336a *(Declaration of coordinates procedures 336a)*≡
`public :: spherical_to_cartesian_2, &`
`spherical_to_cartesian, spherical_to_cartesian_j`

336b *(Implementation of coordinates procedures 336b)*≡
`pure subroutine spherical_to_cartesian_2 (r, phi, theta, x, jacobian)`
`real(kind=default), intent(in) :: r, phi`
`real(kind=default), dimension(:), intent(in) :: theta`
`real(kind=default), dimension(:), intent(out), optional :: x`
`real(kind=default), intent(out), optional :: jacobian`
`real(kind=default), dimension(size(theta)) :: cos_theta`
`real(kind=default), dimension(size(theta)+1) :: product_sin_theta`
`integer :: n, i`
`n = size (theta) + 2`
`cos_theta = cos (theta)`
`product_sin_theta(n-1) = 1.0_default`
`do i = n - 2, 1, -1`
`product_sin_theta(i) = &`
`product_sin_theta(i+1) * sqrt (1 - cos_theta(i)**2)`
`end do`

```

if (present (x)) then
    x(1) = r * product_sin_theta(1) * sin (phi)
    x(2) = r * product_sin_theta(1) * cos (phi)
    x(3:) = r * product_sin_theta(2:n-1) * cos_theta
end if
if (present (jacobian)) then
    jacobian = r**n-1 * product (product_sin_theta)
end if
end subroutine spherical_to_cartesian_2

```

 Note that `call` inside of a function breaks F-compatibility. Here it would be easy to fix, but the inverse can not be coded as a function, unless a type for spherical coordinates is introduced, where `theta` could not be assumed shape ...

337a *(Implementation of coordinates procedures 336b)*+≡

```

pure function spherical_to_cartesian (r, phi, theta) result (x)
    real(kind=default), intent(in) :: r, phi
    real(kind=default), dimension(:), intent(in) :: theta
    real(kind=default), dimension(size(theta)+2) :: x
    call spherical_to_cartesian_2 (r, phi, theta, x = x)
end function spherical_to_cartesian

```

337b *(Implementation of coordinates procedures 336b)*+≡

```

pure function spherical_to_cartesian_j (r, phi, theta) &
    result (jacobian)
    real(kind=default), intent(in) :: r, phi
    real(kind=default), dimension(:), intent(in) :: theta
    real(kind=default) :: jacobian
    call spherical_to_cartesian_2 (r, phi, theta, jacobian = jacobian)
end function spherical_to_cartesian_j

```

337c *(Declaration of coordinates procedures 336a)*+≡

```

public :: cartesian_to_spherical_2, &
        cartesian_to_spherical, cartesian_to_spherical_j

```

337d *(Implementation of coordinates procedures 336b)*+≡

```

pure subroutine cartesian_to_spherical_2 (x, r, phi, theta, jacobian)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), intent(out), optional :: r, phi
    real(kind=default), dimension(:), intent(out), optional :: theta
    real(kind=default), intent(out), optional :: jacobian
    real(kind=default) :: local_r
    real(kind=default), dimension(size(x)-2) :: cos_theta
    real(kind=default), dimension(size(x)-1) :: product_sin_theta

```

```

integer :: n, i
n = size (x)
local_r = sqrt (dot_product (x, x))
if (local_r == 0) then
    if (present (r)) then
        r = 0
    end if
    if (present (phi)) then
        phi = 0
    end if
    if (present (theta)) then
        theta = 0
    end if
    if (present (jacobian)) then
        jacobian = 1
    end if
else
    product_sin_theta(n-1) = 1
do i = n, 3, -1
    if (product_sin_theta(i-1) == 0) then
        cos_theta(i-2) = 0
    else
        cos_theta(i-2) = x(i) / product_sin_theta(i-1) / local_r
    end if
    product_sin_theta(i-2) = &
        product_sin_theta(i-1) * sqrt (1 - cos_theta(i-2)**2)
end do
if (present (r)) then
    r = local_r
end if
if (present (phi)) then
    ! Set phi = 0 for vanishing vector
    if (x(1) == 0 .and. x(2)==0) then
        phi = 0
    else
        phi = atan2 (x(1), x(2))
    end if
end if
if (present (theta)) then
    theta = acos (cos_theta)
end if
if (present (jacobian)) then
    jacobian = local_r**(1-n) / product (product_sin_theta)

```

```

        end if
    end if
end subroutine cartesian_to_spherical_2
```

339a *(Implementation of coordinates procedures 336b)* +≡

```

pure subroutine cartesian_to_spherical (x, r, phi, theta)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), intent(out) :: r, phi
    real(kind=default), dimension(:), intent(out) :: theta
    call cartesian_to_spherical_2 (x, r, phi, theta)
end subroutine cartesian_to_spherical
```

339b *(Implementation of coordinates procedures 336b)* +≡

```

pure function cartesian_to_spherical_j (x) result (jacobian)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default) :: jacobian
    call cartesian_to_spherical_2 (x, jacobian = jacobian)
end function cartesian_to_spherical_j
```

K.2 Trigonometric Spherical Coordinates

339c *(Declaration of coordinates procedures 336a)* +≡

```

public :: spherical_cos_to_cartesian_2, &
         spherical_cos_to_cartesian, spherical_cos_to_cartesian_j
```

Using the cosine, we have to drop P_1 from the Jacobian

339d *(Implementation of coordinates procedures 336b)* +≡

```

pure subroutine spherical_cos_to_cartesian_2 (r, phi, cos_theta, x, jacobian)
    real(kind=default), intent(in) :: r, phi
    real(kind=default), dimension(:), intent(in) :: cos_theta
    real(kind=default), dimension(:), intent(out), optional :: x
    real(kind=default), intent(out), optional :: jacobian
    real(kind=default), dimension(size(cos_theta)+1) :: product_sin_theta
    integer :: n, i
    n = size (cos_theta) + 2
    product_sin_theta(n-1) = 1.0_default
    do i = n - 2, 1, -1
        product_sin_theta(i) = &
            product_sin_theta(i+1) * sqrt (1 - cos_theta(i)**2)
    end do
    if (present (x)) then
        x(1) = r * product_sin_theta(1) * sin (phi)
        x(2) = r * product_sin_theta(1) * cos (phi)
        x(3:) = r * product_sin_theta(2:n-1) * cos_theta
```

```

    end if
    if (present (jacobian)) then
        jacobian = r**(n-1) * product (product_sin_theta(2:))
    end if
end subroutine spherical_cos_to_cartesian_2

340a <Implementation of coordinates procedures 336b>+≡
pure function spherical_cos_to_cartesian (r, phi, theta) result (x)
    real(kind=default), intent(in) :: r, phi
    real(kind=default), dimension(:), intent(in) :: theta
    real(kind=default), dimension(size(theta)+2) :: x
    call spherical_cos_to_cartesian_2 (r, phi, theta, x = x)
end function spherical_cos_to_cartesian

340b <Implementation of coordinates procedures 336b>+≡
pure function spherical_cos_to_cartesian_j (r, phi, theta) &
    result (jacobian)
    real(kind=default), intent(in) :: r, phi
    real(kind=default), dimension(:), intent(in) :: theta
    real(kind=default) :: jacobian
    call spherical_cos_to_cartesian_2 (r, phi, theta, jacobian = jacobian)
end function spherical_cos_to_cartesian_j

340c <Declaration of coordinates procedures 336a>+≡
public :: cartesian_to_spherical_cos_2, &
    cartesian_to_spherical_cos, cartesian_to_spherical_cos_j

340d <Implementation of coordinates procedures 336b>+≡
pure subroutine cartesian_to_spherical_cos_2 (x, r, phi, cos_theta, jacobian)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), intent(out), optional :: r, phi
    real(kind=default), dimension(:), intent(out), optional :: cos_theta
    real(kind=default), intent(out), optional :: jacobian
    real(kind=default) :: local_r
    real(kind=default), dimension(size(x)-2) :: local_cos_theta
    real(kind=default), dimension(size(x)-1) :: product_sin_theta
    integer :: n, i
    n = size (x)
    local_r = sqrt (dot_product (x, x))
    if (local_r == 0) then
        if (present (r)) then
            r = 0
        end if
        if (present (phi)) then
            phi = 0
        end if

```

```

if (present (cos_theta)) then
    cos_theta = 0
end if
if (present (jacobian)) then
    jacobian = 1
end if
else
product_sin_theta(n-1) = 1
do i = n, 3, -1
    if (product_sin_theta(i-1) == 0) then
        local_cos_theta(i-2) = 0
    else
        local_cos_theta(i-2) = x(i) / product_sin_theta(i-1) / local_r
    end if
    product_sin_theta(i-2) = &
        product_sin_theta(i-1) * sqrt (1 - local_cos_theta(i-2)**2)
end do
if (present (r)) then
    r = local_r
end if
if (present (phi)) then
    ! Set phi = 0 for vanishing vector
    if (x(1) == 0 .and. x(2)==0) then
        phi = 0
    else
        phi = atan2 (x(1), x(2))
    end if
end if
if (present (cos_theta)) then
    cos_theta = local_cos_theta
end if
if (present (jacobian)) then
    jacobian = local_r**(1-n) / product (product_sin_theta(2:))
end if
end if
end subroutine cartesian_to_spherical_cos_2

```

341 <Implementation of coordinates procedures 336b>+≡

```

pure subroutine cartesian_to_spherical_cos (x, r, phi, cos_theta)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default), intent(out) :: r, phi
    real(kind=default), dimension(:), intent(out), optional :: cos_theta
    call cartesian_to_spherical_cos_2 (x, r, phi, cos_theta)
end subroutine cartesian_to_spherical_cos

```

342a *(Implementation of coordinates procedures 336b)*+≡

```
pure function cartesian_to_spherical_cos_j (x) result (jacobian)
    real(kind=default), dimension(:), intent(in) :: x
    real(kind=default) :: jacobian
    call cartesian_to_spherical_cos_2 (x, jacobian = jacobian)
end function cartesian_to_spherical_cos_j
```

K.3 Surface of a Sphere

342b *(Declaration of coordinates procedures 336a)*+≡

```
public :: surface
```

$$\int d\Omega_n = \frac{2\pi^{n/2}}{\Gamma(n/2)} = S_n \quad (\text{K.7})$$

342c *(Implementation of coordinates procedures 336b)*+≡

```
pure function surface (n) result (vol)
    integer, intent(in) :: n
    real(kind=default) :: vol
    real(kind=default) :: n_by_2
    n_by_2 = 0.5_default * n
    vol = 2 * PI**n_by_2 / gamma (n_by_2)
end function surface
```

—L—

IDIOMATIC FORTRAN90 INTERFACE FOR MPI

343a $\langle \text{mpi90.f90} \text{ 343a} \rangle \equiv$

```
! mpi90.f90 --
⟨Copyleft notice 1⟩
module mpi90
  use kinds
  use mpi
  implicit none
  private
  ⟨Declaration of mpi90 procedures 343b⟩
  ⟨Interfaces of mpi90 procedures 346c⟩
  ⟨Parameters in mpi90 (never defined)⟩
  ⟨Variables in mpi90 (never defined)⟩
  ⟨Declaration of mpi90 types 348b⟩
  character(len=*), public, parameter :: MPI90_RCS_ID = &
    "$Id: mpi90.nw 314 2010-04-17 20:32:33Z ohl $"
contains
  ⟨Implementation of mpi90 procedures 344a⟩
end module mpi90
```

L.1 Basics

343b $\langle \text{Declaration of mpi90 procedures 343b} \rangle \equiv$

```
public :: mpi90_init
public :: mpi90_finalize
public :: mpi90_abort
public :: mpi90_print_error
public :: mpi90_size
public :: mpi90_rank
```

```

344a <Implementation of mpi90 procedures 344a>≡
    subroutine mpi90_init (error)
        integer, intent(out), optional :: error
        integer :: local_error
        character(len=*), parameter :: FN = "mpi90_init"
        external mpi_init
        call mpi_init (local_error)
        <Handle local_error (no mpi90_abort) 344b>
    end subroutine mpi90_init

344b <Handle local_error (no mpi90_abort) 344b>≡
    if (present (error)) then
        error = local_error
    else
        if (local_error /= MPI_SUCCESS) then
            call mpi90_print_error (local_error, FN)
            stop
        end if
    end if

344c <Handle local_error 344c>≡
    if (present (error)) then
        error = local_error
    else
        if (local_error /= MPI_SUCCESS) then
            call mpi90_print_error (local_error, FN)
            call mpi90_abort (local_error)
            stop
        end if
    end if

344d <Implementation of mpi90 procedures 344a>+≡
    subroutine mpi90_finalize (error)
        integer, intent(out), optional :: error
        integer :: local_error
        character(len=*), parameter :: FN = "mpi90_finalize"
        external mpi_finalize
        call mpi_finalize (local_error)
        <Handle local_error 344c>
    end subroutine mpi90_finalize

344e <Implementation of mpi90 procedures 344a>+≡
    subroutine mpi90_abort (code, domain, error)
        integer, intent(in), optional :: code, domain
        integer, intent(out), optional :: error
        character(len=*), parameter :: FN = "mpi90_abort"

```

```

integer :: local_domain, local_code, local_error
external mpi_abort
if (present (code)) then
    local_code = code
else
    local_code = MPI_ERR_UNKNOWN
end if
<Set default for domain 345b>
call mpi_abort (local_domain, local_code, local_error)
<Handle local_error (no mpi90_abort) 344b>
end subroutine mpi90_abort

345a <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_print_error (error, msg)
    integer, intent(in) :: error
    character(len=*), optional :: msg
    character(len=*), parameter :: FN = "mpi90_print_error"
    integer :: msg_len, local_error
    external mpi_error_string
    call mpi_error_string (error, msg, msg_len, local_error)
    if (local_error /= MPI_SUCCESS) then
        print *, "PANIC: even MPI_ERROR_STRING() failed!!!"
        call mpi90_abort (local_error)
    else if (present (msg)) then
        print *, trim (msg), ": ", trim (msg(msg_len+1:))
    else
        print *, "mpi90: ", trim (msg(msg_len+1:))
    end if
end subroutine mpi90_print_error

345b <Set default for domain 345b>≡
if (present (domain)) then
    local_domain = domain
else
    local_domain = MPI_COMM_WORLD
end if

345c <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_size (sz, domain, error)
    integer, intent(out) :: sz
    integer, intent(in), optional :: domain
    integer, intent(out), optional :: error
    character(len=*), parameter :: FN = "mpi90_size"
    integer :: local_domain, local_error
    external mpi_comm_size

```

```

    <Set default for domain 345b>
    call mpi_comm_size (local_domain, sz, local_error)
    <Handle local_error 344c>
end subroutine mpi90_size

346a <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_rank (rank, domain, error)
    integer, intent(out) :: rank
    integer, intent(in), optional :: domain
    integer, intent(out), optional :: error
    character(len=*), parameter :: FN = "mpi90_rank"
    integer :: local_domain, local_error
    external mpi_comm_rank
    <Set default for domain 345b>
    call mpi_comm_rank (local_domain, rank, local_error)
    <Handle local_error 344c>
end subroutine mpi90_rank

```

L.2 Point to Point

```

346b <Declaration of mpi90 procedures 343b>+≡
public :: mpi90_send
public :: mpi90_receive
public :: mpi90_receive_pointer

346c <Interfaces of mpi90 procedures 346c>≡
interface mpi90_send
    module procedure &
        mpi90_send_integer, mpi90_send_double, &
        mpi90_send_integer_array, mpi90_send_double_array, &
        mpi90_send_integer_array2, mpi90_send_double_array2
    end interface

346d <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_send_integer (value, target, tag, domain, error)
    integer, intent(in) :: value
    integer, intent(in) :: target, tag
    integer, intent(in), optional :: domain
    integer, intent(out), optional :: error
    call mpi90_send_integer_array ((/ value /), target, tag, domain, error)
end subroutine mpi90_send_integer

346e <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_send_double (value, target, tag, domain, error)

```

```

real(kind=default), intent(in) :: value
integer, intent(in) :: target, tag
integer, intent(in), optional :: domain
integer, intent(out), optional :: error
call mpi90_send_double_array ((/ value /), target, tag, domain, error)
end subroutine mpi90_send_double

```

347a *(Implementation of mpi90 procedures 344a)*+≡

```

subroutine mpi90_send_integer_array (buffer, target, tag, domain, error)
    integer, dimension(:), intent(in) :: buffer
    integer, intent(in) :: target, tag
    integer, intent(in), optional :: domain
    integer, intent(out), optional :: error
    character(len=*), parameter :: FN = "mpi90_send_integer_array"
    integer, parameter :: datatype = MPI_INTEGER
    <Body of mpi90_send_*_array 347b>
end subroutine mpi90_send_integer_array

```

347b *(Body of mpi90_send_*_array 347b)*≡

```

integer :: local_domain, local_error
external mpi_send
<Set default for domain 345b>
call mpi_send (buffer, size (buffer), datatype, target, tag, &
               local_domain, local_error)
<Handle local_error 344c>

```

347c *(Implementation of mpi90 procedures 344a)*+≡

```

subroutine mpi90_send_double_array (buffer, target, tag, domain, error)
    real(kind=default), dimension(:), intent(in) :: buffer
    integer, intent(in) :: target, tag
    integer, intent(in), optional :: domain
    integer, intent(out), optional :: error
    character(len=*), parameter :: FN = "mpi90_send_double_array"
    integer, parameter :: datatype = MPI_DOUBLE_PRECISION
    <Body of mpi90_send_*_array 347b>
end subroutine mpi90_send_double_array

```

347d *(Implementation of mpi90 procedures 344a)*+≡

```

subroutine mpi90_send_integer_array2 (value, target, tag, domain, error)
    integer, dimension(:, :, ), intent(in) :: value
    integer, intent(in) :: target, tag
    integer, intent(in), optional :: domain
    integer, intent(out), optional :: error
    integer, dimension(size(value)) :: buffer
    buffer = reshape (value, shape(buffer))
    call mpi90_send_integer_array (buffer, target, tag, domain, error)

```

```

    end subroutine mpi90_send_integer_array2

348a <Implementation of mpi90 procedures 344a>+≡
    subroutine mpi90_send_double_array2 (value, target, tag, domain, error)
        real(kind=default), dimension(:,:), intent(in) :: value
        integer, intent(in) :: target, tag
        integer, intent(in), optional :: domain
        integer, intent(out), optional :: error
        real(kind=default), dimension(size(value)) :: buffer
        buffer = reshape (value, shape(buffer))
        call mpi90_send_double_array (buffer, target, tag, domain, error)
    end subroutine mpi90_send_double_array2

348b <Declaration of mpi90 types 348b>≡
    type, public :: mpi90_status
        integer :: count, source, tag, error
    end type mpi90_status

348c <Implementation of mpi90 procedures 344a>+≡
    subroutine mpi90_receive_integer (value, source, tag, domain, status, error)
        integer, intent(out) :: value
        integer, intent(in), optional :: source, tag, domain
        type(mpi90_status), intent(out), optional :: status
        integer, intent(out), optional :: error
        integer, dimension(1) :: buffer
        call mpi90_receive_integer_array (buffer, source, tag, domain, status, error)
        value = buffer(1)
    end subroutine mpi90_receive_integer

348d <Interfaces of mpi90 procedures 346c>+≡
    interface mpi90_receive
        module procedure &
            mpi90_receive_integer, mpi90_receive_double, &
            mpi90_receive_integer_array, mpi90_receive_double_array, &
            mpi90_receive_integer_array2, mpi90_receive_double_array2
    end interface

348e <Set defaults for source, tag and domain 348e>≡
    if (present (source)) then
        local_source = source
    else
        local_source = MPI_ANY_SOURCE
    end if
    if (present (tag)) then
        local_tag = tag
    else

```

```

        local_tag = MPI_ANY_TAG
    end if
    ⟨Set default for domain 345b⟩

349a ⟨Implementation of mpi90 procedures 344a⟩+≡
    subroutine mpi90_receive_double (value, source, tag, domain, status, error)
        real(kind=default), intent(out) :: value
        integer, intent(in), optional :: source, tag, domain
        type(MPI_Status), intent(out), optional :: status
        integer, intent(out), optional :: error
        real(kind=default), dimension(1) :: buffer
        call mpi90_receive_double_array (buffer, source, tag, domain, status, error)
        value = buffer(1)
    end subroutine mpi90_receive_double

349b ⟨Implementation of mpi90 procedures 344a⟩+≡
    subroutine mpi90_receive_integer_array &
        (buffer, source, tag, domain, status, error)
        integer, dimension(:), intent(out) :: buffer
        integer, intent(in), optional :: source, tag, domain
        type(MPI_Status), intent(out), optional :: status
        integer, intent(out), optional :: error
        character(len=*), parameter :: FN = "mpi90_receive_integer_array"
        integer, parameter :: datatype = MPI_INTEGER
        ⟨Body of mpi90_receive_*_array 349c⟩
    end subroutine mpi90_receive_integer_array

349c ⟨Body of mpi90_receive_*_array 349c⟩≡
    integer :: local_source, local_tag, local_domain, local_error
    integer, dimension(MPI_STATUS_SIZE) :: local_status
    external mpi_receive, mpi_get_count
    ⟨Set defaults for source, tag and domain 348e⟩
    call mpi_recv (buffer, size (buffer), datatype, local_source, local_tag, &
                  local_domain, local_status, local_error)
    ⟨Handle local_error 344c⟩
    if (present (status)) then
        call decode_status (status, local_status, datatype)
    end if

349d ⟨Declaration of mpi90 procedures 343b⟩+≡
    private :: decode_status

349e ⟨Implementation of mpi90 procedures 344a⟩+≡
    subroutine decode_status (status, mpi_status, datatype)

```

⌚ Can we ignore ierror???

```

type(MPI90_Status), intent(out) :: status
integer, dimension(:), intent(in) :: MPI_Status
integer, intent(in), optional :: datatype
integer :: ierror
if (present (datatype)) then
    call MPI_Get_Count (MPI_Status, datatype, status%count, ierror)
else
    status%count = 0
end if
status%source = MPI_Status(MPI_SOURCE)
status%tag = MPI_Status(MPI_TAG)
status%error = MPI_Status(MPI_ERROR)
end subroutine decode_Status

```

- 350a <Implementation of MPI90 procedures 344a>+≡
- ```

subroutine MPI90_Receive_Double_Array &
 (buffer, source, tag, domain, status, error)
real(kind=default), dimension(:), intent(out) :: buffer
integer, intent(in), optional :: source, tag, domain
type(MPI90_Status), intent(out), optional :: status
integer, intent(out), optional :: error
character(len=*), parameter :: FN = "MPI90_Receive_Double_Array"
integer, parameter :: datatype = MPI_DOUBLE_PRECISION
<Body of MPI90_Receive_*_Array 349c>
end subroutine MPI90_Receive_Double_Array

```
- 350b <Implementation of MPI90 procedures 344a>+≡
- ```

subroutine MPI90_Receive_Integer_Array2 &
    (value, source, tag, domain, status, error)
integer, dimension(:, :, ), intent(out) :: value
integer, intent(in), optional :: source, tag, domain
type(MPI90_Status), intent(out), optional :: status
integer, intent(out), optional :: error
integer, dimension(size(value)) :: buffer
call MPI90_Receive_Integer_Array &
    (buffer, source, tag, domain, status, error)
value = reshape (buffer, shape(value))
end subroutine MPI90_Receive_Integer_Array2

```
- 350c <Implementation of MPI90 procedures 344a>+≡
- ```

subroutine MPI90_Receive_Double_Array2 &
 (value, source, tag, domain, status, error)
real(kind=default), dimension(:, :,), intent(out) :: value
integer, intent(in), optional :: source, tag, domain
type(MPI90_Status), intent(out), optional :: status

```

```

integer, intent(out), optional :: error
real(kind=default), dimension(size(value)) :: buffer
call mpi90_receive_double_array &
 (buffer, source, tag, domain, status, error)
 value = reshape (buffer, shape(value))
end subroutine mpi90_receive_double_array2

351a <Interfaces of mpi90 procedures 346c>+≡
 interface mpi90_receive_pointer
 module procedure &
 mpi90_receive_integer_pointer, mpi90_receive_double_pointer
 end interface

351b <Implementation of mpi90 procedures 344a>+≡
 subroutine mpi90_receive_integer_pointer &
 (buffer, source, tag, domain, status, error)
 integer, dimension(:), pointer :: buffer
 integer, intent(in), optional :: source, tag, domain
 type(mpi90_status), intent(out), optional :: status
 integer, intent(out), optional :: error
 character(len=*), parameter :: FN = "mpi90_receive_integer_pointer"
 integer, parameter :: datatype = MPI_INTEGER
 <Body of mpi90_receive_*_pointer 351c>
 end subroutine mpi90_receive_integer_pointer

351c <Body of mpi90_receive_*_pointer 351c>≡
 integer :: local_source, local_tag, local_domain, local_error, buffer_size
 integer, dimension(MPI_STATUS_SIZE) :: local_status
 integer :: ierror
 external mpi_receive, mpi_get_count
 <Set defaults for source, tag and domain 348e>

351d <Body of mpi90_receive_*_pointer 351c>+≡
 call mpi_probe (local_source, local_tag, local_domain, &
 local_status, local_error)
 <Handle local_error 344c>

⌚ Can we ignore ierror???
351e <Body of mpi90_receive_*_pointer 351c>+≡
 call mpi_get_count (local_status, datatype, buffer_size, ierror)
 if (associated (buffer)) then
 if (size (buffer) /= buffer_size) then
 deallocate (buffer)
 allocate (buffer(buffer_size))
 end if

```

```

 else
 allocate (buffer(buffer_size))
 end if

352a <Body of mpi90_receive_*_pointer 351c>+≡
 call mpi_recv (buffer, size (buffer), datatype, local_source, local_tag, &
 local_domain, local_status, local_error)

352b <Body of mpi90_receive_*_pointer 351c>+≡
 <Handle local_error 344c>
 if (present (status)) then
 call decode_status (status, local_status, datatype)
 end if

352c <Implementation of mpi90 procedures 344a>+≡
 subroutine mpi90_receive_double_pointer &
 (buffer, source, tag, domain, status, error)
 real(kind=default), dimension(:), pointer :: buffer
 integer, intent(in), optional :: source, tag, domain
 type(mpi90_status), intent(out), optional :: status
 integer, intent(out), optional :: error
 character(len=*), parameter :: FN = "mpi90_receive_double_pointer"
 integer, parameter :: datatype = MPI_DOUBLE_PRECISION
 <Body of mpi90_receive_*_pointer 351c>
 end subroutine mpi90_receive_double_pointer

```

### L.3 Collective Communication

```

352d <Declaration of mpi90 procedures 343b>+≡
 public :: mpi90_broadcast

352e <Interfaces of mpi90 procedures 346c>+≡
 interface mpi90_broadcast
 module procedure &
 mpi90_broadcast_integer, mpi90_broadcast_integer_array, &
 mpi90_broadcast_integer_array2, mpi90_broadcast_integer_array3, &
 mpi90_broadcast_double, mpi90_broadcast_double_array, &
 mpi90_broadcast_double_array2, mpi90_broadcast_double_array3, &
 mpi90_broadcast_logical, mpi90_broadcast_logical_array, &
 mpi90_broadcast_logical_array2, mpi90_broadcast_logical_array3
 end interface

352f <Set default for domain 345b>+≡
 if (present (domain)) then
 local_domain = domain

```

```

else
 local_domain = MPI_COMM_WORLD
end if

353a <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_broadcast_integer (value, root, domain, error)
 integer, intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 integer, dimension(1) :: buffer
 buffer(1) = value
 call mpi90_broadcast_integer_array (buffer, root, domain, error)
 value = buffer(1)
end subroutine mpi90_broadcast_integer

353b <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_broadcast_double (value, root, domain, error)
 real(kind=default), intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 real(kind=default), dimension(1) :: buffer
 buffer(1) = value
 call mpi90_broadcast_double_array (buffer, root, domain, error)
 value = buffer(1)
end subroutine mpi90_broadcast_double

353c <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_broadcast_logical (value, root, domain, error)
 logical, intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 logical, dimension(1) :: buffer
 buffer(1) = value
 call mpi90_broadcast_logical_array (buffer, root, domain, error)
 value = buffer(1)
end subroutine mpi90_broadcast_logical

353d <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_broadcast_integer_array (buffer, root, domain, error)
 integer, dimension(:), intent(inout) :: buffer
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error

```

```

character(len=*) , parameter :: FN = "mpi90_broadcast_integer_array"
integer, parameter :: datatype = MPI_INTEGER
<Body of mpi90_broadcast_*_array 354a>
end subroutine mpi90_broadcast_integer_array

354a <Body of mpi90_broadcast_*_array 354a>≡
integer :: local_domain, local_error
external mpi_bcast
<Set default for domain 345b>
call mpi_bcast (buffer, size (buffer), datatype, root, &
 local_domain, local_error)
<Handle local_error 344c>

354b <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_broadcast_double_array (buffer, root, domain, error)
 real(kind=default), dimension(:), intent(inout) :: buffer
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 integer, parameter :: datatype = MPI_DOUBLE_PRECISION
 character(len=*) , parameter :: FN = "mpi90_broadcast_double_array"
 <Body of mpi90_broadcast_*_array 354a>
end subroutine mpi90_broadcast_double_array

354c <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_broadcast_logical_array (buffer, root, domain, error)
 logical, dimension(:), intent(inout) :: buffer
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 integer, parameter :: datatype = MPI_LOGICAL
 character(len=*) , parameter :: FN = "mpi90_broadcast_logical_array"
 <Body of mpi90_broadcast_*_array 354a>
end subroutine mpi90_broadcast_logical_array

354d <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_broadcast_integer_array2 (value, root, domain, error)
 integer, dimension(:, :,), intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 integer, dimension(size(value)) :: buffer
 buffer = reshape (value, shape(buffer))
 call mpi90_broadcast_integer_array (buffer, root, domain, error)
 value = reshape (buffer, shape(value))
end subroutine mpi90_broadcast_integer_array2

```

355a *(Implementation of mpi90 procedures 344a)*+≡

```

subroutine mpi90_broadcast_double_array2 (value, root, domain, error)
 real(kind=default), dimension(:,:), intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 real(kind=default), dimension(size(value)) :: buffer
 buffer = reshape (value, shape(buffer))
 call mpi90_broadcast_double_array (buffer, root, domain, error)
 value = reshape (buffer, shape(value))
end subroutine mpi90_broadcast_double_array2
```

355b *(Implementation of mpi90 procedures 344a)*+≡

```

subroutine mpi90_broadcast_logical_array2 (value, root, domain, error)
 logical, dimension(:,:), intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 logical, dimension(size(value)) :: buffer
 buffer = reshape (value, shape(buffer))
 call mpi90_broadcast_logical_array (buffer, root, domain, error)
 value = reshape (buffer, shape(value))
end subroutine mpi90_broadcast_logical_array2
```

355c *(Implementation of mpi90 procedures 344a)*+≡

```

subroutine mpi90_broadcast_integer_array3 (value, root, domain, error)
 integer, dimension(:,:,:), intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 integer, dimension(size(value)) :: buffer
 buffer = reshape (value, shape(buffer))
 call mpi90_broadcast_integer_array (buffer, root, domain, error)
 value = reshape (buffer, shape(value))
end subroutine mpi90_broadcast_integer_array3
```

355d *(Implementation of mpi90 procedures 344a)*+≡

```

subroutine mpi90_broadcast_double_array3 (value, root, domain, error)
 real(kind=default), dimension(:,:,:), intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 real(kind=default), dimension(size(value)) :: buffer
 buffer = reshape (value, shape(buffer))
 call mpi90_broadcast_double_array (buffer, root, domain, error)
```

```
 value = reshape (buffer, shape(value))
end subroutine mpi90_broadcast_double_array3

356 <Implementation of mpi90 procedures 344a>+≡
subroutine mpi90_broadcast_logical_array3 (value, root, domain, error)
 logical, dimension(:,:,:,:), intent(inout) :: value
 integer, intent(in) :: root
 integer, intent(in), optional :: domain
 integer, intent(out), optional :: error
 logical, dimension(size(value)) :: buffer
 buffer = reshape (value, shape(buffer))
 call mpi90_broadcast_logical_array (buffer, root, domain, error)
 value = reshape (buffer, shape(value))
end subroutine mpi90_broadcast_logical_array3
```

# —M—

## POOR MAN'S ELEMENTAL PROCEDURES

On one hand, I want to take advantage of Fortran95's improvements, but on the other hand, I want to continue to use F as a style guide and also allow people with Fortran90 compilers to use the library.

### *M.1 m4 Macros*

```
357a <f95.m4 357a>≡
 dnl f95.m4 --
 divert(-1)dnl
 <Kill m4(1) builtins 357b>
 define('_specific_sv','dnl')
 define('_interface_sv','dnl')
 define('_specific_sva','dnl')
 define('_interface_sva','dnl')
 define('_begin_f90','divert(-1)dnl')
 define('_end_f90','divert''dnl')
 divert''dnl

357b <Kill m4(1) builtins 357b>≡
 undefine('eval')

357c <f90.m4 357c>≡
 dnl f90.m4 --
 divert(-1)dnl
 <Kill m4(1) builtins 357b>
 define('pure','')
 define('elemental','')
 define('_specific_sv','private :: $1_s, $1_v')
 define('_interface_sv','interface $1
 module procedure $1_s, $1_v
 end interface''define($1,$1_s)')
 define('_specific_sva','private :: $1_s, $1_v, $1_a')
```

```

define('_interface_sva','interface $1
 module procedure $1_s, $1_v, $1_a
 end interface')define($1,$1_s)')
define('_begin_f90','dnl')
define('_end_f90','dnl')
divert' dnl

```

## M.2 Miscellaneous Utilities

- 358a *<Implementation of utils procedures 304c>+≡*  
`_begin_f90`
- 358b *<Declaration of utils procedures 303b>+≡*  
`_begin_f90`  
`private :: swap_integer_array, swap_real_array`  
`_end_f90`
- 358c *<Interfaces of utils procedures 303c>+≡*  
`_begin_f90`  
`interface swap`  
 `module procedure swap_integer_array, swap_real_array`  
`end interface`  
`_end_f90`
- 358d *<Implementation of utils procedures 304c>+≡*  
`pure subroutine swap_integer_array (a, b)`  
 `integer, dimension(:), intent(inout) :: a, b`  
 `integer, dimension(max(size(a),size(b))) :: tmp`  
 `tmp = a`  
 `a = b`  
 `b = tmp`  
`end subroutine swap_integer_array`
- 358e *<Implementation of utils procedures 304c>+≡*  
`pure subroutine swap_real_array (a, b)`  
 `real(kind=default), dimension(:), intent(inout) :: a, b`  
 `real(kind=default), dimension(max(size(a),size(b))) :: tmp`  
 `tmp = a`  
 `a = b`  
 `b = tmp`  
`end subroutine swap_real_array`
- 358f *<Declaration of utils procedures 303b>+≡*  
`_specific_sva(gcd)`  
`_specific_sva(lcm)`

359a *<Interfaces of utils procedures 303c>+≡*  
 $_interface\_sva(gcd)$   
 $_interface\_sva(lcm)$

359b *<Implementation of utils procedures 304c>+≡*  
 pure function gcd\_v (m, n) result (gcd\_m\_n)  
 integer, dimension(:,), intent(in) :: m, n  
 integer, dimension(size(m)) :: gcd\_m\_n  
 integer :: i  
 do i = 1, size (m)  
 gcd\_m\_n(i) = gcd (m(i), n(i))  
 end do  
 end function gcd\_v

359c *<Implementation of utils procedures 304c>+≡*  
 pure function lcm\_v (m, n) result (lcm\_m\_n)  
 integer, dimension(:,), intent(in) :: m, n  
 integer, dimension(size(m)) :: lcm\_m\_n  
 integer :: i  
 do i = 1, size (m)  
 lcm\_m\_n(i) = lcm (m(i), n(i))  
 end do  
 end function lcm\_v

This abuses the  $_a$  suffix, which is used elsewhere for two-dimensional arrays:

359d *<Implementation of utils procedures 304c>+≡*  
 pure function gcd\_a (m, n) result (gcd\_m\_n)  
 integer, dimension(:,), intent(in) :: m  
 integer, intent(in) :: n  
 integer, dimension(size(m)) :: gcd\_m\_n  
 integer :: i  
 do i = 1, size (m)  
 gcd\_m\_n(i) = gcd (m(i), n)  
 end do  
 end function gcd\_a

359e *<Implementation of utils procedures 304c>+≡*  
 pure function lcm\_a (m, n) result (lcm\_m\_n)  
 integer, dimension(:,), intent(in) :: m  
 integer, intent(in) :: n  
 integer, dimension(size(m)) :: lcm\_m\_n  
 integer :: i  
 do i = 1, size (m)  
 lcm\_m\_n(i) = lcm (m(i), n)  
 end do  
 end function lcm\_a

360a  $\langle$ Implementation of utils procedures 304c $\rangle + \equiv$   
\_end\_f90

### M.3 Errors and Exceptions

360b  $\langle$ Implementation of exceptions procedures 246c $\rangle + \equiv$   
\_begin\_f90

360c  $\langle$ Declaration of exceptions procedures 246b $\rangle + \equiv$   
\_specific\_sv(raise\_exception)  
\_specific\_sv(clear\_exception)

360d  $\langle$ Interfaces of exceptions procedures 360d $\rangle \equiv$   
\_interface\_sv(raise\_exception)  
\_interface\_sv(clear\_exception)

360e  $\langle$ Implementation of exceptions procedures 246c $\rangle + \equiv$   
pure subroutine raise\_exception\_v (exc, level, message, origin)  
  type(exception), dimension(:), intent(inout) :: exc  
  integer, dimension(:), intent(in) :: level  
  character(len=\*), dimension(:), intent(in), optional :: message, origin  
  integer :: i  
  do i = 1, size (exc)  
    call raise\_exception (exc(i), level(i), message(i), origin(i))  
  end do  
end subroutine raise\_exception\_v

360f  $\langle$ Implementation of exceptions procedures 246c $\rangle + \equiv$   
pure subroutine clear\_exception\_v (exc)  
  type(exception), dimension(:), intent(inout) :: exc  
  integer :: i  
  do i = 1, size (exc)  
    call clear\_exception (exc(i))  
  end do  
end subroutine clear\_exception\_v

360g  $\langle$ Implementation of exceptions procedures 246c $\rangle + \equiv$   
\_end\_f90

### M.4 The Abstract Datatype *division*

360h  $\langle$ Implementation of divisions procedures 38b $\rangle + \equiv$   
\_begin\_f90

- 361a *(Declaration of divisions procedures 38a)* +≡  
  \_specific\_sv(create\_division)  
  \_specific\_sv(create\_empty\_division)  
  \_specific\_sva(copy\_division)  
  \_specific\_sv(set\_rigid\_division)  
  \_specific\_sv(reshape\_division)  
  \_specific\_sv(delete\_division)
- 361b *(Interfaces of divisions procedures 61b)* +≡  
  \_interface\_sv(create\_division)  
  \_interface\_sv(create\_empty\_division)  
  \_interface\_sva(copy\_division)  
  \_interface\_sv(set\_rigid\_division)  
  \_interface\_sv(reshape\_division)  
  \_interface\_sv(delete\_division)
- 361c *(Implementation of divisions procedures 38b)* +≡  
  pure subroutine create\_division\_v (d, x\_min, x\_max, x\_min\_true, x\_max\_true)  
    type/division\_t, dimension(:), intent(out) :: d  
    real(kind=default), dimension(:), intent(in) :: x\_min, x\_max  
    real(kind=default), dimension(:), intent(in), optional :: &  
      x\_min\_true, x\_max\_true  
    integer :: j  
    do j = 1, size(d)  
      if (present(x\_min\_true).and.present(x\_max\_true)) then  
        call create\_division &  
          (d(j), x\_min(j), x\_max(j), x\_min\_true(j), x\_max\_true(j))  
      else  
        call create\_division (d(j), x\_min(j), x\_max(j))  
      end if  
    end do  
  end subroutine create\_division\_v
- 361d *(Implementation of divisions procedures 38b)* +≡  
  pure subroutine create\_empty\_division\_v (d)  
    type/division\_t, dimension(:), intent(out) :: d  
    integer :: j  
    do j = 1, size(d)  
      call create\_empty\_division (d(j))  
    end do  
  end subroutine create\_empty\_division\_v
- 361e *(Implementation of divisions procedures 38b)* +≡  
  pure subroutine copy\_division\_v (lhs, rhs)  
    type/division\_t, dimension(:), intent(inout) :: lhs  
    type/division\_t, dimension(:), intent(in) :: rhs

```

integer :: j
do j = 1, size(lhs)
 call copy_division (lhs(j), rhs(j))
end do
end subroutine copy_division_v

```

This abuses the \_a suffix, which is used elsewhere for two-dimensional arrays:

- 362a *<Implementation of divisions procedures 38b>+≡*
- ```

pure subroutine copy_division_a (lhs, rhs)
    type(division_t), dimension(:), intent(inout) :: lhs
    type(division_t), intent(in) :: rhs
    integer :: j
    do j = 1, size(lhs)
        call copy_division (lhs(j), rhs)
    end do
end subroutine copy_division_a

```
- 362b *<Implementation of divisions procedures 38b>+≡*
- ```

pure subroutine set_rigid_division_v (d, ng)
 type(division_t), dimension(:), intent(inout) :: d
 integer, dimension(:), intent(in) :: ng
 integer :: j
 do j = 1, size(d)
 call set_rigid_division (d(j), ng(j))
 end do
end subroutine set_rigid_division_v

```
- 362c *<Implementation of divisions procedures 38b>+≡*
- ```

pure subroutine reshape_division_v (d, max_num_div, ng, use_variance)
    type(division_t), dimension(:), intent(inout) :: d
    integer, dimension(:), intent(in) :: max_num_div
    integer, dimension(:), intent(in), optional :: ng
    logical, intent(in), optional :: use_variance
    integer :: j
    do j = 1, size(d)
        call reshape_division (d(j), max_num_div(j), ng(j), use_variance)
    end do
end subroutine reshape_division_v

```
- 362d *<Implementation of divisions procedures 38b>+≡*
- ```

pure subroutine delete_division_v (d)
 type(division_t), dimension(:), intent(inout) :: d
 integer :: j
 do j = 1, size(d)
 call delete_division (d(j))
 end do

```

```

 end subroutine delete_division_v

363a <Declaration of divisions procedures 38a>+≡
 _specific_sv(inject_division)
 _specific_sv(inject_division_short)

363b <Interfaces of divisions procedures 61b>+≡
 _interface_sv(inject_division)
 _interface_sv(inject_division_short)

363c <Implementation of divisions procedures 38b>+≡
 pure subroutine inject_division_v (d, r, cell, x, x_mid, idx, wgt)
 type(division_t), dimension(:), intent(in) :: d
 real(kind=default), dimension(:), intent(in) :: r
 integer, dimension(:), intent(in) :: cell
 real(kind=default), dimension(:), intent(out) :: x, x_mid
 integer, dimension(:), intent(out) :: idx
 real(kind=default), dimension(:), intent(out) :: wgt
 integer :: j
 do j = 1, size (d)
 call inject_division (d(j), r(j), cell(j), x(j), &
 x_mid(j), idx(j), wgt(j))
 end do
 end subroutine inject_division_v

363d <Implementation of divisions procedures 38b>+≡
 pure subroutine inject_division_short_v (d, r, x, idx, wgt)
 type(division_t), dimension(:), intent(in) :: d
 real(kind=default), dimension(:), intent(in) :: r
 real(kind=default), dimension(:), intent(out) :: x
 integer, dimension(:), intent(out) :: idx
 real(kind=default), dimension(:), intent(out) :: wgt
 integer :: j
 do j = 1, size (d)
 call inject_division_short (d(j), r(j), x(j), idx(j), wgt(j))
 end do
 end subroutine inject_division_short_v

363e <Declaration of divisions procedures 38a>+≡
 _specific_sv(record_integral)
 _specific_sv(record_variance)
 _specific_sv(clear_integral_and_variance)

363f <Declaration of divisions procedures (removed from WHIZARD) 60c>+≡
 _specific_sv(record_efficiency)

```

364a *<Interfaces of divisions procedures 61b>+≡*  
 $_interface\_sv(record\_integral)$   
 $_interface\_sv(record\_variance)$   
 $_interface\_sv(clear\_integral\_and\_variance)$

364b *<Interfaces of divisions procedures (removed from WHIZARD) 364b>≡*  
 $_interface\_sv(record\_efficiency)$

364c *<Implementation of divisions procedures 38b>+≡*  
 $pure subroutine record\_integral\_v (d, i, f)$   
 $type(division_t), dimension(:), intent(inout) :: d$   
 $integer, dimension(:), intent(in) :: i$   
 $real(kind=default), intent(in) :: f$   
 $integer :: j$   
 $do j = 1, size (d)$   
 $call record\_integral (d(j), i(j), f)$   
 $end do$   
 $end subroutine record\_integral\_v$

364d *<Implementation of divisions procedures 38b>+≡*  
 $pure subroutine record\_variance\_v (d, i, var_f)$   
 $type(division_t), dimension(:), intent(inout) :: d$   
 $integer, dimension(:), intent(in) :: i$   
 $real(kind=default), intent(in) :: var_f$   
 $integer :: j$   
 $do j = 1, size (d)$   
 $call record\_variance (d(j), i(j), var_f)$   
 $end do$   
 $end subroutine record\_variance\_v$

364e *<Implementation of divisions procedures (removed from WHIZARD) 45b>+≡*  
 $pure subroutine record\_efficiency\_v (d, i, eff_f)$   
 $type(division_t), dimension(:), intent(inout) :: d$   
 $integer, dimension(:), intent(in) :: i$   
 $real(kind=default), intent(in) :: eff_f$   
 $integer :: j$   
 $do j = 1, size (d)$   
 $call record\_efficiency (d(j), i(j), eff_f)$   
 $end do$   
 $end subroutine record\_efficiency\_v$

364f *<Implementation of divisions procedures 38b>+≡*  
 $pure subroutine clear\_integral\_and\_variance\_v (d)$   
 $type(division_t), dimension(:), intent(inout) :: d$   
 $integer :: j$   
 $do j = 1, size (d)$

```

 call clear_integral_and_variance (d(j))
 end do
end subroutine clear_integral_and_variance_v

365a <Declaration of divisions procedures 38a>+≡
 _specific_sv(refine_division)

365b <Interfaces of divisions procedures 61b>+≡
 _interface_sv(refine_division)

365c <Implementation of divisions procedures 38b>+≡
pure subroutine refine_division_v (d)
 type(dimension_t), dimension(:), intent(inout) :: d
 integer :: j
 do j = 1, size (d)
 call refine_division (d(j))
 end do
end subroutine refine_division_v

365d <Declaration of divisions procedures 38a>+≡
 _specific_sv(probability)
 _specific_sv(inside_division)
 _specific_sv(stratified_division)
 _specific_sv(volume_division)
 _specific_sv(rigid_division)
 _specific_sv(adaptive_division)
 _specific_sv(quadrupole_division)

365e <Interfaces of divisions procedures 61b>+≡
 _interface_sv(probability)
 _interface_sv(inside_division)
 _interface_sv(stratified_division)
 _interface_sv(volume_division)
 _interface_sv(rigid_division)
 _interface_sv(adaptive_division)
 _interface_sv(quadrupole_division)

365f <Implementation of divisions procedures 38b>+≡
pure function probability_v (d, xi) result (p)
 type(dimension_t), dimension(:), intent(in) :: d
 real(kind=default), dimension(:), intent(in) :: xi
 real(kind=default), dimension(size(d)) :: p
 integer :: j
 do j = 1, size (d)
 p(j) = probability (d(j), xi(j))
 end do
end function probability_v

```

366a *(Implementation of divisions procedures 38b)* +≡

```

pure function inside_division_v (d, x) result (theta)
 type(division_t), dimension(:), intent(in) :: d
 real(kind=default), dimension(:), intent(in) :: x
 logical, dimension(size(d)) :: theta
 integer :: j
 do j = 1, size (d)
 theta(j) = inside_division (d(j), x(j))
 end do
end function inside_division_v
```

366b *(Implementation of divisions procedures 38b)* +≡

```

pure function stratified_division_v (d) result (yorn)
 type(division_t), dimension(:), intent(in) :: d
 logical, dimension(size(d)) :: yorn
 integer :: j
 do j = 1, size (d)
 yorn(j) = stratified_division (d(j))
 end do
end function stratified_division_v
```

366c *(Implementation of divisions procedures 38b)* +≡

```

pure function volume_division_v (d) result (vol)
 type(division_t), dimension(:), intent(in) :: d
 real(kind=default), dimension(size(d)) :: vol
 integer :: j
 do j = 1, size(d)
 vol(j) = volume_division (d(j))
 end do
end function volume_division_v
```

366d *(Implementation of divisions procedures 38b)* +≡

```

pure function rigid_division_v (d) result (n)
 type(division_t), dimension(:), intent(in) :: d
 integer, dimension(size(d)) :: n
 integer :: j
 do j = 1, size(d)
 n(j) = rigid_division (d(j))
 end do
end function rigid_division_v
```

366e *(Implementation of divisions procedures 38b)* +≡

```

pure function adaptive_division_v (d) result (n)
 type(division_t), dimension(:), intent(in) :: d
 integer, dimension(size(d)) :: n
 integer :: j
```

```

 do j = 1, size(d)
 n(j) = adaptive_division (d(j))
 end do
 end function adaptive_division_v

367a <Implementation of divisions procedures 38b>+≡
 pure function quadrupole_division_v (d) result (q)
 type(division_t), dimension(:), intent(in) :: d
 real(kind=default), dimension(size(d)) :: q
 integer :: j
 do j = 1, size (d)
 q(j) = quadrupole_division (d(j))
 end do
 end function quadrupole_division_v

367b <Declaration of divisions procedures 38a>+≡
 _specific_sv(copy_history)
 _specific_sv(summarize_division)

367c <Interfaces of divisions procedures 61b>+≡
 _interface_sv(copy_history)
 _interface_sv(summarize_division)

367d <Implementation of divisions procedures 38b>+≡
 pure subroutine copy_history_v (lhs, rhs)
 type(div_history), dimension(:), intent(inout) :: lhs
 type(div_history), dimension(:), intent(in) :: rhs
 integer :: j
 do j = 1, size (rhs)
 call copy_history (lhs(j), rhs(j))
 end do
 end subroutine copy_history_v

367e <Implementation of divisions procedures 38b>+≡
 pure function summarize_division_v (d) result (s)
 type(division_t), dimension(:), intent(in) :: d
 type(div_history), dimension(size(d)) :: s
 integer :: j
 do j = 1, size (d)
 s(j) = summarize_division (d(j))
 end do
 end function summarize_division_v

367f <Implementation of divisions procedures 38b>+≡
 _end_f90

```

## M.5 The Abstract Datatype *vamp\_grid*

```

368a <Implementation of vamp procedures 77c>+≡
 _begin_f90

368b <Declaration of vamp procedures 77a>+≡
 _specific_sv(vamp_create_empty_grid)
 _specific_sv(vamp_nullify_covariance)
 _specific_sv(vamp_get_variance)
 _specific_sv(vamp_nullify_variance)

368c <Interfaces of vamp procedures 94c>+≡
 _interface_sv(vamp_create_empty_grid)
 _interface_sv(vamp_nullify_covariance)
 _interface_sv(vamp_get_variance)
 _interface_sv(vamp_nullify_variance)

368d <Implementation of vamp procedures 77c>+≡
 pure subroutine vamp_create_empty_grid_v (g)
 type(vamp_grid), dimension(:), intent(inout) :: g
 integer :: i
 do i = 1, size (g)
 call vamp_create_empty_grid (g(i))
 end do
 end subroutine vamp_create_empty_grid_v

368e <Implementation of vamp procedures 77c>+≡
 pure subroutine vamp_nullify_covariance_v (g)
 type(vamp_grid), dimension(:), intent(inout) :: g
 integer :: i
 do i = 1, size (g)
 call vamp_nullify_covariance (g(i))
 end do
 end subroutine vamp_nullify_covariance_v

368f <Implementation of vamp procedures 77c>+≡
 pure function vamp_get_variance_v (g) result (v)
 type(vamp_grid), dimension(:), intent(in) :: g
 real(kind=default), dimension(size(g)) :: v
 integer :: i
 do i = 1, size (g)
 v(i) = vamp_get_variance (g(i))
 end do
 end function vamp_get_variance_v

```

369a *<Implementation of vamp procedures 77c>+≡*  
 pure subroutine vamp\_nullify\_variance\_v (g)  
   type(vamp\_grid), dimension(:), intent(inout) :: g  
   integer :: i  
   do i = 1, size (g)  
     call vamp\_nullify\_variance (g(i))  
   end do  
 end subroutine vamp\_nullify\_variance\_v

369b *<Declaration of vamp procedures 77a>+≡*  
 \_specific\_sv(vamp\_copy\_grid)  
 \_specific\_sv(vamp\_delete\_grid)

369c *<Interfaces of vamp procedures 94c>+≡*  
 \_interface\_sv(vamp\_copy\_grid)  
 \_interface\_sv(vamp\_delete\_grid)

369d *<Implementation of vamp procedures 77c>+≡*  
 pure subroutine vamp\_copy\_grid\_v (lhs, rhs)  
   type(vamp\_grid), dimension(:), intent(inout) :: lhs  
   type(vamp\_grid), dimension(:), intent(in) :: rhs  
   integer :: i  
   do i = 1, size (lhs)  
     call vamp\_copy\_grid (lhs(i), rhs(i))  
   end do  
 end subroutine vamp\_copy\_grid\_v

369e *<Implementation of vamp procedures 77c>+≡*  
 pure subroutine vamp\_delete\_grid\_v (g)  
   type(vamp\_grid), dimension(:), intent(inout) :: g  
   integer :: i  
   do i = 1, size (g)  
     call vamp\_delete\_grid (g(i))  
   end do  
 end subroutine vamp\_delete\_grid\_v

369f *<Declaration of vamp procedures 77a>+≡*  
 \_specific\_sv(vamp\_copy\_grids)  
 \_specific\_sv(vamp\_delete\_grids)

369g *<Interfaces of vamp procedures 94c>+≡*  
 \_interface\_sv(vamp\_copy\_grids)  
 \_interface\_sv(vamp\_delete\_grids)

369h *<Implementation of vamp procedures 77c>+≡*  
 pure subroutine vamp\_copy\_grids\_v (lhs, rhs)  
   type(vamp\_grids), dimension(:), intent(inout) :: lhs

```

 type(vamp_grids), dimension(:), intent(in) :: rhs
 integer :: i
 do i = 1, size (lhs)
 call vamp_copy_grids (lhs(i), rhs(i))
 end do
end subroutine vamp_copy_grids_v

370a <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_delete_grids_v (g)
 type(vamp_grids), dimension(:), intent(inout) :: g
 integer :: i
 do i = 1, size (g)
 call vamp_delete_grids (g(i))
 end do
end subroutine vamp_delete_grids_v

370b <Declaration of vamp procedures 77a>+≡
_specific_sva(vamp_create_history)
_specific_sv(vamp_terminate_history)
_specific_sva(vamp_copy_history)
_specific_sva(vamp_delete_history)

370c <Interfaces of vamp procedures 94c>+≡
_interface_sva(vamp_create_history)
_interface_sv(vamp_terminate_history)
_interface_sva(vamp_copy_history)
_interface_sva(vamp_delete_history)

370d <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_create_history_v (h, ndim, verbose)
 type(vamp_history), dimension(:), intent(inout) :: h
 integer, intent(in), optional :: ndim
 logical, intent(in), optional :: verbose
 integer :: i
 do i = 1, size (h)
 call vamp_create_history (h(i), ndim, verbose)
 end do
end subroutine vamp_create_history_v

370e <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_create_history_a (h, ndim, verbose)
 type(vamp_history), dimension(:, :), intent(inout) :: h
 integer, intent(in), optional :: ndim
 logical, intent(in), optional :: verbose
 integer :: i
 do i = 1, size (h, dim=2)

```

```

 call vamp_create_history_v (h(:,i), ndim, verbose)
 end do
end subroutine vamp_create_history_a

371a <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_terminate_history_v (h)
 type(vamp_history), dimension(:), intent(inout) :: h
 integer :: i
 do i = 1, size (h)
 call vamp_terminate_history (h(i))
 end do
end subroutine vamp_terminate_history_v

371b <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_copy_history_v (lhs, rhs)
 type(vamp_history), dimension(:), intent(out) :: lhs
 type(vamp_history), dimension(:), intent(in) :: rhs
 integer :: i
 do i = 1, size (rhs)
 call vamp_copy_history (lhs(i), rhs(i))
 end do
end subroutine vamp_copy_history_v

371c <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_copy_history_a (lhs, rhs)
 type(vamp_history), dimension(:,:,), intent(out) :: lhs
 type(vamp_history), dimension(:,:,), intent(in) :: rhs
 integer :: i
 do i = 1, size (rhs, dim=2)
 call vamp_copy_history_v (lhs(:,i), rhs(:,i))
 end do
end subroutine vamp_copy_history_a

371d <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_delete_history_v (h)
 type(vamp_history), dimension(:), intent(inout) :: h
 integer :: i
 do i = 1, size (h)
 call vamp_delete_history (h(i))
 end do
end subroutine vamp_delete_history_v

371e <Implementation of vamp procedures 77c>+≡
pure subroutine vamp_delete_history_a (h)
 type(vamp_history), dimension(:,:,), intent(inout) :: h
 integer :: i

```

```
do i = 1, size (h, dim=2)
 call vamp_delete_history_v (h(:,i))
end do
end subroutine vamp_delete_history_a
```

372 <Implementation of vamp procedures 77c>+≡  
\_end\_f90

## —N— IDEAS

### *N.1 Toolbox for Interactive Optimization*

*Idea:* Provide a OpenGL interface to visualize the grid optimization.

*Motivation:* Would help multi channel developers.

*Implementation:* Coding is straightforward, but interface design is hard.

### *N.2 Partially Non-Factorized Importance Sampling*

*Idea:* Allow non-factorized grid optimization in two- or three-dimensional subspaces.

*Motivation:* Handle nastiest subspaces. Non-factorized approaches are impossible in higher than three dimensions (and probably only realistic in two dimensions), but there are cases that are best handled by including non-factorized optimization in two dimensions.

*Implementation:* The problem is that the present `vamp_sample_grid0` can't accomodate this, because other auxiliary information has to be collected, but a generalization is straightforward. Work has to start from an extended `divisions` module.

### *N.3 Correlated Importance Sampling (?)*

*Idea:* Is it possible to include *some* correlations in a mainly factorized context?

*Motivation:* Would be nice ...

*Implementation:* First, I have to think about the maths ...

#### *N.4 Align Coordinate System (i.e. the grid) with Singularities (or the hot region)*

*Idea:* Solve `vegas`' nastiest problem by finding the direction(s) along which singularities are aligned.

*Motivation:* Automatically choose proper coordinate system in generator generators and separate wild and smooth directions.

*Implementation:* Diagonalize the covariance matrix  $\text{cov}(x_i x_j)$  to find better axes. Caveats:

- damp rotations (rotate only if eigenvalues are spread out sufficiently).
- be careful about blow up of the integration volume, which is  $V' = V d^{d/2}$  in the worst case for hypercubes and can be even worse for stretched cubes. (An adaptive grid can help, since we will have more smooth directions!)

*Maybe* try non-linear transformations as well.

#### *N.5 Automagic Multi Channel*

*Idea:* Find and extract one singularity after the other.

*Motivation:* Obvious.

*Implementation:* Either use multiple of `vegas`'  $p(x)$  for importance sampling. Or find hot region(s) and split the integration region (á la signal/background).

—O—  
CROSS REFERENCES

*O.1 Identifiers*

BUFFER\_SIZE: 59b, 60a, 107b, 108a, 108b, 109, 264b  
DEFAULT\_BUFFER\_SIZE: 253a, 260c, 260e, 273b, 274a  
DEFAULT\_SEED: 255a, 255c  
EXC\_DEFAULT: 246a, 246e  
EXC\_ERROR: 89c, 245c, 246a, 246c  
EXC\_FATAL: 50a, 50b, 51a, 90a, 96b, 245c, 246c  
EXC\_INFO: 95b, 168, 178a, 245c, 246c  
EXC\_NONE: 245b, 245c, 246c  
EXC\_WARN: 89c, 98a, 105b, 120, 123b, 134c, 136d, 137a, 168, 175d, 176a, 179b, 245c, 246c  
K: 252a, 252b, 252a, 253d, 253e, 252a, 253f, 254b, 254e, 255d, 256a, 256b, 256c, 256e, 257d, 257f, 258c, 258d, 258f, 252a, 258g, 259a, 259b, 259d, 260c, 260e  
L: 252a, 252b, 253e, 253f, 256b, 256c, 256e, 257f, 258g, 259a  
LIPS3: 224b, 226b, 226f, 227a, 229b, 230a, 230c, 232c, 233b, 233c, 234a, 234b, 234c, 235a, 235b, 235c, 236b, 325g, 326a, 326b, 332d  
LIPS3\_m5i2a3: 226c, 226f, 227a, 227b, 228, 232c, 232d, 233b, 233c, 234a, 234b, 234c, 235a, 235b, 235c  
LIPS3\_momenta: 329e  
LIPS3\_momenta\_massless: 330a  
LIPS3\_s2\_t1\_angles: 329c, 331a  
LIPS3\_s2\_t1\_angles\_massless: 329d, 331b  
LIPS3\_unit: 329a, 330d, 331a  
LIPS3\_unit\_massless: 329b, 330e, 331b  
LIPS3\_unit\_to\_s2\_t1\_angles: 330f, 330g, 331a  
LIPS3\_unit\_to\_s2\_t1\_angles\_m0: 330f, 330g, 331b  
M: 240b, 252c, 253e, 253f, 255d, 256b, 256c, 257c, 257f, 258g, 259a, 273d,

275e, 281c, 281d, 282b, 282c, 282d, 282e, 283a  
MAX\_SEED: 255b, 255c  
MAX\_UNIT: 266d, 267a, 311b, 311c  
MIN\_NUM\_DIV: 46a  
MIN\_UNIT: 266d, 267a, 311b, 311c  
NAME\_LENGTH: 245b, 246a  
NUM\_DIV\_DEFAULT: 77c, 78a, 78a  
PI: 190b, 192, 193a, 193b, 223b, 223c, 224a, 225c, 226f, 227b, 228, 243b,  
285a, 286c, 288b, 326a, 326b, 331e, 332c, 332d, 333, 335, 342c  
PRIMES: 310b, 310c  
QUAD\_POWER: 92, 93b  
TAG\_GRID: 176b, 176c, 177a, 177d  
TAG\_HISTORY: 176c, 177a, 177d  
TAG\_INTEGRAL: 176c, 177a, 177d  
TAG\_NEXT\_FREE: 177d  
TAG\_STD\_DEFS: 177d  
TT: 255b, 255f  
ULP: 258b, 258d, 258e  
VAMP\_MAX\_WASTE: 173d, 175a, 175a  
VAMP\_ROOT: 166d, 167a, 167b, 167c, 168, 170a, 170e, 171a, 172a, 172b,  
173a, 173b, 173d, 175c, 176a, 176b, 176c, 177e, 178a, 178c, 179b, 180d,  
181a, 182d, 182e, 183a, 183b, 183f, 184a, 184b, 184c  
abs\_evec: 127a, 127b, 127c, 127f, 128c, 129a  
accuracy: 93c, 93c, 93c, 93c, 93c, 93c, 93c, 93c, 93c, 95b, 102b, 119b, 139b,  
139c, 140c, 168, 173d, 178a  
adaptive\_division: 57a, 57f, 365d, 365e, 366e  
average: 107b, 109, 132c, 290b, 290c, 291a, 291d, 291e  
avg\_chi2: 93c, 94a, 95a, 102b,  
105a, 106b, 107b, 109, 119b, 122b, 123e, 139b, 139c, 140c, 159b, 161,  
164b, 168, 173d, 177e  
\_begin\_f90: 357a, 357c, 358a, 358b, 358c, 360b, 360h, 368a  
boost\_many\_momentum: 323b, 323c, 325b  
boost\_many\_velocity: 323b, 323c, 324b, 325b  
boost\_momentum: 226f, 323b, 323c, 327c, 327d, 333  
boost\_one\_momentum: 323b, 323c, 325a  
boost\_one\_velocity: 323b, 323c, 324a, 324b  
boost\_velocity: 323b, 323c, 325a  
buffer\_end: 259c, 259e, 260c, 260e, 262f, 264b, 264c, 268c, 269b, 270a,  
270c, 272c, 273c, 273d, 273e, 274a, 274b, 275b, 275c, 275e, 276a, 276b,  
276c, 276d, 276e, 277a, 277b, 279g, 280a  
calls: 83a, 83a, 83a, 83a, 83a, 24d, 83a, 83a, 83a, 83a, 76b, 83a, 83b, 88b,

97c, 99c, 105a, 105e, 106a, 106b, 107b, 109, 123e, 134a, 139b, 139c, 140c, 143b, 144b, 150, 151b, 156b, 158, 159b, 161, 162, 164b, 237, 240a, 240b, 241, 242  
calls\_per\_cell: 76b, 83a, 83b, 87c, 89a, 96b, 97c, 97d, 143b, 144b, 150, 151b, 156b, 158, 162  
cartesian\_to\_spherical: 337c, 339a  
cartesian\_to\_spherical\_2: 337c, 337d, 339a, 339b  
cartesian\_to\_spherical\_cos: 193a, 340c, 341  
cartesian\_to\_spherical\_cos\_2: 195b, 340c, 340d, 341, 342a  
cartesian\_to\_spherical\_cos\_j: 193b, 340c, 342a  
cartesian\_to\_spherical\_j: 337c, 339b  
cell: 86a, 43b, 86a, 86a, 86b, 87b, 87d, 363c  
check\_inverses: 194c, 195a, 198c  
check\_inverses3: 194c, 195b, 198c  
check\_jacobians: 194c, 194d, 198c, 209c, 209d, 216e  
check\_kinematics: 232b, 232c, 237  
cl: 131a, 131b, 131c, 131d  
clear\_exception: 24a, 24b, 24c, 24d, 102b, 119b, 212b, 213, 240a, 240b, 241, 242, 246d, 247a, 248, 360c, 360d, 360f  
clear\_integral\_and\_variance: 44c, 45c, 83a, 86b, 363e, 364a, 364f  
cl\_num: 131a, 131b, 131c, 131d  
cl\_pos: 131a, 131b, 131c, 131d  
collect: 54b, 54c, 55c  
constants: 190b, 220a, 243b, 285a, 287b, 323a, 328d, 332d, 333, 335  
coordinates: 190b, 194b, 198c, 200b, 200c, 335  
copy\_array\_pointer: 52b, 54a, 60d, 60e, 60f, 60g, 69, 96c, 158, 162, 163b, 305d, 305e  
copy\_division: 38a, 51a, 69, 69, 98b, 162, 361a, 361b, 361e, 362a  
copy\_history: 58b, 70b, 106b, 107b, 109, 164b, 367b, 367c, 367d  
copy\_integer\_array2\_pointer: 305d, 305e, 306c  
copy\_integer\_array\_pointer: 305d, 305e, 306a  
copy\_raw\_state: 261c, 262e, 262f, 262g, 263a, 263b  
copy\_raw\_state\_to\_state: 262e, 263a  
copy\_real\_array2\_pointer: 305d, 305e, 306d  
copy\_real\_array\_pointer: 305d, 305e, 306b  
copy\_state: 262e, 262f  
copy\_state\_to\_raw\_state: 261b, 262e, 263b  
cos\_theta: 127d, 127e, 127f, 195b, 326a, 326b, 327c, 327d, 328b, 331d, 331e, 336b, 337d, 339d, 340d, 341  
create\_array\_pointer: 96c, 144b, 151b, 303b, 303c  
create\_division: 38a, 38b, 77c, 361a, 361b, 361c

create\_empty\_division: 38a, 39a, 98c, 146a, 361a, 361b, 361d  
create\_histogram: 212b, 213, 294b, 294c  
create\_histogram1: 294c, 294d, 294f  
create\_histogram2: 294c, 294d, 295a  
create\_integer\_array2\_pointer: 303b, 303c, 305b, 306c  
create\_integer\_array\_pointer: 303b, 303c, 304c, 306a  
create\_raw\_state\_from\_raw\_st: 260b, 260d, 260e, 261c  
create\_raw\_state\_from\_seed: 260b, 260c, 261a  
create\_raw\_state\_from\_state: 260b, 261b  
create\_real\_array2\_pointer: 303b, 303c, 305c, 306d  
create\_real\_array\_pointer: 303b, 303c, 305a, 306b  
create\_sample: 203, 205c, 217e  
create\_state\_from\_raw\_state: 260b, 260e  
create\_state\_from\_seed: 260b, 260c  
create\_state\_from\_state: 260b, 260d  
ctest: 132c  
debug\_division: 56a, 56b  
decode\_status: 349c, 349d, 349e, 352b  
delete\_division: 38a, 70a, 146a, 162, 163a, 361a, 361b, 362d  
delete\_histogram: 212b, 213, 294b, 294c  
delete\_histogram1: 294c, 294d, 296c  
delete\_histogram2: 294c, 294d, 297a  
delete\_sample: 203, 205b, 217f  
delta: 47c, 47c, 47c, 48b, 48c, 114, 194d, 288b  
descr\_fmt: 61c, 62a, 62b, 143b, 144a, 144b, 147d, 148  
destroy\_raw\_state: 261d, 261e, 262a  
destroy\_state: 261d, 261e, 261f  
determinant: 113b, 115b, 315a, 315b, 320d  
diag: 316b, 320b, 320c  
diagonalize\_real\_symmetric: 316b, 127f, 128b, 128c, 129e, 140c, 316a, 316b, 320d  
distribute: 15, 16, 54a, 54c, 55b, 102b  
div\_history: 58a, 58c, 59a, 59b, 68b, 68c, 68d, 70b, 105a, 107b, 109, 367d, 367e  
division\_efficiency: 60c, 60g  
division\_integral: 60c, 60e  
division\_t: 37b, 38b, 39a, 39b, 39c, 43b, 44b, 44d, 45a, 45b, 45c, 45e, 48e, 49b, 50a, 50b, 55d, 56b, 56c, 57b, 57c, 57d, 57e, 57f, 58c, 60d, 60e, 60f, 60g, 61c, 62b, 63b, 64a, 64b, 65b, 66a, 66b, 66d, 67a, 67b, 69, 70a, 76b, 96a, 98d, 361c, 361d, 361e, 362a, 362b, 362c, 362d, 363c, 363d, 364c, 364d, 364e, 364f, 365c, 365f, 366a, 366b, 366c, 366d, 366e, 367a, 367e

division\_variance: 60c, 60f  
division\_x: 60c, 60d  
domain: 77c, 77c, 23c, 24a, 24d, 77c, 77c, 77c, 77c, 116a, 166d, 172a, 185a, 185b, 186a, 186b, 187b, 187c, 188a, 188c, 189, 344e, 345b, 345c, 346a, 346d, 346e, 347a, 347c, 347d, 348a, 348c, 349a, 349b, 350a, 350b, 350c, 351b, 352c, 352f, 353a, 353b, 353c, 353d, 354b, 354c, 354d, 355a, 355b, 355c, 355d, 356  
double\_array2\_fmt: 143b, 144a, 144b  
double\_array\_fmt: 61c, 62a, 62b, 143b, 144a, 144b, 147d, 148  
double\_fmt: 61c, 62a, 62b, 143b, 144a, 144b, 147d, 148  
dump\_division: 56a, 56c, 213  
dv2g: 76b, 83b, 83b, 89b, 97c, 143b, 144b, 150, 151b, 156b, 158, 162  
dx: 37b, 38b, 43b, 44a, 48e, 52b, 54a, 57d, 61c, 62b, 64b, 65b, 66d, 67b, 69, 77c, 113b, 115b, 195a, 195b  
\_end\_f90: 357a, 357c, 358b, 358c, 360a, 360g, 367f, 372  
exception: 23c, 245b, 245b, 50a, 50b, 77c, 79d, 81, 82b, 85e, 92, 93c, 96a, 98d, 100b, 101c, 102b, 116a, 117b, 117d, 118b, 119b, 133d, 135, 137c, 138a, 139b, 139c, 140c, 166d, 167b, 167c, 168, 172a, 172b, 173a, 173d, 180d, 181a, 181b, 181c, 212b, 213, 237, 245b, 246c, 246e, 247a, 247b, 360e, 360f  
exceptions: 245a, 23b, 245a, 37a, 75, 165c, 194b, 200b, 209b, 237, 245a  
f: 22, 44d, 59b, 88a, 88a, 88b, 88c, 88d, 124b, 133d, 134a, 134b, 134c, 190b, 191a, 191b, 191c, 194a, 196b, 203, 205a, 208b, 210b, 212b, 213, 286a, 286b, 286c, 364c  
f0: 203, 204a, 205a  
f2: 88c, 88d  
factorize: 103b, 309d, 310b  
fill\_histogram: 212b, 213, 294b, 294c  
fill\_histogram1: 294c, 294d, 295b  
fill\_histogram2s: 294c, 294d, 296a  
fill\_histogram2v: 294c, 294d, 296a, 296b  
find\_free\_unit: 63b, 64a, 66a, 66b, 147b, 147c, 149a, 149b, 153a, 153b, 155a, 155b, 266d, 267b, 267c, 267d, 267e, 267f, 293a, 297b, 300, 311a, 311c  
f\_max: 76b, 84c, 88b, 88c, 97c, 99c, 105a, 106b, 107b, 109, 123e, 134a, 134c, 136a, 136d, 137a, 84c, 143b, 144b, 150, 151b, 156b, 158, 159b, 161, 162, 164b  
f\_min: 76b, 84c, 88b, 97c, 99c, 105a, 106b, 123e, 84c, 143b, 144b, 150, 151b, 156b, 158, 159b, 161, 162, 164b  
f\_norm: 203, 204a, 204b  
fork\_division: 49c, 50a, 50a, 97d



grid: 23c, 24a, 24b, 24c, 77c, 196b, 210b, 240a, 240b  
 handle\_exception: 24a, 24b, 24c, 24d, 120, 212b, 213, 240a, 240b, 241,  
242, 246b, 246c  
 histogram: 212b, 213, 293b, 294f, 295b, 296c, 297b, 298b, 299d  
 histogram2: 294a, 294a, 295a, 296a, 296b, 297a, 299e, 300  
 histograms: 194b, 200b, 209b, 293a  
 i: 15, 16, 17, 127a, 127a, 43b, 44a, 44b, 44d, 45a, 45b, 47c, 48c, 50a,  
 50b, 52b, 52c, 54a, 54b, 55a, 55b, 55c, 55d, 56b, 56c, 59b, 61c, 62b, 64b,  
 65b, 72e, 73c, 73f, 74b, 74d, 91b, 96a, 96c, 97c, 97d, 127a, 98b, 98c, 98d,  
 99a, 99b, 99c, 100b, 101b, 101c, 102b, 103b, 104b, 107b, 108b, 109, 112a,  
 112b, 114, 127a, 127b, 127c, 127d, 127e, 127f, 128c, 129a, 129e, 131a,  
 131d, 132b, 132c, 143b, 144b, 147d, 148, 150, 151b, 153c, 154b, 156b, 157,  
 158, 160, 168, 187c, 191c, 195a, 195b, 204a, 205a, 212b, 213, 217d, 217e,  
 237, 241, 247b, 265b, 265d, 265f, 266b, 266d, 281b, 281d, 282b, 282c,  
 282d, 282e, 283a, 283b, 286a, 286b, 286c, 288c, 295b, 296b, 297b, 298b,  
 307d, 308a, 308b, 308c, 127a, 310b, 311c, 315b, 320a, 320b, 320d, 324b,  
 332d, 333, 336b, 337d, 339d, 340d, 359b, 359c, 359d, 359e, 360e, 360f,  
 364c, 364d, 364e, 368d, 368e, 368f, 369a, 369d, 369e, 369h, 370a, 370d,  
 370e, 371a, 371b, 371c, 371d, 371e  
 ia: 87d, 88c, 88d, 89a, 133d, 134a  
 ihp: 31b, 31b, 112a, 190b, 193a, 194a, 195a  
 inject\_division: 43a, 43b, 87d, 363a, 363b, 363c  
 inject\_division\_short: 43a, 44b, 134a, 363a, 363b, 363d  
 inside\_division: 57a, 57b, 88a, 365d, 365e, 366a  
 integer\_array\_fmt: 143b, 144a, 144b, 147d, 148  
 integer\_array\_state: 276e, 278f  
 integer\_array\_stateless: 274b, 276e, 278b, 279a  
 integer\_array\_static: 278b, 278f  
 integer\_fmt: 61c, 62a, 62b, 143b, 144a, 144b, 147d, 148  
 integer\_state: 276b, 278f  
 integer\_stateless: 272c, 276b, 277d, 279a  
 integer\_static: 277d, 278f  
 integral: 93c, 93c, 93c, 93c, 23c, 24c, 24d, 93c, 93c, 93c, 93c, 93c,  
 93c, 37b, 38b, 39a, 40b, 44d, 45c, 52b, 93c, 52c, 54a, 54b, 55d, 56b, 56c,  
 58c, 60e, 93c, 61c, 62b, 63a, 64b, 65b, 66d, 67b, 69, 70a, 89c, 93c, 94a,  
95a, 102b, 105a, 106b, 107b, 109, 119b, 122b, 123e, 139b, 139c, 140c,  
 159b, 161, 164b, 168, 173d, 177e, 196b, 197a, 197b, 198b, 210b, 211b,  
 212b, 213, 237, 240a, 240b, 241, 242  
 \_interface\_sv: 357a, 357c, 360d, 361b, 363b, 364a, 364b, 365b, 365e,  
 367c, 368c, 369c, 369g, 370c  
 \_interface\_sva: 357a, 357c, 359a, 361b, 370c



local\_std\_dev: 93c, 95a, 95b, 102b, 105b, 119b, 123b, 168, 173d, 176a, 177e, 178a, 179b  
logical\_fmt: 61c, 62a, 62b, 143b, 144a, 144b  
lorentzian: 190b, 191b, 191c  
lorentzian\_normalized: 190b, 191a, 191b  
lu\_decompose: 312b, 313, 315b, 320d  
luxury\_state: 279h, 281a  
luxury\_state\_integer: 279h, 280a, 280b, 281a  
luxury\_stateless: 279g, 280a, 280d, 280g  
luxury\_state\_real: 280b, 281a  
luxury\_static: 280c, 281a  
luxury\_static\_integer: 280c, 280d, 280e, 281a  
luxury\_static\_real: 280e, 281a  
m: 39c, 40a, 46b, 47b, 40a, 47c, 48b, 48c, 58c, 59b, 309e, 309f, 40a, 310a, 328c, 333, 359b, 359c, 359d, 359e  
map\_domain: 77c, 78b, 79a  
marshal\_div\_history: 68a, 68b, 159b  
marshal\_div\_history\_size: 68a, 68c, 159b, 160  
marshal\_division: 66c, 66d, 156b  
marshal\_division\_size: 66c, 67a, 156b, 157  
marshal\_raw\_state: 268a, 268b, 268c, 269c, 269e, 270a, 270d  
marshal\_raw\_state\_size: 268a, 268b, 269a, 269d, 270b, 271a  
marshal\_state: 268a, 268b, 268c, 269b, 270a  
marshal\_state\_size: 268a, 268b, 269a, 270b  
massless\_isotropic\_decay: 231, 331c, 331d  
midpoint: 297b, 298b, 299a, 299b, 300  
midpoint1: 299b, 299c, 299d  
midpoint2: 299b, 299c, 299e  
more\_pancake\_than\_cigar: 125b, 126a, 126b  
mpi90: 165c, 200c, 218a, 218b, 237, 343a, 345a  
mpi90\_abort: 343b, 344c, 344e, 345a  
mpi90\_broadcast: 17, 168, 173d, 177e, 178a, 187b, 188a, 200c, 218b, 237, 241, 352d, 352e  
mpi90\_broadcast\_double: 352e, 353b  
mpi90\_broadcast\_double\_array: 352e, 353b, 354b, 355a, 355d  
mpi90\_broadcast\_double\_array2: 352e, 355a  
mpi90\_broadcast\_double\_array3: 352e, 355d  
mpi90\_broadcast\_integer: 352e, 353a  
mpi90\_broadcast\_integer\_array: 352e, 353a, 353d, 354d, 355c  
mpi90\_broadcast\_integer\_array2: 352e, 354d  
mpi90\_broadcast\_integer\_array3: 352e, 355c

mpi90\_broadcast\_logical: 352e, 353c  
mpi90\_broadcast\_logical\_array: 352e, 353c, 354c, 355b, 356  
mpi90\_broadcast\_logical\_array2: 352e, 355b  
mpi90\_broadcast\_logical\_array3: 352e, 356  
mpi90\_finalize: 200c, 218b, 237, 343b, 344d  
mpi90\_init: 200c, 218b, 237, 343b, 344a  
mpi90\_print\_error: 343b, 344b, 344c, 345a  
mpi90\_rank: 17, 166d, 167b, 167c, 168, 170a, 170e, 171a, 172a, 172b, 173a,  
173b, 173d, 180d, 181a, 182d, 182e, 183a, 183b, 183f, 184a, 184b, 184c,  
187b, 188a, 200c, 218b, 237, 343b, 346a  
mpi90\_receive: 177a, 185b, 189, 346b, 348d  
mpi90\_receive\_double: 348d, 349a  
mpi90\_receive\_double\_array: 348d, 349a, 350a, 350c  
mpi90\_receive\_double\_array2: 348d, 350c  
mpi90\_receive\_double\_pointer: 351a, 352c  
mpi90\_receive\_integer: 348c, 348d  
mpi90\_receive\_integer\_array: 348c, 348d, 349b, 350b  
mpi90\_receive\_integer\_array2: 348d, 350b  
mpi90\_receive\_integer\_pointer: 351a, 351b  
mpi90\_receive\_pointer: 351a, 351a, 351a, 186b, 346b, 351a  
mpi90\_send: 176c, 185a, 186a, 188c, 346b, 346c  
mpi90\_send\_double: 346c, 346e  
mpi90\_send\_double\_array: 346c, 346e, 347c, 348a  
mpi90\_send\_double\_array2: 346c, 348a  
mpi90\_send\_integer: 346c, 346d  
mpi90\_send\_integer\_array: 346c, 346d, 347a, 347d  
mpi90\_send\_integer\_array2: 346c, 347d  
mpi90\_size: 17, 168, 173d, 200c, 218b, 237, 343b, 345c  
mpi90\_status: 185b, 186b, 189, 348b, 348c, 349a, 349b, 349e, 350a, 350b,  
350c, 351b, 352c  
multi\_channel: 196a, 197a, 198c, 210a, 211a, 216c  
multi\_channel\_generator: 212a, 213, 216d  
ndim: 77c, 79a, 81, 83a, 85e, 86a, 92, 93c, 96a, 96c, 105e, 128c, 129a, 144b,  
146a, 151b, 156b, 157, 158, 159b, 160, 161, 162, 316b, 77c, 77c, 319a,  
370d, 370e  
ng: 37b, 38b, 39b, 39c, 42, 50a, 50b, 42, 51a, 42, 52b, 53, 54a, 57e, 58a,  
58c, 59b, 61c, 62b, 64b, 65b, 66d, 67b, 68b, 68d, 69, 70b, 81, 42, 83a, 84e,  
103b, 104b, 362b, 362c  
norm: 127d, 127f, 204a, 204b  
num\_calls: 80b, 80b, 80b, 80b, 80b, 80b, 24a, 24c, 80b, 80b, 80b, 80b,  
80b, 80b, 80b, 80b, 80b, 80b, 50a, 51a, 52b, 54a, 76b, 77c, 79d,

80b, 81, 82b, 83a, 97c, 111a, 116a, 116b, 117b, 117d, 118b, 80b, 80b, 119b,  
 121b, 138a, 143b, 144b, 147d, 148, 150, 151b, 153c, 154b, 156b, 158, 162,  
 163b, 164a, 166d, 167b, 167c, 172a, 172b, 173a, 173d, 181c, 188a  
**num\_cells**: 81, 83a, 83b, 96a, 97c  
**num\_div**: 42, 42, 42, 39c, 40b, 42, 42, 42, 42, 47c, 42, 50a, 50b, 52a, 52b,  
 53, 58a, 58c, 58e, 59b, 62b, 63a, 65b, 66d, 67b, 68b, 68d, 70b, 76b, 77c,  
 79b, 79d, 80b, 81, 82b, 83a, 92, 42, 96a, 96c, 98c, 116a, 117b, 117d, 118b,  
 139b, 139c, 140c, 143b, 144b, 150, 151b, 156b, 158, 162, 163a, 166d, 167b,  
 167c, 172a, 172b, 173a  
**numeric\_jacobian**: 115a, 115b  
**object**: 176b, 176c, 177a, 177b, 177c  
**one\_to\_two\_massive**: 327a, 327b, 327c  
**one\_to\_two\_massless**: 327a, 327b, 327d  
**on\_shell**: 326a, 326b, 327c, 328a, 328c  
**outer\_product**: 84f, 88c, 89a, 309b, 309c, 313  
**phase\_space**: 224b, 226a, 229b, 230c, 232c, 328d  
**phase\_space\_volume**: 222b, 231, 237, 332b, 332c  
**phi**: 31a, 31a, 31a, 112a, 112b, 113b, 114, 115b, 135, 181a, 190b, 192,  
 193a, 194a, 194d, 195a, 195b, 203, 207c, 208b, 209d, 213, 223b, 223c,  
 224b, 226b, 226c, 226f, 227a, 227b, 228, 232d, 326a, 326b, 327c, 327d,  
 328b, 329c, 329d, 331d, 331e, 332d, 336b, 337a, 337b, 337d, 339a, 339d,  
 340a, 340b, 340d, 341  
**phi1**: 233a, 234a, 236b  
**phi12**: 233a, 233b, 236b, 237  
**phi2**: 232d, 233a, 234b, 236b  
**phi21**: 233a, 233c, 236b, 237  
**print\_LIPS3\_m5i2a3**: 232b, 232d  
**print\_history**: 59a, 59b, 60b, 107b  
**print\_history**,: 60b  
**print\_results**: 198a, 198b, 198c  
**probabilities**: 58c, 58d, 58e  
**probability**: 48d, 48e, 91a, 365d, 365e, 365f  
**psi**: 203, 206, 207c  
**quadrupole**: 80b, 80b, 80b, 80b, 80b, 76b, 77c, 79d, 80b, 81, 82b, 92, 97b,  
 116a, 117b, 117d, 118b, 139b, 139c, 140c, 143b, 144b, 150, 151b, 156b,  
 158, 162, 166d, 167b, 167c, 172a, 172b, 173a  
**quadrupole\_division**: 49a, 49b, 92, 365d, 365e, 367a  
**r**: 43b, 44b, 87d, 88d, 114, 127e, 127f, 128b, 128c, 133d, 134a, 135, 136b,  
 136d, 137a, 191b, 192, 193a, 195b, 249, 251g, 272c, 273a, 273d, 273e,  
 276b, 276c, 276d, 277d, 277e, 278a, 331d, 332a, 332d, 336b, 337a, 337b,  
 337d, 339a, 339d, 340a, 340b, 340d, 341, 363c, 363d

`raise_exception`: 50a, 50b, 51a, 89c, 90a, 95b, 96b, 105b, 120, 123b, 134c, 136d, 137a, 168, 175d, 176a, 178a, 179b, 246d, 246e, 247b, 360c, 360d, 360e  
`random_LIPS3`: 330b, 330c  
`random_LIPS3_unit`: 330b, 330c, 330d  
`random_LIPS3_unit_massless`: 330b, 330c, 330e  
`read_division`: 61a, 61b, 144b  
`read_division_name`: 61a, 61b, 64a  
`read_division_raw`: 61a, 61b, 151b  
`read_division_raw_name`: 61a, 61b, 66b  
`read_division_raw_unit`: 61a, 61b, 65b  
`read_division_unit`: 61a, 61b, 62b, 64a, 66b  
`read_grid_name`: 142a, 142c, 147c, 182a, 182c, 183b  
`read_grid_raw_name`: 142b, 143a, 153b  
`read_grid_raw_unit`: 142b, 143a, 151b, 153b, 154b  
`read_grids_name`: 142a, 142c, 149b, 183c, 183e, 184c  
`read_grids_raw_name`: 142b, 143a, 155b  
`read_grids_raw_unit`: 142b, 143a, 154b, 155b  
`read_grids_unit`: 142a, 142c, 148, 149b, 183c, 183e, 184a  
`read_grid_unit`: 142a, 142c, 144b, 147c, 148, 182a, 182c, 182e  
`read_raw_state_name`: 263f, 264a, 267f  
`read_raw_state_unit`: 263f, 264a, 264c, 265a, 267f  
`read_state_array`: 264c, 265a, 265d, 265e, 266b, 266c  
`read_state_name`: 263f, 264a, 267e  
`read_state_unit`: 263f, 264a, 264c, 267e  
`real_array_state`: 277a, 277b, 278f, 279d  
`real_array_stateless`: 275e, 276a, 277a, 277b, 278c, 278d, 279a, 279e  
`real_array_static`: 278c, 278d, 278f, 279d  
`real_state`: 276c, 276d, 278f, 279d  
`real_stateless`: 273d, 273e, 276c, 276d, 277e, 278a, 279a, 279e  
`real_static`: 277e, 278a, 278f, 279d  
`rebin`: 39c, 45e, 47c, 48a  
`rebining_weights`: 40a, 45e, 46b, 47a, 49b, 58c  
`record_efficiency`: 44c, 45b, 88c, 134a, 363f, 364b, 364e  
`record_integral`: 44c, 44d, 88c, 363e, 364a, 364c  
`record_variance`: 44c, 45a, 89a, 363e, 364a, 364d  
`refine_division`: 45d, 45e, 92, 93a, 365a, 365b, 365c  
`reshape_division`: 38a, 39c, 83a, 361a, 361b, 362c  
`rigid_division`: 57a, 57e, 83a, 84e, 86a, 97c, 365d, 365e, 366d  
`s_buffer`: 254a, 273b, 274a, 277d, 277e, 278a, 278b, 278c, 278d, 280c, 280d, 280e

s\_buffer\_end: 273b, 274a, 277d, 277e, 278a, 278b, 278c, 278d, 280d  
schedule: 173d, 178b, 178c  
seed\_raw\_state: 254c, 254d, 257b, 261a  
seed\_state: 254d, 257b  
seed\_stateless: 254a, 254c, 254e, 257g, 258a  
seed\_static: 254a, 257b  
seed\_value: 254e, 255c, 255d, 255f, 258c, 258d  
select\_rotation\_axis: 125a, 127f, 140c  
select\_rotation\_subspace: 125a, 129b  
select\_subspace\_explicit: 128b, 128c, 129b, 129c  
select\_subspace\_guess: 128c, 129b, 129c  
set\_grid\_options: 79d, 80a, 80b, 81  
set\_rigid\_division: 38a, 39b, 361a, 361b, 362b  
sigma\_raw: 229a, 229c, 230c, 236b  
single\_channel: 196a, 196b, 198c, 210a, 210b, 216a  
single\_channel\_generator: 212a, 212b, 216b  
sin\_theta: 127d, 127e, 127f, 328b, 331d, 331e  
s\_last: 254a, 273b, 274a, 277d, 277e, 278a, 278b, 278c, 278d, 280d  
sort: 126a, 129e, 132c, 140c, 178c, 308d, 309a, 320d  
sort\_real: 307d, 308d, 309a  
sort\_real\_and\_integer: 308c, 308d, 309a  
sort\_real\_and\_real\_array: 308b, 308d, 309a  
specfun: 285a, 287b, 288c, 323a, 335  
\_specific\_sv: 357a, 357c, 360c, 361a, 363a, 363e, 363f, 365a, 365d, 367b,  
368b, 369b, 369f, 370b  
\_specific\_sva: 357a, 357c, 358f, 361a, 370b  
spherical\_cos\_to\_cartesian: 192, 339c, 340a  
spherical\_cos\_to\_cartesian\_2: 195b, 339c, 339d, 340a, 340b  
spherical\_cos\_to\_cartesian\_j: 339c, 340b  
spherical\_to\_cartesian: 336a, 337a  
spherical\_to\_cartesian\_2: 336a, 336b, 337a, 337b  
spherical\_to\_cartesian\_j: 336a, 337b  
s\_state: 254a, 254b, 257d, 277d, 277e, 278a, 278b, 278c, 278d  
standard\_deviation: 132b, 132c, 290b, 291a, 291d  
standard\_deviation\_percent: 49b, 58c, 291c, 291d  
std\_dev: 93c, 94a, 95a,  
102b, 105a, 106b, 107b, 109, 119b, 122b, 123e, 139b, 139c, 140c, 159b,  
161, 164b, 168, 173d, 177e, 198b  
stest: 287b, 288c  
stest\_functions: 287b, 288c  
stratified: 80b, 80b, 80b, 80b, 80b, 80b, 80b, 80b, 80b, 37b, 38b, 39b,

39c, 80b, 42, 44d, 45a, 51a, 80b, 52b, 54a, 57c, 58a, 58c, 59b, 61c, 62b, 64b, 65b, 66d, 67b, 68b, 68d, 69, 70b, 76b, 77c, 79d, 80b, 81, 82b, 80b, 83a, 97b, 105a, 106b, 107b, 109, 116a, 117b, 117d, 118b, 123e, 139b, 139c, 140c, 143b, 144b, 150, 151b, 156b, 158, 159b, 161, 162, 164b, 166d, 167b, 167c, 172a, 172b, 173a

stratified\_division: 57a, 57c, 81, 96b, 365d, 365e, 366b

**subdivide:** 54a, 54c, 55a

371a, 371b, 371c, 371d, 371e  
**sum\_chi2:** 76b, 79d, 89c, 94a, 97a, 99c, 111a, 116a, 117b, 121b, 122b,  
 143b, 144b, 147d, 148, 150, 151b, 153c, 154b, 156b, 158, 162, 163b, 188a  
**sum\_division:** 49c, 51b, 55d, 99b  
**sum\_f:** 87c, 88c, 88d, 89a  
**sum\_f2:** 87c, 88c, 88d, 89a  
**sum\_integral:** 76b, 79d, 89c, 94a, 97a, 99c, 111a, 116a, 117b, 121b, 122b,  
 143b, 144b, 147d, 148, 150, 151b, 153c, 154b, 156b, 158, 162, 163b, 188a  
**summarize\_division:** 58b, 58c, 106b, 367b, 367c, 367e  
**sum\_weights:** 76b, 79d, 84f, 85b, 89c, 94a, 97a, 99c, 111a, 116a, 117b,  
 121b, 122b, 143b, 144b, 147d, 148, 150, 151b, 153c, 154b, 156b, 158, 162,  
 163b, 188a  
**sum\_x:** 89a  
**sum\_xx:** 89a  
**surface:** 191b, 342b, 342c  
**s\_virginal:** 254a, 254b, 257d, 277c  
**swap:** 225a, 306e, 307a, 307d, 308b, 308c, 313, 314d, 358c  
**swap\_integer:** 306e, 307a, 307b  
**swap\_integer\_array:** 358b, 358c, 358d  
**swap\_real:** 306e, 307a, 307c  
**swap\_real\_array:** 358b, 358c, 358e  
**tao\_random\_copy:** 251b, 260d, 262b, 272b  
**tao\_random\_create:** 16, 24a, 198c, 200c, 215, 218b, 237, 259f, 250g, 250h,  
 251f, 251g, 259f, 272b, 282c  
**tao\_random\_destroy:** 251a, 261d, 272b  
**tao\_random\_flush:** 251c, 260c, 260e, 263a, 263c, 272b  
**tao\_random\_luxury:** 250d, 250e, 250f, 280f, 272b, 279g, 280f, 281d  
**tao\_random\_marshall:** 268a, 268b, 283a  
**tao\_random\_marshall\_size:** 268a, 268b, 283a  
**tao\_random\_number:** 278e, 87d, 114, 132c, 134a, 134c, 136b, 136d, 137a,  
 195a, 195b, 217e, 232c, 237, 249, 250b, 251f, 251g, 272b, 278e, 279c, 281d,  
 282b, 282c, 282d, 282e, 283a, 320d, 330d, 330e, 332d, 333  
**tao52\_random\_numbers:** 272a, 284  
**tao\_random\_numbers:** 271c, 23b, 75, 271c, 271c, 132c, 165c, 194b, 198c,  
 200b, 200c, 209b, 217c, 220a, 237, 271c, 272a, 281b, 283b, 284, 320d,  
 328d, 332d, 333  
**tao\_random\_raw\_state:** 250a, 259b, 259b, 259b, 251f, 251g, 259b, 254c,  
 259b, 259c, 259d, 259e, 260e, 261a, 261b, 261c, 262a, 262g, 263a, 263b,  
 264d, 265a, 267d, 267f, 269c, 269d, 269e, 270d, 271a, 271b  
**tao\_random\_read:** 251d, 263f, 272b, 282e  
**tao\_random\_seed:** 198c, 200c, 215, 218b, 237, 256g, 250c, 256g, 272b,

256g, 277c, 281d, 282b, 282e, 283a, 320d  
tao\_random\_state: 14, 15, 16, 17, 259c, 23c, 259c, 259c, 85e, 259c, 93c, 102b, 114, 119b, 133d, 135, 137c, 138a, 139b, 139c, 140c, 168, 173d, 180d, 181a, 181b, 181c, 194d, 195a, 195b, 196b, 197a, 198c, 200c, 209d, 210b, 211a, 212b, 213, 217d, 232c, 237, 259c, 259c, 250a, 259c, 259c, 259c, 251f, 251g, 254d, 259c, 259e, 259c, 260c, 260d, 260e, 261b, 261f, 262f, 263a, 263b, 263c, 264b, 264c, 267c, 267e, 268c, 269a, 269b, 270a, 270b, 270c, 276b, 276c, 276d, 276e, 277a, 277b, 279h, 280a, 280b, 281b, 283b, 330d, 330e  
tao\_random\_test: 251e, 272b, 281b, 283b, 284  
tao\_random\_unmarshal: 268a, 268b, 283a  
tao\_random\_write: 251d, 263d, 272b, 282e  
tao\_test: 284  
two\_to\_three\_massless: 325e, 325f, 326b  
unit: 61c, 62b, 63b, 64a, 64b, 65b, 66a, 66b, 73d, 73f, 107b, 108b, 109, 127e, 128b, 143b, 144b, 147b, 147c, 147d, 148, 149a, 149b, 150, 151b, 153a, 153b, 153c, 154b, 155a, 155b, 182d, 182e, 183f, 184a, 251d, 264b, 264c, 264d, 265a, 265b, 265d, 265f, 266b, 266d, 267c, 267d, 267e, 267f, 297b, 298b, 300, 311c, 316b, 320a, 320c, 320d, 331a, 331b  
unmarshal\_div\_history: 68a, 68d, 161  
unmarshal\_division: 66c, 67b, 158  
unmarshal\_raw\_state: 268a, 268b, 269b, 269e, 270c, 271b  
unmarshal\_state: 268a, 268b, 269b, 270c  
utils: 37a, 75, 132c, 165c, 220a, 237, 293a, 303a, 312a, 320d  
value\_spread: 290b, 291b, 291e  
value\_spread\_percent: 49b, 58c, 291c, 291e  
vamp: 2, 76a, 76a, 76a, 23b, 76a, 59b, 70c, 71b, 75, 76a, 89c, 107b, 109, 132c, 76a, 76a, 165b, 76a, 76a, 190b, 194b, 198c, 200c, 203, 209a, 217c, 220a, 246e  
vamp\_apply\_equivalences: 91b, 91b, 119b  
vamp\_average\_iterations: 94b, 93c, 94b, 94c, 102b, 119b, 120, 122d, 168, 175d, 176a, 179b  
vamp\_average\_iterations\_grid: 94a, 94b, 94c  
vamp\_average\_iterations\_grids: 122b, 122c, 122d  
vamp\_broadcast\_grids: 184d, 188a  
vamp\_broadcast\_many\_grids: 187a, 187c  
vamp\_broadcast\_one\_grid: 187a, 187b, 187c  
vamp\_check\_jacobian: 114, 113a, 114, 194d, 209d  
vamp\_copy\_grid: 162, 77a, 162, 163b, 369b, 369c, 369d  
vamp\_copy\_grids: 163b, 115c, 163b, 369f, 369g, 369h  
vamp\_copy\_history: 164b, 105c, 164b, 370b, 370c, 371b

vamp\_create\_empty\_grid: 15, 17, 77b, 77b, 79b, 100b, 102b, 148, 154b,  
   163b, 166d, 168, 172a, 188a, 368b, 368c, 368d  
 vamp\_create\_grid: 77b, 24a, 77b, 77b, 77c, 77b, 116a, 139c, 140c,  
   166b, 166c, 166d, 196b, 210b, 212b, 240a, 240b, 242  
 vamp\_create\_grids: 172a, 115c, 116a, 171d, 171e, 172a, 172a, 197b, 211b,  
   213, 241  
 vamp\_create\_history: 105e, 105c, 105e, 196b, 197b, 210b, 211b, 213, 237,  
   370b, 370c, 370d  
 vamp\_delete\_grid: 15, 17, 163a, 163a, 163a, 77a, 163a, 101c, 102b, 139c,  
   140c, 148, 154b, 163a, 164a, 166b, 166c, 170a, 196b, 210b, 212b, 240a,  
   240b, 242, 369b, 369c, 369e  
 vamp\_delete\_grids: 164a, 115c, 164a, 171d, 171e, 173c, 197b, 211b, 213,  
   241, 369f, 369g, 370a  
 vamp\_delete\_history: 165a, 105c, 165a, 196b, 197b, 210b, 211b, 212b,  
   213, 370b, 370c, 371d  
 vamp\_discard\_integral: 79d, 24c, 79d, 77c, 79c, 79d, 117b, 119b, 139b,  
   166b, 166c, 167b, 179b, 196b, 210b, 212b, 240a, 240b, 242  
 vamp\_discard\_integrals: 117b, 117a, 117b, 117d, 171d, 171e, 172b,  
   197b, 211b, 213, 241  
 vamp\_equivalence\_final: 73a, 73c  
 vamp\_equivalence\_init: 72c, 72e  
 vamp\_equivalences: 71b, 71b, 75, 76a  
 vamp\_equivalences\_complete: 74c, 74d  
 vamp\_equivalence\_set: 74a, 74b  
 vamp\_equivalences\_final: 73b, 73c  
 vamp\_equivalences\_init: 72d, 72e  
 vamp\_equivalences\_write: 73e, 73f  
 vamp\_equivalence\_write: 73d, 73f, 74d  
 vamp\_fork\_grid: 95c, 15, 17, 95c, 95c, 95d, 95c, 100a, 102b, 168  
 vamp\_fork\_grid\_joints: 15, 17, 101b, 100a, 100b, 101a, 101b, 101c,  
   102b, 168  
 vamp\_fork\_grid\_multi: 95c, 95d, 100b  
 vamp\_fork\_grid\_single: 95c, 95d, 96a, 100b  
 vamp\_get\_covariance: 84f, 84d, 84f, 139c, 140c  
 vamp\_get\_history\_multi: 123c, 123d, 123e  
 vamp\_get\_history\_single: 106b, 105c, 105d, 106b  
 vamp\_get\_variance: 85b, 84d, 85b, 123a, 368b, 368c, 368f  
 vamp\_grid: 14, 15, 17, 76b, 22, 23c, 76b, 76b, 76b, 76b, 76b, 76b, 76b,  
   76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b,  
   76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 76b, 77c,  
   79b, 79d, 80b, 81, 82b, 84c, 84e, 84f, 85a, 85b, 85c, 85e, 91a, 92, 93c,

94a, 96a, 98d, 100a, 100b, 101c, 102b, 106b, 111a, 112a, 124b, 133d, 137c,  
 139b, 139c, 140c, 143b, 144b, 147b, 147c, 150, 151b, 153a, 153b, 156b,  
 157, 158, 162, 163a, 166d, 167b, 167c, 168, 170a, 180d, 181b, 182d, 182e,  
 183a, 183b, 185a, 185b, 186a, 186b, 187b, 187c, 190b, 191c, 194a, 196b,  
 203, 205a, 208b, 210b, 212b, 220a, 229b, 230a, 230c, 231, 236b, 237, 368d,  
 368e, 368f, 369a, 369d, 369e  
**vamp\_grids:** 111a,  
 111a, 111a, 111a, 111a, 91b, 93a, 111a, 111a, 116a, 116b, 117b, 117d,  
 118b, 119b, 121b, 122b, 123a, 123e, 135, 138a, 147d, 148, 149a, 149b,  
 153c, 154b, 155a, 155b, 163b, 164a, 171b, 171c, 172a, 172b, 173a, 173b,  
 173c, 173d, 181a, 181c, 183f, 184a, 184b, 184c, 197a, 211a, 213, 237, 369h,  
 370a  
**vamp\_grid\_type:** 22, 31c, 71a, 71b, 75, 76a, 124b  
**vamp\_history:** 105a, 105a, 93c, 102b, 105a, 105e, 106a, 106b, 107b, 108b,  
 109, 119b, 123e, 137c, 138a, 139b, 139c, 140c, 159b, 160, 161, 164b, 165a,  
 168, 170e, 171a, 173d, 181b, 181c, 188c, 189, 196b, 197b, 210b, 211b,  
 212b, 213, 237, 370d, 370e, 371a, 371b, 371c, 371d, 371e  
**vampi:** 166a, 166a, 166a, 166a, 165b, 165c, 166a, 166a, 166a, 200b, 200c,  
 218a, 218b, 237  
**vamp\_integrate\_grid:** 138b, 139a, 139b, 139c, 140c  
**vamp\_integrate\_region:** 138b, 139a, 139c  
**vamp\_integrate\_x\_region:** 140a, 140b, 140c  
**vampi\_tests:** 200b, 200c  
**vamp\_join\_grid:** 95c, 15, 17, 95c, 95c, 95d, 100a, 102b, 168  
**vamp\_join\_grid\_multi:** 95c, 95d, 101c  
**vamp\_join\_grid\_single:** 95c, 95d, 98d, 101c  
**vamp\_marshall\_grid:** 156b, 29, 156a, 156b, 185a, 186a, 187b  
**vamp\_marshall\_grid\_size:** 157, 157, 29, 156a, 157, 185a, 186a, 187b  
**vamp\_marshall\_history:** 159b, 159a, 159b, 188c  
**vamp\_marshall\_history\_size:** 160, 159a, 160, 188c  
**vamp\_multi\_channel:** 112a, 111b, 112a, 190b, 194a  
**vamp\_multi\_channel10:** 112b, 111b, 112b, 203, 208b  
**vamp\_next\_event\_multi:** 133b, 133c, 135, 180a, 180c, 181a  
**vamp\_next\_event\_single:** 133b, 133c, 133d, 135, 180a, 180c, 180d  
**vamp\_nullify\_covariance:** 85a, 84d, 85a, 119b, 175b, 179b, 368b, 368c,  
 368e  
**vamp\_nullify\_f\_limits:** 84a, 84b, 84c, 92, 93a  
**vamp\_nullify\_variance:** 85c, 84d, 85c, 119b, 175b, 179b, 368b, 368c,  
 369a  
**vamp\_parallel\_mpi:** 165c, 165c, 165c, 165c, 166a  
**vamp\_print\_covariance:** 129d, 129e

vamp\_print\_histories: [106d](#), [107a](#), [108b](#), [170b](#), [170d](#), [171a](#)  
vamp\_print\_history: [106d](#), [106d](#), [107a](#), [170b](#), [170c](#), [170d](#), [196b](#), [197b](#),  
    [210b](#), [211b](#), [212b](#), [213](#), [240a](#), [240b](#), [241](#), [242](#)  
vamp\_print\_one\_history: [106d](#), [107a](#), [107b](#), [108b](#), [170b](#), [170d](#), [170e](#)  
vamp\_probability: [90b](#), [91a](#), [112a](#), [220a](#), [236b](#)  
vamp\_read\_grid: [142c](#), [142a](#), [142c](#), [144b](#), [182a](#), [182b](#), [182c](#)  
vamp\_read\_grid\_raw: [142b](#), [143a](#)  
vamp\_read\_grids: [142c](#), [142a](#), [142c](#), [148](#), [183c](#), [183d](#), [183e](#)  
vamp\_read\_grids\_raw: [142b](#), [143a](#), [154b](#)  
vamp\_receive\_grid: [17](#), [185b](#), [30](#), [168](#), [176b](#), [177a](#), [184d](#), [185b](#), [186b](#)  
vamp\_receive\_history: [177a](#), [188b](#), [189](#)  
vamp\_reduce\_channels: [121b](#), [119b](#), [121a](#), [121b](#), [176a](#), [179b](#)  
vamp\_refine\_grid: [14](#), [15](#), [17](#), [92](#), [85d](#), [92](#), [93c](#), [102b](#), [119b](#), [168](#), [175c](#)  
vamp\_refine\_grids: [85d](#), [93a](#)  
vamp\_refine\_weights: [123a](#), [122a](#), [123a](#), [171d](#), [171e](#), [173b](#), [197b](#), [211b](#),  
    [213](#), [241](#)  
vamp\_reshape\_grid: [82b](#), [82b](#), [79d](#), [82a](#), [82b](#), [118b](#), [166b](#), [166c](#), [167c](#)  
vamp\_reshape\_grid\_internal: [81](#), [82a](#), [82b](#), [92](#)  
vamp\_reshape\_grids: [118b](#), [117b](#), [118a](#), [118b](#)  
vamp\_rest: [75](#), [76a](#)  
vamp\_rigid\_divisions: [15](#), [17](#), [84e](#), [84d](#), [84e](#), [102b](#), [168](#)  
vamp\_sample\_grid: [93c](#), [14](#), [93c](#), [93c](#), [93c](#), [93c](#), [93c](#), [24b](#), [24c](#), [93c](#), [93c](#),  
    [93c](#), [85d](#), [93c](#), [93c](#), [93c](#), [137c](#), [139b](#), [166b](#), [166c](#), [168](#), [179b](#),  
    [181b](#), [196b](#), [210b](#), [212b](#), [240a](#), [240b](#), [242](#)  
vamp\_sample\_grid0: [14](#), [15](#), [85e](#), [17](#), [85e](#), [85d](#), [85e](#), [93c](#), [102b](#), [85e](#), [120](#),  
    [85e](#), [137c](#), [138a](#), [168](#), [85e](#), [175d](#), [181b](#), [181c](#), [85e](#)  
vamp\_sample\_grid\_parallel: [102b](#), [102b](#), [102a](#), [102b](#)  
vamp\_sample\_grids: [119b](#), [119a](#), [119b](#), [138a](#), [171d](#), [171e](#), [119b](#), [173d](#),  
    [197b](#), [211b](#), [213](#), [241](#)  
vamp\_send\_grid: [17](#), [185a](#), [30](#), [168](#), [176b](#), [176c](#), [184d](#), [185a](#), [185a](#),  
    [186a](#)  
vamp\_send\_history: [176c](#), [188b](#), [188c](#)  
vamp\_serial\_mpi: [165b](#), [165b](#), [165b](#), [165c](#), [166a](#)  
vamp\_stat: [37a](#), [75](#), [132c](#), [290a](#)  
vamp\_sum\_channels: [124b](#), [124a](#), [124b](#)  
vamp\_terminate\_history: [106a](#), [105b](#), [105c](#), [106a](#), [120](#), [123b](#), [168](#), [175d](#),  
    [176a](#), [179b](#), [370b](#), [370c](#), [371a](#)  
vamp\_test0: [202b](#), [210b](#), [211b](#), [215](#)  
vamp\_test0\_functions: [203](#), [209b](#), [217c](#)  
vamp\_tests: [194b](#), [198c](#), [194b](#)  
vamp\_tests0: [209a](#), [217c](#), [218a](#)

vamp\_unmarshal\_grid: 158, 29, 156a, 158, 185b, 186b, 187b  
 vamp\_unmarshal\_history: 161, 159a, 161, 189  
 vamp\_update\_weights: 117d, 117c, 117d, 123a, 171d, 171e, 173a  
 vamp\_warmup\_grid: 137c, 137c, 137b, 137c, 180a, 180b, 181b, 212b  
 vamp\_warmup\_grids: 138a, 137b, 138a, 180a, 180b, 181c, 213  
 vamp\_write\_grid: 142c, 142a, 142c, 182a, 182b, 182c, 196b, 210b, 240a,  
     240b  
 vamp\_write\_grid\_raw: 142b, 143a  
 vamp\_write\_grids: 142c, 142a, 142c, 183c, 183d, 183e, 197b, 211b, 241  
 vamp\_write\_grids\_raw: 142b, 143a  
 vamp\_write\_histories: 106d  
 vamp\_write\_history: 106d, 107a  
 vamp\_write\_one\_history: 106d  
 var\_f: 45a, 88d, 88d, 89a, 364d  
 volume\_division: 57a, 57d, 83b, 97c, 365d, 365e, 366c  
 w: 51a, 96b, 190b, 194a, 197b, 203, 208b, 211b, 213, 230b, 230c  
 wgt: 43b, 44a, 44b, 87d, 87d, 87d, 87d, 88a, 88d, 88d, 133d, 134a, 135,  
     136c, 136d, 137a, 363c, 363d  
 wgt0: 131b, 131d  
 wgt1: 131b, 131d  
 wgts: 87d, 88d, 114, 133d, 134a  
 write\_division: 61a, 61b, 143b  
 write\_division\_name: 61a, 61b, 63b  
 write\_division\_raw: 61a, 61b, 150  
 write\_division\_raw\_name: 61a, 61b, 66a  
 write\_division\_raw\_unit: 61a, 61b, 64b  
 write\_division\_unit: 61a, 61b, 61c, 63b, 66a  
 write\_grid\_name: 142a, 142c, 147b, 182a, 182c, 183a  
 write\_grid\_raw\_name: 142b, 143a, 153a  
 write\_grid\_raw\_unit: 142b, 143a, 150, 153a, 153c  
 write\_grids\_name: 142a, 142c, 149a, 183c, 183e, 184b  
 write\_grids\_raw\_name: 142b, 143a, 155a  
 write\_grids\_raw\_unit: 142b, 143a, 153c, 155a  
 write\_grids\_unit: 142a, 142c, 147d, 149a, 183c, 183e, 183f  
 write\_grid\_unit: 142a, 142c, 143b, 147b, 147d, 182a, 182c, 182d  
 write\_histogram: 212b, 213, 294b, 294c, 297b, 300  
 write\_histogram1: 294c, 294d, 297b  
 write\_histogram2: 294c, 294d, 300  
 write\_histogram1\_unit: 294c, 298a, 298b  
 write\_history: 59a, 59b, 60b, 109  
 write\_raw\_state\_name: 263d, 263e, 267d

```

write_raw_state_unit: 263d, 263e, 264b, 264d, 267d
write_state_array: 264b, 264d, 265b, 265c, 265f, 266a
write_state_name: 263d, 263e, 267c
write_state_unit: 263d, 263e, 264b, 267c
wx: 236a, 236b, 241
x: 23a, 31a, 31b, 31c, 87d, 87d, 87d, 87d, 87d, 37b, 38b, 39a, 39b,
 39c, 40b, 43b, 44a, 44b, 45e, 87d, 47c, 48c, 48e, 50a, 50b, 52b, 54a, 55a,
 55b, 55c, 56b, 56c, 57b, 57f, 58c, 58e, 59b, 60d, 61c, 62b, 63a, 64b, 65b,
 66d, 67a, 67b, 69, 70a, 87d, 87d, 88a, 88c, 88d, 91a, 112a, 112b, 113b,
 114, 115b, 124b, 131a, 131d, 133d, 134a, 135, 180d, 181a, 191a, 191b,
 191c, 192, 193a, 193b, 194a, 194d, 195a, 195b, 204a, 205a, 206, 207a,
 207b, 207c, 208a, 208b, 209d, 212b, 213, 223b, 223c, 224b, 226b, 226d,
 227b, 228, 229b, 230a, 230c, 231, 232c, 233b, 233c, 236b, 237, 248, 250f,
 254c, 254e, 255d, 255e, 256a, 256b, 256c, 256e, 256f, 258c, 258d, 258e,
 258f, 258g, 259a, 259b, 259d, 262g, 264d, 265a, 266b, 269c, 269d, 269e,
 270d, 271a, 271b, 276b, 276c, 276d, 276e, 277a, 277b, 286c, 288b, 288c,
 290c, 291a, 291b, 291d, 291e, 295b, 296b, 299d, 299e, 309c, 329a, 329b,
 330d, 330e, 331d, 332a, 336b, 337a, 337d, 339a, 339b, 339d, 340a, 340d,
 341, 342a, 363c, 363d, 366a
x5: 226d, 228, 232c, 233b, 233c, 234c, 235a
x_mid: 43b, 87d, 88d, 89a, 363c
x_new: 47c, 48c

```

## O.2 Refinements

```

⟨API documentation 249⟩
⟨Accept distribution among n workers 104a⟩
⟨Adjust Jacobian 224a⟩
⟨Adjust grid and other state for new num_calls 83a⟩
⟨Adjust h%div iff necessary 106c⟩
⟨Allocate or resize the divisions 98c⟩
⟨Alternative to basic.f90 24d⟩
⟨Application in Rambo mode 242⟩
⟨Application in massless single channel mode 240b⟩
⟨Application in multi channel mode 241⟩
⟨Application in single channel mode 240a⟩
⟨ $A' = P^T(\phi; p, q) \cdot A \cdot P(\phi; p, q)$ 318c⟩
⟨Bail out if any (d == NaN) 47b⟩
⟨Bail out if exception exc raised 98a⟩
⟨Body of create_*_array2_pointer 304b⟩

```

⟨Body of `create_*_array_pointer` 304a⟩  
 ⟨Body of `mpi90_broadcast_*_array` 354a⟩  
 ⟨Body of `mpi90_receive_*_array` 349c⟩  
 ⟨Body of `mpi90_receive_*_pointer` 351c⟩  
 ⟨Body of `mpi90_send_*_array` 347b⟩  
 ⟨Body of `multi_channel` 197b⟩  
 ⟨Body of `tao_random_*` 273a⟩  
 ⟨Body of `tao_random_*_array` 274c⟩  
 ⟨Boost and rescale the vectors 332a⟩  
 ⟨Bootstrap the 52-bit  $\mathbf{x}$  buffer 258d⟩  
 ⟨Bootstrap the  $\mathbf{x}$  buffer 255d⟩  
 ⟨Check optional arguments in `vamp_sample_grid0` 90a⟩  
 ⟨Choose a  $\mathbf{x}$  and calculate  $f(\mathbf{x})$  134a⟩  
 ⟨Cleanup in `vamp_test0` 217f⟩  
 ⟨Clenshaw's recurrence formula 286b⟩  
 ⟨Collect integration and grid optimization data for current cell 89a⟩  
 ⟨Collect integration and grid optimization data for  $\mathbf{x}$  from  $f$  88b⟩  
 ⟨Collect results of `vamp_sample_grid0` 89b⟩  
 ⟨Combine the rest of  $g_s$  onto  $g$  99c⟩  
 ⟨Constants in divisions 65a⟩  
 ⟨Constants in `vamp` 151a⟩  
 ⟨Constants in `vamp_equivalences` 72b⟩  
 ⟨Construct  $\hat{R}(\theta; i, j)$  127e⟩  
 ⟨Copy results of `vamp_sample_grid` to dummy variables 95a⟩  
 ⟨Copy results of `vamp_sample_grids` to dummy variables 177e⟩  
 ⟨Copy the rest of  $g$  to the  $g_s$  96c⟩  
 ⟨Copyleft notice 1⟩  
 ⟨Count up cell, exit if done 86a⟩  
 ⟨Declaration of 30-bit `tao_random_numbers` 265c⟩  
 ⟨Declaration of 52-bit `tao_random_numbers` 266a⟩  
 ⟨Declaration of 30-bit `tao_random_numbers` types 259b⟩  
 ⟨Declaration of 52-bit `tao_random_numbers` types 259d⟩  
 ⟨Declaration of coordinates procedures 336a⟩  
 ⟨Declaration of cross\_section procedures 221d⟩  
 ⟨Declaration of divisions procedures 38a⟩  
 ⟨Declaration of divisions procedures (removed from WHIZARD) 60c⟩  
 ⟨Declaration of divisions types 37b⟩  
 ⟨Declaration of exceptions procedures 246b⟩  
 ⟨Declaration of exceptions types 245b⟩  
 ⟨Declaration of histograms procedures 294b⟩  
 ⟨Declaration of histograms types 293b⟩

⟨Declaration of kinematics procedures 323b⟩  
 ⟨Declaration of kinematics types 325g⟩  
 ⟨Declaration of linalg procedures 312b⟩  
 ⟨Declaration of mpi90 procedures 343b⟩  
 ⟨Declaration of mpi90 types 348b⟩  
 ⟨Declaration of phase\_space procedures 330b⟩  
 ⟨Declaration of phase\_space types 329a⟩  
 ⟨Declaration of procedures in vamp\_tests0 210a⟩  
 ⟨Declaration of procedures in vamp\_tests 194c⟩  
 ⟨Declaration of procedures in vamp\_tests0 (broken?) 209c⟩  
 ⟨Declaration of specfun procedures 285b⟩  
 ⟨Declaration of stest\_functions procedures 288a⟩  
 ⟨Declaration of tao\_random\_numbers 253c⟩  
 ⟨Declaration of tao\_random\_numbers (unused luxury) 280g⟩  
 ⟨Declaration of utils procedures 303b⟩  
 ⟨Declaration of vamp procedures 77a⟩  
 ⟨Declaration of vamp procedures (removed from WHIZARD) 115a⟩  
 ⟨Declaration of vamp types 105a⟩  
 ⟨Declaration of vamp\_equivalences procedures 72d⟩  
 ⟨Declaration of vamp\_equivalences types 71c⟩  
 ⟨Declaration of vamp\_grid\_type types 76b⟩  
 ⟨Declaration of vampi procedures 166b⟩  
 ⟨Declaration of vampi types 171b⟩  
 ⟨Declaration of vamp\_stat procedures 290b⟩  
 ⟨Decode channel into ch and p(:) 207b⟩  
 ⟨Determine  $\phi$  for the Jacobi rotation  $P(\phi; p, q)$  with  $A'_{pq} = 0$  318a⟩  
 ⟨Distribute complete grids among processes 175b⟩  
 ⟨Distribute each grid among processes 179b⟩  
 ⟨Estimate waste of processor time 179a⟩  
 ⟨Execute command 217b⟩  
 ⟨Execute command in vamp\_test (never defined)⟩  
 ⟨Execute tests in vamp\_test0 216a⟩  
 ⟨Exit iterate if accuracy has been reached 95b⟩  
 ⟨Exit iterate if accuracy has been reached (MPI) 178a⟩  
 ⟨Fill state from x 256e⟩  
 ⟨Fork a pseudo stratified sampling division 54a⟩  
 ⟨Fork a pure stratified sampling division 52b⟩  
 ⟨Fork an importance sampling division 51a⟩  
 ⟨Gather exceptions in vamp\_sample\_grid\_parallel 103a⟩  
 ⟨Generate isotropic null vectors 331e⟩  
 ⟨Get cos  $\theta$  and sin  $\theta$  from evecs 127d⟩

⟨Get x in the current cell 87d⟩  
 ⟨Handle g%calls\_per\_cell for d == 0 96b⟩  
 ⟨Handle local\_error 344c⟩  
 ⟨Handle local\_error (no mpi90\_abort) 344b⟩  
 ⟨Handle optional pancake and cigar 128a⟩  
 ⟨Idioms 100a⟩  
 ⟨Implementation of 30-bit tao\_random\_numbers 253b⟩  
 ⟨Implementation of 52-bit tao\_random\_numbers 257e⟩  
 ⟨Implementation of coordinates procedures 336b⟩  
 ⟨Implementation of cross\_section procedures 222a⟩  
 ⟨Implementation of divisions procedures 38b⟩  
 ⟨Implementation of divisions procedures (removed from WHIZARD) 45b⟩  
 ⟨Implementation of exceptions procedures 246c⟩  
 ⟨Implementation of histograms procedures 294f⟩  
 ⟨Implementation of kinematics procedures 324a⟩  
 ⟨Implementation of linalg procedures 313⟩  
 ⟨Implementation of mpi90 procedures 344a⟩  
 ⟨Implementation of phase\_space procedures 330d⟩  
 ⟨Implementation of procedures in vamp\_tests0 210b⟩  
 ⟨Implementation of procedures in vamp\_tests 195a⟩  
 ⟨Implementation of procedures in vamp\_tests (broken?) 194d⟩  
 ⟨Implementation of procedures in vamp\_tests0 (broken?) 209d⟩  
 ⟨Implementation of specfun procedures 286c⟩  
 ⟨Implementation of stest\_functions procedures 288b⟩  
 ⟨Implementation of tao\_random\_numbers 254a⟩  
 ⟨Implementation of utils procedures 304c⟩  
 ⟨Implementation of vamp procedures 77c⟩  
 ⟨Implementation of vamp procedures (removed from WHIZARD) 115b⟩  
 ⟨Implementation of vamp\_equivalences procedures 72c⟩  
 ⟨Implementation of vampi procedures 166d⟩  
 ⟨Implementation of vampi procedures (doesn't work with MPICH yet) 186a⟩  
 ⟨Implementation of vamp\_stat procedures 290c⟩  
 ⟨Implementation of vamp\_test0\_functions procedures 204a⟩  
 ⟨Implementation of vamp\_test\_functions procedures 191a⟩  
 ⟨Increment k until  $\sum m_k \geq \Delta$  and keep the surplus in  $\delta$  48b⟩  
 ⟨Initialize a virginal random number generator 277c⟩  
 ⟨Initialize clusters 131a⟩  
 ⟨Initialize num\_rot 319e⟩  
 ⟨Initialize stratified sampling 42⟩  
 ⟨Ensure that associated (g%map) == .false. 146b⟩  
 ⟨Ensure that associated (g%mu\_x) == .false. 147a⟩

⟨*Insure that size (g%div) == ndim* 146a⟩  
 ⟨*Insure that ubound (d%x, dim=1) == num\_div* 63a⟩  
 ⟨*Interface declaration for func* 22⟩  
 ⟨*Interface declaration for ihp* 31b⟩  
 ⟨*Interface declaration for jacobian* 31c⟩  
 ⟨*Interface declaration for phi* 31a⟩  
 ⟨*Interfaces of 30-bit tao\_random\_numbers* 278e⟩  
 ⟨*Interfaces of 52-bit tao\_random\_numbers* 279c⟩  
 ⟨*Interfaces of divisions procedures* 61b⟩  
 ⟨*Interfaces of divisions procedures (removed from WHIZARD)* 364b⟩  
 ⟨*Interfaces of exceptions procedures* 360d⟩  
 ⟨*Interfaces of histograms procedures* 294c⟩  
 ⟨*Interfaces of kinematics procedures* 323c⟩  
 ⟨*Interfaces of mpi90 procedures* 346c⟩  
 ⟨*Interfaces of phase\_space procedures* 330c⟩  
 ⟨*Interfaces of tao\_random\_numbers* 256g⟩  
 ⟨*Interfaces of tao\_random\_numbers (unused luxury)* 280f⟩  
 ⟨*Interfaces of utils procedures* 303c⟩  
 ⟨*Interfaces of vamp procedures* 94c⟩  
 ⟨*Interfaces of vampi procedures* 170d⟩  
 ⟨*Interpolate the new  $x_i$  from  $x_k$  and  $\delta$*  48c⟩  
 ⟨*Join closest clusters* 131b⟩  
 ⟨*Join importance sampling divisions* 51b⟩  
 ⟨*Join pseudo stratified sampling divisions* 54b⟩  
 ⟨*Join pure stratified sampling divisions* 52c⟩  
 ⟨*Kill m4(1) builtins* 357b⟩  
 ⟨*Load a and refresh state* 253d⟩  
 ⟨*Load 52-bit a and refresh state* 257f⟩  
 ⟨*Local variables in vamp\_sample\_grid0* 87a⟩  
 ⟨*MPI communication example* 29⟩  
 ⟨*MPI communication example'* 30⟩  
 ⟨*Maybe accept unweighted event* 134c⟩  
 ⟨*Maybe accept unweighted multi channel event* 136d⟩  
 ⟨*Maybe accept unweighted multi channel event (old version)* 137a⟩  
 ⟨*Module vamp\_test0\_functions* 203⟩  
 ⟨*Module vamp\_test\_functions* 190b⟩  
 ⟨*Module vamp\_tests* 194b⟩  
 ⟨*Modules used by vamp\_test0* 217c⟩  
 ⟨*Modules used by vamp\_tests0* 209b⟩  
 ⟨*Parallel implementation of  $S_n = S_0(rS_0)^n$  (HPF)* 15⟩  
 ⟨*Parallel implementation of  $S_n = S_0(rS_0)^n$  (MPI)* 17⟩

⟨Parallel usage of  $S_n = S_0(rS_0)^n$  (HPF) 16⟩  
 ⟨Parameters in mpi90 (never defined)⟩  
 ⟨Parameters in tao\_random\_numbers 252a⟩  
 ⟨Parameters in tao\_random\_numbers (alternatives) 252b⟩  
 ⟨Parameters in tao\_random\_test 281c⟩  
 ⟨Parameters in utils 310c⟩  
 ⟨Parameters in vampi 167a⟩  
 ⟨Parameters local to tao\_random\_seed 255a⟩  
 ⟨Parse the commandline in vamp\_test and set command (never defined)⟩  
 ⟨Perform more tests of tao\_random\_numbers 282c⟩  
 ⟨Perform simple tests of tao\_random\_numbers 281d⟩  
 ⟨Perform the Jacobi rotation resulting in  $A'_{pq} = 0$  317⟩  
 ⟨Prepare array buffer and done, todo, chunk 275b⟩  
 ⟨Pull u into the intervall [3, 4] 286a⟩  
 ⟨Read command line and decode it as command (never defined)⟩  
 ⟨Receive the result for channel #ch at the root 177a⟩  
 ⟨Reload buffer or exit 275d⟩  
 ⟨Reset counters in vamp\_sample\_grid0 86b⟩  
 ⟨Resize arrays, iff necessary 40b⟩  
 ⟨Return optional arguments in lu\_decompose 314d⟩  
 ⟨Sample calls\_per\_cell points in the current cell 87c⟩  
 ⟨Sample g%g0%grids(ch) 175d⟩  
 ⟨Sample the grid g%grids(ch) 120⟩  
 ⟨Select channel from weights 136b⟩  
 ⟨Serial implementation of  $S_n = S_0(rS_0)^n$  14⟩  
 ⟨Set default for domain 345b⟩  
 ⟨Set defaults for source, tag and domain 348e⟩  
 ⟨Set i, delta\_x, x, and wgt from xi 44a⟩  
 ⟨Set i(1), i(2) to the axes of the optimal plane 127a⟩  
 ⟨Set i(1), i(2) to the axes of the optimal plane (broken!) 127b⟩  
 ⟨Set iv to the index of the optimal eigenvector 125b⟩  
 ⟨Set j to minloc(key) 308a⟩  
 ⟨Set m to (1, 1, ...) or to rebinning weights from d%variance 40a⟩  
 ⟨Set nu to num or size(v) 275a⟩  
 ⟨Set rev to reverse or .false. 307e⟩  
 ⟨Set  $(s_2, t_1, \phi, \cos \theta_3, \phi_3)$  from  $(x_1, \dots, x_5)$  223b⟩  
 ⟨Set  $(s_2, t_1, \phi, \cos \theta_3, \phi_3)$  from  $(x_1, \dots, x_5)$  (massless case) 223c⟩  
 ⟨Set subspace to the axes of the optimal plane 129a⟩  
 ⟨Set up integrand and region in vamp\_test0 217e⟩  
 ⟨Set up s and t 255f⟩  
 ⟨Set up seed\_value from seed or DEFAULT\_SEED 255c⟩

⟨Setup to fork a pseudo stratified sampling division 53⟩  
 ⟨Setup to fork a pure stratified sampling division 52a⟩  
 ⟨Shift s or t and exit if t ≤ 0 256d⟩  
 ⟨Ship g%g0%grids from the root to the assigned processor 176b⟩  
 ⟨Ship the result for channel #ch back to the root 176c⟩  
 ⟨Specific procedures for 30-bit tao\_random\_number 278f⟩  
 ⟨Specific procedures for 52-bit tao\_random\_number 279d⟩  
 ⟨Specific procedures for tao\_random\_copy 262e⟩  
 ⟨Specific procedures for tao\_random\_create 260b⟩  
 ⟨Specific procedures for tao\_random\_luxury 281a⟩  
 ⟨Specific procedures for tao\_random\_seed 257b⟩  
 ⟨Step last and reload buffer iff necessary 273c⟩  
 ⟨Test a(1) = A\_2027082 282a⟩  
 ⟨Trace results of vamp\_sample\_grid 105b⟩  
 ⟨Trace results of vamp\_sample\_grids 123b⟩  
 ⟨Trivial ktest.f90 333⟩  
 ⟨Types in cross\_section 226c⟩  
 ⟨Unconditionally accept weighted event 134b⟩  
 ⟨Unconditionally accept weighted multi channel event 136c⟩  
 ⟨(Unused) Interfaces of phase\_space procedures 330g⟩  
 ⟨Update last, done and todo and set new chunk 275c⟩  
 ⟨Update num\_rot 319f⟩  
 ⟨Variables in 30-bit tao\_random\_numbers 252c⟩  
 ⟨Variables in 52-bit tao\_random\_numbers 257c⟩  
 ⟨Variables in cross\_section 220b⟩  
 ⟨Variables in divisions 46a⟩  
 ⟨Variables in exceptions 245c⟩  
 ⟨Variables in histograms 294e⟩  
 ⟨Variables in mpi90 (never defined)⟩  
 ⟨Variables in tao\_random\_numbers 267a⟩  
 ⟨Variables in utils 311b⟩  
 ⟨Variables in vamp 78a⟩  
 ⟨Variables in vamp\_test0 217a⟩  
 ⟨Variables local to 52-bit tao\_random\_seed 258b⟩  
 ⟨V' = V · P(ϕ; p, q) 319d⟩  
 ⟨Warm up state 256f⟩  
 ⟨XXX Implementation of cross\_section procedures 221e⟩  
 ⟨XXX Variables in cross\_section 221a⟩  
 ⟨application.f90 220a⟩  
 ⟨basic.f90 23a⟩  
 ⟨52-bit p(z) → p(z)<sup>2</sup> (modulo z<sup>K</sup> + z<sup>L</sup> + 1) 258f⟩

```

⟨52-bit $p(z) \rightarrow zp(z)$ (modulo $z^K + z^L + 1$) 259a⟩
⟨call copy_division (gs%div(j), g%div(j)) 98b⟩
⟨call fork_division (g%div(j), gs%div(j), g%calls_per_cell, ...) 97d⟩
⟨call join_division (g%div(j), gs%div(j)) 99a⟩
⟨call sum_division (g%div(j), gs%div(j)) 99b⟩
⟨ $c_0/2, c_1, c_2, \dots, c_{15}$ for $\Gamma(x)$ 287a⟩
⟨constants.f90 243b⟩
⟨coordinates.f90 335⟩
⟨ctest.f90 132c⟩
⟨divisions.f90 37a⟩
⟨eps = 1 314a⟩
⟨eps = - eps 314b⟩
⟨exceptions.f90 245a⟩
⟨f = wgt * func (x, weights, channel), iff x inside true_domain 88a⟩
⟨f90.m4 357c⟩
⟨f95.m4 357a⟩
⟨histograms.f90 293a⟩
⟨kinematics.f90 323a⟩
⟨ktest.f90 332d⟩
⟨la_sample.f90 320d⟩
⟨linalg.f90 312a⟩
⟨ $m_a \leftrightarrow m_b, m_1 \leftrightarrow m_2$ for channel #1 224c⟩
⟨mpi90.f90 343a⟩
⟨pivots = 0 and eps = 0 314c⟩
⟨ $p_1 \leftrightarrow p_2$ for channel #2 225a⟩
⟨products.f90 322⟩
⟨ $p(z) \rightarrow p(z)^2$ (modulo $z^K + z^L + 1$) 256a⟩
⟨ $p(z) \rightarrow zp(z)$ (modulo $z^K + z^L + 1$) 256c⟩
⟨specfun.f90 285a⟩
⟨stest.f90 287b⟩
⟨tao52_random_numbers.f90 272a⟩
⟨tao_random_numbers.f90 271c⟩
⟨tao_test.f90 284⟩
⟨utils.f90 303a⟩
⟨vamp0_* => vamp_* 166c⟩
⟨vamp.f90 70c⟩
⟨vampi.f90 165b⟩
⟨vampi_test.f90 200a⟩
⟨vampi_test0.f90 218a⟩
⟨vamp_kinds.f90 243a⟩
⟨vamp_stat.f90 290a⟩

```

```
⟨vamp_test.f90 190a⟩
⟨vamp_test0.f90 202b⟩
⟨vamp_test.out 202a⟩
⟨vamp_test0.out 219⟩
⟨weights: $\alpha_i \rightarrow w_{\max,i} \alpha_i$ 136a⟩
```

# INDEX

deficiencies in Fortran90 and F, 74,  
85  
deficiencies of Fortran90 that have  
been fixed in Fortran95, 247  
dependences on external modules,  
85  
Fortran problem, 68  
Fortran sucks, 109  
functional programming rules, 109  
IEEE hacks, 45  
inconvenient F constraints, 112, 313  
more empirical studies helpful, 129  
optimizations not implemented yet,  
101  
Problems with MPICH, 182–184  
remove from finalized program, 331  
system dependencies, 45, 265  
unfinished business, 122

## *Acknowledgements*

## BIBLIOGRAPHY

- [1] G. P. Lepage, J. Comp. Phys. **27**, 192 (1978).
- [2] G. P. Lepage, *VEGAS – An Adaptive Multi-dimensional Integration Program*, Cornell preprint, CLNS-80/447, March 1980.
- [3] T. Ohl, *Vegas Revisited: Adaptive Monte Carlo Integration Beyond Factorization*, hep-ph/9806432, Preprint IKDA 98/15, Darmstadt University of Technology, 1998.
- [4] D. E. Knuth, *Literate Programming*, Vol. 27 of *CSLI Lecture Notes* (Center for the Study of Language and Information, Leland Stanford Junior University, Stanford, CA, 1991).
- [5] N. Ramsey, IEEE Software **11**, 97 (1994).
- [6] American National Standards Institute, *American National Standard Programming Languages FORTRAN, ANSI X3.9-1978*, New York, 1978.
- [7] International Standards Organization, *ISO/IEC 1539:1991, Information technology — Programming Languages — Fortran*, Geneva, 1991.
- [8] International Standards Organization, *ISO/IEC 1539:1997, Information technology — Programming Languages — Fortran*, Geneva, 1997.
- [9] High Performance Fortran Forum, *High Performance Fortran Language Specification, Version 1.1*, Rice University, Houston, Texas, 1994.
- [10] High Performance Fortran Forum, *High Performance Fortran Language Specification, Version 2.0*, Rice University, Houston, Texas, 1997.
- [11] Message Passing Interface Forum, *MPI: A Message Passing Interface Standard*, Technical Report CS-94230, University of Tennessee, Knoxville, Tennessee, 1994.
- [12] J. C. Adams, W. S. Brainerd, J. T. Martin, B. T. Smith, and J. L. Wagner, *Fortran 95 Handbook*, The MIT Press, Cambridge, MA, 1997.

- [13] Michael Metcalf and John Reid, *The F Programming Language*, (Oxford University Press, 1996).
- [14] C. H. Koelbel, D. B. Loveman, R. S. Schreiber, G. L. Steele Jr., and M. E. Zosel, *The High Performance Fortran Handbook*, The MIT Press, Cambridge, MA, 1994.
- [15] D. E. Knuth, *Seminumerical Algorithms* (third edition), Vol. 2 of *The Art of Computer Programming*, (Addison-Wesley, 1997).
- [16] W. H. Press, S. A. Teukolsky, W. T. Vetterling, B. P. Flannery, *Numerical Recipies in C: The Art of Scientific Computing*, 2nd edition, (Cambridge University Press, 1992)
- [17] W. H. Press, S. A. Teukolsky, W. T. Vetterling, B. P. Flannery, *Numerical Recipies in Fortran77: The Art of Scientific Computing*, Volume 1 of *Fortran Numerical Recipies*, 2nd edition, (Cambridge University Press, 1992)
- [18] W. H. Press, S. A. Teukolsky, W. T. Vetterling, B. P. Flannery, *Numerical Recipies in Fortran90: The Art of Parallel Scientific Computing*, Volume 2 of *Fortran Numerical Recipies*, (Cambridge University Press, 1992)
- [19] S. Kawabata, Comp. Phys. Comm. **41**, 127 (1986).
- [20] MINAMI-TATEYA Group, *GRACE Manual*, KEK Report 92-19.
- [21] S. Veseli, Comp. Phys. Comm. **108**, 9 (1998).
- [22] R. Kleiss, R. Pittau, *Weight Optimization in Multichannel Monte Carlo*, Comp. Phys. Comm. **83**, 141 (1994).
- [23] George Marsaglia, *The Marsaglia Random Number CD-ROM*, FSU, Dept. of Statistics and SCRI, 1996.
- [24] Y. L. Luke, *Mathematical Functions and their Approximations*, Academic Press, New York, 1975.
- [25] R. Kleiss, W. J. Stirling, S. D. Ellis, *A New Monte Carlo Treatment of Multiparticle Phase Space at High Energies*, Comp. Phys. Comm. **40**, 359 (1986).