

O'Mega: Optimal Monte-Carlo Event Generation Amplitudes

Thorsten Ohl*

Institut für Theoretische Physik und Astrophysik
Julius-Maximilians-Universität Würzburg
Emil-Hilb-Weg 22, 97074 Würzburg, Germany

Jürgen Reuter†

DESY Theory Group, Notkestr. 85, 22603 Hamburg, Germany

Wolfgang Kilian^{c,‡}

Theoretische Physik 1
Universität Siegen
Walter-Flex-Str. 3, 57068 Siegen, Germany

with contributions from Christian Speckner^{d,§}
as well as Christian Schwinn et al.

unpublished draft, printed 11/14/2013, 10:38

Abstract

...

*ohl@physik.uni-wuerzburg.de, <http://physik.uni-wuerzburg.de/ohl>

†juergen.reuter@desy.de

‡kilian@physik.uni-siegen.de

§cnspeckn@googlemail.com

Copyright © 1999-2013 by

- Wolfgang Kilian <kilian@hep.physik.uni-siegen.de>
- Thorsten Ohl <ohl@physik.uni-wuerzburg.de>
- Jürgen Reuter <juergen.reuter@desy.de>

WHIZARD is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2, or (at your option) any later version.

WHIZARD is distributed in the hope that it will be useful, but *without any warranty*; without even the implied warranty of *merchantability* or *fitness for a particular purpose*. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.

Revision Control

CONTENTS

1	INTRODUCTION	1
1.1	<i>Complexity</i>	1
1.2	<i>Ancestors</i>	2
1.3	<i>Architecture</i>	2
1.3.1	<i>General purpose libraries</i>	2
1.3.2	<i>O'Mega</i>	2
1.3.3	<i>Abstract interfaces</i>	3
1.3.4	<i>Models</i>	3
1.3.5	<i>Targets</i>	4
1.3.6	<i>Applications</i>	4
1.4	<i>The Big To Do Lists</i>	4
1.4.1	<i>Required</i>	4
1.4.2	<i>Useful</i>	4
1.4.3	<i>Future Features</i>	4
1.4.4	<i>Science Fiction</i>	5
2	TUPLES AND POLYTUPLES	6
2.1	<i>Interface of Tuple</i>	6
2.2	<i>Implementation of Tuple</i>	9
2.2.1	<i>Typesafe Combinatorics</i>	10
2.2.2	<i>Pairs</i>	10
2.2.3	<i>Triples</i>	12
2.2.4	<i>Pairs and Triples</i>	13
2.2.5	<i>... and All The Rest</i>	15
3	TOPOLOGIES	19
3.1	<i>Interface of Topology</i>	19
3.1.1	<i>Diagnostics: Counting Diagrams and Factorizations for $\sum_n \lambda_n \phi^n$</i>	20
3.1.2	<i>Emulating HELAC</i>	21
3.2	<i>Implementation of Topology</i>	21
3.2.1	<i>Factorizing Diagrams for ϕ^3</i>	22
3.2.2	<i>Factorizing Diagrams for $\sum_n \lambda_n \phi^n$</i>	25
3.2.3	<i>Factorizing Diagrams for ϕ^4</i>	27
3.2.4	<i>Factorizing Diagrams for $\phi^3 + \phi^4$</i>	27
3.2.5	<i>Diagnostics: Counting Diagrams and Factorizations for $\sum_n \lambda_n \phi^n$</i>	28
3.2.6	<i>Emulating HELAC</i>	34

4	DIRECTED ACYCLICAL GRAPHS	36
4.1	<i>Interface of DAG</i>	36
4.1.1	<i>Forests</i>	36
4.1.2	<i>DAGs</i>	38
4.1.3	<i>Graded Sets, Forests & DAGs</i>	40
4.2	<i>Implementation of DAG</i>	41
4.2.1	<i>The Forest Functor</i>	43
4.2.2	<i>Gradings</i>	43
4.2.3	<i>The DAG Functor</i>	45
5	MOMENTA	51
5.1	<i>Interface of Momentum</i>	51
5.1.1	<i>Scattering Kinematics</i>	53
5.1.2	<i>Decay Kinematics</i>	54
5.2	<i>Implementation of Momentum</i>	55
5.2.1	<i>Lists of Integers</i>	56
5.2.2	<i>Bit Fiddlings</i>	62
5.2.3	<i>Whizard</i>	67
5.2.4	<i>Suggesting a Default Implementation</i>	68
6	CASCADES	69
6.1	<i>Interface of Cascade_syntax</i>	69
6.2	<i>Implementation of Cascade_syntax</i>	69
6.3	<i>Lexer</i>	71
6.4	<i>Parser</i>	72
6.5	<i>Interface of Cascade</i>	73
6.6	<i>Implementation of Cascade</i>	74
7	COLOR	81
7.1	<i>Interface of Color</i>	81
7.1.1	<i>Quantum Numbers</i>	81
7.1.2	<i>Color Flows</i>	81
7.2	<i>Implementation of Color</i>	82
7.2.1	<i>Quantum Numbers</i>	82
7.2.2	<i>Color Flows</i>	84
8	FUSIONS	89
8.1	<i>Interface of Fusion</i>	89
8.1.1	<i>Multiple Amplitudes</i>	92
8.1.2	<i>Tags</i>	94
8.2	<i>Implementation of Fusion</i>	95
8.2.1	<i>Fermi Statistics</i>	96
8.2.2	<i>Dirac Fermions</i>	96
8.2.3	<i>Tags</i>	98
8.2.4	<i>Tagged, the Fusion.Make Functor</i>	100
8.2.5	<i>Fusions with Majorana Fermions</i>	127
8.2.6	<i>Multiple Amplitudes</i>	129

9	LORENTZ REPRESENTATIONS, COUPLINGS, MODELS AND TARGETS	137
9.1	<i>Interface of Coupling</i>	137
9.1.1	<i>Propagators</i>	137
9.1.2	<i>Vertices</i>	139
9.1.3	<i>Gauge Couplings</i>	142
9.1.4	<i>SU(2) Gauge Bosons</i>	152
9.1.5	<i>Quartic Couplings and Auxiliary Fields</i>	154
9.1.6	<i>Gravitinos and supersymmetric currents</i>	155
9.1.7	<i>Perturbative Quantum Gravity and Kaluza-Klein Interactions</i>	155
9.1.8	<i>Dependent Parameters</i>	168
9.1.9	<i>More Exotic Couplings</i>	174
9.2	<i>Interface of Model</i>	174
9.2.1	<i>General Quantum Field Theories</i>	174
9.2.2	<i>Mutable Quantum Field Theories</i>	177
9.2.3	<i>Gauge Field Theories</i>	178
9.2.4	<i>Gauge Field Theories with Broken Gauge Symmetries</i>	179
9.3	<i>Interface of Target</i>	180
10	CONSERVED QUANTUM NUMBERS	182
10.1	<i>Interface of Charges</i>	182
10.1.1	<i>Abstract Type</i>	182
10.1.2	<i>Trivial Realisation</i>	182
10.1.3	<i>Nontrivial Realisations</i>	182
10.2	<i>Implementation of Charges</i>	183
11	COLORIZATION	185
11.1	<i>Interface of Colorize</i>	185
11.1.1	<i>...</i>	185
11.2	<i>Implementation of Colorize</i>	185
11.2.1	<i>Colorizing a Monochrome Model</i>	185
11.2.2	<i>Colorizing a Monochrome Gauge Model</i>	209
12	PROCESSES	212
12.1	<i>Interface of Process</i>	212
12.2	<i>Implementation of Process</i>	213
12.2.1	<i>Select Charge Conserving Processes</i>	214
12.2.2	<i>Parsing Process Descriptions</i>	214
12.2.3	<i>Remove Duplicate Final States</i>	216
13	HARDCODED MODELS	220
13.1	<i>Interface of Modeltools</i>	220
13.1.1	<i>Compilation</i>	220
13.1.2	<i>Mutable Models</i>	220
13.2	<i>Implementation of Modeltools</i>	221
13.2.1	<i>Compilation</i>	221
13.2.2	<i>Mutable Models</i>	225
13.3	<i>Interface of Modellib_SM</i>	227
13.3.1	<i>Hardcoded Models</i>	227
13.4	<i>Implementation of Modellib_SM</i>	228

13.4.1	ϕ^3	228
13.4.2	$\lambda_3\phi^3 + \lambda_4\phi^4$	229
13.4.3	Quantum Electro Dynamics	230
13.4.4	Quantum Chromo Dynamics	233
13.4.5	Complete Minimal Standard Model (Unitarity Gauge)	237
13.4.6	Complete Minimal Standard Model (including some extensions)	239
13.4.7	Incomplete Standard Model in R_ξ Gauge	253
13.4.8	QCD with electroweak insertions.	255
13.4.9	Groves	265
13.4.10	MSM With Cloned Families	270
13.5	Interface of Modellib_BSM	270
13.5.1	More Hardcoded BSM Models	270
13.6	Implementation of Modellib_BSM	271
13.6.1	Littlest Higgs Model	272
13.6.2	Three-Site Higgsless Model	381
13.6.3	2HDM with and without non-trivial flavor structure	396
13.6.4	Complete Minimal Standard Model including additional Resonances	414
13.7	Interface of Modellib_MSSM	429
13.7.1	More Hardcoded Models	429
13.8	Implementation of Modellib_MSSM	429
13.8.1	Minimal Supersymmetric Standard Model	429
13.9	Interface of Modellib_NMSSM	480
13.9.1	Extended Supersymmetric Models	480
13.10	Implementation of Modellib_NMSSM	480
13.10.1	Next-to-Minimal Supersymmetric Standard Model	480
13.11	Interface of Modellib_PSSSM	510
13.11.1	Extended Supersymmetric Models	510
13.12	Implementation of Modellib_PSSSM	511
13.12.1	Extended Supersymmetric Standard Model(s)	511
14	COMPHEP MODELS	549
14.1	Interface of Comphep_syntax	549
14.2	Implementation of Comphep_syntax	549
14.3	Lexer	551
14.4	Parser	552
14.5	Interface of Comphep	553
14.6	Implementation of Comphep	553
15	HARDCODED TARGETS	563
15.1	Interface of Targets	563
15.1.1	Supported Targets	563
15.1.2	Potential Targets	563
15.2	Implementation of Targets	563
15.2.1	Fortran 90/95	564
15.2.2	O'Mega Virtual Machine	638
15.2.3	C	638
15.2.4	O'Caml	638
15.2.5	L ^A T _E X	639

15.3	<i>Interface of Targets_Kmatrix</i>	640
15.4	<i>Implementation of Targets_Kmatrix</i>	640
16	PHASE SPACE	653
16.1	<i>Interface of Phasespace</i>	653
16.2	<i>Implementation of Phasespace</i>	654
16.2.1	<i>Tools</i>	654
16.2.2	<i>Phase Space Parameterization Trees</i>	654
17	WHIZARD	660
17.1	<i>Interface of Whizard</i>	660
17.2	<i>Implementation of Whizard</i>	660
17.2.1	<i>Building Trees</i>	661
17.2.2	<i>Merging Homomorphic Trees</i>	662
17.2.3	<i>Printing Trees</i>	663
17.2.4	<i>Process Dispatcher</i>	665
17.2.5	<i>Makefile</i>	667
18	APPLICATIONS	669
18.1	<i>Sample</i>	669
18.2	<i>Interface of Omega</i>	669
18.3	<i>Implementation of Omega</i>	669
18.3.1	<i>Main Program</i>	671
18.4	<i>Implementation of Omega_QED</i>	675
18.5	<i>Implementation of Omega_SM</i>	675
18.6	<i>Implementation of Omega_SYM</i>	675
A	REVISION CONTROL	684
A.1	<i>Interface of RCS</i>	684
A.2	<i>Implementation of RCS</i>	685
B	AUTOTOOLS	687
B.1	<i>Interface of Config</i>	687
B.2	<i>Implementation of Config</i>	687
C	TEXTUAL OPTIONS	688
C.1	<i>Interface of Options</i>	688
C.2	<i>Implementation of Options</i>	688
D	PROGRESS REPORTS	690
D.1	<i>Interface of Progress</i>	690
D.2	<i>Implementation of Progress</i>	690
E	MORE ON FILENAMES	693
E.1	<i>Interface of ThoFilename</i>	693
E.2	<i>Implementation of ThoFilename</i>	693
F	CACHE FILES	694
F.1	<i>Interface of Cache</i>	694
F.2	<i>Implementation of Cache</i>	695

G	MORE ON LISTS	698
	<i>G.1 Interface of ThoList</i>	698
	<i>G.2 Implementation of ThoList</i>	700
H	MORE ON ARRAYS	706
	<i>H.1 Interface of ThoArray</i>	706
	<i>H.2 Implementation of ThoArray</i>	706
I	MORE ON STRINGS	709
	<i>I.1 Interface of ThoString</i>	709
	<i>I.2 Implementation of ThoString</i>	709
J	POLYMORPHIC MAPS	712
	<i>J.1 Interface of Pmap</i>	712
	<i>J.2 Implementation of Pmap</i>	713
	<i>J.3 Interface of Partial</i>	722
	<i>J.4 Implementation of Partial</i>	723
K	TRIES	725
	<i>K.1 Interface of Trie</i>	725
	<i>K.1.1 Monomorphically</i>	725
	<i>K.1.2 New in O'Caml 3.08</i>	725
	<i>K.1.3 O'Mega customization</i>	726
	<i>K.1.4 Polymorphically</i>	726
	<i>K.1.5 O'Mega customization</i>	727
	<i>K.2 Implementation of Trie</i>	727
	<i>K.2.1 Monomorphically</i>	727
	<i>K.2.2 O'Mega customization</i>	730
	<i>K.2.3 Polymorphically</i>	730
	<i>K.2.4 O'Mega customization</i>	733
L	TENSOR PRODUCTS	734
	<i>L.1 Interface of Product</i>	734
	<i>L.1.1 Lists</i>	734
	<i>L.1.2 Sets</i>	734
	<i>L.2 Implementation of Product</i>	735
	<i>L.2.1 Lists</i>	735
	<i>L.2.2 Sets</i>	736
M	(FIBER) BUNDLES	737
	<i>M.1 Interface of Bundle</i>	737
	<i>M.2 Implementation of Bundle</i>	739
N	POWER SETS	741
	<i>N.1 Interface of PowSet</i>	741
	<i>N.2 Implementation of PowSet</i>	742

O	COMBINATORICS	745
O.1	<i>Interface of Combinatorics</i>	745
O.1.1	<i>Simple Combinatorial Functions</i>	745
O.1.2	<i>Partitions</i>	745
O.1.3	<i>Choices</i>	747
O.1.4	<i>Permutations</i>	747
O.2	<i>Implementation of Combinatorics</i>	747
O.2.1	<i>Simple Combinatorial Functions</i>	748
O.2.2	<i>Partitions</i>	749
O.2.3	<i>Choices</i>	752
O.2.4	<i>Permutations</i>	753
O.3	<i>Interface of Permutation</i>	754
O.4	<i>Implementation of Permutation</i>	755
P	PARTITIONS	760
P.1	<i>Interface of Partition</i>	760
P.2	<i>Implementation of Partition</i>	760
Q	TREES	762
Q.1	<i>Interface of Tree</i>	763
Q.1.1	<i>Abstract Data Type</i>	763
Q.1.2	<i>Homomorphisms</i>	764
Q.1.3	<i>Output</i>	764
Q.2	<i>Implementation of Tree</i>	765
Q.2.1	<i>Abstract Data Type</i>	765
Q.2.2	<i>Homomorphisms</i>	767
Q.2.3	<i>Output</i>	767
Q.2.4	<i>Least Squares Layout</i>	771
R	DEPENDENCY TREES	776
R.1	<i>Interface of Tree2</i>	776
R.2	<i>Implementation of Tree2</i>	776
S	CONSISTENCY CHECKS	777
T	COMPLEX NUMBERS	778
U	ALGEBRA	779
U.1	<i>Interface of Algebra</i>	779
U.1.1	<i>Coefficients</i>	779
U.1.2	<i>Naive Rational Arithmetic</i>	779
U.1.3	<i>Expressions: Terms, Rings and Linear Combinations</i>	780
U.2	<i>Implementation of Algebra</i>	782
U.2.1	<i>Coefficients</i>	782
U.2.2	<i>Naive Rational Arithmetic</i>	782
U.2.3	<i>Expressions: Terms, Rings and Linear Combinations</i>	783
V	SIMPLE LINEAR ALGEBRA	789
V.1	<i>Interface of Linalg</i>	789
V.2	<i>Implementation of Linalg</i>	789
V.2.1	<i>LU Decomposition</i>	790

W TALK TO THE WHIZARD . . .	794
X FORTRAN LIBRARIES	795
X.1 Trivia	795
X.1.1 Inner Product	795
X.1.2 Spinor Vector Space	796
X.1.3 Norm	800
X.2 Spinors Revisited	800
X.2.1 Spinor Vector Space	801
X.2.2 Norm	804
X.3 Vectorspinors	804
X.3.1 Vectorspinor Vector Space	805
X.3.2 Norm	809
X.4 Vectors and Tensors	809
X.4.1 Constructors	810
X.4.2 Inner Products	811
X.4.3 Not Entirely Inner Products	812
X.4.4 Outer Products	813
X.4.5 Vector Space	814
X.4.6 Norm	821
X.4.7 Conjugation	821
X.4.8 ϵ -Tensors	822
X.4.9 Utilities	825
X.5 Polarization vectors	825
X.6 Polarization vectors revisited	828
X.7 Symmetric Tensors	830
X.7.1 Vector Space	831
X.8 Symmetric Polarization Tensors	835
X.9 Couplings	837
X.9.1 Triple Gauge Couplings	841
X.9.2 Quadruple Gauge Couplings	841
X.9.3 Scalar Current	842
X.9.4 Triple Vector Couplings	842
X.10 Graviton Couplings	846
X.11 Tensor Couplings	847
X.12 Scalar-Vector Dim-5 Couplings	847
X.13 Spinor Couplings	850
X.13.1 Fermionic Vector and Axial Couplings	851
X.13.2 Fermionic Scalar and Pseudo Scalar Couplings	864
X.13.3 On Shell Wave Functions	868
X.13.4 Off Shell Wave Functions	871
X.13.5 Propagators	872
X.14 Spinor Couplings Revisited	875
X.14.1 Fermionic Vector and Axial Couplings	876
X.14.2 Fermionic Scalar and Pseudo Scalar Couplings	882
X.14.3 Couplings for BRST Transformations	884
X.14.4 Gravitino Couplings	891
X.14.5 Gravitino 4-Couplings	913
X.14.6 On Shell Wave Functions	923
X.14.7 Off Shell Wave Functions	926

<i>X.14.8 Propagators</i>	926
<i>X.15 Polarization vectorspinors</i>	928
<i>X.16 Color</i>	932
<i>X.16.1 Color Sum</i>	932
<i>X.17 Utilities</i>	933
<i>X.17.1 Helicity Selection Rule Heuristics</i>	933
<i>X.17.2 Diagnostics</i>	934
<i>X.17.3 Obsolete Summation</i>	939
<i>X.18 omega95</i>	941
<i>X.19 omega95 Revisited</i>	942
<i>X.20 Testing</i>	942
<i>X.21 O'Mega Virtual Machine</i>	966
<i>X.21.1 Memory Layout</i>	967
<i>X.21.2 Instruction Set</i>	967
Y INDEX	971

—1—

INTRODUCTION

1.1 Complexity

There are

$$P(n) = \frac{2^n - 2}{2} - n = 2^{n-1} - n - 1 \quad (1.1)$$

independent internal momenta in a n -particle scattering amplitude [1]. This grows much slower than the number

$$F(n) = (2n - 5)!! = (2n - 5) \cdot (2n - 7) \cdot \dots \cdot 3 \cdot 1 \quad (1.2)$$

of tree Feynman diagrams in vanilla ϕ^3 (see table 1.1). There are no known corresponding expressions for theories with more than one particle type. However, empirical evidence from numerical studies [1, 2] as well as explicit counting results from O’Mega suggest

$$P^*(n) \propto 10^{n/2} \quad (1.3)$$

while the factorial growth of the number of Feynman diagrams remains unchecked, of course.

n	$P(n)$	$F(n)$
4	3	3
5	10	15
6	25	105
7	56	945
8	119	10395
9	246	135135
10	501	2027025
11	1012	34459425
12	2035	654729075
13	4082	13749310575
14	8177	316234143225
15	16368	7905853580625
16	32751	213458046676875

Table 1.1: The number of ϕ^3 Feynman diagrams $F(n)$ and independent poles $P(n)$.

The number of independent momenta in an amplitude is a better measure for the complexity of the amplitude than the number of Feynman diagrams, since there can be substantial cancellations among the latter. Therefore it should be possible to express the scattering amplitude more compactly than by a sum over Feynman diagrams.

1.2 Ancestors

Some of the ideas that O’Mega is based on can be traced back to HELAS [5]. HELAS builds Feynman amplitudes by recursively forming off-shell ‘wave functions’ from joining external lines with other external lines or off-shell ‘wave functions’.

The program Madgraph [6] automatically generates Feynman diagrams and writes a Fortran program corresponding to their sum. The amplitudes are calculated by calls to HELAS [5]. Madgraph uses one straightforward optimization: no statement is written more than once. Since each statement corresponds to a collection of trees, this optimization is very effective for up to four particles in the final state. However, since the amplitudes are given as a sum of Feynman diagrams, this optimization can, by design, *not* remove the factorial growth and is substantially weaker than the algorithms of [1, 2] and the algorithm of O’Mega for more particles in the final state.

Then ALPHA [1] (see also the slightly modified variant [2]) provided a numerical algorithm for calculating scattering amplitudes and it could be shown empirically, that the calculational costs are rising with a power instead of factorially.

1.3 Architecture

1.3.1 General purpose libraries

Functions that are not specific to O’Mega and could be part of the O’Caml standard library

ThoList : (mostly) simple convenience functions for lists that are missing from the standard library module *List* (section G, p. 698)

Product : efficient tensor products for lists and sets (section L, p. 734)

Combinatorics : combinatorical formulae, sets of subsets, etc. (section O, p. 745)

1.3.2 O’Mega

The non-trivial algorithms that constitute O’Mega:

DAG : Directed Acyclical Graphs (section 4, p. 36)

Topology : unusual enumerations of unflavored tree diagrams (section 3, p. 19)

Momentum : finite sums of external momenta (section 5, p. 51)




Figure 1.1: Module dependencies in O'Mega.

Fusion : off shell wave functions (section 8, p. 89)

Omega : functor constructing an application from a model and a target (section 18, p. 669)

1.3.3 Abstract interfaces

The domains and co-domains of functors (section 9, p. 137)

Coupling : all possible couplings (not comprehensive yet)

Model : physical models

Target : target programming languages

1.3.4 Models

(section 13, p. 220)

Modellib_SM.QED : Quantum Electrodynamics

Modellib_SM.QCD : Quantum Chromodynamics (not complete yet)

Modellib_SM.SM : Minimal Standard Model (not complete yet)

etc.

1.3.5 Targets

Any programming language that supports arithmetic and a textual representation of programs can be targeted by O’Caml. The implementations translate the abstract expressions derived by *Fusion* to expressions in the target (section 15, p. 563).

Targets.Fortran : Fortran95 language implementation, calling subroutines

Other targets could come in the future: C, C++, O’Caml itself, symbolic manipulation languages, etc.

1.3.6 Applications

(section 18, p. 669)

1.4 The Big To Do Lists

1.4.1 Required

All features required for leading order physics applications are in place.

1.4.2 Useful

1. select allowed helicity combinations for massless fermions
2. Weyl-Van der Waerden spinors
3. speed up helicity sums by using discrete symmetries
4. general triple and quartic vector couplings
5. diagnostics: count corresponding Feynman diagrams more efficiently for more than ten external lines
6. recognize potential cascade decays (τ , b , etc.)
 - warn the user to add additional
 - kill fusions (at runtime), that contribute to a cascade
7. complete standard model in R_ξ -gauge
8. groves (the simple method of cloned generations works)

1.4.3 Future Features

1. investigate if unpolarized squared matrix elements can be calculated faster as traces of density matrices. Unfortunately, the answer appears to be *no* for fermions and *up to a constant factor* for massive vectors. Since the number of fusions in the amplitude grows like $10^{n/2}$, the number of fusions in the squared matrix element grows like 10^n . On the other hand, there are $2^{\#\text{fermions} + \#\text{massless vectors}} \cdot 3^{\#\text{massive vectors}}$ terms in the helicity sum,

which grows *slower* than $10^{n/2}$. The constant factor is probably also not favorable. However, there will certainly be asymptotic gains for sums over gauge (and other) multiplets, like color sums.

2. compile Feynman rules from Lagrangians
3. evaluate amplitudes in O'Caml by compiling it to three address code for a virtual machine

```

type mem = scalar array × spinor array × spinor array × vector array
type instr =
  — VSS of int × int × int
  — SVS of int × int × int
  — AVA of int × int × int
  ...

```

this could be as fast as [1] or [2].

4. a virtual machine will be useful for other target as well, because native code appears to become too large for most compilers for more than ten external particles. Bytecode might even be faster due to improved cache locality.
5. use the virtual machine in O'Giga

1.4.4 *Science Fiction*

1. numerical and symbolical loop calculations with O'TERA: O'MEGA TOOL FOR EVALUATING RENORMALIZED AMPLITUDES

—2—

TUPLES AND POLYTUPLES

2.1 Interface of Tuple

The *Tuple.Poly* interface abstracts the notion of tuples with variable arity. Simple cases are binary polytuples, which are simply pairs and indefinite polytuples, which are nothing but lists. Another example is the union of pairs and triples. The interface is very similar to *List* from the O’Caml standard library, but the *Tuple.Poly* signature allows a more fine grained control of arities. The latter provides typesafe linking of models, targets and topologies.

```
module type Mono =
sig
  type  $\alpha$  t

  val arity :  $\alpha$  t  $\rightarrow$  int
  val max_arity : int

  val compare : ( $\alpha \rightarrow \alpha \rightarrow$  int)  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$  t  $\rightarrow$  int

  val for_all : ( $\alpha \rightarrow$  bool)  $\rightarrow$   $\alpha$  t  $\rightarrow$  bool

  val map : ( $\alpha \rightarrow \beta$ )  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\beta$  t
  val iter : ( $\alpha \rightarrow$  unit)  $\rightarrow$   $\alpha$  t  $\rightarrow$  unit
  val fold_left : ( $\alpha \rightarrow \beta \rightarrow \alpha$ )  $\rightarrow$   $\alpha \rightarrow \beta$  t  $\rightarrow$   $\alpha$ 
  val fold_right : ( $\alpha \rightarrow \beta \rightarrow \beta$ )  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\beta \rightarrow \beta$ 
```

We have applications, where no sensible initial value can be defined:

```
val fold_left_internal : ( $\alpha \rightarrow \alpha \rightarrow \alpha$ )  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$ 
val fold_right_internal : ( $\alpha \rightarrow \alpha \rightarrow \alpha$ )  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$ 

val map2 : ( $\alpha \rightarrow \beta \rightarrow \gamma$ )  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\beta$  t  $\rightarrow$   $\gamma$  t
val split : ( $\alpha \times \beta$ ) t  $\rightarrow$   $\alpha$  t  $\times$   $\beta$  t
```

The distributive tensor product expands a tuple of lists into list of tuples, e. g. for binary tuples:

$$\text{product}([x_1; x_2], [y_1; y_2]) = [(x_1, y_1); (x_1, y_2); (x_2, y_1); (x_2, y_2)] \quad (2.1)$$

NB: *product_fold* is usually much more memory efficient than the combination of *product* and *List.fold_right* for large sets.

```
val product :  $\alpha$  list t  $\rightarrow$   $\alpha$  t list
```

```
val product_fold : (α t → β → β) → α list t → β → β
```

For homogeneous tuples the *power* function could trivially be built from *product*, e. g.:

$$power [x_1; x_2] = product ([x_1; x_2], [x_1; x_2]) = [(x_1, x_1); (x_1, x_2); (x_2, x_1); (x_2, x_2)] \quad (2.2)$$

but it is also well defined for polytuples, e. g. for pairs and triples

$$power [x_1; x_2] = product ([x_1; x_2], [x_1; x_2]) \cup product ([x_1; x_2], [x_1; x_2], [x_1; x_2]) \quad (2.3)$$

For tuples and polytuples with bounded arity, the *power* and *power_fold* functions terminate. In polytuples with unbounded arity, the *power* function always raises *No_termination*. *power_fold* also raises *No_termination*, but could be changed to run until the argument function raises an exception. However, if we need this behaviour, we should implemente *power_iter* instead.

```
val power : α list → α t list
val power_fold : (α t → β → β) → α list → β → β
```

We can also identify all (poly)tuples with permuted elements and return only one representative, e. g.:

$$sym_power [x_1; x_2] = [(x_1, x_1); (x_1, x_2); (x_2, x_2)] \quad (2.4)$$

NB: this function has not yet been implemented, because O'Mega only needs the more efficient special case *graded_sym_power*.

If a set X is graded (i. e. there is a map $\phi : X \rightarrow \mathbf{N}$, called *rank* below), the results of *power* or *sym_power* can canonically be filtered by requiring that the sum of the ranks in each (poly)tuple has one chosen value. Implementing such a function directly is much more efficient than constructing and subsequently disregarding many (poly)tuples. The elements of rank n are at offset $(n - 1)$ in the array. The array is assumed to be *immutable*, even if O'Cam1 doesn't support immutable arrays. NB: *graded_power* has not yet been implemented, because O'Mega only needs *graded_sym_power*.

```
type α graded = α list array
val graded_sym_power : int → α graded → α t list
val graded_sym_power_fold : int → (α t → β → β) → α graded →
  β → β
```



We hope to be able to avoid the next one in the long run, because it mildly breaks typesafety for arities. Unfortunately, we're still working on it ...

```
val to_list : α t → α list
```



The next one is only used for Fermi statistics below, but can not be implemented if there are no binary tuples. It must be retired as soon as possible.

```
val of2_kludge : α → α → α t
```

```

    val rcs : RCS.t
  end

module type Poly =
  sig
    include Mono
    exception Mismatched_arity
    exception No_termination
  end

module type Binary =
  sig
    include Poly (* should become Mono! *)
    val of2 :  $\alpha \rightarrow \alpha \rightarrow \alpha t$ 
  end

module Binary : Binary

module type Ternary =
  sig
    include Mono
    val of3 :  $\alpha \rightarrow \alpha \rightarrow \alpha \rightarrow \alpha t$ 
  end

module Ternary : Ternary

type  $\alpha$  pair_or_triple = T2 of  $\alpha \times \alpha$  | T3 of  $\alpha \times \alpha \times \alpha$ 

module type Mixed23 =
  sig
    include Poly
    val of2 :  $\alpha \rightarrow \alpha \rightarrow \alpha t$ 
    val of3 :  $\alpha \rightarrow \alpha \rightarrow \alpha \rightarrow \alpha t$ 
  end

module Mixed23 : Mixed23

module type Nary =
  sig
    include Poly
    val of2 :  $\alpha \rightarrow \alpha \rightarrow \alpha t$ 
    val of3 :  $\alpha \rightarrow \alpha \rightarrow \alpha \rightarrow \alpha t$ 
    val of_list :  $\alpha \text{ list} \rightarrow \alpha t$ 
  end

module Unbounded_Nary : Nary

module type Bound = sig val max_arity : int end
module Nary (B : Bound) : Nary

```



For completeness sake, we could add most of the *List* signature

- val length : $\alpha t \rightarrow int$
- val hd : $\alpha t \rightarrow \alpha$
- val nth : $\alpha t \rightarrow int \rightarrow \alpha$
- val rev : $\alpha t \rightarrow \alpha t$

- `val rev_map : ($\alpha \rightarrow \beta$) $\rightarrow \alpha\ t \rightarrow \beta\ t$`
- `val iter2 : ($\alpha \rightarrow \beta \rightarrow \text{unit}$) $\rightarrow \alpha\ t \rightarrow \beta\ t \rightarrow \text{unit}$`
- `val rev_map2 : ($\alpha \rightarrow \beta \rightarrow \gamma$) $\rightarrow \alpha\ t \rightarrow \beta\ t \rightarrow \gamma\ t$`
- `val fold_left2 : ($\alpha \rightarrow \beta \rightarrow \gamma \rightarrow \alpha$) $\rightarrow \alpha \rightarrow \beta\ t \rightarrow \gamma\ t \rightarrow \alpha$`
- `val fold_right2 : ($\alpha \rightarrow \beta \rightarrow \gamma \rightarrow \gamma$) $\rightarrow \alpha\ t \rightarrow \beta\ t \rightarrow \gamma \rightarrow \gamma$`
- `val exists : ($\alpha \rightarrow \text{bool}$) $\rightarrow \alpha\ t \rightarrow \text{bool}$`
- `val for_all2 : ($\alpha \rightarrow \beta \rightarrow \text{bool}$) $\rightarrow \alpha\ t \rightarrow \beta\ t \rightarrow \text{bool}$`
- `val exists2 : ($\alpha \rightarrow \beta \rightarrow \text{bool}$) $\rightarrow \alpha\ t \rightarrow \beta\ t \rightarrow \text{bool}$`
- `val mem : $\alpha \rightarrow \alpha\ t \rightarrow \text{bool}$`
- `val memq : $\alpha \rightarrow \alpha\ t \rightarrow \text{bool}$`
- `val find : ($\alpha \rightarrow \text{bool}$) $\rightarrow \alpha\ t \rightarrow \alpha$`
- `val find_all : ($\alpha \rightarrow \text{bool}$) $\rightarrow \alpha\ t \rightarrow \alpha\ \text{list}$`
- `val assoc : $\alpha \rightarrow (\alpha \times \beta)\ t \rightarrow \beta$`
- `val assq : $\alpha \rightarrow (\alpha \times \beta)\ t \rightarrow \beta$`
- `val mem_assoc : $\alpha \rightarrow (\alpha \times \beta)\ t \rightarrow \text{bool}$`
- `val mem_assq : $\alpha \rightarrow (\alpha \times \beta)\ t \rightarrow \text{bool}$`
- `val combine : $\alpha\ t \rightarrow \beta\ t \rightarrow (\alpha \times \beta)\ t$`
- `val sort : ($\alpha \rightarrow \alpha \rightarrow \text{int}$) $\rightarrow \alpha\ t \rightarrow \alpha\ t$`
- `val stable_sort : ($\alpha \rightarrow \alpha \rightarrow \text{int}$) $\rightarrow \alpha\ t \rightarrow \alpha\ t$`

but only if we ever have too much time on our hand ...

2.2 Implementation of *Tuple*

```
let rcs_file = RCS.parse "Tuple" ["Tuples_of_fixed_and_indefinite_arity"]
{ RCS.revision = "$Revision: 4538$";
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
  RCS.author = "$Author: jr-reuter$";
  RCS.source
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg";
module type Mono =
sig
  type  $\alpha\ t$ 
  val arity :  $\alpha\ t \rightarrow \text{int}$ 
  val max_arity :  $\text{int}$ 
  val compare : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha\ t \rightarrow \alpha\ t \rightarrow \text{int}$ 
  val for_all : ( $\alpha \rightarrow \text{bool}$ )  $\rightarrow \alpha\ t \rightarrow \text{bool}$ 
  val map : ( $\alpha \rightarrow \beta$ )  $\rightarrow \alpha\ t \rightarrow \beta\ t$ 
  val iter : ( $\alpha \rightarrow \text{unit}$ )  $\rightarrow \alpha\ t \rightarrow \text{unit}$ 
  val fold_left : ( $\alpha \rightarrow \beta \rightarrow \alpha$ )  $\rightarrow \alpha \rightarrow \beta\ t \rightarrow \alpha$ 
  val fold_right : ( $\alpha \rightarrow \beta \rightarrow \beta$ )  $\rightarrow \alpha\ t \rightarrow \beta \rightarrow \beta$ 
  val fold_left_internal : ( $\alpha \rightarrow \alpha \rightarrow \alpha$ )  $\rightarrow \alpha\ t \rightarrow \alpha$ 
  val fold_right_internal : ( $\alpha \rightarrow \alpha \rightarrow \alpha$ )  $\rightarrow \alpha\ t \rightarrow \alpha$ 
```

```

val map2 : ( $\alpha \rightarrow \beta \rightarrow \gamma$ )  $\rightarrow \alpha\ t \rightarrow \beta\ t \rightarrow \gamma\ t$ 
val split : ( $\alpha \times \beta$ )  $t \rightarrow \alpha\ t \times \beta\ t$ 
val product :  $\alpha\ list\ t \rightarrow \alpha\ t\ list$ 
val product_fold : ( $\alpha\ t \rightarrow \beta \rightarrow \beta$ )  $\rightarrow \alpha\ list\ t \rightarrow \beta \rightarrow \beta$ 
val power :  $\alpha\ list \rightarrow \alpha\ t\ list$ 
val power_fold : ( $\alpha\ t \rightarrow \beta \rightarrow \beta$ )  $\rightarrow \alpha\ list \rightarrow \beta \rightarrow \beta$ 
type  $\alpha\ graded = \alpha\ list\ array$ 
val graded_sym_power :  $int \rightarrow \alpha\ graded \rightarrow \alpha\ t\ list$ 
val graded_sym_power_fold :  $int \rightarrow (\alpha\ t \rightarrow \beta \rightarrow \beta) \rightarrow \alpha\ graded \rightarrow \beta \rightarrow \beta$ 
val to_list :  $\alpha\ t \rightarrow \alpha\ list$ 
val of2_kludge :  $\alpha \rightarrow \alpha \rightarrow \alpha\ t$ 
val rcs :  $RCS.t$ 
end

module type Poly =
sig
  include Mono
  exception Mismatched_arity
  exception No_termination
end

```

2.2.1 Typesafe Combinatorics

Wrap the combinatorial functions with varying arities into typesafe functions with fixed arities. We could provide specialized implementations, but since we *know* that *Impossible* is *never* raised, the present approach is just as good (except for a tiny inefficiency).

```

exception Impossible of string
let impossible name = raise (Impossible name)

let choose2 set =
  List.map (function [x; y]  $\rightarrow (x, y) \mid - \rightarrow impossible\ "choose2"$ )
    (Combinatorics.choose 2 set)

let choose3 set =
  List.map (function [x; y; z]  $\rightarrow (x, y, z) \mid - \rightarrow impossible\ "choose3"$ )
    (Combinatorics.choose 3 set)

```

2.2.2 Pairs

```

module type Binary =
sig
  sig
    include Poly (* should become Mono! *)
    val of2 :  $\alpha \rightarrow \alpha \rightarrow \alpha\ t$ 
  end
end

module Binary =

```

```

struct
  let rcs = RCS.rename rcs_file "Tuple.Binary" ["Pairs"]

  type  $\alpha$  t =  $\alpha \times \alpha$ 

  let arity _ = 2
  let max_arity = 2

  let of2 x y = (x, y)

  let compare cmp (x1, y1) (x2, y2) =
    let cx = cmp x1 x2 in
    if cx  $\neq$  0 then
      cx
    else
      cmp y1 y2

  let for_all p (x, y) = p x  $\wedge$  p y

  let map f (x, y) = (f x, f y)
  let iter f (x, y) = f x; f y
  let fold_left f init (x, y) = f (f init x) y
  let fold_right f (x, y) init = f x (f y init)
  let fold_left_internal f (x, y) = f x y
  let fold_right_internal f (x, y) = f x y

  exception Mismatched_arity

  let map2 f (x1, y1) (x2, y2) = (f x1 x2, f y1 y2)

  let split ((x1, x2), (y1, y2)) = ((x1, y1), (x2, y2))

  let product (lx, ly) =
    Product.list2 (fun x y  $\rightarrow$  (x, y)) lx ly
  let product_fold f (lx, ly) init =
    Product.fold2 (fun x y  $\rightarrow$  f (x, y)) lx ly init

  let power l = product (l, l)
  let power_fold f l = product_fold f (l, l)

```

In the special case of binary fusions, the implementation is very concise.

```

type  $\alpha$  graded =  $\alpha$  list array

let fuse2 f set (i, j) acc =
  if i = j then
    List.fold_right (fun (x, y)  $\rightarrow$  f x y) (choose2 set.(pred i)) acc
  else
    Product.fold2 f set.(pred i) set.(pred j) acc

let graded_sym_power_fold rank f set acc =
  let max_rank = Array.length set in
  List.fold_right (fuse2 (fun x y  $\rightarrow$  f (of2 x y)) set)
    (Partition.pairs rank 1 max_rank) acc

let graded_sym_power rank set =
  graded_sym_power_fold rank (fun pair acc  $\rightarrow$  pair :: acc) set []

let to_list (x, y) = [x; y]

```

```

let of2_kludge = of2
exception No_termination
end

```

2.2.3 Triples

```

module type Ternary =
  sig
    include Mono
    val of3 :  $\alpha \rightarrow \alpha \rightarrow \alpha \rightarrow \alpha t$ 
  end

module Ternary =
  struct
    let rcs = RCS.rename rcs_file "Tuple.Ternary" ["Triples"]

    type  $\alpha t = \alpha \times \alpha \times \alpha$ 

    let arity _ = 3
    let max_arity = 3

    let of3 x y z = (x, y, z)

    let compare cmp (x1, y1, z1) (x2, y2, z2) =
      let cx = cmp x1 x2 in
      if cx  $\neq$  0 then
        cx
      else
        let cy = cmp y1 y2 in
        if cy  $\neq$  0 then
          cy
        else
          cmp z1 z2

    let for_all p (x, y, z) = p x  $\wedge$  p y  $\wedge$  p z

    let map f (x, y, z) = (f x, f y, f z)
    let iter f (x, y, z) = f x; f y; f z
    let fold_left f init (x, y, z) = f (f (f init x) y) z
    let fold_right f (x, y, z) init = f x (f y (f z init))
    let fold_left_internal f (x, y, z) = f (f x y) z
    let fold_right_internal f (x, y, z) = f x (f y z)

    exception Mismatched_arity

    let map2 f (x1, y1, z1) (x2, y2, z2) = (f x1 x2, f y1 y2, f z1 z2)

    let split ((x1, x2), (y1, y2), (z1, z2)) = ((x1, y1, z1), (x2, y2, z2))

    let product (lx, ly, lz) =
      Product.list3 (fun x y z  $\rightarrow$  (x, y, z)) lx ly lz
    let product_fold f (lx, ly, lz) init =
      Product.fold3 (fun x y z  $\rightarrow$  f (x, y, z)) lx ly lz init
  end

```

```

let power l = product (l, l, l)
let power_fold f l = product_fold f (l, l, l)

type  $\alpha$  graded =  $\alpha$  list array

let fuse3 f set (i, j, k) acc =
  if i = j then begin
    if j = k then
      List.fold_right (fun (x, y, z)  $\rightarrow$  f x y z) (choose3 set.(pred i)) acc
    else
      Product.fold2 (fun (x, y) z  $\rightarrow$  f x y z)
        (choose2 set.(pred i)) set.(pred k) acc
  end else begin
    if j = k then
      Product.fold2 (fun x (y, z)  $\rightarrow$  f x y z)
        set.(pred i) (choose2 set.(pred j)) acc
    else
      Product.fold3 (fun x y z  $\rightarrow$  f x y z)
        set.(pred i) set.(pred j) set.(pred k) acc
  end
end

let graded_sym_power_fold rank f set acc =
  let max_rank = Array.length set in
  List.fold_right (fuse3 (fun x y z  $\rightarrow$  f (of3 x y z)) set)
    (Partition.triples rank 1 max_rank) acc

let graded_sym_power rank set =
  graded_sym_power_fold rank (fun pair acc  $\rightarrow$  pair :: acc) set []

let of2_kludge _ = failwith "Tuple.Ternary.of2_kludge"

let to_list (x, y, z) = [x; y; z]
end

```

2.2.4 Pairs and Triples

```

type  $\alpha$  pair_or_triple = T2 of  $\alpha \times \alpha$  | T3 of  $\alpha \times \alpha \times \alpha$ 

module type Mixed23 =
  sig
    include Poly
    val of2 :  $\alpha \rightarrow \alpha \rightarrow \alpha t$ 
    val of3 :  $\alpha \rightarrow \alpha \rightarrow \alpha \rightarrow \alpha t$ 
  end

module Mixed23 =
  struct
    let rcs = RCS.rename rcs_file "Tuple.Mixed23"
      ["Mixed_pairs_and_triples"]

    type  $\alpha t$  =  $\alpha$  pair_or_triple

    let arity = function

```



```

| T2 _ → 2
| T3 _ → 3
let max_arity = 3

let of2 x y = T2 (x, y)
let of3 x y z = T3 (x, y, z)

let compare cmp m1 m2 =
  match m1, m2 with
  | T2 _, T3 _ → -1
  | T3 _, T2 _ → 1
  | T2 (x1, y1), T2 (x2, y2) →
    let cx = cmp x1 x2 in
    if cx ≠ 0 then
      cx
    else
      cmp y1 y2
  | T3 (x1, y1, z1), T3 (x2, y2, z2) →
    let cx = cmp x1 x2 in
    if cx ≠ 0 then
      cx
    else
      let cy = cmp y1 y2 in
      if cy ≠ 0 then
        cy
      else
        cmp z1 z2

let for_all p = function
| T2 (x, y) → p x ∧ p y
| T3 (x, y, z) → p x ∧ p y ∧ p z

let map f = function
| T2 (x, y) → T2 (f x, f y)
| T3 (x, y, z) → T3 (f x, f y, f z)

let iter f = function
| T2 (x, y) → f x; f y
| T3 (x, y, z) → f x; f y; f z

let fold_left f init = function
| T2 (x, y) → f (f init x) y
| T3 (x, y, z) → f (f (f init x) y) z

let fold_right f m init =
  match m with
  | T2 (x, y) → f x (f y init)
  | T3 (x, y, z) → f x (f y (f z init))

let fold_left_internal f m =
  match m with
  | T2 (x, y) → f x y
  | T3 (x, y, z) → f (f x y) z

```

```

let fold_right_internal f m =
  match m with
  | T2 (x, y) → f x y
  | T3 (x, y, z) → f x (f y z)

exception Mismatched_arity
let map2 f m1 m2 =
  match m1, m2 with
  | T2 (x1, y1), T2 (x2, y2) → T2 (f x1 x2, f y1 y2)
  | T3 (x1, y1, z1), T3 (x2, y2, z2) → T3 (f x1 x2, f y1 y2, f z1 z2)
  | T2 _, T3 _ | T3 _, T2 _ → raise Mismatched_arity

let split = function
  | T2 ((x1, x2), (y1, y2)) → (T2 (x1, y1), T2 (x2, y2))
  | T3 ((x1, x2), (y1, y2), (z1, z2)) → (T3 (x1, y1, z1), T3 (x2, y2, z2))

let product = function
  | T2 (lx, ly) → Product.list2 (fun x y → T2 (x, y)) lx ly
  | T3 (lx, ly, lz) → Product.list3 (fun x y z → T3 (x, y, z)) lx ly lz
let product_fold f m init =
  match m with
  | T2 (lx, ly) → Product.fold2 (fun x y → f (T2 (x, y))) lx ly init
  | T3 (lx, ly, lz) →
    Product.fold3 (fun x y z → f (T3 (x, y, z))) lx ly lz init

exception No_termination

let power_fold f l init =
  product_fold f (T2 (l, l)) (product_fold f (T3 (l, l, l)) init)
let power l =
  power_fold (fun m acc → m :: acc) l []

type  $\alpha$  graded =  $\alpha$  list array

let graded_sym_power_fold rank f set acc =
  let max_rank = Array.length set in
  List.fold_right (Binary.fuse2 (fun x y → f (of2 x y)) set)
    (Partition.pairs rank 1 max_rank)
    (List.fold_right (Ternary.fuse3 (fun x y z → f (of3 x y z)) set)
      (Partition.triples rank 1 max_rank) acc)

let graded_sym_power rank set =
  graded_sym_power_fold rank (fun pair acc → pair :: acc) set []

let to_list = function
  | T2 (x, y) → [x; y]
  | T3 (x, y, z) → [x; y; z]

let of2_kludge = of2
end

```

2.2.5 ... and All The Rest

module type *Nary* =

```

sig
  include Poly
  val of2 :  $\alpha \rightarrow \alpha \rightarrow \alpha t$ 
  val of3 :  $\alpha \rightarrow \alpha \rightarrow \alpha \rightarrow \alpha t$ 
  val of_list :  $\alpha list \rightarrow \alpha t$ 
end

module Nary (A : sig val max_arity : int end) =
struct
  let rcs = RCS.rename rcs_file "Tuple.Nary"
    ["Tuples_of_indefinite_arity"]

  type  $\alpha t = \alpha \times \alpha list$ 

  let arity (_, y) = succ (List.length y)
  let max_arity = A.max_arity

  let of2 x y = (x, [y])
  let of3 x y z = (x, [y; z])

  let of_list = function
    | x :: y → (x, y)
    | [] → invalid_arg "Tuple.Nary.of_list: empty"

  let compare cmp (x1, y1) (x2, y2) =
    let c = cmp x1 x2 in
    if c ≠ 0 then
      c
    else
      ThoList.compare ~cmp y1 y2

  let for_all p (x, y) = p x ∧ List.for_all p y

  let map f (x, y) = (f x, List.map f y)
  let iter f (x, y) = f x; List.iter f y
  let fold_left f init (x, y) = List.fold_left f (f init x) y
  let fold_right f (x, y) init = f x (List.fold_right f y init)
  let fold_left_internal f (x, y) = List.fold_left f x y
  let fold_right_internal f (x, y) =
    match List.rev y with
    | [] → x
    | y0 :: y_sans_y0 →
      f x (List.fold_right f (List.rev y_sans_y0) y0)

  exception Mismatched_arity

  let map2 f (x1, y1) (x2, y2) =
    try (f x1 x2, List.map2 f y1 y2) with
    | Invalid_argument _ → raise Mismatched_arity

  let split ((x1, x2), y12) =
    let y1, y2 = List.split y12 in
    ((x1, y1), (x2, y2))

  let product (xl, yl) =
    Product.list (function
      | x :: y → (x, y)

```

```

    | [] → failwith "Tuple.Nary.product" (xl :: yl)
let product_fold f (xl, yl) init =
  Product.fold (function
    | x :: y → f (x, y)
    | [] → failwith "Tuple.Nary.product_fold" (xl :: yl) init
  )
let bounded_power_fold f l init =
  List.fold_right (fun n → product_fold f (l, ThoList.clone (pred n) l))
    (ThoList.range 2 A.max_arity) init
let bounded_power l =
  bounded_power_fold (fun t acc → t :: acc) l []

exception No_termination
let unbounded_power_fold f l init = raise No_termination
let unbounded_power l = raise No_termination

let power_fold, power =
  if A.max_arity > 0 then
    (bounded_power_fold, bounded_power)
  else
    (unbounded_power_fold, unbounded_power)

type  $\alpha$  graded =  $\alpha$  list array

let fuse_n f set partition acc =
  let choose (n, r) =
    Printf.printf "chose: n=%d, r=%d, len=%d\n"
      n r (List.length set.(pred r));
    Combinatorics.choose n set.(pred r) in
  Product.fold (fun wfs → f (List.concat wfs))
    (List.map choose (ThoList.classify partition)) acc

let fuse_n f set partition acc =
  let choose (n, r) = Combinatorics.choose n set.(pred r) in
  Product.fold (fun wfs → f (List.concat wfs))
    (List.map choose (ThoList.classify partition)) acc

```



graded_sym_power_fold is well defined for unbounded arities as well: derive a reasonable replacement from *set*. The length of the flattened *set* is an upper limit, of course, but too pessimistic in most cases.

```

let graded_sym_power_fold rank f set acc =
  let max_rank = Array.length set in
  let degrees = ThoList.range 2 max_arity in
  let partitions =
    ThoList.flatmap
      (fun deg → Partition.tuples deg rank 1 max_rank) degrees in
  List.fold_right (fuse_n (fun wfs → f (of_list wfs))) set partitions acc

let graded_sym_power rank set =
  graded_sym_power_fold rank (fun pair acc → pair :: acc) set []

let to_list (x, y) = x :: y

```

```
    let of2_kludge = of2
  end
module type Bound = sig val max_arity : int end
module Unbounded_Nary = Nary (struct let max_arity = -1 end)
```

—3—

TOPOLOGIES

3.1 Interface of Topology

module type $T =$
 sig

partition is a collection of integers, with arity one larger than the arity of α *children* below. These arities can one fixed number corresponding to homogeneous tuples or a collection of tuples or lists.

type *partition*

partitions n returns the union of all $[n_1; n_2; \dots; n_d]$ with $1 \leq n_1 \leq n_2 \leq \dots \leq n_d \leq \lfloor n/2 \rfloor$ and

$$\sum_{i=1}^d n_i = n \quad (3.1)$$

for d from 3 to d_{\max} , where d_{\max} is a fixed number for each module implementing T . In particular, if `type partition = int × int × int`, then *partitions* n returns all (n_1, n_2, n_3) with $n_1 \leq n_2 \leq n_3$ and $n_1 + n_2 + n_3 = n$.

val *partitions* : int → partition list

A (poly)tuple as implemented by the modules in *Tuple*:

type α *children*

keystones externals returns all keystones for the amplitude with external states *externals* in the vanilla scalar theory with a

$$\sum_{3 \leq k \leq d_{\max}} \lambda_k \phi^k \quad (3.2)$$

interaction. One factor of the products is factorized. In particular, if

$$\text{type } \alpha \text{ children} = \alpha \text{ Tuple.Binary.t} = \alpha \times \alpha,$$

then *keystones externals* returns all keystones for the amplitude with external states *externals* in the vanilla scalar $\lambda\phi^3$ -theory.

val *keystones* : α list → (α list × α list children list) list

The maximal depth of subtrees for a given number of external lines.

```
val max_subtree : int → int
```

Only for diagnostics:

```
val inspect_partition : partition → int list
val rcs : RCS.t
```

```
end
```

```
module Binary : T with type α children = α Tuple.Binary.t
module Ternary : T with type α children = α Tuple.Ternary.t
module Mixed23 : T with type α children = α Tuple.Mixed23.t
module Nary : functor (B : Tuple.Bound) →
  (T with type α children = α Tuple.Nary(B).t)
```

3.1.1 Diagnostics: Counting Diagrams and Factorizations for $\sum_n \lambda_n \phi^n$

The number of diagrams for many particles can easily exceed the range of native integers. Even if we can not calculate the corresponding amplitudes, we want to check combinatorial factors. Therefore we code a functor that can use arbitrary implementations of integers.

```
module type Integer =
sig
  type t
  val zero : t
  val one : t
  val ( + ) : t → t → t
  val ( - ) : t → t → t
  val ( × ) : t → t → t
  val ( / ) : t → t → t
  val pred : t → t
  val succ : t → t
  val ( = ) : t → t → bool
  val ( ≠ ) : t → t → bool
  val ( < ) : t → t → bool
  val ( ≤ ) : t → t → bool
  val ( > ) : t → t → bool
  val ( ≥ ) : t → t → bool
  val of_int : int → t
  val to_int : t → int
  val to_string : t → string
  val compare : t → t → int
  val factorial : t → t
end
```

Of course, native integers will provide the fastest implementation:

```
module Int : Integer
```

```
module type Count =
```

```
sig
```

type *integer*

diagrams f d n returns the number of tree diagrams contributing to the n -point amplitude in vanilla scalar theory with

$$\sum_{3 \leq k \leq d \wedge f(k)} \lambda_k \phi^k \quad (3.3)$$

interaction. The default value of f returns **true** for all arguments.

val *diagrams* : ? $f : (integer \rightarrow bool) \rightarrow integer \rightarrow integer \rightarrow integer$
val *diagrams_via_keystones* : $integer \rightarrow integer \rightarrow integer$

$$\frac{1}{S(n_k, n - n_k)} \frac{1}{S(n_1, n_2, \dots, n_k)} \binom{n_1 + n_2 + \dots + n_k}{n_1, n_2, \dots, n_k} \quad (3.4)$$

val *keystones* : $integer\ list \rightarrow integer$

diagrams_via_keystones d n must produce the same results as *diagrams d n*. This is shown explicitly in tables 3.2, 3.3 and 3.4 for small values of d and n . The test program in appendix S can be used to verify this relation for larger values.

val *diagrams_per_keystone* : $integer \rightarrow integer\ list \rightarrow integer$

end

module *Count* : functor ($I : Integer$) $\rightarrow Count$ with type *integer* = $I.t$

3.1.2 Emulating HELAC

We can also proceed á la [2].

module *Helac* : functor ($B : Tuple.Bound$) \rightarrow
(T with type $\alpha\ children = \alpha\ Tuple.Nary(B).t$)



The following has never been tested, but it is no rocket science and should work anyway ...

module *Helac_Binary* : T with type $\alpha\ children = \alpha\ Tuple.Binary.t$

3.2 Implementation of Topology

```
let rcs_file = RCS.parse "Topology" ["Topologies"]
{ RCS.revision = "$Revision: 4538$";
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
  RCS.author = "$Author: jr-reuter$";
  RCS.source
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
```


n	$partitions\ n$
4	(1,1,2)
5	(1,2,2)
6	(1,2,3), (2,2,2)
7	(1,3,3), (2,2,3)
8	(1,3,4), (2,2,4), (2,3,3)
9	(1,4,4), (2,3,4), (3,3,3)
10	(1,4,5), (2,3,5), (2,4,4), (3,3,4)
11	(1,5,5), (2,4,5), (3,3,5), (3,4,4)
12	(1,5,6), (2,4,6), (2,5,5), (3,3,6), (3,4,5), (4,4,4)
13	(1,6,6), (2,5,6), (3,4,6), (3,5,5), (4,4,5)
14	(1,6,7), (2,5,7), (2,6,6), (3,4,7), (3,5,6), (4,4,6), (4,5,5)
15	(1,7,7), (2,6,7), (3,5,7), (3,6,6), (4,4,7), (4,5,6), (5,5,5)
16	(1,7,8), (2,6,8), (2,7,7), (3,5,8), (3,6,7), (4,4,8), (4,5,7), (4,6,6), (5,5,6)

Table 3.1: $partitions\ n$ for moderate values of n .

```

module type  $T$  =
  sig
    type  $partition$ 
    val  $partitions$  :  $int \rightarrow partition\ list$ 
    type  $\alpha\ children$ 
    val  $keystones$  :  $\alpha\ list \rightarrow (\alpha\ list \times \alpha\ list\ children\ list)\ list$ 
    val  $max\_subtree$  :  $int \rightarrow int$ 
    val  $inspect\_partition$  :  $partition \rightarrow int\ list$ 
    val  $rcs$  :  $RCS.t$ 
  end

```

3.2.1 Factorizing Diagrams for ϕ^3

```

module  $Binary$  =
  struct
    let  $rcs$  =  $RCS.rename\ rcs\_file\ "Topology.Binary"$ 
      ["phi**3_␣topology"]

    type  $partition$  =  $int \times int \times int$ 
    let  $inspect\_partition\ (n1,\ n2,\ n3)$  = [ $n1$ ;  $n2$ ;  $n3$ ]
  end

```

One way [1] to lift the degeneracy is to select the vertex that is closest to the center (see table 3.1):

$$partitions : n \rightarrow \{(n_1, n_2, n_3) \mid n_1 + n_2 + n_3 = n \wedge n_1 \leq n_2 \leq n_3 \leq \lfloor n/2 \rfloor\} \quad (3.5)$$

Other, less symmetric, approaches are possible. The simplest of these is: choose the vertex adjacent to a fixed external line [2]. They will be made available for comparison in the future.

An obvious consequence of $n_1 + n_2 + n_3 = n$ and $n_1 \leq n_2 \leq n_3$ is $n_1 \leq \lfloor n/3 \rfloor$:




Figure 3.1: Topologies with a blatant three-fold permutation symmetry, if the number of external lines is a multiple of three




Figure 3.2: Topologies with a blatant two-fold symmetry.

```

let rec partitions' n n1 =
  if n1 > n / 3 then
    []
  else
    List.map (fun (n2, n3) → (n1, n2, n3))
      (Partition.pairs (n - n1) n1 (n / 2)) @ partitions' n (succ n1)
let partitions n = partitions' n 1
    
```

```

type α children = α Tuple.Binary.t
    
```

There remains one peculiar case, when the number of external lines is even and $n_3 = n_1 + n_2$ (cf. figure 3.3). Unfortunately, this reflection symmetry is not respected by the equivalence classes. E. g.

$$\{1\}\{2,3\}\{4,5,6\} \mapsto \{\{4\}\{5,6\}\{1,2,3\}; \{5\}\{4,6\}\{1,2,3\}; \{6\}\{4,5\}\{1,2,3\}\} \quad (3.6)$$




Figure 3.3: If $n_3 = n_1 + n_2$, the apparently asymmetric topologies on the left hand side have a non obvious two-fold symmetry, that exchanges the two halves. Therefore, the topologies on the right hand side have a four fold symmetry.

n	$(2n - 5)!!$	$\sum N(n_1, n_2, n_3)$
4	3	$3 \cdot (1, 1, 2)$
5	15	$15 \cdot (1, 2, 2)$
6	105	$90 \cdot (1, 2, 3) + 15 \cdot (2, 2, 2)$
7	945	$630 \cdot (1, 3, 3) + 315 \cdot (2, 2, 3)$
8	10395	$6300 \cdot (1, 3, 4) + 1575 \cdot (2, 2, 4) + 2520 \cdot (2, 3, 3)$
9	135135	$70875 \cdot (1, 4, 4) + 56700 \cdot (2, 3, 4) + 7560 \cdot (3, 3, 3)$
10	2027025	$992250 \cdot (1, 4, 5) + 396900 \cdot (2, 3, 5)$ $+ 354375 \cdot (2, 4, 4) + 283500 \cdot (3, 3, 4)$
11	34459425	$15280650 \cdot (1, 5, 5) + 10914750 \cdot (2, 4, 5)$ $+ 4365900 \cdot (3, 3, 5) + 3898125 \cdot (3, 4, 4)$
12	654729075	$275051700 \cdot (1, 5, 6) + 98232750 \cdot (2, 4, 6)$ $+ 91683900 \cdot (2, 5, 5) + 39293100 \cdot (3, 3, 6)$ $+ 130977000 \cdot (3, 4, 5) + 19490625 \cdot (4, 4, 4)$

Table 3.2: Equation (3.9) for small values of n .

However, these reflections will always exchange the two halves and a representative can be chosen by requiring that one fixed momentum remains in one half. We choose to filter out the half of the partitions where the element p appears in the second half, i.e. the list of length $n\beta$.

Finally, a closed expression for the number of Feynman diagrams in the equivalence class (n_1, n_2, n_3) is

$$N(n_1, n_2, n_3) = \frac{(n_1 + n_2 + n_3)!}{S(n_1, n_2, n_3)} \prod_{i=1}^3 \frac{(2n_i - 3)!!}{n_i!} \quad (3.7)$$

where the symmetry factor from the above arguments is

$$S(n_1, n_2, n_3) = \begin{cases} 3! & \text{for } n_1 = n_2 = n_3 \\ 2 \cdot 2 & \text{for } n_3 = 2n_1 = 2n_2 \\ 2 & \text{for } n_1 = n_2 \vee n_2 = n_3 \\ 2 & \text{for } n_1 + n_2 = n_3 \end{cases} \quad (3.8)$$

Indeed, the sum of all Feynman diagrams

$$\sum_{\substack{n_1+n_2+n_3=n \\ 1 \leq n_1 \leq n_2 \leq n_3 \leq \lfloor n/2 \rfloor}} N(n_1, n_2, n_3) = (2n - 5)!! \quad (3.9)$$

can be checked numerically for large values of $n = n_1 + n_2 + n_3$, verifying the symmetry factor (see table 3.2).



P. M. claims to have seen similar formulae in the context of Young tableaux. That's a good occasion to read the new edition of Howard's book ...

Return a list of all inequivalent partitions of the list l in three lists of length $n1$, $n2$ and $n3$, respectively. Common first lists are factored. This is nothing more than a typedafe wrapper around *Combinatorics.factorized_keystones*.




Figure 3.4: Degenerate $(1, 1, 1, 3)$ and $(1, 2, 3)$.

```

exception Impossible of string
let tuple_of_list2 = function
| [x1; x2] → Tuple.Binary.of2 x1 x2
| _ → raise (Impossible "Topology.tuple_of_list")

let keystone (n1, n2, n3) l =
  List.map (fun (p1, p23) → (p1, List.rev_map tuple_of_list2 p23))
    (Combinatorics.factorized_keystones [n1; n2; n3] l)

let keystones l =
  ThoList.flatmap (fun n123 → keystone n123 l) (partitions (List.length l))

let max_subtree n = n / 2
end

```

3.2.2 Factorizing Diagrams for $\sum_n \lambda_n \phi^n$

Mixed ϕ^n adds new degeneracies, as in figure 3.4. They appear if and only if one part takes exactly half of the external lines and can relate central vertices of different arity.

```

module Nary (B : Tuple.Bound) =
struct
  let rcs = RCS.rename rcs_file "Topology.Nary"
    ["phi**n_topology"]

  type partition = int list
  let inspect_partition p = p

  let partition d sum =
    Partition.tuples d sum 1 (sum / 2)

  let rec partitions' d sum =
    if d < 3 then
      []
    else
      partition d sum @ partitions' (pred d) sum

  let partitions sum = partitions' (succ B.max_arity) sum
end

```

n	Σ	Σ
4	4	$1 \cdot (1, 1, 1, 1) + 3 \cdot (1, 1, 2)$
5	25	$10 \cdot (1, 1, 1, 2) + 15 \cdot (1, 2, 2)$
6	220	$40 \cdot (1, 1, 1, 3) + 45 \cdot (1, 1, 2, 2) + 120 \cdot (1, 2, 3) + 15 \cdot (2, 2, 2)$
7	2485	$840 \cdot (1, 1, 2, 3) + 105 \cdot (1, 2, 2, 2) + 1120 \cdot (1, 3, 3) + 420 \cdot (2, 2, 3)$
8	34300	$5250 \cdot (1, 1, 2, 4) + 4480 \cdot (1, 1, 3, 3) + 3360 \cdot (1, 2, 2, 3)$ $+ 105 \cdot (2, 2, 2, 2) + 14000 \cdot (1, 3, 4)$ $+ 2625 \cdot (2, 2, 4) + 4480 \cdot (2, 3, 3)$
9	559405	$126000 \cdot (1, 1, 3, 4) + 47250 \cdot (1, 2, 2, 4) + 40320 \cdot (1, 2, 3, 3)$ $+ 5040 \cdot (2, 2, 2, 3) + 196875 \cdot (1, 4, 4)$ $+ 126000 \cdot (2, 3, 4) + 17920 \cdot (3, 3, 3)$
10	10525900	$1108800 \cdot (1, 1, 3, 5) + 984375 \cdot (1, 1, 4, 4) + 415800 \cdot (1, 2, 2, 5)$ $+ 1260000 \cdot (1, 2, 3, 4) + 179200 \cdot (1, 3, 3, 3) + 78750 \cdot (2, 2, 2, 4)$ $+ 100800 \cdot (2, 2, 3, 3) + 3465000 \cdot (1, 4, 5) + 1108800 \cdot (2, 3, 5)$ $+ 984375 \cdot (2, 4, 4) + 840000 \cdot (3, 3, 4)$

Table 3.3: $\mathcal{L} = \lambda_3\phi^3 + \lambda_4\phi^4$

n	Σ	Σ
4	4	$1 \cdot (1, 1, 1, 1) + 3 \cdot (1, 1, 2)$
5	26	$1 \cdot (1, 1, 1, 1, 1) + 10 \cdot (1, 1, 1, 2) + 15 \cdot (1, 2, 2)$
6	236	$1 \cdot (1, 1, 1, 1, 1, 1) + 15 \cdot (1, 1, 1, 1, 2) + 40 \cdot (1, 1, 1, 3)$ $+ 45 \cdot (1, 1, 2, 2) + 120 \cdot (1, 2, 3) + 15 \cdot (2, 2, 2)$
7	2751	$21 \cdot (1, 1, 1, 1, 1, 2) + 140 \cdot (1, 1, 1, 1, 3) + 105 \cdot (1, 1, 1, 2, 2)$ $+ 840 \cdot (1, 1, 2, 3) + 105 \cdot (1, 2, 2, 2) + 1120 \cdot (1, 3, 3) + 420 \cdot (2, 2, 3)$
8	39179	$224 \cdot (1, 1, 1, 1, 1, 3) + 210 \cdot (1, 1, 1, 1, 2, 2) + 910 \cdot (1, 1, 1, 1, 4)$ $+ 2240 \cdot (1, 1, 1, 2, 3) + 420 \cdot (1, 1, 2, 2, 2) + 5460 \cdot (1, 1, 2, 4)$ $+ 4480 \cdot (1, 1, 3, 3) + 3360 \cdot (1, 2, 2, 3) + 105 \cdot (2, 2, 2, 2)$ $+ 14560 \cdot (1, 3, 4) + 2730 \cdot (2, 2, 4) + 4480 \cdot (2, 3, 3)$

Table 3.4: $\mathcal{L} = \lambda_3\phi^3 + \lambda_4\phi^4 + \lambda_5\phi^5 + \lambda_6\phi^6$

```

module Tuple = Tuple.Nary(B)
type  $\alpha$  children =  $\alpha$  Tuple.t

let keystones' l =
  let n = List.length l in
  ThoList.flatmap (fun p  $\rightarrow$  Combinatorics.factorized_keystones p l)
    (partitions n)

let keystones l =
  List.map (fun (bra, kets)  $\rightarrow$  (bra, List.map Tuple.of_list kets))
    (keystones' l)

let max_subtree n = n / 2

end

module Nary4 = Nary (struct let max_arity = 3 end)

```

3.2.3 Factorizing Diagrams for ϕ^4

```

module Ternary =
struct
  let rcs = RCS.rename rcs_file "Topology.Ternary"
    ["phi**4 $\sqcup$ topology"]
  let rcs = rcs_file
  type partition = int  $\times$  int  $\times$  int  $\times$  int
  let inspect_partition (n1, n2, n3, n4) = [n1; n2; n3; n4]
  type  $\alpha$  children =  $\alpha$  Tuple.Ternary.t
  let collect4 acc = function
    | [x; y; z; u]  $\rightarrow$  (x, y, z, u) :: acc
    | _  $\rightarrow$  acc
  let partitions n =
    List.fold_left collect4 [] (Nary4.partitions n)
  let collect3 acc = function
    | [x; y; z]  $\rightarrow$  Tuple.Ternary.of3 x y z :: acc
    | _  $\rightarrow$  acc
  let keystones l =
    List.map (fun (bra, kets)  $\rightarrow$  (bra, List.fold_left collect3 [] kets))
      (Nary4.keystones' l)
  let max_subtree = Nary4.max_subtree
end

```

3.2.4 Factorizing Diagrams for $\phi^3 + \phi^4$

```

module Mixed23 =
struct
  let rcs = RCS.rename rcs_file "Topology.Mixed23"
    ["phi**3 $\sqcup$ + $\sqcup$ phi**4 $\sqcup$ topology"]
  type partition =

```

```

    | P3 of int × int × int
    | P4 of int × int × int × int
let inspect_partition = function
    | P3 (n1, n2, n3) → [n1; n2; n3]
    | P4 (n1, n2, n3, n4) → [n1; n2; n3; n4]
type α children = α Tuple.Mixed23.t
let collect34 acc = function
    | [x; y; z] → P3 (x, y, z) :: acc
    | [x; y; z; u] → P4 (x, y, z, u) :: acc
    | _ → acc
let partitions n =
    List.fold_left collect34 [] (Nary4.partitions n)
let collect23 acc = function
    | [x; y] → Tuple.Mixed23.of2 x y :: acc
    | [x; y; z] → Tuple.Mixed23.of3 x y z :: acc
    | _ → acc
let keystones l =
    List.map (fun (bra, kets) → (bra, List.fold_left collect23 [] kets))
            (Nary4.keystones' l)
let max_subtree = Nary4.max_subtree
end

```

3.2.5 Diagnostics: Counting Diagrams and Factorizations for $\sum_n \lambda_n \phi^n$

```

module type Integer =
sig
  type t
  val zero : t
  val one : t
  val ( + ) : t → t → t
  val ( - ) : t → t → t
  val ( × ) : t → t → t
  val ( / ) : t → t → t
  val pred : t → t
  val succ : t → t
  val ( = ) : t → t → bool
  val ( ≠ ) : t → t → bool
  val ( < ) : t → t → bool
  val ( ≤ ) : t → t → bool
  val ( > ) : t → t → bool
  val ( ≥ ) : t → t → bool
  val of_int : int → t
  val to_int : t → int
  val to_string : t → string
  val compare : t → t → int
  val factorial : t → t
end

```

O’Caml’s native integers suffice for all applications, but in appendix S, we want to use big integers for numeric checks in high orders:

```

module Int : Integer =
  struct
    type t = int
    let zero = 0
    let one = 1
    let ( + ) = ( + )
    let ( - ) = ( - )
    let ( × ) = ( × )
    let ( / ) = ( / )
    let pred = pred
    let succ = succ
    let ( = ) = ( = )
    let ( ≠ ) = ( ≠ )
    let ( < ) = ( < )
    let ( ≤ ) = ( ≤ )
    let ( > ) = ( > )
    let ( ≥ ) = ( ≥ )
    let of_int n = n
    let to_int n = n
    let to_string = string_of_int
    let compare = compare
    let factorial = Combinatorics.factorial
  end

module type Count =
  sig
    type integer
    val diagrams : ?f:(integer → bool) → integer → integer → integer
    val diagrams_via_keystones : integer → integer → integer
    val keystones : integer list → integer
    val diagrams_per_keystone : integer → integer list → integer
  end

module Count (I : Integer) =
  struct
    let rcs = rcs_file
    let description = ["(still_inoperational)_phi^n_topology"]

    type integer = I.t
    open I
    let two = of_int 2
    let three = of_int 3
  end

```

If *I.t* is an abstract datatype, the polymorphic *Pervasives.min* can fail. Provide our own version using the specific comparison “(\leq)”.

```

let min x y =
  if x ≤ y then
    x
  else

```


y

Counting Diagrams for $\sum_n \lambda_n \phi^n$

Classes of diagrams are defined by the number of vertices and their degrees. We could use fixed size arrays, but we will use a map instead. For efficiency, we also maintain the number of external lines and the total number of propagators.

```
module IMap = Map.Make (struct type t = integer let compare = compare end)

type diagram_class = { ext : integer; prop : integer; v : integer IMap.t }
```

The numbers of external lines, propagators and vertices are determined by the degrees and multiplicities of vertices:

$$E(\{n_3, n_4, \dots\}) = 2 + \sum_{d=3}^{\infty} (d-2)n_d \quad (3.10a)$$

$$P(\{n_3, n_4, \dots\}) = \sum_{d=3}^{\infty} n_d - 1 = V(\{n_3, n_4, \dots\}) - 1 \quad (3.10b)$$

$$V(\{n_3, n_4, \dots\}) = \sum_{d=3}^{\infty} n_d \quad (3.10c)$$

```
let num_ext v =
  List.fold_left (fun sum (d, n) → sum + (d - two) × n) two v

let num_prop v =
  List.fold_left (fun sum (_, n) → sum + n) (zero - one) v
```

The sum of all vertex degrees must be equal to the number of propagator end points. This can be verified easily:

$$2P(\{n_3, n_4, \dots\}) + E(\{n_3, n_4, \dots\}) = \sum_{d=3}^{\infty} dn_d \quad (3.11)$$

```
let add_degree map (d, n) =
  if d < three then
    invalid_arg "add_degree: d < 3"
  else if n < zero then
    invalid_arg "add_degree: n <= 0"
  else if n = zero then
    map
  else
    IMap.add d n map

let create_class v =
  { ext = num_ext v;
    prop = num_prop v;
    v = List.fold_left add_degree IMap.empty v }

let multiplicity cl d =
```

```

if  $d \geq three$  then
  try
     $IMap.find\ d\ cl.v$ 
  with
    |  $Not\_found \rightarrow zero$ 
  else
     $invalid\_arg\ "multiplicity:\_d\leq 3"$ 

```

Remove one vertex of degree d , maintaining the invariants. Raises *Zero* if all vertices of degree d are exhausted.

```

exception Zero

let  $remove\ cl\ d =$ 
  let  $n = pred\ (multiplicity\ cl\ d)$  in
  if  $n < zero$  then
    raise Zero
  else
    {  $ext = cl.ext - (d - two)$ ;
       $prop = pred\ cl.prop$ ;
       $v = if\ n = zero\ then$ 
         $IMap.remove\ d\ cl.v$ 
      else
         $IMap.add\ d\ n\ cl.v$  }

```

Add one vertex of degree d , maintaining the invariants.

```

let  $add\ cl\ d =$ 
  {  $ext = cl.ext + (d - two)$ ;
     $prop = succ\ cl.prop$ ;
     $v = IMap.add\ d\ (succ\ (multiplicity\ cl\ d))\ cl.v$  }

```

Count the number of diagrams. Any diagram can be obtained recursively either from a diagram with one ternary vertex less by insertion of a ternary vertex in an internal or external propagator or from a diagram with a higher order vertex that has its degree reduced by one:

$$\begin{aligned}
D(\{n_3, n_4, \dots\}) = & \\
& (P(\{n_3 - 1, n_4, \dots\}) + E(\{n_3 - 1, n_4, \dots\})) D(\{n_3 - 1, n_4, \dots\}) \\
& + \sum_{d=4}^{\infty} (n_{d-1} + 1) D(\{n_3, n_4, \dots, n_{d-1} + 1, n_d - 1, \dots\}) \quad (3.12)
\end{aligned}$$

```

let rec  $class\_size\ cl =$ 
  if  $cl.ext = two \vee cl.prop = zero$  then
    one
  else
     $IMap.fold\ (fun\ d\ _\ s \rightarrow class\_size\_n\ cl\ d + s)\ cl.v\ (class\_size\_3\ cl)$ 

```

Purely ternary vertices recurse among themselves:

```

and  $class\_size\_3\ cl =$ 
  try
    let  $d' = remove\ cl\ three$  in

```

```

      (d'.ext + d'.prop) × class_size d'
with
| Zero → zero

```

Vertices of higher degree recurse one step towards lower degrees:

```

and class_size_n cl d =
  if d > three then begin
    try
      let d' = pred d in
      let cl' = add (remove cl d) d' in
      multiplicity cl' d' × class_size cl'
    with
    | Zero → zero
  end else
    zero

```

Find all $\{n_3, n_4, \dots, n_d\}$ with

$$E(\{n_3, n_4, \dots, n_d\}) - 2 = \sum_{i=3}^c l(i-2)n_i = \text{sum} \quad (3.13)$$

The implementation is a variant of *tuples* above.

```

let rec distribute_degrees' d sum =
  if d < three then
    invalid_arg "distribute_degrees"
  else if d = three then
    [[(d, sum)]]
  else
    distribute_degrees'' d sum (sum / (d - two))
and distribute_degrees'' d sum n =
  if n < zero then
    []
  else
    List.fold_left (fun ll l → ((d, n) :: l) :: ll)
      (distribute_degrees'' d sum (pred n))
      (distribute_degrees' (pred d) (sum - (d - two) × n))

```

Actually, we need to find all $\{n_3, n_4, \dots, n_d\}$ with

$$E(\{n_3, n_4, \dots, n_d\}) = \text{sum} \quad (3.14)$$

```

let distribute_degrees d sum = distribute_degrees' d (sum - two)

```

Finally we can count all diagrams by adding all possible ways of splitting the degrees of vertices. We can also count diagrams where *all* degrees satisfy a predicate f :

```

let diagrams ?(f = fun _ → true) deg n =
  List.fold_left (fun s d →
    if List.for_all (fun (d', n') → f d' ∨ n' = zero) d then
      s + class_size (create_class d)

```

```

else
  s)
  zero (distribute_degrees deg n)

```

The next two are duplicated from *ThoList* and *Combinatorics*, in order to use the specific comparison functions.

```

let classify l =
  let rec add_to_class a = function
    | [] → [of_int 1, a]
    | (n, a') :: rest →
        if a = a' then
          (succ n, a) :: rest
        else
          (n, a') :: add_to_class a rest
  in
  let rec classify' cl = function
    | [] → cl
    | a :: rest → classify' (add_to_class a cl) rest
  in
  classify' [] l

let permutation_symmetry l =
  List.fold_left (fun s (n, _) → factorial n × s) one (classify l)

let symmetry l =
  let sum = List.fold_left (+) zero l in
  if List.exists (fun x → two × x = sum) l then
    two × permutation_symmetry l
  else
    permutation_symmetry l

```

The number of Feynman diagrams built of vertices with maximum degree d_{\max} in a partition $N_{d,n} = \{n_1, n_2, \dots, n_d\}$ with $n = n_1 + n_2 + \dots + n_d$ and

$$\tilde{F}(d_{\max}, N_{d,n}) = \frac{n!}{|\mathcal{S}(N_{d,n})|\sigma(n_d, n)} \prod_{i=1}^d \frac{F(d_{\max}, n_i + 1)}{n_i!} \quad (3.15)$$

with $|\mathcal{S}(N)|$ the size of the symmetric group of N , $\sigma(n, 2n) = 2$ and $\sigma(n, m) = 1$ otherwise.

```

let keystones p =
  let sum = List.fold_left (+) zero p in
  List.fold_left (fun acc n → acc / (factorial n)) (factorial sum) p
  / symmetry p

let diagrams_per_keystone deg p =
  List.fold_left (fun acc n → acc × diagrams deg (succ n)) one p

```

We must find

$$F(d_{\max}, n) = \sum_{d=3}^{d_{\max}} \sum_{\substack{N=\{n_1, n_2, \dots, n_d\} \\ n_1+n_2+\dots+n_d=n \\ 1 \leq n_1 \leq n_2 \leq \dots \leq n_d \leq \lfloor n/2 \rfloor}} \tilde{F}(d_{\max}, N) \quad (3.16)$$

```

let diagrams_via_keystones deg n =
  let module N = Nary (struct let max_arity = to_int (pred deg) end) in
  List.fold_left
    (fun acc p → acc + diagrams_per_keystone deg p × keystones p)
    zero (List.map (List.map of_int) (N.partitions (to_int n)))
end

```

3.2.6 Emulating HELAC

In [2], one leg is singled out:

```

module Helac (B : Tuple.Bound) =
struct
  let rcs = RCS.rename rcs_file "Topology.Helac"
    ["phi**n", topology, Helac, style]
  module Tuple = Tuple.Nary(B)

  type partition = int list
  let inspect_partition p = p

  let partition d sum =
    Partition.tuples d sum 1 (sum - d + 1)

  let rec partitions' d sum =
    let d' = pred d in
    if d' < 2 then
      []
    else
      List.map (fun p → 1 :: p) (partition d' (pred sum)) @ partitions' d' sum

  let partitions sum = partitions' (succ B.max_arity) sum

  type α children = α Tuple.t

  let keystones' l =
    match l with
    | [] → []
    | head :: tail →
      [[head],
       ThoList.flatmap (fun p → Combinatorics.partitions (List.tl p) tail)
        (partitions (List.length l))]]

  let keystones l =
    List.map (fun (bra, kets) → (bra, List.map Tuple.of_list kets))
      (keystones' l)

  let max_subtree n = pred n
end

```



The following is not tested, but it is no rocket science either ...

```

module Helac_Binary =
struct
  let rcs = RCS.rename rcs_file "Topology.Helac_Binary"
    ["phi**3_topology, Helac_style"]

  type partition = int × int × int
  let inspect_partition (n1, n2, n3) = [n1; n2; n3]

  let partitions sum =
    List.map (fun (n2, n3) → (1, n2, n3))
      (Partition.pairs (sum - 1) 1 (sum - 2))

  type α children = α Tuple.Binary.t

  let keystones' l =
    match l with
    | [] → []
    | head :: tail →
      [[head],
        ThoList.flatmap (fun (_, p2, _) → Combinatorics.split p2 tail)
          (partitions (List.length l))]]

  let keystones l =
    List.map (fun (bra, kets) →
      (bra, List.map (fun (x, y) → Tuple.Binary.of2 x y) kets))
      (keystones' l)

  let max_subtree n = pred n
end

```

—4—

DIRECTED ACYCLICAL GRAPHS

4.1 Interface of DAG

This datastructure describes large collections of trees with many shared nodes. The sharing of nodes is semantically irrelevant, but can turn a factorial complexity to exponential complexity. Note that *DAG* implements only a very specialized subset of Directed Acyclical Graphs (DAGs).

If $T(n, D)$ denotes the set of all binary trees with root n encoded in D , while

$$O(n, D) = \{(e_1, n_1, n'_1), \dots, (e_k, n_k, n'_k)\} \quad (4.1)$$

denotes the set of all *offspring* of n in D , and $\text{tree}(e, t, t')$ denotes the binary tree formed by joining the binary trees t and t' with the label e , then

$$T(n, D) = \{\text{tree}(e_i, t_i, t'_i) \mid (e_i, t_i, t'_i) \in \{e_1\} \times T(n_1, D) \times T(n'_1, D) \cup \dots \cup \{e_k\} \times T(n_k, D) \times T(n'_k, D)\} \quad (4.2)$$

is the recursive definition of the binary trees encoded in D . It is obvious how this definitions translates to n -ary trees (including trees with mixed arity).

4.1.1 Forests

We require edges and nodes to be members of ordered sets. The semantics of *compare* are compatible with *Pervasives.compare*:

$$\text{compare}(x, y) = \begin{cases} -1 & \text{for } x < y \\ 0 & \text{for } x = y \\ 1 & \text{for } x > y \end{cases} \quad (4.3)$$

Note that this requirement does *not* exclude any trees. Even if we consider only topological equivalence classes with anonymous nodes, we can always construct a canonical labeling and order from the children of the nodes. However, if practical applications, we will often have more efficient labelings and orders at our disposal.

```
module type Ord =
  sig
    type t
```

```

    val compare : t → t → int
end

```

A forest F over a set of nodes and a set of edges is a map from the set of nodes N , to the direct product of the set of edges E and the power set 2^N of N augmented by a special element \perp (“bottom”).

$$F : N \rightarrow (E \times 2^N) \cup \{\perp\}$$

$$n \mapsto \begin{cases} (e, \{n'_1, n'_2, \dots\}) \\ \perp \end{cases} \quad (4.4)$$

The nodes are ordered so that cycles can be detected

$$\forall n \in N : F(n) = (e, x) \Rightarrow \forall n' \in x : n > n' \quad (4.5)$$

A suitable function that exists for *all* forests is the depth of the tree beneath a node.

Nodes that are mapped to \perp are called *leaf* nodes and nodes that do not appear in any $F(n)$ are called *root* nodes. There are as many trees in the forest as there are root nodes.

```

module type Forest =
sig
  module Nodes : Ord
  type node = Nodes.t
  type edge

```

A subset $X \subset 2^N$ of the powerset of the set of nodes. The members of X can be characterized by a fixed number of members (e.g. two for binary trees, as in QED). We can also have mixed arities (e.g. two and three for QCD) or even arbitrary arities. However, in most cases, the members of X will have at least two members.

```

  type children

```

This type abbreviation and order allow to apply the *Set.Make* functor to $E \times X$.

```

  type t = edge × children
  val compare : t → t → int

```

Test a predicate for *all* children.

```

  val for_all : (node → bool) → t → bool

```

fold f $(-, children)$ *acc* will calculate

$$f(x_1, f(x_2, \dots f(x_n, acc))) \quad (4.6)$$

where the *children* are $\{x_1, x_2, \dots, x_n\}$. There are slightly more efficient alternatives for fixed arity (in particular binary), but we want to be general.

```

  val fold : (node → α → α) → t → α → α

```

```

end

```

```

module Forest : functor (PT : Tuple.Poly) →
  functor (N : Ord) → functor (E : Ord) →
    Forest with module Nodes = N and type edge = E.t
    and type node = N.t and type children = N.t PT.t

```


4.1.2 DAGs

```

module type T =
  sig
    type node
    type edge

```

In the description of the function we assume for definiteness DAGs of binary trees with `type children = node × node`. However, we will also have implementations with `type children = node list` below.

Other possibilities include `type children = V3 of node × node | V4 of node × node × node`. There's probably never a need to use sets with logarithmic access, but it is easy to add.

```

    type children
    type t

```

The empty DAG.

```

    val empty : t

```

`add_node n dag` returns the DAG `dag` with the node `n`. If the node `n` already exists in `dag`, it is returned unchanged. Otherwise `n` is added without offspring.

```

    val add_node : node → t → t

```

`add_offspring n (e, (n1, n2)) dag` returns the DAG `dag` with the node `n` and its offspring `n1` and `n2` with edge label `e`. Each node can have an arbitrary number of offspring, but identical offspring are added only once. In order to prevent cycles, `add_offspring` requires both `n > n1` and `n > n2` in the given ordering. The nodes `n1` and `n2` are added as by `add_node`. NB: Adding all nodes `n1` and `n2`, even if they are sterile, is not strictly necessary for our applications. It even slows down the code by a few percent. But it is desirable for consistency and allows much more efficient `iter_nodes` and `fold_nodes` below.

```

    val add_offspring : node → edge × children → t → t
    exception Cycle

```

Just like `add_offspring`, but does not check for potential cycles.

```

    val add_offspring_unsafe : node → edge × children → t → t

```

`is_node n dag` returns true iff `n` is a node in `dag`.

```

    val is_node : node → t → bool

```

`is_sterile n dag` returns true iff `n` is a node in `dag` and boasts no offspring.

```

    val is_sterile : node → t → bool

```

`is_offspring n (e, (n1, n2)) dag` returns true iff `n1` and `n2` are offspring of `n` with label `e` in `dag`.

```

    val is_offspring : node → edge × children → t → bool

```

Note that the following functions can run into infinite recursion if the DAG given as argument contains cycles.

The usual functionals for processing all nodes (including sterile) ...

```

val iter_nodes : (node → unit) → t → unit
val map_nodes : (node → node) → t → t
val fold_nodes : (node → α → α) → t → α → α

```

... and all parent/offspring relations. Note that *map* requires *two* functions: one for the nodes and one for the edges and children. This is so because a change in the definition of node is *not* propagated automatically to where it is used as a child.

```

val iter : (node → edge × children → unit) → t → unit
val map : (node → node) →
  (node → edge × children → edge × children) → t → t
val fold : (node → edge × children → α → α) → t → α → α

```



Note that in it's current incarnation, *fold add_offspring dag empty* copies *only* the fertile nodes, while *fold add_offspring dag (fold_nodes add_node dag empty)* includes sterile ones, as does *map (fun n → n) (fun n ec → ec) dag*.

Return the DAG as a list of lists.

```
val lists : t → (node × (edge × children) list) list
```

dependencies dag node returns a canonically sorted *Tree2.t* of all nodes reachable from *node*.

```
val dependencies : t → node → (node, edge) Tree2.t
```

harvest dag n roots returns the DAG *roots* enlarged by all nodes in *dag* reachable from *n*.

```
val harvest : t → node → t → t
```

size dag returns the number of nodes in the DAG *dag*.

```
val size : t → int
```

eval f mul_edge mul_nodes add null unit root dag

```

val eval : (node → α) → (node → edge → β → γ) →
  (α → β → β) → (γ → α → α) → α → β → node → t → α
val eval_memoized : (node → α) → (node → edge → β → γ) →
  (α → β → β) → (γ → α → α) → α → β → node → t → α

```

harvest_list dag nlist returns the part of the DAG *dag* that is reachable from the nodes in *nlist*.

```
val harvest_list : t → node list → t
```

count_trees n dag returns the number of trees with root *n* encoded in the DAG *dag*, i.e. $|T(n, D)|$. NB: the current implementation is very naive and can take a *very* long time for moderately sized DAGs that encode a large set of trees.

```
val count_trees : node → t → int
```

forest root dag

```

val forest : node → t → (node × edge option, node) Tree.t list
val forest_memoized : node → t → (node × edge option, node) Tree.t list

```

```

    val rcs : RCS.t
  end

module Make (F : Forest) :
  T with type node = F.node and type edge = F.edge
  and type children = F.children

```

4.1.3 Graded Sets, Forests & DAGs

A graded ordered¹ set is an ordered set with a map into another ordered set (often the non-negative integers). The grading does not necessarily respect the ordering.

```

module type Graded_Ord =
  sig
    include Ord
    module G : Ord
    val rank : t → G.t
  end

```

For all ordered sets, there are two canonical gradings: a *Chaotic* grading that assigns the same rank (e.g. *unit*) to all elements and the *Discrete* grading that uses the identity map as grading.

```

module type Grader = functor (O : Ord) → Graded_Ord with type t = O.t
module Chaotic : Grader
module Discrete : Grader

```

A graded forest is just a forest in which the nodes form a graded ordered set.



There doesn't appear to be a nice syntax for avoiding the repetition here. Fortunately, the signature is short ...

```

module type Graded_Forest =
  sig
    module Nodes : Graded_Ord
    type node = Nodes.t
    type edge
    type children
    type t = edge × children
    val compare : t → t → int
    val for_all : (node → bool) → t → bool
    val fold : (node → α → α) → t → α → α
  end

module type Forest_Grader = functor (G : Grader) → functor (F : Forest) →

  Graded_Forest with type Nodes.t = F.node
  and type node = F.node
  and type edge = F.edge

```

¹We don't appear to have use for graded unordered sets.

```

and type children = F.children
and type t = F.t

```

```

module Grade_Forest : Forest_Grader

```

Finally, a graded DAG is a DAG in which the nodes form a graded ordered set and the subsets with a given rank can be accessed cheaply.

```

module type Graded =
sig
  include T
  type rank
  val rank : node → rank
  val ranks : t → rank list
  val min_max_rank : t → rank × rank
  val ranked : rank → t → node list
end

module Graded (F : Graded_Forest) :
  Graded with type node = F.node and type edge = F.edge
  and type children = F.children and type rank = F.Nodes.G.t

```

4.2 Implementation of DAG

```

let rcs_file = RCS.parse "DAG" ["Directed_Acyclical_Graph"]
{ RCS.revision = "$Revision: 4538$";
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
  RCS.author = "$Author: jr-reuter$";
  RCS.source
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
module type Ord =
sig
  type t
  val compare : t → t → int
end

module type Forest =
sig
  module Nodes : Ord
  type node = Nodes.t
  type edge
  type children
  type t = edge × children
  val compare : t → t → int
  val for_all : (node → bool) → t → bool
  val fold : (node →  $\alpha$  →  $\alpha$ ) → t →  $\alpha$  →  $\alpha$ 
end

module type T =
sig
  type node

```

```

type edge
type children
type t
val empty : t
val add_node : node → t → t
val add_offspring : node → edge × children → t → t
exception Cycle
val add_offspring_unsafe : node → edge × children → t → t
val is_node : node → t → bool
val is_sterile : node → t → bool
val is_offspring : node → edge × children → t → bool
val iter_nodes : (node → unit) → t → unit
val map_nodes : (node → node) → t → t
val fold_nodes : (node → α → α) → t → α → α
val iter : (node → edge × children → unit) → t → unit
val map : (node → node) →
  (node → edge × children → edge × children) → t → t
val fold : (node → edge × children → α → α) → t → α → α
val lists : t → (node × (edge × children) list) list
val dependencies : t → node → (node, edge) Tree2.t
val harvest : t → node → t → t
val size : t → int
val eval : (node → α) → (node → edge → β → γ) →
  (α → β → β) → (γ → α → α) → α → β → node → t → α
val eval_memoized : (node → α) → (node → edge → β → γ) →
  (α → β → β) → (γ → α → α) → α → β → node → t → α
val harvest_list : t → node list → t
val count_trees : node → t → int
val forest : node → t → (node × edge option, node) Tree.t list
val forest_memoized : node → t → (node × edge option, node) Tree.t list
val rcs : RCS.t
end

module type Graded_Ord =
sig
  include Ord
  module G : Ord
  val rank : t → G.t
end

module type Grader = functor (O : Ord) → Graded_Ord with type t = O.t

module type Graded_Forest =
sig
  module Nodes : Graded_Ord
  type node = Nodes.t
  type edge
  type children
  type t = edge × children
  val compare : t → t → int
  val for_all : (node → bool) → t → bool
  val fold : (node → α → α) → t → α → α

```

```

end

module type Forest_Grader = functor (G : Grader) → functor (F : Forest) →

  Graded_Forest with type Nodes.t = F.node
  and type node = F.node
  and type edge = F.edge
  and type children = F.children
  and type t = F.t

```

4.2.1 The Forest Functor

```

module Forest (PT : Tuple.Poly) (N : Ord) (E : Ord) :
  Forest with module Nodes = N and type edge = E.t
  and type node = N.t and type children = N.t PT.t =
struct
  module Nodes = N
  type edge = E.t
  type node = N.t
  type children = node PT.t
  type t = edge × children

  let compare (e1, n1) (e2, n2) =
    let c = PT.compare N.compare n1 n2 in
    if c ≠ 0 then
      c
    else
      E.compare e1 e2

  let for_all f (_, nodes) = PT.for_all f nodes
  let fold f (_, nodes) acc = PT.fold_right f nodes acc
end

```

4.2.2 Gradings

```

module Chaotic (O : Ord) =
struct
  include O
  module G =
    struct
      type t = unit
      let compare _ _ = 0
    end
  let rank _ = ()
end

module Discrete (O : Ord) =
struct

```

```

    include O
    module G = O
    let rank x = x
  end
module Fake_Grading (O : Ord) =
  struct
    include O
    exception Impossible of string
    module G =
      struct
        type t = unit
        let compare _ _ = raise (Impossible "G.compare")
      end
    let rank _ = raise (Impossible "G.compare")
  end
module Grade_Forest (G : Grader) (F : Forest) =
  struct
    module Nodes = G(F.Nodes)
    type node = Nodes.t
    type edge = F.edge
    type children = F.children
    type t = F.t
    let compare = F.compare
    let for_all = F.for_all
    let fold = F.fold
  end

```



The following can easily be extended to *Map.S* in its full glory, if we ever need it.

```

module type Graded_Map =
  sig
    type key
    type rank
    type  $\alpha$  t
    val empty :  $\alpha$  t
    val add : key  $\rightarrow$   $\alpha$   $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$  t
    val find : key  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$ 
    val mem : key  $\rightarrow$   $\alpha$  t  $\rightarrow$  bool
    val iter : (key  $\rightarrow$   $\alpha$   $\rightarrow$  unit)  $\rightarrow$   $\alpha$  t  $\rightarrow$  unit
    val fold : (key  $\rightarrow$   $\alpha$   $\rightarrow$   $\beta$   $\rightarrow$   $\beta$ )  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\beta$   $\rightarrow$   $\beta$ 
    val ranks :  $\alpha$  t  $\rightarrow$  rank list
    val min_max_rank :  $\alpha$  t  $\rightarrow$  rank  $\times$  rank
    val ranked : rank  $\rightarrow$   $\alpha$  t  $\rightarrow$  key list
  end
module type Graded_Map_Maker = functor (O : Graded_Ord)  $\rightarrow$ 
  Graded_Map with type key = O.t and type rank = O.G.t

```

```

module Graded_Map (O : Graded_Ord) :
  Graded_Map with type key = O.t and type rank = O.G.t =
struct
  module M1 = Map.Make(O.G)
  module M2 = Map.Make(O)

  type key = O.t
  type rank = O.G.t

  type (+α) t = α M2.t M1.t

  let empty = M1.empty
  let add key data map1 =
    let rank = O.rank key in
    let map2 = try M1.find rank map1 with Not_found → M2.empty in
    M1.add rank (M2.add key data map2) map1
  let find key map = M2.find key (M1.find (O.rank key) map)
  let mem key map =
    M2.mem key (try M1.find (O.rank key) map with Not_found → M2.empty)
  let iter f map1 = M1.iter (fun rank → M2.iter f) map1
  let fold f map1 acc1 = M1.fold (fun rank → M2.fold f) map1 acc1

```



The set of ranks and its minimum and maximum should be maintained explicitly!

```

module S1 = Set.Make(O.G)
let ranks map = M1.fold (fun key data acc → key :: acc) map []
let rank_set map = M1.fold (fun key data → S1.add key) map S1.empty
let min_max_rank map =
  let s = rank_set map in
  (S1.min_elt s, S1.max_elt s)

module S2 = Set.Make(O)
let keys map = M2.fold (fun key data acc → key :: acc) map []
let sorted_keys map =
  S2.elements (M2.fold (fun key data → S2.add key) map S2.empty)
let ranked_rank map =
  keys (try M1.find rank map with Not_found → M2.empty)
end

```

4.2.3 The DAG Functor

```

module Maybe_Graded (GMM : Graded_Map_Maker) (F : Graded_Forest) =
struct
  let rcs = RCS.rename rcs_file "DAG.Graded()"
  ["Graded_directed_Acyclical_Graph";
   "representing_binary_or_n-ary_trees"]

  module G = F.Nodes.G

```



```

type node = F.node
type rank = G.t
type edge = F.edge
type children = F.children

```

If we get tired of graded DAGs, we just have to replace *Graded_Map* by *Map* here and remove *ranked* below and gain a tiny amount of simplicity and efficiency.

```

module Parents = GMM(F.Nodes)
module Offspring = Set.Make(F)

type t = Offspring.t Parents.t

let rank = F.Nodes.rank
let ranks = Parents.ranks
let min_max_rank = Parents.min_max_rank
let ranked = Parents.ranked

let empty = Parents.empty

let add_node node dag =
  if Parents.mem node dag then
    dag
  else
    Parents.add node Offspring.empty dag

let add_offspring_unsafe node offspring dag =
  let offsprings =
    try Parents.find node dag with Not_found → Offspring.empty in
  Parents.add node (Offspring.add offspring offsprings)
  (F.fold add_node offspring dag)

exception Cycle

let add_offspring node offspring dag =
  if F.for_all (fun n → F.Nodes.compare n node < 0) offspring then
    add_offspring_unsafe node offspring dag
  else
    raise Cycle

let is_node node dag =
  Parents.mem node dag

let is_sterile node dag =
  try
    Offspring.is_empty (Parents.find node dag)
  with
  | Not_found → false

let is_offspring node offspring dag =
  try
    Offspring.mem offspring (Parents.find node dag)
  with
  | Not_found → false

let iter_nodes f dag =
  Parents.iter (fun n → f n) dag

```

```

let iter f dag =
  Parents.iter (fun node → Offspring.iter (f node)) dag

let map_nodes f dag =
  Parents.fold (fun n → Parents.add (f n)) dag Parents.empty

let map fn fo dag =
  Parents.fold (fun node offspring →
    Parents.add (fn node)
    (Offspring.fold (fun o → Offspring.add (fo node o))
      offspring Offspring.empty)) dag Parents.empty

let fold_nodes f dag acc =
  Parents.fold (fun n _ → f n) dag acc

let fold f dag acc =
  Parents.fold (fun node → Offspring.fold (f node)) dag acc

```



Note that in its current incarnation, *fold add_offspring dag empty* copies *only* the fertile nodes, while *fold add_offspring dag (fold_nodes add_node dag empty)* includes sterile ones, as does *map (fun n → n) (fun n ec → ec) dag*.

```

let dependencies dag node =
  let rec dependencies' node' =
    let offspring = Parents.find node' dag in
    if Offspring.is_empty offspring then
      Tree2.leaf node'
    else
      Tree2.cons
        (Offspring.fold
          (fun o acc →
            (fst o,
             node',
             F.fold (fun wf acc' → dependencies' wf :: acc') o []) :: acc)
          offspring [])
  in
  dependencies' node

let lists dag =
  Sort.list (fun (n1, _) (n2, _) → F.Nodes.compare n1 n2 ≤ 0)
    (Parents.fold (fun node offspring l →
      (node, Offspring.elements offspring) :: l) dag [])

let size dag =
  Parents.fold (fun _ n → succ n) dag 0

let rec harvest dag node roots =
  Offspring.fold
    (fun offspring roots' →
      if is_offspring node offspring roots' then
        roots'
      else

```

```

      F.fold (harvest dag)
        offspring (add_offspring_unsafe node offspring roots')
      (Parents.find node dag) (add_node node roots)
let harvest_list dag nodes =
  List.fold_left (fun roots node → harvest dag node roots) empty nodes

```

Build a closure once, so that we can recurse faster:

```

let eval f mule muln add null unit node dag =
  let rec eval' n =
    if is_sterile n dag then
      f n
    else
      Offspring.fold
        (fun (e, _ as offspring) v0 →
          add (mule n e (F.fold muln' offspring unit)) v0)
        (Parents.find n dag) null
    and muln' n = muln (eval' n) in
  eval' node

let count_trees node dag =
  eval (fun _ → 1) (fun _ _ p → p) ( × ) (+) 0 1 node dag

let build_forest evaluator node dag =
  evaluator (fun n → [Tree.leaf (n, None) n])
    (fun n e p → List.map (fun p' → Tree.cons (n, Some e) p') p)
    (fun p1 p2 → Product.fold2 (fun n nl pl → (n :: nl) :: pl) p1 p2 [])
    (@) [] [[]] node dag

let forest = build_forest eval

```

At least for *count_trees*, the memoizing variant *eval_memoized* is considerably slower than direct recursive evaluation with *eval*.

```

let eval_offspring f mule muln add null unit dag values (node, offspring) =
  let muln' n = muln (Parents.find n values) in
  let v =
    if is_sterile node dag then
      f node
    else
      Offspring.fold
        (fun (e, _ as offspring) v0 →
          add (mule node e (F.fold muln' offspring unit)) v0)
        offspring null
  in
  (v, Parents.add node v values)

let eval_memoized' f mule muln add null unit dag =
  let result, _ =
    List.fold_left
      (fun (v, values) → eval_offspring f mule muln add null unit dag values)
      (null, Parents.empty)
      (Sort.list (fun (n1, _) (n2, _) → F.Nodes.compare n1 n2 ≤ 0)
        (Parents.fold

```

```

      (fun node offspring l → (node, offspring) :: l) dag []) in
    result
  let eval_memoized f mule muln add null unit node dag =
    eval_memoized' f mule muln add null unit
      (harvest dag node empty)
  let forest_memoized = build_forest eval_memoized
end
module type Graded =
sig
  include T
  type rank
  val rank : node → rank
  val ranks : t → rank list
  val min_max_rank : t → rank × rank
  val ranked : rank → t → node list
end
module Graded (F : Graded_Forest) = Maybe_Graded(Graded_Map)(F)

```

The following is not a graded map, obviously. But it can pass as one by the typechecker for constructing non-graded DAGs.

```

module Fake_Graded_Map (O : Graded_Ord) :
  Graded_Map with type key = O.t and type rank = O.G.t =
struct
  module M = Map.Make(O)
  type key = O.t
  type (+α) t = α M.t
  let empty = M.empty
  let add = M.add
  let find = M.find
  let mem = M.mem
  let iter = M.iter
  let fold = M.fold

```

We make sure that the remaining three are never called inside *DAG* and are not visible outside.

```

  type rank = O.G.t
  exception Impossible of string
  let ranks _ = raise (Impossible "ranks")
  let min_max_rank _ = raise (Impossible "min_max_rank")
  let ranked _ _ = raise (Impossible "ranked")
end

```

We could also have used signature projection with a chaotic or discrete grading, but the *Graded_Map* can cost some efficiency. This is probably not the case for the current simple implementation, but future embellishment can change this. Therefore, the ungraded DAG uses *Map* directly, without overhead.

```

module Make (F : Forest) =
  Maybe_Graded(Fake_Graded_Map)(Grade_Forest(Fake_Grading)(F))

```



If O'Caml had *polymorphic recursion*, we could think of even more elegant implementations unifying nodes and offspring (cf. the generalized tries in [\[4\]](#)).

—5—

MOMENTA

5.1 *Interface of Momentum*

Model the finite combinations

$$p = \sum_{n=1}^k c_k \bar{p}_n, \quad (\text{with } c_k \in \{0, 1\}) \quad (5.1)$$

of n_{in} incoming and $k - n_{\text{in}}$ outgoing momenta p_n

$$\bar{p}_n = \begin{cases} -p_n & \text{for } 1 \leq n \leq n_{\text{in}} \\ p_n & \text{for } n_{\text{in}} + 1 \leq n \leq k \end{cases} \quad (5.2)$$

where momentum is conserved

$$\sum_{n=1}^k \bar{p}_n = 0 \quad (5.3)$$

below, we need the notion of ‘rank’ and ‘dimension’:

$$\dim(p) = k \quad (5.4a)$$

$$\text{rank}(p) = \sum_{n=1}^k c_k \quad (5.4b)$$

where ‘dimension’ is *not* the dimension of the underlying space-time, of course.

module type $T =$

sig
type t

Constructor: $(k, N) \rightarrow p = \sum_{n \in N} \bar{p}_n$ and $k = \dim(p)$ is the *overall* number of independent momenta, while $\text{rank}(p) = |N|$ is the number of momenta in p . It would be possible to fix \dim as a functor argument instead. This might be slightly faster and allow a few more compile time checks, but would be much more tedious to use, since the number of particles will be chosen at runtime.

val $of_ints : int \rightarrow int\ list \rightarrow t$

No two indices may be the same. Implementations of of_ints can either raise the exception *Duplicate* or ignore the duplicate, but implementations of add are required to raise *Duplicate*.

exception *Duplicate* of *int*

Raise *Range* iff $n > k$:

exception *Range* of *int*

Binary operations require that both momenta have the same dimension. *Mismatch* is raised if this condition is violated.

exception *Mismatch* of $string \times t \times t$

Negative is raised if the result of *sub* is undefined.

exception *Negative*

The inverses of the constructor (we have $rank\ p = List.length\ (to_ints\ p)$, but *rank* might be more efficient):

```
val to_ints : t → int list
val dim   : t → int
val rank  : t → int
```

Shortcuts: $singleton\ d\ p = of_ints\ d\ [p]$ and $zero\ d = of_ints\ d\ []$:

```
val singleton : int → int → t
val zero      : int → t
```

An arbitrary total order, with the condition $rank(p_1) < rank(p_2) \Rightarrow p_1 < p_2$.

```
val compare : t → t → int
```

Use momentum conservation to construct the negative momentum with positive coefficients:

```
val neg : t → t
```

Return the momentum or its negative, whichever has the lower rank. NB: the present implementation does *not* guarantee that

$$abs\ p = abs\ q \iff p = p \vee p = -q \quad (5.5)$$

for momenta with $rank = dim/2$.

```
val abs : t → t
```

Add and subtract momenta. This can fail, since the coefficients c_k must be either 0 or 1.

```
val add : t → t → t
val sub : t → t → t
```

Once more, but not raising exceptions this time:

```
val try_add : t → t → t option
val try_sub : t → t → t option
```

Not the total order provided by *compare*, but set inclusion of non-zero coefficients instead:

```
val less : t → t → bool
val lesseq : t → t → bool
```

$$p_1 + (\pm p_2) + (\pm p_3) = 0$$

$$\text{val } \text{try_fusion} : t \rightarrow t \rightarrow t \rightarrow (bool \times bool) \text{ option}$$

A textual representation for debugging:

$$\text{val } \text{to_string} : t \rightarrow \text{string}$$

split i n p splits \bar{p}_i into n momenta $\bar{p}_i \rightarrow \bar{p}_i + \bar{p}_{i+1} + \dots + \bar{p}_{i+n-1}$ and makes room via $\bar{p}_{j>i} \rightarrow \bar{p}_{j+n-1}$. This is used for implementating cascade decays, like combining

$$e^+(p_1)e^-(p_2) \rightarrow W^-(p_3)\nu_e(p_4)e^+(p_5) \quad (5.6a)$$

$$W^-(p_3) \rightarrow d(p'_3)\bar{u}(p'_4) \quad (5.6b)$$

to

$$e^+(p_1)e^-(p_2) \rightarrow d(p_3)\bar{u}(p_4)\nu_e(p_5)e^+(p_6) \quad (5.7)$$

in narrow width approximation for the W^- .

$$\text{val } \text{split} : \text{int} \rightarrow \text{int} \rightarrow t \rightarrow t$$

5.1.1 Scattering Kinematics

From here on, we assume scattering kinematics $\{1, 2\} \rightarrow \{3, 4, \dots\}$, i. e. $n_{\text{in}} = 2$.



Since functions like *timelike* can be used for decays as well (in which case they must *always* return **true**, the representation—and consequently the constructors—should be extended by a flag discriminating between the two cases!

module *Scattering* :

sig

Test if the momentum is an incoming one: $p = \bar{p}_1 \vee p = \bar{p}_2$

$$\text{val } \text{incoming} : t \rightarrow bool$$

$$p = \bar{p}_3 \vee p = \bar{p}_4 \vee \dots$$

$$\text{val } \text{outgoing} : t \rightarrow bool$$

$p^2 \geq 0$. NB: *par abus de langage*, we report the incoming individual momenta as spacelike, instead as timelike. This will be useful for phasespace constructions below.

$$\text{val } \text{timelike} : t \rightarrow bool$$

$p^2 \leq 0$. NB: the simple algebraic criterion can be violated for heavy initial state particles.

$$\text{val } \text{spacelike} : t \rightarrow bool$$

$$p = \bar{p}_1 + \bar{p}_2$$

$$\text{val } \text{s_channel_in} : t \rightarrow bool$$

$$p = \bar{p}_3 + \bar{p}_4 + \dots + \bar{p}_n$$

```

    val s_channel_out : t → bool
p =  $\bar{p}_1 + \bar{p}_2 \vee p = \bar{p}_3 + \bar{p}_4 + \dots + \bar{p}_n$ 
    val s_channel : t → bool
 $\bar{p}_1 + \bar{p}_2 \rightarrow \bar{p}_3 + \bar{p}_4 + \dots + \bar{p}_n$ 
    val flip_s_channel_in : t → t
end

```

5.1.2 Decay Kinematics

```

module Decay :
  sig
    Test if the momentum is an incoming one:  $p = \bar{p}_1$ 
    val incoming : t → bool
 $p = \bar{p}_2 \vee p = \bar{p}_3 \vee \dots$ 
    val outgoing : t → bool
 $p^2 \geq 0$ . NB: here, we report the incoming individual momenta as timelike.
    val timelike : t → bool
 $p^2 \leq 0$ .
    val spacelike : t → bool
  end
  val rcs : RCS.t
end
module Lists : T
module Bits : T
module Default : T

```

Wolfgang's funny tree codes:

$$(2^n, 2^{n-1}) \rightarrow (1, 2, 4, \dots, 2^{n-2}) \quad (5.8)$$

```

module type Whizard =
  sig
    type t
    val of_momentum : t → int
    val to_momentum : int → int → t
  end
module ListsW : Whizard with type t = Lists.t
module BitsW : Whizard with type t = Bits.t
module DefaultW : Whizard with type t = Default.t

```

5.2 Implementation of *Momentum*

```

let rcs_file = RCS.parse "Momentum" ["Finite_disjoint_sums_of_momenta"]
{ RCS.revision = "$Revision: 4538$";
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
  RCS.author = "$Author: jr-reuter$";
  RCS.source
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
module type T =
sig
  type t
  val of_ints : int → int list → t
  exception Duplicate of int
  exception Range of int
  exception Mismatch of string × t × t
  exception Negative
  val to_ints : t → int list
  val dim : t → int
  val rank : t → int
  val singleton : int → int → t
  val zero : int → t
  val compare : t → t → int
  val neg : t → t
  val abs : t → t
  val add : t → t → t
  val sub : t → t → t
  val try_add : t → t → t option
  val try_sub : t → t → t option
  val less : t → t → bool
  val lesseq : t → t → bool
  val try_fusion : t → t → t → (bool × bool) option
  val to_string : t → string
  val split : int → int → t → t
  module Scattering :
    sig
      val incoming : t → bool
      val outgoing : t → bool
      val timelike : t → bool
      val spacelike : t → bool
      val s_channel_in : t → bool
      val s_channel_out : t → bool
      val s_channel : t → bool
      val flip_s_channel_in : t → t
    end
  module Decay :
    sig
      val incoming : t → bool
      val outgoing : t → bool
      val timelike : t → bool

```

```

    val spacelike : t → bool
  end
  val rcs : RCS.t
end

```

5.2.1 Lists of Integers

The first implementation (as part of *Fusion*) was based on sorted lists, because I did not want to preclude the use of more general indices than integers. However, there's probably not much use for this generality (the indices are typically generated automatically and integer are the most natural choice) and it is no longer supported by the current signature. Thus one can also use the more efficient implementation based on bitvectors below.

```

module Lists =
  struct
    let rcs = RCS.rename rcs_file "Momentum.Lists()"
      (RCS.description rcs_file @
       ["using_lists_as_representation."])

    type t = { d : int; r : int; p : int list }

    exception Range of int
    exception Duplicate of int

    let rec check d = function
      | p1 :: p2 :: _ when p2 ≤ p1 → raise (Duplicate p1)
      | p1 :: (p2 :: _ as rest) → check d rest
      | [p] when p < 1 ∨ p > d → raise (Range p)
      | [p] → ()
      | [] → ()

    let of_ints d p =
      let p' = List.sort compare p in
      check d p';
      { d = d; r = List.length p; p = p' }

    let to_ints p = p.p
    let dim p = p.d
    let rank p = p.r
    let zero d = { d = d; r = 0; p = [] }
    let singleton d p = { d = d; r = 1; p = [p] }

    let to_string p =
      "[" ^ String.concat "," (List.map string_of_int p.p) ^
      "/" ^ string_of_int p.r ^ "/" ^ string_of_int p.d ^ "]"

    exception Mismatch of string × t × t
    let mismatch s p1 p2 = raise (Mismatch (s, p1, p2))

    let matching f s p1 p2 =
      if p1.d = p2.d then
        f p1 p2

```

```

else
  mismatch s p1 p2
let compare p1 p2 =
  if p1.d = p2.d then begin
    let c = compare p1.r p2.r in
    if c ≠ 0 then
      c
    else
      compare p1.p p2.p
  end else
    mismatch "compare" p1 p2
let rec neg' d i = function
| [] →
  if i ≤ d then
    i :: neg' d (succ i) []
  else
    []
| i' :: rest as p →
  if i' > d then
    failwith "Integer_List.neg: internal error"
  else if i' = i then
    neg' d (succ i) rest
  else
    i :: neg' d (succ i) p
let neg p = { d = p.d; r = p.d - p.r; p = neg' p.d 1 p.p }
let abs p =
  if 2 × p.r > p.d then
    neg p
  else
    p
let rec add' p1 p2 =
  match p1, p2 with
  | [], p → p
  | p, [] → p
  | x1 :: p1', x2 :: p2' →
    if x1 < x2 then
      x1 :: add' p1' p2
    else if x2 < x1 then
      x2 :: add' p1 p2'
    else
      raise (Duplicate x1)
let add p1 p2 =
  if p1.d = p2.d then
    { d = p1.d; r = p1.r + p2.r; p = add' p1.p p2.p }
  else
    mismatch "add" p1 p2

```

```

let rec try_add' d r acc p1 p2 =
  match p1, p2 with
  | [], p → Some ({ d = d; r = r; p = List.rev_append acc p })
  | p, [] → Some ({ d = d; r = r; p = List.rev_append acc p })
  | x1 :: p1', x2 :: p2' →
    if x1 < x2 then
      try_add' d r (x1 :: acc) p1' p2
    else if x2 < x1 then
      try_add' d r (x2 :: acc) p1 p2'
    else
      None

let try_add p1 p2 =
  if p1.d = p2.d then
    try_add' p1.d (p1.r + p2.r) [] p1.p p2.p
  else
    mismatch "try_add" p1 p2

exception Negative

let rec sub' p1 p2 =
  match p1, p2 with
  | p, [] → p
  | [], - → raise Negative
  | x1 :: p1', x2 :: p2' →
    if x1 < x2 then
      x1 :: sub' p1' p2
    else if x1 = x2 then
      sub' p1' p2'
    else
      raise Negative

let rec sub p1 p2 =
  if p1.d = p2.d then begin
    if p1.r ≥ p2.r then
      { d = p1.d; r = p1.r - p2.r; p = sub' p1.p p2.p }
    else
      neg (sub p2 p1)
  end else
    mismatch "sub" p1 p2

let rec try_sub' d r acc p1 p2 =
  match p1, p2 with
  | p, [] → Some ({ d = d; r = r; p = List.rev_append acc p })
  | [], - → None
  | x1 :: p1', x2 :: p2' →
    if x1 < x2 then
      try_sub' d r (x1 :: acc) p1' p2
    else if x1 = x2 then
      try_sub' d r acc p1' p2'
    else
      None

```

```

let try_sub p1 p2 =
  if p1.d = p2.d then begin
    if p1.r ≥ p2.r then
      try_sub' p1.d (p1.r - p2.r) [] p1.p p2.p
    else
      match try_sub' p1.d (p2.r - p1.r) [] p2.p p1.p with
      | None → None
      | Some p → Some (neg p)
  end else
    mismatch "try_sub" p1 p2

let rec less' equal p1 p2 =
  match p1, p2 with
  | [], [] → ¬ equal
  | [], _ → true
  | x1 :: _, [] → false
  | x1 :: p1', x2 :: p2' when x1 = x2 → less' equal p1' p2'
  | x1 :: p1', x2 :: p2' → less' false p1 p2'

let less p1 p2 =
  if p1.d = p2.d then
    less' true p1.p p2.p
  else
    mismatch "sub" p1 p2

let rec lesseq' p1 p2 =
  match p1, p2 with
  | [], _ → true
  | x1 :: _, [] → false
  | x1 :: p1', x2 :: p2' when x1 = x2 → lesseq' p1' p2'
  | x1 :: p1', x2 :: p2' → lesseq' p1 p2'

let lesseq p1 p2 =
  if p1.d = p2.d then
    lesseq' p1.p p2.p
  else
    mismatch "lesseq" p1 p2

module Scattering =
struct
  let incoming p =
    if p.r = 1 then
      match p.p with
      | [1] | [2] → true
      | _ → false
    else
      false

  let outgoing p =
    if p.r = 1 then
      match p.p with
      | [1] | [2] → false
      | _ → true

```

```

    else
      false

let s_channel_in p =
  match p.p with
  | [1; 2] → true
  | _ → false

let rec s_channel_out' d i = function
  | [] → i = succ d
  | i' :: p when i' = i → s_channel_out' d (succ i) p
  | _ → false

let s_channel_out p =
  match p.p with
  | 3 :: p' → s_channel_out' p.d 4 p'
  | _ → false

let s_channel p = s_channel_in p ∨ s_channel_out p

let timelike p =
  match p.p with
  | p1 :: p2 :: _ → p1 > 2 ∨ (p1 = 1 ∧ p2 = 2)
  | p1 :: _ → p1 > 2
  | [] → false

let spacelike p = ¬ (timelike p)

let flip_s_channel_in p =
  if s_channel_in p then
    neg (of_ints p.d [1; 2])
  else
    p

end

module Decay =
  struct

    let incoming p =
      if p.r = 1 then
        match p.p with
        | [1] → true
        | _ → false
      else
        false

    let outgoing p =
      if p.r = 1 then
        match p.p with
        | [1] → false
        | _ → true
      else
        false

    let timelike p =

```

```

    match p.p with
    | [1] → true
    | p1 :: _ → p1 > 1
    | [] → false

    let spacelike p = ¬ (timelike p)

end

let test_sum p inv1 p1 inv2 p2 =
  if p.d = p1.d then begin
    if p.d = p2.d then begin
      match (if inv1 then try_add else try_sub) p p1 with
      | None → false
      | Some p' →
        begin match (if inv2 then try_add else try_sub) p' p2 with
        | None → false
        | Some p'' → p''.r = 0 ∨ p''.r = p.d
        end
      end else
        mismatch "test_sum" p p2
    end else
      mismatch "test_sum" p p1

let try_fusion p p1 p2 =
  if test_sum p false p1 false p2 then
    Some (false, false)
  else if test_sum p true p1 false p2 then
    Some (true, false)
  else if test_sum p false p1 true p2 then
    Some (false, true)
  else if test_sum p true p1 true p2 then
    Some (true, true)
  else
    None

let split i n p =
  let n' = n - 1 in
  let rec split' head = function
    | [] → (p.r, List.rev head)
    | i1 :: ilist →
      if i1 < i then
        split' (i1 :: head) ilist
      else if i1 > i then
        (p.r, List.rev_append head (List.map ((+) n') (i1 :: ilist)))
      else
        (p.r + n',
         List.rev_append head
          ((ThoList.range i1 (i1 + n')) @ (List.map ((+) n') ilist))) in
  let r', p' = split' [] p.p in
  { d = p.d + n'; r = r'; p = p' }

end

```


5.2.2 Bit Fiddlings

Bit vectors are popular in Fortran based implementations [1, 2, 11] and can be more efficient. In particular, when all information is packed into a single integer, much of the memory overhead is reduced.

```
module Bits =
  struct
    let rcs = RCS.rename rcs_file "Momentum.Bits()"
      (RCS.description rcs_file @
       [ "using_bitfields_as_representation." ])

    type t = int
```

Bits 1...21 are used as a bitvector, indicating whether a particular momentum is included. Bits 22...26 represent the numbers of bits set in bits 1...21 and bits 27...31 denote the maximum number of momenta.

```
let mask n = (1 lsl n) - 1
let mask2 = mask 2
let mask5 = mask 5
let mask21 = mask 21

let maskd = mask5 lsl 26
let maskr = mask5 lsl 21
let maskb = mask21

let dim0 p = p land maskd
let rank0 p = p land maskr
let bits0 p = p land maskb

let dim p = (dim0 p) lsr 26
let rank p = (rank0 p) lsr 21
let bits p = bits0 p

let drb0 d r b = d lor r lor b
let drb d r b = d lsl 26 lor r lsl 21 lor b
```

For a 64-bit architecture, the corresponding sizes could be increased to 1...51, 52...57, and 58...63. However, the combinatorical complexity will have killed us long before we can reach these values.

```
exception Range of int
exception Duplicate of int

exception Mismatch of string × t × t
let mismatch s p1 p2 = raise (Mismatch (s, p1, p2))

let of_ints d p =
  let r = List.length p in
  if d ≤ 21 ∧ r ≤ 21 then begin
    List.fold_left (fun b p' →
      if p' ≤ d then
        b lor (1 lsl (pred p'))
```

```

      else
        raise (Range p') (drb d r 0) p
    end else
      raise (Range r)
  let zero d = drb d 0 0
  let singleton d p = drb d 1 (1 lsl (pred p))
  let rec to_ints' acc p b =
    if b = 0 then
      List.rev acc
    else if (b land 1) = 1 then
      to_ints' (p :: acc) (succ p) (b lsr 1)
    else
      to_ints' acc (succ p) (b lsr 1)
  let to_ints p = to_ints' [] 1 (bits p)
  let to_string p =
    "[" ^ String.concat "," (List.map string_of_int (to_ints p)) ^
    "/" ^ string_of_int (rank p) ^ "/" ^ string_of_int (dim p) ^ "]"
  let compare p1 p2 =
    if dim0 p1 = dim0 p2 then begin
      let c = compare (rank0 p1) (rank0 p2) in
      if c ≠ 0 then
        c
      else
        compare (bits p1) (bits p2)
    end else
      mismatch "compare" p1 p2
  let neg p =
    let d = dim p and r = rank p in
    drb d (d - r) ((mask d) land (lnot p))
  let abs p =
    if 2 × (rank p) > dim p then
      neg p
    else
      p
  let add p1 p2 =
    let d1 = dim0 p1 and d2 = dim0 p2 in
    if d1 = d2 then begin
      let b1 = bits p1 and b2 = bits p2 in
      if b1 land b2 = 0 then
        drb0 d1 (rank0 p1 + rank0 p2) (b1 lor b2)
      else
        raise (Duplicate 0)
    end else
      mismatch "add" p1 p2
exception Negative

```

```

let rec sub p1 p2 =
  let d1 = dim0 p1 and d2 = dim0 p2 in
  if d1 = d2 then begin
    let r1 = rank0 p1 and r2 = rank0 p2 in
    if r1 ≥ r2 then begin
      let b1 = bits p1 and b2 = bits p2 in
      if b1 lor b2 = b1 then
        drb0 d1 (r1 - r2) (b1 lxor b2)
      else
        raise Negative
    end else
      neg (sub p2 p1)
  end else
    mismatch "sub" p1 p2

let try_add p1 p2 =
  let d1 = dim0 p1 and d2 = dim0 p2 in
  if d1 = d2 then begin
    let b1 = bits p1 and b2 = bits p2 in
    if b1 land b2 = 0 then
      Some (drb0 d1 (rank0 p1 + rank0 p2) (b1 lor b2))
    else
      None
  end else
    mismatch "try_add" p1 p2

let rec try_sub p1 p2 =
  let d1 = dim0 p1 and d2 = dim0 p2 in
  if d1 = d2 then begin
    let r1 = rank0 p1 and r2 = rank0 p2 in
    if r1 ≥ r2 then begin
      let b1 = bits p1 and b2 = bits p2 in
      if b1 lor b2 = b1 then
        Some (drb0 d1 (r1 - r2) (b1 lxor b2))
      else
        None
    end else
      begin match try_sub p2 p1 with
        | Some p → Some (neg p)
        | None → None
      end
  end else
    mismatch "sub" p1 p2

let lesseq p1 p2 =
  let d1 = dim0 p1 and d2 = dim0 p2 in
  if d1 = d2 then begin
    let r1 = rank0 p1 and r2 = rank0 p2 in
    if r1 ≤ r2 then begin
      let b1 = bits p1 and b2 = bits p2 in
      b1 lor b2 = b2
    end else

```

```

    false
  end else
    mismatch "less" p1 p2
  let less p1 p2 = p1 ≠ p2 ∧ lesseq p1 p2
  let mask_in1 = 1
  let mask_in2 = 2
  let mask_in = mask_in1 lor mask_in2
  module Scattering =
    struct
      let incoming p =
        rank p = 1 ∧ (mask_in land p ≠ 0)
      let outgoing p =
        rank p = 1 ∧ (mask_in land p = 0)
      let timelike p =
        (rank p > 0 ∧ (mask_in land p = 0)) ∨ (bits p = mask_in)
      let spacelike p =
        (rank p > 0) ∧ ¬ (timelike p)
      let s_channel_in p =
        bits p = mask_in
      let s_channel_out p =
        rank p > 0 ∧ (mask_in lxor p = 0)
      let s_channel p =
        s_channel_in p ∨ s_channel_out p
      let flip_s_channel_in p =
        if s_channel_in p then
          neg p
        else
          p
      end
    end
  module Decay =
    struct
      let incoming p =
        rank p = 1 ∧ (mask_in1 land p = mask_in1)
      let outgoing p =
        rank p = 1 ∧ (mask_in1 land p = 0)
      let timelike p =
        incoming p ∨ (rank p > 0 ∧ mask_in1 land p = 0)
      let spacelike p =
        ¬ (timelike p)
      end
    end
  let test_sum p inv1 p1 inv2 p2 =

```

```

let  $d = \text{dim } p$  in
if  $d = \text{dim } p1$  then begin
  if  $d = \text{dim } p2$  then begin
    match (if  $\text{inv1}$  then  $\text{try\_add}$  else  $\text{try\_sub}$ )  $p \ p1$  with
    |  $\text{None} \rightarrow \text{false}$ 
    |  $\text{Some } p' \rightarrow$ 
      begin match (if  $\text{inv2}$  then  $\text{try\_add}$  else  $\text{try\_sub}$ )  $p' \ p2$  with
      |  $\text{None} \rightarrow \text{false}$ 
      |  $\text{Some } p'' \rightarrow$ 
        let  $r = \text{rank } p''$  in
         $r = 0 \vee r = d$ 
      end
    end else
      mismatch "test_sum"  $p \ p2$ 
  end else
    mismatch "test_sum"  $p \ p1$ 
let  $\text{try\_fusion } p \ p1 \ p2 =$ 
  if  $\text{test\_sum } p \ \text{false } p1 \ \text{false } p2$  then
     $\text{Some } (\text{false}, \text{false})$ 
  else if  $\text{test\_sum } p \ \text{true } p1 \ \text{false } p2$  then
     $\text{Some } (\text{true}, \text{false})$ 
  else if  $\text{test\_sum } p \ \text{false } p1 \ \text{true } p2$  then
     $\text{Some } (\text{false}, \text{true})$ 
  else if  $\text{test\_sum } p \ \text{true } p1 \ \text{true } p2$  then
     $\text{Some } (\text{true}, \text{true})$ 
  else
     $\text{None}$ 

```

First create a gap of size $n - 1$ and subsequently fill it if and only if the bit i was set.

```

let  $\text{split } i \ n \ p =$ 
  let  $\text{delta\_d} = n - 1$ 
  and  $b = \text{bits } p$  in
  let  $\text{mask\_low} = \text{mask } (\text{pred } i)$ 
  and  $\text{mask\_i} = 1 \ \text{ls1 } (\text{pred } i)$ 
  and  $\text{mask\_high} = \text{lnot } (\text{mask } i)$  in
  let  $b\_low = \text{mask\_low} \ \text{land } b$ 
  and  $b\_med, \text{delta\_r} =$ 
    if  $\text{mask\_i} \ \text{land } b \neq 0$  then
       $((\text{mask } n) \ \text{ls1 } (\text{pred } i), \text{delta\_d})$ 
    else
       $(0, 0)$ 
  and  $b\_high =$ 
    if  $\text{delta\_d} > 0$  then
       $(\text{mask\_high} \ \text{land } b) \ \text{ls1 } \text{delta\_d}$ 
    else if  $\text{delta\_d} = 0$  then
       $\text{mask\_high} \ \text{land } b$ 
    else
       $(\text{mask\_high} \ \text{land } b) \ \text{lsr } (-\text{delta\_d})$  in
   $\text{drb } (\text{dim } p + \text{delta\_d}) \ (\text{rank } p + \text{delta\_r}) \ (b\_low \ \text{lor } b\_med \ \text{lor } b\_high)$ 

```

end

5.2.3 Whizard

```

module type Whizard =
sig
  type t
  val of_momentum : t → int
  val to_momentum : int → int → t
end

module BitsW =
struct
  type t = Bits.t
  open Bits (* NB: this includes the internal functions not in T! *)

  let of_momentum p =
    let d = dim p in
    let bit_in1 = 1 land p
    and bit_in2 = 1 land (p lsr 1)
    and bits_out = ((mask d) land p) lsr 2 in
    bits_out lor (bit_in1 lsl (d - 1)) lor (bit_in2 lsl (d - 2))

  let rec count_non_zero' acc i last b =
    if i > last then
      acc
    else if (1 lsl (pred i)) land b = 0 then
      count_non_zero' acc (succ i) last b
    else
      count_non_zero' (succ acc) (succ i) last b

  let count_non_zero first last b =
    count_non_zero' 0 first last b

  let to_momentum d w =
    let bit_in1 = 1 land (w lsr (d - 1))
    and bit_in2 = 1 land (w lsr (d - 2))
    and bits_out = (mask (d - 2)) land w in
    let b = (bits_out lsl 2) lor bit_in1 lor (bit_in2 lsl 1) in
    drb d (count_non_zero 1 d b) b
end

```

The following would be a tad more efficient, if coded directly, but there's no point in wasting effort on this.

```

module ListsW =
struct
  type t = Lists.t
  let of_momentum p =
    BitsW.of_momentum (Bits.of_ints p.Lists.d p.Lists.p)
  let to_momentum d w =

```

```

    Lists.of_ints d (Bits.to_ints (BitsW.to_momentum d w))
end

```

5.2.4 Suggesting a Default Implementation

Lists is better tested, but the more recent *Bits* appears to work as well and is *much* more efficient, resulting in a relative factor of better than 2. This performance ratio is larger than I had expected and we are not likely to reach its limit of 21 independent vectors anyway.

```

module Default = Bits
module DefaultW = BitsW

```

—6—

CASCADES

6.1 Interface of *Cascade_syntax*

```
type ('flavor, 'p) t =
| True
| False
| On_shell of 'flavor list × 'p
| On_shell_not of 'flavor list × 'p
| Off_shell of 'flavor list × 'p
| Off_shell_not of 'flavor list × 'p
| Gauss of 'flavor list × 'p
| Gauss_not of 'flavor list × 'p
| Any_flavor of 'p
| Or of ('flavor, 'p) t list
| And of ('flavor, 'p) t list

val mk_true : unit → ('flavor, 'p) t
val mk_false : unit → ('flavor, 'p) t
val mk_on_shell : 'flavor list → 'p → ('flavor, 'p) t
val mk_on_shell_not : 'flavor list → 'p → ('flavor, 'p) t
val mk_off_shell : 'flavor list → 'p → ('flavor, 'p) t
val mk_off_shell_not : 'flavor list → 'p → ('flavor, 'p) t
val mk_gauss : 'flavor list → 'p → ('flavor, 'p) t
val mk_gauss_not : 'flavor list → 'p → ('flavor, 'p) t
val mk_any_flavor : 'p → ('flavor, 'p) t
val mk_or : ('flavor, 'p) t → ('flavor, 'p) t → ('flavor, 'p) t
val mk_and : ('flavor, 'p) t → ('flavor, 'p) t → ('flavor, 'p) t

val to_string : ('flavor → string) → ('p → string) → ('flavor, 'p) t →
  string

exception Syntax_Error of string × int × int
```

6.2 Implementation of *Cascade_syntax*

Concerning the Gaussian propagators, we admit the following: In principle, they would allow for flavor sums like the off-shell lines, but for all practical purposes

they are used only for determining the significance of a specified intermediate state. So we select them in the same manner as on-shell states.

```

type ('flavor, 'p) t =
  | True
  | False
  | On_shell of 'flavor list × 'p
  | On_shell_not of 'flavor list × 'p
  | Off_shell of 'flavor list × 'p
  | Off_shell_not of 'flavor list × 'p
  | Gauss of 'flavor list × 'p
  | Gauss_not of 'flavor list × 'p
  | Any_flavor of 'p
  | Or of ('flavor, 'p) t list
  | And of ('flavor, 'p) t list

let mk_true () = True
let mk_false () = False
let mk_on_shell f p = On_shell (f, p)
let mk_on_shell_not f p = On_shell_not (f, p)
let mk_off_shell f p = Off_shell (f, p)
let mk_off_shell_not f p = Off_shell_not (f, p)
let mk_gauss f p = Gauss (f, p)
let mk_gauss_not f p = Gauss_not (f, p)
let mk_any_flavor p = Any_flavor p

let mk_or c1 c2 =
  match c1, c2 with
  | -, True | True, - → True
  | c, False | False, c → c
  | Or cs, Or cs' → Or (cs @ cs')
  | Or cs, c | c, Or cs → Or (c :: cs)
  | c, c' → Or [c; c']

let mk_and c1 c2 =
  match c1, c2 with
  | c, True | True, c → c
  | c, False | False, c → False
  | And cs, And cs' → And (cs @ cs')
  | And cs, c | c, And cs → And (c :: cs)
  | c, c' → And [c; c']

let to_string flavor_to_string momentum_to_string cascades =
  let rec to_string' = function
    | True → "true"
    | False → "false"
    | On_shell (fs, p) →
        momentum_to_string p ^ "□=□" ^ (String.concat ":" (List.map flavor_to_string fs))
    | On_shell_not (fs, p) →
        momentum_to_string p ^ "□=□!" ^ (String.concat ":" (List.map flavor_to_string fs))
    | Off_shell (fs, p) →
        momentum_to_string p ^ "□~□" ^
        (String.concat ":" (List.map flavor_to_string fs))

```

```

| Off_shell_not (fs, p) →
  momentum_to_string p ^ "□~□!" ^
  (String.concat ":" (List.map flavor_to_string fs))
| Gauss (fs, p) →
  momentum_to_string p ^ "□#□" ^ (String.concat ":" (List.map flavor_to_string fs))
| Gauss_not (fs, p) →
  momentum_to_string p ^ "□#□!" ^ (String.concat ":" (List.map flavor_to_string fs))
| Any_flavor p →
  momentum_to_string p ^ "□~□?"
| Or cs →
  String.concat "□||□" (List.map (fun c → "(" ^ to_string' c ^ ")") cs)
| And cs →
  String.concat "□&□" (List.map (fun c → "(" ^ to_string' c ^ ")") cs) in
to_string' cascades

let int_list_to_string p =
  String.concat "+" (List.map string_of_int (Sort.list (<) p))

exception Syntax_Error of string × int × int

```

6.3 Lexer

```

{
open Cascade_parser
let unquote s =
  String.sub s 1 (String.length s - 2)
}

let digit = ['0'-'9']
let upper = ['A'-'Z']
let lower = ['a'-'z']
let char = upper | lower
let white = [' ' '\t' '\n']

```

We use a very liberal definition of strings for flavor names.

```

rule token = parse
  white { token lexbuf } (* skip blanks *)
| '%' [^'\n']* '\n'
  { token lexbuf } (* skip comments *)
| digit+ { INT (int_of_string (Lexing.lexeme lexbuf)) }
| '+' { PLUS }
| ':' { COLON }
| '~' { OFFSHELL }
| '=' { ONSHELL }
| '#' { GAUSS }
| '!' { NOT }
| '&' '&'? { AND }
| '|' '|'? { OR }
| '(' { LPAREN }
| ')' { RPAREN }

```

```

| char [ ^ ' , ' , \t ' , \n ' , | ' , & ' , ( ' , ) ' , : ' , ] *
      { FLAVOR (Lexing.lexeme lexbuf) }
| ' ' ' [ ^ ' ' ' ] * ' ' '
      { FLAVOR (unquote (Lexing.lexeme lexbuf)) }
| eof { END }

```

6.4 Parser

Header

```

open Cascade_syntax
let parse_error msg =
  raise (Syntax_Error (msg, symbol_start (), symbol_end ()))

```

Token declarations

```

%token < string > FLAVOR
%token < int > INT
%token LPAREN RPAREN
%token AND OR PLUS COLON NOT
%token ONSHELL OFFSHELL GAUSS
%token END
%left OR
%left AND
%left PLUS COLON
%left NOT

%start main
%type < (string, int list) Cascade_syntax.t > main

```

Grammar rules

```

main ::=
  END { mk_true () }
| cascades END { $1 }

cascades ::=
  cascade { $1 }
| LPAREN cascades RPAREN { $2 }
| cascades AND cascades { mk_and $1 $3 }
| cascades OR cascades { mk_or $1 $3 }

```

```

cascade ::=
  | momentum_list { mk_any_flavor $1 }
  | momentum_list ONSHELL flavor_list { mk_on_shell $3 $1 }
  | momentum_list ONSHELL NOT flavor_list { mk_on_shell_not $4 $1 }
  | momentum_list OFFSHELL flavor_list { mk_off_shell $3 $1 }
  | momentum_list OFFSHELL NOT flavor_list { mk_off_shell_not $4 $1 }
  | momentum_list GAUSS flavor_list { mk_gauss $3 $1 }
  | momentum_list GAUSS NOT flavor_list { mk_gauss_not $4 $1 }

momentum_list ::=
  | momentum { [$1] }
  | momentum_list PLUS momentum { $3 :: $1 }

momentum ::=
  | INT { $1 }

flavor_list ::=
  | FLAVOR { [$1] }
  | flavor_list COLON FLAVOR { $3 :: $1 }

```

6.5 Interface of *Cascade*

```

module type T =
  sig
    type flavor
    type p
    type t
    val of_string_list : int → string list → t
    val to_string : t → string

```

An opaque type that describes the set of all constraints on an amplitude and how to construct it from a cascade description.

```

  type selectors
  val to_selectors : t → selectors

```

Don't throw anything away:

```

  val no_cascades : selectors

```

select_wf *s* *is_timelike* *f* *p* *ps* returns true iff either

- the flavor *f* and momentum *p* match the selection *s* or

- *all* combinations of the momenta in *ps* are compatible, i. e. $\pm \sum p_i \leq q$.

The latter test is only required in theories with quartic or higher vertices, where *ps* will be the list of all incoming momenta in a fusion. *is_timelike* is required to determine, whether particles and anti-particles should be distinct.

val select_wf : selectors → (p → bool) → flavor → p → p list → bool
select_p s p ps same as *select_wf s f p ps*, but ignores the flavor *f*

val select_p : selectors → p → p list → bool

on_shell s p

val on_shell : selectors → flavor → p → bool

is_gauss s p

val is_gauss : selectors → flavor → p → bool

partition s returns a partition of the external particles that can not be reordered without violating the cascade constraints.

val partition : selectors → int list list

Diagnostics:

val description : selectors → string option

end

module *Make* (*M* : *Model.T*) (*P* : *Momentum.T*) :
T with type *flavor* = *M.flavor* and type *p* = *P.t*

6.6 Implementation of *Cascade*

module type *T* =

sig

type *flavor*

type *p*

type *t*

val of_string_list : int → string list → t

val to_string : t → string

type *selectors*

val to_selectors : t → selectors

val no_cascades : selectors

val select_wf : selectors → (p → bool) → flavor → p → p list → bool

val select_p : selectors → p → p list → bool

val on_shell : selectors → flavor → p → bool

val is_gauss : selectors → flavor → p → bool

val partition : selectors → int list list

val description : selectors → string option

end

```

module Make (M : Model.T) (P : Momentum.T) :
  (T with type flavor = M.flavor and type p = P.t) =
  struct
    module CS = Cascade_syntax
    type flavor = M.flavor
    type p = P.t
  
```

Since we have

$$p \leq q \iff (-q) \leq (-p) \quad (6.1)$$

also for \leq as set inclusion *lesseq*, only four of the eight combinations are independent

$$\begin{aligned}
 p \leq q &\iff (-q) \leq (-p) \\
 q \leq p &\iff (-p) \leq (-q) \\
 p \leq (-q) &\iff q \leq (-p) \\
 (-q) \leq p &\iff (-p) \leq q
 \end{aligned} \quad (6.2)$$

```

let one_compatible p q =
  let neg_q = P.neg q in
  P.lesseq p q ∨
  P.lesseq q p ∨
  P.lesseq p neg_q ∨
  P.lesseq neg_q p
  
```

'tis wasteful ... (at least by a factor of two, because every momentum combination is generated, including the negative ones.

```

let all_compatible p p_list q =
  let l = List.length p_list in
  if l ≤ 2 then
    one_compatible p q
  else
    let tuple_lengths = ThoList.range 2 (succ l / 2) in
    let tuples = ThoList.flatmap (fun n → Combinatorics.choose n p_list) tuple_lengths in
    let momenta = List.map (List.fold_left P.add (P.zero (P.dim q))) tuples in
    List.for_all (one_compatible q) momenta
  
```

The following assumes that the *flavor list* is always very short. Otherwise one should use an efficient set implementation.

```

type t =
  | True
  | False
  | On_shell of flavor list × P.t
  | On_shell_not of flavor list × P.t
  | Off_shell of flavor list × P.t
  | Off_shell_not of flavor list × P.t
  | Gauss of flavor list × P.t
  | Gauss_not of flavor list × P.t
  | Any_flavor of P.t
  | And of t list
  
```

```
let of_string s =
  Cascade_parser.main Cascade_lexer.token (Lexing.from_string s)
```



If we knew that we're dealing with a scattering, we could apply *P.flip-s-channel-in* to all momenta, so that *1 + 2* accepts the particle and not the antiparticle. Right now, we don't have this information.

```
let import dim cascades =
  let rec import' = function
    | CS.True →
      True
    | CS.False →
      False
    | CS.On_shell (f, p) →
      On_shell (List.map M.flavor_of_string f, P.of_ints dim p)
    | CS.On_shell_not (f, p) →
      On_shell_not (List.map M.flavor_of_string f, P.of_ints dim p)
    | CS.Off_shell (fs, p) →
      Off_shell (List.map M.flavor_of_string fs, P.of_ints dim p)
    | CS.Off_shell_not (fs, p) →
      Off_shell_not (List.map M.flavor_of_string fs, P.of_ints dim p)
    | CS.Gauss (f, p) →
      Gauss (List.map M.flavor_of_string f, P.of_ints dim p)
    | CS.Gauss_not (f, p) →
      Gauss (List.map M.flavor_of_string f, P.of_ints dim p)
    | CS.Any_flavor p →
      Any_flavor (P.of_ints dim p)
    | CS.Or cs →
      invalid_arg "Cascade: OR patterns (||) not supported in this version!"
    | CS.And cs → And (List.map import' cs) in
  import' cascades

let of_string_list dim strings =
  match List.map of_string strings with
  | [] → True
  | first :: next →
    import dim (List.fold_right CS.mk_and next first)

let flavors_to_string fs =
  (String.concat ":" (List.map M.flavor_to_string fs))

let momentum_to_string p =
  String.concat "+" (List.map string_of_int (P.to_ints p))

let rec to_string = function
  | True →
    "true"
  | False →
    "false"
  | On_shell (fs, p) →
    momentum_to_string p ^ "=" ^ flavors_to_string fs
```

```

| On_shell_not (fs, p) →
  momentum_to_string p ^ "≡" ^ flavors_to_string fs
| Off_shell (fs, p) →
  momentum_to_string p ^ "≠" ^ flavors_to_string fs
| Off_shell_not (fs, p) →
  momentum_to_string p ^ "≠" ^ flavors_to_string fs
| Gauss (fs, p) →
  momentum_to_string p ^ "#" ^ flavors_to_string fs
| Gauss_not (fs, p) →
  momentum_to_string p ^ "#!" ^ flavors_to_string fs
| Any_flavor p →
  momentum_to_string p ^ "≠?"
| And cs →
  String.concat "&&" (List.map (fun c → "(" ^ to_string c ^ ")") cs)

type selectors =
{ select_p : p → p list → bool;
  select_wf : (p → bool) → flavor → p → p list → bool;
  on_shell : flavor → p → bool;
  is_gauss : flavor → p → bool;
  partition : int list list;
  description : string option }

let no_cascades =
{ select_p = (fun _ _ → true);
  select_wf = (fun _ _ _ → true);
  on_shell = (fun _ _ → false);
  is_gauss = (fun _ _ → false);
  partition = [];
  description = None }

let select_p s = s.select_p
let select_wf s = s.select_wf
let on_shell s = s.on_shell
let is_gauss s = s.is_gauss
let partition s = s.partition
let description s = s.description

let to_select_p cascades p p_in =
let rec to_select_p' = function
| True → true
| False → false
| On_shell (_, momentum) | On_shell_not (_, momentum)
| Off_shell (_, momentum) | Off_shell_not (_, momentum)
| Gauss (_, momentum) | Gauss_not (_, momentum)
| Any_flavor momentum → all_compatible p p_in momentum
| And [] → false
| And cs → List.for_all to_select_p' cs in
to_select_p' cascades

let to_select_wf cascades is_timelike f p p_in =
let f' = M.conjugate f in
let rec to_select_wf' = function

```



```

| True → true
| False → false
| Off_shell (flavors, momentum) →
  if p = momentum then
    List.mem f' flavors ∨ (if is_timelike p then false else List.mem f flavors)
  else if p = P.neg momentum then
    List.mem f flavors ∨ (if is_timelike p then false else List.mem f' flavors)
  else
    one_compatible p momentum ∧ all_compatible p p_in momentum
| On_shell (flavors, momentum) | Gauss (flavors, momentum) →
  if is_timelike p then begin
    if p = momentum then
      List.mem f' flavors
    else if p = P.neg momentum then
      List.mem f flavors
    else
      one_compatible p momentum ∧ all_compatible p p_in momentum
  end else
    false
| Off_shell_not (flavors, momentum) →
  if p = momentum then
    ¬ (List.mem f' flavors ∨ (if is_timelike p then false else List.mem f flavors))
  else if p = P.neg momentum then
    ¬ (List.mem f flavors ∨ (if is_timelike p then false else List.mem f' flavors))
  else
    one_compatible p momentum ∧ all_compatible p p_in momentum
| On_shell_not (flavors, momentum) | Gauss_not (flavors, momentum) →

  if is_timelike p then begin
    if p = momentum then
      ¬ (List.mem f' flavors)
    else if p = P.neg momentum then
      ¬ (List.mem f flavors)
    else
      one_compatible p momentum ∧ all_compatible p p_in momentum
  end else
    false
| Any_flavor momentum →
  one_compatible p momentum ∧ all_compatible p p_in momentum
| And [] → false
| And cs → List.for_all to_select_wf' cs in
to_select_wf' cascades

```

In case you're wondering: *to_on_shell f p* and *is_gauss f p* only search for on shell conditions and are to be used in a target, not in *Fusion*!

```

let to_on_shell cascades f p =
  let f' = M.conjugate f in
  let rec to_on_shell' = function
    | True | False | Any_flavor _
    | Off_shell (_, _) | Off_shell_not (_, _)

```

```

      | Gauss (_, _) | Gauss_not (_, _) → false
      | On_shell (flavors, momentum) →
        (p = momentum ∨ p = P.neg momentum) ∧ (List.mem f flavors ∨
List.mem f' flavors)
      | On_shell_not (flavors, momentum) →
        (p = momentum ∨ p = P.neg momentum) ∧ ¬ (List.mem f flavors ∨
List.mem f' flavors)
      | And [] → false
      | And cs → List.for_all to_on_shell' cs in
to_on_shell' cascades

let to_gauss cascades f p =
  let f' = M.conjugate f in
  let rec to_gauss' = function
    | True | False | Any_flavor _
    | Off_shell (_, _) | Off_shell_not (_, _)
    | On_shell (_, _) | On_shell_not (_, _) → false
    | Gauss (flavors, momentum) →
      (p = momentum ∨ p = P.neg momentum) ∧ (List.mem f flavors ∨
List.mem f' flavors)
    | Gauss_not (flavors, momentum) →
      (p = momentum ∨ p = P.neg momentum) ∧ ¬ (List.mem f flavors ∨
List.mem f' flavors)
    | And [] → false
    | And cs → List.for_all to_gauss' cs in
to_gauss' cascades

```



Not a working implementation yet, but it isn't used either ...

```

module IPowSet =
  PowSet.Make (struct type t = int let compare = compare let to_string = string_of_int end)

let rec coarsest_partition' = function
  | True | False → IPowSet.empty
  | On_shell (_, momentum) | On_shell_not (_, momentum)
  | Off_shell (_, momentum) | Off_shell_not (_, momentum)
  | Gauss (_, momentum) | Gauss_not (_, momentum)
  | Any_flavor momentum → IPowSet.of_lists [P.to_ints momentum]
  | And [] → IPowSet.empty
  | And cs → IPowSet.basis (IPowSet.union (List.map coarsest_partition' cs))

let coarsest_partition cascades =
  let p = coarsest_partition' cascades in
  if IPowSet.is_empty p then
    []
  else
    IPowSet.to_lists p

let part_to_string part =
  "{" ^ String.concat "," (List.map string_of_int part) ^ "}"

```

```

let partition_to_string = function
| [] → ""
| parts →
    "␣␣grouping␣{" ^ String.concat "," (List.map part_to_string parts) ^ "}"
let to_selectors = function
| True → no_cascades
| c →
    let partition = coarsest_partition c in
    { select_p = to_select_p c;
      select_wf = to_select_wf c;
      on_shell = to_on_shell c;
      is_gauss = to_gauss c;
      partition = partition;
      description = Some (to_string c ^ partition_to_string partition) }
end

```

—7—

COLOR

7.1 Interface of Color

7.1.1 Quantum Numbers

Color is not necessarily the $SU(3)$ of QCD. Conceptually, it can be any *unbroken* symmetry (*broken* symmetries correspond to *Model.flavor*). In order to keep the group theory simple, we confine ourselves to the fundamental and adjoint representation of a single $SU(N_C)$ for the moment. Therefore, particles are either color singlets or live in the defining representation of $SU(N_C)$: $SUN(|N_C|)$, its conjugate $SUN(-|N_C|)$ or in the adjoint representation of $SU(N_C)$: $AdjSUN(N_C)$.

```
type t = Singlet | SUN of int | AdjSUN of int
val conjugate : t → t
val compare : t → t → int
```

7.1.2 Color Flows

```
module type Flow =
sig
  type color
  type t = color list × color list
  val rank : t → int

  val of_list : int list → color
  val ghost : unit → color
  val to_lists : t → int list list
  val in_to_lists : t → int list list
  val out_to_lists : t → int list list
  val ghost_flags : t → bool list
  val in_ghost_flags : t → bool list
  val out_ghost_flags : t → bool list
```

A factor is a list of powers

$$\sum_i \left(\frac{num_i}{den_i} \right)^{power_i} \quad (7.1)$$

```

type power = { num : int; den : int; power : int }
type factor = power list

val factor : t → t → factor
val zero : factor

end

module Flow : Flow

```

7.2 Implementation of *Color*

7.2.1 Quantum Numbers

```

type t =
| Singlet
| SUN of int
| AdjSUN of int

let conjugate = function
| Singlet → Singlet
| SUN n → SUN (-n)
| AdjSUN n → AdjSUN n

let compare c1 c2 =
match c1, c2 with
| Singlet, Singlet → 0
| Singlet, _ → -1
| _, Singlet → 1
| SUN n, SUN n' → compare n n'
| SUN _, AdjSUN _ → -1
| AdjSUN _, SUN _ → 1
| AdjSUN n, AdjSUN n' → compare n n'

module type Line =
sig
  type t
  val conj : t → t
  val equal : t → t → bool
  val to_string : t → string
end

module type Cycles =
sig
  type line
  type t = (line × line) list

```

Contract the graph by connecting lines and return the number of cycles together with the contracted graph.



The semantics of the contracted graph is not yet 100%ly fixed.

```

val contract : t → int × t

```

The same as *contract*, but returns only the number of cycles and raises *Open_line* when not all lines are closed.

```

    val count : t → int
    exception Open_line

    Mainly for debugging ...

    val to_string : t → string

end

module Cycles (L : Line) : Cycles with type line = L.t =
struct
    type line = L.t
    type t = (line × line) list

    exception Open_line

```

NB: The following algorithm for counting the cycles is quadratic since it performs nested scans of the lists. If this was a serious problem one could replace the lists of pairs by a *Map* and replace one power by a logarithm.

```

let rec find_fst c_final c1 disc seen = function
| [] → ((L.conj c_final, c1) :: disc, List.rev seen)
| (c1', c2') as c12' :: rest →
    if L.equal c1 c1' then
        find_snd c_final (L.conj c2') disc [] (List.rev_append seen rest)
    else
        find_fst c_final c1 disc (c12' :: seen) rest

and find_snd c_final c2 disc seen = function
| [] → ((L.conj c_final, L.conj c2) :: disc, List.rev seen)
| (c1', c2') as c12' :: rest →
    if L.equal c2' c2 then begin
        if L.equal c1' c_final then
            (disc, List.rev_append seen rest)
        else
            find_fst c_final (L.conj c1') disc [] (List.rev_append seen rest)
        end else
        find_snd c_final c2 disc (c12' :: seen) rest

let consume = function
| [] → ([], [])
| (c1, c2) :: rest → find_snd (L.conj c1) (L.conj c2) [] [] rest

let contract lines =
    let rec contract' acc disc = function
    | [] → (acc, List.rev disc)
    | rest →
        begin match consume rest with
        | [], rest' → contract' (succ acc) disc rest'
        | disc', rest' → contract' acc (List.rev_append disc' disc) rest'
        end in
    contract' 0 [] lines

```

```

let count lines =
  match contract lines with
  | n, [] → n
  | n, _ → raise Open_line

let to_string lines =
  String.concat ""
  (List.map
   (fun (c1, c2) → "[" ^ L.to_string c1 ^ ", " ^ L.to_string c2 ^ "]")
   lines)

end

```

7.2.2 Color Flows

```

module type Flow =
sig
  type color
  type t = color list × color list
  val rank : t → int
  val of_list : int list → color
  val ghost : unit → color
  val to_lists : t → int list list
  val in_to_lists : t → int list list
  val out_to_lists : t → int list list
  val ghost_flags : t → bool list
  val in_ghost_flags : t → bool list
  val out_ghost_flags : t → bool list
  type power = { num : int; den : int; power : int }
  type factor = power list
  val factor : t → t → factor
  val zero : factor
end

module Flow (* : Flow *) =
struct
  type color =
    | Lines of int × int
    | Ghost

  type t = color list × color list

  let rank cflow =
    2

```

Constructors

```

let ghost () =

```

Ghost

```

let of_list = function
| [c1; c2] → Lines (c1, c2)
| _ → invalid_arg "Color.Flow.of_list: num_lines != 2"

let to_list = function
| Lines (c1, c2) → [c1; c2]
| Ghost → [0; 0]

let to_lists (cfin, cfout) =
(List.map to_list cfin) @ (List.map to_list cfout)

let in_to_lists (cfin, _) =
List.map to_list cfin

let out_to_lists (_, cfout) =
List.map to_list cfout

let ghost_flag = function
| Lines _ → false
| Ghost → true

let ghost_flags (cfin, cfout) =
(List.map ghost_flag cfin) @ (List.map ghost_flag cfout)

let in_ghost_flags (cfin, _) =
List.map ghost_flag cfin

let out_ghost_flags (_, cfout) =
List.map ghost_flag cfout

```

Evaluation

```

type power = { num : int; den : int; power : int }
type factor = power list
let zero = []

let count_ghosts1 colors =
List.fold_left
(fun acc → function Ghost → succ acc | _ → acc)
0 colors

let count_ghosts (fin, fout) =
count_ghosts1 fin + count_ghosts1 fout

type α square =
| Square of α
| Mismatch

let conjugate = function
| Lines (c1, c2) → Lines (-c2, -c1)
| Ghost → Ghost

let cross_in (cin, cout) =

```



```

    cin @ (List.map conjugate cout)

let cross_out (cin, cout) =
  (List.map conjugate cin) @ cout

module C = Cycles (struct
  type t = int
  let conj = (-)
  let equal = (=)
  let to_string = string_of_int
end)

let square f1 f2 =
  let rec square' acc f1' f2' =
    match f1', f2' with
    | [], [] → Square (List.rev acc)
    | -, [] | [], - → Mismatch
    | Ghost :: rest1, Ghost :: rest2 →
      square' acc rest1 rest2
    | Lines (0, 0) :: rest1, Lines (0, 0) :: rest2 →
      square' acc rest1 rest2
    | Lines (0, c1') :: rest1, Lines (0, c2') :: rest2 →
      square' ((c1', c2') :: acc) rest1 rest2
    | Lines (c1, 0) :: rest1, Lines (c2, 0) :: rest2 →
      square' ((c1, c2) :: acc) rest1 rest2
    | Lines (0, -) :: -, - | -, Lines (0, -) :: -
    | Lines (-, 0) :: -, - | -, Lines (-, 0) :: - → Mismatch
    | Lines (-, -) :: -, Ghost :: - | Ghost :: -, Lines (-, -) :: - →
Mismatch
    | Lines (c1, c1') :: rest1, Lines (c2, c2') :: rest2 →
      square' ((c1', c2') :: (c1, c2) :: acc) rest1 rest2 in
  square' [] (cross_out f1) (cross_out f2)

```

In addition to counting closed color loops, we also need to count closed gluon loops. Fortunately, we can use the same algorithm on a different data type, provided it doesn't require all lines to be closed.

```

module C2 = Cycles (struct
  type t = int × int
  let conj (c1, c2) = (- c2, - c1)
  let equal (c1, c2) (c1', c2') = c1 = c1' ∧ c2 = c2'
  let to_string (c1, c2) = "(" ^ string_of_int c1 ^ ", " ^ string_of_int c2 ^ ")"
end)

let square2 f1 f2 =
  let rec square2' acc f1' f2' =
    match f1', f2' with
    | [], [] → Square (List.rev acc)
    | -, [] | [], - → Mismatch
    | Ghost :: rest1, Ghost :: rest2 →
      square2' acc rest1 rest2
    | Lines (0, 0) :: rest1, Lines (0, 0) :: rest2 →
      square2' acc rest1 rest2

```

```

| Lines (0, _) :: rest1, Lines (0, _) :: rest2
| Lines (_, 0) :: rest1, Lines (_, 0) :: rest2 →
  square2' acc rest1 rest2
| Lines (0, _) :: -, - | -, Lines (0, _) :: -
| Lines (_, 0) :: -, - | -, Lines (_, 0) :: - → Mismatch
| Lines (_, -) :: -, Ghost :: - | Ghost :: -, Lines (_, -) :: - →
Mismatch
| Lines (c1, c1') :: rest1, Lines (c2, c2') :: rest2 →
  square2' (((c1, c1'), (c2, c2'))) :: acc rest1 rest2 in
square2' [] (cross_out f1) (cross_out f2)

```

int_power : $n\ p \rightarrow n^p$ for integers is missing from *Pervasives*!

```

let int_power n p =
  let rec int_power' acc i =
    if i < 0 then
      invalid_arg "int_power"
    else if i = 0 then
      acc
    else
      int_power' (n × acc) (pred i) in
  int_power' 1 p

```

Instead of implementing a full fledged algebraic evaluator, let's simply expand the binomial by hand:

$$\left(\frac{N_C^2 - 2}{N_C^2}\right)^n = \sum_{i=0}^n \binom{n}{i} (-2)^i N_C^{-2i} \quad (7.2)$$

NB: Any result of *square* other than *Mismatch* guarantees *count_ghosts f1* = *count_ghosts f2*.

```

let factor f1 f2 =
  match square f1 f2, square2 f1 f2 with
  | Mismatch, - | -, Mismatch → []
  | Square f12, Square f12' →
    let num_cycles = C.count f12
    and num_cycles2, disc = C2.contract f12'
    and num_ghosts = count_ghosts f1 in
    List.map
      (fun i →
        let parity = if num_ghosts mod 2 = 0 then 1 else -1
        and power = num_cycles - num_ghosts in
        let coeff = int_power (-2) i × Combinatorics.binomial num_cycles2 i
        and power2 = - 2 × i in
        { num = parity × coeff;
          den = 1;
          power = power + power2 })
      (ThoList.range 0 num_cycles2)
end

```

later:

module *General_Flow* =

```
struct
  type color =
    | Lines of int list
    | Ghost of int
  type t = color list × color list
  let rank_default = 2 (* Standard model *)
  let rank cflow =
    try
      begin match List.hd cflow with
        | Lines lines → List.length lines
        | Ghost n_lines → n_lines
      end
    with
      | _ → rank_default
end
```

—8—

FUSIONS

8.1 *Interface of Fusion*

module type *T* =

sig

val *options* : *Options.t*

Wavefunctions are an abstract data type, containing a momentum *p* and additional quantum numbers, collected in *flavor*.

type *wf*

Obviously, *flavor* is not restricted to the physical notion of flavor, but can carry spin, color, etc.

type *flavor*

type *flavor_sans_color*

val *flavor* : *wf* → *flavor*

val *flavor_sans_color* : *wf* → *flavor_sans_color*

Momenta are represented by an abstract datatype (defined in *Momentum*) that is optimized for performance. They can be accessed either abstractly or as lists of indices of the external momenta. These indices are assigned sequentially by *amplitude* below.

type *p*

val *momentum* : *wf* → *p*

val *momentum_list* : *wf* → *int list*

At tree level, the wave functions are uniquely specified by *flavor* and momentum. If loops are included, we need to distinguish among orders. Also, if we build a result from an incomplete sum of diagrams, we need to add a distinguishing mark. At the moment, we assume that a *string* that can be attached to the symbol suffices.

val *wf_tag* : *wf* → *string option*

Coupling constants

type *constant*

and right hand sides of assignments. The latter are formed from a sign from Fermi statistics, a coupling (constant and Lorentz structure) and wave functions.

```

type coupling
type rhs
type  $\alpha$  children
val sign : rhs  $\rightarrow$  int
val coupling : rhs  $\rightarrow$  constant Coupling.t
val coupling_tag : rhs  $\rightarrow$  string option

```

In renormalized perturbation theory, couplings come in different orders of the loop expansion. Be prepared: `val order : rhs \rightarrow int`



This is here only for the benefit of *Target* and shall become `val children : rhs \rightarrow wf children` later ...

```

val children : rhs  $\rightarrow$  wf list

```

Fusions come in two types: fusions of wave functions to off-shell wave functions:

$$\phi(p+q) = \phi(p)\phi(q)$$

```

type fusion
val lhs : fusion  $\rightarrow$  wf
val rhs : fusion  $\rightarrow$  rhs list

```

and products at the keystones:

$$\phi(-p-q) \cdot \phi(p)\phi(q)$$

```

type braket
val bra : braket  $\rightarrow$  wf
val ket : braket  $\rightarrow$  rhs list

```

amplitude goldstones incoming outgoing calculates the amplitude for scattering of *incoming* to *outgoing*. If *goldstones* is true, also non-propagating off-shell Goldstone amplitudes are included to allow the checking of Slavnov-Taylor identities.

```

type amplitude
type selectors
val amplitudes : bool  $\rightarrow$  selectors  $\rightarrow$ 
  flavor_sans_color list  $\rightarrow$  flavor_sans_color list  $\rightarrow$  amplitude list
val dependencies : amplitude  $\rightarrow$  wf  $\rightarrow$  (wf, coupling) Tree2.t

```

We should be precise regarding the semantics of the following functions, since modules implementating *Target* must not make any mistakes interpreting the return values. Instead of calculating the amplitude

$$\langle f_3, p_3, f_4, p_4, \dots | T | f_1, p_1, f_2, p_2 \rangle \quad (8.1a)$$


directly, O'Mega calculates the—equivalent, but more symmetrical—crossed amplitude

$$\langle \bar{f}_1, -p_1, \bar{f}_2, -p_2, f_3, p_3, f_4, p_4, \dots | T | 0 \rangle \quad (8.1b)$$

Internally, all flavors are represented by their charge conjugates

$$A(f_1, -p_1, f_2, -p_2, \bar{f}_3, p_3, \bar{f}_4, p_4, \dots) \quad (8.1c)$$

The correspondence of vertex and term in the lagrangian



$$A : \bar{\psi} A \psi \quad (8.2)$$

suggests to denote the *outgoing* particle by the flavor of the *antiparticle* and the *outgoing antiparticle* by the flavor of the particle, since this choice allows to represent the vertex by a triple

$$\bar{\psi} A \psi : (e^+, A, e^-) \quad (8.3)$$

which is more intuitive than the alternative (e^-, A, e^+) . Also, when thinking in terms of building wavefunctions from the outside in, the outgoing *antiparticle* is represented by a *particle* propagator and vice versa¹. *incoming* and *outgoing* are the physical flavors as in (8.1a)

```
val incoming : amplitude → flavor list
val outgoing : amplitude → flavor list
```

externals are flavors and momenta as in (8.1c)

```
val externals : amplitude → wf list
val variables : amplitude → wf list
val fusions : amplitude → fusion list
val brackets : amplitude → bracket list
val on_shell : amplitude → (wf → bool)
val is_gauss : amplitude → (wf → bool)
val constraints : amplitude → string option
val symmetry : amplitude → int
val allowed : amplitude → bool
```

Performance Hacks

```
val initialize_cache : string → unit
val set_cache_name : string → unit
```

¹Even if this choice will appear slightly counter-intuitive on the *Target* side, one must keep in mind that much more people are expected to prepare *Models*.

Diagnostics

```

val check_charges : unit → flavor_sans_color list list
val count_fusions : amplitude → int
val count_propagators : amplitude → int
val count_diagrams : amplitude → int

val forest : wf → amplitude → ((wf × coupling_option, wf) Tree.t) list
val poles : amplitude → wf list list
val s_channel : amplitude → wf list

val tower_to_dot : out_channel → amplitude → unit
val amplitude_to_dot : out_channel → amplitude → unit

val rcs_list : RCS.t list
end

```

There is more than one way to make fusions.

```

module type Maker =
  functor (P : Momentum.T) → functor (M : Model.T) →
    T with type p = P.t
    and type flavor = Colorize.It(M).flavor
    and type flavor_sans_color = M.flavor
    and type constant = M.constant
    and type selectors = Cascade.Make(M)(P).selectors

```

Straightforward Dirac fermions vs. slightly more complicated Majorana fermions:

```

module Binary : Maker
module Binary_Majorana : Maker

module Mixed23 : Maker
module Mixed23_Majorana : Maker

module Nary : functor (B : Tuple.Bound) → Maker
module Nary_Majorana : functor (B : Tuple.Bound) → Maker

```

We can also proceed á la [2]. Empirically, this will use slightly ($O(10\%)$) fewer fusions than the symmetric factorization. Our implementation uses significantly ($O(50\%)$) fewer fusions than reported by [2]. Our pruning of the DAG might be responsible for this.

```

module Helac : functor (B : Tuple.Bound) → Maker
module Helac_Majorana : functor (B : Tuple.Bound) → Maker

```

8.1.1 Multiple Amplitudes

```

module type Multi =
  sig
    exception Mismatch
    val options : Options.t

    type flavor

```

```

type process = flavor list × flavor list
type amplitude
type fusion
type wf
type selectors
type amplitudes

```

Construct all possible color flow amplitudes for a given process.

```

val amplitudes : bool → int option → selectors → process list →
amplitudes
val empty : amplitudes

```

Precompute the vertex table cache.

```

val initialize_cache : string → unit
val set_cache_name : string → unit

```

The list of all combinations of incoming and outgoing particles with a non-vanishing scattering amplitude.

```

val flavors : amplitudes → process list

```

The list of all combinations of incoming and outgoing particles that don't lead to any color flow with non vanishing scattering amplitude.

```

val vanishing_flavors : amplitudes → process list

```

The list of all color flows with a nonvanishing scattering amplitude.

```

val color_flows : amplitudes → Color.Flow.t list

```

The list of all valid helicity combinations.

```

val helicities : amplitudes → (int list × int list) list

```

The list of all amplitudes.

```

val processes : amplitudes → amplitude list

```

$(process_table\ a).(f).(c)$ returns the amplitude for the f th allowed flavor combination and the c th allowed color flow as an *amplitude option*.

```

val process_table : amplitudes → amplitude option array array

```

The list of all non redundant fusions together with the amplitudes they came from.

```

val fusions : amplitudes → (fusion × amplitude) list

```

If there's more than external flavor state, the wavefunctions are *not* uniquely specified by *flavor* and *Momentum.t*. This function can be used to determine how many variables must be allocated.

```

val multiplicity : amplitudes → wf → int

```

This function can be used to disambiguate wavefunctions with the same combination of *flavor* and *Momentum.t*.

```

val dictionary : amplitudes → amplitude → wf → int

```

$(color_factors\ a).(c1).(c2)$ power of N_C for the given product of color flows.

```

    val color_factors : amplitudes → Color.Flow.factor array array
    A description of optional diagram selectors.
    val constraints : amplitudes → string option
end

module type Multi_Maker = functor (Fusion_Maker : Maker) →
  functor (P : Momentum.T) →
    functor (M : Model.T) →
      Multi with type flavor = M.flavor
      and type amplitude = Fusion_Maker(P)(M).amplitude
      and type fusion = Fusion_Maker(P)(M).fusion
      and type wf = Fusion_Maker(P)(M).wf
      and type selectors = Fusion_Maker(P)(M).selectors
module Multi : Multi_Maker

```

8.1.2 Tags

It appears that there are useful applications for tagging couplings and wave functions, e. g. skeleton expansion and diagram selections. We can abstract this in a *Tags* signature:

```

module type Tags =
  sig
    type wf
    type coupling
    type  $\alpha$  children
    val null_wf : wf
    val null_coupling : coupling
    val fuse : coupling → wf children → wf
    val wf_to_string : wf → string option
    val coupling_to_string : coupling → string option
    val options : Options.t
  end

module type Tagger =
  functor (PT : Tuple.Poly) → Tags with type  $\alpha$  children =  $\alpha$  PT.t

module type Tagged_Maker =
  functor (Tagger : Tagger) →
    functor (P : Momentum.T) → functor (M : Model.T) →
      T with type p = P.t
      and type flavor = Colorize.It(M).flavor
      and type flavor_sans_color = M.flavor
      and type constant = M.constant

module Tagged_Binary : Tagged_Maker

```

8.2 Implementation of *Fusion*

```

let rcs_file = RCS.parse "Fusion" ["General_Fusions"]
  { RCS.revision = "$Revision: 4707$";
    RCS.date = "$Date: 2013-10-01 07:57:19 -0700 (Tue, 01 Oct 2013)$";
    RCS.author = "$Author: ohl$";
    RCS.source
      = "$URL: svn+ssh://jr_reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg";

module type T =
sig
  val options : Options.t
  type wf
  type flavor
  type flavor_sans_color
  val flavor : wf → flavor
  val flavor_sans_color : wf → flavor_sans_color
  type p
  val momentum : wf → p
  val momentum_list : wf → int list
  val wf_tag : wf → string option
  type constant
  type coupling
  type rhs
  type  $\alpha$  children
  val sign : rhs → int
  val coupling : rhs → constant Coupling.t
  val coupling_tag : rhs → string option
  val children : rhs → wf list
  type fusion
  val lhs : fusion → wf
  val rhs : fusion → rhs list
  type bracket
  val bra : bracket → wf
  val ket : bracket → rhs list
  type amplitude
  type selectors
  val amplitudes : bool → selectors →
    flavor_sans_color list → flavor_sans_color list → amplitude list
  val dependencies : amplitude → wf → (wf, coupling) Tree2.t
  val incoming : amplitude → flavor list
  val outgoing : amplitude → flavor list
  val externals : amplitude → wf list
  val variables : amplitude → wf list
  val fusions : amplitude → fusion list
  val brackets : amplitude → bracket list
  val on_shell : amplitude → (wf → bool)
  val is_gauss : amplitude → (wf → bool)
  val constraints : amplitude → string option
  val symmetry : amplitude → int

```

```

val allowed : amplitude → bool
val initialize_cache : string → unit
val set_cache_name : string → unit
val check_charges : unit → flavor_sans_color list list
val count_fusions : amplitude → int
val count_propagators : amplitude → int
val count_diagrams : amplitude → int
val forest : wf → amplitude → ((wf × coupling option, wf) Tree.t) list
val poles : amplitude → wf list list
val s_channel : amplitude → wf list
val tower_to_dot : out_channel → amplitude → unit
val amplitude_to_dot : out_channel → amplitude → unit
val rcs_list : RCS.t list
end

module type Maker =
  functor (P : Momentum.T) → functor (M : Model.T) →
    T with type p = P.t
    and type flavor = Colorize.It(M).flavor
    and type flavor_sans_color = M.flavor
    and type constant = M.constant
    and type selectors = Cascade.Make(M)(P).selectors

```

8.2.1 Fermi Statistics

```

module type Stat =
  sig
    type flavor
    type stat
    exception Impossible
    val stat : flavor → int → stat
    val stat_fuse : stat → stat → flavor → stat
    val stat_sign : stat → int
    val rcs : RCS.t
  end

module type Stat_Maker = functor (M : Model.T) →
  Stat with type flavor = M.flavor

```

8.2.2 Dirac Fermions

```

module Stat_Dirac (M : Model.T) : (Stat with type flavor = M.flavor) =
  struct
    let rcs = RCS.rename rcs_file "Fusion.Stat_Dirac()"
      [ "Fermi_statistics_for_Dirac_fermions" ]
    type flavor = M.flavor
  end

```




Figure 8.1: Relative sign from Fermi statistics.

$$\gamma_\mu \psi(1) G^{\mu\nu} \bar{\psi}(2) \gamma_\nu \psi(3) - \gamma_\mu \psi(3) G^{\mu\nu} \bar{\psi}(2) \gamma_\nu \psi(1) \quad (8.4)$$

```

type stat =
| Fermion of int × (int option × int option) list
| AntiFermion of int × (int option × int option) list
| Boson of (int option × int option) list

let stat f p =
  let s = M.fermion f in
  if s = 0 then
    Boson []
  else if s < 0 then
    AntiFermion (p, [])
  else (* if s > 0 then *)
    Fermion (p, [])

exception Impossible

let stat_fuse s1 s2 f =
  match s1, s2 with
  | Boson l1, Boson l2 → Boson (l1 @ l2)
  | Boson l1, Fermion (p, l2) → Fermion (p, l1 @ l2)
  | Boson l1, AntiFermion (p, l2) → AntiFermion (p, l1 @ l2)
  | Fermion (p, l1), Boson l2 → Fermion (p, l1 @ l2)
  | AntiFermion (p, l1), Boson l2 → AntiFermion (p, l1 @ l2)
  | AntiFermion (pbar, l1), Fermion (p, l2) →
    Boson ((Some pbar, Some p) :: l1 @ l2)
  | Fermion (p, l1), AntiFermion (pbar, l2) →
    Boson ((Some pbar, Some p) :: l1 @ l2)
  | Fermion _, Fermion _ | AntiFermion _, AntiFermion _ →
    raise Impossible

```

$$\epsilon(\{(0, 1), (2, 3)\}) = -\epsilon(\{(0, 3), (2, 1)\}) \quad (8.5)$$

```

let permutation_lines =
  let fout, fin = List.split lines in
  let eps_in, _ = Combinatorics.sort_signed compare fin
  and eps_out, _ = Combinatorics.sort_signed compare fout in
  (eps_in × eps_out)

```



This comparing of permutations of fermion lines is a bit tedious and takes a macroscopic fraction of time. However, it's less than 20 %, so we don't focus on improving on it yet.

```
let stat_sign = function
  | Boson lines → permutation lines
  | Fermion (p, lines) → permutation ((None, Some p) :: lines)
  | AntiFermion (pbar, lines) → permutation ((Some pbar, None) :: lines)
end
```

8.2.3 Tags

```
module type Tags =
sig
  type wf
  type coupling
  type  $\alpha$  children
  val null_wf : wf
  val null_coupling : coupling
  val fuse : coupling → wf children → wf
  val wf_to_string : wf → string option
  val coupling_to_string : coupling → string option
  val options : Options.t
end

module type Tagger =
  functor (PT : Tuple.Poly) → Tags with type  $\alpha$  children =  $\alpha$  PT.t

module type Tagged_Maker =
  functor (Tagger : Tagger) →
    functor (P : Momentum.T) → functor (M : Model.T) →
      T with type p = P.t
      and type flavor = Colorize.It(M).flavor
      and type flavor_sans_color = M.flavor
      and type constant = M.constant
```

No tags is one option for good tags ...

```
module No_Tags (PT : Tuple.Poly) =
struct
  type wf = unit
  type coupling = unit
  type  $\alpha$  children =  $\alpha$  PT.t
  let null_wf = ()
  let null_coupling = ()
  let fuse () _ = ()
  let wf_to_string () = None
  let coupling_to_string () = None
  let options = Options.empty
```

end



Here's a simple additive tag that can grow into something useful for loop calculations.

```
module Loop_Tags (PT : Tuple.Poly) =
  struct
    type wf = int
    type coupling = int
    type  $\alpha$  children =  $\alpha$  PT.t
    let null_wf = 0
    let null_coupling = 0
    let fuse c wfs = PT.fold_left (+) c wfs
    let wf_to_string n = Some (string_of_int n)
    let coupling_to_string n = Some (string_of_int n)
    let options = Options.empty
  end
```

Counting QCD and EW orders.

```
module Order_Tags (PT : Tuple.Poly) =
  struct

    let max_qcd_order = ref None
    let max_ew_order = ref None

    exception Negative_Coupling_Order of int

    let set_max_order order_ref n =
      if n  $\geq$  0 then
        order_ref := Some n
      else
        raise (Negative_Coupling_Order n)

    let options = Options.create
      [ "QCD-order", Arg.Int (set_max_order max_qcd_order),
        "set_QCD_order_n [ $\geq$ 0, default none]";
        "EW-order", Arg.Int (set_max_order max_ew_order),
        "set_QCD_order_n [ $\geq$ 0, default none]" ]

    type orders =
      { qcd : int;
        ew : int }

    let null = { qcd = 0; ew = 0 }

    let add o1 o2 =
      { qcd = o1.qcd + o2.qcd;
        ew = o1.ew + o2.ew }

    let to_string o =
      Printf.sprintf "QCD=%d, EW=%d" o.qcd o.ew

    let to_string o =
```

```

    Printf.sprintf "%d-%d" o.qcd o.ew
let qcd_order_in_bounds orders =
  match !max_qcd_order with
  | None → true
  | Some n → orders.qcd ≤ n
let ew_order_in_bounds orders =
  match !max_ew_order with
  | None → true
  | Some n → orders.ew ≤ n
let orders_in_bounds orders =
  qcd_order_in_bounds orders ∧ ew_order_in_bounds orders
type wf = orders
type coupling = orders
type α children = α PT.t
let null_wf = null
let null_coupling = null
let fuse c wfs = PT.fold_left add c wfs
let wf_to_string o = Some (to_string o)
let coupling_to_string o = Some (to_string o)
end

```

8.2.4 Tagged, the *Fusion.Make* Functor

```

module Tagged (Tagger : Tagger) (PT : Tuple.Poly)
  (Stat : Stat_Maker) (T : Topology.T with type α children = α PT.t)
  (P : Momentum.T) (M : Model.T) =
struct
  let rcs = RCS.rename rcs_file "Fusion.Make()"
    [ "Fusions_for_arbitrary_topologies" ]
  type cache_mode = Cache_Use | Cache_Ignore | Cache_Overwrite
  let cache_option = ref Cache_Use
  open Coupling
  module S = Stat(M)
  type stat = S.stat
  let stat = S.stat
  let stat_sign = S.stat_sign

```



This will do *something* for 4-, 6-, ... fermion vertices, but not necessarily the right thing ...

```

let stat_fuse s f =
  PT.fold_right_internal (fun s' acc → S.stat_fuse s' acc f) s
type constant = M.constant

```

Wave Functions

The code below is not yet functional. Too often, we assign to *Tags.null_wf* instead of calling *Tags.fuse*.

We will need two types of amplitudes: with color and without color. Since we can build them using the same types with only *flavor* replaced, it pays to use a functor to set up the scaffolding.

```
module Tags = Tagger(PT)

let options =
  Options.extend Tags.options
  [ "ignore-cache", Arg.Unit (fun () → cache_option := Cache_Ignore),
    "ignore_cached_model_tables";
    "overwrite-cache", Arg.Unit (fun () → cache_option := Cache_Overwrite),
    "overwrite_cached_model_tables" ]
```

In the future, we might want to have *Coupling* among the functor arguments. However, for the moment, *Coupling* is assumed to be comprehensive.

```
module type Tagged_Coupling =
sig
  type sign = int
  type t =
    { sign : sign;
      coupling : constant Coupling.t;
      coupling_tag : Tags.coupling }
  val sign : t → sign
  val coupling : t → constant Coupling.t
  val coupling_tag : t → string option
end

module Tagged_Coupling : Tagged_Coupling =
struct
  type sign = int
  type t =
    { sign : sign;
      coupling : constant Coupling.t;
      coupling_tag : Tags.coupling }
  let sign c = c.sign
  let coupling c = c.coupling
  let coupling_tag_raw c = c.coupling_tag
  let coupling_tag rhs = Tags.coupling_to_string (coupling_tag_raw rhs)
end
```

Amplitudes: Monochrome and Colored

```
module type Amplitude =
sig
```



```

module Tags : Tags

type flavor
type p

type wf =
  { flavor : flavor;
    momentum : p;
    wf_tag : Tags.wf }

val flavor : wf → flavor
val conjugate : wf → wf
val momentum : wf → p
val momentum_list : wf → int list
val wf_tag : wf → string option
val wf_tag_raw : wf → Tags.wf
val order_wf : wf → wf → int
val external_wfs : int → (flavor × int) list → wf list

type α children
type coupling = Tagged_Coupling.t
type rhs = coupling × wf children
val sign : rhs → int
val coupling : rhs → constant Coupling.t
val coupling_tag : rhs → string option
val children : rhs → wf list

type fusion = wf × rhs list
val lhs : fusion → wf
val rhs : fusion → rhs list

type braket = wf × rhs list
val bra : braket → wf
val ket : braket → rhs list

module D :
  DAG.T with type node = wf and type edge = coupling and type children = wf children

val wavefunctions : braket list → wf list

type amplitude =
  { fusions : fusion list;
    brackets : braket list;
    on_shell : (wf → bool);
    is_gauss : (wf → bool);
    constraints : string option;
    incoming : flavor list;
    outgoing : flavor list;
    externals : wf list;
    symmetry : int;
    dependencies : (wf → (wf, coupling) Tree2.t);
    fusion_tower : D.t;
    fusion_dag : D.t }

val incoming : amplitude → flavor list

```

```

val outgoing : amplitude → flavor list
val externals : amplitude → wf list
val variables : amplitude → wf list
val fusions : amplitude → fusion list
val brackets : amplitude → bracket list
val on_shell : amplitude → (wf → bool)
val is_gauss : amplitude → (wf → bool)
val constraints : amplitude → string option
val symmetry : amplitude → int
val dependencies : amplitude → wf → (wf, coupling) Tree2.t
val fusion_dag : amplitude → D.t

end

module Amplitude (PT : Tuple.Poly) (P : Momentum.T) (M : Model.T) :
  Amplitude
  with type p = P.t
  and type flavor = M.flavor
  and type  $\alpha$  children =  $\alpha$  PT.t
  and module Tags = Tags =
  struct

    type flavor = M.flavor
    type p = P.t

    module Tags = Tags

    type wf =
      { flavor : flavor;
        momentum : p;
        wf_tag : Tags.wf }

    let flavor wf = wf.flavor
    let conjugate wf = { wf with flavor = M.conjugate wf.flavor }
    let momentum wf = wf.momentum
    let momentum_list wf = P.to_ints wf.momentum
    let wf_tag wf = Tags.wf_to_string wf.wf_tag
    let wf_tag_raw wf = wf.wf_tag

    let external_wfs rank particles =
      List.map
        (fun (f, p) →
          { flavor = f;
            momentum = P.singleton rank p;
            wf_tag = Tags.null_wf })
        particles

```

Order wavefunctions so that the external come first, then the pairs, etc. Also put possible Goldstone bosons *before* their gauge bosons.

```

let lorentz_ordering f =
  match M.lorentz f with
  | Coupling.Scalar → 0
  | Coupling.Spinor → 1
  | Coupling.ConjSpinor → 2

```

```

| Coupling.Majorana → 3
| Coupling.Vector → 4
| Coupling.Massive_Vector → 5
| Coupling.Tensor_2 → 6
| Coupling.Tensor_1 → 7
| Coupling.Vectorspinor → 8
| Coupling.BRS Coupling.Scalar → 9
| Coupling.BRS Coupling.Spinor → 10
| Coupling.BRS Coupling.ConjSpinor → 11
| Coupling.BRS Coupling.Majorana → 12
| Coupling.BRS Coupling.Vector → 13
| Coupling.BRS Coupling.Massive_Vector → 14
| Coupling.BRS Coupling.Tensor_2 → 15
| Coupling.BRS Coupling.Tensor_1 → 16
| Coupling.BRS Coupling.Vectorspinor → 17
| Coupling.BRS _ → invalid_arg "Fusion.lorentz_ordering:_not_needed"
| Coupling.Maj_Ghost → 18

```

```

let order_flavor f1 f2 =
  let c = compare (lorentz_ordering f1) (lorentz_ordering f2) in
  if c ≠ 0 then
    c
  else
    compare f1 f2

```

Note that *Momentum().compare* guarantees that wavefunctions will be ordered according to *increasing Momentum().rank* of their momenta.

```

let order_wf wf1 wf2 =
  let c = P.compare wf1.momentum wf2.momentum in
  if c ≠ 0 then
    c
  else
    let c = order_flavor wf1.flavor wf2.flavor in
    if c ≠ 0 then
      c
    else
      compare wf1.wf_tag wf2.wf_tag

```

This *must* be a pair matching the *edge × node children* pairs of *DAG.Forest!*

```

type coupling = Tagged_Coupling.t
type α children = α PT.t
type rhs = coupling × wf children
let sign (c, _) = Tagged_Coupling.sign c
let coupling (c, _) = Tagged_Coupling.coupling c
let coupling_tag (c, _) = Tagged_Coupling.coupling_tag c
let children (_, wfs) = PT.to_list wfs

type fusion = wf × rhs list
let lhs (l, _) = l
let rhs (_, r) = r

```

```

type braket = wf × rhs list
let bra (b, _) = b
let ket (_, k) = k

module D = DAG.Make
  (DAG.Forest(PT))
  (struct type t = wf let compare = order_wf end)
  (struct type t = coupling let compare = compare end))

module WFSet =
  Set.Make (struct type t = wf let compare = order_wf end)

let wavefunctions brackets =
  WFSet.elements (List.fold_left (fun set (wf1, wf23) →
    WFSet.add wf1 (List.fold_left (fun set' (_, wfs) →
      PT.fold_right WFSet.add wfs set') set wf23)) WFSet.empty brackets)

type amplitude =
  { fusions : fusion list;
    brackets : braket list;
    on_shell : (wf → bool);
    is_gauss : (wf → bool);
    constraints : string option;
    incoming : flavor list;
    outgoing : flavor list;
    externals : wf list;
    symmetry : int;
    dependencies : (wf → (wf, coupling) Tree2.t);
    fusion_tower : D.t;
    fusion_dag : D.t }

let incoming a = a.incoming
let outgoing a = a.outgoing
let externals a = a.externals
let fusions a = a.fusions
let brackets a = a.brackets
let symmetry a = a.symmetry
let on_shell a = a.on_shell
let is_gauss a = a.is_gauss
let constraints a = a.constraints
let variables a = List.map lhs a.fusions
let dependencies a = a.dependencies
let fusion_dag a = a.fusion_dag

end

module A = Amplitude(PT)(P)(M)

```

Operator insertions can be fused only if they are external.

```

let is_source wf =
  match M.propagator wf.A.flavor with
  | Only_Insertion → P.rank wf.A.momentum = 1
  | _ → true

```

is_goldstone_of *g v* is `true` if and only if *g* is the Goldstone boson corresponding to the gauge particle *v*.

```
let is_goldstone_of g v =
  match M.goldstone v with
  | None → false
  | Some (g', _) → g = g'
```



In the end, *PT.to_list* should become redundant!

```
let fuse_rhs rhs = M.fuse (PT.to_list rhs)
```

Vertices

Compute the set of all vertices in the model from the allowed fusions and the set of all flavors:



One could think of using *M.vertices* instead of *M.fuse2*, *M.fuse3* and *M.fuse* ...

```
module VSet = Map.Make(struct type t = A.flavor let compare = compare end)

let add_vertices f rhs m =
  VSet.add f (try rhs :: VSet.find f m with Not_found → [rhs]) m

let collect_vertices rhs =
  List.fold_right (fun (f1, c) → add_vertices (M.conjugate f1) (c, rhs))
    (fuse_rhs rhs)
```

The set of all vertices with common left fields factored.

I used to think that constant initializers are a good idea to allow compile time optimizations. The down side turned out to be that the constant initializers will be evaluated *every time* the functor is applied. *Relying on the fact that the functor will be called only once is not a good idea!*

```
type vertices = (A.flavor × (constant Coupling.t × A.flavor PT.t) list) list

let vertices_nocache max_degree flavors : vertices =
  VSet.fold (fun f rhs v → (f, rhs) :: v)
    (PT.power_fold collect_vertices flavors VSet.empty) []
```

Performance hack:

```
type vertex_table =
  ((A.flavor × A.flavor × A.flavor) × constant Coupling.vertex3 ×
  constant) list
  × ((A.flavor × A.flavor × A.flavor × A.flavor)
    × constant Coupling.vertex4 × constant) list
  × (A.flavor list × constant Coupling.vertexn × constant) list

module VCache =
  Cache.Make (struct type t = vertex_table end) (struct type t = RCS.t ×
  vertices end)
```

```
let vertices_cache = ref None
let hash = VCache.hash (M.vertices ())
```



Can we do better than the executable name provided by *Config.cache_prefix*???
We need a better way to avoid collisions among the caches for different models in the same program.

```
let cache_name =
  ref (Config.cache_prefix ^ "." ^ Config.cache_suffix)

let set_cache_name name =
  cache_name := name

let initialize_cache dir =
  Printf.eprintf
    "%>>>Initializing vertex table for model %s. This may take some time...\n"
    (RCS.name M.rcs);
  flush stderr;
  VCache.write_dir hash dir !cache_name
    (M.rcs, vertices_nocache (M.max_degree ()) (M.flavors()));
  Printf.eprintf "done.<<<\n"

let vertices max_degree flavors : vertices =
  match !vertices_cache with
  | None →
    begin match !cache_option with
    | Cache_Use →
      begin match VCache.maybe_read hash !cache_name with
      | VCache.Hit (rcs, result) →
        result
      | VCache.Miss →
        Printf.eprintf
          "%>>>Initializing vertex table for model %s. This may take some time...\n"
          (RCS.name M.rcs);
        flush stderr;
        let result = vertices_nocache max_degree flavors in
          VCache.write hash !cache_name (M.rcs, result);
          vertices_cache := Some result;
          Printf.eprintf "done.<<<\n";
          flush stderr;
          result
      | VCache.Stale file →
        Printf.eprintf
          "%>>>Re-initializing stale vertex table for model %s in file %s.\n"
          (RCS.name M.rcs) file;
        Printf.eprintf "This may take some time...\n";
        flush stderr;
        let result = vertices_nocache max_degree flavors in
          VCache.write hash !cache_name (M.rcs, result);
          vertices_cache := Some result;
```

```

        Printf.eprintf "done.<<<\n";
        flush stderr;
        result
    end
| Cache_Overwrite →
    Printf.eprintf
        ">>>Overwriting vertex table for model %s. This may take some time..."
        (RCS.name M.rcs);
    flush stderr;
    let result = vertices_nocache max_degree flavors in
        VCache.write hash !cache_name (M.rcs, result);
        vertices_cache := Some result;
        Printf.eprintf "done.<<<\n";
        flush stderr;
        result
| Cache_Ignore →
    Printf.eprintf
        ">>>Ignoring vertex table for model %s. This may take some time..."
        (RCS.name M.rcs);
    flush stderr;
    let result = vertices_nocache max_degree flavors in
        vertices_cache := Some result;
        Printf.eprintf "done.<<<\n";
        flush stderr;
        result
    end
| Some result → result

```

Partitions

Vertices that are not crossing invariant need special treatment so that they're only generated for the correct combinations of momenta.

NB: the *crossing* checks here are a bit redundant, because *CM.fuse* below will bring the killed vertices back to life and will have to filter once more. Nevertheless, we keep them here, for the unlikely case that anybody ever wants to use uncolored amplitudes directly.

NB: the analogous problem does not occur for *select_wf*, because this applies to momenta instead of vertices.



This approach worked before the *colorize*, but has become *futile*, because *CM.fuse* will bring the killed vertices back to life. We need to implement the same checks there again!!!



Using *PT.Mismatched_arity* is not really good style ...

Tho's approach doesn't work since he does not catch charge conjugated processes or crossed processes. Another very strange thing is that O'Mega

seems always to run in the $q_2 q_3$ timelike case, but not in the other two. (Property of how the DAG is built?). For the $ZZZZ$ vertex I add the same vertex again, but interchange 1 and 3 in the *crossing* vertex

```

let kmatrix_cuts c momenta =
  match c with
  | V4 (Vector4_K_Matrix_tho (disc, -), fusion, -)
  | V4 (Vector4_K_Matrix_jr (disc, -), fusion, -) →
    let s12, s23, s13 =
      begin match PT.to_list momenta with
      | [q1; q2; q3] → (P.Scattering.timelike (P.add q1 q2),
                          P.Scattering.timelike (P.add q2 q3),
                          P.Scattering.timelike (P.add q1 q3))
      | _ → raise PT.Mismatched_arity
      end in
    begin match disc, s12, s23, s13, fusion with
    | 0, true, false, false, (F341 | F431 | F342 | F432 | F123 | F213 |
                             F124 | F214)
    | 0, false, true, false, (F134 | F143 | F234 | F243 | F312 | F321 |
                              F412 | F421)
    | 0, false, false, true, (F314 | F413 | F324 | F423 | F132 | F231 |
                              F142 | F241) →
      true
      | 1, true, false, false, (F341 | F431 | F342 | F432)
      | 1, false, true, false, (F134 | F143 | F234 | F243)
      | 1, false, false, true, (F314 | F413 | F324 | F423) →
        true
        | 2, true, false, false, (F123 | F213 | F124 | F214)
        | 2, false, true, false, (F312 | F321 | F412 | F421)
        | 2, false, false, true, (F132 | F231 | F142 | F241) →
          true
          | 3, true, false, false, (F143 | F413 | F142 | F412 | F321 | F231 |
                                  F324 | F234)
          | 3, false, true, false, (F314 | F341 | F214 | F241 | F132 | F123 |
                                  F432 | F423)
          | 3, false, false, true, (F134 | F431 | F124 | F421 | F312 | F213 |
                                  F342 | F243) →
            true
            | _ → false
    end
  | _ → true

```

Match a set of flavors to a set of momenta. Form the direct product for the lists of momenta two and three with the list of couplings and flavors two and three.

```

let flavor_keystone select_p dim (f1, f23) (p1, p23) =
  ({ A.flavor = f1;
    A.momentum = P.of_ints dim p1;
    A.wf_tag = A.Tags.null_wf },
   Product.fold2 (fun (c, f) p acc →
    try

```



```

let p' = PT.map (P.of_ints dim) p in
if select_p (P.of_ints dim p1) (PT.to_list p') ∧ kmatrix_cuts c p' then
  (c, PT.map2 (fun f'' p'' → { A.flavor = f'';
                                A.momentum = p'';
                                A.wf_tag = A.Tags.null_wf }) f p') :: acc
else
  acc
with
| PT.Mismatched_arity → acc) f23 p23 [])

```

Produce all possible combinations of vertices (flavor keystones) and momenta by forming the direct product. The semantically equivalent *Product.list2* (*flavor_keystone select_wf n*) *vertices k* with *subsequent* filtering would be a *very bad* idea, because a potentially huge intermediate list is built for large models. E. g. for the MSSM this would lead to non-termination by thrashing for $2 \rightarrow 4$ processes on most PCs.

```

let flavor_keystones filter select_p dim vertices keystones =
  Product.fold2 (fun v k acc →
    filter (flavor_keystone select_p dim v k) acc) vertices keystones []

```

Flatten the nested lists of vertices into a list of attached lines.

```

let flatten_keystones t =
  ThoList.flatmap (fun (p1, p23) →
    p1 :: (ThoList.flatmap (fun (_, rhs) → PT.to_list rhs) p23)) t

```

Subtrees

Fuse a tuple of wavefunctions, keeping track of Fermi statistics. Record only the the sign *relative* to the children. (The type annotation is only for documentation.)

```

let fuse select_wf wfss : (A.wf × stat × A.rhs) list =
  if PT.for_all (fun (wf, _) → is_source wf) wfss then
    try
      let wfs, ss = PT.split wfss in
      let flavors = PT.map A.flavor wfs
      and momenta = PT.map A.momentum wfs
      and wf_tags = PT.map A.wf_tag_raw wfs in
      let p = PT.fold_left_internal P.add momenta in
      List.fold_left
        (fun acc (f, c) →
          if select_wf f p (PT.to_list momenta) ∧ kmatrix_cuts c momenta then
            let s = stat_fuse ss f in
            let flip =
              PT.fold_left (fun acc s' → acc × stat_sign s') (stat_sign s) ss in
            ({ A.flavor = f;
              A.momentum = p;
              A.wf_tag = A.Tags.null_wf }, s,
              ({ Tagged_Coupling.sign = flip;
                Tagged_Coupling.coupling = c;

```

```

      Tagged_Coupling.coupling_tag = A.Tags.null_coupling }, wfs)) :: acc
    else
      acc)
    [] (fuse_rhs flavors)
  with
  | P.Duplicate _ | S.Impossible → []
else
  []

```



Eventually, the pairs of *tower* and *dag* in *fusion_tower'* below could and should be replaced by a graded *DAG*. This will look like, but currently *tower* contains statistics information that is missing from *dag*:

Type `node = flavor * p` is not compatible with type `wf * stat`

This should be easy to fix. However, replacing `type t = wf` with `type t = wf × stat` is *not* a good idea because the variable *stat* makes it impossible to test for the existence of a particular *wf* in a *DAG*.



In summary, it seems that $(wf \times stat) \text{ list array} \times A.D.t$ should be replaced by $(wf \rightarrow stat) \times A.D.t$.

```

module GF =
  struct
    module Nodes =
      struct
        type t = A.wf
        module G = struct type t = int let compare = compare end
        let compare = A.order_wf
        let rank wf = P.rank wf.A.momentum
      end
    module Edges = struct type t = A.coupling let compare = compare end
    module F = DAG.Forest(PT)(Nodes)(Edges)
    type node = Nodes.t
    type edge = F.edge
    type children = F.children
    type t = F.t
    let compare = F.compare
    let for_all = F.for_all
    let fold = F.fold
  end

  module D' = DAG.Graded(GF)

  let tower_of_dag dag =
    let _, max_rank = D'.min_max_rank dag in
    Array.init max_rank (fun n → D'.ranked n dag)

```

The function *fusion_tower'* recursively builds the tower of all fusions from bottom up to a chosen level. The argument *tower* is an array of lists, where the

i -th sublist (counting from 0) represents all off shell wave functions depending on $i + 1$ momenta and their Fermistatistics.

$$\begin{aligned} & \left[\{ \phi_1(p_1), \phi_2(p_2), \phi_3(p_3), \dots \}, \right. \\ & \quad \{ \phi_{12}(p_1 + p_2), \phi'_{12}(p_1 + p_2), \dots, \phi_{13}(p_1 + p_3), \dots, \phi_{23}(p_2 + p_3), \dots \}, \\ & \quad \dots \\ & \quad \left. \{ \phi_{1\dots n}(p_1 + \dots + p_n), \phi'_{1\dots n}(p_1 + \dots + p_n), \dots \} \right] \end{aligned} \quad (8.6)$$

The argument *dag* is a DAG representing all the fusions calculated so far. NB: The outer array in *tower* is always very short, so we could also have accessed a list with *List.nth*. Appending of new members at the end brings no loss of performance. NB: the array is supposed to be immutable. The towers must be sorted so that the combinatorical functions can make consistent selections.



Intuitively, this seems to be correct. However, one could have expected that no element appears twice and that this ordering is not necessary ...

```

let grow select_wf tower =
  let rank = succ (Array.length tower) in
  List.sort Pervasives.compare
    (PT.graded_sym_power_fold rank
     (fun wfs acc → fuse select_wf wfs @ acc) tower [])
let add_offspring dag (wf, -, rhs) =
  A.D.add_offspring wf rhs dag
let filter_offspring fusions =
  List.map (fun (wf, s, -) → (wf, s)) fusions
let rec fusion_tower' n_max select_wf tower dag : (A.wf × stat) list array × A.D.t =
  if Array.length tower ≥ n_max then
    (tower, dag)
  else
    let tower' = grow select_wf tower in
    fusion_tower' n_max select_wf
      (Array.append tower [filter_offspring tower'])
      (List.fold_left add_offspring dag tower')
```

Discard the tower and return a map from wave functions to Fermistatistics together with the DAG.

```

let make_external_dag wfs =
  List.fold_left (fun m (wf, -) → A.D.add_node wf m) A.D.empty wfs
let mixed_fold_left f acc lists =
  Array.fold_left (List.fold_left f) acc lists
module Stat_Map =
  Map.Make (struct type t = A.wf let compare = A.order_wf end)
let fusion_tower height select_wf wfs : (A.wf → stat) × A.D.t =
```

```

let tower, dag =
  fusion_tower' height select_wf [|wfs|] (make_external_dag wfs) in
let stats = mixed_fold_left
  (fun m (wf, s) → Stat_Map.add wf s m) Stat_Map.empty tower in
((fun wf → Stat_Map.find wf stats), dag)

```

Calculate the minimal tower of fusions that suffices for calculating the amplitude.

```

let minimal_fusion_tower n select_wf wfs : (A.wf → stat) × A.D.t =
  fusion_tower (T.max_subtree n) select_wf wfs

```

Calculate the complete tower of fusions. It is much larger than required, but it allows a complete set of gauge checks.

```

let complete_fusion_tower select_wf wfs : (A.wf → stat) × A.D.t =
  fusion_tower (List.length wfs - 1) select_wf wfs

```



There is a natural product of two DAGs using *fuse*. Can this be used in a replacement for *fusion_tower*? The hard part is to avoid double counting, of course. A straight forward solution could do a diagonal sum (in order to reject flipped offspring representing the same fusion) and rely on the uniqueness in *DAG* otherwise. However, this will (probably) slow down the procedure significantly, because most fusions (including Fermi signs!) will be calculated before being rejected by *DAG().add_offspring*.

Add to *dag* all Goldstone bosons defined in *tower* that correspond to gauge bosons in *dag*. This is only required for checking Slavnov-Taylor identities in unitarity gauge. Currently, it is not used, because we use the complete tower for gauge checking.

```

let harvest_goldstones tower dag =
  A.D.fold_nodes (fun wf dag' →
    match M.goldstone wf.A.flavor with
    | Some (g, _) →
      let wf' = { wf with A.flavor = g } in
      if A.D.is_node wf' tower then begin
        A.D.harvest tower wf' dag'
      end else begin
        dag'
      end
    | None → dag' ) dag dag

```

Calculate the sign from Fermi statistics that is not already included in the children.



The use of *PT.of2_kludge* is the largest skeleton on the cupboard of unified fusions. Currently, it is just another name for *PT.of2*, but the existence of the latter requires binary fusions. Of course, this is just a symptom for not fully supporting four fermion vertices ...

```

let stat_keystone stats wf1 wfs =

```

```

let wf1' = stats wf1
and wfs' = PT.map stats wfs in
stat_sign
  (stat_fuse
    (PT.of2_kludge wf1' (stat_fuse wfs' (M.conjugate (A.flavor wf1))))
    (A.flavor wf1))
  × PT.fold_left (fun acc wf → acc × stat_sign wf) (stat_sign wf1') wfs'

```

Test all members of a list of wave functions are defined by the DAG simultaneously:

```

let test_rhs dag (_, wfs) =
  PT.for_all (fun wf → is_source wf ∧ A.D.is_node wf dag) wfs

```

Add the keystone ($wf1, pairs$) to acc only if it is present in dag and calculate the statistical factor depending on *stats en passant*:

```

let filter_keystone stats dag (wf1, pairs) acc =
  if is_source wf1 ∧ A.D.is_node wf1 dag then
    match List.filter (test_rhs dag) pairs with
    | [] → acc
    | pairs' → (wf1, List.map (fun (c, wfs) →
      ({ Tagged_Coupling.sign = stat_keystone stats wf1 wfs;
        Tagged_Coupling.coupling = c;
        Tagged_Coupling.coupling_tag = A.Tags.null_coupling },
        wfs)) pairs') :: acc
  else
    acc

```

Amplitudes

```

module C = Cascade.Make(M)(P)
type selectors = C.selectors

let external_wfs n particles =
  List.map (fun (f, p) →
    ({ A.flavor = f;
      A.momentum = P.singleton n p;
      A.wf_tag = A.Tags.null_wf },
      stat f p)) particles

```

Main Function


```


module WFFMap = Map.Make (struct type t = A.wf let compare = compare end)


map_amplitude_wfs f a applies the function  $f : wf \rightarrow wf$  to all wavefunctions
appearing in the amplitude  $a$ .

let map_amplitude_wfs f a =

```








```

let map_rhs (c, wfs) = (c, PT.map f wfs) in
let map_braket (wf, rhs) = (f wf, List.map map_rhs rhs) in
and map_fusion (lhs, rhs) = (f lhs, List.map map_rhs rhs) in
let map_dag = A.D.map f (fun node rhs → map_rhs rhs) in
let tower = map_dag a.A.fusion_tower
and dag = map_dag a.A.fusion_dag in
let dependencies_map =
  A.D.fold (fun wf _ → WFMap.add wf (A.D.dependencies dag wf)) dag WFMap.empty in
{ A.fusions = List.map map_fusion a.A.fusions;
  A.brakets = List.map map_braket a.A.brakets;
  A.on_shell = a.A.on_shell;
  A.is_gauss = a.A.is_gauss;
  A.constraints = a.A.constraints;
  A.incoming = a.A.incoming;
  A.outgoing = a.A.outgoing;
  A.externals = List.map f a.A.externals;
  A.symmetry = a.A.symmetry;
  A.dependencies = (fun wf → WFMap.find wf dependencies_map);
  A.fusion_tower = tower;
  A.fusion_dag = dag }

```

This is the main function that constructs the amplitude for sets of incoming and outgoing particles and returns the results in conveniently packaged pieces.

let *amplitude goldstones selectors fin fout* =

Set up external lines and match flavors with numbered momenta.

```

let f = fin @ List.map M.conjugate fout in
let nin, nout = List.length fin, List.length fout in
let n = nin + nout in
let externals = List.combine f (ThoList.range 1 n) in
let wfs = external_wfs n externals in
let select_p = C.select_p selectors in
let select_wf =
  match fin with
  | [-] → C.select_wf selectors P.Decay.timelike
  | - → C.select_wf selectors P.Scattering.timelike in

```

Build the full fusion tower (including nodes that are never needed in the amplitude).

```

let stats, tower =
  if goldstones then
    complete_fusion_tower select_wf wfs
  else
    minimal_fusion_tower n select_wf wfs in

```

Find all vertices for which *all* off shell wavefunctions are defined by the tower.

```

let brakets =
  flavor_keystones (filter_keystone stats tower) select_p n
  (vertices (M.max_degree ()) (M.flavors ()))

```

$(T.\text{keystones } (ThoList.\text{range } 1\ n))$ in

Remove the part of the DAG that is never needed in the amplitude.

```
let dag =
  if goldstones then
    tower
  else
    A.D.harvest_list tower (A.wavefunctions brackets) in
```

Remove the leaf nodes of the DAG, corresponding to external lines.

```
let fusions =
  List.filter (function (_, []) → false | _ → true) (A.D.lists dag) in
```

Calculate the symmetry factor for identical particles in the final state.

```
let symmetry =
  Combinatorics.symmetry fout in

let dependencies_map =
  A.D.fold (fun wf _ → WFMap.add wf (A.D.dependencies dag wf)) dag WFMap.empty in
```

Finally: package the results:

```
{ A.fusions = fusions;
  A.brackets = brackets;
  A.on_shell = (fun wf → C.on_shell selectors (A.flavor wf) wf.A.momentum);
  A.is_gauss = (fun wf → C.is_gauss selectors (A.flavor wf) wf.A.momentum);
  A.constraints = C.description selectors;
  A.incoming = fin;
  A.outgoing = fout;
  A.externals = List.map fst wfs;
  A.symmetry = symmetry;
  A.dependencies = (fun wf → WFMap.find wf dependencies_map);
  A.fusion_tower = tower;
  A.fusion_dag = dag }
```

Color

```
module CM = Colorize.It(M)
module CA = Amplitude(PT)(P)(CM)

let colorize_wf flavor wf =
  { CA.flavor = flavor;
    CA.momentum = wf.A.momentum;
    CA.wf_tag = wf.A.wf_tag }

let uncolorize_wf wf =
  { A.flavor = CM.flavor_sans_color wf.CA.flavor;
    A.momentum = wf.CA.momentum;
    A.wf_tag = wf.CA.wf_tag }
```



At the end of the day, I shall want to have some sort of *fibred DAG* as abstract data type, with a projection of colored nodes to their uncolored counterparts.

```

module CWFBundle = Bundle.Make
  (struct
    type elt = CA.wf
    let compare_elt = compare
    type base = A.wf
    let compare_base = compare
    let pi wf =
      { A.flavor = CM.flavor_sans_color wf.CA.flavor;
        A.momentum = wf.CA.momentum;
        A.wf_tag = wf.CA.wf_tag }
  end)

```



For now, we can live with simple aggregation:

```

type fibred_dag = { dag : CA.D.t; bundle : CWFBundle.t }

```

Not yet(?) needed: `module CS = Stat (CM)`

```

let colorize_sterile_nodes dag f wf fibred_dag =
  if A.D.is_sterile wf dag then
    let wf', wf_bundle' = f wf fibred_dag in
    { dag = CA.D.add_node wf' fibred_dag.dag;
      bundle = wf_bundle' }
  else
    fibred_dag

let colorize_nodes f wf rhs fibred_dag =
  let wf_rhs_list', wf_bundle' = f wf rhs fibred_dag in
  let dag' =
    List.fold_right
      (fun (wf', rhs') → CA.D.add_offspring wf' rhs')
      wf_rhs_list' fibred_dag.dag in
  { dag = dag';
    bundle = wf_bundle' }

```

O'Caml (correctly) infers the type `val colorize_dag : (D.node → D.edge × D.children → fibred_dag → (CA.D.node × (CA.D.edge × CA.D.children)) list × CWFBundle.t) → (D.node → fibred_dag → CA.D.node × CWFBundle.t) → D.t → CWFBundle.t → fibred_dag`.

```

let colorize_dag f_node f_ext dag wf_bundle =
  A.D.fold (colorize_nodes f_node) dag
    (A.D.fold_nodes (colorize_sterile_nodes dag f_ext) dag
      { dag = CA.D.empty; bundle = wf_bundle })

let colorize_external wf fibred_dag =
  match CWFBundle.inv_pi wf fibred_dag.bundle with
  | [c_wf] → (c_wf, fibred_dag.bundle)

```

```

| [] → failwith "colorize_external:_not_found"
| _ → failwith "colorize_external:_not_unique"

let fuse_c_wf rhs =
  let momenta = PT.map (fun wf → wf.CA.momentum) rhs in
  List.filter
    (fun (_, c) → kmatrix_cuts c momenta)
    (CM.fuse (List.map (fun wf → wf.CA.flavor) (PT.to_list rhs)))

let colorize_coupling c coupling =
  { coupling with Tagged_Coupling.coupling = c }

let colorize_fusion wf (coupling, children) fibered_dag =
  let match_flavor (f, _) = (CM.flavor_sans_color f = A.flavor wf)
  and find_colored wf' = CWFBundle.inv_pi wf' fibered_dag.bundle in
  let fusions =
    ThoList.flatmap
      (fun c_children →
        List.map
          (fun (f, c) →
            (colorize_wf f wf, (colorize_coupling c coupling, c_children)))
          (List.filter match_flavor (fuse_c_wf c_children)))
      (PT.product (PT.map find_colored children)) in
  let bundle =
    List.fold_right (fun (c_wf, _) → CWFBundle.add c_wf) fusions fibered_dag.bundle in
  (fusions, bundle)

let colorize_braket1 (wf, (coupling, children)) fibered_dag =
  let find_colored wf' = CWFBundle.inv_pi wf' fibered_dag.bundle in
  Product.fold2
    (fun bra ket acc →
      List.fold_left
        (fun brackets (f, c) →
          if CM.conjugate bra.CA.flavor = f then
            (bra, (colorize_coupling c coupling, ket)) :: brackets
          else
            brackets)
        acc (fuse_c_wf ket))
    (find_colored wf) (PT.product (PT.map find_colored children)) []

module CWFMap = Map.Make (struct type t = CA.wf let compare = CA.order_wf end)
module CKetSet = Set.Make (struct type t = CA.rhs let compare = compare end)

let factorize_brackets brackets =
  CWFMap.fold
    (fun bra ket acc →
      (bra, CKetSet.elements ket) :: acc)
    (List.fold_left
      (fun map (bra, ket) →
        CWFMap.add
          bra
          (CKetSet.add ket (try CWFMap.find bra map with Not_found →
            CKetSet.empty)))
      map brackets)

```

```

        map)
        CWFMap.empty brackets)
    []
let colorize_braket (wf, rhs_list) fibered_dag =
  factorize_brackets
    (ThoList.flatMap
      (fun rhs → (colorize_braket1 (wf, rhs) fibered_dag))
      rhs_list)
let colorize_amplitude a fin fout =
  let f = fin @ List.map CM.conjugate fout in
  let nin, nout = List.length fin, List.length fout in
  let n = nin + nout in
  let externals = List.combine f (ThoList.range 1 n) in
  let external_wfs = CA.external_wfs n externals in
  let wf_bundle = CWFBundle.of_list external_wfs in
  let fibered_dag =
    colorize_dag colorize_fusion colorize_external a.A.fusion_dag wf_bundle in
  let brackets =
    ThoList.flatMap (fun braket → colorize_braket braket fibered_dag) a.A.brackets in
  let dag = CA.D.harvest_list fibered_dag.dag (CA.wavefunctions brackets) in
  let fusions =
    List.filter (function (_, []) → false | _ → true) (CA.D.lists dag) in
  let dependencies_map =
    CA.D.fold (fun wf _ → CWFMap.add wf (CA.D.dependencies dag wf)) dag CWFMap.empty in
  { CA.fusions = fusions;
    CA.brackets = brackets;
    CA.constraints = a.A.constraints;
    CA.incoming = fin;
    CA.outgoing = fout;
    CA.externals = external_wfs;
    CA.fusion_dag = dag;
    CA.fusion_tower = dag;
    CA.symmetry = a.A.symmetry;
    CA.on_shell = (fun wf → a.A.on_shell (uncolorize_wf wf));
    CA.is_gauss = (fun wf → a.A.is_gauss (uncolorize_wf wf));
    CA.dependencies = (fun wf → CWFMap.find wf dependencies_map) }
let allowed_amplitude =
  match amplitude.CA.brackets with
  | [] → false
  | _ → true
let colorize_amplitudes a =
  List.fold_left
    (fun amps (fin, fout) →
      let amp = colorize_amplitude a fin fout in
      if allowed amp then

```

```

    amp :: amps
  else
    amps)
  [] (CM.amplitude a.A.incoming a.A.outgoing)
let amplitudes goldstones selectors fin fout =
  colorize_amplitudes (amplitude goldstones selectors fin fout)
type flavor = CA.flavor
type flavor_sans_color = A.flavor
type p = A.p
type wf = CA.wf
let flavor = CA.flavor
let flavor_sans_color wf = CM.flavor_sans_color (CA.flavor wf)
let momentum = CA.momentum
let momentum_list = CA.momentum_list
let wf_tag = CA.wf_tag
type coupling = CA.coupling
let sign = CA.sign
let coupling = CA.coupling
let coupling_tag = CA.coupling_tag
type  $\alpha$  children =  $\alpha$  CA.children
type rhs = CA.rhs
let children = CA.children
type fusion = CA.fusion
let lhs = CA.lhs
let rhs = CA.rhs
type bracket = CA.braket
let bra = CA.bra
let ket = CA.ket
type amplitude = CA.amplitude
let incoming = CA.incoming
let outgoing = CA.outgoing
let externals = CA.externals
let fusions = CA.fusions
let brackets = CA.brackets
let symmetry = CA.symmetry
let on_shell = CA.on_shell
let is_gauss = CA.is_gauss
let constraints = CA.constraints
let variables a = List.map lhs (fusions a)
let dependencies = CA.dependencies

```

Checking Conservation Laws

```
let check_charges () =
```

```

let vlist3, vlist4, vlistn = M.vertices () in
List.filter
  (fun flist → ¬ (M.Ch.is_null (M.Ch.sum (List.map M.charges flist))))
  (List.map (fun ((f1, f2, f3), -, -) → [f1; f2; f3]) vlist3
    @ List.map (fun ((f1, f2, f3, f4), -, -) → [f1; f2; f3; f4]) vlist4
    @ List.map (fun (flist, -, -) → flist) vlistn)

```

Diagnostics

```

let count_propagators a =
  List.length a.CA.fusions

let count_fusions a =
  List.fold_left (fun n (_, a) → n + List.length a) 0 a.CA.fusions
  + List.fold_left (fun n (_, t) → n + List.length t) 0 a.CA.brackets
  + List.length a.CA.brackets

```



This brute force approach blows up for more than ten particles. Find a smarter algorithm.

```

let count_diagrams a =
  List.fold_left (fun n (wf1, wf23) →
    n + CA.D.count_trees wf1 a.CA.fusion_dag ×
    (List.fold_left (fun n' (_, wfs) →
      n' + PT.fold_left (fun n'' wf →
        n'' × CA.D.count_trees wf a.CA.fusion_dag) 1 wfs) 0 wf23))
    0 a.CA.brackets

exception Impossible

```



We still need to perform the appropriate charge conjugations so that we get the correct flavors for the external tree representation.

```

let forest' a =
  let below wf = CA.D.forest_memoized wf a.CA.fusion_dag in
  ThoList.flatmap
    (fun (bra, ket) →
      (Product.list2 (fun bra' ket' → bra' :: ket')
        (below bra)
        (ThoList.flatmap
          (fun (_, wfs) →
            Product.list (fun w → w) (PT.to_list (PT.map below wfs))
            ket)))
      a.CA.brackets

let cross wf =
  { CA.flavor = CM.conjugate wf.CA.flavor;

```

```

    CA.momentum = P.neg wf.CA.momentum;
    CA.wf_tag = wf.CA.wf_tag }

let fuse_trees wf ts =
  Tree.fuse (fun (wf', e) → (cross wf', e))
  wf (fun t → List.mem wf (Tree.leafs t)) ts

let forest wf a =
  List.map (fuse_trees wf) (forest' a)

let poles_beneath wf dag =
  CA.D.eval_memoized (fun wf' → [[]])
  (fun wf' _ p → List.map (fun p' → wf' :: p') p)
  (fun wf1 wf2 →
    Product.fold2 (fun wf' wfs' wfs'' → (wf' @ wfs') :: wfs'') wf1 wf2 [])
  (@) [[]] [[]] wf dag

let poles a =
  ThoList.flatmap (fun (wf1, wf23) →
    let poles_wf1 = poles_beneath wf1 a.CA.fusion_dag in
    (ThoList.flatmap (fun (_, wfs) →
      Product.list List.flatten
      (PT.to_list (PT.map (fun wf →
        poles_wf1 @ poles_beneath wf a.CA.fusion_dag) wfs)))
      wf23))
  a.CA.brackets

module WFSets =
  Set.Make (struct type t = CA.wf let compare = CA.order_wf end)

let s_channel a =
  WFSets.elements
  (ThoList.fold_right2
    (fun wf wfs →
      if P.Scattering.timelike wf.CA.momentum then
        WFSets.add wf wfs
      else
        wfs) (poles a) WFSets.empty)

```



This should be much faster! Is it correct? Is it faster indeed?

```

let poles' a =
  List.map CA.lhs a.CA.fusions

let s_channel a =
  WFSets.elements
  (List.fold_right
    (fun wf wfs →
      if P.Scattering.timelike wf.CA.momentum then
        WFSets.add wf wfs
      else
        wfs) (poles' a) WFSets.empty)

```


Pictures

Export the DAG in the `dot(1)` file format so that we can draw pretty pictures to impress audiences ...

```

let p2s p =
  if p ≥ 0 ∧ p ≤ 9 then
    string_of_int p
  else if p ≤ 36 then
    String.make 1 (Char.chr (Char.code 'A' + p - 10))
  else
    "_"

let variable wf =
  CM.flavor_symbol wf.CA.flavor ^
  String.concat "" (List.map p2s (P.to_ints wf.CA.momentum))

module Int = Map.Make (struct type t = int let compare = compare end)

let add_to_list i n m =
  Int.add i (n :: try Int.find i m with Not_found → []) m

let classify_nodes dag =
  Int.fold (fun i n acc → (i, n) :: acc)
    (CA.D.fold_nodes (fun wf → add_to_list (P.rank wf.CA.momentum) wf)
      dag Int.empty) []

let dag_to_dot ch brackets dag =
  Printf.fprintf ch "digraph_Ω_{\n";
  CA.D.iter_nodes (fun wf →
    Printf.fprintf ch "_{\n" [label=] "\n";
    (variable wf) (variable wf)) dag;
  List.iter (fun (_, wfs) →
    Printf.fprintf ch "_{rank=}\n";
    List.iter (fun n →
      Printf.fprintf ch "\n"; (variable n)) wfs;
    Printf.fprintf ch "\n"; (classify_nodes dag));
  List.iter (fun n →
    Printf.fprintf ch "\n->\n"; (variable n))
    (flatten_keystones brackets);
  CA.D.iter (fun n (_, ns) →
    let p = variable n in
    PT.iter (fun n' →
      Printf.fprintf ch "\n->\n"; (variable n')) ns) dag;
  Printf.fprintf ch "\n"

let tower_to_dot ch a =
  dag_to_dot ch a.CA.brackets a.CA.fusion_tower

let amplitude_to_dot ch a =
  dag_to_dot ch a.CA.brackets a.CA.fusion_dag

let rcs_list = [CA.D.rcs; T.rcs; P.rcs; CM.rcs; rcs]

end

```

```

module Make = Tagged(Order_Tags)
module Binary = Make(Tuple.Binary)(Stat_Dirac)(Topology.Binary)
module Tagged_Binary (T : Tagger) =
  Tagged(T)(Tuple.Binary)(Stat_Dirac)(Topology.Binary)

```

8.2.5 Fusions with Majorana Fermions

```

module Stat_Majorana (M : Model.T) : (Stat with type flavor = M.flavor) =
struct
  let rcs = RCS.rename rcs_file "Fusion.Stat_Majorana()"
    [ "Fermi_statistics_with_fermion_number_violation" ]

  type flavor = M.flavor

  type stat =
    | Fermion of int × int list
    | AntiFermion of int × int list
    | Boson of int list
    | Majorana of int × int list

  let stat f p =
    let s = M.fermion f in
    if s = 0 then
      Boson []
    else if s < 0 then
      AntiFermion (p, [])
    else if s = 1 then (* if s = 1 then *)
      Fermion (p, [])
    else (* if s > 1 then *)
      Majorana (p, [])

```



JR sez' (regarding the Majorana Feynman rules): In the formalism of [7], it does not matter to distinguish spinors and conjugate spinors, it is only important to know in which direction a fermion line is calculated. So the sign is made by the calculation together with an additional one due to the permutation of the pairs of endpoints of fermion lines in the direction they are calculated. We propose a “canonical” direction from the right to the left child at a fusion point so we only have to keep in mind which external particle hangs at each side. Therefore we need not to have a list of pairs of conjugate spinors and spinors but just a list in which the pairs are right-left-right-left and so on. Unfortunately it is unavoidable to have couplings with clashing arrows in supersymmetric theories so we need transmutations from fermions in antifermions and vice versa as well. (*JR's probably right, but I need to check myself...*)

```

exception Impossible

let stat_fuse s1 s2 f =

```

```

match s1, s2, M.lorentz f with
| Boson l1, Fermion (p, l2), Coupling.Majorana
| Boson l1, AntiFermion (p, l2), Coupling.Majorana
| Fermion (p, l1), Boson l2, Coupling.Majorana
| AntiFermion (p, l1), Boson l2, Coupling.Majorana
| Majorana (p, l1), Boson l2, Coupling.Majorana
| Boson l1, Majorana (p, l2), Coupling.Majorana →
  Majorana (p, l1 @ l2)
| Boson l1, Fermion (p, l2), Coupling.Spinor
| Boson l1, AntiFermion (p, l2), Coupling.Spinor
| Fermion (p, l1), Boson l2, Coupling.Spinor
| AntiFermion (p, l1), Boson l2, Coupling.Spinor
| Majorana (p, l1), Boson l2, Coupling.Spinor
| Boson l1, Majorana (p, l2), Coupling.Spinor →
  Fermion (p, l1 @ l2)
| Boson l1, Fermion (p, l2), Coupling.ConjSpinor
| Boson l1, AntiFermion (p, l2), Coupling.ConjSpinor
| Fermion (p, l1), Boson l2, Coupling.ConjSpinor
| AntiFermion (p, l1), Boson l2, Coupling.ConjSpinor
| Majorana (p, l1), Boson l2, Coupling.ConjSpinor
| Boson l1, Majorana (p, l2), Coupling.ConjSpinor →
  AntiFermion (p, l1 @ l2)
| Boson l1, Fermion (p, l2), Coupling.Vectorspinor
| Boson l1, AntiFermion (p, l2), Coupling.Vectorspinor
| Fermion (p, l1), Boson l2, Coupling.Vectorspinor
| AntiFermion (p, l1), Boson l2, Coupling.Vectorspinor
| Majorana (p, l1), Boson l2, Coupling.Vectorspinor
| Boson l1, Majorana (p, l2), Coupling.Vectorspinor →
  Majorana (p, l1 @ l2)
| Boson l1, Boson l2, - → Boson (l1 @ l2)
| AntiFermion (p1, l1), Fermion (p2, l2), -
| Fermion (p1, l1), AntiFermion (p2, l2), -
| Fermion (p1, l1), Fermion (p2, l2), -
| AntiFermion (p1, l1), AntiFermion (p2, l2), -
| Fermion (p1, l1), Majorana (p2, l2), -
| Majorana (p1, l1), Fermion (p2, l2), -
| AntiFermion (p1, l1), Majorana (p2, l2), -
| Majorana (p1, l1), AntiFermion (p2, l2), -
| Majorana (p1, l1), Majorana (p2, l2), - →
  Boson ([p2; p1] @ l1 @ l2)
| Boson l1, Majorana (p, l2), - → Majorana (p, l1 @ l2)
| Boson l1, Fermion (p, l2), - → Fermion (p, l1 @ l2)
| Boson l1, AntiFermion (p, l2), - → AntiFermion (p, l1 @ l2)
| Fermion (p, l1), Boson l2, - → Fermion (p, l1 @ l2)
| AntiFermion (p, l1), Boson l2, - → AntiFermion (p, l1 @ l2)
| Majorana (p, l1), Boson l2, - → Majorana (p, l1 @ l2)

let permutation_lines = fst(Combinatorics.sort_signed compare lines)

let stat_sign = function
| Boson lines → permutation_lines

```

```

    | Fermion (p, lines) → permutation (p :: lines)
    | AntiFermion (pbar, lines) → permutation (pbar :: lines)
    | Majorana (pm, lines) → permutation (pm :: lines)
end

module Binary_Majorana =
  Make(Tuple.Binary)(Stat_Majorana)(Topology.Binary)

module Nary (B : Tuple.Bound) =
  Make(Tuple.Nary(B))(Stat_Dirac)(Topology.Nary(B))
module Nary_Majorana (B : Tuple.Bound) =
  Make(Tuple.Nary(B))(Stat_Majorana)(Topology.Nary(B))

module Mixed23 =
  Make(Tuple.Mixed23)(Stat_Dirac)(Topology.Mixed23)
module Mixed23_Majorana =
  Make(Tuple.Mixed23)(Stat_Majorana)(Topology.Mixed23)

module Helac (B : Tuple.Bound) =
  Make(Tuple.Nary(B))(Stat_Dirac)(Topology.Helac(B))
module Helac_Majorana (B : Tuple.Bound) =
  Make(Tuple.Nary(B))(Stat_Majorana)(Topology.Helac(B))

```

8.2.6 Multiple Amplitudes

```

module type Multi =
sig
  exception Mismatch
  val options : Options.t
  type flavor
  type process = flavor list × flavor list
  type amplitude
  type fusion
  type wf
  type selectors
  type amplitudes
  val amplitudes : bool → int option → selectors → process list →
amplitudes
  val empty : amplitudes
  val initialize_cache : string → unit
  val set_cache_name : string → unit
  val flavors : amplitudes → process list
  val vanishing_flavors : amplitudes → process list
  val color_flows : amplitudes → Color.Flow.t list
  val helicities : amplitudes → (int list × int list) list
  val processes : amplitudes → amplitude list
  val process_table : amplitudes → amplitude option array array
  val fusions : amplitudes → (fusion × amplitude) list
  val multiplicity : amplitudes → wf → int
  val dictionary : amplitudes → amplitude → wf → int

```

```

    val color_factors : amplitudes → Color.Flow.factor array array
    val constraints : amplitudes → string option
end

module type Multi_Maker = functor (Fusion_Maker : Maker) →
  functor (P : Momentum.T) →
    functor (M : Model.T) →
      Multi with type flavor = M.flavor
      and type amplitude = Fusion_Maker(P)(M).amplitude
      and type fusion = Fusion_Maker(P)(M).fusion
      and type wf = Fusion_Maker(P)(M).wf
      and type selectors = Fusion_Maker(P)(M).selectors

module Multi (Fusion_Maker : Maker) (P : Momentum.T) (M : Model.T) =
  struct
    exception Mismatch

    type progress_mode =
      | Quiet
      | Channel of out_channel
      | File of string

    let progress_option = ref Quiet

    module CM = Colorize.It(M)
    module F = Fusion_Maker(P)(M)
    module C = Cascade.Make(M)(P)
  end

```



A kludge, at best ...

```

let options = Options.extend F.options
  [ "progress", Arg.Unit (fun () → progress_option := Channel stderr),
    "report_progress_to_the_standard_error_stream";
    "progress_file", Arg.String (fun s → progress_option := File s),
    "report_progress_to_a_file" ]

type flavor = M.flavor
type p = F.p
type process = flavor list × flavor list
type amplitude = F.amplitude
type fusion = F.fusion
type wf = F.wf
type selectors = F.selectors

type flavors = flavor list array
type helicities = int list array
type colors = Color.Flow.t array

type amplitudes' = amplitude array array array
type amplitudes =
  { flavors : process list;
    vanishing_flavors : process list;
  }

```

```

    color_flows : Color.Flow.t list;
    helicities : (int list × int list) list;
    processes : amplitude list;
    process_table : amplitude option array array;
    fusions : (fusion × amplitude) list;
    multiplicity : (wf → int);
    dictionary : (amplitude → wf → int);
    color_factors : Color.Flow.factor array array;
    constraints : string option }

let flavors a = a.flavors
let vanishing_flavors a = a.vanishing_flavors
let color_flows a = a.color_flows
let helicities a = a.helicities
let processes a = a.processes
let process_table a = a.process_table
let fusions a = a.fusions
let multiplicity a = a.multiplicity
let dictionary a = a.dictionary
let color_factors a = a.color_factors
let constraints a = a.constraints

let sans_colors f =
  List.map CM.flavor_sans_color f

let colors (fin, fout) =
  List.map M.color (fin @ fout)

let process_sans_color a =
  (sans_colors (F.incoming a), sans_colors (F.outgoing a))

let color_flow a =
  CM.flow (F.incoming a) (F.outgoing a)

let process_to_string fin fout =
  String.concat "□" (List.map M.flavor_to_string fin)
  ^ "□->□" ^ String.concat "□" (List.map M.flavor_to_string fout)

let count_processes colored_processes =
  List.length colored_processes

module FMap =
  Map.Make (struct type t = process let compare = compare end)

module CMap =
  Map.Make (struct type t = Color.Flow.t let compare = compare end)

```

Recently *Product.list* began to guarantee lexicographic order for sorted arguments. Anyway, we still force a lexicographic order.

```

let rec order_spin_table1 s1 s2 =
  match s1, s2 with
  | h1 :: t1, h2 :: t2 →
    let c = compare h1 h2 in
    if c ≠ 0 then
      c

```

```

      else
        order_spin_table1 t1 t2
    | [], [] → 0
    | - → invalid_arg "order_spin_table: inconsistent lengths"
let order_spin_table (s1_in, s1_out) (s2_in, s2_out) =
  let c = compare s1_in s2_in in
  if c ≠ 0 then
    c
  else
    order_spin_table1 s1_out s2_out
let sort_spin_table table =
  List.sort order_spin_table table
let id x = x
let pair x y = (x, y)

```



Improve support for on shell Ward identities: *Coupling.Vector* → [4] for one and only one external vector.

```

let rec hs_of_lorentz = function
  | Coupling.Scalar → [0]
  | Coupling.Spinor | Coupling.ConjSpinor
  | Coupling.Majorana | Coupling.Maj_Ghost → [-1; 1]
  | Coupling.Vector → [-1; 1]
  | Coupling.Massive_Vector → [-1; 0; 1]
  | Coupling.Tensor_1 → [-1; 0; 1]
  | Coupling.Vectorspinor → [-2; -1; 1; 2]
  | Coupling.Tensor_2 → [-2; -1; 0; 1; 2]
  | Coupling.BRS f → hs_of_lorentz f
let hs_of_flavor f =
  hs_of_lorentz (M.lorentz f)
let hs_of_flavors (fin, fout) =
  (List.map hs_of_flavor fin, List.map hs_of_flavor fout)
let rec unphysical_of_lorentz = function
  | Coupling.Vector → [4]
  | Coupling.Massive_Vector → [4]
  | - → invalid_arg "unphysical_of_lorentz: not a vector particle"
let unphysical_of_flavor f =
  unphysical_of_lorentz (M.lorentz f)
let unphysical_of_flavors1 n f_list =
  ThoList.map i
    (fun i f → if i = n then unphysical_of_flavor f else hs_of_flavor f)
    1 f_list
let unphysical_of_flavors n (fin, fout) =
  (unphysical_of_flavors1 n fin, unphysical_of_flavors1 (n - List.length fin) fout)

```

```

let helicity_table unphysical flavors =
  let hs =
    begin match unphysical with
    | None → List.map hs_of_flavors flavors
    | Some n → List.map (unphysical_of_flavors n) flavors
    end in
  if ¬ (ThoList.homogeneous hs) then
    invalid_arg "Fusion.helicity_table: not all flavors have the same helicity states!"
  else
    match hs with
    | [] → []
    | (hs_in, hs_out) :: _ →
        sort_spin_table (Product.list2 pair (Product.list id hs_in) (Product.list id hs_out))

module Proc = Process.Make(M)

module WFMap = Map.Make (struct type t = F.wf let compare = compare end)
module WFSet2 =
  Set.Make (struct type t = F.wf × (F.wf, F.coupling) Tree2.t let compare = compare end)
module WFMap2 =
  Map.Make (struct type t = F.wf × (F.wf, F.coupling) Tree2.t let compare = compare end)
module WFTSet =
  Set.Make (struct type t = (F.wf, F.coupling) Tree2.t let compare = compare end)

```

All wavefunctions are unique per amplitude. So we can use per-amplitude dependency trees without additional *internal* tags to identify identical wave functions.

NB: we miss potential optimizations, because we assume all coupling to be different, while in fact we have horizontal/family symmetries and non abelian gauge couplings are universal anyway.

```

let disambiguate_fusions amplitudes =
  let fusions =
    ThoList.flatmap (fun amplitude →
      List.map
        (fun fusion → (fusion, F.dependencies amplitude (F.lhs fusion)))
        (F.fusions amplitude))
    amplitudes in
  let duplicates =
    List.fold_left
      (fun map (fusion, dependencies) →
        let wf = F.lhs fusion in
        let set = try WFMap.find wf map with Not_found → WFTSet.empty in
        WFMap.add wf (WFTSet.add dependencies set) map)
      WFMap.empty fusions in
  let multiplicity_map =
    WFMap.fold (fun wf dependencies acc →
      let cardinal = WFTSet.cardinal dependencies in
      if cardinal ≤ 1 then
        acc
      else
        WFMap.add wf cardinal acc)

```



```

    duplicates WFMap.empty
and dictionary_map =
  WFMap.fold (fun wf dependencies acc →
    let cardinal = WFTSet.cardinal dependencies in
    if cardinal ≤ 1 then
      acc
    else
      snd (WFTSet.fold
        (fun dependency (i', acc') →
          (succ i', WFMap2.add (wf, dependency) i' acc'))
        dependencies (1, acc)))
    duplicates WFMap2.empty in
let multiplicity wf =
  WFMap.find wf multiplicity_map
and dictionary_amplitude wf =
  WFMap2.find (wf, F.dependencies amplitude wf) dictionary_map in
(multiplicity, dictionary)

let eliminate_common_fusions1 seen_wfs amplitude =
  List.fold_left
    (fun (seen, acc) f →
      let wf = F.lhs f in
      let dependencies = F.dependencies amplitude wf in
      if WFTSet2.mem (wf, dependencies) seen then
        (seen, acc)
      else
        (WFTSet2.add (wf, dependencies) seen, (f, amplitude) :: acc))
    seen_wfs (F.fusions amplitude)

let eliminate_common_fusions processes =
  let _, rev_fusions =
    List.fold_left
      eliminate_common_fusions1
      (WFTSet2.empty, []) processes in
  List.rev rev_fusions

```

Calculate All The Amplitudes

```
let amplitudes_goldstones_unphysical_select_wf processes =
```



Eventually, we might want to support inhomogeneous helicities. However, this makes little physics sense for external particles on the mass shell, unless we have a model with degenerate massive fermions and bosons.

```

if ¬ (ThoList.homogeneous (List.map hs_of_flavors processes)) then
  invalid_arg "Fusion.Multi.amplitudes: incompatible helicities";
let unique_uncolored_processes =

```

```

    Proc.remove_duplicate_final_states (C.partition select_wf) processes in

let progress =
  match !progress_option with
  | Quiet → Progress.dummy
  | Channel oc → Progress.channel oc (count_processes unique_uncolored_processes)
  | File name → Progress.file name (count_processes unique_uncolored_processes) in

let allowed =
  ThoList.flatmap
    (fun (fi, fo) →
      Progress.begin_step progress (process_to_string fi fo);
      let amps = F.amplitudes goldstones select_wf fi fo in
      begin match amps with
      | [] → Progress.end_step progress "forbidden"
      | _ → Progress.end_step progress "allowed"
      end;
      amps) unique_uncolored_processes in

Progress.summary progress "all_processes_done";

let color_flows =
  ThoList.uniq (List.sort compare (List.map color_flow allowed))
and flavors =
  ThoList.uniq (List.sort compare (List.map process_sans_color allowed)) in

let vanishing_flavors =
  Proc.diff processes flavors in

let helicities =
  helicity_table unphysical flavors in

let f_index =
  fst (List.fold_left
    (fun (m, i) f → (FMap.add f i m, succ i))
    (FMap.empty, 0) flavors)
and c_index =
  fst (List.fold_left
    (fun (m, i) c → (CMap.add c i m, succ i))
    (CMap.empty, 0) color_flows) in

let table =
  Array.make_matrix (List.length flavors) (List.length color_flows) None in
List.iter
  (fun a →
    let f = FMap.find (process_sans_color a) f_index
    and c = CMap.find (color_flow a) c_index in
    table.(f).(c) ← Some (a))
  allowed;

let cf_array = Array.of_list color_flows in
let ncf = Array.length cf_array in
let color_factor_table = Array.make_matrix ncf ncf Color.Flow.zero in
for i = 0 to pred ncf do

```

```

    for  $j = 0$  to  $i$  do
        color_factor_table.( $i$ ).( $j$ ) ←
            Color.Flow.factor cf_array.( $i$ ) cf_array.( $j$ );
        color_factor_table.( $j$ ).( $i$ ) ←
            color_factor_table.( $i$ ).( $j$ )
    done
done;

let fusions = eliminate_common_fusions allowed
and multiplicity, dictionary = disambiguate_fusions allowed in

{ flavors = flavors;
  vanishing_flavors = vanishing_flavors;
  color_flows = color_flows;
  helicities = helicities;
  processes = allowed;
  process_table = table;
  fusions = fusions;
  multiplicity = multiplicity;
  dictionary = dictionary;
  color_factors = color_factor_table;
  constraints = C.description select_wf }

let initialize_cache = F.initialize_cache
let set_cache_name = F.set_cache_name

let empty =
{ flavors = [];
  vanishing_flavors = [];
  color_flows = [];
  helicities = [];
  processes = [];
  process_table = Array.make_matrix 0 0 None;
  fusions = [];
  multiplicity = (fun _ → 1);
  dictionary = (fun _ _ → 1);
  color_factors = Array.make_matrix 0 0 Color.Flow.zero;
  constraints = None }

end

```

—9—

LORENTZ REPRESENTATIONS, COUPLINGS, MODELS AND TARGETS

9.1 Interface of Coupling

The enumeration types used for communication from *Models* to *Targets*. On the physics side, the modules in *Models* must implement the Feynman rules according to the conventions set up here. On the numerics side, the modules in *Targets* must handle all cases according to the same conventions.

9.1.1 Propagators

The Lorentz representation of the particle. NB: O’Mega treats all lines as *outgoing* and particles are therefore transforming as *ConjSpinor* and antiparticles as *Spinor*.

```
type lorentz =
  | Scalar
  | Spinor (*  $\psi$  *)
  | ConjSpinor (*  $\bar{\psi}$  *)
  | Majorana (*  $\chi$  *)
  | Maj_Ghost (* SUSY ghosts *)
  | Vector
  | Massive_Vector
  | Vectorspinor (* supersymmetric currents and gravitinos *)
  | Tensor_1
  | Tensor_2 (* massive gravitons (large extra dimensions) *)
  | BRS of lorentz
```

If there were no vectors or auxiliary fields, we could deduce the propagator from the Lorentz representation. While we’re at it, we can introduce “propagators” for the contact interactions of auxiliary fields as well. *Prop_Gauge* and *Prop_Feynman* are redundant as special cases of *Prop_Rxi*.

The special case *Only_Insertion* corresponds to operator insertions that do not correspond to a propagating field all. These are used for checking Slavnov-Taylor identities

$$\partial_\mu \langle \text{out} | W^\mu(x) | \text{in} \rangle = m_W \langle \text{out} | \phi(x) | \text{in} \rangle \quad (9.1)$$

	only Dirac fermions	incl. Majorana fermions
<i>Prop_Scalar</i>	$\phi(p) \leftarrow \frac{i}{p^2 - m^2 + im\Gamma} \phi(p)$	
<i>Prop_Spinor</i>	$\psi(p) \leftarrow \frac{i(-\not{p} + m)}{p^2 - m^2 + im\Gamma} \psi(p)$	$\psi(p) \leftarrow \frac{i(-\not{p} + m)}{p^2 - m^2 + im\Gamma} \psi(p)$
<i>Prop_ConjSpinor</i>	$\bar{\psi}(p) \leftarrow \bar{\psi}(p) \frac{i(\not{p} + m)}{p^2 - m^2 + im\Gamma}$	$\psi(p) \leftarrow \frac{i(-\not{p} + m)}{p^2 - m^2 + im\Gamma} \psi(p)$
<i>Prop_Majorana</i>	N/A	$\chi(p) \leftarrow \frac{i(-\not{p} + m)}{p^2 - m^2 + im\Gamma} \chi(p)$
<i>Prop_Unitarity</i>	$\epsilon_\mu(p) \leftarrow \frac{i}{p^2 - m^2 + im\Gamma} \left(-g_{\mu\nu} + \frac{p_\mu p_\nu}{m^2} \right) \epsilon^\nu(p)$	
<i>Prop_Feynman</i>	$\epsilon^\nu(p) \leftarrow \frac{-i}{p^2 - m^2 + im\Gamma} \epsilon^\nu(p)$	
<i>Prop_Gauge</i>	$\epsilon_\mu(p) \leftarrow \frac{i}{p^2} \left(-g_{\mu\nu} + (1 - \xi) \frac{p_\mu p_\nu}{p^2} \right) \epsilon^\nu(p)$	
<i>Prop_Rxi</i>	$\epsilon_\mu(p) \leftarrow \frac{i}{p^2 - m^2 + im\Gamma} \left(-g_{\mu\nu} + (1 - \xi) \frac{p_\mu p_\nu}{p^2 - \xi m^2} \right) \epsilon^\nu(p)$	

Table 9.1: Propagators. NB: The sign of the momenta in the spinor propagators comes about because O'Mega treats all momenta as *outgoing* and the charge flow for *Spinor* is therefore opposite to the momentum, while the charge flow for *ConjSpinor* is parallel to the momentum.

<i>Aux_Scalar</i>	$\phi(p) \leftarrow i\phi(p)$
<i>Aux_Spinor</i>	$\psi(p) \leftarrow i\psi(p)$
<i>Aux_ConjSpinor</i>	$\bar{\psi}(p) \leftarrow i\bar{\psi}(p)$
<i>Aux_Vector</i>	$\epsilon^\mu(p) \leftarrow i\epsilon^\mu(p)$
<i>Aux_Tensor_1</i>	$T^{\mu\nu}(p) \leftarrow iT^{\mu\nu}(p)$
<i>Only_Insertion</i>	N/A

Table 9.2: Auxiliary and non propagating fields

of gauge theories in unitarity gauge where the Goldstone bosons are not propagating. Numerically, it would suffice to use a vanishing propagator, but then superfluous fusions would be calculated in production code in which the Slavnov-Taylor identities are not tested.

```

type  $\alpha$  propagator =
  | Prop_Scalar | Prop_Ghost
  | Prop_Spinor | Prop_ConjSpinor | Prop_Majorana
  | Prop_Unitarity | Prop_Feynman | Prop_Gauge of  $\alpha$  | Prop_Rxi of  $\alpha$ 
  | Prop_Tensor_2 | Prop_Vectorspinor
  | Prop_Col_Scalar | Prop_Col_Feynman | Prop_Col_Majorana
  | Prop_Col_Unitarity
  | Aux_Scalar | Aux_Vector | Aux_Tensor_1
  | Aux_Col_Scalar | Aux_Col_Vector | Aux_Col_Tensor_1
  | Aux_Spinor | Aux_ConjSpinor | Aux_Majorana
  | Only_Insertion

```



JR sez' (regarding the Majorana Feynman rules): We don't need different fermionic propagators as supposed by the variable names *Prop_Spinor*, *Prop_ConjSpinor* or *Prop_Majorana*. The propagator in all cases has to be multiplied on the left hand side of the spinor out of which a new one should be built. All momenta are treated as *outgoing*, so for the propagation of the different fermions the following table arises, in which the momentum direction is always downwards and the arrows show whether the momentum and the fermion line, respectively are parallel or antiparallel to the direction of calculation:

Fermion type	fermion arrow	mom.	calc.	sign
Dirac fermion	↑	↑ ↓	↑ ↑	negative
Dirac antifermion	↓	↓ ↓	↑ ↓	negative
Majorana fermion	-	↑ ↓	-	negative

So the sign of the momentum is always negative and no further distinction is needed. (*JR's probably right, but I need to check myself ...*)

```

type width =
  | Vanishing
  | Constant
  | Timelike
  | Running
  | Fudged
  | Custom of string

```

9.1.2 Vertices

The combined $S - P$ and $V - A$ couplings (see tables 9.5, 9.6, 9.8 and 9.12) are redundant, of course, but they allow some targets to create more efficient

numerical code.¹ Choosing VA2 over VA will cause the FORTRAN backend to pass the coupling as a whole array

```

type fermion = Psi | Chi | Grav
type fermionbar = Psibar | Chibar | Gravbar
type boson =
  | SP | SPM | S | P | SL | SR | SLR | VA | V | A | VL | VR |
  VLR | VLRM
  | TVA | TLR | TRL | TVAM | TLRM | TRLM
  | POT | MOM | MOM5 | MOML | MOMR | LMOM | RMOM |
  VMOM | VA2
type boson2 = S2 | P2 | S2P | S2L | S2R | S2LR
  | SV | PV | SLV | SRV | SLRV | V2 | V2LR

```

The integer is an additional coefficient that multiplies the respective coupling constant. This allows to reduce the number of required coupling constants in manifestly symmetric cases. Most of times it will be equal unity, though.

The two vertex types *PBP* and *BBB* for the couplings of two fermions or two antifermions ("clashing arrows") is unavoidable in supersymmetric theories.



... tho doesn't like the names and has promised to find a better mnemonics!

```

type α vertex3 =
  | FBF of int × fermionbar × boson × fermion
  | PBP of int × fermion × boson × fermion
  | BBB of int × fermionbar × boson × fermionbar
  | GBG of int × fermionbar × boson × fermion (* gravitino-boson-fermion
*)
  | Gauge_Gauge_Gauge of int | Aux_Gauge_Gauge of int
  | Scalar_Vector_Vector of int
  | Aux_Vector_Vector of int | Aux_Scalar_Vector of int
  | Scalar_Scalar_Scalar of int | Aux_Scalar_Scalar of int
  | Vector_Scalar_Scalar of int
  | Graviton_Scalar_Scalar of int
  | Graviton_Vector_Vector of int
  | Graviton_Spinor_Spinor of int
  | Dim4_Vector_Vector_Vector_T of int
  | Dim4_Vector_Vector_Vector_L of int
  | Dim4_Vector_Vector_Vector_T5 of int
  | Dim4_Vector_Vector_Vector_L5 of int
  | Dim6_Gauge_Gauge_Gauge of int
  | Dim6_Gauge_Gauge_Gauge_5 of int
  | Aux_DScalar_DScalar of int | Aux_Vector_DScalar of int
  | Dim5_Scalar_Gauge2 of int (* 1/2 φ F1,μν F2μν = -1/2 φ (i∂[μ V1,ν]) (i∂[μ V2ν]) *)
  | Dim5_Scalar_Gauge2_Skew of int
    (* 1/2 φ F1,μν F̃2μν = -φ (i∂μ V1,ν) (i∂ρ V2,σ) εμνρσ *)
  | Dim5_Scalar_Vector_Vector_T of int (* φ (i∂μ V1ν) (i∂ν V2μ) *)
  | Dim5_Scalar_Vector_Vector_TU of int (* (i∂ν φ) (i∂μ V1ν) V2μ *)
  | Dim5_Scalar_Vector_Vector_U of int (* (i∂ν φ) (i∂μ V2ν) V1μ *)

```

¹An additional benefit is that the counting of Feynman diagrams is not upset by a splitting of the vectorial and axial pieces of gauge bosons.

```

| Dim6_Vector_Vector_Vector_T of int (* V1μ((i∂νV2ρ)i $\overleftrightarrow{\partial}_\mu$ (i∂ρV3ν)) *)
| Tensor_2_Vector_Vector of int (* Tμν(V1,μV2,ν + V1,νV2,μ) *)
| Tensor_2_Vector_Vector_1 of int (* Tμν(V1,μV2,ν + V1,νV2,μ - gμ,νV1ρV2,ρ)
*)
| Dim5_Tensor_2_Vector_Vector_1 of int (* Tαβ(V1μi $\overleftrightarrow{\partial}_\alpha$ i $\overleftrightarrow{\partial}_\beta$ V2,μ *)
| Dim5_Tensor_2_Vector_Vector_2 of int
  (* Tαβ(V1μi $\overleftrightarrow{\partial}_\beta$ (i∂μV2,α) + V1μi $\overleftrightarrow{\partial}_\alpha$ (i∂μV2,β)) *)
| Dim7_Tensor_2_Vector_Vector_T of int (* Tαβ((i∂μV1ν)i $\overleftrightarrow{\partial}_\alpha$ i $\overleftrightarrow{\partial}_\beta$ (i∂νV2,μ))
*)

```

As long as we stick to renormalizable couplings, there are only three types of quartic couplings: *Scalar4*, *Scalar2_Vector2* and *Vector4*. However, there are three inequivalent contractions for the latter and the general vertex will be a linear combination with integer coefficients:

$$\text{Scalar4 } 1 : \quad \phi_1 \phi_2 \phi_3 \phi_4 \quad (9.2a)$$

$$\text{Scalar2_Vector2 } 1 : \quad \phi_1 \phi_2 V_3^\mu V_{4,\mu} \quad (9.2b)$$

$$\text{Vector4 } [1, C_12_34] : \quad V_1^\mu V_{2,\mu} V_3^\nu V_{4,\nu} \quad (9.2c)$$

$$\text{Vector4 } [1, C_13_42] : \quad V_1^\mu V_2^\nu V_{3,\mu} V_{4,\nu} \quad (9.2d)$$

$$\text{Vector4 } [1, C_14_23] : \quad V_1^\mu V_2^\nu V_{3,\nu} V_{4,\mu} \quad (9.2e)$$

`type contract4 = C_12_34 | C_13_42 | C_14_23`

`type α vertex4 =`

```


| Scalar4 of int
| Scalar2_Vector2 of int
| Vector4 of (int × contract4) list
| DScalar4 of (int × contract4) list
| DScalar2_Vector2 of (int × contract4) list
| GBBG of int × fermionbar × boson2 × fermion

```

In some applications, we have to allow for contributions outside of perturbation theory. The most prominent example is heavy gauge boson scattering at very high energies, where the perturbative expression violates unitarity.

One solution is the ‘*K*-matrix’ ansatz. Such unitarizations typically introduce effective propagators and/or vertices that violate crossing symmetry and vanish in the *t*-channel. This can be taken care of in *Fusion* by filtering out vertices that have the wrong momenta.

In this case the ordering of the fields in a vertex of the Feynman rules becomes significant. In particular, we assume that (V_1, V_2, V_3, V_4) implies



The list of pairs of parameters denotes the location and strengths of the poles in the K -matrix ansatz:

$$(c_1, a_1, c_2, a_2, \dots, c_n, a_n) \implies f(s) = \sum_{i=1}^n \frac{c_i}{s - a_i} \quad (9.4)$$

```
| Vector4_K_Matrix_tho of int × (α × α) list
| Vector4_K_Matrix_jr of int × (int × contract4) list
```

type α vertexn = unit

An obvious candidate for addition to *boson* is T , of course.



This list is sufficient for the minimal standard model, but not comprehensive enough for most of its extensions, supersymmetric or otherwise. In particular, we need a *general* parameterization for all trilinear vertices. One straightforward possibility are polynomials in the momenta for each combination of fields.



JR sez' (regarding the Majorana Feynman rules): Here we use the rules which can be found in [7] and are more properly described in *Targets* where the performing of the fusion rules in analytical expressions is encoded. (*JR's probably right, but I need to check myself ...*)

Signify which two of three fields are fused:

```
type fuse2 = F23 | F32 | F31 | F13 | F12 | F21
```

Signify which three of four fields are fused:

```
type fuse3 =
| F123 | F231 | F312 | F132 | F321 | F213
| F124 | F241 | F412 | F142 | F421 | F214
| F134 | F341 | F413 | F143 | F431 | F314
| F234 | F342 | F423 | F243 | F432 | F324
```

Explicit enumeration types make no sense for higher degrees.

```
type fusen = int list
```

The third member of the triplet will contain the coupling constant:

```
type α t =
| V3 of α vertex3 × fuse2 × α
| V4 of α vertex4 × fuse3 × α
| Vn of α vertexn × fusen × α
```

9.1.3 Gauge Couplings

Dimension-4 trilinear vector boson couplings

$$f_{abc} \partial^\mu A^{a,\nu} A_\mu^b A_\nu^c \rightarrow i f_{abc} k_1^\mu A^{a,\nu}(k_1) A_\mu^b(k_2) A_\nu^c(k_3)$$

	only Dirac fermions	incl. Majorana fermions
<i>FBF</i> (<i>Psibar</i> , <i>S</i> , <i>Psi</i>): $\mathcal{L}_I = g_S \bar{\psi}_1 S \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_S \bar{\psi}_1 S$	$\psi_2 \leftarrow i \cdot g_S \psi_1 S$
<i>F21</i>	$\bar{\psi}_2 \leftarrow i \cdot g_S S \bar{\psi}_1$	$\psi_2 \leftarrow i \cdot g_S S \psi_1$
<i>F13</i>	$S \leftarrow i \cdot g_S \bar{\psi}_1 \psi_2$	$S \leftarrow i \cdot g_S \psi_1^T C \psi_2$
<i>F31</i>	$S \leftarrow i \cdot g_S \psi_{2,\alpha} \bar{\psi}_{1,\alpha}$	$S \leftarrow i \cdot g_S \psi_2^T C \psi_1$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_S S \psi_2$	$\psi_1 \leftarrow i \cdot g_S S \psi_2$
<i>F32</i>	$\psi_1 \leftarrow i \cdot g_S \psi_2 S$	$\psi_1 \leftarrow i \cdot g_S \psi_2 S$
<i>FBF</i> (<i>Psibar</i> , <i>P</i> , <i>Psi</i>): $\mathcal{L}_I = g_P \bar{\psi}_1 P \gamma_5 \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_P \bar{\psi}_1 \gamma_5 P$	$\psi_2 \leftarrow i \cdot g_P \gamma_5 \psi_1 P$
<i>F21</i>	$\bar{\psi}_2 \leftarrow i \cdot g_P P \bar{\psi}_1 \gamma_5$	$\psi_2 \leftarrow i \cdot g_P P \gamma_5 \psi_1$
<i>F13</i>	$P \leftarrow i \cdot g_P \bar{\psi}_1 \gamma_5 \psi_2$	$P \leftarrow i \cdot g_P \psi_1^T C \gamma_5 \psi_2$
<i>F31</i>	$P \leftarrow i \cdot g_P [\gamma_5 \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$P \leftarrow i \cdot g_P \psi_2^T C \gamma_5 \psi_1$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_P P \gamma_5 \psi_2$	$\psi_1 \leftarrow i \cdot g_P P \gamma_5 \psi_2$
<i>F32</i>	$\psi_1 \leftarrow i \cdot g_P \gamma_5 \psi_2 P$	$\psi_1 \leftarrow i \cdot g_P \gamma_5 \psi_2 P$
<i>FBF</i> (<i>Psibar</i> , <i>V</i> , <i>Psi</i>): $\mathcal{L}_I = g_V \bar{\psi}_1 \not{V} \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_V \bar{\psi}_1 \not{V}$	$\psi_{2,\alpha} \leftarrow i \cdot (-g_V) \psi_{1,\beta} \not{V}_{\alpha\beta}$
<i>F21</i>	$\bar{\psi}_{2,\beta} \leftarrow i \cdot g_V \not{V}_{\alpha\beta} \bar{\psi}_{1,\alpha}$	$\psi_2 \leftarrow i \cdot (-g_V) \not{V} \psi_1$
<i>F13</i>	$V_\mu \leftarrow i \cdot g_V \bar{\psi}_1 \gamma_\mu \psi_2$	$V_\mu \leftarrow i \cdot g_V (\psi_1)^T C \gamma_\mu \psi_2$
<i>F31</i>	$V_\mu \leftarrow i \cdot g_V [\gamma_\mu \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$V_\mu \leftarrow i \cdot (-g_V) (\psi_2)^T C \gamma_\mu \psi_1$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_V \not{V} \psi_2$	$\psi_1 \leftarrow i \cdot g_V \not{V} \psi_2$
<i>F32</i>	$\psi_{1,\alpha} \leftarrow i \cdot g_V \psi_{2,\beta} \not{V}_{\alpha\beta}$	$\psi_{1,\alpha} \leftarrow i \cdot g_V \psi_{2,\beta} \not{V}_{\alpha\beta}$
<i>FBF</i> (<i>Psibar</i> , <i>A</i> , <i>Psi</i>): $\mathcal{L}_I = g_A \bar{\psi}_1 \gamma_5 \not{A} \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_A \bar{\psi}_1 \gamma_5 \not{A}$	$\psi_{2,\alpha} \leftarrow i \cdot g_A \psi_\beta [\gamma_5 \not{A}]_{\alpha\beta}$
<i>F21</i>	$\bar{\psi}_{2,\beta} \leftarrow i \cdot g_A [\gamma_5 \not{A}]_{\alpha\beta} \bar{\psi}_{1,\alpha}$	$\psi_2 \leftarrow i \cdot g_A \gamma_5 \not{A} \psi_1$
<i>F13</i>	$A_\mu \leftarrow i \cdot g_A \bar{\psi}_1 \gamma_5 \gamma_\mu \psi_2$	$A_\mu \leftarrow i \cdot g_A \psi_1^T C \gamma_5 \gamma_\mu \psi_2$
<i>F31</i>	$A_\mu \leftarrow i \cdot g_A [\gamma_5 \gamma_\mu \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$A_\mu \leftarrow i \cdot g_A \psi_2^T C \gamma_5 \gamma_\mu \psi_1$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_A \gamma_5 \not{A} \psi_2$	$\psi_1 \leftarrow i \cdot g_A \gamma_5 \not{A} \psi_2$
<i>F32</i>	$\psi_{1,\alpha} \leftarrow i \cdot g_A \psi_{2,\beta} [\gamma_5 \not{A}]_{\alpha\beta}$	$\psi_{1,\alpha} \leftarrow i \cdot g_A \psi_{2,\beta} [\gamma_5 \not{A}]_{\alpha\beta}$

Table 9.3: Dimension-4 trilinear fermionic couplings. The momenta are unambiguous, because there are no derivative couplings and all participating fields are different.

	only Dirac fermions	incl. Majorana fermions
<i>FBF</i> (<i>Psibar</i> , <i>T</i> , <i>Psi</i>): $\mathcal{L}_I = g_T T_{\mu\nu} \bar{\psi}_1 [\gamma^\mu, \gamma^\nu] - \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_T \bar{\psi}_1 [\gamma^\mu, \gamma^\nu] - T_{\mu\nu}$	$\bar{\psi}_2 \leftarrow i \cdot g_T \dots$
<i>F21</i>	$\bar{\psi}_2 \leftarrow i \cdot g_T T_{\mu\nu} \bar{\psi}_1 [\gamma^\mu, \gamma^\nu] -$	$\bar{\psi}_2 \leftarrow i \cdot g_T \dots$
<i>F13</i>	$T_{\mu\nu} \leftarrow i \cdot g_T \bar{\psi}_1 [\gamma_\mu, \gamma_\nu] - \psi_2$	$T_{\mu\nu} \leftarrow i \cdot g_T \dots$
<i>F31</i>	$T_{\mu\nu} \leftarrow i \cdot g_T [[\gamma_\mu, \gamma_\nu] - \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$T_{\mu\nu} \leftarrow i \cdot g_T \dots$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_T T_{\mu\nu} [\gamma^\mu, \gamma^\nu] - \psi_2$	$\psi_1 \leftarrow i \cdot g_T \dots$
<i>F32</i>	$\psi_1 \leftarrow i \cdot g_T [\gamma^\mu, \gamma^\nu] - \psi_2 T_{\mu\nu}$	$\psi_1 \leftarrow i \cdot g_T \dots$

Table 9.4: Dimension-5 trilinear fermionic couplings (NB: the coefficients and signs are not fixed yet). The momenta are unambiguous, because there are no derivative couplings and all participating fields are different.

$$= -\frac{i}{3!} f_{a_1 a_2 a_3} C^{\mu_1 \mu_2 \mu_3}(k_1, k_2, k_3) A_{\mu_1}^{a_1}(k_1) A_{\mu_2}^{a_2}(k_2) A_{\mu_3}^{a_3}(k_3) \quad (9.5a)$$

with the totally antisymmetric tensor (under simultaneous permutations of all quantum numbers μ_i and k_i) and all momenta *outgoing*

$$C^{\mu_1 \mu_2 \mu_3}(k_1, k_2, k_3) = (g^{\mu_1 \mu_2}(k_1^{\mu_3} - k_2^{\mu_3}) + g^{\mu_2 \mu_3}(k_2^{\mu_1} - k_3^{\mu_1}) + g^{\mu_3 \mu_1}(k_3^{\mu_2} - k_1^{\mu_2})) \quad (9.5b)$$

Since $f_{a_1 a_2 a_3} C^{\mu_1 \mu_2 \mu_3}(k_1, k_2, k_3)$ is totally symmetric (under simultaneous permutations of all quantum numbers a_i , μ_i and k_i), it is easy to take the partial derivative

$$A^{a,\mu}(k_2 + k_3) = -\frac{i}{2!} f_{abc} C^{\mu\rho\sigma}(-k_2 - k_3, k_2, k_3) A_\rho^b(k_2) A_\sigma^c(k_3) \quad (9.6a)$$

with

$$C^{\mu\rho\sigma}(-k_2 - k_3, k_2, k_3) = (g^{\rho\sigma}(k_2^\mu - k_3^\mu) + g^{\mu\sigma}(2k_3^\rho + k_2^\rho) - g^{\mu\rho}(2k_2^\sigma + k_3^\sigma)) \quad (9.6b)$$

i. e.

$$A^{a,\mu}(k_2 + k_3) = -\frac{i}{2!} f_{abc} ((k_2^\mu - k_3^\mu) A^b(k_2) \cdot A^c(k_3) + (2k_3 + k_2) \cdot A^b(k_2) A^{c,\mu}(k_3) - A^{b,\mu}(k_2) A^c(k_3) \cdot (2k_2 + k_3)) \quad (9.6c)$$



Investigate the rearrangements proposed in [5] for improved numerical stability.

Non-Gauge Vector Couplings

As a basis for the dimension-4 couplings of three vector bosons, we choose “transversal” and “longitudinal” (with respect to the first vector field) tensors that are odd and even under permutation of the second and third argument

$$\mathcal{L}_T(V_1, V_2, V_3) = V_1^\mu (V_{2,\nu} i \overleftrightarrow{\partial}_\mu V_3^\nu) = -\mathcal{L}_T(V_1, V_3, V_2) \quad (9.7a)$$

	only Dirac fermions	incl. Majorana fermions
<i>FBF</i> (<i>Psibar</i> , <i>SP</i> , <i>Psi</i>): $\mathcal{L}_I = \bar{\psi}_1 \phi (g_S + g_P \gamma_5) \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot \bar{\psi}_1 (g_S + g_P \gamma_5) \phi$	$\psi_2 \leftarrow i \dots$
<i>F21</i>	$\bar{\psi}_2 \leftarrow i \cdot \phi \bar{\psi}_1 (g_S + g_P \gamma_5)$	$\psi_2 \leftarrow i \dots$
<i>F13</i>	$\phi \leftarrow i \cdot \bar{\psi}_1 (g_S + g_P \gamma_5) \psi_2$	$\phi \leftarrow i \dots$
<i>F31</i>	$\phi \leftarrow i \cdot [(g_S + g_P \gamma_5) \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$\phi \leftarrow i \dots$
<i>F23</i>	$\psi_1 \leftarrow i \cdot \phi (g_S + g_P \gamma_5) \psi_2$	$\psi_1 \leftarrow i \dots$
<i>F32</i>	$\psi_1 \leftarrow i \cdot (g_S + g_P \gamma_5) \psi_2 \phi$	$\psi_1 \leftarrow i \dots$
<i>FBF</i> (<i>Psibar</i> , <i>SL</i> , <i>Psi</i>): $\mathcal{L}_I = g_L \bar{\psi}_1 \phi (1 - \gamma_5) \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_L \bar{\psi}_1 (1 - \gamma_5) \phi$	$\psi_2 \leftarrow i \dots$
<i>F21</i>	$\bar{\psi}_2 \leftarrow i \cdot g_L \phi \bar{\psi}_1 (1 - \gamma_5)$	$\psi_2 \leftarrow i \dots$
<i>F13</i>	$\phi \leftarrow i \cdot g_L \bar{\psi}_1 (1 - \gamma_5) \psi_2$	$\phi \leftarrow i \dots$
<i>F31</i>	$\phi \leftarrow i \cdot g_L [(1 - \gamma_5) \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$\phi \leftarrow i \dots$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_L \phi (1 - \gamma_5) \psi_2$	$\psi_1 \leftarrow i \dots$
<i>F32</i>	$\psi_1 \leftarrow i \cdot g_L (1 - \gamma_5) \psi_2 \phi$	$\psi_1 \leftarrow i \dots$
<i>FBF</i> (<i>Psibar</i> , <i>SR</i> , <i>Psi</i>): $\mathcal{L}_I = g_R \bar{\psi}_1 \phi (1 + \gamma_5) \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_R \bar{\psi}_1 (1 + \gamma_5) \phi$	$\psi_2 \leftarrow i \dots$
<i>F21</i>	$\bar{\psi}_2 \leftarrow i \cdot g_R \phi \bar{\psi}_1 (1 + \gamma_5)$	$\psi_2 \leftarrow i \dots$
<i>F13</i>	$\phi \leftarrow i \cdot g_R \bar{\psi}_1 (1 + \gamma_5) \psi_2$	$\phi \leftarrow i \dots$
<i>F31</i>	$\phi \leftarrow i \cdot g_R [(1 + \gamma_5) \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$\phi \leftarrow i \dots$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_R \phi (1 + \gamma_5) \psi_2$	$\psi_1 \leftarrow i \dots$
<i>F32</i>	$\psi_1 \leftarrow i \cdot g_R (1 + \gamma_5) \psi_2 \phi$	$\psi_1 \leftarrow i \dots$
<i>FBF</i> (<i>Psibar</i> , <i>SLR</i> , <i>Psi</i>): $\mathcal{L}_I = g_L \bar{\psi}_1 \phi (1 - \gamma_5) \psi_2 + g_R \bar{\psi}_1 \phi (1 + \gamma_5) \psi_2$		

Table 9.5: Combined dimension-4 trilinear fermionic couplings.

	only Dirac fermions	incl. Majorana fermions
<i>FBF</i> (<i>Psibar</i> , <i>VA</i> , <i>Psi</i>): $\mathcal{L}_I = \bar{\psi}_1 \not{Z} (g_V - g_A \gamma_5) \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot \bar{\psi}_1 \not{Z} (g_V - g_A \gamma_5)$	$\psi_2 \leftarrow i \dots$
<i>F21</i>	$\bar{\psi}_{2,\beta} \leftarrow i \cdot [\not{Z} (g_V - g_A \gamma_5)]_{\alpha\beta} \bar{\psi}_{1,\alpha}$	$\psi_2 \leftarrow i \dots$
<i>F13</i>	$Z_\mu \leftarrow i \cdot \bar{\psi}_1 \gamma_\mu (g_V - g_A \gamma_5) \psi_2$	$Z_\mu \leftarrow i \dots$
<i>F31</i>	$Z_\mu \leftarrow i \cdot [\gamma_\mu (g_V - g_A \gamma_5) \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$Z_\mu \leftarrow i \dots$
<i>F23</i>	$\psi_1 \leftarrow i \cdot \not{Z} (g_V - g_A \gamma_5) \psi_2$	$\psi_1 \leftarrow i \dots$
<i>F32</i>	$\psi_{1,\alpha} \leftarrow i \cdot \psi_{2,\beta} [\not{Z} (g_V - g_A \gamma_5)]_{\alpha\beta}$	$\psi_1 \leftarrow i \dots$
<i>FBF</i> (<i>Psibar</i> , <i>VL</i> , <i>Psi</i>): $\mathcal{L}_I = g_L \bar{\psi}_1 \not{Z} (1 - \gamma_5) \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_L \bar{\psi}_1 \not{Z} (1 - \gamma_5)$	$\psi_2 \leftarrow i \dots$
<i>F21</i>	$\bar{\psi}_{2,\beta} \leftarrow i \cdot g_L [\not{Z} (1 - \gamma_5)]_{\alpha\beta} \bar{\psi}_{1,\alpha}$	$\psi_2 \leftarrow i \dots$
<i>F13</i>	$Z_\mu \leftarrow i \cdot g_L \bar{\psi}_1 \gamma_\mu (1 - \gamma_5) \psi_2$	$Z_\mu \leftarrow i \dots$
<i>F31</i>	$Z_\mu \leftarrow i \cdot g_L [\gamma_\mu (1 - \gamma_5) \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$Z_\mu \leftarrow i \dots$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_L \not{Z} (1 - \gamma_5) \psi_2$	$\psi_1 \leftarrow i \dots$
<i>F32</i>	$\psi_{1,\alpha} \leftarrow i \cdot g_L \psi_{2,\beta} [\not{Z} (1 - \gamma_5)]_{\alpha\beta}$	$\psi_1 \leftarrow i \dots$
<i>FBF</i> (<i>Psibar</i> , <i>VR</i> , <i>Psi</i>): $\mathcal{L}_I = g_R \bar{\psi}_1 \not{Z} (1 + \gamma_5) \psi_2$		
<i>F12</i>	$\bar{\psi}_2 \leftarrow i \cdot g_R \bar{\psi}_1 \not{Z} (1 + \gamma_5)$	$\psi_2 \leftarrow i \dots$
<i>F21</i>	$\bar{\psi}_{2,\beta} \leftarrow i \cdot g_R [\not{Z} (1 + \gamma_5)]_{\alpha\beta} \bar{\psi}_{1,\alpha}$	$\psi_2 \leftarrow i \dots$
<i>F13</i>	$Z_\mu \leftarrow i \cdot g_R \bar{\psi}_1 \gamma_\mu (1 + \gamma_5) \psi_2$	$Z_\mu \leftarrow i \dots$
<i>F31</i>	$Z_\mu \leftarrow i \cdot g_R [\gamma_\mu (1 + \gamma_5) \psi_2]_\alpha \bar{\psi}_{1,\alpha}$	$Z_\mu \leftarrow i \dots$
<i>F23</i>	$\psi_1 \leftarrow i \cdot g_R \not{Z} (1 + \gamma_5) \psi_2$	$\psi_1 \leftarrow i \dots$
<i>F32</i>	$\psi_{1,\alpha} \leftarrow i \cdot g_R \psi_{2,\beta} [\not{Z} (1 + \gamma_5)]_{\alpha\beta}$	$\psi_1 \leftarrow i \dots$
<i>FBF</i> (<i>Psibar</i> , <i>VLR</i> , <i>Psi</i>): $\mathcal{L}_I = g_L \bar{\psi}_1 \not{Z} (1 - \gamma_5) \psi_2 + g_R \bar{\psi}_1 \not{Z} (1 + \gamma_5) \psi_2$		

Table 9.6: Combined dimension-4 trilinear fermionic couplings continued.

<i>FBF</i> (<i>Psibar</i> , <i>S</i> , <i>Chi</i>): $\bar{\psi}S\chi$	
<i>F12</i> : $\chi \leftarrow \psi S$	<i>F21</i> : $\chi \leftarrow S\psi$
<i>F13</i> : $S \leftarrow \psi^T C\chi$	<i>F31</i> : $S \leftarrow \chi^T C\psi$
<i>F23</i> : $\psi \leftarrow S\chi$	<i>F32</i> : $\psi \leftarrow \chi S$
<i>FBF</i> (<i>Psibar</i> , <i>P</i> , <i>Chi</i>): $\bar{\psi}P\gamma_5\chi$	
<i>F12</i> : $\chi \leftarrow \gamma_5\psi P$	<i>F21</i> : $\chi \leftarrow P\gamma_5\psi$
<i>F13</i> : $P \leftarrow \psi^T C\gamma_5\chi$	<i>F31</i> : $P \leftarrow \chi^T C\gamma_5\psi$
<i>F23</i> : $\psi \leftarrow P\gamma_5\chi$	<i>F32</i> : $\psi \leftarrow \gamma_5\chi P$
<i>FBF</i> (<i>Psibar</i> , <i>V</i> , <i>Chi</i>): $\bar{\psi}\not{V}\chi$	
<i>F12</i> : $\chi_\alpha \leftarrow -\psi_\beta \not{V}_{\alpha\beta}$	<i>F21</i> : $\chi \leftarrow -\not{V}\psi$
<i>F13</i> : $V_\mu \leftarrow \psi^T C\gamma_\mu\chi$	<i>F31</i> : $V_\mu \leftarrow \chi^T C(-\gamma_\mu\psi)$
<i>F23</i> : $\psi \leftarrow \not{V}\chi$	<i>F32</i> : $\psi_\alpha \leftarrow \chi_\beta \not{V}_{\alpha\beta}$
<i>FBF</i> (<i>Psibar</i> , <i>A</i> , <i>Chi</i>): $\bar{\psi}\gamma^5\not{A}\chi$	
<i>F12</i> : $\chi_\alpha \leftarrow \psi_\beta [\gamma^5\not{A}]_{\alpha\beta}$	<i>F21</i> : $\chi \leftarrow \gamma^5\not{A}\psi$
<i>F13</i> : $A_\mu \leftarrow \psi^T C\gamma^5\gamma_\mu\chi$	<i>F31</i> : $A_\mu \leftarrow \chi^T C(\gamma^5\gamma_\mu\psi)$
<i>F23</i> : $\psi \leftarrow \gamma^5\not{A}\chi$	<i>F32</i> : $\psi_\alpha \leftarrow \chi_\beta [\gamma^5\not{A}]_{\alpha\beta}$

Table 9.7: Dimension-4 trilinear couplings including one Dirac and one Majorana fermion

<i>FBF</i> (<i>Psibar</i> , <i>SP</i> , <i>Chi</i>): $\bar{\psi}\phi(g_S + g_P\gamma_5)\chi$	
<i>F12</i> : $\chi \leftarrow (g_S + g_P\gamma_5)\psi\phi$	<i>F21</i> : $\chi \leftarrow \phi(g_S + g_P\gamma_5)\psi$
<i>F13</i> : $\phi \leftarrow \psi^T C(g_S + g_P\gamma_5)\chi$	<i>F31</i> : $\phi \leftarrow \chi^T C(g_S + g_P\gamma_5)\chi$
<i>F23</i> : $\psi \leftarrow \phi(g_S + g_P\gamma_5)\chi$	<i>F32</i> : $\psi \leftarrow (g_S + g_P\gamma_5)\chi\phi$
<i>FBF</i> (<i>Psibar</i> , <i>VA</i> , <i>Chi</i>): $\bar{\psi}\not{Z}(g_V - g_A\gamma_5)\chi$	
<i>F12</i> : $\chi_\alpha \leftarrow \psi_\beta [\not{Z}(-g_V - g_A\gamma_5)]_{\alpha\beta}$	<i>F21</i> : $\chi \leftarrow \not{Z}(-g_V - g_A\gamma_5)\psi$
<i>F13</i> : $Z_\mu \leftarrow \psi^T C\gamma_\mu(g_V - g_A\gamma_5)\chi$	<i>F31</i> : $Z_\mu \leftarrow \chi^T C\gamma_\mu(-g_V - g_A\gamma_5)\psi$
<i>F23</i> : $\psi \leftarrow \not{Z}(g_V - g_A\gamma_5)\chi$	<i>F32</i> : $\psi_\alpha \leftarrow \chi_\beta [\not{Z}(g_V - g_A\gamma_5)]_{\alpha\beta}$

Table 9.8: Combined dimension-4 trilinear fermionic couplings including one Dirac and one Majorana fermion.

<i>FBF (Chibar, S, Psi):</i> $\bar{\chi}S\psi$	
<i>F12:</i> $\psi \leftarrow \chi S$	<i>F21:</i> $\psi \leftarrow S\chi$
<i>F13:</i> $S \leftarrow \chi^T C\psi$	<i>F31:</i> $S \leftarrow \psi^T C\chi$
<i>F23:</i> $\chi \leftarrow S\psi$	<i>F32:</i> $\chi \leftarrow \psi S$
<i>FBF (Chibar, P, Psi):</i> $\bar{\chi}P\gamma_5\psi$	
<i>F12:</i> $\psi \leftarrow \gamma_5\chi P$	<i>F21:</i> $\psi \leftarrow P\gamma_5\chi$
<i>F13:</i> $P \leftarrow \chi^T C\gamma_5\psi$	<i>F31:</i> $P \leftarrow \psi^T C\gamma_5\chi$
<i>F23:</i> $\chi \leftarrow P\gamma_5\psi$	<i>F32:</i> $\chi \leftarrow \gamma_5\psi P$
<i>FBF (Chibar, V, Psi):</i> $\bar{\chi}\not{V}\psi$	
<i>F12:</i> $\psi_\alpha \leftarrow -\chi_\beta \not{V}_{\alpha\beta}$	<i>F21:</i> $\psi \leftarrow -\not{V}\chi$
<i>F13:</i> $V_\mu \leftarrow \chi^T C\gamma_\mu\psi$	<i>F31:</i> $V_\mu \leftarrow \psi^T C(-\gamma_\mu\chi)$
<i>F23:</i> $\chi \leftarrow \not{V}\psi$	<i>F32:</i> $\chi_\alpha \leftarrow \psi_\beta \not{V}_{\alpha\beta}$
<i>FBF (Chibar, A, Psi):</i> $\bar{\chi}\gamma^5\not{A}\psi$	
<i>F12:</i> $\psi_\alpha \leftarrow \chi_\beta [\gamma^5\not{A}]_{\alpha\beta}$	<i>F21:</i> $\psi \leftarrow \gamma^5\not{A}\chi$
<i>F13:</i> $A_\mu \leftarrow \chi^T C(\gamma^5\gamma_\mu\psi)$	<i>F31:</i> $A_\mu \leftarrow \psi^T C\gamma^5\gamma_\mu\chi$
<i>F23:</i> $\chi \leftarrow \gamma^5\not{A}\psi$	<i>F32:</i> $\chi_\alpha \leftarrow \psi_\beta [\gamma^5\not{A}]_{\alpha\beta}$

Table 9.9: Dimension-4 trilinear couplings including one Dirac and one Majorana fermion

<i>FBF (Chibar, SP, Psi):</i> $\bar{\chi}\phi(g_S + g_P\gamma_5)\psi$	
<i>F12:</i> $\psi \leftarrow (g_S + g_P\gamma_5)\chi\phi$	<i>F21:</i> $\psi \leftarrow \phi(g_S + g_P\gamma_5)\chi$
<i>F13:</i> $\phi \leftarrow \chi^T C(g_S + g_P\gamma_5)\psi$	<i>F31:</i> $\phi \leftarrow \psi^T C(g_S + g_P\gamma_5)\chi$
<i>F23:</i> $\chi \leftarrow \phi(g_S + g_P\gamma_5)\psi$	<i>F32:</i> $\chi \leftarrow (g_S + g_P\gamma_5)\psi\phi$
<i>FBF (Chibar, VA, Psi):</i> $\bar{\chi}\not{Z}(g_V - g_A\gamma_5)\psi$	
<i>F12:</i> $\psi_\alpha \leftarrow \chi_\beta [\not{Z}(-g_V - g_A\gamma_5)]_{\alpha\beta}$	<i>F21:</i> $\psi \leftarrow \not{Z}(-g_V - g_A\gamma_5)\chi$
<i>F13:</i> $Z_\mu \leftarrow \chi^T C\gamma_\mu(g_V - g_A\gamma_5)\psi$	<i>F31:</i> $Z_\mu \leftarrow \psi^T C\gamma_\mu(-g_V - g_A\gamma_5)\chi$
<i>F23:</i> $\chi \leftarrow \not{Z}(g_V - g_A\gamma_5)\psi$	<i>F32:</i> $\chi_\alpha \leftarrow \psi_\beta [\not{Z}(g_V - g_A\gamma_5)]_{\alpha\beta}$

Table 9.10: Combined dimension-4 trilinear fermionic couplings including one Dirac and one Majorana fermion.

<i>FBF (Chibar, S, Chi):</i> $\bar{\chi}_a S \chi_b$	
<i>F12:</i> $\chi_b \leftarrow \chi_a S$	<i>F21:</i> $\chi_b \leftarrow S \chi_a$
<i>F13:</i> $S \leftarrow \chi_a^T C \chi_b$	<i>F31:</i> $S \leftarrow \chi_b^T C \chi_a$
<i>F23:</i> $\chi_a \leftarrow S \chi_b$	<i>F32:</i> $\chi_a \leftarrow \chi S_b$
<i>FBF (Chibar, P, Chi):</i> $\bar{\chi}_a P \gamma_5 \psi_b$	
<i>F12:</i> $\chi_b \leftarrow \gamma_5 \chi_a P$	<i>F21:</i> $\chi_b \leftarrow P \gamma_5 \chi_a$
<i>F13:</i> $P \leftarrow \chi_a^T C \gamma_5 \chi_b$	<i>F31:</i> $P \leftarrow \chi_b^T C \gamma_5 \chi_a$
<i>F23:</i> $\chi_a \leftarrow P \gamma_5 \chi_b$	<i>F32:</i> $\chi_a \leftarrow \gamma_5 \chi_b P$
<i>FBF (Chibar, V, Chi):</i> $\bar{\chi}_a \not{V} \chi_b$	
<i>F12:</i> $\chi_{b,\alpha} \leftarrow -\chi_{a,\beta} \not{V}_{\alpha\beta}$	<i>F21:</i> $\chi_b \leftarrow -\not{V} \chi_a$
<i>F13:</i> $V_\mu \leftarrow \chi_a^T C \gamma_\mu \chi_b$	<i>F31:</i> $V_\mu \leftarrow -\chi_b^T C \gamma_\mu \chi_a$
<i>F23:</i> $\chi_a \leftarrow \not{V} \chi_b$	<i>F32:</i> $\chi_{a,\alpha} \leftarrow \chi_{b,\beta} \not{V}_{\alpha\beta}$
<i>FBF (Chibar, A, Chi):</i> $\bar{\chi}_a \gamma^5 \not{A} \chi_b$	
<i>F12:</i> $\chi_{b,\alpha} \leftarrow \chi_{a,\beta} [\gamma^5 \not{A}]_{\alpha\beta}$	<i>F21:</i> $\chi_b \leftarrow \gamma^5 \not{A} \chi_a$
<i>F13:</i> $A_\mu \leftarrow \chi_a^T C \gamma^5 \gamma_\mu \chi_b$	<i>F31:</i> $A_\mu \leftarrow \chi_b^T C (\gamma^5 \gamma_\mu \chi_a)$
<i>F23:</i> $\chi_a \leftarrow \gamma^5 \not{A} \chi_b$	<i>F32:</i> $\chi_{a,\alpha} \leftarrow \chi_{b,\beta} [\gamma^5 \not{A}]_{\alpha\beta}$

Table 9.11: Dimension-4 trilinear couplings of two Majorana fermions

<i>FBF (Chibar, SP, Chi):</i> $\bar{\chi} \phi_a (g_S + g_P \gamma_5) \chi_b$	
<i>F12:</i> $\chi_b \leftarrow (g_S + g_P \gamma_5) \chi_a \phi$	<i>F21:</i> $\chi_b \leftarrow \phi (g_S + g_P \gamma_5) \chi_a$
<i>F13:</i> $\phi \leftarrow \chi_a^T C (g_S + g_P \gamma_5) \chi_b$	<i>F31:</i> $\phi \leftarrow \chi_b^T C (g_S + g_P \gamma_5) \chi_a$
<i>F23:</i> $\chi_a \leftarrow \phi (g_S + g_P \gamma_5) \chi_b$	<i>F32:</i> $\chi_a \leftarrow (g_S + g_P \gamma_5) \chi_b \phi$
<i>FBF (Chibar, VA, Chi):</i> $\bar{\chi}_a \not{Z} (g_V - g_A \gamma_5) \chi_b$	
<i>F12:</i> $\chi_{b,\alpha} \leftarrow \chi_{a,\beta} [\not{Z} (-g_V - g_A \gamma_5)]_{\alpha\beta}$	<i>F21:</i> $\chi_b \leftarrow \not{Z} (-g_V - g_A \gamma_5) \chi_a$
<i>F13:</i> $Z_\mu \leftarrow \chi_a^T C \gamma_\mu (g_V - g_A \gamma_5) \chi_b$	<i>F31:</i> $Z_\mu \leftarrow \chi_b^T C \gamma_\mu (-g_V - g_A \gamma_5) \chi_a$
<i>F23:</i> $\chi_a \leftarrow \not{Z} (g_V - g_A \gamma_5) \chi_b$	<i>F32:</i> $\chi_{a,\alpha} \leftarrow \chi_{b,\beta} [\not{Z} (g_V - g_A \gamma_5)]_{\alpha\beta}$

Table 9.12: Combined dimension-4 trilinear fermionic couplings of two Majorana fermions.

<i>Gauge_Gauge_Gauge</i> : $\mathcal{L}_I = gf_{abc}A_a^\mu A_b^\nu \partial_\mu A_{c,\nu}$
$\therefore A_a^\mu \leftarrow i \cdot (-ig/2) \cdot C_{abc}^{\mu\rho\sigma}(-k_2 - k_3, k_2, k_3) A_\rho^b A_\sigma^c$
<i>Aux_Gauge_Gauge</i> : $\mathcal{L}_I = gf_{abc}X_{a,\mu\nu}(k_1)(A_b^\mu(k_2)A_c^\nu(k_3) - A_b^\nu(k_2)A_c^\mu(k_3))$
<i>F23</i> \vee <i>F32</i> : $X_a^{\mu\nu}(k_2 + k_3) \leftarrow i \cdot gf_{abc}(A_b^\mu(k_2)A_c^\nu(k_3) - A_b^\nu(k_2)A_c^\mu(k_3))$
<i>F12</i> \vee <i>F13</i> : $A_{a,\mu}(k_1 + k_{2/3}) \leftarrow i \cdot gf_{abc}X_{b,\nu\mu}(k_1)A_c^\nu(k_{2/3})$
<i>F21</i> \vee <i>F31</i> : $A_{a,\mu}(k_{2/3} + k_1) \leftarrow i \cdot gf_{abc}A_b^\nu(k_{2/3})X_{c,\mu\nu}(k_1)$

Table 9.13: Dimension-4 Vector Boson couplings with *outgoing* momenta. See (11.1b) and (9.6b) for the definition of the antisymmetric tensor $C^{\mu_1\mu_2\mu_3}(k_1, k_2, k_3)$.

<i>Scalar_Vector_Vector</i> : $\mathcal{L}_I = g\phi V_1^\mu V_{2,\mu}$	
<i>F13</i> : $\leftarrow i \cdot g \cdots$	<i>F31</i> : $\leftarrow i \cdot g \cdots$
<i>F12</i> : $\leftarrow i \cdot g \cdots$	<i>F21</i> : $\leftarrow i \cdot g \cdots$
<i>F23</i> : $\phi \leftarrow i \cdot g V_1^\mu V_{2,\mu}$	<i>F32</i> : $\phi \leftarrow i \cdot g V_{2,\mu} V_1^\mu$
<i>Aux_Vector_Vector</i> : $\mathcal{L}_I = gX V_1^\mu V_{2,\mu}$	
<i>F13</i> : $\leftarrow i \cdot g \cdots$	<i>F31</i> : $\leftarrow i \cdot g \cdots$
<i>F12</i> : $\leftarrow i \cdot g \cdots$	<i>F21</i> : $\leftarrow i \cdot g \cdots$
<i>F23</i> : $X \leftarrow i \cdot g V_1^\mu V_{2,\mu}$	<i>F32</i> : $X \leftarrow i \cdot g V_{2,\mu} V_1^\mu$
<i>Aux_Scalar_Vector</i> : $\mathcal{L}_I = gX^\mu \phi V_\mu$	
<i>F13</i> : $\leftarrow i \cdot g \cdots$	<i>F31</i> : $\leftarrow i \cdot g \cdots$
<i>F12</i> : $\leftarrow i \cdot g \cdots$	<i>F21</i> : $\leftarrow i \cdot g \cdots$
<i>F23</i> : $\leftarrow i \cdot g \cdots$	<i>F32</i> : $\leftarrow i \cdot g \cdots$

Table 9.14: ...

<i>Scalar_Scalar_Scalar</i> : $\mathcal{L}_I = g\phi_1\phi_2\phi_3$	
<i>F13</i> : $\phi_2 \leftarrow i \cdot g\phi_1\phi_3$	<i>F31</i> : $\phi_2 \leftarrow i \cdot g\phi_3\phi_1$
<i>F12</i> : $\phi_3 \leftarrow i \cdot g\phi_1\phi_2$	<i>F21</i> : $\phi_3 \leftarrow i \cdot g\phi_2\phi_1$
<i>F23</i> : $\phi_1 \leftarrow i \cdot g\phi_2\phi_3$	<i>F32</i> : $\phi_1 \leftarrow i \cdot g\phi_3\phi_2$
<i>Aux_Scalar_Scalar</i> : $\mathcal{L}_I = gX\phi_1\phi_2$	
<i>F13</i> : $\leftarrow i \cdot g \cdots$	<i>F31</i> : $\leftarrow i \cdot g \cdots$
<i>F12</i> : $\leftarrow i \cdot g \cdots$	<i>F21</i> : $\leftarrow i \cdot g \cdots$
<i>F23</i> : $X \leftarrow i \cdot g\phi_1\phi_2$	<i>F32</i> : $X \leftarrow i \cdot g\phi_2\phi_1$

Table 9.15: ...

<i>Vector_Scalar_Scalar</i> : $\mathcal{L}_I = gV^\mu\phi_1\overset{\leftrightarrow}{\partial}_\mu\phi_2$	
<i>F23</i> :	$V^\mu(k_2 + k_3) \leftarrow i \cdot g(k_2^\mu - k_3^\mu)\phi_1(k_2)\phi_2(k_3)$
<i>F32</i> :	$V^\mu(k_2 + k_3) \leftarrow i \cdot g(k_2^\mu - k_3^\mu)\phi_2(k_3)\phi_1(k_2)$
<i>F12</i> :	$\phi_2(k_1 + k_2) \leftarrow i \cdot g(k_1^\mu + 2k_2^\mu)V_\mu(k_1)\phi_1(k_2)$
<i>F21</i> :	$\phi_2(k_1 + k_2) \leftarrow i \cdot g(k_1^\mu + 2k_2^\mu)\phi_1(k_2)V_\mu(k_1)$
<i>F13</i> :	$\phi_1(k_1 + k_3) \leftarrow i \cdot g(-k_1^\mu - 2k_3^\mu)V_\mu(k_1)\phi_2(k_3)$
<i>F31</i> :	$\phi_1(k_1 + k_3) \leftarrow i \cdot g(-k_1^\mu - 2k_3^\mu)\phi_2(k_3)V_\mu(k_1)$

Table 9.16: ...

<i>Aux_DScalar_DScalar</i> : $\mathcal{L}_I = g\chi(i\partial_\mu\phi_1)(i\partial^\mu\phi_2)$	
<i>F23</i> :	$\chi(k_2 + k_3) \leftarrow i \cdot g(k_2 \cdot k_3)\phi_1(k_2)\phi_2(k_3)$
<i>F32</i> :	$\chi(k_2 + k_3) \leftarrow i \cdot g(k_3 \cdot k_2)\phi_2(k_3)\phi_1(k_2)$
<i>F12</i> :	$\phi_2(k_1 + k_2) \leftarrow i \cdot g((-k_1 - k_2) \cdot k_2)\chi(k_1)\phi_1(k_2)$
<i>F21</i> :	$\phi_2(k_1 + k_2) \leftarrow i \cdot g(k_2 \cdot (-k_1 - k_2))\phi_1(k_2)\chi(k_1)$
<i>F13</i> :	$\phi_1(k_1 + k_3) \leftarrow i \cdot g((-k_1 - k_3) \cdot k_3)\chi(k_1)\phi_2(k_3)$
<i>F31</i> :	$\phi_1(k_1 + k_3) \leftarrow i \cdot g(k_3 \cdot (-k_1 - k_3))\phi_2(k_3)\chi(k_1)$

Table 9.17: ...

<i>Aux_Vector_DScalar</i> : $\mathcal{L}_I = g\chi V_\mu(i\partial^\mu\phi)$	
<i>F23</i> :	$\chi(k_2 + k_3) \leftarrow i \cdot gk_3^\mu V_\mu(k_2)\phi(k_3)$
<i>F32</i> :	$\chi(k_2 + k_3) \leftarrow i \cdot g\phi(k_3)k_3^\mu V_\mu(k_2)$
<i>F12</i> :	$\phi(k_1 + k_2) \leftarrow i \cdot g\chi(k_1)(-k_1 - k_2)^\mu V_\mu(k_2)$
<i>F21</i> :	$\phi(k_1 + k_2) \leftarrow i \cdot g(-k_1 - k_2)^\mu V_\mu(k_2)\chi(k_1)$
<i>F13</i> :	$V_\mu(k_1 + k_3) \leftarrow i \cdot g(-k_1 - k_3)_\mu\chi(k_1)\phi(k_3)$
<i>F31</i> :	$V_\mu(k_1 + k_3) \leftarrow i \cdot g(-k_1 - k_3)_\mu\phi(k_3)\chi(k_1)$

Table 9.18: ...

$$\mathcal{L}_L(V_1, V_2, V_3) = (i\partial_\mu V_1^\mu) V_{2,\nu} V_3^\nu = \mathcal{L}_L(V_1, V_3, V_2) \quad (9.7b)$$

Using partial integration in \mathcal{L}_L , we find the convenient combinations

$$\mathcal{L}_T(V_1, V_2, V_3) + \mathcal{L}_L(V_1, V_2, V_3) = -2V_1^\mu i\partial_\mu V_{2,\nu} V_3^\nu \quad (9.8a)$$

$$\mathcal{L}_T(V_1, V_2, V_3) - \mathcal{L}_L(V_1, V_2, V_3) = 2V_1^\mu V_{2,\nu} i\partial_\mu V_3^\nu \quad (9.8b)$$

As an important example, we can rewrite the dimension-4 “anomalous” triple gauge couplings

$$\begin{aligned} i\mathcal{L}_{\text{TGC}}(g_1, \kappa, g_4)/g_{VWW} &= g_1 V^\mu (W_{\mu\nu}^- W^{+,\nu} - W_{\mu\nu}^+ W^{-,\nu}) \\ &\quad + \kappa W_\mu^+ W_\nu^- V^{\mu\nu} + g_4 W_\mu^+ W_\nu^- (\partial^\mu V^\nu + \partial^\nu V^\mu) \end{aligned} \quad (9.9)$$

as

$$\begin{aligned} \mathcal{L}_{\text{TGC}}(g_1, \kappa, g_4) &= g_1 \mathcal{L}_T(V, W^-, W^+) \\ &\quad - \frac{\kappa + g_1 - g_4}{2} \mathcal{L}_T(W^-, V, W^+) + \frac{\kappa + g_1 + g_4}{2} \mathcal{L}_T(W^+, V, W^-) \\ &\quad - \frac{\kappa - g_1 - g_4}{2} \mathcal{L}_L(W^-, V, W^+) + \frac{\kappa - g_1 + g_4}{2} \mathcal{L}_L(W^+, V, W^-) \end{aligned} \quad (9.10)$$

CP Violation

$$\mathcal{L}_{\tilde{T}}(V_1, V_2, V_3) = V_{1,\mu} (V_{2,\rho} i\overleftrightarrow{\partial}_\nu V_{3,\sigma}) \epsilon^{\mu\nu\rho\sigma} = +\mathcal{L}_T(V_1, V_3, V_2) \quad (9.11a)$$

$$\mathcal{L}_{\tilde{L}}(V_1, V_2, V_3) = (i\partial_\mu V_{1,\nu}) V_{2,\rho} V_{3,\sigma} \epsilon^{\mu\nu\rho\sigma} = -\mathcal{L}_L(V_1, V_3, V_2) \quad (9.11b)$$

Here the notations \tilde{T} and \tilde{L} are clearly *abuse de langage*, because $\mathcal{L}_{\tilde{L}}(V_1, V_2, V_3)$ is actually the transversal combination, due to the antisymmetry of ϵ . Using partial integration in $\mathcal{L}_{\tilde{L}}$, we could again find combinations

$$\mathcal{L}_{\tilde{T}}(V_1, V_2, V_3) + \mathcal{L}_{\tilde{L}}(V_1, V_2, V_3) = -2V_{1,\mu} V_{2,\nu} i\partial_\rho V_{3,\sigma} \epsilon^{\mu\nu\rho\sigma} \quad (9.12a)$$

$$\mathcal{L}_{\tilde{T}}(V_1, V_2, V_3) - \mathcal{L}_{\tilde{L}}(V_1, V_2, V_3) = -2V_{1,\mu} i\partial_\nu V_{2,\rho} V_{3,\sigma} \epsilon^{\mu\nu\rho\sigma} \quad (9.12b)$$

but we don’t need them, since

$$\begin{aligned} i\mathcal{L}_{\text{TGC}}(g_5, \tilde{\kappa})/g_{VWW} &= g_5 \epsilon_{\mu\nu\rho\sigma} (W^{+,\mu} i\overleftrightarrow{\partial}^\nu W^{-,\nu}) V^\sigma \\ &\quad - \frac{\tilde{\kappa}_V}{2} W_\mu^- W_\nu^+ \epsilon^{\mu\nu\rho\sigma} V_{\rho\sigma} \end{aligned} \quad (9.13)$$

is immediately recognizable as

$$\mathcal{L}_{\text{TGC}}(g_5, \tilde{\kappa})/g_{VWW} = -ig_5 \mathcal{L}_{\tilde{L}}(V, W^-, W^+) + \tilde{\kappa} \mathcal{L}_{\tilde{T}}(V, W^-, W^+) \quad (9.14)$$

9.1.4 *SU(2) Gauge Bosons*

An important special case for table 9.13 are the two usual coordinates of SU(2)

$$W_\pm = \frac{1}{\sqrt{2}} (W_1 \mp iW_2) \quad (9.15)$$

<i>Dim4_Vector_Vector_Vector-T</i> : $\mathcal{L}_I = gV_1^\mu V_{2,\nu} \overleftrightarrow{\partial}_\mu V_3^\nu$
<i>F23</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g(k_2^\mu - k_3^\mu) V_{2,\nu}(k_2) V_3^\nu(k_3)$
<i>F32</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g(k_2^\mu - k_3^\mu) V_3^\nu(k_3) V_{2,\nu}(k_2)$
<i>F12</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g(2k_2^\nu + k_1^\nu) V_{1,\nu}(k_1) V_2^\mu(k_2)$
<i>F21</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g(2k_2^\nu + k_1^\nu) V_2^\mu(k_2) V_{1,\nu}(k_1)$
<i>F13</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g(-k_1^\nu - 2k_3^\nu) V_1^\nu(k_1) V_3^\mu(k_3)$
<i>F31</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g(-k_1^\nu - 2k_3^\nu) V_3^\mu(k_3) V_1^\nu(k_1)$
<i>Dim4_Vector_Vector_Vector-L</i> : $\mathcal{L}_I = gi\partial_\mu V_1^\mu V_{2,\nu} V_3^\nu$
<i>F23</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g(k_2^\mu + k_3^\mu) V_{2,\nu}(k_2) V_3^\nu(k_3)$
<i>F32</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g(k_2^\mu + k_3^\mu) V_3^\nu(k_3) V_{2,\nu}(k_2)$
<i>F12</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g(-k_1^\nu) V_{1,\nu}(k_1) V_2^\mu(k_2)$
<i>F21</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g(-k_1^\nu) V_2^\mu(k_2) V_{1,\nu}(k_1)$
<i>F13</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g(-k_1^\nu) V_1^\nu(k_1) V_3^\mu(k_3)$
<i>F31</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g(-k_1^\nu) V_3^\mu(k_3) V_1^\nu(k_1)$

Table 9.19: ...

<i>Dim4_Vector_Vector_Vector-T5</i> : $\mathcal{L}_I = gV_{1,\mu} V_{2,\rho} \overleftrightarrow{\partial}_\nu V_{3,\sigma} \epsilon^{\mu\nu\rho\sigma}$
<i>F23</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(k_{2,\nu} - k_{3,\nu}) V_{2,\rho}(k_2) V_{3,\sigma}(k_3)$
<i>F32</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(k_{2,\nu} - k_{3,\nu}) V_{3,\sigma}(k_3) V_{2,\rho}(k_2)$
<i>F12</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(2k_{2,\nu} + k_{1,\nu}) V_{1,\rho}(k_1) V_{2,\sigma}(k_2)$
<i>F21</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(2k_{2,\nu} + k_{1,\nu}) V_{2,\sigma}(k_2) V_{1,\rho}(k_1)$
<i>F13</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(-k_{1,\nu} - 2k_{3,\nu}) V_{1,\rho}(k_1) V_{3,\sigma}(k_3)$
<i>F31</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(-k_{1,\nu} - 2k_{3,\nu}) V_{3,\sigma}(k_3) V_{1,\rho}(k_1)$
<i>Dim4_Vector_Vector_Vector-L5</i> : $\mathcal{L}_I = gi\partial_\mu V_{1,\nu} V_{2,\nu} V_{3,\sigma} \epsilon^{\mu\nu\rho\sigma}$
<i>F23</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(k_{2,\nu} + k_{3,\nu}) V_{2,\rho}(k_2) V_{3,\sigma}(k_3)$
<i>F32</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(k_{2,\nu} + k_{3,\nu}) V_{2,\rho}(k_2) V_{3,\sigma}(k_3)$
<i>F12</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(-k_{1,\nu}) V_{1,\rho}(k_1) V_{2,\sigma}(k_2)$
<i>F21</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(-k_{1,\nu}) V_{2,\sigma}(k_2) V_{1,\rho}(k_1)$
<i>F13</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(-k_{1,\nu}) V_{1,\rho}(k_1) V_{3,\sigma}(k_3)$
<i>F31</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g\epsilon^{\mu\nu\rho\sigma}(-k_{1,\nu}) V_{3,\sigma}(k_3) V_{1,\rho}(k_1)$

Table 9.20: ...

<i>Dim6_Gauge_Gauge_Gauge</i> : $\mathcal{L}_I = g F_1^{\mu\nu} F_{2,\nu\rho} F_{3,\rho\mu}$
$\therefore A_1^\mu(k_2 + k_3) \leftarrow -i \cdot \Lambda^{\mu\rho\sigma}(-k_2 - k_3, k_2, k_3) A_{2,\rho} A_{3,\sigma}$

Table 9.21: ...

<i>Dim6_Gauge_Gauge_Gauge_5</i> : $\mathcal{L}_I = g/2 \cdot \epsilon^{\mu\nu\lambda\tau} F_{1,\mu\nu} F_{2,\tau\rho} F_{3,\rho\lambda}$
<i>F23</i> : $A_1^\mu(k_2 + k_3) \leftarrow -i \cdot \Lambda_5^{\mu\rho\sigma}(-k_2 - k_3, k_2, k_3) A_{2,\rho} A_{3,\sigma}$
<i>F32</i> : $A_1^\mu(k_2 + k_3) \leftarrow -i \cdot \Lambda_5^{\mu\rho\sigma}(-k_2 - k_3, k_2, k_3) A_{3,\sigma} A_{2,\rho}$
<i>F12</i> : $A_3^\mu(k_1 + k_2) \leftarrow -i \cdot$
<i>F21</i> : $A_3^\mu(k_1 + k_2) \leftarrow -i \cdot$
<i>F13</i> : $A_2^\mu(k_1 + k_3) \leftarrow -i \cdot$
<i>F31</i> : $A_2^\mu(k_1 + k_3) \leftarrow -i \cdot$

Table 9.22: ...

i. e.

$$W_1 = \frac{1}{\sqrt{2}} (W_+ + W_-) \quad (9.16a)$$

$$W_2 = \frac{i}{\sqrt{2}} (W_+ - W_-) \quad (9.16b)$$

and

$$W_1^\mu W_2^\nu - W_2^\mu W_1^\nu = i (W_-^\mu W_+^\nu - W_+^\mu W_-^\nu) \quad (9.17)$$

Thus the symmtry remains after the change of basis:


$$\begin{aligned} \epsilon^{abc} W_a^{\mu_1} W_b^{\mu_2} W_c^{\mu_3} &= i W_-^{\mu_1} (W_+^{\mu_2} W_3^{\mu_3} - W_3^{\mu_2} W_+^{\mu_3}) \\ &\quad + i W_+^{\mu_1} (W_3^{\mu_2} W_-^{\mu_3} - W_-^{\mu_2} W_3^{\mu_3}) + i W_3^{\mu_1} (W_-^{\mu_2} W_+^{\mu_3} - W_+^{\mu_2} W_-^{\mu_3}) \end{aligned} \quad (9.18)$$

9.1.5 Quartic Couplings and Auxiliary Fields

Quartic couplings can be replaced by cubic couplings to a non-propagating auxiliary field. The quartic term should get a negative sign so that it the energy is bounded from below for identical fields. In the language of functional integrals

$$\begin{aligned} \mathcal{L}_{\phi^4} &= -g^2 \phi_1 \phi_2 \phi_3 \phi_4 \implies \\ \mathcal{L}_{X\phi^2} &= X^* X \pm g X \phi_1 \phi_2 \pm g X^* \phi_3 \phi_4 = (X^* \pm g \phi_1 \phi_2)(X \pm g \phi_3 \phi_4) - g^2 \phi_1 \phi_2 \phi_3 \phi_4 \end{aligned} \quad (9.19a)$$

and in the language of Feynman diagrams



$$(9.19b)$$

The other choice of signs

$$\mathcal{L}'_{X\phi^2} = -X^*X \pm gX\phi_1\phi_2 \mp gX^*\phi_3\phi_4 = -(X^* \pm g\phi_1\phi_2)(X \mp g\phi_3\phi_4) - g^2\phi_1\phi_2\phi_3\phi_4 \quad (9.20)$$

can not be extended easily to identical particles and is therefore not used. For identical particles we have

$$\begin{aligned} \mathcal{L}_{\phi^4} &= -\frac{g^2}{4!}\phi^4 \Rightarrow \\ \mathcal{L}_{X\phi^2} &= \frac{1}{2}X^2 \pm \frac{g}{2}X\phi^2 \pm \frac{g}{2}X\phi^2 = \frac{1}{2}\left(X \pm \frac{g}{2}\phi^2\right)\left(X \pm \frac{g}{2}\phi^2\right) - \frac{g^2}{4!}\phi^4 \end{aligned} \quad (9.21)$$



Explain the factor 1/3 in the functional setting and its relation to the three diagrams in the graphical setting?

Quartic Gauge Couplings

The three crossed versions of figure 9.2 reproduces the quartic coupling in figure 9.1, because

$$\begin{aligned} & -ig^2 f_{a_1 a_2 b} f_{a_3 a_4 b} (g_{\mu_1 \mu_3} g_{\mu_4 \mu_2} - g_{\mu_1 \mu_4} g_{\mu_2 \mu_3}) \\ &= (ig f_{a_1 a_2 b} T_{\mu_1 \mu_2, \nu_1 \nu_2}) \left(\frac{ig^{\nu_1 \nu_3} g^{\nu_2 \nu_4}}{2} \right) (ig f_{a_3 a_4 b} T_{\mu_3 \mu_4, \nu_3 \nu_4}) \end{aligned} \quad (9.24)$$

with $T_{\mu_1 \mu_2, \mu_3 \mu_4} = g_{\mu_1 \mu_3} g_{\mu_4 \mu_2} - g_{\mu_1 \mu_4} g_{\mu_2 \mu_3}$.

9.1.6 Gravitinos and supersymmetric currents

In supergravity theories there is a fermionic partner of the graviton, the gravitino. Therefore we have introduced the Lorentz type *Vectorspinor*.

9.1.7 Perturbative Quantum Gravity and Kaluza-Klein Interactions

The gravitational coupling constant and the relative strength of the dilaton coupling are abbreviated as

$$\kappa = \sqrt{16\pi G_N} \quad (9.25a)$$

$$\omega = \sqrt{\frac{2}{3(n+2)}} = \sqrt{\frac{2}{3(d-2)}}, \quad (9.25b)$$

$$\begin{aligned}
 & \begin{array}{c} k, \mu, a \\ \nearrow \\ p \longrightarrow \bullet \\ \searrow \\ p' \end{array} = +ig\gamma_\mu T_a \quad (9.22a) \\
 & \begin{array}{c} 1 \\ \nearrow \\ 2 \text{ (wavy)} \longrightarrow \bullet \\ \searrow \\ 3 \end{array} = gf_{a_1 a_2 a_3} C^{\mu_1 \mu_2 \mu_3}(k_1, k_2, k_3) \quad (9.22b) \\
 & \begin{array}{c} 1 \\ \nearrow \\ 2 \text{ (wavy)} \longrightarrow \bullet \\ \searrow \\ 3 \end{array} \quad \begin{array}{c} 3 \\ \nearrow \\ 4 \text{ (wavy)} \longrightarrow \bullet \\ \searrow \\ 1 \end{array} = \begin{aligned} & -ig^2 f_{a_1 a_2 b} f_{a_3 a_4 b} (g_{\mu_1 \mu_3} g_{\mu_4 \mu_2} - g_{\mu_1 \mu_4} g_{\mu_2 \mu_3}) \\ & -ig^2 f_{a_1 a_3 b} f_{a_4 a_2 b} (g_{\mu_1 \mu_4} g_{\mu_2 \mu_3} - g_{\mu_1 \mu_2} g_{\mu_3 \mu_4}) \\ & -ig^2 f_{a_1 a_4 b} f_{a_2 a_3 b} (g_{\mu_1 \mu_2} g_{\mu_3 \mu_4} - g_{\mu_1 \mu_3} g_{\mu_4 \mu_2}) \end{aligned} \quad (9.22c)
 \end{aligned}$$

Figure 9.1: Gauge couplings. See (11.1b) for the definition of the antisymmetric tensor $C^{\mu_1 \mu_2 \mu_3}(k_1, k_2, k_3)$.

$$\begin{array}{c} 1 \\ \nearrow \\ 2 \text{ (wavy)} \longrightarrow \bullet \\ \searrow \\ 3 \end{array} \quad \begin{array}{c} 3 \\ \nearrow \\ 4 \text{ (wavy)} \longrightarrow \bullet \\ \searrow \\ 1 \end{array} = -ig^2 f_{a_1 a_2 b} f_{a_3 a_4 b} (g_{\mu_1 \mu_3} g_{\mu_4 \mu_2} - g_{\mu_1 \mu_4} g_{\mu_2 \mu_3}) \quad (9.23)$$

Figure 9.2: Gauge couplings.

<i>GBG (Fermbar, MOM, Ferm):</i> $\bar{\psi}_1(i\cancel{\partial} \pm m)\phi\psi_2$	
<i>F12:</i> $\psi_2 \leftarrow -(\cancel{k} \mp m)\psi_1 S$	<i>F21:</i> $\psi_2 \leftarrow -S(\cancel{k} \mp m)\psi_1$
<i>F13:</i> $S \leftarrow \psi_1^T C(\cancel{k} \pm m)\psi_2$	<i>F31:</i> $S \leftarrow \psi_2^T C(-(\cancel{k} \mp m)\psi_1)$
<i>F23:</i> $\psi_1 \leftarrow S(\cancel{k} \pm m)\psi_2$	<i>F32:</i> $\psi_1 \leftarrow (\cancel{k} \pm m)\psi_2 S$
<i>GBG (Fermbar, MOM5, Ferm):</i> $\bar{\psi}_1(i\cancel{\partial} \pm m)\phi\gamma^5\psi_2$	
<i>F12:</i> $\psi_2 \leftarrow (\cancel{k} \pm m)\gamma^5\psi_1 P$	<i>F21:</i> $\psi_2 \leftarrow P(\cancel{k} \pm m)\gamma^5\psi_1$
<i>F13:</i> $P \leftarrow \psi_1^T C(\cancel{k} \pm m)\gamma^5\psi_2$	<i>F31:</i> $P \leftarrow \psi_2^T C(\cancel{k} \pm m)\gamma^5\psi_1$
<i>F23:</i> $\psi_1 \leftarrow P(\cancel{k} \pm m)\gamma^5\psi_2$	<i>F32:</i> $\psi_1 \leftarrow (\cancel{k} \pm m)\gamma^5\psi_2 P$
<i>GBG (Fermbar, MOML, Ferm):</i> $\bar{\psi}_1(i\cancel{\partial} \pm m)\phi(1 - \gamma^5)\psi_2$	
<i>F12:</i> $\psi_2 \leftarrow -(1 - \gamma^5)(\cancel{k} \mp m)\psi_1\phi$	<i>F21:</i> $\psi_2 \leftarrow -\phi(1 - \gamma^5)(\cancel{k} \mp m)\psi_1$
<i>F13:</i> $\phi \leftarrow \psi_1^T C(\cancel{k} \pm m)(1 - \gamma^5)\psi_2$	<i>F31:</i> $\phi \leftarrow \psi_2^T C(1 - \gamma^5)(-\cancel{k} \mp m)\psi_1$
<i>F23:</i> $\psi_1 \leftarrow \phi(\cancel{k} \pm m)(1 - \gamma^5)\psi_2$	<i>F32:</i> $\psi_1 \leftarrow (\cancel{k} \pm m)(1 - \gamma^5)\psi_2\phi$
<i>GBG (Fermbar, LMOM, Ferm):</i> $\bar{\psi}_1\phi(1 - \gamma^5)(i\cancel{\partial} \pm m)\psi_2$	
<i>F12:</i> $\psi_2 \leftarrow -(\cancel{k} \mp m)\psi_1(1 - \gamma^5)\phi$	<i>F21:</i> $\psi_2 \leftarrow -\phi(\cancel{k} \mp m)(1 - \gamma^5)\psi_1$
<i>F13:</i> $\phi \leftarrow \psi_1^T C(1 - \gamma^5)(\cancel{k} \pm m)\psi_2$	<i>F31:</i> $\phi \leftarrow \psi_2^T C(-(\cancel{k} \mp m)(1 - \gamma^5)\psi_1)$
<i>F23:</i> $\psi_1 \leftarrow \phi(1 - \gamma^5)(\cancel{k} \pm m)\psi_2$	<i>F32:</i> $\psi_1 \leftarrow (1 - \gamma^5)(\cancel{k} \pm m)\psi_2\phi$
<i>GBG (Fermbar, VMOM, Ferm):</i> $\bar{\psi}_1 i\cancel{\partial}_\alpha V_\beta[\gamma^\alpha, \gamma^\beta]\psi_2$	
<i>F12:</i> $\psi_2 \leftarrow -[\cancel{k}, \gamma^\alpha]\psi_1 V_\alpha$	<i>F21:</i> $\psi_2 \leftarrow -[\cancel{k}, V]\psi_1$
<i>F13:</i> $V_\alpha \leftarrow \psi_1^T C[\cancel{k}, \gamma_\alpha]\psi_2$	<i>F31:</i> $V_\alpha \leftarrow \psi_2^T C(-[\cancel{k}, \gamma_\alpha]\psi_1)$
<i>F23:</i> $\psi_1 \leftarrow [\cancel{k}, V]\psi_2$	<i>F32:</i> $\psi_1 \leftarrow [\cancel{k}, \gamma^\alpha]\psi_2 V_\alpha$

Table 9.23: Combined dimension-4 trilinear fermionic couplings including a momentum. *Ferm* stands for *Psi* and *Chi*. The case of *MOMR* is identical to *MOML* if one substitutes $1 + \gamma^5$ for $1 - \gamma^5$, as well as for *LMOM* and *RMOM*. The mass term forces us to keep the chiral projector always on the left after "inverting the line" for *MOML* while on the right for *LMOM*.

<i>GBBG (Fermbar, S2LR, Ferm):</i> $\bar{\psi}_1 S_1 S_2 (g_L P_L + g_R P_R) \psi_2$	
<i>F123 F213 F132 F231 F312 F321:</i>	$\psi_2 \leftarrow S_1 S_2 (g_R P_L + g_L P_R) \psi_1$
<i>F423 F243 F432 F234 F342 F324:</i>	$\psi_1 \leftarrow S_1 S_2 (g_L P_L + g_R P_R) \psi_2$
<i>F134 F143 F314:</i>	$S_1 \leftarrow \psi_1^T C S_2 (g_L P_L + g_R P_R) \psi_2$
<i>F124 F142 F214:</i>	$S_2 \leftarrow \psi_1^T C S_1 (g_L P_L + g_R P_R) \psi_2$
<i>F413 F431 F341:</i>	$S_1 \leftarrow \psi_2^T C S_2 (g_R P_L + g_L P_R) \psi_1$
<i>F412 F421 F241:</i>	$S_2 \leftarrow \psi_2^T C S_1 (g_R P_L + g_L P_R) \psi_1$
<i>GBBG (Fermbar, S2, Ferm):</i> $\bar{\psi}_1 S_1 S_2 \gamma^5 \psi_2$	
<i>F123 F213 F132 F231 F312 F321:</i>	$\psi_2 \leftarrow S_1 S_2 \gamma^5 \psi_1$
<i>F423 F243 F432 F234 F342 F324:</i>	$\psi_1 \leftarrow S_1 S_2 \gamma^5 \psi_2$
<i>F134 F143 F314:</i>	$S_1 \leftarrow \psi_1^T C S_2 \gamma^5 \psi_2$
<i>F124 F142 F214:</i>	$S_2 \leftarrow \psi_1^T C S_1 \gamma^5 \psi_2$
<i>F413 F431 F341:</i>	$S_1 \leftarrow \psi_2^T C S_2 \gamma^5 \psi_1$
<i>F412 F421 F241:</i>	$S_2 \leftarrow \psi_2^T C S_1 \gamma^5 \psi_1$
<i>GBBG (Fermbar, V2, Ferm):</i> $\bar{\psi}_1 [\mathbb{V}_1, \mathbb{V}_2] \psi_2$	
<i>F123 F213 F132 F231 F312 F321:</i>	$\psi_2 \leftarrow -[\mathbb{V}_1, \mathbb{V}_2] \psi_1$
<i>F423 F243 F432 F234 F342 F324:</i>	$\psi_1 \leftarrow [\mathbb{V}_1, \mathbb{V}_2] \psi_2$
<i>F134 F143 F314:</i>	$V_{1\alpha} \leftarrow \psi_1^T C [\gamma_\alpha, \mathbb{V}_2] \psi_2$
<i>F124 F142 F214:</i>	$V_{2\alpha} \leftarrow \psi_1^T C (-[\gamma_\alpha, \mathbb{V}_1]) \psi_2$
<i>F413 F431 F341:</i>	$V_{1\alpha} \leftarrow \psi_2^T C (-[\gamma_\alpha, \mathbb{V}_2]) \psi_1$
<i>F412 F421 F241:</i>	$V_{2\alpha} \leftarrow \psi_2^T C [\gamma_\alpha, \mathbb{V}_1] \psi_1$

Table 9.24: Vertices with two fermions (*Ferm* stands for *Psi* and *Chi*, but not for *Grav*) and two bosons (two scalars, scalar/vector, two vectors) for the BRST transformations. Part I

<i>GBBG (Fermbar, SV, Ferm): $\bar{\psi}_1 \not{V} S \psi_2$</i>						
<i>F123 F213 F132 F231 F312 F321:</i>	$\psi_2 \leftarrow -\not{V} S \psi_1$					
<i>F423 F243 F432 F234 F342 F324:</i>	$\psi_1 \leftarrow \not{V} S \psi_2$					
<i>F134 F143 F314:</i>	$V_\alpha \leftarrow \psi_1^T C \gamma_\alpha S \psi_2$					
<i>F124 F142 F214:</i>	$S \leftarrow \psi_1^T C \not{V} \psi_2$					
<i>F413 F431 F341:</i>	$V_\alpha \leftarrow \psi_2^T C (-\gamma_\alpha S \psi_1)$					
<i>F412 F421 F241:</i>	$S \leftarrow \psi_2^T C (-\not{V} \psi_1)$					
<i>GBBG (Fermbar, PV, Ferm): $\bar{\psi}_1 \not{V} \gamma^5 P \psi_2$</i>						
<i>F123 F213 F132 F231 F312 F321:</i>	$\psi_2 \leftarrow \not{V} \gamma^5 P \psi_1$					
<i>F423 F243 F432 F234 F342 F324:</i>	$\psi_1 \leftarrow \not{V} \gamma^5 P \psi_2$					
<i>F134 F143 F314:</i>	$V_\alpha \leftarrow \psi_1^T C \gamma_\alpha \gamma^5 P \psi_2$					
<i>F124 F142 F214:</i>	$P \leftarrow \psi_1^T C \not{V} \gamma^5 \psi_2$					
<i>F413 F431 F341:</i>	$V_\alpha \leftarrow \psi_2^T C \gamma_\alpha \gamma^5 P \psi_1$					
<i>F412 F421 F241:</i>	$P \leftarrow \psi_2^T C \not{V} \gamma^5 \psi_1$					
<i>GBBG (Fermbar, S(L/R)V, Ferm): $\bar{\psi}_1 \not{V} (1 \mp \gamma^5) \phi \psi_2$</i>						
<i>F123 F213 F132 F231 F312 F321:</i>	$\psi_2 \leftarrow -\not{V} (1 \pm \gamma^5) \phi \psi_1$					
<i>F423 F243 F432 F234 F342 F324:</i>	$\psi_1 \leftarrow \not{V} (1 \mp \gamma^5) \phi \psi_2$					
<i>F134 F143 F314:</i>	$V_\alpha \leftarrow \psi_1^T C \gamma_\alpha (1 \mp \gamma^5) \phi \psi_2$					
<i>F124 F142 F214:</i>	$\phi \leftarrow \psi_1^T C \not{V} (1 \mp \gamma^5) \psi_2$					
<i>F413 F431 F341:</i>	$V_\alpha \leftarrow \psi_2^T C \gamma_\alpha (-(1 \pm \gamma^5) \phi \psi_1)$					
<i>F412 F421 F241:</i>	$\phi \leftarrow \psi_2^T C \not{V} (-(1 \pm \gamma^5) \psi_1)$					

Table 9.25: Vertices with two fermions (*Ferm* stands for *Psi* and *Chi*, but not for *Grav*) and two bosons (two scalars, scalar/vector, two vectors) for the BRST transformations. Part II

<i>GBG (Gravbar, POT, Psi): $\bar{\psi}_\mu S \gamma^\mu \psi$</i>	
<i>F12:</i> $\psi \leftarrow -\gamma^\mu \psi_\mu S$	<i>F21:</i> $\psi \leftarrow -S \gamma^\mu \psi_\mu$
<i>F13:</i> $S \leftarrow \psi_\mu^T C \gamma^\mu \psi$	<i>F31:</i> $S \leftarrow \psi^T C (-\gamma^\mu) \psi_\mu$
<i>F23:</i> $\psi_\mu \leftarrow S \gamma_\mu \psi$	<i>F32:</i> $\psi_\mu \leftarrow \gamma_\mu \psi S$
<i>GBG (Gravbar, S, Psi): $\bar{\psi}_\mu \not{k}_S S \gamma^\mu \psi$</i>	
<i>F12:</i> $\psi \leftarrow \gamma^\mu \not{k}_S \psi_\mu S$	<i>F21:</i> $\psi \leftarrow S \gamma^\mu \not{k}_S \psi_\mu$
<i>F13:</i> $S \leftarrow \psi_\mu^T C \not{k}_S \gamma^\mu \psi$	<i>F31:</i> $S \leftarrow \psi^T C \gamma^\mu \not{k}_S \psi_\mu$
<i>F23:</i> $\psi_\mu \leftarrow S \not{k}_S \gamma_\mu \psi$	<i>F32:</i> $\psi_\mu \leftarrow \not{k}_S \gamma_\mu \psi S$
<i>GBG (Gravbar, P, Psi): $\bar{\psi}_\mu \not{k}_P P \gamma^\mu \gamma_5 \psi$</i>	
<i>F12:</i> $\psi \leftarrow \gamma^\mu \not{k}_P \gamma_5 \psi_\mu P$	<i>F21:</i> $\psi \leftarrow P \gamma^\mu \not{k}_P \gamma_5 \psi_\mu$
<i>F13:</i> $P \leftarrow \psi_\mu^T C \not{k}_P \gamma^\mu \gamma_5 \psi$	<i>F31:</i> $P \leftarrow \psi^T C \gamma^\mu \not{k}_P \gamma_5 \psi_\mu$
<i>F23:</i> $\psi_\mu \leftarrow P \not{k}_P \gamma_\mu \gamma_5 \psi$	<i>F32:</i> $\psi_\mu \leftarrow \not{k}_P \gamma_\mu \gamma_5 \psi P$
<i>GBG (Gravbar, V, Psi): $\bar{\psi}_\mu [\not{k}_V, \gamma^\mu] \gamma^\mu \gamma^5 \psi$</i>	
<i>F12:</i> $\psi \leftarrow \gamma^5 \gamma^\mu [\not{k}_V, \gamma^\alpha] \psi_\mu V_\alpha$	<i>F21:</i> $\psi \leftarrow \gamma^5 \gamma^\mu [\not{k}_V, V] \psi_\mu$
<i>F13:</i> $V_\mu \leftarrow \psi_\rho^T C [\not{k}_V, \gamma_\mu] \gamma^\rho \gamma^5 \psi$	<i>F31:</i> $V_\mu \leftarrow \psi^T C \gamma^5 \gamma^\rho [\not{k}_V, \gamma_\mu] \psi_\rho$
<i>F23:</i> $\psi_\mu \leftarrow [\not{k}_V, V] \gamma_\mu \gamma^5 \psi$	<i>F32:</i> $\psi_\mu \leftarrow [\not{k}_V, \gamma^\alpha] \gamma_\mu \gamma^5 \psi V_\alpha$

Table 9.26: Dimension-5 trilinear couplings including one Dirac, one Gravitino fermion and one additional particle. The option *POT* is for the coupling of the supersymmetric current to the derivative of the quadratic terms in the superpotential.

<i>GBG</i> (<i>Psibar</i> , <i>POT</i> , <i>Grav</i>): $\bar{\psi}\gamma^\mu S\psi_\mu$	
<i>F12</i> : $\psi_\mu \leftarrow -\gamma_\mu \psi S$	<i>F21</i> : $\psi_\mu \leftarrow -S\gamma_\mu \psi$
<i>F13</i> : $S \leftarrow \psi^T C\gamma^\mu \psi_\mu$	<i>F31</i> : $S \leftarrow \psi_\mu^T C(-\gamma^\mu)\psi$
<i>F23</i> : $\psi \leftarrow S\gamma^\mu \psi_\mu$	<i>F32</i> : $\psi \leftarrow \gamma^\mu \psi_\mu S$
<i>GBG</i> (<i>Psibar</i> , <i>S</i> , <i>Grav</i>): $\bar{\psi}\gamma^\mu \not{k}_S S\psi_\mu$	
<i>F12</i> : $\psi_\mu \leftarrow \not{k}_S \gamma_\mu \psi S$	<i>F21</i> : $\psi_\mu \leftarrow S \not{k}_S \gamma_\mu \psi$
<i>F13</i> : $S \leftarrow \psi^T C\gamma^\mu \not{k}_S \psi_\mu$	<i>F31</i> : $S \leftarrow \psi_\mu^T C \not{k}_S \gamma^\mu \psi$
<i>F23</i> : $\psi \leftarrow S\gamma^\mu \not{k}_S \psi_\mu$	<i>F32</i> : $\psi \leftarrow \gamma^\mu \not{k}_S \psi_\mu S$
<i>GBG</i> (<i>Psibar</i> , <i>P</i> , <i>Grav</i>): $\bar{\psi}\gamma^\mu \gamma^5 P \not{k}_P \psi_\mu$	
<i>F12</i> : $\psi_\mu \leftarrow -\not{k}_P \gamma_\mu \gamma^5 \psi P$	<i>F21</i> : $\psi_\mu \leftarrow -P \not{k}_P \gamma_\mu \gamma^5 \psi$
<i>F13</i> : $P \leftarrow \psi^T C\gamma^\mu \gamma^5 \not{k}_P \psi_\mu$	<i>F31</i> : $P \leftarrow -\psi_\mu^T C \not{k}_P \gamma^\mu \gamma^5 \psi$
<i>F23</i> : $\psi \leftarrow P\gamma^\mu \gamma^5 \not{k}_P \psi_\mu$	<i>F32</i> : $\psi \leftarrow \gamma^\mu \gamma^5 \not{k}_P \psi_\mu P$
<i>GBG</i> (<i>Psibar</i> , <i>V</i> , <i>Grav</i>): $\bar{\psi}\gamma^5 \gamma^\mu [\not{k}_V, V]\psi_\mu$	
<i>F12</i> : $\psi_\mu \leftarrow [\not{k}_V, \gamma^\alpha] \gamma_\mu \gamma^5 \psi V_\alpha$	<i>F21</i> : $\psi_\mu \leftarrow [\not{k}_V, V] \gamma_\mu \gamma^5 \psi$
<i>F13</i> : $V_\mu \leftarrow \psi^T C\gamma^5 \gamma^\rho [\not{k}_V, \gamma_\mu] \psi_\rho$	<i>F31</i> : $V_\mu \leftarrow \psi_\rho^T C [\not{k}_V, \gamma_\mu] \gamma^\rho \gamma^5 \psi$
<i>F23</i> : $\psi \leftarrow \gamma^5 \gamma^\mu [\not{k}_V, V] \psi_\mu$	<i>F32</i> : $\psi \leftarrow \gamma^5 \gamma^\mu [\not{k}_V, \gamma^\alpha] \psi_\mu V_\alpha$

Table 9.27: Dimension-5 trilinear couplings including one conjugated Dirac, one Gravitino fermion and one additional particle.

<i>GBG (Gravbar, POT, Chi): $\bar{\psi}_\mu S \gamma^\mu \chi$</i>	
<i>F12:</i> $\chi \leftarrow -\gamma^\mu \psi_\mu S$	<i>F21:</i> $\chi \leftarrow -S \gamma^\mu \psi_\mu$
<i>F13:</i> $S \leftarrow \psi_\mu^T C \gamma^\mu \chi$	<i>F31:</i> $S \leftarrow \chi^T C (-\gamma^\mu) \psi_\mu$
<i>F23:</i> $\psi_\mu \leftarrow S \gamma_\mu \chi$	<i>F32:</i> $\psi_\mu \leftarrow \gamma_\mu \chi S$
<i>GBG (Gravbar, S, Chi): $\bar{\psi}_\mu \not{k}_S S \gamma^\mu \chi$</i>	
<i>F12:</i> $\chi \leftarrow \gamma^\mu \not{k}_S \psi_\mu S$	<i>F21:</i> $\chi \leftarrow S \gamma^\mu \not{k}_S \psi_\mu$
<i>F13:</i> $S \leftarrow \psi_\mu^T C \not{k}_S \gamma^\mu \chi$	<i>F31:</i> $S \leftarrow \chi^T C \gamma^\mu \not{k}_S \psi_\mu$
<i>F23:</i> $\psi_\mu \leftarrow S \not{k}_S \gamma_\mu \chi$	<i>F32:</i> $\psi_\mu \leftarrow \not{k}_S \gamma_\mu \chi S$
<i>GBG (Gravbar, P, Chi): $\bar{\psi}_\mu \not{k}_P P \gamma^\mu \gamma_5 \chi$</i>	
<i>F12:</i> $\chi \leftarrow \gamma^\mu \not{k}_P \gamma_5 \psi_\mu P$	<i>F21:</i> $\chi \leftarrow P \gamma^\mu \not{k}_P \gamma_5 \psi_\mu$
<i>F13:</i> $P \leftarrow \psi_\mu^T C \not{k}_P \gamma^\mu \gamma_5 \chi$	<i>F31:</i> $P \leftarrow \chi^T C \gamma^\mu \not{k}_P \gamma_5 \psi_\mu$
<i>F23:</i> $\psi_\mu \leftarrow P \not{k}_P \gamma_\mu \gamma_5 \chi$	<i>F32:</i> $\psi_\mu \leftarrow \not{k}_P \gamma_\mu \gamma_5 \chi P$
<i>GBG (Gravbar, V, Chi): $\bar{\psi}_\mu [\not{k}_V, V] \gamma^\mu \gamma^5 \chi$</i>	
<i>F12:</i> $\chi \leftarrow \gamma^5 \gamma^\mu [\not{k}_V, \gamma^\alpha] \psi_\mu V_\alpha$	<i>F21:</i> $\chi \leftarrow \gamma^5 \gamma^\mu [\not{k}_V, V] \psi_\mu$
<i>F13:</i> $V_\mu \leftarrow \psi_\rho^T C [\not{k}_V, \gamma_\mu] \gamma^\rho \gamma^5 \chi$	<i>F31:</i> $V_\mu \leftarrow \chi^T C \gamma^5 \gamma^\rho [\not{k}_V, \gamma_\mu] \psi_\rho$
<i>F23:</i> $\psi_\mu \leftarrow [\not{k}_V, V] \gamma_\mu \gamma^5 \chi$	<i>F32:</i> $\psi_\mu \leftarrow [\not{k}_V, \gamma^\alpha] \gamma_\mu \gamma^5 \chi V_\alpha$

Table 9.28: Dimension-5 trilinear couplings including one Majorana, one Gravitino fermion and one additional particle. The table is essentially the same as the one with the Dirac fermion and only written for the sake of completeness.

<i>GBG (Chibar, POT, Grav): $\bar{\chi}\gamma^\mu S\psi_\mu$</i>	
<i>F12:</i> $\psi_\mu \leftarrow -\gamma_\mu \chi S$	<i>F21:</i> $\psi_\mu \leftarrow -S\gamma_\mu \chi$
<i>F13:</i> $S \leftarrow \chi^T C\gamma^\mu \psi_\mu$	<i>F31:</i> $S \leftarrow \psi_\mu^T C(-\gamma^\mu)\chi$
<i>F23:</i> $\chi \leftarrow S\gamma^\mu \psi_\mu$	<i>F32:</i> $\chi \leftarrow \gamma^\mu \psi_\mu S$
<i>GBG (Chibar, S, Grav): $\bar{\chi}\gamma^\mu \not{k}_S S\psi_\mu$</i>	
<i>F12:</i> $\psi_\mu \leftarrow \not{k}_S \gamma_\mu \chi S$	<i>F21:</i> $\psi_\mu \leftarrow S \not{k}_S \gamma_\mu \chi$
<i>F13:</i> $S \leftarrow \chi^T C\gamma^\mu \not{k}_S \psi_\mu$	<i>F31:</i> $S \leftarrow \psi_\mu^T C \not{k}_S \gamma^\mu \chi$
<i>F23:</i> $\chi \leftarrow S\gamma^\mu \not{k}_S \psi_\mu$	<i>F32:</i> $\chi \leftarrow \gamma^\mu \not{k}_S \psi_\mu S$
<i>GBG (Chibar, P, Grav): $\bar{\chi}\gamma^\mu \gamma^5 P \not{k}_P \psi_\mu$</i>	
<i>F12:</i> $\psi_\mu \leftarrow -\not{k}_P \gamma_\mu \gamma^5 \chi P$	<i>F21:</i> $\psi_\mu \leftarrow -P \not{k}_P \gamma_\mu \gamma^5 \chi$
<i>F13:</i> $P \leftarrow \chi^T C\gamma^\mu \gamma^5 \not{k}_P \psi_\mu$	<i>F31:</i> $P \leftarrow -\psi_\mu^T C \not{k}_P \gamma^\mu \gamma^5 \chi$
<i>F23:</i> $\chi \leftarrow P\gamma^\mu \gamma^5 \not{k}_P \psi_\mu$	<i>F32:</i> $\chi \leftarrow \gamma^\mu \gamma^5 \not{k}_P \psi_\mu P$
<i>GBG (Chibar, V, Grav): $\bar{\chi}\gamma^5 \gamma^\mu [\not{k}_V, V]\psi_\mu$</i>	
<i>F12:</i> $\psi_\mu \leftarrow [\not{k}_V, \gamma^\alpha] \gamma_\mu \gamma^5 \chi V_\alpha$	<i>F21:</i> $\psi_\mu \leftarrow [\not{k}_V, V] \gamma_\mu \gamma^5 \chi$
<i>F13:</i> $V_\mu \leftarrow \chi^T C\gamma^5 \gamma^\rho [\not{k}_V, \gamma_\mu] \psi_\rho$	<i>F31:</i> $V_\mu \leftarrow \psi_\rho^T C [\not{k}_V, \gamma_\mu] \gamma^\rho \gamma^5 \chi$
<i>F23:</i> $\chi \leftarrow \gamma^5 \gamma^\mu [\not{k}_V, V] \psi_\mu$	<i>F32:</i> $\chi \leftarrow \gamma^5 \gamma^\mu [\not{k}_V, \gamma^\alpha] \psi_\mu V_\alpha$

Table 9.29: Dimension-5 trilinear couplings including one conjugated Majorana, one Gravitino fermion and one additional particle. This table is not only the same as the one with the conjugated Dirac fermion but also the same part of the Lagrangian density as the one with the Majorana particle on the right of the gravitino.

<i>GBBG</i> (<i>Gravbar</i> , <i>S2</i> , <i>Psi</i>): $\bar{\psi}_\mu S_1 S_2 \gamma^\mu \psi$						
<i>F123</i>	<i>F213</i>	<i>F132</i>	<i>F231</i>	<i>F312</i>	<i>F321</i> :	$\psi \leftarrow -\gamma^\mu S_1 S_2 \psi_\mu$
<i>F423</i>	<i>F243</i>	<i>F432</i>	<i>F234</i>	<i>F342</i>	<i>F324</i> :	$\psi_\mu \leftarrow \gamma_\mu S_1 S_2 \psi$
	<i>F134</i>	<i>F143</i>	<i>F314</i> :	$S_1 \leftarrow \psi_\mu^T C S_2 \gamma^\mu \psi$		
	<i>F124</i>	<i>F142</i>	<i>F214</i> :	$S_2 \leftarrow \psi_\mu^T C S_1 \gamma^\mu \psi$		
	<i>F413</i>	<i>F431</i>	<i>F341</i> :	$S_1 \leftarrow -\psi^T C S_2 \gamma^\mu \psi_\mu$		
	<i>F412</i>	<i>F421</i>	<i>F241</i> :	$S_2 \leftarrow -\psi^T C S_1 \gamma^\mu \psi_\mu$		
<i>GBBG</i> (<i>Gravbar</i> , <i>SV</i> , <i>Psi</i>): $\bar{\psi}_\mu S \mathbb{V} \gamma^\mu \gamma^5 \psi$						
<i>F123</i>	<i>F213</i>	<i>F132</i>	<i>F231</i>	<i>F312</i>	<i>F321</i> :	$\psi \leftarrow \gamma^5 \gamma^\mu S \mathbb{V} \psi_\mu$
<i>F423</i>	<i>F243</i>	<i>F432</i>	<i>F234</i>	<i>F342</i>	<i>F324</i> :	$\psi_\mu \leftarrow \mathbb{V} S \gamma_\mu \gamma^5 \psi$
	<i>F134</i>	<i>F143</i>	<i>F314</i> :	$S \leftarrow \psi_\mu^T C \mathbb{V} \gamma^\mu \gamma^5 \psi$		
	<i>F124</i>	<i>F142</i>	<i>F214</i> :	$V_\mu \leftarrow \psi_\rho^T C S \gamma_\mu \gamma^\rho \gamma^5 \psi$		
	<i>F413</i>	<i>F431</i>	<i>F341</i> :	$S \leftarrow \psi^T C \gamma^5 \gamma^\mu \mathbb{V} \psi_\mu$		
	<i>F412</i>	<i>F421</i>	<i>F241</i> :	$V_\mu \leftarrow \psi^T C S \gamma^5 \gamma^\rho \gamma_\mu \psi_\rho$		
<i>GBBG</i> (<i>Gravbar</i> , <i>PV</i> , <i>Psi</i>): $\bar{\psi}_\mu P \mathbb{V} \gamma^\mu \psi$						
<i>F123</i>	<i>F213</i>	<i>F132</i>	<i>F231</i>	<i>F312</i>	<i>F321</i> :	$\psi \leftarrow \gamma^\mu P \mathbb{V} \psi_\mu$
<i>F423</i>	<i>F243</i>	<i>F432</i>	<i>F234</i>	<i>F342</i>	<i>F324</i> :	$\psi_\mu \leftarrow \mathbb{V} P \gamma_\mu \psi$
	<i>F134</i>	<i>F143</i>	<i>F314</i> :	$P \leftarrow \psi_\mu^T C \mathbb{V} \gamma^\mu \psi$		
	<i>F124</i>	<i>F142</i>	<i>F214</i> :	$V_\mu \leftarrow \psi_\rho^T C P \gamma_\mu \gamma^\rho \psi$		
	<i>F413</i>	<i>F431</i>	<i>F341</i> :	$P \leftarrow \psi^T C \gamma^\mu \mathbb{V} \psi_\mu$		
	<i>F412</i>	<i>F421</i>	<i>F241</i> :	$V_\mu \leftarrow \psi^T C P \gamma^\rho \gamma_\mu \psi_\rho$		
<i>GBBG</i> (<i>Gravbar</i> , <i>V2</i> , <i>Psi</i>): $\bar{\psi}_\mu f_{abc} [V^a, \mathbb{V}^b] \gamma^\mu \gamma^5 \psi$						
<i>F123</i>	<i>F213</i>	<i>F132</i>	<i>F231</i>	<i>F312</i>	<i>F321</i> :	$\psi \leftarrow f_{abc} \gamma^5 \gamma^\mu [V^a, \mathbb{V}^b] \psi_\mu$
<i>F423</i>	<i>F243</i>	<i>F432</i>	<i>F234</i>	<i>F342</i>	<i>F324</i> :	$\psi_\mu \leftarrow f_{abc} [V^a, \mathbb{V}^b] \gamma_\mu \gamma^5 \psi$
<i>F134</i>	<i>F143</i>	<i>F314</i>	<i>F124</i>	<i>F142</i>	<i>F214</i> :	$V_\mu^a \leftarrow \psi_\rho^T C f_{abc} [\gamma_\mu, \mathbb{V}^b] \gamma^\rho \gamma^5 \psi$
<i>F413</i>	<i>F431</i>	<i>F341</i>	<i>F412</i>	<i>F421</i>	<i>F241</i> :	$V_\mu^a \leftarrow \psi^T C f_{abc} \gamma^5 \gamma^\rho [\gamma_\mu, \mathbb{V}^b] \psi_\rho$


Table 9.30: Dimension-5 trilinear couplings including one Dirac, one Gravitino fermion and two additional bosons. In each lines we list the fusion possibilities with the same order of the fermions, but the order of the bosons is arbitrary (of course, one has to take care of this order in the mapping of the wave functions in *fusion*).

<i>GBBG</i> (<i>Psibar</i> , <i>S2</i> , <i>Grav</i>): $\bar{\psi}S_1S_2\gamma^\mu\psi_\mu$	
$F123\ F213\ F132\ F231\ F312\ F321$:	$\psi_\mu \leftarrow -\gamma_\mu S_1S_2\psi$
$F423\ F243\ F432\ F234\ F342\ F324$:	$\psi \leftarrow \gamma^\mu S_1S_2\psi_\mu$
$F134\ F143\ F314$:	$S_1 \leftarrow \psi^T C S_2 \gamma^\mu \psi_\mu$
$F124\ F142\ F214$:	$S_2 \leftarrow \psi^T C S_1 \gamma^\mu \psi_\mu$
$F413\ F431\ F341$:	$S_1 \leftarrow -\psi_\mu^T C S_2 \gamma^\mu \psi$
$F412\ F421\ F241$:	$S_2 \leftarrow -\psi_\mu^T C S_1 \gamma^\mu \psi$
<i>GBBG</i> (<i>Psibar</i> , <i>SV</i> , <i>Grav</i>): $\bar{\psi}S\gamma^\mu\gamma^5\mathcal{V}\psi_\mu$	
$F123\ F213\ F132\ F231\ F312\ F321$:	$\psi_\mu \leftarrow \mathcal{V}S\gamma^5\gamma^\mu\psi$
$F423\ F243\ F432\ F234\ F342\ F324$:	$\psi \leftarrow \gamma^\mu\gamma^5S\mathcal{V}\psi_\mu$
$F134\ F143\ F314$:	$S \leftarrow \psi^T C \gamma^\mu\gamma^5\mathcal{V}\psi$
$F124\ F142\ F214$:	$V_\mu \leftarrow \psi^T C \gamma^\rho\gamma^5S\gamma_\mu\psi_\rho$
$F413\ F431\ F341$:	$S \leftarrow \psi_\mu^T C \mathcal{V}\gamma^5\gamma^\mu\psi$
$F412\ F421\ F241$:	$V_\mu \leftarrow \psi_\rho^T C S\gamma_\mu\gamma^5\gamma^\rho\psi$
<i>GBBG</i> (<i>Psibar</i> , <i>PV</i> , <i>Grav</i>): $\bar{\psi}P\gamma^\mu\mathcal{V}\psi_\mu$	
$F123\ F213\ F132\ F231\ F312\ F321$:	$\psi_\mu \leftarrow \mathcal{V}\gamma_\mu P\psi$
$F423\ F243\ F432\ F234\ F342\ F324$:	$\psi \leftarrow \gamma^\mu\mathcal{V}P\psi_\mu$
$F134\ F143\ F314$:	$P \leftarrow \psi^T C \gamma^\mu\mathcal{V}\psi_\mu$
$F124\ F142\ F214$:	$V_\mu \leftarrow \psi^T C P \gamma^\rho \gamma_\mu \psi_\rho$
$F413\ F431\ F341$:	$P \leftarrow \psi_\mu^T C \mathcal{V}\gamma^\mu\psi$
$F412\ F421\ F241$:	$V_\mu \leftarrow \psi_\rho^T C P \gamma_\mu \gamma^\rho \psi$
<i>GBBG</i> (<i>Psibar</i> , <i>V2</i> , <i>Grav</i>): $\bar{\psi}f_{abc}\gamma^5\gamma^\mu[V^a, \mathcal{V}^b]\psi_\mu$	
$F123\ F213\ F132\ F231\ F312\ F321$:	$\psi_\mu \leftarrow f_{abc}[V^a, \mathcal{V}^b]\gamma_\mu\gamma^5\psi$
$F423\ F243\ F432\ F234\ F342\ F324$:	$\psi \leftarrow f_{abc}\gamma^5\gamma^\mu[V^a, \mathcal{V}^b]\psi_\mu$
$F134\ F143\ F314\ F124\ F142\ F214$:	$V_\mu^a \leftarrow \psi^T C f_{abc}\gamma^5\gamma^\rho[\gamma_\mu, \mathcal{V}^b]\psi_\rho$
$F413\ F431\ F341\ F412\ F421\ F241$:	$V_\mu^a \leftarrow \psi_\rho^T C f_{abc}[\gamma_\mu, \mathcal{V}^b]\gamma^\rho\gamma^5\psi$


Table 9.31: Dimension-5 trilinear couplings including one conjugated Dirac, one Gravitino fermion and two additional bosons. The couplings of Majorana fermions to the gravitino and two bosons are essentially the same as for Dirac fermions and they are omitted here.



$$= -i\frac{\kappa}{2}g_{\mu\nu}m^2 + i\frac{\kappa}{2}C_{\mu\nu,\mu_1\mu_2}k_1^{\mu_1}k_2^{\mu_2} \quad (9.27a)$$



$$= -i\frac{\kappa}{2}m^2C_{\mu\nu,\mu_1\mu_2} - i\frac{\kappa}{2}(k_1k_2C_{\mu\nu,\mu_1\mu_2} + D_{\mu\nu,\mu_1\mu_2}(k_1, k_2) + \xi^{-1}E_{\mu\nu,\mu_1\mu_2}(k_1, k_2)) \quad (9.27b)$$



$$= -i\frac{\kappa}{2}mg_{\mu\nu} - i\frac{\kappa}{8}(\gamma_\mu(p+p')_\nu + \gamma_\nu(p+p')_\mu - 2g_{\mu\nu}(\not{p} + \not{p}')) \quad (9.27c)$$

Figure 9.3: Three-point graviton couplings.

where $n = d - 4$ is the number of extra space dimensions.

In (9.27-9.34), we use the notation of [13]:

$$C_{\mu\nu,\rho\sigma} = g_{\mu\rho}g_{\nu\sigma} + g_{\mu\sigma}g_{\nu\rho} - g_{\mu\nu}g_{\rho\sigma} \quad (9.26a)$$

$$D_{\mu\nu,\rho\sigma}(k_1, k_2) = g_{\mu\nu}k_{1,\sigma}k_{2,\rho} - (g_{\mu\sigma}k_{1,\nu}k_{2,\rho} + g_{\mu\rho}k_{1,\sigma}k_{2,\nu} - g_{\rho\sigma}k_{1,\mu}k_{2,\nu} + (\mu \leftrightarrow \nu)) \quad (9.26b)$$

$$E_{\mu\nu,\rho\sigma}(k_1, k_2) = g_{\mu\nu}(k_{1,\rho}k_{1,\sigma} + k_{2,\rho}k_{2,\sigma} + k_{1,\rho}k_{2,\sigma}) - (g_{\nu\sigma}k_{1,\mu}k_{1,\rho} + g_{\nu\rho}k_{2,\mu}k_{2,\sigma} + (\mu \leftrightarrow \nu)) \quad (9.26c)$$

$$F_{\mu\nu,\rho\sigma\lambda}(k_1, k_2, k_3) = g_{\mu\rho}g_{\sigma\lambda}(k_2 - k_3)_\nu + g_{\mu\sigma}g_{\lambda\rho}(k_3 - k_1)_\nu + g_{\mu\lambda}g_{\rho\sigma}(k_1 - k_2)_\nu + (\mu \leftrightarrow \nu) \quad (9.26d)$$

$$G_{\mu\nu,\rho\sigma\lambda\delta} = g_{\mu\nu}(g_{\rho\sigma}g_{\lambda\delta} - g_{\rho\delta}g_{\lambda\sigma}) + (g_{\mu\rho}g_{\nu\delta}g_{\lambda\sigma} + g_{\mu\lambda}g_{\nu\sigma}g_{\rho\delta} - g_{\mu\rho}g_{\nu\sigma}g_{\lambda\delta} - g_{\mu\lambda}g_{\nu\delta}g_{\rho\sigma} + (\mu \leftrightarrow \nu)) \quad (9.26e)$$

Derivation of (9.27a)

<i>Graviton_Scalar_Scalar:</i> $h_{\mu\nu}C_0^{\mu\nu}(k_1, k_2)\phi_1\phi_2$	
<i>F12</i> <i>F21:</i>	$\phi_2 \leftarrow i \cdot h_{\mu\nu}C_0^{\mu\nu}(k_1, -k - k_1)\phi_1$
<i>F13</i> <i>F31:</i>	$\phi_1 \leftarrow i \cdot h_{\mu\nu}C_0^{\mu\nu}(-k - k_2, k_2)\phi_2$
<i>F23</i> <i>F32:</i>	$h^{\mu\nu} \leftarrow i \cdot C_0^{\mu\nu}(k_1, k_2)\phi_1\phi_2$
<i>Graviton_Vector_Vector:</i> $h_{\mu\nu}C_1^{\mu\nu, \mu_1\mu_2}(k_1, k_2, \xi)V_{\mu_1}V_{\mu_2}$	
<i>F12</i> <i>F21:</i>	$V_2^\mu \leftarrow i \cdot h_{\kappa\lambda}C_1^{\kappa\lambda, \mu\nu}(-k - k_1, k_1\xi)V_{1,\nu}$
<i>F13</i> <i>F31:</i>	$V_1^\mu \leftarrow i \cdot h_{\kappa\lambda}C_1^{\kappa\lambda, \mu\nu}(-k - k_2, k_2, \xi)V_{2,\nu}$
<i>F23</i> <i>F32:</i>	$h^{\mu\nu} \leftarrow i \cdot C_1^{\mu\nu, \mu_1\mu_2}(k_1, k_2, \xi)V_{1,\mu_1}V_{2,\mu_2}$
<i>Graviton_Spinor_Spinor:</i> $h_{\mu\nu}\bar{\psi}_1C_{\frac{1}{2}}^{\mu\nu}(k_1, k_2)\psi_2$	
<i>F12:</i>	$\bar{\psi}_2 \leftarrow i \cdot h_{\mu\nu}\bar{\psi}_1C_{\frac{1}{2}}^{\mu\nu}(k_1, -k - k_1)$
<i>F21:</i>	$\bar{\psi}_2 \leftarrow i \cdot \dots$
<i>F13:</i>	$\psi_1 \leftarrow i \cdot h_{\mu\nu}C_{\frac{1}{2}}^{\mu\nu}(-k - k_2, k_2)\psi_2$
<i>F31:</i>	$\psi_1 \leftarrow i \cdot \dots$
<i>F23:</i>	$h^{\mu\nu} \leftarrow i \cdot \bar{\psi}_1C_{\frac{1}{2}}^{\mu\nu}(k_1, k_2)\psi_2$
<i>F32:</i>	$h^{\mu\nu} \leftarrow i \cdot \dots$

Table 9.32: ...

$$\begin{aligned}
 \phi(k) \cdots \bullet & \begin{array}{l} \nearrow 1 \\ \searrow 2 \end{array} = -i\omega\kappa 2m^2 - i\omega\kappa k_1 k_2 & (9.30a) \\
 \phi(k) \cdots \bullet & \begin{array}{l} \nearrow 1 \\ \searrow 2 \end{array} = -i\omega\kappa g_{\mu_1\mu_2} m^2 - i\omega\kappa \xi^{-1} (k_{1,\mu_1} k_{\mu_2} + k_{2,\mu_2} k_{\mu_1}) & (9.30b) \\
 \phi(k) \cdots \bullet & \begin{array}{l} \nearrow p \\ \searrow p' \end{array} = -i\omega\kappa 2m + i\omega\kappa \frac{3}{4} (\not{p} + \not{p}') & (9.30c)
 \end{aligned}$$

Figure 9.4: Three-point dilaton couplings.

$$L = \frac{1}{2}(\partial_\mu \phi)(\partial^\mu \phi) - \frac{m^2}{2}\phi^2 \quad (9.28a)$$

$$(\partial_\mu \phi) \frac{\partial L}{\partial(\partial^\nu \phi)} = (\partial_\mu \phi)(\partial_\nu \phi) \quad (9.28b)$$

$$T_{\mu\nu} = -g_{\mu\nu}L + (\partial_\mu \phi) \frac{\partial L}{\partial(\partial^\nu \phi)} + \quad (9.28c)$$

$$C_0^{\mu\nu}(k_1, k_2) = C^{\mu\nu, \mu_1\mu_2} k_{1,\mu_1} k_{2,\mu_2} \quad (9.29a)$$

$$C_1^{\mu\nu, \mu_1\mu_2}(k_1, k_2, \xi) = k_1 k_2 C^{\mu\nu, \mu_1\mu_2} + D^{\mu\nu, \mu_1\mu_2}(k_1, k_2) + \xi^{-1} E^{\mu\nu, \mu_1\mu_2}(k_1, k_2) \quad (9.29b)$$

$$C_{\frac{1}{2}, \alpha\beta}^{\mu\nu}(p, p') = \gamma_{\alpha\beta}^\mu (p + p')^\nu + \gamma_{\alpha\beta}^\nu (p + p')^\mu - 2g^{\mu\nu} (\not{p} + \not{p}')_{\alpha\beta} \quad (9.29c)$$

9.1.8 Dependent Parameters

This is a simple abstract syntax for parameter dependencies. Later, there will be a parser for a convenient concrete syntax as a part of a concrete syntax for models. There is no intention to do *any* symbolic manipulation with this. The expressions will be translated directly by *Targets* to the target language.

<i>Dilaton_Scalar_Scalar</i> : $\phi \dots k_1 k_2 \phi_1 \phi_2$
$F12 \mid F21$: $\phi_2 \leftarrow i \cdot k_1 (-k - k_1) \phi \phi_1$
$F13 \mid F31$: $\phi_1 \leftarrow i \cdot (-k - k_2) k_2 \phi \phi_2$
$F23 \mid F32$: $\phi \leftarrow i \cdot k_1 k_2 \phi_1 \phi_2$
<i>Dilaton_Vector_Vector</i> : $\phi \dots$
$F12$: $V_{2,\mu} \leftarrow i \cdot \dots$
$F21$: $V_{2,\mu} \leftarrow i \cdot \dots$
$F13$: $V_{1,\mu} \leftarrow i \cdot \dots$
$F31$: $V_{1,\mu} \leftarrow i \cdot \dots$
$F23$: $\phi \leftarrow i \cdot \dots$
$F32$: $\phi \leftarrow i \cdot \dots$
<i>Dilaton_Spinor_Spinor</i> : $\phi \dots$
$F12$: $\bar{\psi}_2 \leftarrow i \cdot \dots$
$F21$: $\bar{\psi}_2 \leftarrow i \cdot \dots$
$F13$: $\psi_1 \leftarrow i \cdot \dots$
$F31$: $\psi_1 \leftarrow i \cdot \dots$
$F23$: $\phi \leftarrow i \cdot \dots$
$F32$: $\phi \leftarrow i \cdot \dots$

Table 9.33: ...

$$\begin{aligned}
& \text{Diagram 1} = \text{Diagram 2} \quad ??? \quad (9.31a) \\
& \text{Diagram 3} = -ig \frac{\kappa}{2} C_{\mu\nu, \mu_3 \rho} (k_1 - k_2)^\rho T_{n_2 n_1}^{a_3} \quad (9.31b) \\
& \text{Diagram 4} = \text{Diagram 5} \quad ??? \quad (9.31c) \\
& \text{Diagram 6} = -g \frac{\kappa}{2} f^{a_1 a_2 a_3} (C_{\mu\nu, \mu_1 \mu_2} (k_1 - k_2)_{\mu_3} \\
& \quad + C_{\mu\nu, \mu_2 \mu_3} (k_2 - k_3)_{\mu_1} \quad (9.31d) \\
& \quad + C_{\mu\nu, \mu_3 \mu_1} (k_3 - k_1)_{\mu_2} \\
& \quad + F_{\mu\nu, \mu_1 \mu_2 \mu_3} (k_1, k_2, k_3)) \\
& \text{Diagram 7} = \text{Diagram 8} \quad ??? \quad (9.31e) \\
& \text{Diagram 9} = ig \frac{\kappa}{4} (C_{\mu\nu, \mu_3 \rho} - g_{\mu\nu} g_{\mu_3 \rho}) \gamma^\rho T_{n_2 n_1}^{a_3} \quad (9.31f)
\end{aligned}$$

Figure 9.5: Four-point graviton couplings. (9.31a), (9.31c), and (?? are missing in [13], but should be generated by standard model Higgs selfcouplings, Higgs-gaugeboson couplings, and Yukawa couplings.

(9.32a) $= ???$

(9.32b) $= -i\omega\kappa(k_1 + k_2)_{\mu_3} T_{n_1, n_2}^{a_3}$

(9.32c) $= ???$

(9.32d) $= 0$

(9.32e) $= ???$

(9.32f) $= -i\frac{3}{2}\omega g\kappa\gamma_{\mu_3} T_{n_1 n_2}^{a_3}$

Figure 9.6: Four-point dilaton couplings. (9.32a), (9.32c) and (9.32e) are missing in [13], but could be generated by standard model Higgs selfcouplings, Higgs-gaugeboson couplings, and Yukawa couplings.

$$\begin{array}{ccc}
\begin{array}{c} 1 \\ \diagup \\ \bullet \\ \diagdown \\ 4 \end{array} & \begin{array}{c} 2 \\ \diagup \\ \bullet \\ \diagdown \\ 3 \end{array} & \\
h_{\mu\nu} \cdots \cdots & & \\
\end{array} = \quad ???
\end{array}
\tag{9.33a}$$


$$\begin{array}{ccc}
\begin{array}{c} 1 \\ \diagup \\ \bullet \\ \diagdown \\ 4 \end{array} & \begin{array}{c} 2 \\ \diagup \\ \bullet \\ \diagdown \\ 3 \end{array} & \\
h_{\mu\nu} \cdots \cdots & & \\
\end{array} = \quad -ig^2 \frac{\kappa}{2} C_{\mu\nu, \mu_3 \mu_4} (T^{a_3} T^{a_4} + T^{a_4} T^{a_3})_{n_2 n_1}
\end{array}
\tag{9.33b}$$

$$\begin{array}{ccc}
\begin{array}{c} 1 \\ \diagup \\ \bullet \\ \diagdown \\ 4 \end{array} & \begin{array}{c} 2 \\ \diagup \\ \bullet \\ \diagdown \\ 3 \end{array} & \\
h_{\mu\nu} \cdots \cdots & & \\
\end{array} = \quad -ig^2 \frac{\kappa}{2} (f^{ba_1 a_3} f^{ba_2 a_4} G_{\mu\nu, \mu_1 \mu_2 \mu_3 \mu_4} \\
& + f^{ba_1 a_2} f^{ba_3 a_4} G_{\mu\nu, \mu_1 \mu_3 \mu_2 \mu_4} \\
& + f^{ba_1 a_4} f^{ba_2 a_3} G_{\mu\nu, \mu_1 \mu_2 \mu_4 \mu_3})
\end{array}
\tag{9.33c}$$

Figure 9.7: Five-point graviton couplings. (9.33a) is missing in [13], but should be generated by standard model Higgs selfcouplings.



$$(9.34a) \quad = ???$$



$$(9.34b) \quad = i\omega g^2 \kappa g_{\mu_3 \mu_4} (T^{a_3} T^{a_4} + T^{a_4} T^{a_3})_{n_2 n_1}$$



$$(9.34c) \quad = 0$$

Figure 9.8: Five-point dilaton couplings. (9.34a) is missing in [13], but could be generated by standard model Higgs selfcouplings.

```

type  $\alpha$  expr =
  | I | Const of int
  | Atom of  $\alpha$ 
  | Sum of  $\alpha$  expr list
  | Diff of  $\alpha$  expr  $\times$   $\alpha$  expr
  | Neg of  $\alpha$  expr
  | Prod of  $\alpha$  expr list
  | Quot of  $\alpha$  expr  $\times$   $\alpha$  expr
  | Rec of  $\alpha$  expr
  | Pow of  $\alpha$  expr  $\times$  int
  | Sqrt of  $\alpha$  expr
  | Sin of  $\alpha$  expr
  | Cos of  $\alpha$  expr
  | Tan of  $\alpha$  expr
  | Cot of  $\alpha$  expr
  | Atan2 of  $\alpha$  expr  $\times$   $\alpha$  expr
  | Conj of  $\alpha$  expr

type  $\alpha$  variable = Real of  $\alpha$  | Complex of  $\alpha$ 
type  $\alpha$  variable_array = Real_Array of  $\alpha$  | Complex_Array of  $\alpha$ 

type  $\alpha$  parameters =
  { input : ( $\alpha \times$  float) list;
    derived : ( $\alpha$  variable  $\times$   $\alpha$  expr) list;
    derived_arrays : ( $\alpha$  variable_array  $\times$   $\alpha$  expr list) list }

```


<i>Dim5_Scalar_Vector_Vector_T</i> : $\mathcal{L}_I = g\phi(i\partial_\mu V_1^\nu)(i\partial_\nu V_2^\mu)$
<i>F23</i> : $\phi(k_2 + k_3) \leftarrow i \cdot g k_3^\mu V_{1,\mu}(k_2) k_2^\nu V_{2,\nu}(k_3)$
<i>F32</i> : $\phi(k_2 + k_3) \leftarrow i \cdot g k_2^\mu V_{2,\mu}(k_3) k_3^\nu V_{1,\nu}(k_2)$
<i>F12</i> : $V_2^\mu(k_1 + k_2) \leftarrow i \cdot g k_2^\mu \phi(k_1) (-k_1^\nu - k_2^\nu) V_{1,\nu}(k_2)$
<i>F21</i> : $V_2^\mu(k_1 + k_2) \leftarrow i \cdot g k_2^\mu (-k_1^\nu - k_2^\nu) V_{1,\nu}(k_2) \phi(k_1)$
<i>F13</i> : $V_1^\mu(k_1 + k_3) \leftarrow i \cdot g k_3^\mu \phi(k_1) (-k_1^\nu - k_3^\nu) V_{2,\nu}(k_3)$
<i>F31</i> : $V_1^\mu(k_1 + k_3) \leftarrow i \cdot g k_3^\mu (-k_1^\nu - k_3^\nu) V_{2,\nu}(k_3) \phi(k_1)$

Table 9.34: ...

<i>Dim6_Vector_Vector_Vector_T</i> : $\mathcal{L}_I = gV_1^\mu((i\partial_\nu V_2^\rho) i\overleftrightarrow{\partial}_\mu (i\partial_\rho V_3^\nu))$
<i>F23</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g(k_2^\mu - k_3^\mu) k_3^\nu V_{2,\nu}(k_2) k_2^\rho V_{3,\rho}(k_3)$
<i>F32</i> : $V_1^\mu(k_2 + k_3) \leftarrow i \cdot g(k_2^\mu - k_3^\mu) k_2^\nu V_{3,\nu}(k_3) k_3^\rho V_{2,\rho}(k_2)$
<i>F12</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g k_2^\mu (k_1^\nu + 2k_2^\nu) V_{1,\nu}(k_1) (-k_1^\rho - k_2^\rho) V_{2,\rho}(k_2)$
<i>F21</i> : $V_3^\mu(k_1 + k_2) \leftarrow i \cdot g k_2^\mu (-k_1^\rho - k_2^\rho) V_{2,\rho}(k_2) (k_1^\nu + 2k_2^\nu) V_{1,\nu}(k_1)$
<i>F13</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g k_3^\mu (k_1^\nu + 2k_3^\nu) V_{1,\nu}(k_1) (-k_1^\rho - k_3^\rho) V_{3,\rho}(k_3)$
<i>F31</i> : $V_2^\mu(k_1 + k_3) \leftarrow i \cdot g k_3^\mu (-k_1^\rho - k_3^\rho) V_{3,\rho}(k_3) (k_1^\nu + 2k_3^\nu) V_{1,\nu}(k_1)$

Table 9.35: ...

9.1.9 More Exotic Couplings

9.2 Interface of *Model*

9.2.1 General Quantum Field Theories

module type *T* =

sig

flavor abstractly encodes all quantum numbers.

type *flavor*

Color.t encodes the $(\text{SU}(N))$ color representation.

val *color* : *flavor* \rightarrow *Color.t*

The set of conserved charges.

module *Ch* : *Charges.T*

val *charges* : *flavor* \rightarrow *Ch.t*

The PDG particle code for interfacing with Monte Carlos.

<i>Tensor_2_Vector_Vector</i> : $\mathcal{L}_I = gT^{\mu\nu}(V_{1,\mu}V_{2,\nu} + V_{1,\nu}V_{2,\mu})$
<i>F23</i> : $T^{\mu\nu}(k_2 + k_3) \leftarrow i \cdot g(V_{1,\mu}(k_2)V_{2,\nu}(k_3) + V_{1,\nu}(k_2)V_{2,\mu}(k_3))$
<i>F32</i> : $T^{\mu\nu}(k_2 + k_3) \leftarrow i \cdot g(V_{2,\nu}(k_3)V_{1,\mu}(k_2) + V_{2,\mu}(k_3)V_{1,\nu}(k_2))$
<i>F12</i> : $V_2^\mu(k_1 + k_2) \leftarrow i \cdot g(T^{\mu\nu}(k_1) + T^{\nu\mu}(k_1))V_{1,\nu}(k_2)$
<i>F21</i> : $V_2^\mu(k_1 + k_2) \leftarrow i \cdot gV_{1,\nu}(k_2)(T^{\mu\nu}(k_1) + T^{\nu\mu}(k_1))$
<i>F13</i> : $V_1^\mu(k_1 + k_3) \leftarrow i \cdot g(T^{\mu\nu}(k_1) + T^{\nu\mu}(k_1))V_{2,\nu}(k_3)$
<i>F31</i> : $V_1^\mu(k_1 + k_3) \leftarrow i \cdot gV_{2,\nu}(k_3)(T^{\mu\nu}(k_1) + T^{\nu\mu}(k_1))$

Table 9.36: ...

<i>Dim5_Tensor_2_Vector_Vector_1</i> : $\mathcal{L}_I = gT^{\alpha\beta}(V_1^\mu i \overset{\leftrightarrow}{\partial}_\alpha i \overset{\leftrightarrow}{\partial}_\beta V_{2,\mu})$
<i>F23</i> : $T^{\alpha\beta}(k_2 + k_3) \leftarrow i \cdot g(k_2^\alpha - k_3^\alpha)(k_2^\beta - k_3^\beta)V_1^\mu(k_2)V_{2,\mu}(k_3)$
<i>F32</i> : $T^{\alpha\beta}(k_2 + k_3) \leftarrow i \cdot g(k_2^\alpha - k_3^\alpha)(k_2^\beta - k_3^\beta)V_{2,\mu}(k_3)V_1^\mu(k_2)$
<i>F12</i> : $V_2^\mu(k_1 + k_2) \leftarrow i \cdot g(k_1^\alpha + 2k_2^\alpha)(k_1^\beta + 2k_2^\beta)T_{\alpha\beta}(k_1)V_1^\mu(k_2)$
<i>F21</i> : $V_2^\mu(k_1 + k_2) \leftarrow i \cdot g(k_1^\alpha + 2k_2^\alpha)(k_1^\beta + 2k_2^\beta)V_1^\mu(k_2)T_{\alpha\beta}(k_1)$
<i>F13</i> : $V_1^\mu(k_1 + k_3) \leftarrow i \cdot g(k_1^\alpha + 2k_3^\alpha)(k_1^\beta + 2k_3^\beta)T_{\alpha\beta}(k_1)V_2^\mu(k_3)$
<i>F31</i> : $V_1^\mu(k_1 + k_3) \leftarrow i \cdot g(k_1^\alpha + 2k_3^\alpha)(k_1^\beta + 2k_3^\beta)V_2^\mu(k_3)T_{\alpha\beta}(k_1)$

Table 9.37: ...

<i>Dim5_Tensor_2_Vector_Vector_2</i> : $\mathcal{L}_I = gT^{\alpha\beta}(V_1^\mu i \overset{\leftrightarrow}{\partial}_\beta (i\partial_\mu V_{2,\alpha}) + V_1^\mu i \overset{\leftrightarrow}{\partial}_\alpha (i\partial_\mu V_{2,\beta}))$
<i>F23</i> : $T^{\alpha\beta}(k_2 + k_3) \leftarrow i \cdot g(k_3^\beta - k_2^\beta)k_3^\mu V_{1,\mu}(k_2)V_2^\alpha(k_3) + (\alpha \leftrightarrow \beta)$
<i>F32</i> : $T^{\alpha\beta}(k_2 + k_3) \leftarrow i \cdot g(k_3^\beta - k_2^\beta)V_2^\alpha(k_3)k_3^\mu V_{1,\mu}(k_2) + (\alpha \leftrightarrow \beta)$
<i>F12</i> : $V_2^\alpha(k_1 + k_2) \leftarrow i \cdot g(k_1^\beta + 2k_2^\beta)(T^{\alpha\beta}(k_1) + T^{\beta\alpha}(k_1))(k_1^\mu + k_2^\mu)V_{1,\mu}(k_2)$
<i>F21</i> : $V_2^\alpha(k_1 + k_2) \leftarrow i \cdot g(k_1^\mu + k_2^\mu)V_{1,\mu}(k_2)(k_1^\beta + 2k_2^\beta)(T^{\alpha\beta}(k_1) + T^{\beta\alpha}(k_1))$
<i>F13</i> : $V_1^\alpha(k_1 + k_3) \leftarrow i \cdot g(k_1^\beta + 2k_3^\beta)(T^{\alpha\beta}(k_1) + T^{\beta\alpha}(k_1))(k_1^\mu + k_3^\mu)V_{2,\mu}(k_3)$
<i>F31</i> : $V_1^\alpha(k_1 + k_3) \leftarrow i \cdot g(k_1^\mu + k_3^\mu)V_{2,\mu}(k_3)(k_1^\beta + 2k_3^\beta)(T^{\alpha\beta}(k_1) + T^{\beta\alpha}(k_1))$

Table 9.38: ...

<i>Dim7_Tensor_2_Vector_Vector_T</i> : $\mathcal{L}_I = gT^{\alpha\beta}((i\partial^\mu V_1^\nu)i\overleftrightarrow{\partial}_\alpha i\overleftrightarrow{\partial}_\beta(i\partial_\nu V_{2,\mu}))$
<i>F23</i> : $T^{\alpha\beta}(k_2 + k_3) \leftarrow i \cdot g(k_2^\alpha - k_3^\alpha)(k_2^\beta - k_3^\beta)k_3^\mu V_{1,\mu}(k_2)k_2^\nu V_{2,\nu}(k_3)$
<i>F32</i> : $T^{\alpha\beta}(k_2 + k_3) \leftarrow i \cdot g(k_2^\alpha - k_3^\alpha)(k_2^\beta - k_3^\beta)k_2^\nu V_{2,\nu}(k_3)k_3^\mu V_{1,\mu}(k_2)$
<i>F12</i> : $V_2^\mu(k_1 + k_2) \leftarrow i \cdot gk_2^\mu(k_1^\alpha + 2k_2^\alpha)(k_1^\beta + 2k_2^\beta)T_{\alpha\beta}(k_1)(-k_1^\nu - k_2^\nu)V_{1,\nu}(k_2)$
<i>F21</i> : $V_2^\mu(k_1 + k_2) \leftarrow i \cdot gk_2^\mu(-k_1^\nu - k_2^\nu)V_{1,\nu}(k_2)(k_1^\alpha + 2k_2^\alpha)(k_1^\beta + 2k_2^\beta)T_{\alpha\beta}(k_1)$
<i>F13</i> : $V_1^\mu(k_1 + k_3) \leftarrow i \cdot gk_3^\mu(k_1^\alpha + 2k_3^\alpha)(k_1^\beta + 2k_3^\beta)T_{\alpha\beta}(k_1)(-k_1^\nu - k_3^\nu)V_{2,\nu}(k_3)$
<i>F31</i> : $V_1^\mu(k_1 + k_3) \leftarrow i \cdot gk_3^\mu(-k_1^\nu - k_3^\nu)V_{2,\nu}(k_3)(k_1^\alpha + 2k_3^\alpha)(k_1^\beta + 2k_3^\beta)T_{\alpha\beta}(k_1)$

Table 9.39: ...

val pdg : *flavor* → *int*

The Lorentz representation of the particle.

val lorentz : *flavor* → *Coupling.lorentz*

The propagator for the particle, which *can* depend on a gauge parameter.

type gauge

val propagator : *flavor* → *gauge Coupling.propagator*

Not the symbol for the numerical value, but the scheme or strategy.

val width : *flavor* → *Coupling.width*

Charge conjugation, with and without color.

val conjugate : *flavor* → *flavor*

Returns 1 for fermions, −1 for anti-fermions, 2 for Majoranas and 0 otherwise.

val fermion : *flavor* → *int*

The Feynman rules. *vertices* and (*fuse2*, *fuse3*, *fusen*) are redundant, of course. However, *vertices* is required for building functors for models and *vertices* can be recovered from (*fuse2*, *fuse3*, *fusen*) only at great cost.



Nevertheless: *vertices* is a candidate for removal, b/c we can build a smarter *Colorize* functor acting on (*fuse2*, *fuse3*, *fusen*). It can support an arbitrary number of color lines. But we have to test whether it is efficient enough.

type constant

type orders

val max_degree : *unit* → *int*

val vertices : *unit* →

$(((((\text{flavor} \times \text{flavor} \times \text{flavor}) \times \text{constant Coupling.vertex3} \times \text{constant}) \text{ list})$
 $\times (((\text{flavor} \times \text{flavor} \times \text{flavor} \times \text{flavor}) \times \text{constant Coupling.vertex4} \times$
 $\text{constant}) \text{ list}))$
 $\times (((\text{flavor list}) \times \text{constant Coupling.vertexn} \times \text{constant}) \text{ list}))$

val fuse2 : *flavor* → *flavor* → (*flavor* × *constant Coupling.t*) *list*

val fuse3 : *flavor* → *flavor* → *flavor* → (*flavor* × *constant Coupling.t*) *list*

```
val fuse : flavor list → (flavor × constant Coupling.t) list
val orders : constant → orders
```

The list of all known flavors.

```
val flavors : unit → flavor list
```

The flavors that can appear in incoming or outgoing states, grouped in a way that is useful for user interfaces.

```
val external_flavors : unit → (string × flavor list) list
```

The Goldstone bosons corresponding to a gauge field, if any.

```
val goldstone : flavor → (flavor × constant Coupling.expr) option
```

The dependent parameters.

```
val parameters : unit → constant Coupling.parameters
```

Translate from and to convenient textual representations of flavors.

```
val flavor_of_string : string → flavor
val flavor_to_string : flavor → string
```

TeX and L^AT_EX

```
val flavor_to_TeX : flavor → string
```

The following must return unique symbols that are acceptable as symbols in all programming languages under consideration as targets. Strings of alphanumeric characters (starting with a letter) should be safe. Underscores are also usable, but would violate strict Fortran77.

```
val flavor_symbol : flavor → string
val gauge_symbol : gauge → string
val mass_symbol : flavor → string
val width_symbol : flavor → string
val constant_symbol : constant → string
```

Model specific options.

```
val options : Options.t
```

Revision control information.

```
val rcs : RCS.t
```

```
end
```

In addition to hardcoded models, we can have models that are initialized at run time.

9.2.2 Mutable Quantum Field Theories

```
module type Mutable =
```

```
sig
  include T
```

Export only one big initialization function to discourage partial initializations. Labels make this usable.

```

val setup :
  color : (flavor → Color.t) →
  pdg : (flavor → int) →
  lorentz : (flavor → Coupling.lorentz) →
  propagator : (flavor → gauge Coupling.propagator) →
  width : (flavor → Coupling.width) →
  goldstone : (flavor → (flavor × constant Coupling.expr) option) →
  conjugate : (flavor → flavor) →
  fermion : (flavor → int) →
  max_degree : int →
  vertices : (unit →
    (((flavor × flavor × flavor) × constant Coupling.vertex3 ×
    constant) list)
    × (((flavor × flavor × flavor × flavor) × constant Coupling.vertex4 ×
    constant) list)
    × (((flavor list) × constant Coupling.vertexn × constant) list))) →

  fuse : ((flavor → flavor → (flavor × constant Coupling.t) list)
    × (flavor → flavor → flavor →
      (flavor × constant Coupling.t) list)
    × (flavor list → (flavor × constant Coupling.t) list)) →
  flavors : ((string × flavor list) list) →
  parameters : (unit → constant Coupling.parameters) →
  flavor_of_string : (string → flavor) →
  flavor_to_string : (flavor → string) →
  flavor_to_TeX : (flavor → string) →
  flavor_symbol : (flavor → string) →
  gauge_symbol : (gauge → string) →
  mass_symbol : (flavor → string) →
  width_symbol : (flavor → string) →
  constant_symbol : (constant → string) →
  unit
end

```

9.2.3 Gauge Field Theories

The following signatures are used only for model building. The diagrammatics and numerics is supposed to be completely ignorant about the detail of the models and expected to rely on the interface *T* exclusively.



In the end, we might have functors $(M : T) \rightarrow \text{Gauge}$, but we will need to add the quantum numbers to *T*.

```

module type Gauge =
  sig
    include T

```

Matter field carry conserved quantum numbers and can be replicated in generations without changing the gauge sector.

```
type matter_field
```

Gauge bosons proper.

```
type gauge_boson
```

Higgses, Goldstones and all the rest:

```
type other
```

We can query the kind of field

```
type field =
  | Matter of matter_field
  | Gauge of gauge_boson
  | Other of other
val field : flavor → field
```

and we can build new fields of a given kind:

```
val matter_field : matter_field → flavor
val gauge_boson : gauge_boson → flavor
val other : other → flavor
end
```

9.2.4 Gauge Field Theories with Broken Gauge Symmetries

Both are carefully crafted as subtypes of *Gauge* so that they can be used in place of *Gauge* and *T* everywhere:

```
module type Broken_Gauge =
sig
  include Gauge

  type massless
  type massive
  type goldstone

  type kind =
    | Massless of massless
    | Massive of massive
    | Goldstone of goldstone
  val kind : gauge_boson → kind

  val massless : massive → gauge_boson
  val massive : massive → gauge_boson
  val goldstone : goldstone → gauge_boson
end

module type Unitarity_Gauge =
sig
  include Gauge
```

```

type massless
type massive

type kind =
  | Massless of massless
  | Massive of massive
val kind : gauge_boson → kind

val massless : massive → gauge_boson
val massive : massive → gauge_boson

end

module type Colorized =
sig
  include T

  type flavor_sans_color
  val flavor_sans_color : flavor → flavor_sans_color
  val conjugate_sans_color : flavor_sans_color → flavor_sans_color

  val nc : unit → int
  val amplitude : flavor_sans_color list → flavor_sans_color list →
    (flavor list × flavor list) list
  val flow : flavor list → flavor list → Color.Flow.t

end

module type Colorized_Gauge =
sig
  include Gauge

  type flavor_sans_color
  val flavor_sans_color : flavor → flavor_sans_color
  val conjugate_sans_color : flavor_sans_color → flavor_sans_color

  val nc : unit → int
  val amplitude : flavor_sans_color list → flavor_sans_color list →
    (flavor list × flavor list) list
  val flow : flavor list → flavor list → Color.Flow.t

end

```



Interface *vertex.mli* unavailable!



Implementation *vertex.ml* unavailable!

9.3 Interface of *Target*

```

module type T =
sig
  type amplitudes
  val options : Options.t

```

```
type diagnostic = All | Arguments | Momenta | Gauge
```

Format the amplitudes as a sequence of strings.

```
val amplitudes_to_channel : string → out_channel →  
  (diagnostic × bool) list → amplitudes → unit
```

```
val parameters_to_channel : out_channel → unit
```

```
val rsc_list : RCS.t list
```

```
end
```

```
module type Maker =
```

```
  functor (F : Fusion.Maker) →
```

```
    functor (P : Momentum.T) → functor (M : Model.T) →  
      T with type amplitudes = Fusion.Multi(F)(P)(M).amplitudes
```

—10—

CONSERVED QUANTUM NUMBERS

10.1 Interface of Charges

10.1.1 Abstract Type

```
module type T =  
  sig  
    The abstract type of the set of conserved charges or additive quantum  
    numbers.  
    type t  
    Add the quantum numbers of a pair or a list of particles.  
    val add : t → t → t  
    val sum : t list → t  
    Test the charge conservation.  
    val is_null : t → bool  
  end
```

10.1.2 Trivial Realisation

```
module Null : T with type t = unit
```

10.1.3 Nontrivial Realisations

Z

```
module Z : T with type t = int
```

$$\mathbf{Z} \times \mathbf{Z} \times \cdots \times \mathbf{Z}$$

```
module ZZ : T with type t = int list
```

$$\mathbf{Q}$$

```
module Q : T with type t = Algebra.Small_Rational.t
```

$$\mathbf{Q} \times \mathbf{Q} \times \cdots \times \mathbf{Q}$$

```
module QQ : T with type t = Algebra.Small_Rational.t list
```

10.2 Implementation of *Charges*

```
module type T =
  sig
    type t
    val add : t → t → t
    val sum : t list → t
    val is_null : t → bool
  end

module Null : T with type t = unit =
  struct
    type t = unit
    let add () () = ()
    let sum _ = ()
    let is_null _ = true
  end

module Z : T with type t = int =
  struct
    type t = int
    let add = ( + )
    let sum = List.fold_left add 0
    let is_null n = (n = 0)
  end

module ZZ : T with type t = int list =
  struct
    type t = int list
    let add = List.map2 ( + )
    let sum = function
      | [] → []
      | [charges] → charges
      | charges :: rest → List.fold_left add charges rest
    let is_null = List.for_all (fun n → n = 0)
```

```

end

module Rat = Algebra.Small_Rational

module Q : T with type t = Rat.t =
  struct
    type t = Rat.t
    let add = Rat.add
    let sum = List.fold_left Rat.add Rat.null
    let is_null = Rat.is_null
  end

module QQ : T with type t = Rat.t list =
  struct
    type t = Rat.t list
    let add = List.map2 Rat.add
    let sum = function
      | [] → []
      | [charges] → charges
      | charges :: rest → List.fold_left add charges rest
    let is_null = List.for_all Rat.is_null
  end
end

```

—11—

COLORIZATION

11.1 *Interface of Colorize*

11.1.1 ...

```
module It (M : Model.T) :  
  Model.Colorized with type flavor_sans_color = M.flavor  
  and type constant = M.constant and type orders = M.orders  
module Gauge (M : Model.Gauge) :  
  Model.Colorized_Gauge with type flavor_sans_color = M.flavor  
  and type constant = M.constant and type orders = M.orders
```

11.2 *Implementation of Colorize*

```
let rcs_file = RCS.parse "Colorize" ["Colorizing_Monochrome_Models"]  
{ RCS.revision = "$Revision: 4538$";  
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";  
  RCS.author = "$Author: jr-reuter$";  
  RCS.source  
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
```

11.2.1 *Colorizing a Monochrome Model*

```
module It (M : Model.T) =  
  struct  
    let rcs = RCS.rename rcs_file "Colorize.It()"  
      [ "Colorizing_Generic_Monochrome_Models"]  
    open Coupling  
    module C = Color  
    let incomplete s =  
      failwith ("Colorize.It()." ^ s ^ "_not_done_yet!")  
    let invalid s =
```

```

    invalid_arg ("Colorize.It()." ^ s ^ "must not be evaluated!")
let impossible s =
    invalid_arg ("Colorize.It()." ^ s ^ "can't happen!(but just did...)")
let su0 s =
    invalid_arg ("Colorize.It()." ^ s ^ ":found SU(0)!")
let colored_vertex s =
    invalid_arg ("Colorize.It()." ^ s ^ ":colored vertex!")
let baryonic_vertex s =
    invalid_arg ("Colorize.It()." ^ s ^
        ":baryonic(i.e. eps-ijk) vertices not supported yet!")
let color_flow_ambiguous s =
    invalid_arg ("Colorize.It()." ^ s ^ ":ambiguous color flow!")
let color_flow_of_string s =
    let c = int_of_string s in
    if c < 1 then
        invalid_arg ("Colorize.It()." ^ s ^ ":color flow # < 1!")
    else
        c
type cf_in = int
type cf_out = int
type flavor =
    | White of M.flavor
    | CF_in of M.flavor × cf_in
    | CF_out of M.flavor × cf_out
    | CF_io of M.flavor × cf_in × cf_out
    | CF_aux of M.flavor
type flavor_sans_color = M.flavor
let flavor_sans_color = function
    | White f → f
    | CF_in (f, _) → f
    | CF_out (f, _) → f
    | CF_io (f, -, _) → f
    | CF_aux f → f
let pullback f arg1 =
    f (flavor_sans_color arg1)
type gauge = M.gauge
type constant = M.constant
type orders = M.orders
let options = M.options
let color = pullback M.color
let pdg = pullback M.pdg
let lorentz = pullback M.lorentz
let orders = M.orders

```

```

module Ch = M.Ch
let charges = pullback M.charges

```

For the propagator we cannot use pullback because we have to add the case of the color singlet propagator by hand.

```

let cf_aux_propagator = function
| Prop_Scalar → Prop_Col_Scalar (* Spin 0 octets. *)
| Prop_Majorana → Prop_Col_Majorana (* Spin 1/2 octets. *)
| Prop_Feynman → Prop_Col_Feynman (* Spin 1 states, massless. *)
| Prop_Unitarity → Prop_Col_Unitarity (* Spin 1 states, massive. *)
| Aux_Scalar → Aux_Col_Scalar (* constant colored scalar propagator
*)
| Aux_Vector → Aux_Col_Vector (* constant colored vector propaga-
tor *)
| Aux_Tensor_1 → Aux_Col_Tensor_1 (* constant colored tensor
propagator *)
| Prop_Col_Scalar | Prop_Col_Feynman
| Prop_Col_Majorana | Prop_Col_Unitarity
| Aux_Col_Scalar | Aux_Col_Vector | Aux_Col_Tensor_1
→ failwith ("Colorize.It().colorize_propagator:_already_colored_particle!")
| _ → failwith ("Colorize.It().colorize_propagator:_impossible!")

let propagator = function
| CF_aux f → cf_aux_propagator (M.propagator f)
| White f → M.propagator f
| CF_in (f, _) → M.propagator f
| CF_out (f, _) → M.propagator f
| CF_io (f, -, _) → M.propagator f

let width = pullback M.width

let goldstone = function
| White f →
begin match M.goldstone f with
| None → None
| Some (f', g) → Some (White f', g)
end
| CF_in (f, c) →
begin match M.goldstone f with
| None → None
| Some (f', g) → Some (CF_in (f', c), g)
end
| CF_out (f, c) →
begin match M.goldstone f with
| None → None
| Some (f', g) → Some (CF_out (f', c), g)
end
| CF_io (f, c1, c2) →
begin match M.goldstone f with
| None → None
| Some (f', g) → Some (CF_io (f', c1, c2), g)
end

```

```

| CF_aux f →
  begin match M.goldstone f with
  | None → None
  | Some (f', g) → Some (CF_aux f', g)
  end

let conjugate = function
| White f → White (M.conjugate f)
| CF_in (f, c) → CF_out (M.conjugate f, c)
| CF_out (f, c) → CF_in (M.conjugate f, c)
| CF_io (f, c1, c2) → CF_io (M.conjugate f, c2, c1)
| CF_aux f → CF_aux (M.conjugate f)

let conjugate_sans_color = M.conjugate

let fermion = pullback M.fermion

let max_degree = M.max_degree

let flavors () =
  invalid "flavors"

let external_flavors () =
  invalid "external_flavors"

let parameters = M.parameters

module ISet = Set.Make (struct type t = int let compare = compare end)

let nc_value =
  let nc_set =
    List.fold_left
      (fun nc_set f →
        match M.color f with
        | C.Singlet → nc_set
        | C.SUN nc → ISet.add (abs nc) nc_set
        | C.AdjSUN nc → ISet.add (abs nc) nc_set)
      ISet.empty (M.flavors ()) in
  match ISet.elements nc_set with
  | [] → 0
  | [n] → n
  | nc_list →
    invalid_arg
      ("Colorize.It(): more than one value of N_C: " ^
       String.concat ", " (List.map string_of_int nc_list))

let nc () =
  nc_value

let split_color_string s =
  try
    let i1 = String.index s '/' in
    let i2 = String.index_from s (succ i1) '/' in
    let sf = String.sub s 0 i1
    and sc1 = String.sub s (succ i1) (i2 - i1 - 1)
    and sc2 = String.sub s (succ i2) (String.length s - i2 - 1) in

```

```

      (sf, sc1, sc2)
    with
    | Not_found → (s, "", "")
let flavor_of_string s =
  try
    let sf, sc1, sc2 = split_color_string s in
    let f = M.flavor_of_string sf in
    match M.color f with
    | C.Singlet → White f
    | C.SUN nc →
      if nc > 0 then
        CF_in (f, color_flow_of_string sc1)
      else
        CF_out (f, color_flow_of_string sc2)
    | C.AdjSUN _ →
      begin match sc1, sc2 with
      | "", "" → CF_aux f
      | _, _ → CF_io (f, color_flow_of_string sc1, color_flow_of_string sc2)
      end
  with
  | Failure "int_of_string" →
    invalid_arg "Colorize().flavor_of_string: expecting integer"
let flavor_to_string = function
| White f →
  M.flavor_to_string f
| CF_in (f, c) →
  M.flavor_to_string f ^ "/" ^ string_of_int c ^ "/"
| CF_out (f, c) →
  M.flavor_to_string f ^ "/" ^ string_of_int c
| CF_io (f, c1, c2) →
  M.flavor_to_string f ^ "/" ^ string_of_int c1 ^ "/" ^ string_of_int c2
| CF_aux f →
  M.flavor_to_string f ^ "/"
let flavor_to_TeX = function
| White f →
  M.flavor_to_TeX f
| CF_in (f, c) →
  "{" ^ M.flavor_to_TeX f ^ "}" ^ string_of_int c
| CF_out (f, c) →
  "{" ^ M.flavor_to_TeX f ^ "}" ^ string_of_int c
| CF_io (f, c1, c2) →
  "{" ^ M.flavor_to_TeX f ^ "}" ^ string_of_int c1 ^ string_of_int c2
| CF_aux f →
  "{" ^ M.flavor_to_TeX f ^ "}" ^ "0"
let flavor_symbol = function
| White f →
  M.flavor_symbol f
| CF_in (f, c) →

```



```

      M.flavor_symbol f ^ "-" ^ string_of_int c ^ "-"
| CF_out (f, c) →
      M.flavor_symbol f ^ "--" ^ string_of_int c
| CF_io (f, c1, c2) →
      M.flavor_symbol f ^ "-" ^ string_of_int c1 ^ "-" ^ string_of_int c2
| CF_aux f →
      M.flavor_symbol f ^ "--"

```

```
let gauge_symbol = M.gauge_symbol
```

Masses and widths must not depend on the colors anyway!

```

let mass_symbol = pullback M.mass_symbol
let width_symbol = pullback M.width_symbol
let constant_symbol = M.constant_symbol

```

Vertices

Auxiliary functions

```

let mult_vertex3 x = function
| FBF (c, fb, coup, f) →
      FBF ((x × c), fb, coup, f)
| PBP (c, fb, coup, f) →
      PBP ((x × c), fb, coup, f)
| BBB (c, fb, coup, f) →
      BBB ((x × c), fb, coup, f)
| GBG (c, fb, coup, f) →
      GBG ((x × c), fb, coup, f)
| Gauge_Gauge_Gauge c →
      Gauge_Gauge_Gauge (x × c)
| Aux_Gauge_Gauge c →
      Aux_Gauge_Gauge (x × c)
| Scalar_Vector_Vector c →
      Scalar_Vector_Vector (x × c)
| Aux_Vector_Vector c →
      Aux_Vector_Vector (x × c)
| Aux_Scalar_Vector c →
      Aux_Scalar_Vector (x × c)
| Scalar_Scalar_Scalar c →
      Scalar_Scalar_Scalar (x × c)
| Aux_Scalar_Scalar c →
      Aux_Scalar_Scalar (x × c)
| Vector_Scalar_Scalar c →
      Vector_Scalar_Scalar (x × c)
| Graviton_Scalar_Scalar c →
      Graviton_Scalar_Scalar (x × c)

```

```

| Graviton_Vector_Vector c →
  Graviton_Vector_Vector (x × c)
| Graviton_Spinor_Spinor c →
  Graviton_Spinor_Spinor (x × c)
| Dim4_Vector_Vector_Vector_T c →
  Dim4_Vector_Vector_Vector_T (x × c)
| Dim4_Vector_Vector_Vector_L c →
  Dim4_Vector_Vector_Vector_L (x × c)
| Dim4_Vector_Vector_Vector_T5 c →
  Dim4_Vector_Vector_Vector_T5 (x × c)
| Dim4_Vector_Vector_Vector_L5 c →
  Dim4_Vector_Vector_Vector_L5 (x × c)
| Dim6_Gauge_Gauge_Gauge c →
  Dim6_Gauge_Gauge_Gauge (x × c)
| Dim6_Gauge_Gauge_Gauge_5 c →
  Dim6_Gauge_Gauge_Gauge_5 (x × c)
| Aux_DScalar_DScalar c →
  Aux_DScalar_DScalar (x × c)
| Aux_Vector_DScalar c →
  Aux_Vector_DScalar (x × c)
| Dim5_Scalar_Gauge2 c →
  Dim5_Scalar_Gauge2 (x × c)
| Dim5_Scalar_Gauge2_Skew c →
  Dim5_Scalar_Gauge2_Skew (x × c)
| Dim5_Scalar_Vector_Vector_T c →
  Dim5_Scalar_Vector_Vector_T (x × c)
| Dim5_Scalar_Vector_Vector_U c →
  Dim5_Scalar_Vector_Vector_U (x × c)
| Dim5_Scalar_Vector_Vector_TU c →
  Dim5_Scalar_Vector_Vector_TU (x × c)
| Dim6_Vector_Vector_Vector_T c →
  Dim6_Vector_Vector_Vector_T (x × c)
| Tensor_2_Vector_Vector c →
  Tensor_2_Vector_Vector (x × c)
| Dim5_Tensor_2_Vector_Vector_1 c →
  Dim5_Tensor_2_Vector_Vector_1 (x × c)
| Dim5_Tensor_2_Vector_Vector_2 c →
  Dim5_Tensor_2_Vector_Vector_2 (x × c)
| Dim7_Tensor_2_Vector_Vector_T c →
  Dim7_Tensor_2_Vector_Vector_T (x × c)

let mult_vertex4 x = function
| Scalar4 c →
  Scalar4 (x × c)
| Scalar2_Vector2 c →
  Scalar2_Vector2 (x × c)
| Vector4 ic4_list →
  Vector4 (List.map (fun (c, icl) → (x × c, icl)) ic4_list)
| DScalar4 ic4_list →
  DScalar4 (List.map (fun (c, icl) → (x × c, icl)) ic4_list)

```

```

| DScalar2_Vector2 ic4_list →
  DScalar2_Vector2 (List.map (fun (c, icl) → (x × c, icl)) ic4_list)
| GBBG (c, fb, b2, f) →
  GBBG ((x × c), fb, b2, f)
| Vector4_K_Matrix_tho (c, ic4_list) →
  Vector4_K_Matrix_tho ((x × c), ic4_list)
| Vector4_K_Matrix_jr (c, ch2_list) →
  Vector4_K_Matrix_jr ((x × c), ch2_list)

let mult_vertexn x = function
| foo → ignore (incomplete "mult_vertexn"); foo

let mult_vertex x = function
| V3 (v, fuse, c) → V3 (mult_vertex3 x v, fuse, c)
| V4 (v, fuse, c) → V4 (mult_vertex4 x v, fuse, c)
| Vn (v, fuse, c) → Vn (mult_vertexn x v, fuse, c)

```

Below, we will need to permute Lorentz structures. The following permutes the three possible contractions of four vectors. We permute the first three indices, as they correspond to the particles entering the fusion.

```

type permutation4 =
| P123 | P231 | P312
| P213 | P321 | P132

let permute_contract4 = function
| P123 →
  begin function
  | C_12_34 → C_12_34
  | C_13_42 → C_13_42
  | C_14_23 → C_14_23
  end
| P231 →
  begin function
  | C_12_34 → C_14_23
  | C_13_42 → C_12_34
  | C_14_23 → C_13_42
  end
| P312 →
  begin function
  | C_12_34 → C_13_42
  | C_13_42 → C_14_23
  | C_14_23 → C_12_34
  end
| P213 →
  begin function
  | C_12_34 → C_12_34
  | C_13_42 → C_14_23
  | C_14_23 → C_13_42
  end
| P321 →
  begin function
  | C_12_34 → C_14_23

```

```

      | C_13_42 → C_13_42
      | C_14_23 → C_12_34
    end
  | P132 →
    begin function
      | C_12_34 → C_13_42
      | C_13_42 → C_12_34
      | C_14_23 → C_14_23
    end

let permute_contract4_list perm ic4_list =
  List.map (fun (i, c4) → (i, permute_contract4 perm c4)) ic4_list

let permute_vertex4' perm = function
  | Scalar4 c →
    Scalar4 c
  | Vector4 ic4_list →
    Vector4 (permute_contract4_list perm ic4_list)
  | Vector4_K_Matrix_jr (c, ic4_list) →
    Vector4_K_Matrix_jr (c, permute_contract4_list perm ic4_list)
  | Scalar2_Vector2 c →
    incomplete "permute_vertex4'␣Scalar2_Vector2"
  | DScalar4 ic4_list →
    incomplete "permute_vertex4'␣DScalar4"
  | DScalar2_Vector2 ic4_list →
    incomplete "permute_vertex4'␣DScalar2_Vector2"
  | GBBG (c, fb, b2, f) →
    incomplete "permute_vertex4'␣GBBG"
  | Vector4_K_Matrix_tho (c, ch2_list) →
    incomplete "permute_vertex4'␣Vector4_K_Matrix_tho"

let permute_vertex4 perm = function
  | V3 (v, fuse, c) → V3 (v, fuse, c)
  | V4 (v, fuse, c) → V4 (permute_vertex4' perm v, fuse, c)
  | Vn (v, fuse, c) → Vn (v, fuse, c)

```

vertices are *only* used by functor applications and for indexing a cache of pre-computed fusion rules, which is not used for colorized models.

```

let vertices () =
  invalid "vertices"

```

Cubic Vertices



The following pattern matches could eventually become quite long. The O'Caml compiler will (hopefully) optimize them aggressively (<http://pauillac.inria.fr/~maranget/papers/opat/>).

```

let colorize_fusion2 f1 f2 (f, v) =

```

```

match M.color f with
| C.Singlet →
  begin match f1, f2 with
  | White -, White - →
    [White f, v]
  | CF_in (-, c1), CF_out (-, c2')
  | CF_out (-, c1), CF_in (-, c2') →
    if c1 = c2' then
      [White f, v]
    else
      []
  | CF_io (f1, c1, c1'), CF_io (f2, c2, c2') →
    if c1 = c2' ∧ c2 = c1' then
      [White f, v]
    else
      []
  | CF_aux f1, CF_aux f2 →
    [White f, mult_vertex (-(nc ())) v]
  | CF_aux -, CF_io - | CF_io -, CF_aux - →
    []
  | (CF_in - | CF_out - | CF_io - | CF_aux -), White -
  | White -, (CF_in - | CF_out - | CF_io - | CF_aux -)
  | (CF_io - | CF_aux -), (CF_in - | CF_out -)
  | (CF_in - | CF_out -), (CF_io - | CF_aux -)
  | CF_in -, CF_in - | CF_out -, CF_out - →
    colored_vertex "colorize_fusion2"
  end
| C.SUN nc1 →
  begin match f1, f2 with
  | CF_in (-, c1), (White - | CF_aux -)
  | (White - | CF_aux -), CF_in (-, c1) →
    if nc1 > 0 then
      [CF_in (f, c1), v]
    else
      colored_vertex "colorize_fusion2"
  | CF_out (-, c1'), (White - | CF_aux -)
  | (White - | CF_aux -), CF_out (-, c1') →
    if nc1 < 0 then
      [CF_out (f, c1'), v]
    else
      colored_vertex "colorize_fusion2"
  | CF_in (-, c1), CF_io (-, c2, c2')
  | CF_io (-, c2, c2'), CF_in (-, c1) →
    if nc1 > 0 then begin

```


```

        if  $c1 = c2'$  then
            [CF_in ( $f, c2$ ),  $v$ ]
        else
            []
        end else
            colored_vertex "colorize-fusion2"
| CF_out (_,  $c1'$ ), CF_io (_,  $c2, c2'$ )
| CF_io (_,  $c2, c2'$ ), CF_out (_,  $c1'$ ) →
    if  $nc1 < 0$  then begin
        if  $c1' = c2$  then
            [CF_out ( $f, c2'$ ),  $v$ ]
        else
            []
        end else
            colored_vertex "colorize-fusion2"
| CF_in _, CF_in _ →
    if  $nc1 > 0$  then
        baryonic_vertex "colorize-fusion2"
    else
        colored_vertex "colorize-fusion2"
| CF_out _, CF_out _ →
    if  $nc1 < 0$  then
        baryonic_vertex "colorize-fusion2"
    else
        colored_vertex "colorize-fusion2"
| CF_in _, CF_out _ | CF_out _, CF_in _
| (White _ | CF_io _ | CF_aux _),
  (White _ | CF_io _ | CF_aux _) →
    colored_vertex "colorize-fusion2"
end

| C.AdjSUN _ →
    begin match  $f1, f2$  with
    | White _, CF_io (_,  $c1, c2'$ ) | CF_io (_,  $c1, c2'$ ), White _ →
        [CF_io ( $f, c1, c2'$ ),  $v$ ]
    | White _, CF_aux _ | CF_aux _, White _ →
        [CF_aux  $f$ , mult_vertex ( $-(nc ())$ )  $v$ ]
    | CF_in (_,  $c1$ ), CF_out (_,  $c2'$ )
    | CF_out (_,  $c2'$ ), CF_in (_,  $c1$ ) →
        if  $c1 \neq c2'$  then
            [CF_io ( $f, c1, c2'$ ),  $v$ ]
        else
            [CF_aux  $f, v$ ]
    end
end

```

In the adjoint representation



$$= g f_{a_1 a_2 a_3} C^{\mu_1 \mu_2 \mu_3}(k_1, k_2, k_3) \quad (11.1a)$$

with

$$C^{\mu_1 \mu_2 \mu_3}(k_1, k_2, k_3) = (g^{\mu_1 \mu_2}(k_1^{\mu_3} - k_2^{\mu_3}) + g^{\mu_2 \mu_3}(k_2^{\mu_1} - k_3^{\mu_1}) + g^{\mu_3 \mu_1}(k_3^{\mu_2} - k_1^{\mu_2})) \quad (11.1b)$$


while in the color flow basis find from

$$if_{a_1 a_2 a_3} = \text{tr}(T_{a_1}[T_{a_2}, T_{a_3}]) = \text{tr}(T_{a_1} T_{a_2} T_{a_3}) - \text{tr}(T_{a_1} T_{a_3} T_{a_2}) \quad (11.2)$$

the decomposition

$$if_{a_1 a_2 a_3} T_{a_1}^{i_1 j_1} T_{a_2}^{i_2 j_2} T_{a_3}^{i_3 j_3} = \delta^{i_1 j_2} \delta^{i_2 j_3} \delta^{i_3 j_1} - \delta^{i_1 j_3} \delta^{i_3 j_2} \delta^{i_2 j_1}. \quad (11.3)$$

The resulting Feynman rule is



$$= ig (\delta^{i_1 j_3} \delta^{i_2 j_1} \delta^{i_3 j_2} - \delta^{i_1 j_2} \delta^{i_2 j_3} \delta^{i_3 j_1}) C^{\mu_1 \mu_2 \mu_3}(k_1, k_2, k_3) \quad (11.4)$$



We have to generalize this for cases of three particles in the adjoint that are not all gluons (gluinos, scalar octets):

- scalar-scalar-scalar
- scalar-scalar-vector
- scalar-vector-vector
- scalar-fermion-fermion
- vector-fermion-fermion



We could use a better understanding of the signs for the gaugino-gaugino-gaugeboson couplings!!!

```
| CF_io (f1, c1, c1'), CF_io (f2, c2, c2') →
  let sign =
    begin match v with
    | V3 (Gauge_Gauge_Gauge -, -, -)
```

```

*)
| V3 (Aux_Gauge_Gauge -, -, -) → 1
| V3 (FBF (-, -, -, -), fuse2, -) →
  begin match fuse2 with
  | F12 → 1 (* works, but needs theoretical underpinning
  | F21 → - 1 (* dto. *)
  | F31 → 1 (* dto. *)
  | F32 → - 1 (* transposition of F12 (no testcase) *)
  | F23 → 1 (* transposition of F21 (no testcase) *)
  | F13 → - 1 (* transposition of F12 (no testcase) *)
  end
| V3 _ → incomplete "colorize_fusion2_□(V3_□_)"
| V4 _ → impossible "colorize_fusion2_□(V4_□_)"
| Vn _ → impossible "colorize_fusion2_□(Vn_□_)"
end in
if c1' = c2 then
  [CF_io (f, c1, c2'), mult_vertex (-sign) v]
else if c2' = c1 then
  [CF_io (f, c2, c1'), mult_vertex (sign) v]
else
  []
| CF_aux -, CF_io -
| CF_io -, CF_aux -
| CF_aux -, CF_aux - →
  []
| White -, White -
| (White - | CF_io - | CF_aux -), (CF_in - | CF_out -)
| (CF_in - | CF_out -), (White - | CF_io - | CF_aux -)
| CF_in -, CF_in - | CF_out -, CF_out - →
  colored_vertex "colorize_fusion2"
end

```

Quartic Vertices

```

let colorize_fusion3 f1 f2 f3 (f, v) =
  match M.color f with
  | C.Singlet →
    begin match f1, f2, f3 with
    | White -, White -, White - →
      [White f, v]
    | (White - | CF_aux -), CF_in (-, c1), CF_out (-, c2')
    | (White - | CF_aux -), CF_out (-, c1), CF_in (-, c2')
    | CF_in (-, c1), (White - | CF_aux -), CF_out (-, c2')
    | CF_out (-, c1), (White - | CF_aux -), CF_in (-, c2')
    | CF_in (-, c1), CF_out (-, c2'), (White - | CF_aux -)
    
```



```

| CF_out (_, c1), CF_in (_, c2'), (White _ | CF_aux _) →
  if c1 = c2' then
    [White f, v]
  else
    []

| White _, CF_io (_, c1, c1'), CF_io (_, c2, c2')
| CF_io (_, c1, c1'), White _, CF_io (_, c2, c2')
| CF_io (_, c1, c1'), CF_io (_, c2, c2'), White _ →
  if c1 = c2' ∧ c2 = c1' then
    [White f, v]
  else
    []

| White _, CF_aux _, CF_aux _
| CF_aux _, White _, CF_aux _
| CF_aux _, CF_aux _, White _ →
  [White f, mult_vertex (-(nc ())) v]

| White _, CF_io _, CF_aux _
| White _, CF_aux _, CF_io _
| CF_io _, White _, CF_aux _
| CF_aux _, White _, CF_io _
| CF_io _, CF_aux _, White _
| CF_aux _, CF_io _, White _ →
  []

| CF_io (_, c1, c1'), CF_in (_, c2), CF_out (_, c3')
| CF_io (_, c1, c1'), CF_out (_, c3'), CF_in (_, c2)
| CF_in (_, c2), CF_io (_, c1, c1'), CF_out (_, c3')
| CF_out (_, c3'), CF_io (_, c1, c1'), CF_in (_, c2)
| CF_in (_, c2), CF_out (_, c3'), CF_io (_, c1, c1')
| CF_out (_, c3'), CF_in (_, c2), CF_io (_, c1, c1') →
  if c1 = c3' ∧ c1' = c2 then
    [White f, v]
  else
    []

| CF_io (_, c1, c1'), CF_io (_, c2, c2'), CF_io (_, c3, c3') →
  if c1' = c2 ∧ c2' = c3 ∧ c3' = c1 then
    [White f, mult_vertex (-1) v]
  else if c1' = c3 ∧ c2' = c1 ∧ c3' = c2 then
    [White f, mult_vertex (1) v]
  else
    []

| CF_io _, CF_io _, CF_aux _
| CF_io _, CF_aux _, CF_io _
| CF_aux _, CF_io _, CF_io _
| CF_io _, CF_aux _, CF_aux _
| CF_aux _, CF_io _, CF_aux _
| CF_aux _, CF_aux _, CF_io _
| CF_aux _, CF_aux _, CF_aux _ →

```

```

[]

| CF_in -, CF_in -, CF_in -
| CF_out -, CF_out -, CF_out - →
  baryonic_vertex "colorize_fusion3"

| CF_in -, CF_in -, CF_out -
| CF_in -, CF_out -, CF_in -
| CF_out -, CF_in -, CF_in -
| CF_in -, CF_out -, CF_out -
| CF_out -, CF_in -, CF_out -
| CF_out -, CF_out -, CF_in -

| White -, White -, (CF_io - | CF_aux -)
| White -, (CF_io - | CF_aux -), White -
| (CF_io - | CF_aux -), White -, White -

| (White - | CF_io - | CF_aux -), CF_in -, CF_in -
| CF_in -, (White - | CF_io - | CF_aux -), CF_in -
| CF_in -, CF_in -, (White - | CF_io - | CF_aux -)

| (White - | CF_io - | CF_aux -), CF_out -, CF_out -
| CF_out -, (White - | CF_io - | CF_aux -), CF_out -
| CF_out -, CF_out -, (White - | CF_io - | CF_aux -)

| (CF_in - | CF_out -),
  (White - | CF_io - | CF_aux -),
  (White - | CF_io - | CF_aux -)
| (White - | CF_io - | CF_aux -),
  (CF_in - | CF_out -),
  (White - | CF_io - | CF_aux -)
| (White - | CF_io - | CF_aux -),
  (White - | CF_io - | CF_aux -),
  (CF_in - | CF_out -) →
  colored_vertex "colorize_fusion3"

end

| C.SUN nc1 →
  begin match f1, f2, f3 with
    | CF_in (-, c1), CF_io (-, c2, c2'), CF_io (-, c3, c3')
    | CF_io (-, c2, c2'), CF_in (-, c1), CF_io (-, c3, c3')
    | CF_io (-, c2, c2'), CF_io (-, c3, c3'), CF_in (-, c1) →
      if nc1 > 0 then
        if c1 = c2' ∧ c2 = c3' then
          [CF_in (f, c3), v]
        else if c1 = c3' ∧ c3 = c2' then
          [CF_in (f, c2), v]
        else
          []
        else
          colored_vertex "colorize_fusion3"
      | CF_out (-, c1'), CF_io (-, c2, c2'), CF_io (-, c3, c3')

```

```

| CF_io (_, c2, c2'), CF_out (_, c1'), CF_io (_, c3, c3')
| CF_io (_, c2, c2'), CF_io (_, c3, c3'), CF_out (_, c1') →
  if nc1 < 0 then
    if c1' = c2 ∧ c2' = c3 then
      [CF_out (f, c3'), v]
    else if c1' = c3 ∧ c3' = c2 then
      [CF_out (f, c2'), v]
    else
      []
  else
    colored_vertex "colorize_fusion3"
| CF_aux -, CF_in (_, c1), CF_io (_, c2, c2')
| CF_aux -, CF_io (_, c2, c2'), CF_in (_, c1)
| CF_in (_, c1), CF_aux -, CF_io (_, c2, c2')
| CF_io (_, c2, c2'), CF_aux -, CF_in (_, c1)
| CF_in (_, c1), CF_io (_, c2, c2'), CF_aux -
| CF_io (_, c2, c2'), CF_in (_, c1), CF_aux - →
  if nc1 > 0 then
    if c1 = c2' then
      [CF_in (f, c2), mult_vertex (2) v]
    else
      []
  else
    colored_vertex "colorize_fusion3"
| CF_aux -, CF_out (_, c1'), CF_io (_, c2, c2')
| CF_aux -, CF_io (_, c2, c2'), CF_out (_, c1')
| CF_out (_, c1'), CF_aux -, CF_io (_, c2, c2')
| CF_io (_, c2, c2'), CF_aux -, CF_out (_, c1')
| CF_out (_, c1'), CF_io (_, c2, c2'), CF_aux -
| CF_io (_, c2, c2'), CF_out (_, c1'), CF_aux - →
  if nc1 < 0 then
    if c1' = c2 then
      [CF_out (f, c2'), mult_vertex (2) v]
    else
      []
  else
    colored_vertex "colorize_fusion3"
| White -, CF_in (_, c1), CF_io (_, c2, c2')
| White -, CF_io (_, c2, c2'), CF_in (_, c1)
| CF_in (_, c1), White -, CF_io (_, c2, c2')
| CF_io (_, c2, c2'), White -, CF_in (_, c1)
| CF_in (_, c1), CF_io (_, c2, c2'), White -
| CF_io (_, c2, c2'), CF_in (_, c1), White - →
  if nc1 > 0 then
    if c1 = c2' then
      [CF_in (f, c2), v]
    else
      []
  else
    colored_vertex "colorize_fusion3"

```

```

    colored_vertex "colorize-fusion3"
| White -, CF_out (-, c1'), CF_io (-, c2, c2')
| White -, CF_io (-, c2, c2'), CF_out (-, c1')
| CF_out (-, c1'), White -, CF_io (-, c2, c2')
| CF_io (-, c2, c2'), White -, CF_out (-, c1')
| CF_out (-, c1'), CF_io (-, c2, c2'), White -
| CF_io (-, c2, c2'), CF_out (-, c1'), White - →
    if nc1 < 0 then
        if c2 = c1' then
            [CF_out (f, c2'), v]
        else
            []
    else
        colored_vertex "colorize-fusion3"
| CF_in (-, c1), CF_aux -, CF_aux -
| CF_aux -, CF_in (-, c1), CF_aux -
| CF_aux -, CF_aux -, CF_in (-, c1) →
    if nc1 > 0 then
        [CF_in (f, c1), mult_vertex ( 2) v]
    else
        colored_vertex "colorize-fusion3"
| CF_in (-, c1), CF_aux -, White -
| CF_in (-, c1), White -, CF_aux -
| CF_in (-, c1), White -, White -
| CF_aux -, CF_in (-, c1), White -
| White -, CF_in (-, c1), CF_aux -
| White -, CF_in (-, c1), White -
| CF_aux -, White -, CF_in (-, c1)
| White -, CF_aux -, CF_in (-, c1)
| White -, White -, CF_in (-, c1) →
    if nc1 > 0 then
        [CF_in (f, c1), v]
    else
        colored_vertex "colorize-fusion3"
| CF_out (-, c1'), CF_aux -, CF_aux -
| CF_aux -, CF_out (-, c1'), CF_aux -
| CF_aux -, CF_aux -, CF_out (-, c1') →
    if nc1 < 0 then
        [CF_out (f, c1'), mult_vertex ( 2) v]
    else
        colored_vertex "colorize-fusion3"
| CF_out (-, c1'), CF_aux -, White -
| CF_out (-, c1'), White -, CF_aux -
| CF_out (-, c1'), White -, White -
| CF_aux -, CF_out (-, c1'), White -
| White -, CF_out (-, c1'), CF_aux -
| White -, CF_out (-, c1'), White -
| CF_aux -, White -, CF_out (-, c1')

```

```

| White -, CF_aux -, CF_out (-, c1')
| White -, White -, CF_out (-, c1') →
  if nc1 < 0 then
    [CF_out (f, c1'), v]
  else
    colored_vertex "colorize-fusion3"

| CF_in -, CF_in -, CF_out -
| CF_in -, CF_out -, CF_in -
| CF_out -, CF_in -, CF_in - →
  if nc1 > 0 then
    color_flow_ambiguous "colorize-fusion3"
  else
    colored_vertex "colorize-fusion3"

| CF_in -, CF_out -, CF_out -
| CF_out -, CF_in -, CF_out -
| CF_out -, CF_out -, CF_in - →
  if nc1 < 0 then
    color_flow_ambiguous "colorize-fusion3"
  else
    colored_vertex "colorize-fusion3"

| CF_in -, CF_in -, CF_in -
| CF_out -, CF_out -, CF_out -

| (White - | CF_io - | CF_aux -),
  (White - | CF_io - | CF_aux -),
  (White - | CF_io - | CF_aux -)

| (CF_in - | CF_out -),
  (CF_in - | CF_out -),
  (White - | CF_io - | CF_aux -)

| (CF_in - | CF_out -),
  (White - | CF_io - | CF_aux -),
  (CF_in - | CF_out -)

| (White - | CF_io - | CF_aux -),
  (CF_in - | CF_out -),
  (CF_in - | CF_out -) →
  colored_vertex "colorize-fusion3"


end

| C.AdjSUN nc →
  begin match f1, f2, f3 with
    | CF_in (-, c1), CF_out (-, c1'), White -
    | CF_out (-, c1'), CF_in (-, c1), White -
    | CF_in (-, c1), White -, CF_out (-, c1')
    | CF_out (-, c1'), White -, CF_in (-, c1)
    | White -, CF_in (-, c1), CF_out (-, c1')
    | White -, CF_out (-, c1'), CF_in (-, c1) →
      if c1 ≠ c1' then
        [CF_io (f, c1, c1'), v]

```

```

else
  [CF_aux f, v]
| CF_in (-, c1), CF_out (-, c1'), CF_aux -
| CF_out (-, c1'), CF_in (-, c1), CF_aux -
| CF_in (-, c1), CF_aux -, CF_out (-, c1')
| CF_out (-, c1'), CF_aux -, CF_in (-, c1)
| CF_aux -, CF_in (-, c1), CF_out (-, c1')
| CF_aux -, CF_out (-, c1'), CF_in (-, c1) →
  if c1 ≠ c1' then
    [CF_io (f, c1, c1'), mult_vertex (2) v]
  else
    [CF_aux f, mult_vertex (2) v]
| CF_in (-, c1), CF_out (-, c1'), CF_io (-, c2, c2')
| CF_out (-, c1'), CF_in (-, c1), CF_io (-, c2, c2')
| CF_in (-, c1), CF_io (-, c2, c2'), CF_out (-, c1')
| CF_out (-, c1'), CF_io (-, c2, c2'), CF_in (-, c1)
| CF_io (-, c2, c2'), CF_in (-, c1), CF_out (-, c1')
| CF_io (-, c2, c2'), CF_out (-, c1'), CF_in (-, c1) →
  if c1 = c2' ∧ c2 = c1' then
    [CF_aux f, mult_vertex (2) v]
  else if c1 = c2' then
    [CF_io (f, c2, c1'), v]
  else if c2 = c1' then
    [CF_io (f, c1, c2'), v]
  else
    []
    
```



$$\begin{aligned}
 & -ig^2 f_{a_1 a_2 b} f_{a_3 a_4 b} (g_{\mu_1 \mu_3} g_{\mu_4 \mu_2} - g_{\mu_1 \mu_4} g_{\mu_2 \mu_3}) \\
 & -ig^2 f_{a_1 a_3 b} f_{a_4 a_2 b} (g_{\mu_1 \mu_4} g_{\mu_2 \mu_3} - g_{\mu_1 \mu_2} g_{\mu_3 \mu_4}) \\
 & -ig^2 f_{a_1 a_4 b} f_{a_2 a_3 b} (g_{\mu_1 \mu_2} g_{\mu_3 \mu_4} - g_{\mu_1 \mu_3} g_{\mu_4 \mu_2})
 \end{aligned} \tag{11.5}$$

$$\mathcal{P}_4 = \{\{1, 2, 3, 4\}, \{1, 3, 4, 2\}, \{1, 4, 2, 3\}, \{1, 2, 4, 3\}, \{1, 4, 3, 2\}, \{1, 3, 2, 4\}\} \tag{11.6}$$

as the set of permutations of $\{1, 2, 3, 4\}$ with the cyclic permutations factored out, we have:

$$\begin{aligned}
 & = ig^2 \sum_{\{\alpha_k\}_{k=1,2,3,4} \in \mathcal{P}_4} \delta^{i\alpha_1 j\alpha_2} \delta^{i\alpha_2 j\alpha_3} \delta^{i\alpha_3 j\alpha_4} \delta^{i\alpha_4 j\alpha_1} \\
 & \quad (2g_{\mu_{\alpha_1} \mu_{\alpha_3}} g_{\mu_{\alpha_4} \mu_{\alpha_2}} - g_{\mu_{\alpha_1} \mu_{\alpha_4}} g_{\mu_{\alpha_2} \mu_{\alpha_3}} - g_{\mu_{\alpha_1} \mu_{\alpha_2}} g_{\mu_{\alpha_3} \mu_{\alpha_4}})
 \end{aligned} \tag{11.7}$$

The different color connections correspond to permutations of the particles entering the fusion and have to be matched by a corresponding permutation of the Lorentz structure:



We have to generalize this for cases of four particles in the adjoint that are not all gluons:

- scalar-scalar-scalar-scalar
- scalar-scalar-vector-vector

and even ones including fermions (gluinos) if higher dimensional operators are involved.

```
| CF_io (_, c1, c1'), CF_io (_, c2, c2'), CF_io (_, c3, c3') →
|   if c1' = c2 ∧ c2' = c3 then
|     [CF_io (f, c1, c3'), permute_vertex4 P123 v]
|   else if c1' = c3 ∧ c3' = c2 then
|     [CF_io (f, c1, c2'), permute_vertex4 P132 v]
|   else if c2' = c3 ∧ c3' = c1 then
|     [CF_io (f, c2, c1'), permute_vertex4 P231 v]
|   else if c2' = c1 ∧ c1' = c3 then
|     [CF_io (f, c2, c3'), permute_vertex4 P213 v]
|   else if c3' = c1 ∧ c1' = c2 then
|     [CF_io (f, c3, c2'), permute_vertex4 P312 v]
|   else if c3' = c2 ∧ c2' = c1 then
|     [CF_io (f, c3, c1'), permute_vertex4 P321 v]
|   else
|     []
| CF_io -, CF_io -, CF_aux -
| CF_io -, CF_aux -, CF_io -
| CF_aux -, CF_io -, CF_io -
| CF_io -, CF_aux -, CF_aux -
| CF_aux -, CF_aux -, CF_io -
| CF_aux -, CF_io -, CF_aux -
| CF_aux -, CF_aux -, CF_aux - →
|   []
| CF_io (_, c1, c1'), CF_io (_, c2, c2'), White -
| CF_io (_, c1, c1'), White -, CF_io (_, c2, c2')
| White -, CF_io (_, c1, c1'), CF_io (_, c2, c2') →
|   if c1' = c2 then
|     [CF_io (f, c1, c2'), mult_vertex (-1) v]
|   else if c2' = c1 then
|     [CF_io (f, c2, c1'), mult_vertex (1) v]
|   else
|     []
| CF_io (_, c1, c1'), CF_aux -, White -
| CF_aux -, CF_io (_, c1, c1'), White -
| CF_io (_, c1, c1'), White -, CF_aux -
| CF_aux -, White -, CF_io (_, c1, c1')
```

```

| White -, CF_io (_, c1, c1'), CF_aux -
| White -, CF_aux -, CF_io (_, c1, c1') →
  []

| CF_aux -, CF_aux -, White -
| CF_aux -, White -, CF_aux -
| White -, CF_aux -, CF_aux - →
  []

| White -, White -, CF_io (_, c1, c1')
| White -, CF_io (_, c1, c1'), White -
| CF_io (_, c1, c1'), White -, White - →
  [CF_io (f, c1, c1'), v]

| White -, White -, CF_aux -
| White -, CF_aux -, White -
| CF_aux -, White -, White - →
  []

| White -, White -, White -
| (White - | CF_io - | CF_aux -),
  (White - | CF_io - | CF_aux -),
  (CF_in - | CF_out -)
| (White - | CF_io - | CF_aux -),
  (CF_in - | CF_out -),
  (White - | CF_io - | CF_aux -)
| (CF_in - | CF_out -),
  (White - | CF_io - | CF_aux -),
  (White - | CF_io - | CF_aux -)

| CF_in -, CF_in -, (White - | CF_io - | CF_aux -)
| CF_in -, (White - | CF_io - | CF_aux -), CF_in -
| (White - | CF_io - | CF_aux -), CF_in -, CF_in -

| CF_out -, CF_out -, (White - | CF_io - | CF_aux -)
| CF_out -, (White - | CF_io - | CF_aux -), CF_out -
| (White - | CF_io - | CF_aux -), CF_out -, CF_out -

| (CF_in - | CF_out -),
  (CF_in - | CF_out -),
  (CF_in - | CF_out -) →
  colored_vertex "colorize_fusion3"
end

```

Quintic and Higher Vertices

```

let is_white = function
| White - → true
| - → false
let colorize_fusionn flist (f, v) =

```



```

let incomplete_match () =
  incomplete
  ("colorize_fusionn_{\[" ^
   String.concat ",\[" (List.map flavor_to_string flist) ^
   "\]}->\[" ^ M.flavor_to_string f) in
match M.color f with
| C.Singlet →
  if List.for_all is_white flist then
    [White f, v]
  else
    incomplete_match ()
| C.SUN _ →
  if List.for_all is_white flist then
    colored_vertex "colorize_fusionn"
  else
    incomplete_match ()
| C.AdjSUN _ →
  if List.for_all is_white flist then
    colored_vertex "colorize_fusionn"
  else
    incomplete_match ()

let fuse2 f1 f2 =
  ThoList.flatmap
    (colorize_fusion2 f1 f2)
    (M.fuse2 (flavor_sans_color f1) (flavor_sans_color f2))

let fuse3 f1 f2 f3 =
  ThoList.flatmap
    (colorize_fusion3 f1 f2 f3)
    (M.fuse3 (flavor_sans_color f1) (flavor_sans_color f2) (flavor_sans_color f3))

let fuse_list flist =
  ThoList.flatmap
    (colorize_fusionn flist)
    (M.fuse (List.map flavor_sans_color flist))

let fuse = function
| [] | [-] → invalid_arg "Colorize.It().fuse"
| [f1; f2] → fuse2 f1 f2
| [f1; f2; f3] → fuse3 f1 f2 f3
| flist → fuse_list flist

let max_degree = M.max_degree

```

Adding Color to External Particles

```

let count_color_strings f_list =
  let rec count_color_strings' n_in n_out n_glue = function
  | f :: rest →
    begin match M.color f with

```

```

| C.Singlet → count_color_strings' n_in n_out n_glue rest
| C.SUN nc →
  if nc > 0 then
    count_color_strings' (succ n_in) n_out n_glue rest
  else if nc < 0 then
    count_color_strings' n_in (succ n_out) n_glue rest
  else
    su0 "count_color_strings"
| C.AdjSUN _ →
  count_color_strings' (succ n_in) (succ n_out) (succ n_glue) rest
end
| [] → (n_in, n_out, n_glue)
in
count_color_strings' 0 0 0 f_list
let external_color_flows f_list =
  let n_in, n_out, n_glue = count_color_strings f_list in
  if n_in ≠ n_out then
    []
  else
    let color_strings = ThoList.range 1 n_in in
    List.rev_map
      (fun permutation → (color_strings, permutation))
      (Combinatorics.permute color_strings)

```

If there are only adjoints *and* there are no couplings of adjoints to singlets, we can ignore the U(1)-ghosts.

```

let pure_adjoints f_list =
  List.for_all (fun f → match M.color f with C.AdjSUN _ → true |
_ → false) f_list
let two_adjoints_couple_to_singlets () =
  let vertices3, vertices4, verticesn = M.vertices () in
  List.exists (fun ((f1, f2, f3), _, _) →
    match M.color f1, M.color f2, M.color f3 with
    | C.AdjSUN _, C.AdjSUN _, C.Singlet
    | C.AdjSUN _, C.Singlet, C.AdjSUN _
    | C.Singlet, C.AdjSUN _, C.AdjSUN _ → true
    | _ → false) vertices3 ∨
  List.exists (fun ((f1, f2, f3, f4), _, _) →
    match M.color f1, M.color f2, M.color f3, M.color f4 with
    | C.AdjSUN _, C.AdjSUN _, C.Singlet, C.Singlet
    | C.AdjSUN _, C.Singlet, C.AdjSUN _, C.Singlet
    | C.Singlet, C.AdjSUN _, C.AdjSUN _, C.Singlet
    | C.AdjSUN _, C.Singlet, C.Singlet, C.AdjSUN _
    | C.Singlet, C.AdjSUN _, C.Singlet, C.AdjSUN _
    | C.Singlet, C.Singlet, C.AdjSUN _, C.AdjSUN _ → true
    | _ → false) vertices4 ∨
  List.exists (fun (f_list, _, g) → true) verticesn
let external_ghosts f_list =
  if pure_adjoints f_list then

```

```

    two_adjoints_couple_to_singlets ()
  else
    true

```

We use *List.hd* and *List.tl* instead of pattern matching, because we consume *ecf_in* and *ecf_out* at a different pace.

```

let tail_opt = function
| [] → []
| _ :: tail → tail

let head_req = function
| [] →
    invalid_arg "Colorize.It().colorize_crossed_amplitude1:_insufficient_flows"
| x :: _ → x

let rec colorize_crossed_amplitude1 ghosts acc f_list (ecf_in, ecf_out) =
  match f_list, ecf_in, ecf_out with
  | [], [], [] → [List.rev acc]
  | [], _, _ →
    invalid_arg "Colorize.It().colorize_crossed_amplitude1:_leftover_flows"
  | f :: rest, _, _ →
    begin match M.color f with
    | C.Singlet →
        colorize_crossed_amplitude1 ghosts
        (White f :: acc)
        rest (ecf_in, ecf_out)
    | C.SUN nc →
        if nc > 0 then
          colorize_crossed_amplitude1 ghosts
          (CF_in (f, head_req ecf_in) :: acc)
          rest (tail_opt ecf_in, ecf_out)
        else if nc < 0 then
          colorize_crossed_amplitude1 ghosts
          (CF_out (f, head_req ecf_out) :: acc)
          rest (ecf_in, tail_opt ecf_out)
        else
          su0 "colorize_flavor"
    | C.AdjSUN _ →
        let ecf_in' = head_req ecf_in
        and ecf_out' = head_req ecf_out in
        if ecf_in' = ecf_out' then begin
          if ghosts then
            colorize_crossed_amplitude1 ghosts
            (CF_aux f :: acc)
            rest (tail_opt ecf_in, tail_opt ecf_out)
          else
            []
        end else
          colorize_crossed_amplitude1 ghosts
          (CF_io (f, ecf_in', ecf_out') :: acc)
          rest (tail_opt ecf_in, tail_opt ecf_out)

```

```

    end

    let colorize_crossed_amplitude1 ghosts f_list (ecf_in, ecf_out) =
        colorize_crossed_amplitude1 ghosts [] f_list (ecf_in, ecf_out)

    let colorize_crossed_amplitude f_list =
        ThoList.rev_flatmap
            (colorize_crossed_amplitude1 (external_ghosts f_list) f_list)
            (external_color_flows f_list)

    let cross_uncolored p_in p_out =
        (List.map M.conjugate p_in) @ p_out

    let uncross_colored n_in p_lists_colorized =
        let p_in_out_colorized = List.map (ThoList.splitn n_in) p_lists_colorized in
        List.map
            (fun (p_in_colored, p_out_colored) →
                (List.map conjugate p_in_colored, p_out_colored))
            p_in_out_colorized

    let amplitude p_in p_out =
        uncross_colored
            (List.length p_in)
            (colorize_crossed_amplitude (cross_uncolored p_in p_out))

```

The `--` sign in the second component is redundant, but a Whizard convention.

```

let indices = function
| White _ → Color.Flow.of_list [0; 0]
| CF_in (_, c) → Color.Flow.of_list [c; 0]
| CF_out (_, c) → Color.Flow.of_list [0; -c]
| CF_io (_, c1, c2) → Color.Flow.of_list [c1; -c2]
| CF_aux f → Color.Flow.ghost ()

let flow p_in p_out =
    (List.map indices p_in, List.map indices p_out)
end

```

11.2.2 Colorizing a Monochrome Gauge Model

```

module Gauge (M : Model.Gauge) =
struct
    let rcs = RCS.rename rcs_file "Colorize.Gauge()"
        [ "Colorizing_Monochrome_Gauge_Models" ]

    module CM = It(M)

    type flavor = CM.flavor
    type flavor_sans_color = CM.flavor_sans_color
    type gauge = CM.gauge
    type constant = CM.constant

```

```

type orders = CM.orders
module Ch = CM.Ch
let orders = CM.orders
let charges = CM.charges
let flavor_sans_color = CM.flavor_sans_color
let color = CM.color
let pdg = CM.pdg
let lorentz = CM.lorentz
let propagator = CM.propagator
let width = CM.width
let conjugate = CM.conjugate
let conjugate_sans_color = CM.conjugate_sans_color
let fermion = CM.fermion
let max_degree = CM.max_degree
let vertices = CM.vertices
let fuse2 = CM.fuse2
let fuse3 = CM.fuse3
let fuse = CM.fuse
let flavors = CM.flavors
let nc = CM.nc
let external_flavors = CM.external_flavors
let goldstone = CM.goldstone
let parameters = CM.parameters
let flavor_of_string = CM.flavor_of_string
let flavor_to_string = CM.flavor_to_string
let flavor_to_TeX = CM.flavor_to_TeX
let flavor_symbol = CM.flavor_symbol
let gauge_symbol = CM.gauge_symbol
let mass_symbol = CM.mass_symbol
let width_symbol = CM.width_symbol
let constant_symbol = CM.constant_symbol
let options = CM.options

let incomplete s =
  failwith ("Colorize.Gauge()." ^ s ^ "_not_done_yet!")

type matter_field = M.matter_field
type gauge_boson = M.gauge_boson
type other = M.other

type field =
  | Matter of matter_field
  | Gauge of gauge_boson
  | Other of other

let field f =
  incomplete "field"

let matter_field f =
  incomplete "matter_field"

let gauge_boson f =
  incomplete "gauge_boson"

```

```
let other f =  
  incomplete "other"  
let amplitude = CM.amplitude  
let flow = CM.flow  
end
```

—12—

PROCESSES

12.1 Interface of Process

```

module type T =
  sig
    type flavor
  end

```



Eventually this should become an abstract type:

```

type t = flavor list × flavor list
val incoming : t → flavor list
val outgoing : t → flavor list

```

parse_decay *s* decodes a decay description "*a*_□->_□*b*_□*c*_□...", where each word is split into a bag of flavors separated by ':'s.

```

type decay
val parse_decay : string → decay
val expand_decays : decay list → t list

```

parse_scattering *s* decodes a scattering description "*a*_□*b*_□->_□*c*_□*d*_□...", where each word is split into a bag of flavors separated by ':'s.

```

type scattering
val parse_scattering : string → scattering
val expand_scatterings : scattering list → t list

```

parse_process *s* decodes process descriptions

$$\text{"a b c d"} \Rightarrow \text{Any } [a; b; c; d] \quad (12.1a)$$

$$\text{"a -> b c d"} \Rightarrow \text{Decay } (a, [b; c; d]) \quad (12.1b)$$

$$\text{"a b -> c d"} \Rightarrow \text{Scattering } (a, b, [c; d]) \quad (12.1c)$$

where each word is split into a bag of flavors separated by ':'s.

```

type any
type process = Any of any | Decay of decay | Scattering of scattering
val parse_process : string → process

```

remove_duplicate_final_states partition processes removes duplicates from *processes*, which differ only by a permutation of final state particles. The permutation must respect the partitioning given by the offset 1 integers in *partition*.

```
val remove_duplicate_final_states : int list list → t list → t list
```

diff set1 set2 returns the processes in *set1* with the processes in *set2* removed. *set2* does not need to be a subset of *set1*.

```
val diff : t list → t list → t list
```



Not functional yet. Interface subject to change. Should be moved to *Fusion.Multi*, because we will want to cross *colored* matrix elements.

Factor amplitudes that are related by crossing symmetry.

```
val crossing : t list → (flavor list × int list × t) list
```

```
end
```

```
module Make (M : Model.T) : T with type flavor = M.flavor
```

12.2 Implementation of *Process*

```
module type T =
```

```
sig
```

```
  type flavor
```

```
  type t = flavor list × flavor list
```

```
  val incoming : t → flavor list
```

```
  val outgoing : t → flavor list
```

```
  type decay
```

```
  val parse_decay : string → decay
```

```
  val expand_decays : decay list → t list
```

```
  type scattering
```

```
  val parse_scattering : string → scattering
```

```
  val expand_scatterings : scattering list → t list
```

```
  type any
```

```
  type process = Any of any | Decay of decay | Scattering of scattering
```

```
  val parse_process : string → process
```

```
  val remove_duplicate_final_states : int list list → t list → t list
```

```
  val diff : t list → t list → t list
```

```
  val crossing : t list → (flavor list × int list × t) list
```

```
end
```

```
module Make (M : Model.T) =
```

```
struct
```

```
  type flavor = M.flavor
```

```
  type t = flavor list × flavor list
```

```
  let incoming (fin, _) = fin
```

```
  let outgoing (_, fout) = fout
```


12.2.1 Select Charge Conserving Processes

```
let allowed (fin, fout) =
  M.Ch.is_null (M.Ch.sum (List.map M.charges (List.map M.conjugate fin @ fout)))
```

12.2.2 Parsing Process Descriptions

```
type  $\alpha$  bag =  $\alpha$  list

type any = flavor bag list
type decay = flavor bag  $\times$  flavor bag list
type scattering = flavor bag  $\times$  flavor bag  $\times$  flavor bag list

type process =
  | Any of any
  | Decay of decay
  | Scattering of scattering

let unique_flavors f_bags =
  List.for_all (function [f]  $\rightarrow$  true | _  $\rightarrow$  false) f_bags

let unique_final_state = function
  | Any fs  $\rightarrow$  unique_flavors fs
  | Decay (_, fs)  $\rightarrow$  unique_flavors fs
  | Scattering (_, _, fs)  $\rightarrow$  unique_flavors fs

let parse_process process =
  let last = String.length process - 1
  and flavor_off len = M.flavor_of_string (String.sub process off len) in

  let add_flavors flavors = function
    | Any l  $\rightarrow$  Any (List.rev flavors :: l)
    | Decay (i, f)  $\rightarrow$  Decay (i, List.rev flavors :: f)
    | Scattering (i1, i2, f)  $\rightarrow$  Scattering (i1, i2, List.rev flavors :: f) in

  let rec scan_list so_far n =
    if n > last then
      so_far
    else
      let n' = succ n in
      match process.[n] with
      | ' ' | '\n'  $\rightarrow$  scan_list so_far n'
      | '-'  $\rightarrow$  scan_gtr so_far n'
      | c  $\rightarrow$  scan_flavors so_far [] n n'

  and scan_flavors so_far flavors w n =
    if n > last then
      add_flavors (flavor w (last - w + 1) :: flavors) so_far
    else
      let n' = succ n in
      match process.[n] with
      | ' ' | '\n'  $\rightarrow$ 
```

```

        scan_list (add_flavors (flavor w (n - w) :: flavors) so_far) n'
    | ':' → scan_flavors so_far (flavor w (n - w) :: flavors) n' n'
    | _ → scan_flavors so_far flavors w n'
and scan_gtr so_far n =
  if n > last then
    invalid_arg "expecting_>"
  else
    let n' = succ n in
    match process.[n] with
    | '>' →
      begin match so_far with
      | Any [i] → scan_list (Decay (i, [])) n'
      | Any [i2; i1] → scan_list (Scattering (i1, i2, [])) n'
      | Any _ → invalid_arg "only_1_or_2_particles_in_in>"
      | _ → invalid_arg "too_many_>'s"
      end
    | _ → invalid_arg "expecting_>" in
  match scan_list (Any [] 0) with
  | Any l → Any (List.rev l)
  | Decay (i, f) → Decay (i, List.rev f)
  | Scattering (i1, i2, f) → Scattering (i1, i2, List.rev f)
let parse_decay process =
  match parse_process process with
  | Any (i :: f) →
    prerr_endline "missing_>'_in_process_description,_assuming_decay.";
    (i, f)
  | Decay (i, f) → (i, f)
  | _ → invalid_arg "expecting_decay_description:_got_scattering"
let parse_scattering process =
  match parse_process process with
  | Any (i1 :: i2 :: f) →
    prerr_endline "missing_>'_in_process_description,_assuming_scattering.";
    (i1, i2, f)
  | Scattering (i1, i2, f) → (i1, i2, f)
  | _ → invalid_arg "expecting_scattering_description:_got_decay"
let expand_scatterings scatterings =
  ThoList.flatmap
    (function (fin1, fin2, fout) →
      Product.fold
        (fun flist acc →
          match flist with
          | fin1' :: fin2' :: fout' →
            let fin_fout' = ([fin1'; fin2'], fout') in
            if allowed fin_fout' then
              fin_fout' :: acc
            else
              acc
          | _ → failwith "Omega.expand_scatterings:_can't_happen")

```

```

(fin1 :: fin2 :: fout) []) scatterings
let expand_decays decays =
  ThoList.flatmap
    (function (fin, fout) →
      Product.fold
        (fun flist acc →
          match flist with
          | fin' :: fout' →
            let fin_fout' = ([fin'], fout') in
            if allowed fin_fout' then
              fin_fout' :: acc
            else
              acc
          | [] → failwith "Omega.expand_decays:␣can't␣happen")
        (fin :: fout) []) decays

```

12.2.3 Remove Duplicate Final States

Test if all final states are the same. Identical to *ThoList.homogeneous* \circ (*List.map snd*).

```

let rec homogeneous_final_state = function
| [] | [-] → true
| (_, fs1) :: (_, fs2) :: _ as rest →
  if fs1 ≠ fs2 then
    false
  else
    homogeneous_final_state rest

let by_color f1 f2 =
  let c = Color.compare (M.color f1) (M.color f2) in
  if c ≠ 0 then
    c
  else
    compare f1 f2

module Pre_Bundle =
struct
  type elt = t
  type base = elt

  let compare_elt (fin1, fout1) (fin2, fout2) =
    let c = ThoList.compare ~cmp : by_color fin1 fin2 in
    if c ≠ 0 then
      c
    else
      ThoList.compare ~cmp : by_color fout1 fout2

  let compare_base b1 b2 = compare_elt b2 b1
end

```

```

module Process_Bundle = Bundle.Dyn (Pre_Bundle)

let to_string (fin, fout) =
  String.concat "␣" (List.map M.flavor_to_string fin)
  ^ "␣->␣" ^ String.concat "␣" (List.map M.flavor_to_string fout)

let fiber_to_string (base, fiber) =
  (to_string base) ^ "␣->␣[" ^
  (String.concat ",␣" (List.map to_string fiber)) ^ "]"

let bundle_to_strings list =
  List.map fiber_to_string list

```

Subtract $n + 1$ from each element in *index_set* and drop all negative numbers from the result.

```

let shift_left_pred' n index_set =
  List.fold_right
    (fun i acc → let i' = i - n - 1 in if i' < 0 then acc else i' :: acc)
    index_set []

```

Convert 1-based indices for initial and final state to 0-based indices for the final state only. (NB: *ThoList.partitioned_sort* expects 0-based indices.)

```

let shift_left_pred fin index_sets =
  let n = match fin with [-] → 1 | [-;-] → 2 | - → 0 in
  List.fold_right
    (fun iset acc →
      match shift_left_pred' n iset with
      | [] → acc
      | iset' → iset' :: acc)
    index_sets []

```

```

module FSet = Set.Make (struct type t = flavor let compare = compare end)

```

Take a list of final states and return a list of sets of flavors appearing in each slot.

```

let flavors = function
| [] → []
| fs :: fs_list →
  List.fold_right (List.map2 FSet.add) fs_list (List.map FSet.singleton fs)

let flavor_sums flavor_sets =
  let _, result =
    List.fold_left
      (fun (n, acc) flavors →
        if FSet.cardinal flavors = 1 then
          (succ n, acc)
        else
          (succ n, (n, flavors) :: acc))
      (0, []) flavor_sets in
  List.rev result

let overlapping s1 s2 =
  ¬ (FSet.is_empty (FSet.inter s1 s2))

```

```

let rec merge_overlapping (n, flavors) = function
| [] → [[n], flavors]
| (n_list, flavor_set) :: rest →
  if overlapping_flavors flavor_set then
    (n :: n_list, FSet.union flavors flavor_set) :: rest
  else
    (n_list, flavor_set) :: merge_overlapping (n, flavors) rest
let overlapping_flavor_sums flavor_sums =
  List.rev_map
    (fun (n_list, flavor_set) → (n_list, FSet.elements flavor_set))
    (List.fold_right merge_overlapping flavor_sums [])
module ISet = Set.Make (struct type t = int let compare = compare end)
let integer_range n1 n2 =
  let rec integer_range' acc n' =
    if n' < n1 then
      acc
    else
      integer_range' (ISet.add n' acc) (pred n') in
  integer_range' ISet.empty n2
let coarsest_partition = function
| [] → invalid_arg "coarsest_partition: empty process list"
| ((-, fs) :: _) as proc_list →
  let fs_list = List.map snd proc_list in
  let overlaps =
    List.map fst (overlapping_flavor_sums (flavor_sums (flavors fs_list))) in
  let singletons =
    ISet.elements
      (List.fold_right ISet.remove
        (List.concat overlaps) (integer_range 0 (pred (List.length fs)))) in
  List.map (fun n → [n]) singletons @ overlaps
module IPowSet =
  PowSet.Make (struct type t = int let compare = compare let to_string = string_of_int end)
let merge_partitions p_list =
  IPowSet.to_lists (IPowSet.basis (IPowSet.union (List.map IPowSet.of_lists p_list)))
let remove_duplicate_final_states cascade_partition = function
| [] → []
| [process] → [process]
| list →
  if homogeneous_final_state list then
    list
  else
    let partition = coarsest_partition list in
    let pi (fin, fout) =
      let partition' =
        merge_partitions [partition; shift_left_pred fin cascade_partition] in
      (fin, ThoList.partitioned_sort by_color partition' fout) in
    Process_Bundle.base (Process_Bundle.of_list pi list)

```

```

type t' = t
module PSet = Set.Make (struct type t = t' let compare = compare end)

let set list =
  List.fold_right PSet.add list PSet.empty

let diff list1 list2 =
  PSet.elements (PSet.diff (set list1) (set list2))

```



Not functional yet.

```

module Crossing_Projection =
  struct
    type elt = t
    type base = flavor list × int list × t

    let compare_elt (fin1, fout1) (fin2, fout2) =
      let c = ThoList.compare ~cmp : by_color fin1 fin2 in
      if c ≠ 0 then
        c
      else
        ThoList.compare ~cmp : by_color fout1 fout2

    let compare_base (f1, _, _) (f2, _, _) =
      ThoList.compare ~cmp : by_color f1 f2

    let pi (fin, fout as process) =
      let flist, indices =
        ThoList.ariadne_sort ~cmp : by_color (List.map M.conjugate fin @ fout) in
      (flist, indices, process)
  end

module Crossing_Bundle = Bundle.Make (Crossing_Projection)

let crossing processes =
  List.map
    (fun (fin, fout as process) →
      (List.map M.conjugate fin @ fout, [], process))
  processes
end

```

—13—

HARDCODED MODELS

13.1 Interface of Modeltools

13.1.1 Compilation

```
module type Flavor =
sig
  type f
  type c
  val compare : f → f → int
  val conjugate : f → f
end

module type Fusions =
sig
  type t
  type f
  type c
  val fuse2 : t → f → f → (f × c Coupling.t) list
  val fuse3 : t → f → f → f → (f × c Coupling.t) list
  val fuse : t → f list → (f × c Coupling.t) list
  val of_vertices :
    (((f × f × f) × c Coupling.vertex3 × c) list
     × ((f × f × f × f) × c Coupling.vertex4 × c) list
     × (f list × c Coupling.vertexn × c) list) → t
end

module Fusions : functor (F : Flavor) →
  Fusions with type f = F.f and type c = F.c
```

13.1.2 Mutable Models

```
module Mutable : functor (FGC : sig type f and g and c and o end) →
  Model.Mutable with type flavor = FGC.f and type gauge = FGC.g
  and type constant = FGC.c and type orders = FGC.o
```

13.2 Implementation of *Modeltools*

```
let rcs_file = RCS.parse "Modeltools" ["Lagragians"]
{ RCS.revision = "$Revision: 4538$";
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
  RCS.author = "$Author: jr-reuter$";
  RCS.source
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
```

13.2.1 Compilation

Flavors and coupling constants: flavors can be tested for equality and charge conjugation is defined.

```
module type Flavor =
sig
  type f
  type c
  val compare : f → f → int
  val conjugate : f → f
end
```

Compiling fusions from a list of vertices:

```
module type Fusions =
sig
  type t
  type f
  type c
  val fuse2 : t → f → f → (f × c Coupling.t) list
  val fuse3 : t → f → f → f → (f × c Coupling.t) list
  val fuse : t → f list → (f × c Coupling.t) list
  val of_vertices :
    (((f × f × f) × c Coupling.vertex3 × c) list
     × ((f × f × f × f) × c Coupling.vertex4 × c) list
     × (f list × c Coupling.vertexn × c) list) → t
end
```

```
module Fusions (F : Flavor) : Fusions with type f = F.f and type c = F.c =
struct
```

```
  type f = F.f
  type c = F.c

  module F2 =
    struct
      type t = f × f
      let hash = Hashtbl.hash
      let compare (f1, f2) (f1', f2') =
        let c1 = F.compare f1 f1' in
        if c1 ≠ 0 then
```



```

      c1
    else
      F.compare f2 f2'
    let equal f f' = compare f f' = 0
  end
module F3 =
  struct
    type t = f × f × f
    let hash = Hashtbl.hash
    let compare (f1, f2, f3) (f1', f2', f3') =
      let c1 = F.compare f1 f1' in
      if c1 ≠ 0 then
        c1
      else
        let c2 = F.compare f2 f2' in
        if c2 ≠ 0 then
          c2
        else
          F.compare f3 f3'
    let equal f f' = compare f f' = 0
  end
module Fn =
  struct
    type t = f list
    let hash = Hashtbl.hash
    let compare f f' = ThoList.compare ~cmp : F.compare f f'
    let equal f f' = compare f f' = 0
  end
module H2 = Hashtbl.Make (F2)
module H3 = Hashtbl.Make (F3)
module Hn = Hashtbl.Make (Fn)
type t =
  { v3 : (f × c Coupling.t) list H2.t;
    v4 : (f × c Coupling.t) list H3.t;
    vn : (f × c Coupling.t) list Hn.t }
let fuse2 table f1 f2 =
  try
    H2.find table.v3 (f1, f2)
  with
  | Not_found → []
let fuse3 table f1 f2 f3 =
  try
    H3.find table.v4 (f1, f2, f3)
  with
  | Not_found → []
let fusen table f =
  try

```

```

      Hn.find table.vn f
    with
    | Not_found → []
  let fuse table = function
  | [] | [-] → invalid_arg "Fusions().fuse"
  | [f1; f2] → fuse2 table f1 f2
  | [f1; f2; f3] → fuse3 table f1 f2 f3
  | f → fusen table f

```

Note that a pair or a triplet can appear more than once (e.g. $e^+e^- \rightarrow \gamma$ and $e^+e^- \rightarrow Z$). Therefore don't replace the entry, but augment it instead.

```

  let add_fusion2 table f1 f2 fusions =
    H2.add table.v3 (f1, f2) (fusions :: fuse2 table f1 f2)

  let add_fusion3 table f1 f2 f3 fusions =
    H3.add table.v4 (f1, f2, f3) (fusions :: fuse3 table f1 f2 f3)

  let add_fusionn table f fusions =
    Hn.add table.vn f (fusions :: fusen table f)

```



Do we need to take into account the charge conjugation of the coupling constants here?

If some flavors are identical, we must not introduce the same vertex more than once:

```

open Coupling

let permute3 (f1, f2, f3) =
  [ (f1, f2), F.conjugate f3, F12;
    (f2, f1), F.conjugate f3, F21;
    (f2, f3), F.conjugate f1, F23;
    (f3, f2), F.conjugate f1, F32;
    (f3, f1), F.conjugate f2, F31;
    (f1, f3), F.conjugate f2, F13 ]

```

Here we add identical permutations of pairs only once:

```

module F2' = Set.Make (F2)

let add_permute3 table v c set ((f1, f2 as f12), f, p) =
  if F2'.mem f12 set then
    set
  else begin
    add_fusion2 table f1 f2 (f, V3 (v, p, c));
    F2'.add f12 set
  end

let add_vertex3 table (f123, v, c) =
  ignore (List.fold_left (fun set f → add_permute3 table v c set f)
    F2'.empty (permute3 f123))

```



Handling all the cases explicitly is OK for cubic vertices, but starts to become questionable already for quartic couplings. The advantage remains that we can check completeness in *Targets*.

```
let permute4 (f1, f2, f3, f4) =
  [ (f1, f2, f3), F.conjugate f4, F123;
    (f2, f3, f1), F.conjugate f4, F231;
    (f3, f1, f2), F.conjugate f4, F312;
    (f2, f1, f3), F.conjugate f4, F213;
    (f3, f2, f1), F.conjugate f4, F321;
    (f1, f3, f2), F.conjugate f4, F132;
    (f1, f2, f4), F.conjugate f3, F124;
    (f2, f4, f1), F.conjugate f3, F241;
    (f4, f1, f2), F.conjugate f3, F412;
    (f2, f1, f4), F.conjugate f3, F214;
    (f4, f2, f1), F.conjugate f3, F421;
    (f1, f4, f2), F.conjugate f3, F142;
    (f1, f3, f4), F.conjugate f2, F134;
    (f3, f4, f1), F.conjugate f2, F341;
    (f4, f1, f3), F.conjugate f2, F413;
    (f3, f1, f4), F.conjugate f2, F314;
    (f4, f3, f1), F.conjugate f2, F431;
    (f1, f4, f3), F.conjugate f2, F143;
    (f2, f3, f4), F.conjugate f1, F234;
    (f3, f4, f2), F.conjugate f1, F342;
    (f4, f2, f3), F.conjugate f1, F423;
    (f3, f2, f4), F.conjugate f1, F324;
    (f4, f3, f2), F.conjugate f1, F432;
    (f2, f4, f3), F.conjugate f1, F243 ]
```

Add identical permutations of triplets only once:

```
module F3' = Set.Make (F3)

let add_permute4 table v c set ((f1, f2, f3 as f123), f, p) =
  if F3'.mem f123 set then
    set
  else begin
    add_fusion3 table f1 f2 f3 (f, V4 (v, p, c));
    F3'.add f123 set
  end

let add_vertex4 table (f1234, v, c) =
  ignore (List.fold_left (fun set f → add_permute4 table v c set f)
    F3'.empty (permute4 f1234))

let of_vertices (vlist3, vlist4, vlistn) =
  match vlistn with
  | [] →
    let table =
      { v3 = H2.create 37; v4 = H3.create 37; vn = Hn.create 37 } in
    List.iter (add_vertex3 table) vlist3;
```

```

      List.iter (add_vertex4 table) vlist4;
      table
    | - → failwith "Models.Fusions.of_vertices:␣incomplete"
end

```

13.2.2 Mutable Models

```

module Mutable (FGC : sig type f and g and c and o end) =
struct
  type flavor = FGC.f
  type gauge = FGC.g
  type constant = FGC.c
  type orders = FGC.o

  let options = Options.empty

  module Ch = Charges.Null
  let charges _ = ()

  exception Uninitialized of string
  let uninitialized name =
    raise (Uninitialized name)

```

Note that *lookup* works, by the magic of currying, for any arity. But we need to supply one argument to delay evaluation.

Also note that the references are *not* shared among results of functor applications. Simple module renaming causes sharing.

```

let declare template =
  let reference = ref template in
  let update fct = reference := fct
  and lookup arg = !reference arg in
  (update, lookup)

let set_orders, orders =
  declare (fun f → uninitialized "orders")
let set_color, color =
  declare (fun f → uninitialized "color")
let set_pdg, pdg =
  declare (fun f → uninitialized "pdg")
let set_lorentz, lorentz =
  declare (fun f → uninitialized "lorentz")
let set_propagator, propagator =
  declare (fun f → uninitialized "propagator")
let set_width, width =
  declare (fun f → uninitialized "width")
let set_goldstone, goldstone =
  declare (fun f → uninitialized "goldstone")
let set_conjugate, conjugate =
  declare (fun f → uninitialized "conjugate")
let set_fermion, fermion =

```

```

    declare (fun f → uninitialized "fermion")
let set_max_degree, max_degree =
    declare (fun () → uninitialized "max_degree")
let set_vertices, vertices =
    declare (fun () → uninitialized "vertices")
let set_fuse2, fuse2 =
    declare (fun f1 f2 → uninitialized "fuse2")
let set_fuse3, fuse3 =
    declare (fun f1 f2 f3 → uninitialized "fuse3")
let set_fuse, fuse =
    declare (fun f → uninitialized "fuse")
let set_flavors, flavors =
    declare (fun () → [])
let set_external_flavors, external_flavors =
    declare (fun () → [("uninitialized", [])])
let set_parameters, parameters =
    declare (fun f → uninitialized "parameters")
let set_flavor_of_string, flavor_of_string =
    declare (fun f → uninitialized "flavor_of_string")
let set_flavor_to_string, flavor_to_string =
    declare (fun f → uninitialized "flavor_to_string")
let set_flavor_to_TeX, flavor_to_TeX =
    declare (fun f → uninitialized "flavor_to_TeX")
let set_flavor_symbol, flavor_symbol =
    declare (fun f → uninitialized "flavor_symbol")
let set_gauge_symbol, gauge_symbol =
    declare (fun f → uninitialized "gauge_symbol")
let set_mass_symbol, mass_symbol =
    declare (fun f → uninitialized "mass_symbol")
let set_width_symbol, width_symbol =
    declare (fun f → uninitialized "width_symbol")
let set_constant_symbol, constant_symbol =
    declare (fun f → uninitialized "constant_symbol")

let setup ~color ~pdg ~lorentz ~propagator ~width ~goldstone
    ~conjugate ~fermion ~max_degree ~vertices
    ~fuse : (fuse2, fuse3, fuses)
    ~flavors ~parameters ~flavor_of_string ~flavor_to_string
    ~flavor_to_TeX ~flavor_symbol
    ~gauge_symbol ~mass_symbol ~width_symbol ~constant_symbol =
set_color color;
set_pdg pdg;
set_lorentz lorentz;
set_propagator propagator;
set_width width;
set_goldstone goldstone;
set_conjugate conjugate;
set_fermion fermion;
set_max_degree (fun () → max_degree);
set_vertices vertices;

```

```

    set_fuse2 fuse2;
    set_fuse3 fuse3;
    set_fuse fuse;
    set_external_flavors (fun f → flavors);
    let flavors = ThoList.flatmap snd flavors in
    set_flavors (fun f → flavors);
    set_parameters parameters;
    set_flavor_of_string flavor_of_string;
    set_flavor_to_string flavor_to_string;
    set_flavor_to_TeX flavor_to_TeX;
    set_flavor_symbol flavor_symbol;
    set_gauge_symbol gauge_symbol;
    set_mass_symbol mass_symbol;
    set_width_symbol width_symbol;
    set_constant_symbol constant_symbol

let rcs = RCS.rename rcs_file "Models.Mutable" ["Mutable_Model"]
end

```

13.3 Interface of *Modellib_SM*

13.3.1 Hardcoded Models

```

module Phi3 : Model.T with module Ch = Charges.Null
module Phi4 : Model.T with module Ch = Charges.Null
module QED : Model.T with module Ch = Charges.ZZ
module QCD : Model.T with module Ch = Charges.ZZ

module type SM_flags =
sig
  val higgs_triangle : bool (*  $H\gamma\gamma$ ,  $Hg\gamma$  and  $Hgg$ couplings*)
  val higgs_hmm : bool
  val triple_anom : bool
  val quartic_anom : bool
  val higgs_anom : bool
  val k_matrix : bool
  val ckm_present : bool
  val top_anom : bool
  val top_anom_4f : bool
end

module SM_no_anomalous : SM_flags
module SM_anomalous : SM_flags
module SM_k_matrix : SM_flags
module SM_no_anomalous_ckm : SM_flags
module SM_anomalous_ckm : SM_flags
module SM_Higgs : SM_flags
module SM_anomalous_top : SM_flags

module SM : functor (F : SM_flags) → Model.Gauge with module Ch = Charges.QQ
module SM_Rxi : Model.T with module Ch = Charges.QQ

```

```

module SM_QCD : Model.T with module Ch = Charges.QQ

module Groves : functor (M : Model.Gauge) → Model.Gauge with module
Ch = M.Ch

module SM_clones : Model.Gauge with module Ch = Charges.QQ

```

13.4 Implementation of *Modellib_SM*

```

let rcs_file = RCS.parse "Modellib_SM" ["Lagrangians"]
{ RCS.revision = "$Revision: 4538$";
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
  RCS.author = "$Author: jr-reuter$";
  RCS.source
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg

```

13.4.1 ϕ^3

```

module Phi3 =
struct
  let rcs = RCS.rename rcs_file "Modellib.Phi3"
    ["phi**3_with_a_single_flavor"]

  open Coupling

  let options = Options.empty

  type flavor = Phi
  let external_flavors () = [ "", [Phi] ]
  let flavors () = ThoList.flatmap snd (external_flavors ())

  type gauge = unit
  type constant = G

  type orders = unit
  let orders = function
    | _ → ()

  let lorentz _ = Scalar
  let color _ = Color.Singlet
  let propagator _ = Prop.Scalar
  let width _ = Timelike
  let goldstone _ = None
  let conjugate f = f
  let fermion _ = 0

  module Ch = Charges.Null
  let charges _ = ()

  module F = Modeltools.Fusions (struct
    type f = flavor
    type c = constant
    let compare = compare

```

```

    let conjugate = conjugate
end)

let vertices () =
  [(Phi, Phi, Phi), Scalar_Scalar_Scalar 1, G], [], []

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 3
let parameters () = { input = [G, 1.0]; derived = []; derived_arrays = [] }

let flavor_of_string = function
| "p" → Phi
| _ → invalid_arg "Modellib.Phi3.flavor_of_string"

let flavor_to_string Phi = "phi"
let flavor_to_TeX Phi = "\\phi"
let flavor_symbol Phi = "phi"

let gauge_symbol () =
  failwith "Modellib.Phi3.gauge_symbol: internal error"

let pdg _ = 1
let mass_symbol _ = "m"
let width_symbol _ = "w"
let constant_symbol G = "g"

end

```

$$13.4.2 \quad \lambda_3 \phi^3 + \lambda_4 \phi^4$$

```

module Phi4 =
struct
  let rcs = RCS.rename rcs_file "Modellib.Phi4"
    ["phi**4_with_a_single_flavor"]

  open Coupling

  let options = Options.empty

  type flavor = Phi
  let external_flavors () = [ "", [Phi] ]
  let flavors () = ThoList.flatmap snd (external_flavors ())

  type gauge = unit
  type constant = G3 | G4

  type orders = unit
  let orders = function
  | _ → ()

  let lorentz _ = Scalar
  let color _ = Color.Singlet

```



```

let propagator _ = Prop_Scalar
let width _ = Timelike
let goldstone _ = None
let conjugate f = f
let fermion _ = 0

module Ch = Charges.Null
let charges _ = ()

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let vertices () =
  [(Phi, Phi, Phi), Scalar_Scalar_Scalar 1, G3],
  [(Phi, Phi, Phi, Phi), Scalar4 1, G4], []

let fuse2 _ = failwith "Modellib.Phi4.fuse2"
let fuse3 _ = failwith "Modellib.Phi4.fuse3"
let fuse = function
  | [] | [-] → invalid_arg "Modellib.Phi4.fuse"
  | [-; -] → [Phi, V3 (Scalar_Scalar_Scalar 1, F23, G3)]
  | [-; -; -] → [Phi, V4 (Scalar4 1, F234, G4)]
  | _ → []

let max_degree () = 4
let parameters () =
  { input = [G3, 1.0; G4, 1.0]; derived = []; derived_arrays = [] }

let flavor_of_string = function
  | "p" → Phi
  | _ → invalid_arg "Modellib.Phi4.flavor_of_string"

let flavor_to_string Phi = "phi"
let flavor_to_TeX Phi = "\\phi"
let flavor_symbol Phi = "phi"

let gauge_symbol () =
  failwith "Modellib.Phi4.gauge_symbol: internal error"

let pdg _ = 1
let mass_symbol _ = "m"
let width_symbol _ = "w"
let constant_symbol = function
  | G3 → "g3"
  | G4 → "g4"

end

```

13.4.3 Quantum Electro Dynamics

```
module QED =
```

```

struct
  let rcs = RCS.rename rcs_file "Modellib.QED"
    ["QED_with_two_leptonic_flavors"]

  open Coupling

  let options = Options.empty

  type flavor =
    | Electron | Positron
    | Muon | AntiMuon
    | Tau | AntiTau
    | Photon

  let external_flavors () =
    [ "Leptons", [Electron; Positron; Muon; AntiMuon; Tau; AntiTau];
      "Gauge_Bosons", [Photon] ]

  let flavors () = ThoList.flatmap snd (external_flavors ())

  type gauge = unit
  type constant = Q

  type orders = unit
  let orders = function
    | _ → ()

  let lorentz = function
    | Electron | Muon | Tau → Spinor
    | Positron | AntiMuon | AntiTau → ConjSpinor
    | Photon → Vector

  let color _ = Color.Singlet

  let propagator = function
    | Electron | Muon | Tau → Prop_Spinor
    | Positron | AntiMuon | AntiTau → Prop_ConjSpinor
    | Photon → Prop_Feynman

  let width _ = Timelike

  let goldstone _ =
    None

  let conjugate = function
    | Electron → Positron | Positron → Electron
    | Muon → AntiMuon | AntiMuon → Muon
    | Tau → AntiTau | AntiTau → Tau
    | Photon → Photon

  let fermion = function
    | Electron | Muon | Tau → 1
    | Positron | AntiMuon | AntiTau → -1
    | Photon → 0

```

Taking generation numbers makes electric charge redundant.

```

module Ch = Charges.ZZ
let charges = function

```

```

| Electron → [1; 0; 0]
| Muon → [0; 1; 0]
| Tau → [0; 0; 1]
| Positron → [-1; 0; 0]
| AntiMuon → [0; -1; 0]
| AntiTau → [0; 0; -1]
| Photon → [0; 0; 0]

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let vertices () =
  [(Positron, Photon, Electron), FBF (1, Psibar, V, Psi), Q;
   (AntiMuon, Photon, Muon), FBF (1, Psibar, V, Psi), Q;
   (AntiTau, Photon, Tau), FBF (1, Psibar, V, Psi), Q], [], []

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 3

let parameters () = { input = [Q, 1.0]; derived = []; derived_arrays = [] }

let flavor_of_string = function
| "e-" → Electron | "e+" → Positron
| "m-" → Muon | "m+" → AntiMuon
| "t-" → Tau | "t+" → AntiTau
| "A" → Photon
| _ → invalid_arg "Modellib.QED.flavor_of_string"

let flavor_to_string = function
| Electron → "e-" | Positron → "e+"
| Muon → "m-" | AntiMuon → "m+"
| Tau → "t-" | AntiTau → "t+"
| Photon → "A"

let flavor_to_TeX = function
| Electron → "e-" | Positron → "e+"
| Muon → "\mu-" | AntiMuon → "\mu+"
| Tau → "\tau-" | AntiTau → "\tau+"
| Photon → "\gamma"

let flavor_symbol = function
| Electron → "ele" | Positron → "pos"
| Muon → "muo" | AntiMuon → "amu"
| Tau → "tau" | AntiTau → "ata"
| Photon → "gam"

let gauge_symbol () =
  failwith "Modellib.QED.gauge_symbol: internal error"

```

```

let pdg = function
  | Electron → 11 | Positron → -11
  | Muon → 13 | AntiMuon → -13
  | Tau → 15 | AntiTau → -15
  | Photon → 22
let mass_symbol f =
  "mass(" ^ string_of_int (abs (pdg f)) ^ ")"
let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"
let constant_symbol = function
  | Q → "qlép"
end

```

13.4.4 Quantum Chromo Dynamics

```

module QCD =
struct
  let rcs = RCS.rename rcs_file "Modellib.QCD"
    ["QCD"]
  open Coupling
  let options = Options.empty
  type flavor =
    | U | Ubar | D | Dbar
    | C | Cbar | S | Sbar
    | T | Tbar | B | Bbar
    | Gl
  let external_flavors () =
    ["Quarks", [U; D; C; S; T; B; Ubar; Dbar; Cbar; Sbar; Tbar; Bbar];
     "Gauge_Bosons", [Gl]]
  let flavors () = ThoList.flatmap snd (external_flavors ())
  type gauge = unit
  type constant = Gs | G2 | I_Gs
  type orders = unit
  let orders = function
    | _ → ()
  let lorentz = function
    | U | D | C | S | T | B → Spinor
    | Ubar | Dbar | Cbar | Sbar | Tbar | Bbar → ConjSpinor
    | Gl → Vector
  let color = function
    | U | D | C | S | T | B → Color.SUN 3
    | Ubar | Dbar | Cbar | Sbar | Tbar | Bbar → Color.SUN (-3)
    | Gl → Color.AdjSUN 3

```

```

let propagator = function
  | U | D | C | S | T | B → Prop_Spinor
  | Ubar | Dbar | Cbar | Sbar | Tbar | Bbar → Prop_ConjSpinor
  | Gl → Prop_Feynman

let width _ = Timelike

let goldstone _ =
  None

let conjugate = function
  | U → Ubar
  | D → Dbar
  | C → Cbar
  | S → Sbar
  | T → Tbar
  | B → Bbar
  | Ubar → U
  | Dbar → D
  | Cbar → C
  | Sbar → S
  | Tbar → T
  | Bbar → B
  | Gl → Gl

let fermion = function
  | U | D | C | S | T | B → 1
  | Ubar | Dbar | Cbar | Sbar | Tbar | Bbar → -1
  | Gl → 0

module Ch = Charges.ZZ
let charges = function
  | D → [1; 0; 0; 0; 0; 0]
  | U → [0; 1; 0; 0; 0; 0]
  | S → [0; 0; 1; 0; 0; 0]
  | C → [0; 0; 0; 1; 0; 0]
  | B → [0; 0; 0; 0; 1; 0]
  | T → [0; 0; 0; 0; 0; 1]
  | Dbar → [-1; 0; 0; 0; 0; 0]
  | Ubar → [0; -1; 0; 0; 0; 0]
  | Sbar → [0; 0; -1; 0; 0; 0]
  | Cbar → [0; 0; 0; -1; 0; 0]
  | Bbar → [0; 0; 0; 0; -1; 0]
  | Tbar → [0; 0; 0; 0; 0; -1]
  | Gl → [0; 0; 0; 0; 0; 0]

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

```

This is compatible with CD+.

```

let color_current =
  [ ((Dbar, Gl, D), FBF ((-1), Psibar, V, Psi), Gs);
    ((Ubar, Gl, U), FBF ((-1), Psibar, V, Psi), Gs);
    ((Cbar, Gl, C), FBF ((-1), Psibar, V, Psi), Gs);
    ((Sbar, Gl, S), FBF ((-1), Psibar, V, Psi), Gs);
    ((Tbar, Gl, T), FBF ((-1), Psibar, V, Psi), Gs);
    ((Bbar, Gl, B), FBF ((-1), Psibar, V, Psi), Gs)]

let three_gluon =
  [ ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_Gs)]

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]

let four_gluon =
  [ ((Gl, Gl, Gl, Gl), gauge4, G2)]

let vertices3 =
  (color_current @ three_gluon)

let vertices4 = four_gluon

let vertices () =
  (vertices3, vertices4, [])

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let parameters () = { input = [Gs, 1.0]; derived = []; derived_arrays = [] }

let flavor_of_string = function
  | "u" → U
  | "d" → D
  | "c" → C
  | "s" → S
  | "t" → T
  | "b" → B
  | "ubar" → Ubar
  | "dbar" → Dbar
  | "cbar" → Cbar
  | "sbar" → Sbar
  | "tbar" → Tbar
  | "bbar" → Bbar
  | "gl" → Gl
  | _ → invalid_arg "Modellib.QCD.flavor_of_string"

let flavor_to_string = function
  | U → "u"
  | Ubar → "ubar"
  | D → "d"
  | Dbar → "dbar"
  | C → "c"
  | Cbar → "cbar"

```

```

|  $S \rightarrow "s"$ 
|  $Sbar \rightarrow "sbar"$ 
|  $T \rightarrow "t"$ 
|  $Tbar \rightarrow "tbar"$ 
|  $B \rightarrow "b"$ 
|  $Bbar \rightarrow "bbar"$ 
|  $Gl \rightarrow "gl"$ 

let flavor_to_TeX = function
|  $U \rightarrow "u"$ 
|  $Ubar \rightarrow "\bar{u}"$ 
|  $D \rightarrow "d"$ 
|  $Dbar \rightarrow "\bar{d}"$ 
|  $C \rightarrow "c"$ 
|  $Cbar \rightarrow "\bar{c}"$ 
|  $S \rightarrow "s"$ 
|  $Sbar \rightarrow "\bar{s}"$ 
|  $T \rightarrow "t"$ 
|  $Tbar \rightarrow "\bar{t}"$ 
|  $B \rightarrow "b"$ 
|  $Bbar \rightarrow "\bar{b}"$ 
|  $Gl \rightarrow "g"$ 

let flavor_symbol = function
|  $U \rightarrow "u"$ 
|  $Ubar \rightarrow "ubar"$ 
|  $D \rightarrow "d"$ 
|  $Dbar \rightarrow "dbar"$ 
|  $C \rightarrow "c"$ 
|  $Cbar \rightarrow "cbar"$ 
|  $S \rightarrow "s"$ 
|  $Sbar \rightarrow "sbar"$ 
|  $T \rightarrow "t"$ 
|  $Tbar \rightarrow "tbar"$ 
|  $B \rightarrow "b"$ 
|  $Bbar \rightarrow "bbar"$ 
|  $Gl \rightarrow "gl"$ 

let gauge_symbol () =
  failwith "Modellib.QCD.gauge_symbol:_internal_error"

let pdg = function
|  $D \rightarrow 1$  |  $Dbar \rightarrow -1$ 
|  $U \rightarrow 2$  |  $Ubar \rightarrow -2$ 
|  $S \rightarrow 3$  |  $Sbar \rightarrow -3$ 
|  $C \rightarrow 4$  |  $Cbar \rightarrow -4$ 
|  $B \rightarrow 5$  |  $Bbar \rightarrow -5$ 
|  $T \rightarrow 6$  |  $Tbar \rightarrow -6$ 
|  $Gl \rightarrow 21$ 

let mass_symbol f =
  "mass(" ^ string_of_int (abs (pdg f)) ^ ")"

```

```

let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"
let constant_symbol = function
| I_Gs → "(0,1)*gs"
| Gs → "gs"
| G2 → "gs**2"
end

```

13.4.5 Complete Minimal Standard Model (Unitarity Gauge)

```

module type SM_flags =
sig
  val higgs_triangle : bool (*  $H\gamma\gamma$ ,  $Hg\gamma$  and  $Hgg$  couplings *)
  val higgs_hmm : bool
  val triple_anom : bool
  val quartic_anom : bool
  val higgs_anom : bool
  val k_matrix : bool
  val ckm_present : bool
  val top_anom : bool
  val top_anom_4f : bool
end

module SM_no_anomalous : SM_flags =
struct
  let higgs_triangle = false
  let higgs_hmm = false
  let triple_anom = false
  let quartic_anom = false
  let higgs_anom = false
  let k_matrix = false
  let ckm_present = false
  let top_anom = false
  let top_anom_4f = false
end

module SM_no_anomalous_ckm : SM_flags =
struct
  let higgs_triangle = false
  let higgs_hmm = false
  let triple_anom = false
  let quartic_anom = false
  let higgs_anom = false
  let k_matrix = false
  let ckm_present = true
  let top_anom = false
  let top_anom_4f = false
end

```



```

module SM_anomalous : SM_flags =
  struct
    let higgs_triangle = false
    let higgs_hmm = false
    let triple_anom = true
    let quartic_anom = true
    let higgs_anom = true
    let k_matrix = false
    let ckm_present = false
    let top_anom = false
    let top_anom_4f = false
  end

module SM_anomalous_ckm : SM_flags =
  struct
    let higgs_triangle = false
    let higgs_hmm = false
    let triple_anom = true
    let quartic_anom = true
    let higgs_anom = true
    let k_matrix = false
    let ckm_present = true
    let top_anom = false
    let top_anom_4f = false
  end

module SM_k_matrix : SM_flags =
  struct
    let higgs_triangle = false
    let higgs_hmm = false
    let triple_anom = false
    let quartic_anom = true
    let higgs_anom = false
    let k_matrix = true
    let ckm_present = false
    let top_anom = false
    let top_anom_4f = false
  end

module SM_Higgs : SM_flags =
  struct
    let higgs_triangle = true
    let higgs_hmm = true
    let triple_anom = false
    let quartic_anom = false
    let higgs_anom = false
    let k_matrix = false
    let ckm_present = false
    let top_anom = false
    let top_anom_4f = false
  end

```

```

module SM_anomalous_top : SM_flags =
  struct
    let higgs_triangle = false
    let higgs_hmm = false
    let triple_anom = false
    let quartic_anom = false
    let higgs_anom = false
    let k_matrix = false
    let ckm_present = false
    let top_anom = true
    let top_anom_4f = true
  end

```

13.4.6 Complete Minimal Standard Model (including some extensions)

```

module SM (Flags : SM_flags) =
  struct
    let rcs = RCS.rename rcs_file "Modellib.SM"
      [ "minimal_electroweak_standard_model_in_unitarity_gauge" ]

    open Coupling

    let default_width = ref Timelike
    let use_fudged_width = ref false

    let options = Options.create
      [ "constant_width", Arg.Unit (fun () → default_width := Constant),
        "use_constant_width(also_in_t-channel)",
        "fudged_width", Arg.Set use_fudged_width,
        "use_fudge_factor_for_charge_particle_width",
        "custom_width", Arg.String (fun f → default_width := Custom f),
        "use_custom_width",
        "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
        "use_vanishing_width" ]

    type f_aux_top = TTGG | TBWA | TBWZ | TTWW | BBWW |
    let quartic_gauge =
      standard_quartic_gauge @ anomalous_quartic_gauge @ k_matrix_quartic_gauge

    let standard_gauge_higgs =
      [ ((O H, G Wp, G Wm), Scalar_Vector_Vector 1, G_HWW);
        ((O H, G Z, G Z), Scalar_Vector_Vector 1, G_HZZ) ]

    let standard_gauge_higgs4 =
      [ (O H, O H, G Wp, G Wm), Scalar2_Vector2 1, G_HHWW;
        (O H, O H, G Z, G Z), Scalar2_Vector2 1, G_HHZZ ]

    let standard_higgs =
      [ (O H, O H, O H), Scalar_Scalar_Scalar 1, G_H3 ]

    let standard_higgs4 =

```

$$[(O\ H, O\ H, O\ H, O\ H), \text{Scalar}_4\ 1, G\text{-}H_4]$$

WK's couplings (apparently, he still intends to divide by $\Lambda_{\text{EWSB}}^2 = 16\pi^2 v_F^2$):

$$\mathcal{L}_4^\tau = \left[(\partial_\mu H)(\partial^\mu H) + \frac{g^2 v_F^2}{4} V_\mu V^\mu \right]^2 \quad (13.1a)$$

$$\mathcal{L}_5^\tau = \left[(\partial_\mu H)(\partial_\nu H) + \frac{g^2 v_F^2}{4} V_\mu V_\nu \right]^2 \quad (13.1b)$$

with

$$V_\mu V_\nu = \frac{1}{2} (W_\mu^+ W_\nu^- + W_\nu^+ W_\mu^-) + \frac{1}{2 \cos^2 \theta_w} Z_\mu Z_\nu \quad (13.2)$$

(note the symmetrization!), i. e.

$$\mathcal{L}_4 = \alpha_4 \frac{g^4 v_F^4}{16} (V_\mu V_\nu)^2 \quad (13.3a)$$

$$\mathcal{L}_5 = \alpha_5 \frac{g^4 v_F^4}{16} (V_\mu V^\mu)^2 \quad (13.3b)$$

Breaking thinks up

$$\mathcal{L}_4^{\tau, H^4} = [(\partial_\mu H)(\partial^\mu H)]^2 \quad (13.4a)$$

$$\mathcal{L}_5^{\tau, H^4} = [(\partial_\mu H)(\partial^\mu H)]^2 \quad (13.4b)$$

and

$$\mathcal{L}_4^{\tau, H^2 V^2} = \frac{g^2 v_F^2}{2} (\partial_\mu H)(\partial^\mu H) V_\mu V^\mu \quad (13.5a)$$

$$\mathcal{L}_5^{\tau, H^2 V^2} = \frac{g^2 v_F^2}{2} (\partial_\mu H)(\partial_\nu H) V_\mu V_\nu \quad (13.5b)$$

i. e.

$$\mathcal{L}_4^{\tau, H^2 V^2} = \frac{g^2 v_F^2}{2} \left[(\partial_\mu H)(\partial^\mu H) W_\nu^+ W^{-, \nu} + \frac{1}{2 \cos^2 \theta_w} (\partial_\mu H)(\partial^\mu H) Z_\nu Z^\nu \right] \quad (13.6a)$$

$$\mathcal{L}_5^{\tau, H^2 V^2} = \frac{g^2 v_F^2}{2} \left[(W^{+, \mu} \partial_\mu H)(W^{-, \nu} \partial_\nu H) + \frac{1}{2 \cos^2 \theta_w} (Z^\mu \partial_\mu H)(Z^\nu \partial_\nu H) \right] \quad (13.6b)$$

$$\begin{aligned} \tau_8^4 \mathcal{L}_4^{\tau, H^2 V^2} + \tau_8^5 \mathcal{L}_5^{\tau, H^2 V^2} = & \\ & - \frac{g^2 v_F^2}{2} \left[2\tau_8^4 \frac{1}{2} (i\partial_\mu H)(i\partial^\mu H) W_\nu^+ W^{-, \nu} + \tau_8^5 (W^{+, \mu} i\partial_\mu H)(W^{-, \nu} i\partial_\nu H) \right. \\ & \left. + \frac{2\tau_8^4}{\cos^2 \theta_w} \frac{1}{4} (i\partial_\mu H)(i\partial^\mu H) Z_\nu Z^\nu + \frac{\tau_8^5}{\cos^2 \theta_w} \frac{1}{2} (Z^\mu i\partial_\mu H)(Z^\nu i\partial_\nu H) \right] \end{aligned} \quad (13.7)$$

where the two powers of i make the sign conveniently negative, i. e.

$$\alpha_{(\partial H)^2 W^2}^2 = \tau_8^4 g^2 v_F^2 \quad (13.8a)$$

$$\alpha_{(\partial HW)^2}^2 = \frac{\tau_8^5 g^2 v_F^2}{2} \quad (13.8b)$$

$$\alpha_{(\partial H)^2 Z^2}^2 = \frac{\tau_8^4 g^2 v_F^2}{\cos^2 \theta_w} \quad (13.8c)$$

$$\alpha_{(\partial HZ)^2}^2 = \frac{\tau_8^5 g^2 v_F^2}{2 \cos^2 \theta_w} \quad (13.8d)$$

```

let anomalous_gauge_higgs =
  [ (O H, G Ga, G Ga), Dim5_Scalar_Gauge2 1, G_HGaGa_anom;
    (O H, G Ga, G Z), Dim5_Scalar_Gauge2 1, G_HGaZ_anom;
    (O H, G Z, G Z), Dim5_Scalar_Gauge2 1, G_HZZ_anom;
    (O H, G Wp, G Wm), Dim5_Scalar_Gauge2 1, G_HWW_anom;
    (O H, G Ga, G Z), Dim5_Scalar_Vector_Vector_TU 1, G_HGaZ_u;
    (O H, G Z, G Z), Dim5_Scalar_Vector_Vector_U 1, G_HZZ_u;
    (O H, G Wp, G Wm), Dim5_Scalar_Vector_Vector_U 1, G_HWW_u
  ]

let anomalous_gauge_higgs4 =
  []

let anomalous_higgs =
  []

let higgs_triangle_vertices =
  if Flags.higgs_triangle then
    [ (O H, G Ga, G Ga), Dim5_Scalar_Gauge2 1, G_HGaGa;
      (O H, G Ga, G Z), Dim5_Scalar_Gauge2 1, G_HGaZ;
      (O H, G Gl, G Gl), Dim5_Scalar_Gauge2 1, G_Hgg ]
  else
    []

let anomalous_higgs4 =
  []

let gauge_higgs =
  if Flags.higgs_anom then
    standard_gauge_higgs @ anomalous_gauge_higgs
  else
    standard_gauge_higgs

let gauge_higgs4 =
  if Flags.higgs_anom then
    standard_gauge_higgs4 @ anomalous_gauge_higgs4
  else
    standard_gauge_higgs4

let higgs =
  if Flags.higgs_anom then
    standard_higgs @ anomalous_higgs
  else
    standard_higgs

let higgs4 =
  if Flags.higgs_anom then

```

```

    standard_higgs4 @ anomalous_higgs4
else
    standard_higgs4
let goldstone_vertices =
[ ((O Phi0, G Wm, G Wp), Scalar_Vector_Vector 1, I-G-ZWW);
  ((O Phip, G Ga, G Wm), Scalar_Vector_Vector 1, I-Q-W);
  ((O Phip, G Z, G Wm), Scalar_Vector_Vector 1, I-G-ZWW);
  ((O Phim, G Wp, G Ga), Scalar_Vector_Vector 1, I-Q-W);
  ((O Phim, G Wp, G Z), Scalar_Vector_Vector 1, I-G-ZWW) ]

```

Anomalous trilinear interactions $f_i f_j V$ and ttH :

$$\Delta \mathcal{L}_{tt\gamma} = -e \frac{v}{\Lambda^2} \bar{t} i \sigma^{\mu\nu} k_\nu (d_V(k^2) + i d_A(k^2) \gamma_5) t A_\mu \quad (13.9)$$

```

let anomalous_ttA =
  if Flags.top_anom then
    [ ((M (U (-3)), G Ga, M (U 3)), FBF (1, Psibar, TVAM, Psi), G-TVA_ttA) ]
  else
    []

```

$$\Delta \mathcal{L}_{bb\gamma} = -e \frac{v}{\Lambda^2} \bar{b} i \sigma^{\mu\nu} k_\nu (d_V(k^2) + i d_A(k^2) \gamma_5) b A_\mu \quad (13.10)$$

```

let anomalous_bbA =
  if Flags.top_anom then
    [ ((M (D (-3)), G Ga, M (D 3)), FBF (1, Psibar, TVAM, Psi), G-TVA_bbA) ]
  else
    []

```

$$\Delta \mathcal{L}_{ttg} = -g_s \frac{v}{\Lambda^2} \bar{t} \lambda^a i \sigma^{\mu\nu} k_\nu (d_V(k^2) + i d_A(k^2) \gamma_5) t G_\mu^a \quad (13.11)$$

```

let anomalous_ttG =
  if Flags.top_anom then
    [ ((M (U (-3)), G Gl, M (U 3)), FBF (1, Psibar, TVAM, Psi), G-TVA_ttG) ]
  else
    []

```

$$\Delta \mathcal{L}_{ttZ} = -\frac{g}{2c_W} \frac{v^2}{\Lambda^2} \left[\bar{t} \not{Z} (X_L(k^2) P_L + X_R(k^2) P_R) t + \bar{t} \frac{i \sigma^{\mu\nu} k_\nu}{m_Z} (d_V(k^2) + i d_A(k^2) \gamma_5) t Z_\mu \right] \quad (13.12)$$

```

let anomalous_ttZ =
  if Flags.top_anom then
    [ ((M (U (-3)), G Z, M (U 3)), FBF (1, Psibar, VLRM, Psi), G-VLR_ttZ);
      ((M (U (-3)), G Z, M (U 3)), FBF (1, Psibar, TVAM, Psi), G-TVA_ttZ) ]
  else
    []

```

$$\Delta\mathcal{L}_{bbZ} = -\frac{g}{2c_W} \frac{v^2}{\Lambda^2} \bar{b} \frac{i\sigma^{\mu\nu} k_\nu}{m_Z} (d_V(k^2) + id_A(k^2)\gamma_5) b Z_\mu \quad (13.13)$$

```

let anomalous_bbZ =
  if Flags.top_anom then
    [ ((M (D (-3)), G Z, M (D 3)), FBF (1, Psibar, TVAM, Psi), G_TVA_bbZ) ]
  else
    []

```

$$\Delta\mathcal{L}_{tbW} = -\frac{g}{\sqrt{2}} \frac{v^2}{\Lambda^2} \left[\bar{b} W^- (V_L(k^2)P_L + V_R(k^2)P_R)t + \bar{b} \frac{i\sigma^{\mu\nu} k_\nu}{m_W} (g_L(k^2)P_L + g_R(k^2)P_R)t W_\mu^- \right] + \text{H.c.} \quad (13.14)$$

```

let anomalous_tbW =
  if Flags.top_anom then
    [ ((M (D (-3)), G Wm, M (U 3)), FBF (1, Psibar, VLRM, Psi), G_VLR_btW);
      ((M (U (-3)), G Wp, M (D 3)), FBF (1, Psibar, VLRM, Psi), G_VLR_tbW);
      ((M (D (-3)), G Wm, M (U 3)), FBF (1, Psibar, TLRM, Psi), G_TLR_btW);
      ((M (U (-3)), G Wp, M (D 3)), FBF (1, Psibar, TRLM, Psi), G_TRL_tbW) ]
  else
    []

```

$$\Delta\mathcal{L}_{ttH} = -\frac{1}{\sqrt{2}} \bar{t} (Y_V(k^2) + iY_A(k^2)\gamma_5) t H \quad (13.15)$$

```

let anomalous_ttH =
  if Flags.top_anom then
    [ ((M (U (-3)), O H, M (U 3)), FBF (1, Psibar, SPM, Psi), G_SP_ttH) ]
  else
    []

```

quartic fermion-gauge interactions $f_i f_j V_1 V_2$ emerging from gauge-invariant effective operators:

$$\Delta\mathcal{L}_{ttgg} = -\frac{g_s^2}{2} f_{abc} \frac{v}{\Lambda^2} \bar{t} \lambda^a \sigma^{\mu\nu} (d_V(k^2) + id_A(k^2)\gamma_5) t G_\mu^b G_\nu^c \quad (13.16)$$

```

let anomalous_ttGG =
  if Flags.top_anom then
    [ ((M (U (-3)), O (Aux_top (2,1,0,true,TTGG)), M (U 3)), FBF (1, Psibar, TVA, Psi), G_TVA
      ((O (Aux_top (2,1,0,false,TTGG)), G Gl, G Gl), Aux_Gauge_Gauge 1, I_Gs) ]
  else
    []

```

$$\Delta\mathcal{L}_{tbWA} = -i \sin \theta_w \frac{g^2}{2\sqrt{2}} \frac{v^2}{\Lambda^2} \left[\bar{b} \frac{\sigma^{\mu\nu}}{m_W} (g_L(k^2)P_L + g_R(k^2)P_R) t A_\mu W_\nu^- \right] + \text{H.c.} \quad (13.17)$$

```

let anomalous_tbWA =

```

```

if Flags.top_anom then
  [ ((M (D (-3)), O (Aux_top (2, 0, -1, true, TBWA)), M (U 3)), FBF (1, Psibar, TLR, Psi), G_TL
    ((O (Aux_top (2, 0, 1, false, TBWA)), G Ga, G Wm), Aux_Gauge_Gauge 1, I_G_weak);
    ((M (U (-3)), O (Aux_top (2, 0, 1, true, TBWA)), M (D 3)), FBF (1, Psibar, TRL, Psi), G_TRL
    ((O (Aux_top (2, 0, -1, false, TBWA)), G Wp, G Ga), Aux_Gauge_Gauge 1, I_G_weak) ]
else
  []

```

$$\Delta\mathcal{L}_{tbWZ} = -i \cos\theta_w \frac{g^2}{2\sqrt{2}} \frac{v^2}{\Lambda^2} \left[\bar{b} \frac{\sigma^{\mu\nu}}{m_W} (g_L(k^2)P_L + g_R(k^2)P_R) t Z_\mu W_\nu^- \right] + \text{H.c.} \quad (13.18)$$

```

let anomalous_tbWZ =
  if Flags.top_anom then
    [ ((M (D (-3)), O (Aux_top (2, 0, -1, true, TBWZ)), M (U 3)), FBF (1, Psibar, TLR, Psi), G_TL
      ((O (Aux_top (2, 0, 1, false, TBWZ)), G Z, G Wm), Aux_Gauge_Gauge 1, I_G_weak);
      ((M (U (-3)), O (Aux_top (2, 0, 1, true, TBWZ)), M (D 3)), FBF (1, Psibar, TRL, Psi), G_TRL
      ((O (Aux_top (2, 0, -1, false, TBWZ)), G Wp, G Z), Aux_Gauge_Gauge 1, I_G_weak) ]
  else
    []

```

$$\Delta\mathcal{L}_{ttWW} = -i \frac{g^2}{2} \frac{v^2}{\Lambda^2} \bar{t} \frac{\sigma^{\mu\nu}}{m_W} (d_V(k^2) + i d_A(k^2) \gamma_5) t W_\mu^- W_\nu^+ \quad (13.19)$$

```

let anomalous_ttWW =
  if Flags.top_anom then
    [ ((M (U (-3)), O (Aux_top (2, 0, 0, true, TTWW)), M (U 3)), FBF (1, Psibar, TVA, Psi), G_TV
      ((O (Aux_top (2, 0, 0, false, TTWW)), G Wm, G Wp), Aux_Gauge_Gauge 1, I_G_weak) ]
  else
    []

```

$$\Delta\mathcal{L}_{bbWW} = -i \frac{g^2}{2} \frac{v^2}{\Lambda^2} \bar{b} \frac{\sigma^{\mu\nu}}{m_W} (d_V(k^2) + i d_A(k^2) \gamma_5) b W_\mu^- W_\nu^+ \quad (13.20)$$

```

let anomalous_bbWW =
  if Flags.top_anom then
    [ ((M (D (-3)), O (Aux_top (2, 0, 0, true, BBWW)), M (D 3)), FBF (1, Psibar, TVA, Psi), G_TV
      ((O (Aux_top (2, 0, 0, false, BBWW)), G Wm, G Wp), Aux_Gauge_Gauge 1, I_G_weak) ]
  else
    []

```

4-fermion contact terms emerging from operator rewriting:

```

let anomalous_top_qGuG_tt =
  [ ((M (U (-3)), O (Aux_top (1, 1, 0, true, QGUG)), M (U 3)), FBF (1, Psibar, VLR, Psi), G_VLR_q
let anomalous_top_qGuG_ff n =
  List.map mom
    [ ((U (-n), Aux_top (1, 1, 0, false, QGUG), U n), FBF (1, Psibar, V, Psi), Unit);
      ((D (-n), Aux_top (1, 1, 0, false, QGUG), D n), FBF (1, Psibar, V, Psi), Unit) ]

```

```

let anomalous_top_qGuG =
  if Flags.top_anom_4f then
    anomalous_top_qGuG_tt @ ThoList.flatmap anomalous_top_qGuG_ff [1; 2; 3]
  else
    []

let anomalous_top_qBuB_tt =
  [ ((M (U (-3)), O (Aux_top (1, 0, 0, true, QBUB)), M (U 3)), FBF (1, Psibar, VLR, Psi), G_VLR_q
let anomalous_top_qBuB_ff n =
  List.map mom
    [ ((U (-n), Aux_top (1, 0, 0, false, QBUB), U n), FBF (1, Psibar, VLR, Psi), G_VLR_qBuB_u);
      ((D (-n), Aux_top (1, 0, 0, false, QBUB), D n), FBF (1, Psibar, VLR, Psi), G_VLR_qBuB_d);
      ((L (-n), Aux_top (1, 0, 0, false, QBUB), L n), FBF (1, Psibar, VLR, Psi), G_VLR_qBuB_e);
      ((N (-n), Aux_top (1, 0, 0, false, QBUB), N n), FBF (1, Psibar, VL, Psi), G_VL_qBuB_n) ]

let anomalous_top_qBuB =
  if Flags.top_anom_4f then
    anomalous_top_qBuB_tt @ ThoList.flatmap anomalous_top_qBuB_ff [1; 2; 3]
  else
    []

let anomalous_top_qW_tq =
  [ ((M (U (-3)), O (Aux_top (1, 0, 0, true, QW)), M (U 3)), FBF (1, Psibar, VL, Psi), G_VL_qW);
    ((M (D (-3)), O (Aux_top (1, 0, -1, true, QW)), M (U 3)), FBF (1, Psibar, VL, Psi), G_VL_qW);
    ((M (U (-3)), O (Aux_top (1, 0, 1, true, QW)), M (D 3)), FBF (1, Psibar, VL, Psi), G_VL_qW) ]

let anomalous_top_qW_ff n =
  List.map mom
    [ ((U (-n), Aux_top (1, 0, 0, false, QW), U n), FBF (1, Psibar, VL, Psi), G_VL_qW_u);
      ((D (-n), Aux_top (1, 0, 0, false, QW), D n), FBF (1, Psibar, VL, Psi), G_VL_qW_d);
      ((N (-n), Aux_top (1, 0, 0, false, QW), N n), FBF (1, Psibar, VL, Psi), G_VL_qW_u);
      ((L (-n), Aux_top (1, 0, 0, false, QW), L n), FBF (1, Psibar, VL, Psi), G_VL_qW_d);
      ((D (-n), Aux_top (1, 0, -1, false, QW), U n), FBF (1, Psibar, VL, Psi), Half);
      ((U (-n), Aux_top (1, 0, 1, false, QW), D n), FBF (1, Psibar, VL, Psi), Half);
      ((L (-n), Aux_top (1, 0, -1, false, QW), N n), FBF (1, Psibar, VL, Psi), Half);
      ((N (-n), Aux_top (1, 0, 1, false, QW), L n), FBF (1, Psibar, VL, Psi), Half) ]

let anomalous_top_qW =
  if Flags.top_anom_4f then
    anomalous_top_qW_tq @ ThoList.flatmap anomalous_top_qW_ff [1; 2; 3]
  else
    []

let anomalous_top_DuDd =
  if Flags.top_anom_4f then
    [ ((M (U (-3)), O (Aux_top (0, 0, 0, true, DR)), M (U 3)), FBF (1, Psibar, SR, Psi), Half);
      ((M (U (-3)), O (Aux_top (0, 0, 0, false, DR)), M (U 3)), FBF (1, Psibar, SL, Psi), G_SL_DttR);
      ((M (D (-3)), O (Aux_top (0, 0, 0, false, DR)), M (D 3)), FBF (1, Psibar, SR, Psi), G_SR_DttR);
      ((M (U (-3)), O (Aux_top (0, 0, 0, true, DL)), M (U 3)), FBF (1, Psibar, SL, Psi), Half);
      ((M (D (-3)), O (Aux_top (0, 0, 0, false, DL)), M (D 3)), FBF (1, Psibar, SL, Psi), G_SL_DttL);
      ((M (D (-3)), O (Aux_top (0, 0, -1, true, DR)), M (U 3)), FBF (1, Psibar, SR, Psi), Half);
      ((M (U (-3)), O (Aux_top (0, 0, 1, false, DR)), M (D 3)), FBF (1, Psibar, SLR, Psi), G_SLR_D);
      ((M (D (-3)), O (Aux_top (0, 0, -1, true, DL)), M (U 3)), FBF (1, Psibar, SL, Psi), Half);

```



```

      ((M (U (-3)), O (Aux_top (0, 0, 1, false, DL)), M (D 3)), FBF (1, Psibar, SL, Psi), G_SL_DbtL)
    else
      []
  let anomalous_top_quqd1_tq =
    [ ((M (D (-3)), O (Aux_top (0, 0, -1, true, QUQD1R)), M (U 3)), FBF (1, Psibar, SR, Psi), C_quqd1_tq),
      ((M (U (-3)), O (Aux_top (0, 0, 1, true, QUQD1R)), M (D 3)), FBF (1, Psibar, SL, Psi), C_quqd1_tq),
      ((M (D (-3)), O (Aux_top (0, 0, -1, true, QUQD1L)), M (U 3)), FBF (1, Psibar, SL, Psi), C_quqd1_tq),
      ((M (U (-3)), O (Aux_top (0, 0, 1, true, QUQD1L)), M (D 3)), FBF (1, Psibar, SR, Psi), C_quqd1_tq) ]
  let anomalous_top_quqd1_ff n =
    List.map mom
      [ ((U (-n), Aux_top (0, 0, 1, false, QUQD1R), D n), FBF (1, Psibar, SR, Psi), Half);
        ((D (-n), Aux_top (0, 0, -1, false, QUQD1R), U n), FBF (1, Psibar, SL, Psi), Half);
        ((U (-n), Aux_top (0, 0, 1, false, QUQD1L), D n), FBF (1, Psibar, SL, Psi), Half);
        ((D (-n), Aux_top (0, 0, -1, false, QUQD1L), U n), FBF (1, Psibar, SR, Psi), Half) ]
  let anomalous_top_quqd1 =
    if Flags.top_anom_4f then
      anomalous_top_quqd1_tq @ ThoList.flatmap anomalous_top_quqd1_ff [1; 2; 3]
    else
      []
  let anomalous_top_quqd8_tq =
    [ ((M (D (-3)), O (Aux_top (0, 1, -1, true, QUQD8R)), M (U 3)), FBF (1, Psibar, SR, Psi), C_quqd8_tq),
      ((M (U (-3)), O (Aux_top (0, 1, 1, true, QUQD8R)), M (D 3)), FBF (1, Psibar, SL, Psi), C_quqd8_tq),
      ((M (D (-3)), O (Aux_top (0, 1, -1, true, QUQD8L)), M (U 3)), FBF (1, Psibar, SL, Psi), C_quqd8_tq),
      ((M (U (-3)), O (Aux_top (0, 1, 1, true, QUQD8L)), M (D 3)), FBF (1, Psibar, SR, Psi), C_quqd8_tq) ]
  let anomalous_top_quqd8_ff n =
    List.map mom
      [ ((U (-n), Aux_top (0, 1, 1, false, QUQD8R), D n), FBF (1, Psibar, SR, Psi), Half);
        ((D (-n), Aux_top (0, 1, -1, false, QUQD8R), U n), FBF (1, Psibar, SL, Psi), Half);
        ((U (-n), Aux_top (0, 1, 1, false, QUQD8L), D n), FBF (1, Psibar, SL, Psi), Half);
        ((D (-n), Aux_top (0, 1, -1, false, QUQD8L), U n), FBF (1, Psibar, SR, Psi), Half) ]
  let anomalous_top_quqd8 =
    if Flags.top_anom_4f then
      anomalous_top_quqd8_tq @ ThoList.flatmap anomalous_top_quqd8_ff [1; 2; 3]
    else
      []
  let vertices3 =
    (ThoList.flatmap electromagnetic_currents [1; 2; 3] @
     ThoList.flatmap color_currents [1; 2; 3] @
     ThoList.flatmap neutral_currents [1; 2; 3] @
     (if Flags.ckm_present then
        charged_currents_ckm
      else
        charged_currents_triv) @
     yukawa @ triple_gauge @
     gauge_higgs @ higgs @ higgs_triangle_vertices
    @ goldstone_vertices @
    anomalous_ttA @ anomalous_bbA @

```

```

anomalous_ttZ @ anomalous_bbZ @
anomalous_tbW @ anomalous_tbWA @ anomalous_tbWZ @
anomalous_ttWW @ anomalous_bbWW @
anomalous_ttG @ anomalous_ttGG @
anomalous_ttH @
anomalous_top_qGuG @ anomalous_top_qBuB @
anomalous_top_qW @ anomalous_top_DuDd @
anomalous_top_quqd1 @ anomalous_top_quqd8)

```

```

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4
let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4
let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))
| "numu" → M (N 2) | "numubar" → M (N (-2))
| "nutau" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "g" | "gl" → G Gl
| "A" → G Ga | "Z" | "ZO" → G Z
| "W+" → G Wp | "W-" → G Wm
| "H" → O H
| "Aux_t_ttGG0" → O (Aux_top (2, 1, 0, true, TTGG)) | "Aux_ttGG0" →
O (Aux_top (2, 1, 0, false, TTGG))
| "Aux_t_ttbWA+" → O (Aux_top (2, 0, 1, true, TBWA)) | "Aux_ttbWA+" →
O (Aux_top (2, 0, 1, false, TBWA))
| "Aux_t_ttbWA-" → O (Aux_top (2, 0, -1, true, TBWA)) | "Aux_ttbWA-" →
O (Aux_top (2, 0, -1, false, TBWA))
| "Aux_t_ttbWZ+" → O (Aux_top (2, 0, 1, true, TBWZ)) | "Aux_ttbWZ+" →
O (Aux_top (2, 0, 1, false, TBWZ))
| "Aux_t_ttbWZ-" → O (Aux_top (2, 0, -1, true, TBWZ)) | "Aux_ttbWZ-" →
O (Aux_top (2, 0, -1, false, TBWZ))
| "Aux_t_ttWW0" → O (Aux_top (2, 0, 0, true, TTWW)) | "Aux_ttWW0" →
O (Aux_top (2, 0, 0, false, TTWW))
| "Aux_t_bbWW0" → O (Aux_top (2, 0, 0, true, BBWW)) | "Aux_bbWW0" →
O (Aux_top (2, 0, 0, false, BBWW))

```

```

    | "Aux_t_qGuG0" → O (Aux_top (1, 1, 0, true, QGUG)) | "Aux_qGuG0" →
O (Aux_top (1, 1, 0, false, QGUG))
    | "Aux_t_qBuB0" → O (Aux_top (1, 0, 0, true, QBUB)) | "Aux_qBuB0" →
O (Aux_top (1, 0, 0, false, QBUB))
    | "Aux_t_qW0" → O (Aux_top (1, 0, 0, true, QW)) | "Aux_qW0" →
O (Aux_top (1, 0, 0, false, QW))
    | "Aux_t_qW+" → O (Aux_top (1, 0, 1, true, QW)) | "Aux_qW+" →
O (Aux_top (1, 0, 1, false, QW))
    | "Aux_t_qW-" → O (Aux_top (1, 0, -1, true, QW)) | "Aux_qW-" →
O (Aux_top (1, 0, -1, false, QW))
    | "Aux_t_dL0" → O (Aux_top (0, 0, 0, true, DL)) | "Aux_dL0" →
O (Aux_top (0, 0, 0, false, DL))
    | "Aux_t_dL+" → O (Aux_top (0, 0, 1, true, DL)) | "Aux_dL+" →
O (Aux_top (0, 0, 1, false, DL))
    | "Aux_t_dL-" → O (Aux_top (0, 0, -1, true, DL)) | "Aux_dL-" →
O (Aux_top (0, 0, -1, false, DL))
    | "Aux_t_dR0" → O (Aux_top (0, 0, 0, true, DR)) | "Aux_dR0" →
O (Aux_top (0, 0, 0, false, DR))
    | "Aux_t_dR+" → O (Aux_top (0, 0, 1, true, DR)) | "Aux_dR+" →
O (Aux_top (0, 0, 1, false, DR))
    | "Aux_t_dR-" → O (Aux_top (0, 0, -1, true, DR)) | "Aux_dR-" →
O (Aux_top (0, 0, -1, false, DR))
    | "Aux_t_quqd1L+" → O (Aux_top (0, 0, 1, true, QUQD1L)) | "Aux_quqd1L+" →
O (Aux_top (0, 0, 1, false, QUQD1L))
    | "Aux_t_quqd1L-" → O (Aux_top (0, 0, -1, true, QUQD1L)) | "Aux_quqd1L-" →
O (Aux_top (0, 0, -1, false, QUQD1L))
    | "Aux_t_quqd1R+" → O (Aux_top (0, 0, 1, true, QUQD1R)) | "Aux_quqd1R+" →
O (Aux_top (0, 0, 1, false, QUQD1R))
    | "Aux_t_quqd1R-" → O (Aux_top (0, 0, -1, true, QUQD1R)) | "Aux_quqd1R-" →
O (Aux_top (0, 0, -1, false, QUQD1R))
    | "Aux_t_quqd8L+" → O (Aux_top (0, 1, 1, true, QUQD8L)) | "Aux_quqd8L+" →
O (Aux_top (0, 1, 1, false, QUQD8L))
    | "Aux_t_quqd8L-" → O (Aux_top (0, 1, -1, true, QUQD8L)) | "Aux_quqd8L-" →
O (Aux_top (0, 1, -1, false, QUQD8L))
    | "Aux_t_quqd8R+" → O (Aux_top (0, 1, 1, true, QUQD8R)) | "Aux_quqd8R+" →
O (Aux_top (0, 1, 1, false, QUQD8R))
    | "Aux_t_quqd8R-" → O (Aux_top (0, 1, -1, true, QUQD8R)) | "Aux_quqd8R-" →
O (Aux_top (0, 1, -1, false, QUQD8R))
    | _ → invalid_arg "Modellib.SM.flavor_of_string"

let flavor_to_string = function
| M f →
    begin match f with
    | L 1 → "e-" | L (-1) → "e+"
    | L 2 → "mu-" | L (-2) → "mu+"
    | L 3 → "tau-" | L (-3) → "tau+"
    | L _ → invalid_arg
    "Modellib.SM.flavor_to_string:␣invalid␣lepton"
    | N 1 → "nue" | N (-1) → "nuebar"
    | N 2 → "numu" | N (-2) → "numubar"

```

```

| N 3 → "nutau" | N (-3) → "nutaubar"
| N _ → invalid_arg
      "Modellib.SM.flavor_to_string:␣invalid␣neutrino"
| U 1 → "u" | U (-1) → "ubar"
| U 2 → "c" | U (-2) → "cbar"
| U 3 → "t" | U (-3) → "tbar"
| U _ → invalid_arg
      "Modellib.SM.flavor_to_string:␣invalid␣up␣type␣quark"
| D 1 → "d" | D (-1) → "dbar"
| D 2 → "s" | D (-2) → "sbar"
| D 3 → "b" | D (-3) → "bbar"
| D _ → invalid_arg
      "Modellib.SM.flavor_to_string:␣invalid␣down␣type␣quark"
end
| G f →
  begin match f with
  | Gl → "gl"
  | Ga → "A" | Z → "Z"
  | Wp → "W+" | Wm → "W-"
  end
| O f →
  begin match f with
  | Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
  | H → "H"
  | Aux_top (_, -, ch, n, v) → "Aux_" ^ (if n then "t_" else "") ^ (
    begin match v with
    | TTGG → "ttGG" | TBWA → "tbWA" | TBWZ →
"tbWZ"
    | TTWW → "ttWW" | BBWW → "bbWW"
    | QGUG → "qGuG" | QBUB → "qBuB"
    | QW → "qW" | DL → "dL" | DR → "dR"
    | QUQD1L → "quqd1L" | QUQD1R → "quqd1R"
    | QUQD8L → "quqd8L" | QUQD8R → "quqd8R"
    end ) ^ ( if ch > 0 then "+" else if ch < 0 then "-" else "0" )
  end
let flavor_to_TeX = function
| M f →
  begin match f with
  | L 1 → "e~-" | L (-1) → "e~+"
  | L 2 → "\\mu~-" | L (-2) → "\\mu~+"
  | L 3 → "\\tau~-" | L (-3) → "\\tau~+"
  | L _ → invalid_arg
    "Modellib.SM.flavor_to_TeX:␣invalid␣lepton"
  | N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
  | N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
  | N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
  | N _ → invalid_arg
    "Modellib.SM.flavor_to_TeX:␣invalid␣neutrino"
  | U 1 → "u" | U (-1) → "\\bar{u}"

```

```

| U 2 → "c" | U (-2) → "\\bar{c}"
| U 3 → "t" | U (-3) → "\\bar{t}"
| U _ → invalid_arg
      "Modellib.SM.flavor_to_TeX:invalid_up_type_quark"
| D 1 → "d" | D (-1) → "\\bar{d}"
| D 2 → "s" | D (-2) → "\\bar{s}"
| D 3 → "b" | D (-3) → "\\bar{b}"
| D _ → invalid_arg
      "Modellib.SM.flavor_to_TeX:invalid_down_type_quark"
end
| G f →
  begin match f with
  | Gl → "g"
  | Ga → "\\gamma" | Z → "Z"
  | Wp → "W^+" | Wm → "W^- "
  end
| O f →
  begin match f with
  | Phip → "\\phi^+" | Phim → "\\phi^- " | Phi0 →
    "\\phi^0"
  | H → "H"
  | Aux_top (_, -, ch, n, v) → "\\textnormal{Aux-} ^ (if n then \"t_\" else \"\") ^ (
    begin match v with
    | TTGG → "ttGG" | TBWA → "tbWA" | TBWZ →
      "tbWZ"
    | TTWW → "ttWW" | BBWW → "bbWW"
    | QGUG → "qGuG" | QBUB → "qBuB"
    | QW → "qW" | DL → "dL" | DR → "dR"
    | QUQD1L → "quqd1L" | QUQD1R → "quqd1R"
    | QUQD8L → "quqd8L" | QUQD8R → "quqd8R"
    end) ^ (if ch > 0 then "^+" else if ch < 0 then "^-" else "^0") ^ "}"
  end
let flavor_symbol = function
| M f →
  begin match f with
  | L n when n > 0 → "l" ^ string_of_int n
  | L n → "l" ^ string_of_int (abs n) ^ "b"
  | N n when n > 0 → "n" ^ string_of_int n
  | N n → "n" ^ string_of_int (abs n) ^ "b"
  | U n when n > 0 → "u" ^ string_of_int n
  | U n → "u" ^ string_of_int (abs n) ^ "b"
  | D n when n > 0 → "d" ^ string_of_int n
  | D n → "d" ^ string_of_int (abs n) ^ "b"
  end
| G f →
  begin match f with
  | Gl → "gl"
  | Ga → "a" | Z → "z"
  | Wp → "wp" | Wm → "wm"

```

```

    end
  |  $O f \rightarrow$ 
    begin match  $f$  with
    |  $Phip \rightarrow "pp"$  |  $Phim \rightarrow "pm"$  |  $Phi0 \rightarrow "p0"$ 
    |  $H \rightarrow "h"$ 
    |  $Aux\_top(-, -, ch, n, v) \rightarrow "aux\_"$  ^ (if  $n$  then "t_" else "") ^ (
      begin match  $v$  with
      |  $TTGG \rightarrow "ttgg"$  |  $TBWA \rightarrow "tbwa"$  |  $TBWZ \rightarrow$ 
"tbwz"
      |  $TTWW \rightarrow "ttww"$  |  $BBWW \rightarrow "bbww"$ 
      |  $QGUG \rightarrow "qgug"$  |  $QBUB \rightarrow "qbub"$ 
      |  $QW \rightarrow "qw"$  |  $DL \rightarrow "dl"$  |  $DR \rightarrow "dr"$ 
      |  $QUQD1L \rightarrow "quqd1l"$  |  $QUQD1R \rightarrow "quqd1r"$ 
      |  $QUQD8L \rightarrow "quqd8l"$  |  $QUQD8R \rightarrow "quqd8r"$ 
      end) ^ " _ " ^ (if  $ch > 0$  then "p" else if  $ch < 0$  then "m" else "0")
    end
let  $pdg =$  function
|  $M f \rightarrow$ 
  begin match  $f$  with
  |  $L n$  when  $n > 0 \rightarrow 9 + 2 \times n$ 
  |  $L n \rightarrow - 9 + 2 \times n$ 
  |  $N n$  when  $n > 0 \rightarrow 10 + 2 \times n$ 
  |  $N n \rightarrow - 10 + 2 \times n$ 
  |  $U n$  when  $n > 0 \rightarrow 2 \times n$ 
  |  $U n \rightarrow 2 \times n$ 
  |  $D n$  when  $n > 0 \rightarrow - 1 + 2 \times n$ 
  |  $D n \rightarrow 1 + 2 \times n$ 
  end
|  $G f \rightarrow$ 
  begin match  $f$  with
  |  $Gl \rightarrow 21$ 
  |  $Ga \rightarrow 22$  |  $Z \rightarrow 23$ 
  |  $Wp \rightarrow 24$  |  $Wm \rightarrow (-24)$ 
  end
|  $O f \rightarrow$ 
  begin match  $f$  with
  |  $Phip$  |  $Phim \rightarrow 27$  |  $Phi0 \rightarrow 26$ 
  |  $H \rightarrow 25$ 
  |  $Aux\_top(-, -, ch, t, f) \rightarrow$  let  $n =$ 
    begin match  $f$  with
    |  $QW \rightarrow 0$ 
    |  $QUQD1R \rightarrow 1$  |  $QUQD1L \rightarrow 2$ 
    |  $QUQD8R \rightarrow 3$  |  $QUQD8L \rightarrow 4$ 
    |  $- \rightarrow 5$ 
    end
    in  $(602 + 3 \times n - ch) \times (if\ t\ then\ (1)\ else\ (-1))$ 
  end
let  $mass\_symbol\ f =$ 
  "mass(" ^  $string\_of\_int\ (abs\ (pdg\ f))$  ^ ")"

```

```

let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"

let constant_symbol = function
| Unit → "unit" | Half → "half" | Pi → "PI"
| Alpha_QED → "alpha" | E → "e" | G_weak → "g" | Vev →
"vev"
| I_G_weak → "ig"
| Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
| Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdw"
| G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
| G_NC_up → "gncup" | G_NC_down → "gncdwn"
| G_TVA_ttA → "gtva-tta" | G_TVA_bbA → "gtva-bba"
| G_VLR_ttZ → "gvlr-ttz" | G_TVA_ttZ → "gtva-ttz" |
G_TVA_bbZ → "gtva-bbz"
| G_VLR_btW → "gvlr-btw" | G_VLR_tbW → "gvlr-tbw"
| G_TLR_btW → "gtlr-btw" | G_TRL_tbW → "gtrl-tbw"
| G_TLR_btWA → "gtlr-btwa" | G_TRL_tbWA → "gtrl-tbwa"
| G_TLR_btWZ → "gtlr-btwz" | G_TRL_tbWZ → "gtrl-tbwz"
| G_TVA_ttWW → "gtva-ttww" | G_TVA_bbWW → "gtva-bbww"
| G_TVA_ttG → "gtva-ttg" | G_TVA_ttGG → "gtva-ttgg"
| G_SP_ttH → "gsp-tth"
| G_VLR_qGuG → "gvlr-qgug"
| G_VLR_qBuB → "gvlr-qbub"
| G_VLR_qBuB_u → "gvlr-qbub-u" | G_VLR_qBuB_d → "gvlr-qbub-d"
| G_VLR_qBuB_e → "gvlr-qbub-e" | G_VL_qBuB_n → "gvl-qbub-n"
| G_VL_qW → "gvl-qw"
| G_VL_qW_u → "gvl-qw-u" | G_VL_qW_d → "gvl-qw-d"
| G_SL_DttR → "gsl-dttr" | G_SR_DttR → "gsr-dttr" |
G_SL_DttL → "gsl-dttl"
| G_SLR_DbtR → "gslr-dbtr" | G_SL_DbtL → "gsl-dbtl"
| C_quqd1R_bt → "c-quqd1.1" | C_quqd1R_tb → "conjg(c-quqd1.1)"
| C_quqd1L_bt → "conjg(c-quqd1.2)" | C_quqd1L_tb → "c-quqd1.2"
| C_quqd8R_bt → "c-quqd8.1" | C_quqd8R_tb → "conjg(c-quqd8.1)"
| C_quqd8L_bt → "conjg(c-quqd8.2)" | C_quqd8L_tb → "c-quqd8.2"
| G_CC → "gcc"
| G_CCQ (n1, n2) → "gccq" ^ string_of_int n1 ^ string_of_int n2
| I_Q_W → "iqw" | I_G_ZWW → "igzww"
| G_WWWW → "gw4" | G_ZZWW → "gzzww"
| G_AZWW → "gazww" | G_AAWW → "gaaww"
| I_G1_AWW → "ig1a" | I_G1_ZWW → "ig1z"
| I_G1_plus_kappa_plus_G4_AWW → "ig1pkpg4a"
| I_G1_plus_kappa_plus_G4_ZWW → "ig1pkpg4z"
| I_G1_plus_kappa_minus_G4_AWW → "ig1pkmg4a"
| I_G1_plus_kappa_minus_G4_ZWW → "ig1pkmg4z"
| I_G1_minus_kappa_plus_G4_AWW → "ig1mkpg4a"
| I_G1_minus_kappa_plus_G4_ZWW → "ig1mkpg4z"
| I_G1_minus_kappa_minus_G4_AWW → "ig1mkmg4a"
| I_G1_minus_kappa_minus_G4_ZWW → "ig1mkmg4z"

```

```

| I_lambda_AWW → "ila"
| I_lambda_ZWW → "ilz"
| G5_AWW → "rg5a"
| G5_ZWW → "rg5z"
| I_kappa5_AWW → "ik5a"
| I_kappa5_ZWW → "ik5z"
| I_lambda5_AWW → "il5a" | I_lambda5_ZWW → "il5z"
| Alpha_WWWW0 → "alww0" | Alpha_WWWW2 → "alww2"
| Alpha_ZZWW0 → "alzw0" | Alpha_ZZWW1 → "alzw1"
| Alpha_ZZZZ → "alzz"
| D_Alpha_ZZWW0_S → "dalzz0_s(gkm,mkm,"
| D_Alpha_ZZWW0_T → "dalzz0_t(gkm,mkm,"
| D_Alpha_ZZWW1_S → "dalzz1_s(gkm,mkm,"
| D_Alpha_ZZWW1_T → "dalzz1_t(gkm,mkm,"
| D_Alpha_ZZWW1_U → "dalzz1_u(gkm,mkm,"
| D_Alpha_WWWW0_S → "dalww0_s(gkm,mkm,"
| D_Alpha_WWWW0_T → "dalww0_t(gkm,mkm,"
| D_Alpha_WWWW0_U → "dalww0_u(gkm,mkm,"
| D_Alpha_WWWW2_S → "dalww2_s(gkm,mkm,"
| D_Alpha_WWWW2_T → "dalww2_t(gkm,mkm,"
| D_Alpha_ZZZZ_S → "dalz4_s(gkm,mkm,"
| D_Alpha_ZZZZ_T → "dalz4_t(gkm,mkm,"
| G_HWW → "ghww" | G_HZZ → "ghzz"
| G_HHWW → "ghhww" | G_HHZZ → "ghhzz"
| G_Htt → "ghtt" | G_Hbb → "ghbb"
| G_Htautau → "ghtautau" | G_Hcc → "ghcc" | G_Hmm →
"ghmm"
| G_HGaZ → "ghgaz" | G_HGaGa → "ghgaga" | G_Hgg →
"ghgg"
| G_HGaGa_anom → "ghgaga_ac" | G_HGaZ_anom → "ghgaz_ac"
| G_HZZ_anom → "ghzz_ac" | G_HWW_anom → "ghww_ac"
| G_HGaZ_u → "ghgaz_u" | G_HZZ_u → "ghzz_u"
| G_HWW_u → "ghww_u"
| G_H3 → "gh3" | G_H4 → "gh4"
| Gs → "gs" | I_Gs → "igs" | G2 → "gs**2"
| Mass f → "mass" ^ flavor_symbol f
| Width f → "width" ^ flavor_symbol f
| K_Matrix_Coeff i → "kc" ^ string_of_int i
| K_Matrix_Pole i → "kp" ^ string_of_int i
end

```

13.4.7 Incomplete Standard Model in R_ξ Gauge



At the end of the day, we want a functor mapping from gauge models in unitarity gauge to R_ξ gauge and vice versa. For this, we will need a more abstract implementation of (spontaneously broken) gauge theories.


```

module SM_Rxi =
struct
  let rcs = RCS.rename rcs_file "Modellib.SM_Rxi"
    [ "minimal_electroweak_standard_model_in_R-xi_gauge";
      "NB: very incomplete still!, no CKM matrix" ]

  open Coupling

  module SM = SM(SM_no_anomalous)
  let options = SM.options
  type flavor = SM.flavor
  let flavors = SM.flavors
  let external_flavors = SM.external_flavors
  type orders = SM.orders
  type constant = SM.constant
  let orders = SM.orders
  let lorentz = SM.lorentz
  let color = SM.color
  let goldstone = SM.goldstone
  let conjugate = SM.conjugate
  let fermion = SM.fermion

```



Check if it makes sense to have separate gauge fixing parameters for each vector boson. There's probably only one independent parameter for each group factor.

```

type gauge =
  | XiA | XiZ | XiW

let gauge_symbol = function
  | XiA → "xia" | XiZ → "xi0" | XiW → "xipm"

```

Change the gauge boson propagators and make the Goldstone bosons propagating.

```

let propagator = function
  | SM.G SM.Ga → Prop_Gauge XiA
  | SM.G SM.Z → Prop_Rxi XiZ
  | SM.G SM.Wp | SM.G SM.Wm → Prop_Rxi XiW
  | SM.O SM.Phip | SM.O SM.Phim | SM.O SM.Phi0 → Prop_Scalar
  | f → SM.propagator f

let width = SM.width

module Ch = Charges.QQ
let charges = SM.charges

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

```

```

let vertices = SM.vertices
let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 3

let parameters = SM.parameters
let flavor_of_string = SM.flavor_of_string
let flavor_to_string = SM.flavor_to_string
let flavor_to_TeX = SM.flavor_to_TeX
let flavor_symbol = SM.flavor_symbol
let pdg = SM.pdg
let mass_symbol = SM.mass_symbol
let width_symbol = SM.width_symbol
let constant_symbol = SM.constant_symbol
end

```

13.4.8 QCD with electroweak insertions.

```

module SM_QCD =
struct
  let rcs = RCS.rename rcs_file "Modellib.SM_QCD"
    [ "QCD_with_electroweak_insertions" ]

  open Coupling

  let default_width = ref Timelike
  let use_fudged_width = ref false

  let options = Options.create
    [ "constant_width", Arg.Unit (fun () → default_width := Constant),
      "use_constant_width(also_in_t-channel);",
      "fudged_width", Arg.Set use_fudged_width,
      "use_fudge_factor_for_charge_particle_width;",
      "custom_width", Arg.String (fun f → default_width := Custom f),
      "use_custom_width;",
      "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
      "use_vanishing_width" ]

  type matter_field = L of int | N of int | U of int | D of int
  type gauge_boson = Ga | GaX | Wp | Wm | Z | Gl
  type other = H
  type flavor = M of matter_field | G of gauge_boson | O of other

  let matter_field f = M f
  let gauge_boson f = G f
  let other f = O f

  type field =
    | Matter of matter_field

```

```

    | Gauge of gauge_boson
    | Other of other

let field = function
  | M f → Matter f
  | G f → Gauge f
  | O f → Other f

type gauge = unit

let gauge_symbol () =
  failwith "Modellib.SM.QCD.gauge_symbol:␣internal␣error"

let family n = List.map matter_field [ L n; N n; U n; D n ]

let external_flavors () =
  [ "1st_Generation", ThoList.flatmap family [1; -1];
    "2nd_Generation", ThoList.flatmap family [2; -2];
    "3rd_Generation", ThoList.flatmap family [3; -3];
    "Gauge_Bosons", List.map gauge_boson [Ga; GaX; Z; Wp; Wm; Gl];
    "Higgs", List.map other [H] ]

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n =
  if n ≥ 0 then
    Spinor
  else
    ConjSpinor

let lorentz_aux = function
  | 2 → Tensor_1
  | 1 → Vector
  | 0 → Scalar
  | _ → invalid_arg ("SM-QCD.lorentz_aux:␣wrong␣value")

let lorentz = function
  | M f →
    begin match f with
    | L n → spinor n | N n → spinor n
    | U n → spinor n | D n → spinor n
    end
  | G f →
    begin match f with
    | Ga | GaX | Gl → Vector
    | Wp | Wm | Z → Massive_Vector
    end
  | O f →
    begin match f with
    | _ → Scalar
    end

let color = function
  | M (U n) → Color.SUN (if n > 0 then 3 else -3)
  | M (D n) → Color.SUN (if n > 0 then 3 else -3)

```

```

|  $G \ Gl \rightarrow Color.AdjSUN\ 3$ 
|  $- \rightarrow Color.Singlet$ 

let prop_spinor n =
  if  $n \geq 0$  then
    Prop_Spinor
  else
    Prop_ConjSpinor

let prop_aux = function
| 2  $\rightarrow Aux\_Tensor\_1$ 
| 1  $\rightarrow Aux\_Vector$ 
| 0  $\rightarrow Aux\_Scalar$ 
|  $- \rightarrow invalid\_arg\ ("SM\_QCD.prop\_aux:\_wrong\_value")$ 

let propagator = function
|  $M\ f \rightarrow$ 
  begin match  $f$  with
  |  $L\ n \rightarrow prop\_spinor\ n$  |  $N\ n \rightarrow prop\_spinor\ n$ 
  |  $U\ n \rightarrow prop\_spinor\ n$  |  $D\ n \rightarrow prop\_spinor\ n$ 
  end
|  $G\ f \rightarrow$ 
  begin match  $f$  with
  |  $Ga$  |  $GaX$  |  $Gl \rightarrow Prop\_Feynman$ 
  |  $Wp$  |  $Wm$  |  $Z \rightarrow Prop\_Unitarity$ 
  end
|  $O\ f \rightarrow$ 
  begin match  $f$  with
  |  $H \rightarrow Prop\_Scalar$ 
  end
end

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    |  $G\ Wp$  |  $G\ Wm$  |  $M\ (U\ 3)$  |  $M\ (U\ (-3)) \rightarrow Fudged$ 
    |  $- \rightarrow !default\_width$ 
  else
    !default_width

let goldstone _ = None

let conjugate = function
|  $M\ f \rightarrow$ 
  M (begin match  $f$  with
  |  $L\ n \rightarrow L\ (-n)$  |  $N\ n \rightarrow N\ (-n)$ 
  |  $U\ n \rightarrow U\ (-n)$  |  $D\ n \rightarrow D\ (-n)$ 
  end)
|  $G\ f \rightarrow$ 
  G (begin match  $f$  with
  |  $Gl \rightarrow Gl$  |  $Ga \rightarrow GaX$  |  $Z \rightarrow Z$ 
  |  $GaX \rightarrow Ga$  |  $Wp \rightarrow Wm$  |  $Wm \rightarrow Wp$ 

```

```

    end)
  |  $O f \rightarrow$ 
     $O$  (begin match  $f$  with
    |  $H \rightarrow H$ 
    end)

let fermion = function
  |  $M f \rightarrow$ 
    begin match  $f$  with
    |  $L n \rightarrow$  if  $n > 0$  then 1 else -1
    |  $N n \rightarrow$  if  $n > 0$  then 1 else -1
    |  $U n \rightarrow$  if  $n > 0$  then 1 else -1
    |  $D n \rightarrow$  if  $n > 0$  then 1 else -1
    end
  |  $G f \rightarrow$ 
    begin match  $f$  with
    |  $Gl$  |  $Ga$  |  $GaX$  |  $Z$  |  $Wp$  |  $Wm \rightarrow 0$ 
    end
  |  $O _ \rightarrow 0$ 

```

Electrical charge, lepton number, baryon number. We could avoid the rationals altogether by multiplying the first and last by 3 ...

```

module Ch = Charges.QQ
let ( // ) = Algebra.Small_Rational.make

let generation' = function
  | 1  $\rightarrow$  [ 1//1; 0//1; 0//1]
  | 2  $\rightarrow$  [ 0//1; 1//1; 0//1]
  | 3  $\rightarrow$  [ 0//1; 0//1; 1//1]
  | -1  $\rightarrow$  [-1//1; 0//1; 0//1]
  | -2  $\rightarrow$  [ 0//1; -1//1; 0//1]
  | -3  $\rightarrow$  [ 0//1; 0//1; -1//1]
  |  $n \rightarrow$  invalid_arg ("SM-QCD.generation': $\square$ " ^ string_of_int  $n$ )

let generation f =
  match  $f$  with
  |  $M (L n$  |  $N n$  |  $U n$  |  $D n) \rightarrow$  generation'  $n$ 
  |  $G _$  |  $O _ \rightarrow$  [0//1; 0//1; 0//1]

let charge = function
  |  $M f \rightarrow$ 
    begin match  $f$  with
    |  $L n \rightarrow$  if  $n > 0$  then -1//1 else 1//1
    |  $N n \rightarrow$  0//1
    |  $U n \rightarrow$  if  $n > 0$  then 2//3 else -2//3
    |  $D n \rightarrow$  if  $n > 0$  then -1//3 else 1//3
    end
  |  $G f \rightarrow$ 
    begin match  $f$  with
    |  $Gl$  |  $Ga$  |  $GaX$  |  $Z \rightarrow$  0//1
    |  $Wp \rightarrow$  1//1
    |  $Wm \rightarrow$  -1//1

```

```

    end
  |  $O f \rightarrow$ 
    begin match  $f$  with
    |  $H \rightarrow 0//1$ 
    end

let lepton = function
  |  $M f \rightarrow$ 
    begin match  $f$  with
    |  $L n$  |  $N n \rightarrow$  if  $n > 0$  then  $1//1$  else  $-1//1$ 
    |  $U -$  |  $D - \rightarrow 0//1$ 
    end
  |  $G -$  |  $O - \rightarrow 0//1$ 

let baryon = function
  |  $M f \rightarrow$ 
    begin match  $f$  with
    |  $L -$  |  $N - \rightarrow 0//1$ 
    |  $U n$  |  $D n \rightarrow$  if  $n > 0$  then  $1//1$  else  $-1//1$ 
    end
  |  $G -$  |  $O - \rightarrow 0//1$ 

let charges  $f =$ 
  [ charge  $f$ ; lepton  $f$ ; baryon  $f$ ] @ generation  $f$ 

type constant =
  | Unit | Half | Pi | Alpha_QED | Sin2thw
  | Sinthw | Costhw | E | G_weak | I-G_weak | Vev
  | Q_lepton | Q-up | Q-down | G_CC | G_CCQ of int × int
  | G_NC_neutrino | G_NC_lepton | G_NC-up | G_NC-down
  | I-Q-W | G-Htt | G-Hbb | G-Hcc | G-Hmm | G-Htautau
  | Gs | I-Gs | G2
  | Mass of flavor | Width of flavor

type orders = unit
let orders = function
  |  $- \rightarrow ()$ 

```



The current abstract syntax for parameter dependencies is admittedly tedious. Later, there will be a parser for a convenient concrete syntax as a part of a concrete syntax for models. But as these examples show, it should include simple functions.

$$\alpha_{\text{QED}} = \frac{1}{137.0359895} \quad (13.21a)$$

$$\sin^2 \theta_w = 0.23124 \quad (13.21b)$$

```

let input_parameters =
  [ Alpha_QED, 1. /. 137.0359895;
    Sin2thw, 0.23124;

```

```

    Mass (G Z), 91.187;
    Mass (M (N 1)), 0.0; Mass (M (L 1)), 0.51099907 · 10-3;
    Mass (M (N 2)), 0.0; Mass (M (L 2)), 0.105658389;
    Mass (M (N 3)), 0.0; Mass (M (L 3)), 1.77705;
    Mass (M (U 1)), 5.0 · 10-3; Mass (M (D 1)), 3.0 · 10-3;
    Mass (M (U 2)), 1.2; Mass (M (D 2)), 0.1;
    Mass (M (U 3)), 174.0; Mass (M (D 3)), 4.2 ]

let derived_parameters =
[ Real E, Sqrt (Prod [Const 4; Atom Pi; Atom Alpha-QED]);
  Real Sinthw, Sqrt (Atom Sin2thw);
  Real Costhw, Sqrt (Diff (Const 1, Atom Sin2thw));
  Real G_weak, Quot (Atom E, Atom Sinthw);
  Real (Mass (G Wp)), Prod [Atom Costhw; Atom (Mass (G Z))];
  Real Vev, Quot (Prod [Const 2; Atom (Mass (G Wp))], Atom G_weak);
  Real Q_lepton, Atom E;
  Real Q_up, Prod [Quot (Const (-2), Const 3); Atom E];
  Real Q_down, Prod [Quot (Const 1, Const 3); Atom E];
  Real G_CC, Neg (Quot (Atom G_weak, Prod [Const 2; Sqrt (Const 2)]));
  Complex I_Q_W, Prod [I; Atom E]]

let g_over_2_costh =
  Quot (Neg (Atom G_weak), Prod [Const 2; Atom Costhw])

let nc_coupling c t3 q =
  (Real_Array c,
   [Prod [g_over_2_costh; Diff (t3, Prod [Const 2; q; Atom Sin2thw]);
     Prod [g_over_2_costh; t3]])

let half = Quot (Const 1, Const 2)

let derived_parameter_arrays =
[ nc_coupling G_NC_neutrino half (Const 0);
  nc_coupling G_NC_lepton (Neg half) (Const (-1));
  nc_coupling G_NC_up half (Quot (Const 2, Const 3));
  nc_coupling G_NC_down (Neg half) (Quot (Const (-1), Const 3)) ]

let parameters () =
{ input = input_parameters;
  derived = derived_parameters;
  derived_arrays = derived_parameter_arrays }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let mgm ((m1, g, m2), fbf, c) = ((M m1, G g, M m2), fbf, c)
let mom ((m1, o, m2), fbf, c) = ((M m1, O o, M m2), fbf, c)

let electromagnetic_currents n =
  List.map mgm
    [ ((L (-n), GaX, L n), FBF (1, Psibar, V, Psi), Q_lepton);

```

```

((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q-up);
((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q-down) ]

let color_currents n =
  List.map mgm
    [ ((U (-n), Gl, U n), FBF ((-1), Psibar, V, Psi), Gs);
      ((D (-n), Gl, D n), FBF ((-1), Psibar, V, Psi), Gs) ]


$$\mathcal{L}_{\text{NC}} = -\frac{g}{2\cos\theta_W} \sum_i \bar{\psi}_i \not{Z} (g_V^i - g_A^i \gamma_5) \psi_i \quad (13.22)$$


let neutral_currents n =
  List.map mgm
    [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
      ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
      ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
      ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]


$$\mathcal{L}_{\text{CC}} = -\frac{g}{2\sqrt{2}} \sum_i \bar{\psi}_i (T^+ W^+ + T^- W^-) (1 - \gamma_5) \psi_i \quad (13.23)$$


let charged_currents' n =
  List.map mgm
    [ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G_CC);
      ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G_CC) ]

let charged_currents'' n =
  List.map mgm
    [ ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_CC);
      ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G_CC) ]

let charged_currents_triv =
  ThoList.flatmap charged_currents' [1; 2; 3] @
  ThoList.flatmap charged_currents'' [1; 2; 3]

let charged_currents_ckm =
  let charged_currents_2 n1 n2 =
    List.map mgm
      [ ((D (-n1), Wm, U n2), FBF (1, Psibar, VL, Psi), G_CCQ (n2, n1));
        ((U (-n1), Wp, D n2), FBF (1, Psibar, VL, Psi), G_CCQ (n1, n2)) ] in
    ThoList.flatmap charged_currents' [1; 2; 3] @
    List.flatten (Product.list2 charged_currents_2 [1; 2; 3] [1; 2; 3])

let yukawa =
  [ ((M (U (-3)), O H, M (U 3)), FBF (1, Psibar, S, Psi), G_Htt);
    ((M (D (-3)), O H, M (D 3)), FBF (1, Psibar, S, Psi), G_Hbb);
    ((M (U (-2)), O H, M (U 2)), FBF (1, Psibar, S, Psi), G_Hcc);
    ((M (L (-2)), O H, M (L 2)), FBF (1, Psibar, S, Psi), G_Hmm);
    ((M (L (-3)), O H, M (L 3)), FBF (1, Psibar, S, Psi), G_Htautau) ]


$$\mathcal{L}_{\text{TGC}} = -e\partial_\mu A_\nu W_+^\mu W_-^\nu + \dots - e\cot\theta_w \partial_\mu Z_\nu W_+^\mu W_-^\nu + \dots \quad (13.24)$$


```



```

let tgc ((g1, g2, g3), t, c) = ((G g1, G g2, G g3), t, c)

let triple_gauge =
  List.map tgc
    [ ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_Gs)]

let qgc ((g1, g2, g3, g4), t, c) = ((G g1, G g2, G g3, G g4), t, c)

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let quartic_gauge =
  List.map qgc
    [ (Gl, Gl, Gl, Gl), gauge4, G2 ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1; 2; 3] @
   ThoList.flatmap color_currents [1; 2; 3] @
   ThoList.flatmap neutral_currents [1; 2; 3] @
   charged_currents_triv @
   yukawa @ triple_gauge)

let vertices4 =
  quartic_gauge

let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))
| "numu" → M (N 2) | "numubar" → M (N (-2))
| "nutau" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "g" | "gl" → G Gl
| "A" → G Ga | "Z" | "ZO" → G Z
| "W+" → G Wp | "W-" → G Wm
| "H" → O H
| _ → invalid_arg "Modellib.SM.QCD.flavor_of_string"

let flavor_to_string = function
| M f →

```

```

begin match f with
| L 1 → "e-" | L (-1) → "e+"
| L 2 → "mu-" | L (-2) → "mu+"
| L 3 → "tau-" | L (-3) → "tau+"
| L _ → invalid_arg
      "Modellib.SM_QCD.flavor_to_string:␣invalid␣lepton"
| N 1 → "nue" | N (-1) → "nuebar"
| N 2 → "numu" | N (-2) → "numubar"
| N 3 → "nutau" | N (-3) → "nutaubar"
| N _ → invalid_arg
      "Modellib.SM_QCD.flavor_to_string:␣invalid␣neutrino"
| U 1 → "u" | U (-1) → "ubar"
| U 2 → "c" | U (-2) → "cbar"
| U 3 → "t" | U (-3) → "tbar"
| U _ → invalid_arg
      "Modellib.SM_QCD.flavor_to_string:␣invalid␣up␣type␣quark"
| D 1 → "d" | D (-1) → "dbar"
| D 2 → "s" | D (-2) → "sbar"
| D 3 → "b" | D (-3) → "bbar"
| D _ → invalid_arg
      "Modellib.SM_QCD.flavor_to_string:␣invalid␣down␣type␣quark"
end
| G f →
  begin match f with
  | Gl → "gl"
  | Ga | GaX → "A" | Z → "Z"
  | Wp → "W+" | Wm → "W-"
  end
| O f →
  begin match f with
  | H → "H"
  end
end

let flavor_to_TeX = function
| M f →
  begin match f with
  | L 1 → "e~-" | L (-1) → "e~+"
  | L 2 → "\\mu~-" | L (-2) → "\\mu~+"
  | L 3 → "\\tau~-" | L (-3) → "\\tau~+"
  | L _ → invalid_arg
        "Modellib.SM_QCD.flavor_to_TeX:␣invalid␣lepton"
  | N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
  | N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
  | N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
  | N _ → invalid_arg
        "Modellib.SM_QCD.flavor_to_TeX:␣invalid␣neutrino"
  | U 1 → "u" | U (-1) → "\\bar{u}"
  | U 2 → "c" | U (-2) → "\\bar{c}"
  | U 3 → "t" | U (-3) → "\\bar{t}"
  | U _ → invalid_arg

```

```

        "Modellib.SM-QCD.flavor_to_TeX:␣invalid␣up␣type␣quark"
    |  $D\ 1 \rightarrow "d"$  |  $D\ (-1) \rightarrow "\\bar{d}"$ 
    |  $D\ 2 \rightarrow "s"$  |  $D\ (-2) \rightarrow "\\bar{s}"$ 
    |  $D\ 3 \rightarrow "b"$  |  $D\ (-3) \rightarrow "\\bar{b}"$ 
    |  $D\ - \rightarrow invalid\_arg$ 
        "Modellib.SM-QCD.flavor_to_TeX:␣invalid␣down␣type␣quark"
    end
|  $G\ f \rightarrow$ 
    begin match  $f$  with
    |  $G_l \rightarrow "g"$ 
    |  $G_a$  |  $G_a X \rightarrow "\\gamma"$  |  $Z \rightarrow "Z"$ 
    |  $W_p \rightarrow "W^+"$  |  $W_m \rightarrow "W^-"$ 
    end
|  $O\ f \rightarrow$ 
    begin match  $f$  with
    |  $H \rightarrow "H"$ 
    end
let flavor_symbol = function
|  $M\ f \rightarrow$ 
    begin match  $f$  with
    |  $L\ n$  when  $n > 0 \rightarrow "l" ^ {string\_of\_int\ n}$ 
    |  $L\ n \rightarrow "l" ^ {string\_of\_int\ (abs\ n)} ^ {"b"}$ 
    |  $N\ n$  when  $n > 0 \rightarrow "n" ^ {string\_of\_int\ n}$ 
    |  $N\ n \rightarrow "n" ^ {string\_of\_int\ (abs\ n)} ^ {"b"}$ 
    |  $U\ n$  when  $n > 0 \rightarrow "u" ^ {string\_of\_int\ n}$ 
    |  $U\ n \rightarrow "u" ^ {string\_of\_int\ (abs\ n)} ^ {"b"}$ 
    |  $D\ n$  when  $n > 0 \rightarrow "d" ^ {string\_of\_int\ n}$ 
    |  $D\ n \rightarrow "d" ^ {string\_of\_int\ (abs\ n)} ^ {"b"}$ 
    end
|  $G\ f \rightarrow$ 
    begin match  $f$  with
    |  $G_l \rightarrow "gl"$ 
    |  $G_a \rightarrow "a"$  |  $Z \rightarrow "z"$ 
    |  $G_a X \rightarrow "gax"$ 
    |  $W_p \rightarrow "wp"$  |  $W_m \rightarrow "wm"$ 
    end
|  $O\ f \rightarrow$ 
    begin match  $f$  with
    |  $H \rightarrow "h"$ 
    end
let pdg = function
|  $M\ f \rightarrow$ 
    begin match  $f$  with
    |  $L\ n$  when  $n > 0 \rightarrow 9 + 2 \times n$ 
    |  $L\ n \rightarrow -9 + 2 \times n$ 
    |  $N\ n$  when  $n > 0 \rightarrow 10 + 2 \times n$ 
    |  $N\ n \rightarrow -10 + 2 \times n$ 
    |  $U\ n$  when  $n > 0 \rightarrow 2 \times n$ 
    |  $U\ n \rightarrow 2 \times n$ 

```

```

      |  $D\ n$  when  $n > 0 \rightarrow -1 + 2 \times n$ 
      |  $D\ n \rightarrow 1 + 2 \times n$ 
    end
  |  $G\ f \rightarrow$ 
    begin match  $f$  with
    |  $Gl \rightarrow 21$ 
    |  $Ga \mid GaX \rightarrow 22 \mid Z \rightarrow 23$ 
    |  $Wp \rightarrow 24 \mid Wm \rightarrow (-24)$ 
    end
  |  $O\ f \rightarrow$ 
    begin match  $f$  with
    |  $H \rightarrow 25$ 
    end

let mass_symbol  $f =$ 
  "mass(" ^ string_of_int (abs (pdg  $f$ )) ^ ")"

let width_symbol  $f =$ 
  "width(" ^ string_of_int (abs (pdg  $f$ )) ^ ")"

let constant_symbol = function
| Unit  $\rightarrow$  "unit" | Half  $\rightarrow$  "half" | Pi  $\rightarrow$  "PI"
| Alpha_QED  $\rightarrow$  "alpha" | E  $\rightarrow$  "e" | G_weak  $\rightarrow$  "g" | Vev  $\rightarrow$ 
"vev"
| I_G_weak  $\rightarrow$  "ig"
| Sin2thw  $\rightarrow$  "sin2thw" | Sinthw  $\rightarrow$  "sinthw" | Costhw  $\rightarrow$ 
"costhw"
| Q_lepton  $\rightarrow$  "qlp" | Q_up  $\rightarrow$  "qup" | Q_down  $\rightarrow$  "qdown"
| G_NC_lepton  $\rightarrow$  "gnclep" | G_NC_neutrino  $\rightarrow$  "gncneu"
| G_NC_up  $\rightarrow$  "gncup" | G_NC_down  $\rightarrow$  "gncdown"
| G_CC  $\rightarrow$  "gcc"
| G_CCQ ( $n1, n2$ )  $\rightarrow$  "gccq" ^ string_of_int  $n1$  ^ string_of_int  $n2$ 
| I_Q_W  $\rightarrow$  "iqw"
| G_Htt  $\rightarrow$  "ghtt" | G_Hbb  $\rightarrow$  "ghbb"
| G_Htautau  $\rightarrow$  "ghtautau" | G_Hcc  $\rightarrow$  "ghcc" | G_Hmm  $\rightarrow$ 
"ghmm"
| Gs  $\rightarrow$  "gs" | I_Gs  $\rightarrow$  "igs" | G2  $\rightarrow$  "gs**2"
| Mass  $f \rightarrow$  "mass" ^ flavor_symbol  $f$ 
| Width  $f \rightarrow$  "width" ^ flavor_symbol  $f$ 

end

```

13.4.9 Groves

```

module Groves ( $M : Model.Gauge$ ) : Model.Gauge with module Ch = M.Ch =
struct
  let max_generations = 5
  let rcs = RCS.rename M.rcs
  ("Modellib.Groves(" ^ (RCS.name M.rcs) ^ ")")
  ([ "experimental_Groves_functor";

```

```

    Printf.sprintf "for_maximally_%d_flavored_legs"
      (2 × max_generations) ] @
    RCS.description M.rcs)

let options = M.options

type matter_field = M.matter_field × int
type gauge_boson = M.gauge_boson
type other = M.other
type field =
  | Matter of matter_field
  | Gauge of gauge_boson
  | Other of other
type flavor = M of matter_field | G of gauge_boson | O of other
let matter_field (f, g) = M (f, g)
let gauge_boson f = G f
let other f = O f
let field = function
  | M f → Matter f
  | G f → Gauge f
  | O f → Other f
let project = function
  | M (f, _) → M.matter_field f
  | G f → M.gauge_boson f
  | O f → M.other f
let inject g f =
  match M.field f with
  | M.Matter f → M (f, g)
  | M.Gauge f → G f
  | M.Other f → O f
type gauge = M.gauge
let gauge_symbol = M.gauge_symbol
let color f = M.color (project f)
let pdg f = M.pdg (project f)
let lorentz f = M.lorentz (project f)
let propagator f = M.propagator (project f)
let fermion f = M.fermion (project f)
let width f = M.width (project f)
let mass_symbol f = M.mass_symbol (project f)
let width_symbol f = M.width_symbol (project f)
let flavor_symbol f = M.flavor_symbol (project f)

type constant = M.constant
type orders = M.orders
let constant_symbol = M.constant_symbol
let max_degree = M.max_degree
let parameters = M.parameters
let orders = M.orders

let conjugate = function
  | M (_, g) as f → inject g (M.conjugate (project f))
  | f → inject 0 (M.conjugate (project f))

```

```

let read_generation s =
  try
    let offset = String.index s '/' in
      (int_of_string
        (String.sub s (succ offset) (String.length s - offset - 1)),
        String.sub s 0 offset)
  with
  | Not_found → (1, s)

let format_generation c s =
  s ^ "/" ^ string_of_int c

let flavor_of_string s =
  let g, s = read_generation s in
    inject g (M.flavor_of_string s)

let flavor_to_string = function
| M (_, g) as f → format_generation g (M.flavor_to_string (project f))
| f → M.flavor_to_string (project f)

let flavor_to_TeX = function
| M (_, g) as f → format_generation g (M.flavor_to_TeX (project f))
| f → M.flavor_to_TeX (project f)

let goldstone = function
| G _ as f →
  begin match M.goldstone (project f) with
  | None → None
  | Some (f, c) → Some (inject 0 f, c)
  end
| M _ | O _ → None

let clone_generations flavor =
  match M.field flavor with
  | M.Matter f → List.map (fun g → M (f, g)) generations
  | M.Gauge f → [G f]
  | M.Other f → [O f]

let generations = ThoList.range 1 max_generations

let flavors () =
  ThoList.flatmap (clone_generations) (M.flavors ())

let external_flavors () =
  List.map (fun (s, fl) → (s, ThoList.flatmap (clone_generations) fl))
    (M.external_flavors ())

module Ch = M.Ch
let charges f = M.charges (project f)

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

```

In the following functions, we might replace `_` by `(M.Gauge _ | M.Other _)`, in order to allow the compiler to check completeness. However, this makes the code much less readable.

```

let clone3 ((f1, f2, f3), v, c) =
  match M.field f1, M.field f2, M.field f3 with
  | M.Matter _, M.Matter _, M.Matter _ →
    invalid_arg "Modellib.Groves().vertices:_three_matter_fields!"
  | M.Matter f1', M.Matter f2', _ →
    List.map (fun g → ((M (f1', g), M (f2', g), inject 0 f3), v, c))
      generations
  | M.Matter f1', _, M.Matter f3' →
    List.map (fun g → ((M (f1', g), inject 0 f2, M (f3', g)), v, c))
      generations
  | _, M.Matter f2', M.Matter f3' →
    List.map (fun g → ((inject 0 f1, M (f2', g), M (f3', g)), v, c))
      generations
  | M.Matter _, _, _ | _, M.Matter _, _ | _, _, M.Matter _ →
    invalid_arg "Modellib.Groves().vertices:_lone_matter_field!"
  | _, _, _ →
    [(inject 0 f1, inject 0 f2, inject 0 f3), v, c]

let clone4 ((f1, f2, f3, f4), v, c) =
  match M.field f1, M.field f2, M.field f3, M.field f4 with
  | M.Matter _, M.Matter _, M.Matter _, M.Matter _ →
    invalid_arg "Modellib.Groves().vertices:_four_matter_fields!"
  | M.Matter _, M.Matter _, M.Matter _, _
  | M.Matter _, M.Matter _, _, M.Matter _
  | M.Matter _, _, M.Matter _, M.Matter _
  | _, M.Matter _, M.Matter _, M.Matter _ →
    invalid_arg "Modellib.Groves().vertices:_three_matter_fields!"
  | M.Matter f1', M.Matter f2', _, _ →
    List.map (fun g →
      ((M (f1', g), M (f2', g), inject 0 f3, inject 0 f4), v, c))
      generations
  | M.Matter f1', _, M.Matter f3', _ →
    List.map (fun g →
      ((M (f1', g), inject 0 f2, M (f3', g), inject 0 f4), v, c))
      generations
  | M.Matter f1', _, _, M.Matter f4' →
    List.map (fun g →
      ((M (f1', g), inject 0 f2, inject 0 f3, M (f4', g)), v, c))
      generations
  | _, M.Matter f2', M.Matter f3', _ →
    List.map (fun g →
      ((inject 0 f1, M (f2', g), M (f3', g), inject 0 f4), v, c))
      generations
  | _, M.Matter f2', _, M.Matter f4' →
    List.map (fun g →
      ((inject 0 f1, M (f2', g), inject 0 f3, M (f4', g)), v, c))
      generations

```

```

| -, -, M.Matter f3', M.Matter f4' →
  List.map (fun g →
    ((inject 0 f1, inject 0 f2, M (f3', g), M (f4', g)), v, c))
    generations
| M.Matter -, -, -, - | -, M.Matter -, -, -
| -, -, M.Matter -, - | -, -, -, M.Matter - →
  invalid_arg "Modellib.Groves().vertices:_lone_matter_field!"
| -, -, -, - →
  [(inject 0 f1, inject 0 f2, inject 0 f3, inject 0 f4), v, c]

let clonen (fl, v, c) =
  match List.map M.field fl with
  | - → failwith "Modellib.Groves().vertices:_incomplete"

let vertices () =
  let vertices3, vertices4, verticesn = M.vertices () in
  (ThoList.flatmap clone3 vertices3,
   ThoList.flatmap clone4 vertices4,
   ThoList.flatmap clonen verticesn)

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table

```



The following (incomplete) alternative implementations are included for illustrative purposes only:

```

let injectl g fcl =
  List.map (fun (f, c) → (inject g f, c)) fcl

let alt_fuse2 f1 f2 =
  match f1, f2 with
  | M (f1', g1'), M (f2', g2') →
    if g1' = g2' then
      injectl 0 (M.fuse2 (M.matter_field f1') (M.matter_field f2'))
    else
      []
  | M (f1', g'), - → injectl g' (M.fuse2 (M.matter_field f1') (project f2))
  | -, M (f2', g') → injectl g' (M.fuse2 (project f1) (M.matter_field f2'))
  | -, - → injectl 0 (M.fuse2 (project f1) (project f2))

let alt_fuse3 f1 f2 f3 =
  match f1, f2, f3 with
  | M (f1', g1'), M (f2', g2'), M (f3', g3') →
    invalid_arg "Modellib.Groves().fuse3:_three_matter_fields!"
  | M (f1', g1'), M (f2', g2'), - →
    if g1' = g2' then
      injectl 0
        (M.fuse3 (M.matter_field f1') (M.matter_field f2') (project f3))
    else

```



```

| []
| M (f1', g1'), -, M (f3', g3') →
  if g1' = g3' then
    injectl 0
    (M.fuse3 (M.matter_field f1') (project f2) (M.matter_field f3'))
  else
    []
| -, M (f2', g2'), M (f3', g3') →
  if g2' = g3' then
    injectl 0
    (M.fuse3 (project f1) (M.matter_field f2') (M.matter_field f3'))
  else
    []
| M (f1', g'), -, - →
  injectl g' (M.fuse3 (M.matter_field f1') (project f2) (project f3))
| -, M (f2', g'), - →
  injectl g' (M.fuse3 (project f1) (M.matter_field f2') (project f3))
| -, -, M (f3', g') →
  injectl g' (M.fuse3 (project f1) (project f2) (M.matter_field f3'))
| -, -, - → injectl 0 (M.fuse3 (project f1) (project f2) (project f3))
end

```

13.4.10 MSM With Cloned Families

```
module SM_clones = Groves(SM(SM_no_anomalous))
```

13.5 Interface of *Modellib_BSM*

13.5.1 More Hardcoded BSM Models

```

module type BSM_flags =
  sig
    val u1_gauged : bool
    val anom_ferm_ass : bool
  end

module type THDM_flags =
  sig
    val ckm_present : bool
  end

module BSM_bsm : BSM_flags
module BSM_ungauged : BSM_flags
module BSM_anom : BSM_flags
module Littlest : functor (F : BSM_flags) → Model.Gauge with mod-
  ule Ch = Charges.QQ
module Littlest_Tpar : functor (F : BSM_flags) → Model.T with mod-
  ule Ch = Charges.QQ

```

```

module Simplest : functor (F : BSM_flags) → Model.T with module Ch = Charges.QQ
module Xdim : functor (F : BSM_flags) → Model.Gauge with module Ch = Charges.QQ
module UED : functor (F : BSM_flags) → Model.Gauge with module Ch = Charges.QQ
module GravTest : functor (F : BSM_flags) → Model.Gauge with module Ch = Charges.QQ
module THDM : THDM_flags
module THDM_CKM : THDM_flags
module TwoHiggsDoublet : functor (F : THDM_flags) → Model.Gauge with module Ch = Charges.QQ
module Template : functor (F : BSM_flags) → Model.Gauge with module Ch = Charges.QQ

module type Threeshl_options =
  sig
    val include_ckm : bool
    val include_hf : bool
    val diet : bool
  end

module Threeshl_no_ckm : Threeshl_options
module Threeshl_ckm : Threeshl_options
module Threeshl_no_ckm_no_hf : Threeshl_options
module Threeshl_ckm_no_hf : Threeshl_options
module Threeshl_diet_no_hf : Threeshl_options
module Threeshl_diet : Threeshl_options
module Threeshl : functor (Module_options : Threeshl_options) →
  Model.T with module Ch = Charges.QQ

module type VBS_flags =
  sig
    val higgs_triangle : bool (*  $H\gamma\gamma$ ,  $Hg\gamma$  and  $Hgg$  couplings *)
    val higgs_hmm : bool
    val triple_anom : bool
    val quartic_anom : bool
    val higgs_anom : bool
    val k_matrix : bool
    val ckm_present : bool
    val top_anom : bool
    val top_anom_4f : bool
  end

module VBS_kmatrix : VBS_flags

module VBS : functor (F : VBS_flags) → Model.Gauge with module Ch = Charges.QQ

```

13.6 Implementation of *Modellib_BSM*

```

let rcs_file = RCS.parse "Modellib_BSM" ["BSM_Models"]
{ RCS.revision = "$Revision: 4666$";

```

```

RCS.date = "$Date: 2013-09-23 17:29:20 +0200 (Mon, 23 Sep 2013) $";
RCS.author = "$Author: ohl $";
RCS.source
  = "$URL: svn+ssh://jr_reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg

```

13.6.1 Littlest Higgs Model

```

module type BSM_flags =
  sig
    val u1_gauged : bool
    val anom_ferm_ass : bool
  end

module BSM_bsm : BSM_flags =
  struct
    let u1_gauged = true
    let anom_ferm_ass = false
  end

module BSM_ungauged : BSM_flags =
  struct
    let u1_gauged = false
    let anom_ferm_ass = false
  end

module BSM_anom : BSM_flags =
  struct
    let u1_gauged = false
    let anom_ferm_ass = true
  end

module Littlest (Flags : BSM_flags) =
  struct
    let rcs = rcs_file

    open Coupling

    let default_width = ref Timelike
    let use_fudged_width = ref false

    let options = Options.create
      [ "constant_width", Arg.Unit (fun () → default_width := Constant),
        "use_constant_width (also in t-channel)";
        "fudged_width", Arg.Set use_fudged_width,
        "use_fudge_factor_for_charge_particle_width";
        "custom_width", Arg.String (fun f → default_width := Custom f),
        "use_custom_width";
        "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
        "use_vanishing_width" ]

    let gauge_symbol () =
      failwith "Modellib_BSM.Littlest.gauge_symbol: internal error"

```

```

type matter_field = L of int | N of int | U of int | D of int
                  | TopH | TopHb
type gauge_boson = Ga | Wp | Wm | Z | Gl | WHp | WHm
                  | ZH | AH
type other = Phip | Phim | Phi0 | H | Eta | Psi0
            | Psi1 | Psip | Psim | Psipp | Psimm
type flavor = M of matter_field | G of gauge_boson | O of other

let matter_field f = M f
let gauge_boson f = G f
let other f = O f

type field =
  | Matter of matter_field
  | Gauge of gauge_boson
  | Other of other

let field = function
  | M f → Matter f
  | G f → Gauge f
  | O f → Other f

type gauge = unit

let gauge_symbol () =
  failwith "Modellib_BSM.Littlest.gauge_symbol: internal error"

let family n = List.map matter_field [ L n; N n; U n; D n ]

```

Since *Phi* already belongs to the EW Goldstone bosons we use *Psi* for the TeV scale complex triplet.

```

let external_flavors () =
  [ "1st_Generation", ThoList.flatmap family [1; -1];
    "2nd_Generation", ThoList.flatmap family [2; -2];
    "3rd_Generation", ThoList.flatmap family [3; -3];
    "Heavy_Quarks", List.map matter_field [TopH; TopHb];
    "HeavyScalars", List.map other
      [Psi0; Psi1; Psip; Psim; Psipp; Psimm];
    "Gauge_Bosons", List.map gauge_boson
      (if Flags.u1_gauged then
        [Ga; Z; Wp; Wm; Gl; WHp; WHm; ZH; AH]
      else
        [Ga; Z; Wp; Wm; Gl; WHp; WHm; ZH]);
    "Higgs", List.map other
      (if Flags.u1_gauged then [H]
      else [H; Eta]);
    "Goldstone_Bosons", List.map other [Phip; Phim; Phi0] ]

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n =
  if n ≥ 0 then
    Spinor
  else

```

```

    ConjSpinor
let lorentz = function
| M f →
    begin match f with
    | L n → spinor n | N n → spinor n
    | U n → spinor n | D n → spinor n
    | TopH → Spinor | TopHb → ConjSpinor
    end
| G f →
    begin match f with
    | Ga | Gl → Vector
    | Wp | Wm | Z | WHp | WHm | ZH | AH →
Massive_Vector
    end
| O f →
    begin match f with
    | Phip | Phim | Phi0 | H | Eta | Psi0
    | Psi1 | Psip | Psim | Psipp | Psimm → Scalar
    end

let color = function
| M (U n) → Color.SUN (if n > 0 then 3 else -3)
| M (D n) → Color.SUN (if n > 0 then 3 else -3)
| M TopH → Color.SUN 3 | M TopHb → Color.SUN (-3)
| G Gl → Color.AdjSUN 3
| _ → Color.Singlet

let prop_spinor n =
if n ≥ 0 then
    Prop_Spinor
else
    Prop_ConjSpinor

let propagator = function
| M f →
    begin match f with
    | L n → prop_spinor n | N n → prop_spinor n
    | U n → prop_spinor n | D n → prop_spinor n
    | TopH → Prop_Spinor | TopHb → Prop_ConjSpinor
    end
| G f →
    begin match f with
    | Ga | Gl → Prop_Feynman
    | Wp | Wm | Z | WHp | WHm | ZH | AH →
Prop_Unitality
    end
| O f →
    begin match f with
    | Phip | Phim | Phi0 → Only_Insertion
    | H | Eta | Psi0 | Psi1 | Psip | Psim
    | Psipp | Psimm → Prop_Scalar

```

end

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    | G Wp | G Wm | M (U 3) | M (U (-3))
    | G WHp | G WHm | G ZH | G AH
    | M TopH | M TopHb → Fudged
    | _ → !default_width
  else
    !default_width
let goldstone = function
| G f →
  begin match f with
  | Wp → Some (O Phip, Coupling.Const 1)
  | Wm → Some (O Phim, Coupling.Const 1)
  | Z → Some (O Phi0, Coupling.Const 1)
  | _ → None
  end
| _ → None
let conjugate = function
| M f →
  M (begin match f with
  | L n → L (-n) | N n → N (-n)
  | U n → U (-n) | D n → D (-n)
  | TopH → TopHb | TopHb → TopH
  end)
| G f →
  G (begin match f with
  | Gl → Gl | Ga → Ga | Z → Z
  | Wp → Wm | Wm → Wp | WHm → WHp
  | WHp → WHm | ZH → ZH | AH → AH
  end)
| O f →
  O (begin match f with
  | Psi0 → Psi0 | Psi1 → Psi1 | Psip → Psim
  | Psim → Psip | Psipp → Psimm | Psimm → Psipp
  | Phip → Phim | Phim → Phip | Phi0 → Phi0
  | H → H | Eta → Eta
  end)
let fermion = function
| M f →
  begin match f with
  | L n → if n > 0 then 1 else -1
  | N n → if n > 0 then 1 else -1
  | U n → if n > 0 then 1 else -1
  | D n → if n > 0 then 1 else -1

```

```

    | TopH → 1 | TopHb → -1
  end
| G f →
  begin match f with
  | Gl | Ga | Z | Wp | Wm | WHp
  | WHm | AH | ZH → 0
  end
| O f →
  begin match f with
  | Psi0 | Psi1 | Psip | Psim | Psipp | Psimm
  | Phip | Phim | Phi0 | H | Eta → 0
  end
end

```

This model does NOT have a conserved generation charge even in absence of CKM mixing because of the heavy top admixture.

```

module Ch = Charges.QQ
let ( // ) = Algebra.Small_Rational.make

let charge = function
| M f →
  begin match f with
  | L n → if n > 0 then -1//1 else 1//1
  | N n → 0//1
  | U n → if n > 0 then 2//3 else -2//3
  | D n → if n > 0 then -1//3 else 1//3
  | TopH → 2//3
  | TopHb → -2//3
  end
| G f →
  begin match f with
  | Gl | Ga | Z | AH | ZH → 0//1
  | Wp | WHp → 1//1
  | Wm | WHm → -1//1
  end
| O f →
  begin match f with
  | H | Phi0 | Eta | Psi1 | Psi0 → 0//1
  | Phip | Psip → 1//1
  | Phim | Psim → -1//1
  | Psipp → 2//1
  | Psimm → -2//1
  end
end

let lepton = function
| M f →
  begin match f with
  | L n | N n → if n > 0 then 1//1 else -1//1
  | U - | D - | - → 0//1
  end
| G - | O - → 0//1
end

```

```

let baryon = function
| M f →
  begin match f with
  | L _ | N _ → 0//1
  | U n | D n → if n > 0 then 1//1 else -1//1
  | TopH → 1//1
  | TopHb → -1//1
  end
| G _ | O _ → 0//1

let charges f =
[ charge f; lepton f; baryon f]

type constant =
| Unit | Pi | Alpha_QED | Sin2thw
| Sinhw | Costhw | E | G_weak | Vev | VHeavy
| Supp | Supp2
| Sinpsi | Cospsi | Atpsi | ScCs (* Mixing angles of SU(2) *)
| Q_lepton | Q_up | Q_down | Q_Z_up | G_CC | G_CCtop
| G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down |
G_NC_heavy
| G_NC_h_neutrino | G_NC_h_lepton | G_NC_h_up | G_NC_h_down
| G_CC_heavy | G_ZHTHT | G_ZTHT | G_AHTHTH |
G_AHTHT | G_AHTT
| G_CC_WH | G_CC_W
| I_Q_W | I_G_ZWW | I_G_WWW
| I_G_AHWW | I_G_ZHWW | I_G_ZWHW | I_G_AHWHWH |
I_G_ZHWHWH
| I_G_AHWHWH | I_Q_H
| G_WWWW | G_ZZWW | G_AZWW | G_AAWW
| G_WH4 | G_WHWHWW | G_WHWWW | G_WH3W
| G_WWAAH | G_WWAZH | G_WWZZH | G_WWZAH |
G_WWHWAAH
| G_WWHWAZH | G_WWHWZZH | G_WWHWZAH | G_WWZHAH
| G_WWHWZHAH | G_WHWZZ | G_WHWAZ | G_WHWAAH |
G_WHWZAH
| G_WHWZHZH | G_WHWZH AH | G_WHWAZH | G_WHWZZH
| G_HWW | G_HHWW | G_HZZ | G_HHZZ
| G_PsiWW | G_PsiWHW | G_PsiZZ | G_PsiZHZH
| G_PsiZHZ | G_PsiZAH | G_PsiZH AH | G_PsiAH AH
| G_PsiZW | G_PsiZWH | G_PsiAHW | G_PsiAHWH
| G_PsiZHW | G_PsiZHWH
| G_PsippWW | G_PsippWHW | G_PsippWHWH
| G_PsiHW | G_PsiHWH | G_Psi0W | G_Psi0WH
| G_Psi1W | G_Psi1WH | G_PsiPPW | G_PsiPPWH
| G_Psi1HAH | G_Psi01AH | G_AHPsip | G_Psi1HZ
| G_Psi1HZH | G_Psi01Z | G_Psi01ZH | G_ZPsip | G_ZPsipp |
G_ZHPsipp
| G_HHAA | G_HHWW | G_HHZHZ | G_HHAHZ | G_HHZHAH
| G_HPsi0WW | G_HPsi0WHW | G_HPsi0ZZ

```



```

      | G_HPsi0ZHZH | G_HPsi0ZHZ | G_HPsi0AHAAH | G_HPsi0ZAH |
G_HPsi0ZHAH
      | G_HPsipWA | G_HPsipWHA | G_HPsipWZ | G_HPsipWHZ |
G_HPsipWAH
      | G_HPsipWHAH | G_HPsipWZH | G_HPsipWHZH | G_HPsippWW |
G_HPsippWHWH
      | G_HPsippWHW | G_Psi00ZH | G_Psi00AH | G_Psi00ZHAH
      | G_Psi0pWA | G_Psi0pWHA | G_Psi0pWZ | G_Psi0pWHZ |
G_Psi0pWAH
      | G_Psi0pWHAH | G_Psi0pWZH | G_Psi0pWHZH | G_Psi0ppWW |
G_Psi0ppWHWH
      | G_Psi0ppWHW | I_G_Psi0pWA | I_G_Psi0pWHA | I_G_Psi0pWZ |
I_G_Psi0pWHZ
      | I_G_Psi0pWAH | I_G_Psi0pWHAH | I_G_Psi0pWZH | I_G_Psi0pWHZH
      | I_G_Psi0ppWW | I_G_Psi0ppWHWH | I_G_Psi0ppWHW
      | G_PsippZZ | G_PsippZHZH | G_PsippAZ | G_PsippAAH |
G_PsippZAH
      | G_PsippWA | G_PsippWHA | G_PsippWZ | G_PsippWHZ |
G_PsippWAH
      | G_PsippWHAH | G_PsippWZH | G_PsippWHZH
      | G_PsiccZZ | G_PsiccAZ | G_PsiccAAH | G_PsiccZZH |
G_PsiccAZH
      | G_PsiccZAH
      | G_Htt | G_Hbb | G_Hcc | G_Htautau | G_H3 | G_H4
      | G_Hthth | G_Htht | G_Ethth | G_Etht | G_Ett
      | G_HHtt | G_HHthth | G_HHtht
      | G_Psi0tt | G_Psi0bb | G_Psi0cc | G_Psi0tautau
      | G_Psi1tt | G_Psi1bb | G_Psi1cc | G_Psi1tautau
      | G_Psipq3 | G_Psipq2 | G_Psipl3 | G_Psi0tth | G_Psi1tth
      | G_Psipbth | G_Ebb
      | G_HGaGa | G_HGaZ | G_EGaGa | G_EGaZ | G_EGIGl
      | Gs | I_Gs | G2
      | G_HWHW | G_HWHWH | G_HAHAH | G_HZHZ | G_HZHAH |
G_HAHZ
      | Mass of flavor | Width of flavor

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int
let orders = function
  | - → (0,0)
let input_parameters =
  []
let derived_parameters =
  []
let derived_parameter_arrays =
  []
let parameters () =
  { input = input_parameters;

```

```

    derived = derived_parameters;
    derived_arrays = derived_parameter_arrays }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let mgm ((m1, g, m2), fbf, c) = ((M m1, G g, M m2), fbf, c)
let mhm ((m1, h, m2), fbf, c) = ((M m1, O h, M m2), fbf, c)
let tgc ((g1, g2, g3), t, c) = ((G g1, G g2, G g3), t, c)
let qgc ((g1, g2, g3, g4), t, c) = ((G g1, G g2, G g3, G g4), t, c)
let hgg ((h, g1, g2), coup, c) = ((O h, G g1, G g2), coup, c)
let ghg ((g, h1, h2), coup, c) = ((G g, O h1, O h2), coup, c)
let hhg ((h1, h2, g1, g2), coup, c) = ((O h1, O h2, G g1, G g2), coup, c)

let electromagnetic_currents n =
  List.map mgm
    [ ((L (-n), Ga, L n), FBF (1, Psibar, V, Psi), Q_lepton);
      ((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q_up);
      ((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q_down) ]

let neutral_currents n =
  List.map mgm
    [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
      ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
      ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
      ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]

The sign of this coupling is just the one of the T3, being -(1/2) for leptons and
down quarks, and +(1/2) for neutrinos and up quarks.

let neutral_heavy_currents n =
  List.map mgm
    [ ((L (-n), ZH, L n), FBF ((-1), Psibar, VL, Psi), G_NC_heavy);
      ((N (-n), ZH, N n), FBF (1, Psibar, VL, Psi), G_NC_heavy);
      ((U (-n), ZH, U n), FBF (1, Psibar, VL, Psi), G_NC_heavy);
      ((D (-n), ZH, D n), FBF ((-1), Psibar, VL, Psi), G_NC_heavy)]
    @
    (if Flags.u1_gauged then
      [ ((L (-n), AH, L n), FBF (1, Psibar, VA, Psi), G_NC_h_lepton);
        ((N (-n), AH, N n), FBF (1, Psibar, VA, Psi), G_NC_h_neutrino);
        ((D (-n), AH, D n), FBF (1, Psibar, VA, Psi), G_NC_h_down)]
      else
      [])
let color_currents n =
  List.map mgm
    [ ((D (-n), Gl, D n), FBF ((-1), Psibar, V, Psi), Gs);
      ((U (-n), Gl, U n), FBF ((-1), Psibar, V, Psi), Gs)]
let heavy_top_currents =

```

List.map mgm

```
[ ((TopHb, Ga, TopH), FBF (1, Psibar, V, Psi), Q-up);
  ((TopHb, Z, TopH), FBF (1, Psibar, V, Psi), Q-Z-up);
  ((TopHb, Z, U 3), FBF (1, Psibar, VL, Psi), G-ZTHT);
  ((U (-3), Z, TopH), FBF (1, Psibar, VL, Psi), G-ZTHT);
  ((TopHb, ZH, U 3), FBF (1, Psibar, VL, Psi), G-ZHTHT);
  ((U (-3), ZH, TopH), FBF (1, Psibar, VL, Psi), G-ZHTHT);
  ((U (-3), Wp, D 3), FBF (1, Psibar, VL, Psi), G-CCtop);
  ((D (-3), Wm, U 3), FBF (1, Psibar, VL, Psi), G-CCtop);
  ((TopHb, WHp, D 3), FBF (1, Psibar, VL, Psi), G-CC-WH);
  ((D (-3), WHm, TopH), FBF (1, Psibar, VL, Psi), G-CC-WH);
  ((TopHb, Wp, D 3), FBF (1, Psibar, VL, Psi), G-CC-W);
  ((D (-3), Wm, TopH), FBF (1, Psibar, VL, Psi), G-CC-W)]
@
  (if Flags.u1_gauged then
    [ ((U (-3), AH, U 3), FBF (1, Psibar, VA, Psi), G-AHTT);
      ((TopHb, AH, TopH), FBF (1, Psibar, VA, Psi), G-AHTHTH);
      ((TopHb, AH, U 3), FBF (1, Psibar, VR, Psi), G-AHTHT);
      ((U (-3), AH, TopH), FBF (1, Psibar, VR, Psi), G-AHTHT)]
    else
      [])
  )
```

$$\mathcal{L}_{CC} = -\frac{g}{2\sqrt{2}} \sum_i \bar{\psi}_i (T^+ W^+ + T^- W^-) (1 - \gamma_5) \psi_i \quad (13.25)$$

let *charged_currents n* =

List.map mgm

```
[ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G-CC);
  ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G-CC);
  ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G-CC);
  ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G-CC)]
```

let *charged_heavy_currents n* =

List.map mgm

```
[ ((L (-n), WHm, N n), FBF (1, Psibar, VL, Psi), G-CC-heavy);
  ((N (-n), WHp, L n), FBF (1, Psibar, VL, Psi), G-CC-heavy);
  ((D (-n), WHm, U n), FBF (1, Psibar, VL, Psi), G-CC-heavy);
  ((U (-n), WHp, D n), FBF (1, Psibar, VL, Psi), G-CC-heavy)]
@
  (if Flags.u1_gauged then
    [ ((U (-n), AH, U n), FBF (1, Psibar, VA, Psi), G-NC-h-up)]
    else
      [])
  )
```

We specialize the third generation since there is an additional shift coming from the admixture of the heavy top quark. The universal shift, coming from the mixing in the non-Abelian gauge boson sector is unobservable. (Redefinition of coupling constants by measured ones.

let *yukawa* =

List.map mhm

```

[ ((U (-3), H, U 3), FBF (1, Psibar, S, Psi), G_Htt);
  ((D (-3), H, D 3), FBF (1, Psibar, S, Psi), G_Hbb);
  ((U (-2), H, U 2), FBF (1, Psibar, S, Psi), G_Hcc);
  ((L (-3), H, L 3), FBF (1, Psibar, S, Psi), G_Htautau)]

let yukawa_add' =
  List.map mhm
    [ ((TopHb, H, TopH), FBF (1, Psibar, S, Psi), G_Hthth);
      ((TopHb, H, U 3), FBF (1, Psibar, SLR, Psi), G_Htht);
      ((U (-3), H, TopH), FBF (1, Psibar, SLR, Psi), G_Htht);
      ((U (-3), Psi0, U 3), FBF (1, Psibar, S, Psi), G_Psi0tt);
      ((D (-3), Psi0, D 3), FBF (1, Psibar, S, Psi), G_Psi0bb);
      ((U (-2), Psi0, U 2), FBF (1, Psibar, S, Psi), G_Psi0cc);
      ((L (-3), Psi0, L 3), FBF (1, Psibar, S, Psi), G_Psi0tautau);
      ((U (-3), Psi1, U 3), FBF (1, Psibar, P, Psi), G_Psi1tt);
      ((D (-3), Psi1, D 3), FBF (1, Psibar, P, Psi), G_Psi1bb);
      ((U (-2), Psi1, U 2), FBF (1, Psibar, P, Psi), G_Psi1cc);
      ((L (-3), Psi1, L 3), FBF (1, Psibar, P, Psi), G_Psi1tautau);
      ((U (-3), Psip, D 3), FBF (1, Psibar, SLR, Psi), G_Psipq3);
      ((U (-2), Psip, D 2), FBF (1, Psibar, SLR, Psi), G_Psipq2);
      ((N (-3), Psip, L 3), FBF (1, Psibar, SR, Psi), G_Psipl3);
      ((D (-3), Psim, U 3), FBF (1, Psibar, SLR, Psi), G_Psipq3);
      ((D (-2), Psim, U 2), FBF (1, Psibar, SLR, Psi), G_Psipq2);
      ((L (-3), Psim, N 3), FBF (1, Psibar, SL, Psi), G_Psipl3);
      ((TopHb, Psi0, U 3), FBF (1, Psibar, SL, Psi), G_Psi0tth);
      ((U (-3), Psi0, TopH), FBF (1, Psibar, SR, Psi), G_Psi0tth);
      ((TopHb, Psi1, U 3), FBF (1, Psibar, SL, Psi), G_Psi1tth);
      ((U (-3), Psi1, TopH), FBF (1, Psibar, SR, Psi), G_Psi1tth);
      ((TopHb, Psip, D 3), FBF (1, Psibar, SL, Psi), G_Psipbth);
      ((D (-3), Psim, TopH), FBF (1, Psibar, SR, Psi), G_Psipbth)]

let yukawa_add =
  if Flags.u1_gauged then
    yukawa_add'
  else
    yukawa_add' @
    List.map mhm
      [ ((U (-3), Eta, U 3), FBF (1, Psibar, P, Psi), G_Ett);
        ((TopHb, Eta, U 3), FBF (1, Psibar, SLR, Psi), G_Etht);
        ((D (-3), Eta, D 3), FBF (1, Psibar, P, Psi), G_Ebb);
        ((U (-3), Eta, TopH), FBF (1, Psibar, SLR, Psi), G_Etht)]

```

$$\mathcal{L}_{\text{TGC}} = -e\partial_\mu A_\nu W_+^\mu W_-^\nu + \dots - e \cot \theta_w \partial_\mu Z_\nu W_+^\mu W_-^\nu + \dots \quad (13.26)$$

```

let standard_triple_gauge =
  List.map tgc
    [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
      ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW);
      ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_Gs) ]

let heavy_triple_gauge =

```

```

List.map tgc
  ([ ((Ga, WHm, WHp), Gauge_Gauge_Gauge 1, I_Q_W);
    ((Z, WHm, WHp), Gauge_Gauge_Gauge 1, I_G_ZWW);
    ((ZH, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZHWW);
    ((Z, WHm, Wp), Gauge_Gauge_Gauge 1, I_G_ZHWW);
    ((Z, Wm, WHp), Gauge_Gauge_Gauge (-1), I_G_ZHWW);
    ((ZH, WHm, Wp), Gauge_Gauge_Gauge 1, I_G_WWW);
    ((ZH, Wm, WHp), Gauge_Gauge_Gauge (-1), I_G_WWW);
    ((ZH, WHm, WHp), Gauge_Gauge_Gauge (-1), I_G_ZHWHWH)]
    @
    (if Flags.u1_gauged then
      [ ((AH, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_AHWW);
        ((AH, WHm, Wp), Gauge_Gauge_Gauge 1, I_G_AHWHW);
        ((AH, Wm, WHp), Gauge_Gauge_Gauge (-1), I_G_AHWHW);
        ((AH, WHm, WHp), Gauge_Gauge_Gauge 1, I_G_AHWHWH)]
      else
        []))
let triple_gauge =
  standard_triple_gauge @ heavy_triple_gauge
let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let standard_quartic_gauge =
  List.map qgc
    [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
      (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
      (Wm, Z, Wp, Ga), minus_gauge4, G_AZWW;
      (Wm, Ga, Wp, Ga), minus_gauge4, G_AAWW;
      (Gl, Gl, Gl, Gl), gauge4, G2 ]
let heavy_quartic_gauge =
  List.map qgc
    [ (WHm, Wp, WHm, Wp), gauge4, G_WWWW;
      (Wm, WHp, Wm, WHp), gauge4, G_WWWW;
      (WHm, WHp, WHm, WHp), gauge4, G_WH4;
      (Wm, Wp, WHm, WHp), gauge4, G_WHWHWW;
      (Wm, Wp, Wm, WHp), gauge4, G_WHWWWW;
      (Wm, Wp, WHm, Wp), gauge4, G_WHWWWW;
      (WHm, WHp, Wm, WHp), gauge4, G_WH3W;
      (WHm, WHp, WHm, Wp), gauge4, G_WH3W;
      (WHm, Z, WHp, Z), minus_gauge4, G_ZZWW;
      (WHm, Z, WHp, Ga), minus_gauge4, G_AZWW;
      (WHm, Ga, WHp, ZH), minus_gauge4, G_AAWW;
      (WHm, Z, WHp, ZH), minus_gauge4, G_ZZWW;
      (Wm, ZH, Wp, ZH), minus_gauge4, G_WWWW;
      (Wm, Ga, Wp, ZH), minus_gauge4, G_WWAZH;
      (Wm, Z, Wp, ZH), minus_gauge4, G_WWZZH;
      (WHm, Ga, WHp, ZH), minus_gauge4, G_WHWHAZH;
      (WHm, Z, WHp, ZH), minus_gauge4, G_WHWHZZH;
      (WHm, ZH, WHp, ZH), minus_gauge4, G_WH4;
      (WHm, Z, Wp, Z), minus_gauge4, G_WHWZZ;

```

```

      (Wm, Z, WHp, Z), minus_gauge4, G_WHWZZ;
      (WHm, Ga, Wp, Z), minus_gauge4, G_WHWAZ;
      (Wm, Ga, WHp, Z), minus_gauge4, G_WHWAZ;
      (WHm, ZH, Wp, ZH), minus_gauge4, G_WHWZHZH;
      (Wm, ZH, WHp, ZH), minus_gauge4, G_WHWZHZH;
      (WHm, Ga, Wp, ZH), minus_gauge4, G_WHWAZH;
      (Wm, Ga, WHp, ZH), minus_gauge4, G_WHWAZH;
      (WHm, Z, Wp, ZH), minus_gauge4, G_WHWZZH;
      (Wm, Z, WHp, ZH), minus_gauge4, G_WHWZZH]
@
  (if Flags.u1_gauged then
    [ (Wm, Ga, Wp, AH), minus_gauge4, G_WWAAH;
      (Wm, Z, Wp, AH), minus_gauge4, G_WWZAH;
      (WHm, Ga, WHp, AH), minus_gauge4, G_WWHHAAH;
      (WHm, Z, WHp, AH), minus_gauge4, G_WWHHZAH;
      (Wm, ZH, Wp, AH), minus_gauge4, G_WWZHAH;
      (WHm, ZH, WHp, AH), minus_gauge4, G_WWHHZHAH;
      (WHm, Ga, Wp, AH), minus_gauge4, G_WHWAAH;
      (Wm, Ga, WHp, AH), minus_gauge4, G_WHWAAH;
      (WHm, Z, Wp, AH), minus_gauge4, G_WHWZAH;
      (Wm, Z, WHp, AH), minus_gauge4, G_WHWZAH;
      (WHm, ZH, Wp, AH), minus_gauge4, G_WHWZHAH;
      (Wm, ZH, WHp, AH), minus_gauge4, G_WHWZHAH]
    else
      [])
let quartic_gauge =
  standard_quartic_gauge @ heavy_quartic_gauge
let standard_gauge_higgs' =
  List.map hgg
    [ ((H, Wp, Wm), Scalar_Vector_Vector 1, G_HWW);
      ((H, Z, Z), Scalar_Vector_Vector 1, G_HZZ) ]
let heavy_gauge_higgs =
  List.map hgg
    [ ((H, Wp, WHm), Scalar_Vector_Vector 1, G_HWHW);
      ((H, WHp, Wm), Scalar_Vector_Vector 1, G_HWHW);
      ((H, WHp, WHm), Scalar_Vector_Vector 1, G_HWHWH);
      ((H, ZH, ZH), Scalar_Vector_Vector 1, G_HWHWH);
      ((H, ZH, Z), Scalar_Vector_Vector 1, G_HZHZ);
      ((H, Wp, Wm), Scalar_Vector_Vector 1, G_HZHAH)]
@
  (if Flags.u1_gauged then
    [ ((H, AH, AH), Scalar_Vector_Vector 1, G_HAHAH);
      ((H, Z, AH), Scalar_Vector_Vector 1, G_HAHZ)]
    else
      [])
let triplet_gauge_higgs =
  List.map hgg
    [ ((Psi0, Wp, Wm), Scalar_Vector_Vector 1, G_PsiWW);

```

```

((Psi0, WHp, WHm), Scalar_Vector_Vector (-1), G_PsiWW);
((Psi0, WHp, Wm), Scalar_Vector_Vector 1, G_PsiWHW);
((Psi0, WHm, Wp), Scalar_Vector_Vector 1, G_PsiWHW);
((Psi0, Z, Z), Scalar_Vector_Vector 1, G_PsiZZ);
((Psi0, ZH, ZH), Scalar_Vector_Vector 1, G_PsiZHH);
((Psi0, ZH, Z), Scalar_Vector_Vector 1, G_PsiZH);
((Psim, Wp, Z), Scalar_Vector_Vector 1, G_PsiZW);
((Psip, Wm, Z), Scalar_Vector_Vector 1, G_PsiZW);
((Psim, WHp, Z), Scalar_Vector_Vector 1, G_PsiZWH);
((Psip, WHm, Z), Scalar_Vector_Vector 1, G_PsiZWH);
((Psim, Wp, ZH), Scalar_Vector_Vector 1, G_PsiZHW);
((Psip, Wm, ZH), Scalar_Vector_Vector 1, G_PsiZHW);
((Psim, WHp, ZH), Scalar_Vector_Vector 1, G_PsiZHWH);
((Psip, WHm, ZH), Scalar_Vector_Vector 1, G_PsiZHWH);
((Psimm, Wp, Wp), Scalar_Vector_Vector 1, G_PsippWW);
((Psipp, Wm, Wm), Scalar_Vector_Vector 1, G_PsippWW);
((Psimm, WHp, Wp), Scalar_Vector_Vector 1, G_PsippWHW);
((Psipp, WHm, Wm), Scalar_Vector_Vector 1, G_PsippWHW);
((Psimm, WHp, WHp), Scalar_Vector_Vector 1, G_PsippWHWH);
((Psipp, WHm, WHm), Scalar_Vector_Vector 1, G_PsippWHWH)]
@
(if Flags.u1_gauged then
  [((Psi0, AH, Z), Scalar_Vector_Vector 1, G_PsiZAH);
   ((Psi0, AH, ZH), Scalar_Vector_Vector 1, G_PsiZHAH);
   ((Psi0, AH, AH), Scalar_Vector_Vector 1, G_PsiAHAH);
   ((Psim, Wp, AH), Scalar_Vector_Vector 1, G_PsiAHW);
   ((Psip, Wm, AH), Scalar_Vector_Vector 1, G_PsiAHW);
   ((Psim, WHp, AH), Scalar_Vector_Vector 1, G_PsiAHWH);
   ((Psip, WHm, AH), Scalar_Vector_Vector 1, G_PsiAHWH)]
else
  [])
let triplet_gauge2_higgs =
List.map gh
  ([((Wp, H, Psim), Vector_Scalar_Scalar 1, G_PsiHW);
   ((Wm, H, Psip), Vector_Scalar_Scalar 1, G_PsiHW);
   ((WHp, H, Psim), Vector_Scalar_Scalar 1, G_PsiHWH);
   ((WHm, H, Psip), Vector_Scalar_Scalar 1, G_PsiHWH);
   ((Wp, Psi0, Psim), Vector_Scalar_Scalar 1, G_Psi0W);
   ((Wm, Psi0, Psip), Vector_Scalar_Scalar 1, G_Psi0W);
   ((WHp, Psi0, Psim), Vector_Scalar_Scalar 1, G_Psi0WH);
   ((WHm, Psi0, Psip), Vector_Scalar_Scalar 1, G_Psi0WH);
   ((Wp, Psi1, Psim), Vector_Scalar_Scalar 1, G_Psi1W);
   ((Wm, Psi1, Psip), Vector_Scalar_Scalar (-1), G_Psi1W);
   ((WHp, Psi1, Psim), Vector_Scalar_Scalar 1, G_Psi1WH);
   ((WHm, Psi1, Psip), Vector_Scalar_Scalar (-1), G_Psi1WH);
   ((Wp, Psip, Psimm), Vector_Scalar_Scalar 1, G_PsiPPW);
   ((Wm, Psim, Psipp), Vector_Scalar_Scalar 1, G_PsiPPW);
   ((WHp, Psip, Psimm), Vector_Scalar_Scalar 1, G_PsiPPWH);
   ((WHm, Psim, Psipp), Vector_Scalar_Scalar 1, G_PsiPPWH)]

```

```

((Ga, Psip, Psim), Vector_Scalar_Scalar 1, Q_lepton);
((Ga, Psipp, Psimm), Vector_Scalar_Scalar 2, Q_lepton);
((Z, H, Psi1), Vector_Scalar_Scalar 1, G_Psi1HZ);
((ZH, H, Psi1), Vector_Scalar_Scalar 1, G_Psi1HZH);
((Z, Psi0, Psi1), Vector_Scalar_Scalar 1, G_Psi01Z);
((ZH, Psi0, Psi1), Vector_Scalar_Scalar 1, G_Psi01ZH);
((Z, Psip, Psim), Vector_Scalar_Scalar 1, G_ZPsip);
((Z, Psipp, Psimm), Vector_Scalar_Scalar 2, G_ZPsipp);
((ZH, Psipp, Psimm), Vector_Scalar_Scalar 2, G_ZHPsipp)]
@
(if Flags.u1_gauged then
  [((AH, H, Psi1), Vector_Scalar_Scalar 1, G_Psi1HAH);
   ((AH, Psi0, Psi1), Vector_Scalar_Scalar 1, G_Psi01AH);
   ((AH, Psip, Psim), Vector_Scalar_Scalar 1, G_AHPsip);
   ((AH, Psipp, Psimm), Vector_Scalar_Scalar 2, G_AHPsipp)]
  else [])
let standard_gauge_higgs =
  standard_gauge_higgs' @ heavy_gauge_higgs @ triplet_gauge_higgs @
  triplet_gauge2_higgs
let standard_gauge_higgs4 =
  List.map hhgg
  [ (H, H, Wp, Wm), Scalar2_Vector2 1, G_HHWW;
    (H, H, Z, Z), Scalar2_Vector2 1, G_HHZZ ]
let littlest_gauge_higgs4 =
  List.map hhgg
  [ (H, H, WHp, WHm), Scalar2_Vector2 (-1), G_HHWW;
    (H, H, ZH, ZH), Scalar2_Vector2 (-1), G_HHWW;
    (H, H, Wp, WHm), Scalar2_Vector2 1, G_HHWHW;
    (H, H, WHp, Wm), Scalar2_Vector2 1, G_HHWHW;
    (H, H, ZH, Z), Scalar2_Vector2 (-1), G_HHZHZ;
    (H, Psi0, Wp, Wm), Scalar2_Vector2 1, G_HPsi0WW;
    (H, Psi0, WHp, WHm), Scalar2_Vector2 (-1), G_HPsi0WW;
    (H, Psi0, WHp, Wm), Scalar2_Vector2 1, G_HPsi0WHW;
    (H, Psi0, Wp, WHm), Scalar2_Vector2 1, G_HPsi0WHW;
    (H, Psi0, Z, Z), Scalar2_Vector2 1, G_HPsi0ZZ;
    (H, Psi0, ZH, ZH), Scalar2_Vector2 1, G_HPsi0ZHZH;
    (H, Psi0, ZH, Z), Scalar2_Vector2 1, G_HPsi0ZHZ;
    (H, Psim, Wp, Ga), Scalar2_Vector2 1, G_HPsipWA;
    (H, Psip, Wm, Ga), Scalar2_Vector2 1, G_HPsipWA;
    (H, Psim, WHp, Ga), Scalar2_Vector2 1, G_HPsipWHA;
    (H, Psip, WHm, Ga), Scalar2_Vector2 1, G_HPsipWHA;
    (H, Psim, Wp, Z), Scalar2_Vector2 1, G_HPsipWZ;
    (H, Psip, Wm, Z), Scalar2_Vector2 1, G_HPsipWZ;
    (H, Psim, WHp, Z), Scalar2_Vector2 1, G_HPsipWHZ;
    (H, Psip, WHm, Z), Scalar2_Vector2 1, G_HPsipWHZ;
    (H, Psim, Wp, ZH), Scalar2_Vector2 1, G_HPsipWZH;
    (H, Psip, Wm, ZH), Scalar2_Vector2 1, G_HPsipWZH;
    (H, Psim, WHp, ZH), Scalar2_Vector2 1, G_HPsipWHZH;
    (H, Psip, WHm, ZH), Scalar2_Vector2 1, G_HPsipWHZH;

```


$(H, Psimm, Wp, Wp), \text{Scalar2_Vector2 } 1, G_HPsippWW;$
 $(H, Psipp, Wm, Wm), \text{Scalar2_Vector2 } 1, G_HPsippWW;$
 $(H, Psimm, WHp, WHp), \text{Scalar2_Vector2 } 1, G_HPsippWHWH;$
 $(H, Psipp, WHm, WHm), \text{Scalar2_Vector2 } 1, G_HPsippWHWH;$
 $(H, Psimm, WHp, Wp), \text{Scalar2_Vector2 } 1, G_HPsippWHW;$
 $(H, Psipp, WHm, Wm), \text{Scalar2_Vector2 } 1, G_HPsippWHW;$
 $(Psi0, Psi0, Wp, Wm), \text{Scalar2_Vector2 } 2, G_HHWW;$
 $(Psi0, Psi0, WHp, WHm), \text{Scalar2_Vector2 } (-2), G_HHWW;$
 $(Psi0, Psi0, Z, Z), \text{Scalar2_Vector2 } 4, G_HHZZ;$
 $(Psi0, Psi0, ZH, ZH), \text{Scalar2_Vector2 } 1, G_Psi00ZH;$
 $(Psi0, Psi0, WHp, Wm), \text{Scalar2_Vector2 } 2, G_HHWHW;$
 $(Psi0, Psi0, Wp, WHm), \text{Scalar2_Vector2 } 2, G_HHWHW;$
 $(Psi0, Psi0, Z, ZH), \text{Scalar2_Vector2 } 4, G_HHZHZ;$
 $(Psi0, Psim, Wp, Ga), \text{Scalar2_Vector2 } 1, G_Psi0pWA;$
 $(Psi0, Psip, Wm, Ga), \text{Scalar2_Vector2 } 1, G_Psi0pWA;$
 $(Psi0, Psim, WHp, Ga), \text{Scalar2_Vector2 } 1, G_Psi0pWHA;$
 $(Psi0, Psip, WHm, Ga), \text{Scalar2_Vector2 } 1, G_Psi0pWHA;$
 $(Psi0, Psim, Wp, Z), \text{Scalar2_Vector2 } 1, G_Psi0pWZ;$
 $(Psi0, Psip, Wm, Z), \text{Scalar2_Vector2 } 1, G_Psi0pWZ;$
 $(Psi0, Psim, WHp, Z), \text{Scalar2_Vector2 } 1, G_Psi0pWHZ;$
 $(Psi0, Psip, WHm, Z), \text{Scalar2_Vector2 } 1, G_Psi0pWHZ;$
 $(Psi0, Psim, Wp, ZH), \text{Scalar2_Vector2 } 1, G_Psi0pWZH;$
 $(Psi0, Psip, Wm, ZH), \text{Scalar2_Vector2 } 1, G_Psi0pWZH;$
 $(Psi0, Psim, WHp, ZH), \text{Scalar2_Vector2 } 1, G_Psi0pWHZH;$
 $(Psi0, Psip, WHm, ZH), \text{Scalar2_Vector2 } 1, G_Psi0pWHZH;$
 $(Psi0, Psimm, Wp, Wp), \text{Scalar2_Vector2 } 1, G_Psi0ppWW;$
 $(Psi0, Psipp, Wm, Wm), \text{Scalar2_Vector2 } 1, G_Psi0ppWW;$
 $(Psi0, Psimm, WHp, WHp), \text{Scalar2_Vector2 } 1, G_Psi0ppWHWH;$
 $(Psi0, Psipp, WHm, WHm), \text{Scalar2_Vector2 } 1, G_Psi0ppWHWH;$
 $(Psi0, Psimm, WHp, Wp), \text{Scalar2_Vector2 } 1, G_Psi0ppWHW;$
 $(Psi0, Psipp, WHm, Wm), \text{Scalar2_Vector2 } 1, G_Psi0ppWHW;$
 $(Psi1, Psi1, Wp, Wm), \text{Scalar2_Vector2 } 2, G_HHWW;$
 $(Psi1, Psi1, WHp, WHm), \text{Scalar2_Vector2 } (-2), G_HHWW;$
 $(Psi1, Psi1, Z, Z), \text{Scalar2_Vector2 } 4, G_HHZZ;$
 $(Psi1, Psi1, ZH, ZH), \text{Scalar2_Vector2 } 1, G_Psi00ZH;$
 $(Psi1, Psi1, WHp, Wm), \text{Scalar2_Vector2 } 2, G_HHWHW;$
 $(Psi1, Psi1, Wp, WHm), \text{Scalar2_Vector2 } 2, G_HHWHW;$
 $(Psi1, Psi1, Z, ZH), \text{Scalar2_Vector2 } 4, G_HHZHZ;$
 $(Psi1, Psim, Wp, Ga), \text{Scalar2_Vector2 } 1, I_G_Psi0pWA;$
 $(Psi1, Psip, Wm, Ga), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWA;$
 $(Psi1, Psim, WHp, Ga), \text{Scalar2_Vector2 } 1, I_G_Psi0pWHA;$
 $(Psi1, Psip, WHm, Ga), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWHA;$
 $(Psi1, Psim, Wp, Z), \text{Scalar2_Vector2 } 1, I_G_Psi0pWZ;$
 $(Psi1, Psip, Wm, Z), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWZ;$
 $(Psi1, Psim, WHp, Z), \text{Scalar2_Vector2 } 1, I_G_Psi0pWHZ;$
 $(Psi1, Psip, WHm, Z), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWHZ;$
 $(Psi1, Psim, Wp, ZH), \text{Scalar2_Vector2 } 1, I_G_Psi0pWZH;$
 $(Psi1, Psip, Wm, ZH), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWZH;$
 $(Psi1, Psim, WHp, ZH), \text{Scalar2_Vector2 } 1, I_G_Psi0pWHZH;$
 $(Psi1, Psip, WHm, ZH), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWHZH;$

```

(Psi1, Psimm, Wp, Wp), Scalar2_Vector2 1, I_G_Psi0ppWW;
(Psi1, Psipp, Wm, Wm), Scalar2_Vector2 (-1), I_G_Psi0ppWW;
(Psi1, Psimm, WHp, WHp), Scalar2_Vector2 1, I_G_Psi0ppWHWH;
(Psi1, Psipp, WHm, WHm), Scalar2_Vector2 (-1), I_G_Psi0ppWHWH;
(Psi1, Psimm, WHp, Wp), Scalar2_Vector2 1, I_G_Psi0ppWHW;
(Psi1, Psipp, WHm, Wm), Scalar2_Vector2 (-1), I_G_Psi0ppWHW;
(Psip, Psim, Wp, Wm), Scalar2_Vector2 4, G_HHWW;
(Psip, Psim, WHp, WHm), Scalar2_Vector2 1, G_Psi00ZH;
(Psip, Psim, WHp, Wm), Scalar2_Vector2 4, G_HHWHW;
(Psip, Psim, Wp, WHm), Scalar2_Vector2 4, G_HHWHW;
(Psip, Psim, Z, Z), Scalar2_Vector2 1, G_PsippZZ;
(Psip, Psim, Ga, Ga), Scalar2_Vector2 2, G_AAWW;
(Psip, Psim, ZH, ZH), Scalar2_Vector2 1, G_PsippZHZH;
(Psip, Psim, Ga, Z), Scalar2_Vector2 4, G_PsippAZ;
(Psip, Psimm, Wp, Ga), Scalar2_Vector2 1, G_PsippWA;
(Psim, Psipp, Wm, Ga), Scalar2_Vector2 1, G_PsippWA;
(Psip, Psimm, WHp, Ga), Scalar2_Vector2 1, G_PsippWHA;
(Psim, Psipp, WHm, Ga), Scalar2_Vector2 1, G_PsippWHA;
(Psip, Psimm, Wp, Z), Scalar2_Vector2 1, G_PsippWZ;
(Psim, Psipp, Wm, Z), Scalar2_Vector2 1, G_PsippWZ;
(Psip, Psimm, WHp, Z), Scalar2_Vector2 1, G_PsippWHZ;
(Psim, Psipp, WHm, Z), Scalar2_Vector2 1, G_PsippWHZ;
(Psip, Psimm, Wp, ZH), Scalar2_Vector2 1, G_PsippWZH;
(Psim, Psipp, Wm, ZH), Scalar2_Vector2 1, G_PsippWZH;
(Psip, Psimm, WHp, ZH), Scalar2_Vector2 1, G_PsippWHZH;
(Psim, Psipp, WHm, ZH), Scalar2_Vector2 1, G_PsippWHZH;
(Psipp, Psimm, Wp, Wm), Scalar2_Vector2 2, G_HHWW;
(Psipp, Psimm, WHp, WHm), Scalar2_Vector2 (-2), G_HHWW;
(Psipp, Psimm, WHp, Wm), Scalar2_Vector2 2, G_HHWHW;
(Psipp, Psimm, Wp, WHm), Scalar2_Vector2 2, G_HHWHW;
(Psipp, Psimm, Z, Z), Scalar2_Vector2 1, G_PsiccZZ;
(Psipp, Psimm, Ga, Ga), Scalar2_Vector2 8, G_AAWW;
(Psipp, Psimm, ZH, ZH), Scalar2_Vector2 1, G_Psi00ZH;
(Psipp, Psimm, Ga, Z), Scalar2_Vector2 1, G_PsiccAZ;
(Psipp, Psimm, Z, ZH), Scalar2_Vector2 4, G_PsiccZZH;
(Psipp, Psimm, Ga, ZH), Scalar2_Vector2 4, G_PsiccAZH]

```

@

(if *Flags.u1_gauged* then

```

[(H, H, AH, AH), Scalar2_Vector2 1, G_HHAA;
 (H, H, AH, Z), Scalar2_Vector2 (-1), G_HHAHZ;
 (H, H, ZH, AH), Scalar2_Vector2 (-1), G_HHZHAH;
 (H, Psi0, AH, AH), Scalar2_Vector2 1, G_HPsi0AHAH;
 (H, Psi0, Z, AH), Scalar2_Vector2 1, G_HPsi0ZAH;
 (H, Psi0, ZH, AH), Scalar2_Vector2 1, G_HPsi0ZHAH;
 (H, Psim, Wp, AH), Scalar2_Vector2 1, G_HPsipWAH;
 (H, Psip, Wm, AH), Scalar2_Vector2 1, G_HPsipWAH;
 (H, Psim, WHp, AH), Scalar2_Vector2 1, G_HPsipWHAH;
 (H, Psip, WHm, AH), Scalar2_Vector2 1, G_HPsipWHAH;
 (Psi0, Psi0, AH, AH), Scalar2_Vector2 1, G_Psi00AH;
 (Psi0, Psi0, Z, AH), Scalar2_Vector2 4, G_HHAHZ;

```

```

(Psi0, Psi0, AH, ZH), Scalar2_Vector2 1, G_Psi00ZHAAH;
(Psi0, Psim, Wp, AH), Scalar2_Vector2 1, G_Psi0pWAH;
(Psi0, Psip, Wm, AH), Scalar2_Vector2 1, G_Psi0pWAH;
(Psi0, Psim, WHp, AH), Scalar2_Vector2 1, G_Psi0pWHAH;
(Psi0, Psip, WHm, AH), Scalar2_Vector2 1, G_Psi0pWHAH;
(Psi1, Psi1, AH, AH), Scalar2_Vector2 1, G_Psi00AAH;
(Psi1, Psi1, Z, AH), Scalar2_Vector2 4, G_HHAHZ;
(Psi1, Psi1, AH, ZH), Scalar2_Vector2 1, G_Psi00ZHAAH;
(Psi1, Psim, Wp, AH), Scalar2_Vector2 1, I_G_Psi0pWAH;
(Psi1, Psip, Wm, AH), Scalar2_Vector2 (-1), I_G_Psi0pWAH;
(Psi1, Psim, WHp, AH), Scalar2_Vector2 1, I_G_Psi0pWHAH;
(Psi1, Psip, WHm, AH), Scalar2_Vector2 (-1), I_G_Psi0pWHAH;
(Psip, Psim, AH, AH), Scalar2_Vector2 1, G_Psi00AAH;
(Psip, Psim, Ga, AH), Scalar2_Vector2 4, G_PsippAAH;
(Psip, Psim, Z, AH), Scalar2_Vector2 4, G_PsippZAH;
(Psip, Psimm, Wp, AH), Scalar2_Vector2 1, G_PsippWAH;
(Psim, Psipp, Wm, AH), Scalar2_Vector2 1, G_PsippWAH;
(Psip, Psimm, WHp, AH), Scalar2_Vector2 1, G_PsippWHAH;
(Psim, Psipp, WHm, AH), Scalar2_Vector2 1, G_PsippWHAH;
(Psipp, Psimm, AH, AH), Scalar2_Vector2 1, G_Psi00AAH;
(Psipp, Psimm, AH, ZH), Scalar2_Vector2 (-1), G_Psi00ZHAAH;
(Psipp, Psimm, Ga, AH), Scalar2_Vector2 4, G_PsiccAAH;
(Psipp, Psimm, Z, AH), Scalar2_Vector2 4, G_PsiccZAH]
else [])

let standard_higgs =
[ (O H, O H, O H), Scalar_Scalar_Scalar 1, G_H3 ]

let anomaly_higgs =
List.map hgg
[ (Eta, Gl, Gl), Dim5_Scalar_Gauge2_Skew 1, G_EGIGl;
  (Eta, Ga, Ga), Dim5_Scalar_Gauge2_Skew 1, G_EGaGa;
  (Eta, Ga, Z), Dim5_Scalar_Gauge2_Skew 1, G_EGaZ]
(* @ (H, Ga, Ga), Dim5_Scalar_Gauge2 1, G_HGaGa; (H, Ga, Z), Dim5_Scalar_Gauge2 1, G_HGaZ
*)

let standard_higgs4 =
[ (O H, O H, O H, O H), Scalar4 1, G_H4 ]

let gauge_higgs =
standard_gauge_higgs

let gauge_higgs4 =
standard_gauge_higgs4

let higgs =
standard_higgs

let higgs4 =
standard_higgs4

let top_quartic =
[ ((M (U (-3)), O H, O H, M (U 3)), GBBG (1, Psibar, S2, Psi), G_HHtt);
  ((M (TopHb), O H, O H, M TopH), GBBG (1, Psibar, S2, Psi), G_HHthth);

```

```

((M (U (-3)), O H, O H, M TopH), GBBG (1, Psibar, S2LR, Psi), G_HHtht);
((M (TopHb), O H, O H, M (U 3)), GBBG (1, Psibar, S2LR, Psi), G_HHtht)]

let goldstone_vertices =
  List.map hgg
  [ ((Phi0, Wm, Wp), Scalar_Vector_Vector 1, I_G_ZWW);
    ((Phip, Ga, Wm), Scalar_Vector_Vector 1, I_Q_W);
    ((Phip, Z, Wm), Scalar_Vector_Vector 1, I_G_ZWW);
    ((Phim, Wp, Ga), Scalar_Vector_Vector 1, I_Q_W);
    ((Phim, Wp, Z), Scalar_Vector_Vector 1, I_G_ZWW) ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1; 2; 3] @
   ThoList.flatmap color_currents [1; 2; 3] @
   ThoList.flatmap neutral_currents [1; 2; 3] @
   ThoList.flatmap neutral_heavy_currents [1; 2; 3] @
   ThoList.flatmap charged_currents [1; 2; 3] @
   ThoList.flatmap charged_heavy_currents [1; 2; 3] @
   heavy_top_currents @
   (if Flags.u1_gauged then []
    else anomaly_higgs) @
   yukawa @ yukawa_add @ triple_gauge @
   gauge_higgs @ higgs @ goldstone_vertices)

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4 @ top_quartic

let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))
| "numu" → M (N 2) | "numubar" → M (N (-2))
| "nutau" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "th" → M TopH | "thbar" → M TopHb
| "g" → G Gl
| "A" → G Ga | "Z" | "ZO" → G Z
| "AH" | "AHO" | "Ah" | "AhO" → G AH

```

```

| "ZH" | "ZH0" | "Zh" | "Zh0" → G ZH
| "W+" → G Wp | "W-" → G Wm
| "WH+" → G WHp | "WH-" → G WHm
| "H" | "h" → O H | "eta" | "Eta" → O Eta
| "Psi" | "Psi0" | "psi" | "psi0" → O Psi0
| "Psi1" | "psi1" → O Psi1
| "Psi+" | "psi+" | "Psip" | "psip" → O Psip
| "Psi-" | "psi-" | "Psim" | "psim" → O Psim
| "Psi++" | "psi++" | "Psipp" | "psipp" → O Psipp
| "Psi--" | "psi--" | "Psimm" | "psimm" → O Psimm
| _ → invalid_arg "Modellib_BSM.Littlest.flavor_of_string"

let flavor_to_string = function
| M f →
  begin match f with
  | L 1 → "e-" | L (-1) → "e+"
  | L 2 → "mu-" | L (-2) → "mu+"
  | L 3 → "tau-" | L (-3) → "tau+"
  | L _ → invalid_arg "Modellib_BSM.Littlest.flavor_to_string"
  | N 1 → "nue" | N (-1) → "nuebar"
  | N 2 → "numu" | N (-2) → "numubar"
  | N 3 → "nutau" | N (-3) → "nutaubar"
  | N _ → invalid_arg "Modellib_BSM.Littlest.flavor_to_string"
  | U 1 → "u" | U (-1) → "ubar"
  | U 2 → "c" | U (-2) → "cbar"
  | U 3 → "t" | U (-3) → "tbar"
  | U _ → invalid_arg "Modellib_BSM.Littlest.flavor_to_string"
  | D 1 → "d" | D (-1) → "dbar"
  | D 2 → "s" | D (-2) → "sbar"
  | D 3 → "b" | D (-3) → "bbar"
  | D _ → invalid_arg "Modellib_BSM.Littlest.flavor_to_string"
  | TopH → "th" | TopHb → "thbar"
  end
| G f →
  begin match f with
  | Gl → "g"
  | Ga → "A" | Z → "Z"
  | Wp → "W+" | Wm → "W-"
  | ZH → "ZH" | AH → "AH" | WHp → "WHp" | WHm → "WHm"
  end
| O f →
  begin match f with
  | Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
  | H → "H" | Eta → "Eta"
  | Psi0 → "Psi0" | Psi1 → "Psi1" | Psip → "Psi+"
  | Psim → "Psi-" | Psipp → "Psi++" | Psimm → "Psi--"
  end

let flavor_to_TeX = function
| M f →
  begin match f with

```

```

| L 1 → "e^-" | L (-1) → "e^+"
| L 2 → "\\mu^-" | L (-2) → "\\mu^+"
| L 3 → "\\tau^-" | L (-3) → "\\tau^+"
| L _ → invalid_arg "Modellib_BSM.Littlest.flavor_to_TeX"
| N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
| N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
| N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
| N _ → invalid_arg "Modellib_BSM.Littlest.flavor_to_TeX"
| U 1 → "u" | U (-1) → "\\bar{u}"
| U 2 → "c" | U (-2) → "\\bar{c}"
| U 3 → "t" | U (-3) → "\\bar{t}"
| U _ → invalid_arg "Modellib_BSM.Littlest.flavor_to_TeX"
| D 1 → "d" | D (-1) → "\\bar{d}"
| D 2 → "s" | D (-2) → "\\bar{s}"
| D 3 → "b" | D (-3) → "\\bar{b}"
| D _ → invalid_arg "Modellib_BSM.Littlest.flavor_to_TeX"
| TopH → "T" | TopHb → "\\bar{T}"
end
| G f →
  begin match f with
  | Gl → "g"
  | Ga → "\\gamma" | Z → "Z"
  | Wp → "W^+" | Wm → "W^-"
  | ZH → "Z_H" | AH → "\\gamma_H" | WHp → "W_H^+" |
WHm → "W_H^-"
  end
| O f →
  begin match f with
  | Phip → "\\Phi^+" | Phim → "\\Phi^-" | Phi0 →
"\\Phi^0"
  | H → "H" | Eta → "\\eta"
  | Psi0 → "\\Psi_S" | Psi1 → "\\Psi_P" | Psip → "\\Psi^+"
  | Psim → "\\Psi^-" | Psipp → "\\Psi^{++}" | Psimm →
"\\Psi^{--}"
  end
let flavor_symbol = function
| M f →
  begin match f with
  | L n when n > 0 → "l" ^ string_of_int n
  | L n → "l" ^ string_of_int (abs n) ^ "b"
  | N n when n > 0 → "n" ^ string_of_int n
  | N n → "n" ^ string_of_int (abs n) ^ "b"
  | U n when n > 0 → "u" ^ string_of_int n
  | U n → "u" ^ string_of_int (abs n) ^ "b"
  | D n when n > 0 → "d" ^ string_of_int n
  | D n → "d" ^ string_of_int (abs n) ^ "b"
  | TopH → "th" | TopHb → "thb"
  end
| G f →

```

```

begin match f with
| Gl → "g1"
| Ga → "a" | Z → "z"
| Wp → "wp" | Wm → "wm"
| ZH → "zh" | AH → "ah" | WHp → "whp" | WHm → "whm"
end
| O f →
begin match f with
| Phip → "pp" | Phim → "pm" | Phi0 → "p0"
| H → "h" | Eta → "eta"
| Psi0 → "psi0" | Psi1 → "psi1" | Psip → "psip"
| Psim → "psim" | Psipp → "psipp" | Psimm → "psimm"
end

```

There are PDG numbers for Z' , Z'' , W' , 32-34, respectively. We just introduce a number 38 for $Y0$ as a Z'' . As well, there is the number 8 for a t' . But we cheat a little bit and take the number 35 which is reserved for a heavy scalar Higgs for the Eta scalar. For the heavy Higgs states we take 35 and 36 for the neutral ones, 37 for the charged and 38 for the doubly-charged. The pseudoscalar gets the 39.

```

let pdg = function
| M f →
begin match f with
| L n when n > 0 → 9 + 2 × n
| L n → - 9 + 2 × n
| N n when n > 0 → 10 + 2 × n
| N n → - 10 + 2 × n
| U n when n > 0 → 2 × n
| U n → 2 × n
| D n when n > 0 → - 1 + 2 × n
| D n → 1 + 2 × n
| TopH → 8 | TopHb → (-8)
end
| G f →
begin match f with
| Gl → 21
| Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| AH → 32 | ZH → 33 | WHp → 34 | WHm → (-34)
end
| O f →
begin match f with
| Phip | Phim → 27 | Phi0 → 26
| Psi0 → 35 | Psi1 → 36 | Psip → 37 | Psim → (-37)
| Psipp → 38 | Psimm → (-38)
| H → 25 | Eta → 39
end
let mass_symbol f =
"mass(" ^ string_of_int (abs (pdg f)) ^ ")"

```

```

let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"

let constant_symbol = function
  | Unit → "unit" | Pi → "PI" | VHeavy → "vheavy"
  | Alpha_QED → "alpha" | E → "e" | G_weak → "g" | Vev →
"vev"
  | Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
  | Sinpsi → "sinpsi" | Cospsi → "cospsi"
  | Atpsi → "atpsi" | Sccs → "sccs"
  | Supp → "vF" | Supp2 → "v2F2"
  | Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdown"
  | Q_Z_up → "qzup"
  | G_ZHTHT → "gzhtht" | G_ZTHT → "gzhtht"
  | G_AHTHTH → "gahthth" | G_AHTHT → "gahtht" | G_AHTT →
"gahtt"
  | G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
  | G_NC_up → "gncup" | G_NC_down → "gncdown"
  | G_CC → "gcc" | G_CCtop → "gcctop" | G_CC_heavy →
"gcch"
  | G_CC_WH → "gccwh" | G_CC_W → "gccw"
  | G_NC_h_lepton → "gnchlep" | G_NC_h_neutrino → "gnchneu"
  | G_NC_h_up → "gnchup" | G_NC_h_down → "gnchdown"
  | G_NC_heavy → "gnch"
  | I_Q_W → "iqw" | I_G_ZWW → "igzww" | I_G_WWW →
"igwww"
  | I_G_AHWW → "igahww" | I_G_ZHWW → "igzhww" | I_G_ZWHW →
"igzwhw"
  | I_G_AHWHWH → "igahwhwh" | I_G_ZHWHWH → "igzhwhwh"
  | I_G_AHWHW → "igahwhw"
  | I_Q_H → "iqh"
  | G_WWWW → "gw4" | G_ZZWW → "gzzww"
  | G_AZWW → "gazww" | G_AAWW → "gaaww"
  | G_WH4 → "gwh4" | G_WHWHWW → "gwhwhww" | G_WHWWW →
"gwhwww"
  | G_WH3W → "gwh3w"
  | G_WWAAH → "gwwaah" | G_WWAZH → "gwwazh" | G_WWZZH →
"gwwzzh"
  | G_WWZAH → "gwwzah" | G_WHWHAAH → "gwhwhaah"
  | G_WHWHAZH → "gwhwhazh" | G_WHWHZZH → "gwhwhzzh"
  | G_WHWHZAH → "gwhwhzah"
  | G_WWZHAAH → "gwwzhah" | G_WHWHZHAAH → "gwhwhzhah"
  | G_WHWZZ → "gwhwzz" | G_WHWAZ → "gwhwaz"
  | G_WHWAHAH → "gwhwaah" | G_WHWZAH → "gwhwzah"
  | G_WHWZHZZH → "gwhwzhzh" | G_WHWZHAAH → "gwhwzhah"
  | G_WHWAZH → "gwhwazh" | G_WHWZZH → "gwhwzzh"
  | G_HWW → "ghww" | G_HZZ → "ghzz"
  | G_HHWW → "ghhww" | G_HHZZ → "ghhzz"
  | G_HWHW → "ghwhw" | G_HWHWH → "ghwhwh" | G_HAHAH →

```



```

"ghahah"
| G_HZHZ → "ghzhz" | G_HZHAH → "ghzhah"
| G_HAHZ → "ghahz"
| G_Htt → "ghtt" | G_Hbb → "ghbb"
| G_Htautau → "ghtautau" | G_Hcc → "ghcc"
| G_Hthth → "ghthth" | G_Htht → "ghtht"
| G_HHtt → "ghhtt" | G_HHthth → "ghhthth" | G_HHtht →
"ghhtht"
| G_Psi0tt → "gpsi0tt" | G_Psi0bb → "gpsi0bb"
| G_Psi0cc → "gpsi0cc" | G_Psi0tautau → "gpsi0tautau"
| G_Psi1tt → "gpsi1tt" | G_Psi1bb → "gpsi1bb"
| G_Psi1cc → "gpsi1cc" | G_Psi1tautau → "gpsi1tautau"
| G_Psipq3 → "gpsipq3" | G_Psipq2 → "gpsipq2" | G_Psipl3 →
"gpsil3"
| G_Psi0tth → "gpsi0tth" | G_Psi1tth → "gpsi1tth"
| G_Psipbth → "gpsipbth"
| G_Ethth → "gethth" | G_Etht → "getht"
| G_Ett → "gett" | G_Ebb → "gebb"
| G_HGaGa → "ghgaga" | G_HGaZ → "ghgaz"
| G_EGaGa → "geaa" | G_EGaZ → "geaz" | G_EGIGl → "gegg"
| G_H3 → "gh3" | G_H4 → "gh4"
| G_PsiWW → "gpsiww" | G_PsiWHW → "gpsiwhw"
| G_PsiZZ → "gpsizz" | G_PsiZHZH → "gpsizhzh"
| G_PsiZHZ → "gpsizhz" | G_PsiZAH → "gpsizah"
| G_PsiZHAH → "gpsizhah" | G_PsiAHAH → "gpsiahah"
| G_PsiZW → "gpsizw" | G_PsiZWH → "gpsizwh" | G_PsiAHW →
"gpsiahw"
| G_PsiAHWH → "gpsiahwh" | G_PsiZHW → "gpsizhw"
| G_PsiZHWH → "gpsizhwh"
| G_PsippWW → "gpsippww" | G_PsippWHW → "gpsippwhw"
| G_PsippWHWH → "gpsippwhwh"
| Gs → "gs" | G2 → "gs**2" | I_Gs → "igs"
| G_PsiHW → "gpsihw" | G_PsiHWH → "gpsihwh"
| G_Psi0W → "gpsi0w" | G_Psi0WH → "gpsi0wh"
| G_Psi1W → "gpsi1w" | G_Psi1WH → "gpsi1wh"
| G_PsiPPW → "gpsippw" | G_PsiPPWH → "gpsippwh"
| G_Psi1HAH → "gpsihah" | G_Psi01AH → "gpsi0ah"
| G_AHPsip → "gahpsip" | G_Psi1HZ → "gpsi1hz"
| G_Psi1HZH → "gpsi1hzh" | G_Psi01Z → "gpsi01z"
| G_Psi01ZH → "gpsi01zh" | G_ZPsip → "gzpsip"
| G_ZPsipp → "gzpsipp" | G_ZHPsipp → "gzhpsipp"
| G_HHAA → "ghhaa" | G_HHWW → "ghhwhw" | G_HHZHZ →
"ghhzhz"
| G_HHAHZ → "ghhahz" | G_HHZHAH → "ghhzhah"
| G_HPsi0WW → "ghpsi0ww" | G_HPsi0WHW → "ghpsi0whw"
| G_HPsi0ZZ → "ghpsi0zz" | G_HPsi0ZHZH → "ghpsi0zhzh"
| G_HPsi0ZHZ → "ghpsi0zhz" | G_HPsi0AHAH → "ghpsi0ahah"
| G_HPsi0ZAH → "ghpsi0zah" | G_HPsi0ZHAH → "ghpsi0zhah"
| G_HPsipWA → "ghpsipwa" | G_HPsipWHA → "ghpsipwha"
| G_HPsipWZ → "ghpsipwz" | G_HPsipWHZ → "ghpsiwhz"

```

```

| G_HPsipWAH → "ghpsipwah" | G_HPsipWHAH → "ghpsipwhah"
| G_HPsipWZH → "ghpsipwzh" | G_HPsipWHZH → "ghpsipwhzh"
| G_HPsippWW → "ghpsippww" | G_HPsippWHWH → "ghpsippwhwh"
| G_HPsippWHW → "ghpsippwhw" | G_Psi00ZH → "gpsi00zh"
| G_Psi00AH → "gpsi00ah" | G_Psi00ZHAH → "gpsi00zhah"
| G_Psi0pWA → "gpsi0pwa" | G_Psi0pWHA → "gpsi0pwha"
| G_Psi0pWZ → "gpsi0pwz" | G_Psi0pWHZ → "gpsi0pwhz"
| G_Psi0pWAH → "gpsi0pwah" | G_Psi0pWHAH → "gpsi0pwhah"
| G_Psi0pWZH → "gpsi0pwzh" | G_Psi0pWHZH → "gpsi0pwhzh"
| G_Psi0ppWW → "gpsi0ppww" | G_Psi0ppWHWH → "gpsi0ppwhwh"
| G_Psi0ppWHW → "gpsi0ppwhw"
| I_G_Psi0pWA → "i_gpsi0pwa" | I_G_Psi0pWHA → "i_gpsi0pwha"
| I_G_Psi0pWZ → "i_gpsi0pwz" | I_G_Psi0pWHZ → "i_gpsi0pwhz"
| I_G_Psi0pWAH → "i_gpsi0pwah" | I_G_Psi0pWHAH → "i_gpsi0pwhah"
| I_G_Psi0pWZH → "i_gpsi0pwzh" | I_G_Psi0pWHZH → "i_gpsi0pwhzh"
| I_G_Psi0ppWW → "i_gpsi0ppww" | I_G_Psi0ppWHWH →
"i_gpsi0ppwhwh"
| I_G_Psi0ppWHW → "i_gpsi0ppwhw"
| G_PsippZZ → "gpsippzz" | G_PsippZHZH → "gpsippzhzh"
| G_PsippAZ → "gpsippaz" | G_PsippAAH → "gpsippaah"
| G_PsippZAH → "gpsippzah"
| G_PsippWA → "gpsippwa" | G_PsippWHA → "gpsippwha"
| G_PsippWZ → "gpsippwz" | G_PsippWHZ → "gpsippwhz"
| G_PsippWAH → "gpsippwah" | G_PsippWHAH → "gpsippwhah"
| G_PsippWZH → "gpsippwzh" | G_PsippWHZH → "gpsippwhzh"
| G_PsiccZZ → "gpsiccz" | G_PsiccAZ → "gpsiccaz"
| G_PsiccAAH → "gpsiccaah" | G_PsiccZZH → "gpsiccczh"
| G_PsiccAZH → "gpsiccazh" | G_PsiccZAH → "gpsiccczah"
| Mass f → "mass" ^ flavor_symbol f
| Width f → "width" ^ flavor_symbol f

end

module Littlest_Tpar (Flags : BSM_flags) =
struct
  let rcs = rcs_file

  open Coupling

  let default_width = ref Timelike
  let use_fudged_width = ref false

  let options = Options.create
  [ "constant_width", Arg.Unit (fun () → default_width := Constant),
    "use_constant_width(also_in_t-channel)";
    "fudged_width", Arg.Set use_fudged_width,
    "use_fudge_factor_for_charge_particle_width";
    "custom_width", Arg.String (fun f → default_width := Custom f),
    "use_custom_width";
    "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
    "use_vanishing_width" ]

  type flavor = L of int | N of int | U of int | D of int

```

```

      | Topp | Toppb
      | Ga | Wp | Wm | Z | Gl | Lodd of int | Nodd of int
      | Uodd of int | Dodd of int
      | WHp | WHm | ZH | AH | Phip | Phim | Phi0 | H | Eta |
Psi0
      | Psi1 | Psip | Psim | Psipp | Psimm

```

```
type gauge = unit
```

```
let gauge_symbol () =
```

```
  failwith "Modellib.BSM.Littlest_Tpar.gauge_symbol: internal error"
```

```
let family n = [ L n; N n; U n; D n; Dodd n; Nodd n; Lodd n; Uodd n ]
```

Since *Phi* already belongs to the EW Goldstone bosons we use *Psi* for the TeV scale complex triplet.

We use the notation *Todd1* = *Uodd 3*, *Todd2* = *Uodd 4*.

```
let external_flavors () =
```

```

  [ "1st_Generation", ThoList.flatmap family [1; -1];
    "2nd_Generation", ThoList.flatmap family [2; -2];
    "3rd_Generation", ThoList.flatmap family [3; -3];
    "Heavy_Quarks", [Topp; Toppb; Uodd 4; Uodd (-4)];
    "HeavyScalars", [Psi0; Psi1; Psip; Psim; Psipp; Psimm];
    "Gauge_Bosons", if Flags.u1_gauged then
      [ Ga; Z; Wp; Wm; Gl; WHp; WHm; ZH; AH ]
    else
      [ Ga; Z; Wp; Wm; Gl; WHp; WHm; ZH ];
    "Higgs", if Flags.u1_gauged then [H]
    else [H; Eta];
    "Goldstone_Bosons", [Phip; Phim; Phi0] ]

```

```
let flavors () = ThoList.flatmap snd (external_flavors ())
```

```
let spinor n =
```

```
  if n ≥ 0 then
```

```
    Spinor
```

```
  else
```

```
    ConjSpinor
```

```
let lorentz = function
```

```

  | L n → spinor n | N n → spinor n
  | U n → spinor n | D n → spinor n
  | Topp → Spinor | Toppb → ConjSpinor
  | Ga | Gl → Vector
  | Wp | Wm | Z | WHp | WHm | ZH | AH → Massive_Vector
  | _ → Scalar

```

```
let color = function
```

```

  | U n → Color.SUN (if n > 0 then 3 else -3)
  | Uodd n → Color.SUN (if n > 0 then 3 else -3)
  | D n → Color.SUN (if n > 0 then 3 else -3)
  | Dodd n → Color.SUN (if n > 0 then 3 else -3)
  | Topp → Color.SUN 3 | Toppb → Color.SUN (-3)
  | Gl → Color.AdjSUN 3

```

```

| _ → Color.Singlet
let prop_spinor n =
  if n ≥ 0 then
    Prop_Spinor
  else
    Prop_ConjSpinor
let propagator = function
| L n → prop_spinor n | N n → prop_spinor n
| Lodd n → prop_spinor n | Nodd n → prop_spinor n
| U n → prop_spinor n | D n → prop_spinor n
| Uodd n → prop_spinor n | Dodd n → prop_spinor n
| Topp → Prop_Spinor | Toppb → Prop_ConjSpinor
| Ga | Gl → Prop_Feynman
| Wp | Wm | Z | WHp | WHm | ZH | AH → Prop_Unitarity
| Phip | Phim | Phi0 → Only_Insertion
| H | Eta | Psi0 | Psi1 | Psip | Psim | Psipp | Psimm →
Prop_Scalar

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    | Wp | Wm | U 3 | U (-3)
    | WHp | WHm | ZH | AH
    | Uodd _ | Dodd _ | Nodd _ | Lodd _
    | Topp | Toppb → Fudged
    | _ → !default_width
  else
    !default_width
let goldstone = function
| Wp → Some (Phip, Coupling.Const 1)
| Wm → Some (Phim, Coupling.Const 1)
| Z → Some (Phi0, Coupling.Const 1)
| _ → None
let conjugate = function
| L n → L (-n) | N n → N (-n)
| Lodd n → L (-n) | Nodd n → N (-n)
| U n → U (-n) | D n → D (-n)
| Uodd n → U (-n) | Dodd n → D (-n)
| Topp → Toppb | Toppb → Topp
| Gl → Gl | Ga → Ga | Z → Z
| Wp → Wm | Wm → Wp | WHm → WHp
| WHp → WHm | ZH → ZH | AH → AH
| Psi0 → Psi0 | Psi1 → Psi1 | Psip → Psim
| Psim → Psip | Psipp → Psimm | Psimm → Psipp
| Phip → Phim | Phim → Phip | Phi0 → Phi0
| H → H | Eta → Eta

```

```

let fermion = function
| L n → if n > 0 then 1 else -1
| N n → if n > 0 then 1 else -1
| U n → if n > 0 then 1 else -1
| D n → if n > 0 then 1 else -1
| Lodd n → if n > 0 then 1 else -1
| Nodd n → if n > 0 then 1 else -1
| Uodd n → if n > 0 then 1 else -1
| Dodd n → if n > 0 then 1 else -1
| Topp → 1 | Toppb → -1
| Gl | Ga | Z | Wp | Wm | WHp | WHm | AH | ZH → 0
| _ → 0

module Ch = Charges.QQ
let ( // ) = Algebra.Small_Rational.make

let charge = function
| L n | Lodd n → if n > 0 then -1//1 else 1//1
| N n | Nodd n → 0//1
| U n | Uodd n → if n > 0 then 2//3 else -2//3
| D n | Dodd n → if n > 0 then -1//3 else 1//3
| Topp → 2//3
| Toppb → -2//3
| Gl | Ga | Z | AH | ZH → 0//1
| Wp | WHp → 1//1
| Wm | WHm → -1//1
| H | Phi0 | Eta | Psi1 | Psi0 → 0//1
| Phip | Psip → 1//1
| Phim | Psim → -1//1
| Psipp → 2//1
| Psimm → -2//1

let lepton = function
| L n | N n | Lodd n | Nodd n
  → if n > 0 then 1//1 else -1//1
| U _ | D _ | _ → 0//1

let baryon = function
| L _ | N _ → 0//1
| U n | D n | Uodd n | Dodd n
  → if n > 0 then 1//1 else -1//1
| Topp → 1//1
| Toppb → -1//1
| _ → 0//1

let charges f =
[ charge f; lepton f; baryon f ]

type constant =
| Unit | Pi | Alpha_QED | Sin2thw
| Sinthw | Costhw | E | G_weak | Vev | VHeavy
| Supp | Supp2
| Sinpsi | Cospsi | Atpsi | Sccs (* Mixing angles of SU(2) *)

```

```

      | Q_lepton | Q_up | Q_down | Q_Z_up | G_CC | G_CCtop
      | G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down |
G_NC_heavy
      | G_NC_h_neutrino | G_NC_h_lepton | G_NC_h_up | G_NC_h_down
      | G_CC_heavy | G_ZHTHT | G_ZTHT | G_AHTHTH |
G_AHTHT | G_AHTT
      | G_CC_WH | G_CC_W
      | Gs | I_Gs | G2
      | I_Q_W | I_G_ZWW | I_G_WWW
      | I_G_AHWW | I_G_ZHWW | I_G_ZWHW | I_G_AHWHWH |
I_G_ZHWHWH
      | I_G_AHWHWH | I_Q_H
      | G_WWWW | G_ZZWW | G_AZWW | G_AAWW
      | G_WH4 | G_WHWHWW | G_WHWWW | G_WH3W
      | G_WWAAH | G_WWAZH | G_WWZZH | G_WWZAH |
G_WWHWAAH
      | G_WWHWAZH | G_WWHWZZH | G_WWHWZAH | G_WWZHAH
      | G_WHWHZHAH | G_WHWZZ | G_WHWAZ | G_WHWAAH |
G_WHWZAH
      | G_WHWZHZH | G_WHWZHAH | G_WHWAZH | G_WHWZZH
      | G_HWW | G_HHWW | G_HZZ | G_HHZZ
      | G_PsiWW | G_PsiWHW | G_PsiZZ | G_PsiZHZH
      | G_PsiZH | G_PsiZAH | G_PsiZHAH | G_PsiAAH
      | G_PsiZW | G_PsiZWH | G_PsiAHW | G_PsiAHWH
      | G_PsiZHW | G_PsiZHWH
      | G_PsippWW | G_PsippWHW | G_PsippWHWH
      | G_PsiHW | G_PsiHWH | G_Psi0W | G_Psi0WH
      | G_Psi1W | G_Psi1WH | G_PsiPPW | G_PsiPPWH
      | G_Psi1HAH | G_Psi01AH | G_AHPsip | G_Psi1HZ
      | G_Psi1HZH | G_Psi01Z | G_Psi01ZH | G_ZPsip | G_ZPsipp |
G_ZHPsipp
      | G_HHAA | G_HHWW | G_HHZH | G_HHAH | G_HHZHAH
      | G_HPsi0WW | G_HPsi0WHW | G_HPsi0ZZ
      | G_HPsi0ZHZH | G_HPsi0ZHZ | G_HPsi0AAH | G_HPsi0ZAH |
G_HPsi0ZHAH
      | G_HPsipWA | G_HPsipWHA | G_HPsipWZ | G_HPsipWHZ |
G_HPsipWAH
      | G_HPsipWHAH | G_HPsipWZH | G_HPsipWHZH | G_HPsippWW |
G_HPsippWHWH
      | G_HPsippWHW | G_Psi00ZH | G_Psi00AH | G_Psi00ZHAH
      | G_Psi0pWA | G_Psi0pWHA | G_Psi0pWZ | G_Psi0pWHZ |
G_Psi0pWAH
      | G_Psi0pWHAH | G_Psi0pWZH | G_Psi0pWHZH | G_Psi0ppWW |
G_Psi0ppWHWH
      | G_Psi0ppWHW | I_G_Psi0pWA | I_G_Psi0pWHA | I_G_Psi0pWZ |
I_G_Psi0pWHZ
      | I_G_Psi0pWAH | I_G_Psi0pWHAH | I_G_Psi0pWZH | I_G_Psi0pWHZH
      | I_G_Psi0ppWW | I_G_Psi0ppWHWH | I_G_Psi0ppWHW
      | G_PsippZZ | G_PsippZHZH | G_PsippAZ | G_PsippAAH |
G_PsippZAH

```

```

      | G_PsippWA | G_PsippWHA | G_PsippWZ | G_PsippWHZ |
G_PsippWAH
      | G_PsippWHAH | G_PsippWZH | G_PsippWHZH
      | G_PsiccZZ | G_PsiccAZ | G_PsiccAAH | G_PsiccZZH |
G_PsiccAZH
      | G_PsiccZAH
      | G_Htt | G_Hbb | G_Hcc | G_Htautau | G_H3 | G_H4
      | G_Hthth | G_Htht | G_Ethth | G_Etht | G_Ett
      | G_HHtt | G_HHthth | G_HHtht
      | G_Psi0tt | G_Psi0bb | G_Psi0cc | G_Psi0tautau
      | G_Psi1tt | G_Psi1bb | G_Psi1cc | G_Psi1tautau
      | G_Psipq3 | G_Psipq2 | G_Psipl3 | G_Psi0tth | G_Psi1tth
      | G_Psipbth | G_Ebb
      | G_HGaGa | G_HGaZ | G_EGaGa | G_EGaZ | G_EGIGl
      | G_HWHW | G_HWHWH | G_HAHAH | G_HZHZ | G_HZHAH |
G_HAHZ
      | Mass of flavor | Width of flavor

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int

let orders = function
  | _ → (0,0)

let input_parameters =
  []

let derived_parameters =
  []

let derived_parameter_arrays =
  []

let parameters () =
  { input = input_parameters;
    derived = derived_parameters;
    derived_arrays = derived_parameter_arrays }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let electromagnetic_currents n =
  [ ((L (-n), Ga, L n), FBF (1, Psibar, V, Psi), Q_lepton);
    ((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q_up);
    ((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q_down) ]

let color_currents n =
  [ ((U (-n), Gl, U n), FBF ((-1), Psibar, V, Psi), Gs);
    ((D (-n), Gl, D n), FBF ((-1), Psibar, V, Psi), Gs) ]

```

```

let neutral_currents n =
  [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
    ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
    ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
    ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]

```

The sign of this coupling is just the one of the T3, being $-(1/2)$ for leptons and down quarks, and $+(1/2)$ for neutrinos and up quarks.

```

let neutral_heavy_currents n =
  [ ((L (-n), ZH, L n), FBF ((-1), Psibar, VL, Psi), G_NC_heavy);
    ((N (-n), ZH, N n), FBF (1, Psibar, VL, Psi), G_NC_heavy);
    ((U (-n), ZH, U n), FBF (1, Psibar, VL, Psi), G_NC_heavy);
    ((D (-n), ZH, D n), FBF ((-1), Psibar, VL, Psi), G_NC_heavy)]
  @
  (if Flags.u1_gauged then
    [ ((L (-n), AH, L n), FBF (1, Psibar, VA, Psi), G_NC_h_lepton);
      ((N (-n), AH, N n), FBF (1, Psibar, VA, Psi), G_NC_h_neutrino);
      ((D (-n), AH, D n), FBF (1, Psibar, VA, Psi), G_NC_h_down)]
    else
    [])

```

```

let heavy_top_currents =
  [ ((Toppb, Ga, Topp), FBF (1, Psibar, V, Psi), Q_up);
    ((Toppb, Z, Topp), FBF (1, Psibar, V, Psi), Q_Z_up);
    ((Toppb, Z, U 3), FBF (1, Psibar, VL, Psi), G_ZTHT);
    ((U (-3), Z, Topp), FBF (1, Psibar, VL, Psi), G_ZTHT);
    ((Toppb, ZH, U 3), FBF (1, Psibar, VL, Psi), G_ZHTHT);
    ((U (-3), ZH, Topp), FBF (1, Psibar, VL, Psi), G_ZHTHT);
    ((U (-3), Wp, D 3), FBF (1, Psibar, VL, Psi), G_CCtop);
    ((D (-3), Wm, U 3), FBF (1, Psibar, VL, Psi), G_CCtop);
    ((Toppb, WHp, D 3), FBF (1, Psibar, VL, Psi), G_CC_WH);
    ((D (-3), WHm, Topp), FBF (1, Psibar, VL, Psi), G_CC_WH);
    ((Toppb, Wp, D 3), FBF (1, Psibar, VL, Psi), G_CC_W);
    ((D (-3), Wm, Topp), FBF (1, Psibar, VL, Psi), G_CC_W)]
  @
  (if Flags.u1_gauged then
    [ ((U (-3), AH, U 3), FBF (1, Psibar, VA, Psi), G_AHTT);
      ((Toppb, AH, Topp), FBF (1, Psibar, VA, Psi), G_AHTHTH);
      ((Toppb, AH, U 3), FBF (1, Psibar, VR, Psi), G_AHTHT);
      ((U (-3), AH, Topp), FBF (1, Psibar, VR, Psi), G_AHTHT)]
    else
    [])

```

$$\mathcal{L}_{CC} = -\frac{g}{2\sqrt{2}} \sum_i \bar{\psi}_i (T^+ W^+ + T^- W^-) (1 - \gamma_5) \psi_i \quad (13.27)$$

```

let charged_currents n =
  [ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G_CC);
    ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G_CC);
    ((L (-n), WHm, N n), FBF (1, Psibar, VL, Psi), G_CC_heavy);

```



```

((N (-n), WHp, L n), FBF (1, Psibar, VL, Psi), G_CC_heavy);
((D (-n), WHm, U n), FBF (1, Psibar, VL, Psi), G_CC_heavy);
((U (-n), WHp, D n), FBF (1, Psibar, VL, Psi), G_CC_heavy)]

let quark_currents n =
  [ ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_CC);
    ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G_CC)]
  @
  (if Flags.u1_gauged then
    [ ((U (-n), AH, U n), FBF (1, Psibar, VA, Psi), G_NC_h-up)]
    else
    [])

```

We specialize the third generation since there is an additional shift coming from the admixture of the heavy top quark. The universal shift, coming from the mixing in the non-Abelian gauge boson sector is unobservable. (Redefinition of coupling constants by measured ones.

```

let yukawa =
  [ ((U (-3), H, U 3), FBF (1, Psibar, S, Psi), G_Htt);
    ((D (-3), H, D 3), FBF (1, Psibar, S, Psi), G_Hbb);
    ((U (-2), H, U 2), FBF (1, Psibar, S, Psi), G_Hcc);
    ((L (-3), H, L 3), FBF (1, Psibar, S, Psi), G_Htautau)]

let yukawa_add' =
  [ ((Toppb, H, Topp), FBF (1, Psibar, S, Psi), G_Hthth);
    ((Toppb, H, U 3), FBF (1, Psibar, SLR, Psi), G_Htht);
    ((U (-3), H, Topp), FBF (1, Psibar, SLR, Psi), G_Htht);
    ((U (-3), Psi0, U 3), FBF (1, Psibar, S, Psi), G_Psi0tt);
    ((D (-3), Psi0, D 3), FBF (1, Psibar, S, Psi), G_Psi0bb);
    ((U (-2), Psi0, U 2), FBF (1, Psibar, S, Psi), G_Psi0cc);
    ((L (-3), Psi0, L 3), FBF (1, Psibar, S, Psi), G_Psi0tautau);
    ((U (-3), Psi1, U 3), FBF (1, Psibar, P, Psi), G_Psi1tt);
    ((D (-3), Psi1, D 3), FBF (1, Psibar, P, Psi), G_Psi1bb);
    ((U (-2), Psi1, U 2), FBF (1, Psibar, P, Psi), G_Psi1cc);
    ((L (-3), Psi1, L 3), FBF (1, Psibar, P, Psi), G_Psi1tautau);
    ((U (-3), Psip, D 3), FBF (1, Psibar, SLR, Psi), G_Psipq3);
    ((U (-2), Psip, D 2), FBF (1, Psibar, SLR, Psi), G_Psipq2);
    ((N (-3), Psip, L 3), FBF (1, Psibar, SR, Psi), G_Psipl3);
    ((D (-3), Psim, U 3), FBF (1, Psibar, SLR, Psi), G_Psipq3);
    ((D (-2), Psim, U 2), FBF (1, Psibar, SLR, Psi), G_Psipq2);
    ((L (-3), Psim, N 3), FBF (1, Psibar, SL, Psi), G_Psipl3);
    ((Toppb, Psi0, U 3), FBF (1, Psibar, SL, Psi), G_Psi0tth);
    ((U (-3), Psi0, Topp), FBF (1, Psibar, SR, Psi), G_Psi0tth);
    ((Toppb, Psi1, U 3), FBF (1, Psibar, SL, Psi), G_Psi1tth);
    ((U (-3), Psi1, Topp), FBF (1, Psibar, SR, Psi), G_Psi1tth);
    ((Toppb, Psip, D 3), FBF (1, Psibar, SL, Psi), G_Psipbth);
    ((D (-3), Psim, Topp), FBF (1, Psibar, SR, Psi), G_Psipbth)]

let yukawa_add =
  if Flags.u1_gauged then
    yukawa_add'
  else

```

```

yukawa_add' @
[ ((U (-3), Eta, U 3), FBF (1, Psibar, P, Psi), G_Ett);
  ((Toppb, Eta, U 3), FBF (1, Psibar, SLR, Psi), G_Etht);
  ((D (-3), Eta, D 3), FBF (1, Psibar, P, Psi), G_Ebb);
  ((U (-3), Eta, Topp), FBF (1, Psibar, SLR, Psi), G_Etht)]

```

$$\mathcal{L}_{\text{TGC}} = -e\partial_\mu A_\nu W_+^\mu W_-^\nu + \dots - e\cot\theta_w\partial_\mu Z_\nu W_+^\mu W_-^\nu + \dots \quad (13.28)$$

Check.

```

let standard_triple_gauge =
  [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
    ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW);
    ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_Gs) ]

let heavy_triple_gauge =
  [ ((Ga, WHm, WHp), Gauge_Gauge_Gauge 1, I_Q_W);
    ((Z, WHm, WHp), Gauge_Gauge_Gauge 1, I_G_ZWW);
    ((ZH, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZHWW);
    ((Z, WHm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWHW);
    ((Z, Wm, WHp), Gauge_Gauge_Gauge (-1), I_G_ZWHW);
    ((ZH, WHm, Wp), Gauge_Gauge_Gauge 1, I_G_WWW);
    ((ZH, Wm, WHp), Gauge_Gauge_Gauge (-1), I_G_WWW);
    ((ZH, WHm, WHp), Gauge_Gauge_Gauge (-1), I_G_ZHWHWH) ]
  @
  (if Flags.u1_gauged then
    [ ((AH, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_AHWW);
      ((AH, WHm, Wp), Gauge_Gauge_Gauge 1, I_G_AHWHW);
      ((AH, Wm, WHp), Gauge_Gauge_Gauge (-1), I_G_AHWHW);
      ((AH, WHm, WHp), Gauge_Gauge_Gauge 1, I_G_AHWHWH) ]
    else
    [])

let triple_gauge =
  standard_triple_gauge @ heavy_triple_gauge

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let standard_quartic_gauge =
  [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
    (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
    (Wm, Z, Wp, Ga), minus_gauge4, G_AZWW;
    (Wm, Ga, Wp, Ga), minus_gauge4, G_AAWW;
    (Gl, Gl, Gl, Gl), gauge4, G2 ]

let heavy_quartic_gauge =
  [ (WHm, Wp, WHm, Wp), gauge4, G_WWWW;
    (Wm, WHp, Wm, WHp), gauge4, G_WWWW;
    (WHm, WHp, WHm, WHp), gauge4, G_WH4;
    (Wm, Wp, WHm, WHp), gauge4, G_WHWHWW;
    (Wm, Wp, Wm, WHp), gauge4, G_WHWWW;
    (Wm, Wp, WHm, Wp), gauge4, G_WHWWW;

```

```

(WHm, WHp, Wm, WHp), gauge4, G-WH3W;
(WHm, WHp, WHm, Wp), gauge4, G-WH3W;
(WHm, Z, WHp, Z), minus-gauge4, G-ZZWW;
(WHm, Z, WHp, Ga), minus-gauge4, G-AZWW;
(WHm, Ga, WHp, ZH), minus-gauge4, G-AAWW;
(WHm, Z, WHp, ZH), minus-gauge4, G-ZZWW;
(Wm, ZH, Wp, ZH), minus-gauge4, G-WWWW;
(Wm, Ga, Wp, ZH), minus-gauge4, G-WWAZH;
(Wm, Z, Wp, ZH), minus-gauge4, G-WWZZH;
(WHm, Ga, WHp, ZH), minus-gauge4, G-WHWHAZH;
(WHm, Z, WHp, ZH), minus-gauge4, G-WHWHZZH;
(WHm, ZH, WHp, ZH), minus-gauge4, G-WH4;
(WHm, Z, Wp, Z), minus-gauge4, G-WHWZZ;
(Wm, Z, WHp, Z), minus-gauge4, G-WHWZZ;
(WHm, Ga, Wp, Z), minus-gauge4, G-WHWAZ;
(Wm, Ga, WHp, Z), minus-gauge4, G-WHWAZ;
(WHm, ZH, Wp, ZH), minus-gauge4, G-WHWZHZH;
(Wm, ZH, WHp, ZH), minus-gauge4, G-WHWZHZH;
(WHm, Ga, Wp, ZH), minus-gauge4, G-WHWAZH;
(Wm, Ga, WHp, ZH), minus-gauge4, G-WHWAZH;
(WHm, Z, Wp, ZH), minus-gauge4, G-WHWZZH;
(Wm, Z, WHp, ZH), minus-gauge4, G-WHWZZH]
@
  (if Flags.u1_gauged then
[ (Wm, Ga, Wp, AH), minus-gauge4, G-WWAAH;
  (Wm, Z, Wp, AH), minus-gauge4, G-WWZAH;
  (WHm, Ga, WHp, AH), minus-gauge4, G-WHWHAAH;
  (WHm, Z, WHp, AH), minus-gauge4, G-WHWHZAH;
  (Wm, ZH, Wp, AH), minus-gauge4, G-WWZHAAH;
  (WHm, ZH, WHp, AH), minus-gauge4, G-WHWHZHAAH;
  (WHm, Ga, Wp, AH), minus-gauge4, G-WHWAAH;
  (Wm, Ga, WHp, AH), minus-gauge4, G-WHWAAH;
  (WHm, Z, Wp, AH), minus-gauge4, G-WHWZAH;
  (Wm, Z, WHp, AH), minus-gauge4, G-WHWZAH;
  (WHm, ZH, Wp, AH), minus-gauge4, G-WHWZHAAH;
  (Wm, ZH, WHp, AH), minus-gauge4, G-WHWZHAAH]
  else
  [])
let quartic_gauge =
  standard-quartic-gauge @ heavy-quartic-gauge
let standard_gauge_higgs' =
[ ((H, Wp, Wm), Scalar_Vector_Vector 1, G_HWW);
  ((H, Z, Z), Scalar_Vector_Vector 1, G_HZZ) ]
let heavy_gauge_higgs =
[ ((H, Wp, WHm), Scalar_Vector_Vector 1, G_HWHW);
  ((H, WHp, Wm), Scalar_Vector_Vector 1, G_HWHW);
  ((H, WHp, WHm), Scalar_Vector_Vector 1, G_HWHWH);
  ((H, ZH, ZH), Scalar_Vector_Vector 1, G_HWHWH);
  ((H, ZH, Z), Scalar_Vector_Vector 1, G_HZH);

```

```

((H, Wp, Wm), Scalar_Vector_Vector 1, G_HZHAH)]
@
  (if Flags.u1_gauged then
[ ((H, AH, AH), Scalar_Vector_Vector 1, G_HAHAH);
  ((H, Z, AH), Scalar_Vector_Vector 1, G_HAHZ)]
  else
  [])

let triplet_gauge_higgs =
[ ((Psi0, Wp, Wm), Scalar_Vector_Vector 1, G_PsiWW);
  ((Psi0, WHp, WHm), Scalar_Vector_Vector (-1), G_PsiWW);
  ((Psi0, WHp, Wm), Scalar_Vector_Vector 1, G_PsiWHW);
  ((Psi0, WHm, Wp), Scalar_Vector_Vector 1, G_PsiWHW);
  ((Psi0, Z, Z), Scalar_Vector_Vector 1, G_PsiZZ);
  ((Psi0, ZH, ZH), Scalar_Vector_Vector 1, G_PsiZHZH);
  ((Psi0, ZH, Z), Scalar_Vector_Vector 1, G_PsiZHZ);
  ((Psim, Wp, Z), Scalar_Vector_Vector 1, G_PsiZW);
  ((Psip, Wm, Z), Scalar_Vector_Vector 1, G_PsiZW);
  ((Psim, WHp, Z), Scalar_Vector_Vector 1, G_PsiZWH);
  ((Psip, WHm, Z), Scalar_Vector_Vector 1, G_PsiZWH);
  ((Psim, Wp, ZH), Scalar_Vector_Vector 1, G_PsiZHW);
  ((Psip, Wm, ZH), Scalar_Vector_Vector 1, G_PsiZHW);
  ((Psim, WHp, ZH), Scalar_Vector_Vector 1, G_PsiZHWH);
  ((Psip, WHm, ZH), Scalar_Vector_Vector 1, G_PsiZHWH);
  ((Psimm, Wp, Wp), Scalar_Vector_Vector 1, G_PsippWW);
  ((Psipp, Wm, Wm), Scalar_Vector_Vector 1, G_PsippWW);
  ((Psimm, WHp, Wp), Scalar_Vector_Vector 1, G_PsippWHW);
  ((Psipp, WHm, Wm), Scalar_Vector_Vector 1, G_PsippWHW);
  ((Psimm, WHp, WHp), Scalar_Vector_Vector 1, G_PsippWHWH);
  ((Psipp, WHm, WHm), Scalar_Vector_Vector 1, G_PsippWHWH)]
@
  (if Flags.u1_gauged then
[ ((Psi0, AH, Z), Scalar_Vector_Vector 1, G_PsiZAH);
  ((Psi0, AH, ZH), Scalar_Vector_Vector 1, G_PsiZHAH);
  ((Psi0, AH, AH), Scalar_Vector_Vector 1, G_PsiAHAH);
  ((Psim, Wp, AH), Scalar_Vector_Vector 1, G_PsiAHW);
  ((Psip, Wm, AH), Scalar_Vector_Vector 1, G_PsiAHW);
  ((Psim, WHp, AH), Scalar_Vector_Vector 1, G_PsiAHWH);
  ((Psip, WHm, AH), Scalar_Vector_Vector 1, G_PsiAHWH)]
  else
  [])

let triplet_gauge2_higgs =
[ ((Wp, H, Psim), Vector_Scalar_Scalar 1, G_PsiHW);
  ((Wm, H, Psip), Vector_Scalar_Scalar 1, G_PsiHW);
  ((WHp, H, Psim), Vector_Scalar_Scalar 1, G_PsiHWH);
  ((WHm, H, Psip), Vector_Scalar_Scalar 1, G_PsiHWH);
  ((Wp, Psi0, Psim), Vector_Scalar_Scalar 1, G_Psi0W);
  ((Wm, Psi0, Psip), Vector_Scalar_Scalar 1, G_Psi0W);
  ((WHp, Psi0, Psim), Vector_Scalar_Scalar 1, G_Psi0WH);
  ((WHm, Psi0, Psip), Vector_Scalar_Scalar 1, G_Psi0WH);

```

```

((Wp, Psi1, Psim), Vector_Scalar_Scalar 1, G_Psi1W);
((Wm, Psi1, Psip), Vector_Scalar_Scalar (-1), G_Psi1W);
((WHp, Psi1, Psim), Vector_Scalar_Scalar 1, G_Psi1WH);
((WHm, Psi1, Psip), Vector_Scalar_Scalar (-1), G_Psi1WH);
((Wp, Psip, Psimm), Vector_Scalar_Scalar 1, G_PsiPPW);
((Wm, Psim, Psipp), Vector_Scalar_Scalar 1, G_PsiPPW);
((WHp, Psip, Psimm), Vector_Scalar_Scalar 1, G_PsiPPWH);
((WHm, Psim, Psipp), Vector_Scalar_Scalar 1, G_PsiPPWH);
((Ga, Psip, Psim), Vector_Scalar_Scalar 1, Q_lepton);
((Ga, Psipp, Psimm), Vector_Scalar_Scalar 2, Q_lepton);
((Z, H, Psi1), Vector_Scalar_Scalar 1, G_Psi1HZ);
((ZH, H, Psi1), Vector_Scalar_Scalar 1, G_Psi1HZH);
((Z, Psi0, Psi1), Vector_Scalar_Scalar 1, G_Psi01Z);
((ZH, Psi0, Psi1), Vector_Scalar_Scalar 1, G_Psi01ZH);
((Z, Psip, Psim), Vector_Scalar_Scalar 1, G_ZPsip);
((Z, Psipp, Psimm), Vector_Scalar_Scalar 2, G_ZPsipp);
((ZH, Psipp, Psimm), Vector_Scalar_Scalar 2, G_ZHPsipp)]
@
  (if Flags.u1_gauged then
[ (AH, H, Psi1), Vector_Scalar_Scalar 1, G_Psi1HAH);
  (AH, Psi0, Psi1), Vector_Scalar_Scalar 1, G_Psi01AH);
  (AH, Psip, Psim), Vector_Scalar_Scalar 1, G_AHPsip);
  (AH, Psipp, Psimm), Vector_Scalar_Scalar 2, G_AHPsipp)]
  else [])
let standard_gauge_higgs =
  standard_gauge_higgs' @ heavy_gauge_higgs @ triplet_gauge_higgs @
  triplet_gauge2_higgs
let standard_gauge_higgs4 =
  [ (H, H, Wp, Wm), Scalar2_Vector2 1, G_HHWW;
    (H, H, Z, Z), Scalar2_Vector2 1, G_HHZZ ]
let littlest_gauge_higgs4 =
  [ (H, H, WHp, WHm), Scalar2_Vector2 (-1), G_HHWW;
    (H, H, ZH, ZH), Scalar2_Vector2 (-1), G_HHWW;
    (H, H, Wp, WHm), Scalar2_Vector2 1, G_HHWHW;
    (H, H, WHp, Wm), Scalar2_Vector2 1, G_HHWHW;
    (H, H, ZH, Z), Scalar2_Vector2 (-1), G_HHZHZ;
    (H, Psi0, Wp, Wm), Scalar2_Vector2 1, G_HPsi0WW;
    (H, Psi0, WHp, WHm), Scalar2_Vector2 (-1), G_HPsi0WW;
    (H, Psi0, WHp, Wm), Scalar2_Vector2 1, G_HPsi0WHW;
    (H, Psi0, Wp, WHm), Scalar2_Vector2 1, G_HPsi0WHW;
    (H, Psi0, Z, Z), Scalar2_Vector2 1, G_HPsi0ZZ;
    (H, Psi0, ZH, ZH), Scalar2_Vector2 1, G_HPsi0ZHZH;
    (H, Psi0, ZH, Z), Scalar2_Vector2 1, G_HPsi0ZHZ;
    (H, Psim, Wp, Ga), Scalar2_Vector2 1, G_HPsipWA;
    (H, Psip, Wm, Ga), Scalar2_Vector2 1, G_HPsipWA;
    (H, Psim, WHp, Ga), Scalar2_Vector2 1, G_HPsipWHA;
    (H, Psip, WHm, Ga), Scalar2_Vector2 1, G_HPsipWHA;
    (H, Psim, Wp, Z), Scalar2_Vector2 1, G_HPsipWZ;
    (H, Psip, Wm, Z), Scalar2_Vector2 1, G_HPsipWZ;

```

$(H, Psim, WHp, Z), \text{Scalar2_Vector2 } 1, G_HPsipWHZ;$
 $(H, Psip, WHm, Z), \text{Scalar2_Vector2 } 1, G_HPsipWHZ;$
 $(H, Psim, Wp, ZH), \text{Scalar2_Vector2 } 1, G_HPsipWZH;$
 $(H, Psip, Wm, ZH), \text{Scalar2_Vector2 } 1, G_HPsipWZH;$
 $(H, Psim, WHp, ZH), \text{Scalar2_Vector2 } 1, G_HPsipWHZH;$
 $(H, Psip, WHm, ZH), \text{Scalar2_Vector2 } 1, G_HPsipWHZH;$
 $(H, Psimm, Wp, Wp), \text{Scalar2_Vector2 } 1, G_HPsippWW;$
 $(H, Psipp, Wm, Wm), \text{Scalar2_Vector2 } 1, G_HPsippWW;$
 $(H, Psimm, WHp, WHp), \text{Scalar2_Vector2 } 1, G_HPsippWHWH;$
 $(H, Psipp, WHm, WHm), \text{Scalar2_Vector2 } 1, G_HPsippWHWH;$
 $(H, Psimm, WHp, Wp), \text{Scalar2_Vector2 } 1, G_HPsippWHW;$
 $(H, Psipp, WHm, Wm), \text{Scalar2_Vector2 } 1, G_HPsippWHW;$
 $(Psi0, Psi0, Wp, Wm), \text{Scalar2_Vector2 } 2, G_HHWW;$
 $(Psi0, Psi0, WHp, WHm), \text{Scalar2_Vector2 } (-2), G_HHWW;$
 $(Psi0, Psi0, Z, Z), \text{Scalar2_Vector2 } 4, G_HHZZ;$
 $(Psi0, Psi0, ZH, ZH), \text{Scalar2_Vector2 } 1, G_Psi00ZH;$
 $(Psi0, Psi0, WHp, Wm), \text{Scalar2_Vector2 } 2, G_HHWHW;$
 $(Psi0, Psi0, Wp, WHm), \text{Scalar2_Vector2 } 2, G_HHWHW;$
 $(Psi0, Psi0, Z, ZH), \text{Scalar2_Vector2 } 4, G_HHZHZ;$
 $(Psi0, Psim, Wp, Ga), \text{Scalar2_Vector2 } 1, G_Psi0pWA;$
 $(Psi0, Psip, Wm, Ga), \text{Scalar2_Vector2 } 1, G_Psi0pWA;$
 $(Psi0, Psim, WHp, Ga), \text{Scalar2_Vector2 } 1, G_Psi0pWHA;$
 $(Psi0, Psip, WHm, Ga), \text{Scalar2_Vector2 } 1, G_Psi0pWHA;$
 $(Psi0, Psim, Wp, Z), \text{Scalar2_Vector2 } 1, G_Psi0pWZ;$
 $(Psi0, Psip, Wm, Z), \text{Scalar2_Vector2 } 1, G_Psi0pWZ;$
 $(Psi0, Psim, WHp, Z), \text{Scalar2_Vector2 } 1, G_Psi0pWHZ;$
 $(Psi0, Psip, WHm, Z), \text{Scalar2_Vector2 } 1, G_Psi0pWHZ;$
 $(Psi0, Psim, Wp, ZH), \text{Scalar2_Vector2 } 1, G_Psi0pWZH;$
 $(Psi0, Psip, Wm, ZH), \text{Scalar2_Vector2 } 1, G_Psi0pWZH;$
 $(Psi0, Psim, WHp, ZH), \text{Scalar2_Vector2 } 1, G_Psi0pWHZH;$
 $(Psi0, Psip, WHm, ZH), \text{Scalar2_Vector2 } 1, G_Psi0pWHZH;$
 $(Psi0, Psimm, Wp, Wp), \text{Scalar2_Vector2 } 1, G_Psi0ppWW;$
 $(Psi0, Psipp, Wm, Wm), \text{Scalar2_Vector2 } 1, G_Psi0ppWW;$
 $(Psi0, Psimm, WHp, WHp), \text{Scalar2_Vector2 } 1, G_Psi0ppWHWH;$
 $(Psi0, Psipp, WHm, WHm), \text{Scalar2_Vector2 } 1, G_Psi0ppWHWH;$
 $(Psi0, Psimm, WHp, Wp), \text{Scalar2_Vector2 } 1, G_Psi0ppWHW;$
 $(Psi0, Psipp, WHm, Wm), \text{Scalar2_Vector2 } 1, G_Psi0ppWHW;$
 $(Psi1, Psi1, Wp, Wm), \text{Scalar2_Vector2 } 2, G_HHWW;$
 $(Psi1, Psi1, WHp, WHm), \text{Scalar2_Vector2 } (-2), G_HHWW;$
 $(Psi1, Psi1, Z, Z), \text{Scalar2_Vector2 } 4, G_HHZZ;$
 $(Psi1, Psi1, ZH, ZH), \text{Scalar2_Vector2 } 1, G_Psi00ZH;$
 $(Psi1, Psi1, WHp, Wm), \text{Scalar2_Vector2 } 2, G_HHWHW;$
 $(Psi1, Psi1, Wp, WHm), \text{Scalar2_Vector2 } 2, G_HHWHW;$
 $(Psi1, Psi1, Z, ZH), \text{Scalar2_Vector2 } 4, G_HHZHZ;$
 $(Psi1, Psim, Wp, Ga), \text{Scalar2_Vector2 } 1, I_G_Psi0pWA;$
 $(Psi1, Psip, Wm, Ga), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWA;$
 $(Psi1, Psim, WHp, Ga), \text{Scalar2_Vector2 } 1, I_G_Psi0pWHA;$
 $(Psi1, Psip, WHm, Ga), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWHA;$
 $(Psi1, Psim, Wp, Z), \text{Scalar2_Vector2 } 1, I_G_Psi0pWZ;$
 $(Psi1, Psip, Wm, Z), \text{Scalar2_Vector2 } (-1), I_G_Psi0pWZ;$

```

(Psi1, Psim, WHp, Z), Scalar2_Vector2 1, I_G_Psi0pWHZ;
(Psi1, Psip, WHm, Z), Scalar2_Vector2 (-1), I_G_Psi0pWHZ;
(Psi1, Psim, Wp, ZH), Scalar2_Vector2 1, I_G_Psi0pWZH;
(Psi1, Psip, Wm, ZH), Scalar2_Vector2 (-1), I_G_Psi0pWZH;
(Psi1, Psim, WHp, ZH), Scalar2_Vector2 1, I_G_Psi0pWHZH;
(Psi1, Psip, WHm, ZH), Scalar2_Vector2 (-1), I_G_Psi0pWHZH;
(Psi1, Psimm, Wp, Wp), Scalar2_Vector2 1, I_G_Psi0ppWW;
(Psi1, Psipp, Wm, Wm), Scalar2_Vector2 (-1), I_G_Psi0ppWW;
(Psi1, Psimm, WHp, WHp), Scalar2_Vector2 1, I_G_Psi0ppWHWH;
(Psi1, Psipp, WHm, WHm), Scalar2_Vector2 (-1), I_G_Psi0ppWHWH;
(Psi1, Psimm, WHp, Wp), Scalar2_Vector2 1, I_G_Psi0ppWHW;
(Psi1, Psipp, WHm, Wm), Scalar2_Vector2 (-1), I_G_Psi0ppWHW;
(Psip, Psim, Wp, Wm), Scalar2_Vector2 4, G_HHWW;
(Psip, Psim, WHp, WHm), Scalar2_Vector2 1, G_Psi00ZH;
(Psip, Psim, WHp, Wm), Scalar2_Vector2 4, G_HHWHW;
(Psip, Psim, Wp, WHm), Scalar2_Vector2 4, G_HHWHW;
(Psip, Psim, Z, Z), Scalar2_Vector2 1, G_PsippZZ;
(Psip, Psim, Ga, Ga), Scalar2_Vector2 2, G_AAWW;
(Psip, Psim, ZH, ZH), Scalar2_Vector2 1, G_PsippZHZH;
(Psip, Psim, Ga, Z), Scalar2_Vector2 4, G_PsippAZ;
(Psip, Psimm, Wp, Ga), Scalar2_Vector2 1, G_PsippWA;
(Psim, Psipp, Wm, Ga), Scalar2_Vector2 1, G_PsippWA;
(Psip, Psimm, WHp, Ga), Scalar2_Vector2 1, G_PsippWHA;
(Psim, Psipp, WHm, Ga), Scalar2_Vector2 1, G_PsippWHA;
(Psip, Psimm, Wp, Z), Scalar2_Vector2 1, G_PsippWZ;
(Psim, Psipp, Wm, Z), Scalar2_Vector2 1, G_PsippWZ;
(Psip, Psimm, WHp, Z), Scalar2_Vector2 1, G_PsippWHZ;
(Psim, Psipp, WHm, Z), Scalar2_Vector2 1, G_PsippWHZ;
(Psip, Psimm, Wp, ZH), Scalar2_Vector2 1, G_PsippWZH;
(Psim, Psipp, Wm, ZH), Scalar2_Vector2 1, G_PsippWZH;
(Psip, Psimm, WHp, ZH), Scalar2_Vector2 1, G_PsippWHZH;
(Psim, Psipp, WHm, ZH), Scalar2_Vector2 1, G_PsippWHZH;
(Psipp, Psimm, Wp, Wm), Scalar2_Vector2 2, G_HHWW;
(Psipp, Psimm, WHp, WHm), Scalar2_Vector2 (-2), G_HHWW;
(Psipp, Psimm, WHp, Wm), Scalar2_Vector2 2, G_HHWHW;
(Psipp, Psimm, Wp, WHm), Scalar2_Vector2 2, G_HHWHW;
(Psipp, Psimm, Z, Z), Scalar2_Vector2 1, G_PsiccZZ;
(Psipp, Psimm, Ga, Ga), Scalar2_Vector2 8, G_AAWW;
(Psipp, Psimm, ZH, ZH), Scalar2_Vector2 1, G_Psi00ZH;
(Psipp, Psimm, Ga, Z), Scalar2_Vector2 1, G_PsiccAZ;
(Psipp, Psimm, Z, ZH), Scalar2_Vector2 4, G_PsiccZZH;
(Psipp, Psimm, Ga, ZH), Scalar2_Vector2 4, G_PsiccAZH]
@
(if Flags.u1_gauged then
[(H, H, AH, AH), Scalar2_Vector2 1, G_HHAA;
(H, H, AH, Z), Scalar2_Vector2 (-1), G_HHAHZ;
(H, H, ZH, AH), Scalar2_Vector2 (-1), G_HHZHAH;
(H, Psi0, AH, AH), Scalar2_Vector2 1, G_HPsi0AHAH;
(H, Psi0, Z, AH), Scalar2_Vector2 1, G_HPsi0ZAH;
(H, Psi0, ZH, AH), Scalar2_Vector2 1, G_HPsi0ZHAH;

```

```

(H, Psim, Wp, AH), Scalar2_Vector2 1, G_HPsipWAH;
(H, Psip, Wm, AH), Scalar2_Vector2 1, G_HPsipWAH;
(H, Psim, WHp, AH), Scalar2_Vector2 1, G_HPsipWHAH;
(H, Psip, WHm, AH), Scalar2_Vector2 1, G_HPsipWHAH;
(Psi0, Psi0, AH, AH), Scalar2_Vector2 1, G_Psi00AH;
(Psi0, Psi0, Z, AH), Scalar2_Vector2 4, G_HHAHZ;
(Psi0, Psi0, AH, ZH), Scalar2_Vector2 1, G_Psi00ZHAH;
(Psi0, Psim, Wp, AH), Scalar2_Vector2 1, G_Psi0pWAH;
(Psi0, Psip, Wm, AH), Scalar2_Vector2 1, G_Psi0pWAH;
(Psi0, Psim, WHp, AH), Scalar2_Vector2 1, G_Psi0pWHAH;
(Psi0, Psip, WHm, AH), Scalar2_Vector2 1, G_Psi0pWHAH;
(Psi1, Psi1, AH, AH), Scalar2_Vector2 1, G_Psi00AH;
(Psi1, Psi1, Z, AH), Scalar2_Vector2 4, G_HHAHZ;
(Psi1, Psi1, AH, ZH), Scalar2_Vector2 1, G_Psi00ZHAH;
(Psi1, Psim, Wp, AH), Scalar2_Vector2 1, I_G_Psi0pWAH;
(Psi1, Psip, Wm, AH), Scalar2_Vector2 (-1), I_G_Psi0pWAH;
(Psi1, Psim, WHp, AH), Scalar2_Vector2 1, I_G_Psi0pWHAH;
(Psi1, Psip, WHm, AH), Scalar2_Vector2 (-1), I_G_Psi0pWHAH;
(Psip, Psim, AH, AH), Scalar2_Vector2 1, G_Psi00AH;
(Psip, Psim, Ga, AH), Scalar2_Vector2 4, G_PsippAAH;
(Psip, Psim, Z, AH), Scalar2_Vector2 4, G_PsippZAH;
(Psip, Psimm, Wp, AH), Scalar2_Vector2 1, G_PsippWAH;
(Psim, Psipp, Wm, AH), Scalar2_Vector2 1, G_PsippWAH;
(Psip, Psimm, WHp, AH), Scalar2_Vector2 1, G_PsippWHAH;
(Psim, Psipp, WHm, AH), Scalar2_Vector2 1, G_PsippWHAH;
(Psipp, Psimm, AH, AH), Scalar2_Vector2 1, G_Psi00AH;
(Psipp, Psimm, AH, ZH), Scalar2_Vector2 (-1), G_Psi00ZHAH;
(Psipp, Psimm, Ga, AH), Scalar2_Vector2 4, G_PsiccAAH;
(Psipp, Psimm, Z, AH), Scalar2_Vector2 4, G_PsiccZAH]
else []

let standard_higgs =
[ (H, H, H), Scalar_Scalar_Scalar 1, G_H3 ]

let anomaly_higgs =
[ (Eta, Gl, Gl), Dim5_Scalar_Gauge2_Skew 1, G_EGIGl;
  (Eta, Ga, Ga), Dim5_Scalar_Gauge2_Skew 1, G_EGaGa;
  (Eta, Ga, Z), Dim5_Scalar_Gauge2_Skew 1, G_EGaZ]
(* @ (H, Ga, Ga), Dim5_Scalar_Gauge2 1, G_HGaGa; (H, Ga, Z), Dim5_Scalar_Gauge2 1, G_HGaZ
*)

let standard_higgs4 =
[ (H, H, H, H), Scalar4 1, G_H4 ]

let gauge_higgs =
standard_gauge_higgs

let gauge_higgs4 =
standard_gauge_higgs4

let higgs =
standard_higgs

```



```

let higgs4 =
  standard_higgs4

let top_quartic =
  [ ((U (-3), H, H, U 3), GBBG (1, Psibar, S2, Psi), G_HHtt);
    ((Toppb, H, H, Topp), GBBG (1, Psibar, S2, Psi), G_HHthth);
    ((U (-3), H, H, Topp), GBBG (1, Psibar, S2LR, Psi), G_HHtht);
    ((Toppb, H, H, U 3), GBBG (1, Psibar, S2LR, Psi), G_HHtht)]

let goldstone_vertices =
  [ ((Phi0, Wm, Wp), Scalar_Vector_Vector 1, I-G-ZWW);
    ((Phip, Ga, Wm), Scalar_Vector_Vector 1, I-Q-W);
    ((Phip, Z, Wm), Scalar_Vector_Vector 1, I-G-ZWW);
    ((Phim, Wp, Ga), Scalar_Vector_Vector 1, I-Q-W);
    ((Phim, Wp, Z), Scalar_Vector_Vector 1, I-G-ZWW) ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1;2;3] @
   ThoList.flatmap neutral_currents [1;2;3] @
   ThoList.flatmap color_currents [1;2;3] @
   ThoList.flatmap neutral_heavy_currents [1;2;3] @
   ThoList.flatmap charged_currents [1;2;3] @
   ThoList.flatmap quark_currents [1;2] @
   heavy_top_currents @
   (if Flags.u1_gauged then []
    else anomaly_higgs) @
   yukawa @ yukawa_add @ triple_gauge @
   gauge_higgs @ higgs @ goldstone_vertices)

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4 @ top_quartic

let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → L 1 | "e+" → L (-1)
| "mu-" → L 2 | "mu+" → L (-2)
| "tau-" → L 3 | "tau+" → L (-3)
| "nue" → N 1 | "nuebar" → N (-1)
| "numu" → N 2 | "numubar" → N (-2)
| "nuta" → N 3 | "nutaubar" → N (-3)
| "u" → U 1 | "ubar" → U (-1)
| "c" → U 2 | "cbar" → U (-2)
| "t" → U 3 | "tbar" → U (-3)
| "d" → D 1 | "dbar" → D (-1)
| "s" → D 2 | "sbar" → D (-2)

```

```

| "b" → D 3 | "bbar" → D (-3)
| "tp" → Topp | "tpbar" → Toppb
| "g" → Gl
| "A" → Ga | "Z" | "Z0" → Z
| "AH" | "AH0" | "Ah" | "Ah0" → AH
| "ZH" | "ZH0" | "Zh" | "Zh0" → ZH
| "W+" → Wp | "W-" → Wm
| "WH+" → WHp | "WH-" → WHm
| "H" | "h" → H | "eta" | "Eta" → Eta
| "Psi" | "Psi0" | "psi" | "psi0" → Psi0
| "Psi1" | "psi1" → Psi1
| "Psi+" | "psi+" | "Psip" | "psip" → Psip
| "Psi-" | "psi-" | "Psim" | "psim" → Psim
| "Psi++" | "psi++" | "Psipp" | "psipp" → Psipp
| "Psi--" | "psi--" | "Psimm" | "psimm" → Psimm
| _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_of_string"

let flavor_to_string = function
| L 1 → "e-" | L (-1) → "e+"
| L 2 → "mu-" | L (-2) → "mu+"
| L 3 → "tau-" | L (-3) → "tau+"
| L _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_string"
| N 1 → "nue" | N (-1) → "nuebar"
| N 2 → "numu" | N (-2) → "numubar"
| N 3 → "nutau" | N (-3) → "nutaubar"
| N _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_string"
| Lodd 1 → "l1odd-" | Lodd (-1) → "l1odd+"
| Lodd 2 → "l2odd-" | Lodd (-2) → "l2odd+"
| Lodd 3 → "l3odd-" | Lodd (-3) → "l3odd+"
| Lodd _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_string"
| Nodd 1 → "n1odd" | Nodd (-1) → "n1oddbar"
| Nodd 2 → "n2odd" | Nodd (-2) → "n2oddbar"
| Nodd 3 → "n3odd" | Nodd (-3) → "n3oddbar"
| Nodd _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_string"
| U 1 → "u" | U (-1) → "ubar"
| U 2 → "c" | U (-2) → "cbar"
| U 3 → "t" | U (-3) → "tbar"
| U _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_string"
| D 1 → "d" | D (-1) → "dbar"
| D 2 → "s" | D (-2) → "sbar"
| D 3 → "b" | D (-3) → "bbar"
| D _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_string"
| Uodd 1 → "uodd" | Uodd (-1) → "uoddbar"
| Uodd 2 → "codd" | Uodd (-2) → "coddbar"
| Uodd 3 → "t1odd" | Uodd (-3) → "t1oddbar"
| Uodd 4 → "t2odd" | Uodd (-4) → "t2oddbar"
| Uodd _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_string"
| Dodd 1 → "dodd" | Dodd (-1) → "doddbar"
| Dodd 2 → "sodd" | Dodd (-2) → "soddbar"
| Dodd 3 → "bodd" | Dodd (-3) → "boddbar"

```

```

| Dodd _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_string"
| Topp → "tp" | Toppb → "tpbar"
| Gl → "g"
| Ga → "A" | Z → "Z"
| Wp → "W+" | Wm → "W-"
| ZH → "ZH" | AH → "AH" | WHp → "WHp" | WHm → "WHm"
| Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
| H → "H" | Eta → "Eta"
| Psi0 → "Psi0" | Psi1 → "Psi1" | Psip → "Psi+"
| Psim → "Psi-" | Psipp → "Psi++" | Psimm → "Psi--"

let flavor_to_TeX = function
| L 1 → "e~-" | L (-1) → "e^+"
| L 2 → "\\mu~-" | L (-2) → "\\mu^+"
| L 3 → "\\tau~-" | L (-3) → "\\tau^+"
| L _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_TeX"
| N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
| N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
| N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
| N _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_TeX"
| Lodd 1 → "L_1~-" | Lodd (-1) → "L_1^+"
| Lodd 2 → "L_2~-" | Lodd (-2) → "L_2^+"
| Lodd 3 → "L_3~-" | Lodd (-3) → "L_3^+"
| Lodd _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_TeX"
| Nodd 1 → "N_1" | Nodd (-1) → "\\bar{N}_1"
| Nodd 2 → "N_2" | Nodd (-2) → "\\bar{N}_2"
| Nodd 3 → "N_3" | Nodd (-3) → "\\bar{N}_3"
| Nodd _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_TeX"
| U 1 → "u" | U (-1) → "\\bar{u}"
| U 2 → "c" | U (-2) → "\\bar{c}"
| U 3 → "t" | U (-3) → "\\bar{t}"
| U _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_TeX"
| D 1 → "d" | D (-1) → "\\bar{d}"
| D 2 → "s" | D (-2) → "\\bar{s}"
| D 3 → "b" | D (-3) → "\\bar{b}"
| D _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_TeX"
| Uodd 1 → "U" | Uodd (-1) → "\\bar{U}"
| Uodd 2 → "C" | Uodd (-2) → "\\bar{C}"
| Uodd 3 → "T_1" | Uodd (-3) → "\\bar{T}_1"
| Uodd 4 → "T_2" | Uodd (-4) → "\\bar{T}_2"
| Uodd _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_TeX"
| Dodd 1 → "D" | Dodd (-1) → "\\bar{D}"
| Dodd 2 → "S" | Dodd (-2) → "\\bar{S}"
| Dodd 3 → "B" | Dodd (-3) → "\\bar{B}"
| Dodd _ → invalid_arg "Modellib_BSM.Littlest_Tpar.flavor_to_TeX"
| Topp → "T^\\prime" | Toppb → "\\bar{T}^\\prime"
| Gl → "g"
| Ga → "\\gamma" | Z → "Z"
| Wp → "W^+" | Wm → "W^-"
| ZH → "Z-H" | AH → "\\gamma_H" | WHp → "W-H^+" |

```

```

WHm → "W_H^-"
| Phip → "\\Phi^+" | Phim → "\\Phi^-" | Phi0 → "\\Phi^0"
| H → "H" | Eta → "\\eta"
| Psi0 → "\\Psi_S" | Psi1 → "\\Psi_P" | Psip → "\\Psi^+"
| Psim → "\\Psi^-" | Psipp → "\\Psi^{++}" | Psimm →
"\\Psi^{--}"
let flavor_symbol = function
| L n when n > 0 → "l" ^ string_of_int n
| L n → "l" ^ string_of_int (abs n) ^ "b"
| Lodd n when n > 0 → "lodd" ^ string_of_int n
| Lodd n → "lodd" ^ string_of_int (abs n) ^ "b"
| N n when n > 0 → "n" ^ string_of_int n
| N n → "n" ^ string_of_int (abs n) ^ "b"
| Nodd n when n > 0 → "nodd" ^ string_of_int n
| Nodd n → "nodd" ^ string_of_int (abs n) ^ "b"
| U n when n > 0 → "u" ^ string_of_int n
| U n → "u" ^ string_of_int (abs n) ^ "b"
| D n when n > 0 → "d" ^ string_of_int n
| D n → "d" ^ string_of_int (abs n) ^ "b"
| Uodd n when n > 0 → "uodd" ^ string_of_int n
| Uodd n → "uodd" ^ string_of_int (abs n) ^ "b"
| Dodd n when n > 0 → "dodd" ^ string_of_int n
| Dodd n → "dodd" ^ string_of_int (abs n) ^ "b"
| Topp → "tp" | Toppb → "tpb"
| Gl → "gl"
| Ga → "a" | Z → "z"
| Wp → "wp" | Wm → "wm"
| ZH → "zh" | AH → "ah" | WHp → "whp" | WHm → "whm"
| Phip → "pp" | Phim → "pm" | Phi0 → "p0"
| H → "h" | Eta → "eta"
| Psi0 → "psi0" | Psi1 → "psi1" | Psip → "psip"
| Psim → "psim" | Psipp → "psipp" | Psimm → "psimm"

```

There are PDG numbers for Z', Z'', W', 32-34, respectively. We just introduce a number 38 for Y0 as a Z''. As well, there is the number 8 for a t'. But we cheat a little bit and take the number 35 which is reserved for a heavy scalar Higgs for the Eta scalar. For the heavy Higgs states we take 35 and 36 for the neutral ones, 37 for the charged and 38 for the doubly-charged. The pseudoscalar gets the 39. For the odd fermions we add 40 to the values for the SM particles.

```

let pdg = function
| L n when n > 0 → 9 + 2 × n
| L n → - 9 + 2 × n
| N n when n > 0 → 10 + 2 × n
| N n → - 10 + 2 × n
| U n when n > 0 → 2 × n
| U n → 2 × n
| D n when n > 0 → - 1 + 2 × n
| D n → 1 + 2 × n
| Lodd n when n > 0 → 49 + 2 × n
| Lodd n → - 49 + 2 × n

```

```

|  $Nodd\ n\ when\ n > 0 \rightarrow 50 + 2 \times n$ 
|  $Nodd\ n \rightarrow -50 + 2 \times n$ 
|  $Uodd\ n\ when\ n > 0 \rightarrow 40 + 2 \times n$ 
|  $Uodd\ n \rightarrow -40 + 2 \times n$ 
|  $Dodd\ n\ when\ n > 0 \rightarrow 39 + 2 \times n$ 
|  $Dodd\ n \rightarrow -39 + 2 \times n$ 
|  $Topp \rightarrow 8 \mid Toppb \rightarrow (-8)$ 
|  $Gl \rightarrow 21$ 
|  $Ga \rightarrow 22 \mid Z \rightarrow 23$ 
|  $Wp \rightarrow 24 \mid Wm \rightarrow (-24)$ 
|  $AH \rightarrow 32 \mid ZH \rightarrow 33 \mid WHp \rightarrow 34 \mid WHm \rightarrow (-34)$ 
|  $Phip \mid Phim \rightarrow 27 \mid Phi0 \rightarrow 26$ 
|  $Psi0 \rightarrow 35 \mid Psi1 \rightarrow 36 \mid Psip \rightarrow 37 \mid Psim \rightarrow (-37)$ 
|  $Psipp \rightarrow 38 \mid Psimm \rightarrow (-38)$ 
|  $H \rightarrow 25 \mid Eta \rightarrow 39$ 

let mass_symbol f =
  "mass(" ^ string_of_int (abs (pdg f)) ^ ")"

let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"

let constant_symbol = function
| Unit → "unit" | Pi → "PI" | VHeavy → "vheavy"
| Alpha_QED → "alpha" | E → "e" | G_weak → "g" | Vev →
"vev"
| Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
| Sinpsi → "sinpsi" | Cospsi → "cospsi"
| Atpsi → "atpsi" | Sccs → "sccs"
| Supp → "vF" | Supp2 → "v2F2"
| Q_lepton → "qllep" | Q_up → "qup" | Q_down → "qdown"
| Q_Z_up → "qzup"
| G_ZHTHT → "gzhtht" | G_ZTHT → "gzhtht"
| G_AHTHTH → "gahthth" | G_AHTHT → "gahtht" | G_AHTT →
"gahtt"
| G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
| G_NC_up → "gncup" | G_NC_down → "gncdown"
| G_CC → "gcc" | G_CCtop → "gcctop" | G_CC_heavy →
"gcch"
| G_CC_WH → "gccwh" | G_CC_W → "gccw"
| G_NC_h_lepton → "gnchlep" | G_NC_h_neutrino → "gnchneu"
| G_NC_h_up → "gnchup" | G_NC_h_down → "gnchdown"
| G_NC_heavy → "gnch"
| I_Q_W → "iqw" | I_G_ZWW → "igzww" | I_G_WWW →
"igwww"
| I_G_AHWW → "igahww" | I_G_ZHWW → "igzhww" | I_G_ZWHW →
"igzwhw"
| I_G_AHWHWH → "igahwhwh" | I_G_ZHWHWH → "igzhwhwh"
| I_G_AHWHW → "igahwhw"
| I_Q_H → "iqh"
| Gs → "gs" | I_Gs → "igs" | G2 → "gs**2"

```

```

| G_WWWWW → "gw4" | G_ZZWW → "gzzww"
| G_AZWW → "gazww" | G_AAWW → "gaaww"
| G_WH4 → "gwh4" | G_WHWHWW → "gwhwhww" | G_WHWWW →
"gwhwww"
| G_WH3W → "gwh3w"
| G_WWAAH → "gwwaah" | G_WWAZH → "gwwazh" | G_WWZZH →
"gwzzzh"
| G_WWZAH → "gwzzah" | G_WHWHAAH → "gwhwhaah"
| G_WHWHAZH → "gwhwhazh" | G_WHWHZZH → "gwhwhzzh"
| G_WHWHZAH → "gwhwhzah"
| G_WWZHAH → "gwzzhah" | G_WHWHZHAH → "gwhwhzhah"
| G_WHWZZ → "gwhwzz" | G_WHWAZ → "gwhwaz"
| G_WHWAAH → "gwhwaah" | G_WHWZAH → "gwhwzah"
| G_WHWZHZH → "gwhwzhzh" | G_WHWZHAH → "gwhwzhah"
| G_WHWAZH → "gwhwazh" | G_WHWZZH → "gwhwzzh"
| G_HWW → "ghww" | G_HZZ → "ghzz"
| G_HHWW → "ghhww" | G_HHZZ → "ghhzz"
| G_HWHW → "ghwhw" | G_HWHWH → "ghwhwh" | G_HAHAAH →
"ghahah"
| G_HZHZ → "ghzhz" | G_HZHAH → "ghzhah"
| G_HAHZ → "ghahz"
| G_Htt → "ghtt" | G_Hbb → "ghbb"
| G_Htautau → "ghtautau" | G_Hcc → "ghcc"
| G_Hthth → "ghthth" | G_Htht → "ghtht"
| G_HHtt → "ghhtt" | G_HHthth → "ghhthth" | G_HHtht →
"ghhtht"
| G_Psi0tt → "gpsi0tt" | G_Psi0bb → "gpsi0bb"
| G_Psi0cc → "gpsi0cc" | G_Psi0tautau → "gpsi0tautau"
| G_Psi1tt → "gpsi1tt" | G_Psi1bb → "gpsi1bb"
| G_Psi1cc → "gpsi1cc" | G_Psi1tautau → "gpsi1tautau"
| G_Psipq3 → "gpsipq3" | G_Psipq2 → "gpsipq2" | G_Psipl3 →
"gpsil3"
| G_Psi0th → "gpsi0th" | G_Psi1th → "gpsi1th"
| G_Psipbth → "gpsipbth"
| G_Ethth → "gethth" | G_Etht → "getht"
| G_Ett → "gett" | G_Ebb → "gebb"
| G_HGaGa → "ghgaga" | G_HGaZ → "ghgaz"
| G_EGaGa → "geaa" | G_EGaZ → "geaz" | G_EGIGl → "gegg"
| G_H3 → "gh3" | G_H4 → "gh4"
| G_PsiWW → "gpsiw" | G_PsiWHW → "gpsiwhw"
| G_PsiZZ → "gpsizz" | G_PsiZHZH → "gpsizhzh"
| G_PsiZHZ → "gpsizhz" | G_PsiZAH → "gpsizah"
| G_PsiZHAH → "gpsizhah" | G_PsiAHAAH → "gpsiahah"
| G_PsiZW → "gpsizw" | G_PsiZWH → "gpsizwh" | G_PsiAHW →
"gpsiahw"
| G_PsiAHWH → "gpsiahwh" | G_PsiZHW → "gpsizhw"
| G_PsiZHWH → "gpsizhwh"
| G_PsippWW → "gpsippww" | G_PsippWHW → "gpsippwhw"
| G_PsippWHWH → "gpsippwhwh"
| G_PsiHW → "gpsihw" | G_PsiHWH → "gpsihwh"

```

```

| G_Psi0W → "gpsi0w" | G_Psi0WH → "gpsi0wh"
| G_Psi1W → "gpsi1w" | G_Psi1WH → "gpsi1wh"
| G_PsiPPW → "gpsippw" | G_PsiPPWH → "gpsippwh"
| G_Psi1HAH → "gpsihah" | G_Psi01AH → "gpsi0ah"
| G_AHPsip → "gahpsip" | G_Psi1HZ → "gpsi1hz"
| G_Psi1HZH → "gpsi1hzh" | G_Psi01Z → "gpsi01z"
| G_Psi01ZH → "gpsi01zh" | G_ZPsip → "gzpsip"
| G_ZPsipp → "gzpsipp" | G_ZHPsipp → "gzhpsipp"
| G_HHAA → "ghhaa" | G_HHWHW → "ghhwhw" | G_HHZHZ →
"ghhzhz"
| G_HHAHZ → "ghhahz" | G_HHZHAH → "ghhzhah"
| G_HPsi0WW → "ghpsi0ww" | G_HPsi0WHW → "ghpsi0whw"
| G_HPsi0ZZ → "ghpsi0zz" | G_HPsi0ZHZH → "ghpsi0zhzh"
| G_HPsi0ZHZ → "ghpsi0zhz" | G_HPsi0AAH → "ghpsi0ahah"
| G_HPsi0ZAH → "ghpsi0zah" | G_HPsi0ZHAH → "ghpsi0zhah"
| G_HPsipWA → "ghpsipwa" | G_HPsipWHA → "ghpsipwha"
| G_HPsipWZ → "ghpsipwz" | G_HPsipWHZ → "ghpsipwhz"
| G_HPsipWAH → "ghpsipwah" | G_HPsipWHAH → "ghpsipwhah"
| G_HPsipWZH → "ghpsipwzh" | G_HPsipWHZH → "ghpsipwhzh"
| G_HPsippWW → "ghpsippww" | G_HPsippWHWH → "ghpsippwhwh"
| G_HPsippWHW → "ghpsippwhw" | G_Psi00ZH → "gpsi00zh"
| G_Psi00AH → "gpsi00ah" | G_Psi00ZHAH → "gpsi00zhah"
| G_Psi0pWA → "gpsi0pwa" | G_Psi0pWHA → "gpsi0pwha"
| G_Psi0pWZ → "gpsi0pwz" | G_Psi0pWHZ → "gpsi0pwhz"
| G_Psi0pWAH → "gpsi0pwah" | G_Psi0pWHAH → "gpsi0pwhah"
| G_Psi0pWZH → "gpsi0pwzh" | G_Psi0pWHZH → "gpsi0pwhzh"
| G_Psi0ppWW → "gpsi0ppww" | G_Psi0ppWHWH → "gpsi0ppwhwh"
| G_Psi0ppWHW → "gpsi0ppwhw"
| I_G_Psi0pWA → "i_gpsi0pwa" | I_G_Psi0pWHA → "i_gpsi0pwha"
| I_G_Psi0pWZ → "i_gpsi0pwz" | I_G_Psi0pWHZ → "i_gpsi0pwhz"
| I_G_Psi0pWAH → "i_gpsi0pwah" | I_G_Psi0pWHAH → "i_gpsi0pwhah"
| I_G_Psi0pWZH → "i_gpsi0pwzh" | I_G_Psi0pWHZH → "i_gpsi0pwhzh"
| I_G_Psi0ppWW → "i_gpsi0ppww" | I_G_Psi0ppWHWH →
|i_gpsi0ppwhwh"
| I_G_Psi0ppWHW → "i_gpsi0ppwhw"
| G_PsippZZ → "gpsippzz" | G_PsippZHZH → "gpsippzhzh"
| G_PsippAZ → "gpsippaz" | G_PsippAAH → "gpsippaah"
| G_PsippZAH → "gpsippzah"
| G_PsippWA → "gpsippwa" | G_PsippWHA → "gpsippwha"
| G_PsippWZ → "gpsippwz" | G_PsippWHZ → "gpsippwhz"
| G_PsippWAH → "gpsippwah" | G_PsippWHAH → "gpsippwhah"
| G_PsippWZH → "gpsippwzh" | G_PsippWHZH → "gpsippwhzh"
| G_PsiccZZ → "gpsiccz" | G_PsiccAZ → "gpsiccz"
| G_PsiccAAH → "gpsiccaah" | G_PsiccZZH → "gpsicczzh"
| G_PsiccAZH → "gpsiccazh" | G_PsiccZAH → "gpsicczah"
| Mass f → "mass" ^ flavor_symbol f
| Width f → "width" ^ flavor_symbol f

```

end

module *Simplest* (Flags : BSM_flags) =

```

struct
  let rcs = rcs_file

  open Coupling

  let default_width = ref Timelike
  let use_fudged_width = ref false

  let options = Options.create
  [ "constant_width", Arg.Unit (fun () → default_width := Constant),
    "use_constant_width(also_in_t-channel)",
    "fudged_width", Arg.Set use_fudged_width,
    "use_fudge_factor_for_charge_particle_width",
    "custom_width", Arg.String (fun f → default_width := Custom f),
    "use_custom_width",
    "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
    "use_vanishing_width" ]

```

We do not introduce the Goldstones for the heavy vectors here. The heavy quarks are simply numerated by their generation, the assignments whether they are up- or down-type will be defined by the model.

```

type flavor = L of int | N of int | U of int | D of int | QH of int
             | NH of int | Wp | Wm | Ga | Z | Xp | Xm | X0 | Y0 | ZH
             | Phip | Phim | Phi0 | H | Eta | Gl

type gauge = unit

let gauge_symbol () =
  failwith "Modellib_BSM.Simplest.gauge_symbol: internal error"

let family n = [ L n; N n; U n; D n; QH n; NH n ]

```

Note that we add all heavy quarks, U , D , C , S , in order to have both embeddings included.

```

let external_flavors () =
  [ "1st_Generation_(incl._heavy)", ThoList.flatmap family [1; -1];
    "2nd_Generation_(incl._heavy)", ThoList.flatmap family [2; -2];
    "3rd_Generation_(incl._heavy)", ThoList.flatmap family [3; -3];
    "Gauge_Bosons", [Ga; Z; Wp; Wm; Gl; Xp; Xm; X0; Y0; ZH];
    "Higgs", [H; Eta];
    "Goldstone_Bosons", [Phip; Phim; Phi0] ]

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n =
  if n ≥ 0 then
    Spinor
  else
    ConjSpinor

let lorentz = function
  | L n → spinor n | N n → spinor n
  | U n → spinor n | D n → spinor n
  | QH n → spinor n | NH n → spinor n
  | Ga | Gl → Vector

```



```

| Wp | Wm | Z | Xp | Xm | X0 | Y0 | ZH → Massive_Vector
| _ → Scalar

let color = function
| U n → Color.SUN (if n > 0 then 3 else -3)
| D n → Color.SUN (if n > 0 then 3 else -3)
| QH n → Color.SUN (if n > 0 then 3 else -3)
| Gl → Color.AdjSUN 3
| _ → Color.Singlet

let prop_spinor n =
if n ≥ 0 then
Prop_Spinor
else
Prop_ConjSpinor

let propagator = function
| L n → prop_spinor n | N n → prop_spinor n
| U n → prop_spinor n | D n → prop_spinor n
| QH n → prop_spinor n | NH n → prop_spinor n
| Ga | Gl → Prop_Feynman
| Wp | Wm | Z | Xp | Xm | X0 | Y0 | ZH → Prop_Unitarity
| Phip | Phim | Phi0 → Only_Insertion
| H | Eta → Prop_Scalar

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
if !use_fudged_width then
match f with
| Wp | Wm | U 3 | U (-3) | QH _ | NH _ → Fudged
| _ → !default_width
else
!default_width

let goldstone = function
| Wp → Some (Phip, Coupling.Const 1)
| Wm → Some (Phim, Coupling.Const 1)
| Z → Some (Phi0, Coupling.Const 1)
| _ → None

let conjugate = function
| L n → L (-n) | N n → N (-n)
| U n → U (-n) | D n → D (-n)
| QH n → QH (-n) | NH n → NH (-n)
| Ga → Ga | Gl → Gl | Z → Z
| Wp → Wm | Wm → Wp
| Xp → Xm | Xm → Xp | X0 → X0 | Y0 → Y0 | ZH → ZH
| Phip → Phim | Phim → Phip | Phi0 → Phi0
| H → H | Eta → Eta

let fermion = function
| L n → if n > 0 then 1 else -1

```

```

|  $N\ n \rightarrow \text{if } n > 0 \text{ then } 1 \text{ else } -1$ 
|  $U\ n \rightarrow \text{if } n > 0 \text{ then } 1 \text{ else } -1$ 
|  $D\ n \rightarrow \text{if } n > 0 \text{ then } 1 \text{ else } -1$ 
|  $QH\ n \rightarrow \text{if } n > 0 \text{ then } 1 \text{ else } -1$ 
|  $NH\ n \rightarrow \text{if } n > 0 \text{ then } 1 \text{ else } -1$ 
|  $Ga\ |\ Gl\ |\ Z\ |\ Wp\ |\ Wm\ |\ Xp\ |\ Xm\ |\ X0\ |\ Y0\ |\ ZH \rightarrow 0$ 
|  $- \rightarrow 0$ 

module Ch = Charges.QQ
let ( // ) = Algebra.Small_Rational.make

let charge = function
|  $L\ n \rightarrow \text{if } n > 0 \text{ then } -1//1 \text{ else } 1//1$ 
|  $N\ n\ |\ NH\ n \rightarrow 0//1$ 
|  $U\ n \rightarrow \text{if } n > 0 \text{ then } 2//3 \text{ else } -2//3$ 
|  $QH\ 3 \rightarrow 2//3\ |\ QH\ (-3) \rightarrow -2//3$ 
|  $QH\ (1\ |\ 2) \rightarrow$ 
|   if Flags.anom_ferm_ass then
|     2//3
|   else
|     -1//3
|  $QH\ ((-1)\ |\ (-2)) \rightarrow$ 
|   if Flags.anom_ferm_ass then
|     -2//3
|   else
|     1//3
|  $QH\ n \rightarrow \text{invalid\_arg } ("Simplest.charge:\_\square QH\_\square" ^ \text{string\_of\_int } n)$ 
|  $D\ n \rightarrow \text{if } n > 0 \text{ then } -1//3 \text{ else } 1//3$ 
|  $Gl\ |\ Ga\ |\ Z\ |\ ZH\ |\ X0\ |\ Y0 \rightarrow 0//1$ 
|  $Wp\ |\ Xp \rightarrow 1//1$ 
|  $Wm\ |\ Xm \rightarrow -1//1$ 
|  $H\ |\ Phi0\ |\ Eta \rightarrow 0//1$ 
|  $Phip \rightarrow 1//1$ 
|  $Phim \rightarrow -1//1$ 

let lepton = function
|  $L\ n\ |\ N\ n\ |\ NH\ n$ 
|    $\rightarrow \text{if } n > 0 \text{ then } 1//1 \text{ else } -1//1$ 
|  $U\ -\ |\ D\ -\ |\ - \rightarrow 0//1$ 

let baryon = function
|  $L\ -\ |\ N\ - \rightarrow 0//1$ 
|  $U\ n\ |\ D\ n\ |\ QH\ n$ 
|    $\rightarrow \text{if } n > 0 \text{ then } 1//1 \text{ else } -1//1$ 
|  $- \rightarrow 0//1$ 

let charges f =
[ charge f; lepton f; baryon f ]

type constant =
| Unit | Pi | Alpha_QED | Sin2thw
| Sinthw | Costhw | E | G_weak | Vev | VHeavy
| Supp | Supp2

```

```

| Sinpsi | Cospsi | Atpsi | Scs (* Mixing angles of SU(2) *)
| Q_lepton | Q_up | Q_down | Q_Z_up | G_CC | I_G_CC
| G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down
| G_NC_X | G_NC_X_t | G_NC_Y | G_NC_Y_t | G_NC_H
| G_NC_h_neutrino | G_NC_h_lepton | G_NC_h_up | G_NC_h_down
| G_NC_h_top | G_NC_h_bot | G_NCH_N | G_NCH_U |
G_NCH_D | G_NCHt
| G_zhthth
| I_Q_W | I_G_ZWW | I_G_WWW
| I_G_Z1 | I_G_Z2 | I_G_Z3 | I_G_Z4 | I_G_Z5 | I_G_Z6
| I_Q_H | G_s | I_G_s | G2
| G_WWW | G_ZZWW | G_AZWW | G_AAWW
| I_Q_ZH
| G_HWW | G_HHWW | G_HZZ | G_HHZZ | G_HHZZH
| G_heavy_HVV | G_heavy_HWW | G_heavy_HZZ | G_HHthth
| G_Htt | G_Hbb | G_Hcc | G_Htautau | G_H3 | G_H4
| G_Hthth | G_Htht | G_Ethth | G_Etht | G_Ett | G_Hqh
| G_Ebb | G_ZEH | G_ZHEH | G_Hgg
| G_HGaGa | G_HGaZ | G_EGaGa | G_EGaZ | G_EGIGl
| Mass of flavor | Width of flavor

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int

let orders = function
| - → (0,0)

```



The current abstract syntax for parameter dependencies is admittedly tedious. Later, there will be a parser for a convenient concrete syntax as a part of a concrete syntax for models. But as these examples show, it should include simple functions.

```

let input_parameters =
[]

let derived_parameters =
[]

let derived_parameter_arrays =
[]

let parameters () =
{ input = input_parameters;
  derived = derived_parameters;
  derived_arrays = derived_parameter_arrays }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate

```

```

end)

let electromagnetic_currents n =
  [ ((L (-n), Ga, L n), FBF (1, Psibar, V, Psi), Q_lepton);
    ((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q_up);
    ((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q_down) ]

let color_currents n =
  [ ((D (-n), Gl, D n), FBF ((-1), Psibar, V, Psi), Gs);
    ((U (-n), Gl, U n), FBF ((-1), Psibar, V, Psi), Gs);
    ((QH (-n), Gl, QH n), FBF ((-1), Psibar, V, Psi), Gs) ]

let neutral_currents n =
  [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
    ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
    ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
    ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]

let xy_currents =
  ThoList.flatmap
    (fun n → [ ((N (-n), X0, N n), FBF ((-1), Psibar, VL, Psi), G_NC_X);
                ((L (-n), Xm, N n), FBF ((-1), Psibar, VL, Psi), G_NC_X);
                ((N (-n), Xp, L n), FBF ((-1), Psibar, VL, Psi), G_NC_X);
                ((N (-n), Y0, N n), FBF ((-1), Psibar, VL, Psi), G_NC_Y);
                ((NH (-n), X0, N n), FBF ((-1), Psibar, VL, Psi), G_CC);
                ((N (-n), X0, NH n), FBF ((-1), Psibar, VL, Psi), G_CC);
                ((NH (-n), Y0, N n), FBF ((-1), Psibar, VL, Psi), I_G_CC);
                ((N (-n), Y0, NH n), FBF ((-1), Psibar, VL, Psi), I_G_CC);
                ((L (-n), Xm, NH n), FBF ((-1), Psibar, VL, Psi), G_CC);
                ((NH (-n), Xp, L n), FBF ((-1), Psibar, VL, Psi), G_CC)]

  [1; 2; 3]

  @
  [ ((U (-3), X0, U 3), FBF (1, Psibar, VL, Psi), G_NC_X_t);
    ((U (-3), Y0, U 3), FBF (1, Psibar, VL, Psi), G_NC_Y_t);
    ((U (-3), X0, QH 3), FBF (1, Psibar, VL, Psi), G_CC);
    ((QH (-3), X0, U 3), FBF (1, Psibar, VL, Psi), G_CC);
    ((U (-3), Y0, QH 3), FBF (1, Psibar, VL, Psi), I_G_CC);
    ((QH (-3), Y0, U 3), FBF (1, Psibar, VL, Psi), I_G_CC);
    ((D (-3), Xm, U 3), FBF (1, Psibar, VL, Psi), G_NC_X_t);
    ((U (-3), Xp, D 3), FBF (1, Psibar, VL, Psi), G_NC_X_t);
    ((D (-3), Xm, QH 3), FBF (1, Psibar, VL, Psi), G_CC);
    ((QH (-3), Xp, D 3), FBF (1, Psibar, VL, Psi), G_CC);
    ((QH (-3), Wp, D 3), FBF (1, Psibar, VL, Psi), G_NC_X_t);
    ((D (-3), Wm, QH 3), FBF (1, Psibar, VL, Psi), G_NC_X_t);
    ((QH (-3), Z, U 3), FBF (1, Psibar, VL, Psi), G_NCHt);
    ((U (-3), Z, QH 3), FBF (1, Psibar, VL, Psi), G_NCHt) ]

  @
  ThoList.flatmap
    (fun n →
      if Flags.anom_ferm_ass then
        [ ((U (-n), X0, U n), FBF ((-1), Psibar, VL, Psi), G_NC_X);
          ((U (-n), Y0, U n), FBF ((-1), Psibar, VL, Psi), G_NC_Y);
        ]
      else
        []
    )

```

```

((D (-n), Xm, U n), FBF ((-1), Psibar, VL, Psi), G_NC_X);
((U (-n), Xp, D n), FBF ((-1), Psibar, VL, Psi), G_NC_X);
((QH (-n), X0, U n), FBF ((-1), Psibar, VL, Psi), G_CC);
((U (-n), X0, QH n), FBF ((-1), Psibar, VL, Psi), G_CC);
((QH (-n), Y0, U n), FBF ((-1), Psibar, VL, Psi), I_G_CC);
((U (-n), Y0, QH n), FBF ((-1), Psibar, VL, Psi), I_G_CC);
((D (-n), Xm, QH n), FBF ((-1), Psibar, VL, Psi), G_CC);
((QH (-n), Xp, D n), FBF ((-1), Psibar, VL, Psi), G_CC);
((QH (-n), Wp, D n), FBF ((-1), Psibar, VL, Psi), G_NC_X);
((D (-n), Wm, QH n), FBF ((-1), Psibar, VL, Psi), G_NC_X);
((QH (-n), Z, U n), FBF (1, Psibar, VL, Psi), G_NC_H);
((U (-n), Z, QH n), FBF (1, Psibar, VL, Psi), G_NC_H)]
else
[ ((D (-n), X0, D n), FBF (1, Psibar, VL, Psi), G_NC_X);
  ((D (-n), Y0, D n), FBF (1, Psibar, VL, Psi), G_NC_Y);
  ((D (-n), Xm, U n), FBF (1, Psibar, VL, Psi), G_NC_X);
  ((U (-n), Xp, D n), FBF (1, Psibar, VL, Psi), G_NC_X);
  ((QH (-n), X0, D n), FBF ((-1), Psibar, VL, Psi), G_CC);
  ((D (-n), X0, QH n), FBF ((-1), Psibar, VL, Psi), G_CC);
  ((QH (-n), Y0, D n), FBF ((-1), Psibar, VL, Psi), I_G_CC);
  ((D (-n), Y0, QH n), FBF ((-1), Psibar, VL, Psi), I_G_CC);
  ((QH (-n), Xm, U n), FBF (1, Psibar, VL, Psi), G_CC);
  ((U (-n), Xp, QH n), FBF (1, Psibar, VL, Psi), G_CC);
  ((QH (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_NC_X);
  ((U (-n), Wp, QH n), FBF (1, Psibar, VL, Psi), G_NC_X);
  ((QH (-n), Z, D n), FBF (1, Psibar, VL, Psi), G_NC_H);
  ((D (-n), Z, QH n), FBF (1, Psibar, VL, Psi), G_NC_H))]
[1; 2]

```

The sign of this coupling is just the one of the T3, being $-(1/2)$ for leptons and down quarks, and $+(1/2)$ for neutrinos and up quarks.

```

let neutral_heavy_currents n =
[ ((L (-n), ZH, L n), FBF (1, Psibar, VLR, Psi), G_NC_h_lepton);
  ((N (-n), ZH, N n), FBF ((-1), Psibar, VLR, Psi), G_NC_h_neutrino);
  ((U (-n), ZH, U n), FBF ((-1), Psibar, VLR, Psi), (if n = 3 then
    G_NC_h_top else G_NC_h_up));
  ((D (-n), ZH, D n), FBF (1, Psibar, VLR, Psi), (if n = 3 then
    G_NC_h_bot else G_NC_h_down));
  ((NH (-n), ZH, NH n), FBF (1, Psibar, VLR, Psi), G_NCH_N);
  ((QH (-n), ZH, QH n), FBF (1, Psibar, VLR, Psi), (if n = 3 then
    G_NCH_U else if Flags.anom_ferm_ass then G_NCH_U else G_NCH_D))]

let heavy_currents n =
[ ((QH (-n), Ga, QH n), FBF (1, Psibar, V, Psi), (if n = 3 then Q_up else
  if Flags.anom_ferm_ass then Q_up else Q_down))]

let charged_currents n =
[ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G_CC);
  ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G_CC);
  ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_CC);
  ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G_CC) ]

```

```

let yukawa =
  [ ((U (-3), H, U 3), FBF (1, Psibar, S, Psi), G_Htt);
    ((D (-3), H, D 3), FBF (1, Psibar, S, Psi), G_Hbb);
    ((U (-2), H, U 2), FBF (1, Psibar, S, Psi), G_Hcc);
    ((L (-3), H, L 3), FBF (1, Psibar, S, Psi), G_Htautau) ]

let yukawa_add =
  [ ((QH (-3), H, U 3), FBF (1, Psibar, SL, Psi), G_Htht);
    ((U (-3), H, QH 3), FBF (1, Psibar, SR, Psi), G_Htht);
    ((QH (-3), Eta, U 3), FBF (1, Psibar, SR, Psi), G_Etht);
    ((U (-3), Eta, QH 3), FBF (1, Psibar, SL, Psi), G_Etht);
    ((D (-3), Eta, D 3), FBF (1, Psibar, P, Psi), G_Ebb);
    ((U (-3), Eta, U 3), FBF (1, Psibar, P, Psi), G_Ett)]
  @
  ThoList.flatmap
    (fun n →
      if Flags.anom_ferm_ass then
        [ ((QH (-n), H, U n), FBF (1, Psibar, SL, Psi), G_Hqhq);
          ((U (-n), H, QH n), FBF (1, Psibar, SR, Psi), G_Hqhq)]
        else
        [ ((QH (-n), H, D n), FBF (1, Psibar, SL, Psi), G_Hqhq);
          ((D (-n), H, QH n), FBF (1, Psibar, SR, Psi), G_Hqhq)]
        [1; 2])

let standard_triple_gauge =
  [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
    ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW);
    ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_Gs)]

let heavy_triple_gauge =
  [ ((Ga, Xm, Xp), Gauge_Gauge_Gauge 1, I_Q_W);
    ((Z, Xm, Xp), Gauge_Gauge_Gauge 1, I_Q_ZH);
    ((Z, X0, Y0), Gauge_Gauge_Gauge 1, I_G_Z1);
    ((ZH, X0, Y0), Gauge_Gauge_Gauge 1, I_G_Z2);
    ((Y0, Wm, Xp), Gauge_Gauge_Gauge 1, I_G_Z3);
    ((Y0, Wp, Xm), Gauge_Gauge_Gauge (-1), I_G_Z3);
    ((X0, Wm, Xp), Gauge_Gauge_Gauge 1, I_G_Z4);
    ((X0, Wp, Xm), Gauge_Gauge_Gauge 1, I_G_Z4);
    ((ZH, Xm, Xp), Gauge_Gauge_Gauge 1, I_G_Z5);
    ((ZH, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_Z6)]

let triple_gauge =
  standard_triple_gauge @ heavy_triple_gauge

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let standard_quartic_gauge =
  [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
    (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
    (Wm, Z, Wp, Ga), minus_gauge4, G_AZWW;
    (Wm, Ga, Wp, Ga), minus_gauge4, G_AAWW;
    (Gl, Gl, Gl, Gl), gauge4, G2]

```

```

let heavy_quartic_gauge =
  []

let quartic_gauge =
  standard_quartic_gauge @ heavy_quartic_gauge

let standard_gauge_higgs' =
  [ ((H, Wp, Wm), Scalar_Vector_Vector 1, G_HWW);
    ((H, Z, Z), Scalar_Vector_Vector 1, G_HZZ) ]

let heavy_gauge_higgs =
  [ ((H, Wp, Xm), Scalar_Vector_Vector 1, G_heavy_HWW);
    ((H, Wm, Xp), Scalar_Vector_Vector 1, G_heavy_HWW);
    ((H, Z, X0), Scalar_Vector_Vector 1, G_heavy_HVV);
    ((H, ZH, X0), Scalar_Vector_Vector 1, G_heavy_HVV) ]

let standard_gauge_higgs =
  standard_gauge_higgs' @ heavy_gauge_higgs

let standard_gauge_higgs4 =
  [ (H, H, Wp, Wm), Scalar2_Vector2 1, G_HHWW;
    (H, H, Z, Z), Scalar2_Vector2 1, G_HHZZ ]

let heavy_gauge_higgs4 =
  [ (H, H, Z, ZH), Scalar2_Vector2 1, G_HHZZH;
    (H, H, Xp, Xm), Scalar2_Vector2 (-1), G_HHWW;
    (H, H, ZH, ZH), Scalar2_Vector2 (-1), G_HHZZ ]

let standard_higgs =
  [ (H, H, H), Scalar_Scalar_Scalar 1, G_H3 ]

let anomaly_higgs =
  [ (Eta, Gl, Gl), Dim5_Scalar_Gauge2_Skew 1, G_EGIGl;
    (Eta, Ga, Ga), Dim5_Scalar_Gauge2_Skew 1, G_EGaGa;
    (Eta, Ga, Z), Dim5_Scalar_Gauge2_Skew 1, G_EGaZ ]
(* @ (H, Ga, Ga), Dim5_Scalar_Gauge2 1, G_HGaGa; (H, Ga, Z), Dim5_Scalar_Gauge2 1, G_HGaZ
*)

let standard_higgs4 =
  [ (H, H, H, H), Scalar4 1, G_H4 ]

let gauge_higgs =
  standard_gauge_higgs

let gauge_higgs4 =
  standard_gauge_higgs4 @ heavy_gauge_higgs4

let higgs =
  standard_higgs

let eta_higgs_gauge =
  [ (Z, Eta, H), Vector_Scalar_Scalar 1, G_ZEH;
    (ZH, Eta, H), Vector_Scalar_Scalar 1, G_ZHEH;
    (X0, Eta, H), Vector_Scalar_Scalar 1, G_CC ]

let top_quartic =
  [ ((QH (-3), H, H, QH 3), GBBG (1, Psibar, S2, Psi), G_HHthth) ]

```

```

let higgs4 =
  standard_higgs4

let goldstone_vertices =
  [ ((Phi0, Wm, Wp), Scalar_Vector_Vector 1, I-G-ZWW);
    ((Phip, Ga, Wm), Scalar_Vector_Vector 1, I-Q-W);
    ((Phip, Z, Wm), Scalar_Vector_Vector 1, I-G-ZWW);
    ((Phim, Wp, Ga), Scalar_Vector_Vector 1, I-Q-W);
    ((Phim, Wp, Z), Scalar_Vector_Vector 1, I-G-ZWW) ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1;2;3] @
   ThoList.flatmap color_currents [1;2;3] @
   ThoList.flatmap neutral_currents [1;2;3] @
   ThoList.flatmap neutral_heavy_currents [1;2;3] @
   ThoList.flatmap heavy_currents [1;2;3] @
   ThoList.flatmap charged_currents [1;2;3] @
   xy_currents @ anomaly_higgs @
   eta_higgs_gauge @
   yukawa @ yukawa_add @
   triple_gauge @
   gauge_higgs @ higgs @ goldstone_vertices)

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4

let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → L 1 | "e+" → L (-1)
| "mu-" → L 2 | "mu+" → L (-2)
| "tau-" → L 3 | "tau+" → L (-3)
| "nue" → N 1 | "nuebar" → N (-1)
| "numu" → N 2 | "numubar" → N (-2)
| "nuta" → N 3 | "nutaubar" → N (-3)
| "nh1" → NH 1 | "nh1bar" → NH (-1)
| "nh2" → NH 2 | "nh2bar" → NH (-2)
| "nh3" → NH 3 | "nh3bar" → NH (-3)
| "u" → U 1 | "ubar" → U (-1)
| "c" → U 2 | "cbar" → U (-2)
| "t" → U 3 | "tbar" → U (-3)
| "d" → D 1 | "dbar" → D (-1)
| "s" → D 2 | "sbar" → D (-2)
| "b" → D 3 | "bbar" → D (-3)
| "uh" → if Flags.anom_ferm_ass then QH 1 else invalid_arg
          "Modellib-BSM.Simplest.flavor_of_string"

```



```

| "dh" → if Flags.anom_ferm_ass then invalid_arg
|   "Modellib_BSM.Simplest.flavor_of_string" else QH 1
| "uhbar" → if Flags.anom_ferm_ass then QH (-1) else invalid_arg
|   "Modellib_BSM.Simplest.flavor_of_string"
| "dhbar" → if Flags.anom_ferm_ass then invalid_arg
|   "Modellib_BSM.Simplest.flavor_of_string" else QH (-1)
| "ch" → if Flags.anom_ferm_ass then QH 2 else invalid_arg
|   "Modellib_BSM.Simplest.flavor_of_string"
| "sh" → if Flags.anom_ferm_ass then invalid_arg
|   "Modellib_BSM.Simplest.flavor_of_string" else QH 2
| "chbar" → if Flags.anom_ferm_ass then QH (-2) else invalid_arg
|   "Modellib_BSM.Simplest.flavor_of_string"
| "shbar" → if Flags.anom_ferm_ass then invalid_arg
|   "Modellib_BSM.Simplest.flavor_of_string" else QH (-2)
| "th" → QH 3 | "thbar" → QH (-3)
| "eta" | "Eta" → Eta
| "A" → Ga | "Z" | "Z0" → Z | "g" | "g1" → Gl
| "ZH" | "ZH0" | "Zh" | "Zh0" → ZH
| "W+" → Wp | "W-" → Wm
| "X+" → Xp | "X-" → Xm
| "X0" → X0 | "Y0" → Y0
| "H" → H
| _ → invalid_arg "Modellib_BSM.Simplest.flavor_of_string"

let flavor_to_string = function
| L 1 → "e-" | L (-1) → "e+"
| L 2 → "mu-" | L (-2) → "mu+"
| L 3 → "tau-" | L (-3) → "tau+"
| L _ → invalid_arg
|   "Modellib_BSM.Simplest.flavor_to_string:␣invalid␣lepton"
| N 1 → "nue" | N (-1) → "nuebar"
| N 2 → "numu" | N (-2) → "numubar"
| N 3 → "nutau" | N (-3) → "nutaubar"
| N _ → invalid_arg
|   "Modellib_BSM.Simplest.flavor_to_string:␣invalid␣neutrino"
| U 1 → "u" | U (-1) → "ubar"
| U 2 → "c" | U (-2) → "cbar"
| U 3 → "t" | U (-3) → "tbar"
| U _ → invalid_arg
|   "Modellib_BSM.Simplest.flavor_to_string:␣invalid␣up␣type␣quark"
| D 1 → "d" | D (-1) → "dbar"
| D 2 → "s" | D (-2) → "sbar"
| D 3 → "b" | D (-3) → "bbar"
| D _ → invalid_arg
|   "Modellib_BSM.Simplest.flavor_to_string:␣invalid␣down␣type␣quark"
| QH 1 → if Flags.anom_ferm_ass then "uh" else "dh"
| QH 2 → if Flags.anom_ferm_ass then "ch" else "sh"
| QH 3 → "th"
| QH (-1) → if Flags.anom_ferm_ass then "uhbar" else "dhbar"
| QH (-2) → if Flags.anom_ferm_ass then "chbar" else "shbar"

```

```

| QH (-3) → "thbar"
| QH _ → invalid_arg
| "Modellib_BSM.Simplest.flavor_to_string:␣invalid␣heavy␣quark"
| NH n when n > 0 → "nh" ^ string_of_int n
| NH n → "nh" ^ string_of_int (abs n) ^ "bar"
| Ga → "A" | Z → "Z" | Gl → "g1"
| Wp → "W+" | Wm → "W-"
| Xp → "X+" | Xm → "X-" | X0 → "X0" | Y0 → "Y0" | ZH →
"ZH"
| Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
| H → "H" | Eta → "Eta"

let flavor_to_TeX = function
| L 1 → "e^-" | L (-1) → "\\e^+"
| L 2 → "\\mu^-" | L (-2) → "\\mu^+"
| L 3 → "\\tau^-" | L (-3) → "\\tau^+"
| L _ → invalid_arg
| "Modellib_BSM.Simplest.flavor_to_TeX:␣invalid␣lepton"
| N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
| N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
| N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
| N _ → invalid_arg
| "Modellib_BSM.Simplest.flavor_to_TeX:␣invalid␣neutrino"
| U 1 → "u" | U (-1) → "\\bar{u}"
| U 2 → "c" | U (-2) → "\\bar{c}"
| U 3 → "t" | U (-3) → "\\bar{t}"
| U _ → invalid_arg
| "Modellib_BSM.Simplest.flavor_to_TeX:␣invalid␣up␣type␣quark"
| D 1 → "d" | D (-1) → "\\bar{d}"
| D 2 → "s" | D (-2) → "\\bar{s}"
| D 3 → "b" | D (-3) → "\\bar{b}"
| D _ → invalid_arg
| "Modellib_BSM.Simplest.flavor_to_TeX:␣invalid␣down␣type␣quark"
| QH 1 → if Flags.anom_ferm_ass then "U" else "D"
| QH 2 → if Flags.anom_ferm_ass then "C" else "S"
| QH 3 → "T"
| QH (-1) → if Flags.anom_ferm_ass then "\\bar{U}" else "\\bar{D}"
| QH (-2) → if Flags.anom_ferm_ass then "\\bar{C}" else "\\bar{S}"
| QH (-3) → "thbar"
| QH _ → invalid_arg
| "Modellib_BSM.Simplest.flavor_to_TeX:␣invalid␣heavy␣quark"
| NH n when n > 0 → "N_" ^ string_of_int n
| NH n → "\\bar{N}_-" ^ string_of_int (abs n)
| Ga → "\\gamma" | Z → "Z" | Gl → "g"
| Wp → "W^+" | Wm → "W^-"
| Xp → "X^+" | Xm → "X^-" | X0 → "X^0" | Y0 → "Y^0" |
ZH → "Z_H"
| Phip → "\\phi^+" | Phim → "\\phi^-" | Phi0 → "\\phi^0"
| H → "H" | Eta → "\\eta"

let flavor_symbol = function

```

```

| L n when n > 0 → "l" ^ string_of_int n
| L n → "l" ^ string_of_int (abs n) ^ "b"
| N n when n > 0 → "n" ^ string_of_int n
| N n → "n" ^ string_of_int (abs n) ^ "b"
| U n when n > 0 → "u" ^ string_of_int n
| U n → "u" ^ string_of_int (abs n) ^ "b"
| D n when n > 0 → "d" ^ string_of_int n
| D n → "d" ^ string_of_int (abs n) ^ "b"
| NH n when n > 0 → "nh" ^ string_of_int n
| NH n → "nh" ^ string_of_int (abs n) ^ "b"
| QH n when n > 0 → "qh" ^ string_of_int n
| QH n → "qh" ^ string_of_int (abs n) ^ "b"
| Ga → "a" | Z → "z" | Gl → "g1"
| Wp → "wp" | Wm → "wm"
| Xp → "xp" | Xm → "xm" | X0 → "x0" | Y0 → "y0" | ZH →
"zh"
| Phip → "pp" | Phim → "pm" | Phi0 → "p0"
| H → "h" | Eta → "eta"

```

There are PDG numbers for Z' , Z'' , W' , 32-34, respectively. We just introduce a number 38 for $Y0$ as a Z'' . As well, there is the number 8 for a t' . But we cheat a little bit and take the number 35 which is reserved for a heavy scalar Higgs for the Eta scalar.

We abuse notation for the heavy quarks and take the PDG code for their SUSY partners!!! (What about an update of the PDG numbering scheme?) Thereby we take only those for up-type (s)quarks. The heavy neutrinos get the numbers of the sneutrinos.

```

let pdg = function
| L n when n > 0 → 9 + 2 × n
| L n → - 9 + 2 × n
| N n when n > 0 → 10 + 2 × n
| N n → - 10 + 2 × n
| U n when n > 0 → 2 × n
| U n → 2 × n
| D n when n > 0 → - 1 + 2 × n
| D n → 1 + 2 × n
| NH n when n > 0 → 1000010 + 2 × n
| NH n → - 1000010 + 2 × n
| QH 3 → 1000006
| QH (-3) → - 1000006
| QH n when n > 0 → if Flags.anom_ferm_ass then
1000000 + 2 × n else 999999 + 2 × n
| QH n → if Flags.anom_ferm_ass then
- 1000000 + 2 × n else - 999999 + 2 × n
| Gl → 21
| Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| Xp → 34 | Xm → (-34) | ZH → 32 | X0 → 33 | Y0 → 38
| Phip | Phim → 27 | Phi0 → 26
| H → 25 | Eta → 36

```

As in the case of SUSY we introduce an internal dummy pdf code in order to have manageable arrays. Heavy neutrinos get numbers 41,43,45, while the heavy quarks have the numbers 40,42,44. I take them all as up type here.

```

let pdg-mw = function
| L n when n > 0 → 9 + 2 × n
| L n → - 9 + 2 × n
| N n when n > 0 → 10 + 2 × n
| N n → - 10 + 2 × n
| U n when n > 0 → 2 × n
| U n → 2 × n
| D n when n > 0 → - 1 + 2 × n
| D n → 1 + 2 × n
| NH n when n > 0 → 39 + 2 × n
| NH n → - 39 + 2 × n
| QH n when n > 0 → 38 + 2 × n
| QH n → - 38 + 2 × n
| Gl → 21
| Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| Xp → 34 | Xm → (-34) | ZH → 32 | X0 → 33 | Y0 → 38
| Phip | Phim → 27 | Phi0 → 26
| H → 25 | Eta → 36

let mass-symbol f =
"mass(" ^ string-of-int (abs (pdg-mw f)) ^ ")"

let width-symbol f =
"width(" ^ string-of-int (abs (pdg-mw f)) ^ ")"

let constant-symbol = function
| Unit → "unit" | Pi → "PI" | VHeavy → "vheavy"
| Alpha-QED → "alpha" | E → "e" | G-weak → "g" | Vev →
"vev"
| Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
| Sinpsi → "sinpsi" | Cospsi → "cospsi"
| Atpsi → "atpsi" | Sccs → "sccs"
| Supp → "vF" | Supp2 → "v2F2"
| Q-lepton → "qllep" | Q-up → "qup" | Q-down → "qdwn"
| Q-Z-up → "qzup"
| G-zhthth → "gzhthth"
| G-NC-lepton → "gnclep" | G-NC-neutrino → "gncneu"
| G-NC-up → "gncup" | G-NC-down → "gncdwn"
| G-NC-X → "gncx" | G-NC-X-t → "gncxt"
| G-NC-Y → "gncy" | G-NC-Y-t → "gncyt" | G-NC-H →
"gnch"
| G-CC → "gcc" | I-G-CC → "i_gcc"
| G-NC-h-lepton → "gnchlep" | G-NC-h-neutrino → "gnchneu"
| G-NC-h-up → "gnchup" | G-NC-h-down → "gnchdwn"
| G-NC-h-top → "gnchtop" | G-NC-h-bot → "gnchbot"

```

```

|  $G_{NCH-N} \rightarrow$  "gnchn" |  $G_{NCH-U} \rightarrow$  "gnchu" |  $G_{NCH-D} \rightarrow$ 
"gnchd"
|  $G_{NCHt} \rightarrow$  "gncht"
|  $I_{Q-W} \rightarrow$  "iqw" |  $I_{G-ZWW} \rightarrow$  "igzww" |  $I_{G-WWW} \rightarrow$ 
"igwww"
|  $I_{Q-H} \rightarrow$  "iqh" |  $I_{Q-ZH} \rightarrow$  "iqzh"
|  $I_{G-Z1} \rightarrow$  "igz1" |  $I_{G-Z2} \rightarrow$  "igz2" |  $I_{G-Z3} \rightarrow$  "igz3"
|  $I_{G-Z4} \rightarrow$  "igz4" |  $I_{G-Z5} \rightarrow$  "igz5" |  $I_{G-Z6} \rightarrow$  "igz6"
|  $G_{HHthth} \rightarrow$  "ghhthth"
|  $G_{WWWW} \rightarrow$  "gw4" |  $G_{ZZWW} \rightarrow$  "gzzww"
|  $G_{AZWW} \rightarrow$  "gazww" |  $G_{AAWW} \rightarrow$  "gaaww"
|  $G_{HWW} \rightarrow$  "ghww" |  $G_{HZZ} \rightarrow$  "ghzz"
|  $G_{heavy-HVV} \rightarrow$  "ghyhvv"
|  $G_{heavy-HWW} \rightarrow$  "ghyhww"
|  $G_{heavy-HZZ} \rightarrow$  "ghyhzz"
|  $G_{HHWW} \rightarrow$  "ghhww" |  $G_{HHZZ} \rightarrow$  "ghhzz"
|  $G_{HHZZH} \rightarrow$  "ghhzzh"
|  $G_{Hgg} \rightarrow$  "ghgg"
|  $G_{Htt} \rightarrow$  "ghtt" |  $G_{Hbb} \rightarrow$  "ghbb"
|  $G_{Htautau} \rightarrow$  "ghtautau" |  $G_{Hcc} \rightarrow$  "ghcc"
|  $G_{Hthth} \rightarrow$  "ghthth" |  $G_{Htht} \rightarrow$  "ghtht"
|  $G_{Hqh} \rightarrow$  "ghqh"
|  $G_{Ethth} \rightarrow$  "gethth" |  $G_{Etht} \rightarrow$  "getht"
|  $G_{Ett} \rightarrow$  "gett" |  $G_{Ebb} \rightarrow$  "gebb"
|  $G_{HGaGa} \rightarrow$  "ghgaga" |  $G_{HGaZ} \rightarrow$  "ghgaz"
|  $G_{EGaGa} \rightarrow$  "geaa" |  $G_{EGaZ} \rightarrow$  "geaz" |  $G_{EGlGl} \rightarrow$  "gegg"
|  $G_{ZEH} \rightarrow$  "gzeh" |  $G_{ZHEH} \rightarrow$  "gzheh"
|  $G_{H3} \rightarrow$  "gh3" |  $G_{H4} \rightarrow$  "gh4"
|  $Mass\ f \rightarrow$  "mass" ^ flavor_symbol f
|  $Width\ f \rightarrow$  "width" ^ flavor_symbol f
|  $G_s \rightarrow$  "gs" |  $I_{G_s} \rightarrow$  "igs" |  $G_2 \rightarrow$  "gs**2"
end

```

```

module Xdim (Flags : BSM_flags) =
struct
  let rcs = RCS.rename rcs_file "Modellib_BSM.Xdim"
    [ "SM_with_extradimensional_resonances" ]

  open Coupling

  let default_width = ref Timelike
  let use_fudged_width = ref false

  let options = Options.create
    [ "constant_width", Arg.Unit (fun () → default_width := Constant),
      "use_constant_width(also_in_t-channel)",
      "fudged_width", Arg.Set use_fudged_width,
      "use_fudge_factor_for_charge_particle_width",
      "custom_width", Arg.String (fun f → default_width := Custom f),
      "use_custom_width",
      "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
      "use_vanishing_width" ]

```

```

type matter_field = L of int | N of int | U of int | D of int
type gauge_boson = Ga | Wp | Wm | Z | Gl
type other = Phip | Phim | Phi0 | H | Grav
type flavor = M of matter_field | G of gauge_boson | O of other

let matter_field f = M f
let gauge_boson f = G f
let other f = O f

type field =
  | Matter of matter_field
  | Gauge of gauge_boson
  | Other of other

let field = function
  | M f → Matter f
  | G f → Gauge f
  | O f → Other f

type gauge = unit

let gauge_symbol () =
  failwith "Modellib_BSM.Xdim.gauge_symbol:␣internal␣error"

let family n = List.map matter_field [ L n; N n; U n; D n ]

let external_flavors () =
  [ "1st_Generation", ThoList.flatmap family [1; -1];
    "2nd_Generation", ThoList.flatmap family [2; -2];
    "3rd_Generation", ThoList.flatmap family [3; -3];
    "Gauge_Bosons", List.map gauge_boson [Ga; Z; Wp; Wm; Gl];
    "Higgs", List.map other [H];
    "Graviton", List.map other [Grav];
    "Goldstone_Bosons", List.map other [Phip; Phim; Phi0] ]

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n =
  if n ≥ 0 then
    Spinor
  else
    ConjSpinor

let lorentz = function
  | M f →
    begin match f with
    | L n → spinor n | N n → spinor n
    | U n → spinor n | D n → spinor n
    end
  | G f →
    begin match f with
    | Ga | Gl → Vector
    | Wp | Wm | Z → Massive_Vector
    end
  | O f →

```

```

    begin match f with
    | Grav → Tensor_2
    | _ → Scalar
    end

let color = function
| M (U n) → Color.SUN (if n > 0 then 3 else -3)
| M (D n) → Color.SUN (if n > 0 then 3 else -3)
| G Gl → Color.AdjSUN 3
| _ → Color.Singlet

let prop_spinor n =
  if n ≥ 0 then
    Prop_Spinor
  else
    Prop_ConjSpinor

let propagator = function
| M f →
  begin match f with
  | L n → prop_spinor n | N n → prop_spinor n
  | U n → prop_spinor n | D n → prop_spinor n
  end
| G f →
  begin match f with
  | Ga | Gl → Prop_Feynman
  | Wp | Wm | Z → Prop_Unitarity
  end
| O f →
  begin match f with
  | Phip | Phim | Phi0 → Only_Insertion
  | H → Prop_Scalar
  | Grav → Prop_Tensor_2
  end
end

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    | G Wp | G Wm | M (U 3) | M (U (-3)) | O Grav → Fudged
    | _ → !default_width
  else
    !default_width

let goldstone = function
| G f →
  begin match f with
  | Wp → Some (O Phip, Coupling.Const 1)
  | Wm → Some (O Phim, Coupling.Const 1)
  | Z → Some (O Phi0, Coupling.Const 1)
  | _ → None
end

```

```

    end
  | _ → None
let conjugate = function
  | M f →
    M (begin match f with
      | L n → L (-n) | N n → N (-n)
      | U n → U (-n) | D n → D (-n)
    end)
  | G f →
    G (begin match f with
      | Gl → Gl | Ga → Ga | Z → Z
      | Wp → Wm | Wm → Wp
    end)
  | O f →
    O (begin match f with
      | Phip → Phim | Phim → Phip | Phi0 → Phi0
      | H → H | Grav → Grav
    end)
let fermion = function
  | M f →
    begin match f with
      | L n → if n > 0 then 1 else -1
      | N n → if n > 0 then 1 else -1
      | U n → if n > 0 then 1 else -1
      | D n → if n > 0 then 1 else -1
    end
  | G f →
    begin match f with
      | Gl | Ga | Z | Wp | Wm → 0
    end
  | O _ → 0
module Ch = Charges.QQ
let ( / ) = Algebra.Small_Rational.make
let generation' = function
  | 1 → [ 1//1; 0//1; 0//1]
  | 2 → [ 0//1; 1//1; 0//1]
  | 3 → [ 0//1; 0//1; 1//1]
  | -1 → [-1//1; 0//1; 0//1]
  | -2 → [ 0//1; -1//1; 0//1]
  | -3 → [ 0//1; 0//1; -1//1]
  | n → invalid_arg ("Xdim.generation':␣" ^ string_of_int n)
let generation f =
  match f with
  | M (L n | N n | U n | D n) → generation' n
  | G _ | O _ → [0//1; 0//1; 0//1]
let charge = function
  | M f →

```



```

begin match f with
| L n → if n > 0 then -1//1 else 1//1
| N n → 0//1
| U n → if n > 0 then 2//3 else -2//3
| D n → if n > 0 then -1//3 else 1//3
end
| G f →
begin match f with
| Gl | Ga | Z → 0//1
| Wp → 1//1
| Wm → -1//1
end
| O f →
begin match f with
| H | Phi0 | Grav → 0//1
| Phip → 1//1
| Phim → -1//1
end
end

let lepton = function
| M f →
begin match f with
| L n | N n → if n > 0 then 1//1 else -1//1
| U - | D - → 0//1
end
| G - | O - → 0//1
end

let baryon = function
| M f →
begin match f with
| L - | N - → 0//1
| U n | D n → if n > 0 then 1//1 else -1//1
end
| G - | O - → 0//1
end

let charges f =
[ charge f; lepton f; baryon f] @ generation f

type constant =
| Unit | Pi | Alpha_QED | Sin2thw
| Sinthw | Costhw | E | G_weak | Vev
| Q_lepton | Q_up | Q_down | G_CC | G_CCQ of int×int
| G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down
| Gs | I_Gs | G2
| I_Q_W | I_G_ZWW
| G_WWWW | G_ZZWW | G_AZWW | G_AAWW
| G_HWW | G_HHWW | G_HZZ | G_HHZZ
| G_Htt | G_Hbb | G_Hcc | G_Htautau | G_H3 | G_H4
| G_HGaZ | G_HGaGa | G_Hgg | G_Grav
| Mass of flavor | Width of flavor

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int

let orders = function
  | - → (0,0)

let input_parameters =
  []

let derived_parameters =
  []

let derived_parameter_arrays =
  []

let parameters () =
  { input = input_parameters;
    derived = derived_parameters;
    derived_arrays = derived_parameter_arrays }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let mgm ((m1, g, m2), fbf, c) = ((M m1, G g, M m2), fbf, c)
let mom ((m1, o, m2), fbf, c) = ((M m1, O o, M m2), fbf, c)

let electromagnetic_currents n =
  List.map mgm
    [ ((L (-n), Ga, L n), FBF (1, Psibar, V, Psi), Q_lepton);
      ((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q_up);
      ((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q_down) ]

let neutral_currents n =
  List.map mgm
    [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
      ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
      ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
      ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]

let color_currents n =
  List.map mgm
    [ ((U (-n), Gl, U n), FBF ((-1), Psibar, V, Psi), Gs);
      ((D (-n), Gl, D n), FBF ((-1), Psibar, V, Psi), Gs) ]

let charged_currents n =
  List.map mgm
    [ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G_CC);
      ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G_CC);
      ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_CC);
      ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G_CC) ]

let gravity_currents n =
  List.map mom

```

```

[ ((L (-n), Grav, L n), Graviton_Spinor_Spinor 1, G_Grav);
  ((N (-n), Grav, N n), Graviton_Spinor_Spinor 1, G_Grav);
  ((U (-n), Grav, U n), Graviton_Spinor_Spinor 1, G_Grav);
  ((D (-n), Grav, D n), Graviton_Spinor_Spinor 1, G_Grav) ]

let yukawa =
  List.map mom
    [ ((U (-3), H, U 3), FBF (1, Psibar, S, Psi), G_Htt);
      ((D (-3), H, D 3), FBF (1, Psibar, S, Psi), G_Hbb);
      ((U (-2), H, U 2), FBF (1, Psibar, S, Psi), G_Hcc);
      ((L (-3), H, L 3), FBF (1, Psibar, S, Psi), G_Htautau) ]

let tgc ((g1, g2, g3), t, c) = ((G g1, G g2, G g3), t, c)

let standard_triple_gauge =
  List.map tgc
    [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
      ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW);
      ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_Gs) ]

let triple_gauge =
  standard_triple_gauge

let qgc ((g1, g2, g3, g4), t, c) = ((G g1, G g2, G g3, G g4), t, c)

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let standard_quartic_gauge =
  List.map qgc
    [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
      (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
      (Wm, Z, Wp, Ga), minus_gauge4, G_AZWW;
      (Wm, Ga, Wp, Ga), minus_gauge4, G_AAWW;
      (Gl, Gl, Gl, Gl), gauge4, G2]

let quartic_gauge =
  standard_quartic_gauge

let gravity_gauge =
  [ (O Grav, G Z, G Z), Graviton_Vector_Vector 1, G_Grav;
    (O Grav, G Wp, G Wm), Graviton_Vector_Vector 1, G_Grav;
    (O Grav, G Ga, G Ga), Graviton_Vector_Vector 1, G_Grav;
    (O Grav, G Gl, G Gl), Graviton_Vector_Vector 1, G_Grav ]

let standard_gauge_higgs =
  [ ((O H, G Wp, G Wm), Scalar_Vector_Vector 1, G_HWW);
    ((O H, G Z, G Z), Scalar_Vector_Vector 1, G_HZZ) ]

let standard_gauge_higgs4 =
  [ (O H, O H, G Wp, G Wm), Scalar2_Vector2 1, G_HHWW;
    (O H, O H, G Z, G Z), Scalar2_Vector2 1, G_HHZZ ]

let standard_higgs =
  [ (O H, O H, O H), Scalar_Scalar_Scalar 1, G_H3 ]

let standard_higgs4 =

```

```

[ (O H, O H, O H, O H), Scalar4 1, G-H4 ]

let gravity_higgs =
  [ (O Grav, O H, O H), Graviton_Scalar_Scalar 1, G-Grav]

let anomalous_gauge_higgs =
  []

let anomalous_gauge_higgs4 =
  []

let anomalous_higgs =
  []

let anomaly_higgs =
  [ (O H, G Ga, G Ga), Dim5_Scalar_Gauge2 1, G-HGaGa;
    (O H, G Ga, G Z), Dim5_Scalar_Gauge2 1, G-HGaZ;
    (O H, G Gl, G Gl), Dim5_Scalar_Gauge2 1, G-Hgg ]

let anomalous_higgs4 =
  []

let gauge_higgs =
  standard_gauge_higgs

let gauge_higgs4 =
  standard_gauge_higgs4

let higgs =
  standard_higgs @ gravity_higgs

let higgs4 =
  standard_higgs4

let goldstone_vertices =
  [ ((O Phi0, G Wm, G Wp), Scalar_Vector_Vector 1, I-G-ZWW);
    ((O Phip, G Ga, G Wm), Scalar_Vector_Vector 1, I-Q-W);
    ((O Phip, G Z, G Wm), Scalar_Vector_Vector 1, I-G-ZWW);
    ((O Phim, G Wp, G Ga), Scalar_Vector_Vector 1, I-Q-W);
    ((O Phim, G Wp, G Z), Scalar_Vector_Vector 1, I-G-ZWW) ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1; 2; 3] @
   ThoList.flatmap neutral_currents [1; 2; 3] @
   ThoList.flatmap color_currents [1; 2; 3] @
   ThoList.flatmap charged_currents [1; 2; 3] @
   ThoList.flatmap gravity_currents [1; 2; 3] @
   yukawa @ triple_gauge @ gravity_gauge @
   gauge_higgs @ higgs @ anomaly_higgs
   @ goldstone_vertices)

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4

let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))
| "numu" → M (N 2) | "numubar" → M (N (-2))
| "nutau" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "g" | "gl" → G Gl
| "A" → G Ga | "Z" | "Z0" → G Z
| "W+" → G Wp | "W-" → G Wm
| "H" → O H
| "GG" → O Grav
| _ → invalid_arg "Modellib_BSM.Xdim.flavor_of_string"

let flavor_to_string = function
| M f →
  begin match f with
  | L 1 → "e-" | L (-1) → "e+"
  | L 2 → "mu-" | L (-2) → "mu+"
  | L 3 → "tau-" | L (-3) → "tau+"
  | L _ → invalid_arg
    "Modellib_BSM.Xdim.flavor_to_string:␣invalid␣lepton"
  | N 1 → "nue" | N (-1) → "nuebar"
  | N 2 → "numu" | N (-2) → "numubar"
  | N 3 → "nutau" | N (-3) → "nutaubar"
  | N _ → invalid_arg
    "Modellib_BSM.Xdim.flavor_to_string:␣invalid␣neutrino"
  | U 1 → "u" | U (-1) → "ubar"
  | U 2 → "c" | U (-2) → "cbar"
  | U 3 → "t" | U (-3) → "tbar"
  | U _ → invalid_arg
    "Modellib_BSM.Xdim.flavor_to_string:␣invalid␣up␣type␣quark"
  | D 1 → "d" | D (-1) → "dbar"
  | D 2 → "s" | D (-2) → "sbar"
  | D 3 → "b" | D (-3) → "bbar"
  | D _ → invalid_arg
    "Modellib_BSM.Xdim.flavor_to_string:␣invalid␣down␣type␣quark"
  end
| G f →

```

```

begin match f with
| Gl → "g"
| Ga → "A" | Z → "Z"
| Wp → "W+" | Wm → "W-"
end
| Of →
begin match f with
| Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
| H → "H" | Grav → "GG"
end
end

let flavor_to_TeX = function
| Mf →
begin match f with
| L1 → "e^-" | L(-1) → "e^+"
| L2 → "\\mu^-" | L(-2) → "\\mu^+"
| L3 → "\\tau^-" | L(-3) → "\\tau^+"
| L_ → invalid_arg
"Modellib_BSM.Xdim.flavor_to_TeX:␣invalid␣lepton"
| N1 → "\\nu_e" | N(-1) → "\\bar{\\nu}_e"
| N2 → "\\nu_\\mu" | N(-2) → "\\bar{\\nu}_\\mu"
| N3 → "\\nu_\\tau" | N(-3) → "\\bar{\\nu}_\\tau"
| N_ → invalid_arg
"Modellib_BSM.Xdim.flavor_to_TeX:␣invalid␣neutrino"
| U1 → "u" | U(-1) → "\\bar{u}"
| U2 → "c" | U(-2) → "\\bar{c}"
| U3 → "t" | U(-3) → "\\bar{t}"
| U_ → invalid_arg
"Modellib_BSM.Xdim.flavor_to_TeX:␣invalid␣up␣type␣quark"
| D1 → "d" | D(-1) → "\\bar{d}"
| D2 → "s" | D(-2) → "\\bar{s}"
| D3 → "b" | D(-3) → "\\bar{b}"
| D_ → invalid_arg
"Modellib_BSM.Xdim.flavor_to_TeX:␣invalid␣down␣type␣quark"
end
| Gf →
begin match f with
| Gl → "g"
| Ga → "\\gamma" | Z → "Z"
| Wp → "W^+" | Wm → "W^-"
end
| Of →
begin match f with
| Phip → "\\phi^+" | Phim → "\\phi^-" | Phi0 →
"\\phi^0"
| H → "H" | Grav → "G"
end
end

let flavor_symbol = function
| Mf →
begin match f with

```

```

| L n when n > 0 → "l" ^ string_of_int n
| L n → "l" ^ string_of_int (abs n) ^ "b"
| N n when n > 0 → "n" ^ string_of_int n
| N n → "n" ^ string_of_int (abs n) ^ "b"
| U n when n > 0 → "u" ^ string_of_int n
| U n → "u" ^ string_of_int (abs n) ^ "b"
| D n when n > 0 → "d" ^ string_of_int n
| D n → "d" ^ string_of_int (abs n) ^ "b"
end
| G f →
  begin match f with
  | Gl → "gl"
  | Ga → "a" | Z → "z"
  | Wp → "wp" | Wm → "wm"
  end
| O f →
  begin match f with
  | Phip → "pp" | Phim → "pm" | Phi0 → "p0"
  | H → "h" | Grav → "gv"
  end
let pdg = function
| M f →
  begin match f with
  | L n when n > 0 → 9 + 2 × n
  | L n → - 9 + 2 × n
  | N n when n > 0 → 10 + 2 × n
  | N n → - 10 + 2 × n
  | U n when n > 0 → 2 × n
  | U n → 2 × n
  | D n when n > 0 → - 1 + 2 × n
  | D n → 1 + 2 × n
  end
| G f →
  begin match f with
  | Gl → 21
  | Ga → 22 | Z → 23
  | Wp → 24 | Wm → (-24)
  end
| O f →
  begin match f with
  | Phip | Phim → 27 | Phi0 → 26
  | H → 25 | Grav → 39
  end
let mass_symbol f =
  "mass(" ^ string_of_int (abs (pdg f)) ^ ")"
let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"
let constant_symbol = function

```

```

| Unit → "unit" | Pi → "PI"
| Alpha_QED → "alpha" | E → "e" | G_weak → "g" | Vev →
"vev"
| Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
| Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdown"
| G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
| G_NC_up → "gncup" | G_NC_down → "gncdown"
| Gs → "gs" | I_Gs → "igs" | G2 → "gs**2"
| G_CC → "gcc"
| G_CCQ (n1, n2) → "gccq" ^ string_of_int n1 ^ string_of_int n2
| I_Q_W → "iqw" | I_G_ZWW → "igzww"
| G_WWWW → "gw4" | G_ZZWW → "gzzww"
| G_AZWW → "gazww" | G_AA WW → "gaaww"
| G_HWW → "ghww" | G_HZZ → "ghzz"
| G_HHWW → "ghhww" | G_HHZZ → "ghhzz"
| G_Htt → "ghtt" | G_Hbb → "ghbb"
| G_Htautau → "ghtautau" | G_Hcc → "ghcc"
| G_HGaZ → "ghgaz" | G_HGaGa → "ghgaga" | G_Hgg →
"ghgg"
| G_H3 → "gh3" | G_H4 → "gh4" | G_Grav → "ggrav"
| Mass f → "mass" ^ flavor_symbol f
| Width f → "width" ^ flavor_symbol f

end

module UED (Flags : BSM_flags) =
struct
  let rcs = RCS.rename rcs_file "Modellib_BSM.UED"
    [ "Universal_Extra_Dimensions" ]

  open Coupling

  let default_width = ref Timelike
  let use_fudged_width = ref false

  let options = Options.create
    [ "constant_width", Arg.Unit (fun () → default_width := Constant),
      "use_constant_width_(also_in_t-channel)";
      "fudged_width", Arg.Set use_fudged_width,
      "use_fudge_factor_for_charge_particle_width";
      "custom_width", Arg.String (fun f → default_width := Custom f),
      "use_custom_width";
      "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
      "use_vanishing_width" ]

  type matter_field = L of int | N of int | U of int | D of int
    | L_K1_L of int | L_K1_R of int | N_K1 of int
    | L_K2_L of int | L_K2_R of int | N_K2 of int
    | U_K1_L of int | U_K2_L of int | D_K1_L of int | D_K2_L of int
    | U_K1_R of int | U_K2_R of int | D_K1_R of int | D_K2_R of int
  type gauge_boson = Ga | Wp | Wm | Z | Gl | Gl_K1 | Gl_K2
    | B1 | B2 | Z1 | Z2 | Wp1 | Wm1 | Wp2 | Wm2

```



```

type other = Phip | Phim | Phi0 | H | H1up | H1um
           | H1dp | H1dm | H2up | H2um | H2dp | H2dm
           | Grav
type flavor = M of matter_field | G of gauge_boson | O of other
let matter_field f = M f
let gauge_boson f = G f
let other f = O f
type field =
  | Matter of matter_field
  | Gauge of gauge_boson
  | Other of other
let field = function
  | M f → Matter f
  | G f → Gauge f
  | O f → Other f
type gauge = unit
let gauge_symbol () =
  failwith "Modellib_BSM.UED.gauge_symbol:␣internal␣error"
let family n = List.map matter_field [ L n; N n; U n; D n; L_K1_L n;
  L_K1_R n; L_K2_L n; L_K2_R n; N_K1 n; N_K2 n; U_K1_L n; U_K2_L n;
  D_K1_L n; D_K2_L n; U_K1_R n; U_K2_R n; D_K1_R n; D_K2_R n]

```

We don't introduce a special index for the higher excitations but make them parts of the particles' names.

```

let external_flavors () =
  [ "1st_Generation", ThoList.flatmap family [1; -1];
    "2nd_Generation", ThoList.flatmap family [2; -2];
    "3rd_Generation", ThoList.flatmap family [3; -3];
    "Gauge_Bosons", List.map gauge_boson [Ga; Z; Wp; Wm; Gl;
      Gl_K1; Gl_K2; B1; B2; Z1; Z2; Wp1; Wm1; Wp2; Wm2];
    "Higgs", List.map other [H; H1up; H1um; H1dp; H1dm;
      H2up; H2um; H2dp; H2dm];
    "Graviton", List.map other [Grav];
    "Goldstone_Bosons", List.map other [Phip; Phim; Phi0] ]
let flavors () = ThoList.flatmap snd (external_flavors ())
let spinor n =
  if n ≥ 0 then
    Spinor
  else
    ConjSpinor
let lorentz = function
  | M f →
    begin match f with
    | L n → spinor n | N n → spinor n
    | U n → spinor n | D n → spinor n
    | L_K1_L n → spinor n | L_K1_R n → spinor n

```

```

| L_K2_L n → spinor n | L_K2_R n → spinor n
| N_K1 n → spinor n | N_K2 n → spinor n
| U_K1_L n → spinor n | U_K1_R n → spinor n
| U_K2_L n → spinor n | U_K2_R n → spinor n
| D_K1_L n → spinor n | D_K1_R n → spinor n
| D_K2_L n → spinor n | D_K2_R n → spinor n
end
| G f →
  begin match f with
  | Ga | Gl → Vector
  | Wp | Wm | Z | Gl_K1 | Gl_K2 | B1 | B2
  | Z1 | Z2 | Wp1 | Wm1 | Wp2 | Wm2 → Massive_Vector
  end
| O f →
  begin match f with
  | Grav → Tensor_2
  | _ → Scalar
  end
end

let color = function
| M (U n) → Color.SUN (if n > 0 then 3 else -3)
| M (D n) → Color.SUN (if n > 0 then 3 else -3)
| M (U_K1_L n) → Color.SUN (if n > 0 then 3 else -3)
| M (D_K1_L n) → Color.SUN (if n > 0 then 3 else -3)
| M (U_K1_R n) → Color.SUN (if n > 0 then 3 else -3)
| M (D_K1_R n) → Color.SUN (if n > 0 then 3 else -3)
| M (U_K2_L n) → Color.SUN (if n > 0 then 3 else -3)
| M (D_K2_L n) → Color.SUN (if n > 0 then 3 else -3)
| M (U_K2_R n) → Color.SUN (if n > 0 then 3 else -3)
| M (D_K2_R n) → Color.SUN (if n > 0 then 3 else -3)
| G Gl | G Gl_K1 | G Gl_K2 → Color.AdjSUN 3
| _ → Color.Singlet
end

let prop_spinor n =
  if n ≥ 0 then
    Prop_Spinor
  else
    Prop_ConjSpinor
end

let propagator = function
| M f →
  begin match f with
  | L n → prop_spinor n | N n → prop_spinor n
  | U n → prop_spinor n | D n → prop_spinor n
  | L_K1_L n → prop_spinor n | L_K1_R n → prop_spinor n
  | L_K2_L n → prop_spinor n | L_K2_R n → prop_spinor n
  | N_K1 n → prop_spinor n | N_K2 n → prop_spinor n
  | U_K1_L n → prop_spinor n | U_K1_R n → prop_spinor n
  | U_K2_L n → prop_spinor n | U_K2_R n → prop_spinor n
  | D_K1_L n → prop_spinor n | D_K1_R n → prop_spinor n
  | D_K2_L n → prop_spinor n | D_K2_R n → prop_spinor n
  end
end

```

```

| G f →
  begin match f with
  | Ga | Gl → Prop_Feynman
  | Wp | Wm | Z | Gl_K1 | Gl_K2 | B1 | B2
  | Z1 | Z2 | Wp1 | Wm1 | Wp2 | Wm2 → Prop_Unitarity
  end
| O f →
  begin match f with
  | Phip | Phim | Phi0 → Only_Insertion
  | H | H1up | H1um | H1dp | H1dm | H2up
  | H2um | H2dp | H2dm → Prop_Scalar
  | Grav → Prop_Tensor_2
  end

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    | G Wp | G Wm | M (U 3) | M (U (-3)) | O Grav → Fudged
    | _ → !default_width
  else
    !default_width
let goldstone = function
| G f →
  begin match f with
  | Wp → Some (O Phip, Coupling.Const 1)
  | Wm → Some (O Phim, Coupling.Const 1)
  | Z → Some (O Phi0, Coupling.Const 1)
  | _ → None
  end
| _ → None
let conjugate = function
| M f →
  M (begin match f with
  | L n → L (-n) | N n → N (-n)
  | U n → U (-n) | D n → D (-n)
  | L_K1_L n → L_K1_L (-n) | L_K1_R n → L_K1_R (-n)
  | L_K2_L n → L_K2_L (-n) | L_K2_R n → L_K2_R (-n)
  | N_K1 n → N_K1 (-n) | N_K2 n → N_K2 (-n)
  | U_K1_L n → U_K1_L (-n) | U_K1_R n → U_K1_R (-n)
  | U_K2_L n → U_K2_L (-n) | U_K2_R n → U_K2_R (-n)
  | D_K1_L n → D_K1_L (-n) | D_K1_R n → D_K1_R (-n)
  | D_K2_L n → D_K2_L (-n) | D_K2_R n → D_K2_R (-n)
  end)
| G f →
  G (begin match f with
  | Gl → Gl | Ga → Ga | Z → Z
  | Wp → Wm | Wm → Wp

```

```

B2      | Gl_K1 → Gl_K1 | Gl_K2 → Gl_K2 | B1 → B1 | B2 →
      | Z1 → Z1 | Z2 → Z2 | Wp1 → Wm1 | Wm1 → Wp1
      | Wp2 → Wm2 | Wm2 → Wp2
      end)
| O f →
  O (begin match f with
    | Phip → Phim | Phim → Phip | Phi0 → Phi0
    | H → H | H1up → H1um | H1um → H1up
    | H1dp → H1dm | H1dm → H1dp
    | H2up → H2um | H2um → H2up
    | H2dp → H2dm | H2dm → H2dp
    | Grav → Grav
  end)
let fermion = function
| M f →
  begin match f with
    | L n → if n > 0 then 1 else -1
    | N n → if n > 0 then 1 else -1
    | U n → if n > 0 then 1 else -1
    | D n → if n > 0 then 1 else -1
    | L_K1_L n → if n > 0 then 1 else -1
    | L_K2_L n → if n > 0 then 1 else -1
    | L_K1_R n → if n > 0 then 1 else -1
    | L_K2_R n → if n > 0 then 1 else -1
    | U_K1_L n → if n > 0 then 1 else -1
    | U_K2_L n → if n > 0 then 1 else -1
    | U_K1_R n → if n > 0 then 1 else -1
    | U_K2_R n → if n > 0 then 1 else -1
    | D_K1_L n → if n > 0 then 1 else -1
    | D_K2_L n → if n > 0 then 1 else -1
    | D_K1_R n → if n > 0 then 1 else -1
    | D_K2_R n → if n > 0 then 1 else -1
    | N_K1 n → if n > 0 then 1 else -1
    | N_K2 n → if n > 0 then 1 else -1
  end
| G f →
  begin match f with
    | Gl | Ga | Z | Wp | Wm | Gl_K1 | Gl_K2
    | B1 | B2 | Z1 | Z2 | Wp1 | Wm1 | Wp2
    | Wm2 → 0
  end
| O _ → 0
module Ch = Charges.QQ
let ( // ) = Algebra.Small_Rational.make
let generation' = function
| 1 → [ 1//1; 0//1; 0//1 ]
| 2 → [ 0//1; 1//1; 0//1 ]

```

```

| 3 → [ 0//1; 0//1; 1//1]
| -1 → [-1//1; 0//1; 0//1]
| -2 → [ 0//1; -1//1; 0//1]
| -3 → [ 0//1; 0//1; -1//1]
| n → invalid_arg ("SM.generation':␣" ^ string_of_int n)

let generation f =
  match f with
  | M (L n | N n | U n | D n | L_K1_L n | L_K2_L n
      | L_K1_R n | L_K2_R n | N_K1 n | N_K2 n | U_K1_L n
      | U_K2_L n | U_K1_R n | U_K2_R n | D_K1_L n |
D_K2_L n
      | D_K1_R n | D_K2_R n) → generation' n
  | G _ | O _ → [0//1; 0//1; 0//1]

let charge = function
| M f →
  begin match f with
  | L n | L_K1_L n | L_K2_L n | L_K1_R n
  | L_K2_R n → if n > 0 then -1//1 else 1//1
  | N n | N_K1 n | N_K2 n → 0//1
  | U n | U_K1_L n | U_K2_L n | U_K1_R n
  | U_K2_R n → if n > 0 then 2//3 else -2//3
  | D n | D_K1_L n | D_K2_L n | D_K1_R n
  | D_K2_R n → if n > 0 then -1//3 else 1//3
  end
| G f →
  begin match f with
  | Gl | Gl_K1 | Gl_K2 | Ga | Z
  | B1 | B2 | Z1 | Z2 → 0//1
  | Wp | Wp1 | Wp2 → 1//1
  | Wm | Wm1 | Wm2 → -1//1
  end
| O f →
  begin match f with
  | H | Phi0 | Grav → 0//1
  | H1up | H1dp | H2up | H2dp | Phip → 1//1
  | H1um | H1dm | H2um | H2dm | Phim → -1//1
  end

let lepton = function
| M f →
  begin match f with
  | L n | N n | L_K1_L n | L_K1_R n | L_K2_L n
  | L_K2_R n | N_K1 n | N_K2 n → if n > 0 then 1//1 else -
1//1
  | U _ | D _ | _ → 0//1
  end
| G _ | O _ → 0//1

let baryon = function
| M f →

```

```

begin match f with
| U n | D n | U_K1_L n | U_K1_R n | U_K2_L n
| U_K2_R n | D_K1_L n | D_K1_R n | D_K2_L n
| D_K2_R n → if n > 0 then 1//1 else -1//1
| L - | N - | - → 0//1
end
| G - | O - → 0//1
let charges f =
[ charge f; lepton f; baryon f] @ generation f
type constant =
| Unit | Pi | Alpha_QED | Sin2thw
| Sinthw | Costhw | E | G_weak | Vev
| Q_lepton | Q_up | Q_down | G_CC | G_CCQ of int × int
| G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down
| I_Q_W | I_G_ZWW | I_Q_W_K | I_G_ZWW_K1 |
I_G_ZWW_K2
| I_G_ZWW_K3
| G_WWWW | G_ZZWW | G_AZWW | G_AAWW
| G_HWW | G_HHWW | G_HZZ | G_HHZZ
| G_Htt | G_Hbb | G_Hcc | G_Htautau | G_H3 | G_H4
| G_HGaZ | G_HGaGa | G_Hgg
| Gs | I_Gs | I_GsRt2 | G2 | G22 | G_Grav
| Mass of flavor | Width of flavor

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int
let orders = function
| - → (0,0)
let input_parameters =
[]
let derived_parameters =
[]
let derived_parameter_arrays =
[]
let parameters () =
{ input = input_parameters;
  derived = derived_parameters;
  derived_arrays = derived_parameter_arrays }
module F = Modeltools.Fusions (struct
type f = flavor
type c = constant
let compare = compare
let conjugate = conjugate
end)
let mgm ((m1, g, m2), fbf, c) = ((M m1, G g, M m2), fbf, c)
let mom ((m1, o, m2), fbf, c) = ((M m1, O o, M m2), fbf, c)

```

```

let electromagnetic_currents n =
  List.map mgm
    [ ((L (-n), Ga, L n), FBF (1, Psibar, V, Psi), Q_lepton);
      ((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q_up);
      ((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q_down) ]

let neutral_currents n =
  List.map mgm
    [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
      ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
      ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
      ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]

let charged_currents n =
  List.map mgm
    [ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G_CC);
      ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G_CC);
      ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_CC);
      ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G_CC) ]

let color_currents n =
  List.map mgm
    [ ((U (-n), Gl, U n), FBF ((-1), Psibar, V, Psi), Gs);
      ((D (-n), Gl, D n), FBF ((-1), Psibar, V, Psi), Gs) ]

let gravity_currents n =
  List.map mom
    [ ((L (-n), Grav, L n), Graviton_Spinor_Spinor 1, G_Grav);
      ((N (-n), Grav, N n), Graviton_Spinor_Spinor 1, G_Grav);
      ((U (-n), Grav, U n), Graviton_Spinor_Spinor 1, G_Grav);
      ((D (-n), Grav, D n), Graviton_Spinor_Spinor 1, G_Grav) ]

let yukawa =
  List.map mom
    [ ((U (-3), H, U 3), FBF (1, Psibar, S, Psi), G_Htt);
      ((D (-3), H, D 3), FBF (1, Psibar, S, Psi), G_Hbb);
      ((U (-2), H, U 2), FBF (1, Psibar, S, Psi), G_Hcc);
      ((L (-3), H, L 3), FBF (1, Psibar, S, Psi), G_Htautau) ]

let tgc ((g1, g2, g3), t, c) = ((G g1, G g2, G g3), t, c)

```

Gluons should be included in just that way.

```

let standard_triple_gauge =
  List.map tgc
    [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
      ((Ga, Wm1, Wp1), Gauge_Gauge_Gauge 1, I_Q_W_K);
      ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW);
      ((Z, Wm1, Wp1), Gauge_Gauge_Gauge 1, I_G_ZWW_K1);
      ((Z1, Wm, Wp1), Gauge_Gauge_Gauge 1, I_G_ZWW_K2);
      ((Z1, Wm1, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW_K2);
      ((Z2, Wm1, Wp2), Gauge_Gauge_Gauge 1, I_G_ZWW_K3);
      ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_Gs);
      ((Gl, Gl_K2, Gl_K2), Gauge_Gauge_Gauge (-1), I_Gs);

```

```

      ((Gl, Gl_K1, Gl_K1), Gauge_Gauge_Gauge 1, I_Gs);
      ((Gl_K2, Gl_K1, Gl_K1), Gauge_Gauge_Gauge 1, I_GsRt2)]

let triple_gauge =
  standard_triple_gauge

let qgc ((g1, g2, g3, g4), t, c) = ((G g1, G g2, G g3, G g4), t, c)

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let standard_quartic_gauge =
  List.map qgc
    [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
      (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
      (Wm, Z, Wp, Ga), minus_gauge4, G_AZWW;
      (Wm, Ga, Wp, Ga), minus_gauge4, G_AAWW;
      ((Gl, Gl, Gl, Gl), gauge4, G2);
      ((Gl, Gl, Gl_K1, Gl_K1), gauge4, G2);
      ((Gl, Gl, Gl_K2, Gl_K2), gauge4, G2);
      ((Gl_K1, Gl_K1, Gl_K2, Gl_K2), gauge4, G2);
      ((Gl_K2, Gl_K2, Gl_K2, Gl_K2), gauge4, G22)]

let quartic_gauge =
  standard_quartic_gauge

let gravity_gauge =
  [ (O Grav, G Z, G Z), Graviton_Vector_Vector 1, G_Grav;
    (O Grav, G Wp, G Wm), Graviton_Vector_Vector 1, G_Grav;
    (O Grav, G Ga, G Ga), Graviton_Vector_Vector 1, G_Grav;
    (O Grav, G Gl, G Gl), Graviton_Vector_Vector 1, G_Grav ]

let standard_gauge_higgs =
  [ ((O H, G Wp, G Wm), Scalar_Vector_Vector 1, G_HWW);
    ((O H, G Z, G Z), Scalar_Vector_Vector 1, G_HZZ) ]

let standard_gauge_higgs4 =
  [ (O H, O H, G Wp, G Wm), Scalar2_Vector2 1, G_HHWW;
    (O H, O H, G Z, G Z), Scalar2_Vector2 1, G_HHZZ ]

let standard_higgs =
  [ (O H, O H, O H), Scalar_Scalar_Scalar 1, G_H3 ]

let standard_higgs4 =
  [ (O H, O H, O H, O H), Scalar4 1, G_H4 ]

let gravity_higgs =
  [ (O Grav, O H, O H), Graviton_Scalar_Scalar 1, G_Grav ]

let anomalous_gauge_higgs =
  []

let anomalous_gauge_higgs4 =
  []

let anomalous_higgs =
  []

```



```

let anomaly_higgs =
  [ (O H, G Ga, G Ga), Dim5_Scalar_Gauge2 1, G_HGaGa;
    (O H, G Ga, G Z), Dim5_Scalar_Gauge2 1, G_HGaZ;
    (O H, G Gl, G Gl), Dim5_Scalar_Gauge2 1, G_Hgg ]

let anomalous_higgs4 =
  []

let gauge_higgs =
  standard_gauge_higgs

let gauge_higgs4 =
  standard_gauge_higgs4

let higgs =
  standard_higgs @ gravity_higgs

let higgs4 =
  standard_higgs4

let goldstone_vertices =
  [ ((O Phi0, G Wm, G Wp), Scalar_Vector_Vector 1, I-G-ZWW);
    ((O Phip, G Ga, G Wm), Scalar_Vector_Vector 1, I-Q-W);
    ((O Phip, G Z, G Wm), Scalar_Vector_Vector 1, I-G-ZWW);
    ((O Phim, G Wp, G Ga), Scalar_Vector_Vector 1, I-Q-W);
    ((O Phim, G Wp, G Z), Scalar_Vector_Vector 1, I-G-ZWW) ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1;2;3] @
   ThoList.flatmap neutral_currents [1;2;3] @
   ThoList.flatmap charged_currents [1;2;3] @
   ThoList.flatmap color_currents [1;2;3] @
   ThoList.flatmap gravity_currents [1;2;3] @
   yukawa @ triple_gauge @ gravity_gauge @
   gauge_higgs @ higgs @ anomaly_higgs
   @ goldstone_vertices)

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4

let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))
| "numu" → M (N 2) | "numubar" → M (N (-2))

```

```

| "nutaui" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "uk1l" → M (U_K1_L 1) | "uk1lbar" → M (U_K1_L (-1))
| "ck1l" → M (U_K1_L 2) | "ck1lbar" → M (U_K1_L (-2))
| "tk1l" → M (U_K1_L 3) | "tk1lbar" → M (U_K1_L (-3))
| "dk1l" → M (D_K1_L 1) | "dk1lbar" → M (D_K1_L (-1))
| "sk1l" → M (D_K1_L 2) | "sk1lbar" → M (D_K1_L (-2))
| "bk1l" → M (D_K1_L 3) | "bk1lbar" → M (D_K1_L (-3))
| "uk1r" → M (U_K1_R 1) | "uk1rbar" → M (U_K1_R (-1))
| "ck1r" → M (U_K1_R 2) | "ck1rbar" → M (U_K1_R (-2))
| "tk1r" → M (U_K1_R 3) | "tk1rbar" → M (U_K1_R (-3))
| "dk1r" → M (D_K1_R 1) | "dk1rbar" → M (D_K1_R (-1))
| "sk1r" → M (D_K1_R 2) | "sk1rbar" → M (D_K1_R (-2))
| "bk1r" → M (D_K1_R 3) | "bk1rbar" → M (D_K1_R (-3))
| "uk2l" → M (U_K2_L 1) | "uk2lbar" → M (U_K2_L (-1))
| "ck2l" → M (U_K2_L 2) | "ck2lbar" → M (U_K2_L (-2))
| "tk2l" → M (U_K2_L 3) | "tk2lbar" → M (U_K2_L (-3))
| "dk2l" → M (D_K2_L 1) | "dk2lbar" → M (D_K2_L (-1))
| "sk2l" → M (D_K2_L 2) | "sk2lbar" → M (D_K2_L (-2))
| "bk2l" → M (D_K2_L 3) | "bk2lbar" → M (D_K2_L (-3))
| "uk2r" → M (U_K2_R 1) | "uk2rbar" → M (U_K2_R (-1))
| "ck2r" → M (U_K2_R 2) | "ck2rbar" → M (U_K2_R (-2))
| "tk2r" → M (U_K2_R 3) | "tk2rbar" → M (U_K2_R (-3))
| "dk2r" → M (D_K2_R 1) | "dk2rbar" → M (D_K2_R (-1))
| "sk2r" → M (D_K2_R 2) | "sk2rbar" → M (D_K2_R (-2))
| "bk2r" → M (D_K2_R 3) | "bk2rbar" → M (D_K2_R (-3))
| "g" | "gl" → G Gl
| "g_k1" | "gl_k1" → G Gl_K1
| "g_k2" | "gl_k2" → G Gl_K2
| "b1" → G B1 | "b2" → G B2 | "z1" → G Z1 | "z2" → G Z2
| "W1+" → G Wp1 | "W1-" → G Wm1
| "W2+" → G Wp2 | "W2-" → G Wm2
| "A" → G Ga | "Z" | "Z0" → G Z
| "W+" → G Wp | "W-" → G Wm
| "H" → O H | "H1u+" → O H1up | "H1u-" → O H1um
| "H1d+" → O H1dp | "H1d-" → O H1dm
| "H2u+" → O H2up | "H2u-" → O H2um
| "H2d+" → O H2dp | "H2d-" → O H2dm
| "GG" → O Grav
| "ek1l-" → M (L_K1_L 1) | "ek1l+" → M (L_K1_L (-1))
| "muk1l-" → M (L_K1_L 2) | "mu1l+" → M (L_K1_L (-2))
| "tauk1l-" → M (L_K1_L 3) | "tauk1l+" → M (L_K1_L (-3))
| "ek1r-" → M (L_K1_R 1) | "ek1r+" → M (L_K1_R (-1))
| "muk1r-" → M (L_K1_R 2) | "mu1r+" → M (L_K1_R (-2))
| "tau1r-" → M (L_K1_R 3) | "tauk1r+" → M (L_K1_R (-3))

```

```

| "ek2l-" → M (L_K2_L 1) | "ek2l+" → M (L_K2_L (-1))
| "muk2l-" → M (L_K2_L 2) | "mu2l+" → M (L_K2_L (-2))
| "tauk2l-" → M (L_K2_L 3) | "tauk2l+" → M (L_K2_L (-3))
| "ek2r-" → M (L_K2_R 1) | "ek2r+" → M (L_K2_R (-1))
| "muk2r-" → M (L_K2_R 2) | "mu2r+" → M (L_K2_R (-2))
| "tau2r-" → M (L_K2_R 3) | "tauk2r+" → M (L_K2_R (-3))
| "nuek1" → M (N_K1 1) | "nuek1bar" → M (N_K1 (-1))
| "numuk1" → M (N_K1 2) | "numuk1bar" → M (N_K1 (-2))
| "nutauk1" → M (N_K1 3) | "nutauk1bar" → M (N_K1 (-3))
| "nuek2" → M (N_K2 1) | "nuek2bar" → M (N_K2 (-1))
| "numuk2" → M (N_K2 2) | "numuk2bar" → M (N_K2 (-2))
| "nutauk2" → M (N_K2 3) | "nutauk2bar" → M (N_K2 (-3))
| - → invalid_arg "Modellib_BSM.UED.flavor_of_string"

let flavor_to_string = function
| M f →
  begin match f with
  | L 1 → "e-" | L (-1) → "e+"
  | L 2 → "mu-" | L (-2) → "mu+"
  | L 3 → "tau-" | L (-3) → "tau+"
  | L _ → invalid_arg
    "Modellib_BSM.UED.flavor_to_string:␣invalid␣lepton"
  | N 1 → "nue" | N (-1) → "nuebar"
  | N 2 → "numu" | N (-2) → "numubar"
  | N 3 → "nutau" | N (-3) → "nutaubar"
  | N _ → invalid_arg
    "Modellib_BSM.UED.flavor_to_string:␣invalid␣neutrino"
  | U 1 → "u" | U (-1) → "ubar"
  | U 2 → "c" | U (-2) → "cbar"
  | U 3 → "t" | U (-3) → "tbar"
  | U _ → invalid_arg
    "Modellib_BSM.UED.flavor_to_string:␣invalid␣up␣type␣quark"
  | D 1 → "d" | D (-1) → "dbar"
  | D 2 → "s" | D (-2) → "sbar"
  | D 3 → "b" | D (-3) → "bbar"
  | D _ → invalid_arg
    "Modellib_BSM.UED.flavor_to_string:␣invalid␣down␣type␣quark"
  | U_K1_L 1 → "uk1l" | U_K1_L (-1) → "uk1lbar"
  | U_K1_L 2 → "ck1l" | U_K1_L (-2) → "ck1lbar"
  | U_K1_L 3 → "tk1l" | U_K1_L (-3) → "tk1lbar"
  | U_K1_L _ → invalid_arg
    "Modellib_BSM.UED.flavor_to_string:␣invalid␣up␣type␣quark"
  | D_K1_L 1 → "dk1l" | D_K1_L (-1) → "dk1lbar"
  | D_K1_L 2 → "sk1l" | D_K1_L (-2) → "sk1lbar"
  | D_K1_L 3 → "bk1l" | D_K1_L (-3) → "bk1lbar"
  | D_K1_L _ → invalid_arg
    "Modellib_BSM.UED.flavor_to_string:␣invalid␣down␣type␣quark"
  | U_K1_R 1 → "uk1r" | U_K1_R (-1) → "uk1rbar"
  | U_K1_R 2 → "ck1r" | U_K1_R (-2) → "ck1rbar"
  | U_K1_R 3 → "tk1r" | U_K1_R (-3) → "tk1rbar"

```

```

| U_K1_R _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_up_type_quark"
| D_K1_R 1 → "dk1r" | D_K1_R (-1) → "dk1rbar"
| D_K1_R 2 → "sk1r" | D_K1_R (-2) → "sk1rbar"
| D_K1_R 3 → "bk1r" | D_K1_R (-3) → "bk1rbar"
| D_K1_R _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_down_type_quark"
| U_K2_L 1 → "uk2l" | U_K2_L (-1) → "uk2lbar"
| U_K2_L 2 → "ck2l" | U_K2_L (-2) → "ck2lbar"
| U_K2_L 3 → "tk2l" | U_K2_L (-3) → "tk2lbar"
| U_K2_L _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_up_type_quark"
| D_K2_L 1 → "dk2l" | D_K2_L (-1) → "dk2lbar"
| D_K2_L 2 → "sk2l" | D_K2_L (-2) → "sk2lbar"
| D_K2_L 3 → "bk2l" | D_K2_L (-3) → "bk2lbar"
| D_K2_L _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_down_type_quark"
| U_K2_R 1 → "uk2r" | U_K2_R (-1) → "uk2rbar"
| U_K2_R 2 → "ck2r" | U_K2_R (-2) → "ck2rbar"
| U_K2_R 3 → "tk2r" | U_K2_R (-3) → "tk2rbar"
| U_K2_R _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_up_type_quark"
| D_K2_R 1 → "dk2r" | D_K2_R (-1) → "dk2rbar"
| D_K2_R 2 → "sk2r" | D_K2_R (-2) → "sk2rbar"
| D_K2_R 3 → "bk2r" | D_K2_R (-3) → "bk2rbar"
| D_K2_R _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_down_type_quark"
| L_K1_L 1 → "ek1l-" | L_K1_L (-1) → "ek1l+"
| L_K1_L 2 → "muk1l-" | L_K1_L (-2) → "muk1l+"
| L_K1_L 3 → "tau1l-" | L_K1_L (-3) → "tau1l+"
| L_K1_L _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_lepton"
| L_K1_R 1 → "ek1r-" | L_K1_R (-1) → "ek1r+"
| L_K1_R 2 → "muk1r-" | L_K1_R (-2) → "muk1r+"
| L_K1_R 3 → "tau1r-" | L_K1_R (-3) → "tau1r+"
| L_K1_R _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_lepton"
| L_K2_L 1 → "ek2l-" | L_K2_L (-1) → "ek2l+"
| L_K2_L 2 → "muk2l-" | L_K2_L (-2) → "muk2l+"
| L_K2_L 3 → "tau2l-" | L_K2_L (-3) → "tau2l+"
| L_K2_L _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_lepton"
| L_K2_R 1 → "ek2r-" | L_K2_R (-1) → "ek2r+"
| L_K2_R 2 → "muk2r-" | L_K2_R (-2) → "muk2r+"
| L_K2_R 3 → "tau2r-" | L_K2_R (-3) → "tau2r+"
| L_K2_R _ → invalid_arg
| "Modellib_BSM.UED.flavor_to_string:_invalid_lepton"
| N_K1 1 → "nuek1" | N_K1 (-1) → "nuek1bar"
| N_K1 2 → "numuk1" | N_K1 (-2) → "numuk1bar"
| N_K1 3 → "nutauk1" | N_K1 (-3) → "nutauk1bar"

```

```

| N_K1 _ → invalid_arg
      "Modellib_BSM.UED.flavor_to_string:␣invalid␣neutrino"
| N_K2 1 → "nuek2" | N_K2 (-1) → "nuek2bar"
| N_K2 2 → "numuk2" | N_K2 (-2) → "numuk2bar"
| N_K2 3 → "nutauk2" | N_K2 (-3) → "nutauk2bar"
| N_K2 _ → invalid_arg
      "Modellib_BSM.UED.flavor_to_string:␣invalid␣neutrino"
end
| G f →
  begin match f with
  | Gl → "g"
  | Ga → "A" | Z → "Z"
  | Wp → "W+" | Wm → "W-"
  | Gl_K1 → "gk1" | Gl_K2 → "gk2"
  | B1 → "b1" | B2 → "b2" | Z1 → "z1" | Z2 → "z2"
  | Wp1 → "W1+" | Wm1 → "W1-"
  | Wp2 → "W2+" | Wm2 → "W2-"
  end
| O f →
  begin match f with
  | Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
  | H → "H" | H1up → "H1u+" | H1um → "H1u-"
  | H1dp → "H1d+" | H1dm → "H1d-"
  | H2up → "H2u+" | H2um → "H2u-"
  | H2dp → "H2d+" | H2dm → "H2d-"
  | Grav → "GG"
  end
let flavor_to_TeX = function
| M f →
  begin match f with
  | L 1 → "e~-" | L (-1) → "e~+"
  | L 2 → "\\mu~-" | L (-2) → "\\mu~+"
  | L 3 → "\\tau~-" | L (-3) → "\\tau~+"
  | L _ → invalid_arg
      "Modellib_BSM.UED.flavor_to_TeX:␣invalid␣lepton"
  | N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
  | N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
  | N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
  | N _ → invalid_arg
      "Modellib_BSM.UED.flavor_to_TeX:␣invalid␣neutrino"
  | U 1 → "u" | U (-1) → "\\bar{u}"
  | U 2 → "c" | U (-2) → "\\bar{c}"
  | U 3 → "t" | U (-3) → "\\bar{t}"
  | U _ → invalid_arg
      "Modellib_BSM.UED.flavor_to_TeX:␣invalid␣up␣type␣quark"
  | D 1 → "d" | D (-1) → "dbar"
  | D 2 → "s" | D (-2) → "sbar"
  | D 3 → "b" | D (-3) → "bbar"
  | D _ → invalid_arg

```

```

    "Modellib_BSM.UED.flavor_to_TeX:invalid_down_type_quark"
| U_K1_L1 → "u^\\prime_L" | U_K1_L(-1) → "\\bar{u}^\\prime_L"
| U_K1_L2 → "c^\\prime_L" | U_K1_L(-2) → "\\bar{c}^\\prime_L"
| U_K1_L3 → "t^\\prime_L" | U_K1_L(-3) → "\\bar{t}^\\prime_L"
| U_K1_L_ → invalid_arg
    "Modellib_BSM.UED.flavor_to_TeX:invalid_up_type_quark"
| D_K1_L1 → "d^\\prime_L" | D_K1_L(-1) → "\\bar{d}^\\prime_L"
| D_K1_L2 → "s^\\prime_L" | D_K1_L(-2) → "\\bar{s}^\\prime_L"
| D_K1_L3 → "b^\\prime_L" | D_K1_L(-3) → "\\bar{b}^\\prime_L"
| D_K1_L_ → invalid_arg
    "Modellib_BSM.UED.flavor_to_TeX:invalid_down_type_quark"
| U_K1_R1 → "u^\\prime_R" | U_K1_R(-1) → "\\bar{u}^\\prime_R"
| U_K1_R2 → "c^\\prime_R" | U_K1_R(-2) → "\\bar{c}^\\prime_R"
| U_K1_R3 → "t^\\prime_R" | U_K1_R(-3) → "\\bar{t}^\\prime_R"
| U_K1_R_ → invalid_arg
    "Modellib_BSM.UED.flavor_to_TeX:invalid_up_type_quark"
| D_K1_R1 → "d^\\prime_R" | D_K1_R(-1) → "\\bar{d}^\\prime_R"
| D_K1_R2 → "s^\\prime_R" | D_K1_R(-2) → "\\bar{s}^\\prime_R"
| D_K1_R3 → "b^\\prime_R" | D_K1_R(-3) → "\\bar{b}^\\prime_R"
| D_K1_R_ → invalid_arg
    "Modellib_BSM.UED.flavor_to_TeX:invalid_down_type_quark"
| U_K2_L1 → "u^{\\prime\\prime}_L" | U_K2_L(-1) →
"\\bar{u}^{\\prime\\prime}_L"
| U_K2_L2 → "c^{\\prime\\prime}_L" | U_K2_L(-2) →
"\\bar{c}^{\\prime\\prime}_L"
| U_K2_L3 → "t^{\\prime\\prime}_L" | U_K2_L(-3) →
"\\bar{t}^{\\prime\\prime}_L"
| U_K2_L_ → invalid_arg
    "Modellib_BSM.UED.flavor_to_TeX:invalid_up_type_quark"
| D_K2_L1 → "d^{\\prime\\prime}_L" | D_K2_L(-1) →
"\\bar{d}^{\\prime\\prime}_L"
| D_K2_L2 → "s^{\\prime\\prime}_L" | D_K2_L(-2) →
"\\bar{s}^{\\prime\\prime}_L"
| D_K2_L3 → "b^{\\prime\\prime}_L" | D_K2_L(-3) →
"\\bar{b}^{\\prime\\prime}_L"
| D_K2_L_ → invalid_arg
    "Modellib_BSM.UED.flavor_to_TeX:invalid_down_type_quark"
| U_K2_R1 → "u^{\\prime\\prime}_R" | U_K2_R(-1) →
"\\bar{u}^{\\prime\\prime}_R"
| U_K2_R2 → "c^{\\prime\\prime}_R" | U_K2_R(-2) →
"\\bar{c}^{\\prime\\prime}_R"
| U_K2_R3 → "t^{\\prime\\prime}_R" | U_K2_R(-3) →
"\\bar{t}^{\\prime\\prime}_R"
| U_K2_R_ → invalid_arg
    "Modellib_BSM.UED.flavor_to_TeX:invalid_up_type_quark"
| D_K2_R1 → "d^{\\prime\\prime}_R" | D_K2_R(-1) →
"\\bar{d}^{\\prime\\prime}_R"
| D_K2_R2 → "s^{\\prime\\prime}_R" | D_K2_R(-2) →
"\\bar{s}^{\\prime\\prime}_R"
| D_K2_R3 → "b^{\\prime\\prime}_R" | D_K2_R(-3) →
"\\bar{b}^{\\prime\\prime}_R"
| D_K2_R_ → invalid_arg
    "Modellib_BSM.UED.flavor_to_TeX:invalid_down_type_quark"

```

```

| L_K1_L 1 → "e_L^{\prime,-}" | L_K1_L (-1) → "\bar{e}_L^{\prime,+}"
| L_K1_L 2 → "\mu_L^{\prime,-}" | L_K1_L (-2) →
"\bar{\mu}_L^{\prime,+}"
| L_K1_L 3 → "\tau_L^{\prime,-}" | L_K1_L (-3) →
"\bar{\tau}_L^{\prime,+}"
| L_K1_L _ → invalid_arg
"Modellib_BSM.UED.flavor_to_TeX:\invalid_\lepton"
| L_K1_R 1 → "e_R^{\prime,-}" | L_K1_R (-1) →
"\bar{e}_R^{\prime,+}"
| L_K1_R 2 → "\mu_R^{\prime,-}" | L_K1_R (-2) →
"\bar{\mu}_R^{\prime,+}"
| L_K1_R 3 → "\tau_R^{\prime,-}" | L_K1_R (-3) →
"\bar{\tau}_R^{\prime,+}"
| L_K1_R _ → invalid_arg
"Modellib_BSM.UED.flavor_to_TeX:\invalid_\lepton"
| L_K2_L 1 → "e^{\prime\prime\prime,-}_L" | L_K2_L (-1) →
"\bar{e}_L^{\prime\prime\prime,+}"
| L_K2_L 2 → "\mu_L^{\prime\prime\prime,-}" | L_K2_L (-2) →
"\bar{\mu}_L^{\prime\prime\prime,+}"
| L_K2_L 3 → "\tau_L^{\prime\prime\prime,-}" | L_K2_L (-3) →
"\bar{\tau}_L^{\prime\prime\prime,+}"
| L_K2_L _ → invalid_arg
"Modellib_BSM.UED.flavor_to_TeX:\invalid_\lepton"
| L_K2_R 1 → "e_R^{\prime\prime\prime,-}" | L_K2_R (-1) →
"\bar{e}_R^{\prime\prime\prime,+}"
| L_K2_R 2 → "\mu_R^{\prime\prime\prime,-}" | L_K2_R (-2) →
"\bar{\mu}_R^{\prime\prime\prime,+}"
| L_K2_R 3 → "\tau_R^{\prime\prime\prime,-}" | L_K2_R (-3) →
"\bar{\tau}_R^{\prime\prime\prime,+}"
| L_K2_R _ → invalid_arg
"Modellib_BSM.UED.flavor_to_TeX:\invalid_\lepton"
| N_K1 1 → "\nu_e^{\prime}" | N_K1 (-1) → "\bar{\nu}_e^{\prime}"
| N_K1 2 → "\nu_\mu^{\prime}" | N_K1 (-2) → "\bar{\nu}_\mu^{\prime}"
| N_K1 3 → "\nu_\tau^{\prime}" | N_K1 (-3) → "\bar{\nu}_\tau^{\prime}"
| N_K1 _ → invalid_arg
"Modellib_BSM.UED.flavor_to_TeX:\invalid_\neutrino"
| N_K2 1 → "\nu_e^{\prime\prime\prime}" | N_K2 (-1) →
"\bar{\nu}_e^{\prime\prime\prime}"
| N_K2 2 → "\nu_\mu^{\prime\prime\prime}" | N_K2 (-2) →
"\bar{\nu}_\mu^{\prime\prime\prime}"
| N_K2 3 → "\nu_\tau^{\prime\prime\prime}" | N_K2 (-3) →
"\bar{\nu}_\tau^{\prime\prime\prime}"
| N_K2 _ → invalid_arg
"Modellib_BSM.UED.flavor_to_TeX:\invalid_\neutrino"
end
| G f →
begin match f with
| Gl → "g"
| Ga → "\gamma" | Z → "Z"
| Wp → "W^+" | Wm → "W^-"
```

```

| Gl_K1 → "g^\\prime" | Gl_K2 → "g^{\\prime\\prime}"
| B1 → "B^\\prime" | B2 → "B^{\\prime\\prime}"
| Z1 → "Z^\\prime" | Z2 → "Z^{\\prime\\prime}"
| Wp1 → "W^{\\prime,+}" | Wm1 → "W^{\\prime,-}"
| Wp2 → "W^{\\prime\\prime,+}" | Wm2 → "W^{\\prime\\prime,-}"
end
| O f →
begin match f with
| Phip → "\\phi^+" | Phim → "\\phi^-" | Phi0 →
"\\phi^0"
| H → "H" | H1up → "H1u+" | H1um → "H1u-"
| H1dp → "H1d+" | H1dm → "H1d-"
| H2up → "H2u+" | H2um → "H2u-"
| H2dp → "H2d+" | H2dm → "H2d-"
| Grav → "G^\\prime"
end
let flavor_symbol = function
| M f →
begin match f with
| L n when n > 0 → "l" ^ string_of_int n
| L n → "l" ^ string_of_int (abs n) ^ "b"
| N n when n > 0 → "n" ^ string_of_int n
| N n → "n" ^ string_of_int (abs n) ^ "b"
| U n when n > 0 → "u" ^ string_of_int n
| U n → "u" ^ string_of_int (abs n) ^ "b"
| D n when n > 0 → "d" ^ string_of_int n
| D n → "d" ^ string_of_int (abs n) ^ "b"
| L_K1_L n when n > 0 → "lk1l" ^ string_of_int n
| L_K1_L n → "lk1l" ^ string_of_int (abs n) ^ "b"
| L_K1_R n when n > 0 → "lk1r" ^ string_of_int n
| L_K1_R n → "lk1r" ^ string_of_int (abs n) ^ "b"
| L_K2_L n when n > 0 → "lk2l" ^ string_of_int n
| L_K2_L n → "lk2l" ^ string_of_int (abs n) ^ "b"
| L_K2_R n when n > 0 → "lk2r" ^ string_of_int n
| L_K2_R n → "lk2r" ^ string_of_int (abs n) ^ "b"
| U_K1_L n when n > 0 → "uk1l" ^ string_of_int n
| U_K1_L n → "uk1l" ^ string_of_int (abs n) ^ "b"
| U_K1_R n when n > 0 → "uk1r" ^ string_of_int n
| U_K1_R n → "uk1r" ^ string_of_int (abs n) ^ "b"
| U_K2_L n when n > 0 → "uk2l" ^ string_of_int n
| U_K2_L n → "uk2l" ^ string_of_int (abs n) ^ "b"
| U_K2_R n when n > 0 → "uk2r" ^ string_of_int n
| U_K2_R n → "uk2r" ^ string_of_int (abs n) ^ "b"
| D_K1_L n when n > 0 → "dk1l" ^ string_of_int n
| D_K1_L n → "dk1l" ^ string_of_int (abs n) ^ "b"
| D_K1_R n when n > 0 → "dk1r" ^ string_of_int n
| D_K1_R n → "dk1r" ^ string_of_int (abs n) ^ "b"
| D_K2_L n when n > 0 → "dk2l" ^ string_of_int n
| D_K2_L n → "dk2l" ^ string_of_int (abs n) ^ "b"

```



```

| D_K2_R n when n > 0 → "dk2r" ^ string_of_int n
| D_K2_R n → "dk2r" ^ string_of_int (abs n) ^ "b"
| N_K1 n when n > 0 → "nk1" ^ string_of_int n
| N_K1 n → "nk1" ^ string_of_int (abs n) ^ "b"
| N_K2 n when n > 0 → "nk2" ^ string_of_int n
| N_K2 n → "nk2" ^ string_of_int (abs n) ^ "b"
end
| G f →
begin match f with
| Gl → "g1"
| Ga → "a" | Z → "z"
| Wp → "wp" | Wm → "wm"
| Gl_K1 → "gk1" | Gl_K2 → "gk2"
| B1 → "b1" | B2 → "b2" | Z1 → "z1" | Z2 → "z2"
| Wp1 → "wp1" | Wm1 → "wm1"
| Wp2 → "wp2" | Wm2 → "wm2"
end
| O f →
begin match f with
| Phip → "pp" | Phim → "pm" | Phi0 → "p0"
| H → "h" | H1up → "h1up" | H1um → "h1um"
| H1dp → "h1dp" | H1dm → "h1dm"
| H2up → "h2up" | H2um → "h2um"
| H2dp → "h2dp" | H2dm → "h2dm"
| Grav → "gv"
end
let pdg = function
| M f →
begin match f with
| L n when n > 0 → 9 + 2 × n
| L n → - 9 + 2 × n
| N n when n > 0 → 10 + 2 × n
| N n → - 10 + 2 × n
| U n when n > 0 → 2 × n
| U n → 2 × n
| D n when n > 0 → - 1 + 2 × n
| D n → 1 + 2 × n
| U_K1_L n when n > 0 → 4000000 + 2 × n
| U_K1_L n → - 4000000 + 2 × n
| D_K1_L n when n > 0 → 3999999 + 2 × n
| D_K1_L n → - 3999999 + 2 × n
| U_K1_R n when n > 0 → 5000000 + 2 × n
| U_K1_R n → - 5000000 + 2 × n
| D_K1_R n when n > 0 → 4999999 + 2 × n
| D_K1_R n → - 4999999 + 2 × n
| U_K2_L n when n > 0 → 6000000 + 2 × n
| U_K2_L n → - 6000000 + 2 × n
| D_K2_L n when n > 0 → 5999999 + 2 × n
| D_K2_L n → - 5999999 + 2 × n

```

```

| U_K2_R n when n > 7000000 → 2 × n
| U_K2_R n → - 7000000 + 2 × n
| D_K2_R n when n > 0 → 6999999 + 2 × n
| D_K2_R n → - 6999999 + 2 × n
| L_K1_L n when n > 0 → 4000009 + 2 × n
| L_K1_L n → - 4000009 + 2 × n
| L_K1_R n when n > 0 → 5000009 + 2 × n
| L_K1_R n → - 5000009 + 2 × n
| L_K2_L n when n > 0 → 6000009 + 2 × n
| L_K2_L n → - 6000009 + 2 × n
| L_K2_R n when n > 0 → 7000009 + 2 × n
| L_K2_R n → - 7000009 + 2 × n
| N_K1 n when n > 0 → 4000010 + 2 × n
| N_K1 n → - 4000010 + 2 × n
| N_K2 n when n > 0 → 6000010 + 2 × n
| N_K2 n → - 6000010 + 2 × n
end
| G f →
begin match f with
| Gl → 21
| Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| Gl_K1 → 4000021 | Gl_K2 → 6000021
| B1 → 4000022 | B2 → 6000022
| Z1 → 4000023 | Z2 → 6000024
| Wp1 → 4000024 | Wm1 → (-4000024)
| Wp2 → 6000024 | Wm2 → (-6000024)
end
| O f →
begin match f with
| Phip | Phim → 27 | Phi0 → 26
| H → 25 | H1up → 4000036 | H1um → (-4000036)
| H1dp → 4000037 | H1dm → (-4000037)
| H2up → 6000036 | H2um → (-6000036)
| H2dp → 6000037 | H2dm → (-6000037)
| Grav → 39
end

let mass_symbol f =
"mass(" ^ string_of_int (abs (pdg f)) ^ ")"
let width_symbol f =
"width(" ^ string_of_int (abs (pdg f)) ^ ")"
let constant_symbol = function
| Unit → "unit" | Pi → "PI"
| Alpha_QED → "alpha" | E → "e" | G_weak → "g" | Vev →
"vev"
| Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
| Q_lepton → "qllep" | Q_up → "qup" | Q_down → "qdown"
| G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"

```

```

|  $G_{NC\_up} \rightarrow \text{"gncup"} \mid G_{NC\_down} \rightarrow \text{"gncdwn"}$ 
|  $G_{CC} \rightarrow \text{"gcc"}$ 
|  $G_{CCQ}(n1, n2) \rightarrow \text{"gccq"} \wedge \text{string\_of\_int } n1 \wedge \text{string\_of\_int } n2$ 
|  $I_{Q\_W} \rightarrow \text{"iqw"} \mid I_{G\_ZWW} \rightarrow \text{"igzww"}$ 
|  $I_{Q\_W\_K} \rightarrow \text{"iqwk"} \mid I_{G\_ZWW\_K1} \rightarrow \text{"igzwwk1"}$ 
|  $I_{G\_ZWW\_K2} \rightarrow \text{"igzwwk2"} \mid I_{G\_ZWW\_K3} \rightarrow \text{"igzwwk3"}$ 
|  $G_{WWWW} \rightarrow \text{"gw4"} \mid G_{ZZWW} \rightarrow \text{"gzzww"}$ 
|  $G_{AZWW} \rightarrow \text{"gazww"} \mid G_{AAWW} \rightarrow \text{"gaaww"}$ 
|  $G_{HWW} \rightarrow \text{"ghww"} \mid G_{HZZ} \rightarrow \text{"ghzz"}$ 
|  $G_{HHWW} \rightarrow \text{"ghhww"} \mid G_{HHZZ} \rightarrow \text{"ghhzz"}$ 
|  $G_{Htt} \rightarrow \text{"ghtt"} \mid G_{Hbb} \rightarrow \text{"ghbb"}$ 
|  $G_{Htautau} \rightarrow \text{"ghtautau"} \mid G_{Hcc} \rightarrow \text{"ghcc"}$ 
|  $G_{HGaZ} \rightarrow \text{"ghgaz"} \mid G_{HGaGa} \rightarrow \text{"ghgaga"} \mid G_{Hgg} \rightarrow$ 
"ghgg"
|  $G_{H3} \rightarrow \text{"gh3"} \mid G_{H4} \rightarrow \text{"gh4"}$ 
|  $G_2 \rightarrow \text{"gs**2"} \mid G_s \rightarrow \text{"gs"} \mid I_{Gs} \rightarrow \text{"igs"} \mid I_{GsRt2} \rightarrow$ 
"igs/sqrt(2.0_default)"
|  $G_{22} \rightarrow \text{"gs**2/2.0_default"}$ 
|  $G_{Grav} \rightarrow \text{"ggrav"}$ 
|  $Mass\ f \rightarrow \text{"mass"} \wedge \text{flavor\_symbol } f$ 
|  $Width\ f \rightarrow \text{"width"} \wedge \text{flavor\_symbol } f$ 

end

module GravTest (Flags : BSM_flags) =
struct
  let rcs = RCS.rename rcs_file "Modellib_BSM.GravTest"
    [ "Testing_of_Gravitinos" ]

  open Coupling

  let default_width = ref Timelike
  let use_fudged_width = ref false

  let options = Options.create
    [ "constant_width", Arg.Unit (fun () → default_width := Constant),
      "use_constant_width(also_in_t-channel)",
      "fudged_width", Arg.Set use_fudged_width,
      "use_fudge_factor_for_charge_particle_width",
      "custom_width", Arg.String (fun f → default_width := Custom f),
      "use_custom_width",
      "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
      "use_vanishing_width" ]

  type matter_field = L of int | N of int | U of int | D of int | SL of int
  type gauge_boson = Ga | Wp | Wm | Z | Gl | Phino
  type other = Phip | Phim | Phi0 | H | Grino
  type flavor = M of matter_field | G of gauge_boson | O of other

  let matter_field f = M f
  let gauge_boson f = G f
  let other f = O f

  type field =

```

```

| Matter of matter_field
| Gauge of gauge_boson
| Other of other

let field = function
| M f → Matter f
| G f → Gauge f
| O f → Other f

type gauge = unit

let gauge_symbol () =
  failwith "Modellib_BSM.SM.gauge_symbol: internal_error"

let family n = List.map matter_field [ L n; SL n; N n; U n; D n ]

let external_flavors () =
  [ "1st_Generation", ThoList.flatmap family [1; -1];
    "2nd_Generation", ThoList.flatmap family [2; -2];
    "3rd_Generation", ThoList.flatmap family [3; -3];
    "Gauge_Bosons", List.map gauge_boson [Ga; Z; Wp; Wm; Gl; Phino];
    "Higgs", List.map other [H];
    "Gravitino", List.map other [Grino];
    "Goldstone_Bosons", List.map other [Phip; Phim; Phi0] ]

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n =
  if n ≥ 0 then
    Spinor
  else
    ConjSpinor

let lorentz = function
| M f →
  begin match f with
  | L n → spinor n | N n → spinor n
  | U n → spinor n | D n → spinor n
  | SL _ → Scalar
  end
| G f →
  begin match f with
  | Ga | Gl → Vector
  | Wp | Wm | Z → Massive_Vector
  | Phino → Majorana
  end
| O f →
  begin match f with
  | Grino → Vectorspinor
  | _ → Scalar
  end

let color = function
| M (U n) → Color.SUN (if n > 0 then 3 else -3)
| M (D n) → Color.SUN (if n > 0 then 3 else -3)

```

```

|  $G \ Gl \rightarrow Color.AdjSUN\ 3$ 
|  $- \rightarrow Color.Singlet$ 

let prop_spinor n =
  if  $n \geq 0$  then
    Prop_Spinor
  else
    Prop_ConjSpinor

let propagator = function
|  $M \ f \rightarrow$ 
  begin match  $f$  with
  |  $L \ n \rightarrow prop\_spinor\ n$  |  $N \ n \rightarrow prop\_spinor\ n$ 
  |  $U \ n \rightarrow prop\_spinor\ n$  |  $D \ n \rightarrow prop\_spinor\ n$ 
  |  $SL \ n \rightarrow Prop\_Scalar$ 
  end
|  $G \ f \rightarrow$ 
  begin match  $f$  with
  |  $Ga \mid Gl \rightarrow Prop\_Feynman$ 
  |  $Wp \mid Wm \mid Z \rightarrow Prop\_Unitarity$ 
  |  $Phino \rightarrow Prop\_Majorana$ 
  end
|  $O \ f \rightarrow$ 
  begin match  $f$  with
  |  $Phip \mid Phim \mid Phi0 \rightarrow Only\_Insertion$ 
  |  $H \rightarrow Prop\_Scalar$ 
  |  $Grino \rightarrow Prop\_Vectorspinor$ 
  end
end

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    |  $G \ Wp \mid G \ Wm \mid M \ (U\ 3) \mid M \ (U\ (-3)) \mid O \ Grino \rightarrow Fudged$ 
    |  $- \rightarrow !default\_width$ 
  else
    !default_width

let goldstone = function
|  $G \ f \rightarrow$ 
  begin match  $f$  with
  |  $Wp \rightarrow Some\ (O\ Phip,\ Coupling.Const\ 1)$ 
  |  $Wm \rightarrow Some\ (O\ Phim,\ Coupling.Const\ 1)$ 
  |  $Z \rightarrow Some\ (O\ Phi0,\ Coupling.Const\ 1)$ 
  |  $- \rightarrow None$ 
  end
|  $- \rightarrow None$ 

let conjugate = function
|  $M \ f \rightarrow$ 
  M (begin match  $f$  with

```

```

    |  $L\ n \rightarrow L\ (-n)$  |  $N\ n \rightarrow N\ (-n)$ 
    |  $U\ n \rightarrow U\ (-n)$  |  $D\ n \rightarrow D\ (-n)$ 
    |  $SL\ n \rightarrow SL\ (-n)$ 
  end)
|  $G\ f \rightarrow$ 
   $G$  (begin match  $f$  with
    |  $Gl \rightarrow Gl$  |  $Ga \rightarrow Ga$  |  $Z \rightarrow Z$ 
    |  $Wp \rightarrow Wm$  |  $Wm \rightarrow Wp$  |  $Phino \rightarrow Phino$ 
  end)
|  $O\ f \rightarrow$ 
   $O$  (begin match  $f$  with
    |  $Phip \rightarrow Phim$  |  $Phim \rightarrow Phip$  |  $Phi0 \rightarrow Phi0$ 
    |  $H \rightarrow H$  |  $Grino \rightarrow Grino$ 
  end)

let fermion = function
|  $M\ f \rightarrow$ 
  begin match  $f$  with
    |  $L\ n \rightarrow$  if  $n > 0$  then 1 else -1
    |  $N\ n \rightarrow$  if  $n > 0$  then 1 else -1
    |  $U\ n \rightarrow$  if  $n > 0$  then 1 else -1
    |  $D\ n \rightarrow$  if  $n > 0$  then 1 else -1
    |  $SL\ _ \rightarrow 0$ 
  end
|  $G\ f \rightarrow$ 
  begin match  $f$  with
    |  $Gl$  |  $Ga$  |  $Z$  |  $Wp$  |  $Wm \rightarrow 0$ 
    |  $Phino \rightarrow 2$ 
  end
|  $O\ f \rightarrow$ 
  begin match  $f$  with
    |  $Grino \rightarrow 2$ 
    |  $_ \rightarrow 0$ 
  end
end

module Ch = Charges.QQ

let ( // ) = Algebra.Small_Rational.make

let generation' = function
| 1  $\rightarrow$  [ 1//1; 0//1; 0//1 ]
| 2  $\rightarrow$  [ 0//1; 1//1; 0//1 ]
| 3  $\rightarrow$  [ 0//1; 0//1; 1//1 ]
| -1  $\rightarrow$  [-1//1; 0//1; 0//1 ]
| -2  $\rightarrow$  [ 0//1; -1//1; 0//1 ]
| -3  $\rightarrow$  [ 0//1; 0//1; -1//1 ]
|  $n \rightarrow$  invalid_arg ("SM3.generation': $\square$ " ^ string_of_int  $n$ )

let generation f =
  match  $f$  with
  |  $M\ (L\ n \mid N\ n \mid U\ n \mid D\ n \mid SL\ n) \rightarrow$  generation'  $n$ 
  |  $G\ _ \mid O\ _ \rightarrow$  [0//1; 0//1; 0//1]

```

```

let charge = function
| M f →
  begin match f with
  | L n → if n > 0 then -1//1 else 1//1
  | SL n → if n > 0 then -1//1 else 1//1
  | N n → 0//1
  | U n → if n > 0 then 2//3 else -2//3
  | D n → if n > 0 then -1//3 else 1//3
  end
| G f →
  begin match f with
  | Gl | Ga | Z | Phino → 0//1
  | Wp → 1//1
  | Wm → -1//1
  end
| O f →
  begin match f with
  | H | Phi0 | Grino → 0//1
  | Phip → 1//1
  | Phim → -1//1
  end

let lepton = function
| M f →
  begin match f with
  | L n | N n | SL n → if n > 0 then 1//1 else -1//1
  | U _ | D _ → 0//1
  end
| G _ | O _ → 0//1

let baryon = function
| M f →
  begin match f with
  | L _ | N _ | SL _ → 0//1
  | U n | D n → if n > 0 then 1//1 else -1//1
  end
| G _ | O _ → 0//1

let charges f =
[ charge f; lepton f; baryon f ] @ generation f

type constant =
| Unit | Pi | Alpha_QED | Sin2thw
| Sinthw | Costhw | E | G_weak | Vev
| Q_lepton | Q_up | Q_down | G_CC | G_CCQ of int×int
| G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down
| I_Q_W | I_G_ZWW
| G_WWWW | G_ZZWW | G_AZWW | G_AAWW
| G_HWW | G_HHWW | G_HZZ | G_HHZZ
| G_Htt | G_Hbb | G_Hcc | G_Htautau | G_H3 | G_H4
| G_HGaZ | G_HGaGa | G_Hgg
| G_strong | G_Grav

```

| *Mass of flavor* | *Width of flavor*

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int

let orders = function
  | - → (0,0)

let input_parameters =
  []

let derived_parameters =
  []

let derived_parameter_arrays =
  []

let parameters () =
  { input = input_parameters;
    derived = derived_parameters;
    derived_arrays = derived_parameter_arrays }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let mgm ((m1, g, m2), fbf, c) = ((M m1, G g, M m2), fbf, c)
let mom ((m1, o, m2), fbf, c) = ((M m1, O o, M m2), fbf, c)

let electromagnetic_currents n =
  List.map mgm
    [ ((L (-n), Ga, L n), FBF (1, Psibar, V, Psi), Q_lepton);
      ((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q_up);
      ((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q_down) ]

let neutral_currents n =
  List.map mgm
    [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
      ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
      ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
      ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]

let charged_currents n =
  List.map mgm
    [ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G_CC);
      ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G_CC);
      ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_CC);
      ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G_CC) ]

let yukawa =
  List.map mom
    [ ((L (-3), H, U 3), FBF (1, Psibar, S, Psi), G_Htt);
      ((D (-3), H, D 3), FBF (1, Psibar, S, Psi), G_Hbb);

```



```

      ((U (-2), H, U 2), FBF (1, Psibar, S, Psi), G_Hcc);
      ((L (-3), H, L 3), FBF (1, Psibar, S, Psi), G_Htautau) ]
let tgc ((g1, g2, g3), t, c) = ((G g1, G g2, G g3), t, c)
let standard_triple_gauge =
  List.map tgc
    [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
      ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW) ]
let triple_gauge =
  standard_triple_gauge
let qgc ((g1, g2, g3, g4), t, c) = ((G g1, G g2, G g3, G g4), t, c)
let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let standard_quartic_gauge =
  List.map qgc
    [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
      (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
      (Wm, Z, Wp, Ga), minus_gauge4, G_AZWW;
      (Wm, Ga, Wp, Ga), minus_gauge4, G_AAWW ]
let quartic_gauge =
  standard_quartic_gauge
let standard_gauge_higgs =
  [ ((O H, G Wp, G Wm), Scalar_Vector_Vector 1, G_HWW);
    ((O H, G Z, G Z), Scalar_Vector_Vector 1, G_HZZ) ]
let standard_gauge_higgs4 =
  [ (O H, O H, G Wp, G Wm), Scalar2_Vector2 1, G_HHWW;
    (O H, O H, G Z, G Z), Scalar2_Vector2 1, G_HHZZ ]
let standard_higgs =
  [ (O H, O H, O H), Scalar_Scalar_Scalar 1, G_H3 ]
let standard_higgs4 =
  [ (O H, O H, O H, O H), Scalar4 1, G_H4 ]
let anomalous_gauge_higgs =
  []
let anomalous_gauge_higgs4 =
  []
let anomalous_higgs =
  []
let anomaly_higgs =
  [ (O H, G Ga, G Ga), Dim5_Scalar_Gauge2 1, G_HGaGa;
    (O H, G Ga, G Z), Dim5_Scalar_Gauge2 1, G_HGaZ;
    (O H, G Gl, G Gl), Dim5_Scalar_Gauge2 1, G_Hgg ]
let gravitino_coup n =
  [ (O Grino, M (SL (-n)), M (L n)), GBG (1, Gravbar, POT, Psi), G_Grav;
    (M (L (-n)), M (SL n), O Grino), GBG (1, Psibar, POT, Grav), G_Grav ]

```

```

let gravitino_gauge =
  [ (O Grino, G Ga, G Phino), GBG (1, Gravbar, V, Chi), G_Grav ]

let anomalous_higgs4 =
  []

let gauge_higgs =
  standard_gauge_higgs

let gauge_higgs4 =
  standard_gauge_higgs4

let higgs =
  standard_higgs

let higgs4 =
  standard_higgs4

let goldstone_vertices =
  [ ((O Phi0, G Wm, G Wp), Scalar_Vector_Vector 1, I_G_ZWW);
    ((O Phip, G Ga, G Wm), Scalar_Vector_Vector 1, I_Q_W);
    ((O Phip, G Z, G Wm), Scalar_Vector_Vector 1, I_G_ZWW);
    ((O Phim, G Wp, G Ga), Scalar_Vector_Vector 1, I_Q_W);
    ((O Phim, G Wp, G Z), Scalar_Vector_Vector 1, I_G_ZWW) ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1; 2; 3] @
   ThoList.flatmap neutral_currents [1; 2; 3] @
   ThoList.flatmap charged_currents [1; 2; 3] @
   ThoList.flatmap gravitino_coup [1; 2; 3] @
   gravitino_gauge @
   yukawa @ triple_gauge @
   gauge_higgs @ higgs @ anomaly_higgs
   @ goldstone_vertices)

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4

let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "se-" → M (SL 1) | "se+" → M (SL (-1))
| "smu-" → M (SL 2) | "smu+" → M (SL (-2))
| "stau-" → M (SL 3) | "stau+" → M (SL (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))

```

```

| "numu" → M (N 2) | "numubar" → M (N (-2))
| "nutau" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "g" | "gl" → G Gl
| "A" → G Ga | "Z" | "Z0" → G Z
| "W+" → G Wp | "W-" → G Wm
| "H" → O H
| "GG" → O Grino
| "phino" | "Phino" → G Phino
| - → invalid_arg "Modellib_BSM.GravTest.flavor_of_string"

let flavor_to_string = function
| M f →
  begin match f with
  | L 1 → "e-" | L (-1) → "e+"
  | L 2 → "mu-" | L (-2) → "mu+"
  | L 3 → "tau-" | L (-3) → "tau+"
  | L _ → invalid_arg
    "Modellib_BSM.GravTest.flavor_to_string:␣invalid␣lepton"
  | SL 1 → "se-" | SL (-1) → "se+"
  | SL 2 → "smu-" | SL (-2) → "smu+"
  | SL 3 → "stau-" | SL (-3) → "stau+"
  | SL _ → invalid_arg
    "Modellib_BSM.GravTest.flavor_to_string:␣invalid␣slepton"
  | N 1 → "nue" | N (-1) → "nuebar"
  | N 2 → "numu" | N (-2) → "numubar"
  | N 3 → "nutau" | N (-3) → "nutaubar"
  | N _ → invalid_arg
    "Modellib_BSM.GravTest.flavor_to_string:␣invalid␣neutrino"
  | U 1 → "u" | U (-1) → "ubar"
  | U 2 → "c" | U (-2) → "cbar"
  | U 3 → "t" | U (-3) → "tbar"
  | U _ → invalid_arg
    "Modellib_BSM.SM.flavor_to_string:␣invalid␣up␣type␣quark"
  | D 1 → "d" | D (-1) → "dbar"
  | D 2 → "s" | D (-2) → "sbar"
  | D 3 → "b" | D (-3) → "bbar"
  | D _ → invalid_arg
    "Modellib_BSM.GravTest.flavor_to_string:␣invalid␣down␣type␣quark"
  end
| G f →
  begin match f with
  | Gl → "g"
  | Ga → "A" | Z → "Z"
  | Wp → "W+" | Wm → "W-"

```

```

    | Phino → "phino"
  end
| O f →
  begin match f with
    | Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
    | H → "H" | Grino → "GG"
  end
let flavor_to_TeX = function
| M f →
  begin match f with
    | L 1 → "e^-" | L (-1) → "e^+"
    | L 2 → "\\mu^-" | L (-2) → "\\mu^+"
    | L 3 → "\\tau^-" | L (-3) → "\\tau^+"
    | L _ → invalid_arg
    "Modellib_BSM.GravTest.flavor_to_TeX:␣invalid␣lepton"
    | SL 1 → "\\tilde{e}^-" | SL (-1) → "\\tilde{e}^+"
    | SL 2 → "\\tilde{\\mu}^-" | SL (-2) → "\\tilde{\\mu}^+"
    | SL 3 → "\\tilde{\\tau}^-" | SL (-3) → "\\tilde{\\tau}^+"
    | SL _ → invalid_arg
    "Modellib_BSM.GravTest.flavor_to_TeX:␣invalid␣slepton"
    | N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
    | N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
    | N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
    | N _ → invalid_arg
    "Modellib_BSM.GravTest.flavor_to_TeX:␣invalid␣neutrino"
    | U 1 → "u" | U (-1) → "\\bar{u}"
    | U 2 → "c" | U (-2) → "\\bar{c}"
    | U 3 → "t" | U (-3) → "\\bar{t}"
    | U _ → invalid_arg
    "Modellib_BSM.SM.flavor_to_TeX:␣invalid␣up␣type␣quark"
    | D 1 → "d" | D (-1) → "\\bar{d}"
    | D 2 → "s" | D (-2) → "\\bar{s}"
    | D 3 → "b" | D (-3) → "\\bar{b}"
    | D _ → invalid_arg
    "Modellib_BSM.GravTest.flavor_to_TeX:␣invalid␣down␣type␣quark"
  end
| G f →
  begin match f with
    | Gl → "g"
    | Ga → "\\gamma" | Z → "Z"
    | Wp → "W^+" | Wm → "W^- "
    | Phino → "\\tilde{\\phi}"
  end
| O f →
  begin match f with
    | Phip → "\\phi^+" | Phim → "\\phi^-" | Phi0 →
    "\\phi^0"
    | H → "H" | Grino → "\\tilde{G}"
  end
end

```

```

let flavor_symbol = function
| M f →
  begin match f with
  | L n when n > 0 → "l" ^ string_of_int n
  | L n → "l" ^ string_of_int (abs n) ^ "b"
  | SL n when n > 0 → "sl" ^ string_of_int n
  | SL n → "sl" ^ string_of_int (abs n) ^ "b"
  | N n when n > 0 → "n" ^ string_of_int n
  | N n → "n" ^ string_of_int (abs n) ^ "b"
  | U n when n > 0 → "u" ^ string_of_int n
  | U n → "u" ^ string_of_int (abs n) ^ "b"
  | D n when n > 0 → "d" ^ string_of_int n
  | D n → "d" ^ string_of_int (abs n) ^ "b"
  end
| G f →
  begin match f with
  | Gl → "gl"
  | Ga → "a" | Z → "z"
  | Wp → "wp" | Wm → "wm"
  | Phino → "phino"
  end
| O f →
  begin match f with
  | Phip → "pp" | Phim → "pm" | Phi0 → "p0"
  | H → "h" | Grino → "gv"
  end
end

let pdg = function
| M f →
  begin match f with
  | L n when n > 0 → 9 + 2 × n
  | L n → - 9 + 2 × n
  | SL n when n > 0 → 39 + 2 × n
  | SL n → - 39 + 2 × n
  | N n when n > 0 → 10 + 2 × n
  | N n → - 10 + 2 × n
  | U n when n > 0 → 2 × n
  | U n → 2 × n
  | D n when n > 0 → - 1 + 2 × n
  | D n → 1 + 2 × n
  end
| G f →
  begin match f with
  | Gl → 21
  | Ga → 22 | Z → 23
  | Wp → 24 | Wm → (-24)
  | Phino → 46
  end
| O f →
  begin match f with

```

```

    | Phip | Phim → 27 | Phi0 → 26
    | H → 25 | Grino → 39
  end

let mass_symbol f =
  "mass(" ^ string_of_int (abs (pdg f)) ^ ")"

let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"

let constant_symbol = function
  | Unit → "unit" | Pi → "PI"
  | Alpha_QED → "alpha" | E → "e" | G_weak → "g" | Vev →
"vev"
  | Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
  | Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdown"
  | G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
  | G_NC_up → "gncup" | G_NC_down → "gncdown"
  | G_CC → "gcc"
  | G_CCQ (n1, n2) → "gccq" ^ string_of_int n1 ^ string_of_int n2
  | I_Q_W → "iqw" | I_G_ZWW → "igzww"
  | G_WWWW → "gw4" | G_ZZWW → "gzzww"
  | G_AZWW → "gazww" | G_AAWW → "gaaww"
  | G_HWW → "ghww" | G_HZZ → "ghzz"
  | G_HHWW → "ghhww" | G_HHZZ → "ghhzz"
  | G_Htt → "ghtt" | G_Hbb → "ghbb"
  | G_Htautau → "ghtautau" | G_Hcc → "ghcc"
  | G_HGaZ → "ghgaz" | G_HGaGa → "ghgaga" | G_Hgg →
"ghgg"
  | G_H3 → "gh3" | G_H4 → "gh4"
  | G_strong → "gs" | G_Grav → "ggrav"
  | Mass f → "mass" ^ flavor_symbol f
  | Width f → "width" ^ flavor_symbol f
end

module Template (Flags : BSM_flags) =
struct
  let rcs = RCS.rename rcs_file "Modellib_BSM.Template"
    [ "Template_for_user-defined_BSM_model" ]

  open Coupling

  let default_width = ref Timelike
  let use_fudged_width = ref false

  let options = Options.create
    [ "constant_width", Arg.Unit (fun () → default_width := Constant),
      "use_constant_width(also_in_t-channel)";
      "fudged_width", Arg.Set use_fudged_width,
      "use_fudge_factor_for_charge_particle_width";
      "custom_width", Arg.String (fun f → default_width := Custom f),
      "use_custom_width";

```

```

    "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
    "use_vanishing_width"]

type matter_field = L of int | N of int | U of int | D of int
type gauge_boson = Ga | Wp | Wm | Z | Gl
type other = Phip | Phim | Phi0 | H
type flavor = M of matter_field | G of gauge_boson | O of other

let matter_field f = M f
let gauge_boson f = G f
let other f = O f

type field =
| Matter of matter_field
| Gauge of gauge_boson
| Other of other

let field = function
| M f → Matter f
| G f → Gauge f
| O f → Other f

type gauge = unit

let gauge_symbol () =
  failwith "Modellib_BSM.Template.gauge_symbol: internal error"

let family n = List.map matter_field [ L n; N n; U n; D n ]

let external_flavors () =
  [ "1st_Generation", ThoList.flatmap family [1; -1];
    "2nd_Generation", ThoList.flatmap family [2; -2];
    "3rd_Generation", ThoList.flatmap family [3; -3];
    "Gauge_Bosons", List.map gauge_boson [Ga; Z; Wp; Wm; Gl];
    "Higgs", List.map other [H];
    "Goldstone_Bosons", List.map other [Phip; Phim; Phi0] ]

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n =
  if n ≥ 0 then
    Spinor
  else
    ConjSpinor

let lorentz = function
| M f →
  begin match f with
  | L n → spinor n | N n → spinor n
  | U n → spinor n | D n → spinor n
  end
| G f →
  begin match f with
  | Ga | Gl → Vector
  | Wp | Wm | Z → Massive_Vector
  end

```

```

|  $O f \rightarrow \text{Scalar}$ 
let color = function
|  $M (U n) \rightarrow \text{Color.SUN (if } n > 0 \text{ then } 3 \text{ else } -3)$ 
|  $M (D n) \rightarrow \text{Color.SUN (if } n > 0 \text{ then } 3 \text{ else } -3)$ 
|  $G Gl \rightarrow \text{Color.AdjSUN } 3$ 
|  $- \rightarrow \text{Color.Singlet}$ 
let prop_spinor n =
if  $n \geq 0$  then
  Prop_Spinor
else
  Prop_ConjSpinor
let propagator = function
|  $M f \rightarrow$ 
  begin match  $f$  with
  |  $L n \rightarrow \text{prop\_spinor } n$  |  $N n \rightarrow \text{prop\_spinor } n$ 
  |  $U n \rightarrow \text{prop\_spinor } n$  |  $D n \rightarrow \text{prop\_spinor } n$ 
  end
|  $G f \rightarrow$ 
  begin match  $f$  with
  |  $Ga$  |  $Gl \rightarrow \text{Prop\_Feynman}$ 
  |  $Wp$  |  $Wm$  |  $Z \rightarrow \text{Prop\_Unitarity}$ 
  end
|  $O f \rightarrow$ 
  begin match  $f$  with
  |  $Phip$  |  $Phim$  |  $Phi0 \rightarrow \text{Only\_Insertion}$ 
  |  $H \rightarrow \text{Prop\_Scalar}$ 
  end
end

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
if !use_fudged_width then
  match  $f$  with
  |  $G Wp$  |  $G Wm$  |  $M (U 3)$  |  $M (U (-3)) \rightarrow \text{Fudged}$ 
  |  $- \rightarrow \text{!default\_width}$ 
else
  !default_width
let goldstone = function
|  $G f \rightarrow$ 
  begin match  $f$  with
  |  $Wp \rightarrow \text{Some (O Phip, Coupling.Const 1)}$ 
  |  $Wm \rightarrow \text{Some (O Phim, Coupling.Const 1)}$ 
  |  $Z \rightarrow \text{Some (O Phi0, Coupling.Const 1)}$ 
  |  $- \rightarrow \text{None}$ 
  end
|  $- \rightarrow \text{None}$ 
let conjugate = function
|  $M f \rightarrow$ 

```



```

      M (begin match f with
        | L n → L (-n) | N n → N (-n)
        | U n → U (-n) | D n → D (-n)
      end)
    | G f →
      G (begin match f with
        | Gl → Gl | Ga → Ga | Z → Z
        | Wp → Wm | Wm → Wp
      end)
    | O f →
      O (begin match f with
        | Phip → Phim | Phim → Phip | Phi0 → Phi0
        | H → H
      end)

let fermion = function
| M f →
  begin match f with
    | L n → if n > 0 then 1 else -1
    | N n → if n > 0 then 1 else -1
    | U n → if n > 0 then 1 else -1
    | D n → if n > 0 then 1 else -1
  end
| G f →
  begin match f with
    | Gl | Ga | Z | Wp | Wm → 0
  end
| O _ → 0

module Ch = Charges.QQ

let ( / / ) = Algebra.Small_Rational.make

let generation' = function
| 1 → [ 1//1; 0//1; 0//1]
| 2 → [ 0//1; 1//1; 0//1]
| 3 → [ 0//1; 0//1; 1//1]
| -1 → [-1//1; 0//1; 0//1]
| -2 → [ 0//1; -1//1; 0//1]
| -3 → [ 0//1; 0//1; -1//1]
| n → invalid_arg ("Template.generation':␣" ^ string_of_int n)

let generation f =
  match f with
  | M (L n | N n | U n | D n) → generation' n
  | G _ | O _ → [0//1; 0//1; 0//1]

let charge = function
| M f →
  begin match f with
    | L n → if n > 0 then -1//1 else 1//1
    | N n → 0//1
    | U n → if n > 0 then 2//3 else -2//3
  end

```

```

      |  $D\ n \rightarrow$  if  $n > 0$  then  $-1//3$  else  $1//3$ 
    end
  |  $G\ f \rightarrow$ 
    begin match  $f$  with
    |  $Gl$  |  $Ga$  |  $Z \rightarrow 0//1$ 
    |  $Wp \rightarrow 1//1$ 
    |  $Wm \rightarrow -1//1$ 
    end
  |  $O\ f \rightarrow$ 
    begin match  $f$  with
    |  $H$  |  $Phi0 \rightarrow 0//1$ 
    |  $Phip \rightarrow 1//1$ 
    |  $Phim \rightarrow -1//1$ 
    end
let lepton = function
  |  $M\ f \rightarrow$ 
    begin match  $f$  with
    |  $L\ n$  |  $N\ n \rightarrow$  if  $n > 0$  then  $1//1$  else  $-1//1$ 
    |  $U\ -$  |  $D\ - \rightarrow 0//1$ 
    end
  |  $G\ -$  |  $O\ - \rightarrow 0//1$ 
let baryon = function
  |  $M\ f \rightarrow$ 
    begin match  $f$  with
    |  $L\ -$  |  $N\ - \rightarrow 0//1$ 
    |  $U\ n$  |  $D\ n \rightarrow$  if  $n > 0$  then  $1//1$  else  $-1//1$ 
    end
  |  $G\ -$  |  $O\ - \rightarrow 0//1$ 
let charges  $f =$ 
  [charge  $f$ ; lepton  $f$ ; baryon  $f$ ] @ generation  $f$ 
type constant =
  | Unit | Pi | Alpha_QED | Sin2thw
  | Sinthw | Costhw | E | G_weak | Vev
  | Q_lepton | Q_up | Q_down | G_CC
  | G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down
  | I_Q_W | I_G_ZWW
  | G_WWWW | G_ZZWW | G_AZWW | G_AAWW
  | G_HWW | G_HHWW | G_HZZ | G_HHZZ
  | G_Htt | G_Hbb | G_Hcc | G_Hmm | G_Htautau | G_H3 |
G_H4
  | G_HGaZ | G_HGaGa | G_Hgg
  | Gs | I_Gs | G2
  | Mass of flavor | Width of flavor

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int  $\times$  int
let orders = function
  | -  $\rightarrow$  (0,0)

```

```

let input_parameters = []
let derived_parameters = []
let derived_parameter_arrays = []
let parameters () =
  { input = input_parameters;
    derived = derived_parameters;
    derived_arrays = derived_parameter_arrays }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let mgm ((m1, g, m2), fbf, c) = ((M m1, G g, M m2), fbf, c)

let electromagnetic_currents n =
  List.map mgm
    [ ((L (-n), Ga, L n), FBF (1, Psibar, V, Psi), Q_lepton);
      ((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q_up);
      ((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q_down) ]

let color_currents n =
  List.map mgm
    [ ((U (-n), Gl, U n), FBF ((-1), Psibar, V, Psi), Gs);
      ((D (-n), Gl, D n), FBF ((-1), Psibar, V, Psi), Gs) ]

let neutral_currents n =
  List.map mgm
    [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
      ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
      ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
      ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]

let charged_currents n =
  List.map mgm
    [ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G_CC);
      ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G_CC);
      ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_CC);
      ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G_CC) ]

let yukawa =
  [ ((M (U (-3)), O H, M (U 3)), FBF (1, Psibar, S, Psi), G_Htt);
    ((M (D (-3)), O H, M (D 3)), FBF (1, Psibar, S, Psi), G_Hbb);
    ((M (U (-2)), O H, M (U 2)), FBF (1, Psibar, S, Psi), G_Hcc);
    ((M (L (-2)), O H, M (L 2)), FBF (1, Psibar, S, Psi), G_Hmm);
    ((M (L (-3)), O H, M (L 3)), FBF (1, Psibar, S, Psi), G_Htautau) ]

let tgc ((g1, g2, g3), t, c) = ((G g1, G g2, G g3), t, c)

let triple_gauge =
  List.map tgc

```

```

[ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I-Q-W);
  ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I-G-ZWW);
  ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I-Gs) ]

let qgc ((g1, g2, g3, g4), t, c) = ((G g1, G g2, G g3, G g4), t, c)

let gauge4 = Vector4 [(2, C-13-42); (-1, C-12-34); (-1, C-14-23)]
let minus_gauge4 = Vector4 [(-2, C-13-42); (1, C-12-34); (1, C-14-23)]
let quartic_gauge =
  List.map qgc
    [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
      (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
      (Wm, Z, Wp, Ga), minus_gauge4, G_AZWW;
      (Wm, Ga, Wp, Ga), minus_gauge4, G_AAWW;
      (Gl, Gl, Gl, Gl), gauge4, G2]

let gauge_higgs =
  [ ((O H, G Wp, G Wm), Scalar_Vector_Vector 1, G_HWW);
    ((O H, G Z, G Z), Scalar_Vector_Vector 1, G_HZZ) ]

let gauge_higgs4 =
  [ (O H, O H, G Wp, G Wm), Scalar2_Vector2 1, G_HHWW;
    (O H, O H, G Z, G Z), Scalar2_Vector2 1, G_HHZZ ]

let higgs =
  [ (O H, O H, O H), Scalar_Scalar_Scalar 1, G_H3 ]

let higgs4 =
  [ (O H, O H, O H, O H), Scalar4 1, G_H4 ]

let anomaly_higgs =
  []
  (* (O H, G Ga, G Ga), Dim5_Scalar_Gauge2 1, G_HGaGa; (O H, G Ga, G Z), Dim5_Scalar_Gauge2 1,
  *)

let goldstone_vertices =
  [ ((O Phi0, G Wm, G Wp), Scalar_Vector_Vector 1, I-G-ZWW);
    ((O Phi0, G Ga, G Wm), Scalar_Vector_Vector 1, I-Q-W);
    ((O Phi0, G Z, G Wm), Scalar_Vector_Vector 1, I-G-ZWW);
    ((O Phim, G Wp, G Ga), Scalar_Vector_Vector 1, I-Q-W);
    ((O Phim, G Wp, G Z), Scalar_Vector_Vector 1, I-G-ZWW) ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1; 2; 3] @
   ThoList.flatmap color_currents [1; 2; 3] @
   ThoList.flatmap neutral_currents [1; 2; 3] @
   ThoList.flatmap charged_currents [1; 2; 3] @
   yukawa @ triple_gauge @ gauge_higgs @ higgs @
   anomaly_higgs @ goldstone_vertices)

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4

let vertices () = (vertices3, vertices4, [])

let table = F.of_vertices (vertices ())

```

```

let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))
| "numu" → M (N 2) | "numubar" → M (N (-2))
| "nutau" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "g" | "gl" → G Gl
| "A" → G Ga | "Z" | "Z0" → G Z
| "W+" → G Wp | "W-" → G Wm
| "H" → O H
| _ → invalid_arg "Modellib_BSM.Template.flavor_of_string"

let flavor_to_string = function
| M f →
  begin match f with
  | L 1 → "e-" | L (-1) → "e+"
  | L 2 → "mu-" | L (-2) → "mu+"
  | L 3 → "tau-" | L (-3) → "tau+"
  | L _ → invalid_arg
    "Modellib_BSM.Template.flavor_to_string:␣invalid␣lepton"
  | N 1 → "nue" | N (-1) → "nuebar"
  | N 2 → "numu" | N (-2) → "numubar"
  | N 3 → "nutau" | N (-3) → "nutaubar"
  | N _ → invalid_arg
    "Modellib_BSM.Template.flavor_to_string:␣invalid␣neutrino"
  | U 1 → "u" | U (-1) → "ubar"
  | U 2 → "c" | U (-2) → "cbar"
  | U 3 → "t" | U (-3) → "tbar"
  | U _ → invalid_arg
    "Modellib_BSM.Template.flavor_to_string:␣invalid␣up␣type␣quark"
  | D 1 → "d" | D (-1) → "dbar"
  | D 2 → "s" | D (-2) → "sbar"
  | D 3 → "b" | D (-3) → "bbar"
  | D _ → invalid_arg
    "Modellib_BSM.Template.flavor_to_string:␣invalid␣down␣type␣quark"
  end
| G f →
  begin match f with
  | Gl → "g"

```

```

|  $Ga \rightarrow "A" \mid Z \rightarrow "Z"$ 
|  $Wp \rightarrow "W+" \mid Wm \rightarrow "W-"$ 
end
|  $Of \rightarrow$ 
  begin match  $f$  with
  |  $Phip \rightarrow "phi+" \mid Phim \rightarrow "phi-" \mid Phi0 \rightarrow "phi0"$ 
  |  $H \rightarrow "H"$ 
  end
let flavor_to_TeX = function
|  $Mf \rightarrow$ 
  begin match  $f$  with
  |  $L1 \rightarrow "e^-" \mid L(-1) \rightarrow "e^+" \mid$ 
  |  $L2 \rightarrow "\\mu^-" \mid L(-2) \rightarrow "\\mu^+" \mid$ 
  |  $L3 \rightarrow "\\tau^-" \mid L(-3) \rightarrow "\\tau^+" \mid$ 
  |  $L\_ \rightarrow invalid\_arg$ 
  |  $N1 \rightarrow "\\nu_e" \mid N(-1) \rightarrow "\\bar{\\nu}_e"$ 
  |  $N2 \rightarrow "\\nu_{\\mu}" \mid N(-2) \rightarrow "\\bar{\\nu}_{\\mu}"$ 
  |  $N3 \rightarrow "\\nu_{\\tau}" \mid N(-3) \rightarrow "\\bar{\\nu}_{\\tau}"$ 
  |  $N\_ \rightarrow invalid\_arg$ 
  |  $U1 \rightarrow "u" \mid U(-1) \rightarrow "\\bar{u}"$ 
  |  $U2 \rightarrow "c" \mid U(-2) \rightarrow "\\bar{c}"$ 
  |  $U3 \rightarrow "t" \mid U(-3) \rightarrow "\\bar{t}"$ 
  |  $U\_ \rightarrow invalid\_arg$ 
  |  $D1 \rightarrow "d" \mid D(-1) \rightarrow "\\bar{d}"$ 
  |  $D2 \rightarrow "s" \mid D(-2) \rightarrow "\\bar{s}"$ 
  |  $D3 \rightarrow "b" \mid D(-3) \rightarrow "\\bar{b}"$ 
  |  $D\_ \rightarrow invalid\_arg$ 
  |  $Gf \rightarrow$ 
    begin match  $f$  with
    |  $Gl \rightarrow "g"$ 
    |  $Ga \rightarrow "\\gamma" \mid Z \rightarrow "Z"$ 
    |  $Wp \rightarrow "W^+" \mid Wm \rightarrow "W^-"$ 
    end
  |  $Of \rightarrow$ 
    begin match  $f$  with
    |  $Phip \rightarrow "\\phi^+" \mid Phim \rightarrow "\\phi^-"$ 
    |  $Phi0 \rightarrow "\\phi^0"$ 
    |  $H \rightarrow "H"$ 
    end
  |  $Mf \rightarrow$ 
    begin match  $f$  with
    |  $L n$  when  $n > 0 \rightarrow "1" ^ {string\_of\_int\ n}$ 
    |  $L n \rightarrow "1" ^ {string\_of\_int\ (abs\ n)} ^ "b"$ 

```

```

| N n when n > 0 → "n" ^ string_of_int n
| N n → "n" ^ string_of_int (abs n) ^ "b"
| U n when n > 0 → "u" ^ string_of_int n
| U n → "u" ^ string_of_int (abs n) ^ "b"
| D n when n > 0 → "d" ^ string_of_int n
| D n → "d" ^ string_of_int (abs n) ^ "b"
end
| G f →
  begin match f with
  | Gl → "gl"
  | Ga → "a" | Z → "z"
  | Wp → "wp" | Wm → "wm"
  end
| O f →
  begin match f with
  | Phip → "pp" | Phim → "pm" | Phi0 → "p0"
  | H → "h"
  end
let pdg = function
| M f →
  begin match f with
  | L n when n > 0 → 9 + 2 × n
  | L n → - 9 + 2 × n
  | N n when n > 0 → 10 + 2 × n
  | N n → - 10 + 2 × n
  | U n when n > 0 → 2 × n
  | U n → 2 × n
  | D n when n > 0 → - 1 + 2 × n
  | D n → 1 + 2 × n
  end
| G f →
  begin match f with
  | Gl → 21
  | Ga → 22 | Z → 23
  | Wp → 24 | Wm → (-24)
  end
| O f →
  begin match f with
  | Phip | Phim → 27 | Phi0 → 26
  | H → 25
  end
let mass_symbol f =
  "mass(" ^ string_of_int (abs (pdg f)) ^ ")"
let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"
let constant_symbol = function
| Unit → "unit" | Pi → "PI"

```

```

| Alpha_QED → "alpha" | E → "e" | G_weak → "g" | Vev →
"vev"
| Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
| Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdwn"
| G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
| G_NC_up → "gncup" | G_NC_down → "gncdwn"
| G_CC → "gcc"
| I_Q_W → "iqw" | I_G_ZWW → "igzww"
| G_WWWW → "gw4" | G_ZZWW → "gzzww"
| G_AZWW → "gazww" | G_AAWW → "gaaww"
| G_HWW → "ghww" | G_HZZ → "ghzz"
| G_HHWW → "ghhww" | G_HHZZ → "ghhzz"
| G_Htt → "ghtt" | G_Hbb → "ghbb"
| G_Htautau → "ghtautau" | G_Hcc → "ghcc" | G_Hmm →
"ghmm"
| G_HGaZ → "ghgaz" | G_HGaGa → "ghgaga" | G_Hgg →
"ghgg"
| G_H3 → "gh3" | G_H4 → "gh4"
| Gs → "gs" | I_Gs → "igs" | G2 → "gs**2"
| Mass f → "mass" ^ flavor_symbol f
| Width f → "width" ^ flavor_symbol f
end

```

13.6.2 Three-Site Higgsless Model

```

module type Threeshl_options =
  sig
    val include_ckm : bool
    val include_hf : bool
    val diet : bool
  end

module Threeshl_no_ckm : Threeshl_options =
  struct
    let include_ckm = false
    let include_hf = true
    let diet = false
  end

module Threeshl_ckm : Threeshl_options =
  struct
    let include_ckm = true
    let include_hf = true
    let diet = false
  end

module Threeshl_no_ckm_no_hf : Threeshl_options =
  struct

```



```

    let include_ckm = false
    let include_hf = false
    let diet = false
  end

  module Threeshl_ckm_no_hf : Threeshl_options =
    struct
      let include_ckm = true
      let include_hf = false
      let diet = false
    end

  module Threeshl_diet_no_hf : Threeshl_options =
    struct
      let include_ckm = false
      let include_hf = false
      let diet = true
    end

  module Threeshl_diet : Threeshl_options =
    struct
      let include_ckm = false
      let include_hf = true
      let diet = true
    end
end

```

We use one generic implementation of the model and implement different features via option modules given to a functor

```

module Threeshl (Module_options : Threeshl_options) =
  struct
    open Coupling

    let modname = "Modellib_BSM.Threeshl"

    let rCS =
    let renderbool = function true → "true" | false → "false"
    in RCS.rename rCS_file "Modellib_BSM.Threeshl"
      ["Three-Site_Higgsless_Model," ^
        "flavor_mixing:" ^ (renderbool Module_options.include_ckm) ^
        ",heavy_fermions:" ^ (renderbool Module_options.include_hf) ^
        ",reduced_set_of_couplings:" ^ (renderbool Module_options.diet)
      ]
  end

```

Shamelessly stolen from *Modellib.SM3*, but with no support for fudged width yet

```
let default_width = ref Timelike
```

If this flag is set true, all gauge bosons are assumed to be massless and are assigned feynman gauge propagators. This in conjunction with the unbroken three site model is intended for checking gauge invariance via the ward identities.

```
let all_feynman = ref false
```

```

let options = Options.create [
  "constant_width", Arg.Unit (fun _ → default_width := Constant),
    "use_constant_width(also_in_t-channel)";
  "custom_width", Arg.String (fun x → default_width := Custom x),
    "use_custom_width";
  "cancel_widths", Arg.Unit (fun _ → default_width := Vanishing),
    "use_vanishing_width";
  "all_feynman", Arg.Unit (fun _ → all_feynman := true),
    "assign_feynman_gauge_propagators_to_all_gauge_bosons\n"
    ^ "\t(for checking the ward identities); use only if you *really* know\n"
    ^ "\twhat you are doing"]

```

The quantum numbers that are carried by the particles. *csign* is *not* the charge carried by the particle, but differentiates between particles (Pos) and antiparticles (Neg)

```

type kkmode = Light | Heavy
type generation = Gen0 | Gen1 | Gen2
type csign = Pos | Neg
type isospin = Iso_up | Iso_down

```

Necessary to represent the indices of the couplings defined in FORTRAN

```

type kk2 = Light2 | Heavy2 | Light_Heavy

```

Map the different types to the constants used in the FORTRAN module

```

let fspec_of_kkmode = function Light → "l_mode" | Heavy →
  "h_mode"
let fspec_of_kk2 = function
  Light2 → "l_mode" | Heavy2 → "h_mode" | Light_Heavy →
  "lh_mode"
let fspec_of_gen = function Gen0 → "gen_0" | Gen1 → "gen_1" |
  Gen2 → "gen_2"
let fspec_of_iso = function Iso_up → "iso_up" | Iso_down →
  "iso_down"

```

Covert the “charge sign” into a numeric sign (used e.g. in the determination of the MCID codes)

```

let int_of_csign = function Pos → 1 | Neg → -1

```

Convert the generation into an integer (dito)

```

let int_of_gen = function Gen0 → 1 | Gen1 → 2 | Gen2 → 3

```

The type *flavor* is implemented as a variant. Fermions are implemented as a variant differentiating between leptons and quarks (seemed the most natural way as this is also the way in which the FORTRAN code is structured). Bosons are implemented as a variant the differentiates between *W*, *Z* and *A*. All other quantum numbers that are required for identifying the particles are carried by the variant constructors.

```

type fermion =
  | Lepton of (kkmode × csign × generation × isospin)
  | Quark of (kkmode × csign × generation × isospin)

```

```

type boson =
  | W of (kkmode × csign)
  | Z of kkmode
  | A
  | G

```

```

type flavor = Fermion of fermion | Boson of boson

```

Helpers to construct particles from quantum numbers

```

let lepton kk cs gen iso = Lepton (kk, cs, gen, iso)
let quark kk cs gen iso = Quark (kk, cs, gen, iso)
let w kk cs = W (kk, cs)
let z kk = Z kk
let flavor_of_f x = Fermion x
let flavor_of_b x = Boson x

```

Map a list of functions to the list (partially) applied to a value

```

let revmap funs v = List.map (fun x → x v) funs

```

The same for a list of values; the result is flattened

```

let revmap2 funs vals = ThoList.flatmap (revmap funs) vals

```

Functions to loop the constructors over quantum numbers for list creation purposes

```

let loop_kk flist = revmap2 flist [Light; Heavy]
let loop_cs flist = revmap2 flist [Pos; Neg]
let loop_gen flist = revmap2 flist [Gen0; Gen1; Gen2]
let loop_iso flist = revmap2 flist [Iso-up; Iso-down]
let loop_kk2 flist = revmap2 flist [Light2; Heavy2; Light_Heavy]

```

Conditional looping over kk modes depending on whether to include heavy fermions

```

let cloop_kk flist = match Module_options.include_hf with
  | true → loop_kk flist
  | false → revmap flist Light
let cloop_kk2 flist = match Module_options.include_hf with
  | true → loop_kk2 flist
  | false → revmap flist Light2

```

Having defined the necessary helpers, the magic of currying makes building lists of particles as easy as nesting the loop functions in the correct order...

```

let all_leptons = loop_iso (loop_gen (loop_cs (cloop_kk [lepton] )))
let all_quarks = loop_iso (loop_gen (loop_cs (cloop_kk [quark] )))
let all_bosons = (loop_cs (loop_kk [w] )) @ [Z Light; Z Heavy; A; G]

```

Converts a flavor spec to the BCD identifier defined in the FORTRAN module. Splitting the function into two parts **prefix** and **rump** removes a lot of redundancy.

```

let bcdi_of_flavor =
let prefix = function
  | Fermion (Lepton (Heavy, -, -, -)) | Fermion (Quark (Heavy, -, -, -))

```

```

| Boson (W (Heavy, _)) | Boson (Z Heavy) → "h"
| _ → ""
in let rump = function
| Fermion (Lepton spec) → (match spec with
| (_, _, Gen0, Iso_up) → "nue"
| (_, _, Gen0, Iso_down) → "e"
| (_, _, Gen1, Iso_up) → "numu"
| (_, _, Gen1, Iso_down) → "mu"
| (_, _, Gen2, Iso_up) → "nutau"
| (_, _, Gen2, Iso_down) → "tau")
| Fermion (Quark spec) → (match spec with
| (_, _, Gen0, Iso_up) → "u"
| (_, _, Gen0, Iso_down) → "d"
| (_, _, Gen1, Iso_up) → "c"
| (_, _, Gen1, Iso_down) → "s"
| (_, _, Gen2, Iso_up) → "t"
| (_, _, Gen2, Iso_down) → "b")
| Boson (W _) → "w" | Boson (Z _) → "z"
| Boson A → invalid_arg (modname ^ ".bcd_of_flavor:_no_bcd_for_photon!")
| Boson G → invalid_arg (modname ^ ".bcd_of_flavor:_no_bcd_for_gluon!")
in function x → (prefix x) ^ (rump x) ^ "_bcd"

```

The function defined in the model signature which returns the colour representation of a particle

```

let color =
let quarkrep = function
| (_, Pos, _, _) → Color.SUN 3
| (_, Neg, _, _) → Color.SUN (-3)
in function
| Fermion (Quark x) → quarkrep x
| Boson G → Color.AdjSUN 3
| _ → Color.Singlet

```

Function for calculating the MCID code of a particle. Conventions have been chosen such that the heavy modes are identified by the same numbers as the light ones, prefixed with 99. This is supposedly in accord with the conventions for adding new particles to the list of MCID codes. This function is required by the signature.

```

let pdg =
let iso_delta = function Iso_down → 0 | Iso_up → 1
in let gen_delta = function Gen0 → 0 | Gen1 → 2 | Gen2 → 4
in let kk_delta = function Light → 0 | Heavy → 9900
in function
| Fermion (Lepton (kk, cs, gen, iso)) →
(int_of_csign cs) × (11 + (gen_delta gen) + (iso_delta iso) + (kk_delta kk))
| Fermion (Quark (kk, cs, gen, iso)) →
(int_of_csign cs) × (1 + (gen_delta gen) + (iso_delta iso) + (kk_delta kk))
| Boson (W (kk, cs)) → (int_of_csign cs) × (24 + (kk_delta kk))
| Boson (Z kk) → 23 + (kk_delta kk)
| Boson A → 22

```

```
| Boson G → 21
```

Returns the lorentz representation of a particle; required by the signature.

```
let lorentz =
let spinor = function
| (_, Pos, _, _) → Spinor
| (_, Neg, _, _) → ConjSpinor
in function
| Fermion (Lepton x) | Fermion (Quark x) → spinor x
| Boson (W _) | Boson (Z _) → Massive_Vector
| Boson A → Vector
| Boson G → Vector
```

O'Mega supports models that allow different gauges; however, we only implement unitary gauge and therefore stub this (SM3 does the same thing). The `gauge` type as well as `gauge_symbol` are required by the signature.

```
type gauge = unit
let gauge_symbol () =
  failwith (modname ^ ".gauge_symbol:␣internal␣error")
```

Returns the propagator for a given particle type. Required by signature.

```
let propagator =
let spinorprop = function
| (_, Pos, _, _) → Prop_Spinor
| (_, Neg, _, _) → Prop_ConjSpinor
in function
| Fermion (Lepton x) | Fermion (Quark x) → spinorprop x
| Boson (W _) | Boson (Z _) →
  (match !all_feynman with false → Prop_Unitarity | true →
   Prop_Feynman)
| Boson A → Prop_Feynman
| Boson G → Prop_Feynman
```

Return the width of a particle, required by signature.

TODO: Refine such that stable particles always are treated via vanishing width, as this might speed up the generated code a bit.

```
let width _ = !default_width
```

Returns the conjugate particle; required by signature.

```
let conjugate =
let conj_csign = function
| Pos → Neg
| Neg → Pos
in function
| Fermion (Lepton (kk, cs, gen, iso)) → Fermion (Lepton (kk, conj_csign cs, gen, iso))
| Fermion (Quark (kk, cs, gen, iso)) → Fermion (Quark (kk, conj_csign cs, gen, iso))
| Boson (W (kk, cs)) → Boson (W (kk, conj_csign cs))
| x → x
```

Tells the diagram generator whether a particle is a fermion, a conjugate fermion or a boson. Required by signature

```

let fermion = function
  | Fermion (Lepton (_, cs, _, _)) | Fermion (Quark (_, cs, _, _)) →
int_of_csign cs
  | Boson _ → 0

```

Charges are: charge, lepton number, baryon number, generation. Required by signature

```

module Ch = Charges.QQ
let ( // ) = Algebra.Small_Rational.make

let qn_charge = function
  | Boson b → (match b with
    | W (_, c) → (int_of_csign (c)) // 1
    | _ → 0//1)
  | Fermion f → (match f with
    | Lepton (_, c, _, Iso_up) → 0//1
    | Lepton (_, c, _, Iso_down) → (-1 × int_of_csign (c)) // 1
    | Quark (_, c, _, Iso_up) → (2 × int_of_csign (c)) // 3
    | Quark (_, c, _, Iso_down) → (-1 × int_of_csign (c)) // 3)

let qn_lepton = function
  | Fermion (Lepton (_, c, _, _)) → int_of_csign (c) // 1
  | _ → 0//1

let qn_baryon = function
  | Fermion (Quark (_, c, _, _)) → int_of_csign (c) // 1
  | _ → 0//1

```

Generation is conditional: if we enable the nontrivial CKM matrix, all particles carry generation 0; 0; 0

```

let qn_generation x =
  let qn cs gen =
    let c = int_of_csign (cs) in
    match gen with
    | Gen0 → [c//1; 0//1; 0//1]
    | Gen1 → [0//1; c//1; 0//1]
    | Gen2 → [0//1; 0//1; c//1]
  in
  if Module_options.include_ckm then
    [0//1; 0//1; 0//1]
  else
    match x with
    | Fermion (Lepton (_, c, g, _)) → qn c g
    | Fermion (Quark (_, c, g, _)) → qn c g
    | _ → [0//1; 0//1; 0//1]

let charges x =
  [qn_charge x; qn_lepton x; qn_baryon x] @ (qn_generation x)

```

A variant to represent the different coupling constants, choosen to mimic the FORTRAN part. Required by signature.

```

type constant =

```

```

      | G_a_lep | G_a_quark of isospin
      | G_auw | G_aauw
      | G_w_lep of (kkmode × kkmode × generation × kkmode ×
generation)
      | G_w_quark of (kkmode × kkmode × generation × kkmode ×
generation)
      | G_z_lep of (kkmode × kk2 × generation × isospin)
      | G_z_quark of (kkmode × kk2 × generation × isospin)
      | G_wwz of (kk2 × kkmode)
      | G_wwzz of (kk2 × kk2)
      | G_wwza of (kk2 × kkmode)
      | G_www of int
      | G_s
      | IG_s
      | G_s2

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int

let orders = function
  | _ → (0,0)

```

Functions for the construction of constants from indices

```

let g_a_quark x = G_a_quark x
let g_w_lep kk1 kk2 gen1 kk3 gen2 = G_w_lep (kk1, kk2, gen1, kk3, gen2)
let g_w_quark kk1 kk2 gen1 kk3 gen2 = G_w_quark (kk1, kk2, gen1, kk3, gen2)
let g_z_lep kk1 kk2 gen iso = G_z_lep (kk1, kk2, gen, iso)
let g_z_quark kk1 kk2 gen iso = G_z_quark (kk1, kk2, gen, iso)
let g_wwz kk1 kk2 = G_wwz (kk1, kk2)
let g_wwzz kk1 kk2 = G_wwzz (kk1, kk2)
let g_wwza kk1 kk2 = G_wwza (kk1, kk2)
let g_www nhw = if (nhw ≥ 0) ∧ (nhw ≤ 4) then G_www nhw
  else failwith (modname ^ ".g_www: invalid integer, very bad")

```

Build a list of the different constants

```

let clist = [G_a_lep; G_auw; G_aauw] @ (loop_iso [g_a_quark]) @
  (loop_gen (cloop_kk (loop_gen (cloop_kk (loop_kk [g_w_lep] ))))) @
  (loop_gen (cloop_kk (loop_gen (cloop_kk (loop_kk [g_w_quark] ))))) @
  (loop_iso (loop_gen (cloop_kk2 (loop_kk [g_z_lep] )))) @
  (loop_iso (loop_gen (cloop_kk2 (loop_kk [g_z_quark] )))) @
  (loop_kk (loop_kk2 [g_wwz] )) @ (loop_kk2 (loop_kk2 [g_wwzz] )) @
  (loop_kk (loop_kk2 [g_wwza] )) @ (List.map g_www [0; 1; 2; 3; 4])

```

Maximum number of lines meeting at a vertex, required by signature.

```

let max_degree () = 4

```

Transform a pair of kk identifiers into a kk2 identifier

```

let get_kk2 = function (Light, Light) → Light2 | (Heavy, Heavy) →
Heavy2
  | (Light, Heavy) | (Heavy, Light) → Light_Heavy

```

Flip isospin

```
let conj_iso = function Iso_up → Iso_down | Iso_down → Iso_up
```

Below, lists of couplings are generated which ultimately are joined into a list of all couplings in the model. The generated lists can be viewed using the `dump.ml` script in the O'Mega toplevel directory.

The individual couplings are defined as 5-tupels resp. 6-tupels consisting in this order of the particles meeting at the vertex, the coupling type (see `couplings.ml`) and the coupling constant.

List of llA type vertices

```
let vertices_all =
let vgen kk gen =
  ((Fermion (Lepton (kk, Neg, gen, Iso_down)), Boson A, Fermion (Lepton (kk, Pos, gen,
    Iso_down))), FBF(1, Psibar, V, Psi), G_a_lep)
in loop_gen (cloop_kk [vgen])
```

List of qqA type vertices

```
let vertices_aqq =
let vgen kk gen iso =
  ((Fermion (Quark (kk, Neg, gen, iso)), Boson A, Fermion (Quark (kk, Pos, gen,
    iso))), FBF(1, Psibar, V, Psi), G_a_quark iso)
in loop_iso (loop_gen (cloop_kk [vgen]))
```

List of νlW type vertices

```
let vertices_wll =
let vgen kkw kk_f kk_fbar iso_f gen =
  ((Fermion (Lepton (kk_fbar, Neg, gen, conj_iso iso_f)),
    Boson (W (kkw, (match iso_f with Iso_up → Neg | _ →
Pos))),
    Fermion (Lepton (kk_f, Pos, gen, iso_f))),
    FBF (1, Psibar, VA2, Psi),
    G_w_lep (kkw, (match iso_f with Iso_up → kk_f | _ →
kk_fbar), gen,
    (match iso_f with Iso_up → kk_fbar | _ → kk_f), gen) )
in loop_gen (loop_iso (cloop_kk (cloop_kk (loop_kk [vgen] ))))
```

The same list, but without couplings between the W' and light fermions

```
let vertices_wll_diet =
let filter = function
  | ((Fermion (Lepton (Light, _, _, _)), Boson (W (Heavy, _)),
    Fermion (Lepton (Light, _, _, _))), _, _) → false
  | _ → true
in List.filter filter vertices_wll
```

List of udW type vertices, flavor-diagonal

```
let vertices_wqq_no_ckm =
let vgen kkw kk_f kk_fbar iso_f gen =
  ((Fermion (Quark (kk_fbar, Neg, gen, conj_iso iso_f)),
    Boson (W (kkw, (match iso_f with Iso_up → Neg | _ →
Pos))),
```



```

      Fermion (Quark (kk_f, Pos, gen, iso_f))),
      FBF (1, Psibar, VA2, Psi),
      G_w_quark (kkw, (match iso_f with Iso-up → kk_f | _ →
kk_fbar), gen,
      (match iso_f with Iso-up → kk_fbar | _ → kk_f), gen) )
in loop_gen (loop_iso (cloop_kk (cloop_kk (loop_kk [vgen] ))))

```

The same list, but without couplings between the W' and the first two generations of quarks

```

let vertices_wqq_no_ckm_diet =
let filter = function
  | ((Fermion (Quark (Light, _, gen, _)), Boson (W (Heavy, _)),
      Fermion (Quark (Light, _, _, _))), _, _) →
      (match gen with Gen2 → true | _ → false)
  | _ → true
in List.filter filter vertices_wqq_no_ckm

List of udW type vertices, including non flavor-diagonal couplings

let vertices_wqq =
let vgen kkw kk_f gen_f kk_fbar gen_fbar iso_f =
  ((Fermion (Quark (kk_fbar, Neg, gen_fbar, conj_iso iso_f)),
      Boson (W (kkw, (match iso_f with Iso-up → Neg | _ →
Pos))),
      Fermion (Quark (kk_f, Pos, gen_f, iso_f))),
      FBF (1, Psibar, VA2, Psi),
      G_w_quark (match iso_f with
        | Iso-up → (kkw, kk_f, gen_f, kk_fbar, gen_fbar)
        | Iso-down → (kkw, kk_fbar, gen_fbar, kk_f, gen_f)))
in loop_iso (loop_gen (cloop_kk (loop_gen (cloop_kk (loop_kk [vgen] )))))

```

List of llZ / $\nu\nu Z$ type vertices

```

let vertices_zll =
let vgen kkz kk_f kk_fbar gen iso =
  ((Fermion (Lepton (kk_fbar, Neg, gen, iso)), Boson (Z kkz),
      Fermion (Lepton (kk_f, Pos, gen, iso))),
      FBF (1, Psibar, VA2, Psi),
      G_z_lep (kkz, get_kk2 (kk_f, kk_fbar), gen, iso))
in loop_iso (loop_gen (cloop_kk (cloop_kk (loop_kk [vgen] ))))

```

List of qqZ type vertices

```

let vertices_zqq =
let vgen kkz kk_f kk_fbar gen iso =
  ((Fermion (Quark (kk_fbar, Neg, gen, iso)), Boson (Z kkz),
      Fermion (Quark (kk_f, Pos, gen, iso))),
      FBF (1, Psibar, VA2, Psi),
      G_z_quark (kkz, get_kk2 (kk_f, kk_fbar), gen, iso))
in loop_iso (loop_gen (cloop_kk (cloop_kk (loop_kk [vgen] ))))

```

$gq\bar{q}$

```

let vertices_gqq =

```

```

let vgen kk gen iso =
  ((Fermion (Quark (kk, Neg, gen, iso)), Boson G, Fermion (Quark (kk, Pos, gen, iso))),
   FBF (1, Psibar, V, Psi), G_s)
in loop_iso (loop_gen (cloop_kk [vgen]))

AWW

let vertices_aww =
let vgen kk =
  ((Boson A, Boson (W (kk, Pos)), Boson (W (kk, Neg))), Gauge_Gauge_Gauge 1, G_aww)
in loop_kk [vgen]

ZWW

let vertices_zww =
let vgen kkz kkwp kkwm =
  ((Boson (Z kkz), Boson (W (kkwp, Pos)), Boson (W (kkwm, Neg))), Gauge_Gauge_Gauge 1,
   G_wwz (get_kk2 (kkwp, kkwm), kkz))
in loop_kk (loop_kk (loop_kk [vgen]))

ggg

let vertices_ggg = [(Boson G, Boson G, Boson G), Gauge_Gauge_Gauge (-1), IG_s]

Stolen from Modellib.SM; the signs seem to be OK. See couplings.ml
for more docs.

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]

AAWW

let vertices_aaww =
let vgen kk =
  ((Boson A, Boson (W (kk, Pos)), Boson A, Boson (W (kk, Neg))), minus_gauge4, G_aaww)
in loop_kk [vgen]

WWZZ

let vertices_wwzz =
let vgen kkwp kkwm kk2z =
  ((Boson (Z (match kk2z with Heavy2 → Heavy | Light2 |
Light_Heavy → Light)),
   Boson (W (kkwp, Pos)),
   Boson (Z (match kk2z with Heavy2 | Light_Heavy → Heavy |
Light2 → Light)),
   Boson (W (kkwm, Neg))), minus_gauge4, G_wwzz (get_kk2 (kkwp, kkwm), kk2z))
in loop_kk2 (loop_kk (loop_kk [vgen]))

WWZA

let vertices_wwza =
let vgen kkwp kkwm kkz =
  ((Boson A, Boson (W (kkwp, Pos)), Boson (Z kkz), Boson (W (kkwm, Neg))),
   minus_gauge4, G_wwza (get_kk2 (kkwp, kkwm), kkz))
in loop_kk (loop_kk (loop_kk [vgen]))

WWWW

```

```

let vertices_www =
let count = function Light2 → 0 | Light_Heavy → 1 | Heavy2 → 2
in let vgen kk2wp kk2wm =
  ((Boson (W ((match kk2wp with Heavy2 → Heavy | Light2 |
    Light_Heavy → Light), Pos)),
    Boson (W ((match kk2wm with Heavy2 → Heavy | Light2 |
    Light_Heavy → Light), Neg)),
    Boson (W ((match kk2wp with Heavy2 | Light_Heavy → Heavy |
    Light2 → Light), Pos)),
    Boson (W ((match kk2wm with Heavy2 | Light_Heavy →
    Heavy | Light2 → Light), Neg))),
    gauge4, G_www ((count kk2wp) + (count kk2wm)))
in loop_kk2 (loop_kk2 [vgen])

gggg

let vertices_gggg = [(Boson G, Boson G, Boson G, Boson G), gauge4, G_s2]

```

The list of couplings is transformed into the fusion lists required by the generator by the `Model.Fusions` functor.

This is copy& paste from the other models; check again with Thorsten if it is correct

```

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end )

```

Not sure yet whether `F.fusex` also creates the conjugate vertices; by looking at the implementation of the other models, I assume it doesn't. Still, better ask Thorsten to be sure!!!

Update: Still didn't get to ask, but since the results are consistent, I suspect my assertion is correct.

The stuff below is required by the signature.

```

let vertices () = (vertices_all @ vertices_aqq @
  (match Module_options.diet with
    | false → vertices_wll
    | true → vertices_wll_diet) @
  (match (Module_options.include_ckm, Module_options.diet) with
    | (true, false) → vertices_wqq
    | (false, false) → vertices_wqq_no_ckm
    | (false, true) → vertices_wqq_no_ckm_diet
    | (true, true) → raise (Failure
      ("Modules4.Threesh1.vertices:_CKM_matrix_together_with_option_diet_is_not" ^
        "_implemented_yet!"))) @
  vertices_zll @ vertices_zqq @ vertices_auw @ vertices_zww @ vertices_gqq @ vertices_ggg,
  vertices_aauw @ vertices_wvzz @ vertices_wvza @ vertices_www @ vertices_gggg
  , [])
let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table

```

```
let fuse3 = F.fuse3 table
let fuse = F.fuse table
```

A function that returns a list of a flavours known to the model, required by the signature.

```
let flavors () = (List.map flavor_of_f (all_leptons @ all_quarks)) @
  (List.map flavor_of_b all_bosons)
```

ditto, external flavours, also required.

```
let external_flavors () = [
  "light_leptons", List.map flavor_of_f (loop_iso (loop_gen (loop_cs [lepton Light])));
  "light_quarks", List.map flavor_of_f (loop_iso (loop_gen (loop_cs [quark Light])));
  "light_gauge_bosons", List.map flavor_of_b [W (Light, Pos); W (Light, Neg); Z Light; A];
  "heavy_gauge_bosons", List.map flavor_of_b [W (Heavy, Pos); W (Heavy, Neg); Z Heavy] @
  (match Module_options.include_hf with
  | true → [
    "heavy_leptons", List.map flavor_of_f (loop_iso (loop_gen (loop_cs [lepton Heavy])));
    "heavy_quarks", List.map flavor_of_f (loop_iso (loop_gen (loop_cs [quark Heavy])))]
  | false → []) @ ["gluons", [Boson G]]
```

Which of the particles are goldstones? → none. Required by the signature.

```
let goldstone x = None
```

This is wrong but handy for debugging the constant identifier generation via -params. Usually, this function would return a record consisting of the parameters as well as expression for the dependent quantities that can be used to generate FORTRAN code for calculating them. However, we have a separate module for the threeshl, so we can abuse this for debugging. Required by signature.

```
let parameters () = {input = List.map (fun x → (x, 0.)) clist;
  derived = []; derived_arrays = []}
```

Convert a flavour into a ID string with which it will be referred by the user interface of the compiled generator. Required by signature

```
let flavor_to_string =
let prefix = function
  | Fermion (Lepton (Heavy, -, -, -)) | Fermion (Quark (Heavy, -, -, -))
  | Boson (W (Heavy, -)) | Boson (Z Heavy) → "H"
  | _ → ""
in let postfix = function
  | Fermion (Lepton (-, cs, -, Iso_down)) → (match cs with Pos →
  "-" | Neg → "+")
  | Fermion (Quark (-, Neg, -, -)) | Fermion (Lepton (-, Neg, -, Iso_up)) →
  "bar"
  | Boson (W (-, cs)) → (match cs with Pos → "+" | Neg → "-")
  | _ → ""
in let rump = function
  | Fermion (Lepton desc) → (match desc with
  | (-, -, Gen0, Iso_up) → "nue"
```

```

| (-, -, Gen0, Iso_down) → "e"
| (-, -, Gen1, Iso_up) → "numu"
| (-, -, Gen1, Iso_down) → "mu"
| (-, -, Gen2, Iso_up) → "nutau"
| (-, -, Gen2, Iso_down) → "tau")
| Fermion (Quark desc) → (match desc with
| (-, -, Gen0, Iso_up) → "u"
| (-, -, Gen0, Iso_down) → "d"
| (-, -, Gen1, Iso_up) → "c"
| (-, -, Gen1, Iso_down) → "s"
| (-, -, Gen2, Iso_up) → "t"
| (-, -, Gen2, Iso_down) → "b")
| Boson (W _) → "W" | Boson (Z _) → "Z" | Boson A → "A" |
Boson G → "g1"
in function x → (prefix x) ^ (rump x) ^ (postfix x)

```

Conversion of the ID string into a particle flavor. Instead of going through all cases again, we generate a “dictionary” of flavor / ID pairs which we use to identify the correct flavor. Required by signature.

```

let flavor_of_string x =
let dict = List.map (fun x → (x, flavor_to_string x)) (flavors ())
in let get_ident = function (x, _) → x
in try
  get_ident (List.find (fun (_, y) → (x = y)) dict)
with
  Not_found → (match x with
  | "g" → Boson G
  | _ → invalid_arg (modname ^ ".flavor_of_string")
  )

```

Converts a flavor into a symbol used as identification in the generated FORTRAN code (has to comply to the conventions of valid FORTRAN identifiers therefore). We stick to the same conventions as SM3, prefixing heavy modes with a H. Required by signature.

```

let flavor_symbol =
let prefix = function
| Fermion (Lepton (Heavy, -, -, -)) | Fermion (Quark (Heavy, -, -, -))
| Boson (W (Heavy, -)) | Boson (Z Heavy) → "H"
| _ → ""
in let postfix = function
| Fermion (Lepton (_, Neg, -, -)) | Fermion (Quark (_, Neg, -, -)) →
"b"
| _ → ""
in let rump = function
| Fermion spec → (match spec with
| Lepton (_, -, gen, Iso_up) → "n" ^ (string_of_int (int_of_gen gen))
| Lepton (_, -, gen, Iso_down) → "l" ^ (string_of_int (int_of_gen gen))
| Quark (_, -, gen, Iso_up) → "u" ^ (string_of_int (int_of_gen gen))
| Quark (_, -, gen, Iso_down) → "d" ^ (string_of_int (int_of_gen gen))
| Boson spec → (match spec with

```

```

      | W (_, Pos) → "wp" | W (_, Neg) → "wm"
      | Z _ → "z" | A → "a" | G → "g1" )
in function
  x → (prefix x) ^ (rump x) ^ (postfix x)

Generate TeX for a flavor

let flavor_to_TeX =
let bar x y = match x with Neg → "\\overline{" ^ y ^ "}" | Pos →
y
in let pm x y = match x with Neg → "{" ^ y ^ "}^+" | Pos →
"{ " ^ y ^ " }^- "
in let prime x y = match x with Light → y | Heavy → "{" ^ y ^ "}^\\prime"
in function
  | Fermion (Lepton desc) → (match desc with
    | (kk, cs, gen, Iso_up) → prime kk (bar cs (match gen with
      | Gen0 → "\\nu_e"
      | Gen1 → "\\nu_\\mu"
      | Gen2 → "\\nu_\\tau"))
    | (kk, cs, gen, Iso_down) → prime kk (pm cs (match gen with
      | Gen0 → "e" | Gen1 → "\\mu" | Gen2 → "\\tau")))
  | Fermion (Quark (kk, cs, gen, iso)) → prime kk (bar cs (match (gen, iso) with
    | (Gen0, Iso_up) → "u"
    | (Gen0, Iso_down) → "d"
    | (Gen1, Iso_up) → "c"
    | (Gen1, Iso_down) → "s"
    | (Gen2, Iso_up) → "t"
    | (Gen2, Iso_down) → "b"))
  | Boson spec → (match spec with
    | W (kk, cs) → prime kk (pm (match cs with Pos → Neg |
Neg → Pos) "W")
    | Z kk → prime kk "Z"
    | A → "A" | G → "g")

```

Returns the string referring to the particle mass in the generated FORTRAN code. Required by signature.

```

let mass_symbol = function
  | Boson A | Boson G → "0._default"
  | x → "mass_array(" ^ (bcdi_of_flavor x) ^ ")"

```

Dito, for width. Required by signature.

```

let width_symbol = function
  | Boson A | Boson G → "0._default"
  | x → "width_array(" ^ (bcdi_of_flavor x) ^ ")"

```

Determines the string referring to a coupling constant in the generated FORTRAN code. Required by signature.

```

let constant_symbol =
let c = ",_□"
in let g_w_ferm = function
  (kk1, kk2, gen1, kk3, gen2) →

```

```

      ":" ^ (fspec_of_kkmode kk1) ^ c ^ (fspec_of_kkmode kk2) ^ c ^ (fspec_of_gen gen1) ^ c ^
      (fspec_of_kkmode kk3) ^ c ^ (fspec_of_gen gen2)
in let g_z_ferm = function
  (kk1, kk2, gen, iso) →
    ":" ^ (fspec_of_kkmode kk1) ^ c ^ (fspec_of_kk2 kk2) ^ c ^ (fspec_of_gen gen) ^ c ^
    (fspec_of_iso iso)
in function
  | G_a_lep → "g_a_lep"
  | G_s → "g_s_norm"
  | IG_s → "ig_s_norm"
  | G_s2 → "g_s_norm2"
  | G_a_quark iso → "g_a_quark(" ^ (fspec_of_iso iso) ^ ")"
  | G_www → "ig_www"
  | G_aaww → "g_aaww"
  | G_w_lep spec → "g_w_lep_va(" ^ (g_w_ferm spec) ^ ")"
  | G_w_quark spec → "g_w_quark_va(" ^ (g_w_ferm spec) ^ ")"
  | G_z_lep spec → "g_z_lep_va(" ^ (g_z_ferm spec) ^ ")"
  | G_z_quark spec → "g_z_quark_va(" ^ (g_z_ferm spec) ^ ")"
  | G_wwz (kk1, kk2) → "ig_wwz(" ^ (fspec_of_kk2 kk1) ^ c ^
    (fspec_of_kkmode kk2) ^ ")"
  | G_wwzz (kk1, kk2) → "g_wwzz(" ^ (fspec_of_kk2 kk1) ^ c ^
    (fspec_of_kk2 kk2) ^ ")"
  | G_wwza (kk1, kk2) → "g_wwza(" ^ (fspec_of_kk2 kk1) ^ c ^
    (fspec_of_kkmode kk2) ^ ")"
  | G_www nhw → if (0 ≤ nhw) ∧ (nhw ≤ 4) then
    "g_www(" ^ (string_of_int nhw) ^ ")"
    else failwith "Modules4.Threeshl.constant_symbol: invalid int for G_www; very bad"
end

```

13.6.3 2HDM with and without non-trivial flavor structure

```

module type THDM_flags =
  sig
    val ckm_present : bool
  end

module THDM : THDM_flags =
  struct
    let ckm_present = false
  end

module THDM_CKM : THDM_flags =
  struct
    let ckm_present = true
  end

module TwoHiggsDoublet (Flags : THDM_flags) =
  struct
    let rcs = rcs_file
  end

```

```

open Coupling

let default_width = ref Timelike
let use_fudged_width = ref false

let options = Options.create
[ "constant_width", Arg.Unit (fun () → default_width := Constant),
  "use_constant_width_(also_in_t-channel)",
  "fudged_width", Arg.Set use_fudged_width,
  "use_fudge_factor_for_charge_particle_width",
  "custom_width", Arg.String (fun f → default_width := Custom f),
  "use_custom_width",
  "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
  "use_vanishing_width" ]

type matter_field = L of int | N of int | U of int | D of int
type gauge_boson = Ga | Wp | Wm | Z | Gl
type other = Phip | Phim | Phi0 | Hh | HA | HH | Hp | Hm
type flavor = M of matter_field | G of gauge_boson | O of other

let matter_field f = M f
let gauge_boson f = G f
let other f = O f

type field =
| Matter of matter_field
| Gauge of gauge_boson
| Other of other

let field = function
| M f → Matter f
| G f → Gauge f
| O f → Other f

type gauge = unit

let gauge_symbol () =
  failwith "Modellib_BSM.TwoHiggsDoublet.gauge_symbol: internal error"

let family n = List.map matter_field [ L n; N n; U n; D n ]

let external_flavors () =
[ "1st_Generation", ThoList.flatmap family [1; -1];
  "2nd_Generation", ThoList.flatmap family [2; -2];
  "3rd_Generation", ThoList.flatmap family [3; -3];
  "Gauge_Bosons", List.map gauge_boson [Ga; Z; Wp; Wm; Gl];
  "Higgs", List.map other [Hh; HH; HA; Hp; Hm];
  "Goldstone_Bosons", List.map other [Phip; Phim; Phi0] ]

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n =
  if n ≥ 0 then
    Spinor
  else
    ConjSpinor

```



```

let lorentz = function
| M f →
  begin match f with
  | L n → spinor n | N n → spinor n
  | U n → spinor n | D n → spinor n
  end
| G f →
  begin match f with
  | Ga | Gl → Vector
  | Wp | Wm | Z → Massive_Vector
  end
| O f → Scalar

let color = function
| M (U n) → Color.SUN (if n > 0 then 3 else -3)
| M (D n) → Color.SUN (if n > 0 then 3 else -3)
| G Gl → Color.AdjSUN 3
| - → Color.Singlet

let prop_spinor n =
  if n ≥ 0 then
    Prop_Spinor
  else
    Prop_ConjSpinor

let propagator = function
| M f →
  begin match f with
  | L n → prop_spinor n | N n → prop_spinor n
  | U n → prop_spinor n | D n → prop_spinor n
  end
| G f →
  begin match f with
  | Ga | Gl → Prop_Feynman
  | Wp | Wm | Z → Prop_Unitarity
  end
| O f →
  begin match f with
  | Phip | Phim | Phi0 → Only_Insertion
  | Hh | HH | HA | Hp | Hm → Prop_Scalar
  end
end

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    | G Wp | G Wm | M (U 3) | M (U (-3)) → Fudged
    | - → !default_width
  else
    !default_width

```

```

let goldstone = function
| G f →
  begin match f with
  | Wp → Some (O Phip, Coupling.Const 1)
  | Wm → Some (O Phim, Coupling.Const 1)
  | Z → Some (O Phi0, Coupling.Const 1)
  | _ → None
  end
| _ → None

let conjugate = function
| M f →
  M (begin match f with
  | L n → L (-n) | N n → N (-n)
  | U n → U (-n) | D n → D (-n)
  end)
| G f →
  G (begin match f with
  | Gl → Gl | Ga → Ga | Z → Z
  | Wp → Wm | Wm → Wp
  end)
| O f →
  O (begin match f with
  | Phip → Phim | Phim → Phip | Phi0 → Phi0
  | Hh → Hh | HH → HH | HA → HA
  | Hp → Hm | Hm → Hp
  end)

let fermion = function
| M f →
  begin match f with
  | L n → if n > 0 then 1 else -1
  | N n → if n > 0 then 1 else -1
  | U n → if n > 0 then 1 else -1
  | D n → if n > 0 then 1 else -1
  end
| G f →
  begin match f with
  | Gl | Ga | Z | Wp | Wm → 0
  end
| O _ → 0

```

Electrical charge, lepton number, baryon number. We could avoid the rationals altogether by multiplying the first and last by 3 ...

```

module Ch = Charges.QQ
let ( // ) = Algebra.Small_Rational.make

let generation' = function
| 1 → [ 1//1; 0//1; 0//1 ]
| 2 → [ 0//1; 1//1; 0//1 ]
| 3 → [ 0//1; 0//1; 1//1 ]
| -1 → [-1//1; 0//1; 0//1 ]

```

```

| - 2 → [ 0//1; - 1//1; 0//1]
| - 3 → [ 0//1; 0//1; - 1//1]
| n → invalid_arg ("Modellib_BSM.TwoHiggsDoublet.generation':␣" ^ string_of_int n)

let generation f =
  if Flags.ckm_present then
    []
  else
    match f with
    | M (L n | N n | U n | D n) → generation' n
    | G _ | O _ → [ 0//1; 0//1; 0//1]

let charge = function
| M f →
  begin match f with
  | L n → if n > 0 then -1//1 else 1//1
  | N n → 0//1
  | U n → if n > 0 then 2//3 else -2//3
  | D n → if n > 0 then -1//3 else 1//3
  end
| G f →
  begin match f with
  | Gl | Ga | Z → 0//1
  | Wp → 1//1
  | Wm → -1//1
  end
| O f →
  begin match f with
  | Hh | HH | HA | Phi0 → 0//1
  | Hp | Phip → 1//1
  | Hm | Phim → -1//1
  end

let lepton = function
| M f →
  begin match f with
  | L n | N n → if n > 0 then 1//1 else -1//1
  | U _ | D _ → 0//1
  end
| G _ | O _ → 0//1

let baryon = function
| M f →
  begin match f with
  | L _ | N _ → 0//1
  | U n | D n → if n > 0 then 1//1 else -1//1
  end
| G _ | O _ → 0//1

let charges f =
  [ charge f; lepton f; baryon f ] @ generation f

type constant =

```

```

| Unit | Pi | Alpha_QED | Sin2thw
| Sinthw | Costhw | E | G_weak | Vev
| Q_lepton | Q_up | Q_down | G_CC
| G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down
| I_Q_W | I_G_ZWW | I_G_WWW
| G_WWWW | G_ZZWW | G_AZWW | G_AAWW
| G_htt | G_hbb | G_hcc | G_hatautau | G_hmumu
| G_Htt | G_Hbb | G_Hcc | G_Hatautau | G_Hmumu
| I_G_Att | I_G_Abb | I_G_Acc | I_G_Atautau | I_G_Amumu
| G_Htb | G_Hcs | G_Htaunu | G_Hmunu
| Gs | I_Gs | G2
| G_AHpHm | G_ZHpHm | G_Zh1h2 | G_Zh1h3 | G_Zh2h3
| G_WpHmh1 | G_WpHmh2 | G_WpHmh3 | G_WmHph1 |
G_WmHph2
| G_WmHph3 | G_h1ZZ | G_h2ZZ | G_h3ZZ | G_h1WpWm |
G_h2WpWm
| G_h3WpWm | G_hhWpWm | G_hhZZ | G_HpHmAA |
G_HpHmZZ | G_HpHmAZ
| G_HpHmWpWm | G_h1HpAWm | G_h2HpAWm | G_h3HpAWm |
G_h1HpZWm
| G_h2HpZWm | G_h3HpZWm | G_h1HpAWmC | G_h2HpAWmC |
G_h3HpAWmC
| G_h1HpZWmC | G_h2HpZWmC | G_h3HpZWmC | G_h1HpHm |
G_h2HpHm | G_h3HpHm
| G_h111 | G_h112 | G_h113 | G_h221 | G_h222 | G_h223 |
G_h331 | G_h332
| G_h333 | G_h123 | G_HpHmHpHm | G_HpHm11 | G_HpHm12 |
G_HpHm13
| G_HpHm22 | G_HpHm23 | G_HpHm33 | G_h1111 | G_h1112 |
G_h1113
| G_h1122 | G_h1123 | G_h1133 | G_h1222 | G_h1223 |
G_h1233 | G_h1333
| G_h2222 | G_h2223 | G_h2233 | G_h2333 | G_h3333
| G_h1uu | G_h2uu | G_h3uu | G_h1uc | G_h2uc | G_h3uc |
G_h1ut
| G_h2ut | G_h3ut | G_h1cu | G_h2cu | G_h3cu | G_h1cc |
G_h2cc
| G_h3cc | G_h1ct | G_h2ct | G_h3ct | G_h1tu | G_h2tu |
G_h3tu
| G_h1tc | G_h2tc | G_h3tc | G_h1tt | G_h2tt | G_h3tt
| G_h1dd | G_h2dd | G_h3dd | G_h1ds | G_h2ds | G_h3ds |
G_h1db
| G_h2db | G_h3db | G_h1sd | G_h2sd | G_h3sd | G_h1ss |
G_h2ss
| G_h3ss | G_h1sb | G_h2sb | G_h3sb | G_h1bd | G_h2bd |
G_h3bd
| G_h1bs | G_h2bs | G_h3bs | G_h1bb | G_h2bb | G_h3bb
| G_hud | G_hus | G_hub | G_hcd | G_hcs | G_hcb | G_htd |
G_hts | G_htb
| G_hdu | G_hdc | G_hdt | G_hsu | G_hsc | G_hst | G_hbu |

```

```

G_hbc | G_hbt
      | G_he1n1 | G_he1n2 | G_he1n3 | G_he2n1 | G_he2n2 |
G_he2n3 | G_he3n1
      | G_he3n2 | G_he3n3 | G_hn1e1 | G_hn1e2 | G_hn1e3 |
G_hn2e1 | G_hn2e2
      | G_hn2e3 | G_hn3e1 | G_hn3e2 | G_hn3e3
      | G_h1e1e1 | G_h2e1e1 | G_h3e1e1 | G_h1e1e2 | G_h2e1e2 |
G_h3e1e2
      | G_h1e1e3 | G_h2e1e3 | G_h3e1e3 | G_h1e2e1 | G_h2e2e1 |
G_h3e2e1
      | G_h1e2e2 | G_h2e2e2 | G_h3e2e2 | G_h1e2e3 | G_h2e2e3 |
G_h3e2e3
      | G_h1e3e1 | G_h2e3e1 | G_h3e3e1 | G_h1e3e2 | G_h2e3e2 |
G_h3e3e2
      | G_h1e3e3 | G_h2e3e3 | G_h3e3e3
      | Mass of flavor | Width of flavor

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int
let orders = function
  | _ → (0,0)
let parameters () =
  { input = []; derived = []; derived_arrays = [] }
module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

```

$$\mathcal{L}_{\text{EM}} = -e \sum_i q_i \bar{\psi}_i \not{A} \psi_i \quad (13.29)$$

```

let mgm ((m1, g, m2), fbf, c) = ((M m1, G g, M m2), fbf, c)
let electromagnetic_currents n =
  List.map mgm
  [ ((L (-n), Ga, L n), FBF (1, Psibar, V, Psi), Q_lepton);
    ((U (-n), Ga, U n), FBF (1, Psibar, V, Psi), Q_up);
    ((D (-n), Ga, D n), FBF (1, Psibar, V, Psi), Q_down) ]
let color_currents n =
  List.map mgm
  [ ((U (-n), Gl, U n), FBF (1, Psibar, V, Psi), Gs);
    ((D (-n), Gl, D n), FBF (1, Psibar, V, Psi), Gs) ]

```

$$\mathcal{L}_{\text{NC}} = -\frac{g}{2 \cos \theta_W} \sum_i \bar{\psi}_i \not{Z} (g_V^i - g_A^i \gamma_5) \psi_i \quad (13.30)$$

```

let neutral_currents n =
  List.map mgm
    [ ((L (-n), Z, L n), FBF (1, Psibar, VA, Psi), G_NC_lepton);
      ((N (-n), Z, N n), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
      ((U (-n), Z, U n), FBF (1, Psibar, VA, Psi), G_NC_up);
      ((D (-n), Z, D n), FBF (1, Psibar, VA, Psi), G_NC_down) ]

```

$$\mathcal{L}_{CC} = -\frac{g}{2\sqrt{2}} \sum_i \bar{\psi}_i (T^+ W^+ + T^- W^-) (1 - \gamma_5) \psi_i \quad (13.31)$$

```

let charged_currents n =
  List.map mgm
    [ ((L (-n), Wm, N n), FBF (1, Psibar, VL, Psi), G_CC);
      ((N (-n), Wp, L n), FBF (1, Psibar, VL, Psi), G_CC);
      ((D (-n), Wm, U n), FBF (1, Psibar, VL, Psi), G_CC);
      ((U (-n), Wp, D n), FBF (1, Psibar, VL, Psi), G_CC) ]

```

```

let yukawa =
  [ ((M (U (-1)), O Hh, M (U 1)), FBF (1, Psibar, SP, Psi), G_h1uu);
    ((M (U (-1)), O HH, M (U 1)), FBF (1, Psibar, SP, Psi), G_h2uu);
    ((M (U (-1)), O HA, M (U 1)), FBF (1, Psibar, SP, Psi), G_h3uu);
    ((M (U (-2)), O Hh, M (U 2)), FBF (1, Psibar, SP, Psi), G_h1cc);
    ((M (U (-2)), O HH, M (U 2)), FBF (1, Psibar, SP, Psi), G_h2cc);
    ((M (U (-2)), O HA, M (U 2)), FBF (1, Psibar, SP, Psi), G_h3cc);
    ((M (U (-3)), O Hh, M (U 3)), FBF (1, Psibar, SP, Psi), G_h1tt);
    ((M (U (-3)), O HH, M (U 3)), FBF (1, Psibar, SP, Psi), G_h2tt);
    ((M (U (-3)), O HA, M (U 3)), FBF (1, Psibar, SP, Psi), G_h3tt);

    ((M (D (-1)), O Hh, M (D 1)), FBF (1, Psibar, SP, Psi), G_h1dd);
    ((M (D (-1)), O HH, M (D 1)), FBF (1, Psibar, SP, Psi), G_h2dd);
    ((M (D (-1)), O HA, M (D 1)), FBF (1, Psibar, SP, Psi), G_h3dd);
    ((M (D (-2)), O Hh, M (D 2)), FBF (1, Psibar, SP, Psi), G_h1ss);
    ((M (D (-2)), O HH, M (D 2)), FBF (1, Psibar, SP, Psi), G_h2ss);
    ((M (D (-2)), O HA, M (D 2)), FBF (1, Psibar, SP, Psi), G_h3ss);
    ((M (D (-3)), O Hh, M (D 3)), FBF (1, Psibar, SP, Psi), G_h1bb);
    ((M (D (-3)), O HH, M (D 3)), FBF (1, Psibar, SP, Psi), G_h2bb);
    ((M (D (-3)), O HA, M (D 3)), FBF (1, Psibar, SP, Psi), G_h3bb);

    ((M (U (-1)), O Hp, M (D 1)), FBF (1, Psibar, SP, Psi), G_hud);
    ((M (U (-2)), O Hp, M (D 2)), FBF (1, Psibar, SP, Psi), G_hcs);
    ((M (U (-3)), O Hp, M (D 3)), FBF (1, Psibar, SP, Psi), G_hbt);

    ((M (D (-1)), O Hm, M (U 1)), FBF (1, Psibar, SP, Psi), G_hdu);
    ((M (D (-2)), O Hm, M (U 2)), FBF (1, Psibar, SP, Psi), G_hsc);
    ((M (D (-3)), O Hm, M (U 3)), FBF (1, Psibar, SP, Psi), G_hbt);

    ((M (L (-1)), O Hh, M (L 1)), FBF (1, Psibar, SP, Psi), G_h1e1e1);
    ((M (L (-1)), O HH, M (L 1)), FBF (1, Psibar, SP, Psi), G_h2e1e1);
    ((M (L (-1)), O HA, M (L 1)), FBF (1, Psibar, SP, Psi), G_h3e1e1);
    ((M (L (-2)), O Hh, M (L 2)), FBF (1, Psibar, SP, Psi), G_h1e2e2);
    ((M (L (-2)), O HH, M (L 2)), FBF (1, Psibar, SP, Psi), G_h2e2e2);
    ((M (L (-2)), O HA, M (L 2)), FBF (1, Psibar, SP, Psi), G_h3e2e2);

```

```

((M (L (-3)), O Hh, M (L 3)), FBF (1, Psibar, SP, Psi), G_h1e3e3);
((M (L (-3)), O HH, M (L 3)), FBF (1, Psibar, SP, Psi), G_h2e3e3);
((M (L (-3)), O HA, M (L 3)), FBF (1, Psibar, SP, Psi), G_h3e3e3)

```

] @

if *Flags.ckm_present* then

```

[ ((M (U (-1)), O Hh, M (U 2)), FBF (1, Psibar, SP, Psi), G_h1uc);
  ((M (U (-1)), O Hh, M (U 3)), FBF (1, Psibar, SP, Psi), G_h1ut);
  ((M (U (-2)), O Hh, M (U 1)), FBF (1, Psibar, SP, Psi), G_h1cu);
  ((M (U (-2)), O Hh, M (U 3)), FBF (1, Psibar, SP, Psi), G_h1ct);
  ((M (U (-1)), O HH, M (U 2)), FBF (1, Psibar, SP, Psi), G_h2uc);
  ((M (U (-1)), O HH, M (U 3)), FBF (1, Psibar, SP, Psi), G_h2ut);
  ((M (U (-1)), O HA, M (U 2)), FBF (1, Psibar, SP, Psi), G_h3uc);
  ((M (U (-1)), O HA, M (U 3)), FBF (1, Psibar, SP, Psi), G_h3ut);
  ((M (U (-2)), O HH, M (U 1)), FBF (1, Psibar, SP, Psi), G_h2cu);
  ((M (U (-2)), O HH, M (U 3)), FBF (1, Psibar, SP, Psi), G_h2ct);
  ((M (U (-2)), O HA, M (U 1)), FBF (1, Psibar, SP, Psi), G_h3cu);
  ((M (U (-2)), O HA, M (U 3)), FBF (1, Psibar, SP, Psi), G_h3ct);
  ((M (U (-3)), O Hh, M (U 1)), FBF (1, Psibar, SP, Psi), G_h1tu);
  ((M (U (-3)), O Hh, M (U 2)), FBF (1, Psibar, SP, Psi), G_h1tc);
  ((M (U (-3)), O HH, M (U 1)), FBF (1, Psibar, SP, Psi), G_h2tu);
  ((M (U (-3)), O HH, M (U 2)), FBF (1, Psibar, SP, Psi), G_h2tc);
  ((M (U (-3)), O HA, M (U 1)), FBF (1, Psibar, SP, Psi), G_h3tu);
  ((M (U (-3)), O HA, M (U 2)), FBF (1, Psibar, SP, Psi), G_h3tc);

  ((M (D (-1)), O Hh, M (D 2)), FBF (1, Psibar, SP, Psi), G_h1ds);
  ((M (D (-1)), O Hh, M (D 3)), FBF (1, Psibar, SP, Psi), G_h1db);
  ((M (D (-1)), O HH, M (D 2)), FBF (1, Psibar, SP, Psi), G_h2ds);
  ((M (D (-1)), O HH, M (D 3)), FBF (1, Psibar, SP, Psi), G_h2db);
  ((M (D (-1)), O HA, M (D 2)), FBF (1, Psibar, SP, Psi), G_h3ds);
  ((M (D (-1)), O HA, M (D 3)), FBF (1, Psibar, SP, Psi), G_h3db);
  ((M (D (-2)), O Hh, M (D 1)), FBF (1, Psibar, SP, Psi), G_h1sd);
  ((M (D (-2)), O Hh, M (D 3)), FBF (1, Psibar, SP, Psi), G_h1sb);
  ((M (D (-2)), O HH, M (D 1)), FBF (1, Psibar, SP, Psi), G_h2sd);
  ((M (D (-2)), O HH, M (D 3)), FBF (1, Psibar, SP, Psi), G_h2sb);
  ((M (D (-2)), O HA, M (D 1)), FBF (1, Psibar, SP, Psi), G_h3sd);

  ((M (L (-1)), O Hh, M (L 2)), FBF (1, Psibar, SP, Psi), G_h1e1e2);
  ((M (L (-1)), O Hh, M (L 3)), FBF (1, Psibar, SP, Psi), G_h1e1e3);
  ((M (L (-1)), O HH, M (L 2)), FBF (1, Psibar, SP, Psi), G_h2e1e2);
  ((M (L (-1)), O HH, M (L 3)), FBF (1, Psibar, SP, Psi), G_h2e1e3);
  ((M (L (-1)), O HA, M (L 2)), FBF (1, Psibar, SP, Psi), G_h3e1e2);
  ((M (L (-1)), O HA, M (L 3)), FBF (1, Psibar, SP, Psi), G_h3e1e3);
  ((M (L (-2)), O Hh, M (L 1)), FBF (1, Psibar, SP, Psi), G_h1e2e1);
  ((M (L (-2)), O Hh, M (L 3)), FBF (1, Psibar, SP, Psi), G_h1e2e3);
  ((M (L (-2)), O HH, M (L 1)), FBF (1, Psibar, SP, Psi), G_h2e2e1);
  ((M (L (-2)), O HH, M (L 3)), FBF (1, Psibar, SP, Psi), G_h2e2e3);
  ((M (L (-2)), O HA, M (L 1)), FBF (1, Psibar, SP, Psi), G_h3e2e1);
  ((M (L (-2)), O HA, M (L 3)), FBF (1, Psibar, SP, Psi), G_h3e2e3);
  ((M (L (-3)), O Hh, M (L 1)), FBF (1, Psibar, SP, Psi), G_h1e3e1);
  ((M (L (-3)), O Hh, M (L 2)), FBF (1, Psibar, SP, Psi), G_h1e3e2);
  ((M (L (-3)), O HH, M (L 1)), FBF (1, Psibar, SP, Psi), G_h2e3e1);

```

```

((M (L (-3)), O HH, M (L 2)), FBF (1, Psibar, SP, Psi), G_h2e3e2);
((M (L (-3)), O HA, M (L 1)), FBF (1, Psibar, SP, Psi), G_h3e3e1);
((M (L (-3)), O HA, M (L 2)), FBF (1, Psibar, SP, Psi), G_h3e3e2) ]
else
[]

```

$$\mathcal{L}_{\text{TGC}} = -e\partial_\mu A_\nu W_+^\mu W_-^\nu + \dots - e\cot\theta_w\partial_\mu Z_\nu W_+^\mu W_-^\nu + \dots \quad (13.32)$$

```

let tgc ((g1, g2, g3), t, c) = ((G g1, G g2, G g3), t, c)

```

```

let triple_gauge =
  List.map tgc
    [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
      ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW);
      ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_Gs) ]

```

$$\mathcal{L}_{\text{QGC}} = -g^2 W_{+,\mu} W_{-,\nu} W_+^\mu W_-^\nu + \dots \quad (13.33)$$

Actually, quartic gauge couplings are a little bit more straightforward using auxiliary fields. Here we have to impose the antisymmetry manually:

$$\begin{aligned} & (W_1^{+,\mu} W_2^{-,\nu} - W_1^{+,\nu} W_2^{-,\mu})(W_{3,\mu}^+ W_{4,\nu}^- - W_{3,\nu}^+ W_{4,\mu}^-) \\ & = 2(W_1^+ W_3^+)(W_2^- W_4^-) - 2(W_1^+ W_4^-)(W_2^- W_3^+) \end{aligned} \quad (13.34a)$$

also (V can be A or Z)

$$\begin{aligned} & (W_1^{+,\mu} V_2^\nu - W_1^{+,\nu} V_2^\mu)(W_{3,\mu}^- V_{4,\nu} - W_{3,\nu}^- V_{4,\mu}) \\ & = 2(W_1^+ W_3^-)(V_2 V_4) - 2(W_1^+ V_4)(V_2 W_3^-) \end{aligned} \quad (13.34b)$$

$$W^{+,\mu} W^{-,\nu} W_\mu^+ W_\nu^- \quad (13.35a)$$

```

let qgc ((g1, g2, g3, g4), t, c) = ((G g1, G g2, G g3, G g4), t, c)
let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let quartic_gauge =
  List.map qgc
    [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
      (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
      (Wm, Z, Wp, Ga), minus_gauge4, G_AZWW;
      (Wm, Ga, Wp, Ga), minus_gauge4, G_AAWW;
      (Gl, Gl, Gl, Gl), gauge4, G2]

let gauge_higgs =
  [ (G Ga, O Hp, O Hm), Vector_Scalar_Scalar 1, G_AHpHm;
    (G Z, O Hp, O Hm), Vector_Scalar_Scalar 1, G_ZHpHm;
    (G Z, O Hh, O HH), Vector_Scalar_Scalar 1, G_Zh1h2;
    (G Z, O Hh, O HA), Vector_Scalar_Scalar 1, G_Zh1h3;

```



```

(G Z, O HH, O HA), Vector_Scalar_Scalar 1, G_Zh2h3;
(G Wp, O Hm, O Hh), Vector_Scalar_Scalar 1, G_WpHmh1;
(G Wp, O Hm, O HH), Vector_Scalar_Scalar 1, G_WpHmh2;
(G Wp, O Hm, O HA), Vector_Scalar_Scalar 1, G_WpHmh3;
(G Wm, O Hp, O Hh), Vector_Scalar_Scalar 1, G_WmHph1;
(G Wm, O Hp, O HH), Vector_Scalar_Scalar 1, G_WmHph2;
(G Wm, O Hp, O HA), Vector_Scalar_Scalar 1, G_WmHph3;
(O Hh, G Z, G Z), Scalar_Vector_Vector 1, G_h1ZZ;
(O HH, G Z, G Z), Scalar_Vector_Vector 1, G_h2ZZ;
(O HA, G Z, G Z), Scalar_Vector_Vector 1, G_h3ZZ;
(O Hh, G Wp, G Wm), Scalar_Vector_Vector 1, G_h1WpWm;
(O HH, G Wp, G Wm), Scalar_Vector_Vector 1, G_h2WpWm;
(O HA, G Wp, G Wm), Scalar_Vector_Vector 1, G_h3WpWm ]

let gauge_higgs4 =
[ (O Hh, O Hh, G Wp, G Wm), Scalar2_Vector2 1, G_hhWpWm;
  (O HH, O HH, G Wp, G Wm), Scalar2_Vector2 1, G_hhWpWm;
  (O HA, O HA, G Wp, G Wm), Scalar2_Vector2 1, G_hhWpWm;
  (O Hh, O Hh, G Z, G Z), Scalar2_Vector2 1, G_hhZZ;
  (O HH, O HH, G Z, G Z), Scalar2_Vector2 1, G_hhZZ;
  (O HA, O HA, G Z, G Z), Scalar2_Vector2 1, G_hhZZ;
  (O Hp, O Hm, G Ga, G Ga), Scalar2_Vector2 1, G_HpHmAA;
  (O Hp, O Hm, G Z, G Z), Scalar2_Vector2 1, G_HpHmZZ;
  (O Hp, O Hm, G Ga, G Z), Scalar2_Vector2 1, G_HpHmAZ;
  (O Hp, O Hm, G Wp, G Wm), Scalar2_Vector2 1, G_HpHmWpWm;
  (O Hh, O Hp, G Ga, G Wm), Scalar2_Vector2 1, G_h1HpAWm;
  (O HH, O Hp, G Ga, G Wm), Scalar2_Vector2 1, G_h2HpAWm;
  (O HA, O Hp, G Ga, G Wm), Scalar2_Vector2 1, G_h3HpAWm;
  (O Hh, O Hp, G Z, G Wm), Scalar2_Vector2 1, G_h1HpZWm;
  (O HH, O Hp, G Z, G Wm), Scalar2_Vector2 1, G_h2HpZWm;
  (O HA, O Hp, G Z, G Wm), Scalar2_Vector2 1, G_h3HpZWm;
  (O Hh, O Hm, G Ga, G Wp), Scalar2_Vector2 1, G_h1HpAWmC;
  (O HH, O Hm, G Ga, G Wp), Scalar2_Vector2 1, G_h2HpAWmC;
  (O HA, O Hm, G Ga, G Wp), Scalar2_Vector2 1, G_h3HpAWmC;
  (O Hh, O Hm, G Z, G Wp), Scalar2_Vector2 1, G_h1HpZWmC;
  (O HH, O Hm, G Z, G Wp), Scalar2_Vector2 1, G_h2HpZWmC;
  (O HA, O Hm, G Z, G Wp), Scalar2_Vector2 1, G_h3HpZWmC ]

let higgs =
[ (O Hh, O Hp, O Hm), Scalar_Scalar_Scalar 1, G_h1HpHm;
  (O HH, O Hp, O Hm), Scalar_Scalar_Scalar 1, G_h2HpHm;
  (O HA, O Hp, O Hm), Scalar_Scalar_Scalar 1, G_h3HpHm;
  (O Hh, O Hh, O Hh), Scalar_Scalar_Scalar 1, G_h111;
  (O Hh, O Hh, O HH), Scalar_Scalar_Scalar 1, G_h112;
  (O Hh, O Hh, O HA), Scalar_Scalar_Scalar 1, G_h113;
  (O HH, O HH, O Hh), Scalar_Scalar_Scalar 1, G_h221;
  (O HH, O HH, O HH), Scalar_Scalar_Scalar 1, G_h222;
  (O HH, O HH, O HA), Scalar_Scalar_Scalar 1, G_h223;
  (O HA, O HA, O Hh), Scalar_Scalar_Scalar 1, G_h331;
  (O HA, O HA, O HH), Scalar_Scalar_Scalar 1, G_h332;
  (O HA, O HA, O HA), Scalar_Scalar_Scalar 1, G_h333;

```

```

      (O Hh, O HH, O HA), Scalar_Scalar_Scalar 1, G_h123 ]

let higgs4 =
  [ (O Hp, O Hm, O Hp, O Hm), Scalar4 1, G_HpHmHpHm;
    (O Hp, O Hm, O Hh, O Hh), Scalar4 1, G_HpHm11;
    (O Hp, O Hm, O Hh, O HH), Scalar4 1, G_HpHm12;
    (O Hp, O Hm, O Hh, O HA), Scalar4 1, G_HpHm13;
    (O Hp, O Hm, O HH, O HH), Scalar4 1, G_HpHm22;
    (O Hp, O Hm, O HH, O HA), Scalar4 1, G_HpHm23;
    (O Hp, O Hm, O HA, O HA), Scalar4 1, G_HpHm33;
    (O Hh, O Hh, O Hh, O Hh), Scalar4 1, G_h1111;
    (O Hh, O Hh, O Hh, O HH), Scalar4 1, G_h1112;
    (O Hh, O Hh, O Hh, O HA), Scalar4 1, G_h1113;
    (O Hh, O Hh, O HH, O HH), Scalar4 1, G_h1122;
    (O Hh, O Hh, O HH, O HA), Scalar4 1, G_h1123;
    (O Hh, O Hh, O HA, O HA), Scalar4 1, G_h1133;
    (O Hh, O HH, O HH, O HH), Scalar4 1, G_h1222;
    (O Hh, O HH, O HH, O HA), Scalar4 1, G_h1223;
    (O Hh, O HH, O HA, O HA), Scalar4 1, G_h1233;
    (O Hh, O HA, O HA, O HA), Scalar4 1, G_h1333;
    (O HH, O HH, O HH, O HH), Scalar4 1, G_h2222;
    (O HH, O HH, O HH, O HA), Scalar4 1, G_h2223;
    (O HH, O HH, O HA, O HA), Scalar4 1, G_h2233;
    (O HH, O HA, O HA, O HA), Scalar4 1, G_h2333;
    (O HA, O HA, O HA, O HA), Scalar4 1, G_h3333 ]

let goldstone_vertices =
  [ ((O Phi0, G Wm, G Wp), Scalar_Vector_Vector 1, I_G-ZWW);
    ((O Phip, G Ga, G Wm), Scalar_Vector_Vector 1, I_Q-W);
    ((O Phip, G Z, G Wm), Scalar_Vector_Vector 1, I_G-ZWW);
    ((O Phim, G Wp, G Ga), Scalar_Vector_Vector 1, I_Q-W);
    ((O Phim, G Wp, G Z), Scalar_Vector_Vector 1, I_G-ZWW) ]

let vertices3 =
  (ThoList.flatmap electromagnetic_currents [1;2;3] @
   ThoList.flatmap color_currents [1;2;3] @
   ThoList.flatmap neutral_currents [1;2;3] @
   ThoList.flatmap charged_currents [1;2;3] @
   yukawa @ triple_gauge @
   gauge_higgs @ higgs @ goldstone_vertices)

let vertices4 =
  quartic_gauge @ gauge_higgs4 @ higgs4

let vertices () = (vertices3, vertices4, [])

For efficiency, make sure that F.of_vertices vertices is evaluated only once.

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

```

```

let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))
| "numu" → M (N 2) | "numubar" → M (N (-2))
| "nutau" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "g" → G Gl
| "A" → G Ga | "Z" | "Z0" → G Z
| "W+" → G Wp | "W-" → G Wm
| "h0" → O Hh
| "H0" → O HH
| "A0" → O HA
| _ → invalid_arg "Modellib_BSM.TwoHiggsDoublet.flavor_of_string"

let flavor_to_string = function
| M f →
  begin match f with
  | L 1 → "e-" | L (-1) → "e+"
  | L 2 → "mu-" | L (-2) → "mu+"
  | L 3 → "tau-" | L (-3) → "tau+"
  | L _ → invalid_arg
    "Modellib_BSM.TwoHiggsDoublet.flavor_to_string:␣invalid␣lepton"
  | N 1 → "nue" | N (-1) → "nuebar"
  | N 2 → "numu" | N (-2) → "numubar"
  | N 3 → "nutau" | N (-3) → "nutaubar"
  | N _ → invalid_arg
    "Modellib_BSM.TwoHiggsDoublet.flavor_to_string:␣invalid␣neutrino"
  | U 1 → "u" | U (-1) → "ubar"
  | U 2 → "c" | U (-2) → "cbar"
  | U 3 → "t" | U (-3) → "tbar"
  | U _ → invalid_arg
    "Modellib_BSM.TwoHiggsDoublet.flavor_to_string:␣invalid␣up␣type␣quark"
  | D 1 → "d" | D (-1) → "dbar"
  | D 2 → "s" | D (-2) → "sbar"
  | D 3 → "b" | D (-3) → "bbar"
  | D _ → invalid_arg
    "Modellib_BSM.TwoHiggsDoublet.flavor_to_string:␣invalid␣down␣type␣quark"
  end
| G f →
  begin match f with
  | Gl → "g"
  | Ga → "A" | Z → "Z"
  | Wp → "W+" | Wm → "W-"

```

```

    end
  |  $O f \rightarrow$ 
    begin match  $f$  with
    |  $Phip \rightarrow$  "phi+" |  $Phim \rightarrow$  "phi-" |  $Phi0 \rightarrow$  "phi0"
    |  $Hh \rightarrow$  "h0" |  $HH \rightarrow$  "H0" |  $HA \rightarrow$  "A0"
    |  $Hp \rightarrow$  "H+" |  $Hm \rightarrow$  "H-"
    end

let flavor_to_TeX = function
|  $M f \rightarrow$ 
  begin match  $f$  with
  |  $L 1 \rightarrow$  "e^-" |  $L (-1) \rightarrow$  "e^+"
  |  $L 2 \rightarrow$  "\\mu^-" |  $L (-2) \rightarrow$  "\\mu^+"
  |  $L 3 \rightarrow$  "\\tau^-" |  $L (-3) \rightarrow$  "\\tau^+"
  |  $L _ \rightarrow$  invalid_arg
    "Modellib_BSM.TwoHiggsDoublet.flavor_to_TeX:_invalid_lepton"
  |  $N 1 \rightarrow$  "\\nu_e" |  $N (-1) \rightarrow$  "\\bar{\nu}_e"
  |  $N 2 \rightarrow$  "\\nu_\mu" |  $N (-2) \rightarrow$  "\\bar{\nu}_\mu"
  |  $N 3 \rightarrow$  "\\nu_\tau" |  $N (-3) \rightarrow$  "\\bar{\nu}_\tau"
  |  $N _ \rightarrow$  invalid_arg
    "Modellib_BSM.TwoHiggsDoublet.flavor_to_TeX:_invalid_neutrino"
  |  $U 1 \rightarrow$  "u" |  $U (-1) \rightarrow$  "\\bar{u}"
  |  $U 2 \rightarrow$  "c" |  $U (-2) \rightarrow$  "\\bar{c}"
  |  $U 3 \rightarrow$  "t" |  $U (-3) \rightarrow$  "\\bar{t}"
  |  $U _ \rightarrow$  invalid_arg
    "Modellib_BSM.TwoHiggsDoublet.flavor_to_TeX:_invalid_up_type_quark"
  |  $D 1 \rightarrow$  "d" |  $D (-1) \rightarrow$  "\\bar{d}"
  |  $D 2 \rightarrow$  "s" |  $D (-2) \rightarrow$  "\\bar{s}"
  |  $D 3 \rightarrow$  "b" |  $D (-3) \rightarrow$  "\\bar{b}"
  |  $D _ \rightarrow$  invalid_arg
    "Modellib_BSM.TwoHiggsDoublet.flavor_to_TeX:_invalid_down_type_quark"
  end
|  $G f \rightarrow$ 
  begin match  $f$  with
  |  $Gl \rightarrow$  "g"
  |  $Ga \rightarrow$  "\\gamma" |  $Z \rightarrow$  "Z"
  |  $Wp \rightarrow$  "W^+" |  $Wm \rightarrow$  "W^-"
  end
|  $O f \rightarrow$ 
  begin match  $f$  with
  |  $Phip \rightarrow$  "\\phi^+" |  $Phim \rightarrow$  "\\phi^-" |  $Phi0 \rightarrow$ 
    "\\phi^0"
  |  $Hh \rightarrow$  "h^0" |  $HH \rightarrow$  "H^0" |  $HA \rightarrow$  "A^0"
  |  $Hp \rightarrow$  "H^+" |  $Hm \rightarrow$  "H^-"
  end

let flavor_symbol = function
|  $M f \rightarrow$ 
  begin match  $f$  with
  |  $L n$  when  $n > 0 \rightarrow$  "l" ^ string_of_int  $n$ 
  |  $L n \rightarrow$  "l" ^ string_of_int (abs  $n$ ) ^ "b"

```

```

|  $N\ n$  when  $n > 0 \rightarrow "n" \wedge \text{string\_of\_int } n$ 
|  $N\ n \rightarrow "n" \wedge \text{string\_of\_int } (\text{abs } n) \wedge "b"$ 
|  $U\ n$  when  $n > 0 \rightarrow "u" \wedge \text{string\_of\_int } n$ 
|  $U\ n \rightarrow "u" \wedge \text{string\_of\_int } (\text{abs } n) \wedge "b"$ 
|  $D\ n$  when  $n > 0 \rightarrow "d" \wedge \text{string\_of\_int } n$ 
|  $D\ n \rightarrow "d" \wedge \text{string\_of\_int } (\text{abs } n) \wedge "b"$ 
end
|  $G\ f \rightarrow$ 
  begin match  $f$  with
  |  $Gl \rightarrow "g1"$ 
  |  $Ga \rightarrow "a" \mid Z \rightarrow "z"$ 
  |  $Wp \rightarrow "wp" \mid Wm \rightarrow "wm"$ 
  end
|  $O\ f \rightarrow$ 
  begin match  $f$  with
  |  $Phip \rightarrow "pp" \mid Phim \rightarrow "pm" \mid Phi0 \rightarrow "p0"$ 
  |  $Hh \rightarrow "h" \mid HH \rightarrow "h0" \mid HA \rightarrow "a0"$ 
  |  $Hp \rightarrow "hp" \mid Hm \rightarrow "hm"$ 
  end
let  $pdg = \text{function}$ 
|  $M\ f \rightarrow$ 
  begin match  $f$  with
  |  $L\ n$  when  $n > 0 \rightarrow 9 + 2 \times n$ 
  |  $L\ n \rightarrow -9 + 2 \times n$ 
  |  $N\ n$  when  $n > 0 \rightarrow 10 + 2 \times n$ 
  |  $N\ n \rightarrow -10 + 2 \times n$ 
  |  $U\ n$  when  $n > 0 \rightarrow 2 \times n$ 
  |  $U\ n \rightarrow 2 \times n$ 
  |  $D\ n$  when  $n > 0 \rightarrow -1 + 2 \times n$ 
  |  $D\ n \rightarrow 1 + 2 \times n$ 
  end
|  $G\ f \rightarrow$ 
  begin match  $f$  with
  |  $Gl \rightarrow 21$ 
  |  $Ga \rightarrow 22 \mid Z \rightarrow 23$ 
  |  $Wp \rightarrow 24 \mid Wm \rightarrow (-24)$ 
  end
|  $O\ f \rightarrow$ 
  begin match  $f$  with
  |  $Phip \rightarrow 27 \mid Phim \rightarrow -27 \mid Phi0 \rightarrow 26$ 
  |  $Hh \rightarrow 25$ 
  |  $HH \rightarrow 35$ 
  |  $HA \rightarrow 36$ 
  |  $Hp \rightarrow 37$ 
  |  $Hm \rightarrow -37$ 
  end
let  $\text{mass\_symbol } f =$ 
  "mass("  $\wedge \text{string\_of\_int } (\text{abs } (pdg\ f)) \wedge "$ 

```

```

let width_symbol f =
  "width(" ^ string_of_int (abs (pdg f)) ^ ")"

let constant_symbol = function
  | Unit → "unit" | Pi → "PI"
  | Alpha_QED → "alpha" | E → "e" | G_weak → "g" | Vev →
"vev"
  | Sin2thw → "sin2thw" | Sinthw → "sinthw" | Costhw →
"costhw"
  | Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdown"
  | G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
  | G_NC_up → "gncup" | G_NC_down → "gncdown"
  | G_CC → "gcc"
  | I_Q_W → "iqw" | I_G_ZWW → "igzww" | I_G_WWW →
"igwww"
  | G_WWWW → "gw4" | G_ZZWW → "gzzww"
  | G_AZWW → "gazww" | G_AAWW → "gaaww"
  | G_htt → "ghtt" | G_hbb → "ghbb" | G_hcc → "ghcc"
  | G_Htt → "gh0tt" | G_Hbb → "gh0bb" | G_Hcc → "gh0cc"
  | I_G_Att → "iga0tt" | I_G_Abb → "iga0bb" | I_G_Acc →
"iga0cc"
  | G_hatautau → "ghatautau" | G_hmumu → "ghmumu"
  | G_Hatautau → "gh0atautau" | G_Hmumu → "gh0mumu"
  | I_G_Atautau → "iga0atautau" | I_G_Amumu → "iga0mumu"
  | G_Htb → "ghptb" | G_Hcs → "ghpcs"
  | G_Htaunu → "ghptaunu" | G_Hmunu → "ghpmunu"
  | Gs → "gs" | I_Gs → "igs" | G2 → "gs**2"
  | G_AHpHm → "gAHpHm" | G_ZHpHm → "gZHpHm"
  | G_Zh1h2 → "gZh1h2" | G_Zh1h3 → "gZh1h3"
  | G_Zh2h3 → "gZh2h3" | G_WpHmh1 → "gWpHmh1"
  | G_WpHmh2 → "gWpHmh2" | G_WpHmh3 → "gWpHmh3"
  | G_WmHph1 → "gWmHph1" | G_WmHph2 → "gWmHph2"
  | G_WmHph3 → "gWmHph3" | G_h1ZZ → "gh1ZZ"
  | G_h2ZZ → "gh2ZZ" | G_h3ZZ → "gh3ZZ"
  | G_h1WpWm → "gh1WpWm" | G_h2WpWm → "gh2WpWm"
  | G_h3WpWm → "gh3WpWm" | G_hhWpWm → "ghhWpWm"
  | G_hhZZ → "ghhZZ" | G_HpHmAA → "gHpHmAA"
  | G_HpHmZZ → "gHpHmZZ" | G_HpHmAZ → "gHpHmAZ"
  | G_HpHmWpWm → "gHpHmWpWm" | G_h1HpAWm → "gh1HpAWm"
  | G_h2HpAWm → "gh2HpAWm" | G_h3HpAWm → "gh3HpAWm"
  | G_h1HpZWm → "gh1HpZWm" | G_h2HpZWm → "gh2HpZWm"
  | G_h3HpZWm → "gh3HpZWm" | G_h1HpAWmC → "gh1HpAWmC"
  | G_h2HpAWmC → "gh2HpAWmC" | G_h3HpAWmC → "gh3HpAWmC"
  | G_h1HpZWmC → "gh1HpZWmC" | G_h2HpZWmC → "gh2HpZWmC"
  | G_h3HpZWmC → "gh3HpZWmC" | G_h1HpHm → "gh1HpHm"
  | G_h2HpHm → "gh2HpHm" | G_h3HpHm → "gh3HpHm"
  | G_h111 → "gh111" | G_h112 → "gh112" | G_h113 → "gh113"
  | G_h221 → "gh221" | G_h222 → "gh222" | G_h223 → "gh223"
  | G_h331 → "gh331" | G_h332 → "gh332"
  | G_h333 → "gh333" | G_h123 → "gh123"

```

$G_HpHmHpHm \rightarrow "gHpHmHpHm"$	$G_HpHm11 \rightarrow "gHpHm11"$
$G_HpHm12 \rightarrow "gHpHm12"$	$G_HpHm13 \rightarrow "gHpHm13"$
$G_HpHm22 \rightarrow "gHpHm22"$	$G_HpHm23 \rightarrow "gHpHm23"$
$G_HpHm33 \rightarrow "gHpHm33"$	$G_h1111 \rightarrow "gh1111"$
$G_h1112 \rightarrow "gh1112"$	$G_h1113 \rightarrow "gh1113"$
$G_h1122 \rightarrow "gh1122"$	$G_h1123 \rightarrow "gh1123"$
$G_h1133 \rightarrow "gh1133"$	$G_h1222 \rightarrow "gh1222"$
$G_h1223 \rightarrow "gh1223"$	$G_h1233 \rightarrow "gh1233"$
$G_h1333 \rightarrow "gh1333"$	$G_h2222 \rightarrow "gh2222"$
$G_h2223 \rightarrow "gh2223"$	$G_h2233 \rightarrow "gh2233"$
$G_h2333 \rightarrow "gh2333"$	$G_h3333 \rightarrow "gh3333"$
$G_h1uu \rightarrow "gh1uu"$	$G_h2uu \rightarrow "gh2uu"$
$G_h3uu \rightarrow "gh3uu"$	$G_h1uc \rightarrow "gh1uc"$
$G_h2uc \rightarrow "gh2uc"$	$G_h3uc \rightarrow "gh3uc"$
$G_h1ut \rightarrow "gh1ut"$	$G_h2ut \rightarrow "gh2ut"$
$G_h3ut \rightarrow "gh3ut"$	$G_h1cu \rightarrow "gh1cu"$
$G_h2cu \rightarrow "gh2cu"$	$G_h3cu \rightarrow "gh3cu"$
$G_h1cc \rightarrow "gh1cc"$	$G_h2cc \rightarrow "gh2cc"$
$G_h3cc \rightarrow "gh3cc"$	$G_h1ct \rightarrow "gh1ct"$
$G_h2ct \rightarrow "gh2ct"$	$G_h3ct \rightarrow "gh3ct"$
$G_h1tu \rightarrow "gh1tu"$	$G_h2tu \rightarrow "gh2tu"$
$G_h3tu \rightarrow "gh3tu"$	$G_h1tc \rightarrow "gh1tc"$
$G_h2tc \rightarrow "gh2tc"$	$G_h3tc \rightarrow "gh3tc"$
$G_h1tt \rightarrow "gh1tt"$	$G_h2tt \rightarrow "gh2tt"$
$G_h3tt \rightarrow "gh3tt"$	
$G_h1dd \rightarrow "gh1dd"$	$G_h2dd \rightarrow "gh2dd"$
$G_h3dd \rightarrow "gh3dd"$	$G_h1ds \rightarrow "gh1ds"$
$G_h2ds \rightarrow "gh2ds"$	$G_h3ds \rightarrow "gh3ds"$
$G_h1db \rightarrow "gh1db"$	$G_h2db \rightarrow "gh2db"$
$G_h3db \rightarrow "gh3db"$	$G_h1sd \rightarrow "gh1sd"$
$G_h2sd \rightarrow "gh2sd"$	$G_h3sd \rightarrow "gh3sd"$
$G_h1ss \rightarrow "gh1ss"$	$G_h2ss \rightarrow "gh2ss"$
$G_h3ss \rightarrow "gh3ss"$	$G_h1sb \rightarrow "gh1sb"$
$G_h2sb \rightarrow "gh2sb"$	$G_h3sb \rightarrow "gh3sb"$
$G_h1bd \rightarrow "gh1bd"$	$G_h2bd \rightarrow "gh2bd"$
$G_h3bd \rightarrow "gh3bd"$	$G_h1bs \rightarrow "gh1bs"$
$G_h2bs \rightarrow "gh2bs"$	$G_h3bs \rightarrow "gh3bs"$
$G_h1bb \rightarrow "gh1bb"$	$G_h2bb \rightarrow "gh2bb"$
$G_h3bb \rightarrow "gh3bb"$	
$G_hud \rightarrow "ghud"$	$G_hus \rightarrow "ghus"$
$G_hub \rightarrow "ghub"$	$G_hcd \rightarrow "ghcd"$
$G_hcs \rightarrow "ghcs"$	$G_hcb \rightarrow "ghcb"$
$G_htd \rightarrow "ghtd"$	$G_hts \rightarrow "ghts"$
$G_htb \rightarrow "ghtb"$	
$G_hdu \rightarrow "ghdu"$	$G_hdc \rightarrow "ghdc"$
$G_hdt \rightarrow "ghdt"$	$G_hsu \rightarrow "ghsu"$
$G_hsc \rightarrow "ghsc"$	$G_hst \rightarrow "ghst"$
$G_hbu \rightarrow "ghbu"$	$G_hbc \rightarrow "ghbc"$
$G_hbt \rightarrow "ghbt"$	
$G_he1n1 \rightarrow "ghe1n1"$	$G_he1n2 \rightarrow "ghe1n2"$

```

| G_he1n3 → "ghe1n3" | G_he2n1 → "ghe2n1"
| G_he2n2 → "ghe2n2" | G_he2n3 → "ghe2n3"
| G_he3n1 → "ghe3n1" | G_he3n2 → "ghe3n2"
| G_he3n3 → "ghe3n3" | G_hn1e1 → "ghn1e1"
| G_hn1e2 → "ghn1e2" | G_hn1e3 → "ghn1e3"
| G_hn2e1 → "ghn2e1" | G_hn2e2 → "ghn2e2"
| G_hn2e3 → "ghn2e3" | G_hn3e1 → "ghn3e1"
| G_hn3e2 → "ghn3e2" | G_hn3e3 → "ghn3e3"
| G_h1e1e1 → "gh1e1e1" | G_h2e1e1 → "gh2e1e1"
| G_h3e1e1 → "gh3e1e1" | G_h1e1e2 → "gh1e1e2"
| G_h2e1e2 → "gh2e1e2" | G_h3e1e2 → "gh3e1e2"
| G_h1e1e3 → "gh1e1e3" | G_h2e1e3 → "gh2e1e3"
| G_h3e1e3 → "gh3e1e3" | G_h1e2e1 → "gh1e2e1"
| G_h2e2e1 → "gh2e2e1" | G_h3e2e1 → "gh3e2e1"
| G_h1e2e2 → "gh1e2e2" | G_h2e2e2 → "gh2e2e2"
| G_h3e2e2 → "gh3e2e2" | G_h1e2e3 → "gh1e2e3"
| G_h2e2e3 → "gh2e2e3" | G_h3e2e3 → "gh3e2e3"
| G_h1e3e1 → "gh1e3e1" | G_h2e3e1 → "gh2e3e1"
| G_h3e3e1 → "gh3e3e1" | G_h1e3e2 → "gh1e3e2"
| G_h2e3e2 → "gh2e3e2" | G_h3e3e2 → "gh3e3e2"
| G_h1e3e3 → "gh1e3e3" | G_h2e3e3 → "gh2e3e3"
| G_h3e3e3 → "gh3e3e3"
| Mass f → "mass" ^ flavor_symbol f
| Width f → "width" ^ flavor_symbol f
end

module type VBS_flags =
sig
  val higgs_triangle : bool (*  $H\gamma\gamma$ ,  $Hg\gamma$  and  $Hgg$  couplings *)
  val higgs_hmm : bool
  val triple_anom : bool
  val quartic_anom : bool
  val higgs_anom : bool
  val k_matrix : bool
  val ckm_present : bool
  val top_anom : bool
  val top_anom_4f : bool
end

module VBS_kmatrix : VBS_flags =
struct
  let higgs_triangle = false
  let higgs_hmm = false
  let triple_anom = false
  let quartic_anom = true
  let higgs_anom = false
  let k_matrix = true
  let ckm_present = false
  let top_anom = false
  let top_anom_4f = false
end

```


13.6.4 Complete Minimal Standard Model including additional Resonances

```

module VBS (Flags : VBS_flags) =
  struct
    let rcs = RCS.rename rcs_file "Modellib_BSM.VBS"
      [ "minimal_electroweak_standard_model_in_unitarity_gauge_with_additional_Vectorboson"

    open Coupling

    let default_width = ref Timelike
    let use_fudged_width = ref false

    let options = Options.create
      [ "constant_width", Arg.Unit (fun () → default_width := Constant),
        "use_constant_width_also_in_t-channel";
        "fudged_width", Arg.Set use_fudged_width,
        "use_fudge_factor_for_charge_particle_width";
        "custom_width", Arg.String (fun f → default_width := Custom f),
        "use_custom_width";
        "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
        "use_vanishing_width"]

    type f_aux_top = TTGG | TBWA | TBWZ | TTWW | BBWW |
    let quartic_gauge =
      standard_quartic_gauge @ anomalous_quartic_gauge @ k_matrix_quartic_gauge

    let standard_gauge_higgs =
      [ ((O H, G Wp, G Wm), Scalar_Vector_Vector 1, G_HWW);
        ((O H, G Z, G Z), Scalar_Vector_Vector 1, G_HZZ) ]

    let standard_gauge_higgs4 =
      [ (O H, O H, G Wp, G Wm), Scalar2_Vector2 1, G_HHWW;
        (O H, O H, G Z, G Z), Scalar2_Vector2 1, G_HHZZ ]

    let standard_higgs =
      [ (O H, O H, O H), Scalar_Scalar_Scalar 1, G_H3 ]

    let standard_higgs4 =
      [ (O H, O H, O H, O H), Scalar4 1, G_H4 ]
  
```

WK's couplings (apparently, he still intends to divide by $\Lambda_{\text{WSB}}^2 = 16\pi^2 v_F^2$):

$$\mathcal{L}_4^\tau = \left[(\partial_\mu H)(\partial^\mu H) + \frac{g^2 v_F^2}{4} V_\mu V^\mu \right]^2 \quad (13.36a)$$

$$\mathcal{L}_5^\tau = \left[(\partial_\mu H)(\partial_\nu H) + \frac{g^2 v_F^2}{4} V_\mu V_\nu \right]^2 \quad (13.36b)$$

with

$$V_\mu V_\nu = \frac{1}{2} (W_\mu^+ W_\nu^- + W_\nu^+ W_\mu^-) + \frac{1}{2 \cos^2 \theta_w} Z_\mu Z_\nu \quad (13.37)$$

(note the symmetrization!), i. e.

$$\mathcal{L}_4 = \alpha_4 \frac{g^4 v_F^4}{16} (V_\mu V_\nu)^2 \quad (13.38a)$$

$$\mathcal{L}_5 = \alpha_5 \frac{g^4 v_F^4}{16} (V_\mu V^\mu)^2 \quad (13.38b)$$

Breaking thinks up

$$\mathcal{L}_4^{\tau, H^4} = [(\partial_\mu H)(\partial^\mu H)]^2 \quad (13.39a)$$

$$\mathcal{L}_5^{\tau, H^4} = [(\partial_\mu H)(\partial^\mu H)]^2 \quad (13.39b)$$

and

$$\mathcal{L}_4^{\tau, H^2 V^2} = \frac{g^2 v_F^2}{2} (\partial_\mu H)(\partial^\mu H) V_\mu V^\mu \quad (13.40a)$$

$$\mathcal{L}_5^{\tau, H^2 V^2} = \frac{g^2 v_F^2}{2} (\partial_\mu H)(\partial_\nu H) V_\mu V_\nu \quad (13.40b)$$

i. e.

$$\mathcal{L}_4^{\tau, H^2 V^2} = \frac{g^2 v_F^2}{2} \left[(\partial_\mu H)(\partial^\mu H) W_\nu^+ W^{-, \nu} + \frac{1}{2 \cos^2 \theta_w} (\partial_\mu H)(\partial^\mu H) Z_\nu Z^\nu \right] \quad (13.41a)$$

$$\mathcal{L}_5^{\tau, H^2 V^2} = \frac{g^2 v_F^2}{2} \left[(W^{+, \mu} \partial_\mu H)(W^{-, \nu} \partial_\nu H) + \frac{1}{2 \cos^2 \theta_w} (Z^\mu \partial_\mu H)(Z^\nu \partial_\nu H) \right] \quad (13.41b)$$

$$\begin{aligned} \tau_8^4 \mathcal{L}_4^{\tau, H^2 V^2} + \tau_8^5 \mathcal{L}_5^{\tau, H^2 V^2} = & \\ & - \frac{g^2 v_F^2}{2} \left[2\tau_8^4 \frac{1}{2} (i\partial_\mu H)(i\partial^\mu H) W_\nu^+ W^{-, \nu} + \tau_8^5 (W^{+, \mu} i\partial_\mu H)(W^{-, \nu} i\partial_\nu H) \right. \\ & \left. + \frac{2\tau_8^4}{\cos^2 \theta_w} \frac{1}{4} (i\partial_\mu H)(i\partial^\mu H) Z_\nu Z^\nu + \frac{\tau_8^5}{\cos^2 \theta_w} \frac{1}{2} (Z^\mu i\partial_\mu H)(Z^\nu i\partial_\nu H) \right] \end{aligned} \quad (13.42)$$

where the two powers of i make the sign conveniently negative, i. e.

$$\alpha_{(\partial H)^2 W^2}^2 = \tau_8^4 g^2 v_F^2 \quad (13.43a)$$

$$\alpha_{(\partial H W)^2}^2 = \frac{\tau_8^5 g^2 v_F^2}{2} \quad (13.43b)$$

$$\alpha_{(\partial H)^2 Z^2}^2 = \frac{\tau_8^4 g^2 v_F^2}{\cos^2 \theta_w} \quad (13.43c)$$

$$\alpha_{(\partial H Z)^2}^2 = \frac{\tau_8^5 g^2 v_F^2}{2 \cos^2 \theta_w} \quad (13.43d)$$

let *anomalous_gauge_higgs* =
 $[(O \ H, \ G \ Ga, \ G \ Ga), \ Dim5_Scalar_Gauge2 \ 1, \ G_HG a Ga_anom;$
 $(O \ H, \ G \ Ga, \ G \ Z), \ Dim5_Scalar_Gauge2 \ 1, \ G_HG a Z_anom;$

```

      (O H, G Z, G Z), Dim5_Scalar_Gauge2 1, G_HZZ_anom;
      (O H, G Wp, G Wm), Dim5_Scalar_Gauge2 1, G_HWW_anom;
      (O H, G Ga, G Z), Dim5_Scalar_Vector_Vector_U 1, G_HGaZ_u;
      (O H, G Z, G Z), Dim5_Scalar_Vector_Vector_U 1, G_HZZ_u;
      (O H, G Wp, G Wm), Dim5_Scalar_Vector_Vector_U 1, G_HWW_u;
      (O H, G Wm, G Wp), Dim5_Scalar_Vector_Vector_U 1, G_HWW_u
    ]
  let anomalous_gauge_higgs4 =
    []
  let anomalous_higgs =
    []
  let higgs_triangle_vertices =
    if Flags.higgs_triangle then
      [ (O H, G Ga, G Ga), Dim5_Scalar_Gauge2 1, G_HGaGa;
        (O H, G Ga, G Z), Dim5_Scalar_Gauge2 1, G_HGaZ;
        (O H, G Gl, G Gl), Dim5_Scalar_Gauge2 1, G_Hgg ]
    else
      []
  let anomalous_higgs4 =
    []
  let gauge_higgs =
    if Flags.higgs_anom then
      standard_gauge_higgs @ anomalous_gauge_higgs
    else
      standard_gauge_higgs
  let gauge_higgs4 =
    if Flags.higgs_anom then
      standard_gauge_higgs4 @ anomalous_gauge_higgs4
    else
      standard_gauge_higgs4
  let higgs =
    if Flags.higgs_anom then
      standard_higgs @ anomalous_higgs
    else
      standard_higgs
  let higgs4 =
    if Flags.higgs_anom then
      standard_higgs4 @ anomalous_higgs4
    else
      standard_higgs4
  let goldstone_vertices =
    [ ((O Phi0, G Wm, G Wp), Scalar_Vector_Vector 1, I_G_ZWW);
      ((O Phip, G Ga, G Wm), Scalar_Vector_Vector 1, I_Q_W);
      ((O Phip, G Z, G Wm), Scalar_Vector_Vector 1, I_G_ZWW);
      ((O Phim, G Wp, G Ga), Scalar_Vector_Vector 1, I_Q_W);
      ((O Phim, G Wp, G Z), Scalar_Vector_Vector 1, I_G_ZWW) ]

```

New Resonances



There is an extra minus in the Lagrangian to have the same sign as HWW or HZZ vertex. Effectivly this doesn't matter for VBS, because $(-1)^2 = 1$. This is only for completeness.

$$\mathbf{V}_\mu = -ig\mathbf{W}_\mu + ig'\mathbf{B}_\mu \quad (13.44a)$$

$$\mathbf{W}_\mu = W_\mu^a \frac{\tau^a}{2} \quad (13.44b)$$

$$\mathbf{B}_\mu = W_\mu^a \frac{\tau^3}{2} \quad (13.44c)$$

$$\tau^{++} = \tau^+ \otimes \tau^+ \quad (13.44d)$$

$$\tau^+ = \frac{1}{2} (\tau^+ \otimes \tau^3 + \tau^3 + \tau^+) \quad (13.44e)$$

$$\tau^0 = \frac{1}{\sqrt{6}} (\tau^3 \otimes \tau^3 - \tau^+ \otimes \tau^- - \tau^- + \tau^+) \quad (13.44f)$$

$$\tau^- = \frac{1}{2} (\tau^- \otimes \tau^3 + \tau^3 + \tau^-) \quad (13.44g)$$

$$\tau^{--} = \tau^- \otimes \tau^- \quad (13.44h)$$

Scalar Isoscalar

$$\mathcal{L}_\sigma = -\frac{g_\sigma v}{2} \text{tr} [\mathbf{V}_\mu \mathbf{V}^\mu] \sigma \quad (13.45)$$

let *rsigma3* =

[((*O Rsigma*, *G Wp*, *G Wm*), *Scalar_Vector_Vector* 1, *G_SWW*);
 ((*O Rsigma*, *G Z*, *G Z*), *Scalar_Vector_Vector* 1, *G_SZZ*)]

let *rsigma4* =

[(*O Rsigma*, *O Rsigma*, *G Wp*, *G Wm*), *Scalar2_Vector2* 1, *G_SSWW*;
 (*O Rsigma*, *O Rsigma*, *G Z*, *G Z*), *Scalar2_Vector2* 1, *G_SZZ*]

Scalar Isotensor

$$\mathcal{L}_\phi = \frac{g_\phi v}{4} \text{Tr} \left[\left(\mathbf{V}_\mu \otimes \mathbf{V}^\mu - \frac{\tau^{aa}}{6} \text{Tr} [\mathbf{V}_\mu \mathbf{V}^\mu] \right) \phi \right] \quad (13.46a)$$

$$\phi = \sqrt{2} (\phi^{++} \tau^{++} + \phi^+ \tau^+ + \phi^0 \tau^0 + \phi^- \tau^- + \phi^{--} \tau^{--}) \quad (13.46b)$$

let *rphi3* =

[((*O Rphin*, *G Wp*, *G Wm*), *Scalar_Vector_Vector* 1, *G_PNWW*);
 ((*O Rphin*, *G Z*, *G Z*), *Scalar_Vector_Vector* 1, *G_PNZZ*);
 ((*O Rhip*, *G Z*, *G Wm*), *Scalar_Vector_Vector* 1, *G_PWZ*);
 ((*O Rhipp*, *G Wm*, *G Wm*), *Scalar_Vector_Vector* 1, *G_PWW*);
 ((*O Rphim*, *G Wp*, *G Z*), *Scalar_Vector_Vector* 1, *G_PWZ*);
 ((*O Rphimm*, *G Wp*, *G Wp*), *Scalar_Vector_Vector* 1, *G_PWW*)]

Tensor IsoScalar

let *rf3* =

[((*O Rf*, *G Wp*, *G Wm*), *Tensor2_Vector_Vector_1* 1, *G_FWW*);

$$((O \text{ Rf}, G \text{ Z}, G \text{ Z}), \text{Tensor_2_Vector_Vector_1 } 1, G_FZZ)]$$

Tensor Isotensor

$$\mathcal{L}_t \quad (13.47a)$$

```

let rt3 =
  [ ((O Rtn, G Wp, G Wm), Tensor_2_Vector_Vector_1 1, G_TNWW);
    ((O Rtn, G Z, G Z), Tensor_2_Vector_Vector_1 1, G_TNZZ) ;
    ((O Rtp, G Z, G Wm), Tensor_2_Vector_Vector_1 1, G_TWZ) ;
    ((O Rtp, G Wm, G Wm), Tensor_2_Vector_Vector_1 1, G_TWW) ;
    ((O Rtm, G Wp, G Z), Tensor_2_Vector_Vector_1 1, G_TWZ) ;
    ((O Rtm, G Wp, G Wp), Tensor_2_Vector_Vector_1 1, G_TWW) ]

```

Anomalous trilinear interactions $f_i f_j V$ and ttH :

$$\Delta \mathcal{L}_{tt\gamma} = -e \frac{v}{\Lambda^2} \bar{t} i \sigma^{\mu\nu} k_\nu (d_V(k^2) + id_A(k^2) \gamma_5) t A_\mu \quad (13.48)$$

```

let anomalous_ttA =
  if Flags.top_anom then
    [ ((M (U (-3)), G Ga, M (U 3)), FBF (1, Psibar, TVAM, Psi), G_TVA_ttA) ]
  else
    []

```

$$\Delta \mathcal{L}_{bb\gamma} = -e \frac{v}{\Lambda^2} \bar{b} i \sigma^{\mu\nu} k_\nu (d_V(k^2) + id_A(k^2) \gamma_5) b A_\mu \quad (13.49)$$

```

let anomalous_bbA =
  if Flags.top_anom then
    [ ((M (D (-3)), G Ga, M (D 3)), FBF (1, Psibar, TVAM, Psi), G_TVA_bbA) ]
  else
    []

```

$$\Delta \mathcal{L}_{ttg} = -g_s \frac{v}{\Lambda^2} \bar{t} \lambda^a i \sigma^{\mu\nu} k_\nu (d_V(k^2) + id_A(k^2) \gamma_5) t G_\mu^a \quad (13.50)$$

```

let anomalous_ttG =
  if Flags.top_anom then
    [ ((M (U (-3)), G Gl, M (U 3)), FBF (1, Psibar, TVAM, Psi), G_TVA_ttG) ]
  else
    []

```

$$\Delta \mathcal{L}_{ttZ} = -\frac{g}{2c_W} \frac{v^2}{\Lambda^2} \left[\bar{t} \not{Z} (X_L(k^2) P_L + X_R(k^2) P_R) t + \bar{t} \frac{i \sigma^{\mu\nu} k_\nu}{m_Z} (d_V(k^2) + id_A(k^2) \gamma_5) t Z_\mu \right] \quad (13.51)$$

```

let anomalous_ttZ =
  if Flags.top_anom then
    [ ((M (U (-3)), G Z, M (U 3)), FBF (1, Psibar, VLRM, Psi), G_VLR_ttZ);
      ((M (U (-3)), G Z, M (U 3)), FBF (1, Psibar, TVAM, Psi), G_TVA_ttZ) ]

```

```

else
[]

```

$$\Delta\mathcal{L}_{bbZ} = -\frac{g}{2c_W} \frac{v^2}{\Lambda^2} \bar{b} \frac{i\sigma^{\mu\nu} k_\nu}{m_Z} (d_V(k^2) + id_A(k^2)\gamma_5) b Z_\mu \quad (13.52)$$

```

let anomalous_bbZ =
if Flags.top_anom then
[ ((M (D (-3)), G Z, M (D 3)), FBF (1, Psibar, TVAM, Psi), G_TVA_bbZ) ]
else
[]

```

$$\Delta\mathcal{L}_{tbW} = -\frac{g}{\sqrt{2}} \frac{v^2}{\Lambda^2} \left[\bar{b} W^- (V_L(k^2)P_L + V_R(k^2)P_R)t + \bar{b} \frac{i\sigma^{\mu\nu} k_\nu}{m_W} (g_L(k^2)P_L + g_R(k^2)P_R)t W_\mu^- \right] + \text{H.c.} \quad (13.53)$$

```

let anomalous_tbW =
if Flags.top_anom then
[ ((M (D (-3)), G Wm, M (U 3)), FBF (1, Psibar, VLRM, Psi), G_VLR_btW);
  ((M (U (-3)), G Wp, M (D 3)), FBF (1, Psibar, VLRM, Psi), G_VLR_tbW);
  ((M (D (-3)), G Wm, M (U 3)), FBF (1, Psibar, TLRM, Psi), G_TLR_btW);
  ((M (U (-3)), G Wp, M (D 3)), FBF (1, Psibar, TRLM, Psi), G_TRL_tbW) ]
else
[]

```

$$\Delta\mathcal{L}_{ttH} = -\frac{1}{\sqrt{2}} \bar{t} (Y_V(k^2) + iY_A(k^2)\gamma_5) t H \quad (13.54)$$

```

let anomalous_ttH =
if Flags.top_anom then
[ ((M (U (-3)), O H, M (U 3)), FBF (1, Psibar, SPM, Psi), G_SP_ttH) ]
else
[]

```

quartic fermion-gauge interactions $f_i f_j V_1 V_2$ emerging from gauge-invariant effective operators:

$$\Delta\mathcal{L}_{ttgg} = -\frac{g_s^2}{2} f_{abc} \frac{v}{\Lambda^2} \bar{t} \lambda^a \sigma^{\mu\nu} (d_V(k^2) + id_A(k^2)\gamma_5) t G_\mu^b G_\nu^c \quad (13.55)$$

```

let anomalous_ttGG =
if Flags.top_anom then
[ ((M (U (-3)), O (Aux_top (2,1,0,true,TTGG)), M (U 3)), FBF (1, Psibar, TVA, Psi), G_TVA
  ((O (Aux_top (2,1,0,false,TTGG)), G Gl, G Gl), Aux_Gauge_Gauge 1, I_Gs) ]
else
[]

```

$$\Delta\mathcal{L}_{tbWA} = -i \sin \theta_w \frac{g^2}{2\sqrt{2}} \frac{v^2}{\Lambda^2} \left[\bar{b} \frac{\sigma^{\mu\nu}}{m_W} (g_L(k^2)P_L + g_R(k^2)P_R) t A_\mu W_\nu^- \right] + \text{H.c.} \quad (13.56)$$

```

let anomalous_tbWA =
  if Flags.top_anom then
    [ ((M (D (-3)), O (Aux_top (2, 0, -1, true, TBWA)), M (U 3)), FBF (1, Psibar, TLR, Psi), G_TL
      ((O (Aux_top (2, 0, 1, false, TBWA)), G Ga, G Wm), Aux_Gauge_Gauge 1, I_G_weak);
      ((M (U (-3)), O (Aux_top (2, 0, 1, true, TBWA)), M (D 3)), FBF (1, Psibar, TRL, Psi), G_TRL
      ((O (Aux_top (2, 0, -1, false, TBWA)), G Wp, G Ga), Aux_Gauge_Gauge 1, I_G_weak) ]
  else
    []

```

$$\Delta\mathcal{L}_{tbWZ} = -i \cos\theta_w \frac{g^2}{2\sqrt{2}} \frac{v^2}{\Lambda^2} \left[\bar{b} \frac{\sigma^{\mu\nu}}{m_W} (g_L(k^2)P_L + g_R(k^2)P_R) t Z_\mu W_\nu^- \right] + \text{H.c.} \quad (13.57)$$

```

let anomalous_tbWZ =
  if Flags.top_anom then
    [ ((M (D (-3)), O (Aux_top (2, 0, -1, true, TBWZ)), M (U 3)), FBF (1, Psibar, TLR, Psi), G_TL
      ((O (Aux_top (2, 0, 1, false, TBWZ)), G Z, G Wm), Aux_Gauge_Gauge 1, I_G_weak);
      ((M (U (-3)), O (Aux_top (2, 0, 1, true, TBWZ)), M (D 3)), FBF (1, Psibar, TRL, Psi), G_TRL
      ((O (Aux_top (2, 0, -1, false, TBWZ)), G Wp, G Z), Aux_Gauge_Gauge 1, I_G_weak) ]
  else
    []

```

$$\Delta\mathcal{L}_{ttWW} = -i \frac{g^2}{2} \frac{v^2}{\Lambda^2} \bar{t} \frac{\sigma^{\mu\nu}}{m_W} (d_V(k^2) + i d_A(k^2) \gamma_5) t W_\mu^- W_\nu^+ \quad (13.58)$$

```

let anomalous_ttWW =
  if Flags.top_anom then
    [ ((M (U (-3)), O (Aux_top (2, 0, 0, true, TTWW)), M (U 3)), FBF (1, Psibar, TVA, Psi), G_TVA
      ((O (Aux_top (2, 0, 0, false, TTWW)), G Wm, G Wp), Aux_Gauge_Gauge 1, I_G_weak) ]
  else
    []

```

$$\Delta\mathcal{L}_{bbWW} = -i \frac{g^2}{2} \frac{v^2}{\Lambda^2} \bar{b} \frac{\sigma^{\mu\nu}}{m_W} (d_V(k^2) + i d_A(k^2) \gamma_5) b W_\mu^- W_\nu^+ \quad (13.59)$$

```

let anomalous_bbWW =
  if Flags.top_anom then
    [ ((M (D (-3)), O (Aux_top (2, 0, 0, true, BBWW)), M (D 3)), FBF (1, Psibar, TVA, Psi), G_TVA
      ((O (Aux_top (2, 0, 0, false, BBWW)), G Wm, G Wp), Aux_Gauge_Gauge 1, I_G_weak) ]
  else
    []

```

4-fermion contact terms emerging from operator rewriting:

```

let anomalous_top_qGuG_tt =
  [ ((M (U (-3)), O (Aux_top (1, 1, 0, true, QGUG)), M (U 3)), FBF (1, Psibar, VLR, Psi), G_VLR_q
let anomalous_top_qGuG_ff n =
  List.map mom
    [ ((U (-n), Aux_top (1, 1, 0, false, QGUG), U n), FBF (1, Psibar, V, Psi), Unit);
      ((D (-n), Aux_top (1, 1, 0, false, QGUG), D n), FBF (1, Psibar, V, Psi), Unit) ]

```

```

let anomalous_top_qGuG =
  if Flags.top_anom_4f then
    anomalous_top_qGuG_tt @ ThoList.flatmap anomalous_top_qGuG_ff [1; 2; 3]
  else
    []

let anomalous_top_qBuB_tt =
  [((M (U (-3)), O (Aux_top (1, 0, 0, true, QBUB)), M (U 3)), FBF (1, Psibar, VLR, Psi), G_VLR_q
let anomalous_top_qBuB_ff n =
  List.map mom
  [((U (-n), Aux_top (1, 0, 0, false, QBUB), U n), FBF (1, Psibar, VLR, Psi), G_VLR_qBuB_u);
    ((D (-n), Aux_top (1, 0, 0, false, QBUB), D n), FBF (1, Psibar, VLR, Psi), G_VLR_qBuB_d);
    ((L (-n), Aux_top (1, 0, 0, false, QBUB), L n), FBF (1, Psibar, VLR, Psi), G_VLR_qBuB_e);
    ((N (-n), Aux_top (1, 0, 0, false, QBUB), N n), FBF (1, Psibar, VL, Psi), G_VL_qBuB_n)]

let anomalous_top_qBuB =
  if Flags.top_anom_4f then
    anomalous_top_qBuB_tt @ ThoList.flatmap anomalous_top_qBuB_ff [1; 2; 3]
  else
    []

let anomalous_top_qW_tq =
  [((M (U (-3)), O (Aux_top (1, 0, 0, true, QW)), M (U 3)), FBF (1, Psibar, VL, Psi), G_VL_qW);
    ((M (D (-3)), O (Aux_top (1, 0, -1, true, QW)), M (U 3)), FBF (1, Psibar, VL, Psi), G_VL_qW);
    ((M (U (-3)), O (Aux_top (1, 0, 1, true, QW)), M (D 3)), FBF (1, Psibar, VL, Psi), G_VL_qW)]

let anomalous_top_qW_ff n =
  List.map mom
  [((U (-n), Aux_top (1, 0, 0, false, QW), U n), FBF (1, Psibar, VL, Psi), G_VL_qW_u);
    ((D (-n), Aux_top (1, 0, 0, false, QW), D n), FBF (1, Psibar, VL, Psi), G_VL_qW_d);
    ((N (-n), Aux_top (1, 0, 0, false, QW), N n), FBF (1, Psibar, VL, Psi), G_VL_qW_u);
    ((L (-n), Aux_top (1, 0, 0, false, QW), L n), FBF (1, Psibar, VL, Psi), G_VL_qW_d);
    ((D (-n), Aux_top (1, 0, -1, false, QW), U n), FBF (1, Psibar, VL, Psi), Half);
    ((U (-n), Aux_top (1, 0, 1, false, QW), D n), FBF (1, Psibar, VL, Psi), Half);
    ((L (-n), Aux_top (1, 0, -1, false, QW), N n), FBF (1, Psibar, VL, Psi), Half);
    ((N (-n), Aux_top (1, 0, 1, false, QW), L n), FBF (1, Psibar, VL, Psi), Half)]

let anomalous_top_qW =
  if Flags.top_anom_4f then
    anomalous_top_qW_tq @ ThoList.flatmap anomalous_top_qW_ff [1; 2; 3]
  else
    []

let anomalous_top_DuDd =
  if Flags.top_anom_4f then
    [((M (U (-3)), O (Aux_top (0, 0, 0, true, DR)), M (U 3)), FBF (1, Psibar, SR, Psi), Half);
      ((M (U (-3)), O (Aux_top (0, 0, 0, false, DR)), M (U 3)), FBF (1, Psibar, SL, Psi), G_SL_DttR);
      ((M (D (-3)), O (Aux_top (0, 0, 0, false, DR)), M (D 3)), FBF (1, Psibar, SR, Psi), G_SR_DttR);
      ((M (U (-3)), O (Aux_top (0, 0, 0, true, DL)), M (U 3)), FBF (1, Psibar, SL, Psi), Half);
      ((M (D (-3)), O (Aux_top (0, 0, 0, false, DL)), M (D 3)), FBF (1, Psibar, SL, Psi), G_SL_DttL);
      ((M (D (-3)), O (Aux_top (0, 0, -1, true, DR)), M (U 3)), FBF (1, Psibar, SR, Psi), Half);
      ((M (U (-3)), O (Aux_top (0, 0, 1, false, DR)), M (D 3)), FBF (1, Psibar, SLR, Psi), G_SLR_D);
      ((M (D (-3)), O (Aux_top (0, 0, -1, true, DL)), M (U 3)), FBF (1, Psibar, SL, Psi), Half);
  ]

```



```

      ((M (U (-3)), O (Aux_top (0,0,1,false,DL)), M (D 3)), FBF (1, Psibar, SL, Psi), G_SL_DbtL)
    else
      []
  let vertices3 =
    (ThoList.flatmap electromagnetic_currents [1;2;3] @
     ThoList.flatmap color_currents [1;2;3] @
     ThoList.flatmap neutral_currents [1;2;3] @
     (if Flags.ckm_present then
        charged_currents_ckm
      else
        charged_currents_triv) @
     yukawa @ triple_gauge @
     gauge_higgs @ higgs @ higgs_triangle_vertices
     @ goldstone_vertices @
     rsigma3 @ rphi3 @ rf3 @ rt3 @
     anomalous_ttA @ anomalous_bbA @
     anomalous_ttZ @ anomalous_bbZ @
     anomalous_tbW @ anomalous_tbWA @ anomalous_tbWZ @
     anomalous_ttWW @ anomalous_bbWW @
     anomalous_ttG @ anomalous_ttGG @
     anomalous_ttH @
     anomalous_top_qGuG @ anomalous_top_qBuB @
     anomalous_top_qW @ anomalous_top_DuDd)
  let vertices4 =
    quartic_gauge @ gauge_higgs4 @ higgs4 @ rsigma4
  let vertices () = (vertices3, vertices4, [])

```

For efficiency, make sure that *F.of_vertices vertices* is evaluated only once.

```

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let flavor_of_string = function
| "e-" → M (L 1) | "e+" → M (L (-1))
| "mu-" → M (L 2) | "mu+" → M (L (-2))
| "tau-" → M (L 3) | "tau+" → M (L (-3))
| "nue" → M (N 1) | "nuebar" → M (N (-1))
| "numu" → M (N 2) | "numubar" → M (N (-2))
| "nutau" → M (N 3) | "nutaubar" → M (N (-3))
| "u" → M (U 1) | "ubar" → M (U (-1))
| "c" → M (U 2) | "cbar" → M (U (-2))
| "t" → M (U 3) | "tbar" → M (U (-3))
| "d" → M (D 1) | "dbar" → M (D (-1))
| "s" → M (D 2) | "sbar" → M (D (-2))
| "b" → M (D 3) | "bbar" → M (D (-3))
| "g" | "g1" → G Gl
| "A" → G Ga | "Z" | "Z0" → G Z

```

```

| "W+" → G Wp | "W-" → G Wm
| "H" → O H | "Rsigma" → O Rsigma
| "Rphi0" → O Rphin
| "Rphi+" → O Rhip | "Rphi-" → O Rphim
| "Rphi++" → O Rhip | "Rphi--" → O Rphimm
| "Rf" → O Rf
| "Rt0" → O Rtn
| "Rt+" → O Rtp | "Rt-" → O Rtm
| "Rt++" → O Rtp | "Rt--" → O Rtmm
| "Aux_t_ttGG0" → O (Aux_top (2, 1, 0, true, TTGG)) | "Aux_ttGG0" →
O (Aux_top (2, 1, 0, false, TTGG))
| "Aux_t_tbWA+" → O (Aux_top (2, 0, 1, true, TBWA)) | "Aux_tbWA+" →
O (Aux_top (2, 0, 1, false, TBWA))
| "Aux_t_tbWA-" → O (Aux_top (2, 0, -1, true, TBWA)) | "Aux_tbWA-" →
O (Aux_top (2, 0, -1, false, TBWA))
| "Aux_t_tbWZ+" → O (Aux_top (2, 0, 1, true, TBWZ)) | "Aux_tbWZ+" →
O (Aux_top (2, 0, 1, false, TBWZ))
| "Aux_t_tbWZ-" → O (Aux_top (2, 0, -1, true, TBWZ)) | "Aux_tbWZ-" →
O (Aux_top (2, 0, -1, false, TBWZ))
| "Aux_t_ttWW0" → O (Aux_top (2, 0, 0, true, TTWW)) | "Aux_ttWW0" →
O (Aux_top (2, 0, 0, false, TTWW))
| "Aux_t_bbWW0" → O (Aux_top (2, 0, 0, true, BBWW)) | "Aux_bbWW0" →
O (Aux_top (2, 0, 0, false, BBWW))
| "Aux_t_qGuG0" → O (Aux_top (1, 1, 0, true, QGUG)) | "Aux_qGuG0" →
O (Aux_top (1, 1, 0, false, QGUG))
| "Aux_t_qBuB0" → O (Aux_top (1, 0, 0, true, QBUB)) | "Aux_qBuB0" →
O (Aux_top (1, 0, 0, false, QBUB))
| "Aux_t_qW0" → O (Aux_top (1, 0, 0, true, QW)) | "Aux_qW0" →
O (Aux_top (1, 0, 0, false, QW))
| "Aux_t_qW+" → O (Aux_top (1, 0, 1, true, QW)) | "Aux_qW+" →
O (Aux_top (1, 0, 1, false, QW))
| "Aux_t_qW-" → O (Aux_top (1, 0, -1, true, QW)) | "Aux_qW-" →
O (Aux_top (1, 0, -1, false, QW))
| "Aux_t_dL0" → O (Aux_top (0, 0, 0, true, DL)) | "Aux_dL0" →
O (Aux_top (0, 0, 0, false, DL))
| "Aux_t_dL+" → O (Aux_top (0, 0, 1, true, DL)) | "Aux_dL+" →
O (Aux_top (0, 0, 1, false, DL))
| "Aux_t_dL-" → O (Aux_top (0, 0, -1, true, DL)) | "Aux_dL-" →
O (Aux_top (0, 0, -1, false, DL))
| "Aux_t_dR0" → O (Aux_top (0, 0, 0, true, DR)) | "Aux_dR0" →
O (Aux_top (0, 0, 0, false, DR))
| "Aux_t_dR+" → O (Aux_top (0, 0, 1, true, DR)) | "Aux_dR+" →
O (Aux_top (0, 0, 1, false, DR))
| "Aux_t_dR-" → O (Aux_top (0, 0, -1, true, DR)) | "Aux_dR-" →
O (Aux_top (0, 0, -1, false, DR))
| _ → invalid_arg "Modellib_BSM.VBS.flavor_of_string"

let flavor_to_string = function
| M f →
begin match f with

```

```

| L 1 → "e-" | L (-1) → "e+"
| L 2 → "mu-" | L (-2) → "mu+"
| L 3 → "tau-" | L (-3) → "tau+"
| L _ → invalid_arg
      "Modellib_BSM.VBS.flavor_to_string:␣invalid␣lepton"
| N 1 → "nue" | N (-1) → "nuebar"
| N 2 → "numu" | N (-2) → "numubar"
| N 3 → "nutau" | N (-3) → "nutaubar"
| N _ → invalid_arg
      "Modellib_BSM.VBS.flavor_to_string:␣invalid␣neutrino"
| U 1 → "u" | U (-1) → "ubar"
| U 2 → "c" | U (-2) → "cbar"
| U 3 → "t" | U (-3) → "tbar"
| U _ → invalid_arg
      "Modellib_BSM.VBS.flavor_to_string:␣invalid␣up␣type␣quark"
| D 1 → "d" | D (-1) → "dbar"
| D 2 → "s" | D (-2) → "sbar"
| D 3 → "b" | D (-3) → "bbar"
| D _ → invalid_arg
      "Modellib_BSM.VBS.flavor_to_string:␣invalid␣down␣type␣quark"
end
| G f →
  begin match f with
  | Gl → "gl"
  | Ga → "A" | Z → "Z"
  | Wp → "W+" | Wm → "W-"
  end
| O f →
  begin match f with
  | Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
  | H → "H" | Rsigma → "Rsigma"
  | Rphin → "Rphin" | Rhip → "Rphi+" | Rphim → "Rphi-"
  | Rhipp → "Rphi++" | Rphimm → "Rphi--"
  | Rf → "Rf"
  | Rtn → "Rtn" | Rtp → "Rt+" | Rtm → "Rt-"
  | Rtp → "Rt++" | Rtm → "Rt--"
  | Aux_top (_, _, ch, n, v) → "Aux_" ^ (if n then "t_" else "") ^ (
    begin match v with
    | TTGG → "ttGG" | TBWA → "tbWA" | TBWZ →
      "tbWZ"
    | TTWW → "ttWW" | BBWW → "bbWW"
    | QGUG → "qGuG" | QBUB → "qBuB"
    | QW → "qW" | DL → "dL" | DR → "dR"
    end ) ^ ( if ch > 0 then "+" else if ch < 0 then "-" else "0" )
  end
let flavor_to_TeX = function
| M f →
  begin match f with
  | L 1 → "e^-" | L (-1) → "e^+"

```

```

| L 2 → "\\mu^- " | L (-2) → "\\mu^+"
| L 3 → "\\tau^- " | L (-3) → "\\tau^+"
| L _ → invalid_arg
      "Modellib_BSM.VBS.flavor_to_TeX:␣invalid␣lepton"
| N 1 → "\\nu_e " | N (-1) → "\\bar{\\nu}_e"
| N 2 → "\\nu_\\mu " | N (-2) → "\\bar{\\nu}_\\mu"
| N 3 → "\\nu_\\tau " | N (-3) → "\\bar{\\nu}_\\tau"
| N _ → invalid_arg
      "Modellib_BSM.VBS.flavor_to_TeX:␣invalid␣neutrino"
| U 1 → "u " | U (-1) → "\\bar{u}"
| U 2 → "c " | U (-2) → "\\bar{c}"
| U 3 → "t " | U (-3) → "\\bar{t}"
| U _ → invalid_arg
      "Modellib_BSM.VBS.flavor_to_TeX:␣invalid␣up␣type␣quark"
| D 1 → "d " | D (-1) → "\\bar{d}"
| D 2 → "s " | D (-2) → "\\bar{s}"
| D 3 → "b " | D (-3) → "\\bar{b}"
| D _ → invalid_arg
      "Modellib_BSM.VBS.flavor_to_TeX:␣invalid␣down␣type␣quark"
end
| G f →
  begin match f with
  | Gl → "g"
  | Ga → "\\gamma" | Z → "Z"
  | Wp → "W^+" | Wm → "W^- "
  end
| O f →
  begin match f with
  | Phip → "\\phi^+" | Phim → "\\phi^- " | Phi0 →
    "\\phi^0"
  | H → "H" | Rsigma → "\\sigma"
  | Rhip → "\\phi^+" | Rphim → "\\phi^- " | Rphin →
    "\\phi^0"
  | Rhipp → "\\phi^{++}" | Rphimm → "\\phi^{--}"
  | Rf → "f"
  | Rtp → "t^+" | Rtm → "t^- " | Rtn → "t^0"
  | Rtp → "t^{++}" | Rtm → "t^{--}"
  | Aux_top (_, -, ch, n, v) → "\\textnormal{Aux}_" ^ (if n then "t_" else "") ^ (
    begin match v with
    | TTGG → "ttGG" | TBWA → "tbWA" | TBWZ →
      "tbWZ"
    | TTWW → "ttWW" | BBWW → "bbWW"
    | QGUG → "qGuG" | QBUB → "qBuB"
    | QW → "qW" | DL → "dL" | DR → "dR"
    end) ^ (if ch > 0 then "^+" else if ch < 0 then "^-" else "^0") ^ "}"
  end
let flavor_symbol = function
| M f →
  begin match f with

```

```

| L n when n > 0 → "l" ^ string_of_int n
| L n → "l" ^ string_of_int (abs n) ^ "b"
| N n when n > 0 → "n" ^ string_of_int n
| N n → "n" ^ string_of_int (abs n) ^ "b"
| U n when n > 0 → "u" ^ string_of_int n
| U n → "u" ^ string_of_int (abs n) ^ "b"
| D n when n > 0 → "d" ^ string_of_int n
| D n → "d" ^ string_of_int (abs n) ^ "b"
end
| G f →
  begin match f with
  | Gl → "gl"
  | Ga → "a" | Z → "z"
  | Wp → "wp" | Wm → "wm"
  end
| O f →
  begin match f with
  | Phip → "pp" | Phim → "pm" | Phi0 → "p0"
  | H → "h" | Rsigma → "rsi"
  | Rhip → "rpp" | Rphim → "rpm" | Rphin → "rpn"
  | Rhipp → "rppp" | Rphimm → "rpmm"
  | Rf → "rf"
  | Rtp → "rtp" | Rtm → "rtm" | Rtn → "rtn"
  | Rtp → "rtpp" | Rtm → "rtmm"
  | Aux_top (_, _, ch, n, v) → "aux_" ^ (if n then "t_" else "") ^ (
    begin match v with
    | TTGG → "ttgg" | TBWA → "tbwa" | TBWZ →
"tbwz"
    | TTWW → "ttww" | BBWW → "bbww"
    | QGUG → "qgug" | QBUB → "qbub"
    | QW → "qw" | DL → "dl" | DR → "dr"
    end) ^ "-" ^ (if ch > 0 then "p" else if ch < 0 then "m" else "0")
  end
end

```

Introducing new Resonances from 45, there are no PDG values

```

let pdg = function
| M f →
  begin match f with
  | L n when n > 0 → 9 + 2 × n
  | L n → - 9 + 2 × n
  | N n when n > 0 → 10 + 2 × n
  | N n → - 10 + 2 × n
  | U n when n > 0 → 2 × n
  | U n → 2 × n
  | D n when n > 0 → - 1 + 2 × n
  | D n → 1 + 2 × n
  end
| G f →
  begin match f with
  | Gl → 21
  end
end

```

```

      |  $G_a \rightarrow 22$  |  $Z \rightarrow 23$ 
      |  $W_p \rightarrow 24$  |  $W_m \rightarrow (-24)$ 
    end
  |  $O f \rightarrow$ 
    begin match  $f$  with
    |  $Phip$  |  $Phim \rightarrow 27$  |  $Phi0 \rightarrow 26$ 
    |  $H \rightarrow 25$  |  $Rsigma \rightarrow 45$ 
    |  $Rphin \rightarrow 46$  |  $Rhiph$  |  $Rphim \rightarrow 47$ 
    |  $Rhipp$  |  $Rphimm \rightarrow 48$ 
    |  $Rf \rightarrow 52$ 
    |  $Rtn \rightarrow 53$  |  $Rtp$  |  $Rtm \rightarrow 54$ 
    |  $Rtpp$  |  $Rtmm \rightarrow 55$ 
    |  $Aux\_top(-, -, -, -, -) \rightarrow 81$ 
    end

let mass_symbol  $f =$ 
  "mass(" ^ string_of_int (abs (pdg  $f$ )) ^ ")"

let width_symbol  $f =$ 
  "width(" ^ string_of_int (abs (pdg  $f$ )) ^ ")"

let constant_symbol = function
|  $Unit \rightarrow$  "unit" |  $Half \rightarrow$  "half" |  $Pi \rightarrow$  "PI"
|  $Alpha\_QED \rightarrow$  "alpha" |  $E \rightarrow$  "e" |  $G\_weak \rightarrow$  "g" |  $Vev \rightarrow$ 
"vev"
|  $I\_G\_weak \rightarrow$  "ig"
|  $Sin2thw \rightarrow$  "sin2thw" |  $Sinthw \rightarrow$  "sinthw" |  $Costhw \rightarrow$ 
"costhw"
|  $Q\_lepton \rightarrow$  "qllep" |  $Q\_up \rightarrow$  "qup" |  $Q\_down \rightarrow$  "qdown"
|  $G\_NC\_lepton \rightarrow$  "gnclep" |  $G\_NC\_neutrino \rightarrow$  "gncneu"
|  $G\_NC\_up \rightarrow$  "gncup" |  $G\_NC\_down \rightarrow$  "gncdown"
|  $G\_TVA\_ttA \rightarrow$  "gtva\_tta" |  $G\_TVA\_bbA \rightarrow$  "gtva\_bba"
|  $G\_VLR\_ttZ \rightarrow$  "gvlr\_ttz" |  $G\_TVA\_ttZ \rightarrow$  "gtva\_ttz" |
 $G\_TVA\_bbZ \rightarrow$  "gtva\_bbz"
|  $G\_VLR\_btW \rightarrow$  "gvlr\_btw" |  $G\_VLR\_tbW \rightarrow$  "gvlr\_tbw"
|  $G\_TLR\_btW \rightarrow$  "gtlr\_btw" |  $G\_TRL\_tbW \rightarrow$  "gtrl\_tbw"
|  $G\_TLR\_btWA \rightarrow$  "gtlr\_btwa" |  $G\_TRL\_tbWA \rightarrow$  "gtrl\_tbwa"
|  $G\_TLR\_btWZ \rightarrow$  "gtlr\_btwz" |  $G\_TRL\_tbWZ \rightarrow$  "gtrl\_tbwz"
|  $G\_TVA\_ttWW \rightarrow$  "gtva\_ttww" |  $G\_TVA\_bbWW \rightarrow$  "gtva\_bbww"
|  $G\_TVA\_ttG \rightarrow$  "gtva\_ttg" |  $G\_TVA\_ttGG \rightarrow$  "gtva\_ttgg"
|  $G\_SP\_ttH \rightarrow$  "gsp\_tth"
|  $G\_VLR\_qGuG \rightarrow$  "gvlr\_qgug"
|  $G\_VLR\_qBuB \rightarrow$  "gvlr\_qbub"
|  $G\_VLR\_qBuB\_u \rightarrow$  "gvlr\_qbub\_u" |  $G\_VLR\_qBuB\_d \rightarrow$  "gvlr\_qbub\_d"
|  $G\_VLR\_qBuB\_e \rightarrow$  "gvlr\_qbub\_e" |  $G\_VL\_qBuB\_n \rightarrow$  "gvl\_qbub\_n"
|  $G\_VL\_qW \rightarrow$  "gvl\_qw"
|  $G\_VL\_qW\_u \rightarrow$  "gvl\_qw\_u" |  $G\_VL\_qW\_d \rightarrow$  "gvl\_qw\_d"
|  $G\_SL\_DttR \rightarrow$  "gsl\_dttr" |  $G\_SR\_DttR \rightarrow$  "gsr\_dttr" |
 $G\_SL\_DttL \rightarrow$  "gsl\_dttl"
|  $G\_SLR\_DbtR \rightarrow$  "gslr\_dbtr" |  $G\_SL\_DbtL \rightarrow$  "gsl\_dbtl"
|  $G\_CC \rightarrow$  "gcc"
|  $G\_CCQ(n1, n2) \rightarrow$  "gccq" ^ string_of_int  $n1$  ^ string_of_int  $n2$ 

```

```

| I_Q_W → "iqw" | I_G_ZWW → "igzww"
| G_WWWW → "gw4" | G_ZZWW → "gzzww"
| G_AZWW → "gazww" | G_AAWW → "gaaww"
| I_G1_AWW → "ig1a" | I_G1_ZWW → "ig1z"
| I_G1_plus_kappa_plus_G4_AWW → "ig1pkpg4a"
| I_G1_plus_kappa_plus_G4_ZWW → "ig1pkpg4z"
| I_G1_plus_kappa_minus_G4_AWW → "ig1pkmg4a"
| I_G1_plus_kappa_minus_G4_ZWW → "ig1pkmg4z"
| I_G1_minus_kappa_plus_G4_AWW → "ig1mkpg4a"
| I_G1_minus_kappa_plus_G4_ZWW → "ig1mkpg4z"
| I_G1_minus_kappa_minus_G4_AWW → "ig1mkmg4a"
| I_G1_minus_kappa_minus_G4_ZWW → "ig1mkmg4z"
| I_lambda_AWW → "ila"
| I_lambda_ZWW → "ilz"
| G5_AWW → "rg5a"
| G5_ZWW → "rg5z"
| I_kappa5_AWW → "ik5a"
| I_kappa5_ZWW → "ik5z"
| I_lambda5_AWW → "il5a" | I_lambda5_ZWW → "il5z"
| Alpha_WWWW0 → "alww0" | Alpha_WWWW2 → "alww2"
| Alpha_ZZWW0 → "alzw0" | Alpha_ZZWW1 → "alzw1"
| Alpha_ZZZZ → "alzz"
| D_Alpha_ZZWW0_S → "dalzz0_s(gkm,mkm,"
| D_Alpha_ZZWW0_T → "dalzz0_t(gkm,mkm,"
| D_Alpha_ZZWW1_S → "dalzz1_s(gkm,mkm,"
| D_Alpha_ZZWW1_T → "dalzz1_t(gkm,mkm,"
| D_Alpha_ZZWW1_U → "dalzz1_u(gkm,mkm,"
| D_Alpha_WWWW0_S → "dalww0_s(gkm,mkm,"
| D_Alpha_WWWW0_T → "dalww0_t(gkm,mkm,"
| D_Alpha_WWWW0_U → "dalww0_u(gkm,mkm,"
| D_Alpha_WWWW2_S → "dalww2_s(gkm,mkm,"
| D_Alpha_WWWW2_T → "dalww2_t(gkm,mkm,"
| D_Alpha_ZZZZ_S → "dalz4_s(gkm,mkm,"
| D_Alpha_ZZZZ_T → "dalz4_t(gkm,mkm,"
| G_HWW → "ghww" | G_HZZ → "ghzz"
| G_HHWW → "ghhww" | G_HHZZ → "ghhzz"
| G_SWW → "gsww" | G_SZZ → "gszz"
| G_PNWW → "gpnww" | G_PNZZ → "gpnzz"
| G_PWZ → "gpwz" | G_PWW → "gpww"
| G_FWW → "gfw" | G_FZZ → "gfzz"
| G_TNWW → "gtnww" | G_TNZZ → "gtnzz"
| G_TWZ → "gtwz" | G_TWW → "gtww"
| G_SSWW → "gssww" | G_SSZZ → "gsszz"
| G_Htt → "ghtt" | G_Hbb → "ghbb"
| G_Htautau → "ghtautau" | G_Hcc → "ghcc" | G_Hmm →
"ghmm"
| G_HGaZ → "ghgaz" | G_HGaGa → "ghgaga" | G_Hgg →
"ghgg"
| G_HGaGa_anom → "ghgaga_ac" | G_HGaZ_anom → "ghgaz_ac"
| G_HZZ_anom → "ghzz_ac" | G_HWW_anom → "ghww_ac"

```

```

| G_HGaZ_u → "ghgaz_u" | G_HZZ_u → "ghzz_u"
| G_HWW_u → "ghww_u"
| G_H3 → "gh3" | G_H4 → "gh4"
| Gs → "gs" | I_Gs → "igs" | G2 → "gs**2"
| Mass f → "mass" ^ flavor_symbol f
| Width f → "width" ^ flavor_symbol f
| K_Matrix_Coeff i → "kc" ^ string_of_int i
| K_Matrix_Pole i → "kp" ^ string_of_int i
end

```

13.7 Interface of *Modellib_MSSM*

13.7.1 More Hardcoded Models

```

module type MSSM_flags =
  sig
    val include_goldstone : bool
    val include_four : bool
    val ckm_present : bool
    val gravitino : bool
    val higgs_triangle : bool
  end

module MSSM_no_goldstone : MSSM_flags
module MSSM_goldstone : MSSM_flags
module MSSM_no_4 : MSSM_flags
module MSSM_no_4_ckm : MSSM_flags
module MSSM_Grav : MSSM_flags
module MSSM_Hgg : MSSM_flags
module MSSM : functor (F : MSSM_flags) → Model.T with module Ch = Charges.QQ

```

13.8 Implementation of *Modellib_MSSM*

Id : *modellib_MSSM.ml*45382013-08-23 16:09:06Zjr_reuter

```

let rcs_file = RCS.parse "Modellib_MSSM" ["MSSM"]
{ RCS.revision = "$Revision: 4538$";
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
  RCS.author = "$Author: jr-reuter$";
  RCS.source
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg

```

13.8.1 Minimal Supersymmetric Standard Model

```

module type MSSM_flags =
  sig
    val include_goldstone : bool

```



```

    val include_four : bool
    val ckm_present : bool
    val gravitino : bool
    val higgs_triangle : bool
  end

module MSSM_no_goldstone : MSSM_flags =
  struct
    let include_goldstone = false
    let include_four = true
    let ckm_present = false
    let gravitino = false
    let higgs_triangle = false
  end

module MSSM_goldstone : MSSM_flags =
  struct
    let include_goldstone = true
    let include_four = true
    let ckm_present = false
    let gravitino = false
    let higgs_triangle = false
  end

module MSSM_no_4 : MSSM_flags =
  struct
    let include_goldstone = false
    let include_four = false
    let ckm_present = false
    let gravitino = false
    let higgs_triangle = false
  end

module MSSM_no_4_ckm : MSSM_flags =
  struct
    let include_goldstone = false
    let include_four = false
    let ckm_present = true
    let gravitino = false
    let higgs_triangle = false
  end

module MSSM_Grav : MSSM_flags =
  struct
    let include_goldstone = false
    let include_four = false
    let ckm_present = false
    let gravitino = true
    let higgs_triangle = false
  end

module MSSM_Hgg : MSSM_flags =
  struct

```

```

    let include_goldstone = false
    let include_four = false
    let ckm_present = false
    let gravitino = false
    let higgs_triangle = true
  end

module MSSM (Flags : MSSM_flags) =
  struct
    let rcs = RCS.rename rcs_file "Modellib_MSSM.MSSM"
      [ "MSSM" ]

    open Coupling

    let default_width = ref Timelike
    let use_fudged_width = ref false

    let options = Options.create
      [ "constant_width", Arg.Unit (fun () → default_width := Constant),
        "use_constant_width_also_in_t-channel";
        "fudged_width", Arg.Set use_fudged_width,
        "use_fudge_factor_for_charge_particle_width";
        "custom_width", Arg.String (fun f → default_width := Custom f),
        "use_custom_width";
        "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
        "use_vanishing_width"]

    type gen =
      | G of int | GG of gen × gen

    let rec string_of_gen = function
      | G n when n > 0 → string_of_int n
      | G n → string_of_int (abs n) ^ "c"
      | GG (g1, g2) → string_of_gen g1 ^ "-" ^ string_of_gen g2
  end

```

With this we distinguish the flavour.

```

type sff =
  | SL | SN | SU | SD

let string_of_sff = function
  | SL → "s1" | SN → "sn" | SU → "su" | SD → "sd"

```

With this we distinguish the mass eigenstates. At the moment we have to cheat a little bit for the sneutrinos. Because we are dealing with massless neutrinos there is only one sort of sneutrino.

```

type sfm =
  | M1 | M2

let string_of_sfm = function
  | M1 → "1" | M2 → "2"

```

We also introduce special types for the charginos and neutralinos.

```

type char =
  | C1 | C2 | C1c | C2c

```

```

type neu =
  | N1 | N2 | N3 | N4
let int_of_char = function
  | C1 → 1 | C2 → 2 | C1c → -1 | C2c → -2
let string_of_char = function
  | C1 → "1" | C2 → "2" | C1c → "-1" | C2c → "-2"
let conj_char = function
  | C1 → C1c | C2 → C2c | C1c → C1 | C2c → C2
let string_of_neu = function
  | N1 → "1" | N2 → "2" | N3 → "3" | N4 → "4"

```

Also we need types to distinguish the Higgs bosons. We follow the conventions of Kuroda, which means

$$H_1 = \begin{pmatrix} \frac{1}{\sqrt{2}}(v_1 + H^0 \cos \alpha - h^0 \sin \alpha + iA^0 \sin \beta - i\phi^0 \cos \beta) \\ H^- \sin \beta - \phi^- \cos \beta \end{pmatrix}, \quad (13.60)$$

$$H_2 = \begin{pmatrix} H^+ \cos \beta + \phi^+ \sin \beta \\ \frac{1}{\sqrt{2}}(v_2 + H^0 \sin \alpha + h^0 \cos \alpha + iA^0 \cos \beta + i\phi^0 \sin \beta) \end{pmatrix} \quad (13.61)$$

This is a different sign convention compared to, e.g., Weinberg's volume iii. We will refer to it as *GS+*.

```

type higgs =
  | H1 (* the light scalar Higgs *)
  | H2 (* the heavy scalar Higgs *)
  | H3 (* the pseudoscalar Higgs *)
  | H4 (* the charged Higgs *)
  | H5 (* the neutral Goldstone boson *)
  | H6 (* the charged Goldstone boson *)
  | DH of higgs × higgs
let rec string_of_higgs = function
  | H1 → "h1" | H2 → "h2" | H3 → "h3" | H4 → "h4"
  | H5 → "p1" | H6 → "p2"
  | DH (h1, h2) → string_of_higgs h1 ^ string_of_higgs h2
type flavor =
  | L of int | N of int
  | U of int | D of int
  | Sup of sfm × int | Sdown of sfm × int
  | Ga | Wp | Wm | Z | Gl
  | Slepton of sfm × int | Sneutrino of int
  | Neutralino of neu | Chargino of char
  | Gluino | Grino
  | Phip | Phim | Phi0 | H_Heavy | H_Light | Hp | Hm | A
type gauge = unit
let gauge_symbol () =
  failwith "Modellib_MSSM.MSSM.gauge_symbol: internal error"

```

At this point we will forget graviton and -tino.

```

let lep_family g = [ L g; N g; Slepton (M1, g);
                    Slepton (M2, g); Sneutrino g ]

let family g =
  [ L g; N g; Slepton (M1, g); Slepton (M2, g); Sneutrino g;
    U g; D g; Sup (M1, g); Sup (M2, g); Sdown (M1, g);
    Sdown (M2, g)]

let external_flavors'' =
  [ "1st_Generation", ThoList.flatmap family [1; -1];
    "2nd_Generation", ThoList.flatmap family [2; -2];
    "3rd_Generation", ThoList.flatmap family [3; -3];
    "Gauge_Bosons", [Ga; Z; Wp; Wm; Gl];
    "Charginos", [Chargino C1; Chargino C2; Chargino C1c; Chargino C2c];
    "Neutralinos", [Neutralino N1; Neutralino N2; Neutralino N3;
                    Neutralino N4];
    "Higgs_Bosons", [H_Heavy; H_Light; Hp; Hm; A];
    "Gluinos", [Gluino]]

let external_flavors' =
  if Flags.gravitino then external_flavors'' @ ["Gravitino", [Grino]]
  else
    external_flavors''

let external_flavors () =
  if Flags.include_goldstone then external_flavors' @ ["Goldstone_Bosons",
                                                       [Phip; Phim; Phi0]]
  else
    external_flavors'

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n =
  if n ≥ 0 then
    Spinor
  else if
    n ≤ 0 then
    ConjSpinor
  else
    invalid_arg "Modellib-MSSM.MSSM.spinor:_internal_error"

let lorentz = function
| L g → spinor g | N g → spinor g
| U g → spinor g | D g → spinor g
| Chargino c → spinor (int_of_char c)
| Ga → Vector
| Gl → Vector
| Wp | Wm | Z → Massive_Vector
| H_Heavy | H_Light | Hp | Hm | A → Scalar
| Phip | Phim | Phi0 → Scalar
| Sup _ | Sdown _ | Slepton _ | Sneutrino _ → Scalar
| Neutralino _ → Majorana
| Gluino → Majorana
| Grino → Vectorspinor

```

```

let color = function
| U g → Color.SUN (if g > 0 then 3 else -3)
| Sup (m, g) → Color.SUN (if g > 0 then 3 else -3)
| D g → Color.SUN (if g > 0 then 3 else -3)
| Sdown (m, g) → Color.SUN (if g > 0 then 3 else -3)
| Gl | Gluino → Color.AdjSUN 3
| - → Color.Singlet

let prop_spinor n =
if n ≥ 0 then
  Prop_Spinor
else if
  n ≤ 0 then
  Prop_ConjSpinor
else
  invalid_arg "Modellib_MSSM.MSSM.prop_spinor: internal error"

let propagator = function
| L g → prop_spinor g | N g → prop_spinor g
| U g → prop_spinor g | D g → prop_spinor g
| Chargino c → prop_spinor (int_of_char c)
| Ga | Gl → Prop_Feynman
| Wp | Wm | Z → Prop_Unitarity
| H_Heavy | H_Light | Hp | Hm | A → Prop_Scalar
| Phip | Phim | Phi0 → if Flags.include_goldstone then Prop_Scalar
                        else Only_Insertion
| Slepton _ | Sneutrino _ | Sup _ | Sdown _ → Prop_Scalar
| Gluino → Prop_Majorana | Neutralino _ → Prop_Majorana
| Grino → Only_Insertion

```

Note, that we define the gravitino only as an insertion since when using propagators we are effectively going to a higher order in the gravitational coupling. This would enforce us to also include higher-dimensional vertices with two gravitinos for a consistent power counting in $1/M_{\text{Planck}}$.

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
if !use_fudged_width then
  match f with
  | Wp | Wm | U 3 | U (-3) → Fudged
  | - → !default_width
else
  !default_width

```

For the Goldstone bosons we adopt the conventions of the Kuroda paper.

$$H_1 \equiv \begin{pmatrix} (v_1 + H^0 \cos \alpha - h^0 \sin \alpha + iA^0 \sin \beta - i \cos \beta \phi^0) / \sqrt{2} \\ H^- \sin \beta - \phi^- \cos \beta \end{pmatrix} \quad (13.62a)$$

$$H_2 \equiv \begin{pmatrix} H^+ \cos \beta + \phi^+ \sin \beta \\ (v_2 + H^0 \sin \alpha + h^0 \cos \alpha + iA^0 \cos \beta + i\phi^0 \sin \beta) / \sqrt{2} \end{pmatrix} \quad (13.62b)$$

```

let goldstone = function
| Wp → Some (Phip, Coupling.Const 1)
| Wm → Some (Phim, Coupling.Const 1)
| Z → Some (Phi0, Coupling.Const 1)
| _ → None

let conjugate = function
| L g → L (-g) | N g → N (-g)
| U g → U (-g) | D g → D (-g)
| Sup (m, g) → Sup (m, -g)
| Sdown (m, g) → Sdown (m, -g)
| Slepton (m, g) → Slepton (m, -g)
| Sneutrino g → Sneutrino (-g)
| Gl → Gl (* — Gl0 -i Gl0 *)
| Ga → Ga | Z → Z | Wp → Wm | Wm → Wp
| H_Heavy → H_Heavy | H_Light → H_Light | A → A
| Hp → Hm | Hm → Hp
| Phip → Phim | Phim → Phip | Phi0 → Phi0
| Gluino → Gluino
| Grino → Grino
| Neutralino n → Neutralino n | Chargino c → Chargino (conj_char c)

let fermion = function
| L g → if g > 0 then 1 else -1
| N g → if g > 0 then 1 else -1
| U g → if g > 0 then 1 else -1
| D g → if g > 0 then 1 else -1
| Gl | Ga | Z | Wp | Wm → 0 (* — Gl0 -i 0 *)
| H_Heavy | H_Light | Hp | Hm | A → 0
| Phip | Phim | Phi0 → 0
| Neutralino _ → 2
| Chargino c → if (int_of_char c) > 0 then 1 else -1
| Sup _ → 0 | Sdown _ → 0
| Slepton _ → 0 | Sneutrino _ → 0
| Gluino | Grino → 2

```

Because the O'Caml compiler only allows 248 constructors we must divide the constants into subgroups of constants, e.g. for the Higgs couplings. In the MSSM there are a lot of angles among the parameters, the Weinberg-angle, the angle describing the Higgs vacuum structure, the mixing angle of the real parts of the Higgs doublets, the mixing angles of the sfermions. Therefore we are going to define the trigonometric functions of those angles not as constants but as functors of the angles. Sums and differences of angles are only used as arguments for the α and β angles, so it makes no sense to define special functions for differences and sums of angles.

```

type angle =
| Thw | Al | Be | Th_SF of sff × int | Delta | CKM_12 |
CKM_13 | CKM_23

let string_of_angle = function
| Thw → "thw" | Al → "al" | Be → "be" | Delta → "d"

```

```

| CKM_12 → "ckm12" | CKM_13 → "ckm13" | CKM_23 →
"ckm23"
| Th_SF (f, g) → "th" ^ string_of_sff f ^ string_of_int g

```

We introduce a Boolean type *vc* as a pseudonym for Vertex Conjugator to distinguish between vertices containing complex mixing matrices like the CKM-matrix or the sfermion or neutralino/chargino-mixing matrices, which have to become complex conjugated. The true-option stands for the conjugated vertex, the false-option for the unconjugated vertex.

```

type vc = bool
type constant =
| Unit | Pi | Alpha_QED | Sin2thw
| Sin of angle | Cos of angle | E | G | Vev | Tanb | Tana
| Cos2be | Cos2al | Sin2be | Sin2al | Sin4al | Sin4be | Cos4be
| Cosapb | Cosamb | Sinapb | Sinamb | Cos2am2b | Sin2am2b
| Edelta
| Mu | AU of int | AD of int | AL of int
| V_CKM of int×int | M_SF of sff × int×sfm × sfm
| M_V of char×char (* left chargino mixing matrix *)
| M_U of char×char (* right chargino mixing matrix *)
| M_N of neu × neu (* neutralino mixing matrix *)
| V_0 of neu × neu | A_0 of neu × neu | V_P of char×char |
A_P of char×char
| L_CN of char×neu | R_CN of char×neu | L_NC of neu × char |
R_NC of neu × char
| S_NNH1 of neu × neu | P_NNH1 of neu × neu
| S_NNH2 of neu × neu | P_NNH2 of neu × neu
| S_NNA of neu × neu | P_NNA of neu × neu
| S_NNG of neu × neu | P_NNG of neu × neu
| L_CNG of char×neu | R_CNG of char×neu
| L_NCH of neu × char | R_NCH of neu × char
| Q_lepton | Q_up | Q_down | Q_charg
| G_Z | G_CC | G_CCQ of vc × int×int
| G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down
| I_Q_W | I_G_ZWW | G_WWW | G_ZZWW | G_PZWW |
G_PPWW
| G_strong | G_SS | I_G_S | G_S_Sqrt
| Gs
| M of flavor | W of flavor
| G_NZN of neu × neu | G_CZC of char×char
| G_YUK of int×int
| G_YUK_1 of int×int | G_YUK_2 of int×int | G_YUK_3 of int×int
| G_YUK_4 of int×int | G_NHC of neu×char | G_CHN of char×neu
| G_YUK_C of vc × int×char×sff × sfm
| G_YUK_Q of vc × int×int×char×sff × sfm
| G_YUK_N of vc × int×neu × sff × sfm
| G_YUK_G of vc × int×sff × sfm
| G_NGC of neu × char | G_CGN of char×neu
| SUM_1
| G_NWC of neu × char | G_CWN of char×neu

```

G_CH1C of $char \times char$ | G_CH2C of $char \times char$ | G_CAC of $char \times char$
 G_CGC of $char \times char$
 G_SWS of $vc \times int \times int \times sfm \times sfm$
 G_SLSNW of $vc \times int \times sfm$
 G_ZSF of $sff \times int \times sfm \times sfm$
 G_CICIH1 of $neu \times neu$ | G_CICIH2 of $neu \times neu$ | G_CICIA of $neu \times$
 neu
 G_CICIG of $neu \times neu$
 G_GH of int | G_GHGo of int
 G_GLGLH | G_GLGLHH | G_GLGLA | G_PPH | G_PPHH |
 G_PPA
 G_WWSFSF of $sff \times int \times sfm \times sfm$
 G_WPSLSN of $vc \times int \times sfm$
 G_H3 of int | G_H4 of int
 G_HGo3 of int | G_HGo4 of int | G_GG4 of int
 G_H1SFSF of $sff \times int \times sfm \times sfm$ | G_H2SFSF of $sff \times int \times sfm \times sfm$
 G_ASFSF of $sff \times int \times sfm \times sfm$
 G_HSNSL of $vc \times int \times sfm$
 G_GoSFSF of $sff \times int \times sfm \times sfm$
 G_GoSNSL of $vc \times int \times sfm$
 G_HSUSD of $vc \times sfm \times sfm \times int \times int$ | G_GSUSD of $vc \times sfm \times$
 $sfm \times int \times int$
 G_WPSUSD of $vc \times sfm \times sfm \times int \times int$
 G_WZSUSD of $vc \times sfm \times sfm \times int \times int$
 G_WZSLSN of $vc \times int \times sfm$ | $G_GLISQSQ$
 G_PPSFSF of sff
 G_ZZSFSF of $sff \times int \times sfm \times sfm$ | G_ZPSFSF of $sff \times int \times sfm \times sfm$
 $G_GLZSFSF$ of $sff \times int \times sfm \times sfm$ | $G_GLPSQSQ$
 $G_GLWSUSD$ of $vc \times sfm \times sfm \times int \times int$
 G_GH4 of int | G_GHGo4 of int
 $G_H1H2SFSF$ of $sff \times sfm \times sfm \times int$
 $G_H1H1SFSF$ of $sff \times sfm \times sfm \times int$
 $G_H2H2SFSF$ of $sff \times sfm \times sfm \times int$
 G_HHSFSF of $sff \times sfm \times sfm \times int$
 G_AASFSF of $sff \times sfm \times sfm \times int$
 $G_HH1SLSN$ of $vc \times sfm \times int$ | $G_HH2SLSN$ of $vc \times sfm \times int$
 G_HASLSN of $vc \times sfm \times int$
 $G_HH1SUSD$ of $vc \times sfm \times sfm \times int \times int$
 $G_HH2SUSD$ of $vc \times sfm \times sfm \times int \times int$
 G_HASUSD of $vc \times sfm \times sfm \times int \times int$
 $G_AG0SFSF$ of $sff \times sfm \times sfm \times int$
 G_HGSFSF of $sff \times sfm \times sfm \times int$
 G_GGSFSF of $sff \times sfm \times sfm \times int$
 $G_G0G0SFSF$ of $sff \times sfm \times sfm \times int$
 G_HGSNSL of $vc \times sfm \times int$ | $G_H1GSNSL$ of $vc \times sfm \times int$
 $G_H2GSNSL$ of $vc \times sfm \times int$ | G_AGSNSL of $vc \times sfm \times int$
 G_GGSNSL of $vc \times sfm \times int$
 G_HGSUSD of $vc \times sfm \times sfm \times int \times int$
 $G_H1GSUSD$ of $vc \times sfm \times sfm \times int \times int$
 $G_H2GSUSD$ of $vc \times sfm \times sfm \times int \times int$


```

| G_AGSUSD of  $vc \times sfm \times sfm \times int \times int$ 
| G_GGSUSD of  $vc \times sfm \times sfm \times int \times int$ 
| G_SN4 of  $int \times int$ 
| G_SN2SL2_1 of  $sfm \times sfm \times int \times int$  | G_SN2SL2_2 of  $sfm \times sfm \times$ 
int  $\times int$ 
| G_SF4 of  $sff \times sff \times sfm \times sfm \times sfm \times sfm \times int \times int$ 
| G_SF4_3 of  $sff \times sff \times sfm \times sfm \times sfm \times sfm \times int \times int \times int$ 
| G_SF4_4 of  $sff \times sff \times sfm \times sfm \times sfm \times sfm \times int \times int \times int \times int$ 
| G_SL4 of  $sfm \times sfm \times sfm \times sfm \times int$ 
| G_SL4_2 of  $sfm \times sfm \times sfm \times sfm \times int \times int$ 
| G_SN2SQ2 of  $sff \times sfm \times sfm \times int \times int$ 
| G_SL2SQ2 of  $sff \times sfm \times sfm \times sfm \times sfm \times int \times int$ 
| G_SUSDSNSL of  $vc \times sfm \times sfm \times sfm \times int \times int \times int$ 
| G_SU4 of  $sfm \times sfm \times sfm \times sfm \times int$ 
| G_SU4_2 of  $sfm \times sfm \times sfm \times sfm \times int \times int$ 
| G_SD4 of  $sfm \times sfm \times sfm \times sfm \times int$ 
| G_SD4_2 of  $sfm \times sfm \times sfm \times sfm \times int \times int$ 
| G_SU2SD2 of  $sfm \times sfm \times sfm \times sfm \times int \times int \times int \times int$ 
| G_HSF31 of  $higgs \times int \times sfm \times sfm \times sff \times sff$ 
| G_HSF32 of  $higgs \times int \times int \times sfm \times sfm \times sff \times sff$ 
| G_HSF41 of  $higgs \times int \times sfm \times sfm \times sff \times sff$ 
| G_HSF42 of  $higgs \times int \times int \times sfm \times sfm \times sff \times sff$ 
| G_Grav | G_Gr_Ch of char | G_Gr_Z_Neu of neu
| G_Gr_A_Neu of neu | G_Gr4_Neu of neu
| G_Gr4_A_Ch of char | G_Gr4_Z_Ch of char
| G_Grav_N | G_Grav_U of  $int \times sfm$  | G_Grav_D of  $int \times sfm$ 
| G_Grav_L of  $int \times sfm$  | G_Grav_Uc of  $int \times sfm$  | G_Grav_Dc of  $int \times sfm$ 
| G_Grav_Lc of  $int \times sfm$  | G_GravGl
| G_Gr_H_Ch of char | G_Gr_H1_Neu of neu
| G_Gr_H2_Neu of neu | G_Gr_H3_Neu of neu
| G_Gr4A_Sl of  $int \times sfm$  | G_Gr4A_Slc of  $int \times sfm$ 
| G_Gr4A_Su of  $int \times sfm$  | G_Gr4A_Suc of  $int \times sfm$ 
| G_Gr4A_Sd of  $int \times sfm$  | G_Gr4A_Sdc of  $int \times sfm$ 
| G_Gr4Z_Sn | G_Gr4Z_Snc
| G_Gr4Z_Sl of  $int \times sfm$  | G_Gr4Z_Slc of  $int \times sfm$ 
| G_Gr4Z_Su of  $int \times sfm$  | G_Gr4Z_Suc of  $int \times sfm$ 
| G_Gr4Z_Sd of  $int \times sfm$  | G_Gr4Z_Sdc of  $int \times sfm$ 
| G_Gr4W_Sl of  $int \times sfm$  | G_Gr4W_Slc of  $int \times sfm$ 
| G_Gr4W_Su of  $int \times sfm$  | G_Gr4W_Suc of  $int \times sfm$ 
| G_Gr4W_Sd of  $int \times sfm$  | G_Gr4W_Sdc of  $int \times sfm$ 
| G_Gr4W_Sn | G_Gr4W_Snc
| G_Gr4GL_Su of  $int \times sfm$  | G_Gr4GL_Suc of  $int \times sfm$ 
| G_Gr4GL_Sd of  $int \times sfm$  | G_Gr4GL_Sdc of  $int \times sfm$ 
| G_Gr4_Z_H1 of neu | G_Gr4_Z_H2 of neu | G_Gr4_Z_H3 of neu
| G_Gr4_W_H of neu | G_Gr4_W_Hc of neu | G_Gr4_H_A of char
| G_Gr4_H_Z of char

```

Two integer counters for the QCD and EW order of the couplings.

type *orders* = $int \times int$

```

let orders = function
| - → (0,0)

let ferm_of_sff = function
| SL, g → (L g) | SN, g → (N g)
| SU, g → (U g) | SD, g → (D g)

```

$$\alpha_{\text{QED}} = \frac{1}{137.0359895} \quad (13.63a)$$

$$\sin^2 \theta_w = 0.23124 \quad (13.63b)$$

Here we must perhaps allow for complex input parameters. So split them into their modulus and their phase. At first, we leave them real; the generalization to complex parameters is obvious.

```

module Ch = Charges.QQ

let ( / ) = Algebra.Small_Rational.make

let generation' = function
| 1 → [ 1//1; 0//1; 0//1]
| 2 → [ 0//1; 1//1; 0//1]
| 3 → [ 0//1; 0//1; 1//1]
| -1 → [-1//1; 0//1; 0//1]
| -2 → [ 0//1; -1//1; 0//1]
| -3 → [ 0//1; 0//1; -1//1]
| n → invalid_arg ("MSSM.generation':␣" ^ string_of_int n)

let generation f =
if Flags.ckm_present then
[]
else
match f with
| L n | N n | U n | D n | Sup (_, n)
| Sdown (_, n) | Slepton (_, n)
| Sneutrino n → generation' n
| - → [0//1; 0//1; 0//1]

let charge = function
| L n → if n > 0 then -1//1 else 1//1
| Slepton (_, n) → if n > 0 then -1//1 else 1//1
| N n → 0//1
| Sneutrino n → 0//1
| U n → if n > 0 then 2//3 else -2//3
| Sup (_, n) → if n > 0 then 2//3 else -2//3
| D n → if n > 0 then -1//3 else 1//3
| Sdown (_, n) → if n > 0 then -1//3 else 1//3
| Gl | Ga | Z | Neutralino _ | Gluino → 0//1
| Wp → 1//1
| Wm → -1//1
| H_Heavy | H_Light | Phi0 → 0//1
| Hp | Phip → 1//1

```

```

| Hm | Phim → -1//1
| Chargino (C1 | C2) → 1//1
| Chargino (C1c | C2c) → -1//1
| - → 0//1

let lepton = function
| L n | N n → if n > 0 then 1//1 else -1//1
| Slepton (-, n)
| Sneutrino n → if n > 0 then 1//1 else -1//1
| - → 0//1

let baryon = function
| U n | D n → if n > 0 then 1//1 else -1//1
| Sup (-, n) | Sdown (-, n) → if n > 0 then 1//1 else -1//1
| - → 0//1

let charges f =
[ charge f; lepton f; baryon f] @ generation f

let parameters () =
{ input = [];
  derived = [];
  derived_arrays = [] }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

```

For the couplings there are generally two possibilities concerning the sign of the covariant derivative.

$$CD^\pm = \partial_\mu \pm igT^a A_\mu^a \quad (13.64)$$

The particle data group defines the signs consistently to be positive. Since the convention for that signs also influence the phase definitions of the gaugino/higgsino fields via the off-diagonal entries in their mass matrices it would be the best to adopt that convention.

** REVISED: Compatible with CD+. **

```

let electromagnetic_currents_3 g =
[ ((U (-g), Ga, U g), FBF (1, Psibar, V, Psi), Q_up);
  ((D (-g), Ga, D g), FBF (1, Psibar, V, Psi), Q_down);
  ((L (-g), Ga, L g), FBF (1, Psibar, V, Psi), Q_lepton) ]

```

** REVISED: Compatible with CD+. **

```

let electromagnetic_sfermion_currents g m =
[ ((Ga, Slepton (m, -g), Slepton (m, g)), Vector_Scalar_Scalar 1, Q_lepton);
  ((Ga, Sup (m, -g), Sup (m, g)), Vector_Scalar_Scalar 1, Q_up);
  ((Ga, Sdown (m, -g), Sdown (m, g)), Vector_Scalar_Scalar 1, Q_down) ]

```

** REVISED: Compatible with CD+. **

```

let electromagnetic_currents_2 c =

```

```

let cc = conj_char c in
[ ((Chargino cc, Ga, Chargino c), FBF (1, Psibar, V, Psi), Q_charg) ]

```

** REVISED: Compatible with CD+. **

```

let neutral_currents g =
[ ((L (-g), Z, L g), FBF (1, Psibar, VA, Psi), G_NC_lepton);
  ((N (-g), Z, N g), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
  ((U (-g), Z, U g), FBF (1, Psibar, VA, Psi), G_NC_up);
  ((D (-g), Z, D g), FBF (1, Psibar, VA, Psi), G_NC_down) ]

```

$$\mathcal{L}_{CC} = \mp \frac{g}{2\sqrt{2}} \sum_i \bar{\psi}_i \gamma^\mu (1 - \gamma_5) (T^+ W_\mu^+ + T^- W_\mu^-) \psi_i, \quad (13.65)$$

where the sign corresponds to CD_\pm , respectively.

** REVISED: Compatible with CD+. **

Remark: The definition with the other sign compared to the SM files comes from the fact that $g_{cc} = 1/(2\sqrt{2})$ is used overwhelmingly often in the SUSY Feynman rules, so that JR decided to use a different definition for g_{cc} in SM and MSSM.

```

let charged_currents g =
[ ((L (-g), Wm, N g), FBF ((-1), Psibar, VL, Psi), G_CC);
  ((N (-g), Wp, L g), FBF ((-1), Psibar, VL, Psi), G_CC) ]

```

The quark with the inverted generation (the antiparticle) is the outgoing one, the other the incoming. The vertex attached to the outgoing up-quark contains the CKM matrix element *not* complex conjugated, while the vertex with the outgoing down-quark has the conjugated CKM matrix element.

** REVISED: Compatible with CD+. **

```

let charged_quark_currents g h =
[ ((D (-g), Wm, U h), FBF ((-1), Psibar, VL, Psi), G_CCQ (true,g,h));
  ((U (-g), Wp, D h), FBF ((-1), Psibar, VL, Psi), G_CCQ (false,h,g))]

```

** REVISED: Compatible with CD+. **

```

let charged_chargino_currents n c =
let cc = conj_char c in
[ ((Chargino cc, Wp, Neutralino n),
   FBF (1, Psibar, VLR, Chi), G_CWN (c,n));
  ((Neutralino n, Wm, Chargino c),
   FBF (1, Chibar, VLR, Psi), G_NWC (n,c)) ]

```

** REVISED: Compatible with CD+. **

```

let charged_slepton_currents g m =
[ ((Wm, Slepton (m, -g), Sneutrino g), Vector_Scalar_Scalar (-1), G_SLSNW
   (true,g,m));
  ((Wp, Slepton (m, g), Sneutrino (-g)), Vector_Scalar_Scalar 1, G_SLSNW
   (false,g,m)) ]

```

** REVISED: Compatible with CD+. **

```

let charged_squark_currents' g h m1 m2 =
[ ((Wm, Sup (m1, g), Sdown (m2, -h)), Vector_Scalar_Scalar (-1), G_SWS

```

```

      (true,g,h,m1,m2));
      ((Wp, Sup (m1,-g), Sdown (m2,h)), Vector_Scalar_Scalar 1, G_SWS
      (false,g,h,m1,m2)) ]
let charged_squark_currents g h = List.flatten (Product.list2
      (charged_squark_currents' g h) [M1;M2] [M1;M2])
** REVISED: Compatible with CD+. **

let neutral_sfermion_currents' g m1 m2 =
  [ ((Z, Slepton (m1,-g), Slepton (m2,g)), Vector_Scalar_Scalar (-1), G_ZSF
    (SL,g,m1,m2));
    ((Z, Sup (m1,-g), Sup (m2,g)), Vector_Scalar_Scalar (-1), G_ZSF
    (SU,g,m1,m2));
    ((Z, Sdown (m1,-g), Sdown (m2,g)), Vector_Scalar_Scalar (-1), G_ZSF
    (SD,g,m1,m2)) ]
let neutral_sfermion_currents g =
  List.flatten (Product.list2 (neutral_sfermion_currents'
    g) [M1;M2] [M1;M2]) @
  [ ((Z, Sneutrino (-g), Sneutrino g), Vector_Scalar_Scalar (-1), G_ZSF
    (SN,g,M1,M1)) ]

```

The reality of the coupling of the Z-boson to two identical neutralinos makes the vector part of the coupling vanish. So we distinguish them not by the name but by the structure of the couplings.

** REVISED: Compatible with CD+. **

```

let neutral_Z_1 (n,m) =
  [ ((Neutralino n, Z, Neutralino m), FBF (1, Chibar, VA, Chi),
    (G_NZN (n,m))) ]
(***) REVISED: Compatible with CD+. (***)
let neutral_Z_2 n =
  [ ((Neutralino n, Z, Neutralino n), FBF (1, Chibar, Coupling.A, Chi),
    (G_NZN (n,n)) ) ]

```

** REVISED: Compatible with CD+. **

```

let charged_Z c1 c2 =
  let cc1 = conj_char c1 in
  ((Chargino cc1, Z, Chargino c2), FBF ((-1), Psibar, VA, Psi),
    G_CZC (c1,c2))

```

** REVISED: Compatible with CD+. **

```

let yukawa_v =
  [ ((Gluino, Gl, Gluino), FBF (1, Chibar, V, Chi), Gs) ]

```

** REVISED: Independent of the sign of CD. **

```

let yukawa_higgs g =
  [ ((N (-g), Hp, L g), FBF (1, Psibar, Coupling.SR, Psi), G_YUK (6,g));
    ((L (-g), Hm, N g), FBF (1, Psibar, Coupling.SL, Psi), G_YUK (6,g));
    ((L (-g), H_Heavy, L g), FBF (1, Psibar, S, Psi), G_YUK (7,g));
    ((L (-g), H_Light, L g), FBF (1, Psibar, S, Psi), G_YUK (8,g));
    ((L (-g), A, L g), FBF (1, Psibar, P, Psi), G_YUK (9,g));
    ((U (-g), H_Heavy, U g), FBF (1, Psibar, S, Psi), G_YUK (10,g));

```

```

((U (-g), H_Light, U g), FBF (1, Psibar, S, Psi), G_YUK (11, g));
((U (-g), A, U g), FBF (1, Psibar, P, Psi), G_YUK (12, g));
((D (-g), H_Heavy, D g), FBF (1, Psibar, S, Psi), G_YUK (13, g));
((D (-g), H_Light, D g), FBF (1, Psibar, S, Psi), G_YUK (14, g));
((D (-g), A, D g), FBF (1, Psibar, P, Psi), G_YUK (15, g)) ]

```

** REVISED: Compatible with CD+ and GS+. **

```

let yukawa_goldstone g =
[ ((N (-g), Phip, L g), FBF (1, Psibar, Coupling.SR, Psi), G_YUK (19, g));
  ((L (-g), Phim, N g), FBF (1, Psibar, Coupling.SL, Psi), G_YUK (19, g));
  ((L (-g), Phi0, L g), FBF (1, Psibar, P, Psi), G_YUK (16, g));
  ((U (-g), Phi0, U g), FBF (1, Psibar, P, Psi), G_YUK (17, g));
  ((D (-g), Phi0, D g), FBF (1, Psibar, P, Psi), G_YUK (18, g)) ]

```

** REVISED: Independent of the sign of CD. **

```

let yukawa_higgs_quark (g, h) =
[ ((U (-g), Hp, D h), FBF (1, Psibar, SLR, Psi), G_YUK_1 (g, h));
  ((D (-h), Hm, U g), FBF (1, Psibar, SLR, Psi), G_YUK_2 (g, h)) ]

```

** REVISED: Compatible with CD+ and GS+. **

```

let yukawa_goldstone_quark g h =
[ ((U (-g), Phip, D h), FBF (1, Psibar, SLR, Psi), G_YUK_3 (g, h));
  ((D (-h), Phim, U g), FBF (1, Psibar, SLR, Psi), G_YUK_4 (g, h)) ]

```

** REVISED: Compatible with CD+.

```

let yukawa_higgs_2' (c1, c2) =
let cc1 = conj_char c1 in
[ ((Chargino cc1, H_Heavy, Chargino c2), FBF (1, Psibar, SLR, Psi),
  G_CH2C (c1, c2));
  ((Chargino cc1, H_Light, Chargino c2), FBF (1, Psibar, SLR, Psi),
  G_CH1C (c1, c2));
  ((Chargino cc1, A, Chargino c2), FBF (1, Psibar, SLR, Psi),
  G_CAC (c1, c2)) ]
let yukawa_higgs_2'' c =
let cc = conj_char c in
[ ((Chargino cc, H_Heavy, Chargino c), FBF (1, Psibar, S, Psi),
  G_CH2C (c, c));
  ((Chargino cc, H_Light, Chargino c), FBF (1, Psibar, S, Psi),
  G_CH1C (c, c));
  ((Chargino cc, A, Chargino c), FBF (1, Psibar, P, Psi),
  G_CAC (c, c)) ]
let yukawa_higgs_2 =
  ThoList.flatmap yukawa_higgs_2' [(C1, C2); (C2, C1)] @
  ThoList.flatmap yukawa_higgs_2'' [C1; C2]

```

** REVISED: Compatible with CD+ and GS+. **

```

let yukawa_goldstone_2' (c1, c2) =
let cc1 = conj_char c1 in
[ ((Chargino cc1, Phi0, Chargino c2), FBF (1, Psibar, SLR, Psi),
  G_CGC (c1, c2)) ]

```

```

let yukawa_goldstone_2'' c =
  let cc = conj_char c in
  [ ((Chargino cc, Phi0, Chargino c), FBF (1, Psibar, P, Psi),
      G_CGC (c, c)) ]
let yukawa_goldstone_2 =
  ThoList.flatmap yukawa_goldstone_2' [(C1, C2); (C2, C1)] @
  ThoList.flatmap yukawa_goldstone_2'' [C1; C2]

** REVISED: Compatible with CD+. **

let higgs_charg_neutr n c =
  let cc = conj_char c in
  [ ((Neutralino n, Hm, Chargino c), FBF (-1, Chibar, SLR, Psi),
      G_NHC (n, c));
    ((Chargino cc, Hp, Neutralino n), FBF (-1, Psibar, SLR, Chi),
      G_CHN (c, n)) ]

** REVISED: Compatible with CD+ and GS+. **

let goldstone_charg_neutr n c =
  let cc = conj_char c in
  [ ((Neutralino n, Phim, Chargino c), FBF (1, Chibar, SLR, Psi),
      G_NGC (n, c));
    ((Chargino cc, Phip, Neutralino n), FBF (1, Psibar, SLR, Chi),
      G_CGN (c, n)) ]

** REVISED: Compatible with CD+. **

let higgs_neutr' (n, m) =
  [ ((Neutralino n, H_Heavy, Neutralino m), FBF (1, Chibar, SP, Chi),
      G_CICIH2 (n, m));
    ((Neutralino n, H_Light, Neutralino m), FBF (1, Chibar, SP, Chi),
      G_CICIH1 (n, m));
    ((Neutralino n, A, Neutralino m), FBF (1, Chibar, SP, Chi),
      G_CICIA (n, m)) ]
let higgs_neutr'' n =
  [ ((Neutralino n, H_Heavy, Neutralino n), FBF (1, Chibar, S, Chi),
      G_CICIH2 (n, n));
    ((Neutralino n, H_Light, Neutralino n), FBF (1, Chibar, S, Chi),
      G_CICIH1 (n, n));
    ((Neutralino n, A, Neutralino n), FBF (1, Chibar, P, Chi),
      G_CICIA (n, n)) ]
let higgs_neutr =
  ThoList.flatmap higgs_neutr' [(N1, N2); (N1, N3); (N1, N4);
    (N2, N3); (N2, N4); (N3, N4)] @
  ThoList.flatmap higgs_neutr'' [N1; N2; N3; N4]

** REVISED: Compatible with CD+ and GS+. **

let goldstone_neutr' (n, m) =
  [ ((Neutralino n, Phi0, Neutralino m), FBF (1, Chibar, SP, Chi),
      G_CICIG (n, m)) ]
let goldstone_neutr'' n =
  [ ((Neutralino n, Phi0, Neutralino n), FBF (1, Chibar, P, Chi),

```

```

      G_CICIG (n, n)) ]
let goldstone_neutr =
  ThoList.flatmap goldstone_neutr' [(N1, N2); (N1, N3); (N1, N4);
    (N2, N3); (N2, N4); (N3, N4)] @
  ThoList.flatmap goldstone_neutr'' [N1; N2; N3; N4]
** REVISED: Compatible with CD+. **

let yukawa_n_1 n g =
  [ ((Neutralino n, Slepton (M1, -g), L g), FBF (1, Chibar, Coupling.SL,
    Psi), G_YUK_N (true, g, n, SL, M1));
    ((Neutralino n, Slepton (M2, -g), L g), FBF (1, Chibar, SR, Psi),
    G_YUK_N (true, g, n, SL, M2));
    ((L (-g), Slepton (M1, g), Neutralino n), FBF (1, Psibar, SR, Chi),
    G_YUK_N (false, g, n, SL, M1));
    ((L (-g), Slepton (M2, g), Neutralino n), FBF (1, Psibar, Coupling.SL,
    Chi), G_YUK_N (false, g, n, SL, M2));
    ((Neutralino n, Sup (M1, -g), U g), FBF (1, Chibar, Coupling.SL,
    Psi), G_YUK_N (true, g, n, SU, M1));
    ((Neutralino n, Sup (M2, -g), U g), FBF (1, Chibar, SR, Psi),
    G_YUK_N (true, g, n, SU, M2));
    ((U (-g), Sup (M1, g), Neutralino n), FBF (1, Psibar, SR, Chi),
    G_YUK_N (false, g, n, SU, M1));
    ((U (-g), Sup (M2, g), Neutralino n), FBF (1, Psibar, Coupling.SL,
    Chi), G_YUK_N (false, g, n, SU, M2));
    ((Neutralino n, Sdown (M1, -g), D g), FBF (1, Chibar, Coupling.SL,
    Psi), G_YUK_N (true, g, n, SD, M1));
    ((Neutralino n, Sdown (M2, -g), D g), FBF (1, Chibar, SR, Psi),
    G_YUK_N (true, g, n, SD, M2));
    ((D (-g), Sdown (M1, g), Neutralino n), FBF (1, Psibar, SR, Chi),
    G_YUK_N (false, g, n, SD, M1));
    ((D (-g), Sdown (M2, g), Neutralino n), FBF (1, Psibar, Coupling.SL,
    Chi), G_YUK_N (false, g, n, SD, M2)) ]
let yukawa_n_2 n m =
  [ ((Neutralino n, Slepton (m, -3), L 3), FBF (1, Chibar, SLR, Psi),
    G_YUK_N (true, 3, n, SL, m));
    ((L (-3), Slepton (m, 3), Neutralino n), FBF (1, Psibar, SLR, Chi),
    G_YUK_N (false, 3, n, SL, m));
    ((Neutralino n, Sup (m, -3), U 3), FBF (1, Chibar, SLR, Psi),
    G_YUK_N (true, 3, n, SU, m));
    ((U (-3), Sup (m, 3), Neutralino n), FBF (1, Psibar, SLR, Chi),
    G_YUK_N (false, 3, n, SU, m));
    ((Neutralino n, Sdown (m, -3), D 3), FBF (1, Chibar, SLR, Psi),
    G_YUK_N (true, 3, n, SD, m));
    ((D (-3), Sdown (m, 3), Neutralino n), FBF (1, Psibar, SLR, Chi),
    G_YUK_N (false, 3, n, SD, m)) ]
let yukawa_n_3 n g =
  [ ((Neutralino n, Sneutrino (-g), N g), FBF (1, Chibar, Coupling.SL,
    Psi), G_YUK_N (true, g, n, SN, M1));
    ((N (-g), Sneutrino g, Neutralino n), FBF (1, Psibar, SR, Chi),
    G_YUK_N (false, g, n, SN, M1)) ]

```



```

let yukawa_n_4 g =
  [ ((U (-g), Sup (M1, g), Gluino), FBF ((-1), Psibar, SR, Chi), G_S_Sqrt);
    ((D (-g), Sdown (M1, g), Gluino), FBF ((-1), Psibar, SR, Chi), G_S_Sqrt);
    ((Gluino, Sup (M1, -g), U g), FBF ((-1), Chibar, Coupling.SL, Psi), G_S_Sqrt);
    ((Gluino, Sdown (M1, -g), D g), FBF ((-1), Chibar, Coupling.SL, Psi), G_S_Sqrt);
    ((U (-g), Sup (M2, g), Gluino), FBF (1, Psibar, Coupling.SL, Chi), G_S_Sqrt);
    ((D (-g), Sdown (M2, g), Gluino), FBF (1, Psibar, Coupling.SL, Chi), G_S_Sqrt);
    ((Gluino, Sup (M2, -g), U g), FBF (1, Chibar, SR, Psi), G_S_Sqrt);
    ((Gluino, Sdown (M2, -g), D g), FBF (1, Chibar, SR, Psi), G_S_Sqrt)]

let yukawa_n_5 m =
  [ ((U (-3), Sup (m, 3), Gluino), FBF (1, Psibar, SLR, Chi),
      G_YUK_G (false, 3, SU, m));
    ((D (-3), Sdown (m, 3), Gluino), FBF (1, Psibar, SLR, Chi),
      G_YUK_G (false, 3, SD, m));
    ((Gluino, Sup (m, -3), U 3), FBF (1, Chibar, SLR, Psi),
      G_YUK_G (true, 3, SU, m));
    ((Gluino, Sdown (m, -3), D 3), FBF (1, Chibar, SLR, Psi),
      G_YUK_G (true, 3, SD, m))]

let yukawa_n =
  List.flatten (Product.list2 yukawa_n_1 [N1; N2; N3; N4] [1; 2]) @
  List.flatten (Product.list2 yukawa_n_2 [N1; N2; N3; N4] [M1; M2]) @
  List.flatten (Product.list2 yukawa_n_3 [N1; N2; N3; N4] [1; 2; 3]) @
  ThoList.flatmap yukawa_n_4 [1; 2] @
  ThoList.flatmap yukawa_n_5 [M1; M2]

** REVISED: Compatible with CD+. **

let yukawa_c_1 c g =
  let cc = conj_char c in
  [ ((L (-g), Sneutrino g, Chargino cc), BBB (1, Psibar, Coupling.SR,
      Psibar), G_YUK_C (true, g, c, SN, M1));
    ((Chargino c, Sneutrino (-g), L g), PBP (1, Psi, Coupling.SL, Psi),
      G_YUK_C (false, g, c, SN, M1)) ]

let yukawa_c_2 c =
  let cc = conj_char c in
  [ ((L (-3), Sneutrino 3, Chargino cc), BBB (1, Psibar, SLR,
      Psibar), G_YUK_C (true, 3, c, SN, M1));
    ((Chargino c, Sneutrino (-3), L 3), PBP (1, Psi, SLR, Psi),
      G_YUK_C (false, 3, c, SN, M1)) ]

let yukawa_c_3 c m g =
  let cc = conj_char c in
  [ ((N (-g), Slepton (m, g), Chargino c), FBF (1, Psibar, Coupling.SR,
      Psi), G_YUK_C (true, g, c, SL, m));
    ((Chargino cc, Slepton (m, -g), N g), FBF (1, Psibar, Coupling.SL,
      Psi), G_YUK_C (false, g, c, SL, m)) ]

let yukawa_c c =
  ThoList.flatmap (yukawa_c_1 c) [1; 2] @
  yukawa_c_2 c @
  List.flatten (Product.list2 (yukawa_c_3 c) [M1] [1; 2]) @
  List.flatten (Product.list2 (yukawa_c_3 c) [M1; M2] [3])

** REVISED: Compatible with CD+. **

```

```

let yukawa_cq' c (g, h) m =
  let cc = conj_char c in
    [ ((Chargino c, Sup (m, -g), D h), PBP (1, Psi, SLR, Psi),
        G_YUK_Q (false, g, h, c, SU, m));
      ((D (-h), Sup (m, g), Chargino cc), BBB (1, Psibar, SLR, Psibar),
        G_YUK_Q (true, g, h, c, SU, m));
      ((Chargino cc, Sdown (m, -h), U g), FBF (1, Psibar, SLR, Psi),
        G_YUK_Q (true, g, h, c, SD, m));
      ((U (-g), Sdown (m, h), Chargino c), FBF (1, Psibar, SLR, Psi),
        G_YUK_Q (false, g, h, c, SD, m)) ]
let yukawa_cq'' c (g, h) =
  let cc = conj_char c in
    [ ((Chargino c, Sup (M1, -g), D h), PBP (1, Psi, Coupling.SL, Psi),
        G_YUK_Q (false, g, h, c, SU, M1));
      ((D (-h), Sup (M1, g), Chargino cc),
        BBB (1, Psibar, Coupling.SR, Psibar), G_YUK_Q (true, g, h, c, SU, M1));
      ((Chargino cc, Sdown (M1, -h), U g),
        FBF (1, Psibar, Coupling.SL, Psi), G_YUK_Q (true, g, h, c, SD, M1));
      ((U (-g), Sdown (M1, h), Chargino c),
        FBF (1, Psibar, Coupling.SR, Psi), G_YUK_Q (false, g, h, c, SD, M1)) ]
let yukawa_cq c =
  if Flags.ckm-present then
    List.flatten (Product.list2 (yukawa_cq' c) [(1, 3); (2, 3); (3, 3);
                                                (3, 2); (3, 1)] [M1; M2]) @
    ThoList.flatmap (yukawa_cq'' c) [(1, 1); (1, 2); (2, 1); (2, 2)]
  else
    ThoList.flatmap (yukawa_cq' c (3, 3)) [M1; M2] @
    ThoList.flatmap (yukawa_cq'' c) [(1, 1); (2, 2)]

** REVISED: Compatible with CD+. Remark: Singlet and octet gluon ex-
change. The coupling is divided by sqrt(2) to account for the correct normal-
ization of the Lie algebra generators. **

let col_currents g =
  [ ((D (-g), Gl, D g), FBF ((-1), Psibar, V, Psi), Gs);
    ((U (-g), Gl, U g), FBF ((-1), Psibar, V, Psi), Gs)]

** REVISED: Compatible with CD+. Remark: Singlet and octet gluon ex-
change. The coupling is divided by sqrt(2) to account for the correct normal-
ization of the Lie algebra generators. **

let col_sfermion_currents g m =
  [ ((Gl, Sup (m, -g), Sup (m, g)), Vector_Scalar_Scalar (-1), Gs);
    ((Gl, Sdown (m, -g), Sdown (m, g)), Vector_Scalar_Scalar (-1), Gs)]

The gravitino coupling is generically 1/(4MPl.)
** Triple vertices containing graivitinos. **

let triple_gravitino' g =
  [ ((Grino, Sneutrino (-g), N g), GBG (1, Gravbar, Coupling.SL, Psi), G_Grav_N);
    ((N (-g), Sneutrino g, Grino), GBG (1, Psibar, Coupling.SL, Grav), G_Grav_N)]

let triple_gravitino'' g m =
  [ ((Grino, Slepton (m, -g), L g), GBG (1, Gravbar, SLR, Psi), G_Grav_L (g, m));

```

```

((L(-g), Slepton(m, g), Grino), GBG(1, Psibar, SLR, Grav), G-Grav-Lc(g, m));
((Grino, Sup(m, -g), U g), GBG(1, Gravbar, SLR, Psi), G-Grav-U(g, m));
((U(-g), Sup(m, g), Grino), GBG(1, Psibar, SLR, Grav), G-Grav-Uc(g, m));
((Grino, Sdown(m, -g), D g), GBG(1, Gravbar, SLR, Psi), G-Grav-D(g, m));
((D(-g), Sdown(m, g), Grino), GBG(1, Psibar, SLR, Grav), G-Grav-Dc(g, m))]

let higgs_ch_gravitino c =
  let cc = conj_char c in
  [((Grino, Hm, Chargino c), GBG(1, Gravbar, SLR, Psi), G-Gr-H-Ch c);
   ((Chargino cc, Hp, Grino), GBG(1, Psibar, SLR, Grav), G-Gr-H-Ch cc)]

let higgs_neu_gravitino n =
  [((Grino, H-Light, Neutralino n), GBG(1, Gravbar, SLR, Chi), G-Gr-H1-Neu n);
   ((Grino, H-Heavy, Neutralino n), GBG(1, Gravbar, SLR, Chi), G-Gr-H2-Neu n);
   ((Grino, A, Neutralino n), GBG(1, Gravbar, SLR, Chi), G-Gr-H3-Neu n)]

let gravitino_gaugino_3 =
  [((Grino, Gl, Gluino), GBG(1, Gravbar, V, Chi), G-Grav);
   ((Gluino, Gl, Grino), GBG(1, Chibar, V, Grav), G-Grav);
   ((Chargino C1c, Wp, Grino), GBG(1, Psibar, VLR, Grav), G-Gr-Ch C1);
   ((Chargino C2c, Wp, Grino), GBG(1, Psibar, VLR, Grav), G-Gr-Ch C2);
   ((Grino, Wm, Chargino C1), GBG(1, Gravbar, VLR, Psi), G-Gr-Ch C1c);
   ((Grino, Wm, Chargino C2), GBG(1, Gravbar, VLR, Psi), G-Gr-Ch C2c);
   ((Grino, Z, Neutralino N1), GBG(1, Gravbar, VLR, Chi), G-Gr-Z-Neu N1);
   ((Grino, Z, Neutralino N2), GBG(1, Gravbar, VLR, Chi), G-Gr-Z-Neu N2);
   ((Grino, Z, Neutralino N3), GBG(1, Gravbar, VLR, Chi), G-Gr-Z-Neu N3);
   ((Grino, Z, Neutralino N4), GBG(1, Gravbar, VLR, Chi), G-Gr-Z-Neu N4);
   ((Grino, Ga, Neutralino N1), GBG(1, Gravbar, VLR, Chi), G-Gr-A-Neu N1);
   ((Grino, Ga, Neutralino N2), GBG(1, Gravbar, VLR, Chi), G-Gr-A-Neu N2);
   ((Grino, Ga, Neutralino N3), GBG(1, Gravbar, VLR, Chi), G-Gr-A-Neu N3);
   ((Grino, Ga, Neutralino N4), GBG(1, Gravbar, VLR, Chi), G-Gr-A-Neu N4)]

let triple_gravitino =
  ThoList.flatmap triple_gravitino' [1; 2; 3] @
  List.flatten (Product.list2 triple_gravitino'' [1; 2; 3] [M1; M2]) @
  ThoList.flatmap higgs_ch_gravitino [C1; C2] @
  ThoList.flatmap higgs_neu_gravitino [N1; N2; N3; N4] @
  gravitino_gaugino_3

** REVISED: Compatible with CD+. **

let triple_gauge =
  [((Ga, Wm, Wp), Gauge-Gauge-Gauge 1, I-Q-W);
   ((Z, Wm, Wp), Gauge-Gauge-Gauge 1, I-G-ZWW);
   ((Gl, Gl, Gl), Gauge-Gauge-Gauge 1, I-G-S)]

** REVISED: Independent of the sign of CD. **

let gauge4 = Vector4 [(2, C-13-42); (-1, C-12-34); (-1, C-14-23)]
let gluon4 = Vector4 [(-1, C-13-42); (-1, C-12-34); (-1, C-14-23)]
let minus_gauge4 = Vector4 [(-2, C-13-42); (1, C-12-34); (1, C-14-23)]
let quartic_gauge =
  [(Wm, Wp, Wm, Wp), gauge4, G-WWWW;
   (Wm, Z, Wp, Z), minus_gauge4, G-ZZWW]

```

```

(Wm, Z, Wp, Ga), minus_gauge4, G_PZWW;
(Wm, Ga, Wp, Ga), minus_gauge4, G_PPWW;
(Gl, Gl, Gl, Gl), gauge4, G_SS]

```

The *Scalar_Vector_Vector* couplings do not depend on the choice of the sign of the covariant derivative since they are quadratic in the gauge couplings.

** REVISED: Compatible with CD+. **

** Revision: 2005-03-10: first two vertices corrected. **

```

let gauge_higgs =
[ ((Wm, Hp, A), Vector_Scalar_Scalar 1, G_GH 1);
  ((Wp, Hm, A), Vector_Scalar_Scalar 1, G_GH 1);
  ((Z, H_Heavy, A), Vector_Scalar_Scalar 1, G_GH 3);
  ((Z, H_Light, A), Vector_Scalar_Scalar 1, G_GH 2);
  ((H_Heavy, Wp, Wm), Scalar_Vector_Vector 1, G_GH 5);
  ((H_Light, Wp, Wm), Scalar_Vector_Vector 1, G_GH 4);
  ((Wm, Hp, H_Heavy), Vector_Scalar_Scalar 1, G_GH 7);
  ((Wp, Hm, H_Heavy), Vector_Scalar_Scalar (-1), G_GH 7);
  ((Wm, Hp, H_Light), Vector_Scalar_Scalar 1, G_GH 6);
  ((Wp, Hm, H_Light), Vector_Scalar_Scalar (-1), G_GH 6);
  ((H_Heavy, Z, Z), Scalar_Vector_Vector 1, G_GH 9);
  ((H_Light, Z, Z), Scalar_Vector_Vector 1, G_GH 8);
  ((Z, Hp, Hm), Vector_Scalar_Scalar 1, G_GH 10);
  ((Ga, Hp, Hm), Vector_Scalar_Scalar 1, G_GH 11) ] @
(if Flags.higgs_triangle then
[ ((H_Light, Gl, Gl), Dim5_Scalar_Gauge2 1, G_GLGLH);
  ((H_Heavy, Gl, Gl), Dim5_Scalar_Gauge2 1, G_GLGLHH);
  ((A, Gl, Gl), Dim5_Scalar_Gauge2_Skew 1, G_GLGLA);
  ((H_Light, Ga, Ga), Dim5_Scalar_Gauge2 1, G_PPH);
  ((H_Heavy, Ga, Ga), Dim5_Scalar_Gauge2 1, G_PPHH);
  ((A, Ga, Ga), Dim5_Scalar_Gauge2 1, G_PPA)]
else
[])

```

** REVISED: Compatible with CD+ and GS+. **

```

let gauge_higgs_gold =
[ ((Wp, Phi0, Phim), Vector_Scalar_Scalar 1, G_GH 1);
  ((Wm, Phi0, Phip), Vector_Scalar_Scalar 1, G_GH 1);
  ((Z, H_Heavy, Phi0), Vector_Scalar_Scalar 1, G_GH 2);
  ((Z, H_Light, Phi0), Vector_Scalar_Scalar (-1), G_GH 3);
  ((Wp, H_Heavy, Phim), Vector_Scalar_Scalar 1, G_GH 6);
  ((Wm, H_Heavy, Phip), Vector_Scalar_Scalar (-1), G_GH 6);
  ((Wp, H_Light, Phim), Vector_Scalar_Scalar (-1), G_GH 7);
  ((Wm, H_Light, Phip), Vector_Scalar_Scalar 1, G_GH 7);
  ((Phim, Wp, Ga), Scalar_Vector_Vector 1, G_GHGo 1);
  ((Phip, Wm, Ga), Scalar_Vector_Vector 1, G_GHGo 1);
  ((Phim, Wp, Z), Scalar_Vector_Vector 1, G_GHGo 2);
  ((Phip, Wm, Z), Scalar_Vector_Vector 1, G_GHGo 2);
  ((Z, Phip, Phim), Vector_Scalar_Scalar 1, G_GH 10);
  ((Ga, Phip, Phim), Vector_Scalar_Scalar 1, G_GH 11) ]

```

```

let gauge_higgs4 =
[ ((A, A, Z, Z), Scalar2_Vector2 1, G_GH4 1);
  ((H_Heavy, H_Heavy, Z, Z), Scalar2_Vector2 1, G_GH4 3);
  ((H_Light, H_Light, Z, Z), Scalar2_Vector2 1, G_GH4 2);
  ((Hp, Hm, Z, Z), Scalar2_Vector2 1, G_GH4 4);
  ((Hp, Hm, Ga, Ga), Scalar2_Vector2 1, G_GH4 5);
  ((Hp, Hm, Ga, Z), Scalar2_Vector2 1, G_GH4 6);
  ((Hp, H_Heavy, Wm, Z), Scalar2_Vector2 1, G_GH4 8);
  ((Hm, H_Heavy, Wp, Z), Scalar2_Vector2 1, G_GH4 8);
  ((Hp, H_Light, Wm, Z), Scalar2_Vector2 1, G_GH4 7);
  ((Hm, H_Light, Wp, Z), Scalar2_Vector2 1, G_GH4 7);
  ((Hp, H_Heavy, Wm, Ga), Scalar2_Vector2 1, G_GH4 10);
  ((Hm, H_Heavy, Wp, Ga), Scalar2_Vector2 1, G_GH4 10);
  ((Hp, H_Light, Wm, Ga), Scalar2_Vector2 1, G_GH4 9);
  ((Hm, H_Light, Wp, Ga), Scalar2_Vector2 1, G_GH4 9);
  ((A, A, Wp, Wm), Scalar2_Vector2 1, G_GH4 11);
  ((H_Heavy, H_Heavy, Wp, Wm), Scalar2_Vector2 1, G_GH4 13);
  ((H_Light, H_Light, Wp, Wm), Scalar2_Vector2 1, G_GH4 12);
  ((Hp, Hm, Wp, Wm), Scalar2_Vector2 1, G_GH4 14);
  ((Hp, A, Wm, Z), Scalar2_Vector2 1, G_GH4 15);
  ((Hm, A, Wp, Z), Scalar2_Vector2 (-1), G_GH4 15);
  ((Hp, A, Wm, Ga), Scalar2_Vector2 1, G_GH4 16);
  ((Hm, A, Wp, Ga), Scalar2_Vector2 (-1), G_GH4 16) ]

let gauge_higgs_gold4 =
[ ((Z, Z, Phi0, Phi0), Scalar2_Vector2 1, G_GHGo4 1);
  ((Z, Z, Phip, Phim), Scalar2_Vector2 1, G_GHGo4 2);
  ((Ga, Ga, Phip, Phim), Scalar2_Vector2 1, G_GHGo4 3);
  ((Z, Ga, Phip, Phim), Scalar2_Vector2 1, G_GHGo4 4);
  ((Wp, Wm, Phip, Phim), Scalar2_Vector2 1, G_GHGo4 5);
  ((Wp, Wm, Phi0, Phi0), Scalar2_Vector2 1, G_GHGo4 5);
  ((Wp, Z, Phim, Phi0), Scalar2_Vector2 1, G_GHGo4 6);
  ((Wm, Z, Phip, Phi0), Scalar2_Vector2 (-1), G_GHGo4 6);
  ((Wp, Ga, Phim, Phi0), Scalar2_Vector2 1, G_GHGo4 7);
  ((Wm, Ga, Phip, Phi0), Scalar2_Vector2 (-1), G_GHGo4 7);
  ((Wp, Z, Phim, H_Heavy), Scalar2_Vector2 1, G_GHGo4 9);
  ((Wm, Z, Phip, H_Heavy), Scalar2_Vector2 1, G_GHGo4 9);
  ((Wp, Ga, Phim, H_Heavy), Scalar2_Vector2 1, G_GHGo4 11);
  ((Wm, Ga, Phip, H_Heavy), Scalar2_Vector2 1, G_GHGo4 11);
  ((Wp, Z, Phim, H_Light), Scalar2_Vector2 1, G_GHGo4 8);
  ((Wm, Z, Phip, H_Light), Scalar2_Vector2 1, G_GHGo4 8);
  ((Wp, Ga, Phim, H_Light), Scalar2_Vector2 1, G_GHGo4 10);
  ((Wm, Ga, Phip, H_Light), Scalar2_Vector2 1, G_GHGo4 10) ]

let gauge_sfermion4' g m1 m2 =
[ ((Wp, Wm, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1,
   G_WWSFSF (SL, g, m1, m2));
  ((Z, Ga, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1,
   G_ZPSFSF (SL, g, m1, m2));
  ((Z, Z, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1, G_ZZSFSF
   (SL, g, m1, m2));

```

```

((Wp, Wm, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_WWSFSF
  (SU, g, m1, m2));
((Wp, Wm, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1, G_WWSFSF
  (SD, g, m1, m2));
((Z, Z, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_ZZSFSF
  (SU, g, m1, m2));
((Z, Z, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1, G_ZZSFSF
  (SD, g, m1, m2));
((Z, Ga, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_ZPSFSF
  (SU, g, m1, m2));
((Z, Ga, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1, G_ZPSFSF
  (SD, g, m1, m2)) ]
let gauge_sfermion4'' g m =
[ ((Wp, Ga, Slepton (m, g), Sneutrino (-g)), Scalar2_Vector2 1, G_WPSLSN
  (false, g, m));
  ((Wm, Ga, Slepton (m, -g), Sneutrino g), Scalar2_Vector2 1,
    G_WPSLSN (true, g, m));
  ((Wp, Z, Slepton (m, g), Sneutrino (-g)), Scalar2_Vector2 1, G_WZSLN
    (false, g, m));
  ((Wm, Z, Slepton (m, -g), Sneutrino g), Scalar2_Vector2 1,
    G_WZSLN (true, g, m));
  ((Ga, Ga, Slepton (m, g), Slepton (m, -g)), Scalar2_Vector2 1, G_PPSFSF SL);
  ((Ga, Ga, Sup (m, g), Sup (m, -g)), Scalar2_Vector2 1, G_PPSFSF SU);
  ((Ga, Ga, Sdown (m, g), Sdown (m, -g)), Scalar2_Vector2 1, G_PPSFSF SD)]
let gauge_sfermion4 g =
List.flatten (Product.list2 (gauge_sfermion4' g) [M1; M2] [M1; M2]) @
ThoList.flatmap (gauge_sfermion4'' g) [M1; M2] @
[ ((Wp, Wm, Sneutrino g, Sneutrino (-g)), Scalar2_Vector2 1, G_WWSFSF
  (SN, g, M1, M1));
  ((Z, Z, Sneutrino g, Sneutrino (-g)), Scalar2_Vector2 1, G_ZZSFSF
  (SN, g, M1, M1)) ]
let gauge_squark4'' g h m1 m2 =
[ ((Wp, Ga, Sup (m1, -g), Sdown (m2, h)), Scalar2_Vector2 1, G_WPSUSD
  (false, m1, m2, g, h));
  ((Wm, Ga, Sup (m1, g), Sdown (m2, -h)), Scalar2_Vector2 1, G_WPSUSD
  (true, m1, m2, g, h));
  ((Wp, Z, Sup (m1, -g), Sdown (m2, h)), Scalar2_Vector2 1, G_WZSUSD
  (false, m1, m2, g, h));
  ((Wm, Z, Sup (m1, g), Sdown (m2, -h)), Scalar2_Vector2 1, G_WZSUSD
  (true, m1, m2, g, h)) ]
let gauge_squark4' g h = List.flatten (Product.list2 (gauge_squark4'' g h)
  [M1; M2] [M1; M2])
let gauge_squark4 =
if Flags.ckm_present then
  List.flatten (Product.list2 gauge_squark4' [1; 2; 3] [1; 2; 3])
else
  ThoList.flatmap (fun g → gauge_squark4' g) [1; 2; 3]
let gluon_w_squark'' g h m1 m2 =
[ ((Gl, Wp, Sup (m1, -g), Sdown (m2, h)),

```

```

      Scalar2_Vector2 1, G_GlWSUSD (false,m1,m2,g,h));
      ((Gl, Wm, Sup (m1,g), Sdown (m2,-h)),
      Scalar2_Vector2 1, G_GlWSUSD (true,m1,m2,g,h)) ]
let gluon_w_squark' g h =
  List.flatten (Product.list2 (gluon_w_squark'' g h) [M1;M2] [M1;M2])
let gluon_w_squark =
  if Flags.ckm-present then
    List.flatten (Product.list2 gluon_w_squark' [1;2;3] [1;2;3])
  else
    ThoList.flatmap (fun g → gluon_w_squark' g g) [1;2;3]
let gluon_gauge_squark' g m1 m2 =
  [ ((Gl, Z, Sup (m1,g), Sup (m2,-g)), Scalar2_Vector2 2, G_GlZSFSF (SU,g,m1,m2));
    ((Gl, Z, Sdown (m1,g), Sdown (m2,-g)), Scalar2_Vector2 2, G_GlZSFSF (SD,g,m1,m2)) ]
let gluon_gauge_squark'' g m =
  [ ((Gl, Ga, Sup (m,g), Sup (m,-g)), Scalar2_Vector2 2, G_GlPSQSQ);
    ((Gl, Ga, Sdown (m,g), Sdown (m,-g)), Scalar2_Vector2 (-1), G_GlPSQSQ) ]
let gluon_gauge_squark g =
  List.flatten (Product.list2 (gluon_gauge_squark' g) [M1;M2] [M1;M2]) @
  ThoList.flatmap (gluon_gauge_squark'' g) [M1;M2]
let gluon2_squark2 g m =
  [ ((Gl, Gl, Sup (m,g), Sup (m,-g)), Scalar2_Vector2 1, G_GlGlSQSQ);
    ((Gl, Gl, Sdown (m,g), Sdown (m,-g)), Scalar2_Vector2 1, G_GlGlSQSQ) ]

** REVISED: Independent of the sign of CD. **

let higgs =
  [ ((Hp, Hm, H_Heavy), Scalar_Scalar_Scalar 1, G_H3 1);
    ((Hp, Hm, H_Light), Scalar_Scalar_Scalar 1, G_H3 2);
    ((H_Heavy, H_Heavy, H_Light), Scalar_Scalar_Scalar 1, G_H3 3);
    ((H_Heavy, H_Heavy, H_Heavy), Scalar_Scalar_Scalar 1, G_H3 4);
    ((H_Light, H_Light, H_Light), Scalar_Scalar_Scalar 1, G_H3 5);
    ((H_Heavy, H_Light, H_Light), Scalar_Scalar_Scalar 1, G_H3 6);
    ((H_Heavy, A, A), Scalar_Scalar_Scalar 1, G_H3 7);
    ((H_Light, A, A), Scalar_Scalar_Scalar 1, G_H3 8) ]

** REVISED: Compatible with GS+, independent of the sign of CD. **

let higgs_gold =
  [ ((H_Heavy, A, Phi0), Scalar_Scalar_Scalar 1, G_HGo3 1);
    ((H_Light, A, Phi0), Scalar_Scalar_Scalar 1, G_HGo3 2);
    ((H_Heavy, Hp, Phim), Scalar_Scalar_Scalar 1, G_HGo3 3);
    ((H_Heavy, Hm, Phip), Scalar_Scalar_Scalar 1, G_HGo3 3);
    ((H_Light, Hp, Phim), Scalar_Scalar_Scalar 1, G_HGo3 4);
    ((H_Light, Hm, Phip), Scalar_Scalar_Scalar 1, G_HGo3 4);
    ((A, Hp, Phim), Scalar_Scalar_Scalar (-1), G_HGo3 5);
    ((A, Hm, Phip), Scalar_Scalar_Scalar 1, G_HGo3 5);
    ((H_Heavy, Phi0, Phi0), Scalar_Scalar_Scalar (-1), G_H3 7);
    ((H_Heavy, Phip, Phim), Scalar_Scalar_Scalar (-1), G_H3 7);
    ((H_Light, Phi0, Phi0), Scalar_Scalar_Scalar (-1), G_H3 8);
    ((H_Light, Phip, Phim), Scalar_Scalar_Scalar (-1), G_H3 8) ]

```

Here follow purely scalar quartic vertices which are only available for the no-Whizard colored version.

** REVISED: Independent of the sign of CD. **

```
let higgs4 =
  [ ((Hp, Hm, Hp, Hm), Scalar4 1, G_H4 1);
    ((Hp, Hm, H_Heavy, H_Heavy), Scalar4 1, G_H4 2);
    ((Hp, Hm, H_Light, H_Light), Scalar4 1, G_H4 3);
    ((Hp, Hm, H_Heavy, H_Light), Scalar4 1, G_H4 4);
    ((Hp, Hm, A, A), Scalar4 1, G_H4 5);
    ((H_Heavy, H_Heavy, H_Heavy, H_Heavy), Scalar4 1, G_H4 6);
    ((H_Light, H_Light, H_Light, H_Light), Scalar4 1, G_H4 6);
    ((H_Heavy, H_Heavy, H_Light, H_Light), Scalar4 1, G_H4 7);
    ((H_Heavy, H_Light, H_Light, H_Light), Scalar4 1, G_H4 8);
    ((H_Heavy, H_Heavy, H_Heavy, H_Light), Scalar4 (-1), G_H4 8);
    ((H_Heavy, H_Heavy, A, A), Scalar4 1, G_H4 9);
    ((H_Light, H_Light, A, A), Scalar4 (-1), G_H4 9);
    ((H_Heavy, H_Light, A, A), Scalar4 1, G_H4 10);
    ((A, A, A, A), Scalar4 1, G_H4 11) ]
```

** REVISED: Compatible with GS+, independent of the sign of CD. **

```
let higgs_gold4 =
  [ ((H_Heavy, H_Heavy, A, Phi0), Scalar4 1, G_HGo4 1);
    ((H_Heavy, H_Light, A, Phi0), Scalar4 1, G_HGo4 2);
    ((H_Light, H_Light, A, Phi0), Scalar4 (-1), G_HGo4 1);
    ((A, A, A, Phi0), Scalar4 3, G_HGo4 3);
    ((Hp, Hm, A, Phi0), Scalar4 1, G_HGo4 3);
    ((H_Heavy, H_Heavy, Hp, Phim), Scalar4 1, G_HGo4 4);
    ((H_Heavy, H_Heavy, Hm, Phip), Scalar4 1, G_HGo4 4);
    ((H_Heavy, H_Light, Hp, Phim), Scalar4 1, G_HGo4 5);
    ((H_Heavy, H_Light, Hm, Phip), Scalar4 1, G_HGo4 5);
    ((H_Light, H_Light, Hp, Phim), Scalar4 (-1), G_HGo4 4);
    ((H_Light, H_Light, Hm, Phip), Scalar4 (-1), G_HGo4 4);
    ((A, A, Hp, Phim), Scalar4 1, G_HGo4 6);
    ((A, A, Hm, Phip), Scalar4 1, G_HGo4 6);
    ((H_Heavy, A, Hp, Phim), Scalar4 1, G_HGo4 7);
    ((H_Heavy, A, Hm, Phip), Scalar4 (-1), G_HGo4 7);
    ((H_Light, A, Hp, Phim), Scalar4 1, G_HGo4 8);
    ((H_Light, A, Hm, Phip), Scalar4 (-1), G_HGo4 8);
    ((Hp, Hm, Hp, Phim), Scalar4 2, G_HGo4 6);
    ((Hp, Hm, Hm, Phip), Scalar4 2, G_HGo4 6);
    ((H_Heavy, H_Heavy, Phi0, Phi0), Scalar4 (-1), G_H4 9);
    ((H_Heavy, H_Light, Phi0, Phi0), Scalar4 (-1), G_H4 10);
    ((H_Light, H_Light, Phi0, Phi0), Scalar4 1, G_H4 9);
    ((A, A, Phi0, Phi0), Scalar4 1, G_HGo4 9);
    ((Hp, Hm, Phi0, Phi0), Scalar4 1, G_HGo4 10);
    ((H_Heavy, Hp, Phim, Phi0), Scalar4 1, G_HGo4 8);
    ((H_Heavy, Hm, Phip, Phi0), Scalar4 (-1), G_HGo4 8);
    ((H_Light, Hp, Phim, Phi0), Scalar4 (-1), G_HGo4 7);
    ((H_Light, Hm, Phip, Phi0), Scalar4 1, G_HGo4 7);
    ((A, Hp, Phim, Phi0), Scalar4 1, G_HGo4 11);
```



```

((A, Hm, Phip, Phi0), Scalar4 1, G_HGo4 11);
((H_Heavy, H_Heavy, Phip, Phim), Scalar4 1, G_HGo4 12);
((H_Heavy, H_Light, Phip, Phim), Scalar4 1, G_HGo4 13);
((H_Light, H_Light, Phip, Phim), Scalar4 1, G_HGo4 14);
((A, A, Phip, Phim), Scalar4 1, G_HGo4 15);
((Hp, Hm, Phip, Phim), Scalar4 1, G_HGo4 16);
((Hp, Hp, Phim, Phim), Scalar4 1, G_HGo4 17);
((Hm, Hm, Phip, Phip), Scalar4 1, G_HGo4 17);
((Hp, Phim, Phi0, Phi0), Scalar4 (-1), G_HGo4 6);
((Hm, Phip, Phi0, Phi0), Scalar4 (-1), G_HGo4 6);
((A, Phi0, Phi0, Phi0), Scalar4 (-3), G_HGo4 6);
((A, Phi0, Phip, Phim), Scalar4 (-1), G_HGo4 6);
((Hp, Phim, Phip, Phim), Scalar4 (-2), G_HGo4 6);
((Hm, Phip, Phip, Phim), Scalar4 (-2), G_HGo4 6) ]

```

** REVISED: Independent of the sign of CD and GS. **

```

let goldstone4 =
[ ((Phi0, Phi0, Phi0, Phi0), Scalar4 1, G_GG4 1);
  ((Phip, Phim, Phi0, Phi0), Scalar4 1, G_GG4 2);
  ((Phip, Phim, Phip, Phim), Scalar4 1, G_GG4 3) ]

```

The vertices of the type Higgs - Sfermion - Sfermion are independent of the choice of the CD sign since they are quadratic in the gauge coupling.

** REVISED: Independent of the sign of CD. **

```

let higgs_sneutrino' g =
[ ((H_Heavy, Sneutrino g, Sneutrino (-g)), Scalar_Scalar_Scalar 1,
   G_H2SFSF (SN, g, M1, M1));
  ((H_Light, Sneutrino g, Sneutrino (-g)), Scalar_Scalar_Scalar 1,
   G_H1SFSF (SN, g, M1, M1));
  ((Hp, Sneutrino (-g), Slepton (M1, g)), Scalar_Scalar_Scalar 1,
   G_HSNSL (false, g, M1));
  ((Hm, Sneutrino g, Slepton (M1, -g)), Scalar_Scalar_Scalar 1,
   G_HSNSL (true, g, M1)) ]
let higgs_sneutrino'' =
[ ((Hp, Sneutrino (-3), Slepton (M2, 3)), Scalar_Scalar_Scalar 1,
   G_HSNSL (false, 3, M2));
  ((Hm, Sneutrino 3, Slepton (M2, -3)), Scalar_Scalar_Scalar 1,
   G_HSNSL (false, 3, M2)) ]
let higgs_sneutrino =
  ThoList.flatmap higgs_sneutrino' [1; 2; 3] @ higgs_sneutrino''

```

Under the assumption that there is no mixing between the left- and right-handed sfermions for the first two generations there is only a coupling of the form Higgs - sfermion1 - sfermion2 for the third generation. All the others are suppressed by m_f/M_W .

** REVISED: Independent of the sign of CD. **

```

let higgs_sfermion' g m1 m2 =
[ ((H_Heavy, Slepton (m1, g), Slepton (m2, -g)), Scalar_Scalar_Scalar 1,
   G_H2SFSF (SL, g, m1, m2));
  ((H_Light, Slepton (m1, g), Slepton (m2, -g)), Scalar_Scalar_Scalar 1,

```

```

      G_H1SFSF (SL, g, m1, m2));
    ((H_Heavy, Sup (m1, g), Sup (m2, -g)), Scalar_Scalar_Scalar 1,
      G_H2SFSF (SU, g, m1, m2));
    ((H_Heavy, Sdown (m1, g), Sdown (m2, -g)), Scalar_Scalar_Scalar 1,
      G_H2SFSF (SD, g, m1, m2));
    ((H_Light, Sup (m1, g), Sup (m2, -g)), Scalar_Scalar_Scalar 1,
      G_H1SFSF (SU, g, m1, m2));
    ((H_Light, Sdown (m1, g), Sdown (m2, -g)), Scalar_Scalar_Scalar 1,
      G_H1SFSF (SD, g, m1, m2)) ]
let higgs_sfermion'' m1 m2 =
  [ ((A, Slepton (m1, 3), Slepton (m2, -3)), Scalar_Scalar_Scalar 1,
      G_ASFSF (SL, 3, m1, m2));
    ((A, Sup (m1, 3), Sup (m2, -3)), Scalar_Scalar_Scalar 1,
      G_ASFSF (SU, 3, m1, m2));
    ((A, Sdown (m1, 3), Sdown (m2, -3)), Scalar_Scalar_Scalar 1,
      G_ASFSF (SD, 3, m1, m2)) ]
let higgs_sfermion = List.flatten (Product.list2 (higgs_sfermion' 3)
  [M1; M2] [M1; M2]) @
  (higgs_sfermion' 1 M1 M1) @ (higgs_sfermion' 1 M2 M2) @
  (higgs_sfermion' 2 M1 M1) @ (higgs_sfermion' 2 M2 M2) @
  List.flatten (Product.list2 higgs_sfermion'' [M1; M2] [M1; M2])

** REVISED: Independent of the sign of CD, compatible with GS+. **

let goldstone_sfermion' g m1 m2 =
  [ ((Phi0, Slepton (m1, g), Slepton (m2, -g)), Scalar_Scalar_Scalar 1,
      G_GoSFSF (SL, g, m1, m2));
    ((Phi0, Sup (m1, g), Sup (m2, -g)), Scalar_Scalar_Scalar 1,
      G_GoSFSF (SU, g, m1, m2));
    ((Phi0, Sdown (m1, g), Sdown (m2, -g)), Scalar_Scalar_Scalar 1,
      G_GoSFSF (SD, g, m1, m2))]
let goldstone_sfermion'' g =
  [ ((Phip, Sneutrino (-g), Slepton (M1, g)), Scalar_Scalar_Scalar 1,
      G_GoSNSL (false, g, M1));
    ((Phim, Sneutrino g, Slepton (M1, -g)), Scalar_Scalar_Scalar 1,
      G_GoSNSL (true, g, M1)) ]
let goldstone_sfermion''' g =
  [ ((Phip, Sneutrino (-g), Slepton (M2, g)), Scalar_Scalar_Scalar 1,
      G_GoSNSL (false, g, M2));
    ((Phim, Sneutrino g, Slepton (M2, -g)), Scalar_Scalar_Scalar 1,
      G_GoSNSL (true, g, M2))]
let goldstone_sfermion =
  List.flatten (Product.list2 (goldstone_sfermion' 3) [M1; M2] [M1; M2]) @
  ThoList.flatmap goldstone_sfermion'' [1; 2; 3] @
  goldstone_sfermion''' 3

** REVISED: Independent of the sign of CD. **

let higgs_squark' g h m1 m2 =
  [ ((Hp, Sup (m1, -g), Sdown (m2, h)), Scalar_Scalar_Scalar 1,
      G_HSUSD (false, m1, m2, g, h));
    ((Hm, Sup (m1, g), Sdown (m2, -h)), Scalar_Scalar_Scalar 1,

```

```

      G_HSUSD (true,m1,m2,g,h)) ]
let higgs_squark_a g h = higgs_squark' g h M1 M1
let higgs_squark_b (g,h) = List.flatten (Product.list2 (higgs_squark' g h)
                                                    [M1; M2] [M1; M2])

let higgs_squark =
  if Flags.ckm-present then
    List.flatten (Product.list2 higgs_squark_a [1; 2] [1; 2]) @
    ThoList.flatmap higgs_squark_b [(1, 3); (2, 3); (3, 3); (3, 1); (3, 2)]
  else
    higgs_squark_a 1 1 @ higgs_squark_a 2 2 @ higgs_squark_b (3, 3)

** REVISED: Independent of the sign of CD, compatible with GS+. **

let goldstone_squark' g h m1 m2 =
  [ ((Phip, Sup (m1, -g), Sdown (m2, h)), Scalar_Scalar_Scalar 1,
      G_GSUSD (false,m1,m2,g,h));
    ((Phim, Sup (m1, g), Sdown (m2, -h)), Scalar_Scalar_Scalar 1,
      G_GSUSD (true,m1,m2,g,h)) ]
let goldstone_squark_a g h = goldstone_squark' g h M1 M1
let goldstone_squark_b (g,h) = List.flatten (Product.list2
      (goldstone_squark' g h) [M1; M2] [M1; M2])
let goldstone_squark =
  List.flatten (Product.list2 goldstone_squark_a [1; 2] [1; 2]) @
  ThoList.flatmap goldstone_squark_b [(1, 3); (2, 3); (3, 3); (3, 1); (3, 2)]

BAUSTELLE: For the quartic scalar coupligs we does not allow whiz_col.

let higgs_sneutrino4' g m =
  [ ((Hp, H_Heavy, Slepton (m, g), Sneutrino (-g)), Scalar4 1,
      G_HH2SLSN (false,m,g));
    ((Hm, H_Heavy, Slepton (m, -g), Sneutrino g), Scalar4 1,
      G_HH2SLSN (true,m,g));
    ((Hp, H_Light, Slepton (m, g), Sneutrino (-g)), Scalar4 1,
      G_HH1SLSN (false,m,g));
    ((Hm, H_Light, Slepton (m, -g), Sneutrino g), Scalar4 1,
      G_HH1SLSN (true,m,g));
    ((Hp, A, Slepton (m, g), Sneutrino (-g)), Scalar4 1,
      G_HASLSN (false,m,g));
    ((Hm, A, Slepton (m, -g), Sneutrino g), Scalar4 1,
      G_HASLSN (true,m,g)) ]
let higgs_sneutrino4 g =
  ThoList.flatmap (higgs_sneutrino4' g) [M1; M2] @
  [ ((H_Heavy, H_Heavy, Sneutrino g, Sneutrino (-g)), Scalar4 1,
      G_H2H2SFSF (SN, M1, M1, g));
    ((H_Heavy, H_Light, Sneutrino g, Sneutrino (-g)), Scalar4 1,
      G_H1H2SFSF (SN, M1, M1, g));
    ((H_Light, H_Light, Sneutrino g, Sneutrino (-g)), Scalar4 1,
      G_H1H1SFSF (SN, M1, M1, g));
    ((Hp, Hm, Sneutrino g, Sneutrino (-g)), Scalar4 1, G_HHSFSF (SN, M1, M1, g)) ]

let higgs_sfermion4' g m1 m2 =
  [ ((H_Heavy, H_Heavy, Slepton (m1, g), Slepton (m2, -g)), Scalar4 1,
      G_H2H2SFSF (SL, m1, m2, g));

```

```

((H_Heavy, H_Light, Slepton (m1, g), Slepton (m2, -g)), Scalar4 1,
  G_H1H2SFSS (SL, m1, m2, g));
((H_Light, H_Light, Slepton (m1, g), Slepton (m2, -g)), Scalar4 1,
  G_H1H1SFSS (SL, m1, m2, g));
((A, A, Slepton (m1, g), Slepton (m2, -g)), Scalar4 1,
  G_AASFSS (SL, m1, m2, g));
((Hp, Hm, Slepton (m1, g), Slepton (m2, -g)), Scalar4 1,
  G_HHSFSS (SL, m1, m2, g));
((H_Heavy, H_Heavy, Sup (m1, g), Sup (m2, -g)), Scalar4 1,
  G_H2H2SFSS (SU, m1, m2, g));
((H_Heavy, H_Heavy, Sdown (m1, g), Sdown (m2, -g)), Scalar4 1,
  G_H2H2SFSS (SD, m1, m2, g));
((H_Light, H_Light, Sup (m1, g), Sup (m2, -g)), Scalar4 1,
  G_H1H1SFSS (SU, m1, m2, g));
((H_Light, H_Light, Sdown (m1, g), Sdown (m2, -g)), Scalar4 1,
  G_H1H1SFSS (SD, m1, m2, g));
((H_Light, H_Heavy, Sup (m1, g), Sup (m2, -g)), Scalar4 1,
  G_H1H2SFSS (SU, m1, m2, g));
((H_Light, H_Heavy, Sdown (m1, g), Sdown (m2, -g)), Scalar4 1,
  G_H1H2SFSS (SD, m1, m2, g));
((Hp, Hm, Sup (m1, g), Sup (m2, -g)), Scalar4 1, G_HHSFSS (SU, m1, m2, g));
((Hp, Hm, Sdown (m1, g), Sdown (m2, -g)), Scalar4 1, G_HHSFSS (SD, m1, m2, g));
((A, A, Sup (m1, g), Sup (m2, -g)), Scalar4 1, G_AASFSS (SU, m1, m2, g));
((A, A, Sdown (m1, g), Sdown (m2, -g)), Scalar4 1, G_AASFSS (SD, m1, m2, g)) ]
let higgs-sfermion4 g = List.flatten (Product.list2 (higgs-sfermion4' g)
                                                    [M1; M2] [M1; M2])

let higgs-squark4' g h m1 m2 =
[ ((Hp, H_Light, Sup (m1, -g), Sdown (m2, h)), Scalar4 1,
  G_HH1SUSD (false, m1, m2, g, h));
  ((Hm, H_Light, Sup (m1, g), Sdown (m2, -h)), Scalar4 1,
  G_HH1SUSD (true, m1, m2, g, h));
  ((Hp, H_Heavy, Sup (m1, -g), Sdown (m2, h)), Scalar4 1,
  G_HH2SUSD (false, m1, m2, g, h));
  ((Hm, H_Heavy, Sup (m1, g), Sdown (m2, -h)), Scalar4 1,
  G_HH2SUSD (true, m1, m2, g, h));
  ((Hp, A, Sup (m1, -g), Sdown (m2, h)), Scalar4 1,
  G_HASUSD (false, m1, m2, g, h));
  ((Hm, A, Sup (m1, g), Sdown (m2, -h)), Scalar4 1,
  G_HASUSD (true, m1, m2, g, h)) ]
let higgs-squark4 g h = List.flatten (Product.list2 (higgs-squark4' g h)
                                                    [M1; M2] [M1; M2])

let higgs-gold-sneutrino' g m =
[ ((Hp, Phi0, Sneutrino (-g), Slepton (m, g)), Scalar4 1, G_HGSNSL (false, m, g));
  ((Hm, Phi0, Sneutrino g, Slepton (m, -g)), Scalar4 1, G_HGSNSL (true, m, g));
  ((H_Heavy, Phip, Sneutrino (-g), Slepton (m, g)), Scalar4 1,
  G_H2GSNSL (false, m, g));
  ((H_Heavy, Phim, Sneutrino g, Slepton (m, -g)), Scalar4 1,
  G_H2GSNSL (true, m, g));
  ((H_Light, Phip, Sneutrino (-g), Slepton (m, g)), Scalar4 1,

```

```

      G_H1GSNSL (false,m,g));
    ((H_Light, Phim, Sneutrino g, Slepton (m,-g)), Scalar4 1,
      G_H1GSNSL (true,m,g));
    ((A, Phip, Sneutrino (-g), Slepton (m,g)), Scalar4 1, G_AGSNSL (false,m,g));
    ((A, Phim, Sneutrino g, Slepton (m,-g)), Scalar4 1, G_AGSNSL (true,m,g));
    ((Phi0, Phip, Sneutrino (-g), Slepton (m,g)), Scalar4 1, G_GGSNSL (false,m,g));
    ((Phi0, Phim, Sneutrino g, Slepton (m,-g)), Scalar4 1, G_GGSNSL (true,m,g))]
let higgs_gold_sneutrino g =
  ThoList.flatmap (higgs_gold_sneutrino' g) [M1; M2] @
  [ ((A, Phi0, Sneutrino g, Sneutrino (-g)), Scalar4 1,
      G_AG0SFSF (SN, M1, M1, g));
    ((Hp, Phim, Sneutrino g, Sneutrino (-g)), Scalar4 1,
      G_HGSFSF (SN, M1, M1, g));
    ((Hm, Phip, Sneutrino g, Sneutrino (-g)), Scalar4 1,
      G_HGSFSF (SN, M1, M1, g));
    ((Phip, Phim, Sneutrino g, Sneutrino (-g)), Scalar4 1,
      G_GGSFSF (SN, M1, M1, g));
    ((Phi0, Phi0, Sneutrino g, Sneutrino (-g)), Scalar4 1,
      G_G0G0SFSF (SN, M1, M1, g)) ]
let higgs_gold_sfermion' g m1 m2 =
  [ ((A, Phi0, Slepton (m1,g), Slepton (m2,-g)), Scalar4 1,
      G_AG0SFSF (SL, m1, m2, g));
    ((Hp, Phim, Slepton (m1,g), Slepton (m2,-g)), Scalar4 1,
      G_HGSFSF (SL, m1, m2, g));
    ((Hm, Phip, Slepton (m1,g), Slepton (m2,-g)), Scalar4 1,
      G_HGSFSF (SL, m1, m2, g));
    ((Phip, Phim, Slepton (m1,g), Slepton (m2,-g)), Scalar4 1,
      G_GGSFSF (SL, m1, m2, g));
    ((Phi0, Phi0, Slepton (m1,g), Slepton (m2,-g)), Scalar4 1,
      G_G0G0SFSF (SL, m1, m2, g));
    ((A, Phi0, Sup (m1,g), Sup (m2,-g)), Scalar4 1, G_AG0SFSF (SU, m1, m2, g));
    ((A, Phi0, Sdown (m1,g), Sdown (m2,-g)), Scalar4 1,
      G_AG0SFSF (SD, m1, m2, g));
    ((Hp, Phim, Sup (m1,g), Sup (m2,-g)), Scalar4 1, G_HGSFSF (SU, m1, m2, g));
    ((Hm, Phip, Sup (m1,g), Sup (m2,-g)), Scalar4 1, G_HGSFSF (SU, m1, m2, g));
    ((Hp, Phim, Sdown (m1,g), Sdown (m2,-g)), Scalar4 1,
      G_HGSFSF (SD, m1, m2, g));
    ((Hm, Phip, Sdown (m1,g), Sdown (m2,-g)), Scalar4 1,
      G_HGSFSF (SD, m1, m2, g));
    ((Phip, Phim, Sup (m1,g), Sup (m2,-g)), Scalar4 1,
      G_GGSFSF (SU, m1, m2, g));
    ((Phip, Phim, Sdown (m1,g), Sdown (m2,-g)), Scalar4 1,
      G_GGSFSF (SD, m1, m2, g));
    ((Phi0, Phi0, Sup (m1,g), Sup (m2,-g)), Scalar4 1,
      G_G0G0SFSF (SU, m1, m2, g));
    ((Phi0, Phi0, Sdown (m1,g), Sdown (m2,-g)), Scalar4 1,
      G_G0G0SFSF (SD, m1, m2, g)) ]
let higgs_gold_sfermion g = List.flatten (Product.list2
  (higgs_gold_sfermion' g) [M1; M2] [M1; M2])

```

```

let higgs_gold_squark' g h m1 m2 =
  [ ((Hp, Phi0, Sup (m1, -g), Sdown (m2, h)), Scalar4 1,
      G_HGSUSD (false, m1, m2, g, h));
    ((Hm, Phi0, Sup (m1, g), Sdown (m2, -h)), Scalar4 1,
      G_HGSUSD (true, m1, m2, g, h));
    ((H_Heavy, Phip, Sup (m1, -g), Sdown (m2, h)), Scalar4 1,
      G_H2GSUSD (false, m1, m2, g, h));
    ((H_Heavy, Phim, Sup (m1, g), Sdown (m2, -h)), Scalar4 1,
      G_H2GSUSD (true, m1, m2, g, h));
    ((H_Light, Phip, Sup (m1, -g), Sdown (m2, h)), Scalar4 1,
      G_H1GSUSD (false, m1, m2, g, h));
    ((H_Light, Phim, Sup (m1, g), Sdown (m2, -h)), Scalar4 1,
      G_H1GSUSD (true, m1, m2, g, h));
    ((A, Phip, Sup (m1, -g), Sdown (m2, h)), Scalar4 1,
      G_AGSUSD (false, m1, m2, g, h));
    ((A, Phim, Sup (m1, g), Sdown (m2, -h)), Scalar4 1,
      G_AGSUSD (true, m1, m2, g, h));
    ((Phi0, Phip, Sup (m1, -g), Sdown (m2, h)), Scalar4 1,
      G_GGSUSD (false, m1, m2, g, h));
    ((Phi0, Phim, Sup (m1, g), Sdown (m2, -h)), Scalar4 1,
      G_GGSUSD (true, m1, m2, g, h)) ]
let higgs_gold_squark g h = List.flatten (Product.list2 (higgs_gold_squark'
  g h) [M1; M2] [M1; M2])

let sneutrino4' (g, h) =
  [ ((Sneutrino g, Sneutrino h, Sneutrino (-g), Sneutrino (-h)), Scalar4 1,
      G_SN4 (g, h))]
let sneutrino4 = ThoList.flatmap sneutrino4'
  [(1, 1); (1, 2); (1, 3); (2, 2); (2, 3); (3, 3)]

let sneu2_slep2_1' g h m1 m2 =
  ((Sneutrino (-g), Sneutrino g, Slepton (m1, -h), Slepton (m2, h)), Scalar4 1,
    G_SN2SL2_1 (m1, m2, g, h))
let sneu2_slep2_2' (g, h) m1 m2 =
  ((Sneutrino g, Sneutrino (-h), Slepton (m1, -g), Slepton (m2, h)), Scalar4 1,
    G_SN2SL2_2 (m1, m2, g, h))
let sneu2_slep2_1 g h = Product.list2 (sneu2_slep2_1' g h) [M1; M2] [M1; M2]
let sneu2_slep2_2 (g, h) = Product.list2 (sneu2_slep2_2' (g, h)) [M1; M2] [M1; M2]

```

The 4-slepton-vertices have the following structure: The sleptons come up in pairs of a positive and a negative slepton of the same generation; there is no vertex with e.g. two negative selectrons and two positive smuons, that of course would be a contradiction to the conservation of the separate slepton numbers of each generation which is not implemented in the MSSM. Because there is no CKM-mixing for the sleptons (in case of massless neutrinos) we maximally have two different generations of sleptons in a 4-slepton-vertex.

```

let slepton4_1gen' g (m1, m2, m3, m4) =
  [ ((Slepton (m1, -g), Slepton (m2, g), Slepton (m3, -g), Slepton (m4, g)),
      Scalar4 1, G_SL4 (m1, m2, m3, m4, g)) ]
let slepton4_1gen g = ThoList.flatmap (slepton4_1gen' g) [(M1, M1, M1, M1);
  (M1, M1, M1, M2); (M1, M1, M2, M1); (M1, M1, M2, M2); (M1, M2, M1, M2); (M1, M2, M2, M1);
  (M2, M1, M1, M1); (M2, M1, M1, M2); (M2, M1, M2, M1); (M2, M1, M2, M2); (M2, M2, M1, M1);
  (M2, M2, M1, M2); (M2, M2, M2, M1); (M2, M2, M2, M2)]

```

```

      (M1, M2, M2, M2); (M2, M1, M2, M2); (M2, M2, M2, M2) ]
let slepton4_2gen' (g, h) (m1, m2) (m3, m4) =
  ((Slepton (m1, -g), Slepton (m2, g), Slepton (m3, -h), Slepton (m4, h)),
   Scalar4 1, G_SL4_2 (m1, m2, m3, m4, g, h))
let slepton4_2gen (g, h) =
  Product.list2 (slepton4_2gen' (g, h)) [(M1, M1); (M1, M2); (M2, M1); (M2, M2)]
  [(M1, M1); (M1, M2); (M2, M1); (M2, M2)]
let sneu2_squark2' g h m1 m2 =
  [ ((Sneutrino (-g), Sneutrino g, Sup (m1, -h), Sup (m2, h)), Scalar4 1,
     G_SN2SQ2 (SU, m1, m2, g, h));
    ((Sneutrino (-g), Sneutrino g, Sdown (m1, -h), Sdown (m2, h)), Scalar4 1,
     G_SN2SQ2 (SD, m1, m2, g, h)) ]
let sneu2_squark2 g h = List.flatten (Product.list2 (sneu2_squark2' g h)
  [M1; M2] [M1; M2])
let slepton2_squark2'' g h m1 m2 m3 m4 =
  [ ((Slepton (m1, -g), Slepton (m2, g), Sup (m3, -h), Sup (m4, h)), Scalar4 1,
     G_SL2SQ2 (SU, m1, m2, m3, m4, g, h));
    ((Slepton (m1, -g), Slepton (m2, g), Sdown (m3, -h), Sdown (m4, h)),
     Scalar4 1, G_SL2SQ2 (SD, m1, m2, m3, m4, g, h)) ]
let slepton2_squark2' g h m1 m2 =
  List.flatten (Product.list2 (slepton2_squark2'' g h m1 m2) [M1; M2] [M1; M2])
let slepton2_squark2 g h =
  List.flatten (Product.list2 (slepton2_squark2' g h) [M1; M2] [M1; M2])
let slep_sneu_squark2'' g1 g2 g3 m1 m2 m3 =
  [ ((Sup (m1, -g1), Sdown (m2, g2), Slepton (m3, -g3), Sneutrino g3),
     Scalar4 1, G_SUSDSNSL (false, m1, m2, m3, g1, g2, g3));
    ((Sup (m1, g1), Sdown (m2, -g2), Slepton (m3, g3), Sneutrino (-g3)),
     Scalar4 1, G_SUSDSNSL (true, m1, m2, m3, g1, g2, g3)) ]
let slep_sneu_squark2' g1 g2 g3 m1 =
  List.flatten (Product.list2 (slep_sneu_squark2'' g1 g2 g3 m1)
  [M1; M2] [M1; M2])
let slep_sneu_squark2 g1 g2 =
  List.flatten (Product.list2 (slep_sneu_squark2' g1 g2) [1; 2; 3] [M1; M2])

```

There are three kinds of 4-squark-vertices: Four up-Squarks, four down-squarks or two up- and two down-squarks.

```

let sup4_1gen' g (m1, m2, m3, m4) =
  [ ((Sup (m1, -g), Sup (m2, g), Sup (m3, -g), Sup (m4, g)), Scalar4 1,
     G_SU4 (m1, m2, m3, m4, g)) ]
let sup4_1gen g = ThoList.flatmap (sup4_1gen' g) [(M1, M1, M1, M1);
  (M1, M1, M1, M2); (M1, M1, M2, M1); (M1, M1, M2, M2); (M1, M2, M1, M2); (M1, M2, M2, M1);
  (M1, M2, M2, M2); (M2, M1, M2, M2); (M2, M2, M2, M2) ]
let sup4_2gen' (g, h) (m1, m2) (m3, m4) =
  ((Sup (m1, -g), Sup (m2, g), Sup (m3, -h), Sup (m4, h)), Scalar4 1,
   G_SU4_2 (m1, m2, m3, m4, g, h))
let sup4_2gen (g, h) =
  Product.list2 (sup4_2gen' (g, h)) [(M1, M1); (M1, M2); (M2, M1); (M2, M2)]
  [(M1, M1); (M1, M2); (M2, M1); (M2, M2)]

```

```

let sdown4_1gen' g (m1, m2, m3, m4) =
  [ ((Sdown (m1, -g), Sdown (m2, g), Sdown (m3, -g), Sdown (m4, g)), Scalar4 1,
      G_SD4 (m1, m2, m3, m4, g)) ]
let sdown4_1gen g = ThoList.flatmap (sdown4_1gen' g) [(M1, M1, M1, M1);
  (M1, M1, M1, M2); (M1, M1, M2, M1); (M1, M1, M2, M2); (M1, M2, M1, M2); (M1, M2, M2, M1);
  (M1, M2, M2, M2); (M2, M1, M2, M2); (M2, M2, M2, M2) ]
let sdown4_2gen' (g, h) (m1, m2) (m3, m4) =
  ((Sdown (m1, -g), Sdown (m2, g), Sdown (m3, -h), Sdown (m4, h)), Scalar4 1,
      G_SD4_2 (m1, m2, m3, m4, g, h))
let sdown4_2gen (g, h) =
  Product.list2 (sdown4_2gen' (g, h)) [(M1, M1); (M1, M2); (M2, M1); (M2, M2)]
  [(M1, M1); (M1, M2); (M2, M1); (M2, M2)]
let sup2_sdown2_3 g1 g2 g3 g4 m1 m2 m3 m4 =
  ((Sup (m1, -g1), Sup (m2, g2), Sdown (m3, -g3), Sdown
      (m4, g4)), Scalar4 1, G_SU2SD2 (m1, m2, m3, m4, g1, g2, g3, g4))
let sup2_sdown2_2 g1 g2 g3 g4 m1 m2 =
  Product.list2 (sup2_sdown2_3 g1 g2 g3 g4 m1 m2) [M1; M2] [M1; M2]
let sup2_sdown2_1 g1 g2 g3 g4 =
  List.flatten (Product.list2 (sup2_sdown2_2 g1 g2 g3 g4) [M1; M2] [M1; M2])
let sup2_sdown2 g1 g2 =
  List.flatten (Product.list2 (sup2_sdown2_1 g1 g2) [1; 2; 3] [1; 2; 3])
let quartic_grav_gauge g m =
  [ ((Grino, Slepton (m, -g), Ga, L g), GBBG (1, Gravbar, SLRV, Psi), G_Gr4A_Sl (g, m));
    ((L (-g), Slepton (m, g), Ga, Grino), GBBG (1, Psibar, SLRV, Grav), G_Gr4A_Slc (g, m));
    ((Grino, Sup (m, -g), Ga, U g), GBBG (1, Gravbar, SLRV, Psi), G_Gr4A_Su (g, m));
    ((U (-g), Sup (m, g), Ga, Grino), GBBG (1, Psibar, SLRV, Grav), G_Gr4A_Suc (g, m));
    ((Grino, Sdown (m, -g), Ga, D g), GBBG (1, Gravbar, SLRV, Psi), G_Gr4A_Sd (g, m));
    ((D (-g), Sdown (m, g), Ga, Grino), GBBG (1, Psibar, SLRV, Grav), G_Gr4A_Sdc (g, m));
    ((Grino, Slepton (m, -g), Z, L g), GBBG (1, Gravbar, SLRV, Psi), G_Gr4Z_Sl (g, m));
    ((L (-g), Slepton (m, g), Z, Grino), GBBG (1, Psibar, SLRV, Grav), G_Gr4Z_Slc (g, m));
    ((Grino, Sup (m, -g), Z, U g), GBBG (1, Gravbar, SLRV, Psi), G_Gr4Z_Su (g, m));
    ((U (-g), Sup (m, g), Z, Grino), GBBG (1, Psibar, SLRV, Grav), G_Gr4Z_Suc (g, m));
    ((Grino, Sdown (m, -g), Z, D g), GBBG (1, Gravbar, SLRV, Psi), G_Gr4Z_Sd (g, m));
    ((D (-g), Sdown (m, g), Z, Grino), GBBG (1, Psibar, SLRV, Grav), G_Gr4Z_Sdc (g, m));
    ((Grino, Sup (m, -g), Gl, U g), GBBG (1, Gravbar, SLRV, Psi), G_Gr4Gl_Su (g, m));
    ((U (-g), Sup (m, g), Gl, Grino), GBBG (1, Psibar, SLRV, Grav), G_Gr4Gl_Suc (g, m));
    ((Grino, Sdown (m, -g), Gl, D g), GBBG (1, Gravbar, SLRV, Psi), G_Gr4Gl_Sd (g, m));
    ((D (-g), Sdown (m, g), Gl, Grino), GBBG (1, Psibar, SLRV, Grav), G_Gr4Gl_Sdc (g, m));
    ((Grino, Slepton (m, -g), Wm, N g), GBBG (1, Gravbar, SLV, Psi), G_Gr4W_Sl (g, m));
    ((N (-g), Slepton (m, g), Wp, Grino), GBBG (1, Psibar, SLV, Grav), G_Gr4Z_Slc (g, m));
    ((Grino, Sup (m, -g), Wp, D g), GBBG (1, Gravbar, SLV, Psi), G_Gr4W_Su (g, m));
    ((D (-g), Sup (m, g), Wm, Grino), GBBG (1, Psibar, SLV, Grav), G_Gr4W_Suc (g, m));
    ((Grino, Sdown (m, -g), Wm, U g), GBBG (1, Gravbar, SLV, Psi), G_Gr4W_Sd (g, m));
    ((U (-g), Sdown (m, g), Wp, Grino), GBBG (1, Psibar, SLV, Grav), G_Gr4W_Sdc (g, m)) ]
let quartic_grav_sneutrino g =
  [ ((Grino, Sneutrino (-g), Z, N g), GBBG (1, Gravbar, SLV, Psi), G_Gr4Z_Sn);
    ((N (-g), Sneutrino g, Z, Grino), GBBG (1, Psibar, SLV, Grav), G_Gr4Z_Snc);
    ((Grino, Sneutrino (-g), Wp, L g), GBBG (1, Gravbar, SLV, Psi), G_Gr4W_Sn);
    ((L (-g), Sneutrino g, Wm, Grino), GBBG (1, Psibar, SLV, Grav), G_Gr4W_Snc) ]

```



```

let quartic_grav_neu n =
  [ ((Grino, Wp, Wm, Neutralino n), GBBG (1, Gravbar, V2LR, Chi), G-Gr4-Neu n);
    ((Grino, H-Light, Z, Neutralino n), GBBG (1, Gravbar, SLRV, Chi), G-Gr4-Z-H1 n);
    ((Grino, H-Heavy, Z, Neutralino n), GBBG (1, Gravbar, SLRV, Chi), G-Gr4-Z-H2 n);
    ((Grino, A, Z, Neutralino n), GBBG (1, Gravbar, SLRV, Chi), G-Gr4-Z-H3 n);
    ((Grino, Hm, Wp, Neutralino n), GBBG (1, Gravbar, SLRV, Chi), G-Gr4-W-H n);
    ((Grino, Hp, Wm, Neutralino n), GBBG (1, Gravbar, SLRV, Chi), G-Gr4-W-Hc n) ]

let quartic_grav_char c =
  let cc = conj_char c in
  [ ((Grino, Wm, Ga, Chargino c), GBBG (1, Gravbar, V2LR, Psi), G-Gr4-A-Ch c);
    ((Grino, Wm, Z, Chargino c), GBBG (1, Gravbar, V2LR, Psi), G-Gr4-Z-Ch c);
    ((Chargino cc, Wp, Ga, Grino), GBBG ((-1), Psibar, V2LR, Grav), G-Gr4-A-Ch cc);
    ((Chargino cc, Wp, Z, Grino), GBBG ((-1), Psibar, V2LR, Grav), G-Gr4-Z-Ch cc);
    ((Grino, Hm, Ga, Chargino c), GBBG (1, Gravbar, SLRV, Psi), G-Gr4-H-A c);
    ((Chargino cc, Hp, Ga, Grino), GBBG (1, Psibar, SLRV, Grav), G-Gr4-H-A cc);
    ((Grino, Hm, Z, Chargino c), GBBG (1, Gravbar, SLRV, Psi), G-Gr4-H-Z c);
    ((Chargino cc, Hp, Z, Grino), GBBG (1, Psibar, SLRV, Grav), G-Gr4-H-Z cc) ]

let quartic_gravitino =
  [ ((Grino, Gl, Gl, Gluino), GBBG (1, Gravbar, V2, Chi), G-GravGl) ] @
  ThoList.flatmap quartic_grav_neu [N1; N2; N3; N4] @
  ThoList.flatmap quartic_grav_char [C1; C2] @
  List.flatten (Product.list2 quartic_grav_gauge [1; 2; 3] [M1; M2]) @
  ThoList.flatmap quartic_grav_sneutrino [1; 2; 3]

let vertices3'' =
  if Flags.ckm-present then
    (ThoList.flatmap electromagnetic_currents_3 [1; 2; 3] @
     ThoList.flatmap electromagnetic_currents_2 [C1; C2] @
     List.flatten (Product.list2
                   electromagnetic_sfermion_currents [1; 2; 3] [M1; M2]) @
     ThoList.flatmap neutral_currents [1; 2; 3] @
     ThoList.flatmap neutral_sfermion_currents [1; 2; 3] @
     ThoList.flatmap charged_currents [1; 2; 3] @
     List.flatten (Product.list2 charged_slepton_currents [1; 2; 3]
                    [M1; M2]) @
     List.flatten (Product.list2 charged_quark_currents [1; 2; 3]
                    [1; 2; 3]) @
     List.flatten (Product.list2 charged_squark_currents [1; 2; 3]
                    [1; 2; 3]) @
     ThoList.flatmap yukawa_higgs_quark [(1, 3); (2, 3); (3, 3); (3, 1); (3, 2)] @
     yukawa_higgs 3 @ yukawa_n @
     ThoList.flatmap yukawa_c [C1; C2] @
     ThoList.flatmap yukawa_cq [C1; C2] @
     List.flatten (Product.list2 charged_chargino_currents [N1; N2; N3; N4]
                    [C1; C2]) @ triple_gauge @
     ThoList.flatmap neutral_Z_1 [(N1, N2); (N1, N3); (N1, N4); (N2, N3); (N2, N4);
                                   (N3, N4)] @
     ThoList.flatmap neutral_Z_2 [N1; N2; N3; N4] @
     Product.list2 charged_Z [C1; C2] [C1; C2] @
     gauge_higgs @ higgs @ yukawa_higgs_2 @

```

```

List.flatten (Product.list2 higgs_charg_neutr [N1; N2; N3; N4] [C1; C2]) @
higgs_neutr @ higgs_sneutrino @ higgs_sfermion @
higgs_squark @ yukawa_v @
ThoList.flatmap col_currents [1; 2; 3] @
List.flatten (Product.list2 col_sfermion_currents [1; 2; 3] [M1; M2]))
else
(ThoList.flatmap electromagnetic_currents_3 [1; 2; 3] @
ThoList.flatmap electromagnetic_currents_2 [C1; C2] @
List.flatten (Product.list2
electromagnetic_sfermion_currents [1; 2; 3] [M1; M2]) @
ThoList.flatmap neutral_currents [1; 2; 3] @
ThoList.flatmap neutral_sfermion_currents [1; 2; 3] @
ThoList.flatmap charged_currents [1; 2; 3] @
List.flatten (Product.list2 charged_slepton_currents [1; 2; 3]
[M1; M2]) @
charged_quark_currents 1 1 @
charged_quark_currents 2 2 @
charged_quark_currents 3 3 @
charged_squark_currents 1 1 @
charged_squark_currents 2 2 @
charged_squark_currents 3 3 @
ThoList.flatmap yukawa_higgs_quark [(3, 3)] @
yukawa_higgs 3 @ yukawa_n @
ThoList.flatmap yukawa_c [C1; C2] @
ThoList.flatmap yukawa_cq [C1; C2] @
List.flatten (Product.list2 charged_chargino_currents [N1; N2; N3; N4]
[C1; C2]) @ triple_gauge @
ThoList.flatmap neutral_Z_1 [(N1, N2); (N1, N3); (N1, N4); (N2, N3); (N2, N4);
(N3, N4)] @
ThoList.flatmap neutral_Z_2 [N1; N2; N3; N4] @
Product.list2 charged_Z [C1; C2] [C1; C2] @
gauge_higgs @ higgs @ yukawa_higgs_2 @
List.flatten (Product.list2 higgs_charg_neutr [N1; N2; N3; N4] [C1; C2]) @
higgs_neutr @ higgs_sneutrino @ higgs_sfermion @
higgs_squark @ yukawa_v @
ThoList.flatmap col_currents [1; 2; 3] @
List.flatten (Product.list2 col_sfermion_currents [1; 2; 3] [M1; M2]))

let vertices3' =
if Flags.gravitino then (vertices3'' @ triple_gravitino)
else vertices3''
let vertices3 =
if Flags.include_goldstone then
(vertices3' @ yukawa_goldstone 3 @
gauge_higgs_gold @ higgs_gold @ yukawa_goldstone_2 @
(if Flags.ckm_present then
List.flatten (Product.list2 yukawa_goldstone_quark [1; 2; 3]
[1; 2; 3]) @
List.flatten (Product.list2 goldstone_charg_neutr [N1; N2; N3; N4]
[C1; C2]))

```

```

else
  yukawa_goldstone_quark 1 1 @
  yukawa_goldstone_quark 2 2 @
  yukawa_goldstone_quark 3 3) @
  goldstone_neutr @ goldstone_sfermion @ goldstone_squark)
else vertices3'
let vertices4''' =
  (quartic_gauge @ higgs4 @ gauge_higgs4 @
   ThoList.flatmap gauge_sfermion4 [1; 2; 3] @
   gauge_squark4 @ gluon_w_squark @
   List.flatten (Product.list2 gluon2_squark2 [1; 2; 3] [M1; M2]) @
   ThoList.flatmap gluon_gauge_squark [1; 2; 3])
let vertices4'' =
  if Flags.gravitino then (vertices4''' @ quartic_gravitino)
  else vertices4'''
let vertices4' =
  if Flags.include_four then
    (vertices4'' @
     ThoList.flatmap higgs_sfermion4 [1; 2; 3] @
     ThoList.flatmap higgs_sneutrino4 [1; 2; 3] @
     List.flatten (Product.list2 higgs_squark4 [1; 2; 3] [1; 2; 3]) @
     sneutrino4 @
     List.flatten (Product.list2 sneu2_slep2_1 [1; 2; 3] [1; 2; 3]) @
     ThoList.flatmap sneu2_slep2_2 [(1, 2); (1, 3); (2, 3); (2, 1); (3, 1); (3, 2)] @
     ThoList.flatmap slepton4_1gen [1; 2; 3] @
     ThoList.flatmap slepton4_2gen [(1, 2); (1, 3); (2, 3)] @
     List.flatten (Product.list2 sneu2_squark2 [1; 2; 3] [1; 2; 3]) @
     List.flatten (Product.list2 slepton2_squark2 [1; 2; 3] [1; 2; 3]) @
     List.flatten (Product.list2 slep_sneu_squark2 [1; 2; 3] [1; 2; 3]) @
     ThoList.flatmap sup4_1gen [1; 2; 3] @
     ThoList.flatmap sup4_2gen [(1, 2); (1, 3); (2, 3)] @
     ThoList.flatmap sdown4_1gen [1; 2; 3] @
     ThoList.flatmap sdown4_2gen [(1, 2); (1, 3); (2, 3)] @
     List.flatten (Product.list2 sup2_sdown2 [1; 2; 3] [1; 2; 3]))
  else
    vertices4''
let vertices4 =
  if Flags.include_goldstone then
    (vertices4' @ higgs_gold4 @ gauge_higgs_gold4 @ goldstone4 @
     ThoList.flatmap higgs_gold_sneutrino [1; 2; 3] @
     ThoList.flatmap higgs_gold_sfermion [1; 2; 3] @
     List.flatten (Product.list2 higgs_gold_squark [1; 2; 3] [1; 2; 3]))
  else
    vertices4'
let vertices () = (vertices3, vertices4, [])
let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table

```

```

let max_degree () = 4
let flavor_of_string s =
  match s with
  | "e-" → L 1 | "e+" → L (-1)
  | "mu-" → L 2 | "mu+" → L (-2)
  | "tau-" → L 3 | "tau+" → L (-3)
  | "nue" → N 1 | "nuebar" → N (-1)
  | "numu" → N 2 | "numubar" → N (-2)
  | "nutau" → N 3 | "nutaubar" → N (-3)
  | "se1-" → Slepton (M1,1) | "se1+" → Slepton (M1,-1)
  | "smu1-" → Slepton (M1,2) | "smu1+" → Slepton (M1,-2)
  | "stau1-" → Slepton (M1,3) | "stau1+" → Slepton (M1,-3)
  | "se2-" → Slepton (M2,1) | "se2+" → Slepton (M2,-1)
  | "smu2-" → Slepton (M2,2) | "smu2+" → Slepton (M2,-2)
  | "stau2-" → Slepton (M2,3) | "stau2+" → Slepton (M2,-3)
  | "snue" → Sneutrino 1 | "snue*" → Sneutrino (-1)
  | "snumu" → Sneutrino 2 | "snumu*" → Sneutrino (-2)
  | "snutau" → Sneutrino 3 | "snutau*" → Sneutrino (-3)
  | "u" → U 1 | "ubar" → U (-1)
  | "c" → U 2 | "cbar" → U (-2)
  | "t" → U 3 | "tbar" → U (-3)
  | "d" → D 1 | "dbar" → D (-1)
  | "s" → D 2 | "sbar" → D (-2)
  | "b" → D 3 | "bbar" → D (-3)
  | "A" → Ga | "Z" | "ZO" → Z
  | "W+" → Wp | "W-" → Wm
  | "gl" | "g" → Gl
  | "H" → H_Heavy | "h" → H_Light | "A0" → A
  | "H+" → Hp | "H-" → Hm
  | "phi0" → Phi0 | "phi+" → Phip | "phim" → Phim
  | "su1" → Sup (M1,1) | "su1c" → Sup (M1,-1)
  | "sc1" → Sup (M1,2) | "sc1c" → Sup (M1,-2)
  | "st1" → Sup (M1,3) | "st1c" → Sup (M1,-3)
  | "su2" → Sup (M2,1) | "su2c" → Sup (M2,-1)
  | "sc2" → Sup (M2,2) | "sc2c" → Sup (M2,-2)
  | "st2" → Sup (M2,3) | "st2c" → Sup (M2,-3)
  | "sgl" | "sg" → Gluino
  | "sd1" → Sdown (M1,1) | "sd1c" → Sdown (M1,-1)
  | "ss1" → Sdown (M1,2) | "ss1c" → Sdown (M1,-2)
  | "sb1" → Sdown (M1,3) | "sb1c" → Sdown (M1,-3)
  | "sd2" → Sdown (M2,1) | "sd2c" → Sdown (M2,-1)
  | "ss2" → Sdown (M2,2) | "ss2c" → Sdown (M2,-2)
  | "sb2" → Sdown (M2,3) | "sb2c" → Sdown (M2,-3)
  | "neu1" → Neutralino N1 | "neu2" → Neutralino N2
  | "neu3" → Neutralino N3 | "neu4" → Neutralino N4
  | "ch1+" → Chargino C1 | "ch2+" → Chargino C2
  | "ch1-" → Chargino C1c | "ch2-" → Chargino C2c
  | "GR" → Grino
  | _ → invalid_arg "Modellib_MSSM.MSSM.flavor_of_string"

```

```

let flavor_to_string = function
| L 1 → "e-" | L (-1) → "e+"
| L 2 → "mu-" | L (-2) → "mu+"
| L 3 → "tau-" | L (-3) → "tau+"
| N 1 → "nue" | N (-1) → "nuebar"
| N 2 → "numu" | N (-2) → "numubar"
| N 3 → "nutau" | N (-3) → "nutaubar"
| U 1 → "u" | U (-1) → "ubar"
| U 2 → "c" | U (-2) → "cbar"
| U 3 → "t" | U (-3) → "tbar"
| D 1 → "d" | D (-1) → "dbar"
| D 2 → "s" | D (-2) → "sbar"
| D 3 → "b" | D (-3) → "bbar"
| L _ → invalid_arg
      "Modellib_MSSM.MSSM.flavor_to_string:␣invalid␣lepton"
| N _ → invalid_arg
      "Modellib_MSSM.MSSM.flavor_to_string:␣invalid␣neutrino"
| U _ → invalid_arg
      "Modellib_MSSM.MSSM.flavor_to_string:␣invalid␣up␣type␣quark"
| D _ → invalid_arg
      "Modellib_MSSM.MSSM.flavor_to_string:␣invalid␣down␣type␣quark"
| Gl → "gl" | Gluino → "sgl"
| Ga → "A" | Z → "Z" | Wp → "W+" | Wm → "W-"
| Phip → "phi+" | Phim → "phi-" | Phi0 → "phi0"
| H_Heavy → "H" | H_Light → "h" | A → "A0"
| Hp → "H+" | Hm → "H-"
| Slepton (M1,1) → "se1-" | Slepton (M1,-1) → "se1+"
| Slepton (M1,2) → "smu1-" | Slepton (M1,-2) → "smu1+"
| Slepton (M1,3) → "stau1-" | Slepton (M1,-3) → "stau1+"
| Slepton (M2,1) → "se2-" | Slepton (M2,-1) → "se2+"
| Slepton (M2,2) → "smu2-" | Slepton (M2,-2) → "smu2+"
| Slepton (M2,3) → "stau2-" | Slepton (M2,-3) → "stau2+"
| Sneutrino 1 → "snue" | Sneutrino (-1) → "snue*"
| Sneutrino 2 → "snumu" | Sneutrino (-2) → "snumu*"
| Sneutrino 3 → "snutau" | Sneutrino (-3) → "snutau*"
| Sup (M1,1) → "su1" | Sup (M1,-1) → "su1c"
| Sup (M1,2) → "sc1" | Sup (M1,-2) → "sc1c"
| Sup (M1,3) → "st1" | Sup (M1,-3) → "st1c"
| Sup (M2,1) → "su2" | Sup (M2,-1) → "su2c"
| Sup (M2,2) → "sc2" | Sup (M2,-2) → "sc2c"
| Sup (M2,3) → "st2" | Sup (M2,-3) → "st2c"
| Sdown (M1,1) → "sd1" | Sdown (M1,-1) → "sd1c"
| Sdown (M1,2) → "ss1" | Sdown (M1,-2) → "ss1c"
| Sdown (M1,3) → "sb1" | Sdown (M1,-3) → "sb1c"
| Sdown (M2,1) → "sd2" | Sdown (M2,-1) → "sd2c"
| Sdown (M2,2) → "ss2" | Sdown (M2,-2) → "ss2c"
| Sdown (M2,3) → "sb2" | Sdown (M2,-3) → "sb2c"
| Neutralino N1 → "neu1"
| Neutralino N2 → "neu2"
| Neutralino N3 → "neu3"

```

```

| Neutralino  $N_4 \rightarrow$  "neu4"
| Slepton  $\_ \rightarrow$  invalid_arg
|   "Modellib_MSSM.MSSM.flavor_to_string:␣invalid␣slepton"
| Sneutrino  $\_ \rightarrow$  invalid_arg
|   "Modellib_MSSM.MSSM.flavor_to_string:␣invalid␣sneutrino"
| Sup  $\_ \rightarrow$  invalid_arg
|   "Modellib_MSSM.MSSM.flavor_to_string:␣invalid␣up␣type␣squark"
| Sdown  $\_ \rightarrow$  invalid_arg
|   "Modellib_MSSM.MSSM.flavor_to_string:␣invalid␣down␣type␣squark"
| Chargino  $C1 \rightarrow$  "ch1+" | Chargino  $C1c \rightarrow$  "ch1-"
| Chargino  $C2 \rightarrow$  "ch2+" | Chargino  $C2c \rightarrow$  "ch2-"
| Grino  $\rightarrow$  "GR"

let flavor_symbol = function
| L g when g > 0  $\rightarrow$  "l" ^ string_of_int g
| L g  $\rightarrow$  "l" ^ string_of_int (abs g) ^ "b"
| N g when g > 0  $\rightarrow$  "n" ^ string_of_int g
| N g  $\rightarrow$  "n" ^ string_of_int (abs g) ^ "b"
| U g when g > 0  $\rightarrow$  "u" ^ string_of_int g
| U g  $\rightarrow$  "u" ^ string_of_int (abs g) ^ "b"
| D g when g > 0  $\rightarrow$  "d" ^ string_of_int g
| D g  $\rightarrow$  "d" ^ string_of_int (abs g) ^ "b"
| Gl  $\rightarrow$  "gl" | Ga  $\rightarrow$  "a" | Z  $\rightarrow$  "z"
| Wp  $\rightarrow$  "wp" | Wm  $\rightarrow$  "wm"
| Slepton (M1, g) when g > 0  $\rightarrow$  "sl1" ^ string_of_int g
| Slepton (M1, g)  $\rightarrow$  "sl1c" ^ string_of_int (abs g)
| Slepton (M2, g) when g > 0  $\rightarrow$  "sl2" ^ string_of_int g
| Slepton (M2, g)  $\rightarrow$  "sl2c" ^ string_of_int (abs g)
| Sneutrino g when g > 0  $\rightarrow$  "sn" ^ string_of_int g
| Sneutrino g  $\rightarrow$  "snc" ^ string_of_int (abs g)
| Sup (M1, g) when g > 0  $\rightarrow$  "su1" ^ string_of_int g
| Sup (M1, g)  $\rightarrow$  "su1c" ^ string_of_int (abs g)
| Sup (M2, g) when g > 0  $\rightarrow$  "su2" ^ string_of_int g
| Sup (M2, g)  $\rightarrow$  "su2c" ^ string_of_int (abs g)
| Sdown (M1, g) when g > 0  $\rightarrow$  "sd1" ^ string_of_int g
| Sdown (M1, g)  $\rightarrow$  "sd1c" ^ string_of_int (abs g)
| Sdown (M2, g) when g > 0  $\rightarrow$  "sd2" ^ string_of_int g
| Sdown (M2, g)  $\rightarrow$  "sd2c" ^ string_of_int (abs g)
| Neutralino n  $\rightarrow$  "neu" ^ (string_of_neu n)
| Chargino c when (int_of_char c) > 0  $\rightarrow$  "cp" ^ string_of_char c
| Chargino c  $\rightarrow$  "cm" ^ string_of_int (abs (int_of_char c))
| Gluino  $\rightarrow$  "sgl" | Phip  $\rightarrow$  "pp" | Phim  $\rightarrow$  "pm" | Phi0  $\rightarrow$  "p0"
| H_Heavy  $\rightarrow$  "h0h" | H_Light  $\rightarrow$  "h0l" | A  $\rightarrow$  "a0"
| Hp  $\rightarrow$  "hp" | Hm  $\rightarrow$  "hm" | Grino  $\rightarrow$  "gv"

let flavor_to_TeX = function
| L 1  $\rightarrow$  "e-" | L (-1)  $\rightarrow$  "e+"
| L 2  $\rightarrow$  "μ-" | L (-2)  $\rightarrow$  "μ+"
| L 3  $\rightarrow$  "τ-" | L (-3)  $\rightarrow$  "τ+"
| N 1  $\rightarrow$  "νe" | N (-1)  $\rightarrow$  "ν̄e"
| N 2  $\rightarrow$  "νμ" | N (-2)  $\rightarrow$  "ν̄μ"

```

```

|  $N\ 3 \rightarrow \backslash\backslash\mathrm{nu}\backslash\backslash\mathrm{tau}$  |  $N\ (-3) \rightarrow \backslash\backslash\mathrm{bar}\{\backslash\backslash\mathrm{nu}\}\backslash\backslash\mathrm{tau}$ 
|  $U\ 1 \rightarrow \mathrm{u}$  |  $U\ (-1) \rightarrow \backslash\backslash\mathrm{bar}\{\mathrm{u}\}$ 
|  $U\ 2 \rightarrow \mathrm{c}$  |  $U\ (-2) \rightarrow \backslash\backslash\mathrm{bar}\{\mathrm{c}\}$ 
|  $U\ 3 \rightarrow \mathrm{t}$  |  $U\ (-3) \rightarrow \backslash\backslash\mathrm{bar}\{\mathrm{t}\}$ 
|  $D\ 1 \rightarrow \mathrm{d}$  |  $D\ (-1) \rightarrow \backslash\backslash\mathrm{bar}\{\mathrm{d}\}$ 
|  $D\ 2 \rightarrow \mathrm{s}$  |  $D\ (-2) \rightarrow \backslash\backslash\mathrm{bar}\{\mathrm{s}\}$ 
|  $D\ 3 \rightarrow \mathrm{b}$  |  $D\ (-3) \rightarrow \backslash\backslash\mathrm{bar}\{\mathrm{b}\}$ 
|  $L\ _ \rightarrow \mathrm{invalid\_arg}$ 
| "Modellib_MSSM.MSSM.flavor_to_TeX:_invalid_lepton"
|  $N\ _ \rightarrow \mathrm{invalid\_arg}$ 
| "Modellib_MSSM.MSSM.flavor_to_TeX:_invalid_neutrino"
|  $U\ _ \rightarrow \mathrm{invalid\_arg}$ 
| "Modellib_MSSM.MSSM.flavor_to_TeX:_invalid_up_type_quark"
|  $D\ _ \rightarrow \mathrm{invalid\_arg}$ 
| "Modellib_MSSM.MSSM.flavor_to_TeX:_invalid_down_type_quark"
|  $Gl \rightarrow \mathrm{g}$  |  $Gluino \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{g}\}$ 
|  $Ga \rightarrow \backslash\backslash\mathrm{gamma}$  |  $Z \rightarrow \mathrm{Z}$  |  $Wp \rightarrow \mathrm{W}^+$  |  $Wm \rightarrow \mathrm{W}^-$ 
|  $Phip \rightarrow \backslash\backslash\mathrm{phi}^+$  |  $Phim \rightarrow \backslash\backslash\mathrm{phi}^-$  |  $Phi0 \rightarrow \backslash\backslash\mathrm{phi}^0$ 
|  $H\_Heavy \rightarrow \mathrm{H}^0$  |  $H\_Light \rightarrow \mathrm{h}^0$  |  $A \rightarrow \mathrm{A}^0$ 
|  $Hp \rightarrow \mathrm{H}^+$  |  $Hm \rightarrow \mathrm{H}^-$ 
|  $Slepton\ (M1,1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{e}\}_1^-$ 
|  $Slepton\ (M1,-1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{e}\}_1^+$ 
|  $Slepton\ (M1,2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{mu}\}_1^-$ 
|  $Slepton\ (M1,-2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{mu}\}_1^+$ 
|  $Slepton\ (M1,3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{tau}\}_1^-$ 
|  $Slepton\ (M1,-3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{tau}\}_1^+$ 
|  $Slepton\ (M2,1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{e}\}_2^-$ 
|  $Slepton\ (M2,-1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{e}\}_2^+$ 
|  $Slepton\ (M2,2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{mu}\}_2^-$ 
|  $Slepton\ (M2,-2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{mu}\}_2^+$ 
|  $Slepton\ (M2,3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{tau}\}_2^-$ 
|  $Slepton\ (M2,-3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{tau}\}_2^+$ 
|  $Sneutrino\ 1 \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{nu}\}\mathrm{e}$ 
|  $Sneutrino\ (-1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{nu}\}\mathrm{e}^*$ 
|  $Sneutrino\ 2 \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{nu}\}\backslash\backslash\mathrm{mu}$ 
|  $Sneutrino\ (-2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{nu}\}\backslash\backslash\mathrm{mu}^*$ 
|  $Sneutrino\ 3 \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{nu}\}\backslash\backslash\mathrm{tau}$ 
|  $Sneutrino\ (-3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\backslash\backslash\mathrm{nu}\}\backslash\backslash\mathrm{tau}^*$ 
|  $Sup\ (M1,1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{u}\}_1$ 
|  $Sup\ (M1,-1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{u}\}_1^*$ 
|  $Sup\ (M1,2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{c}\}_1$ 
|  $Sup\ (M1,-2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{c}\}_1^*$ 
|  $Sup\ (M1,3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{t}\}_1$ 
|  $Sup\ (M1,-3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{t}\}_1^*$ 
|  $Sup\ (M2,1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{u}\}_2$ 
|  $Sup\ (M2,-1) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{u}\}_2^*$ 
|  $Sup\ (M2,2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{c}\}_2$ 
|  $Sup\ (M2,-2) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{c}\}_2^*$ 
|  $Sup\ (M2,3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{t}\}_2$ 
|  $Sup\ (M2,-3) \rightarrow \backslash\backslash\mathrm{widetilde}\{\mathrm{t}\}_2^*$ 

```

```

| Sdown (M1,1) → "\\widetilde{d}_1"
| Sdown (M1,-1) → "\\widetilde{d}_1^*"
| Sdown (M1,2) → "\\widetilde{s}_1"
| Sdown (M1,-2) → "\\widetilde{s}_1^*"
| Sdown (M1,3) → "\\widetilde{b}_1"
| Sdown (M1,-3) → "\\widetilde{b}_1^*"
| Sdown (M2,1) → "\\widetilde{d}_2"
| Sdown (M2,-1) → "\\widetilde{d}_2^*"
| Sdown (M2,2) → "\\widetilde{s}_2"
| Sdown (M2,-2) → "\\widetilde{s}_2^*"
| Sdown (M2,3) → "\\widetilde{b}_2"
| Sdown (M2,-3) → "\\widetilde{b}_2^*"
| Neutralino N1 → "\\widetilde{\\chi}^0_1"
| Neutralino N2 → "\\widetilde{\\chi}^0_2"
| Neutralino N3 → "\\widetilde{\\chi}^0_3"
| Neutralino N4 → "\\widetilde{\\chi}^0_4"
| Slepton _ → invalid_arg
| "Modellib_MSSM.MSSM.flavor_to_TeX:_invalid_slepton"
| Sneutrino _ → invalid_arg
| "Modellib_MSSM.MSSM.flavor_to_TeX:_invalid_sneutrino"
| Sup _ → invalid_arg
| "Modellib_MSSM.MSSM.flavor_to_TeX:_invalid_up_type_squark"
| Sdown _ → invalid_arg
| "Modellib_MSSM.MSSM.flavor_to_TeX:_invalid_down_type_squark"
| Chargino C1 → "\\widetilde{\\chi}_1^+"
| Chargino C1c → "\\widetilde{\\chi}_1^-"
| Chargino C2 → "\\widetilde{\\chi}_2^+"
| Chargino C2c → "\\widetilde{\\chi}_2^-"
| Grino → "\\widetilde{G}"

let pdg = function
| L g when g > 0 → 9 + 2 × g
| L g → - 9 + 2 × g
| N g when g > 0 → 10 + 2 × g
| N g → - 10 + 2 × g
| U g when g > 0 → 2 × g
| U g → 2 × g
| D g when g > 0 → - 1 + 2 × g
| D g → 1 + 2 × g
| Gl → 21 | Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| H_Light → 25 | H_Heavy → 35 | A → 36
| Hp → 37 | Hm → (-37)
| Phip | Phim → 27 | Phi0 → 26
| Slepton (M1,g) when g > 0 → 1000009 + 2 × g
| Slepton (M1,g) → - 1000009 + 2 × g
| Slepton (M2,g) when g > 0 → 2000009 + 2 × g
| Slepton (M2,g) → - 2000009 + 2 × g
| Sneutrino g when g > 0 → 1000010 + 2 × g
| Sneutrino g → - 1000010 + 2 × g

```

```

| Sup (M1, g) when g > 0 → 1000000 + 2 × g
| Sup (M1, g) → - 1000000 + 2 × g
| Sup (M2, g) when g > 0 → 2000000 + 2 × g
| Sup (M2, g) → - 2000000 + 2 × g
| Sdown (M1, g) when g > 0 → 999999 + 2 × g
| Sdown (M1, g) → - 999999 + 2 × g
| Sdown (M2, g) when g > 0 → 1999999 + 2 × g
| Sdown (M2, g) → - 1999999 + 2 × g
| Gluino → 1000021
| Grino → 1000039
| Chargino C1 → 1000024 | Chargino C1c → (-1000024)
| Chargino C2 → 1000037 | Chargino C2c → (-1000037)
| Neutralino N1 → 1000022 | Neutralino N2 → 1000023
| Neutralino N3 → 1000025 | Neutralino N4 → 1000035

```

We must take care of the pdg numbers for the two different kinds of sfermions in the MSSM. The particle data group in its Monte Carlo particle numbering scheme takes only into account mixtures of the third generation squarks and the stau. For the other sfermions we will use the number of the lefthanded field for the lighter mixed state and the one for the righthanded for the heavier. Below are the official pdg numbers from the Particle Data Group. In order not to produce arrays with some million entries in the Fortran code for the masses and the widths we introduce our private pdg numbering scheme which only extends not too far beyond 42. Our private scheme then has the following pdf numbers (for the sparticles the subscripts *L/R* and *1/2* are taken synonymously):

d	down-quark	1
u	up-quark	2
s	strange-quark	3
c	charm-quark	4
b	bottom-quark	5
t	top-quark	6
e^-	electron	11
ν_e	electron-neutrino	12
μ^-	muon	13
ν_μ	muon-neutrino	14
τ^-	tau	15
ν_τ	tau-neutrino	16
g	gluon	(9) 21
γ	photon	22
Z^0	Z-boson	23
W^+	W-boson	24
h^0	light Higgs boson	25
H^0	heavy Higgs boson	35
A^0	pseudoscalar Higgs	36
H^\pm	charged Higgs	37
$\tilde{\psi}_\mu$	gravitino	39
\tilde{d}_L	down-squark 1	41
\tilde{u}_L	up-squark 1	42
\tilde{s}_L	strange-squark 1	43
\tilde{c}_L	charm-squark 1	44
\tilde{b}_L	bottom-squark 1	45
\tilde{t}_L	top-squark 1	46
\tilde{d}_R	down-squark 2	47
\tilde{u}_R	up-squark 2	48
\tilde{s}_R	strange-squark 2	49
\tilde{c}_R	charm-squark 2	50
\tilde{b}_R	bottom-squark 2	51
\tilde{t}_R	top-squark 2	52
\tilde{e}_L	selectron 1	53
$\tilde{\nu}_{e,L}$	electron-sneutrino	54
$\tilde{\mu}_L$	smuon 1	55
$\tilde{\nu}_{\mu,L}$	muon-sneutrino	56
$\tilde{\tau}_L$	stau 1	57
$\tilde{\nu}_{\tau,L}$	tau-sneutrino	58
\tilde{e}_R	selectron 2	59
$\tilde{\mu}_R$	smuon 2	61
$\tilde{\tau}_R$	stau 2	471 63
\tilde{g}	gluino	64
$\tilde{\chi}_1^0$	neutralino 1	65
$\tilde{\chi}_2^0$	neutralino 2	66
$\tilde{\chi}_3^0$	neutralino 3	67
$\tilde{\chi}_4^0$	neutralino 4	68
$\tilde{\chi}_1^\pm$	chargino 1	69

```

let pdg_mw = function
| L g when g > 0 → 9 + 2 × g
| L g → - 9 + 2 × g
| N g when g > 0 → 10 + 2 × g
| N g → - 10 + 2 × g
| U g when g > 0 → 2 × g
| U g → 2 × g
| D g when g > 0 → - 1 + 2 × g
| D g → 1 + 2 × g
| Gl → 21 | Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| H_Light → 25 | H_Heavy → 35 | A → 36
| Hp → 37 | Hm → (-37)
| Phip | Phim → 27 | Phi0 → 26
| Sup (M1, g) when g > 0 → 40 + 2 × g
| Sup (M1, g) → - 40 + 2 × g
| Sup (M2, g) when g > 0 → 46 + 2 × g
| Sup (M2, g) → - 46 + 2 × g
| Sdown (M1, g) when g > 0 → 39 + 2 × g
| Sdown (M1, g) → - 39 + 2 × g
| Sdown (M2, g) when g > 0 → 45 + 2 × g
| Sdown (M2, g) → - 45 + 2 × g
| Slepton (M1, g) when g > 0 → 51 + 2 × g
| Slepton (M1, g) → - 51 + 2 × g
| Slepton (M2, g) when g > 0 → 57 + 2 × g
| Slepton (M2, g) → - 57 + 2 × g
| Sneutrino g when g > 0 → 52 + 2 × g
| Sneutrino g → - 52 + 2 × g
| Grino → 39
| Gluino → 64
| Chargino C1 → 69 | Chargino C1c → (-69)
| Chargino C2 → 70 | Chargino C2c → (-70)
| Neutralino N1 → 65 | Neutralino N2 → 66
| Neutralino N3 → 67 | Neutralino N4 → 68

let mass_symbol f =
"mass(" ^ string_of_int (abs (pdg_mw f)) ^ ")"

let width_symbol f =
"width(" ^ string_of_int (abs (pdg_mw f)) ^ ")"

let conj_symbol = function
| false, str → str
| true, str → str ^ "_c"

let constant_symbol = function
| Unit → "unit" | Pi → "PI"
| Alpha_QED → "alpha" | E → "e" | G → "g" | Vev → "vev"
| Sin2thw → "sin2thw" | Eidelta → "eidelta" | Mu → "mu" |
G_Z → "gz"
| Sin a → "sin" ^ string_of_angle a | Cos a → "cos" ^ string_of_angle a

```

```

| Sin2am2b → "sin2am2b" | Cos2am2b → "cos2am2b" | Sinamb →
"sinamb"
| Sinapb → "sinapb" | Cosamb → "cosamb" | Cosapb → "cosapb"
| Cos4be → "cos4be" | Sin4be → "sin4be" | Sin4al → "sin4al"
| Sin2al → "sin2al" | Cos2al → "cos2al" | Sin2be → "sin2be"
| Cos2be → "cos2be" | Tana → "tana" | Tanb → "tanb"
| Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdown"
| Q_charg → "qchar"
| V_CKM (g1, g2) → "vckm_" ^ string_of_int g1 ^ string_of_int g2
| M_SF (f, g, m1, m2) → "mix_" ^ string_of_sff f ^ string_of_int g
^ string_of_sfm m1 ^ string_of_sfm m2
| AL g → "al_" ^ string_of_int g
| AD g → "ad_" ^ string_of_int g
| AU g → "au_" ^ string_of_int g
| A_0 (n1, n2) → "a0_" ^ string_of_neu n1 ^ string_of_neu n2
| A_P (c1, c2) → "ap_" ^ string_of_char c1 ^ string_of_char c2
| V_0 (n1, n2) → "v0_" ^ string_of_neu n1 ^ string_of_neu n2
| V_P (c1, c2) → "vp_" ^ string_of_char c1 ^ string_of_char c2
| M_N (n1, n2) → "mn_" ^ string_of_neu n1 ^ string_of_neu n2
| M_U (c1, c2) → "mu_" ^ string_of_char c1 ^ string_of_char c2
| M_V (c1, c2) → "mv_" ^ string_of_char c1 ^ string_of_char c2
| L_NC (n, c) → "lnc_" ^ string_of_neu n ^ string_of_char c
| R_NC (n, c) → "rnc_" ^ string_of_neu n ^ string_of_char c
| L_CN (c, n) → "lcn_" ^ string_of_char c ^ string_of_neu n
| R_CN (c, n) → "rcn_" ^ string_of_char c ^ string_of_neu n
| L_NCH (n, c) → "lnch_" ^ string_of_neu n ^ string_of_char c
| R_NCH (n, c) → "rnch_" ^ string_of_neu n ^ string_of_char c
| L_CNG (c, n) → "lcng_" ^ string_of_char c ^ string_of_neu n
| R_CNG (c, n) → "rcng_" ^ string_of_char c ^ string_of_neu n
| S_NNA (n1, n2) → "snna_" ^ string_of_neu n1 ^ string_of_neu n2
| P_NNA (n1, n2) → "pnna_" ^ string_of_neu n1 ^ string_of_neu n2
| S_NNG (n1, n2) → "snng_" ^ string_of_neu n1 ^ string_of_neu n2
| P_NNG (n1, n2) → "pnng_" ^ string_of_neu n1 ^ string_of_neu n2
| S_NNH1 (n1, n2) → "snnh1_" ^ string_of_neu n1 ^ string_of_neu n2
| P_NNH1 (n1, n2) → "pnnh1_" ^ string_of_neu n1 ^ string_of_neu n2
| S_NNH2 (n1, n2) → "snnh2_" ^ string_of_neu n1 ^ string_of_neu n2
| P_NNH2 (n1, n2) → "pnnh2_" ^ string_of_neu n1 ^ string_of_neu n2
| G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
| G_NC_up → "gncup" | G_NC_down → "gncdown"
| G_CC → "gcc"
| G_CCQ (vc, g1, g2) → conj_symbol (vc, "gccq_" ^ string_of_int g1 ^ "-"
^ string_of_int g2)
| I_Q_W → "iqw" | I_G_ZWW → "igzww"
| G_WWWW → "gw4" | G_ZZWW → "gzzww"
| G_PZWW → "gpzww" | G_PPWW → "gppww"
| G_GH 1 → "ghaw"
| G_GH 2 → "gh1az" | G_GH 3 → "gh2az"
| G_GH 4 → "gh1ww" | G_GH 5 → "gh2ww"
| G_GH 6 → "ghh1w" | G_GH 7 → "ghh2w"
| G_GH 8 → "gh1zz" | G_GH 9 → "gh2zz"

```

```

| G_GH 10 → "ghhz" | G_GH 11 → "ghhp"
| G_GH _ → failwith "this_G_GH_coupling_is_not_available"
| G_GLGLH → "gglglh" | G_GLGLHH → "gglglhh"
| G_GLGLA → "gglgla" | G_PPH → "gpph"
| G_PPHH → "gpphh" | G_PPA → "gppa"
| G_GHGo n → "g_hgh(" ^ string_of_int n ^ ")"
| G_GH4 1 → "gaazz" | G_GH4 2 → "gh1h1zz" | G_GH4 3 →
"gh2h2zz"
| G_GH4 4 → "ghphmzz" | G_GH4 5 → "ghphmpp" | G_GH4 6 →
"ghphpz"
| G_GH4 7 → "ghh1wz" | G_GH4 8 → "ghh2wz"
| G_GH4 9 → "ghh1wp" | G_GH4 10 → "ghh2wp"
| G_GH4 11 → "gaaww" | G_GH4 12 → "gh1h1ww" | G_GH4 13 →
"gh2h2ww"
| G_GH4 14 → "ghhww" | G_GH4 15 → "ghawz" | G_GH4 16 →
"ghawp"
| G_GH4 _ → failwith "this_G_GH4_coupling_is_not_available"
| G_CICIH1 (n1,n2) → "gcicih1-" ^ string_of_neu n1 ^ "-"
^ string_of_neu n2
| G_CICIH2 (n1,n2) → "gcicih2-" ^ string_of_neu n1 ^ "-"
^ string_of_neu n2
| G_CICIA (n1,n2) → "gcicia-" ^ string_of_neu n1 ^ "-"
^ string_of_neu n2
| G_CICIG (n1,n2) → "gcicig-" ^ string_of_neu n1 ^ "-"
^ string_of_neu n2
| G_H3 n → "gh3-" ^ string_of_int n
| G_H4 n → "gh4-" ^ string_of_int n
| G_HGo3 n → "ghg3-" ^ string_of_int n
| G_HGo4 n → "ghg4-" ^ string_of_int n
| G_GG4 n → "ggg4-" ^ string_of_int n
| G_strong → "gs" | G_SS → "gs**2"
| Gs → "gs"
| I_G_S → "igs"
| G_S_Sqrt → "gssq"
| G_NWC (n,c) → "gnwc-" ^ string_of_neu n ^ "-" ^ string_of_char c
| G_CWN (c,n) → "gcwn-" ^ string_of_char c ^ "-" ^ string_of_neu n
| G_CH1C (c1,c2) → "gch1c-" ^ string_of_char c1 ^ "-" ^ string_of_char c2
| G_CH2C (c1,c2) → "gch2c-" ^ string_of_char c1 ^ "-" ^ string_of_char c2
| G_CAC (c1,c2) → "gcac-" ^ string_of_char c1 ^ "-" ^ string_of_char c2
| G_CGC (c1,c2) → "gcgc-" ^ string_of_char c1 ^ "-" ^ string_of_char c2
| G_YUK (i,g) → "g-yuk" ^ string_of_int i ^ "-" ^ string_of_int g
| G_NZN (n1,n2) → "gnzn-" ^ string_of_neu n1 ^ "-" ^ string_of_neu n2
| G_CZC (c1,c2) → "gczc-" ^ string_of_char c1 ^ "-" ^ string_of_char
c2
| G_YUK_1 (n,m) → "g-yuk1-" ^ string_of_int n ^ "-" ^ string_of_int m
| G_YUK_2 (n,m) → "g-yuk2-" ^ string_of_int n ^ "-" ^ string_of_int m
| G_YUK_3 (n,m) → "g-yuk3-" ^ string_of_int n ^ "-" ^ string_of_int m
| G_YUK_4 (n,m) → "g-yuk4-" ^ string_of_int n ^ "-" ^ string_of_int m
| G_YUK_C (vc,g,c,sf,m) → conj_symbol (vc, "g-yuk_ch" ^ string_of_char c
^ "-" ^ string_of_sff sf ^ string_of_sfm m ^ "-" ^ string_of_int g )

```

```

| G_YUK_N (vc, g, n, sf, m) → conj_symbol (vc, "g-yuk-n" ^ string_of_neu n
    ^ "-" ^ string_of_sff sf ^ string_of_sfm m ^ "-" ^ string_of_int g)
| G_YUK_G (vc, g, sf, m) → conj_symbol (vc, "g-yuk-g" ^ string_of_sff sf
    ^ string_of_sfm m ^ "-" ^ string_of_int g)
| G_YUK_Q (vc, g1, g2, c, sf, m) → conj_symbol (vc, "g-yuk-ch" ^ string_of_char c
    ^ "-" ^ string_of_sff sf ^ string_of_sfm m ^ "-" ^ string_of_int g1
    ^ "-" ^ string_of_int g2)
| G_NHC (n, c) → "g-nhc-" ^ string_of_neu n ^ "-" ^ string_of_char c
| G_CHN (c, n) → "g-chn-" ^ string_of_neu n ^ "-" ^ string_of_char c
| G_NGC (n, c) → "g-ngc-" ^ string_of_neu n ^ string_of_char c
| G_CGN (c, n) → "g-cgn-" ^ string_of_char c ^ string_of_neu n
| SUM_1 → "sum1"
| G_SLSNW (vc, g, m) → conj_symbol (vc, "gs1" ^ string_of_sfm m ^ "-"
    ^ string_of_int g ^ "snw")
| G_ZSF (f, g, m1, m2) → "g" ^ string_of_sff f ^ string_of_sfm m1 ^ "z"
    ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_WWSFSF (f, g, m1, m2) → "gww" ^ string_of_sff f ^ string_of_sfm m1
    ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_WPSLSN (vc, g, m) → conj_symbol (vc, "gpws1" ^ string_of_sfm m
    ^ "sn-" ^ string_of_int g)
| G_WZSLSN (vc, g, m) → conj_symbol (vc, "gwzs1" ^ string_of_sfm m
    ^ "sn-" ^ string_of_int g)
| G_H1SFSF (f, g, m1, m2) → "gh1" ^ string_of_sff f ^ string_of_sfm m1
    ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_H2SFSF (f, g, m1, m2) → "gh2" ^ string_of_sff f ^ string_of_sfm m1
    ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_ASFSF (f, g, m1, m2) → "ga" ^ string_of_sff f ^ string_of_sfm m1
    ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_HSNSL (vc, g, m) → conj_symbol (vc, "ghsns1" ^ string_of_sfm m ^ "-"
    ^ string_of_int g)
| G_GoSFSF (f, g, m1, m2) → "ggo" ^ string_of_sff f ^ string_of_sfm m1
    ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_GoSNSL (vc, g, m) → conj_symbol (vc, "ggosns1" ^ string_of_sfm m ^ "-"
    ^ string_of_int g)
| G_HSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "ghsu" ^ string_of_sfm m1
    ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1 ^ "-"
    ^ string_of_int g2)
| G_GSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "ggsu" ^ string_of_sfm m1
    ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1 ^ "-"
    ^ string_of_int g2)
| G_WPSUSD (vc, m1, m2, n, m) → conj_symbol (vc, "gpwpsu" ^ string_of_sfm m1
    ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int n ^ "-"
    ^ string_of_int m)
| G_WZSUSD (vc, m1, m2, n, m) → conj_symbol (vc, "gzwpsu" ^ string_of_sfm m1
    ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int n ^ "-"
    ^ string_of_int m)
| G_SWS (vc, g1, g2, m1, m2) → conj_symbol (vc, "gs" ^ string_of_sfm m1 ^ "ws"
    ^ string_of_sfm m2 ^ "-" ^ string_of_int g1 ^ "-" ^ string_of_int g2)
| G_GlGlSqsQ → "gglglsqsq"
| G_PPSFSF f → "gpp" ^ string_of_sff f ^ string_of_sff f

```

```

| G_ZZSF (f, g, m1, m2) → "gzz" ^ string_of_sff f ^ string_of_sfm m1
  ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_ZPSF (f, g, m1, m2) → "gzp" ^ string_of_sff f ^ string_of_sfm m1
  ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_GLPSQSQ → "gg1psqsq"
| G_GLZSF (f, g, m1, m2) → "gg1" ^ string_of_sff f ^ string_of_sfm m1
  ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int g
| G_GLWSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "gg1wsu"
  ^ string_of_sfm m1 ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1
  ^ "-" ^ string_of_int g2)
| G_GHGo4 1 → "gzzg0g0" | G_GHGo4 2 → "gzzgpgm"
| G_GHGo4 3 → "gppgpgm" | G_GHGo4 4 → "gzpgpgm"
| G_GHGo4 5 → "gwwgpgm" | G_GHGo4 6 → "gwwg0g0"
| G_GHGo4 7 → "gwzg0g" | G_GHGo4 8 → "gwzg0g"
| G_GHGo4 9 → "gwzh1g" | G_GHGo4 10 → "gwzh2g"
| G_GHGo4 11 → "gwph1g" | G_GHGo4 12 → "gwph2g"
| G_GHGo4 _ → failwith "Coupling_G_GHGo4_is_not_available"
| G_HSF31 (h, g, m1, m2, f1, f2) → "g-" ^ string_of_higgs h ^
  string_of_int g ^ string_of_sfm m1 ^ string_of_sfm m2 ^
  string_of_sff f1 ^ string_of_sff f2
| G_HSF32 (h, g1, g2, m1, m2, f1, f2) → "g-" ^ string_of_higgs h ^
  string_of_int g1 ^ "-" ^ string_of_int g2 ^ string_of_sfm m1 ^
  string_of_sfm m2 ^ string_of_sff f1 ^ string_of_sff f2
| G_HSF41 (h, g, m1, m2, f1, f2) → "g-" ^ string_of_higgs h ^
  string_of_int g ^ string_of_sfm m1 ^ string_of_sfm m2 ^
  string_of_sff f1 ^ string_of_sff f2
| G_HSF42 (h, g1, g2, m1, m2, f1, f2) → "g-" ^ string_of_higgs h ^
  string_of_int g1 ^ "-" ^ string_of_int g2 ^ string_of_sfm m1 ^
  string_of_sfm m2 ^ string_of_sff f1 ^ string_of_sff f2
| G_H1H1SFSF (f, m1, m2, n) → "gh1h1" ^ string_of_sff f ^ string_of_sfm
  m1 ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_H1H2SFSF (f, m1, m2, n) → "gh1h2" ^ string_of_sff f ^ string_of_sfm
  m1 ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_H2H2SFSF (f, m1, m2, n) → "gh2h2" ^ string_of_sff f ^ string_of_sfm
  m1 ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_HHSFSF (f, m1, m2, n) → "ghh" ^ string_of_sff f ^ string_of_sfm m1
  ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_AASF (f, m1, m2, n) → "gaa" ^ string_of_sff f ^ string_of_sfm m1
  ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_HH1SUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "ghh1su"
  ^ string_of_sfm m1 ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1
  ^ "-" ^ string_of_int g2)
| G_HH2SUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "ghh2su"
  ^ string_of_sfm m1 ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1
  ^ "-" ^ string_of_int g2)
| G_HASUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "ghasu"
  ^ string_of_sfm m1 ^ "sd" ^ string_of_sfm m2 ^ "-"
  ^ string_of_int g1 ^ "-" ^ string_of_int g2 ^ "-c")
| G_HH1SLN (vc, m, g) → conj_symbol (vc, "ghh1sl" ^ string_of_sfm m
  ^ "sn-" ^ string_of_int g)

```

```

| G_HH2SLSN (vc, m, g) → conj_symbol (vc, "ghh2s1" ^ string_of_sfm m
                                         ^ "sn_" ^ string_of_int g)
| G_HASLSN (vc, m, g) → conj_symbol (vc, "ghas1" ^ string_of_sfm m
                                         ^ "sn_" ^ string_of_int g)
| G_AG0SFSF (f, m1, m2, n) → "gag0" ^ string_of_sff f ^ string_of_sfm m1
                               ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_HGSFSF (f, m1, m2, n) → "ghg" ^ string_of_sff f ^ string_of_sfm m1
                              ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_GGSFSF (f, m1, m2, n) → "ggg" ^ string_of_sff f ^ string_of_sfm m1
                              ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_G0G0SFSF (f, m1, m2, n) → "gg0g0" ^ string_of_sff f ^ string_of_sfm m1
                                ^ string_of_sff f ^ string_of_sfm m2 ^ "-" ^ string_of_int n
| G_HGSNSL (vc, m, n) → conj_symbol (vc, "ghgsns1" ^ string_of_sfm m ^ "-"
                                         ^ string_of_int n)
| G_H1GSNSL (vc, m, n) → conj_symbol (vc, "gh1gsns1" ^ string_of_sfm m ^ "-"
                                         ^ string_of_int n)
| G_H2GSNSL (vc, m, n) → conj_symbol (vc, "gh2gsns1" ^ string_of_sfm m ^ "-"
                                         ^ string_of_int n)
| G_AGSNSL (vc, m, n) → conj_symbol (vc, "gagsns1" ^ string_of_sfm m ^ "-"
                                         ^ string_of_int n)
| G_GGSNSL (vc, m, n) → conj_symbol (vc, "gggsns1" ^ string_of_sfm m ^ "-"
                                         ^ string_of_int n)
| G_HGSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "gghpsu" ^ string_of_sfm m1
                                                  ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1 ^ "-"
                                                  ^ string_of_int g2)
| G_H1GSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "gh1gpsu" ^ string_of_sfm m1
                                                  ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1 ^ "-"
                                                  ^ string_of_int g2)
| G_H2GSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "gh2gpsu" ^ string_of_sfm m1
                                                  ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1 ^ "-"
                                                  ^ string_of_int g2)
| G_AGSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "gagpsu" ^ string_of_sfm m1
                                                  ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1 ^ "-"
                                                  ^ string_of_int g2)
| G_GGSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "gggpsu" ^ string_of_sfm m1
                                                  ^ "sd" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1 ^ "-"
                                                  ^ string_of_int g2)
| G_SN4 (g1, g2) → "gsn4_" ^ string_of_int g1 ^ "-" ^ string_of_int g2
| G_SN2SL2_1 (m1, m2, g1, g2) → "gs1_" ^ string_of_int g1 ^ "_s1_"
                                ^ string_of_int g1 ^ "_s1" ^ string_of_sfm m1 ^ "-" ^ string_of_int g2
                                ^ "_s1" ^ string_of_sfm m2 ^ "-" ^ string_of_int g2
| G_SN2SL2_2 (m1, m2, g1, g2) → "gs1_" ^ string_of_int g1 ^ "_s1_"
                                ^ string_of_int g2 ^ "_s1" ^ string_of_sfm m1 ^ "-" ^ string_of_int g1
                                ^ "_s1" ^ string_of_sfm m2 ^ "-" ^ string_of_int g2 ^ "_mix"
| G_SF4 (f1, f2, m1, m2, m3, m4, g1, g2) → "gsf" ^ string_of_sff f1 ^
string_of_sff f2 ^ string_of_sfm m1 ^ string_of_sfm m2 ^
string_of_sfm m3 ^ string_of_sfm m4 ^ string_of_int g1 ^
string_of_int g2
| G_SF4_3 (f1, f2, m1, m2, m3, m4, g1, g2, g3) → "gsf" ^ string_of_sff f1 ^
string_of_sff f2 ^ string_of_sfm m1 ^ string_of_sfm m2 ^

```



```

      string_of_sfm m3 ^ string_of_sfm m4 ^ string_of_int g1 ^
      string_of_int g2 ^ "-" ^ string_of_int g3
| G_SF4_4 (f1, f2, m1, m2, m3, m4, g1, g2, g3, g4) → "gsf" ^ string_of_sff f1 ^
      string_of_sff f2 ^ string_of_sfm m1 ^ string_of_sfm m2 ^
      string_of_sfm m3 ^ string_of_sfm m4 ^ string_of_int g1 ^ "-" ^
      string_of_int g2 ^ string_of_int g3 ^ "-" ^ string_of_int g4
| G_SL4 (m1, m2, m3, m4, g) → "gsl" ^ string_of_sfm m1 ^ "-"
      ^ "s1" ^ string_of_sfm m2 ^ "-" ^ "s1" ^ string_of_sfm m3 ^ "-"
      ^ "s1" ^ string_of_sfm m4 ^ "-" ^ string_of_int g
| G_SL4_2 (m1, m2, m3, m4, g1, g2) → "gsl" ^ string_of_sfm m1 ^ "-"
      ^ "s1" ^ string_of_sfm m2 ^ "-" ^ "s1" ^ string_of_sfm m3 ^ "-"
      ^ "s1" ^ string_of_sfm m4 ^ "-" ^ string_of_int g1 ^ "-" ^
      string_of_int g2
| G_SN2SQ2 (f, m1, m2, g1, g2) → "gsn-" ^ string_of_int g1 ^ "-sn-"
      ^ string_of_int g1 ^ "-" ^ string_of_sff f ^ string_of_sfm m1 ^ "-"
      ^ string_of_int g2 ^ "-" ^ string_of_sff f ^ string_of_sfm m2 ^ "-"
      ^ string_of_int g2
| G_SL2SQ2 (f, m1, m2, m3, m4, g1, g2) → "gsl" ^ string_of_sfm m1 ^ "-"
      ^ string_of_int g1 ^ "-s1" ^ string_of_sfm m2 ^ "-" ^ string_of_int g1
      ^ "-" ^ string_of_sff f ^ string_of_sfm m3 ^ "-" ^ string_of_int g2
      ^ "-" ^ string_of_sff f ^ string_of_sfm m4 ^ "-" ^ string_of_int g2
| G_SUSDSNSL (vc, m1, m2, m3, g1, g2, g3) → conj_symbol (vc, "gsl"
      ^ string_of_sfm m3 ^ "-" ^ string_of_int g3 ^ "-sn-" ^ string_of_int g3
      ^ "_su" ^ string_of_sfm m1 ^ "-" ^ string_of_int g1 ^ "-sd"
      ^ string_of_sfm m2 ^ "-" ^ string_of_int g2)
| G_SU4 (m1, m2, m3, m4, g) → "gsu" ^ string_of_sfm m1 ^ "-"
      ^ "_su" ^ string_of_sfm m2 ^ "-" ^ "_su" ^ string_of_sfm m3 ^ "-" ^
      "_su" ^ string_of_sfm m4 ^ "-" ^ string_of_int g
| G_SU4_2 (m1, m2, m3, m4, g1, g2) → "gsu" ^ string_of_sfm m1 ^ "-"
      ^ "_su" ^ string_of_sfm m2 ^ "-" ^ "_su" ^ string_of_sfm m3 ^ "-" ^
      "_su" ^ string_of_sfm m4 ^ "-" ^ string_of_int g1 ^ "-" ^
      string_of_int g2
| G_SD4 (m1, m2, m3, m4, g) → "gsd" ^ string_of_sfm m1 ^ "-"
      ^ "_sd" ^ string_of_sfm m2 ^ "-" ^ "_sd" ^ string_of_sfm m3 ^ "-"
      ^ "_sd" ^ string_of_sfm m4 ^ "-" ^ string_of_int g
| G_SD4_2 (m1, m2, m3, m4, g1, g2) → "gsd" ^ string_of_sfm m1 ^ "-"
      ^ "_sd" ^ string_of_sfm m2 ^ "-" ^ "_sd" ^ string_of_sfm m3 ^ "-"
      ^ "_sd" ^ string_of_sfm m4 ^ "-" ^ string_of_int g1 ^ "-" ^
      string_of_int g2
| G_SU2SD2 (m1, m2, m3, m4, g1, g2, g3, g4) → "gsu" ^ string_of_sfm m1
      ^ "-" ^ string_of_int g1 ^ "-su" ^ string_of_sfm m2 ^ "-"
      ^ string_of_int g2 ^ "-sd" ^ string_of_sfm m3 ^ "-" ^ string_of_int g3
      ^ "-sd" ^ string_of_sfm m4 ^ "-" ^ string_of_int g4
| M f → "mass" ^ flavor_symbol f
| W f → "width" ^ flavor_symbol f
| G_Grav → "ggrav" | G_Gr_Ch C1 → "ggrch1" | G_Gr_Ch C2 →
"ggrch2"
| G_Gr_Ch C1c → "ggrch1c" | G_Gr_Ch C2c → "ggrch2c"
| G_Gr_Z_Neu n → "ggrzneu" ^ string_of_neu n
| G_Gr_A_Neu n → "ggraneu" ^ string_of_neu n

```

```

| G_Gr4_Neu n → "ggr4neu" ^ string_of_neu n
| G_Gr4_A_Ch C1 → "ggr4ach1" | G_Gr4_A_Ch C2 → "ggr4ach2"
| G_Gr4_A_Ch C1c → "ggr4ach1c" | G_Gr4_A_Ch C2c →
"ggr4ach2c"
| G_Gr4_Z_Ch C1 → "ggr4zch1" | G_Gr4_Z_Ch C2 → "ggr4zch2"
| G_Gr4_Z_Ch C1c → "ggr4zch1c" | G_Gr4_Z_Ch C2c →
"ggr4zch2c"
| G_Grav_N → "ggravn"
| G_GravGl → "gs□*□ggrav"
| G_Grav_L (g, m) → "ggravl" ^ string_of_int g ^ string_of_sfm m
| G_Grav_Lc (g, m) → "ggravl" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Grav_U (g, m) → "ggravu" ^ string_of_int g ^ string_of_sfm m
| G_Grav_Uc (g, m) → "ggravu" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Grav_D (g, m) → "ggravd" ^ string_of_int g ^ string_of_sfm m
| G_Grav_Dc (g, m) → "ggravd" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr_H_Ch C1 → "ggrhch1" | G_Gr_H_Ch C2 → "ggrhch2"
| G_Gr_H_Ch C1c → "ggrhch1c" | G_Gr_H_Ch C2c → "ggrhch2c"
| G_Gr_H1_Neu n → "ggrh1neu" ^ string_of_neu n
| G_Gr_H2_Neu n → "ggrh2neu" ^ string_of_neu n
| G_Gr_H3_Neu n → "ggrh3neu" ^ string_of_neu n
| G_Gr4A_Sl (g, m) → "ggr4asl" ^ string_of_int g ^ string_of_sfm m
| G_Gr4A_Slc (g, m) → "ggr4asl" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4A_Su (g, m) → "ggr4asu" ^ string_of_int g ^ string_of_sfm m
| G_Gr4A_Suc (g, m) → "ggr4asu" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4A_Sd (g, m) → "ggr4asd" ^ string_of_int g ^ string_of_sfm m
| G_Gr4A_Sdc (g, m) → "ggr4asd" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4Z_Sn → "ggr4zsn" | G_Gr4Z_Snc → "ggr4zsnc"
| G_Gr4Z_Sl (g, m) → "ggr4zsl" ^ string_of_int g ^ string_of_sfm m
| G_Gr4Z_Slc (g, m) → "ggr4zsl" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4Z_Su (g, m) → "ggr4zsu" ^ string_of_int g ^ string_of_sfm m
| G_Gr4Z_Suc (g, m) → "ggr4zsu" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4Z_Sd (g, m) → "ggr4zsd" ^ string_of_int g ^ string_of_sfm m
| G_Gr4Z_Sdc (g, m) → "ggr4zsd" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4W_Sl (g, m) → "ggr4ws1" ^ string_of_int g ^ string_of_sfm m
| G_Gr4W_Slc (g, m) → "ggr4ws1" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4W_Su (g, m) → "ggr4wsu" ^ string_of_int g ^ string_of_sfm m
| G_Gr4W_Suc (g, m) → "ggr4wsu" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4W_Sd (g, m) → "ggr4wsd" ^ string_of_int g ^ string_of_sfm m
| G_Gr4W_Sdc (g, m) → "ggr4wsd" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4Gl_Su (g, m) → "ggr4glsu" ^ string_of_int g ^ string_of_sfm m
| G_Gr4Gl_Suc (g, m) → "ggr4glsu" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4Gl_Sd (g, m) → "ggr4glsd" ^ string_of_int g ^ string_of_sfm m
| G_Gr4Gl_Sdc (g, m) → "ggr4glsd" ^ string_of_int g ^ string_of_sfm m ^ "c"
| G_Gr4_Z_H1 n → "ggr4zh1-" ^ string_of_neu n
| G_Gr4_Z_H2 n → "ggr4zh2-" ^ string_of_neu n
| G_Gr4_Z_H3 n → "ggr4zh3-" ^ string_of_neu n
| G_Gr4_W_H n → "ggr4wh-" ^ string_of_neu n
| G_Gr4_W_Hc n → "ggr4whc-" ^ string_of_neu n
| G_Gr4_H_A C1 → "ggr4ha1" | G_Gr4_H_A C2 → "ggr4ha2"
| G_Gr4_H_A C1c → "ggr4ha1c" | G_Gr4_H_A C2c → "ggr4ha2c"

```

```

| G_Gr4_H_Z C1 → "ggr4hz1" | G_Gr4_H_Z C2 → "ggr4hz2"
| G_Gr4_H_Z C1c → "ggr4hz1c" | G_Gr4_H_Z C2c → "ggr4hz2c"
| G_Gr4_W_Sn → "ggr4wsn"
| G_Gr4_W_Snc → "ggr4wsnc"
end

```

13.9 Interface of *Modellib_NMSSM*

13.9.1 Extended Supersymmetric Models

We do not introduce the possibility here of using four point couplings or not. We simply add the relevant and leave the rest out. No possibility for Goldstone bosons is given. But we allow for CKM mixing.

```

module type NMSSM_flags =
sig
  val ckm_present : bool
  val higgs_triangle : bool (* Hγγ, Hgγ and Hggcouplings*)
end

module NMSSM : NMSSM_flags
module NMSSM_CKM : NMSSM_flags
module NMSSM_Hgg : NMSSM_flags
module NMSSM_func : functor (F : NMSSM_flags) → Model.T with mod-
ule Ch = Charges.QQ

```

13.10 Implementation of *Modellib_NMSSM*

```

let rcs_file = RCS.parse "Modellib_NMSSM" ["NMSSM"]
{ RCS.revision = "$Revision: 4538$";
  RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
  RCS.author = "$Author: jr_reuter$";
  RCS.source
    = "$URL: svn+ssh://jr_reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg

```

13.10.1 Next-to-Minimal Supersymmetric Standard Model

This is based on the NMSSM implementation by Felix Braam. Note that for the Higgs sector vertices the conventions of the Franke/Fraas paper have been used.

```

module type NMSSM_flags =
sig
  val ckm_present : bool
  val higgs_triangle : bool
end

module NMSSM : NMSSM_flags =
struct

```

```

    let ckm_present = false
    let higgs_triangle = false
  end

module NMSSM_CKM : NMSSM_flags =
  struct
    let ckm_present = true
    let higgs_triangle = false
  end

module NMSSM_Hgg : NMSSM_flags =
  struct
    let ckm_present = false
    let higgs_triangle = true
  end

module NMSSM_func (Flags : NMSSM_flags) =
  struct
    let rcs = RCS.rename rcs_file "Modellib_NMSSM.NMSSM"
      [ "NMSSM" ]

    open Coupling

    let default_width = ref Timelike
    let use_fudged_width = ref false

    let options = Options.create
      [ "constant_width", Arg.Unit (fun () → default_width := Constant),
        "use_constant_width_also_in_t-channel";
        "fudged_width", Arg.Set use_fudged_width,
        "use_fudge_factor_for_charge_particle_width";
        "custom_width", Arg.String (fun f → default_width := Custom f),
        "use_custom_width";
        "cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
        "use_vanishing_width" ]
  end

```

Yields a list of tuples consistig of the off-diag combinations of the elements in "set".

```

let choose2 set =
  List.map (function [x; y] → (x, y) | _ → failwith "choose2")
    (Combinatorics.choose 2 set)

```

pairs appends the diagonal combinations to *choose2*.

```

let rec diag = function
  | [] → []
  | x1 :: rest → (x1, x1) :: diag rest

```

```

let pairs l = choose2 l @ diag l

```

```

let rec cloop set i j k =
  if i > ((List.length set) - 1) then []
  else if j > i then cloop set (succ i) (j - i - 1) (j - i - 1)
  else if k > j then cloop set i (succ j) (k - j - 1)
  else (List.nth set i, List.nth set j, List.nth set k) :: cloop set i j (succ k)

```

```

let triples set = cloop set 0 0 0

let rec two_and_one' l1 z n =
  if n < 0 then []
  else
    ((fst (List.nth (pairs l1) n)), (snd (List.nth (pairs l1) n)), z) :: two_and_one' l1 z (pred n)

let two_and_one l1 l2 =
  let f z = two_and_one' l1 z ((List.length (pairs l1)) - 1)
  in
    List.flatten ( List.map f l2 )

type gen =
  | G of int | GG of gen × gen

let rec string_of_gen = function
  | G n when n > 0 → string_of_int n
  | G n → string_of_int (abs n) ^ "c"
  | GG (g1, g2) → string_of_gen g1 ^ "-" ^ string_of_gen g2

```

With this we distinguish the flavour.

```

type sff =
  | SL | SN | SU | SD

let string_of_sff = function
  | SL → "s1" | SN → "sn" | SU → "su" | SD → "sd"

```

With this we distinguish the mass eigenstates. At the moment we have to cheat a little bit for the sneutrinos. Because we are dealing with massless neutrinos there is only one sort of sneutrino.

```

type sfm =
  | M1 | M2

let string_of_sfm = function
  | M1 → "1" | M2 → "2"

```

We also introduce special types for the charginos and neutralinos.

```

type char =
  | C1 | C2 | C1c | C2c

type neu =
  | N1 | N2 | N3 | N4 | N5

let int_of_char = function
  | C1 → 1 | C2 → 2 | C1c → -1 | C2c → -2

let string_of_char = function
  | C1 → "1" | C2 → "2" | C1c → "-1" | C2c → "-2"

let conj_char = function
  | C1 → C1c | C2 → C2c | C1c → C1 | C2c → C2

let string_of_neu = function
  | N1 → "1" | N2 → "2" | N3 → "3" | N4 → "4" | N5 → "5"

```

For the Higgs bosons, we follow the conventions of Franke/Fraas.

```

type shiggs =
  | S1 | S2 | S3

type phiggs =
  | P1 | P2

let string_of_shiggs = function
  | S1 → "1" | S2 → "2" | S3 → "3"

let string_of_phiggs = function
  | P1 → "1" | P2 → "2"

type flavor =
  | L of int | N of int
  | U of int | D of int
  | Sup of sfm × int | Sdown of sfm × int
  | Ga | Wp | Wm | Z | Gl
  | Slepton of sfm × int | Sneutrino of int
  | Neutralino of neu | Chargino of char
  | Gluino
  | SHiggs of shiggs | Hp | Hm | PHiggs of phiggs

let string_of_fermion_type = function
  | L _ → "l" | U _ → "u" | D _ → "d" | N _ → "n"
  | _ → failwith "Modellib_NMSSM.NMSSM.string_of_fermion_type:␣invalid␣fermion␣type"

let string_of_fermion_gen = function
  | L g | U g | D g | N g → string_of_int (abs (g))
  | _ → failwith "Modellib_NMSSM.NMSSM.string_of_fermion_gen:␣invalid␣fermion␣type"

type gauge = unit

let gauge_symbol () =
  failwith "Modellib_NMSSM.NMSSM.gauge_symbol:␣internal␣error"

```

At this point we will forget graviton and -ino.

```

let family g = [ L g; N g; Slepton (M1, g);
                 Slepton (M2, g); Sneutrino g;
                 U g; D g; Sup (M1, g); Sup (M2, g);
                 Sdown (M1, g); Sdown (M2, g)]

let external_flavors () =
  [ "1st␣Generation␣matter", ThoList.flatmap family [1; -1];
    "2nd␣Generation␣matter", ThoList.flatmap family [2; -2];
    "3rd␣Generation␣matter", ThoList.flatmap family [3; -3];
    "Gauge␣Bosons", [Ga; Z; Wp; Wm; Gl];
    "Charginos", [Chargino C1; Chargino C2; Chargino C1c; Chargino C2c];
    "Neutralinos", [Neutralino N1; Neutralino N2; Neutralino N3;
                    Neutralino N4; Neutralino N5];
    "Higgs␣Bosons", [SHiggs S1; SHiggs S2; SHiggs S3; Hp; Hm; PHiggs P1; PHiggs P2];
    "Gluino", [Gluino]]

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n m =
  if n ≥ 0 ∧ m ≥ 0 then

```

```

    Spinor
  else if
     $n \leq 0 \wedge m \leq 0$  then
      ConjSpinor
    else
      invalid_arg "Modellib_NMSSM.NMSSM.spinor:␣internal␣error"

let lorentz = function
| L g → spinor g 0 | N g → spinor g 0
| U g → spinor g 0 | D g → spinor g 0
| Chargino c → spinor (int_of_char c) 0
| Ga | Gl → Vector
| Wp | Wm | Z → Massive_Vector
| SHiggs _ | PHiggs _ | Hp | Hm
| Sup _ | Sdown _ | Slepton _ | Sneutrino _ → Scalar
| Neutralino _ | Gluino → Majorana

let color = function
| U g → Color.SUN (if g > 0 then 3 else -3)
| Sup (m, g) → Color.SUN (if g > 0 then 3 else -3)
| D g → Color.SUN (if g > 0 then 3 else -3)
| Sdown (m, g) → Color.SUN (if g > 0 then 3 else -3)
| Gl | Gluino → Color.AdjSUN 3
| _ → Color.Singlet

let prop_spinor n m =
  if  $n \geq 0 \wedge m \geq 0$  then
    Prop_Spinor
  else if
     $n \leq 0 \wedge m \leq 0$  then
      Prop_ConjSpinor
    else
      invalid_arg "Modellib_NMSSM.NMSSM.prop_spinor:␣internal␣error"

let propagator = function
| L g → prop_spinor g 0 | N g → prop_spinor g 0
| U g → prop_spinor g 0 | D g → prop_spinor g 0
| Chargino c → prop_spinor (int_of_char c) 0
| Ga | Gl → Prop_Feynman
| Wp | Wm | Z → Prop_Unitarity
| SHiggs _ | PHiggs _ → Prop_Scalar
| Hp | Hm → Prop_Scalar
| Sup _ | Sdown _ | Slepton _ | Sneutrino _ → Prop_Scalar
| Gluino → Prop_Majorana
| Neutralino _ → Prop_Majorana

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    | Wp | Wm | U 3 | U (-3) → Fudged

```

```

    | _ → !default_width
  else
    !default_width
let goldstone _ = None
let conjugate = function
| L g → L (-g) | N g → N (-g)
| U g → U (-g) | D g → D (-g)
| Sup (m, g) → Sup (m, -g)
| Sdown (m, g) → Sdown (m, -g)
| Slepton (m, g) → Slepton (m, -g)
| Sneutrino g → Sneutrino (-g)
| Gl → Gl | Ga → Ga | Z → Z
| Wp → Wm | Wm → Wp
| SHiggs s → SHiggs s
| PHiggs p → PHiggs p
| Hp → Hm | Hm → Hp
| Gluino → Gluino
| Neutralino n → Neutralino n | Chargino c → Chargino (conj_char c)
let fermion = function
| L g → if g > 0 then 1 else -1
| N g → if g > 0 then 1 else -1
| U g → if g > 0 then 1 else -1
| D g → if g > 0 then 1 else -1
| Gl | Ga | Z | Wp | Wm → 0
| SHiggs _ | Hp | Hm | PHiggs _ → 0
| Neutralino _ → 2
| Chargino c → if (int_of_char c) > 0 then 1 else -1
| Sup _ → 0 | Sdown _ → 0
| Slepton _ → 0 | Sneutrino _ → 0
| Gluino → 2
module Ch = Charges.QQ
let ( // ) = Algebra.Small_Rational.make
let generation' = function
| 1 → [ 1//1; 0//1; 0//1]
| 2 → [ 0//1; 1//1; 0//1]
| 3 → [ 0//1; 0//1; 1//1]
| -1 → [-1//1; 0//1; 0//1]
| -2 → [ 0//1; -1//1; 0//1]
| -3 → [ 0//1; 0//1; -1//1]
| n → invalid_arg ("NMSSM.generation':␣" ^ string_of_int n)
let generation f =
  if Flags.ckm_present then
    []
  else
    match f with
    | L n | N n | U n | D n | Sup (_, n)
    | Sdown (_, n) | Slepton (_, n)

```



```

| Sneutrino n → generation' n
| - → [0//1; 0//1; 0//1]

let charge = function
| L n → if n > 0 then -1//1 else 1//1
| Slepton (_, n) → if n > 0 then -1//1 else 1//1
| N n → 0//1
| Sneutrino n → 0//1
| U n → if n > 0 then 2//3 else -2//3
| Sup (_, n) → if n > 0 then 2//3 else -2//3
| D n → if n > 0 then -1//3 else 1//3
| Sdown (_, n) → if n > 0 then -1//3 else 1//3
| Gl | Ga | Z | Neutralino - | Gluino → 0//1
| Wp → 1//1
| Wm → -1//1
| SHiggs - | PHiggs - → 0//1
| Hp → 1//1
| Hm → -1//1
| Chargino (C1 | C2) → 1//1
| Chargino (C1c | C2c) → -1//1

let lepton = function
| L n | N n → if n > 0 then 1//1 else -1//1
| Slepton (_, n)
| Sneutrino n → if n > 0 then 1//1 else -1//1
| - → 0//1

let baryon = function
| U n | D n → if n > 0 then 1//1 else -1//1
| Sup (_, n) | Sdown (_, n) → if n > 0 then 1//1 else -1//1
| - → 0//1

let charges f =
[ charge f; lepton f; baryon f ] @ generation f

```

We introduce a Boolean type *vc* as a pseudonym for Vertex Conjugator to distinguish between vertices containing complex mixing matrices like the CKM-matrix or the sfermion or neutralino/chargino-mixing matrices, which have to become complex conjugated. The true-option stands for the conjugated vertex, the false-option for the unconjugated vertex.

```

type vc = bool

type constant =
| E | G
| Mu (*lambda*sj*) | Lambda
| Q_lepton | Q_up | Q_down | Q_charg
| G_Z | G_CC | G_CCQ of vc × int × int
| G_NC_neutrino | G_NC_lepton | G_NC_up | G_NC_down
| I_Q_W | I_G_ZWW | G_WWWW | G_ZZWW | G_PZWW |
G_PPWW
| G_SS | I_G_S | Gs
| G_NZN of neu × neu | G_CZC of char × char
| G_YUK_FFS of flavor × flavor × shiggs

```

```

| G_YUK_FFP of flavor × flavor × phiggs
| G_YUK_LCN of int
| G_YUK_UCD of int × int | G_YUK_DCU of int × int
| G_NHC of vc × neu × char
| G_YUK_C of vc × flavor × char × sff × sfm
| G_YUK_Q of vc × int × flavor × char × sff × sfm
| G_YUK_N of vc × flavor × neu × sff × sfm
| G_YUK_G of vc × flavor × sff × sfm
| G_NWC of neu × char | G_CWN of char × neu
| G_CSC of char × char × shiggs
| G_CPC of char × char × phiggs
| G_WSQ of vc × int × int × sfm × sfm
| G_SLSNW of vc × int × sfm
| G_ZSF of sff × int × sfm × sfm
| G_CICIS of neu × neu × shiggs
| G_CICIP of neu × neu × phiggs
| G_GH_WPC of phiggs | G_GH_WSC of shiggs
| G_GH_ZSP of shiggs × phiggs | G_GH_WWS of shiggs
| G_GH_ZZS of shiggs | G_GH_ZCC
| G_GH_GaCC
| G_GH4_ZZPP of phiggs × phiggs
| G_GH4_ZZSS of shiggs × shiggs
| G_GH4_ZZCC | G_GH4_GaGaCC
| G_GH4_ZGaCC | G_GH4_WWCC
| G_GH4_WWPP of phiggs × phiggs
| G_GH4_WWSS of shiggs × shiggs
| G_GH4_ZWSC of shiggs
| G_GH4_GaWSC of shiggs
| G_GH4_ZWPC of phiggs
| G_GH4_GaWPC of phiggs
| G_WWSFSF of sff × int × sfm × sfm
| G_WPSLSN of vc × int × sfm
| G_H3_SCC of shiggs
| G_H3_SSS of shiggs × shiggs × shiggs
| G_H3_SPP of shiggs × phiggs × phiggs
| G_SFSFS of shiggs × sff × int × sfm × sfm
| G_SFSFP of phiggs × sff × int × sfm × sfm
| G_HSNSL of vc × int × sfm
| G_HSUSD of vc × sfm × sfm × int × int
| G_WPSUSD of vc × sfm × sfm × int × int
| G_WZSUSD of vc × sfm × sfm × int × int
| G_WZSLSN of vc × int × sfm | G_GlGlSQSQ
| G_PPSFSF of sff
| G_ZZSFSF of sff × int × sfm × sfm | G_ZPSFSF of sff × int × sfm × sfm
| G_GlZSFSF of sff × int × sfm × sfm | G_GlPSQSQ
| G_GlWSUSD of vc × sfm × sfm × int × int
| G_GLUGLUA0 of phiggs | G_GLUGLUH0 of shiggs

```

Two integer counters for the QCD and EW order of the couplings.

type *orders* = *int* × *int*

```
let orders = function
| - → (0,0)
```

$$\alpha_{\text{QED}} = \frac{1}{137.0359895} \quad (13.66a)$$

$$\sin^2 \theta_w = 0.23124 \quad (13.66b)$$

Here we must perhaps allow for complex input parameters. So split them into their modulus and their phase. At first, we leave them real; the generalization to complex parameters is obvious.

```
let parameters () =
{ input = [];
  derived = [];
  derived_arrays = [] }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)
```

For the couplings there are generally two possibilities concerning the sign of the covariant derivative.

$$D^\pm = \partial_\mu \pm ig T^a A_\mu^a \quad (13.67)$$

The particle data group defines the signs consistently to be positive. Since the convention for that signs also influence the phase definitions of the gaugino/higgsino fields via the off-diagonal entries in their mass matrices it would be the best to adopt that convention.

** REVISED: Compatible with CD+. FB **

```
let electromagnetic_currents_3 g =
[ ((L (-g), Ga, L g), FBF (1, Psibar, V, Psi), Q_lepton);
  ((U (-g), Ga, U g), FBF (1, Psibar, V, Psi), Q_up);
  ((D (-g), Ga, D g), FBF (1, Psibar, V, Psi), Q_down)]
```

** REVISED: Compatible with CD+. FB**

```
let electromagnetic_sfermion_currents g m =
[ ((Ga, Slepton (m, -g), Slepton (m, g)), Vector_Scalar_Scalar 1, Q_lepton);
  ((Ga, Sup (m, -g), Sup (m, g)), Vector_Scalar_Scalar 1, Q_up);
  ((Ga, Sdown (m, -g), Sdown (m, g)), Vector_Scalar_Scalar 1, Q_down)]
```

** REVISED: Compatible with CD+. FB**

```
let electromagnetic_currents_2 c =
let cc = conj_char c in
[ ((Chargino cc, Ga, Chargino c), FBF (1, Psibar, V, Psi), Q_charg)]
```

** REVISED: Compatible with CD+. FB**

```
let neutral_currents g =
[ ((L (-g), Z, L g), FBF (1, Psibar, VA, Psi), G_NC_lepton);
```

```

((N (-g), Z, N g), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
((U (-g), Z, U g), FBF (1, Psibar, VA, Psi), G_NC_up);
((D (-g), Z, D g), FBF (1, Psibar, VA, Psi), G_NC_down)]

```

$$\mathcal{L}_{CC} = \mp \frac{g}{2\sqrt{2}} \sum_i \bar{\psi}_i \gamma^\mu (1 - \gamma_5) (T^+ W_\mu^+ + T^- W_\mu^-) \psi_i, \quad (13.68)$$

where the sign corresponds to CD_\pm , respectively.

** REVISED: Compatible with CD_+ . **

Remark: The definition with the other sign compared to the SM files comes from the fact that $g_{cc} = 1/(2\sqrt{2})$ is used overwhelmingly often in the SUSY Feynman rules, so that JR decided to use a different definition for g_{cc} in SM and MSSM.

* FB *

```

let charged_currents g =
  [ ((L (-g), Wm, N g), FBF ((-1), Psibar, VL, Psi), G_CC);
    ((N (-g), Wp, L g), FBF ((-1), Psibar, VL, Psi), G_CC) ]

```

The quark with the inverted generation (the antiparticle) is the outgoing one, the other the incoming. The vertex attached to the outgoing up-quark contains the CKM matrix element *not* complex conjugated, while the vertex with the outgoing down-quark has the conjugated CKM matrix element.

** REVISED: Compatible with CD_+ . FB **

```

let charged_quark_currents g h =
  [ ((D (-g), Wm, U h), FBF ((-1), Psibar, VL, Psi), G_CCQ (true,g,h));
    ((U (-g), Wp, D h), FBF ((-1), Psibar, VL, Psi), G_CCQ (false,h,g))]

```

** REVISED: Compatible with CD_+ . FB **

```

let charged_chargino_currents n c =
  let cc = conj_char c in
  [ ((Chargino cc, Wp, Neutralino n),
      FBF (1, Psibar, VLR, Chi), G_CWN (c,n));
    ((Neutralino n, Wm, Chargino c),
      FBF (1, Chibar, VLR, Psi), G_NWC (n,c)) ]

```

** REVISED: Compatible with CD_+ . FB**

```

let charged_slepton_currents g m =
  [ ((Wm, Slepton (m, -g), Sneutrino g), Vector_Scalar_Scalar (-1), G_SLSNW
      (true,g,m));
    ((Wp, Slepton (m, g), Sneutrino (-g)), Vector_Scalar_Scalar 1, G_SLSNW
      (false,g,m)) ]

```

** REVISED: Compatible with CD_+ . FB**

```

let charged_squark_currents' g h m1 m2 =
  [ ((Wm, Sup (m1, g), Sdown (m2, -h)), Vector_Scalar_Scalar (-1), G_WSQ
      (true,g,h,m1,m2));
    ((Wp, Sup (m1, -g), Sdown (m2, h)), Vector_Scalar_Scalar 1, G_WSQ
      (false,g,h,m1,m2)) ]
let charged_squark_currents g h =
  List.flatten (Product.list2 (charged_squark_currents' g h) [M1; M2] [M1; M2])

```

** REVISED: Compatible with CD+. FB **

```

let neutral_sfermion_currents' g m1 m2 =
  [ ((Z, Slepton (m1, -g), Slepton (m2, g)), Vector_Scalar_Scalar (-1),
      G_ZSF (SL, g, m1, m2));
    ((Z, Sup (m1, -g), Sup (m2, g)), Vector_Scalar_Scalar (-1),
      G_ZSF (SU, g, m1, m2));
    ((Z, Sdown (m1, -g), Sdown (m2, g)), Vector_Scalar_Scalar (-1),
      G_ZSF (SD, g, m1, m2))]
let neutral_sfermion_currents g =
  List.flatten (Product.list2 (neutral_sfermion_currents'
    g) [M1; M2] [M1; M2]) @
  [ ((Z, Sneutrino (-g), Sneutrino g), Vector_Scalar_Scalar (-1),
      G_ZSF (SN, g, M1, M1)) ]

```

** REVISED: Compatible with CD+. FB**

```

let neutral_Z (n, m) =
  [ ((Neutralino n, Z, Neutralino m), FBF (1, Chibar, VLR, Chi),
      (G_NZN (n, m))) ]

```

** REVISED: Compatible with CD+. FB**

```

let charged_Z c1 c2 =
  let cc1 = conj_char c1 in
  ((Chargino cc1, Z, Chargino c2), FBF ((-1), Psibar, VA, Psi),
    G_CZC (c1, c2))

```

** REVISED: Compatible with CD+. Remark: This is pure octet. FB**

```

let yukawa_v =
  [ (Gluino, Gl, Gluino), FBF (1, Chibar, V, Chi), Gs]

```

** REVISED: Independent of the sign of CD. **

** REVISED: Felix Braam: Compact version using new COMBOS + FF-Couplings

```

let yukawa_higgs_FFS f s =
  [ ((conjugate f, SHiggs s, f), FBF (1, Psibar, S, Psi),
      G_YUK_FFS (conjugate f, f, s))]
let yukawa_higgs_FFP f p =
  [ ((conjugate f, PHiggs p, f), FBF (1, Psibar, P, Psi),
      G_YUK_FFP (conjugate f, f, p))]
let yukawa_higgs_NLC g =
  [ ((N (-g), Hp, L g), FBF (1, Psibar, Coupling.SR, Psi), G_YUK_LCN g);
    ((L (-g), Hm, N g), FBF (1, Psibar, Coupling.SL, Psi), G_YUK_LCN g)]
let yukawa_higgs g =
  yukawa_higgs_NLC g @
  List.flatten (Product.list2 yukawa_higgs_FFS [L g; U g; D g] [S1; S2; S3]) @
  List.flatten (Product.list2 yukawa_higgs_FFP [L g; U g; D g] [P1; P2])

```

** REVISED: Independent of the sign of CD. FB**

```

let yukawa_higgs_quark (g, h) =
  [ ((U (-g), Hp, D h), FBF (1, Psibar, SLR, Psi), G_YUK_UCD (g, h));

```

$((D(-h), Hm, U g), FBF(1, Psibar, SLR, Psi), G_YUK_DCU(g, h))]$

** REVISED: Compatible with CD+. **

** REVISED: Felix Braam: Compact version using new COMBOS

```
let yukawa_shiggs_2 c1 c2 s =
  let cc1 = conj_char c1 in
    ((Chargino cc1, SHiggs s, Chargino c2), FBF(1, Psibar, SLR, Psi),
     G_CSC(c1, c2, s))
```

```
let yukawa_phiggs_2 c1 c2 p =
  let cc1 = conj_char c1 in
    ((Chargino cc1, PHiggs p, Chargino c2), FBF(1, Psibar, SLR, Psi),
     G_CPC(c1, c2, p))
```

```
let yukawa_higgs_2 =
  Product.list3 yukawa_shiggs_2 [C1; C2] [C1; C2] [S1; S2; S3] @
  Product.list3 yukawa_phiggs_2 [C1; C2] [C1; C2] [P1; P2]
```

** REVISED: Compatible with CD+.FB **

```
let higgs_charg_neutr n c =
  let cc = conj_char c in
    [ ((Neutralino n, Hm, Chargino c), FBF(-1, Chibar, SLR, Psi),
       G_NHC(false, n, c));
      ((Chargino cc, Hp, Neutralino n), FBF(-1, Psibar, SLR, Chi),
       G_NHC(true, n, c)) ]
```

** REVISED: Compatible with CD+. **

** REVISED: Felix Braam: Compact version using new COMBOS

```
let shiggs_neutr (n, m, s) =
  ((Neutralino n, SHiggs s, Neutralino m), FBF(1, Chibar, SLR, Chi),
   G_CICIS(n, m, s))
let phiggs_neutr (n, m, p) =
  ((Neutralino n, PHiggs p, Neutralino m), FBF(1, Chibar, SLR, Chi),
   G_CICIP(n, m, p))
```

```
let higgs_neutr =
  List.map shiggs_neutr (two_and_one [N1; N2; N3; N4; N5] [S1; S2; S3]) @
  List.map phiggs_neutr (two_and_one [N1; N2; N3; N4; N5] [P1; P2])
```

** REVISED: Compatible with CD+. FB**

```
let yukawa_n_2 n m g =
  [ ((Neutralino n, Slepton (m, -g), L g), FBF(1, Chibar, SLR, Psi),
     G_YUK_N(true, L g, n, SL, m));
    ((L(-g), Slepton (m, g), Neutralino n), FBF(1, Psibar, SLR, Chi),
     G_YUK_N(false, L g, n, SL, m));
    ((Neutralino n, Sup (m, -g), U g), FBF(1, Chibar, SLR, Psi),
     G_YUK_N(true, U g, n, SU, m));
    ((U(-g), Sup (m, g), Neutralino n), FBF(1, Psibar, SLR, Chi),
     G_YUK_N(false, U g, n, SU, m));
    ((Neutralino n, Sdown (m, -g), D g), FBF(1, Chibar, SLR, Psi),
     G_YUK_N(true, D g, n, SD, m));
    ((D(-g), Sdown (m, g), Neutralino n), FBF(1, Psibar, SLR, Chi),
```

```

      G_YUK_N (false,D g, n, SD, m)) ]
let yukawa_n_3 n g =
  [ ((Neutralino n, Sneutrino (-g), N g), FBF (1, Chibar, SLR, Psi),
      G_YUK_N (true,N g, n, SN, M1));
    ((N (-g), Sneutrino g, Neutralino n), FBF (1, Psibar, SLR, Chi),
      G_YUK_N (false,N g, n, SN, M1)) ]
let yukawa_n_5 g m =
  [ ((U (-g), Sup (m, g), Gluino), FBF (1, Psibar, SLR, Chi),
      G_YUK_G (false,U g, SU, m));
    ((D (-g), Sdown (m, g), Gluino), FBF (1, Psibar, SLR, Chi),
      G_YUK_G (false,D g, SD, m));
    ((Gluino, Sup (m, -g), U g), FBF (1, Chibar, SLR, Psi),
      G_YUK_G (true,U g, SU, m));
    ((Gluino, Sdown (m, -g), D g), FBF (1, Chibar, SLR, Psi),
      G_YUK_G (true,D g, SD, m))]
let yukawa_n =
  List.flatten (Product.list3 yukawa_n_2 [N1; N2; N3; N4; N5] [M1; M2] [1; 2; 3]) @
  List.flatten (Product.list2 yukawa_n_3 [N1; N2; N3; N4; N5] [1; 2; 3]) @
  List.flatten (Product.list2 yukawa_n_5 [1; 2; 3] [M1; M2])

** REVISED: Compatible with CD+.FB **

let yukawa_c_2 c g =
  let cc = conj_char c in
  [ ((L (-g), Sneutrino g, Chargino cc), BBB (1, Psibar, SLR,
      Psibar), G_YUK_C (true,L g, c, SN, M1));
    ((Chargino c, Sneutrino (-g), L g), PBP (1, Psi, SLR, Psi),
      G_YUK_C (false,L g, c, SN, M1)) ]
let yukawa_c_3 c m g =
  let cc = conj_char c in
  [ ((N (-g), Slepton (m, g), Chargino c), FBF (1, Psibar, SLR,
      Psi), G_YUK_C (true,N g, c, SL, m));
    ((Chargino cc, Slepton (m, -g), N g), FBF (1, Psibar, SLR,
      Psi), G_YUK_C (false,N g, c, SL, m)) ]
let yukawa_c c =
  ThoList.flatmap (yukawa_c_2 c) [1; 2; 3] @
  List.flatten (Product.list2 (yukawa_c_3 c) [M1; M2] [1; 2; 3])

** REVISED: Compatible with CD+. FB**

let yukawa_cq' c (g, h) m =
  let cc = conj_char c in
  [ ((Chargino c, Sup (m, -g), D h), PBP (1, Psi, SLR, Psi),
      G_YUK_Q (false,g, D h, c, SU, m));
    ((D (-h), Sup (m, g), Chargino cc), BBB (1, Psibar, SLR, Psibar),
      G_YUK_Q (true,g, D h, c, SU, m));
    ((Chargino cc, Sdown (m, -g), U h), FBF (1, Psibar, SLR, Psi),
      G_YUK_Q (true,g, U h, c, SD, m));
    ((U (-h), Sdown (m, g), Chargino c), FBF (1, Psibar, SLR, Psi),
      G_YUK_Q (false,g, U h, c, SD, m)) ]
let yukawa_cq c =
  if Flags.ckm_present then

```

```

      List.flatten (Product.list2 (yukawa_cq' c) [(1, 1); (1, 2); (2, 1); (2, 2); (1, 3); (2, 3); (3, 3); (3, 2); (3, 1)] [M
else
      List.flatten (Product.list2 (yukawa_cq' c) [(1, 1); (2, 2); (3, 3)] [M1; M2])

** REVISÉD: Compatible with CD+. Remark: Singlet and octet gluon ex-
change. The coupling is divided by sqrt(2) to account for the correct normal-
ization of the Lie algebra generators. **FB

let col_currents g =
  [ ((D (-g), Gl, D g), FBF ((-1), Psibar, V, Psi), Gs);
    ((U (-g), Gl, U g), FBF ((-1), Psibar, V, Psi), Gs)]

** REVISÉD: Compatible with CD+. Remark: Singlet and octet gluon ex-
change. The coupling is divided by sqrt(2) to account for the correct normal-
ization of the Lie algebra generators. **FB

let chg = function
  | M1 → M2 | M2 → M1

let col_sfermion_currents g m =
  [ ((Gl, Sup (m, -g), Sup (m, g)), Vector_Scalar_Scalar (-1), Gs);
    ((Gl, Sdown (m, -g), Sdown (m, g)), Vector_Scalar_Scalar (-1), Gs)]

** REVISÉD: Compatible with CD+. **FB

let triple_gauge =
  [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
    ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW);
    ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_G_S)]

** REVISÉD: Independent of the sign of CD. **FB

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let quartic_gauge =
  [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;
    (Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
    (Wm, Z, Wp, Ga), minus_gauge4, G_PZWW;
    (Wm, Ga, Wp, Ga), minus_gauge4, G_PPWW;
    (Gl, Gl, Gl, Gl), gauge4, G_SS]

The Scalar_Vector_Vector couplings do not depend on the choice of the sign of
the covariant derivative since they are quadratic in the gauge couplings.
* Effective Higgs-Gluon-Gluon coupling. *

let gauge_higgs_GlGlS s =
  ((SHiggs s, Gl, Gl), Dim5_Scalar_Gauge2 1, G_GLUGLUH0 s)
let gauge_higgs_GlGlP p =
  ((PHiggs p, Gl, Gl), Dim5_Scalar_Gauge2_Skew 1, G_GLUGLUA0 p)

** REVISÉD: Compatible with CD+. FB**
** Revision: 2005-03-10: first two vertices corrected. **
** REVISÉD: Compact version using new COMBOS
** REVISÉD: Couplings adjusted to FF-convention

let gauge_higgs_WPC p =
  [ ((Wm, Hp, PHiggs p), Vector_Scalar_Scalar 1, G_GH_WPC p);

```

```

      ((Wp, Hm, PHiggs p), Vector_Scalar_Scalar 1, G_GH_WPC p)]
let gauge_higgs_WSC s =
  [((Wm, Hp, SHiggs s), Vector_Scalar_Scalar 1, G_GH_WSC s);
   ((Wp, Hm, SHiggs s), Vector_Scalar_Scalar (-1), G_GH_WSC s)]
let gauge_higgs_ZSP s p =
  [((Z, SHiggs s, PHiggs p), Vector_Scalar_Scalar 1, G_GH_ZSP (s, p))]
let gauge_higgs_WWS s =
  ((SHiggs s, Wp, Wm), Scalar_Vector_Vector 1, G_GH_WWS s)
let gauge_higgs_ZZS s =
  ((SHiggs s, Z, Z), Scalar_Vector_Vector 1, G_GH_ZZS s)
let gauge_higgs_ZCC =
  ((Z, Hp, Hm), Vector_Scalar_Scalar 1, G_GH_ZCC )
let gauge_higgs_GaCC =
  ((Ga, Hp, Hm), Vector_Scalar_Scalar 1, G_GH_GaCC )

let gauge_higgs =
  ThoList.flatmap gauge_higgs_WPC [P1; P2] @
  ThoList.flatmap gauge_higgs_WSC [S1; S2; S3] @
  List.flatten (Product.list2 gauge_higgs_ZSP [S1; S2; S3] [P1; P2]) @
  List.map gauge_higgs_WWS [S1; S2; S3] @
  List.map gauge_higgs_ZZS [S1; S2; S3] @
  [gauge_higgs_ZCC] @ [gauge_higgs_GaCC] @
  (if Flags.higgs_triangle then
    List.map gauge_higgs_GIGIS [S1; S2; S3] @
    List.map gauge_higgs_GIGIP [P1; P2]
  else
    [])

** REVISED: Compact version using new COMBOS
** REVISED: Couplings adjusted to FF-convention

let gauge_higgs4_ZZPP (p1, p2) =
  ((PHiggs p1, PHiggs p2, Z, Z), Scalar2_Vector2 1, G_GH4_ZZPP (p1, p2))

let gauge_higgs4_ZZSS (s1, s2) =
  ((SHiggs s1, SHiggs s2, Z, Z), Scalar2_Vector2 1, G_GH4_ZZSS (s1, s2))

let gauge_higgs4_ZZCC =
  ((Hp, Hm, Z, Z), Scalar2_Vector2 1, G_GH4_ZZCC)

let gauge_higgs4_GaGaCC =
  ((Hp, Hm, Ga, Ga), Scalar2_Vector2 1, G_GH4_GaGaCC)

let gauge_higgs4_ZGaCC =
  ((Hp, Hm, Ga, Z), Scalar2_Vector2 1, G_GH4_ZGaCC )

let gauge_higgs4_WWCC =
  ((Hp, Hm, Wp, Wm), Scalar2_Vector2 1, G_GH4_WWCC )

let gauge_higgs4_WWPP (p1, p2) =
  ((PHiggs p1, PHiggs p2, Wp, Wm), Scalar2_Vector2 1, G_GH4_WWPP (p1, p2))

let gauge_higgs4_WWSS (s1, s2) =
  ((SHiggs s1, SHiggs s2, Wp, Wm), Scalar2_Vector2 1, G_GH4_WWSS (s1, s2))

```

```

let gauge_higgs4_ZWSC s =
  [ ((Hp, SHiggs s, Wm, Z), Scalar2_Vector2 1, G_GH4_ZWSC s);
    ((Hm, SHiggs s, Wp, Z), Scalar2_Vector2 1, G_GH4_ZWSC s)]

let gauge_higgs4_GaWSC s =
  [ ((Hp, SHiggs s, Wm, Ga), Scalar2_Vector2 1, G_GH4_GaWSC s);
    ((Hm, SHiggs s, Wp, Ga), Scalar2_Vector2 1, G_GH4_GaWSC s)]

let gauge_higgs4_ZWPC p =
  [ ((Hp, PHiggs p, Wm, Z), Scalar2_Vector2 1, G_GH4_ZWPC p);
    ((Hm, PHiggs p, Wp, Z), Scalar2_Vector2 (-1), G_GH4_ZWPC p)]

let gauge_higgs4_GaWPC p =
  [ ((Hp, PHiggs p, Wm, Ga), Scalar2_Vector2 1, G_GH4_GaWPC p);
    ((Hm, PHiggs p, Wp, Ga), Scalar2_Vector2 (-1), G_GH4_GaWPC p)]

let gauge_higgs4 =
  List.map gauge_higgs4_ZZPP (pairs [P1; P2]) @
  List.map gauge_higgs4_ZZSS (pairs [S1; S2; S3]) @
  [gauge_higgs4_ZZCC] @ [gauge_higgs4_GaGaCC] @
  [gauge_higgs4_ZGaCC] @ [gauge_higgs4_WWCC] @
  List.map gauge_higgs4_WWPP (pairs [P1; P2]) @
  List.map gauge_higgs4_WWSS (pairs [S1; S2; S3]) @
  ThoList.flatmap gauge_higgs4_ZWSC [S1; S2; S3] @
  ThoList.flatmap gauge_higgs4_GaWSC [S1; S2; S3] @
  ThoList.flatmap gauge_higgs4_ZWPC [P1; P2] @
  ThoList.flatmap gauge_higgs4_GaWPC [P1; P2]
*****FB***

let gauge_sfermion4' g m1 m2 =
  [ ((Wp, Wm, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1,
    G_WWSFSF (SL, g, m1, m2));
    ((Z, Ga, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1,
    G_ZPSFSF (SL, g, m1, m2));
    ((Z, Z, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1,
    G_ZZSFSF (SL, g, m1, m2));
    ((Wp, Wm, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_WWSFSF
    (SU, g, m1, m2));
    ((Wp, Wm, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1,
    G_WWSFSF (SD, g, m1, m2));
    ((Z, Z, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_ZZSFSF
    (SU, g, m1, m2));
    ((Z, Z, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1, G_ZZSFSF
    (SD, g, m1, m2));
    ((Z, Ga, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_ZPSFSF
    (SU, g, m1, m2));
    ((Z, Ga, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1, G_ZPSFSF
    (SD, g, m1, m2)) ]

let gauge_sfermion4'' g m =
  [ ((Wp, Ga, Slepton (m, g), Sneutrino (-g)), Scalar2_Vector2 1,
    G_WPSLSN (false, g, m));
    ((Wm, Ga, Slepton (m, -g), Sneutrino g), Scalar2_Vector2 1,

```

```

      G_WPSLSN (true,g,m));
    ((Wp, Z, Slepton (m,g), Sneutrino (-g)), Scalar2_Vector2 1,
      G_WZSLSN(false,g,m));
    ((Wm, Z, Slepton (m,-g), Sneutrino g), Scalar2_Vector2 1,
      G_WZSLSN (true,g,m));
    ((Ga, Ga, Slepton (m,g), Slepton (m,-g)), Scalar2_Vector2 1,
      G_PPSFSF SL);
    ((Ga, Ga, Sup (m,g), Sup (m,-g)), Scalar2_Vector2 1, G_PPSFSF SU);
    ((Ga, Ga, Sdown (m,g), Sdown (m,-g)), Scalar2_Vector2 1, G_PPSFSF SD)]

let gauge_sfermion4 g =
  List.flatten (Product.list2 (gauge_sfermion4' g) [M1;M2] [M1;M2]) @
  ThoList.flatmap (gauge_sfermion4'' g) [M1;M2] @
  [ ((Wp, Wm, Sneutrino g, Sneutrino (-g)), Scalar2_Vector2 1, G_WWSFSF
    (SN,g,M1,M1));
    ((Z, Z, Sneutrino g, Sneutrino (-g)), Scalar2_Vector2 1, G_ZZSFSF
    (SN,g,M1,M1)) ]

** Added by Felix Braam. **

let gauge_squark4'' g h m1 m2 =
  [ ((Wp, Ga, Sup (m1,-g), Sdown (m2,h)), Scalar2_Vector2 1, G_WPSUSD
    (false,m1,m2,g,h));
    ((Wm, Ga, Sup (m1,g), Sdown (m2,-h)), Scalar2_Vector2 1, G_WPSUSD
    (true,m1,m2,g,h));
    ((Wp, Z, Sup (m1,-g), Sdown (m2,h)), Scalar2_Vector2 1, G_WZSUSD
    (false,m1,m2,g,h));
    ((Wm, Z, Sup (m1,g), Sdown (m2,-h)), Scalar2_Vector2 1, G_WZSUSD
    (true,m1,m2,g,h)) ]
let gauge_squark4' g h = List.flatten (Product.list2 (gauge_squark4'' g h)
  [M1;M2] [M1;M2])

let gauge_squark4 =
  if Flags.ckm_present then
    List.flatten (Product.list2 gauge_squark4' [1;2;3] [1;2;3])
  else
    ThoList.flatmap (fun g → gauge_squark4' g g) [1;2;3]

*****FB*****

let gluon_w_squark'' g h m1 m2 =
  [ ((Gl, Wp, Sup (m1,-g), Sdown (m2,h)),
    Scalar2_Vector2 1, G_GlWSUSD (false,m1,m2,g,h));
    ((Gl, Wm, Sup (m1,g), Sdown (m2,-h)),
    Scalar2_Vector2 1, G_GlWSUSD (true,m1,m2,g,h)) ]
let gluon_w_squark' g h =
  List.flatten (Product.list2 (gluon_w_squark'' g h) [M1;M2] [M1;M2])
let gluon_w_squark =
  if Flags.ckm_present then
    List.flatten (Product.list2 gluon_w_squark' [1;2;3] [1;2;3])
  else
    ThoList.flatmap (fun g → gluon_w_squark' g g) [1;2;3]

*****FB*****

```

```

let gluon_gauge_squark' g m1 m2 =
  [ ((Gl, Z, Sup (m1, g), Sup (m2, -g)),
      Scalar2_Vector2 2, G_GLZSFSF (SU, g, m1, m2));
    ((Gl, Z, Sdown (m1, g), Sdown (m2, -g)),
      Scalar2_Vector2 2, G_GLZSFSF (SD, g, m1, m2)) ]
let gluon_gauge_squark'' g m =
  [ ((Gl, Ga, Sup (m, g), Sup (m, -g)), Scalar2_Vector2 2, G_GLPSQSQ);
    ((Gl, Ga, Sdown (m, g), Sdown (m, -g)), Scalar2_Vector2 (-1), G_GLPSQSQ) ]
let gluon_gauge_squark g =
  List.flatten (Product.list2 (gluon_gauge_squark' g) [M1; M2] [M1; M2]) @
  ThoList.flatmap (gluon_gauge_squark'' g) [M1; M2]
(******FB******)
let gluon2_squark2' g m =
  [ ((Gl, Gl, Sup (m, g), Sup (m, -g)), Scalar2_Vector2 2, G_GLGLSQSQ);
    ((Gl, Gl, Sdown (m, g), Sdown (m, -g)), Scalar2_Vector2 2, G_GLGLSQSQ) ]
let gluon2_squark2 g =
  ThoList.flatmap (gluon2_squark2' g) [M1; M2]
** REVISED: Independent of the sign of CD. *FB*
** REVISED: Compact version using new COMBOS
** REVISED: Couplings adjusted to FF-convention

let higgs_SCC s =
  ((Hp, Hm, SHiggs s), Scalar_Scalar_Scalar 1, G_H3_SCC s)
let higgs_SSS (s1, s2, s3) =
  ((SHiggs s1, SHiggs s2, SHiggs s3), Scalar_Scalar_Scalar 1,
    G_H3_SSS (s1, s2, s3))
let higgs_SPP (p1, p2, s) =
  ((SHiggs s, PHiggs p1, PHiggs p2), Scalar_Scalar_Scalar 1,
    G_H3_SPP (s, p1, p2))

let higgs =
  List.map higgs_SCC [S1; S2; S3] @
  List.map higgs_SSS (triples [S1; S2; S3]) @
  List.map higgs_SPP (two_and_one [P1; P2] [S1; S2; S3])

let higgs4 = []
(* The vertices of the type Higgs - Sfermion - Sfermion are independent of the
choice of the CD sign since they are quadratic in the gauge coupling. *)
** REVISED: Independent of the sign of CD. **

let higgs_sneutrino' s g =
  ((SHiggs s, Sneutrino g, Sneutrino (-g)), Scalar_Scalar_Scalar 1,
    G_SFSSFS (s, SN, g, M1, M1))
let higgs_sneutrino'' g m =
  [ ((Hp, Sneutrino (-g), Slepton (m, g)), Scalar_Scalar_Scalar 1,
      G_HSNSL (false, g, m));
    ((Hm, Sneutrino g, Slepton (m, -g)), Scalar_Scalar_Scalar 1,
      G_HSNSL (true, g, m))]
let higgs_sneutrino =
  Product.list2 higgs_sneutrino' [S1; S2; S3] [1; 2; 3] @

```

List.flatten (Product.list2 higgs_sneutrino'' [1; 2; 3] [M1; M2])

Under the assumption that there is no mixing between the left- and right-handed sfermions for the first two generations there is only a coupling of the form Higgs - sfermion1 - sfermion2 for the third generation. All the others are suppressed by m_f/M_W .

** REVISED: Independent of the sign of CD. **

```

let higgs_sfermion_S s g m1 m2 =
  [ ((SHiggs s, Slepton (m1, g), Slepton (m2, -g)), Scalar_Scalar_Scalar 1,
      G_SFSFS (s, SL, g, m1, m2));
    ((SHiggs s, Sup (m1, g), Sup (m2, -g)), Scalar_Scalar_Scalar 1,
      G_SFSFS (s, SU, g, m1, m2));
    ((SHiggs s, Sdown (m1, g), Sdown (m2, -g)), Scalar_Scalar_Scalar 1,
      G_SFSFS (s, SD, g, m1, m2))]

let higgs_sfermion' g m1 m2 =
  (higgs_sfermion_S S1 g m1 m2) @ (higgs_sfermion_S S2 g m1 m2) @ (higgs_sfermion_S S3 g m1 m2)

let higgs_sfermion_P p g m1 m2 =
  [ ((PHiggs p, Slepton (m1, g), Slepton (m2, -g)), Scalar_Scalar_Scalar 1,
      G_SFSFP (p, SL, g, m1, m2));
    ((PHiggs p, Sup (m1, g), Sup (m2, -g)), Scalar_Scalar_Scalar 1,
      G_SFSFP (p, SU, g, m1, m2));
    ((PHiggs p, Sdown (m1, g), Sdown (m2, -g)), Scalar_Scalar_Scalar 1,
      G_SFSFP (p, SD, g, m1, m2)) ]

let higgs_sfermion'' g m1 m2 =
  (higgs_sfermion_P P1 g m1 m2) @ (higgs_sfermion_P P2 g m1 m2)
let higgs_sfermion = List.flatten (Product.list3 higgs_sfermion' [1; 2; 3] [M1; M2] [M1; M2]) @
  List.flatten (Product.list3 higgs_sfermion'' [1; 2; 3] [M1; M2] [M1; M2])

```

** REVISED: Independent of the sign of CD. **

```

let higgs_squark' g h m1 m2 =
  [ ((Hp, Sup (m1, -g), Sdown (m2, h)), Scalar_Scalar_Scalar 1,
      G_HSUSD (false, m1, m2, g, h));
    ((Hm, Sup (m1, g), Sdown (m2, -h)), Scalar_Scalar_Scalar 1,
      G_HSUSD (true, m1, m2, g, h)) ]

let higgs_squark_a g h = higgs_squark' g h M1 M1
let higgs_squark_b (g, h) = List.flatten (Product.list2 (higgs_squark' g h)
  [M1; M2] [M1; M2])

let higgs_squark =
  if Flags.ckm_present then
    List.flatten (Product.list2 higgs_squark_a [1; 2] [1; 2]) @
    ThoList.flatmap higgs_squark_b [(1, 3); (2, 3); (3, 3); (3, 1); (3, 2)]
  else
    higgs_squark_a 1 1 @ higgs_squark_a 2 2 @ higgs_squark_b (3, 3)

let vertices3 =
  (ThoList.flatmap electromagnetic_currents_3 [1; 2; 3] @
    ThoList.flatmap electromagnetic_currents_2 [C1; C2] @
    List.flatten (Product.list2 electromagnetic_sfermion_currents [1; 2; 3]
  [M1; M2]) @

```

```

    ThoList.flatmap neutral_currents [1; 2; 3] @
    ThoList.flatmap neutral_sfermion_currents [1; 2; 3] @
    ThoList.flatmap charged_currents [1; 2; 3] @
    List.flatten (Product.list2 charged_slepton_currents [1; 2; 3]
                  [M1; M2]) @
  (if Flags.ckm-present then
    List.flatten (Product.list2 charged_quark_currents [1; 2; 3]
                      [1; 2; 3]) @
    List.flatten (Product.list2 charged_squark_currents [1; 2; 3]
                      [1; 2; 3]) @
    ThoList.flatmap yukawa_higgs_quark [(1, 3); (2, 3); (3, 3); (3, 1); (3, 2)]
  else
    charged_quark_currents 1 1 @
    charged_quark_currents 2 2 @
    charged_quark_currents 3 3 @
    charged_squark_currents 1 1 @
    charged_squark_currents 2 2 @
    charged_squark_currents 3 3 @
    ThoList.flatmap yukawa_higgs_quark [(3, 3)] @
    yukawa_higgs 3 @ yukawa_n @
    ThoList.flatmap yukawa_c [C1; C2] @
    ThoList.flatmap yukawa_cq [C1; C2] @
    List.flatten (Product.list2 charged_chargino_currents [N1; N2; N3; N4; N5]
                  [C1; C2]) @ triple_gauge @
    ThoList.flatmap neutral_Z (pairs [N1; N2; N3; N4; N5]) @
    Product.list2 charged_Z [C1; C2] [C1; C2] @
    gauge_higgs @ higgs @ yukawa_higgs_2 @
    List.flatten (Product.list2 higgs_charg_neutr [N1; N2; N3; N4; N5] [C1; C2]) @
    higgs_neutr @ higgs_sneutrino @ higgs_sfermion @
    higgs_squark @ yukawa_v @
    ThoList.flatmap col_currents [1; 2; 3] @
    List.flatten (Product.list2 col_sfermion_currents [1; 2; 3] [M1; M2]))

let vertices4 =
  (quartic_gauge @ higgs4 @ gauge_higgs4 @
   ThoList.flatmap gauge_sfermion4 [1; 2; 3] @
   gauge_squark4 @ gluon_w_squark @
   ThoList.flatmap gluon2_squark2 [1; 2; 3] @
   ThoList.flatmap gluon_gauge_squark [1; 2; 3])

let vertices () = (vertices3, vertices4, [])

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

```

SLHA2-Nomenclature for neutral Higgses

```

let flavor_of_string s =
  match s with
  | "e-" → L 1 | "e+" → L (-1)

```

```

| "mu-" → L 2 | "mu+" → L (-2)
| "tau-" → L 3 | "tau+" → L (-3)
| "nue" → N 1 | "nuebar" → N (-1)
| "numu" → N 2 | "numubar" → N (-2)
| "nutau" → N 3 | "nutaubar" → N (-3)
| "se1-" → Slepton (M1,1) | "se1+" → Slepton (M1,-1)
| "smu1-" → Slepton (M1,2) | "smu1+" → Slepton (M1,-2)
| "stau1-" → Slepton (M1,3) | "stau1+" → Slepton (M1,-3)
| "se2-" → Slepton (M2,1) | "se2+" → Slepton (M2,-1)
| "smu2-" → Slepton (M2,2) | "smu2+" → Slepton (M2,-2)
| "stau2-" → Slepton (M2,3) | "stau2+" → Slepton (M2,-3)
| "snue" → Sneutrino 1 | "snue*" → Sneutrino (-1)
| "snumu" → Sneutrino 2 | "snumu*" → Sneutrino (-2)
| "snutau" → Sneutrino 3 | "snutau*" → Sneutrino (-3)
| "u" → U 1 | "ubar" → U (-1)
| "c" → U 2 | "cbar" → U (-2)
| "t" → U 3 | "tbar" → U (-3)
| "d" → D 1 | "dbar" → D (-1)
| "s" → D 2 | "sbar" → D (-2)
| "b" → D 3 | "bbar" → D (-3)
| "A" → Ga | "Z" | "Z0" → Z
| "W+" → Wp | "W-" → Wm
| "g1" | "g" → Gl
| "h01" → SHiggs S1 | "h02" → SHiggs S2 | "h03" →
SHiggs S3
| "A01" → PHiggs P1 | "A02" → PHiggs P2
| "H+" → Hp | "H-" → Hm
| "su1" → Sup (M1,1) | "su1c" → Sup (M1,-1)
| "sc1" → Sup (M1,2) | "sc1c" → Sup (M1,-2)
| "st1" → Sup (M1,3) | "st1c" → Sup (M1,-3)
| "su2" → Sup (M2,1) | "su2c" → Sup (M2,-1)
| "sc2" → Sup (M2,2) | "sc2c" → Sup (M2,-2)
| "st2" → Sup (M2,3) | "st2c" → Sup (M2,-3)
| "sg1" | "sg" → Gluino
| "sd1" → Sdown (M1,1) | "sd1c" → Sdown (M1,-1)
| "ss1" → Sdown (M1,2) | "ss1c" → Sdown (M1,-2)
| "sb1" → Sdown (M1,3) | "sb1c" → Sdown (M1,-3)
| "sd2" → Sdown (M2,1) | "sd2c" → Sdown (M2,-1)
| "ss2" → Sdown (M2,2) | "ss2c" → Sdown (M2,-2)
| "sb2" → Sdown (M2,3) | "sb2c" → Sdown (M2,-3)
| "neu1" → Neutralino N1 | "neu2" → Neutralino N2
| "neu3" → Neutralino N3 | "neu4" → Neutralino N4
| "neu5" → Neutralino N5
| "ch1+" → Chargino C1 | "ch2+" → Chargino C2
| "ch1-" → Chargino C1c | "ch2-" → Chargino C2c
| s → invalid_arg ("Fatal_error: %s\Modellib_NMSSM.NMSSM.flavor_of_string:" ^ s)

let flavor_to_string = function
| L 1 → "e-" | L (-1) → "e+"
| L 2 → "mu-" | L (-2) → "mu+"

```

```

| L 3 → "tau-" | L (-3) → "tau+"
| N 1 → "nue" | N (-1) → "nuebar"
| N 2 → "numu" | N (-2) → "numubar"
| N 3 → "nutau" | N (-3) → "nutaubar"
| U 1 → "u" | U (-1) → "ubar"
| U 2 → "c" | U (-2) → "cbar"
| U 3 → "t" | U (-3) → "tbar"
| U _ → invalid_arg
| "Modellib_NMSSM.NMSSM.flavor_to_string:_invalid_up_type_quark"
| D 1 → "d" | D (-1) → "dbar"
| D 2 → "s" | D (-2) → "sbar"
| D 3 → "b" | D (-3) → "bbar"
| D _ → invalid_arg
| "Modellib_NMSSM.NMSSM.flavor_to_string:_invalid_down_type_quark"
| Gl → "gl" | Gluino → "sgl"
| Ga → "A" | Z → "Z"
| Wp → "W+" | Wm → "W-"
| SHiggs S1 → "h01" | SHiggs S2 → "h02" | SHiggs S3 → "h03"
| PHiggs P1 → "A01" | PHiggs P2 → "A02"
| Hp → "H+" | Hm → "H-"
| Slepton (M1,1) → "se1-" | Slepton (M1,-1) → "se1+"
| Slepton (M1,2) → "smu1-" | Slepton (M1,-2) → "smu1+"
| Slepton (M1,3) → "stau1-" | Slepton (M1,-3) → "stau1+"
| Slepton (M2,1) → "se2-" | Slepton (M2,-1) → "se2+"
| Slepton (M2,2) → "smu2-" | Slepton (M2,-2) → "smu2+"
| Slepton (M2,3) → "stau2-" | Slepton (M2,-3) → "stau2+"
| Sneutrino 1 → "snue" | Sneutrino (-1) → "snue*"
| Sneutrino 2 → "snumu" | Sneutrino (-2) → "snumu*"
| Sneutrino 3 → "snutau" | Sneutrino (-3) → "snutau*"
| Sup (M1,1) → "su1" | Sup (M1,-1) → "su1c"
| Sup (M1,2) → "sc1" | Sup (M1,-2) → "sc1c"
| Sup (M1,3) → "st1" | Sup (M1,-3) → "st1c"
| Sup (M2,1) → "su2" | Sup (M2,-1) → "su2c"
| Sup (M2,2) → "sc2" | Sup (M2,-2) → "sc2c"
| Sup (M2,3) → "st2" | Sup (M2,-3) → "st2c"
| Sdown (M1,1) → "sd1" | Sdown (M1,-1) → "sd1c"
| Sdown (M1,2) → "ss1" | Sdown (M1,-2) → "ss1c"
| Sdown (M1,3) → "sb1" | Sdown (M1,-3) → "sb1c"
| Sdown (M2,1) → "sd2" | Sdown (M2,-1) → "sd2c"
| Sdown (M2,2) → "ss2" | Sdown (M2,-2) → "ss2c"
| Sdown (M2,3) → "sb2" | Sdown (M2,-3) → "sb2c"
| Neutralino N1 → "neu1"
| Neutralino N2 → "neu2"
| Neutralino N3 → "neu3"
| Neutralino N4 → "neu4"
| Neutralino N5 → "neu5"
| Chargino C1 → "ch1+" | Chargino C1c → "ch1-"
| Chargino C2 → "ch2+" | Chargino C2c → "ch2-"
| _ → invalid_arg "Modellib_NMSSM.NMSSM.flavor_to_string"

```



```

let flavor_to_TeX = function
| L 1 → "e^--" | L (-1) → "e^+"
| L 2 → "\\mu^--" | L (-2) → "\\mu^+"
| L 3 → "\\tau^--" | L (-3) → "\\tau^+"
| N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
| N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
| N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
| U 1 → "u" | U (-1) → "\\bar{u}"
| U 2 → "c" | U (-2) → "\\bar{c}"
| U 3 → "t" | U (-3) → "\\bar{t}"
| D 1 → "d" | D (-1) → "\\bar{d}"
| D 2 → "s" | D (-2) → "\\bar{s}"
| D 3 → "b" | D (-3) → "\\bar{b}"
| L _ → invalid_arg
      "Modellib_NMSSM.flavor_to_TeX: invalid lepton"
| N _ → invalid_arg
      "Modellib_NMSSM.flavor_to_TeX: invalid neutrino"
| U _ → invalid_arg
      "Modellib_NMSSM.flavor_to_TeX: invalid up type quark"
| D _ → invalid_arg
      "Modellib_NMSSM.flavor_to_TeX: invalid down type quark"
| Gl → "g" | Gluino → "\\widetilde{g}"
| Ga → "\\gamma" | Z → "Z" | Wp → "W^+" | Wm → "W^- "
| SHiggs S1 → "S_1" | SHiggs S2 → "S_2" | SHiggs S3 → "S_3"
| PHiggs P1 → "P_1" | PHiggs P2 → "P_2"
| Hp → "H^+" | Hm → "H^- "
| Slepton (M1,1) → "\\widetilde{e}_1^- "
| Slepton (M1,-1) → "\\widetilde{e}_1^+ "
| Slepton (M1,2) → "\\widetilde{\\mu}_1^- "
| Slepton (M1,-2) → "\\widetilde{\\mu}_1^+ "
| Slepton (M1,3) → "\\widetilde{\\tau}_1^- "
| Slepton (M1,-3) → "\\widetilde{\\tau}_1^+ "
| Slepton (M2,1) → "\\widetilde{e}_2^- "
| Slepton (M2,-1) → "\\widetilde{e}_2^+ "
| Slepton (M2,2) → "\\widetilde{\\mu}_2^- "
| Slepton (M2,-2) → "\\widetilde{\\mu}_2^+ "
| Slepton (M2,3) → "\\widetilde{\\tau}_2^- "
| Slepton (M2,-3) → "\\widetilde{\\tau}_2^+ "
| Sneutrino 1 → "\\widetilde{\\nu}_e"
| Sneutrino (-1) → "\\widetilde{\\nu}_e^*"
| Sneutrino 2 → "\\widetilde{\\nu}_\\mu"
| Sneutrino (-2) → "\\widetilde{\\nu}_\\mu^*"
| Sneutrino 3 → "\\widetilde{\\nu}_\\tau"
| Sneutrino (-3) → "\\widetilde{\\nu}_\\tau^*"
| Sup (M1,1) → "\\widetilde{u}_1"
| Sup (M1,-1) → "\\widetilde{u}_1^*"
| Sup (M1,2) → "\\widetilde{c}_1"
| Sup (M1,-2) → "\\widetilde{c}_1^*"
| Sup (M1,3) → "\\widetilde{t}_1"
| Sup (M1,-3) → "\\widetilde{t}_1^*"

```

```

| Sup (M2,1) → "\\widetilde{u}_{-2}"
| Sup (M2,-1) → "\\widetilde{u}_{-2}*"
| Sup (M2,2) → "\\widetilde{c}_{-2}"
| Sup (M2,-2) → "\\widetilde{c}_{-2}*"
| Sup (M2,3) → "\\widetilde{t}_{-2}"
| Sup (M2,-3) → "\\widetilde{t}_{-2}*"
| Sdown (M1,1) → "\\widetilde{d}_{-1}"
| Sdown (M1,-1) → "\\widetilde{d}_{-1}*"
| Sdown (M1,2) → "\\widetilde{s}_{-1}"
| Sdown (M1,-2) → "\\widetilde{s}_{-1}*"
| Sdown (M1,3) → "\\widetilde{b}_{-1}"
| Sdown (M1,-3) → "\\widetilde{b}_{-1}*"
| Sdown (M2,1) → "\\widetilde{d}_{-2}"
| Sdown (M2,-1) → "\\widetilde{d}_{-2}*"
| Sdown (M2,2) → "\\widetilde{s}_{-2}"
| Sdown (M2,-2) → "\\widetilde{s}_{-2}*"
| Sdown (M2,3) → "\\widetilde{b}_{-2}"
| Sdown (M2,-3) → "\\widetilde{b}_{-2}*"
| Neutralino N1 → "\\widetilde{\\chi}^0_{-1}"
| Neutralino N2 → "\\widetilde{\\chi}^0_{-2}"
| Neutralino N3 → "\\widetilde{\\chi}^0_{-3}"
| Neutralino N4 → "\\widetilde{\\chi}^0_{-4}"
| Neutralino N5 → "\\widetilde{\\chi}^0_{-5}"
| Slepton _ → invalid_arg
| "Modellib_NMSSM.NMSSM.flavor_to_TeX:_invalid_slepton"
| Sneutrino _ → invalid_arg
| "Modellib_NMSSM.NMSSM.flavor_to_TeX:_invalid_sneutrino"
| Sup _ → invalid_arg
| "Modellib_NMSSM.NMSSM.flavor_to_TeX:_invalid_up_type_squark"
| Sdown _ → invalid_arg
| "Modellib_NMSSM.NMSSM.flavor_to_TeX:_invalid_down_type_squark"
| Chargino C1 → "\\widetilde{\\chi}^{-1}_{+}"
| Chargino C1c → "\\widetilde{\\chi}^{-1}_{-}"
| Chargino C2 → "\\widetilde{\\chi}^{-2}_{+}"
| Chargino C2c → "\\widetilde{\\chi}^{-2}_{-}"

let flavor_symbol = function
| L g when g > 0 → "l" ^ string_of_int g
| L g → "l" ^ string_of_int (abs g) ^ "b"
| N g when g > 0 → "n" ^ string_of_int g
| N g → "n" ^ string_of_int (abs g) ^ "b"
| U g when g > 0 → "u" ^ string_of_int g
| U g → "u" ^ string_of_int (abs g) ^ "b"
| D g when g > 0 → "d" ^ string_of_int g
| D g → "d" ^ string_of_int (abs g) ^ "b"
| Gl → "gl"
| Ga → "a" | Z → "z"
| Wp → "wp" | Wm → "wm"
| Slepton (M1,g) when g > 0 → "s1l" ^ string_of_int g
| Slepton (M1,g) → "s1lc" ^ string_of_int (abs g)

```

```

| Slepton (M2, g) when g > 0 → "s12" ^ string_of_int g
| Slepton (M2, g) → "s12c" ^ string_of_int (abs g)
| Sneutrino g when g > 0 → "sn" ^ string_of_int g
| Sneutrino g → "snc" ^ string_of_int (abs g)
| Sup (M1, g) when g > 0 → "su1" ^ string_of_int g
| Sup (M1, g) → "su1c" ^ string_of_int (abs g)
| Sup (M2, g) when g > 0 → "su2" ^ string_of_int g
| Sup (M2, g) → "su2c" ^ string_of_int (abs g)
| Sdown (M1, g) when g > 0 → "sd1" ^ string_of_int g
| Sdown (M1, g) → "sd1c" ^ string_of_int (abs g)
| Sdown (M2, g) when g > 0 → "sd2" ^ string_of_int g
| Sdown (M2, g) → "sd2c" ^ string_of_int (abs g)
| Neutralino n → "neu" ^ (string_of_neu n)
| Chargino c when (int_of_char c) > 0 → "cp" ^ string_of_char c
| Chargino c → "cm" ^ string_of_int (abs (int_of_char c))
| Gluino → "sg1"
| SHiggs s → "h0" ^ (string_of_shiggs s)
| PHiggs p → "A0" ^ (string_of_phiggs p)
| Hp → "hp" | Hm → "hm"

let pdg = function
| L g when g > 0 → 9 + 2 × g
| L g → - 9 + 2 × g
| N g when g > 0 → 10 + 2 × g
| N g → - 10 + 2 × g
| U g when g > 0 → 2 × g
| U g → 2 × g
| D g when g > 0 → - 1 + 2 × g
| D g → 1 + 2 × g
| Gl → 21
| Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| SHiggs S1 → 25 | SHiggs S2 → 35 | SHiggs S3 → 45
| PHiggs P1 → 36 | PHiggs P2 → 46
| Hp → 37 | Hm → (-37)
| Slepton (M1, g) when g > 0 → 1000009 + 2 × g
| Slepton (M1, g) → - 1000009 + 2 × g
| Slepton (M2, g) when g > 0 → 2000009 + 2 × g
| Slepton (M2, g) → - 2000009 + 2 × g
| Sneutrino g when g > 0 → 1000010 + 2 × g
| Sneutrino g → - 1000010 + 2 × g
| Sup (M1, g) when g > 0 → 1000000 + 2 × g
| Sup (M1, g) → - 1000000 + 2 × g
| Sup (M2, g) when g > 0 → 2000000 + 2 × g
| Sup (M2, g) → - 2000000 + 2 × g
| Sdown (M1, g) when g > 0 → 999999 + 2 × g
| Sdown (M1, g) → - 999999 + 2 × g
| Sdown (M2, g) when g > 0 → 1999999 + 2 × g
| Sdown (M2, g) → - 1999999 + 2 × g
| Gluino → 1000021

```

	<i>Chargino C1</i>	→	1000024		<i>Chargino C1c</i>	→	(−1000024)
	<i>Chargino C2</i>	→	1000037		<i>Chargino C2c</i>	→	(−1000037)
	<i>Neutralino N1</i>	→	1000022		<i>Neutralino N2</i>	→	1000023
	<i>Neutralino N3</i>	→	1000025		<i>Neutralino N4</i>	→	1000035
	<i>Neutralino N5</i>	→	1000045				

We must take care of the pdg numbers for the two different kinds of sfermions in the MSSM. The particle data group in its Monte Carlo particle numbering scheme takes only into account mixtures of the third generation squarks and the stau. For the other sfermions we will use the number of the lefthanded field for the lighter mixed state and the one for the righthanded for the heavier. Below are the official pdg numbers from the Particle Data Group. In order not to produce arrays with some million entries in the Fortran code for the masses and the widths we introduce our private pdg numbering scheme which only extends not too far beyond 42. Our private scheme then has the following pdf numbers (for the sparticles the subscripts L/R and $1/2$ are taken synonymously):

d	down-quark	1
u	up-quark	2
s	strange-quark	3
c	charm-quark	4
b	bottom-quark	5
t	top-quark	6
e^-	electron	11
ν_e	electron-neutrino	12
μ^-	muon	13
ν_μ	muon-neutrino	14
τ^-	tau	15
ν_τ	tau-neutrino	16
g	gluon	(9) 21
γ	photon	22
Z^0	Z-boson	23
W^+	W-boson	24
h^0	light Higgs boson	25
H^0	heavy Higgs boson	35
A^0	pseudoscalar Higgs	36
H^\pm	charged Higgs	37
\tilde{d}_L	down-squark 1	41
\tilde{u}_L	up-squark 1	42
\tilde{s}_L	strange-squark 1	43
\tilde{c}_L	charm-squark 1	44
\tilde{b}_L	bottom-squark 1	45
\tilde{t}_L	top-squark 1	46
\tilde{d}_R	down-squark 2	47
\tilde{u}_R	up-squark 2	48
\tilde{s}_R	strange-squark 2	49
\tilde{c}_R	charm-squark 2	50
\tilde{b}_R	bottom-squark 2	51
\tilde{t}_R	top-squark 2	52
\tilde{e}_L	selectron 1	53
$\tilde{\nu}_{e,L}$	electron-sneutrino	54
$\tilde{\mu}_L$	smuon 1	55
$\tilde{\nu}_{\mu,L}$	muon-sneutrino	56
$\tilde{\tau}_L$	stau 1	57
$\tilde{\nu}_{\tau,L}$	tau-sneutrino	58
\tilde{e}_R	selectron 2	59
$\tilde{\mu}_R$	smuon 2	61
$\tilde{\tau}_R$	stau 2	63
\tilde{g}	gluino 506	64
$\tilde{\chi}_1^0$	neutralino 1	65
$\tilde{\chi}_2^0$	neutralino 2	66
$\tilde{\chi}_3^0$	neutralino 3	67
$\tilde{\chi}_4^0$	neutralino 4	68
$\tilde{\chi}_5^0$	neutralino 5	69
$\tilde{\chi}_1^\pm$	chargino 1	70

```

let pdg_mw = function
| L g when g > 0 → 9 + 2 × g
| L g → - 9 + 2 × g
| N g when g > 0 → 10 + 2 × g
| N g → - 10 + 2 × g
| U g when g > 0 → 2 × g
| U g → 2 × g
| D g when g > 0 → - 1 + 2 × g
| D g → 1 + 2 × g
| Gl → 21
| Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| SHiggs S1 → 25 | SHiggs S2 → 35 | PHiggs P1 → 36
| Hp → 37 | Hm → (-37)
| Sup (M1, g) when g > 0 → 40 + 2 × g
| Sup (M1, g) → - 40 + 2 × g
| Sup (M2, g) when g > 0 → 46 + 2 × g
| Sup (M2, g) → - 46 + 2 × g
| Sdown (M1, g) when g > 0 → 39 + 2 × g
| Sdown (M1, g) → - 39 + 2 × g
| Sdown (M2, g) when g > 0 → 45 + 2 × g
| Sdown (M2, g) → - 45 + 2 × g
| Slepton (M1, g) when g > 0 → 51 + 2 × g
| Slepton (M1, g) → - 51 + 2 × g
| Slepton (M2, g) when g > 0 → 57 + 2 × g
| Slepton (M2, g) → - 57 + 2 × g
| Sneutrino g when g > 0 → 52 + 2 × g
| Sneutrino g → - 52 + 2 × g
| Gluino → 64
| Chargino C1 → 70 | Chargino C1c → (-70)
| Chargino C2 → 71 | Chargino C2c → (-71)
| Neutralino N1 → 65 | Neutralino N2 → 66
| Neutralino N3 → 67 | Neutralino N4 → 68
| Neutralino N5 → 69
| PHiggs P2 → 72 | SHiggs S3 → 73

let mass_symbol f =
"mass(" ^ string_of_int (abs (pdg_mw f)) ^ ")"

let width_symbol f =
"width(" ^ string_of_int (abs (pdg_mw f)) ^ ")"

let conj_symbol = function
| false, str → str
| true, str → str ^ "_c"

let constant_symbol = function
| E → "e" | G → "g"
| Mu → "mu" | Lambda → "lambda" | G_Z → "gz"
| Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdown"
| Q_charg → "qchar"
| G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"

```

```

| G_NC_up → "gncup" | G_NC_down → "gncdwn"
| G_CC → "gcc"
| G_CCQ (vc, g1, g2) → conj_symbol (vc, "g_ccq" ) ^ "(" ^
  string_of_int g1 ^ ", " ^ string_of_int g2 ^ ")"
| I_Q_W → "iqw" | I_G_ZWW → "igzww"
| G_WWWW → "gw4" | G_ZZWW → "gzzww"
| G_PZWW → "gpzww" | G_PPWW → "gppww"
| G_GH4_ZZPP (p1, p2) → "g_ZZA0A0(" ^ string_of_phiggs p1 ^ ", "
  ^ string_of_phiggs p2 ^ ")"
| G_GH4_ZZSS (s1, s2) → "g_ZZh0h0(" ^ string_of_shiggs s1 ^ ", "
  ^ string_of_shiggs s2 ^ ")"
| G_GH4_ZZCC → "g-zzhphm"
| G_GH4_GaGaCC → "g-AAhphm"
| G_GH4_ZGaCC → "g-zAhphm"
| G_GH4_WWCC → "g-wwhphm"
| G_GH4_WWPP (p1, p2) → "g-WWA0A0(" ^ string_of_phiggs p1 ^ ", "
  ^ string_of_phiggs p2 ^ ")"
| G_GH4_WWSS (s1, s2) → "g-WWh0h0(" ^ string_of_shiggs s1 ^ ", "
  ^ string_of_shiggs s2 ^ ")"
| G_GH4_ZWSC s → "g-ZWhph0(" ^ string_of_shiggs s ^ ")"
| G_GH4_GaWSC s → "g-AWhph0(" ^ string_of_shiggs s ^ ")"
| G_GH4_ZWPC p → "g-ZWhpA0(" ^ string_of_phiggs p ^ ")"
| G_GH4_GaWPC p → "g-AWhpA0(" ^ string_of_phiggs p ^ ")"
| G_CICIS (n1, n2, s) → "g-neuneuh0(" ^ string_of_neu n1 ^ ", "
  ^ string_of_neu n2 ^ ", " ^ string_of_shiggs s ^ ")"
| G_CICIP (n1, n2, p) → "g-neuneuA0(" ^ string_of_neu n1 ^ ", "
  ^ string_of_neu n2 ^ ", " ^ string_of_phiggs p ^ ")"
| G_H3_SCC s → "g-h0hphm(" ^ string_of_shiggs s ^ ")"
| G_H3_SPP (s, p1, p2) → "g_h0A0A0(" ^ string_of_shiggs s ^ ", "
  ^ string_of_phiggs p1 ^ ", " ^ string_of_phiggs p2 ^ ")"
| G_H3_SSS (s1, s2, s3) → "g-h0h0h0(" ^ string_of_shiggs s1 ^ ", "
  ^ string_of_shiggs s2 ^ ", " ^ string_of_shiggs s3 ^ ")"
| G_CSC (c1, c2, s) → "g-chchh0(" ^ string_of_char c1 ^ ", "
  ^ string_of_char c2 ^ ", " ^ string_of_shiggs s ^ ")"
| G_CPC (c1, c2, p) → "g-chchA0(" ^ string_of_char c1 ^ ", "
  ^ string_of_char c2 ^ ", " ^ string_of_phiggs p ^ ")"
| G_YUK_FFS (f1, f2, s) → "g-yuk_h0-" ^ string_of_fermion_type f1 ^
  string_of_fermion_type f2 ^ "(" ^ string_of_shiggs s ^ ", "
  ^ string_of_fermion_gen f1 ^ ")"
| G_YUK_FFP (f1, f2, p) → "g-yuk_A0-" ^ string_of_fermion_type f1 ^
  string_of_fermion_type f2 ^ "(" ^ string_of_phiggs p ^ ", "
  ^ string_of_fermion_gen f1 ^ ")"
| G_YUK_LCN g → "g-yuk_hp_ln(" ^ string_of_int g ^ ")"
| G_NWC (n, c) → "g-nwc(" ^ string_of_char c ^ ", " ^ string_of_neu n
  ^ ")"
| G_CWN (c, n) → "g-cwn(" ^ string_of_char c ^ ", " ^ string_of_neu n
  ^ ")"
| G_SLSNW (vc, g, m) → conj_symbol (vc, "g-wslsn") ^ "(" ^
  string_of_int g ^ ", " ^ string_of_sfm m ^ ")"
| G_NZN (n1, n2) → "g-zneuneu(" ^ string_of_neu n1 ^ ", "

```

```

      ^ string_of_neu n2 ^ ") "
| G_CZC (c1, c2) → "g-zchch(" ^ string_of_char c1 ^ ", " ^
      string_of_char c2 ^ ") "
| Gs → "gs"
| G_YUK_UCD (n, m) → "g-yuk-hp-ud(" ^ string_of_int n ^ ", " ^
      string_of_int m ^ ") "
| G_YUK_DCU (n, m) → "g-yuk-hm-du(" ^ string_of_int n ^ ", " ^
      string_of_int m ^ ") "
| G_YUK_N (vc, f, n, sf, m) → conj_symbol (vc, "g-yuk-neu-" ^
      string_of_fermion_type f ^ string_of_sff sf) ^ "(" ^
      string_of_fermion_gen f ^ ", " ^ string_of_neu n ^ ", " ^
      string_of_sfm m ^ ") "
| G_YUK_G (vc, f, sf, m) → conj_symbol (vc, "g-yuk-gluino-" ^
      string_of_fermion_type f ^ string_of_sff sf) ^ "(" ^
      string_of_fermion_gen f ^ ", " ^ string_of_sfm m ^ ") "
| G_YUK_C (vc, f, c, sf, m) → conj_symbol (vc, "g-yuk-char-" ^
      string_of_fermion_type f ^ string_of_sff sf) ^ "(" ^
      string_of_fermion_gen f ^ ", " ^ string_of_char c ^ ", " ^
      string_of_sfm m ^ ") "
| G_YUK_Q (vc, g1, f, c, sf, m) → conj_symbol (vc, "g-yuk-char-" ^
      string_of_fermion_type f ^ string_of_sff sf) ^ "(" ^ string_of_int
      g1 ^ ", " ^ string_of_fermion_gen f ^ ", " ^ string_of_char c ^ ", " ^
      string_of_sfm m ^ ") "
| G_WPSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "g-wA-susd") ^ "(" ^
      string_of_int g1 ^ ", " ^ string_of_int g2 ^ ", " ^ string_of_sfm m1 ^
      ", " ^ string_of_sfm m2 ^ ") "
| G_WZSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "g-wz-susd") ^ "(" ^
      string_of_int g1 ^ ", " ^ string_of_int g2 ^ ", " ^ string_of_sfm m1 ^
      ", " ^ string_of_sfm m2 ^ ") "
| G_GH_ZSP (s, p) → "g-zh0a0(" ^ string_of_shiggs s ^ ", " ^
      string_of_phiggs p ^ ") "
| G_GH_WSC s → "g-Whph0(" ^ string_of_shiggs s ^ ") "
| G_GH_WPC p → "g-WhpA0(" ^ string_of_phiggs p ^ ") "
| G_GH_ZZS s → "g-ZZh0(" ^ string_of_shiggs s ^ ") "
| G_GH_WWS s → "g-WWh0(" ^ string_of_shiggs s ^ ") "
| G_GLUGLUH0 s → "g-glugluh0(" ^ string_of_shiggs s ^ ") "
| G_GLUGLUA0 p → "g-gluglua0(" ^ string_of_phiggs p ^ ") "
| G_GH_ZCC → "g-Zhmhp"
| G_GH_GaCC → "g-Ahmhp"
| G_ZSF (f, g, m1, m2) → "g-z" ^ string_of_sff f ^ string_of_sff f ^ "(" ^
      string_of_int g ^ ", " ^ string_of_sfm m1 ^ ", " ^ string_of_sfm m2
      ^ ") "
| G_HSNSL (vc, g, m) → conj_symbol (vc, "g-hp-s1" ^ string_of_sfm m ^
      "sn1") ^ "(" ^ string_of_int g ^ ") "
| G_GLISQSQ → "g-gg-sqsq"
| G_PPSFSF f → "g-AA-" ^ string_of_sff f ^ string_of_sff f
| G_ZZSFSF (f, g, m1, m2) → "g-zz-" ^ string_of_sff f ^ string_of_sff f ^
      "(" ^ string_of_int g ^ ", " ^ string_of_sfm m1
      ^ ", " ^ string_of_sfm m2 ^ ") "
| G_ZPSFSF (f, g, m1, m2) → "g-zA-" ^ string_of_sff f ^ string_of_sff f ^

```



```

      "(" ^ string_of_int g ^ "," ^ string_of_sfm m1
      ^ "," ^ string_of_sfm m2 ^ ")"
| G_GLPSQSQ → "g-gA-sqsq"
| G_GLZSFSF (f, g, m1, m2) → "g-gz-" ^ string_of_sff f ^ string_of_sff f ^
      "(" ^ string_of_int g ^ "," ^ string_of_sfm m1 ^ "," ^ string_of_sfm
      m2 ^ ")"
| G_GLWSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "g-gw-susd") ^ "(" ^
      string_of_int g1 ^ "," ^ string_of_int g2 ^ "," ^ string_of_sfm m1 ^
      "," ^ string_of_sfm m2 ^ ")"
| G_SS → "gs**2"
| I_G_S → "igs"
| G_NHC (vc, n, c) → conj_symbol (vc, "g-neuhmchar") ^ "(" ^
      string_of_neu n ^ "," ^ string_of_char c ^ ")"
| G_WWSFSF (f, g, m1, m2) → "g-ww-" ^ string_of_sff f
      ^ string_of_sff f ^ "(" ^ string_of_int g ^ "," ^ string_of_sfm m1 ^
      "," ^ string_of_sfm m2 ^ ")"
| G_WPSLSN (vc, g, m) → conj_symbol (vc, "g-wA-slsn") ^ "(" ^
      string_of_int g ^ "," ^ string_of_sfm m ^ ")"
| G_WZSLSN (vc, g, m) → conj_symbol (vc, "g-wz-slsn") ^ "(" ^ string_of_int
      g ^ "," ^ string_of_sfm m ^ ")"
| G_SFSFS (s, f, g, m1, m2) → "g-h0-" ^ string_of_sff f ^ string_of_sfm m1
      ^ string_of_sff f ^ string_of_sfm m2 ^ "(" ^ string_of_shiggs s ^ ","
      ^ string_of_int g ^ ")"
| G_SFSEFP (p, f, g, m1, m2) → "g-A0-" ^ string_of_sff f ^ string_of_sfm m1
      ^ string_of_sff f ^ string_of_sfm m2 ^ "(" ^ string_of_phiggs p ^ ","
      ^ string_of_int g ^ ")"
| G_HSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "g-hp-su" ^ string_of_sfm
      m1 ^ "sd" ^ string_of_sfm m2) ^ "(" ^ string_of_int g1 ^ ","
      ^ string_of_int g2 ^ ")"
| G_WSQ (vc, g1, g2, m1, m2) → conj_symbol (vc, "g-wsusd") ^ "(" ^
      ^ string_of_int g1 ^ "," ^ string_of_int g2 ^ "," ^ string_of_sfm m1
      ^ "," ^ string_of_sfm m2 ^ ")"

```

end

13.11 Interface of *Modellib_PSSSM*

13.11.1 Extended Supersymmetric Models

We do not introduce the possibility here of using four point couplings or not. We simply add the relevant and leave the rest out. No possibility for Goldstone bosons is given. But we allow for CKM mixing.

```

module type extMSSM_flags =
  sig
    val ck_m_present : bool
  end

module PSSSM : extMSSM_flags
module PSSSM_QCD : extMSSM_flags

```

```
module ExtMSSM : functor (F : extMSSM_flags) → Model.T with mod-
ule Ch = Charges.QQ
```

13.12 Implementation of *Modellib_PSSSM*

```
let rcs_file = RCS.parse "Modellib_PSSSM" ["Extended_SUSY_models"]
{ RCS.revision = "$Revision: 4193$";
  RCS.date = "$Date: 2013-04-20 11:46:00 +0200 (Sat, 20 Apr 2013)$";
  RCS.author = "$Author: jr-reuter$";
  RCS.source
    = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
```

13.12.1 Extended Supersymmetric Standard Model(s)

This is based on the NMSSM implementation by Felix Braam, and extended to the exotica – leptoquarks, leptoquarkinos, additional Higgses etc. – by Daniel Wiesler. Note that for the Higgs sector vertices the conventions of the Franke/Fraas paper have been used.

```
module type extMSSM_flags =
sig
  val ckm_present : bool
end

module PSSSM : extMSSM_flags =
struct
  let ckm_present = false
end

module PSSSM_QCD : extMSSM_flags =
struct
  let ckm_present = false
end

module ExtMSSM (Flags : extMSSM_flags) =
struct
  let rcs = RCS.rename rcs_file "Modellib_PSSSM.NMSSM"
    [ "Extended_SUSY_models" ]

  open Coupling

  let default_width = ref Timelike
  let use_fudged_width = ref false

  let options = Options.create
    [ "constant_width", Arg.Unit (fun () → default_width := Constant),
      "use_constant_width_(also_in_t-channel)";
      "fudged_width", Arg.Set use_fudged_width,
      "use_fudge_factor_for_charge_particle_width";
      "custom_width", Arg.String (fun f → default_width := Custom f),
      "use_custom_width";
```

```
"cancel_widths", Arg.Unit (fun () → default_width := Vanishing),
"use_vanishing_width"]
```

additional combinatorics

yields a list of tuples consistig of the off-diag combinations of the elements in "set"

```
let choose2 set =
  List.map (function [x;y] → (x,y) | _ → failwith "choose2")
    (Combinatorics.choose 2 set)
```

pairs

pairs appends the diagonal combinations to *choose2*

```
let rec diag = function
| [] → []
| x1 :: rest → (x1, x1) :: diag rest

let pairs l = choose2 l @ diag l
```

triples

rank 3 generalization of *pairs*

```
let rec cloop set i j k =
  if i > ((List.length set) - 1) then []
  else if j > i then cloop set (succ i) (j - i - 1) (j - i - 1)
  else if k > j then cloop set i (succ j) (k - j - 1)
  else (List.nth set i, List.nth set j, List.nth set k) :: cloop set i j (succ k)

let triples set = cloop set 0 0 0
(* two_and_one *)

let rec two_and_one' l1 z n =
  if n < 0 then []
  else
    ((fst (List.nth (pairs l1) n)), (snd (List.nth (pairs l1) n)), z) :: two_and_one' l1 z (pred n)

let two_and_one l1 l2 =
  let f z = two_and_one' l1 z ((List.length (pairs l1)) - 1)
  in
    List.flatten ( List.map f l2 )

type gen =
| G of int | GG of gen × gen

let rec string_of_gen = function
| G n when n > 0 → string_of_int n
| G n → string_of_int (abs n) ^ "c"
| GG (g1,g2) → string_of_gen g1 ^ "-" ^ string_of_gen g2
```

With this we distinguish the flavour.

```
type sff =
| SL | SN | SU | SD

let string_of_sff = function
| SL → "s1" | SN → "sn" | SU → "su" | SD → "sd"
```

With this we distinguish the mass eigenstates. At the moment we have to cheat a little bit for the sneutrinos. Because we are dealing with massless neutrinos there is only one sort of sneutrino.

```

type sfm =
  | M1 | M2

let string_of_sfm = function
  | M1 → "1" | M2 → "2"

```

We also introduce special types for the charginos and neutralinos.

```

type char =
  | C1 | C2 | C1c | C2c | C3 | C3c | C4 | C4c

type neu =
  | N1 | N2 | N3 | N4 | N5 | N6 | N7 | N8 | N9 | N10 | N11

let int_of_char = function
  | C1 → 1 | C2 → 2 | C1c → -1 | C2c → -2
  | C3 → 3 | C4 → 4 | C3c → -3 | C4c → -4

let string_of_char c = string_of_int (int_of_char c)

let conj_char = function
  | C1 → C1c | C2 → C2c | C1c → C1 | C2c → C2
  | C3 → C3c | C4 → C4c | C3c → C3 | C4c → C4

let string_of_neu = function
  | N1 → "1" | N2 → "2" | N3 → "3" | N4 → "4" | N5 →
"5" | N6 → "6"
  | N7 → "7" | N8 → "8" | N9 → "9" | N10 → "10" | N11 → "11"

```

For NMSSM-like the Higgs bosons, we follow the conventions of Franke/Fraas. Daniel Wiesler: extended to E6 models.

```

type shiggs =
  | S1 | S2 | S3 | S4 | S5 | S6 | S7 | S8 | S9

type phiggs =
  | P1 | P2 | P3 | P4 | P5 | P6 | P7

HCx is always the  $H^+$ , HCxc the  $H^-$ .

type chiggs =
  | HC1 | HC2 | HC3 | HC4 | HC5 | HC1c | HC2c | HC3c |
HC4c | HC5c

let conj_chiggs = function
  | HC1 → HC1c | HC2 → HC2c | HC1c → HC1 | HC2c → HC2
  | HC3 → HC3c | HC4 → HC4c | HC3c → HC3 | HC4c → HC4
  | HC5 → HC5c | HC5c → HC5

let string_of_shiggs = function
  | S1 → "1" | S2 → "2" | S3 → "3" | S4 → "4" | S5 → "5"
  | S6 → "6" | S7 → "7" | S8 → "8" | S9 → "9"

let string_of_phiggs = function
  | P1 → "1" | P2 → "2" | P3 → "3" | P4 → "4" | P5 → "5"

```

```

| P6 → "6" | P7 → "7"

let nlist = [ N1; N2; N3; N4; N5; N6; N7; N8; N9; N10; N11 ]
let slist = [ S1; S2; S3; S4; S5; S6; S7; S8; S9 ]
let plist = [ P1; P2; P3; P4; P5; P6; P7 ]
let clist = [ HC1; HC2; HC3; HC4; HC5; HC1c; HC2c; HC3c; HC4c; HC5c ]
let charlist = [ C1; C2; C3; C4; C1c; C2c; C3c; C4c ]

type flavor =
| L of int | N of int
| U of int | D of int
| Sup of sfm × int | Sdown of sfm × int
| Ga | Wp | Wm | Z | Gl
| Slepton of sfm × int | Sneutrino of int
| Neutralino of neu | Chargino of char
| Gluino | SHiggs of shiggs | PHiggs of phiggs
| CHiggs of chiggs
| LQ of sfm × int
| LQino of int

let string_of_fermion_type = function
| L _ → "l" | U _ → "u" | D _ → "d" | N _ → "n"
| _ → failwith
      "Modellib_PSSSM.ExtMSSM.string_of_fermion_type:␣invalid␣fermion␣type"

let string_of_fermion_gen = function
| L g | U g | D g | N g → string_of_int (abs (g))
| _ → failwith
      "Modellib_PSSSM.ExtMSSM.string_of_fermion_gen:␣invalid␣fermion␣type"

type gauge = unit

let gauge_symbol () =
  failwith "Modellib_PSSSM.ExtMSSM.gauge_symbol:␣internal␣error"

```

At this point we will forget graviton and -ino.

```

let family g = [ L g; N g; Slepton (M1, g);
                 Slepton (M2, g); Sneutrino g;
                 U g; D g; Sup (M1, g); Sup (M2, g);
                 Sdown (M1, g); Sdown (M2, g);
                 LQ (M1, g); LQ (M2, g); LQino g ]

let external_flavors () =
[ "1st␣Generation␣matter", ThoList.flatmap family [1; -1];
  "2nd␣Generation␣matter", ThoList.flatmap family [2; -2];
  "3rd␣Generation␣matter", ThoList.flatmap family [3; -3];
  "Gauge␣Bosons", [Ga; Z; Wp; Wm; Gl];
  "Charginos", List.map (fun a → Chargino a) charlist;
  "Neutralinos", List.map (fun a → Neutralino a) nlist;
  "Higgs␣Bosons", List.map (fun a → SHiggs a) slist @
    List.map (fun a → PHiggs a) plist @
    List.map (fun a → CHiggs a) clist;
  "Gluino", [Gluino]]

```

```

let flavors () = ThoList.flatmap snd (external_flavors ())

let spinor n m =
  if n ≥ 0 ∧ m ≥ 0 then
    Spinor
  else if
    n ≤ 0 ∧ m ≤ 0 then
    ConjSpinor
  else
    invalid_arg "Modellib_PSSSM.ExtMSSM.spinor:␣internal␣error"

let lorentz = function
| L g → spinor g 0 | N g → spinor g 0
| U g → spinor g 0 | D g → spinor g 0
| LQino g → spinor g 0
| Chargino c → spinor (int_of_char c) 0
| Ga | Gl → Vector
| Wp | Wm | Z → Massive_Vector
| SHiggs - | PHiggs - | CHiggs -
| Sup - | Sdown - | Slepton - | Sneutrino - | LQ - → Scalar
| Neutralino - | Gluino → Majorana

let color = function
| U g → Color.SUN (if g > 0 then 3 else -3)
| Sup (m, g) → Color.SUN (if g > 0 then 3 else -3)
| D g → Color.SUN (if g > 0 then 3 else -3)
| Sdown (m, g) → Color.SUN (if g > 0 then 3 else -3)
| LQ (m, g) → Color.SUN (if g > 0 then 3 else -3)
| LQino g → Color.SUN (if g > 0 then 3 else -3)
| Gl | Gluino → Color.AdjSUN 3
| - → Color.Singlet

let prop_spinor n m =
  if n ≥ 0 ∧ m ≥ 0 then
    Prop_Spinor
  else if
    n ≤ 0 ∧ m ≤ 0 then
    Prop_ConjSpinor
  else
    invalid_arg "Modellib_PSSSM.ExtMSSM.prop_spinor:␣internal␣error"

let propagator = function
| L g → prop_spinor g 0 | N g → prop_spinor g 0
| U g → prop_spinor g 0 | D g → prop_spinor g 0
| LQino g → prop_spinor g 0
| Chargino c → prop_spinor (int_of_char c) 0
| Ga | Gl → Prop_Feynman
| Wp | Wm | Z → Prop_Unitarity
| SHiggs - | PHiggs - | CHiggs - → Prop_Scalar
| Sup - | Sdown - | Slepton - | Sneutrino - → Prop_Scalar
| LQ - → Prop_Scalar
| Gluino → Prop_Majorana
| Neutralino - → Prop_Majorana

```

Optionally, ask for the fudge factor treatment for the widths of charged particles. Currently, this only applies to W^\pm and top.

```

let width f =
  if !use_fudged_width then
    match f with
    | Wp | Wm | U 3 | U (-3) → Fudged
    | _ → !default_width
  else
    !default_width

let goldstone _ = None

let conjugate = function
| L g → L (-g) | N g → N (-g)
| U g → U (-g) | D g → D (-g)
| Sup (m, g) → Sup (m, -g)
| Sdown (m, g) → Sdown (m, -g)
| Slepton (m, g) → Slepton (m, -g)
| Sneutrino g → Sneutrino (-g)
| Gl → Gl | Ga → Ga | Z → Z
| Wp → Wm | Wm → Wp
| SHiggs s → SHiggs s
| PHiggs p → PHiggs p
| CHiggs c → CHiggs (conj_chiggs c)
| Gluino → Gluino
| Neutralino n → Neutralino n | Chargino c → Chargino (conj_char c)
| LQino g → LQino (-g)
| LQ (m, g) → LQ (m, -g)

let fermion = function
| L g → if g > 0 then 1 else -1
| N g → if g > 0 then 1 else -1
| U g → if g > 0 then 1 else -1
| D g → if g > 0 then 1 else -1
| Gl | Ga | Z | Wp | Wm → 0
| SHiggs _ | PHiggs _ | CHiggs _ → 0
| Neutralino _ → 2
| Chargino c → if (int_of_char c) > 0 then 1 else -1
| Sup _ → 0 | Sdown _ → 0
| Slepton _ → 0 | Sneutrino _ → 0
| Gluino → 2
| LQ _ → 0
| LQino g → if g > 0 then 1 else -1

```

This model does NOT have a conserved generation quantum number.

```

module Ch = Charges.QQ

let ( // ) = Algebra.Small_Rational.make

let charge = function
| L n → if n > 0 then -1//1 else 1//1
| Slepton (_, n) → if n > 0 then -1//1 else 1//1

```

```

|  $N\ n \rightarrow 0//1$ 
|  $Sneutrino\ n \rightarrow 0//1$ 
|  $U\ n \rightarrow \text{if } n > 0 \text{ then } 2//3 \text{ else } -2//3$ 
|  $Sup\ (-, n) \rightarrow \text{if } n > 0 \text{ then } 2//3 \text{ else } -2//3$ 
|  $D\ n \mid LQ\ (-, n) \mid LQino\ n \rightarrow \text{if } n > 0 \text{ then } -1//3 \text{ else } 1//3$ 
|  $Sdown\ (-, n) \rightarrow \text{if } n > 0 \text{ then } -1//3 \text{ else } 1//3$ 
|  $Gl \mid Ga \mid Z \mid Neutralino\ - \mid Gluino \rightarrow 0//1$ 
|  $Wp \rightarrow 1//1$ 
|  $Wm \rightarrow -1//1$ 
|  $SHiggs\ - \mid PHiggs\ - \rightarrow 0//1$ 
|  $CHiggs\ (HC1 \mid HC2 \mid HC3 \mid HC4 \mid HC5) \rightarrow 1//1$ 
|  $CHiggs\ (HC1c \mid HC2c \mid HC3c \mid HC4c \mid HC5c) \rightarrow -1//1$ 
|  $Chargino\ (C1 \mid C2 \mid C3 \mid C4) \rightarrow 1//1$ 
|  $Chargino\ (C1c \mid C2c \mid C3c \mid C4c) \rightarrow -1//1$ 

let lepton = function
|  $L\ n \mid N\ n \rightarrow \text{if } n > 0 \text{ then } 1//1 \text{ else } -1//1$ 
|  $Slepton\ (-, n)$ 
|  $Sneutrino\ n \rightarrow \text{if } n > 0 \text{ then } 1//1 \text{ else } -1//1$ 
|  $LQ\ (-, n) \mid LQino\ n \rightarrow \text{if } n > 0 \text{ then } 1//1 \text{ else } -1//1$ 
|  $- \rightarrow 0//1$ 

let baryon = function
|  $U\ n \mid D\ n \rightarrow \text{if } n > 0 \text{ then } 1//1 \text{ else } -1//1$ 
|  $Sup\ (-, n) \mid Sdown\ (-, n) \rightarrow \text{if } n > 0 \text{ then } 1//1 \text{ else } -1//1$ 
|  $LQ\ (-, n) \mid LQino\ n \rightarrow \text{if } n > 0 \text{ then } 1//1 \text{ else } -1//1$ 
|  $- \rightarrow 0//1$ 

let charges f =
[ charge f; lepton f; baryon f]

```

We introduce a Boolean type *vc* as a pseudonym for Vertex Conjugator to distinguish between vertices containing complex mixing matrices like the CKM-matrix or the sfermion or neutralino/chargino-mixing matrices, which have to become complex conjugated. The true-option stands for the conjugated vertex, the false-option for the unconjugated vertex.

```

type vc = bool

type constant =
|  $E \mid G$ 
|  $Q\_lepton \mid Q\_up \mid Q\_down \mid Q\_charg$ 
|  $G\_Z \mid G\_CC \mid G\_CCQ\ \text{of } vc \times int \times int$ 
|  $G\_NC\_neutrino \mid G\_NC\_lepton \mid G\_NC\_up \mid G\_NC\_down$ 
|  $I\_Q\_W \mid I\_G\_ZWW \mid G\_WWWW \mid G\_ZZWW \mid G\_PZWW \mid$ 
 $G\_PPWW$ 
|  $G\_strong \mid G\_SS \mid I\_G\_S$ 
|  $G_s$ 
|  $G\_NZN\ \text{of } neu \times neu \mid G\_CZC\ \text{of } char \times char$ 
|  $G\_YUK\_FFS\ \text{of } flavor \times flavor \times shiggs$ 
|  $G\_YUK\_FFP\ \text{of } flavor \times flavor \times phiggs$ 
|  $G\_YUK\_LCN\ \text{of } int$ 
|  $G\_YUK\_UCD\ \text{of } int \times int \mid G\_YUK\_DCU\ \text{of } int \times int$ 

```


G_NHC of $vc \times neu \times char$
 G_YUK_C of $vc \times flavor \times char \times sff \times sfm$
 G_YUK_Q of $vc \times int \times flavor \times char \times sff \times sfm$
 G_YUK_N of $vc \times flavor \times neu \times sff \times sfm$
 G_YUK_G of $vc \times flavor \times sff \times sfm$
 G_NWC of $neu \times char$ | G_CWN of $char \times neu$
 G_CSC of $char \times char \times shiggs$
 G_CPC of $char \times char \times phiggs$
 G_WSQ of $vc \times int \times int \times sfm \times sfm$
 G_SLSNW of $vc \times int \times sfm$
 G_ZSF of $sff \times int \times sfm \times sfm$
 G_CICIS of $neu \times neu \times shiggs$
 G_CICIP of $neu \times neu \times phiggs$
 G_GH_WPC of $phiggs$ | G_GH_WSC of $shiggs$
 G_GH_ZSP of $shiggs \times phiggs$ | G_GH_WWS of $shiggs$
 G_GH_ZZS of $shiggs$ | G_GH_ZCC
 G_GH_GaCC
 G_GH4_ZZPP of $phiggs \times phiggs$
 G_GH4_ZZSS of $shiggs \times shiggs$
 G_GH4_ZZCC | G_GH4_GaGaCC
 G_GH4_ZGaCC | G_GH4_WWCC
 G_GH4_WWPP of $phiggs \times phiggs$
 G_GH4_WWSS of $shiggs \times shiggs$
 G_GH4_ZWSC of $shiggs$
 G_GH4_GaWSC of $shiggs$
 G_GH4_ZWPC of $phiggs$
 G_GH4_GaWPC of $phiggs$
 G_WWSFSF of $sff \times int \times sfm \times sfm$
 G_WPSLSN of $vc \times int \times sfm$
 G_H3_SCC of $shiggs$
 G_H3_SSS of $shiggs \times shiggs \times shiggs$
 G_H3_SPP of $shiggs \times phiggs \times phiggs$
 G_SFSFS of $shiggs \times sff \times int \times sfm \times sfm$
 G_SFSFP of $phiggs \times sff \times int \times sfm \times sfm$
 G_HSNSL of $vc \times int \times sfm$
 G_HSUSD of $vc \times sfm \times sfm \times int \times int$
 G_WPSUSD of $vc \times sfm \times sfm \times int \times int$
 G_WZSUSD of $vc \times sfm \times sfm \times int \times int$
 G_WZSLSN of $vc \times int \times sfm$ | $G_GLISQSQ$
 G_PPSFSF of sff
 G_ZZSFSF of $sff \times int \times sfm \times sfm$ | G_ZPSFSF of $sff \times int \times sfm \times sfm$
 $G_GLZSFSF$ of $sff \times int \times sfm \times sfm$ | $G_GLPSQSQ$
 $G_GLWSUSD$ of $vc \times sfm \times sfm \times int \times int$
 $G_YUK_LQ_S$ of $int \times shiggs \times int$
 $G_YUK_LQ_P$ of $int \times phiggs \times int$
 G_LQ_NEU of $sfm \times int \times int \times neu$
 $G_LQ_EC_UC$ of $vc \times sfm \times int \times int \times int$
 G_LQ_GG of $sfm \times int \times int$
 G_LQ_SSU of $sfm \times sfm \times sfm \times int \times int \times int$
 G_LQ_SSD of $sfm \times sfm \times int \times int \times int$

```

| G_LQ_S of sfm × sfm × int × shiggs × int
| G_LQ_P of sfm × sfm × int × phiggs × int
| G_ZLQ of int × sfm × sfm
| G_ZZLQLQ | G_ZPLQLQ | G_PPLQLQ | G_ZGLQLQ |
G_PGILQLQ | G_NLQC | G_GLGLQLQ

```

Two integer counters for the QCD and EW order of the couplings.

```

type orders = int × int
let orders = function
| _ → (0,0)

```

$$\alpha_{\text{QED}} = \frac{1}{137.0359895} \quad (13.69a)$$

$$\sin^2 \theta_w = 0.23124 \quad (13.69b)$$

Here we must perhaps allow for complex input parameters. So split them into their modulus and their phase. At first, we leave them real; the generalization to complex parameters is obvious.

```

let parameters () =
{ input = [];
  derived = [];
  derived_arrays = [] }

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

```

For the couplings there are generally two possibilities concerning the sign of the covariant derivative.

$$\text{CD}^\pm = \partial_\mu \pm ig T^a A_\mu^a \quad (13.70)$$

The particle data group defines the signs consistently to be positive. Since the convention for that signs also influence the phase definitions of the gaugino/higgsino fields via the off-diagonal entries in their mass matrices it would be the best to adopt that convention.

** REVISED: Compatible with CD+. FB **

```

let electromagnetic_currents_3 g =
[ ((L (-g), Ga, L g), FBF (1, Psibar, V, Psi), Q_lepton);
  ((U (-g), Ga, U g), FBF (1, Psibar, V, Psi), Q_up);
  ((D (-g), Ga, D g), FBF (1, Psibar, V, Psi), Q_down)]

```

** REVISED: Compatible with CD+. FB**

```

let electromagnetic_sfermion_currents g m =
[ ((Ga, Slepton (m, -g), Slepton (m, g)), Vector_Scalar_Scalar 1, Q_lepton);
  ((Ga, Sup (m, -g), Sup (m, g)), Vector_Scalar_Scalar 1, Q_up);
  ((Ga, Sdown (m, -g), Sdown (m, g)), Vector_Scalar_Scalar 1, Q_down)]

```

** REVISED: Compatible with CD+. FB**

```
let electromagnetic_currents_2 c =
  let cc = conj_char c in
  [ ((Chargino cc, Ga, Chargino c), FBF (1, Psibar, V, Psi), Q_charg) ]
```

** REVISED: Compatible with CD+. FB**

```
let neutral_currents g =
  [ ((L (-g), Z, L g), FBF (1, Psibar, VA, Psi), G_NC_lepton);
    ((N (-g), Z, N g), FBF (1, Psibar, VA, Psi), G_NC_neutrino);
    ((U (-g), Z, U g), FBF (1, Psibar, VA, Psi), G_NC_up);
    ((D (-g), Z, D g), FBF (1, Psibar, VA, Psi), G_NC_down)]
```

$$\mathcal{L}_{CC} = \mp \frac{g}{2\sqrt{2}} \sum_i \bar{\psi}_i \gamma^\mu (1 - \gamma_5) (T^+ W_\mu^+ + T^- W_\mu^-) \psi_i, \quad (13.71)$$

where the sign corresponds to CD_\pm , respectively.

** REVISED: Compatible with CD+. **

Remark: The definition with the other sign compared to the SM files comes from the fact that $g_{cc} = 1/(2\sqrt{2})$ is used overwhelmingly often in the SUSY Feynman rules, so that JR decided to use a different definition for g_{cc} in SM and MSSM.

* FB *

```
let charged_currents g h =
  [ ((L (-g), Wm, N g), FBF ((-1), Psibar, VL, Psi), G_CC);
    ((N (-g), Wp, L g), FBF ((-1), Psibar, VL, Psi), G_CC) ]
```

The quark with the inverted generation (the antiparticle) is the outgoing one, the other the incoming. The vertex attached to the outgoing up-quark contains the CKM matrix element *not* complex conjugated, while the vertex with the outgoing down-quark has the conjugated CKM matrix element.

** REVISED: Compatible with CD+. FB **

```
let charged_quark_currents g h =
  [ ((D (-g), Wm, U h), FBF ((-1), Psibar, VL, Psi), G_CCQ (true,g,h));
    ((U (-g), Wp, D h), FBF ((-1), Psibar, VL, Psi), G_CCQ (false,h,g))]
```

** REVISED: Compatible with CD+.FB **

```
let charged_chargino_currents n c =
  let cc = conj_char c in
  [ ((Chargino cc, Wp, Neutralino n),
      FBF (1, Psibar, VLR, Chi), G_CWN (c,n));
    ((Neutralino n, Wm, Chargino c),
      FBF (1, Chibar, VLR, Psi), G_NWC (n,c)) ]
```

** REVISED: Compatible with CD+. FB**

```
let charged_slepton_currents g m =
  [ ((Wm, Slepton (m, -g), Sneutrino g), Vector_Scalar_Scalar (-1), G_SLSNW
      (true,g,m));
    ((Wp, Slepton (m, g), Sneutrino (-g)), Vector_Scalar_Scalar 1, G_SLSNW
      (false,g,m)) ]
```

** REVISED: Compatible with CD+. FB**

```
let charged_squark_currents' g h m1 m2 =
  [ ((Wm, Sup (m1, g), Sdown (m2, -h)), Vector_Scalar_Scalar (-1), G_WSQ
    (true, g, h, m1, m2));
    ((Wp, Sup (m1, -g), Sdown (m2, h)), Vector_Scalar_Scalar 1, G_WSQ
    (false, g, h, m1, m2)) ]
let charged_squark_currents g h =
  List.flatten (Product.list2 (charged_squark_currents' g h) [M1; M2] [M1; M2] )
```

** REVISED: Compatible with CD+. FB **

```
let neutral_sfermion_currents' g m1 m2 =
  [ ((Z, Slepton (m1, -g), Slepton (m2, g)), Vector_Scalar_Scalar (-1),
    G_ZSF (SL, g, m1, m2));
    ((Z, Sup (m1, -g), Sup (m2, g)), Vector_Scalar_Scalar (-1),
    G_ZSF (SU, g, m1, m2));
    ((Z, Sdown (m1, -g), Sdown (m2, g)), Vector_Scalar_Scalar (-1),
    G_ZSF (SD, g, m1, m2))]
let neutral_sfermion_currents g =
  List.flatten (Product.list2 (neutral_sfermion_currents'
    g) [M1; M2] [M1; M2]) @
  [ ((Z, Sneutrino (-g), Sneutrino g), Vector_Scalar_Scalar (-1),
    G_ZSF (SN, g, M1, M1)) ]
```

The reality of the coupling of the Z-boson to two identical neutralinos makes the vector part of the coupling vanish. So we distinguish them not by the name but by the structure of the couplings.

** REVISED: Compatible with CD+. FB**

```
let neutral_Z (n, m) =
  [ ((Neutralino n, Z, Neutralino m), FBF (1, Chibar, VA, Chi),
    (G_NZN (n, m))) ]
```

** REVISED: Compatible with CD+. FB**

```
let charged_Z c1 c2 =
  let cc1 = conj_char c1 in
  ((Chargino cc1, Z, Chargino c2), FBF ((-1), Psibar, VA, Psi),
    G_CZC (c1, c2))
```

** REVISED: Compatible with CD+. Remark: This is pure octet. FB**

```
let yukawa_v =
  [ (Gluino, Gl, Gluino), FBF (1, Chibar, V, Chi), Gs]
```

** REVISED: Independent of the sign of CD. **

** REVISED: Felix Braam: Compact version using new COMBOS + FF-Couplings

```
let yukawa_higgs_FFS f s =
  [ ((conjgate f, SHiggs s, f), FBF (1, Psibar, S, Psi),
    G_YUK_FFS (conjgate f, f, s))]
let yukawa_higgs_FFP f p =
  [ ((conjgate f, PHiggs p, f), FBF (1, Psibar, P, Psi),
    G_YUK_FFP (conjgate f, f, p))]
```

JR: Only the first charged Higgs.

```

let yukawa_higgs_NLC g =
  [ ((N (-g), CHiggs HC1, L g), FBF (1, Psibar, Coupling.SR, Psi),
      G_YUK_LCN g);
    ((L (-g), CHiggs HC1c, N g), FBF (1, Psibar, Coupling.SL, Psi),
      G_YUK_LCN g) ]

let yukawa_higgs g =
  yukawa_higgs_NLC g @
  List.flatten ( Product.list2 yukawa_higgs_FFS [L g; U g; D g] [S1; S2; S3] ) @
  List.flatten ( Product.list2 yukawa_higgs_FFP [L g; U g; D g] [P1; P2] )

```

JR: Only the first charged Higgs.

** REVISED: Independent of the sign of CD. FB**

```

let yukawa_higgs_quark (g, h) =
  [ ((U (-g), CHiggs HC1, D h), FBF (1, Psibar, SLR, Psi),
      G_YUK_UCD (g, h));
    ((D (-h), CHiggs HC1c, U g), FBF (1, Psibar, SLR, Psi),
      G_YUK_DCU (g, h)) ]

```

** REVISED: Compatible with CD+.FB

** REVISED: Compact version using new COMBOS

```

let yukawa_shiggs_2 c1 c2 s =
  let cc1 = conj_char c1 in
    ((Chargino cc1, SHiggs s, Chargino c2), FBF (1, Psibar, SLR, Psi),
      G_CSC (c1, c2, s))

let yukawa_phiggs_2 c1 c2 p =
  let cc1 = conj_char c1 in
    ((Chargino cc1, PHiggs p, Chargino c2), FBF (1, Psibar, SLR, Psi),
      G_CPC (c1, c2, p))

let yukawa_higgs_2 =
  Product.list3 yukawa_shiggs_2 [C1; C2] [C1; C2] [S1; S2; S3] @
  Product.list3 yukawa_phiggs_2 [C1; C2] [C1; C2] [P1; P2]

```

JR: Only the first charged Higgs.

** REVISED: Compatible with CD+.FB **

```

let higgs_charg_neutr n c =
  let cc = conj_char c in
    [ ((Neutralino n, CHiggs HC1c, Chargino c), FBF (-1, Chibar, SLR, Psi),
        G_NHC (false, n, c));
      ((Chargino cc, CHiggs HC1, Neutralino n), FBF (-1, Psibar, SLR, Chi),
        G_NHC (true, n, c)) ]

```

** REVISED: Compatible with CD+. FB**

** REVISED: Compact version using new COMBOS

```

let shiggs_neutr (n, m, s) =
  ((Neutralino n, SHiggs s, Neutralino m), FBF (1, Chibar, SP, Chi),
    G_CICIS (n, m, s))

let phiggs_neutr (n, m, p) =

```

```

((Neutralino n, PHiggs p, Neutralino m), FBF (1, Chibar, SP, Chi),
  G_CICIP (n, m, p))

let higgs_neutr =
  List.map shiggs_neutr (two_and_one [N1; N2; N3; N4; N5] [S1; S2; S3]) @
  List.map phiggs_neutr (two_and_one [N1; N2; N3; N4; N5] [P1; P2])

** REVISED: Compatible with CD+. FB**

let yukawa_n_2 n m g =
  [ ((Neutralino n, Slepton (m, -g), L g), FBF (1, Chibar, SLR, Psi),
      G_YUK_N (true, L g, n, SL, m));
    ((L (-g), Slepton (m, g), Neutralino n), FBF (1, Psibar, SLR, Chi),
      G_YUK_N (false, L g, n, SL, m));
    ((Neutralino n, Sup (m, -g), U g), FBF (1, Chibar, SLR, Psi),
      G_YUK_N (true, U g, n, SU, m));
    ((U (-g), Sup (m, g), Neutralino n), FBF (1, Psibar, SLR, Chi),
      G_YUK_N (false, U g, n, SU, m));
    ((Neutralino n, Sdown (m, -g), D g), FBF (1, Chibar, SLR, Psi),
      G_YUK_N (true, D g, n, SD, m));
    ((D (-g), Sdown (m, g), Neutralino n), FBF (1, Psibar, SLR, Chi),
      G_YUK_N (false, D g, n, SD, m)) ]

let yukawa_n_3 n g =
  [ ((Neutralino n, Sneutrino (-g), N g), FBF (1, Chibar, SLR, Psi),
      G_YUK_N (true, N g, n, SN, M1));
    ((N (-g), Sneutrino g, Neutralino n), FBF (1, Psibar, SLR, Chi),
      G_YUK_N (false, N g, n, SN, M1)) ]

let yukawa_n_5 g m =
  [ ((U (-g), Sup (m, g), Gluino), FBF (1, Psibar, SLR, Chi),
      G_YUK_G (false, U g, SU, m));
    ((D (-g), Sdown (m, g), Gluino), FBF (1, Psibar, SLR, Chi),
      G_YUK_G (false, D g, SD, m));
    ((Gluino, Sup (m, -g), U g), FBF (1, Chibar, SLR, Psi),
      G_YUK_G (true, U g, SU, m));
    ((Gluino, Sdown (m, -g), D g), FBF (1, Chibar, SLR, Psi),
      G_YUK_G (true, D g, SD, m))]

let yukawa_n =
  List.flatten (Product.list3 yukawa_n_2 [N1; N2; N3; N4; N5] [M1; M2] [1; 2; 3]) @
  List.flatten (Product.list2 yukawa_n_3 [N1; N2; N3; N4; N5] [1; 2; 3]) @
  List.flatten (Product.list2 yukawa_n_5 [1; 2; 3] [M1; M2])

** REVISED: Compatible with CD+.FB **

let yukawa_c_2 c g =
  let cc = conj_char c in
  [ ((L (-g), Sneutrino g, Chargino cc), BBB (1, Psibar, SLR,
      Psibar), G_YUK_C (true, L g, c, SN, M1));
    ((Chargino c, Sneutrino (-g), L g), PBP (1, Psi, SLR, Psi),
      G_YUK_C (false, L g, c, SN, M1)) ]

let yukawa_c_3 c m g =
  let cc = conj_char c in
  [ ((N (-g), Slepton (m, g), Chargino c), FBF (1, Psibar, SLR,

```

```

      Psi), G_YUK_C (true, N g, c, SL, m));
      ((Chargino cc, Slepton (m, -g), N g), FBF (1, Psibar, SLR,
      Psi), G_YUK_C (false, N g, c, SL, m)) ]
let yukawa_c c =
  ThoList.flatmap (yukawa_c-2 c) [1; 2; 3] @
  List.flatten (Product.list2 (yukawa_c-3 c) [M1; M2] [1; 2; 3])
** REVISED: Compatible with CD+. FB**

let yukawa_cq' c (g, h) m =
  let cc = conj_char c in
  [ ((Chargino c, Sup (m, -g), D h), PBP (1, Psi, SLR, Psi),
    G_YUK_Q (false, g, D h, c, SU, m));
    ((D (-h), Sup (m, g), Chargino cc), BBB (1, Psibar, SLR, Psibar),
    G_YUK_Q (true, g, D h, c, SU, m));
    ((Chargino cc, Sdown (m, -g), U h), FBF (1, Psibar, SLR, Psi),
    G_YUK_Q (true, g, U h, c, SD, m));
    ((U (-h), Sdown (m, g), Chargino c), FBF (1, Psibar, SLR, Psi),
    G_YUK_Q (false, g, U h, c, SD, m)) ]
let yukawa_cq c =
  if Flags.ckm_present then
    List.flatten (Product.list2 (yukawa_cq' c) [(1, 1); (1, 2); (2, 1); (2, 2); (1, 3); (2, 3); (3, 3); (3, 2); (3, 1)] [M
  else
    List.flatten (Product.list2 (yukawa_cq' c) [(1, 1); (2, 2); (3, 3)] [M1; M2])
** REVISED: Compatible with CD+. Remark: Singlet and octet gluon ex-
change. The coupling is divided by sqrt(2) to account for the correct normal-
ization of the Lie algebra generators. **FB

let col_currents g =
  [ ((D (-g), Gl, D g), FBF ((-1), Psibar, V, Psi), Gs);
    ((U (-g), Gl, U g), FBF ((-1), Psibar, V, Psi), Gs)]
** REVISED: Compatible with CD+. Remark: Singlet and octet gluon ex-
change. The coupling is divided by sqrt(2) to account for the correct normal-
ization of the Lie algebra generators. **FB
* LQ-coupl. **DW*

let chg = function
  | M1 → M2 | M2 → M1

* LQ - Yuk's *

let yuk_lqino_se_uc1' g1 g2 g3 m =
  let cm = chg m in
  [ ((U (-g3), Slepton (m, -g2), LQino g1), FBF (1, Psibar, SLR, Psi),
    G_LQ_EC_UC (true, cm, g1, g2, g3)) ]

let yuk_lqino_se_uc1 g1 g2 g3 =
  ThoList.flatmap (yuk_lqino_se_uc1' g1 g2 g3) [M1; M2]

let yuk_lqino_se_uc2' g1 g2 g3 m =
  let cm = chg m in
  [ ((LQino (-g1), Slepton (m, g2), U g3), FBF (1, Psibar, SLR, Psi),
    G_LQ_EC_UC (false, cm, g1, g2, g3)) ]

```

```

let yuk_lqino_se_uc2 g1 g2 g3 =
  ThoList.flatmap (yuk_lqino_se_uc2' g1 g2 g3) [M1; M2]

let yuk_lqino_sn_dc1 g1 g2 g3 =
  [ ((D (-g3), Sneutrino (-g2), LQino g1), FBF (-1, Psibar, SLR, Psi),
      G_LQ_EC_UC (true, M2, g1, g2, g3)) ]

let yuk_lqino_sn_dc2 g1 g2 g3 =
  [ ((LQino (-g1), Sneutrino g2, D g3), FBF (-1, Psibar, SLR, Psi),
      G_LQ_EC_UC (false, M2, g1, g2, g3)) ]

let yuk_lqino_ec_su1' g1 g2 g3 m =
  let cm = chg m in
  [ ((LQino (-g1), Sup (m, g3), L g2), FBF (1, Psibar, SLR, Psi),
      G_LQ_EC_UC (true, cm, g1, g2, g3)) ]

let yuk_lqino_ec_su1 g1 g2 g3 =
  ThoList.flatmap (yuk_lqino_ec_su1' g1 g2 g3) [M1; M2]

let yuk_lqino_ec_su2' g1 g2 g3 m =
  let cm = chg m in
  [ ((L (-g2), Sup (m, -g3), LQino (g1)), FBF (1, Psibar, SLR, Psi),
      G_LQ_EC_UC (false, cm, g1, g2, g3)) ]

let yuk_lqino_ec_su2 g1 g2 g3 =
  ThoList.flatmap (yuk_lqino_ec_su2' g1 g2 g3) [M1; M2]

let yuk_lqino_nc_sd1 g1 g2 g3 =
  [ ((LQino (-g1), Sdown (M1, g3), N g2), FBF (-1, Psibar, SLR, Psi),
      G_LQ_EC_UC (true, M2, g1, g2, g3)) ]

let yuk_lqino_nc_sd2 g1 g2 g3 =
  [ ((N (-g2), Sdown (M1, -g3), LQino (g1)), FBF (-1, Psibar, SLR, Psi),
      G_LQ_EC_UC (false, M2, g1, g2, g3)) ]

let yuk_lq_ec_uc' g1 g2 g3 m =
  [ ((L (-g2), LQ (m, g1), U (-g3)), BBB (1, Psibar, SLR, Psibar),
      G_LQ_EC_UC (false, m, g1, g2, g3)) ]

let yuk_lq_ec_uc g1 g2 g3 =
  ThoList.flatmap (yuk_lq_ec_uc' g1 g2 g3) [M1; M2]

let yuk_lq_ec_uc2' g1 g2 g3 m =
  [ ((L (g2), LQ (m, -g1), U (g3)), PBP (1, Psi, SLR, Psi),
      G_LQ_EC_UC (true, m, g1, g2, g3)) ]

let yuk_lq_ec_uc2 g1 g2 g3 =
  ThoList.flatmap (yuk_lq_ec_uc2' g1 g2 g3) [M1; M2]

let yuk_lq_nc_dc g1 g2 g3 =
  [ ((N (-g2), LQ (M2, g1), D (-g3)), BBB (-1, Psibar, SLR, Psibar),
      G_LQ_EC_UC (false, M2, g1, g2, g3)) ]

let yuk_lq_nc_dc2 g1 g2 g3 =
  [ ((N (g2), LQ (M2, -g1), D (g3)), PBP (-1, Psi, SLR, Psi),
      G_LQ_EC_UC (true, M2, g1, g2, g3)) ]

```

** Daniel Wiesler: LQ - F-Term w/ vev **


```

let lq_se_su' g1 g2 g3 m1 m2 m3 =
  [ ((LQ (m1, g1), Slepton (m2, -g2), Sup (m3, -g3)), Scalar_Scalar_Scalar 1,
    G_LQ_SSU (m1, m2, m3, g1, g2, g3)) ]

let lq_se_su g1 g2 g3 =
  List.flatten (Product.list3 (lq_se_su' g1 g2 g3) [M1; M2] [M1; M2] [M1; M2] )

let lq_snu_sd' g1 g2 g3 m1 m2 =
  [ ((LQ (m1, g1), Sdown (m2, -g2), Sneutrino (-g3)), Scalar_Scalar_Scalar 1,
    G_LQ_SSD (m1, m2, g1, g2, g3)) ]

let lq_snu_sd g1 g2 g3 =
  List.flatten (Product.list2 (lq_snu_sd' g1 g2 g3) [M1; M2] [M1; M2] )

** Daniel Wiesler: LQ - Higgs **

let lq_shiggs' g1 s g2 m1 m2 =
  [ ((LQ (m1, g1), SHiggs s, LQ (m2, -g2)), Scalar_Scalar_Scalar 1, G_LQ_S (m1, m2, g1, s, g2))]

let lq_shiggs g1 s g2 =
  List.flatten ( Product.list2 (lq_shiggs' g1 s g2) [M1; M2] [M1; M2])

let lq_phiggs' g1 p g2 m1 m2 =
  [ ((LQ (m1, g1), PHiggs p, LQ (m2, -g2)), Scalar_Scalar_Scalar 1, G_LQ_P (m1, m2, g1, p, g2))]

let lq_phiggs g1 p g2 =
  List.flatten ( Product.list2 (lq_phiggs' g1 p g2) [M1; M2] [M1; M2])

let yuk_lqino_shiggs g1 s g2 =
  [ ((LQino (-g1), SHiggs s, LQino g2), FBF (1, Psibar, SLR, Psi),
    G_YUK_LQ_S (g1, s, g2)) ]

let yuk_lqino_phiggs g1 p g2 =
  [ ((LQino (-g1), PHiggs p, LQino g2), FBF (1, Psibar, SLR, Psi),
    G_YUK_LQ_P (g1, p, g2)) ]

** Daniel Wiesler: LQ - Neutralinos. **

let lqino_lq_neu' n g1 g2 m =
  [ ((Neutralino n, LQ (m, -g1), LQino g2), FBF (1, Chibar, SLR, Psi),
    G_LQ_NEU (m, g1, g2, n)) ]

let lqino_lq_neu n g1 g2 =
  ThoList.flatmap (lqino_lq_neu' n g1 g2) [M1; M2]

let lqino_lq_neu2' n g1 g2 m =
  [ ((LQino (-g2), LQ (m, g1), Neutralino n), FBF (1, Psibar, SLR, Chi),
    G_LQ_NEU (m, g1, g2, n)) ]

let lqino_lq_neu2 n g1 g2 =
  ThoList.flatmap (lqino_lq_neu2' n g1 g2) [M1; M2]

** Daniel Wiesler: LQ-LQino-Gluino **

let lqino_lq_gg' g1 g2 m =
  [ ((Gluino, LQ (m, -g1), LQino g2), FBF (1, Chibar, SLR, Psi),
    G_LQ_GG (m, g1, g2)) ]

let lqino_lq_gg g1 g2 =

```

```

    ThoList.flatmap (lqino_lq_gg' g1 g2) [M1; M2]
** Daniel Wiesler: LQ - Gauge **
let col_lqino_currents g =
  [ ((LQino (-g), Gl, LQino g), FBF ((-1), Psibar, V, Psi), Gs)]
let neutr_lqino_current g =
  [ ((LQino (-g), Z, LQino g), FBF (1, Psibar, V, Psi), G_NLQC)]
let col_lq_currents m g =
  [ ((Gl, LQ (m, -g), LQ (m, g)), Vector_Scalar_Scalar (-1), Gs)]
let lq_neutr_Z g m1 m2 =
  [ ((Z, LQ (m1, -g), LQ (m2, g)), Vector_Scalar_Scalar (-1), G_ZLQ (g, m1, m2))]
let em_lq_currents g m =
  [ ((Ga, LQ (m, -g), LQ (m, g)), Vector_Scalar_Scalar 1, Q_down)]
let em_lqino_currents g =
  [ ((LQino (-g), Ga, LQino g), FBF (1, Psibar, V, Psi), Q_down)]
let gluon2_lq2' g m =
  [ ((LQ (m, g), LQ (m, -g), Gl, Gl), Scalar2_Vector2 2, G_GlGlLQLQ)]
let gluon2_lq2 g =
  ThoList.flatmap (gluon2_lq2' g) [M1; M2]
let lq_gauge4' g m =
  [ ((Z, Z, LQ (m, g), LQ (m, -g)), Scalar2_Vector2 1, G_ZZLQLQ);
    ((Z, Ga, LQ (m, g), LQ (m, -g)), Scalar2_Vector2 1, G_ZPLQLQ);
    ((Ga, Ga, LQ (m, g), LQ (m, -g)), Scalar2_Vector2 1, G_PPLQLQ)]
let lq_gauge4 g =
  ThoList.flatmap (lq_gauge4' g) [M1; M2]
let lq_gg_gauge2' g m =
  [ ((Z, Gl, LQ (m, g), LQ (m, -g)), Scalar2_Vector2 1, G_ZGILQLQ);
    ((Ga, Gl, LQ (m, g), LQ (m, -g)), Scalar2_Vector2 1, G_PGILQLQ)]
let lq_gg_gauge2 g =
  ThoList.flatmap (lq_gg_gauge2' g) [M1; M2]
let col_sfermion_currents g m =
  [ ((Gl, Sup (m, -g), Sup (m, g)), Vector_Scalar_Scalar (-1), Gs);
    ((Gl, Sdown (m, -g), Sdown (m, g)), Vector_Scalar_Scalar (-1), Gs)]
** REVISED: Compatible with CD+. **FB
let triple_gauge =
  [ ((Ga, Wm, Wp), Gauge_Gauge_Gauge 1, I_Q_W);
    ((Z, Wm, Wp), Gauge_Gauge_Gauge 1, I_G_ZWW);
    ((Gl, Gl, Gl), Gauge_Gauge_Gauge 1, I_G_S)]
** REVISED: Independent of the sign of CD. **FB
let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]
let minus_gauge4 = Vector4 [(-2, C_13_42); (1, C_12_34); (1, C_14_23)]
let quartic_gauge =
  [ (Wm, Wp, Wm, Wp), gauge4, G_WWWW;

```

```

(Wm, Z, Wp, Z), minus_gauge4, G_ZZWW;
(Wm, Z, Wp, Ga), minus_gauge4, G_PZWW;
(Wm, Ga, Wp, Ga), minus_gauge4, G_PPWW;
(Gl, Gl, Gl, Gl), gauge4, G_SS]

```

The *Scalar_Vector_Vector* couplings do not depend on the choice of the sign of the covariant derivative since they are quadratic in the gauge couplings.

JR: Only the first charged Higgs.

** REVISED: Compatible with CD+. **

** Revision: 2005-03-10: first two vertices corrected. **

** REVISED: Felix Braam: Compact version using new COMBOS

** REVISED: Felix Braam: Couplings adjusted to FF-convention

```

let gauge_higgs_WPC p =
  [ ((Wm, CHiggs HC1, PHiggs p), Vector_Scalar_Scalar 1, G_GH_WPC p);
    ((Wp, CHiggs HC1c, PHiggs p), Vector_Scalar_Scalar 1, G_GH_WPC p)]
let gauge_higgs_WSC s =
  [ ((Wm, CHiggs HC1, SHiggs s), Vector_Scalar_Scalar 1, G_GH_WSC s);
    ((Wp, CHiggs HC1c, SHiggs s), Vector_Scalar_Scalar (-1), G_GH_WSC s)]
let gauge_higgs_ZSP s p =
  [ ((Z, SHiggs s, PHiggs p), Vector_Scalar_Scalar 1, G_GH_ZSP (s, p))]
let gauge_higgs_WWS s =
  [ ((SHiggs s, Wp, Wm), Scalar_Vector_Vector 1, G_GH_WWS s)]
let gauge_higgs_ZZS s =
  [ ((SHiggs s, Z, Z), Scalar_Vector_Vector 1, G_GH_ZZS s)]
let gauge_higgs_ZCC =
  [ ((Z, CHiggs HC1, CHiggs HC1c), Vector_Scalar_Scalar 1, G_GH_ZCC )]
let gauge_higgs_GaCC =
  [ ((Ga, CHiggs HC1, CHiggs HC1c), Vector_Scalar_Scalar 1, G_GH_GaCC )]
let gauge_higgs =
  ThoList.flatmap gauge_higgs_WPC [P1; P2] @
  ThoList.flatmap gauge_higgs_WSC [S1; S2; S3] @
  List.flatten (Product.list2 gauge_higgs_ZSP [S1; S2; S3] [P1; P2]) @
  List.map gauge_higgs_WWS [S1; S2; S3] @
  List.map gauge_higgs_ZZS [S1; S2; S3] @
  [gauge_higgs_ZCC] @ [gauge_higgs_GaCC]

```

** REVISED: Compact version using new COMBOS

** REVISED: Couplings adjusted to FF-convention

```

let gauge_higgs4_ZZPP (p1, p2) =
  ((PHiggs p1, PHiggs p2, Z, Z), Scalar2_Vector2 1, G_GH4_ZZPP (p1, p2))
let gauge_higgs4_ZZSS (s1, s2) =
  ((SHiggs s1, SHiggs s2, Z, Z), Scalar2_Vector2 1, G_GH4_ZZSS (s1, s2))

```

JR: Only the first charged Higgs.

```

let gauge_higgs4_ZZCC =
  ((CHiggs HC1, CHiggs HC1c, Z, Z), Scalar2_Vector2 1, G_GH4_ZZCC)
let gauge_higgs4_GaGaCC =
  ((CHiggs HC1, CHiggs HC1c, Ga, Ga), Scalar2_Vector2 1, G_GH4_GaGaCC)

```

```

let gauge_higgs4_ZGaCC =
  ((CHiggs HC1, CHiggs HC1c, Ga, Z), Scalar2_Vector2 1, G_GH4_ZGaCC)
let gauge_higgs4_WWCC =
  ((CHiggs HC1, CHiggs HC1c, Wp, Wm), Scalar2_Vector2 1, G_GH4_WWCC)
let gauge_higgs4_WWPP (p1, p2) =
  ((PHiggs p1, PHiggs p2, Wp, Wm), Scalar2_Vector2 1, G_GH4_WWPP (p1, p2))
let gauge_higgs4_WWSS (s1, s2) =
  ((SHiggs s1, SHiggs s2, Wp, Wm), Scalar2_Vector2 1, G_GH4_WWSS (s1, s2))

```

JR: Only the first charged Higgs.

```

let gauge_higgs4_ZWSC s =
  [((CHiggs HC1, SHiggs s, Wm, Z), Scalar2_Vector2 1, G_GH4_ZWSC s);
   ((CHiggs HC1c, SHiggs s, Wp, Z), Scalar2_Vector2 1, G_GH4_ZWSC s)]
let gauge_higgs4_GaWSC s =
  [((CHiggs HC1, SHiggs s, Wm, Ga), Scalar2_Vector2 1, G_GH4_GaWSC s);
   ((CHiggs HC1c, SHiggs s, Wp, Ga), Scalar2_Vector2 1, G_GH4_GaWSC s)]
let gauge_higgs4_ZWPC p =
  [((CHiggs HC1, PHiggs p, Wm, Z), Scalar2_Vector2 1, G_GH4_ZWPC p);
   ((CHiggs HC1c, PHiggs p, Wp, Z), Scalar2_Vector2 (-1), G_GH4_ZWPC p)]
let gauge_higgs4_GaWPC p =
  [((CHiggs HC1, PHiggs p, Wm, Ga), Scalar2_Vector2 1, G_GH4_GaWPC p);
   ((CHiggs HC1c, PHiggs p, Wp, Ga), Scalar2_Vector2 (-1),
    G_GH4_GaWPC p)]
let gauge_higgs4 =
  List.map gauge_higgs4_ZZPP (pairs [P1; P2]) @
  List.map gauge_higgs4_ZZSS (pairs [S1; S2; S3]) @
  [gauge_higgs4_ZZCC] @ [gauge_higgs4_GaGaCC] @
  [gauge_higgs4_ZGaCC] @ [gauge_higgs4_WWCC] @
  List.map gauge_higgs4_WWPP (pairs [P1; P2]) @
  List.map gauge_higgs4_WWSS (pairs [S1; S2; S3]) @
  ThoList.flatmap gauge_higgs4_ZWSC [S1; S2; S3] @
  ThoList.flatmap gauge_higgs4_GaWSC [S1; S2; S3] @
  ThoList.flatmap gauge_higgs4_ZWPC [P1; P2] @
  ThoList.flatmap gauge_higgs4_GaWPC [P1; P2]

```

** Added by Felix Braam. **

```

let gauge_sfermion4' g m1 m2 =
  [((Wp, Wm, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1,
    G_WWSFSF (SL, g, m1, m2));
   ((Z, Ga, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1,
    G_ZPSFSF (SL, g, m1, m2));
   ((Z, Z, Slepton (m1, g), Slepton (m2, -g)), Scalar2_Vector2 1,
    G_ZZSFSF (SL, g, m1, m2));
   ((Wp, Wm, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_WWSFSF
    (SU, g, m1, m2));
   ((Wp, Wm, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1, G_WWSFSF
    (SD, g, m1, m2));

```

```

((Z, Z, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_ZZSFSSF
  (SU, g, m1, m2));
((Z, Z, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1, G_ZZSFSSF
  (SD, g, m1, m2));
((Z, Ga, Sup (m1, g), Sup (m2, -g)), Scalar2_Vector2 1, G_ZPSFSSF
  (SU, g, m1, m2));
((Z, Ga, Sdown (m1, g), Sdown (m2, -g)), Scalar2_Vector2 1, G_ZPSFSSF
  (SD, g, m1, m2)) ]

let gauge_sfermion4'' g m =
[ ((Wp, Ga, Slepton (m, g), Sneutrino (-g)), Scalar2_Vector2 1,
  G_WPSLSN (false, g, m));
  ((Wm, Ga, Slepton (m, -g), Sneutrino g), Scalar2_Vector2 1,
  G_WPSLSN (true, g, m));
  ((Wp, Z, Slepton (m, g), Sneutrino (-g)), Scalar2_Vector2 1,
  G_WZLSN (false, g, m));
  ((Wm, Z, Slepton (m, -g), Sneutrino g), Scalar2_Vector2 1,
  G_WZLSN (true, g, m));
  ((Ga, Ga, Slepton (m, g), Slepton (m, -g)), Scalar2_Vector2 1, G_PPSFSSF SL);
  ((Ga, Ga, Sup (m, g), Sup (m, -g)), Scalar2_Vector2 1, G_PPSFSSF SU);
  ((Ga, Ga, Sdown (m, g), Sdown (m, -g)), Scalar2_Vector2 1, G_PPSFSSF SD)]

let gauge_sfermion4 g =
List.flatten (Product.list2 (gauge_sfermion4' g) [M1; M2] [M1; M2]) @
ThoList.flatmap (gauge_sfermion4'' g) [M1; M2] @
[ ((Wp, Wm, Sneutrino g, Sneutrino (-g)), Scalar2_Vector2 1, G_WWSFSSF
  (SN, g, M1, M1));
  ((Z, Z, Sneutrino g, Sneutrino (-g)), Scalar2_Vector2 1, G_ZZSFSSF
  (SN, g, M1, M1)) ]

** Modified by Felix Braam. **

let gauge_squark4'' g h m1 m2 =
[ ((Wp, Ga, Sup (m1, -g), Sdown (m2, h)), Scalar2_Vector2 1, G_WPSUSD
  (false, m1, m2, g, h));
  ((Wm, Ga, Sup (m1, g), Sdown (m2, -h)), Scalar2_Vector2 1, G_WPSUSD
  (true, m1, m2, g, h));
  ((Wp, Z, Sup (m1, -g), Sdown (m2, h)), Scalar2_Vector2 1, G_WZSUSD
  (false, m1, m2, g, h));
  ((Wm, Z, Sup (m1, g), Sdown (m2, -h)), Scalar2_Vector2 1, G_WZSUSD
  (true, m1, m2, g, h)) ]

let gauge_squark4' g h = List.flatten (Product.list2 (gauge_squark4'' g h)
  [M1; M2] [M1; M2])

let gauge_squark4 =
if Flags.ckm_present then
  List.flatten (Product.list2 gauge_squark4' [1; 2; 3] [1; 2; 3])
else
  ThoList.flatmap (fun g → gauge_squark4' g g) [1; 2; 3]

let gluon_w_squark'' g h m1 m2 =
[ ((Gl, Wp, Sup (m1, -g), Sdown (m2, h)),
  Scalar2_Vector2 1, G_GlWSUSD (false, m1, m2, g, h));
  ((Gl, Wm, Sup (m1, g), Sdown (m2, -h)),
  Scalar2_Vector2 1, G_GlWSUSD (true, m1, m2, g, h)) ]

```

```

      Scalar2_Vector2 1, G_GlWSUSD (true,m1,m2,g,h)) ]
let gluon_w_squark' g h =
  List.flatten (Product.list2 (gluon_w_squark'' g h) [M1;M2] [M1;M2])
let gluon_w_squark =
  if Flags.ckm-present then
    List.flatten (Product.list2 gluon_w_squark' [1;2;3] [1;2;3])
  else
    ThoList.flatmap (fun g → gluon_w_squark' g g) [1;2;3]
** Modified by Felix Braam. **

let gluon_gauge_squark' g m1 m2 =
  [ ((Gl, Z, Sup (m1,g), Sup (m2,-g)),
    Scalar2_Vector2 2, G_GLZSFSF (SU,g,m1,m2));
    ((Gl, Z, Sdown (m1,g), Sdown (m2,-g)),
    Scalar2_Vector2 2, G_GLZSFSF (SD,g,m1,m2)) ]
let gluon_gauge_squark'' g m =
  [ ((Gl, Ga, Sup (m,g), Sup (m,-g)), Scalar2_Vector2 2, G_GLPSQSQ);
    ((Gl, Ga, Sdown (m,g), Sdown (m,-g)), Scalar2_Vector2 (-1), G_GLPSQSQ) ]
** Modified by Felix Braam. **

let gluon_gauge_squark g =
  List.flatten (Product.list2 (gluon_gauge_squark' g) [M1;M2] [M1;M2]) @
  ThoList.flatmap (gluon_gauge_squark'' g) [M1;M2]
let gluon2_squark2' g m =
  [ ((Gl, Gl, Sup (m,g), Sup (m,-g)), Scalar2_Vector2 2, G_GLGLSQSQ);
    ((Gl, Gl, Sdown (m,g), Sdown (m,-g)), Scalar2_Vector2 2, G_GLGLSQSQ) ]
let gluon2_squark2 g =
  ThoList.flatmap (gluon2_squark2' g) [M1;M2]
JR: Only the first charged Higgs.
** REVISED: Independent of the sign of CD. **
** REVISED: Felix Braam: Compact version using new COMBOS
** REVISED: Felix Braam: Couplings adjusted to FF-convention

let higgs_SCC s =
  ((CHiggs HC1, CHiggs HC1c, SHiggs s), Scalar_Scalar_Scalar 1,
   G_H3_SCC s)
let higgs_SSS (s1,s2,s3) =
  ((SHiggs s1, SHiggs s2, SHiggs s3), Scalar_Scalar_Scalar 1,
   G_H3_SSS (s1,s2,s3))
let higgs_SPP (p1,p2,s) =
  ((SHiggs s, PHiggs p1, PHiggs p2), Scalar_Scalar_Scalar 1,
   G_H3_SPP (s,p1,p2))

let higgs =
  List.map higgs_SCC [S1;S2;S3]@
  List.map higgs_SSS (triples [S1;S2;S3])@
  List.map higgs_SPP (two_and_one [P1;P2] [S1;S2;S3])

let higgs4 = []
(* The vertices of the type Higgs - Sfermion - Sfermion are independent of the
choice of the CD sign since they are quadratic in the gauge coupling. *)

```

JR: Only the first charged Higgs.

** REVISED: Independent of the sign of CD. **

```

let higgs_sneutrino' s g =
  ((SHiggs s, Sneutrino g, Sneutrino (-g)), Scalar_Scalar_Scalar 1,
   G_SFSSFS (s, SN, g, M1, M1))
let higgs_sneutrino'' g m =
  [((CHiggs HC1, Sneutrino (-g), Slepton (m, g)),
    Scalar_Scalar_Scalar 1, G_HSNSL (false, g, m));
   ((CHiggs HC1c, Sneutrino g, Slepton (m, -g)), Scalar_Scalar_Scalar 1,
    G_HSNSL (true, g, m))]
let higgs_sneutrino =
  Product.list2 higgs_sneutrino' [S1; S2; S3] [1; 2; 3] @
  List.flatten ( Product.list2 higgs_sneutrino'' [1; 2; 3] [M1; M2] )

```

Under the assumption that there is no mixing between the left- and right-handed sfermions for the first two generations there is only a coupling of the form Higgs - sfermion1 - sfermion2 for the third generation. All the others are suppressed by m_f/M_W .

** REVISED: Independent of the sign of CD. **

```

let higgs_sfermion_S s g m1 m2 =
  [((SHiggs s, Slepton (m1, g), Slepton (m2, -g)), Scalar_Scalar_Scalar 1,
    G_SFSSFS (s, SL, g, m1, m2));
   ((SHiggs s, Sup (m1, g), Sup (m2, -g)), Scalar_Scalar_Scalar 1,
    G_SFSSFS (s, SU, g, m1, m2));
   ((SHiggs s, Sdown (m1, g), Sdown (m2, -g)), Scalar_Scalar_Scalar 1,
    G_SFSSFS (s, SD, g, m1, m2))]
let higgs_sfermion' g m1 m2 =
  (higgs_sfermion_S S1 g m1 m2) @ (higgs_sfermion_S S2 g m1 m2) @ (higgs_sfermion_S S3 g m1 m2)
let higgs_sfermion_P p g m1 m2 =
  [((PHiggs p, Slepton (m1, g), Slepton (m2, -g)), Scalar_Scalar_Scalar 1,
    G_SFSSFP (p, SL, g, m1, m2));
   ((PHiggs p, Sup (m1, g), Sup (m2, -g)), Scalar_Scalar_Scalar 1,
    G_SFSSFP (p, SU, g, m1, m2));
   ((PHiggs p, Sdown (m1, g), Sdown (m2, -g)), Scalar_Scalar_Scalar 1,
    G_SFSSFP (p, SD, g, m1, m2))]
let higgs_sfermion'' g m1 m2 =
  (higgs_sfermion_P P1 g m1 m2) @ (higgs_sfermion_P P2 g m1 m2)
let higgs_sfermion = List.flatten (Product.list3 higgs_sfermion' [1; 2; 3] [M1; M2] [M1; M2]) @
  List.flatten (Product.list3 higgs_sfermion'' [1; 2; 3] [M1; M2] [M1; M2])

```

JR: Only the first charged Higgs.

** REVISED: Independent of the sign of CD. **

```

let higgs_squark' g h m1 m2 =
  [((CHiggs HC1, Sup (m1, -g), Sdown (m2, h)), Scalar_Scalar_Scalar 1,
    G_HSUSD (false, m1, m2, g, h));
   ((CHiggs HC1c, Sup (m1, g), Sdown (m2, -h)), Scalar_Scalar_Scalar 1,
    G_HSUSD (true, m1, m2, g, h))]
let higgs_squark_a g h = higgs_squark' g h M1 M1

```

```

let higgs_squark_b (g, h) = List.flatten (Product.list2 (higgs_squark' g h)
                                                         [M1; M2] [M1; M2])

let higgs_squark =
  if Flags.ckm_present then
    List.flatten (Product.list2 higgs_squark_a [1; 2] [1; 2]) @
    ThoList.flatmap higgs_squark_b [(1, 3); (2, 3); (3, 3); (3, 1); (3, 2)]
  else
    higgs_squark_a 1 1 @ higgs_squark_a 2 2 @ higgs_squark_b (3, 3)

let vertices3 =
  (ThoList.flatmap electromagnetic_currents_3 [1; 2; 3] @
   ThoList.flatmap electromagnetic_currents_2 [C1; C2] @
   List.flatten (Product.list2 electromagnetic_sfermion_currents [1; 2; 3]
                                                           [M1; M2]) @
   ThoList.flatmap neutral_currents [1; 2; 3] @
   ThoList.flatmap neutral_sfermion_currents [1; 2; 3] @
   ThoList.flatmap charged_currents [1; 2; 3] @
   List.flatten (Product.list2 charged_slepton_currents [1; 2; 3]
                                                           [M1; M2]) @
   (if Flags.ckm_present then
    List.flatten (Product.list2 charged_quark_currents [1; 2; 3]
                                                           [1; 2; 3]) @
    List.flatten (Product.list2 charged_squark_currents [1; 2; 3]
                                                           [1; 2; 3]) @
    ThoList.flatmap yukawa_higgs_quark [(1, 3); (2, 3); (3, 3); (3, 1); (3, 2)]
  else
    charged_quark_currents 1 1 @
    charged_quark_currents 2 2 @
    charged_quark_currents 3 3 @
    charged_squark_currents 1 1 @
    charged_squark_currents 2 2 @
    charged_squark_currents 3 3 @
    ThoList.flatmap yukawa_higgs_quark [(3, 3)] @
    yukawa_higgs 3 @ yukawa_n @
    ThoList.flatmap yukawa_c [C1; C2] @
    ThoList.flatmap yukawa_cq [C1; C2] @
    List.flatten (Product.list2 charged_chargino_currents [N1; N2; N3; N4; N5]
                                                           [C1; C2]) @ triple_gauge @
    ThoList.flatmap neutral_Z (pairs [N1; N2; N3; N4; N5]) @
    Product.list2 charged_Z [C1; C2] [C1; C2] @
    gauge_higgs @ higgs @ yukawa_higgs_2 @
    List.flatten (Product.list2 higgs_charg_neutr [N1; N2; N3; N4; N5] [C1; C2]) @
    higgs_neutr @ higgs_sneutrino @ higgs_sfermion @
    higgs_squark @ yukawa_v @
    ThoList.flatmap col_currents [1; 2; 3] @
    List.flatten (Product.list2 col_sfermion_currents [1; 2; 3] [M1; M2]) @
    List.flatten (Product.list2 col_lq_currents [M1; M2] [1; 2; 3]) @
    ThoList.flatmap col_lqino_currents [1; 2; 3] @
    ThoList.flatmap em_lqino_currents [1; 2; 3] @
    ThoList.flatmap neutr_lqino_current [1; 2; 3] @

```



```

List.flatten (Product.list3 yuk_lqino_se_uc1 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_se_uc2 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_ec_su1 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_ec_su2 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_sn_dc1 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_sn_dc2 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_nc_sd1 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_nc_sd2 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lq_ec_uc [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lq_ec_uc2 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lq_nc_dc [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lq_nc_dc2 [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 lq_neutr_Z [1; 2; 3] [M1; M2] [M1; M2]) @
List.flatten (Product.list2 em_lq_currents [1; 2; 3] [M1; M2]) @
List.flatten (Product.list3 lq_shiggs [1; 2; 3] [S1; S2; S3; S4; S5; S6; S7; S8; S9] [1; 2; 3]) @
List.flatten (Product.list3 lq_phiggs [1; 2; 3] [P1; P2; P3; P4; P5; P6; P7] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_shiggs [1; 2; 3] [S1; S2; S3; S4; S5; S6; S7; S8; S9] [1; 2; 3]) @
List.flatten (Product.list3 yuk_lqino_phiggs [1; 2; 3] [P1; P2; P3; P4; P5; P6; P7] [1; 2; 3]) @
List.flatten (Product.list3 lqino_lq_neu_nlist [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 lqino_lq_neu2_nlist [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 lq_se_su [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list3 lq_snu_sd [1; 2; 3] [1; 2; 3] [1; 2; 3]) @
List.flatten (Product.list2 lqino_lq_gg [1; 2; 3] [1; 2; 3])

let vertices4 =
  (quartic_gauge @ higgs4 @ gauge_higgs4 @
   ThoList.flatmap gauge_sfermion4 [1; 2; 3] @
   gauge_squark4 @ gluon_w_squark @
   ThoList.flatmap gluon2_squark2 [1; 2; 3] @
   ThoList.flatmap gluon_gauge_squark [1; 2; 3] @
   ThoList.flatmap gluon2_lq2 [1; 2; 3] @
   ThoList.flatmap lq_gauge4 [1; 2; 3] @
   ThoList.flatmap lq_gg_gauge2 [1; 2; 3])

let vertices () = (vertices3, vertices4, [])

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

```

SLHA2-Nomenclature for neutral Higgses

```

let flavor_of_string s =
  match s with
  | "e-" → L 1 | "e+" → L (-1)
  | "mu-" → L 2 | "mu+" → L (-2)
  | "tau-" → L 3 | "tau+" → L (-3)
  | "nue" → N 1 | "nuebar" → N (-1)
  | "numu" → N 2 | "numubar" → N (-2)
  | "nutau" → N 3 | "nutaubar" → N (-3)
  | "se1-" → Slepton (M1, 1) | "se1+" → Slepton (M1, -1)

```

	"smu1-" \rightarrow <i>Slepton</i> (<i>M1</i> , 2) "smu1+" \rightarrow <i>Slepton</i> (<i>M1</i> , -2)
	"stau1-" \rightarrow <i>Slepton</i> (<i>M1</i> , 3) "stau1+" \rightarrow <i>Slepton</i> (<i>M1</i> , -3)
	"se2-" \rightarrow <i>Slepton</i> (<i>M2</i> , 1) "se2+" \rightarrow <i>Slepton</i> (<i>M2</i> , -1)
	"smu2-" \rightarrow <i>Slepton</i> (<i>M2</i> , 2) "smu2+" \rightarrow <i>Slepton</i> (<i>M2</i> , -2)
	"stau2-" \rightarrow <i>Slepton</i> (<i>M2</i> , 3) "stau2+" \rightarrow <i>Slepton</i> (<i>M2</i> , -3)
	"snue" \rightarrow <i>Sneutrino</i> 1 "snue*" \rightarrow <i>Sneutrino</i> (-1)
	"snumu" \rightarrow <i>Sneutrino</i> 2 "snumu*" \rightarrow <i>Sneutrino</i> (-2)
	"snutau" \rightarrow <i>Sneutrino</i> 3 "snutau*" \rightarrow <i>Sneutrino</i> (-3)
	"u" \rightarrow <i>U</i> 1 "ubar" \rightarrow <i>U</i> (-1)
	"c" \rightarrow <i>U</i> 2 "cbar" \rightarrow <i>U</i> (-2)
	"t" \rightarrow <i>U</i> 3 "tbar" \rightarrow <i>U</i> (-3)
	"d" \rightarrow <i>D</i> 1 "dbar" \rightarrow <i>D</i> (-1)
	"s" \rightarrow <i>D</i> 2 "sbar" \rightarrow <i>D</i> (-2)
	"b" \rightarrow <i>D</i> 3 "bbar" \rightarrow <i>D</i> (-3)
	"A" \rightarrow <i>Ga</i> "Z" "Z0" \rightarrow <i>Z</i>
	"W+" \rightarrow <i>Wp</i> "W-" \rightarrow <i>Wm</i>
	"gl" "g" \rightarrow <i>Gl</i>
<i>SHiggs S3</i>	"h01" \rightarrow <i>SHiggs S1</i> "h02" \rightarrow <i>SHiggs S2</i> "h03" \rightarrow
	"A01" \rightarrow <i>PHiggs P1</i> "A02" \rightarrow <i>PHiggs P2</i>
<i>SHiggs S6</i>	"h04" \rightarrow <i>SHiggs S4</i> "h05" \rightarrow <i>SHiggs S5</i> "h06" \rightarrow
	"A03" \rightarrow <i>PHiggs P3</i> "A04" \rightarrow <i>PHiggs P4</i>
<i>SHiggs S9</i>	"h07" \rightarrow <i>SHiggs S7</i> "h08" \rightarrow <i>SHiggs S8</i> "h09" \rightarrow
<i>PHiggs P7</i>	"A05" \rightarrow <i>PHiggs P5</i> "A06" \rightarrow <i>PHiggs P6</i> "A07" \rightarrow
(* JR: Only the first charged Higgs. *)	
	"H+" \rightarrow <i>CHiggs HC1</i> "H-" \rightarrow <i>CHiggs HC1c</i>
	"su1" \rightarrow <i>Sup</i> (<i>M1</i> , 1) "su1c" \rightarrow <i>Sup</i> (<i>M1</i> , -1)
	"sc1" \rightarrow <i>Sup</i> (<i>M1</i> , 2) "sc1c" \rightarrow <i>Sup</i> (<i>M1</i> , -2)
	"st1" \rightarrow <i>Sup</i> (<i>M1</i> , 3) "st1c" \rightarrow <i>Sup</i> (<i>M1</i> , -3)
	"su2" \rightarrow <i>Sup</i> (<i>M2</i> , 1) "su2c" \rightarrow <i>Sup</i> (<i>M2</i> , -1)
	"sc2" \rightarrow <i>Sup</i> (<i>M2</i> , 2) "sc2c" \rightarrow <i>Sup</i> (<i>M2</i> , -2)
	"st2" \rightarrow <i>Sup</i> (<i>M2</i> , 3) "st2c" \rightarrow <i>Sup</i> (<i>M2</i> , -3)
	"sgl" "sg" \rightarrow <i>Gluino</i>
	"sd1" \rightarrow <i>Sdown</i> (<i>M1</i> , 1) "sd1c" \rightarrow <i>Sdown</i> (<i>M1</i> , -1)
	"ss1" \rightarrow <i>Sdown</i> (<i>M1</i> , 2) "ss1c" \rightarrow <i>Sdown</i> (<i>M1</i> , -2)
	"sb1" \rightarrow <i>Sdown</i> (<i>M1</i> , 3) "sb1c" \rightarrow <i>Sdown</i> (<i>M1</i> , -3)
	"sd2" \rightarrow <i>Sdown</i> (<i>M2</i> , 1) "sd2c" \rightarrow <i>Sdown</i> (<i>M2</i> , -1)
	"ss2" \rightarrow <i>Sdown</i> (<i>M2</i> , 2) "ss2c" \rightarrow <i>Sdown</i> (<i>M2</i> , -2)
	"sb2" \rightarrow <i>Sdown</i> (<i>M2</i> , 3) "sb2c" \rightarrow <i>Sdown</i> (<i>M2</i> , -3)
	"neu1" \rightarrow <i>Neutralino N1</i> "neu2" \rightarrow <i>Neutralino N2</i>
	"neu3" \rightarrow <i>Neutralino N3</i> "neu4" \rightarrow <i>Neutralino N4</i>
	"neu5" \rightarrow <i>Neutralino N5</i> "neu6" \rightarrow <i>Neutralino N6</i>
	"neu7" \rightarrow <i>Neutralino N7</i> "neu8" \rightarrow <i>Neutralino N8</i>
	"neu9" \rightarrow <i>Neutralino N9</i> "neu10" \rightarrow <i>Neutralino N10</i>
	"neu11" \rightarrow <i>Neutralino N11</i>
	"ch1+" \rightarrow <i>Chargino C1</i> "ch2+" \rightarrow <i>Chargino C2</i>
	"ch1-" \rightarrow <i>Chargino C1c</i> "ch2-" \rightarrow <i>Chargino C2c</i>

```

| "ch3+" → Chargino C3 | "ch4+" → Chargino C4
| "ch3-" → Chargino C3c | "ch4-" → Chargino C4c
| "lq11" → LQ (M1,1) | "lq11c" → LQ (M1,-1)
| "lq12" → LQ (M2,1) | "lq12c" → LQ (M2,-1)
| "lq21" → LQ (M1,2) | "lq21c" → LQ (M1,-2)
| "lq22" → LQ (M2,2) | "lq22c" → LQ (M2,-2)
| "lq31" → LQ (M1,3) | "lq31c" → LQ (M1,-3)
| "lq32" → LQ (M2,3) | "lq32c" → LQ (M2,-3)
| "lqino1" → LQino 1 | "lqino1b" → LQino (-1)
| "lqino2" → LQino 2 | "lqino2b" → LQino (-2)
| "lqino3" → LQino 3 | "lqino3b" → LQino (-3)
| s → invalid_arg ("HUBABUBA:_%s_Modellib_PSSSM.ExtMSSM.flavor_of_string:" ^ s)

let flavor_to_string = function
| L 1 → "e-" | L (-1) → "e+"
| L 2 → "mu-" | L (-2) → "mu+"
| L 3 → "tau-" | L (-3) → "tau+"
| N 1 → "nue" | N (-1) → "nuebar"
| N 2 → "numu" | N (-2) → "numubar"
| N 3 → "nutau" | N (-3) → "nutaubar"
| U 1 → "u" | U (-1) → "ubar"
| U 2 → "c" | U (-2) → "cbar"
| U 3 → "t" | U (-3) → "tbar"
| U _ → invalid_arg
| "Modellib_PSSSM.ExtMSSM.flavor_to_string:_invalid_up_type_quark"
| D 1 → "d" | D (-1) → "dbar"
| D 2 → "s" | D (-2) → "sbar"
| D 3 → "b" | D (-3) → "bbar"
| D _ → invalid_arg
| "Modellib_PSSSM.ExtMSSM.flavor_to_string:_invalid_down_type_quark"
| Gl → "g1" | Gluino → "sg1"
| Ga → "A" | Z → "Z"
| Wp → "W+" | Wm → "W-"
| SHiggs S1 → "h01" | SHiggs S2 → "h02" | SHiggs S3 → "h03"
| PHiggs P1 → "A01" | PHiggs P2 → "A02"
| SHiggs S4 → "h04" | SHiggs S5 → "h05" | SHiggs S6 → "h06"
| PHiggs P3 → "A03" | PHiggs P4 → "A04"
| SHiggs S7 → "h07" | SHiggs S8 → "h08" | SHiggs S9 → "h09"
| PHiggs P5 → "A05" | PHiggs P6 → "A06" | PHiggs P7 → "A07"
(* JR: Only the first charged Higgs. *)
| CHiggs HC1 → "H+" | CHiggs HC1c → "H-"
| CHiggs HC2 → "HX_1+" | CHiggs HC2c → "HX_1-"
| CHiggs HC3 → "HX_2+" | CHiggs HC3c → "HX_2-"
| CHiggs HC4 → "HX_3+" | CHiggs HC4c → "HX_3-"
| CHiggs HC5 → "HX_4+" | CHiggs HC5c → "HX_4-"
| Slepton (M1,1) → "se1-" | Slepton (M1,-1) → "se1+"
| Slepton (M1,2) → "smu1-" | Slepton (M1,-2) → "smu1+"
| Slepton (M1,3) → "stau1-" | Slepton (M1,-3) → "stau1+"
| Slepton (M2,1) → "se2-" | Slepton (M2,-1) → "se2+"
| Slepton (M2,2) → "smu2-" | Slepton (M2,-2) → "smu2+"

```

```

| Slepton (M2,3) → "stau2-" | Slepton (M2,-3) → "stau2+"
| Sneutrino 1 → "snue" | Sneutrino (-1) → "snue*"
| Sneutrino 2 → "snumu" | Sneutrino (-2) → "snumu*"
| Sneutrino 3 → "snutau" | Sneutrino (-3) → "snutau*"
| Sup (M1,1) → "su1" | Sup (M1,-1) → "su1c"
| Sup (M1,2) → "sc1" | Sup (M1,-2) → "sc1c"
| Sup (M1,3) → "st1" | Sup (M1,-3) → "st1c"
| Sup (M2,1) → "su2" | Sup (M2,-1) → "su2c"
| Sup (M2,2) → "sc2" | Sup (M2,-2) → "sc2c"
| Sup (M2,3) → "st2" | Sup (M2,-3) → "st2c"
| Sdown (M1,1) → "sd1" | Sdown (M1,-1) → "sd1c"
| Sdown (M1,2) → "ss1" | Sdown (M1,-2) → "ss1c"
| Sdown (M1,3) → "sb1" | Sdown (M1,-3) → "sb1c"
| Sdown (M2,1) → "sd2" | Sdown (M2,-1) → "sd2c"
| Sdown (M2,2) → "ss2" | Sdown (M2,-2) → "ss2c"
| Sdown (M2,3) → "sb2" | Sdown (M2,-3) → "sb2c"
| Neutralino n → "neu" ^ string_of_neu n
| Chargino C1 → "ch1+" | Chargino C1c → "ch1-"
| Chargino C2 → "ch2+" | Chargino C2c → "ch2-"
| Chargino C3 → "ch3+" | Chargino C3c → "ch3-"
| Chargino C4 → "ch4+" | Chargino C4c → "ch4-"
| LQ (M1,1) → "lq11" | LQ (M1,-1) → "lq11c"
| LQ (M2,1) → "lq12" | LQ (M2,-1) → "lq12c"
| LQ (M1,2) → "lq21" | LQ (M1,-2) → "lq21c"
| LQ (M2,2) → "lq22" | LQ (M2,-2) → "lq22c"
| LQ (M1,3) → "lq31" | LQ (M1,-3) → "lq31c"
| LQ (M2,3) → "lq32" | LQ (M2,-3) → "lq32c"
| LQino 1 → "lqino1" | LQino (-1) → "lqino1b"
| LQino 2 → "lqino2" | LQino (-2) → "lqino2b"
| LQino 3 → "lqino3" | LQino (-3) → "lqino3b"
| _ → invalid_arg "Modellib_PSSSM.ExtMSSM.flavor_to_string"

let flavor_to_TeX = function
| L 1 → "e~-" | L (-1) → "e~+"
| L 2 → "\\mu~-" | L (-2) → "\\mu~+"
| L 3 → "\\tau~-" | L (-3) → "\\tau~+"
| N 1 → "\\nu_e" | N (-1) → "\\bar{\\nu}_e"
| N 2 → "\\nu_\\mu" | N (-2) → "\\bar{\\nu}_\\mu"
| N 3 → "\\nu_\\tau" | N (-3) → "\\bar{\\nu}_\\tau"
| U 1 → "u" | U (-1) → "\\bar{u}"
| U 2 → "c" | U (-2) → "\\bar{c}"
| U 3 → "t" | U (-3) → "\\bar{t}"
| D 1 → "d" | D (-1) → "\\bar{d}"
| D 2 → "s" | D (-2) → "\\bar{s}"
| D 3 → "b" | D (-3) → "\\bar{b}"
| L _ → invalid_arg
|         "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:~invalid~lepton"
| N _ → invalid_arg
|         "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:~invalid~neutrino"
| U _ → invalid_arg

```

```

      "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:invalid_up_type_quark"
| D - → invalid_arg
      "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:invalid_down_type_quark"
| Gl → "g" | Gluino → "\\widetilde{g}"
| Ga → "\\gamma" | Z → "Z" | Wp → "W^+" | Wm → "W^-
| SHiggs S1 → "S_1" | SHiggs S2 → "S_2" | SHiggs S3 → "S_3"
| SHiggs S4 → "S_4" | SHiggs S5 → "S_5" | SHiggs S6 → "S_6"
| SHiggs S7 → "S_7" | SHiggs S8 → "S_8" | SHiggs S9 → "S_9"
| PHiggs P1 → "P_1" | PHiggs P2 → "P_2" | PHiggs P3 → "P_3"
| PHiggs P4 → "P_4" | PHiggs P5 → "P_5" | PHiggs P6 → "P_6"
| PHiggs P7 → "P_7"
| CHiggs HC1 → "H^+" | CHiggs HC1c → "H^-"
| CHiggs HC2 → "X_{H,1}^+" | CHiggs HC2c → "X_{H,1}^-"
| CHiggs HC3 → "X_{H,2}^+" | CHiggs HC3c → "X_{H,2}^-"
| CHiggs HC4 → "X_{H,3}^+" | CHiggs HC4c → "X_{H,3}^-"
| CHiggs HC5 → "X_{H,4}^+" | CHiggs HC5c → "X_{H,4}^-"
| Slepton (M1,1) → "\\widetilde{e}_1^-"
| Slepton (M1,-1) → "\\widetilde{e}_1^+"
| Slepton (M1,2) → "\\widetilde{\\mu}_1^-"
| Slepton (M1,-2) → "\\widetilde{\\mu}_1^+"
| Slepton (M1,3) → "\\widetilde{\\tau}_1^-"
| Slepton (M1,-3) → "\\widetilde{\\tau}_1^+"
| Slepton (M2,1) → "\\widetilde{e}_2^-"
| Slepton (M2,-1) → "\\widetilde{e}_2^+"
| Slepton (M2,2) → "\\widetilde{\\mu}_2^-"
| Slepton (M2,-2) → "\\widetilde{\\mu}_2^+"
| Slepton (M2,3) → "\\widetilde{\\tau}_2^-"
| Slepton (M2,-3) → "\\widetilde{\\tau}_2^+"
| Sneutrino 1 → "\\widetilde{\\nu}_e"
| Sneutrino (-1) → "\\widetilde{\\nu}_e^*"
| Sneutrino 2 → "\\widetilde{\\nu}_\\mu"
| Sneutrino (-2) → "\\widetilde{\\nu}_\\mu^*"
| Sneutrino 3 → "\\widetilde{\\nu}_\\tau"
| Sneutrino (-3) → "\\widetilde{\\nu}_\\tau^*"
| Sup (M1,1) → "\\widetilde{u}_1"
| Sup (M1,-1) → "\\widetilde{u}_1^*"
| Sup (M1,2) → "\\widetilde{c}_1"
| Sup (M1,-2) → "\\widetilde{c}_1^*"
| Sup (M1,3) → "\\widetilde{t}_1"
| Sup (M1,-3) → "\\widetilde{t}_1^*"
| Sup (M2,1) → "\\widetilde{u}_2"
| Sup (M2,-1) → "\\widetilde{u}_2^*"
| Sup (M2,2) → "\\widetilde{c}_2"
| Sup (M2,-2) → "\\widetilde{c}_2^*"
| Sup (M2,3) → "\\widetilde{t}_2"
| Sup (M2,-3) → "\\widetilde{t}_2^*"
| Sdown (M1,1) → "\\widetilde{d}_1"
| Sdown (M1,-1) → "\\widetilde{d}_1^*"
| Sdown (M1,2) → "\\widetilde{s}_1"
| Sdown (M1,-2) → "\\widetilde{s}_1^*"

```

```

| Sdown (M1,3) → "\\widetilde{b}_1"
| Sdown (M1,-3) → "\\widetilde{b}_1^*"
| Sdown (M2,1) → "\\widetilde{d}_2"
| Sdown (M2,-1) → "\\widetilde{d}_2^*"
| Sdown (M2,2) → "\\widetilde{s}_2"
| Sdown (M2,-2) → "\\widetilde{s}_2^*"
| Sdown (M2,3) → "\\widetilde{b}_2"
| Sdown (M2,-3) → "\\widetilde{b}_2^*"
| Neutralino N1 → "\\widetilde{\\chi}^0_1"
| Neutralino N2 → "\\widetilde{\\chi}^0_2"
| Neutralino N3 → "\\widetilde{\\chi}^0_3"
| Neutralino N4 → "\\widetilde{\\chi}^0_4"
| Neutralino N5 → "\\widetilde{\\chi}^0_5"
| Neutralino N6 → "\\widetilde{\\chi}^0_6"
| Neutralino N7 → "\\widetilde{\\chi}^0_7"
| Neutralino N8 → "\\widetilde{\\chi}^0_8"
| Neutralino N9 → "\\widetilde{\\chi}^0_9"
| Neutralino N10 → "\\widetilde{\\chi}^0_{10}"
| Neutralino N11 → "\\widetilde{\\chi}^0_{11}"
| Slepton _ → invalid_arg
| "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:␣invalid␣slepton"
| Sneutrino _ → invalid_arg
| "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:␣invalid␣sneutrino"
| Sup _ → invalid_arg
| "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:␣invalid␣up␣type␣squark"
| Sdown _ → invalid_arg
| "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:␣invalid␣down␣type␣squark"
| Chargino C1 → "\\widetilde{\\chi}^1_+"
| Chargino C1c → "\\widetilde{\\chi}^1_-"
| Chargino C2 → "\\widetilde{\\chi}^2_+"
| Chargino C2c → "\\widetilde{\\chi}^2_-"
| Chargino C3 → "\\widetilde{\\chi}^3_+"
| Chargino C3c → "\\widetilde{\\chi}^3_-"
| Chargino C4 → "\\widetilde{\\chi}^4_+"
| Chargino C4c → "\\widetilde{\\chi}^4_-"
| LQ (M1,1) → "D_{1,,1}" | LQ (M1,-1) → "D_{1,,1}^*"
| LQ (M2,1) → "D_{1,,2}" | LQ (M2,-1) → "D_{1,,2}^*"
| LQ (M1,2) → "D_{2,,1}" | LQ (M1,-2) → "D_{2,,1}^*"
| LQ (M2,2) → "D_{2,,2}" | LQ (M2,-2) → "D_{2,,2}^*"
| LQ (M1,3) → "D_{3,,1}" | LQ (M1,-3) → "D_{3,,1}^*"
| LQ (M2,3) → "D_{3,,2}" | LQ (M2,-3) → "D_{3,,2}^*"
| LQino 1 → "\\widetilde{D}_1" | LQino (-1) → "\\bar\\widetilde{D}_1"
| LQino 2 → "\\widetilde{D}_2" | LQino (-2) → "\\bar\\widetilde{D}_2"
| LQino 3 → "\\widetilde{D}_3" | LQino (-3) → "\\bar\\widetilde{D}_3"
| LQ _ → invalid_arg
| "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:␣invalid␣leptoquark␣type"
| LQino _ → invalid_arg
| "Modellib_PSSSM.ExtMSSM.flavor_to_TeX:␣invalid␣leptoquarkino␣type"

```

let *flavor_symbol* = function

```

| L g when g > 0 → "l" ^ string_of_int g
| L g → "l" ^ string_of_int (abs g) ^ "b"
| N g when g > 0 → "n" ^ string_of_int g
| N g → "n" ^ string_of_int (abs g) ^ "b"
| U g when g > 0 → "u" ^ string_of_int g
| U g → "u" ^ string_of_int (abs g) ^ "b"
| D g when g > 0 → "d" ^ string_of_int g
| D g → "d" ^ string_of_int (abs g) ^ "b"
| Gl → "gl"
| Ga → "a" | Z → "z"
| Wp → "wp" | Wm → "wm"
| Slepton (M1, g) when g > 0 → "sl1" ^ string_of_int g
| Slepton (M1, g) → "sl1c" ^ string_of_int (abs g)
| Slepton (M2, g) when g > 0 → "sl2" ^ string_of_int g
| Slepton (M2, g) → "sl2c" ^ string_of_int (abs g)
| Sneutrino g when g > 0 → "sn" ^ string_of_int g
| Sneutrino g → "snc" ^ string_of_int (abs g)
| Sup (M1, g) when g > 0 → "su1" ^ string_of_int g
| Sup (M1, g) → "su1c" ^ string_of_int (abs g)
| Sup (M2, g) when g > 0 → "su2" ^ string_of_int g
| Sup (M2, g) → "su2c" ^ string_of_int (abs g)
| Sdown (M1, g) when g > 0 → "sd1" ^ string_of_int g
| Sdown (M1, g) → "sd1c" ^ string_of_int (abs g)
| Sdown (M2, g) when g > 0 → "sd2" ^ string_of_int g
| Sdown (M2, g) → "sd2c" ^ string_of_int (abs g)
| Neutralino n → "neu" ^ (string_of_neu n)
| Chargino c when (int_of_char c) > 0 → "cp" ^ string_of_char c
| Chargino c → "cm" ^ string_of_int (abs (int_of_char c))
| Gluino → "sgl"
| SHiggs s → "h0" ^ (string_of_shiggs s)
| PHiggs p → "A0" ^ (string_of_phiggs p)
| CHiggs HC1 → "hp" | CHiggs HC1c → "hm"
| CHiggs _ → invalid_arg "charged_Higgs_not_yet_implemented"
| LQ (M1, g) when g > 0 → "lq" ^ string_of_int g ^ "1"
| LQ (M1, g) → "lq" ^ string_of_int (abs g) ^ "1c"
| LQ (M2, g) when g > 0 → "lq" ^ string_of_int g ^ "2"
| LQ (M2, g) → "lq" ^ string_of_int (abs g) ^ "2c"
| LQino g when g > 0 → "lqino" ^ string_of_int g
| LQino g → "lqino" ^ string_of_int (abs g) ^ "b"

let pdg = function
| L g when g > 0 → 9 + 2 × g
| L g → - 9 + 2 × g
| N g when g > 0 → 10 + 2 × g
| N g → - 10 + 2 × g
| U g when g > 0 → 2 × g
| U g → 2 × g
| D g when g > 0 → - 1 + 2 × g
| D g → 1 + 2 × g
| Gl → 21

```

```

|  $Ga \rightarrow 22$  |  $Z \rightarrow 23$ 
|  $Wp \rightarrow 24$  |  $Wm \rightarrow (-24)$ 
|  $SHiggs\ S1 \rightarrow 25$  |  $SHiggs\ S2 \rightarrow 35$  |  $PHiggs\ P1 \rightarrow 36$ 
(* JR: Only the first charged Higgs. *)
|  $CHiggs\ HC1 \rightarrow 37$  |  $CHiggs\ HC1c \rightarrow (-37)$ 
|  $CHiggs\ - \rightarrow invalid\_arg\ "charged\_Higgs\_not\_yet\_implemented"$ 
|  $Slepton\ (M1, g) \text{ when } g > 0 \rightarrow 1000009 + 2 \times g$ 
|  $Slepton\ (M1, g) \rightarrow -1000009 + 2 \times g$ 
|  $Slepton\ (M2, g) \text{ when } g > 0 \rightarrow 2000009 + 2 \times g$ 
|  $Slepton\ (M2, g) \rightarrow -2000009 + 2 \times g$ 
|  $Sneutrino\ g \text{ when } g > 0 \rightarrow 1000010 + 2 \times g$ 
|  $Sneutrino\ g \rightarrow -1000010 + 2 \times g$ 
|  $Sup\ (M1, g) \text{ when } g > 0 \rightarrow 1000000 + 2 \times g$ 
|  $Sup\ (M1, g) \rightarrow -1000000 + 2 \times g$ 
|  $Sup\ (M2, g) \text{ when } g > 0 \rightarrow 2000000 + 2 \times g$ 
|  $Sup\ (M2, g) \rightarrow -2000000 + 2 \times g$ 
|  $Sdown\ (M1, g) \text{ when } g > 0 \rightarrow 999999 + 2 \times g$ 
|  $Sdown\ (M1, g) \rightarrow -999999 + 2 \times g$ 
|  $Sdown\ (M2, g) \text{ when } g > 0 \rightarrow 1999999 + 2 \times g$ 
|  $Sdown\ (M2, g) \rightarrow -1999999 + 2 \times g$ 
|  $Gluino \rightarrow 1000021$ 
(* JR: only the first two charginos. *)
|  $Chargino\ C1 \rightarrow 1000024$  |  $Chargino\ C1c \rightarrow (-1000024)$ 
|  $Chargino\ C2 \rightarrow 1000037$  |  $Chargino\ C2c \rightarrow (-1000037)$ 
|  $Chargino\ C3 \rightarrow 1000039$  |  $Chargino\ C3c \rightarrow (-1000039)$ 
|  $Chargino\ C4 \rightarrow 1000041$  |  $Chargino\ C4c \rightarrow (-1000041)$ 
|  $Neutralino\ N1 \rightarrow 1000022$  |  $Neutralino\ N2 \rightarrow 1000023$ 
|  $Neutralino\ N3 \rightarrow 1000025$  |  $Neutralino\ N4 \rightarrow 1000035$ 
(* According to SLHA2 (not anymore !?)*
|  $Neutralino\ N5 \rightarrow 1000045$  |  $Neutralino\ N6 \rightarrow 1000046$ 
|  $Neutralino\ N7 \rightarrow 1000047$  |  $Neutralino\ N8 \rightarrow 1000048$ 
|  $Neutralino\ N9 \rightarrow 1000049$  |  $Neutralino\ N10 \rightarrow 1000050$ 
|  $Neutralino\ N11 \rightarrow 1000051$ 
|  $PHiggs\ P2 \rightarrow 46$  |  $PHiggs\ P3 \rightarrow 47$  |  $PHiggs\ P4 \rightarrow 48$ 
|  $PHiggs\ P5 \rightarrow 49$  |  $PHiggs\ P6 \rightarrow 50$  |  $PHiggs\ P7 \rightarrow 51$ 
|  $SHiggs\ S3 \rightarrow 45$  |  $SHiggs\ S4 \rightarrow 52$  |  $SHiggs\ S5 \rightarrow 53$ 
|  $SHiggs\ S6 \rightarrow 54$  |  $SHiggs\ S7 \rightarrow 55$  |  $SHiggs\ S8 \rightarrow 56$ 
|  $SHiggs\ S9 \rightarrow 57$ 
|  $LQ\ (M1, g) \text{ when } g > 0 \rightarrow 1000059 + g$ 
|  $LQ\ (M1, g) \rightarrow -1000059 + g$ 
|  $LQ\ (M2, g) \text{ when } g > 0 \rightarrow 2000059 + g$ 
|  $LQ\ (M2, g) \rightarrow -2000059 + g$ 
|  $LQino\ g \text{ when } g > 0 \rightarrow 59 + g$ 
|  $LQino\ g \rightarrow -59 + g$ 

```

We must take care of the pdg numbers for the two different kinds of sfermions in the MSSM. The particle data group in its Monte Carlo particle numbering scheme takes only into account mixtures of the third generation squarks and the stau. For the other sfermions we will use the number of the lefthanded field for the lighter mixed state and the one for the righthanded for the heavier. Below

are the official pdg numbers from the Particle Data Group. In order not to produce arrays with some million entries in the Fortran code for the masses and the widths we introduce our private pdg numbering scheme which only extends not too far beyond 42. Our private scheme then has the following pdf numbers (for the sparticles the subscripts L/R and $1/2$ are taken synonymously):

d	down-quark	1
u	up-quark	2
s	strange-quark	3
c	charm-quark	4
b	bottom-quark	5
t	top-quark	6
e^-	electron	11
ν_e	electron-neutrino	12
μ^-	muon	13
ν_μ	muon-neutrino	14
τ^-	tau	15
ν_τ	tau-neutrino	16
g	gluon	(9) 21
γ	photon	22
Z^0	Z-boson	23
W^+	W-boson	24
h^0	light Higgs boson	25
H^0	heavy Higgs boson	35
A^0	pseudoscalar Higgs	36
H^\pm	charged Higgs	37
\tilde{d}_L	down-squark 1	41
\tilde{u}_L	up-squark 1	42
\tilde{s}_L	strange-squark 1	43
\tilde{c}_L	charm-squark 1	44
\tilde{b}_L	bottom-squark 1	45
\tilde{t}_L	top-squark 1	46
\tilde{d}_R	down-squark 2	47
\tilde{u}_R	up-squark 2	48
\tilde{s}_R	strange-squark 2	49
\tilde{c}_R	charm-squark 2	50
\tilde{b}_R	bottom-squark 2	51
\tilde{t}_R	top-squark 2	52
\tilde{e}_L	selectron 1	53
$\tilde{\nu}_{e,L}$	electron-sneutrino	54
$\tilde{\mu}_L$	smuon 1	55
$\tilde{\nu}_{\mu,L}$	muon-sneutrino	56
$\tilde{\tau}_L$	stau 1	57
$\tilde{\nu}_{\tau,L}$	tau-sneutrino	58
\tilde{e}_R	selectron 2	59
$\tilde{\mu}_R$	smuon 2	61
$\tilde{\tau}_R$	stau 2	63
\tilde{g}	gluino 543	64
$\tilde{\chi}_1^0$	neutralino 1	65
$\tilde{\chi}_2^0$	neutralino 2	66
$\tilde{\chi}_3^0$	neutralino 3	67
$\tilde{\chi}_4^0$	neutralino 4	68
$\tilde{\chi}_5^0$	neutralino 5	69
$\tilde{\chi}_1^\pm$	chargino 1	70

```

let pdg_mw = function
| L g when g > 0 → 9 + 2 × g
| L g → - 9 + 2 × g
| N g when g > 0 → 10 + 2 × g
| N g → - 10 + 2 × g
| U g when g > 0 → 2 × g
| U g → 2 × g
| D g when g > 0 → - 1 + 2 × g
| D g → 1 + 2 × g
| Gl → 21
| Ga → 22 | Z → 23
| Wp → 24 | Wm → (-24)
| SHiggs S1 → 25 | SHiggs S2 → 35 | PHiggs P1 → 36
(* JR: Only the first charged Higgs. *)
| CHiggs HC1 → 37 | CHiggs HC1c → (-37)
| CHiggs _ → invalid_arg "charged_Higgs_not_yet_implemented"
| Sup (M1, g) when g > 0 → 40 + 2 × g
| Sup (M1, g) → - 40 + 2 × g
| Sup (M2, g) when g > 0 → 46 + 2 × g
| Sup (M2, g) → - 46 + 2 × g
| Sdown (M1, g) when g > 0 → 39 + 2 × g
| Sdown (M1, g) → - 39 + 2 × g
| Sdown (M2, g) when g > 0 → 45 + 2 × g
| Sdown (M2, g) → - 45 + 2 × g
| Slepton (M1, g) when g > 0 → 51 + 2 × g
| Slepton (M1, g) → - 51 + 2 × g
| Slepton (M2, g) when g > 0 → 57 + 2 × g
| Slepton (M2, g) → - 57 + 2 × g
| Sneutrino g when g > 0 → 52 + 2 × g
| Sneutrino g → - 52 + 2 × g
| Gluino → 64
(* JR: Only the first two charginos. *)
| Chargino C1 → 70 | Chargino C1c → (-70)
| Chargino C2 → 71 | Chargino C2c → (-71)
| Chargino C3 → 106 | Chargino C3c → (-106)
| Chargino C4 → 107 | Chargino C4c → (-107)
| Neutralino N1 → 65 | Neutralino N2 → 66
| Neutralino N3 → 67 | Neutralino N4 → 68
| Neutralino N5 → 69 | Neutralino N6 → 100
| Neutralino N7 → 101 | Neutralino N8 → 102
| Neutralino N9 → 103 | Neutralino N10 → 104
| Neutralino N11 → 105
| PHiggs P2 → 72 | PHiggs P3 → 89 | PHiggs P4 → 90
| PHiggs P5 → 91 | PHiggs P6 → 92 | PHiggs P7 → 93
| SHiggs S3 → 73 | SHiggs S4 → 94 | SHiggs S5 → 95
| SHiggs S6 → 96 | SHiggs S7 → 97 | SHiggs S8 → 98
| SHiggs S9 → 99
| LQ (M1, g) when g > 0 → 78 + 2 × g
| LQ (M1, g) → - 78 + 2 × g
| LQ (M2, g) when g > 0 → 79 + 2 × g

```

```

|  $LQ(M2, g) \rightarrow -79 + 2 \times g$ 
|  $LQino\ g \text{ when } g > 0 \rightarrow 85 + g$ 
|  $LQino\ g \rightarrow -85 + g$ 

let mass_symbol f =
  "mass(" ^ string_of_int (abs (pdg-mw f)) ^ ")"

let width_symbol f =
  "width(" ^ string_of_int (abs (pdg-mw f)) ^ ")"

let conj_symbol = function
| false, str → str
| true, str → str ^ "_c"

let constant_symbol = function
| E → "e" | G → "g" | G_Z → "gz"
| Q_lepton → "qlep" | Q_up → "qup" | Q_down → "qdwn"
| Q_charg → "qchar"
| G_NC_lepton → "gnclep" | G_NC_neutrino → "gncneu"
| G_NC_up → "gncup" | G_NC_down → "gncdwn"
| G_CC → "gcc"
| G_CCQ (vc, g1, g2) → conj_symbol (vc, "g-ccq") ^ "(" ^
  string_of_int g1 ^ ", " ^ string_of_int g2 ^ ")"
| I_Q_W → "iqw" | I_G_ZWW → "igzww"
| G_WWWW → "gw4" | G_ZZWW → "gzzww"
| G_PZWW → "gpzww" | G_PPWW → "gppww"
| G_GH4_ZZPP (p1, p2) → "g-ZZA0A0(" ^ string_of_phiggs p1 ^ ", " ^
  string_of_phiggs p2 ^ ")"
| G_GH4_ZZSS (s1, s2) → "g-ZZh0h0(" ^ string_of_shiggs s1 ^ ", " ^
  string_of_shiggs s2 ^ ")"
| G_GH4_ZZCC → "g-zzhphm"
| G_GH4_GaGaCC → "g-AAhphm"
| G_GH4_ZGaCC → "g-zAhphm"
| G_GH4_WWCC → "g-wwhphm"
| G_GH4_WWPP (p1, p2) → "g-WWA0A0(" ^ string_of_phiggs p1 ^ ", " ^
  string_of_phiggs p2 ^ ")"
| G_GH4_WWSS (s1, s2) → "g-WWh0h0(" ^ string_of_shiggs s1 ^ ", " ^
  string_of_shiggs s2 ^ ")"
| G_GH4_ZWSC s → "g-ZWhph0(" ^ string_of_shiggs s ^ ")"
| G_GH4_GaWSC s → "g-AWhph0(" ^ string_of_shiggs s ^ ")"
| G_GH4_ZWPC p → "g-ZWhpA0(" ^ string_of_phiggs p ^ ")"
| G_GH4_GaWPC p → "g-AWhpA0(" ^ string_of_phiggs p ^ ")"
| G_CICIS (n1, n2, s) → "g-neuneuh0(" ^ string_of_neu n1 ^ ", " ^
  string_of_neu n2 ^ ", " ^ string_of_shiggs s ^ ")"
| G_CICIP (n1, n2, p) → "g-neuneuA0(" ^ string_of_neu n1 ^ ", " ^
  string_of_neu n2 ^ ", " ^ string_of_phiggs p ^ ")"
| G_H3_SCC s → "g-h0hphm(" ^ string_of_shiggs s ^ ")"
| G_H3_SPP (s, p1, p2) → "g-h0A0A0(" ^ string_of_shiggs s ^ ", " ^
  string_of_phiggs p1 ^ ", " ^ string_of_phiggs p2 ^ ")"
| G_H3_SSS (s1, s2, s3) → "g-h0h0h0(" ^ string_of_shiggs s1 ^ ", " ^
  string_of_shiggs s2 ^ ", " ^ string_of_shiggs s3 ^ ")"
| G_CSC (c1, c2, s) → "g-chchh0(" ^ string_of_char c1 ^ ", " ^

```

```

      string_of_char c2 ^ "," ^ string_of_shiggs s ^ ")"
| G_CPC (c1, c2, p) → "g_chchA0(" ^ string_of_char c1 ^ "," ^
      string_of_char c2 ^ "," ^ string_of_phiggs p ^ ")"
| G_YUK_FFS (f1, f2, s) → "g-yuk_h0-" ^ string_of_fermion_type f1 ^
      string_of_fermion_type f2 ^ "(" ^ string_of_shiggs s ^ "," ^
      string_of_fermion_gen f1 ^ ")"
| G_YUK_FFP (f1, f2, p) → "g-yuk_A0-" ^ string_of_fermion_type f1 ^
      string_of_fermion_type f2 ^ "(" ^ string_of_phiggs p ^ "," ^
      string_of_fermion_gen f1 ^ ")"
| G_YUK_LCN g → "g-yuk_hp_ln(" ^ string_of_int g ^ ")"
| G_NWC (n, c) → "g_nwc(" ^ string_of_char c ^ "," ^ string_of_neu n ^ ")"
| G_CWN (c, n) → "g_cwn(" ^ string_of_char c ^ "," ^ string_of_neu n ^ ")"
| G_SLSNW (vc, g, m) → conj_symbol (vc, "g_wsln") ^ "(" ^ string_of_int g
      ^ "," ^ string_of_sfm m ^ ")"
| G_NZN (n1, n2) → "g_zneuneu(" ^ string_of_neu n1 ^ "," ^
      ^ string_of_neu n2 ^ ")"
| G_CZC (c1, c2) → "g_zchch(" ^ string_of_char c1 ^ "," ^
      ^ string_of_char c2 ^ ")"
| Gs → "gs"
| G_YUK_UCD (n, m) → "g-yuk_hp_ud(" ^ string_of_int n ^ "," ^
      string_of_int m ^ ")"
| G_YUK_DCU (n, m) → "g-yuk_hm_du(" ^ string_of_int n ^ "," ^
      string_of_int m ^ ")"
| G_YUK_N (vc, f, n, sf, m) → conj_symbol (vc, "g-yuk_neu-" ^
      string_of_fermion_type f ^ string_of_sff sf) ^ "(" ^
      string_of_fermion_gen f ^ "," ^ string_of_neu n ^ "," ^
      string_of_sfm m ^ ")"
| G_YUK_G (vc, f, sf, m) → conj_symbol (vc, "g-yuk_gluino-" ^
      string_of_fermion_type f ^ string_of_sff sf) ^ "(" ^
      string_of_fermion_gen f ^ "," ^ string_of_sfm m ^ ")"
| G_YUK_C (vc, f, c, sf, m) → conj_symbol (vc, "g-yuk_char-" ^
      string_of_fermion_type f ^ string_of_sff sf) ^ "(" ^
      string_of_fermion_gen f ^ "," ^ string_of_char c ^ "," ^
      string_of_sfm m ^ ")"
| G_YUK_Q (vc, g1, f, c, sf, m) → conj_symbol (vc, "g-yuk_char-" ^
      string_of_fermion_type f ^ string_of_sff sf) ^ "(" ^ string_of_int g1 ^
      ^ "," ^ string_of_fermion_gen f ^ "," ^ string_of_char c ^ "," ^
      string_of_sfm m ^ ")"
| G_WPSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "g_wA_susd") ^ "(" ^
      string_of_int g1 ^ "," ^ string_of_int g2 ^ "," ^ string_of_sfm m1 ^
      ^ "," ^ string_of_sfm m2 ^ ")"
| G_WZSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "g_wz_susd") ^ "(" ^
      string_of_int g1 ^ "," ^ string_of_int g2 ^ "," ^ string_of_sfm m1
      ^ "," ^ string_of_sfm m2 ^ ")"

```

(* 3vertex: Higgs-Gauge a la Franke-Fraas *)

Nomenclature consistent with *flavor_of_string*

```

| G_GH_ZSP (s, p) → "g_zh0a0(" ^ string_of_shiggs s ^ "," ^
      string_of_phiggs p ^ ")"
| G_GH_WSC s → "g_Whph0(" ^ string_of_shiggs s ^ ")"

```

```

| G_GH_WPC p → "g_WhpA0(" ^ string_of_phiggs p ^ ")"
| G_GH_ZZS s → "g_ZZh0(" ^ string_of_shiggs s ^ ")"
| G_GH_WWS s → "g_WWh0(" ^ string_of_shiggs s ^ ")"
| G_GH_ZCC → "g_Zhmhp"
| G_GH_GaCC → "g_Ahmhp"
| G_ZSF (f, g, m1, m2) → "g-z" ^ string_of_sff f ^ string_of_sff f ^ "(" ^
  string_of_int g ^ ", " ^ string_of_sfm m1 ^ ", " ^ string_of_sfm m2 ^ ")"
| G_HSNSL (vc, g, m) → conj_symbol (vc, "g_hp_sl" ^ string_of_sfm m ^ "sn1")
  ^ "(" ^ string_of_int g ^ ")"
| G_GlGLSQSQ → "g-gg-sqsq"
| G_PPSFSF f → "g-AA-" ^ string_of_sff f ^ string_of_sff f
| G_ZZSFSF (f, g, m1, m2) → "g-zz-" ^ string_of_sff f ^ string_of_sff f ^ "(" ^
  string_of_int g ^ ", " ^ string_of_sfm m1 ^ ", " ^ string_of_sfm m2 ^ ")"
| G_ZPSFSF (f, g, m1, m2) → "g-zA-" ^ string_of_sff f ^ string_of_sff f ^ "(" ^
  string_of_int g ^ ", " ^ string_of_sfm m1 ^ ", " ^ string_of_sfm m2 ^ ")"
| G_GlPSQSQ → "g-gA-sqsq"
| G_GLZSFSF (f, g, m1, m2) → "g-gz-" ^ string_of_sff f ^ string_of_sff f ^
  "(" ^ string_of_int g ^ ", " ^ string_of_sfm m1 ^ ", " ^ string_of_sfm
  m2 ^ ")"
| G_GlWSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "g-gw-susd") ^ "(" ^
  string_of_int g1 ^ ", " ^ string_of_int g2 ^ ", " ^ string_of_sfm m1 ^ ", "
  ^ string_of_sfm m2 ^ ")"
| G_strong → "gs" | G_SS → "gs**2"
| I_G_S → "igs"
| G_NHC (vc, n, c) → conj_symbol (vc, "g_neuhmchar") ^ "(" ^
  string_of_neu n ^ ", " ^ string_of_char c ^ ")"
| G_WWSFSF (f, g, m1, m2) → "g-ww-" ^ string_of_sff f ^ string_of_sff f ^
  "(" ^ string_of_int g ^ ", " ^ string_of_sfm m1 ^ ", " ^ string_of_sfm m2
  ^ ")"
| G_WPSLSN (vc, g, m) → conj_symbol (vc, "g-wA-slslsn") ^ "(" ^ string_of_int g
  ^ ", " ^ string_of_sfm m ^ ")"
| G_WZLSN (vc, g, m) → conj_symbol (vc, "g-wz-slslsn") ^ "(" ^ string_of_int
  g ^ ", " ^ string_of_sfm m ^ ")"
| G_SFSFS (s, f, g, m1, m2) → "g-h0-" ^ string_of_sff f ^ string_of_sfm m1
  ^ string_of_sff f ^ string_of_sfm m2 ^ "(" ^ string_of_shiggs s ^ ", " ^
  string_of_int g ^ ")"
| G_SFSFP (p, f, g, m1, m2) → "g-A0-" ^ string_of_sff f ^ string_of_sfm m1
  ^ string_of_sff f ^ string_of_sfm m2 ^ "(" ^ string_of_phiggs p ^ ", " ^
  string_of_int g ^ ")"
| G_HSUSD (vc, m1, m2, g1, g2) → conj_symbol (vc, "g_hp-su" ^ string_of_sfm m1
  ^ "sd" ^ string_of_sfm m2 ) ^ "(" ^ string_of_int g1 ^ ", "
  ^ string_of_int g2 ^ ")"
| G_WSQ (vc, g1, g2, m1, m2) → conj_symbol (vc, "g-wsusd") ^ "(" ^
  string_of_int g1 ^ ", " ^ string_of_int g2 ^ ", " ^ string_of_sfm m1 ^
  ", " ^ string_of_sfm m2 ^ ")"
| G_YUK_LQ_S (g1, s, g3) → "g-yuk_lq-s(" ^ string_of_int g1 ^ ", " ^
  string_of_shiggs s ^ ", " ^ string_of_int g3 ^ ")"
| G_YUK_LQ_P (g1, p, g3) → "g-yuk_lq-p(" ^ string_of_int g1 ^ ", " ^
  string_of_phiggs p ^ ", " ^ string_of_int g3 ^ ")"
| G_LQ_NEU (m, g1, g2, n) → "g_lq-neu(" ^ string_of_sfm m ^ ", " ^

```

```

      string_of_int g1 ^ "," ^ string_of_int g2 ^ "," ^ string_of_neu n ^ ")"
| G_LQ_GG (m, g1, g2) → "g_lq_gg(" ^ string_of_sfm m ^ "," ^
      string_of_int g1 ^ "," ^ string_of_int g2 ^ ")"
| G_LQ_EC_UC (vc, m, g1, g2, g3) → conj_symbol(vc, "g_lq_ec_uc") ^ "(" ^
      string_of_sfm m ^ "," ^ string_of_int g1 ^ "," ^ string_of_int g2 ^ "," ^
      ^ string_of_int g3 ^ ")"
| G_LQ_SSU (m1, m2, m3, g1, g2, g3) → "g_lq_sst(" ^ string_of_sfm m1 ^ "," ^
      string_of_sfm m2 ^ "," ^ string_of_sfm m3 ^ "," ^ string_of_int g1 ^ "," ^
      string_of_int g2 ^ "," ^ string_of_int g3 ^ ")"
| G_LQ_SSD (m1, m2, g1, g2, g3) → "g_lq_ssta(" ^ string_of_sfm m1 ^ "," ^
      string_of_sfm m2 ^ "," ^ string_of_int g1 ^ "," ^ string_of_int g2 ^
      ^ string_of_int g3 ^ ")"
| G_LQ_S (m1, m2, g1, s, g2) → "g_lq_s(" ^ string_of_sfm m1 ^ "," ^ string_of_sfm m2 ^ "," ^
      ^ string_of_int g1 ^ "," ^ string_of_shiggs s ^ "," ^ string_of_int g2 ^ ")"
| G_LQ_P (m1, m2, g1, p, g2) → "g_lq_s(" ^ string_of_sfm m1 ^ "," ^ string_of_sfm m2 ^ "," ^
      ^ string_of_int g1 ^ "," ^ string_of_phiggs p ^ "," ^ string_of_int g2 ^ ")"
| G_ZLQ (g, m1, m2) → "g_zlqlq(" ^ string_of_int g ^ "," ^
      string_of_sfm m1 ^ "," ^ string_of_sfm m2 ^ ")"
| G_ZZLQLQ → "g-zz_lqlq"
| G_ZPLQLQ → "g-zA_lqlq"
| G_PPLQLQ → "g-AA_lqlq"
| G_ZGLQLQ → "g-zg_lqlq"
| G_PGILQLQ → "g-Ag_lqlq"
| G_GILQLQ → "g-gg_lqlq"
| G_NLQC → "g-nlqc"

```

end

—14—

COMPHEP MODELS

14.1 Interface of *Comphep_syntax*

```
type raw =  
  | I | Integer of int | Symbol of string  
  | Application of string × raw  
  | Dotproduct of raw × raw  
  | Product of (raw × int) list  
  | Sum of (raw × int) list  
  
val symbol : string → raw  
val integer : int → raw  
val imag : raw  
  
val apply : string → raw → raw  
val dot : raw → raw → raw  
val multiply : raw → raw → raw  
val divide : raw → raw → raw  
val power : raw → int → raw  
val add : raw → raw → raw  
val subtract : raw → raw → raw  
val neg : raw → raw
```

14.2 Implementation of *Comphep_syntax*

```
type raw =  
  | I | Integer of int | Symbol of string  
  | Application of string × raw  
  | Dotproduct of raw × raw  
  | Product of (raw × int) list  
  | Sum of (raw × int) list  
  
let symbol name = Symbol name  
let integer n = Integer n  
let imag = I  
  
let apply f x = Application (f, x)  
let dot x y = Dotproduct (x, y)
```



```
let negate = List.map (fun (x, c) → (x, - c))
let scale n = List.map (fun (x, c) → (x, n × c))
```

```
let add1 (x, c) y =
  if c = 0 then
    y
  else
    try
      let c' = List.assoc x y + c in
      if c' = 0 then
        List.remove_assoc x y
      else
        (x, c') :: (List.remove_assoc x y)
    with
    | Not_found → (x, c) :: y
```

```
let addn = List.fold_right add1
```

```
let multiply x y =
  match x, y with
  | Product x', Product y' → Product (addn x' y')
  | Integer n, Product y' → Product (scale n y')
  | Product x', Integer n → Product (scale n x')
  | -, Product y' → Product (add1 (x, 1) y')
  | Product x', - → Product (add1 (y, 1) x')
  | - when x = y → Product ([ (x, 2) ])
  | - → Product ([ (x, 1); (y, 1) ])
```

```
let divide x y =
  match y with
  | Product y' → multiply x (Product (negate y'))
  | - when x = y → Product ([ ])
  | - → Product ([ (x, 1); (y, -1) ])
```

```
let power x n =
  match x with
  | Product x' → Product (scale n x')
  | x → Product ([ (x, n) ])
```

```
let add x y =
  match x, y with
  | Sum x', Sum y' → Sum (addn x' y')
  | -, Sum y' → Sum (add1 (x, 1) y')
  | Sum x', - → Sum (add1 (y, 1) x')
  | - when x = y → Sum ([ (x, 2) ])
  | - → Sum ([ (x, 1); (y, 1) ])
```

```
let subtract x y =
  match y with
  | Sum y' → add x (Sum (negate y'))
  | - when x = y → Sum ([ ])
  | - → Sum ([ (x, 1); (y, -1) ])
```

```
let neg = function
```

```

| Sum x → Sum (negate x)
| x → Sum [(x, -1)]

type vector =
| Momentum of int
| Index of int
| Index' of int

let vector_keyword = function
| "p1" → Some (Momentum 1)
| "p2" → Some (Momentum 2)
| "p3" → Some (Momentum 3)
| "p4" → Some (Momentum 4)
| "m1" → Some (Index 1)
| "m2" → Some (Index 2)
| "m3" → Some (Index 3)
| "m4" → Some (Index 4)
| "M1" → Some (Index' 1)
| "M2" → Some (Index' 2)
| "M3" → Some (Index' 3)
| "M4" → Some (Index' 4)
| _ → None

```

14.3 Lexer

```

{
open Comphep_parser
}

let digit = ['0'-'9']
let upper = ['A'-'Z']
let lower = ['a'-'z']
let alpha = upper | lower
let alphanum = alpha | digit

let symbol = alpha alphanum*
let integer = digit+

rule token = parse
  [' ' '\t'] { token lexbuf } (* skip blanks *)
| "(" { LPAREN }
| ")" { RPAREN }
| "i" { I }
| "." { DOT }
| "**" { POWER }
| "*" { MULT }
| "/" { DIV }
| "+" { PLUS }
| "-" { MINUS }
| symbol { SYMBOL (Lexing.lexeme lexbuf) }
| integer { INT (int_of_string (Lexing.lexeme lexbuf)) }

```

```
| - { failwith ("lexer_fails_@" ^ Lexing.lexeme lexbuf) }
| eof { END }
```

14.4 Parser

Header

```
module S = Comphep_syntax
```

Token declarations

```
%token < string > SYMBOL
%token < int > INT
%token I
%token LPAREN RPAREN
%token DOT MULT DIV POWER PLUS MINUS
%token END

%left PLUS MINUS
%left MULT DIV
%nonassoc UNARY
%nonassoc POWER
%nonassoc DOT

%start expr
%type < Comphep_syntax.raw > expr
```

Grammar rules

```
expr ::=
  e END { $1 }

e ::=
  SYMBOL { S.symbol $1 }
| INT { S.integer $1 }
| I { S.imag }
| SYMBOL LPAREN e RPAREN { S.apply $1 $3 }
| LPAREN e RPAREN { $2 }
| e DOT e { S.dot $1 $3 }
| e MULT e { S.multiply $1 $3 }
| e DIV e { S.divide $1 $3 }
| e PLUS e { S.add $1 $3 }
| e MINUS e { S.subtract $1 $3 }
```

```
| PLUS e %prec UNARY { $2 }
| MINUS e %prec UNARY { S.neg $2 }
| e POWER INT { S.power $1 $3 }
```

14.5 Interface of *Comphep*

Wolfgang's idea: read *Comphep*'s model files:

```
module Model : Model.T
```

14.6 Implementation of *Comphep*

```
let rcs_file = RCS.parse "Comphep" ["Plagiarizing_CompHEP_models_..."]
  { RCS.revision = "$Revision: 4538$";
    RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
    RCS.author = "$Author: jr_reuter$";
    RCS.source
      = "$URL: svn+ssh://jr_reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg"
```

A friendlier *String.sub* that returns an empty string instead of raising an exception. Instead of the length, the second argument denotes the last position.

```
let substring buffer i1 i2 =
  let imax = String.length buffer - 1 in
  let i1 = max i1 0
  and i2 = min i2 imax in
  let len = i2 - i1 + 1 in
  if len > 0 then
    String.sub buffer i1 len
  else
    ""

let first_non_white buffer =
  let len = String.length buffer in
  let rec skip_white i =
    if i ≥ len then
      i
    else if buffer.[i] ≠ ' ' ∧ buffer.[i] ≠ '\t' then
      i
    else
      skip_white (succ i) in
  skip_white 0

let last_non_white buffer =
  let len = String.length buffer in
  let rec skip_white i =
    if i < 0 then
      i
    else if buffer.[i] ≠ ' ' ∧ buffer.[i] ≠ '\t' then
      i
```

```


    else
      skip_white (pred i) in
      skip_white (pred len)
let gobble_white buffer =
  substring buffer (first_non_white buffer) (last_non_white buffer)
let gobble_arrows buffer =
  let imax = String.length buffer - 1 in
  if imax ≥ 0 then
    gobble_white
      (substring buffer
        (if buffer.[0] = '>' then 1 else 0)
        (if buffer.[imax] = '<' then pred imax else imax))
  else
    ""
let fold_lines ic f init =
  let rec fold_lines' acc =
    let continue =
      try
        let acc' = f (input_line ic) acc in
        fun () → fold_lines' acc'
      with
        | End_of_file → fun () → acc in
    continue () in
  fold_lines' init
let column_tabs line =
  let len = String.length line in
  let rec tabs' acc i =
    if i ≥ len then
      List.rev acc
    else if line.[i] = '|' then
      tabs' (i :: acc) (succ i)
    else
      tabs' acc (succ i)
  in
  tabs' [] 0
let columns tabs line =
  let imax = String.length line - 1 in
  let rec columns' acc i = function
    | [] → List.rev_map gobble_white (substring line i imax :: acc)
    | tab :: rest →
      if tab < i then
        invalid_arg "columns: clash"
      else if (match rest with [] → false | _ → true)
        ∧ line.[tab] ≠ '|' then
        invalid_arg "columns: expecting '|'"
      else
        columns' (substring line i (pred tab) :: acc) (succ tab) rest
  in

```

```

    columns' [] 0 tabs
let input_table name =
  let ic = open_in name in
  let model = input_line ic in
  let table = input_line ic in
  let line = input_line ic in
  let tabs = column_tabs line in
  let titles = columns tabs line in
  let rows = fold_lines ic (fun line acc →
    if String.length line > 0 ∧ line.[0] = '=' then
      acc
    else
      columns tabs line :: acc) [] in
  close_in ic;
  (gobble_white model, gobble_white table, List.map gobble_arrows titles, rows)
let substitute_char (cold, cnew) s =
  for i = 0 to String.length s - 1 do
    if s.[i] = cold then
      s.[i] ← cnew
  done;
  s
let sanitize_symbol s =
  List.fold_right substitute_char [( '+', 'p' ); ( '-', 'm' )] (String.copy s)

```


 Fodder for a future *Coupling* module ...

```

let rec fermion_of_lorentz = function
| Coupling.Spinor → 1
| Coupling.ConjSpinor → -1
| Coupling.Majorana → 1
| Coupling.Maj_Ghost → 1
| Coupling.Vectorspinor → 1
| Coupling.Vector | Coupling.Massive_Vector → 0
| Coupling.Scalar | Coupling.Tensor_1 | Coupling.Tensor_2 → 0
| Coupling.BRS f → fermion_of_lorentz f

let rec conjugate_lorentz = function
| Coupling.Spinor → Coupling.ConjSpinor
| Coupling.ConjSpinor → Coupling.Spinor
| Coupling.BRS f → Coupling.BRS (conjugate_lorentz f)
| f → f

```

 Currently, this operates on the sanitized symbol names.

```

let pdg_heuristic name =
  match name with

```

```

| "e1" → 11 | "E1" → -11 | "n1" → 12 | "N1" → -12
| "e2" → 13 | "E2" → -13 | "n2" → 14 | "N2" → -14
| "e3" → 15 | "E3" → -15 | "n3" → 16 | "N3" → -16
| "u" → 2 | "U" → -2 | "d" → 1 | "D" → -1
| "c" → 4 | "C" → -4 | "s" → 3 | "S" → -3
| "t" → 6 | "T" → -6 | "b" → 5 | "B" → -5
| "G" → 21 | "A" → 22 | "Z" → 23
| "Wp" → 24 | "Wm" → -24 | "H" → 25
| _ → invalid_arg ("pdg_heuristic_ failed:_" ^ name)

module Model =
  struct
    type flavor = int
    type constant = string
    type gauge = unit
    type orders = unit

    module M = Modeltools.Mutable
      (struct type f = flavor type g = gauge type c = constant type o = orders end)

    let orders = M.orders
    let flavors = M.flavors
    let external_flavors = M.external_flavors
    let lorentz = M.lorentz
    let color = M.color
    let propagator = M.propagator
    let width = M.width
    let goldstone = M.goldstone
    let conjugate = M.conjugate
    let fermion = M.fermion
    let vertices = M.vertices
    let fuse2 = M.fuse2
    let fuse3 = M.fuse3
    let fuse = M.fuse
    let max_degree = M.max_degree
    let parameters = M.parameters
    let flavor_of_string = M.flavor_of_string
    let flavor_to_string = M.flavor_to_string
    let flavor_to_TeX = M.flavor_to_TeX
    let flavor_symbol = M.flavor_symbol
    let gauge_symbol = M.gauge_symbol
    let pdg = M.pdg
    let mass_symbol = M.mass_symbol
    let width_symbol = M.width_symbol
    let constant_symbol = M.constant_symbol
    module Ch = M.Ch
    let charges = M.charges

    let rcs = rcs_file

    type symbol =
      | Selfconjugate of string

```

```

| Conjugates of string × string

type particle =
{ p_name : string;
  p_symbol : symbol;
  p_spin : Coupling.lorentz;
  p_mass : Comphep_syntax.raw;
  p_width : Comphep_syntax.raw;
  p_color : Color.t;
  p_aux : string option }

let count_flavors particles =
List.fold_left (fun n p → n +
  match p.p_symbol with
  | Selfconjugate _ → 1
  | Conjugates _ → 2) 0 particles

type particle_flavor =
{ f_name : string;
  f_conjugate : int;
  f_symbol : string;
  f_pdg : int;
  f_spin : Coupling.lorentz;
  f_propagator : gauge Coupling.propagator;
  f_fermion : int;
  f_mass : string;
  f_width : string;
  f_color : Color.t;
  f_aux : string option }

let real_variable = function
| Comphep_syntax.Integer 0 → "zero"
| Comphep_syntax.Symbol s → s
| _ → invalid_arg "real_variable"

let dummy_flavor =
{ f_name = "";
  f_conjugate = -1;
  f_symbol = "";
  f_pdg = 0;
  f_spin = Coupling.Scalar;
  f_propagator = Coupling.Prop_Scalar;
  f_fermion = 0;
  f_mass = real_variable (Comphep_syntax.integer 0);
  f_width = real_variable (Comphep_syntax.integer 0);
  f_color = Color.Singlet;
  f_aux = None }

let propagator_of_lorentz = function
| Coupling.Scalar → Coupling.Prop_Scalar
| Coupling.Spinor → Coupling.Prop_Spinor
| Coupling.ConjSpinor → Coupling.Prop_ConjSpinor
| Coupling.Majorana → Coupling.Prop_Majorana

```



```

| Coupling.Maj_Ghost → invalid_arg
|   "propagator_of_lorentz:␣SUSY␣ghosts␣do␣not␣propagate"
| Coupling.Vector → Coupling.Prop_Feynman
| Coupling.Massive_Vector → Coupling.Prop_Unitarity
| Coupling.Vectorspinor →
|   invalid_arg "propagator_of_lorentz:␣Vectorspinor"
| Coupling.Tensor_1 → invalid_arg "propagator_of_lorentz:␣Tensor_1"
| Coupling.Tensor_2 → invalid_arg "propagator_of_lorentz:␣Tensor_2"
| Coupling.BRS_ → invalid_arg "propagator_of_lorentz:␣no␣BRST"

let flavor_of_particle symbol conjg particle =
  let spin = particle.p_spin in
  { f_name = particle.p_name;
    f_conjugate = conjg;
    f_symbol = symbol;
    f_pdg = pdg_heuristic symbol;
    f_spin = spin;
    f_propagator = propagator_of_lorentz spin;
    f_fermion = fermion_of_lorentz spin;
    f_mass = real_variable particle.p_mass;
    f_width = real_variable particle.p_width;
    f_color = particle.p_color;
    f_aux = particle.p_aux }

let flavor_of_antiparticle symbol conjg particle =
  let spin = conjugate_lorentz particle.p_spin in
  { f_name = "anti-" ^ particle.p_name;
    f_conjugate = conjg;
    f_symbol = symbol;
    f_pdg = pdg_heuristic symbol;
    f_spin = spin;
    f_propagator = propagator_of_lorentz spin;
    f_fermion = fermion_of_lorentz spin;
    f_mass = real_variable particle.p_mass;
    f_width = real_variable particle.p_width;
    f_color = Color.conjugate particle.p_color;
    f_aux = particle.p_aux }

let parse_expr text =
  try
    Comphep_parser.expr Comphep_lexer.token (Lexing.from_string text)
  with
  | Parsing.Parse_error → invalid_arg ("parse␣error:␣" ^ text)

let parse_function_row = function
| name :: fct :: comment :: _ → (name, parse_expr fct, comment)
| _ → invalid_arg "parse_function_row"

let parse_lagrangian_row = function
| p1 :: p2 :: p3 :: p4 :: c :: t :: _ →
  ((p1, p2, p3, p4), parse_expr c, parse_expr t)
| _ → invalid_arg "parse_lagrangian_row"

```

```

let parse_symbol s1 s2 =
  if s1 = s2 then
    Selfconjugate (sanitize_symbol s1)
  else
    Conjugates (sanitize_symbol s1, sanitize_symbol s2)

let parse_spin spin =
  match int_of_string spin with
  | 0 → Coupling.Scalar
  | 1 → Coupling.Spinor
  | 2 → Coupling.Vector
  | _ → invalid_arg ("parse_spin:␣spin␣=" ^ spin)

let parse_color color =
  match int_of_string color with
  | 1 → Color.Singlet
  | 3 → Color.SUN 3
  | 8 → Color.AdjSUN 3
  | _ → invalid_arg ("parse_color:␣color␣=" ^ color)

let parse_particle_row = function
| name :: symbol :: symbol_cc :: spin :: mass :: width :: color ::
  aux :: _ →
  { p_name = name;
    p_symbol = parse_symbol symbol symbol_cc;
    p_spin = parse_spin spin;
    p_mass = parse_expr mass;
    p_width = parse_expr width;
    p_color = parse_color color;
    p_aux = match aux with "" → None | _ → Some aux }
| _ → invalid_arg "parse_particle_row"

let parse_variable_row = function
| name :: value :: comment :: _ →
  (name, float_of_string value, comment)
| _ → invalid_arg "parse_variable_row"

let parse_table parse_row name =
  let model, table, titles, rows = input_table name in
  (model, table, titles, List.rev_map parse_row rows)

let input_functions = parse_table parse_function_row
let input_lagrangian = parse_table parse_lagrangian_row
let input_particles = parse_table parse_particle_row
let input_variables = parse_table parse_variable_row

let input_model dir idx =
  let idx = string_of_int idx in
  (input_particles (dir ^ "/prtcls" ^ idx ^ ".mdl"),
   input_variables (dir ^ "/vars" ^ idx ^ ".mdl"),
   input_functions (dir ^ "/func" ^ idx ^ ".mdl"),
   input_lagrangian (dir ^ "/lgrng" ^ idx ^ ".mdl"))

let flavors_of_particles particles =

```

```

let flavors = Array.create (count_flavors particles) dummy_flavor in
ignore (List.fold_left (fun n p →
  match p.p_symbol with
  | Selfconjugate f →
    flavors.(n) ← flavor_of_particle f n p;
    n + 1
  | Conjugates (f1, f2) →
    flavors.(n) ← flavor_of_particle f1 (n + 1) p;
    flavors.(n + 1) ← flavor_of_antiparticle f2 n p;
    n + 2) 0 particles);
flavors

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let translate_tensor3 _ = Coupling.Scalar_Scalar_Scalar 1
let translate_tensor4 _ = Coupling.Scalar4 1
let translate_constant _ = ""

let init_flavors_variables_functions_vertices =
  let fmax = Array.length flavors - 1 in
  let flist = ThoList.range 0 fmax in
  let clamp_flavor msg f =
    if f ≥ 0 ∨ f ≤ fmax then
      f
    else
      invalid_arg (msg ^ ":invalid flavor:" ^ string_of_int f) in
  let flavor_hash = Hashtbl.create 37 in
  let flavor_of_string s =
    try
      Hashtbl.find flavor_hash s
    with
    | Not_found → invalid_arg ("flavor_of_string:" ^ s) in
  for f = 0 to fmax do
    Hashtbl.add flavor_hash flavors.(f).f_symbol f
  done;
  let vertices3, vertices4 =
    List.fold_left (fun (v3, v4) ((p1, p2, p3, p4), c, t) →
      if p4 = "" then
        ((flavor_of_string p1, flavor_of_string p2, flavor_of_string p3),
         translate_tensor3 t, translate_constant c) :: v3, v4)
      else
        (v3, ((flavor_of_string p1, flavor_of_string p2,
          flavor_of_string p3, flavor_of_string p4),
          translate_tensor4 t, translate_constant c) :: v4))
      ([], []) vertices in
  let max_degree = match vertices4 with [] → 3 | _ → 4 in
  let all_vertices () = (vertices3, vertices4, []) in

```

```

let table = F.of_vertices (all_vertices ()) in
let input_parameters =
  (real_variable (Comphep_syntax.integer 0), 0.0) ::
  (List.map (fun (n, v, _) → (n, v)) variables) in
let derived_parameters =
  List.map (fun (n, f, _) → (Coupling.Real n, Coupling.Const 0))
    functions in
M.setup
~color : (fun f → flavors.(clamp_flavor "color" f).f_color)
~pdg : (fun f → flavors.(clamp_flavor "pdg" f).f_pdg)
~lorentz : (fun f → flavors.(clamp_flavor "spin" f).f_spin)
~propagator : (fun f →
  flavors.(clamp_flavor "propagator" f).f_propagator)
~width : (fun f → Coupling.Constant)
~goldstone : (fun f → None)
~conjugate : (fun f → flavors.(clamp_flavor "conjugate" f).f_conjugate)
~fermion : (fun f → flavors.(clamp_flavor "fermion" f).f_fermion)
~max_degree
~vertices : all_vertices
~fuse : (F.fuse2 table, F.fuse3 table, F.fuse table)
~flavors : ([("All_␣Flavors", flist)])
~parameters : (fun () →
  { Coupling.input = input_parameters;
    Coupling.derived = derived_parameters;
    Coupling.derived_arrays = [] })
~flavor_of_string
~flavor_to_string : (fun f →
  flavors.(clamp_flavor "flavor_to_string" f).f_name)
~flavor_to_TeX : (fun f →
  flavors.(clamp_flavor "flavor_to_TeX" f).f_name)
~flavor_symbol : (fun f →
  flavors.(clamp_flavor "flavor_symbol" f).f_symbol)
~gauge_symbol : (fun () → "")
~mass_symbol : (fun f →
  flavors.(clamp_flavor "mass_symbol" f).f_mass)
~width_symbol : (fun f →
  flavors.(clamp_flavor "width_symbol" f).f_width)
~constant_symbol : (fun c → failwith "constant_symbol")

let particles_file = ref "prtcls1.mdl"
let variables_file = ref "vars1.mdl"
let functions_file = ref "func1.mdl"
let lagrangian_file = ref "lgrng1.mdl"

let load () =
  let (_, -, -, p), v, f, l =
    (input_particles !particles_file, input_variables !variables_file,
     input_functions !functions_file, input_lagrangian !lagrangian_file) in
  init (flavors_of_particles p) [] [] []

let options = Options.create
  [ ("p", Arg.String (fun name → particles_file := name),

```

```

"CompHEP_particles_file_(default:_ ^ !particles_file ^ ")");
("v", Arg.String (fun name → variables_file := name),
"CompHEP_variables_file_(default:_ ^ !variables_file ^ ")");
("f", Arg.String (fun name → functions_file := name),
"CompHEP_functions_file_(default:_ ^ !functions_file ^ ")");
("l", Arg.String (fun name → lagrangian_file := name),
"CompHEP_lagrangian_file_(default:_ ^ !lagrangian_file ^ ")");
("exec", Arg.Unit load,
"load_the_model_files_(required_before_any_particle)");
("help", Arg.Unit (fun () →
  print_endline
    ("[" ^ String.concat "|"
      (List.map M.flavor_to_string (M.flavors ())) ^ "]")),
  "print_information_on_the_model")]
```

end

—15—

HARDCODED TARGETS

15.1 *Interface of Targets*

```
module Dummy : Target.Maker
```

15.1.1 *Supported Targets*

```
module Fortran : Target.Maker  
module Fortran_Majorana : Target.Maker
```

15.1.2 *Potential Targets*

```
module VM : Target.Maker  
module Fortran77 : Target.Maker  
module C : Target.Maker  
module Cpp : Target.Maker  
module Java : Target.Maker  
module Ocaml : Target.Maker  
module LaTeX : Target.Maker
```

15.2 *Implementation of Targets*

```
let rsc_file = RCS.parse "Targets" ["Code_Generation"]  
  { RCS.revision = "$Revision: 4662$";  
    RCS.date = "$Date: 2013-09-23 15:21:34 +0200 (Mon, 23 Sep 2013)$";  
    RCS.author = "$Author: msekulla$";  
    RCS.source  
      = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg  
module Dummy (F : Fusion.Maker) (P : Momentum.T) (M : Model.T) =  
  struct  
    let rsc_list = []  
    type amplitudes = Fusion.Multi(F)(P)(M).amplitudes
```

```

type diagnostic = All | Arguments | Momenta | Gauge
let options = Options.empty
let amplitudes_to_channel cmdline oc amplitudes = failwith "Targets.Dummy"
let parameters_to_channel oc = failwith "Targets.Dummy"
end

```

15.2.1 Fortran 90/95

Dirac Fermions

We factor out the code for fermions so that we can use the simpler implementation for Dirac fermions if the model contains no Majorana fermions.

```

module type Fermions =
sig
  open Coupling
  val psi_type : string
  val psibar_type : string
  val chi_type : string
  val grav_type : string
  val psi_incoming : string
  val brs_psi_incoming : string
  val psibar_incoming : string
  val brs_psibar_incoming : string
  val chi_incoming : string
  val brs_chi_incoming : string
  val grav_incoming : string
  val psi_outgoing : string
  val brs_psi_outgoing : string
  val psibar_outgoing : string
  val brs_psibar_outgoing : string
  val chi_outgoing : string
  val brs_chi_outgoing : string
  val grav_outgoing : string
  val psi_propagator : string
  val psibar_propagator : string
  val chi_propagator : string
  val grav_propagator : string
  val psi_projector : string
  val psibar_projector : string
  val chi_projector : string
  val grav_projector : string
  val psi_gauss : string
  val psibar_gauss : string
  val chi_gauss : string
  val grav_gauss : string
  val print_current : int × fermionbar × boson × fermion →

```

```

    string → string → string → fuse2 → unit
val print_current_mom : int × fermionbar × boson × fermion →
    string → string → string → string → string → string
    → fuse2 → unit
val print_current_p : int × fermion × boson × fermion →
    string → string → string → fuse2 → unit
val print_current_b : int × fermionbar × boson × fermionbar →
    string → string → string → fuse2 → unit
val print_current_g : int × fermionbar × boson × fermion →
    string → string → string → string → string → string
    → fuse2 → unit
val print_current_g4 : int × fermionbar × boson2 × fermion →
    string → string → string → string → fuse3 → unit
val reverse_braket : lorentz → bool
val use_module : string
val require_library : string list
val rcs : RCS.t
end

module Fortran_Fermions : Fermions =
struct
  let rcs = RCS.rename rcs_file "Targets.Fortran_Fermions()"
    [ "generates_Fortran95_code_for_Dirac_fermions";
      "using_revision_2000_10_A_of_module_omega95" ]

  open Coupling
  open Format

  let psi_type = "spinor"
  let psibar_type = "conjspinor"
  let chi_type = "???"
  let grav_type = "???"

  let psi_incoming = "u"
  let brs_psi_incoming = "brs_u"
  let psibar_incoming = "vbar"
  let brs_psibar_incoming = "brs_vbar"
  let chi_incoming = "???"
  let brs_chi_incoming = "???"
  let grav_incoming = "???"
  let psi_outgoing = "v"
  let brs_psi_outgoing = "brs_v"
  let psibar_outgoing = "ubar"
  let brs_psibar_outgoing = "brs_ubar"
  let chi_outgoing = "???"
  let brs_chi_outgoing = "???"
  let grav_outgoing = "???"

  let psi_propagator = "pr_psi"
  let psibar_propagator = "pr_psibar"
  let chi_propagator = "???"
  let grav_propagator = "???"

```



```

let psi_projector = "pj-psi"
let psibar_projector = "pj-psibar"
let chi_projector = "???"
let grav_projector = "???"

let psi_gauss = "pg-psi"
let psibar_gauss = "pg-psibar"
let chi_gauss = "???"
let grav_gauss = "???"

let format_coupling coeff c =
  match coeff with
  | 1 → c
  | -1 → "(-" ^ c ^ ")"
  | coeff → string_of_int coeff ^ "*" ^ c

let format_coupling_2 coeff c =
  match coeff with
  | 1 → c
  | -1 → "-" ^ c
  | coeff → string_of_int coeff ^ "*" ^ c

```



JR's coupling constant HACK, necessitated by tho's bad design descition.

```

let fastener s i ?p () =
  try
    let offset = (String.index s '(') in
    if ((String.get s (String.length s - 1)) ≠ ')') then
      failwith "fastener: wrong usage of parentheses"
    else
      let func_name = (String.sub s 0 offset) and
      tail =
        (String.sub s (succ offset) (String.length s - offset - 2)) in
      if (String.contains func_name ')') ∨
        (String.contains tail '(') ∨
        (String.contains tail ')') then
        failwith "fastener: wrong usage of parentheses"
      else
        func_name ^ "(" ^ string_of_int i ^ ", " ^ tail ^ ")"
  with
  | Not_found →
    if (String.contains s ')') then
      failwith "fastener: wrong usage of parentheses"
    else
      match p with
      | None → s ^ "(" ^ string_of_int i ^ ")"
      | Some p → s ^ "(" ^ p ^ "*" ^ p ^ ", " ^ string_of_int i ^ ")"

let print_fermion_current coeff f c wf1 wf2 fusion =
  let c = format_coupling coeff c in
  match fusion with

```

```

| F13 → printf "%s_ff(%s,%s,%s)" f c wf1 wf2
| F31 → printf "%s_ff(%s,%s,%s)" f c wf2 wf1
| F23 → printf "f_%sf(%s,%s,%s)" f c wf1 wf2
| F32 → printf "f_%sf(%s,%s,%s)" f c wf2 wf1
| F12 → printf "f_f%s(%s,%s,%s)" f c wf1 wf2
| F21 → printf "f_f%s(%s,%s,%s)" f c wf2 wf1

```



Using a two element array for the combined vector-axial and scalar-pseudo couplings helps to support HELAS as well. Since we will probably never support general boson couplings with HELAS, it might be retired in favor of two separate variables. For this *Model.constant_symbol* has to be generalized.



NB: passing the array instead of two separate constants would be a *bad* idea, because the support for Majorana spinors below will have to flip signs!

```

let print_fermion_current2 coeff f c wf1 wf2 fusion =
  let c = format_coupling_2 coeff c in
  let c1 = fastener c 1 ()
  and c2 = fastener c 2 () in
  match fusion with
  | F13 → printf "%s_ff(%s,%s,%s,%s)" f c1 c2 wf1 wf2
  | F31 → printf "%s_ff(%s,%s,%s,%s)" f c1 c2 wf2 wf1
  | F23 → printf "f_%sf(%s,%s,%s,%s)" f c1 c2 wf1 wf2
  | F32 → printf "f_%sf(%s,%s,%s,%s)" f c1 c2 wf2 wf1
  | F12 → printf "f_f%s(%s,%s,%s,%s)" f c1 c2 wf1 wf2
  | F21 → printf "f_f%s(%s,%s,%s,%s)" f c1 c2 wf2 wf1

let print_fermion_current_mom1 coeff f c wf1 wf2 p1 p2 p12 fusion =
  let c = format_coupling coeff c in
  let c1 = fastener c 1 and
      c2 = fastener c 2 in
  match fusion with
  | F13 → printf "%s_ff(%s,%s,%s,%s)" f (c1 ~p : p12 ()) (c2 ~p :
p12 ()) wf1 wf2
  | F31 → printf "%s_ff(%s,%s,%s,%s)" f (c1 ~p : p12 ()) (c2 ~p :
p12 ()) wf2 wf1
  | F23 → printf "f_%sf(%s,%s,%s,%s)" f (c1 ~p : p1 ()) (c2 ~p :
p1 ()) wf1 wf2
  | F32 → printf "f_%sf(%s,%s,%s,%s)" f (c1 ~p : p2 ()) (c2 ~p :
p2 ()) wf2 wf1
  | F12 → printf "f_f%s(%s,%s,%s,%s)" f (c1 ~p : p2 ()) (c2 ~p :
p2 ()) wf1 wf2
  | F21 → printf "f_f%s(%s,%s,%s,%s)" f (c1 ~p : p1 ()) (c2 ~p :
p1 ()) wf2 wf1

let print_fermion_current_mom2 coeff f c wf1 wf2 p1 p2 p12 fusion =
  let c = format_coupling coeff c in

```

```

let c1 = fastener c 1 and
    c2 = fastener c 2 in
match fusion with
| F13 → printf "%s_ff(%s,%s,@,%s,%s,%s)" f (c1 ~p : p12 ()) (c2 ~p :
p12 ()) wf1 wf2 p12
| F31 → printf "%s_ff(%s,%s,@,%s,%s,%s)" f (c1 ~p : p12 ()) (c2 ~p :
p12 ()) wf2 wf1 p12
| F23 → printf "f_%sf(%s,%s,@,%s,%s,%s)" f (c1 ~p : p1 ()) (c2 ~p :
p1 ()) wf1 wf2 p1
| F32 → printf "f_%sf(%s,%s,@,%s,%s,%s)" f (c1 ~p : p2 ()) (c2 ~p :
p2 ()) wf2 wf1 p2
| F12 → printf "f_f%s(%s,%s,@,%s,%s,%s)" f (c1 ~p : p2 ()) (c2 ~p :
p2 ()) wf1 wf2 p2
| F21 → printf "f_f%s(%s,%s,@,%s,%s,%s)" f (c1 ~p : p1 ()) (c2 ~p :
p1 ()) wf2 wf1 p1

let print_current = function
| coeff, Psibar, VA, Psi → print_fermion_current2 coeff "va"
| coeff, Psibar, VA2, Psi → print_fermion_current coeff "va2"
| coeff, Psibar, V, Psi → print_fermion_current coeff "v"
| coeff, Psibar, A, Psi → print_fermion_current coeff "a"
| coeff, Psibar, VL, Psi → print_fermion_current coeff "vl"
| coeff, Psibar, VR, Psi → print_fermion_current coeff "vr"
| coeff, Psibar, VLR, Psi → print_fermion_current2 coeff "vlr"
| coeff, Psibar, SP, Psi → print_fermion_current2 coeff "sp"
| coeff, Psibar, S, Psi → print_fermion_current coeff "s"
| coeff, Psibar, P, Psi → print_fermion_current coeff "p"
| coeff, Psibar, SL, Psi → print_fermion_current coeff "sl"
| coeff, Psibar, SR, Psi → print_fermion_current coeff "sr"
| coeff, Psibar, SLR, Psi → print_fermion_current2 coeff "slr"
| coeff, Psibar, _, Psi → invalid_arg
    "Targets.Fortran.Fermions:_no_superpotential_here"
| _, Chibar, _, _ | _, _, _, Chi → invalid_arg
    "Targets.Fortran.Fermions:_Majorana_spinors_not_handled"
| _, Gravbar, _, _ | _, _, _, Grav → invalid_arg
    "Targets.Fortran.Fermions:_Gravitinos_not_handled"

let print_current_mom = function
| coeff, Psibar, VLRM, Psi → print_fermion_current_mom1 coeff "vlr"
| coeff, Psibar, SPM, Psi → print_fermion_current_mom1 coeff "sp"
| coeff, Psibar, TVA, Psi → print_fermion_current_mom1 coeff "tva"
| coeff, Psibar, TVAM, Psi → print_fermion_current_mom2 coeff "tvam"
| coeff, Psibar, TLR, Psi → print_fermion_current_mom1 coeff "tlr"
| coeff, Psibar, TLRM, Psi → print_fermion_current_mom2 coeff "tlrm"
| coeff, Psibar, TRL, Psi → print_fermion_current_mom1 coeff "trl"
| coeff, Psibar, TRLM, Psi → print_fermion_current_mom2 coeff "trlm"
| coeff, Psibar, _, Psi → invalid_arg
    "Targets.Fortran.Fermions:_only_sigma_tensor_coupling_here"
| _, Chibar, _, _ | _, _, _, Chi → invalid_arg
    "Targets.Fortran.Fermions:_Majorana_spinors_not_handled"
| _, Gravbar, _, _ | _, _, _, Grav → invalid_arg

```

```

    "Targets.Fortran.Fermions:_Gravitinos_not_handled"
let print_current_p = function
| -, -, -, - → invalid_arg
    "Targets.Fortran.Fermions:_No_clashing_arrows_here"
let print_current_b = function
| -, -, -, - → invalid_arg
    "Targets.Fortran.Fermions:_No_clashing_arrows_here"
let print_current_g = function
| -, -, -, - → invalid_arg
    "Targets.Fortran.Fermions:_No_gravitinos_here"
let print_current_g4 = function
| -, -, -, - → invalid_arg
    "Targets.Fortran.Fermions:_No_gravitinos_here"
let reverse_braket = function
| Spinor → true
| - → false
let use_module = "omega95"
let require_library =
["omega.spinors.2010_01_A"; "omega.spinor_cpls.2010_01_A"]
end

```

Main Functor

```

module Make_Fortran (Fermions : Fermions)
(Fusion_Maker : Fusion.Maker) (P : Momentum.T) (M : Model.T) =
struct
let rcs_list =
[ RCS.rename rcs_file "Targets.Make_Fortran()"
  [ "Interface_for_Whizard2.X";
    "NB:_non-gauge_vector_couplings_are_not_available_yet" ];
  Fermions.rcs ]
let require_library =
Fermions.require_library @
[ "omega_vectors.2010_01_A"; "omega_polarizations.2010_01_A";
  "omega_couplings.2010_01_A"; "omega_color.2010_01_A";
  "omega_utils.2010_01_A" ]
module CM = Colorize.It(M)
module F = Fusion_Maker(P)(M)
type amplitude = F.amplitude
module CF = Fusion.Multi(Fusion_Maker)(P)(M)
type amplitudes = CF.amplitudes
open Coupling
open Format

```

```

type output_mode =
  | Single_Function
  | Single_Module of int
  | Single_File of int
  | Multi_File of int

let line_length = ref 80
let continuation_lines = ref (-1) (* 255 *)
let kind = ref "default"
let fortran95 = ref true
let module_name = ref "omega_amplitude"
let output_mode = ref (Single_Module 10)
let use_modules = ref []
let whizard = ref false
let parameter_module = ref ""
let md5sum = ref None
let no_write = ref false
let km_write = ref false
let km_pure = ref false
let openmp = ref false

let options = Options.create
[ "90", Arg.Clear fortran95,
  "don't use Fortran95 features that are not in Fortran90";
  "kind", Arg.String (fun s → kind := s),
  "real and complex kind (default: " ^ !kind ^ ")";
  "width", Arg.Int (fun w → line_length := w), "maximum line length";
  "continuation", Arg.Int (fun l → continuation_lines := l),
  "maximum # of continuation lines";
  "module", Arg.String (fun s → module_name := s), "module name";
  "single_function", Arg.Unit (fun () → output_mode := Single_Function),
  "compute the matrix element(s) in a monolithic function";
  "split_function", Arg.Int (fun n → output_mode := Single_Module n),
  "split the matrix element(s) into small functions [default, size=10]";
  "split_module", Arg.Int (fun n → output_mode := Single_File n),
  "split the matrix element(s) into small modules";
  "split_file", Arg.Int (fun n → output_mode := Multi_File n),
  "split the matrix element(s) into small files";
  "use", Arg.String (fun s → use_modules := s :: !use_modules),
  "use module";
  "parameter_module", Arg.String (fun s → parameter_module := s),
  "parameter module";
  "md5sum", Arg.String (fun s → md5sum := Some s),
  "transfer MD5 checksum";
  "whizard", Arg.Set whizard, "include WHIZARD interface";
  "no_write", Arg.Set no_write, "no 'write' statements";
  "kmatrix_write", Arg.Set km_write, "write K matrix functions";
  "kmatrix_write_pure", Arg.Set km_pure, "write K matrix pure functions";
  "openmp", Arg.Set openmp, "activate OpenMP support in generated code"]

```

Fortran style line continuation:

Default function to output spaces (copied from `format.ml`).

```

let blank_line = String.make 80 ' '
let rec display_blanks oc n =
  if n > 0 then
    if n ≤ 80 then
      output oc blank_line 0 n
    else begin
      output oc blank_line 0 80;
      display_blanks oc (n - 80)
    end
  end

```

Default function to output new lines (copied from `format.ml`).

```

let display_newline oc () =
  output oc "\n" 0 1

```

`current_continuation_line`

- ≤ 0 : not continuing: print a straight newline,
- > 0 : continuing: append "`␣&`" until we run up to `!continuation_lines`.
NB: `!continuation_lines < 0` means *unlimited* continuation lines.

```

let current_continuation_line = ref 1
exception Continuation_Lines of int

let fortran_newline oc () =
  if !current_continuation_line > 0 then begin
    if !continuation_lines ≥ 0 ∧ !current_continuation_line > !continuation_lines then
      raise (Continuation_Lines !current_continuation_line)
    else begin
      output oc "␣&" 0 2;
      incr current_continuation_line
    end
  end;
  display_newline oc ()

let nl () =
  current_continuation_line := 0;
  print_newline ();
  current_continuation_line := 1

```

Make a formatter with default functions to output spaces and new lines.

```

let setup_fortran_formatter width oc =
  set_all_formatter_output_functions
    ~out : (output oc)
    ~flush : (fun () → flush oc)
    ~newline : (fortran_newline oc)
    ~spaces : (display_blanks oc);
  set_margin (width - 2)

let print_list = function
| [] → ()
| a :: rest →
  print_string a;

```

```
List.iter (fun s → printf ",@_%s" s) rest
```

Variables and Declarations

"NC" is already used up in the module "constants":

```
let nc_parameter = "N_"
let omega_color_factor_abbrev = "OCF"
let openmp_tld_type = "thread_local_data"
let openmp_tld = "tld"

let flavors_symbol ?(decl = false) flavors =
  (if !openmp ∧ ¬ decl then openmp_tld ^ "%" else "" ) ^
  "oks_" ^ String.concat "" (List.map CM.flavor_symbol flavors)

let p2s p =
  if p ≥ 0 ∧ p ≤ 9 then
    string_of_int p
  else if p ≤ 36 then
    String.make 1 (Char.chr (Char.code 'A' + p - 10))
  else
    "_"

let format_momentum p =
  "p" ^ String.concat "" (List.map p2s p)

let format_p wf =
  String.concat "" (List.map p2s (F.momentum_list wf))

let ext_momentum wf =
  match F.momentum_list wf with
  | [n] → n
  | _ → invalid_arg "Targets.Fortran.ext_momentum"

module PSet = Set.Make (struct type t = int list let compare = compare end)
module WFSets = Set.Make (struct type t = F.wf let compare = compare end)

let add_tag wf name =
  match F.wf_tag wf with
  | None → name
  | Some tag → name ^ "_" ^ tag

let variable ?(decl = false) wf =
  (if !openmp ∧ ¬ decl then openmp_tld ^ "%" else "")
  ^ add_tag wf ("owf_" ^ CM.flavor_symbol (F.flavor wf) ^ "_" ^ format_p wf)

let momentum wf = "p" ^ format_p wf
let spin wf = "s(" ^ string_of_int (ext_momentum wf) ^ ")"

let format_multiple_variable ?(decl = false) wf i =
  variable ~decl : decl wf ^ "_X" ^ string_of_int i

let multiple_variable ?(decl = false) amplitude dictionary wf =
  try
    format_multiple_variable ~decl : decl wf (dictionary amplitude wf)
```

```

with
| Not_found → variable wf
let multiple_variables ?(decl = false) multiplicity wf =
  try
    List.map
      (format_multiple_variable ~decl : decl wf)
      (ThoList.range 1 (multiplicity wf))
  with
  | Not_found → [variable ~decl : decl wf]
let declaration_chunk_size = 64
let declare_list_chunk multiplicity t = function
| [] → ()
| wfs →
  printf "~~~~~@(<2>%s:::" t;
  print_list (ThoList.flatmap (multiple_variables ~decl : true multiplicity) wfs); nl ()
let declare_list multiplicity t = function
| [] → ()
| wfs →
  List.iter
    (declare_list_chunk multiplicity t)
    (ThoList.chopn declaration_chunk_size wfs)
type declarations =
{ scalars : F.wf list;
  spinors : F.wf list;
  conjspinors : F.wf list;
  realspinors : F.wf list;
  ghostspinors : F.wf list;
  vectorspinors : F.wf list;
  vectors : F.wf list;
  ward_vectors : F.wf list;
  massive_vectors : F.wf list;
  tensors_1 : F.wf list;
  tensors_2 : F.wf list;
  brs_scalars : F.wf list;
  brs_spinors : F.wf list;
  brs_conjspinors : F.wf list;
  brs_realspinors : F.wf list;
  brs_vectorspinors : F.wf list;
  brs_vectors : F.wf list;
  brs_massive_vectors : F.wf list }
let rec classify_wfs' acc = function
| [] → acc
| wf :: rest →
  classify_wfs'
    (match CM.lorentz (F.flavor wf) with
    | Scalar → {acc with scalars = wf :: acc.scalars}
    | Spinor → {acc with spinors = wf :: acc.spinors})

```

```

| ConjSpinor → {acc with conjspinors = wf :: acc.conjspinors}
| Majorana → {acc with realspinors = wf :: acc.realspinors}
| Maj_Ghost → {acc with ghostspinors = wf :: acc.ghostspinors}
| Vectorspinor →
  {acc with vectorspinors = wf :: acc.vectorspinors}
| Vector → {acc with vectors = wf :: acc.vectors}
| Massive_Vector →
  {acc with massive_vectors = wf :: acc.massive_vectors}
| Tensor_1 → {acc with tensors_1 = wf :: acc.tensors_1}
| Tensor_2 → {acc with tensors_2 = wf :: acc.tensors_2}
| BRS_Scalar → {acc with brs_scalars = wf :: acc.brs_scalars}
| BRS_Spinor → {acc with brs_spinors = wf :: acc.brs_spinors}
| BRS_ConjSpinor → {acc with brs_conjspinors =
  wf :: acc.brs_conjspinors}
| BRS_Majorana → {acc with brs_realspinors =
  wf :: acc.brs_realspinors}
| BRS_Vectorspinor → {acc with brs_vectorspinors =
  wf :: acc.brs_vectorspinors}
| BRS_Vector → {acc with brs_vectors = wf :: acc.brs_vectors}
| BRS_Massive_Vector → {acc with brs_massive_vectors =
  wf :: acc.brs_massive_vectors}
| BRS_ → invalid_arg "Targets.wfs_classify':_not_needed_here"
rest
let classify_wfs wfs = classify_wfs'
{ scalars = []; spinors = []; conjspinors = []; realspinors = [];
  ghostspinors = []; vectorspinors = []; vectors = [];
  ward_vectors = [];
  massive_vectors = []; tensors_1 = []; tensors_2 = [];
  brs_scalars = []; brs_spinors = []; brs_conjspinors = [];
  brs_realspinors = []; brs_vectorspinors = [];
  brs_vectors = []; brs_massive_vectors = [] }
wfs

```

Parameters

```

type α parameters =
{ real_singles : α list;
  real_arrays : (α × int) list;
  complex_singles : α list;
  complex_arrays : (α × int) list }

let rec classify_singles acc = function
| [] → acc
| Real p :: rest → classify_singles
  { acc with real_singles = p :: acc.real_singles } rest
| Complex p :: rest → classify_singles
  { acc with complex_singles = p :: acc.complex_singles } rest

let rec classify_arrays acc = function

```

```

| [] → acc
| (Real_Array p, rhs) :: rest → classify_arrays
  { acc with real_arrays =
    (p, List.length rhs) :: acc.real_arrays } rest
| (Complex_Array p, rhs) :: rest → classify_arrays
  { acc with complex_arrays =
    (p, List.length rhs) :: acc.complex_arrays } rest

let classify_parameters params =
  classify_arrays
    (classify_singles
      { real_singles = [];
        real_arrays = [];
        complex_singles = [];
        complex_arrays = [] }
      (List.map fst params.derived)) params.derived_arrays

```



Unify this with the other code using *ThoList.chopn*.

```

let rec schisma n l =
  if List.length l ≤ n then
    [l]
  else
    let a, b = ThoList.splitn n l in
    [a] @ (schisma n b)

let rec schisma_num i n l =
  if List.length l ≤ n then
    [(i, l)]
  else
    let a, b = ThoList.splitn n l in
    [(i, a)] @ (schisma_num (i + 1) n b)

let declare_parameters' t = function
| [] → ()
| plist →
  printf "%s@ [<2>%s(kind=%s), %spublic, %s save %s:: %s" t !kind;
  print_list (List.map CM.constant_symbol plist); nl ()

let declare_parameters t plist =
  List.iter (declare_parameters' t) plist

let declare_parameter_array t (p, n) =
  printf "%s@ [<2>%s(kind=%s), %sdimension(%d), %spublic, %s save %s:: %s"
    t !kind n (CM.constant_symbol p); nl ()

let default_parameter (x, v) =
  printf "%s@ %s = %s" (CM.constant_symbol x) v !kind

let declare_default_parameters t = function
| [] → ()
| p :: plist →

```

```

    printf "%u@(<2>%s(kind=%s),_public,_save_::" t !kind;
    default_parameter p;
    List.iter (fun p' → printf ","; default_parameter p') plist;
    nl ()

let rec format_constant = function
| I → sprintf "cmplx_(0.0-_%s,_1.0-_%s)" !kind !kind
| Const c when c < 0 → sprintf "(%d.0-_%s)" c !kind
| Const c → sprintf "%d.0-_%s" c !kind
| _ → invalid_arg "format_constant"

let rec eval_parameter' = function
| I → printf "cmplx_(0.0-_%s,_1.0-_%s)" !kind !kind
| Const c when c < 0 → printf "(%d.0-_%s)" c !kind
| Const c → printf "%d.0-_%s" c !kind
| Atom x → printf "%s" (CM.constant_symbol x)
| Sum [] → printf "0.0-_%s" !kind
| Sum [x] → eval_parameter' x
| Sum (x :: xs) →
    printf "@,("; eval_parameter' x;
    List.iter (fun x → printf "@,_+"; eval_parameter' x) xs;
    printf ")"
| Diff (x, y) →
    printf "@,("; eval_parameter' x;
    printf "_-"; eval_parameter' y; printf ")"
| Neg x → printf "@,(_-"; eval_parameter' x; printf ")"
| Prod [] → printf "1.0-_%s" !kind
| Prod [x] → eval_parameter' x
| Prod (x :: xs) →
    printf "@,("; eval_parameter' x;
    List.iter (fun x → printf "_*"; eval_parameter' x) xs;
    printf ")"
| Quot (x, y) →
    printf "@,("; eval_parameter' x;
    printf "_/"; eval_parameter' y; printf ")"
| Rec x →
    printf "@,_(1.0-_%s_/_)" !kind; eval_parameter' x; printf ")"
| Pow (x, n) →
    printf "@,("; eval_parameter' x; printf "**%d" n; printf ")"
| Sqrt x → printf "@,sqrt_("; eval_parameter' x; printf ")"
| Sin x → printf "@,sin_("; eval_parameter' x; printf ")"
| Cos x → printf "@,cos_("; eval_parameter' x; printf ")"
| Tan x → printf "@,tan_("; eval_parameter' x; printf ")"
| Cot x → printf "@,cot_("; eval_parameter' x; printf ")"
| Atan2 (y, x) → printf "@,atan2_("; eval_parameter' y;
    printf ",_"; eval_parameter' x; printf ")"
| Conj x → printf "@,conj_("; eval_parameter' x; printf ")"

let strip_single_tag = function
| Real x → x
| Complex x → x

```

```

let strip_array_tag = function
| Real_Array x → x
| Complex_Array x → x

let eval_parameter (lhs, rhs) =
let x = CM.constant_symbol (strip_single_tag lhs) in
printf "%%s=" x; eval_parameter' rhs; nl ()

let eval_para_list n l =
printf "subroutine_setup_parameters%s" (string_of_int n); nl();
List.iter eval_parameter l;
printf "end_subroutine_setup_parameters%s" (string_of_int n); nl()

let eval_parameter_pair (lhs, rhs) =
let x = CM.constant_symbol (strip_array_tag lhs) in
let _ = List.fold_left (fun i rhs' →
printf "%%s(%d)=" x i; eval_parameter' rhs'; nl ();
succ i) 1 rhs in
()

let eval_para_pair_list n l =
printf "subroutine_setup_parameters%s" (string_of_int n); nl();
List.iter eval_parameter_pair l;
printf "end_subroutine_setup_parameters%s" (string_of_int n); nl()

let print_echo fmt p =
let s = CM.constant_symbol p in
printf "%%write(unit=*,fmt=fmt-%s)\\"%s\",%s"
fmt s s; nl ()

let print_echo_array fmt (p, n) =
let s = CM.constant_symbol p in
for i = 1 to n do
printf "%%write(unit=*,fmt=fmt-%s_array)\\"fmt ;
printf "\"%s\",%d,%s(%d)" s i s i; nl ()
done

let parameters_to_fortran oc params =
setup_fortran_formatter !line_length oc;
let declarations = classify_parameters params in
printf "module%s" !parameter_module; nl ();
printf "%%use_kinds"; nl ();
printf "%%use_constants"; nl ();
printf "%%implicit_none"; nl ();
printf "%%private"; nl ();
printf "%%[%2>public::setup_parameters";
if !no_write then begin
printf "!No_print_parameters"; nl();
end else begin
printf "@,print_parameters"; nl ();
end;
declare_default_parameters "real" params.input;
declare_parameters "real" (schisma 69 declarations.real_singles);
List.iter (declare_parameter_array "real") declarations.real_arrays;

```

```

declare_parameters "complex" (schisma 69 declarations.complex_singles);
List.iter (declare_parameter_array "complex") declarations.complex_arrays;
printf "contains"; nl ();
printf "!!!!!derived_parameters:"; nl ();
let shredded = schisma_num 1 120 params.derived in
let shredded_arrays = schisma_num 1 120 params.derived_arrays in
  let num_sub = List.length shredded in
  let num_sub_arrays = List.length shredded_arrays in
printf "!!!!!!length: %s" (string_of_int (List.length params.derived));
  nl();
printf "!!!!!!Num_Sub: %s" (string_of_int num_sub); nl();
List.iter (fun (i, l) → eval_para_list i l) shredded;
List.iter (fun (i, l) → eval_para_pair_list (num_sub + i) l)
  shredded_arrays;
printf "!!subroutine_setup_parameters()"; nl();
let sum_sub = num_sub + num_sub_arrays in
for i = 1 to sum_sub do
  printf "!!!!call_setup_parameters%s" (string_of_int i); nl();
done;
printf "!!end_subroutine_setup_parameters"; nl();
if !no_write then begin
  printf "!No_print_parameters"; nl();
end else begin
  printf "!!subroutine_print_parameters()"; nl();
  printf "!!!!@ [<2>character (len=*) , parameter : ";
  printf "@_fmt_real = \"(A12, 4X, ' = ', E25.18) \", ";
  printf "@_fmt_complex = \"(A12, 4X, ' = ', E25.18, ' + i * ', E25.18) \", ";
  printf "@_fmt_real_array = \"(A12, ' (', I2.2, ') ', ' = ', E25.18) \", ";
  printf "@_fmt_complex_array = ";
  printf "\"(A12, ' (', I2.2, ') ', ' = ', E25.18, ' + i * ', E25.18) \""; nl ();
  printf "!!!!@ [<2>write (unit = *, _fmt = \"(A) \") @, ";
  printf "\"default_values_for_the_input_parameters:\""; nl ();
  List.iter (fun (p, _) → print_echo "real" p) params.input;
  printf "!!!!@ [<2>write (unit = *, _fmt = \"(A) \") @, ";
  printf "\"derived_parameters:\""; nl ();
  List.iter (print_echo "real") declarations.real_singles;
  List.iter (print_echo "complex") declarations.complex_singles;
  List.iter (print_echo_array "real") declarations.real_arrays;
  List.iter (print_echo_array "complex") declarations.complex_arrays;
  printf "!!end_subroutine_print_parameters"; nl();
end;
printf "end_module %s" !parameter_module; nl ();
printf "!0'Mega_revision_control_information:"; nl ();
List.iter (fun s → printf "!!!!%s" s; nl ())
  (ThoList.flatmap RCS.summary (M.rcs :: rcs_list));
printf "!!!program_test_parameters"; nl();
printf "!!!use %s" !parameter_module; nl();
printf "!!!call_setup_parameters()"; nl();
printf "!!!call_print_parameters()"; nl();
printf "!!!end_program_test_parameters"; nl()

```

Run-Time Diagnostics

```

type diagnostic = All | Arguments | Momenta | Gauge
type diagnostic_mode = Off | Warn | Panic

let warn mode =
  match !mode with
  | Off → false
  | Warn → true
  | Panic → true

let panic mode =
  match !mode with
  | Off → false
  | Warn → false
  | Panic → true

let suffix mode =
  if panic mode then
    "panic"
  else
    "warn"

let diagnose_arguments = ref Off
let diagnose_momenta = ref Off
let diagnose_gauge = ref Off

let rec parse_diagnostic = function
| All, panic →
  parse_diagnostic (Arguments, panic);
  parse_diagnostic (Momenta, panic);
  parse_diagnostic (Gauge, panic)
| Arguments, panic →
  diagnose_arguments := if panic then Panic else Warn
| Momenta, panic →
  diagnose_momenta := if panic then Panic else Warn
| Gauge, panic →
  diagnose_gauge := if panic then Panic else Warn

```

If diagnostics are required, we have to switch off Fortran95 features like pure functions.

```

let parse_diagnostics = function
| [] → ()
| diagnostics →
  fortran95 := false;
  List.iter parse_diagnostic diagnostics

```

Amplitude

```

let declare_momenta_chunk = function
| [] → ()
| momenta →
    printf "UUUU@ [<2>type(momentum)_::_";
    print_list (List.map format_momentum momenta); nl ()

let declare_momenta = function
| [] → ()
| momenta →
    List.iter
        declare_momenta_chunk
        (ThoList.chopn declaration_chunk_size momenta)

let declare_wavefunctions multiplicity wfs =
let wfs' = classify_wfs wfs in
declare_list multiplicity ("complex(kind=" ^ !kind ^ ")")
    (wfs'.scalars @ wfs'.brs_scalars);
declare_list multiplicity ("type(" ^ Fermions.psi_type ^ ")")
    (wfs'.spinors @ wfs'.brs_spinors);
declare_list multiplicity ("type(" ^ Fermions.psibar_type ^ ")")
    (wfs'.conjspinors @ wfs'.brs_conjspinors);
declare_list multiplicity ("type(" ^ Fermions.chi_type ^ ")")
    (wfs'.realspinors @ wfs'.brs_realspinors @ wfs'.ghostspinors);
declare_list multiplicity ("type(" ^ Fermions.grav_type ^ ")") wfs'.vectorspinors;
declare_list multiplicity "type(vector)" (wfs'.vectors @ wfs'.massive_vectors @
    wfs'.brs_vectors @ wfs'.brs_massive_vectors @ wfs'.ward_vectors);
declare_list multiplicity "type(tensor2odd)" wfs'.tensors_1;
declare_list multiplicity "type(tensor)" wfs'.tensors_2

let flavors a = F.incoming a @ F.outgoing a

let declare_brackets_chunk = function
| [] → ()
| amplitudes →
    printf "UUUU@ [<2>complex(kind=%s)_::_ !kind;
    print_list (List.map (fun a → flavors_symbol ~ decl :true (flavors a)) amplitudes); nl ()

let declare_brackets = function
| [] → ()
| amplitudes →
    List.iter
        declare_brackets_chunk
        (ThoList.chopn declaration_chunk_size amplitudes)

let print_variable_declarations amplitudes =
let multiplicity = CF.multiplicity amplitudes
and processes = CF.processes amplitudes in
declare_momenta
    (PSet.elements
        (List.fold_left
            (fun set a →

```

```

        PSet.union set (List.fold_right
                        (fun wf → PSet.add (F.momentum_list wf))
                        (F.externals a) PSet.empty))
        PSet.empty processes));
declare_momenta
  (PSet.elements
   (List.fold_left
    (fun set a →
     PSet.union set (List.fold_right
                     (fun wf → PSet.add (F.momentum_list wf))
                     (F.variables a) PSet.empty))
    PSet.empty processes));
if !openmp then begin
  printf "%%type%%s@ [<2>" openmp_tld_type;
  nl ();
end ;
declare_wavefunctions_multiplicity
  (WFSet.elements
   (List.fold_left
    (fun set a →
     WFSet.union set (List.fold_right WFSet.add (F.externals a) WFSet.empty))
    WFSet.empty processes));
declare_wavefunctions_multiplicity
  (WFSet.elements
   (List.fold_left
    (fun set a →
     WFSet.union set (List.fold_right WFSet.add (F.variables a) WFSet.empty))
    WFSet.empty processes));
declare_brackets_processes;
if !openmp then begin
  printf "@]%%end%%type%%s\n" openmp_tld_type;
  printf "%%type%%s) : %%s" openmp_tld_type openmp_tld;
  nl ();
end

```

print_current is the most important function that has to match the functions in *omega95* (see appendix X). It offers plentiful opportunities for making mistakes, in particular those related to signs. We start with a few auxiliary functions:

```

let children2 rhs =
  match F.children rhs with
  | [wf1; wf2] → (wf1, wf2)
  | - → failwith "Targets.children2: can't happen"
let children3 rhs =
  match F.children rhs with
  | [wf1; wf2; wf3] → (wf1, wf2, wf3)
  | - → invalid_arg "Targets.children3: can't happen"

```

Note that it is (marginally) faster to multiply the two scalar products with the coupling constant than the four vector components.



This could be part of *omegalib* as well ...


```

let format_coeff = function
| 1 → ""
| -1 → "-"
| coeff → "(" ^ string_of_int coeff ^ ")*"

let format_coupling coeff c =
match coeff with
| 1 → c
| -1 → "(-" ^ c ^ ")"
| coeff → string_of_int coeff ^ "*" ^ c

```



The following is error prone and should be generated automatically.

```

let print_vector4 c wf1 wf2 wf3 fusion (coeff, contraction) =
match contraction, fusion with
| C_12_34, (F341 | F431 | F342 | F432 | F123 | F213 | F124 | F214)
| C_13_42, (F241 | F421 | F243 | F423 | F132 | F312 | F134 | F314)
| C_14_23, (F231 | F321 | F234 | F324 | F142 | F412 | F143 |
F413) →
printf "((%s%s)*(%s*s))*%s" (format_coeff coeff) c wf1 wf2 wf3
| C_12_34, (F134 | F143 | F234 | F243 | F312 | F321 | F412 | F421)
| C_13_42, (F124 | F142 | F324 | F342 | F213 | F231 | F413 | F431)
| C_14_23, (F123 | F132 | F423 | F432 | F214 | F241 | F314 |
F341) →
printf "((%s%s)*(%s*s))*%s" (format_coeff coeff) c wf2 wf3 wf1
| C_12_34, (F314 | F413 | F324 | F423 | F132 | F231 | F142 | F241)
| C_13_42, (F214 | F412 | F234 | F432 | F123 | F321 | F143 | F341)
| C_14_23, (F213 | F312 | F243 | F342 | F124 | F421 | F134 |
F431) →
printf "((%s%s)*(%s*s))*%s" (format_coeff coeff) c wf1 wf3 wf2

let print_add_vector4 c wf1 wf2 wf3 fusion (coeff, contraction) =
printf "@_+_";
print_vector4 c wf1 wf2 wf3 fusion (coeff, contraction)

let print_vector4_km c pa pb wf1 wf2 wf3 fusion (coeff, contraction) =
match contraction, fusion with
| C_12_34, (F341 | F431 | F342 | F432 | F123 | F213 | F124 | F214)
| C_13_42, (F241 | F421 | F243 | F423 | F132 | F312 | F134 | F314)
| C_14_23, (F231 | F321 | F234 | F324 | F142 | F412 | F143 |
F413) →
printf "((%s%s%s+%s))*(%s*s))*%s"
(format_coeff coeff) c pa pb wf1 wf2 wf3
| C_12_34, (F134 | F143 | F234 | F243 | F312 | F321 | F412 | F421)
| C_13_42, (F124 | F142 | F324 | F342 | F213 | F231 | F413 | F431)
| C_14_23, (F123 | F132 | F423 | F432 | F214 | F241 | F314 |
F341) →
printf "((%s%s%s+%s))*(%s*s))*%s"
(format_coeff coeff) c pa pb wf2 wf3 wf1
| C_12_34, (F314 | F413 | F324 | F423 | F132 | F231 | F142 | F241)

```

```

| C_13_42, (F214 | F412 | F234 | F432 | F123 | F321 | F143 | F341)
| C_14_23, (F213 | F312 | F243 | F342 | F124 | F421 | F134 |
F431) →
    printf "((%s%s%s+%s))*(%s*%s))*%s"
        (format_coeff coeff) c pa pb wf1 wf3 wf2

let print_add_vector4_km c pa pb wf1 wf2 wf3 fusion (coeff, contraction) =
    printf "@_+";
    print_vector4_km c pa pb wf1 wf2 wf3 fusion (coeff, contraction)

let print_dscalar4 c wf1 wf2 wf3 p1 p2 p3 p123
    fusion (coeff, contraction) =
    match contraction, fusion with
    | C_12_34, (F341 | F431 | F342 | F432 | F123 | F213 | F124 | F214)
    | C_13_42, (F241 | F421 | F243 | F423 | F132 | F312 | F134 | F314)
    | C_14_23, (F231 | F321 | F234 | F324 | F142 | F412 | F143 |
F413) →
        printf "((%s%s)*(%s*%s))*(%s*%s))*%s*%s*%s"
            (format_coeff coeff) c p1 p2 p3 p123 wf1 wf2 wf3
        | C_12_34, (F134 | F143 | F234 | F243 | F312 | F321 | F412 | F421)
        | C_13_42, (F124 | F142 | F324 | F342 | F213 | F231 | F413 | F431)
        | C_14_23, (F123 | F132 | F423 | F432 | F214 | F241 | F314 |
F341) →
            printf "((%s%s)*(%s*%s))*(%s*%s))*%s*%s*%s"
                (format_coeff coeff) c p2 p3 p1 p123 wf1 wf2 wf3
            | C_12_34, (F314 | F413 | F324 | F423 | F132 | F231 | F142 | F241)
            | C_13_42, (F214 | F412 | F234 | F432 | F123 | F321 | F143 | F341)
            | C_14_23, (F213 | F312 | F243 | F342 | F124 | F421 | F134 |
F431) →
                printf "((%s%s)*(%s*%s))*(%s*%s))*%s*%s*%s"
                    (format_coeff coeff) c p1 p3 p2 p123 wf1 wf2 wf3

let print_add_dscalar4 c wf1 wf2 wf3 p1 p2 p3 p123
    fusion (coeff, contraction) =
    printf "@_+";
    print_dscalar4 c wf1 wf2 wf3 p1 p2 p3 p123 fusion (coeff, contraction)

let print_dscalar2_vector2 c wf1 wf2 wf3 p1 p2 p3 p123
    fusion (coeff, contraction) =
    failwith "Targets.Fortran.print_dscalar2_vector2: incomplete!";
    match contraction, fusion with
    | C_12_34, (F134 | F143 | F234 | F243) →
        printf "((%s%s)*(%s*%s))*(%s*%s))*%s"
            (format_coeff coeff) c p123 p1 wf2 wf3 wf1
    | C_12_34, (F312 | F321 | F412 | F421) →
        printf "((%s%s)*(%s*%s))*(%s*%s))*%s"
            (format_coeff coeff) c p2 p3 wf2 wf3 wf1
    | C_12_34, (F341 | F431 | F342 | F432 | F123 | F213 | F124 | F214)
    | C_13_42, (F241 | F421 | F243 | F423 | F132 | F312 | F134 | F314)
    | C_14_23, (F231 | F321 | F234 | F324 | F142 | F412 | F143 |
F413) →
        printf "((%s%s)*(%s*%s))*(%s*%s))*%s*%s*%s"

```

```

      (format_coeff coeff) c p1 p2 p3 p123 wf1 wf2 wf3
    | C_13_42, (F124 | F142 | F324 | F342 | F213 | F231 | F413 | F431)
    | C_14_23, (F123 | F132 | F423 | F432 | F214 | F241 | F314 |
F341) →
      printf "(%s%s)*(%s*s)*(%s*s)*%s*s*s)"
      (format_coeff coeff) c p2 p3 p1 p123 wf1 wf2 wf3
    | C_12_34, (F314 | F413 | F324 | F423 | F132 | F231 | F142 | F241)
    | C_13_42, (F214 | F412 | F234 | F432 | F123 | F321 | F143 | F341)
    | C_14_23, (F213 | F312 | F243 | F342 | F124 | F421 | F134 |
F431) →
      printf "(%s%s)*(%s*s)*(%s*s)*%s*s*s)"
      (format_coeff coeff) c p1 p3 p2 p123 wf1 wf2 wf3
let print_add_dscalar2_vector2 c wf1 wf2 wf3 p1 p2 p3 p123
  fusion (coeff, contraction) =
  printf "@_+";
  print_dscalar2_vector2 c wf1 wf2 wf3 p1 p2 p3 p123
  fusion (coeff, contraction)
let print_current_amplitude_dictionary rhs =
  match F.coupling rhs with
  | V3 (vertex, fusion, constant) →
    let ch1, ch2 = children2 rhs in
    let wf1 = multiple_variable_amplitude_dictionary ch1
    and wf2 = multiple_variable_amplitude_dictionary ch2
    and p1 = momentum ch1
    and p2 = momentum ch2
    and m1 = CM.mass_symbol (F.flavor ch1)
    and m2 = CM.mass_symbol (F.flavor ch2) in
    let c = CM.constant_symbol constant in
    printf "@,%s" (if (F.sign rhs) < 0 then "-" else "+");
    begin match vertex with

```

Fermionic currents $\bar{\psi}A\psi$ and $\bar{\psi}\phi\psi$ are handled by the *Fermions* module, since they depend on the choice of Feynman rules: Dirac or Majorana.

```

  | FBF (coeff, fb, b, f) →
    begin match coeff, fb, b, f with
    | -, Psibar, VLRM, Psi | -, Psibar, SPM, Psi
    | -, Psibar, TVA, Psi | -, Psibar, TVAM, Psi
    | -, Psibar, TLR, Psi | -, Psibar, TLRM, Psi
    | -, Psibar, TRL, Psi | -, Psibar, TRLM, Psi →
      let p12 = Printf.sprintf "(-s-%s)" p1 p2 in
      Fermions.print_current_mom (coeff, fb, b, f) c wf1 wf2 p1 p2
      p12 fusion
    | -, -, -, - →
      Fermions.print_current (coeff, fb, b, f) c wf1 wf2 fusion
    end
  | PBP (coeff, f1, b, f2) →
    Fermions.print_current_p (coeff, f1, b, f2) c wf1 wf2 fusion
  | BBB (coeff, fb1, b, fb2) →
    Fermions.print_current_b (coeff, fb1, b, fb2) c wf1 wf2 fusion

```

```
| GBG (coeff, fb, b, f) → let p12 =
  Printf.sprintf "(-%s-%s)" p1 p2 in
  Fermions.print_current_g (coeff, fb, b, f) c wf1 wf2 p1 p2
  p12 fusion
```

Table 9.13 is a bit misleading, since it includes totally antisymmetric structure constants. The space-time part alone is also totally antisymmetric:

```
| Gauge_Gauge_Gauge coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F31 | F12) →
    printf "g_gg(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | (F32 | F13 | F21) →
    printf "g_gg(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end
```

In *Aux_Gauge_Gauge*, we can not rely on antisymmetry alone, because of the different Lorentz representations of the auxiliary and the gauge field. Instead we have to provide the sign in

$$(V_2 \wedge V_3) \cdot T_1 = \begin{cases} V_2 \cdot (T_1 \cdot V_3) = -V_2 \cdot (V_3 \cdot T_1) \\ V_3 \cdot (V_2 \cdot T_1) = -V_3 \cdot (T_1 \cdot V_2) \end{cases} \quad (15.1)$$

ourselves. Alternatively, one could provide *g_xg* mirroring *g_gx*.

```
| Aux_Gauge_Gauge coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "x_gg(%s,%s,%s)" c wf1 wf2
  | F32 → printf "x_gg(%s,%s,%s)" c wf2 wf1
  | F12 → printf "g_gx(%s,%s,%s)" c wf2 wf1
  | F21 → printf "g_gx(%s,%s,%s)" c wf1 wf2
  | F13 → printf "(-1)*g_gx(%s,%s,%s)" c wf2 wf1
  | F31 → printf "(-1)*g_gx(%s,%s,%s)" c wf1 wf2
  end
```

These cases are symmetric and we just have to juxtapose the correct fields and provide parentheses to minimize the number of multiplications.

```
| Scalar_Vector_Vector coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) → printf "%s*(%s*%s)" c wf1 wf2
  | (F12 | F13) → printf "(%s*%s)*%s" c wf1 wf2
  | (F21 | F31) → printf "(%s*%s)*%s" c wf2 wf1
  end

| Aux_Vector_Vector coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) → printf "%s*(%s*%s)" c wf1 wf2
  | (F12 | F13) → printf "(%s*%s)*%s" c wf1 wf2
  | (F21 | F31) → printf "(%s*%s)*%s" c wf2 wf1
```

end

Even simpler:

```
| Scalar_Scalar_Scalar coeff →
  printf "(%s*%s*%s)" (format_coupling coeff c) wf1 wf2

| Aux_Scalar_Scalar coeff →
  printf "(%s*%s*%s)" (format_coupling coeff c) wf1 wf2

| Aux_Scalar_Vector coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F13 | F31) → printf "%s*(%s*%s)" c wf1 wf2
  | (F23 | F21) → printf "(%s*%s)*%s" c wf1 wf2
  | (F32 | F12) → printf "(%s*%s)*%s" c wf2 wf1
  end

| Vector_Scalar_Scalar coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "v_ss(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F32 → printf "v_ss(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | F12 → printf "s_vs(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F21 → printf "s_vs(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | F13 → printf "(-1)*s_vs(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F31 → printf "(-1)*s_vs(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end

| Graviton_Scalar_Scalar coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F12 → printf "s_gravs(%s,%s,-(%s+%s),%s,%s,%s)" c m2 p1 p2 p2 wf1 wf2
  | F21 → printf "s_gravs(%s,%s,-(%s+%s),%s,%s,%s)" c m1 p1 p2 p1 wf2 wf1
  | F13 → printf "s_gravs(%s,%s,%s,-(%s+%s),%s,%s)" c m2 p2 p1 p2 wf1 wf2
  | F31 → printf "s_gravs(%s,%s,%s,-(%s+%s),%s,%s)" c m1 p1 p1 p2 wf2 wf1
  | F23 → printf "grav_ss(%s,%s,%s,%s,%s,%s)" c m1 p1 p2 wf1 wf2
  | F32 → printf "grav_ss(%s,%s,%s,%s,%s,%s)" c m1 p2 p1 wf2 wf1
  end
```

In producing a vector in the fusion we always contract the rightmost index with the vector wavefunction from *rhs*. So the first momentum is always the one of the vector boson produced in the fusion, while the second one is that from the *rhs*. This makes the cases *F12* and *F13* as well as *F21* and *F31* equal. In principle, we could have already done this for the *Graviton_Scalar_Scalar* case.

```
| Graviton_Vector_Vector coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F12 | F13) → printf "v_gravv(%s,%s,-(%s+%s),%s,%s,%s)" c m2 p1 p2 p2 wf1 wf2
  | (F21 | F31) → printf "v_gravv(%s,%s,-(%s+%s),%s,%s,%s)" c m1 p1 p2 p1 wf2 wf1
  | F23 → printf "grav_vv(%s,%s,%s,%s,%s,%s)" c m1 p1 p2 wf1 wf2
  | F32 → printf "grav_vv(%s,%s,%s,%s,%s,%s)" c m1 p2 p1 wf2 wf1
  end
```

```

| Graviton_Spinor_Spinor coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "f_gravf(%s,%s,-(%s+%s),(-%s),%s,%s)" c m2 p1 p2 p2 wf1 wf2
  | F32 → printf "f_gravf(%s,%s,-(%s+%s),(-%s),%s,%s)" c m1 p1 p2 p1 wf2 wf1
  | F12 → printf "f_fgrav(%s,%s,%s,%s+%s,%s,%s)" c m1 p1 p1 p2 wf1 wf2
  | F21 → printf "f_fgrav(%s,%s,%s,%s+%s,%s,%s)" c m2 p2 p1 p2 wf2 wf1
  | F13 → printf "grav_ff(%s,%s,%s,(-%s),%s,%s)" c m1 p1 p2 wf1 wf2
  | F31 → printf "grav_ff(%s,%s,%s,(-%s),%s,%s)" c m1 p2 p1 wf2 wf1
  end

| Dim4_Vector_Vector_Vector_T coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "tkv_vv(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F32 → printf "tkv_vv(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | F12 → printf "tv_kv v(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F21 → printf "tv_kv v(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | F13 → printf "(-1)*tv_kv v(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F31 → printf "(-1)*tv_kv v(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end

| Dim4_Vector_Vector_Vector_L coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "lkv_vv(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F32 → printf "lkv_vv(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | F12 | F13 → printf "lv_kv v(%s,%s,%s,%s,%s)" c wf1 p1 wf2
  | F21 | F31 → printf "lv_kv v(%s,%s,%s,%s,%s)" c wf2 p2 wf1
  end

| Dim6_Gauge_Gauge_Gauge coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 | F31 | F12 →
    printf "kg_kgkg(%s,%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F32 | F13 | F21 →
    printf "kg_kgkg(%s,%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end

| Dim4_Vector_Vector_Vector_T5 coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "t5kv_vv(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F32 → printf "t5kv_vv(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | F12 | F13 → printf "t5v_kv v(%s,%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F21 | F31 → printf "t5v_kv v(%s,%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end

| Dim4_Vector_Vector_Vector_L5 coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "l5kv_vv(%s,%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2

```

```

| F32 → printf "15kv_vv(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
| F12 → printf "15v_kv(%s,%s,%s,%s)" c wf1 p1 wf2
| F21 → printf "15v_kv(%s,%s,%s,%s)" c wf2 p2 wf1
| F13 → printf "(-1)*15v_kv(%s,%s,%s,%s)" c wf1 p1 wf2
| F31 → printf "(-1)*15v_kv(%s,%s,%s,%s)" c wf2 p2 wf1
end

| Dim6_Gauge_Gauge_Gauge_5 coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "kg5_kgkg(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F32 → printf "kg5_kgkg(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | F12 → printf "kg_kg5kg(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F21 → printf "kg_kg5kg(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | F13 → printf "(-1)*kg_kg5kg(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F31 → printf "(-1)*kg_kg5kg(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end

| Aux_DScalar_DScalar coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) →
    printf "%s*(%s*%s)*(%s*%s)" c p1 p2 wf1 wf2
  | (F12 | F13) →
    printf "%s*(-((%s+%s)*%s))*(%s*%s)" c p1 p2 p2 wf1 wf2
  | (F21 | F31) →
    printf "%s*(-((%s+%s)*%s))*(%s*%s)" c p1 p2 p1 wf1 wf2
  end

| Aux_Vector_DScalar coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "%s*(%s*%s)*%s" c wf1 p2 wf2
  | F32 → printf "%s*(%s*%s)*%s" c wf2 p1 wf1
  | F12 → printf "%s*(-((%s+%s)*%s))*%s" c p1 p2 wf2 wf1
  | F21 → printf "%s*(-((%s+%s)*%s))*%s" c p1 p2 wf1 wf2
  | (F13 | F31) → printf "(-(%s+%s))*(%s*%s*%s)" p1 p2 c wf1 wf2
  end

| Dim5_Scalar_Gauge2 coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) → printf "(%s)*((%s*%s)*(%s*%s))_-(%s*%s)*(%s*%s)"
    c p1 wf2 p2 wf1 p1 p2 wf2 wf1
  | (F12 | F13) → printf "(%s)*%s*(-((%s+%s)*%s))*%s_-(%s*%s)*%s"
    c wf1 p1 p2 wf2 p2 p1 p2 p2 wf2
  | (F21 | F31) → printf "(%s)*%s*(-((%s+%s)*%s))*%s_-(%s*%s)*%s"
    c wf2 p2 p1 wf1 p1 p1 p2 p1 wf1
  end

| Dim5_Scalar_Gauge2_Skew coeff →
  let c = format_coupling coeff c in
  begin match fusion with

```

```

| (F23 | F32) → printf "(-_phi_vv_(%s,%s,%s,%s,%s))" c p1 p2 wf1 wf2
| (F12 | F13) → printf "(-_v_phiv_(%s,%s,%s,%s,%s))" c wf1 p1 p2 wf2
| (F21 | F31) → printf "v_phiv_(%s,%s,%s,%s,%s)" c wf2 p1 p2 wf1
end

| Dim5_Scalar_Vector_Vector_T coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) → printf "(%s)*(%s*%s)*(%s*%s)" c p1 wf2 p2 wf1
  | (F12 | F13) → printf "(%s)*%s*(-((%s+%s)*%s))*%s" c wf1 p1 p2 wf2 p2
  | (F21 | F31) → printf "(%s)*%s*(-((%s+%s)*%s))*%s" c wf2 p2 p1 wf1 p1
  end

| Dim5_Scalar_Vector_Vector_U coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) → printf "phi_u_vv_(%s,%s,%s,%s,%s)" c p1 p2 wf1 wf2
  | (F12 | F13) → printf "v_u_phiv_(%s,%s,%s,%s,%s)" c wf1 p1 p2 wf2
  | (F21 | F31) → printf "v_u_phiv_(%s,%s,%s,%s,%s)" c wf2 p2 p1 wf1
  end

| Dim5_Scalar_Vector_Vector_TU coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "(%s)*((%s*%s)*(-( %s+%s)*%s))_(_(-( %s+%s)*%s)*(%s*%s))"
    c p1 wf2 p1 p2 wf1 p1 p2 p1 wf1 wf2
  | F32 → printf "(%s)*((%s*%s)*(-( %s+%s)*%s))_(_(-( %s+%s)*%s)*(%s*%s))"
    c p2 wf1 p1 p2 wf2 p1 p2 p2 wf1 wf2
  | F12 → printf "(%s)*%s*((%s*%s)*%s_(_(%s*%s)*%s))"
    c wf1 p1 wf2 p2 p1 p2 wf2
  | F21 → printf "(%s)*%s*((%s*%s)*%s_(_(%s*%s)*%s))"
    c wf2 p2 wf1 p1 p1 p2 wf1
  | F13 → printf "(%s)*%s*((-( %s+%s)*%s)*%s_(_(-( %s+%s)*%s)*%s)"
    c wf1 p1 p2 wf2 p1 p1 p2 p1 wf2
  | F31 → printf "(%s)*%s*((-( %s+%s)*%s)*%s_(_(-( %s+%s)*%s)*%s)"
    c wf2 p1 p2 wf1 p2 p1 p2 p2 wf1
  end

| Dim6_Vector_Vector_Vector_T coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "(%s)*(%s*%s)*(%s*%s)*(%s-%s)" c p2 wf1 p1 wf2 p1 p2
  | F32 → printf "(%s)*(%s*%s)*(%s*%s)*(%s-%s)" c p1 wf2 p2 wf1 p2 p1
  | (F12 | F13) → printf "(%s)*((%s+2*%s)*%s)*(-( (%s+%s)*%s))*%s"
    c p1 p2 wf1 p1 p2 wf2 p2
  | (F21 | F31) → printf "(%s)*((-( (%s+%s)*%s))*(%s+2*%s)*%s)*%s"
    c p2 p1 wf1 p2 p1 wf2 p1
  end

| Tensor_2_Vector_Vector coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) → printf "t2_vv(%s,%s,%s)" c wf1 wf2

```



```

| (F12 | F13) → printf "v_t2v(%s,%s,%s)" c wf1 wf2
| (F21 | F31) → printf "v_t2v(%s,%s,%s)" c wf2 wf1
end

| Tensor_2_Vector_Vector_1 coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) → printf "t2_vv_1(%s,%s,%s)" c wf1 wf2
  | (F12 | F13) → printf "v_t2v_1(%s,%s,%s)" c wf1 wf2
  | (F21 | F31) → printf "v_t2v_1(%s,%s,%s)" c wf2 wf1
  end

| Dim5_Tensor_2_Vector_Vector_1 coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | (F23 | F32) → printf "t2_vv_d5_1(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | (F12 | F13) → printf "v_t2v_d5_1(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | (F21 | F31) → printf "v_t2v_d5_1(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end

| Dim5_Tensor_2_Vector_Vector_2 coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "t2_vv_d5_2(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F32 → printf "t2_vv_d5_2(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | (F12 | F13) → printf "v_t2v_d5_2(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | (F21 | F31) → printf "v_t2v_d5_2(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end

| Dim7_Tensor_2_Vector_Vector_T coeff →
  let c = format_coupling coeff c in
  begin match fusion with
  | F23 → printf "t2_vv_d7(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | F32 → printf "t2_vv_d7(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  | (F12 | F13) → printf "v_t2v_d7(%s,%s,%s,%s,%s)" c wf1 p1 wf2 p2
  | (F21 | F31) → printf "v_t2v_d7(%s,%s,%s,%s,%s)" c wf2 p2 wf1 p1
  end

end

```

Flip the sign to account for the i^2 relative to diagrams with only cubic couplings.

```

| V4 (vertex, fusion, constant) →
  let c = CM.constant_symbol constant
  and ch1, ch2, ch3 = children3 rhs in
  let wf1 = multiple_variable_amplitude_dictionary ch1
  and wf2 = multiple_variable_amplitude_dictionary ch2
  and wf3 = multiple_variable_amplitude_dictionary ch3
  and p1 = momentum ch1
  and p2 = momentum ch2
  and p3 = momentum ch3 in
  printf "@,%s" (if (F.sign rhs) < 0 then "+" else "-");
  begin match vertex with
  | Scalar4 coeff →

```

```

    printf "(%s*%s*%s*%s)" (format_coupling coeff c) wf1 wf2 wf3
| Scalar2_Vector2 coeff →
  let c = format_coupling coeff c in
  begin match fusion with
    | F134 | F143 | F234 | F243 →
      printf "%s*%s*%s*%s" c wf1 wf2 wf3
    | F314 | F413 | F324 | F423 →
      printf "%s*%s*%s*%s" c wf2 wf1 wf3
    | F341 | F431 | F342 | F432 →
      printf "%s*%s*%s*%s" c wf3 wf1 wf2
    | F312 | F321 | F412 | F421 →
      printf "(%s*%s*%s)*%s" c wf2 wf3 wf1
    | F231 | F132 | F241 | F142 →
      printf "(%s*%s*%s)*%s" c wf1 wf3 wf2
    | F123 | F213 | F124 | F214 →
      printf "(%s*%s*%s)*%s" c wf1 wf2 wf3
  end
| Vector4_contractions →
  begin match contractions with
    | [] → invalid_arg "Targets.print_current:␣Vector4␣[]"
    | head :: tail →
      printf "(";
      print_vector4 c wf1 wf2 wf3 fusion head;
      List.iter (print_add_vector4 c wf1 wf2 wf3 fusion) tail;
      printf ")"
  end
| Vector4_K_Matrix_tho (disc, poles) →
  let pa, pb =
    begin match fusion with
      | (F341 | F431 | F342 | F432 | F123 | F213 | F124 |
F214) → (p1, p2)
      | (F134 | F143 | F234 | F243 | F312 | F321 | F412 |
F421) → (p2, p3)
      | (F314 | F413 | F324 | F423 | F132 | F231 | F142 |
F241) → (p1, p3)
    end in
    printf "(%s*(%s*%s)*(%s*%s)*(%s*%s)@,%*("
      c p1 wf1 p2 wf2 p3 wf3;
    List.iter (fun (coeff, pole) →
      printf "+%s/((%s+%s)*(%s+%s)-%s)"
        (CM.constant_symbol coeff) pa pb pa pb
        (CM.constant_symbol pole))
      poles;
    printf ")*(-%s-%s-%s))" p1 p2 p3
| Vector4_K_Matrix_jr (disc, contractions) →
  let pa, pb =
    begin match disc, fusion with
      | 3, (F143 | F413 | F142 | F412 | F321 | F231 | F324 |
F234) → (p1, p2)
      | 3, (F314 | F341 | F214 | F241 | F132 | F123 | F432 |

```

```

F423) → (p2, p3)
      | 3, (F134 | F431 | F124 | F421 | F312 | F213 | F342 |
F243) → (p1, p3)
      | -, (F341 | F431 | F342 | F432 | F123 | F213 | F124 |
F214) → (p1, p2)
      | -, (F134 | F143 | F234 | F243 | F312 | F321 | F412 |
F421) → (p2, p3)
      | -, (F314 | F413 | F324 | F423 | F132 | F231 | F142 |
F241) → (p1, p3)
      end in
      begin match contractions with
      | [] → invalid_arg "Targets.print_current:␣Vector4_K_Matrix_jr␣"
      | head :: tail →
          printf "(";
          print_vector4_km c pa pb wf1 wf2 wf3 fusion head;
          List.iter (print_add_vector4_km c pa pb wf1 wf2 wf3 fusion)
            tail;
          printf ")"
      end
      | GBBG (coeff, fb, b, f) →
          Fermions.print_current_g4 (coeff, fb, b, f) c wf1 wf2 wf3
            fusion

```



In principle, p_4 could be obtained from the left hand side ...

```

| DScalar4 contractions →
  let p123 = Printf.sprintf "(-%s-%s-%s)" p1 p2 p3 in
  begin match contractions with
  | [] → invalid_arg "Targets.print_current:␣DScalar4␣"
  | head :: tail →
      printf "(";
      print_dscalar4 c wf1 wf2 wf3 p1 p2 p3 p123 fusion head;
      List.iter (print_add_dscalar4
                  c wf1 wf2 wf3 p1 p2 p3 p123 fusion) tail;
      printf ")"
  end
| DScalar2_Vector2 contractions →
  let p123 = Printf.sprintf "(-%s-%s-%s)" p1 p2 p3 in
  begin match contractions with
  | [] → invalid_arg "Targets.print_current:␣DScalar4␣"
  | head :: tail →
      printf "(";
      print_dscalar2_vector2
        c wf1 wf2 wf3 p1 p2 p3 p123 fusion head;
      List.iter (print_add_dscalar2_vector2
                  c wf1 wf2 wf3 p1 p2 p3 p123 fusion) tail;
      printf ")"
  end
end

```

```

end
| Vn (_, -, -) →
  invalid_arg "Targets.print_current: n-ary fusion"
let print_propagator f p m gamma =
  let minus_third = "(-1.0_" ^ !kind ^ "/3.0_" ^ !kind ^ ")" in
  let w =
    begin match CM.width f with
    | Vanishing | Fudged → "0.0_" ^ !kind
    | Constant → gamma
    | Timelike → "wd_tl(" ^ p ^ ", " ^ gamma ^ ")"
    | Running →
      failwith "Targets.Fortran: running width not yet available"
    | Custom f → f ^ "(" ^ p ^ ", " ^ gamma ^ ")"
    end in
  match CM.propagator f with
  | Prop_Scalar →
    printf "pr_phi(%s,%s,%s," p m w
  | Prop_Col_Scalar →
    printf "%s*_pr_phi(%s,%s,%s," minus_third p m w
  | Prop_Ghost → printf "(0,1)*_pr_phi(%s,%s,%s," p m w
  | Prop_Spinor →
    printf "%s(%s,%s,%s," Fermions.psi_propagator p m w
  | Prop_ConjSpinor →
    printf "%s(%s,%s,%s," Fermions.psibar_propagator p m w
  | Prop_Majorana →
    printf "%s(%s,%s,%s," Fermions.chi_propagator p m w
  | Prop_Col_Majorana →
    printf "%s*_s(%s,%s,%s," minus_third Fermions.chi_propagator p m w
  | Prop_Unitarity →
    printf "pr_unitarity(%s,%s,%s," p m w
  | Prop_Col_Unitarity →
    printf "%s*_pr_unitarity(%s,%s,%s," minus_third p m w
  | Prop_Feynman →
    printf "pr_feynman(%s," p
  | Prop_Col_Feynman →
    printf "%s*_pr_feynman(%s," minus_third p
  | Prop_Gauge xi →
    printf "pr_gauge(%s,%s," p (CM.gauge_symbol xi)
  | Prop_Rxi xi →
    printf "pr_rxi(%s,%s,%s,%s," p m w (CM.gauge_symbol xi)
  | Prop_Tensor_2 →
    printf "pr_tensor(%s,%s,%s," p m w
  | Prop_Vectorspinor →
    printf "pr_grav(%s,%s,%s," p m w
  | Aux_Scalar | Aux_Spinor | Aux_ConjSpinor | Aux_Majorana
  | Aux_Vector | Aux_Tensor_1 → printf "("
  | Aux_Col_Scalar | Aux_Col_Vector | Aux_Col_Tensor_1 →
    printf "%s*_(" minus_third
  | Only_Insertion → printf "("

```

```

let print_projector f p m gamma =
  let minus_third = "(-1.0_" ^ !kind ^ "/3.0_" ^ !kind ^ ")" in
  match CM.propagator f with
  | Prop_Scalar →
    printf "pj-phi(%s,%s," m gamma
  | Prop_Col_Scalar →
    printf "%s*␣pj-phi(%s,%s," minus_third m gamma
  | Prop_Ghost →
    printf "(0,1)␣*␣pj-phi(%s,%s," m gamma
  | Prop_Spinor →
    printf "%s(%s,%s,%s," Fermions.psi_projector p m gamma
  | Prop_ConjSpinor →
    printf "%s(%s,%s,%s," Fermions.psibar_projector p m gamma
  | Prop_Majorana →
    printf "%s(%s,%s,%s," Fermions.chi_projector p m gamma
  | Prop_Col_Majorana →
    printf "%s*␣%s(%s,%s,%s," minus_third Fermions.chi_projector p m gamma
  | Prop_Unitarity →
    printf "pj-unitarity(%s,%s,%s," p m gamma
  | Prop_Col_Unitarity →
    printf "%s*␣pj-unitarity(%s,%s,%s," minus_third p m gamma
  | Prop_Feynman | Prop_Col_Feynman →
    invalid_arg "no␣on-shell␣Feynman␣propagator!"
  | Prop_Gauge xi →
    invalid_arg "no␣on-shell␣massless␣gauge␣propagator!"
  | Prop_Rxi xi →
    invalid_arg "no␣on-shell␣Rxi␣propagator!"
  | Prop_Vectorspinor →
    printf "pj-grav(%s,%s,%s," p m gamma
  | Prop_Tensor_2 →
    printf "pj-tensor(%s,%s,%s," p m gamma
  | Aux_Scalar | Aux_Spinor | Aux_ConjSpinor | Aux_Majorana
  | Aux_Vector | Aux_Tensor_1 → printf "("
  | Aux_Col_Scalar | Aux_Col_Vector | Aux_Col_Tensor_1 →
printf "%s*␣(" minus_third
  | Only_Insertion → printf "("

let print_gauss f p m gamma =
  let minus_third = "(-1.0_" ^ !kind ^ "/3.0_" ^ !kind ^ ")" in
  match CM.propagator f with
  | Prop_Scalar →
    printf "pg-phi(%s,%s,%s," p m gamma
  | Prop_Ghost →
    printf "(0,1)␣*␣pg-phi(%s,%s,%s," p m gamma
  | Prop_Spinor →
    printf "%s(%s,%s,%s," Fermions.psi_projector p m gamma
  | Prop_ConjSpinor →
    printf "%s(%s,%s,%s," Fermions.psibar_projector p m gamma
  | Prop_Majorana →
    printf "%s(%s,%s,%s," Fermions.chi_projector p m gamma

```

```

| Prop_Col_Majorana →
  printf "%s*%s(%s,%s,%s," minus_third Fermions.chi_projector p m gamma
| Prop_Unitarity →
  printf "pg_unitarity(%s,%s,%s," p m gamma
| Prop_Feynman | Prop_Col_Feynman →
  invalid_arg "no_on-shell_Feynman_propagator!"
| Prop_Gauge xi →
  invalid_arg "no_on-shell_massless_gauge_propagator!"
| Prop_Rxi xi →
  invalid_arg "no_on-shell_Rxi_propagator!"
| Prop_Tensor_2 →
  printf "pg_tensor(%s,%s,%s," p m gamma
| Aux_Scalar | Aux_Spinor | Aux_ConjSpinor | Aux_Majorana
| Aux_Vector | Aux_Tensor_1 → printf "("
| Only_Insertion → printf "("
| - → invalid_arg "targets:print_gauss:_not_available"

let print_fusion_diagnostics amplitude dictionary fusion =
  if warn_diagnose_gauge then begin
    let lhs = F.lhs fusion in
    let f = F.flavor lhs
    and v = variable lhs
    and p = momentum lhs in
    let mass = CM.mass_symbol f in
    match CM.propagator f with
    | Prop_Gauge _ | Prop_Feynman
    | Prop_Rxi _ | Prop_Unitarity →
      printf "%%[<2>%s=" v;
      List.iter (print_current amplitude dictionary) (F.rhs fusion); nl();
      begin match CM.goldstone f with
      | None →
        printf "%%call_omega_ward_%s(\"%s\",%s,%s,%s)"
          (suffix_diagnose_gauge) v mass p v; nl ()
      | Some (g, phase) →
        let gv = add_tag lhs (CM.flavor_symbol g ^ "-" ^ format_p lhs) in
        printf "%%call_omega_slavnov_%s"
          (suffix_diagnose_gauge);
        printf "(@(\"%s\",%s,%s,%s,@,%s*%s)"
          v mass p v (format_constant phase) gv; nl ()
      end
    | - → ()
  end

let print_fusion amplitude dictionary fusion =
  let lhs = F.lhs fusion in
  let f = F.flavor lhs in
  printf "%%[<2>%s=@,_" (multiple_variable amplitude dictionary lhs);
  if F.on_shell amplitude lhs then
    print_projector f (momentum lhs)
    (CM.mass_symbol f) (CM.width_symbol f)
  else

```

```

    if F.is_gauss amplitude lhs then
      print_gauss f (momentum lhs)
      (CM.mass_symbol f) (CM.width_symbol f)
    else
      print_propagator f (momentum lhs)
      (CM.mass_symbol f) (CM.width_symbol f);
    List.iter (print_current amplitude dictionary) (F.rhs fusion);
    printf " "; nl ()

let print_momenta seen_momenta amplitude =
  List.fold_left (fun seen f →
    let wf = F.lhs f in
    let p = F.momentum_list wf in
    if ¬ (PSet.mem p seen) then begin
      let rhs1 = List.hd (F.rhs f) in
      printf "%%s=%%s" (momentum wf)
      (String.concat "++"
        (List.map momentum (F.children rhs1))); nl ()
    end;
    PSet.add p seen)
  seen_momenta (F.fusions amplitude)

let print_fusions dictionary fusions =
  List.iter
    (fun (f, amplitude) →
      print_fusion_diagnostics amplitude dictionary f;
      print_fusion amplitude dictionary f)
  fusions

let print_braket amplitude dictionary name braket =
  let bra = F.bra braket
  and ket = F.ket braket in
  printf "%%s@[%s=%%s@,++" name name;
  begin match Fermions.reverse_braket (CM.lorentz (F.flavor bra)) with
  | false →
    printf "%s*(@," (multiple_variable amplitude dictionary bra);
    List.iter (print_current amplitude dictionary) ket;
    printf ")"
  | true →
    printf "(@,";
    List.iter (print_current amplitude dictionary) ket;
    printf ")*%s" (multiple_variable amplitude dictionary bra)
  end; nl ()

```

$$iT = i^{\# \text{vertices}} i^{\# \text{propagators}} \dots = i^{n-2} i^{n-3} \dots = -i(-1)^n \dots \quad (15.2)$$



tho : we write some brackets twice using different names. Is it useful to cache them?

```

let print_brackets dictionary amplitude =

```

```

let name = flavors_symbol (flavors amplitude) in
printf "%%%%%s=0" name; nl ();
List.iter (print_braket amplitude dictionary name) (F.brackets amplitude);
let n = List.length (F.externals amplitude) in
if n mod 2 = 0 then begin
  printf "%%%%@ [<2>%s=@,%s!%d_vertices,%d_propagators"
    name name (n - 2) (n - 3); nl ()
end else begin
  printf "%%%%!%s=%s!%d_vertices,%d_propagators"
    name name (n - 2) (n - 3); nl ()
end;
let s = F.symmetry amplitude in
if s > 1 then
  printf "%%%%@ [<2>%s=@,%s@,%sqrt(%d.0-%s)!symmetry_factor" name name s !kind
else
  printf "%%%%!unit_symmetry_factor";
nl ()

let print_incoming wf =
  let p = momentum wf
  and s = spin wf
  and f = F.flavor wf in
  let m = CM.mass_symbol f in
  match CM.lorentz f with
  | Scalar → printf "1"
  | BRS_Scalar → printf "(0,-1)%s*%s-%s**2" p p m
  | Spinor →
    printf "%s(%s,%s,%s)" Fermions.psi_incoming m p s
  | BRS_Spinor →
    printf "%s(%s,%s,%s)" Fermions.brs_psi_incoming m p s
  | ConjSpinor →
    printf "%s(%s,%s,%s)" Fermions.psibar_incoming m p s
  | BRS_ConjSpinor →
    printf "%s(%s,%s,%s)" Fermions.brs_psibar_incoming m p s
  | Majorana →
    printf "%s(%s,%s,%s)" Fermions.chi_incoming m p s
  | Maj_Ghost → printf "ghost(%s,%s,%s)" m p s
  | BRS_Majorana →
    printf "%s(%s,%s,%s)" Fermions.brs_chi_incoming m p s
  | Vector | Massive_Vector →
    printf "eps(%s,%s,%s)" m p s
  | BRS_Vector | BRS_Massive_Vector → printf
    "(0,1)%s*%s-%s**2)%s*eps(%s,%s,%s)" p p m p s
  | Vectorspinor | BRS_Vectorspinor →
    printf "%s(%s,%s,%s)" Fermions.grav_incoming m p s
  | Tensor_1 → invalid_arg "Tensor_1_only_internal"
  | Tensor_2 → printf "eps2(%s,%s,%s)" m p s
  | _ → invalid_arg "no_such_BRST_transformations"

let print_outgoing wf =
  let p = momentum wf

```



```

and s = spin wf
and f = F.flavor wf in
let m = CM.mass_symbol f in
match CM.lorentz f with
| Scalar → printf "1"
| BRS Scalar → printf "(0,-1)␣*␣(%s␣*␣%s␣␣%s**2)" p p m
| Spinor →
  printf "%s␣(%s,␣%s,␣%s)" Fermions.psi_outgoing m p s
| BRS Spinor →
  printf "%s␣(%s,␣%s,␣%s)" Fermions.brs_psi_outgoing m p s
| ConjSpinor →
  printf "%s␣(%s,␣%s,␣%s)" Fermions.psibar_outgoing m p s
| BRS ConjSpinor →
  printf "%s␣(%s,␣%s,␣%s)" Fermions.brs_psibar_outgoing m p s
| Majorana →
  printf "%s␣(%s,␣%s,␣%s)" Fermions.chi_outgoing m p s
| BRS Majorana →
  printf "%s␣(%s,␣%s,␣%s)" Fermions.brs_chi_outgoing m p s
| Maj_Ghost → printf "ghost␣(%s,␣%s,␣%s)" m p s
| Vector | Massive_Vector →
  printf "conj␣(eps␣(%s,␣%s,␣%s))" m p s
| BRS Vector | BRS Massive_Vector → printf
  "(0,1)␣*␣(%s*%s-%s**2)␣*␣(conj␣(eps␣(%s,␣%s,␣%s)))" p p m m p s
| Vectorspinor | BRS Vectorspinor →
  printf "%s␣(%s,␣%s,␣%s)" Fermions.grav_incoming m p s
| Tensor_1 → invalid_arg "Tensor_1␣only␣internal"
| Tensor_2 → printf "conj␣(eps2␣(%s,␣%s,␣%s))" m p s
| BRS _ → invalid_arg "no␣such␣BRST␣transformations"

let twice_spin wf =
  match CM.lorentz (F.flavor wf) with
  | Scalar | BRS Scalar → "0"
  | Spinor | ConjSpinor | Majorana | Maj_Ghost | Vectorspinor
  | BRS Spinor | BRS ConjSpinor | BRS Majorana | BRS Vectorspinor →
    "1"
  | Vector | BRS Vector | Massive_Vector | BRS Massive_Vector →
    "2"
  | Tensor_1 → "2"
  | Tensor_2 → "4"
  | BRS _ → invalid_arg "Targets.twice_spin:␣no␣such␣BRST␣transformation"

let print_argument_diagnostics amplitude =
  let externals = (F.externals amplitude) in
  let n = List.length externals
  and masses = List.map (fun wf → CM.mass_symbol (F.flavor wf)) externals in
  if warn_diagnose_arguments then begin
    printf "␣␣␣␣call␣omega_check_arguments_%s␣(%d,␣k)"
      (suffix_diagnose_arguments) n; nl ()
  end;
  if warn_diagnose_momenta then begin
    printf "␣␣␣␣@[<2>call␣omega_check_momenta_%s␣((/␣"

```

```

        (suffix diagnose_momenta);
    print_list masses;
    printf "%d/%d", k; nl ()
end

let print_external_momenta amplitude =
    let externals =
        List.combine
            (F.externals amplitude)
            (List.map (fun _ → true) (F.incoming amplitude) @
                List.map (fun _ → false) (F.outgoing amplitude)) in
    List.iter (fun (wf, incoming) →
        if incoming then
            printf "%d=%d-%d", k, momentum wf, ext_momentum wf
        else
            printf "%d=%d", k, momentum wf; nl () externals
    ) externals

let print_externals_seen_wfs amplitude =
    let externals =
        List.combine
            (F.externals amplitude)
            (List.map (fun _ → true) (F.incoming amplitude) @
                List.map (fun _ → false) (F.outgoing amplitude)) in
    List.fold_left (fun seen (wf, incoming) →
        if ¬ (WFSets.mem wf seen) then begin
            printf "%d@<2>%d=%d", k, momentum wf;
            (if incoming then print_incoming else print_outgoing) wf; nl ()
        end;
        WFSets.add wf seen) seen_wfs externals

let flavors_to_string flavors =
    String.concat " " (List.map CM.flavor_to_string flavors)

let process_to_string amplitude =
    flavors_to_string (F.incoming amplitude) ^ "→" ^
    flavors_to_string (F.outgoing amplitude)

let flavors_sans_color_to_string flavors =
    String.concat " " (List.map M.flavor_to_string flavors)

let process_sans_color_to_string (fin, fout) =
    flavors_sans_color_to_string fin ^ "→" ^
    flavors_sans_color_to_string fout

let print_fudge_factor amplitude =
    let name = flavors_symbol (flavors amplitude) in
    List.iter (fun wf →
        let p = momentum wf
        and f = F.flavor wf in
        match CM.width f with
        | Fudged →
            let m = CM.mass_symbol f

```

```

and w = CM.width_symbol f in
printf "UUUUUUif_ (%s>0.0_%s)_then" w !kind; nl ();
printf "UUUUUUU@ [<2>%s=_%s@_*_ (%s*%s-_%s**2)"
      name name p p m;
printf "@_/_cplx_ (%s*%s-_%s**2,_%s*%s,_kind=%s)"
      p p m m w !kind; nl();
printf "UUUUUUend_if"; nl ()
| _ → () (F.s_channel amplitude)

let num_helicities amplitudes =
  List.length (CF.helicities amplitudes)

```

Spin, Flavor & Color Tables

The following abomination is required to keep the number of continuation lines as low as possible. FORTRAN77-style **DATA** statements are actually a bit nicer here, but they are not available for *constant* arrays.



We used to have a more elegant design with a sentinel 0 added to each initializer, but some revisions of the Compaq/Digital Compiler have a bug that causes it to reject this variant.



The actual table writing code using **reshape** should be factored, since it's the same algorithm every time.

```

let print_integer_parameter name value =
  printf "UU@ [<2>integer,_parameter_:_%s=_%d" name value; nl ()

let print_real_parameter name value =
  printf "UU@ [<2>real(kind=%s),_parameter_:_%s=_%d"
    !kind name value; nl ()

let print_logical_parameter name value =
  printf "UU@ [<2>logical,_parameter_:_%s=_%s."
    name (if value then "true" else "false"); nl ()

let num_particles_in amplitudes =
  match CF.flavors amplitudes with
  | [] → 0
  | (fin, _) :: _ → List.length fin

let num_particles_out amplitudes =
  match CF.flavors amplitudes with
  | [] → 0
  | (_, fout) :: _ → List.length fout

let num_particles amplitudes =
  match CF.flavors amplitudes with
  | [] → 0
  | (fin, fout) :: _ → List.length fin + List.length fout

```

```

module CFlow = Color.Flow

let num_color_flows amplitudes =
  List.length (CF.color_flows amplitudes)

let num_color_indices_default = 2 (* Standard model *)

let num_color_indices amplitudes =
  try CFlow.rank (List.hd (CF.color_flows amplitudes)) with _ → num_color_indices_default

let color_to_string c =
  "(" ^ (String.concat "," (List.map (Printf.sprintf "%3d") c)) ^ ")"

let cflow_to_string cflow =
  String.concat "_" (List.map color_to_string (CFlow.in_to_lists cflow)) ^ "_->" ^
  String.concat "_" (List.map color_to_string (CFlow.out_to_lists cflow))

let protected = ""
let protected = ",_protected" (* Fortran 2003! *)

let print_spin_table_old abbrev name = function
| [] →
  printf "%d@(<2>integer,_dimension(n_prt,0))_::";
  printf "@_table_spin_%s" name; nl ()
| _ :: tuples' as tuples →
  ignore (List.fold_left (fun i (tuple1, tuple2) →
    printf "%d@(<2>integer,_dimension(n_prt),_parameter,_private)_::";
    printf "@_%s%04d_=(/_%s_/" abbrev i
      (String.concat "," (List.map (Printf.sprintf "%2d") (tuple1 @ tuple2)));
    nl (); succ i) 1 tuples);
  printf
    "%d@(<2>integer,_dimension(n_prt,n_hel),_parameter)_::";
  printf "@_table_spin_%s=@_reshape_(_(_/" name;
  printf "@_%s%04d" abbrev 1;
  ignore (List.fold_left (fun i tuple →
    printf ",@_%s%04d" abbrev i; succ i) 2 tuples');
  printf "@_/_(_/_n_prt,_n_hel_/_)_"; nl ()

let print_spin_table name tuples =
  printf "%d@(<2>integer,_dimension(n_prt,n_hel),_save%s_::_table_spin_%s"
    protected name; nl();
  match tuples with
  | [] → ()
  | _ →
    ignore (List.fold_left (fun i (tuple1, tuple2) →
      printf "%d@(<2>data_table_spin-%s(:,%4d)_/_%s_/" name i
        (String.concat "," (List.map (Printf.sprintf "%2d") (tuple1 @ tuple2)));
      nl (); succ i) 1 tuples)

let print_spin_tables amplitudes =
  (* print_spin_table_old "s" "states_old" (CF.helicities amplitudes);

*)
  print_spin_table "states" (CF.helicities amplitudes);
  nl ()

```

```

let print_flavor_table_old n abbrev name = function
| [] →
  printf "%d@[%d>integer,%dimension(n_prt,0)]:";
  printf "@table_flavor-%s" name; nl ()
| - :: tuples' as tuples →
  ignore (List.fold_left (fun i tuple →
    printf
      "%d@[%d>integer,%dimension(n_prt),%parameter,%private]:";
      printf "@%s%04d=%(/%s/)!%s" abbrev i
        (String.concat ", "
          (List.map (fun f → Printf.sprintf "%3d" (M.pdg f)) tuple))
          (String.concat " " (List.map M.flavor_to_string tuple));
        nl (); succ i) 1 tuples);
  printf
    "%d@[%d>integer,%dimension(n_prt,n_flg),%parameter]:";
    printf "@table_flavor-%s=@%reshape(/" name;
    printf "@%s%04d" abbrev 1;
    ignore (List.fold_left (fun i tuple →
      printf ",@%s%04d" abbrev i; succ i) 2 tuples');
    printf "@(/,%n_flg)/)"; nl ()

let print_flavor_table n name tuples =
  printf "%d@[%d>integer,%dimension(n_prt,n_flg),%save%=:table_flavor-%s"
    protected name; nl();
  match tuples with
  | [] → ()
  | - →
    ignore (List.fold_left (fun i tuple →
      printf "%d@[%d>data_table_flavor-%s(,%4d)/%s/!%s" name i
        (String.concat ", "
          (List.map (fun f → Printf.sprintf "%3d" (M.pdg f)) tuple))
          (String.concat " " (List.map M.flavor_to_string tuple));
        nl (); succ i) 1 tuples)

let print_flavor_tables amplitudes =
  let n = num_particles amplitudes in
  (* print_flavor_table_old n "f" "states_old" (List.map (fun (fin, fout) →
    fin @ fout) (CF.flavors amplitudes)); *)
  print_flavor_table n "states"
    (List.map (fun (fin, fout) → fin @ fout) (CF.flavors amplitudes));
  nl ()

let num_flavors amplitudes =
  List.length (CF.flavors amplitudes)

let print_color_flows_table_old abbrev = function
| [] →
  printf "%d@[%d>integer,%dimension(n_cindex,%n_prt,%n_cflow)]:";
  printf "@table_color_flows"; nl ()
| - :: tuples' as tuples →
  ignore (List.fold_left (fun i tuple →
    printf

```

```

        "␣␣@ [<2>integer,␣dimension(n_cindex,␣n_prt),␣parameter,␣private␣::";
        printf "@␣%s%04d␣=␣reshape␣(␣/␣" abbrev i;
        begin match CFlow.to_lists tuple with
        | [] → ()
        | cf1 :: cf_n →
            printf "@␣%s" (String.concat "," (List.map string_of_int cf1));
            List.iter (function cf →
                printf ",@␣␣%s" (String.concat "," (List.map string_of_int cf))) cf_n
        end;
        printf "@␣/),@␣(/␣n_cindex,␣n_prt␣/␣)␣";
        nl (); succ i) 1 tuples);
    printf
        "␣␣@ [<2>integer,␣dimension(n_cindex,␣n_prt,␣n_cflow),␣parameter␣::";
        printf "@␣table_color_flows_old␣=@␣reshape␣(␣/␣";
        printf "@␣%s%04d" abbrev 1;
        ignore (List.fold_left (fun i tuple →
            printf ",@␣%s%04d" abbrev i; succ i) 2 tuples');
        printf "@␣/),@␣(/␣n_cindex,␣n_prt,␣n_cflow␣/␣)␣"; nl ()
let print_ghost_flags_table_old abbrev = function
| [] →
    printf "␣␣@ [<2>logical,␣dimension(n_prt,␣n_cflow)␣::";
    printf "@␣table_ghost_flags"; nl ()
| _ :: tuples' as tuples →
    ignore (List.fold_left (fun i tuple →
        printf
            "␣␣@ [<2>logical,␣dimension(n_prt),␣parameter,␣private␣::";
            printf "@␣%s%04d␣=␣(␣/␣" abbrev i;
            begin match CFlow.ghost_flags tuple with
            | [] → ()
            | gf1 :: gfn →
                printf "@␣%s" (if gf1 then "T" else "F");
                List.iter (function gf → printf ",@␣␣%s" (if gf then "T" else "F")) gfn
            end;
            printf "@␣/␣";
            nl (); succ i) 1 tuples);
    printf
        "␣␣@ [<2>logical,␣dimension(n_prt,␣n_cflow),␣parameter␣::";
        printf "@␣table_ghost_flags_old␣=@␣reshape␣(␣/␣";
        printf "@␣%s%04d" abbrev 1;
        ignore (List.fold_left (fun i tuple →
            printf ",@␣%s%04d" abbrev i; succ i) 2 tuples');
        printf "@␣/),@␣(/␣n_prt,␣n_cflow␣/␣)␣"; nl ()
let print_color_flows_table tuples =
    printf
        "␣␣@ [<2>integer,␣dimension(n_cindex,n_prt,n_cflow),␣save%s␣::␣table_color_flows"
        protected; nl ();
    match tuples with
    | [] → ()
    | _ :: tuples' as tuples →

```

```

    ignore (List.fold_left (fun i tuple →
      begin match CFlow.to_lists tuple with
      | [] → ()
      | cf1 :: cfn →
        printf "%u@ [<2>data_table_color_flows(:,%4d) ]/" i;
        printf "@%s" (String.concat "," (List.map string_of_int cf1));
        List.iter (function cf →
          printf ",@%s" (String.concat "," (List.map string_of_int cf))) cfn;
        printf "@_/"; nl ()
      end;
      succ i) 1 tuples)

let print_ghost_flags_table tuples =
  printf
    "%u@ [<2>logical, dimension(n_prt,n_cflow), save%s::table_ghost_flags"
    protected; nl ();
  match tuples with
  | [] → ()
  | _ →
    ignore (List.fold_left (fun i tuple →
      begin match CFlow.ghost_flags tuple with
      | [] → ()
      | gf1 :: gfn →
        printf "%u@ [<2>data_table_ghost_flags(:,%4d) ]/" i;
        printf "@%s" (if gf1 then "T" else "F");
        List.iter (function gf → printf ",@%s" (if gf then "T" else "F")) gfn;
        printf "@_/";
        nl ()
      end;
      succ i) 1 tuples)

let format_power_of x
  { Color.Flow.num = num; Color.Flow.den = den; Color.Flow.power = pwr } =
  match num, den, pwr with
  | -, 0, _ → invalid_arg "format_power_of: zero denominator"
  | 0, _, _ → "+zero"
  | 1, 1, 0 | -1, -1, 0 → "+one"
  | -1, 1, 0 | 1, -1, 0 → "-one"
  | 1, 1, 1 | -1, -1, 1 → "+" ^ x
  | -1, 1, 1 | 1, -1, 1 → "-" ^ x
  | 1, 1, -1 | -1, -1, -1 → "+1/" ^ x
  | -1, 1, -1 | 1, -1, -1 → "-1/" ^ x
  | 1, 1, p | -1, -1, p →
    "+" ^ (if p > 0 then "" else "1/") ^ x ^ "*" ^ string_of_int (abs p)
  | -1, 1, p | 1, -1, p →
    "-" ^ (if p > 0 then "" else "1/") ^ x ^ "*" ^ string_of_int (abs p)
  | n, 1, 0 →
    (if n < 0 then "-" else "+") ^ string_of_int (abs n) ^ ".0_" ^ !kind
  | n, d, 0 →
    (if n × d < 0 then "-" else "+") ^
    string_of_int (abs n) ^ ".0_" ^ !kind ^ "/" ^

```

```

    string_of_int (abs d)
| n, 1, 1 →
    (if n < 0 then "-" else "+") ^ string_of_int (abs n) ^ "*" ^ x
| n, 1, -1 →
    (if n < 0 then "-" else "+") ^ string_of_int (abs n) ^ "/" ^ x
| n, d, 1 →
    (if n × d < 0 then "-" else "+") ^
    string_of_int (abs n) ^ ".0_" ^ !kind ^ "/" ^
    string_of_int (abs d) ^ "*" ^ x
| n, d, -1 →
    (if n × d < 0 then "-" else "+") ^
    string_of_int (abs n) ^ ".0_" ^ !kind ^ "/" ^
    string_of_int (abs d) ^ "/" ^ x
| n, 1, p →
    (if n < 0 then "-" else "+") ^ string_of_int (abs n) ^
    (if p > 0 then "*" else "/") ^ x ^ "**" ^ string_of_int (abs p)
| n, d, p →
    (if n × d < 0 then "-" else "+") ^
    string_of_int (abs n) ^ ".0_" ^ !kind ^ "/" ^
    string_of_int (abs d) ^
    (if p > 0 then "*" else "/") ^ x ^ "**" ^ string_of_int (abs p)

let format_powers_of x = function
| [] → "zero"
| powers → String.concat "" (List.map (format_power_of x) powers)

let print_color_factor_table_old table =
let n_cflow = Array.length table in
let n_cfactors = ref 0 in
for c1 = 0 to pred n_cflow do
  for c2 = 0 to pred n_cflow do
    match table.(c1).(c2) with
    | [] → ()
    | _ → incr n_cfactors
  done
done;
print_integer_parameter "n_cfactors" !n_cfactors;
if n_cflow ≤ 0 then begin
  printf "%d@(<2>type(%s), dimension(n_cfactors)):"
    omega_color_factor_abbrev;
  printf "@table_color_factors"; nl ()
end else begin
  printf
    "%d@(<2>type(%s), dimension(n_cfactors), parameter):"
    omega_color_factor_abbrev;
  printf "@table_color_factors=%d/@";
  let comma = ref "" in
  for c1 = 0 to pred n_cflow do
    for c2 = 0 to pred n_cflow do
      match table.(c1).(c2) with
      | [] → ()

```



```

      | cf →
        printf "%s@_s(%d,%d,%s)" !comma omega_color_factor_abbrev
          (succ c1) (succ c2) (format_powers_of nc_parameter cf);
        comma := ","
      done
done;
printf "@_/"; nl ()
end

```



We can optimize the following slightly by reusing common color factor parameters.

```

let print_color_factor_table table =
  let n_cflow = Array.length table in
  let n_cfactors = ref 0 in
  for c1 = 0 to pred n_cflow do
    for c2 = 0 to pred n_cflow do
      match table.(c1).(c2) with
      | [] → ()
      | _ → incr n_cfactors
    done
  done;
  print_integer_parameter "n_cfactors" !n_cfactors;
  printf "%%@<2>type(%s),_dimension(n_cfactors),_save%s_:"
    omega_color_factor_abbrev protected;
  printf "@_table_color_factors"; nl ();
  let i = ref 1 in
  if n_cflow > 0 then begin
    for c1 = 0 to pred n_cflow do
      for c2 = 0 to pred n_cflow do
        match table.(c1).(c2) with
        | [] → ()
        | cf →
          printf "%%@<2>real(kind=%s),_parameter,_private:_:_color_factor_%06d=_%s"
            !kind !i (format_powers_of nc_parameter cf);
          nl ();
          printf "%%@<2>data_table_color_factors(%6d)_/_s(%d,%d,color_factor_%06d)_\n"
            !i omega_color_factor_abbrev (succ c1) (succ c2) !i;
          incr i;
          nl ();
        done
      done
    end
  end

let print_color_tables amplitudes =
  let cflows = CF.color_flows amplitudes
  and cfactors = CF.color_factors amplitudes in
  (* print_color_flows_table_old "c" cflows; nl (); *)
  print_color_flows_table cflows; nl ();

```

```

(* print_ghost_flags_table_old "g" cflows; nl (); *)
print_ghost_flags_table cflows; nl ();
(* print_color_factor_table_old cfactors; nl (); *)
print_color_factor_table cfactors; nl ()

let option_to_logical = function
| Some _ → "T"
| None → "F"

let print_flavor_color_table_old abbrev n_flv n_cflow table =
if n_flv ≤ 0 ∨ n_cflow ≤ 0 then begin
  printf "%%@[<2>logical,%%dimension(n_flv,%%n_cflow)%%: ";
  printf "@_flv_col_is_allowed"; nl ()
end else begin
  for c = 0 to pred n_cflow do
    printf
      "%%@[<2>logical,%%dimension(n_flv),%%parameter,%%private%%: ";
    printf "@_%%s%04d=%%(/%%s" abbrev (succ c) (option_to_logical table.(0).(c));
    for f = 1 to pred n_flv do
      printf ",%%s" (option_to_logical table.(f).(c))
    done;
    printf "@_/"; nl ()
  done;
  printf
    "%%@[<2>logical,%%dimension(n_flv,%%n_cflow),%%parameter%%: ";
    printf "@_flv_col_is_allowed_old=%%reshape_%%(/%%s%04d" abbrev 1;
    for c = 1 to pred n_cflow do
      printf ",%%s%04d" abbrev (succ c)
    done;
    printf "@_/),%%(/%%n_flv,%%n_cflow%%)%%"; nl ()
  end

let print_flavor_color_table n_flv n_cflow table =
  printf
    "%%@[<2>logical,%%dimension(n_flv,%%n_cflow),%%save%%s%%: %%_flv_col_is_allowed"
    protected; nl ();
  if n_flv > 0 then begin
    for c = 0 to pred n_cflow do
      printf
        "%%@[<2>data_%%flv_col_is_allowed(:,%%4d)%%/" (succ c);
        printf "@_%%s" (option_to_logical table.(0).(c));
        for f = 1 to pred n_flv do
          printf ",%%s" (option_to_logical table.(f).(c))
        done;
        printf "@_/"; nl ()
    done;
  end

let print_amplitude_table a =
  (* print_flavor_color_table_old "a" (num_flavors a) (List.length (CF.color_flows a)) (CF.process_ta
*)
  print_flavor_color_table

```

```

      (num_flavors a) (List.length (CF.color_flows a)) (CF.process_table a);
    nl ();
    printf
      "%%@ [<2>complex(kind=%s), dimension(n_flg, n_cflow, n_hel), save:: amp" !kind;
    nl ();
    nl ()

let print_helicity_selection_table () =
  printf "%%@ [<2>logical, dimension(n_hel), save:: ";
  printf "hel_is_allowed= T"; nl ();
  printf "%%@ [<2>real(kind=%s), dimension(n_hel), save:: " !kind;
  printf "hel_max_abs= 0"; nl ();
  printf "%%@ [<2>real(kind=%s), save:: " !kind;
  printf "hel_sum_abs= 0, ";
  printf "hel_threshold= 1E10"; nl ();
  printf "%%@ [<2>integer, save:: ";
  printf "hel_count= 0, ";
  printf "hel_cutoff= 100"; nl ();
  printf "%%@ [<2>integer:: ";
  printf "i"; nl ();
  printf "%%@ [<2>integer, save, dimension(n_hel):: ";
  printf "hel_map= (/ (i, i= 1, n_hel) /)"; nl ();
  printf "%%@ [<2>integer, save:: hel_finite= n_hel"; nl ();
  nl ()

```

Optional MD5 sum function

```

let print_md5sum_functions = function
| Some s →
  printf "%%@ [<5>"; if !fortran95 then printf "pure ";
  printf "function md5sum"; nl ();
  printf "%%character(len=32):: md5sum"; nl ();
  printf "%%DON'T EVEN THINK of modifying the following line!"; nl ();
  printf "%%md5sum= \"%s\" s"; nl ();
  printf "%%end function md5sum"; nl ();
  nl ()
| None → ()

```

Maintenance & Inquiry Functions

```

let print_maintenance_functions amplitudes =
  if !whizard then begin
    printf "%%subroutine init(par)"; nl ();
    printf "%%real(kind=%s), dimension(*), intent(in):: par" !kind; nl ();
    printf "%%call import_from_whizard(par)"; nl ();
    printf "%%end subroutine init"; nl ();
    nl ();
  end

```

```

        printf "subroutine_final()"; nl ();
        printf "end_subroutine_final"; nl ();
        nl ();
        printf "subroutine_update_alpha_s(alpha_s)"; nl ();
        printf "real(kind=%s),intent(in)::alpha_s" !kind; nl ();
        printf "call_model_update_alpha_s(alpha_s)"; nl ();
        printf "end_subroutine_update_alpha_s"; nl ();
        nl ();
    end

let print_inquiry_function_openmp () = begin
    printf "pure_function_openmp_supported()_result(status)"; nl ();
    printf "logical::status"; nl ();
    printf "status=%s" (if !fortran95 then ".true." else ".false."); nl ();
    printf "end_function_openmp_supported"; nl ();
    nl ();
end

let print_inquiry_function_declarations name =
    printf "@[<2>public::number-%s,@%s" name name;
    nl ()

let print_numeric_inquiry_functions () =
    printf "@[<5>"; if !fortran95 then printf "pure";
    printf "function_number_particles_in()_result(n)"; nl ();
    printf "integer::n"; nl ();
    printf "n=n_in"; nl ();
    printf "end_function_number_particles_in"; nl ();
    nl ();
    printf "@[<5>"; if !fortran95 then printf "pure";
    printf "function_number_particles_out()_result(n)"; nl ();
    printf "integer::n"; nl ();
    printf "n=n_out"; nl ();
    printf "end_function_number_particles_out"; nl ();
    nl ();

let print_numeric_inquiry_functions (f, v) =
    printf "@[<5>"; if !fortran95 then printf "pure";
    printf "function_%s()_result(n)" f; nl ();
    printf "integer::n"; nl ();
    printf "n=%s" v; nl ();
    printf "end_function_%s" f; nl ();
    nl ();

let print_inquiry_functions name =
    printf "@[<5>"; if !fortran95 then printf "pure";
    printf "function_number-%s()_result(n)" name; nl ();
    printf "integer::n"; nl ();
    printf "n=size(table-%s,dim=2)" name; nl ();
    printf "end_function_number-%s" name; nl ();
    nl ();
    printf "@[<5>"; if !fortran95 then printf "pure";
    printf "subroutine_%s(a)" name; nl ();

```

```

    printf "uuuinteger, dimension(:, :), intent(out)u::ua"; nl ();
    printf "uuuuau=table-%s" name; nl ();
    printf "uuendsubroutine%s" name; nl ();
    nl ();

let print_color_flows () =
    printf "uu@ [<5>"; if !fortran95 then printf "pureu";
    printf "function_number_color_indicesu()resultu(n)"; nl ();
    printf "uuuintegeru::un"; nl ();
    printf "uuuunu=sizeu(table_color_flows, dim=1)"; nl ();
    printf "uuendfunction_number_color_indices"; nl ();
    nl ();
    printf "uu@ [<5>"; if !fortran95 then printf "pureu";
    printf "function_number_color_flowsu()resultu(n)"; nl ();
    printf "uuuintegeru::un"; nl ();
    printf "uuuunu=sizeu(table_color_flows, dim=3)"; nl ();
    printf "uuendfunction_number_color_flows"; nl ();
    nl ();
    printf "uu@ [<5>"; if !fortran95 then printf "pureu";
    printf "subroutine_color_flowsu(a, ug)"; nl ();
    printf "uuuinteger, dimension(:, :, :), intent(out)u::ua"; nl ();
    printf "uuuulogical, dimension(:, :), intent(out)u::ug"; nl ();
    printf "uuuuau=table_color_flows"; nl ();
    printf "uuuugu=table_ghost_flags"; nl ();
    printf "uuendsubroutine_color_flows"; nl ();
    nl ();

let print_color_factors () =
    printf "uu@ [<5>"; if !fortran95 then printf "pureu";
    printf "function_number_color_factorsu()resultu(n)"; nl ();
    printf "uuuintegeru::un"; nl ();
    printf "uuuunu=sizeu(table_color_factors)"; nl ();
    printf "uuendfunction_number_color_factors"; nl ();
    nl ();
    printf "uu@ [<5>"; if !fortran95 then printf "pureu";
    printf "subroutine_color_factorsu(cf)"; nl ();
    printf "uuuu type(%s), dimension(:), intent(out)u::ucf"
        omega_color_factor_abbrev; nl ();
    printf "uuuu cfu=table_color_factors"; nl ();
    printf "uuendsubroutine_color_factors"; nl ();
    nl ();
    printf "uu@ [<5>"; if !fortran95 then printf "pureu";
    printf "function_color_sumu(flv, uhel)resultu(amp2)"; nl ();
    printf "uuuinteger, intent(in)u::uflv, uhel"; nl ();
    printf "uuuu real(kind=%s)u::uamp2" !kind; nl ();
    printf "uuuu amp2u=realu(omega_color_sumu(flv, uhel, uamp, u table_color_factors))"; nl ();
    printf "uuendfunction_color_sum"; nl ();
    nl ();

let print_dispatch_functions () =
    printf "uu@ [<5>";
    printf "subroutine_new_eventu(p)"; nl ();

```

```

printf "      real(kind=%s), dimension(0:3,*), intent(in) :: p" !kind; nl ();
printf "      logical :: mask_dirty"; nl ();
printf "      integer :: hel"; nl ();
printf "      call calculate_amplitudes(amp, p, hel_is_allowed)"; nl ();
printf "      if ((hel_threshold.gt..0).and.(hel_count.le.hel_cutoff)) then"; nl ();
printf "        call @(<3>omega_update_helicity_selection@(hel_count,@amp,@";
printf "hel_max_abs,@hel_sum_abs,@hel_is_allowed,@hel_threshold,@hel_cutoff,@mask";
printf "        if (mask_dirty) then"; nl ();
printf "          hel_finite=0"; nl ();
printf "          do hel=1, n_hel"; nl ();
printf "            if (hel_is_allowed(hel)) then"; nl ();
printf "              hel_finite=hel_finite+1"; nl ();
printf "              hel_map(hel_finite)=hel"; nl ();
printf "            end if"; nl ();
printf "          end do"; nl ();
printf "        end if"; nl ();
printf "      end if"; nl ();
printf "    end subroutine new_event"; nl ();
nl ();
printf "    @(<5>";
printf "    subroutine reset_helicity_selection(threshold,cutoff)"; nl ();
printf "      real(kind=%s), intent(in) :: threshold" !kind; nl ();
printf "      integer, intent(in) :: cutoff"; nl ();
printf "      integer :: i"; nl ();
printf "      hel_is_allowed=T"; nl ();
printf "      hel_max_abs=0"; nl ();
printf "      hel_sum_abs=0"; nl ();
printf "      hel_count=0"; nl ();
printf "      hel_threshold=threshold"; nl ();
printf "      hel_cutoff=cutoff"; nl ();
printf "      hel_map=/(i,i=1,n_hel)/"; nl ();
printf "      hel_finite=n_hel"; nl ();
printf "    end subroutine reset_helicity_selection"; nl ();
nl ();
printf "    @(<5>"; if !fortran95 then printf "pure";
printf "    function is_allowed(flv,hel,col) result(yorn)"; nl ();
printf "      logical :: yorn"; nl ();
printf "      integer, intent(in) :: flv,hel,col"; nl ();
printf "      yorn=hel_is_allowed(hel).and.";
printf "flv_col_is_allowed(flv,col)"; nl ();
printf "    end function is_allowed"; nl ();
nl ();
printf "    @(<5>"; if !fortran95 then printf "pure";
printf "    function get_amplitude(flv,hel,col) result(amp_result)"; nl ();
printf "      complex(kind=%s) :: amp_result" !kind; nl ();
printf "      integer, intent(in) :: flv,hel,col"; nl ();
printf "      amp_result=amp(flv,col,hel)"; nl ();
printf "    end function get_amplitude"; nl ();
nl ();

```

Main Function

```

let format_power_of_nc
  { Color.Flow.num = num; Color.Flow.den = den; Color.Flow.power = pwr } =
  match num, den, pwr with
  | -, 0, _ → invalid_arg "format_power_of_nc: zero denominator"
  | 0, _, _ → ""
  | 1, 1, 0 | -1, -1, 0 → "+1"
  | -1, 1, 0 | 1, -1, 0 → "-1"
  | 1, 1, 1 | -1, -1, 1 → "+N"
  | -1, 1, 1 | 1, -1, 1 → "-N"
  | 1, 1, -1 | -1, -1, -1 → "+1/N"
  | -1, 1, -1 | 1, -1, -1 → "-1/N"
  | 1, 1, p | -1, -1, p →
    "+" ^ (if p > 0 then "" else "1/") ^ "N" ^ string_of_int (abs p)
  | -1, 1, p | 1, -1, p →
    "-" ^ (if p > 0 then "" else "1/") ^ "N" ^ string_of_int (abs p)
  | n, 1, 0 →
    (if n < 0 then "-" else "+") ^ string_of_int (abs n)
  | n, d, 0 →
    (if n × d < 0 then "-" else "+") ^
    string_of_int (abs n) ^ "/" ^ string_of_int (abs d)
  | n, 1, 1 →
    (if n < 0 then "-" else "+") ^ string_of_int (abs n) ^ "N"
  | n, 1, -1 →
    (if n < 0 then "-" else "+") ^ string_of_int (abs n) ^ "/N"
  | n, d, 1 →
    (if n × d < 0 then "-" else "+") ^
    string_of_int (abs n) ^ "/" ^ string_of_int (abs d) ^ "N"
  | n, d, -1 →
    (if n × d < 0 then "-" else "+") ^
    string_of_int (abs n) ^ "/" ^ string_of_int (abs d) ^ "/N"
  | n, 1, p →
    (if n < 0 then "-" else "+") ^ string_of_int (abs n) ^
    (if p > 0 then "*" else "/") ^ "N" ^ string_of_int (abs p)
  | n, d, p →
    (if n × d < 0 then "-" else "+") ^ string_of_int (abs n) ^ "/" ^
    string_of_int (abs d) ^ (if p > 0 then "*" else "/") ^ "N" ^ string_of_int (abs p)

let format_powers_of_nc = function
  | [] → "0"
  | powers → String.concat "_" (List.map format_power_of_nc powers)

let print_description cmdline amplitudes () =
  printf "!File generated automatically by 0'Mega"; nl();
  printf "!"; nl();
  printf "!_s" cmdline; nl();
  printf "!"; nl();
  printf "!with all scattering amplitudes for the process(es)"; nl();

```

```

printf "!"; nl ();
printf "!uuuflavor_ucombinations:"; nl ();
printf "!"; nl ();
ThoList.iteri
  (fun i process →
    printf "!uuuuu%3d:_%s" i (process_sans_color_to_string process); nl ())
  1 (CF.flavors amplitudes);
printf "!"; nl ();
printf "!uuucolor_uflows:"; nl ();
printf "!"; nl ();
ThoList.iteri
  (fun i cflow →
    printf "!uuuuu%3d:_%s" i (cflow_to_string cflow); nl ())
  1 (CF.color_flows amplitudes);
printf "!"; nl ();
printf "!uuuuuNB:_.i.g._not_all_color_flows_contribute_to_all_flavor"; nl ();
printf "!uuuuucombinations._uuConsult_the_array_FLV_COL_IS_ALLOWED"; nl ();
printf "!uuuuubelow_for_the_allowed_combinations."; nl ();
printf "!"; nl ();
printf "!uuuColor_uFactors:"; nl ();
printf "!"; nl ();
let cfactors = CF.color_factors amplitudes in
for c1 = 0 to pred (Array.length cfactors) do
  for c2 = 0 to c1 do
    match cfactors.(c1).(c2) with
    | [] → ()
    | cfactor →
      printf "!uuuuu(%3d,%3d):_%s"
        (succ c1) (succ c2) (format_powers_of_nc cfactor); nl ()
  done
done;
printf "!"; nl ();
printf "!uuuvanishing_or_redundant_flavor_ucombinations:"; nl ();
printf "!"; nl ();
List.iter (fun process →
  printf "!uuuuuuuuuuu%s" (process_sans_color_to_string process); nl ())
  (CF.vanishing_flavors amplitudes);
printf "!"; nl ();
begin
  match CF.constraints amplitudes with
  | None → ()
  | Some s →
    printf
      "!uuu_diagram_selection_(MIGHT_BREAK_GAUGE_INVARIANCE!!!):"; nl ();
    printf "!"; nl ();
    printf "!uuuuu%s" s; nl ();
    printf "!"; nl ();
end;
begin match RCS.description M.rcs with
| line1 :: lines →

```



```

    printf "!in%s" line1; nl ();
    List.iter (fun s → printf "!!!!s" s; nl ()) lines
  | [] → printf "!in%s" (RCS.name M.rcs); nl ()
end;
printf "!"; nl ()

let print_version () =
  printf "!0'Mega_revision_control_information:"; nl ();
  List.iter (fun s → printf "!!!!s" s; nl ())
    (ThoList.flatmap RCS.summary (M.rcs :: rcs_list @ F.rcs_list))

```

Printing Modules

```

type accessibility =
  | Public
  | Private
  | Protected (* Fortran 2003 *)

let accessibility_to_string = function
  | Public → "public"
  | Private → "private"
  | Protected → "protected"

type used_symbol =
  | As_Is of string
  | Aliased of string × string

let print_used_symbol = function
  | As_Is name → printf "%s" name
  | Aliased (orig, alias) → printf "%s=>%s" alias orig

type used_module =
  | Full of string
  | Full_Aliased of string × (string × string) list
  | Subset of string × used_symbol list

let print_used_module = function
  | Full name
  | Full_Aliased (name, [])
  | Subset (name, []) →
    printf "use%s" name;
    nl ()
  | Full_Aliased (name, aliases) →
    printf " @[<5>use%s" name;
    List.iter
      (fun (orig, alias) → printf ",%s=>%s" alias orig)
      aliases;
    nl ()
  | Subset (name, used_symbol :: used_symbols) →
    printf " @[<5>use%s,only:" name;
    print_used_symbol used_symbol;

```

```

        List.iter (fun s → printf ",_"; print_used_symbol s) used_symbols;
        nl ()

type fortran_module =
{ module_name : string;
  default_accessibility : accessibility;
  used_modules : used_module list;
  public_symbols : string list;
  print_declarations : (unit → unit) list;
  print_implementations : (unit → unit) list }

let print_public = function
| name1 :: names →
    printf "___@(<2>public_::_%" name1;
    List.iter (fun n → printf ",_%" n) names; nl ()
| [] → ()

let print_public_interface generic procedures =
    printf "___public_::_%" generic; nl ();
    begin match procedures with
    | name1 :: names →
        printf "___interface_%" generic; nl ();
        printf "____@(<2>module_procedure_%" name1;
        List.iter (fun n → printf ",_%" n) names; nl ();
        printf "___end_interface"; nl ();
        print_public procedures
    | [] → ()
    end

let print_module m =
    printf "module_%" m.module_name; nl ();
    List.iter print_used_module m.used_modules;
    printf "___implicit_none"; nl ();
    printf "___%" (accessibility_to_string m.default_accessibility); nl ();
    print_public m.public_symbols; nl ();
    begin match m.print_declarations with
    | [] → ()
    | print_declarations →
        List.iter (fun f → f ()) print_declarations; nl ()
    end;
    begin match m.print_implementations with
    | [] → ()
    | print_implementations →
        printf "contains"; nl (); nl ();
        List.iter (fun f → f ()) print_implementations; nl ()
    end;
    printf "end_module_%" m.module_name; nl ()

let print_modules modules =
    List.iter print_module modules;
    print_version ();
    print_flush ()

```

```

let module_to_file line_length oc prelude m =
  output_string oc (m.module_name ^ "\n");
  let filename = m.module_name ^ ".f90" in
  let channel = open_out filename in
  setup_fortran_formatter line_length channel;
  prelude ();
  print_modules [m];
  close_out channel

let modules_to_file line_length oc prelude = function
| [] → ()
| m :: mlist →
  module_to_file line_length oc prelude m;
  List.iter (module_to_file line_length oc (fun () → ())) mlist

```

Chopping Up Amplitudes

```

let num_fusions_brackets size amplitudes =
  let num_fusions =
    max 1 size in
  let count_brackets =
    List.fold_left
      (fun sum process → sum + List.length (F.brackets process))
      0 (CF.processes amplitudes)
  and count_processes =
    List.length (CF.processes amplitudes) in
  if count_brackets > 0 then
    let num_brackets =
      max 1 ((num_fusions × count_processes) / count_brackets) in
    (num_fusions, num_brackets)
  else
    (num_fusions, 1)

let chop_amplitudes size amplitudes =
  let num_fusions, num_brackets = num_fusions_brackets size amplitudes in
  (ThoList.enumerate 1 (ThoList.chopn num_fusions (CF.fusions amplitudes)),
   ThoList.enumerate 1 (ThoList.chopn num_brackets (CF.processes amplitudes)))

let print_compute_fusions1 dictionary (n, fusions) =
  if !openmp then begin
    printf "subroutine_compute_fusions_%04d(%s)" n openmp_tld; nl ();
    printf "<5>type(%s),intent(inout):_%s" openmp_tld_type openmp_tld; nl ();
  end else begin
    printf "<5>subroutine_compute_fusions_%04d()" n; nl ();
  end;
  print_fusions dictionary fusions;
  printf "end_subroutine_compute_fusions_%04d" n; nl ()

and print_compute_brackets1 dictionary (n, processes) =
  if !openmp then begin

```

```

    printf "subroutine_compute_brackets_%04d(%s)" n openmp_tld; nl ();
    printf "[@<5>type(%s),intent(inout):_s" openmp_tld_type openmp_tld; nl ();
end else begin
    printf "[@<5>subroutine_compute_brackets_%04d()" n; nl ();
end;
List.iter (print_brackets dictionary) processes;
printf "end_subroutine_compute_brackets_%04d" n; nl ()

```

Common Stuff

```

let omega_public_symbols =
  ["number_particles_in"; "number_particles_out";
   "number_color_indices";
   "reset_helicity_selection"; "new_event";
   "is_allowed"; "get_amplitude"; "color_sum"; "openmp_supported"] @
  ThoList.flatmap
    (fun n → ["number_" ^ n; n])
    ["spin_states"; "flavor_states"; "color_flows"; "color_factors"]

let whizard_public_symbols md5sum =
  ["init"; "final"; "update_alpha_s"] @
  (match md5sum with Some _ → ["md5sum"] | None → [])

let used_modules () =
  [Full "kinds";
   Full Fermions.use_module;
   Full_Aliased ("omega_color", ["omega_color_factor", omega_color_factor_abbrev])] @
  List.map
    (fun m → Full m)
    (match !parameter_module with "" → !use_modules | pm →
pm :: !use_modules)

let public_symbols () =
  if !whizard then
    omega_public_symbols @ (whizard_public_symbols !md5sum)
  else
    omega_public_symbols

let print_constants amplitudes =
  printf "DON'T EVEN THINK of removing the following!"; nl ();
  printf "If the compiler complains about undeclared"; nl ();
  printf "or undefined variables, you are compiling"; nl ();
  printf "against an incompatible omega95 module!"; nl ();
  printf "[@<2>integer, dimension(%d), parameter, private:_]"
    (List.length require_library);
  printf "require=@_/@";
  print_list require_library;
  printf "_/"; nl(); nl ();

```

Using these parameters makes sense for documentation, but in practice, there is no need to ever change them.

```

List.iter
  (function name, value → print_integer_parameter name (value amplitudes))
  [ ("n_prt", num_particles);
    ("n_in", num_particles_in);
    ("n_out", num_particles_out);
    ("n_cflow", num_color_flows); (* Number of different color ampli-
tudes. *)
    ("n_cindex", num_color_indices); (* Maximum rank of color ten-
sors. *)
    ("n_flv", num_flavors); (* Number of different flavor amplitudes.
*)
    ("n_hel", num_helicities) (* Number of different helicity amplitudes.
*) ];
  nl ();
Abbreviations.
printf "!!NB: you MUST NOT change the value of %s here!!" nc_parameter; nl();
printf "!!It is defined here for convenience only and must be"; nl ();
printf "!!compatible with hardcoded values in the amplitude!"; nl ();
print_real_parameter nc_parameter (CM.nc ()); (* NC *)
List.iter
  (function name, value → print_logical_parameter name value)
  [ ("F", false); ("T", true) ]; nl ();
print_spin_tables amplitudes;
print_flavor_tables amplitudes;
print_color_tables amplitudes;
print_amplitude_table amplitudes;
print_helicity_selection_table ()
let print_interface amplitudes =
  print_md5sum_functions !md5sum;
  print_maintenance_functions amplitudes;
  List.iter print_numeric_inquiry_functions
    [("number_particles_in", "n_in");
     ("number_particles_out", "n_out")];
  List.iter print_inquiry_functions
    ["spin_states"; "flavor_states"];
  print_inquiry_function_openmp ();
  print_color_flows ();
  print_color_factors ();
  print_dispatch_functions ();
  nl();
  current_continuation_line := 0;
  if !km_write ∨ !km_pure then (Targets_Kmatrix.Fortran.print !km_pure);
  current_continuation_line := 1;
  nl()
let print_calculate_amplitudes_declarations_computations amplitudes =
  printf "@[<5>subroutine calculate_amplitudes(amp, k, mask)"; nl ();
  printf "complex(kind=%s), dimension(:, :, :), intent(out) : amp" !kind; nl ();
  printf "real(kind=%s), dimension(0:3, *), intent(in) : k" !kind; nl ();

```

```

printf "logical,dimension(:),intent(in)_:_mask"; nl ();
printf "integer,dimension(n_prt)_:_s"; nl ();
printf "integer:_:h,hi"; nl ();
declarations ();
begin match CF.processes amplitudes with
| p :: - → print_external_momenta p
| - → ()
end;
ignore (List.fold_left print_momenta PSet.empty (CF.processes amplitudes));
printf "amp=_0"; nl ();
if num_helicities amplitudes > 0 then begin
  printf "if(hel_finite==0)return"; nl ();
  if !openmp then begin
    printf "!$OMP_PARALLEL_DO_DEFAULT(SHARED)_PRIVATE(s,h,%s)_SCHEDULE(STATIC)" openmp;
  end;
  printf "do hi=_1,hel_finite"; nl ();
  printf "h=_hel_map(hi)"; nl ();
  printf "s=_table_spin_states(:,h)"; nl ();
  ignore (List.fold_left print_externals WFS.empty (CF.processes amplitudes));
  computations ();
  List.iter print_fudge_factor (CF.processes amplitudes);
  (* This sorting should slightly improve cache locality. *)
  let triple_snd = fun (_, x, _) → x
  in let triple_fst = fun (x, _, _) → x
  in let rec builder1 flvi flowi flows = match flows with
    | (Some a) :: tl → (flvi, flowi, flavors_symbol (flavors a)) :: (builder1 flvi (flowi + 1) tl)
    | None :: tl → builder1 flvi (flowi + 1) tl
    | [] → []
  in let rec builder2 flvi flvs = match flvs with
    | flv :: tl → (builder1 flvi 1 flv) @ (builder2 (flvi + 1) tl)
    | [] → []
  in let unsorted = builder2 1 (List.map Array.to_list (Array.to_list (CF.process_table amplitudes)))
  in let sorted = List.sort (fun a b →
    if (triple_snd a ≠ triple_snd b) then triple_snd a - triple_snd b else (triple_fst a - triple_fst b))
    unsorted
  in List.iter (fun (flvi, flowi, flv) →
    (printf "amp(%d,%d,h)_=%s" flvi flowi flv; nl ());) sorted;

  printf "end_do"; nl ();
  if !openmp then begin
    printf "!$OMP_END_PARALLEL_DO"; nl ();
  end;
end;
printf "end_subroutine_calculate_amplitudes"; nl ()

let print_compute_chops chopped_fusions chopped_brackets () =
  List.iter
    (fun (i, _) → printf "call_compute_fusions_%04d_(%s)" i
      (if !openmp then openmp_tld else ""); nl ());
  chopped_fusions;
  List.iter

```

```

(fun (i, _) → printf "        call compute_brackets_%04d (%s)" i
  (if !openmp then openmp_tld else ""); nl ())
chopped_brackets

```

Single Function

```

let amplitudes_to_channel_single_function cmdline oc amplitudes =

let print_declarations () =
  print_constants amplitudes

and print_implementations () =
  print_interface amplitudes;
  print_calculate_amplitudes
    (fun () → print_variable_declarations amplitudes)
    (fun () →
      print_fusions (CF.dictionary amplitudes) (CF.fusions amplitudes);
      List.iter
        (print_brackets (CF.dictionary amplitudes))
        (CF.processes amplitudes))
    amplitudes in

let fortran_module =
  { module_name = !module_name;
    used_modules = used_modules ();
    default_accessibility = Private;
    public_symbols = public_symbols ();
    print_declarations = [print_declarations];
    print_implementations = [print_implementations] } in

setup_fortran_formatter !line_length oc;
print_description cmdline amplitudes ();
print_modules [fortran_module]

```

Single Module

```

let amplitudes_to_channel_single_module cmdline oc size amplitudes =

let print_declarations () =
  print_constants amplitudes;
  print_variable_declarations amplitudes

and print_implementations () =
  print_interface amplitudes in

let chopped_fusions, chopped_brackets =
  chop_amplitudes size amplitudes in

let dictionary = CF.dictionary amplitudes in

let print_compute_amplitudes () =

```

```

    print_calculate_amplitudes
      (fun () → ())
      (print_compute_chops chopped_fusions chopped_brackets)
      amplitudes

and print_compute_fusions () =
  List.iter (print_compute_fusions1 dictionary) chopped_fusions

and print_compute_brackets () =
  List.iter (print_compute_brackets1 dictionary) chopped_brackets in

let fortran_module =
  { module_name = !module_name;
    used_modules = used_modules ();
    default_accessibility = Private;
    public_symbols = public_symbols ();
    print_declarations = [print_declarations];
    print_implementations = [print_implementations;
                             print_compute_amplitudes;
                             print_compute_fusions;
                             print_compute_brackets] } in

setup_fortran_formatter !line_length oc;
print_description cmdline amplitudes ();
print_modules [fortran_module]

```

Multiple Modules

```

let modules_of_amplitudes cmdline oc size amplitudes =

  let name = !module_name in

  let print_declarations () =
    print_constants amplitudes
  and print_variables () =
    print_variable_declarations amplitudes in

  let constants_module =
    { module_name = name ^ "_constants";
      used_modules = used_modules ();
      default_accessibility = Public;
      public_symbols = [];
      print_declarations = [print_declarations];
      print_implementations = [] } in

  let variables_module =
    { module_name = name ^ "_variables";
      used_modules = used_modules ();
      default_accessibility = Public;
      public_symbols = [];
      print_declarations = [print_variables];
      print_implementations = [] } in

```



```

let dictionary = CF.dictionary amplitudes in

let print_compute_fusions (n, fusions) () =
  if !openmp then begin
    printf "subroutine_compute_fusions_%04d(%s)" n openmp_tld; nl ();
    printf "type(%s), intent(inout) : %s" openmp_tld_type openmp_tld; nl ();
  end else begin
    printf "subroutine_compute_fusions_%04d()" n; nl ();
  end;
  print_fusions dictionary fusions;
  printf "end_subroutine_compute_fusions_%04d" n; nl () in

let print_compute_brackets (n, processes) () =
  if !openmp then begin
    printf "subroutine_compute_brackets_%04d(%s)" n openmp_tld; nl ();
    printf "type(%s), intent(inout) : %s" openmp_tld_type openmp_tld; nl ();
  end else begin
    printf "subroutine_compute_brackets_%04d()" n; nl ();
  end;
  List.iter (print_brackets dictionary) processes;
  printf "end_subroutine_compute_brackets_%04d" n; nl () in

let fusions_module (n, _ as fusions) =
  let tag = Printf.sprintf "_fusions_%04d" n in
  { module_name = name ^ tag;
    used_modules = (used_modules ()) @
      [Full constants_module.module_name;
       Full variables_module.module_name];
    default_accessibility = Private;
    public_symbols = ["compute" ^ tag];
    print_declarations = [];
    print_implementations = [print_compute_fusions fusions] } in

let brackets_module (n, _ as processes) =
  let tag = Printf.sprintf "_brackets_%04d" n in
  { module_name = name ^ tag;
    used_modules = (used_modules ()) @
      [Full constants_module.module_name;
       Full variables_module.module_name];
    default_accessibility = Private;
    public_symbols = ["compute" ^ tag];
    print_declarations = [];
    print_implementations = [print_compute_brackets processes] } in

let chopped_fusions, chopped_brackets =
  chop_amplitudes size amplitudes in

let fusions_modules =
  List.map fusions_module chopped_fusions in

let brackets_modules =
  List.map brackets_module chopped_brackets in

let print_implementations () =

```

```

    print_interface amplitudes;
    print_calculate_amplitudes
      (fun () → ())
      (print_compute_chops chopped_fusions chopped_brackets)
      amplitudes in

let public_module =
  { module_name = name;
    used_modules = (used_modules () @
                    [Full constants_module.module_name;
                     Full variables_module.module_name ] @
                    List.map
                      (fun m → Full m.module_name)
                      (fusions_modules @ brackets_modules));
    default_accessibility = Private;
    public_symbols = public_symbols ();
    print_declarations = [];
    print_implementations = [print_implementations] }
and private_modules =
  [constants_module; variables_module] @ fusions_modules @ brackets_modules in

(public_module, private_modules)

let amplitudes_to_channel_single_file cmdline oc size amplitudes =
  let public_module, private_modules =
    modules_of_amplitudes cmdline oc size amplitudes in
  setup_fortran_formatter !line_length oc;
  print_description cmdline amplitudes ();
  print_modules (private_modules @ [public_module])

let amplitudes_to_channel_multi_file cmdline oc size amplitudes =
  let public_module, private_modules =
    modules_of_amplitudes cmdline oc size amplitudes in
  modules_to_file !line_length oc
    (print_description cmdline amplitudes)
    (public_module :: private_modules)

```

Dispatch

```

let amplitudes_to_channel cmdline oc diagnostics amplitudes =
  parse_diagnostics diagnostics;
  match !output_mode with
  | Single_Function →
    amplitudes_to_channel_single_function cmdline oc amplitudes
  | Single_Module size →
    amplitudes_to_channel_single_module cmdline oc size amplitudes
  | Single_File size →
    amplitudes_to_channel_single_file cmdline oc size amplitudes
  | Multi_File size →
    amplitudes_to_channel_multi_file cmdline oc size amplitudes

```

```

    let parameters_to_channel oc =
      parameters_to_fortran oc (CM.parameters ())
  end
module Fortran = Make_Fortran(Fortran_Fermions)

```

Majorana Fermions



JR sez' (regarding the Majorana Feynman rules): For this function we need a different approach due to our aim of implementing the fermion vertices with the right line as ingoing (in a calculational sense) and the left line in a fusion as outgoing. In defining all external lines and the fermionic wavefunctions built out of them as ingoing we have to invert the left lines to make them outgoing. This happens by multiplying them with the inverse charge conjugation matrix in an appropriate representation and then transposing it. We must distinguish whether the direction of calculation and the physical direction of the fermion number flow are parallel or antiparallel. In the first case we can use the "normal" Feynman rules for Dirac particles, while in the second, according to the paper of Denner et al., we have to reverse the sign of the vector and antisymmetric bilinears of the Dirac spinors, cf. the *Coupling* module.

Note the subtlety for the left- and righthanded couplings: Only the vector part of these couplings changes in the appropriate cases its sign, changing the chirality to the negative of the opposite. (*JR's probably right, but I need to check myself ...*)

```

module Fortran_Majorana_Fermions : Fermions =
  struct
    let rcs = RCS.rename rcs_file "Targets.Fortran_Majorana_Fermions()"
    [ "generates_Fortran95_code_for_Dirac_and_Majorana_fermions";
      "using_revision_2003_03_A_of_module_omega95_bispinors" ]
    open Coupling
    open Format

    let psi_type = "bispinor"
    let psibar_type = "bispinor"
    let chi_type = "bispinor"
    let grav_type = "vectorspinor"
  end

```



JR sez' (regarding the Majorana Feynman rules): Because of our rules for fermions we are going to give all incoming fermions a u spinor and all outgoing fermions a v spinor, no matter whether they are Dirac fermions, antifermions or Majorana fermions. (*JR's probably right, but I need to check myself ...*)

```

let psi_incoming = "u"
let brs_psi_incoming = "brs_u"
let psibar_incoming = "u"
let brs_psibar_incoming = "brs_u"
let chi_incoming = "u"
let brs_chi_incoming = "brs_u"
let grav_incoming = "ueps"

let psi_outgoing = "v"
let brs_psi_outgoing = "brs_v"
let psibar_outgoing = "v"
let brs_psibar_outgoing = "brs_v"
let chi_outgoing = "v"
let brs_chi_outgoing = "brs_v"
let grav_outgoing = "veps"

let psi_propagator = "pr_psi"
let psibar_propagator = "pr_psi"
let chi_propagator = "pr_psi"
let grav_propagator = "pr_grav"

let psi_projector = "pj_psi"
let psibar_projector = "pj_psi"
let chi_projector = "pj_psi"
let grav_projector = "pj_grav"

let psi_gauss = "pg_psi"
let psibar_gauss = "pg_psi"
let chi_gauss = "pg_psi"
let grav_gauss = "pg_grav"

let format_coupling coeff c =
  match coeff with
  | 1 → c
  | -1 → "(-" ^ c ^ ")"
  | coeff → string_of_int coeff ^ "*" ^ c

let format_coupling_2 coeff c =
  match coeff with
  | 1 → c
  | -1 → "-" ^ c
  | coeff → string_of_int coeff ^ "*" ^ c

```



JR's coupling constant HACK, necessitated by tho's bad design descition.

```

let fastener s i =
  try
    let offset = (String.index s '(') in
    if ((String.get s (String.length s - 1)) ≠ ')') then
      failwith "fastener: wrong usage of parentheses"
    else
      let func_name = (String.sub s 0 offset) and

```

```

        tail =
        (String.sub s (succ offset) (String.length s - offset - 2)) in
    if (String.contains func_name ' ') ∨
       (String.contains tail ' ') ∨
       (String.contains tail ' ') then
        failwith "fastener: wrong usage of parentheses"
    else
        func_name ^ "(" ^ string_of_int i ^ ", " ^ tail ^ ")"
with
| Not_found →
    if (String.contains s ' ') then
        failwith "fastener: wrong usage of parentheses"
    else
        s ^ "(" ^ string_of_int i ^ ")"

let print_fermion_current coeff f c wf1 wf2 fusion =
    let c = format_coupling coeff c in
    match fusion with
    | F13 | F31 → printf "%s_ff(%s,%s,%s)" f c wf1 wf2
    | F23 | F21 → printf "f_%sf(%s,%s,%s)" f c wf1 wf2
    | F32 | F12 → printf "f_%sf(%s,%s,%s)" f c wf2 wf1

let print_fermion_current2 coeff f c wf1 wf2 fusion =
    let c = format_coupling_2 coeff c in
    let c1 = fastener c 1 and
        c2 = fastener c 2 in
    match fusion with
    | F13 | F31 → printf "%s_ff(%s,%s,%s,%s)" f c1 c2 wf1 wf2
    | F23 | F21 → printf "f_%sf(%s,%s,%s,%s)" f c1 c2 wf1 wf2
    | F32 | F12 → printf "f_%sf(%s,%s,%s,%s)" f c1 c2 wf2 wf1

let print_fermion_current_vector coeff f c wf1 wf2 fusion =
    let c = format_coupling coeff c in
    match fusion with
    | F13 → printf "%s_ff(%s,%s,%s)" f c wf1 wf2
    | F31 → printf "%s_ff(-%s,%s,%s)" f c wf1 wf2
    | F23 → printf "f_%sf(%s,%s,%s)" f c wf1 wf2
    | F32 → printf "f_%sf(%s,%s,%s)" f c wf2 wf1
    | F12 → printf "f_%sf(-%s,%s,%s)" f c wf2 wf1
    | F21 → printf "f_%sf(-%s,%s,%s)" f c wf1 wf2

let print_fermion_current2_vector coeff f c wf1 wf2 fusion =
    let c = format_coupling_2 coeff c in
    let c1 = fastener c 1 and
        c2 = fastener c 2 in
    match fusion with
    | F13 → printf "%s_ff(%s,%s,%s,%s)" f c1 c2 wf1 wf2
    | F31 → printf "%s_ff(-(s),%s,%s,%s)" f c1 c2 wf1 wf2
    | F23 → printf "f_%sf(%s,%s,%s,%s)" f c1 c2 wf1 wf2
    | F32 → printf "f_%sf(%s,%s,%s,%s)" f c1 c2 wf2 wf1
    | F12 → printf "f_%sf(-(s),%s,%s,%s)" f c1 c2 wf2 wf1
    | F21 → printf "f_%sf(-(s),%s,%s,%s)" f c1 c2 wf1 wf2

```

```

let print_fermion_current_chiral coeff f1 f2 c wf1 wf2 fusion =
  let c = format_coupling coeff c in
  match fusion with
  | F13 → printf "%s_ff(%s,%s,%s)" f1 c wf1 wf2
  | F31 → printf "%s_ff(-%s,%s,%s)" f2 c wf1 wf2
  | F23 → printf "f_%sf(%s,%s,%s)" f1 c wf1 wf2
  | F32 → printf "f_%sf(%s,%s,%s)" f1 c wf2 wf1
  | F12 → printf "f_%sf(-%s,%s,%s)" f2 c wf2 wf1
  | F21 → printf "f_%sf(-%s,%s,%s)" f2 c wf1 wf2

let print_fermion_current2_chiral coeff f c wf1 wf2 fusion =
  let c = format_coupling_2 coeff c in
  let c1 = fastener c 1 and
      c2 = fastener c 2 in
  match fusion with
  | F13 → printf "%s_ff(%s,%s,%s,%s)" f c1 c2 wf1 wf2
  | F31 → printf "%s_ff(-(s),-(s),%s,%s)" f c2 c1 wf1 wf2
  | F23 → printf "f_%sf(%s,%s,%s,%s)" f c1 c2 wf1 wf2
  | F32 → printf "f_%sf(%s,%s,%s,%s)" f c1 c2 wf2 wf1
  | F12 → printf "f_%sf(-(s),-(s),%s,%s)" f c2 c1 wf2 wf1
  | F21 → printf "f_%sf(-(s),-(s),%s,%s)" f c2 c1 wf1 wf2

let print_current = function
  | coeff, -, VA, - → print_fermion_current2_vector coeff "va"
  | coeff, -, V, - → print_fermion_current_vector coeff "v"
  | coeff, -, A, - → print_fermion_current coeff "a"
  | coeff, -, VL, - → print_fermion_current_chiral coeff "vl" "vr"
  | coeff, -, VR, - → print_fermion_current_chiral coeff "vr" "vl"
  | coeff, -, VLR, - → print_fermion_current2_chiral coeff "vlr"
  | coeff, -, SP, - → print_fermion_current2 coeff "sp"
  | coeff, -, S, - → print_fermion_current coeff "s"
  | coeff, -, P, - → print_fermion_current coeff "p"
  | coeff, -, SL, - → print_fermion_current coeff "sl"
  | coeff, -, SR, - → print_fermion_current coeff "sr"
  | coeff, -, SLR, - → print_fermion_current2 coeff "slr"
  | coeff, -, POT, - → print_fermion_current_vector coeff "pot"
  | coeff, -, -, - → invalid_arg
    "Targets.Fortran-Majorana-Fermions:_Not_needed_in_the_models"

let print_current_p = function
  | coeff, Psi, SL, Psi → print_fermion_current coeff "sl"
  | coeff, Psi, SR, Psi → print_fermion_current coeff "sr"
  | coeff, Psi, SLR, Psi → print_fermion_current2 coeff "slr"
  | coeff, -, -, - → invalid_arg
    "Targets.Fortran-Majorana-Fermions:_Not_needed_in_the_used_models"

let print_current_b = function
  | coeff, Psibar, SL, Psibar → print_fermion_current coeff "sl"
  | coeff, Psibar, SR, Psibar → print_fermion_current coeff "sr"
  | coeff, Psibar, SLR, Psibar → print_fermion_current2 coeff "slr"
  | coeff, -, -, - → invalid_arg
    "Targets.Fortran-Majorana-Fermions:_Not_needed_in_the_used_models"

```

This function is for the vertices with three particles including two fermions but also a momentum, therefore with a dimensionful coupling constant, e.g. the gravitino vertices. One has to distinguish between the two kinds of canonical orders in the string of gamma matrices. Of course, the direction of the string of gamma matrices is reversed if one goes from the *Gravbar*, *-*, *Psi* to the *Psibar*, *-*, *Grav* vertices, and the same is true for the couplings of the gravitino to the Majorana fermions. For more details see the tables in the *coupling* implementation.

We now have to fix the directions of the momenta. For making the compiler happy and because we don't want to make constructions of infinite complexity we list the momentum including vertices without gravitinos here; the pattern matching says that's better. Perhaps we have to find a better name now.

For the cases of *MOM*, *MOM5*, *MOML* and *MOMR* which arise only in BRST transformations we take the mass as a coupling constant. For *VMOM* we don't need a mass either. These vertices are like kinetic terms and so need not have a coupling constant. By this we avoid a strange and awful construction with a new variable. But be careful with a generalization if you want to use these vertices for other purposes.

```

let format_coupling_mom coeff c =
  match coeff with
  | 1 → c
  | -1 → "(-" ^ c ^ ")"
  | coeff → string_of_int coeff ^ "*" ^ c

let commute_proj f =
  match f with
  | "moml" → "lmom"
  | "momr" → "rmom"
  | "lmom" → "moml"
  | "rmom" → "momr"
  | "svl" → "svr"
  | "svr" → "svl"
  | "sl" → "sr"
  | "sr" → "sl"
  | "s" → "s"
  | "p" → "p"
  | _ → invalid_arg "Targets:Fortran-Majorana-Fermions: wrong case"

let print_fermion_current_mom coeff f c wf1 wf2 p1 p2 p12 fusion =
  let c = format_coupling_mom coeff c in
  let c1 = fastener c 1 and
    c2 = fastener c 2 in
  match fusion with
  | F13 → printf "%s_ff(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p12
  | F31 → printf "%s_ff(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p12
  | F23 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p1
  | F32 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf2 wf1 p2
  | F12 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf2 wf1 p2
  | F21 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p1

let print_fermion_current_mom_vector coeff f c wf1 wf2 p1 p2 p12 fusion =

```

```

let c = format_coupling_mom coeff c in
let c1 = fastener c 1 and
    c2 = fastener c 2 in
match fusion with
| F13 → printf "%s_ff(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p12
| F31 → printf "%s_ff(-%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p12
| F23 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p1
| F32 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf2 wf1 p2
| F12 → printf "f_%sf(-%s,%s,%s,%s,%s)" f c1 c2 wf2 wf1 p2
| F21 → printf "f_%sf(-%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p1

let print_fermion_current_mom_sign coeff f c wf1 wf2 p1 p2 p12 fusion =
let c = format_coupling_mom coeff c in
let c1 = fastener c 1 and
    c2 = fastener c 2 in
match fusion with
| F13 → printf "%s_ff(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p12
| F31 → printf "%s_ff(%s,%s,%s,%s,-(%s))" f c1 c2 wf1 wf2 p12
| F23 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p1
| F32 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf2 wf1 p2
| F12 → printf "f_%sf(%s,%s,%s,%s,-(%s))" f c1 c2 wf2 wf1 p2
| F21 → printf "f_%sf(%s,%s,%s,%s,-(%s))" f c1 c2 wf1 wf2 p1

let print_fermion_current_mom_sign_1 coeff f c wf1 wf2 p1 p2 p12 fusion =
let c = format_coupling coeff c in
match fusion with
| F13 → printf "%s_ff(%s,%s,%s,%s,%s)" f c wf1 wf2 p12
| F31 → printf "%s_ff(%s,%s,%s,-(%s))" f c wf1 wf2 p12
| F23 → printf "f_%sf(%s,%s,%s,%s,%s)" f c wf1 wf2 p1
| F32 → printf "f_%sf(%s,%s,%s,%s,%s)" f c wf2 wf1 p2
| F12 → printf "f_%sf(%s,%s,%s,-(%s))" f c wf2 wf1 p2
| F21 → printf "f_%sf(%s,%s,%s,-(%s))" f c wf1 wf2 p1

let print_fermion_current_mom_chiral coeff f c wf1 wf2 p1 p2 p12 fusion =
let c = format_coupling_mom coeff c and
    cf = commute_proj f in
let c1 = fastener c 1 and
    c2 = fastener c 2 in
match fusion with
| F13 → printf "%s_ff(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p12
| F31 → printf "%s_ff(%s,%s,%s,%s,-(%s))" cf c1 c2 wf1 wf2 p12
| F23 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf1 wf2 p1
| F32 → printf "f_%sf(%s,%s,%s,%s,%s)" f c1 c2 wf2 wf1 p2
| F12 → printf "f_%sf(%s,%s,%s,%s,-(%s))" cf c1 c2 wf2 wf1 p2
| F21 → printf "f_%sf(%s,%s,%s,%s,-(%s))" cf c1 c2 wf1 wf2 p1

let print_fermion_g_current coeff f c wf1 wf2 p1 p2 p12 fusion =
let c = format_coupling coeff c in
match fusion with
| F13 → printf "%s_grf(%s,%s,%s,%s,%s)" f c wf1 wf2 p12
| F31 → printf "%s_fgr(%s,%s,%s,%s,%s)" f c wf1 wf2 p12
| F23 → printf "gr_%sf(%s,%s,%s,%s,%s)" f c wf1 wf2 p1

```



```

| F32 → printf "gr_%sf(%s,%s,%s,%s)" f c wf2 wf1 p2
| F12 → printf "f_%sgr(%s,%s,%s,%s)" f c wf2 wf1 p2
| F21 → printf "f_%sgr(%s,%s,%s,%s)" f c wf1 wf2 p1
let print_fermion_g_2_current coeff f c wf1 wf2 p1 p2 p12 fusion =
  let c = format_coupling coeff c in
  match fusion with
  | F13 → printf "%s_grf(%s(1),%s(2),%s,%s,%s)" f c c wf1 wf2 p12
  | F31 → printf "%s_fgr(%s(1),%s(2),%s,%s,%s)" f c c wf1 wf2 p12
  | F23 → printf "gr_%sf(%s(1),%s(2),%s,%s,%s)" f c c wf1 wf2 p1
  | F32 → printf "gr_%sf(%s(1),%s(2),%s,%s,%s)" f c c wf2 wf1 p2
  | F12 → printf "f_%sgr(%s(1),%s(2),%s,%s,%s)" f c c wf2 wf1 p2
  | F21 → printf "f_%sgr(%s(1),%s(2),%s,%s,%s)" f c c wf1 wf2 p1
let print_fermion_g_current_rev coeff f c wf1 wf2 p1 p2 p12 fusion =
  let c = format_coupling coeff c in
  match fusion with
  | F13 → printf "%s_fgr(%s,%s,%s,%s)" f c wf1 wf2 p12
  | F31 → printf "%s_grf(%s,%s,%s,%s)" f c wf1 wf2 p12
  | F23 → printf "f_%sgr(%s,%s,%s,%s)" f c wf1 wf2 p1
  | F32 → printf "f_%sgr(%s,%s,%s,%s)" f c wf2 wf1 p2
  | F12 → printf "gr_%sf(%s,%s,%s,%s)" f c wf2 wf1 p2
  | F21 → printf "gr_%sf(%s,%s,%s,%s)" f c wf1 wf2 p1
let print_fermion_g_2_current_rev coeff f c wf1 wf2 p1 p2 p12 fusion =
  let c = format_coupling coeff c in
  match fusion with
  | F13 → printf "%s_fgr(%s(1),%s(2),%s,%s,%s)" f c c wf1 wf2 p12
  | F31 → printf "%s_grf(%s(1),%s(2),%s,%s,%s)" f c c wf1 wf2 p12
  | F23 → printf "f_%sgr(%s(1),%s(2),%s,%s,%s)" f c c wf1 wf2 p1
  | F32 → printf "f_%sgr(%s(1),%s(2),%s,%s,%s)" f c c wf2 wf1 p2
  | F12 → printf "gr_%sf(%s(1),%s(2),%s,%s,%s)" f c c wf2 wf1 p2
  | F21 → printf "gr_%sf(%s(1),%s(2),%s,%s,%s)" f c c wf1 wf2 p1
let print_fermion_g_current_vector coeff f c wf1 wf2 p1 p2 p12 fusion =
  let c = format_coupling coeff c in
  match fusion with
  | F13 → printf "%s_grf(%s,%s,%s)" f c wf1 wf2
  | F31 → printf "%s_fgr(-%s,%s,%s)" f c wf1 wf2
  | F23 → printf "gr_%sf(%s,%s,%s)" f c wf1 wf2
  | F32 → printf "gr_%sf(%s,%s,%s)" f c wf2 wf1
  | F12 → printf "f_%sgr(-%s,%s,%s)" f c wf2 wf1
  | F21 → printf "f_%sgr(-%s,%s,%s)" f c wf1 wf2
let print_fermion_g_current_vector_rev coeff f c wf1 wf2 p1 p2 p12 fusion =
  let c = format_coupling coeff c in
  match fusion with
  | F13 → printf "%s_fgr(%s,%s,%s)" f c wf1 wf2
  | F31 → printf "%s_grf(-%s,%s,%s)" f c wf1 wf2
  | F23 → printf "f_%sgr(%s,%s,%s)" f c wf1 wf2
  | F32 → printf "f_%sgr(%s,%s,%s)" f c wf2 wf1
  | F12 → printf "gr_%sf(-%s,%s,%s)" f c wf2 wf1
  | F21 → printf "gr_%sf(-%s,%s,%s)" f c wf1 wf2

```

```

let print_current_g = function
| coeff, -, MOM, - → print_fermion_current_mom_sign coeff "mom"
| coeff, -, MOM5, - → print_fermion_current_mom coeff "mom5"
| coeff, -, MOML, - → print_fermion_current_mom_chiral coeff "moml"
| coeff, -, MOMR, - → print_fermion_current_mom_chiral coeff "momr"
| coeff, -, LMOM, - → print_fermion_current_mom_chiral coeff "lmom"
| coeff, -, RMOM, - → print_fermion_current_mom_chiral coeff "rmom"
| coeff, -, VMOM, - → print_fermion_current_mom_sign_1 coeff "vmom"
| coeff, Gravbar, S, - → print_fermion_g_current coeff "s"
| coeff, Gravbar, SL, - → print_fermion_g_current coeff "sl"
| coeff, Gravbar, SR, - → print_fermion_g_current coeff "sr"
| coeff, Gravbar, SLR, - → print_fermion_g_2_current coeff "slr"
| coeff, Gravbar, P, - → print_fermion_g_current coeff "p"
| coeff, Gravbar, V, - → print_fermion_g_current coeff "v"
| coeff, Gravbar, VLR, - → print_fermion_g_2_current coeff "vlr"
| coeff, Gravbar, POT, - → print_fermion_g_current_vector coeff "pot"
| coeff, -, S, Grav → print_fermion_g_current_rev coeff "s"
| coeff, -, SL, Grav → print_fermion_g_current_rev coeff "sl"
| coeff, -, SR, Grav → print_fermion_g_current_rev coeff "sr"
| coeff, -, SLR, Grav → print_fermion_g_2_current_rev coeff "slr"
| coeff, -, P, Grav → print_fermion_g_current_rev (-coeff) "p"
| coeff, -, V, Grav → print_fermion_g_current_rev coeff "v"
| coeff, -, VLR, Grav → print_fermion_g_2_current_rev coeff "vlr"
| coeff, -, POT, Grav → print_fermion_g_current_vector_rev coeff "pot"
| coeff, -, -, - → invalid_arg
    "Targets.Fortran-Majorana-Fermions: not used in the models"

let print_current_mom = function
| coeff, -, -, - → invalid_arg
    "Targets.Fortran-Majorana-Fermions: Not needed in the models"

```

We need support for dimension-5 vertices with two fermions and two bosons, appearing in theories of supergravity and also together with in insertions of the supersymmetric current. There is a canonical order *fermionbar*, *boson_1*, *boson_2*, *fermion*, so what one has to do is a mapping from the fusions *F123* etc. to the order of the three wave functions *wf1*, *wf2* and *wf3*.

The function *d_p* (for distinct the particle) distinguishes which particle (scalar or vector) must be fused to in the special functions.

```

let d_p = function
| 1, ("sv" | "pv" | "svl" | "svr" | "slrv") → "1"
| 1, - → ""
| 2, ("sv" | "pv" | "svl" | "svr" | "slrv") → "2"
| 2, - → ""
| -, - → invalid_arg "Targets.Fortran-Majorana-Fermions: not used"

let wf_of_f wf1 wf2 wf3 f =
  match f with
  | (F123 | F423) → [wf2; wf3; wf1]
  | (F213 | F243 | F143 | F142 | F413 | F412) → [wf1; wf3; wf2]
  | (F132 | F432) → [wf3; wf2; wf1]
  | (F231 | F234 | F134 | F124 | F431 | F421) → [wf1; wf2; wf3]

```

```

| (F312 | F342) → [wf3; wf1; wf2]
| (F321 | F324 | F314 | F214 | F341 | F241) → [wf2; wf1; wf3]
let print_fermion_g4_brs_vector_current coeff f c wf1 wf2 wf3 fusion =
  let cf = commute_proj f and
    cp = format_coupling coeff c and
    cm = if f = "pv" then
      format_coupling coeff c
    else
      format_coupling (-coeff) c
  and
    d1 = d_p (1, f) and
    d2 = d_p (2, f) and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "f_%sf(%s,%s,%s,%s)" cf cm f1 f2 f3
  | (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "f_%sf(%s,%s,%s,%s)" f cp f1 f2 f3
  | (F134 | F143 | F314) → printf "%s%s_ff(%s,%s,%s,%s)" f d1 cp f1 f2 f3
  | (F124 | F142 | F214) → printf "%s%s_ff(%s,%s,%s,%s)" f d2 cp f1 f2 f3
  | (F413 | F431 | F341) → printf "%s%s_ff(%s,%s,%s,%s)" cf d1 cm f1 f2 f3
  | (F241 | F412 | F421) → printf "%s%s_ff(%s,%s,%s,%s)" cf d2 cm f1 f2 f3
let print_fermion_g4_svlr_current coeff f c wf1 wf2 wf3 fusion =
  let c = format_coupling_2 coeff c and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  let c1 = fastener c 1 and
    c2 = fastener c 2 in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "f_svlrf(-(s),-(s),%s,%s,%s)" c2 c1 f1 f2 f3
  | (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "f_svlrf(%s,%s,%s,%s,%s)" c1 c2 f1 f2 f3
  | (F134 | F143 | F314) →
    printf "svlr2_ff(%s,%s,%s,%s,%s)" c1 c2 f1 f2 f3
  | (F124 | F142 | F214) →
    printf "svlr1_ff(%s,%s,%s,%s,%s)" c1 c2 f1 f2 f3
  | (F413 | F431 | F341) →
    printf "svlr2_ff(-(s),-(s),%s,%s,%s)" c2 c1 f1 f2 f3
  | (F241 | F412 | F421) →
    printf "svlr1_ff(-(s),-(s),%s,%s,%s)" c2 c1 f1 f2 f3
let print_fermion_s2_current coeff f c wf1 wf2 wf3 fusion =
  let cp = format_coupling coeff c and
    cm = if f = "p" then
      format_coupling (-coeff) c
    else

```

```

    format_coupling coeff c
and
    cf = commute_proj f and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
match fusion with
| (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "%s*%f-%sf(%s,%s,%s)" f1 cf cm f2 f3
| (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "%s*%f-%sf(%s,%s,%s)" f1 f cp f2 f3
| (F134 | F143 | F314) →
    printf "%s*%s-%ff(%s,%s,%s)" f2 f cp f1 f3
| (F124 | F142 | F214) →
    printf "%s*%s-%ff(%s,%s,%s)" f2 f cp f1 f3
| (F413 | F431 | F341) →
    printf "%s*%s-%ff(%s,%s,%s)" f2 cf cm f1 f3
| (F241 | F412 | F421) →
    printf "%s*%s-%ff(%s,%s,%s)" f2 cf cm f1 f3
let print_fermion_s2p_current coeff f c wf1 wf2 wf3 fusion =
    let c = format_coupling_2 coeff c and
        f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
        f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
        f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
    let c1 = fastener c 1 and
        c2 = fastener c 2 in
    match fusion with
    | (F123 | F213 | F132 | F231 | F312 | F321) →
        printf "%s*%f-%sf(%s,-(%s),%s,%s)" f1 f c1 c2 f2 f3
    | (F423 | F243 | F432 | F234 | F342 | F324) →
        printf "%s*%f-%sf(%s,%s,%s,%s)" f1 f c1 c2 f2 f3
    | (F134 | F143 | F314) →
        printf "%s*%s-%ff(%s,%s,%s,%s)" f2 f c1 c2 f1 f3
    | (F124 | F142 | F214) →
        printf "%s*%s-%ff(%s,%s,%s,%s)" f2 f c1 c2 f1 f3
    | (F413 | F431 | F341) →
        printf "%s*%s-%ff(%s,-(%s),%s,%s)" f2 f c1 c2 f1 f3
    | (F241 | F412 | F421) →
        printf "%s*%s-%ff(%s,-(%s),%s,%s)" f2 f c1 c2 f1 f3
let print_fermion_s2lr_current coeff f c wf1 wf2 wf3 fusion =
    let c = format_coupling_2 coeff c and
        f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
        f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
        f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
    let c1 = fastener c 1 and
        c2 = fastener c 2 in
    match fusion with
    | (F123 | F213 | F132 | F231 | F312 | F321) →
        printf "%s*%f-%sf(%s,%s,%s,%s)" f1 f c2 c1 f2 f3

```

```

| (F423 | F243 | F432 | F234 | F342 | F324) →
  printf "%s*%s-%sf(%s,%s,%s,%s)" f1 f c1 c2 f2 f3
| (F134 | F143 | F314) →
  printf "%s*%s-%ff(%s,%s,%s,%s)" f2 f c1 c2 f1 f3
| (F124 | F142 | F214) →
  printf "%s*%s-%ff(%s,%s,%s,%s)" f2 f c1 c2 f1 f3
| (F413 | F431 | F341) →
  printf "%s*%s-%ff(%s,%s,%s,%s)" f2 f c2 c1 f1 f3
| (F241 | F412 | F421) →
  printf "%s*%s-%ff(%s,%s,%s,%s)" f2 f c2 c1 f1 f3
let print_fermion_g4_current coeff f c wf1 wf2 wf3 fusion =
  let c = format_coupling coeff c and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "f-%sgr(-(s),-(s),%s,%s,%s)" f c f1 f2 f3
  | (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "gr-%sf(%s,%s,%s,%s)" f c f1 f2 f3
  | (F134 | F143 | F314 | F124 | F142 | F214) →
    printf "%s-grf(%s,%s,%s,%s)" f c f1 f2 f3
  | (F413 | F431 | F341 | F241 | F412 | F421) →
    printf "%s-fgr(-(s),-(s),%s,%s,%s)" f c f1 f2 f3
let print_fermion_2_g4_current coeff f c wf1 wf2 wf3 fusion =
  let f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  let c = format_coupling_2 coeff c in
  let c1 = fastener c 1 and
    c2 = fastener c 2 in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "f-%sgr(-(s),-(s),%s,%s,%s)" f c2 c1 f1 f2 f3
  | (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "gr-%sf(%s,%s,%s,%s,%s)" f c1 c2 f1 f2 f3
  | (F134 | F143 | F314 | F124 | F142 | F214) →
    printf "%s-grf(%s,%s,%s,%s,%s)" f c1 c2 f1 f2 f3
  | (F413 | F431 | F341 | F241 | F412 | F421) →
    printf "%s-fgr(-(s),-(s),%s,%s,%s)" f c2 c1 f1 f2 f3
let print_fermion_2_g4_current coeff f c wf1 wf2 wf3 fusion =
  let f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  let c = format_coupling_2 coeff c in
  let c1 = fastener c 1 and
    c2 = fastener c 2 in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →

```

```

    printf "f-%sgr(-(s),-(s),s,s,s)" f c2 c1 f1 f2 f3
| (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "gr-%sf(s,s,s,s,s)" f c1 c2 f1 f2 f3
| (F134 | F143 | F314 | F124 | F142 | F214) →
    printf "s-grf(s,s,s,s,s)" f c1 c2 f1 f2 f3
| (F413 | F431 | F341 | F241 | F412 | F421) →
    printf "s-fgr(-(s),-(s),s,s,s)" f c2 c1 f1 f2 f3
let print_fermion_g4_current_rev coeff f c wf1 wf2 wf3 fusion =
  let c = format_coupling coeff c and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "f-%sgr(s,s,s,s,s)" f c f1 f2 f3
  | (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "gr-%sf(-(s),s,s,s,s)" f c f1 f2 f3
  | (F134 | F143 | F314 | F124 | F142 | F214) →
    printf "s-grf(-(s),s,s,s,s)" f c f1 f2 f3
  | (F413 | F431 | F341 | F241 | F412 | F421) →
    printf "s-fgr(s,s,s,s,s)" f c f1 f2 f3

```

Here we have to distinguish which of the two bosons is produced in the fusion of three particles which include both fermions.

```

let print_fermion_g4_vector_current coeff f c wf1 wf2 wf3 fusion =
  let c = format_coupling coeff c and
    d1 = d_p (1, f) and
    d2 = d_p (2, f) and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "f-%sgr(s,s,s,s,s)" f c f1 f2 f3
  | (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "gr-%sf(s,s,s,s,s)" f c f1 f2 f3
  | (F134 | F143 | F314) → printf "s%s-grf(s,s,s,s,s)" f d1 c f1 f2 f3
  | (F124 | F142 | F214) → printf "s%s-grf(s,s,s,s,s)" f d2 c f1 f2 f3
  | (F413 | F431 | F341) → printf "s%s-fgr(s,s,s,s,s)" f d1 c f1 f2 f3
  | (F241 | F412 | F421) → printf "s%s-fgr(s,s,s,s,s)" f d2 c f1 f2 f3
let print_fermion_2_g4_vector_current coeff f c wf1 wf2 wf3 fusion =
  let d1 = d_p (1, f) and
    d2 = d_p (2, f) and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  let c = format_coupling_2 coeff c in
  let c1 = fastener c 1 and
    c2 = fastener c 2 in

```

```

match fusion with
| (F123 | F213 | F132 | F231 | F312 | F321) →
  printf "f-%sgr(%s,%s,%s,%s,%s)" f c1 c2 f1 f2 f3
| (F423 | F243 | F432 | F234 | F342 | F324) →
  printf "gr-%sf(%s,%s,%s,%s,%s)" f c1 c2 f1 f2 f3
| (F134 | F143 | F314) → printf "%s%s-grf(%s,%s,%s,%s,%s)" f d1 c1 c2 f1 f2 f3
| (F124 | F142 | F214) → printf "%s%s-grf(%s,%s,%s,%s,%s)" f d2 c1 c2 f1 f2 f3
| (F413 | F431 | F341) → printf "%s%s-fgr(%s,%s,%s,%s,%s)" f d1 c1 c2 f1 f2 f3
| (F241 | F412 | F421) → printf "%s%s-fgr(%s,%s,%s,%s,%s)" f d2 c1 c2 f1 f2 f3
let print_fermion_g4_vector_current_rev coeff f c wf1 wf2 wf3 fusion =
  let c = format_coupling coeff c and
    d1 = d_p (1,f) and
    d2 = d_p (2,f) and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "gr-%sf(%s,%s,%s,%s,%s)" f c f1 f2 f3
  | (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "f-%sgr(%s,%s,%s,%s,%s)" f c f1 f2 f3
  | (F134 | F143 | F314) → printf "%s%s-fgr(%s,%s,%s,%s,%s)" f d1 c f1 f2 f3
  | (F124 | F142 | F214) → printf "%s%s-fgr(%s,%s,%s,%s,%s)" f d2 c f1 f2 f3
  | (F413 | F431 | F341) → printf "%s%s-grf(%s,%s,%s,%s,%s)" f d1 c f1 f2 f3
  | (F241 | F412 | F421) → printf "%s%s-grf(%s,%s,%s,%s,%s)" f d2 c f1 f2 f3
let print_fermion_2_g4_current_rev coeff f c wf1 wf2 wf3 fusion =
  let c = format_coupling_2 coeff c in
  let c1 = fastener c 1 and
    c2 = fastener c 2 and
    d1 = d_p (1,f) and
    d2 = d_p (2,f) in
  let f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
  match fusion with
  | (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "gr-%sf(%s,%s,%s,%s,%s)" f c1 c2 f1 f2 f3
  | (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "f-%sgr(-(s),-(s),%s,%s,%s)" f c1 c2 f1 f2 f3
  | (F134 | F143 | F314) →
    printf "%s%s-fgr(-(s),-(s),%s,%s,%s)" f d1 c1 c2 f1 f2 f3
  | (F124 | F142 | F214) →
    printf "%s%s-fgr(-(s),-(s),%s,%s,%s)" f d2 c1 c2 f1 f2 f3
  | (F413 | F431 | F341) →
    printf "%s%s-grf(%s,%s,%s,%s,%s)" f d1 c1 c2 f1 f2 f3
  | (F241 | F412 | F421) →
    printf "%s%s-grf(%s,%s,%s,%s,%s)" f d2 c1 c2 f1 f2 f3
let print_fermion_2_g4_vector_current_rev coeff f c wf1 wf2 wf3 fusion =
  (* Here we put in the extra minus sign from the coeff. *)

```

```

let c = format_coupling_coeff c in
let c1 = fastener c 1 and
    c2 = fastener c 2 in
let d1 = d_p (1,f) and
    d2 = d_p (2,f) and
    f1 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 0) and
    f2 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 1) and
    f3 = (List.nth (wf_of_f wf1 wf2 wf3 fusion) 2) in
match fusion with
| (F123 | F213 | F132 | F231 | F312 | F321) →
    printf "gr-%s(%s,%s,%s,%s)" f c1 c2 f1 f2 f3
| (F423 | F243 | F432 | F234 | F342 | F324) →
    printf "f-%sgr(%s,%s,%s,%s)" f c1 c2 f1 f2 f3
| (F134 | F143 | F314) → printf "%s%-fgr(%s,%s,%s,%s)" f d1 c1 c2 f1 f2 f3
| (F124 | F142 | F214) → printf "%s%-fgr(%s,%s,%s,%s)" f d2 c1 c2 f1 f2 f3
| (F413 | F431 | F341) → printf "%s%-grf(%s,%s,%s,%s)" f d1 c1 c2 f1 f2 f3
| (F241 | F412 | F421) → printf "%s%-grf(%s,%s,%s,%s)" f d2 c1 c2 f1 f2 f3
let print_current_g4 = function
| coeff, Gravbar, S2, _ → print_fermion_g4_current coeff "s2"
| coeff, Gravbar, SV, _ → print_fermion_g4_vector_current coeff "sv"
| coeff, Gravbar, SLV, _ → print_fermion_g4_vector_current coeff "slv"
| coeff, Gravbar, SRV, _ → print_fermion_g4_vector_current coeff "srv"
| coeff, Gravbar, SLRV, _ → print_fermion_2_g4_vector_current coeff "slrv"
| coeff, Gravbar, PV, _ → print_fermion_g4_vector_current coeff "pv"
| coeff, Gravbar, V2, _ → print_fermion_g4_current coeff "v2"
| coeff, Gravbar, V2LR, _ → print_fermion_2_g4_current coeff "v2lr"
| coeff, Gravbar, _, _ → invalid_arg "print_current_g4: not implemented"
| coeff, _, S2, Grav → print_fermion_g4_current_rev coeff "s2"
| coeff, _, SV, Grav → print_fermion_g4_vector_current_rev (-coeff) "sv"
| coeff, _, SLV, Grav → print_fermion_g4_vector_current_rev (-coeff) "slv"
| coeff, _, SRV, Grav → print_fermion_g4_vector_current_rev (-coeff) "srv"
| coeff, _, SLRV, Grav → print_fermion_2_g4_vector_current_rev coeff "slrv"
| coeff, _, PV, Grav → print_fermion_g4_vector_current_rev coeff "pv"
| coeff, _, V2, Grav → print_fermion_g4_vector_current_rev coeff "v2"
| coeff, _, V2LR, Grav → print_fermion_2_g4_current_rev coeff "v2lr"
| coeff, _, _, Grav → invalid_arg "print_current_g4: not implemented"
| coeff, _, S2, _ → print_fermion_s2_current coeff "s"
| coeff, _, P2, _ → print_fermion_s2_current coeff "p"
| coeff, _, S2P, _ → print_fermion_s2p_current coeff "sp"
| coeff, _, S2L, _ → print_fermion_s2_current coeff "sl"
| coeff, _, S2R, _ → print_fermion_s2_current coeff "sr"
| coeff, _, S2LR, _ → print_fermion_s2lr_current coeff "slr"
| coeff, _, V2, _ → print_fermion_g4_brs_vector_current coeff "v2"
| coeff, _, SV, _ → print_fermion_g4_brs_vector_current coeff "sv"
| coeff, _, PV, _ → print_fermion_g4_brs_vector_current coeff "pv"
| coeff, _, SLV, _ → print_fermion_g4_brs_vector_current coeff "svl"
| coeff, _, SRV, _ → print_fermion_g4_brs_vector_current coeff "svr"
| coeff, _, SLRV, _ → print_fermion_g4_svlr_current coeff "svlr"
| coeff, _, V2LR, _ → invalid_arg "Targets.print_current: not available"

```



```

let reverse_braket _ = false
let use_module = "omega95_bispinors"
let require_library =
  ["omega_bispinors_2010_01_A"; "omega_bispinor_cpls_2010_01_A"]
end
module Fortran_Majorana = Make_Fortran(Fortran_Majorana_Fermions)

```

FORTRAN 77

```
module Fortran77 = Dummy
```

15.2.2 O'Mega Virtual Machine

```
module VM = Dummy
```

15.2.3 C

```
module C = Dummy
```

C++

```
module Cpp = Dummy
```

Java

```
module Java = Dummy
```

15.2.4 O'Caml

```
module Ocaml = Dummy
```

15.2.5 *LaTeX*

```

module LaTeX = Dummy

List.iter print_current (F.rhs fusion);
let propagate code =
  printi { code = code; sign = 0; coupl = 0;
           lhs = int_of_string (format_p lhs);
           rhs1 = abs (M.pdg f); rhs2 = abs (M.pdg f) } in
match M.propagator f with
| Prop_Scalar → propagate ovm_PROPAGATE_SCALAR
| Prop_Col_Scalar →
  failwith "print_fusion: Prop_Col_Scalar not implemented yet!"
| Prop_Ghost →
  failwith "print_fusion: Prop_Ghost not implemented yet!"
| Prop_Spinor → propagate ovm_PROPAGATE_SPINOR
| Prop_ConjSpinor → propagate ovm_PROPAGATE_CONJSPINOR
| Prop_Majorana | Prop_Col_Majorana →
  failwith "print_fusion: Prop_Majorana not implemented yet!"
| Prop_Unitarity → propagate ovm_PROPAGATE_UNITARITY
| Prop_Col_Unitarity →
  failwith "print_fusion: Prop_Col_Unitarity not implemented yet!"
| Prop_Feynman → propagate ovm_PROPAGATE_FEYNMAN
| Prop_Col_Feynman →
  failwith "print_fusion: Prop_Col_Feynman not implemented yet!"
| Prop_Gauge xi →
  failwith "print_fusion: Prop_Gauge not implemented yet!"
| Prop_Rxi xi →
  failwith "print_fusion: Prop_Rxi not implemented yet!"
| Prop_Vectorspinor →
  failwith "print_fusion: Prop_Vectorspinor not implemented yet!"
| Prop_Tensor_2 → propagate ovm_PROPAGATE_TENSOR2
| Aux_Scalar | Aux_Spinor | Aux_ConjSpinor | Aux_Majorana
| Aux_Vector | Aux_Tensor_1 → ()
| Only_Insertion → ()

module P = Set.Make (struct type t = int list let compare = compare end)

let rec add_momenta lhs = function
| [] | [-] → invalid_arg "add_momenta"
| [rhs1; rhs2] →
  printi { code = ovm_ADD_MOMENTA; sign = 0; coupl = 0;
           lhs = int_of_string (format_p lhs);
           rhs1 = int_of_string (format_p rhs1);
           rhs2 = int_of_string (format_p rhs2) }
| rhs1 :: rhs →
  add_momenta lhs rhs;
  add_momenta lhs [lhs; rhs1]

let print_fusions amplitude =
  printf "@\n@(<2>BEGIN_FUSIONS";
  let momenta =

```

```

      List.fold_left (fun seen f →
        let wf = F.lhs f in
        let p = F.momentum_list wf in
        let momentum = format_p wf in
        if ¬ (P.mem p seen) then
          add_momenta wf (F.children (List.hd (F.rhs f)));
        print_fusion f;
        P.add p seen) P.empty (F.fusions amplitude)
    in
    printf "@]\nEND_FUSIONS"

let print_brackets amplitude =
  printf "@\n@ [<2>BEGIN_BRACKETS";
  printf "@\n!!!_not_implemented_yet_!!!";
  printf "@]\nEND_BRACKETS"

let print_fudge_factor amplitude =
  printf "@\n@ [<2>BEGIN_FUDGE";
  printf "@\n!!!_not_implemented_yet_!!!";
  printf "@]\nEND_FUDGE"

let amplitude_to_channel oc diagnostics amplitude =
  set_formatter_out_channel oc;
  printf "@\n@ [<2>BEGIN_AMPLITUDE_%s" (format_process amplitude);
  print externals amplitude;
  print_fusions amplitude;
  print_brackets amplitude;
  print_fudge_factor amplitude;
  printf "@]\nEND_AMPLITUDE"

let amplitudes_to_channel oc diagnostics amplitudes =
  List.iter (amplitude_to_channel oc diagnostics) (MF.allowed amplitudes)

let parameters_to_channel oc =
  set_formatter_out_channel oc;
  printf "@ [<2>BEGIN_PARAMETERS@\n";
  printf "!!!_not_implemented_yet_!!!@\n";
  printf "END_PARAMETERS@\n"

end

i × )

```

15.3 Interface of *Targets_Kmatrix*

```
module Fortran : sig val print : bool → unit end
```

15.4 Implementation of *Targets_Kmatrix*

```
let rcs_file = RCS.parse "Targets_Kmatrix" ["K-Matrix_Support_routines"]
{ RCS.revision = "$Revision: 4678$";
```

```

RCS.date = "$Date: 2013-09-25 08:32:49 +0200 (Wed, 25 Sep 2013) $";
RCS.author = "$Author: jr-reuter $";
RCS.source
= "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
module Fortran =
struct
  open Format

  let nl = print_newline

  Special functions for the K matrix approach. This might be generalized to other
  functions that have to have access to the parameters and coupling constants.
  At the moment, this is hardcoded.

  let print_pure_functions =
  let pure =
    if pure_functions then
      "pure_"
    else
      "" in
    printf "%sfunction_width_res(z,res,w_wkm,m,g)_result(w)" pure; nl ();
    printf "real(kind=default), intent(in) :: z, w_wkm, m, g"; nl ();
    printf "integer, intent(in) :: res"; nl ();
    printf "real(kind=default) :: w"; nl ();
    printf "if (z.eq.0 .AND. w_wkm.eq.0) then"; nl ();
    printf "w=0"; nl ();
    printf "else"; nl ();
    printf "if (w_wkm.eq.0) then"; nl ();
    printf "select case (res)"; nl ();
    printf "case (1) !! Scalar isosinglet"; nl ();
    printf "w=3.*g**2/32./Pi*_m**3/vev**2"; nl ();
    printf "case (2) !! Scalar isoquintet"; nl ();
    printf "w=g**2/64./Pi*_m**3/vev**2"; nl ();
    printf "case (3) !! Vector isotriplet"; nl ();
    printf "w=g**2/48./Pi*_m"; nl ();
    printf "case (4) !! Tensor isosinglet"; nl ();
    printf "w=g**2/320./Pi*_m**3/vev**2"; nl ();
    printf "case (5) !! Tensor isoquintet"; nl ();
    printf "w=g**2/1920./Pi*_m**3/vev**2"; nl ();
    printf "case default"; nl ();
    printf "w=0"; nl ();
    printf "end select"; nl ();
    printf "else"; nl ();
    printf "w=w_wkm"; nl ();
    printf "end if"; nl ();
    printf "end if"; nl ();
    printf "end function_width_res"; nl ();

```

```

nl ();
printf "%sfunction_s0stu(s,m)result(s0)" pure; nl ();
printf "real(kind=default),intent(in)::s,m"; nl ();
printf "real(kind=default)::s0"; nl ();
printf "if(m.ge.1.0e08)then"; nl ();
printf "s0=0"; nl ();
printf "else"; nl ();
printf "s0=m**2-s/2+m**4/s*log(m**2/(s+m**2))"; nl ();
printf "endif"; nl ();
printf "endfunction_s0stu"; nl ();
nl ();
printf "%sfunction_s1stu(s,m)result(s1)" pure; nl ();
printf "real(kind=default),intent(in)::s,m"; nl ();
printf "real(kind=default)::s1"; nl ();
printf "if(m.ge.1.0e08)then"; nl ();
printf "s1=0"; nl ();
printf "else"; nl ();
printf "s1=2*m**4/s+s/6+m**4/s**2*(2*m**2+s)&"; nl ();
printf "log(m**2/(s+m**2))"; nl ();
printf "endif"; nl ();
printf "endfunction_s1stu"; nl ();
nl ();
printf "%sfunction_s2stu(s,m)result(s2)" pure; nl ();
printf "real(kind=default),intent(in)::s,m"; nl ();
printf "real(kind=default)::s2"; nl ();
printf "if(m.ge.1.0e08)then"; nl ();
printf "s2=0"; nl ();
printf "else"; nl ();
printf "s2=m**4/s**2*(6*m**2+3*s)&"; nl ();
printf "m**4/s**3*(6*m**4+6*m**2*s+s**2)&"; nl ();
printf "log(m**2/(s+m**2))"; nl ();
printf "endif"; nl ();
printf "endfunction_s2stu"; nl ();
nl ();
printf "!!!%sfunction_s3stu(s,m)result(s3)" pure; nl ();
printf "!!!real(kind=default),intent(in)::s,m"; nl ();
printf "!!!real(kind=default)::s3"; nl ();
printf "!!!if(m.ge.1.0e08)then"; nl ();
printf "!!!s3=0"; nl ();
printf "!!!else"; nl ();
printf "!!!s3=m**4/s**3*(60*m**4+60*m**2*s+11*s**2)&"; nl ();
printf "m**4/s**4*(2*m**2+s)*(10*m**4+10*m**2*s+s**2)&"; nl ();
printf "log(m**2/(s+m**2))"; nl ();
printf "!!!endif"; nl ();
printf "!!!endfunction_s3stu"; nl ();
nl ();
printf "%sfunction_p0stu(s,m)result(p0)" pure; nl ();
printf "real(kind=default),intent(in)::s,m"; nl ();
printf "real(kind=default)::p0"; nl ();
printf "if(m.ge.1.0e08)then"; nl ();

```

```

printf "p0=0"; nl ();
printf "else"; nl ();
printf "p0=1+(2*s+m**2)*log(m**2/(s+m**2))/s"; nl ();
printf "endif"; nl ();
printf "endfunction_p0stu"; nl();
nl ();
printf "%sfunction_p1stu(s,m)result(p1)" pure; nl ();
printf "real(kind=default),intent(in)::s,m"; nl ();
printf "real(kind=default)::p1"; nl ();
printf "if(m.ge.1.0e08)then"; nl ();
printf "p1=0"; nl ();
printf "else"; nl ();
printf "p1=(m**2+2*s)/s**2*(2*s+(2*m**2+s)&"; nl();
printf "log(m**2/(s+m**2)))"; nl ();
printf "endif"; nl ();
printf "endfunction_p1stu"; nl();
nl ();
printf "%sfunction_d0stu(s,m)result(d0)" pure; nl ();
printf "real(kind=default),intent(in)::s,m"; nl ();
printf "real(kind=default)::d0"; nl ();
printf "if(m.ge.1.0e08)then"; nl ();
printf "d0=0"; nl ();
printf "else"; nl ();
printf "d0=(2*m**2+11*s)/2+(m**4+6*m**2*s+6*s**2)&"; nl();
printf "s*log(m**2/(s+m**2))"; nl ();
printf "endif"; nl ();
printf "endfunction_d0stu"; nl();
nl ();
printf "%sfunction_d1stu(s,m)result(d1)" pure; nl ();
printf "real(kind=default),intent(in)::s,m"; nl ();
printf "real(kind=default)::d1"; nl ();
printf "if(m.ge.1.0e08)then"; nl ();
printf "d1=0"; nl ();
printf "else"; nl ();
printf "d1=(s*(12*m**4+72*m**2*s+73*s**2)&"; nl();
printf "6*(2*m**2+s)*(m**4+6*m**2*s+6*s**2)&"; nl();
printf "log(m**2/(s+m**2)))/6/s**2"; nl ();
printf "endif"; nl ();
printf "endfunction_d1stu"; nl();
nl ();
printf "%sfunction_da00(cc,s,m)result(amp_00)" pure; nl ();
printf "real(kind=default),intent(in)::s"; nl ();
printf "real(kind=default),dimension(1:8),intent(in)::cc"; nl ();
printf "real(kind=default),dimension(1:5),intent(in)::m"; nl ();
printf "complex(kind=default)::a00_0,a00_1,a00_a,a00_f"; nl ();
printf "complex(kind=default),dimension(1:7)::a00"; nl ();
printf "complex(kind=default)::ii,jj,amp_00"; nl ();
printf "real(kind=default)::kappal,kappam,kappat"; nl ();
printf "ii=cmplx(0.0,1.0/32.0/Pi,default)"; nl ();
printf "jj=s**2/vev**4*ii"; nl ();

```

```

printf "        kappal_cc(8)*((mass(23)**2+mass(24)**2)/m(4)**2-2*mass(23)**2*mass(24)
printf "        kappam_cc(8)*((mass(23)**4+mass(24)**4)/m(4)**2/(mass(23)**2+mass(24)*
printf "        2*mass(23)**2*mass(24)**2/m(4)**4)"; nl ();
printf "        kppat_cc(8)*mass(23)**2*mass(24)**2/m(4)**4"; nl ();
printf "        !!!_Longitudinal"; nl ();
printf "        !!!_Scalar_isosinglet"; nl ();
printf "        a00(1)_cc(1)**2/vev**2*_s0stu(s,m(1))"; nl ();
printf "        if(cc(1)/=0) then"; nl ();
printf "        a00(1)_cc(1)-3.0*cc(1)**2/vev**2*_cc(1)"; nl ();
printf "        s**2/cmplx(s-m(1)**2,s**2/m(1)**3*width_res(w_res,1,wkm(1),m
printf "        end_if"; nl ();
printf "        !!!_Scalar_isoquintet"; nl ();
printf "        a00(2)_cc(2)**2/vev**2*_s0stu(s,m(2))/3.0"; nl ();
printf "        !!!_Vector_isotriplet"; nl ();
printf "        a00(3)_cc(3)**2*(4.0*p0stu(s,m(3)))+6.0*s/m(3)**2"; nl ();
printf "        !!!_Tensor_isosinglet"; nl ();
printf "        a00(4)_cc(4)**2/vev**2/3*_cc(4)*d0stu(s,m(4))"; nl ();
printf "        2*kappal*s0stu(s,m(4))"; nl ();
printf "        if(cc(4)/=0).and.(kappal/=0) then"; nl ();
printf "        a00(4)_cc(4)**2/vev**2*kappal*_cc(4)"; nl ();
printf "        s**2/cmplx(s-m(4)**2,s**2/m(4)**3*10*kappal*width_res(w_res,
printf "        end_if"; nl ();
printf "        !!!_Tensor_isoquintet"; nl ();
printf "        a00(5)_cc(5)**2/vev**2*(d0stu(s,m(5))"); nl ();
printf "        /3.0)/6.0"; nl ();
printf "        !!!_Transversal"; nl ();
printf "        !!!_Tensor_isosinglet"; nl ();
printf "        a00(6)_cc(6)**2/Pi/vev**6*mass(23)**2*mass(24)**2/4*_s**2"; nl ();
printf "        *(2-2*s/m(4)**2+s**2/m(4)**4)+kppat/2"; nl ();
printf "        if(a00(6)/=0) then"; nl ();
printf "        a00(6)_cc(6)/cmplx(s-m(4)**2,w_res/32/Pi*_realpart(a00(6)),defa
printf "        end_if"; nl ();
printf "        a00(6)_cc(6)**2/Pi/vev**6*mass(23)**2*mass(24)**2/12*_s0stu
printf "        *(3*(1+2*s/m(4)**2+2*s**2/m(4)**4)+kppat)"; nl ();
printf "        !!!_Mixed"; nl ();
printf "        !!!_Tensor_isosinglet"; nl ();
printf "        a00(7)_cc(7)*cc(6)*cc(4)/Pi/vev**4*(mass(23)**2+mass(24)**2)/4*_s**
printf "        *(1-4*s/m(4)**2+2*s**2/m(4)**4)+kappam"; nl ();
printf "        if(a00(7)/=0) then"; nl ();
printf "        a00(7)_cc(7)/cmplx(s-m(4)**2,w_res/32/Pi*_realpart(a00(7)),defa
printf "        end_if"; nl ();
printf "        a00(7)_cc(7)*cc(6)*cc(4)/Pi/vev**4*(mass(23)**2+mass(24)**2)/
printf "        *(12*s/m(4)**2+12*s**2/m(4)**4+2*kappam)"; nl ();
printf "        !!!_Fudge-Higgs"; nl ();
printf "        a00_f_cc(2)*fudge_higgs*s/vev**2"; nl ();
printf "        a00_f_cc(1)*5*(1-ghvva)**2/vev**2*mass(25)**2"; nl ();
printf "        !!!_Lowenergy_theory_alphas"; nl ();
printf "        a00_0_cc(8)*(7.*a4+11.*a5)/3.*s**2/vev**4"; nl ();
printf "        a00_1_cc(25.*log(lam_reg**2/s)/9+11./54.0_default)*s**2/vev**4"; nl ();
printf "        a00_a_cc(1)*a00_0_cc(1)+a00_1_cc(1)/16./Pi**2"; nl ();

```

```

printf "!!!!Unitarize"; nl ();
printf "!!!!if (fudge_km/=0) then"; nl ();
printf "!!!!amp_00=sum(a00)+a00_f+a00_a"; nl ();
printf "!!!!if (amp_00/=0) then"; nl ();
printf "!!!!amp_00=_a00_a-_a00_f-_part_r*(sum(a00)-a00(3))+1/(realpart(a00)-a00(3)); nl ();
printf "!!!!endif"; nl ();
printf "!!!!else"; nl ();
printf "!!!!amp_00=(1-part_r)*sum(a00)+part_r*a00(3)+a00_f"; nl ();
printf "!!!!endif"; nl ();
printf "!!!!amp_00=vev**4/s**2*_amp_00"; nl ();
printf "!!!!endfunction_da00"; nl ();
nl ();
printf "%sfunction_da02(cc,s,m) result(amp_02)" pure; nl ();
printf "!!!!real(kind=default),intent(in):_s"; nl ();
printf "!!!!real(kind=default),dimension(1:8),intent(in):_cc"; nl ();
printf "!!!!real(kind=default),dimension(1:5),intent(in):_m"; nl ();
printf "!!!!complex(kind=default):_a02_0,_a02_1,_a02_a"; nl ();
printf "!!!!complex(kind=default),dimension(1:7):_a02"; nl ();
printf "!!!!complex(kind=default):_ii,_jj,_amp_02"; nl ();
printf "!!!!real(kind=default):_kappal,_kappam,_kappat"; nl ();
printf "!!!!ii=_cmplx(0.0,1.0/32.0/Pi,default)"; nl ();
printf "!!!!jj=_s**2/vev**4*ii"; nl ();
printf "!!!!kappal=_cc(8)*((mass(23)**2+mass(24)**2)/m(4)**2-2*mass(23)**2*mass(24)**2/m(4)**4)"; nl ();
printf "!!!!kappam=_cc(8)*((mass(23)**4+mass(24)**4)/m(4)**2/(mass(23)**2+mass(24)**2))"; nl ();
printf "!!!!kappat=_cc(8)*mass(23)**2*mass(24)**2/m(4)**4"; nl ();
printf "!!!!Longitudinal"; nl ();
printf "!!!!Scalar_isosinglet"; nl ();
printf "!!!!a02(1)=-2.0*cc(1)**2/vev**2*_s2stu(s,m(1))"; nl ();
printf "!!!!Scalar_isoquintet"; nl ();
printf "!!!!a02(2)=-5.0*cc(2)**2/vev**2*_s2stu(s,m(2))/3.0"; nl ();
printf "!!!!Vector_isotriplet"; nl ();
printf "!!!!a02(3)=-4.0*cc(3)**2*(2*s+m(3)**2)*s2stu(s,m(3))/m(3)**4"; nl ();
printf "!!!!Tensor_isosinglet"; nl ();
printf "!!!!a02(4)=-_cc(4)**2/vev**2/3*_&"; nl ();
printf "!!!!(1.+6.*s/m(4)**2+6.*s**2/m(4)**4)-2*kappal)*_s2stu(s,m(4))"; nl ();
printf "!!!!if (cc(4)/=0) then"; nl ();
printf "!!!!a02(4)=-a02(4)-_cc(4)**2/vev**2/10._&"; nl ();
printf "!!!!*_s**2/cmplx(s-m(4)**2,width_res(w_res,4,wkm(4),m(4),cc(4)),_&"; nl ();
printf "!!!!endif"; nl ();
printf "!!!!Tensor_isoquintet"; nl ();
printf "!!!!a02(5)=-_cc(5)**2/vev**2*(5.0*(1.0+6.0*_&"; nl ();
printf "!!!!s/m(5)**2+6.0*s**2/m(5)**4)*s2stu(s,m(5))/3.0_&"; nl ();
printf "!!!!)/6.0"; nl ();
printf "!!!!Transversal"; nl ();
printf "!!!!Tensor_isosinglet"; nl ();
printf "!!!!a02(6)=-_cc(6)**2/Pi/vev**6*mass(23)**2*mass(24)**2/40*_s**2"; nl ();
printf "!!!!if (a02(6)/=0) then"; nl ();
printf "!!!!a02(6)=-a02(6)/cmplx(s-m(4)**2,-w_res/32/Pi*_realpart(a02(6)),default)"; nl ();
printf "!!!!endif"; nl ();

```



```

printf "a02(6)=a02(6)-cc(6)**2/Pi/vev**6*mass(23)**2*mass(24)**2/12*(s2stu
printf "*(3*(1+2*s/m(4)**2+2*s**2/m(4)**4)+kappat)"; nl ();
printf "!!!Mixed"; nl ();
printf "!!!Tensor_isosinglet"; nl ();
printf "a02(7)=cc(7)*cc(6)*cc(4)/Pi/vev**4*(mass(23)**2+mass(24)**2)/20*(s2stu
printf "*(s**2)"; nl ();
printf "if(a02(7)/=0)then"; nl ();
printf "a02(7)=a02(7)/cmplx(s-m(4)**2,-w_res/32/Pi*realpart(a02(7)),defa
printf "endif"; nl ();
printf "a02(7)=a02(7)-cc(7)*cc(6)*cc(4)/Pi/vev**4*(mass(23)**2+mass(24)**2)/
printf "*(12*s/m(4)**2+12*s**2/m(4)**4+2*kappam)"; nl ();
printf "!!!Low_energy_theory_alphas"; nl ();
printf "a02_0=(8.*(2.*a4+a5)/15.)*s**2/vev**4"; nl ();
printf "a02_1=(log(lam_reg**2/s)/9.-7./135.0_default)*s**2/vev**4"; nl ();
printf "a02_a=a02_0!!!+a02_1/16/Pi**2"; nl ();
printf "!!!Unitarize"; nl ();
printf "if(fudge_km/=0)then"; nl ();
printf "amp_02=sum(a02)+a02_a"; nl ();
printf "if(amp_02/=0)then"; nl ();
printf "amp_02=-a02_a-part_r*(sum(a02)-a02(3))+1/(realpart(1/amp_
printf "endif"; nl ();
printf "else"; nl ();
printf "amp_02=(1-part_r)*sum(a02)+part_r*a02(3)"; nl ();
printf "endif"; nl ();
printf "amp_02=vev**4/s**2*amp_02"; nl ();
printf "endfunction_da02"; nl ();
nl ();
printf "%sfunction_da11(cc,s,m)result(amp_11)" pure; nl ();
printf "real(kind=default),intent(in):s"; nl ();
printf "real(kind=default),dimension(1:8),intent(in):cc"; nl ();
printf "real(kind=default),dimension(1:5),intent(in):m"; nl ();
printf "complex(kind=default):a11_0,a11_1,a11_a,a11_f"; nl ();
printf "complex(kind=default),dimension(1:7):a11"; nl ();
printf "complex(kind=default):ii,jj,amp_11"; nl ();
printf "real(kind=default):kappal,kappam,kappat"; nl ();
printf "ii=cmplx(0.0,1.0/32.0/Pi,default)"; nl ();
printf "jj=s**2/vev**4*ii"; nl ();
printf "kappal=cc(8)*((mass(23)**2+mass(24)**2)/m(4)**2-2*mass(23)**2*mass(24)
printf "kappam=cc(8)*((mass(23)**4+mass(24)**4)/m(4)**2/(mass(23)**2+mass(24)
printf "kappat=cc(8)*mass(23)**2*mass(24)**2/m(4)**4"; nl ();
printf "Longitudinal"; nl ();
printf "Scalar_isosinglet"; nl ();
printf "a11(1)=2.0*cc(1)**2/vev**2*s1stu(s,m(1))"; nl ();
printf "Scalar_isoquintet"; nl ();
printf "a11(2)=5.0*cc(2)**2/vev**2*s1stu(s,m(2))/6.0"; nl ();
printf "Vector_isotriplet"; nl ();
printf "a11(3)=cc(3)**2*&"; nl ();
printf "*(s/m(3)**2+2.0*up1stu(s,m(3)))"; nl ();
printf "if(cc(3)/=0)then"; nl ();

```

```

printf "aaaaaaaaa11(3)=a11(3)-2./3.*cc(3)**2*&"; nl ();
printf "aaaaaaaaaaaaaaaaaaaaa s/cmplx(s-m(3)**2,s/m(3)*width_res(w_res,3,wkm(3),m(3),cc(3))
printf "aaaaaaaend_if"; nl ();
printf "aaaaaaa!!!Tensor_isosinglet"; nl ();
printf "aaaaaaa11(4)=cc(4)**2/vev**2*(d1stu(s,m(4)-2*kappal*s1stu(s,m(4)))&"; nl ();
printf "aaaaaaaaaaaaaaaaaaaaa/3.0"; nl ();
printf "aaaaaaa!!!Tensor_isoquintet"; nl ();
printf "aaaaaaa11(5)=5.0*cc(5)**2/vev**2*(d1stu(s,m(5)))&"; nl ();
printf "aaaaaaaaaaaaaaaaaaaaa)/36.0"; nl ();
printf "aaaaaaa!!!Tensor_transversal"; nl ();
printf "aaaaaaa!!!Tensor_isosinglet"; nl ();
printf "aaaaaaa11(6)=cc(6)**2/Pi/vev**6*mass(23)**2*mass(24)**2/12*(s1stu(s,m(4))
printf "aaaaaaaaaaaaaaaaaaaaa(3*(1+2*s/m(4)**2+2*s**2/m(4)**4)+kappat)cc(6)-2*(s/m(4)**2+s**2/m(4)
printf "aaaaaaa!!!Mixed"; nl ();
printf "aaaaaaa!!!Tensor_isosinglet"; nl ();
printf "aaaaaaa11(7)=cc(7)*cc(6)*cc(4)/Pi/vev**4*(mass(23)**2+mass(24)**2)/12*(s1
printf "aaaaaaaaaaaaaaaaaaaaa*(12*s/m(4)**2+12*s**2/m(4)**4+2*kappam)cc(6)-2*(s/m(4)**2+s**2/m(4)
printf "aaaaaaa!!!Fudge-Higgs"; nl ();
printf "aaaaaaa11_f=fudge_higgs*s/3./vev**2"; nl ();
printf "aaaaaaa!!!Low_energy_theory_alphas"; nl ();
printf "aaaaaaa11_0=4.*(a4-a5)/3.*s**2/vev**4"; nl ();
printf "aaaaaaa11_1=1.0/54.0-default*s**2/vev**4"; nl ();
printf "aaaaaaa11_a=a11_0!!!+a11_1/16/Pi**2"; nl ();
printf "aaaaaaa!!!Unitarize"; nl ();
printf "aaaaaaaif(fudge_km/=0)then"; nl ();
printf "aaaaaaaamp_11=sum(a11)+a11_f+a11_a"; nl ();
printf "aaaaaaaif(amp_11/=0)then"; nl ();
printf "aaaaaaaamp_11=cc(11)-a11_a-part_r*(sum(a11)-a11(3))+1/(realpart(1/amp_
printf "aaaaaaaend_if"; nl ();
printf "aaaaaaaelse"; nl ();
printf "aaaaaaaamp_11=cc(11)-part_r*(sum(a11)-a11(3))+a11_f"; nl ();
printf "aaaaaaaend_if"; nl ();
printf "aaaaaaaamp_11=vev**4/s**2*amp_11"; nl ();
printf "aaaaaaaend_function_da11"; nl ();
nl ();
printf "aaaaa%sfunction_da20(cc,s,m)result(amp_20)" pure; nl ();
printf "aaaaaaa real(kind=default),intent(in):s"; nl ();
printf "aaaaaaa real(kind=default),dimension(1:8),intent(in):cc"; nl ();
printf "aaaaaaa real(kind=default),dimension(1:5),intent(in):m"; nl ();
printf "aaaaaaa complex(kind=default):a20_0,a20_1,a20_a,a20_f"; nl ();
printf "aaaaaaa complex(kind=default),dimension(1:7):a20"; nl ();
printf "aaaaaaa complex(kind=default):ii,jj,amp_20"; nl ();
printf "aaaaaaa real(kind=default):kappal,kappam,kappat"; nl ();
printf "aaaaaaa ii=cc(11)+1.0/32.0/Pi,default"; nl ();
printf "aaaaaaa jj=s**2/vev**4*ii"; nl ();
printf "aaaaaaa!!!Scalar_isosinglet"; nl ();
printf "aaaaaaa kappal=cc(8)*((mass(23)**2+mass(24)**2)/m(4)**2-2*mass(23)**2*mass(24)
printf "aaaaaaa kappam=cc(8)*((mass(23)**4+mass(24)**4)/m(4)**2/(mass(23)**2+mass(24)
printf "aaaaaaa kappat=cc(8)*mass(23)**2*mass(24)**2/m(4)**4"; nl ();
printf "aaaaaaa kappat=cc(8)*mass(23)**2*mass(24)**2/m(4)**4"; nl ();

```

```

printf "!!!!!!Longitudinal"; nl ();
printf "!!!!!!a20(1)=-2.0*cc(1)**2/vev**2*_s0stu(s,m(1))"; nl ();
printf "!!!!!!ScalarIsoquintet"; nl ();
printf "!!!!!!a20(2)=-cc(2)**2/vev**2/6.*_s0stu(s,m(2))"; nl ();
printf "!!!!!!if(cc(2)/=0)then"; nl ();
printf "!!!!!!a20(2)=a20(2)-cc(2)**2/vev**2/2.*&"; nl ();
printf "!!!!!!s**2/cmplx(s-m(2)**2,s**2/m(2)**3*width_res(w_res,2,wkm(2),m(2))"; nl ();
printf "!!!!!!end_if"; nl ();
printf "!!!!!!VectorIsotriplet"; nl ();
printf "!!!!!!a20(3)=cc(3)**2*(2.0*p0stu(s,m(3)))+3.0*s/m(3)**2"; nl ();
printf "!!!!!!TensorIsosinglet"; nl ();
printf "!!!!!!a20(4)=-cc(4)**2/vev**2*(d0stu(s,m(4))-2*kappal*s0stu(s,m(4)))&"; nl ();
printf "!!!!!!/3.0"; nl ();
printf "!!!!!!TensorIsoquintet"; nl ();
printf "!!!!!!a20(5)=-cc(5)**2/vev**2*(d0stu(s,m(5)))&"; nl ();
printf "!!!!!!/36.0"; nl ();
printf "!!!!!!Transversal"; nl ();
printf "!!!!!!TensorIsosinglet"; nl ();
printf "!!!!!!a20(6)=-cc(6)**2/Pi/vev**6*mass(23)**2*mass(24)**2/12*_s0stu(s,m(4))"; nl ();
printf "!!!!!!*(3*(1+2*s/m(4)**2+2*s**2/m(4)**4)+kappat*_s**2/(s/m(4)**2-s**2/vev**2))"; nl ();
printf "!!!!!!Mixed"; nl ();
printf "!!!!!!TensorIsosinglet"; nl ();
printf "!!!!!!a20(7)=-cc(7)*cc(6)*cc(4)/Pi/vev**4*(mass(23)**2+mass(24)**2)/12*_s0stu(s,m(4))"; nl ();
printf "!!!!!!*(12*s/m(4)**2+12*s**2/m(4)**4+2*kappam*_s**2/(s/m(4)**2-s**2/vev**2))"; nl ();
printf "!!!!!!Fudge-Higgs"; nl ();
printf "!!!!!!a20_f=-fudge_higgs*s/vev**2"; nl ();
printf "!!!!!!a20_f=a20_f-0*2*(1-ghvva)**2/vev**2*mass(25)**2"; nl ();
printf "!!!!!!LowEnergyTheoryAlphas"; nl ();
printf "!!!!!!a20_0=16*(2*a4+a5)/3*s**2/vev**4"; nl ();
printf "!!!!!!a20_1=(10*log(lam_reg**2/s)/9+25/108.0-default)*_s**2/vev**4"; nl ();
printf "!!!!!!a20_a=a20_0+!!+a20_1/16/Pi**2"; nl ();
printf "!!!!!!Unitarize"; nl ();
printf "!!!!!!if(fudge_km/=0)then"; nl ();
printf "!!!!!!amp_20=sum(a20)+a20_f+a20_a"; nl ();
printf "!!!!!!if(amp_20/=0)then"; nl ();
printf "!!!!!!amp_20=-a20_a-a20_f-part_r*(sum(a20)-a20(3))+1/(realpart(a20)-a20(3))"; nl ();
printf "!!!!!!end_if"; nl ();
printf "!!!!!!else"; nl ();
printf "!!!!!!amp_20=(1-part_r)*sum(a20)+part_r*a20(3)+a20_f"; nl ();
printf "!!!!!!end_if"; nl ();
printf "!!!!!!amp_20=vev**4/s**2*_amp_20"; nl ();
printf "!!!!!!end_function_da20"; nl ();
nl ();
printf "!!!!!!%sfunction_da22(cc,s,m)result(amp_22)" pure; nl ();
printf "!!!!!!real(kind=default),intent(in)::s"; nl ();
printf "!!!!!!real(kind=default),dimension(1:8),intent(in)::cc"; nl ();
printf "!!!!!!real(kind=default),dimension(1:5),intent(in)::m"; nl ();
printf "!!!!!!complex(kind=default)::a22_0,a22_1,a22_a,a22_r"; nl ();
printf "!!!!!!complex(kind=default),dimension(1:7)::a22"; nl ();
printf "!!!!!!complex(kind=default)::iii,ujj,amp_22"; nl ();

```

```

printf "real(kind=default)_:kappal,kappam,kappat"; nl ();
printf "uuuuuu_ii_=cmplx(0.0,1.0/32.0/Pi,default)"; nl ();
printf "uuuuuu_jj_=s**2/vev**4*ii"; nl ();
printf "uuuuuu_kappal_=cc(8)*((mass(23)**2+mass(24)**2)/m(4)**2-2*mass(23)**2*mass(24))"; nl ();
printf "uuuuuu_kappam_=cc(8)*((mass(23)**4+mass(24)**4)/m(4)**2/(mass(23)**2+mass(24)))"; nl ();
printf "uuuuuuuuuuuuuuuuuuuu_u2*mass(23)**2*mass(24)**2/m(4)**4"; nl ();
printf "uuuuuu_kappat_=cc(8)*mass(23)**2*mass(24)**2/m(4)**4"; nl ();
printf "uuuuuu!!!_Longitudinal"; nl ();
printf "uuuuuu!!!_Scalar_isosinglet"; nl ();
printf "uuuuuu_a22(1)_=_u2.0*cc(1)**2/vev**2*_us2stu(s,m(1))"; nl ();
printf "uuuuuu!!!_Scalar_isoquintet"; nl ();
printf "uuuuuu_a22(2)_=_ucc(2)**2/vev**2*_us2stu(s,m(2))/6.0"; nl ();
printf "uuuuuu!!!_Vector_triplet"; nl ();
printf "uuuuuu_a22(3)_=_u2.0*cc(3)**2*(2*s+m(3)**2)*s2stu(s,m(3))/m(3)**4"; nl ();
printf "uuuuuu!!!_Tensor_isosinglet"; nl ();
printf "uuuuuu_a22(4)_=_ucc(4)**2/vev**2*((1.0+_u6.0*s/m(4)**2)&"; nl ();
printf "uuuuuuuuuuuuuuuuuuuu+6.0*s**2/m(4)**4-2*kappal)*s2stu(s,m(4))/3.0"; nl ();
printf "uuuuuu!!!_Tensor_isoquintet"; nl ();
printf "uuuuuu_a22(5)_=_ucc(5)**2/vev**2/36._u*&"; nl ();
printf "uuuuuuuuuuuuuuuuuuuu((1.+6.*s/m(5)**2+6.*s**2/m(5)**4)_u*&"; nl ();
printf "uuuuuuuuuuuuuuuuuuuu*_us2stu(s,m(5)))"; nl ();
printf "uuuuuuif_(cc(5)/=0)_then"; nl ();
printf "uuuuuu_a22(5)_=_a22(5)_ucc(5)**2/vev**2/60._u*&"; nl ();
printf "uuuuuuuuuuuuuuuuuuuu_s**2/cmplx(s-m(5)**2,s**2/m(5)**3*width_res(w_res,5,wkm(5),m(5)))"; nl ();
printf "uuuuuuend_if"; nl ();
printf "uuuuuu!!!_Transversal"; nl ();
printf "uuuuuu!!!_Tensor_isosinglet"; nl ();
printf "uuuuuu_a22(6)_=_ucc(6)**2/Pi/vev**6*mass(23)**2*mass(24)**2/12._u*(s2stu(s,m(4))"; nl ();
printf "uuuuuuuuuuuuuuuuuuuu*_u(3*(1+2*s/m(4)**2+2*s**2/m(4)**4)+kappat_)"); nl ();
printf "uuuuuu!!!_Mixed"; nl ();
printf "uuuuuu!!!_Tensor_isosinglet"; nl ();
printf "uuuuuu_a22(7)_=_ucc(7)*cc(6)*cc(4)/Pi/vev**4*(mass(23)**2+mass(24)**2)/12._u*(s2"; nl ();
printf "uuuuuuuuuuuuuuuuuuuu*_u(12*s/m(4)**2+12*s**2/m(4)**4+2*kappam_)"); nl ();
printf "uuuuuu!!!_Low_energy_theory_alphas"; nl ();
printf "uuuuuu_a22_0=_u4*(a4+_u2*a5)/15*s**2/vev**4_u"; nl ();
printf "uuuuuu_a22_1=_u(2*log(lam_reg**2/s)/45-_u247/5400.0_default)*s**2/vev**4"; nl ();
printf "uuuuuu_a22_a=_a22_0!!!+_a22_1/16/Pi**2"; nl ();
printf "uuuuuu!!!_Unitarize"; nl ();
printf "uuuuuuif_(fudge_km/=0)_then"; nl ();
printf "uuuuuuuu_AMP_22=_sum(a22)+a22_a"; nl ();
printf "uuuuuuuuif_(AMP_22/=0)_then"; nl ();
printf "uuuuuuuuAMP_22=_u_a22_a_u_part_r*_u(sum(a22)_u_a22(3))_u+1/(realpart(1/AMP_22)); nl ();
printf "uuuuuuuuend_if"; nl ();
printf "uuuuuuelse"; nl ();
printf "uuuuuuuuAMP_22=_u(1-part_r)_u*sum(a22)_u+part_r*_u_a22(3)"; nl ();
printf "uuuuuuend_if"; nl ();
printf "uuuuuuAMP_22=_vev**4/s**2*_uAMP_22"; nl ();
printf "uu_end_function_da22"; nl ();
nl ();
printf "uu%sfunction_dalzz0_s(cc,m,k)_result_(alzz0_s)" pure; nl ();

```

```

printf "%%%%%%%%type(momentum),intent(in)::uk"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:8),intent(in)::cc"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:5),intent(in)::um"; nl ();
printf "%%%%%%%%complex(kind=default)::alzz0_s"; nl ();
printf "%%%%%%%%real(kind=default)::s"; nl ();
printf "%%%%%%%%s=uk*k"; nl ();
printf "%%%%%%%%alzz0_s=2*g**4/coshw**2*((da00(cc,s,m)uk"; nl ();
printf "%%%%%%%%da20(cc,s,m))/24uk"; nl ();
printf "%%%%%%%%(5.)*(da02(cc,s,m)-da22(cc,s,m))/12"; nl ();
printf "%%end_function_dalzz0_s"; nl ();
nl ();
printf "%%sfunction_dalzz0_t(cc,m,k)result(alzz0_t)" pure; nl ();
printf "%%%%%%%%type(momentum),intent(in)::uk"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:8),intent(in)::cc"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:5),intent(in)::um"; nl ();
printf "%%%%%%%%complex(kind=default)::alzz0_t"; nl ();
printf "%%%%%%%%real(kind=default)::s"; nl ();
printf "%%%%%%%%s=uk*k"; nl ();
printf "%%%%%%%%alzz0_t=(5.)*g**4/coshw**2*(da02(cc,s,m)uk"; nl ();
printf "%%%%%%%%da22(cc,s,m))/4"; nl ();
printf "%%end_function_dalzz0_t"; nl ();
nl ();
printf "%%sfunction_dalzz1_s(cc,m,k)result(alzz1_s)" pure; nl ();
printf "%%%%%%%%type(momentum),intent(in)::uk"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:8),intent(in)::cc"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:5),intent(in)::um"; nl ();
printf "%%%%%%%%complex(kind=default)::alzz1_s"; nl ();
printf "%%%%%%%%real(kind=default)::s"; nl ();
printf "%%%%%%%%s=uk*k"; nl ();
printf "%%%%%%%%alzz1_s=ug**4/coshw**2*(da20(cc,s,m)/8uk"; nl ();
printf "%%%%%%%%(5.)*da22(cc,s,m)/4"; nl ();
printf "%%end_function_dalzz1_s"; nl ();
nl ();
printf "%%sfunction_dalzz1_t(cc,m,k)result(alzz1_t)" pure; nl ();
printf "%%%%%%%%type(momentum),intent(in)::uk"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:8),intent(in)::cc"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:5),intent(in)::um"; nl ();
printf "%%%%%%%%complex(kind=default)::alzz1_t"; nl ();
printf "%%%%%%%%real(kind=default)::s"; nl ();
printf "%%%%%%%%s=uk*k"; nl ();
printf "%%%%%%%%alzz1_t=ug**4/coshw**2*(-(3.)*da11(cc,s,m)/8uk"; nl ();
printf "%%%%%%%%+3*(5.)*da22(cc,s,m)/8"; nl ();
printf "%%end_function_dalzz1_t"; nl ();
nl ();
printf "%%sfunction_dalzz1_u(cc,m,k)result(alzz1_u)" pure; nl ();
printf "%%%%%%%%type(momentum),intent(in)::uk"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:8),intent(in)::cc"; nl ();
printf "%%%%%%%%real(kind=default),dimension(1:5),intent(in)::um"; nl ();
printf "%%%%%%%%complex(kind=default)::alzz1_u"; nl ();
printf "%%%%%%%%real(kind=default)::s"; nl ();

```

[illegible]

```

    printf "UUUUUUreal(kind=default),dimension(1:8),intent(in)_:cc"; nl ();
    printf "UUUUUUreal(kind=default),dimension(1:5),intent(in)_:m"; nl ();
    printf "UUUUUUcomplex(kind=default)_:alww2-t"; nl ();
    printf "UUUUUUreal(kind=default)_:s"; nl ();
    printf "UUUUUU s=k*k"; nl ();
    printf "UUUUUUalww2-t=3*(5.)*g**4*da22(cc,s,m)/4"; nl ();
    printf "UUendfunctiondalww2-t"; nl ();
    nl ();
    printf "UU%sfunctiondalz4-s(cc,m,k)result(alz4-s)" pure; nl ();
    printf "UUUUUUtype(momentum),intent(in)_:k"; nl ();
    printf "UUUUUUreal(kind=default),dimension(1:8),intent(in)_:cc"; nl ();
    printf "UUUUUUreal(kind=default),dimension(1:5),intent(in)_:m"; nl ();
    printf "UUUUUUcomplex(kind=default)_:alz4-s"; nl ();
    printf "UUUUUUreal(kind=default)_:s"; nl ();
    printf "UUUUUU s=k*k"; nl ();
    printf "UUUUUUalz4-s=g**4/costhw**4*((da00(cc,s,m)&"; nl ();
    printf "UUUUUUUUUUUUUU+2*da20(cc,s,m))/12&"; nl ();
    printf "UUUUUUUUUUUUUU-(5.)*(da02(cc,s,m)+2*da22(cc,s,m))/6)"; nl ();
    printf "UUendfunctiondalz4-s"; nl ();
    nl ();
    printf "UU@ [<5>";
    printf "UU%sfunctiondalz4-t(cc,m,k)result(alz4-t)" pure; nl ();
    printf "UUUUUUtype(momentum),intent(in)_:k"; nl ();
    printf "UUUUUUreal(kind=default),dimension(1:8),intent(in)_:cc"; nl ();
    printf "UUUUUUreal(kind=default),dimension(1:5),intent(in)_:m"; nl ();
    printf "UUUUUUcomplex(kind=default)_:alz4-t"; nl ();
    printf "UUUUUUreal(kind=default)_:s"; nl ();
    printf "UUUUUU s=k*k"; nl ();
    printf "UUUUUUalz4-t=g**4/costhw**4*(5.)*(da02(cc,s,m)&"; nl ();
    printf "UUUUUUUUUUUUUU+2*da22(cc,s,m))/4"; nl ();
    printf "UUendfunctiondalz4-t"; nl ();
    nl ();
end

```

—16—

PHASE SPACE

16.1 Interface of Phasespace

```

module type T =
  sig
    type momentum

    type  $\alpha$  t
    type  $\alpha$  decay
  end

```

Sort individual decays and complete phasespaces in a canonical order to determine topological equivalence classes.

```

val sort : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha$  t  $\rightarrow \alpha$  t
val sort_decay : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha$  decay  $\rightarrow \alpha$  decay

```

Functionals:

```

val map : ( $\alpha \rightarrow \beta$ )  $\rightarrow \alpha$  t  $\rightarrow \beta$  t
val map_decay : ( $\alpha \rightarrow \beta$ )  $\rightarrow \alpha$  decay  $\rightarrow \beta$  decay

val eval : ( $\alpha \rightarrow \beta$ )  $\rightarrow (\alpha \rightarrow \beta) \rightarrow (\alpha \rightarrow \beta \rightarrow \beta \rightarrow \beta) \rightarrow \alpha$  t  $\rightarrow \beta$  t
val eval_decay : ( $\alpha \rightarrow \beta$ )  $\rightarrow (\alpha \rightarrow \beta \rightarrow \beta \rightarrow \beta) \rightarrow \alpha$  decay  $\rightarrow \beta$  decay

```

of_momenta *f1 f2 plist* constructs the phasespace parameterization for a process $f_1 f_2 \rightarrow X$ with flavor decoration from pairs of outgoing momenta and flavors *plist* and initial flavors *f1* and *f2*

```

val of_momenta :  $\alpha \rightarrow \alpha \rightarrow (\text{momentum} \times \alpha)$  list  $\rightarrow (\text{momentum} \times \alpha)$  t
val decay_of_momenta : ( $\text{momentum} \times \alpha$ ) list  $\rightarrow (\text{momentum} \times \alpha)$  decay

exception Duplicate of momentum
exception Unordered of momentum
exception Incomplete of momentum

```

end

```

module Make (M : Momentum.T) : T with type momentum = M.t

```


16.2 Implementation of *Phasespace*

16.2.1 Tools

These are candidates for *ThoList* and not specific to phase space.

```
let rec first_match' mismatch f = function
| [] → None
| x :: rest →
  if f x then
    Some (x, List.rev_append mismatch rest)
  else
    first_match' (x :: mismatch) f rest
```

Returns $(x, X \setminus \{x\})$ if $\exists x \in X : f(x)$.

```
let first_match f l = first_match' [] f l
```

```
let rec first_pair' mismatch1 f l1 l2 =
  match l1 with
  | [] → None
  | x1 :: rest1 →
    begin match first_match (f x1) l2 with
    | None → first_pair' (x1 :: mismatch1) f rest1 l2
    | Some (x2, rest2) →
      Some ((x1, x2), (List.rev_append mismatch1 rest1, rest2))
    end
```

Returns $((x, y), (X \setminus \{x\}, Y \setminus \{y\}))$ if $\exists x \in X : \exists y \in Y : f(x, y)$.

```
let first_pair f l1 l2 = first_pair' [] f l1 l2
```

16.2.2 Phase Space Parameterization Trees

```
module type T =
sig
  type momentum
  type  $\alpha$  t
  type  $\alpha$  decay
  val sort : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha$  t  $\rightarrow \alpha$  t
  val sort_decay : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha$  decay  $\rightarrow \alpha$  decay
  val map : ( $\alpha \rightarrow \beta$ )  $\rightarrow \alpha$  t  $\rightarrow \beta$  t
  val map_decay : ( $\alpha \rightarrow \beta$ )  $\rightarrow \alpha$  decay  $\rightarrow \beta$  decay
  val eval : ( $\alpha \rightarrow \beta$ )  $\rightarrow (\alpha \rightarrow \beta) \rightarrow (\alpha \rightarrow \beta \rightarrow \beta \rightarrow \beta) \rightarrow \alpha$  t  $\rightarrow \beta$  t
  val eval_decay : ( $\alpha \rightarrow \beta$ )  $\rightarrow (\alpha \rightarrow \beta \rightarrow \beta \rightarrow \beta) \rightarrow \alpha$  decay  $\rightarrow \beta$  decay
  val of_momenta :  $\alpha \rightarrow \alpha \rightarrow (\text{momentum} \times \alpha)$  list  $\rightarrow (\text{momentum} \times \alpha)$  t
  val decay_of_momenta : ( $\text{momentum} \times \alpha$ ) list  $\rightarrow (\text{momentum} \times \alpha)$  decay
  exception Duplicate of momentum
  exception Unordered of momentum
  exception Incomplete of momentum
```

```

end

module Make (M : Momentum.T) =
struct
  type momentum = M.t

```



Finally, we came back to binary trees ...

Cascade Decays

```

type  $\alpha$  decay =
| Leaf of  $\alpha$ 
| Branch of  $\alpha \times \alpha$  decay  $\times \alpha$  decay

```



Trees of type $(\text{momentum} \times \alpha \text{ option}) \text{ decay}$ can be build easily and mapped to $(\text{momentum} \times \alpha) \text{ decay}$ later, once all the α slots are filled. A more elegant functor operating on $\beta \text{ decay}$ directly (with *Momentum* style functions defined for β) would not allow holes in the $\beta \text{ decay}$ during the construction.

```

let label = function
| Leaf p → p
| Branch (p, -, -) → p

let rec sort_decay cmp = function
| Leaf _ as l → l
| Branch (p, d1, d2) →
  let d1' = sort_decay cmp d1
  and d2' = sort_decay cmp d2 in
  if cmp (label d1') (label d2') ≤ 0 then
    Branch (p, d1', d2')
  else
    Branch (p, d2', d1')

let rec map_decay f = function
| Leaf p → Leaf (f p)
| Branch (p, d1, d2) → Branch (f p, map_decay f d1, map_decay f d2)

let rec eval_decay fl fb = function
| Leaf p → Leaf (fl p)
| Branch (p, d1, d2) →
  let d1' = eval_decay fl fb d1
  and d2' = eval_decay fl fb d2 in
  Branch (fb p (label d1') (label d2'), d1', d2')

```

Assuming that $p > p_D \vee p = p_D \vee p < p_D$, where p_D is the overall momentum of a decay tree D , we can add p to D at the top or somewhere in the middle. Note that ' $<$ ' is not a total ordering and the operation can fail (raise exceptions) if the set of momenta does not correspond to a tree. Also note that a momentum

can already be present without flavor as a complement in a branching entered earlier.

```

exception Duplicate of momentum
exception Unordered of momentum

let rec embed_in_decay (p, f as pf) = function
| Leaf (p', f' as pf') as d' →
  if M.less p' p then
    Branch ((p, Some f), d', Leaf (M.sub p p', None))
  else if M.less p p' then
    Branch (pf', Leaf (p, Some f), Leaf (M.sub p' p, None))
  else if p = p' then
    begin match f' with
    | None → Leaf (p, Some f)
    | Some _ → raise (Duplicate p)
    end
  else
    raise (Unordered p)
| Branch ((p', f' as pf'), d1, d2) as d' →
  let p1, _ = label d1
  and p2, _ = label d2 in
  if M.less p' p then
    Branch ((p, Some f), d', Leaf (M.sub p p', None))
  else if M.lesseq p p1 then
    Branch (pf', embed_in_decay pf d1, d2)
  else if M.lesseq p p2 then
    Branch (pf', d1, embed_in_decay pf d2)
  else if p = p' then
    begin match f' with
    | None → Branch ((p, Some f), d1, d2)
    | Some _ → raise (Duplicate p)
    end
  else
    raise (Unordered p)

```



Note that both *embed_in_decay* and *embed_in_decays* below do *not* commute, and should process ‘bigger’ momenta first, because disjoint sub-momenta will create disjoint subtrees in the latter and raise exceptions in the former.

```

exception Incomplete of momentum

let finalize1 = function
| p, Some f → (p, f)
| p, None → raise (Incomplete p)

let finalize_decay t = map_decay finalize1 t

```

Process the momenta starting in with the highest *M.rank*:

```

let sort_momenta plist =
  List.sort (fun (p1, _) (p2, _) → M.compare p1 p2) plist

```




Figure 16.1: Phasespace parameterization for $2 \rightarrow n$ scattering by a sequence of cascade decays.

```
let decay_of_momenta plist =
  match sort_momenta plist with
  | (p, f) :: rest →
    finalize_decay (List.fold_right embed_in_decay rest (Leaf (p, Some f)))
  | [] → invalid_arg "Phasespace.decay_of_momenta:␣empty"
```

$2 \rightarrow n$ Scattering

A general $2 \rightarrow n$ scattering process can be parameterized by a sequence of cascade decays. The most symmetric representation is a little bit redundant and enters each t -channel momentum twice.

```
type  $\alpha$  t = ( $\alpha \times \alpha$  decay  $\times \alpha$ ) list
```

⚠ let *topology* = *map snd* has type $(\text{momentum} \times \alpha) t \rightarrow \alpha t$ and can be used to define topological equivalence classes “up to permutations of momenta,” which are useful for calculating Whizard “groves”¹ [11].

```
let sort cmp = List.map (fun (l, d, r) → (l, sort_decay cmp d, r))
let map f = List.map (fun (l, d, r) → (f l, map_decay f d, f r))
let eval ft fl fb = List.map (fun (l, d, r) → (ft l, eval_decay fl fb d, ft r))
```

Find a tree with a defined ordering relation with respect to p or create a new one at the end of the list.

```
let rec embed_in_decays (p, f as pf) = function
| [] → [Leaf (p, Some f)]
| d' :: rest →
  let p', _ = label d' in
```

¹Not to be confused with gauge invariant classes of Feynman diagrams [12].

```

if  $M.lesseq\ p'\ p \vee M.less\ p\ p'$  then
   $embed\_in\_decay\ pf\ d' :: rest$ 
else
   $d' :: embed\_in\_decays\ pf\ rest$ 

```

Collecting Ingredients

```

type  $\alpha\ unfinished\_decays =$ 
  {  $n : int$ ;
     $t\_channel : (momentum \times \alpha\ option)\ list$ ;
     $decays : (momentum \times \alpha\ option)\ decay\ list$  }

let  $empty\ n = \{ n = n; t\_channel = []; decays = [] \}$ 

let  $insert\_in\_unfinished\_decays\ (p, f\ as\ pf)\ d =$ 
  if  $M.Scattering.spacelike\ p$  then
    {  $d\ with\ t\_channel = (p, Some\ f) :: d.t\_channel$  }
  else
    {  $d\ with\ decays = embed\_in\_decays\ pf\ d.decays$  }

let  $flip\_incoming\ plist =$ 
   $List.map\ (\fun\ (p', f') \rightarrow (M.Scattering.flip\_s\_channel\_in\ p', f'))\ plist$ 

let  $unfinished\_decays\_of\_momenta\ n\ f2\ p =$ 
   $List.fold\_right\ insert\_in\_unfinished\_decays$ 
   $(sort\_momenta\ (flip\_incoming\ ((M.of\_ints\ n\ [2], f2) :: p)))\ (empty\ n)$ 

```

Assembling Ingredients

```

let  $sort3\ compare\ x\ y\ z =$ 
  let  $a = [x; y; z]$  in
   $Array.sort\ compare\ a$ ;
   $(a.(0), a.(1), a.(2))$ 

```

Take advantage of the fact that sorting with $M.compare$ sorts with *rising* values of $M.rank$:

```

let  $allows\_momentum\_fusion\ (p, -)\ (p1, -)\ (p2, -) =$ 
  let  $p2', p1', p' = sort3\ M.compare\ p\ p1\ p2$  in
  match  $M.try\_fusion\ p'\ p1'\ p2'$  with
  |  $Some\ _ \rightarrow true$ 
  |  $None \rightarrow false$ 

let  $allows\_fusion\ p1\ p2\ d = allows\_momentum\_fusion\ (label\ d)\ p1\ p2$ 

let rec  $thread\_unfinished\_decays'\ p\ acc\ tlist\ dlist =$ 
  match  $first\_pair\ (allows\_fusion\ p)\ tlist\ dlist$  with
  |  $None \rightarrow (p, acc, tlist, dlist)$ 
  |  $Some\ ((t, -\ as\ td), (tlist', dlist')) \rightarrow$ 
     $thread\_unfinished\_decays'\ t\ (td :: acc)\ tlist'\ dlist'$ 

```

```

let thread_unfinished_decays p c =
  match thread_unfinished_decays' p [] c.t_channel c.decays with
  | -, pairs, [], [] → pairs
  | - → failwith "thread_unfinished_decays"

let rec combine_decays = function
| [] → []
| ((t, f as tf), d) :: rest →
  let p, _ = label d in
  begin match M.try_sub t p with
  | Some p' → (tf, d, (p', f)) :: combine_decays rest
  | None → (tf, d, (M.sub (M.neg t) p, f)) :: combine_decays rest
  end

let finalize t = map finalize1 t

let of_momenta f1 f2 = function
| (p, _) :: _ as l →
  let n = M.dim p in
  finalize (combine_decays
    (thread_unfinished_decays (M.of_ints n [1], Some f1)
      (unfinished_decays_of_momenta n f2 l)))
| [] → []

```

Diagnostics

```

let p_to_string p =
  String.concat "" (List.map string_of_int (M.to_ints (M.abs p)))

let rec to_string1 = function
| Leaf p → "(" ^ p_to_string p ^ ")"
| Branch (_, d1, d2) → "(" ^ to_string1 d1 ^ to_string1 d2 ^ ")"

let to_string ps =
  String.concat "/"
  (List.map (fun (p1, d, p2) →
    p_to_string p1 ^ to_string1 d ^ p_to_string p2) ps)

```

Examples

```

let try_thread_unfinished_decays p c =
  thread_unfinished_decays' p [] c.t_channel c.decays

let try_of_momenta f = function
| (p, _) :: _ as l →
  let n = M.dim p in
  try_thread_unfinished_decays
    (M.of_ints n [1], None) (unfinished_decays_of_momenta n f l)
| [] → invalid_arg "try_of_momenta"

end

```

—17—

WHIZARD

Talk to [11].

17.1 Interface of Whizard

```

module type T =
  sig
    type t
    type amplitude
    val trees : amplitude → t
    val merge : t → t
    val write : out_channel → string → t → unit
  end

module Make (FM : Fusion.Maker) (P : Momentum.T)
  (PW : Momentum.Whizard with type t = P.t) (M : Model.T) :
  T with type amplitude = FM(P)(M).amplitude

val write_interface : out_channel → string list → unit
val write_makefile : out_channel → α → unit
val write_makefile_processes : out_channel → string list → unit

```

17.2 Implementation of Whizard

```

let rcs = RCS.parse "Whizard" ["Whizard_Interface"]
  { RCS.revision = "$Revision: 4538$";
    RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
    RCS.author = "$Author: jr-reuter$";
    RCS.source
      = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg";
  }

open Printf

module type T =
  sig
    type t
    type amplitude
  end

```

```

    val trees : amplitude → t
    val merge : t → t
    val write : out_channel → string → t → unit
end

module Make (FM : Fusion.Maker) (P : Momentum.T)
  (PW : Momentum.Whizard with type t = P.t) (M : Model.T) =
struct
  module F = FM(P)(M)

  type tree = (P.t × F.flavor list) list

  module Poles = Map.Make
    (struct
      type t = int × int
      let compare (s1, t1) (s2, t2) =
        let c = compare s2 s1 in
        if c ≠ 0 then
          c
        else
          compare t1 t2
    end)

  let add_tree maps tree trees =
    Poles.add maps
      (try tree :: (Poles.find maps trees) with Not_found → [tree]) trees

  type t =
    { in1 : F.flavor;
      in2 : F.flavor;
      out : F.flavor list;
      trees : tree list Poles.t }

  type amplitude = F.amplitude

```

17.2.1 Building Trees

A singularity is to be mapped if it is timelike and not the overall *s*-channel.

```

let timelike_map c = P.Scattering.timelike c ∧ ¬ (P.Scattering.s_channel c)

let count_maps n clist =
  List.fold_left (fun (s, t as cnt) (c, _) →
    if timelike_map c then
      (succ s, t)
    else if P.Scattering.spacelike c then
      (s, succ t)
    else
      cnt) (0, 0) clist

let poles_to_whizard n trees poles =
  let tree = List.map (fun wf →
    (P.Scattering.flip_s_channel_in (F.momentum wf), [F.flavor wf])) poles in

```



```
add_tree (count_maps n tree) tree trees
```



I must reinstate the *conjugate* eventually!

```
let trees a =
  match F.externals a with
  | in1 :: in2 :: out →
    let n = List.length out + 2 in
    { in1 = F.flavor in1;
      in2 = F.flavor in2;
      out = List.map (fun f → (* M.conjugate *) (F.flavor f)) out;
      trees = List.fold_left
        (poles_to_whizard n) Poles.empty (F.poles a) }
  | _ → invalid_arg "Whizard().trees"
```

17.2.2 Merging Homomorphic Trees

```
module Pole_Map =
  Map.Make (struct type t = P.t list let compare = compare end)
module Flavor_Set =
  Set.Make (struct type t = F.flavor let compare = compare end)

let add_flavors flist fset =
  List.fold_right Flavor_Set.add flist fset

let set_of_flavors flist =
  List.fold_right Flavor_Set.add flist Flavor_Set.empty

let pack_tree map t =
  let c, f =
    List.split (List.sort (fun (c1, _) (c2, _) →
      compare (PW.of_momentum c2) (PW.of_momentum c1))) t) in
  let f' =
    try
      List.map2 add_flavors f (Pole_Map.find c map)
    with
    | Not_found → List.map set_of_flavors f in
  Pole_Map.add c f' map

let pack_map trees = List.fold_left pack_tree Pole_Map.empty trees

let merge_sets clist flist =
  List.map2 (fun c f → (c, Flavor_Set.elements f)) clist flist

let unpack_map map =
  Pole_Map.fold (fun c f l → (merge_sets c f) :: l) map []
```

If a singularity is to be mapped (i.e. if it is timelike and not the overall *s*-channel), expand merged particles again:

```
let unfold1 (c, f) =
```

```

if timelike_map c then
  List.map (fun f' → (c, [f'])) f
else
  [(c, f)]
let unfold_tree tree = Product.list (fun x → x) (List.map unfold1 tree)
let unfold trees = ThoList.flatMap unfold_tree trees
let merge t =
  { t with trees = Poles.map
    (fun t' → unfold (unpack_map (pack_map t')) t.trees }

```

17.2.3 Printing Trees

```

let flavors_to_string f =
  String.concat "/" (List.map M.flavor_to_string f)
let whizard_tree t =
  "tree_" ^
  (String.concat "_" (List.rev_map (fun (c, _) →
    (string_of_int (PW.of_momentum c))) t)) ^
  "_!" ^
  (String.concat ",_" (List.rev_map (fun (_, f) → flavors_to_string f) t))
let whizard_tree_debug t =
  "tree_" ^
  (String.concat "_" (List.rev_map (fun (c, _) →
    ("[" ^ (String.concat "+" (List.map string_of_int (P.to_ints c))) ^ "]" )
    (List.sort (fun (t1, _) (t2, _) →
      let c =
        compare
          (List.length (P.to_ints t2))
          (List.length (P.to_ints t1)) in
      if c ≠ 0 then
        c
      else
        compare t1 t2) t))) ^
    "!" ^
  (String.concat ",_" (List.rev_map (fun (_, f) → flavors_to_string f) t))
let format_maps = function
| (0, 0) → "neither_mapped_timelike_nor_spacelike_poles"
| (0, 1) → "no_mapped_timelike_poles_one_spacelike_pole"
| (0, n) → "no_mapped_timelike_poles_" ^
  string_of_int n ^ "spacelike_poles"
| (1, 0) → "one_mapped_timelike_pole_no_spacelike_pole"
| (1, 1) → "one_mapped_timelike_and_spacelike_pole_each"
| (1, n) → "one_mapped_timelike_and_" ^
  string_of_int n ^ "spacelike_poles"
| (n, 0) → string_of_int n ^

```

```

        "mapped_timelike_poles_and_no_spacelike_pole"
    | (n, 1) → string_of_int n ^
        "mapped_timelike_poles_and_one_spacelike_pole"
    | (n, n') → string_of_int n ^ "mapped_timelike_and_" ^
        string_of_int n' ^ "spacelike_poles"

let format_flavor f =
  match flavors_to_string f with
  | "d" → "d" | "dbar" → "D"
  | "u" → "u" | "ubar" → "U"
  | "s" → "s" | "sbar" → "S"
  | "c" → "c" | "cbar" → "C"
  | "b" → "b" | "bbar" → "B"
  | "t" → "t" | "tbar" → "T"
  | "e-" → "e1" | "e+" → "E1"
  | "nue" → "n1" | "nuebar" → "N1"
  | "mu-" → "e2" | "mu+" → "E2"
  | "numu" → "n2" | "numubar" → "N2"
  | "tau-" → "e3" | "tau+" → "E3"
  | "nutau" → "n3" | "nutaubar" → "N3"
  | "g" → "G" | "A" → "A" | "Z" → "Z"
  | "W+" → "W+" | "W-" → "W-"
  | "H" → "H"
  | s → s ^ "(not_translated)"

module Mappable =
  Set.Make (struct type t = string let compare = compare end)
let mappable =
  List.fold_right Mappable.add
    [ "T"; "Z"; "W+"; "W-"; "H" ] Mappable.empty

let analyze_tree ch t =
  List.iter (fun (c, f) →
    let f' = format_flavor f
    and c' = PW.of_momentum c in
    if P.Scattering.timelike c then begin
      if P.Scattering.s_channel c then
        fprintf ch "!!!!!!_overall_s-channel_%d_%s_not_mapped\n" c' f'
      else if Mappable.mem f' mappable then
        fprintf ch "!!!!!!map_%d_s-channel_%s\n" c' f'
      else
        fprintf ch
          "!!!!!!_%d_s-channel_%s_can't_be_mapped_by_whizard\n"
          c' f'
    end else
      fprintf ch "!!!!!!_t-channel_%d_%s_not_mapped\n" c' f') t

let write ch pid t =
  failwith "Whizard.Make().write:incomplete"
  fprintf ch "process_%s\n" pid;
  Poles.iter (fun maps ds →
    fprintf ch "\n!!!!!!_%d_times_%s:\n"

```

$i \times)$
en

17.2.4 Process Dispatcher

```

let arguments = function
| [] → (" ", " ")
| args →
    let arg_list = String.concat ",_" (List.map snd args) in
    (arg_list, ",_" ^ arg_list)

let import_prefix ch pid name =
    fprintf ch "use%s,only:_%s-_%s=>_%s!NODEP!\n"
        pid pid name name

let declare_argument ch (arg_type, arg) =
    fprintf ch "use%s,intent(in):_%s\n" arg_type arg

let call_function ch pid result name args =
    fprintf ch "case_(pr_%s)\n" pid;
    fprintf ch "use%s-_%s-_%s(%s)\n" result pid name args

let default_function ch result default =
    fprintf ch "case_default\n";
    fprintf ch "usecall_invalid_process_(pid)\n";
    fprintf ch "use%s\n" result default

let call_subroutine ch pid name args =
    fprintf ch "case_(pr_%s)\n" pid;
    fprintf ch "usecall%s-_%s-_%s(%s)\n" pid name args

let default_subroutine ch =
    fprintf ch "case_default\n";
    fprintf ch "usecall_invalid_process_(pid)\n"

let write_interface_subroutine ch wrapper name args processes =
    let arg_list, arg_list' = arguments args in
    fprintf ch "subroutine_%s_(pid%s)\n" wrapper arg_list';
    List.iter (fun p → import_prefix ch p name) processes;
    List.iter (declare_argument ch) (("character(len=*)", "pid") :: args);
    fprintf ch "useselect_case_(pid)\n";
    List.iter (fun p → call_subroutine ch p name arg_list) processes;

```

```

    default_subroutine ch;
    fprintf ch "_____end_select\n";
    fprintf ch "____end_subroutine_%s\n" wrapper

let write_interface_function ch wrapper name
    (result_type, result, default) args processes =
    let arg_list, arg_list' = arguments args in
    fprintf ch "____function_%s_(pid%s)_result_(%s)\n" wrapper arg_list' result;
    List.iter (fun p → import_prefix ch p name) processes;
    List.iter (declare_argument ch) (("character(len=*)", "pid") :: args);
    fprintf ch "_____s_:_%s\n" result_type result;
    fprintf ch "_____select_case_(pid)\n";
    List.iter (fun p → call_function ch p result name arg_list) processes;
    default_function ch result default;
    fprintf ch "_____end_select\n";
    fprintf ch "____end_function_%s\n" wrapper

let write_other_interface_functions ch =
    fprintf ch "____subroutine_invalid_process_(pid)\n";
    fprintf ch "_____character(len=*)_intent(in):_pid\n";
    fprintf ch "_____print_*,_\"PANIC:\"";
    fprintf ch "____process_\'"/trim(pid)/\'_not_available!\n";
    fprintf ch "____end_subroutine_invalid_process\n";
    fprintf ch "____function_n_tot_(pid)_result_(n)\n";
    fprintf ch "_____character(len=*)_intent(in):_pid\n";
    fprintf ch "_____integer:_n\n";
    fprintf ch "_____n=_n_in(pid)+_n_out(pid)\n";
    fprintf ch "____end_function_n_tot\n"

let write_other_declarations ch =
    fprintf ch "____public:_n_in,_n_out,_n_tot,_pdg_code\n";
    fprintf ch "____public:_allow_helicities\n";
    fprintf ch "____public:_create,_destroy\n";
    fprintf ch "____public:_set_const,_sqme\n";
    fprintf ch "____interface_create\n";
    fprintf ch "_____module_procedure_process_create\n";
    fprintf ch "____end_interface\n";
    fprintf ch "____interface_destroy\n";
    fprintf ch "_____module_procedure_process_destroy\n";
    fprintf ch "____end_interface\n";
    fprintf ch "____interface_set_const\n";
    fprintf ch "_____module_procedure_process_set_const\n";
    fprintf ch "____end_interface\n";
    fprintf ch "____interface_sqme\n";
    fprintf ch "_____module_procedure_process_sqme\n";
    fprintf ch "____end_interface\n"

let write_interface ch names =
    fprintf ch "module_process_interface\n";
    fprintf ch "____use_kinds,_only:_default____!NODEP!\n";
    fprintf ch "____use_parameters,_only:_parameter_set\n";
    fprintf ch "____implicit_none\n";

```

```

fprintf ch "private\n";
List.iter (fun p →
  fprintf ch
    "character(len=*),parameter,public::pr_%s=\"%s\"\n" p p)
  names;
write_other_declarations ch;
fprintf ch "contains\n";
write_interface_function ch "n_in" "n_in" ("integer", "n", "0") [] names;
write_interface_function ch "n_out" "n_out" ("integer", "n", "0") [] names;
write_interface_function ch "pdg_code" "pdg_code"
  ("integer", "n", "0") [ "integer", "i" ] names;
write_interface_function ch "allow_helicities" "allow_helicities"
  ("logical", "yorn", ".false.") [] names;
write_interface_subroutine ch "process_create" "create" [] names;
write_interface_subroutine ch "process_destroy" "destroy" [] names;
write_interface_subroutine ch "process_set_const" "set_const"
  [ "type(parameter_set)", "par" ] names;
write_interface_function ch "process_sqme" "sqme"
  ("real(kind=default)", "sqme", "0")
  [ "real(kind=default),dimension(0:,:)", "p";
    "integer,dimension(:),optional", "h" ] names;
write_other_interface_functions ch;
fprintf ch "end_module_process_interface\n"

```

17.2.5 Makefile

```

let write_makefile ch names =
  fprintf ch "KINDS=@./@KINDS@\n";
  fprintf ch "HELAS=@./@HELAS@\n";
  fprintf ch "F90=@F90@\n";
  fprintf ch "F90FLAGS=@F90FLAGS@\n";
  fprintf ch "F90INCL=@-I$(KINDS)-I$(HELAS)\n";
  fprintf ch "F90COMMON=@omega_bundle_whizard.f90";
  fprintf ch "@file_utils.f90_process_interface.f90\n";
  fprintf ch "include_Makefile.processes\n";
  fprintf ch "F90SRC=@$(F90COMMON)$(F90PROCESSES)\n";
  fprintf ch "OBJ=@$(F90SRC:.f90=.o)\n";
  fprintf ch "MOD=@$(F90SRC:.f90=.mod)\n";
  fprintf ch "archive:@processes.a\n";
  fprintf ch "processes.a:@$(OBJ)\n";
  fprintf ch "\t$(AR) r @$(OBJ)\n";
  fprintf ch "\t@RANLIB @$(OBJ)\n";
  fprintf ch "clean:\n";
  fprintf ch "\trm -f @$(OBJ)\n";
  fprintf ch "realclean:\n";
  fprintf ch "\trm -f @processes.a\n";
  fprintf ch "parameters.o:@file_utils.o\n";
  fprintf ch "omega_bundle_whizard.o:@parameters.o\n";

```

```

fprintf ch "process_interface.o:\parameters.o\n";
fprintf ch "%%.o:%%.f90$(KINDS)/kinds.f90\n";
fprintf ch "\t$(F90)$(F90FLAGS)$(F90INCL)-c<\n"

let write_makefile_processes ch names =
  fprintf ch "F90PROCESSES=";
  List.iter (fun f → fprintf ch "\\\n%%s.f90" f) names;
  fprintf ch "\n";
  List.iter (fun f →
    fprintf ch "%s.o:\omega_bundle_whizard.o\parameters.o\n" f;
    fprintf ch "process_interface.o:%%s.o\n" f) names

```

—18—

APPLICATIONS

18.1 *Sample*

18.2 *Interface of Omega*

```
module type T =  
  sig  
    val main : unit → unit
```



This used to be only intended for debugging O’Giga, but might live longer
...

```
  type flavor  
  val diagrams : flavor → flavor → flavor list →  
    ((flavor × Momentum.Default.t) ×  
     (flavor × Momentum.Default.t,  
      flavor × Momentum.Default.t) Tree.t) list  
end  
  
module Make (FM : Fusion.Maker) (TM : Target.Maker) (M : Model.T) :  
  T with type flavor = M.flavor
```

18.3 *Implementation of Omega*

```
module P = Momentum.Default  
module P_Whizard = Momentum.DefaultW  
  
module type T =  
  sig  
    val main : unit → unit  
    type flavor  
    val diagrams : flavor → flavor → flavor list →  
      ((flavor × Momentum.Default.t) ×  
       (flavor × Momentum.Default.t,  
        flavor × Momentum.Default.t) Tree.t) list  
  end
```



```
module Make (Fusion_Maker : Fusion.Maker) (Target_Maker : Target.Maker) (M : Model.T) =
  struct
```



max_lines = 8 is plenty, since amplitudes with 8 gluons still take several *days* to construct.

```
  module CM = Colorize.It(M)
  type flavor = M.flavor
  module Proc = Process.Make(M)
```



NB: this causes the constant initializers in *Fusion_Maker* more than once. Such side effects must be avoided if the initializers involve expensive computations. *Relying on the fact that the functor will be called only once is not a good idea!*

```
  module F = Fusion_Maker(P)(M)
  module CF = Fusion.Multi(Fusion_Maker)(P)(M)
  module T = Target_Maker(Fusion_Maker)(P)(M)
  module W = Whizard.Make(Fusion_Maker)(P)(P_Whizard)(M)
  module C = Cascade.Make(M)(P)

  let version () =
    List.iter (fun s → prerr_endline ("RCS:␣" ^ s))
      (ThoList.flatmap RCS.summary (CM.rcs :: T.rcs_list @ F.rcs_list))

  let debug (str, descr, opt, var) =
    [ "-warning:" ^ str, Arg.Unit (fun () → var := (opt, false) :: !var),
      "check␣" ^ descr ^ "␣and␣print␣warning␣on␣error";
      "-error:" ^ str, Arg.Unit (fun () → var := (opt, true) :: !var),
      "check␣" ^ descr ^ "␣and␣terminate␣on␣error" ]

  let rec include_goldstones = function
    | [] → false
    | (T.Gauge, _) :: _ → true
    | _ :: rest → include_goldstones rest

  let p2s p =
    if p ≥ 0 ∧ p ≤ 9 then
      string_of_int p
    else if p ≤ 36 then
      String.make 1 (Char.chr (Char.code 'A' + p - 10))
    else
      "_"

  let format_p wf =
    String.concat "" (List.map p2s (F.momentum_list wf))

  let variable wf = M.flavor_to_string (F.flavor_sans_color wf) ^ "[" ^ format_p wf ^ "]"
  let variable' wf = M.flavor_symbol (F.flavor_sans_color wf) ^ "[" ^ format_p wf ^ "]"
```

```

let read_lines_rev file =
  let ic = open_in file in
  let rev_lines = ref [] in
  let rec slurp () =
    rev_lines := input_line ic :: !rev_lines;
    slurp () in
  try
    slurp ()
  with
  | End_of_file →
    close_in ic;
    !rev_lines

let read_lines file =
  List.rev (read_lines_rev file)

type cache_mode =
  | Cache_Default
  | Cache_Initialize of string

let cache_option =
  ref Cache_Default

let unphysical_polarization = ref None

```

18.3.1 Main Program

```

let main () =
  let usage =
    "usage:_" ^ Sys.argv.(0) ^
    "_"[options]_" " ^ String.concat "|" (List.map M.flavor_to_string
      (ThoList.flatmap snd (M.external_flavors ()))) ^ " "

  and rev_scatterings = ref []
  and rev_decays = ref []
  and cascades = ref []
  and checks = ref []
  and output_file = ref None
  and print_forest = ref false
  and template = ref false
  and feynmf = ref None
  and feynmf_tex = ref false
  and quiet = ref false
  and write = ref true
  and params = ref false
  and poles = ref false
  and dag_out = ref None
  and dag0_out = ref None in
  Arg.parse
    (Options.cmdline "-target:" T.options @
     Options.cmdline "-model:" M.options @

```

```

Options.cmdline "-fusion:" CF.options @
ThoList.flatmap debug
  [ "", "arguments", T.All, checks;
    "a", "#_of_input_arguments", T.Arguments, checks;
    "m", "input_momenta", T.Momenta, checks;
    "g", "internal_Ward_identities", T.Gauge, checks] @
[ ("-o", Arg.String (fun s → output_file := Some s),
  "write_to_given_file_instead_of_dev/stdout");
  ("-scatter", Arg.String (fun s → rev_scatterings := s :: !rev_scatterings),
  "in1_in2->out1_out2...");
  ("-scatter_file",
  Arg.String (fun s → rev_scatterings := read_lines_rev s @ !rev_scatterings),
  "in1_in2->out1_out2...");
  ("-decay", Arg.String (fun s → rev_decays := s :: !rev_decays),
  "in->out1_out2...");
  ("-decay_file", Arg.String (fun s → rev_decays := read_lines_rev s @ !rev_decays),
  "in->out1_out2...");
  ("-cascade", Arg.String (fun s → cascades := s :: !cascades),
  "select_diagrams");
  ("-initialize", Arg.String (fun s → cache_option := Cache_Initialize s),
  "precompute_large_lookup_table(s) and store them in the directory");
  ("-unphysical", Arg.Int (fun i → unphysical_polarization := Some i),
  "select_unphysical_polarization_state_for_one_particle_to_test_Ward_Identities");
  ("-template", Arg.Set template,
  "write_a_template_for_using_handwritten_amplitudes_with_WHIZARD");
  ("-forest", Arg.Set print_forest, "Diagrammatic_expansion");
  ("-feynmf", Arg.String (fun s → feynmf := Some s), "print_feynmf/mp_output");
  ("-feynmf_tex", Arg.Set feynmf_tex, "print_feynmf/mp/LaTeX_output");
  ("-revision", Arg.Unit version, "print_revision_control_information");
  ("-quiet", Arg.Set quiet, "don't_print_a_summary");
  ("-summary", Arg.Clear write, "print_only_a_summary");
  ("-params", Arg.Set params, "print_the_model_parameters");
  ("-poles", Arg.Set poles, "print_the_Monte_Carlo_poles");
  ("-dag", Arg.String (fun s → dag_out := Some s), "print_minimal_DAG");
  ("-full_dag", Arg.String (fun s → dag0_out := Some s), "print_complete_DAG"))]
(fun _ → prerr_endline usage; exit 1)
usage;

let cmdline =
  String.concat " " (List.map ThoString.quote (Array.to_list Sys.argv)) in

let output_channel =
  match !output_file with
  | None → stdout
  | Some name → open_out name in

let processes =
  try
    ThoList.uniq
      (List.sort compare
        (match List.rev !rev_scatterings, List.rev !rev_decays with
         | [], [] → []

```

```

| scatterings, [] →
  Proc.expand_scatterings (List.map Proc.parse_scattering scatterings)
| [], decays →
  Proc.expand_decays (List.map Proc.parse_decay decays)
| scatterings, decays →
  invalid_arg "mixed_scattering_and_decay!")
with
| Invalid_argument s →
  begin
    Printf.eprintf "0'Mega: invalid_process_specification: %s!\n" s;
    flush stderr;
    []
  end in

```



This is still crude. Eventually, we want to catch *all* exceptions and write an empty (but compilable) amplitude unless one of the special options is selected.

```

begin match processes, !cache_option, !params with
| [], Cache_Initialize dir, false →
  F.initialize_cache dir;
  exit 0
| -, -, true →
  T.parameters_to_channel output_channel;
  exit 0
| [], -, false →
  T.amplitudes_to_channel cmdline output_channel !checks CF.empty;
  exit 0
| -, -, false →
  let selectors =
    let fin, fout = List.hd processes in
    C.to_selectors (C.of_string_list (List.length fin + List.length fout) !cascades) in
  let amplitudes =
    try
      begin match F.check_charges () with
      | [] → ()
      | violators →
          let violator_strings =
            String.concat ", "
              (List.map
                (fun flist →
                  "(" ^ String.concat ", " (List.map M.flavor_to_string flist) ^ ")")
                violators) in
          failwith ("charge_violating_vertices: " ^ violator_strings)
        end;
      CF.amplitudes (include_goldstones !checks) !unphysical_polarization selectors processes
    with
    | exc →

```

```

begin
  Printf.eprintf
    "0'Mega: exception %s in amplitude construction!\n"
    (Printexc.to_string exc);
  flush stderr;
  CF.empty;
end in

if !write then
  T.amplitudes_to_channel cmdline output_channel !checks amplitudes;
if ¬ !quiet then begin
  List.iter
    (fun amplitude →
      Printf.eprintf "SUMMARY: %d fusions, %d propagators"
        (F.count_fusions amplitude) (F.count_propagators amplitude);
      flush stderr;
      Printf.eprintf ", %d diagrams" (F.count_diagrams amplitude);
      Printf.eprintf "\n")
    (CF.processes amplitudes);
end;

if !poles then begin
  List.iter
    (fun amplitude →
      W.write output_channel "omega" (W.merge (W.trees amplitude)))
    (CF.processes amplitudes);
end;

begin match !dag0_out with
| Some name →
  let ch = open_out name in
  List.iter (F.tower_to_dot ch) (CF.processes amplitudes);
  close_out ch
| None → ()
end;

begin match !dag_out with
| Some name →
  let ch = open_out name in
  List.iter (F.amplitude_to_dot ch) (CF.processes amplitudes);
  close_out ch
| None → ()
end;

if !print_forest then
  List.iter
    (fun amplitude →
      List.iter (fun t → Printf.eprintf "%s\n"
        (Tree.to_string
          (Tree.map (fun (wf, _) → variable wf) (fun _ →
            "")) t)))
      (F.forest (List.hd (F.externals amplitude)) amplitude))

```

```

      (CF.processes amplitudes);
begin match !output_file with
| None → ()
| Some name → close_out output_channel
end;
exit 0
end

```



This was only intended for debugging O’Giga ...

```

let decode wf =
  (F.flavor wf, (F.momentum wf : Momentum.Default.t))

let diagrams in1 in2 out =
  match F.amplitudes false C.no_cascades [in1; in2] out with
  | a :: _ →
    let wf1 = List.hd (F.externals a)
    and wf2 = List.hd (List.tl (F.externals a)) in
    let wf2 = decode wf2 in
    List.map (fun t →
      (wf2,
        Tree.map (fun (wf, _) → decode wf) decode t))
      (F.forest wf1 a)
  | [] → []

let diagrams in1 in2 out =
  failwith "Omega().diagrams: disabled"
end

```

18.4 Implementation of *Omega_QED*

```

module O = Omega.Make(Fusion.Binary)(Targets.Fortran)(Modellib_SM.QED)
let _ = O.main ()

```

18.5 Implementation of *Omega_SM*

```

module O = Omega.Make(Fusion.Mixed23)(Targets.Fortran)
  (Modellib_SM.SM(Modellib_SM.SM_no_anomalous))
let _ = O.main ()

```

18.6 Implementation of *Omega_SYM*

```

let rcs_file = RCS.parse "omega_SYM"
  ["SuperYang-Mills(incomplete,just_for_stress-testing,Colorize.It())"]
{ RCS.revision = "$Revision: 4538$";

```

```

RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013) $";
RCS.author = "$Author: jr-reuter $";
RCS.source
  = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
module SYM =
struct
  let rcs = rcs_file
  open Coupling
  let options = Options.empty
  let nc = 3
  type flavor =
    | Q of int | SQ of int
    | G of int | SG of int
    | Phi
  let generations = ThoList.range 1 1
  let generations_pairs =
    List.map
      (function [a; b] → (a, b)
       | _ → failwith "omega_SYM.generations_pairs")
      (Product.power 2 generations)
  let generations_triples =
    List.map
      (function [a; b; c] → (a, b, c)
       | _ → failwith "omega_SYM.generations_triples")
      (Product.power 3 generations)
  let generations_quadruples =
    List.map
      (function [a; b; c; d] → (a, b, c, d)
       | _ → failwith "omega_SYM.generations_quadruples")
      (Product.power 4 generations)
  let external_flavors () =
    [ "Quarks", List.map (fun i → Q i) generations;
      "Anti-Quarks", List.map (fun i → Q (-i)) generations;
      "SQuarks", List.map (fun i → SQ i) generations;
      "Anti-SQuarks", List.map (fun i → SQ (-i)) generations;
      "Gluons", List.map (fun i → G i) generations;
      "SGluons", List.map (fun i → SG i) generations;
      "Other", [Phi]]
  let flavors () =
    ThoList.flatmap snd (external_flavors ())
  type gauge = unit
  type constant =
    | G_saa of int × int
    | G_saaa of int × int × int

```

```

|  $G3$  of  $int \times int \times int$ 
|  $I\_G3$  of  $int \times int \times int$ 
|  $G4$  of  $int \times int \times int \times int$ 

type orders = unit
let orders = function
| _  $\rightarrow$  ()

let lorentz = function
|  $Q\ i \rightarrow$ 
  if  $i > 0$  then
    Spinor
  else if  $i < 0$  then
    ConjSpinor
  else
    invalid_arg "SYM.lorentz_⊔(Q_⊔0)"
|  $SQ\ _ \mid \Phi \rightarrow$  Scalar
|  $G\ _ \rightarrow$  Vector
|  $SG\ _ \rightarrow$  Majorana

let color = function
|  $Q\ i \mid SQ\ i \rightarrow$ 
  Color.SUN (if  $i > 0$  then nc else if  $i < 0$  then -nc else invalid_arg "SYM.color_⊔(Q_⊔0)")
|  $G\ _ \mid SG\ _ \rightarrow$  Color.AdjSUN nc
|  $\Phi \rightarrow$  Color.Singlet

let propagator = function
|  $Q\ i \rightarrow$ 
  if  $i > 0$  then
    Prop_Spinor
  else if  $i < 0$  then
    Prop_ConjSpinor
  else
    invalid_arg "SYM.lorentz_⊔(Q_⊔0)"
|  $SQ\ _ \mid \Phi \rightarrow$  Prop_Scalar
|  $G\ _ \rightarrow$  Prop_Feynman
|  $SG\ _ \rightarrow$  Prop_Majorana

let width _ = Timelike
let goldstone _ = None

let conjugate = function
|  $Q\ i \rightarrow Q\ (-i)$ 
|  $SQ\ i \rightarrow SQ\ (-i)$ 
|  $(G\ _ \mid SG\ _ \mid \Phi)$  as  $p \rightarrow p$ 

let fermion = function
|  $Q\ i \rightarrow$ 
  if  $i > 0$  then
    1
  else if  $i < 0$  then
    -1
  else
    invalid_arg "SYM.fermion_⊔(Q_⊔0)"

```



```

| SQ - | G - | Phi → 0
| SG - → 2

module Ch = Charges.Null
let charges _ = ()

module F = Modeltools.Fusions (struct
  type f = flavor
  type c = constant
  let compare = compare
  let conjugate = conjugate
end)

let quark_current =
  List.map
    (fun (i, j, k) →
      ((Q (-i), G j, Q k), FBF (-1, Psibar, V, Psi), G3 (i, j, k)))
    generations_triples

let squark_current =
  List.map
    (fun (i, j, k) →
      ((G j, SQ i, SQ (-k)), Vector_Scalar_Scalar 1, G3 (i, j, k)))
    generations_triples

let three_gluon =
  List.map
    (fun (i, j, k) →
      ((G i, G j, G k), Gauge_Gauge_Gauge 1, I_G3 (i, j, k)))
    generations_triples

let gluon2_phi =
  List.map
    (fun (i, j) →
      ((Phi, G i, G j), Dim5_Scalar_Gauge2 1, G_saa (i, j)))
    generations_pairs

let vertices3 =
  quark_current @ squark_current @ three_gluon @ gluon2_phi

let gauge4 = Vector4 [(2, C_13_42); (-1, C_12_34); (-1, C_14_23)]

let squark_seagull =
  List.map
    (fun (i, j, k, l) →
      ((SQ i, SQ (-j), G k, G l), Scalar2_Vector2 1, G4 (i, j, k, l)))
    generations_quadruples

let four_gluon =
  List.map
    (fun (i, j, k, l) →
      ((G i, G j, G k, G l), gauge4, G4 (i, j, k, l)))
    generations_quadruples

```



We need at least a *Dim6_Scalar_Gauge3* vertex to support this.

```

let gluon3_phi =
  []

let vertices4 =
  squark_seagull @ four_gluon @ gluon3_phi

let vertices () =
  (vertices3, vertices4, [])

let table = F.of_vertices (vertices ())
let fuse2 = F.fuse2 table
let fuse3 = F.fuse3 table
let fuse = F.fuse table
let max_degree () = 4

let parameters () = { input = []; derived = []; derived_arrays = [] }

let invalid_flavor s =
  invalid_arg ("omega-SYM.flavor-of-string:␣" ^ s)

let flavor_of_string s =
  let l = String.length s in
  if l < 2 then
    invalid_flavor s
  else if l = 2 then
    if String.sub s 0 1 = "q" then
      Q (int_of_string (String.sub s 1 1))
    else if String.sub s 0 1 = "Q" then
      Q (-(int_of_string (String.sub s 1 1)))
    else if String.sub s 0 1 = "g" then
      G (int_of_string (String.sub s 1 1))
    else
      invalid_flavor s
  else if l = 3 then
    if s = "phi" then
      Phi
    else if String.sub s 0 2 = "sq" then
      SQ (int_of_string (String.sub s 2 1))
    else if String.sub s 0 2 = "sQ" then
      SQ (-(int_of_string (String.sub s 2 1)))
    else if String.sub s 0 2 = "sg" then
      SG (int_of_string (String.sub s 2 1))
    else
      invalid_flavor s
  else
    invalid_flavor s

let flavor_to_string = function
| Q i →
  if i > 0 then
    "q" ^ string_of_int i

```

```

else if  $i < 0$  then
  "Q" ^ string_of_int (-i)
else
  invalid_arg "SYM.flavor_to_string⊥(Q⊥0)"
| SQ i →
  if  $i > 0$  then
    "sq" ^ string_of_int i
  else if  $i < 0$  then
    "sQ" ^ string_of_int (-i)
  else
    invalid_arg "SYM.flavor_to_string⊥(SQ⊥0)"
| G i → "g" ^ string_of_int i
| SG i → "sg" ^ string_of_int i
| Phi → "phi"

let flavor_to_TeX = function
| Q i →
  if  $i > 0$  then
    "q_{" ^ string_of_int i ^ "}"
  else if  $i < 0$  then
    "{\bar{q}}_{" ^ string_of_int (-i) ^ "}"
  else
    invalid_arg "SYM.flavor_to_string⊥(Q⊥0)"
| SQ i →
  if  $i > 0$  then
    "{\tilde{q}}_{" ^ string_of_int i ^ "}"
  else if  $i < 0$  then
    "{\bar{\tilde{q}}}_{" ^ string_of_int (-i) ^ "}"
  else
    invalid_arg "SYM.flavor_to_string⊥(SQ⊥0)"
| G i → "g_{" ^ string_of_int i ^ "}"
| SG i → "{\tilde{g}}_{" ^ string_of_int i ^ "}"
| Phi → "phi"

let flavor_symbol = function
| Q i →
  if  $i > 0$  then
    "q" ^ string_of_int i
  else if  $i < 0$  then
    "qbar" ^ string_of_int (-i)
  else
    invalid_arg "SYM.flavor_to_string⊥(Q⊥0)"
| SQ i →
  if  $i > 0$  then
    "sq" ^ string_of_int i
  else if  $i < 0$  then
    "sqbar" ^ string_of_int (-i)
  else
    invalid_arg "SYM.flavor_to_string⊥(SQ⊥0)"
| G i → "g" ^ string_of_int i
| SG i → "sg" ^ string_of_int i

```

```

    | Phi → "phi"
let gauge_symbol () =
  failwith "omega-SYM.gauge-symbol: internal error"
let pdg _ = 0
let mass_symbol _ = "0.0-default"
let width_symbol _ = "0.0-default"
let string_of_int_list int_list =
  "(" ^ String.concat "," (List.map string_of_int int_list) ^ ")"
let constant_symbol = function
  | G_saa (i, j) → "g_saa" ^ string_of_int_list [i; j]
  | G_saaa (i, j, k) → "g_saaa" ^ string_of_int_list [i; j; k]
  | G3 (i, j, k) → "g3" ^ string_of_int_list [i; j; k]
  | I_G3 (i, j, k) → "ig3" ^ string_of_int_list [i; j; k]
  | G4 (i, j, k, l) → "g4" ^ string_of_int_list [i; j; k; l]
end
module O = Omega.Make(Fusion.Mixed23)(Targets.Fortran_Majorana)(SYM)
let _ = O.main ()

```

ACKNOWLEDGEMENTS

We thank Mauro Moretti for fruitful discussions of the ALPHA algorithm [1], that inspired our solution of the double counting problem.

We thank Wolfgang Kilian for providing the WHIZARD environment that turns our numbers into real events with unit weight. Thanks to the ECFA/DESY workshops and their participants for providing a showcase. Thanks to Edward Boos for discussions in Kaluza-Klein gravitons.

This research is supported by Bundesministerium für Bildung und Forschung, Germany, (05 HT9RDA) and Deutsche Forschungsgemeinschaft (MA 676/6-1).

Thanks to the Caml and Objective Caml teams from INRIA for the development and the lean and mean implementation of a programming language that does not insult the programmer's intelligence.

BIBLIOGRAPHY

- [1] F. Caravaglios, M. Moretti, Z. Phys. **C74** (1997) 291.
- [2] A. Kanaki, C. Papadopoulos, DEMO-HEP-2000/01, hep-ph/0002082, February 2000.
- [3] Xavier Leroy, *The Objective Caml system, documentation and user's guide*, Technical Report, INRIA, 1997.
- [4] Chris Okasaki, *Purely Functional Data Structures*, Cambridge University Press, 1998.
- [5] H. Murayama, I. Watanabe, K. Hagiwara, KEK Report 91-11, January 1992.
- [6] T. Stelzer, W.F. Long, Comput. Phys. Commun. **81** (1994) 357.
- [7] A. Denner, H. Eck, O. Hahn and J. Küblbeck, Phys. Lett. **B291** (1992) 278; Nucl. Phys. **B387** (1992) 467.
- [8] V. Barger, A. L. Stange, R. J. N. Phillips, Phys. Rev. **D45**, (1992) 1751.
- [9] T. Ohl, *Lord of the Rings*, (Computer algebra library for O'Caml, unpublished).
- [10] T. Ohl, *Bocages*, (Feynman diagram library for O'Caml, unpublished).
- [11] W. Kilian, *WHIZARD*, University of Karlsruhe, 2000.
- [12] E. E. Boos, T. Ohl, Phys. Rev. Lett. **83** (1999) 480.
- [13] T. Han, J. D. Lykken and R. Zhang, Phys. Rev. **D59** (1999) 105006 [hep-ph/9811350].
- [14] William H. Press, Saul A. Teukolsky, William T. Vetterling, Brian P. Flannery, *Numerical Recipes: The Art of Scientific Computing*, Second Edition, Cambridge University Press, 1992.
- [15] P. Cvitanović, Phys. Rev. **D14** (1976) 1536.

—A—

REVISION CONTROL

A.1 Interface of *RCS*

This is a very simple library for exporting and accessing **RCS** and **CVS** revision control information. In addition, module names and short descriptions are supported as well.

If multiple applications are constructed by functors, the functions in this module can be used to identify the concrete implementations. In the context of O’Mega, this is particularly important for physics models and target languages. One structure of type *raw* has to be initialized in each file by the raw RCS keyword strings. It can remain private to the module, because it is only used as argument to the function *parse*.

`type raw = { revision : string; date : string; author : string; source : string }`

Parsed revision control info:

`type t`

parse name description keywords initializes revision control info:

`val parse : string → string list → raw → t`

rename rcs name description changes the name and description. This is useful if more than one module is defined in a file.

`val rename : t → string → string list → t`

Access individual parts of the revision control information:

`val name : t → string`

`val description : t → string list`

`val revision : t → string`

`val date : t → string`

`val author : t → string`

This one tries **URL** (svn), **Source** (CVS) and **Id**, in that order, for the filename.

`val source : t → string`

Return the formatted revision control info as a list of strings suitable for printing to the terminal or embedding in the output:

`val summary : t → string list`

A.2 Implementation of RCS

```

type raw = { revision : string; date : string; author : string; source : string }

type t =
  { name : string;
    description : string list;
    rcs_revision : string;
    rcs_date : string;
    rcs_author : string;
    rcs_source : string }

let name r = r.name
let description r = r.description
let revision r = r.rcs_revision
let date r = r.rcs_date
let author r = r.rcs_author
let source r = r.rcs_source

module TS = ThoString

let strip_dollars s =
  TS.strip_from_last '$' (TS.strip_prefix "$" s)

let strip_keyword k s =
  TS.strip_prefix_star ' ' (TS.strip_prefix ":" (TS.strip_required_prefix k s))

let parse1 k s =
  strip_keyword k (strip_dollars s)

let strip_before_keyword k s =
  try
    let i = TS.index_string k s in
    String.sub s i (String.length s - i)
  with
  | Not_found → s

let strip_before_a_keyword k_list s =
  let rec strip_before_a_keyword' = function
    | k :: k_rest →
        begin try
          let i = TS.index_string k s in
          String.sub s i (String.length s - i)
        with
        | Not_found → strip_before_a_keyword' k_rest
        end
    | [] → s in
  strip_before_a_keyword' k_list

let parse_source s =
  let s = strip_dollars s in

```

Required for the transition from CVS to Subversion, because the latter doesn't support the `Source` keyword. `URL` is probably the way to go, but we leave in `Id` as a fallback option.


```

try strip_keyword "URL" s with Invalid_argument _ →
  try strip_keyword "Source" s with Invalid_argument _ →
    TS.strip_from_first ' ' (strip_keyword "Id" s)

```

Assume that the SVN repository follows the recommended layout and that all files can be found beneath `/trunk/`, `/branches/` or `/tags/`. Strip everything before that.

```

let strip_svn_repos s =
  strip_before_a_keyword ["/trunk/"; "/branches/"; "/tags/"] s

let parse_name_description r =
  { name = name;
    description = description;
    rcs_revision = parse1 "Revision" r.revision;
    rcs_date = parse1 "Date" r.date;
    rcs_author = parse1 "Author" r.author;
    rcs_source = strip_svn_repos (parse_source r.source) }

let rename_rcs name description =
  { rcs with name = name; description = description }

let summary rcs =
  [ name rcs ^ ":" ] @
  List.map (fun s → "  " ^ s) (description rcs) @
  [ "  Source:" ^ source rcs;
    "  revision:" ^ revision rcs ^ "checked_in_by" ^
    author rcs ^ "at" ^ date rcs ]

```

—B—

AUTOTOOLS

B.1 Interface of Config

Cache writing is attempted in the order `[system_cache_dir]`, `[user_cache_dir]`, `["."]` and cache reading in the opposite order.

```
val system_cache_dir : string
val user_cache_dir   : string

val cache_prefix : string
val cache_suffix : string

val openmp : bool
```

B.2 Implementation of Config

```
let system_cache_dir = "/Users/reuter/local/packages/whizard/omega/inst/var/cache"
let user_cache_dir   = "/Users/reuter/.whizard/var/cache"
```



This relies on the fact that the executable names should be unique.

```
let cache_prefix =
  let basename = Filename.basename Sys.executable_name in
  try Filename.chop_extension basename with | _ → basename

let cache_suffix = "vertices"

let openmp = false
```

—C—

TEXTUAL OPTIONS

C.1 Interface of Options

```
type t
val empty : t
val merge : t → t → t
val extend : t → (string × Arg.spec × string) list → t
val create : (string × Arg.spec × string) list → t
val parse : t → string × string → unit
val list : t → (string × string) list
val cmdline : string → t → (string × Arg.spec × string) list
exception Invalid of string × string
```

C.2 Implementation of Options

```
module A = Map.Make (struct type t = string let compare = compare end)
type t =
  { actions : Arg.spec A.t;
    raw : (string × Arg.spec × string) list }
let empty = { actions = A.empty; raw = [] }
let extend old options =
  { actions = List.fold_left
    (fun a (s, f, _) → A.add s f a) old.actions options;
    raw = options @ old.raw }
let create = extend empty
let merge o1 o2 =
  extend o1 o2.raw
exception Invalid of string × string
let parse options (name, value) =
  try
    match A.find name options.actions with
    | Arg.Unit f → f ()
```

```
| Arg.Set b → b := true
| Arg.Clear b → b := false
| Arg.String f → f value
| Arg.Int f → f (int_of_string value)
| Arg.Float f → f (float_of_string value)
| _ → invalid_arg "Options.parse"
with
| Not_found → raise (Invalid (name, value))

let list options =
  List.map (fun (o, _, d) → (o, d)) options.raw

let cmdline prefix options =
  List.map (fun (o, f, d) → (prefix ^ o, f, d)) options.raw
```

—D—

PROGRESS REPORTS

D.1 Interface of Progress

```
type t
val dummy : t
val channel : out_channel → int → t
val file : string → int → t
val open_file : string → int → t
val reset : t → int → string → unit
val begin_step : t → string → unit
val end_step : t → string → unit
val summary : t → string → unit
```

D.2 Implementation of Progress

```
type channel =
| Channel of out_channel
| File of string
| Open_File of string × out_channel

type state =
{ channel : channel;
  mutable steps : int;
  mutable digits : int;
  mutable step : int;
  created : float;
  mutable last_reset : float;
  mutable last_begin : float; }

type t = state option

let digits n =
  if n > 0 then
    succ (truncate (log10 (float n)))
  else
    invalid_arg "Progress.digits: non-positive argument"

let mod_float2 a b =
```

```

let modulus = mod_float a b in
((a - . modulus) /. b, modulus)

let time_to_string seconds =
  let minutes, seconds = mod_float2 seconds 60. in
  if minutes > 0.0 then
    let hours, minutes = mod_float2 minutes 60. in
    if hours > 0.0 then
      let days, hours = mod_float2 hours 24. in
      if days > 0.0 then
        Printf.sprintf "%.0f:%02.0f_days" days hours
      else
        Printf.sprintf "%.0f:%02.0f_hrs" hours minutes
      else
        Printf.sprintf "%.0f:%02.0f_mins" minutes seconds
    else
      Printf.sprintf "%.2f_secs" seconds

let create_channel steps =
  let now = Sys.time () in
  Some { channel = channel;
        steps = steps;
        digits = digits steps;
        step = 0;
        created = now;
        last_reset = now;
        last_begin = now }

let dummy =
  None

let channel oc =
  create (Channel oc)

let file name =
  let oc = open_out name in
  close_out oc;
  create (File name)

let open_file name =
  let oc = open_out name in
  create (Open_File (name, oc))

let close_channel state =
  match state.channel with
  | Channel oc →
    flush oc
  | File _ → ()
  | Open_File (_, oc) →
    flush oc;
    close_out oc

let use_channel state f =
  match state.channel with

```

```

| Channel oc | Open_File (_, oc) →
  f oc;
  flush oc
| File name →
  let oc = open_out_gen [Open_append; Open_creat] 644 name in
  f oc;
  flush oc;
  close_out oc

let reset state steps msg =
  match state with
  | None → ()
  | Some state →
    let now = Sys.time () in
    state.steps ← steps;
    state.digits ← digits steps;
    state.step ← 0;
    state.last_reset ← now;
    state.last_begin ← now

let begin_step state msg =
  match state with
  | None → ()
  | Some state →
    let now = Sys.time () in
    state.step ← succ state.step;
    state.last_begin ← now;
    use_channel state (fun oc →
      Printf.fprintf oc "[%0*d/%0*d] %s. . ." state.digits state.step state.digits state.steps msg)

let end_step state msg =
  match state with
  | None → ()
  | Some state →
    let now = Sys.time () in
    let last = now - . state.last_begin in
    let elapsed = now - . state.last_reset in
    let estimated = float state.steps * . elapsed /. float state.step in
    let remaining = estimated - . elapsed in
    use_channel state (fun oc →
      Printf.fprintf oc "%s. [time: %s, total: %s, remaining: %s]\n" msg
        (time_to_string last) (time_to_string estimated) (time_to_string remaining))

let summary state msg =
  match state with
  | None → ()
  | Some state →
    let now = Sys.time () in
    use_channel state (fun oc →
      Printf.fprintf oc "%s. [total %s, time: %s]\n" msg
        (time_to_string (now - . state.created)));
    close_channel state

```

—E—

MORE ON FILENAMES

E.1 Interface of ThoFilename

```
val split : string → string list
val join  : string list → string
val expand_home : string → string
```

E.2 Implementation of ThoFilename

```
let rec split' acc path =
  match Filename.dirname path, Filename.basename path with
  | "/", basename → "/" :: basename :: acc
  | ".", basename → basename :: acc
  | dirname, basename → split' (basename :: acc) dirname

let split path =
  split' [] path

let join = function
  | [] → "."
  | [basename] → basename
  | dirname :: rest → List.fold_left Filename.concat dirname rest

let expand_home path =
  match split path with
  | ("~" | "$HOME" | "${HOME}") :: rest →
    join ((try Sys.getenv "HOME" with Not_found → "/tmp") :: rest)
  | _ → path
```

—F—

CACHE FILES

F.1 Interface of Cache

```
module type T =
  sig
    type key
    type hash = string
    type value

    type  $\alpha$  result =
      | Hit of  $\alpha$ 
      | Miss
      | Stale of string

    exception Mismatch of string  $\times$  string  $\times$  string

    val hash : key  $\rightarrow$  hash
    val exists : hash  $\rightarrow$  string  $\rightarrow$  bool
    val find : hash  $\rightarrow$  string  $\rightarrow$  string option
    val write : hash  $\rightarrow$  string  $\rightarrow$  value  $\rightarrow$  unit
    val write_dir : hash  $\rightarrow$  string  $\rightarrow$  string  $\rightarrow$  value  $\rightarrow$  unit
    val read : hash  $\rightarrow$  string  $\rightarrow$  value
    val maybe_read : hash  $\rightarrow$  string  $\rightarrow$  value result

  end

module type Key =
  sig
    type t
  end

module type Value =
  sig
    type t
  end

module Make (Key : Key) (Value : Value) :
  T with type key = Key.t and type value = Value.t
```

F.2 Implementation of Cache

```

let search_path =
  [ Filename.current_dir_name;
    ThoFilename.expand_home Config.user_cache_dir;
    Config.system_cache_dir ]

module type T =
  sig
    type key
    type hash = string
    type value

    type  $\alpha$  result =
      | Hit of  $\alpha$ 
      | Miss
      | Stale of string

    exception Mismatch of string  $\times$  string  $\times$  string

    val hash : key  $\rightarrow$  hash
    val exists : hash  $\rightarrow$  string  $\rightarrow$  bool
    val find : hash  $\rightarrow$  string  $\rightarrow$  string option
    val write : hash  $\rightarrow$  string  $\rightarrow$  value  $\rightarrow$  unit
    val write_dir : hash  $\rightarrow$  string  $\rightarrow$  string  $\rightarrow$  value  $\rightarrow$  unit
    val read : hash  $\rightarrow$  string  $\rightarrow$  value
    val maybe_read : hash  $\rightarrow$  string  $\rightarrow$  value result
  end

module type Key =
  sig
    type t
  end
end

module type Value =
  sig
    type t
  end
end

module Make (Key : Key) (Value : Value) =
  struct
    type key = Key.t
    type hash = string
    type value = Value.t

    type tagged =
      { tag : hash;
        value : value; }

    let hash value =
      Digest.string (Marshal.to_string value [])

    let find_first path name =

```

```

let rec find_first' = function
| [] → raise Not_found
| dir :: path →
  let f = Filename.concat dir name in
  if Sys.file_exists f then
    f
  else
    find_first' path
in
find_first' path

let find hash name =
  try Some (find_first search_path name) with Not_found → None

let exists hash name =
  match find hash name with
  | None → false
  | Some _ → true

let try_first f path name =
  let rec try_first' = function
  | [] → raise Not_found
  | dir :: path →
    try (f (Filename.concat dir name), dir) with _ → try_first' path
  in
  try_first' path

let open_in_bin_first = try_first open_in_bin
let open_out_bin_last path = try_first open_out_bin (List.rev path)

let write hash name value =
  let oc, _ = open_out_bin_last search_path name in
  Marshal.to_channel oc { tag = hash; value = value } [];
  close_out oc

let write_dir hash dir name value =
  let oc = open_out_bin (Filename.concat dir name) in
  Marshal.to_channel oc { tag = hash; value = value } [];
  close_out oc

type  $\alpha$  result =
| Hit of  $\alpha$ 
| Miss
| Stale of string

exception Mismatch of string  $\times$  string  $\times$  string

let read hash name =
  let ic, dir = open_in_bin_first search_path name in
  let { tag = tag; value = value } = Marshal.from_channel ic in
  close_in ic;
  if tag = hash then
    value
  else
    raise (Mismatch (Filename.concat dir name, hash, tag))

```

```
let maybe_read hash name =  
  try  
    Hit (read hash name)  
  with  
  | Not_found → Miss  
  | Mismatch (file, -, -) → Stale file  
end
```

—G—

MORE ON LISTS

G.1 Interface of ThoList

splitn $n\ l = (hdn\ l, tln\ l)$, but more efficient.

val *hdn* : $int \rightarrow \alpha\ list \rightarrow \alpha\ list$

val *tln* : $int \rightarrow \alpha\ list \rightarrow \alpha\ list$

val *splitn* : $int \rightarrow \alpha\ list \rightarrow \alpha\ list \times \alpha\ list$

chop $n\ l$ chops l into pieces of size n (except for the last one, which contains the remainder).

val *chopn* : $int \rightarrow \alpha\ list \rightarrow \alpha\ list\ list$

of_subarray $n\ m\ a$ is $[a.(n); a.(n+1); \dots; a.(m)]$. Values of n and m out of bounds are silently shifted towards these bounds.

val *of_subarray* : $int \rightarrow int \rightarrow \alpha\ array \rightarrow \alpha\ list$

range $s\ n\ m$ is $[n; n+s; n+2s; \dots; m - ((m-n) \bmod s)]$

val *range* : $?stride : int \rightarrow int \rightarrow int \rightarrow int\ list$

enumerate $s\ n\ [a1; a2; \dots]$ is $[(n, a1); (n+s, a2); \dots]$

val *enumerate* : $?stride : int \rightarrow int \rightarrow \alpha\ list \rightarrow (int \times \alpha)\ list$

Compress identical elements in a sorted list. Identity is determined using the polymorphic equality function *Pervasives*.(=).

val *uniq* : $\alpha\ list \rightarrow \alpha\ list$

Test if all members of a list are structurally identical (actually *homogeneous* l and $List.length\ (uniq\ l) \leq 1$ are equivalent, but the former is more efficient if a mismatch comes early).

val *homogeneous* : $\alpha\ list \rightarrow bool$

compare $cmp\ l1\ l2$ compare two lists $l1$ and $l2$ according to cmp . cmp defaults to the polymorphic *Pervasives*.compare.

val *compare* : $?cmp : (\alpha \rightarrow \alpha \rightarrow int) \rightarrow \alpha\ list \rightarrow \alpha\ list \rightarrow int$

Collect and count identical elements in a list. Identity is determined using the polymorphic equality function *Pervasives*.(=). *classify* does not assume that

the list is sorted. However, it is $O(n)$ for sorted lists and $O(n^2)$ in the worst case.

`val classify : α list \rightarrow ($\text{int} \times \alpha$) list`

Collect the second factors with a common first factor in lists.

`val factorize : ($\alpha \times \beta$) list \rightarrow ($\alpha \times \beta$ list) list`

`flatMap f` is equivalent to `flatten \circ (map f)`, but more efficient, because no intermediate lists are built. Unfortunately, it is not tail recursive.

`val flatmap : ($\alpha \rightarrow \beta$ list) \rightarrow α list \rightarrow β list`

`rev_flatmap f` is equivalent to `flatten \circ (rev_map (rev \circ f)) = rev \circ (flatMap f)`, but more efficient, because no intermediate lists are built. It is tail recursive.

`val rev_flatmap : ($\alpha \rightarrow \beta$ list) \rightarrow α list \rightarrow β list`

`val clone : int \rightarrow $\alpha \rightarrow$ α list`

`val multiply : int \rightarrow α list \rightarrow α list`



Invent other names to avoid confusions with `List.fold_left2` and `List.fold_right2`.

`val fold_right2 : ($\alpha \rightarrow \beta \rightarrow \beta$) \rightarrow α list list \rightarrow $\beta \rightarrow \beta$`

`val fold_left2 : ($\beta \rightarrow \alpha \rightarrow \beta$) \rightarrow $\beta \rightarrow$ α list list \rightarrow β`

`iteri f n [a; b; c]` evaluates `f n a`, `f (n + 1) b` and `f (n + 2) c`.

`val iteri : (int \rightarrow $\alpha \rightarrow$ unit) \rightarrow int \rightarrow α list \rightarrow unit`

`val mapi : (int \rightarrow $\alpha \rightarrow \beta$) \rightarrow int \rightarrow α list \rightarrow β list`

`iteri2 f n m [[aa; ab]; [ba; bb]]` evaluates `f n m aa`, `f n (m + 1) ab`, `f (n + 1) m ba` and `f (n + 1) (m + 1) bb`. NB: the nested lists need not be rectangular.

`val iteri2 : (int \rightarrow int \rightarrow $\alpha \rightarrow$ unit) \rightarrow int \rightarrow int \rightarrow α list list \rightarrow unit`

Transpose a *rectangular* list of lists like a matrix.

`val transpose : α list list \rightarrow α list list`

`interleave f list` walks through `list` and inserts the result of `f` applied to the reversed list of elements before and the list of elements after. The empty lists at the beginning and end are included!

`val interleave : (α list \rightarrow α list \rightarrow α list) \rightarrow α list \rightarrow α list`

`interleave_nearest f list` is like `interleave f list`, but `f` looks only at the nearest neighbors.

`val interleave_nearest : ($\alpha \rightarrow \alpha \rightarrow \alpha$ list) \rightarrow α list \rightarrow α list`

`partitioned_sort cmp index_sets list` sorts the sublists of `list` specified by the `index_sets` and the complement of their union. **NB:** the sorting follows to order in the lists in `index_sets`. **NB:** the indices are 0-based.

`val partitioned_sort : ($\alpha \rightarrow \alpha \rightarrow$ int) \rightarrow int list list \rightarrow α list \rightarrow α list`

exception `Overlapping_indices`

exception `Out_of_bounds`

ariadne_sort cmp list sorts *list* according to *cmp* (default *Pervasives.compare*) keeping track of the original order by a 0-based list of indices.

`val ariadne_sort : ?cmp : ($\alpha \rightarrow \alpha \rightarrow \text{int}$) $\rightarrow \alpha \text{ list} \rightarrow \alpha \text{ list} \times \text{int list}$`

ariadne_unsort (ariadne_sort cmp list) returns *list*.

`val ariadne_unsort : $\alpha \text{ list} \times \text{int list} \rightarrow \alpha \text{ list}$`

G.2 Implementation of *ThoList*

```

let rec hdn n l =
  if n ≤ 0 then
    []
  else
    match l with
    | x :: rest → x :: hdn (pred n) rest
    | [] → invalid_arg "ThoList.hdn"

let rec tln n l =
  if n ≤ 0 then
    l
  else
    match l with
    | _ :: rest → tln (pred n) rest
    | [] → invalid_arg "ThoList.tln"

let rec splitn' n l1_rev l2 =
  if n ≤ 0 then
    (List.rev l1_rev, l2)
  else
    match l2 with
    | x :: l2' → splitn' (pred n) (x :: l1_rev) l2'
    | [] → invalid_arg "ThoList.splitn_n>len"

let splitn n l =
  if n < 0 then
    invalid_arg "ThoList.splitn_n<0"
  else
    splitn' n [] l

```

This is *splitn'* all over again, but without the exception.

```

let rec chopn'' n l1_rev l2 =
  if n ≤ 0 then
    (List.rev l1_rev, l2)
  else
    match l2 with
    | x :: l2' → chopn'' (pred n) (x :: l1_rev) l2'
    | [] → (List.rev l1_rev, [])

let rec chopn' n ll_rev = function
  | [] → List.rev ll_rev

```

```

| l →
  begin match chopn'' n [] l with
  | [], [] → List.rev ll_rev
  | l1, [] → List.rev (l1 :: ll_rev)
  | l1, l2 → chopn' n (l1 :: ll_rev) l2
  end

let chopn n l =
  if n ≤ 0 then
    invalid_arg "ThoList.chopn: n ≤ 0"
  else
    chopn' n [] l

let of_subarray n1 n2 a =
  let rec of_subarray' n1 n2 =
    if n1 > n2 then
      []
    else
      a.(n1) :: of_subarray' (succ n1) n2 in
  of_subarray' (max 0 n1) (min n2 (pred (Array.length a)))

let range ?(stride = 1) n1 n2 =
  if stride ≤ 0 then
    invalid_arg "ThoList.range: stride ≤ 0"
  else
    let rec range' n =
      if n > n2 then
        []
      else
        n :: range' (n + stride) in
    range' n1

```

Tail recursive:

```

let enumerate ?(stride = 1) n l =
  let _, l_rev =
    List.fold_left
      (fun (i, acc) a → (i + stride, (i, a) :: acc))
      (n, []) l in
  List.rev l_rev

```

This is *not* tail recursive!

```

let rec flatmap f = function
| [] → []
| x :: rest → f x @ flatmap f rest

```

This is!

```

let rev_flatmap f l =
  let rec rev_flatmap' acc f = function
  | [] → acc
  | x :: rest → rev_flatmap' (List.rev_append (f x) acc) f rest in
  rev_flatmap' [] f l

```



```

let fold_left2 f acc lists =
  List.fold_left (List.fold_left f) acc lists

let fold_right2 f lists acc =
  List.fold_right (List.fold_right f) lists acc

let iteri f start list =
  ignore (List.fold_left (fun i a → f i a; succ i) start list)

let iteri2 f start_outer star_inner lists =
  iteri (fun j → iteri (f j) star_inner) start_outer lists

let mapi f start list =
  let next, list' =
    List.fold_left (fun (i, acc) a → (succ i, f i a :: acc)) (start, []) list in
  List.rev list'

Is there a more efficient implementation?

let transpose lists =
  let rec transpose' rest =
    if List.for_all ((=) []) rest then
      []
    else
      List.map List.hd rest :: transpose' (List.map List.tl rest) in
  try
    transpose' lists
  with
  | Failure "tl" → invalid_arg "ThoList.transpose: not rectangular"

let compare ?(cmp = Pervasives.compare) l1 l2 =
  let rec compare' l1' l2' =
    match l1', l2' with
    | [], [] → 0
    | [], _ → -1
    | _, [] → 1
    | n1 :: r1, n2 :: r2 →
      let c = cmp n1 n2 in
      if c ≠ 0 then
        c
      else
        compare' r1 r2
  in
  compare' l1 l2

let rec uniq' x = function
| [] → []
| x' :: rest →
  if x' = x then
    uniq' x rest
  else
    x' :: uniq' x' rest

let uniq = function
| [] → []

```

```

| x :: rest → x :: uniq' x rest
let rec homogeneous = function
| [] | [-] → true
| a1 :: (a2 :: _ as rest) →
  if a1 ≠ a2 then
    false
  else
    homogeneous rest

```

If we needed it, we could use a polymorphic version of *Set* to speed things up from $O(n^2)$ to $O(n \ln n)$. But not before it matters somewhere ...

```

let classify l =
  let rec add_to_class a = function
  | [] → [1, a]
  | (n, a') :: rest →
    if a = a' then
      (succ n, a) :: rest
    else
      (n, a') :: add_to_class a rest
  in
  let rec classify' cl = function
  | [] → cl
  | a :: rest → classify' (add_to_class a cl) rest
  in
  classify' [] l
let rec factorize l =
  let rec add_to_class x y = function
  | [] → [(x, [y])]
  | (x', ys) :: rest →
    if x = x' then
      (x, y :: ys) :: rest
    else
      (x', ys) :: add_to_class x y rest
  in
  let rec factorize' fl = function
  | [] → fl
  | (x, y) :: rest → factorize' (add_to_class x y fl) rest
  in
  List.map (fun (x, ys) → (x, List.rev ys)) (factorize' [] l)
let rec clone n x =
  if n < 0 then
    invalid_arg "ThoList.clone"
  else if n = 0 then
    []
  else
    x :: clone (pred n) x
let interleave f list =
  let rec interleave' rev_head tail =

```

```

    let rev_head' = List.rev_append (f rev_head tail) rev_head in
    match tail with
    | [] → List.rev rev_head'
    | x :: tail' → interleave' (x :: rev_head') tail'
  in
  interleave' [] list

let interleave_nearest f list =
  interleave
    (fun head tail →
      match head, tail with
      | h :: _, t :: _ → f h t
      | _ → [])
    list

let rec rev_multiply n rl l =
  if n < 0 then
    invalid_arg "ThoList.multiply"
  else if n = 0 then
    []
  else
    List.rev_append rl (rev_multiply (pred n) rl l)

let multiply n l = rev_multiply n (List.rev l) l

module ISet = Set.Make (struct type t = int let compare = Pervasives.compare end)

exception Overlapping_indices
exception Out_of_bounds

let iset_of_list list =
  List.fold_right ISet.add list ISet.empty

let iset_list_union list =
  List.fold_right ISet.union list ISet.empty

let complement_index_sets n index_set_lists =
  let index_sets = List.map iset_of_list index_set_lists in
  let index_set = iset_list_union index_sets in
  let size_index_sets =
    List.fold_left (fun acc s → ISet.cardinal s + acc) 0 index_sets in
  if size_index_sets ≠ ISet.cardinal index_set then
    raise Overlapping_indices
  else if ISet.exists (fun i → i < 0 ∨ i ≥ n) index_set then
    raise Overlapping_indices
  else
    match ISet.elements (ISet.diff (iset_of_list (range 0 (pred n))) index_set) with
    | [] → index_set_lists
    | complement → complement :: index_set_lists

let sort_section cmp array index_set =
  List.iter2
    (Array.set array)
    index_set (List.sort cmp (List.map (Array.get array) index_set))

```

```

let partitioned_sort cmp index_sets list =
  let array = Array.of_list list in
  List.fold_left
    (fun () → sort_section cmp array)
    () (complement_index_sets (List.length list) index_sets);
  Array.to_list array

let ariadne_sort ?(cmp = Pervasives.compare) list =
  let sorted =
    List.sort (fun (n1, a1) (n2, a2) → cmp a1 a2) (enumerate 0 list) in
  (List.map snd sorted, List.map fst sorted)

let ariadne_unsort (sorted, indices) =
  List.map snd
    (List.sort
      (fun (n1, a1) (n2, a2) → Pervasives.compare n1 n2)
      (List.map2 (fun n a → (n, a)) indices sorted))

```

—H—

MORE ON ARRAYS

H.1 Interface of ThoArray

Compressed arrays, i. e. arrays with only unique elements and an embedding that allows to recover the original array. NB: in the current implementation, compressing saves space, if *and only if* objects of type α require more storage than integers. The main use of α *compressed* is *not* for saving space, anyway, but for avoiding the repetition of hard calculations.

```
type  $\alpha$  compressed
val uniq :  $\alpha$  compressed  $\rightarrow$   $\alpha$  array
val embedding :  $\alpha$  compressed  $\rightarrow$  int array
```

These two are inverses of each other:

```
val compress :  $\alpha$  array  $\rightarrow$   $\alpha$  compressed
val uncompress :  $\alpha$  compressed  $\rightarrow$   $\alpha$  array
```

One can play the same game for matrices.

```
type  $\alpha$  compressed2
val uniq2 :  $\alpha$  compressed2  $\rightarrow$   $\alpha$  array array
val embedding1 :  $\alpha$  compressed2  $\rightarrow$  int array
val embedding2 :  $\alpha$  compressed2  $\rightarrow$  int array
```

Again, these two are inverses of each other:

```
val compress2 :  $\alpha$  array array  $\rightarrow$   $\alpha$  compressed2
val uncompress2 :  $\alpha$  compressed2  $\rightarrow$   $\alpha$  array array
```

H.2 Implementation of ThoArray

```
type  $\alpha$  compressed =
  { uniq :  $\alpha$  array;
    embedding : int array }

let uniq a = a.uniq
let embedding a = a.embedding

type  $\alpha$  compressed2 =
  { uniq2 :  $\alpha$  array array;
```

```

    embedding1 : int array;
    embedding2 : int array }

let uniq2 a = a.uniq2
let embedding1 a = a.embedding1
let embedding2 a = a.embedding2

module PMap = Pmap.Tree

let compress a =
  let last = Array.length a - 1 in
  let embedding = Array.make (succ last) (-1) in
  let rec scan num_uniq uniq elements n =
    if n > last then
      { uniq = Array.of_list (List.rev elements);
        embedding = embedding }
    else
      match PMap.find_opt compare a.(n) uniq with
      | Some n' →
        embedding.(n) ← n';
        scan num_uniq uniq elements (succ n)
      | None →
        embedding.(n) ← num_uniq;
        scan
          (succ num_uniq)
          (PMap.add compare a.(n) num_uniq uniq)
          (a.(n) :: elements)
          (succ n) in
    scan 0 PMap.empty [] 0

let uncompress a =
  Array.map (Array.get a.uniq) a.embedding

```



Using *transpose* simplifies the algorithms, but can be inefficient. If this turns out to be the case, we should add special treatments for symmetric matrices.

```

let transpose a =
  let dim1 = Array.length a
  and dim2 = Array.length a.(0) in
  let a' = Array.make_matrix dim2 dim1 a.(0).(0) in
  for i1 = 0 to pred dim1 do
    for i2 = 0 to pred dim2 do
      a'.(i2).(i1) ← a.(i1).(i2)
    done
  done;
  a'

let compress2 a =
  let c2 = compress a in
  let c12_transposed = compress (transpose c2.uniq) in
  { uniq2 = transpose c12_transposed.uniq;

```

```
    embedding1 = c12_transposed.embedding;  
    embedding2 = c2.embedding }  
let uncompress2 a =  
  let a2 = uncompress { uniq = a.uniq2; embedding = a.embedding2 } in  
  transpose (uncompress { uniq = transpose a2; embedding = a.embedding1 })
```

— I —

MORE ON STRINGS

I.1 Interface of ThoString

This is a very simple library if stroing manipulation functions missing in O'Caml's standard library.

strip_prefix prefix string returns *string* with 0 or 1 occurences of a leading *prefix* removed.

```
val strip_prefix : string → string → string
```

strip_prefix_star prefix string returns *string* with any number of leading ocurences of *prefix* removed.

```
val strip_prefix_star : char → string → string
```

strip_prefix prefix string returns *string* with a leading *prefix* removed, raises *Invalid_argument* if there's no match.

```
val strip_required_prefix : string → string → string
```

strip_from_first c s returns *s* with everything starting from the first *c* removed.
strip_from_last c s returns *s* with everything starting from the last *c* removed.

```
val strip_from_first : char → string → string
```

```
val strip_from_last : char → string → string
```

index_string pattern string returns the index of the first occurence of *pattern* in *string*, if any. Raises *Not_found*, if *pattern* is not in *string*.

```
val index_string : string → string → int
```

This silently fails if the argument contains both single and double quotes!

```
val quote : string → string
```

I.2 Implementation of ThoString

```
let strip_prefix p s =  
  let lp = String.length p  
  and ls = String.length s in  
  if lp > ls then  
    s
```



```

else
  let rec strip_prefix' i =
    if i ≥ lp then
      String.sub s i (ls - i)
    else if p.[i] ≠ s.[i] then
      s
    else
      strip_prefix' (succ i)
  in
  strip_prefix' 0
let strip_prefix_star p s =
  let ls = String.length s in
  if ls < 1 then
    s
  else
    let rec strip_prefix_star' i =
      if i < ls then begin
        if p ≠ s.[i] then
          String.sub s i (ls - i)
        else
          strip_prefix_star' (succ i)
      end else
        ""
    in
    strip_prefix_star' 0
let strip_required_prefix p s =
  let lp = String.length p
  and ls = String.length s in
  if lp > ls then
    invalid_arg ("strip_required_prefix:␣expected␣'" ^ p ^ "'␣got␣'" ^ s ^ "'")
  else
    let rec strip_prefix' i =
      if i ≥ lp then
        String.sub s i (ls - i)
      else if p.[i] ≠ s.[i] then
        invalid_arg ("strip_required_prefix:␣expected␣'" ^ p ^ "'␣got␣'" ^ s ^ "'")
      else
        strip_prefix' (succ i)
    in
    strip_prefix' 0
let strip_from_first c s =
  try
    String.sub s 0 (String.index s c)
  with
  | Not_found → s
let strip_from_last c s =
  try
    String.sub s 0 (String.rindex s c)

```

```

with
| Not_found → s

let index_string pat s =
  let lpat = String.length pat
  and ls = String.length s in
  if lpat = 0 then
    0
  else
    let rec index_string' n =
      let i = String.index_from s n pat.[0] in
      if i + lpat > ls then
        raise Not_found
      else
        if String.compare pat (String.sub s i lpat) = 0 then
          i
        else
          index_string' (succ i)
    in
    index_string' 0

let quote s =
  if String.contains s ' ' ∨ String.contains s '\n' then begin
    if String.contains s '"' then
      "\"" ^ s ^ "\""
    else
      "\"\" ^ s ^ "\""
  end else
    s

```

—J—

POLYMORPHIC MAPS

From [9].

J.1 Interface of Pmap

Module *Pmap*: association tables over a polymorphic type¹.

module type *T* =

```
sig
  type ('key, α) t
  val empty : ('key, α) t
  val is_empty : ('key, α) t → bool
  val singleton : 'key → α → ('key, α) t
  val add : ('key → 'key → int) → 'key → α → ('key, α) t →
    ('key, α) t
  val update : ('key → 'key → int) → (α → α → α) →
    'key → α → ('key, α) t → ('key, α) t
  val cons : ('key → 'key → int) → (α → α → α option) →
    'key → α → ('key, α) t → ('key, α) t
  val find : ('key → 'key → int) → 'key → ('key, α) t → α
  val find_opt : ('key → 'key → int) → 'key → ('key, α) t → α option
  val choose : ('key, α) t → 'key × α
  val choose_opt : ('key, α) t → ('key × α) option
  val uncons : ('key, α) t → 'key × α × ('key, α) t
  val uncons_opt : ('key, α) t → ('key × α × ('key, α) t) option
  val elements : ('key, α) t → ('key × α) list
  val mem : ('key → 'key → int) → 'key → ('key, α) t → bool
  val remove : ('key → 'key → int) → 'key → ('key, α) t → ('key, α) t
  val union : ('key → 'key → int) → (α → α → α) →
    ('key, α) t → ('key, α) t → ('key, α) t
  val compose : ('key → 'key → int) → (α → α → α option) →
    ('key, α) t → ('key, α) t → ('key, α) t
  val iter : ('key → α → unit) → ('key, α) t → unit
  val map : (α → β) → ('key, α) t → ('key, β) t
  val mapi : ('key → α → β) → ('key, α) t → ('key, β) t
  val fold : ('key → α → β → β) → ('key, α) t → β → β
```

¹Extension of code © 1996 by Xavier Leroy

```

    val compare : ('key → 'key → int) → (α → α → int) →
      ('key, α) t → ('key, α) t → int
    val canonicalize : ('key → 'key → int) → ('key, α) t → ('key, α) t
  end

```

Balanced trees: logarithmic access, but representation not unique.

```
module Tree : T
```

Sorted lists: representation unique, but linear access.

```
module List : T
```

J.2 Implementation of Pmap

```
module type T =
```

```

  sig
    type ('key, α) t
    val empty : ('key, α) t
    val is_empty : ('key, α) t → bool
    val singleton : 'key → α → ('key, α) t
    val add : ('key → 'key → int) → 'key → α → ('key, α) t →
      ('key, α) t
    val update : ('key → 'key → int) → (α → α → α) →
      'key → α → ('key, α) t → ('key, α) t
    val cons : ('key → 'key → int) → (α → α → α option) →
      'key → α → ('key, α) t → ('key, α) t
    val find : ('key → 'key → int) → 'key → ('key, α) t → α
    val find_opt : ('key → 'key → int) → 'key → ('key, α) t → α option
    val choose : ('key, α) t → 'key × α
    val choose_opt : ('key, α) t → ('key × α) option
    val uncons : ('key, α) t → 'key × α × ('key, α) t
    val uncons_opt : ('key, α) t → ('key × α × ('key, α) t) option
    val elements : ('key, α) t → ('key × α) list
    val mem : ('key → 'key → int) → 'key → ('key, α) t → bool
    val remove : ('key → 'key → int) → 'key → ('key, α) t → ('key, α) t
    val union : ('key → 'key → int) → (α → α → α) →
      ('key, α) t → ('key, α) t → ('key, α) t
    val compose : ('key → 'key → int) → (α → α → α option) →
      ('key, α) t → ('key, α) t → ('key, α) t
    val iter : ('key → 'key → unit) → ('key, α) t → unit
    val map : (α → β) → ('key, α) t → ('key, β) t
    val mapi : ('key → α → β) → ('key, α) t → ('key, β) t
    val fold : ('key → α → β → β) → ('key, α) t → β → β
    val compare : ('key → 'key → int) → (α → α → int) →
      ('key, α) t → ('key, α) t → int
    val canonicalize : ('key → 'key → int) → ('key, α) t → ('key, α) t
  end

```

```
module Tree =
```

```
  struct
```

```

type ('key,  $\alpha$ ) t =
| Empty
| Node of ('key,  $\alpha$ ) t  $\times$  'key  $\times$   $\alpha$   $\times$  ('key,  $\alpha$ ) t  $\times$  int

let empty = Empty

let is_empty = function
| Empty  $\rightarrow$  true
| _  $\rightarrow$  false

let singleton k d =
Node (Empty, k, d, Empty, 1)

let height = function
| Empty  $\rightarrow$  0
| Node (_, _, _, _, h)  $\rightarrow$  h

let create l x d r =
let hl = height l and hr = height r in
Node (l, x, d, r, (if hl  $\geq$  hr then hl + 1 else hr + 1))

let bal l x d r =
let hl = match l with Empty  $\rightarrow$  0 | Node (_, _, _, _, h)  $\rightarrow$  h in
let hr = match r with Empty  $\rightarrow$  0 | Node (_, _, _, _, h)  $\rightarrow$  h in
if hl > hr + 2 then begin
match l with
| Empty  $\rightarrow$  invalid_arg "Map.bal"
| Node (ll, lv, ld, lr, _)  $\rightarrow$ 
if height ll  $\geq$  height lr then
create ll lv ld (create lr x d r)
else begin
match lr with
| Empty  $\rightarrow$  invalid_arg "Map.bal"
| Node (lrl, lrv, lrd, lrr, _)  $\rightarrow$ 
create (create ll lv ld lrl) lrv lrd (create lrr x d r)
end
end else if hr > hl + 2 then begin
match r with
| Empty  $\rightarrow$  invalid_arg "Map.bal"
| Node (rl, rv, rd, rr, _)  $\rightarrow$ 
if height rr  $\geq$  height rl then
create (create l x d rl) rv rd rr
else begin
match rl with
| Empty  $\rightarrow$  invalid_arg "Map.bal"
| Node (rll, rlv, rld, rlr, _)  $\rightarrow$ 
create (create l x d rll) rlv rld (create rlr rv rd rr)
end
end else
Node (l, x, d, r, (if hl  $\geq$  hr then hl + 1 else hr + 1))

let rec join l x d r =
match bal l x d r with
| Empty  $\rightarrow$  invalid_arg "Pmap.join"

```

```

| Node (l', x', d', r', _) as t' →
  let d = height l' - height r' in
  if d < -2 ∨ d > 2 then
    join l' x' d' r'
  else
    t'

```

Merge two trees *t1* and *t2* into one. All elements of *t1* must precede the elements of *t2*. Assumes $\text{height } t1 - \text{height } t2 \leq 2$.

```

let rec merge t1 t2 =
  match t1, t2 with
  | Empty, t → t
  | t, Empty → t
  | Node (l1, v1, d1, r1, h1), Node (l2, v2, d2, r2, h2) →
    bal l1 v1 d1 (bal (merge r1 l2) v2 d2 r2)

```

Same as merge, but does not assume anything about *t1* and *t2*.

```

let rec concat t1 t2 =
  match t1, t2 with
  | Empty, t → t
  | t, Empty → t
  | Node (l1, v1, d1, r1, h1), Node (l2, v2, d2, r2, h2) →
    join l1 v1 d1 (join (concat r1 l2) v2 d2 r2)

```

Splitting

```

let rec split cmp x = function
| Empty → (Empty, None, Empty)
| Node (l, v, d, r, _) →
  let c = cmp x v in
  if c = 0 then
    (l, Some d, r)
  else if c < 0 then
    let ll, vl, rl = split cmp x l in
    (ll, vl, join rl v d r)
  else (* if c > 0 then *)
    let lr, vr, rr = split cmp x r in
    (join l v d lr, vr, rr)

let rec find cmp x = function
| Empty → raise Not_found
| Node (l, v, d, r, _) →
  let c = cmp x v in
  if c = 0 then
    d
  else if c < 0 then
    find cmp x l
  else (* if c > 0 *)
    find cmp x r

let rec find_opt cmp x = function
| Empty → None

```

```

| Node (l, v, d, r, _) →
  let c = cmp x v in
  if c = 0 then
    Some d
  else if c < 0 then
    find_opt cmp x l
  else (* if c > 0 *)
    find_opt cmp x r

let rec mem cmp x = function
| Empty → false
| Node (l, v, d, r, _) →
  let c = cmp x v in
  if c = 0 then
    true
  else if c < 0 then
    mem cmp x l
  else (* if c > 0 *)
    mem cmp x r

let choose = function
| Empty → raise Not_found
| Node (l, v, d, r, _) → (v, d)

let choose_opt = function
| Empty → None
| Node (l, v, d, r, _) → Some (v, d)

let uncons = function
| Empty → raise Not_found
| Node (l, v, d, r, h) → (v, d, merge l r)

let uncons_opt = function
| Empty → None
| Node (l, v, d, r, h) → Some (v, d, merge l r)

let rec remove cmp x = function
| Empty → Empty
| Node (l, v, d, r, h) →
  let c = cmp x v in
  if c = 0 then
    merge l r
  else if c < 0 then
    bal (remove cmp x l) v d r
  else (* if c > 0 *)
    bal l v d (remove cmp x r)

let rec cons cmp resolve x data' = function
| Empty → Node (Empty, x, data', Empty, 1)
| Node (l, v, data, r, h) →
  let c = cmp x v in
  if c = 0 then
    match resolve data' data with
    | Some data'' → Node (l, x, data'', r, h)

```

```

    | None → merge l r
  else if c < 0 then
    bal (cons cmp resolve x data' l) v data r
  else (* if c > 0 *)
    bal l v data (cons cmp resolve x data' r)
let rec update cmp resolve x data' = function
  | Empty → Node (Empty, x, data', Empty, 1)
  | Node (l, v, data, r, h) →
    let c = cmp x v in
    if c = 0 then
      Node (l, x, resolve data' data, r, h)
    else if c < 0 then
      bal (update cmp resolve x data' l) v data r
    else (* if c > 0 *)
      bal l v data (update cmp resolve x data' r)
let add cmp x data = update cmp (fun n o → n) x data
let rec compose cmp resolve s1 s2 =
  match s1, s2 with
  | Empty, t2 → t2
  | t1, Empty → t1
  | Node (l1, v1, d1, r1, h1), Node (l2, v2, d2, r2, h2) →
    if h1 ≥ h2 then
      if h2 = 1 then
        cons cmp (fun o n → resolve n o) v2 d2 s1
      else begin
        match split cmp v1 s2 with
        | l2', None, r2' →
          join (compose cmp resolve l1 l2') v1 d1
            (compose cmp resolve r1 r2')
        | l2', Some d, r2' →
          begin match resolve d1 d with
          | None →
            concat (compose cmp resolve l1 l2')
              (compose cmp resolve r1 r2')
          | Some d →
            join (compose cmp resolve l1 l2') v1 d
              (compose cmp resolve r1 r2')
          end
        end
      end
    else
      if h1 = 1 then
        cons cmp resolve v1 d1 s2
      else begin
        match split cmp v2 s1 with
        | l1', None, r1' →
          join (compose cmp resolve l1' l2) v2 d2
            (compose cmp resolve r1' r2)
        | l1', Some d, r1' →
          begin match resolve d d2 with
          | None →
            concat (compose cmp resolve l1' l2)
              (compose cmp resolve r1' r2)
          | Some d →
            join (compose cmp resolve l1' l2) v2 d
              (compose cmp resolve r1' r2)
          end
        end
      end
    end

```



```

      | None →
        concat (compose cmp resolve l1' l2)
                (compose cmp resolve r1' r2)
      | Some d →
        join (compose cmp resolve l1' l2) v2 d
              (compose cmp resolve r1' r2)
    end
  end

let rec union cmp resolve s1 s2 =
  match s1, s2 with
  | Empty, t2 → t2
  | t1, Empty → t1
  | Node (l1, v1, d1, r1, h1), Node (l2, v2, d2, r2, h2) →
    if h1 ≥ h2 then
      if h2 = 1 then
        update cmp (fun o n → resolve n o) v2 d2 s1
      else begin
        match split cmp v1 s2 with
        | l2', None, r2' →
          join (union cmp resolve l1 l2') v1 d1
              (union cmp resolve r1 r2')
        | l2', Some d, r2' →
          join (union cmp resolve l1 l2') v1 (resolve d1 d)
              (union cmp resolve r1 r2')
        end
      end
    else
      if h1 = 1 then
        update cmp resolve v1 d1 s2
      else begin
        match split cmp v2 s1 with
        | l1', None, r1' →
          join (union cmp resolve l1' l2) v2 d2
              (union cmp resolve r1' r2)
        | l1', Some d, r1' →
          join (union cmp resolve l1' l2) v2 (resolve d d2)
              (union cmp resolve r1' r2)
        end
      end
    end

let rec iter f = function
  | Empty → ()
  | Node (l, v, d, r, _) → iter f l; f v d; iter f r

let rec map f = function
  | Empty → Empty
  | Node (l, v, d, r, h) → Node (map f l, v, f v d, map f r, h)

let rec mapi f = function
  | Empty → Empty
  | Node (l, v, d, r, h) → Node (mapi f l, v, f v d, mapi f r, h)

let rec fold f m accu =

```

```

match m with
| Empty → accu
| Node (l, v, d, r, _) → fold f l (f v d (fold f r accu))

let rec compare' cmp_k cmp_d l1 l2 =
  match l1, l2 with
  | [], [] → 0
  | [], _ → -1
  | _, [] → 1
  | Empty :: t1, Empty :: t2 → compare' cmp_k cmp_d t1 t2
  | Node (Empty, v1, d1, r1, _) :: t1,
    Node (Empty, v2, d2, r2, _) :: t2 →
    let cv = cmp_k v1 v2 in
    if cv ≠ 0 then begin
      cv
    end else begin
      let cd = cmp_d d1 d2 in
      if cd ≠ 0 then
        cd
      else
        compare' cmp_k cmp_d (r1 :: t1) (r2 :: t2)
    end
  | Node (l1, v1, d1, r1, _) :: t1, t2 →
    compare' cmp_k cmp_d (l1 :: Node (Empty, v1, d1, r1, 0) :: t1) t2
  | t1, Node (l2, v2, d2, r2, _) :: t2 →
    compare' cmp_k cmp_d t1 (l2 :: Node (Empty, v2, d2, r2, 0) :: t2)

let compare cmp_k cmp_d m1 m2 = compare' cmp_k cmp_d [m1] [m2]

let rec elements' accu = function
| Empty → accu
| Node (l, v, d, r, _) → elements' ((v, d) :: elements' accu r) l

let elements s =
  elements' [] s

let canonicalize cmp m =
  fold (add cmp) m empty

end

module List =
  struct
    type ('key, α) t = ('key × α) list

    let empty = []

    let is_empty = function
    | [] → true
    | _ → false

    let singleton k d = [(k, d)]

    let rec cons cmp resolve k' d' = function
    | [] → [(k', d')]
    | ((k, d) as kd :: rest) as list →

```

```

    let c = cmp k' k in
    if c = 0 then
      match resolve d' d with
      | None → rest
      | Some d'' → (k', d'') :: rest
    else if c < 0 then (* k' < k *)
      (k', d') :: list
    else (* if c > 0, i.e. k < k' *)
      kd :: cons cmp resolve k' d' rest

let rec update cmp resolve k' d' = function
| [] → [(k', d')]
| ((k, d) as kd :: rest) as list →
  let c = cmp k' k in
  if c = 0 then
    (k', resolve d' d) :: rest
  else if c < 0 then (* k' < k *)
    (k', d') :: list
  else (* if c > 0, i.e. k < k' *)
    kd :: update cmp resolve k' d' rest

let add cmp k' d' list =
  update cmp (fun n o → n) k' d' list

let rec find cmp k' = function
| [] → raise Not_found
| (k, d) :: rest →
  let c = cmp k' k in
  if c = 0 then
    d
  else if c < 0 then (* k' < k *)
    raise Not_found
  else (* if c > 0, i.e. k < k' *)
    find cmp k' rest

let rec find_opt cmp k' = function
| [] → None
| (k, d) :: rest →
  let c = cmp k' k in
  if c = 0 then
    Some d
  else if c < 0 then (* k' < k *)
    None
  else (* if c > 0, i.e. k < k' *)
    find_opt cmp k' rest

let choose = function
| [] → raise Not_found
| kd :: _ → kd

let rec choose_opt = function
| [] → None
| kd :: _ → Some kd

```

```

let uncons = function
| [] → raise Not_found
| (k, d) :: rest → (k, d, rest)

let uncons_opt = function
| [] → None
| (k, d) :: rest → Some (k, d, rest)

let elements list = list

let rec mem cmp k' = function
| [] → false
| (k, d) :: rest →
  let c = cmp k' k in
  if c = 0 then
    true
  else if c < 0 then (* k' < k *)
    false
  else (* if c > 0, i.e. k < k' *)
    mem cmp k' rest

let rec remove cmp k' = function
| [] → []
| ((k, d) as kd :: rest) as list →
  let c = cmp k' k in
  if c = 0 then
    rest
  else if c < 0 then (* k' < k *)
    list
  else (* if c > 0, i.e. k < k' *)
    kd :: remove cmp k' rest

let rec compare cmp_k cmp_d m1 m2 =
  match m1, m2 with
  | [], [] → 0
  | [], _ → -1
  | _, [] → 1
  | (k1, d1) :: rest1, (k2, d2) :: rest2 →
    let c = cmp_k k1 k2 in
    if c = 0 then begin
      let c' = cmp_d d1 d2 in
      if c' = 0 then
        compare cmp_k cmp_d rest1 rest2
      else
        c'
    end else
      c

let rec iter f = function
| [] → ()
| (k, d) :: rest → f k d; iter f rest

let rec map f = function
| [] → []

```

```

| (k, d) :: rest → (k, f d) :: map f rest
let rec mapi f = function
| [] → []
| (k, d) :: rest → (k, f k d) :: mapi f rest
let rec fold f m accu =
  match m with
  | [] → accu
  | (k, d) :: rest → fold f rest (f k d accu)
let rec compose cmp resolve m1 m2 =
  match m1, m2 with
  | [], [] → []
  | [], m → m
  | m, [] → m
  | ((k1, d1) as kd1 :: rest1), ((k2, d2) as kd2 :: rest2) →
    let c = cmp k1 k2 in
    if c = 0 then
      match resolve d1 d2 with
      | None → compose cmp resolve rest1 rest2
      | Some d → (k1, d) :: compose cmp resolve rest1 rest2
    else if c < 0 then (* k1 < k2 *)
      kd1 :: compose cmp resolve rest1 m2
    else (* if c > 0, i.e. k2 < k1 *)
      kd2 :: compose cmp resolve m1 rest2
let rec union cmp resolve m1 m2 =
  match m1, m2 with
  | [], [] → []
  | [], m → m
  | m, [] → m
  | ((k1, d1) as kd1 :: rest1), ((k2, d2) as kd2 :: rest2) →
    let c = cmp k1 k2 in
    if c = 0 then
      (k1, resolve d1 d2) :: union cmp resolve rest1 rest2
    else if c < 0 then (* k1 < k2 *)
      kd1 :: union cmp resolve rest1 m2
    else (* if c > 0, i.e. k2 < k1 *)
      kd2 :: union cmp resolve m1 rest2
let canonicalize cmp x = x
end

```

J.3 Interface of *Partial*

Partial maps that are constructed from assoc lists.

```

module type T =
sig
  type domain
  type α t

```

```

    val of_list : (domain × α) list → α t
    val of_lists : domain list → α list → α t
    val apply : α t → domain → α
end

module Make : functor (D : Map.OrderedType) → T with type domain = D.t
module Test : sig val suite : OUnit.test end

```

J.4 Implementation of *Partial*

```

module type T =
sig
  type domain
  type α t
  val of_list : (domain × α) list → α t
  val of_lists : domain list → α list → α t
  val apply : α t → domain → α
end

module Make (D : Map.OrderedType) : T with type domain = D.t =
struct

  module M = Map.Make (D)

  type domain = D.t
  type α t = α M.t

  let of_list l =
    List.fold_left (fun m (d, v) → M.add d v m) M.empty l

  let of_lists domain values =
    of_list
    (try
      List.rev_map2 (fun d v → (d, v)) domain values
    with
      | Invalid_argument "List.rev_map2" →
        invalid_arg "Partial.of_lists: length mismatch")

  let apply partial d = M.find d partial

end

module Test : sig val suite : OUnit.test end =
struct

  open OUnit

  module P = Make (struct type t = int let compare = compare end)

  let apply_ok =
    "apply/ok" >::
    (fun () →
      let p = P.of_list [ (0, "a"); (1, "b"); (2, "c") ]
      and l = [ 0; 1; 2 ] in
      assert_equal [ "a"; "b"; "c" ] (List.map (P.apply p) l))

```

```
let suite_apply =  
  "apply" >:::  
    [apply_ok]  
let suite =  
  "Partial" >:::  
    [suite_apply]  
let time () =  
  ()  
end
```

—K—

TRIES

From [4], extended for [9].

K.1 Interface of Trie

K.1.1 Monomorphically

```
module type T =  
  sig  
    type key  
    type (+α) t  
    val empty : α t  
    val is_empty : α t → bool
```

Standard trie interface:

```
    val add : key → α → α t → α t  
    val find : key → α t → α
```

Functionals:

```
    val remove : key → α t → α t  
    val mem : key → α t → bool  
    val map : (α → β) → α t → β t  
    val mapi : (key → α → β) → α t → β t  
    val iter : (key → α → unit) → α t → unit  
    val fold : (key → α → β → β) → α t → β → β
```

Try to match a longest prefix and return the unmatched rest.

```
    val longest : key → α t → α option × key
```

Try to match a shortest prefix and return the unmatched rest.

```
    val shortest : key → α t → α option × key
```

K.1.2 New in O’Caml 3.08

```
    val compare : (α → α → int) → α t → α t → int
```



```
val equal : ( $\alpha \rightarrow \alpha \rightarrow \text{bool}$ )  $\rightarrow \alpha t \rightarrow \alpha t \rightarrow \text{bool}$ 
```

K.1.3 O’Mega customization

export f_open f_close f_descend f_match trie allows us to export the trie *trie* as source code to another programming language.

```
val export : ( $\text{int} \rightarrow \text{unit}$ )  $\rightarrow (\text{int} \rightarrow \text{unit}) \rightarrow$   

  ( $\text{int} \rightarrow \text{key} \rightarrow \text{unit}$ )  $\rightarrow (\text{int} \rightarrow \text{key} \rightarrow \alpha \rightarrow \text{unit}) \rightarrow \alpha t \rightarrow \text{unit}$   

end
```

O’Caml’s *Map.S* prior to Version 3.12:

```
module type Map_S =  

sig  

  type key  

  type ( $+\alpha$ ) t  

  val empty :  $\alpha t$   

  val is_empty :  $\alpha t \rightarrow \text{bool}$   

  val add :  $\text{key} \rightarrow \alpha \rightarrow \alpha t \rightarrow \alpha t$   

  val find :  $\text{key} \rightarrow \alpha t \rightarrow \alpha$   

  val remove :  $\text{key} \rightarrow \alpha t \rightarrow \alpha t$   

  val mem :  $\text{key} \rightarrow \alpha t \rightarrow \text{bool}$   

  val iter : ( $\text{key} \rightarrow \alpha \rightarrow \text{unit}$ )  $\rightarrow \alpha t \rightarrow \text{unit}$   

  val map : ( $\alpha \rightarrow \beta$ )  $\rightarrow \alpha t \rightarrow \beta t$   

  val mapi : ( $\text{key} \rightarrow \alpha \rightarrow \beta$ )  $\rightarrow \alpha t \rightarrow \beta t$   

  val fold : ( $\text{key} \rightarrow \alpha \rightarrow \beta \rightarrow \beta$ )  $\rightarrow \alpha t \rightarrow \beta \rightarrow \beta$   

  val compare : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha t \rightarrow \alpha t \rightarrow \text{int}$   

  val equal : ( $\alpha \rightarrow \alpha \rightarrow \text{bool}$ )  $\rightarrow \alpha t \rightarrow \alpha t \rightarrow \text{bool}$   

end  

module Make (M : Map_S) : T with type key = M.key list  

module MakeMap (M : Map_S) : Map_S with type key = M.key list
```

K.1.4 Polymorphically

```
module type Poly =  

sig  

  type ( $\alpha, \beta$ ) t  

  val empty : ( $\alpha, \beta$ ) t
```

Standard trie interface:

```
val add : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha \text{ list} \rightarrow \beta \rightarrow (\alpha, \beta) t \rightarrow (\alpha, \beta) t$   

val find : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha \text{ list} \rightarrow (\alpha, \beta) t \rightarrow \beta$ 
```

Functionals:

```
val remove : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha \text{ list} \rightarrow (\alpha, \beta) t \rightarrow (\alpha, \beta) t$   

val mem : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha \text{ list} \rightarrow (\alpha, \beta) t \rightarrow \text{bool}$ 
```

```

val map : ( $\beta \rightarrow \gamma$ )  $\rightarrow$  ( $\alpha, \beta$ )  $t \rightarrow$  ( $\alpha, \gamma$ )  $t$ 
val mapi : ( $\alpha \text{ list} \rightarrow \beta \rightarrow \gamma$ )  $\rightarrow$  ( $\alpha, \beta$ )  $t \rightarrow$  ( $\alpha, \gamma$ )  $t$ 
val iter : ( $\alpha \text{ list} \rightarrow \beta \rightarrow \text{unit}$ )  $\rightarrow$  ( $\alpha, \beta$ )  $t \rightarrow \text{unit}$ 
val fold : ( $\alpha \text{ list} \rightarrow \beta \rightarrow \gamma \rightarrow \gamma$ )  $\rightarrow$  ( $\alpha, \beta$ )  $t \rightarrow \gamma \rightarrow \gamma$ 

```

Try to match a longest prefix and return the unmatched rest.

```

val longest : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow$   $\alpha \text{ list} \rightarrow$  ( $\alpha, \beta$ )  $t \rightarrow \beta \text{ option} \times \alpha \text{ list}$ 

```

Try to match a shortest prefix and return the unmatched rest.

```

val shortest : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow$   $\alpha \text{ list} \rightarrow$  ( $\alpha, \beta$ )  $t \rightarrow \beta \text{ option} \times \alpha \text{ list}$ 

```

K.1.5 O'Mega customization

export f_open f_close f_descend f_match trie allows us to export the trie *trie* as source code to another programming language.

```

val export : ( $\text{int} \rightarrow \text{unit}$ )  $\rightarrow$  ( $\text{int} \rightarrow \text{unit}$ )  $\rightarrow$ 
  ( $\text{int} \rightarrow \alpha \text{ list} \rightarrow \text{unit}$ )  $\rightarrow$  ( $\text{int} \rightarrow \alpha \text{ list} \rightarrow \beta \rightarrow \text{unit}$ )  $\rightarrow$  ( $\alpha, \beta$ )  $t \rightarrow$ 
   $\text{unit}$ 
end
module MakePoly (M : Pmap.T) : Poly

```

K.2 Implementation of *Trie*

K.2.1 Monomorphically

```

module type T =
sig
  type key
  type (+ $\alpha$ )  $t$ 
  val empty :  $\alpha t$ 
  val is_empty :  $\alpha t \rightarrow \text{bool}$ 
  val add :  $\text{key} \rightarrow \alpha \rightarrow \alpha t \rightarrow \alpha t$ 
  val find :  $\text{key} \rightarrow \alpha t \rightarrow \alpha$ 
  val remove :  $\text{key} \rightarrow \alpha t \rightarrow \alpha t$ 
  val mem :  $\text{key} \rightarrow \alpha t \rightarrow \text{bool}$ 
  val map : ( $\alpha \rightarrow \beta$ )  $\rightarrow \alpha t \rightarrow \beta t$ 
  val mapi : ( $\text{key} \rightarrow \alpha \rightarrow \beta$ )  $\rightarrow \alpha t \rightarrow \beta t$ 
  val iter : ( $\text{key} \rightarrow \alpha \rightarrow \text{unit}$ )  $\rightarrow \alpha t \rightarrow \text{unit}$ 
  val fold : ( $\text{key} \rightarrow \alpha \rightarrow \beta \rightarrow \beta$ )  $\rightarrow \alpha t \rightarrow \beta \rightarrow \beta$ 
  val longest :  $\text{key} \rightarrow \alpha t \rightarrow \alpha \text{ option} \times \text{key}$ 
  val shortest :  $\text{key} \rightarrow \alpha t \rightarrow \alpha \text{ option} \times \text{key}$ 
  val compare : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow \alpha t \rightarrow \alpha t \rightarrow \text{int}$ 
  val equal : ( $\alpha \rightarrow \alpha \rightarrow \text{bool}$ )  $\rightarrow \alpha t \rightarrow \alpha t \rightarrow \text{bool}$ 
  val export : ( $\text{int} \rightarrow \text{unit}$ )  $\rightarrow$  ( $\text{int} \rightarrow \text{unit}$ )  $\rightarrow$ 
    ( $\text{int} \rightarrow \text{key} \rightarrow \text{unit}$ )  $\rightarrow$  ( $\text{int} \rightarrow \text{key} \rightarrow \alpha \rightarrow \text{unit}$ )  $\rightarrow \alpha t \rightarrow \text{unit}$ 
end

```

O’Caml’s *Map.S* prior to Version 3.12:

```

module type Map_S =
sig
  type key
  type (+α) t
  val empty : α t
  val is_empty : α t → bool
  val add : key → α → α t → α t
  val find : key → α t → α
  val remove : key → α t → α t
  val mem : key → α t → bool
  val iter : (key → α → unit) → α t → unit
  val map : (α → β) → α t → β t
  val mapi : (key → α → β) → α t → β t
  val fold : (key → α → β → β) → α t → β → β
  val compare : (α → α → int) → α t → α t → int
  val equal : (α → α → bool) → α t → α t → bool
end

module Make (M : Map_S) : (T with type key = M.key list) =
struct

```

Derived from SML code by Chris Okasaki [4].

```

  type key = M.key list
  type α t = Trie of α option × α t M.t
  let empty = Trie (None, M.empty)
  let is_empty = function
    | Trie (None, m) →
      m = M.empty (* after O’Caml 3.08: M.is_empty m *)
    | _ → false
  let rec add key data trie =
    match key, trie with
    | [], Trie (_, children) → Trie (Some data, children)
    | k :: rest, Trie (node, children) →
      let t = try M.find k children with Not_found → empty in
      Trie (node, M.add k (add rest data t) children)
  let rec find key trie =
    match key, trie with
    | [], Trie (None, _) → raise Not_found
    | [], Trie (Some data, _) → data
    | k :: rest, Trie (_, children) → find rest (M.find k children)

```

The rest is my own fault ...

```

  let find1 k children =
    try Some (M.find k children) with Not_found → None
  let add_non_empty k t children =
    if t = empty then

```

```

    M.remove k children
  else
    M.add k t children

let rec remove key trie =
  match key, trie with
  | [], Trie (_, children) → Trie (None, children)
  | k :: rest, (Trie (node, children) as orig) →
    match find1 k children with
    | None → orig
    | Some t → Trie (node, add_non_empty k (remove rest t) children)

let rec mem key trie =
  match key, trie with
  | [], Trie (None, _) → false
  | [], Trie (Some data, _) → true
  | k :: rest, Trie (_, children) →
    match find1 k children with
    | None → false
    | Some t → mem rest t

let rec map f = function
  | Trie (Some data, children) →
    Trie (Some (f data), M.map (map f) children)
  | Trie (None, children) → Trie (None, M.map (map f) children)

let rec mapi' key f = function
  | Trie (Some data, children) →
    Trie (Some (f key data), descend key f children)
  | Trie (None, children) → Trie (None, descend key f children)
and descend key f = M.mapi (fun k → mapi' (key @ [k]) f)
let mapi f = mapi' [] f

let rec iter' key f = function
  | Trie (Some data, children) → f key data; descend key f children
  | Trie (None, children) → descend key f children
and descend key f = M.iter (fun k → iter' (key @ [k]) f)
let iter f = iter' [] f

let rec fold' key f t acc =
  match t with
  | Trie (Some data, children) → descend key f children (f key data acc)
  | Trie (None, children) → descend key f children acc
and descend key f = M.fold (fun k → fold' (key @ [k]) f)
let fold f t acc = fold' [] f t acc

let rec longest' partial partial_rest key trie =
  match key, trie with
  | [], Trie (data, _) → (data, [])
  | k :: rest, Trie (data, children) →
    match data, find1 k children with
    | None, None → (partial, partial_rest)
    | Some _, None → (data, key)
    | _, Some t → longest' partial partial_rest rest t

```

```

let longest key = longest' None key key
let rec shortest' partial partial_rest key trie =
  match key, trie with
  | [], Trie (data, _) → (data, [])
  | k :: rest, Trie (Some _ as data, children) → (data, key)
  | k :: rest, Trie (None, children) →
    match find1 k children with
    | None → (partial, partial_rest)
    | Some t → shortest' partial partial_rest rest t
let shortest key = shortest' None key key

```

K.2.2 O'Mega customization

```

let rec export' n key f_open f_close f_descend f_match = function
| Trie (Some data, children) →
  f_match n key data;
  if children ≠ M.empty then
    descend n key f_open f_close f_descend f_match children
| Trie (None, children) →
  if children ≠ M.empty then begin
    f_descend n key;
    descend n key f_open f_close f_descend f_match children
  end
and descend n key f_open f_close f_descend f_match children =
  f_open n;
  M.iter (fun k →
    export' (succ n) (k :: key) f_open f_close f_descend f_match) children;
  f_close n

let export f_open f_close f_descend f_match =
  export' 0 [] f_open f_close f_descend f_match

let compare _ _ _ =
  failwith "incomplete"

let equal _ _ _ =
  failwith "incomplete"

end

module MakeMap (M : Map_S) : (Map_S with type key = M.key list) = Make(M)

```

K.2.3 Polymorphically

```

module type Poly =
sig
  type (α, β) t
  val empty : (α, β) t

```

```

val add : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow$   $\alpha$  list  $\rightarrow$   $\beta \rightarrow (\alpha, \beta) t \rightarrow (\alpha, \beta) t$ 
val find : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow$   $\alpha$  list  $\rightarrow (\alpha, \beta) t \rightarrow \beta$ 
val remove : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow$   $\alpha$  list  $\rightarrow (\alpha, \beta) t \rightarrow (\alpha, \beta) t$ 
val mem : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow$   $\alpha$  list  $\rightarrow (\alpha, \beta) t \rightarrow \text{bool}$ 
val map : ( $\beta \rightarrow \gamma$ )  $\rightarrow (\alpha, \beta) t \rightarrow (\alpha, \gamma) t$ 
val mapi : ( $\alpha$  list  $\rightarrow \beta \rightarrow \gamma$ )  $\rightarrow (\alpha, \beta) t \rightarrow (\alpha, \gamma) t$ 
val iter : ( $\alpha$  list  $\rightarrow \beta \rightarrow \text{unit}$ )  $\rightarrow (\alpha, \beta) t \rightarrow \text{unit}$ 
val fold : ( $\alpha$  list  $\rightarrow \beta \rightarrow \gamma \rightarrow \gamma$ )  $\rightarrow (\alpha, \beta) t \rightarrow \gamma \rightarrow \gamma$ 
val longest : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow$   $\alpha$  list  $\rightarrow (\alpha, \beta) t \rightarrow \beta \text{ option} \times \alpha$  list
val shortest : ( $\alpha \rightarrow \alpha \rightarrow \text{int}$ )  $\rightarrow$   $\alpha$  list  $\rightarrow (\alpha, \beta) t \rightarrow \beta \text{ option} \times \alpha$  list
val export : ( $\text{int} \rightarrow \text{unit}$ )  $\rightarrow (\text{int} \rightarrow \text{unit}) \rightarrow$ 
  ( $\text{int} \rightarrow \alpha$  list  $\rightarrow \text{unit}$ )  $\rightarrow (\text{int} \rightarrow \alpha$  list  $\rightarrow \beta \rightarrow \text{unit}) \rightarrow (\alpha, \beta) t \rightarrow$ 
  unit
end

module MakePoly (M : Pmap.T) : Poly =
  struct

```

Derived from SML code by Chris Okasaki [4].

```

type ( $\alpha, \beta$ ) t = Trie of  $\beta \text{ option} \times (\alpha, (\alpha, \beta) t) M.t$ 

let empty = Trie (None, M.empty)

let rec add cmp key data trie =
  match key, trie with
  | [], Trie (_, children)  $\rightarrow$  Trie (Some data, children)
  | k :: rest, Trie (node, children)  $\rightarrow$ 
    let t = try M.find cmp k children with Not_found  $\rightarrow$  empty in
    Trie (node, M.add cmp k (add cmp rest data t) children)

let rec find cmp key trie =
  match key, trie with
  | [], Trie (None, _)  $\rightarrow$  raise Not_found
  | [], Trie (Some data, _)  $\rightarrow$  data
  | k :: rest, Trie (_, children)  $\rightarrow$  find cmp rest (M.find cmp k children)

```

The rest is my own fault ...

```

let find1 cmp k children =
  try Some (M.find cmp k children) with Not_found  $\rightarrow$  None

let add_non_empty cmp k t children =
  if t = empty then
    M.remove cmp k children
  else
    M.add cmp k t children

let rec remove cmp key trie =
  match key, trie with
  | [], Trie (_, children)  $\rightarrow$  Trie (None, children)
  | k :: rest, (Trie (node, children) as orig)  $\rightarrow$ 
    match find1 cmp k children with
    | None  $\rightarrow$  orig
    | Some t  $\rightarrow$  Trie (node, add_non_empty cmp k (remove cmp rest t) children)

```

```

let rec mem cmp key trie =
  match key, trie with
  | [], Trie (None, _) → false
  | [], Trie (Some data, _) → true
  | k :: rest, Trie (_, children) →
    match find1 cmp k children with
    | None → false
    | Some t → mem cmp rest t

let rec map f = function
  | Trie (Some data, children) →
    Trie (Some (f data), M.map (map f) children)
  | Trie (None, children) → Trie (None, M.map (map f) children)

let rec mapi' key f = function
  | Trie (Some data, children) →
    Trie (Some (f key data), descend key f children)
  | Trie (None, children) → Trie (None, descend key f children)
and descend key f = M.mapi (fun k → mapi' (key @ [k]) f)
let mapi f = mapi' [] f

let rec iter' key f = function
  | Trie (Some data, children) → f key data; descend key f children
  | Trie (None, children) → descend key f children
and descend key f = M.iter (fun k → iter' (key @ [k]) f)
let iter f = iter' [] f

let rec fold' key f t acc =
  match t with
  | Trie (Some data, children) → descend key f children (f key data acc)
  | Trie (None, children) → descend key f children acc
and descend key f = M.fold (fun k → fold' (key @ [k]) f)
let fold f t acc = fold' [] f t acc

let rec longest' cmp partial partial_rest key trie =
  match key, trie with
  | [], Trie (data, _) → (data, [])
  | k :: rest, Trie (data, children) →
    match data, find1 cmp k children with
    | None, None → (partial, partial_rest)
    | Some _, None → (data, key)
    | _, Some t → longest' cmp partial partial_rest rest t
let longest cmp key = longest' cmp None key key

let rec shortest' cmp partial partial_rest key trie =
  match key, trie with
  | [], Trie (data, _) → (data, [])
  | k :: rest, Trie (Some _ as data, children) → (data, key)
  | k :: rest, Trie (None, children) →
    match find1 cmp k children with
    | None → (partial, partial_rest)
    | Some t → shortest' cmp partial partial_rest rest t
let shortest cmp key = shortest' cmp None key key

```

K.2.4 O'Mega customization

```

let rec export' n key f_open f_close f_descend f_match = function
| Trie (Some data, children) →
    f_match n key data;
    if children ≠ M.empty then
        descend n key f_open f_close f_descend f_match children
| Trie (None, children) →
    if children ≠ M.empty then begin
        f_descend n key;
        descend n key f_open f_close f_descend f_match children
    end
and descend n key f_open f_close f_descend f_match children =
    f_open n;
    M.iter (fun k →
        export' (succ n) (k :: key) f_open f_close f_descend f_match) children;
    f_close n

let export f_open f_close f_descend f_match =
    export' 0 [] f_open f_close f_descend f_match
end

```

—L—

TENSOR PRODUCTS

From [9].

L.1 Interface of Product

L.1.1 Lists

Since April 2001, we preserve lexicographic ordering.

```
val fold2 : ( $\alpha \rightarrow \beta \rightarrow \gamma \rightarrow \gamma$ )  $\rightarrow \alpha$  list  $\rightarrow \beta$  list  $\rightarrow \gamma \rightarrow \gamma$ 
val fold3 : ( $\alpha \rightarrow \beta \rightarrow \gamma \rightarrow \delta \rightarrow \delta$ )  $\rightarrow \alpha$  list  $\rightarrow \beta$  list  $\rightarrow \gamma$  list  $\rightarrow \delta \rightarrow \delta$ 
val fold : ( $\alpha$  list  $\rightarrow \beta \rightarrow \beta$ )  $\rightarrow \alpha$  list list  $\rightarrow \beta \rightarrow \beta$ 

val list2 : ( $\alpha \rightarrow \beta \rightarrow \gamma$ )  $\rightarrow \alpha$  list  $\rightarrow \beta$  list  $\rightarrow \gamma$  list
val list3 : ( $\alpha \rightarrow \beta \rightarrow \gamma \rightarrow \delta$ )  $\rightarrow \alpha$  list  $\rightarrow \beta$  list  $\rightarrow \gamma$  list  $\rightarrow \delta$  list
val list : ( $\alpha$  list  $\rightarrow \beta$ )  $\rightarrow \alpha$  list list  $\rightarrow \beta$  list

val power : int  $\rightarrow \alpha$  list  $\rightarrow \alpha$  list list
val thread :  $\alpha$  list list  $\rightarrow \alpha$  list list
```

L.1.2 Sets

'a_set is actually α set for a suitable *set*, but this relation can not be expressed polymorphically (in *set*) in O'Caml. The two sets can be of different type, but we provide a symmetric version as syntactic sugar.

type α set

```
type ( $\alpha$ , 'a_set,  $\beta$ ) fold = ( $\alpha \rightarrow \beta \rightarrow \beta$ )  $\rightarrow$  'a_set  $\rightarrow \beta \rightarrow \beta$ 
```

```
type ( $\alpha$ , 'a_set,  $\beta$ , 'b_set,  $\gamma$ ) fold2 =
  ( $\alpha \rightarrow \beta \rightarrow \gamma \rightarrow \gamma$ )  $\rightarrow$  'a_set  $\rightarrow$  'b_set  $\rightarrow \gamma \rightarrow \gamma$ 
```

```
val outer : ( $\alpha$ , 'a_set,  $\gamma$ ) fold  $\rightarrow$  ( $\beta$ , 'b_set,  $\gamma$ ) fold  $\rightarrow$ 
```

```
  ( $\alpha$ , 'a_set,  $\beta$ , 'b_set,  $\gamma$ ) fold2
```

```
val outer_self : ( $\alpha$ , 'a_set,  $\beta$ ) fold  $\rightarrow$  ( $\alpha$ , 'a_set,  $\alpha$ , 'a_set,  $\beta$ ) fold2
```

L.2 Implementation of *Product*

L.2.1 Lists

We use the tail recursive *List.fold_left* over *List.fold_right* for efficiency, but revert the argument lists in order to preserve lexicographic ordering. The argument lists are much shorter than the results, so the cost of the *List.rev* is negligible.

```
let fold2_rev f l1 l2 acc =
  List.fold_left (fun acc1 x1 →
    List.fold_left (fun acc2 x2 → f x1 x2 acc2) acc1 l2) acc l1
```

```
let fold2 f l1 l2 acc =
  fold2_rev f (List.rev l1) (List.rev l2) acc
```

```
let fold3_rev f l1 l2 l3 acc =
  List.fold_left (fun acc1 x1 → fold2 (f x1) l2 l3 acc1) acc l1
```

```
let fold3 f l1 l2 l3 acc =
  fold3_rev f (List.rev l1) (List.rev l2) (List.rev l3) acc
```

If all lists have the same type, there's also

```
let rec fold_rev f ll acc =
  match ll with
  | [] → acc
  | [l] → List.fold_left (fun acc' x → f [x] acc') acc l
  | l :: rest →
    List.fold_left (fun acc' x → fold_rev (fun xr → f (x :: xr)) rest acc') acc l
```

```
let fold f ll acc = fold_rev f (List.map List.rev ll) acc
```

```
let list2 op l1 l2 =
  fold2 (fun x1 x2 c → op x1 x2 :: c) l1 l2 []
```


```
let list3 op l1 l2 l3 =
  fold3 (fun x1 x2 x3 c → op x1 x2 x3 :: c) l1 l2 l3 []
```

```
let list op ll =
  fold (fun l c → op l :: c) ll []
```

```
let power n l =
  list (fun x → x) (ThoList.clone n l)
```

Reshuffling lists:

$$[[a_1; \dots; a_k]; [b_1; \dots; b_k]; [c_1; \dots; c_k]; \dots] \rightarrow [[a_1; b_1; c_1; \dots]; [a_2; b_2; c_2; \dots]; \dots] \quad (\text{L.1})$$

 *tho* : Is this really an optimal implementation?

```
let thread = function
  | head :: tail →
    List.map List.rev
    (List.fold_left (fun i acc → List.map2 (fun a b → b :: a) i acc)
```

```

      (List.map (fun i → [i]) head) tail)
| [] → []

```

L.2.2 Sets

The implementation is amazingly simple:

```
type α set
```

```
type (α, 'a_set, β) fold = (α → β → β) → 'a_set → β → β
```

```
type (α, 'a_set, β, 'b_set, γ) fold2 =
  (α → β → γ → γ) → 'a_set → 'b_set → γ → γ
```

```
let outer fold1 fold2 f l1 l2 = fold1 (fun x1 → fold2 (f x1) l2) l1
```

```
let outer_self fold f l1 l2 = fold (fun x1 → fold (f x1) l2) l1
```

—M—

(FIBER) BUNDLES

M.1 Interface of Bundle

See figure [M.1](#) for the geometric intuition behind the bundle structure.



Does the current implementation support faithful projections with a forgetful comparison in the base?

```
module type Elt_Base =  
  sig  
    type elt  
    type base  
    val compare_elt : elt → elt → int
```




Figure M.1: The bundle structure implemented by *Bundle.T*

```

    val compare_base : base → base → int
  end
module type Projection =
sig
  include Elt_Base

   $\pi : E \rightarrow B$ 

  val pi : elt → base
end
module type T =
sig
  type t
  type elt
  type fiber = elt list
  type base

  val add : elt → t → t
  val of_list : elt list → t

   $\pi : E \rightarrow B$ 

  val pi : elt → base

   $\pi^{-1} : B \rightarrow E$ 

  val inv_pi : base → t → fiber

  val base : t → base list

   $\pi^{-1} \circ \pi$ 

  val fiber : elt → t → fiber

  val fibers : t → (base × fiber) list
end
module Make (P : Projection) : T with type elt = P.elt and type base = P.base

```

The same thing again, but with a projection that is not hardcoded, but passed as an argument at runtime.

```

module type Dyn =
sig
  type t
  type elt
  type fiber = elt list
  type base

  val add : (elt → base) → elt → t → t
  val of_list : (elt → base) → elt list → t
  val inv_pi : base → t → fiber
  val base : t → base list
  val fiber : (elt → base) → elt → t → fiber
  val fibers : t → (base × fiber) list
end
module Dyn (P : Elt_Base) : Dyn with type elt = P.elt and type base = P.base

```

M.2 Implementation of Bundle

```

module type Elt_Base =
  sig
    type elt
    type base
    val compare_elt : elt → elt → int
    val compare_base : base → base → int
  end

module type Dyn =
  sig
    type t
    type elt
    type fiber = elt list
    type base
    val add : (elt → base) → elt → t → t
    val of_list : (elt → base) → elt list → t
    val inv_pi : base → t → fiber
    val base : t → base list
    val fiber : (elt → base) → elt → t → fiber
    val fibers : t → (base × fiber) list
  end

module Dyn (P : Elt_Base) =
  struct

    type elt = P.elt
    type base = P.base

    type fiber = elt list

    module InvPi = Map.Make (struct type t = P.base let compare = P.compare_base end)
    module Fiber = Set.Make (struct type t = P.elt let compare = P.compare_elt end)

    type t = Fiber.t InvPi.t

    let add_pi element fibers =
      let base = pi element in
      let fiber =
        try InvPi.find base fibers with Not_found → Fiber.empty in
      InvPi.add base (Fiber.add element fiber) fibers

    let of_list pi list =
      List.fold_right (add_pi) list InvPi.empty

    let fibers bundle =
      InvPi.fold
        (fun base fiber acc → (base, Fiber.elements fiber) :: acc) bundle []

    let base bundle =
      InvPi.fold
        (fun base fiber acc → base :: acc) bundle []

    let inv_pi base bundle =

```

```

      try
        Fiber.elements (InvPi.find base bundle)
      with
      | Not_found → []
    let fiber pi elt bundle =
      inv_pi (pi elt) bundle
  end

module type Projection =
sig
  include Elt_Base
  val pi : elt → base
end

module type T =
sig
  type t
  type elt
  type fiber = elt list
  type base
  val add : elt → t → t
  val of_list : elt list → t
  val pi : elt → base
  val inv_pi : base → t → fiber
  val base : t → base list
  val fiber : elt → t → fiber
  val fibers : t → (base × fiber) list
end

module Make (P : Projection) =
struct
  module D = Dyn (P)

  type elt = D.elt
  type base = D.base
  type fiber = D.fiber
  type t = D.t

  let pi = P.pi

  let add = D.add pi
  let of_list = D.of_list pi
  let base = D.base
  let inv_pi = D.inv_pi
  let fibers = D.fibers

  let fiber elt bundle =
    inv_pi (pi elt) bundle
end

```

—N—

POWER SETS

N.1 Interface of PowSet

Manipulate the power set, i. e. the set of all subsets, of an set *Ordered_Type*. The concrete order is actually irrelevant, we just need it to construct *Set.Ss* in the implementation. In fact, what we are implementating is the *free semilattice* generated from the set of subsets of *Ordered_Type*, where the join operation is the set union.

The non trivial operation is *basis*, which takes a set of subsets and returns the smallest set of disjoint subsets from which the argument can be reconstructed by forming unions. It is used in O’Mega for finding coarsest partitions of sets of partiticles.



Eventually, this could be generalized from *power set* or *semi lattice* to *lattice* with a notion of subtraction.

```
module type Ordered_Type =
  sig
    type t
    val compare : t → t → int

    Debugging ...

    val to_string : t → string
  end
```

```
module type T =
  sig
    type elt
    type t
```

```
    val empty : t
    val is_empty : t → bool
```

Set union (a. k. a. join).

```
    val union : t list → t
```

Construct the abstract type from a list of subsets represented as lists and the inverse operation.

```
    val of_lists : elt list list → t
```



```

    val to_lists : t → elt list list

    The smallest set of disjoint subsets that generates the given subset.

    val basis : t → t

    Debugging ...

    val to_string : t → string
  end

module Make (E : Ordered_Type) : T with type elt = E.t

```

N.2 Implementation of *PowSet*

```

module type Ordered_Type =
  sig
    type t
    val compare : t → t → int
    val to_string : t → string
  end

module type T =
  sig
    type elt
    type t
    val empty : t
    val is_empty : t → bool
    val union : t list → t
    val of_lists : elt list list → t
    val to_lists : t → elt list list
    val basis : t → t
    val to_string : t → string
  end

module Make (E : Ordered_Type) =
  struct

    type elt = E.t

    module ESet = Set.Make (E)
    type set = ESet.t

    module EPowSet = Set.Make (ESet)
    type t = EPowSet.t

    let empty = EPowSet.empty
    let is_empty = EPowSet.is_empty

    let union s_list =
      List.fold_right EPowSet.union s_list EPowSet.empty

    let set_to_string set =
      "{" ^ String.concat ", " (List.map E.to_string (ESet.elements set)) ^ "}"
  end

```

```

let to_string powset =
  "{" ^ String.concat "," (List.map set_to_string (EPowSet.elements powset)) ^ "}"

let set_of_list list =
  List.fold_right ESet.add list ESet.empty

let of_lists lists =
  List.fold_right
    (fun list acc → EPowSet.add (set_of_list list) acc)
    lists EPowSet.empty

let to_lists ps =
  List.map ESet.elements (EPowSet.elements ps)

product (s1, s2) = s1 ∘ s2 = {s1 \ s2, s1 ∩ s2, s2 \ s1} \ {∅}

let product s1 s2 =
  List.fold_left
    (fun pset set → if ESet.is_empty set then pset else EPowSet.add set pset)
    EPowSet.empty [ESet.diff s1 s2; ESet.inter s1 s2; ESet.diff s2 s1]

let disjoint s1 s2 =
  ESet.is_empty (ESet.inter s1 s2)

```

In *augment_basis_overlapping* ($s, \{s_i\}_i$), we are guaranteed that

$$\forall_i : s \cap s_i \neq \emptyset \quad (\text{N.1a})$$

$$\forall_{i \neq j} : s_i \cap s_j = \emptyset. \quad (\text{N.1b})$$

Therefore from (N.1b)

$$\forall_{i \neq j} : (s \cap s_i) \cap (s \cap s_j) = s \cap (s_i \cap s_j) = s \cap \emptyset = \emptyset \quad (\text{N.2a})$$

$$\forall_{i \neq j} : (s_i \setminus s) \cap (s_j \setminus s) \subset s_i \cap s_j = \emptyset \quad (\text{N.2b})$$

$$\forall_{i \neq j} : (s \setminus s_i) \cap (s_j \setminus s) \subset s \cap \bar{s} = \emptyset \quad (\text{N.2c})$$

$$\forall_{i \neq j} : (s \cap s_i) \cap (s_j \setminus s) \subset s \cap \bar{s} = \emptyset, \quad (\text{N.2d})$$

but in general

$$\exists_{i \neq j} : (s \setminus s_i) \cap (s \setminus s_j) \neq \emptyset \quad (\text{N.3a})$$

$$\exists_{i \neq j} : (s \setminus s_i) \cap (s \cap s_j) \neq \emptyset, \quad (\text{N.3b})$$

because, e. g., for $s_i = \{i\}$ and $s = \{1, 2, 3\}$

$$(s \setminus s_1) \cap (s \setminus s_2) = \{2, 3\} \cap \{1, 3\} = \{3\} \quad (\text{N.4a})$$

$$(s \setminus s_1) \cap (s \cap s_2) = \{2, 3\} \cap \{2\} = \{2\}. \quad (\text{N.4b})$$

Summarizing:

$\forall_{i \neq j} : A_i \cap A_j$	$s_j \setminus s$	$s \cap s_j$	$s \setminus s_j$
$s_i \setminus s$	\emptyset	\emptyset	\emptyset
$s \cap s_i$	\emptyset	\emptyset	$\neq \emptyset$
$s \setminus s_i$	\emptyset	$\neq \emptyset$	$\neq \emptyset$

Fortunately, we also know from (N.1a) that

$$\forall_i : |s \setminus s_i| < |s| \quad (\text{N.5a})$$

$$\forall_i : |s \cap s_i| < \min(|s|, |s_i|) \quad (\text{N.5b})$$

$$\forall_i : |s_i \setminus s| < |s_i| \quad (\text{N.5c})$$

and can call *basis* recursively without risking non-termination.

```

let rec basis ps =
  EPowSet.fold augment_basis ps EPowSet.empty
and augment_basis s ps =
  if EPowSet.mem s ps then
    ps
  else
    let no_overlaps, overlaps = EPowSet.partition (disjoint s) ps in
    if EPowSet.is_empty overlaps then
      EPowSet.add s ps
    else
      EPowSet.union no_overlaps (augment_basis_overlapping s overlaps)
and augment_basis_overlapping s ps =
  basis (EPowSet.fold (fun s' → EPowSet.union (product s s')) ps EPowSet.empty)
end

```

—O—

COMBINATORICS

O.1 Interface of Combinatorics

This type is defined just for documentation. Below, most functions will construct a (possibly nested) *list* of partitions or permutations of a α *seq*.

`type α seq = α list`

O.1.1 Simple Combinatorial Functions

The functions

$$\text{factorial} : n \rightarrow n! \quad (\text{O.1a})$$

$$\text{binomial} : (n, k) \rightarrow \binom{n}{k} = \frac{n!}{k!(n-k)!} \quad (\text{O.1b})$$

$$\text{multinomial} : [n_1; n_2; \dots; n_k] \rightarrow \binom{n_1 + n_2 + \dots + n_k}{n_1, n_2, \dots, n_k} = \frac{(n_1 + n_2 + \dots + n_k)!}{n_1! n_2! \dots n_k!} \quad (\text{O.1c})$$

have not been optimized. They can quickly run out of the range of native integers.

`val factorial : int → int`
`val binomial : int → int → int`
`val multinomial : int list → int`

symmetry l returns the size of the symmetric group on l , i. e. the product of the factorials of the numbers of identical elements.

`val symmetry : α list → int`

O.1.2 Partitions

partitions $[n_1; n_2; \dots; n_k] [x_1; x_2; \dots; x_n]$, where $n = n_1 + n_2 + \dots + n_k$, returns all inequivalent partitions of $[x_1; x_2; \dots; x_n]$ into parts of size n_1, n_2, \dots, n_k . The order of the n_i is not respected. There are

$$\frac{1}{S(n_1, n_2, \dots, n_k)} \binom{n_1 + n_2 + \dots + n_k}{n_1, n_2, \dots, n_k} \quad (\text{O.2})$$

such partitions, where the symmetry factor $S(n_1, n_2, \dots, n_k)$ is the size of the permutation group of $[n_1; n_2; \dots; n_k]$ as determined by the function *symmetry*.

val partitions : $int\ list \rightarrow \alpha\ seq \rightarrow \alpha\ seq\ list\ list$

ordered_partitions is identical to *partitions*, except that the order of the n_i is respected. There are

$$\binom{n_1 + n_2 + \dots + n_k}{n_1, n_2, \dots, n_k} \quad (O.3)$$

such partitions.

val ordered_partitions : $int\ list \rightarrow \alpha\ seq \rightarrow \alpha\ seq\ list\ list$

keystones m l is equivalent to *partitions m l*, except for the special case when the length of l is even and m contains a part that has exactly half the length of l . In this case only the half of the partitions is created that has the head of l in the longest part.

val keystones : $int\ list \rightarrow \alpha\ seq \rightarrow \alpha\ seq\ list\ list$

It can be beneficial to factorize a common part in the partitions and keystones:

val factorized_partitions : $int\ list \rightarrow \alpha\ seq \rightarrow (\alpha\ seq \times \alpha\ seq\ list\ list)\ list$

val factorized_keystones : $int\ list \rightarrow \alpha\ seq \rightarrow (\alpha\ seq \times \alpha\ seq\ list\ list)\ list$

Special Cases

partitions is built from components that can be convenient by themselves, even though they are just special cases of *partitions*.

split k l returns the list of all inequivalent splits of the list l into one part of length k and the rest. There are

$$\frac{1}{S(|l| - k, k)} \binom{|l|}{k} \quad (O.4)$$

such splits. After replacing the pairs by two-element lists, *split k l* is equivalent to *partitions [k; length l - k] l*.

val split : $int \rightarrow \alpha\ seq \rightarrow (\alpha\ seq \times \alpha\ seq)\ list$

Create both equipartitions of lists of even length. There are

$$\binom{|l|}{k} \quad (O.5)$$

such splits. After replacing the pairs by two-element lists, the result of *ordered_split k l* is equivalent to *ordered_partitions [k; length l - k] l*.

val ordered_split : $int \rightarrow \alpha\ seq \rightarrow (\alpha\ seq \times \alpha\ seq)\ list$

multi_split n k l returns the list of all inequivalent splits of the list l into n parts of length k and the rest.

val multi_split : $int \rightarrow int \rightarrow \alpha\ seq \rightarrow (\alpha\ seq\ list \times \alpha\ seq)\ list$

val ordered_multi_split : $int \rightarrow int \rightarrow \alpha\ seq \rightarrow (\alpha\ seq\ list \times \alpha\ seq)\ list$

O.1.3 Choices

choose n $[x_1; x_2; \dots; x_n]$ returns the list of all n -element subsets of $[x_1; x_2; \dots; x_n]$.
choose n is equivalent to $(\text{map fst}) \circ (\text{ordered_split } n)$.

`val choose : int → α seq → α seq list`

multi_choose n k is equivalent to $(\text{map fst}) \circ (\text{multi_split } n \ k)$.

`val multi_choose : int → int → α seq → α seq list list`

`val ordered_multi_choose : int → int → α seq → α seq list list`

O.1.4 Permutations

`val permute : α seq → α seq list`

Graded Permutations

`val permute_signed : α seq → (int × α seq) list`

`val permute_even : α seq → α seq list`

`val permute_odd : α seq → α seq list`

Tensor Products of Permutations

In other words: permutations which respect compartmentalization.

`val permute_tensor : α seq list → α seq list list`

`val permute_tensor_signed : α seq list → (int × α seq list) list`

`val permute_tensor_even : α seq list → α seq list list`

`val permute_tensor_odd : α seq list → α seq list list`

Sorting

`val sort_signed : (α → α → int) → α list → int × α list`

O.2 Implementation of Combinatorics

`type α seq = α list`

O.2.1 Simple Combinatorial Functions

```

let rec factorial' fn n =
  if n < 1 then
    fn
  else
    factorial' (n × fn) (pred n)

let factorial n =
  if 0 ≤ n ∧ n ≤ 12 then
    factorial' 1 n
  else
    invalid_arg "Combinatorics.factorial"

```

$$\begin{aligned}
\binom{n}{k} &= \frac{n!}{k!(n-k)!} = \frac{n(n-1)\cdots(n-k+1)}{k(k-1)\cdots 1} \\
&= \frac{n(n-1)\cdots(k+1)}{(n-k)(n-k-1)\cdots 1} = \begin{cases} B_{n-k+1}(n, k) & \text{for } k \leq \lfloor n/2 \rfloor \\ B_{k+1}(n, n-k) & \text{for } k > \lfloor n/2 \rfloor \end{cases} \quad (\text{O.6})
\end{aligned}$$

where

$$B_{n_{\min}}(n, k) = \begin{cases} nB_{n_{\min}}(n-1, k) & \text{for } n \geq n_{\min} \\ \frac{1}{k}B_{n_{\min}}(n, k-1) & \text{for } k > 1 \\ 1 & \text{otherwise} \end{cases} \quad (\text{O.7})$$

```

let rec binomial' n_min n k acc =
  if n ≥ n_min then
    binomial' n_min (pred n) k (n × acc)
  else if k > 1 then
    binomial' n_min n (pred k) (acc / k)
  else
    acc

```

```

let binomial n k =
  if k > n / 2 then
    binomial' (k + 1) n (n - k) 1
  else
    binomial' (n - k + 1) n k 1

```

Overflows later, but takes much more time:

$$\binom{n}{k} = \binom{n-1}{k} + \binom{n-1}{k-1} \quad (\text{O.8})$$

```

let rec slow_binomial n k =
  if n < 0 ∨ k < 0 then
    invalid_arg "Combinatorics.binomial"
  else if k = 0 ∨ k = n then
    1
  else

```

```

    slow_binomial (pred n) k + slow_binomial (pred n) (pred k)
let multinomial n_list =
  List.fold_left (fun acc n → acc / (factorial n))
    (factorial (List.fold_left (+) 0 n_list)) n_list
let symmetry l =
  List.fold_left (fun s (n, _) → s × factorial n) 1 (ThoList.classify l)

```

O.2.2 Partitions

The inner steps of the recursion (i.e. $n = 1$) are expanded as follows

$$\begin{aligned}
 \text{split}'(1, [p_k; p_{k-1}; \dots; p_1], [x_l; x_{l-1}; \dots; x_1], [x_{l+1}; x_{l+2}; \dots; x_m]) = \\
 & ([p_1; \dots; p_k; x_{l+1}], [x_1; \dots; x_l; x_{l+2}; \dots; x_m]); \\
 & ([p_1; \dots; p_k; x_{l+2}], [x_1; \dots; x_l; x_{l+1}; x_{l+3}; \dots; x_m]); \dots; \\
 & ([p_1; \dots; p_k; x_m], [x_1; \dots; x_l; x_{l+1}; \dots; x_{m-1}]) \quad (\text{O.9})
 \end{aligned}$$

while the outer steps (i.e. $n > 1$) perform the same with one element moved from the last argument to the first argument. At the n th level we have

$$\begin{aligned}
 \text{split}'(n, [p_k; p_{k-1}; \dots; p_1], [x_l; x_{l-1}; \dots; x_1], [x_{l+1}; x_{l+2}; \dots; x_m]) = \\
 & ([p_1; \dots; p_k; x_{l+1}; x_{l+2}; \dots; x_{l+n}], [x_1; \dots; x_l; x_{l+n+1}; \dots; x_m]); \dots; \\
 & ([p_1; \dots; p_k; x_{m-n+1}; x_{m-n+2}; \dots; x_m], [x_1; \dots; x_l; x_{l+1}; \dots; x_{m-n}]) \quad (\text{O.10})
 \end{aligned}$$

where the order of the $[x_1; x_2; \dots; x_m]$ is maintained in the partitions. Variations on this multiple recursion idiom are used many times below.

```

let rec split' n rev_part rev_head = function
| [] → []
| x :: tail →
  let rev_part' = x :: rev_part
  and parts = split' n rev_part (x :: rev_head) tail in
  if n < 1 then
    failwith "Combinatorics.split': can't happen"
  else if n = 1 then
    (List.rev rev_part', List.rev_append rev_head tail) :: parts
  else
    split' (pred n) rev_part' rev_head tail @ parts

```

Kick off the recursion for $0 < n < |l|$ and handle the cases $n \in \{0, |l|\}$ explicitly. Use reflection symmetry for a small optimization.

```

let ordered_split_unsafe n abs_l l =
  let abs_l = List.length l in
  if n = 0 then
    [], l
  else if n = abs_l then
    l, []
  else if n ≤ abs_l / 2 then

```



```

    split' n [] [] l
  else
    List.rev_map (fun (a, b) → (b, a)) (split' (abs_l - n) [] [] l)

```

Check the arguments and call the workhorse:

```

let ordered_split n l =
  let abs_l = List.length l in
  if n < 0 ∨ n > abs_l then
    invalid_arg "Combinatorics.ordered_split"
  else
    ordered_split_unsafe n abs_l l

```

Handle equipartitions specially:

```

let split n l =
  let abs_l = List.length l in
  if n < 0 ∨ n > abs_l then
    invalid_arg "Combinatorics.split"
  else begin
    if 2 × n = abs_l then
      match l with
      | [] → failwith "Combinatorics.split: can't happen"
      | x :: tail →
          List.map (fun (p1, p2) → (x :: p1, p2)) (split' (pred n) [] [] tail)
    else
      ordered_split_unsafe n abs_l l
  end
end

```

If we chop off parts repeatedly, we can either keep permutations or suppress them. Generically, *attach_to_fst* has type

$$(\alpha \times \beta) \text{ list} \rightarrow \alpha \text{ list} \rightarrow (\alpha \text{ list} \times \beta) \text{ list} \rightarrow (\alpha \text{ list} \times \beta) \text{ list}$$

and semantics

$$\begin{aligned} \text{attach_to_fst}([(a_1, b_1), (a_2, b_2), \dots, (a_m, b_m)], [a'_1, a'_2, \dots]) = \\ [[a_1, a'_1, \dots], b_1], [[a_2, a'_1, \dots], b_2], \dots, [[a_m, a'_1, \dots], b_m] \end{aligned} \quad (\text{O.11})$$

(where some of the result can be filtered out), assumed to be prepended to the final argument.

```

let rec multi_split' attach_to_fst n size splits =
  if n ≤ 0 then
    splits
  else
    multi_split' attach_to_fst (pred n) size
    (List.fold_left (fun acc (parts, tail) →
      attach_to_fst (ordered_split size tail) parts acc) [] splits)

let attach_to_fst_unsorted splits parts acc =
  List.fold_left (fun acc' (p, rest) → (p :: parts, rest) :: acc') acc splits

```

Similarly, if the second argument is a list of lists:

```

let prepend_to_fst_unsorted splits parts acc =
  List.fold_left (fun acc' (p, rest) → (p @ parts, rest) :: acc') acc splits

let attach_to_fst_sorted splits parts acc =
  match parts with
  | [] → List.fold_left (fun acc' (p, rest) → ([p], rest) :: acc') acc splits
  | p :: _ as parts →
    List.fold_left (fun acc' (p', rest) →
      if p' > p then
        (p' :: parts, rest) :: acc'
      else
        acc') acc splits

let multi_split n size l =
  multi_split' attach_to_fst_sorted n size ([], l)

let ordered_multi_split n size l =
  multi_split' attach_to_fst_unsorted n size ([], l)

let rec partitions' splits = function
  | [] → List.map (fun (h, r) → (List.rev h, r)) splits
  | (1, size) :: more →
    partitions'
    (List.fold_left (fun acc (parts, rest) →
      attach_to_fst_unsorted (split size rest) parts acc)
      [] splits) more
  | (n, size) :: more →
    partitions'
    (List.fold_left (fun acc (parts, rest) →
      prepend_to_fst_unsorted (multi_split n size rest) parts acc)
      [] splits) more

let partitions multiplicities l =
  if List.fold_left (+) 0 multiplicities ≠ List.length l then
    invalid_arg "Combinatorics.partitions"
  else
    List.map fst (partitions' ([], l)
      (ThoList.classify (List.sort compare multiplicities)))

let rec ordered_partitions' splits = function
  | [] → List.map (fun (h, r) → (List.rev h, r)) splits
  | size :: more →
    ordered_partitions'
    (List.fold_left (fun acc (parts, rest) →
      attach_to_fst_unsorted (ordered_split size rest) parts acc)
      [] splits) more

let ordered_partitions multiplicities l =
  if List.fold_left (+) 0 multiplicities ≠ List.length l then
    invalid_arg "Combinatorics.ordered_partitions"
  else
    List.map fst (ordered_partitions' ([], l) multiplicities)

let hdtl = function

```

```

| [] → invalid_arg "Combinatorics.htdl"
| h :: t → (h, t)

```

```

let factorized_partitions multiplicities l =
  ThoList.factorize (List.map hdtl (partitions multiplicities l))

```

In order to construct keystones (cf. chapter 3), we must eliminate reflections consistently. For this to work, the lengths of the parts *must not* be reordered arbitrarily. Ordering with monotonously falling lengths would be incorrect however, because then some remainders could fake a reflection symmetry and partitions would be dropped erroneously. Therefore we put the longest first and order the remaining with rising lengths:

```

let longest_first l =
  match ThoList.classify (List.sort (fun n1 n2 → compare n2 n1) l) with
  | [] → []
  | longest :: rest → longest :: List.rev rest

let keystones multiplicities l =
  if List.fold_left (+) 0 multiplicities ≠ List.length l then
    invalid_arg "Combinatorics.keystones"
  else
    List.map fst (partitions' ([], l) (longest_first multiplicities))

let factorized_keystones multiplicities l =
  ThoList.factorize (List.map hdtl (keystones multiplicities l))

```

O.2.3 Choices

The implementation is very similar to *split'*, but here we don't have to keep track of the complements of the chosen sets.

```

let rec choose' n rev_choice = function
| [] → []
| x :: tail →
  let rev_choice' = x :: rev_choice
  and choices = choose' n rev_choice tail in
  if n < 1 then
    failwith "Combinatorics.choose': can't happen"
  else if n = 1 then
    List.rev rev_choice' :: choices
  else
    choose' (pred n) rev_choice' tail @ choices

```

choose *n* is equivalent to $(List.map fst) \circ (split_ordered\ n)$, but more efficient.

```

let choose n l =
  let abs_l = List.length l in
  if n < 0 then
    invalid_arg "Combinatorics.choose"
  else if n > abs_l then
    []
  else if n = 0 then

```

```

    [[]]
  else if  $n = \text{abs\_}l$  then
    [ $l$ ]
  else
    choose'  $n$  []  $l$ 
let multi_choose  $n$  size  $l$  =
  List.map fst (multi_split  $n$  size  $l$ )
let ordered_multi_choose  $n$  size  $l$  =
  List.map fst (ordered_multi_split  $n$  size  $l$ )

```

O.2.4 Permutations

```

let rec insert  $x$  = function
| [] → [[ $x$ ]]
|  $h :: t$  as  $l$  →
  ( $x :: l$ ) :: List.rev_map (fun  $l' \rightarrow h :: l'$ ) (insert  $x$   $t$ )
let permute  $l$  =
  List.fold_left (fun acc  $x \rightarrow \text{ThoList.rev\_flatmap}$  (insert  $x$ ) acc) [[]]  $l$ 

```

Graded Permutations

```

let rec insert_signed  $x$  = function
| ( $\text{eps}$ , []) → [( $\text{eps}$ , [ $x$ ])]
| ( $\text{eps}$ ,  $h :: t$ ) → ( $\text{eps}$ ,  $x :: h :: t$ ) ::
  (List.map (fun ( $\text{eps}'$ ,  $l'$ ) → ( $-\text{eps}'$ ,  $h :: l'$ )) (insert_signed  $x$  ( $\text{eps}$ ,  $t$ )))
let rec permute_signed' = function
| ( $\text{eps}$ , []) → [( $\text{eps}$ , [])]
| ( $\text{eps}$ ,  $h :: t$ ) → ThoList.flatmap (insert_signed  $h$ ) (permute_signed' ( $\text{eps}$ ,  $t$ ))
let permute_signed  $l$  =
  permute_signed' (1,  $l$ )

```

The following are wasting at most a factor of two and there's probably no point in improving on this ...

```

let filter_sign  $s$   $l$  =
  List.map snd (List.filter (fun ( $\text{eps}$ , _) →  $\text{eps} = s$ )  $l$ )
let permute_even  $l$  =
  filter_sign 1 (permute_signed  $l$ )
let permute_odd  $l$  =
  filter_sign (-1) (permute_signed  $l$ )

```

Tensor Products of Permutations

```

let permute_tensor ll =
  Product.list (fun l → l) (List.map permute ll)

let join_signs l =
  let el, pl = List.split l in
  (List.fold_left (fun acc x → x × acc) 1 el, pl)

let permute_tensor_signed ll =
  Product.list join_signs (List.map permute_signed ll)

let permute_tensor_even l =
  filter_sign 1 (permute_tensor_signed l)

let permute_tensor_odd l =
  filter_sign (-1) (permute_tensor_signed l)

let insert_inorder_signed order x (eps, l) =
  let rec insert eps' accu = function
    | [] → (eps × eps', List.rev_append accu [x])
    | h :: t →
        if order x h = 0 then
          invalid_arg
            "Combinatorics.insert_inorder_signed: identical elements"
        else if order x h < 0 then
          (eps × eps', List.rev_append accu (x :: h :: t))
        else
          insert (-eps') (h :: accu) t
  in
  insert 1 [] l

```

Sorting

```

let sort_signed order l =
  List.fold_left (fun acc x → insert_inorder_signed order x acc) (1, []) l

```

O.3 Interface of Permutation

```

module type T =
sig
  type t
  val of_list : int list → t
  val of_array : int array → t
  val inverse : t → t
  val compose : t → t → t
  val list : t → α list → α list
  val array : t → α array → α array
end

```

```

module Using_Lists : T
module Using_Arrays : T

module Default : T

module Test : functor (P : T) →
  sig val suite : OUnit.test val time : unit → unit end

```

O.4 Implementation of *Permutation*

```

module type T =
  sig
    type t
    val of_list : int list → t
    val of_array : int array → t
    val inverse : t → t
    val compose : t → t → t
    val list : t → α list → α list
    val array : t → α array → α array
  end

module Using_Lists : T =
  struct
    type t = int list

    let of_list p =
      if List.sort compare p ≠ (ThoList.range 0 (List.length p - 1)) then
        invalid_arg "Permutation.of_list"
      else
        p

    let of_array p =
      try
        of_list (Array.to_list p)
      with
      | Invalid_argument "Permutation.of_list" →
        invalid_arg "Permutation.of_array"

    let inverse p = snd (ThoList.ariadne_sort p)

    let list p l =
      List.map snd
        (List.sort compare
          (try
             List.rev_map2 (fun i x → (i, x)) p l
           with
           | Invalid_argument "List.rev_map2" →
            invalid_arg "Permutation.list:_length_mismatch"))

    let array p a =
      try
        Array.of_list (list p (Array.to_list a))

```

```

with
| Invalid_argument "Permutation.list:␣length␣mismatch" →
  invalid_arg "Permutation.array:␣length␣mismatch"

```

Probably not optimal (or really inefficient), but correct by associativity.

```

let compose p q =
  list (inverse q) p
end

module Using_Arrays : T =
struct

  type t = int array

  let of_list p =
    if List.sort compare p ≠ (ThoList.range 0 (List.length p - 1)) then
      invalid_arg "Permutation.of_list"
    else
      Array.of_list p

  let of_array p =
    try
      of_list (Array.to_list p)
    with
    | Invalid_argument "Permutation.of_list" →
      invalid_arg "Permutation.of_array"

  let inverse p =
    let len_p = Array.length p in
    let p' = Array.make len_p p.(0) in
    for i = 0 to pred len_p do
      p'.(p.(i)) ← i
    done;
    p'

  let array p a =
    let len_a = Array.length a
    and len_p = Array.length p in
    if len_a ≠ len_p then
      invalid_arg "Permutation.array:␣length␣mismatch";
    let a' = Array.make len_a a.(0) in
    for i = 0 to pred len_a do
      a'.(p.(i)) ← a.(i)
    done;
    a'

  let list p l =
    try
      Array.to_list (array p (Array.of_list l))
    with
    | Invalid_argument "Permutation.array:␣length␣mismatch" →
      invalid_arg "Permutation.list:␣length␣mismatch"

```

```

    let compose p q =
      array (inverse q) p
    end
  module Default = Using_Arrays
  To shuffle an array a of n elements (indices 0..n-1):
    for i from n - 1 downto 1 do j = random integer with 0 ≤ j ≤ i exchange aj and ai
    To initialize an array a of n elements to a randomly shuffled copy of source,
    both 0-based:
      a[0] = source[0] for i from 1 to n - 1 do j = random integer with 0 ≤ j ≤ i ai = aj aj = source[i]
  let shuffle l =
    let a = Array.of_list l in
    for n = Array.length a - 1 downto 1 do
      let k = Random.int (succ n) in
      if k ≠ n then
        let tmp = Array.get a n in
        Array.set a n (Array.get a k);
        Array.set a k tmp
      done;
    Array.to_list a
  let time f x =
    let start = Sys.time () in
    let f_x = f x in
    let stop = Sys.time () in
    (f_x, stop - . start)
  let print_time msg f x =
    let f_x, seconds = time f x in
    Printf.printf "%s took %10.2f ms\n" msg (seconds * . 1000.);
    f_x
  module Test (P : T) : sig val suite : OUnit.test val time : unit → unit end =
  struct
    open OUnit
    open P
    let of_list_overlap =
      "overlap" >::
      (fun () →
        assert_raises (Invalid_argument "Permutation.of_list")
          (fun () →
            of_list [0; 1; 2; 2]))
    let of_list_gap =
      "gap" >::
      (fun () →
        assert_raises (Invalid_argument "Permutation.of_list")
          (fun () →
            of_list [0; 1; 2; 4; 5]))
  end

```



```

let of_list_ok =
  "ok" >::
    (fun () →
      let l = ThoList.range 0 10 in
      assert_equal (of_list l) (of_list l))

let suite_of_list =
  "of_list" >:::
    [of_list_overlap;
     of_list_gap;
     of_list_ok]

let apply_invalid_lengths =
  "invalid/lengths" >::
    (fun () →
      assert_raises
        (Invalid_argument "Permutation.list:_length_mismatch")
      (fun () →
        list (of_list [0; 1; 2; 3; 4]) [0; 1; 2; 3]))

let apply_ok =
  "ok" >::
    (fun () →
      assert_equal [2; 0; 1; 3; 5; 4]
        (list (of_list [1; 2; 0; 3; 5; 4]) [0; 1; 2; 3; 4; 5]))

let suite_apply =
  "apply" >:::
    [apply_invalid_lengths;
     apply_ok]

let inverse_ok =
  "ok" >::
    (fun () →
      let l = shuffle (ThoList.range 0 1000) in
      let p = of_list (shuffle l) in
      assert_equal l (list (inverse p) (list p l)))

let suite_inverse =
  "inverse" >:::
    [inverse_ok]

let compose_ok =
  "ok" >::
    (fun () →
      let id = ThoList.range 0 1000 in
      let p = of_list (shuffle id)
      and q = of_list (shuffle id)
      and l = id in
      assert_equal (list p (list q l)) (list (compose p q) l))

let compose_inverse_ok =
  "inverse/ok" >::
    (fun () →

```

```

    let id = ThoList.range 0 1000 in
    let p = of_list (shuffle id)
    and q = of_list (shuffle id) in
    assert_equal
      (compose (inverse p) (inverse q))
      (inverse (compose q p)))

let suite_compose =
  "compose" >:::
    [compose_ok;
     compose_inverse_ok]

let suite =
  "Permutations" >:::
    [suite_of_list;
     suite_apply;
     suite_inverse;
     suite_compose]

let repeat_repetitions size =
  let id = ThoList.range 0 size in
  let p = of_list (shuffle id)
  and l = shuffle (List.map string_of_int id) in
  print_time (Printf.sprintf "reps=%d, len=%d" repetitions size)
    (fun () →
      for i = 1 to repetitions do
        ignore (P.list p l)
      done)
    ())

let time () =
  repeat 100000 10;
  repeat 10000 100;
  repeat 1000 1000;
  repeat 100 10000;
  repeat 10 100000;
  ()

end

```

—P—

PARTITIONS

P.1 Interface of Partition

pairs n $n1$ $n2$ returns all (unordered) pairs of integers with the sum n in the range from $n1$ to $n2$.

`val pairs : int → int → int → (int × int) list`
`val triples : int → int → int → (int × int × int) list`

tuples d n n_{\min} n_{\max} returns all $[n_1; n_2; \dots; n_d]$ with $n_{\min} \leq n_1 \leq n_2 \leq \dots \leq n_d \leq n_{\max}$ and

$$\sum_{i=1}^d n_i = n \quad (\text{P.1})$$

`val tuples : int → int → int → int → int list list`
`val rcs : RCS.t`

P.2 Implementation of Partition

```
let rcs = RCS.parse "Partition" ["Partitions"]
  { RCS.revision = "$Revision: 4538$";
    RCS.date = "$Date: 2013-08-23 18:09:06 +0200 (Fri, 23 Aug 2013)$";
    RCS.author = "$Author: jr-reuter$";
    RCS.source
      = "$URL: svn+ssh://jr-reuter@login.hepforge.org/hepforge/svn/whizard/trunk/src/omeg
```

All unordered pairs of integers with the same sum n in a given range $\{n_1, \dots, n_2\}$:

$$\text{pairs} : (n, n_1, n_2) \rightarrow \{(i, j) \mid i + j = n \wedge n_1 \leq i \leq j \leq n_2\} \quad (\text{P.2})$$

```
let rec pairs' acc n1 n2 =
  if n1 > n2 then
    List.rev acc
  else
    pairs' ((n1, n2) :: acc) (succ n1) (pred n2)
let pairs sum min_n1 max_n2 =
  let n1 = max min_n1 (sum - max_n2) in
```

```

let n2 = sum - n1 in
if n2 ≤ max_n2 then
  pairs' [] n1 n2
else
  []

let rec tuples d sum n_min n_max =
  if d ≤ 0 then
    invalid_arg "tuples"
  else if d > 1 then
    tuples' d sum n_min n_max n_min
  else if sum ≥ n_min ∧ sum ≤ n_max then
    [[sum]]
  else
    []

and tuples' d sum n_min n_max n =
  if n > n_max then
    []
  else
    List.fold_right (fun l ll → (n :: l) :: ll)
      (tuples (pred d) (sum - n) (max n_min n) n_max)
      (tuples' d sum n_min n_max (succ n))

```



When I find a little spare time, I can provide a dedicated implementation, but we *know* that *Impossible* is *never* raised and the present approach is just as good (except for a possible tiny inefficiency).

```

exception Impossible of string
let impossible name = raise (Impossible name)

let triples sum n_min n_max =
  List.map (function [n1; n2; n3] → (n1, n2, n3) | _ → impossible "triples")
    (tuples 3 sum n_min n_max)

```

Q TREES

From [10]: Trees with one root admit a straightforward recursive definition

$$T(N, L) = L \cup N \times T(N, L) \times T(N, L) \quad (\text{Q.1})$$

that is very well adapted to mathematical reasoning. Such recursive definitions are useful because they allow us to prove properties of elements by induction

$$\begin{aligned} \forall l \in L : p(l) \wedge (\forall n \in N : \forall t_1, t_2 \in T(N, L) : p(t_1) \wedge p(t_2) \Rightarrow p(n \times t_1 \times t_2)) \\ \implies \forall t \in T(N, L) : p(t) \end{aligned} \quad (\text{Q.2})$$

i. e. establishing a property for all leaves and showing that a node automatically satisfies the property if it is true for all children proves the property for *all* trees. This induction is of course modelled after standard mathematical induction

$$p(1) \wedge (\forall n \in \mathbf{N} : p(n) \Rightarrow p(n+1)) \implies \forall n \in \mathbf{N} : p(n) \quad (\text{Q.3})$$

The recursive definition (Q.1) is mirrored by the two tree construction functions¹

$$\text{leaf} : \nu \times \lambda \rightarrow (\nu, \lambda)T \quad (\text{Q.4a})$$

$$\text{node} : \nu \times (\nu, \lambda)T \times (\nu, \lambda)T \rightarrow (\nu, \lambda)T \quad (\text{Q.4b})$$

Renaming leaves and nodes leaves the structure of the tree invariant. Therefore, morphisms $L \rightarrow L'$ and $N \rightarrow N'$ of the sets of leaves and nodes induce natural homomorphisms $T(N, L) \rightarrow T(N', L')$ of trees

$$\text{map} : (\nu \rightarrow \nu') \times (\lambda \rightarrow \lambda') \times (\nu, \lambda)T \rightarrow (\nu', \lambda')T \quad (\text{Q.5})$$

The homomorphisms constructed by *map* are trivial, but ubiquitous. More interesting are the morphisms

$$\begin{aligned} \text{fold} : (\nu \times \lambda \rightarrow \alpha) \times (\nu \times \alpha \times \alpha \rightarrow \alpha) \times (\nu, \lambda)T &\rightarrow \alpha \\ (f_1, f_2, l \in L) &\mapsto f_1(l) \\ (f_1, f_2, (n, t_1, t_2)) &\mapsto f_2(n, \text{fold}(f_1, f_2, t_1), \text{fold}(f_1, f_2, t_2)) \end{aligned} \quad (\text{Q.6})$$

¹To make the introduction more accessible to non-experts, I avoid the ‘curried’ notation for functions with multiple arguments and use tuples instead. The actual implementation takes advantage of curried functions, however. Experts can read $\alpha \rightarrow \beta \rightarrow \gamma$ for $\alpha \times \beta \rightarrow \gamma$.

and

$$\begin{aligned}
 fan : (\nu \times \lambda \rightarrow \{\alpha\}) \times (\nu \times \alpha \times \alpha \rightarrow \{\alpha\}) \times (\nu, \lambda)T &\rightarrow \{\alpha\} \\
 (f_1, f_2, l \in L) &\mapsto f_1(l) \\
 (f_1, f_2, (n, t_1, t_2)) &\mapsto f_2(n, fold(f_1, f_2, t_1) \otimes fold(f_1, f_2, t_2))
 \end{aligned} \tag{Q.7}$$

where the tensor product notation means that f_2 is applied to all combinations of list members in the argument:

$$\phi(\{x\} \otimes \{y\}) = \{\phi(x, y) | x \in \{x\} \wedge y \in \{y\}\} \tag{Q.8}$$

But note that due to the recursive nature of trees, fan is *not* a morphism from $T(N, L)$ to $T(N \otimes N, L)$.

If we identify singleton sets with their members, $fold$ could be viewed as a special case of fan , but that is probably more confusing than helpful. Also, using the special case $\alpha = (\nu', \lambda')T$, the homomorphism map can be expressed in terms of $fold$ and the constructors

$$\begin{aligned}
 map : (\nu \rightarrow \nu') \times (\lambda \rightarrow \lambda') \times (\nu, \lambda)T &\rightarrow (\nu', \lambda')T \\
 (f, g, t) &\mapsto fold(leaf \circ (f \times g), node \circ (f \times id \times id), t)
 \end{aligned} \tag{Q.9}$$

$fold$ is much more versatile than map , because it can be used with constructors for other tree representations to translate among different representations. The target type can also be a mathematical expression. This is used extensively below for evaluating Feynman diagrams.

Using fan with $\alpha = (\nu', \lambda')T$ can be used to construct a multitude of homomorphic trees. In fact, below it will be used extensively to construct all Feynman diagrams $\{(\nu, \{p_1, \dots, p_n\})T\}$ of a given topology $t \in (\emptyset, \{1, \dots, n\})T$.



The physicist in me guesses that there is another morphism of trees that is related to fan like a Lie-algebra is related to the it's Lie-group. I have not been able to pin it down, but I guess that it is a generalization of $grow$ below.

Q.1 Interface of *Tree*

This module provides utilities for generic decorated trees, such as FeynMF output.

Q.1.1 Abstract Data Type

`type` $(\nu, \lambda) t$

`leaf` $n l$ returns a tree consisting of a single leaf of type n connected to l .

`val leaf` : $\nu \rightarrow \lambda \rightarrow (\nu, \lambda) t$

`cons` $n ch$ returns a tree node.

`val cons` : $\nu \rightarrow (\nu, \lambda) t \text{ list} \rightarrow (\nu, \lambda) t$

node *t* returns the top node of the tree *t*.

val *node* : (ν , λ) *t* \rightarrow ν

leafs *t* returns a list of all leafs *in order*.

val *leafs* : (ν , λ) *t* \rightarrow λ *list*

nodes *t* returns a list of all nodes in post-order. This guarantees that the root node can be stripped from the result by *List.tl*.

val *nodes* : (ν , λ) *t* \rightarrow ν *list*

fuse conjg root contains_root trees joins the *trees*, using the leaf *root* in one of the trees as root of the new tree. *contains_root* guides the search for the subtree containing *root* as a leaf. **fun** *t* \rightarrow *List.mem* *root* (*leafs* *t*) is acceptable, but more efficient solutions could be available in special circumstances.

val *fuse* : ($\nu \rightarrow \nu$) \rightarrow $\lambda \rightarrow ((\nu, \lambda) t \rightarrow \text{bool}) \rightarrow (\nu, \lambda) t \text{ list} \rightarrow (\nu, \lambda) t$

sort lesseq *t* return a sorted copy of the tree *t*: node labels are ignored and nodes are according to the supremum of the leaf labels in the corresponding subtree.

val *sort* : ($\lambda \rightarrow \lambda \rightarrow \text{bool}$) \rightarrow (ν , λ) *t* \rightarrow (ν , λ) *t*

Q.1.2 Homomorphisms

val *map* : ($'n1 \rightarrow 'n2$) \rightarrow ($'l1 \rightarrow 'l2$) \rightarrow ($'n1$, $'l1$) *t* \rightarrow ($'n2$, $'l2$) *t*


val *fold* : ($\nu \rightarrow \lambda \rightarrow \alpha$) \rightarrow ($\nu \rightarrow \alpha \text{ list} \rightarrow \alpha$) \rightarrow (ν , λ) *t* \rightarrow α

val *fan* : ($\nu \rightarrow \lambda \rightarrow \alpha \text{ list}$) \rightarrow ($\nu \rightarrow \alpha \text{ list} \rightarrow \alpha \text{ list}$) \rightarrow
 (ν , λ) *t* \rightarrow $\alpha \text{ list}$

Q.1.3 Output

val *to_string* : (*string*, *string*) *t* \rightarrow *string*

Feynmf

 *style* : (*string* \times *string*) *option* should be replaced by *style* : *string option*; *tex_label* : *string option*

type *feynmf* =
 { *style* : (*string* \times *string*) *option*;
 rev : *bool*;
 label : *string option*;
 tension : *float option* }

val *vanilla* : *feynmf*

```
val sty : (string × string) × bool × string → feynmf
```

to_feynmf file to_string i2 t write the trees in the list *t* to the file named *file*. The leaf *i2* is used as the second incoming particle and *to_string* is used to convert leaf labels to L^AT_EX-strings.

```
val to_feynmf : bool ref → string → (λ → string) → λ → (feynmf, λ) t list → unit
```

Least Squares Layout

A general graph with edges of type ε , internal nodes of type ν , and external nodes of type *'ext*.

```
type (ε, ν, 'ext) graph
```

```
val graph_of_tree : (ν → ν → ε) → (ν → ν) → ν → (ν, ν) t → (ε, ν, ν) graph
```

A general graph with the layout of the external nodes fixed.

```
type (ε, ν, 'ext) ext_layout
```

```
val left_to_right : int → (ε, ν, 'ext) graph → (ε, ν, 'ext) ext_layout
```

A general graph with the layout of all nodes fixed.

```
type (ε, ν, 'ext) layout
```

```
val layout : (ε, ν, 'ext) ext_layout → (ε, ν, 'ext) layout
```

```
val dump : (ε, ν, 'ext) layout → unit
```

```
val iter_edges : (ε → float × float → float × float → unit) → (ε, ν, 'ext) layout → unit
```

```
val iter_internal : (float × float → unit) → (ε, ν, 'ext) layout → unit
```

```
val iter_incoming : ('ext × float × float → unit) → (ε, ν, 'ext) layout → unit
```

```
val iter_outgoing : ('ext × float × float → unit) → (ε, ν, 'ext) layout → unit
```

Q.2 Implementation of *Tree*

Q.2.1 Abstract Data Type

```
type (ν, λ) t =
  | Leaf of ν × λ
  | Node of ν × (ν, λ) t list
```

```
let leaf n l = Leaf (n, l)
```

```
let cons n children = Node (n, children)
```

Presenting the leaves *in order* comes naturally, but will be useful below.

```
let rec leafs = function
  | Leaf (_, l) → [l]
```



```

| Node (_, ch) → ThoList.flatmap leafs ch
let node = function
| Leaf (n, _) → n
| Node (n, _) → n

```

This guarantees that the root node can be stripped from the result by *List.tl*.

```

let rec nodes = function
| Leaf _ → []
| Node (n, ch) → n :: ThoList.flatmap nodes ch

```


first_match *p list* returns $(x, list')$, where x is the first element of *list* for which $p\ x = \text{true}$ and *list'* is *list* sans x .

```

let first_match p list =
  let rec first_match' no_match = function
    | [] → invalid_arg "Tree.fuse: prospective root not found"
    | t :: rest when p t → (t, List.rev_append no_match rest)
    | t :: rest → first_match' (t :: no_match) rest in
  first_match' [] list

```

One recursion step in *fuse'* rotates the topmost tree node, moving the prospective root up:



```

let fuse conjg root contains_root trees =
  let rec fuse' subtrees =
    match first_match contains_root subtrees with

```

If the prospective root is contained in a leaf, we have either found the root—in which case we're done—or have failed catastrophically:

```

| Leaf (n, l), children →
  if l = root then
    Node (conjg n, children)
  else
    invalid_arg "Tree.fuse: root predicate inconsistent"

```

Otherwise, we perform a rotation as in (Q.10) and connect all nodes that do not contain the root to a new node. For efficiency, we append the new node at the end and prevent *first_match* from searching for the root in it in vain again. Since *root_children* is probably rather short, this should be a good strategy.

```

| Node (n, root_children), other_children →
  fuse' (root_children @ [Node (conjg n, other_children)]) in
  fuse' trees

```

Sorting is also straightforward, we only have to keep track of the suprema of the subtrees:

```
type ( $\alpha$ ,  $\beta$ ) with_supremum = { sup :  $\alpha$ ; data :  $\beta$  }
```

Since the lists are rather short, *Sort.list* could be replaced by an optimized version, but we're not (yet) dealing with the most important speed bottleneck here:

```
let rec sort' lesseq = function
| Leaf (_, l) as e → { sup = l; data = e }
| Node (n, ch) →
  let ch' = Sort.list
    (fun x y → lesseq x.sup y.sup) (List.map (sort' lesseq) ch) in
  { sup = (List.hd (List.rev ch')).sup;
    data = Node (n, List.map (fun x → x.data) ch') }
```

finally, throw away the overall supremum:

```
let sort lesseq t = (sort' lesseq t).data
```

Q.2.2 Homomorphisms

Isomorphisms are simple:

```
let rec map fn fl = function
| Leaf (n, l) → Leaf (fn n, fl l)
| Node (n, ch) → Node (fn n, List.map (map fn fl) ch)
```

homomorphisms are not more complicated:

```
let rec fold leaf node = function
| Leaf (n, l) → leaf n l
| Node (n, ch) → node n (List.map (fold leaf node) ch)
```

and tensor products are fun:

```
let rec fan leaf node = function
| Leaf (n, l) → leaf n l
| Node (n, ch) → Product.fold
  (fun ch' t → node n ch' @ t) (List.map (fan leaf node) ch) []
```

Q.2.3 Output

```
let leaf_to_string n l =
  if n = "" then
    l
  else if l = "" then
    n
  else
    n ^ "(" ^ l ^ ")"
```

```

let node_to_string n ch =
  "(" ^ (if n == "" then "" else n ^ ":") ^ (String.concat "," ch) ^ ")"
let to_string t =
  fold leaf_to_string node_to_string t

```

Feynmf

Add a value that is greater than all suprema

```

type  $\alpha$  supremum_or_infinity = Infinity | Sup of  $\alpha$ 
type ( $\alpha$ ,  $\beta$ ) with_supremum_or_infinity =
  { sup :  $\alpha$  supremum_or_infinity; data :  $\beta$  }
let with_infinity lesseq x y =
  match x.sup, y.sup with
  | Infinity, _ → false
  | _, Infinity → true
  | Sup x', Sup y' → lesseq x' y'

```

Using this, we can sort the tree in another way that guarantees that a particular leaf (*i2*) is moved as far to the end as possible. We can then flip this leaf from outgoing to incoming without introducing a crossing:

```

let rec sort_2i' lesseq i2 = function
| Leaf (_, l) as e →
  { sup = if l == i2 then Infinity else Sup l; data = e }
| Node (n, ch) →
  let ch' = Sort.list (with_infinity lesseq)
    (List.map (sort_2i' lesseq i2) ch) in
  { sup = (List.hd (List.rev ch')).sup;
    data = Node (n, List.map (fun x → x.data) ch') }

```

again, throw away the overall supremum:

```

let sort_2i lesseq i2 t = (sort_2i' lesseq i2 t).data

```

```

type feynmf =
  { style : (string × string) option;
    rev : bool;
    label : string option;
    tension : float option }

```

open *Printf*

```

let style prop =
  match prop.style with
  | None → ("plain","")
  | Some s → s

```

```

let species prop = fst (style prop)
let tex_lbl prop = snd (style prop)

```

```

let leaf_label tex io leaf lab = function

```

```

| None → fprintf tex "\fmflabel{${s}}{${s}}\n" lab io leaf
| Some s →
    fprintf tex "\fmflabel{${s}}{^{(s)}}{${s}}\n" s lab io leaf

```

We try to draw diagrams more symmetrically by reducing the tension on the outgoing external lines.



This is insufficient for asymmetrical cascade decays.

```

let rec leaf_node tex to_string i2 n prop leaf =
  let io, tension, rev =
    if leaf = i2 then
      ("i", "", ¬ prop.rev)
    else
      ("o", "", tension=0.5, prop.rev) in
  leaf_label tex io (to_string leaf) (tex_lbl prop) prop.label ;
  fprintf tex "\fmfdot{v%d}\n" n;
  if rev then
    fprintf tex "\fmf{${s}}{${s},v%d}\n"
      (species prop) tension io (to_string leaf) n
  else
    fprintf tex "\fmf{${s}}{v%d,${s}}\n"
      (species prop) tension n io (to_string leaf)

and int_node tex to_string i2 n n' prop t =
  if prop.rev then
    fprintf tex
      "\fmf{${s},label=\begin{scriptsize}${s}\end{scriptsize}}{v%d,v%d}\n"
      (species prop) (tex_lbl prop) n' n
  else
    fprintf tex
      "\fmf{${s},label=\begin{scriptsize}${s}\end{scriptsize}}{v%d,v%d}\n"
      (species prop) (tex_lbl prop) n n';
    fprintf tex "\fmfdot{v%d,v%d}\n" n n';
    edges_feynmf' tex to_string i2 n' t

and leaf_or_int_node tex to_string i2 n n' = function
| Leaf (prop, l) → leaf_node tex to_string i2 n prop l
| Node (prop, _) as t → int_node tex to_string i2 n n' prop t

and edges_feynmf' tex to_string i2 n = function
| Leaf (prop, l) → leaf_node tex to_string i2 n prop l
| Node (_, ch) →
  ignore (List.fold_right
    (fun t' n' →
      leaf_or_int_node tex to_string i2 n n' t';
      succ n') ch (4 × n))

let edges_feynmf tex to_string i2 t =
  let n = 1 in
  begin match t with
  | Leaf _ → ()
  | Node (prop, _) →

```




Figure Q.1: Note that this is subtly different ...

```

leaf_label tex "i" "1" (tex_lbl prop) prop.label;
if prop.rev then
  fprintf tex "\fmf{%s}{i1,v%d}\n" (species prop) n
else
  fprintf tex "\fmf{%s}{v%d,i1}\n" (species prop) n
end;
fprintf tex "\fmf{dot}{v%d}\n" n;
edges_feynmf' tex to_string i2 n t

let to_feynmf_channel tex to_string i2 t =
  let t' = sort_2i (≤) i2 t in
  let out = List.map to_string (List.filter (fun a → i2 ≠ a) (leaves t')) in
  fprintf tex "\fmfframe(6,7)(6,6){%%\n";
  fprintf tex "\begin{fmfgraph*}(35,30)\n";
  fprintf tex "\fmfpen{.1pt}\n";
  fprintf tex "\fmfset{arrow_len}{2mm}\n";
  fprintf tex "\fmfleft{i1,i%s}\n" (to_string i2);
  fprintf tex "\fmfright{o%s}\n" (String.concat ",o" out);
  List.iter (fun s → fprintf tex "\fmflabel{${s$}{i%s}\n" s s)
    ["1"; (to_string i2)];
  List.iter (fun s → fprintf tex "\fmflabel{${s$}{o%s}\n" s s) out;
  edges_feynmf tex to_string i2 t';
  fprintf tex "\end{fmfgraph*}}\n"

let to_feynmf_latex file to_string i2 t =
  if !latex then
    let tex = open_out (file ^ ".tex") in
    fprintf tex "\documentclass[10pt]{article}\n";
    fprintf tex "\usepackage{feynmp}\n";
    fprintf tex "\textwidth18.5cm\n";
    fprintf tex "\evensidemargin1.5cm\n";
    fprintf tex "\oddsidemargin1.5cm\n";
    fprintf tex "\setlength{\unitlength}{1mm}\n";
    fprintf tex "\begin{document}\n";
    fprintf tex "\begin{fmffile}{%s.fmf}\n" file;
    List.iter (to_feynmf_channel tex to_string i2) t;

```

```

    fprintf tex "\n";
    fprintf tex "\\end{fmffile}\n";
    fprintf tex "\\end{document}\n";
    close_out tex
  else
    let tex = open_out file in
      List.iter (to_feynmf_channel tex to_string i2) t;
      close_out tex
let vanilla = { style = None; rev = false; label = None; tension = None }
let sty (s, r, l) = { vanilla with style = Some s; rev = r; label = Some l }

```

Q.2.4 Least Squares Layout

$$L = \frac{1}{2} \sum_{i \neq i'} T_{ii'} (x_i - x_{i'})^2 + \frac{1}{2} \sum_{i,j} T'_{ij} (x_i - e_j)^2 \quad (\text{Q.11})$$

and thus

$$0 = \frac{\partial L}{\partial x_i} = \sum_{i' \neq i} T_{ii'} (x_i - x_{i'}) + \sum_j T'_{ij} (x_i - e_j) \quad (\text{Q.12})$$

or

$$\left(\sum_{i' \neq i} T_{ii'} + \sum_j T'_{ij} \right) x_i - \sum_{i' \neq i} T_{ii'} x_{i'} = \sum_j T'_{ij} e_j \quad (\text{Q.13})$$

where we can assume that

$$T_{ii'} = T_{i'i} \quad (\text{Q.14a})$$

$$T_{ii} = 0 \quad (\text{Q.14b})$$

```

type α node_with_tension = { node : α; tension : float }
let unit_tension t =
  map (fun n → { node = n; tension = 1.0 }) (fun l → l) t
let leaves_and_nodes i2 t =
  let t' = sort_2i (≤) i2 t in
  match nodes t' with
  | [] → failwith "Tree.nodes_and_leafs: impossible"
  | i1 :: _ as n → (i1, i2, List.filter (fun l → l ≠ i2) (leafs t'), n)

```

Not tail recursive, but they're unlikely to meet any deep trees:

```

let rec internal_edges_from n = function
| Leaf _ → []
| Node (n', ch) → (n', n) :: (ThoList.flatmap (internal_edges_from n') ch)

```

The root node of the tree represents a vertex (node) and an external line (leaf) of the Feynman diagram simultaneously. Thus it requires special treatment:

```

let internal_edges = function
| Leaf _ → []

```

```

| Node (n, ch) → ThoList.flatmap (internal_edges_from n) ch

let rec external_edges_from n = function
| Leaf (n', -) → [(n', n)]
| Node (n', ch) → ThoList.flatmap (external_edges_from n') ch

let external_edges = function
| Leaf (n, -) → [(n, n)]
| Node (n, ch) → (n, n) :: ThoList.flatmap (external_edges_from n) ch

type ('edge, 'node, 'ext) graph =
{ int_nodes : 'node array;
  ext_nodes : 'ext array;
  int_edges : ('edge × int × int) list;
  ext_edges : ('edge × int × int) list }

module M = Pmap.Tree

Invert an array, viewed as a map from non-negative integers into a set. The
result is a map from the set to the integers: val invert_array :  $\alpha$  array →
( $\alpha$ , int) M.t

let invert_array_unsafe a =
fst (Array.fold_left (fun (m, i) a_i →
  (M.add compare a_i i m, succ i)) (M.empty, 0) a)

exception Not_invertible

let add_unique key data map =
if M.mem compare key map then
  raise Not_invertible
else
  M.add compare key data map

let invert_array a =
fst (Array.fold_left (fun (m, i) a_i →
  (add_unique a_i i m, succ i)) (M.empty, 0) a)

let graph_of_tree nodes2edge conjugate i2 t =
let i1, out, vertices = leafs_and_nodes i2 t in
let int_nodes = Array.of_list vertices
and ext_nodes = Array.of_list (conjugate i1 :: i2 :: out) in
let int_nodes_index_table = invert_array int_nodes
and ext_nodes_index_table = invert_array ext_nodes in
let int_nodes_index n = M.find compare n int_nodes_index_table
and ext_nodes_index n = M.find compare n ext_nodes_index_table in
{ int_nodes = int_nodes;
  ext_nodes = ext_nodes;
  int_edges = List.map
    (fun (n1, n2) →
      (nodes2edge n1 n2, int_nodes_index n1, int_nodes_index n2))
    (internal_edges t);
  ext_edges = List.map
    (fun (e, n) →
      let e' =

```

```

        if  $e = i1$  then
            conjugate  $e$ 
        else
             $e$  in
                (nodes2edge  $e'$   $n$ , ext_nodes_index  $e'$ , int_nodes_index  $n$ )
            (external_edges  $t$ ) }
let int_incidence  $f$  null  $g$  =
    let  $n$  = Array.length  $g.int\_nodes$  in
    let incidence = Array.make_matrix  $n$   $n$  null in
    List.iter (fun (edge,  $n1$ ,  $n2$ ) →
        if  $n1 \neq n2$  then begin
            let  $edge'$  =  $f$  edge  $g.int\_nodes.(n1)$   $g.int\_nodes.(n2)$  in
            incidence.( $n1$ ).( $n2$ ) ←  $edge'$ ;
            incidence.( $n2$ ).( $n1$ ) ←  $edge'$ 
        end)
     $g.int\_edges$ ;
    incidence
let ext_incidence  $f$  null  $g$  =
    let  $n\_int$  = Array.length  $g.int\_nodes$ 
    and  $n\_ext$  = Array.length  $g.ext\_nodes$  in
    let incidence = Array.make_matrix  $n\_int$   $n\_ext$  null in
    List.iter (fun (edge,  $e$ ,  $n$ ) →
        incidence.( $n$ ).( $e$ ) ←  $f$  edge  $g.ext\_nodes.(e)$   $g.int\_nodes.(n)$ )
     $g.ext\_edges$ ;
    incidence
let division  $n$  =
    if  $n < 0$  then
        []
    else if  $n = 1$  then
        [0.5]
    else
        let  $n'$  = pred  $n$  in
        let  $d$  = 1.0 /. (float  $n'$ ) in
        let rec division'  $i$  acc =
            if  $i < 0$  then
                acc
            else
                division' (pred  $i$ ) (float  $i$  *.  $d$  :: acc) in
        division'  $n'$  []
type ( $\varepsilon$ ,  $\nu$ , 'ext) ext_layout = ( $\varepsilon$ ,  $\nu$ , 'ext × float × float) graph
type ( $\varepsilon$ ,  $\nu$ , 'ext) layout = ( $\varepsilon$ ,  $\nu$  × float × float, 'ext) ext_layout
let left_to_right num_in  $g$  =
    if num_in < 1 then
        invalid_arg "left_to_right"
    else
        let num_out = Array.length  $g.ext\_nodes$  - num_in in
        if num_out < 1 then
            invalid_arg "left_to_right"

```



```

else
  let incoming =
    List.map2 (fun e y → (e, 0.0, y))
      (Array.to_list (Array.sub g.ext_nodes 0 num_in))
      (division num_in)
  and outgoing =
    List.map2 (fun e y → (e, 1.0, y))
      (Array.to_list (Array.sub g.ext_nodes num_in num_out))
      (division num_out) in
  { g with ext_nodes = Array.of_list (incoming @ outgoing) }

```

Reformulating (Q.13)

$$Ax = b_x \quad (\text{Q.15a})$$

$$Ay = b_y \quad (\text{Q.15b})$$

with

$$A_{ii'} = \left(\sum_{i'' \neq i} T_{ii''} + \sum_j T'_{ij} \right) \delta_{ii'} - T_{ii'} \quad (\text{Q.16a})$$

$$(b_{x/y})_i = \sum_j T'_{ij} (e_{x/y})_j \quad (\text{Q.16b})$$

```

let sum a = Array.fold_left (+.) 0.0 a
let tension_to_equation t t' e =
  let xe, ye = List.split e in
  let bx = Linalg.matmulv t' (Array.of_list xe)
  and by = Linalg.matmulv t' (Array.of_list ye)
  and a = Array.init (Array.length t)
    (fun i →
      let a_i = Array.map (~-. ) t.(i) in
      a_i.(i) ← a_i.(i) + . sum t.(i) + . sum t'.(i);
      a_i) in
  (a, bx, by)
let layout g =
  let ext_nodes =
    List.map (fun (_, x, y) → (x, y)) (Array.to_list g.ext_nodes) in
  let a, bx, by =
    tension_to_equation
      (int_incidence (fun _ _ → 1.0) 0.0 g)
      (ext_incidence (fun _ _ → 1.0) 0.0 g) ext_nodes in
  match Linalg.solve_many a [bx; by] with
  | [x; y] → { g with int_nodes = Array.mapi
    (fun i n → (n, x.(i), y.(i))) g.int_nodes }
  | _ → failwith "impossible"
let iter_edges f g =
  List.iter (fun (edge, n1, n2) →
    let _, x1, y1 = g.int_nodes.(n1)

```

```

    and _, x2, y2 = g.int_nodes.(n2) in
      f edge (x1, y1) (x2, y2)) g.int_edges;
  List.iter (fun (edge, e, n) →
    let _, x1, y1 = g.ext_nodes.(e)
    and _, x2, y2 = g.int_nodes.(n) in
      f edge (x1, y1) (x2, y2)) g.ext_edges

let iter_internal f g =
  Array.iter (fun (node, x, y) → f (x, y)) g.int_nodes

let iter_incoming f g =
  f g.ext_nodes.(0);
  f g.ext_nodes.(1)

let iter_outgoing f g =
  for i = 2 to pred (Array.length g.ext_nodes) do
    f g.ext_nodes.(i)
  done

let dump g =
  Array.iter (fun (_, x, y) → Printf.eprintf "(%g,%g)␣" x y) g.ext_nodes;
  Printf.eprintf "\n␣=>␣";
  Array.iter (fun (_, x, y) → Printf.eprintf "(%g,%g)␣" x y) g.int_nodes;
  Printf.eprintf "\n"

```

—R—

DEPENDENCY TREES

R.1 Interface of Tree2

Dependency trees for wavefunctions.

```

type (ν, ε) t
val cons : (ε × ν × (ν, ε) t list) list → (ν, ε) t
val leaf : ν → (ν, ε) t
val to_string : (ν → string) → (ε → string) → (ν, ε) t → string

```

R.2 Implementation of Tree2

Dependency trees for wavefunctions.

```

type (ν, ε) t =
  | Node of (ε × ν × (ν, ε) t list) list
  | Leaf of ν

let leaf node = Leaf node

let sort_children (edge, node, children) =
  (edge, node, List.sort compare children)

let cons fusions = Node (List.sort compare (List.map sort_children fusions))

let rec to_string n2s e2s = function
  | Leaf n → n2s n
  | Node children →
      "{" ^
      String.concat "," ^
      (List.map
        (fun (e, n, ch_list) →
          e2s e ^ ":" ^ n2s n ^
          "<(" ^ (String.concat ";" ^ (List.map (to_string n2s e2s) ch_list)) ^ ")")
        children) ^
      "}"

```

—S—
CONSISTENCY CHECKS



Application count.ml unavailable!

—T—

COMPLEX NUMBERS



Interface `complex.mli` unavailable!



Implementation `complex.ml` unavailable!

—U— ALGEBRA

U.1 Interface of Algebra

U.1.1 Coefficients

For our algebra, we need coefficient rings.

```
module type CRing =  
  sig  
    type t  
    val null : t  
    val unit : t  
    val mul : t → t → t  
    val add : t → t → t  
    val sub : t → t → t  
    val neg : t → t  
    val to_string : t → string  
  end
```

And rational numbers provide a particularly important example:

```
module type Rational =  
  sig  
    include CRing  
    val is_null : t → bool  
    val is_unit : t → bool  
    val make : int → int → t  
    val to_ratio : t → int × int  
    val to_float : t → float  
  end
```

U.1.2 Naive Rational Arithmetic



This *is* dangerous and will overflow even for simple applications. The production code will have to be linked to a library for large integer arithmetic.

```
module Small_Rational : Rational
```

U.1.3 Expressions: Terms, Rings and Linear Combinations

The tensor algebra will be spanned by an abelian monoid:

module type *Term* =

```
sig
  type  $\alpha$  t
  val unit : unit  $\rightarrow$   $\alpha$  t
  val is_unit :  $\alpha$  t  $\rightarrow$  bool
  val atom :  $\alpha \rightarrow \alpha$  t
  val power : int  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$  t
  val mul :  $\alpha$  t  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$  t
  val map : ( $\alpha \rightarrow \beta$ )  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\beta$  t
  val to_string : ( $\alpha \rightarrow$  string)  $\rightarrow$   $\alpha$  t  $\rightarrow$  string
```

The derivative of a term is *not* a term, but a sum of terms instead:

$$D(f_1^{p_1} f_2^{p_2} \dots f_n^{p_n}) = \sum_i (Df_i) p_i f_1^{p_1} f_2^{p_2} \dots f_i^{p_i-1} \dots f_n^{p_n} \quad (\text{U.1})$$

The function returns the sum as a list of triples $(Df_i, p_i, f_1^{p_1} f_2^{p_2} \dots f_i^{p_i-1} \dots f_n^{p_n})$. Summing the terms is left to the calling module and the Df_i are *not* guaranteed to be different. NB: The function implementating the inner derivative, is supposed to return *Some* Df_i and *None*, iff Df_i vanishes.

```
val derive : ( $\alpha \rightarrow \beta$  option)  $\rightarrow$   $\alpha$  t  $\rightarrow$  ( $\beta \times$  int  $\times$   $\alpha$  t) list
```

convenience function

```
val product :  $\alpha$  t list  $\rightarrow$   $\alpha$  t
val atoms :  $\alpha$  t  $\rightarrow$   $\alpha$  list
```

end

module type *Ring* =

```
sig
  module C : Rational
  type  $\alpha$  t
  val null : unit  $\rightarrow$   $\alpha$  t
  val unit : unit  $\rightarrow$   $\alpha$  t
  val is_null :  $\alpha$  t  $\rightarrow$  bool
  val is_unit :  $\alpha$  t  $\rightarrow$  bool
  val atom :  $\alpha \rightarrow \alpha$  t
  val scale : C.t  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$  t
  val add :  $\alpha$  t  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$  t
  val sub :  $\alpha$  t  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$  t
  val mul :  $\alpha$  t  $\rightarrow$   $\alpha$  t  $\rightarrow$   $\alpha$  t
  val neg :  $\alpha$  t  $\rightarrow$   $\alpha$  t
```

Again

$$D(f_1^{p_1} f_2^{p_2} \dots f_n^{p_n}) = \sum_i (Df_i) p_i f_1^{p_1} f_2^{p_2} \dots f_i^{p_i-1} \dots f_n^{p_n} \quad (\text{U.2})$$

but, iff Df_i can be identified with a f' , we know how to perform the sum.

```
val derive_inner : ( $\alpha \rightarrow \alpha t$ )  $\rightarrow \alpha t \rightarrow \alpha t$  (* this? *)
val derive_inner' : ( $\alpha \rightarrow \alpha t option$ )  $\rightarrow \alpha t \rightarrow \alpha t$  (* or that? *)
```

Below, we will need partial derivatives that lead out of the ring: *derive_outer* *derive_atom* *term* returns a list of partial derivatives β with non-zero coefficients α t :

```
val derive_outer : ( $\alpha \rightarrow \beta option$ )  $\rightarrow \alpha t \rightarrow (\beta \times \alpha t) list$ 
```

convenience functions

```
val sum :  $\alpha t list \rightarrow \alpha t$ 
```

```
val product :  $\alpha t list \rightarrow \alpha t$ 
```

The list of all generators appearing in an expression:

```
val atoms :  $\alpha t \rightarrow \alpha list$ 
```

```
val to_string : ( $\alpha \rightarrow string$ )  $\rightarrow \alpha t \rightarrow string$ 
```

end

module type *Linear* =

sig

module *C* : *Ring*

type (α, γ) *t*

```
val null : unit  $\rightarrow (\alpha, \gamma) t$ 
```

```
val atom :  $\alpha \rightarrow (\alpha, \gamma) t$ 
```

```
val singleton :  $\gamma C.t \rightarrow \alpha \rightarrow (\alpha, \gamma) t$ 
```

```
val scale :  $\gamma C.t \rightarrow (\alpha, \gamma) t \rightarrow (\alpha, \gamma) t$ 
```

```
val add : ( $\alpha, \gamma$ ) t  $\rightarrow (\alpha, \gamma) t \rightarrow (\alpha, \gamma) t$ 
```

```
val sub : ( $\alpha, \gamma$ ) t  $\rightarrow (\alpha, \gamma) t \rightarrow (\alpha, \gamma) t$ 
```

A partial derivative w.r.t. a vector maps from a coefficient ring to the dual vector space.

```
val partial : ( $\gamma \rightarrow (\alpha, \gamma) t$ )  $\rightarrow \gamma C.t \rightarrow (\alpha, \gamma) t$ 
```

A linear combination of vectors

$$linear[(v_1, c_1); (v_2, c_2); \dots; (v_n, c_n)] = \sum_{i=1}^n c_i \cdot v_i \quad (\text{U.3})$$

```
val linear : (( $\alpha, \gamma$ ) t  $\times \gamma C.t$ ) list  $\rightarrow (\alpha, \gamma) t$ 
```

Some convenience functions

```
val map : ( $\alpha \rightarrow \gamma C.t \rightarrow (\beta, \delta) t$ )  $\rightarrow (\alpha, \gamma) t \rightarrow (\beta, \delta) t$ 
```

```
val sum : ( $\alpha, \gamma$ ) t list  $\rightarrow (\alpha, \gamma) t$ 
```

The list of all generators and the list of all generators of coefficients appearing in an expression:

```
val atoms : ( $\alpha, \gamma$ ) t  $\rightarrow \alpha list \times \gamma list$ 
```

```
val to_string : ( $\alpha \rightarrow string$ )  $\rightarrow (\gamma \rightarrow string) \rightarrow (\alpha, \gamma) t \rightarrow string$ 
```

end

module *Term* : *Term*

module *Make_Ring* (*C* : *Rational*) (*T* : *Term*) : *Ring*

module *Make_Linear* (*C* : *Ring*) : *Linear* with module *C* = *C*

U.2 Implementation of Algebra

The terms will be small and there's no need to be fancy and/or efficient. It's more important to have a unique representation.

```
module PM = Pmap.List
```

U.2.1 Coefficients

For our algebra, we need coefficient rings.

```
module type CRing =
sig
  type t
  val null : t
  val unit : t
  val mul : t → t → t
  val add : t → t → t
  val sub : t → t → t
  val neg : t → t
  val to_string : t → string
end
```

And rational numbers provide a particularly important example:

```
module type Rational =
sig
  include CRing
  val is_null : t → bool
  val is_unit : t → bool
  val make : int → int → t
  val to_ratio : t → int × int
  val to_float : t → float
end
```

U.2.2 Naive Rational Arithmetic



This *is* dangerous and will overflow even for simple applications. The production code will have to be linked to a library for large integer arithmetic.

Anyway, here's Euclid's algorithm:

```
let rec gcd i1 i2 =
  if i2 = 0 then
    abs i1
  else
    gcd i2 (i1 mod i2)
let lcm i1 i2 = (i1 / gcd i1 i2) × i2
```

```

module Small_Rational : Rational =
  struct
    type t = int × int
    let is_null (n, -) = (n = 0)
    let is_unit (n, d) = (n ≠ 0) ∧ (n = d)
    let null = (0, 1)
    let unit = (1, 1)
    let make n d =
      let c = gcd n d in
      (n / c, d / c)
    let mul (n1, d1) (n2, d2) = make (n1 × n2) (d1 × d2)
    let add (n1, d1) (n2, d2) = make (n1 × d2 + n2 × d1) (d1 × d2)
    let sub (n1, d1) (n2, d2) = make (n1 × d2 - n2 × d1) (d1 × d2)
    let neg (n, d) = (-n, d)
    let to_ratio (n, d) =
      if d < 0 then
        (-n, -d)
      else
        (n, d)
    let to_float (n, d) = float n /. float d
    let to_string (n, d) =
      if d = 1 then
        Printf.sprintf "%d" n
      else
        Printf.sprintf "(%d/%d)" n d
  end
end

```

U.2.3 Expressions: Terms, Rings and Linear Combinations

The tensor algebra will be spanned by an abelian monoid:

```

module type Term =
  sig
    type  $\alpha$  t
    val unit : unit →  $\alpha$  t
    val is_unit :  $\alpha$  t → bool
    val atom :  $\alpha$  →  $\alpha$  t
    val power : int →  $\alpha$  t →  $\alpha$  t
    val mul :  $\alpha$  t →  $\alpha$  t →  $\alpha$  t
    val map : ( $\alpha$  →  $\beta$ ) →  $\alpha$  t →  $\beta$  t
    val to_string : ( $\alpha$  → string) →  $\alpha$  t → string
    val derive : ( $\alpha$  →  $\beta$  option) →  $\alpha$  t → ( $\beta$  × int ×  $\alpha$  t) list
    val product :  $\alpha$  t list →  $\alpha$  t
    val atoms :  $\alpha$  t →  $\alpha$  list
  end

module type Ring =
  sig
    module C : Rational
    type  $\alpha$  t
  end

```

```

val null : unit →  $\alpha$  t
val unit : unit →  $\alpha$  t
val is_null :  $\alpha$  t → bool
val is_unit :  $\alpha$  t → bool
val atom :  $\alpha$  →  $\alpha$  t
val scale :  $C.t$  →  $\alpha$  t →  $\alpha$  t
val add :  $\alpha$  t →  $\alpha$  t →  $\alpha$  t
val sub :  $\alpha$  t →  $\alpha$  t →  $\alpha$  t
val mul :  $\alpha$  t →  $\alpha$  t →  $\alpha$  t
val neg :  $\alpha$  t →  $\alpha$  t
val derive_inner : ( $\alpha$  →  $\alpha$  t) →  $\alpha$  t →  $\alpha$  t (* this? *)
val derive_inner' : ( $\alpha$  →  $\alpha$  t option) →  $\alpha$  t →  $\alpha$  t (* or that? *)
val derive_outer : ( $\alpha$  →  $\beta$  option) →  $\alpha$  t → ( $\beta \times \alpha$  t) list
val sum :  $\alpha$  t list →  $\alpha$  t
val product :  $\alpha$  t list →  $\alpha$  t
val atoms :  $\alpha$  t →  $\alpha$  list
val to_string : ( $\alpha$  → string) →  $\alpha$  t → string
end

module type Linear =
sig
  module C : Ring
  type ( $\alpha$ ,  $\gamma$ ) t
  val null : unit → ( $\alpha$ ,  $\gamma$ ) t
  val atom :  $\alpha$  → ( $\alpha$ ,  $\gamma$ ) t
  val singleton :  $\gamma$  C.t →  $\alpha$  → ( $\alpha$ ,  $\gamma$ ) t
  val scale :  $\gamma$  C.t → ( $\alpha$ ,  $\gamma$ ) t → ( $\alpha$ ,  $\gamma$ ) t
  val add : ( $\alpha$ ,  $\gamma$ ) t → ( $\alpha$ ,  $\gamma$ ) t → ( $\alpha$ ,  $\gamma$ ) t
  val sub : ( $\alpha$ ,  $\gamma$ ) t → ( $\alpha$ ,  $\gamma$ ) t → ( $\alpha$ ,  $\gamma$ ) t
  val partial : ( $\gamma$  → ( $\alpha$ ,  $\gamma$ ) t) →  $\gamma$  C.t → ( $\alpha$ ,  $\gamma$ ) t
  val linear : (( $\alpha$ ,  $\gamma$ ) t ×  $\gamma$  C.t) list → ( $\alpha$ ,  $\gamma$ ) t
  val map : ( $\alpha$  →  $\gamma$  C.t → ( $\beta$ ,  $\delta$ ) t) → ( $\alpha$ ,  $\gamma$ ) t → ( $\beta$ ,  $\delta$ ) t
  val sum : ( $\alpha$ ,  $\gamma$ ) t list → ( $\alpha$ ,  $\gamma$ ) t
  val atoms : ( $\alpha$ ,  $\gamma$ ) t →  $\alpha$  list ×  $\gamma$  list
  val to_string : ( $\alpha$  → string) → ( $\gamma$  → string) → ( $\alpha$ ,  $\gamma$ ) t → string
end

module Term : Term =
struct
  module M = PM
  type  $\alpha$  t = ( $\alpha$ , int) M.t
  let unit () = M.empty
  let is_unit = M.is_empty
  let atom f = M.singleton f 1
  let power p x = M.map (( × ) p) x
  let insert1 binop f p term =
    let p' = binop (try M.find compare f term with Not_found → 0) p in
    if p' = 0 then

```

```

      M.remove compare f term
    else
      M.add compare f p' term

let mul1 f p term = insert1 (+) f p term
let mul x y = M.fold mul1 x y

let map f term = M.fold (fun t → mul1 (f t)) term M.empty

let to_string fmt term =
  String.concat "*"
  (M.fold (fun f p acc →
    (if p = 0 then
      "1"
    else if p = 1 then
      fmt f
    else
      "[" ^ fmt f ^ "]" ^ string_of_int p) :: acc) term [])

let derive derive1 x =
  M.fold (fun f p dx →
    if p ≠ 0 then
      match derive1 f with
      | Some df → (df, p, mul1 f (pred p) (M.remove compare f x)) :: dx
      | None → dx
    else
      dx) x []

let product factors =
  List.fold_left mul (unit ()) factors

let atoms t =
  List.map fst (PM.elements t)

end

module Make_Ring (C : Rational) (T : Term) : Ring =
struct

  module C = C
  let one = C.unit

  module M = PM

  type α t = (α T.t, C.t) M.t

  let null () = M.empty
  let is_null = M.is_empty

  let power t p = M.singleton t p
  let unit () = power (T.unit ()) one

  let is_unit t = unit () = t

```



The following should be correct too, but produces too many false positives instead! What's going on?

```

let broken__is_unit t =
  match M.elements t with
  | [(t, p)] → T.is_unit t ∨ C.is_null p
  | _ → false
let atom t = power (T.atom t) one
let scale c x = M.map (C.mul c) x
let insert1 binop t c sum =
  let c' = binop (try M.find compare t sum with Not_found → C.null) c in
  if C.is_null c' then
    M.remove compare t sum
  else
    M.add compare t c' sum

```

```
let add x y = M.fold (insert1 C.add) x y
```

```
let sub x y = M.fold (insert1 C.sub) y x
```

One might be tempted to use *Product.outer_self* *M.fold* instead, but this would require us to combine *tx* and *cx* to *(tx, cx)*.

```

let fold2 f x y =
  M.fold (fun tx cx → M.fold (f tx cx) y) x
let mul x y =
  fold2 (fun tx cx ty cy → insert1 C.add (T.mul tx ty) (C.mul cx cy))
    x y (null ())
let neg x =
  sub (null ()) x
let neg x =
  scale (C.neg C.unit) x

```

Multiply the *derivatives* by *c* and add the result to *dx*.

```

let add_derivatives derivatives c dx =
  List.fold_left (fun acc (df, dt_c, dt_t) →
    add (mul df (power dt_t (C.mul c (C.make dt_c 1)))) acc) dx derivatives
let derive_inner derive1 x =
  M.fold (fun t →
    add_derivatives (T.derive (fun f → Some (derive1 f)) t)) x (null ())
let derive_inner' derive1 x =
  M.fold (fun t → add_derivatives (T.derive derive1 t)) x (null ())
let collect_derivatives derivatives c dx =
  List.fold_left (fun acc (df, dt_c, dt_t) →
    (df, power dt_t (C.mul c (C.make dt_c 1))) :: acc) dx derivatives
let derive_outer derive1 x =
  M.fold (fun t → collect_derivatives (T.derive derive1 t)) x []
let sum terms =
  List.fold_left add (null ()) terms

```

```

let product factors =
  List.fold_left mul (unit ()) factors

let atoms t =
  ThoList.uniq (List.sort compare
    (ThoList.flatmap (fun (t, _) → T.atoms t) (PM.elements t)))

let to_string fmt sum =
  "(" ^ String.concat "□+□"
    (M.fold (fun t c acc →
      if C.is_null c then
        acc
      else if C.is_unit c then
        T.to_string fmt t :: acc
      else if C.is_unit (C.neg c) then
        ("(-" ^ T.to_string fmt t ^ ")") :: acc
      else
        (C.to_string c ^ "*" ^ T.to_string fmt t ^ ")") :: acc) sum []) ^ ")"

end

module Make_Linear (C : Ring) : Linear with module C = C =
struct
  module C = C
  module M = PM
  type (α, γ) t = (α, γ C.t) M.t
  let null () = M.empty
  let is_null = M.is_empty
  let atom a = M.singleton a (C.unit ())
  let singleton c a = M.singleton a c
  let scale c x = M.map (C.mul c) x
  let insert1 binop t c sum =
    let c' = binop (try M.find compare t sum with Not_found → C.null ()) c in
    if C.is_null c' then
      M.remove compare t sum
    else
      M.add compare t c' sum
  let add x y = M.fold (insert1 C.add) x y
  let sub x y = M.fold (insert1 C.sub) y x
  let map f t =
    M.fold (fun a c → add (f a c)) t M.empty
  let sum terms =
    List.fold_left add (null ()) terms
  let linear terms =
    List.fold_left (fun acc (a, c) → add (scale c a) acc) (null ()) terms
  let partial_derive t =
    let d t' =

```

```

    let dt' = derive t' in
    if is_null dt' then
      None
    else
      Some dt' in
    linear (C.derive_outer d t)

let atoms t =
  let a, c = List.split (PM.elements t) in
  (a, ThoList.uniq (List.sort compare (ThoList.flatmap C.atoms c)))

let to_string fmt cfmt sum =
  "(" ^ String.concat "□+□"
    (M.fold (fun t c acc →
      if C.is_null c then
        acc
      else if C.is_unit c then
        fmt t :: acc
      else if C.is_unit (C.neg c) then
        ("(-" ^ fmt t ^ ")") :: acc
      else
        (C.to_string cfmt c ^ "*" ^ fmt t) :: acc)
    sum []) ^ ")")
end

```

—V—

SIMPLE LINEAR ALGEBRA

V.1 Interface of Linalg

```
exception Singular
exception Not_Square

val copy_matrix : float array array → float array array
val matmul : float array array → float array array → float array array
val matmulv : float array array → float array → float array
val lu_decompose : float array array → float array array × float array array
val solve : float array array → float array → float array
val solve_many : float array array → float array list → float array list
```

V.2 Implementation of Linalg

This is not a functional implementations, but uses imperative array in Fortran style for maximum speed.

```
exception Singular
exception Not_Square

let copy_matrix a =
  Array.init (Array.length a)
    (fun i → Array.copy a.(i))

let matmul a b =
  let ni = Array.length a
  and nj = Array.length b.(0)
  and n = Array.length b in
  let ab = Array.make_matrix ni nj 0.0 in
  for i = 0 to pred ni do
    for j = 0 to pred nj do
      for k = 0 to pred n do
        ab.(i).(j) ← ab.(i).(j) + . a.(i).(k) * . b.(k).(j)
      done
    done
  done;
  ab
```



```

let matmulv a v =
  let na = Array.length a in
  let nv = Array.length v in
  let v' = Array.make na 0.0 in
  for i = 0 to pred na do
    for j = 0 to pred nv do
      v'.(i) ← v'.(i) + . a.(i).(j) *. v.(j)
    done
  done;
  v'

let maxabsval a : float =
  let x = ref (abs_float a.(0)) in
  for i = 1 to Array.length a - 1 do
    x := max !x (abs_float a.(i))
  done;
  !x

```

V.2.1 LU Decomposition

$$A = LU \quad (\text{V.1a})$$

In more detail

$$\begin{pmatrix} a_{00} & a_{01} & \dots & a_{0(n-1)} \\ a_{10} & a_{11} & \dots & a_{1(n-1)} \\ \vdots & \vdots & \ddots & \vdots \\ a_{(n-1)0} & a_{(n-1)1} & \dots & a_{(n-1)(n-1)} \end{pmatrix} = \begin{pmatrix} 1 & 0 & \dots & 0 \\ l_{10} & 1 & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ l_{(n-1)0} & l_{(n-1)1} & \dots & 1 \end{pmatrix} \begin{pmatrix} u_{00} & u_{01} & \dots & u_{0(n-1)} \\ 0 & u_{11} & \dots & u_{1(n-1)} \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & u_{(n-1)(n-1)} \end{pmatrix} \quad (\text{V.1b})$$

Rewriting (V.1) in block matrix notation

$$\begin{pmatrix} a_{00} & a_{0\cdot} \\ a_{\cdot 0} & A \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ l_{\cdot 0} & L \end{pmatrix} \begin{pmatrix} u_{00} & u_{0\cdot} \\ 0 & U \end{pmatrix} = \begin{pmatrix} u_{00} & u_{0\cdot} \\ l_{\cdot 0} u_{00} & l_{\cdot 0} \otimes u_{0\cdot} + LU \end{pmatrix} \quad (\text{V.2})$$

we can solve it easily

$$u_{00} = a_{00} \quad (\text{V.3a})$$

$$u_{0\cdot} = a_{0\cdot} \quad (\text{V.3b})$$

$$l_{\cdot 0} = \frac{a_{\cdot 0}}{a_{00}} \quad (\text{V.3c})$$

$$LU = A - \frac{a_{\cdot 0} \otimes a_{0\cdot}}{a_{00}} \quad (\text{V.3d})$$

and (V.3c) and (V.3d) define a simple iterative algorithm if we work from the outside in. It just remains to add pivoting.

```

let swap a i j =
  let a_i = a.(i) in
  a.(i) ← a.(j);
  a.(j) ← a_i

let pivot_column v a n =
  let n' = ref n
  and max_va = ref (v.(n) *. (abs_float a.(n).(n))) in
  for i = succ n to Array.length v - 1 do
    let va_i = v.(i) *. (abs_float a.(i).(n)) in
    if va_i > !max_va then begin
      n' := i;
      max_va := va_i
    end
  done;
  !n'

let lu_decompose_in_place a =
  let n = Array.length a in
  let eps = ref 1
  and pivots = Array.make n 0
  and v =
    try
      Array.init n (fun i →
        let a_i = a.(i) in
        if Array.length a_i ≠ n then
          raise Not_Square;
        1.0 /. (maxabsval a_i))
    with
    | Division_by_zero → raise Singular in
  for i = 0 to pred n do
    let pivot = pivot_column v a i in
    if pivot ≠ i then begin
      swap a pivot i;
      eps := - !eps;
      v.(pivot) ← v.(i)
    end;
    pivots.(i) ← pivot;
    let inv_a_ii =
      try 1.0 /. a.(i).(i) with Division_by_zero → raise Singular in
    for j = succ i to pred n do
      a.(j).(i) ← inv_a_ii *. a.(j).(i)
    done;
    for j = succ i to pred n do
      for k = succ i to pred n do
        a.(j).(k) ← a.(j).(k) - . a.(j).(i) *. a.(i).(k)
      done
    done
  done;
  (pivots, !eps)

```

```

let lu_decompose_split a pivots =
  let n = Array.length pivots in
  let l = Array.make_matrix n n 0.0 in
  let u = Array.make_matrix n n 0.0 in
  for i = 0 to pred n do
    l.(i).(i) ← 1.0;
    for j = succ i to pred n do
      l.(j).(i) ← a.(j).(i)
    done
  done;
  for i = pred n downto 0 do
    swap l i pivots.(i)
  done;
  for i = 0 to pred n do
    for j = 0 to i do
      u.(j).(i) ← a.(j).(i)
    done
  done;
  (l, u)

let lu_decompose a =
  let a = copy_matrix a in
  let pivots, _ = lu_decompose_in_place a in
  lu_decompose_split a pivots

let lu_backsubstitute a pivots b =
  let n = Array.length a in
  let nonzero = ref (-1) in
  let b = Array.copy b in
  for i = 0 to pred n do
    let ll = pivots.(i) in
    let b_i = ref (b.(ll)) in
    b.(ll) ← b.(i);
    if !nonzero ≥ 0 then
      for j = !nonzero to pred i do
        b_i := !b_i - . a.(i).(j) * . b.(j)
      done
    else if !b_i ≠ 0.0 then
      nonzero := i;
      b.(i) ← !b_i
  done;
  for i = pred n downto 0 do
    let b_i = ref (b.(i)) in
    for j = succ i to pred n do
      b_i := !b_i - . a.(i).(j) * . b.(j)
    done;
    b.(i) ← !b_i / . a.(i).(i)
  done;
  b

let solve_destructive a b =
  let pivot, _ = lu_decompose_in_place a in

```

```
    lu_backsubstitute a pivot b  
  
let solve_many_destructive a bs =  
  let pivot, _ = lu_decompose_in_place a in  
    List.map (lu_backsubstitute a pivot) bs  
  
let solve a b =  
  solve_destructive (copy_matrix a) b  
  
let solve_many a bs =  
  solve_many_destructive (copy_matrix a) bs
```

—W—

TALK TO THE WHIZARD . . .

Talk to [\[11\]](#).



Temporarily disabled, until, we implement some conditional weaving . . .

—X—

FORTTRAN LIBRARIES

X.1 Trivia

```
<omega_spinors.f90>≡
  <Cotypeleft>
  module omega_spinors
    use kinds
    use constants
    implicit none
    private
    public :: operator (*), operator (+), operator (-)
    public :: abs
    <intrinsic :: abs>
    type, public :: conjspinor
      ! private (omegalib needs access, but DON'T TOUCH IT!)
      complex(kind=default), dimension(4) :: a
    end type conjspinor
    type, public :: spinor
      ! private (omegalib needs access, but DON'T TOUCH IT!)
      complex(kind=default), dimension(4) :: a
    end type spinor
    <Declaration of operations for spinors>
    integer, parameter, public :: omega_spinors_2010_01_A = 0
  contains
    <Implementation of operations for spinors>
  end module omega_spinors
```

```
<intrinsic :: abs (if working)>≡
  intrinsic :: abs
```

```
<intrinsic :: conjg (if working)>≡
  intrinsic :: conjg
```

well, the Intel Fortran Compiler chokes on these with an internal error:

```
<intrinsic :: abs>≡
```

```
<intrinsic :: conjg>≡
```

X.1.1 Inner Product

```
<Declaration of operations for spinors>≡
```

```

interface operator (*)
  module procedure conjspinor_spinor
end interface
private :: conjspinor_spinor

```

$$\bar{\psi}\psi' \quad (X.1)$$

NB: `dot_product` conjugates its first argument, we can either cancel this or inline `dot_product`:

(Implementation of operations for spinors) \equiv

```

pure function conjspinor_spinor (psibar, psi) result (psibarpsi)
  complex(kind=default) :: psibarpsi
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  psibarpsi = psibar%a(1)*psi%a(1) + psibar%a(2)*psi%a(2) &
    + psibar%a(3)*psi%a(3) + psibar%a(4)*psi%a(4)
end function conjspinor_spinor

```

X.1.2 Spinor Vector Space

Scalar Multiplication

(Declaration of operations for spinors) $+\equiv$

```

interface operator (*)
  module procedure integer_spinor, spinor_integer, &
    real_spinor, double_spinor, &
    complex_spinor, dcomplex_spinor, &
    spinor_real, spinor_double, &
    spinor_complex, spinor_dcomplex
end interface
private :: integer_spinor, spinor_integer, real_spinor, &
  double_spinor, complex_spinor, dcomplex_spinor, &
  spinor_real, spinor_double, spinor_complex, spinor_dcomplex

```

(Implementation of operations for spinors) $+\equiv$

```

pure function integer_spinor (x, y) result (xy)
  integer, intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function integer_spinor

```

(Implementation of operations for spinors) $+\equiv$

```

pure function real_spinor (x, y) result (xy)
  real(kind=single), intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function real_spinor
pure function double_spinor (x, y) result (xy)
  real(kind=default), intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a

```

```

end function double_spinor
pure function complex_spinor (x, y) result (xy)
  complex(kind=single), intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function complex_spinor
pure function dcomplex_spinor (x, y) result (xy)
  complex(kind=default), intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function dcomplex_spinor
pure function spinor_integer (y, x) result (xy)
  integer, intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function spinor_integer
pure function spinor_real (y, x) result (xy)
  real(kind=single), intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function spinor_real
pure function spinor_double (y, x) result (xy)
  real(kind=default), intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function spinor_double
pure function spinor_complex (y, x) result (xy)
  complex(kind=single), intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function spinor_complex
pure function spinor_dcomplex (y, x) result (xy)
  complex(kind=default), intent(in) :: x
  type(spinor), intent(in) :: y
  type(spinor) :: xy
  xy%a = x * y%a
end function spinor_dcomplex

(Declaration of operations for spinors)+≡
interface operator (*)
  module procedure integer_conjspinor, conjspinor_integer, &
    real_conjspinor, double_conjspinor, &
    complex_conjspinor, dcomplex_conjspinor, &
    conjspinor_real, conjspinor_double, &
    conjspinor_complex, conjspinor_dcomplex
end interface
private :: integer_conjspinor, conjspinor_integer, real_conjspinor, &
  double_conjspinor, complex_conjspinor, dcomplex_conjspinor, &
  conjspinor_real, conjspinor_double, conjspinor_complex, &

```



```

        conjspinor_dcomplex
<Implementation of operations for spinors>+≡
pure function integer_conjspinor (x, y) result (xy)
    integer, intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function integer_conjspinor
pure function real_conjspinor (x, y) result (xy)
    real(kind=single), intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function real_conjspinor
pure function double_conjspinor (x, y) result (xy)
    real(kind=default), intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function double_conjspinor
pure function complex_conjspinor (x, y) result (xy)
    complex(kind=single), intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function complex_conjspinor
pure function dcomplex_conjspinor (x, y) result (xy)
    complex(kind=default), intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function dcomplex_conjspinor
pure function conjspinor_integer (y, x) result (xy)
    integer, intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function conjspinor_integer
pure function conjspinor_real (y, x) result (xy)
    real(kind=single), intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function conjspinor_real
pure function conjspinor_double (y, x) result (xy)
    real(kind=default), intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function conjspinor_double
pure function conjspinor_complex (y, x) result (xy)
    complex(kind=single), intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy

```

```

    xy%a = x * y%a
end function conjspinor_complex
pure function conjspinor_dcomplex (y, x) result (xy)
    complex(kind=default), intent(in) :: x
    type(conjspinor), intent(in) :: y
    type(conjspinor) :: xy
    xy%a = x * y%a
end function conjspinor_dcomplex

```

Unary Plus and Minus

```

<Declaration of operations for spinors>+≡
interface operator (+)
    module procedure plus_spinor, plus_conjspinor
end interface
private :: plus_spinor, plus_conjspinor
interface operator (-)
    module procedure neg_spinor, neg_conjspinor
end interface
private :: neg_spinor, neg_conjspinor

<Implementation of operations for spinors>+≡
pure function plus_spinor (x) result (plus_x)
    type(spinor), intent(in) :: x
    type(spinor) :: plus_x
    plus_x%a = x%a
end function plus_spinor
pure function neg_spinor (x) result (neg_x)
    type(spinor), intent(in) :: x
    type(spinor) :: neg_x
    neg_x%a = - x%a
end function neg_spinor

<Implementation of operations for spinors>+≡
pure function plus_conjspinor (x) result (plus_x)
    type(conjspinor), intent(in) :: x
    type(conjspinor) :: plus_x
    plus_x%a = x%a
end function plus_conjspinor
pure function neg_conjspinor (x) result (neg_x)
    type(conjspinor), intent(in) :: x
    type(conjspinor) :: neg_x
    neg_x%a = - x%a
end function neg_conjspinor

```

Addition and Subtraction

```

<Declaration of operations for spinors>+≡
interface operator (+)
    module procedure add_spinor, add_conjspinor
end interface
private :: add_spinor, add_conjspinor
interface operator (-)
    module procedure sub_spinor, sub_conjspinor
end interface

```

```

private :: sub_spinor, sub_conjspinor

<Implementation of operations for spinors>+≡
pure function add_spinor (x, y) result (xy)
  type(spinor), intent(in) :: x, y
  type(spinor) :: xy
  xy%a = x%a + y%a
end function add_spinor
pure function sub_spinor (x, y) result (xy)
  type(spinor), intent(in) :: x, y
  type(spinor) :: xy
  xy%a = x%a - y%a
end function sub_spinor

<Implementation of operations for spinors>+≡
pure function add_conjspinor (x, y) result (xy)
  type(conjspinor), intent(in) :: x, y
  type(conjspinor) :: xy
  xy%a = x%a + y%a
end function add_conjspinor
pure function sub_conjspinor (x, y) result (xy)
  type(conjspinor), intent(in) :: x, y
  type(conjspinor) :: xy
  xy%a = x%a - y%a
end function sub_conjspinor

```

X.1.3 Norm

```

<Declaration of operations for spinors>+≡
interface abs
  module procedure abs_spinor, abs_conjspinor
end interface
private :: abs_spinor, abs_conjspinor

<Implementation of operations for spinors>+≡
pure function abs_spinor (psi) result (x)
  type(spinor), intent(in) :: psi
  real(kind=default) :: x
  x = sqrt (dot_product (psi%a, psi%a))
end function abs_spinor

<Implementation of operations for spinors>+≡
pure function abs_conjspinor (psibar) result (x)
  real(kind=default) :: x
  type(conjspinor), intent(in) :: psibar
  x = sqrt (dot_product (psibar%a, psibar%a))
end function abs_conjspinor

```

X.2 Spinors Revisited

```

(omega_bispinors.f90)≡
<Cpyleft>
module omega_bispinors
  use kinds

```

```

use constants
implicit none
private
public :: operator (*), operator (+), operator (-)
public :: abs
type, public :: bispinor
    ! private (omegalib needs access, but DON'T TOUCH IT!)
    complex(kind=default), dimension(4) :: a
end type bispinor
<Declaration of operations for bispinors>
integer, parameter, public :: omega_bispinors_2010_01_A = 0
contains
    <Implementation of operations for bispinors>
end module omega_bispinors

<Declaration of operations for bispinors>≡
interface operator (*)
    module procedure spinor_product
end interface
private :: spinor_product

```

$$\bar{\psi}\psi' \quad (X.2)$$

NB: dot_product conjugates its first argument, we have to cancel this.

```

<Implementation of operations for bispinors>≡
pure function spinor_product (psil, psir) result (psilpsir)
    complex(kind=default) :: psilpsir
    type(bispinor), intent(in) :: psil, psir
    type(bispinor) :: psidum
    psidum%a(1) = psir%a(2)
    psidum%a(2) = - psir%a(1)
    psidum%a(3) = - psir%a(4)
    psidum%a(4) = psir%a(3)
    psilpsir = dot_product (conjg (psil%a), psidum%a)
end function spinor_product

```

X.2.1 Spinor Vector Space

Scalar Multiplication

```

<Declaration of operations for bispinors>+≡
interface operator (*)
    module procedure integer_bispinor, bispinor_integer, &
        real_bispinor, double_bispinor, &
        complex_bispinor, dcomplex_bispinor, &
        bispinor_real, bispinor_double, &
        bispinor_complex, bispinor_dcomplex
end interface
private :: integer_bispinor, bispinor_integer, real_bispinor, &
    double_bispinor, complex_bispinor, dcomplex_bispinor, &
    bispinor_real, bispinor_double, bispinor_complex, bispinor_dcomplex

<Implementation of operations for bispinors>+≡
pure function integer_bispinor (x, y) result (xy)

```

```

    type(bispinor) :: xy
    integer, intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function integer_bispinor

<Implementation of operations for bispinors>+≡
pure function real_bispinor (x, y) result (xy)
    type(bispinor) :: xy
    real(kind=single), intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function real_bispinor

<Implementation of operations for bispinors>+≡
pure function double_bispinor (x, y) result (xy)
    type(bispinor) :: xy
    real(kind=default), intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function double_bispinor

<Implementation of operations for bispinors>+≡
pure function complex_bispinor (x, y) result (xy)
    type(bispinor) :: xy
    complex(kind=single), intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function complex_bispinor

<Implementation of operations for bispinors>+≡
pure function dcomplex_bispinor (x, y) result (xy)
    type(bispinor) :: xy
    complex(kind=default), intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function dcomplex_bispinor

<Implementation of operations for bispinors>+≡
pure function bispinor_integer (y, x) result (xy)
    type(bispinor) :: xy
    integer, intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function bispinor_integer

<Implementation of operations for bispinors>+≡
pure function bispinor_real (y, x) result (xy)
    type(bispinor) :: xy
    real(kind=single), intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function bispinor_real

<Implementation of operations for bispinors>+≡
pure function bispinor_double (y, x) result (xy)
    type(bispinor) :: xy
    real(kind=default), intent(in) :: x

```

```

    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function bispinor_double

<Implementation of operations for bispinors>+≡
pure function bispinor_complex (y, x) result (xy)
    type(bispinor) :: xy
    complex(kind=single), intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function bispinor_complex

<Implementation of operations for bispinors>+≡
pure function bispinor_dcomplex (y, x) result (xy)
    type(bispinor) :: xy
    complex(kind=default), intent(in) :: x
    type(bispinor), intent(in) :: y
    xy%a = x * y%a
end function bispinor_dcomplex

```

Unary Plus and Minus

```

<Declaration of operations for bispinors>+≡
interface operator (+)
    module procedure plus_bispinor
end interface
private :: plus_bispinor
interface operator (-)
    module procedure neg_bispinor
end interface
private :: neg_bispinor

<Implementation of operations for bispinors>+≡
pure function plus_bispinor (x) result (plus_x)
    type(bispinor) :: plus_x
    type(bispinor), intent(in) :: x
    plus_x%a = x%a
end function plus_bispinor

<Implementation of operations for bispinors>+≡
pure function neg_bispinor (x) result (neg_x)
    type(bispinor) :: neg_x
    type(bispinor), intent(in) :: x
    neg_x%a = - x%a
end function neg_bispinor

```

Addition and Subtraction

```

<Declaration of operations for bispinors>+≡
interface operator (+)
    module procedure add_bispinor
end interface
private :: add_bispinor
interface operator (-)
    module procedure sub_bispinor
end interface

```

```

private :: sub_bispinor

<Implementation of operations for bispinors>+=
pure function add_bispinor (x, y) result (xy)
  type(bispinor) :: xy
  type(bispinor), intent(in) :: x, y
  xy%a = x%a + y%a
end function add_bispinor

<Implementation of operations for bispinors>+=
pure function sub_bispinor (x, y) result (xy)
  type(bispinor) :: xy
  type(bispinor), intent(in) :: x, y
  xy%a = x%a - y%a
end function sub_bispinor

```

X.2.2 Norm

```

<Declaration of operations for bispinors>+=
interface abs
  module procedure abs_bispinor
end interface
private :: abs_bispinor

<Implementation of operations for bispinors>+=
pure function abs_bispinor (psi) result (x)
  real(kind=default) :: x
  type(bispinor), intent(in) :: psi
  x = sqrt (dot_product (psi%a, psi%a))
end function abs_bispinor

```

X.3 Vectorspinors

```

<omega_vectorspinors.f90>=
<Copleft>
module omega_vectorspinors
  use kinds
  use constants
  use omega_bispinors
  use omega_vectors
  implicit none
  private
  public :: operator (*), operator (+), operator (-)
  public :: abs
  type, public :: vectorspinor
    ! private (omegalib needs access, but DON'T TOUCH IT!)
    type(bispinor), dimension(4) :: psi
  end type vectorspinor
  <Declaration of operations for vectorspinors>
  integer, parameter, public :: omega_vectorspinors_2010_01_A = 0
contains
  <Implementation of operations for vectorspinors>
end module omega_vectorspinors

```

(Declaration of operations for vectorspinors)≡

```

interface operator (*)
  module procedure vspinor_product
end interface
private :: vspinor_product

```

$$\bar{\psi}^{\mu}\psi'_{\mu} \quad (X.3)$$

(Implementation of operations for vectorspinors)≡

```

pure function vspinor_product (psil, psir) result (psilpsir)
  complex(kind=default) :: psilpsir
  type(vectorspinor), intent(in) :: psil, psir
  psilpsir = psil%psi(1) * psir%psi(1) &
    - psil%psi(2) * psir%psi(2) &
    - psil%psi(3) * psir%psi(3) &
    - psil%psi(4) * psir%psi(4)
end function vspinor_product

```

X.3.1 Vectorspinor Vector Space

Scalar Multiplication

(Declaration of operations for vectorspinors)+≡

```

interface operator (*)
  module procedure integer_vectorspinor, vectorspinor_integer, &
    real_vectorspinor, double_vectorspinor, &
    complex_vectorspinor, dcomplex_vectorspinor, &
    vectorspinor_real, vectorspinor_double, &
    vectorspinor_complex, vectorspinor_dcomplex, &
    momentum_vectorspinor, vectorspinor_momentum
end interface
private :: integer_vectorspinor, vectorspinor_integer, real_vectorspinor, &
  double_vectorspinor, complex_vectorspinor, dcomplex_vectorspinor, &
  vectorspinor_real, vectorspinor_double, vectorspinor_complex, &
  vectorspinor_dcomplex

```

(Implementation of operations for vectorspinors)+≡

```

pure function integer_vectorspinor (x, y) result (xy)
  type(vectorspinor) :: xy
  integer, intent(in) :: x
  type(vectorspinor), intent(in) :: y
  integer :: k
  do k = 1,4
    xy%psi(k) = x * y%psi(k)
  end do
end function integer_vectorspinor

```

(Implementation of operations for vectorspinors)+≡

```

pure function real_vectorspinor (x, y) result (xy)
  type(vectorspinor) :: xy
  real(kind=single), intent(in) :: x
  type(vectorspinor), intent(in) :: y
  integer :: k
  do k = 1,4
    xy%psi(k) = x * y%psi(k)
  end do
end function real_vectorspinor

```



```

    end do
end function real_vectorspinor

<Implementation of operations for vectorspinors>+≡
pure function double_vectorspinor (x, y) result (xy)
    type(vectorspinor) :: xy
    real(kind=default), intent(in) :: x
    type(vectorspinor), intent(in) :: y
    integer :: k
    do k = 1,4
        xy%psi(k) = x * y%psi(k)
    end do
end function double_vectorspinor

<Implementation of operations for vectorspinors>+≡
pure function complex_vectorspinor (x, y) result (xy)
    type(vectorspinor) :: xy
    complex(kind=single), intent(in) :: x
    type(vectorspinor), intent(in) :: y
    integer :: k
    do k = 1,4
        xy%psi(k) = x * y%psi(k)
    end do
end function complex_vectorspinor

<Implementation of operations for vectorspinors>+≡
pure function dcomplex_vectorspinor (x, y) result (xy)
    type(vectorspinor) :: xy
    complex(kind=default), intent(in) :: x
    type(vectorspinor), intent(in) :: y
    integer :: k
    do k = 1,4
        xy%psi(k) = x * y%psi(k)
    end do
end function dcomplex_vectorspinor

<Implementation of operations for vectorspinors>+≡
pure function vectorspinor_integer (y, x) result (xy)
    type(vectorspinor) :: xy
    integer, intent(in) :: x
    type(vectorspinor), intent(in) :: y
    integer :: k
    do k = 1,4
        xy%psi(k) = y%psi(k) * x
    end do
end function vectorspinor_integer

<Implementation of operations for vectorspinors>+≡
pure function vectorspinor_real (y, x) result (xy)
    type(vectorspinor) :: xy
    real(kind=single), intent(in) :: x
    type(vectorspinor), intent(in) :: y
    integer :: k
    do k = 1,4
        xy%psi(k) = y%psi(k) * x
    end do
end function vectorspinor_real

```

```

<Implementation of operations for vectorspinors>+≡
pure function vectorspinor_double (y, x) result (xy)
  type(vectorspinor) :: xy
  real(kind=default), intent(in) :: x
  type(vectorspinor), intent(in) :: y
  integer :: k
  do k = 1,4
    xy%psi(k) = y%psi(k) * x
  end do
end function vectorspinor_double

<Implementation of operations for vectorspinors>+≡
pure function vectorspinor_complex (y, x) result (xy)
  type(vectorspinor) :: xy
  complex(kind=single), intent(in) :: x
  type(vectorspinor), intent(in) :: y
  integer :: k
  do k = 1,4
    xy%psi(k) = y%psi(k) * x
  end do
end function vectorspinor_complex

<Implementation of operations for vectorspinors>+≡
pure function vectorspinor_dcomplex (y, x) result (xy)
  type(vectorspinor) :: xy
  complex(kind=default), intent(in) :: x
  type(vectorspinor), intent(in) :: y
  integer :: k
  do k = 1,4
    xy%psi(k) = y%psi(k) * x
  end do
end function vectorspinor_dcomplex

<Implementation of operations for vectorspinors>+≡
pure function momentum_vectorspinor (y, x) result (xy)
  type(bispinor) :: xy
  type(momentum), intent(in) :: y
  type(vectorspinor), intent(in) :: x
  integer :: k
  do k = 1,4
    xy%a(k) = y%t      * x%psi(1)%a(k) - y%x(1) * x%psi(2)%a(k) - &
              y%x(2) * x%psi(3)%a(k) - y%x(3) * x%psi(4)%a(k)
  end do
end function momentum_vectorspinor

<Implementation of operations for vectorspinors>+≡
pure function vectorspinor_momentum (y, x) result (xy)
  type(bispinor) :: xy
  type(momentum), intent(in) :: x
  type(vectorspinor), intent(in) :: y
  integer :: k
  do k = 1,4
    xy%a(k) = x%t      * y%psi(1)%a(k) - x%x(1) * y%psi(2)%a(k) - &
              x%x(2) * y%psi(3)%a(k) - x%x(3) * y%psi(4)%a(k)
  end do
end function vectorspinor_momentum

```

Unary Plus and Minus

```

<Declaration of operations for vectorspinors>+≡
  interface operator (+)
    module procedure plus_vectorspinor
  end interface
  private :: plus_vectorspinor
  interface operator (-)
    module procedure neg_vectorspinor
  end interface
  private :: neg_vectorspinor

<Implementation of operations for vectorspinors>+≡
  pure function plus_vectorspinor (x) result (plus_x)
    type(vectorspinor) :: plus_x
    type(vectorspinor), intent(in) :: x
    integer :: k
    do k = 1,4
      plus_x%psi(k) = + x%psi(k)
    end do
  end function plus_vectorspinor

<Implementation of operations for vectorspinors>+≡
  pure function neg_vectorspinor (x) result (neg_x)
    type(vectorspinor) :: neg_x
    type(vectorspinor), intent(in) :: x
    integer :: k
    do k = 1,4
      neg_x%psi(k) = - x%psi(k)
    end do
  end function neg_vectorspinor

```

Addition and Subtraction

```

<Declaration of operations for vectorspinors>+≡
  interface operator (+)
    module procedure add_vectorspinor
  end interface
  private :: add_vectorspinor
  interface operator (-)
    module procedure sub_vectorspinor
  end interface
  private :: sub_vectorspinor

<Implementation of operations for vectorspinors>+≡
  pure function add_vectorspinor (x, y) result (xy)
    type(vectorspinor) :: xy
    type(vectorspinor), intent(in) :: x, y
    integer :: k
    do k = 1,4
      xy%psi(k) = x%psi(k) + y%psi(k)
    end do
  end function add_vectorspinor

```

```

<Implementation of operations for vectorspinors>+=
pure function sub_vectorspinor (x, y) result (xy)
  type(vectorspinor) :: xy
  type(vectorspinor), intent(in) :: x, y
  integer :: k
  do k = 1,4
    xy%psi(k) = x%psi(k) - y%psi(k)
  end do
end function sub_vectorspinor

```

X.3.2 Norm

```

<Declaration of operations for vectorspinors>+=
interface abs
  module procedure abs_vectorspinor
end interface
private :: abs_vectorspinor

<Implementation of operations for vectorspinors>+=
pure function abs_vectorspinor (psi) result (x)
  real(kind=default) :: x
  type(vectorspinor), intent(in) :: psi
  x = sqrt (dot_product (psi%psi(1)%a, psi%psi(1)%a) &
    - dot_product (psi%psi(2)%a, psi%psi(2)%a) &
    - dot_product (psi%psi(3)%a, psi%psi(3)%a) &
    - dot_product (psi%psi(4)%a, psi%psi(4)%a))
end function abs_vectorspinor

```

X.4 Vectors and Tensors

Condensed representation of antisymmetric rank-2 tensors:

$$\begin{pmatrix} T^{00} & T^{01} & T^{02} & T^{03} \\ T^{10} & T^{11} & T^{12} & T^{13} \\ T^{20} & T^{21} & T^{22} & T^{23} \\ T^{30} & T^{31} & T^{32} & T^{33} \end{pmatrix} = \begin{pmatrix} 0 & T_e^1 & T_e^2 & T_e^3 \\ -T_e^1 & 0 & T_b^3 & -T_b^2 \\ -T_e^2 & -T_b^3 & 0 & T_b^1 \\ -T_e^3 & T_b^2 & -T_b^1 & 0 \end{pmatrix} \quad (X.4)$$

```

<omega_vectors.f90>=
<Cotypeleft>
module omega_vectors
  use kinds
  use constants
  implicit none
  private
  public :: assignment (=)
  public :: operator (*), operator (+), operator (-), operator (.wedge.)
  public :: abs, conjg
  public :: random_momentum
  <intrinsic :: abs>
  <intrinsic :: conjg>
  type, public :: momentum
  ! private (omegalib needs access, but DON'T TOUCH IT!)
  real(kind=default) :: t

```

```

        real(kind=default), dimension(3) :: x
    end type momentum
    type, public :: vector
        ! private (omegalib needs access, but DON'T TOUCH IT!)
        complex(kind=default) :: t
        complex(kind=default), dimension(3) :: x
    end type vector
    type, public :: tensor2odd
        ! private (omegalib needs access, but DON'T TOUCH IT!)
        complex(kind=default), dimension(3) :: e
        complex(kind=default), dimension(3) :: b
    end type tensor2odd
    <Declaration of operations for vectors>
    integer, parameter, public :: omega_vectors_2010_01_A = 0
contains
    <Implementation of operations for vectors>
end module omega_vectors

```

X.4.1 Constructors

```

<Declaration of operations for vectors>≡
    interface assignment (=)
        module procedure momentum_of_array, vector_of_momentum, &
            vector_of_array, vector_of_double_array, &
            array_of_momentum, array_of_vector
    end interface
    private :: momentum_of_array, vector_of_momentum, vector_of_array, &
        vector_of_double_array, array_of_momentum, array_of_vector

<Implementation of operations for vectors>≡
    pure subroutine momentum_of_array (m, p)
        type(momentum), intent(out) :: m
        real(kind=default), dimension(0:), intent(in) :: p
        m%t = p(0)
        m%x = p(1:3)
    end subroutine momentum_of_array
    pure subroutine array_of_momentum (p, v)
        real(kind=default), dimension(0:), intent(out) :: p
        type(momentum), intent(in) :: v
        p(0) = v%t
        p(1:3) = v%x
    end subroutine array_of_momentum

<Implementation of operations for vectors>+≡
    pure subroutine vector_of_array (v, p)
        type(vector), intent(out) :: v
        complex(kind=default), dimension(0:), intent(in) :: p
        v%t = p(0)
        v%x = p(1:3)
    end subroutine vector_of_array
    pure subroutine vector_of_double_array (v, p)
        type(vector), intent(out) :: v
        real(kind=default), dimension(0:), intent(in) :: p
        v%t = p(0)
        v%x = p(1:3)
    end subroutine vector_of_double_array

```

```

end subroutine vector_of_double_array
pure subroutine array_of_vector (p, v)
  complex(kind=default), dimension(0:), intent(out) :: p
  type(vector), intent(in) :: v
  p(0) = v%t
  p(1:3) = v%x
end subroutine array_of_vector
<Implementation of operations for vectors>+≡
pure subroutine vector_of_momentum (v, p)
  type(vector), intent(out) :: v
  type(momentum), intent(in) :: p
  v%t = p%t
  v%x = p%x
end subroutine vector_of_momentum

```

X.4.2 Inner Products

```

<Declaration of operations for vectors>+≡
interface operator (*)
  module procedure momentum_momentum, vector_vector, &
    vector_momentum, momentum_vector, tensor2odd_tensor2odd
end interface
private :: momentum_momentum, vector_vector, vector_momentum, &
  momentum_vector, tensor2odd_tensor2odd

<Implementation of operations for vectors>+≡
pure function momentum_momentum (x, y) result (xy)
  type(momentum), intent(in) :: x
  type(momentum), intent(in) :: y
  real(kind=default) :: xy
  xy = x%t*y%t - x%x(1)*y%x(1) - x%x(2)*y%x(2) - x%x(3)*y%x(3)
end function momentum_momentum
pure function momentum_vector (x, y) result (xy)
  type(momentum), intent(in) :: x
  type(vector), intent(in) :: y
  complex(kind=default) :: xy
  xy = x%t*y%t - x%x(1)*y%x(1) - x%x(2)*y%x(2) - x%x(3)*y%x(3)
end function momentum_vector
pure function vector_momentum (x, y) result (xy)
  type(vector), intent(in) :: x
  type(momentum), intent(in) :: y
  complex(kind=default) :: xy
  xy = x%t*y%t - x%x(1)*y%x(1) - x%x(2)*y%x(2) - x%x(3)*y%x(3)
end function vector_momentum
pure function vector_vector (x, y) result (xy)
  type(vector), intent(in) :: x
  type(vector), intent(in) :: y
  complex(kind=default) :: xy
  xy = x%t*y%t - x%x(1)*y%x(1) - x%x(2)*y%x(2) - x%x(3)*y%x(3)
end function vector_vector

```

Just like classical electrodynamics:

$$\frac{1}{2}T_{\mu\nu}U^{\mu\nu} = \frac{1}{2}(-T^{0i}U^{0i} - T^{i0}U^{i0} + T^{ij}U^{ij}) = T_b^k U_b^k - T_e^k U_e^k \quad (\text{X.5})$$

```

<Implementation of operations for vectors>+≡
pure function tensor2odd_tensor2odd (x, y) result (xy)
  type(tensor2odd), intent(in) :: x
  type(tensor2odd), intent(in) :: y
  complex(kind=default) :: xy
  xy = x%b(1)*y%b(1) + x%b(2)*y%b(2) + x%b(3)*y%b(3) &
    - x%e(1)*y%e(1) - x%e(2)*y%e(2) - x%e(3)*y%e(3)
end function tensor2odd_tensor2odd

```

X.4.3 Not Entirely Inner Products

```

<Declaration of operations for vectors>+≡
interface operator (*)
  module procedure momentum_tensor2odd, tensor2odd_momentum, &
    vector_tensor2odd, tensor2odd_vector
end interface
private :: momentum_tensor2odd, tensor2odd_momentum, vector_tensor2odd, &
  tensor2odd_vector

```

$$y^\nu = x_\mu T^{\mu\nu} : y^0 = -x^i T^{i0} = x^i T^{0i} \quad (\text{X.6a})$$

$$y^1 = x^0 T^{01} - x^2 T^{21} - x^3 T^{31} \quad (\text{X.6b})$$

$$y^2 = x^0 T^{02} - x^1 T^{12} - x^3 T^{32} \quad (\text{X.6c})$$

$$y^3 = x^0 T^{03} - x^1 T^{13} - x^2 T^{23} \quad (\text{X.6d})$$

```

<Implementation of operations for vectors>+≡
pure function vector_tensor2odd (x, t2) result (xt2)
  type(vector), intent(in) :: x
  type(tensor2odd), intent(in) :: t2
  type(vector) :: xt2
  xt2%t = x%x(1)*t2%e(1) + x%x(2)*t2%e(2) + x%x(3)*t2%e(3)
  xt2%x(1) = x%t*t2%e(1) + x%x(2)*t2%b(3) - x%x(3)*t2%b(2)
  xt2%x(2) = x%t*t2%e(2) + x%x(3)*t2%b(1) - x%x(1)*t2%b(3)
  xt2%x(3) = x%t*t2%e(3) + x%x(1)*t2%b(2) - x%x(2)*t2%b(1)
end function vector_tensor2odd
pure function momentum_tensor2odd (x, t2) result (xt2)
  type(momentum), intent(in) :: x
  type(tensor2odd), intent(in) :: t2
  type(vector) :: xt2
  xt2%t = x%x(1)*t2%e(1) + x%x(2)*t2%e(2) + x%x(3)*t2%e(3)
  xt2%x(1) = x%t*t2%e(1) + x%x(2)*t2%b(3) - x%x(3)*t2%b(2)
  xt2%x(2) = x%t*t2%e(2) + x%x(3)*t2%b(1) - x%x(1)*t2%b(3)
  xt2%x(3) = x%t*t2%e(3) + x%x(1)*t2%b(2) - x%x(2)*t2%b(1)
end function momentum_tensor2odd

```

$$y^\mu = T^{\mu\nu} x_\nu : y^0 = -T^{0i} x^i \quad (\text{X.7a})$$

$$y^1 = T^{10} x^0 - T^{12} x^2 - T^{13} x^3 \quad (\text{X.7b})$$

$$y^2 = T^{20} x^0 - T^{21} x^1 - T^{23} x^3 \quad (\text{X.7c})$$

$$y^3 = T^{30} x^0 - T^{31} x^1 - T^{32} x^2 \quad (\text{X.7d})$$

```

<Implementation of operations for vectors>+≡
pure function tensor2odd_vector (t2, x) result (t2x)
  type(tensor2odd), intent(in) :: t2
  type(vector), intent(in) :: x
  type(vector) :: t2x
  t2x%t = - t2%e(1)*x%x(1) - t2%e(2)*x%x(2) - t2%e(3)*x%x(3)
  t2x%x(1) = - t2%e(1)*x%t + t2%b(2)*x%x(3) - t2%b(3)*x%x(2)
  t2x%x(2) = - t2%e(2)*x%t + t2%b(3)*x%x(1) - t2%b(1)*x%x(3)
  t2x%x(3) = - t2%e(3)*x%t + t2%b(1)*x%x(2) - t2%b(2)*x%x(1)
end function tensor2odd_vector
pure function tensor2odd_momentum (t2, x) result (t2x)
  type(tensor2odd), intent(in) :: t2
  type(momentum), intent(in) :: x
  type(vector) :: t2x
  t2x%t = - t2%e(1)*x%x(1) - t2%e(2)*x%x(2) - t2%e(3)*x%x(3)
  t2x%x(1) = - t2%e(1)*x%t + t2%b(2)*x%x(3) - t2%b(3)*x%x(2)
  t2x%x(2) = - t2%e(2)*x%t + t2%b(3)*x%x(1) - t2%b(1)*x%x(3)
  t2x%x(3) = - t2%e(3)*x%t + t2%b(1)*x%x(2) - t2%b(2)*x%x(1)
end function tensor2odd_momentum

```

X.4.4 Outer Products

```

<Declaration of operations for vectors>+≡
interface operator (.wedge.)
  module procedure momentum_wedge_momentum, &
    momentum_wedge_vector, vector_wedge_momentum, vector_wedge_vector
end interface
private :: momentum_wedge_momentum, momentum_wedge_vector, &
  vector_wedge_momentum, vector_wedge_vector

```

```

<Implementation of operations for vectors>+≡
pure function momentum_wedge_momentum (x, y) result (t2)
  type(momentum), intent(in) :: x
  type(momentum), intent(in) :: y
  type(tensor2odd) :: t2
  t2%e = x%t * y%x - x%x * y%t
  t2%b(1) = x%x(2) * y%x(3) - x%x(3) * y%x(2)
  t2%b(2) = x%x(3) * y%x(1) - x%x(1) * y%x(3)
  t2%b(3) = x%x(1) * y%x(2) - x%x(2) * y%x(1)
end function momentum_wedge_momentum
pure function momentum_wedge_vector (x, y) result (t2)
  type(momentum), intent(in) :: x
  type(vector), intent(in) :: y
  type(tensor2odd) :: t2
  t2%e = x%t * y%x - x%x * y%t
  t2%b(1) = x%x(2) * y%x(3) - x%x(3) * y%x(2)
  t2%b(2) = x%x(3) * y%x(1) - x%x(1) * y%x(3)
  t2%b(3) = x%x(1) * y%x(2) - x%x(2) * y%x(1)
end function momentum_wedge_vector
pure function vector_wedge_momentum (x, y) result (t2)
  type(vector), intent(in) :: x
  type(momentum), intent(in) :: y
  type(tensor2odd) :: t2
  t2%e = x%t * y%x - x%x * y%t

```



```

t2%b(1) = x%x(2) * y%x(3) - x%x(3) * y%x(2)
t2%b(2) = x%x(3) * y%x(1) - x%x(1) * y%x(3)
t2%b(3) = x%x(1) * y%x(2) - x%x(2) * y%x(1)
end function vector_wedge_momentum
pure function vector_wedge_vector (x, y) result (t2)
  type(vector), intent(in) :: x
  type(vector), intent(in) :: y
  type(tensor2odd) :: t2
  t2%e = x%t * y%x - x%x * y%t
  t2%b(1) = x%x(2) * y%x(3) - x%x(3) * y%x(2)
  t2%b(2) = x%x(3) * y%x(1) - x%x(1) * y%x(3)
  t2%b(3) = x%x(1) * y%x(2) - x%x(2) * y%x(1)
end function vector_wedge_vector

```

X.4.5 Vector Space

Scalar Multiplication

(Declaration of operations for vectors)+≡

```

interface operator (*)
  module procedure integer_momentum, real_momentum, double_momentum, &
    complex_momentum, dcomplex_momentum, &
    integer_vector, real_vector, double_vector, &
    complex_vector, dcomplex_vector, &
    integer_tensor2odd, real_tensor2odd, double_tensor2odd, &
    complex_tensor2odd, dcomplex_tensor2odd, &
    momentum_integer, momentum_real, momentum_double, &
    momentum_complex, momentum_dcomplex, &
    vector_integer, vector_real, vector_double, &
    vector_complex, vector_dcomplex, &
    tensor2odd_integer, tensor2odd_real, tensor2odd_double, &
    tensor2odd_complex, tensor2odd_dcomplex
end interface
private :: integer_momentum, real_momentum, double_momentum, &
  complex_momentum, dcomplex_momentum, integer_vector, real_vector, &
  double_vector, complex_vector, dcomplex_vector, &
  integer_tensor2odd, real_tensor2odd, double_tensor2odd, &
  complex_tensor2odd, dcomplex_tensor2odd, momentum_integer, &
  momentum_real, momentum_double, momentum_complex, &
  momentum_dcomplex, vector_integer, vector_real, vector_double, &
  vector_complex, vector_dcomplex, tensor2odd_integer, &
  tensor2odd_real, tensor2odd_double, tensor2odd_complex, &
  tensor2odd_dcomplex

```

(Implementation of operations for vectors)+≡

```

pure function integer_momentum (x, y) result (xy)
  integer, intent(in) :: x
  type(momentum), intent(in) :: y
  type(momentum) :: xy
  xy%t = x * y%t
  xy%x = x * y%x
end function integer_momentum
pure function real_momentum (x, y) result (xy)
  real(kind=single), intent(in) :: x

```

```

        type(momentum), intent(in) :: y
        type(momentum) :: xy
        xy%t = x * y%t
        xy%x = x * y%x
    end function real_momentum
    pure function double_momentum (x, y) result (xy)
        real(kind=default), intent(in) :: x
        type(momentum), intent(in) :: y
        type(momentum) :: xy
        xy%t = x * y%t
        xy%x = x * y%x
    end function double_momentum
    pure function complex_momentum (x, y) result (xy)
        complex(kind=single), intent(in) :: x
        type(momentum), intent(in) :: y
        type(vector) :: xy
        xy%t = x * y%t
        xy%x = x * y%x
    end function complex_momentum
    pure function dcomplex_momentum (x, y) result (xy)
        complex(kind=default), intent(in) :: x
        type(momentum), intent(in) :: y
        type(vector) :: xy
        xy%t = x * y%t
        xy%x = x * y%x
    end function dcomplex_momentum

    (Implementation of operations for vectors) +=
    pure function integer_vector (x, y) result (xy)
        integer, intent(in) :: x
        type(vector), intent(in) :: y
        type(vector) :: xy
        xy%t = x * y%t
        xy%x = x * y%x
    end function integer_vector
    pure function real_vector (x, y) result (xy)
        real(kind=single), intent(in) :: x
        type(vector), intent(in) :: y
        type(vector) :: xy
        xy%t = x * y%t
        xy%x = x * y%x
    end function real_vector
    pure function double_vector (x, y) result (xy)
        real(kind=default), intent(in) :: x
        type(vector), intent(in) :: y
        type(vector) :: xy
        xy%t = x * y%t
        xy%x = x * y%x
    end function double_vector
    pure function complex_vector (x, y) result (xy)
        complex(kind=single), intent(in) :: x
        type(vector), intent(in) :: y
        type(vector) :: xy
        xy%t = x * y%t
        xy%x = x * y%x

```

```

end function complex_vector
pure function dcomplex_vector (x, y) result (xy)
  complex(kind=default), intent(in) :: x
  type(vector), intent(in) :: y
  type(vector) :: xy
  xy%t = x * y%t
  xy%x = x * y%x
end function dcomplex_vector

<Implementation of operations for vectors>+≡
pure function integer_tensor2odd (x, t2) result (xt2)
  integer, intent(in) :: x
  type(tensor2odd), intent(in) :: t2
  type(tensor2odd) :: xt2
  xt2%e = x * t2%e
  xt2%b = x * t2%b
end function integer_tensor2odd
pure function real_tensor2odd (x, t2) result (xt2)
  real(kind=single), intent(in) :: x
  type(tensor2odd), intent(in) :: t2
  type(tensor2odd) :: xt2
  xt2%e = x * t2%e
  xt2%b = x * t2%b
end function real_tensor2odd
pure function double_tensor2odd (x, t2) result (xt2)
  real(kind=default), intent(in) :: x
  type(tensor2odd), intent(in) :: t2
  type(tensor2odd) :: xt2
  xt2%e = x * t2%e
  xt2%b = x * t2%b
end function double_tensor2odd
pure function complex_tensor2odd (x, t2) result (xt2)
  complex(kind=single), intent(in) :: x
  type(tensor2odd), intent(in) :: t2
  type(tensor2odd) :: xt2
  xt2%e = x * t2%e
  xt2%b = x * t2%b
end function complex_tensor2odd
pure function dcomplex_tensor2odd (x, t2) result (xt2)
  complex(kind=default), intent(in) :: x
  type(tensor2odd), intent(in) :: t2
  type(tensor2odd) :: xt2
  xt2%e = x * t2%e
  xt2%b = x * t2%b
end function dcomplex_tensor2odd

<Implementation of operations for vectors>+≡
pure function momentum_integer (y, x) result (xy)
  integer, intent(in) :: x
  type(momentum), intent(in) :: y
  type(momentum) :: xy
  xy%t = x * y%t
  xy%x = x * y%x
end function momentum_integer
pure function momentum_real (y, x) result (xy)

```

```

    real(kind=single), intent(in) :: x
    type(momentum), intent(in) :: y
    type(momentum) :: xy
    xy%t = x * y%t
    xy%x = x * y%x
end function momentum_real
pure function momentum_double (y, x) result (xy)
    real(kind=default), intent(in) :: x
    type(momentum), intent(in) :: y
    type(momentum) :: xy
    xy%t = x * y%t
    xy%x = x * y%x
end function momentum_double
pure function momentum_complex (y, x) result (xy)
    complex(kind=single), intent(in) :: x
    type(momentum), intent(in) :: y
    type(vector) :: xy
    xy%t = x * y%t
    xy%x = x * y%x
end function momentum_complex
pure function momentum_dcomplex (y, x) result (xy)
    complex(kind=default), intent(in) :: x
    type(momentum), intent(in) :: y
    type(vector) :: xy
    xy%t = x * y%t
    xy%x = x * y%x
end function momentum_dcomplex

(Implementation of operations for vectors)+≡
pure function vector_integer (y, x) result (xy)
    integer, intent(in) :: x
    type(vector), intent(in) :: y
    type(vector) :: xy
    xy%t = x * y%t
    xy%x = x * y%x
end function vector_integer
pure function vector_real (y, x) result (xy)
    real(kind=single), intent(in) :: x
    type(vector), intent(in) :: y
    type(vector) :: xy
    xy%t = x * y%t
    xy%x = x * y%x
end function vector_real
pure function vector_double (y, x) result (xy)
    real(kind=default), intent(in) :: x
    type(vector), intent(in) :: y
    type(vector) :: xy
    xy%t = x * y%t
    xy%x = x * y%x
end function vector_double
pure function vector_complex (y, x) result (xy)
    complex(kind=single), intent(in) :: x
    type(vector), intent(in) :: y
    type(vector) :: xy
    xy%t = x * y%t

```

```

    xy%x = x * y%x
end function vector_dcomplex
pure function vector_dcomplex (y, x) result (xy)
    complex(kind=default), intent(in) :: x
    type(vector), intent(in) :: y
    type(vector) :: xy
    xy%t = x * y%t
    xy%x = x * y%x
end function vector_dcomplex

(Implementation of operations for vectors)+≡
pure function tensor2odd_integer (t2, x) result (t2x)
    type(tensor2odd), intent(in) :: t2
    integer, intent(in) :: x
    type(tensor2odd) :: t2x
    t2x%e = x * t2%e
    t2x%b = x * t2%b
end function tensor2odd_integer
pure function tensor2odd_real (t2, x) result (t2x)
    type(tensor2odd), intent(in) :: t2
    real(kind=single), intent(in) :: x
    type(tensor2odd) :: t2x
    t2x%e = x * t2%e
    t2x%b = x * t2%b
end function tensor2odd_real
pure function tensor2odd_double (t2, x) result (t2x)
    type(tensor2odd), intent(in) :: t2
    real(kind=default), intent(in) :: x
    type(tensor2odd) :: t2x
    t2x%e = x * t2%e
    t2x%b = x * t2%b
end function tensor2odd_double
pure function tensor2odd_complex (t2, x) result (t2x)
    type(tensor2odd), intent(in) :: t2
    complex(kind=single), intent(in) :: x
    type(tensor2odd) :: t2x
    t2x%e = x * t2%e
    t2x%b = x * t2%b
end function tensor2odd_complex
pure function tensor2odd_dcomplex (t2, x) result (t2x)
    type(tensor2odd), intent(in) :: t2
    complex(kind=default), intent(in) :: x
    type(tensor2odd) :: t2x
    t2x%e = x * t2%e
    t2x%b = x * t2%b
end function tensor2odd_dcomplex

```

Unary Plus and Minus

```

(Declaration of operations for vectors)+≡
interface operator (+)
    module procedure plus_momentum, plus_vector, plus_tensor2odd
end interface
private :: plus_momentum, plus_vector, plus_tensor2odd

```

```

interface operator (-)
  module procedure neg_momentum, neg_vector, neg_tensor2odd
end interface
private :: neg_momentum, neg_vector, neg_tensor2odd

<Implementation of operations for vectors>+≡
pure function plus_momentum (x) result (plus_x)
  type(momentum), intent(in) :: x
  type(momentum) :: plus_x
  plus_x = x
end function plus_momentum
pure function neg_momentum (x) result (neg_x)
  type(momentum), intent(in) :: x
  type(momentum) :: neg_x
  neg_x%t = - x%t
  neg_x%x = - x%x
end function neg_momentum

<Implementation of operations for vectors>+≡
pure function plus_vector (x) result (plus_x)
  type(vector), intent(in) :: x
  type(vector) :: plus_x
  plus_x = x
end function plus_vector
pure function neg_vector (x) result (neg_x)
  type(vector), intent(in) :: x
  type(vector) :: neg_x
  neg_x%t = - x%t
  neg_x%x = - x%x
end function neg_vector

<Implementation of operations for vectors>+≡
pure function plus_tensor2odd (x) result (plus_x)
  type(tensor2odd), intent(in) :: x
  type(tensor2odd) :: plus_x
  plus_x = x
end function plus_tensor2odd
pure function neg_tensor2odd (x) result (neg_x)
  type(tensor2odd), intent(in) :: x
  type(tensor2odd) :: neg_x
  neg_x%e = - x%e
  neg_x%b = - x%b
end function neg_tensor2odd

```

Addition and Subtraction

```

<Declaration of operations for vectors>+≡
interface operator (+)
  module procedure add_momentum, add_vector, &
    add_vector_momentum, add_momentum_vector, add_tensor2odd
end interface
private :: add_momentum, add_vector, add_vector_momentum, &
  add_momentum_vector, add_tensor2odd
interface operator (-)
  module procedure sub_momentum, sub_vector, &

```

```

        sub_vector_momentum, sub_momentum_vector, sub_tensor2odd
end interface
private :: sub_momentum, sub_vector, sub_vector_momentum, &
        sub_momentum_vector, sub_tensor2odd

<Implementation of operations for vectors>+≡
pure function add_momentum (x, y) result (xy)
    type(momentum), intent(in) :: x, y
    type(momentum) :: xy
    xy%t = x%t + y%t
    xy%x = x%x + y%x
end function add_momentum
pure function add_vector (x, y) result (xy)
    type(vector), intent(in) :: x, y
    type(vector) :: xy
    xy%t = x%t + y%t
    xy%x = x%x + y%x
end function add_vector
pure function add_momentum_vector (x, y) result (xy)
    type(momentum), intent(in) :: x
    type(vector), intent(in) :: y
    type(vector) :: xy
    xy%t = x%t + y%t
    xy%x = x%x + y%x
end function add_momentum_vector
pure function add_vector_momentum (x, y) result (xy)
    type(vector), intent(in) :: x
    type(momentum), intent(in) :: y
    type(vector) :: xy
    xy%t = x%t + y%t
    xy%x = x%x + y%x
end function add_vector_momentum
pure function add_tensor2odd (x, y) result (xy)
    type(tensor2odd), intent(in) :: x, y
    type(tensor2odd) :: xy
    xy%e = x%e + y%e
    xy%b = x%b + y%b
end function add_tensor2odd

<Implementation of operations for vectors>+≡
pure function sub_momentum (x, y) result (xy)
    type(momentum), intent(in) :: x, y
    type(momentum) :: xy
    xy%t = x%t - y%t
    xy%x = x%x - y%x
end function sub_momentum
pure function sub_vector (x, y) result (xy)
    type(vector), intent(in) :: x, y
    type(vector) :: xy
    xy%t = x%t - y%t
    xy%x = x%x - y%x
end function sub_vector
pure function sub_momentum_vector (x, y) result (xy)
    type(momentum), intent(in) :: x
    type(vector), intent(in) :: y

```

```

    type(vector) :: xy
    xy%t = x%t - y%t
    xy%x = x%x - y%x
end function sub_momentum_vector
pure function sub_vector_momentum (x, y) result (xy)
    type(vector), intent(in) :: x
    type(momentum), intent(in) :: y
    type(vector) :: xy
    xy%t = x%t - y%t
    xy%x = x%x - y%x
end function sub_vector_momentum
pure function sub_tensor2odd (x, y) result (xy)
    type(tensor2odd), intent(in) :: x, y
    type(tensor2odd) :: xy
    xy%e = x%e - y%e
    xy%b = x%b - y%b
end function sub_tensor2odd

```

X.4.6 Norm

Not the covariant length!

(Declaration of operations for vectors)+≡

```

interface abs
    module procedure abs_momentum, abs_vector, abs_tensor2odd
end interface
private :: abs_momentum, abs_vector, abs_tensor2odd

```

(Implementation of operations for vectors)+≡

```

pure function abs_momentum (x) result (absx)
    type(momentum), intent(in) :: x
    real(kind=default) :: absx
    absx = sqrt (x%t*x%t + dot_product (x%x, x%x))
end function abs_momentum
pure function abs_vector (x) result (absx)
    type(vector), intent(in) :: x
    real(kind=default) :: absx
    absx = sqrt (conjg(x%t)*x%t + dot_product (x%x, x%x))
end function abs_vector
pure function abs_tensor2odd (x) result (absx)
    type(tensor2odd), intent(in) :: x
    real(kind=default) :: absx
    absx = sqrt (dot_product (x%e, x%e) + dot_product (x%b, x%b))
end function abs_tensor2odd

```

X.4.7 Conjugation

(Declaration of operations for vectors)+≡

```

interface conjg
    module procedure conjg_momentum, conjg_vector, conjg_tensor2odd
end interface
private :: conjg_momentum, conjg_vector, conjg_tensor2odd

```

(Implementation of operations for vectors)+≡

```

pure function conjg_momentum (x) result (conjg_x)

```



```

    type(momentum), intent(in) :: x
    type(momentum) :: conjg_x
    conjg_x = x
end function conjg_momentum
pure function conjg_vector (x) result (conjg_x)
    type(vector), intent(in) :: x
    type(vector) :: conjg_x
    conjg_x%t = conjg (x%t)
    conjg_x%x = conjg (x%x)
end function conjg_vector
pure function conjg_tensor2odd (t2) result (conjg_t2)
    type(tensor2odd), intent(in) :: t2
    type(tensor2odd) :: conjg_t2
    conjg_t2%e = conjg (t2%e)
    conjg_t2%b = conjg (t2%b)
end function conjg_tensor2odd

```

X.4.8 ϵ -Tensors

$$\epsilon_{0123} = 1 = -\epsilon^{0123} \quad (\text{X.8})$$

in particular

$$\epsilon(p_1, p_2, p_3, p_4) = \epsilon_{\mu_1 \mu_2 \mu_3 \mu_4} p_1^{\mu_1} p_2^{\mu_2} p_3^{\mu_3} p_4^{\mu_4} = p_1^0 p_2^1 p_3^2 p_4^3 \pm \dots \quad (\text{X.9})$$

(Declaration of operations for vectors)+≡

```

interface pseudo_scalar
    module procedure pseudo_scalar_momentum, pseudo_scalar_vector, &
        pseudo_scalar_vec_mom
end interface
public :: pseudo_scalar
private :: pseudo_scalar_momentum, pseudo_scalar_vector

```

(Implementation of operations for vectors)+≡

```

pure function pseudo_scalar_momentum (p1, p2, p3, p4) result (eps1234)
    type(momentum), intent(in) :: p1, p2, p3, p4
    real(kind=default) :: eps1234
    eps1234 = &
        p1%t * p2%x(1) * (p3%x(2) * p4%x(3) - p3%x(3) * p4%x(2)) &
        + p1%t * p2%x(2) * (p3%x(3) * p4%x(1) - p3%x(1) * p4%x(3)) &
        + p1%t * p2%x(3) * (p3%x(1) * p4%x(2) - p3%x(2) * p4%x(1)) &
        - p1%x(1) * p2%x(2) * (p3%x(3) * p4%t - p3%t * p4%x(3)) &
        - p1%x(1) * p2%x(3) * (p3%t * p4%x(2) - p3%x(2) * p4%t) &
        - p1%x(1) * p2%t * (p3%x(2) * p4%x(3) - p3%x(3) * p4%x(2)) &
        + p1%x(2) * p2%x(3) * (p3%t * p4%x(1) - p3%x(1) * p4%t) &
        + p1%x(2) * p2%t * (p3%x(1) * p4%x(3) - p3%x(3) * p4%x(1)) &
        + p1%x(2) * p2%x(1) * (p3%x(3) * p4%t - p3%t * p4%x(3)) &
        - p1%x(3) * p2%t * (p3%x(1) * p4%x(2) - p3%x(2) * p4%x(1)) &
        - p1%x(3) * p2%x(1) * (p3%x(2) * p4%t - p3%t * p4%x(2)) &
        - p1%x(3) * p2%x(2) * (p3%t * p4%x(1) - p3%x(1) * p4%t)
end function pseudo_scalar_momentum

```

(Implementation of operations for vectors)+≡

```

pure function pseudo_scalar_vector (p1, p2, p3, p4) result (eps1234)
    type(vector), intent(in) :: p1, p2, p3, p4

```

```

complex(kind=default) :: eps1234
eps1234 = &
  p1%t      * p2%x(1) * (p3%x(2) * p4%x(3) - p3%x(3) * p4%x(2)) &
+ p1%t      * p2%x(2) * (p3%x(3) * p4%x(1) - p3%x(1) * p4%x(3)) &
+ p1%t      * p2%x(3) * (p3%x(1) * p4%x(2) - p3%x(2) * p4%x(1)) &
- p1%x(1) * p2%x(2) * (p3%x(3) * p4%t      - p3%t      * p4%x(3)) &
- p1%x(1) * p2%x(3) * (p3%t      * p4%x(2) - p3%x(2) * p4%t      ) &
- p1%x(1) * p2%t      * (p3%x(2) * p4%x(3) - p3%x(3) * p4%x(2)) &
+ p1%x(2) * p2%x(3) * (p3%t      * p4%x(1) - p3%x(1) * p4%t      ) &
+ p1%x(2) * p2%t      * (p3%x(1) * p4%x(3) - p3%x(3) * p4%x(1)) &
+ p1%x(2) * p2%x(1) * (p3%x(3) * p4%t      - p3%t      * p4%x(3)) &
- p1%x(3) * p2%t      * (p3%x(1) * p4%x(2) - p3%x(2) * p4%x(1)) &
- p1%x(3) * p2%x(1) * (p3%x(2) * p4%t      - p3%t      * p4%x(2)) &
- p1%x(3) * p2%x(2) * (p3%t      * p4%x(1) - p3%x(1) * p4%t      )
end function pseudo_scalar_vector

<Implementation of operations for vectors>+≡
pure function pseudo_scalar_vec_mom (p1, v1, p2, v2) result (eps1234)
  type(momentum), intent(in)  :: p1, p2
  type(vector), intent(in)    :: v1, v2
  complex(kind=default) :: eps1234
  eps1234 = &
    p1%t      * v1%x(1) * (p2%x(2) * v2%x(3) - p2%x(3) * v2%x(2)) &
+ p1%t      * v1%x(2) * (p2%x(3) * v2%x(1) - p2%x(1) * v2%x(3)) &
+ p1%t      * v1%x(3) * (p2%x(1) * v2%x(2) - p2%x(2) * v2%x(1)) &
- p1%x(1) * v1%x(2) * (p2%x(3) * v2%t      - p2%t      * v2%x(3)) &
- p1%x(1) * v1%x(3) * (p2%t      * v2%x(2) - p2%x(2) * v2%t      ) &
- p1%x(1) * v1%t      * (p2%x(2) * v2%x(3) - p2%x(3) * v2%x(2)) &
+ p1%x(2) * v1%x(3) * (p2%t      * v2%x(1) - p2%x(1) * v2%t      ) &
+ p1%x(2) * v1%t      * (p2%x(1) * v2%x(3) - p2%x(3) * v2%x(1)) &
+ p1%x(2) * v1%x(1) * (p2%x(3) * v2%t      - p2%t      * v2%x(3)) &
- p1%x(3) * v1%t      * (p2%x(1) * v2%x(2) - p2%x(2) * v2%x(1)) &
- p1%x(3) * v1%x(1) * (p2%x(2) * v2%t      - p2%t      * v2%x(2)) &
- p1%x(3) * v1%x(2) * (p2%t      * v2%x(1) - p2%x(1) * v2%t      )
end function pseudo_scalar_vec_mom

```

$$\epsilon_{\mu}(p_1, p_2, p_3) = \epsilon_{\mu\mu_1\mu_2\mu_3} p_1^{\mu_1} p_2^{\mu_2} p_3^{\mu_3} \quad (\text{X.10})$$

i. e.

$$\epsilon_0(p_1, p_2, p_3) = p_1^1 p_2^2 p_3^3 \pm \dots \quad (\text{X.11a})$$

$$\epsilon_1(p_1, p_2, p_3) = p_1^2 p_2^3 p_3^0 \pm \dots \quad (\text{X.11b})$$

$$\epsilon_2(p_1, p_2, p_3) = -p_1^3 p_2^0 p_3^1 \pm \dots \quad (\text{X.11c})$$

$$\epsilon_3(p_1, p_2, p_3) = p_1^0 p_2^1 p_3^2 \pm \dots \quad (\text{X.11d})$$

```

<Declaration of operations for vectors>+≡
interface pseudo_vector
  module procedure pseudo_vector_momentum, pseudo_vector_vector, &
    pseudo_vector_vec_mom
end interface
public :: pseudo_vector
private :: pseudo_vector_momentum, pseudo_vector_vector

```

```

<Implementation of operations for vectors>+≡
pure function pseudo_vector_momentum (p1, p2, p3) result (eps123)
  type(momentum), intent(in) :: p1, p2, p3
  type(momentum) :: eps123
  eps123%t = &
    + p1%x(1) * (p2%x(2) * p3%x(3) - p2%x(3) * p3%x(2)) &
    + p1%x(2) * (p2%x(3) * p3%x(1) - p2%x(1) * p3%x(3)) &
    + p1%x(3) * (p2%x(1) * p3%x(2) - p2%x(2) * p3%x(1))
  eps123%x(1) = &
    + p1%x(2) * (p2%x(3) * p3%t - p2%t * p3%x(3)) &
    + p1%x(3) * (p2%t * p3%x(2) - p2%x(2) * p3%t) &
    + p1%t * (p2%x(2) * p3%x(3) - p2%x(3) * p3%x(2))
  eps123%x(2) = &
    - p1%x(3) * (p2%t * p3%x(1) - p2%x(1) * p3%t) &
    - p1%t * (p2%x(1) * p3%x(3) - p2%x(3) * p3%x(1)) &
    - p1%x(1) * (p2%x(3) * p3%t - p2%t * p3%x(3))
  eps123%x(3) = &
    + p1%t * (p2%x(1) * p3%x(2) - p2%x(2) * p3%x(1)) &
    + p1%x(1) * (p2%x(2) * p3%t - p2%t * p3%x(2)) &
    + p1%x(2) * (p2%t * p3%x(1) - p2%x(1) * p3%t)
end function pseudo_vector_momentum

```

```

<Implementation of operations for vectors>+≡
pure function pseudo_vector_vector (p1, p2, p3) result (eps123)
  type(vector), intent(in) :: p1, p2, p3
  type(vector) :: eps123
  eps123%t = &
    + p1%x(1) * (p2%x(2) * p3%x(3) - p2%x(3) * p3%x(2)) &
    + p1%x(2) * (p2%x(3) * p3%x(1) - p2%x(1) * p3%x(3)) &
    + p1%x(3) * (p2%x(1) * p3%x(2) - p2%x(2) * p3%x(1))
  eps123%x(1) = &
    + p1%x(2) * (p2%x(3) * p3%t - p2%t * p3%x(3)) &
    + p1%x(3) * (p2%t * p3%x(2) - p2%x(2) * p3%t) &
    + p1%t * (p2%x(2) * p3%x(3) - p2%x(3) * p3%x(2))
  eps123%x(2) = &
    - p1%x(3) * (p2%t * p3%x(1) - p2%x(1) * p3%t) &
    - p1%t * (p2%x(1) * p3%x(3) - p2%x(3) * p3%x(1)) &
    - p1%x(1) * (p2%x(3) * p3%t - p2%t * p3%x(3))
  eps123%x(3) = &
    + p1%t * (p2%x(1) * p3%x(2) - p2%x(2) * p3%x(1)) &
    + p1%x(1) * (p2%x(2) * p3%t - p2%t * p3%x(2)) &
    + p1%x(2) * (p2%t * p3%x(1) - p2%x(1) * p3%t)
end function pseudo_vector_vector

```

```

<Implementation of operations for vectors>+≡
pure function pseudo_vector_vec_mom (p1, p2, v) result (eps123)
  type(momentum), intent(in) :: p1, p2
  type(vector), intent(in) :: v
  type(vector) :: eps123
  eps123%t = &
    + p1%x(1) * (p2%x(2) * v%x(3) - p2%x(3) * v%x(2)) &
    + p1%x(2) * (p2%x(3) * v%x(1) - p2%x(1) * v%x(3)) &
    + p1%x(3) * (p2%x(1) * v%x(2) - p2%x(2) * v%x(1))
  eps123%x(1) = &
    + p1%x(2) * (p2%x(3) * v%t - p2%t * v%x(3)) &

```

```

+ p1%x(3) * (p2%t * v%x(2) - p2%x(2) * v%t ) &
+ p1%t * (p2%x(2) * v%x(3) - p2%x(3) * v%x(2))
eps123%x(2) = &
- p1%x(3) * (p2%t * v%x(1) - p2%x(1) * v%t ) &
- p1%t * (p2%x(1) * v%x(3) - p2%x(3) * v%x(1)) &
- p1%x(1) * (p2%x(3) * v%t - p2%t * v%x(3))
eps123%x(3) = &
+ p1%t * (p2%x(1) * v%x(2) - p2%x(2) * v%x(1)) &
+ p1%x(1) * (p2%x(2) * v%t - p2%t * v%x(2)) &
+ p1%x(2) * (p2%t * v%x(1) - p2%x(1) * v%t )
end function pseudo_vector_vec_mom

```

X.4.9 Utilities

<Declaration of operations for vectors>+≡

<Implementation of operations for vectors>+≡

```

subroutine random_momentum (p, pabs, m)
  type(momentum), intent(out) :: p
  real(kind=default), intent(in) :: pabs, m
  real(kind=default), dimension(2) :: r
  real(kind=default) :: phi, cos_th
  call random_number (r)
  phi = 2*PI * r(1)
  cos_th = 2 * r(2) - 1
  p%t = sqrt (pabs**2 + m**2)
  p%x = pabs * (/ cos_th * cos(phi), cos_th * sin(phi), sqrt (1 - cos_th**2) /)
end subroutine random_momentum

```

X.5 Polarization vectors

<omega_polarizations.f90>≡

<Copleft>

```

module omega_polarizations
  use kinds
  use constants
  use omega_vectors
  implicit none
  private
  <Declaration of polarization vectors>
  integer, parameter, public :: omega_polarizations_2010_01_A = 0
contains
  <Implementation of polarization vectors>
end module omega_polarizations

```

Here we use a phase convention for the polarization vectors compatible with the angular momentum coupling to spin 3/2 and spin 2.

$$\epsilon_1^\mu(k) = \frac{1}{|\vec{k}| \sqrt{k_x^2 + k_y^2}} (0; k_z k_x, k_y k_z, -k_x^2 - k_y^2) \quad (\text{X.12a})$$

$$\epsilon_2^\mu(k) = \frac{1}{\sqrt{k_x^2 + k_y^2}} (0; -k_y, k_x, 0) \quad (\text{X.12b})$$

$$\epsilon_3^\mu(k) = \frac{k_0}{m|\vec{k}|} \left(\vec{k}^2/k_0; k_x, k_y, k_z \right) \quad (\text{X.12c})$$

and

$$\epsilon_\pm^\mu(k) = \frac{1}{\sqrt{2}} (\epsilon_1^\mu(k) \pm i\epsilon_2^\mu(k)) \quad (\text{X.13a})$$

$$\epsilon_0^\mu(k) = \epsilon_3^\mu(k) \quad (\text{X.13b})$$

i. e.

$$\epsilon_+^\mu(k) = \frac{1}{\sqrt{2}\sqrt{k_x^2 + k_y^2}} \left(0; \frac{k_z k_x}{|\vec{k}|} - ik_y, \frac{k_y k_z}{|\vec{k}|} + ik_x, -\frac{k_x^2 + k_y^2}{|\vec{k}|} \right) \quad (\text{X.14a})$$

$$\epsilon_-^\mu(k) = \frac{1}{\sqrt{2}\sqrt{k_x^2 + k_y^2}} \left(0; \frac{k_z k_x}{|\vec{k}|} + ik_y, \frac{k_y k_z}{|\vec{k}|} - ik_x, -\frac{k_x^2 + k_y^2}{|\vec{k}|} \right) \quad (\text{X.14b})$$

$$\epsilon_0^\mu(k) = \frac{k_0}{m|\vec{k}|} \left(\vec{k}^2/k_0; k_x, k_y, k_z \right) \quad (\text{X.14c})$$

Determining the mass from the momenta is a numerically haphazardous for light particles. Therefore, we accept some redundancy and pass the mass explicitly.

(Declaration of polarization vectors)≡

```
public :: eps
```

(Implementation of polarization vectors)≡

```
pure function eps (m, k, s) result (e)
  type(vector) :: e
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: k
  integer, intent(in) :: s
  real(kind=default) :: kt, kabs, kabs2, sqrt2
  sqrt2 = sqrt (2.0_default)
  kabs2 = dot_product (k%x, k%x)
  e%t = 0
  e%x = 0
  if (kabs2 > 0) then
    kabs = sqrt (kabs2)
    select case (s)
    case (1)
      kt = sqrt (k%x(1)**2 + k%x(2)**2)
      if (abs(kt) <= epsilon(kt) * kabs) then
        if (k%x(3) > 0) then
          e%x(1) = cmplx ( 1, 0, kind=default) / sqrt2
          e%x(2) = cmplx ( 0, 1, kind=default) / sqrt2
        else
          e%x(1) = cmplx (- 1, 0, kind=default) / sqrt2
          e%x(2) = cmplx ( 0, 1, kind=default) / sqrt2
        end if
      else
        e%x(1) = cmplx ( k%x(3)*k%x(1)/kabs, &
          - k%x(2), kind=default) / kt / sqrt2
        e%x(2) = cmplx ( k%x(3)*k%x(2)/kabs, &
          k%x(1), kind=default) / kt / sqrt2
```

```

        e%x(3) = - kt / kabs / sqrt2
    end if
case (-1)
    kt = sqrt (k%x(1)**2 + k%x(2)**2)
    if (abs(kt) <= epsilon(kt) * kabs) then
        if (k%x(3) > 0) then
            e%x(1) = cmplx ( 1, 0, kind=default) / sqrt2
            e%x(2) = cmplx ( 0, -1, kind=default) / sqrt2
        else
            e%x(1) = cmplx ( -1, 0, kind=default) / sqrt2
            e%x(2) = cmplx ( 0, -1, kind=default) / sqrt2
        end if
    else
        e%x(1) = cmplx ( k%x(3)*k%x(1)/kabs, &
            k%x(2), kind=default) / kt / sqrt2
        e%x(2) = cmplx ( k%x(2)*k%x(3)/kabs, &
            - k%x(1), kind=default) / kt / sqrt2
        e%x(3) = - kt / kabs / sqrt2
    end if
case (0)
    if (m > 0) then
        e%t = kabs / m
        e%x = k%t / (m*kabs) * k%x
    end if
case (3)
    e = (0,1) * k
case (4)
    if (m > 0) then
        e = (1 / m) * k
    else
        e = (1 / k%t) * k
    end if
end select
else !!! for particles in their rest frame defined to be
    !!! polarized along the 3-direction
    select case (s)
    case (1)
        e%x(1) = cmplx ( 1, 0, kind=default) / sqrt2
        e%x(2) = cmplx ( 0, 1, kind=default) / sqrt2
    case (-1)
        e%x(1) = cmplx ( 1, 0, kind=default) / sqrt2
        e%x(2) = cmplx ( 0, -1, kind=default) / sqrt2
    case (0)
        if (m > 0) then
            e%x(3) = 1
        end if
    case (4)
        if (m > 0) then
            e = (1 / m) * k
        else
            e = (1 / k%t) * k
        end if
    end select
end if
end if

```

```
end function eps
```

X.6 Polarization vectors revisited

```
(omega_polarizations_madgraph.f90)≡
<Coyleft>
module omega_polarizations_madgraph
  use kinds
  use constants
  use omega_vectors
  implicit none
  private
  <Declaration of polarization vectors for madgraph>
  integer, parameter, public :: omega_pols_madgraph_2010_01_A = 0
contains
  <Implementation of polarization vectors for madgraph>
end module omega_polarizations_madgraph
```

This set of polarization vectors is compatible with HELAS [5]:

$$\epsilon_1^\mu(k) = \frac{1}{|\vec{k}|\sqrt{k_x^2 + k_y^2}} (0; k_z k_x, k_y k_z, -k_x^2 - k_y^2) \quad (\text{X.15a})$$

$$\epsilon_2^\mu(k) = \frac{1}{\sqrt{k_x^2 + k_y^2}} (0; -k_y, k_x, 0) \quad (\text{X.15b})$$

$$\epsilon_3^\mu(k) = \frac{k_0}{m|\vec{k}|} (\vec{k}^2/k_0; k_x, k_y, k_z) \quad (\text{X.15c})$$

and

$$\epsilon_\pm^\mu(k) = \frac{1}{\sqrt{2}} (\mp \epsilon_1^\mu(k) - i \epsilon_2^\mu(k)) \quad (\text{X.16a})$$

$$\epsilon_0^\mu(k) = \epsilon_3^\mu(k) \quad (\text{X.16b})$$

i. e.

$$\epsilon_+^\mu(k) = \frac{1}{\sqrt{2}\sqrt{k_x^2 + k_y^2}} \left(0; -\frac{k_z k_x}{|\vec{k}|} + i k_y, -\frac{k_y k_z}{|\vec{k}|} - i k_x, \frac{k_x^2 + k_y^2}{|\vec{k}|} \right) \quad (\text{X.17a})$$

$$\epsilon_-^\mu(k) = \frac{1}{\sqrt{2}\sqrt{k_x^2 + k_y^2}} \left(0; \frac{k_z k_x}{|\vec{k}|} + i k_y, \frac{k_y k_z}{|\vec{k}|} - i k_x, -\frac{k_x^2 + k_y^2}{|\vec{k}|} \right) \quad (\text{X.17b})$$

$$\epsilon_0^\mu(k) = \frac{k_0}{m|\vec{k}|} (\vec{k}^2/k_0; k_x, k_y, k_z) \quad (\text{X.17c})$$

Fortunately, for comparing with squared matrix generated by Madgraph we can also use the modified version, since the difference is only a phase and does *not* mix helicity states. Determining the mass from the momenta is a numerically haphazardous for light particles. Therefore, we accept some redundancy and pass the mass explicitly.

```
<Declaration of polarization vectors for madgraph>≡
public :: eps
```

(Implementation of polarization vectors for madgraph)≡

```

pure function eps (m, k, s) result (e)
  type(vector) :: e
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: k
  integer, intent(in) :: s
  real(kind=default) :: kt, kabs, kabs2, sqrt2
  sqrt2 = sqrt (2.0_default)
  kabs2 = dot_product (k%x, k%x)
  e%t = 0
  e%x = 0
  if (kabs2 > 0) then
    kabs = sqrt (kabs2)
    select case (s)
    case (1)
      kt = sqrt (k%x(1)**2 + k%x(2)**2)
      if (abs(kt) <= epsilon(kt) * kabs) then
        if (k%x(3) > 0) then
          e%x(1) = cmplx ( - 1, 0, kind=default) / sqrt2
          e%x(2) = cmplx ( 0, - 1, kind=default) / sqrt2
        else
          e%x(1) = cmplx ( 1, 0, kind=default) / sqrt2
          e%x(2) = cmplx ( 0, - 1, kind=default) / sqrt2
        end if
      else
        e%x(1) = cmplx ( - k%x(3)*k%x(1)/kabs, &
          k%x(2), kind=default) / kt / sqrt2
        e%x(2) = cmplx ( - k%x(2)*k%x(3)/kabs, &
          - k%x(1), kind=default) / kt / sqrt2
        e%x(3) = kt / kabs / sqrt2
      end if
    case (-1)
      kt = sqrt (k%x(1)**2 + k%x(2)**2)
      if (abs(kt) <= epsilon(kt) * kabs) then
        if (k%x(3) > 0) then
          e%x(1) = cmplx ( 1, 0, kind=default) / sqrt2
          e%x(2) = cmplx ( 0, - 1, kind=default) / sqrt2
        else
          e%x(1) = cmplx ( -1, 0, kind=default) / sqrt2
          e%x(2) = cmplx ( 0, - 1, kind=default) / sqrt2
        end if
      else
        e%x(1) = cmplx ( k%x(3)*k%x(1)/kabs, &
          k%x(2), kind=default) / kt / sqrt2
        e%x(2) = cmplx ( k%x(2)*k%x(3)/kabs, &
          - k%x(1), kind=default) / kt / sqrt2
        e%x(3) = - kt / kabs / sqrt2
      end if
    case (0)
      if (m > 0) then
        e%t = kabs / m
        e%x = k%t / (m*kabs) * k%x
      end if
    case (3)

```



```

        e = (0,1) * k
    case (4)
        if (m > 0) then
            e = (1 / m) * k
        else
            e = (1 / k%t) * k
        end if
    end select
else    !!! for particles in their rest frame defined to be
        !!! polarized along the 3-direction
    select case (s)
    case (1)
        e%x(1) = cmplx ( - 1, 0, kind=default) / sqrt2
        e%x(2) = cmplx ( 0, - 1, kind=default) / sqrt2
    case (-1)
        e%x(1) = cmplx ( 1, 0, kind=default) / sqrt2
        e%x(2) = cmplx ( 0, - 1, kind=default) / sqrt2
    case (0)
        if (m > 0) then
            e%x(3) = 1
        end if
    case (4)
        if (m > 0) then
            e = (1 / m) * k
        else
            e = (1 / k%t) * k
        end if
    end select
end if
end function eps

```

X.7 Symmetric Tensors

Spin-2 polarization tensors are symmetric, transversal and traceless

$$\epsilon_m^{\mu\nu}(k) = \epsilon_m^{\nu\mu}(k) \quad (\text{X.18a})$$

$$k_\mu \epsilon_m^{\mu\nu}(k) = k_\nu \epsilon_m^{\mu\nu}(k) = 0 \quad (\text{X.18b})$$

$$\epsilon_{m,\mu}^\mu(k) = 0 \quad (\text{X.18c})$$

with $m = 1, 2, 3, 4, 5$. Our current representation is redundant and does *not* enforce symmetry or tracelessness.

`<omega_tensors.f90>≡`

`<Cotypeleft>`

`module omega_tensors`

`use kinds`

`use constants`

`use omega_vectors`

`implicit none`

`private`

`public :: operator (*), operator (+), operator (-), &`

`operator (.tprod.)`

`public :: abs, conjg`

```

    <intrinsic :: abs>
    <intrinsic :: conjg>
    type, public :: tensor
        ! private (omegalib needs access, but DON'T TOUCH IT!)
        complex(kind=default), dimension(0:3,0:3) :: t
    end type tensor
    <Declaration of operations for tensors>
    integer, parameter, public :: omega_tensors_2010_01_A = 0
contains
    <Implementation of operations for tensors>
end module omega_tensors

```

X.7.1 Vector Space

Scalar Multiplication

```

<Declaration of operations for tensors>≡
    interface operator (*)
        module procedure integer_tensor, real_tensor, double_tensor, &
            complex_tensor, dcomplex_tensor
    end interface
    private :: integer_tensor, real_tensor, double_tensor
    private :: complex_tensor, dcomplex_tensor

<Implementation of operations for tensors>≡
    pure function integer_tensor (x, y) result (xy)
        integer, intent(in) :: x
        type(tensor), intent(in) :: y
        type(tensor) :: xy
        xy%t = x * y%t
    end function integer_tensor
    pure function real_tensor (x, y) result (xy)
        real(kind=single), intent(in) :: x
        type(tensor), intent(in) :: y
        type(tensor) :: xy
        xy%t = x * y%t
    end function real_tensor
    pure function double_tensor (x, y) result (xy)
        real(kind=default), intent(in) :: x
        type(tensor), intent(in) :: y
        type(tensor) :: xy
        xy%t = x * y%t
    end function double_tensor
    pure function complex_tensor (x, y) result (xy)
        complex(kind=single), intent(in) :: x
        type(tensor), intent(in) :: y
        type(tensor) :: xy
        xy%t = x * y%t
    end function complex_tensor
    pure function dcomplex_tensor (x, y) result (xy)
        complex(kind=default), intent(in) :: x
        type(tensor), intent(in) :: y
        type(tensor) :: xy
        xy%t = x * y%t
    end function dcomplex_tensor

```

Addition and Subtraction

```

<Declaration of operations for tensors>+≡
  interface operator (+)
    module procedure plus_tensor
  end interface
  private :: plus_tensor
  interface operator (-)
    module procedure neg_tensor
  end interface
  private :: neg_tensor

<Implementation of operations for tensors>+≡
  pure function plus_tensor (t1) result (t2)
    type(tensor), intent(in) :: t1
    type(tensor) :: t2
    t2 = t1
  end function plus_tensor
  pure function neg_tensor (t1) result (t2)
    type(tensor), intent(in) :: t1
    type(tensor) :: t2
    t2%t = - t1%t
  end function neg_tensor

<Declaration of operations for tensors>+≡
  interface operator (+)
    module procedure add_tensor
  end interface
  private :: add_tensor
  interface operator (-)
    module procedure sub_tensor
  end interface
  private :: sub_tensor

<Implementation of operations for tensors>+≡
  pure function add_tensor (x, y) result (xy)
    type(tensor), intent(in) :: x, y
    type(tensor) :: xy
    xy%t = x%t + y%t
  end function add_tensor
  pure function sub_tensor (x, y) result (xy)
    type(tensor), intent(in) :: x, y
    type(tensor) :: xy
    xy%t = x%t - y%t
  end function sub_tensor

<Declaration of operations for tensors>+≡
  interface operator (.tprod.)
    module procedure out_prod_vv, out_prod_vm, &
      out_prod_mv, out_prod_mm
  end interface
  private :: out_prod_vv, out_prod_vm, &
    out_prod_mv, out_prod_mm

<Implementation of operations for tensors>+≡
  pure function out_prod_vv (v, w) result (t)
    type(tensor) :: t

```

```

    type(vector), intent(in) :: v, w
    integer :: i, j
    t%t(0,0) = v%t * w%t
    t%t(0,1:3) = v%t * w%x
    t%t(1:3,0) = v%x * w%t
    do i = 1, 3
        do j = 1, 3
            t%t(i,j) = v%x(i) * w%x(j)
        end do
    end do
end function out_prod_vv

<Implementation of operations for tensors>+≡
pure function out_prod_vm (v, m) result (t)
    type(tensor) :: t
    type(vector), intent(in) :: v
    type(momentum), intent(in) :: m
    integer :: i, j
    t%t(0,0) = v%t * m%t
    t%t(0,1:3) = v%t * m%x
    t%t(1:3,0) = v%x * m%t
    do i = 1, 3
        do j = 1, 3
            t%t(i,j) = v%x(i) * m%x(j)
        end do
    end do
end function out_prod_vm

<Implementation of operations for tensors>+≡
pure function out_prod_mv (m, v) result (t)
    type(tensor) :: t
    type(vector), intent(in) :: v
    type(momentum), intent(in) :: m
    integer :: i, j
    t%t(0,0) = m%t * v%t
    t%t(0,1:3) = m%t * v%x
    t%t(1:3,0) = m%x * v%t
    do i = 1, 3
        do j = 1, 3
            t%t(i,j) = m%x(i) * v%x(j)
        end do
    end do
end function out_prod_mv

<Implementation of operations for tensors>+≡
pure function out_prod_mm (m, n) result (t)
    type(tensor) :: t
    type(momentum), intent(in) :: m, n
    integer :: i, j
    t%t(0,0) = m%t * n%t
    t%t(0,1:3) = m%t * n%x
    t%t(1:3,0) = m%x * n%t
    do i = 1, 3
        do j = 1, 3
            t%t(i,j) = m%x(i) * n%x(j)
        end do
    end do

```

```

        end do
    end function out_prod_mm

<Declaration of operations for tensors>+≡
    interface abs
        module procedure abs_tensor
    end interface
    private :: abs_tensor

<Implementation of operations for tensors>+≡
    pure function abs_tensor (t) result (abs_t)
        type(tensor), intent(in) :: t
        real(kind=default) :: abs_t
        abs_t = sqrt (sum ((abs (t%t))*2))
    end function abs_tensor

<Declaration of operations for tensors>+≡
    interface conjg
        module procedure conjg_tensor
    end interface
    private :: conjg_tensor

<Implementation of operations for tensors>+≡
    pure function conjg_tensor (t) result (conjg_t)
        type(tensor), intent(in) :: t
        type(tensor) :: conjg_t
        conjg_t%t = conjg (t%t)
    end function conjg_tensor

<Declaration of operations for tensors>+≡
    interface operator (*)
        module procedure tensor_tensor, vector_tensor, tensor_vector, &
            momentum_tensor, tensor_momentum
    end interface
    private :: tensor_tensor, vector_tensor, tensor_vector, &
        momentum_tensor, tensor_momentum

<Implementation of operations for tensors>+≡
    pure function tensor_tensor (t1, t2) result (t1t2)
        type(tensor), intent(in) :: t1
        type(tensor), intent(in) :: t2
        complex(kind=default) :: t1t2
        integer :: i1, i2
        t1t2 = t1%t(0,0)*t2%t(0,0) &
            - dot_product (conjg (t1%t(0,1:)), t2%t(0,1:)) &
            - dot_product (conjg (t1%t(1:,0)), t2%t(1:,0))
        do i1 = 1, 3
            do i2 = 1, 3
                t1t2 = t1t2 + t1%t(i1,i2)*t2%t(i1,i2)
            end do
        end do
    end function tensor_tensor

<Implementation of operations for tensors>+≡
    pure function tensor_vector (t, v) result (tv)
        type(tensor), intent(in) :: t
        type(vector), intent(in) :: v
        type(vector) :: tv

```

```

    tv%t = t%t(0,0) * v%t - dot_product (conjg (t%t(0,1:)), v%x)
    tv%x(1) = t%t(0,1) * v%t - dot_product (conjg (t%t(1,1:)), v%x)
    tv%x(2) = t%t(0,2) * v%t - dot_product (conjg (t%t(2,1:)), v%x)
    tv%x(3) = t%t(0,3) * v%t - dot_product (conjg (t%t(3,1:)), v%x)
end function tensor_vector

```

(Implementation of operations for tensors)+≡

```

pure function vector_tensor (v, t) result (vt)
  type(vector), intent(in) :: v
  type(tensor), intent(in) :: t
  type(vector) :: vt
  vt%t = v%t * t%t(0,0) - dot_product (conjg (v%x), t%t(1:,0))
  vt%x(1) = v%t * t%t(0,1) - dot_product (conjg (v%x), t%t(1:,1))
  vt%x(2) = v%t * t%t(0,2) - dot_product (conjg (v%x), t%t(1:,2))
  vt%x(3) = v%t * t%t(0,3) - dot_product (conjg (v%x), t%t(1:,3))
end function vector_tensor

```

(Implementation of operations for tensors)+≡

```

pure function tensor_momentum (t, p) result (tp)
  type(tensor), intent(in) :: t
  type(momentum), intent(in) :: p
  type(vector) :: tp
  tp%t = t%t(0,0) * p%t - dot_product (conjg (t%t(0,1:)), p%x)
  tp%x(1) = t%t(0,1) * p%t - dot_product (conjg (t%t(1,1:)), p%x)
  tp%x(2) = t%t(0,2) * p%t - dot_product (conjg (t%t(2,1:)), p%x)
  tp%x(3) = t%t(0,3) * p%t - dot_product (conjg (t%t(3,1:)), p%x)
end function tensor_momentum

```

(Implementation of operations for tensors)+≡

```

pure function momentum_tensor (p, t) result (pt)
  type(momentum), intent(in) :: p
  type(tensor), intent(in) :: t
  type(vector) :: pt
  pt%t = p%t * t%t(0,0) - dot_product (p%x, t%t(1:,0))
  pt%x(1) = p%t * t%t(0,1) - dot_product (p%x, t%t(1:,1))
  pt%x(2) = p%t * t%t(0,2) - dot_product (p%x, t%t(1:,2))
  pt%x(3) = p%t * t%t(0,3) - dot_product (p%x, t%t(1:,3))
end function momentum_tensor

```

X.8 Symmetric Polarization Tensors

$$\epsilon_{+2}^{\mu\nu}(k) = \epsilon_+^\mu(k)\epsilon_+^\nu(k) \quad (\text{X.19a})$$

$$\epsilon_{+1}^{\mu\nu}(k) = \frac{1}{\sqrt{2}} (\epsilon_+^\mu(k)\epsilon_0^\nu(k) + \epsilon_0^\mu(k)\epsilon_+^\nu(k)) \quad (\text{X.19b})$$

$$\epsilon_0^{\mu\nu}(k) = \frac{1}{\sqrt{6}} (\epsilon_+^\mu(k)\epsilon_-^\nu(k) + \epsilon_-^\mu(k)\epsilon_+^\nu(k) - 2\epsilon_0^\mu(k)\epsilon_0^\nu(k)) \quad (\text{X.19c})$$

$$\epsilon_{-1}^{\mu\nu}(k) = \frac{1}{\sqrt{2}} (\epsilon_-^\mu(k)\epsilon_0^\nu(k) + \epsilon_0^\mu(k)\epsilon_-^\nu(k)) \quad (\text{X.19d})$$

$$\epsilon_{-2}^{\mu\nu}(k) = \epsilon_-^\mu(k)\epsilon_-^\nu(k) \quad (\text{X.19e})$$

Note that $\epsilon_{\pm 2, \mu}^{\mu}(k) = \epsilon_{\pm}^{\mu}(k) \epsilon_{\pm, \mu}(k) \propto \epsilon_{\pm}^{\mu}(k) \epsilon_{\mp, \mu}^*(k) = 0$ and that the sign in $\epsilon_0^{\mu\nu}(k)$ insures its tracelessness¹.

```

(omega_tensor_polarizations.f90)≡
  <Cotypeleft>
  module omega_tensor_polarizations
    use kinds
    use constants
    use omega_vectors
    use omega_tensors
    use omega_polarizations
    implicit none
    private
    <Declaration of polarization tensors>
    integer, parameter, public :: omega_tensor_pols_2010_01_A = 0
  contains
    <Implementation of polarization tensors>
  end module omega_tensor_polarizations

<Declaration of polarization tensors>≡
  public :: eps2

<Implementation of polarization tensors>≡
  pure function eps2 (m, k, s) result (t)
    type(tensor) :: t
    real(kind=default), intent(in) :: m
    type(momentum), intent(in) :: k
    integer, intent(in) :: s
    type(vector) :: ep, em, e0
    t%t = 0
    select case (s)
    case (2)
      ep = eps (m, k, 1)
      t = ep.tprod.ep
    case (1)
      ep = eps (m, k, 1)
      e0 = eps (m, k, 0)
      t = (1 / sqrt (2.0_default)) &
        * ((ep.tprod.e0) + (e0.tprod.ep))
    case (0)
      ep = eps (m, k, 1)
      e0 = eps (m, k, 0)
      em = eps (m, k, -1)
      t = (1 / sqrt (6.0_default)) &
        * ((ep.tprod.em) + (em.tprod.ep) - 2*(e0.tprod.e0))
    case (-1)
      e0 = eps (m, k, 0)
      em = eps (m, k, -1)
      t = (1 / sqrt (2.0_default)) &
        * ((em.tprod.e0) + (e0.tprod.em))
    case (-2)

```

¹ On the other hand, with the shift operator $L_- |+\rangle = e^{i\phi} |0\rangle$ and $L_- |0\rangle = e^{i\chi} |-\rangle$, we find

$$L_-^2 |++\rangle = 2e^{2i\phi} |00\rangle + e^{i(\phi+\chi)} (|+-\rangle + |--\rangle)$$

i.e. $\chi - \phi = \pi$, if we want to identify $\epsilon_{-,0,+}^{\mu}$ with $|-,0,+\rangle$.

```

        em = eps (m, k, -1)
        t = em.tprod.em
    end select
end function eps2

```

X.9 Couplings

```

⟨omega_couplings.f90⟩≡
  ⟨Copyleft⟩
  module omega_couplings
    use kinds
    use constants
    use omega_vectors
    use omega_tensors
    implicit none
    private
    ⟨Declaration of couplings⟩
    ⟨Declaration of propagators⟩
    integer, parameter, public :: omega_couplings_2010_01_A = 0
  contains
    ⟨Implementation of couplings⟩
    ⟨Implementation of propagators⟩
  end module omega_couplings

⟨Declaration of propagators⟩≡
  public :: wd_tl

⟨Declaration of propagators⟩+≡
  public :: gauss

```

$$\Theta(p^2)\Gamma \quad (X.20)$$

```

⟨Implementation of propagators⟩≡
  pure function wd_tl (p, w) result (width)
    real(kind=default) :: width
    type(momentum), intent(in) :: p
    real(kind=default), intent(in) :: w
    if (p*p > 0) then
      width = w
    else
      width = 0
    end if
  end function wd_tl

⟨Implementation of propagators⟩+≡
  pure function gauss (x, mu, w) result (gg)
    real(kind=default) :: gg
    real(kind=default), intent(in) :: x, mu, w
    if (w > 0) then
      gg = exp(-(x - mu**2)**2/4.0_default/mu**2/w**2) * &
        sqrt(sqrt(PI/2)) / w / mu
    else
      gg = 1.0_default
    end if
  end function gauss

```


(Declaration of propagators)+≡

```
public :: pr_phi, pr_unitarity, pr_feynman, pr_gauge, pr_rxi
public :: pj_phi, pj_unitarity
public :: pg_phi, pg_unitarity
```

$$\frac{i}{p^2 - m^2 + im\Gamma} \phi \quad (X.21)$$

(Implementation of propagators)+≡

```
pure function pr_phi (p, m, w, phi) result (pphi)
  complex(kind=default) :: pphi
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  complex(kind=default), intent(in) :: phi
  pphi = (1 / cmplx (p*p - m**2, m*w, kind=default)) * phi
end function pr_phi
```

$$\sqrt{\frac{\pi}{MT}} \phi \quad (X.22)$$

(Implementation of propagators)+≡

```
pure function pj_phi (m, w, phi) result (pphi)
  complex(kind=default) :: pphi
  real(kind=default), intent(in) :: m, w
  complex(kind=default), intent(in) :: phi
  pphi = (0, -1) * sqrt (PI / m / w) * phi
end function pj_phi
```

(Implementation of propagators)+≡

```
pure function pg_phi (p, m, w, phi) result (pphi)
  complex(kind=default) :: pphi
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  complex(kind=default), intent(in) :: phi
  pphi = ((0, 1) * gauss (p*p, m, w)) * phi
end function pg_phi
```

$$\frac{i}{p^2 - m^2 + im\Gamma} \left(-g_{\mu\nu} + \frac{p_\mu p_\nu}{m^2} \right) \epsilon^\nu(p) \quad (X.23)$$

NB: the explicit cast to `vector` is required here, because a specific `complex_momentum` procedure for `operator (*)` would introduce ambiguities. NB: we used to use the constructor `vector (p%t, p%x)` instead of the temporary variable, but the Intel Fortran Compiler choked on it.

(Implementation of propagators)+≡

```
pure function pr_unitarity (p, m, w, e) result (pe)
  type(vector) :: pe
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  type(vector), intent(in) :: e
  type(vector) :: pv
  pv = p
  pe = - (1 / cmplx (p*p - m**2, m*w, kind=default)) &
    * (e - (p*e / m**2) * pv)
end function pr_unitarity
```

$$\sqrt{\frac{\pi}{M\Gamma}} \left(-g_{\mu\nu} + \frac{p_\mu p_\nu}{m^2} \right) \epsilon^\nu(p) \quad (\text{X.24})$$

(Implementation of propagators)+≡

```

pure function pj_unitarity (p, m, w, e) result (pe)
  type(vector) :: pe
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  type(vector), intent(in) :: e
  type(vector) :: pv
  pv = p
  pe = (0, 1) * sqrt (PI / m / w) * (e - (p*e / m**2) * pv)
end function pj_unitarity

```

(Implementation of propagators)+≡

```

pure function pg_unitarity (p, m, w, e) result (pe)
  type(vector) :: pe
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  type(vector), intent(in) :: e
  type(vector) :: pv
  pv = p
  pe = - gauss (p*p, m, w) &
    * (e - (p*e / m**2) * pv)
end function pg_unitarity

```

$$\frac{-i}{p^2} \epsilon^\nu(p) \quad (\text{X.25})$$

(Implementation of propagators)+≡

```

pure function pr_feynman (p, e) result (pe)
  type(vector) :: pe
  type(momentum), intent(in) :: p
  type(vector), intent(in) :: e
  pe = - (1 / (p*p)) * e
end function pr_feynman

```

$$\frac{i}{p^2} \left(-g_{\mu\nu} + (1 - \xi) \frac{p_\mu p_\nu}{p^2} \right) \epsilon^\nu(p) \quad (\text{X.26})$$

(Implementation of propagators)+≡

```

pure function pr_gauge (p, xi, e) result (pe)
  type(vector) :: pe
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: xi
  type(vector), intent(in) :: e
  real(kind=default) :: p2
  type(vector) :: pv
  p2 = p*p
  pv = p
  pe = - (1 / p2) * (e - ((1 - xi) * (p*e) / p2) * pv)
end function pr_gauge

```

$$\frac{i}{p^2 - m^2 + im\Gamma} \left(-g_{\mu\nu} + (1 - \xi) \frac{p_\mu p_\nu}{p^2 - \xi m^2} \right) \epsilon^\nu(p) \quad (\text{X.27})$$

```

<Implementation of propagators>+≡
pure function pr_rxi (p, m, w, xi, e) result (pe)
  type(vector) :: pe
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w, xi
  type(vector), intent(in) :: e
  real(kind=default) :: p2
  type(vector) :: pv
  p2 = p*p
  pv = p
  pe = - (1 / cmplx (p2 - m**2, m*w, kind=default)) &
    * (e - ((1 - xi) * (p*e) / (p2 - xi * m**2)) * pv)
end function pr_rxi

```

```

<Declaration of propagators>+≡
public :: pr_tensor

```

$$\frac{iP^{\mu\nu,\rho\sigma}(p, m)}{p^2 - m^2 + im\Gamma} T_{\rho\sigma} \quad (\text{X.28a})$$

with

$$P^{\mu\nu,\rho\sigma}(p, m) = \frac{1}{2} \left(g^{\mu\rho} - \frac{p^\mu p^\rho}{m^2} \right) \left(g^{\nu\sigma} - \frac{p^\nu p^\sigma}{m^2} \right) + \frac{1}{2} \left(g^{\mu\sigma} - \frac{p^\mu p^\sigma}{m^2} \right) \left(g^{\nu\rho} - \frac{p^\nu p^\rho}{m^2} \right) - \frac{1}{3} \left(g^{\mu\nu} - \frac{p^\mu p^\nu}{m^2} \right) \left(g^{\rho\sigma} - \frac{p^\rho p^\sigma}{m^2} \right) \quad (\text{X.28b})$$

Be careful with raising and lowering of indices:

$$g^{\mu\nu} - \frac{k^\mu k^\nu}{m^2} = \begin{pmatrix} 1 - k^0 k^0 / m^2 & -k^0 \vec{k} / m^2 \\ -\vec{k} k^0 / m^2 & -\mathbf{1} - \vec{k} \otimes \vec{k} / m^2 \end{pmatrix} \quad (\text{X.29a})$$

$$g^\mu{}_\nu - \frac{k^\mu k_\nu}{m^2} = \begin{pmatrix} 1 - k^0 k^0 / m^2 & k^0 \vec{k} / m^2 \\ -\vec{k} k^0 / m^2 & \mathbf{1} + \vec{k} \otimes \vec{k} / m^2 \end{pmatrix} \quad (\text{X.29b})$$

```

<Implementation of propagators>+≡
pure function pr_tensor (p, m, w, t) result (pt)
  type(tensor) :: pt
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  type(tensor), intent(in) :: t
  complex(kind=default) :: p_dd_t
  real(kind=default), dimension(0:3,0:3) :: p_uu, p_ud, p_du, p_dd
  integer :: i, j
  p_uu(0,0) = 1 - p%t * p%t / m**2
  p_uu(0,1:3) = - p%t * p%x / m**2
  p_uu(1:3,0) = p_uu(0,1:3)
  do i = 1, 3
    do j = 1, 3
      p_uu(i,j) = - p%x(i) * p%x(j) / m**2
    end do
  end do

```

```

    end do
  end do
  do i = 1, 3
    p_uu(i,i) = - 1 + p_uu(i,i)
  end do
  p_ud(:,0) = p_uu(:,0)
  p_ud(:,1:3) = - p_uu(:,1:3)
  p_du = transpose (p_ud)
  p_dd(:,0) = p_du(:,0)
  p_dd(:,1:3) = - p_du(:,1:3)
  p_dd_t = 0
  do i = 0, 3
    do j = 0, 3
      p_dd_t = p_dd_t + p_dd(i,j) * t%t(i,j)
    end do
  end do
  pt%t = matmul (p_ud, matmul (0.5_default * (t%t + transpose (t%t)), p_du)) &
    - (p_dd_t / 3.0_default) * p_uu
  pt%t = pt%t / cmplx (p*p - m**2, m*w, kind=default)
end function pr_tensor

```

X.9.1 Triple Gauge Couplings

(Declaration of couplings)≡

```
public :: g_gg
```

According to (9.6c)

$$\begin{aligned}
 A^{a,\mu}(k_1 + k_2) = & -ig((k_1^\mu - k_2^\mu)A^{a_1}(k_1) \cdot A^{a_2}(k_2) \\
 & + (2k_2 + k_1) \cdot A^{a_1}(k_1)A^{a_2,\mu}(k_2) - A^{a_1,\mu}(k_1)A^{a_2}(k_2) \cdot (2k_1 + k_2)) \quad (X.30)
 \end{aligned}$$

(Implementation of couplings)≡

```

pure function g_gg (g, a1, k1, a2, k2) result (a)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: a1, a2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: a
  a = (0, -1) * g * ((k1 - k2) * (a1 * a2) &
    + ((2*k2 + k1) * a1) * a2 - a1 * ((2*k1 + k2) * a2))
end function g_gg

```

X.9.2 Quadruple Gauge Couplings

(Declaration of couplings)+≡

```
public :: x_gg, g_gx
```

$$T^{a,\mu\nu}(k_1 + k_2) = g(A^{a_1,\mu}(k_1)A^{a_2,\nu}(k_2) - A^{a_1,\nu}(k_1)A^{a_2,\mu}(k_2)) \quad (X.31)$$

(Implementation of couplings)+≡

```

pure function x_gg (g, a1, a2) result (x)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: a1, a2
  type(tensor2odd) :: x
  x = g * (a1 .wedge. a2)
end function x_gg

```

$$A^{a,\mu}(k_1 + k_2) = g A_\nu^{a_1}(k_1) T^{a_2, \nu\mu}(k_2) \quad (\text{X.32})$$

(Implementation of couplings) +=

```

pure function g_gx (g, a1, x) result (a)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: a1
  type(tensor2odd), intent(in) :: x
  type(vector) :: a
  a = g * (a1 * x)
end function g_gx

```

X.9.3 Scalar Current

(Declaration of couplings) +=

```

public :: v_ss, s_vs

```

$$V^\mu(k_1 + k_2) = g(k_1^\mu - k_2^\mu) \phi_1(k_1) \phi_2(k_2) \quad (\text{X.33})$$

(Implementation of couplings) +=

```

pure function v_ss (g, phi1, k1, phi2, k2) result (v)
  complex(kind=default), intent(in) :: g, phi1, phi2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: v
  v = (k1 - k2) * (g * phi1 * phi2)
end function v_ss

```

$$\phi(k_1 + k_2) = g(k_1^\mu + 2k_2^\mu) V_\mu(k_1) \phi(k_2) \quad (\text{X.34})$$

(Implementation of couplings) +=

```

pure function s_vs (g, v1, k1, phi2, k2) result (phi)
  complex(kind=default), intent(in) :: g, phi2
  type(vector), intent(in) :: v1
  type(momentum), intent(in) :: k1, k2
  complex(kind=default) :: phi
  phi = g * ((k1 + 2*k2) * v1) * phi2
end function s_vs

```

X.9.4 Triple Vector Couplings

(Declaration of couplings) +=

```

public :: tkv_vv, lkv_vv, tv_kv, lv_kv, kg_kgkg
public :: t5kv_vv, l5kv_vv, t5v_kv, l5v_kv, kg5_kgkg, kg_kg5kg

```

$$V^\mu(k_1 + k_2) = ig(k_1 - k_2)^\mu V_1^\nu(k_1) V_{2,\nu}(k_2) \quad (\text{X.35})$$

(Implementation of couplings) +=

```

pure function tkv_vv (g, v1, k1, v2, k2) result (v)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: v
  v = (k1 - k2) * ((0, 1) * g * (v1*v2))
end function tkv_vv

```

$$V^\mu(k_1 + k_2) = ig\epsilon^{\mu\nu\rho\sigma}(k_1 - k_2)_\nu V_{1,\rho}(k_1)V_{2,\sigma}(k_2) \quad (X.36)$$

(Implementation of couplings)+≡

```
pure function t5kv_vv (g, v1, k1, v2, k2) result (v)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: v
  type(vector) :: k
  k = k1 - k2
  v = (0, 1) * g * pseudo_vector (k, v1, v2)
end function t5kv_vv
```

$$V^\mu(k_1 + k_2) = ig(k_1 + k_2)^\mu V_1^\nu(k_1)V_{2,\nu}(k_2) \quad (X.37)$$

(Implementation of couplings)+≡

```
pure function lkv_vv (g, v1, k1, v2, k2) result (v)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: v
  v = (k1 + k2) * ((0, 1) * g * (v1*v2))
end function lkv_vv
```

$$V^\mu(k_1 + k_2) = ig\epsilon^{\mu\nu\rho\sigma}(k_1 + k_2)_\nu V_{1,\rho}(k_1)V_{2,\sigma}(k_2) \quad (X.38)$$

(Implementation of couplings)+≡

```
pure function l5kv_vv (g, v1, k1, v2, k2) result (v)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: v
  type(vector) :: k
  k = k1 + k2
  v = (0, 1) * g * pseudo_vector (k, v1, v2)
end function l5kv_vv
```

$$V^\mu(k_1 + k_2) = ig(k_2 - k)^\nu V_{1,\nu}(k_1)V_2^\mu(k_2) = ig(2k_2 + k_1)^\nu V_{1,\nu}(k_1)V_2^\mu(k_2) \quad (X.39)$$

using $k = -k_1 - k_2$

(Implementation of couplings)+≡

```
pure function tv_kv (g, v1, k1, v2, k2) result (v)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: v
  v = v2 * ((0, 1) * g * ((2*k2 + k1)*v1))
end function tv_kv
```

$$V^\mu(k_1 + k_2) = ig\epsilon^{\mu\nu\rho\sigma}(2k_2 + k_1)_\nu V_{1,\rho}(k_1)V_{2,\sigma}(k_2) \quad (X.40)$$

(Implementation of couplings)+≡

```

pure function t5v_kv (g, v1, k1, v2, k2) result (v)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: v
  type(vector) :: k
  k = k1 + 2*k2
  v = (0, 1) * g * pseudo_vector (k, v1, v2)
end function t5v_kv

```

$$V^\mu(k_1 + k_2) = -igk_1^\nu V_{1,\nu}(k_1) V_2^\mu(k_2) \quad (\text{X.41})$$

using $k = -k_1 - k_2$

(Implementation of couplings) +=

```

pure function lv_kv (g, v1, k1, v2) result (v)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1
  type(vector) :: v
  v = v2 * ((0, -1) * g * (k1*v1))
end function lv_kv

```

$$V^\mu(k_1 + k_2) = -ig\epsilon^{\mu\nu\rho\sigma} k_{1,\nu} V_{1,\rho}(k_1) V_{2,\sigma}(k_2) \quad (\text{X.42})$$

(Implementation of couplings) +=

```

pure function l5v_kv (g, v1, k1, v2) result (v)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1
  type(vector) :: v
  type(vector) :: k
  k = k1
  v = (0, -1) * g * pseudo_vector (k, v1, v2)
end function l5v_kv

```

$$A^\mu(k_1 + k_2) = igk^\nu \left(F_{1,\nu}{}^\rho(k_1) F_{2,\rho\mu}(k_2) - F_{1,\mu}{}^\rho(k_1) F_{2,\rho\nu}(k_2) \right) \quad (\text{X.43})$$

with $k = -k_1 - k_2$, i.e.

$$\begin{aligned}
A^\mu(k_1 + k_2) = -ig \Big(& [(kk_2)(k_1 A_2) - (k_1 k_2)(k A_2)] A_1^\mu \\
& + [(k_1 k_2)(k A_1) - (kk_1)(k_2 A_1)] A_2^\mu \\
& + [(k_2 A_1)(k A_2) - (kk_2)(A_1 A_2)] k_1^\mu \\
& + [(kk_1)(A_1 A_2) - (k A_1)(k_1 A_2)] k_2^\mu \Big) \quad (\text{X.44})
\end{aligned}$$

(Implementation of couplings) +=

```

pure function kg_kgkg (g, a1, k1, a2, k2) result (a)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: a1, a2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: a
  real(kind=default) :: k1k1, k2k2, k1k2, kk1, kk2

```

```

complex(kind=default) :: a1a2, k2a1, ka1, k1a2, ka2
k1k1 = k1 * k1
k1k2 = k1 * k2
k2k2 = k2 * k2
kk1 = k1k1 + k1k2
kk2 = k1k2 + k2k2
k2a1 = k2 * a1
ka1 = k2a1 + k1 * a1
k1a2 = k1 * a2
ka2 = k1a2 + k2 * a2
a1a2 = a1 * a2
a = (0, -1) * g * ( (kk2 * k1a2 - k1k2 * ka2) * a1 &
+ (k1k2 * ka1 - kk1 * k2a1) * a2 &
+ (ka2 * k2a1 - kk2 * a1a2) * k1 &
+ (kk1 * a1a2 - ka1 * k1a2) * k2 )
end function kg_kgkg

```

$$A^\mu(k_1 + k_2) = ig\epsilon^{\mu\nu\rho\sigma}k_\nu F_{1,\rho}{}^\lambda(k_1)F_{2,\lambda\sigma}(k_2) \quad (\text{X.45})$$

with $k = -k_1 - k_2$, i. e.

$$A^\mu(k_1 + k_2) = -2ig\epsilon^{\mu\nu\rho\sigma}k_\nu \left((k_2 A_1)k_{1,\rho}A_{2,\sigma} + (k_1 A_2)A_{1,\rho}k_{2,\sigma} \right. \\ \left. - (A_1 A_2)k_{1,\rho}k_{2,\sigma} - (k_1 k_2)A_{1,\rho}A_{2,\sigma} \right) \quad (\text{X.46})$$

(Implementation of couplings) +=

```

pure function kg5_kgkg (g, a1, k1, a2, k2) result (a)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: a1, a2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: a
  type(vector) :: kv, k1v, k2v
  kv = - k1 - k2
  k1v = k1
  k2v = k2
  a = (0, -2) * g * ( (k2*A1) * pseudo_vector (kv, k1v, a2 ) &
+ (k1*A2) * pseudo_vector (kv, A1 , k2v) &
- (A1*A2) * pseudo_vector (kv, k1v, k2v) &
- (k1*k2) * pseudo_vector (kv, a1 , a2 ) )
end function kg5_kgkg

```

$$A^\mu(k_1 + k_2) = igk_\nu \left(\epsilon^{\mu\rho\lambda\sigma} F_{1,\rho}{}^\nu - \epsilon^{\nu\rho\lambda\sigma} F_{1,\rho}{}^\mu \right) \frac{1}{2} F_{1,\lambda\sigma} \quad (\text{X.47})$$

with $k = -k_1 - k_2$, i. e.

$$A^\mu(k_1 + k_2) = -ig \left(\epsilon^{\mu\rho\lambda\sigma} (k k_2) A_{2,\rho} - \epsilon^{\mu\rho\lambda\sigma} (k A_2) k_{2,\rho} - k_2^\mu \epsilon^{\nu\rho\lambda\sigma} k_n u A_{2,\rho} + A_2^\mu \epsilon^{\nu\rho\lambda\sigma} k_n u k_{2,\rho} \right) k_{1,\lambda} A_{1,\sigma} \quad (\text{X.48})$$



This is not the most efficient way of doing it: $\epsilon^{\mu\nu\rho\sigma} F_{1,\rho\sigma}$ should be cached!

(Implementation of couplings) +=

```

pure function kg_kg5kg (g, a1, k1, a2, k2) result (a)
  complex(kind=default), intent(in) :: g

```



```

type(vector), intent(in) :: a1, a2
type(momentum), intent(in) :: k1, k2
type(vector) :: a
type(vector) :: kv, k1v, k2v
kv = - k1 - k2
k1v = k1
k2v = k2
a = (0, -1) * g * ( (kv*k2v) * pseudo_vector (a2 , k1v, a1) &
- (kv*a2 ) * pseudo_vector (k2v, k1v, a1) &
- k2v * pseudo_scalar (kv, a2, k1v, a1) &
+ a2 * pseudo_scalar (kv, k2v, k1v, a1) )
end function kg_kg5kg

```

X.10 Graviton Couplings

(Declaration of couplings)+≡

```
public :: s_gravs, v_gravv, grav_ss, grav_vv
```

(Implementation of couplings)+≡

```

pure function s_gravs (g, m, k1, k2, t, s) result (phi)
  complex(kind=default), intent(in) :: g, s
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: k1, k2
  type(tensor), intent(in) :: t
  complex(kind=default) :: phi, t_tr
  t_tr = t%(0,0) - t%(1,1) - t%(2,2) - t%(3,3)
  phi = g * s * (((t*k1)*k2) + ((t*k2)*k1) &
- g * (m**2 + (k1*k2))*t_tr)/2.0_default
end function s_gravs

```

(Implementation of couplings)+≡

```

pure function grav_ss (g, m, k1, k2, s1, s2) result (t)
  complex(kind=default), intent(in) :: g, s1, s2
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: k1, k2
  type(tensor) :: t_metric, t
  t_metric%t = 0
  t_metric%t(0,0) = 1.0_default
  t_metric%t(1,1) = - 1.0_default
  t_metric%t(2,2) = - 1.0_default
  t_metric%t(3,3) = - 1.0_default
  t = g*s1*s2/2.0_default * (-m**2 + (k1*k2)) * t_metric &
+ (k1.tprod.k2) + (k2.tprod.k1))
end function grav_ss

```

(Implementation of couplings)+≡

```

pure function v_gravv (g, m, k1, k2, t, v) result (vec)
  complex(kind=default), intent(in) :: g
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: k1, k2
  type(vector), intent(in) :: v
  type(tensor), intent(in) :: t
  complex(kind=default) :: t_tr
  real(kind=default) :: xi

```

```

type(vector) :: vec
xi = 1.0_default
t_tr = t%t(0,0) - t%t(1,1) - t%t(2,2) - t%t(3,3)
vec = (-g)/ 2.0_default * (((k1*k2) + m**2) * &
    (t*v + v*t - t_tr * v) + t_tr * (k1*v) * k2 &
    - (k1*v) * ((k2*t) + (t*k2)) &
    - ((k1*(t*v)) + (v*(t*k1))) * k2 &
    + ((k1*(t*k2)) + (k2*(t*k1))) * v)
!!!      Unitarity gauge: xi -> Infinity
!!!      + (1.0_default/xi) * (t_tr * ((k1*v)*k2) + &
!!!      (k2*v)*k2 + (k2*v)*k1 - (k1*(t*v))*k1 + &
!!!      (k2*v)*(k2*t) - (v*(t*k1))*k1 - (k2*v)*(t*k2)))
end function v_gravv

<Implementation of couplings>+=
pure function grav_vv (g, m, k1, k2, v1, v2) result (t)
    complex(kind=default), intent(in) :: g
    type(momentum), intent(in) :: k1, k2
    real(kind=default), intent(in) :: m
    real(kind=default) :: xi
    type(vector), intent (in) :: v1, v2
    type(tensor) :: t_metric, t
    xi = 0.00001_default
    t_metric%t = 0
    t_metric%t(0,0) = 1.0_default
    t_metric%t(1,1) = - 1.0_default
    t_metric%t(2,2) = - 1.0_default
    t_metric%t(3,3) = - 1.0_default
    t = (-g)/2.0_default * ( &
        ((k1*k2) + m**2) * ( &
            (v1.tprod.v2) + (v2.tprod.v1) - (v1*v2) * t_metric) &
        + (v1*k2)*(v2*k1)*t_metric &
        - (k2*v1)*((v2.tprod.k1) + (k1.tprod.v2)) &
        - (k1*v2)*((v1.tprod.k2) + (k2.tprod.v1)) &
        + (v1*v2)*((k1.tprod.k2) + (k2.tprod.k1)))
    !!!      Unitarity gauge: xi -> Infinity
    !!!      + (1.0_default/xi) * ( &
    !!!      ((k1*v1)*(k1*v2) + (k2*v1)*(k2*v2) + (k1*v1)*(k2*v2))* &
    !!!      t_metric) - (k1*v1) * ((k1.tprod.v2) + (v2.tprod.k1)) &
    !!!      - (k2*v2) * ((k2.tprod.v1) + (v1.tprod.k2)))
end function grav_vv

```

X.11 Tensor Couplings

```

<Declaration of couplings>+=
public :: t2_vv, v_t2v, t2_vv_1, v_t2v_1

```

X.12 Scalar-Vector Dim-5 Couplings

```

<Declaration of couplings>+=
public :: phi_vv, v_phiv, phi_u_vv, v_u_phiv

```

```

<Implementation of couplings>+=
pure function phi_vv (g, k1, k2, v1, v2) result (phi)
  complex(kind=default), intent(in) :: g
  type(momentum), intent(in) :: k1, k2
  type(vector), intent(in) :: v1, v2
  complex(kind=default) :: phi
  phi = g * pseudo_scalar (k1, v1, k2, v2)
end function phi_vv

<Implementation of couplings>+=
pure function v_phiv (g, phi, k1, k2, v) result (w)
  complex(kind=default), intent(in) :: g, phi
  type(vector), intent(in) :: v
  type(momentum), intent(in) :: k1, k2
  type(vector) :: w
  w = g * phi * pseudo_vector (k1, k2, v)
end function v_phiv

<Implementation of couplings>+=
pure function phi_u_vv (g, k1, k2, v1, v2) result (phi)
  complex(kind=default), intent(in) :: g
  type(momentum), intent(in) :: k1, k2
  type(vector), intent(in) :: v1, v2
  complex(kind=default) :: phi
  phi = g * ((k1*v2)*((-k1+k2))*v1) + &
           (k2*v1)*((-k1+k2))*v2) + &
           (((k1+k2)*(k1+k2)) * (v1*v2)))
end function phi_u_vv

<Implementation of couplings>+=
pure function v_u_phiv (g, phi, k1, k2, v) result (w)
  complex(kind=default), intent(in) :: g, phi
  type(vector), intent(in) :: v
  type(momentum), intent(in) :: k1, k2
  type(vector) :: w
  w = g * phi * ((k1*v)*k2 + &
                 ((-k1+k2))*v)*k1 + &
                 ((k1*k1)*v))
end function v_u_phiv

<Implementation of couplings>+=
pure function t2_vv (g, v1, v2) result (t)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(tensor) :: t
  type(tensor) :: tmp
  tmp = v1.tprod.v2
  t%t = g * (tmp%t + transpose (tmp%t))
end function t2_vv

<Implementation of couplings>+=
pure function v_t2v (g, t, v) result (tv)
  complex(kind=default), intent(in) :: g
  type(tensor), intent(in) :: t
  type(vector), intent(in) :: v
  type(vector) :: tv
  type(tensor) :: tmp

```

```

    tmp%t = t%t + transpose (t%t)
    tv = g * (tmp * v)
end function v_t2v

<Implementation of couplings>+=
pure function t2_vv_1 (g, v1, v2) result (t)
  complex(kind=default), intent(in) :: g
  complex(kind=default) :: tmp_s
  type(vector), intent(in) :: v1, v2
  type(tensor) :: tmp
  type(tensor) :: t_metric, t
  t_metric%t = 0
  t_metric%t(0,0) = 1.0_default
  t_metric%t(1,1) = - 1.0_default
  t_metric%t(2,2) = - 1.0_default
  t_metric%t(3,3) = - 1.0_default
  tmp = v1.tprod.v2
  tmp_s = v1 * v2
  t%t = g * (tmp%t + transpose (tmp%t) - tmp_s * t_metric%t )
end function t2_vv_1

<Implementation of couplings>+=
pure function v_t2v_1 (g, t, v) result (tv)
  complex(kind=default), intent(in) :: g
  type(tensor), intent(in) :: t
  type(vector), intent(in) :: v
  type(vector) :: tv, tmp_tv
  type(tensor) :: tmp
  tmp_tv = ( t%t(0,0)+t%t(1,1)+t%t(2,2)+t%t(3,3) ) * v
  tmp%t = t%t + transpose (t%t)
  tv = g * (tmp * v - tmp_tv)
end function v_t2v_1

<Declaration of couplings>+=
public :: t2_vv_d5_1, v_t2v_d5_1

<Implementation of couplings>+=
pure function t2_vv_d5_1 (g, v1, k1, v2, k2) result (t)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(tensor) :: t
  t = (g * (v1 * v2)) * (k1-k2).tprod.(k1-k2)
end function t2_vv_d5_1

<Implementation of couplings>+=
pure function v_t2v_d5_1 (g, t1, k1, v2, k2) result (tv)
  complex(kind=default), intent(in) :: g
  type(tensor), intent(in) :: t1
  type(vector), intent(in) :: v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: tv
  tv = (g * ((k1+2*k2).tprod.(k1+2*k2) * t1)) * v2
end function v_t2v_d5_1

<Declaration of couplings>+=
public :: t2_vv_d5_2, v_t2v_d5_2

```

```

<Implementation of couplings>+=
pure function t2_vv_d5_2 (g, v1, k1, v2, k2) result (t)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(tensor) :: t
  t = (g * (k2 * v1)) * (k2-k1).tprod.v2
  t%t = t%t + transpose (t%t)
end function t2_vv_d5_2

<Implementation of couplings>+=
pure function v_t2v_d5_2 (g, t1, k1, v2, k2) result (tv)
  complex(kind=default), intent(in) :: g
  type(tensor), intent(in) :: t1
  type(vector), intent(in) :: v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: tv
  type(tensor) :: tmp
  type(momentum) :: k1_k2, k1_2k2
  k1_k2 = k1 + k2
  k1_2k2 = k1_k2 + k2
  tmp%t = t1%t + transpose (t1%t)
  tv = (g * (k1_k2 * v2)) * (k1_2k2 * tmp)
end function v_t2v_d5_2

<Declaration of couplings>+=
public :: t2_vv_d7, v_t2v_d7

<Implementation of couplings>+=
pure function t2_vv_d7 (g, v1, k1, v2, k2) result (t)
  complex(kind=default), intent(in) :: g
  type(vector), intent(in) :: v1, v2
  type(momentum), intent(in) :: k1, k2
  type(tensor) :: t
  t = (g * (k2 * v1) * (k1 * v2)) * (k1-k2).tprod.(k1-k2)
end function t2_vv_d7

<Implementation of couplings>+=
pure function v_t2v_d7 (g, t1, k1, v2, k2) result (tv)
  complex(kind=default), intent(in) :: g
  type(tensor), intent(in) :: t1
  type(vector), intent(in) :: v2
  type(momentum), intent(in) :: k1, k2
  type(vector) :: tv
  type(vector) :: k1_k2, k1_2k2
  k1_k2 = k1 + k2
  k1_2k2 = k1_k2 + k2
  tv = (- g * (k1_k2 * v2) * (k1_2k2.tprod.k1_2k2 * t1)) * k2
end function v_t2v_d7

```

X.13 Spinor Couplings

```

<omega_spinor_couplings.f90>=
<Cotypeleft>
module omega_spinor_couplings

```

```

use kinds
use constants
use omega_spinors
use omega_vectors
use omega_tensors
use omega_couplings
implicit none
private
<Declaration of spinor on shell wave functions>
<Declaration of spinor off shell wave functions>
<Declaration of spinor currents>
<Declaration of spinor propagators>
integer, parameter, public :: omega_spinor_cppls_2010_01_A = 0
contains
<Implementation of spinor on shell wave functions>
<Implementation of spinor off shell wave functions>
<Implementation of spinor currents>
<Implementation of spinor propagators>
end module omega_spinor_couplings
    
```

See table X.1 for the names of Fortran functions. We could have used long names instead, but this would increase the chance of running past continuation line limits without adding much to the legibility.

X.13.1 Fermionic Vector and Axial Couplings

There's more than one chiral representation. This one is compatible with HELAS [5].

$$\gamma^0 = \begin{pmatrix} 0 & \mathbf{1} \\ \mathbf{1} & 0 \end{pmatrix}, \gamma^i = \begin{pmatrix} 0 & \sigma^i \\ -\sigma^i & 0 \end{pmatrix}, \gamma_5 = i\gamma^0\gamma^1\gamma^2\gamma^3 = \begin{pmatrix} -\mathbf{1} & 0 \\ 0 & \mathbf{1} \end{pmatrix} \quad (\text{X.49})$$

Therefore

$$g_S + g_P\gamma_5 = \begin{pmatrix} g_S - g_P & 0 & 0 & 0 \\ 0 & g_S - g_P & 0 & 0 \\ 0 & 0 & g_S + g_P & 0 \\ 0 & 0 & 0 & g_S + g_P \end{pmatrix} \quad (\text{X.50a})$$

$$g_V\gamma^0 - g_A\gamma^0\gamma_5 = \begin{pmatrix} 0 & 0 & g_V - g_A & 0 \\ 0 & 0 & 0 & g_V - g_A \\ g_V + g_A & 0 & 0 & 0 \\ 0 & g_V + g_A & 0 & 0 \end{pmatrix} \quad (\text{X.50b})$$

$$g_V\gamma^1 - g_A\gamma^1\gamma_5 = \begin{pmatrix} 0 & 0 & 0 & g_V - g_A \\ 0 & 0 & g_V - g_A & 0 \\ 0 & -g_V - g_A & 0 & 0 \\ -g_V - g_A & 0 & 0 & 0 \end{pmatrix} \quad (\text{X.50c})$$

$$g_V\gamma^2 - g_A\gamma^2\gamma_5 = \begin{pmatrix} 0 & 0 & 0 & -i(g_V - g_A) \\ 0 & 0 & i(g_V - g_A) & 0 \\ 0 & i(g_V + g_A) & 0 & 0 \\ -i(g_V + g_A) & 0 & 0 & 0 \end{pmatrix} \quad (\text{X.50d})$$

$\bar{\psi}(g_V\gamma^\mu - g_A\gamma^\mu\gamma_5)\psi$	<code>va_ff(gv, ga, psi, psi)</code>
$g_V\bar{\psi}\gamma^\mu\psi$	<code>v_ff(gv, psi, psi)</code>
$g_A\bar{\psi}\gamma_5\gamma^\mu\psi$	<code>a_ff(ga, psi, psi)</code>
$g_L\bar{\psi}\gamma^\mu(1 - \gamma_5)\psi$	<code>vl_ff(gL, psi, psi)</code>
$g_R\bar{\psi}\gamma^\mu(1 + \gamma_5)\psi$	<code>vr_ff(gR, psi, psi)</code>
$\bar{\psi}(g_V - g_A\gamma_5)\psi$	<code>f_vaf(gv, ga, V, psi)</code>
$g_V\bar{\psi}\psi$	<code>f_vf(gv, V, psi)</code>
$g_A\gamma_5\bar{\psi}\psi$	<code>f_af(ga, V, psi)</code>
$g_L\bar{\psi}(1 - \gamma_5)\psi$	<code>f_vlf(gL, V, psi)</code>
$g_R\bar{\psi}(1 + \gamma_5)\psi$	<code>f_vrf(gR, V, psi)</code>
$\bar{\psi}\psi(g_V - g_A\gamma_5)$	<code>f_fva(gv, ga, psi, V)</code>
$g_V\bar{\psi}\psi$	<code>f_fv(gv, psi, V)</code>
$g_A\bar{\psi}\gamma_5\psi$	<code>f_fa(ga, psi, V)</code>
$g_L\bar{\psi}(1 - \gamma_5)\psi$	<code>f_fvl(gL, psi, V)</code>
$g_R\bar{\psi}(1 + \gamma_5)\psi$	<code>f_fvr(gR, psi, V)</code>

Table X.1: Mnemonically abbreviated names of Fortran functions implementing fermionic vector and axial currents.

$$g_V\gamma^3 - g_A\gamma^3\gamma_5 = \begin{pmatrix} 0 & 0 & g_V - g_A & 0 \\ 0 & 0 & 0 & -g_V + g_A \\ -g_V - g_A & 0 & 0 & 0 \\ 0 & g_V + g_A & 0 & 0 \end{pmatrix} \quad (\text{X.50e})$$

(Declaration of spinor currents)≡

```
public :: va_ff, v_ff, a_ff, vl_ff, vr_ff, vlr_ff, grav_ff, va2_ff, &
        tva_ff, tlr_ff, trl_ff, tvam_ff, tlrn_ff, trlm_ff
```

(Implementation of spinor currents)≡

```
pure function va_ff (gv, ga, psibar, psi) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: gv, ga
    type(conjspinor), intent(in) :: psibar
    type(spinor), intent(in) :: psi
    complex(kind=default) :: gl, gr
    complex(kind=default) :: g13, g14, g23, g24, g31, g32, g41, g42
    gl = gv + ga
    gr = gv - ga
    g13 = psibar%a(1)*psi%a(3)
    g14 = psibar%a(1)*psi%a(4)
    g23 = psibar%a(2)*psi%a(3)
    g24 = psibar%a(2)*psi%a(4)
    g31 = psibar%a(3)*psi%a(1)
    g32 = psibar%a(3)*psi%a(2)
    g41 = psibar%a(4)*psi%a(1)
    g42 = psibar%a(4)*psi%a(2)
    j%t = gr * ( g13 + g24 ) + gl * ( g31 + g42 )
    j%x(1) = gr * ( g14 + g23 ) - gl * ( g32 + g41 )
    j%x(2) = (gr * ( - g14 + g23 ) + gl * ( g32 - g41 )) * (0, 1)
    j%x(3) = gr * ( g13 - g24 ) + gl * ( - g31 + g42 )
end function va_ff
```

$\bar{\psi}(g_S + g_P\gamma_5)\psi$	<code>sp_ff($g_S, g_P, \bar{\psi}, \psi$)</code>
$g_S\bar{\psi}\psi$	<code>s_ff($g_S, \bar{\psi}, \psi$)</code>
$g_P\bar{\psi}\gamma_5\psi$	<code>p_ff($g_P, \bar{\psi}, \psi$)</code>
$g_L\bar{\psi}(1 - \gamma_5)\psi$	<code>sl_ff($g_L, \bar{\psi}, \psi$)</code>
$g_R\bar{\psi}(1 + \gamma_5)\psi$	<code>sr_ff($g_R, \bar{\psi}, \psi$)</code>
$\phi(g_S + g_P\gamma_5)\psi$	<code>f_spf(g_S, g_P, ϕ, ψ)</code>
$g_S\phi\psi$	<code>f_sf(g_S, ϕ, ψ)</code>
$g_P\phi\gamma_5\psi$	<code>f_pf(g_P, ϕ, ψ)</code>
$g_L\phi(1 - \gamma_5)\psi$	<code>f_slf(g_L, ϕ, ψ)</code>
$g_R\phi(1 + \gamma_5)\psi$	<code>f_srf(g_R, ϕ, ψ)</code>
$\psi\phi(g_S + g_P\gamma_5)$	<code>f_fsp(g_S, g_P, ψ, ϕ)</code>
$g_S\psi\phi$	<code>f_fs(g_S, ψ, ϕ)</code>
$g_P\psi\phi\gamma_5$	<code>f_fp(g_P, ψ, ϕ)</code>
$g_L\psi\phi(1 - \gamma_5)$	<code>f_fsl(g_L, ψ, ϕ)</code>
$g_R\psi\phi(1 + \gamma_5)$	<code>f_fsr(g_R, ψ, ϕ)</code>

Table X.2: Mnemonically abbreviated names of Fortran functions implementing fermionic scalar and pseudo scalar “currents”.

(Implementation of spinor currents)+≡

```

pure function va2_ff (gva, psibar, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in), dimension(2) :: gva
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  complex(kind=default) :: gl, gr
  complex(kind=default) :: g13, g14, g23, g24, g31, g32, g41, g42
  gl = gva(1) + gva(2)
  gr = gva(1) - gva(2)
  g13 = psibar%a(1)*psi%a(3)
  g14 = psibar%a(1)*psi%a(4)
  g23 = psibar%a(2)*psi%a(3)
  g24 = psibar%a(2)*psi%a(4)
  g31 = psibar%a(3)*psi%a(1)
  g32 = psibar%a(3)*psi%a(2)
  g41 = psibar%a(4)*psi%a(1)
  g42 = psibar%a(4)*psi%a(2)
  j%t = gr * ( g13 + g24) + gl * ( g31 + g42)
  j%x(1) = gr * ( g14 + g23) - gl * ( g32 + g41)
  j%x(2) = (gr * ( - g14 + g23) + gl * ( g32 - g41)) * (0, 1)
  j%x(3) = gr * ( g13 - g24) + gl * ( - g31 + g42)
end function va2_ff

```

(Implementation of spinor currents)+≡

```

pure function tva_ff (gv, ga, psibar, psi) result (t)
  type(tensor2odd) :: t
  complex(kind=default), intent(in) :: gv, ga
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  complex(kind=default) :: gl, gr
  complex(kind=default) :: g12, g21, g1m2, g34, g43, g3m4

```



```

gr      = gv + ga
gl      = gv - ga
g12     = psibar%a(1)*psi%a(2)
g21     = psibar%a(2)*psi%a(1)
g1m2    = psibar%a(1)*psi%a(1) - psibar%a(2)*psi%a(2)
g34     = psibar%a(3)*psi%a(4)
g43     = psibar%a(4)*psi%a(3)
g3m4    = psibar%a(3)*psi%a(3) - psibar%a(4)*psi%a(4)
t%e(1)  = (gl * ( - g12 - g21) + gr * ( g34 + g43)) * (0, 1)
t%e(2)  = gl * ( - g12 + g21) + gr * ( g34 - g43)
t%e(3)  = (gl * ( - g1m2      ) + gr * ( g3m4      )) * (0, 1)
t%b(1)  = gl * ( g12 + g21) + gr * ( g34 + g43)
t%b(2)  = (gl * ( - g12 + g21) + gr * ( - g34 + g43)) * (0, 1)
t%b(3)  = gl * ( g1m2      ) + gr * ( g3m4      )
end function tva_ff

<Implementation of spinor currents>+=
pure function tlr_ff (gl, gr, psibar, psi) result (t)
  type(tensor2odd) :: t
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  t = tva_ff (gr+gl, gr-gl, psibar, psi)
end function tlr_ff

<Implementation of spinor currents>+=
pure function trl_ff (gr, gl, psibar, psi) result (t)
  type(tensor2odd) :: t
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  t = tva_ff (gr+gl, gr-gl, psibar, psi)
end function trl_ff

<Implementation of spinor currents>+=
pure function tvam_ff (gv, ga, psibar, psi, p) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gv, ga
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  type(momentum), intent(in) :: p
  j = (tva_ff(gv, ga, psibar, psi) * p) * (0,1)
end function tvam_ff

<Implementation of spinor currents>+=
pure function tlrm_ff (gl, gr, psibar, psi, p) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  type(momentum), intent(in) :: p
  j = tvam_ff (gr+gl, gr-gl, psibar, psi, p)
end function tlrm_ff

<Implementation of spinor currents>+=
pure function trlm_ff (gr, gl, psibar, psi, p) result (j)
  type(vector) :: j

```

```

complex(kind=default), intent(in) :: gl, gr
type(conjspinor), intent(in) :: psibar
type(spinor), intent(in) :: psi
type(momentum), intent(in) :: p
j = tvam_ff (gr+gl, gr-gl, psibar, psi, p)
end function trlm_ff

```

Special cases that avoid some multiplications

(Implementation of spinor currents)+≡

```

pure function v_ff (gv, psibar, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gv
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  complex(kind=default) :: g13, g14, g23, g24, g31, g32, g41, g42
  g13 = psibar%a(1)*psi%a(3)
  g14 = psibar%a(1)*psi%a(4)
  g23 = psibar%a(2)*psi%a(3)
  g24 = psibar%a(2)*psi%a(4)
  g31 = psibar%a(3)*psi%a(1)
  g32 = psibar%a(3)*psi%a(2)
  g41 = psibar%a(4)*psi%a(1)
  g42 = psibar%a(4)*psi%a(2)
  j%t = gv * ( g13 + g24 + g31 + g42)
  j%x(1) = gv * ( g14 + g23 - g32 - g41)
  j%x(2) = gv * ( - g14 + g23 + g32 - g41) * (0, 1)
  j%x(3) = gv * ( g13 - g24 - g31 + g42)
end function v_ff

```

(Implementation of spinor currents)+≡

```

pure function a_ff (ga, psibar, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: ga
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  complex(kind=default) :: g13, g14, g23, g24, g31, g32, g41, g42
  g13 = psibar%a(1)*psi%a(3)
  g14 = psibar%a(1)*psi%a(4)
  g23 = psibar%a(2)*psi%a(3)
  g24 = psibar%a(2)*psi%a(4)
  g31 = psibar%a(3)*psi%a(1)
  g32 = psibar%a(3)*psi%a(2)
  g41 = psibar%a(4)*psi%a(1)
  g42 = psibar%a(4)*psi%a(2)
  j%t = ga * ( - g13 - g24 + g31 + g42)
  j%x(1) = - ga * ( g14 + g23 + g32 + g41)
  j%x(2) = ga * ( g14 - g23 + g32 - g41) * (0, 1)
  j%x(3) = ga * ( - g13 + g24 - g31 + g42)
end function a_ff

```

(Implementation of spinor currents)+≡

```

pure function vl_ff (gl, psibar, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gl
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi

```

```

complex(kind=default) :: gl2
complex(kind=default) :: g31, g32, g41, g42
gl2 = 2 * gl
g31 = psibar%a(3)*psi%a(1)
g32 = psibar%a(3)*psi%a(2)
g41 = psibar%a(4)*psi%a(1)
g42 = psibar%a(4)*psi%a(2)
j%t    = gl2 * ( g31 + g42)
j%x(1) = - gl2 * ( g32 + g41)
j%x(2) = gl2 * ( g32 - g41) * (0, 1)
j%x(3) = gl2 * ( - g31 + g42)
end function vl_ff

<Implementation of spinor currents>+=
pure function vr_ff (gr, psibar, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gr
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  complex(kind=default) :: gr2
  complex(kind=default) :: g13, g14, g23, g24
  gr2 = 2 * gr
  g13 = psibar%a(1)*psi%a(3)
  g14 = psibar%a(1)*psi%a(4)
  g23 = psibar%a(2)*psi%a(3)
  g24 = psibar%a(2)*psi%a(4)
  j%t    = gr2 * ( g13 + g24)
  j%x(1) = gr2 * ( g14 + g23)
  j%x(2) = gr2 * ( - g14 + g23) * (0, 1)
  j%x(3) = gr2 * ( g13 - g24)
end function vr_ff

<Implementation of spinor currents>+=
pure function grav_ff (g, m, kb, k, psibar, psi) result (j)
  type(tensor) :: j
  complex(kind=default), intent(in) :: g
  real(kind=default), intent(in) :: m
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  type(momentum), intent(in) :: kb, k
  complex(kind=default) :: g2, g8, c_dum
  type(vector) :: v_dum
  type(tensor) :: t_metric
  t_metric%t = 0
  t_metric%t(0,0) = 1.0_default
  t_metric%t(1,1) = - 1.0_default
  t_metric%t(2,2) = - 1.0_default
  t_metric%t(3,3) = - 1.0_default
  g2 = g/2.0_default
  g8 = g/8.0_default
  v_dum = v_ff(g8, psibar, psi)
  c_dum = (- m) * s_ff (g2, psibar, psi) - (kb+k)*v_dum
  j = c_dum*t_metric - (((kb+k).tprod.v_dum) + &
    (v_dum.tprod.(kb+k)))
end function grav_ff

```

$$g_L \gamma_\mu (1 - \gamma_5) + g_R \gamma_\mu (1 + \gamma_5) = (g_L + g_R) \gamma_\mu - (g_L - g_R) \gamma_\mu \gamma_5 = g_V \gamma_\mu - g_A \gamma_\mu \gamma_5 \quad (\text{X.51})$$

... give the compiler the benefit of the doubt that it will optimize the function all. If not, we could inline it ...

```

<Implementation of spinor currents>+=
pure function vlr_ff (gl, gr, psibar, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  j = va_ff (gl+gr, gl-gr, psibar, psi)
end function vlr_ff

```

and

$$\not{v} - \not{a} \gamma_5 = \begin{pmatrix} 0 & 0 & v_- - a_- & -v^* + a^* \\ 0 & 0 & -v + a & v_+ - a_+ \\ v_+ + a_+ & v^* + a^* & 0 & 0 \\ v + a & v_- + a_- & 0 & 0 \end{pmatrix} \quad (\text{X.52})$$

with $v_\pm = v_0 \pm v_3$, $a_\pm = a_0 \pm a_3$, $v = v_1 + iv_2$, $v^* = v_1 - iv_2$, $a = a_1 + ia_2$, and $a^* = a_1 - ia_2$. But note that $*$ is *not* complex conjugation for complex v_μ or a_μ .

```

<Declaration of spinor currents>+=
public :: f_vaf, f_vf, f_af, f_vlf, f_vrf, f_vlrf, f_va2f, &
         f_tvaf, f_tlr, f_trlf, f_tvamf, f_tlrnf, f_trlmf

```

```

<Implementation of spinor currents>+=
pure function f_vaf (gv, ga, v, psi) result (vpsi)
  type(spinor) :: vpsi
  complex(kind=default), intent(in) :: gv, ga
  type(vector), intent(in) :: v
  type(spinor), intent(in) :: psi
  complex(kind=default) :: gl, gr
  complex(kind=default) :: vp, vm, v12, v12s
  gl = gv + ga
  gr = gv - ga
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = gr * ( vm * psi%a(3) - v12s * psi%a(4))
  vpsi%a(2) = gr * ( - v12 * psi%a(3) + vp * psi%a(4))
  vpsi%a(3) = gl * ( vp * psi%a(1) + v12s * psi%a(2))
  vpsi%a(4) = gl * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_vaf

```

```

<Implementation of spinor currents>+=
pure function f_va2f (gva, v, psi) result (vpsi)
  type(spinor) :: vpsi
  complex(kind=default), intent(in), dimension(2) :: gva
  type(vector), intent(in) :: v
  type(spinor), intent(in) :: psi

```

```

complex(kind=default) :: gl, gr
complex(kind=default) :: vp, vm, v12, v12s
gl = gva(1) + gva(2)
gr = gva(1) - gva(2)
vp = v%t + v%x(3)
vm = v%t - v%x(3)
v12 = v%x(1) + (0,1)*v%x(2)
v12s = v%x(1) - (0,1)*v%x(2)
vpsi%a(1) = gr * ( vm * psi%a(3) - v12s * psi%a(4))
vpsi%a(2) = gr * ( - v12 * psi%a(3) + vp * psi%a(4))
vpsi%a(3) = gl * ( vp * psi%a(1) + v12s * psi%a(2))
vpsi%a(4) = gl * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_va2f

<Implementation of spinor currents>+=
pure function f_tvaf (gv, ga, t, psi) result (tpsi)
  type(spinor) :: tpsi
  complex(kind=default), intent(in) :: gv, ga
  type(tensor2odd), intent(in) :: t
  type(spinor), intent(in) :: psi
  complex(kind=default) :: gl, gr
  complex(kind=default) :: e21, e21s, b12, b12s, be3, be3s
  gr = gv + ga
  gl = gv - ga
  e21 = t%e(2) + t%e(1)*(0,1)
  e21s = t%e(2) - t%e(1)*(0,1)
  b12 = t%b(1) + t%b(2)*(0,1)
  b12s = t%b(1) - t%b(2)*(0,1)
  be3 = t%b(3) + t%e(3)*(0,1)
  be3s = t%b(3) - t%e(3)*(0,1)
  tpsi%a(1) = 2*gl * ( psi%a(1) * be3 + psi%a(2) * ( e21 +b12s))
  tpsi%a(2) = 2*gl * ( - psi%a(2) * be3 + psi%a(1) * (-e21s+b12 ))
  tpsi%a(3) = 2*gr * ( psi%a(3) * be3s + psi%a(4) * (-e21 +b12s))
  tpsi%a(4) = 2*gr * ( - psi%a(4) * be3s + psi%a(3) * ( e21s+b12 ))
end function f_tvaf

<Implementation of spinor currents>+=
pure function f_tlrif (gl, gr, t, psi) result (tpsi)
  type(spinor) :: tpsi
  complex(kind=default), intent(in) :: gl, gr
  type(tensor2odd), intent(in) :: t
  type(spinor), intent(in) :: psi
  tpsi = f_tvaf (gr+gl, gr-gl, t, psi)
end function f_tlrif

<Implementation of spinor currents>+=
pure function f_trlif (gr, gl, t, psi) result (tpsi)
  type(spinor) :: tpsi
  complex(kind=default), intent(in) :: gl, gr
  type(tensor2odd), intent(in) :: t
  type(spinor), intent(in) :: psi
  tpsi = f_tvaf (gr+gl, gr-gl, t, psi)
end function f_trlif

<Implementation of spinor currents>+=
pure function f_tvamf (gv, ga, v, psi, k) result (vpsi)

```

```

    type(spinor) :: vpsi
    complex(kind=default), intent(in) :: gv, ga
    type(vector), intent(in) :: v
    type(spinor), intent(in) :: psi
    type(momentum), intent(in) :: k
    type(tensor2odd) :: t
    t = (v.wedge.k) * (0, 0.5)
    vpsi = f_tvaf(gv, ga, t, psi)
end function f_tvamf

<Implementation of spinor currents>+≡
pure function f_tlrnf (gl, gr, v, psi, k) result (vpsi)
    type(spinor) :: vpsi
    complex(kind=default), intent(in) :: gl, gr
    type(vector), intent(in) :: v
    type(spinor), intent(in) :: psi
    type(momentum), intent(in) :: k
    vpsi = f_tvamf (gr+gl, gr-gl, v, psi, k)
end function f_tlrnf

<Implementation of spinor currents>+≡
pure function f_trlmf (gr, gl, v, psi, k) result (vpsi)
    type(spinor) :: vpsi
    complex(kind=default), intent(in) :: gl, gr
    type(vector), intent(in) :: v
    type(spinor), intent(in) :: psi
    type(momentum), intent(in) :: k
    vpsi = f_tvamf (gr+gl, gr-gl, v, psi, k)
end function f_trlmf

<Implementation of spinor currents>+≡
pure function f_vf (gv, v, psi) result (vpsi)
    type(spinor) :: vpsi
    complex(kind=default), intent(in) :: gv
    type(vector), intent(in) :: v
    type(spinor), intent(in) :: psi
    complex(kind=default) :: vp, vm, v12, v12s
    vp = v%t + v%x(3)
    vm = v%t - v%x(3)
    v12 = v%x(1) + (0,1)*v%x(2)
    v12s = v%x(1) - (0,1)*v%x(2)
    vpsi%a(1) = gv * ( vm * psi%a(3) - v12s * psi%a(4))
    vpsi%a(2) = gv * ( - v12 * psi%a(3) + vp * psi%a(4))
    vpsi%a(3) = gv * ( vp * psi%a(1) + v12s * psi%a(2))
    vpsi%a(4) = gv * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_vf

<Implementation of spinor currents>+≡
pure function f_af (ga, v, psi) result (vpsi)
    type(spinor) :: vpsi
    complex(kind=default), intent(in) :: ga
    type(vector), intent(in) :: v
    type(spinor), intent(in) :: psi
    complex(kind=default) :: vp, vm, v12, v12s
    vp = v%t + v%x(3)
    vm = v%t - v%x(3)

```

```

v12 = v%x(1) + (0,1)*v%x(2)
v12s = v%x(1) - (0,1)*v%x(2)
vpsi%a(1) = ga * ( - vm * psi%a(3) + v12s * psi%a(4))
vpsi%a(2) = ga * ( v12 * psi%a(3) - vp * psi%a(4))
vpsi%a(3) = ga * ( vp * psi%a(1) + v12s * psi%a(2))
vpsi%a(4) = ga * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_af

```

(Implementation of spinor currents)+≡

```

pure function f_vlf (gl, v, psi) result (vpsi)
  type(spinor) :: vpsi
  complex(kind=default), intent(in) :: gl
  type(vector), intent(in) :: v
  type(spinor), intent(in) :: psi
  complex(kind=default) :: gl2
  complex(kind=default) :: vp, vm, v12, v12s
  gl2 = 2 * gl
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = 0
  vpsi%a(2) = 0
  vpsi%a(3) = gl2 * ( vp * psi%a(1) + v12s * psi%a(2))
  vpsi%a(4) = gl2 * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_vlf

```

(Implementation of spinor currents)+≡

```

pure function f_vrf (gr, v, psi) result (vpsi)
  type(spinor) :: vpsi
  complex(kind=default), intent(in) :: gr
  type(vector), intent(in) :: v
  type(spinor), intent(in) :: psi
  complex(kind=default) :: gr2
  complex(kind=default) :: vp, vm, v12, v12s
  gr2 = 2 * gr
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = gr2 * ( vm * psi%a(3) - v12s * psi%a(4))
  vpsi%a(2) = gr2 * ( - v12 * psi%a(3) + vp * psi%a(4))
  vpsi%a(3) = 0
  vpsi%a(4) = 0
end function f_vrf

```

(Implementation of spinor currents)+≡

```

pure function f_vlrf (gl, gr, v, psi) result (vpsi)
  type(spinor) :: vpsi
  complex(kind=default), intent(in) :: gl, gr
  type(vector), intent(in) :: v
  type(spinor), intent(in) :: psi
  vpsi = f_vaf (gl+gr, gl-gr, v, psi)
end function f_vlrf

```

(Declaration of spinor currents)+≡

```

public :: f_fva, f_fv, f_fa, f_fvl, f_fvr, f_fvlr, f_fva2, &
        f_ftva, f_ftlr, f_ftrl, f_ftvam, f_ftlrm, f_ftrlm

<Implementation of spinor currents>+≡
pure function f_fva (gv, ga, psibar, v) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: gv, ga
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  complex(kind=default) :: gl, gr
  complex(kind=default) :: vp, vm, v12, v12s
  gl = gv + ga
  gr = gv - ga
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  psibarv%a(1) = gl * ( psibar%a(3) * vp + psibar%a(4) * v12 )
  psibarv%a(2) = gl * ( psibar%a(3) * v12s + psibar%a(4) * vm )
  psibarv%a(3) = gr * ( psibar%a(1) * vm - psibar%a(2) * v12 )
  psibarv%a(4) = gr * ( - psibar%a(1) * v12s + psibar%a(2) * vp )
end function f_fva

<Implementation of spinor currents>+≡
pure function f_fva2 (gva, psibar, v) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in), dimension(2) :: gva
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  complex(kind=default) :: gl, gr
  complex(kind=default) :: vp, vm, v12, v12s
  gl = gva(1) + gva(2)
  gr = gva(1) - gva(2)
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  psibarv%a(1) = gl * ( psibar%a(3) * vp + psibar%a(4) * v12 )
  psibarv%a(2) = gl * ( psibar%a(3) * v12s + psibar%a(4) * vm )
  psibarv%a(3) = gr * ( psibar%a(1) * vm - psibar%a(2) * v12 )
  psibarv%a(4) = gr * ( - psibar%a(1) * v12s + psibar%a(2) * vp )
end function f_fva2

<Implementation of spinor currents>+≡
pure function f_ftva (gv, ga, psibar, t) result (psibart)
  type(conjspinor) :: psibart
  complex(kind=default), intent(in) :: gv, ga
  type(conjspinor), intent(in) :: psibar
  type(tensor2odd), intent(in) :: t
  complex(kind=default) :: gl, gr
  complex(kind=default) :: e21, e21s, b12, b12s, be3, be3s
  gr = gv + ga
  gl = gv - ga
  e21 = t%e(2) + t%e(1)*(0,1)
  e21s = t%e(2) - t%e(1)*(0,1)
  b12 = t%b(1) + t%b(2)*(0,1)

```



```

b12s = t%b(1) - t%b(2)*(0,1)
be3  = t%b(3) + t%e(3)*(0,1)
be3s = t%b(3) - t%e(3)*(0,1)
psibart%a(1) = 2*gl * ( psibar%a(1) * be3  + psibar%a(2) * (-e21s+b12 ))
psibart%a(2) = 2*gl * ( - psibar%a(2) * be3  + psibar%a(1) * ( e21 +b12s))
psibart%a(3) = 2*gr * ( psibar%a(3) * be3s + psibar%a(4) * ( e21s+b12 ))
psibart%a(4) = 2*gr * ( - psibar%a(4) * be3s + psibar%a(3) * (-e21 +b12s))
end function f_ftva

<Implementation of spinor currents>+≡
pure function f_ftlr (gl, gr, psibar, t) result (psibart)
  type(conjspinor) :: psibart
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(tensor2odd), intent(in) :: t
  psibart = f_ftva (gr+gl, gr-gl, psibar, t)
end function f_ftlr

<Implementation of spinor currents>+≡
pure function f_ftrl (gr, gl, psibar, t) result (psibart)
  type(conjspinor) :: psibart
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(tensor2odd), intent(in) :: t
  psibart = f_ftva (gr+gl, gr-gl, psibar, t)
end function f_ftrl

<Implementation of spinor currents>+≡
pure function f_ftvam (gv, ga, psibar, v, k) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: gv, ga
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  type(momentum), intent(in) :: k
  type(tensor2odd) :: t
  t = (v.wedge.k) * (0, 0.5)
  psibarv = f_ftva(gv, ga, psibar, t)
end function f_ftvam

<Implementation of spinor currents>+≡
pure function f_ftlrm (gl, gr, psibar, v, k) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  type(momentum), intent(in) :: k
  psibarv = f_ftvam (gr+gl, gr-gl, psibar, v, k)
end function f_ftlrm

<Implementation of spinor currents>+≡
pure function f_ftrlm (gr, gl, psibar, v, k) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  type(momentum), intent(in) :: k
  psibarv = f_ftvam (gr+gl, gr-gl, psibar, v, k)

```

```
end function f_ftrlm
```

(Implementation of spinor currents)+≡

```
pure function f_fv (gv, psibar, v) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: gv
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  complex(kind=default) :: vp, vm, v12, v12s
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  psibarv%a(1) = gv * ( psibar%a(3) * vp + psibar%a(4) * v12)
  psibarv%a(2) = gv * ( psibar%a(3) * v12s + psibar%a(4) * vm )
  psibarv%a(3) = gv * ( psibar%a(1) * vm - psibar%a(2) * v12)
  psibarv%a(4) = gv * ( - psibar%a(1) * v12s + psibar%a(2) * vp )
end function f_fv
```

(Implementation of spinor currents)+≡

```
pure function f_fa (ga, psibar, v) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: ga
  type(vector), intent(in) :: v
  type(conjspinor), intent(in) :: psibar
  complex(kind=default) :: vp, vm, v12, v12s
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  psibarv%a(1) = ga * ( psibar%a(3) * vp + psibar%a(4) * v12)
  psibarv%a(2) = ga * ( psibar%a(3) * v12s + psibar%a(4) * vm )
  psibarv%a(3) = ga * ( - psibar%a(1) * vm + psibar%a(2) * v12)
  psibarv%a(4) = ga * ( psibar%a(1) * v12s - psibar%a(2) * vp )
end function f_fa
```

(Implementation of spinor currents)+≡

```
pure function f_fvl (gl, psibar, v) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: gl
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  complex(kind=default) :: gl2
  complex(kind=default) :: vp, vm, v12, v12s
  gl2 = 2 * gl
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  psibarv%a(1) = gl2 * ( psibar%a(3) * vp + psibar%a(4) * v12)
  psibarv%a(2) = gl2 * ( psibar%a(3) * v12s + psibar%a(4) * vm )
  psibarv%a(3) = 0
  psibarv%a(4) = 0
end function f_fvl
```

(Implementation of spinor currents)+≡

```

pure function f_fvr (gr, psibar, v) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: gr
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  complex(kind=default) :: gr2
  complex(kind=default) :: vp, vm, v12, v12s
  gr2 = 2 * gr
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  psibarv%a(1) = 0
  psibarv%a(2) = 0
  psibarv%a(3) = gr2 * ( psibar%a(1) * vm - psibar%a(2) * v12)
  psibarv%a(4) = gr2 * ( - psibar%a(1) * v12s + psibar%a(2) * vp )
end function f_fvr

```

(Implementation of spinor currents)+≡

```

pure function f_fvlr (gl, gr, psibar, v) result (psibarv)
  type(conjspinor) :: psibarv
  complex(kind=default), intent(in) :: gl, gr
  type(conjspinor), intent(in) :: psibar
  type(vector), intent(in) :: v
  psibarv = f_fva (gl+gr, gl-gr, psibar, v)
end function f_fvlr

```

X.13.2 Fermionic Scalar and Pseudo Scalar Couplings

(Declaration of spinor currents)+≡

```

public :: sp_ff, s_ff, p_ff, sl_ff, sr_ff, slr_ff

```

(Implementation of spinor currents)+≡

```

pure function sp_ff (gs, gp, psibar, psi) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gs, gp
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  j = (gs - gp) * (psibar%a(1)*psi%a(1) + psibar%a(2)*psi%a(2)) &
      + (gs + gp) * (psibar%a(3)*psi%a(3) + psibar%a(4)*psi%a(4))
end function sp_ff

```

(Implementation of spinor currents)+≡

```

pure function s_ff (gs, psibar, psi) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gs
  type(conjspinor), intent(in) :: psibar
  type(spinor), intent(in) :: psi
  j = gs * (psibar * psi)
end function s_ff

```

(Implementation of spinor currents)+≡

```

pure function p_ff (gp, psibar, psi) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gp
  type(conjspinor), intent(in) :: psibar

```

```

    type(spinor), intent(in) :: psi
    j = gp * ( psibar%a(3)*psi%a(3) + psibar%a(4)*psi%a(4) &
              - psibar%a(1)*psi%a(1) - psibar%a(2)*psi%a(2))
end function p_ff

<Implementation of spinor currents>+=
pure function sl_ff (gl, psibar, psi) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: gl
    type(conjspinor), intent(in) :: psibar
    type(spinor), intent(in) :: psi
    j = 2 * gl * (psibar%a(1)*psi%a(1) + psibar%a(2)*psi%a(2))
end function sl_ff

<Implementation of spinor currents>+=
pure function sr_ff (gr, psibar, psi) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: gr
    type(conjspinor), intent(in) :: psibar
    type(spinor), intent(in) :: psi
    j = 2 * gr * (psibar%a(3)*psi%a(3) + psibar%a(4)*psi%a(4))
end function sr_ff


$$g_L(1 - \gamma_5) + g_R(1 + \gamma_5) = (g_R + g_L) + (g_R - g_L)\gamma_5 = g_S + g_P\gamma_5 \quad (X.53)$$


<Implementation of spinor currents>+=
pure function slr_ff (gl, gr, psibar, psi) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: gl, gr
    type(conjspinor), intent(in) :: psibar
    type(spinor), intent(in) :: psi
    j = sp_ff (gr+gl, gr-gl, psibar, psi)
end function slr_ff

<Declaration of spinor currents>+=
public :: f_spf, f_sf, f_pf, f_slf, f_srf, f_slrf

<Implementation of spinor currents>+=
pure function f_spf (gs, gp, phi, psi) result (phipsi)
    type(spinor) :: phipsi
    complex(kind=default), intent(in) :: gs, gp
    complex(kind=default), intent(in) :: phi
    type(spinor), intent(in) :: psi
    phipsi%a(1:2) = ((gs - gp) * phi) * psi%a(1:2)
    phipsi%a(3:4) = ((gs + gp) * phi) * psi%a(3:4)
end function f_spf

<Implementation of spinor currents>+=
pure function f_sf (gs, phi, psi) result (phipsi)
    type(spinor) :: phipsi
    complex(kind=default), intent(in) :: gs
    complex(kind=default), intent(in) :: phi
    type(spinor), intent(in) :: psi
    phipsi%a = (gs * phi) * psi%a
end function f_sf

```

```

<Implementation of spinor currents>+≡
pure function f_pf (gp, phi, psi) result (phipsi)
  type(spinor) :: phipsi
  complex(kind=default), intent(in) :: gp
  complex(kind=default), intent(in) :: phi
  type(spinor), intent(in) :: psi
  phipsi%a(1:2) = (- gp * phi) * psi%a(1:2)
  phipsi%a(3:4) = ( gp * phi) * psi%a(3:4)
end function f_pf

<Implementation of spinor currents>+≡
pure function f_slf (gl, phi, psi) result (phipsi)
  type(spinor) :: phipsi
  complex(kind=default), intent(in) :: gl
  complex(kind=default), intent(in) :: phi
  type(spinor), intent(in) :: psi
  phipsi%a(1:2) = (2 * gl * phi) * psi%a(1:2)
  phipsi%a(3:4) = 0
end function f_slf

<Implementation of spinor currents>+≡
pure function f_srf (gr, phi, psi) result (phipsi)
  type(spinor) :: phipsi
  complex(kind=default), intent(in) :: gr
  complex(kind=default), intent(in) :: phi
  type(spinor), intent(in) :: psi
  phipsi%a(1:2) = 0
  phipsi%a(3:4) = (2 * gr * phi) * psi%a(3:4)
end function f_srf

<Implementation of spinor currents>+≡
pure function f_slrf (gl, gr, phi, psi) result (phipsi)
  type(spinor) :: phipsi
  complex(kind=default), intent(in) :: gl, gr
  complex(kind=default), intent(in) :: phi
  type(spinor), intent(in) :: psi
  phipsi = f_spf (gr+gl, gr-gl, phi, psi)
end function f_slrf

<Declaration of spinor currents>+≡
public :: f_fsp, f_fs, f_fp, f_fsl, f_fsr, f_fslr

<Implementation of spinor currents>+≡
pure function f_fsp (gs, gp, psibar, phi) result (psibarphi)
  type(conjspinor) :: psibarphi
  complex(kind=default), intent(in) :: gs, gp
  type(conjspinor), intent(in) :: psibar
  complex(kind=default), intent(in) :: phi
  psibarphi%a(1:2) = ((gs - gp) * phi) * psibar%a(1:2)
  psibarphi%a(3:4) = ((gs + gp) * phi) * psibar%a(3:4)
end function f_fsp

<Implementation of spinor currents>+≡
pure function f_fs (gs, psibar, phi) result (psibarphi)
  type(conjspinor) :: psibarphi
  complex(kind=default), intent(in) :: gs
  type(conjspinor), intent(in) :: psibar

```

```

        complex(kind=default), intent(in) :: phi
        psibarphi%a = (gs * phi) * psibar%a
    end function f_fs

<Implementation of spinor currents>+≡
    pure function f_fp (gp, psibar, phi) result (psibarphi)
        type(conjspinor) :: psibarphi
        complex(kind=default), intent(in) :: gp
        type(conjspinor), intent(in) :: psibar
        complex(kind=default), intent(in) :: phi
        psibarphi%a(1:2) = (- gp * phi) * psibar%a(1:2)
        psibarphi%a(3:4) = ( gp * phi) * psibar%a(3:4)
    end function f_fp

<Implementation of spinor currents>+≡
    pure function f_fsl (gl, psibar, phi) result (psibarphi)
        type(conjspinor) :: psibarphi
        complex(kind=default), intent(in) :: gl
        type(conjspinor), intent(in) :: psibar
        complex(kind=default), intent(in) :: phi
        psibarphi%a(1:2) = (2 * gl * phi) * psibar%a(1:2)
        psibarphi%a(3:4) = 0
    end function f_fsl

<Implementation of spinor currents>+≡
    pure function f_fsr (gr, psibar, phi) result (psibarphi)
        type(conjspinor) :: psibarphi
        complex(kind=default), intent(in) :: gr
        type(conjspinor), intent(in) :: psibar
        complex(kind=default), intent(in) :: phi
        psibarphi%a(1:2) = 0
        psibarphi%a(3:4) = (2 * gr * phi) * psibar%a(3:4)
    end function f_fsr

<Implementation of spinor currents>+≡
    pure function f_fslr (gl, gr, psibar, phi) result (psibarphi)
        type(conjspinor) :: psibarphi
        complex(kind=default), intent(in) :: gl, gr
        type(conjspinor), intent(in) :: psibar
        complex(kind=default), intent(in) :: phi
        psibarphi = f_fsp (gr+gl, gr-gl, psibar, phi)
    end function f_fslr

<Declaration of spinor currents>+≡
    public :: f_gravf, f_fgrav

<Implementation of spinor currents>+≡
    pure function f_gravf (g, m, kb, k, t, psi) result (tpsi)
        type(spinor) :: tpsi
        complex(kind=default), intent(in) :: g
        real(kind=default), intent(in) :: m
        type(spinor), intent(in) :: psi
        type(tensor), intent(in) :: t
        type(momentum), intent(in) :: kb, k
        complex(kind=default) :: g2, g8, t_tr
        type(vector) :: kkb
        kkb = k + kb

```

```

g2 = g / 2.0_default
g8 = g / 8.0_default
t_tr = t%t(0,0) - t%t(1,1) - t%t(2,2) - t%t(3,3)
tpsi = (- f_sf (g2, cmplx (m,0.0, kind=default), psi) &
        - f_vf ((g8*m), kkb, psi)) * t_tr - &
        f_vf (g8,(t*kkb + kkb*t),psi)
end function f_gravf

<Implementation of spinor currents>+=
pure function f_fgrav (g, m, kb, k, psibar, t) result (psibart)
  type(conjspinor) :: psibart
  complex(kind=default), intent(in) :: g
  real(kind=default), intent(in) :: m
  type(conjspinor), intent(in) :: psibar
  type(tensor), intent(in) :: t
  type(momentum), intent(in) :: kb, k
  type(vector) :: kkb
  complex(kind=default) :: g2, g8, t_tr
  kkb = k + kb
  g2 = g / 2.0_default
  g8 = g / 8.0_default
  t_tr = t%t(0,0) - t%t(1,1) - t%t(2,2) - t%t(3,3)
  psibart = (- f_fs (g2, psibar, cmplx (m, 0.0, kind=default)) &
            - f_fv ((g8 * m), psibar, kkb)) * t_tr - &
            f_fv (g8,psibar,(t*kkb + kkb*t))
end function f_fgrav

```

X.13.3 On Shell Wave Functions

```

<Declaration of spinor on shell wave functions>=
public :: u, ubar, v, vbar
private :: chi_plus, chi_minus

```

$$\chi_+(\vec{p}) = \frac{1}{\sqrt{2|\vec{p}|(|\vec{p}| + p_3)}} \begin{pmatrix} |\vec{p}| + p_3 \\ p_1 + ip_2 \end{pmatrix} \quad (\text{X.54a})$$

$$\chi_-(\vec{p}) = \frac{1}{\sqrt{2|\vec{p}|(|\vec{p}| + p_3)}} \begin{pmatrix} -p_1 + ip_2 \\ |\vec{p}| + p_3 \end{pmatrix} \quad (\text{X.54b})$$

```

<Implementation of spinor on shell wave functions>=
pure function chi_plus (p) result (chi)
  complex(kind=default), dimension(2) :: chi
  type(momentum), intent(in) :: p
  real(kind=default) :: pabs
  pabs = sqrt (dot_product (p%x, p%x))
  if (pabs + p%x(3) <= 1000 * epsilon (pabs) * pabs) then
    chi = (/ cmplx ( 0.0, 0.0, kind=default), &
           cmplx ( 1.0, 0.0, kind=default) /)
  else
    chi = 1 / sqrt (2*pabs*(pabs + p%x(3))) &
          * (/ cmplx (pabs + p%x(3), kind=default), &
             cmplx (p%x(1), p%x(2), kind=default) /)
  end if
end function chi_plus

```

```

<Implementation of spinor on shell wave functions>+≡
pure function chi_minus (p) result (chi)
  complex(kind=default), dimension(2) :: chi
  type(momentum), intent(in) :: p
  real(kind=default) :: pabs
  pabs = sqrt (dot_product (p%x, p%x))
  if (pabs + p%x(3) <= 1000 * epsilon (pabs) * pabs) then
    chi = (/ cmplx (-1.0, 0.0, kind=default), &
           cmplx ( 0.0, 0.0, kind=default) /)
  else
    chi = 1 / sqrt (2*pabs*(pabs + p%x(3))) &
          * (/ cmplx (-p%x(1), p%x(2), kind=default), &
             cmplx (pabs + p%x(3), kind=default) /)
  end if
end function chi_minus

```

$$u_{\pm}(p, |m|) = \begin{pmatrix} \sqrt{p_0 \mp |\vec{p}|} \cdot \chi_{\pm}(\vec{p}) \\ \sqrt{p_0 \pm |\vec{p}|} \cdot \chi_{\pm}(\vec{p}) \end{pmatrix} \quad u_{\pm}(p, -|m|) = \begin{pmatrix} -i\sqrt{p_0 \mp |\vec{p}|} \cdot \chi_{\pm}(\vec{p}) \\ +i\sqrt{p_0 \pm |\vec{p}|} \cdot \chi_{\pm}(\vec{p}) \end{pmatrix} \quad (\text{X.55})$$

Determining the mass from the momenta is a numerically haphazardous for light particles. Therefore, we accept some redundancy and pass the mass explicitly. Even if the mass is not used in the chiral representation, we do so for symmetry with polarization vectors and to be prepared for other representations.

```

<Implementation of spinor on shell wave functions>+≡
pure function u (mass, p, s) result (psi)
  type(spinor) :: psi
  real(kind=default), intent(in) :: mass
  type(momentum), intent(in) :: p
  integer, intent(in) :: s
  complex(kind=default), dimension(2) :: chi
  real(kind=default) :: pabs, delta, m
  m = abs(mass)
  pabs = sqrt (dot_product (p%x, p%x))
  if (m < epsilon (m) * pabs) then
    delta = 0
  else
    delta = sqrt (max (p%t - pabs, 0._default))
  end if
  select case (s)
  case (1)
    chi = chi_plus (p)
    psi%a(1:2) = delta * chi
    psi%a(3:4) = sqrt (p%t + pabs) * chi
  case (-1)
    chi = chi_minus (p)
    psi%a(1:2) = sqrt (p%t + pabs) * chi
    psi%a(3:4) = delta * chi
  case default
    pabs = m ! make the compiler happy and use m
    psi%a = 0
  end select
  if (mass < 0) then

```



```

        psi%a(1:2) = - imago * psi%a(1:2)
        psi%a(3:4) = + imago * psi%a(3:4)
    end if
end function u

```

(Implementation of spinor on shell wave functions)+≡

```

pure function ubar (m, p, s) result (psibar)
    type(conjspinor) :: psibar
    real(kind=default), intent(in) :: m
    type(momentum), intent(in) :: p
    integer, intent(in) :: s
    type(spinor) :: psi
    psi = u (m, p, s)
    psibar%a(1:2) = conjg (psi%a(3:4))
    psibar%a(3:4) = conjg (psi%a(1:2))
end function ubar

```

$$v_{\pm}(p) = \begin{pmatrix} \mp \sqrt{p_0 \pm |\vec{p}|} \cdot \chi_{\mp}(\vec{p}) \\ \pm \sqrt{p_0 \mp |\vec{p}|} \cdot \chi_{\mp}(\vec{p}) \end{pmatrix} \quad (\text{X.56})$$

(Implementation of spinor on shell wave functions)+≡

```

pure function v (mass, p, s) result (psi)
    type(spinor) :: psi
    real(kind=default), intent(in) :: mass
    type(momentum), intent(in) :: p
    integer, intent(in) :: s
    complex(kind=default), dimension(2) :: chi
    real(kind=default) :: pabs, delta, m
    m = abs(mass)
    pabs = sqrt (dot_product (p%x, p%x))
    if (m < epsilon (m) * pabs) then
        delta = 0
    else
        delta = sqrt (max (p%t - pabs, 0._default))
    end if
    select case (s)
    case (1)
        chi = chi_minus (p)
        psi%a(1:2) = - sqrt (p%t + pabs) * chi
        psi%a(3:4) = delta * chi
    case (-1)
        chi = chi_plus (p)
        psi%a(1:2) = delta * chi
        psi%a(3:4) = - sqrt (p%t + pabs) * chi
    case default
        pabs = m ! make the compiler happy and use m
        psi%a = 0
    end select
    if (mass < 0) then
        psi%a(1:2) = - imago * psi%a(1:2)
        psi%a(3:4) = + imago * psi%a(3:4)
    end if
end function v

```

(Implementation of spinor on shell wave functions)+≡

```

pure function vbar (m, p, s) result (psibar)
  type(conjspinor) :: psibar
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: p
  integer, intent(in) :: s
  type(spinor) :: psi
  psi = v (m, p, s)
  psibar%a(1:2) = conjg (psi%a(3:4))
  psibar%a(3:4) = conjg (psi%a(1:2))
end function vbar

```

X.13.4 Off Shell Wave Functions

I've just taken this over from Christian Schwinn's version.

(Declaration of spinor off shell wave functions)≡

```
public :: brs_u, brs_ubar, brs_v, brs_vbar
```

The off-shell wave functions needed for gauge checking are obtained from the LSZ-formulas:

$$\langle \text{Out} | d^\dagger | \text{In} \rangle = i \int d^4x \bar{v} e^{-ikx} (i\rlap{\not{\partial}} - m) \langle \text{Out} | \psi | \text{In} \rangle \quad (\text{X.57a})$$

$$\langle \text{Out} | b | \text{In} \rangle = -i \int d^4x \bar{u} e^{ikx} (i\rlap{\not{\partial}} - m) \langle \text{Out} | \psi | \text{In} \rangle \quad (\text{X.57b})$$

$$\langle \text{Out} | d | \text{In} \rangle = i \int d^4x \langle \text{Out} | \bar{\psi} | \text{In} \rangle (-i\overleftarrow{\rlap{\not{\partial}}} - m) v e^{ikx} \quad (\text{X.57c})$$

$$\langle \text{Out} | b^\dagger | \text{In} \rangle = -i \int d^4x \langle \text{Out} | \bar{\psi} | \text{In} \rangle (-i\overleftarrow{\rlap{\not{\partial}}} - m) u e^{-ikx} \quad (\text{X.57d})$$

Since the relative sign between fermions and antifermions is ignored for on-shell amplitudes we must also ignore it here, so all wavefunctions must have a $(-i)$ factor. In momentum space we have:

$$brsu(p) = (-i)(\rlap{\not{p}} - m)u(p) \quad (\text{X.58})$$

(Implementation of spinor off shell wave functions)≡

```

pure function brs_u (m, p, s) result (dpsi)
  type(spinor) :: dpsi, psi
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: p
  integer, intent(in) :: s
  type (vector)::vp
  complex(kind=default), parameter :: one = (1, 0)
  vp=p
  psi=u(m,p,s)
  dpsi=cplx(0.0,-1.0)*(f_vf(one,vp,psi)-m*psi)
end function brs_u

```

$$brsv(p) = i(\rlap{\not{p}} + m)v(p) \quad (\text{X.59})$$

(Implementation of spinor off shell wave functions)+≡

```

pure function brs_v (m, p, s) result (dpsi)
  type(spinor) :: dpsi, psi

```

```

real(kind=default), intent(in) :: m
type(momentum), intent(in) :: p
integer, intent(in) :: s
type (vector)::vp
complex(kind=default), parameter :: one = (1, 0)
vp=p
psi=v(m,p,s)
dpsi=cmlpx(0.0,1.0)*(f_vf(one,vp,psi)+m*psi)
end function brs_v

```

$$brs\bar{u}(p) = (-i)\bar{u}(p)(\not{p} - m) \quad (X.60)$$

(Implementation of spinor off shell wave functions) +≡

```

pure function brs_ubar (m, p, s) result (dpsibar)
type(conjspinor) :: dpsibar, psibar
real(kind=default), intent(in) :: m
type(momentum), intent(in) :: p
integer, intent(in) :: s
type (vector)::vp
complex(kind=default), parameter :: one = (1, 0)
vp=p
psibar=ubar(m,p,s)
dpsibar=cmlpx(0.0,-1.0)*(f_fv(one,psibar,vp)-m*psibar)
end function brs_ubar

```

$$brs\bar{v}(p) = (i)\bar{v}(p)(\not{p} + m) \quad (X.61)$$

(Implementation of spinor off shell wave functions) +≡

```

pure function brs_vbar (m, p, s) result (dpsibar)
type(conjspinor) :: dpsibar, psibar
real(kind=default), intent(in) :: m
type(momentum), intent(in) :: p
integer, intent(in) :: s
type (vector)::vp
complex(kind=default), parameter :: one = (1, 0)
vp=p
psibar=vbar(m,p,s)
dpsibar=cmlpx(0.0,1.0)*(f_fv(one,psibar,vp)+m*psibar)
end function brs_vbar

```

NB: The remarks on momentum flow in the propagators don't apply here since the incoming momenta are flipped for the wave functions.

X.13.5 Propagators

NB: the common factor of i is extracted:

(Declaration of spinor propagators) ≡

```

public :: pr_psi, pr_psibar
public :: pj_psi, pj_psibar
public :: pg_psi, pg_psibar

```

$$\frac{i(-\not{p} + m)}{p^2 - m^2 + im\Gamma} \psi \quad (X.62)$$

NB: the sign of the momentum comes about because all momenta are treated as *outgoing* and the particle charge flow is therefore opposite to the momentum.

\langle Implementation of spinor propagators $\rangle \equiv$

```
pure function pr_psi (p, m, w, psi) result (ppsi)
  type(spinor) :: ppsi
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  type(spinor), intent(in) :: psi
  type(vector) :: vp
  complex(kind=default), parameter :: one = (1, 0)
  vp = p
  ppsi = (1 / cmplx (p*p - m**2, m*w, kind=default)) &
    * (- f_vf (one, vp, psi) + m * psi)
end function pr_psi
```

$$\sqrt{\frac{\pi}{M\Gamma}}(-\not{p} + m)\psi \quad (\text{X.63})$$

\langle Implementation of spinor propagators $\rangle + \equiv$

```
pure function pj_psi (p, m, w, psi) result (ppsi)
  type(spinor) :: ppsi
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  type(spinor), intent(in) :: psi
  type(vector) :: vp
  complex(kind=default), parameter :: one = (1, 0)
  vp = p
  ppsi = (0, -1) * sqrt (PI / m / w) * (- f_vf (one, vp, psi) + m * psi)
end function pj_psi
```

\langle Implementation of spinor propagators $\rangle + \equiv$

```
pure function pg_psi (p, m, w, psi) result (ppsi)
  type(spinor) :: ppsi
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  type(spinor), intent(in) :: psi
  type(vector) :: vp
  complex(kind=default), parameter :: one = (1, 0)
  vp = p
  ppsi = gauss(p*p, m, w) * (- f_vf (one, vp, psi) + m * psi)
end function pg_psi
```

$$\bar{\psi} \frac{i(\not{p} + m)}{p^2 - m^2 + im\Gamma} \quad (\text{X.64})$$

NB: the sign of the momentum comes about because all momenta are treated as *outgoing* and the antiparticle charge flow is therefore parallel to the momentum.

\langle Implementation of spinor propagators $\rangle + \equiv$

```
pure function pr_psi_bar (p, m, w, psi_bar) result (ppsi_bar)
  type(conjspinor) :: ppsi_bar
  type(momentum), intent(in) :: p
  real(kind=default), intent(in) :: m, w
  type(conjspinor), intent(in) :: psi_bar
  type(vector) :: vp
```

```

complex(kind=default), parameter :: one = (1, 0)
vp = p
ppsibar = (1 / cmplx (p*p - m**2, m*w, kind=default)) &
    * (f_fv (one, psibar, vp) + m * psibar)
end function pr_psibar

```

$$\sqrt{\frac{\pi}{M\Gamma}}\bar{\psi}(\not{p} + m) \quad (\text{X.65})$$

NB: the sign of the momentum comes about because all momenta are treated as *outgoing* and the antiparticle charge flow is therefore parallel to the momentum.

(Implementation of spinor propagators)+≡

```

pure function pj_psibar (p, m, w, psibar) result (ppsibar)
    type(conjspinor) :: ppsibar
    type(momentum), intent(in) :: p
    real(kind=default), intent(in) :: m, w
    type(conjspinor), intent(in) :: psibar
    type(vector) :: vp
    complex(kind=default), parameter :: one = (1, 0)
    vp = p
    ppsibar = (0, -1) * sqrt (PI / m / w) * (f_fv (one, psibar, vp) + m * psibar)
end function pj_psibar

```

(Implementation of spinor propagators)+≡

```

pure function pg_psibar (p, m, w, psibar) result (ppsibar)
    type(conjspinor) :: ppsibar
    type(momentum), intent(in) :: p
    real(kind=default), intent(in) :: m, w
    type(conjspinor), intent(in) :: psibar
    type(vector) :: vp
    complex(kind=default), parameter :: one = (1, 0)
    vp = p
    ppsibar = gauss (p*p, m, w) * (f_fv (one, psibar, vp) + m * psibar)
end function pg_psibar

```

$$\frac{i(-\not{p} + m)}{p^2 - m^2 + im\Gamma} \sum_n \psi_n \otimes \bar{\psi}_n \quad (\text{X.66})$$

NB: the temporary variables `psi(1:4)` are not nice, but the compilers should be able to optimize the unnecessary copies away. In any case, even if the copies are performed, they are (probably) negligible compared to the floating point multiplications anyway ...

(Not used yet) Declaration of operations for spinors≡

```

type, public :: spinordyad
    ! private (omgalib needs access, but DON'T TOUCH IT!)
    complex(kind=default), dimension(4,4) :: a
end type spinordyad

```

(Not used yet) Implementation of spinor propagators≡

```

pure function pr_dyadleft (p, m, w, psipsibar) result (psipsibarp)
    type(spinordyad) :: psipsibarp
    type(momentum), intent(in) :: p
    real(kind=default), intent(in) :: m, w
    type(spinordyad), intent(in) :: psipsibar

```

```

integer :: i
type(vector) :: vp
type(spinor), dimension(4) :: psi
complex(kind=default) :: pole
complex(kind=default), parameter :: one = (1, 0)
vp = p
pole = 1 / cmplx (p*p - m**2, m*w, kind=default)
do i = 1, 4
    psi(i)%a = psipsibar%a(:,i)
    psi(i) = pole * (- f_vf (one, vp, psi(i)) + m * psi(i))
    psipsibar%a(:,i) = psi(i)%a
end do
end function pr_dyadleft

```

$$\sum_n \psi_n \otimes \bar{\psi}_n \frac{i(\not{p} + m)}{p^2 - m^2 + im\Gamma} \quad (\text{X.67})$$

(Not used yet) Implementation of spinor propagators \equiv

```

pure function pr_dyadright (p, m, w, psipsibar) result (psipsibarp)
type(spinordyad) :: psipsibarp
type(momentum), intent(in) :: p
real(kind=default), intent(in) :: m, w
type(spinordyad), intent(in) :: psipsibar
integer :: i
type(vector) :: vp
type(conjspinor), dimension(4) :: psibar
complex(kind=default) :: pole
complex(kind=default), parameter :: one = (1, 0)
vp = p
pole = 1 / cmplx (p*p - m**2, m*w, kind=default)
do i = 1, 4
    psibar(i)%a = psipsibar%a(i,:)
    psibar(i) = pole * (f_fv (one, psibar(i), vp) + m * psibar(i))
    psipsibarp%a(i,:) = psibar(i)%a
end do
end function pr_dyadright

```

X.14 Spinor Couplings Revisited

(omega_bispinor_couplings.f90) \equiv

(Copyleft)

```

module omega_bispinor_couplings
    use kinds
    use constants
    use omega_bispinors
    use omega_vectorspinors
    use omega_vectors
    use omega_couplings
    implicit none
    private
    (Declaration of bispinor on shell wave functions)
    (Declaration of bispinor off shell wave functions)
    (Declaration of bispinor currents)

```

```

    <Declaration of bispinor propagators>
    integer, parameter, public :: omega_bispinor_cpls_2010_01_A = 0
contains
    <Implementation of bispinor on shell wave functions>
    <Implementation of bispinor off shell wave functions>
    <Implementation of bispinor currents>
    <Implementation of bispinor propagators>
end module omega_bispinor_couplings
    
```

See table X.1 for the names of Fortran functions. We could have used long names instead, but this would increase the chance of running past continuation line limits without adding much to the legibility.

X.14.1 Fermionic Vector and Axial Couplings

There's more than one chiral representation. This one is compatible with HELAS [5].

$$\gamma^0 = \begin{pmatrix} 0 & \mathbf{1} \\ \mathbf{1} & 0 \end{pmatrix}, \quad \gamma^i = \begin{pmatrix} 0 & \sigma^i \\ -\sigma^i & 0 \end{pmatrix}, \quad \gamma_5 = i\gamma^0\gamma^1\gamma^2\gamma^3 = \begin{pmatrix} -\mathbf{1} & 0 \\ 0 & \mathbf{1} \end{pmatrix}, \quad (\text{X.68a})$$

$$C = \begin{pmatrix} \epsilon & 0 \\ 0 & -\epsilon \end{pmatrix}, \quad \epsilon = \begin{pmatrix} 0 & \mathbf{1} \\ -\mathbf{1} & 0 \end{pmatrix}. \quad (\text{X.68b})$$

Therefore

$$g_S + g_P\gamma_5 = \begin{pmatrix} g_S - g_P & 0 & 0 & 0 \\ 0 & g_S - g_P & 0 & 0 \\ 0 & 0 & g_S + g_P & 0 \\ 0 & 0 & 0 & g_S + g_P \end{pmatrix} \quad (\text{X.69a})$$

$$g_V\gamma^0 - g_A\gamma^0\gamma_5 = \begin{pmatrix} 0 & 0 & g_V - g_A & 0 \\ 0 & 0 & 0 & g_V - g_A \\ g_V + g_A & 0 & 0 & 0 \\ 0 & g_V + g_A & 0 & 0 \end{pmatrix} \quad (\text{X.69b})$$

$$g_V\gamma^1 - g_A\gamma^1\gamma_5 = \begin{pmatrix} 0 & 0 & 0 & g_V - g_A \\ 0 & 0 & g_V - g_A & 0 \\ 0 & -g_V - g_A & 0 & 0 \\ -g_V - g_A & 0 & 0 & 0 \end{pmatrix} \quad (\text{X.69c})$$

$$g_V\gamma^2 - g_A\gamma^2\gamma_5 = \begin{pmatrix} 0 & 0 & 0 & -i(g_V - g_A) \\ 0 & 0 & i(g_V - g_A) & 0 \\ 0 & i(g_V + g_A) & 0 & 0 \\ -i(g_V + g_A) & 0 & 0 & 0 \end{pmatrix} \quad (\text{X.69d})$$

$$g_V\gamma^3 - g_A\gamma^3\gamma_5 = \begin{pmatrix} 0 & 0 & g_V - g_A & 0 \\ 0 & 0 & 0 & -g_V + g_A \\ -g_V - g_A & 0 & 0 & 0 \\ 0 & g_V + g_A & 0 & 0 \end{pmatrix} \quad (\text{X.69e})$$

and

$$C(g_S + g_P\gamma_5) = \begin{pmatrix} 0 & g_S - g_P & 0 & 0 \\ -g_S + g_P & 0 & 0 & 0 \\ 0 & 0 & 0 & -g_S - g_P \\ 0 & 0 & g_S + g_P & 0 \end{pmatrix} \quad (\text{X.70a})$$

$$C(g_V\gamma^0 - g_A\gamma^0\gamma_5) = \begin{pmatrix} 0 & 0 & 0 & g_V - g_A \\ 0 & 0 & -g_V + g_A & 0 \\ 0 & -g_V - g_A & 0 & 0 \\ g_V + g_A & 0 & 0 & 0 \end{pmatrix} \quad (\text{X.70b})$$

$$C(g_V\gamma^1 - g_A\gamma^1\gamma_5) = \begin{pmatrix} 0 & 0 & g_V - g_A & 0 \\ 0 & 0 & 0 & -g_V + g_A \\ g_V + g_A & 0 & 0 & 0 \\ 0 & -g_V - g_A & 0 & 0 \end{pmatrix} \quad (\text{X.70c})$$

$$C(g_V\gamma^2 - g_A\gamma^2\gamma_5) = \begin{pmatrix} 0 & 0 & i(g_V - g_A) & 0 \\ 0 & 0 & 0 & i(g_V - g_A) \\ i(g_V + g_A) & 0 & 0 & 0 \\ 0 & i(g_V + g_A) & 0 & 0 \end{pmatrix} \quad (\text{X.70d})$$

$$C(g_V\gamma^3 - g_A\gamma^3\gamma_5) = \begin{pmatrix} 0 & 0 & 0 & -g_V + g_A \\ 0 & 0 & -g_V + g_A & 0 \\ 0 & -g_V - g_A & 0 & 0 \\ -g_V - g_A & 0 & 0 & 0 \end{pmatrix} \quad (\text{X.70e})$$

(Declaration of bispinor currents)≡

```
public :: va_ff, v_ff, a_ff, vl_ff, vr_ff, vlr_ff, va2_ff
```

(Implementation of bispinor currents)≡

```
pure function va_ff (gv, ga, psil, psir) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gv, ga
  type(bispinor), intent(in) :: psil, psir
  complex(kind=default) :: gl, gr
  complex(kind=default) :: g13, g14, g23, g24, g31, g32, g41, g42
  gl = gv + ga
  gr = gv - ga
  g13 = psil%a(1)*psir%a(3)
  g14 = psil%a(1)*psir%a(4)
  g23 = psil%a(2)*psir%a(3)
  g24 = psil%a(2)*psir%a(4)
  g31 = psil%a(3)*psir%a(1)
  g32 = psil%a(3)*psir%a(2)
  g41 = psil%a(4)*psir%a(1)
  g42 = psil%a(4)*psir%a(2)
  j%t = gr * ( g14 - g23) + gl * ( - g32 + g41)
  j%x(1) = gr * ( g13 - g24) + gl * ( g31 - g42)
  j%x(2) = (gr * ( g13 + g24) + gl * ( g31 + g42)) * (0, 1)
  j%x(3) = gr * ( - g14 - g23) + gl * ( - g32 - g41)
end function va_ff
```

(Implementation of bispinor currents)+≡

```
pure function va2_ff (gva, psil, psir) result (j)
  type(vector) :: j
  complex(kind=default), intent(in), dimension(2) :: gva
  type(bispinor), intent(in) :: psil, psir
  complex(kind=default) :: gl, gr
  complex(kind=default) :: g13, g14, g23, g24, g31, g32, g41, g42
  gl = gva(1) + gva(2)
```



```

gr = gva(1) - gva(2)
g13 = psil%a(1)*psir%a(3)
g14 = psil%a(1)*psir%a(4)
g23 = psil%a(2)*psir%a(3)
g24 = psil%a(2)*psir%a(4)
g31 = psil%a(3)*psir%a(1)
g32 = psil%a(3)*psir%a(2)
g41 = psil%a(4)*psir%a(1)
g42 = psil%a(4)*psir%a(2)
j%t    = gr * ( g14 - g23) + gl * ( - g32 + g41)
j%x(1) = gr * ( g13 - g24) + gl * ( g31 - g42)
j%x(2) = (gr * ( g13 + g24) + gl * ( g31 + g42)) * (0, 1)
j%x(3) = gr * ( - g14 - g23) + gl * ( - g32 - g41)
end function va2_ff

```

(Implementation of bispinor currents)+≡

```

pure function v_ff (gv, psil, psir) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gv
  type(bispinor), intent(in) :: psil, psir
  complex(kind=default) :: g13, g14, g23, g24, g31, g32, g41, g42
  g13 = psil%a(1)*psir%a(3)
  g14 = psil%a(1)*psir%a(4)
  g23 = psil%a(2)*psir%a(3)
  g24 = psil%a(2)*psir%a(4)
  g31 = psil%a(3)*psir%a(1)
  g32 = psil%a(3)*psir%a(2)
  g41 = psil%a(4)*psir%a(1)
  g42 = psil%a(4)*psir%a(2)
  j%t    = gv * ( g14 - g23 - g32 + g41)
  j%x(1) = gv * ( g13 - g24 + g31 - g42)
  j%x(2) = gv * ( g13 + g24 + g31 + g42) * (0, 1)
  j%x(3) = gv * ( - g14 - g23 - g32 - g41)
end function v_ff

```

(Implementation of bispinor currents)+≡

```

pure function a_ff (ga, psil, psir) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: ga
  type(bispinor), intent(in) :: psil, psir
  complex(kind=default) :: g13, g14, g23, g24, g31, g32, g41, g42
  g13 = psil%a(1)*psir%a(3)
  g14 = psil%a(1)*psir%a(4)
  g23 = psil%a(2)*psir%a(3)
  g24 = psil%a(2)*psir%a(4)
  g31 = psil%a(3)*psir%a(1)
  g32 = psil%a(3)*psir%a(2)
  g41 = psil%a(4)*psir%a(1)
  g42 = psil%a(4)*psir%a(2)
  j%t    = -ga * ( g14 - g23 + g32 - g41)
  j%x(1) = -ga * ( g13 - g24 - g31 + g42)
  j%x(2) = -ga * ( g13 + g24 - g31 - g42) * (0, 1)
  j%x(3) = -ga * ( - g14 - g23 + g32 + g41)
end function a_ff

```

(Implementation of bispinor currents)+≡

```

pure function vl_ff (gl, psil, psir) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: gl
    type(bispinor), intent(in) :: psil, psir
    complex(kind=default) :: gl2
    complex(kind=default) :: g31, g32, g41, g42
    gl2 = 2 * gl
    g31 = psil%a(3)*psir%a(1)
    g32 = psil%a(3)*psir%a(2)
    g41 = psil%a(4)*psir%a(1)
    g42 = psil%a(4)*psir%a(2)
    j%t = gl2 * ( - g32 + g41)
    j%x(1) = gl2 * ( g31 - g42)
    j%x(2) = gl2 * ( g31 + g42) * (0, 1)
    j%x(3) = gl2 * ( - g32 - g41)
end function vl_ff
    
```

(Implementation of bispinor currents)+≡

```

pure function vr_ff (gr, psil, psir) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: gr
    type(bispinor), intent(in) :: psil, psir
    complex(kind=default) :: gr2
    complex(kind=default) :: g13, g14, g23, g24
    gr2 = 2 * gr
    g13 = psil%a(1)*psir%a(3)
    g14 = psil%a(1)*psir%a(4)
    g23 = psil%a(2)*psir%a(3)
    g24 = psil%a(2)*psir%a(4)
    j%t = gr2 * ( g14 - g23)
    j%x(1) = gr2 * ( g13 - g24)
    j%x(2) = gr2 * ( g13 + g24) * (0, 1)
    j%x(3) = gr2 * ( - g14 - g23)
end function vr_ff
    
```

(Implementation of bispinor currents)+≡

```

pure function vlr_ff (gl, gr, psibar, psi) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: gl, gr
    type(bispinor), intent(in) :: psibar
    type(bispinor), intent(in) :: psi
    j = va_ff (gl+gr, gl-gr, psibar, psi)
end function vlr_ff
    
```

and

$$\not{v} - \not{a}\gamma_5 = \begin{pmatrix} 0 & 0 & v_- - a_- & -v^* + a^* \\ 0 & 0 & -v + a & v_+ - a_+ \\ v_+ + a_+ & v^* + a^* & 0 & 0 \\ v + a & v_- + a_- & 0 & 0 \end{pmatrix} \quad (\text{X.71})$$

with $v_{\pm} = v_0 \pm v_3$, $a_{\pm} = a_0 \pm a_3$, $v = v_1 + iv_2$, $v^* = v_1 - iv_2$, $a = a_1 + ia_2$, and $a^* = a_1 - ia_2$. But note that \cdot^* is *not* complex conjugation for complex v_{μ} or a_{μ} .

(Declaration of bispinor currents)+≡

```

public :: f_vaf, f_vf, f_af, f_vlf, f_vrf, f_vlrf, f_va2f
    
```

```

<Implementation of bispinor currents>+=
pure function f_vaf (gv, ga, v, psi) result (vpsi)
  type(bispinor) :: vpsi
  complex(kind=default), intent(in) :: gv, ga
  type(vector), intent(in) :: v
  type(bispinor), intent(in) :: psi
  complex(kind=default) :: gl, gr
  complex(kind=default) :: vp, vm, v12, v12s
  gl = gv + ga
  gr = gv - ga
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = gr * ( vm * psi%a(3) - v12s * psi%a(4))
  vpsi%a(2) = gr * ( - v12 * psi%a(3) + vp * psi%a(4))
  vpsi%a(3) = gl * ( vp * psi%a(1) + v12s * psi%a(2))
  vpsi%a(4) = gl * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_vaf

```

```

<Implementation of bispinor currents>+=
pure function f_va2f (gva, v, psi) result (vpsi)
  type(bispinor) :: vpsi
  complex(kind=default), intent(in), dimension(2) :: gva
  type(vector), intent(in) :: v
  type(bispinor), intent(in) :: psi
  complex(kind=default) :: gl, gr
  complex(kind=default) :: vp, vm, v12, v12s
  gl = gva(1) + gva(2)
  gr = gva(1) - gva(2)
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = gr * ( vm * psi%a(3) - v12s * psi%a(4))
  vpsi%a(2) = gr * ( - v12 * psi%a(3) + vp * psi%a(4))
  vpsi%a(3) = gl * ( vp * psi%a(1) + v12s * psi%a(2))
  vpsi%a(4) = gl * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_va2f

```

```

<Implementation of bispinor currents>+=
pure function f_vf (gv, v, psi) result (vpsi)
  type(bispinor) :: vpsi
  complex(kind=default), intent(in) :: gv
  type(vector), intent(in) :: v
  type(bispinor), intent(in) :: psi
  complex(kind=default) :: vp, vm, v12, v12s
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = gv * ( vm * psi%a(3) - v12s * psi%a(4))
  vpsi%a(2) = gv * ( - v12 * psi%a(3) + vp * psi%a(4))
  vpsi%a(3) = gv * ( vp * psi%a(1) + v12s * psi%a(2))
  vpsi%a(4) = gv * ( v12 * psi%a(1) + vm * psi%a(2))

```

```

end function f_vf

<Implementation of bispinor currents>+≡
pure function f_af (ga, v, psi) result (vpsi)
  type(bispinor) :: vpsi
  complex(kind=default), intent(in) :: ga
  type(vector), intent(in) :: v
  type(bispinor), intent(in) :: psi
  complex(kind=default) :: vp, vm, v12, v12s
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = ga * ( - vm * psi%a(3) + v12s * psi%a(4))
  vpsi%a(2) = ga * ( v12 * psi%a(3) - vp * psi%a(4))
  vpsi%a(3) = ga * ( vp * psi%a(1) + v12s * psi%a(2))
  vpsi%a(4) = ga * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_af

<Implementation of bispinor currents>+≡
pure function f_vlf (gl, v, psi) result (vpsi)
  type(bispinor) :: vpsi
  complex(kind=default), intent(in) :: gl
  type(vector), intent(in) :: v
  type(bispinor), intent(in) :: psi
  complex(kind=default) :: gl2
  complex(kind=default) :: vp, vm, v12, v12s
  gl2 = 2 * gl
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = 0
  vpsi%a(2) = 0
  vpsi%a(3) = gl2 * ( vp * psi%a(1) + v12s * psi%a(2))
  vpsi%a(4) = gl2 * ( v12 * psi%a(1) + vm * psi%a(2))
end function f_vlf

<Implementation of bispinor currents>+≡
pure function f_vrf (gr, v, psi) result (vpsi)
  type(bispinor) :: vpsi
  complex(kind=default), intent(in) :: gr
  type(vector), intent(in) :: v
  type(bispinor), intent(in) :: psi
  complex(kind=default) :: gr2
  complex(kind=default) :: vp, vm, v12, v12s
  gr2 = 2 * gr
  vp = v%t + v%x(3)
  vm = v%t - v%x(3)
  v12 = v%x(1) + (0,1)*v%x(2)
  v12s = v%x(1) - (0,1)*v%x(2)
  vpsi%a(1) = gr2 * ( vm * psi%a(3) - v12s * psi%a(4))
  vpsi%a(2) = gr2 * ( - v12 * psi%a(3) + vp * psi%a(4))
  vpsi%a(3) = 0
  vpsi%a(4) = 0
end function f_vrf

```

```

<Implementation of bispinor currents>+≡
pure function f_vlrf (gl, gr, v, psi) result (vpsi)
  type(bispinor) :: vpsi
  complex(kind=default), intent(in) :: gl, gr
  type(vector), intent(in) :: v
  type(bispinor), intent(in) :: psi
  vpsi = f_vaf (gl+gr, gl-gr, v, psi)
end function f_vlrf

```

X.14.2 Fermionic Scalar and Pseudo Scalar Couplings

```

<Declaration of bispinor currents>+≡
public :: sp_ff, s_ff, p_ff, sl_ff, sr_ff, slr_ff

<Implementation of bispinor currents>+≡
pure function sp_ff (gs, gp, psil, psir) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gs, gp
  type(bispinor), intent(in) :: psil, psir
  j = (gs - gp) * (psil%a(1)*psir%a(2) - psil%a(2)*psir%a(1)) &
      + (gs + gp) * (- psil%a(3)*psir%a(4) + psil%a(4)*psir%a(3))
end function sp_ff

<Implementation of bispinor currents>+≡
pure function s_ff (gs, psil, psir) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gs
  type(bispinor), intent(in) :: psil, psir
  j = gs * (psil * psir)
end function s_ff

<Implementation of bispinor currents>+≡
pure function p_ff (gp, psil, psir) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gp
  type(bispinor), intent(in) :: psil, psir
  j = gp * (- psil%a(1)*psir%a(2) + psil%a(2)*psir%a(1) &
            - psil%a(3)*psir%a(4) + psil%a(4)*psir%a(3))
end function p_ff

<Implementation of bispinor currents>+≡
pure function sl_ff (gl, psil, psir) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gl
  type(bispinor), intent(in) :: psil, psir
  j = 2 * gl * (psil%a(1)*psir%a(2) - psil%a(2)*psir%a(1))
end function sl_ff

<Implementation of bispinor currents>+≡
pure function sr_ff (gr, psil, psir) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gr
  type(bispinor), intent(in) :: psil, psir
  j = 2 * gr * (- psil%a(3)*psir%a(4) + psil%a(4)*psir%a(3))
end function sr_ff

```

```

<Implementation of bispinor currents>+≡
pure function slr_ff (gl, gr, psibar, psi) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gl, gr
  type(bispinor), intent(in) :: psibar
  type(bispinor), intent(in) :: psi
  j = sp_ff (gr+gl, gr-gl, psibar, psi)
end function slr_ff

<Declaration of bispinor currents>+≡
public :: f_spf, f_sf, f_pf, f_slf, f_srf, f_slrf

<Implementation of bispinor currents>+≡
pure function f_spf (gs, gp, phi, psi) result (phipsi)
  type(bispinor) :: phipsi
  complex(kind=default), intent(in) :: gs, gp
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi
  phipsi%a(1:2) = ((gs - gp) * phi) * psi%a(1:2)
  phipsi%a(3:4) = ((gs + gp) * phi) * psi%a(3:4)
end function f_spf

<Implementation of bispinor currents>+≡
pure function f_sf (gs, phi, psi) result (phipsi)
  type(bispinor) :: phipsi
  complex(kind=default), intent(in) :: gs
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi
  phipsi%a = (gs * phi) * psi%a
end function f_sf

<Implementation of bispinor currents>+≡
pure function f_pf (gp, phi, psi) result (phipsi)
  type(bispinor) :: phipsi
  complex(kind=default), intent(in) :: gp
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi
  phipsi%a(1:2) = (- gp * phi) * psi%a(1:2)
  phipsi%a(3:4) = ( gp * phi) * psi%a(3:4)
end function f_pf

<Implementation of bispinor currents>+≡
pure function f_slf (gl, phi, psi) result (phipsi)
  type(bispinor) :: phipsi
  complex(kind=default), intent(in) :: gl
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi
  phipsi%a(1:2) = (2 * gl * phi) * psi%a(1:2)
  phipsi%a(3:4) = 0
end function f_slf

<Implementation of bispinor currents>+≡
pure function f_srf (gr, phi, psi) result (phipsi)
  type(bispinor) :: phipsi
  complex(kind=default), intent(in) :: gr
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi

```

```

    phipsi%a(1:2) = 0
    phipsi%a(3:4) = (2 * gr * phi) * psi%a(3:4)
end function f_srf

<Implementation of bispinor currents>+≡
pure function f_slrf (gl, gr, phi, psi) result (phipsi)
    type(bispinor) :: phipsi
    complex(kind=default), intent(in) :: gl, gr
    complex(kind=default), intent(in) :: phi
    type(bispinor), intent(in) :: psi
    phipsi = f_spf (gr+gl, gr-gl, phi, psi)
end function f_slrf

```

X.14.3 Couplings for BRST Transformations

3-Couplings

The lists of needed gamma matrices can be found in the next subsection with the gravitino couplings.

```

<Declaration of bispinor currents>+≡
    private :: vv_ff, f_vvf

<Declaration of bispinor currents>+≡
    public :: vmom_ff, mom_ff, mom5_ff, moml_ff, momr_ff, lmom_ff, rmom_ff

<Implementation of bispinor currents>+≡
pure function vv_ff (psibar, psi, k) result (psibarpsi)
    type(vector) :: psibarpsi
    type(bispinor), intent(in) :: psibar, psi
    type(vector), intent(in) :: k
    complex(kind=default) :: kp, km, k12, k12s
    type(bispinor) :: kgpsi1, kgpsi2, kgpsi3, kgpsi4
    kp = k%t + k%x(3)
    km = k%t - k%x(3)
    k12 = k%x(1) + (0,1)*k%x(2)
    k12s = k%x(1) - (0,1)*k%x(2)
    kgpsi1%a(1) = -k%x(3) * psi%a(1) - k12s * psi%a(2)
    kgpsi1%a(2) = -k12 * psi%a(1) + k%x(3) * psi%a(2)
    kgpsi1%a(3) = k%x(3) * psi%a(3) + k12s * psi%a(4)
    kgpsi1%a(4) = k12 * psi%a(3) - k%x(3) * psi%a(4)
    kgpsi2%a(1) = ((0,-1) * k%x(2)) * psi%a(1) - km * psi%a(2)
    kgpsi2%a(2) = -kp * psi%a(1) + ((0,1) * k%x(2)) * psi%a(2)
    kgpsi2%a(3) = ((0,-1) * k%x(2)) * psi%a(3) + kp * psi%a(4)
    kgpsi2%a(4) = km * psi%a(3) + ((0,1) * k%x(2)) * psi%a(4)
    kgpsi3%a(1) = (0,1) * (k%x(1) * psi%a(1) + km * psi%a(2))
    kgpsi3%a(2) = (0,-1) * (kp * psi%a(1) + k%x(1) * psi%a(2))
    kgpsi3%a(3) = (0,1) * (k%x(1) * psi%a(3) - kp * psi%a(4))
    kgpsi3%a(4) = (0,1) * (km * psi%a(3) - k%x(1) * psi%a(4))
    kgpsi4%a(1) = -k%t * psi%a(1) - k12s * psi%a(2)
    kgpsi4%a(2) = k12 * psi%a(1) + k%t * psi%a(2)
    kgpsi4%a(3) = k%t * psi%a(3) - k12s * psi%a(4)
    kgpsi4%a(4) = k12 * psi%a(3) - k%t * psi%a(4)
    psibarpsi%t = 2 * (psibar * kgpsi1)
    psibarpsi%x(1) = 2 * (psibar * kgpsi2)
    psibarpsi%x(2) = 2 * (psibar * kgpsi3)

```

```

    psibarpsi%x(3) = 2 * (psibar * kgpsi4)
end function vv_ff

```

(Implementation of bispinor currents)+≡

```

pure function f_vvf (v, psi, k) result (kvpsi)
    type(bispinor) :: kvpsi
    type(bispinor), intent(in) :: psi
    type(vector), intent(in) :: k, v
    complex(kind=default) :: kv30, kv21, kv01, kv31, kv02, kv32
    complex(kind=default) :: ap, am, bp, bm, bps, bms
    kv30 = k%x(3) * v%t - k%t * v%x(3)
    kv21 = (0,1) * (k%x(2) * v%x(1) - k%x(1) * v%x(2))
    kv01 = k%t * v%x(1) - k%x(1) * v%t
    kv31 = k%x(3) * v%x(1) - k%x(1) * v%x(3)
    kv02 = (0,1) * (k%t * v%x(2) - k%x(2) * v%t)
    kv32 = (0,1) * (k%x(3) * v%x(2) - k%x(2) * v%x(3))
    ap = 2 * (kv30 + kv21)
    am = 2 * (-kv30 + kv21)
    bp = 2 * (kv01 + kv31 + kv02 + kv32)
    bm = 2 * (kv01 - kv31 + kv02 - kv32)
    bps = 2 * (kv01 + kv31 - kv02 - kv32)
    bms = 2 * (kv01 - kv31 - kv02 + kv32)
    kvpsi%a(1) = am * psi%a(1) + bms * psi%a(2)
    kvpsi%a(2) = bp * psi%a(1) - am * psi%a(2)
    kvpsi%a(3) = ap * psi%a(3) - bps * psi%a(4)
    kvpsi%a(4) = -bm * psi%a(3) - ap * psi%a(4)
end function f_vvf

```

(Implementation of bispinor currents)+≡

```

pure function vmom_ff (g, psibar, psi, k) result (psibarpsi)
    type(vector) :: psibarpsi
    complex(kind=default), intent(in) :: g
    type(bispinor), intent(in) :: psibar, psi
    type(momentum), intent(in) :: k
    type(vector) :: vk
    vk = k
    psibarpsi = g * vv_ff (psibar, psi, vk)
end function vmom_ff

```

(Implementation of bispinor currents)+≡

```

pure function mom_ff (g, m, psibar, psi, k) result (psibarpsi)
    complex(kind=default) :: psibarpsi
    type(bispinor), intent(in) :: psibar, psi
    type(momentum), intent(in) :: k
    complex(kind=default), intent(in) :: g, m
    type(bispinor) :: kmpsi
    complex(kind=default) :: kp, km, k12, k12s
    kp = k%t + k%x(3)
    km = k%t - k%x(3)
    k12 = k%x(1) + (0,1)*k%x(2)
    k12s = k%x(1) - (0,1)*k%x(2)
    kmpsi%a(1) = km * psi%a(3) - k12s * psi%a(4)
    kmpsi%a(2) = kp * psi%a(4) - k12 * psi%a(3)
    kmpsi%a(3) = kp * psi%a(1) + k12s * psi%a(2)
    kmpsi%a(4) = k12 * psi%a(1) + km * psi%a(2)
    psibarpsi = g * (psibar * kmpsi) + s_ff (m, psibar, psi)

```



```

end function mom_ff

<Implementation of bispinor currents>+≡
pure function mom5_ff (g, m, psibar, psi, k) result (psibarpsi)
  complex(kind=default) :: psibarpsi
  type(bispinor), intent(in) :: psibar, psi
  type(momentum), intent(in) :: k
  complex(kind=default), intent(in) :: g, m
  type(bispinor) :: g5psi
  g5psi%a(1:2) = - psi%a(1:2)
  g5psi%a(3:4) = psi%a(3:4)
  psibarpsi = mom_ff (g, m, psibar, g5psi, k)
end function mom5_ff

<Implementation of bispinor currents>+≡
pure function moml_ff (g, m, psibar, psi, k) result (psibarpsi)
  complex(kind=default) :: psibarpsi
  type(bispinor), intent(in) :: psibar, psi
  type(momentum), intent(in) :: k
  complex(kind=default), intent(in) :: g, m
  type(bispinor) :: leftpsi
  leftpsi%a(1:2) = 2 * psi%a(1:2)
  leftpsi%a(3:4) = 0
  psibarpsi = mom_ff (g, m, psibar, leftpsi, k)
end function moml_ff

<Implementation of bispinor currents>+≡
pure function momr_ff (g, m, psibar, psi, k) result (psibarpsi)
  complex(kind=default) :: psibarpsi
  type(bispinor), intent(in) :: psibar, psi
  type(momentum), intent(in) :: k
  complex(kind=default), intent(in) :: g, m
  type(bispinor) :: rightpsi
  rightpsi%a(1:2) = 0
  rightpsi%a(3:4) = 2 * psi%a(3:4)
  psibarpsi = mom_ff (g, m, psibar, rightpsi, k)
end function momr_ff

<Implementation of bispinor currents>+≡
pure function lmom_ff (g, m, psibar, psi, k) result (psibarpsi)
  complex(kind=default) :: psibarpsi
  type(bispinor), intent(in) :: psibar, psi
  type(momentum), intent(in) :: k
  complex(kind=default), intent(in) :: g, m
  psibarpsi = mom_ff (g, m, psibar, psi, k) + &
    mom5_ff (g,-m, psibar, psi, k)
end function lmom_ff

<Implementation of bispinor currents>+≡
pure function rmom_ff (g, m, psibar, psi, k) result (psibarpsi)
  complex(kind=default) :: psibarpsi
  type(bispinor), intent(in) :: psibar, psi
  type(momentum), intent(in) :: k
  complex(kind=default), intent(in) :: g, m
  psibarpsi = mom_ff (g, m, psibar, psi, k) - &
    mom5_ff (g,-m, psibar, psi, k)
end function rmom_ff

```

```

<Declaration of bispinor currents>+≡
  public :: f_vmomf, f_momf, f_mom5f, f_momlf, f_momrf, f_lmomf, f_rmomf

<Implementation of bispinor currents>+≡
  pure function f_vmomf (g, v, psi, k) result (kvpsi)
    type(bispinor) :: kvpsi
    type(bispinor), intent(in) :: psi
    complex(kind=default), intent(in) :: g
    type(momentum), intent(in) :: k
    type(vector), intent(in) :: v
    type(vector) :: vk
    vk = k
    kvpsi = g * f_vvf (v, psi, vk)
  end function f_vmomf

<Implementation of bispinor currents>+≡
  pure function f_momf (g, m, phi, psi, k) result (kmpsi)
    type(bispinor) :: kmpsi
    type(bispinor), intent(in) :: psi
    complex(kind=default), intent(in) :: phi, g, m
    type(momentum), intent(in) :: k
    complex(kind=default) :: kp, km, k12, k12s
    kp = k%t + k%x(3)
    km = k%t - k%x(3)
    k12 = k%x(1) + (0,1)*k%x(2)
    k12s = k%x(1) - (0,1)*k%x(2)
    kmpsi%a(1) = km * psi%a(3) - k12s * psi%a(4)
    kmpsi%a(2) = -k12 * psi%a(3) + kp * psi%a(4)
    kmpsi%a(3) = kp * psi%a(1) + k12s * psi%a(2)
    kmpsi%a(4) = k12 * psi%a(1) + km * psi%a(2)
    kmpsi = g * (phi * kmpsi) + f_sf (m, phi, psi)
  end function f_momf

<Implementation of bispinor currents>+≡
  pure function f_mom5f (g, m, phi, psi, k) result (kmpsi)
    type(bispinor) :: kmpsi
    type(bispinor), intent(in) :: psi
    complex(kind=default), intent(in) :: phi, g, m
    type(momentum), intent(in) :: k
    type(bispinor) :: g5psi
    g5psi%a(1:2) = - psi%a(1:2)
    g5psi%a(3:4) = psi%a(3:4)
    kmpsi = f_momf (g, m, phi, g5psi, k)
  end function f_mom5f

<Implementation of bispinor currents>+≡
  pure function f_momlf (g, m, phi, psi, k) result (kmpsi)
    type(bispinor) :: kmpsi
    type(bispinor), intent(in) :: psi
    complex(kind=default), intent(in) :: phi, g, m
    type(momentum), intent(in) :: k
    type(bispinor) :: leftpsi
    leftpsi%a(1:2) = 2 * psi%a(1:2)
    leftpsi%a(3:4) = 0
    kmpsi = f_momf (g, m, phi, leftpsi, k)
  end function f_momlf

```

```

<Implementation of bispinor currents>+≡
pure function f_momrf (g, m, phi, psi, k) result (kmpsi)
  type(bispinor) :: kmpsi
  type(bispinor), intent(in) :: psi
  complex(kind=default), intent(in) :: phi, g, m
  type(momentum), intent(in) :: k
  type(bispinor) :: rightpsi
  rightpsi%a(1:2) = 0
  rightpsi%a(3:4) = 2 * psi%a(3:4)
  kmpsi = f_momf (g, m, phi, rightpsi, k)
end function f_momrf

<Implementation of bispinor currents>+≡
pure function f_lmomf (g, m, phi, psi, k) result (kmpsi)
  type(bispinor) :: kmpsi
  type(bispinor), intent(in) :: psi
  complex(kind=default), intent(in) :: phi, g, m
  type(momentum), intent(in) :: k
  kmpsi = f_momf (g, m, phi, psi, k) + &
    f_mom5f (g,-m, phi, psi, k)
end function f_lmomf

<Implementation of bispinor currents>+≡
pure function f_rmomf (g, m, phi, psi, k) result (kmpsi)
  type(bispinor) :: kmpsi
  type(bispinor), intent(in) :: psi
  complex(kind=default), intent(in) :: phi, g, m
  type(momentum), intent(in) :: k
  kmpsi = f_momf (g, m, phi, psi, k) - &
    f_mom5f (g,-m, phi, psi, k)
end function f_rmomf

```

4-Couplings

```

<Declaration of bispinor currents>+≡
public :: v2_ff, sv1_ff, sv2_ff, pv1_ff, pv2_ff, svl1_ff, svl2_ff, &
  svr1_ff, svr2_ff, svlr1_ff, svlr2_ff

<Implementation of bispinor currents>+≡
pure function v2_ff (g, psibar, v, psi) result (v2)
  type(vector) :: v2
  complex (kind=default), intent(in) :: g
  type(bispinor), intent(in) :: psibar, psi
  type(vector), intent(in) :: v
  v2 = (-g) * vv_ff (psibar, psi, v)
end function v2_ff

<Implementation of bispinor currents>+≡
pure function sv1_ff (g, psibar, v, psi) result (phi)
  complex(kind=default) :: phi
  type(bispinor), intent(in) :: psibar, psi
  type(vector), intent(in) :: v
  complex(kind=default), intent(in) :: g
  phi = psibar * f_vf (g, v, psi)
end function sv1_ff

```

```

<Implementation of bispinor currents>+≡
pure function sv2_ff (g, psibar, phi, psi) result (v)
  type(vector) :: v
  complex(kind=default), intent(in) :: phi, g
  type(bispinor), intent(in) :: psibar, psi
  v = phi * v_ff (g, psibar, psi)
end function sv2_ff

<Implementation of bispinor currents>+≡
pure function pv1_ff (g, psibar, v, psi) result (phi)
  complex(kind=default) :: phi
  type(bispinor), intent(in) :: psibar, psi
  type(vector), intent(in) :: v
  complex(kind=default), intent(in) :: g
  phi = - (psibar * f_af (g, v, psi))
end function pv1_ff

<Implementation of bispinor currents>+≡
pure function pv2_ff (g, psibar, phi, psi) result (v)
  type(vector) :: v
  complex(kind=default), intent(in) :: phi, g
  type(bispinor), intent(in) :: psibar, psi
  v = -(phi * a_ff (g, psibar, psi))
end function pv2_ff

<Implementation of bispinor currents>+≡
pure function svl1_ff (g, psibar, v, psi) result (phi)
  complex(kind=default) :: phi
  type(bispinor), intent(in) :: psibar, psi
  type(vector), intent(in) :: v
  complex(kind=default), intent(in) :: g
  phi = psibar * f_vlf (g, v, psi)
end function svl1_ff

<Implementation of bispinor currents>+≡
pure function svl2_ff (g, psibar, phi, psi) result (v)
  type(vector) :: v
  complex(kind=default), intent(in) :: phi, g
  type(bispinor), intent(in) :: psibar, psi
  v = phi * vl_ff (g, psibar, psi)
end function svl2_ff

<Implementation of bispinor currents>+≡
pure function svr1_ff (g, psibar, v, psi) result (phi)
  complex(kind=default) :: phi
  type(bispinor), intent(in) :: psibar, psi
  type(vector), intent(in) :: v
  complex(kind=default), intent(in) :: g
  phi = psibar * f_vrf (g, v, psi)
end function svr1_ff

<Implementation of bispinor currents>+≡
pure function svr2_ff (g, psibar, phi, psi) result (v)
  type(vector) :: v
  complex(kind=default), intent(in) :: phi, g
  type(bispinor), intent(in) :: psibar, psi
  v = phi * vr_ff (g, psibar, psi)
end function svr2_ff

```

```

<Implementation of bispinor currents>+≡
pure function svlr1_ff (gl, gr, psibar, v, psi) result (phi)
  complex(kind=default) :: phi
  type(bispinor), intent(in) :: psibar, psi
  type(vector), intent(in) :: v
  complex(kind=default), intent(in) :: gl, gr
  phi = psibar * f_vlrf (gl, gr, v, psi)
end function svlr1_ff

<Implementation of bispinor currents>+≡
pure function svlr2_ff (gl, gr, psibar, phi, psi) result (v)
  type(vector) :: v
  complex(kind=default), intent(in) :: phi, gl, gr
  type(bispinor), intent(in) :: psibar, psi
  v = phi * vlr_ff (gl, gr, psibar, psi)
end function svlr2_ff

<Declaration of bispinor currents>+≡
public :: f_v2f, f_svf, f_pvf, f_svlf, f_svr, f_svlrf

<Implementation of bispinor currents>+≡
pure function f_v2f (g, v1, v2, psi) result (vpsi)
  type(bispinor) :: vpsi
  complex(kind=default), intent(in) :: g
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: v1, v2
  vpsi = g * f_vvf (v2, psi, v1)
end function f_v2f

<Implementation of bispinor currents>+≡
pure function f_svf (g, phi, v, psi) result (pvpsi)
  type(bispinor) :: pvpsi
  complex(kind=default), intent(in) :: g, phi
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: v
  pvpsi = phi * f_vf (g, v, psi)
end function f_svf

<Implementation of bispinor currents>+≡
pure function f_pvf (g, phi, v, psi) result (pvpsi)
  type(bispinor) :: pvpsi
  complex(kind=default), intent(in) :: g, phi
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: v
  pvpsi = -(phi * f_af (g, v, psi))
end function f_pvf

<Implementation of bispinor currents>+≡
pure function f_svlf (g, phi, v, psi) result (pvpsi)
  type(bispinor) :: pvpsi
  complex(kind=default), intent(in) :: g, phi
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: v
  pvpsi = phi * f_vlf (g, v, psi)
end function f_svlf

<Implementation of bispinor currents>+≡
pure function f_svr (g, phi, v, psi) result (pvpsi)

```

```

    type(bispinor) :: pvpsi
    complex(kind=default), intent(in) :: g, phi
    type(bispinor), intent(in) :: psi
    type(vector), intent(in) :: v
    pvpsi = phi * f_vrf (g, v, psi)
end function f_svr

<Implementation of bispinor currents>+≡
pure function f_svlrf (gl, gr, phi, v, psi) result (pvpsi)
    type(bispinor) :: pvpsi
    complex(kind=default), intent(in) :: gl, gr, phi
    type(bispinor), intent(in) :: psi
    type(vector), intent(in) :: v
    pvpsi = phi * f_vlrf (gl, gr, v, psi)
end function f_svlrf

X.14.4 Gravitino Couplings

<Declaration of bispinor currents>+≡
public :: pot_grf, pot_fgr, s_grf, s_fgr, p_grf, p_fgr, &
        sl_grf, sl_fgr, sr_grf, sr_fgr, slr_grf, slr_fgr

<Declaration of bispinor currents>+≡
private :: fgvgr, fgvg5gr, fggvvgr, grkgf, grkkgf, grkkkgf, &
        fgkgr, fg5gkgr, grvgf, grg5vgf, grkgggf, fggkkgf

<Implementation of bispinor currents>+≡
pure function pot_grf (g, gravbar, psi) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: g
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(vectorspinor) :: gamma_psi
    gamma_psi%psi(1)%a(1) = psi%a(3)
    gamma_psi%psi(1)%a(2) = psi%a(4)
    gamma_psi%psi(1)%a(3) = psi%a(1)
    gamma_psi%psi(1)%a(4) = psi%a(2)
    gamma_psi%psi(2)%a(1) = psi%a(4)
    gamma_psi%psi(2)%a(2) = psi%a(3)
    gamma_psi%psi(2)%a(3) = - psi%a(2)
    gamma_psi%psi(2)%a(4) = - psi%a(1)
    gamma_psi%psi(3)%a(1) = (0,-1) * psi%a(4)
    gamma_psi%psi(3)%a(2) = (0,1) * psi%a(3)
    gamma_psi%psi(3)%a(3) = (0,1) * psi%a(2)
    gamma_psi%psi(3)%a(4) = (0,-1) * psi%a(1)
    gamma_psi%psi(4)%a(1) = psi%a(3)
    gamma_psi%psi(4)%a(2) = - psi%a(4)
    gamma_psi%psi(4)%a(3) = - psi%a(1)
    gamma_psi%psi(4)%a(4) = psi%a(2)
    j = g * (gravbar * gamma_psi)
end function pot_grf

<Implementation of bispinor currents>+≡
pure function pot_fgr (g, psibar, grav) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: g

```

```

type(bispinor), intent(in) :: psibar
type(vectorspinor), intent(in) :: grav
type(bispinor) :: gamma_grav
gamma_grav%a(1) = grav%psi(1)%a(3) - grav%psi(2)%a(4) + &
  ((0,1)*grav%psi(3)%a(4)) - grav%psi(4)%a(3)
gamma_grav%a(2) = grav%psi(1)%a(4) - grav%psi(2)%a(3) - &
  ((0,1)*grav%psi(3)%a(3)) + grav%psi(4)%a(4)
gamma_grav%a(3) = grav%psi(1)%a(1) + grav%psi(2)%a(2) - &
  ((0,1)*grav%psi(3)%a(2)) + grav%psi(4)%a(1)
gamma_grav%a(4) = grav%psi(1)%a(2) + grav%psi(2)%a(1) + &
  ((0,1)*grav%psi(3)%a(1)) - grav%psi(4)%a(2)
j = g * (psibar * gamma_grav)
end function pot_fgr

<Implementation of bispinor currents>+=
pure function grvgf (gravbar, psi, k) result (j)
  complex(kind=default) :: j
  complex(kind=default) :: kp, km, k12, k12s
  type(vectorspinor), intent(in) :: gravbar
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: k
  type(vectorspinor) :: kg_psi
  kp = k%t + k%x(3)
  km = k%t - k%x(3)
  k12 = k%x(1) + (0,1)*k%x(2)
  k12s = k%x(1) - (0,1)*k%x(2)
  !!! Since we are taking the spinor product here, NO explicit
  !!! charge conjugation matrix is needed!
  kg_psi%psi(1)%a(1) = km * psi%a(1) - k12s * psi%a(2)
  kg_psi%psi(1)%a(2) = (-k12) * psi%a(1) + kp * psi%a(2)
  kg_psi%psi(1)%a(3) = kp * psi%a(3) + k12s * psi%a(4)
  kg_psi%psi(1)%a(4) = k12 * psi%a(3) + km * psi%a(4)
  kg_psi%psi(2)%a(1) = k12s * psi%a(1) - km * psi%a(2)
  kg_psi%psi(2)%a(2) = (-kp) * psi%a(1) + k12 * psi%a(2)
  kg_psi%psi(2)%a(3) = k12s * psi%a(3) + kp * psi%a(4)
  kg_psi%psi(2)%a(4) = km * psi%a(3) + k12 * psi%a(4)
  kg_psi%psi(3)%a(1) = (0,1) * (k12s * psi%a(1) + km * psi%a(2))
  kg_psi%psi(3)%a(2) = (0,1) * (-kp * psi%a(1) - k12 * psi%a(2))
  kg_psi%psi(3)%a(3) = (0,1) * (k12s * psi%a(3) - kp * psi%a(4))
  kg_psi%psi(3)%a(4) = (0,1) * (km * psi%a(3) - k12 * psi%a(4))
  kg_psi%psi(4)%a(1) = (-km) * psi%a(1) - k12s * psi%a(2)
  kg_psi%psi(4)%a(2) = k12 * psi%a(1) + kp * psi%a(2)
  kg_psi%psi(4)%a(3) = kp * psi%a(3) - k12s * psi%a(4)
  kg_psi%psi(4)%a(4) = k12 * psi%a(3) - km * psi%a(4)
  j = gravbar * kg_psi
end function grvgf

<Implementation of bispinor currents>+=
pure function grg5vgf (gravbar, psi, k) result (j)
  complex(kind=default) :: j
  type(vectorspinor), intent(in) :: gravbar
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: k
  type(bispinor) :: g5_psi
  g5_psi%a(1:2) = - psi%a(1:2)

```

```

    g5_psi%a(3:4) = psi%a(3:4)
    j = grvgf (gravbar, g5_psi, k)
end function grg5vgf

<Implementation of bispinor currents>+≡
pure function s_grf (g, gravbar, psi, k) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: g
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(momentum), intent(in) :: k
    type(vector) :: vk
    vk = k
    j = g * grvgf (gravbar, psi, vk)
end function s_grf

<Implementation of bispinor currents>+≡
pure function sl_grf (gl, gravbar, psi, k) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: gl
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(bispinor) :: psi_l
    type(momentum), intent(in) :: k
    psi_l%a(1:2) = psi%a(1:2)
    psi_l%a(3:4) = 0
    j = s_grf (gl, gravbar, psi_l, k)
end function sl_grf

<Implementation of bispinor currents>+≡
pure function sr_grf (gr, gravbar, psi, k) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: gr
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(bispinor) :: psi_r
    type(momentum), intent(in) :: k
    psi_r%a(1:2) = 0
    psi_r%a(3:4) = psi%a(3:4)
    j = s_grf (gr, gravbar, psi_r, k)
end function sr_grf

<Implementation of bispinor currents>+≡
pure function slr_grf (gl, gr, gravbar, psi, k) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: gl, gr
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(momentum), intent(in) :: k
    j = sl_grf (gl, gravbar, psi, k) + sr_grf (gr, gravbar, psi, k)
end function slr_grf

<Implementation of bispinor currents>+≡
pure function fgkgr (psibar, grav, k) result (j)
    complex(kind=default) :: j
    complex(kind=default) :: kp, km, k12, k12s
    type(bispinor), intent(in) :: psibar

```



```

type(vectorspinor), intent(in) :: grav
type(vector), intent(in) :: k
type(bispinor) :: gk_grav
kp = k%t + k%x(3)
km = k%t - k%x(3)
k12 = k%x(1) + (0,1)*k%x(2)
k12s = k%x(1) - (0,1)*k%x(2)
!!! Since we are taking the spinor product here, NO explicit
!!! charge conjugation matrix is needed!
gk_grav%a(1) = kp * grav%psi(1)%a(1) + k12s * grav%psi(1)%a(2) &
               - k12 * grav%psi(2)%a(1) - km * grav%psi(2)%a(2) &
               + (0,1) * k12 * grav%psi(3)%a(1) &
               + (0,1) * km * grav%psi(3)%a(2) &
               - kp * grav%psi(4)%a(1) - k12s * grav%psi(4)%a(2)
gk_grav%a(2) = k12 * grav%psi(1)%a(1) + km * grav%psi(1)%a(2) &
               - kp * grav%psi(2)%a(1) - k12s * grav%psi(2)%a(2) &
               - (0,1) * kp * grav%psi(3)%a(1) &
               - (0,1) * k12s * grav%psi(3)%a(2) &
               + k12 * grav%psi(4)%a(1) + km * grav%psi(4)%a(2)
gk_grav%a(3) = km * grav%psi(1)%a(3) - k12s * grav%psi(1)%a(4) &
               - k12 * grav%psi(2)%a(3) + kp * grav%psi(2)%a(4) &
               + (0,1) * k12 * grav%psi(3)%a(3) &
               - (0,1) * kp * grav%psi(3)%a(4) &
               + km * grav%psi(4)%a(3) - k12s * grav%psi(4)%a(4)
gk_grav%a(4) = - k12 * grav%psi(1)%a(3) + kp * grav%psi(1)%a(4) &
               + km * grav%psi(2)%a(3) - k12s * grav%psi(2)%a(4) &
               + (0,1) * km * grav%psi(3)%a(3) &
               - (0,1) * k12s * grav%psi(3)%a(4) &
               + k12 * grav%psi(4)%a(3) - kp * grav%psi(4)%a(4)
j = psibar * gk_grav
end function fgkgr

(Implementation of bispinor currents)+≡
pure function fg5gkgr (psibar, grav, k) result (j)
complex(kind=default) :: j
type(bispinor), intent(in) :: psibar
type(vectorspinor), intent(in) :: grav
type(vector), intent(in) :: k
type(bispinor) :: psibar_g5
psibar_g5%a(1:2) = - psibar%a(1:2)
psibar_g5%a(3:4) = psibar%a(3:4)
j = fgkgr (psibar_g5, grav, k)
end function fg5gkgr

(Implementation of bispinor currents)+≡
pure function s_fgr (g, psibar, grav, k) result (j)
complex(kind=default) :: j
complex(kind=default), intent(in) :: g
type(bispinor), intent(in) :: psibar
type(vectorspinor), intent(in) :: grav
type(momentum), intent(in) :: k
type(vector) :: vk
vk = k
j = g * fgkgr (psibar, grav, vk)
end function s_fgr
    
```

(Implementation of bispinor currents)+≡

```
pure function sl_fgr (gl, psibar, grav, k) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gl
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_l
  type(vectorspinor), intent(in) :: grav
  type(momentum), intent(in) :: k
  psibar_l%a(1:2) = psibar%a(1:2)
  psibar_l%a(3:4) = 0
  j = s_fgr (gl, psibar_l, grav, k)
end function sl_fgr
```

(Implementation of bispinor currents)+≡

```
pure function sr_fgr (gr, psibar, grav, k) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gr
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_r
  type(vectorspinor), intent(in) :: grav
  type(momentum), intent(in) :: k
  psibar_r%a(1:2) = 0
  psibar_r%a(3:4) = psibar%a(3:4)
  j = s_fgr (gr, psibar_r, grav, k)
end function sr_fgr
```

(Implementation of bispinor currents)+≡

```
pure function slr_fgr (gl, gr, psibar, grav, k) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gl, gr
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_r
  type(vectorspinor), intent(in) :: grav
  type(momentum), intent(in) :: k
  j = sl_fgr (gl, psibar, grav, k) + sr_fgr (gr, psibar, grav, k)
end function slr_fgr
```

(Implementation of bispinor currents)+≡

```
pure function p_grf (g, gravbar, psi, k) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: g
  type(vectorspinor), intent(in) :: gravbar
  type(bispinor), intent(in) :: psi
  type(momentum), intent(in) :: k
  type(vector) :: vk
  vk = k
  j = g * grg5vgf (gravbar, psi, vk)
end function p_grf
```

(Implementation of bispinor currents)+≡

```
pure function p_fgr (g, psibar, grav, k) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: g
  type(bispinor), intent(in) :: psibar
  type(vectorspinor), intent(in) :: grav
  type(momentum), intent(in) :: k
```

```

    type(vector) :: vk
    vk = k
    j = g * fg5gkgr (psibar, grav, vk)
end function p_fgr

<Declaration of bispinor currents>+≡
public :: f_potgr, f_sgr, f_pgr, f_vgr, f_vlgr, f_slgr, f_srgr, f_slrgr

<Implementation of bispinor currents>+≡
pure function f_potgr (g, phi, psi) result (phipsi)
    type(bispinor) :: phipsi
    complex(kind=default), intent(in) :: g
    complex(kind=default), intent(in) :: phi
    type(vectorspinor), intent(in) :: psi
    phipsi%a(1) = (g * phi) * (psi%psi(1)%a(3) - psi%psi(2)%a(4) + &
        ((0,1)*psi%psi(3)%a(4)) - psi%psi(4)%a(3))
    phipsi%a(2) = (g * phi) * (psi%psi(1)%a(4) - psi%psi(2)%a(3) - &
        ((0,1)*psi%psi(3)%a(3)) + psi%psi(4)%a(4))
    phipsi%a(3) = (g * phi) * (psi%psi(1)%a(1) + psi%psi(2)%a(2) - &
        ((0,1)*psi%psi(3)%a(2)) + psi%psi(4)%a(1))
    phipsi%a(4) = (g * phi) * (psi%psi(1)%a(2) + psi%psi(2)%a(1) + &
        ((0,1)*psi%psi(3)%a(1)) - psi%psi(4)%a(2))
end function f_potgr
    
```

The slashed notation:

$$\not{k} = \begin{pmatrix} 0 & 0 & k_- & -k^* \\ 0 & 0 & -k & k_+ \\ k_+ & k^* & 0 & 0 \\ k & k_- & 0 & 0 \end{pmatrix}, \quad \not{k}\gamma_5 = \begin{pmatrix} 0 & 0 & k_- & -k^* \\ 0 & 0 & -k & k_+ \\ -k_+ & -k^* & 0 & 0 \\ -k & -k_- & 0 & 0 \end{pmatrix} \quad (\text{X.72})$$

with $k_{\pm} = k_0 \pm k_3$, $k = k_1 + ik_2$, $k^* = k_1 - ik_2$. But note that \cdot^* is *not* complex conjugation for complex k_{μ} .

$$\gamma^0 \not{k} = \begin{pmatrix} k_+ & k^* & 0 & 0 \\ k & k_- & 0 & 0 \\ 0 & 0 & k_- & -k^* \\ 0 & 0 & -k & k_+ \end{pmatrix}, \quad \gamma^0 \not{k}\gamma_5 = \begin{pmatrix} -k_+ & -k^* & 0 & 0 \\ -k & -k_- & 0 & 0 \\ 0 & 0 & k_- & -k^* \\ 0 & 0 & -k & k_+ \end{pmatrix} \quad (\text{X.73a})$$

$$\gamma^1 \not{k} = \begin{pmatrix} k & k_- & 0 & 0 \\ k_+ & k^* & 0 & 0 \\ 0 & 0 & k & -k_+ \\ 0 & 0 & -k_- & k^* \end{pmatrix}, \quad \gamma^1 \not{k}\gamma_5 = \begin{pmatrix} -k & -k_- & 0 & 0 \\ -k_+ & -k^* & 0 & 0 \\ 0 & 0 & k & -k_+ \\ 0 & 0 & -k_- & k^* \end{pmatrix} \quad (\text{X.73b})$$

$$\gamma^2 \not{k} = \begin{pmatrix} -ik & -ik_- & 0 & 0 \\ ik_+ & ik^* & 0 & 0 \\ 0 & 0 & -ik & ik_+ \\ 0 & 0 & -ik_- & ik^* \end{pmatrix}, \quad \gamma^2 \not{k}\gamma_5 = \begin{pmatrix} ik & ik_- & 0 & 0 \\ -ik_+ & -ik^* & 0 & 0 \\ 0 & 0 & -ik & ik_+ \\ 0 & 0 & -ik_- & ik^* \end{pmatrix} \quad (\text{X.73c})$$

$$\gamma^3 \not{k} = \begin{pmatrix} k_+ & k^* & 0 & 0 \\ -k & -k_- & 0 & 0 \\ 0 & 0 & -k_- & k^* \\ 0 & 0 & -k & k_+ \end{pmatrix}, \quad \gamma^3 \not{k}\gamma_5 = \begin{pmatrix} -k_+ & -k^* & 0 & 0 \\ k & k_- & 0 & 0 \\ 0 & 0 & -k_- & k^* \\ 0 & 0 & -k & k_+ \end{pmatrix} \quad (\text{X.73d})$$

and

$$\not{k}\gamma^0 = \begin{pmatrix} k_- & -k^* & 0 & 0 \\ -k & k_+ & 0 & 0 \\ 0 & 0 & k_+ & k^* \\ 0 & 0 & k & k_- \end{pmatrix}, \quad \not{k}\gamma^0\gamma^5 = \begin{pmatrix} -k_- & k^* & 0 & 0 \\ k & -k_+ & 0 & 0 \\ 0 & 0 & k_+ & k^* \\ 0 & 0 & k & k_- \end{pmatrix} \quad (\text{X.74a})$$

$$\not{k}\gamma^1 = \begin{pmatrix} k^* & -k_- & 0 & 0 \\ -k_+ & k & 0 & 0 \\ 0 & 0 & k^* & k_+ \\ 0 & 0 & k_- & k \end{pmatrix}, \quad \not{k}\gamma^1\gamma^5 = \begin{pmatrix} -k^* & k_- & 0 & 0 \\ k_+ & -k & 0 & 0 \\ 0 & 0 & k^* & k_+ \\ 0 & 0 & k_- & k \end{pmatrix} \quad (\text{X.74b})$$

$$\not{k}\gamma^2 = \begin{pmatrix} ik^* & ik_- & 0 & 0 \\ -ik_+ & -ik & 0 & 0 \\ 0 & 0 & ik^* & -ik_+ \\ 0 & 0 & ik_- & -ik \end{pmatrix}, \quad \not{k}\gamma^2\gamma^5 = \begin{pmatrix} -ik^* & -ik_- & 0 & 0 \\ ik_+ & ik & 0 & 0 \\ 0 & 0 & ik^* & -ik_+ \\ 0 & 0 & ik_- & -ik \end{pmatrix} \quad (\text{X.74c})$$

$$\not{k}\gamma^3 = \begin{pmatrix} -k_- & -k^* & 0 & 0 \\ k & k_+ & 0 & 0 \\ 0 & 0 & k_+ & -k^* \\ 0 & 0 & k & -k_- \end{pmatrix}, \quad \not{k}\gamma^3\gamma^5 = \begin{pmatrix} k_- & k^* & 0 & 0 \\ -k & -k_+ & 0 & 0 \\ 0 & 0 & k_+ & -k^* \\ 0 & 0 & k & -k_- \end{pmatrix} \quad (\text{X.74d})$$

and

$$C\gamma^0\not{k} = \begin{pmatrix} k & k_- & 0 & 0 \\ -k_+ & -k^* & 0 & 0 \\ 0 & 0 & k & -k_+ \\ 0 & 0 & k_- & -k^* \end{pmatrix}, \quad C\gamma^0\not{k}\gamma^5 = \begin{pmatrix} -k & -k_- & 0 & 0 \\ k_+ & k^* & 0 & 0 \\ 0 & 0 & k & -k_+ \\ 0 & 0 & k_- & -k^* \end{pmatrix} \quad (\text{X.75a})$$

$$C\gamma^1\not{k} = \begin{pmatrix} k_+ & k^* & 0 & 0 \\ -k & -k_- & 0 & 0 \\ 0 & 0 & k_- & -k^* \\ 0 & 0 & k & -k_+ \end{pmatrix}, \quad C\gamma^1\not{k}\gamma^5 = \begin{pmatrix} -k_+ & -k^* & 0 & 0 \\ k & k_- & 0 & 0 \\ 0 & 0 & k_- & -k^* \\ 0 & 0 & k & -k_+ \end{pmatrix} \quad (\text{X.75b})$$

$$C\gamma^2\not{k} = \begin{pmatrix} ik_+ & ik^* & 0 & 0 \\ ik & ik_- & 0 & 0 \\ 0 & 0 & ik_- & -ik^* \\ 0 & 0 & -ik & ik_+ \end{pmatrix}, \quad C\gamma^2\not{k}\gamma^5 = \begin{pmatrix} -ik_+ & -ik^* & 0 & 0 \\ -ik & -ik_- & 0 & 0 \\ 0 & 0 & ik_- & -ik^* \\ 0 & 0 & -ik & ik_+ \end{pmatrix} \quad (\text{X.75c})$$

$$C\gamma^3\not{k} = \begin{pmatrix} -k & -k_- & 0 & 0 \\ -k_+ & -k^* & 0 & 0 \\ 0 & 0 & k & -k_+ \\ 0 & 0 & -k_- & k^* \end{pmatrix}, \quad C\gamma^3\not{k}\gamma^5 = \begin{pmatrix} k & k_- & 0 & 0 \\ k_+ & k^* & 0 & 0 \\ 0 & 0 & k & -k_+ \\ 0 & 0 & -k_- & k^* \end{pmatrix} \quad (\text{X.75d})$$

and

$$C\not{k}\gamma^0 = \begin{pmatrix} -k & k^+ & 0 & 0 \\ -k_- & k^* & 0 & 0 \\ 0 & 0 & -k & -k_- \\ 0 & 0 & k_+ & k^* \end{pmatrix}, \quad C\not{k}\gamma^0\gamma^5 = \begin{pmatrix} k & -k_+ & 0 & 0 \\ k_- & -k^* & 0 & 0 \\ 0 & 0 & -k & -k_- \\ 0 & 0 & k_+ & k^* \end{pmatrix} \quad (\text{X.76a})$$

$$C\not{k}\gamma^1 = \begin{pmatrix} -k_+ & k & 0 & 0 \\ -k^* & k_- & 0 & 0 \\ 0 & 0 & -k_- & -k \\ 0 & 0 & k^* & k_+ \end{pmatrix}, \quad C\not{k}\gamma^1\gamma^5 = \begin{pmatrix} k_+ & -k & 0 & 0 \\ k^* & -k_- & 0 & 0 \\ 0 & 0 & -k_- & -k \\ 0 & 0 & k^* & k_+ \end{pmatrix} \quad (\text{X.76b})$$

$$C\not{k}\gamma^2 = \begin{pmatrix} -ik_+ & -ik & 0 & 0 \\ -ik^* & -ik_- & 0 & 0 \\ 0 & 0 & -ik_- & ik \\ 0 & 0 & ik^* & -ik_+ \end{pmatrix}, \quad C\not{k}\gamma^2\gamma^5 = \begin{pmatrix} ik_+ & ik & 0 & 0 \\ ik^* & ik_- & 0 & 0 \\ 0 & 0 & -ik_- & ik \\ 0 & 0 & ik^* & -ik_+ \end{pmatrix} \quad (\text{X.76c})$$

$$C\not{k}\gamma^3 = \begin{pmatrix} k & k_+ & 0 & 0 \\ k_- & k^* & 0 & 0 \\ 0 & 0 & -k & k_- \\ 0 & 0 & k_+ & -k^* \end{pmatrix}, \quad C\not{k}\gamma^3\gamma^5 = \begin{pmatrix} -k & -k_+ & 0 & 0 \\ -k_- & -k^* & 0 & 0 \\ 0 & 0 & -k & k_- \\ 0 & 0 & k_+ & -k^* \end{pmatrix} \quad (\text{X.76d})$$

```

(Implementation of bispinor currents)+≡
pure function fgvr (psi, k) result (kpsi)
  type(bispinor) :: kpsi
  complex(kind=default) :: kp, km, k12, k12s
  type(vector), intent(in) :: k
  type(vectorspinor), intent(in) :: psi
  kp = k%t + k%x(3)
  km = k%t - k%x(3)
  k12 = k%x(1) + (0,1)*k%x(2)
  k12s = k%x(1) - (0,1)*k%x(2)
  kpsi%a(1) = kp * psi%psi(1)%a(1) + k12s * psi%psi(1)%a(2) &
    - k12 * psi%psi(2)%a(1) - km * psi%psi(2)%a(2) &
    + (0,1) * k12 * psi%psi(3)%a(1) + (0,1) * km * psi%psi(3)%a(2) &
    - kp * psi%psi(4)%a(1) - k12s * psi%psi(4)%a(2)
  kpsi%a(2) = k12 * psi%psi(1)%a(1) + km * psi%psi(1)%a(2) &
    - kp * psi%psi(2)%a(1) - k12s * psi%psi(2)%a(2) &
    - (0,1) * kp * psi%psi(3)%a(1) - (0,1) * k12s * psi%psi(3)%a(2) &
    + k12 * psi%psi(4)%a(1) + km * psi%psi(4)%a(2)
  kpsi%a(3) = km * psi%psi(1)%a(3) - k12s * psi%psi(1)%a(4) &
    - k12 * psi%psi(2)%a(3) + kp * psi%psi(2)%a(4) &
    + (0,1) * k12 * psi%psi(3)%a(3) - (0,1) * kp * psi%psi(3)%a(4) &
    + km * psi%psi(4)%a(3) - k12s * psi%psi(4)%a(4)
  kpsi%a(4) = - k12 * psi%psi(1)%a(3) + kp * psi%psi(1)%a(4) &
    + km * psi%psi(2)%a(3) - k12s * psi%psi(2)%a(4) &
    + (0,1) * km * psi%psi(3)%a(3) - (0,1) * k12s * psi%psi(3)%a(4) &
    + k12 * psi%psi(4)%a(3) - kp * psi%psi(4)%a(4)
end function fgvr

```

(Implementation of bispinor currents)+≡

```

pure function f_sgr (g, phi, psi, k) result (phipsi)
  type(bispinor) :: phipsi
  complex(kind=default), intent(in) :: g
  complex(kind=default), intent(in) :: phi
  type(momentum), intent(in) :: k
  type(vectorspinor), intent(in) :: psi
  type(vector) :: vk
  vk = k
  phipsi = (g * phi) * fgvgr (psi, vk)
end function f_sgr

<Implementation of bispinor currents>+≡
pure function f_slgr (gl, phi, psi, k) result (phipsi)
  type(bispinor) :: phipsi
  complex(kind=default), intent(in) :: gl
  complex(kind=default), intent(in) :: phi
  type(momentum), intent(in) :: k
  type(vectorspinor), intent(in) :: psi
  phipsi = f_sgr (gl, phi, psi, k)
  phipsi%a(3:4) = 0
end function f_slgr

<Implementation of bispinor currents>+≡
pure function f_srgr (gr, phi, psi, k) result (phipsi)
  type(bispinor) :: phipsi
  complex(kind=default), intent(in) :: gr
  complex(kind=default), intent(in) :: phi
  type(momentum), intent(in) :: k
  type(vectorspinor), intent(in) :: psi
  phipsi = f_sgr (gr, phi, psi, k)
  phipsi%a(1:2) = 0
end function f_srgr

<Implementation of bispinor currents>+≡
pure function f_slrgr (gl, gr, phi, psi, k) result (phipsi)
  type(bispinor) :: phipsi, phipsi_l, phipsi_r
  complex(kind=default), intent(in) :: gl, gr
  complex(kind=default), intent(in) :: phi
  type(momentum), intent(in) :: k
  type(vectorspinor), intent(in) :: psi
  phipsi_l = f_slgr (gl, phi, psi, k)
  phipsi_r = f_srgr (gr, phi, psi, k)
  phipsi%a(1:2) = phipsi_l%a(1:2)
  phipsi%a(3:4) = phipsi_r%a(3:4)
end function f_slrgr

<Implementation of bispinor currents>+≡
pure function fgvg5gr (psi, k) result (kpsi)
  type(bispinor) :: kpsi
  type(vector), intent(in) :: k
  type(vectorspinor), intent(in) :: psi
  type(bispinor) :: kpsi_dum
  kpsi_dum = fgvgr (psi, k)
  kpsi%a(1:2) = - kpsi_dum%a(1:2)
  kpsi%a(3:4) = kpsi_dum%a(3:4)
end function fgvg5gr

```

```

<Implementation of bispinor currents>+=
pure function f_pgr (g, phi, psi, k) result (phipsi)
    type(bispinor) :: phipsi
    complex(kind=default), intent(in) :: g
    complex(kind=default), intent(in) :: phi
    type(momentum), intent(in) :: k
    type(vectorspinor), intent(in) :: psi
    type(vector) :: vk
    vk = k
    phipsi = (g * phi) * fgvg5gr (psi, vk)
end function f_pgr
    
```

The needed construction of gamma matrices involving the commutator of two gamma matrices. For the slashed terms we use as usual the abbreviations $k_{\pm} = k_0 \pm k_3$, $k = k_1 + ik_2$, $k^* = k_1 - ik_2$ and analogous expressions for the vector v^{μ} . We remind you that $*$ is *not* complex conjugation for complex k_{μ} . Furthermore we introduce (in what follows the brackets around the vector indices have the usual meaning of antisymmetrizing with respect to the indices inside the brackets, here without a factor two in the denominator)

$$a_+ = k_+ v_- + k v^* - k_- v_+ - k^* v = 2(k_{[3} v_{0]} + ik_{[2} v_{1]}) \quad (\text{X.77a})$$

$$a_- = k_- v_+ + k v^* - k_+ v_- - k^* v = 2(-k_{[3} v_{0]} + ik_{[2} v_{1]}) \quad (\text{X.77b})$$

$$b_+ = 2(k_+ v - k v_+) = 2(k_{[0} v_{1]} + k_{[3} v_{1]} + ik_{[0} v_{2]} + ik_{[3} v_{2]}) \quad (\text{X.77c})$$

$$b_- = 2(k_- v - k v_-) = 2(k_{[0} v_{1]} - k_{[3} v_{1]} + ik_{[0} v_{2]} - ik_{[3} v_{2]}) \quad (\text{X.77d})$$

$$b_{+*} = 2(k_+ v^* - k^* v_+) = 2(k_{[0} v_{1]} + k_{[3} v_{1]} - ik_{[0} v_{2]} - ik_{[3} v_{2]}) \quad (\text{X.77e})$$

$$b_{-*} = 2(k_- v^* - k^* v_-) = 2(k_{[0} v_{1]} - k_{[3} v_{1]} - ik_{[0} v_{2]} + ik_{[3} v_{2]}) \quad (\text{X.77f})$$

Of course, one could introduce a more advanced notation, but we don't want to become confused.

$$[\not{k}, \gamma^0] = \begin{pmatrix} -2k_3 & -2k^* & 0 & 0 \\ -2k & 2k_3 & 0 & 0 \\ 0 & 0 & 2k_3 & 2k^* \\ 0 & 0 & 2k & -2k_3 \end{pmatrix} \quad (\text{X.78a})$$

$$[\not{k}, \gamma^1] = \begin{pmatrix} -2ik_2 & -2k_- & 0 & 0 \\ -2k_+ & 2ik_2 & 0 & 0 \\ 0 & 0 & -2ik_2 & 2k_+ \\ 0 & 0 & 2k_- & 2ik_2 \end{pmatrix} \quad (\text{X.78b})$$

$$[\not{k}, \gamma^2] = \begin{pmatrix} 2ik_1 & 2ik_- & 0 & 0 \\ -2ik_+ & -2ik_1 & 0 & 0 \\ 0 & 0 & 2ik_1 & -2ik_+ \\ 0 & 0 & 2ik_- & -2ik_1 \end{pmatrix} \quad (\text{X.78c})$$

$$[\not{k}, \gamma^3] = \begin{pmatrix} -2k_0 & -2k^* & 0 & 0 \\ 2k & 2k_0 & 0 & 0 \\ 0 & 0 & 2k_0 & -2k^* \\ 0 & 0 & 2k & -2k_0 \end{pmatrix} \quad (\text{X.78d})$$

$$[k, V] = \begin{pmatrix} a_- & b_{-*} & 0 & 0 \\ b_+ & -a_- & 0 & 0 \\ 0 & 0 & a_+ & -b_{+*} \\ 0 & 0 & -b_- & -a_+ \end{pmatrix} \quad (\text{X.78e})$$

$$\gamma^5 \gamma^0 [k, V] = \begin{pmatrix} 0 & 0 & -a_+ & b_{+*} \\ 0 & 0 & b_- & a_+ \\ a_- & b_{-*} & 0 & 0 \\ b_+ & -a_- & 0 & 0 \end{pmatrix} \quad (\text{X.78f})$$

$$\gamma^5 \gamma^1 [k, V] = \begin{pmatrix} 0 & 0 & b_- & a_+ \\ 0 & 0 & -a_+ & b_{+*} \\ -b_+ & a_- & 0 & 0 \\ -a_- & -b_{-*} & 0 & 0 \end{pmatrix} \quad (\text{X.78g})$$

$$\gamma^5 \gamma^2 [k, V] = \begin{pmatrix} 0 & 0 & -ib_- & -ia_+ \\ 0 & 0 & -ia_+ & ib_{+*} \\ ib_+ & -ia_- & 0 & 0 \\ -ia_- & -ib_{-*} & 0 & 0 \end{pmatrix} \quad (\text{X.78h})$$

$$\gamma^5 \gamma^3 [k, V] = \begin{pmatrix} 0 & 0 & -a_+ & b_{+*} \\ 0 & 0 & -b_- & -a_+ \\ -a_- & -b_{-*} & 0 & 0 \\ b_+ & -a_- & 0 & 0 \end{pmatrix} \quad (\text{X.78i})$$

and

$$[k, V] \gamma^0 \gamma^5 = \begin{pmatrix} 0 & 0 & a_- & b_{-*} \\ 0 & 0 & b_+ & -a_- \\ -a_+ & b_{+*} & 0 & 0 \\ b_- & a_+ & 0 & 0 \end{pmatrix} \quad (\text{X.79a})$$

$$[k, V] \gamma^1 \gamma^5 = \begin{pmatrix} 0 & 0 & b_{-*} & a_- \\ 0 & 0 & -a_- & b_+ \\ -b_{+*} & a_+ & 0 & 0 \\ -a_+ & -b_- & 0 & 0 \end{pmatrix} \quad (\text{X.79b})$$

$$[k, V] \gamma^2 \gamma^5 = \begin{pmatrix} 0 & 0 & ib_{-*} & -ia_- \\ 0 & 0 & -ia_- & -ib_+ \\ -ib_{+*} & -ia_+ & 0 & 0 \\ -ia_+ & ib_- & 0 & 0 \end{pmatrix} \quad (\text{X.79c})$$

$$[k, V] \gamma^3 \gamma^5 = \begin{pmatrix} 0 & 0 & a_- & -b_{-*} \\ 0 & 0 & b_+ & a_- \\ a_+ & b_{+*} & 0 & 0 \\ -b_- & a_+ & 0 & 0 \end{pmatrix} \quad (\text{X.79d})$$

In what follows l always means twice the value of k , e.g. $l_+ = 2k_+$. We use the abbreviation $C^{\mu\nu} \equiv C[k, \gamma^\mu] \gamma^\nu \gamma^5$.

$$C^{00} = \begin{pmatrix} 0 & 0 & -l & -l_3 \\ 0 & 0 & l_3 & l^* \\ l & -l_3 & 0 & 0 \\ -l_3 & -l^* & 0 & 0 \end{pmatrix}, \quad C^{20} = \begin{pmatrix} 0 & 0 & -il_+ & -il_1 \\ 0 & 0 & -il_1 & -il_- \\ il_- & -il_1 & 0 & 0 \\ -il_1 & il_+ & 0 & 0 \end{pmatrix} \quad (\text{X.80a})$$

$$C^{01} = \begin{pmatrix} 0 & 0 & l_3 & -l \\ 0 & 0 & l^* & l_3 \\ l_3 & -l & 0 & 0 \\ l^* & l_3 & 0 & 0 \end{pmatrix}, \quad C^{21} = \begin{pmatrix} 0 & 0 & -il_1 & -il_+ \\ 0 & 0 & -il_- & -il_1 \\ il_1 & -il_- & 0 & 0 \\ -il_+ & il_1 & 0 & 0 \end{pmatrix} \quad (\text{X.80b})$$

$$C^{02} = \begin{pmatrix} 0 & 0 & il_3 & il \\ 0 & 0 & il^* & -il_3 \\ il_3 & il & 0 & 0 \\ il^* & -il_3 & 0 & 0 \end{pmatrix}, \quad C^{22} = \begin{pmatrix} 0 & 0 & l_1 & -l_+ \\ 0 & 0 & l_- & -l_1 \\ -l_1 & -l_- & 0 & 0 \\ l_+ & l_1 & 0 & 0 \end{pmatrix} \quad (\text{X.80c})$$

$$C^{03} = \begin{pmatrix} 0 & 0 & -l & -l_3 \\ 0 & 0 & l_3 & -l^* \\ -l & -l_3 & 0 & 0 \\ l_3 & -l^* & 0 & 0 \end{pmatrix}, \quad C^{23} = \begin{pmatrix} 0 & 0 & -il_+ & il_1 \\ 0 & 0 & -il_1 & il_- \\ -il_- & -il_1 & 0 & 0 \\ il_1 & il_+ & 0 & 0 \end{pmatrix} \quad (\text{X.80d})$$

$$C^{10} = \begin{pmatrix} 0 & 0 & -l_+ & il_2 \\ 0 & 0 & il_2 & l_- \\ l_- & il_2 & 0 & 0 \\ il_2 & -l_+ & 0 & 0 \end{pmatrix}, \quad C^{30} = \begin{pmatrix} 0 & 0 & l & l_0 \\ 0 & 0 & l_0 & l^* \\ l & -l_0 & 0 & 0 \\ -l_0 & l^* & 0 & 0 \end{pmatrix} \quad (\text{X.80e})$$

$$C^{11} = \begin{pmatrix} 0 & 0 & il_2 & -l_+ \\ 0 & 0 & l_- & il_2 \\ -il_2 & -l_- & 0 & 0 \\ l_+ & -il_2 & 0 & 0 \end{pmatrix}, \quad C^{31} = \begin{pmatrix} 0 & 0 & l_0 & l \\ 0 & 0 & l^* & l_0 \\ l_0 & -l & 0 & 0 \\ -l^* & l_0 & 0 & 0 \end{pmatrix} \quad (\text{X.80f})$$

$$C^{12} = \begin{pmatrix} 0 & 0 & -l_2 & il_+ \\ 0 & 0 & il_- & l_2 \\ l_2 & il_- & 0 & 0 \\ il_+ & -l_2 & 0 & 0 \end{pmatrix}, \quad C^{32} = \begin{pmatrix} 0 & 0 & il_0 & -il \\ 0 & 0 & il^* & -il_0 \\ il_0 & il & 0 & 0 \\ -il^* & -il_0 & 0 & 0 \end{pmatrix} \quad (\text{X.80g})$$

$$C^{13} = \begin{pmatrix} 0 & 0 & -l_+ & -il_2 \\ 0 & 0 & il_2 & -l_- \\ -l_- & il_2 & 0 & 0 \\ -il_2 & -l_+ & 0 & 0 \end{pmatrix}, \quad C^{33} = \begin{pmatrix} 0 & 0 & l & -l_0 \\ 0 & 0 & l_0 & -l^* \\ -l & -l_0 & 0 & 0 \\ l_0 & l^* & 0 & 0 \end{pmatrix} \quad (\text{X.80h})$$

and, with the abbreviation $\tilde{C}^{\mu\nu} \equiv C\gamma^5\gamma^\nu[k, \gamma^\mu]$ (note the reversed order of the indices!)

$$\tilde{C}^{00} = \begin{pmatrix} 0 & 0 & -l & l_3 \\ 0 & 0 & l_3 & l^* \\ l & -l_3 & 0 & 0 \\ -l_3 & -l^* & 0 & 0 \end{pmatrix}, \quad \tilde{C}^{20} = \begin{pmatrix} 0 & 0 & -il_- & il_1 \\ 0 & 0 & il_1 & -il_+ \\ il_+ & il_1 & 0 & 0 \\ il_1 & il_- & 0 & 0 \end{pmatrix} \quad (\text{X.81a})$$

$$\tilde{C}^{01} = \begin{pmatrix} 0 & 0 & -l_3 & -l^* \\ 0 & 0 & l & -l_3 \\ -l_3 & -l^* & 0 & 0 \\ l & -l_3 & 0 & 0 \end{pmatrix}, \quad \tilde{C}^{21} = \begin{pmatrix} 0 & 0 & -il_1 & il_+ \\ 0 & 0 & il_- & -il_1 \\ il_1 & il_- & 0 & 0 \\ il_+ & il_1 & 0 & 0 \end{pmatrix} \quad (\text{X.81b})$$

$$\tilde{C}^{02} = \begin{pmatrix} 0 & 0 & -il_3 & -il^* \\ 0 & 0 & -il & il_3 \\ -il_3 & -il^* & 0 & 0 \\ -il & il_3 & 0 & 0 \end{pmatrix}, \quad \tilde{C}^{22} = \begin{pmatrix} 0 & 0 & l_1 & -l_+ \\ 0 & 0 & l_- & -l_1 \\ -l_1 & -l_- & 0 & 0 \\ l_+ & l_1 & 0 & 0 \end{pmatrix} \quad (\text{X.81c})$$

$$\tilde{C}^{03} = \begin{pmatrix} 0 & 0 & l & -l_3 \\ 0 & 0 & l_3 & l^* \\ l & -l_3 & 0 & 0 \\ l_3 & l^* & 0 & 0 \end{pmatrix}, \quad \tilde{C}^{23} = \begin{pmatrix} 0 & 0 & il_- & -il_1 \\ 0 & 0 & il_1 & -il_+ \\ il_+ & il_1 & 0 & 0 \\ -il_1 & -il_- & 0 & 0 \end{pmatrix} \quad (\text{X.81d})$$

$$\tilde{C}^{10} = \begin{pmatrix} 0 & 0 & -l_- & -il_2 \\ 0 & 0 & -il_2 & l_+ \\ l_+ & -il_2 & 0 & 0 \\ -il_2 & -l_- & 0 & 0 \end{pmatrix}, \quad \tilde{C}^{30} = \begin{pmatrix} 0 & 0 & -l & l_0 \\ 0 & 0 & l_0 & -l^* \\ -l & -l_0 & 0 & 0 \\ -l_0 & -l^* & 0 & 0 \end{pmatrix} \quad (\text{X.81e})$$

$$\tilde{C}^{11} = \begin{pmatrix} 0 & 0 & il_2 & -l_+ \\ 0 & 0 & l_- & il_2 \\ -il_2 & -l_- & 0 & 0 \\ l_+ & -il_2 & 0 & 0 \end{pmatrix}, \quad \tilde{C}^{31} = \begin{pmatrix} 0 & 0 & -l_0 & l^* \\ 0 & 0 & l & -l_0 \\ -l_0 & -l^* & 0 & 0 \\ -l & -l_0 & 0 & 0 \end{pmatrix} \quad (\text{X.81f})$$

$$\tilde{C}^{12} = \begin{pmatrix} 0 & 0 & -l_2 & -il_+ \\ 0 & 0 & -il_- & l_2 \\ l_2 & -il_- & 0 & 0 \\ -il_+ & -l_2 & 0 & 0 \end{pmatrix}, \quad \tilde{C}^{32} = \begin{pmatrix} 0 & 0 & -il_0 & il^* \\ 0 & 0 & -il & il_0 \\ -il_0 & -il^* & 0 & 0 \\ il & il_0 & 0 & 0 \end{pmatrix} \quad (\text{X.81g})$$

$$\tilde{C}^{13} = \begin{pmatrix} 0 & 0 & l_- & il_2 \\ 0 & 0 & -il_2 & l_+ \\ l_+ & -il_2 & 0 & 0 \\ il_2 & l_- & 0 & 0 \end{pmatrix}, \quad \tilde{C}^{33} = \begin{pmatrix} 0 & 0 & l & -l_0 \\ 0 & 0 & l_0 & -l^* \\ -l & -l_0 & 0 & 0 \\ l_0 & l^* & 0 & 0 \end{pmatrix} \quad (\text{X.81h})$$

(Implementation of bispinor currents)+≡

```
pure function fggvgr (v, psi, k) result (psikv)
  type(bispinor) :: psikv
  type(vectorspinor), intent(in) :: psi
  type(vector), intent(in) :: v, k
  complex(kind=default) :: kv30, kv21, kv01, kv31, kv02, kv32
  complex(kind=default) :: ap, am, bp, bm, bps, bms
  kv30 = k%x(3) * v%t - k%t * v%x(3)
  kv21 = (0,1) * (k%x(2) * v%x(1) - k%x(1) * v%x(2))
  kv01 = k%t * v%x(1) - k%x(1) * v%t
  kv31 = k%x(3) * v%x(1) - k%x(1) * v%x(3)
  kv02 = (0,1) * (k%t * v%x(2) - k%x(2) * v%t)
  kv32 = (0,1) * (k%x(3) * v%x(2) - k%x(2) * v%x(3))
  ap = 2 * (kv30 + kv21)
  am = 2 * (-kv30 + kv21)
  bp = 2 * (kv01 + kv31 + kv02 + kv32)
  bm = 2 * (kv01 - kv31 + kv02 - kv32)
  bps = 2 * (kv01 + kv31 - kv02 - kv32)
  bms = 2 * (kv01 - kv31 - kv02 + kv32)
```

```

psikv%a(1) = (-ap) * psi%psi(1)%a(3) + bps * psi%psi(1)%a(4) &
+ (-bm) * psi%psi(2)%a(3) + (-ap) * psi%psi(2)%a(4) &
+ (0,1) * (bm * psi%psi(3)%a(3) + ap * psi%psi(3)%a(4)) &
+ ap * psi%psi(4)%a(3) + (-bps) * psi%psi(4)%a(4)
psikv%a(2) = bm * psi%psi(1)%a(3) + ap * psi%psi(1)%a(4) &
+ ap * psi%psi(2)%a(3) + (-bps) * psi%psi(2)%a(4) &
+ (0,1) * (ap * psi%psi(3)%a(3) - bps * psi%psi(3)%a(4)) &
+ bm * psi%psi(4)%a(3) + ap * psi%psi(4)%a(4)
psikv%a(3) = am * psi%psi(1)%a(1) + bms * psi%psi(1)%a(2) &
+ bp * psi%psi(2)%a(1) + (-am) * psi%psi(2)%a(2) &
+ (0,-1) * (bp * psi%psi(3)%a(1) + (-am) * psi%psi(3)%a(2)) &
+ am * psi%psi(4)%a(1) + bms * psi%psi(4)%a(2)
psikv%a(4) = bp * psi%psi(1)%a(1) + (-am) * psi%psi(1)%a(2) &
+ am * psi%psi(2)%a(1) + bms * psi%psi(2)%a(2) &
+ (0,1) * (am * psi%psi(3)%a(1) + bms * psi%psi(3)%a(2)) &
+ (-bp) * psi%psi(4)%a(1) + am * psi%psi(4)%a(2)
end function fggvgr

<Implementation of bispinor currents>+=
pure function f_vgr (g, v, psi, k) result (psikkkv)
    type(bispinor) :: psikkkv
    type(vectorspinor), intent(in) :: psi
    type(vector), intent(in) :: v
    type(momentum), intent(in) :: k
    complex(kind=default), intent(in) :: g
    type(vector) :: vk
    vk = k
    psikkkv = g * (fggvgr (v, psi, vk))
end function f_vgr

<Implementation of bispinor currents>+=
pure function f_vlgr (gl, gr, v, psi, k) result (psikv)
    type(bispinor) :: psikv
    type(vectorspinor), intent(in) :: psi
    type(vector), intent(in) :: v
    type(momentum), intent(in) :: k
    complex(kind=default), intent(in) :: gl, gr
    type(vector) :: vk
    vk = k
    psikv = fggvgr (v, psi, vk)
    psikv%a(1:2) = gl * psikv%a(1:2)
    psikv%a(3:4) = gr * psikv%a(3:4)
end function f_vlgr

<Declaration of bispinor currents>+=
public :: gr_potf, gr_sf, gr_pf, gr_vf, gr_vlrf, gr_slf, gr_srf, gr_slrf

<Implementation of bispinor currents>+=
pure function gr_potf (g, phi, psi) result (phipsi)
    type(vectorspinor) :: phipsi
    complex(kind=default), intent(in) :: g
    complex(kind=default), intent(in) :: phi
    type(bispinor), intent(in) :: psi
    phipsi%psi(1)%a(1) = (g * phi) * psi%a(3)
    phipsi%psi(1)%a(2) = (g * phi) * psi%a(4)
    phipsi%psi(1)%a(3) = (g * phi) * psi%a(1)

```

```

phipsi%psi(1)%a(4) = (g * phi) * psi%a(2)
phipsi%psi(2)%a(1) = (g * phi) * psi%a(4)
phipsi%psi(2)%a(2) = (g * phi) * psi%a(3)
phipsi%psi(2)%a(3) = ((-g) * phi) * psi%a(2)
phipsi%psi(2)%a(4) = ((-g) * phi) * psi%a(1)
phipsi%psi(3)%a(1) = ((0,-1) * g * phi) * psi%a(4)
phipsi%psi(3)%a(2) = ((0,1) * g * phi) * psi%a(3)
phipsi%psi(3)%a(3) = ((0,1) * g * phi) * psi%a(2)
phipsi%psi(3)%a(4) = ((0,-1) * g * phi) * psi%a(1)
phipsi%psi(4)%a(1) = (g * phi) * psi%a(3)
phipsi%psi(4)%a(2) = ((-g) * phi) * psi%a(4)
phipsi%psi(4)%a(3) = ((-g) * phi) * psi%a(1)
phipsi%psi(4)%a(4) = (g * phi) * psi%a(2)
end function gr_potf

```

(Implementation of bispinor currents)+≡

```

pure function grkgf (psi, k) result (kpsi)
  type(vectorspinor) :: kpsi
  complex(kind=default) :: kp, km, k12, k12s
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: k
  kp = k%t + k%x(3)
  km = k%t - k%x(3)
  k12 = k%x(1) + (0,1)*k%x(2)
  k12s = k%x(1) - (0,1)*k%x(2)
  kpsi%psi(1)%a(1) = km * psi%a(1) - k12s * psi%a(2)
  kpsi%psi(1)%a(2) = (-k12) * psi%a(1) + kp * psi%a(2)
  kpsi%psi(1)%a(3) = kp * psi%a(3) + k12s * psi%a(4)
  kpsi%psi(1)%a(4) = k12 * psi%a(3) + km * psi%a(4)
  kpsi%psi(2)%a(1) = k12s * psi%a(1) - km * psi%a(2)
  kpsi%psi(2)%a(2) = (-kp) * psi%a(1) + k12 * psi%a(2)
  kpsi%psi(2)%a(3) = k12s * psi%a(3) + kp * psi%a(4)
  kpsi%psi(2)%a(4) = km * psi%a(3) + k12 * psi%a(4)
  kpsi%psi(3)%a(1) = (0,1) * (k12s * psi%a(1) + km * psi%a(2))
  kpsi%psi(3)%a(2) = (0,-1) * (kp * psi%a(1) + k12 * psi%a(2))
  kpsi%psi(3)%a(3) = (0,1) * (k12s * psi%a(3) - kp * psi%a(4))
  kpsi%psi(3)%a(4) = (0,1) * (km * psi%a(3) - k12 * psi%a(4))
  kpsi%psi(4)%a(1) = -(km * psi%a(1) + k12s * psi%a(2))
  kpsi%psi(4)%a(2) = k12 * psi%a(1) + kp * psi%a(2)
  kpsi%psi(4)%a(3) = kp * psi%a(3) - k12s * psi%a(4)
  kpsi%psi(4)%a(4) = k12 * psi%a(3) - km * psi%a(4)
end function grkgf

```

(Implementation of bispinor currents)+≡

```

pure function gr_sf (g, phi, psi, k) result (phipsi)
  type(vectorspinor) :: phipsi
  complex(kind=default), intent(in) :: g
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi
  type(momentum), intent(in) :: k
  type(vector) :: vk
  vk = k
  phipsi = (g * phi) * grkgf (psi, vk)
end function gr_sf

```

(Implementation of bispinor currents)+≡

```

pure function gr_slf (gl, phi, psi, k) result (phipsi)
  type(vectorspinor) :: phipsi
  complex(kind=default), intent(in) :: gl
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_l
  type(momentum), intent(in) :: k
  psi_l%a(1:2) = psi%a(1:2)
  psi_l%a(3:4) = 0
  phipsi = gr_sf (gl, phi, psi_l, k)
end function gr_slf

<Implementation of bispinor currents>+≡
pure function gr_srf (gr, phi, psi, k) result (phipsi)
  type(vectorspinor) :: phipsi
  complex(kind=default), intent(in) :: gr
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_r
  type(momentum), intent(in) :: k
  psi_r%a(1:2) = 0
  psi_r%a(3:4) = psi%a(3:4)
  phipsi = gr_sf (gr, phi, psi_r, k)
end function gr_srf

<Implementation of bispinor currents>+≡
pure function gr_slrf (gl, gr, phi, psi, k) result (phipsi)
  type(vectorspinor) :: phipsi
  complex(kind=default), intent(in) :: gl, gr
  complex(kind=default), intent(in) :: phi
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_r
  type(momentum), intent(in) :: k
  phipsi = gr_slf (gl, phi, psi, k) + gr_srf (gr, phi, psi, k)
end function gr_slrf

<Implementation of bispinor currents>+≡
pure function grkggf (psi, k) result (kpsi)
  type(vectorspinor) :: kpsi
  complex(kind=default) :: kp, km, k12, k12s
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: k
  kp = k%t + k%x(3)
  km = k%t - k%x(3)
  k12 = k%x(1) + (0,1)*k%x(2)
  k12s = k%x(1) - (0,1)*k%x(2)
  kpsi%psi(1)%a(1) = (-km) * psi%a(1) + k12s * psi%a(2)
  kpsi%psi(1)%a(2) = k12 * psi%a(1) - kp * psi%a(2)
  kpsi%psi(1)%a(3) = kp * psi%a(3) + k12s * psi%a(4)
  kpsi%psi(1)%a(4) = k12 * psi%a(3) + km * psi%a(4)
  kpsi%psi(2)%a(1) = (-k12s) * psi%a(1) + km * psi%a(2)
  kpsi%psi(2)%a(2) = kp * psi%a(1) - k12 * psi%a(2)
  kpsi%psi(2)%a(3) = k12s * psi%a(3) + kp * psi%a(4)
  kpsi%psi(2)%a(4) = km * psi%a(3) + k12 * psi%a(4)
  kpsi%psi(3)%a(1) = (0,-1) * (k12s * psi%a(1) + km * psi%a(2))
  kpsi%psi(3)%a(2) = (0,1) * (kp * psi%a(1) + k12 * psi%a(2))

```

```

kpsi%psi(3)%a(3) = (0,1) * (k12s * psi%a(3) - kp * psi%a(4))
kpsi%psi(3)%a(4) = (0,1) * (km * psi%a(3) - k12 * psi%a(4))
kpsi%psi(4)%a(1) = km * psi%a(1) + k12s * psi%a(2)
kpsi%psi(4)%a(2) = -(k12 * psi%a(1) + kp * psi%a(2))
kpsi%psi(4)%a(3) = kp * psi%a(3) - k12s * psi%a(4)
kpsi%psi(4)%a(4) = k12 * psi%a(3) - km * psi%a(4)
end function grkggf

```

(Implementation of bispinor currents)+≡

```

pure function gr_pf (g, phi, psi, k) result (phipsi)
    type(vectorspinor) :: phipsi
    complex(kind=default), intent(in) :: g
    complex(kind=default), intent(in) :: phi
    type(bispinor), intent(in) :: psi
    type(momentum), intent(in) :: k
    type(vector) :: vk
    vk = k
    phipsi = (g * phi) * grkggf (psi, vk)
end function gr_pf

```

(Implementation of bispinor currents)+≡

```

pure function grkkggf (v, psi, k) result (psikv)
    type(vectorspinor) :: psikv
    type(bispinor), intent(in) :: psi
    type(vector), intent(in) :: v, k
    complex(kind=default) :: kv30, kv21, kv01, kv31, kv02, kv32
    complex(kind=default) :: ap, am, bp, bm, bps, bms, imago
    imago = (0.0_default, 1.0_default)
    kv30 = k%x(3) * v%t - k%t * v%x(3)
    kv21 = imago * (k%x(2) * v%x(1) - k%x(1) * v%x(2))
    kv01 = k%t * v%x(1) - k%x(1) * v%t
    kv31 = k%x(3) * v%x(1) - k%x(1) * v%x(3)
    kv02 = imago * (k%t * v%x(2) - k%x(2) * v%t)
    kv32 = imago * (k%x(3) * v%x(2) - k%x(2) * v%x(3))
    ap = 2 * (kv30 + kv21)
    am = 2 * ((-kv30) + kv21)
    bp = 2 * (kv01 + kv31 + kv02 + kv32)
    bm = 2 * (kv01 - kv31 + kv02 - kv32)
    bps = 2 * (kv01 + kv31 - kv02 - kv32)
    bms = 2 * (kv01 - kv31 - kv02 + kv32)
    psikv%psi(1)%a(1) = am * psi%a(3) + bms * psi%a(4)
    psikv%psi(1)%a(2) = bp * psi%a(3) + (-am) * psi%a(4)
    psikv%psi(1)%a(3) = (-ap) * psi%a(1) + bps * psi%a(2)
    psikv%psi(1)%a(4) = bm * psi%a(1) + ap * psi%a(2)
    psikv%psi(2)%a(1) = bms * psi%a(3) + am * psi%a(4)
    psikv%psi(2)%a(2) = (-am) * psi%a(3) + bp * psi%a(4)
    psikv%psi(2)%a(3) = (-bps) * psi%a(1) + ap * psi%a(2)
    psikv%psi(2)%a(4) = (-ap) * psi%a(1) + (-bm) * psi%a(2)
    psikv%psi(3)%a(1) = imago * (bms * psi%a(3) - am * psi%a(4))
    psikv%psi(3)%a(2) = (-imago) * (am * psi%a(3) + bp * psi%a(4))
    psikv%psi(3)%a(3) = (-imago) * (bps * psi%a(1) + ap * psi%a(2))
    psikv%psi(3)%a(4) = imago * ((-ap) * psi%a(1) + bm * psi%a(2))
    psikv%psi(4)%a(1) = am * psi%a(3) + (-bms) * psi%a(4)
    psikv%psi(4)%a(2) = bp * psi%a(3) + am * psi%a(4)
    psikv%psi(4)%a(3) = ap * psi%a(1) + bps * psi%a(2)

```

```

    psikv%psi(4)%a(4) = (-bm) * psi%a(1) + ap * psi%a(2)
end function grkkggf

<Implementation of bispinor currents>+=
pure function gr_vf (g, v, psi, k) result (psikv)
    type(vectorspinor) :: psikv
    type(bispinor), intent(in) :: psi
    type(vector), intent(in) :: v
    type(momentum), intent(in) :: k
    complex(kind=default), intent(in) :: g
    type(vector) :: vk
    vk = k
    psikv = g * (grkkggf (v, psi, vk))
end function gr_vf

<Implementation of bispinor currents>+=
pure function gr_vlrf (gl, gr, v, psi, k) result (psikv)
    type(vectorspinor) :: psikv
    type(bispinor), intent(in) :: psi
    type(bispinor) :: psi_l, psi_r
    type(vector), intent(in) :: v
    type(momentum), intent(in) :: k
    complex(kind=default), intent(in) :: gl, gr
    type(vector) :: vk
    vk = k
    psi_l%a(1:2) = psi%a(1:2)
    psi_l%a(3:4) = 0
    psi_r%a(1:2) = 0
    psi_r%a(3:4) = psi%a(3:4)
    psikv = gl * grkkggf (v, psi_l, vk) + gr * grkkggf (v, psi_r, vk)
end function gr_vlrf

<Declaration of bispinor currents>+=
public :: v_grf, v_fgr

<Declaration of bispinor currents>+=
public :: vlr_grf, vlr_fgr

 $V^\mu = \psi_\rho^T C^{\mu\rho} \psi$ 

<Implementation of bispinor currents>+=
pure function grkgggf (psil, psir, k) result (j)
    type(vector) :: j
    type(vectorspinor), intent(in) :: psil
    type(bispinor), intent(in) :: psir
    type(vector), intent(in) :: k
    type(vectorspinor) :: c_psir0, c_psir1, c_psir2, c_psir3
    complex(kind=default) :: kp, km, k12, k12s, ik2
    kp = k%t + k%x(3)
    km = k%t - k%x(3)
    k12 = (k%x(1) + (0,1)*k%x(2))
    k12s = (k%x(1) - (0,1)*k%x(2))
    ik2 = (0,1) * k%x(2)
    !!! New version:
    c_psir0%psi(1)%a(1) = (-k%x(3)) * psir%a(3) + (-k12s) * psir%a(4)
    c_psir0%psi(1)%a(2) = (-k12) * psir%a(3) + k%x(3) * psir%a(4)
    c_psir0%psi(1)%a(3) = (-k%x(3)) * psir%a(1) + (-k12s) * psir%a(2)
    c_psir0%psi(1)%a(4) = (-k12) * psir%a(1) + k%x(3) * psir%a(2)

```

```

c_psi0%psi(2)%a(1) = (-k12s) * psir%a(3) + (-k%x(3)) * psir%a(4)
c_psi0%psi(2)%a(2) = k%x(3) * psir%a(3) + (-k12) * psir%a(4)
c_psi0%psi(2)%a(3) = k12s * psir%a(1) + k%x(3) * psir%a(2)
c_psi0%psi(2)%a(4) = (-k%x(3)) * psir%a(1) + k12 * psir%a(2)
c_psi0%psi(3)%a(1) = (0,1) * ((-k12s) * psir%a(3) + k%x(3) * psir%a(4))
c_psi0%psi(3)%a(2) = (0,1) * (k%x(3) * psir%a(3) + k12 * psir%a(4))
c_psi0%psi(3)%a(3) = (0,1) * (k12s * psir%a(1) + (-k%x(3)) * psir%a(2))
c_psi0%psi(3)%a(4) = (0,1) * ((-k%x(3)) * psir%a(1) + (-k12) * psir%a(2))
c_psi0%psi(4)%a(1) = (-k%x(3)) * psir%a(3) + k12s * psir%a(4)
c_psi0%psi(4)%a(2) = (-k12) * psir%a(3) + (-k%x(3)) * psir%a(4)
c_psi0%psi(4)%a(3) = k%x(3) * psir%a(1) + (-k12s) * psir%a(2)
c_psi0%psi(4)%a(4) = k12 * psir%a(1) + k%x(3) * psir%a(2)
!!!
c_psi1%psi(1)%a(1) = (-ik2) * psir%a(3) + (-km) * psir%a(4)
c_psi1%psi(1)%a(2) = (-kp) * psir%a(3) + ik2 * psir%a(4)
c_psi1%psi(1)%a(3) = ik2 * psir%a(1) + (-kp) * psir%a(2)
c_psi1%psi(1)%a(4) = (-km) * psir%a(1) + (-ik2) * psir%a(2)
c_psi1%psi(2)%a(1) = (-km) * psir%a(3) + (-ik2) * psir%a(4)
c_psi1%psi(2)%a(2) = ik2 * psir%a(3) + (-kp) * psir%a(4)
c_psi1%psi(2)%a(3) = kp * psir%a(1) + (-ik2) * psir%a(2)
c_psi1%psi(2)%a(4) = ik2 * psir%a(1) + km * psir%a(2)
c_psi1%psi(3)%a(1) = ((0,-1) * km) * psir%a(3) + (-k%x(2)) * psir%a(4)
c_psi1%psi(3)%a(2) = (-k%x(2)) * psir%a(3) + ((0,1) * kp) * psir%a(4)
c_psi1%psi(3)%a(3) = ((0,1) * kp) * psir%a(1) + (-k%x(2)) * psir%a(2)
c_psi1%psi(3)%a(4) = (-k%x(2)) * psir%a(1) + ((0,-1) * km) * psir%a(2)
c_psi1%psi(4)%a(1) = (-ik2) * psir%a(3) + km * psir%a(4)
c_psi1%psi(4)%a(2) = (-kp) * psir%a(3) + (-ik2) * psir%a(4)
c_psi1%psi(4)%a(3) = (-ik2) * psir%a(1) + (-kp) * psir%a(2)
c_psi1%psi(4)%a(4) = km * psir%a(1) + (-ik2) * psir%a(2)
!!!
c_psi2%psi(1)%a(1) = (0,1) * (k%x(1) * psir%a(3) + km * psir%a(4))
c_psi2%psi(1)%a(2) = (0,-1) * (kp * psir%a(3) + k%x(1) * psir%a(4))
c_psi2%psi(1)%a(3) = (0,1) * ((-k%x(1)) * psir%a(1) + kp * psir%a(2))
c_psi2%psi(1)%a(4) = (0,1) * ((-km) * psir%a(1) + k%x(1) * psir%a(2))
c_psi2%psi(2)%a(1) = (0,1) * (km * psir%a(3) + k%x(1) * psir%a(4))
c_psi2%psi(2)%a(2) = (0,-1) * (k%x(1) * psir%a(3) + kp * psir%a(4))
c_psi2%psi(2)%a(3) = (0,-1) * (kp * psir%a(1) + (-k%x(1)) * psir%a(2))
c_psi2%psi(2)%a(4) = (0,-1) * (k%x(1) * psir%a(1) + (-km) * psir%a(2))
c_psi2%psi(3)%a(1) = (-km) * psir%a(3) + k%x(1) * psir%a(4)
c_psi2%psi(3)%a(2) = k%x(1) * psir%a(3) + (-kp) * psir%a(4)
c_psi2%psi(3)%a(3) = kp * psir%a(1) + k%x(1) * psir%a(2)
c_psi2%psi(3)%a(4) = k%x(1) * psir%a(1) + km * psir%a(2)
c_psi2%psi(4)%a(1) = (0,1) * (k%x(1) * psir%a(3) + (-km) * psir%a(4))
c_psi2%psi(4)%a(2) = (0,1) * ((-kp) * psir%a(3) + k%x(1) * psir%a(4))
c_psi2%psi(4)%a(3) = (0,1) * (k%x(1) * psir%a(1) + kp * psir%a(2))
c_psi2%psi(4)%a(4) = (0,1) * (km * psir%a(1) + k%x(1) * psir%a(2))
!!!
c_psi3%psi(1)%a(1) = (-k%t) * psir%a(3) - k12s * psir%a(4)
c_psi3%psi(1)%a(2) = k12 * psir%a(3) + k%t * psir%a(4)
c_psi3%psi(1)%a(3) = (-k%t) * psir%a(1) + k12s * psir%a(2)
c_psi3%psi(1)%a(4) = (-k12) * psir%a(1) + k%t * psir%a(2)
c_psi3%psi(2)%a(1) = (-k12s) * psir%a(3) + (-k%t) * psir%a(4)
c_psi3%psi(2)%a(2) = k%t * psir%a(3) + k12 * psir%a(4)
c_psi3%psi(2)%a(3) = (-k12s) * psir%a(1) + k%t * psir%a(2)

```



```

c_psi3%psi(2)%a(4) = (-k%t) * psir%a(1) + k12 * psir%a(2)
c_psi3%psi(3)%a(1) = (0,-1) * (k12s * psir%a(3) + (-k%t) * psir%a(4))
c_psi3%psi(3)%a(2) = (0,1) * (k%t * psir%a(3) + (-k12) * psir%a(4))
c_psi3%psi(3)%a(3) = (0,-1) * (k12s * psir%a(1) + k%t * psir%a(2))
c_psi3%psi(3)%a(4) = (0,-1) * (k%t * psir%a(1) + k12 * psir%a(2))
c_psi3%psi(4)%a(1) = (-k%t) * psir%a(3) + k12s * psir%a(4)
c_psi3%psi(4)%a(2) = k12 * psir%a(3) + (-k%t) * psir%a(4)
c_psi3%psi(4)%a(3) = k%t * psir%a(1) + k12s * psir%a(2)
c_psi3%psi(4)%a(4) = k12 * psir%a(1) + k%t * psir%a(2)
j%t    = 2 * (psil * c_psi0)
j%x(1) = 2 * (psil * c_psi1)
j%x(2) = 2 * (psil * c_psi2)
j%x(3) = 2 * (psil * c_psi3)
end function grkggff

(Implementation of bispinor currents)+≡
pure function v_grf (g, psil, psir, k) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: g
    type(vectorspinor), intent(in) :: psil
    type(bispinor), intent(in) :: psir
    type(momentum), intent(in) :: k
    type(vector) :: vk
    vk = k
    j = g * grkggff (psil, psir, vk)
end function v_grf

(Implementation of bispinor currents)+≡
pure function vlr_grf (gl, gr, psil, psir, k) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: gl, gr
    type(vectorspinor), intent(in) :: psil
    type(bispinor), intent(in) :: psir
    type(bispinor) :: psir_l, psir_r
    type(momentum), intent(in) :: k
    type(vector) :: vk
    vk = k
    psir_l%a(1:2) = psir%a(1:2)
    psir_l%a(3:4) = 0
    psir_r%a(1:2) = 0
    psir_r%a(3:4) = psir%a(3:4)
    j = gl * grkggff (psil, psir_l, vk) + gr * grkggff (psil, psir_r, vk)
end function vlr_grf

 $V^\mu = \psi^T \tilde{C}^{\mu\rho} \psi_\rho$ ; remember the reversed index order in  $\tilde{C}$ .

(Implementation of bispinor currents)+≡
pure function fggkggr (psil, psir, k) result (j)
    type(vector) :: j
    type(vectorspinor), intent(in) :: psir
    type(bispinor), intent(in) :: psil
    type(vector), intent(in) :: k
    type(bispinor) :: c_psi0, c_psi1, c_psi2, c_psi3
    complex(kind=default) :: kp, km, k12, k12s, ik1, ik2
    kp = k%t + k%x(3)
    km = k%t - k%x(3)
    k12 = k%x(1) + (0,1)*k%x(2)

```

```

k12s = k%x(1) - (0,1)*k%x(2)
ik1 = (0,1) * k%x(1)
ik2 = (0,1) * k%x(2)
c_psi0%a(1) = k%x(3) * (psir%psi(1)%a(4) + psir%psi(4)%a(4) &
    + psir%psi(2)%a(3) + (0,1) * psir%psi(3)%a(3)) - &
    k12 * (psir%psi(1)%a(3) + psir%psi(4)%a(3)) + &
    k12s * (psir%psi(2)%a(4) + (0,1) * psir%psi(3)%a(4))
c_psi0%a(2) = k%x(3) * (psir%psi(1)%a(3) - psir%psi(4)%a(3) + &
    psir%psi(2)%a(4) - (0,1) * psir%psi(3)%a(4)) + &
    k12s * (psir%psi(1)%a(4) - psir%psi(4)%a(4)) - &
    k12 * (psir%psi(2)%a(3) - (0,1) * psir%psi(3)%a(3))
c_psi0%a(3) = k%x(3) * (-psir%psi(1)%a(2) + psir%psi(4)%a(2) + &
    psir%psi(2)%a(1) + (0,1) * psir%psi(3)%a(1)) + &
    k12 * (psir%psi(1)%a(1) - psir%psi(4)%a(1)) + &
    k12s * (psir%psi(2)%a(2) + (0,1) * psir%psi(3)%a(2))
c_psi0%a(4) = k%x(3) * (-psir%psi(1)%a(1) - psir%psi(4)%a(1) + &
    psir%psi(2)%a(2) - (0,1) * psir%psi(3)%a(2)) - &
    k12s * (psir%psi(1)%a(2) + psir%psi(4)%a(2)) - &
    k12 * (psir%psi(2)%a(1) - (0,1) * psir%psi(3)%a(1))

!!!
c_psi1%a(1) = ik2 * (-psir%psi(1)%a(4) - psir%psi(4)%a(4) - &
    psir%psi(2)%a(3) - (0,1) * psir%psi(3)%a(3)) - &
    km * (psir%psi(1)%a(3) + psir%psi(4)%a(3)) + &
    kp * (psir%psi(2)%a(4) + (0,1) * psir%psi(3)%a(4))
c_psi1%a(2) = ik2 * (-psir%psi(1)%a(3) - psir%psi(2)%a(4) + &
    psir%psi(4)%a(3) + (0,1) * psir%psi(3)%a(4)) + &
    kp * (psir%psi(1)%a(4) - psir%psi(4)%a(4)) - &
    km * (psir%psi(2)%a(3) - (0,1) * psir%psi(3)%a(3))
c_psi1%a(3) = ik2 * (-psir%psi(1)%a(2) + psir%psi(2)%a(1) + &
    psir%psi(4)%a(2) + (0,1) * psir%psi(3)%a(1)) + &
    kp * (psir%psi(1)%a(1) - psir%psi(4)%a(1)) + &
    km * (psir%psi(2)%a(2) + (0,1) * psir%psi(3)%a(2))
c_psi1%a(4) = ik2 * (-psir%psi(1)%a(1) + psir%psi(2)%a(2) - &
    psir%psi(4)%a(1) - (0,1) * psir%psi(3)%a(2)) - &
    km * (psir%psi(1)%a(2) + psir%psi(4)%a(2)) - &
    kp * (psir%psi(2)%a(1) - (0,1) * psir%psi(3)%a(1))

!!!
c_psi2%a(1) = ik1 * (psir%psi(2)%a(3) + psir%psi(1)%a(4) &
    + psir%psi(4)%a(4) + (0,1) * psir%psi(3)%a(3)) - &
    ((0,1)*km) * (psir%psi(1)%a(3) + psir%psi(4)%a(3)) &
    + kp * (psir%psi(3)%a(4) - (0,1) * psir%psi(2)%a(4))
c_psi2%a(2) = ik1 * (psir%psi(1)%a(3) + psir%psi(2)%a(4) - &
    psir%psi(4)%a(3) - (0,1) * psir%psi(3)%a(4)) - &
    ((0,1)*kp) * (psir%psi(1)%a(4) - psir%psi(4)%a(4)) &
    - km * (psir%psi(3)%a(3) + (0,1) * psir%psi(2)%a(3))
c_psi2%a(3) = ik1 * (psir%psi(1)%a(2) - psir%psi(2)%a(1) - &
    psir%psi(4)%a(2) - (0,1) * psir%psi(3)%a(1)) + &
    ((0,1)*kp) * (psir%psi(1)%a(1) - psir%psi(4)%a(1)) &
    + km * (psir%psi(3)%a(2) - (0,1) * psir%psi(2)%a(2))
c_psi2%a(4) = ik1 * (psir%psi(1)%a(1) - psir%psi(2)%a(2) + &
    psir%psi(4)%a(1) + (0,1) * psir%psi(3)%a(2)) + &
    ((0,1)*km) * (psir%psi(1)%a(2) + psir%psi(4)%a(2)) - &
    kp * (psir%psi(3)%a(1) + (0,1) * psir%psi(2)%a(1))

!!!

```

```

c_psi3%a(1) = k%t * (psir%psi(1)%a(4) + psir%psi(4)%a(4) + &
    psir%psi(2)%a(3) + (0,1) * psir%psi(3)%a(3)) - &
    k12 * (psir%psi(1)%a(3) + psir%psi(4)%a(3)) - &
    k12s * (psir%psi(2)%a(4) + (0,1) * psir%psi(3)%a(4))
c_psi3%a(2) = k%t * (psir%psi(1)%a(3) - psir%psi(4)%a(3) + &
    psir%psi(2)%a(4) - (0,1) * psir%psi(3)%a(4)) - &
    k12s * (psir%psi(1)%a(4) - psir%psi(4)%a(4)) - &
    k12 * (psir%psi(2)%a(3) - (0,1) * psir%psi(3)%a(3))
c_psi3%a(3) = k%t * (-psir%psi(1)%a(2) + psir%psi(2)%a(1) + &
    psir%psi(4)%a(2) + (0,1) * psir%psi(3)%a(1)) - &
    k12 * (psir%psi(1)%a(1) - psir%psi(4)%a(1)) + &
    k12s * (psir%psi(2)%a(2) + (0,1) * psir%psi(3)%a(2))
c_psi3%a(4) = k%t * (-psir%psi(1)%a(1) + psir%psi(2)%a(2) - &
    psir%psi(4)%a(1) - (0,1) * psir%psi(3)%a(2)) - &
    k12s * (psir%psi(1)%a(2) + psir%psi(4)%a(2)) + &
    k12 * (psir%psi(2)%a(1) - (0,1) * psir%psi(3)%a(1))
!!! Because we explicitly multiplied the charge conjugation matrix
!!! we have to omit it from the spinor product and take the
!!! ordinary product!
j%t = 2 * dot_product (conjg (psil%a), c_psi0%a)
j%x(1) = 2 * dot_product (conjg (psil%a), c_psi1%a)
j%x(2) = 2 * dot_product (conjg (psil%a), c_psi2%a)
j%x(3) = 2 * dot_product (conjg (psil%a), c_psi3%a)
end function fggkggr

(Implementation of bispinor currents)+≡
pure function v_fgr (g, psil, psir, k) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: g
    type(vectorspinor), intent(in) :: psir
    type(bispinor), intent(in) :: psil
    type(momentum), intent(in) :: k
    type(vector) :: vk
    vk = k
    j = g * fggkggr (psil, psir, vk)
end function v_fgr

(Implementation of bispinor currents)+≡
pure function vlr_fgr (gl, gr, psil, psir, k) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: gl, gr
    type(vectorspinor), intent(in) :: psir
    type(bispinor), intent(in) :: psil
    type(bispinor) :: psil_l
    type(bispinor) :: psil_r
    type(momentum), intent(in) :: k
    type(vector) :: vk
    vk = k
    psil_l%a(1:2) = psil%a(1:2)
    psil_l%a(3:4) = 0
    psil_r%a(1:2) = 0
    psil_r%a(3:4) = psil%a(3:4)
    j = gl * fggkggr (psil_l, psir, vk) + gr * fggkggr (psil_r, psir, vk)
end function vlr_fgr
    
```

X.14.5 Gravitino 4-Couplings

```

<Declaration of bispinor currents>+≡
  public :: f_s2gr, f_svgr, f_slvgr, f_srvgr, f_slrvgr, f_pvgr, f_v2gr, f_v2lgr

<Implementation of bispinor currents>+≡
  pure function f_s2gr (g, phi1, phi2, psi) result (phipsi)
    type(bispinor) :: phipsi
    type(vectorspinor), intent(in) :: psi
    complex(kind=default), intent(in) :: g
    complex(kind=default), intent(in) :: phi1, phi2
    phipsi = phi2 * f_potgr (g, phi1, psi)
  end function f_s2gr

<Implementation of bispinor currents>+≡
  pure function f_svgr (g, phi, v, grav) result (phigrav)
    type(bispinor) :: phigrav
    type(vectorspinor), intent(in) :: grav
    type(vector), intent(in) :: v
    complex(kind=default), intent(in) :: g, phi
    phigrav = (g * phi) * fgvg5gr (grav, v)
  end function f_svgr

<Implementation of bispinor currents>+≡
  pure function f_slvgr (gl, phi, v, grav) result (phigrav)
    type(bispinor) :: phigrav, phidum
    type(vectorspinor), intent(in) :: grav
    type(vector), intent(in) :: v
    complex(kind=default), intent(in) :: gl, phi
    phidum = (gl * phi) * fgvg5gr (grav, v)
    phigrav%a(1:2) = phidum%a(1:2)
    phigrav%a(3:4) = 0
  end function f_slvgr

<Implementation of bispinor currents>+≡
  pure function f_srvgr (gr, phi, v, grav) result (phigrav)
    type(bispinor) :: phigrav, phidum
    type(vectorspinor), intent(in) :: grav
    type(vector), intent(in) :: v
    complex(kind=default), intent(in) :: gr, phi
    phidum = (gr * phi) * fgvg5gr (grav, v)
    phigrav%a(1:2) = 0
    phigrav%a(3:4) = phidum%a(3:4)
  end function f_srvgr

<Implementation of bispinor currents>+≡
  pure function f_slrvgr (gl, gr, phi, v, grav) result (phigrav)
    type(bispinor) :: phigrav, phidum
    type(vectorspinor), intent(in) :: grav
    type(vector), intent(in) :: v
    complex(kind=default), intent(in) :: gl, gr, phi
    phigrav = f_slvgr (gl, phi, v, grav) + f_srvgr (gr, phi, v, grav)
  end function f_slrvgr

<Implementation of bispinor currents>+≡
  pure function f_pvgr (g, phi, v, grav) result (phigrav)
    type(bispinor) :: phigrav

```

```

    type(vectorspinor), intent(in) :: grav
    type(vector), intent(in) :: v
    complex(kind=default), intent(in) :: g, phi
    phigrav = (g * phi) * fgvgvgr (grav, v)
end function f_pvgr

<Implementation of bispinor currents>+≡
pure function f_v2gr (g, v1, v2, grav) result (psi)
    type(bispinor) :: psi
    complex(kind=default), intent(in) :: g
    type(vectorspinor), intent(in) :: grav
    type(vector), intent(in) :: v1, v2
    psi = g * fgvgvgr (v2, grav, v1)
end function f_v2gr

<Implementation of bispinor currents>+≡
pure function f_v2lrg (gl, gr, v1, v2, grav) result (psi)
    type(bispinor) :: psi
    complex(kind=default), intent(in) :: gl, gr
    type(vectorspinor), intent(in) :: grav
    type(vector), intent(in) :: v1, v2
    psi = fgvgvgr (v2, grav, v1)
    psi%a(1:2) = gl * psi%a(1:2)
    psi%a(3:4) = gr * psi%a(3:4)
end function f_v2lrg

<Declaration of bispinor currents>+≡
public :: gr_s2f, gr_svf, gr_pvf, gr_slvf, gr_srvf, gr_slrvf, gr_v2f, gr_v2lrf

<Implementation of bispinor currents>+≡
pure function gr_s2f (g, phi1, phi2, psi) result (phipsi)
    type(vectorspinor) :: phipsi
    type(bispinor), intent(in) :: psi
    complex(kind=default), intent(in) :: g
    complex(kind=default), intent(in) :: phi1, phi2
    phipsi = phi2 * gr_potf (g, phi1, psi)
end function gr_s2f

<Implementation of bispinor currents>+≡
pure function gr_svf (g, phi, v, psi) result (phipsi)
    type(vectorspinor) :: phipsi
    type(bispinor), intent(in) :: psi
    type(vector), intent(in) :: v
    complex(kind=default), intent(in) :: g, phi
    phipsi = (g * phi) * grkggf (psi, v)
end function gr_svf

<Implementation of bispinor currents>+≡
pure function gr_slvf (gl, phi, v, psi) result (phipsi)
    type(vectorspinor) :: phipsi
    type(bispinor), intent(in) :: psi
    type(bispinor) :: psi_l
    type(vector), intent(in) :: v
    complex(kind=default), intent(in) :: gl, phi
    psi_l%a(1:2) = psi%a(1:2)
    psi_l%a(3:4) = 0
    phipsi = (gl * phi) * grkggf (psi_l, v)
end function gr_slvf

```

```

<Implementation of bispinor currents>+≡
pure function gr_srvf (gr, phi, v, psi) result (phipsi)
  type(vectorspinor) :: phipsi
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_r
  type(vector), intent(in) :: v
  complex(kind=default), intent(in) :: gr, phi
  psi_r%a(1:2) = 0
  psi_r%a(3:4) = psi%a(3:4)
  phipsi = (gr * phi) * grkkgf (psi_r, v)
end function gr_srvf

<Implementation of bispinor currents>+≡
pure function gr_slrvf (gl, gr, phi, v, psi) result (phipsi)
  type(vectorspinor) :: phipsi
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_r
  type(vector), intent(in) :: v
  complex(kind=default), intent(in) :: gl, gr, phi
  phipsi = gr_slvf (gl, phi, v, psi) + gr_srvf (gr, phi, v, psi)
end function gr_slrvf

<Implementation of bispinor currents>+≡
pure function gr_pvf (g, phi, v, psi) result (phipsi)
  type(vectorspinor) :: phipsi
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: v
  complex(kind=default), intent(in) :: g, phi
  phipsi = (g * phi) * grkgf (psi, v)
end function gr_pvf

<Implementation of bispinor currents>+≡
pure function gr_v2f (g, v1, v2, psi) result (vvpsi)
  type(vectorspinor) :: vvpsi
  complex(kind=default), intent(in) :: g
  type(bispinor), intent(in) :: psi
  type(vector), intent(in) :: v1, v2
  vvpsi = g * grkkgf (v2, psi, v1)
end function gr_v2f

<Implementation of bispinor currents>+≡
pure function gr_v2lrf (gl, gr, v1, v2, psi) result (vvpsi)
  type(vectorspinor) :: vvpsi
  complex(kind=default), intent(in) :: gl, gr
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_l, psi_r
  type(vector), intent(in) :: v1, v2
  psi_l%a(1:2) = psi%a(1:2)
  psi_l%a(3:4) = 0
  psi_r%a(1:2) = 0
  psi_r%a(3:4) = psi%a(3:4)
  vvpsi = gl * grkkgf (v2, psi_l, v1) + gr * grkkgf (v2, psi_r, v1)
end function gr_v2lrf

<Declaration of bispinor currents>+≡
public :: s2_grf, s2_fgr, sv1_grf, sv2_grf, sv1_fgr, sv2_fgr, &
         slv1_grf, slv2_grf, slv1_fgr, slv2_fgr, &

```

```

        srv1_grf, srv2_grf, srv1_fgr, srv2_fgr, &
        slrv1_grf, slrv2_grf, slrv1_fgr, slrv2_fgr, &
        pv1_grf, pv2_grf, pv1_fgr, pv2_fgr, v2_grf, v2_fgr, &
        v2lr_grf, v2lr_fgr
    )
    <Implementation of bispinor currents>+≡
    pure function s2_grf (g, gravbar, phi, psi) result (j)
        complex(kind=default) :: j
        complex(kind=default), intent(in) :: g, phi
        type(vectorspinor), intent(in) :: gravbar
        type(bispinor), intent(in) :: psi
        j = phi * pot_grf (g, gravbar, psi)
    end function s2_grf

    <Implementation of bispinor currents>+≡
    pure function s2_fgr (g, psibar, phi, grav) result (j)
        complex(kind=default) :: j
        complex(kind=default), intent(in) :: g, phi
        type(bispinor), intent(in) :: psibar
        type(vectorspinor), intent(in) :: grav
        j = phi * pot_fgr (g, psibar, grav)
    end function s2_fgr

    <Implementation of bispinor currents>+≡
    pure function sv1_grf (g, gravbar, v, psi) result (j)
        complex(kind=default) :: j
        complex(kind=default), intent(in) :: g
        type(vectorspinor), intent(in) :: gravbar
        type(bispinor), intent(in) :: psi
        type(vector), intent(in) :: v
        j = g * grg5vgf (gravbar, psi, v)
    end function sv1_grf

    <Implementation of bispinor currents>+≡
    pure function slv1_grf (gl, gravbar, v, psi) result (j)
        complex(kind=default) :: j
        complex(kind=default), intent(in) :: gl
        type(vectorspinor), intent(in) :: gravbar
        type(bispinor), intent(in) :: psi
        type(bispinor) :: psi_l
        type(vector), intent(in) :: v
        psi_l%a(1:2) = psi%a(1:2)
        psi_l%a(3:4) = 0
        j = gl * grg5vgf (gravbar, psi_l, v)
    end function slv1_grf

    <Implementation of bispinor currents>+≡
    pure function srv1_grf (gr, gravbar, v, psi) result (j)
        complex(kind=default) :: j
        complex(kind=default), intent(in) :: gr
        type(vectorspinor), intent(in) :: gravbar
        type(bispinor), intent(in) :: psi
        type(bispinor) :: psi_r
        type(vector), intent(in) :: v
        psi_r%a(1:2) = 0
        psi_r%a(3:4) = psi%a(3:4)
        j = gr * grg5vgf (gravbar, psi_r, v)

```

```

end function srv1_grf

<Implementation of bispinor currents>+≡
pure function slrv1_grf (gl, gr, gravbar, v, psi) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: gl, gr
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(bispinor) :: psi_l, psi_r
    type(vector), intent(in) :: v
    psi_l%a(1:2) = psi%a(1:2)
    psi_l%a(3:4) = 0
    psi_r%a(1:2) = 0
    psi_r%a(3:4) = psi%a(3:4)
    j = gl * grg5vgf (gravbar, psi_l, v) + gr * grg5vgf (gravbar, psi_r, v)
end function slrv1_grf

```

$$C\gamma^0\gamma^0 = -C\gamma^1\gamma^1 = -C\gamma^2\gamma^2 = C\gamma^3\gamma^3 = C = \begin{pmatrix} 0 & 1 & 0 & 0 \\ -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & -1 \\ 0 & 0 & 1 & 0 \end{pmatrix} \quad (\text{X.82a})$$

$$C\gamma^0\gamma^1 = -C\gamma^1\gamma^0 = \begin{pmatrix} -1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & -1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \quad (\text{X.82b})$$

$$C\gamma^0\gamma^2 = -C\gamma^2\gamma^0 = \begin{pmatrix} -i & 0 & 0 & 0 \\ 0 & -i & 0 & 0 \\ 0 & 0 & -i & 0 \\ 0 & 0 & 0 & -i \end{pmatrix} \quad (\text{X.82c})$$

$$C\gamma^0\gamma^3 = -C\gamma^3\gamma^0 = \begin{pmatrix} 0 & 1 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{pmatrix} \quad (\text{X.82d})$$

$$C\gamma^1\gamma^2 = -C\gamma^2\gamma^1 = \begin{pmatrix} 0 & i & 0 & 0 \\ i & 0 & 0 & 0 \\ 0 & 0 & 0 & -i \\ 0 & 0 & -i & 0 \end{pmatrix} \quad (\text{X.82e})$$

$$C\gamma^1\gamma^3 = -C\gamma^3\gamma^1 = \begin{pmatrix} -1 & 0 & 0 & 0 \\ 0 & -1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \quad (\text{X.82f})$$

$$C\gamma^2\gamma^3 = -C\gamma^3\gamma^2 = \begin{pmatrix} -i & 0 & 0 & 0 \\ 0 & i & 0 & 0 \\ 0 & 0 & i & 0 \\ 0 & 0 & 0 & -i \end{pmatrix} \quad (\text{X.82g})$$

```

<Implementation of bispinor currents>+≡
pure function sv2_grf (g, gravbar, phi, psi) result (j)
    type(vector) :: j

```



```

complex(kind=default), intent(in) :: g, phi
type(vectorspinor), intent(in) :: gravbar
type(bispinor), intent(in) :: psi
type(vectorspinor) :: g0_psi, g1_psi, g2_psi, g3_psi
g0_psi%psi(1)%a(1:2) = - psi%a(1:2)
g0_psi%psi(1)%a(3:4) = psi%a(3:4)
g0_psi%psi(2)%a(1) = psi%a(2)
g0_psi%psi(2)%a(2) = psi%a(1)
g0_psi%psi(2)%a(3) = psi%a(4)
g0_psi%psi(2)%a(4) = psi%a(3)
g0_psi%psi(3)%a(1) = (0,-1) * psi%a(2)
g0_psi%psi(3)%a(2) = (0,1) * psi%a(1)
g0_psi%psi(3)%a(3) = (0,-1) * psi%a(4)
g0_psi%psi(3)%a(4) = (0,1) * psi%a(3)
g0_psi%psi(4)%a(1) = psi%a(1)
g0_psi%psi(4)%a(2) = - psi%a(2)
g0_psi%psi(4)%a(3) = psi%a(3)
g0_psi%psi(4)%a(4) = - psi%a(4)
g1_psi%psi(1)%a(1:4) = - g0_psi%psi(2)%a(1:4)
g1_psi%psi(2)%a(1:4) = - g0_psi%psi(1)%a(1:4)
g1_psi%psi(3)%a(1) = (0,1) * psi%a(1)
g1_psi%psi(3)%a(2) = (0,-1) * psi%a(2)
g1_psi%psi(3)%a(3) = (0,-1) * psi%a(3)
g1_psi%psi(3)%a(4) = (0,1) * psi%a(4)
g1_psi%psi(4)%a(1) = - psi%a(2)
g1_psi%psi(4)%a(2) = psi%a(1)
g1_psi%psi(4)%a(3) = psi%a(4)
g1_psi%psi(4)%a(4) = - psi%a(3)
g2_psi%psi(1)%a(1:4) = - g0_psi%psi(3)%a(1:4)
g2_psi%psi(2)%a(1:4) = - g1_psi%psi(3)%a(1:4)
g2_psi%psi(3)%a(1:4) = - g0_psi%psi(1)%a(1:4)
g2_psi%psi(4)%a(1) = (0,1) * psi%a(2)
g2_psi%psi(4)%a(2) = (0,1) * psi%a(1)
g2_psi%psi(4)%a(3) = (0,-1) * psi%a(4)
g2_psi%psi(4)%a(4) = (0,-1) * psi%a(3)
g3_psi%psi(1)%a(1:4) = - g0_psi%psi(4)%a(1:4)
g3_psi%psi(2)%a(1:4) = - g1_psi%psi(4)%a(1:4)
g3_psi%psi(3)%a(1:4) = - g2_psi%psi(4)%a(1:4)
g3_psi%psi(4)%a(1:4) = - g0_psi%psi(1)%a(1:4)
j%t = (g * phi) * (gravbar * g0_psi)
j%x(1) = (g * phi) * (gravbar * g1_psi)
j%x(2) = (g * phi) * (gravbar * g2_psi)
j%x(3) = (g * phi) * (gravbar * g3_psi)
end function sv2_grf

```

(Implementation of bispinor currents) \equiv

```

pure function slv2_grf (gl, gravbar, phi, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gl, phi
  type(vectorspinor), intent(in) :: gravbar
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_l
  psi_l%a(1:2) = psi%a(1:2)
  psi_l%a(3:4) = 0
  j = sv2_grf (gl, gravbar, phi, psi_l)

```

```

end function slv2_grf

<Implementation of bispinor currents>+≡
pure function srv2_grf (gr, gravbar, phi, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gr, phi
  type(vectorspinor), intent(in) :: gravbar
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_r
  psi_r%a(1:2) = 0
  psi_r%a(3:4) = psi%a(3:4)
  j = sv2_grf (gr, gravbar, phi, psi_r)
end function srv2_grf

<Implementation of bispinor currents>+≡
pure function slrv2_grf (gl, gr, gravbar, phi, psi) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gl, gr, phi
  type(vectorspinor), intent(in) :: gravbar
  type(bispinor), intent(in) :: psi
  type(bispinor) :: psi_l, psi_r
  psi_l%a(1:2) = psi%a(1:2)
  psi_l%a(3:4) = 0
  psi_r%a(1:2) = 0
  psi_r%a(3:4) = psi%a(3:4)
  j = sv2_grf (gl, gravbar, phi, psi_l) + sv2_grf (gr, gravbar, phi, psi_r)
end function slrv2_grf

<Implementation of bispinor currents>+≡
pure function sv1_fgr (g, psibar, v, grav) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: g
  type(bispinor), intent(in) :: psibar
  type(vectorspinor), intent(in) :: grav
  type(vector), intent(in) :: v
  j = g * fg5gkgr (psibar, grav, v)
end function sv1_fgr

<Implementation of bispinor currents>+≡
pure function slv1_fgr (gl, psibar, v, grav) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gl
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_l
  type(vectorspinor), intent(in) :: grav
  type(vector), intent(in) :: v
  psibar_l%a(1:2) = psibar%a(1:2)
  psibar_l%a(3:4) = 0
  j = gl * fg5gkgr (psibar_l, grav, v)
end function slv1_fgr

<Implementation of bispinor currents>+≡
pure function srv1_fgr (gr, psibar, v, grav) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gr
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_r

```

```

type(vectorspinor), intent(in) :: grav
type(vector), intent(in) :: v
psibar_r%a(1:2) = 0
psibar_r%a(3:4) = psibar%a(3:4)
j = gr * fg5gkgr (psibar_r, grav, v)
end function srv1_fgr

```

(Implementation of bispinor currents)+≡

```

pure function slrv1_fgr (gl, gr, psibar, v, grav) result (j)
  complex(kind=default) :: j
  complex(kind=default), intent(in) :: gl, gr
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_l, psibar_r
  type(vectorspinor), intent(in) :: grav
  type(vector), intent(in) :: v
  psibar_l%a(1:2) = psibar%a(1:2)
  psibar_l%a(3:4) = 0
  psibar_r%a(1:2) = 0
  psibar_r%a(3:4) = psibar%a(3:4)
  j = gl * fg5gkgr (psibar_l, grav, v) + gr * fg5gkgr (psibar_r, grav, v)
end function slrv1_fgr

```

(Implementation of bispinor currents)+≡

```

pure function sv2_fgr (g, psibar, phi, grav) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: g, phi
  type(bispinor), intent(in) :: psibar
  type(vectorspinor), intent(in) :: grav
  type(bispinor) :: g0_grav, g1_grav, g2_grav, g3_grav
  g0_grav%a(1) = -grav%psi(1)%a(1) + grav%psi(2)%a(2) - &
    (0,1) * grav%psi(3)%a(2) + grav%psi(4)%a(1)
  g0_grav%a(2) = -grav%psi(1)%a(2) + grav%psi(2)%a(1) + &
    (0,1) * grav%psi(3)%a(1) - grav%psi(4)%a(2)
  g0_grav%a(3) = grav%psi(1)%a(3) + grav%psi(2)%a(4) - &
    (0,1) * grav%psi(3)%a(4) + grav%psi(4)%a(3)
  g0_grav%a(4) = grav%psi(1)%a(4) + grav%psi(2)%a(3) + &
    (0,1) * grav%psi(3)%a(3) - grav%psi(4)%a(4)
  !!!
  g1_grav%a(1) = grav%psi(1)%a(2) - grav%psi(2)%a(1) + &
    (0,1) * grav%psi(3)%a(1) - grav%psi(4)%a(2)
  g1_grav%a(2) = grav%psi(1)%a(1) - grav%psi(2)%a(2) - &
    (0,1) * grav%psi(3)%a(2) + grav%psi(4)%a(1)
  g1_grav%a(3) = grav%psi(1)%a(4) + grav%psi(2)%a(3) - &
    (0,1) * grav%psi(3)%a(3) + grav%psi(4)%a(4)
  g1_grav%a(4) = grav%psi(1)%a(3) + grav%psi(2)%a(4) + &
    (0,1) * grav%psi(3)%a(4) - grav%psi(4)%a(3)
  !!!
  g2_grav%a(1) = (0,1) * (-grav%psi(1)%a(2) - grav%psi(2)%a(1) + &
    grav%psi(4)%a(2)) - grav%psi(3)%a(1)
  g2_grav%a(2) = (0,1) * (grav%psi(1)%a(1) + grav%psi(2)%a(2) + &
    grav%psi(4)%a(1)) - grav%psi(3)%a(2)
  g2_grav%a(3) = (0,1) * (-grav%psi(1)%a(4) + grav%psi(2)%a(3) - &
    grav%psi(4)%a(4)) + grav%psi(3)%a(3)
  g2_grav%a(4) = (0,1) * (grav%psi(1)%a(3) - grav%psi(2)%a(4) - &
    grav%psi(4)%a(3)) + grav%psi(3)%a(4)

```

```

!!!
g3_grav%a(1) = -grav%psi(1)%a(2) + grav%psi(2)%a(2) - &
               (0,1) * grav%psi(3)%a(2) - grav%psi(4)%a(1)
g3_grav%a(2) = grav%psi(1)%a(1) - grav%psi(2)%a(1) - &
               (0,1) * grav%psi(3)%a(1) - grav%psi(4)%a(2)
g3_grav%a(3) = -grav%psi(1)%a(2) - grav%psi(2)%a(4) + &
               (0,1) * grav%psi(3)%a(4) + grav%psi(4)%a(3)
g3_grav%a(4) = -grav%psi(1)%a(4) + grav%psi(2)%a(3) + &
               (0,1) * grav%psi(3)%a(3) + grav%psi(4)%a(4)
j%t      = (g * phi) * (psibar * g0_grav)
j%x(1)   = (g * phi) * (psibar * g1_grav)
j%x(2)   = (g * phi) * (psibar * g2_grav)
j%x(3)   = (g * phi) * (psibar * g3_grav)
end function sv2_fgr

(Implementation of bispinor currents)+≡
pure function slv2_fgr (gl, psibar, phi, grav) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gl, phi
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_l
  type(vectorspinor), intent(in) :: grav
  psibar_l%a(1:2) = psibar%a(1:2)
  psibar_l%a(3:4) = 0
  j = sv2_fgr (gl, psibar_l, phi, grav)
end function slv2_fgr

(Implementation of bispinor currents)+≡
pure function srv2_fgr (gr, psibar, phi, grav) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gr, phi
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_r
  type(vectorspinor), intent(in) :: grav
  psibar_r%a(1:2) = 0
  psibar_r%a(3:4) = psibar%a(3:4)
  j = sv2_fgr (gr, psibar_r, phi, grav)
end function srv2_fgr

(Implementation of bispinor currents)+≡
pure function slrv2_fgr (gl, gr, psibar, phi, grav) result (j)
  type(vector) :: j
  complex(kind=default), intent(in) :: gl, gr, phi
  type(bispinor), intent(in) :: psibar
  type(bispinor) :: psibar_l, psibar_r
  type(vectorspinor), intent(in) :: grav
  psibar_l%a(1:2) = psibar%a(1:2)
  psibar_l%a(3:4) = 0
  psibar_r%a(1:2) = 0
  psibar_r%a(3:4) = psibar%a(3:4)
  j = sv2_fgr (gl, psibar_l, phi, grav) + sv2_fgr (gr, psibar_r, phi, grav)
end function slrv2_fgr

(Implementation of bispinor currents)+≡
pure function pv1_grf (g, gravbar, v, psi) result (j)
  complex(kind=default) :: j

```

```

    complex(kind=default), intent(in) :: g
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(vector), intent(in) :: v
    j = g * grvgf (gravbar, psi, v)
end function pv1_grf

<Implementation of bispinor currents>+≡
pure function pv2_grf (g, gravbar, phi, psi) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: g, phi
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(bispinor) :: g5_psi
    g5_psi%a(1:2) = - psi%a(1:2)
    g5_psi%a(3:4) = psi%a(3:4)
    j = sv2_grf (g, gravbar, phi, g5_psi)
end function pv2_grf

<Implementation of bispinor currents>+≡
pure function pv1_fgr (g, psibar, v, grav) result (j)
    complex(kind=default) :: j
    complex(kind=default), intent(in) :: g
    type(bispinor), intent(in) :: psibar
    type(vectorspinor), intent(in) :: grav
    type(vector), intent(in) :: v
    j = g * fgkgr (psibar, grav, v)
end function pv1_fgr

<Implementation of bispinor currents>+≡
pure function pv2_fgr (g, psibar, phi, grav) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: g, phi
    type(vectorspinor), intent(in) :: grav
    type(bispinor), intent(in) :: psibar
    type(bispinor) :: psibar_g5
    psibar_g5%a(1:2) = - psibar%a(1:2)
    psibar_g5%a(3:4) = psibar%a(3:4)
    j = sv2_fgr (g, psibar_g5, phi, grav)
end function pv2_fgr

<Implementation of bispinor currents>+≡
pure function v2_grf (g, gravbar, v, psi) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: g
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi
    type(vector), intent(in) :: v
    j = -g * grkggff (gravbar, psi, v)
end function v2_grf

<Implementation of bispinor currents>+≡
pure function v2lr_grf (gl, gr, gravbar, v, psi) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: gl, gr
    type(vectorspinor), intent(in) :: gravbar
    type(bispinor), intent(in) :: psi

```

```

    type(bispinor) :: psi_l, psi_r
    type(vector), intent(in) :: v
    psi_l%a(1:2) = psi%a(1:2)
    psi_l%a(3:4) = 0
    psi_r%a(1:2) = 0
    psi_r%a(3:4) = psi%a(3:4)
    j = -(gl * grkgggf (gravbar, psi_l, v) + gr * grkgggf (gravbar, psi_r, v))
end function v2lr_grf

(Implementation of bispinor currents)+≡
pure function v2_fgr (g, psibar, v, grav) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: g
    type(vectorspinor), intent(in) :: grav
    type(bispinor), intent(in) :: psibar
    type(vector), intent(in) :: v
    j = -g * fggkggr (psibar, grav, v)
end function v2_fgr

(Implementation of bispinor currents)+≡
pure function v2lr_fgr (gl, gr, psibar, v, grav) result (j)
    type(vector) :: j
    complex(kind=default), intent(in) :: gl, gr
    type(vectorspinor), intent(in) :: grav
    type(bispinor), intent(in) :: psibar
    type(bispinor) :: psibar_l, psibar_r
    type(vector), intent(in) :: v
    psibar_l%a(1:2) = psibar%a(1:2)
    psibar_l%a(3:4) = 0
    psibar_r%a(1:2) = 0
    psibar_r%a(3:4) = psibar%a(3:4)
    j = -(gl * fggkggr (psibar_l, grav, v) + gr * fggkggr (psibar_r, grav, v))
end function v2lr_fgr

```

X.14.6 On Shell Wave Functions

(Declaration of bispinor on shell wave functions)≡

```

public :: u, v, ghost

```

$$\chi_+(\vec{p}) = \frac{1}{\sqrt{2|\vec{p}|(|\vec{p}| + p_3)}} \begin{pmatrix} |\vec{p}| + p_3 \\ p_1 + ip_2 \end{pmatrix} \quad (\text{X.83a})$$

$$\chi_-(\vec{p}) = \frac{1}{\sqrt{2|\vec{p}|(|\vec{p}| + p_3)}} \begin{pmatrix} -p_1 + ip_2 \\ |\vec{p}| + p_3 \end{pmatrix} \quad (\text{X.83b})$$

$$u_{\pm}(p) = \begin{pmatrix} \sqrt{p_0 \mp |\vec{p}|} \cdot \chi_{\pm}(\vec{p}) \\ \sqrt{p_0 \pm |\vec{p}|} \cdot \chi_{\pm}(\vec{p}) \end{pmatrix} \quad (\text{X.84})$$

(Implementation of bispinor on shell wave functions)≡

```

pure function u (mass, p, s) result (psi)
    type(bispinor) :: psi
    real(kind=default), intent(in) :: mass
    type(momentum), intent(in) :: p
    integer, intent(in) :: s

```

```

complex(kind=default), dimension(2) :: chip, chim
real(kind=default) :: pabs, norm, delta, m
m = abs(mass)
pabs = sqrt (dot_product (p%x, p%x))
if (m < epsilon (m) * pabs) then
    delta = 0
else
    delta = sqrt (max (p%t - pabs, 0._default))
end if
if (pabs + p%x(3) <= 1000 * epsilon (pabs) * pabs) then
    chip = (/ cmplx ( 0.0, 0.0, kind=default), &
             cmplx ( 1.0, 0.0, kind=default) /)
    chim = (/ cmplx (-1.0, 0.0, kind=default), &
             cmplx ( 0.0, 0.0, kind=default) /)
else
    norm = 1 / sqrt (2*pabs*(pabs + p%x(3)))
    chip = norm * (/ cmplx (pabs + p%x(3), kind=default), &
                    cmplx (p%x(1), p%x(2), kind=default) /)
    chim = norm * (/ cmplx (-p%x(1), p%x(2), kind=default), &
                    cmplx (pabs + p%x(3), kind=default) /)
end if
if (s > 0) then
    psi%a(1:2) = delta * chip
    psi%a(3:4) = sqrt (p%t + pabs) * chip
else
    psi%a(1:2) = sqrt (p%t + pabs) * chim
    psi%a(3:4) = delta * chim
end if
pabs = m ! make the compiler happy and use m
if (mass < 0) then
    psi%a(1:2) = - imago * psi%a(1:2)
    psi%a(3:4) = + imago * psi%a(3:4)
end if
end function u

```

$$v_{\pm}(p) = \begin{pmatrix} \mp \sqrt{p_0 \pm |\vec{p}|} \cdot \chi_{\mp}(\vec{p}) \\ \pm \sqrt{p_0 \mp |\vec{p}|} \cdot \chi_{\mp}(\vec{p}) \end{pmatrix} \quad (\text{X.85})$$

(Implementation of bispinor on shell wave functions)+≡

```

pure function v (mass, p, s) result (psi)
type(bispinor) :: psi
real(kind=default), intent(in) :: mass
type(momentum), intent(in) :: p
integer, intent(in) :: s
complex(kind=default), dimension(2) :: chip, chim
real(kind=default) :: pabs, norm, delta, m
pabs = sqrt (dot_product (p%x, p%x))
m = abs(mass)
if (m < epsilon (m) * pabs) then
    delta = 0
else
    delta = sqrt (max (p%t - pabs, 0._default))
end if
if (pabs + p%x(3) <= 1000 * epsilon (pabs) * pabs) then

```

```

        chip = (/ cmplx ( 0.0, 0.0, kind=default), &
                 cmplx ( 1.0, 0.0, kind=default) /)
        chim = (/ cmplx (-1.0, 0.0, kind=default), &
                 cmplx ( 0.0, 0.0, kind=default) /)
    else
        norm = 1 / sqrt (2*pabs*(pabs + p%x(3)))
        chip = norm * (/ cmplx (pabs + p%x(3), kind=default), &
                        cmplx (p%x(1), p%x(2), kind=default) /)
        chim = norm * (/ cmplx (-p%x(1), p%x(2), kind=default), &
                        cmplx (pabs + p%x(3), kind=default) /)
    end if
    if (s > 0) then
        psi%a(1:2) = - sqrt (p%t + pabs) * chim
        psi%a(3:4) = delta * chim
    else
        psi%a(1:2) = delta * chip
        psi%a(3:4) = - sqrt (p%t + pabs) * chip
    end if
    pabs = m ! make the compiler happy and use m
    if (mass < 0) then
        psi%a(1:2) = - imago * psi%a(1:2)
        psi%a(3:4) = + imago * psi%a(3:4)
    end if
end function v

(Implementation of bispinor on shell wave functions)+≡
pure function ghost (m, p, s) result (psi)
    type(bispinor) :: psi
    real(kind=default), intent(in) :: m
    type(momentum), intent(in) :: p
    integer, intent(in) :: s
    psi%a(:) = 0
    select case (s)
    case (1)
        psi%a(1) = 1
        psi%a(2:4) = 0
    case (2)
        psi%a(1) = 0
        psi%a(2) = 1
        psi%a(3:4) = 0
    case (3)
        psi%a(1:2) = 0
        psi%a(3) = 1
        psi%a(4) = 0
    case (4)
        psi%a(1:3) = 0
        psi%a(4) = 1
    case (5)
        psi%a(1) = 1.4
        psi%a(2) = - 2.3
        psi%a(3) = - 71.5
        psi%a(4) = 0.1
    end select
end function ghost

```


X.14.7 Off Shell Wave Functions

This is the same as for the Dirac fermions except that the expressions for [ubar] and [vbar] are missing.

(Declaration of bispinor off shell wave functions)≡

```
public :: brs_u, brs_v
```

In momentum space we have:

$$brsu(p) = (-i)(\not{p} - m)u(p) \quad (X.86)$$

(Implementation of bispinor off shell wave functions)≡

```
pure function brs_u (m, p, s) result (dpsi)
  type(bispinor) :: dpsi, psi
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: p
  integer, intent(in) :: s
  type (vector)::vp
  complex(kind=default), parameter :: one = (1, 0)
  vp=p
  psi=u(m,p,s)
  dpsi=cplx(0.0,-1.0)*(f_vf(one,vp,psi)-m*psi)
end function brs_u
```

$$brsv(p) = i(\not{p} + m)v(p) \quad (X.87)$$

(Implementation of bispinor off shell wave functions)+≡

```
pure function brs_v (m, p, s) result (dpsi)
  type(bispinor) :: dpsi, psi
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: p
  integer, intent(in) :: s
  type (vector)::vp
  complex(kind=default), parameter :: one = (1, 0)
  vp=p
  psi=v(m,p,s)
  dpsi=cplx(0.0,1.0)*(f_vf(one,vp,psi)+m*psi)
end function brs_v
```

X.14.8 Propagators

(Declaration of bispinor propagators)≡

```
public :: pr_psi, pr_grav
public :: pj_psi, pg_psi
```

$$\frac{i(-\not{p} + m)}{p^2 - m^2 + im\Gamma}\psi \quad (X.88)$$

NB: the sign of the momentum comes about because all momenta are treated as *outgoing* and the particle charge flow is therefore opposite to the momentum.

(Implementation of bispinor propagators)≡

```
pure function pr_psi (p, m, w, psi) result (ppsi)
  type(bispinor) :: ppsi
  type(momentum), intent(in) :: p
```

```

real(kind=default), intent(in) :: m, w
type(bispinor), intent(in) :: psi
type(vector) :: vp
complex(kind=default), parameter :: one = (1, 0)
vp = p
ppsi = (1 / cmplx (p*p - m**2, m*w, kind=default)) &
      * (- f_vf (one, vp, psi) + m * psi)
end function pr_psi

```

$$\sqrt{\frac{\pi}{M\Gamma}}(-\not{p} + m)\psi \quad (\text{X.89})$$

(Implementation of bispinor propagators)+≡

```

pure function pj_psi (p, m, w, psi) result (ppsi)
type(bispinor) :: ppsi
type(momentum), intent(in) :: p
real(kind=default), intent(in) :: m, w
type(bispinor), intent(in) :: psi
type(vector) :: vp
complex(kind=default), parameter :: one = (1, 0)
vp = p
ppsi = (0, -1) * sqrt (PI / m / w) * (- f_vf (one, vp, psi) + m * psi)
end function pj_psi

```

(Implementation of bispinor propagators)+≡

```

pure function pg_psi (p, m, w, psi) result (ppsi)
type(bispinor) :: ppsi
type(momentum), intent(in) :: p
real(kind=default), intent(in) :: m, w
type(bispinor), intent(in) :: psi
type(vector) :: vp
complex(kind=default), parameter :: one = (1, 0)
vp = p
ppsi = gauss (p*p, m, w) * (- f_vf (one, vp, psi) + m * psi)
end function pg_psi

```

$$\frac{i \left\{ (-\not{p} + m) \left(-\eta_{\mu\nu} + \frac{p_\mu p_\nu}{m^2} \right) + \frac{1}{3} \left(\gamma_\mu - \frac{p_\mu}{m} \right) (\not{p} + m) \left(\gamma_\nu - \frac{p_\nu}{m} \right) \right\}}{p^2 - m^2 + im\Gamma} \psi^\nu \quad (\text{X.90})$$

(Implementation of bispinor propagators)+≡

```

pure function pr_grav (p, m, w, grav) result (propgrav)
type(vectorspinor) :: propgrav
type(momentum), intent(in) :: p
real(kind=default), intent(in) :: m, w
type(vectorspinor), intent(in) :: grav
type(vector) :: vp
type(bispinor) :: pgrav, ggrav, ggrav1, ggrav2, ppgrav
type(vectorspinor) :: etagrav_dum, etagrav, pppgrav, &
      gg_grav_dum, gg_grav
complex(kind=default), parameter :: one = (1, 0)
real(kind=default) :: minv
integer :: i
vp = p

```

```

minv = 1/m
pgrav = p%t      * grav%psi(1) - p%x(1) * grav%psi(2) - &
          p%x(2) * grav%psi(3) - p%x(3) * grav%psi(4)
ggrav%a(1) = grav%psi(1)%a(3) - grav%psi(2)%a(4) + (0,1) * &
          grav%psi(3)%a(4) - grav%psi(4)%a(3)
ggrav%a(2) = grav%psi(1)%a(4) - grav%psi(2)%a(3) - (0,1) * &
          grav%psi(3)%a(3) + grav%psi(4)%a(4)
ggrav%a(3) = grav%psi(1)%a(1) + grav%psi(2)%a(2) - (0,1) * &
          grav%psi(3)%a(2) + grav%psi(4)%a(1)
ggrav%a(4) = grav%psi(1)%a(2) + grav%psi(2)%a(1) + (0,1) * &
          grav%psi(3)%a(1) - grav%psi(4)%a(2)
ggrav1 = ggrav - minv * pgrav
ggrav2 = f_vf (one, vp, ggrav1) + m * ggrav - pgrav
ppgrav = (-minv**2) * f_vf (one, vp, pgrav) + minv * pgrav
do i = 1, 4
  etagrav_dum%psi(i) = f_vf (one, vp, grav%psi(i))
end do
etagrav = etagrav_dum - m * grav
pppgrav%psi(1) = p%t      * ppgrav
pppgrav%psi(2) = p%x(1) * ppgrav
pppgrav%psi(3) = p%x(2) * ppgrav
pppgrav%psi(4) = p%x(3) * ppgrav
gg_grav_dum%psi(1) = p%t      * ggrav2
gg_grav_dum%psi(2) = p%x(1) * ggrav2
gg_grav_dum%psi(3) = p%x(2) * ggrav2
gg_grav_dum%psi(4) = p%x(3) * ggrav2
gg_grav = gr_potf (one, one, ggrav2) - minv * gg_grav_dum
propgrav = (1 / cplx (p*p - m**2, m*w, kind=default)) * &
  (etagrav + pppgrav + (1/3.0_default) * gg_grav)
end function pr_grav

```

X.15 Polarization vectorspinors

Here we construct the wavefunctions for (massive) gravitinos out of the wavefunctions of (massive) vectorbosons and (massive) Majorana fermions.

$$\psi_{(u;3/2)}^\mu(k) = \epsilon_+^\mu(k) \cdot u(k, +) \quad (\text{X.91a})$$

$$\psi_{(u;1/2)}^\mu(k) = \sqrt{\frac{1}{3}} \epsilon_+^\mu(k) \cdot u(k, -) + \sqrt{\frac{2}{3}} \epsilon_0^\mu(k) \cdot u(k, +) \quad (\text{X.91b})$$

$$\psi_{(u;-1/2)}^\mu(k) = \sqrt{\frac{2}{3}} \epsilon_0^\mu(k) \cdot u(k, -) + \sqrt{\frac{1}{3}} \epsilon_-^\mu(k) \cdot u(k, +) \quad (\text{X.91c})$$

$$\psi_{(u;-3/2)}^\mu(k) = \epsilon_-^\mu(k) \cdot u(k, -) \quad (\text{X.91d})$$

and in the same manner for $\psi_{(v;s)}^\mu$ with u replaced by v and with the conjugated polarization vectors. These gravitino wavefunctions obey the Dirac equation, they are transverse and they fulfill the irreducibility condition

$$\gamma_\mu \psi_{(u/v;s)}^\mu = 0. \quad (\text{X.92})$$

`<omega_vspinor_polarizations.f90>≡
<Copleft>`

```

module omega_vspinor_polarizations
  use kinds
  use constants
  use omega_vectors
  use omega_bispinors
  use omega_bispinor_couplings
  use omega_vectorspinors
  implicit none
  <Declaration of polarization vectorspinors>
  integer, parameter, public :: omega_vspinor_pols_2010_01_A = 0
contains
  <Implementation of polarization vectorspinors>
end module omega_vspinor_polarizations

<Declaration of polarization vectorspinors>≡
  public :: ueps, veps
  private :: eps
  private :: outer_product

```

Here we implement the polarization vectors for vectorbosons with trigonometric functions, without the rotating of components done in HELAS [5]. These are only used for generating the polarization vectorspinors.

$$\epsilon_+^\mu(k) = \frac{-e^{+i\phi}}{\sqrt{2}} (0; \cos\theta \cos\phi - i \sin\phi, \cos\theta \sin\phi + i \cos\phi, -\sin\theta) \quad (\text{X.93a})$$

$$\epsilon_-^\mu(k) = \frac{e^{-i\phi}}{\sqrt{2}} (0; \cos\theta \cos\phi + i \sin\phi, \cos\theta \sin\phi - i \cos\phi, -\sin\theta) \quad (\text{X.93b})$$

$$\epsilon_0^\mu(k) = \frac{1}{m} \left(|\vec{k}|; k^0 \sin\theta \cos\phi, k^0 \sin\theta \sin\phi, k^0 \cos\theta \right) \quad (\text{X.93c})$$

Determining the mass from the momenta is a numerically haphazardous for light particles. Therefore, we accept some redundancy and pass the mass explicitly. For the case that the momentum lies totally in the z -direction we take the convention $\cos\phi = 1$ and $\sin\phi = 0$.

```

<Implementation of polarization vectorspinors>≡
  pure function eps (mass, k, s) result (e)
    type(vector) :: e
    real(kind=default), intent(in) :: mass
    type(momentum), intent(in) :: k
    integer, intent(in) :: s
    real(kind=default) :: kabs, kabs2, sqrt2, m
    real(kind=default) :: cos_phi, sin_phi, cos_th, sin_th
    complex(kind=default) :: epiphi, emiphi
    sqrt2 = sqrt (2.0_default)
    kabs2 = dot_product (k%x, k%x)
    m = abs(mass)
    if (kabs2 > 0) then
      kabs = sqrt (kabs2)
      if ((k%x(1) == 0) .and. (k%x(2) == 0)) then
        cos_phi = 1
        sin_phi = 0
      else
        cos_phi = k%x(1) / sqrt(k%x(1)**2 + k%x(2)**2)
        sin_phi = k%x(2) / sqrt(k%x(1)**2 + k%x(2)**2)

```

```

end if
cos_th = k%x(3) / kabs
sin_th = sqrt(1 - cos_th**2)
ephiphi = cos_phi + (0,1) * sin_phi
emiphi = cos_phi - (0,1) * sin_phi
e%t = 0
e%x = 0
select case (s)
case (1)
  e%x(1) = ehiphi * (-cos_th * cos_phi + (0,1) * sin_phi) / sqrt2
  e%x(2) = ehiphi * (-cos_th * sin_phi - (0,1) * cos_phi) / sqrt2
  e%x(3) = ehiphi * ( sin_th / sqrt2)
case (-1)
  e%x(1) = emiphi * ( cos_th * cos_phi + (0,1) * sin_phi) / sqrt2
  e%x(2) = emiphi * ( cos_th * sin_phi - (0,1) * cos_phi) / sqrt2
  e%x(3) = emiphi * (-sin_th / sqrt2)
case (0)
  if (m > 0) then
    e%t = kabs / m
    e%x = k%t / (m*kabs) * k%x
  end if
case (4)
  if (m > 0) then
    e = (1 / m) * k
  else
    e = (1 / k%t) * k
  end if
end select
else  !!! for particles in their rest frame defined to be
      !!! polarized along the 3-direction
  e%t = 0
  e%x = 0
  select case (s)
  case (1)
    e%x(1) = cmplx ( - 1, 0, kind=default) / sqrt2
    e%x(2) = cmplx ( 0, 1, kind=default) / sqrt2
  case (-1)
    e%x(1) = cmplx ( 1, 0, kind=default) / sqrt2
    e%x(2) = cmplx ( 0, 1, kind=default) / sqrt2
  case (0)
    if (m > 0) then
      e%x(3) = 1
    end if
  case (4)
    if (m > 0) then
      e = (1 / m) * k
    else
      e = (1 / k%t) * k
    end if
  end select
end if
end function eps

```

(Implementation of polarization vectorspinors)+≡
 pure function ueps (m, k, s) result (t)

```

type(vectorspinor) :: t
real(kind=default), intent(in) :: m
type(momentum), intent(in) :: k
integer, intent(in) :: s
integer :: i
type(vector) :: ep, e0, em
type(bispinor) :: up, um
do i = 1, 4
    t%psi(i)%a = 0
end do
select case (s)
case (2)
    ep = eps (m, k, 1)
    up = u (m, k, 1)
    t = outer_product (ep, up)
case (1)
    ep = eps (m, k, 1)
    e0 = eps (m, k, 0)
    up = u (m, k, 1)
    um = u (m, k, -1)
    t = (1 / sqrt (3.0_default)) * (outer_product (ep, um) &
        + sqrt (2.0_default) * outer_product (e0, up))
case (-1)
    e0 = eps (m, k, 0)
    em = eps (m, k, -1)
    up = u (m, k, 1)
    um = u (m, k, -1)
    t = (1 / sqrt (3.0_default)) * (sqrt (2.0_default) * &
        outer_product (e0, um) + outer_product (em, up))
case (-2)
    em = eps (m, k, -1)
    um = u (m, k, -1)
    t = outer_product (em, um)
end select
end function ueps

```

(Implementation of polarization vectorspinors)+≡

```

pure function veps (m, k, s) result (t)
type(vectorspinor) :: t
real(kind=default), intent(in) :: m
type(momentum), intent(in) :: k
integer, intent(in) :: s
integer :: i
type(vector) :: ep, e0, em
type(bispinor) :: vp, vm
do i = 1, 4
    t%psi(i)%a = 0
end do
select case (s)
case (2)
    ep = conjg(eps (m, k, 1))
    vp = v (m, k, 1)
    t = outer_product (ep, vp)
case (1)
    ep = conjg(eps (m, k, 1))

```

```

    e0 = conjg(eps (m, k, 0))
    vp = v (m, k, 1)
    vm = v (m, k, -1)
    t = (1 / sqrt (3.0_default)) * (outer_product (ep, vm) &
        + sqrt (2.0_default) * outer_product (e0, vp))
case (-1)
    e0 = conjg(eps (m, k, 0))
    em = conjg(eps (m, k, -1))
    vp = v (m, k, 1)
    vm = v (m, k, -1)
    t = (1 / sqrt (3.0_default)) * (sqrt (2.0_default) &
        * outer_product (e0, vm) + outer_product (em, vp))
case (-2)
    em = conjg(eps (m, k, -1))
    vm = v (m, k, -1)
    t = outer_product (em, vm)
end select
end function veps

```

(Implementation of polarization vectorspinors) \equiv

```

pure function outer_product (ve, sp) result (vs)
    type(vectorspinor) :: vs
    type(vector), intent(in) :: ve
    type(bispinor), intent(in) :: sp
    integer :: i
    vs%psi(1)%a(1:4) = ve%t * sp%a(1:4)
    do i = 1, 3
        vs%psi((i+1))%a(1:4) = ve%x(i) * sp%a(1:4)
    end do
end function outer_product

```

X.16 Color

(omega_color.f90) \equiv

(Cotypeleft)

```

module omega_color
    use kinds
    implicit none
    private
    (Declaration of color types)
    (Declaration of color functions)
    integer, parameter, public :: omega_color_2010_01_A = 0
contains
    (Implementation of color functions)
end module omega_color

```

X.16.1 Color Sum

(Declaration of color types) \equiv

```

public :: omega_color_factor
type omega_color_factor
    integer :: i1, i2
    complex(kind=default) :: factor

```

```

end type omega_color_factor

<Declaration of color functions>≡
public :: omega_color_sum

<Implementation of color functions>≡
pure function omega_color_sum (flv, hel, amp, cf) result (amp2)
  complex(kind=default) :: amp2
  integer, intent(in) :: flv, hel
  complex(kind=default), dimension(:,:), intent(in) :: amp
  type(omega_color_factor), dimension(:), intent(in) :: cf
  integer :: n
  amp2 = 0
  do n = 1, size (cf)
    amp2 = amp2 &
      + cf(n)%factor * amp(flv,cf(n)%i1,hel) * conjg (amp(flv,cf(n)%i2,hel))
  end do
end function omega_color_sum

```

X.17 Utilities

```

<omega_utils.f90>≡
<Copyleft>
module omega_utils
  use kinds
  use omega_vectors
  use omega_polarizations
  implicit none
  private
  <Declaration of utility functions>
  <Numerical tolerances>
  integer, parameter, public :: omega_utils_2010_01_A = 0
contains
  <Implementation of utility functions>
end module omega_utils

```

X.17.1 Helicity Selection Rule Heuristics

```

<Declaration of utility functions>≡
public :: omega_update_helicity_selection

<Implementation of utility functions>≡
pure subroutine omega_update_helicity_selection &
  (count, amp, max_abs, sum_abs, mask, threshold, cutoff, mask_dirty)
  integer, intent(inout) :: count
  complex(kind=default), dimension(:,:), intent(in) :: amp
  real(kind=default), dimension(:), intent(inout) :: max_abs
  real(kind=default), intent(inout) :: sum_abs
  logical, dimension(:), intent(inout) :: mask
  real(kind=default), intent(in) :: threshold
  integer, intent(in) :: cutoff
  logical, intent(out) :: mask_dirty
  integer :: h
  real(kind=default) :: avg

```



```

mask_dirty = .false.
if (threshold > 0) then
  count = count + 1
  if (count <= cutoff) then
    forall (h = lbound (amp, 3) : ubound (amp, 3))
      max_abs(h) = max (max_abs(h), maxval (abs (amp(:,h))))
    end forall
    sum_abs = sum_abs + sum (abs (amp))
    if (count == cutoff) then
      avg = sum_abs / size (amp) / cutoff
      mask = max_abs >= threshold * epsilon (avg) * avg
      mask_dirty = .true.
    end if
  end if
end if
end subroutine omega_update_helicity_selection

```

X.17.2 Diagnostics

(Declaration of utility functions)+≡

```
public :: omega_report_helicity_selection
```

We should try to use `msg_message` from WHIZARD's diagnostics module, but this would spoil independent builds.

(Implementation of utility functions)+≡

```

subroutine omega_report_helicity_selection (mask, spin_states, threshold, unit)
  logical, dimension(:), intent(in) :: mask
  integer, dimension(:,:), intent(in) :: spin_states
  real(kind=default), intent(in) :: threshold
  integer, intent(in), optional :: unit
  integer :: u
  integer :: h, i
  if (present(unit)) then
    u = unit
  else
    u = 6
  end if
  if (u >= 0) then
    write (unit = u, &
      fmt = "('| ', 'Contributing Helicity Combinations: ', I5, ' of ', I5)") &
      count (mask), size (mask)
    write (unit = u, &
      fmt = "('| ', 'Threshold: amp / avg > ', E9.2, ' = ', E9.2, ' * epsilon()')") &
      threshold * epsilon (threshold), threshold
    i = 0
    do h = 1, size (mask)
      if (mask(h)) then
        i = i + 1
        write (unit = u, fmt = "('| ', I4, ': ', 20I4)") i, spin_states (:, h)
      end if
    end do
  end if
end subroutine omega_report_helicity_selection

```

<Declaration of utility functions>+≡

```
public :: omega_ward_warn, omega_ward_panic
```

The O'Mega amplitudes have only one particle off shell and are the sum of *all* possible diagrams with the other particles on-shell.



The problem with these gauge checks is that are numerically very small amplitudes that vanish analytically and that violate transversality. The hard part is to determine the thresholds that make these tests usable.

<Implementation of utility functions>+≡

```
subroutine omega_ward_warn (name, m, k, e)
  character(len=*), intent(in) :: name
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: k
  type(vector), intent(in) :: e
  type(vector) :: ek
  real(kind=default) :: abs_eke, abs_ek_abs_e
  ek = eps (m, k, 4)
  abs_eke = abs (ek * e)
  abs_ek_abs_e = abs (ek) * abs (e)
  print *, name, ":", abs_eke / abs_ek_abs_e, abs (ek), abs (e)
  if (abs_eke > 1000 * epsilon (abs_ek_abs_e)) then
    print *, "O'Mega: warning: non-transverse vector field: ", &
      name, ":", abs_eke / abs_ek_abs_e, abs (e)
  end if
end subroutine omega_ward_warn
```

<Implementation of utility functions>+≡

```
subroutine omega_ward_panic (name, m, k, e)
  character(len=*), intent(in) :: name
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: k
  type(vector), intent(in) :: e
  type(vector) :: ek
  real(kind=default) :: abs_eke, abs_ek_abs_e
  ek = eps (m, k, 4)
  abs_eke = abs (ek * e)
  abs_ek_abs_e = abs (ek) * abs (e)
  if (abs_eke > 1000 * epsilon (abs_ek_abs_e)) then
    print *, "O'Mega: panic: non-transverse vector field: ", &
      name, ":", abs_eke / abs_ek_abs_e, abs (e)
    stop
  end if
end subroutine omega_ward_panic
```

<Declaration of utility functions>+≡

```
public :: omega_slavnov_warn, omega_slavnov_panic
```

<Implementation of utility functions>+≡

```
subroutine omega_slavnov_warn (name, m, k, e, phi)
  character(len=*), intent(in) :: name
  real(kind=default), intent(in) :: m
  type(momentum), intent(in) :: k
  type(vector), intent(in) :: e
  complex(kind=default), intent(in) :: phi
  type(vector) :: ek
```

```

    real(kind=default) :: abs_eke, abs_ek_abs_e
    ek = eps (m, k, 4)
    abs_eke = abs (ek * e - phi)
    abs_ek_abs_e = abs (ek) * abs (e)
    print *, name, ":", abs_eke / abs_ek_abs_e, abs (ek), abs (e)
    if (abs_eke > 1000 * epsilon (abs_ek_abs_e)) then
        print *, "O'Mega: warning: non-transverse vector field: ", &
            name, ":", abs_eke / abs_ek_abs_e, abs (e)
    end if
end subroutine omega_slavnov_warn

<Implementation of utility functions>+≡
subroutine omega_slavnov_panic (name, m, k, e, phi)
    character(len=*), intent(in) :: name
    real(kind=default), intent(in) :: m
    type(momentum), intent(in) :: k
    type(vector), intent(in) :: e
    complex(kind=default), intent(in) :: phi
    type(vector) :: ek
    real(kind=default) :: abs_eke, abs_ek_abs_e
    ek = eps (m, k, 4)
    abs_eke = abs (ek * e - phi)
    abs_ek_abs_e = abs (ek) * abs (e)
    if (abs_eke > 1000 * epsilon (abs_ek_abs_e)) then
        print *, "O'Mega: panic: non-transverse vector field: ", &
            name, ":", abs_eke / abs_ek_abs_e, abs (e)
        stop
    end if
end subroutine omega_slavnov_panic

<Declaration of utility functions>+≡
public :: omega_check_arguments_warn, omega_check_arguments_panic

<Implementation of utility functions>+≡
subroutine omega_check_arguments_warn (n, k)
    integer, intent(in) :: n
    real(kind=default), dimension(0:,:), intent(in) :: k
    integer :: i
    i = size(k,dim=1)
    if (i /= 4) then
        print *, "O'Mega: warning: wrong # of dimensions:", i
    end if
    i = size(k,dim=2)
    if (i /= n) then
        print *, "O'Mega: warning: wrong # of momenta:", i, &
            ", expected", n
    end if
end subroutine omega_check_arguments_warn

<Implementation of utility functions>+≡
subroutine omega_check_arguments_panic (n, k)
    integer, intent(in) :: n
    real(kind=default), dimension(0:,:), intent(in) :: k
    logical :: error
    integer :: i
    error = .false.

```

```

i = size(k,dim=1)
if (i /= n) then
  print *, "O'Mega: warning: wrong # of dimensions:", i
  error = .true.
end if
i = size(k,dim=2)
if (i /= n) then
  print *, "O'Mega: warning: wrong # of momenta:", i, &
    ", expected", n
  error = .true.
end if
if (error) then
  stop
end if
end subroutine omega_check_arguments_panic

<Declaration of utility functions>+≡
public :: omega_check_helicities_warn, omega_check_helicities_panic
private :: omega_check_helicity

<Implementation of utility functions>+≡
function omega_check_helicity (m, smax, s) result (error)
  real(kind=default), intent(in) :: m
  integer, intent(in) :: smax, s
  logical :: error
  select case (smax)
  case (0)
    error = (s /= 0)
  case (1)
    error = (abs (s) /= 1)
  case (2)
    if (m == 0.0_default) then
      error = .not. (abs (s) == 1 .or. abs (s) == 4)
    else
      error = .not. (abs (s) <= 1 .or. abs (s) == 4)
    end if
  case (4)
    error = .true.
  case default
    error = .true.
  end select
end function omega_check_helicity

<Implementation of utility functions>+≡
subroutine omega_check_helicities_warn (m, smax, s)
  real(kind=default), dimension(:), intent(in) :: m
  integer, dimension(:), intent(in) :: smax, s
  integer :: i
  do i = 1, size (m)
    if (omega_check_helicity (m(i), smax(i), s(i))) then
      print *, "O'Mega: warning: invalid helicity", s(i)
    end if
  end do
end subroutine omega_check_helicities_warn

<Implementation of utility functions>+≡

```

```

subroutine omega_check_helicities_panic (m, smax, s)
  real(kind=default), dimension(:), intent(in) :: m
  integer, dimension(:), intent(in) :: smax, s
  logical :: error
  logical :: error1
  integer :: i
  error = .false.
  do i = 1, size (m)
    error1 = omega_check_helicity (m(i), smax(i), s(i))
    if (error1) then
      print *, "O'Mega: panic: invalid helicity", s(i)
      error = .true.
    end if
  end do
  if (error) then
    stop
  end if
end subroutine omega_check_helicities_panic

<Declaration of utility functions>+≡
public :: omega_check_momenta_warn, omega_check_momenta_panic
private :: check_momentum_conservation, check_mass_shell

<Numerical tolerances>≡
integer, parameter, private :: MOMENTUM_TOLERANCE = 10000

<Implementation of utility functions>+≡
function check_momentum_conservation (k) result (error)
  real(kind=default), dimension(0:,:), intent(in) :: k
  logical :: error
  error = any (abs (sum (k(:,3:), dim = 2) - k(:,1) - k(:,2)) > &
    MOMENTUM_TOLERANCE * epsilon (maxval (abs (k), dim = 2)))
  if (error) then
    print *, sum (k(:,3:), dim = 2) - k(:,1) - k(:,2)
    print *, MOMENTUM_TOLERANCE * epsilon (maxval (abs (k), dim = 2)), &
      maxval (abs (k), dim = 2)
  end if
end function check_momentum_conservation

<Numerical tolerances>+≡
integer, parameter, private :: ON_SHELL_TOLERANCE = 1000000

<Implementation of utility functions>+≡
function check_mass_shell (m, k) result (error)
  real(kind=default), intent(in) :: m
  real(kind=default), dimension(0:), intent(in) :: k
  real(kind=default) :: e2
  logical :: error
  e2 = k(1)**2 + k(2)**2 + k(3)**2 + m**2
  error = abs (k(0)**2 - e2) > ON_SHELL_TOLERANCE * epsilon (max (k(0)**2, e2))
  if (error) then
    print *, k(0)**2 - e2
    print *, ON_SHELL_TOLERANCE * epsilon (max (k(0)**2, e2)), max (k(0)**2, e2)
  end if
end function check_mass_shell

<Implementation of utility functions>+≡

```

```

subroutine omega_check_momenta_warn (m, k)
  real(kind=default), dimension(:), intent(in) :: m
  real(kind=default), dimension(0:,:), intent(in) :: k
  integer :: i
  if (check_momentum_conservation (k)) then
    print *, "O'Mega: warning: momentum not conserved"
  end if
  do i = 1, size(m)
    if (check_mass_shell (m(i), k(:,i))) then
      print *, "O'Mega: warning: particle #", i, "not on-shell"
    end if
  end do
end subroutine omega_check_momenta_warn

```

(Implementation of utility functions)+≡

```

subroutine omega_check_momenta_panic (m, k)
  real(kind=default), dimension(:), intent(in) :: m
  real(kind=default), dimension(0:,:), intent(in) :: k
  logical :: error
  logical :: error1
  integer :: i
  error = check_momentum_conservation (k)
  if (error) then
    print *, "O'Mega: panic: momentum not conserved"
  end if
  do i = 1, size(m)
    error1 = check_mass_shell (m(i), k(0:,i))
    if (error1) then
      print *, "O'Mega: panic: particle #", i, "not on-shell"
      error = .true.
    end if
  end do
  if (error) then
    stop
  end if
end subroutine omega_check_momenta_panic

```

X.17.3 *Obsolete Summation*

Spin/Helicity Summation

(Declaration of obsolete utility functions)≡

```

public :: omega_sum, omega_sum_nonzero, omega_nonzero
private :: state_index

```

(Implementation of obsolete utility functions)≡

```

pure function omega_sum (omega, p, states, fixed) result (sigma)
  real(kind=default) :: sigma
  real(kind=default), dimension(0:,:), intent(in) :: p
  integer, dimension(:), intent(in), optional :: states, fixed
  <interface for O'Mega Amplitude>
  integer, dimension(size(p,dim=2)) :: s, nstates
  integer :: j
  complex(kind=default) :: a
  if (present (states)) then

```

```

        nstates = states
    else
        nstates = 2
    end if
    sigma = 0
    s = -1
    sum_spins: do
        if (present (fixed)) then
            !!! print *, 's = ', s, ', fixed = ', fixed, ', nstates = ', nstates, &
            !!!      ', fixed|s = ', merge (fixed, s, mask = nstates == 0)
            a = omega (p, merge (fixed, s, mask = nstates == 0))
        else
            a = omega (p, s)
        end if
        sigma = sigma + a * conjg(a)
        <Step s like a n-ary number and terminate when all (s == -1)>
    end do sum_spins
    sigma = sigma / num_states (2, nstates(1:2))
end function omega_sum

```

We're looping over all spins like a n -ary numbers $(-1, \dots, -1, -1)$, $(-1, \dots, -1, 0)$, $(-1, \dots, -1, 1)$, $(-1, \dots, 0, -1)$, \dots , $(1, \dots, 1, 0)$, $(1, \dots, 1, 1)$:

```

<Step s like a n-ary number and terminate when all (s == -1)>≡
    do j = size (p, dim = 2), 1, -1
        select case (nstates (j))
        case (3) ! massive vectors
            s(j) = modulo (s(j) + 2, 3) - 1
        case (2) ! spinors, massless vectors
            s(j) = - s(j)
        case (1) ! scalars
            s(j) = -1
        case (0) ! fized spin
            s(j) = -1
        case default ! ???
            s(j) = -1
        end select
        if (s(j) /= -1) then
            cycle sum_spins
        end if
    end do
    exit sum_spins

```

The dual operation evaluates an n -number:

```

<Implementation of obsolete utility functions>+≡
    pure function state_index (s, states) result (n)
        integer, dimension(:), intent(in) :: s
        integer, dimension(:), intent(in), optional :: states
        integer :: n
        integer :: j, p
        n = 1
        p = 1
        if (present (states)) then
            do j = size (s), 1, -1
                select case (states(j))
                case (3)

```

```

        n = n + p * (s(j) + 1)
      case (2)
        n = n + p * (s(j) + 1) / 2
      end select
      p = p * states(j)
    end do
  else
    do j = size (s), 1, -1
      n = n + p * (s(j) + 1) / 2
      p = p * 2
    end do
  end if
end function state_index
<interface for O'Mega Amplitude>≡
interface
  pure function omega (p, s) result (me)
    use kinds
    implicit none
    complex(kind=default) :: me
    real(kind=default), dimension(0,:), intent(in) :: p
    integer, dimension(:), intent(in) :: s
  end function omega
end interface
<Declaration of obsolete utility functions>+≡
public :: num_states
<Implementation of obsolete utility functions>+≡
pure function num_states (n, states) result (ns)
  integer, intent(in) :: n
  integer, dimension(:), intent(in), optional :: states
  integer :: ns
  if (present (states)) then
    ns = product (states, mask = states == 2 .or. states == 3)
  else
    ns = 2**n
  end if
end function num_states

```

X.18 omega95

```

<omega95.f90>≡
<Copyleft>
module omega95
  use constants
  use omega_spinors
  use omega_vectors
  use omega_polarizations
  use omega_tensors
  use omega_tensor_polarizations
  use omega_couplings
  use omega_spinor_couplings
  use omega_color
  use omega_utils

```



```

public
end module omega95

```

X.19 omega95 Revisited

```

⟨omega95_bispinors.f90⟩≡
⟨Copyleft⟩
module omega95_bispinors
  use constants
  use omega_bispinors
  use omega_vectors
  use omega_vectorspinors
  use omega_polarizations
  use omega_vspinor_polarizations
  use omega_couplings
  use omega_bispinor_couplings
  use omega_color
  use omega_utils
public
end module omega95_bispinors

```

X.20 Testing

```

⟨omega_testtools.f90⟩≡
⟨Copyleft⟩
module omega_testtools
  use kinds
  implicit none
  private
  real(kind=default), parameter, private :: THRESHOLD_DEFAULT = 0.6
  real(kind=default), parameter, private :: THRESHOLD_WARN = 0.8
  ⟨Declaration of test support functions⟩
contains
  ⟨Implementation of test support functions⟩
end module omega_testtools

```

Quantify the agreement of two real or complex numbers

$$\text{agreement}(x, y) = \frac{\ln \Delta(x, y)}{\ln \epsilon} \in [0, 1] \quad (\text{X.94})$$

with

$$\Delta(x, y) = \frac{|x - y|}{\max(|x|, |y|)} \quad (\text{X.95})$$

and values outside $[0, 1]$ replaced the closed value in the interval. In other words

- 1 for $x - y = \max(|x|, |y|) \cdot \mathcal{O}(\epsilon)$ and
- 0 for $x - y = \max(|x|, |y|) \cdot \mathcal{O}(1)$

with logarithmic interpolation. The cases $x = 0$ and $y = 0$ must be treated separately.

```

⟨Declaration of test support functions⟩≡

```

```

public :: agreement
interface agreement
    module procedure agreement_real, agreement_complex, &
        agreement_real_complex, agreement_complex_real, &
        agreement_integer_complex, agreement_complex_integer, &
        agreement_integer_real, agreement_real_integer
end interface
private :: agreement_real, agreement_complex, &
    agreement_real_complex, agreement_complex_real, &
    agreement_integer_complex, agreement_complex_integer, &
    agreement_integer_real, agreement_real_integer

<Implementation of test support functions>≡
elemental function agreement_real (x, y, base) result (a)
    real(kind=default) :: a
    real(kind=default), intent(in) :: x, y
    real(kind=default), intent(in), optional :: base
    real(kind=default) :: scale, dxy
    if (present (base)) then
        scale = max (abs (x), abs (y), abs (base))
    else
        scale = max (abs (x), abs (y))
    end if
    if (ieee_is_nan (x) .or. ieee_is_nan (y)) then
        a = 0
    else if (scale <= 0) then
        a = -1
    else
        dxy = abs (x - y) / scale
        if (dxy <= 0.0_default) then
            a = 1
        else
            a = log (dxy) / log (epsilon (scale))
            a = max (0.0_default, min (1.0_default, a))
            if (ieee_is_nan (a)) then
                a = 0
            end if
        end if
    end if
    if (ieee_is_nan (a)) then
        a = 0
    end if
end function agreement_real

Poor man's replacement

<Implementation of test support functions>+≡
elemental function ieee_is_nan (x) result (yorn)
    logical :: yorn
    real (kind=default), intent(in) :: x
    yorn = (x /= x)
end function ieee_is_nan

<Implementation of test support functions>+≡
elemental function agreement_complex (x, y, base) result (a)
    real(kind=default) :: a
    complex(kind=default), intent(in) :: x, y

```

```

real(kind=default), intent(in), optional :: base
real(kind=default) :: scale, dxy
if (present (base)) then
    scale = max (abs (x), abs (y), abs (base))
else
    scale = max (abs (x), abs (y))
end if
if (      ieee_is_nan (real (x, kind=default)) .or. ieee_is_nan (aimag (x)) &
    .or. ieee_is_nan (real (y, kind=default)) .or. ieee_is_nan (aimag (y))) then
    a = 0
else if (scale <= 0) then
    a = -1
else
    dxy = abs (x - y) / scale
    if (dxy <= 0.0_default) then
        a = 1
    else
        a = log (dxy) / log (epsilon (scale))
        a = max (0.0_default, min (1.0_default, a))
        if (ieee_is_nan (a)) then
            a = 0
        end if
    end if
end if
if (ieee_is_nan (a)) then
    a = 0
end if
end function agreement_complex

```

(Implementation of test support functions)+≡

```

elemental function agreement_real_complex (x, y, base) result (a)
real(kind=default) :: a
real(kind=default), intent(in) :: x
complex(kind=default), intent(in) :: y
real(kind=default), intent(in), optional :: base
a = agreement_complex (cmplx (x, kind=default), y, base)
end function agreement_real_complex

```

(Implementation of test support functions)+≡

```

elemental function agreement_complex_real (x, y, base) result (a)
real(kind=default) :: a
complex(kind=default), intent(in) :: x
real(kind=default), intent(in) :: y
real(kind=default), intent(in), optional :: base
a = agreement_complex (x, cmplx (y, kind=default), base)
end function agreement_complex_real

```

(Implementation of test support functions)+≡

```

elemental function agreement_integer_complex (x, y, base) result (a)
real(kind=default) :: a
integer, intent(in) :: x
complex(kind=default), intent(in) :: y
real(kind=default), intent(in), optional :: base
a = agreement_complex (cmplx (x, kind=default), y, base)
end function agreement_integer_complex

```

```

<Implementation of test support functions>+≡
elemental function agreement_complex_integer (x, y, base) result (a)
  real(kind=default) :: a
  complex(kind=default), intent(in) :: x
  integer, intent(in) :: y
  real(kind=default), intent(in), optional :: base
  a = agreement_complex (x, cmplx (y, kind=default), base)
end function agreement_complex_integer

```

```

<Implementation of test support functions>+≡
elemental function agreement_integer_real (x, y, base) result (a)
  real(kind=default) :: a
  integer, intent(in) :: x
  real(kind=default), intent(in) :: y
  real(kind=default), intent(in), optional :: base
  a = agreement_real (real(x, kind=default), y, base)
end function agreement_integer_real

```

```

<Implementation of test support functions>+≡
elemental function agreement_real_integer (x, y, base) result (a)
  real(kind=default) :: a
  real(kind=default), intent(in) :: x
  integer, intent(in) :: y
  real(kind=default), intent(in), optional :: base
  a = agreement_real (x, real (y, kind=default), base)
end function agreement_real_integer

```

```

<Declaration of test support functions>+≡
public:: vanishes
interface vanishes
  module procedure vanishes_real, vanishes_complex
end interface
private :: vanishes_real, vanishes_complex

```

```

<Implementation of test support functions>+≡
elemental function vanishes_real (x, scale) result (a)
  real(kind=default) :: a
  real(kind=default), intent(in) :: x
  real(kind=default), intent(in), optional :: scale
  real(kind=default) :: scaled_x
  if (x == 0.0_default) then
    a = 1
    return
  else if (ieee_is_nan (x)) then
    a = 0
    return
  end if
  scaled_x = x
  if (present (scale)) then
    if (scale /= 0) then
      scaled_x = x / abs (scale)
    else
      a = 0
      return
    end if
  else
    a = 0
  end if
end function vanishes_real

```

```

    end if
    a = log (abs (scaled_x)) / log (epsilon (scaled_x))
    a = max (0.0_default, min (1.0_default, a))
    if (ieee_is_nan (a)) then
        a = 0
    end if
end function vanishes_real

<Implementation of test support functions>+≡
elemental function vanishes_complex (x, scale) result (a)
    real(kind=default) :: a
    complex(kind=default), intent(in) :: x
    real(kind=default), intent(in), optional :: scale
    a = vanishes_real (abs (x), scale)
end function vanishes_complex

<Declaration of test support functions>+≡
public :: expect
interface expect
    module procedure expect_integer, expect_real, expect_complex, &
        expect_real_integer, expect_integer_real, &
        expect_complex_integer, expect_integer_complex, &
        expect_complex_real, expect_real_complex
end interface
private :: expect_integer, expect_real, expect_complex, &
    expect_real_integer, expect_integer_real, &
    expect_complex_integer, expect_integer_complex, &
    expect_complex_real, expect_real_complex

<Implementation of test support functions>+≡
subroutine expect_integer (x, x0, msg, passed, quiet, buffer, unit)
    integer, intent(in) :: x, x0
    character(len=*), intent(in) :: msg
    logical, intent(inout), optional :: passed
    logical, intent(in), optional :: quiet
    character(len=*), intent(inout), optional :: buffer
    integer, intent(in), optional :: unit
    logical :: failed, verbose
    character(len=*), parameter :: fmt = "(1X,A,': ',A)"
    character(len=*), parameter :: &
        fmt_verbose = "(1X,A,': ',A,' [expected ',I6,', got ',I6,']')'"
    failed = .false.
    verbose = .true.
    if (present (quiet)) then
        verbose = .not.quiet
    end if
    if (x == x0) then
        if (verbose) then
            if (.not. (present (buffer) .or. present (unit))) then
                write (unit = *, fmt = fmt) msg, "passed"
            end if
            if (present (unit)) then
                write (unit = unit, fmt = fmt) msg, "passed"
            end if
            if (present (buffer)) then
                write (unit = buffer, fmt = fmt) msg, "passed"
            end if
        end if
    end if
end subroutine expect_integer

```

```

        end if
    end if
else
    if (.not. (present (buffer) .or. present (unit))) then
        write (unit = *, fmt = fmt_verbose) msg, "failed", x0, x
    end if
    if (present (unit)) then
        write (unit = unit, fmt = fmt_verbose) msg, "failed", x0, x
    end if
    if (present (buffer)) then
        write (unit = buffer, fmt = fmt_verbose) msg, "failed", x0, x
    end if
    failed = .true.
end if
if (present (passed)) then
    passed = passed .and. .not.failed
end if
end subroutine expect_integer

```

(Implementation of test support functions)+≡

```

subroutine expect_real (x, x0, msg, passed, threshold, quiet)
    real(kind=default), intent(in) :: x, x0
    character(len=*), intent(in) :: msg
    logical, intent(inout), optional :: passed
    real(kind=default), intent(in), optional :: threshold
    logical, intent(in), optional :: quiet
    logical :: failed, verbose
    real(kind=default) :: agreement_threshold
    character(len=*), parameter :: fmt = "(1X,A,' : ',A,' at ',I4,'%')'"
    character(len=*), parameter :: fmt_verbose = "(1X,A,' : ',A,' at ',I4,'%'," // &
        "' [expected ',E10.3,', got ',E10.3,']'"
    real(kind=default) :: a
    failed = .false.
    verbose = .true.
    if (present (quiet)) then
        verbose = .not.quiet
    end if
    if (x == x0) then
        if (verbose) then
            write (unit = *, fmt = fmt) msg, "passed", 100
        end if
    else
        if (x0 == 0) then
            a = vanishes (x)
        else
            a = agreement (x, x0)
        end if
        if (present (threshold)) then
            agreement_threshold = threshold
        else
            agreement_threshold = THRESHOLD_DEFAULT
        end if
        if (a >= agreement_threshold) then
            if (verbose) then
                if (a >= THRESHOLD_WARN) then

```

```

        write (unit = *, fmt = fmt) msg, "passed", int (a * 100)
    else
        write (unit = *, fmt = fmt_verbose) msg, "passed", int (a * 100), x0, x
    end if
end if
else
    failed = .true.
    write (unit = *, fmt = fmt_verbose) msg, "failed", int (a * 100), x0, x
end if
end if
if (present (passed)) then
    passed = passed .and. .not.failed
end if
end subroutine expect_real

```

(Implementation of test support functions)+≡

```

subroutine expect_complex (x, x0, msg, passed, threshold, quiet)
    complex(kind=default), intent(in) :: x, x0
    character(len=*), intent(in) :: msg
    logical, intent(inout), optional :: passed
    real(kind=default), intent(in), optional :: threshold
    logical, intent(in), optional :: quiet
    logical :: failed, verbose
    real(kind=default) :: agreement_threshold
    character(len=*), parameter :: fmt = "(1X,A,' : ',A,' at ',I4,'%')'"
    character(len=*), parameter :: fmt_verbose = "(1X,A,' : ',A,' at ',I4,'%'," // &
        "' [expected (' ,E10.3,' ,',E10.3,'), got (' ,E10.3,' ,',E10.3,')]'"
    character(len=*), parameter :: fmt_phase = "(1X,A,' : ',A,' at ',I4,'%'," // &
        "' [modulus passed at ',I4,'%',' , phases ',F5.3,' vs. ',F5.3,'])'"
    real(kind=default) :: a, a_modulus
    failed = .false.
    verbose = .true.
    if (present (quiet)) then
        verbose = .not.quiet
    end if
    if (x == x0) then
        if (verbose) then
            write (unit = *, fmt = fmt) msg, "passed", 100
        end if
    else
        if (x0 == 0) then
            a = vanishes (x)
        else
            a = agreement (x, x0)
        end if
        if (present (threshold)) then
            agreement_threshold = threshold
        else
            agreement_threshold = THRESHOLD_DEFAULT
        end if
        if (a >= agreement_threshold) then
            if (verbose) then
                if (a >= THRESHOLD_WARN) then
                    write (unit = *, fmt = fmt) msg, "passed", int (a * 100)
                else

```

```

        write (unit = *, fmt = fmt_verbose) msg, "passed", int (a * 100), x0, x
    end if
end if
else
    a_modulus = agreement (abs (x), abs (x0))
    if (a_modulus >= agreement_threshold) then
        write (unit = *, fmt = fmt_phase) msg, "failed", int (a * 100), &
            int (a_modulus * 100), &
            atan2 (real (x, kind=default), aimag (x)), &
            atan2 (real (x0, kind=default), aimag (x0))
    else
        write (unit = *, fmt = fmt_verbose) msg, "failed", int (a * 100), x0, x
    end if
    failed = .true.
end if
end if
if (present (passed)) then
    passed = passed .and. .not.failed
end if
end subroutine expect_complex

<Implementation of test support functions>+≡
subroutine expect_real_integer (x, x0, msg, passed, threshold, quiet)
    real(kind=default), intent(in) :: x
    integer, intent(in) :: x0
    character(len=*), intent(in) :: msg
    real(kind=default), intent(in), optional :: threshold
    logical, intent(inout), optional :: passed
    logical, intent(in), optional :: quiet
    call expect_real (x, real (x0, kind=default), msg, passed, threshold, quiet)
end subroutine expect_real_integer

<Implementation of test support functions>+≡
subroutine expect_integer_real (x, x0, msg, passed, threshold, quiet)
    integer, intent(in) :: x
    real(kind=default), intent(in) :: x0
    character(len=*), intent(in) :: msg
    real(kind=default), intent(in), optional :: threshold
    logical, intent(inout), optional :: passed
    logical, intent(in), optional :: quiet
    call expect_real (real (x, kind=default), x0, msg, passed, threshold, quiet)
end subroutine expect_integer_real

<Implementation of test support functions>+≡
subroutine expect_complex_integer (x, x0, msg, passed, threshold, quiet)
    complex(kind=default), intent(in) :: x
    integer, intent(in) :: x0
    character(len=*), intent(in) :: msg
    logical, intent(inout), optional :: passed
    real(kind=default), intent(in), optional :: threshold
    logical, intent(in), optional :: quiet
    call expect_complex (x, cmplx (x0, kind=default), msg, passed, threshold, quiet)
end subroutine expect_complex_integer

<Implementation of test support functions>+≡
subroutine expect_integer_complex (x, x0, msg, passed, threshold, quiet)

```



```

integer, intent(in) :: x
complex(kind=default), intent(in) :: x0
character(len=*), intent(in) :: msg
logical, intent(inout), optional :: passed
real(kind=default), intent(in), optional :: threshold
logical, intent(in), optional :: quiet
call expect_complex (cmplx (x, kind=default), x0, msg, passed, threshold, quiet)
end subroutine expect_integer_complex

<Implementation of test support functions>+≡
subroutine expect_complex_real (x, x0, msg, passed, threshold, quiet)
  complex(kind=default), intent(in) :: x
  real(kind=default), intent(in) :: x0
  character(len=*), intent(in) :: msg
  logical, intent(inout), optional :: passed
  real(kind=default), intent(in), optional :: threshold
  logical, intent(in), optional :: quiet
  call expect_complex (x, cmplx (x0, kind=default), msg, passed, threshold, quiet)
end subroutine expect_complex_real

<Implementation of test support functions>+≡
subroutine expect_real_complex (x, x0, msg, passed, threshold, quiet)
  real(kind=default), intent(in) :: x
  complex(kind=default), intent(in) :: x0
  character(len=*), intent(in) :: msg
  logical, intent(inout), optional :: passed
  real(kind=default), intent(in), optional :: threshold
  logical, intent(in), optional :: quiet
  call expect_complex (cmplx (x, kind=default), x0, msg, passed, threshold, quiet)
end subroutine expect_real_complex

<Declaration of test support functions>+≡
public :: expect_zero
interface expect_zero
  module procedure expect_zero_integer, expect_zero_real, expect_zero_complex
end interface
private :: expect_zero_integer, expect_zero_real, expect_zero_complex

<Implementation of test support functions>+≡
subroutine expect_zero_integer (x, msg, passed)
  integer, intent(in) :: x
  character(len=*), intent(in) :: msg
  logical, intent(inout), optional :: passed
  call expect_integer (x, 0, msg, passed)
end subroutine expect_zero_integer

<Implementation of test support functions>+≡
subroutine expect_zero_real (x, scale, msg, passed, threshold, quiet)
  real(kind=default), intent(in) :: x, scale
  character(len=*), intent(in) :: msg
  logical, intent(inout), optional :: passed
  real(kind=default), intent(in), optional :: threshold
  logical, intent(in), optional :: quiet
  logical :: failed, verbose
  real(kind=default) :: agreement_threshold
  character(len=*), parameter :: fmt = "(1X,A,': ',A,' at ',I4,'%')'"
  character(len=*), parameter :: fmt_verbose = "(1X,A,': ',A,' at ',I4,'%'," // &

```

```

      '' [expected 0 (relative to ',E10.3,') got ',E10.3,')]''
real(kind=default) :: a
failed = .false.
verbose = .true.
if (present (quiet)) then
  verbose = .not.quiet
end if
if (x == 0) then
  if (verbose) then
    write (unit = *, fmt = fmt) msg, "passed", 100
  end if
else
  a = vanishes (x, scale = scale)
  if (present (threshold)) then
    agreement_threshold = threshold
  else
    agreement_threshold = THRESHOLD_DEFAULT
  end if
  if (a >= agreement_threshold) then
    if (verbose) then
      if (a >= THRESHOLD_WARN) then
        write (unit = *, fmt = fmt) msg, "passed", int (a * 100)
      else
        write (unit = *, fmt = fmt_verbose) msg, "passed", int (a * 100), scale, x
      end if
    end if
  else
    failed = .true.
    write (unit = *, fmt = fmt_verbose) msg, "failed", int (a * 100), scale, x
  end if
end if
if (present (passed)) then
  passed = passed .and. .not.failed
end if
end subroutine expect_zero_real

<Implementation of test support functions>+≡
subroutine expect_zero_complex (x, scale, msg, passed, threshold, quiet)
  complex(kind=default), intent(in) :: x
  real(kind=default), intent(in) :: scale
  character(len=*), intent(in) :: msg
  logical, intent(inout), optional :: passed
  real(kind=default), intent(in), optional :: threshold
  logical, intent(in), optional :: quiet
  call expect_zero_real (abs (x), scale, msg, passed, threshold, quiet)
end subroutine expect_zero_complex

<Implementation of test support functions>+≡
subroutine print_matrix (a)
  complex(kind=default), dimension(:, :), intent(in) :: a
  integer :: row
  do row = 1, size (a, dim=1)
    write (unit = *, fmt = "(10(tr2, f5.2, ' ', f5.2, 'I'))") a(row, :)
  end do
end subroutine print_matrix

```

```

<Declaration of test support functions>+≡
  public :: print_matrix

<test_omega95.f90>≡
  <Copyleft>
  program test_omega95
    use kinds
    use omega95
    use omega_testtools
    implicit none
    real(kind=default) :: m, pabs, qabs, w
    real(kind=default), dimension(0:3) :: r
    complex(kind=default) :: c_one, c_nil
    type(momentum) :: p, q, p0
    type(vector) :: vp, vq, vtest, v0
    type(tensor) :: ttest
    integer, dimension(8) :: date_time
    integer :: rsize
    logical :: passed
    call date_and_time (values = date_time)
    call random_seed (size = rsize)
    call random_seed (put = spread (product (date_time), dim = 1, ncopies = rsize))
    w = 1.4142
    c_one = 1.0_default
    c_nil = 0.0_default
    m = 13
    pabs = 42
    qabs = 137
    call random_number (r)
    vtest%t = cmplx (10.0_default * r(0), kind=default)
    vtest%x(1:3) = cmplx (10.0_default * r(1:3), kind=default)
    ttest = vtest.tprod.vtest
    call random_momentum (p, pabs, m)
    call random_momentum (q, qabs, m)
    call random_momentum (p0, 0.0_default, m)
    vp = p
    vq = q
    v0 = p0
    passed = .true.
    <Test omega95>
    if (.not. passed) then
      stop 1
    end if
  end program test_omega95

<Test omega95>≡
  print *, "*** Checking the equations of motion ***:"
  call expect (abs(f_vf(c_one, vp, u(m, p, +1)) - m * u(m, p, +1)), 0, "[p-m]u(+)=0", passed)
  call expect (abs(f_vf(c_one, vp, u(m, p, -1)) - m * u(m, p, -1)), 0, "[p-m]u(-)=0", passed)
  call expect (abs(f_vf(c_one, vp, v(m, p, +1)) + m * v(m, p, +1)), 0, "[p+m]v(+)=0", passed)
  call expect (abs(f_vf(c_one, vp, v(m, p, -1)) + m * v(m, p, -1)), 0, "[p+m]v(-)=0", passed)
  call expect (abs(f_fv(c_one, ubar(m, p, +1), vp) - m * ubar(m, p, +1)), 0, "|ubar(+)[p-m]|=0", passed)
  call expect (abs(f_fv(c_one, ubar(m, p, -1), vp) - m * ubar(m, p, -1)), 0, "|ubar(-)[p-m]|=0", passed)
  call expect (abs(f_fv(c_one, vbar(m, p, +1), vp) + m * vbar(m, p, +1)), 0, "|vbar(+)[p+m]|=0", passed)
  call expect (abs(f_fv(c_one, vbar(m, p, -1), vp) + m * vbar(m, p, -1)), 0, "|vbar(-)[p+m]|=0", passed)

```

```

print *, "*** Checking the equations of motion for negative mass***:"
call expect (abs(f_vf(c_one, vp, u(-m, p, +1)) + m * u(-m, p, +1)), 0, "[p+m]u(+)=0", passed)
call expect (abs(f_vf(c_one, vp, u(-m, p, -1)) + m * u(-m, p, -1)), 0, "[p+m]u(-)=0", passed)
call expect (abs(f_vf(c_one, vp, v(-m, p, +1)) - m * v(-m, p, +1)), 0, "[p-m]v(+)=0", passed)
call expect (abs(f_vf(c_one, vp, v(-m, p, -1)) - m * v(-m, p, -1)), 0, "[p-m]v(-)=0", passed)
call expect (abs(f_fv(c_one, ubar(-m, p, +1), vp) + m * ubar(-m, p, +1)), 0, "|ubar(+)[p+m]|=0", passed)
call expect (abs(f_fv(c_one, ubar(-m, p, -1), vp) + m * ubar(-m, p, -1)), 0, "|ubar(-)[p+m]|=0", passed)
call expect (abs(f_fv(c_one, vbar(-m, p, +1), vp) - m * vbar(-m, p, +1)), 0, "|vbar(+)[p-m]|=0", passed)
call expect (abs(f_fv(c_one, vbar(-m, p, -1), vp) - m * vbar(-m, p, -1)), 0, "|vbar(-)[p-m]|=0", passed)

<Test omega95>+≡
print *, "*** Checking the normalization ***:"
call expect (ubar(m, p, +1) * u(m, p, +1), +2 * m, "ubar(+)*u(+)=+2m", passed)
call expect (ubar(m, p, -1) * u(m, p, -1), +2 * m, "ubar(-)*u(-)=+2m", passed)
call expect (vbar(m, p, +1) * v(m, p, +1), -2 * m, "vbar(+)*v(+)=+2m", passed)
call expect (vbar(m, p, -1) * v(m, p, -1), -2 * m, "vbar(-)*v(-)=+2m", passed)
call expect (ubar(m, p, +1) * v(m, p, +1), 0, "ubar(+)*v(+)=0", passed)
call expect (ubar(m, p, -1) * v(m, p, -1), 0, "ubar(-)*v(-)=0", passed)
call expect (vbar(m, p, +1) * u(m, p, +1), 0, "vbar(+)*u(+)=0", passed)
call expect (vbar(m, p, -1) * u(m, p, -1), 0, "vbar(-)*u(-)=0", passed)
print *, "*** Checking the normalization for negative masses***:"
call expect (ubar(-m, p, +1) * u(-m, p, +1), -2 * m, "ubar(+)*u(+)=+2m", passed)
call expect (ubar(-m, p, -1) * u(-m, p, -1), -2 * m, "ubar(-)*u(-)=+2m", passed)
call expect (vbar(-m, p, +1) * v(-m, p, +1), +2 * m, "vbar(+)*v(+)=+2m", passed)
call expect (vbar(-m, p, -1) * v(-m, p, -1), +2 * m, "vbar(-)*v(-)=+2m", passed)
call expect (ubar(-m, p, +1) * v(-m, p, +1), 0, "ubar(+)*v(+)=0", passed)
call expect (ubar(-m, p, -1) * v(-m, p, -1), 0, "ubar(-)*v(-)=0", passed)
call expect (vbar(-m, p, +1) * u(-m, p, +1), 0, "vbar(+)*u(+)=0", passed)
call expect (vbar(-m, p, -1) * u(-m, p, -1), 0, "vbar(-)*u(-)=0", passed)

<Test omega95>+≡
print *, "*** Checking the currents ***:"
call expect (abs(v_ff(c_one, ubar(m, p, +1), u(m, p, +1)) - 2 * vp), 0, "ubar(+).V.u(+)=2p", passed)
call expect (abs(v_ff(c_one, ubar(m, p, -1), u(m, p, -1)) - 2 * vp), 0, "ubar(-).V.u(-)=2p", passed)
call expect (abs(v_ff(c_one, vbar(m, p, +1), v(m, p, +1)) - 2 * vp), 0, "vbar(+).V.v(+)=2p", passed)
call expect (abs(v_ff(c_one, vbar(m, p, -1), v(m, p, -1)) - 2 * vp), 0, "vbar(-).V.v(-)=2p", passed)
print *, "*** Checking the currents for negative masses***:"
call expect (abs(v_ff(c_one, ubar(-m, p, +1), u(-m, p, +1)) - 2 * vp), 0, "ubar(+).V.u(+)=2p", passed)
call expect (abs(v_ff(c_one, ubar(-m, p, -1), u(-m, p, -1)) - 2 * vp), 0, "ubar(-).V.u(-)=2p", passed)
call expect (abs(v_ff(c_one, vbar(-m, p, +1), v(-m, p, +1)) - 2 * vp), 0, "vbar(+).V.v(+)=2p", passed)
call expect (abs(v_ff(c_one, vbar(-m, p, -1), v(-m, p, -1)) - 2 * vp), 0, "vbar(-).V.v(-)=2p", passed)

<Test omega95>+≡
print *, "*** Checking current conservation ***:"
call expect ((vp - vq) * v_ff(c_one, ubar(m, p, +1), u(m, q, +1))), 0, "d(ubar(+).V.u(+))=0", passed)
call expect ((vp - vq) * v_ff(c_one, ubar(m, p, -1), u(m, q, -1))), 0, "d(ubar(-).V.u(-))=0", passed)
call expect ((vp - vq) * v_ff(c_one, vbar(m, p, +1), v(m, q, +1))), 0, "d(vbar(+).V.v(+))=0", passed)
call expect ((vp - vq) * v_ff(c_one, vbar(m, p, -1), v(m, q, -1))), 0, "d(vbar(-).V.v(-))=0", passed)
print *, "*** Checking current conservation for negative masses***:"
call expect ((vp - vq) * v_ff(c_one, ubar(-m, p, +1), u(-m, q, +1))), 0, "d(ubar(+).V.u(+))=0", passed)
call expect ((vp - vq) * v_ff(c_one, ubar(-m, p, -1), u(-m, q, -1))), 0, "d(ubar(-).V.u(-))=0", passed)
call expect ((vp - vq) * v_ff(c_one, vbar(-m, p, +1), v(-m, q, +1))), 0, "d(vbar(+).V.v(+))=0", passed)
call expect ((vp - vq) * v_ff(c_one, vbar(-m, p, -1), v(-m, q, -1))), 0, "d(vbar(-).V.v(-))=0", passed)

<Test omega95>+≡
if (m == 0) then

```

```

    print *, "*** Checking axial current conservation ***:"
    call expect ((vp-vq)*a_ff(c_one,ubar(m,p,+1),u(m,q,+1)), 0, "d(ubar(+).A.u(+))=0", passed)
    call expect ((vp-vq)*a_ff(c_one,ubar(m,p,-1),u(m,q,-1)), 0, "d(ubar(-).A.u(-))=0", passed)
    call expect ((vp-vq)*a_ff(c_one,vbar(m,p,+1),v(m,q,+1)), 0, "d(vbar(+).A.v(+))=0", passed)
    call expect ((vp-vq)*a_ff(c_one,vbar(m,p,-1),v(m,q,-1)), 0, "d(vbar(-).A.v(-))=0", passed)
end if

<Test omega95>+≡
print *, "*** Checking implementation of the sigma vertex funktions ***:"
call expect ((vp*tvam_ff(c_one,c_nil,ubar(m,p,+1),u(m,q,+1),q) - (p*q-m**2)*(ubar(m,p,+1)*u(m,q,+1)
    "p*[ubar(p,+).(Isigma*q).u(q,+)] - (p*q-m^2)*ubar(p,+).u(q,+) = 0", passed)
call expect ((vp*tvam_ff(c_one,c_nil,ubar(m,p,-1),u(m,q,-1),q) - (p*q-m**2)*(ubar(m,p,-1)*u(m,q,-1)
    "p*[ubar(p,-).(Isigma*q).u(q,-)] - (p*q-m^2)*ubar(p,-).u(q,-) = 0", passed)
call expect ((vp*tvam_ff(c_one,c_nil,vbar(m,p,+1),v(m,q,+1),q) - (p*q-m**2)*(vbar(m,p,+1)*v(m,q,+1)
    "p*[vbar(p,+).(Isigma*q).v(q,+)] - (p*q-m^2)*vbar(p,+).v(q,+) = 0", passed)
call expect ((vp*tvam_ff(c_one,c_nil,vbar(m,p,-1),v(m,q,-1),q) - (p*q-m**2)*(vbar(m,p,-1)*v(m,q,-1)
    "p*[vbar(p,-).(Isigma*q).v(q,-)] - (p*q-m^2)*vbar(p,-).v(q,-) = 0", passed)
call expect ((ubar(m,p,+1)*f_tvamf(c_one,c_nil,vp,u(m,q,+1),q) - (p*q-m**2)*(ubar(m,p,+1)*u(m,q,+1)
    "ubar(p,+).[p*(Isigma*q).u(q,+)] - (p*q-m^2)*ubar(p,+).u(q,+) = 0", passed)
call expect ((ubar(m,p,-1)*f_tvamf(c_one,c_nil,vp,u(m,q,-1),q) - (p*q-m**2)*(ubar(m,p,-1)*u(m,q,-1)
    "ubar(p,-).[p*(Isigma*q).u(q,-)] - (p*q-m^2)*ubar(p,-).u(q,-) = 0", passed)
call expect ((vbar(m,p,+1)*f_tvamf(c_one,c_nil,vp,v(m,q,+1),q) - (p*q-m**2)*(vbar(m,p,+1)*v(m,q,+1)
    "vbar(p,+).[p*(Isigma*q).v(q,+)] - (p*q-m^2)*vbar(p,+).v(q,+) = 0", passed)
call expect ((vbar(m,p,-1)*f_tvamf(c_one,c_nil,vp,v(m,q,-1),q) - (p*q-m**2)*(vbar(m,p,-1)*v(m,q,-1)
    "vbar(p,-).[p*(Isigma*q).v(q,-)] - (p*q-m^2)*vbar(p,-).v(q,-) = 0", passed)
call expect ((f_ftvam(c_one,c_nil,ubar(m,p,+1),vp,q)*u(m,q,+1) - (p*q-m**2)*(ubar(m,p,+1)*u(m,q,+1)
    "[ubar(p,+).p*(Isigma*q)].u(q,+) - (p*q-m^2)*ubar(p,+).u(q,+) = 0", passed)
call expect ((f_ftvam(c_one,c_nil,ubar(m,p,-1),vp,q)*u(m,q,-1) - (p*q-m**2)*(ubar(m,p,-1)*u(m,q,-1)
    "[ubar(p,-).p*(Isigma*q)].u(q,-) - (p*q-m^2)*ubar(p,-).u(q,-) = 0", passed)
call expect ((f_ftvam(c_one,c_nil,vbar(m,p,+1),vp,q)*v(m,q,+1) - (p*q-m**2)*(vbar(m,p,+1)*v(m,q,+1)
    "[vbar(p,+).p*(Isigma*q)].v(q,+) - (p*q-m^2)*vbar(p,+).v(q,+) = 0", passed)
call expect ((f_ftvam(c_one,c_nil,vbar(m,p,-1),vp,q)*v(m,q,-1) - (p*q-m**2)*(vbar(m,p,-1)*v(m,q,-1)
    "[vbar(p,-).p*(Isigma*q)].v(q,-) - (p*q-m^2)*vbar(p,-).v(q,-) = 0", passed)

call expect ((vp*tvam_ff(c_nil,c_one,ubar(m,p,+1),u(m,q,+1),q) - (p*q+m**2)*p_ff(c_one,ubar(m,p,+1)
    "p*[ubar(p,+).(Isigma*q).g5.u(q,+)] - (p*q+m^2)*ubar(p,+).g5.u(q,+) = 0", passed)
call expect ((vp*tvam_ff(c_nil,c_one,ubar(m,p,-1),u(m,q,-1),q) - (p*q+m**2)*p_ff(c_one,ubar(m,p,-1)
    "p*[ubar(p,-).(Isigma*q).g5.u(q,-)] - (p*q+m^2)*ubar(p,-).g5.u(q,-) = 0", passed)
call expect ((vp*tvam_ff(c_nil,c_one,vbar(m,p,+1),v(m,q,+1),q) - (p*q+m**2)*p_ff(c_one,vbar(m,p,+1)
    "p*[vbar(p,+).(Isigma*q).g5.v(q,+)] - (p*q+m^2)*vbar(p,+).g5.v(q,+) = 0", passed)
call expect ((vp*tvam_ff(c_nil,c_one,vbar(m,p,-1),v(m,q,-1),q) - (p*q+m**2)*p_ff(c_one,vbar(m,p,-1)
    "p*[vbar(p,-).(Isigma*q).g5.v(q,-)] - (p*q+m^2)*vbar(p,-).g5.v(q,-) = 0", passed)
call expect ((ubar(m,p,+1)*f_tvamf(c_nil,c_one,vp,u(m,q,+1),q) - (p*q+m**2)*p_ff(c_one,ubar(m,p,+1)
    "p*[ubar(p,+).(Isigma*q).g5.u(q,+)] - (p*q+m^2)*ubar(p,+).g5.u(q,+) = 0", passed)
call expect ((ubar(m,p,-1)*f_tvamf(c_nil,c_one,vp,u(m,q,-1),q) - (p*q+m**2)*p_ff(c_one,ubar(m,p,-1)
    "p*[ubar(p,-).(Isigma*q).g5.u(q,-)] - (p*q+m^2)*ubar(p,-).g5.u(q,-) = 0", passed)
call expect ((vbar(m,p,+1)*f_tvamf(c_nil,c_one,vp,v(m,q,+1),q) - (p*q+m**2)*p_ff(c_one,vbar(m,p,+1)
    "p*[vbar(p,+).(Isigma*q).g5.v(q,+)] - (p*q+m^2)*vbar(p,+).g5.v(q,+) = 0", passed)
call expect ((vbar(m,p,-1)*f_tvamf(c_nil,c_one,vp,v(m,q,-1),q) - (p*q+m**2)*p_ff(c_one,vbar(m,p,-1)
    "p*[vbar(p,-).(Isigma*q).g5.v(q,-)] - (p*q+m^2)*vbar(p,-).g5.v(q,-) = 0", passed)
call expect ((f_ftvam(c_nil,c_one,ubar(m,p,+1),vp,q)*u(m,q,+1) - (p*q+m**2)*p_ff(c_one,ubar(m,p,+1)
    "p*[ubar(p,+).(Isigma*q).g5.u(q,+)] - (p*q+m^2)*ubar(p,+).g5.u(q,+) = 0", passed)
call expect ((f_ftvam(c_nil,c_one,ubar(m,p,-1),vp,q)*u(m,q,-1) - (p*q+m**2)*p_ff(c_one,ubar(m,p,-1)
    "p*[ubar(p,-).(Isigma*q).g5.u(q,-)] - (p*q+m^2)*ubar(p,-).g5.u(q,-) = 0", passed)
call expect ((f_ftvam(c_nil,c_one,vbar(m,p,+1),vp,q)*v(m,q,+1) - (p*q+m**2)*p_ff(c_one,vbar(m,p,+1)

```

```

    "p*[vbar(p,+).(Isigma*q).g5.v(q,+)] - (p*q+m^2)*vbar(p,+).g5.v(q,+) = 0", passed)
call expect ((f_ftvam(c_nil,c_one,vbar(m,p,-1),vp,q)*v(m,q,-1) - (p*q+m**2)*p_ff(c_one,vbar(m,p,-1)
    "p*[vbar(p,-).(Isigma*q).g5.v(q,-)] - (p*q+m^2)*vbar(p,-).g5.v(q,-) = 0", passed)
<Test omega95)+≡
print *, "*** Checking polarisation vectors: ***"
call expect (conjg(eps(m,p, 1))*eps(m,p, 1), -1, "e( 1).e( 1)=-1", passed)
call expect (conjg(eps(m,p, 1))*eps(m,p,-1), 0, "e( 1).e(-1)= 0", passed)
call expect (conjg(eps(m,p,-1))*eps(m,p, 1), 0, "e(-1).e( 1)= 0", passed)
call expect (conjg(eps(m,p,-1))*eps(m,p,-1), -1, "e(-1).e(-1)=-1", passed)
call expect (p*eps(m,p, 1), 0, "p.e( 1)= 0", passed)
call expect (p*eps(m,p,-1), 0, "p.e(-1)= 0", passed)
if (m > 0) then
    call expect (conjg(eps(m,p, 1))*eps(m,p, 0), 0, "e( 1).e( 0)= 0", passed)
    call expect (conjg(eps(m,p, 0))*eps(m,p, 1), 0, "e( 0).e( 1)= 0", passed)
    call expect (conjg(eps(m,p, 0))*eps(m,p, 0), -1, "e( 0).e( 0)=-1", passed)
    call expect (conjg(eps(m,p, 0))*eps(m,p,-1), 0, "e( 0).e(-1)= 0", passed)
    call expect (conjg(eps(m,p,-1))*eps(m,p, 0), 0, "e(-1).e( 0)= 0", passed)
    call expect (p*eps(m,p, 0), 0, "p.e( 0)= 0", passed)
end if
<Test omega95)+≡
print *, "*** Checking epsilon tensor: ***"
call expect (pseudo_scalar(eps(m,p,1),eps(m,q,1),eps(m,p,0),eps(m,q,0)), &
    - pseudo_scalar(eps(m,q,1),eps(m,p,1),eps(m,p,0),eps(m,q,0)), "eps(1<->2)", passed)
call expect (pseudo_scalar(eps(m,p,1),eps(m,q,1),eps(m,p,0),eps(m,q,0)), &
    - pseudo_scalar(eps(m,p,0),eps(m,q,1),eps(m,p,1),eps(m,q,0)), "eps(1<->3)", passed)
call expect (pseudo_scalar(eps(m,p,1),eps(m,q,1),eps(m,p,0),eps(m,q,0)), &
    - pseudo_scalar(eps(m,q,0),eps(m,q,1),eps(m,p,0),eps(m,p,1)), "eps(1<->4)", passed)
call expect (pseudo_scalar(eps(m,p,1),eps(m,q,1),eps(m,p,0),eps(m,q,0)), &
    - pseudo_scalar(eps(m,p,1),eps(m,p,0),eps(m,q,1),eps(m,q,0)), "eps(2<->3)", passed)
call expect (pseudo_scalar(eps(m,p,1),eps(m,q,1),eps(m,p,0),eps(m,q,0)), &
    - pseudo_scalar(eps(m,p,1),eps(m,q,0),eps(m,p,0),eps(m,q,1)), "eps(2<->4)", passed)
call expect (pseudo_scalar(eps(m,p,1),eps(m,q,1),eps(m,p,0),eps(m,q,0)), &
    - pseudo_scalar(eps(m,p,1),eps(m,q,1),eps(m,q,0),eps(m,p,0)), "eps(3<->4)", passed)
call expect (pseudo_scalar(eps(m,p,1),eps(m,q,1),eps(m,p,0),eps(m,q,0)), &
    eps(m,p,1)*pseudo_vector(eps(m,q,1),eps(m,p,0),eps(m,q,0)), "eps'", passed)

```

$$\frac{1}{2}[x \wedge y]_{\mu\nu}^*[x \wedge y]^{\mu\nu} = \frac{1}{2}(x_\mu^*y_\nu^* - x_\nu^*y_\mu^*)(x^\mu y^\nu - x^\nu y^\mu) = (x^*x)(y^*y) - (x^*y)(y^*x) \quad (\text{X.96})$$

```

<Test omega95)+≡
print *, "*** Checking tensors: ***"
call expect (conjg(p.wedge.q)*(p.wedge.q), (p*p)*(q*q)-(p*q)**2, &
    "[p,q].[q,p]=p.p*q.q-p.q^2", passed)
call expect (conjg(p.wedge.q)*(q.wedge.p), (p*q)**2-(p*p)*(q*q), &
    "[p,q].[q,p]=p.q^2-p.p*q.q", passed)

```

i. e.

$$\frac{1}{2}[p \wedge \epsilon(p, i)]_{\mu\nu}^*[p \wedge \epsilon(p, j)]^{\mu\nu} = -p^2 \delta_{ij} \quad (\text{X.97})$$

```

<Test omega95)+≡
call expect (conjg(p.wedge.eps(m,p, 1))*(p.wedge.eps(m,p, 1)), -p*p, &
    "[p,e( 1)].[p,e( 1)]=-p.p", passed)
call expect (conjg(p.wedge.eps(m,p, 1))*(p.wedge.eps(m,p,-1)), 0, &

```

```

    "[p,e( 1)].[p,e(-1)]=0", passed)
call expect (conjg(p.wedge.eps(m,p,-1))*(p.wedge.eps(m,p, 1)), 0, &
    "[p,e(-1)].[p,e( 1)]=0", passed)
call expect (conjg(p.wedge.eps(m,p,-1))*(p.wedge.eps(m,p,-1)), -p*p, &
    "[p,e(-1)].[p,e(-1)]=-p.p", passed)
if (m > 0) then
    call expect (conjg(p.wedge.eps(m,p, 1))*(p.wedge.eps(m,p, 0)), 0, &
        "[p,e( 1)].[p,e( 0)]=0", passed)
    call expect (conjg(p.wedge.eps(m,p, 0))*(p.wedge.eps(m,p, 1)), 0, &
        "[p,e( 0)].[p,e( 1)]=0", passed)
    call expect (conjg(p.wedge.eps(m,p, 0))*(p.wedge.eps(m,p, 0)), -p*p, &
        "[p,e( 0)].[p,e( 0)]=-p.p", passed)
    call expect (conjg(p.wedge.eps(m,p, 0))*(p.wedge.eps(m,p,-1)), 0, &
        "[p,e( 1)].[p,e(-1)]=0", passed)
    call expect (conjg(p.wedge.eps(m,p,-1))*(p.wedge.eps(m,p, 0)), 0, &
        "[p,e(-1)].[p,e( 0)]=0", passed)
end if
also

```

$$[x \wedge y]_{\mu\nu} z^\nu = x_\mu(yz) - y_\mu(xz) \quad (X.98)$$

$$z_\mu[x \wedge y]^{\mu\nu} = (zx)y^\nu - (zy)x^\nu \quad (X.99)$$

```

<Test omega95>+=
call expect (abs ((p.wedge.eps(m,p, 1))*p + (p*p)*eps(m,p, 1)), 0, &
    "[p,e( 1)].p=-p.p*e( 1)", passed)
call expect (abs ((p.wedge.eps(m,p, 0))*p + (p*p)*eps(m,p, 0)), 0, &
    "[p,e( 0)].p=-p.p*e( 0)", passed)
call expect (abs ((p.wedge.eps(m,p,-1))*p + (p*p)*eps(m,p,-1)), 0, &
    "[p,e(-1)].p=-p.p*e(-1)", passed)
call expect (abs (p*(p.wedge.eps(m,p, 1)) - (p*p)*eps(m,p, 1)), 0, &
    "p.[p,e( 1)]=p.p*e( 1)", passed)
call expect (abs (p*(p.wedge.eps(m,p, 0)) - (p*p)*eps(m,p, 0)), 0, &
    "p.[p,e( 0)]=p.p*e( 0)", passed)
call expect (abs (p*(p.wedge.eps(m,p,-1)) - (p*p)*eps(m,p,-1)), 0, &
    "p.[p,e(-1)]=p.p*e(-1)", passed)

<Test omega95>+=
print *, "*** Checking polarisation tensors: ***"
call expect (conjg(eps2(m,p, 2))*eps2(m,p, 2), 1, "e2( 2).e2( 2)=1", passed)
call expect (conjg(eps2(m,p, 2))*eps2(m,p,-2), 0, "e2( 2).e2(-2)=0", passed)
call expect (conjg(eps2(m,p,-2))*eps2(m,p, 2), 0, "e2(-2).e2( 2)=0", passed)
call expect (conjg(eps2(m,p,-2))*eps2(m,p,-2), 1, "e2(-2).e2(-2)=1", passed)
if (m > 0) then
    call expect (conjg(eps2(m,p, 2))*eps2(m,p, 1), 0, "e2( 2).e2( 1)=0", passed)
    call expect (conjg(eps2(m,p, 2))*eps2(m,p, 0), 0, "e2( 2).e2( 0)=0", passed)
    call expect (conjg(eps2(m,p, 2))*eps2(m,p,-1), 0, "e2( 2).e2(-1)=0", passed)
    call expect (conjg(eps2(m,p, 1))*eps2(m,p, 2), 0, "e2( 1).e2( 2)=0", passed)
    call expect (conjg(eps2(m,p, 1))*eps2(m,p, 1), 1, "e2( 1).e2( 1)=1", passed)
    call expect (conjg(eps2(m,p, 1))*eps2(m,p, 0), 0, "e2( 1).e2( 0)=0", passed)
    call expect (conjg(eps2(m,p, 1))*eps2(m,p,-1), 0, "e2( 1).e2(-1)=0", passed)
    call expect (conjg(eps2(m,p, 1))*eps2(m,p,-2), 0, "e2( 1).e2(-2)=0", passed)
    call expect (conjg(eps2(m,p, 0))*eps2(m,p, 2), 0, "e2( 0).e2( 2)=0", passed)
    call expect (conjg(eps2(m,p, 0))*eps2(m,p, 1), 0, "e2( 0).e2( 1)=0", passed)
    call expect (conjg(eps2(m,p, 0))*eps2(m,p, 0), 1, "e2( 0).e2( 0)=1", passed)
end if

```

```

call expect (conjg(eps2(m,p, 0))*eps2(m,p,-1), 0, "e2( 0).e2(-1)=0", passed)
call expect (conjg(eps2(m,p, 0))*eps2(m,p,-2), 0, "e2( 0).e2(-2)=0", passed)
call expect (conjg(eps2(m,p,-1))*eps2(m,p, 2), 0, "e2(-1).e2( 2)=0", passed)
call expect (conjg(eps2(m,p,-1))*eps2(m,p, 1), 0, "e2(-1).e2( 1)=0", passed)
call expect (conjg(eps2(m,p,-1))*eps2(m,p, 0), 0, "e2(-1).e2( 0)=0", passed)
call expect (conjg(eps2(m,p,-1))*eps2(m,p,-1), 1, "e2(-1).e2(-1)=1", passed)
call expect (conjg(eps2(m,p,-1))*eps2(m,p,-2), 0, "e2(-1).e2(-2)=0", passed)
call expect (conjg(eps2(m,p,-2))*eps2(m,p, 1), 0, "e2(-2).e2( 1)=0", passed)
call expect (conjg(eps2(m,p,-2))*eps2(m,p, 0), 0, "e2(-2).e2( 0)=0", passed)
call expect (conjg(eps2(m,p,-2))*eps2(m,p,-1), 0, "e2(-2).e2(-1)=0", passed)
end if

<Test omega95>+=
call expect (      abs(p*eps2(m,p, 2) ), 0, " |p.e2( 2)| =0", passed)
call expect (      abs(eps2(m,p, 2)*p), 0, " |e2( 2).p|=0", passed)
call expect (      abs(p*eps2(m,p,-2) ), 0, " |p.e2(-2)| =0", passed)
call expect (      abs(eps2(m,p,-2)*p), 0, " |e2(-2).p|=0", passed)
if (m > 0) then
  call expect (      abs(p*eps2(m,p, 1) ), 0, " |p.e2( 1)| =0", passed)
  call expect (      abs(eps2(m,p, 1)*p), 0, " |e2( 1).p|=0", passed)
  call expect (      abs(p*eps2(m,p, 0) ), 0, " |p.e2( 0)| =0", passed)
  call expect (      abs(eps2(m,p, 0)*p), 0, " |e2( 0).p|=0", passed)
  call expect (      abs(p*eps2(m,p,-1) ), 0, " |p.e2(-1)| =0", passed)
  call expect (      abs(eps2(m,p,-1)*p), 0, " |e2(-1).p|=0", passed)
end if

<XXX Test omega95>=
print *, " *** Checking the polarization tensors for massive gravitons:"
call expect (abs(p * eps2(m,p,2)), 0, "p.e(+2)=0", passed)
call expect (abs(p * eps2(m,p,1)), 0, "p.e(+1)=0", passed)
call expect (abs(p * eps2(m,p,0)), 0, "p.e( 0)=0", passed)
call expect (abs(p * eps2(m,p,-1)), 0, "p.e(-1)=0", passed)
call expect (abs(p * eps2(m,p,-2)), 0, "p.e(-2)=0", passed)
call expect (abs(trace(eps2 (m,p,2))), 0, "Tr[e(+2)]=0", passed)
call expect (abs(trace(eps2 (m,p,1))), 0, "Tr[e(+1)]=0", passed)
call expect (abs(trace(eps2 (m,p,0))), 0, "Tr[e( 0)]=0", passed)
call expect (abs(trace(eps2 (m,p,-1))), 0, "Tr[e(-1)]=0", passed)
call expect (abs(trace(eps2 (m,p,-2))), 0, "Tr[e(-2)]=0", passed)
call expect (abs(eps2(m,p,2) * eps2(m,p,2)), 1, &
  "e(2).e(2) = 1", passed)
call expect (abs(eps2(m,p,2) * eps2(m,p,1)), 0, &
  "e(2).e(1) = 0", passed)
call expect (abs(eps2(m,p,2) * eps2(m,p,0)), 0, &
  "e(2).e(0) = 0", passed)
call expect (abs(eps2(m,p,2) * eps2(m,p,-1)), 0, &
  "e(2).e(-1) = 0", passed)
call expect (abs(eps2(m,p,2) * eps2(m,p,-2)), 0, &
  "e(2).e(-2) = 0", passed)
call expect (abs(eps2(m,p,1) * eps2(m,p,1)), 1, &
  "e(1).e(1) = 1", passed)
call expect (abs(eps2(m,p,1) * eps2(m,p,0)), 0, &
  "e(1).e(0) = 0", passed)
call expect (abs(eps2(m,p,1) * eps2(m,p,-1)), 0, &
  "e(1).e(-1) = 0", passed)
call expect (abs(eps2(m,p,1) * eps2(m,p,-2)), 0, &

```



```

    "e(1).e(-2) = 0", passed)
call expect (abs(eps2(m,p,0) * eps2(m,p,0)), 1, &
    "e(0).e(0) = 1", passed)
call expect (abs(eps2(m,p,0) * eps2(m,p,-1)), 0, &
    "e(0).e(-1) = 0", passed)
call expect (abs(eps2(m,p,0) * eps2(m,p,-2)), 0, &
    "e(0).e(-2) = 0", passed)
call expect (abs(eps2(m,p,-1) * eps2(m,p,-1)), 1, &
    "e(-1).e(-1) = 1", passed)
call expect (abs(eps2(m,p,-1) * eps2(m,p,-2)), 0, &
    "e(-1).e(-2) = 0", passed)
call expect (abs(eps2(m,p,-2) * eps2(m,p,-2)), 1, &
    "e(-2).e(-2) = 1", passed)

<Test omega95>+=
print *, " *** Checking the graviton propagator:"
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_tensor(p,m,w,eps2(m,p,-2)))), 0, "p.pr.e(-2)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_tensor(p,m,w,eps2(m,p,-1)))), 0, "p.pr.e(-1)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_tensor(p,m,w,eps2(m,p,0)))), 0, "p.pr.e(0)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_tensor(p,m,w,eps2(m,p,1)))), 0, "p.pr.e(1)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_tensor(p,m,w,eps2(m,p,2)))), 0, "p.pr.e(2)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_tensor(p,m,w,ttest))), 0, "p.pr.ttest", passed)

<test_omega95_bispinors.f90>=
<Copleft>
program test_omega95_bispinors
    use kinds
    use omega95_bispinors
    use omega_vspinor_polarizations
    use omega_testtools
    implicit none
    integer :: i, j
    real(kind=default) :: m, pabs, qabs, tabs, zabs, w
    real(kind=default), dimension(4) :: r
    complex(kind=default) :: c_one, c_two
    type(momentum) :: p, q, t, z, p_0
    type(vector) :: vp, vq, vt, vz
    type(vectorspinor) :: testv
    logical :: passed
    call random_seed ()
    c_one = 1
    c_two = 2
    w = 1.4142
    m = 13
    pabs = 42
    qabs = 137
    tabs = 84
    zabs = 3.1415
    p_0%t = m

```

```

p_0%x = 0
call random_momentum (p, pabs, m)
call random_momentum (q, qabs, m)
call random_momentum (t, tabs, m)
call random_momentum (z, zabs, m)
call random_number (r)
do i = 1, 4
  testv%psi(1)%a(i) = (0.0_default, 0.0_default)
end do
do i = 2, 3
  do j = 1, 4
    testv%psi(i)%a(j) = cmplx (10.0_default * r(j))
  end do
end do
testv%psi(4)%a(1) = (1.0_default, 0.0_default)
testv%psi(4)%a(2) = (0.0_default, 2.0_default)
testv%psi(4)%a(3) = (1.0_default, 0.0_default)
testv%psi(4)%a(4) = (3.0_default, 0.0_default)
vp = p
vq = q
vt = t
vz = z
passed = .true.
<Test omega95_bispinors>
if (.not. passed) then
  stop 1
end if
end program test_omega95_bispinors

<Test omega95_bispinors>≡
print *, "*** Checking the equations of motion ***:"
call expect (abs(f_vf(c_one,vp,u(m,p,+1))-m*u(m,p,+1)), 0, "[p-m]u(+)=0", passed)
call expect (abs(f_vf(c_one,vp,u(m,p,-1))-m*u(m,p,-1)), 0, "[p-m]u(-)=0", passed)
call expect (abs(f_vf(c_one,vp,v(m,p,+1))+m*v(m,p,+1)), 0, "[p+m]v(+)=0", passed)
call expect (abs(f_vf(c_one,vp,v(m,p,-1))+m*v(m,p,-1)), 0, "[p+m]v(-)=0", passed)
print *, "*** Checking the equations of motion for negative masses***:"
call expect (abs(f_vf(c_one,vp,u(-m,p,+1))+m*u(-m,p,+1)), 0, "[p+m]u(+)=0", passed)
call expect (abs(f_vf(c_one,vp,u(-m,p,-1))+m*u(-m,p,-1)), 0, "[p+m]u(-)=0", passed)
call expect (abs(f_vf(c_one,vp,v(-m,p,+1))-m*v(-m,p,+1)), 0, "[p-m]v(+)=0", passed)
call expect (abs(f_vf(c_one,vp,v(-m,p,-1))-m*v(-m,p,-1)), 0, "[p-m]v(-)=0", passed)

<Test omega95_bispinors>+≡
print *, "*** Checking the normalization ***:"
call expect (s_ff(c_one,v(m,p,+1),u(m,p,+1)), +2*m, "ubar(+)*u(+)=+2m", passed)
call expect (s_ff(c_one,v(m,p,-1),u(m,p,-1)), +2*m, "ubar(-)*u(-)=+2m", passed)
call expect (s_ff(c_one,u(m,p,+1),v(m,p,+1)), -2*m, "vbar(+)*v(+)=+2m", passed)
call expect (s_ff(c_one,u(m,p,-1),v(m,p,-1)), -2*m, "vbar(-)*v(-)=+2m", passed)
call expect (s_ff(c_one,v(m,p,+1),v(m,p,+1)), 0, "ubar(+)*v(+)=0", passed)
call expect (s_ff(c_one,v(m,p,-1),v(m,p,-1)), 0, "ubar(-)*v(-)=0", passed)
call expect (s_ff(c_one,u(m,p,+1),u(m,p,+1)), 0, "vbar(+)*u(+)=0", passed)
call expect (s_ff(c_one,u(m,p,-1),u(m,p,-1)), 0, "vbar(-)*u(-)=0", passed)
print *, "*** Checking the normalization for negative masses***:"
call expect (s_ff(c_one,v(-m,p,+1),u(-m,p,+1)), -2*m, "ubar(+)*u(+)=+2m", passed)
call expect (s_ff(c_one,v(-m,p,-1),u(-m,p,-1)), -2*m, "ubar(-)*u(-)=+2m", passed)
call expect (s_ff(c_one,u(-m,p,+1),v(-m,p,+1)), +2*m, "vbar(+)*v(+)=+2m", passed)

```

```

call expect (s_ff(c_one,u(-m,p,-1),v(-m,p,-1)), +2*m, "vbar(-)*v(-)=+2m", passed)
call expect (s_ff(c_one,v(-m,p,+1),v(-m,p,+1)), 0, "ubar(+)*v(+)=0 ", passed)
call expect (s_ff(c_one,v(-m,p,-1),v(-m,p,-1)), 0, "ubar(-)*v(-)=0 ", passed)
call expect (s_ff(c_one,u(-m,p,+1),u(-m,p,+1)), 0, "vbar(+)*u(+)=0 ", passed)
call expect (s_ff(c_one,u(-m,p,-1),u(-m,p,-1)), 0, "vbar(-)*u(-)=0 ", passed)

<Test omega95_bispinors>+≡
print *, "*** Checking the currents ***:"
call expect (abs(v_ff(c_one,v(m,p,+1),u(m,p,+1))-2*vp), 0, "ubar(+).V.u(+)=2p", passed)
call expect (abs(v_ff(c_one,v(m,p,-1),u(m,p,-1))-2*vp), 0, "ubar(-).V.u(-)=2p", passed)
call expect (abs(v_ff(c_one,u(m,p,+1),v(m,p,+1))-2*vp), 0, "vbar(+).V.v(+)=2p", passed)
call expect (abs(v_ff(c_one,u(m,p,-1),v(m,p,-1))-2*vp), 0, "vbar(-).V.v(-)=2p", passed)
print *, "*** Checking the currents for negative masses***:"
call expect (abs(v_ff(c_one,v(-m,p,+1),u(-m,p,+1))-2*vp), 0, "ubar(+).V.u(+)=2p", passed)
call expect (abs(v_ff(c_one,v(-m,p,-1),u(-m,p,-1))-2*vp), 0, "ubar(-).V.u(-)=2p", passed)
call expect (abs(v_ff(c_one,u(-m,p,+1),v(-m,p,+1))-2*vp), 0, "vbar(+).V.v(+)=2p", passed)
call expect (abs(v_ff(c_one,u(-m,p,-1),v(-m,p,-1))-2*vp), 0, "vbar(-).V.v(-)=2p", passed)

<Test omega95_bispinors>+≡
print *, "*** Checking current conservation ***:"
call expect ((vp-vq)*v_ff(c_one,v(m,p,+1),u(m,q,+1))), 0, "d(ubar(+).V.u(+))=0", passed)
call expect ((vp-vq)*v_ff(c_one,v(m,p,-1),u(m,q,-1))), 0, "d(ubar(-).V.u(-))=0", passed)
call expect ((vp-vq)*v_ff(c_one,u(m,p,+1),v(m,q,+1))), 0, "d(vbar(+).V.v(+))=0", passed)
call expect ((vp-vq)*v_ff(c_one,u(m,p,-1),v(m,q,-1))), 0, "d(vbar(-).V.v(-))=0", passed)

<Test omega95_bispinors>+≡
print *, "*** Checking current conservation for negative masses***:"
call expect ((vp-vq)*v_ff(c_one,v(-m,p,+1),u(-m,q,+1))), 0, "d(ubar(+).V.u(+))=0", passed)
call expect ((vp-vq)*v_ff(c_one,v(-m,p,-1),u(-m,q,-1))), 0, "d(ubar(-).V.u(-))=0", passed)
call expect ((vp-vq)*v_ff(c_one,u(-m,p,+1),v(-m,q,+1))), 0, "d(vbar(+).V.v(+))=0", passed)
call expect ((vp-vq)*v_ff(c_one,u(-m,p,-1),v(-m,q,-1))), 0, "d(vbar(-).V.v(-))=0", passed)

<Test omega95_bispinors>+≡
if (m == 0) then
  print *, "*** Checking axial current conservation ***:"
  call expect ((vp-vq)*a_ff(c_one,v(m,p,+1),u(m,q,+1))), 0, "d(ubar(+).A.u(+))=0", passed)
  call expect ((vp-vq)*a_ff(c_one,v(m,p,-1),u(m,q,-1))), 0, "d(ubar(-).A.u(-))=0", passed)
  call expect ((vp-vq)*a_ff(c_one,u(m,p,+1),v(m,q,+1))), 0, "d(vbar(+).A.v(+))=0", passed)
  call expect ((vp-vq)*a_ff(c_one,u(m,p,-1),v(m,q,-1))), 0, "d(vbar(-).A.v(-))=0", passed)
end if

<Test omega95_bispinors>+≡
print *, "*** Checking polarization vectors: ***"
call expect (conjg(eps(m,p, 1))*eps(m,p, 1), -1, "e( 1).e( 1)=-1", passed)
call expect (conjg(eps(m,p, 1))*eps(m,p,-1), 0, "e( 1).e(-1)= 0", passed)
call expect (conjg(eps(m,p,-1))*eps(m,p, 1), 0, "e(-1).e( 1)= 0", passed)
call expect (conjg(eps(m,p,-1))*eps(m,p,-1), -1, "e(-1).e(-1)=-1", passed)
call expect (
  p*eps(m,p, 1), 0, " p.e( 1)= 0", passed)
call expect (
  p*eps(m,p,-1), 0, " p.e(-1)= 0", passed)
if (m > 0) then
  call expect (conjg(eps(m,p, 1))*eps(m,p, 0), 0, "e( 1).e( 0)= 0", passed)
  call expect (conjg(eps(m,p, 0))*eps(m,p, 1), 0, "e( 0).e( 1)= 0", passed)
  call expect (conjg(eps(m,p, 0))*eps(m,p, 0), -1, "e( 0).e( 0)=-1", passed)
  call expect (conjg(eps(m,p, 0))*eps(m,p,-1), 0, "e( 0).e(-1)= 0", passed)
  call expect (conjg(eps(m,p,-1))*eps(m,p, 0), 0, "e(-1).e( 0)= 0", passed)
  call expect (
    p*eps(m,p, 0), 0, " p.e( 0)= 0", passed)
end if

```

(Test omega95_bispinors)+≡

```
print *, "*** Checking polarization vectorspinors: ***"
call expect (abs(p * ueps(m, p, 2)), 0, "p.ueps ( 2)= 0", passed)
call expect (abs(p * ueps(m, p, 1)), 0, "p.ueps ( 1)= 0", passed)
call expect (abs(p * ueps(m, p, -1)), 0, "p.ueps (-1)= 0", passed)
call expect (abs(p * ueps(m, p, -2)), 0, "p.ueps (-2)= 0", passed)
call expect (abs(p * veps(m, p, 2)), 0, "p.veps ( 2)= 0", passed)
call expect (abs(p * veps(m, p, 1)), 0, "p.veps ( 1)= 0", passed)
call expect (abs(p * veps(m, p, -1)), 0, "p.veps (-1)= 0", passed)
call expect (abs(p * veps(m, p, -2)), 0, "p.veps (-2)= 0", passed)
print *, "*** Checking polarization vectorspinors (neg. masses): ***"
call expect (abs(p * ueps(-m, p, 2)), 0, "p.ueps ( 2)= 0", passed)
call expect (abs(p * ueps(-m, p, 1)), 0, "p.ueps ( 1)= 0", passed)
call expect (abs(p * ueps(-m, p, -1)), 0, "p.ueps (-1)= 0", passed)
call expect (abs(p * ueps(-m, p, -2)), 0, "p.ueps (-2)= 0", passed)
call expect (abs(p * veps(-m, p, 2)), 0, "p.veps ( 2)= 0", passed)
call expect (abs(p * veps(-m, p, 1)), 0, "p.veps ( 1)= 0", passed)
call expect (abs(p * veps(-m, p, -1)), 0, "p.veps (-1)= 0", passed)
call expect (abs(p * veps(-m, p, -2)), 0, "p.veps (-2)= 0", passed)
print *, "*** in the rest frame ***"
call expect (abs(p_0 * ueps(m, p_0, 2)), 0, "p0.ueps ( 2)= 0", passed)
call expect (abs(p_0 * ueps(m, p_0, 1)), 0, "p0.ueps ( 1)= 0", passed)
call expect (abs(p_0 * ueps(m, p_0, -1)), 0, "p0.ueps (-1)= 0", passed)
call expect (abs(p_0 * ueps(m, p_0, -2)), 0, "p0.ueps (-2)= 0", passed)
call expect (abs(p_0 * veps(m, p_0, 2)), 0, "p0.veps ( 2)= 0", passed)
call expect (abs(p_0 * veps(m, p_0, 1)), 0, "p0.veps ( 1)= 0", passed)
call expect (abs(p_0 * veps(m, p_0, -1)), 0, "p0.veps (-1)= 0", passed)
call expect (abs(p_0 * veps(m, p_0, -2)), 0, "p0.veps (-2)= 0", passed)
print *, "*** in the rest frame (neg. masses) ***"
call expect (abs(p_0 * ueps(-m, p_0, 2)), 0, "p0.ueps ( 2)= 0", passed)
call expect (abs(p_0 * ueps(-m, p_0, 1)), 0, "p0.ueps ( 1)= 0", passed)
call expect (abs(p_0 * ueps(-m, p_0, -1)), 0, "p0.ueps (-1)= 0", passed)
call expect (abs(p_0 * ueps(-m, p_0, -2)), 0, "p0.ueps (-2)= 0", passed)
call expect (abs(p_0 * veps(-m, p_0, 2)), 0, "p0.veps ( 2)= 0", passed)
call expect (abs(p_0 * veps(-m, p_0, 1)), 0, "p0.veps ( 1)= 0", passed)
call expect (abs(p_0 * veps(-m, p_0, -1)), 0, "p0.veps (-1)= 0", passed)
call expect (abs(p_0 * veps(-m, p_0, -2)), 0, "p0.veps (-2)= 0", passed)
```

(Test omega95_bispinors)+≡

```
print *, "*** Checking the irreducibility condition: ***"
call expect (abs(f_potgr (c_one, c_one, ueps(m, p, 2))), 0, "g.ueps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p, 1))), 0, "g.ueps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p, -1))), 0, "g.ueps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p, -2))), 0, "g.ueps (-2)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p, 2))), 0, "g.veps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p, 1))), 0, "g.veps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p, -1))), 0, "g.veps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p, -2))), 0, "g.veps (-2)", passed)
print *, "*** Checking the irreducibility condition (neg. masses): ***"
call expect (abs(f_potgr (c_one, c_one, ueps(-m, p, 2))), 0, "g.ueps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(-m, p, 1))), 0, "g.ueps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(-m, p, -1))), 0, "g.ueps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(-m, p, -2))), 0, "g.ueps (-2)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(-m, p, 2))), 0, "g.veps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(-m, p, 1))), 0, "g.veps ( 1)", passed)
```

```

call expect (abs(f_potgr (c_one, c_one, veps(-m, p, -1))), 0, "g.veps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(-m, p, -2))), 0, "g.veps (-2)", passed)
print *, "*** in the rest frame ***"
call expect (abs(f_potgr (c_one, c_one, ueps(m, p_0, 2))), 0, "g.ueps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p_0, 1))), 0, "g.ueps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p_0, -1))), 0, "g.ueps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p_0, -2))), 0, "g.ueps (-2)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p_0, 2))), 0, "g.veps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p_0, 1))), 0, "g.veps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p_0, -1))), 0, "g.veps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p_0, -2))), 0, "g.veps (-2)", passed)
print *, "*** in the rest frame (neg. masses) ***"
call expect (abs(f_potgr (c_one, c_one, ueps(m, p_0, 2))), 0, "g.ueps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p_0, 1))), 0, "g.ueps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p_0, -1))), 0, "g.ueps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, ueps(m, p_0, -2))), 0, "g.ueps (-2)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p_0, 2))), 0, "g.veps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p_0, 1))), 0, "g.veps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p_0, -1))), 0, "g.veps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, veps(m, p_0, -2))), 0, "g.veps (-2)", passed)
<Test omega95_bispinors)+≡
print *, "*** Testing vectorspinor normalization ***"
call expect (veps(m,p, 2)*ueps(m,p, 2), -2*m, "ueps( 2).ueps( 2)= -2m", passed)
call expect (veps(m,p, 1)*ueps(m,p, 1), -2*m, "ueps( 1).ueps( 1)= -2m", passed)
call expect (veps(m,p,-1)*ueps(m,p,-1), -2*m, "ueps(-1).ueps(-1)= -2m", passed)
call expect (veps(m,p,-2)*ueps(m,p,-2), -2*m, "ueps(-2).ueps(-2)= -2m", passed)
call expect (ueps(m,p, 2)*veps(m,p, 2), 2*m, "veps( 2).veps( 2)= +2m", passed)
call expect (ueps(m,p, 1)*veps(m,p, 1), 2*m, "veps( 1).veps( 1)= +2m", passed)
call expect (ueps(m,p,-1)*veps(m,p,-1), 2*m, "veps(-1).veps(-1)= +2m", passed)
call expect (ueps(m,p,-2)*veps(m,p,-2), 2*m, "veps(-2).veps(-2)= +2m", passed)
call expect (ueps(m,p, 2)*ueps(m,p, 2), 0, "ueps( 2).veps( 2)= 0", passed)
call expect (ueps(m,p, 1)*ueps(m,p, 1), 0, "ueps( 1).veps( 1)= 0", passed)
call expect (ueps(m,p,-1)*ueps(m,p,-1), 0, "ueps(-1).veps(-1)= 0", passed)
call expect (ueps(m,p,-2)*ueps(m,p,-2), 0, "ueps(-2).veps(-2)= 0", passed)
call expect (veps(m,p, 2)*veps(m,p, 2), 0, "veps( 2).ueps( 2)= 0", passed)
call expect (veps(m,p, 1)*veps(m,p, 1), 0, "veps( 1).ueps( 1)= 0", passed)
call expect (veps(m,p,-1)*veps(m,p,-1), 0, "veps(-1).ueps(-1)= 0", passed)
call expect (veps(m,p,-2)*veps(m,p,-2), 0, "veps(-2).ueps(-2)= 0", passed)
print *, "*** Testing vectorspinor normalization (neg. masses) ***"
call expect (veps(-m,p, 2)*ueps(-m,p, 2), +2*m, "ueps( 2).ueps( 2)= +2m", passed)
call expect (veps(-m,p, 1)*ueps(-m,p, 1), +2*m, "ueps( 1).ueps( 1)= +2m", passed)
call expect (veps(-m,p,-1)*ueps(-m,p,-1), +2*m, "ueps(-1).ueps(-1)= +2m", passed)
call expect (veps(-m,p,-2)*ueps(-m,p,-2), +2*m, "ueps(-2).ueps(-2)= +2m", passed)
call expect (ueps(-m,p, 2)*veps(-m,p, 2), -2*m, "veps( 2).veps( 2)= -2m", passed)
call expect (ueps(-m,p, 1)*veps(-m,p, 1), -2*m, "veps( 1).veps( 1)= -2m", passed)
call expect (ueps(-m,p,-1)*veps(-m,p,-1), -2*m, "veps(-1).veps(-1)= -2m", passed)
call expect (ueps(-m,p,-2)*veps(-m,p,-2), -2*m, "veps(-2).veps(-2)= -2m", passed)
call expect (ueps(-m,p, 2)*ueps(-m,p, 2), 0, "ueps( 2).veps( 2)= 0", passed)
call expect (ueps(-m,p, 1)*ueps(-m,p, 1), 0, "ueps( 1).veps( 1)= 0", passed)
call expect (ueps(-m,p,-1)*ueps(-m,p,-1), 0, "ueps(-1).veps(-1)= 0", passed)
call expect (ueps(-m,p,-2)*ueps(-m,p,-2), 0, "ueps(-2).veps(-2)= 0", passed)
call expect (veps(-m,p, 2)*veps(-m,p, 2), 0, "veps( 2).ueps( 2)= 0", passed)
call expect (veps(-m,p, 1)*veps(-m,p, 1), 0, "veps( 1).ueps( 1)= 0", passed)
call expect (veps(-m,p,-1)*veps(-m,p,-1), 0, "veps(-1).ueps(-1)= 0", passed)

```

```

call expect (veps(-m,p,-2)*veps(-m,p,-2), 0, "veps(-2).ueps(-2)= 0", passed)
print *, "*** in the rest frame ***"
call expect (veps(m,p_0, 2)*ueps(m,p_0, 2), -2*m, "ueps( 2).ueps( 2)= -2m", passed)
call expect (veps(m,p_0, 1)*ueps(m,p_0, 1), -2*m, "ueps( 1).ueps( 1)= -2m", passed)
call expect (veps(m,p_0,-1)*ueps(m,p_0,-1), -2*m, "ueps(-1).ueps(-1)= -2m", passed)
call expect (veps(m,p_0,-2)*ueps(m,p_0,-2), -2*m, "ueps(-2).ueps(-2)= -2m", passed)
call expect (ueps(m,p_0, 2)*veps(m,p_0, 2), 2*m, "veps( 2).veps( 2)= +2m", passed)
call expect (ueps(m,p_0, 1)*veps(m,p_0, 1), 2*m, "veps( 1).veps( 1)= +2m", passed)
call expect (ueps(m,p_0,-1)*veps(m,p_0,-1), 2*m, "veps(-1).veps(-1)= +2m", passed)
call expect (ueps(m,p_0,-2)*veps(m,p_0,-2), 2*m, "veps(-2).veps(-2)= +2m", passed)
call expect (ueps(m,p_0, 2)*ueps(m,p_0, 2), 0, "ueps( 2).veps( 2)= 0", passed)
call expect (ueps(m,p_0, 1)*ueps(m,p_0, 1), 0, "ueps( 1).veps( 1)= 0", passed)
call expect (ueps(m,p_0,-1)*ueps(m,p_0,-1), 0, "ueps(-1).veps(-1)= 0", passed)
call expect (ueps(m,p_0,-2)*ueps(m,p_0,-2), 0, "ueps(-2).veps(-2)= 0", passed)
call expect (veps(m,p_0, 2)*veps(m,p_0, 2), 0, "veps( 2).ueps( 2)= 0", passed)
call expect (veps(m,p_0, 1)*veps(m,p_0, 1), 0, "veps( 1).ueps( 1)= 0", passed)
call expect (veps(m,p_0,-1)*veps(m,p_0,-1), 0, "veps(-1).ueps(-1)= 0", passed)
call expect (veps(m,p_0,-2)*veps(m,p_0,-2), 0, "veps(-2).ueps(-2)= 0", passed)
print *, "*** in the rest frame (neg. masses) ***"
call expect (veps(-m,p_0, 2)*ueps(-m,p_0, 2), +2*m, "ueps( 2).ueps( 2)= +2m", passed)
call expect (veps(-m,p_0, 1)*ueps(-m,p_0, 1), +2*m, "ueps( 1).ueps( 1)= +2m", passed)
call expect (veps(-m,p_0,-1)*ueps(-m,p_0,-1), +2*m, "ueps(-1).ueps(-1)= +2m", passed)
call expect (veps(-m,p_0,-2)*ueps(-m,p_0,-2), +2*m, "ueps(-2).ueps(-2)= +2m", passed)
call expect (ueps(-m,p_0, 2)*veps(-m,p_0, 2), -2*m, "veps( 2).veps( 2)= -2m", passed)
call expect (ueps(-m,p_0, 1)*veps(-m,p_0, 1), -2*m, "veps( 1).veps( 1)= -2m", passed)
call expect (ueps(-m,p_0,-1)*veps(-m,p_0,-1), -2*m, "veps(-1).veps(-1)= -2m", passed)
call expect (ueps(-m,p_0,-2)*veps(-m,p_0,-2), -2*m, "veps(-2).veps(-2)= -2m", passed)
call expect (ueps(-m,p_0, 2)*ueps(-m,p_0, 2), 0, "ueps( 2).veps( 2)= 0", passed)
call expect (ueps(-m,p_0, 1)*ueps(-m,p_0, 1), 0, "ueps( 1).veps( 1)= 0", passed)
call expect (ueps(-m,p_0,-1)*ueps(-m,p_0,-1), 0, "ueps(-1).veps(-1)= 0", passed)
call expect (ueps(-m,p_0,-2)*ueps(-m,p_0,-2), 0, "ueps(-2).veps(-2)= 0", passed)
call expect (veps(-m,p_0, 2)*veps(-m,p_0, 2), 0, "veps( 2).ueps( 2)= 0", passed)
call expect (veps(-m,p_0, 1)*veps(-m,p_0, 1), 0, "veps( 1).ueps( 1)= 0", passed)
call expect (veps(-m,p_0,-1)*veps(-m,p_0,-1), 0, "veps(-1).ueps(-1)= 0", passed)
call expect (veps(-m,p_0,-2)*veps(-m,p_0,-2), 0, "veps(-2).ueps(-2)= 0", passed)

( Test omega95_bispinors ) +=
print *, "*** Majorana properties of gravitino vertices: ***"
call expect (abs(u (m,q,1) * f_sgr (c_one, c_one, ueps(m,p,2), t) + &
    ueps(m,p,2) * gr_sf(c_one,c_one,u(m,q,1),t)), 0, "f_sgr + gr_sf = 0", passed)
!!! call expect (abs(u (m,q,-1) * f_sgr (c_one, c_one, ueps(m,p,2), t) + &
    ueps(m,p,2) * gr_sf(c_one,c_one,u(m,q,-1),t)), 0, "f_sgr + gr_sf = 0", passed)
!!! call expect (abs(u (m,q,1) * f_sgr (c_one, c_one, ueps(m,p,1), t) + &
    ueps(m,p,1) * gr_sf(c_one,c_one,u(m,q,1),t)), 0, "f_sgr + gr_sf = 0", passed)
!!! call expect (abs(u (m,q,-1) * f_sgr (c_one, c_one, ueps(m,p,1), t) + &
    ueps(m,p,1) * gr_sf(c_one,c_one,u(m,q,-1),t)), 0, "f_sgr + gr_sf = 0", passed)
!!! call expect (abs(u (m,q,1) * f_sgr (c_one, c_one, ueps(m,p,-1), t) + &
    ueps(m,p,-1) * gr_sf(c_one,c_one,u(m,q,1),t)), 0, "f_sgr + gr_sf = 0", passed)
!!! call expect (abs(u (m,q,-1) * f_sgr (c_one, c_one, ueps(m,p,-1), t) + &
    ueps(m,p,-1) * gr_sf(c_one,c_one,u(m,q,-1),t)), 0, "f_sgr + gr_sf = 0", passed)
!!! call expect (abs(u (m,q,1) * f_sgr (c_one, c_one, ueps(m,p,-2), t) + &
    ueps(m,p,-2) * gr_sf(c_one,c_one,u(m,q,1),t)), 0, "f_sgr + gr_sf = 0", passed)
!!! call expect (abs(u (m,q,-1) * f_sgr (c_one, c_one, ueps(m,p,-2), t) + &
    ueps(m,p,-2) * gr_sf(c_one,c_one,u(m,q,-1),t)), 0, "f_sgr + gr_sf = 0", passed)
call expect (abs(u (m,q,1) * f_slgr (c_one, c_one, ueps(m,p,2), t) + &

```

```

    ueps(m,p,2) * gr_slrf(c_one,c_one,u(m,q,1),t)), 0, "f_slgr + gr_slrf = 0", passed)
call expect (abs(u (m,q,1) * f_srgr (c_one, c_one, ueps(m,p,2), t) + &
    ueps(m,p,2) * gr_srf(c_one,c_one,u(m,q,1),t))), 0, "f_srgr + gr_srf = 0", passed)
call expect (abs(u (m,q,1) * f_slrgr (c_one, c_two, c_one, ueps(m,p,2), t) + &
    ueps(m,p,2) * gr_slrf(c_one,c_two,c_one,u(m,q,1),t))), 0, "f_slrgr + gr_slrf = 0", passed)
call expect (abs(u (m,q,1) * f_pgr (c_one, c_one, ueps(m,p,2), t) + &
    ueps(m,p,2) * gr_pf(c_one,c_one,u(m,q,1),t))), 0, "f_pgr + gr_pf = 0", passed)
call expect (abs(u (m,q,1) * f_vgr (c_one, vt, ueps(m,p,2), p+q) + &
    ueps(m,p,2) * gr_vf(c_one,vt,u(m,q,1),p+q))), 0, "f_vgr + gr_vf = 0", passed)
call expect (abs(u (m,q,1) * f_vlrgr (c_one, c_two, vt, ueps(m,p,2), p+q) + &
    ueps(m,p,2) * gr_vlrf(c_one,c_two,vt,u(m,q,1),p+q))), 0, "f_vlrgr + gr_vlrf = 0", passed)
!!! call expect (abs(u (m,q,-1) * f_vgr (c_one, vt, ueps(m,p,2), p+q) + &
!!! ueps(m,p,2) * gr_vf(c_one,vt,u(m,q,-1),p+q))), 0, "f_vgr + gr_vf = 0", passed)
!!! call expect (abs(u (m,q,1) * f_vgr (c_one, vt, ueps(m,p,1), p+q) + &
!!! ueps(m,p,1) * gr_vf(c_one,vt,u(m,q,1),p+q))), 0, "f_vgr + gr_vf = 0", passed)
!!! call expect (abs(u (m,q,-1) * f_vgr (c_one, vt, ueps(m,p,1), p+q) + &
!!! ueps(m,p,1) * gr_vf(c_one,vt,u(m,q,-1),p+q))), 0, "f_vgr + gr_vf = 0", passed)
!!! call expect (abs(u (m,q,1) * f_vgr (c_one, vt, ueps(m,p,-1), p+q) + &
!!! ueps(m,p,-1) * gr_vf(c_one,vt,u(m,q,1),p+q))), 0, "f_vgr + gr_vf = 0", passed)
!!! call expect (abs(u (m,q,-1) * f_vgr (c_one, vt, ueps(m,p,-1), p+q) + &
!!! ueps(m,p,-1) * gr_vf(c_one,vt,u(m,q,-1),p+q))), 0, "f_vgr + gr_vf = 0", passed)
!!! call expect (abs(v (m,q,1) * f_vgr (c_one, vt, ueps(m,p,-2), p+q) + &
!!! ueps(m,p,-2) * gr_vf(c_one,vt,v(m,q,1),p+q))), 0, "f_vgr + gr_vf = 0", passed)
!!! call expect (abs(u (m,q,-1) * f_vgr (c_one, vt, ueps(m,p,-2), p+q) + &
!!! ueps(m,p,-2) * gr_vf(c_one,vt,u(m,q,-1),p+q))), 0, "f_vgr + gr_vf = 0", passed)
call expect (abs(s_grf (c_one, ueps(m,p,2), u(m,q,1),t) + &
    s_fgr(c_one,u(m,q,1),ueps(m,p,2),t))), 0, "s_grf + s_fgr = 0", passed)
call expect (abs(sl_grf (c_one, ueps(m,p,2), u(m,q,1),t) + &
    sl_fgr(c_one,u(m,q,1),ueps(m,p,2),t))), 0, "sl_grf + sl_fgr = 0", passed)
call expect (abs(sr_grf (c_one, ueps(m,p,2), u(m,q,1),t) + &
    sr_fgr(c_one,u(m,q,1),ueps(m,p,2),t))), 0, "sr_grf + sr_fgr = 0", passed)
call expect (abs(slr_grf (c_one, c_two, ueps(m,p,2), u(m,q,1),t) + &
    slr_fgr(c_one,c_two,u(m,q,1),ueps(m,p,2),t))), 0, "slr_grf + slr_fgr = 0", passed)
call expect (abs(p_grf (c_one, ueps(m,p,2), u(m,q,1),t) + &
    p_fgr(c_one,u(m,q,1),ueps(m,p,2),t))), 0, "p_grf + p_fgr = 0", passed)
call expect (abs(v_grf (c_one, ueps(m,p,2), u(m,q,1),t) + &
    v_fgr(c_one,u(m,q,1),ueps(m,p,2),t))), 0, "v_grf + v_fgr = 0", passed)
call expect (abs(vlr_grf (c_one, c_two, ueps(m,p,2), u(m,q,1),t) + &
    vlr_fgr(c_one,c_two,u(m,q,1),ueps(m,p,2),t))), 0, "vlr_grf + vlr_fgr = 0", passed)
call expect (abs(u(m,p,1) * f_potgr (c_one,c_one,testv) - testv * gr_potf &
    (c_one,c_one,u (m,p,1))), 0, "f_potgr - gr_potf = 0", passed)
call expect (abs (pot_fgr (c_one,u(m,p,1),testv) - pot_grf(c_one, &
    testv,u(m,p,1))), 0, "pot_fgr - pot_grf = 0", passed)
call expect (abs(u(m,p,1) * f_s2gr (c_one,c_one,c_one,testv) - testv * gr_s2f &
    (c_one,c_one,c_one,u (m,p,1))), 0, "f_s2gr - gr_s2f = 0", passed)
call expect (abs (s2_fgr (c_one,u(m,p,1),c_one,testv) - s2_grf(c_one, &
    testv,c_one,u(m,p,1))), 0, "s2_fgr - s2_grf = 0", passed)
call expect (abs(u (m,q,1) * f_svgr (c_one, c_one, vt, ueps(m,p,2)) + &
    ueps(m,p,2) * gr_svrf(c_one,c_one,vt,u(m,q,1))), 0, "f_svgr + gr_svrf = 0", passed)
call expect (abs(u (m,q,1) * f_slvgr (c_one, c_one, vt, ueps(m,p,2)) + &
    ueps(m,p,2) * gr_slvf(c_one,c_one,vt,u(m,q,1))), 0, "f_slvgr + gr_slvf = 0", passed)
call expect (abs(u (m,q,1) * f_srvgr (c_one, c_one, vt, ueps(m,p,2)) + &
    ueps(m,p,2) * gr_srvf(c_one,c_one,vt,u(m,q,1))), 0, "f_srvgr + gr_srvf = 0", passed)
call expect (abs(u (m,q,1) * f_slrvgr (c_one, c_two, c_one, vt, ueps(m,p,2)) + &

```

```

    ueps(m,p,2) * gr_slrvf(c_one,c_two,c_one,vt,u(m,q,1))), 0, "f_slrvgr + gr_slrvf = 0", passed)
call expect (abs (sv1_fgr (c_one,u(m,p,1),vt,ueps(m,q,2)) + sv1_grf(c_one, &
    ueps(m,q,2),vt,u(m,p,1))), 0, "sv1_fgr + sv1_grf = 0", passed)
call expect (abs (sv2_fgr (c_one,u(m,p,1),c_one,ueps(m,q,2)) + sv2_grf(c_one, &
    ueps(m,q,2),c_one,u(m,p,1))), 0, "sv2_fgr + sv2_grf = 0", passed)
call expect (abs (slv1_fgr (c_one,u(m,p,1),vt,ueps(m,q,2)) + slv1_grf(c_one, &
    ueps(m,q,2),vt,u(m,p,1))), 0, "slv1_fgr + slv1_grf = 0", passed)
call expect (abs (srv2_fgr (c_one,u(m,p,1),c_one,ueps(m,q,2)) + srv2_grf(c_one, &
    ueps(m,q,2),c_one,u(m,p,1))), 0, "srv2_fgr + srv2_grf = 0", passed)
call expect (abs (slrv1_fgr (c_one,c_two,u(m,p,1),vt,ueps(m,q,2)) + slrv1_grf(c_one,c_two, &
    ueps(m,q,2),vt,u(m,p,1))), 0, "slrv1_fgr + slrv1_grf = 0", passed)
call expect (abs (slrv2_fgr (c_one,c_two,u(m,p,1),c_one,ueps(m,q,2)) + slrv2_grf(c_one, &
    c_two,ueps(m,q,2),c_one,u(m,p,1))), 0, "slrv2_fgr + slrv2_grf = 0", passed)
call expect (abs(u (m,q,1) * f_pvgr (c_one, c_one, vt, ueps(m,p,2)) + &
    ueps(m,p,2) * gr_pvgr(c_one,c_one,vt,u(m,q,1))), 0, "f_pvgr + gr_pvgr = 0", passed)
call expect (abs (pv1_fgr (c_one,u(m,p,1),vt,ueps(m,q,2)) + pv1_grf(c_one, &
    ueps(m,q,2),vt,u(m,p,1))), 0, "pv1_fgr + pv1_grf = 0", passed)
call expect (abs (pv2_fgr (c_one,u(m,p,1),c_one,ueps(m,q,2)) + pv2_grf(c_one, &
    ueps(m,q,2),c_one,u(m,p,1))), 0, "pv2_fgr + pv2_grf = 0", passed)
call expect (abs(u (m,q,1) * f_v2gr (c_one, vt, vz, ueps(m,p,2)) + &
    ueps(m,p,2) * gr_v2f(c_one,vt,vz,u(m,q,1))), 0, "f_v2gr + gr_v2f = 0", passed)
call expect (abs(u (m,q,1) * f_v2lrgr (c_one, c_two, vt, vz, ueps(m,p,2)) + &
    ueps(m,p,2) * gr_v2lrgr(c_one,c_two,vt,vz,u(m,q,1))), 0, "f_v2lrgr + gr_v2lrgr = 0", passed)
call expect (abs (v2_fgr (c_one,u(m,p,1),vt,ueps(m,q,2)) + v2_grf(c_one, &
    ueps(m,q,2),vt,u(m,p,1))), 0, "v2_fgr + v2_grf = 0", passed)
call expect (abs (v2lr_fgr (c_one,c_two,u(m,p,1),vt,ueps(m,q,2)) + v2lr_grf(c_one, c_two, &
    ueps(m,q,2),vt,u(m,p,1))), 0, "v2lr_fgr + v2lr_grf = 0", passed)

<Test omega95_bispinors>+≡
print *, "*** Testing the gravitino propagator: ***"
print *, "Transversality:"
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,testv))), 0, "p.pr.test", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,ueps(m,p,2)))), 0, "p.pr.ueps ( 2)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,ueps(m,p,1)))), 0, "p.pr.ueps ( 1)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,ueps(m,p,-1)))), 0, "p.pr.ueps (-1)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,ueps(m,p,-2)))), 0, "p.pr.ueps (-2)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,veps(m,p,2)))), 0, "p.pr.veps ( 2)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,veps(m,p,1)))), 0, "p.pr.veps ( 1)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,veps(m,p,-1)))), 0, "p.pr.veps (-1)", passed)
call expect (abs(p * (cmplx (p*p - m**2, m*w, kind=default) * &
    pr_grav(p,m,w,veps(m,p,-2)))), 0, "p.pr.veps (-2)", passed)
print *, "Irreducibility:"
call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
    kind=default) * pr_grav(p,m,w,testv))), 0, "g.pr.test", passed)
call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
    kind=default) * pr_grav(p,m,w,ueps(m,p,2)))))), 0, &
    "g.pr.ueps ( 2)", passed)

```



```

call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
kind=default) * pr_grav(p,m,w,ueps(m,p,1))))), 0, &
"g.pr.ueps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
kind=default) * pr_grav(p,m,w,ueps(m,p,-1))))), 0, &
"g.pr.ueps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
kind=default) * pr_grav(p,m,w,ueps(m,p,-2))))), 0, &
"g.pr.ueps (-2)", passed)
call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
kind=default) * pr_grav(p,m,w,veps(m,p,2))))), 0, &
"g.pr.veps ( 2)", passed)
call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
kind=default) * pr_grav(p,m,w,veps(m,p,1))))), 0, &
"g.pr.veps ( 1)", passed)
call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
kind=default) * pr_grav(p,m,w,veps(m,p,-1))))), 0, &
"g.pr.veps (-1)", passed)
call expect (abs(f_potgr (c_one, c_one, (cmplx (p*p - m**2, m*w, &
kind=default) * pr_grav(p,m,w,veps(m,p,-2))))), 0, &
"g.pr.veps (-2)", passed)

<omega_bundle.f90>≡
<omega_vectors.f90>
<omega_spinors.f90>
<omega_bispinors.f90>
<omega_vectorspinors.f90>
<omega_polarizations.f90>
<omega_tensors.f90>
<omega_tensor_polarizations.f90>
<omega_couplings.f90>
<omega_spinor_couplings.f90>
<omega_bispinor_couplings.f90>
<omega_vspinor_polarizations.f90>
<omega_utils.f90>
<omega95.f90>
<omega95_bispinors.f90>
<omega_parameters.f90>
<omega_parameters_madgraph.f90>

<omega_bundle_whizard.f90>≡
<omega_bundle.f90>
<omega_parameters_whizard.f90>

```

X.21 O'Mega Virtual Machine

```

<omegavm95.f90>≡
<Copyleft>
module omegavm95
  use kinds
  use omega95
  ! use omega95_bispinors
  implicit none
  private

```

```

    <OVM Procedure Declarations>
    <OVM Data Declarations>
    <OVM Instructions>
contains
    <OVM Procedure Implementations>
end module omegavm95

```

X.21.1 Memory Layout

On one hand, we need a memory pool for all the intermediate results

```

<OVM Data Declarations>≡
  type, public :: ovm
  private
    complex(kind=default) :: amp
    type(momentum), dimension(:), pointer :: p
    complex(kind=default), dimension(:), pointer :: phi
    type(spinor), dimension(:), pointer :: psi
    type(conjspinor), dimension(:), pointer :: psibar
    ! type(bispinor), dimension(:), pointer :: chi
    type(vector), dimension(:), pointer :: v
  end type ovm

<OVM Procedure Declarations>≡
  public :: alloc

<OVM Procedure Implementations>≡
  subroutine alloc (vm, momenta, scalars, spinors, conjspinors, vectors)
    type(ovm), intent(inout) :: vm
    integer, intent(in) :: momenta, scalars, spinors, conjspinors, vectors
    allocate (vm%p(momenta))
    allocate (vm%phi(scalars))
    allocate (vm%psi(spinors))
    allocate (vm%psibar(conjspinors))
    allocate (vm%v(vectors))
  end subroutine alloc

```

and on the other hand, we need to access coupling parameters that define the environment

```

<OVM Data Declarations>+≡
  type, public :: ovm_env
  private
    real(kind=default), dimension(:), pointer :: gr
    real(kind=default), dimension(:, :), pointer :: gr2
    complex(kind=default), dimension(:), pointer :: gc
    complex(kind=default), dimension(:, :), pointer :: gc2
  end type ovm_env

```

NB: during, execution, the type of the coupling constant is implicit in the instruction.



How to load coupling constants? Is brute force linear lookup good enough?

X.21.2 Instruction Set

```

<OVM Data Declarations>+≡

```

```

integer, parameter, private :: MAX_RHS = 3
type, public :: instr
  private
    integer :: code, sign, coupl, lhs
    integer, dimension(MAX_RHS) :: rhs
end type instr

<OVM Procedure Declarations>+≡
  public :: eval

<OVM Procedure Implementations>+≡
  pure subroutine eval (vm, amp, env, amplitude, p, s)
    type(ovm), intent(inout) :: vm
    complex(kind=default), intent(out) :: amp
    type(ovm_env), intent(in) :: env
    type(instr), dimension(:), intent(in) :: amplitude
    real(kind=default), dimension(0:,:), intent(in) :: p
    integer, dimension(:), intent(in) :: s
    integer :: code, sign, coupl, lhs
    integer, dimension(MAX_RHS) :: rhs
    integer :: i, pc
    vm%p(1) = - p(:,1)
    vm%p(2) = - p(:,2)
    do i = 3, size (p, dim = 2)
      vm%p(i) = p(:,i)
    end do
    do pc = 1, size (amplitude)
      code = amplitude(pc)%code
      sign = amplitude(pc)%sign
      coupl = amplitude(pc)%coupl
      lhs = amplitude(pc)%lhs
      rhs = amplitude(pc)%rhs
      select case (code)
        <cases of code>
      end select
    end do
    amp = vm%amp
  end subroutine eval

```

Loading External states

```

<OVM Instructions>≡
  integer, public, parameter :: OVM_LOAD_SCALAR = 1
  integer, public, parameter :: OVM_LOAD_U = 2
  integer, public, parameter :: OVM_LOAD_UBAR = 3
  integer, public, parameter :: OVM_LOAD_V = 4
  integer, public, parameter :: OVM_LOAD_VBAR = 5
  integer, public, parameter :: OVM_LOAD_VECTOR = 6

<cases of code>≡
  case (OVM_LOAD_SCALAR)
    vm%phi(lhs) = 1
  case (OVM_LOAD_U)
    if (lhs <= 2) then
      vm%psi(lhs) = u (env%gr(coupl), - vm%p(rhs(1)), s(rhs(2)))

```

```

        else
            vm%psi(lhs) = u (env%gr(coupl), vm%p(rhs(1)), s(rhs(2)))
        end if
    case (OVM_LOAD_UBAR)
        if (lhs <= 2) then
            vm%psibar(lhs) = ubar (env%gr(coupl), - vm%p(rhs(1)), s(rhs(2)))
        else
            vm%psibar(lhs) = ubar (env%gr(coupl), vm%p(rhs(1)), s(rhs(2)))
        end if
    case (OVM_LOAD_V)
        if (lhs <= 2) then
            vm%psi(lhs) = v (env%gr(coupl), - vm%p(rhs(1)), s(rhs(2)))
        else
            vm%psi(lhs) = v (env%gr(coupl), vm%p(rhs(1)), s(rhs(2)))
        end if
    case (OVM_LOAD_VBAR)
        if (lhs <= 2) then
            vm%psibar(lhs) = vbar (env%gr(coupl), - vm%p(rhs(1)), s(rhs(2)))
        else
            vm%psibar(lhs) = vbar (env%gr(coupl), vm%p(rhs(1)), s(rhs(2)))
        end if
    case (OVM_LOAD_VECTOR)
        if (lhs <= 2) then
            vm%v(lhs) = eps (env%gr(coupl), - vm%p(rhs(1)), s(rhs(2)))
        else
            vm%v(lhs) = eps (env%gr(coupl), vm%p(rhs(1)), s(rhs(2)))
        end if

<OVM Instructions>+≡
    integer, public, parameter :: OVM_ADD_MOMENTA = 10

<cases of code>+≡
    case (OVM_ADD_MOMENTA)
        vm%p(lhs) = vm%p(rhs(1)) + vm%p(rhs(2))

<OVM Instructions>+≡
    integer, public, parameter :: OVM_PROPAGATE_SCALAR = 11
    integer, public, parameter :: OVM_PROPAGATE_SPINOR = 12

<cases of code>+≡
    case (OVM_PROPAGATE_SCALAR)
        vm%phi(lhs) = pr_phi (vm%p(lhs), env%gr(rhs(1)), env%gr(rhs(2)), vm%phi(lhs))
    case (OVM_PROPAGATE_SPINOR)
        vm%psi(lhs) = pr_psi (vm%p(lhs), env%gr(rhs(1)), env%gr(rhs(2)), vm%psi(lhs))

<OVM Instructions>+≡
    integer, public, parameter :: OVM_FUSE_VECTOR_PSIBAR_PSI = 21
    integer, public, parameter :: OVM_FUSE_PSI_VECTOR_PSI = 22
    integer, public, parameter :: OVM_FUSE_PSIBAR_PSIBAR_VECTOR = 23

<cases of code>+≡
    case (OVM_FUSE_VECTOR_PSIBAR_PSI)
        vm%v(lhs) = &
            v_ff (sign*env%gc(coupl), vm%psibar(rhs(1)), vm%psi(rhs(2)))
    case (OVM_FUSE_PSI_VECTOR_PSI)
        vm%psi(lhs) = &
            f_vf (sign*env%gc(coupl), vm%v(rhs(1)), vm%psi(rhs(2)))

```

```

case (OVM_FUSE_PSIBAR_PSIBAR_VECTOR)
  vm%psibar(lhs) = &
    f_fv (sign*env%gc(coupl), vm%psibar(rhs(1)), vm%v(rhs(2)))
<Copyleft>≡
! $Id: omegalib.nw 4662 2013-09-23 13:21:34Z msekulla $
!
! Copyright (C) 1999-2009 by
!   Wolfgang Kilian <kilian@physik.uni-siegen.de>
!   Thorsten Ohl <ohl@physik.uni-wuerzburg.de>
!   Juergen Reuter <juergen.reuter@desy.de>
!
! WHIZARD is free software; you can redistribute it and/or modify it
! under the terms of the GNU General Public License as published by
! the Free Software Foundation; either version 2, or (at your option)
! any later version.
!
! WHIZARD is distributed in the hope that it will be useful, but
! WITHOUT ANY WARRANTY; without even the implied warranty of
! MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
! GNU General Public License for more details.
!
! You should have received a copy of the GNU General Public License
! along with this program; if not, write to the Free Software
! Foundation, Inc., 675 Mass Ave, Cambridge, MA 02139, USA.
!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!

```

—Y—

INDEX

This index has been generated automatically and might not be 100%ly accurate. In particular, hyperlinks have been observed to be off by one page.

*, **28, 29, 20**, used: 782, 783,
 784, 748, 748, 749, 750,
 754, 754, 769, 29, 30, 31,
 32, 32, 33, 33, 33, 34, 48,
 57, 63, 87, 87, 550, 190,
 191, 97, 110, 113, 124,
 251, 264, 265, 469, 472,
 504, 507, 540, 544, 292,
 313, 328, 329, 340, 358,
 370, 380, 385, 387, 410,
 426, 604, 612, 616, ??, ??
 +, **28, 29, 20**, used: ??, ??, ??,
 ??, 714, 714, 701, 701,
 704, 711, 783, 785, 748,
 748, 749, 751, 751, 752,
 29, 30, 30, 31, 31, 31, 32,
 33, 33, 34, 34, 48, 57, 58,
 61, 63, 64, 66, 183, 183,
 85, 87, 662, 550, 553, 557,
 559, 214, 99, 99, 118, 122,
 124, 124, 126, 670, 673,
 251, 264, 469, 472, 504,
 507, 540, 544, 292, 313,
 328, 329, 340, 358, 370,
 380, 385, 391, 410, 426,
 572, 575, 577, 600, 616,
 618, ??, ??
 -, **28, 29, 20**, used: ??, 714,
 707, 709, 710, 710, 755,
 756, 757, 685, 685, 790,
 791, 783, 748, 749, 760,
 761, 773, 22, 29, 30, 30,
 31, 31, 32, 32, 32, 34, 35,
 57, 58, 58, 61, 62, 63, 64,
 64, 66, 67, 67, 87, 553,
 554, 554, 555, 560, ??,
 188, 214, 214, 217, 113,
 126, 132, 670, 239, 251,
 267, 481, 482, 512, 512,
 414, 566, 570, 571, 572,
 596, 618, 625, 71
 /, **28, 29, 20**, used: 782, 783,
 748, 748, 749, 749, 22, 25,
 25, 27, 29, 32, 33, 75, 239,
 414, 616
 //, **239, 258, 439, 485, 516,**
276, 298, 319, 333, 345,
363, 374, 387, 399, 414,
 ??, ??, used: 239, 258,
 258, 258, 259, 259, 439,
 439, 439, 440, 440, 485,
 485, 486, 486, 486, 516,
 517, 517, 276, 276, 276,
 298, 298, 298, 319, 319,
 319, 333, 333, 333, 334,
 334, 345, 346, 346, 346,
 346, 363, 363, 363, 364,
 364, 374, 374, 374, 375,
 375, 387, 387, 387, 387,
 399, 400, 400, 400, 400,
 414, ??, ??, ??, ??, ??,
 ??, ??, ??, ??, ??
 <, **28, 29, 20**, used: 714, 715,
 715, 715, 716, 716, 716,
 717, 719, 720, 720, 720,
 721, 721, 722, 722, 700,
 703, 704, 704, 710, 783,
 748, 748, 749, 750, 750,
 752, 752, 754, 773, 773,
 25, 29, 30, 31, 32, 32, 34,
 46, 56, 57, 57, 58, 58, 61,
 87, 553, 554, 71, 186, 194,
 195, 195, 199, 200, 201,
 201, 201, 202, 206, 208,
 217, 218, 97, 127, 248,
 249, 250, 482, 512, 423,
 424, 425, 576, 576, 584,
 590, 604, 612, 677, 677,
 677, 677, 679, 679, 680,
 680
 <=, **28, 29, 20**, used: ??, 700,
 700, 700, 700, 701, 701,
 748, 749, 750, 760, 761,
 770, 771, 29, 29, 47, 48,
 56, 57, 62, 64, 655, 560,
 75, 100, 100, 126, 133,
 670, 433, 434, 483, 484,
 515, 515, 388, 395, 570,
 572, 575, 575, 605, 607
 <>, **28, 29, 20**, used: ??, 719,
 702, 703, 704, 709, 710,
 710, 755, 756, 756, 757,
 730, 733, 791, 792, 783,
 785, 751, 751, 752, 770,
 771, 773, 11, 12, 14, 16,
 29, 43, 57, 63, 65, 65, 66,
 221, 222, 661, 663, 553,
 553, 554, 195, 202, 203,
 207, 216, 216, 216, 219,
 103, 104, 131, 132

=, **28, 29, 20**, used: ??, ??, ??, ??, ??, ??, ??, ??, 715, 715, 715, 716, 716, 716, 717, 717, 718, 719, 720, 720, 720, 721, 721, 721, 722, 722, 702, 702, 703, 703, 703, 704, 711, 696, 728, 728, 731, 782, 783, 784, 785, 785, 748, 749, 749, 750, 752, 752, 753, 754, 766, 767, 767, 768, 769, 772, 773, 11, 13, 29, 30, 31, 31, 32, 32, 33, 33, 56, 57, 57, 57, 58, 58, 58, 58, 58, 59, 59, 59, 59, 59, 59, 59, 60, 60, 60, 60, 61, 63, 63, 63, 64, 64, 64, 64, 65, 65, 65, 65, 65, 65, 65, 65, 66, 67, 656, 183, 183, 86, 86, 87, 87, 221, 222, 222, 550, 550, 550, 550, 550, 554, 554, 555, 555, 558, 560, 77, 78, 79, 194, 194, 194, 195, 196, 197, 198, 198, 198, 199, 199, 200, 200, 200, 201, 203, 204, 204, 208, 217, 97, 105, 106, 121, 121, 127, 132, 269, 269, 322, 322, 394, 596, 632, 632, 679

>, **28, 29, 20**, used: ??, 714, 714, 701, 701, 707, 709, 710, 711, 690, 691, 791, 748, 748, 750, 750, 751, 752, 760, 761, 761, 17, 22, 29, 32, 56, 57, 57, 60, 60, 61, 63, 65, 65, 65, 65, 66, 67, 553, 555, 189, 194, 194, 195, 199, 200, 200, 201, 201, 202, 206, 208, 214, 214, 215, 239, 248, 249, 250, 251, 256, 258, 258, 259, 259, 264, 264, 431, 434, 435, 439, 440, 440, 467, 469, 472, 481, 482, 484, 485, 486, 486, 486, 503, 504, 507, 512, 512, 515, 516, 516, 517, 517, 539, 540, 544, 274, 275, 276, 276, 276, 291,

292, 296, 298, 298, 298,
 298, 313, 313, 318, 318,
 319, 319, 319, 326, 327,
 327, 328, 329, 332, 333,
 333, 334, 334, 339, 340,
 343, 345, 346, 346, 346,
 357, 358, 361, 363, 363,
 364, 364, 369, 370, 373,
 374, 374, 375, 375, 379,
 380, 398, 399, 400, 400,
 400, 409, 410, 414, 423,
 424, 425, 426, 570, 571,
 596, 604, 606, 607, 612,
 616, 618, ??, ??, ??, ??,
 ??, ??, ??, ??, ??, ??, ??,
 ??, ??, ??, 677, 677, 677,
 677, 679, 680, 680
 >:, ??, ??, used:
 >::, ??, ??, used: 723, 757, 757,
 758, 758, 758, 758, 758,
 758
 >:::, ??, ??, used: 724, 724, 758,
 758, 758, 759, 759
 >=, 28, 29, 20, used: 714, 714,
 717, 718, 704, 709, 710,
 792, 748, 761, 29, 30, 58,
 58, 64, 64, 553, 554, 554,
 560, 99, 112, 126, 670,
 239, 256, 257, 433, 434,
 483, 484, 515, 515, 273,
 274, 296, 297, 317, 318,
 331, 332, 342, 343, 361,
 362, 372, 373, 388, 397,
 398, 414, 571, 572, ??, ??,
 ??, ??
 ?arg_specs (label), ??, ??, used:
 ?cmp (label), ??, 702, 705, ??,
 698, 700, used:
 ?decl (label), 572, 572, 572,
 572, 573, used:
 ?env (label), ??, ??, used:
 ?epsilon (label), ??, ??, used:
 ?exit_code (label), ??, ??, used:
 ?f (label), 29, 32, 21, used:
 ?foutput (label), ??, ??, used:
 ?mode (label), ??, ??, used: ??
 ?msg (label), ??, ??, ??, ??, ??,
 ??, ??, ??, ??, used: ??,
 ??, ??, ??
 ?p (label), 566, used:

- ?pp_diff* (label), ??, ??, used:
?prefix (label), ??, ??, used:
?printer (label), ??, ??, used:
?set_verbose (label), ??, ??,
 used:
?sinput (label), ??, ??, used:
?skip (label), ??, ??, used:
?stride (label), **701, 701, 698,**
 698, used:
?suffix (label), ??, ??, used:
?use_stderr (label), ??, ??, used:

?verbose (label), ??, ??, ??, ??,
 used:
 @?, ??, ??, used:
 A, **432, 384, 140**, used: **433,**
 435, 442, 442, 443, 444,
 448, 449, 449, 452, 452,
 453, 453, 454, 456, 456,
 457, 457, 458, 458, 462,
 465, 384, 389, 389, 391,
 391, 391, 393
 A (module), **688, 105**, used: **688,**
 688, 688, 688, 105, 106,
 106, 106, 109, 110, 111,
 112, 112, 112, 112, 112,
 113, 113, 113, 113, 114,
 114, 114, 114, 114, 119,
 119, 119, 119, 119, 119,
 120, 120, 120, 121, 122,
 122, 122, 122, 123
abs, **55, 57, 63, 52**, used: **782,**
 659, 188, 233, 233, 236,
 236, 250, 251, 252, 264,
 265, 265, 431, 467, 472,
 472, 482, 483, 503, 507,
 507, 512, 514, 539, 545,
 545, 291, 292, 292, 313,
 314, 314, 326, 327, 327,
 329, 329, 339, 340, 340,
 357, 359, 359, 369, 371,
 371, 379, 380, 380, 409,
 410, 410, 425, 427, 427,
 604, 612, ??, ??, ??, ??,
 ??, ??
accessibility (type), **614**, used:
 615
accessibility_to_string, **614**, used:
 615

actions (field), **688**, used: **688,**
 688, 688, ??, ??
AD, **436**, used:
add, **713, 717, 720, 739, 739,**
 740, 740, 727, 728, 728,
 730, 731, 782, 783, 783,
 784, 786, 787, 31, 44,
 45, 49, 55, 57, 63, 183,
 183, 183, 183, 184, 184,
 550, 99, 712, 738, 738,
 725, 726, 726, 779, 780,
 781, 52, 182, 549, used:
 ??, ??, 723, 719, 704, 707,
 739, 739, 740, 743, 743,
 743, 744, 728, 728, 731,
 731, 784, 786, 786, 786,
 786, 786, 787, 787, 787,
 787, 787, 688, 772, 772,
 30, 31, 31, 32, 45, 45, 45,
 46, 46, 47, 47, 49, 183,
 183, 184, 184, 223, 223,
 223, 223, 224, 661, 662,
 662, 662, 664, 550, ??,
 560, 75, 188, 217, 218,
 219, 100, 105, 106, 109,
 110, 112, 114, 119, 121,
 121, 122, 125, 125, 126,
 133, 134, 135, 580, 596,
 599, 552
add', **57**, used: **57, 57**
add1, **550**, used: **550, 550, 550**
addn, **550**, used: **550, 550**
add_degree, **30**, used: **30**
add_derivatives, **786**, used: **786,**
 786
add_flavors, **662**, used: **662**
add_fusion2, **223**, used: **223**
add_fusion3, **223**, used: **224**
add_fusionn, **223**, used:
add_node, **41, 46, 38**, used: **46,**
 47, 112, 120
add_non_empty, **728, 731**, used:
 729, 731
add_offspring, **41, 46, 112, 38,**
 used: **112, 112, 120**
add_offspring_unsafe, **41, 46,**
 38, used: **46, 47**
add_permute3, **223**, used: **223**
add_permute4, **224**, used: **224**
add_tag, **572**, used: **572, 595**

- add_to_list*, **126**, used: **126**
- add_tree*, **661**, used: **661**
- add_unique*, **772**, used: **772**
- add_vertex3*, **223**, used: **224**
- add_vertex4*, **224**, used: **224**
- add_vertices*, **106**, used: **106**
- AdjSUN*, **82, 81**, used: **82, 559, 233, 239, 256, 434, 484, 515, 274, 296, 318, 332, 343, 361, 373, 385, 398, 414, ??, ??, 677**
- AH*, **273, 295**, used: **273, 275, 279, 279, 280, 281, 282, 283, 283, 284, 285, 289, 296, 297, 301, 301, 302, 303, 303, 304, 305, 305, 306, 310**
- Al*, **435**, used:
- AL*, **436**, used:
- Algebra* (module), **782, 779**, used: **184, 239, 258, 439, 485, 516, 276, 298, 319, 333, 345, 363, 374, 387, 399, 414, ??, ??, 183, 183**
- Aliased*, **614**, used:
- All*, **563, 579, 180**, used: **671**
- allowed*, **214, 95, 122, 91**, used: **215, 216, 122**
- allows_fusion*, **658**, used: **658**
- allows_momentum_fusion*, **658**, used: **658**
- all_bosons*, **384**, used: **393**
- all_compatible*, **75**, used: **77, 77**
- all_feynman*, **382**, used: **382, 386**
- all_leptons*, **384**, used: **393**
- all_quarks*, **384**, used: **393**
- alpha* (camllex regexpr), **551**, used: **551, 551**
- alphanum* (camllex regexpr), **551**, used: **551**
- Alpha-QED*, **239, 259, 436, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: **239, 259, 260, 414**
- Alpha-WWWW0*, **239, 414**, used: **239, 414**
- Alpha-WWWW2*, **239, 414**, used: **239, 414**
- Alpha-ZZWW0*, **239, 414**, used: **239, 414**
- Alpha-ZZWW1*, **239, 414**, used: **239, 414**
- Alpha-ZZZZ*, **239, 414**, used: **239, 414**
- alt_fuse2*, **269**, used:
- alt_fuse3*, **269**, used:
- amplitude*, **209, 211, 118, 180, 180**, used: **211, 122, 123**
- amplitude* (type), **660, 661, 95, 102, 105, 123, 129, 130, 569, 660, 90, 92**, used: **660, 661, 95, 102, 123, 129, 130, 130, 130, 130, 569, 660, 660, 90, 90, 91, 91, 91, 91, 92, 92, 92, 93, 93, 93, 93, 94**
- Amplitude* (module), **103**, used: **105, 119**
- Amplitude* (sig), **101**, used: **103**
- amplitudes*, **95, 123, 129, 134, 90, 93**, used: **135, 673, 675**
- amplitudes* (type), **129, 130, 563, 569, 180, 92**, used: **129, 563, 569, 181, 181, 93, 93, 93, 93, 93, 93, 93, 93, 93, 93, 94**
- amplitudes'* (type), **130**, used:
- amplitudes_to_channel*, **563, 623, 181**, used: **673, 674**
- amplitudes_to_channel_multi_file*, **623**, used: **623**
- amplitudes_to_channel_single_file*, **623**, used: **623**
- amplitudes_to_channel_single_function*, **620**, used: **623**
- amplitudes_to_channel_single_module*, **620**, used: **623**
- amplitude_to_dot*, **95, 126, 92**, used: **674**
- analyze_tree*, **664**, used:
- And*, **70, 75, 69**, used: **70, 76**
- AND*, **??, ??**, used: **??, 71**
- AND* (camlyacc token), **72**, used: **72, 72**
- angle* (type), **435**, used: **436**
- anomalous_bbA*, **242, 418**, used: **246, 422**

- anomalous_bbWW*, **244, 420**,
used: **246, 422**
- anomalous_bbZ*, **243, 419**, used:
246, 422
- anomalous_gauge_higgs*, **241**,
337, 349, 366, 415,
used: **241, 416**
- anomalous_gauge_higgs4*, **241**,
337, 349, 366, 416,
used: **241, 416**
- anomalous_higgs*, **241, 337, 349**,
366, 416, used: **241, 416**
- anomalous_higgs4*, **241, 337**,
350, 367, 416, used: **241**,
416
- anomalous_quartic_gauge*, **239**,
414, used: **239, 414**
- anomalous_tbW*, **243, 419**, used:
246, 422
- anomalous_tbWA*, **243, 419**,
used: **246, 422**
- anomalous_tbWZ*, **244, 420**,
used: **246, 422**
- anomalous_top_DuDd*, **245, 421**,
used: **246, 422**
- anomalous_top_qBuB*, **245, 421**,
used: **246, 422**
- anomalous_top_qBuB_ff*, **245**,
421, used: **245, 421**
- anomalous_top_qBuB_tt*, **245**,
421, used: **245, 421**
- anomalous_top_qGuG*, **244, 421**,
used: **246, 422**
- anomalous_top_qGuG_ff*, **244**,
420, used: **244, 421**
- anomalous_top_qGuG_tt*, **244**,
420, used: **244, 421**
- anomalous_top_quqd1*, **246**,
used: **246**
- anomalous_top_quqd1_ff*, **246**,
used: **246**
- anomalous_top_quqd1_tq*, **246**,
used: **246**
- anomalous_top_quqd8*, **246**,
used: **246**
- anomalous_top_quqd8_ff*, **246**,
used: **246**
- anomalous_top_quqd8_tq*, **246**,
used: **246**
- anomalous_top_qW*, **245, 421**,
used: **246, 422**
- anomalous_top_qW_ff*, **245**,
421, used: **245, 421**
- anomalous_top_qW_tq*, **245**,
421, used: **245, 421**
- anomalous_triple_gauge*, **239**,
414, used: **239, 414**
- anomalous_ttA*, **242, 418**, used:
246, 422
- anomalous_ttG*, **242, 418**, used:
246, 422
- anomalous_ttGG*, **243, 419**,
used: **246, 422**
- anomalous_ttH*, **243, 419**, used:
246, 422
- anomalous_ttWW*, **244, 420**,
used: **246, 422**
- anomalous_ttZ*, **242, 418**, used:
246, 422
- anomaly_higgs*, **288, 309, 324**,
337, 349, 366, 377,
used: **289, 310, 325, 337**,
350, 367, 377
- Anomtop* (module), **??**, used: **??**
- anom_ferm_ass*, **272, 272, 272**,
272, 270, used: **319, 321**,
322, 322, 323, 325, 326,
327, 328
- AntiFermion*, **97, 127**, used: **97**,
97, 127, 127
- AntiMuon*, **231**, used: **231, 231**,
232, 232
- AntiTau*, **231**, used: **231, 231**,
232, 232
- any* (type), **213, 214, 212**, used:
213, 214, 212
- Any*, **213, 214, 212**, used: **214**,
215
- Any_flavor*, **70, 75, 69**, used: **70**,
76
- Application*, **549, 549**, used: **549**
- apply*, **723, 723, 549, 722, 549**,
used: **723, ??, 552**
- apply_invalid_lengths*, **758**, used:
758
- apply_ok*, **723, 758**, used: **724**,
758
- arguments*, **665**, used: **665, 666**

- Arguments*, **563, 579, 180**, used:
671, 579
ariadne_sort, **705, 700**, used:
755, 219
ariadne_unsort, **705, 700**, used:
arity, **9, 11, 12, 13, 16, 6**, used:
array, **755, 755, 756, 754**, used:

assert_bool, **??, ??**, used: **??**
assert_command, **??, ??**, used:
assert_equal, **??, ??, ??, ??, ??**,
??, ??, used: **??, ??, ??**,
??, ??, 723, 758, 758, 758,
758, 758
assert_failure, **??, ??**, used: **??**,
??, ??, ??, ??
assert_raises, **??, ??**, used: **757**,
757, 758
assert_string, **??, ??**, used:
As_Is, **614**, used:
Atan2, **168**, used:
atom, **783, 783, 784, 784, 786**,
787, 780, 780, 781,
used: **786**
Atom, **168**, used: **239, 260, 260**,
260, 414
atoms, **783, 783, 784, 785, 787**,
788, 780, 781, 781,
used: **787, 788**
Atpsi, **277, 298, 319**, used:
attach_tofst_sorted, **751**, used:
751
attach_tofst_unsorted, **750**,
used: **751, 751, 751**
AU, **436**, used:
augment_basis, **744**, used: **744**
augment_basis_overlapping, **744**,
used: **744**
author, **685, 684**, used: **686**
author (field), **685, 684**, used:
686, 760, 9, 21, 41, 55,
221, 660, 553, 185, 95,
228, 429, 480, 511, 271,
640, 563, ??, ??, 675
Aux_Col_Scalar, **139**, used: **187**
Aux_Col_Tensor_1, **139**, used:
187
Aux_Col_Vector, **139**, used: **187**
Aux_ConjSpinor, **139**, used:

Aux_DScalar_DScalar, **140**,
used: **190**
Aux_Gauge_Gauge, **140**, used:
190, 243, 243, 244, 244,
244, 419, 419, 420, 420,
420
Aux_Majorana, **139**, used:
Aux_Scalar, **139**, used: **239, 257**,
414
Aux_Scalar_Scalar, **140**, used:
190
Aux_Scalar_Vector, **140**, used:
190
Aux_Spinor, **139**, used:
Aux_Tensor_1, **139**, used: **239**,
257, 414
Aux_top, **239, 414**, used: **239**,
243, 243, 244, 244, 244,
244, 244, 245, 245, 245,
245, 245, 246, 246, 246,
246, 247, 414, 419, 419,
420, 420, 420, 420, 420,
421, 421, 421, 421, 421,
422
aux_top_flavors, **239, 414**, used:
239, 414
Aux_Vector, **139**, used: **239, 257**,
414
Aux_Vector_DScalar, **140**, used:
190
Aux_Vector_Vector, **140**, used:
190
A_0, **436**, used:
A_P, **436**, used:
B, **233**, used: **233, 234, 234, 235**
B1, **341**, used: **342, 344, 350**
B2, **341**, used: **342, 344, 350**
bag (type), **214**, used: **214**
bal, **714**, used: **714, 715, 716**,
716, 717
baryon, **239, 259, 440, 486**,
517, 276, 298, 319, 334,
346, 364, 375, 400, 414,
??, ??, used: **239, 259**,
440, 486, 517, 277, 298,
319, 334, 347, 364, 375,
400, 414, ??, ??
baryonic_vertex, **186**, used: **195**,
195, 199

- base*, **739, 739, 740, 740, 738**,
738, used: 740, 218
base (type), **739, 739, 739, 740**,
740, 216, 219, 120, 737,
738, 738, used: 739, 739,
739, 739, 740, 740, 740,
737, 738, 738, 738, 738,
738, 738, 738, 738
basis, **742, 744, 742**, used: 744,
79, 218
Bbar, **233**, used: 233, 234, 234,
235
BBB, **140**, used: 190, 446, 446,
492, 492, 523, 524, 525,
525
BBWW, **239, 414**, used: 239,
244, 247, 414, 420, 422
bcdi_of_flavor, **384**, used: 395,
395
Be, **435**, used:
begin_step, **692, 690**, used: 135
Binary (module), **10, 22, 127, 8**,
20, 92, used: 15, 23, 24,
35, 35, 127, 129, 675, ??,
20, 21
Binary (sig), **10, 8**, used: 8
Binary_Majorana (module), **129**,
92, used:
binomial, **748, 745**, used: 87
binomial', **748**, used: 748, 748
bits, **62**, used: 63, 63, 63, 64, 64,
64, 64, 65, 65, 66
Bits (module), **62, 54**, used: 67,
67, 68, 54
bits0, **62**, used: 62
BitsW (module), **67, 54**, used:
67, 68
blank_line, **570**, used: 570
boson (type), **384, 140**, used:
384, 564, 140
Boson, **97, 127, 384**, used: 97,
97, 127, 127, 384, 386,
389, 389, 389, 389, 390,
390, 390, 390, 391, 391,
391, 391, 391, 391, 391,
392, 393, 394
boson2 (type), **140**, used: 564,
141
Bound (sig), **18, 8**, used: 25, 34,
129, 129, 8, 20, 21, 92, 92
bounded_power, **17**, used: 17
bounded_power_fold, **17**, used:
17, 17
bra, **95, 102, 104, 123, 90**, used:
123, 596
bracket, **??, ??**, used: ??
bracket_tmpfile, **??, ??**, used: ??
braket (type), **95, 102, 104, 123**,
90, used: 95, 102, 102,
102, 102, 105, 123, 90, 91
brakets, **95, 102, 105, 123, 91**,
used: 123, 596, 616
brakets (field), **102, 105**, used:
105, 114, 122, 122, 124,
124, 124, 125, 126, 126
Branch, **655**, used: 655, 655, 655,
656
Broken_Gauge (sig), **179**, used:
broken__is_unit, **786**, used:
BRs, **137**, used: 555
brs_chi_incoming, **564, 565**,
625, used: 597
brs_chi_outgoing, **564, 565, 625**,
used: 597
brs_conjspinors (field), **573**,
used: 573, 574, 580
brs_massive_vectors (field), **573**,
used: 573, 574, 580
brs_psibar_incoming, **564, 565**,
625, used: 597
brs_psibar_outgoing, **564, 565**,
625, used: 597
brs_psi_incoming, **564, 565**,
625, used: 597
brs_psi_outgoing, **564, 565, 625**,
used: 597
brs_realspinors (field), **573**, used:
573, 574, 580
brs_scalars (field), **573**, used:
573, 574, 580
brs_spinors (field), **573**, used:
573, 574, 580
brs_vectors (field), **573**, used:
573, 574, 580
brs_vectorspinors (field), **573**,
used: 573, 574
BSM_anom (module), **272, 270**,
used: ??

- BSM_bsm* (module), **272, 270**,
used: ??, ??, ??, ??, ??,
??, ??
- BSM_flags* (sig), **272, 270**, used:
272, 272, 272, 272, 295,
316, 330, 341, 360, 371,
270
- BSM_ungauged* (module), **272**,
270, used: ??
- buff_printf*, ??, used: ??, ??
- build_forest*, **48**, used: **48, 49**
- bundle* (field), **120**, used: **120,**
120, 120, 120, 121, 121
- Bundle* (module), **739, 737**,
used: **216, 219, 120**
- bundle_to_strings*, **217**, used:
- by_color*, **216**, used: **216, 218,**
219, 219, 219
- c* (type), **221, 221, 221, 225,**
556, 560, 228, 230, 232,
234, 239, 254, 260, 267,
440, 488, 519, 279, 300,
320, 335, 347, 365, 376,
392, 402, 414, ??, ??,
678, 220, 220, 220,
used: **221, 221, 221, 222,**
225, 220, 220, 220
- C*, **233**, used: **233, 234, 234, 235**
- C* (module), **783, 784, 785, 787,**
86, 185, 114, 130, 670,
638, 780, 781, 563, used:
783, 784, 87, 114, 118,
119, 134, 136, 673, 675,
780, 781, 781, 781
- C1*, **431, 482, 513**, used: **432,**
433, 443, 443, 448, 448,
462, 462, 463, 465, 482,
483, 491, 498, 499, 513,
514, 522, 533, 534
- C1c*, **431, 482, 513**, used: **432,**
433, 448, 465, 482, 483,
499, 513, 514, 534
- C2*, **431, 482, 513**, used: **432,**
433, 443, 443, 448, 448,
462, 462, 463, 465, 482,
483, 491, 498, 499, 513,
514, 522, 533, 534
- C2* (module), **86**, used: **87**
- C2c*, **431, 482, 513**, used: **432,**
433, 448, 465, 482, 483,
499, 513, 514, 534
- C3*, **513**, used: **513, 514, 534**
- C3c*, **513**, used: **513, 514, 534**
- C4*, **513**, used: **513, 514, 534**
- C4c*, **513**, used: **513, 514, 534**
- CA* (module), **119**, used: **119,**
119, 120, 120, 120, 120,
120, 121, 121, 121, 122,
122, 122, 122, 122, 122,
123, 123, 123, 123, 123,
123, 123, 124, 124, 124,
124, 124, 125, 125, 125,
125, 125, 125, 126, 126,
126, 126, 126, 126
- Cache* (module), **695, 694**, used:
106
- Cache_Default*, **671**, used: **671**
- Cache_Ignore*, **100**, used: **101**
- Cache_Initialize*, **671**, used: **671**
- cache_mode* (type), **100, 671**,
used:
- cache_name*, **107**, used: **107, 107,**
107
- cache_option*, **100, 671**, used:
101, 107, 671, 673
- Cache_Overwrite*, **100**, used: **101**
- cache_prefix*, **687, 687**, used: **107**
- cache_suffix*, **687, 687**, used: **107**
- Cache_Use*, **100**, used: **100**
- call_function*, **665**, used: **666**
- call_subroutine*, **665**, used: **665**
- canonicalize*, **713, 719, 722,**
712, used:
- cascade* (camlyacc non-terminal),
72, used: **72**
- Cascade* (module), **74, 73**, used:
96, 114, 130, 670, 92
- cascades* (camlyacc non-terminal),
72, used: **72, 72**
- Cascade_lexer* (module), ??, ??,
71, used: **76**
- Cascade_parser* (module), ??, ??,
72, used: ??, **76**, ??, **71**
- Cascade_syntax* (module), **69**,
used: ??, ??, **75**, ??,
72, 72
- Cbar*, **233**, used: **233, 234, 234,**
235
- CF* (module), **670, 569**, used:
671, 673, 673, 674, 674,

- 674, 674, 674, 569, 580,
600, 600, 600, 600, 601,
601, 601, 602, 602, 606,
607, 612, 616, 616, 618,
620, 620, 622
- CFlow* (module), **601**, used: 601,
601, 602, 603, 603, 604
- cflow_to_string*, **601**, used: 612
- CF_aux*, **186**, used: 187, 188,
189, 195, 195, 202, 203,
203, 208
- cf_aux_propagator*, **187**, used:
187
- cf_in* (type), **186**, used: 186
- CF_in*, **186**, used: 187, 188, 189,
194, 194, 199, 200, 200,
201, 201, 208
- CF_io*, **186**, used: 187, 188, 189,
195, 195, 196, 202, 203,
203, 204, 204, 205, 208
- cf_out* (type), **186**, used: 186
- CF_out*, **186**, used: 187, 188,
189, 194, 195, 199, 200,
201, 201, 201, 208
- Ch* (module), **225, 556, 186,**
209, 228, 230, 231, 234,
239, 254, 258, 267, 439,
485, 516, 276, 298, 319,
333, 345, 363, 374, 387,
399, 414, ??, ??, 678,
174, used: 556, 186, 209,
214, 123, 265, 267, 174,
228
- channel*, **691, 690**, used: 135
- channel* (field), **690**, used: 691,
691
- channel* (type), **690**, used: 690
- Channel*, **690, 130**, used: 691,
130
- Chaotic* (module), **43, 40**, used:
- char* (type), **431, 482, 513**, used:
- char* (camllex regexp), **71**, used:
- charge*, **239, 258, 439, 486, 516,**
276, 298, 319, 333, 346,
363, 374, 400, 414, ??,
??, used: 239, 259, 440,
486, 517, 277, 298, 319,
334, 347, 364, 375, 400,
414, ??, ??, 678, 174,
used: 556, 186, 209, 214,
123, 254, 267
- Charges* (module), **183, 182**,
used: 225, 228, 230, 231,
234, 239, 254, 258, 439,
485, 516, 276, 298, 319,
- 334, 347, 364, 375, 400,
414, ??, ??
- charged_chargino_currents*, **441,**
489, 520, used: 462, 498,
533
- charged_currents*, **441, 489, 520,**
280, 301, 322, 335, 348,
365, 376, 403, ??, ??,
used: 462, 498, 533, 289,
310, 325, 337, 350, 367,
377, 407, ??, ??
- charged_currents'*, **239, 261,**
414, ??, used: 239, 261,
261, 414, ??
- charged_currents''*, **239, 261,**
414, used: 239, 261, 414
- charged_currents_ckm*, **239, 261,**
414, used: 246, 422
- charged_currents_triv*, **239, 261,**
414, used: 246, 262, 422
- charged_heavy_currents*, **280**,
used: 289
- charged_quark_currents*, **441,**
489, 520, used: 462, 498,
533
- charged_slepton_currents*, **441,**
489, 520, used: 462, 498,
533
- charged_squark_currents*, **441,**
489, 521, used: 462, 498,
533
- charged_squark_currents'*, **441,**
489, 521, used: 441, 489,
521
- charged_up_currents*, **??**, used:
??
- charged_Z*, **442, 490, 521**, used:
462, 498, 533
- charges*, **225, 556, 186, 209,**
228, 230, 231, 234, 239,
254, 259, 267, 440, 486,
517, 277, 298, 319, 334,
347, 364, 375, 387, 400,
414, ??, ??, 678, 174,
used: 556, 186, 209, 214,
123, 254, 267

- 333, 345, 363, 374, 387,
 399, 414, ??, ??, 678, 174,
 227, 227, 227, 228, 429,
 480, 510, 270, 271, 271
Chargino, **432, 483, 514**, used:
 433, 435, 440, 441, 442,
 443, 443, 444, 444, 446,
 446, 448, 448, 462, 465,
 483, 485, 488, 489, 490,
 491, 491, 491, 492, 492,
 499, 514, 516, 520, 520,
 521, 522, 522, 522, 523,
 524, 534
charlist, **514**, used: 514
check, **56**, used: 56, 56
check_charges, **95, 123, 92**, used:
 673
chg, **493, 524**, used: 524, 524,
 525, 525
Chi, **140**, used: 441, 442, 442,
 444, 444, 444, 444, 445,
 448, 448, 462, 462, 489,
 490, 490, 491, 491, 491,
 492, 520, 521, 521, 522,
 522, 523, 523, 526, 367
Chibar, **140**, used: 441, 442, 442,
 444, 444, 444, 444, 445,
 448, 489, 490, 490, 491,
 491, 491, 492, 520, 521,
 521, 522, 522, 523, 523,
 526, 526
chiggs (type), **513**, used: 514
CHiggs, **514**, used: 514, 516, 522,
 522, 522, 528, 528, 528,
 528, 529, 529, 529, 529,
 529, 531, 532, 532, 534
children, **95, 102, 104, 123, 90**,
 used: 123, 581, 581, 596
children (type), **21, 23, 25, 27**,
27, 34, 35, 41, 41, 42,
43, 44, 45, 95, 98, 98,
99, 100, 102, 104, 111,
123, 19, 37, 38, 40, 89,
94, used: 21, 41, 41, 42,
 43, 43, 44, 45, 98, 98, 100,
 102, 102, 103, 104, 111,
 123, 19, 20, 21, 21, 37, 37,
 38, 38, 38, 39, 39, 40, 40,
 40, 41, 94, 94
children2, **581**, used: 584
children3, **581**, used: 590
chi_gauss, **564, 566, 625**, used:
chi_incoming, **564, 565, 625**,
 used: 597
chi_outgoing, **564, 565, 625**,
 used: 597
chi_projector, **564, 565, 625**,
 used: 594, 594
chi_propagator, **564, 565, 625**,
 used: 593
chi_type, **564, 565, 624**, used:
 580
choose, **713, 716, 720, 752, 712**,
747, used: 10, 10, 17, 17,
 75, 481, 512
choose', **752**, used: 752, 752
choose2, **10, 481, 512**, used: 11,
 13, 481, 512
choose3, **10**, used: 13
choose_opt, **713, 716, 720, 712**,
 used:
chopn, **701, 698**, used: 573, 580,
 580, 616
chopn', **700**, used: 700, 701
chopn'', **700**, used: 700, 700
chop_amplitudes, **616**, used: 620,
 622
CKetSet (module), **121**, used:
 121
CKM_12, **435**, used:
CKM_13, **435**, used:
CKM_23, **435**, used:
ckm_present, **237, 237, 237**,
238, 238, 238, 238, 238,
429, 430, 430, 430, 430,
430, 430, 480, 480, 481,
481, 511, 511, 511, 396,
396, 396, 413, 413, 227,
429, 480, 510, 270, 271,
 used: 239, 246, 439, 446,
 451, 451, 455, 462, 463,
 485, 492, 496, 496, 498,
 498, 524, 530, 530, 532,
 533, 400, 404, 414, 422
classify, **703, 33, 699**, used: 749,
 751, 752, 17, 17, 33
classify_arrays, **574**, used: 574,
 575
classify_nodes, **126**, used: 126

- classify_parameters*, **575**, used: **577**
- classify_singles*, **574**, used: **574**, **575**
- classify_wfs*, **574**, used: **580**
- classify_wfs'*, **573**, used: **573**, **574**
- class_size*, **31**, used: **31**, **32**, **32**
- class_size_3*, **31**, used: **31**
- class_size_n*, **32**, used: **31**
- clist*, **514**, **388**, used: **514**, **393**
- clone*, **703**, **267**, **699**, used: **703**, **735**, **17**, **267**, **267**
- clone3*, **268**, used: **269**
- clone4*, **268**, used: **269**
- clonen*, **269**, used: **269**
- cloop*, **481**, **512**, used: **481**, **482**, **512**, **512**
- cloop_kk*, **384**, used: **384**, **388**, **389**, **389**, **389**, **390**, **390**, **390**, **390**
- cloop_kk2*, **384**, used: **388**
- close_channel*, **691**, used: **692**
- CM* (module), **209**, **119**, **130**, **670**, **569**, used: **209**, **211**, **211**, **119**, **119**, **120**, **121**, **121**, **121**, **122**, **122**, **123**, **124**, **126**, **126**, **131**, **131**, **670**, **572**, **572**, **573**, **575**, **575**, **575**, **576**, **577**, **577**, **577**, **577**, **584**, **590**, **593**, **594**, **594**, **595**, **595**, **596**, **597**, **597**, **598**, **598**, **599**, **599**, **618**, **624**
- CMap* (module), **131**, used: **135**, **135**
- cmdline*, **689**, **688**, used: **671**
- cmp_float*, **??**, **??**, used: **??**
- coarsest_partition*, **79**, **218**, used: **80**, **218**
- coarsest_partition'*, **79**, used: **79**, **79**
- collect23*, **27**, used: **27**
- collect3*, **27**, used: **27**
- collect34*, **27**, used: **27**
- collect4*, **27**, used: **27**
- collect_derivatives*, **786**, used: **786**
- collect_vertices*, **106**, used: **106**
- COLON*, **??**, **??**, used: **??**, **71**
- COLON* (camlyacc token), **72**, used: **72**, **73**
- color*, **225**, **556**, **186**, **209**, **228**, **229**, **231**, **233**, **239**, **254**, **256**, **266**, **434**, **484**, **515**, **274**, **296**, **318**, **332**, **343**, **361**, **373**, **385**, **398**, **414**, **??**, **??**, **677**, **174**, used: **556**, **186**, **188**, **189**, **193**, **197**, **205**, **206**, **207**, **207**, **208**, **209**, **216**, **131**, **254**, **266**
- color* (label), **226**, **178**, used: **560**
- color* (type), **84**, **84**, **88**, **81**, used: **84**, **84**, **88**, **81**, **81**
- Color* (module), **82**, **81**, used: **557**, **557**, **557**, **558**, **559**, **185**, **209**, **216**, **129**, **130**, **130**, **131**, **135**, **135**, **136**, **228**, **229**, **231**, **233**, **239**, **256**, **434**, **484**, **515**, **274**, **296**, **318**, **332**, **343**, **361**, **373**, **385**, **398**, **414**, **601**, **??**, **??**, **677**, **174**, **178**, **180**, **180**, **93**, **93**
- colored_vertex*, **186**, used: **194**, **194**, **194**, **194**, **195**, **195**, **195**, **195**, **197**, **199**, **199**, **199**, **200**, **200**, **200**, **201**, **201**, **201**, **201**, **202**, **202**, **202**, **205**, **205**
- Colorize* (module), **185**, **185**, used: **96**, **98**, **119**, **130**, **670**, **569**, **92**, **94**
- Colorized* (sig), **180**, used: **185**
- Colorized_Gauge* (sig), **180**, used: **185**
- colorize_amplitude*, **122**, used: **122**
- colorize_amplitudes*, **122**, used: **123**
- colorize_braket*, **122**, used: **122**
- colorize_braket1*, **121**, used: **122**
- colorize_coupling*, **121**, used: **121**, **121**
- colorize_crossed_amplitude*, **209**, used: **209**
- colorize_crossed_amplitude1*, **208**, **209**, used: **208**, **209**, **209**

- colorize_dag*, **120**, used: **122**
- colorize_external*, **120**, used: **122**
- colorize_fusion*, **121**, used: **122**
- colorize_fusion2*, **193**, used: **206**
- colorize_fusion3*, **197**, used: **206**
- colorize_fusionnn*, **205**, used: **206**
- colorize_nodes*, **120**, used: **120**
- colorize_sterile_nodes*, **120**, used: **120**
- colorize_wf*, **119**, used: **121**
- colors*, **131**, used:
- colors* (type), **130**, used:
- color_current*, **234**, used: **235**
- color_currents*, **239, 261, 279, 300, 321, 335, 348, 376, 402, 414, ??, ??**, used: **246, 262, 289, 310, 325, 337, 350, 377, 407, 422, ??, ??**
- color_factors*, **129, 131, 93**, used: **606, 612**
- color_factors* (field), **130**, used: **131, 136, 136**
- color_flow*, **131**, used: **135, 135**
- color_flows*, **129, 131, 93**, used: **601, 601, 606, 607, 612**
- color_flows* (field), **130**, used: **131, 136**
- color_flow_ambiguous*, **186**, used: **202, 202**
- color_flow_of_string*, **186**, used: **189**
- color_to_string*, **601**, used: **601**
- columns*, **554**, used: **555**
- column_tabs*, **554**, used: **555**
- col_currents*, **447, 493, 524**, used: **462, 498, 533**
- col_lqino_currents*, **527**, used: **533**
- col_lq_currents*, **527**, used: **533**
- col_sfermion_currents*, **447, 493, 527**, used: **462, 498, 533**
- Combinatorics* (module), **747, 745**, used: **10, 10, 17, 17, 25, 27, 29, 34, 35, 87, 75, 207, 97, 119, 128, 481, 512**
- combine_decays*, **659**, used: **659, 659**
- commute_proj*, **628**, used: **629, 632, 632**
- compare*, **??, ??, ??, ??, 723, 713, 719, 721, 702, 704, 739, 742, 727, 728, 730, 688, 9, 11, 12, 14, 16, 28, 29, 30, 41, 41, 42, 43, 43, 44, 44, 55, 57, 63, 82, 221, 221, 222, 222, 661, 662, 664, 560, 79, 188, 217, 218, 218, 219, 105, 105, 106, 111, 112, 114, 121, 125, 126, 131, 131, 133, 228, 230, 232, 234, 239, 254, 260, 267, 440, 488, 519, 279, 300, 320, 335, 347, 365, 376, 392, 402, 414, 572, ??, ??, 678, ??, ??, 712, 698, 741, 725, 726, 6, 20, 36, 37, 40, 52, 81, 220**, used: **??, ??, ??, ??, ??, 723, 721, 702, 704, 705, 705, 707, 711, 755, 755, 756, 776, 776, 784, 785, 786, 787, 787, 788, 688, 751, 752, 772, 772, 772, 16, 29, 30, 43, 44, 46, 47, 48, 56, 57, 63, 656, 658, 82, 221, 222, 222, 661, 662, 662, 663, 664, 560, 79, 188, 216, 216, 217, 218, 218, 219, 219, 219, 97, 103, 104, 105, 106, 111, 112, 114, 120, 121, 126, 128, 131, 131, 131, 132, 133, 135, 672, 228, 230, 232, 234, 239, 254, 260, 267, 440, 488, 519, 279, 300, 320, 335, 347, 365, 376, 392, 402, 414, 572, ??, ??, 678**
- compare'*, **719**, used: **719, 719**
- compare_base*, **739, 216, 219, 120, 737**, used: **739**
- compare_elt*, **739, 216, 219, 120, 737**, used: **739, 216**
- Comphep* (module), **553, 553**, used:
- Comphep_lexer* (module), **??, ??, 551**, used: **558**
- Comphep_parser* (module), **??,**

- ??, **552**, used: ??, **558**,
??, **551**
- Comphep_syntax* (module), **549**,
549, used: ??, ??, **557**,
557, **560**, ??, **552**, **552**
- complement_index_sets*, **704**,
used: **704**
- complete_fusion_tower*, **113**,
used: **118**
- Complex*, **173**, used: **239**, **260**,
414
- Complex_Array*, **173**, used:
- complex_arrays* (field), **574**,
used: **574**, **575**, **577**
- complex_singles* (field), **574**,
used: **574**, **575**, **577**
- compose*, **713**, **717**, **722**, **755**,
756, **756**, **712**, **754**,
used: **717**, **722**, **758**, **758**
- compose_inverse_ok*, **758**, used:
759
- compose_ok*, **758**, used: **759**
- compress*, **707**, **706**, used: **707**
- compress2*, **707**, **706**, used:
- compressed* (type), **706**, **706**,
used: **706**, **706**
- compressed2* (type), **706**, **706**,
used: **706**, **706**
- concat*, **715**, used: ??, ??, ??,
715, **717**, **742**, **742**, **693**,
695, **696**, **696**, **696**, **776**,
785, **787**, **788**, **767**, **770**,
17, **17**, **56**, **63**, **659**, **659**,
84, **663**, **663**, **663**, **665**,
561, **70**, **71**, **76**, **76**, **76**, **79**,
79, **188**, **205**, **217**, **217**,
218, **126**, **131**, **670**, **671**,
672, **673**, **572**, **572**, **572**,
596, **599**, **599**, **601**, **601**,
601, **601**, **601**, **602**, **602**,
603, **605**, **612**, **681**
- Config* (module), **687**, **687**, used:
695, **107**
- conj*, **82**, **86**, **86**, used: **83**, **83**, **83**
- Conj*, **168**, used:
- ConjSpinor*, **137**, used: **555**, **231**,
233, **239**, **256**, **433**, **483**,
515, **273**, **274**, **296**, **296**,
317, **331**, **342**, **361**, **372**,
386, **397**, **414**, ??, ??, **677**
- conjspinors* (field), **573**, used:
573, **574**, **580**
- conjugate*, **82**, **85**, **221**, **225**,
556, **560**, **188**, **209**, **102**,
103, **228**, **228**, **229**, **230**,
231, **232**, **234**, **234**, **239**,
254, **254**, **257**, **260**, **266**,
267, **435**, **440**, **485**, **488**,
516, **519**, **275**, **279**, **297**,
300, **318**, **320**, **333**, **335**,
344, **347**, **362**, **365**, **373**,
376, **386**, **392**, **399**, **402**,
414, ??, ??, ??, ??, **677**,
678, **176**, **81**, **220**, used:
85, **86**, **223**, **224**, **556**, **558**,
560, **77**, **78**, **79**, **188**, **188**,
209, **209**, **209**, **214**, **219**,
219, **103**, **106**, **113**, **118**,
121, **122**, **124**, **228**, **230**,
232, **234**, **239**, **254**, **254**,
260, **266**, **267**, **440**, **488**,
490, **519**, **521**, **279**, **300**,
320, **335**, **347**, **365**, **376**,
392, **402**, **414**, ??, ??, **678**
- conjugate* (label), **226**, **178**, used:
560
- Conjugates*, **556**, used: **558**
- conjugate_lorentz*, **555**, used:
555, **558**
- conjugate_sans_color*, **188**, **209**,
180, **180**, used: **209**
- conj_char*, **432**, **482**, **513**, used:
435, **440**, **441**, **442**, **443**,
443, **444**, **444**, **446**, **446**,
448, **462**, **485**, **488**, **489**,
490, **491**, **491**, **491**, **492**,
492, **516**, **520**, **520**, **521**,
522, **522**, **522**, **523**, **524**
- conj_chiggs*, **513**, used: **516**
- conj_iso*, **389**, used: **389**, **389**,
390
- conj_symbol*, **472**, **507**, **545**,
used: **472**, **507**, **545**, **546**
- cons*, **713**, **716**, **719**, **776**, **765**,
712, **776**, **763**, used: **716**,
717, **719**, **47**, **48**
- Const*, **168**, used: **560**, **239**, **260**,
260, **260**, **260**, **435**,
275, **297**, **318**, **332**, **344**,
362, **373**, **398**, **414**, ??, ??

- constant* (type), **225, 556, 186, 209, 95, 100, 228, 229, 231, 233, 239, 254, 259, 266, 436, 486, 517, 277, 298, 319, 334, 347, 364, 375, 387, 400, 414, ??, ??, 676, 176, 89**, used: 556, 560, 186, 209, 95, 96, 98, 100, 101, 101, 102, 106, 106, 228, 230, 232, 234, 239, 254, 254, 260, 266, 267, 440, 488, 519, 279, 300, 320, 335, 347, 365, 376, 392, 402, 414, ??, ??, 678, 176, 177, 177, 177, 178, 220, 185, 185, 89, 92, 94
- Constant*, **139**, used: 560, 239, 255, 431, 481, 511, 272, 295, 317, 330, 341, 360, 371, 382, 397, 414, ??, ??
- constant_symbol*, **225, 556, 190, 209, 229, 230, 233, 237, 252, 255, 265, 266, 472, 507, 545, 293, 314, 329, 340, 359, 371, 380, 395, 411, 427, ??, ??, 681, 177**, used: 556, 190, 209, 255, 266, 575, 575, 575, 576, 577, 577, 577, 584, 590
- constant_symbol* (label), **226, 178**, used: 560
- constraints*, **95, 102, 105, 123, 129, 131, 91, 94**, used: 123, 612
- constraints* (field), **102, 105, 130**, used: 105, 114, 119, 122, 131, 136, 136
- consume*, **83**, used: 83
- continuation_lines*, **570**, used: 570, 571
- Continuation_Lines* (exn), **571**, used:
- contract*, **82, 83**, used: 84, 87
- contract4* (type), **141**, used: 141, 142
- copy_matrix*, **789, 789**, used: 792, 793, 793
- Cos*, **436, 168**, used:
- Cos2al*, **436**, used:
- Cos2am2b*, **436**, used:
- Cos2be*, **436**, used:
- Cos4be*, **436**, used:
- Cosamb*, **436**, used:
- Cosapb*, **436**, used:
- Cospsi*, **277, 298, 319**, used:
- Costhw*, **239, 259, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: 239, 260, 260, 414
- Cot*, **168**, used:
- count*, **83, 84**, used: 87
- Count* (module), **29, 21**, used:
- Count* (sig), **29, 20**, used: 21
- count_color_strings*, **206**, used: 207
- count_diagrams*, **95, 124, 92**, used: 674
- count_flavors*, **557**, used: 559
- count_fusions*, **95, 124, 92**, used: 674
- count_ghosts*, **85**, used: 87
- count_ghosts1*, **85**, used: 85
- count_maps*, **661**, used: 661
- count_non_zero*, **67**, used: 67
- count_non_zero'*, **67**, used: 67, 67
- count_processes*, **131**, used: 135
- count_propagators*, **95, 124, 92**, used: 674
- count_trees*, **41, 48, 39**, used: 124
- coupling*, **95, 101, 101, 102, 104, 123, 89**, used: 104, 123, 584
- coupling* (field), **101, 101**, used: 101, 110, 114
- coupling* (type), **95, 98, 98, 99, 100, 102, 104, 123, 89, 94**, used: 95, 98, 101, 101, 102, 102, 102, 102, 104, 105, 105, 111, 123, 133, 90, 92, 94
- Coupling* (module), **137**, used: 221, 222, 223, 555, 557, 557, 557, 557, 559, 560, 560, 185, 95, 100, 101, 101, 102, 106, 106, 228, 229, 231, 233, 239, 239,

- 254, 255, 431, 435, 442,
442, 443, 445, 446, 446,
447, 481, 490, 511, 522,
272, 275, 295, 297, 317,
318, 330, 332, 341, 344,
360, 362, 371, 373, 382,
397, 398, 414, 414, 564,
565, 569, 624, ??, ??, ??,
??, 676, 176, 176, 176,
176, 177, 177, 178, 220, 89
- coupling_tag*, **95, 101, 101, 102,**
104, 123, 90, used: 104,
123
- coupling_tag* (field), **101, 101**,
used: 101, 110, 114
- coupling_tag_raw*, **101**, used: 101
- coupling_to_string*, **98, 98, 99,**
100, 94, used: 101
- Cpp* (module), **638, 563**, used:
- create*, **714, 691, 688, 688**, used:
??, ??, 714, 691, 691, 691,
224, 559, 560, 561, 99,
239, 255, 431, 481, 511,
272, 295, 317, 330, 341,
360, 371, 382, 397, 414,
570, ??, ??
- created* (field), **690**, used: 691,
692
- create_class*, **30**, used: 32
- CRing* (sig), **782, 779**, used: 782,
779
- cross*, **124**, used: 125
- crossing*, **213, 219, 213**, used:
- Crossing_Bundle* (module), **219**,
used:
- Crossing_Projection* (module),
219, used: 219
- cross_in*, **85**, used:
- cross_out*, **86**, used: 86, 86
- cross_uncolored*, **209**, used: 209
- CS* (module), **75**, used: 76
- csign* (type), **383**, used: 383, 384
- current_continuation_line*, **571**,
used: 571, 571, 618
- Custom*, **139**, used: 239, 255,
431, 481, 511, 272, 295,
317, 330, 341, 360, 371,
382, 397, 414, ??, ??
- CWFBundle* (module), **120**,
used: 120, 120, 121, 121,
122
- CWFMap* (module), **121**, used:
121, 122, 122
- Cycle* (exn), **41, 46, 38**, used:
- Cycles* (module), **83**, used: 86, 86
- Cycles* (sig), **82**, used: 83
- C_12_34*, **141**, used: 192, 235,
239, 262, 448, 493, 527,
282, 303, 323, 336, 349,
366, 377, 391, 405, 414,
??, ??, 678
- C_13_42*, **141**, used: 192, 235,
239, 262, 448, 493, 527,
282, 303, 323, 336, 349,
366, 377, 391, 405, 414,
??, ??, 678
- C_14_23*, **141**, used: 192, 235,
239, 262, 448, 493, 527,
282, 303, 323, 336, 349,
366, 377, 391, 405, 414,
??, ??, 678
- C_quqd1L_bt*, **239**, used: 246
- C_quqd1L_tb*, **239**, used: 246
- C_quqd1R_bt*, **239**, used: 246
- C_quqd1R_tb*, **239**, used: 246
- C_quqd8L_bt*, **239**, used: 246
- C_quqd8L_tb*, **239**, used: 246
- C_quqd8R_bt*, **239**, used: 246
- C_quqd8R_tb*, **239**, used: 246
- d* (field), **56**, used: 56, 56, 57,
57, 57, 57, 58, 58, 58, 59,
59, 60, 60, 61, 61, 67
- D*, **233, 239, 255, 432, 483,**
514, 273, 295, 317, 331,
341, 360, 372, 397, 414,
??, ??, used: 233, 234,
234, 235, 239, 242, 243,
243, 243, 244, 244, 244,
245, 245, 245, 245, 246,
246, 246, 246, 247, 256,
257, 259, 260, 261, 261,
261, 261, 261, 262, 433,
435, 439, 440, 441, 441,
442, 443, 443, 443, 445,
446, 447, 447, 461, 465,
483, 485, 488, 488, 489,
490, 490, 491, 492, 492,
493, 499, 514, 516, 519,
520, 520, 522, 522, 523,
523, 524, 524, 525, 525,

- 525, 525, 534, 273, 275,
279, 279, 279, 279, 279,
280, 280, 280, 281, 281,
289, 296, 297, 300, 300,
300, 301, 301, 301, 302,
302, 302, 302, 310, 317,
318, 321, 321, 321, 321,
322, 322, 323, 323, 325,
331, 333, 335, 335, 335,
335, 335, 336, 338, 342,
344, 348, 348, 348, 348,
348, 348, 350, 361, 362,
365, 365, 365, 365, 367,
372, 373, 376, 376, 376,
376, 376, 378, 397, 399,
402, 402, 402, 403, 403,
403, 403, 404, 407, 414,
418, 419, 419, 419, 420,
420, 420, 421, 421, 421,
421, 422, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??
- D* (module), **740, 102, 105**,
used: 740, 740, 102, 102,
105, 112, 112, 112, 112,
113, 113, 113, 114, 114,
114, 119, 119, 119, 120,
120, 120, 120, 122, 122,
122, 124, 124, 125, 126,
126, 126
- D'* (module), **111**, used: 111
- dag* (field), **120**, used: 120, 122
- DAG* (module), **41, 36**, used:
102, 105, 111, 111
- dag_to_dot*, **126**, used: 126, 126
- data* (field), **767, 768**, used: 767,
767, 768, 768
- date*, **685, 684**, used: 686
- date* (field), **685, 684**, used: 686,
760, 9, 21, 41, 55, 221,
660, 553, 185, 95, 228,
429, 480, 511, 271, 640,
563, ??, ??, 675
- Dbar*, **233**, used: 233, 234, 234,
235
- debug*, **670**, used: 671
- decay* (type), **654, 655, 213**,
214, 653, 212, used: 654,
655, 657, 658, 213, 214,
653, 653, 653, 653, 212,
212
- Decay*, **213, 214, 212**, used: 214,
215, 215
- Decay* (module), **55, 60, 65, 54**,
used: 118
- decays* (field), **658**, used: 658,
658, 658, 659
- decay_of_momenta*, **654, 657**,
653, used:
- declarations* (type), **573**, used:
- declaration_chunk_size*, **573**,
used: 573, 580, 580
- declare*, **225**, used: 225
- declare_argument*, **665**, used:
665, 666
- declare_brackets*, **580**, used: 580
- declare_brackets_chunk*, **580**,
used: 580
- declare_default_parameters*, **575**,
used: 577
- declare_list*, **573**, used: 580
- declare_list_chunk*, **573**, used:
573
- declare_momenta*, **580**, used: 580
- declare_momenta_chunk*, **580**,
used: 580
- declare_parameters*, **575**, used:
577
- declare_parameters'*, **575**, used:
575
- declare_parameter_array*, **575**,
used: 577
- declare_wavefunctions*, **580**,
used: 580
- decode*, **675**, used: 675
- Default* (module), **757, 68, 755**,
54, used: 669, 669, 675,
54, 669
- DefaultW* (module), **68, 54**,
used: 669
- default_accessibility* (field), **615**,
used: 615, 620, 621, 621,
621, 622, 622, 623
- default_function*, **665**, used: 666
- default_parameter*, **575**, used:
575
- default_subroutine*, **665**, used:
665
- default_width*, **239, 255, 431**,
481, 511, 272, 295, 317,

- 330, 341, 360, 371, 382, 397, 414, ??, ??, used:**
239, 239, 255, 257, 431, 434, 481, 484, 511, 516, 272, 275, 295, 297, 317, 318, 330, 332, 341, 344, 360, 362, 371, 373, 382, 386, 397, 398, 414, 414, ??, ??, ??, ??
- Delta*, **435**, used:
- den* (field), **84, 85, 82**, used: **87**
- dependencies*, **41, 47, 95, 102, 105, 123, 39, 90**, used: **114, 119, 122, 123, 133, 134**
- dependencies* (field), **102, 105**, used: **105, 114, 119, 122**
- derive*, **783, 785, 780**, used: **786, 786, 786**
- derived* (field), **173**, used: **560, 229, 230, 232, 235, 239, 260, 440, 488, 519, 278, 300, 320, 335, 347, 365, 376, 393, 402, 414, 575, 577, ??, ??, 679**
- derived_arrays* (field), **173**, used: **560, 229, 230, 232, 235, 239, 260, 440, 488, 519, 278, 300, 320, 335, 347, 365, 376, 393, 402, 414, 575, 577, ??, ??, 679**
- derived_parameters*, **239, 260, 278, 300, 320, 335, 347, 365, 376, 414, ??, ??**, used: **239, 260, 278, 300, 320, 335, 347, 365, 376, 414, ??, ??**
- derived_parameter_arrays*, **239, 260, 278, 300, 320, 335, 347, 365, 376, 414, ??, ??**, used: **239, 260, 278, 300, 320, 335, 347, 365, 376, 414, ??, ??**
- derive_inner*, **783, 786, 781**, used:
- derive_inner'*, **783, 786, 781**, used:
- derive_outer*, **783, 786, 781**, used: **787**
- descend*, **729, 729, 729, 730, 732, 732, 732, 733**, used: **729, 729, 729, 730, 732, 732, 732, 733**
- description*, **685, 29, 74, 77, 684, 74**, used: **686, 56, 62, 119, 136, 265, 612**
- description* (field), **685, 77**, used: **685, 77, 77, 80**
- DH*, **432**, used:
- diag*, **481, 512**, used: **481, 481, 512, 512**
- diagnose_arguments*, **579**, used: **579, 598**
- diagnose_gauge*, **579**, used: **579, 595**
- diagnose_momenta*, **579**, used: **579, 598**
- diagnostic* (type), **563, 579, 180**, used: **181**
- diagnostic_mode* (type), **579**, used:
- diagrams*, **29, 32, 669, 675, 675, 21, 669**, used: **33**
- diagrams_per_keystone*, **29, 33, 21**, used: **34**
- diagrams_via_keystones*, **29, 34, 21**, used:
- diagram_class* (type), **30**, used:
- dictionary*, **129, 131, 93**, used: **620, 620, 622**
- dictionary* (field), **130**, used: **131, 136**
- diet*, **381, 381, 381, 381, 382, 382, 382, 271**, used: **382, 392**
- diff*, **213, 219, 213**, used: **??, 704, 743, 219, 135**
- Diff*, **168**, used: **239, 260, 260, 414**
- DIFF_ELEMENT* (sig), **??, ??**, used: **??, ??, ??, ??**
- digit* (camlllex regexpr), **71, 551**, used: **71, 551, 551**
- digits*, **690**, used: **691, 692**
- digits* (field), **690**, used: **691, 692, 692**
- dim*, **55, 56, 62, 52**, used: **63, 63, 63, 65, 66, 67, 659, 659, 75**

- dim0*, **62**, used: **62**, **63**, **63**, **64**,
64, **64**, **64**
Dim4_Vector_Vector_Vector_L,
140, used: **190**, **239**, **414**
Dim4_Vector_Vector_Vector_L5,
140, used: **190**, **239**, **414**
Dim4_Vector_Vector_Vector_T,
140, used: **190**, **239**, **414**
Dim4_Vector_Vector_Vector_T5,
140, used: **190**, **239**, **414**
Dim5_Scalar_Gauge2, **140**,
used: **190**, **241**, **241**, **449**,
493, **337**, **349**, **366**, **415**,
416, **678**
Dim5_Scalar_Gauge2_Skew,
140, used: **190**, **449**, **493**,
288, **309**, **324**
Dim5_Scalar_Vector_Vector_T,
140, used: **190**
Dim5_Scalar_Vector_Vector_TU,
140, used: **190**, **241**
Dim5_Scalar_Vector_Vector_U,
140, used: **190**, **241**, **415**
Dim5_Tensor_2_Vector_Vector_1,
140, used: **190**
Dim5_Tensor_2_Vector_Vector_2,
140, used: **190**
Dim6_Gauge_Gauge_Gauge,
140, used: **190**, **239**, **414**
Dim6_Gauge_Gauge_Gauge_5,
140, used: **190**, **239**, **414**
Dim6_Vector_Vector_Vector_T,
140, used: **190**
Dim7_Tensor_2_Vector_Vector_T,
140, used: **190**
disambiguate_fusions, **133**, used:
136
Discrete (module), **43**, **40**, used:
disjoint, **743**, used: **744**
display_blanks, **570**, used: **570**,
571
display_newline, **571**, used: **571**
distribute_degrees, **32**, used: **32**
distribute_degrees', **32**, used: **32**,
32
distribute_degrees'', **32**, used: **32**,
32
DIV, **??**, **??**, used: **??**, **551**
DIV (camlyacc token), **552**,
used: **552**, **552**
divide, **550**, **549**, used: **??**, **552**
division, **773**, used: **773**
DL, **239**, **414**, used: **239**, **245**,
247, **414**, **421**, **422**
Dodd, **295**, used: **296**
domain (type), **723**, **723**, **722**,
used: **723**, **723**, **722**, **723**
dot, **549**, **549**, used: **??**, **552**
DOT, **??**, **??**, used: **??**, **551**
DOT (camlyacc token), **552**,
used: **552**, **552**
Dotproduct, **549**, **549**, used: **549**
DR, **239**, **414**, used: **239**, **245**,
247, **414**, **421**, **422**
drb, **62**, used: **62**, **63**, **63**, **63**, **66**,
67
drb0, **62**, used: **63**, **64**, **64**, **64**
DScalar2_Vector2, **141**, used:
191
DScalar4, **141**, used: **191**
dummy, **691**, **690**, used: **135**
Dummy (module), **563**, **563**,
used: **638**, **638**, **638**, **638**,
638, **638**, **639**
dummy_flavor, **557**, used: **559**
dump, **775**, **765**, used:
Duplicate (exn), **55**, **56**, **62**, **654**,
656, **51**, **653**, used:
Dyn (module), **739**, **738**, used:
740, **216**
Dyn (sig), **739**, **738**, used: **738**
D_Alpha_WWWW0_S, **239**,
414, used: **239**, **414**
D_Alpha_WWWW0_T, **239**,
414, used: **239**, **414**
D_Alpha_WWWW0_U, **239**,
414, used: **239**, **414**
D_Alpha_WWWW2_S, **239**,
414, used: **239**, **414**
D_Alpha_WWWW2_T, **239**,
414, used: **239**, **414**
D_Alpha_ZZWW0_S, **239**, **414**,
used: **239**, **414**
D_Alpha_ZZWW0_T, **239**, **414**,
used: **239**, **414**
D_Alpha_ZZWW1_S, **239**, **414**,
used: **239**, **414**
D_Alpha_ZZWW1_T, **239**, **414**,
used: **239**, **414**

- D_Alpha_ZZWW1_U*, **239, 414**,
 used: **239, 414**
D_Alpha_ZZZZ_S, **239, 414**,
 used: **239, 414**
D_Alpha_ZZZZ_T, **239, 414**,
 used: **239, 414**
D_K1_L, **341**, used: **342, 344**,
350
D_K1_R, **341**, used: **342, 344**,
350
D_K2_L, **341**, used: **342, 344**,
350
D_K2_R, **341**, used: **342, 344**,
350
d_p, **631**, used: **632, 635, 635**,
636, 636, 636
e (type), **??, ??, ??, ??**, used:
??, ??, ??, ??, ??, ??, ??
e (camlyacc non-terminal), **552**,
 used: **552, 552**
E, **239, 259, 436, 486, 517**,
277, 298, 319, 334, 347,
364, 375, 400, 414, ??,
 used: **239, 260, 414**
edge (type), **41, 41, 42, 43, 44**,
45, 111, 37, 38, 40,
 used: **41, 41, 42, 43, 43**,
44, 45, 102, 111, 37, 37,
38, 38, 38, 39, 39, 39, 39,
39, 40, 40, 40, 41
Edges (module), **111**, used: **111**
edges_feynmf, **769**, used: **770**
edges_feynmf', **769**, used: **769**,
769
EEnd, **??, ??**, used: **??**
Eidelta, **436**, used:
electromagnetic_currents, **239**,
260, 279, 300, 321, 335,
348, 365, 376, 402, 414,
??, ??, used: **246, 262**,
289, 310, 325, 337, 350,
367, 377, 407, 422, ??, ??
electromagnetic_currents', **??**,
 used: **??**
electromagnetic_currents_2, **440**,
488, 520, used: **462, 498**,
533
electromagnetic_currents_3, **440**,
488, 519, used: **462, 498**,
533
electromagnetic_sfermion_currents,
440, 488, 519, used: **462**,
498, 533
Electron, **231**, used: **231, 231**,
232, 232
elements, **713, 719, 721, 712**,
 used: **704, 739, 739, 742**,
742, 743, 785, 786, 787,
788, 45, 47, 662, 188, 218,
218, 219, 105, 121, 125,
125, 580
elements', **719**, used: **719, 719**
eliminate_common_fusions, **134**,
 used: **136**
eliminate_common_fusions1,
134, used: **134**
elt (type), **739, 739, 739, 740**,
740, 742, 742, 216, 219,
120, 737, 738, 738, 741,
 used: **739, 739, 739, 739**,
739, 740, 740, 740, 742,
216, 737, 738, 738, 738,
738, 738, 738, 738, 738,
741, 742
Elt_Base (sig), **739, 737**, used:
739, 740, 738, 738
embedding, **706, 706**, used:
embedding (field), **706**, used: **706**,
707, 707, 708
embedding1, **707, 706**, used:
embedding1 (field), **706**, used:
707, 707, 708
embedding2, **707, 706**, used:
embedding2 (field), **706**, used:
707, 707, 708
embed_in_decay, **656**, used: **656**,
657, 657
embed_in_decays, **657**, used:
657, 658
empty, **713, 714, 719, 742, 742**,
727, 728, 728, 730, 731,
688, 41, 44, 45, 46, 49,
658, 129, 136, 712, 741,
725, 726, 726, 688, 38,
93, used: **??, ??, 723**,
719, 704, 704, 707, 739,
739, 742, 743, 743, 743,
744, 744, 728, 728, 728,
728, 730, 731, 731, 731,
733, 784, 785, 785, 787,

- 787, 688, 688, 772, 772,
30, 45, 45, 45, 46, 46, 46,
47, 47, 48, 48, 49, 49, 658,
223, 224, 225, 662, 662,
662, 664, 79, 188, 218,
219, 98, 99, 105, 106, 112,
112, 114, 119, 120, 121,
122, 125, 125, 126, 133,
134, 135, 673, 673, 228,
229, 231, 233, 563, 580,
618, 676
- Empty*, **713**, used: 714, 714, 715,
716, 716, 717, 718, 718,
719
- em_lqino_currents*, **527**, used:
533
- em_lq_currents*, **527**, used: 533
- em_up_type_currents*, **??**, used:
??
- END*, **??, ??, ??, ??**, used: **??**,
??, 71, 551
- END* (camlyacc token), **72, 552**,
used: 72, 552
- end_step*, **692, 690**, used: 135
- enumerate*, **701, 698**, used: 705,
616
- EPowSet* (module), **742**, used:
742, 742, 742, 743, 743,
743, 744, 744, 744
- equal*, **727, 728, 730, 82, 86, 86**,
221, 222, 222, 725, 726,
used: 83, 83
- EResult*, **??, ??**, used: **??**
- ESet* (module), **742**, used: 742,
742, 742, 743, 743, 743,
743
- EStart*, **??, ??**, used: **??**
- Eta*, **273, 295, 317**, used: 273,
275, 281, 288, 289, 296,
297, 302, 309, 310, 317,
318, 323, 324, 324, 325
- eta_higgs_gauge*, **324**, used: 325
- eval*, **41, 48, 654, 657, 39, 653**,
used: 48, 48
- eval_decay*, **654, 655, 653**, used:
655, 657
- eval_memoized*, **41, 49, 39**, used:
49, 125
- eval_memoized'*, **48**, used: 49
- eval_offspring*, **48**, used: 48
- eval_parameter*, **577**, used: 577
- eval_parameter'*, **576**, used: 576,
577, 577
- eval_parameter_pair*, **577**, used:
577
- eval_para_list*, **577**, used: 577
- eval_para_pair_list*, **577**, used:
577
- ew* (field), **99**, used: 99, 99, 99,
99, 100
- ew_order_in_bounds*, **100**, used:
100
- exists*, **695, 696, 694**, used: 704,
33, 207
- expand_decays*, **213, 216, 212**,
used: 672
- expand_home*, **693, 693**, used:
695
- expand_scatterings*, **213, 215**,
212, used: 672
- export*, **727, 730, 730, 733, 726**,
727, used:
727, used: 730, 730,
733, 733
- export'*, **730, 733**, used: 730, 730,
733, 733
- expr*, **??, ??**, used: 558
- expr* (type), **168**, used: 168, 173,
177, 178
- expr* (camlyacc non-terminal),
552, used: 552
- ext* (field), **30**, used: 30, 31, 31,
31, 31
- extend*, **688, 688**, used: 688, 688,
101, 130
- externals*, **95, 102, 105, 123, 91**,
used: 662, 123, 674, 675,
580, 596, 598, 599, 599
- externals* (field), **102, 105**, used:
105, 114
- external_color_flows*, **207**, used:
209
- external_edges*, **772**, used: 772
- external_edges_from*, **772**, used:
772, 772
- external_flavors*, **225, 556, 188**,
209, 228, 229, 231, 233,
239, 254, 256, 267, 433,
483, 514, 273, 296, 317,
331, 342, 361, 372, 393,
397, 414, ??, ??, 676,
177, used: 556, 209, 671,

- 228, 229, 231, 233, 239,
254, 256, 267, 433, 483,
514, 273, 296, 317, 331,
342, 361, 372, 397, 414,
??, ??, 676
external_flavors', 433, used: 433
external_flavors'', 433, used: 433
external_ghosts, 207, used: 209
external_wfs, 102, 103, 114,
used: 118, 122
ExtMSSM (module), 511, 510,
used: ??
extMSSM_flags (sig), 511, 510,
used: 511, 511, 511, 510
ext_edges (field), 772, used: 772,
773, 774
ext_incidence, 773, used: 774
ext_layout (type), 773, 765,
used: 773, 765, 765
ext_momentum, 572, used: 572,
599
ext_nodes (field), 772, used: 773,
773, 774, 774, 775, 775,
775
f (type), 221, 221, 221, 225,
556, 560, 228, 230, 232,
234, 239, 254, 260, 267,
440, 488, 519, 279, 300,
320, 335, 347, 365, 376,
392, 402, 414, ??, ??,
678, 220, 220, 220,
used: 221, 221, 221, 221,
221, 222, 222, 222, 225,
220, 220, 220, 220
F (module), 661, 560, 111, 130,
670, 228, 230, 232, 234,
239, 254, 260, 267, 440,
488, 519, 279, 300, 320,
335, 347, 365, 376, 392,
402, 414, 569, ??, ??,
678, used: 661, 661, 661,
661, 662, 662, 560, 111,
130, 130, 131, 131, 133,
133, 134, 135, 136, 670,
670, 670, 673, 673, 674,
674, 674, 674, 675, 675,
229, 232, 235, 247, 255,
262, 269, 464, 499, 534,
289, 310, 325, 337, 350,
367, 377, 392, 407, 422,
569, 572, 572, 572, 572,
572, 573, 573, 580, 580,
581, 581, 584, 590, 595,
595, 596, 596, 596, 597,
597, 598, 598, 599, 599,
599, 599, 614, 616, ??, ??,
679
F12, 142, used: 223
F123, 142, used: 224
F124, 142, used: 224
F13, 142, used: 223
F132, 142, used: 224
F134, 142, used: 224
F142, 142, used: 224
F143, 142, used: 224
F2 (module), 221, used: 222, 223
F2' (module), 223, used: 223,
223
F21, 142, used: 223
F213, 142, used: 224
F214, 142, used: 224
F23, 142, used: 223, 230
F231, 142, used: 224
F234, 142, used: 224, 230
F241, 142, used: 224
F243, 142, used: 224
F3 (module), 222, used: 222, 224
F3' (module), 224, used: 224,
224
F31, 142, used: 223
F312, 142, used: 224
F314, 142, used: 224
F32, 142, used: 223
F321, 142, used: 224
F324, 142, used: 224
F341, 142, used: 224
F342, 142, used: 224
F412, 142, used: 224
F413, 142, used: 224
F421, 142, used: 224
F423, 142, used: 224
F431, 142, used: 224
F432, 142, used: 224
factor, 84, 87, 82, used: 135
factor (type), 84, 85, 82, used:
84, 129, 130, 82, 93
factorial, 748, 28, 29, 745, 20,
used: 749, 749, 29, 33, 33
factorial', 748, used: 748, 748

- factorize*, **703, 699**, used: **752, 752**
factorized_keystones, **752, 746**, used: **25, 27**
factorized_partitions, **752, 746**, used:
factorize_brackets, **121**, used: **122**
Fake_Graded_Map (module), **49**, used: **49**
Fake_Grading (module), **44**, used: **49**
False, **70, 75, 69**, used: **70, 70, 76**
family, **239, 256, 433, 483, 514, 273, 296, 317, 331, 342, 361, 372, 397, 414, ??, ??**, used: **239, 256, 433, 483, 514, 273, 296, 317, 331, 342, 361, 372, 397, 414, ??, ??**
fan, **767, 764**, used: **767**
fastener, **566, 625**, used: **567, 567, 567, 626, 626, 627, 628, 628, 629, 629, 632, 633, 633, 634, 634, 635, 636, 636**
FBF, **140**, used: **190, 232, 234, 239, 242, 242, 242, 242, 243, 243, 243, 243, 243, 244, 244, 244, 244, 244, 245, 245, 245, 245, 245, 246, 246, 246, 246, 260, 261, 261, 261, 261, 261, 440, 440, 441, 441, 441, 441, 442, 442, 442, 442, 443, 443, 443, 443, 443, 443, 444, 444, 444, 444, 445, 446, 446, 447, 488, 488, 488, 489, 489, 489, 490, 490, 490, 490, 490, 491, 491, 491, 491, 491, 492, 492, 492, 493, 519, 520, 520, 520, 520, 520, 521, 521, 521, 521, 522, 522, 522, 522, 522, 523, 523, 523, 524, 524, 524, 524, 525, 525, 525, 525, 525, 525, 525, 526, 526, 526, 526, 527, 527, 527, 279, 279, 279, 279, 279, 279, 280, 280, 280, 281, 281, 300, 300, 300, 301, 301, 301, 302, 302, 302, 302, 321, 321, 321, 321, 321, 322, 322, 322, 323, 323, 335, 335, 335, 335, 336, 348, 348, 348, 348, 348, 365, 365, 365, 365, 376, 376, 376, 376, 389, 389, 389, 390, 390, 390, 390, 402, 402, 402, 403, 403, 403, 403, 403, 403, 404, 404, 404, 414, 418, 418, 418, 418, 419, 419, 419, 419, 420, 420, 420, 420, 421, 421, 421, 421, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, 678**
fermion, **225, 556, 188, 209, 228, 229, 231, 234, 239, 254, 258, 266, 435, 485, 516, 275, 298, 318, 333, 345, 363, 374, 386, 399, 414, ??, ??, 677, 176**, used: **556, 188, 209, 97, 127, 254, 266**
fermion (label), **226, 178**, used: **560**
fermion (type), **383, 140**, used: **384, 564, 140, 141**
Fermion, **97, 127, 384**, used: **97, 97, 127, 127, 384, 386, 389, 389, 389, 389, 390, 390, 390, 390**
fermionbar (type), **140**, used: **564, 140, 141**
Fermions (sig), **564**, used: **565, 569, 624**
fermion_of_lorentz, **555**, used: **555, 558, 558**
ferm_of_sff, **439**, used:
feynmf (type), **768, 764**, used: **764, 765**
fiber, **739, 740, 740, 740, 738, 738**, used:
fiber (type), **739, 739, 740, 740, 738, 738**, used: **739, 740, 740, 738, 738, 738, 738, 738**

-
- Fiber* (module), **739**, used: **739**,
739, **739**, **739**
 - fibered_dag* (type), **120**, used:
 - fibers*, **739**, **739**, **740**, **740**, **738**,
738, used: **740**
 - fiber_to_string*, **217**, used: **217**
 - field*, **210**, **239**, **256**, **266**, **273**,
331, **342**, **361**, **372**, **397**,
414, **??**, **??**, **179**, used:
266, **267**, **268**, **268**, **269**
 - field* (type), **210**, **239**, **255**, **266**,
273, **331**, **342**, **360**, **372**,
397, **414**, **??**, **??**, **179**,
used: **179**
 - file*, **691**, **690**, used: **135**
 - File*, **690**, **130**, used: **691**, **130**
 - filter_keystone*, **114**, used: **118**
 - filter_offspring*, **112**, used: **112**
 - filter_sign*, **753**, used: **753**, **753**,
754, **754**
 - finalize*, **659**, used: **659**
 - finalize1*, **656**, used: **656**, **659**
 - finalize_decay*, **656**, used: **657**
 - find*, **713**, **715**, **720**, **695**, **696**,
727, **728**, **728**, **730**, **731**,
44, **45**, **49**, **712**, **694**,
725, **726**, **726**, used: **723**,
715, **720**, **739**, **739**, **696**,
728, **728**, **728**, **731**, **731**,
731, **784**, **786**, **787**, **688**,
772, **30**, **45**, **45**, **46**, **46**, **46**,
47, **47**, **48**, **48**, **49**, **222**,
222, **222**, **661**, **662**, **560**,
106, **112**, **114**, **119**, **121**,
122, **126**, **133**, **135**, **394**
 - find1*, **728**, **731**, used: **729**, **729**,
729, **730**, **731**, **732**, **732**,
732
 - find_first*, **695**, used: **696**
 - findfst*, **83**, used: **83**, **83**
 - find_opt*, **713**, **715**, **720**, **712**,
used: **715**, **720**, **707**
 - find_snd*, **83**, used: **83**, **83**, **83**
 - first_match*, **766**, **654**, used: **766**,
654
 - first_match'*, **654**, used: **654**, **654**
 - first_non_white*, **553**, used: **554**
 - first_pair*, **654**, used: **658**
 - first_pair'*, **654**, used: **654**, **654**
 - flatMap*, **701**, **699**, used: **701**,
787, **788**, **753**, **765**, **766**,
771, **771**, **772**, **772**, **17**, **25**,
27, **34**, **35**, **226**, **663**, **75**,
206, **206**, **206**, **215**, **216**,
110, **121**, **122**, **122**, **124**,
125, **133**, **135**, **670**, **671**,
228, **229**, **231**, **233**, **239**,
244, **245**, **245**, **246**, **246**,
246, **256**, **256**, **261**, **261**,
262, **267**, **267**, **269**, **433**,
433, **443**, **443**, **444**, **444**,
445, **446**, **446**, **448**, **450**,
451, **451**, **452**, **454**, **455**,
455, **456**, **456**, **457**, **459**,
459, **460**, **460**, **462**, **462**,
464, **483**, **483**, **492**, **494**,
495, **496**, **496**, **496**, **497**,
497, **498**, **498**, **499**, **514**,
514, **523**, **524**, **525**, **525**,
525, **525**, **525**, **526**, **526**,
526, **527**, **527**, **527**, **528**,
529, **530**, **530**, **530**, **531**,
531, **532**, **533**, **534**, **273**,
273, **289**, **296**, **296**, **310**,
317, **317**, **321**, **323**, **325**,
331, **331**, **337**, **342**, **342**,
350, **361**, **361**, **367**, **372**,
372, **377**, **384**, **397**, **397**,
407, **414**, **421**, **421**, **421**,
422, **573**, **577**, **614**, **617**,
??, **??**, **??**, **??**, **??**, **??**, **??**,
??, **??**, **676**
 - flatten_keystones*, **110**, used: **126**
 - flavor*, **95**, **102**, **103**, **123**, **89**,
used: **661**, **662**, **110**, **113**,
119, **121**, **123**, **675**, **572**,
573, **584**, **595**, **595**, **596**,
597, **597**, **598**, **598**, **599**
 - flavor* (field), **102**, **103**, used:
103, **103**, **104**, **105**, **109**,
110, **113**, **114**, **119**, **120**,
121, **121**, **124**, **126**
 - flavor* (type), **225**, **556**, **74**, **75**,
186, **209**, **213**, **213**, **95**,
96, **96**, **102**, **103**, **123**,
127, **129**, **130**, **669**, **670**,
228, **229**, **231**, **233**, **239**,
254, **255**, **266**, **432**, **483**,
514, **273**, **295**, **317**, **331**,

- 341, 360, 372, 384, 397, 414, ??, ??, 676, 174, 73, 212, 89, 92, 669**,
used: 661, 661, 662, 556,
560, 74, 75, 75, 75, 77,
186, 186, 209, 213, 213,
213, 214, 217, 219, 95, 96,
96, 96, 96, 96, 98, 102,
102, 102, 102, 103, 103,
103, 105, 106, 106, 106,
123, 127, 127, 129, 130,
130, 130, 669, 670, 228,
230, 232, 234, 239, 254,
254, 259, 260, 267, 436,
440, 486, 488, 517, 519,
277, 279, 298, 300, 319,
320, 334, 335, 347, 347,
364, 365, 375, 376, 392,
400, 402, 414, ??, ??, ??,
??, 678, 174, 174, 174,
176, 176, 176, 176, 176,
176, 177, 177, 177, 177,
177, 177, 178, 179, 179,
180, 180, 180, 180, 220,
74, 74, 74, 74, 185, 185,
212, 212, 213, 213, 89, 91,
92, 92, 94, 94, 669, 669
- Flavor* (sig), **221, 220**, used:
221, 220
- FLAVOR*, **??, ??**, used: **??, ??**,
71
- FLAVOR* (camlyacc token), **72**,
used: **73**
- flavors*, **225, 556, 188, 209, 217, 129, 131, 228, 229, 231, 233, 239, 254, 256, 267, 433, 483, 514, 273, 296, 317, 331, 342, 361, 372, 393, 397, 414, 580, ??, ??, 676, 177, 93**, used:
556, 561, 188, 209, 218,
107, 118, 254, 267, 394,
580, 596, 599, 600, 600,
600, 602, 602, 612, 618
- flavors* (field), **130**, used: **131**,
136
- flavors* (label), **226, 178**, used:
- flavors* (type), **130**, used:
- flavors_of_particles*, **559**, used:
561
- flavors_sans_color_to_string*,
599, used: **599**
- flavors_symbol*, **572**, used: **580**,
596, 599, 618
- flavors_to_string*, **663, 76, 599**,
used: **663, 663, 664, 76**,
599
- flavor_keystone*, **109**, used: **110**
- flavor_keystones*, **110**, used: **118**
- flavor_list* (camlyacc
non-terminal), **73**, used:
72, 73
- flavor_of_antiparticle*, **558**, used:
559
- flavor_of_b*, **384**, used: **393, 393**
- flavor_of_f*, **384**, used: **393, 393**
- flavor_of_particle*, **558**, used:
559
- flavor_of_string*, **225, 556, 189, 209, 229, 230, 232, 235, 247, 255, 262, 267, 465, 499, 534, 289, 310, 325, 338, 350, 367, 378, 394, 407, 422, ??, ??, 679, 177**, used: **556, 76, 189**,
209, 214, 255, 267
- flavor_of_string* (label), **226**,
178, used:
- flavor_sans_color*, **186, 209, 95, 123, 180, 180, 89**, used:
186, 206, 206, 206, 209,
119, 120, 121, 123, 131,
670
- flavor_sans_color* (type), **186**,
209, 95, 123, 180, 180,
89, used: **209, 95, 96, 98**,
180, 180, 180, 180, 185,
185, 89, 90, 92, 92, 94
- Flavor_Set* (module), **662**, used:
662, 662, 662
- flavor_sums*, **217**, used: **218**
- flavor_symbol*, **225, 556, 189, 209, 229, 230, 232, 236, 250, 255, 264, 266, 467, 503, 539, 291, 313, 327, 339, 357, 369, 379, 394, 409, 425, ??, ??, 680, 177**, used: **556, 189, 209**,
126, 670, 252, 255, 265,
266, 472, 293, 314, 329,

- 340, 359, 371, 380, 411,
427, 572, 572, 595, ??, ??
- flavor_symbol* (label), **226, 178**,
used: 560
- flavor_to_string*, **225, 556, 189**,
209, 229, 230, 232, 235,
248, 255, 262, 267, 465,
500, 536, 290, 311, 326,
338, 352, 368, 378, 393,
408, 423, ??, ??, 679,
177, used: 663, 556, 561,
76, 189, 205, 209, 217,
131, 670, 671, 673, 255,
267, 394, 599, 599, 601,
602
- flavor_to_string* (label), **226**,
178, used: 560
- flavor_to_TeX*, **225, 556, 189**,
209, 229, 230, 232, 236,
249, 255, 263, 267, 467,
501, 537, 290, 312, 327,
339, 354, 369, 379, 395,
409, 424, ??, ??, 680,
177, used: 556, 189, 209,
255, 267
- flavor_to_TeX* (label), **226, 178**,
used: 560
- flip_incoming*, **658**, used: 658
- flip_s_channel_in*, **55, 60, 65**,
54, used: 658, 661
- flow*, **209, 211, 180, 180**, used:
211, 131
- Flow* (module), **84, 82**, used:
209, 129, 130, 130, 131,
135, 135, 136, 601, 180,
180, 93, 93
- Flow* (sig), **84, 81**, used: 82
- FMap* (module), **131**, used: 135,
135
- Fn* (module), **222**, used: 222
- fold*, **713, 718, 722, 727, 728**,
729, 730, 732, 735, 767,
41, 41, 42, 43, 44, 44,
45, 47, 49, 111, 712,
725, 726, 726, 734, 764,
37, 39, 40, used: 718,
719, 722, 739, 739, 744,
744, 729, 732, 785, 785,
785, 785, 786, 786, 786,
786, 786, 786, 787, 787,
- 787, 788, 735, 767, 767,
768, 16, 17, 17, 31, 44, 45,
45, 45, 46, 47, 47, 47, 47,
47, 47, 47, 47, 48, 48, 48,
49, 662, 215, 216, 106,
111, 114, 119, 120, 121,
122, 126, 133
- fold* (type), **736, 734**, used: 734
- fold'*, **729, 732**, used: 729, 732
- fold2*, **786, 735, 734**, used: 786,
735, 735, 11, 11, 13, 15,
48, 109, 110, 121, 125
- fold2* (type), **736, 734**, used: 734
- fold2_rev*, **735**, used: 735
- fold3*, **735, 734**, used: 735, 12,
13, 15
- fold3_rev*, **735**, used: 735
- fold_left*, **9, 11, 12, 14, 16, 6**,
used: ??, ??, ??, 723,
701, 701, 702, 702, 704,
704, 743, 693, 785, 786,
786, 786, 786, 787, 787,
688, 735, 735, 735, 735,
749, 749, 750, 750, 750,
751, 751, 751, 751, 751,
752, 753, 754, 754, 772,
772, 774, 16, 27, 27, 30,
30, 30, 32, 32, 33, 33, 33,
33, 34, 48, 48, 62, 183,
183, 184, 184, 85, 223,
224, 661, 662, 662, 557,
559, 560, 75, 188, 217, 99,
100, 105, 110, 112, 112,
112, 113, 121, 121, 122,
124, 124, 133, 134, 134,
135, 577, 580, 596, 599,
601, 601, 601, 602, 602,
603, 603, 604, 616, 618
- fold_left2*, **701, 699**, used:
- fold_lefti*, ??, used: ??, ??
- fold_left_internal*, **9, 11, 12, 14**,
16, 6, used: 110
- fold_lines*, **554**, used: 555
- fold_nodes*, **41, 47, 38**, used:
113, 120, 126
- fold_rev*, **735**, used: 735, 735
- fold_right*, **9, 11, 12, 14, 16, 6**,
used: 702, 704, 704, 739,
742, 743, 743, 761, 769,
11, 11, 13, 13, 15, 16, 17,

- 17, 43, 657, 658, 662, 662,
664, 550, 555, 76, 217,
217, 217, 218, 218, 219,
105, 106, 120, 121, 125,
580
- fold_right2*, **702**, **699**, used: 125
- fold_right_internal*, **9**, **11**, **12**,
14, **16**, **6**, used: 100
- forest*, **41**, **48**, **95**, **125**, **39**, **92**,
used: 674, 675
- Forest* (module), **43**, **37**, used:
105, 111
- Forest* (sig), **41**, **37**, used: 43, 43,
44, 49, 37, 40, 40
- forest'*, **124**, used: 125
- Forest_Grader* (sig), **43**, **40**,
used: 41
- forest_memoized*, **41**, **49**, **39**,
used: 124
- format_coeff*, **582**, used: 582,
582, 583, 583
- format_constant*, **576**, used: 595
- format_coupling*, **566**, **582**, **625**,
used: 566, 567, 567, 585,
585, 585, 585, 586, 586,
586, 586, 586, 586, 587,
587, 587, 587, 587, 587,
588, 588, 588, 588, 588,
589, 589, 589, 589, 589,
590, 590, 590, 590, 590,
626, 626, 627, 629, 629,
630, 630, 630, 630, 630,
632, 632, 634, 635, 635,
636, 636
- format_coupling_2*, **566**, **625**,
used: 567, 626, 626, 627,
632, 633, 633, 634, 634,
635, 636
- format_coupling_mom*, **628**,
used: 628, 628, 629, 629
- format_flavor*, **664**, used: 664
- format_generation*, **267**, used:
267, 267
- format_maps*, **663**, used:
- format_momentum*, **572**, used:
580
- format_multiple_variable*, **572**,
used: 572, 573
- format_p*, **670**, **572**, used: 670,
572, 572, 595
- format_powers_of*, **605**, used:
605, 606
- format_powers_of_nc*, **612**, used:
612
- format_power_of*, **604**, used: 605
- format_power_of_nc*, **612**, used:
612
- Fortran* (module), **641**, **624**,
640, **563**, used: 618, 675,
??, 675, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??
- Fortran77* (module), **638**, **563**,
used:
- fortran95*, **570**, used: 570, 579,
608, 609, 609, 609, 610,
610, 610
- Fortran_Fermions* (module),
565, used: 624
- Fortran_Majorana* (module),
638, **563**, used: ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, 681
- Fortran_Majorana_Fermions*
(module), **624**, used:
638
- fortran_module* (type), **615**,
used:
- fortran_newline*, **571**, used: 571
- for_all*, **9**, **11**, **12**, **14**, **16**, **41**,
42, **43**, **44**, **111**, **6**, **37**,
40, used: 702, 16, 32, 43,
44, 46, 183, 184, 75, 77,
77, 78, 79, 205, 207, 214,
110, 111, 114
- four_gluon*, **235**, **678**, used: 235,
679
- FSet* (module), **217**, used: 217,
217, 217, 218, 218
- fspec_of_gen*, **383**, used: 395
- fspec_of_iso*, **383**, used: 395
- fspec_of_kk2*, **383**, used: 395
- fspec_of_kkmode*, **383**, used: 395
- Fudged*, **139**, used: 239, 257, 434,
484, 516, 275, 297, 318,
332, 344, 362, 373, 398,
414, ??
- Full*, **614**, used: 617, 622, 622,
623
- Full_Aliased*, **614**, used: 617

- functions_file*, **561**, used: **561**,
561
- fuse*, **766, 221, 223, 225, 556**,
206, 209, 98, 98, 99,
100, 110, 229, 230, 232,
235, 247, 255, 262, 269,
464, 499, 534, 289, 310,
325, 337, 350, 367, 377,
392, 407, 422, ??, ??,
679, 176, 764, 220, 94,
used: **556, 560, 206, 209**,
106, 112, 121, 125, 229,
232, 235, 247, 255, 262,
269, 464, 499, 534, 289,
310, 325, 337, 350, 367,
377, 392, 407, 422, ??, ??,
679
- fuse* (label), **226, 178**, used: **560**
- fuse2*, **11, 221, 222, 225, 556**,
206, 209, 229, 230, 232,
235, 247, 255, 262, 269,
464, 499, 534, 289, 310,
325, 337, 350, 367, 377,
392, 407, 422, ??, ??,
679, 176, 220, used: **11**,
15, 223, 223, 556, 560,
206, 206, 209, 229, 232,
235, 247, 255, 262, 269,
269, 464, 499, 534, 289,
310, 325, 337, 350, 367,
377, 392, 407, 422, ??, ??,
679
- fuse2* (type), **142**, used: **564, 142**
- fuse3*, **13, 221, 222, 225, 556**,
206, 209, 229, 230, 232,
235, 247, 255, 262, 269,
464, 499, 534, 289, 310,
325, 337, 350, 367, 377,
392, 407, 422, ??, ??,
679, 176, 220, used: **13**,
15, 223, 223, 556, 560,
206, 206, 209, 229, 232,
235, 247, 255, 262, 269,
269, 464, 499, 534, 289,
310, 325, 337, 350, 367,
377, 392, 407, 422, ??, ??,
679
- fuse3* (type), **142**, used: **564, 142**
- fusen*, **222**, used: **223, 223**
- fusen* (type), **142**, used: **142**
- fuse_c_wf*, **121**, used: **121, 121**
- fuse_list*, **206**, used: **206**
- fuse_n*, **17, 17**, used: **17**
- fuse_rhs*, **106**, used: **106, 110**
- fuse_trees*, **125**, used: **125**
- fusion* (type), **95, 102, 104, 123**,
129, 130, 90, 92, used:
95, 102, 102, 102, 105,
123, 129, 130, 130, 130,
90, 91, 93, 94
- Fusion* (module), **95, 89**, used:
661, 670, 670, 563, 569,
569, 675, ??, 675, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, 681, 181, 660, 669
- fusions*, **95, 102, 105, 123, 129**,
131, 91, 93, used: **123**,
133, 134, 596, 616, 620
- fusions* (field), **102, 105, 130**,
used: **105, 114, 124, 124**,
125, 131, 136
- Fusions* (module), **221, 220**,
used: **560, 228, 230, 232**,
234, 239, 254, 260, 267,
440, 488, 519, 279, 300,
320, 335, 347, 365, 376,
392, 402, 414, ??, ??, 678
- Fusions* (sig), **221, 220**, used:
221, 220
- fusion_dag*, **102, 105**, used:
- fusion_dag* (field), **102, 105**,
used: **105, 114, 119, 122**,
122, 124, 124, 125, 126
- fusion_tower*, **112**, used: **113**,
113
- fusion_tower* (field), **102, 105**,
used: **114, 119, 122, 126**
- fusion_tower'*, **112**, used: **112**,
112
- f_aux* (field), **557**, used: **557**,
558, 558
- f_aux_top* (type), **239, 414**,
used: **239, 414**
- f_color* (field), **557**, used: **557**,
558, 558, 560
- f_conjugate* (field), **557**, used:
557, 558, 558, 560

- f_fermion* (field), **557**, used: **557**,
558, 558, 560
f_mass (field), **557**, used: **557**,
558, 558, 560
f_name (field), **557**, used: **557**,
558, 558, 560
f_pdg (field), **557**, used: **557**,
558, 558, 560
f_propagator (field), **557**, used:
557, 558, 558, 560
f_spin (field), **557**, used: **557**,
558, 558, 560
f_symbol (field), **557**, used: **557**,
558, 558, 560
f_width (field), **557**, used: **557**,
558, 558, 560
g (type), **225, 556, 220**, used:
225, 220
G, **228, 239, 255, 266, 431**,
436, 482, 486, 512, 517,
273, 331, 341, 360, 372,
384, 397, 414, ??, ??,
676, used: **229, 229, 239**,
239, 239, 241, 241, 242,
242, 242, 242, 242, 243,
243, 243, 243, 244, 244,
244, 247, 255, 257, 259,
260, 260, 261, 262, 262,
266, 267, 273, 275, 279,
289, 331, 333, 335, 336,
336, 336, 336, 336, 337,
337, 338, 342, 344, 347,
348, 349, 349, 349, 349,
349, 350, 350, 360, 362,
365, 366, 366, 366, 366,
366, 367, 367, 367, 372,
373, 376, 376, 377, 377,
377, 377, 378, 384, 390,
391, 392, 393, 394, 397,
399, 402, 405, 405, 405,
406, 407, 407, 414, 414,
414, 415, 416, 416, 417,
417, 417, 417, 418, 418,
418, 418, 418, 419, 419,
419, 419, 420, 420, 420,
422, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??,
676, 678, 678, 678, 678,
678, 678, 679
G (module), **42, 43, 43, 44, 45**,
111, 40, used: **42, 44, 45**,
45, 45, 45, 45, 49, 49, 40,
41
G2, **233, 239, 259, 277, 298**,
319, 334, 347, 375, 400,
414, ??, ??, used: **235**,
239, 262, 282, 303, 323,
336, 349, 377, 405, 414,
??, ??
G22, **347**, used: **349**
G3, **229, 676**, used: **230, 230**,
678, 678
G4, **229, 676**, used: **230, 230**,
678, 678
G5_AWW, **239, 414**, used: **239**,
414
G5_ZWW, **239, 414**, used: **239**,
414
Ga, **239, 255, 432, 483, 514**,
273, 295, 317, 331, 341,
360, 372, 397, 414, ??,
??, used: **239, 241, 241**,
242, 242, 242, 243, 247,
256, 257, 260, 262, 433,
435, 440, 440, 440, 448,
448, 448, 449, 449, 449,
450, 450, 451, 452, 461,
462, 465, 483, 485, 488,
488, 488, 493, 493, 493,
494, 494, 495, 495, 495,
495, 496, 496, 499, 514,
516, 519, 519, 520, 527,
527, 527, 527, 527, 527,
528, 528, 528, 529, 529,
529, 530, 530, 531, 534,
273, 275, 279, 279, 281,
281, 282, 282, 284, 285,
288, 289, 289, 296, 297,
300, 301, 303, 303, 303,
303, 305, 306, 309, 310,
310, 317, 318, 321, 322,
323, 323, 323, 324, 325,
325, 331, 333, 335, 336,
336, 336, 337, 337, 338,
342, 344, 348, 348, 349,
349, 349, 350, 350, 361,
362, 365, 366, 366, 366,
367, 367, 367, 372, 373,
376, 376, 377, 377, 378,

- 397, 399, 402, 405, 405,
405, 406, 407, 407, 414,
415, 416, 416, 418, 418,
419, 422, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??
- gauge* (type), **225, 556, 186,**
209, 228, 229, 231, 233,
239, 254, 256, 266, 432,
483, 514, 273, 296, 317,
331, 342, 361, 372, 386,
397, 414, ??, ??, 676,
176, used: 556, 557, 186,
209, 266, 176, 177, 178,
220
- Gauge*, **210, 239, 255, 266, 273,**
331, 342, 360, 372, 397,
414, 563, 579, ??, ??,
179, 180, used: 671, 239,
256, 266, 273, 331, 342,
361, 372, 397, 414, 579,
??, ??
- Gauge* (module), **209, 185**, used:
- Gauge* (sig), **178**, used: 209, 265,
179, 179, 180, 185, 227,
228, 270, 271
- gauge4*, **235, 239, 262, 448,**
493, 527, 282, 303, 323,
336, 349, 366, 377, 391,
405, 414, ??, ??, 678,
used: 235, 239, 262, 448,
493, 527, 282, 282, 303,
303, 323, 336, 349, 366,
377, 391, 392, 405, 414,
??, ??, 678
- gauge_boson*, **210, 239, 255,**
266, 273, 331, 342, 360,
372, 397, 414, ??, ??,
179, used: 239, 256, 266,
273, 331, 342, 361, 372,
397, 414, ??, ??
- gauge_boson* (type), **210, 239,**
255, 266, 273, 331, 341,
360, 372, 397, 414, ??,
??, 179, used: 210, 210,
239, 255, 255, 266, 273,
273, 331, 331, 341, 342,
360, 360, 372, 372, 397,
397, 414, ??, ??, ??, ??,
- 179, 179, 179, 179, 180,
180
- Gauge_Gauge_Gauge*, **140**, used:
190, 235, 239, 262, 448,
493, 527, 281, 281, 303,
303, 323, 323, 336, 348,
366, 376, 391, 391, 391,
405, 414, ??, ??, 678
- gauge_higgs*, **241, 449, 494, 528,**
288, 309, 324, 337, 350,
367, 377, 405, 416, ??,
??, used: 246, 462, 498,
533, 289, 310, 325, 337,
350, 367, 377, 407, 422,
??, ??
- gauge_higgs4*, **241, 449, 495,**
529, 288, 309, 324, 337,
350, 367, 377, 406, 416,
??, ??, used: 247, 464,
499, 534, 289, 310, 325,
337, 350, 367, 377, 407,
422, ??, ??
- gauge_higgs4_GaGaCC*, **494,**
528, used: 495, 529
- gauge_higgs4_GaWPC*, **495,**
529, used: 495, 529
- gauge_higgs4_GaWSC*, **495,**
529, used: 495, 529
- gauge_higgs4_WWCC*, **494, 529,**
used: 495, 529
- gauge_higgs4_WWPP*, **494, 529,**
used: 495, 529
- gauge_higgs4_WWSS*, **494, 529,**
used: 495, 529
- gauge_higgs4_ZGaCC*, **494, 528,**
used: 495, 529
- gauge_higgs4_ZWPC*, **495, 529,**
used: 495, 529
- gauge_higgs4_ZWSC*, **494, 529,**
used: 495, 529
- gauge_higgs4_ZZCC*, **494, 528,**
used: 495, 529
- gauge_higgs4_ZZPP*, **494, 528,**
used: 495, 529
- gauge_higgs4_ZZSS*, **494, 528,**
used: 495, 529
- gauge_higgs_GaCC*, **493, 528,**
used: 494, 528
- gauge_higgs_GlGlP*, **493**, used:
494

- gauge_higgs_GlGls*, **493**, used: **494**
gauge_higgs_gold, **449**, used: **463**
gauge_higgs_gold4, **450**, used: **464**
gauge_higgs_WPC, **493, 528**, used: **494, 528**
gauge_higgs_WSC, **493, 528**, used: **494, 528**
gauge_higgs_WWS, **493, 528**, used: **494, 528**
gauge_higgs_ZCC, **493, 528**, used: **494, 528**
gauge_higgs_ZSP, **493, 528**, used: **494, 528**
gauge_higgs_ZZS, **493, 528**, used: **494, 528**
gauge_sfermion4, **450, 496, 530**, used: **464, 499, 534**
gauge_sfermion4', **450, 495, 529**, used: **450, 496, 530**
gauge_sfermion4'', **450, 495, 530**, used: **450, 496, 530**
gauge_squark4, **451, 496, 530**, used: **464, 499, 534**
gauge_squark4', **451, 496, 530**, used: **451, 496, 530**
gauge_squark4'', **451, 496, 530**, used: **451, 496, 530**
gauge_symbol, **225, 556, 190, 209, 229, 230, 232, 236, 239, 254, 256, 266, 432, 483, 514, 272, 273, 296, 317, 331, 342, 361, 372, 386, 397, 414, ??, ??, 681, 177**, used: **556, 190, 209, 266, 593**
gauge_symbol (label), **226, 178**, used: **560**
Gauss, **70, 75, 69**, used: **70, 76**
GAUSS, **??, ??**, used: **??, 71**
GAUSS (camlyacc token), **72**, used: **72**
Gauss_not, **70, 75, 69**, used: **70**
GaX, **255**, used: **256, 257, 260**
GBBG, **141**, used: **191, 461, 461, 462, 462, 462, 288, 310, 324**
GBG, **140**, used: **190, 447, 447, 448, 448, 448, 366, 367**
gcd, **782**, used: **782, 782, 783**
gen (type), **431, 482, 512**, used: **431, 482, 512**
Gen0, **383**, used: **384**
Gen1, **383**, used: **384**
Gen2, **383**, used: **384**
General_Flow (module), **87**, used:
generation, **239, 258, 439, 485, 333, 346, 363, 374, 400, 414, ??, ??**, used: **239, 259, 440, 486, 334, 347, 364, 375, 400, 414, ??, ??**
generation (type), **383**, used: **383, 387**
generation', **239, 258, 439, 485, 333, 345, 363, 374, 399, 414, ??, ??**, used: **239, 258, 439, 485, 333, 346, 363, 374, 400, 414, ??, ??**
generations, **267, 676**, used: **267, 267, 268, 268, 676, 676, 676, 676**
generations_pairs, **676**, used: **678**
generations_quadruples, **676**, used: **678, 678**
generations_triples, **676**, used: **678, 678, 678**
get_kk2, **388**, used: **390, 390, 391, 391, 391**
GF (module), **111**, used: **111**
GG, **431, 482, 512**, used:
ghh, **279**, used: **284**
ghost, **84, 84, 81**, used: **209**
Ghost, **84, 88**, used: **84, 85**
ghostspinors (field), **573**, used: **573, 574, 580**
ghost_flag, **85**, used: **85, 85, 85**
ghost_flags, **84, 85, 81**, used: **603, 604**
Gl, **233, 239, 255, 432, 483, 514, 273, 295, 317, 331, 341, 360, 372, 397, 414, ??, ??**, used: **233, 234, 234, 235, 235, 235, 239, 241, 242, 243, 247, 256, 257, 261, 262, 262, 262, 433, 435, 442, 447, 447, 448, 448, 448, 449, 451, 452, 452, 461, 462, 465,**

- 483, 485, 490, 493, 493,
493, 493, 493, 496, 496,
497, 499, 514, 516, 521,
524, 527, 527, 527, 527,
527, 527, 527, 530, 531,
531, 534, 273, 275, 279,
281, 282, 288, 289, 296,
297, 300, 303, 303, 309,
310, 317, 318, 321, 323,
323, 324, 325, 331, 333,
335, 336, 336, 336, 337,
338, 342, 344, 348, 348,
349, 349, 349, 350, 361,
362, 366, 367, 372, 373,
376, 376, 377, 378, 397,
399, 402, 405, 405, 407,
414, 416, 418, 419, 422,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??
- global_verb*ose, ??, used: ??, ??,
??, ??
- Gluino*, **432, 483, 514**, used:
433, 435, 442, 445, 448,
462, 465, 483, 485, 490,
492, 499, 514, 516, 521,
523, 526, 534
- gluon2_lq2*, **527**, used: 534
- gluon2_lq2'*, **527**, used: 527
- gluon2_phi*, **678**, used: 678
- gluon2_squark2*, **452, 497, 531**,
used: 464, 499, 534
- gluon2_squark2'*, **497, 531**, used:
497, 531
- gluon3_phi*, **679**, used: 679
- gluon4*, **448**, used:
- gluon_gauge_squark*, **452, 497**,
531, used: 464, 499, 534
- gluon_gauge_squark'*, **452, 496**,
531, used: 452, 497, 531
- gluon_gauge_squark''*, **452, 496**,
531, used: 452, 497, 531
- gluon_w_squark*, **451, 496, 530**,
used: 464, 499, 534
- gluon_w_squark'*, **451, 496, 530**,
used: 451, 496, 530
- gluon_w_squark''*, **451, 496**,
530, used: 451, 496, 530
- Gl_K1*, **341**, used: 342, 344, 348,
349, 350
- Gl_K2*, **341**, used: 342, 344, 348,
349, 350
- gobble_arrows*, **554**, used: 555
- gobble_white*, **554**, used: 554,
554, 555
- goldstone*, **225, 556, 187, 209**,
228, 229, 231, 234, 239,
254, 257, 267, 435, 485,
516, 275, 297, 318, 332,
344, 362, 373, 393, 398,
414, ??, ??, 677, 177,
179, used: 556, 187, 209,
106, 113, 254, 267, 595
- goldstone* (label), **226, 178**, used:
560
- goldstone* (type), **179**, used: 179,
179
- Goldstone*, **179**, used:
- goldstone4*, **454**, used: 464
- goldstone_charg_neutr*, **444**,
used: 463
- goldstone_neutr*, **444**, used: 463
- goldstone_neutr'*, **444**, used: 444
- goldstone_neutr''*, **444**, used: 444
- goldstone_sfermion*, **455**, used:
463
- goldstone_sfermion'*, **455**, used:
455
- goldstone_sfermion''*, **455**, used:
455
- goldstone_sfermion'''*, **455**, used:
455
- goldstone_squark*, **456**, used: 463
- goldstone_squark'*, **456**, used:
456
- goldstone_squark_a*, **456**, used:
456
- goldstone_squark_b*, **456**, used:
456
- goldstone_vertices*, **242, 289**,
310, 325, 337, 350, 367,
377, 407, 416, ??, ??,
used: 246, 289, 310, 325,
337, 350, 367, 377, 407,
422, ??, ??
- graded* (type), **9, 11, 13, 15, 17**,
7, used: 9, 7
- Graded* (module), **49, 41**, used:
111
- Graded* (sig), **49, 41**, used: 41

- Graded_Forest* (sig), **42, 40**,
used: **43, 45, 49, 40, 41**
- Graded_Map* (module), **45**, used:
49
- Graded_Map* (sig), **44**, used: **44**,
45, 49
- Graded_Map_Maker* (sig), **44**,
used: **45**
- Graded_Ord* (sig), **42, 40**, used:
42, 42, 44, 45, 49, 40, 40
- graded_sym_power*, **9, 11, 13**,
15, 17, 7, used:
- graded_sym_power_fold*, **9, 11**,
13, 15, 17, 7, used: **11**,
13, 15, 17, 112
- Grader* (sig), **42, 40**, used: **43**,
44, 40, 40
- Grade_Forest* (module), **44, 41**,
used: **49**
- graph* (type), **772, 765**, used:
773, 765, 765
- graph_of_tree*, **772, 765**, used:
- Grav*, **331, 341, 140**, used: **447**,
447, 448, 448, 461, 461,
462, 331, 333, 335, 336,
337, 338, 342, 344, 348,
349, 349, 350, 366
- Gravbar*, **140**, used: **447, 447**,
448, 448, 448, 461, 461,
462, 462, 462, 366, 367
- gravitino*, **429, 430, 430, 430**,
430, 430, 430, 429,
used: **433, 463, 464**
- gravitino_coup*, **366**, used: **367**
- gravitino_gauge*, **367**, used: **367**
- gravitino_gaugino_3*, **448**, used:
448
- Graviton_Scalar_Scalar*, **140**,
used: **190, 337, 349**
- Graviton_Spinor_Spinor*, **140**,
used: **190, 335, 348**
- Graviton_Vector_Vector*, **140**,
used: **190, 336, 349**
- gravity_currents*, **335, 348**, used:
337, 350
- gravity_gauge*, **336, 349**, used:
337, 350
- gravity_higgs*, **337, 349**, used:
337, 350
- GravTest* (module), **360, 270**,
used: **??**
- grav_gauss*, **564, 566, 625**, used:
- grav_incoming*, **564, 565, 625**,
used: **597, 597**
- grav_outgoing*, **564, 565, 625**,
used:
- grav_projector*, **564, 565, 625**,
used:
- grav_propagator*, **564, 565, 625**,
used:
- grav_type*, **564, 565, 624**, used:
580
- Grino*, **432, 360**, used: **433, 435**,
447, 447, 448, 448, 448,
461, 461, 462, 462, 462,
465, 361, 362, 366, 367,
367
- Groves* (module), **265, 228**, used:
270
- grow*, **112**, used: **112**
- Gs*, **233, 239, 259, 436, 486**,
517, 277, 298, 319, 334,
347, 375, 400, 414, ??,
??, used: **234, 235, 239**,
261, 442, 447, 447, 490,
493, 493, 521, 524, 527,
527, 527, 279, 300, 321,
335, 348, 376, 402, 414,
??, ??
- G_AASF*, **436**, used: **456**
- G_aaww*, **387**, used: **388, 391**
- G_AAWW*, **239, 277, 298, 319**,
334, 347, 364, 375, 400,
414, ??, ??, used: **239**,
282, 282, 285, 303, 303,
306, 323, 336, 349, 366,
377, 405, 414, ??, ??
- G_AG0SFSF*, **436**, used: **457**,
458
- G_AGSNSL*, **436**, used: **457**
- G_AGSUSD*, **436**, used: **458**
- G_AHpHm*, **400**, used: **405**
- G_AHPsip*, **277, 298**, used: **284**,
305
- G_AHTHT*, **277, 298**, used:
279, 301
- G_AHTHTH*, **277, 298**, used:
279, 301

- G_AHTT*, **277, 298**, used: **279, 301**
G_ASFSF, **436**, used: **454**
G_auw, **387**, used: **388, 391**
G_AZWW, **239, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: **239, 282, 282, 303, 303, 323, 336, 349, 366, 377, 405, 414, ??, ??**
G_a-lep, **387**, used: **388, 389**
g_a-quark, **388**, used: **388**
G_a-quark, **387**, used: **388, 389**
G_CAC, **436**, used: **443**
G_CC, **239, 259, 436, 486, 517, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: **239, 260, 261, 261, 441, 489, 520, 280, 301, 302, 321, 322, 324, 335, 348, 365, 376, 403, 414, ??, ??**
G_CCQ, **239, 259, 436, 486, 517, 334, 347, 364, 414**, used: **239, 261, 441, 489, 520, 414**
G_CCTop, **277, 298**, used: **279, 301**
G_CC-heavy, **277, 298**, used: **280, 301**
G_CC-W, **277, 298**, used: **279, 301**
G_CC-WH, **277, 298**, used: **279, 301**
G_CGC, **436**, used: **443**
G_CGN, **436**, used: **444**
G_CH1C, **436**, used: **443**
G_CH2C, **436**, used: **443**
G_CHN, **436**, used: **444**
G_CICIA, **436**, used: **444**
G_CICIG, **436**, used: **444**
G_CICIH1, **436**, used: **444**
G_CICIH2, **436**, used: **444**
G_CICIP, **486, 517**, used: **491, 522**
G_CICIS, **486, 517**, used: **491, 522**
G_CPC, **486, 517**, used: **491, 522**
G_CSC, **486, 517**, used: **491, 522**
G_CWN, **436, 486, 517**, used: **441, 489, 520**
G_CZC, **436, 486, 517**, used: **442, 490, 521**
G_Ebb, **277, 298, 319**, used: **281, 302, 323**
G_EGaGa, **277, 298, 319**, used: **288, 309, 324**
G_EGaZ, **277, 298, 319**, used: **288, 309, 324**
G_EGIGl, **277, 298, 319**, used: **288, 309, 324**
G_Etht, **277, 298, 319**, used: **281, 302, 323**
G_Ethth, **277, 298, 319**, used: **281, 302, 323**
G_Ett, **277, 298, 319**, used: **281, 302, 323**
G_FWW, **414**, used: **417**
G_FZZ, **414**, used: **417**
G_G0G0SFSF, **436**, used: **457, 458**
G_GG4, **436**, used: **454**
G_GGSFSF, **436**, used: **457, 458**
G_GGSNSL, **436**, used: **457**
G_GGSUSD, **436**, used: **458**
G_GH, **436**, used: **449, 449**
G_GH4, **436**, used: **449**
G_GH4_GaGaCC, **486, 517**, used: **494, 528**
G_GH4_GaWPC, **486, 517**, used: **495, 529**
G_GH4_GaWSC, **486, 517**, used: **495, 529**
G_GH4_WWCC, **486, 517**, used: **494, 529**
G_GH4_WWPP, **486, 517**, used: **494, 529**
G_GH4_WWSS, **486, 517**, used: **494, 529**
G_GH4_ZGaCC, **486, 517**, used: **494, 528**
G_GH4_ZWPC, **486, 517**, used: **495, 529**
G_GH4_ZWSC, **486, 517**, used: **494, 529**
G_GH4_ZZCC, **486, 517**, used: **494, 528**

- G_GH4_ZZPP*, **486, 517**, used: 494, 528
G_GH4_ZZSS, **486, 517**, used: 494, 528
G_GHGo, **436**, used: 449
G_GHGo4, **436**, used: 450
G_GH_GaCC, **486, 517**, used: 493, 528
G_GH_WPC, **486, 517**, used: 493, 528
G_GH_WSC, **486, 517**, used: 493, 528
G_GH_WWS, **486, 517**, used: 493, 528
G_GH_ZCC, **486, 517**, used: 493, 528
G_GH_ZSP, **486, 517**, used: 493, 528
G_GH_ZZS, **486, 517**, used: 493, 528
G_GLGLA, **436**, used: 449
G_GLGLH, **436**, used: 449
G_GLGLHH, **436**, used: 449
G_GLGLQLQ, **517**, used: 527
G_GLISQSQ, **436, 486, 517**, used: 452, 497, 531
G_GIPSQSQ, **436, 486, 517**, used: 452, 496, 531
G_GLUGLUA0, **486**, used: 493
G_GLUGLUH0, **486**, used: 493
G_GIWSUSD, **436, 486, 517**, used: 451, 496, 530
G_GLZSFsf, **436, 486, 517**, used: 452, 496, 531
G_GoSFSF, **436**, used: 455
G_GoSNsL, **436**, used: 455
G_Gr4A_Sd, **436**, used: 461
G_Gr4A_Sdc, **436**, used: 461
G_Gr4A_Sl, **436**, used: 461
G_Gr4A_Slc, **436**, used: 461
G_Gr4A_Su, **436**, used: 461
G_Gr4A_Suc, **436**, used: 461
G_Gr4Gl_Sd, **436**, used: 461
G_Gr4Gl_Sdc, **436**, used: 461
G_Gr4Gl_Su, **436**, used: 461
G_Gr4Gl_Suc, **436**, used: 461
G_Gr4W_Sd, **436**, used: 461
G_Gr4W_Sdc, **436**, used: 461
G_Gr4W_Sl, **436**, used: 461
G_Gr4W_Slc, **436**, used: 461
G_Gr4W_Sn, **436**, used: 461
G_Gr4W_Snc, **436**, used: 461
G_Gr4W_Su, **436**, used: 461
G_Gr4W_Suc, **436**, used: 461
G_Gr4Z_Sd, **436**, used: 461
G_Gr4Z_Sdc, **436**, used: 461
G_Gr4Z_Sl, **436**, used: 461
G_Gr4Z_Slc, **436**, used: 461
G_Gr4Z_Sn, **436**, used: 461
G_Gr4Z_Snc, **436**, used: 461
G_Gr4Z_Su, **436**, used: 461
G_Gr4Z_Suc, **436**, used: 461
G_Gr4_A_Ch, **436**, used: 462
G_Gr4_H_A, **436**, used: 462
G_Gr4_H_Z, **436**, used: 462
G_Gr4_Neu, **436**, used: 462
G_Gr4_W_H, **436**, used: 462
G_Gr4_W_Hc, **436**, used: 462
G_Gr4_Z_Ch, **436**, used: 462
G_Gr4_Z_H1, **436**, used: 462
G_Gr4_Z_H2, **436**, used: 462
G_Gr4_Z_H3, **436**, used: 462
G_Grav, **436, 334, 347, 364**, used: 448, 335, 336, 337, 348, 349, 349, 366, 367
G_GravGl, **436**, used: 462
G_Grav_D, **436**, used: 447
G_Grav_Dc, **436**, used: 447
G_Grav_L, **436**, used: 447
G_Grav_Lc, **436**, used: 447
G_Grav_N, **436**, used: 447
G_Grav_U, **436**, used: 447
G_Grav_Uc, **436**, used: 447
G_Gr_A_Neu, **436**, used: 448
G_Gr_Ch, **436**, used: 448
G_Gr_H1_Neu, **436**, used: 448
G_Gr_H2_Neu, **436**, used: 448
G_Gr_H3_Neu, **436**, used: 448
G_Gr_H_Ch, **436**, used: 448
G_Gr_Z_Neu, **436**, used: 448
G_GSUSD, **436**, used: 456
G_h111, **400**, used: 406
G_h1111, **400**, used: 407
G_h1112, **400**, used: 407
G_h1113, **400**, used: 407
G_h112, **400**, used: 406
G_h1122, **400**, used: 407
G_h1123, **400**, used: 407
G_h113, **400**, used: 406
G_h1133, **400**, used: 407

G_h1222, 400, used: 407
G_h1223, 400, used: 407
G_h123, 400, used: 406
G_h1233, 400, used: 407
G_h1333, 400, used: 407
G_h1bb, 400, used: 403
G_h1bd, 400, used:
G_h1bs, 400, used:
G_h1cc, 400, used: 403
G_h1ct, 400, used: 404
G_h1cu, 400, used: 404
G_h1db, 400, used: 404
G_h1dd, 400, used: 403
G_h1ds, 400, used: 404
G_h1e1e1, 400, used: 403
G_h1e1e2, 400, used: 404
G_h1e1e3, 400, used: 404
G_h1e2e1, 400, used: 404
G_h1e2e2, 400, used: 403
G_h1e2e3, 400, used: 404
G_h1e3e1, 400, used: 404
G_h1e3e2, 400, used: 404
G_h1e3e3, 400, used: 403
G_H1GSNSL, 436, used: 457
G_H1GSUSD, 436, used: 458
G_H1H1SFSS, 436, used: 456,
456
G_H1H2SFSS, 436, used: 456,
456
G_h1HpAWm, 400, used: 406
G_h1HpAWmC, 400, used: 406
G_h1HpHm, 400, used: 406
G_h1HpZWm, 400, used: 406
G_h1HpZWmC, 400, used: 406
G_h1sb, 400, used: 404
G_h1sd, 400, used: 404
G_H1SFSS, 436, used: 454, 454
G_h1ss, 400, used: 403
G_h1tc, 400, used: 404
G_h1tt, 400, used: 403
G_h1tu, 400, used: 404
G_h1uc, 400, used: 404
G_h1ut, 400, used: 404
G_h1uu, 400, used: 403
G_h1WpWm, 400, used: 405
G_h1ZZ, 400, used: 405
G_h221, 400, used: 406
G_h222, 400, used: 406
G_h2222, 400, used: 407
G_h2223, 400, used: 407
G_h223, 400, used: 406
G_h2233, 400, used: 407
G_h2333, 400, used: 407
G_h2bb, 400, used: 403
G_h2bd, 400, used:
G_h2bs, 400, used:
G_h2cc, 400, used: 403
G_h2ct, 400, used: 404
G_h2cu, 400, used: 404
G_h2db, 400, used: 404
G_h2dd, 400, used: 403
G_h2ds, 400, used: 404
G_h2e1e1, 400, used: 403
G_h2e1e2, 400, used: 404
G_h2e1e3, 400, used: 404
G_h2e2e1, 400, used: 404
G_h2e2e2, 400, used: 403
G_h2e2e3, 400, used: 404
G_h2e3e1, 400, used: 404
G_h2e3e2, 400, used: 404
G_h2e3e3, 400, used: 403
G_H2GSNSL, 436, used: 457
G_H2GSUSD, 436, used: 458
G_H2H2SFSS, 436, used: 456,
456
G_h2HpAWm, 400, used: 406
G_h2HpAWmC, 400, used: 406
G_h2HpHm, 400, used: 406
G_h2HpZWm, 400, used: 406
G_h2HpZWmC, 400, used: 406
G_h2sb, 400, used: 404
G_h2sd, 400, used: 404
G_H2SFSS, 436, used: 454, 454
G_h2ss, 400, used: 403
G_h2tc, 400, used: 404
G_h2tt, 400, used: 403
G_h2tu, 400, used: 404
G_h2uc, 400, used: 404
G_h2ut, 400, used: 404
G_h2uu, 400, used: 403
G_h2WpWm, 400, used: 405
G_h2ZZ, 400, used: 405
G_H3, 239, 436, 277, 298, 319,
334, 347, 364, 375, 414,
??, ??, used: 239, 452,
452, 288, 309, 324, 336,
349, 366, 377, 414, ??, ??
G_h331, 400, used: 406
G_h332, 400, used: 406
G_h333, 400, used: 406

- G_h3333*, **400**, used: **407**
G_h3bb, **400**, used: **403**
G_h3bd, **400**, used:
G_h3bs, **400**, used:
G_h3cc, **400**, used: **403**
G_h3ct, **400**, used: **404**
G_h3cu, **400**, used: **404**
G_h3db, **400**, used: **404**
G_h3dd, **400**, used: **403**
G_h3ds, **400**, used: **404**
G_h3e1e1, **400**, used: **403**
G_h3e1e2, **400**, used: **404**
G_h3e1e3, **400**, used: **404**
G_h3e2e1, **400**, used: **404**
G_h3e2e2, **400**, used: **403**
G_h3e2e3, **400**, used: **404**
G_h3e3e1, **400**, used: **404**
G_h3e3e2, **400**, used: **404**
G_h3e3e3, **400**, used: **403**
G_h3HpAWm, **400**, used: **406**
G_h3HpAWmC, **400**, used: **406**
G_h3HpHm, **400**, used: **406**
G_h3HpZWm, **400**, used: **406**
G_h3HpZWmC, **400**, used: **406**
G_h3sb, **400**, used:
G_h3sd, **400**, used: **404**
G_h3ss, **400**, used: **403**
G_h3tc, **400**, used: **404**
G_h3tt, **400**, used: **403**
G_h3tu, **400**, used: **404**
G_h3uc, **400**, used: **404**
G_h3ut, **400**, used: **404**
G_h3uu, **400**, used: **403**
G_h3WpWm, **400**, used: **405**
G_h3ZZ, **400**, used: **405**
G_H3_SCC, **486**, **517**, used:
497, **531**
G_H3_SPP, **486**, **517**, used:
497, **531**
G_H3_SSS, **486**, **517**, used: **497**,
531
G_H4, **239**, **436**, **277**, **298**, **319**,
334, **347**, **364**, **375**, **414**,
??, **??**, used: **239**, **453**,
453, **288**, **309**, **324**, **336**,
349, **366**, **377**, **414**, **??**, **??**
G_HAHAH, **277**, **298**, used:
283, **304**
G_HAHZ, **277**, **298**, used: **283**,
304
G_HASLSN, **436**, used: **456**
G_HASUSD, **436**, used: **457**
G_hbb, **400**, used:
G_Hbb, **239**, **259**, **277**, **298**,
319, **334**, **347**, **364**, **375**,
400, **414**, **??**, **??**, used:
239, **261**, **280**, **302**, **323**,
336, **348**, **365**, **376**, **414**,
??, **??**
G_hbc, **400**, used:
G_hbt, **400**, used: **403**
G_hbu, **400**, used:
G_hcb, **400**, used:
G_hcc, **400**, used:
G_Hcc, **239**, **259**, **277**, **298**,
319, **334**, **347**, **364**, **375**,
400, **414**, **??**, **??**, used:
239, **261**, **280**, **302**, **323**,
336, **348**, **365**, **376**, **414**,
??, **??**
G_hcd, **400**, used:
G_hcs, **400**, used: **403**
G_Hcs, **400**, used:
G_hdc, **400**, used:
G_hdt, **400**, used:
G_hdu, **400**, used: **403**
G_he1n1, **400**, used:
G_he1n2, **400**, used:
G_he1n3, **400**, used:
G_he2n1, **400**, used:
G_he2n2, **400**, used:
G_he2n3, **400**, used:
G_he3n1, **400**, used:
G_he3n2, **400**, used:
G_he3n3, **400**, used:
G_heavy_HVV, **319**, used: **324**
G_heavy_HWW, **319**, used: **324**
G_heavy_HZZ, **319**, used:
G_HGaGa, **239**, **277**, **298**, **319**,
334, **347**, **364**, **375**, **414**,
used: **241**, **337**, **349**, **366**,
416
G_HGaGa_anom, **239**, **414**,
used: **241**, **415**
G_HGaZ, **239**, **277**, **298**, **319**,
334, **347**, **364**, **375**, **414**,
used: **241**, **337**, **349**, **366**,
416
G_HGaZ_anom, **239**, **414**, used:
241, **415**

- G_HGaZ_u*, **239, 414**, used:
 241, 415
G_Hgg, **239, 319, 334, 347**,
 364, 375, 414, used: **241**,
 337, 349, 366, 416
G_HGo3, **436**, used: **452**
G_HGo4, **436**, used: **453**
G_HGSFSF, **436**, used: **457, 458**
G_HGSNSL, **436**, used: **457**
G_HGSUSD, **436**, used: **458**
G_HH1SLN, **436**, used: **456**
G_HH1SUSD, **436**, used: **457**
G_HH2SLN, **436**, used: **456**
G_HH2SUSD, **436**, used: **457**
G_HHAA, **277, 298**, used: **285**,
 306
G_HHAHZ, **277, 298**, used: **285**,
 306
G_HHSFSF, **436**, used: **456, 456**
G_HHtht, **277, 298**, used: **288**,
 310
G_HHthth, **277, 298, 319**, used:
 288, 310, 324
G_HHtt, **277, 298**, used: **288**,
 310
G_HHWHW, **277, 298**, used:
 285, 306
G_hhWpWm, **400**, used: **406**
G_HHWW, **239, 277, 298, 319**,
 334, 347, 364, 375, 414,
 ??, ??, used: **239, 285**,
 285, 306, 306, 324, 324,
 336, 349, 366, 377, 414,
 ??, ??
G_HHZHAA, **277, 298**, used:
 285, 306
G_HHZHZ, **277, 298**, used: **285**,
 306
G_hhZZ, **400**, used: **406**
G_HHZZ, **239, 277, 298, 319**,
 334, 347, 364, 375, 414,
 ??, ??, used: **239, 285**,
 285, 306, 306, 324, 324,
 336, 349, 366, 377, 414,
 ??, ??
G_HHZZH, **319**, used: **324**
G_Hmm, **239, 259, 375, 414**,
 used: **239, 261, 376, 414**
G_hmumu, **400**, used:
G_Hmumu, **400**, used:
G_Hmunu, **400**, used:
G_hn1e1, **400**, used:
G_hn1e2, **400**, used:
G_hn1e3, **400**, used:
G_hn2e1, **400**, used:
G_hn2e2, **400**, used:
G_hn2e3, **400**, used:
G_hn3e1, **400**, used:
G_hn3e2, **400**, used:
G_hn3e3, **400**, used:
G_HpHm11, **400**, used: **407**
G_HpHm12, **400**, used: **407**
G_HpHm13, **400**, used: **407**
G_HpHm22, **400**, used: **407**
G_HpHm23, **400**, used: **407**
G_HpHm33, **400**, used: **407**
G_HpHmAA, **400**, used: **406**
G_HpHmAZ, **400**, used: **406**
G_HpHmHpHm, **400**, used: **407**
G_HpHmWpWm, **400**, used: **406**
G_HpHmZZ, **400**, used: **406**
G_HPsi0AHAH, **277, 298**, used:
 285, 306
G_HPsi0WHW, **277, 298**, used:
 285, 306
G_HPsi0WW, **277, 298**, used:
 285, 306
G_HPsi0ZAH, **277, 298**, used:
 285, 306
G_HPsi0ZHAH, **277, 298**, used:
 285, 306
G_HPsi0ZHZ, **277, 298**, used:
 285, 306
G_HPsi0ZHZH, **277, 298**, used:
 285, 306
G_HPsi0ZZ, **277, 298**, used:
 285, 306
G_HPsippWHW, **277, 298**,
 used: **285, 306**
G_HPsippWHWH, **277, 298**,
 used: **285, 306**
G_HPsippWW, **277, 298**, used:
 285, 306
G_HPsipWA, **277, 298**, used:
 285, 306
G_HPsipWAH, **277, 298**, used:
 285, 306
G_HPsipWHA, **277, 298**, used:
 285, 306

- G_HPsipWHAH*, **277, 298**,
 used: **285, 306**
G_HPsipWHZ, **277, 298**, used:
285, 306
G_HPsipWHZH, **277, 298**, used:
285, 306
G_HPsipWZ, **277, 298**, used:
285, 306
G_HPsipWZH, **277, 298**, used:
285, 306
G_Hqh, **319**, used: **323**
G_hsc, **400**, used: **403**
G_HSF31, **436**, used:
G_HSF32, **436**, used:
G_HSF41, **436**, used:
G_HSF42, **436**, used:
G_HSNSL, **436, 486, 517**, used:
454, 497, 532
G_hst, **400**, used:
G_hsu, **400**, used:
G_HSUSD, **436, 486, 517**, used:
455, 498, 532
G_Htaunu, **400**, used:
G_htautau, **400**, used:
G_Htautau, **239, 259, 277, 298,**
319, 334, 347, 364, 375,
400, 414, ??, ??, used:
239, 261, 280, 302, 323,
336, 348, 365, 376, 414,
??, ??
G_htb, **400**, used: **403**
G_Htb, **400**, used:
G_htd, **400**, used:
G_Htht, **277, 298, 319**, used:
281, 302, 323
G_Hthth, **277, 298, 319**, used:
281, 302
G_hths, **400**, used:
G_htht, **400**, used:
G_Htt, **239, 259, 277, 298, 319,**
334, 347, 364, 375, 400,
414, ??, ??, used: **239,**
261, 280, 302, 323, 336,
348, 365, 376, 414, ??, ??
G_hub, **400**, used:
G_hud, **400**, used: **403**
G_hus, **400**, used:
G_HWWH, **277, 298**, used: **283,**
304
G_HWWH, **277, 298**, used:
283, 304
G_HWW, **239, 277, 298, 319,**
334, 347, 364, 375, 414,
??, ??, used: **239, 283,**
304, 324, 336, 349, 366,
377, 414, ??, ??
G_HWW_anom, **239, 414**, used:
241, 415
G_HWW_u, **239, 414**, used:
241, 415
G_HZHAH, **277, 298**, used: **283,**
304
G_HZHZ, **277, 298**, used: **283,**
304
G_HZZ, **239, 277, 298, 319,**
334, 347, 364, 375, 414,
??, ??, used: **239, 283,**
304, 324, 336, 349, 366,
377, 414, ??, ??
G_HZZ_anom, **239, 414**, used:
241, 415
G_HZZ_u, **239, 414**, used: **241,**
415
G_LQ_EC_UC, **517**, used: **524,**
524, 525, 525, 525, 525,
525, 525, 525, 525, 525,
525
G_LQ_GG, **517**, used: **526**
G_LQ_NEU, **517**, used: **526,**
526
G_LQ_P, **517**, used: **526**
G_LQ_S, **517**, used: **526**
G_LQ_SSD, **517**, used: **526**
G_LQ_SSU, **517**, used: **525**
G_NCHt, **319**, used: **321**
G_NCH_D, **319**, used: **322**
G_NCH_N, **319**, used: **322**
G_NCH_U, **319**, used: **322**
G_NC_down, **239, 259, 436,**
486, 517, 277, 298, 319,
334, 347, 364, 375, 400,
414, ??, ??, used: **239,**
260, 261, 441, 488, 520,
279, 300, 321, 335, 348,
365, 376, 402, 414, ??, ??
G_NC_H, **319**, used: **321**
G_NC_heavy, **277, 298**, used:
279, 301
G_NC_h_bot, **319**, used: **322**

- G_NC_h_down*, **277, 298, 319**,
 ??, used: **279, 301, 322**,
 ??
G_NC_h_lepton, **277, 298, 319**,
 ??, used: **279, 301, 322**,
 ??
G_NC_h_neutrino, **277, 298**,
319, ??, used: **279, 301**,
322, ??
G_NC_h_top, **319**, used: **322**
G_NC_h_up, **277, 298, 319**, ??,
 used: **280, 302, 322**, ??
G_NC_lepton, **239, 259, 436**,
486, 517, 277, 298, 319,
334, 347, 364, 375, 400,
414, ??, ??, used: **239**,
260, 261, 441, 488, 520,
279, 300, 321, 335, 348,
365, 376, 402, 414, ??, ??
G_NC_neutrino, **239, 259, 436**,
486, 517, 277, 298, 319,
334, 347, 364, 375, 400,
414, ??, ??, used: **239**,
260, 261, 441, 488, 520,
279, 300, 321, 335, 348,
365, 376, 402, 414, ??, ??
G_NC_top, ??, used: ??
G_NC_up, **239, 259, 436, 486**,
517, 277, 298, 319, 334,
347, 364, 375, 400, 414,
 ??, ??, used: **239, 260**,
261, 441, 488, 520, 279,
300, 321, 335, 348, 365,
376, 402, 414, ??, ??
G_NC_X, **319**, used: **321**
G_NC_X_t, **319**, used: **321**
G_NC_Y, **319**, used: **321**
G_NC_Y_t, **319**, used: **321**
G_NGC, **436**, used: **444**
G_NHC, **436, 486, 517**, used:
444, 491, 522
G_NLQC, **517**, used: **527**
G_NWC, **436, 486, 517**, used:
441, 489, 520
G_NZN, **436, 486, 517**, used:
442, 490, 521
g_over_2_coth, **239, 260, 414**,
 used: **239, 260, 414**
G_PGILQLQ, **517**, used: **527**
G_PNWW, **414**, used: **417**
G_PNZZ, **414**, used: **417**
G_PPA, **436**, used: **449**
G_PPH, **436**, used: **449**
G_PPHH, **436**, used: **449**
G_PPLQLQ, **517**, used: **527**
G_PPSFSF, **436, 486, 517**,
 used: **450, 495, 530**
G_PPWW, **436, 486, 517**, used:
448, 493, 527
G_Psi00AH, **277, 298**, used:
285, 306
G_Psi00ZH, **277, 298**, used:
285, 306
G_Psi00ZHAH, **277, 298**, used:
285, 306
G_Psi01AH, **277, 298**, used:
284, 305
G_Psi01Z, **277, 298**, used: **284**,
305
G_Psi01ZH, **277, 298**, used:
284, 305
G_Psi0bb, **277, 298**, used: **281**,
302
G_Psi0cc, **277, 298**, used: **281**,
302
G_Psi0ppWHW, **277, 298**, used:
285, 306
G_Psi0ppWHWH, **277, 298**,
 used: **285, 306**
G_Psi0ppWW, **277, 298**, used:
285, 306
G_Psi0pWA, **277, 298**, used:
285, 306
G_Psi0pWAH, **277, 298**, used:
285, 306
G_Psi0pWHA, **277, 298**, used:
285, 306
G_Psi0pWHAH, **277, 298**, used:
285, 306
G_Psi0pWHZ, **277, 298**, used:
285, 306
G_Psi0pWHZH, **277, 298**, used:
285, 306
G_Psi0pWZ, **277, 298**, used:
285, 306
G_Psi0pWZH, **277, 298**, used:
285, 306
G_Psi0tautau, **277, 298**, used:
281, 302

- G_Psi0tt*, **277, 298**, used: **281, 302**
G_Psi0tth, **277, 298**, used: **281, 302**
G_Psi0W, **277, 298**, used: **284, 305**
G_Psi0WH, **277, 298**, used: **284, 305**
G_Psi1bb, **277, 298**, used: **281, 302**
G_Psi1cc, **277, 298**, used: **281, 302**
G_Psi1HAH, **277, 298**, used: **284, 305**
G_Psi1HZ, **277, 298**, used: **284, 305**
G_Psi1HZZ, **277, 298**, used: **284, 305**
G_Psi1tautau, **277, 298**, used: **281, 302**
G_Psi1tt, **277, 298**, used: **281, 302**
G_Psi1tth, **277, 298**, used: **281, 302**
G_Psi1W, **277, 298**, used: **284, 305**
G_Psi1WH, **277, 298**, used: **284, 305**
G_PsiAAH, **277, 298**, used: **283, 305**
G_PsiAHW, **277, 298**, used: **283, 305**
G_PsiAHHW, **277, 298**, used: **283, 305**
G_PsicAAH, **277, 298**, used: **285, 306**
G_PsicAZ, **277, 298**, used: **285, 306**
G_PsicAZH, **277, 298**, used: **285, 306**
G_PsicZAH, **277, 298**, used: **285, 306**
G_PsicZZ, **277, 298**, used: **285, 306**
G_PsicZZH, **277, 298**, used: **285, 306**
G_PsiHW, **277, 298**, used: **284, 305**
G_PsiHWH, **277, 298**, used: **284, 305**
G_Psipbth, **277, 298**, used: **281, 302**
G_Psipl3, **277, 298**, used: **281, 302**
G_PsippAAH, **277, 298**, used: **285, 306**
G_PsippAZ, **277, 298**, used: **285, 306**
G_PsiPPW, **277, 298**, used: **284, 305**
G_PsippWA, **277, 298**, used: **285, 306**
G_PsippWAH, **277, 298**, used: **285, 306**
G_PsiPPWH, **277, 298**, used: **284, 305**
G_PsippWHA, **277, 298**, used: **285, 306**
G_PsippWHAH, **277, 298**, used: **285, 306**
G_PsippWHW, **277, 298**, used: **283, 305**
G_PsippWHWH, **277, 298**, used: **283, 305**
G_PsippWHZ, **277, 298**, used: **285, 306**
G_PsippWHZH, **277, 298**, used: **285, 306**
G_PsippWW, **277, 298**, used: **283, 305**
G_PsippWZ, **277, 298**, used: **285, 306**
G_PsippWZH, **277, 298**, used: **285, 306**
G_PsippZAH, **277, 298**, used: **285, 306**
G_PsippZHZZ, **277, 298**, used: **285, 306**
G_PsippZZ, **277, 298**, used: **285, 306**
G_Psiqq2, **277, 298**, used: **281, 302**
G_Psiqq3, **277, 298**, used: **281, 302**
G_PsiWHW, **277, 298**, used: **283, 305**
G_PsiWW, **277, 298**, used: **283, 305**
G_PsiZAH, **277, 298**, used: **283, 305**

- G_PsiZHAH*, **277, 298**, used: 283, 305
G_PsiZHW, **277, 298**, used: 283, 305
G_PsiZHWH, **277, 298**, used: 283, 305
G_PsiZHZ, **277, 298**, used: 283, 305
G_PsiZHZH, **277, 298**, used: 283, 305
G_PsiZW, **277, 298**, used: 283, 305
G_PsiZWH, **277, 298**, used: 283, 305
G_PsiZZ, **277, 298**, used: 283, 305
G_PWW, **414**, used: 417
G_PWZ, **414**, used: 417
G_PZWW, **436, 486, 517**, used: 448, 493, 527
G_s, **387**, used: 390
G_s2, **387**, used: 392
G_saa, **676**, used: 678
G_saaa, **676**, used: 678
G_SD4, **436**, used: 460
G_SD4_2, **436**, used: 460
G_SF4, **436**, used: 436
G_SF4_3, **436**, used: 436
G_SF4_4, **436**, used: 436
G_SFSFP, **486, 517**, used: 498, 532
G_SFSFS, **486, 517**, used: 497, 498, 532, 532
G_SL2SQ2, **436**, used: 460
G_SL4, **436**, used: 459
G_SL4_2, **436**, used: 459
G_SLR_DbtR, **239, 414**, used: 245, 421
G_SLSNW, **436, 486, 517**, used: 441, 489, 520
G_SL_DbtL, **239, 414**, used: 245, 421
G_SL_DttL, **239, 414**, used: 245, 421
G_SL_DttR, **239, 414**, used: 245, 421
G_SN2SL2_1, **436**, used: 459
G_SN2SL2_2, **436**, used: 459
G_SN2SQ2, **436**, used: 460
G_SN4, **436**, used: 459
G_SP_ttH, **239, 414**, used: 243, 419
G_SR_DttR, **239, 414**, used: 245, 421
G_SS, **436, 486, 517**, used: 448, 493, 527
G_SSWW, **414**, used: 417
G_SSZZ, **414**, used: 417
G_strong, **436, 517, 364**, used: 461
G_SU2SD2, **436**, used: 461
G_SU4, **436**, used: 460
G_SU4_2, **436**, used: 460
G_SUSDSNSL, **436**, used: 460
G_SWS, **436**, used: 441
G_SWW, **414**, used: 417
G_SZZ, **414**, used: 417
G_S_Sqrt, **436**, used: 445
G_TLR_btW, **239, 414**, used: 243, 419
G_TLR_btWA, **239, 414**, used: 243, 419
G_TLR_btWZ, **239, 414**, used: 244, 420
G_TNWW, **414**, used: 418
G_TNZZ, **414**, used: 418
G_TRL_tbW, **239, 414**, used: 243, 419
G_TRL_tbWA, **239, 414**, used: 243, 419
G_TRL_tbWZ, **239, 414**, used: 244, 420
G_TVA_bbA, **239, 414**, used: 242, 418
G_TVA_bbWW, **239, 414**, used: 244, 420
G_TVA_bbZ, **239, 414**, used: 243, 419
G_TVA_ttA, **239, 414**, used: 242, 418
G_TVA_ttG, **239, 414**, used: 242, 418
G_TVA_ttGG, **239, 414**, used: 243, 419
G_TVA_ttWW, **239, 414**, used: 244, 420
G_TVA_ttZ, **239, 414**, used: 242, 418
G_TWW, **414**, used: 418
G_TWZ, **414**, used: 418

- G_VLR_btW*, **239, 414**, used: 243, 419
G_VLR_qBuB, **239, 414**, used: 245, 421
G_VLR_qBuB_d, **239, 414**, used: 245, 421
G_VLR_qBuB_e, **239, 414**, used: 245, 421
G_VLR_qBuB_u, **239, 414**, used: 245, 421
G_VLR_qGuG, **239, 414**, used: 244, 420
G_VLR_tbW, **239, 414**, used: 243, 419
G_VLR_ttZ, **239, 414**, used: 242, 418
G_VL_qBuB_n, **239, 414**, used: 245, 421
G_VL_qW, **239, 414**, used: 245, 421
G_VL_qW_d, **239, 414**, used: 245, 421
G_VL_qW_u, **239, 414**, used: 245, 421
G_weak, **239, 259, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: 239, 260, 260, 414
G_WH3W, **277, 298**, used: 282, 303
G_WH4, **277, 298**, used: 282, 303
G_WHAAH, **277, 298**, used: 282, 303
G_WHWAZ, **277, 298**, used: 282, 303
G_WHWAZH, **277, 298**, used: 282, 303
G_WHWHAAH, **277, 298**, used: 282, 303
G_WHWHAZH, **277, 298**, used: 282, 303
G_WHWHWW, **277, 298**, used: 282, 303
G_WHWHZAH, **277, 298**, used: 282, 303
G_WHWHZHAAH, **277, 298**, used: 282, 303
G_WHWHZZH, **277, 298**, used: 282, 303
G_WHWWW, **277, 298**, used: 282, 303
G_WHWZAH, **277, 298**, used: 282, 303
G_WHWZHAAH, **277, 298**, used: 282, 303
G_WHWZHZH, **277, 298**, used: 282, 303
G_WHWZZ, **277, 298**, used: 282, 303
G_WHWZZH, **277, 298**, used: 282, 303
G_WmHph1, **400**, used: 405
G_WmHph2, **400**, used: 405
G_WmHph3, **400**, used: 405
G_WpHmh1, **400**, used: 405
G_WpHmh2, **400**, used: 405
G_WpHmh3, **400**, used: 405
G_WPSLSN, **436, 486, 517**, used: 450, 495, 530
G_WPSUSD, **436, 486, 517**, used: 451, 496, 530
G_WSQ, **486, 517**, used: 489, 521
G_WWAAH, **277, 298**, used: 282, 303
G_WWAZH, **277, 298**, used: 282, 303
G_WWSFSF, **436, 486, 517**, used: 450, 495, 496, 529, 530
g_www, **388**, used: 388
G_www, **387**, used: 388, 391
G_WWWW, **239, 436, 486, 517, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: 239, 448, 493, 527, 282, 282, 303, 303, 323, 336, 349, 366, 377, 405, 414, ??, ??
g_wwz, **388**, used: 388
G_wwz, **387**, used: 388, 391
g_wwza, **388**, used: 388
G_wwza, **387**, used: 388, 391
G_WWZAH, **277, 298**, used: 282, 303
G_WWZHAAH, **277, 298**, used: 282, 303
g_wwzz, **388**, used: 388
G_wwzz, **387**, used: 388, 391

- G_WWZZH*, **277, 298**, used: **282, 303**
G_WZSLSN, **436, 486, 517**, used: **450, 495, 530**
G_WZSUSD, **436, 486, 517**, used: **451, 496, 530**
g_w_lep, **388**, used: **388**
G_w_lep, **387**, used: **388, 389**
g_w_quark, **388**, used: **388**
G_w_quark, **387**, used: **388, 389, 390**
G_YUK, **436**, used: **442, 443**
G_YUK_1, **436**, used: **443**
G_YUK_2, **436**, used: **443**
G_YUK_3, **436**, used: **443**
G_YUK_4, **436**, used: **443**
G_YUK_C, **436, 486, 517**, used: **446, 492, 523**
G_YUK_DCU, **486, 517**, used: **490, 522**
G_YUK_FFP, **486, 517**, used: **490, 521**
G_YUK_FFS, **486, 517**, used: **490, 521**
G_YUK_G, **436, 486, 517**, used: **445, 492, 523**
G_YUK_LCN, **486, 517**, used: **490, 522**
G_YUK_LQ_P, **517**, used: **526**
G_YUK_LQ_S, **517**, used: **526**
G_YUK_N, **436, 486, 517**, used: **445, 491, 523**
G_YUK_Q, **436, 486, 517**, used: **446, 492, 524**
G_YUK_UCD, **486, 517**, used: **490, 522**
G_Z, **436, 486, 517**, used:
G_ZEH, **319**, used: **324**
G_ZGILQLQ, **517**, used: **527**
G_Zh1h2, **400**, used: **405**
G_Zh1h3, **400**, used: **405**
G_Zh2h3, **400**, used: **405**
G_ZHEH, **319**, used: **324**
G_ZHpHm, **400**, used: **405**
G_ZHPsipp, **277, 298**, used: **284, 305**
G_ZHTHT, **277, 298**, used: **279, 301**
G_zhthth, **319**, used:
G_ZLQ, **517**, used: **527**
G_ZPLQLQ, **517**, used: **527**
G_ZPSFSF, **436, 486, 517**, used: **450, 495, 529**
G_ZPsip, **277, 298**, used: **284, 305**
G_ZPsipp, **277, 298**, used: **284, 305**
G_ZSF, **436, 486, 517**, used: **442, 490, 521**
G_ZTHT, **277, 298**, used: **279, 301**
G_ZZLQLQ, **517**, used: **527**
G_ZZSFSF, **436, 486, 517**, used: **450, 495, 496, 529, 530**
G_ZZWW, **239, 436, 486, 517, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: **239, 448, 493, 527, 282, 282, 303, 303, 323, 336, 349, 366, 377, 405, 414, ??, ??**
g_z_lep, **388**, used: **388**
G_z_lep, **387**, used: **388, 390**
g_z_quark, **388**, used: **388**
G_z_quark, **387**, used: **388, 390**
H, **239, 255, 273, 295, 317, 331, 341, 360, 372, 414, ??, ??**, used: **239, 239, 239, 239, 241, 241, 243, 247, 256, 257, 261, 262, 273, 275, 280, 281, 283, 283, 284, 285, 285, 288, 288, 288, 289, 296, 297, 302, 302, 304, 304, 305, 306, 306, 309, 309, 310, 310, 317, 318, 323, 323, 324, 324, 324, 324, 324, 324, 324, 324, 325, 331, 333, 336, 336, 336, 336, 336, 337, 337, 338, 342, 344, 348, 349, 349, 349, 349, 349, 349, 349, 350, 361, 362, 365, 366, 366, 366, 366, 366, 367, 372, 373, 376, 377, 377, 377, 377, 378, 414, 414, 414, 414, 414, 415, 416, 419, 422, ??, ??, ??, ??, ??, ??**

- ??, ??, ??, ??, ??, ??, ??,
 ??, ??, ??, ??
- H1*, **432**, used:
- H1dm*, **341**, used: 342, 344, 350
- H1dp*, **341**, used: 342, 344, 350
- H1um*, **341**, used: 342, 344, 350
- H1up*, **341**, used: 342, 344, 350
- H2*, **432**, used:
- H2* (module), **222**, used: 222,
 222, 223, 224
- H2dm*, **341**, used: 342, 344, 350
- H2dp*, **341**, used: 342, 344, 350
- H2um*, **341**, used: 342, 344, 350
- H2up*, **341**, used: 342, 344, 350
- H3*, **432**, used:
- H3* (module), **222**, used: 222,
 222, 223, 224
- H4*, **432**, used:
- H5*, **432**, used:
- H6*, **432**, used:
- HA*, **397**, used: 397, 399, 403,
 403, 403, 404, 404, 404,
 405, 406, 406, 407, 407
- half*, **239, 260, 414**, used: 239,
 260, 414
- Half*, **239, 259, 414**, used: 245,
 245, 246, 246, 421, 421
- harvest*, **41, 47, 39**, used: 47, 48,
 49, 113
- harvest_goldstones*, **113**, used:
- harvest_list*, **41, 48, 39**, used:
 119, 122
- hash*, **695, 695, 221, 222, 222**,
107, 694, used: 221, 222,
 222, 107, 107, 107
- hash* (type), **695, 695, 694**, used:
 695, 695, 694
- HC1*, **513**, used: 513, 514, 522,
 522, 522, 528, 528, 528,
 528, 529, 529, 529, 529,
 529, 531, 532, 532, 534
- HC1c*, **513**, used: 513, 514, 522,
 522, 522, 528, 528, 528,
 528, 529, 529, 529, 529,
 529, 531, 532, 532, 534
- HC2*, **513**, used: 513, 514
- HC2c*, **513**, used: 513, 514
- HC3*, **513**, used: 513, 514
- HC3c*, **513**, used: 513, 514
- HC4*, **513**, used: 513, 514
- HC4c*, **513**, used: 513, 514
- HC5*, **513**, used: 513, 514
- HC5c*, **513**, used: 513, 514
- hdn*, **700, 698**, used: 700
- hdl*, **751**, used: 752, 752
- head_req*, **208**, used: 208
- Heavy*, **383**, used: 384, 384, 391,
 391, 393
- Heavy2*, **383**, used: 384, 388
- heavy_currents*, **322**, used: 325
- heavy_gauge_higgs*, **283, 304**,
324, used: 285, 306, 324
- heavy_gauge_higgs4*, **324**, used:
 324
- heavy_quartic_gauge*, **282, 303**,
323, used: 283, 304, 324
- heavy_top_currents*, **279, 301**,
 used: 289, 310
- heavy_triple_gauge*, **281, 303**,
323, used: 282, 303, 323
- height*, **714**, used: 714, 714, 714
- Helac* (module), **34, 129, 21, 92**,
 used: 129
- Helac_Binary* (module), **35, 21**,
 used:
- Helac_Majorana* (module), **129**,
92, used:
- helicities*, **129, 131, 93**, used:
 600, 601
- helicities* (field), **130**, used: 131,
 136
- helicities* (type), **130**, used:
- helicity_table*, **133**, used: 135
- hgg*, **279**, used: 283, 283, 283,
 288, 289
- Hh*, **397**, used: 397, 399, 403,
 403, 403, 404, 404, 404,
 405, 406, 406, 407, 407
- HH*, **397**, used: 397, 399, 403,
 403, 403, 404, 404, 404,
 405, 406, 406, 407, 407
- hhgg*, **279**, used: 285, 285
- higgs*, **241, 452, 497, 531, 288**,
309, 324, 337, 350, 367,
377, 406, 416, ??, ??,
 used: 246, 462, 498, 533,
 289, 310, 325, 337, 350,
 367, 377, 407, 422, ??, ??
- higgs* (type), **432**, used: 432, 436

- higgs4*, **241, 453, 497, 531, 288, 309, 325, 337, 350, 367, 377, 407, 416, ??, ??**,
 used: **247, 464, 499, 534, 289, 310, 325, 337, 350, 367, 377, 407, 422, ??, ??**
- higgs_anom*, **237, 237, 237, 238, 238, 238, 238, 413, 413, 227, 271**, used: **241, 241, 241, 241, 416, 416, 416, 416**
- higgs_charg_neutr*, **444, 491, 522**, used: **462, 498, 533**
- higgs_ch_gravitino*, **448**, used: **448**
- higgs_gold*, **452**, used: **463**
- higgs_gold4*, **453**, used: **464**
- higgs_gold_sf*, **458**, used: **464**
- higgs_gold_sf*, **458**, used: **458**
- higgs_gold_sneutrino*, **457**, used: **464**
- higgs_gold_sneutrino'*, **457**, used: **457**
- higgs_gold_squark*, **458**, used: **464**
- higgs_gold_squark'*, **458**, used: **458**
- higgs_hmm*, **237, 237, 237, 238, 238, 238, 238, 413, 413, 227, 271**, used: **239, 414**
- higgs_neutr*, **444, 491, 523**, used: **462, 498, 533**
- higgs_neutr'*, **444**, used: **444**
- higgs_neutr''*, **444**, used: **444**
- higgs_neu_gravitino*, **448**, used: **448**
- higgs_SCC*, **497, 531**, used: **497, 531**
- higgs_sf*, **454, 498, 532**, used: **462, 498, 533**
- higgs_sf*, **454, 498, 532**, used: **454, 498, 532**
- higgs_sf*, **454, 498, 532**, used: **454, 498, 532**
- higgs_sf*, **456**, used: **464**
- higgs_sf*, **456**, used: **456**
- higgs_sf*, **498, 532**, used: **498, 532**
- higgs_sf*, **498, 532**, used: **498, 532**
- higgs_sf*, **454, 497, 532**, used: **454, 497, 532**
- higgs_sf*, **456**, used: **464**
- higgs_sf*, **456**, used: **456**
- higgs_SF*, **497, 531**, used: **497, 531**
- higgs_squark*, **455, 498, 532**, used: **462, 498, 533**
- higgs_squark'*, **455, 498, 532**, used: **455, 498, 532**
- higgs_squark4*, **457**, used: **464**
- higgs_squark4'*, **457**, used: **457**
- higgs_squark_a*, **455, 498, 532**, used: **455, 498, 532**
- higgs_squark_b*, **455, 498, 532**, used: **455, 498, 532**
- higgs_SSS*, **497, 531**, used: **497, 531**
- higgs_triangle*, **237, 237, 237, 238, 238, 238, 238, 238, 429, 430, 430, 430, 430, 430, 430, 480, 480, 481, 481, 413, 413, 227, 429, 480, 271**, used: **241, 449, 494, 416**
- higgs_triangle_vertices*, **241, 416**, used: **246, 422**
- Hit*, **695, 696, 694**, used: **697**
- Hm*, **432, 483, 397**, used: **433, 435, 442, 443, 444, 448, 449, 449, 452, 452, 453, 453, 454, 455, 456, 456, 457, 457, 458, 458, 462, 462, 465, 483, 485, 490, 490, 491, 493, 494, 494, 494, 494, 494, 495, 495, 495, 497, 497, 498, 499, 397, 399, 403, 405, 406, 406, 407**
- Hn (module)*, **222**, used: **222, 222, 223, 224**

- homogeneous*, **703, 698**, used:
703, 133, 134
homogeneous_final_state, **216**,
used: **216, 218**
Hp, **432, 483, 397**, used: **433**,
435, 442, 443, 444, 448,
449, 449, 452, 452, 453,
453, 454, 455, 456, 456,
457, 457, 458, 458, 462,
462, 465, 483, 485, 490,
490, 491, 493, 494, 494,
494, 494, 494, 495, 495,
495, 497, 497, 498, 499,
397, 399, 403, 405, 406,
406, 407
hs_of_flavor, **132**, used: **132, 132**
hs_of_flavors, **132**, used: **133**,
134
hs_of_lorentz, **132**, used: **132**,
132
H_Heavy, **432**, used: **433, 435**,
442, 443, 444, 448, 449,
449, 449, 450, 452, 452,
453, 453, 454, 454, 456,
456, 457, 457, 458, 462,
465
H_Light, **432**, used: **433, 435**,
442, 443, 444, 448, 449,
449, 449, 450, 452, 452,
453, 453, 454, 454, 456,
456, 457, 457, 458, 462,
465
I, **549, ??, 168, 549, ??**, used:
549, ??, 239, 260, 414, 551
I (camlyacc token), **552**, used:
552
id, **132**, used: **133**
IG_s, **387**, used: **391**
imag, **549, 549**, used: **??, 552**
IMap (module), **30**, used: **30, 30**,
30, 30, 31, 31, 31
import, **76**, used: **76**
import_prefixed, **665**, used: **665**,
666
impossible, **761, 10, 186**, used:
761, 10, 10, 196
Impossible (exn), **761, 10, 24**,
44, 49, 96, 97, 124, 127,
used:
in1 (field), **661**, used:
in2 (field), **661**, used:
include_anomalous, **??, ??, ??**,
??, ??, ??, used:
include_ckm, **381, 381, 381**,
381, 382, 382, 382, 271,
used: **382, 387, 392**
include_four, **429, 430, 430**,
430, 430, 430, 430, 429,
used: **464**
include_goldstone, **429, 430**,
430, 430, 430, 430, 430,
429, used: **433, 434, 463**,
464
include_goldstones, **670**, used:
670, 673
include_hf, **381, 381, 381, 381**,
382, 382, 382, 271,
used: **382, 384, 393**
incoming, **55, 59, 60, 65, 65**,
213, 213, 95, 102, 105,
123, 53, 54, 212, 91,
used: **65, 123, 131, 131**,
580, 599, 599, 599
incoming (field), **102, 105**, used:
105, 114, 119, 122, 122
incomplete, **185, 210**, used: **192**,
193, 196, 205, 210, 210,
210, 211
Incomplete (exn), **654, 656, 653**,
used:
Index, **551**, used: **551**
Index', **551**, used: **551**
index_string, **711, 709**, used:
685, 685
indices, **209**, used: **209**
Infinity, **768**, used: **768**
init, **560**, used: **789, 791, 774**,
561, 111
initialize_cache, **95, 107, 129**,
136, 91, 93, used: **136**,
673
inject, **266**, used: **266, 267, 267**,
268, 268, 269
injectl, **269**, used: **269, 269**
input (field), **173**, used: **560, 229**,
230, 232, 235, 239, 260,
440, 488, 519, 278, 300,
320, 335, 347, 365, 376,
393, 402, 414, 577, ??, ??,
679

input_functions, **559**, used: **559**,
561
input_lagrangian, **559**, used: **559**,
561
input_model, **559**, used:
input_parameters, **239**, **259**,
278, **300**, **320**, **335**, **347**,
365, **376**, **414**, **??**, **??**,
used: **239**, **260**, **278**, **300**,
320, **335**, **347**, **365**, **376**,
414, **??**, **??**
input_particles, **559**, used: **559**,
561
input_table, **555**, used: **559**
input_variables, **559**, used: **559**,
561
insert, **753**, used: **753**, **753**
insert1, **784**, **786**, **787**, used:
785, **786**, **786**, **786**, **787**
insert_inorder_signed, **754**, used:
754
insert_in_unfinished_decays,
658, used: **658**
insert_signed, **753**, used: **753**,
753
inspect_partition, **21**, **22**, **25**, **27**,
27, **34**, **35**, **20**, used:
29, **126**, **20**, used:
126, **126**
INT, **??**, **??**, **??**, **??**, used: **??**,
??, **71**, **551**
INT (camlyacc token), **72**, **552**,
used: **73**, **552**
integer, **549**, **549**, used: **??**, **557**,
560, **552**
integer (type), **29**, **29**, **20**, used:
29, **30**, **30**, **21**, **21**, **21**, **21**
integer (camlllex regexpr), **551**,
used: **551**
Integer, **549**, **549**, used: **549**
Integer (sig), **28**, **20**, used: **29**,
29, **20**, **21**
integer_range, **218**, used: **218**
interleave, **703**, **699**, used: **704**
interleave_nearest, **704**, **699**,
used:
internal_edges, **771**, used: **772**
internal_edges_from, **771**, used:
771, **771**
int_edges (field), **772**, used: **772**,
773, **774**
int_incidence, **773**, used: **774**
int_list_to_string, **71**, used:
int_node, **769**, used: **769**
int_nodes (field), **772**, used: **773**,
773, **774**, **774**, **775**, **775**
int_of_char, **432**, **482**, **513**,
used: **433**, **434**, **435**, **467**,
484, **484**, **485**, **503**, **513**,
515, **515**, **516**, **539**
int_of_csign, **383**, used: **385**,
386, **387**, **387**, **387**, **387**
int_of_gen, **383**, used: **394**
int_power, **87**, used: **87**
invalid, **185**, used: **188**, **188**, **193**
Invalid (exn), **688**, **688**, used:
invalid_flavor, **679**, used: **679**
inverse, **755**, **755**, **756**, **754**,
used: **756**, **756**, **758**, **758**
inverse_ok, **758**, used: **758**
invert_array, **772**, used: **772**
invert_array_unsafe, **772**, used:
InvPi (module), **739**, used: **739**,
739, **739**, **739**, **739**, **739**
inv_pi, **739**, **739**, **740**, **740**, **738**,
738, used: **740**, **740**, **740**,
120, **121**, **121**
in_ghost_flags, **84**, **85**, **81**, used:
in_to_lists, **84**, **85**, **81**, used: **601**
IPowSet (module), **79**, **218**,
used: **79**, **79**, **218**
ISet (module), **704**, **188**, **218**,
used: **704**, **704**, **704**, **188**,
218, **218**
iset_list_union, **704**, used: **704**
iset_of_list, **704**, used: **704**
isospin (type), **383**, used: **383**,
387
Iso_down, **383**, used: **384**, **389**,
389
Iso_up, **383**, used: **384**, **389**
is_empty, **713**, **714**, **719**, **742**,
742, **727**, **728**, **728**, **712**,
741, **725**, **726**, used: **742**,
743, **743**, **744**, **784**, **785**,
787, **46**, **47**, **79**, **217**
is_error, **??**, used: **??**
is_failure, **??**, used: **??**

- is_gauss*, **74, 77, 95, 102, 105**,
123, 74, 91, used: **119**,
123, 595
is_gauss (field), **77, 102, 105**,
used: **77, 77, 80, 105, 114**,
119, 122
is_goldstone_of, **106**, used:
is_node, **41, 46, 38**, used: **113**,
114, 114
is_null, **782, 783, 783, 785**,
787, 183, 183, 183, 183,
184, 184, 779, 780, 182,
used: **786, 786, 787, 787**,
787, 788, 184, 184, 214,
123
is_offspring, **41, 46, 38**, used: **47**
is_skip, **??**, used: **??**
is_source, **105**, used: **110, 114**,
114
is_sterile, **41, 46, 38**, used: **48**,
48, 120
is_success, **??**, used:
is_todo, **??**, used: **??**
is_unit, **782, 783, 783, 783**,
784, 785, 779, 780, 780,
used: **786, 787, 788**
is_white, **205**, used: **205**
It (module), **185, 185**, used: **209**,
96, 98, 119, 130, 670, 569,
92, 94
iter, **713, 718, 721, 727, 728**,
729, 730, 732, 9, 11, 12,
14, 16, 41, 44, 45, 47,
49, 712, 725, 726, 726,
6, 39, used: **??, ??, ??**,
??, ??, ??, ??, ??, 718,
721, 729, 730, 732, 733,
770, 770, 773, 773, 774,
775, 775, 16, 45, 46, 47,
49, 224, 664, 665, 666,
666, 668, 126, 135, 670,
674, 674, 674, 674, 674,
571, 573, 575, 575, 576,
577, 577, 577, 579, 580,
580, 590, 592, 592, 595,
595, 596, 596, 596, 599,
599, 602, 603, 603, 604,
612, 614, 614, 615, 615,
615, 615, 616, 616, 617,
618, 618, 618, 619, 620,
621, 621, 622
iter', **729, 732**, used: **729, 732**
iteri, **702, 699**, used: **702, 612**
iteri2, **702, 699**, used:
iter_edges, **774, 765**, used:
iter_incoming, **775, 765**, used:
iter_internal, **775, 765**, used:
iter_nodes, **41, 46, 38**, used: **126**
iter_outgoing, **775, 765**, used:
I_G1_AWW, **239, 414**, used:
239, 414
I_G1_minus_kappa_minus_G4_AWW,
239, 414, used: **239, 414**
I_G1_minus_kappa_minus_G4_ZWW,
239, 414, used: **239, 414**
I_G1_minus_kappa_plus_G4_AWW,
239, 414, used: **239, 414**
I_G1_minus_kappa_plus_G4_ZWW,
239, 414, used: **239, 414**
I_G1_plus_kappa_minus_G4_AWW,
239, 414, used: **239, 414**
I_G1_plus_kappa_minus_G4_ZWW,
239, 414, used: **239, 414**
I_G1_plus_kappa_plus_G4_AWW,
239, 414, used: **239, 414**
I_G1_plus_kappa_plus_G4_ZWW,
239, 414, used: **239, 414**
I_G1_ZWW, **239, 414**, used:
239, 414
I_G3, **676**, used: **678**
I_Gs, **233, 239, 259, 277, 298**,
319, 334, 347, 375, 400,
414, ??, ??, used: **235**,
239, 243, 262, 281, 303,
323, 336, 348, 376, 405,
414, 419, ??, ??
I_GsRt2, **347**, used: **348**
I_G_Abb, **400**, used:
I_G_Acc, **400**, used:
I_G_AHWW, **277, 298**, used:
281, 303
I_G_AHWWH, **277, 298**,
used: **281, 303**
I_G_AHWW, **277, 298**, used:
281, 303
I_G_Amumu, **400**, used:
I_G_Atautau, **400**, used:
I_G_Att, **400**, used:
I_G_CC, **319**, used: **321**

- I_G_PsiOppWHW*, **277, 298**,
 used: **285, 306**
I_G_PsiOppWHWH, **277, 298**,
 used: **285, 306**
I_G_PsiOppWW, **277, 298**,
 used: **285, 306**
I_G_PsiOppWA, **277, 298**, used:
285, 306
I_G_PsiOppWAH, **277, 298**,
 used: **285, 306**
I_G_PsiOppWHA, **277, 298**, used:
285, 306
I_G_PsiOppWHAH, **277, 298**,
 used: **285, 306**
I_G_PsiOppWHZ, **277, 298**, used:
285, 306
I_G_PsiOppWHZH, **277, 298**,
 used: **285, 306**
I_G_PsiOppWZ, **277, 298**, used:
285, 306
I_G_PsiOppWZH, **277, 298**,
 used: **285, 306**
I_G_S, **436, 486, 517**, used:
448, 493, 527
I_G_weak, **239, 259, 414**, used:
239, 243, 244, 244, 244,
414, 419, 420, 420, 420
I_G_WWW, **277, 298, 319**,
400, ??, used: **281, 303**
I_G_Z1, **319**, used: **323**
I_G_Z2, **319**, used: **323**
I_G_Z3, **319**, used: **323**
I_G_Z4, **319**, used: **323**
I_G_Z5, **319**, used: **323**
I_G_Z6, **319**, used: **323**
I_G_ZHWHWH, **277, 298**,
 used: **281, 303**
I_G_ZHWW, **277, 298**, used:
281, 303
I_G_ZWHW, **277, 298**, used:
281, 303
I_G_ZWW, **239, 436, 486, 517,**
277, 298, 319, 334, 347,
364, 375, 400, 414, ??,
??, used: **239, 242, 448,**
493, 527, 281, 281, 289,
303, 303, 310, 323, 325,
336, 337, 348, 350, 366,
367, 376, 377, 405, 407,
414, 416, ??, ??, ??, ??
- I_G_ZWW_K1*, **347**, used: **348**
I_G_ZWW_K2, **347**, used: **348**
I_G_ZWW_K3, **347**, used: **348**
I_kappa5_AWW, **239, 414**,
 used: **239, 414**
I_kappa5_ZWW, **239, 414**,
 used: **239, 414**
I_lambda5_AWW, **239, 414**,
 used: **239, 414**
I_lambda5_ZWW, **239, 414**,
 used: **239, 414**
I_lambda_AWW, **239, 414**,
 used: **239, 414**
I_lambda_ZWW, **239, 414**,
 used: **239, 414**
I_Q_H, **277, 298, 319**, used:
I_Q_W, **239, 259, 436, 486,**
517, 277, 298, 319, 334,
347, 364, 375, 400, 414,
??, ??, used: **239, 242,**
260, 448, 493, 527, 281,
281, 289, 303, 303, 310,
323, 323, 325, 336, 337,
348, 350, 366, 367, 376,
377, 405, 407, 414, 416,
??, ??, ??, ??
I_Q_W_K, **347**, used: **348**
I_Q_ZH, **319**, used: **323**
Java (module), **638, 563**, used:
join, **714, 693, 693**, used: **714,**
715, 715, 717, 718, 693
join_signs, **754**, used: **754**
ket, **95, 102, 104, 123, 90**, used:
123, 596
key (type), **695, 695, 727, 728,**
728, 44, 45, 49, 694,
725, 726, used: **695, 727,**
728, 728, 728, 730, 44, 44,
45, 49, ??, 694, 694, 725,
725, 725, 725, 726, 726,
726
Key (sig), **695, 694**, used: **695,**
694
keys, **45**, used: **45**
keystone, **25**, used: **25**
keystones, **752, 21, 25, 27, 27,**
27, 29, 33, 34, 35, 746,
19, 21, used: **752, 34, 118**
keystones', **27, 34, 35**, used: **27,**
27, 27, 34, 35

- kind*, **570, 179, 180**, used: 570,
575, 575, 575, 575, 576,
576, 580, 580, 593, 594,
594, 596, 599, 600, 604,
606, 607, 608, 608, 610,
610, 618
- kind* (type), **179, 180**, used: 179,
180
- kk2* (type), **383**, used: 387
- kkmode* (type), **383**, used: 383,
384, 387
- kmatrix_cuts*, **109**, used: 109,
110, 121
- km_pure*, **570**, used: 570, 618
- km_write*, **570**, used: 570, 618
- k_matrix*, **237, 237, 237, 238,**
238, 238, 238, 238, 413,
413, ??, ??, ??, ??, ??,
??, 227, 271, used: 239,
414
- K_Matrix_Coeff*, **239, 414**,
used:
- K_Matrix_Pole*, **239, 414**, used:
- k_matrix_quartic_gauge*, **239,**
414, used: 239, 414
- L*, **239, 255, 432, 483, 514,**
273, 295, 317, 331, 341,
360, 372, 397, 414, ??,
??, used: 239, 245, 245,
247, 256, 257, 259, 260,
261, 261, 261, 262, 433,
435, 439, 440, 441, 441,
442, 443, 445, 446, 447,
461, 461, 465, 483, 485,
488, 488, 489, 490, 490,
491, 492, 499, 514, 516,
519, 520, 520, 522, 522,
523, 523, 525, 525, 525,
525, 534, 273, 275, 279,
279, 279, 280, 280, 280,
281, 289, 296, 297, 300,
300, 301, 301, 302, 302,
310, 317, 318, 321, 321,
321, 322, 322, 323, 325,
331, 333, 335, 335, 335,
335, 336, 338, 342, 344,
348, 348, 348, 348, 348,
350, 361, 362, 365, 365,
365, 365, 366, 367, 372,
373, 376, 376, 376, 376,
378, 397, 399, 402, 402,
403, 403, 404, 407, 414,
421, 421, 422, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??
- label*, **655**, used: 655, 655, 656,
657, 658, 659
- label* (field), **768, 764**, used: 769,
769, 771, 771
- Label*, **??, ??**, used: ??, ??, ??
- lagrangian_file*, **561**, used: 561,
561
- Lambda*, **486**, used:
- last_begin* (field), **690**, used: 691,
692, 692, 692
- last_non_white*, **553**, used: 554
- last_reset* (field), **690**, used: 691,
692, 692
- LaTeX* (module), **639, 563**,
used:
- layout*, **774, 765**, used:
- layout* (type), **773, 765**, used:
765, 765
- lcm*, **782**, used:
- leaf*, **776, 765, 776, 763**, used:
47, 48
- Leaf*, **776, 765, 655**, used: 776,
765, 767, 655, 655, 656,
657, 657
- leafs*, **765, 764**, used: 765, 770,
771, 125
- leafs_and_nodes*, **771**, used: 772
- leaf_label*, **768**, used: 769, 769
- leaf_node*, **769**, used: 769, 769
- leaf_or_int_node*, **769**, used: 769
- leaf_to_string*, **767**, used: 768
- left_to_right*, **773, 765**, used:
- lepton*, **239, 259, 440, 486, 517,**
276, 298, 319, 334, 346,
364, 375, 384, 400, 414,
??, ??, used: 239, 259,
440, 486, 517, 277, 298,
319, 334, 347, 364, 375,
384, 393, 400, 414, ??, ??
- Lepton*, **383**, used: 384, 386, 389,
389, 390
- lep_family*, **433**, used:
- less*, **55, 59, 65, 52**, used: 656,
657

- less'*, **59**, used: 59, 59
lesseq, **55, 59, 64, 52**, used: 65, 656, 657, 75
lesseq', **59**, used: 59, 59
lhs, **95, 102, 104, 123, 90**, used: 105, 123, 123, 125, 133, 134, 595, 595, 596
Light, **383**, used: 384, 384, 384, 391, 391, 393
Light2, **383**, used: 384, 384, 388
Light_Heavy, **383**, used: 384, 388
Linalg (module), **789, 789**, used: 774, 774
line (type), **82, 83**, used: 82, 83, 83
Line (sig), **82**, used: 83
linear, **784, 787, 781**, used: 787
Linear (sig), **784, 781**, used: 787, 781
Lines, **84, 88**, used: 85, 85
line_length, **570**, used: 570, 577, 620, 621, 623, 623
list, **755, 755, 756, 689, 735, 754, 688, 734**, used:
List (module), **719, 713**, used:
 ??, ??, ??, ??, ??, ??, ??,
 ??, ??, ??, ??, ??, ??, ??,
 723, 723, 723, 700, 700,
 700, 701, 701, 701, 702,
 702, 702, 702, 703, 703,
 704, 704, 704, 704, 704,
 704, 704, 705, 705, 707,
 755, 755, 756, 759, 739,
 742, 742, 742, 743, 743,
 743, 743, 686, 693, 696,
 793, 776, 776, 776, 782,
 785, 785, 786, 786, 786,
 786, 787, 787, 787, 788,
 688, 689, 689, 735, 735,
 735, 735, 735, 735, 735,
 749, 749, 749, 749, 750,
 750, 750, 750, 750, 751,
 751, 751, 751, 751, 752,
 752, 752, 752, 752, 752,
 753, 753, 753, 753, 753,
 753, 754, 754, 754, 754,
 754, 760, 761, 761, 766,
 767, 767, 767, 767, 768,
 769, 770, 770, 771, 772,
 773, 773, 773, 774, 774,
 774, 10, 10, 11, 11, 13, 13,
 15, 16, 16, 16, 16, 16, 17,
 17, 17, 17, 22, 25, 25, 27,
 27, 27, 27, 30, 30, 30, 32,
 32, 33, 33, 33, 33, 34, 34,
 34, 34, 35, 35, 35, 48, 48,
 48, 56, 56, 57, 58, 61, 62,
 63, 63, 654, 654, 656, 657,
 657, 658, 658, 659, 659,
 183, 183, 184, 184, 83, 83,
 83, 84, 85, 85, 85, 85, 85,
 85, 85, 85, 86, 86, 86, 87,
 88, 223, 224, 224, 661,
 661, 662, 662, 662, 662,
 662, 662, 662, 663, 663,
 663, 663, 664, 664, 665,
 665, 666, 666, 668, 550,
 550, 550, 554, 554, 555,
 555, 557, 559, 559, 560,
 561, 70, 71, 75, 76, 76, 76,
 76, 76, 77, 77, 78, 79, 79,
 79, 79, 188, 191, 193, 205,
 206, 207, 207, 207, 208,
 209, 209, 209, 209, 214,
 214, 214, 215, 217, 217,
 217, 217, 217, 217, 217,
 218, 218, 218, 219, 219,
 219, 97, 103, 105, 105,
 106, 110, 112, 112, 112,
 112, 112, 113, 114, 114,
 114, 118, 119, 119, 120,
 121, 121, 121, 121, 122,
 122, 122, 123, 123, 124,
 124, 124, 125, 125, 125,
 125, 125, 125, 126, 126,
 131, 131, 131, 131, 132,
 132, 132, 133, 133, 134,
 134, 134, 135, 135, 135,
 670, 670, 671, 671, 672,
 672, 673, 673, 674, 674,
 674, 674, 674, 675, 239,
 244, 245, 245, 246, 246,
 256, 256, 260, 261, 261,
 261, 261, 261, 262, 262,
 267, 267, 268, 268, 269,
 269, 441, 442, 445, 446,
 446, 448, 450, 451, 451,
 452, 454, 455, 455, 456,
 456, 457, 458, 458, 460,
 460, 460, 461, 462, 462,

463, 464, 481, 481, 482,
482, 489, 490, 490, 491,
492, 492, 492, 494, 495,
496, 496, 496, 497, 497,
497, 498, 498, 498, 512,
512, 512, 512, 514, 521,
521, 522, 523, 523, 523,
524, 526, 526, 526, 526,
528, 529, 530, 530, 530,
531, 531, 532, 532, 532,
533, 273, 273, 279, 279,
279, 279, 279, 280, 280,
280, 281, 281, 281, 281,
282, 282, 283, 283, 283,
284, 285, 285, 288, 289,
331, 331, 335, 335, 335,
335, 335, 336, 336, 336,
342, 342, 348, 348, 348,
348, 348, 348, 348, 349,
361, 361, 365, 365, 365,
365, 366, 366, 372, 372,
376, 376, 376, 376, 376,
377, 384, 388, 389, 390,
393, 393, 393, 394, 397,
397, 402, 402, 402, 403,
405, 405, 414, 420, 421,
421, 571, 572, 572, 572,
573, 573, 574, 575, 575,
575, 575, 575, 575, 576,
577, 577, 577, 577, 579,
580, 580, 580, 580, 580,
590, 592, 592, 595, 595,
596, 596, 596, 596, 598,
599, 599, 599, 599, 599,
600, 600, 600, 600, 601,
601, 601, 601, 601, 601,
601, 602, 602, 602, 602,
603, 603, 604, 605, 607,
612, 612, 614, 614, 615,
615, 615, 615, 616, 616,
616, 617, 617, 617, 618,
618, 618, 619, 620, 621,
621, 622, 622, 622, 623,
632, 632, 632, 633, 633,
634, 634, 634, 635, 635,
635, 636, 636, 636, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, 676, 676, 676, 676,
678, 678, 678, 678, 678,
678, 681
list2, **735, 734**, used: 11, 15, 124,
133, 239, 261, 441, 442,
445, 446, 446, 448, 450,
451, 451, 452, 454, 455,
455, 456, 456, 457, 458,
458, 459, 459, 460, 460,
460, 460, 460, 461, 462,
462, 463, 464, 489, 490,
490, 492, 492, 492, 494,
496, 496, 496, 497, 497,
498, 498, 521, 521, 522,
523, 523, 524, 526, 526,
526, 528, 530, 530, 530,
531, 532, 532, 533, 414
list3, **735, 734**, used: 12, 15,
491, 492, 498, 522, 523,
526, 532, 533
ListItem, ??, ??, used: ??, ??, ??
lists, **41, 47, 39**, used: 119, 122
Lists (module), **56, 54**, used: 67,
54
ListSimpleMake (module), ??,
??, used:
ListsW (module), **67, 54**, used:
Littlest (module), **272, 270**,
used: ??, ??
littlest_gauge_higgs4, **285, 306**,
used:
Littlest_Tpar (module), **295**,
270, used: ??
LMOM, **140**, used:
load, **561**, used: 561
Lodd, **295**, used: 296
longest, **727, 729, 730, 732**,
725, 727, used:
longest', **729, 732**, used: 729, 732
longest_first, **752**, used: 752
loop_cs, **384**, used: 384, 393
loop_gen, **384**, used: 384, 388,
389, 389, 389, 389, 390,
390, 390, 390, 393
loop_iso, **384**, used: 384, 388,
389, 389, 389, 390, 390,
390, 390, 393
loop_kk, **384**, used: 384, 384,
388, 389, 389, 390, 390,
390, 391, 391, 391, 391,
391

M (module), **723, 784, 785,**
787, 772, 49, 556, used:
723, 723, 723, 784, 784,
784, 784, 784, 785, 785,
785, 785, 785, 785, 785,
786, 786, 786, 786, 786,
786, 786, 786, 786, 787,

- 787, 787, 787, 787, 787,
787, 788, 772, 772, 772,
772, 49, 556, 560, 561
- M1*, **431, 482, 513**, used: 433,
441, 442, 445, 446, 446,
448, 450, 451, 451, 452,
454, 454, 455, 455, 456,
456, 456, 457, 457, 458,
458, 459, 459, 460, 460,
460, 460, 460, 461, 462,
462, 464, 465, 483, 489,
490, 491, 492, 492, 492,
493, 496, 496, 496, 497,
497, 497, 498, 498, 498,
499, 514, 521, 521, 523,
523, 523, 524, 524, 524,
525, 525, 525, 525, 525,
525, 525, 526, 526, 526,
526, 526, 526, 526, 527,
527, 527, 530, 530, 530,
531, 531, 532, 532, 532,
533, 534
- M1* (module), **45**, used: 45, 45,
45, 45
- M2*, **431, 482, 513**, used: 433,
441, 442, 445, 446, 446,
448, 450, 451, 451, 452,
454, 454, 455, 455, 456,
456, 456, 457, 457, 458,
458, 459, 459, 460, 460,
460, 460, 460, 461, 462,
462, 464, 465, 483, 489,
490, 492, 492, 492, 493,
496, 496, 496, 497, 497,
497, 498, 498, 498, 499,
514, 521, 521, 523, 523,
524, 524, 524, 525, 525,
525, 525, 525, 525, 525,
525, 525, 525, 525, 526,
526, 526, 526, 526, 526,
526, 527, 527, 527, 530,
530, 530, 531, 531, 532,
532, 532, 533, 534
- M2* (module), **45**, used: 45, 45,
45
- main*, **??, 669, 671, ??, 669**,
used: 76, 675, ??, 675, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
- ??, ??, ??, ??, ??, ??, ??,
??, ??, 681
- main* (camlyacc non-terminal),
72, used: 72
- Majorana*, **127, 137**, used: 127,
127, 433, 484, 515, 361,
677
- Maj_Ghost*, **137**, used:
- make*, **782, 783, 779**, used: ??,
??, 707, 756, 756, 790,
791, 783, 786, 786, 126,
670, 239, 258, 439, 485,
516, 276, 298, 319, 333,
345, 363, 374, 387, 399,
414, 570, 572, ??, ??
- Make* (module), **723, 740, 742**,
695, 728, 49, 655, 661,
75, 213, 126, 670, 723,
738, 742, 694, 726, 40,
653, 660, 74, 213, 669,
used: ??, ??, 723, 723,
704, 739, 742, 742, 730,
688, 30, 45, 45, 45, 46, 49,
222, 223, 224, 661, 662,
664, 79, 188, 217, 218,
218, 219, 219, 96, 105,
105, 106, 106, 112, 114,
114, 120, 121, 125, 126,
127, 129, 129, 129, 129,
130, 131, 131, 133, 133,
670, 670, 572, 675, ??,
675, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, 681, 92
- MakeMap* (module), **730, 726**,
used:
- MakePoly* (module), **731, 727**,
used:
- Maker* (sig), **96, 181, 92**, used:
661, 130, 130, 670, 563,
569, 181, 660, 92, 92, 92,
92, 94, 669, 563, 563, 563
- make_external_dag*, **112**, used:
112
- Make_Fortran* (module), **569**,
used: 624, 638
- Make_Linear* (module), **787**,
781, used:

- Make_Ring* (module), **785, 781**,
used:
- map*, **713, 718, 721, 727, 728**,
729, 730, 732, 783, 784,
785, 787, 767, 9, 11, 12,
14, 16, 41, 47, 654, 657,
712, 725, 726, 726, 780,
781, 764, 6, 39, 653,
used: **??, 723, 718, 721**,
702, 703, 704, 704, 705,
705, 707, 755, 759, 742,
742, 743, 686, 729, 732,
793, 776, 776, 784, 785,
786, 787, 689, 689, 735,
735, 750, 751, 751, 751,
751, 752, 752, 752, 753,
753, 753, 753, 754, 754,
761, 767, 767, 767, 767,
768, 770, 771, 772, 774,
774, 10, 10, 16, 17, 17, 22,
25, 27, 27, 27, 34, 34, 34,
35, 35, 48, 56, 61, 63, 657,
658, 659, 659, 659, 84, 85,
85, 85, 85, 85, 85, 85, 86,
87, 661, 662, 662, 663,
663, 663, 663, 665, 550,
555, 560, 561, 70, 71, 75,
76, 76, 76, 76, 76, 79, 79,
79, 188, 191, 193, 205,
206, 209, 209, 209, 214,
217, 217, 217, 217, 218,
218, 219, 219, 103, 105,
109, 110, 112, 113, 114,
114, 114, 118, 119, 121,
121, 121, 122, 123, 123,
124, 125, 125, 125, 125,
126, 131, 131, 131, 132,
133, 133, 134, 135, 670,
671, 672, 672, 673, 674,
675, 239, 244, 245, 245,
246, 246, 256, 256, 260,
261, 261, 261, 261, 261,
262, 262, 267, 267, 268,
268, 269, 269, 481, 482,
491, 494, 495, 497, 512,
512, 514, 523, 528, 529,
531, 273, 273, 279, 279,
279, 279, 279, 280, 280,
280, 281, 281, 281, 281,
282, 282, 283, 283, 283,
284, 285, 285, 288, 289,
331, 331, 335, 335, 335,
335, 335, 336, 336, 336,
342, 342, 348, 348, 348,
348, 348, 348, 348, 349,
361, 361, 365, 365, 365,
365, 366, 366, 372, 372,
376, 376, 376, 376, 376,
377, 384, 388, 393, 393,
393, 394, 397, 397, 402,
402, 402, 403, 405, 405,
414, 420, 421, 421, 572,
572, 572, 573, 575, 575,
580, 580, 596, 598, 599,
599, 599, 599, 601, 601,
601, 601, 601, 602, 602,
602, 603, 605, 612, 617,
618, 622, 622, 623, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, 676, 676, 676, 676,
678, 678, 678, 678, 678,
678, 681
- map2*, **9, 11, 12, 15, 16, 6**, used:
- 705, 735, 773, 16, 183**,
184, 662, 662, 217, 109
- map_i*, **??, 713, 718, 722, 702**,
727, 728, 729, 730, 732,
712, 699, 725, 726, 726,
used: **??, 718, 722, 729**,
732, 774, 132
- map_i'*, **729, 732**, used: **729, 732**
- mappable*, **664**, used: **664**
- Mappable* (module), **664**, used:
664, 664
- map_amplitude_wfs*, **114**, used:
- map_decay*, **654, 655, 653**, used:
655, 656, 657
- map_nodes*, **41, 47, 38**, used:
- Map-S* (sig), **728, 726**, used:
728, 730, 726
- mask*, **62**, used: **62, 63, 66, 67, 67**
- mask2*, **62**, used:
- mask21*, **62**, used: **62**
- mask5*, **62**, used: **62**
- maskb*, **62**, used: **62**
- maskd*, **62**, used: **62**
- maskr*, **62**, used: **62**
- mask_in*, **65**, used: **65, 65, 65**,
65, 65

- mask_in1*, **65**, used: **65, 65, 65, 65**
- mask_in2*, **65**, used: **65**
- Mass*, **239, 259, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: **239, 259, 260, 414**
- massive*, **179, 180**, used:
- massive* (type), **179, 180**, used: **179, 179, 180, 180**
- Massive*, **179, 180**, used:
- Massive_Vector*, **137**, used: **239, 256, 433, 484, 515, 274, 296, 317, 331, 342, 361, 372, 386, 398, 414, ??, ??**
- massive_vectors* (field), **573**, used: **573, 574, 580**
- massless*, **179, 180**, used:
- massless* (type), **179, 180**, used: **179, 180**
- Massless*, **179, 180**, used:
- mass_symbol*, **225, 556, 190, 209, 229, 230, 233, 236, 251, 255, 265, 266, 472, 507, 545, 292, 314, 329, 340, 359, 371, 380, 395, 410, 427, ??, ??, 681, 177**, used: **556, 190, 209, 255, 266, 584, 595, 595, 597, 597, 598, 599**
- mass_symbol* (label), **226, 178**, used: **560**
- matching*, **56**, used:
- matmul*, **789, 789**, used:
- matmulv*, **790, 789**, used: **774**
- Matter*, **210, 239, 255, 266, 273, 331, 342, 360, 372, 397, 414, ??, ??, 179**, used: **239, 256, 266, 273, 331, 342, 361, 372, 397, 414, ??, ??**
- matter_field*, **210, 239, 255, 266, 273, 331, 342, 360, 372, 397, 414, ??, ??, 179**, used: **239, 256, 266, 269, 269, 273, 273, 331, 342, 361, 372, 397, 414, ??, ??**
- matter_field* (type), **210, 239, 255, 266, 273, 331, 341, 360, 372, 397, 414, ??, ??, ??, 179**, used: **210, 210, 239, 255, 255, 266, 273, 273, 331, 331, 341, 342, 360, 360, 372, 372, 397, 397, 414, ??, ??, ??, ??, 179, 179**
- maxabsval*, **790**, used: **791**
- max_arity*, **9, 11, 12, 13, 16, 16, 18, 27, 34, 6, 8**, used: **16, 17, 17, 17, 25, 34**
- max_degree*, **225, 556, 188, 206, 209, 229, 230, 232, 235, 247, 255, 262, 266, 464, 499, 534, 289, 310, 325, 337, 350, 367, 377, 388, 407, 422, ??, ??, 679, 176**, used: **556, 188, 206, 209, 107, 118, 266**
- max_degree* (label), **226, 178**, used:
- max_ew_order*, **99**, used: **99, 100**
- max_generations*, **265**, used: **265, 267**
- max_qcd_order*, **99**, used: **99, 100**
- max_subtree*, **21, 25, 27, 27, 27, 34, 35, 19**, used: **27, 27, 113**
- maybe_backtrace*, **??**, used: **??, ??**
- Maybe_Graded* (module), **45**, used: **49, 49**
- maybe_read*, **695, 697, 694**, used: **107**
- md5sum*, **570**, used: **570, 617, 618**
- mem*, **713, 716, 721, 727, 728, 729, 730, 732, 44, 45, 49, 712, 725, 726, 726**, used: **??, 716, 721, 744, 729, 732, 772, 45, 46, 46, 46, 49, 223, 224, 664, 77, 78, 79, 125, 134, 596, 599**
- merge*, **715, 688, 660, 663, 688, 660**, used: **715, 716, 716, 716, 716, 674**
- merge_overlapping*, **218**, used: **218, 218**
- merge_partitions*, **218**, used: **218**

- merge_sets*, **662**, used: **662**
mgm, **239, 260, 279, 335, 347, 365, 376, 402, 414, ??**,
 used: **239, 260, 261, 261, 261, 261, 279, 279, 279, 279, 280, 280, 335, 335, 335, 335, 348, 348, 348, 348, 365, 365, 365, 376, 376, 376, 376, 402, 402, 402, 403, 414, ??, ??, ??, ??, ??, ??, ??, ??**
mhm, **279**, used: **280, 281, 281**
min, **29**, used: **701, 553**
minimal_fusion_tower, **113**,
 used: **118**
MINUS, **??, ??**, used: **??, 551**
MINUS (camlyacc token), **552**,
 used: **552, 552**
minus_gauge4, **239, 262, 448, 493, 527, 282, 303, 323, 336, 349, 366, 377, 391, 405, 414, ??, ??**, used:
239, 448, 493, 527, 282, 282, 303, 303, 323, 336, 349, 366, 377, 391, 391, 391, 405, 414, ??, ??
min_max_rank, **44, 45, 46, 49, 49, 41**, used: **46, 111**
mismatch, **56, 62**, used: **56, 57, 57, 58, 58, 58, 59, 59, 61, 63, 63, 64, 64, 64, 64, 65**
Mismatch, **85**, used: **696, 56, 62, 86, 86**
Mismatch (exn), **695, 696, 55, 56, 62, 129, 130, 694, 52, 92**, used:
52, 92
Mismatched_arity (exn), **10, 11, 12, 15, 16, 8**, used:
12, 15, 16, 8
Miss, **695, 696, 694**, used: **697**
Mixed23 (module), **13, 27, 129, 8, 20, 92**, used: **27, 129, ??, 675, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, 681, 20**
Mixed23 (sig), **13, 8**, used: **8**
Mixed23_Majorana (module),
129, 92, used: **??, ??, ??, ??, ??, ??, ??, ??, ??**
mixed_fold_left, **112**, used: **112**
mk_and, **70, 69**, used: **??, 76, 72**
mk_any_flavor, **70, 69**, used: **??, 72**
mk_false, **70, 69**, used:
70, 69
mk_gauss, **70, 69**, used: **??, 72**
mk_gauss_not, **70, 69**, used: **??, 72**
mk_off_shell, **70, 69**, used: **??, 72**
mk_off_shell_not, **70, 69**, used:
??, 72
mk_on_shell, **70, 69**, used: **??, 72**
mk_on_shell_not, **70, 69**, used:
??, 72
mk_or, **70, 69**, used: **??, 72**
mk_true, **70, 69**, used: **??, 72**
Model (module), **556, 174, 553**,
 used: **661, 75, 185, 209, 213, 96, 96, 96, 98, 100, 103, 127, 130, 130, 670, 265, 563, 569, 181, 220, 660, 553, 74, 185, 185, 213, 92, 94, 94, 669, 227, 227, 227, 228, 429, 480, 510, 270, 271, 271**
Modellib_BSM (module), **271, 270**, used: **??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??**
Modellib_MSSM (module), **429, 429**, used: **??, ??, ??, ??**
Modellib_NMSSM (module),
480, 480, used: **??, ??, ??**
Modellib_PSSSM (module), **511, 510**, used: **??**
Modellib_SM (module), **228, 227**, used: **675, ??, 675, ??, ??, ??, ??, ??, ??, ??, ??**
Modeltools (module), **221, 220**,
 used: **556, 560, 228, 230, 232, 234, 239, 254, 260, 267, 440, 488, 519, 279, 300, 320, 335, 347, 365, 376, 392, 402, 414, ??, ??, 678**
modname, **382**, used: **384, 386, 388, 394**

- modules_of_amplitudes*, **621**,
used: **623, 623**
- modules_to_file*, **616**, used: **623**
- module_name*, **570**, used: **570**,
620, 621, 621
- module_name* (field), **615**, used:
615, 615, 620, 621, 621,
621, 622, 622, 623
- module_to_file*, **615**, used: **616**
- mod_float2*, **690**, used: **691**
- mom*, **239, 260, 335, 347, 365**,
414, ??, used: **244, 245**,
245, 246, 246, 335, 336,
348, 348, 365, 420, 421,
421
- MOM*, **140**, used:
- MOM5*, **140**, used:
- Momenta*, **563, 579, 180**, used:
671, 579
- momentum*, **95, 102, 103, 123**,
572, 89, used: **661, 110**,
123, 675, 584, 590, 595,
595, 596, 597, 597, 599,
599
- momentum* (field), **102, 103**,
used: **103, 103, 104, 105**,
109, 110, 111, 114, 119,
119, 119, 120, 121, 124,
125, 125, 126, 126
- momentum* (type), **654, 655**,
653, used: **654, 656, 656**,
658, 653, 653, 653
- momentum* (camlyacc
non-terminal), **73**, used:
73
- Momentum*, **551**, used: **551**
- Momentum* (module), **55, 51**,
used: **655, 661, 75, 96, 98**,
100, 103, 130, 130, 669,
669, 675, 563, 569, 181,
653, 660, 74, 92, 94, 94,
669
- momentum_list*, **95, 102, 103**,
123, 89, used: **123, 670**,
572, 572, 580, 596
- momentum_list* (camlyacc
non-terminal), **73**, used:
72, 73
- momentum_to_string*, **76**, used:
76
- MOML*, **140**, used:
- MOMR*, **140**, used:
- Mono* (sig), **9, 6**, used: **10, 12, 8**,
8
- MSSM* (module), **431, 429**,
used: **??, ??, ??, ??**
- MSSM_flags* (sig), **429, 429**,
used: **430, 430, 430, 430**,
430, 430, 431, 429
- MSSM_goldstone* (module), **430**,
429, used:
- MSSM_Grav* (module), **430**,
429, used: **??**
- MSSM_Hgg* (module), **430, 429**,
used: **??**
- MSSM_no_4* (module), **430**,
429, used: **??**
- MSSM_no_4_ckm* (module),
430, 429, used: **??**
- MSSM_no_goldstone* (module),
430, 429, used:
- Mu*, **436, 486**, used:
- mul*, **782, 783, 783, 783, 785**,
786, 779, 780, 780,
used: **785, 786, 786, 786**,
786, 786, 787
- mul1*, **785**, used: **785, 785, 785**
- MULT*, **??, ??**, used: **??, 551**
- MULT* (camlyacc token), **552**,
used: **552, 552**
- Multi* (module), **130, 94**, used:
670, 563, 569, 181
- Multi* (sig), **129, 92**, used: **130**,
94
- multinomial*, **749, 745**, used:
- multiple_variable*, **572**, used:
584, 590, 595, 596
- multiple_variables*, **573**, used:
573
- multiplicity*, **30, 129, 131, 93**,
used: **31, 31, 32, 580**
- multiplicity* (field), **130**, used:
131, 136
- multiply*, **704, 550, 699, 549**,
used: **550, ??, 552**
- multi_choose*, **753, 747**, used:
- Multi_File*, **569**, used: **570**
- Multi_Maker* (sig), **130, 94**,
used: **94**

multi_split, **751, 746**, used: **751, 753**
multi_split', **750**, used: **750, 751, 751**
mult_vertex, **192**, used: **194, 195, 196, 198, 198, 200, 200, 201, 201, 203, 203, 204**
mult_vertex3, **190**, used: **192**
mult_vertex4, **191**, used: **192**
mult_vertexn, **192**, used: **192**
Muon, **231**, used: **231, 231, 232, 232**
Mutable (module), **225, 220**, used: **556**
Mutable (sig), **177**, used: **220**
M_N, **436**, used:
M_SF, **436**, used:
M_U, **436**, used:
M_V, **436**, used:
n (field), **658**, used:
N, **239, 255, 432, 483, 514, 273, 295, 317, 331, 341, 360, 372, 397, 414, ??, ??**, used: **239, 245, 245, 247, 256, 257, 259, 261, 261, 262, 433, 435, 439, 441, 441, 442, 443, 445, 446, 447, 461, 461, 465, 483, 485, 488, 489, 490, 491, 492, 499, 514, 516, 520, 520, 522, 523, 523, 525, 525, 525, 525, 534, 273, 275, 279, 279, 280, 280, 281, 289, 296, 297, 300, 301, 301, 302, 310, 317, 318, 321, 321, 322, 322, 325, 331, 333, 335, 335, 335, 338, 342, 344, 348, 348, 348, 350, 361, 362, 365, 365, 367, 372, 373, 376, 376, 378, 397, 399, 402, 403, 407, 414, 421, 421, 422, ??, ??, ??, ??, ??, ??, ??, ??, ??**
N1, **432, 482, 513**, used: **433, 444, 444, 445, 448, 448, 462, 462, 463, 465, 483, 491, 492, 498, 499, 514, 523, 523, 533, 534**
N10, **513**, used: **514, 534**
N11, **513**, used: **514, 534**
N2, **432, 482, 513**, used: **433, 444, 444, 445, 448, 448, 462, 462, 463, 465, 483, 491, 492, 498, 499, 514, 523, 523, 533, 534**
N3, **432, 482, 513**, used: **433, 444, 444, 445, 448, 448, 462, 462, 463, 465, 483, 491, 492, 498, 499, 514, 523, 523, 533, 534**
N4, **432, 482, 513**, used: **433, 444, 444, 445, 448, 448, 462, 462, 463, 465, 483, 491, 492, 498, 499, 514, 523, 523, 533, 534**
N5, **482, 513**, used: **483, 491, 492, 498, 499, 514, 523, 523, 533, 534**
N6, **513**, used: **514, 534**
N7, **513**, used: **514, 534**
N8, **513**, used: **514, 534**
N9, **513**, used: **514, 534**
name, **685, 684**, used: **686, 107, 107, 265, 612**
name (field), **685**, used: **685**
Nary (module), **16, 25, 129, 8, 20, 92**, used: **18, 25, 27, 34, 34, 129, 129, 20, 21**
Nary (sig), **15, 8**, used: **8, 8**
Nary4 (module), **27**, used: **27, 27**
Nary-Majorana (module), **129, 92**, used:
nc, **188, 209, 676, 180, 180**, used: **194, 195, 198, 209, 618, 677**
nc_coupling, **239, 260, 414**, used: **239, 260, 414**
nc_parameter, **572**, used: **605, 606, 618**
nc_value, **188**, used: **188**
neg, **782, 783, 783, 786, 786, 55, 57, 63, 550, 779, 780, 52, 549**, used: **786, 787, 788, 57, 58, 58, 60, 63, 64, 64, 65, 659, ??, 75, 77, 78, 79, 124, 552**
Neg, **383, 168**, used: **239, 260, 260, 260, 384, 386, 389,**

- 389, 389, 389, 390, 390,
390, 390, 391, 391, 391,
391, 391, 391, 393, 395,
414
neg', **57**, used: 57, 57
negate, **550**, used: 550, 550, 550
Negative (exn), **55, 58, 63, 52**,
used:
Negative_Coupling_Order (exn),
99, used:
neu (type), **432, 482, 513**, used:
432, 436, 483, 486, 514,
517
Neutralino, **432, 483, 514**, used:
433, 435, 441, 442, 444,
444, 444, 444, 445, 448,
448, 462, 465, 483, 485,
489, 490, 491, 491, 491,
499, 514, 516, 520, 521,
522, 522, 523, 526, 526,
534
neutral_currents, **239, 261, 441**,
488, 520, 279, 300, 321,
335, 348, 365, 376, 402,
414, ??, ??, used: 246,
262, 462, 498, 533, 289,
310, 325, 337, 350, 367,
377, 407, 422, ??, ??
neutral_currents', ??, used: ??
neutral_heavy_currents, **279**,
301, 322, ??, used: 289,
310, 325, ??
neutral_sfermion_currents, **442**,
490, 521, used: 462, 498,
533
neutral_sfermion_currents', **442**,
490, 521, used: 442, 490,
521
neutral_up_type_currents, ??,
used: ??
neutral_Z, **490, 521**, used: 498,
533
neutral_Z_1, **442**, used: 462
neutral_Z_2, **442**, used: 462
neutr_lqino_current, **527**, used:
533
NH, **317**, used: 317, 318, 321,
322, 325
nl, **641, 571**, used: 641, 573, 575,
575, 575, 577, 577, 577,
577, 577, 577, 577, 580,
580, 580, 595, 595, 596,
596, 596, 598, 599, 599,
599, 600, 600, 600, 601,
601, 601, 601, 602, 602,
602, 603, 603, 604, 605,
606, 606, 607, 607, 607,
608, 608, 608, 609, 609,
609, 609, 609, 610, 610,
610, 612, 614, 614, 615,
615, 615, 616, 616, 617,
617, 618, 618, 618, 619,
619, 622, 622
nlist, **514**, used: 514, 533
NMSSM (module), **480, 480**,
used: ??
NMSSM_CKM (module), **481**,
480, used: ??
NMSSM_flags (sig), **480, 480**,
used: 480, 481, 481, 481,
480
NMSSM_func (module), **481**,
480, used: ??, ??, ??
NMSSM_Hgg (module), **481**,
480, used: ??
Nodd, **295**, used: 296
node, **766, 764**, used:
node (field), **771**, used: 771
node (type), ??, **41, 41, 42, 43**,
44, 45, 111, ??, 37, 38,
40, used: ??, 41, 41, 42,
43, 43, 45, 49, 102, ??,
??, 37, 37, 37, 38, 38, 38,
38, 38, 38, 38, 39, 39, 39,
39, 39, 39, 39, 39, 40, 40,
40, 41, 41
Node, **713, 776, 765**, used: 714,
714, 714, 716, 717, 718,
718, 719, 776, 765, 766,
766, 767, 767, 768
nodes, **766, 764**, used: 766, 771
Nodes (module), **41, 42, 43, 44**,
111, 37, 40, used: 41, 42,
43, 44, 45, 46, 46, 46, 47,
48, 111, 37, 40, 40, 41
node_to_string, **767**, used: 768
node_with_tension (type), **771**,
used:
NOT, ??, ??, used: ??, 71

- NOT* (camlyacc token), **72**, used:
72, 72
- Not_invertible* (exn), **772**, used:
- Not_Square* (exn), **789, 789**,
used:
- no_cascades*, **74, 77, 73**, used:
80, 675
- No_Tags* (module), **98**, used:
- No_termination* (exn), **10, 12**,
15, 17, 8, used:
- no_write*, **570**, used: **570, 577**
- null*, **782, 783, 783, 784, 785**,
787, 99, 779, 780, 781,
used: **786, 786, 786, 786**,
786, 786, 787, 787, 787,
184, 100
- Null* (module), **183, 182**, used:
225, 228, 230, 678, 227
- null_coupling*, **98, 98, 99, 100**,
94, used: **110, 114**
- null_wf*, **98, 98, 99, 100, 94**,
used: **103, 109, 110, 114**
- num* (field), **84, 85, 82**, used: **87**
- num_color_flows*, **601**, used: **617**
- num_color_indices*, **601**, used:
617
- num_color_indices_default*, **601**,
used: **601**
- num_ext*, **30**, used: **30**
- num_flavors*, **602**, used: **607, 617**
- num_fusions_brackets*, **616**, used:
616
- num_helicities*, **600**, used: **617**,
618
- num_particles*, **600**, used: **602**,
617
- num_particles_in*, **600**, used: **617**
- num_particles_out*, **600**, used:
617
- num_prop*, **30**, used: **30**
- N_K1*, **341**, used: **342, 344, 350**
- N_K2*, **341**, used: **342, 344, 350**
- o* (type), **225, 556, 220**, used:
225, 220
- O*, **239, 255, 266, 273, 331**,
341, 360, 372, 397, 414,
??, ??, used: **239, 239**,
239, 239, 239, 241, 241,
242, 243, 243, 243, 244,
244, 244, 244, 245, 245,
245, 246, 246, 247, 255,
257, 260, 261, 262, 266,
267, 273, 275, 275, 279,
288, 288, 288, 289, 331,
332, 333, 335, 336, 336,
336, 336, 336, 337, 337,
337, 338, 342, 344, 344,
347, 349, 349, 349, 349,
349, 349, 349, 350, 350,
360, 362, 362, 365, 366,
366, 366, 366, 366, 366,
367, 367, 367, 372, 373,
373, 376, 377, 377, 377,
377, 377, 378, 397, 398,
399, 403, 403, 403, 403,
403, 404, 404, 404, 405,
406, 406, 407, 407, 407,
414, 414, 414, 414, 414,
415, 416, 416, 417, 417,
417, 417, 418, 419, 419,
419, 420, 420, 420, 420,
421, 421, 421, 422, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??
- O* (module), **675, ??, 675, ??**,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??
- Ocaml* (module), **638, 563**, used:
- of2*, **10, 11, 13, 14, 15, 16, 8, 8**,
8, used: **11, 11, 15, 15, 17**,
24, 27, 35
- of2_kludge*, **9, 11, 13, 15, 17, 7**,
used: **113**
- of3*, **12, 12, 13, 14, 15, 16, 8, 8**,
8, used: **13, 15, 27, 27**
- Off*, **579**, used: **579**
- OFFSHELL*, **??, ??**, used: **??, 71**
- OFFSHELL* (camlyacc token),
72, used: **72**
- Offspring* (module), **46**, used: **46**,

- 46, 46, 46, 46, 47, 47, 47,
47, 47, 47, 48, 48
- Off_shell*, **70, 75, 69**, used: **70**,
76
- Off_shell_not*, **70, 75, 69**, used:
70, 76
- of_array*, **755, 755, 756, 754**,
used:
- of_int*, **28, 29, 20**, used: **29, 33**,
34
- of_ints*, **55, 56, 62, 51**, used: **60**,
67, 658, 659, 659, 76, 109
- of_list*, **??, ??, ??, 723, 723**,
755, 755, 756, 739, 739,
740, 740, 15, 16, 84, 85,
??, 722, 754, 738, 738,
8, 81, used: **??, ??, 723**,
723, 704, 707, 755, 755,
756, 756, 756, 757, 757,
757, 758, 758, 758, 758,
758, 758, 759, 740, 772,
773, 774, 17, 27, 34, 209,
218, 122, 135
- of_lists*, **723, 723, 742, 743**,
722, 741, used: **79, 218**
- of_list_gap*, **757**, used: **758**
- of_list_ok*, **758**, used: **758**
- of_list_overlap*, **757**, used: **758**
- of_momenta*, **654, 659, 653**,
used:
- of_momentum*, **67, 67, 67, 54**,
used: **67, 662, 663, 664**
- of_string*, **76**, used: **76**
- of_string_list*, **74, 76, 73**, used:
673
- of_subarray*, **701, 698**, used:
- of_vertices*, **221, 224, 220**, used:
560, 229, 232, 235, 247,
255, 262, 269, 464, 499,
534, 289, 310, 325, 337,
350, 367, 377, 392, 407,
422, ??, ??, 679
- Omega* (module), **669, 669**, used:
675, ??, 675, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
681
- Omega_2HDM* (module), **??**,
used:
- Omega_2HDM_CKM* (module),
??, used:
- omega_color_factor_abbrev*, **572**,
used: **605, 606, 610, 617**
- Omega_GravTest* (module), **??**,
used:
- Omega_Littlest* (module), **??**,
used:
- Omega_Littlest_Eta* (module),
??, used:
- Omega_Littlest_Tpar* (module),
??, used:
- Omega_MSSM* (module), **??**,
used:
- Omega_MSSM_CKM* (module),
??, used:
- Omega_MSSM_Grav* (module),
??, used:
- Omega_MSSM_Hgg* (module),
??, used:
- Omega_NMSSM* (module), **??**,
used:
- Omega_NMSSM_CKM* (module),
??, used:
- Omega_NMSSM_Hgg* (module),
??, used:
- Omega_PSSSM* (module), **??**,
used:
- omega_public_symbols*, **617**,
used: **617**
- Omega_QCD* (module), **??**, used:
- Omega_QED* (module), **675**,
used:
- Omega_Simplest* (module), **??**,
used:
- Omega_Simplest_univ* (module),
??, used:
- Omega_SM* (module), **675**, used:
- Omega_SM_ac* (module), **??**,
used:
- Omega_SM_ac_CKM* (module),
??, used:
- Omega_SM_CKM* (module), **??**,
used:
- Omega_SM_Higgs* (module), **??**,
used:

- Omega_SM_km* (module), ??,
used:
- Omega_SM_QCD* (module), ??,
used:
- Omega_SM_top* (module), ??,
used:
- Omega_SM_top_anom* (module),
??, used:
- Omega_SYM* (module), **675**,
used:
- Omega_Template* (module), ??,
used:
- Omega_Threshl* (module), ??,
used:
- Omega_Threshl_nohf* (module),
??, used:
- Omega_UED* (module), ??, used:
- Omega_VBS* (module), ??, used:
- Omega_Xdim* (module), ??, used:
- Omega_Zprime* (module), ??,
used:
- one*, **785, 28, 29, 20**, used: **785**,
786, 30, 31, 33, 33
- one_compatible*, **75**, used: **75, 77**
- Only_Insertion*, **139**, used: **239**,
434, 274, 297, 318, 332,
343, 362, 373, 398, 414,
??, ??
- ONHELL*, ??, ??, used: ??, **71**
- ONHELL* (camlyacc token), **72**,
used: **72**
- on_shell*, **74, 77, 95, 102, 105**,
123, 74, 91, used: **119**,
123, 595
- on_shell* (field), **77, 102, 105**,
used: **77, 77, 80, 105, 114**,
119, 122
- On_shell*, **70, 75, 69**, used: **70**,
76
- On_shell_not*, **70, 75, 69**, used:
70, 76
- openmp*, **687, 570, 687**, used:
570, 572, 572, 580, 609,
616, 616, 618, 619, 619,
622, 622
- openmp_tld*, **572**, used: **572, 572**,
580, 616, 616, 618, 619,
622, 622
- openmp_tld_type*, **572**, used: **580**,
616, 616, 622, 622
- open_file*, **691, 690**, used:
- Open_File*, **690**, used: **691**
- open_in_bin_first*, **696**, used:
696
- Open_line* (exn), **83, 83**, used:
- open_out_bin_last*, **696**, used:
696
- options*, **225, 561, 186, 209, 95**,
98, 98, 99, 99, 101, 129,
130, 228, 229, 231, 233,
239, 254, 255, 266, 431,
481, 511, 272, 295, 317,
330, 341, 360, 371, 382,
397, 414, 563, 570, ??,
??, **676, 177, 180, 89**,
92, 94, used: **186, 209**,
101, 130, 671, 254, 266
- Options* (module), **688, 688**,
used: **225, 561, 95, 98, 98**,
99, 99, 101, 129, 130, 671,
228, 229, 231, 233, 239,
255, 431, 481, 511, 272,
295, 317, 330, 341, 360,
371, 382, 397, 414, 563,
570, ??, ??, 676, 177, 180,
89, 92, 94
- option_to_logical*, **607**, used:
607, 607
- Or*, **70, 69**, used: **70**
- OR*, ??, ??, used: ??, **71**
- OR* (camlyacc token), **72**, used:
72, 72
- Ord* (sig), **41, 36**, used: **41, 42**,
42, 43, 43, 43, 44, 37, 37,
40, 40
- ordered_multi_choose*, **753, 747**,
used:
- ordered_multi_split*, **751, 746**,
used: **753**
- ordered_partitions*, **751, 746**,
used:
- ordered_partitions'*, **751**, used:
751, 751
- ordered_split*, **750, 746**, used:
750, 751
- ordered_split_unsafe*, **749**, used:
750, 750

- Ordered_Type* (sig), **742, 741**,
 used: **742, 742**
- orders*, **225, 556, 186, 209, 228,**
229, 231, 233, 239, 254,
259, 266, 438, 488, 519,
278, 300, 320, 335, 347,
365, 375, 388, 402, 414,
??, ??, 677, 176, used:
556, 186, 209, 254, 266
- orders* (type), **225, 556, 186,**
209, 99, 228, 229, 231,
233, 239, 254, 259, 266,
438, 487, 519, 278, 300,
320, 334, 347, 365, 375,
388, 402, 414, ??, ??,
677, 176, used: **556, 186,**
209, 100, 254, 266, 176,
220, 185, 185
- orders_in_bounds*, **100**, used:
- order_flavor*, **103**, used: **104**
- order_spin_table*, **132**, used: **132**
- order_spin_table1*, **131**, used:
131, 132
- Order_Tags* (module), **99**, used:
126
- order_wf*, **102, 104**, used: **105,**
105, 111, 112, 121, 125
- other*, **211, 239, 255, 266, 273,**
331, 342, 360, 372, 397,
414, ??, ??, 179, used:
239, 256, 266, 273, 331,
342, 361, 372, 397, 414,
??, ??
- other* (type), **210, 239, 255,**
266, 273, 331, 341, 360,
372, 397, 414, ??, ??,
179, used: **210, 210, 239,**
255, 255, 266, 273, 273,
331, 331, 341, 342, 360,
360, 372, 372, 397, 397,
414, ??, ??, ??, ??, 179,
179
- Other*, **210, 239, 255, 266, 273,**
331, 342, 360, 372, 397,
414, ??, ??, 179, used:
239, 256, 266, 273, 331,
342, 361, 372, 397, 414,
??, ??
- OUnit* (module), **??, ??**, used:
??, 723, 723, 757, 757,
723, 755
- OUnitDiff* (module), **??, ??**,
 used:
- out* (field), **661**, used:
- outer*, **736, 734**, used:
- outer_self*, **736, 734**, used:
- outgoing*, **55, 59, 60, 65, 65,**
213, 213, 95, 102, 105,
123, 53, 54, 212, 91,
 used: **123, 131, 131, 580,**
599, 599, 599
- outgoing* (field), **102, 105**, used:
105, 114, 119, 122, 122
- output_mode*, **570**, used: **570,**
623
- output_mode* (type), **569**, used:
- out_ghost_flags*, **84, 85, 81**,
 used:
- Out_of_bounds* (exn), **704, 699**,
 used:
- out_to_lists*, **84, 85, 81**, used:
601
- overlapping*, **217**, used: **218**
- overlapping_flavor_sums*, **218**,
 used: **218**
- Overlapping_indices* (exn), **704,**
699, used:
- p* (field), **56**, used: **56, 57, 57, 58,**
58, 58, 59, 59
- p* (type), **74, 75, 95, 102, 103,**
123, 130, 73, 89, used:
74, 75, 77, 95, 96, 98, 102,
102, 103, 103, 123, 130,
74, 74, 74, 74, 74, 89, 92,
94
- P*, **140**, used: **442, 443, 443, 443,**
444, 444, 490, 521, 281,
281, 302, 302, 323
- P* (module), **723, 669**, used: **723,**
670
- P1*, **483, 513**, used: **483, 490,**
491, 491, 494, 495, 497,
498, 499, 514, 522, 522,
523, 528, 529, 531, 532,
533, 534
- P123*, **192**, used: **204**
- P132*, **192**, used: **204**
- P2*, **483, 513, 140**, used: **483,**
490, 491, 491, 494, 495,
497, 498, 499, 514, 522,

- 522, 523, 528, 529, 531,
532, 533, 534
- P213*, 192, used: 204
- P231*, 192, used: 204
- p2s*, 126, 670, 572, used: 126,
670, 572, 572
- P3*, 27, 513, used: 27, 514, 533,
534
- P312*, 192, used: 204
- P321*, 192, used: 204
- P4*, 27, 513, used: 27, 514, 533,
534
- P5*, 513, used: 514, 533, 534
- P6*, 513, used: 514, 533, 534
- P7*, 513, used: 514, 533, 534
- pack_map*, 662, used: 663
- pack_tree*, 662, used: 662
- pair*, 132, used: 133
- pairs*, 760, 481, 512, 760, used:
11, 15, 22, 35, 482, 482,
495, 498, 512, 512, 529,
533
- pairs'*, 760, used: 760, 760
- pair-or-triple* (type), 13, 8,
used: 13
- panic*, 579, used: 579
- Panic*, 579, used: 579
- parameters*, 225, 556, 188, 209,
229, 230, 232, 235, 239,
255, 260, 266, 440, 488,
519, 278, 300, 320, 335,
347, 365, 376, 393, 402,
414, ??, ??, 679, 177,
used: 556, 188, 209, 255,
266, 624
- parameters* (label), 226, 178,
used: 560
- parameters* (type), 574, 173,
used: 177, 178
- parameters_to_channel*, 563,
624, 181, used: 673
- parameters_to_fortran*, 577,
used: 624
- parameter_module*, 570, used:
570, 577, 617
- Parents* (module), 46, used: 46,
46, 46, 46, 46, 46, 46,
46, 47, 47, 47, 47, 47, 47,
47, 47, 47, 48, 48, 48
- parse*, 686, 688, 684, 688, used:
??, 760, 9, 21, 41, 55, 221,
660, 553, 185, 95, 671,
228, 429, 480, 511, 271,
640, 563, ??, ??, 675
- parse1*, 685, used: 686
- parse_color*, 559, used: 559
- parse_decay*, 213, 215, 212,
used: 672
- parse_diagnostic*, 579, used: 579,
579
- parse_diagnostics*, 579, used: 623
- parse_error*, ??, 72, used: ??,
??, ??, ??
- parse_expr*, 558, used: 558, 558,
559
- parse_function_row*, 558, used:
559
- parse_lagrangian_row*, 558, used:
559
- parse_particle_row*, 559, used:
559
- parse_process*, 213, 214, 212,
used: 215, 215
- parse_scattering*, 213, 215, 212,
used: 672
- parse_source*, 685, used: 686
- parse_spin*, 559, used: 559
- parse_symbol*, 558, used: 559
- parse_table*, 559, used: 559
- parse_variable_row*, 559, used:
559
- partial*, 784, 787, 781, used:
- Partial* (module), 723, 722,
used:
- particle* (type), 557, used:
- particles_file*, 561, used: 561, 561
- particle_flavor* (type), 557, used:
- partition*, 25, 34, 74, 77, 74,
used: 744, 25, 34, 134
- partition* (field), 77, used: 77, 77
- partition* (type), 21, 22, 25, 27,
27, 34, 35, 19, used: 21,
19, 20
- Partition* (module), 760, 760,
used: 11, 13, 15, 17, 22,
25, 34, 35
- partitioned_sort*, 704, 699, used:
218

- partitions*, **751, 21, 23, 25, 27, 27, 34, 35, 746, 19**,
used: **752, 25, 27, 27, 27, 34, 34, 35**
- partitions'*, **751, 22, 25, 34**,
used: **751, 751, 752, 22, 23, 25, 25, 34, 34**
- partition_to_string*, **79**, used: **80**
- part_to_string*, **79**, used: **79**
- path* (type), **??, ??, used: ??, ??, ??, ??, ??, ??**
- PBP*, **140**, used: **190, 446, 446, 492, 492, 523, 524, 525, 525**
- pdg*, **225, 556, 186, 209, 229, 230, 233, 236, 251, 255, 264, 266, 469, 504, 540, 292, 313, 328, 340, 358, 370, 380, 385, 410, 426, ??, ??, 681, 174**, used:
556, 186, 209, 233, 233, 236, 236, 251, 252, 255, 265, 265, 266, 292, 292, 314, 314, 340, 340, 359, 359, 371, 371, 380, 380, 410, 410, 427, 427, 601, 602, ??, ??, ??, ??
- pdg* (label), **226, 178**, used: **560**
- pdg_heuristic*, **555**, used: **558, 558**
- pdg_mw*, **472, 507, 544, 329**,
used: **472, 472, 507, 507, 545, 545, 329, 329**
- perform_test*, **??, ??, used: ??**
- permutation*, **97, 128**, used: **98, 128**
- Permutation* (module), **755, 754**,
used:
- permutation4* (type), **192**, used:
- permutation_symmetry*, **33**, used:
33
- permute*, **753, 747**, used: **754, 207**
- permute3*, **223**, used: **223**
- permute4*, **224**, used: **224**
- permute_contract4*, **192**, used:
193
- permute_contract4_list*, **193**,
used: **193**
- permute_even*, **753, 747**, used:
- permute_odd*, **753, 747**, used:
- permute_signed*, **753, 747**, used:
753, 753, 754
- permute_signed'*, **753**, used: **753, 753**
- permute_tensor*, **754, 747**, used:
- permute_tensor_even*, **754, 747**,
used:
- permute_tensor_odd*, **754, 747**,
used:
- permute_tensor_signed*, **754, 747**, used: **754, 754**
- permute_vertex4*, **193**, used: **204**
- permute_vertex4'*, **193**, used: **193**
- Phasespace* (module), **654, 653**,
used:
- Phi*, **228, 229, 676**, used: **228, 229, 229, 229, 230, 230, 230, 676, 678, 679**
- Phi0*, **239, 432, 273, 295, 317, 331, 341, 360, 372, 397, 414, ??, ??**, used: **239, 242, 433, 435, 435, 443, 443, 444, 449, 450, 452, 453, 454, 455, 457, 458, 458, 465, 273, 275, 275, 289, 296, 297, 297, 310, 317, 318, 318, 325, 331, 332, 333, 337, 342, 344, 344, 350, 361, 362, 362, 367, 372, 373, 373, 377, 397, 398, 399, 407, 414, 416, ??, ??, ??, ??, ??, ??, ??, ??, ??**
- Phi3* (module), **228, 227**, used:
- Phi4* (module), **229, 227**, used:
- phiggs* (type), **483, 513**, used:
483, 486, 514, 517
- PHiggs*, **483, 514**, used: **483, 485, 490, 491, 491, 493, 493, 494, 494, 495, 495, 497, 498, 499, 514, 516, 521, 522, 522, 526, 526, 528, 528, 529, 529, 529, 531, 532, 534**
- phiggs_neutr*, **491, 522**, used:
491, 523
- Phim*, **239, 432, 273, 295, 317, 331, 341, 360, 372, 397, 414, ??, ??**, used: **239,**

- 242, 433, 435, 435, 443,
443, 444, 449, 450, 452,
453, 454, 455, 456, 457,
458, 458, 465, 273, 275,
275, 289, 296, 297, 297,
310, 317, 318, 318, 325,
331, 332, 333, 337, 342,
344, 344, 350, 361, 362,
362, 367, 372, 373, 373,
377, 397, 398, 399, 407,
414, 416, ??, ??, ??, ??,
??, ??, ??, ??
- Phino*, 360, used: 361, 362, 367,
367
- Phip*, 239, 432, 273, 295, 317,
331, 341, 360, 372, 397,
414, ??, ??, used: 239,
242, 433, 435, 435, 443,
443, 444, 449, 450, 452,
453, 454, 455, 456, 457,
458, 458, 465, 273, 275,
275, 289, 296, 297, 297,
310, 317, 318, 318, 325,
331, 332, 333, 337, 342,
344, 344, 350, 361, 362,
362, 367, 372, 373, 373,
377, 397, 398, 399, 407,
414, 416, ??, ??, ??, ??,
??, ??, ??, ??
- Photon*, 231, used: 231, 231, 232,
232
- pi*, 740, 740, 740, 219, 120,
738, 738, used: 740, 740,
740
- Pi*, 239, 259, 436, 277, 298,
319, 334, 347, 364, 375,
400, 414, ??, ??, used:
239, 260, 414
- pivot_column*, 791, used: 791
- plist*, 514, used: 514
- PLUS*, ??, ??, ??, ??, used: ??,
??, 71, 551
- PLUS* (camlyacc token), 72, 552,
used: 72, 73, 552, 552
- PM* (module), 782, used: 784,
785, 785, 787, 787, 788
- Pmap* (module), 713, 712, used:
707, 731, 782, 772, 727
- PMap* (module), 707, used: 707
- poles*, 95, 125, 92, used: 662, 125
- Poles* (module), 661, used: 661,
661, 662, 663
- poles'*, 125, used: 125
- poles_beneath*, 125, used: 125
- poles_to_whizard*, 661, used: 662
- Pole_Map* (module), 662, used:
662, 662, 662
- Poly* (sig), 730, 10, 726, 8, used:
731, 10, 13, 15, 43, 98, 98,
99, 99, 100, 103, 727, 8, 8,
8, 37, 94
- Pos*, 383, used: 384, 386, 389,
389, 389, 389, 390, 390,
390, 390, 391, 391, 391,
391, 391, 391, 393, 395
- Positron*, 231, used: 231, 231,
232, 232
- POT*, 140, used: 366
- Pow*, 168, used:
- power*, 783, 784, 785, 735, 9,
11, 12, 15, 17, 550, 780,
734, 7, 549, used: 785,
786, 786, 786, ??, 676,
676, 676, 552
- power* (field), 84, 85, 82, used:
- power* (type), 84, 85, 82, used:
84, 85, 82
- POWER*, ??, ??, used: ??, 551
- POWER* (camlyacc token), 552,
used: 552, 552
- power_fold*, 9, 11, 12, 15, 17, 7,
used: 15, 106
- PowSet* (module), 742, 741,
used: 79, 218
- pp_comma_separator*, ??, ??,
used:
- pp_diff*, ??, ??, ??, ??, used: ??,
??
- pp_printer*, ??, ??, ??, ??, ??,
??, used: ??, ??, ??, ??,
??, ??
- pp_print_gen*, ??, used: ??, ??,
??
- pp_print_sep*, ??, ??, used: ??,
??, ??
- pred*, 28, 29, 20, used: 700, 700,
700, 700, 701, 703, 704,
704, 707, 756, 756, 789,
790, 791, 791, 792, 785,
748, 748, 748, 749, 750,

- 750, 752, 760, 761, 773,
775, 11, 13, 17, 17, 17, 25,
29, 31, 32, 32, 34, 34, 34,
35, 62, 63, 66, 67, 87, 553,
554, 554, 218, 218, 135,
482, 512, 605, 606, 607,
607, 612
- prepend_tofst_unsorted*, 750,
used: 751
- Pre_Bundle* (module), 216, used:
216
- print*, 641, 640, used: 618
- print_add_dscalar2_vector2*,
584, used: 592
- print_add_dscalar4*, 583, used:
592
- print_add_vector4*, 582, used:
590
- print_add_vector4_km*, 583,
used: 590
- print_amplitude_table*, 607, used:
618
- print_argument_diagnostics*,
598, used:
- print_braket*, 596, used: 596
- print_brackets*, 596, used: 616,
620, 622
- print_calculate_amplitudes*, 618,
used: 620, 620, 622
- print_color_factors*, 610, used:
618
- print_color_factor_table*, 606,
used: 606
- print_color_factor_table_old*,
605, used:
- print_color_flows*, 610, used: 618
- print_color_flows_table*, 603,
used: 606
- print_color_flows_table_old*, 602,
used:
- print_color_tables*, 606, used:
618
- print_compute_brackets1*, 616,
used: 621
- print_compute_chops*, 619, used:
620, 622
- print_compute_fusions1*, 616,
used: 621
- print_constants*, 617, used: 620,
620, 621
- print_current*, 564, 568, 584,
627, used: 584, 595, 595,
596
- print_current_b*, 564, 569, 627,
used: 584
- print_current_g*, 564, 569, 631,
used: 584
- print_current_g4*, 564, 569,
637, used: 590
- print_current_mom*, 564, 568,
631, used: 584
- print_current_p*, 564, 569, 627,
used: 584
- print_declarations* (field), 615,
used: 615
- print_description*, 612, used:
620, 621, 623, 623
- print_dispatch_functions*, 610,
used: 618
- print_dscalar2_vector2*, 583,
used: 584, 592
- print_dscalar4*, 583, used: 583,
592
- print_echo*, 577, used: 577
- print_echo_array*, 577, used: 577
- print_externals*, 599, used: 618
- print_external_momenta*, 599,
used: 618
- print_fermion_2_g4_current*,
634, 634, used: 637
- print_fermion_2_g4_current_rev*,
636, used: 637
- print_fermion_2_g4_vector_current*,
635, used: 637
- print_fermion_2_g4_vector_current_rev*,
636, used: 637
- print_fermion_current*, 566,
626, used: 568, 627, 627,
627
- print_fermion_current2*, 567,
626, used: 568, 627, 627,
627
- print_fermion_current2_chiral*,
627, used: 627
- print_fermion_current2_vector*,
626, used: 627
- print_fermion_current_chiral*,
627, used: 627
- print_fermion_current_mom*,
628, used: 631

- print_fermion_current_mom1*,
 567, used: 568
print_fermion_current_mom2,
 567, used: 568
print_fermion_current_mom_chiral,
 629, used: 631
print_fermion_current_mom_sign,
 629, used: 631
print_fermion_current_mom_sign_1,
 629, used: 631
print_fermion_current_mom_vector,
 628, used:
print_fermion_current_vector,
 626, used: 627
print_fermion_g4_brs_vector_current,
 632, used: 637
print_fermion_g4_current, 634,
 used: 637
print_fermion_g4_current_rev,
 635, used: 637
print_fermion_g4_svlr_current,
 632, used: 637
print_fermion_g4_vector_current,
 635, used: 637
print_fermion_g4_vector_current_rev,
 636, used: 637
print_fermion_g_2_current, 630,
 used: 631
print_fermion_g_2_current_rev,
 630, used: 631
print_fermion_g_current, 629,
 used: 631
print_fermion_g_current_rev,
 630, used: 631
print_fermion_g_current_vector,
 630, used: 631
print_fermion_g_current_vector_rev,
 630, used: 631
print_fermion_s2lr_current, 633,
 used: 637
print_fermion_s2p_current, 633,
 used: 637
print_fermion_s2_current, 632,
 used: 637
print_flavor_color_table, 607,
 used: 607
print_flavor_color_table_old,
 607, used:
print_flavor_table, 602, used:
 602
print_flavor_tables, 602, used:
 618
print_flavor_table_old, 601,
 used:
print_fudge_factor, 599, used:
 618
print_fusion, 595, used: 596
print_fusions, 596, used: 616,
 620, 622
print_fusion_diagnostics, 595,
 used: 596
print_gauss, 594, used: 595
print_ghost_flags_table, 604,
 used: 606
print_ghost_flags_table_old, 603,
 used:
print_helicity_selection_table,
 608, used: 618
print_implementations (field),
 615, used: 615, 621, 621,
 622, 622
print_incoming, 597, used: 599
print_inquiry_functions, 609,
 used: 618
print_inquiry_function_declarations,
 609, used:
print_inquiry_function_openmp,
 609, used: 618
print_integer_parameter, 600,
 used: 605, 606, 617
print_interface, 618, used: 620,
 620, 622
print_list, 571, used: 573, 575,
 580, 580, 598, 617
print_logical_parameter, 600,
 used: 618
print_maintenance_functions,
 608, used: 618
print_md5sum_functions, 608,
 used: 618
print_module, 615, used: 615
print_modules, 615, used: 615,
 620, 621, 623
print_momenta, 596, used: 618
print_numeric_inquiry_functions,
 609, 609, used: 618
print_outgoing, 597, used: 599
print_projector, 594, used: 595
print_propagator, 593, used: 595
print_public, 615, used: 615, 615

- print_public_interface*, **615**,
used:
- print_real_parameter*, **600**, used:
618
- print_spin_table*, **601**, used: **601**
- print_spin_tables*, **601**, used: **618**
- print_spin_table_old*, **601**, used:
- print_time*, **757**, used: **759**
- print_used_module*, **614**, used:
615
- print_used_symbol*, **614**, used:
614
- print_variable_declarations*, **580**,
used: **620, 620, 621**
- print_vector4*, **582**, used: **582**,
590
- print_vector4_km*, **582**, used:
583, 590
- print_version*, **614**, used: **615**
- Private*, **614**, used: **620, 621, 622**,
622, 623
- Proc* (module), **133, 670**, used:
134, 135, 672
- process* (type), **213, 214, 129**,
130, 212, 92, used: **213**,
129, 130, 131, 212, 93, 93,
93
- Process* (module), **213, 212**,
used: **133, 670**
- processes*, **129, 131, 93**, used:
580, 616, 616, 618, 620
- processes* (field), **130**, used: **131**,
136
- Process_Bundle* (module), **216**,
used: **218**
- process_sans_color*, **131**, used:
135, 135
- process_sans_color_to_string*,
599, used: **612**
- process_table*, **129, 131, 93**,
used: **607, 618**
- process_table* (field), **130**, used:
131, 136, 136
- process_to_string*, **131, 599**,
used: **135**
- Prod*, **168**, used: **239, 260, 260**,
260, 414
- product*, **743, 783, 783, 785**,
786, 9, 11, 12, 15, 16,
780, 781, 6, used: **744**,
11, 12, 121, 121
- Product*, **549, 549**, used: **550**,
550, 550
- Product* (module), **735, 734**,
used: **754, 754, 767, 11**,
11, 12, 13, 15, 16, 17, 17,
48, 663, 215, 216, 109,
110, 121, 124, 125, 125,
133, 239, 261, 441, 442,
445, 446, 446, 448, 450,
451, 451, 452, 454, 455,
455, 456, 456, 457, 458,
458, 459, 459, 460, 460,
460, 460, 460, 461, 462,
462, 463, 464, 489, 490,
490, 491, 492, 492, 492,
494, 496, 496, 496, 497,
497, 498, 498, 498, 521,
521, 522, 522, 523, 523,
524, 526, 526, 526, 526,
528, 530, 530, 530, 531,
532, 532, 532, 533, 414,
676, 676, 676
- product_fold*, **9, 11, 12, 15, 16**,
6, used: **11, 12, 15, 17**
- Progress* (module), **690, 690**,
used: **135, 135, 135**
- progress_mode* (type), **130**, used:
- progress_option*, **130**, used: **130**,
135
- project*, **266**, used: **266, 266, 267**,
267, 267, 267, 269, 269
- Projection* (sig), **740, 738**, used:
740, 738
- prop* (field), **30**, used: **30, 31, 31**,
31, 31
- propagator*, **225, 556, 187, 209**,
228, 229, 231, 234, 239,
254, 257, 266, 434, 484,
515, 274, 297, 318, 332,
343, 362, 373, 386, 398,
414, ??, ??, 677, 176,
used: **556, 187, 209, 105**,
254, 266, 593, 594, 594,
595
- propagator* (label), **226, 178**,
used: **560**

- propagator* (type), **139**, used:
 557, 176, 178
propagator_of_lorentz, **557**,
 used: 558, 558
prop_aux, **239, 257, 414**, used:
 239, 414
Prop_Col_Feynman, **139**, used:
 187
Prop_Col_Majorana, **139**, used:
 187
Prop_Col_Scalar, **139**, used: 187
Prop_Col_Unitarity, **139**, used:
 187
Prop_ConjSpinor, **139**, used:
 557, 231, 234, 239, 257,
 434, 484, 515, 274, 274,
 297, 297, 318, 332, 343,
 362, 373, 386, 398, 414,
 ??, ??, 677
Prop_Feynman, **139**, used: 557,
 231, 234, 239, 257, 434,
 484, 515, 274, 297, 318,
 332, 343, 362, 373, 386,
 398, 414, ??, ??, 677
Prop_Gauge, **139**, used: 254
Prop_Ghost, **139**, used:
Prop_Majorana, **139**, used: 557,
 434, 484, 515, 362, 677
Prop_Rxi, **139**, used: 254
Prop_Scalar, **139**, used: 557,
 557, 228, 229, 239, 254,
 257, 434, 484, 515, 274,
 297, 318, 332, 343, 362,
 373, 398, 414, ??, ??, 677
prop_spinor, **239, 257, 434**,
 484, 515, 274, 297, 318,
 332, 343, 362, 373, 398,
 414, ??, ??, used: 239,
 257, 434, 484, 515, 274,
 297, 318, 332, 343, 362,
 373, 398, 414, ??, ??
Prop_Spinor, **139**, used: 557,
 231, 234, 239, 257, 434,
 484, 515, 274, 274, 297,
 297, 318, 332, 343, 362,
 373, 386, 398, 414, ??, ??,
 677
Prop_Tensor_2, **139**, used: 332,
 343, 414
Prop_Unitarity, **139**, used: 557,
 239, 257, 434, 484, 515,
 274, 297, 318, 332, 343,
 362, 373, 386, 398, 414,
 ??, ??
Prop_Vectorspinor, **139**, used:
 362
protected, **601**, used: 601, 602,
 603, 604, 606, 607
Protected, **614**, used:
PSet (module), **219, 572**, used:
 219, 219, 580, 596, 618
Psi, **140**, used: 232, 234, 239,
 242, 242, 242, 242, 243,
 243, 243, 243, 243, 244,
 244, 244, 244, 244, 245,
 245, 245, 245, 245, 246,
 246, 246, 246, 260, 261,
 261, 261, 261, 261, 261,
 440, 440, 441, 441, 441,
 441, 442, 442, 443, 443,
 443, 443, 443, 444, 444,
 445, 446, 446, 447, 447,
 447, 448, 448, 461, 461,
 462, 488, 488, 488, 489,
 489, 489, 490, 490, 490,
 491, 491, 491, 491, 492,
 492, 492, 493, 519, 520,
 520, 520, 520, 520, 521,
 521, 522, 522, 522, 522,
 522, 523, 523, 523, 524,
 524, 524, 524, 525, 525,
 525, 525, 525, 525, 525,
 525, 526, 526, 526, 526,
 527, 527, 527, 279, 279,
 279, 279, 279, 280, 280,
 280, 281, 281, 288, 300,
 300, 300, 301, 301, 301,
 302, 302, 302, 302, 310,
 321, 321, 321, 321, 322,
 322, 322, 323, 323, 324,
 335, 335, 335, 335, 336,
 348, 348, 348, 348, 348,
 365, 365, 365, 365, 366,
 376, 376, 376, 376, 376,
 389, 389, 389, 389, 390,
 390, 390, 390, 402, 402,
 402, 403, 403, 403, 403,
 403, 403, 404, 404, 404,
 414, 418, 418, 418, 418,

- 419, 419, 419, 419, 419,
420, 420, 420, 420, 420,
421, 421, 421, 421, 421,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, 678
- Psi0*, **273, 295**, used: 273, 275,
281, 283, 284, 285, 289,
296, 297, 302, 305, 305,
306, 310
- Psi1*, **273, 295**, used: 273, 275,
281, 284, 285, 289, 296,
297, 302, 305, 306, 310
- Psibar*, **140**, used: 232, 234, 239,
242, 242, 242, 242, 243,
243, 243, 243, 243, 244,
244, 244, 244, 244, 245,
245, 245, 245, 245, 246,
246, 246, 246, 260, 261,
261, 261, 261, 261, 261,
440, 440, 441, 441, 441,
441, 442, 442, 443, 443,
443, 443, 443, 444, 444,
445, 446, 446, 447, 447,
447, 448, 448, 461, 461,
462, 488, 488, 488, 489,
489, 489, 490, 490, 490,
491, 491, 491, 491, 492,
492, 492, 493, 519, 520,
520, 520, 520, 520, 521,
521, 522, 522, 522, 522,
522, 523, 523, 523, 524,
524, 524, 524, 525, 525,
525, 525, 525, 525, 525,
525, 526, 526, 526, 527,
527, 527, 279, 279, 279,
279, 279, 280, 280, 280,
281, 281, 288, 300, 300,
300, 301, 301, 301, 302,
302, 302, 302, 310, 321,
321, 321, 321, 322, 322,
322, 323, 323, 324, 335,
335, 335, 335, 336, 348,
348, 348, 348, 348, 365,
365, 365, 365, 366, 376,
376, 376, 376, 376, 389,
389, 389, 389, 390, 390,
390, 390, 402, 402, 402,
403, 403, 403, 403, 403,
403, 404, 404, 404, 414,
418, 418, 418, 418, 419,
- 419, 419, 419, 419, 420,
420, 420, 420, 420, 421,
421, 421, 421, 421, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, 678
- psibar_gauss*, **564, 566, 625**,
used:
psibar_incoming, **564, 565, 625**,
used: 597
psibar_outgoing, **564, 565, 625**,
used: 597
psibar_projector, **564, 565, 625**,
used: 594, 594
psibar_propagator, **564, 565**,
625, used: 593
psibar_type, **564, 565, 624**, used:
580
- Psim*, **273, 295**, used: 273, 275,
281, 283, 284, 285, 289,
296, 297, 302, 305, 305,
306, 310
- Psimm*, **273, 295**, used: 273,
275, 283, 284, 285, 289,
296, 297, 305, 305, 306,
310
- Psip*, **273, 295**, used: 273, 275,
281, 283, 284, 285, 289,
296, 297, 302, 305, 305,
306, 310
- Psipp*, **273, 295**, used: 273, 275,
283, 284, 285, 289, 296,
297, 305, 305, 306, 310
- psi_gauss*, **564, 566, 625**, used:
psi_incoming, **564, 565, 625**,
used: 597
psi_outgoing, **564, 565, 625**,
used: 597
psi_projector, **564, 565, 625**,
used: 594, 594
psi_propagator, **564, 565, 625**,
used: 593
psi_type, **564, 565, 624**, used:
580
- PSSSM* (module), **511, 510**,
used: ??
PSSSM_QCD (module), **511**,
510, used:
Public, **614**, used: 621, 621
public_symbols, **617**, used: 620,
621, 623

- public_symbols* (field), **615**, used: 615, 620, 621, 621, 621, 622, 622, 623
- pullback*, **186**, used: 186, 186, 187, 188, 190
- pure_adjoints*, **207**, used: 207
- PV*, **140**, used:
- p_aux* (field), **557**, used: 558, 558, 559
- p_color* (field), **557**, used: 558, 558, 559
- p_mass* (field), **557**, used: 558, 558, 559
- p_name* (field), **557**, used: 558, 558, 559
- P_NNA*, **436**, used:
- P_NNG*, **436**, used:
- P_NNH1*, **436**, used:
- P_NNH2*, **436**, used:
- p_spin* (field), **557**, used: 558, 558, 559
- p_symbol* (field), **557**, used: 557, 559, 559
- p_to_string*, **659**, used: 659, 659
- P_Whizard* (module), **669**, used: 670
- p_width* (field), **557**, used: 558, 558, 559
- Q*, **231**, **676**, used: 232, 232, 676, 677, 678, 679
- Q* (module), **184**, **183**, used:
- QBUB*, **239**, **414**, used: 239, 245, 245, 247, 414, 421, 421, 422
- qcd* (field), **99**, used: 99, 99, 99, 99, 100
- QCD* (module), **233**, **227**, used: ??
- qcd_order_in_bounds*, **100**, used: 100
- QED* (module), **230**, **227**, used: 675
- qgc*, **239**, **262**, **279**, **336**, **349**, **366**, **377**, **405**, **414**, ??, ??, used: 239, 262, 282, 282, 336, 349, 366, 377, 405, 414, ??, ??
- QGUG*, **239**, **414**, used: 239, 244, 244, 247, 414, 420, 420, 422
- QH*, **317**, used: 317, 318, 321, 321, 322, 322, 323, 324, 325
- qn_baryon*, **387**, used: 387
- qn_charge*, **387**, used: 387
- qn_generation*, **387**, used: 387
- qn_lepton*, **387**, used: 387
- QQ* (module), **184**, **183**, used: 239, 254, 258, 439, 485, 516, 276, 298, 319, 333, 345, 363, 374, 387, 399, 414, ??, ??, 227, 227, 228, 429, 480, 510, 270, 271, 271
- quark*, **384**, used: 384, 393
- Quark*, **383**, used: 384, 386, 389, 389, 390, 390, 390
- quark_current*, **678**, used: 678
- quark_currents*, **302**, used: 310
- quartic_anom*, **237**, **237**, **237**, **238**, **238**, **238**, **238**, **238**, **413**, **413**, **227**, **271**, used: 239, 414
- quartic_gauge*, **239**, **262**, **448**, **493**, **527**, **283**, **304**, **324**, **336**, **349**, **366**, **377**, **405**, **414**, ??, ??, used: 247, 262, 464, 499, 534, 289, 310, 325, 337, 350, 367, 377, 407, 422, ??, ??
- quartic_gravitino*, **462**, used: 464
- quartic_grav_char*, **462**, used: 462
- quartic_grav_gauge*, **461**, used: 462
- quartic_grav_neu*, **462**, used: 462
- quartic_grav_sneutrino*, **461**, used: 462
- Quiet*, **130**, used: 130
- Quot*, **168**, used: 239, 260, 260, 260, 260, 414
- quote*, **711**, **709**, used: 672
- QUQD1L*, **239**, used: 239, 246, 246, 247
- QUQD1R*, **239**, used: 239, 246, 246, 247
- QUQD8L*, **239**, used: 239, 246, 246, 247
- QUQD8R*, **239**, used: 239, 246, 246, 247

- QW*, **239, 414**, used: 239, 245, 245, 247, 414, 421, 421, 422
- Q_charg*, **436, 486, 517**, used: 440, 488, 520
- Q_down*, **239, 259, 436, 486, 517, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: 239, 260, 260, 440, 440, 488, 488, 519, 519, 527, 527, 279, 300, 321, 322, 335, 348, 365, 376, 402, 414, ??, ??
- Q_lepton*, **239, 259, 436, 486, 517, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: 239, 260, 260, 440, 440, 488, 488, 519, 519, 279, 284, 300, 305, 321, 335, 348, 365, 376, 402, 414, ??, ??
- Q_top*, **??**, used: ??
- Q_up*, **239, 259, 436, 486, 517, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: 239, 260, 260, 440, 440, 488, 488, 519, 519, 279, 279, 300, 301, 321, 322, 335, 348, 365, 376, 402, 414, ??, ??
- Q_Z_up*, **277, 298, 319**, used: 279, 301
- r* (field), **56**, used: 56, 56, 56, 57, 57, 57, 57, 58, 58, 58, 59, 59, 60, 60, 61, 61
- raises*, **??**, used: ??
- range*, **701, 698**, used: 704, 755, 756, 758, 758, 758, 758, 759, 17, 17, 61, 87, 560, 75, 207, 118, 118, 122, 267, 573, 676
- Range* (exn), **55, 56, 62, 52**, used:
- rank*, **42, 43, 43, 44, 46, 49, 55, 56, 62, 84, 84, 88, 111, 40, 41, 52, 81**, used: 45, 46, 63, 63, 63, 65, 65, 65, 65, 65, 65, 65, 66, 105, 111, 126, 601
- rank* (type), **44, 45, 45, 49, 49, 41**, used: 44, 44, 45, 49, 49, 41, 41
- rank0*, **62**, used: 62, 63, 63, 64, 64, 64, 64
- ranked*, **44, 45, 46, 49, 49, 41**, used: 46, 111
- ranks*, **44, 45, 46, 49, 49, 41**, used: 46
- rank_default*, **88**, used: 88
- rank_set*, **45**, used: 45
- Rat* (module), **184**, used: 184, 184
- Rational* (sig), **782, 779**, used: 783, 783, 785, 779, 780, 781
- raw* (field), **688**, used: 688, 688, 688, 689, 689
- raw* (type), **685, 549, 684, 549**, used: 549, ??, 557, 684, 549, 549, 549, ??, 552
- rcs*, **760, 9, 10, 12, 13, 16, 21, 22, 25, 27, 27, 29, 34, 35, 41, 45, 55, 56, 62, 227, 660, 556, 185, 209, 96, 96, 100, 127, 228, 229, 230, 233, 239, 254, 255, 265, 431, 481, 511, 272, 295, 316, 330, 341, 360, 371, 382, 396, 414, 564, 565, 624, ??, ??, 676, 177, 760, 7, 20, 40, 54**, used: 107, 107, 126, 670, 265, 569, 577, 612, 614
- RCS* (module), **685, 684**, used: 760, 9, 9, 10, 12, 13, 16, 21, 21, 22, 25, 27, 27, 34, 35, 41, 41, 45, 55, 55, 56, 62, 221, 227, 660, 553, 185, 185, 209, 95, 95, 96, 96, 100, 106, 107, 107, 127, 670, 228, 228, 229, 230, 233, 239, 254, 255, 265, 429, 431, 480, 481, 511, 511, 271, 330, 341, 360, 371, 382, 414, 640, 563, 564, 565, 569, 577, 612, 614, 624, ??, ??, 675, 177, 181, 760, 7, 20, 40, 54, 92

-
- rcs_author* (field), **685**, used:
685, 686
 - rcs_date* (field), **685**, used: 685,
686
 - rcs_file*, **9, 21, 41, 55, 221, 553,**
185, 95, 228, 429, 480,
511, 271, 640, 563, ??,
??, 675, used: 10, 12, 13,
16, 22, 25, 27, 27, 29, 34,
35, 45, 56, 62, 227, 556,
185, 209, 96, 100, 127,
228, 229, 230, 233, 239,
254, 255, 431, 481, 511,
272, 295, 316, 330, 341,
360, 371, 382, 396, 414,
565, 569, 624, ??, ??, 676
 - rcs_list*, **95, 126, 563, 569, 181,**
92, used: 670, 577, 614
 - rcs_revision* (field), **685**, used:
685, 686
 - rcs_source* (field), **685**, used:
685, 686
 - read*, **695, 696, 694**, used: 697
 - read_generation*, **267**, used: 267
 - read_lines*, **671**, used:
 - read_lines_rev*, **670**, used: 671,
671
 - Real*, **173**, used: 560, 239, 260,
414
 - realspinors* (field), **573**, used:
573, 574, 580
 - Real_Array*, **173**, used: 239, 260,
414
 - real_arrays* (field), **574**, used:
574, 575, 577
 - real_singles* (field), **574**, used:
574, 575, 577
 - real_variable*, **557**, used: 557,
558, 558, 560
 - Rec*, **168**, used:
 - remove*, **713, 716, 721, 727,**
728, 729, 730, 731, 31,
712, 725, 726, 726,
used: ??, 716, 721, 728,
729, 731, 731, 784, 785,
786, 787, 31, 31, 32, 218
 - remove_duplicate_final_states*,
213, 218, 213, used: 134
 - rename*, **686, 684**, used: 10, 12,
13, 16, 22, 25, 27, 27, 34,
35, 45, 56, 62, 227, 185,
209, 96, 100, 127, 228,
229, 230, 233, 239, 254,
255, 265, 431, 481, 511,
330, 341, 360, 371, 382,
414, 565, 569, 624
 - repeat*, **759**, used: 759
 - require_library*, **564, 569, 569,**
638, used: 569, 617
 - RError*, ??, ??, used: ??
 - reset*, **692, 690**, used:
 - result* (type), **695, 696, 694,**
used: 695, 694
 - result_flavour*, ??, used: ??
 - result_msg*, ??, used: ??
 - result_path*, ??, used: ??
 - rev* (field), **768, 764**, used: 769,
769, 769, 771, 771
 - reverse_braket*, **564, 569, 637,**
used: 596
 - revision*, **685, 684**, used: 686
 - revision* (field), **685, 684**, used:
686, 760, 9, 21, 41, 55,
221, 660, 553, 185, 95,
228, 429, 480, 511, 271,
640, 563, ??, ??, 675
 - revmap*, **384**, used: 384, 384
 - revmap2*, **384**, used: 384
 - rev_flatmap*, **701, 699**, used:
753, 209
 - rev_multiply*, **704**, used: 704, 704
 - Rf*, **414**, used: 414, 417, 422
 - rf3*, **417**, used: 422
 - RFailure*, ??, ??, used: ??
 - rhs*, **95, 102, 104, 123, 90**, used:
123, 595, 595, 596
 - rhs* (type), **95, 102, 104, 123,**
89, used: 95, 102, 102,
102, 104, 104, 110, 121,
123, 89, 90, 90, 90, 90
 - Ring* (sig), **783, 780**, used: 784,
785, 787, 781, 781
 - RMOM*, **140**, used:
 - RPAREN*, ??, ??, ??, ??, used:
??, ??, 71, 551
 - RPAREN* (camlyacc token), **72,**
552, used: 72, 552
 - rphi3*, **417**, used: 422
 - Rphim*, **414**, used: 414, 417, 422

- Rphimm*, **414**, used: 414, 417, 422
Rphin, **414**, used: 414, 417, 422
Rphip, **414**, used: 414, 417, 422
Rphipp, **414**, used: 414, 417
Rsigma, **414**, used: 414, 417, 417, 422
rsigma3, **417**, used: 422
rsigma4, **417**, used: 422
RSkip, **??**, **??**, used: **??**
RSuccess, **??**, **??**, used: **??**
rt3, **418**, used: 422
Rtm, **414**, used: 414, 418, 422
Rtmm, **414**, used: 414, 418, 422
Rtn, **414**, used: 414, 418, 422
RTodo, **??**, **??**, used: **??**
Rtp, **414**, used: 414, 418, 422
Rtpp, **414**, used: 414, 418
Running, **139**, used:
run_test_tt, **??**, **??**, used: **??**
run_test_tt_main, **??**, **??**, used:
R_CN, **436**, used:
R_CNG, **436**, used:
R_NC, **436**, used:
R_NCH, **436**, used:
S, **233**, **140**, used: 233, 234, 234, 235, 239, 261, 442, 443, 444, 490, 521, 280, 281, 302, 302, 323, 336, 348, 365, 376, 414, **??**, **??**
S (module), **??**, **100**, **552**, used: **??**, **100**, **100**, 552
S (sig), **??**, **??**, used: **??**, **??**, **??**, **??**
S1, **482**, **513**, used: 483, 490, 491, 491, 494, 495, 497, 497, 498, 499, 514, 522, 522, 523, 528, 529, 531, 532, 532, 533, 534
S1 (module), **45**, used: 45
S2, **482**, **513**, **140**, used: 483, 490, 491, 491, 494, 495, 497, 497, 498, 499, 514, 522, 522, 523, 528, 529, 531, 532, 532, 533, 534, 288, 310, 324
S2 (module), **45**, used: 45
S2L, **140**, used:
S2LR, **140**, used: 288, 310
S2P, **140**, used:
S2R, **140**, used:
S3, **482**, **513**, used: 483, 490, 491, 491, 494, 495, 497, 497, 498, 499, 514, 522, 522, 523, 528, 529, 531, 532, 532, 533, 534
S4, **513**, used: 514, 533, 534
S5, **513**, used: 514, 533, 534
S6, **513**, used: 514, 533, 534
S7, **513**, used: 514, 533, 534
S8, **513**, used: 514, 533, 534
S9, **513**, used: 514, 533, 534
sanitize_symbol, **555**, used: 558
sans_colors, **131**, used: 131
Sbar, **233**, used: 233, 234, 234, 235
Scalar, **137**, used: 557, 559, 228, 229, 239, 256, 256, 433, 484, 515, 274, 296, 317, 331, 342, 361, 372, 398, 414, **??**, **??**, 677
Scalar2_Vector2, **141**, used: 191, 239, 449, 450, 450, 451, 451, 452, 452, 494, 494, 494, 494, 494, 494, 495, 495, 495, 495, 496, 496, 496, 496, 496, 497, 527, 527, 527, 528, 528, 528, 528, 528, 529, 529, 529, 529, 529, 529, 529, 529, 530, 530, 531, 531, 285, 285, 306, 306, 324, 324, 336, 349, 366, 377, 406, 414, 417, **??**, **??**, 678
Scalar4, **141**, used: 560, 191, 193, 230, 230, 239, 453, 453, 454, 456, 456, 457, 457, 458, 458, 459, 459, 459, 460, 460, 460, 460, 460, 461, 288, 309, 324, 336, 349, 366, 377, 407, 414, **??**, **??**
scalars (field), **573**, used: 573, 574, 580
Scalar_Scalar_Scalar, **140**, used: 560, 190, 229, 230, 230, 239, 452, 452, 454, 454, 455, 455, 456, 497, 497, 498, 498, 498, 525, 526,

- 526, 526, 531, 532, 532,
532, 532, 288, 309, 324,
336, 349, 366, 377, 406,
414, ??, ??
- Scalar_Vector_Vector*, **140**, used:
190, 239, 242, 449, 449,
493, 528, 283, 283, 283,
289, 304, 304, 305, 310,
324, 324, 325, 336, 337,
349, 350, 366, 367, 377,
377, 405, 407, 414, 416,
417, 417, ??, ??, ??, ??
- scale*, **783, 784, 786, 787, 550**,
780, 781, used: 786, 787,
550, 550
- scattering* (type), **213, 214, 212**,
used: 213, 214, 212, 212
- Scattering*, **213, 214, 212**, used:
214, 215, 215
- Scattering* (module), **55, 59, 65**,
53, used: 658, 658, 661,
661, 661, 664, 109, 118,
125, 125
- Sccs*, **277, 298, 319**, used:
- schisma*, **575**, used: 575, 577
- schisma_num*, **575**, used: 575,
577
- SD*, **431, 482, 512**, used: 442,
445, 446, 450, 452, 454,
455, 456, 458, 460, 460,
490, 491, 492, 492, 495,
495, 496, 498, 498, 521,
523, 523, 524, 529, 530,
531, 532, 532
- Sdown*, **432, 483, 514**, used:
433, 435, 440, 441, 442,
445, 446, 447, 447, 450,
451, 451, 452, 452, 454,
455, 455, 456, 456, 457,
458, 458, 460, 460, 460,
460, 461, 461, 465, 483,
485, 488, 489, 490, 491,
492, 492, 493, 495, 495,
496, 496, 496, 497, 498,
498, 498, 499, 514, 516,
519, 521, 521, 523, 523,
524, 525, 525, 526, 527,
529, 530, 530, 530, 531,
531, 532, 532, 532, 534
- sdown4_1gen*, **460**, used: 464
- sdown4_1gen'*, **460**, used: 460
- sdown4_2gen*, **460**, used: 464
- sdown4_2gen'*, **460**, used: 460
- search_path*, **695**, used: 696, 696,
696
- selectors* (type), **74, 77, 95, 114**,
129, 130, 73, 90, 92,
used: 74, 74, 74, 95, 96,
114, 129, 130, 130, 73, 73,
74, 74, 74, 74, 74, 90,
92, 93, 94
- select_p*, **74, 77, 74**, used: 118
- select_p* (field), **77**, used: 77, 77,
80
- select_wf*, **74, 77, 74**, used: 118
- select_wf* (field), **77**, used: 77,
77, 80
- Selfconjugate*, **556**, used: 558
- seq* (type), **747, 745**, used: 746,
746, 746, 746, 746, 746,
746, 747, 747, 747, 747,
747
- set*, **219**, used: ??, 704, 707, 707,
756, 756, 757, 789, 790,
790, 791, 791, 792, 773,
773, 774, 555, 559, 219,
135, 135
- set* (type), **742, 736, 734**, used:
- Set* (module), ??, used: ??, ??,
??, ??, ??, ??, ??, 704,
739, 742, 742, 45, 45, 46,
223, 224, 662, 664, 188,
217, 218, 219, 105, 121,
125, 133, 572
- SetMake* (module), ??, ??, used:
- SetTestPath* (module), ??, used:
??
- setup*, **226, 178**, used: 560
- setup_fortran_formatter*, **571**,
used: 577, 615, 620, 621,
623
- set_cache_name*, **95, 107, 129**,
136, 91, 93, used: 136
- set_color*, **225**, used: 226
- set_conjugate*, **225**, used: 226
- set_constant_symbol*, **225**, used:
226
- set_external_flavors*, **225**, used:
226
- set_fermion*, **225**, used: 226

- set_flavors*, **225**, used: 226
set_flavor_of_string, **225**, used: 226
set_flavor_symbol, **225**, used: 226
set_flavor_to_string, **225**, used: 226
set_flavor_to_TeX, **225**, used: 226
set_fuse, **225**, used: 226
set_fuse2, **225**, used: 226
set_fuse3, **225**, used: 226
set_gauge_symbol, **225**, used: 226
set_goldstone, **225**, used: 226
set_lorentz, **225**, used: 226
set_mass_symbol, **225**, used: 226
set_max_degree, **225**, used: 226
set_max_order, **99**, used: 99
set_of_flavors, **662**, used: 662
set_of_list, **743**, used: 743
set_orders, **225**, used:
set_parameters, **225**, used: 226
set_pdg, **225**, used: 226
set_propagator, **225**, used: 226
set_to_string, **742**, used: 742
set_vertices, **225**, used: 226
set_width, **225**, used: 226
set_width_symbol, **225**, used: 226
sff (type), **431, 482, 512**, used: 435, 436, 486, 517
sfm (type), **431, 482, 513**, used: 432, 436, 483, 486, 514, 517
SG, **676**, used: 676, 679
shift_left_pred, **217**, used: 218
shift_left_pred', **217**, used: 217
shiggs (type), **482, 513**, used: 483, 486, 514, 517
SHiggs, **483, 514**, used: 483, 485, 490, 491, 491, 493, 493, 494, 494, 494, 495, 497, 497, 498, 499, 514, 516, 521, 522, 522, 526, 526, 528, 528, 529, 529, 529, 531, 532, 532, 534
shiggs_neutr, **491, 522**, used: 491, 523
shortest, **727, 730, 730, 732, 725, 727**, used:
- shortest'*, **730, 732**, used: 730, 732
shuffle, **757**, used: 758, 758, 758, 759
sign, **95, 101, 101, 102, 104, 123, 89**, used: 104, 123, 584, 590
sign (field), **101, 101**, used: 101, 110, 114
sign (type), **101, 101**, used: 101, 101
Simplest (module), **316, 270**, used: ??, ??
Sin, **436, 168**, used:
Sin2al, **436**, used:
Sin2am2b, **436**, used:
Sin2be, **436**, used:
Sin2thw, **239, 259, 436, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: 239, 259, 260, 260, 414
Sin4al, **436**, used:
Sin4be, **436**, used:
Sinamb, **436**, used:
Sinapb, **436**, used:
Singlet, **82, 81**, used: 82, 557, 559, 228, 229, 231, 239, 256, 434, 484, 515, 274, 296, 318, 332, 343, 361, 373, 385, 398, 414, ??, ??, 677
singleton, **713, 714, 719, 784, 787, 55, 56, 63, 712, 781, 52**, used: 784, 785, 787, 217, 103, 114
Single_File, **569**, used: 570
Single_Function, **569**, used: 570
Single_Module, **569**, used: 570, 570
Singular (exn), **789, 789**, used:
Sinpsi, **277, 298, 319**, used:
Sinthw, **239, 259, 277, 298, 319, 334, 347, 364, 375, 400, 414, ??, ??**, used: 239, 260, 414
size, **41, 47, 39**, used:
Skip (exn), **??**, used:
skip_if, **??, ??**, used: ??

- SL*, **431, 482, 512, 360, 140**,
used: **245, 246, 246, 246,**
246, 442, 442, 443, 445,
446, 446, 447, 450, 454,
455, 456, 458, 490, 490,
491, 492, 495, 495, 498,
498, 521, 522, 523, 523,
529, 530, 532, 532, 281,
302, 323, 361, 362, 366,
367, 421
- Slepton*, **432, 483, 514**, used:
433, 435, 440, 441, 442,
445, 446, 447, 450, 454,
454, 455, 456, 456, 457,
458, 459, 459, 460, 460,
461, 465, 483, 485, 488,
489, 490, 491, 492, 495,
495, 497, 498, 498, 499,
514, 516, 519, 520, 521,
523, 523, 524, 524, 525,
529, 530, 532, 532, 532,
534
- slepton2_squark2*, **460**, used: **464**
- slepton2_squark2'*, **460**, used:
460
- slepton2_squark2''*, **460**, used:
460
- slepton4_1gen*, **459**, used: **464**
- slepton4_1gen'*, **459**, used: **459**
- slepton4_2gen*, **459**, used: **464**
- slepton4_2gen'*, **459**, used: **459**
- slep_sneu_squark2*, **460**, used:
464
- slep_sneu_squark2'*, **460**, used:
460
- slep_sneu_squark2''*, **460**, used:
460
- slist*, **514**, used: **514**
- slow_binomial*, **748**, used: **748**
- SLR*, **140**, used: **245, 443, 443,**
443, 443, 444, 444, 445,
446, 446, 447, 448, 448,
490, 491, 491, 491, 491,
491, 492, 492, 492, 522,
522, 522, 522, 523, 523,
523, 524, 524, 524, 525,
525, 525, 525, 525, 525,
525, 525, 525, 525, 526,
526, 526, 526, 526, 281,
281, 302, 302, 421
- SLRV*, **140**, used: **461, 462, 462**
- SLV*, **140**, used: **461, 461**
- SM* (module), **239, 254, 227**,
used: **254, 254, 254, 254,**
255, 255, 270, 675, ??, ??,
??, ??, ??, ??
- Small-Rational* (module), **783,**
779, used: **184, 239, 258,**
439, 485, 516, 276, 298,
319, 333, 345, 363, 374,
387, 399, 414, ??, ??, 183,
183
- SM_anomalous* (module), **238,**
227, used: **??**
- SM_anomalous_ckm* (module),
238, 227, used: **??**
- SM_anomalous_top* (module),
238, 227, used: **??**
- SM_clones* (module), **270, 228**,
used:
- SM_flags* (sig), **237, ??, ??, 227**,
used: **237, 237, 238, 238,**
238, 238, 238, 239, ??, ??,
??, ??, ??, ??, 227, 227
- SM_gluons* (module), **??, ??**,
used:
- SM_Higgs* (module), **238, 227**,
used: **??**
- SM_k_matrix* (module), **238,**
227, used: **??**
- SM_no_anomalous* (module),
237, ??, ??, 227, used:
254, 270, 675, ??, ??
- SM_no_anomalous_ckm* (module),
237, 227, used: **??**
- SM_QCD* (module), **255, 227**,
used: **??**
- SM_Rxi* (module), **254, 227**,
used:
- SN*, **431, 482, 512**, used: **442,**
445, 446, 450, 454, 456,
457, 490, 491, 492, 496,
497, 521, 523, 523, 530,
532
- sneu2_slep2_1*, **459**, used: **464**
- sneu2_slep2_1'*, **459**, used: **459**
- sneu2_slep2_2*, **459**, used: **464**
- sneu2_slep2_2'*, **459**, used: **459**
- sneu2_squark2*, **460**, used: **464**
- sneu2_squark2'*, **460**, used: **460**

- Sneutrino*, **432, 483, 514**, used:
433, 435, 441, 442, 445,
446, 447, 450, 454, 455,
456, 457, 459, 459, 460,
460, 461, 465, 483, 485,
489, 490, 491, 492, 495,
496, 497, 499, 514, 516,
520, 521, 523, 523, 525,
525, 526, 530, 530, 532,
534
- sneutrino4*, **459**, used: **464**
- sneutrino4'*, **459**, used: **459**
- solve*, **793, 789**, used:
- solve_destructive*, **792**, used: **793**
- solve_many*, **793, 789**, used: **774**
- solve_many_destructive*, **793**,
used: **793**
- sort*, **767, 654, 657, 764, 653**,
used: **704, 705, 705, 755,**
755, 756, 776, 776, 787,
788, 751, 752, 56, 656,
658, 662, 663, 112, 132,
135, 672, 618
- sort'*, **767**, used: **767, 767**
- sort3*, **658**, used: **658**
- sorted_keys*, **45**, used:
- sort_2i*, **768**, used: **770, 771**
- sort_2i'*, **768**, used: **768, 768**
- sort_children*, **776**, used: **776**
- sort_decay*, **654, 655, 653**, used:
655, 657
- sort_momenta*, **656**, used: **657,**
658
- sort_section*, **704**, used: **704**
- sort_signed*, **754, 747**, used: **97,**
128
- sort_spin_table*, **132**, used: **133**
- source*, **685, 684**, used: **686**
- source* (field), **685, 684**, used:
686, 760, 9, 21, 41, 55,
221, 660, 553, 185, 95,
228, 429, 480, 511, 271,
640, 563, ??, ??, 675
- SP*, **140**, used: **444, 444, 522,**
403, 403, 403, 403, 403,
404, 404, 404
- spacelike*, **55, 60, 61, 65, 65, 53,**
54, used: **658, 661**
- species*, **768**, used: **769, 769, 769**
- spin*, **572**, used: **597, 597**
- spinor*, **239, 256, 433, 483, 515,**
273, 296, 317, 331, 342,
361, 372, 397, 414, ??,
??, used: 239, 256, 433,
484, 515, 274, 296, 317,
331, 342, 361, 372, 398,
414, ??, ??
- Spinor*, **137**, used: **555, 559, 231,**
233, 239, 256, 433, 483,
515, 273, 274, 296, 296,
317, 331, 342, 361, 372,
386, 397, 414, ??, ??, 677
- spinors* (field), **573**, used: **573,**
574, 580
- split*, **715, 693, 750, 9, 11, 12,**
15, 16, 55, 61, 66, 693,
746, 6, 53, used: **715,**
717, 718, 693, 788, 751,
754, 774, 16, 35, 662, 97,
110
- split'*, **693, 749**, used: **693, 693,**
749, 749, 750
- splitn*, **700, 698**, used: **209, 575,**
575
- splitn'*, **700**, used: **700, 700**
- split_color_string*, **188**, used: **189**
- SPM*, **140**, used: **243, 419**
- SQ*, **676**, used: **676, 677, 678,**
678, 679
- Sqrt*, **168**, used: **239, 260, 414**
- square*, **86**, used: **87**
- square* (type), **85**, used:
- Square*, **85**, used: **86, 86**
- square2*, **86**, used: **87**
- squark_current*, **678**, used: **678**
- squark_seagull*, **678**, used: **679**
- SR*, **140**, used: **245, 246, 246,**
246, 246, 442, 443, 445,
446, 446, 490, 522, 281,
302, 323, 421
- SRV*, **140**, used:
- Stale*, **695, 696, 694**, used: **697**
- standard_gauge_higgs*, **239, 285,**
306, 324, 336, 349, 366,
414, used: **241, 288, 309,**
324, 337, 350, 367, 416
- standard_gauge_higgs'*, **283, 304,**
324, used: **285, 306, 324**
- standard_gauge_higgs4*, **239,**
285, 306, 324, 336, 349,

- 366, 414**, used: **241, 288, 309, 324, 337, 350, 367, 416**
- standard_higgs*, **239, 288, 309, 324, 336, 349, 366, 414**, used: **241, 288, 309, 324, 337, 350, 367, 416**
- standard_higgs4*, **239, 288, 309, 324, 336, 349, 366, 414**, used: **241, 288, 309, 325, 337, 350, 367, 416**
- standard_quartic_gauge*, **239, 282, 303, 323, 336, 349, 366, 414**, used: **239, 283, 304, 324, 336, 349, 366, 414**
- standard_triple_gauge*, **239, 281, 303, 323, 336, 348, 366, 414**, used: **239, 282, 303, 323, 336, 349, 366, 414**
- stat*, **96, 97, 100, 127**, used: **100, 114**
- stat* (type), **96, 97, 100, 127**, used: **96, 100, 110, 112, 112, 113, 113**
- Stat* (sig), **96**, used: **96, 96, 127**
- state* (type), **690**, used: **690**
- Stat_Dirac* (module), **96**, used: **127, 129, 129, 129**
- stat_fuse*, **96, 97, 100, 127**, used: **100, 110, 113**
- stat_keystone*, **113**, used: **114**
- Stat_Majorana* (module), **127**, used: **129, 129, 129, 129**
- Stat_Maker* (sig), **96**, used: **100**
- Stat_Map* (module), **112**, used: **112**
- stat_sign*, **96, 98, 100, 128**, used: **100, 110, 113**
- step* (field), **690**, used: **691, 692, 692, 692**
- steps* (field), **690**, used: **692, 692**
- string_of_angle*, **435**, used: **472**
- string_of_char*, **432, 482, 513**, used: **467, 472, 503, 507, 539, 545, 546**
- string_of_fermion_gen*, **483, 514**, used: **507, 545**
- string_of_fermion_type*, **483, 514**, used: **507, 545**
- string_of_gen*, **431, 482, 512**, used: **431, 482, 512**
- string_of_higgs*, **432**, used: **432, 472**
- string_of_int_list*, **681**, used: **681**
- string_of_neu*, **432, 482, 513**, used: **467, 472, 503, 507, 536, 539, 545, 546**
- string_of_node*, **??, ??**, used: **??**
- string_of_path*, **??, ??**, used: **??, ??, ??**
- string_of_phiggs*, **483, 513**, used: **503, 507, 539, 545, 546**
- string_of_sff*, **431, 482, 512**, used: **435, 472, 507, 545, 546**
- string_of_sfm*, **431, 482, 513**, used: **472, 507, 545, 546**
- string_of_shiggs*, **483, 513**, used: **503, 507, 539, 545, 546**
- strip_array_tag*, **576**, used: **577**
- strip_before_a_keyword*, **685**, used: **686**
- strip_before_keyword*, **685**, used: **685**
- strip_dollars*, **685**, used: **685, 685**
- strip_from_first*, **710, 709**, used: **685**
- strip_from_last*, **710, 709**, used: **685**
- strip_keyword*, **685**, used: **685, 685**
- strip_prefix*, **709, 709**, used: **685, 685**
- strip_prefix_star*, **710, 709**, used: **685**
- strip_required_prefix*, **710, 709**, used: **685**
- strip_single_tag*, **576**, used: **577**
- strip_svn_repos*, **686**, used: **686**
- sty*, **771, 764**, used: **768**
- style*, **768**, used: **768**
- style* (field), **768, 764**, used: **768, 771, 771**
- SU*, **431, 482, 512**, used: **442, 445, 446, 450, 452, 454, 455, 456, 458, 460, 460, 490, 491, 492, 492, 495, 495, 496, 498, 498, 521,**

- 523, 523, 524, 529, 530,
531, 532, 532
su0, **186**, used: 206, 208
sub, **782, 783, 783, 784, 786,**
787, 55, 58, 64, 779,
780, 781, 52, used: ??,
??, 709, 710, 710, 710,
710, 711, 685, 685, 786,
786, 787, 773, 58, 64, 656,
659, 553, ??, 188, 214,
267, 566, 625, 679, 71
sub', **58**, used: 58, 58
Subset, **614**, used:
substitute_char, **555**, used: 555
substring, **553**, used: 554, 554,
554
subtract, **550, 549**, used: ??, 552
succ, **28, 29, 20**, used: 701, 702,
702, 703, 707, 709, 710,
710, 711, 757, 690, 692,
730, 733, 791, 791, 791,
792, 760, 761, 769, 772,
772, 16, 22, 25, 29, 31, 33,
33, 34, 47, 57, 60, 63, 67,
83, 85, 661, 553, 554, 554,
75, 188, 206, 214, 214,
215, 217, 112, 133, 135,
267, 481, 512, 566, 577,
601, 601, 601, 602, 602,
603, 603, 604, 605, 606,
607, 607, 612, 625
suffix, **579**, used: 595, 598
suite, **723, 724, 757, 759, 723,**
755, used:
suite_apply, **724, 758**, used: 724,
759
suite_compose, **759**, used: 759
suite_inverse, **758**, used: 759
suite_of_list, **758**, used: 759
sum, **783, 784, 786, 787, 774,**
183, 183, 183, 183, 184,
184, 781, 781, 182,
used: 774, 214, 123
Sum, **549, 168, 549**, used: 550,
550, 550
summary, **686, 692, 684, 690,**
used: 135, 670, 577, 614
SUM_1, **436**, used:
SUN, **82, 81**, used: 82, 559, 233,
239, 256, 434, 484, 515,
274, 296, 318, 332, 343,
361, 373, 385, 398, 414,
??, ??, 677
sup (field), **767, 768**, used: 767,
768, 768
Sup, **768, 432, 483, 514**, used:
768, 433, 435, 440, 441,
442, 445, 446, 447, 447,
450, 451, 451, 452, 452,
454, 455, 455, 456, 456,
457, 458, 458, 460, 460,
460, 460, 461, 461, 465,
483, 485, 488, 489, 490,
491, 492, 492, 493, 495,
495, 496, 496, 496, 497,
498, 498, 498, 499, 514,
516, 519, 521, 521, 523,
523, 524, 525, 525, 525,
527, 529, 530, 530, 530,
531, 531, 532, 532, 532,
534
sup2_sdown2, **461**, used: 464
sup2_sdown2_1, **461**, used: 461
sup2_sdown2_2, **461**, used: 461
sup2_sdown2_3, **461**, used: 461
sup4_1gen, **460**, used: 464
sup4_1gen', **460**, used: 460
sup4_2gen, **460**, used: 464
sup4_2gen', **460**, used: 460
Supp, **277, 298, 319**, used:
Supp2, **277, 298, 319**, used:
supremum_or_infinity (type),
768, used: 768
SV, **140**, used:
swap, **790**, used: 791, 791
SYM (module), **676**, used: 681
symbol, **549, 549**, used: ??, 552
symbol (type), **556**, used: 557
symbol (camllex regexpr), **551**,
used: 551
Symbol, **549, 549**, used: 549
SYMBOL, ??, ??, used: ??, 551
SYMBOL (camlyacc token), **552**,
used: 552
symmetry, **749, 33, 95, 102,**
105, 123, 745, 91, used:
33, 119, 123, 596
symmetry (field), **102, 105**, used:
105, 114, 122

Syntax_Error (exn), **71, 69**,
 used:
system_cache_dir, **687, 687**,
 used: **695**
s_channel, **55, 60, 65, 95, 125**,
 125, 54, 92, used: **661**,
 664, 599
s_channel_in, **55, 60, 65, 53**,
 used: **60, 60, 65, 65**
s_channel_out, **55, 60, 65, 53**,
 used: **60, 65**
s_channel_out', **60**, used: **60, 60**
S_NNA, **436**, used:
S_NNG, **436**, used:
S_NNH1, **436**, used:
S_NNH2, **436**, used:
t (type), **??, ??, ??, ??, 723**,
 723, 723, 713, 713, 719,
 704, 755, 755, 756, 739,
 739, 739, 740, 740, 742,
 742, 742, 685, 695, 695,
 690, 727, 728, 728, 730,
 731, 776, 782, 783, 783,
 783, 784, 784, 785, 787,
 688, 688, 765, 9, 11, 12,
 13, 16, 28, 29, 30, 41,
 41, 41, 42, 43, 43, 44,
 44, 44, 45, 46, 49, 55,
 56, 62, 67, 67, 67, 654,
 657, 183, 183, 183, 183,
 184, 184, 82, 82, 82, 83,
 84, 84, 86, 86, 88, 221,
 221, 222, 222, 222, 660,
 661, 661, 662, 664, 70,
 74, 75, 79, 188, 213,
 213, 217, 218, 218, 219,
 101, 101, 105, 105, 106,
 106, 111, 112, 114, 121,
 125, 126, 131, 131, 133,
 572, 142, ??, ??, 722,
 712, 754, 738, 738, 741,
 741, 684, 694, 694, 690,
 725, 726, 726, 776, 779,
 780, 780, 781, 688, 763,
 6, 20, 36, 37, 38, 40, 51,
 54, 653, 182, 81, 81,
 220, 660, 69, 73, 212,
 72, 72, 552, 552, used:
 ??, ??, ??, ??, ??, ??, ??,
 ??, ??, ??, ??, 723, 723,
 723, 713, 713, 755, 739,
 739, 740, 740, 742, 742,
 742, 742, 742, 695, 727,
 728, 728, 730, 731, 776,
 782, 782, 783, 783, 784,
 784, 785, 787, 688, 765, 9,
 10, 12, 13, 15, 21, 23, 25,
 27, 27, 28, 29, 30, 34, 35,
 41, 41, 41, 42, 42, 42, 43,
 43, 44, 44, 44, 45, 45, 45,
 45, 46, 49, 49, 49, 55, 56,
 62, 67, 67, 67, 654, 655,
 183, 183, 183, 183, 184,
 184, 82, 82, 83, 83, 83, 83,
 84, 221, 222, 660, 661,
 661, 661, 662, 557, 557,
 70, ??, 74, 74, 75, 75, 75,
 213, 216, 219, 219, 95, 96,
 96, 98, 98, 98, 98, 99, 100,
 100, 101, 101, 102, 102,
 102, 103, 103, 104, 105,
 106, 106, 111, 112, 112,
 113, 113, 120, 129, 130,
 130, 131, 133, 669, 675,
 564, 174, 174, 176, 177,
 177, 178, 180, 180, 180,
 181, ??, ??, ??, ??, ??,
 ??, ??, ??, ??, ??, 722,
 723, 712, 754, 738, 738,
 738, 738, 738, 738, 741,
 741, 741, 741, 741, 742,
 742, 742, 684, 684, 684,
 684, 684, 694, 690, 725,
 725, 725, 725, 725, 725,
 726, 726, 726, 726, 726,
 727, 727, 727, 776, 776,
 779, 779, 780, 780, 780,
 780, 781, 781, 781, 781,
 781, 781, 781, 781, 781,
 781, 781, 688, 760, 763,
 763, 764, 764, 764, 764,
 764, 764, 764, 765, 765, 6,
 6, 6, 6, 6, 6, 6, 7, 7, 7,
 7, 7, 8, 8, 8, 8, 20, 20, 20,
 21, 21, 21, 36, 37, 37, 37,
 37, 37, 38, 38, 38, 38, 38,
 38, 38, 38, 39, 39, 39, 39,
 39, 39, 39, 39, 39, 40, 40,
 40, 40, 40, 41, 41, 51, 52,
 52, 52, 52, 52, 52, 52, 52

- 52, 53, 53, 53, 53, 53, 53,
53, 53, 53, 54, 54, 54, 54,
54, 54, 54, 54, 54, 653,
653, 653, 653, 653, 182,
182, 182, 182, 183, 183,
183, 81, 81, 81, 82, 220,
660, 660, 69, 69, 69, ??,
73, 73, 74, 212, 212, 212,
213, 213, 213, 89, 89, 90,
92, 92, 92, 92, 93, 94, 94,
94, 669, 72
T, **233**, used: 233, 234, 234, 235
T (module), **670**, used: 670, 671,
673, 674
T (sig), **723, 713, 755, 740**,
742, 695, 727, 21, 41,
55, 654, 183, 660, 74,
213, 95, 669, 174, 180,
722, 712, 754, 738, 741,
694, 725, 19, 38, 51,
653, 182, 660, 73, 212,
89, 669, used: 723, 755,
756, 757, 728, 731, 49,
655, 183, 183, 183, 184,
184, 661, 75, 185, 213, 96,
96, 96, 98, 100, 127, 130,
130, 670, 563, 569, 174,
177, 178, 180, 181, 723,
713, 713, 754, 755, 755,
738, 742, 694, 726, 727,
20, 21, 21, 40, 41, 54, 653,
182, 182, 183, 183, 183,
660, 553, 74, 185, 213, 92,
94, 94, 669, 227, 227, 429,
480, 510, 270, 271
t' (type), **219**, used: 219
T2, **13, 8**, used: 14, 14, 15, 15,
15, 15
T3, **13, 8**, used: 14, 14, 15, 15,
15, 15
table, **229, 232, 235, 247, 255**,
262, 269, 464, 499, 534,
289, 310, 325, 337, 350,
367, 377, 392, 407, 422,
??, ??, **679**, used: 229,
232, 235, 247, 255, 262,
269, 464, 499, 534, 289,
310, 325, 337, 350, 367,
377, 392, 407, 422, ??, ??,
679
tag (field), **695**, used: 696, 696
tagged (type), **695**, used:
Tagged (module), **100**, used: 126,
127
Tagged_Binary (module), **127**,
94, used:
Tagged_Coupling (module), **101**,
used: 102, 104, 110, 114,
121
Tagged_Coupling (sig), **101**,
used: 101
Tagged_Maker (sig), **98, 94**,
used: 94
Tagger (sig), **98, 94**, used: 98,
100, 127, 94
Tags (module), **101, 102, 103**,
used: 101, 101, 101, 102,
102, 103, 103, 103, 103,
103, 109, 110, 114, 114
Tags (sig), **98, 94**, used: 98, 102,
94
tail_opt, **208**, used: 208
Tan, **168**, used:
Tana, **436**, used:
Tanb, **436**, used:
Target (module), **180**, used: 670,
669, 563, 563, 563
Targets (module), **563, 563**,
used: 675, ??, 675, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, 681
Targets_Kmatrix (module), **640**,
640, used: 618
Tau, **231**, used: 231, 231, 232,
232
Tbar, **233**, used: 233, 234, 234,
235
TBWA, **239, 414**, used: 239,
243, 247, 414, 419, 422
TBWZ, **239, 414**, used: 239,
244, 247, 414, 420, 422
Template (module), **371, 270**,
used: ??
tension (field), **768, 771, 764**,
used: 771, 771
tension_to_equation, **774**, used:
774

- tensors_1* (field), **573**, used: **573**,
574, **580**
tensors_2 (field), **573**, used: **573**,
574, **580**
Tensor_1, **137**, used: **239**, **256**,
414
Tensor_2, **137**, used: **331**, **342**,
414
Tensor_2_Vector_Vector, **140**,
used: **190**
Tensor_2_Vector_Vector_1,
140, used: **417**, **418**
Term (module), **784**, **781**, used:
Term (sig), **783**, **780**, used: **784**,
785, **781**, **781**
Ternary (module), **12**, **27**, **8**, **20**,
used: **15**, **27**, **20**
Ternary (sig), **12**, **8**, used: **8**
test (type), **??**, **??**, used: **??**, **723**,
757, **??**, **??**, **??**, **??**, **??**,
??, **??**, **??**, **??**, **??**, **??**,
723, **755**
Test (module), **723**, **757**, **723**,
755, used:
TestCase, **??**, **??**, used: **??**, **??**,
??
TestLabel, **??**, **??**, used: **??**, **??**,
??
TestList, **??**, **??**, used: **??**, **??**, **??**
test_case_count, **??**, **??**, used:
??, **??**, **??**
test_case_paths, **??**, **??**, used: **??**
test_decorate, **??**, **??**, used: **??**
test_event (type), **??**, **??**, used:
??
test_filter, **??**, **??**, used: **??**
test_fun (type), **??**, **??**, used: **??**,
??, **??**, **??**
test_result (type), **??**, **??**, used:
??, **??**, **??**, **??**, **??**
test_rhs, **114**, used: **114**
test_sum, **61**, **65**, used: **61**, **66**
tex_lbl, **768**, used: **769**, **769**, **769**
tgc, **239**, **261**, **279**, **336**, **348**,
366, **376**, **405**, **414**, **??**,
??, used: **239**, **262**, **281**,
281, **336**, **348**, **366**, **376**,
405, **414**, **??**, **??**
THDM (module), **396**, **270**,
used: **??**
THDM_CKM (module), **396**,
270, used: **??**
THDM_flags (sig), **396**, **270**,
used: **396**, **396**, **396**, **270**
ThoArray (module), **706**, **706**,
used:
ThoFilename (module), **693**,
693, used: **695**
ThoList (module), **700**, **698**,
used: **755**, **755**, **756**, **758**,
758, **758**, **758**, **759**, **787**,
788, **735**, **749**, **751**, **752**,
752, **752**, **753**, **753**, **765**,
766, **771**, **771**, **772**, **772**,
16, **17**, **17**, **17**, **17**, **25**, **27**,
34, **35**, **61**, **87**, **222**, **226**,
663, **560**, **75**, **206**, **206**,
206, **207**, **209**, **209**, **215**,
216, **216**, **218**, **219**, **219**,
219, **110**, **118**, **118**, **121**,
122, **122**, **122**, **124**, **125**,
125, **132**, **133**, **133**, **134**,
135, **135**, **670**, **671**, **672**,
228, **229**, **231**, **233**, **239**,
244, **245**, **245**, **246**, **246**,
246, **256**, **256**, **261**, **261**,
262, **267**, **267**, **267**, **269**,
433, **433**, **443**, **443**, **444**,
444, **445**, **446**, **446**, **448**,
450, **451**, **451**, **452**, **454**,
455, **455**, **456**, **456**, **457**,
459, **459**, **460**, **460**, **462**,
462, **464**, **483**, **483**, **492**,
494, **495**, **496**, **496**, **496**,
497, **497**, **498**, **498**, **499**,
514, **514**, **523**, **524**, **525**,
525, **525**, **525**, **525**, **526**,
526, **526**, **527**, **527**, **527**,
528, **529**, **530**, **530**, **530**,
531, **531**, **532**, **533**, **534**,
273, **273**, **289**, **296**, **296**,
310, **317**, **317**, **321**, **323**,
325, **331**, **331**, **337**, **342**,
342, **350**, **361**, **361**, **367**,
372, **372**, **377**, **384**, **397**,
397, **407**, **414**, **421**, **421**,
421, **422**, **573**, **573**, **573**,
575, **575**, **577**, **580**, **580**,
612, **614**, **616**, **617**, **??**, **??**,
??, **??**, **??**, **??**, **??**, **??**, **??**,

- 676, 676
ThoString (module), **709, 709**,
 used: **685, 672**
thread, **735, 734**, used:
thread_unfinished_decays, **658**,
 used: **659**
thread_unfinished_decays', **658**,
 used: **658, 658, 659**
three, **29**, used: **30, 30, 31, 32, 32**
Threshl (module), **382, 271**,
 used: **??, ??**
Threshl_ckm (module), **381**,
271, used:
Threshl_ckm_no_hf (module),
382, 271, used:
Threshl_diet (module), **382**,
271, used:
Threshl_diet_no_hf (module),
382, 271, used:
Threshl_no_ckm (module), **381**,
271, used: **??**
Threshl_no_ckm_no_hf (module),
381, 271, used: **??**
Threshl_options (sig), **381, 271**,
 used: **381, 381, 381, 382**,
382, 382, 382, 271
three_gluon, **235, 678**, used: **235**,
678
Thw, **435**, used:
Th_SF, **435**, used:
time, **724, 757, 757, 759, 755**,
 used: **757, 757, 691, 692**,
692, 692, 692
timelike, **55, 60, 60, 65, 65, 53**,
54, used: **60, 61, 65, 65**,
661, 664, 109, 118, 125,
125
Timelike, **139**, used: **228, 229**,
231, 234, 239, 255, 431,
481, 511, 272, 295, 317,
330, 341, 360, 371, 382,
397, 414, ??, ??, 677
timelike_map, **661**, used: **661**,
662
time_fun, **??**, used: **??**
time_to_string, **691**, used: **692**,
692
tlm, **700, 698**, used: **700**
TLR, **140**, used: **243, 244, 419**,
420
TLRM, **140**, used: **243, 419**
todo, **??, ??**, used:
Todo (exn), **??**, used:
token, **??, ??, ??, ??**, used: **??**,
558, ??, ??, 76, 71, 551
token (type), **??, ??, ??, ??**,
 used: **??, ??, ??, ??**
token (camllex parsing rule), **71**,
551, used:
TopH, **273**, used: **273, 275, 279**,
281, 281, 288, 289
TopHb, **273**, used: **273, 275, 279**,
281, 281, 288, 289
Topology (module), **21, 19**, used:
100, 127, 129, 129, 129,
129
Topp, **295**, used: **296, 297, 301**,
302, 302, 310, 310
Toppb, **295**, used: **296, 297, 301**,
302, 302, 310, 310
top_anom, **237, 237, 237, 238**,
238, 238, 238, 238, 413,
413, 227, 271, used: **242**,
242, 242, 242, 243, 243,
243, 243, 243, 244, 244,
244, 418, 418, 418, 418,
419, 419, 419, 419, 419,
420, 420, 420
top_anom_4f, **237, 237, 237**,
238, 238, 238, 238, 238,
413, 413, 227, 271, used:
244, 245, 245, 245, 246,
246, 421, 421, 421, 421
top_quartic, **288, 310, 324**, used:
289, 310
tower_of_dag, **111**, used:
tower_to_dot, **95, 126, 92**, used:
674
to_feynmf, **770, 765**, used:
to_feynmf_channel, **770**, used:
770
to_float, **782, 783, 779**, used:
to_gauss, **79**, used: **80**
to_int, **28, 29, 20**, used: **34**
to_ints, **55, 56, 63, 52**, used: **63**,
67, 659, 663, 76, 79, 103,
126
to_ints', **63**, used: **63, 63**
to_list, **9, 11, 13, 15, 17, 85, 7**,
 used: **704, 755, 755, 756**

- 756, 757, 773, 774, 85, 85,
85, 104, 106, 109, 109,
110, 110, 121, 124, 125,
672, 618
- to_lists*, 742, 743, 84, 85, 741,
81, used: 79, 218, 602,
603
- to_momentum*, 67, 67, 67, 54,
used: 67
- to_on_shell*, 78, used: 80
- to_ratio*, 782, 783, 779, used:
- to_selectors*, 74, 80, 73, used:
673
- to_select_p*, 77, used: 80
- to_select_wf*, 77, used: 80
- to_string*, 742, 742, 742, 776,
782, 783, 783, 783, 784,
785, 787, 788, 768, 28,
29, 55, 56, 63, 659, 82,
83, 84, 86, 86, 70, 74,
76, 79, 217, 218, 99, 99,
741, 742, 776, 779, 780,
781, 781, 764, 20, 53,
69, 73, used: ??, ??, 742,
695, 776, 787, 788, 84, 76,
80, 217, 100, 673, 674
- to_string1*, 659, used: 659, 659
- translate_constant*, 560, used:
560
- translate_tensor3*, 560, used: 560
- translate_tensor4*, 560, used: 560
- transpose*, 702, 707, 699, used:
707, 708
- tree* (type), 661, used: 661
- Tree* (module), 713, 765, 713,
763, used: 707, 772, 41,
48, 95, 125, 669, 674, 675,
39, 92, 669
- Tree2* (module), 776, 776, used:
41, 47, 95, 102, 102, 105,
133, 39, 90
- trees*, 660, 662, 660, used: 674
- trees* (field), 661, used: 662, 663
- Trie*, 728, 731, used: 728, 728,
729, 729, 729, 731, 731,
731, 732, 732
- Trie* (module), 727, 725, used:
- triples*, 761, 482, 512, 760,
used: 13, 15, 497, 531
- triplet_gauge2_higgs*, 284, 305,
used: 285, 306
- triplet_gauge_higgs*, 283, 305,
used: 285, 306
- triple_anom*, 237, 237, 237,
238, 238, 238, 238, 238,
413, 413, 227, 271,
used: 239, 414
- triple_gauge*, 239, 262, 448,
493, 527, 282, 303, 323,
336, 349, 366, 376, 405,
414, ??, ??, used: 246,
262, 462, 498, 533, 289,
310, 325, 337, 350, 367,
377, 407, 422, ??, ??
- triple_gravitino*, 448, used: 463
- triple_gravitino'*, 447, used: 448
- triple_gravitino''*, 447, used: 448
- TRL*, 140, used: 243, 244, 419,
420
- TRLM*, 140, used: 243, 419
- True*, 70, 75, 69, used: 70, 70,
76, 76
- try_add*, 55, 58, 64, 52, used:
61, 65
- try_add'*, 57, used: 57, 58
- try_first*, 696, used: 696
- try_fusion*, 55, 61, 66, 53, used:
658
- try_of_momenta*, 659, used:
- try_sub*, 55, 58, 64, 52, used:
61, 64, 65, 659
- try_sub'*, 58, used: 58, 58
- try_thread_unfinished_decays*,
659, used: 659
- TS* (module), 685, used: 685,
685, 685, 685, 685
- TTGG*, 239, 414, used: 239,
243, 247, 414, 419, 422
- TTWW*, 239, 414, used: 239,
244, 247, 414, 420, 422
- Tuple* (module), 9, 25, 34, 6,
used: 23, 24, 25, 25, 27,
27, 27, 34, 34, 34, 35, 35,
43, 98, 98, 99, 99, 100,
103, 127, 129, 129, 129,
129, 20, 21, 21, 37, 92, 92,
94
- tuples*, 761, 760, used: 761, 761,
17, 25, 34

- tuples'*, **761**, used: 761, 761
tuple_of_list2, **24**, used: 25
TVA, **140**, used: 243, 244, 244, 419, 420, 420
TVAM, **140**, used: 242, 242, 242, 242, 243, 418, 418, 418, 418, 419
twice_spin, **598**, used:
two, **29**, used: 30, 31, 31, 31, 32, 32, 32, 33
TwoHiggsDoublet (module), **396**, **270**, used: ??, ??
two_adjoints_couple_to_singlets, **207**, used: 207
two_and_one, **482**, **512**, used: 491, 497, 523, 531
two_and_one', **482**, **512**, used: 482, 482, 512, 512
t_channel (field), **658**, used: 658, 658, 658, 659
U, **233**, **239**, **255**, **432**, **483**, **514**, **273**, **295**, **317**, **331**, **341**, **360**, **372**, **397**, **414**, ??, ??, used: 233, 234, 234, 235, 239, 242, 242, 242, 243, 243, 243, 243, 244, 244, 244, 244, 245, 245, 245, 245, 246, 246, 246, 246, 247, 256, 257, 259, 260, 261, 261, 261, 261, 262, 433, 435, 439, 440, 441, 441, 442, 443, 443, 443, 445, 446, 447, 447, 461, 465, 483, 485, 488, 488, 489, 490, 490, 491, 492, 492, 493, 499, 514, 516, 519, 520, 520, 522, 522, 523, 523, 524, 524, 524, 524, 525, 525, 534, 273, 275, 279, 279, 279, 279, 281, 280, 280, 280, 281, 281, 288, 289, 296, 297, 300, 300, 300, 301, 301, 301, 302, 302, 302, 302, 310, 310, 317, 318, 321, 321, 321, 321, 322, 322, 323, 323, 325, 331, 333, 335, 335, 335, 335, 336, 338, 342, 344, 348, 348, 348, 348, 350, 361, 362, 365, 365, 365, 365, 367, 372, 373, 376, 376, 376, 376, 376, 378, 397, 399, 402, 402, 402, 403, 403, 403, 403, 404, 407, 414, 418, 418, 418, 419, 419, 419, 419, 420, 420, 420, 420, 421, 421, 421, 421, 422, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??
u1_gauged, **272**, **272**, **272**, **272**, **270**, used: 273, 279, 279, 280, 281, 281, 282, 283, 283, 284, 285, 289, 296, 301, 301, 302, 302, 303, 303, 304, 305, 305, 306, 310
Ubar, **233**, used: 233, 234, 234, 235
UED (module), **341**, **270**, used: ??
Unbounded_Nary (module), **18**, **8**, used:
unbounded_power, **17**, used: 17
unbounded_power_fold, **17**, used: 17
uncolorize_wf, **119**, used: 122
uncompress, **707**, **706**, used: 708
uncompress2, **708**, **706**, used:
uncons, **713**, **716**, **721**, **712**, used:
uncons_opt, **713**, **716**, **721**, **712**, used:
uncross_colored, **209**, used: 209
unfinished_decays (type), **658**, used:
unfinished_decays_of_momenta, **658**, used: 659, 659
unfold, **663**, used: 663
unfold1, **662**, used: 663
unfold_tree, **663**, used: 663
Uninitialized (exn), **225**, used:
union, **713**, **718**, **722**, **742**, **742**, **712**, **741**, used: 718, 722, 704, 742, 744, 744, 79, 218, 218, 580

- uniq*, **702, 706, 698, 706**, used:
787, 788, 135, 672
- uniq* (field), **706**, used: 706, 707,
707, 708
- uniq'*, **702**, used: 702, 702
- uniq2*, **707, 706**, used:
- uniq2* (field), **706**, used: 707,
707, 708
- unique_final_state*, **214**, used:
- unique_flavors*, **214**, used: 214
- unit*, **782, 783, 783, 783, 784,**
785, 779, 780, 780,
used:
- Unit*, **239, 259, 436, 277, 298,**
319, 334, 347, 364, 375,
400, 414, ??, ??, used:
??, 561, 101, 130, 670,
671, 239, 244, 255, 431,
481, 511, 272, 295, 317,
330, 341, 360, 371, 382,
397, 414, 420, 570, ??, ??
- Unitarity_Gauge* (sig), **179**,
used:
- uninitialized*, **225**, used: 225
- unit_tension*, **771**, used:
- Unordered* (exn), **654, 656, 653**,
used:
- unpack_map*, **662**, used: 663
- unphysical_of_flavor*, **132**, used:
132
- unphysical_of_flavors*, **132**, used:
133
- unphysical_of_flavors1*, **132**,
used: 132
- unphysical_of_lorentz*, **132**,
used: 132
- unphysical_polarization*, **671**,
used: 671, 673
- unquote*, **??, 71**, used: ??, 71
- Uodd*, **295**, used: 296, 296
- update*, **713, 717, 720, 712**,
used: 717, 717, 718, 720,
720
- upper* (camllex regexp), **71, 551**,
used: 71, 551
- used_module* (type), **614**, used:
615
- used_modules*, **617**, used: 620,
621, 621, 621, 622, 622,
623
- used_modules* (field), **615**, used:
615, 620, 621, 621, 621,
622, 622, 623
- used_symbol* (type), **614**, used:
614
- user_cache_dir*, **687, 687**, used:
695
- use_channel*, **691**, used: 692,
692, 692
- use_fudged_width*, **239, 255,**
431, 481, 511, 272, 295,
317, 330, 341, 360, 371,
397, 414, ??, ??, used:
239, 239, 255, 257, 431,
434, 481, 484, 511, 516,
272, 275, 295, 297, 317,
318, 330, 332, 341, 344,
360, 362, 371, 373, 397,
398, 414, 414, ??, ??, ??,
??
- use_module*, **564, 569, 638**,
used: 617
- use_modules*, **570**, used: 570, 617
- Using_Arrays* (module), **756**,
754, used: 757
- Using_Lists* (module), **755, 754**,
used:
- U_K1_L*, **341**, used: 342, 344,
350
- U_K1_R*, **341**, used: 342, 344,
350
- U_K2_L*, **341**, used: 342, 344,
350
- U_K2_R*, **341**, used: 342, 344,
350
- v* (field), **30**, used: 30, 31, 31, 31
- V*, **140**, used: 232, 234, 239, 244,
260, 261, 440, 440, 442,
447, 448, 488, 488, 490,
493, 519, 520, 521, 524,
527, 527, 527, 279, 279,
279, 300, 300, 301, 321,
321, 322, 335, 335, 348,
348, 365, 367, 376, 376,
389, 389, 390, 402, 402,
414, 420, ??, ??, ??, ??,
678
- V2*, **140**, used: 462
- V2LR*, **140**, used: 462, 462

- v3* (field), **222**, used: **222**, **223**,
224
- V3*, **142**, used: **223**, **192**, **193**, **230**
- v4* (field), **222**, used: **222**, **223**,
224
- V4*, **142**, used: **224**, **192**, **193**, **230**
- VA*, **140**, used: **239**, **261**, **441**,
442, **442**, **488**, **490**, **520**,
521, **521**, **279**, **279**, **279**,
280, **300**, **301**, **301**, **302**,
321, **335**, **348**, **365**, **376**,
402, **414**, **??**, **??**, **??**
- VA2*, **140**, used: **389**, **389**, **390**,
390, **390**
- value* (field), **695**, used:
- value* (type), **695**, **695**, **694**,
used: **695**, **695**, **694**, **694**
- Value* (sig), **695**, **694**, used: **695**,
694
- vanilla*, **771**, **764**, used: **771**
- Vanishing*, **139**, used: **239**, **255**,
431, **481**, **511**, **272**, **295**,
317, **330**, **341**, **360**, **371**,
382, **397**, **414**, **??**, **??**
- vanishing_flavors*, **129**, **131**, **93**,
used: **612**
- vanishing_flavors* (field), **130**,
used: **131**, **136**
- variable*, **126**, **670**, **572**, used:
126, **674**, **572**, **572**, **573**,
595, **599**
- variable* (type), **173**, used: **173**
- variable'*, **670**, used:
- variables*, **95**, **102**, **105**, **123**, **91**,
used: **580**
- variables_file*, **561**, used: **561**,
561
- variable_array* (type), **173**, used:
173
- VBS* (module), **414**, **271**, used:
??
- VBS_flags* (sig), **413**, **271**, used:
413, **414**, **271**, **271**
- VBS_kmatrix* (module), **413**,
271, used: **??**
- vc* (type), **436**, **486**, **517**, used:
436, **486**, **517**
- VCache* (module), **106**, used:
107, **107**, **107**
- vector* (type), **551**, used:
- Vector*, **137**, used: **559**, **231**, **233**,
239, **256**, **256**, **433**, **484**,
515, **274**, **296**, **317**, **331**,
342, **361**, **372**, **386**, **398**,
414, **??**, **??**, **677**
- Vector4*, **141**, used: **191**, **193**,
235, **239**, **262**, **448**, **493**,
527, **282**, **303**, **323**, **336**,
349, **366**, **377**, **391**, **405**,
414, **??**, **??**, **678**
- Vector4_K_Matrix_jr*, **141**,
used: **191**, **193**, **239**, **414**
- Vector4_K_Matrix_tho*, **141**,
used: **191**
- vectors* (field), **573**, used: **573**,
574, **580**
- Vectorspinor*, **137**, used: **433**, **361**
- vectorspinors* (field), **573**, used:
573, **574**, **580**
- vector_keyword*, **551**, used:
- Vector_Scalar_Scalar*, **140**, used:
190, **440**, **441**, **441**, **442**,
447, **449**, **449**, **488**, **489**,
489, **490**, **493**, **493**, **519**,
520, **521**, **521**, **527**, **527**,
527, **527**, **528**, **284**, **305**,
324, **405**, **678**
- version*, **670**, used: **671**
- vertex3* (type), **140**, used: **221**,
106, **142**, **176**, **178**, **220**
- vertex4* (type), **141**, used: **221**,
106, **142**, **176**, **178**, **220**
- vertexn* (type), **142**, used: **221**,
106, **142**, **176**, **178**, **220**
- vertex_table* (type), **106**, used:
106
- vertices*, **225**, **556**, **193**, **209**,
107, **229**, **230**, **232**, **235**,
247, **255**, **262**, **269**, **464**,
499, **534**, **289**, **310**, **325**,
337, **350**, **367**, **377**, **392**,
407, **422**, **??**, **??**, **679**,
176, used: **556**, **207**, **209**,
107, **118**, **123**, **229**, **232**,
235, **247**, **255**, **255**, **262**,
269, **269**, **464**, **499**, **534**,
289, **310**, **325**, **337**, **350**,
367, **377**, **392**, **407**, **422**,
??, **??**, **679**
- vertices* (label), **226**, **178**, used:

vertices (type), **106**, used: **106**,
106, **107**
vertices3, **235**, **246**, **262**, **463**,
498, **533**, **289**, **310**, **325**,
337, **350**, **367**, **377**, **407**,
422, **??**, **??**, **678**, used:
235, **247**, **262**, **464**, **499**,
534, **289**, **310**, **325**, **337**,
350, **367**, **377**, **407**, **422**,
??, **??**, **679**
vertices3', **463**, used: **463**
vertices3'', **462**, used: **463**
vertices4, **235**, **247**, **262**, **464**,
499, **534**, **289**, **310**, **325**,
337, **350**, **367**, **377**, **407**,
422, **??**, **??**, **679**, used:
235, **247**, **262**, **464**, **499**,
534, **289**, **310**, **325**, **337**,
350, **367**, **377**, **407**, **422**,
??, **??**, **679**
vertices4', **464**, used: **464**
vertices4'', **464**, used: **464**
vertices4''', **464**, used: **464**
vertices_aaww, **391**, used: **392**
vertices_all, **389**, used: **392**
vertices_aqq, **389**, used: **392**
vertices_aww, **391**, used: **392**
vertices_cache, **107**, used: **107**
vertices_ggg, **391**, used: **392**
vertices_gggg, **392**, used: **392**
vertices_gqq, **390**, used: **392**
vertices_nocache, **106**, used: **107**,
107
vertices_wll, **389**, used: **389**, **392**
vertices_wll_diet, **389**, used: **392**
vertices_wqq, **390**, used: **392**
vertices_wqq_no_ckm, **389**, used:
390, **392**
vertices_wqq_no_ckm_diet, **390**,
used: **392**
vertices_www, **391**, used: **392**
vertices_wwza, **391**, used: **392**
vertices_wwzz, **391**, used: **392**
vertices_zll, **390**, used: **392**
vertices_zqq, **390**, used: **392**
vertices_zww, **391**, used: **392**
Vev, **239**, **259**, **436**, **277**, **298**,
319, **334**, **347**, **364**, **375**,
400, **414**, **??**, **??**, used:
239, **260**, **414**
VHeavy, **277**, **298**, **319**, used:
VL, **140**, used: **239**, **245**, **245**,
245, **261**, **261**, **261**, **441**,
441, **489**, **489**, **520**, **520**,
279, **279**, **280**, **280**, **301**,
301, **301**, **302**, **321**, **322**,
335, **348**, **365**, **376**, **403**,
414, **421**, **421**, **421**, **??**, **??**
VLR, **140**, used: **244**, **245**, **245**,
441, **448**, **489**, **490**, **520**,
322, **420**, **421**, **421**
VLRM, **140**, used: **242**, **243**, **418**,
419
VM (module), **638**, **563**, used:
VMOM, **140**, used:
vn (field), **222**, used: **222**, **223**,
224
Vn, **142**, used: **192**, **193**
VR, **140**, used: **279**, **301**
VSet (module), **106**, used: **106**,
106
V_0, **436**, used:
V_CKM, **436**, used:
V_P, **436**, used:
w, **384**, used: **384**
W, **436**, **384**, used: **384**, **386**,
389, **389**, **390**, **391**, **391**,
391, **391**, **391**, **391**, **393**
W (module), **670**, used: **674**
ward_vectors (field), **573**, used:
574, **580**
warn, **579**, used: **595**, **598**
Warn, **579**, used: **579**
was_successful, **??**, used: **??**, **??**,
??
wavefunctions, **102**, **105**, used:
119, **122**
wf (type), **95**, **98**, **98**, **99**, **100**,
102, **103**, **123**, **129**, **130**,
89, **92**, **94**, used: **95**, **98**,
102, **102**, **102**, **102**, **102**,
102, **102**, **102**, **102**, **103**,
104, **104**, **104**, **105**, **105**,
105, **110**, **111**, **112**, **112**,
112, **113**, **113**, **114**, **120**,
121, **123**, **125**, **129**, **130**,
130, **130**, **133**, **572**, **573**,
89, **89**, **89**, **90**, **90**, **90**, **90**,
91, **91**, **92**, **93**, **93**, **94**, **94**

- WfMap* (module), **114, 133**,
 used: **114, 119, 119, 133**
WfMap2 (module), **133**, used:
133
WfSet (module), **105, 125, 572**,
 used: **105, 125, 125, 580**,
599, 618
WfSet2 (module), **133**, used:
134, 134
WfTSet (module), **133**, used:
133
wf_of_f, **631**, used: **632, 632**,
632, 633, 633, 634, 634,
634, 635, 635, 636,
636, 636
wf_tag, **95, 102, 103, 123, 89**,
 used: **123, 572**
wf_tag (field), **102, 103**, used:
103, 103, 104, 109, 110,
114, 119, 119, 120, 124
wf_tag_raw, **102, 103**, used: **110**
wf_to_string, **98, 98, 99, 100**,
94, used: **103**
white (camllex regexp), **71**,
 used: **71**
White, **186**, used: **187, 188, 189**,
194, 194, 194, 194, 197,
197, 198, 198, 198, 198,
205, 208
whizard, **570**, used: **570, 608, 617**
Whizard (module), **660, 660**,
 used: **670**
Whizard (sig), **67, 54**, used: **661**,
54, 660
whizard_public_symbols, **617**,
 used: **617**
whizard_tree, **663**, used:
whizard_tree_debug, **663**, used:
WHm, **273, 295**, used: **273, 275**,
279, 280, 281, 282, 283,
283, 284, 285, 289, 296,
297, 301, 301, 303, 303,
304, 305, 305, 306, 310
WHp, **273, 295**, used: **273, 275**,
279, 280, 281, 282, 283,
283, 284, 285, 289, 296,
297, 301, 301, 303, 303,
304, 305, 305, 306, 310
width, **225, 556, 187, 209, 228**,
229, 231, 234, 239, 254,
257, 266, 434, 484, 516,
275, 297, 318, 332, 344,
362, 373, 386, 398, 414,
??, ??, 677, 176, used:
556, 187, 209, 254, 266,
593, 599
width (label), **226, 178**, used:
560
width (type), **139**, used: **176, 178**
Width, **239, 259, 277, 298, 319**,
334, 347, 364, 375, 400,
414, ??, ??, used:
width_symbol, **225, 556, 190**,
209, 229, 230, 233, 236,
252, 255, 265, 266, 472,
507, 545, 292, 314, 329,
340, 359, 371, 380, 395,
410, 427, ??, ??, 681,
177, used: **556, 190, 209**,
255, 266, 595, 599
width_symbol (label), **226, 178**,
 used: **560**
with_infinity, **768**, used: **768**
with_supremum (type), **767**,
 used:
with_supremum_or_infinity (type),
768, used:
Wm, **239, 255, 432, 483, 514**,
273, 295, 317, 331, 341,
360, 372, 397, 414, ??,
??, used: **239, 239, 239**,
241, 242, 243, 243, 244,
244, 244, 247, 256, 257,
261, 261, 261, 262, 433,
435, 441, 441, 441, 441,
441, 448, 448, 448, 449,
449, 449, 450, 450, 451,
451, 461, 461, 462, 462,
465, 483, 485, 489, 489,
489, 489, 489, 493, 493,
493, 494, 494, 494, 494,
495, 495, 495, 495, 495,
496, 496, 496, 499, 514,
516, 520, 520, 520, 520,
521, 527, 527, 528, 529,
529, 529, 529, 529, 529,
529, 529, 530, 530, 530,
530, 534, 273, 275, 279,
280, 281, 281, 282, 282,
283, 283, 283, 284, 285,

- 285, 289, 289, 296, 297,
301, 301, 302, 303, 303,
303, 303, 304, 304, 305,
305, 306, 306, 310, 310,
317, 318, 321, 322, 323,
323, 323, 324, 324, 324,
325, 325, 331, 333, 335,
336, 336, 336, 336, 336,
337, 338, 342, 344, 348,
348, 349, 349, 349, 349,
350, 350, 361, 362, 365,
366, 366, 366, 366, 367,
367, 372, 373, 376, 376,
377, 377, 377, 377, 378,
397, 399, 403, 405, 405,
405, 406, 407, 407, 414,
414, 414, 415, 416, 417,
417, 417, 417, 418, 419,
419, 420, 420, 420, 422,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??
- Wm1*, **341**, used: 342, 344, 348,
350
- Wm2*, **341**, used: 342, 344, 350
- Wp*, **239, 255, 432, 483, 514,**
273, 295, 317, 331, 341,
360, 372, 397, 414, ??,
??, used: 239, 239, 239,
241, 242, 243, 243, 244,
244, 244, 247, 256, 257,
260, 261, 261, 261, 262,
433, 435, 441, 441, 441,
441, 441, 448, 448, 448,
449, 449, 449, 450, 450,
451, 451, 461, 461, 462,
462, 465, 483, 485, 489,
489, 489, 489, 489, 493,
493, 493, 494, 494, 494,
494, 495, 495, 495, 495,
495, 496, 496, 496, 499,
514, 516, 520, 520, 520,
520, 521, 527, 527, 528,
529, 529, 529, 529, 529,
529, 529, 529, 530, 530,
530, 530, 534, 273, 275,
279, 280, 281, 281, 282,
282, 283, 283, 283, 284,
285, 285, 289, 289, 296,
297, 301, 301, 302, 303,
303, 303, 303, 304, 304,
305, 305, 306, 306, 310,
310, 317, 318, 321, 322,
323, 323, 323, 324, 324,
324, 325, 325, 331, 333,
335, 336, 336, 336, 336,
336, 337, 338, 342, 344,
348, 348, 349, 349, 349,
349, 350, 350, 361, 362,
365, 366, 366, 366, 366,
367, 367, 372, 373, 376,
376, 377, 377, 377, 377,
378, 397, 399, 403, 405,
405, 405, 406, 407, 407,
414, 414, 414, 415, 416,
417, 417, 417, 417, 418,
419, 419, 420, 420, 420,
422, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??, ??,
??, ??, ??, ??, ??, ??
- Wp1*, **341**, used: 342, 344, 348,
350
- Wp2*, **341**, used: 342, 344, 348,
350
- write*, **695, 696, 660, 664, 694,**
660, used: ??, 107
- write_dir*, **695, 696, 694**, used:
107
- write_interface*, **666, 660**, used:
write_interface_function, **666**,
used: 666
- write_interface_subroutine*, **665**,
used: 666
- write_makefile*, **667, 660**, used:
write_makefile_processes, **668**,
660, used:
- write_other_declarations*, **666**,
used: 666
- write_other_interface_functions*,
666, used: 666
- X0*, **317**, used: 317, 318, 321,
323, 324, 324, 325
- Xdim* (module), **330, 270**, used:
??
- XiA*, **254**, used: 254
- XiW*, **254**, used: 254
- XiZ*, **254**, used: 254
- Xm*, **317**, used: 317, 318, 321,
323, 324, 324, 325

- Xp*, **317**, used: 317, 318, 321, 323, 324, 324, 325
xy-currents, **321**, used: 325
Y0, **317**, used: 317, 318, 321, 323, 325
yukawa, **239, 261, 280, 302, 323, 336, 348, 365, 376, 403, 414, ??, ??**, used: 246, 262, 289, 310, 325, 337, 350, 367, 377, 407, 422, ??, ??
yukawa-add, **281, 302, 323**, used: 289, 310, 325
yukawa-add', **281, 302**, used: 281, 302
yukawa-c, **446, 492, 523**, used: 462, 498, 533
yukawa-cq, **446, 492, 524**, used: 462, 498, 533
yukawa-cq', **446, 492, 524**, used: 446, 492, 524
yukawa-cq'', **446**, used: 446
yukawa-c-1, **446**, used: 446
yukawa-c-2, **446, 492, 523**, used: 446, 492, 523
yukawa-c-3, **446, 492, 523**, used: 446, 492, 523
yukawa-goldstone, **443**, used: 463
yukawa-goldstone-2, **443**, used: 463
yukawa-goldstone-2', **443**, used: 443
yukawa-goldstone-2'', **443**, used: 443
yukawa-goldstone-quark, **443**, used: 463
yukawa-higgs, **442, 490, 522**, used: 462, 498, 533
yukawa-higgs-2, **443, 491, 522**, used: 462, 498, 533
yukawa-higgs-2', **443**, used: 443
yukawa-higgs-2'', **443**, used: 443
yukawa-higgs-FFP, **490, 521**, used: 490, 522
yukawa-higgs-FFS, **490, 521**, used: 490, 522
yukawa-higgs-NLC, **490, 522**, used: 490, 522
yukawa-higgs-quark, **443, 490, 522**, used: 462, 498, 533
yukawa-n, **445, 492, 523**, used: 462, 498, 533
yukawa-n-1, **445**, used: 445
yukawa-n-2, **445, 491, 523**, used: 445, 492, 523
yukawa-n-3, **445, 491, 523**, used: 445, 492, 523
yukawa-n-4, **445**, used: 445
yukawa-n-5, **445, 492, 523**, used: 445, 492, 523
yukawa-phiggs-2, **491, 522**, used: 491, 522
yukawa-shiggs-2, **491, 522**, used: 491, 522
yukawa-v, **442, 490, 521**, used: 462, 498, 533
yuk-lqino-ec-su1, **525**, used: 533
yuk-lqino-ec-su1', **525**, used: 525
yuk-lqino-ec-su2, **525**, used: 533
yuk-lqino-ec-su2', **525**, used: 525
yuk-lqino-nc-sd1, **525**, used: 533
yuk-lqino-nc-sd2, **525**, used: 533
yuk-lqino-phiggs, **526**, used: 533
yuk-lqino-se-uc1, **524**, used: 533
yuk-lqino-se-uc1', **524**, used: 524
yuk-lqino-se-uc2, **525**, used: 533
yuk-lqino-se-uc2', **524**, used: 525
yuk-lqino-shiggs, **526**, used: 533
yuk-lqino-sn-dc1, **525**, used: 533
yuk-lqino-sn-dc2, **525**, used: 533
yuk-lq-ec-uc, **525**, used: 533
yuk-lq-ec-uc', **525**, used: 525
yuk-lq-ec-uc2, **525**, used: 533
yuk-lq-ec-uc2', **525**, used: 525
yuk-lq-nc-dc, **525**, used: 533
yuk-lq-nc-dc2, **525**, used: 533

- yyact*, ??, ??, used: ??, ??
yycheck, ??, ??, used: ??, ??
yydefred, ??, ??, used: ??, ??
yydgoto, ??, ??, used: ??, ??
yygindex, ??, ??, used: ??, ??
yylen, ??, ??, used: ??, ??
yylhs, ??, ??, used: ??, ??
yynames_block, ??, ??, used: ??, ??
yynames_const, ??, ??, used: ??, ??
yyrindex, ??, ??, used: ??, ??
yyindex, ??, ??, used: ??, ??
yytable, ??, ??, used: ??, ??
yytables, ??, ??, used: ??, ??
yytablesize, ??, ??, used: ??, ??
yytransl_block, ??, ??, used: ??, ??
yytransl_const, ??, ??, used: ??, ??
z, **384**, used:
Z, **239, 255, 432, 483, 514, 273, 295, 317, 331, 341, 360, 372, 384, 397, 414, ??, ??, used: 239, 239, 239, 241, 241, 242, 242, 243, 244, 247, 256, 257, 259, 260, 261, 262, 433, 435, 441, 442, 442, 442, 448, 448, 448, 449, 449, 449, 450, 450, 451, 452, 461, 461, 462, 462, 465, 483, 485, 488, 490, 490, 490, 493, 493, 493, 494, 494, 494, 494, 494, 495, 495, 495, 496, 496, 496, 499, 514, 516, 520, 521, 521, 521, 527, 527, 527, 527, 527, 527, 527, 528, 528, 528, 528, 529, 529, 529, 530, 530, 530, 531, 534, 273, 275, 279, 279, 281, 281, 282, 282, 283, 283, 283, 284, 285, 285, 288, 289, 289, 296, 297, 300, 301, 303, 303, 303, 303, 304, 304, 305, 305, 306, 306, 309, 310, 310, 317, 318, 321, 321, 323, 323, 323, 324, 324, 324,**
324, 324, 324, 325, 325, 331, 333, 335, 336, 336, 336, 336, 336, 337, 337, 338, 342, 344, 348, 348, 349, 349, 349, 349, 349, 350, 350, 361, 362, 365, 366, 366, 366, 366, 366, 367, 367, 372, 373, 376, 376, 377, 377, 377, 377, 378, 384, 384, 390, 390, 391, 391, 391, 393, 397, 399, 402, 405, 405, 405, 406, 407, 407, 414, 414, 414, 415, 416, 416, 417, 417, 417, 417, 418, 418, 419, 420, 422, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??, ??
Z (module), **183, 182**, used:
Z1, **341**, used: **342, 344, 348, 350**
Z2, **341**, used: **342, 344, 348, 350**
zero, **28, 29, 55, 56, 63, 84, 85, 20, 52, 82**, used: **30, 30, 30, 31, 31, 31, 32, 32, 32, 33, 33, 34, 75, 135, 136**
Zero (exn), **31**, used:
ZH, **273, 295, 317, ??**, used: **273, 275, 279, 279, 281, 282, 283, 283, 284, 285, 289, 296, 297, 301, 301, 303, 303, 304, 305, 305, 306, 310, 317, 318, 322, 323, 324, 324, 324, 325, ??, ??, ??, ??**
Zprime (module), ??, used: ??
ZZ (module), **183, 183**, used: **231, 234, 227**
--ocaml_lex_tables, ??, ??, used: ??, ??
--ocaml_lex_token_rec, ??, ??, used: ??, ??, ??, ??